

The L^AT_EX3 Sources

The L^AT_EX3 Project*

September 29, 2012

Abstract

This is the reference documentation for the `expl3` programming environment. The `expl3` modules set up an experimental naming scheme for L^AT_EX commands, which allow the L^AT_EX programmer to systematically name functions and variables, and specify the argument types of functions.

The T_EX and ε -T_EX primitives are all given a new name according to these conventions. However, in the main direct use of the primitives is not required or encouraged: the `expl3` modules define an independent low-level L^AT_EX3 programming language.

At present, the `expl3` modules are designed to be loaded on top of L^AT_EX 2 ε . In time, a L^AT_EX3 format will be produced based on this code. This allows the code to be used in L^AT_EX 2 ε packages *now* while a stand-alone L^AT_EX3 is developed.

While `expl3` is still experimental, the bundle is now regarded as broadly stable. The syntax conventions and functions provided are now ready for wider use. There may still be changes to some functions, but these will be minor when compared to the scope of `expl3`.

New modules will be added to the distributed version of `expl3` as they reach maturity.

*E-mail: latex-team@latex-project.org

Contents

I	Introduction to <code>expl3</code> and this document	1
1	Naming functions and variables	1
1.1	Terminological inexactitude	3
2	Documentation conventions	3
3	Formal language conventions which apply generally	5
4	TeX concepts not supported by L ^A T _E X3	5
II	The <code>l3bootstrap</code> package: Bootstrap code	6
1	Using the L ^A T _E X3 modules	6
1.1	Internal functions and variables	7
III	The <code>l3names</code> package: Namespace for primitives	8
1	Setting up the L ^A T _E X3 programming language	8
IV	The <code>l3basics</code> package: Basic definitions	9
1	No operation functions	9
2	Grouping material	9
3	Control sequences and functions	10
3.1	Defining functions	10
3.2	Defining new functions using parameter text	10
3.3	Defining new functions using the signature	12
3.4	Copying control sequences	15
3.5	Deleting control sequences	15
3.6	Showing control sequences	16
3.7	Converting to and from control sequences	16
4	Using or removing tokens and arguments	17
4.1	Selecting tokens from delimited arguments	19

5	Predicates and conditionals	19
5.1	Tests on control sequences	20
5.2	Testing string equality	21
5.3	Engine-specific conditionals	22
5.4	Primitive conditionals	22
6	Internal kernel functions	23
V	The l3expan package: Argument expansion	26
1	Defining new variants	26
2	Methods for defining variants	27
3	Introducing the variants	27
4	Manipulating the first argument	28
5	Manipulating two arguments	29
6	Manipulating three arguments	30
7	Unbraced expansion	31
8	Preventing expansion	31
9	Internal functions and variables	33
VI	The l3prg package: Control structures	34
1	Defining a set of conditional functions	34
2	The boolean data type	36
3	Boolean expressions	38
4	Logical loops	39
5	Producing n copies	40
6	Detecting TeX's mode	40
7	Primitive conditionals	41
8	Internal programming functions	41

VII	The <code>l3quark</code> package: Quarks	43
1	Introduction to quarks and scan marks	43
1.1	Quarks	43
2	Defining quarks	44
3	Quark tests	44
4	Recursion	45
5	Clearing quarks away	46
6	An example of recursion with quarks	46
7	Internal quark functions	47
8	Scan marks	47
VIII	The <code>l3token</code> package: Token manipulation	48
1	All possible tokens	48
2	Character tokens	49
3	Generic tokens	52
4	Converting tokens	53
5	Token conditionals	53
6	Peeking ahead at the next token	57
7	Decomposing a macro definition	59
IX	The <code>l3int</code> package: Integers	61
1	Integer expressions	61
2	Creating and initialising integers	62
3	Setting and incrementing integers	63
4	Using integers	64
5	Integer expression conditionals	64

6	Integer expression loops	65
7	Integer step functions	67
8	Formatting integers	67
9	Converting from other formats to integers	69
10	Viewing integers	70
11	Constant integers	71
12	Scratch integers	71
13	Primitive conditionals	72
14	Internal functions	72
X	The <code>l3skip</code> package: Dimensions and skips	74
1	Creating and initialising <code>dim</code> variables	74
2	Setting <code>dim</code> variables	75
3	Utilities for dimension calculations	75
4	Dimension expression conditionals	76
5	Dimension expression loops	77
6	Using <code>dim</code> expressions and variables	78
7	Viewing <code>dim</code> variables	79
8	Constant dimensions	79
9	Scratch dimensions	79
10	Creating and initialising <code>skip</code> variables	80
11	Setting <code>skip</code> variables	80
12	Skip expression conditionals	81
13	Using <code>skip</code> expressions and variables	81
14	Viewing <code>skip</code> variables	82

15	Constant skips	82
16	Scratch skips	82
17	Inserting skips into the output	83
18	Creating and initialising <code>muskip</code> variables	83
19	Setting <code>muskip</code> variables	84
20	Using <code>muskip</code> expressions and variables	84
21	Viewing <code>muskip</code> variables	85
22	Constant muskips	85
23	Scratch muskips	85
24	Primitive conditional	85
25	Internal functions	86
 XI The <code>l3tl</code> package: Token lists		87
1	Creating and initialising token list variables	88
2	Adding data to token list variables	89
3	Modifying token list variables	89
4	Reassigning token list category codes	90
5	Reassigning token list character codes	90
6	Token list conditionals	91
7	Mapping to token lists	92
8	Using token lists	94
9	Working with the content of token lists	95
10	The first token from a token list	96
11	Viewing token lists	99
12	Constant token lists	99

13	Scratch token lists	99
14	Internal functions	100
XII The l3seq package: Sequences and stacks		101
1	Creating and initialising sequences	101
2	Appending data to sequences	102
3	Recovering items from sequences	102
4	Recovering values from sequences with branching	103
5	Modifying sequences	104
6	Sequence conditionals	105
7	Mapping to sequences	105
8	Sequences as stacks	107
9	Constant and scratch sequences	108
10	Viewing sequences	108
11	Internal sequence functions	108
XIII The l3clist package: Comma separated lists		110
1	Creating and initialising comma lists	110
2	Adding data to comma lists	111
3	Modifying comma lists	112
4	Comma list conditionals	112
5	Mapping to comma lists	113
6	Comma lists as stacks	115
7	Viewing comma lists	116
8	Constant and scratch comma lists	117

XIV	The <code> 3prop</code> package: Property lists	118
1	Creating and initialising property lists	118
2	Adding entries to property lists	119
3	Recovering values from property lists	119
4	Modifying property lists	120
5	Property list conditionals	120
6	Recovering values from property lists with branching	120
7	Mapping to property lists	121
8	Viewing property lists	122
9	Scratch property lists	123
10	Constants	123
11	Internal property list functions	123
XV	The <code> 3box</code> package: Boxes	124
1	Creating and initialising boxes	124
2	Using boxes	125
3	Measuring and setting box dimensions	125
4	Box conditionals	126
5	The last box inserted	127
6	Constant boxes	127
7	Scratch boxes	127
8	Viewing box contents	127
9	Horizontal mode boxes	128
10	Vertical mode boxes	129
11	Primitive box conditionals	131

XVI	The <code>l3coffins</code> package: Coffin code layer	132
1	Creating and initialising coffins	132
2	Setting coffin content and poles	132
3	Joining and using coffins	134
4	Measuring coffins	134
5	Coffin diagnostics	135
	5.1 Constants and variables	135
XVII	The <code>l3color</code> package: Colour support	136
1	Colour in boxes	136
XVIII	The <code>l3msg</code> package: Messages	137
1	Creating new messages	137
2	Contextual information for messages	138
3	Issuing messages	139
4	Redirecting messages	141
5	Low-level message functions	142
6	Kernel-specific functions	143
7	Expandable errors	144
8	Internal <code>l3msg</code> functions	145
XIX	The <code>l3keys</code> package: Key–value interfaces	146
1	Creating keys	147
2	Sub-dividing keys	151
3	Choice and multiple choice keys	151
4	Setting keys	153
5	Setting known keys only	154

6	Utility functions for keys	154
7	Low-level interface for parsing key–val lists	154
XX	The <code>l3file</code> package: File and I/O operations	157
1	File operation functions	157
1.1	Input–output stream management	158
1.2	Reading from files	159
2	Writing to files	160
2.1	Wrapping lines in output	161
2.2	Constant input–output streams	162
2.3	Primitive conditionals	162
2.4	Internal file functions and variables	162
2.5	Internal input–output functions	163
XXI	The <code>l3fp</code> package: floating points	164
1	Creating and initialising floating point variables	165
2	Setting floating point variables	165
3	Using floating point numbers	166
4	Floating point conditionals	167
5	Floating point expression loops	168
6	Some useful constants, and scratch variables	169
7	Floating point exceptions	170
8	Viewing floating points	171
9	Floating point expressions	172
9.1	Input of floating point numbers	172
9.2	Precedence of operators	173
9.3	Operations	173
10	Disclaimer and roadmap	178
XXII	The <code>l3luatex</code> package: LuaTeX-specific functions	181
1	Breaking out to Lua	181

2	Category code tables	182
XXIII	The <i>I3candidates</i> package: Experimental additions to <i>I3kernel</i>	184
1	Additions to <i>I3basics</i>	184
2	Additions to <i>I3box</i>	184
2.1	Affine transformations	184
2.2	Viewing part of a box	185
2.3	Internal variables	186
3	Additions to <i>I3clist</i>	187
4	Additions to <i>I3coffins</i>	188
5	Additions to <i>I3file</i>	189
6	Additions to <i>I3fp</i>	190
7	Additions to <i>I3prop</i>	190
8	Additions to <i>I3seq</i>	191
9	Additions to <i>I3skip</i>	193
10	Additions to <i>I3tl</i>	193
11	Additions to <i>I3tokens</i>	194
XXIV	Implementation	195
1	<i>I3bootstrap</i> implementation	195
1.1	Format-specific code	195
1.2	Package-specific code part one	196
1.3	The <code>\pdfstrcmp</code> primitive in <i>Xe</i> T _E X	197
1.4	Engine requirements	197
1.5	Package-specific code part two	198
1.6	Dealing with package-mode meta-data	199
1.7	The L ^A T _E X3 code environment	201
1.8	Deprecated functions	203
2	<i>I3names</i> implementation	203

3	<i>l3basics</i> implementation	213
3.1	Renaming some TeX primitives (again)	213
3.2	Defining some constants	215
3.3	Defining functions	216
3.4	Selecting tokens	217
3.5	Gobbling tokens from input	218
3.6	Conditional processing and definitions	218
3.7	Dissecting a control sequence	224
3.8	Exist or free	226
3.9	Defining and checking (new) functions	228
3.10	More new definitions	230
3.11	Copying definitions	231
3.12	Undefining functions	232
3.13	Generating parameter text from argument count	232
3.14	Defining functions from a given number of arguments	233
3.15	Using the signature to define functions	234
3.16	Checking control sequence equality	236
3.17	Diagnostic functions	237
3.18	Engine specific definitions	237
3.19	Doing nothing functions	238
3.20	String comparisons	238
3.21	Breaking out of mapping functions	240
3.22	Deprecated functions	240
4	<i>l3expan</i> implementation	242
4.1	General expansion	242
4.2	Hand-tuned definitions	246
4.3	Definitions with the automated technique	248
4.4	Last-unbraced versions	249
4.5	Preventing expansion	251
4.6	Defining function variants	251
4.7	Variants which cannot be created earlier	258
5	<i>l3prg</i> implementation	258
5.1	Primitive conditionals	258
5.2	Defining a set of conditional functions	259
5.3	The boolean data type	259
5.4	Boolean expressions	261
5.5	Logical loops	266
5.6	Producing n copies	267
5.7	Detecting TeX's mode	269
5.8	Internal programming functions	269
5.9	Deprecated functions	272

6	I3quark implementation	275
6.1	Quarks	275
6.2	Scan marks	278
6.3	Deprecated quark functions	279
7	I3token implementation	279
7.1	Character tokens	279
7.2	Generic tokens	281
7.3	Token conditionals	283
7.4	Peeking ahead at the next token	292
7.5	Decomposing a macro definition	297
7.6	Deprecated functions	298
8	I3int implementation	301
8.1	Integer expressions	301
8.2	Creating and initialising integers	303
8.3	Setting and incrementing integers	305
8.4	Using integers	306
8.5	Integer expression conditionals	306
8.6	Integer expression loops	309
8.7	Integer step functions	310
8.8	Formatting integers	311
8.9	Converting from other formats to integers	316
8.10	Viewing integer	320
8.11	Constant integers	320
8.12	Scratch integers	321
8.13	Deprecated functions	322
9	I3skip implementation	323
9.1	Length primitives renamed	323
9.2	Creating and initialising <code>dim</code> variables	324
9.3	Setting <code>dim</code> variables	325
9.4	Utilities for dimension calculations	325
9.5	Dimension expression conditionals	326
9.6	Dimension expression loops	328
9.7	Using <code>dim</code> expressions and variables	329
9.8	Viewing <code>dim</code> variables	330
9.9	Constant dimensions	330
9.10	Scratch dimensions	330
9.11	Creating and initialising <code>skip</code> variables	331
9.12	Setting <code>skip</code> variables	332
9.13	Skip expression conditionals	332
9.14	Using <code>skip</code> expressions and variables	333
9.15	Inserting skips into the output	333
9.16	Viewing <code>skip</code> variables	334
9.17	Constant skips	334

9.18	Scratch skips	334
9.19	Creating and initialising <code>muskip</code> variables	334
9.20	Setting <code>muskip</code> variables	335
9.21	Using <code>muskip</code> expressions and variables	336
9.22	Viewing <code>muskip</code> variables	336
9.23	Constant muskips	337
9.24	Scratch muskips	337
9.25	Deprecated functions	337
10	<code>l3tl</code> implementation	338
10.1	Functions	338
10.2	Constant token lists	340
10.3	Adding to token list variables	340
10.4	Reassigning token list category codes	342
10.5	Reassigning token list character codes	343
10.6	Modifying token list variables	343
10.7	Token list conditionals	346
10.8	Mapping to token lists	349
10.9	Using token lists	351
10.10	Working with the contents of token lists	351
10.11	Token by token changes	353
10.12	The first token from a token list	355
10.13	Viewing token lists	361
10.14	Scratch token lists	361
10.15	Deprecated functions	361
11	<code>l3seq</code> implementation	364
11.1	Allocation and initialisation	365
11.2	Appending data to either end	367
11.3	Modifying sequences	367
11.4	Sequence conditionals	369
11.5	Recovering data from sequences	369
11.6	Mapping to sequences	373
11.7	Sequence stacks	375
11.8	Viewing sequences	376
11.9	Scratch sequences	376
11.10	Deprecated interfaces	376

12	I3clist implementation	377
12.1	Allocation and initialisation	378
12.2	Removing spaces around items	379
12.3	Adding data to comma lists	380
12.4	Comma lists as stacks	381
12.5	Modifying comma lists	383
12.6	Comma list conditionals	384
12.7	Mapping to comma lists	385
12.8	Viewing comma lists	388
12.9	Scratch comma lists	389
12.10	Deprecated interfaces	389
13	I3prop implementation	390
13.1	Allocation and initialisation	391
13.2	Accessing data in property lists	392
13.3	Property list conditionals	395
13.4	Recovering values from property lists with branching	397
13.5	Mapping to property lists	397
13.6	Viewing property lists	398
13.7	Deprecated interfaces	399
14	I3box implementation	400
14.1	Creating and initialising boxes	400
14.2	Measuring and setting box dimensions	402
14.3	Using boxes	402
14.4	Box conditionals	402
14.5	The last box inserted	403
14.6	Constant boxes	403
14.7	Scratch boxes	404
14.8	Viewing box contents	404
14.9	Horizontal mode boxes	405
14.10	Vertical mode boxes	406
14.11	Deprecated functions	408
15	I3coffins Implementation	408
15.1	Coffins: data structures and general variables	409
15.2	Basic coffin functions	410
15.3	Measuring coffins	414
15.4	Coffins: handle and pole management	415
15.5	Coffins: calculation of pole intersections	417
15.6	Aligning and typesetting of coffins	420
15.7	Coffin diagnostics	425
15.8	Messages	431
16	I3color Implementation	431

17	I3msg implementation	432
17.1	Creating messages	433
17.2	Messages: support functions and text	434
17.3	Showing messages: low level mechanism	435
17.4	Displaying messages	437
17.5	Kernel-specific functions	444
17.6	Expandable errors	449
17.7	Showing variables	451
17.8	Deprecated functions	453
18	I3keys Implementation	455
18.1	Low-level interface	455
18.2	Constants and variables	458
18.3	The key defining mechanism	460
18.4	Turning properties into actions	461
18.5	Creating key properties	466
18.6	Setting keys	469
18.7	Utilities	472
18.8	Messages	473
18.9	Deprecated functions	474
19	I3file implementation	474
19.1	File operations	475
19.2	Input operations	479
19.2.1	Variables and constants	480
19.2.2	Stream management	481
19.2.3	Reading input	484
19.3	Output operations	485
19.3.1	Variables and constants	485
19.4	Stream management	486
19.4.1	Deferred writing	488
19.4.2	Immediate writing	488
19.4.3	Special characters for writing	489
19.4.4	Hard-wrapping lines to a character count	489
19.5	Messages	494
19.6	Deprecated functions	495
20	I3fp implementation	496
21	I3fp-aux implementation	496

22	Internal storage of floating points numbers	496
22.1	Using arguments and semicolons	497
22.2	Constants, and structure of floating points	498
22.3	Overflow, underflow, and exact zero	500
22.4	Expanding after a floating point number	500
22.5	Packing digits	502
22.6	Decimate (dividing by a power of 10)	504
22.7	Functions for use within primitive conditional branches	506
22.8	Small integer floating points	507
22.9	Length of a floating point array	508
22.10	x-like expansion expandably	508
22.11	Messages	509
23	I3fp-traps Implementation	509
23.1	Flags	510
23.2	Traps	510
23.3	Errors	514
23.4	Messages	514
24	I3fp-round implementation	515
24.1	Rounding tools	515
24.2	The round function	518
25	I3fp-parse implementation	520
26	Precedences	520
27	Evaluating an expression	521
28	Work plan	521
28.1	Storing results	521
28.2	Precedence	523
28.3	Infix operators	524
28.4	Prefix operators, parentheses, and functions	526
28.5	Type detection	529
29	Internal representation	529

30	Internal parsing functions	530
30.1	Expansion control	531
30.2	Fp object type	532
30.3	Reading digits	532
30.4	Parsing one operand	533
30.4.1	Trimming leading zeros	538
30.4.2	Exact zero	540
30.4.3	Small significand	540
30.4.4	Large significand	542
30.4.5	Finding the exponent	544
30.4.6	Beyond 16 digits: rounding	547
30.5	Main functions	550
30.6	Main functions	551
30.7	Prefix operators	553
30.7.1	Identifiers	553
30.7.2	Unary minus, plus, not	555
30.7.3	Other prefixes	555
30.8	Infix operators	556
31	Messages	562
32	I3fp-logic Implementation	562
32.1	Syntax of internal functions	562
32.2	Existence test	563
32.3	Comparison	563
32.4	Floating point expression loops	565
32.5	Extrema	567
32.6	Boolean operations	568
32.7	Ternary operator	569
33	I3fp-basics Implementation	570
33.1	Common to several operations	570
33.2	Addition and subtraction	571
33.2.1	Sign, exponent, and special numbers	572
33.2.2	Absolute addition	574
33.2.3	Absolute subtraction	576
33.3	Multiplication	581
33.3.1	Signs, and special numbers	581
33.3.2	Absolute multiplication	582
33.4	Division	585
33.4.1	Signs, and special numbers	585
33.4.2	Work plan	586
33.4.3	Implementing the significand division	589
33.5	Unary operations	594

34	l3fp-extended implementation	594
34.1	Description of extended fixed points	595
34.2	Helpers for extended fixed points	595
34.3	Dividing a fixed point number by a small integer	596
34.4	Adding and subtracting fixed points	597
34.5	Multiplying fixed points	598
34.6	Combining product and sum of fixed points	599
34.7	Converting from fixed point to floating point	601
35	l3fp-expo implementation	606
35.1	Logarithm	607
35.1.1	Work plan	607
35.1.2	Some constants	607
35.1.3	Sign, exponent, and special numbers	607
35.1.4	Absolute ln	608
35.2	Exponential	615
35.2.1	Sign, exponent, and special numbers	615
35.3	Power	620
36	Implementation	627
36.1	Direct trigonometric functions	627
36.1.1	Sign and special numbers	627
36.1.2	Small and tiny arguments	630
36.1.3	Reduction of large arguments	632
36.2	Computing the power series	633
37	l3fp-convert implementation	636
37.1	Trimming trailing zeros	636
37.2	Scientific notation	637
37.3	Decimal representation	638
37.4	Token list representation	640
37.5	Formatting	641
37.6	Convert to dimension or integer	641
37.7	Convert from a dimension	642
37.8	Use and eval	643
37.9	Convert an array of floating points to a comma list	643
38	l3fp-assign implementation	644
38.1	Assigning values	644
38.2	Updating values	645
38.3	Showing values	645
38.4	Some useful constants and scratch variables	646
39	l3fp-old implementation	646
39.1	Compatibility	646

40	I3luatex implementation	649
40.1	Category code tables	650
40.2	Messages	654
40.3	Deprecated functions	654
41	I3candidates Implementation	654
41.1	Additions to I3box	654
41.2	Affine transformations	654
41.3	Viewing part of a box	662
41.4	Additions to I3clist	663
41.5	Additions to I3coffins	667
41.6	Rotating coffins	667
41.7	Resizing coffins	672
41.8	Additions to I3file	674
41.9	Additions to I3fp	675
41.10	Additions to I3prop	675
41.11	Additions to I3seq	676
41.12	Additions to I3skip	681
41.13	Additions to I3tl	681
41.14	Additions to I3tokens	684
	Index	686

Part I

Introduction to `expl3` and this document

This document is intended to act as a comprehensive reference manual for the `expl3` language. A general guide to the L^AT_EX3 programming language is found in [expl3.pdf](#).

1 Naming functions and variables

L^AT_EX3 does not use @ as a “letter” for defining internal macros. Instead, the symbols _ and : are used in internal macro names to provide structure. The name of each *function* is divided into logical units using _, while : separates the *name* of the function from the *argument specifier* (“arg-spec”). This describes the arguments expected by the function. In most cases, each argument is represented by a single letter. The complete list of arg-spec letters for a function is referred to as the *signature* of the function.

Each function name starts with the *module* to which it belongs. Thus apart from a small number of very basic functions, all `expl3` function names contain at least one underscore to divide the module name from the descriptive name of the function. For example, all functions concerned with comma lists are in module `cclist` and begin `\cclist_`.

Every function must include an argument specifier. For functions which take no arguments, this will be blank and the function name will end :. Most functions take one or more arguments, and use the following argument specifiers:

- D The D specifier means *do not use*. All of the T_EX primitives are initially \let to a D name, and some are then given a second name. Only the kernel team should use anything with a D specifier!
- N and n These mean *no manipulation*, of a single token for N and of a set of tokens given in braces for n. Both pass the argument through exactly as given. Usually, if you use a single token for an n argument, all will be well.
- c This means *csname*, and indicates that the argument will be turned into a csname before being used. So So `\foo:c {ArgumentOne}` will act in the same way as `\foo:N \ArgumentOne`.
- V and v These mean *value of variable*. The V and v specifiers are used to get the content of a variable without needing to worry about the underlying T_EX structure containing the data. A V argument will be a single token (similar to N), for example `\foo:V \MyVariable`; on the other hand, using v a csname is constructed first, and then the value is recovered, for example `\foo:v {MyVariable}`.
- o This means *expansion once*. In general, the V and v specifiers are favoured over o for recovering stored information. However, o is useful for correctly processing information with delimited arguments.

- x** The **x** specifier stands for *exhaustive expansion*: every token in the argument is fully expanded until only unexpandable ones remain. The **\edef** primitive carries out this type of expansion. Functions which feature an **x**-type argument are in general *not* expandable, unless specifically noted.
- f** The **f** specifier stands for *full expansion*, and in contrast to **x** stops at the first non-expandable item (reading the argument from left to right) without trying to expand it. For example, when setting a token list variable (a macro used for storage), the sequence

```
\tl_set:Nn \l_my_a_t1 { A }
\tl_set:Nn \l_my_b_t1 { B }
\tl_set:Nf \l_my_a_t1 { \l_my_a_t1 \l_my_b_t1 }
```

will leave **\l_my_a_t1** with the content **A\l_my_b_t1**, as **A** cannot be expanded and so terminates expansion before **\l_my_b_t1** is considered.

T and F For logic tests, there are the branch specifiers **T** (*true*) and **F** (*false*). Both specifiers treat the input in the same way as **n** (no change), but make the logic much easier to see.

- p** The letter **p** indicates **\TeX** *parameters*. Normally this will be used for delimited functions as **expl3** provides better methods for creating simple sequential arguments.
- w** Finally, there is the **w** specifier for *weird* arguments. This covers everything else, but mainly applies to delimited values (where the argument must be terminated by some arbitrary string).

Notice that the argument specifier describes how the argument is processed prior to being passed to the underlying function. For example, **\foo:c** will take its argument, convert it to a control sequence and pass it to **\foo:N**.

Variables are named in a similar manner to functions, but begin with a single letter to define the type of variable:

- c** Constant: global parameters whose value should not be changed.
- g** Parameters whose value should only be set globally.
- l** Parameters whose value should only be set locally.

Each variable name is then build up in a similar way to that of a function, typically starting with the module¹ name and then a descriptive part. Variables end with a short identifier to show the variable type:

bool Either true or false.

box Box register.

¹The module names are not used in case of generic scratch registers defined in the data type modules, e.g., the **int** module contains some scratch variables called **\l_tmpa_int**, **\l_tmpb_int**, and so on. In such a case adding the module name up front to denote the module and in the back to indicate the type, as in **\l_int_tmpa_int** would be very unreadable.

clist Comma separated list.

coffin a “box with handles” — a higher-level data type for carrying out **box** alignment operations.

dim “Rigid” lengths.

fp floating-point values;

int Integer-valued count register.

prop Property list.

seq “Sequence”: a data-type used to implement lists (with access at both ends) and stacks.

skip “Rubber” lengths.

stream An input or output stream (for reading from or writing to, respectively).

t1 Token list variables: placeholder for a token list.

1.1 Terminological inexactitude

A word of warning. In this document, and others referring to the `expl3` programming modules, we often refer to “variables” and “functions” as if they were actual constructs from a real programming language. In truth, `TeX` is a macro processor, and functions are simply macros that may or may not take arguments and expand to their replacement text. Many of the common variables are *also* macros, and if placed into the input stream will simply expand to their definition as well — a “function” with no arguments and a “token list variable” are in truth one and the same. On the other hand, some “variables” are actually registers that must be initialised and their values set and retrieved with specific functions.

The conventions of the `expl3` code are designed to clearly separate the ideas of “macros that contain data” and “macros that contain code”, and a consistent wrapper is applied to all forms of “data” whether they be macros or actually registers. This means that sometimes we will use phrases like “the function returns a value”, when actually we just mean “the macro expands to something”. Similarly, the term “execute” might be used in place of “expand” or it might refer to the more specific case of “processing in `TeX`’s stomach” (if you are familiar with the `TeXbook` parlance).

If in doubt, please ask; chances are we’ve been hasty in writing certain definitions and need to be told to tighten up our terminology.

2 Documentation conventions

This document is typeset with the experimental `l3doc` class; several conventions are used to help describe the features of the code. A number of conventions are used here to make the documentation clearer.

Each group of related functions is given in a box. For a function with a “user” name, this might read:

\ExplSyntaxOn ... \ExplSyntaxOff

The textual description of how the function works would appear here. The syntax of the function is shown in mono-spaced text to the right of the box. In this example, the function takes no arguments and so the name of the function is simply reprinted.

For programming functions, which use `_` and `:` in their name there are a few additional conventions: If two related functions are given with identical names but different argument specifiers, these are termed *variants* of each other, and the latter functions are printed in grey to show this more clearly. They will carry out the same function but will take different types of argument:

\seq_new:N *(sequence)*
\seq_new:c

When a number of variants are described, the arguments are usually illustrated only for the base function. Here, *(sequence)* indicates that `\seq_new:N` expects the name of a sequence. From the argument specifier, `\seq_new:c` also expects a sequence name, but as a name rather than as a control sequence. Each argument given in the illustration should be described in the following text.

Fully expandable functions Some functions are fully expandable, which allows it to be used within an `x`-type argument (in plain TeX terms, inside an `\edef`), as well as within an `f`-type argument. These fully expandable functions are indicated in the documentation by a star:

\cs_to_str:N *

As with other functions, some text should follow which explains how the function works. Usually, only the star will indicate that the function is expandable. In this case, the function expects a *(cs)*, shorthand for a *(control sequence)*.

Restricted expandable functions A few functions are fully expandable but cannot be fully expanded within an `f`-type argument. In this case a hollow star is used to indicate this:

\seq_map_function:NN *

Conditional functions Conditional (`if`) functions are normally defined in three variants, with `T`, `F` and `TF` argument specifiers. This allows them to be used for different “true”/“false” branches, depending on which outcome the conditional is being used to test. To indicate this without repetition, this information is given in a shortened form:

`\xetex_if_engine:TF *`

`\xetex_if_engine:TF {<true code>} {<false code>}`

The underlining and italic of TF indicates that `\xetex_if_engine:T`, `\xetex_if_engine:F` and `\xetex_if_engine:TF` are all available. Usually, the illustration will use the TF variant, and so both `<true code>` and `<false code>` will be shown. The two variant forms T and F take only `<true code>` and `<false code>`, respectively. Here, the star also shows that this function is expandable. With some minor exceptions, *all* conditional functions in the `expl3` modules should be defined in this way.

Variables, constants and so on are described in a similar manner:

`\l_tmpa_tl`

A short piece of text will describe the variable: there is no syntax illustration in this case.

In some cases, the function is similar to one in L^AT_EX 2_ε or plain TeX. In these cases, the text will include an extra “**TeXhackers note**” section:

`\token_to_str:N *`

`\token_to_str:N <token>`

The normal description text.

TeXhackers note: Detail for the experienced TeX or L^AT_EX 2_ε programmer. In this case, it would point out that this function is the TeX primitive `\string`.

3 Formal language conventions which apply generally

As this is a formal reference guide for L^AT_EX3 programming, the descriptions of functions are intended to be reasonably “complete”. However, there is also a need to avoid repetition. Formal ideas which apply to general classes of function are therefore summarised here.

For tests which have a TF argument specification, the test is evaluated to give a logically TRUE or FALSE result. Depending on this result, either the `<true code>` or the `<false code>` will be left in the input stream. In the case where the test is expandable, and a predicate (`_p`) variant is available, the logical value determined by the test is left in the input stream: this will typically be part of a larger logical construct.

4 TeX concepts not supported by L^AT_EX3

The TeX concept of an “`\outer`” macro is *not supported* at all by L^AT_EX3. As such, the functions provided here may break when used on top of L^AT_EX 2_ε if `\outer` tokens are used in the arguments.

Part II

The **l3bootstrap** package

Bootstrap code

1 Using the L^AT_EX3 modules

The modules documented in `source3` are designed to be used on top of L^AT_EX2_ε and are loaded all as one with the usual `\usepackage{expl3}` or `\RequirePackage{expl3}` instructions. These modules will also form the basis of the L^AT_EX3 format, but work in this area is incomplete and not included in this documentation at present.

As the modules use a coding syntax different from standard L^AT_EX2_ε it provides a few functions for setting it up.

```
\ExplSyntaxOn
\ExplSyntaxOff
```

Updated: 2011-08-13

```
\ExplSyntaxOn <code> \ExplSyntaxOff
```

The `\ExplSyntaxOn` function switches to a category code régime in which spaces are ignored and in which the colon (`:`) and underscore (`_`) are treated as “letters”, thus allowing access to the names of code functions and variables. Within this environment, `~` is used to input a space. The `\ExplSyntaxOff` reverts to the document category code régime.

```
\ProvidesExplPackage
\ProvidesExplClass
\ProvidesExplFile
```

These functions act broadly in the same way as the L^AT_EX2_ε kernel functions `\ProvidesPackage`, `\ProvidesClass` and `\ProvidesFile`. However, they also implicitly switch `\ExplSyntaxOn` for the remainder of the code with the file. At the end of the file, `\ExplSyntaxOff` will be called to reverse this. (This is the same concept as L^AT_EX2_ε provides in turning on `\makeatletter` within package and class code.)

```
\GetIdInfo
```

Updated: 2012-06-04

```
\RequirePackage{l3bootstrap}
\GetIdInfo $Id: <SVN info field> $ {\<description>}
```

Extracts all information from a SVN field. Spaces are not ignored in these fields. The information pieces are stored in separate control sequences with `\ExplFileName` for the part of the file name leading up to the period, `\ExplFileDate` for date, `\ExplFileVersion` for version and `\ExplFileDescription` for the description.

To summarize: Every single package using this syntax should identify itself using one of the above methods. Special care is taken so that every package or class file loaded with `\RequirePackage` or alike are loaded with usual L^AT_EX2_ε category codes and the L^AT_EX3 category code scheme is reloaded when needed afterwards. See implementation for details. If you use the `\GetIdInfo` command you can use the information when loading a package with

```
\ProvidesExplPackage{\ExplFileName}
{\ExplFileDate}{\ExplFileVersion}{\ExplFileDescription}
```

1.1 Internal functions and variables

`__expl_package_check:`

`__expl_package_check:`

Used to ensure that all parts of `expl3` are loaded together (*i.e.* as part of `expl3`). Issues an error if a kernel package is loaded independently of the bundle.

`\l_kernel_expl_bool`

A boolean which records the current code syntax status: `true` if currently inside a code environment. This variable should only be set by `\ExplSyntaxOn`/`\ExplSyntaxOff`.

Part III

The **I3names** package

Namespace for primitives

1 Setting up the L^AT_EX3 programming language

This module is at the core of the L^AT_EX3 programming language. It performs the following tasks:

- defines new names for all T_EX primitives;
- switches to the category code régime for programming;
- provides support settings for building the code as a T_EX format.

This module is entirely dedicated to primitives, which should not be used directly within L^AT_EX3 code (outside of “kernel-level” code). As such, the primitives are not documented here: *The T_EXbook*, *T_EX by Topic* and the manuals for pdfT_EX, X_ET_EX and LuaT_EX should be consulted for details of the primitives. These are named based on the engine which first introduced them:

\tex_... Introduced by T_EX itself;
\etex_... Introduced by the ε -T_EX extensions;
\pdftex_... Introduced by pdfT_EX;
\xetex_... Introduced by X_ET_EX;
\luatex_... Introduced by LuaT_EX.

Part IV

The **I3basics** package

Basic definitions

As the name suggest this package holds some basic definitions which are needed by most or all other packages in this set.

Here we describe those functions that are used all over the place. With that we mean functions dealing with the construction and testing of control sequences. Furthermore the basic parts of conditional processing are covered; conditional processing dealing with specific data types is described in the modules specific for the respective data types.

1 No operation functions

\prg_do_nothing: *

\prg_do_nothing:

An expandable function which does nothing at all: leaves nothing in the input stream after a single expansion.

\scan_stop:

\scan_stop:

A non-expandable function which does nothing. Does not vanish on expansion but produces no typeset output.

2 Grouping material

\group_begin:
\group_end:

\group_begin:
\group_end:

These functions begin and end a group for definition purposes. Assignments are local to groups unless carried out in a global manner. (A small number of exceptions to this rule will be noted as necessary elsewhere in this document.) Each \group_begin: must be matched by a \group_end:, although this does not have to occur within the same function. Indeed, it is often necessary to start a group within one function and finish it within another, for example when seeking to use non-standard category codes.

\group_insert_after:N <*token*>

Adds <*token*> to the list of <*tokens*> to be inserted when the current group level ends. The list of <*tokens*> to be inserted will be empty at the beginning of a group: multiple applications of \group_insert_after:N may be used to build the inserted list one <*token*> at a time. The current group level may be closed by a \group_end: function or by a token with category code 2 (close-group). The later will be a } if standard category codes apply.

3 Control sequences and functions

As \TeX is a macro language, creating new functions means creating macros. At point of use, a function is replaced by the replacement text (“code”) in which each parameter in the code (#1, #2, etc.) is replaced the appropriate arguments absorbed by the function. In the following, $\langle \text{code} \rangle$ is therefore used as a shorthand for “replacement text”.

Functions which are not “protected” will be fully expanded inside an \mathbf{x} expansion. In contrast, “protected” functions are not expanded within \mathbf{x} expansions.

3.1 Defining functions

Functions can be created with no requirement that they are declared first (in contrast to variables, which must always be declared). Declaring a function before setting up the code means that the name chosen will be checked and an error raised if it is already in use. The name of a function can be checked at the point of definition using the $\backslash\text{cs_new...}$ functions: this is recommended for all functions which are defined for the first time.

There are three ways to define new functions. All classes define a function to expand to the substitution text. Within the substitution text the actual parameters are substituted for the formal parameters (#1, #2, ...).

new Create a new function with the **new** scope, such as $\backslash\text{cs_new:Npn}$. The definition is global and will result in an error if it is already defined.

set Create a new function with the **set** scope, such as $\backslash\text{cs_set:Npn}$. The definition is restricted to the current \TeX group and will not result in an error if the function is already defined.

gset Create a new function with the **gset** scope, such as $\backslash\text{cs_gset:Npn}$. The definition is global and will not result in an error if the function is already defined.

Within each set of scope there are different ways to define a function. The differences depend on restrictions on the actual parameters and the expandability of the resulting function.

nopar Create a new function with the **nopar** restriction, such as $\backslash\text{cs_set_nopar:Npn}$. The parameter may not contain $\backslash\text{par}$ tokens.

protected Create a new function with the **protected** restriction, such as $\backslash\text{cs_set_protected:Npn}$. The parameter may contain $\backslash\text{par}$ tokens but the function will not expand within an \mathbf{x} -type expansion.

3.2 Defining new functions using parameter text

$\backslash\text{cs_new:Npn}$
 $\backslash\text{cs_new:(cpn|Npx|cpx)}$

$\backslash\text{cs_new:Npn } \langle \text{function} \rangle \langle \text{parameters} \rangle \{ \langle \text{code} \rangle \}$

Creates $\langle \text{function} \rangle$ to expand to $\langle \text{code} \rangle$ as replacement text. Within the $\langle \text{code} \rangle$, the $\langle \text{parameters} \rangle$ (#1, #2, etc.) will be replaced by those absorbed by the function. The definition is global and an error will result if the $\langle \text{function} \rangle$ is already defined.

<code>\cs_new_nopar:Npn</code>	<code>\cs_new_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_new_nopar:(cpn Npx cpx)</code>	Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ (#1, #2, etc.) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain \par tokens. The definition is global and an error will result if the $\langle function \rangle$ is already defined.
<code>\cs_new_protected:Npn</code>	<code>\cs_new_protected:Npn <function> <parameters> {<code>}</code>
<code>\cs_new_protected:(cpn Npx cpx)</code>	Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ (#1, #2, etc.) will be replaced by those absorbed by the function. The $\langle function \rangle$ will not expand within an x-type argument. The definition is global and an error will result if the $\langle function \rangle$ is already defined.
<code>\cs_new_protected_nopar:Npn</code>	<code>\cs_new_protected_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_new_protected_nopar:(cpn Npx cpx)</code>	Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ (#1, #2, etc.) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain \par tokens. The $\langle function \rangle$ will not expand within an x-type argument. The definition is global and an error will result if the $\langle function \rangle$ is already defined.
<code>\cs_set:Npn</code>	<code>\cs_set:Npn <function> <parameters> {<code>}</code>
<code>\cs_set:(cpn Npx cpx)</code>	Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ (#1, #2, etc.) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current TeX group level.
<code>\cs_set_nopar:Npn</code>	<code>\cs_set_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_set_nopar:(cpn Npx cpx)</code>	Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ (#1, #2, etc.) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain \par tokens. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current TeX group level.
<code>\cs_set_protected:Npn</code>	<code>\cs_set_protected:Npn <function> <parameters> {<code>}</code>
<code>\cs_set_protected:(cpn Npx cpx)</code>	Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ (#1, #2, etc.) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current TeX group level. The $\langle function \rangle$ will not expand within an x-type argument.

```
\cs_set_protected_nopar:Npn           \cs_set_protected_nopar:Npn <function> <parameters> {{code}}
\cs_set_protected_nopar:(cpn|Npx|cpx)
```

Sets *<function>* to expand to *<code>* as replacement text. Within the *<code>*, the *<parameters>* (#1, #2, etc.) will be replaced by those absorbed by the function. When the *<function>* is used the *<parameters>* absorbed cannot contain `\par` tokens. The assignment of a meaning to the *<function>* is restricted to the current TeX group level. The *<function>* will not expand within an x-type argument.

```
\cs_gset:Npn                         \cs_gset:Npn <function> <parameters> {{code}}
\cs_gset:(cpn|Npx|cpx)
```

Globally sets *<function>* to expand to *<code>* as replacement text. Within the *<code>*, the *<parameters>* (#1, #2, etc.) will be replaced by those absorbed by the function. The assignment of a meaning to the *<function>* is *not* restricted to the current TeX group level: the assignment is global.

```
\cs_gset_nopar:Npn                   \cs_gset_nopar:Npn <function> <parameters> {{code}}
```

Globally sets *<function>* to expand to *<code>* as replacement text. Within the *<code>*, the *<parameters>* (#1, #2, etc.) will be replaced by those absorbed by the function. When the *<function>* is used the *<parameters>* absorbed cannot contain `\par` tokens. The assignment of a meaning to the *<function>* is *not* restricted to the current TeX group level: the assignment is global.

```
\cs_gset_protected:Npn              \cs_gset_protected:Npn <function> <parameters> {{code}}
\cs_gset_protected:(cpn|Npx|cpx)
```

Globally sets *<function>* to expand to *<code>* as replacement text. Within the *<code>*, the *<parameters>* (#1, #2, etc.) will be replaced by those absorbed by the function. The assignment of a meaning to the *<function>* is *not* restricted to the current TeX group level: the assignment is global. The *<function>* will not expand within an x-type argument.

```
\cs_gset_protected_nopar:Npn        \cs_gset_protected_nopar:Npn <function> <parameters> {{code}}
\cs_gset_protected_nopar:(cpn|Npx|cpx)
```

Globally sets *<function>* to expand to *<code>* as replacement text. Within the *<code>*, the *<parameters>* (#1, #2, etc.) will be replaced by those absorbed by the function. When the *<function>* is used the *<parameters>* absorbed cannot contain `\par` tokens. The assignment of a meaning to the *<function>* is *not* restricted to the current TeX group level: the assignment is global. The *<function>* will not expand within an x-type argument.

3.3 Defining new functions using the signature

```
\cs_new:Nn                           \cs_new:Nn <function> {{code}}
\cs_new:(cn|Nx|cx)
```

Creates *<function>* to expand to *<code>* as replacement text. Within the *<code>*, the number of *<parameters>* is detected automatically from the function signature. These *<parameters>* (#1, #2, etc.) will be replaced by those absorbed by the function. The definition is global and an error will result if the *<function>* is already defined.

```
\cs_new_nopar:Nn
```

```
\cs_new_nopar:(cn|Nx|cx)
```

```
\cs_new_nopar:Nn <function> {<code>}
```

Creates *<function>* to expand to *<code>* as replacement text. Within the *<code>*, the number of *<parameters>* is detected automatically from the function signature. These *<parameters>* (#1, #2, etc.) will be replaced by those absorbed by the function. When the *<function>* is used the *<parameters>* absorbed cannot contain \par tokens. The definition is global and an error will result if the *<function>* is already defined.

```
\cs_new_protected:Nn
```

```
\cs_new_protected:(cn|Nx|cx)
```

```
\cs_new_protected:Nn <function> {<code>}
```

Creates *<function>* to expand to *<code>* as replacement text. Within the *<code>*, the number of *<parameters>* is detected automatically from the function signature. These *<parameters>* (#1, #2, etc.) will be replaced by those absorbed by the function. The *<function>* will not expand within an x-type argument. The definition is global and an error will result if the *<function>* is already defined.

```
\cs_new_protected_nopar:Nn
```

```
\cs_new_protected_nopar:(cn|Nx|cx)
```

```
\cs_new_protected_nopar:Nn <function> {<code>}
```

Creates *<function>* to expand to *<code>* as replacement text. Within the *<code>*, the number of *<parameters>* is detected automatically from the function signature. These *<parameters>* (#1, #2, etc.) will be replaced by those absorbed by the function. When the *<function>* is used the *<parameters>* absorbed cannot contain \par tokens. The *<function>* will not expand within an x-type argument. The definition is global and an error will result if the *<function>* is already defined.

```
\cs_set:Nn
```

```
\cs_set:(cn|Nx|cx)
```

```
\cs_set:Nn <function> {<code>}
```

Sets *<function>* to expand to *<code>* as replacement text. Within the *<code>*, the number of *<parameters>* is detected automatically from the function signature. These *<parameters>* (#1, #2, etc.) will be replaced by those absorbed by the function. The assignment of a meaning to the *<function>* is restricted to the current T_EX group level.

```
\cs_set_nopar:Nn
```

```
\cs_set_nopar:(cn|Nx|cx)
```

```
\cs_set_nopar:Nn <function> {<code>}
```

Sets *<function>* to expand to *<code>* as replacement text. Within the *<code>*, the number of *<parameters>* is detected automatically from the function signature. These *<parameters>* (#1, #2, etc.) will be replaced by those absorbed by the function. When the *<function>* is used the *<parameters>* absorbed cannot contain \par tokens. The assignment of a meaning to the *<function>* is restricted to the current T_EX group level.

```
\cs_set_protected:Nn
```

```
\cs_set_protected:(cn|Nx|cx)
```

```
\cs_set_protected:Nn <function> {<code>}
```

Sets *<function>* to expand to *<code>* as replacement text. Within the *<code>*, the number of *<parameters>* is detected automatically from the function signature. These *<parameters>* (#1, #2, etc.) will be replaced by those absorbed by the function. The *<function>* will not expand within an x-type argument. The assignment of a meaning to the *<function>* is restricted to the current T_EX group level.

```
\cs_set_protected_nopar:Nn      \cs_set_protected_nopar:Nn <function> {<code>}
\cs_set_protected_nopar:(cn|Nx|cx)
```

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ (#1, #2, etc.) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain \par tokens. The $\langle function \rangle$ will not expand within an x-type argument. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current T_EX group level.

```
\cs_gset:Nn                      \cs_gset:Nn <function> {<code>}
\cs_gset:(cn|Nx|cx)
```

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ (#1, #2, etc.) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is global.

```
\cs_gset_nopar:Nn                \cs_gset_nopar:Nn <function> {<code>}
\cs_gset_nopar:(cn|Nx|cx)
```

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ (#1, #2, etc.) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain \par tokens. The assignment of a meaning to the $\langle function \rangle$ is global.

```
\cs_gset_protected:Nn           \cs_gset_protected:Nn <function> {<code>}
\cs_gset_protected:(cn|Nx|cx)
```

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ (#1, #2, etc.) will be replaced by those absorbed by the function. The $\langle function \rangle$ will not expand within an x-type argument. The assignment of a meaning to the $\langle function \rangle$ is global.

```
\cs_gset_protected_nopar:Nn     \cs_gset_protected_nopar:Nn <function> {<code>}
\cs_gset_protected_nopar:(cn|Nx|cx)
```

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ (#1, #2, etc.) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain \par tokens. The $\langle function \rangle$ will not expand within an x-type argument. The assignment of a meaning to the $\langle function \rangle$ is global.

`\cs_generate_from_arg_count:NNnn` `\cs_generate_from_arg_count:Nnnn <function> <creator> <number>`
`\cs_generate_from_arg_count:(cNnn|Ncnn)` `<code>`

Updated: 2012-01-14

Uses the *<creator>* function (which should have signature `Npn`, for example `\cs_new:Npn`) to define a *<function>* which takes *<number>* arguments and has *<code>* as replacement text. The *<number>* of arguments is an integer expression, evaluated as detailed for `\int_eval:n`.

3.4 Copying control sequences

Control sequences (not just functions as defined above) can be set to have the same meaning using the functions described here. Making two control sequences equivalent means that the second control sequence is a *copy* of the first (rather than a pointer to it). Thus the old and new control sequence are not tied together: changes to one are not reflected in the other.

In the following text “cs” is used as an abbreviation for “control sequence”.

`\cs_new_eq:NN`
`\cs_new_eq:(Nc|cN|cc)`

Globally creates *<control sequence₁>* and sets it to have the same meaning as *<control sequence₂>* or *<token>*. The second control sequence may subsequently be altered without affecting the copy.

`\cs_set_eq:NN`
`\cs_set_eq:(Nc|cN|cc)`

Sets *<control sequence₁>* to have the same meaning as *<control sequence₂>* (or *<token>*). The second control sequence may subsequently be altered without affecting the copy. The assignment of a meaning to the *<control sequence₁>* is restricted to the current TeX group level.

`\cs_gset_eq:NN`
`\cs_gset_eq:(Nc|cN|cc)`

Globally sets *<control sequence₁>* to have the same meaning as *<control sequence₂>* (or *<token>*). The second control sequence may subsequently be altered without affecting the copy. The assignment of a meaning to the *<control sequence₁>* is *not* restricted to the current TeX group level: the assignment is global.

3.5 Deleting control sequences

There are occasions where control sequences need to be deleted. This is handled in a very simple manner.

`\cs_undefine:N`
`\cs_undefine:c`

Sets *<control sequence>* to be globally undefined.

Updated: 2011-09-15

3.6 Showing control sequences

\cs_meaning:N ★
\cs_meaning:c ★
Updated: 2011-12-22

\cs_meaning:N *(control sequence)*

This function expands to the *meaning* of the *(control sequence)* control sequence. This will show the *(replacement text)* for a macro.

TeXhackers note: This is TeX's \meaning primitive. The c variant correctly reports undefined arguments.

\cs_show:N
\cs_show:c
Updated: 2012-09-09

\cs_show:N *(control sequence)*

Displays the definition of the *(control sequence)* on the terminal.

TeXhackers note: This is similar to the TeX primitive \show, wrapped to a fixed number of characters per line.

3.7 Converting to and from control sequences

\use:c ★

\use:c {*(control sequence name)*}

Converts the given *(control sequence name)* into a single control sequence token. This process requires two expansions. The content for *(control sequence name)* may be literal material or from other expandable functions. The *(control sequence name)* must, when fully expanded, consist of character tokens which are not active: typically, they will be of category code 10 (space), 11 (letter) or 12 (other), or a mixture of these.

As an example of the \use:c function, both

\use:c { a b c }

and

```
\tl_new:N \l_my_tl
\tl_set:Nn \l_my_tl { a b c }
\use:c { \tl_use:N \l_my_tl }
```

would be equivalent to

\abc

after two expansions of \use:c.

\cs:w ★
\cs_end: ★

\cs:w *(control sequence name)* \cs_end:

Converts the given *(control sequence name)* into a single control sequence token. This process requires one expansion. The content for *(control sequence name)* may be literal material or from other expandable functions. The *(control sequence name)* must, when fully expanded, consist of character tokens which are not active: typically, they will be of category code 10 (space), 11 (letter) or 12 (other), or a mixture of these.

TeXhackers note: These are the TeX primitives \csname and \endcsname.

As an example of the `\cs:w` and `\cs_end:` functions, both

```
\cs:w a b c \cs_end:
```

and

```
\tl_new:N \l_my_tl  
\tl_set:Nn \l_my_tl { a b c }  
\cs:w \tl_use:N \l_my_tl \cs_end:
```

would be equivalent to

```
\abc
```

after one expansion of `\cs:w`.

`\cs_to_str:N` *

Converts the given *<control sequence>* into a series of characters with category code 12 (other), except spaces, of category code 10. The sequence will *not* include the current escape token, *cf.* `\token_to_str:N`. Full expansion of this function requires exactly 2 expansion steps, and so an **x**-type expansion, or two **o**-type expansions will be required to convert the *<control sequence>* to a sequence of characters in the input stream. In most cases, an **f**-expansion will be correct as well, but this loses a space at the start of the result.

4 Using or removing tokens and arguments

Tokens in the input can be read and used or read and discarded. If one or more tokens are wrapped in braces then in absorbing them the outer set will be removed. At the same time, the category code of each token is set when the token is read by a function (if it is read more than once, the category code is determined by the the situation in force when first function absorbs the token).

`\use:n` *
`\use:(nn|nnn|nnnn)` *

```
\use:n   {\langle group_1\rangle}  
\use:nn  {\langle group_1\rangle} {\langle group_2\rangle}  
\use:nnn {\langle group_1\rangle} {\langle group_2\rangle} {\langle group_3\rangle}  
\use:nnnn {\langle group_1\rangle} {\langle group_2\rangle} {\langle group_3\rangle} {\langle group_4\rangle}
```

As illustrated, these functions will absorb between one and four arguments, as indicated by the argument specifier. The braces surrounding each argument will be removed leaving the remaining tokens in the input stream. The category code of these tokens will also be fixed by this process (if it has not already been by some other absorption). All of these functions require only a single expansion to operate, so that one expansion of

```
\use:nn { abc } { { def } }
```

will result in the input stream containing

```
abc { def }
```

i.e. only the outer braces will be removed.

`\use_i:nn` ★ `\use_i:nn {<arg1>} {<arg2>}`
`\use_ii:nn` ★

These functions absorb two arguments from the input stream. The function `\use_i:nn` discards the second argument, and leaves the content of the first argument in the input stream. `\use_ii:nn` discards the first argument and leaves the content of the second argument in the input stream. The category code of these tokens will also be fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect.

`\use_i:nnn` ★ `\use_i:nnn {<arg1>} {<arg2>} {<arg3>}`
`\use_ii:nnn` ★
`\use_iii:nnn` ★

These functions absorb three arguments from the input stream. The function `\use_i:nnn` discards the second and third arguments, and leaves the content of the first argument in the input stream. `\use_ii:nnn` and `\use_iii:nnn` work similarly, leaving the content of second or third arguments in the input stream, respectively. The category code of these tokens will also be fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect.

`\use_i:nnnn` ★ `\use_i:nnnn {<arg1>} {<arg2>} {<arg3>} {<arg4>}`
`\use_ii:nnnn` ★
`\use_iii:nnnn` ★
`\use_iv:nnnn` ★

These functions absorb four arguments from the input stream. The function `\use_i:nnnn` discards the second, third and fourth arguments, and leaves the content of the first argument in the input stream. `\use_ii:nnnn`, `\use_iii:nnnn` and `\use_iv:nnnn` work similarly, leaving the content of second, third or fourth arguments in the input stream, respectively. The category code of these tokens will also be fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect.

`\use_i_ii:nnn` ★ `\use_i_ii:nnn {<arg1>} {<arg2>} {<arg3>}`

This functions will absorb three arguments and leave the content of the first and second in the input stream. The category code of these tokens will also be fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect. An example:

```
\use_i_ii:nnn { abc } { { def } } { ghi }
```

will result in the input stream containing

```
abc { def }
```

i.e. the outer braces will be removed and the third group will be removed.

`\use_none:n` ★ `\use_none:n {<group1>}`
`\use_none:(nn|nnn|nnnn|nnnnn|nnnnnn|nnnnnnn|nnnnnnnn|nnnnnnnnn)` ★

These functions absorb between one and nine groups from the input stream, leaving nothing on the resulting input stream. These functions work after a single expansion. One or more of the `n` arguments may be an unbraced single token (*i.e.* an `N` argument).

\use:x

\use:x {*expandable tokens*}

Updated: 2011-12-31

Fully expands the *<expandable tokens>* and inserts the result into the input stream at the current location. Any hash characters (#) in the argument must be doubled.

4.1 Selecting tokens from delimited arguments

A different kind of function for selecting tokens from the token stream are those that use delimited arguments.

\use_none_delimit_by_q_nil:w	★ \use_none_delimit_by_q_nil:w { <i>balanced text</i> } \q_nil
\use_none_delimit_by_q_stop:w	★ \use_none_delimit_by_q_stop:w { <i>balanced text</i> } \q_stop
\use_none_delimit_by_q_recursion_stop:w	★ \use_none_delimit_by_q_recursion_stop:w { <i>balanced text</i> } \q_recursion_stop

Absorb the *<balanced text>* form the input stream delimited by the marker given in the function name, leaving nothing in the input stream.

\use_i_delimit_by_q_nil:nw	★ \use_i_delimit_by_q_nil:nw {\ <i>inserted tokens</i> } { <i>balanced text</i> }
\use_i_delimit_by_q_stop:nw	★ \q_nil
\use_i_delimit_by_q_recursion_stop:nw	★ \use_i_delimit_by_q_stop:nw {\ <i>inserted tokens</i> } { <i>balanced text</i> } \q_stop \use_i_delimit_by_q_recursion_stop:nw {\ <i>inserted tokens</i> } { <i>balanced text</i> } \q_recursion_stop

Absorb the *<balanced text>* form the input stream delimited by the marker given in the function name, leaving *<inserted tokens>* in the input stream for further processing.

5 Predicates and conditionals

LATEX3 has three concepts for conditional flow processing:

Branching conditionals Functions that carry out a test and then execute, depending on its result, either the code supplied as the *<true code>* or the *<false code>*. These arguments are denoted with T and F, respectively. An example would be

\cs_if_free:cTF {abc} {*true code*} {*false code*}

a function that will turn the first argument into a control sequence (since it's marked as c) then checks whether this control sequence is still free and then depending on the result carry out the code in the second argument (true case) or in the third argument (false case).

These type of functions are known as "conditionals"; whenever a TF function is defined it will usually be accompanied by T and F functions as well. These are provided for convenience when the branch only needs to go a single way. Package writers are free to choose which types to define but the kernel definitions will always provide all three versions.

Important to note is that these branching conditionals with $\langle true\ code \rangle$ and/or $\langle false\ code \rangle$ are always defined in a way that the code of the chosen alternative can operate on following tokens in the input stream.

These conditional functions may or may not be fully expandable, but if they are expandable they will be accompanied by a “predicate” for the same test as described below.

Predicates “Predicates” are functions that return a special type of boolean value which can be tested by the boolean expression parser. All functions of this type are expandable and have names that end with `_p` in the description part. For example,

```
\cs_if_free_p:N
```

would be a predicate function for the same type of test as the conditional described above. It would return “true” if its argument (a single token denoted by `N`) is still free for definition. It would be used in constructions like

```
\bool_if:nTF {
  \cs_if_free_p:N \l_tmpz_tl || \cs_if_free_p:N \g_tmpz_tl
} {\langle true code \rangle} {\langle false code \rangle}
```

For each predicate defined, a “branching conditional” will also exist that behaves like a conditional described above.

Primitive conditionals There is a third variety of conditional, which is the original concept used in plain TeX and L^AT_EX 2 _{ε} . Their use is discouraged in expl3 (although still used in low-level definitions) because they are more fragile and in many cases require more expansion control (hence more code) than the two types of conditionals described above.

<u><code>\c_true_bool</code></u> <u><code>\c_false_bool</code></u>	Constants that represent <code>true</code> and <code>false</code> , respectively. Used to implement predicates.
---	---

5.1 Tests on control sequences

<u><code>\cs_if_eq_p:NN</code></u> *	<code>\cs_if_eq_p:NN {\langle cs₁ \rangle} {\langle cs₂ \rangle}</code>
<u><code>\cs_if_eq:NNTF</code></u> *	<code>\cs_if_eq:NNTF {\langle cs₁ \rangle} {\langle cs₂ \rangle} {\langle true code \rangle} {\langle false code \rangle}</code>

Compares the definition of two $\langle control\ sequences \rangle$ and is logically `true` the same, i.e. if they have exactly the same definition when examined with `\cs_show:N`.

<u><code>\cs_if_exist_p:N</code></u> *	<code>\cs_if_exist_p:N {\langle control\ sequence \rangle}</code>
<u><code>\cs_if_exist_p:c</code></u> *	<code>\cs_if_exist:NTF {\langle control\ sequence \rangle} {\langle true code \rangle} {\langle false code \rangle}</code>
<u><code>\cs_if_exist:NTF</code></u> *	Tests whether the $\langle control\ sequence \rangle$ is currently defined (whether as a function or another control sequence type). Any valid definition of $\langle control\ sequence \rangle$ will evaluate as <code>true</code> .
<u><code>\cs_if_exist:cTF</code></u> *	

\cs_if_free_p:N	★	\cs_if_free_p:N <i><control sequence></i>
\cs_if_free_p:c	★	\cs_if_free:NTF <i><control sequence></i> { <i>true code</i> } { <i>false code</i> }
\cs_if_free:NTF	★	Tests whether the <i><control sequence></i> is currently free to be defined. This test will be
\cs_if_free:cTF	★	false if the <i><control sequence></i> currently exists (as defined by \cs_if_exist:N).

5.2 Testing string equality

\str_if_eq_p:nn	★	\str_if_eq_p:nn { <i>tl₁</i> } { <i>tl₂</i> }
\str_if_eq_p:(Vn on no nV VV)	★	\str_if_eq:nnTF { <i>tl₁</i> } { <i>tl₂</i> } { <i>true code</i> } { <i>false code</i> }
\str_if_eq:nnTF	★	
\str_if_eq:(Vn on no nV VV)TF	★	

Compares the two *<token lists>* on a character by character basis, and is **true** if the two lists contain the same characters in the same order. Thus for example

```
\str_if_eq_p:no { abc } { \tl_to_str:n { abc } }
```

is logically **true**.

\str_if_eq_x_p:nn	★	\str_if_eq_x_p:nn { <i>tl₁</i> } { <i>tl₂</i> }
\str_if_eq_x:nnTF	★	\str_if_eq_x:nnTF { <i>tl₁</i> } { <i>tl₂</i> } { <i>true code</i> } { <i>false code</i> }

New: 2012-06-05

Compares the full expansion of two *<token lists>* on a character by character basis, and is **true** if the two lists contain the same characters in the same order. Thus for example

```
\str_if_eq_x_p:nn { abc } { \tl_to_str:n { abc } }
```

is logically **true**.

\str_case:nnn	★	\str_case:nnn { <i>test string</i> }
\str_case:onm	★	{ { <i>string case₁</i> } { <i>code case₁</i> } { <i>string case₂</i> } { <i>code case₂</i> } ... { <i>string case_n</i> } { <i>code case_n</i> } }

New: 2012-06-03

This function compares the *<test string>* in turn with each of the *<string cases>*. If the two are equal (as described for \str_if_eq:nnTF then the associated *<code>* is left in the input stream. If none of the tests are **true** then the *else code* will be left in the input stream.

\str_case_x:nnn *

New: 2012-06-05

```
\str_case_x:nnn {\test string}
{
  {\string case1} {\code case1}
  {\string case2} {\code case2}
  ...
  {\string casen} {\code casen}
}
{\else code}
```

This function compares the full expansion of the *<test string>* in turn with the full expansion of the *<string cases>*. If the two full expansions are equal (as described for \str_if_eq:nnTF then the associated *<code>* is left in the input stream. If none of the tests are true then the *else code* will be left in the input stream. The *<test string>* is expanded in each comparison, and must always yield the same result: for example, random numbers should not be used within this string.

5.3 Engine-specific conditionals

\luatex_if_engine_p: *

\luatex_if_engine:TF *

Updated: 2011-09-06

```
\luatex_if_luatex:TF {\true code} {\false code}
```

Detects if the document is being compiled using LuaTeX.

\pdftex_if_engine_p: *

\pdftex_if_engine:TF *

Updated: 2011-09-06

```
\pdftex_if_engine:TF {\true code} {\false code}
```

Detects if the document is being compiled using pdftEX.

\xetex_if_engine_p: *

\xetex_if_engine:TF *

Updated: 2011-09-06

```
\xetex_if_engine:TF {\true code} {\false code}
```

Detects if the document is being compiled using XETEX.

5.4 Primitive conditionals

The ε -TEX engine itself provides many different conditionals. Some expand whatever comes after them and others don't. Hence the names for these underlying functions will often contain a :w part but higher level functions are often available. See for instance \int_compare_p:nNn which is a wrapper for \if_int_compare:w.

Certain conditionals deal with specific data types like boxes and fonts and are described there. The ones described below are either the universal conditionals or deal with control sequences. We will prefix primitive conditionals with \if_.

<code>\if_true:</code>	★	<code>\if_true: <true code> \else: <false code> \fi:</code>
<code>\if_false:</code>	★	<code>\if_false: <true code> \else: <false code> \fi:</code>
<code>\or:</code>	★	<code>\reverse_if:N <primitive conditional></code>
<code>\else:</code>	★	<code>\if_true: always executes <true code>, while \if_false: always executes <false code>.</code>
<code>\fi:</code>	★	<code>\reverse_if:N reverses any two-way primitive conditional. \else: and \fi: delimit the branches of the conditional. \or: is used in case switches, see \3int for more.</code>
<code>\reverse_if:N</code>	★	

TExHackers note: These are equivalent to their corresponding TeX primitive conditionals; `\reverse_if:N` is ε-TEx's `\unless`.

<code>\if_meaning:w</code>	★	<code>\if_meaning:w <arg₁> <arg₂> <true code> \else: <false code> \fi:</code>
		<code>\if_meaning:w</code> executes <code><true code></code> when <code><arg₁></code> and <code><arg₂></code> are the same, otherwise it executes <code><false code></code> . <code><arg₁></code> and <code><arg₂></code> could be functions, variables, tokens; in all cases the <i>unexpanded</i> definitions are compared.

TExHackers note: This is TeX's `\ifx`.

<code>\if:w</code>	★	<code>\if:w <token₁> <token₂> <true code> \else: <false code> \fi:</code>
<code>\if_charcode:w</code>	★	<code>\if_catcode:w <token₁> <token₂> <true code> \else: <false code> \fi:</code>
<code>\if_catcode:w</code>	★	These conditionals will expand any following tokens until two unexpandable tokens are left. If you wish to prevent this expansion, prefix the token in question with <code>\exp_not:N</code> . <code>\if_catcode:w</code> tests if the category codes of the two tokens are the same whereas <code>\if:w</code> tests if the character codes are identical. <code>\if_charcode:w</code> is an alternative name for <code>\if:w</code> .

<code>\if_cs_exist:N</code>	★	<code>\if_cs_exist:N <cs> <true code> \else: <false code> \fi:</code>
<code>\if_cs_exist:w</code>	★	<code>\if_cs_exist:w <tokens> \cs_end: <true code> \else: <false code> \fi:</code>
		Check if <code><cs></code> appears in the hash table or if the control sequence that can be formed from <code><tokens></code> appears in the hash table. The latter function does not turn the control sequence in question into <code>\scan_stop:!</code> This can be useful when dealing with control sequences which cannot be entered as a single token.

<code>\if_mode_horizontal:</code>	★	<code>\if_mode_horizontal: <true code> \else: <false code> \fi:</code>
<code>\if_mode_vertical:</code>	★	Execute <code><true code></code> if currently in horizontal mode, otherwise execute <code><false code></code> . Similar for the other functions.
<code>\if_mode_math:</code>	★	
<code>\if_mode_inner:</code>	★	

6 Internal kernel functions

<code>__chk_if_exist_cs:N</code>		<code>__chk_if_exist_cs:N <cs></code>
<code>__chk_if_exist_cs:c</code>		This function checks that <code><cs></code> exists according to the criteria for <code>\cs_if_exist_p:N</code> , and if not raises a kernel-level error.

__chk_if_free_cs:N
__chk_if_free_cs:c

__chk_if_free_cs:N *(cs)*

This function checks that *(cs)* is free according to the criteria for \cs_if_free_p:N, and if not raises a kernel-level error.

__cs_count_signature:N ★
__cs_count_signature:c ★

__cs_count_signature:N *(function)*

Splits the *(function)* into the *(name)* (*i.e.* the part before the colon) and the *(signature)* (*i.e.* after the colon). The *(number)* of tokens in the *(signature)* is then left in the input stream. If there was no *(signature)* then the result is the marker value -1.

__cs_split_function:NN ★

__cs_split_function:NN *(function)* *(processor)*

Splits the *(function)* into the *(name)* (*i.e.* the part before the colon) and the *(signature)* (*i.e.* after the colon). This information is then placed in the input stream after the *(processor)* function in three parts: the *(name)*, the *(signature)* and a logic token indicating if a colon was found (to differentiate variables from function names). The *(name)* will not include the escape character, and both the *(name)* and *(signature)* are made up of tokens with category code 12 (other). The *(processor)* should be a function with argument specification :nnN (plus any trailing arguments needed).

__cs_get_function_name:N ★ __cs_get_function_name:N *(function)*

Splits the *(function)* into the *(name)* (*i.e.* the part before the colon) and the *(signature)* (*i.e.* after the colon). The *(name)* is then left in the input stream without the escape character present made up of tokens with category code 12 (other).

__cs_get_function_signature:N ★ __cs_get_function_signature:N *(function)*

Splits the *(function)* into the *(name)* (*i.e.* the part before the colon) and the *(signature)* (*i.e.* after the colon). The *(signature)* is then left in the input stream made up of tokens with category code 12 (other).

__cs_tmp:w

Function used for various short-term usages, for instance defining functions whose definition involves tokens which are hard to insert normally (spaces, characters with category other).

__kernel_register_show:N
__kernel_register_show:c

__kernel_register_show:N *(register)*

Used to show the contents of a T_EX register at the terminal, formatted such that internal parts of the mechanism are not visible.

__prg_case_end:nw

__prg_case_end:nw {*(code)*} *(tokens)* \q_recursion_stop

Used to terminate case statements (\int_case:nnn, etc.) by removing trailing *(tokens)* and the end marker \q_recursion_stop, and inserting the *(code)* for the successful case.

__str_if_eq_x_return:nn

```
\__str_if_eq_x_return:nn {\langle tl1 ⟩} {\langle tl2 ⟩}
```

Compares the full expansion of two *⟨token lists⟩* on a character by character basis, and is `true` if the two lists contain the same characters in the same order. Either `\prg_return_true:` or `\prg_return_false:` is then left in the input stream. This is a version of `\str_if_eq_x:nn(TF)` coded for speed.

Part V

The **\3expan** package

Argument expansion

This module provides generic methods for expanding TeX arguments in a systematic manner. The functions in this module all have prefix `exp`.

Not all possible variations are implemented for every base function. Instead only those that are used within the L^AT_EX3 kernel or otherwise seem to be of general interest are implemented. Consult the module description to find out which functions are actually defined. The next section explains how to define missing variants.

1 Defining new variants

The definition of variant forms for base functions may be necessary when writing new functions or when applying a kernel function in a situation that we haven't thought of before.

Internally preprocessing of arguments is done with functions from the `\exp_` module. They all look alike, an example would be `\exp_args:NNo`. This function has three arguments, the first and the second are a single tokens, while the third argument should be given in braces. Applying `\exp_args:NNo` will expand the content of third argument once before any expansion of the first and second arguments. If `\seq_gpush:N` was not defined it could be coded in the following way:

```
\exp_args:NNo \seq_gpush:Nn
  \g_file_name_stack
  \l_tmpa_t1
```

In other words, the first argument to `\exp_args:NNo` is the base function and the other arguments are preprocessed and then passed to this base function. In the example the first argument to the base function should be a single token which is left unchanged while the second argument is expanded once. From this example we can also see how the variants are defined. They just expand into the appropriate `\exp_` function followed by the desired base function, *e.g.*

```
\cs_new_nopar:Npn \seq_gpush:No { \exp_args:NNo \seq_gpush:Nn }
```

Providing variants in this way in style files is uncritical as the `\cs_new_nopar:Npn` function will silently accept definitions whenever the new definition is identical to an already given one. Therefore adding such definition to later releases of the kernel will not make such style files obsolete.

The steps above may be automated by using the function `\cs_generate_variant:Nn`, described next.

2 Methods for defining variants

\cs_generate_variant:Nn

Updated: 2012-08-28

```
\cs_generate_variant:Nn <parent control sequence> {<variant argument specifiers>}
```

This function is used to define argument-specifier variants of the *<parent control sequence>* for L^AT_EX3 code-level macros. The *<parent control sequence>* is first separated into the *<base name>* and *<original argument specifier>*. The comma-separated list of *<variant argument specifiers>* is then used to define variants of the *<original argument specifier>* where these are not already defined. For each *<variant>* given, a function is created which will expand its arguments as detailed and pass them to the *<parent control sequence>*. So for example

```
\cs_set:Npn \foo:Nn #1#2 { code here }
\cs_generate_variant:Nn \foo:Nn { c }
```

will create a new function `\foo:c` which will expand its first argument into a control sequence name and pass the result to `\foo:Nn`. Similarly

```
\cs_generate_variant:Nn \foo:Nn { NV , cV }
```

would generate the functions `\foo:NV` and `\foo:cV` in the same way. The `\cs_generate_variant:Nn` function can only be applied if the *<parent control sequence>* is already defined. If the *<parent control sequence>* is protected then the new sequence will also be protected. The *<variant>* is created globally, as is any `\exp_args:N`(*variant*) function needed to carry out the expansion.

3 Introducing the variants

The available internal functions for argument expansion come in two flavours, some of them are faster than others. Therefore it is usually best to follow the following guidelines when defining new functions that are supposed to come with variant forms:

- Arguments that might need expansion should come first in the list of arguments to make processing faster.
- Arguments that should consist of single tokens should come first.
- Arguments that need full expansion (*i.e.*, are denoted with `x`) should be avoided if possible as they can not be processed expandably, *i.e.*, functions of this type will not work correctly in arguments that are themselves subject to `x` expansion.
- In general, unless in the last position, multi-token arguments `n`, `f`, and `o` will need special processing which is not fast. Therefore it is best to use the optimized functions, namely those that contain only `N`, `c`, `V`, and `v`, and, in the last position, `o`, `f`, with possible trailing `N` or `n`, which are not expanded.

The `V` type returns the value of a register, which can be one of `t1`, `num`, `int`, `skip`, `dim`, `toks`, or built-in T_EX registers. The `v` type is the same except it first creates a

control sequence out of its argument before returning the value. This recent addition to the argument specifiers may shake things up a bit as most places where `o` is used will be replaced by `V`. The documentation you are currently reading will therefore require a fair bit of re-writing.

In general, the programmer should not need to be concerned with expansion control. When simply using the content of a variable, functions with a `V` specifier should be used. For those referred to by `(cs)name`, the `v` specifier is available for the same purpose. Only when specific expansion steps are needed, such as when using delimited arguments, should the lower-level functions with `o` specifiers be employed.

The `f` type is so special that it deserves an example. Let's pretend we want to set `\aaa` equal to the control sequence stemming from turning `b \l_tmpa_t1 b` into a control sequence. Furthermore we want to store the execution of it in a `(tl var)`. In this example we assume `\l_tmpa_t1` contains the text string `lur`. The straightforward approach is

```
\tl_set:Nn \l_tmpb_t1 { \cs_set_eq:Nc \aaa { b \l_tmpa_t1 b } }
```

Unfortunately this only puts `\exp_args:NNc \cs_set_eq:NN \aaa {b \l_tmpa_t1 b}` into `\l_tmpb_t1` and not `\cs_set_eq:NN \aaa = \blurb` as we probably wanted. Using `\tl_set:Nx` is not an option as that will die horribly. Instead we can do a

```
\tl_set:Nf \l_tmpb_t1 { \cs_set_eq:Nc \aaa { b \l_tmpa_t1 b } }
```

which puts the desired result in `\l_tmpb_t1`. It requires `\tl_set:Nf` to be defined as

```
\cs_set_nopar:Npn \tl_set:Nf { \exp_args:NNf \tl_set:Nn }
```

If you use this type of expansion in conditional processing then you should stick to using `TF` type functions only as it does not try to finish any `\if... \fi:` itself!

4 Manipulating the first argument

These functions are described in detail: expansion of multiple tokens follows the same rules but is described in a shorter fashion.

`\exp_args:N` \star `\exp_args:N` $\langle function \rangle \{ \langle tokens \rangle \} \dots$

This function absorbs two arguments (the `function` name and the `tokens`). The `tokens` are expanded once, and the result is inserted in braces into the input stream *after* reinsertion of the `function`. Thus the `function` may take more than one argument: all others will be left unchanged.

`\exp_args:Nc` \star `\exp_args:Nc` $\langle function \rangle \{ \langle tokens \rangle \}$

This function absorbs two arguments (the `function` name and the `tokens`). The `tokens` are expanded until only characters remain, and are then turned into a control sequence. (An internal error will occur if such a conversion is not possible). The result is inserted into the input stream *after* reinsertion of the `function`. Thus the `function` may take more than one argument: all others will be left unchanged.

The `:cc` variant constructs the `function` name in the same manner as described for the `tokens`.

`\exp_args:NV *` `\exp_args:NV <function> <variable>`

This function absorbs two arguments (the names of the *<function>* and the the *<variable>*). The content of the *<variable>* are recovered and placed inside braces into the input stream *after* reinsertion of the *<function>*. Thus the *<function>* may take more than one argument: all others will be left unchanged.

`\exp_args:Nv *` `\exp_args:Nv <function> {{<tokens>}}`

This function absorbs two arguments (the *<function>* name and the *<tokens>*). The *<tokens>* are expanded until only characters remain, and are then turned into a control sequence. (An internal error will occur if such a conversion is not possible). This control sequence should be the name of a *<variable>*. The content of the *<variable>* are recovered and placed inside braces into the input stream *after* reinsertion of the *<function>*. Thus the *<function>* may take more than one argument: all others will be left unchanged.

`\exp_args:Nf *` `\exp_args:Nf <function> {{<tokens>}}`

This function absorbs two arguments (the *<function>* name and the *<tokens>*). The *<tokens>* are fully expanded until the first non-expandable token or space is found, and the result is inserted in braces into the input stream *after* reinsertion of the *<function>*. Thus the *<function>* may take more than one argument: all others will be left unchanged.

`\exp_args:Nx` `\exp_args:Nx <function> {{<tokens>}}`

This function absorbs two arguments (the *<function>* name and the *<tokens>*) and exhaustively expands the *<tokens>* second. The result is inserted in braces into the input stream *after* reinsertion of the *<function>*. Thus the *<function>* may take more than one argument: all others will be left unchanged.

5 Manipulating two arguments

`\exp_args:NNo` `* \exp_args:NNc <token1> <token2> {{<tokens>}}`
`\exp_args:(NNc|NNv|NNV|NNf|Nco|Ncf|Ncc|NVV)` `*`

These optimized functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments.

`\exp_args:Nno` `* \exp_args:Noo <token> {{<tokens1>}} {{<tokens2>}}`
`\exp_args:(NnV|Nnf|Noo|Nof|Noc|Nff|Nfo|Nnc)` `*`

Updated: 2012-01-14

These functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments. These functions need special (slower) processing.

```
\exp_args:NNx          \exp_args:NNx <token1> <token2> {<tokens>}  
\exp_args:(Nnx|Ncx|Nox|Nxo|Nxx)
```

These functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments. These functions are not expandable.

6 Manipulating three arguments

```
\exp_args:NNNo          * \exp_args:NNNo <token1> <token2> <token3> {<tokens>}  
\exp_args:(NNNV|Nccc|NcNc|NcNo|Ncco) *
```

These optimized functions absorb four arguments and expand the second, third and fourth as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second argument, *etc.*

```
\exp_args:NNoo          * \exp_args:NNNo <token1> <token2> <token3> {<tokens>}  
\exp_args:(NNno|Nnno|Nnnnc|Nooo) *
```

These functions absorb four arguments and expand the second, third and fourth as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second argument, *etc.* These functions need special (slower) processing.

```
\exp_args:NNnx          \exp_args:NNnx <token1> <token2> {<tokens1>} {<tokens2>}  
\exp_args:(NNox|Nnnx|Nnox|Nnox|Ncnx|Nccx)
```

These functions absorb four arguments and expand the second, third and fourth as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second argument, *etc.*

7 Unbraced expansion

\exp_last_unbraced:Nf	*	\exp_last_unbraced:Nno <i><token></i>
\exp_last_unbraced:(NV No Nv Nco NcV NNV NNo Nno Noo Nfo NNNV NNNo NnNo)	*	<i><tokens₁></i> <i><tokens₂></i>

Updated: 2012-02-12

These functions absorb the number of arguments given by their specification, carry out the expansion indicated and leave the results in the input stream, with the last argument not surrounded by the usual braces. Of these, the :Nno, :Noo, and :Nfo variants need special (slower) processing.

TeXhackers note: As an optimization, the last argument is unbraced by some of those functions before expansion. This can cause problems if the argument is empty: for instance, \exp_last_unbraced:Nf \mypkg_foo:w { } \q_stop leads to an infinite loop, as the quark is f-expanded.

\exp_last_unbraced:Nx	\exp_last_unbraced:Nx <i><function></i> { <i><tokens></i> }
-----------------------	---

This function fully expands the *<tokens>* and leaves the result in the input stream after reinsertion of *<function>*. This function is not expandable.

\exp_last_two_unbraced:Noo *	\exp_last_two_unbraced:Noo <i><token></i> <i><tokens₁></i> { <i><tokens₂></i> }
------------------------------	---

This function absorbs three arguments and expands the second and third once. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments, which are not wrapped in braces. This function needs special (slower) processing.

\exp_after:wN *	\exp_after:wN <i><token₁></i> <i><token₂></i>
-----------------	---

Carries out a single expansion of *<token₂>* (which may consume arguments) prior to the expansion of *<token₁>*. If *<token₂>* is a TeX primitive, it will be executed rather than expanded, while if *<token₂>* has not expanded (for example, if it is a character) then it will be left unchanged. It is important to notice that *<token₁>* may be *any* single token, including group-opening and -closing tokens ({ or }) assuming normal TeX category codes). Unless specifically required, expansion should be carried out using an appropriate argument specifier variant or the appropriate \exp_arg:N function.

TeXhackers note: This is the TeX primitive \expandafter renamed.

8 Preventing expansion

Despite the fact that the following functions are all about preventing expansion, they're designed to be used in an expandable context and hence are all marked as being 'expandable' since they themselves will not appear after the expansion has completed.

<u>\exp_not:N</u> *	<code>\exp_not:N <token></code>	Prevents expansion of the <i><token></i> in a context where it would otherwise be expanded, for example an x-type argument.
		TeXhackers note: This is the TeX <code>\noexpand</code> primitive.
<u>\exp_not:c</u> *	<code>\exp_not:c {<tokens>}</code>	Expands the <i><tokens></i> until only unexpandable content remains, and then converts this into a control sequence. Further expansion of this control sequence is then inhibited.
<u>\exp_not:n</u> *	<code>\exp_not:n {<tokens>}</code>	Prevents expansion of the <i><tokens></i> in a context where they would otherwise be expanded, for example an x-type argument.
		TeXhackers note: This is the ε-TeX <code>\unexpanded</code> primitive. Hence its argument <i>must</i> be surrounded by braces.
<u>\exp_not:V</u> *	<code>\exp_not:V <variable></code>	Recovers the content of the <i><variable></i> , then prevents expansion of this material in a context where it would otherwise be expanded, for example an x-type argument.
<u>\exp_not:v</u> *	<code>\exp_not:v {<tokens>}</code>	Expands the <i><tokens></i> until only unexpandable content remains, and then converts this into a control sequence (which should be a <i><variable></i> name). The content of the <i><variable></i> is recovered, and further expansion is prevented in a context where it would otherwise be expanded, for example an x-type argument.
<u>\exp_not:o</u> *	<code>\exp_not:o {<tokens>}</code>	Expands the <i><tokens></i> once, then prevents any further expansion in a context where they would otherwise be expanded, for example an x-type argument.
<u>\exp_not:f</u> *	<code>\exp_not:f {<tokens>}</code>	Expands <i><tokens></i> fully until the first unexpandable token is found. Expansion then stops, and the result of the expansion (including any tokens which were not expanded) is protected from further expansion.
<u>\exp_stop_f:</u> *	<code>\function:f <tokens> \exp_stop_f: <more tokens></code>	This function terminates an f-type expansion. Thus if a function <code>\function:f</code> starts an f-type expansion and all of <i><tokens></i> are expandable <code>\exp_stop:f</code> will terminate the expansion of tokens even if <i><more tokens></i> are also expandable. The function itself is an implicit space token. Inside an x-type expansion, it will retain its form, but when typeset it produces the underlying space (_).

Updated: 2011-06-03

9 Internal functions and variables

\l__exp_internal_tl

The `\exp_` module has its private variables to temporarily store results of the argument expansion. This is done to avoid interference with other functions using temporary variables.

```
\:::n \cs_set_nopar:Npn \exp_args:Ncof { \:::c \:::o \:::f \::: }
```

Internal forms for the base expansion types. These names do *not* conform to the general L^AT_EX3 approach as this makes them more readily visible in the log and so forth.

```
\:::c  
\:::o  
\:::f  
\:::x  
\:::v  
\:::V  
\:::
```

Part VI

The `\l3prg` package

Control structures

Conditional processing in L^AT_EX3 is defined as something that performs a series of tests, possibly involving assignments and calling other functions that do not read further ahead in the input stream. After processing the input, a *state* is returned. The typical states returned are `<true>` and `<false>` but other states are possible, say an `<error>` state for erroneous input, *e.g.*, text as input in a function comparing integers.

L^AT_EX3 has two forms of conditional flow processing based on these states. The first form is predicate functions that turn the returned state into a boolean `<true>` or `<false>`. For example, the function `\cs_if_free:p:N` checks whether the control sequence given as its argument is free and then returns the boolean `<true>` or `<false>` values to be used in testing with `\if_predicate:w` or in functions to be described below. The second form is the kind of functions choosing a particular argument from the input stream based on the result of the testing as in `\cs_if_free:NTF` which also takes one argument (the `N`) and then executes either `true` or `false` depending on the result. Important to note here is that the arguments are executed after exiting the underlying `\if... \fi:` structure.

1 Defining a set of conditional functions

```
\prg_new_conditional:Npnn \prg_new_conditional:Nnn
\prg_set_conditional:Npnn \prg_set_conditional:Nnn
```

Updated: 2012-02-06

These functions create a family of conditionals using the same `{<code>}` to perform the test created. Those conditionals are expandable if `<code>` is. The `new` versions will check for existing definitions and perform assignments globally (*cf.* `\cs_new:Npn`) whereas the `set` versions do no check and perform assignments locally (*cf.* `\cs_set:Npn`). The conditionals created are dependent on the comma-separated list of `<conditions>`, which should be one or more of p, T, F and TF.

```
\prg_new_protected_conditional:Npnn \prg_new_protected_conditional:Nnn
\prg_set_protected_conditional:Npnn \prg_set_protected_conditional:Nnn
```

Updated: 2012-02-06

These functions create a family of protected conditionals using the same `{<code>}` to perform the test created. The `<code>` does not need to be expandable. The `new` version will check for existing definitions and perform assignments globally (*cf.* `\cs_new:Npn`) whereas the `set` version will not (*cf.* `\cs_set:Npn`). The conditionals created are depended on the comma-separated list of `<conditions>`, which should be one or more of T, F and TF (not p).

The conditionals are defined by `\prg_new_conditional:Npnn` and friends as:

- `\langle name\rangle_p:(arg spec)` — a predicate function which will supply either a logical `true` or logical `false`. This function is intended for use in cases where one or more logical tests are combined to lead to a final outcome. This function will not work properly for `protected` conditionals.
- `\langle name\rangle:(arg spec)T` — a function with one more argument than the original `(arg spec)` demands. The `\langle true branch\rangle` code in this additional argument will be left on the input stream only if the test is `true`.
- `\langle name\rangle:(arg spec)F` — a function with one more argument than the original `(arg spec)` demands. The `\langle false branch\rangle` code in this additional argument will be left on the input stream only if the test is `false`.
- `\langle name\rangle:(arg spec)TF` — a function with two more arguments than the original `(arg spec)` demands. The `\langle true branch\rangle` code in the first additional argument will be left on the input stream if the test is `true`, while the `\langle false branch\rangle` code in the second argument will be left on the input stream if the test is `false`.

The `\langle code\rangle` of the test may use `\langle parameters\rangle` as specified by the second argument to `\prg_set_conditional:Npnn`: this should match the `\langle argument specification\rangle` but this is not enforced. The `Nnn` versions infer the number of arguments from the argument specification given (*cf.* `\cs_new:Nn`, etc.). Within the `\langle code\rangle`, the functions `\prg_return_true:` and `\prg_return_false:` are used to indicate the logical outcomes of the test.

An example can easily clarify matters here:

```
\prg_set_conditional:Npnn \foo_if_bar:NN #1#2 { p , T , TF }
{
  \if_meaning:w \l_tmpa_tl #1
    \prg_return_true:
  \else:
    \if_meaning:w \l_tmpa_tl #2
      \prg_return_true:
    \else:
      \prg_return_false:
    \fi:
  \fi:
}
```

This defines the function `\foo_if_bar_p:NN`, `\foo_if_bar:NNTF` and `\foo_if_bar:NNT` but not `\foo_if_bar:NNF` (because `F` is missing from the `\langle conditions\rangle` list). The return statements take care of resolving the remaining `\else:` and `\fi:` before returning the state. There must be a return statement for each branch, failing to do so will result in an error if that branch is executed.

```
\prg_new_eq_conditional:NNn \prg_new_eq_conditional:NNn \⟨name1⟩:(arg spec1) \⟨name2⟩:(arg spec2)
\prg_set_eq_conditional:NNn {⟨conditions⟩}
```

These functions copies a family of conditionals. The `new` version will check for existing definitions (*cf.* `\cs_new:Npn`) whereas the `set` version will not (*cf.* `\cs_set:Npn`). The conditionals copied are depended on the comma-separated list of `⟨conditions⟩`, which should be one or more of `p`, `T`, `F` and `TF`.

```
\prg_return_true: *
\prg_return_false: *
```

These functions define the logical state at the end of a conditional. As such, they should appear within the code for a conditional statement generated by `\prg_set_conditional:Npnn`, *etc.*

2 The boolean data type

This section describes a boolean data type which is closely connected to conditional processing as sometimes you want to execute some code depending on the value of a switch (*e.g.*, draft/final) and other times you perhaps want to use it as a predicate function in an `\if_predicate:w` test. The problem of the primitive `\if_false:` and `\if_true:` tokens is that it is not always safe to pass them around as they may interfere with scanning for termination of primitive conditional processing. Therefore, we employ two canonical booleans: `\c_true_bool` or `\c_false_bool`. Besides preventing problems as described above, it also allows us to implement a simple boolean parser supporting the logical operations And, Or, Not, *etc.* which can then be used on both the boolean type and predicate functions.

All conditional `\bool_` functions except assignments are expandable and expect the input to also be fully expandable (which will generally mean being constructed from predicate functions, possibly nested).

```
\bool_new:N \bool_new:c
```

Creates a new `⟨boolean⟩` or raises an error if the name is already taken. The declaration is global. The `⟨boolean⟩` will initially be `false`.

```
\bool_set_false:N \bool_set_false:c \bool_gset_false:N \bool_gset_false:c
```

`\bool_set_true:N \bool_set_true:c \bool_gset_true:N \bool_gset_true:c`

`\bool_set_true:N ⟨boolean⟩`

Sets `⟨boolean⟩` logically `true`.

`\bool_set_eq:NN`
`\bool_set_eq:(cN|Nc|cc)`
`\bool_gset_eq:NN`
`\bool_gset_eq:(cN|Nc|cc)`

`\bool_set_eq:NN <boolean1> <boolean2>`

Sets the content of `<boolean1>` equal to that of `<boolean2>`.

`\bool_set:Nn`
`\bool_set:cN`
`\bool_gset:Nn`
`\bool_gset:cN`

Updated: 2012-07-08

`\bool_set:Nn <boolean> {<boolexpr>}`

Evaluates the `<boolean expression>` as described for `\bool_if:n(TF)`, and sets the `<boolean>` variable to the logical truth of this evaluation.

`\bool_if_p:N *`
`\bool_if_p:c *`
`\bool_if:NTF *`
`\bool_if:cTF *`

`\bool_if_p:N <boolean>`

`\bool_if:NTF <boolean> {<true code>} {<false code>}`

Tests the current truth of `<boolean>`, and continues expansion based on this result.

`\bool_show:N`
`\bool_show:c`

New: 2012-02-09

`\bool_show:N <boolean>`

Displays the logical truth of the `<boolean>` on the terminal.

`\bool_show:n`

New: 2012-02-09

Updated: 2012-07-08

`\bool_show:n {<boolean expression>}`

Displays the logical truth of the `<boolean expression>` on the terminal.

`\bool_if_exist_p:N *`
`\bool_if_exist_p:c *`
`\bool_if_exist:NTF *`
`\bool_if_exist:cTF *`

New: 2012-03-03

`\bool_if_exist_p:N <boolean>`

`\bool_if_exist:NTF <boolean> {<true code>} {<false code>}`

Tests whether the `<boolean>` is currently defined. This does not check that the `<boolean>` really is a boolean variable.

`\l_tmpa_bool`
`\l_tmpb_bool`

A scratch boolean for local assignment. It is never used by the kernel code, and so is safe for use with any L^AT_EX3-defined function. However, it may be overwritten by other non-kernel code and so should only be used for short-term storage.

`\g_tmpa_bool`
`\g_tmpb_bool`

A scratch boolean for global assignment. It is never used by the kernel code, and so is safe for use with any L^AT_EX3-defined function. However, it may be overwritten by other non-kernel code and so should only be used for short-term storage.

3 Boolean expressions

As we have a boolean datatype and predicate functions returning boolean *true* or *false* values, it seems only fitting that we also provide a parser for *boolean expressions*.

A boolean expression is an expression which given input in the form of predicate functions and boolean variables, return boolean *true* or *false*. It supports the logical operations And, Or and Not as the well-known infix operators `&&`, `||` and `!` with their usual precedences. In addition to this, parentheses can be used to isolate sub-expressions. For example,

```
\int_compare_p:n { 1 = 1 } &&
(
  \int_compare_p:n { 2 = 3 } ||
  \int_compare_p:n { 4 = 4 } ||
  \int_compare_p:n { 1 = \error } % is skipped
) &&
! ( \int_compare_p:n { 2 = 4 } )
```

is a valid boolean expression. Note that minimal evaluation is carried out whenever possible so that whenever a truth value cannot be changed any more, the remaining tests within the current group are skipped.

```
\bool_if_p:n *
\bool_if:nTF *
```

Updated: 2012-07-08

Tests the current truth of *boolean expression*, and continues expansion based on this result. The *boolean expression* should consist of a series of predicates or boolean variables with the logical relationship between these defined using `&&` (“And”), `||` (“Or”), `!` (“Not”) and parentheses. Minimal evaluation is used in the processing, so that once a result is defined there is not further expansion of the tests. For example

```
\bool_if_p:n
{
  \int_compare_p:nNn { 1 } = { 1 }
  &&
  (
    \int_compare_p:nNn { 2 } = { 3 } ||
    \int_compare_p:nNn { 4 } = { 4 } ||
    \int_compare_p:nNn { 1 } = { \error } % is skipped
  )
  &&
  ! \int_compare_p:nNn { 2 } = { 4 }
}
```

will be `true` and will not evaluate `\int_compare_p:nNn { 1 } = { \error }`. The logical Not applies to the next predicate or group.

`\bool_not_p:n` ★

Updated: 2012-07-08

`\bool_not_p:n {<boolean expression>}`

Function version of `!(<boolean expression>)` within a boolean expression.

`\bool_xor_p:nn` ★

Updated: 2012-07-08

`\bool_xor_p:nn {<boolexp1>} {<boolexp2>}`

Implements an “exclusive or” operation between two boolean expressions. There is no infix operation for this logical operator.

4 Logical loops

Loops using either boolean expressions or stored boolean values.

`\bool_do_until:Nn` ★

`\bool_do_until:cn` ★

`\bool_do_until:Nn <boolean> {<code>}`

Places the `<code>` in the input stream for T_EX to process, and then checks the logical value of the `<boolean>`. If it is `false` then the `<code>` will be inserted into the input stream again and the process will loop until the `<boolean>` is `true`.

`\bool_do_while:Nn` ★

`\bool_do_while:cn` ★

`\bool_do_while:Nn <boolean> {<code>}`

Places the `<code>` in the input stream for T_EX to process, and then checks the logical value of the `<boolean>`. If it is `true` then the `<code>` will be inserted into the input stream again and the process will loop until the `<boolean>` is `false`.

`\bool_until_do:Nn` ★

`\bool_until_do:cn` ★

`\bool_until_do:Nn <boolean> {<code>}`

This function firsts checks the logical value of the `<boolean>`. If it is `false` the `<code>` is placed in the input stream and expanded. After the completion of the `<code>` the truth of the `<boolean>` is re-evaluated. The process will then loop until the `<boolean>` is `true`.

`\bool_while_do:Nn` ★

`\bool_while_do:cn` ★

`\bool_while_do:Nn <boolean> {<code>}`

This function firsts checks the logical value of the `<boolean>`. If it is `true` the `<code>` is placed in the input stream and expanded. After the completion of the `<code>` the truth of the `<boolean>` is re-evaluated. The process will then loop until the `<boolean>` is `false`.

`\bool_do_until:nn` ★

Updated: 2012-07-08

`\bool_do_until:nn {<boolean expression>} {<code>}`

Places the `<code>` in the input stream for T_EX to process, and then checks the logical value of the `<boolean expression>` as described for `\bool_if:nTF`. If it is `false` then the `<code>` will be inserted into the input stream again and the process will loop until the `<boolean expression>` evaluates to `true`.

`\bool_do_while:nn` ★

Updated: 2012-07-08

`\bool_do_while:nn {<boolean expression>} {<code>}`

Places the `<code>` in the input stream for T_EX to process, and then checks the logical value of the `<boolean expression>` as described for `\bool_if:nTF`. If it is `true` then the `<code>` will be inserted into the input stream again and the process will loop until the `<boolean expression>` evaluates to `false`.

\bool_until_do:nn ☆

Updated: 2012-07-08

\bool_until_do:nn {*boolean expression*} {*code*}

This function firsts checks the logical value of the *boolean expression* (as described for \bool_if:nTF). If it is **false** the *code* is placed in the input stream and expanded. After the completion of the *code* the truth of the *boolean expression* is re-evaluated. The process will then loop until the *boolean expression* is **true**.

\bool_while_do:nn ☆

Updated: 2012-07-08

\bool_while_do:nn {*boolean expression*} {*code*}

This function firsts checks the logical value of the *boolean expression* (as described for \bool_if:nTF). If it is **true** the *code* is placed in the input stream and expanded. After the completion of the *code* the truth of the *boolean expression* is re-evaluated. The process will then loop until the *boolean expression* is **false**.

5 Producing n copies

\prg_replicate:nn ☆

Updated: 2011-07-04

\prg_replicate:nn {*integer expression*} {*tokens*}

Evaluates the *integer expression* (which should be zero or positive) and creates the resulting number of copies of the *tokens*. The function is both expandable and safe for nesting. It yields its result after two expansion steps.

6 Detecting T_EX's mode

\mode_if_horizontal_p: ☆

\mode_if_horizontal:TF ☆

\mode_if_horizontal_p:

\mode_if_horizontal:TF {*true code*} {*false code*}

Detects if T_EX is currently in horizontal mode.

\mode_if_inner_p: ☆

\mode_if_inner:TF ☆

\mode_if_inner_p:

\mode_if_inner:TF {*true code*} {*false code*}

Detects if T_EX is currently in inner mode.

\mode_if_math_p: ☆

\mode_if_math:TF ☆

Updated: 2011-09-05

\mode_if_math:TF {*true code*} {*false code*}

Detects if T_EX is currently in maths mode.

\mode_if_vertical_p: ☆

\mode_if_vertical:TF ☆

\mode_if_vertical_p:

\mode_if_vertical:TF {*true code*} {*false code*}

Detects if T_EX is currently in vertical mode.

7 Primitive conditionals

\if_predicate:w *

\if_predicate:w *(predicate)* *(true code)* \else: *(false code)* \fi:

This function takes a predicate function and branches according to the result. (In practice this function would also accept a single boolean variable in place of the *(predicate)* but to make the coding clearer this should be done through \if_bool:N.)

\if_bool:N *

\if_bool:N *(boolean)* *(true code)* \else: *(false code)* \fi:

This function takes a boolean variable and branches according to the result.

8 Internal programming functions

\group_align_safe_begin: *

\group_align_safe_end: *

Updated: 2011-08-11

\group_align_safe_begin:

...

\group_align_safe_end:

These functions are used to enclose material in a TeX alignment environment within a specially-constructed group. This group is designed in such a way that it does not add brace groups to the output but does act as a group for the & token inside \halign. This is necessary to allow grabbing of tokens for testing purposes, as TeX uses group level to determine the effect of alignment tokens. Without the special grouping, the use of a function such as \peek_after:Nw will result in a forbidden comparison of the internal \endtemplate token, yielding a fatal error. Each \group_align_safe_begin: must be matched by a \group_align_safe_end:, although this does not have to occur within the same function.

\scan_align_safe_stop:

Updated: 2011-09-06

\scan_align_safe_stop:

Stops TeX's scanner looking for expandable control sequences at the beginning of an alignment cell. This function is required, for example, to obtain the expected output when testing \mode_if_math:TF at the start of a math array cell: placing \scan_align_safe_stop: before \mode_if_math:TF will give the correct result. This function does not destroy any kerning if used in other locations, but *does* render functions non-expandable.

TeXhackers note: This is a protected version of \prg_do_nothing:, which therefore stops TeX's scanner in the circumstances described without producing any affect on the output.

_prg_variable_get_scope:N * _prg_variable_get_scope:N *(variable)*

Returns the scope (g for global, blank otherwise) for the *(variable)*.

_prg_variable_get_type:N * _prg_variable_get_type:N *(variable)*

Returns the type of *(variable)* (tl, int, etc.)

<u>__prg_break_point:Nn</u> *	<pre>__prg_break_point:Nn \<type>_map_break: <tokens></pre> <p>Used to mark the end of a recursion or mapping: the functions <code>\<type>_map_break:</code> and <code>\<type>_map_break:n</code> use this to break out of the loop. After the loop ends, the <code><tokens></code> are inserted into the input stream. This occurs even if the the break functions are <i>not</i> applied: <code>__prg_break_point:Nn</code> is functionally-equivalent in these cases to <code>\use_if:nn</code>.</p>
<u>__prg_map_break:Nn</u> *	<pre>__prg_map_break:Nn \<type>_map_break: {<user code>}</pre> \dots <pre>__prg_break_point:Nn \<type>_map_break: {<ending code>}</pre> <p>Breaks a recursion in mapping contexts, inserting in the input stream the <code><user code></code> after the <code><ending code></code> for the loop. The function breaks loops, inserting their <code><ending code></code>, until reaching a loop with the same <code><type></code> as its first argument. This <code>\<type>-map_break:</code> argument is simply used as a recognizable marker for the <code><type></code>.</p>
<u>\g__prg_map_int</u>	<p>This integer is used by non-expandable mapping functions to track the level of nesting in force. The functions <code>__prg_map_1:w</code>, <code>__prg_map_2:w</code>, <i>etc.</i>, labelled by <code>\g__prg_map_int</code> hold functions to be mapped over various list datatypes in inline and variable mappings.</p>
<u>__prg_break_point:</u> *	<p>This copy of <code>\prg_do_nothing:</code> is used to mark the end of a fast short-term recursions: the function <code>__prg_break:n</code> uses this to break out of the loop.</p>
<u>__prg_break:</u> *	$__prg_break:n \{<tokens>\} \dots __prg_break_point:$
<u>__prg_break:n</u> *	<p>Breaks a recursion which has no <code><ending code></code> and which is not a user-breakable mapping (see for instance <code>\prop_get:Nn</code>), and inserts <code><tokens></code> in the input stream.</p>

Part VII

The **I3quark** package

Quarks

1 Introduction to quarks and scan marks

Two special types of constants in L^AT_EX3 are “quarks” and “scan marks”. By convention all constants of type quark start out with `\q_`, and scan marks start with `\s_`. Scan marks are for internal use by the kernel: they are not intended for more general use.

1.1 Quarks

Quarks are control sequences that expand to themselves and should therefore *never* be executed directly in the code. This would result in an endless loop!

They are meant to be used as delimiter in weird functions, with the most common use case as the ‘stop token’ (*i.e.* `\q_stop`). For example, when writing a macro to parse a user-defined date

```
\date_parse:n {19/June/1981}
```

one might write a command such as

```
\cs_new:Npn \date_parse:n #1 { \date_parse_aux:w #1 \q_stop }
\cs_new:Npn \date_parse_aux:w #1 / #2 / #3 \q_stop
{ <do something with the date> }
```

Quarks are sometimes also used as error return values for functions that receive erroneous input. For example, in the function `\prop_get:NnN` to retrieve a value stored in some key of a property list, if the key does not exist then the return value is the quark `\q_no_value`. As mentioned above, such quarks are extremely fragile and it is imperative when using such functions that code is carefully written to check for pathological cases to avoid leakage of a quark into an uncontrolled environment.

Quarks also permit the following ingenious trick when parsing tokens: when you pick up a token in a temporary variable and you want to know whether you have picked up a particular quark, all you have to do is compare the temporary variable to the quark using `\tl_if_eq:NNTF`. A set of special quark testing functions is set up below. All the quark testing functions are expandable although the ones testing only single tokens are much faster. An example of the quark testing functions and their use in recursion can be seen in the implementation of `\clist_map_function:NN`.

2 Defining quarks

\quark_new:N *(quark)*

Creates a new *(quark)* which expands only to *(quark)*. The *(quark)* will be defined globally, and an error message will be raised if the name was already taken.

\q_stop Used as a marker for delimited arguments, such as

```
\cs_set:Npn \tmp:w #1#2 \q_stop {#1}
```

\q_mark Used as a marker for delimited arguments when **\q_stop** is already in use.

Quark to mark a null value in structured variables or functions. Used as an end delimiter when this may itself may need to be tested (in contrast to **\q_stop**, which is only ever used as a delimiter).

\q_no_value A canonical value for a missing value, when one is requested from a data structure. This is therefore used as a “return” value by functions such as **\prop_get:NnN** if there is no data to return.

3 Quark tests

The method used to define quarks means that the single token (**N**) tests are faster than the multi-token (**n**) tests. The later should therefore only be used when the argument can definitely take more than a single token.

\quark_if_nil_p:N * *\quark_if_nil_p:N* *(token)*
\quark_if_nil:nTF * *\quark_if_nil:nTF* *(token)* {*true code*} {*false code*}

Tests if the *(token)* is equal to **\q_nil**.

\quark_if_nil_p:n * *\quark_if_nil_p:n* {*token list*}
\quark_if_nil_p:(o|V) * *\quark_if_nil_p:(o|V)* {*token list*} {*true code*} {*false code*}
\quark_if_nil:nTF * *\quark_if_nil:nTF* {*token list*} {*true code*} {*false code*}
\quark_if_nil:(o|V)TF * Tests if the *(token list)* contains only **\q_nil** (distinct from *(token list)* being empty or containing **\q_nil** plus one or more other tokens).

\quark_if_no_value_p:N * *\quark_if_no_value_p:N* *(token)*
\quark_if_no_value_p:c * *\quark_if_no_value:c* *(token)* {*true code*} {*false code*}
\quark_if_no_value:nTF * *\quark_if_no_value:nTF* {*token list*} {*true code*} {*false code*}
\quark_if_no_value:cTF * Tests if the *(token)* is equal to **\q_no_value**.

\quark_if_no_value_p:n * *\quark_if_no_value_p:n* {*token list*}
\quark_if_no_value:nTF * *\quark_if_no_value:nTF* {*token list*} {*true code*} {*false code*}
Tests if the *(token list)* contains only **\q_no_value** (distinct from *(token list)* being empty or containing **\q_no_value** plus one or more other tokens).

4 Recursion

This module provides a uniform interface to intercepting and terminating loops as when one is doing tail recursion. The building blocks follow below and an example is shown in Section 6.

/q_recursion_tail

This quark is appended to the data structure in question and appears as a real element there. This means it gets any list separators around it. Can you guess why the documentation for this quark requires us to write the control sequence with the wrong slash before it?

\q_recursion_stop

This quark is added *after* the data structure. Its purpose is to make it possible to terminate the recursion at any point easily.

\quark_if_recursion_tail_stop:N \quark_if_recursion_tail_stop:N <token>

Tests if *<token>* contains only the marker \q_recursion_tail, and if so terminates the recursion this is part of using \use_none_delimit_by_q_recursion_stop:w. The recursion input must include the marker tokens \q_recursion_tail and \q_recursion_stop as the last two items.

\quark_if_recursion_tail_stop:n \quark_if_recursion_tail_stop:n {<token list>}

\quark_if_recursion_tail_stop:o

Updated: 2011-09-06

Tests if the *<token list>* contains only \q_recursion_tail, and if so terminates the recursion this is part of using \use_none_delimit_by_q_recursion_stop:w. The recursion input must include the marker tokens \q_recursion_tail and \q_recursion_stop as the last two items.

\quark_if_recursion_tail_stop_do:Nn \quark_if_recursion_tail_stop_do:Nn <token> {<insertion>}

Tests if *<token>* contains only the marker \q_recursion_tail, and if so terminates the recursion this is part of using \use_none_delimit_by_q_recursion_stop:w. The recursion input must include the marker tokens \q_recursion_tail and \q_recursion_stop as the last two items. The *<insertion>* code is then added to the input stream after the recursion has ended.

\quark_if_recursion_tail_stop_do:nn \quark_if_recursion_tail_stop_do:nn {<token list>} {<insertion>}

\quark_if_recursion_tail_stop_do:on

Updated: 2011-09-06

Tests if the *<token list>* contains only \q_recursion_tail, and if so terminates the recursion this is part of using \use_none_delimit_by_q_recursion_stop:w. The recursion input must include the marker tokens \q_recursion_tail and \q_recursion_stop as the last two items. The *<insertion>* code is then added to the input stream after the recursion has ended.

5 Clearing quarks away

```
\use_none_delimit_by_q_recursion_stop:w \use_none_delimit_by_q_recursion_stop:w <tokens>
\q_recursion_stop
```

Used to prematurely terminate a recursion using `\q_recursion_stop` as the end marker, removing any remaining `<tokens>` from the input stream.

```
\use_i_delimit_by_q_recursion_stop:nw \use_i_delimit_by_q_recursion_stop:nw {<insertion>}
<tokens> \q_recursion_stop
```

Used to prematurely terminate a recursion using `\q_recursion_stop` as the end marker, removing any remaining `<tokens>` from the input stream. The `<insertion>` is then made into the input stream after the end of the recursion.

6 An example of recursion with quarks

Quarks are mainly used internally in the `expl3` code to define recursion functions such as `\tl_map_inline:nn` and so on. Here is a small example to demonstrate how to use quarks in this fashion. We shall define a command called `\my_map dbl:nn` which takes a token list and applies an operation to every *pair* of tokens. For example, `\my_map dbl:nn {abcd} {[--#1--#2--]~}` would produce “[a-b] [-c-d]”. Using quarks to define such functions simplifies their logic and ensures robustness in many cases.

Here's the definition of `\my_map dbl:nn`. First of all, define the function that will do the processing based on the inline function argument #2. Then initiate the recursion using an internal function. The token list #1 is terminated using `\q_recursion_tail`, with delimiters according to the type of recursion (here a pair of `\q_recursion_tail`), concluding with `\q_recursion_stop`. These quarks are used to mark the end of the token list being operated upon.

```
1 \cs_new:Npn \my_map dbl:nn #1#2
2   {
3     \cs_set:Npn \__my_map dbl_fn:nn ##1 ##2 {#2}
4     \__my_map dbl:nn #1 \q_recursion_tail \q_recursion_tail \q_recursion_stop
5   }
```

The definition of the internal recursion function follows. First check if either of the input tokens are the termination quarks. Then, if not, apply the inline function to the two arguments.

```
6 \cs_new:Nn \__my_map dbl:nn
7   {
8     \quark_if_recursion_tail_stop:n {#1}
9     \quark_if_recursion_tail_stop:n {#2}
10    \__my_map dbl_fn:nn {#1} {#2}
```

Finally, recurse:

```
11   \__my_map dbl:nn
12 }
```

Note that contrarily to L^AT_EX3 built-in mapping functions, this mapping function cannot be nested, since the second map will overwrite the definition of `__my_map dbl fn:nn`.

7 Internal quark functions

`__quark_if_recursion_tail_break:NN` `__quark_if_recursion_tail_break:nN {<token list>}`
`__quark_if_recursion_tail_break:nN` `\langle type\rangle_map_break:`

Tests if *<token list>* contains only `\q_recursion_tail`, and if so terminates the recursion using `\langle type\rangle_map_break:`. The recursion end should be marked by `\prg_break_point:Nn \langle type\rangle_map_break:`.

8 Scan marks

Scan marks are control sequences set equal to `\scan_stop:`, hence will never expand in an expansion context and will be (largely) invisible if they are encountered in a typesetting context.

Like quarks, they can be used as delimiters in weird functions and are often safer to use for this purpose. Since they are harmless when executed by T_EX in non-expandable contexts, they can be used to mark the end of a set of instructions. This allows to skip to that point if the end of the instructions should not be performed (see l3regex).

The scan marks system is only for internal use by the kernel team in a small number of very specific places. These functions should not be used more generally.

`__scan_new:N` `__scan_new:N <scan mark>`

Creates a new *<scan mark>* which is set equal to `\scan_stop:`. The *<scan mark>* will be defined globally, and an error message will be raised if the name was already taken by another scan mark.

`\s_stop` Used at the end of a set of instructions, as a marker that can be jumped to using `__use_none_delimit_by_s_stop:w`.

`__use_none_delimit_by_s_stop:w` `__use_none_delimit_by_s_stop:w <tokens> \s_stop`

Removes the *<tokens>* and `\s_stop` from the input stream. This leads to a low-level T_EX error if `\s_stop` is absent.

Part VIII

The `I3token` package

Token manipulation

This module deals with tokens. Now this is perhaps not the most precise description so let's try with a better description: When programming in `TeX`, it is often desirable to know just what a certain token is: is it a control sequence or something else. Similarly one often needs to know if a control sequence is expandable or not, a macro or a primitive, how many arguments it takes etc. Another thing of great importance (especially when it comes to document commands) is looking ahead in the token stream to see if a certain character is present and maybe even remove it or disregard other tokens while scanning. This module provides functions for both and as such will have two primary function categories: `\token_` for anything that deals with tokens and `\peek_` for looking ahead in the token stream.

Most of the time we will be using the term “token” but most of the time the function we're describing can equally well be used on a control sequence as such one is one token as well.

We shall refer to lists of tokens as `tlists` and such lists represented by a single control sequence is a “token list variable” `tl var`. Functions for these two types are found in the `I3tl` module.

1 All possible tokens

Let us start by reviewing every case that a given token can fall into. It is very important to distinguish two aspects of a token: its meaning, and what it looks like.

For instance, `\if:w`, `\if_charcode:w`, and `\tex_if:D` are three for the same internal operation of `TeX`, namely the primitive testing the next two characters for equality of their character code. They behave identically in many situations. However, `TeX` distinguishes them when searching for a delimited argument. Namely, the example function `\show_until_if:w` defined below will take everything until `\if:w` as an argument, despite the presence of other copies of `\if:w` under different names.

```
\cs_new:Npn \show_until_if:w #1 \if:w { \tl_show:n {#1} }
\show_until_if:w \tex_if:D \if_charcode:w \if:w
```

2 Character tokens

\char_set_catcode_escape:N	\char_set_catcode_letter:N <i>(character)</i>
\char_set_catcode_group_begin:N	
\char_set_catcode_group_end:N	
\char_set_catcode_math_toggle:N	
\char_set_catcode_alignment:N	
\char_set_catcode_end_line:N	
\char_set_catcode_parameter:N	
\char_set_catcode_math_superscript:N	
\char_set_catcode_math_subscript:N	
\char_set_catcode_ignore:N	
\char_set_catcode_space:N	
\char_set_catcode_letter:N	
\char_set_catcode_other:N	
\char_set_catcode_active:N	
\char_set_catcode_comment:N	
\char_set_catcode_invalid:N	

Sets the category code of the *(character)* to that indicated in the function name. Depending on the current category code of the *(token)* the escape token may also be needed:

\char_set_catcode_other:N \%

The assignment is local.

\char_set_catcode_escape:n	\char_set_catcode_letter:n { <i>(integer expression)</i> }
\char_set_catcode_group_begin:n	
\char_set_catcode_group_end:n	
\char_set_catcode_math_toggle:n	
\char_set_catcode_alignment:n	
\char_set_catcode_end_line:n	
\char_set_catcode_parameter:n	
\char_set_catcode_math_superscript:n	
\char_set_catcode_math_subscript:n	
\char_set_catcode_ignore:n	
\char_set_catcode_space:n	
\char_set_catcode_letter:n	
\char_set_catcode_other:n	
\char_set_catcode_active:n	
\char_set_catcode_comment:n	
\char_set_catcode_invalid:n	

Sets the category code of the *(character)* which has character code as given by the *(integer expression)*. This version can be used to set up characters which cannot otherwise be given (*cf.* the N-type variants). The assignment is local.

\char_set_catcode:nn

```
\char_set_catcode:nn {\langle intexpr1\rangle} {\langle intexpr2\rangle}
```

These functions set the category code of the *character* which has character code as given by the *integer expression*. The first *integer expression* is the character code and the second is the category code to apply. The setting applies within the current TeX group. In general, the symbolic functions `\char_set_catcode_<type>` should be preferred, but there are cases where these lower-level functions may be useful.

\char_value_catcode:n *

```
\char_value_catcode:n {\langle integer expression\rangle}
```

Expands to the current category code of the *character* with character code given by the *integer expression*.

\char_show_value_catcode:n

```
\char_show_value_catcode:n {\langle integer expression\rangle}
```

Displays the current category code of the *character* with character code given by the *integer expression* on the terminal.

\char_set_lccode:nn

```
\char_set_lccode:nn {\langle intexpr1\rangle} {\langle intexpr2\rangle}
```

This function set up the behaviour of *character* when found inside `\tl_to_lowercase:n`, such that *character₁* will be converted into *character₂*. The two *characters* may be specified using an *integer expression* for the character code concerned. This may include the TeX ‘*character*’ method for converting a single character into its character code:

```
\char_set_lccode:nn { '\A } { '\a } % Standard behaviour  
\char_set_lccode:nn { '\A } { '\A + 32 }  
\char_set_lccode:nn { 50 } { 60 }
```

The setting applies within the current TeX group.

\char_value_lccode:n *

```
\char_value_lccode:n {\langle integer expression\rangle}
```

Expands to the current lower case code of the *character* with character code given by the *integer expression*.

\char_show_value_lccode:n

```
\char_show_value_lccode:n {\langle integer expression\rangle}
```

Displays the current lower case code of the *character* with character code given by the *integer expression* on the terminal.

`\char_set_uccode:nn`

This function set up the behaviour of *<character>* when found inside `\tl_to_uppercase:n`, such that *<character₁>* will be converted into *<character₂>*. The two *<characters>* may be specified using an *<integer expression>* for the character code concerned. This may include the TeX ‘*<character>*’ method for converting a single character into its character code:

```
\char_set_uccode:nn { '\a } { '\A } % Standard behaviour
\char_set_uccode:nn { '\A } { '\A - 32 }
\char_set_uccode:nn { 60 } { 50 }
```

The setting applies within the current TeX group.

`\char_value_uccode:n *`

`\char_value_uccode:n {<integer expression>}`

Expands to the current upper case code of the *<character>* with character code given by the *<integer expression>*.

`\char_show_value_uccode:n`

`\char_show_value_uccode:n {<integer expression>}`

Displays the current upper case code of the *<character>* with character code given by the *<integer expression>* on the terminal.

`\char_set_mathcode:nn`

`\char_set_mathcode:nn {<integer>} {<integer>}`

This function sets up the math code of *<character>*. The *<character>* is specified as an *<integer expression>* which will be used as the character code of the relevant character. The setting applies within the current TeX group.

`\char_value_mathcode:n *`

`\char_value_mathcode:n {<integer expression>}`

Expands to the current math code of the *<character>* with character code given by the *<integer expression>*.

`\char_show_value_mathcode:n`

`\char_show_value_mathcode:n {<integer expression>}`

Displays the current math code of the *<character>* with character code given by the *<integer expression>* on the terminal.

`\char_set_sfcode:nn`

`\char_set_sfcode:nn {<integer>} {<integer>}`

This function sets up the space factor for the *<character>*. The *<character>* is specified as an *<integer expression>* which will be used as the character code of the relevant character. The setting applies within the current TeX group.

`\char_value_sfcode:n *`

`\char_value_sfcode:n {<integer expression>}`

Expands to the current space factor for the *<character>* with character code given by the *<integer expression>*.

`\char_show_value_sfcode:n`

`\char_show_value_sfcode:n {<integer expression>}`

Displays the current space factor for the *<character>* with character code given by the *<integer expression>* on the terminal.

`\l_char_active_seq`

New: 2012-01-23

Used to track which tokens will require special handling at the document level as they are of category *<active>* (catcode 13). Each entry in the sequence consists of a single active character. Active tokens should be added to the sequence when they are defined for general document use.

`\l_char_special_seq`

New: 2012-01-23

Used to track which tokens will require special handling when working with verbatim-like material at the document level as they are not of categories *<letter>* (catcode 11) or *<other>* (catcode 12). Each entry in the sequence consists of a single escaped token, for example `\\"` for the backslash or `\{` for an opening brace. Escaped tokens should be added to the sequence when they are defined for general document use.

3 Generic tokens

`\token_new:Nn`

`\token_new:Nn <token1> {<token2>}`

Defines *<token₁>* to globally be a snapshot of *<token₂>*. This will be an implicit representation of *<token₂>*.

`\c_group_begin_token`
`\c_group_end_token`
`\c_math_toggle_token`
`\c_alignment_token`
`\c_parameter_token`
`\c_math_superscript_token`
`\c_math_subscript_token`
`\c_space_token`

These are implicit tokens which have the category code described by their name. They are used internally for test purposes but are also available to the programmer for other uses.

`\c_catcode_letter_token`
`\c_catcode_other_token`

These are implicit tokens which have the category code described by their name. They are used internally for test purposes and should not be used other than for category code tests.

`\c_catcode_active_tl`

A token list containing an active token. This is used internally for test purposes and should not be used other than in appropriately-constructed category code tests.

4 Converting tokens

<code>\token_to_meaning:N *</code>	<code>\token_to_meaning:N <token></code>
<code>\token_to_meaning:c *</code>	Inserts the current meaning of the <code><token></code> into the input stream as a series of characters of category code 12 (other). This will be the primitive TeX description of the <code><token></code> , thus for example both functions defined by <code>\cs_set_nopar:Npn</code> and token list variables defined using <code>\tl_new:N</code> will be described as macros .

TeXhackers note: This is the TeX primitive `\meaning`.

<code>\token_to_str:N *</code>	<code>\token_to_str:N <token></code>
<code>\token_to_str:c *</code>	Converts the given <code><token></code> into a series of characters with category code 12 (other). The current escape character will be the first character in the sequence, although this will also have category code 12 (the escape character is part of the <code><token></code>). This function requires only a single expansion.

TeXhackers note: `\token_to_str:N` is the TeX primitive `\string` renamed.

5 Token conditionals

<code>\token_if_group_begin_p:N *</code>	<code>\token_if_group_begin_p:N <token></code>
<code>\token_if_group_begin:NTF *</code>	<code>\token_if_group_begin:NTF <token> {<true code>} {<false code>}</code>

Tests if `<token>` has the category code of a begin group token (`{` when normal TeX category codes are in force). Note that an explicit begin group token cannot be tested in this way, as it is not a valid N-type argument.

<code>\token_if_group_end_p:N *</code>	<code>\token_if_group_end_p:N <token></code>
<code>\token_if_group_end:NTF *</code>	<code>\token_if_group_end:NTF <token> {<true code>} {<false code>}</code>

Tests if `<token>` has the category code of an end group token (`}` when normal TeX category codes are in force). Note that an explicit end group token cannot be tested in this way, as it is not a valid N-type argument.

<code>\token_if_math_toggle_p:N *</code>	<code>\token_if_math_toggle_p:N <token></code>
<code>\token_if_math_toggle:NTF *</code>	<code>\token_if_math_toggle:NTF <token> {<true code>} {<false code>}</code>

Tests if `<token>` has the category code of a math shift token (`$` when normal TeX category codes are in force).

<code>\token_if_alignment_p:N *</code>	<code>\token_if_alignment_p:N <token></code>
<code>\token_if_alignment:NTF *</code>	<code>\token_if_alignment:NTF <token> {<true code>} {<false code>}</code>

Tests if `<token>` has the category code of an alignment token (`&` when normal TeX category codes are in force).

<code>\token_if_parameter_p:N *</code>	<code>\token_if_parameter_p:N <token></code>
<code>\token_if_parameter:NTF *</code>	<code>\token_if_alignment:NTF <token> {\{true code\}} {\{false code\}}</code>
Tests if $\langle token \rangle$ has the category code of a macro parameter token (# when normal TeX category codes are in force).	
<code>\token_if_math_superscript_p:N *</code>	<code>\token_if_math_superscript_p:N <token></code>
<code>\token_if_math_superscript:NTF *</code>	<code>\token_if_math_superscript:NTF <token> {\{true code\}} {\{false code\}}</code>
Tests if $\langle token \rangle$ has the category code of a superscript token (^ when normal TeX category codes are in force).	
<code>\token_if_math_subscript_p:N *</code>	<code>\token_if_math_subscript_p:N <token></code>
<code>\token_if_math_subscript:NTF *</code>	<code>\token_if_math_subscript:NTF <token> {\{true code\}} {\{false code\}}</code>
Tests if $\langle token \rangle$ has the category code of a subscript token (_) when normal TeX category codes are in force).	
<code>\token_if_space_p:N *</code>	<code>\token_if_space_p:N <token></code>
<code>\token_if_space:NTF *</code>	<code>\token_if_space:NTF <token> {\{true code\}} {\{false code\}}</code>
Tests if $\langle token \rangle$ has the category code of a space token. Note that an explicit space token with character code 32 cannot be tested in this way, as it is not a valid N-type argument.	
<code>\token_if_letter_p:N *</code>	<code>\token_if_letter_p:N <token></code>
<code>\token_if_letter:NTF *</code>	<code>\token_if_letter:NTF <token> {\{true code\}} {\{false code\}}</code>
Tests if $\langle token \rangle$ has the category code of a letter token.	
<code>\token_if_other_p:N *</code>	<code>\token_if_other_p:N <token></code>
<code>\token_if_other:NTF *</code>	<code>\token_if_other:NTF <token> {\{true code\}} {\{false code\}}</code>
Tests if $\langle token \rangle$ has the category code of an “other” token.	
<code>\token_if_active_p:N *</code>	<code>\token_if_active_p:N <token></code>
<code>\token_if_active:NTF *</code>	<code>\token_if_active:NTF <token> {\{true code\}} {\{false code\}}</code>
Tests if $\langle token \rangle$ has the category code of an active character.	
<code>\token_if_eq_catcode_p:NN *</code>	<code>\token_if_eq_catcode_p:NN <token₁> <token₂></code>
<code>\token_if_eq_catcode:NNTF *</code>	<code>\token_if_eq_catcode:NNTF <token₁> <token₂> {\{true code\}} {\{false code\}}</code>
Tests if the two $\langle tokens \rangle$ have the same category code.	
<code>\token_if_eq_charcode_p:NN *</code>	<code>\token_if_eq_charcode_p:NN <token₁> <token₂></code>
<code>\token_if_eq_charcode:NNTF *</code>	<code>\token_if_eq_charcode:NNTF <token₁> <token₂> {\{true code\}} {\{false code\}}</code>
Tests if the two $\langle tokens \rangle$ have the same character code.	

```
\token_if_eq_meaning_p:NN ★ \token_if_eq_meaning_p>NN <token1> <token2>
\token_if_eq_meaning:NNTF ★ \token_if_eq_meaning:NNTF <token1> <token2> {{true code}} {{false code}}
```

Tests if the two *<tokens>* have the same meaning when expanded.

```
\token_if_macro_p:N ★ \token_if_macro_p:N <token>
\token_if_macro:NTF ★ \token_if_macro:NTF <token> {{true code}} {{false code}}
```

Updated: 2011-05-23

Tests if the *<token>* is a TeX macro.

```
\token_if_cs_p:N ★ \token_if_cs_p:N <token>
\token_if_cs:NTF ★ \token_if_cs:NTF <token> {{true code}} {{false code}}
```

Tests if the *<token>* is a control sequence.

```
\token_if_expandable_p:N ★ \token_if_expandable_p:N <token>
\token_if_expandable:NTF ★ \token_if_expandable:NTF <token> {{true code}} {{false code}}
```

Tests if the *<token>* is expandable. This test returns *false* for an undefined token.

```
\token_if_long_macro_p:N ★ \token_if_long_macro_p:N <token>
\token_if_long_macro:NTF ★ \token_if_long_macro:NTF <token> {{true code}} {{false code}}
```

Updated: 2012-01-20

Tests if the *<token>* is a long macro.

```
\token_if_protected_macro_p:N ★ \token_if_protected_macro_p:N <token>
\token_if_protected_macro:NTF ★ \token_if_protected_macro:NTF <token> {{true code}} {{false code}}
```

Updated: 2012-01-20

Tests if the *<token>* is a protected macro: a macro which is both protected and long will return logical *false*.

```
\token_if_protected_long_macro_p:N ★ \token_if_protected_long_macro_p:N <token>
\token_if_protected_long_macro:NTF ★ \token_if_protected_long_macro:NTF <token> {{true code}} {{false code}}
```

Updated: 2012-01-20

Tests if the *<token>* is a protected long macro.

```
\token_if_chardef_p:N ★ \token_if_chardef_p:N <token>
\token_if_chardef:NTF ★ \token_if_chardef:NTF <token> {{true code}} {{false code}}
```

Updated: 2012-01-20

Tests if the *<token>* is defined to be a chardef.

TeXhackers note: Booleans, boxes and small integer constants are implemented as chardefs.

```
\token_if_mathchardef_p:N ★ \token_if_mathchardef_p:N ⟨token⟩  
\token_if_mathchardef:NTF ★ \token_if_mathchardef:NTF ⟨token⟩ {⟨true code⟩} {⟨false code⟩}
```

Updated: 2012-01-20

Tests if the ⟨token⟩ is defined to be a mathchardef.

```
\token_if_dim_register_p:N ★ \token_if_dim_register_p:N ⟨token⟩  
\token_if_dim_register:NTF ★ \token_if_dim_register:NTF ⟨token⟩ {⟨true code⟩} {⟨false code⟩}
```

Updated: 2012-01-20

Tests if the ⟨token⟩ is defined to be a dimension register.

```
\token_if_int_register_p:N ★ \token_if_int_register_p:N ⟨token⟩  
\token_if_int_register:NTF ★ \token_if_int_register:NTF ⟨token⟩ {⟨true code⟩} {⟨false code⟩}
```

Updated: 2012-01-20

Tests if the ⟨token⟩ is defined to be a integer register.

TeXhackers note: Constant integers may be implemented as integer registers, chardefs, or mathchardefs depending on their value.

```
\token_if_muskip_register_p:N ★ \token_if_muskip_register_p:N ⟨token⟩  
\token_if_muskip_register:NTF ★ \token_if_muskip_register:NTF ⟨token⟩ {⟨true code⟩} {⟨false code⟩}
```

New: 2012-02-15

Tests if the ⟨token⟩ is defined to be a muskip register.

```
\token_if_skip_register_p:N ★ \token_if_skip_register_p:N ⟨token⟩  
\token_if_skip_register:NTF ★ \token_if_skip_register:NTF ⟨token⟩ {⟨true code⟩} {⟨false code⟩}
```

Updated: 2012-01-20

Tests if the ⟨token⟩ is defined to be a skip register.

```
\token_if_toks_register_p:N ★ \token_if_toks_register_p:N ⟨token⟩  
\token_if_toks_register:NTF ★ \token_if_toks_register:NTF ⟨token⟩ {⟨true code⟩} {⟨false code⟩}
```

Updated: 2012-01-20

Tests if the ⟨token⟩ is defined to be a toks register (not used by LATEX3).

```
\token_if_primitive_p:N ★ \token_if_primitive_p:N ⟨token⟩  
\token_if_primitive:NTF ★ \token_if_primitive:NTF ⟨token⟩ {⟨true code⟩} {⟨false code⟩}
```

Updated: 2011-05-23

Tests if the ⟨token⟩ is an engine primitive.

6 Peeking ahead at the next token

There is often a need to look ahead at the next token in the input stream while leaving it in place. This is handled using the “peek” functions. The generic `\peek_after:Nw` is provided along with a family of predefined tests for common cases. As peeking ahead does *not* skip spaces the predefined tests include both a space-respecting and space-skipping version.

`\peek_after:Nw`

`\peek_after:Nw <function> <token>`

Locally sets the test variable `\l_peek_token` equal to `<token>` (as an implicit token, *not* as a token list), and then expands the `<function>`. The `<token>` will remain in the input stream as the next item after the `<function>`. The `<token>` here may be `\`, `{` or `}` (assuming normal TeX category codes), *i.e.* it is not necessarily the next argument which would be grabbed by a normal function.

`\peek_gafter:Nw`

`\peek_gafter:Nw <function> <token>`

Globally sets the test variable `\g_peek_token` equal to `<token>` (as an implicit token, *not* as a token list), and then expands the `<function>`. The `<token>` will remain in the input stream as the next item after the `<function>`. The `<token>` here may be `\`, `{` or `}` (assuming normal TeX category codes), *i.e.* it is not necessarily the next argument which would be grabbed by a normal function.

`\l_peek_token`

Token set by `\peek_after:Nw` and available for testing as described above.

`\g_peek_token`

Token set by `\peek_gafter:Nw` and available for testing as described above.

`\peek_catcode:NTF`

Updated: 2011-07-02

`\peek_catcode:NTF <test token> {{true code}} {{false code}}`

Tests if the next `<token>` in the input stream has the same category code as the `<test token>` (as defined by the test `\token_if_eq_catcode:NNTF`). Spaces are respected by the test and the `<token>` will be left in the input stream after the `<true code>` or `<false code>` (as appropriate to the result of the test).

`\peek_catcode_ignore_spaces:NTF`

Updated: 2011-07-02

`\peek_catcode_ignore_spaces:NTF <test token> {{true code}} {{false code}}`

Tests if the next `<token>` in the input stream has the same category code as the `<test token>` (as defined by the test `\token_if_eq_catcode:NNTF`). Spaces are ignored by the test and the `<token>` will be left in the input stream after the `<true code>` or `<false code>` (as appropriate to the result of the test).

\peek_catcode_remove:NTF

Updated: 2011-07-02

```
\peek_catcode_remove:NTF {test token} {{true code}} {{false code}}
```

Tests if the next *token* in the input stream has the same category code as the *test token* (as defined by the test \token_if_eq_catcode:NNTF). Spaces are respected by the test and the *token* will be removed from the input stream if the test is true. The function will then place either the *true code* or *false code* in the input stream (as appropriate to the result of the test).

\peek_catcode_remove_ignore_spaces:NTF

Updated: 2011-07-02

```
\peek_catcode_remove_ignore_spaces:NTF {test token} {{true code}} {{false code}}
```

Tests if the next *token* in the input stream has the same category code as the *test token* (as defined by the test \token_if_eq_catcode:NNTF). Spaces are ignored by the test and the *token* will be removed from the input stream if the test is true. The function will then place either the *true code* or *false code* in the input stream (as appropriate to the result of the test).

\peek_charcode:NTF

Updated: 2011-07-02

```
\peek_charcode:NTF {test token} {{true code}} {{false code}}
```

Tests if the next *token* in the input stream has the same character code as the *test token* (as defined by the test \token_if_eq_charcode:NNTF). Spaces are respected by the test and the *token* will be left in the input stream after the *true code* or *false code* (as appropriate to the result of the test).

\peek_charcode_ignore_spaces:NTF

Updated: 2011-07-02

```
\peek_charcode_ignore_spaces:NTF {test token} {{true code}} {{false code}}
```

Tests if the next *token* in the input stream has the same character code as the *test token* (as defined by the test \token_if_eq_charcode:NNTF). Spaces are ignored by the test and the *token* will be left in the input stream after the *true code* or *false code* (as appropriate to the result of the test).

\peek_charcode_remove:NTF

Updated: 2011-07-02

```
\peek_charcode_remove:NTF {test token} {{true code}} {{false code}}
```

Tests if the next *token* in the input stream has the same character code as the *test token* (as defined by the test \token_if_eq_charcode:NNTF). Spaces are respected by the test and the *token* will be removed from the input stream if the test is true. The function will then place either the *true code* or *false code* in the input stream (as appropriate to the result of the test).

\peek_charcode_remove_ignore_spaces:NTF

Updated: 2011-07-02

```
\peek_charcode_remove_ignore_spaces:NTF {test token}
```

```
 {{true code}} {{false code}}
```

Tests if the next *token* in the input stream has the same character code as the *test token* (as defined by the test \token_if_eq_charcode:NNTF). Spaces are ignored by the test and the *token* will be removed from the input stream if the test is true. The function will then place either the *true code* or *false code* in the input stream (as appropriate to the result of the test).

`\peek_meaning:NTF`

Updated: 2011-07-02

`\peek_meaning:NTF {test token} {\{true code\}} {\{false code\}}`

Tests if the next *token* in the input stream has the same meaning as the *test token* (as defined by the test `\token_if_eq_meaning:NNTF`). Spaces are respected by the test and the *token* will be left in the input stream after the *true code* or *false code* (as appropriate to the result of the test).

`\peek_meaning_ignore_spaces:NTF`

Updated: 2011-07-02

`\peek_meaning_ignore_spaces:NTF {test token} {\{true code\}} {\{false code\}}`

Tests if the next *token* in the input stream has the same meaning as the *test token* (as defined by the test `\token_if_eq_meaning:NNTF`). Spaces are ignored by the test and the *token* will be left in the input stream after the *true code* or *false code* (as appropriate to the result of the test).

`\peek_meaning_remove:NTF`

Updated: 2011-07-02

`\peek_meaning_remove:NTF {test token} {\{true code\}} {\{false code\}}`

Tests if the next *token* in the input stream has the same meaning as the *test token* (as defined by the test `\token_if_eq_meaning:NNTF`). Spaces are respected by the test and the *token* will be removed from the input stream if the test is true. The function will then place either the *true code* or *false code* in the input stream (as appropriate to the result of the test).

`\peek_meaning_remove_ignore_spaces:NTF`

Updated: 2011-07-02

`\peek_meaning_remove_ignore_spaces:NTF {test token} {\{true code\}} {\{false code\}}`

Tests if the next *token* in the input stream has the same meaning as the *test token* (as defined by the test `\token_if_eq_meaning:NNTF`). Spaces are ignored by the test and the *token* will be removed from the input stream if the test is true. The function will then place either the *true code* or *false code* in the input stream (as appropriate to the result of the test).

7 Decomposing a macro definition

These functions decompose T_EX macros into their constituent parts: if the *token* passed is not a macro then no decomposition can occur. In the later case, all three functions leave `\scan_stop:` in the input stream.

\token_get_arg_spec:N *

`\token_get_arg_spec:N <token>`

If the `<token>` is a macro, this function will leave the primitive T_EX argument specification in input stream as a string of tokens of category code 12 (with spaces having category code 10). Thus for example for a token `\next` defined by

```
\cs_set:Npn \next #1#2 { x #1 y #2 }
```

will leave `#1#2` in the input stream. If the `<token>` is not a macro then `\scan_stop:` will be left in the input stream

T_EXhackers note: If the arg spec. contains the string `->`, then the `spec` function will produce incorrect results.

\token_get_replacement_spec:N *

`\token_get_replacement_spec:N <token>`

If the `<token>` is a macro, this function will leave the replacement text in input stream as a string of tokens of category code 12 (with spaces having category code 10). Thus for example for a token `\next` defined by

```
\cs_set:Npn \next #1#2 { x #1~y #2 }
```

will leave `x#1 y#2` in the input stream. If the `<token>` is not a macro then `\scan_stop:` will be left in the input stream

\token_get_prefix_spec:N *

`\token_get_prefix_spec:N <token>`

If the `<token>` is a macro, this function will leave the T_EX prefixes applicable in input stream as a string of tokens of category code 12 (with spaces having category code 10). Thus for example for a token `\next` defined by

```
\cs_set:Npn \next #1#2 { x #1~y #2 }
```

will leave `\long` in the input stream. If the `<token>` is not a macro then `\scan_stop:` will be left in the input stream

Part IX

The **I3int** package

Integers

Calculation and comparison of integer values can be carried out using literal numbers, `int` registers, constants and integers stored in token list variables. The standard operators `+`, `-`, `/` and `*` and parentheses can be used within such expressions to carry arithmetic operations. This module carries out these functions on *integer expressions* (“`intexpr`”).

1 Integer expressions

`\int_eval:n` *

`\int_eval:n {<integer expression>}`

Evaluates the *<integer expression>*, expanding any integer and token list variables within the *<expression>* to their content (without requiring `\int_use:N`/`\tl_use:N`) and applying the standard mathematical rules. For example both

```
\int_eval:n { 5 + 4 * 3 - ( 3 + 4 * 5 ) }
```

and

```
\tl_new:N \l_my_tl
\tl_set:Nn \l_my_tl { 5 }
\int_new:N \l_my_int
\int_set:Nn \l_my_int { 4 }
\int_eval:n { \l_my_tl + \l_my_int * 3 - ( 3 + 4 * 5 ) }
```

both evaluate to -6 . The `{<integer expression>}` may contain the operators `+`, `-`, `*` and `/`, along with parenthesis `(` and `)`. After two expansions, `\int_eval:n` yields an *<integer denotation>* which is left in the input stream. This is *not* an *<internal integer>*, and therefore requires suitable termination if used in a TeX-style integer assignment.

`\int_abs:n` *

Updated: 2012-09-26

`\int_abs:n {<integer expression>}`

Evaluates the *<integer expression>* as described for `\int_eval:n` and leaves the absolute value of the result in the input stream as an *<integer denotation>* after two expansions.

`\int_div_round:nn` *

Updated: 2012-09-26

`\int_div_round:nn {<intexpr1>} {<intexpr2>}`

Evaluates the two *<integer expressions>* as described earlier, then calculates the result of dividing the first value by the second, rounding any remainder. Ties are rounded away from zero. Note that this is identical to using `/` directly in an *<integer expression>*. The result is left in the input stream as an *<integer denotation>* after two expansions.

\int_div_truncate:nn *

Updated: 2012-02-09

\int_div_truncate:nn {{integer₁}} {{integer₂}}

Evaluates the two *<integer expressions>* as described earlier, then calculates the result of dividing the first value by the second, truncating any remainder. Note that division using / rounds the result. The result is left in the input stream as an *<integer denotation>* after two expansions.

\int_max:nn *

\int_min:nn *

Updated: 2012-09-26

\int_max:nn {{integer₁}} {{integer₂}}

\int_min:nn {{integer₁}} {{integer₂}}

Evaluates the *<integer expressions>* as described for \int_eval:n and leaves either the larger or smaller value in the input stream as an *<integer denotation>* after two expansions.

\int_mod:nn *

Updated: 2012-09-26

\int_mod:nn {{integer₁}} {{integer₂}}

Evaluates the two *<integer expressions>* as described earlier, then calculates the integer remainder of dividing the first expression by the second. This is left in the input stream as an *<integer denotation>* after two expansions.

2 Creating and initialising integers

\int_new:N

\int_new:c

\int_new:N <integer>

Creates a new *<integer>* or raises an error if the name is already taken. The declaration is global. The *<integer>* will initially be equal to 0.

\int_const:Nn

\int_const:cn

Updated: 2011-10-22

\int_const:Nn <integer> {{integer expression}}

Creates a new constant *<integer>* or raises an error if the name is already taken. The value of the *<integer>* will be set globally to the *<integer expression>*.

\int_zero:N

\int_zero:c

\int_gzero:N

\int_gzero:c

\int_zero:N <integer>

Sets *<integer>* to 0.

\int_zero_new:N

\int_zero_new:c

\int_gzero_new:N

\int_gzero_new:c

New: 2011-12-13

\int_zero_new:N <integer>

Ensures that the *<integer>* exists globally by applying \int_new:N if necessary, then applies \int_(g)zero:N to leave the *<integer>* set to zero.

\int_set_eq:NN

\int_set_eq:(cN|Nc|cc)

\int_gset_eq:NN

\int_gset_eq:(cN|Nc|cc)

\int_set_eq:NN <integer₁> <integer₂>

Sets the content of *<integer₁>* equal to that of *<integer₂>*.

\int_if_exist_p:N ***** \int_if_exist_p:N *<int>*
\int_if_exist_p:c ***** \int_if_exist:NTF *<int>* {\{true code\}} {\{false code\}}
\int_if_exist:NTF ***** Tests whether the *<int>* is currently defined. This does not check that the *<int>* really is an integer variable.

Updated: 2012-03-03

3 Setting and incrementing integers

\int_add:Nn \int_add:Nn *<integer>* {\{integer expression\}}
\int_add:cn \int_gadd:Nn \int_gadd:cn
Adds the result of the *<integer expression>* to the current content of the *<integer>*.

Updated: 2011-10-22

\int_decr:N \int_decr:N *<integer>*
\int_decr:c \int_gdecr:N \int_gdecr:c
Decreases the value stored in *<integer>* by 1.

\int_incr:N \int_incr:N *<integer>*
\int_incr:c \int_gincr:N \int_gincr:c
Increases the value stored in *<integer>* by 1.

\int_set:Nn \int_set:Nn *<integer>* {\{integer expression\}}
\int_set:cn \int_gset:Nn \int_gset:cn
Sets *<integer>* to the value of *<integer expression>*, which must evaluate to an integer (as described for \int_eval:n).

Updated: 2011-10-22

\int_sub:Nn \int_sub:Nn *<integer>* {\{integer expression\}}
\int_sub:cn \int.gsub:Nn \int.gsub:cn
Subtracts the result of the *<integer expression>* from the current content of the *<integer>*.

Updated: 2011-10-22

4 Using integers

```
\int_use:N    *
\int_use:c   *
```

Updated: 2011-10-22

```
\int_use:N <integer>
```

Recovers the content of an *<integer>* and places it directly in the input stream. An error will be raised if the variable does not exist or if it is invalid. Can be omitted in places where an *<integer>* is required (such as in the first and third arguments of `\int_compare:nNnTF`).

TeXhackers note: `\int_use:N` is the TeX primitive `\the`: this is one of several L^AT_EX3 names for this primitive.

5 Integer expression conditionals

```
\int_compare_p:nNn *
\int_compare:nNnTF *
```

```
\int_compare_p:nNn {\<intexpr1>} {\<relation>} {\<intexpr2>}
\int_compare:nNnTF
  {\<intexpr1>} {\<relation>} {\<intexpr2>}
  {\<true code>} {\<false code>}
```

This function first evaluates each of the *<integer expressions>* as described for `\int_eval:n`. The two results are then compared using the *<relation>*:

Equal	=
Greater than	>
Less than	<

```
\int_compare_p:n *
\int_compare:nTF *
```

```
\int_compare_p:n {\<intexpr1>} {\<relation>} {\<intexpr2>}
\int_compare:nTF
  {\<intexpr1>} {\<relation>} {\<intexpr2>}
  {\<true code>} {\<false code>}
```

This function first evaluates each of the *<integer expressions>* as described for `\int_eval:n`. The two results are then compared using the *<relation>*:

Equal	= or ==
Greater than or equal to	>=
Greater than	>
Less than or equal to	<=
Less than	<
Not equal	!=

\int_case:nnn *

New: 2012-06-03

```
\int_case:nnn {\test integer expression}
{
  {\intexpr case1} {\code case1}
  {\intexpr case2} {\code case2}
  ...
  {\intexpr casen} {\code casen}
}
{\else code}
```

This function evaluates the *<test integer expression>* and compares this in turn to each of the *<integer expression cases>*. If the two are equal then the associated *<code>* is left in the input stream. If none of the tests are **true** then the **else** *code* will be left in the input stream. For example

```
\int_case:nnn
{ 2 * 5 }
{
  { 5 }      { Small }
  { 4 + 6 }  { Medium }
  { -2 * 10 } { Negative }
}
{ No idea! }
```

will leave “Medium” in the input stream.

\int_if_even_p:n *

\int_if_odd_p:n *

\int_if_even:nTF *

\int_if_odd_p:n *

\int_if_odd:nTF *

This function first evaluates the *<integer expression>* as described for \int_eval:n. It then evaluates if this is odd or even, as appropriate.

6 Integer expression loops

\int_do_until:nNnn *

```
\int_do_until:nNnn {\intexpr1} {\relation} {\intexpr2} {\code}
```

Places the *<code>* in the input stream for TeX to process, and then evaluates the relationship between the two *<integer expressions>* as described for \int_compare:nNnTF. If the test is **false** then the *<code>* will be inserted into the input stream again and a loop will occur until the *<relation>* is **true**.

\int_do_while:nNnn *

```
\int_do_while:nNnn {\intexpr1} {\relation} {\intexpr2} {\code}
```

Places the *<code>* in the input stream for TeX to process, and then evaluates the relationship between the two *<integer expressions>* as described for \int_compare:nNnTF. If the test is **true** then the *<code>* will be inserted into the input stream again and a loop will occur until the *<relation>* is **false**.

<code>\int_until_do:nNnn ☆</code>	<code>\int_until_do:nNnn {\langle intexpr_1\rangle \langle relation\rangle {\langle intexpr_2\rangle} {\langle code\rangle}}</code>
	Evaluates the relationship between the two <i><integer expressions></i> as described for <code>\int_compare:nNnTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is <code>false</code> . After the <i><code></i> has been processed by TeX the test will be repeated, and a loop will occur until the test is <code>true</code> .
<code>\int_while_do:nNnn ☆</code>	<code>\int_while_do:nNnn {\langle intexpr_1\rangle \langle relation\rangle {\langle intexpr_2\rangle} {\langle code\rangle}}</code>
	Evaluates the relationship between the two <i><integer expressions></i> as described for <code>\int_compare:nNnTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is <code>true</code> . After the <i><code></i> has been processed by TeX the test will be repeated, and a loop will occur until the test is <code>false</code> .
<code>\int_do_until:nn ☆</code>	<code>\int_do_until:nn { \langle intexpr_1\rangle \langle relation\rangle {\langle intexpr_2\rangle} } {\langle code\rangle}</code>
	Places the <i><code></i> in the input stream for TeX to process, and then evaluates the relationship between the two <i><integer expressions></i> as described for <code>\int_compare:nTF</code> . If the test is <code>false</code> then the <i><code></i> will be inserted into the input stream again and a loop will occur until the <i><relation></i> is <code>true</code> .
<code>\int_do_while:nn ☆</code>	<code>\int_do_while:nn { \langle intexpr_1\rangle \langle relation\rangle {\langle intexpr_2\rangle} } {\langle code\rangle}</code>
	Places the <i><code></i> in the input stream for TeX to process, and then evaluates the relationship between the two <i><integer expressions></i> as described for <code>\int_compare:nTF</code> . If the test is <code>true</code> then the <i><code></i> will be inserted into the input stream again and a loop will occur until the <i><relation></i> is <code>false</code> .
<code>\int_until_do:nn ☆</code>	<code>\int_until_do:nn { \langle intexpr_1\rangle \langle relation\rangle {\langle intexpr_2\rangle} } {\langle code\rangle}</code>
	Evaluates the relationship between the two <i><integer expressions></i> as described for <code>\int_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is <code>false</code> . After the <i><code></i> has been processed by TeX the test will be repeated, and a loop will occur until the test is <code>true</code> .
<code>\int_while_do:nn ☆</code>	<code>\int_while_do:nn { \langle intexpr_1\rangle \langle relation\rangle {\langle intexpr_2\rangle} } {\langle code\rangle}</code>
	Evaluates the relationship between the two <i><integer expressions></i> as described for <code>\int_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is <code>true</code> . After the <i><code></i> has been processed by TeX the test will be repeated, and a loop will occur until the test is <code>false</code> .

7 Integer step functions

\int_step_function:nnN 

New: 2012-06-04
Updated: 2012-06-29

\int_step_function:nnN {<initial value>} {<step>} {<final value>} {<function>}

This function first evaluates the *<initial value>*, *<step>* and *<final value>*, all of which should be integer expressions. The *<function>* is then placed in front of each *<value>* from the *<initial value>* to the *<final value>* in turn (using *<step>* between each *<value>*). Thus *<function>* should absorb one numerical argument. For example

```
\cs_set:Npn \my_func:n #1 { [I-saw~#1] \quad }
\int_step_function:nnN { 1 } { 1 } { 5 } \my_func:n
```

would print

```
[I saw 1] [I saw 2] [I saw 3] [I saw 4] [I saw 5]
```

\int_step_inline:nnn

New: 2012-06-04
Updated: 2012-06-29

\int_step_inline:nnn {<initial value>} {<step>} {<final value>} {<code>}

This function first evaluates the *<initial value>*, *<step>* and *<final value>*, all of which should be integer expressions. The *<code>* is then placed in front of each *<value>* from the *<initial value>* to the *<final value>* in turn (using *<step>* between each *<value>*). Thus the *<code>* should define a function of one argument (#1).

\int_step_variable:nnNn

New: 2012-06-04
Updated: 2012-06-29

\int_step_variable:nnNn

{<initial value>} {<step>} {<final value>} {tl var} {<code>}

This function first evaluates the *<initial value>*, *<step>* and *<final value>*, all of which should be integer expressions. The *<code>* is inserted into the input stream, with the *<tl var>* defined as the current *<value>*. Thus the *<code>* should make use of the *<tl var>*.

8 Formatting integers

Integers can be placed into the output stream with formatting. These conversions apply to any integer expressions.

\int_to_arabic:n 

Updated: 2011-10-22

\int_to_arabic:n {<integer expression>}

Places the value of the *<integer expression>* in the input stream as digits, with category code 12 (other).

\int_to_alpha:n *
\int_to_Alph:n *

Updated: 2011-09-17

`\int_to_alpha:n {<integer expression>}`

Evaluates the *<integer expression>* and converts the result into a series of letters, which are then left in the input stream. The conversion rule uses the 26 letters of the English alphabet, in order, adding letters when necessary to increase the total possible range of representable numbers. Thus

`\int_to_alpha:n { 1 }`

places **a** in the input stream,

`\int_to_alpha:n { 26 }`

is represented as **z** and

`\int_to_alpha:n { 27 }`

is converted to **aa**. For conversions using other alphabets, use `\int_convert_to_symbols:nnn` to define an alphabet-specific function. The basic `\int_to_alpha:n` and `\int_to_Alph:n` functions should not be modified.

\int_to_symbols:nnn *

Updated: 2011-09-17

`\int_to_symbols:nnn`
 `{<integer expression>} {<total symbols>}`
 `(value to symbol mapping)`

This is the low-level function for conversion of an *<integer expression>* into a symbolic form (which will often be letters). The *<total symbols>* available should be given as an integer expression. Values are actually converted to symbols according to the *<value to symbol mapping>*. This should be given as *<total symbols>* pairs of entries, a number and the appropriate symbol. Thus the `\int_to_alpha:n` function is defined as

```
\cs_new:Npn \int_to_alpha:n #1
{
  \int_convert_to_symbols:nnn {#1} { 26 }
  {
    { 1 } { a }
    { 2 } { b }
    ...
    { 26 } { z }
  }
}
```

\int_to_binary:n *

Updated: 2011-09-17

`\int_to_binary:n {<integer expression>}`

Calculates the value of the *<integer expression>* and places the binary representation of the result in the input stream.

`\int_to_hexadecimal:n` ★

Updated: 2011-09-17

`\int_to_binary:n {<integer expression>}`

Calculates the value of the *<integer expression>* and places the hexadecimal (base 16) representation of the result in the input stream. Upper case letters are used for digits beyond 9.

`\int_to_octal:n` ★

Updated: 2011-09-17

`\int_to_octal:n {<integer expression>}`

Calculates the value of the *<integer expression>* and places the octal (base 8) representation of the result in the input stream.

`\int_to_base:mn` ★

Updated: 2011-09-17

`\int_to_base:mn {<integer expression>} {<base>}`

Calculates the value of the *<integer expression>* and converts it into the appropriate representation in the *<base>*; the later may be given as an integer expression. For bases greater than 10 the higher “digits” are represented by the upper case letters from the English alphabet. The maximum *<base>* value is 36.

TeXhackers note: This is a generic version of `\int_to_binary:n`, etc.

`\int_to_roman:n` ★

`\int_to_Roman:n` ★

Updated: 2011-10-22

`\int_to_roman:n {<integer expression>}`

Places the value of the *<integer expression>* in the input stream as Roman numerals, either lower case (`\int_to_roman:n`) or upper case (`\int_to_Roman:n`). The Roman numerals are letters with category code 11 (letter).

9 Converting from other formats to integers

`\int_from_alpha:n` ★

`\int_from_alpha:n {<letters>}`

Converts the *<letters>* into the integer (base 10) representation and leaves this in the input stream. The *<letters>* are treated using the English alphabet only, with “a” equal to 1 through to “z” equal to 26. Either lower or upper case letters may be used. This is the inverse function of `\int_to_alpha:n`.

`\int_from_binary:n` ★

`\int_from_binary:n {<binary number>}`

Converts the *<binary number>* into the integer (base 10) representation and leaves this in the input stream.

`\int_from_hexadecimal:n` ★

`\int_from_hexadecimal:n {<hexadecimal number>}`

Converts the *<hexadecimal number>* into the integer (base 10) representation and leaves this in the input stream. Digits greater than 9 may be represented in the *<hexadecimal number>* by upper or lower case letters.

`\int_from_octal:n *`

`\int_from_octal:n {\octal number}`

Converts the $\langle\text{octal number}\rangle$ into the integer (base 10) representation and leaves this in the input stream.

`\int_from_roman:n *`

`\int_from_roman:n {\roman numeral}`

Converts the $\langle\text{roman numeral}\rangle$ into the integer (base 10) representation and leaves this in the input stream. The $\langle\text{roman numeral}\rangle$ may be in upper or lower case; if the numeral is not valid then the resulting value will be -1 .

`\int_from_base:nn *`

`\int_from_base:nn {\number} {\base}`

Converts the $\langle\text{number}\rangle$ in $\langle\text{base}\rangle$ into the appropriate value in base 10. The $\langle\text{number}\rangle$ should consist of digits and letters (either lower or upper case), plus optionally a leading sign. The maximum $\langle\text{base}\rangle$ value is 36.

10 Viewing integers

`\int_show:N`

`\int_show:N {\integer}`

Displays the value of the $\langle\text{integer}\rangle$ on the terminal.

`\int_show:n`

`\int_show:n {\integer expression}`

Displays the result of evaluating the $\langle\text{integer expression}\rangle$ on the terminal.

New: 2011-11-22

Updated: 2012-05-27

11 Constant integers

\c_minus_one
\c_zero
\c_one
\c_two
\c_three
\c_four
\c_five
\c_six
\c_seven
\c_eight
\c_nine
\c_ten
\c_eleven
\c_twelve
\c_thirteen
\c_fourteen
\c_fifteen
\c_sixteen
\c_thirty_two
\c_one_hundred
\c_two_hundred_fifty_five
\c_two_hundred_fifty_six
\c_one_thousand
\c_ten_thousand

Integer values used with primitive tests and assignments: self-terminating nature makes these more convenient and faster than literal numbers.

\c_max_int

The maximum value that can be stored as an integer.

\c_max_register_int

Maximum number of registers.

12 Scratch integers

\l_tmpa_int
\l_tmpb_int

Scratch integer for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

\g_tmpa_int
\g_tmpb_int

Scratch integer for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

13 Primitive conditionals

\if_int_compare:w \star \if_int_compare:w $\langle integer_1 \rangle \langle relation \rangle \langle integer_2 \rangle$
 ⟨true code⟩
 \else:
 ⟨false code⟩
 \fi:

Compare two integers using $\langle relation \rangle$, which must be one of =, < or > with category code 12. The \else: branch is optional.

TeXhackers note: These are both names for the TeX primitive \ifnum.

\if_case:w \star \if_case:w $\langle integer \rangle \langle case_0 \rangle$
 \or: \star \or: ⟨case₁⟩
 \or: ...
 \else: ⟨default⟩
 \fi:

Selects a case to execute based on the value of the $\langle integer \rangle$. The first case ($\langle case_0 \rangle$) is executed if $\langle integer \rangle$ is 0, the second ($\langle case_1 \rangle$) if the $\langle integer \rangle$ is 1, etc. The $\langle integer \rangle$ may be a literal, a constant or an integer expression (e.g. using \int_eval:n).

TeXhackers note: These are the TeX primitives \ifcase and \or.

\if_int_odd:w \star \if_int_odd:w $\langle tokens \rangle \langle optional\ space \rangle$
 ⟨true code⟩
 \else:
 ⟨true code⟩
 \fi:

Expands $\langle tokens \rangle$ until a non-numeric token or a space is found, and tests whether the resulting $\langle integer \rangle$ is odd. If so, $\langle true code \rangle$ is executed. The \else: branch is optional.

TeXhackers note: This is the TeX primitive \ifodd.

14 Internal functions

__int_to_roman:w \star __int_to_roman:w $\langle integer \rangle \langle space \rangle$ or $\langle non-expandable\ token \rangle$

Converts $\langle integer \rangle$ to its lower case Roman representation. Expansion ends when a space or non-expandable token is found. Note that this function produces a string of letters with category code 12 and that protected functions are expanded by this process. Negative $\langle integer \rangle$ values result in no output, although the function does not terminate expansion until a suitable endpoint is found in the same way as for positive numbers.

TeXhackers note: This is the TeX primitive \romannumeral renamed.

_int_value:w \star _int_value:w *<integer>*
 _int_value:w *<tokens>* *(optional space)*

Expands *<tokens>* until an *<integer>* is formed. One space may be gobbled in the process.

TExhacker's note: This is the TEx primitive \number.

_int_eval:w \star _int_eval:w *<intexpr>* _int_eval_end:
_int_eval_end: \star

Evaluates *<integer expression>* as described for \int_eval:n. The evaluation stops when an unexpandable token which is not a valid part of an integer is read or when _int_eval_end: is reached. The latter is gobbled by the scanner mechanism: _int_eval_end: itself is unexpandable but used correctly the entire construct is expandable.

TExhacker's note: This is the ε -TEx primitive \numexpr.

_prg_compare_error: _prg_compare_error:
_prg_compare_error:Nw

These are used within \int_compare:n(TF), \dim_compare:n(TF) and so on to recover correctly if the n-type argument does not contain a properly-formed relation.

Part X

The `\3skip` package

Dimensions and skips

L^AT_EX3 provides two general length variables: `dim` and `skip`. Lengths stored as `dim` variables have a fixed length, whereas `skip` lengths have a rubber (stretch/shrink) component. In addition, the `muskip` type is available for use in math mode: this is a special form of `skip` where the lengths involved are determined by the current math font (in `mu`). There are common features in the creation and setting of length variables, but for clarity the functions are grouped by variable type.

1 Creating and initialising `dim` variables

`\dim_new:N` `\dim_new:c` `\dim_new:Nn` `\dim_new:cn`

Creates a new `(dimension)` or raises an error if the name is already taken. The declaration is global. The `(dimension)` will initially be equal to 0 pt.

`\dim_const:Nn` `\dim_const:cn`
New: 2012-03-05

`\dim_const:Nn` `\dim_const:cn` `\dim_const:N` `\dim_const:c`

Creates a new constant `(dimension)` or raises an error if the name is already taken. The value of the `(dimension)` will be set globally to the `(dimension expression)`.

`\dim_zero:N` `\dim_zero:c` `\dim_gzero:N` `\dim_gzero:c`

Sets `(dimension)` to 0 pt.

`\dim_zero_new:N` `\dim_zero_new:c` `\dim_gzero_new:N` `\dim_gzero_new:c`

New: 2012-01-07

`\dim_zero_new:N` `\dim_zero_new:c` `\dim_gzero_new:N` `\dim_gzero_new:c`

Ensures that the `(dimension)` exists globally by applying `\dim_new:N` if necessary, then applies `\dim_(g)zero:N` to leave the `(dimension)` set to zero.

`\dim_if_exist_p:N` * `\dim_if_exist_p:c` * `\dim_if_exist:NTF` * `\dim_if_exist:cTF` *

New: 2012-03-03

`\dim_if_exist_p:N` `\dim_if_exist_p:c` `\dim_if_exist:NTF` `\dim_if_exist:cTF`

Tests whether the `(dimension)` is currently defined. This does not check that the `(dimension)` really is a dimension variable.

2 Setting dim variables

\dim_add:Nn
\dim_add:cn
\dim_gadd:Nn
\dim_gadd:cn

Updated: 2011-10-22

\dim_add:Nn *dimension* {*dimension expression*}

Adds the result of the *dimension expression* to the current content of the *dimension*.

\dim_set:Nn
\dim_set:cn
\dim_gset:Nn
\dim_gset:cn

Updated: 2011-10-22

\dim_set:Nn *dimension* {*dimension expression*}

Sets *dimension* to the value of *dimension expression*, which must evaluate to a length with units.

\dim_set_eq:NN
\dim_set_eq:(cN|Nc|cc)
\dim_gset_eq:NN
\dim_gset_eq:(cN|Nc|cc)

\dim_set_eq:NN *dimension*₁ *dimension*₂

Sets the content of *dimension*₁ equal to that of *dimension*₂.

\dim_sub:Nn
\dim_sub:cn
\dim_gsub:Nn
\dim_gsub:cn

Updated: 2011-10-22

\dim_sub:Nn *dimension* {*dimension expression*}

Subtracts the result of the *dimension expression* from the current content of the *dimension*.

\dim_abs:n ★
Updated: 2012-09-26

\dim_abs:n {*dimexpr*}

Converts the *dimexpr* to its absolute value, leaving the result in the input stream as a *dimension denotation*.

\dim_max:nn ★
\dim_min:nn ★
New: 2012-09-09
Updated: 2012-09-26

\dim_max:nn {*dimexpr*₁} {*dimexpr*₂}

\dim_min:nn {*dimexpr*₁} {*dimexpr*₂}

Evaluates the two *dimension expressions* and leaves either the maximum or minimum value in the input stream as appropriate, as a *dimension denotation*.

`\dim_ratio:nn` ☆

Updated: 2011-10-22

`\dim_ratio:nn {<dimexpr1>} {<dimexpr2>}`

Parses the two *dimension expressions* and converts the ratio of the two to a form suitable for use inside a *dimension expression*. This ratio is then left in the input stream, allowing syntax such as

```
\dim_set:Nn \l_my_dim
{ 10 pt * \dim_ratio:nn { 5 pt } { 10 pt } }
```

The output of `\dim_ratio:nn` on full expansion is a ration expression between two integers, with all distances converted to scaled points. Thus

```
\tl_set:Nx \l_my_tl { \dim_ratio:nn { 5 pt } { 10 pt } }
\tl_show:N \l_my_tl
```

will display 327680/655360 on the terminal.

4 Dimension expression conditionals

`\dim_compare_p:nNn` ☆

`\dim_compare:nNnTF` ☆

`\@_compare_p:nNn {<dimexpr1>} <relation> {<dimexpr2>}`
`\dim_compare:nNnTF`
 `{<dimexpr1>} <relation> {<dimexpr2>}`
 `{<true code>} {<false code>}`

This function first evaluates each of the *dimension expressions* as described for `\dim_eval:n`. The two results are then compared using the *relation*:

Equal	=
Greater than	>
Less than	<

`\dim_compare_p:n` ☆

`\dim_compare:nTF` ☆

`\@_compare_p:n { <dimexpr1>} <relation> {<dimexpr2>}`
`\dim_compare:nTF`
 `{ <dimexpr1>} <relation> {<dimexpr2>}`
 `{<true code>} {<false code>}`

This function first evaluates each of the *dimension expressions* as described for `\dim_eval:n`. The two results are then compared using the *relation*:

Equal	= or ==
Greater than or equal to	>=
Greater than	>
Less than or equal to	<=
Less than	<
Not equal	!=

\dim_case:nnn New: 2012-06-03

```
\dim_case:nnn {\test dimension expression}
{
  {\dimexpr case1} {\code case1}
  {\dimexpr case2} {\code case2}
  ...
  {\dimexpr casen} {\code casen}
}
{\else code}
```

This function evaluates the *(test dimension expression)* and compares this in turn to each of the *(dimension expression cases)*. If the two are equal then the associated *(code)* is left in the input stream. If none of the tests are **true** then the **else** code will be left in the input stream. For example

```
\dim_set:Nn \l_tmpa_dim { 5 pt }
\dim_case:nnn
{ 2 \l_tmpa_dim }
{
  { 5 pt }      { Small }
  { 4 pt + 6 pt } { Medium }
  { - 10 pt }    { Negative }
}
{ No idea! }
```

will leave “Medium” in the input stream.

5 Dimension expression loops

\dim_do_until:nNnn 

```
\dim_do_until:nNnn {\dimexpr1} {\relation} {\dimexpr2} {\code}
```

Places the *(code)* in the input stream for T_EX to process, and then evaluates the relationship between the two *(dimension expressions)* as described for **\dim_compare:nNnTF**. If the test is **false** then the *(code)* will be inserted into the input stream again and a loop will occur until the *(relation)* is **true**.

\dim_do_while:nNnn 

```
\dim_do_while:nNnn {\dimexpr1} {\relation} {\dimexpr2} {\code}
```

Places the *(code)* in the input stream for T_EX to process, and then evaluates the relationship between the two *(dimension expressions)* as described for **\dim_compare:nNnTF**. If the test is **true** then the *(code)* will be inserted into the input stream again and a loop will occur until the *(relation)* is **false**.

\dim_until_do:nNnn 

```
\dim_until_do:nNnn {\dimexpr1} {\relation} {\dimexpr2} {\code}
```

Evaluates the relationship between the two *(dimension expressions)* as described for **\dim_compare:nNnTF**, and then places the *(code)* in the input stream if the *(relation)* is **false**. After the *(code)* has been processed by T_EX the test will be repeated, and a loop will occur until the test is **true**.

<code>\dim_while_do:nNnn ☆</code>	<code>\dim_while_do:nNnn {<dimexpr₁>} <relation> {<dimexpr₂>} {<code>}</code>
	Evaluates the relationship between the two <i>dimension expressions</i> as described for <code>\dim_compare:nNnTF</code> , and then places the <i>code</i> in the input stream if the <i>relation</i> is true. After the <i>code</i> has been processed by TeX the test will be repeated, and a loop will occur until the test is false.
<code>\dim_do_until:nn ☆</code>	<code>\dim_do_until:nn {<dimexpr₁>} <relation> {<dimexpr₂>} {<code>}</code>
	Places the <i>code</i> in the input stream for TeX to process, and then evaluates the relationship between the two <i>dimension expressions</i> as described for <code>\dim_compare:nTF</code> . If the test is false then the <i>code</i> will be inserted into the input stream again and a loop will occur until the <i>relation</i> is true.
<code>\dim_do_while:nn ☆</code>	<code>\dim_do_while:nn {<dimexpr₁>} <relation> {<dimexpr₂>} {<code>}</code>
	Places the <i>code</i> in the input stream for TeX to process, and then evaluates the relationship between the two <i>dimension expressions</i> as described for <code>\dim_compare:nTF</code> . If the test is true then the <i>code</i> will be inserted into the input stream again and a loop will occur until the <i>relation</i> is false.
<code>\dim_until_do:nn ☆</code>	<code>\dim_until_do:nn {<dimexpr₁>} <relation> {<dimexpr₂>} {<code>}</code>
	Evaluates the relationship between the two <i>dimension expressions</i> as described for <code>\dim_compare:nTF</code> , and then places the <i>code</i> in the input stream if the <i>relation</i> is false. After the <i>code</i> has been processed by TeX the test will be repeated, and a loop will occur until the test is true.
<code>\dim_while_do:nn ☆</code>	<code>\dim_while_do:nn {<dimexpr₁>} <relation> {<dimexpr₂>} {<code>}</code>
	Evaluates the relationship between the two <i>dimension expressions</i> as described for <code>\dim_compare:nTF</code> , and then places the <i>code</i> in the input stream if the <i>relation</i> is true. After the <i>code</i> has been processed by TeX the test will be repeated, and a loop will occur until the test is false.

6 Using dim expressions and variables

<code>\dim_eval:n *</code>	<code>\dim_eval:n {<dimension expression>}</code>
Updated: 2011-10-22	Evaluates the <i>dimension expression</i> , expanding any dimensions and token list variables within the <i>expression</i> to their content (without requiring <code>\dim_use:N</code> / <code>\tl_use:N</code>) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a <i>dimension denotation</i> after two expansions. This will be expressed in points (pt), and will require suitable termination if used in a TeX-style assignment as it is not an <i>internal dimension</i> .

\dim_use:N ★ **\dim_use:c** ★ `\dim_use:N <dimension>`
Recovers the content of a *<dimension>* and places it directly in the input stream. An error will be raised if the variable does not exist or if it is invalid. Can be omitted in places where a *<dimension>* is required (such as in the argument of `\dim_eval:n`).

TeXhackers note: `\dim_use:N` is the TeX primitive `\the`: this is one of several L^AT_EX3 names for this primitive.

7 Viewing dim variables

\dim_show:N `\dim_show:N <dimension>`
\dim_show:c Displays the value of the *<dimension>* on the terminal.

\dim_show:n `\dim_show:n <dimension expression>`
New: 2011-11-22
Updated: 2012-05-27 Displays the result of evaluating the *<dimension expression>* on the terminal.

8 Constant dimensions

\c_max_dim The maximum value that can be stored as a dimension or skip (these are equivalent).
\c_zero_dim A zero length as a dimension or a skip (these are equivalent).

9 Scratch dimensions

\l_tmpa_dim **\l_tmpb_dim** Scratch dimension for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

\g_tmpa_dim **\g_tmpb_dim** Scratch dimension for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

10 Creating and initialising skip variables

\skip_new:N *skip*

\skip_new:c

Creates a new *skip* or raises an error if the name is already taken. The declaration is global. The *skip* will initially be equal to 0 pt.

\skip_const:Nn *skip* {*skip expression*}

\skip_const:cn

New: 2012-03-05

Creates a new constant *skip* or raises an error if the name is already taken. The value of the *skip* will be set globally to the *skip expression*.

\skip_zero:N *skip*

\skip_zero:c

\skip_gzero:N *skip*

\skip_gzero:c

Sets *skip* to 0 pt.

\skip_zero_new:N *skip*

\skip_zero_new:c

\skip_gzero_new:N *skip*

\skip_gzero_new:c

New: 2012-01-07

Ensures that the *skip* exists globally by applying \skip_new:N if necessary, then applies \skip_(g)zero:N to leave the *skip* set to zero.

\skip_if_exist_p:N *

\skip_if_exist_p:c *

\skip_if_exist:NTF *

\skip_if_exist:cTF *

New: 2012-03-03

\skip_if_exist_p:N *skip*

\skip_if_exist:NTF *skip* {*true code*} {*false code*}

Tests whether the *skip* is currently defined. This does not check that the *skip* really is a skip variable.

\skip_add:Nn

\skip_add:cn

\skip_gadd:Nn

\skip_gadd:cn

Updated: 2011-10-22

\skip_add:Nn *skip* {*skip expression*}

Adds the result of the *skip expression* to the current content of the *skip*.

\skip_set:Nn

\skip_set:cn

\skip_gset:Nn

\skip_gset:cn

Updated: 2011-10-22

\skip_set:Nn *skip* {*skip expression*}

Sets *skip* to the value of *skip expression*, which must evaluate to a length with units and may include a rubber component (for example 1 cm plus 0.5 cm).

```
\skip_set_eq:NN
\skip_set_eq:(cN|Nc|cc)
\skip_gset_eq:NN
\skip_gset_eq:(cN|Nc|cc)
```

```
\skip_set_eq:NN <skip1> <skip2>
```

Sets the content of $\langle \text{skip}_1 \rangle$ equal to that of $\langle \text{skip}_2 \rangle$.

```
\skip_sub:Nn
\skip_sub:cn
\skip_gsub:Nn
\skip_gsub:cn
```

Updated: 2011-10-22

```
\skip_sub:Nn <skip> {\<skip expression>}
```

Subtracts the result of the $\langle \text{skip expression} \rangle$ from the current content of the $\langle \text{skip} \rangle$.

```
\skip_if_eq_p:nn *
\skip_if_eq:nnTF *
```

```
\skip_if_eq_p:nn {\<skipexpr1>} {\<skipexpr2>}
\dim_compare:nTF
  {\<skipexpr1>} {\<skipexpr2>}
  {\<true code>} {\<false code>}
```

This function first evaluates each of the $\langle \text{skip expressions} \rangle$ as described for \skip_eval:n . The two results are then compared for exact equality, *i.e.* both the fixed and rubber components must be the same for the test to be true.

```
\skip_if_finite_p:n *
\skip_if_finite:nTF *
```

New: 2012-03-05

```
\skip_if_finite_p:n {\<skipexpr>}
\skip_if_finite:nTF {\<skipexpr>} {\<true code>} {\<false code>}
```

Evaluates the $\langle \text{skip expression} \rangle$ as described for \skip_eval:n , and then tests if all of its components are finite.

13 Using skip expressions and variables

```
\skip_eval:n *
```

Updated: 2011-10-22

```
\skip_eval:n {\<skip expression>}
```

Evaluates the $\langle \text{skip expression} \rangle$, expanding any skips and token list variables within the $\langle \text{expression} \rangle$ to their content (without requiring $\text{\skip_use:N}/\text{\tl_use:N}$) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a $\langle \text{glue denotation} \rangle$ after two expansions. This will be expressed in points (pt), and will require suitable termination if used in a TeX-style assignment as it is *not* an $\langle \text{internal glue} \rangle$.

\skip_use:N ★ \skip_use:N *skip*

\skip_use:c ★ Recovers the content of a *skip* and places it directly in the input stream. An error will be raised if the variable does not exist or if it is invalid. Can be omitted in places where a *dimension* is required (such as in the argument of \skip_eval:n).

TeXhackers note: \skip_use:N is the TeX primitive \the: this is one of several L^AT_EX3 names for this primitive.

14 Viewing skip variables

\skip_show:N \skip_show:N *skip*

\skip_show:c Displays the value of the *skip* on the terminal.

\skip_show:n \skip_show:n *skip expression*

New: 2011-11-22 Displays the result of evaluating the *skip expression* on the terminal.

Updated: 2012-05-27

15 Constant skips

\c_max_skip The maximum value that can be stored as a dimension or skip (these are equivalent).

\c_zero_skip A zero length as a dimension or a skip (these are equivalent).

16 Scratch skips

\l_tmpa_skip Scratch skip for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

\g_tmpa_skip Scratch skip for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

17 Inserting skips into the output

\skip_horizontal:N
\skip_horizontal:(c|n)

Updated: 2011-10-22

\skip_horizontal:N *skip*
\skip_horizontal:n {{*skipexpr*}}

Inserts a horizontal *skip* into the current list.

TeXhackers note: \skip_horizontal:N is the TeX primitive \hskip renamed.

\skip_vertical:N
\skip_vertical:(c|n)

Updated: 2011-10-22

\skip_vertical:N *skip*
\skip_vertical:n {{*skipexpr*}}

Inserts a vertical *skip* into the current list.

TeXhackers note: \skip_vertical:N is the TeX primitive \vskip renamed.

18 Creating and initialising muskip variables

\muskip_new:N
\muskip_new:c

\muskip_new:N *muskip*

Creates a new *muskip* or raises an error if the name is already taken. The declaration is global. The *muskip* will initially be equal to 0mu.

\muskip_const:Nn
\muskip_const:cn

New: 2012-03-05

\muskip_const:Nn *muskip* {{*muskip expression*}}

Creates a new constant *muskip* or raises an error if the name is already taken. The value of the *muskip* will be set globally to the *muskip expression*.

\muskip_zero:N
\muskip_zero:c
\muskip_gzero:N
\muskip_gzero:c

\skip_zero:N *muskip*

Sets *muskip* to 0mu.

\muskip_zero_new:N
\muskip_zero_new:c
\muskip_gzero_new:N
\muskip_gzero_new:c

New: 2012-01-07

\muskip_zero_new:N *muskip*

Ensures that the *muskip* exists globally by applying \muskip_new:N if necessary, then applies \muskip_(g)zero:N to leave the *muskip* set to zero.

\muskip_if_exist_p:N ★
\muskip_if_exist_p:c ★
\muskip_if_exist:NTF ★
\muskip_if_exist:cTF ★

New: 2012-03-03

\muskip_if_exist_p:N *muskip*

\muskip_if_exist:NTF *muskip* {{*true code*}} {{*false code*}}

Tests whether the *muskip* is currently defined. This does not check that the *muskip* really is a muskip variable.

19 Setting `muskip` variables

```
\muskip_add:Nn
\muskip_add:cn
\muskip_gadd:Nn
\muskip_gadd:cn
```

Updated: 2011-10-22

`\muskip_add:Nn <muskip> {<muskip expression>}`

Adds the result of the `<muskip expression>` to the current content of the `<muskip>`.

```
\muskip_set:Nn
\muskip_set:cn
\muskip_gset:Nn
\muskip_gset:cn
```

Updated: 2011-10-22

`\muskip_set:Nn <muskip> {<muskip expression>}`

Sets `<muskip>` to the value of `<muskip expression>`, which must evaluate to a math length with units and may include a rubber component (for example `1 mu plus 0.5 mu`).

```
\muskip_set_eq:NN
\muskip_set_eq:(cN|Nc|cc)
\muskip_gset_eq:NN
\muskip_gset_eq:(cN|Nc|cc)
```

Updated: 2011-10-22

`\muskip_set_eq:NN <muskip1> <muskip2>`

Sets the content of `<muskip1>` equal to that of `<muskip2>`.

```
\muskip_sub:Nn
\muskip_sub:cn
\muskip_gsub:Nn
\muskip_gsub:cn
```

Updated: 2011-10-22

`\muskip_sub:Nn <muskip> {<muskip expression>}`

Subtracts the result of the `<muskip expression>` from the current content of the `<skip>`.

```
\muskip_eval:n *
```

Updated: 2011-10-22

`\muskip_eval:n {<muskip expression>}`

Evaluates the `<muskip expression>`, expanding any skips and token list variables within the `<expression>` to their content (without requiring `\muskip_use:N/\tl_use:N`) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a `<muglue denotation>` after two expansions. This will be expressed in `mu`, and will require suitable termination if used in a TeX-style assignment as it is *not* an `<internal muglue>`.

```
\muskip_use:N *
\muskip_use:c *
```

`\muskip_use:N <muskip>`

Recovering the content of a `<skip>` and places it directly in the input stream. An error will be raised if the variable does not exist or if it is invalid. Can be omitted in places where a `<dimension>` is required (such as in the argument of `\muskip_eval:n`).

TeXhackers note: `\muskip_use:N` is the TeX primitive `\the:` this is one of several L^AT_EX3 names for this primitive.

21 Viewing muskip variables

\muskip_show:N
\muskip_show:c

\muskip_show:N <muskip>

Displays the value of the <muskip> on the terminal.

\muskip_show:n

\muskip_show:n <muskip expression>

New: 2011-11-22
Updated: 2012-05-27

Displays the result of evaluating the <muskip expression> on the terminal.

22 Constant muskips

\c_max_muskip

The maximum value that can be stored as a muskip.

\c_zero_muskip

A zero length as a muskip.

23 Scratch muskips

\l_tmpa_muskip
\l_tmpb_muskip

Scratch muskip for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

\g_tmpa_muskip
\g_tmpb_muskip

Scratch muskip for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

24 Primitive conditional

\if_dim:w <dimen₁> <relation> <dimen₂>
 <true code>
\else:
 <false>
\fi:

Compare two dimensions. The <relation> is one of <, = or > with category code 12.

T_EXhackers note: This is the T_EX primitive \ifdim.

25 Internal functions

<code>__dim_eval:w *</code>	<code>__dim_eval:w <dimexpr> __dim_eval_end:</code>
<code>__dim_eval_end: *</code>	Evaluates $\langle dimension\ expression \rangle$ as described for <code>\dim_eval:n</code> . The evaluation stops when an unexpandable token which is not a valid part of a dimension is read or when <code>__dim_eval_end:</code> is reached. The latter is gobbled by the scanner mechanism: <code>__dim_eval_end:</code> itself is unexpandable but used correctly the entire construct is expandable.

TeXhackers note: This is the ε -TeX primitive `\dimexpr`.

<code>__dim_strip_bp:n *</code>	<code>__dim_strip_bp:n {\langle dimension expression \rangle}</code>
<code>__dim_strip_pt:n *</code>	<code>__dim_strip_pt:n {\langle dimension expression \rangle}</code>
New: 2011-11-11	

Evaluates the $\langle dimension\ expression \rangle$, expanding any dimensions and token list variables within the $\langle expression \rangle$ to their content (without requiring `\dim_use:N/\t1_use:N`) and applying the standard mathematical rules. The magnitude of the result, expressed in big points (bp) or points (pt), will be left in the input stream with *no units*. If the decimal part of the magnitude is zero, this will be omitted.

If the $\{\langle dimension\ expression \rangle\}$ contains additional units, these will be ignored, so for example

```
\__dim_strip_pt:n { 1 bp pt }
```

will leave 1.00374 in the input stream (*i.e.* the magnitude of one “big point” when converted to points).

Part XI

The `\l3tl` package

Token lists

`TeX` works with tokens, and `LATEX3` therefore provides a number of functions to deal with lists of tokens. Token lists may be present directly in the argument to a function:

```
\foo:n { a collection of \tokens }
```

or may be stored in a so-called “token list variable”, which have the suffix `tl`: a token list variable can also be used as the argument to a function, for example

```
\foo:N \l_some_tl
```

In both cases, functions are available to test and manipulate the lists of tokens, and these have the module prefix `tl`. In many cases, functions which can be applied to token list variables are paired with similar functions for application to explicit lists of tokens: the two “views” of a token list are therefore collected together here.

A token list (explicit, or stored in a variable) can be seen either as a list of “items”, or a list of “tokens”. An item is whatever `\use:n` would grab as its argument: a single non-space token or a brace group, with optional leading explicit space characters (each item is thus itself a token list). A token is either a normal `N` argument, or `,`, `{`, or `}` (assuming normal `TeX` category codes). Thus for example

```
{ Hello } ~ world
```

contains six items (`Hello`, `w`, `o`, `r`, `l` and `d`), but thirteen tokens (`{`, `H`, `e`, `l`, `o`, `}`, `,`, `w`, `o`, `r`, `l` and `d`). Functions which act on items are often faster than their analogue acting directly on tokens.

TeXhackers note: When `TeX` fetches an undelimited argument from the input stream, explicit character tokens with character code 32 (space) and category code 10 (space), which we here call “explicit space characters”, are ignored. If the following token is an explicit character token with category code 1 (begin-group) and an arbitrary character code, then `TeX` scans ahead to obtain an equal number of explicit character tokens with category code 1 (begin-group) and 2 (end-group), and the resulting list of tokens (with outer braces removed) becomes the argument. Otherwise, a single token is taken as the argument for the macro: we call such single tokens “N-type”, as they are suitable to be used as an argument for a function with the signature `:N`.

When `TeX` reads a character of category code 10 for the first time, it is converted to an explicit space character, with character code 32, regardless of the initial character code. “Funny” spaces with a different category code, can be produced using `\tl_to_lowercase:n` or `\tl_to_uppercase:n`. Explicit space characters are also produced as a result of `\token_to_str:N`, `\tl_to_str:n`, etc.

1 Creating and initialising token list variables

\tl_new:N *tl var*
\tl_new:c

Creates a new *tl var* or raises an error if the name is already taken. The declaration is global. The *tl var* will initially be empty.

\tl_const:Nn
\tl_const:(Nx|cn|cx)

\tl_const:Nn *tl var* {*token list*}

Creates a new constant *tl var* or raises an error if the name is already taken. The value of the *tl var* will be set globally to the *token list*.

\tl_clear:N
\tl_clear:c
\tl_gclear:N
\tl_gclear:c

\tl_clear:N *tl var*

Clears all entries from the *tl var* within the scope of the current TeX group.

\tl_clear_new:N
\tl_clear_new:c
\tl_gclear_new:N
\tl_gclear_new:c

\tl_clear_new:N *tl var*

Ensures that the *tl var* exists globally by applying \tl_new:N if necessary, then applies \tl_(g)clear:N to leave the *tl var* empty.

\tl_set_eq:NN
\tl_set_eq:(cN|Nc|cc)
\tl_gset_eq:NN
\tl_gset_eq:(cN|Nc|cc)

\tl_set_eq:NN *tl var₁* *tl var₂*

Sets the content of *tl var₁* equal to that of *tl var₂*.

\tl_concat:NNN
\tl_concat:ccc
\tl_gconcat:NNN
\tl_gconcat:ccc

New: 2012-05-18

\tl_concat:NNN *tl var₁* *tl var₂* *tl var₃*

Concatenates the content of *tl var₂* and *tl var₃* together and saves the result in *tl var₁*. The *tl var₂* will be placed at the left side of the new token list.

\tl_if_exist_p:N *
\tl_if_exist_p:c *
\tl_if_exist:NTF *
\tl_if_exist:cTF *

\tl_if_exist_p:N *tl var*

\tl_if_exist:NTF *tl var* {*true code*} {*false code*}

Tests whether the *tl var* is currently defined. This does not check that the *tl var* really is a token list variable.

New: 2012-03-03

2 Adding data to token list variables

```
\tl_set:Nn
\tl_set:(NV|Nv|No|Nf|Nx|cn|cV|cv|co|cf|cx)
\tl_gset:Nn
\tl_gset:(NV|Nv|No|Nf|Nx|cn|cV|cv|co|cf|cx)
```

```
\tl_set:Nn <tl var> {\langle tokens \rangle}
```

Sets $\langle tl\ var \rangle$ to contain $\langle tokens \rangle$, removing any previous content from the variable.

```
\tl_put_left:Nn
\tl_put_left:(NV|No|Nx|cn|cV|co|cx)
\tl_gput_left:Nn
\tl_gput_left:(NV|No|Nx|cn|cV|co|cx)
```

```
\tl_put_left:Nn <tl var> {\langle tokens \rangle}
```

Appends $\langle tokens \rangle$ to the left side of the current content of $\langle tl\ var \rangle$.

```
\tl_put_right:Nn
\tl_put_right:(NV|No|Nx|cn|cV|co|cx)
\tl_gput_right:Nn
\tl_gput_right:(NV|No|Nx|cn|cV|co|cx)
```

```
\tl_put_right:Nn <tl var> {\langle tokens \rangle}
```

Appends $\langle tokens \rangle$ to the right side of the current content of $\langle tl\ var \rangle$.

3 Modifying token list variables

```
\tl_replace_once:Nnn
\tl_replace_once:cnn
\tl_greplace_once:Nnn
\tl_greplace_once:cnn
```

Updated: 2011-08-11

```
\tl_replace_once:Nnn <tl var> {\langle old tokens \rangle} {\langle new tokens \rangle}
```

Replaces the first (leftmost) occurrence of $\langle old\ tokens \rangle$ in the $\langle tl\ var \rangle$ with $\langle new\ tokens \rangle$. $\langle Old\ tokens \rangle$ cannot contain {, } or # (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

```
\tl_replace_all:Nnn
\tl_replace_all:cnn
\tl_greplace_all:Nnn
\tl_greplace_all:cnn
```

Updated: 2011-08-11

```
\tl_replace_all:Nnn <tl var> {\langle old tokens \rangle} {\langle new tokens \rangle}
```

Replaces all occurrences of $\langle old\ tokens \rangle$ in the $\langle tl\ var \rangle$ with $\langle new\ tokens \rangle$. $\langle Old\ tokens \rangle$ cannot contain {, } or # (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6). As this function operates from left to right, the pattern $\langle old\ tokens \rangle$ may remain after the replacement (see `\tl_remove_all:Nn` for an example).

```
\tl_remove_once:Nn
\tl_remove_once:cn
\tl_gremove_once:Nn
\tl_gremove_once:cn
```

Updated: 2011-08-11

```
\tl_remove_once:Nn <tl var> {\langle tokens \rangle}
```

Removes the first (leftmost) occurrence of $\langle tokens \rangle$ from the $\langle tl\ var \rangle$. $\langle Tokens \rangle$ cannot contain {, } or # (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

\tl_remove_all:Nn
\tl_remove_all:cn
\tl_gremove_all:Nn
\tl_gremove_all:cn

Updated: 2011-08-11

\tl_remove_all:Nn *tl var* {*tokens*}

Removes all occurrences of *tokens* from the *tl var*. *Tokens* cannot contain {, } or # (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6). As this function operates from left to right, the pattern *tokens* may remain after the removal, for instance,

\tl_set:Nn \l_tmpa_tl {abbccd} \tl_remove_all:Nn \l_tmpa_tl {bc}

will result in \l_tmpa_tl containing abcd.

4 Reassigning token list category codes

\tl_set_rescan:Nnn
\tl_set_rescan:(Nno|Nnx|cnn|cno|cnx)
\tl_gset_rescan:Nnn
\tl_gset_rescan:(Nno|Nnx|cnn|cno|cnx)

Updated: 2011-12-18

\tl_set_rescan:Nnn *tl var* {*setup*} {*tokens*}

Sets *tl var* to contain *tokens*, applying the category code régime specified in the *setup* before carrying out the assignment. This allows the *tl var* to contain material with category codes other than those that apply when *tokens* are absorbed. See also \tl_rescan:nn.

\tl_rescan:nn

Updated: 2011-12-18

\tl_rescan:nn {*setup*} {*tokens*}

Rescans *tokens* applying the category code régime specified in the *setup*, and leaves the resulting tokens in the input stream. See also \tl_set_rescan:Nnn.

5 Reassigning token list character codes

\tl_to_lowercase:n
Updated: 2012-09-08

\tl_to_lowercase:n {*tokens*}

Works through all of the *tokens*, replacing each character token with the lower case equivalent as defined by \char_set_lccode:nn. Characters with no defined lower case character code are left unchanged. This process does not alter the category code assigned to the *tokens*.

TeXhackers note: This is a wrapper around the TeX primitive \lowercase.

`\tl_to_uppercase:n`

Updated: 2012-09-08

`\tl_to_uppercase:n {<tokens>}`

Works through all of the *<tokens>*, replacing each character token with the upper case equivalent as defined by `\char_set_uccode:nn`. Characters with no defined upper case character code are left unchanged. This process does not alter the category code assigned to the *<tokens>*.

TeXhackers note: This is a wrapper around the TeX primitive `\uppercase`.

6 Token list conditionals

`\tl_if_blank_p:n` *

`\tl_if_blank_p:(V|o)` *

`\tl_if_blank:nTF` *

`\tl_if_blank:(V|o)TF` *

`\tl_if_blank_p:n {<token list>}`

`\tl_if_blank:nTF {<token list>} {<true code>} {<false code>}`

Tests if the *<token list>* consists only of blank spaces (*i.e.* contains no item). The test is **true** if *<token list>* is zero or more explicit space characters (explicit tokens with character code 32 and category code 10), and is **false** otherwise.

`\tl_if_empty_p:N` *

`\tl_if_empty_p:c` *

`\tl_if_empty:NTF` *

`\tl_if_empty:cTF` *

`\tl_if_empty_p:N {tl var}`

`\tl_if_empty:NTF {tl var} {<true code>} {<false code>}`

Tests if the *<token list variable>* is entirely empty (*i.e.* contains no tokens at all).

`\tl_if_empty_p:n` *

`\tl_if_empty_p:(V|o)` *

`\tl_if_empty:nTF` *

`\tl_if_empty:(V|o)TF` *

`\tl_if_empty_p:n {<token list>}`

`\tl_if_empty:nTF {<token list>} {<true code>} {<false code>}`

Tests if the *<token list>* is entirely empty (*i.e.* contains no tokens at all).

New: 2012-05-24

Updated: 2012-06-05

`\tl_if_eq_p>NN` *

`\tl_if_eq_p:(Nc|cN|cc)` *

`\tl_if_eq:NNTF` *

`\tl_if_eq:(Nc|cN|cc)TF` *

`\tl_if_eq_p>NN {<tl var1>} {<tl var2>}`

`\tl_if_eq:NNTF {<tl var1>} {<tl var2>} {<true code>} {<false code>}`

Compares the content of two *<token list variables>* and is logically **true** if the two contain the same list of tokens (*i.e.* identical in both the list of characters they contain and the category codes of those characters). Thus for example

```
\tl_set:Nn \l_tmpa_tl { abc }
\tl_set:Nx \l_tmpb_tl { \tl_to_str:n { abc } }
\tl_if_eq:NNTF \l_tmpa_tl \l_tmpb_tl { true } { false }
```

yields **false**.

`\tl_if_eq:nNTF` *

`\tl_if_eq:nNTF {<token list1>} {<token list2>} {<true code>} {<false code>}`

Tests if *<token list₁>* and *<token list₂>* contain the same list of tokens, both in respect of character codes and category codes.

```
\tl_if_in:NnTF
\tl_if_in:cNTF
```

```
\tl_if_in:NnTF <tl var> {<token list>} {{true code}} {{false code}}
```

Tests if the *<token list>* is found in the content of the *<tl var>*. The *<token list>* cannot contain the tokens {, } or # (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

```
\tl_if_in:nnTF
\tl_if_in:(Vn|on|no)TF
```

```
\tl_if_in:nnTF {<token list1>} {<token list2>} {{true code}} {{false code}}
```

Tests if *<token list₂>* is found inside *<token list₁>*. The *<token list₂>* cannot contain the tokens {, } or # (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

```
\tl_if_single_p:N ★
\tl_if_single_p:c ★
\tl_if_single:NTF ★
\tl_if_single:cTF ★
```

Updated: 2011-08-13

```
\tl_if_single_p:N {<tl var>}
\tl_if_single:NTF {<tl var>} {{true code}} {{false code}}
```

Tests if the content of the *<tl var>* consists of a single item, *i.e.* is a single normal token (neither an explicit space character nor a begin-group character) or a single brace group, surrounded by optional spaces on both sides. In other words, such a token list has token count 1 according to `\tl_count:N`.

```
\tl_if_single_p:n ★
\tl_if_single:nTF ★
```

Updated: 2011-08-13

```
\tl_if_single_p:n {<token list>}
\tl_if_single:nTF {<token list>} {{true code}} {{false code}}
```

Tests if the *<token list>* has exactly one item, *i.e.* is a single normal token (neither an explicit space character nor a begin-group character) or a single brace group, surrounded by optional spaces on both sides. In other words, such a token list has token count 1 according to `\tl_count:n`.

```
\tl_case:Nnn ★
\tl_case:cnn ★
```

New: 2012-06-03

```
\tl_case:Nnn <test token list variable>
{
  <token list variable case1> {{code case1}}
  <token list variable case2> {{code case2}}
  ...
  <token list variable casen> {{code casen}}
}
{{else code}}
```

This function compares the *<test token list variable>* in turn with each of the *<token list variable cases>*. If the two are equal (as described for `\tl_if_eq:NNTF`) then the associated *<code>* is left in the input stream. If none of the tests are `true` then the `else` code will be left in the input stream.

7 Mapping to token lists

```
\tl_map_function:NN ★
\tl_map_function:cN ★
```

Updated: 2012-06-29

```
\tl_map_function:NN <tl var> <function>
```

Applies *<function>* to every *<item>* in the *<tl var>*. The *<function>* will receive one argument for each iteration. This may be a number of tokens if the *<item>* was stored within braces. Hence the *<function>* should anticipate receiving n-type arguments. See also `\tl_map_function:nN`.

\tl_map_function:nN ☆

Updated: 2012-06-29

\tl_map_function:nN *<token list>* *<function>*

Applies *<function>* to every *<item>* in the *<token list>*. The *<function>* will receive one argument for each iteration. This may be a number of tokens if the *<item>* was stored within braces. Hence the *<function>* should anticipate receiving n-type arguments. See also \tl_map_function:NN.

\tl_map_inline:Nn

\tl_map_inline:cn

Updated: 2012-06-29

\tl_map_inline:Nn *tl var* {*inline function*}

Applies the *<inline function>* to every *<item>* stored within the *<tl var>*. The *<inline function>* should consist of code which will receive the *<item>* as #1. One in line mapping can be nested inside another. See also \tl_map_function:NN.

\tl_map_inline:nn

Updated: 2012-06-29

\tl_map_inline:nn *<token list>* {*inline function*}

Applies the *<inline function>* to every *<item>* stored within the *<token list>*. The *<inline function>* should consist of code which will receive the *<item>* as #1. One in line mapping can be nested inside another. See also \tl_map_function:nN.

\tl_map_variable>NNn

\tl_map_variable:cNn

Updated: 2012-06-29

\tl_map_variable>NNn *tl var* *<variable>* {*function*}

Applies the *<function>* to every *<item>* stored within the *<tl var>*. The *<function>* should consist of code which will receive the *<item>* stored in the *<variable>*. One variable mapping can be nested inside another. See also \tl_map_inline:Nn.

\tl_map_variable:nNn

Updated: 2012-06-29

\tl_map_variable:nNn *<token list>* *<variable>* {*function*}

Applies the *<function>* to every *<item>* stored within the *<token list>*. The *<function>* should consist of code which will receive the *<item>* stored in the *<variable>*. One variable mapping can be nested inside another. See also \tl_map_inline:nn.

\tl_map_break: ☆

Updated: 2012-06-29

\tl_map_break:

Used to terminate a \tl_map_... function before all entries in the *<token list variable>* have been processed. This will normally take place within a conditional statement, for example

```
\tl_map_inline:Nn \l_my_tl
{
  \str_if_eq:nnT { #1 } { bingo } { \tl_map_break: }
  % Do something useful
}
```

See also \tl_map_break:n. Use outside of a \tl_map_... scenario will lead to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted by the internal macro __prg_break_point:Nn before the *<tokens>* are inserted into the input stream. This will depend on the design of the mapping function.

\tl_map_break:n 

Updated: 2012-06-29

\tl_map_break:n {<tokens>}

Used to terminate a \tl_map_... function before all entries in the *<token list variable>* have been processed, inserting the *<tokens>* after the mapping has ended. This will normally take place within a conditional statement, for example

```
\tl_map_inline:Nn \l_my_tl
{
  \str_if_eq:nnT { #1 } { bingo }
    { \tl_map_break:n { <tokens> } }
  % Do something useful
}
```

Use outside of a \tl_map_... scenario will lead to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted by the internal macro __prg_break_point:Nn before the *<tokens>* are inserted into the input stream. This will depend on the design of the mapping function.

8 Using token lists

\tl_to_str:N 
\tl_to_str:c 

\tl_to_str:N <tl var>

Converts the content of the *<tl var>* into a series of characters with category code 12 (other) with the exception of spaces, which retain category code 10 (space). This *<string>* is then left in the input stream.

\tl_to_str:n 

\tl_to_str:n {<tokens>}

Converts the given *<tokens>* into a series of characters with category code 12 (other) with the exception of spaces, which retain category code 10 (space). This *<string>* is then left in the input stream. Note that this function requires only a single expansion.

T_EXhackers note: This is the ε -T_EX primitive \detokenize. Hence its argument *must* be given within braces.

\tl_use:N 
\tl_use:c 

\tl_use:N <tl var>

Recovering the content of a *<tl var>* and places it directly in the input stream. An error will be raised if the variable does not exist or if it is invalid. Note that it is possible to use a *<tl var>* directly without an accessor function.

9 Working with the content of token lists

\tl_count:n *
\tl_count:(V|o) *
New: 2012-05-13

\tl_count:n {*tokens*}

Counts the number of *items* in *tokens* and leaves this information in the input stream. Unbraced tokens count as one element as do each token group ({...}). This process will ignore any unprotected spaces within *tokens*. See also \tl_count:N. This function requires three expansions, giving an *integer denotation*.

\tl_count:N *
\tl_count:c *
New: 2012-05-13

\tl_count:N {*tl var*}

Counts the number of token groups in the *tl var* and leaves this information in the input stream. Unbraced tokens count as one element as do each token group ({...}). This process will ignore any unprotected spaces within the *tl var*. See also \tl_count:n. This function requires three expansions, giving an *integer denotation*.

\tl_reverse:n *
\tl_reverse:(V|o) *
Updated: 2012-01-08

\tl_reverse:n {*token list*}

Reverses the order of the *items* in the *token list*, so that *item₁**item₂**item₃* ... *item_n* becomes *item_n*...*item₃**item₂**item₁*. This process will preserve unprotected space within the *token list*. Tokens are not reversed within braced token groups, which keep their outer set of braces. In situations where performance is important, consider \tl_reverse_items:n. See also \tl_reverse:N.

TeXhackers note: The result is returned within \exp_not:n, which means that the token list will not expand further when appearing in an x-type argument expansion.

\tl_reverse:N
\tl_reverse:c
\tl_greverse:N
\tl_greverse:c
Updated: 2012-01-08

\tl_reverse:N {*tl var*}

Reverses the order of the *items* stored in *tl var*, so that *item₁**item₂**item₃* ... *item_n* becomes *item_n*...*item₃**item₂**item₁*. This process will preserve unprotected spaces within the *token list variable*. Braced token groups are copied without reversing the order of tokens, but keep the outer set of braces. See also \tl_reverse:n, and, for improved performance, \tl_reverse_items:n.

\tl_reverse_items:n *
New: 2012-01-08

\tl_reverse_items:n {*token list*}

Reverses the order of the *items* stored in *tl var*, so that {{*item₁*}{{*item₂*}{{*item₃*}} ... {{*item_n*}}} becomes {{*item_n*}} ... {{*item₃*}}{{*item₂*}}{{*item₁*}}}. This process will remove any unprotected space within the *token list*. Braced token groups are copied without reversing the order of tokens, and keep the outer set of braces. Items which are initially not braced are copied with braces in the result. In cases where preserving spaces is important, consider the slower function \tl_reverse:n.

TeXhackers note: The result is returned within \exp_not:n, which means that the token list will not expand further when appearing in an x-type argument expansion.

`\tl_trim_spaces:n` *

New: 2011-07-09

Updated: 2012-06-25

`\tl_trim_spaces:n {<token list>}`

Removes any leading and trailing explicit space characters (explicit tokens with character code 32 and category code 10) from the *<token list>* and leaves the result in the input stream.

TeXhackers note: The result is returned within `\exp_not:n`, which means that the token list will not expand further when appearing in an `x`-type argument expansion.

`\tl_trim_spaces:N`
`\tl_trim_spaces:c`
`\tl_gtrim_spaces:N`
`\tl_gtrim_spaces:c`

New: 2011-07-09

`\tl_trim_spaces:N <tl var>`

Removes any leading and trailing explicit space characters (explicit tokens with character code 32 and category code 10) from the content of the *<tl var>*.

10 The first token from a token list

Functions which deal with either only the very first item (balanced text or single normal token) in a token list, or the remaining tokens.

`\tl_head:N` *

`\tl_head:(n|V|v|f)` *

Updated: 2012-09-09

`\tl_head:n {<token list>}`

Leaves in the input stream the first *item* in the *<token list>*, discarding the rest of the *<token list>*. All leading explicit space characters (explicit tokens with character code 32 and category code 10) are discarded; for example

`\tl_head:n { abc }`

and

`\tl_head:n { ~ abc }`

will both leave `a` in the input stream. If the “head” is a brace group, rather than a single token, the braces will be removed, and so

`\tl_head:n { ~ { ~ ab } c }`

yields `ab`. A blank *<token list>* (see `\tl_if_blank:nTF`) will result in `\tl_head:n` leaving nothing in the input stream.

TeXhackers note: The result is returned within `\exp_not:n`, which means that the token list will not expand further when appearing in an `x`-type argument expansion.

```
\tl_head:w token list) { } \q_stop
```

Leaves in the input stream the first *item* in the *token list*, discarding the rest of the *token list*. All leading explicit space characters (explicit tokens with character code 32 and category code 10) are discarded. A blank *token list* (which consists only of space characters) will result in a low-level TeX error, which may be avoided by the inclusion of an empty group in the input (as shown), without the need for an explicit test. Alternatively, `\tl_if_blank:nF` may be used to avoid using the function with a “blank” argument. This function requires only a single expansion, and thus is suitable for use within an o-type expansion. In general, `\tl_head:n` should be preferred if the number of expansions is not critical.

```
\tl_tail:N      *
\tl_tail:(n|V|v|f) *
```

Updated: 2012-09-01

```
\tl_tail:n {token list}
```

Discards all leading explicit space characters (explicit tokens with character code 32 and category code 10) and the first *item* in the *token list*, and leaves the remaining tokens in the input stream. Thus for example

```
\tl_tail:n { a ~ {bc} d }
```

and

```
\tl_tail:n { ~ a ~ {bc} d }
```

will both leave `~ a ~ {bc} d` in the input stream. A blank *token list* (see `\tl_if_blank:nTF`) will result in `\tl_tail:n` leaving nothing in the input stream.

TeXhackers note: The result is returned within `\exp_not:n`, which means that the token list will not expand further when appearing in an x-type argument expansion.

```
\str_head:n *
\str_tail:n *
```

New: 2011-08-10

```
\str_head:n {token list}
\str_tail:n {token list}
```

Converts the *token list* into a string, as described for `\tl_to_str:n`. The `\str_head:n` function then leaves the first character of this string in the input stream. The `\str_tail:n` function leaves all characters except the first in the input stream. The first character may be a space. If the *token list* argument is entirely empty, nothing is left in the input stream.

```
\tl_if_head_eq_catcode_p:nN *
\tl_if_head_eq_catcode:nNTF *
```

Updated: 2012-07-09

```
\tl_if_head_eq_catcode_p:nN {token list} <test token>
\tl_if_head_eq_catcode:nNTF {token list} <test token>
  {<true code>} {<false code>}
```

Tests if the first *token* in the *token list* has the same category code as the *test token*. In the case where the *token list* is empty, the test will always be `false`.

```
\tl_if_head_eq_charcode_p:nN ★ \tl_if_head_eq_charcode_p:nN {\langle token list\rangle} {test token}
\tl_if_head_eq_charcode_p:fN ★ \tl_if_head_eq_charcode:nNTF {\langle token list\rangle} {test token}
\tl_if_head_eq_charcode:nNTF ★   {\langle true code\rangle} {\langle false code\rangle}
\tl_if_head_eq_charcode:fNTF ★
```

Updated: 2012-07-09

Tests if the first *<token>* in the *<token list>* has the same character code as the *<test token>*. In the case where the *<token list>* is empty, the test will always be **false**.

```
\tl_if_head_eq_meaning_p:nN ★ \tl_if_head_eq_meaning_p:nN {\langle token list\rangle} {test token}
\tl_if_head_eq_meaning:nNTF ★ \tl_if_head_eq_meaning:nNTF {\langle token list\rangle} {test token}
                                {\langle true code\rangle} {\langle false code\rangle}
```

Updated: 2012-07-09

Tests if the first *<token>* in the *<token list>* has the same meaning as the *<test token>*. In the case where *<token list>* is empty, the test will always be **false**.

```
\tl_if_head_is_group_p:n ★ \tl_if_head_is_group_p:n {\langle token list\rangle}
\tl_if_head_is_group:nTF ★ \tl_if_head_is_group:nTF {\langle token list\rangle} {\langle true code\rangle} {\langle false code\rangle}
```

New: 2012-07-08

Tests if the first *<token>* in the *<token list>* is an explicit begin-group character (with category code 1 and any character code), in other words, if the *<token list>* starts with a brace group. In particular, the test is **false** if the *<token list>* starts with an implicit token such as `\c_group_begin_token`, or if it is empty. This function is useful to implement actions on token lists on a token by token basis.

```
\tl_if_head_is_N_type_p:n ★ \tl_if_head_is_N_type_p:n {\langle token list\rangle}
\tl_if_head_is_N_type:nTF ★ \tl_if_head_is_N_type:nTF {\langle token list\rangle} {\langle true code\rangle} {\langle false code\rangle}
```

New: 2012-07-08

Tests if the first *<token>* in the *<token list>* is a normal N-type argument. In other words, it is neither an explicit space character (explicit token with character code 32 and category code 10) nor an explicit begin-group character (with category code 1 and any character code). An empty argument yields **false**, as it does not have a “normal” first token. This function is useful to implement actions on token lists on a token by token basis.

```
\tl_if_head_is_space_p:n ★ \tl_if_head_is_space_p:n {\langle token list\rangle}
\tl_if_head_is_space:nTF ★ \tl_if_head_is_space:nTF {\langle token list\rangle} {\langle true code\rangle} {\langle false code\rangle}
```

Updated: 2012-07-08

Tests if the first *<token>* in the *<token list>* is an explicit space character (explicit token with character code 12 and category code 10). In particular, the test is **false** if the *<token list>* starts with an implicit token such as `\c_space_token`, or if it is empty. This function is useful to implement actions on token lists on a token by token basis.

11 Viewing token lists

\tl_show:N
\tl_show:c
Updated: 2012-09-09

\tl_show:N *tl var*
Displays the content of the *tl var* on the terminal.

TeXhackers note: This is similar to the TeX primitive \show, wrapped to a fixed number of characters per line.

\tl_show:n
Updated: 2012-09-09

\tl_show:n *token list*
Displays the *token list* on the terminal.

TeXhackers note: This is similar to the ε -TeX primitive \showtokens, wrapped to a fixed number of characters per line.

12 Constant token lists

\c_empty_tl

Constant that is always empty.

\c_job_name_tl
Updated: 2011-08-18

Constant that gets the “job name” assigned when TeX starts.

TeXhackers note: This copies the contents of the primitive \jobname. It is a constant that is set by TeX and should not be overwritten by the package.

\c_space_tl

An explicit space character contained in a token list (compare this with \c_space_token). For use where an explicit space is required.

13 Scratch token lists

\l_tmpa_tl
\l_tmpb_tl

Scratch token lists for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

\g_tmpa_tl
\g_tmpb_tl

Scratch token lists for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

14 Internal functions

__tl_trim_spaces:nn `__tl_trim_spaces:nn { \q_mark <token list> } {<continuation>}`

This function removes all leading and trailing explicit space characters from the *<token list>*, and expands to the *<continuation>*, followed by a brace group containing `\use-none:n \q_mark <trimmed token list>`. For instance, `\tl_trim_spaces:n` is implemented by taking the *<continuation>* to be `\exp_not:o`, and the o-type expansion removes the `\q_mark`. This function is also used in `\clist` and `\candidates`.

Part XII

The **l3seq** package

Sequences and stacks

L^AT_EX3 implements a “sequence” data type, which contain an ordered list of entries which may contain any *(balanced text)*. It is possible to map functions to sequences such that the function is applied to every item in the sequence.

Sequences are also used to implement stack functions in L^AT_EX3. This is achieved using a number of dedicated stack functions.

1 Creating and initialising sequences

`\seq_new:N` *(sequence)*

`\seq_new:c`

Creates a new *(sequence)* or raises an error if the name is already taken. The declaration is global. The *(sequence)* will initially contain no items.

`\seq_clear:N` *(sequence)*

`\seq_clear:c`

Clears all items from the *(sequence)*.

`\seq_clear_new:N` *(sequence)*

`\seq_clear_new:c`

Ensures that the *(sequence)* exists globally by applying `\seq_new:N` if necessary, then applies `\seq_(g)clear:N` to leave the *(sequence)* empty.

`\seq_set_eq:NN` *(sequence₁)* *(sequence₂)*

`\seq_set_eq:(cN|Nc|cc)`

`\seq_gset_eq:NN`

`\seq_gset_eq:(cN|Nc|cc)`

Sets the content of *(sequence₁)* equal to that of *(sequence₂)*.

`\seq_set_split:Nnn` *(sequence)* *{(delimiter)}* *{(token list)}*

`\seq_set_split:NnV`

`\seq_gset_split:Nnn`

`\seq_gset_split:NnV`

Splits the *(token list)* into *(items)* separated by *(delimiter)*, and assigns the result to the *(sequence)*. Spaces on both sides of each *(item)* are ignored, then one set of outer braces is removed (if any); this space trimming behaviour is identical to that of l3clist functions.

Empty *(items)* are preserved by `\seq_set_split:Nnn`, and can be removed afterwards using `\seq_remove_all:Nn` *(sequence)* *{()}*. The *(delimiter)* may not contain {, } or # (assuming T_EX’s normal category code régime). If the *(delimiter)* is empty, the *(token list)* is split into *(items)* as a *(token list)*.

New: 2011-08-15

Updated: 2012-07-02

```
\seq_concat:NNN
\seq_concat:ccc
\seq_gconcat:NNN
\seq_gconcat:ccc
```

```
\seq_concat:NNN <sequence1> <sequence2> <sequence3>
```

Concatenates the content of *<sequence₂>* and *<sequence₃>* together and saves the result in *<sequence₁>*. The items in *<sequence₂>* will be placed at the left side of the new sequence.

```
\seq_if_exist_p:N *
\seq_if_exist_p:c *
\seq_if_exist:NTF *
\seq_if_exist:cTF *
```

```
\seq_if_exist_p:N <sequence>
```

```
\seq_if_exist:NTF <sequence> {<true code>} {<false code>}
```

Tests whether the *<sequence>* is currently defined. This does not check that the *<sequence>* really is a sequence variable.

New: 2012-03-03

2 Appending data to sequences

```
\seq_put_left:Nn
\seq_put_left:(NV|Nv|No|Nx|cn|cV|cv|co|cx)
\seq_gput_left:Nn
\seq_gput_left:(NV|Nv|No|Nx|cn|cV|cv|co|cx)
```

```
\seq_put_left:Nn <sequence> {<item>}
```

Appends the *<item>* to the left of the *<sequence>*.

```
\seq_put_right:Nn
\seq_put_right:(NV|Nv|No|Nx|cn|cV|cv|co|cx)
\seq_gput_right:Nn
\seq_gput_right:(NV|Nv|No|Nx|cn|cV|cv|co|cx)
```

```
\seq_put_right:Nn <sequence> {<item>}
```

Appends the *<item>* to the right of the *<sequence>*.

3 Recovering items from sequences

Items can be recovered from either the left or the right of sequences. For implementation reasons, the actions at the left of the sequence are faster than those acting on the right. These functions all assign the recovered material locally, *i.e.* setting the *<token list variable>* used with `\tl_set:Nn` and *never* `\tl_gset:Nn`.

```
\seq_get_left>NN
\seq_get_left:cN
```

Updated: 2012-05-14

```
\seq_get_left>NN <sequence> <token list variable>
```

Stores the left-most item from a *<sequence>* in the *<token list variable>* without removing it from the *<sequence>*. The *<token list variable>* is assigned locally. If *<sequence>* is empty the *<token list variable>* will contain the special marker `\q_no_value`.

```
\seq_get_right>NN
\seq_get_right:cN
```

Updated: 2012-05-19

```
\seq_get_right>NN <sequence> <token list variable>
```

Stores the right-most item from a *<sequence>* in the *<token list variable>* without removing it from the *<sequence>*. The *<token list variable>* is assigned locally. If *<sequence>* is empty the *<token list variable>* will contain the special marker `\q_no_value`.

```
\seq_pop_left:NN
```

```
\seq_pop_left:cN
```

Updated: 2012-05-14

```
\seq_pop_left:NN <sequence> <token list variable>
```

Pops the left-most item from a *<sequence>* into the *<token list variable>*, i.e. removes the item from the sequence and stores it in the *<token list variable>*. Both of the variables are assigned locally. If *<sequence>* is empty the *<token list variable>* will contain the special marker `\q_no_value`.

```
\seq_gpop_left:NN
```

```
\seq_gpop_left:cN
```

Updated: 2012-05-14

```
\seq_gpop_left:NN <sequence> <token list variable>
```

Pops the left-most item from a *<sequence>* into the *<token list variable>*, i.e. removes the item from the sequence and stores it in the *<token list variable>*. The *<sequence>* is modified globally, while the assignment of the *<token list variable>* is local. If *<sequence>* is empty the *<token list variable>* will contain the special marker `\q_no_value`.

```
\seq_pop_right:NN
```

```
\seq_pop_right:cN
```

Updated: 2012-05-19

```
\seq_pop_right:NN <sequence> <token list variable>
```

Pops the right-most item from a *<sequence>* into the *<token list variable>*, i.e. removes the item from the sequence and stores it in the *<token list variable>*. Both of the variables are assigned locally. If *<sequence>* is empty the *<token list variable>* will contain the special marker `\q_no_value`.

```
\seq_gpop_right:NN
```

```
\seq_gpop_right:cN
```

Updated: 2012-05-19

```
\seq_gpop_right:NN <sequence> <token list variable>
```

Pops the right-most item from a *<sequence>* into the *<token list variable>*, i.e. removes the item from the sequence and stores it in the *<token list variable>*. The *<sequence>* is modified globally, while the assignment of the *<token list variable>* is local. If *<sequence>* is empty the *<token list variable>* will contain the special marker `\q_no_value`.

4 Recovering values from sequences with branching

The functions in this section combine tests for non-empty sequences with recovery of an item from the sequence. They offer increased readability and performance over separate testing and recovery phases.

```
\seq_get_left:NNTF
```

```
\seq_get_left:cNTF
```

New: 2012-05-14

Updated: 2012-05-19

```
\seq_get_left:NNTF <sequence> <token list variable> {{true code}} {{false code}}
```

If the *<sequence>* is empty, leaves the *<false code>* in the input stream. The value of the *<token list variable>* is not defined in this case and should not be relied upon. If the *<sequence>* is non-empty, stores the left-most item from a *<sequence>* in the *<token list variable>* without removing it from a *<sequence>*. The *<token list variable>* is assigned locally.

```
\seq_get_right:NNTF
```

```
\seq_get_right:cNTF
```

New: 2012-05-19

```
\seq_get_right:NNTF <sequence> <token list variable> {{true code}} {{false code}}
```

If the *<sequence>* is empty, leaves the *<false code>* in the input stream. The value of the *<token list variable>* is not defined in this case and should not be relied upon. If the *<sequence>* is non-empty, stores the right-most item from a *<sequence>* in the *<token list variable>* without removing it from a *<sequence>*. The *<token list variable>* is assigned locally.

\seq_pop_left:NNTF

\seq_pop_left:cNTF

New: 2012-05-14

Updated: 2012-05-19

\seq_pop_left:NNTF *sequence* *token list variable* {\i>true code} {\i>false code}

If the *sequence* is empty, leaves the *false code* in the input stream. The value of the *token list variable* is not defined in this case and should not be relied upon. If the *sequence* is non-empty, pops the left-most item from a *sequence* in the *token list variable*, i.e. removes the item from a *sequence*. Both the *sequence* and the *token list variable* are assigned locally.

\seq_gpop_left:NNTF

\seq_gpop_left:cNTF

New: 2012-05-14

Updated: 2012-05-19

\seq_gpop_left:NNTF *sequence* *token list variable* {\i>true code} {\i>false code}

If the *sequence* is empty, leaves the *false code* in the input stream. The value of the *token list variable* is not defined in this case and should not be relied upon. If the *sequence* is non-empty, pops the left-most item from a *sequence* in the *token list variable*, i.e. removes the item from a *sequence*. The *sequence* is modified globally, while the *token list variable* is assigned locally.

\seq_pop_right:NNTF

\seq_pop_right:cNTF

New: 2012-05-19

\seq_pop_right:NNTF *sequence* *token list variable* {\i>true code} {\i>false code}

If the *sequence* is empty, leaves the *false code* in the input stream. The value of the *token list variable* is not defined in this case and should not be relied upon. If the *sequence* is non-empty, pops the right-most item from a *sequence* in the *token list variable*, i.e. removes the item from a *sequence*. Both the *sequence* and the *token list variable* are assigned locally.

\seq_gpop_right:NNTF

\seq_gpop_right:cNTF

New: 2012-05-19

\seq_gpop_right:NNTF *sequence* *token list variable* {\i>true code} {\i>false code}

If the *sequence* is empty, leaves the *false code* in the input stream. The value of the *token list variable* is not defined in this case and should not be relied upon. If the *sequence* is non-empty, pops the right-most item from a *sequence* in the *token list variable*, i.e. removes the item from a *sequence*. The *sequence* is modified globally, while the *token list variable* is assigned locally.

5 Modifying sequences

While sequences are normally used as ordered lists, it may be necessary to modify the content. The functions here may be used to update sequences, while retaining the order of the unaffected entries.

\seq_remove_duplicates:N

\seq_remove_duplicates:c

\seq_gremove_duplicates:N

\seq_gremove_duplicates:c

\seq_remove_duplicates:N *sequence*

Removes duplicate items from the *sequence*, leaving the left most copy of each item in the *sequence*. The *item* comparison takes place on a token basis, as for \tl_if_eq:nn(TF).

TeXhackers note: This function iterates through every item in the *sequence* and does a comparison with the *items* already checked. It is therefore relatively slow with large sequences.

`\seq_remove_all:Nn`
`\seq_remove_all:cn`
`\seq_gremove_all:Nn`
`\seq_gremove_all:cn`

`\seq_remove_all:Nn <sequence> {<item>}`

Removes every occurrence of `<item>` from the `<sequence>`. The `<item>` comparison takes place on a token basis, as for `\tl_if_eq:nn(TF)`.

6 Sequence conditionals

`\seq_if_empty_p:N *`
`\seq_if_empty_p:c *`
`\seq_if_empty:NTF *`
`\seq_if_empty:cTF *`

`\seq_if_empty_p:N <sequence>`

`\seq_if_empty:NTF <sequence> {{true code}} {{false code}}`

Tests if the `<sequence>` is empty (containing no items).

`\seq_if_in:NnTF`
`\seq_if_in:(NV|Nv|No|Nx|cn|cV|cv|co|cx)TF`

`\seq_if_in:NnTF <sequence> {<item>} {{true code}} {{false code}}`

Tests if the `<item>` is present in the `<sequence>`.

7 Mapping to sequences

`\seq_map_function>NN *`
`\seq_map_function:CN *`

Updated: 2012-06-29

`\seq_map_function:NN <sequence> <function>`

Applies `<function>` to every `<item>` stored in the `<sequence>`. The `<function>` will receive one argument for each iteration. The `<items>` are returned from left to right. The function `\seq_map_inline:Nn` is in general more efficient than `\seq_map_function:NN`. One mapping may be nested inside another.

`\seq_map_inline:Nn`
`\seq_map_inline:cn`

Updated: 2012-06-29

`\seq_map_inline:Nn <sequence> {<inline function>}`

Applies `<inline function>` to every `<item>` stored within the `<sequence>`. The `<inline function>` should consist of code which will receive the `<item>` as #1. One in line mapping can be nested inside another. The `<items>` are returned from left to right.

`\seq_map_variable>NNn`
`\seq_map_variable:(Ncn|cNn|ccn)`

Updated: 2012-06-29

`\seq_map_variable:NNn <sequence> {tl var.} {{function using tl var.}}`

Stores each entry in the `<sequence>` in turn in the `{tl var.}` and applies the `<function using tl var.>` The `<function>` will usually consist of code making use of the `<tl var.>`, but this is not enforced. One variable mapping can be nested inside another. The `<items>` are returned from left to right.

\seq_map_break: ★Updated: 2012-06-29

\seq_map_break:

Used to terminate a `\seq_map_...` function before all entries in the *(sequence)* have been processed. This will normally take place within a conditional statement, for example

```
\seq_map_inline:Nn \l_my_seq
{
    \str_if_eq:nnTF { #1 } { bingo }
        { \seq_map_break: }
        {
            % Do something useful
        }
}
```

Use outside of a `\seq_map_...` scenario will lead to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted by the internal macro `__prg_break_point:Nn` before further items are taken from the input stream. This will depend on the design of the mapping function.

\seq_map_break:n ★Updated: 2012-06-29

\seq_map_break:n {<tokens>}

Used to terminate a `\seq_map_...` function before all entries in the *(sequence)* have been processed, inserting the *(tokens)* after the mapping has ended. This will normally take place within a conditional statement, for example

```
\seq_map_inline:Nn \l_my_seq
{
    \str_if_eq:nnTF { #1 } { bingo }
        { \seq_map_break:n { <tokens> } }
        {
            % Do something useful
        }
}
```

Use outside of a `\seq_map_...` scenario will lead to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted by the internal macro `__prg_break_point:Nn` before the *(tokens)* are inserted into the input stream. This will depend on the design of the mapping function.

\seq_count:N ★

\seq_count:c ★New: 2012-07-13

\seq_count:N <sequence>

Leaves the number of items in the *(sequence)* in the input stream as an *(integer denotation)*. The total number of items in a *(sequence)* will include those which are empty and duplicates, *i.e.* every item in a *(sequence)* is unique.

8 Sequences as stacks

Sequences can be used as stacks, where data is pushed to and popped from the top of the sequence. (The left of a sequence is the top, for performance reasons.) The stack functions for sequences are not intended to be mixed with the general ordered data functions detailed in the previous section: a sequence should either be used as an ordered data type or as a stack, but not in both ways.

\seq_get:NN

\seq_get:cN

Updated: 2012-05-14

\seq_get:NN *<sequence>* *<token list variable>*

Reads the top item from a *<sequence>* into the *<token list variable>* without removing it from the *<sequence>*. The *<token list variable>* is assigned locally. If *<sequence>* is empty the *<token list variable>* will contain the special marker \q_no_value.

\seq_pop:NN

\seq_pop:cN

Updated: 2012-05-14

\seq_pop:NN *<sequence>* *<token list variable>*

Pops the top item from a *<sequence>* into the *<token list variable>*. Both of the variables are assigned locally. If *<sequence>* is empty the *<token list variable>* will contain the special marker \q_no_value.

\seq_gpop:NN

\seq_gpop:cN

Updated: 2012-05-14

\seq_gpop:NN *<sequence>* *<token list variable>*

Pops the top item from a *<sequence>* into the *<token list variable>*. The *<sequence>* is modified globally, while the *<token list variable>* is assigned locally. If *<sequence>* is empty the *<token list variable>* will contain the special marker \q_no_value.

\seq_get:NNTF

\seq_get:cNTF

New: 2012-05-14

Updated: 2012-05-19

\seq_get:NNTF *<sequence>* *<token list variable>* {{*true code*}} {{*false code*}}

If the *<sequence>* is empty, leaves the *<false code>* in the input stream. The value of the *<token list variable>* is not defined in this case and should not be relied upon. If the *<sequence>* is non-empty, stores the top item from a *<sequence>* in the *<token list variable>* without removing it from the *<sequence>*. The *<token list variable>* is assigned locally.

\seq_pop:NNTF

\seq_pop:cNTF

New: 2012-05-14

Updated: 2012-05-19

\seq_pop:NNTF *<sequence>* *<token list variable>* {{*true code*}} {{*false code*}}

If the *<sequence>* is empty, leaves the *<false code>* in the input stream. The value of the *<token list variable>* is not defined in this case and should not be relied upon. If the *<sequence>* is non-empty, pops the top item from the *<sequence>* in the *<token list variable>*, i.e. removes the item from the *<sequence>*. Both the *<sequence>* and the *<token list variable>* are assigned locally.

\seq_gpop:NNTF

\seq_gpop:cNTF

New: 2012-05-14

Updated: 2012-05-19

\seq_gpop:NNTF *<sequence>* *<token list variable>* {{*true code*}} {{*false code*}}

If the *<sequence>* is empty, leaves the *<false code>* in the input stream. The value of the *<token list variable>* is not defined in this case and should not be relied upon. If the *<sequence>* is non-empty, pops the top item from the *<sequence>* in the *<token list variable>*, i.e. removes the item from the *<sequence>*. The *<sequence>* is modified globally, while the *<token list variable>* is assigned locally.

```
\seq_push:Nn  
\seq_push:(NV|Nv|No|Nx|cn|cV|cv|co|cx)  
\seq_gpush:Nn  
\seq_gpush:(NV|Nv|No|Nx|cn|cV|cv|co|cx)
```

```
\seq_push:Nn <sequence> {(item)}
```

Adds the {*item*} to the top of the *sequence*.

9 Constant and scratch sequences

```
\c_empty_seq
```

Constant that is always empty.

New: 2012-07-02

```
\l_tmpa_seq
```

```
\l_tmpb_seq
```

New: 2012-04-26

Scratch sequences for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

```
\g_tmpa_seq
```

```
\g_tmpb_seq
```

New: 2012-04-26

Scratch sequences for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

10 Viewing sequences

```
\seq_show:N
```

```
\seq_show:C
```

Updated: 2012-09-09

```
\seq_show:N <sequence>
```

Displays the entries in the *sequence* in the terminal.

11 Internal sequence functions

```
\_seq_item:n *
```

```
\_seq_item:n <item>
```

The internal token used to begin each sequence entry. If expanded outside of a mapping or manipulation function, an error will be raised. The definition should always be set globally.

```
\_seq_push_item_def:n
```

```
\_seq_push_item_def:x
```

```
\_seq_push_item_def:n <code>
```

Saves the definition of `_seq_item:n` and redefines it to accept one parameter and expand to *code*. This function should always be balanced by use of `_seq_pop_item_def:`.

__seq_pop_item_def: __seq_pop_item_def:
Restores the definition of __seq_item:n most recently saved by __seq_push_item_def:n. This function should always be used in a balanced pair with __seq_push_item_def:n.

Part XIII

The **I3clist** package

Comma separated lists

Comma lists contain ordered data where items can be added to the left or right end of the list. The resulting ordered list can then be mapped over using `\clist_map_function:N`. Several items can be added at once, and spaces are removed from both sides of each item on input. Hence,

```
\clist_new:N \l_my_clist
\clist_put_left:Nn \l_my_clist { ~ a ~ , ~ {b} ~ }
\clist_put_right:Nn \l_my_clist { ~ {c~} , d }
```

results in `\l_my_clist` containing `a,{b},{c~},d`. Comma lists cannot contain empty items, thus

```
\clist_clear_new:N \l_my_clist
\clist_put_right:Nn \l_my_clist { , ~ , , }
\clist_if_empty:NTF \l_my_clist { true } { false }
```

will leave `true` in the input stream. To include an item which contains a comma, or starts or ends with a space, surround it with braces. The sequence data type should be preferred to comma lists if items are to contain `{, }`, or `#` (assuming the usual `TEX` category codes apply).

1 Creating and initialising comma lists

```
\clist_new:N \clist_new:c
```

Creates a new `(comma list)` or raises an error if the name is already taken. The declaration is global. The `(comma list)` will initially contain no items.

```
\clist_clear:N \clist_clear:c
\clist_gclear:N \clist_gclear:c
```

Clears all items from the `(comma list)`.

```
\clist_clear_new:N \clist_clear_new:c
\clist_gclear_new:N \clist_gclear_new:c
```

Ensures that the `(comma list)` exists globally by applying `\clist_new:N` if necessary, then applies `\clist_(g)clear:N` to leave the list empty.

```
\clist_set_eq:NN
\clist_set_eq:(cN|Nc|cc)
\clist_gset_eq:NN
\clist_gset_eq:(cN|Nc|cc)
```

```
\clist_set_eq:NN <comma list1> <comma list2>
```

Sets the content of *<comma list₁>* equal to that of *<comma list₂>*.

```
\clist_concat:NNN
\clist_concat:ccc
\clist_gconcat:NNN
\clist_gconcat:ccc
```

```
\clist_concat:NNN <comma list1> <comma list2> <comma list3>
```

Concatenates the content of *<comma list₂>* and *<comma list₃>* together and saves the result in *<comma list₁>*. The items in *<comma list₂>* will be placed at the left side of the new comma list.

```
\clist_if_exist_p:N *
\clist_if_exist_p:c *
\clist_if_exist:NTF *
\clist_if_exist:cTF *
```

```
\clist_if_exist_p:N <comma list>
\clist_if_exist:NTF <comma list> {<true code>} {<false code>}
```

Tests whether the *<comma list>* is currently defined. This does not check that the *<comma list>* really is a comma list.

New: 2012-03-03

2 Adding data to comma lists

```
\clist_set:Nn
\clist_set:(NV|No|Nx|cn|cV|co|cx)
\clist_gset:Nn
\clist_gset:(NV|No|Nx|cn|cV|co|cx)
```

New: 2011-09-06

```
\clist_set:Nn <comma list> {<item1>, ..., <itemn>}
```

Sets *<comma list>* to contain the *<items>*, removing any previous content from the variable. Spaces are removed from both sides of each item.

```
\clist_put_left:Nn
\clist_put_left:(NV|No|Nx|cn|cV|co|cx)
\clist_gput_left:Nn
\clist_gput_left:(NV|No|Nx|cn|cV|co|cx)
```

Updated: 2011-09-05

```
\clist_put_left:Nn <comma list> {<item1>, ..., <itemn>}
```

Appends the *<items>* to the left of the *<comma list>*. Spaces are removed from both sides of each item.

```
\clist_put_right:Nn
\clist_put_right:(NV|No|Nx|cn|cV|co|cx)
\clist_gput_right:Nn
\clist_gput_right:(NV|No|Nx|cn|cV|co|cx)
```

Updated: 2011-09-05

```
\clist_put_right:Nn <comma list> {<item1>, ..., <itemn>}
```

Appends the *<items>* to the right of the *<comma list>*. Spaces are removed from both sides of each item.

3 Modifying comma lists

While comma lists are normally used as ordered lists, it may be necessary to modify the content. The functions here may be used to update comma lists, while retaining the order of the unaffected entries.

```
\clist_remove_duplicates:N  \clist_remove_duplicates:N <comma list>
\clist_remove_duplicates:c
\clist_gremove_duplicates:N
\clist_gremove_duplicates:c
```

Removes duplicate items from the *<comma list>*, leaving the left most copy of each item in the *<comma list>*. The *<item>* comparison takes place on a token basis, as for `\tl_if_eq:nn(TF)`.

TeXhackers note: This function iterates through every item in the *<comma list>* and does a comparison with the *<items>* already checked. It is therefore relatively slow with large comma lists. Furthermore, it will not work if any of the items in the *<comma list>* contains {, }, or # (assuming the usual TeX category codes apply).

```
\clist_remove_all:Nn
\clist_remove_all:cn
\clist_gremove_all:Nn
\clist_gremove_all:cn
```

Updated: 2011-09-06

Removes every occurrence of *<item>* from the *<comma list>*. The *<item>* comparison takes place on a token basis, as for `\tl_if_eq:nn(TF)`.

TeXhackers note: The *<item>* may not contain {, }, or # (assuming the usual TeX category codes apply).

4 Comma list conditionals

```
\clist_if_empty_p:N *
\clist_if_empty_p:c *
\clist_if_empty:NTF
\clist_if_empty:cTF *
```

Tests if the *<comma list>* is empty (containing no items).

```
\clist_if_in:NnTF          \clist_if_in:NnTF <comma list> {<item>} {<true code>} {<false code>}
```

Updated: 2011-09-06

Tests if the $\langle item \rangle$ is present in the $\langle comma\ list \rangle$. In the case of an **n**-type $\langle comma\ list \rangle$, spaces are stripped from each item, but braces are not removed. Hence,

```
\clist_if_in:nnTF { a , {b}~ , {b} , c } { b } {true} {false}
```

yields **false**.

TeXhackers note: The $\langle item \rangle$ may not contain {, }, or # (assuming the usual **TEX** category codes apply), and should not contain , nor start or end with a space.

5 Mapping to comma lists

The functions described in this section apply a specified function to each item of a comma list.

When the comma list is given explicitly, as an **n**-type argument, spaces are trimmed around each item. If the result of trimming spaces is empty, the item is ignored. Otherwise, if the item is surrounded by braces, one set is removed, and the result is passed to the mapped function. Thus, if your comma list that is being mapped is {a,{b},,{},c} then the arguments passed to the mapped function are ‘a’, ‘{b}’, an empty argument, and ‘c’.

When the comma list is given as an **N**-type argument, spaces have already been trimmed on input, and items are simply stripped of one set of braces if any. This case is more efficient than using **n**-type comma lists.

```
\clist_map_function:NN      ☆  \clist_map_function:NN <comma list> <function>
```

Updated: 2012-06-29

Applies $\langle function \rangle$ to every $\langle item \rangle$ stored in the $\langle comma\ list \rangle$. The $\langle function \rangle$ will receive one argument for each iteration. The $\langle items \rangle$ are returned from left to right. The function **\clist_map_inline:Nn** is in general more efficient than **\clist_map_function:NN**. One mapping may be nested inside another.

```
\clist_map_inline:Nn
```

```
\clist_map_inline:(cn|nn)
```

Updated: 2012-06-29

```
\clist_map_inline:Nn <comma list> {<inline function>}
```

Applies $\langle inline\ function \rangle$ to every $\langle item \rangle$ stored within the $\langle comma\ list \rangle$. The $\langle inline\ function \rangle$ should consist of code which will receive the $\langle item \rangle$ as #1. One in line mapping can be nested inside another. The $\langle items \rangle$ are returned from left to right.

```
\clist_map_variable:Nn      \clist_map_variable:Nn <comma list> <tl var.> {{function using tl var.}}
\clist_map_variable:(cNn|nNn)
```

Updated: 2012-06-29

Stores each entry in the *<comma list>* in turn in the *<tl var.>* and applies the *<function using tl var.>* The *<function>* will usually consist of code making use of the *<tl var.>*, but this is not enforced. One variable mapping can be nested inside another. The *(items)* are returned from left to right.

```
\clist_map_break: ☆      \clist_map_break:
```

Updated: 2012-06-29

Used to terminate a `\clist_map_...` function before all entries in the *<comma list>* have been processed. This will normally take place within a conditional statement, for example

```
\clist_map_inline:Nn \l_my_clist
{
  \str_if_eq:nnTF { #1 } { bingo }
    { \clist_map_break: }
  {
    % Do something useful
  }
}
```

Use outside of a `\clist_map_...` scenario will lead to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted by the internal macro `__prg_break_point:Nn` before further items are taken from the input stream. This will depend on the design of the mapping function.

\clist_map_break:n ☆

Updated: 2012-06-29

\clist_map_break:n {*tokens*}

Used to terminate a \clist_map_... function before all entries in the *comma list* have been processed, inserting the *tokens* after the mapping has ended. This will normally take place within a conditional statement, for example

```
\clist_map_inline:Nn \l_my_clist
{
  \str_if_eq:nnTF { #1 } { bingo }
    { \clist_map_break:n { <tokens> } }
    {
      % Do something useful
    }
}
```

Use outside of a \clist_map_... scenario will lead to low level T_EX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted by the internal macro __prg_break_point:Nn before the *tokens* are inserted into the input stream. This will depend on the design of the mapping function.

\clist_count:N ★

\clist_count:(c|n) ★

New: 2012-07-13

\clist_count:N *comma list*

Leaves the number of items in the *comma list* in the input stream as an *integer denotation*. The total number of items in a *comma list* will include those which are duplicates, *i.e.* every item in a *comma list* is unique.

6 Comma lists as stacks

Comma lists can be used as stacks, where data is pushed to and popped from the top of the comma list. (The left of a comma list is the top, for performance reasons.) The stack functions for comma lists are not intended to be mixed with the general ordered data functions detailed in the previous section: a comma list should either be used as an ordered data type or as a stack, but not in both ways.

\clist_get:NN

\clist_get:cN

Updated: 2012-05-14

\clist_get:NN *comma list* *token list variable*

Stores the left-most item from a *comma list* in the *token list variable* without removing it from the *comma list*. The *token list variable* is assigned locally. If the *comma list* is empty the *token list variable* will contain the marker value \q_no_value.

\clist_get:NNTF

\clist_get:cNTF

New: 2012-05-14

\clist_get:NNTF *comma list* *token list variable* {*true code*} {*false code*}

If the *comma list* is empty, leaves the *false code* in the input stream. The value of the *token list variable* is not defined in this case and should not be relied upon. If the *comma list* is non-empty, stores the top item from the *comma list* in the *token list variable* without removing it from the *comma list*. The *token list variable* is assigned locally.

\clist_pop:NN
\clist_pop:cN

Updated: 2011-09-06

\clist_pop:NN *(comma list)* *(token list variable)*

Pops the left-most item from a *(comma list)* into the *(token list variable)*, i.e. removes the item from the comma list and stores it in the *(token list variable)*. Both of the variables are assigned locally.

\clist_gpop:NN
\clist_gpop:cN

New: 2012-05-14

\clist_gpop:NN *(comma list)* *(token list variable)*

Pops the left-most item from a *(comma list)* into the *(token list variable)*, i.e. removes the item from the comma list and stores it in the *(token list variable)*. The *(comma list)* is modified globally, while the assignment of the *(token list variable)* is local.

\clist_pop:NNTF
\clist_pop:cNTF

New: 2012-05-14

\clist_pop:NNTF *(sequence)* *(token list variable)* {\i(true code)} {\i(false code)}

If the *(comma list)* is empty, leaves the *(false code)* in the input stream. The value of the *(token list variable)* is not defined in this case and should not be relied upon. If the *(comma list)* is non-empty, pops the top item from the *(comma list)* in the *(token list variable)*, i.e. removes the item from the *(comma list)*. Both the *(comma list)* and the *(token list variable)* are assigned locally.

\clist_gpop:NNTF
\clist_gpop:cNTF

New: 2012-05-14

\clist_gpop:NNTF *(comma list)* *(token list variable)* {\i(true code)} {\i(false code)}

If the *(comma list)* is empty, leaves the *(false code)* in the input stream. The value of the *(token list variable)* is not defined in this case and should not be relied upon. If the *(comma list)* is non-empty, pops the top item from the *(comma list)* in the *(token list variable)*, i.e. removes the item from the *(comma list)*. The *(comma list)* is modified globally, while the *(token list variable)* is assigned locally.

\clist_push:Nn
\clist_push:(NV|No|Nx|cn|cV|co|cx)
\clist_gpush:Nn
\clist_gpush:(NV|No|Nx|cn|cV|co|cx)

\clist_push:Nn *(comma list)* {\i{items}}

Adds the {\i{items}} to the top of the *(comma list)*. Spaces are removed from both sides of each item.

7 Viewing comma lists

\clist_show:N
\clist_show:c

Updated: 2012-09-09

\clist_show:N *(comma list)*

Displays the entries in the *(comma list)* in the terminal.

\clist_show:n
\clist_show:n

Updated: 2012-09-09

\clist_show:n {\i{tokens}}

Displays the entries in the comma list in the terminal.

8 Constant and scratch comma lists

`\c_empty_clist`

Constant that is always empty.

New: 2012-07-02

`\l_tmpa_clist`

`\l_tmpb_clist`

New: 2011-09-06

Scratch comma lists for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

`\g_tmpa_clist`

`\g_tmpb_clist`

New: 2011-09-06

Scratch comma lists for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

Part XIV

The `\prop` package

Property lists

L^AT_EX3 implements a “property list” data type, which contain an unordered list of entries each of which consists of a $\langle key \rangle$ and an associated $\langle value \rangle$. The $\langle key \rangle$ and $\langle value \rangle$ may both be any $\langle balanced\ text \rangle$. It is possible to map functions to property lists such that the function is applied to every key–value pair within the list.

Each entry in a property list must have a unique $\langle key \rangle$: if an entry is added to a property list which already contains the $\langle key \rangle$ then the new entry will overwrite the existing one. The $\langle keys \rangle$ are compared on a string basis, using the same method as `\str_if_eq:nn`.

Property lists are intended for storing key-based information for use within code. This is in contrast to key–value lists, which are a form of *input* parsed by the `keys` module.

1 Creating and initialising property lists

`\prop_new:N`
`\prop_new:c`

`\prop_new:N <property list>`

Creates a new $\langle property\ list \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle property\ list \rangle$ will initially contain no entries.

`\prop_clear:N`
`\prop_clear:c`
`\prop_gclear:N`
`\prop_gclear:c`

`\prop_clear:N <property list>`

Clears all entries from the $\langle property\ list \rangle$.

`\prop_clear_new:N`
`\prop_clear_new:c`
`\prop_gclear_new:N`
`\prop_gclear_new:c`

`\prop_clear_new:N <property list>`

Ensures that the $\langle property\ list \rangle$ exists globally by applying `\prop_new:N` if necessary, then applies `\prop_(g)clear:N` to leave the list empty.

`\prop_set_eq:NN`
`\prop_set_eq:(cN|Nc|cc)`
`\prop_gset_eq:NN`
`\prop_gset_eq:(cN|Nc|cc)`

`\prop_set_eq:NN <property list1> <property list2>`

Sets the content of $\langle property\ list_1 \rangle$ equal to that of $\langle property\ list_2 \rangle$.

2 Adding entries to property lists

```
\prop_put:Nnn
\prop_put:(NnV|Nno|Nnx|NVn|NVV|Non|Noo|cnn|cnV|cno|cnx|cVn|cVV|con|coo)
\prop_gput:Nnn
\prop_gput:(NnV|Nno|Nnx|NVn|NVV|Non|Noo|cnn|cnV|cno|cnx|cVn|cVV|con|coo)
```

Updated: 2012-07-09

```
\prop_put:Nnn <property list>
{<key>} {<value>}
```

Adds an entry to the *<property list>* which may be accessed using the *<key>* and which has *<value>*. Both the *<key>* and *<value>* may contain any *<balanced text>*. The *<key>* is stored after processing with `\tl_to_str:n`, meaning that category codes are ignored. If the *<key>* is already present in the *<property list>*, the existing entry is overwritten by the new *<value>*.

```
\prop_put_if_new:Nnn
\prop_put_if_new:cnn
\prop_gput_if_new:Nnn
\prop_gput_if_new:cnn
```

```
\prop_put_if_new:Nnn <property list> {<key>} {<value>}
```

If the *<key>* is present in the *<property list>* then no action is taken. If the *<key>* is not present in the *<property list>* then a new entry is added. Both the *<key>* and *<value>* may contain any *<balanced text>*. The *<key>* is stored after processing with `\tl_to_str:n`, meaning that category codes are ignored.

3 Recovering values from property lists

```
\prop_get:NnN
\prop_get:(NVN|NoN|cnN|cVN|coN)
```

Updated: 2011-08-28

```
\prop_get:NnN <property list> {<key>} <tl var>
```

Recovering the *<value>* stored with *<key>* from the *<property list>*, and places this in the *<token list variable>*. If the *<key>* is not found in the *<property list>* then the *<token list variable>* will contain the special marker `\q_no_value`. The *<token list variable>* is set within the current `TEX` group. See also `\prop_get:NnNTF`.

```
\prop_pop:NnN
\prop_pop:(NoN|cnN|coN)
```

Updated: 2011-08-18

```
\prop_pop:NnN <property list> {<key>} <tl var>
```

Recovering the *<value>* stored with *<key>* from the *<property list>*, and places this in the *<token list variable>*. If the *<key>* is not found in the *<property list>* then the *<token list variable>* will contain the special marker `\q_no_value`. The *<key>* and *<value>* are then deleted from the property list. Both assignments are local. See also `\prop_pop:NnNTF`.

```
\prop_gpop:NnN
\prop_gpop:(NoN|cnN|coN)
```

Updated: 2011-08-18

```
\prop_gpop:NnN <property list> {<key>} <tl var>
```

Recovering the *<value>* stored with *<key>* from the *<property list>*, and places this in the *<token list variable>*. If the *<key>* is not found in the *<property list>* then the *<token list variable>* will contain the special marker `\q_no_value`. The *<key>* and *<value>* are then deleted from the property list. The *<property list>* is modified globally, while the assignment of the *<token list variable>* is local. See also `\prop_gpop:NnNTF`.

4 Modifying property lists

```
\prop_remove:Nn
\prop_remove:(NV|cn|cV)
\prop_gremove:Nn
\prop_gremove:(NV|cn|cV)
```

New: 2012-05-12

```
\prop_remove:Nn <property list> {<key>}
```

Removes the entry listed under *<key>* from the *<property list>*. If the *<key>* is not found in the *<property list>* no change occurs, *i.e.* there is no need to test for the existence of a key before deleting it.

5 Property list conditionals

```
\prop_if_exist_p:N *
\prop_if_exist_p:c *
\prop_if_exist:NTF *
\prop_if_exist:cTF *
```

New: 2012-03-03

```
\prop_if_exist_p:N <property list>
\prop_if_exist:NTF <property list> {<true code>} {<false code>}
```

Tests whether the *<property list>* is currently defined. This does not check that the *<property list>* really is a property list variable.

```
\prop_if_empty_p:N *
\prop_if_empty_p:c *
\prop_if_empty:NTF *
\prop_if_empty:cTF *
```

New: 2012-03-03

```
\prop_if_empty_p:N <property list>
\prop_if_empty:NTF <property list> {<true code>} {<false code>}
```

Tests if the *<property list>* is empty (containing no entries).

```
\prop_if_in_p:Nn
\prop_if_in_p:(NV|No|cn|cV|co)
\prop_if_in:NnTF
\prop_if_in:(NV|No|cn|cV|co)TF *
```

Updated: 2011-09-15

```
* \prop_if_in:NnTF <property list> {<key>} {<true code>} {<false code>}
```

Tests if the *<key>* is present in the *<property list>*, making the comparison using the method described by `\str_if_eq:nnTF`.

TExhackers note: This function iterates through every key-value pair in the *<property list>* and is therefore slower than using the non-expandable `\prop_get:NnTF`.

6 Recovering values from property lists with branching

The functions in this section combine tests for the presence of a key in a property list with recovery of the associated valued. This makes them useful for cases where different cases follow dependent on the presence or absence of a key in a property list. They offer increased readability and performance over separate testing and recovery phases.

```
\prop_get:NnNTF
```

```
\prop_get:(NVN|NoN|cnN|cVN|coN)TF
```

Updated: 2012-05-19

```
\prop_get:NnNTF <property list> {<key>} <token list variable>
{<true code>} {<false code>}
```

If the *<key>* is not present in the *<property list>*, leaves the *<false code>* in the input stream. The value of the *<token list variable>* is not defined in this case and should not be relied upon. If the *<key>* is present in the *<property list>*, stores the corresponding *<value>* in the *<token list variable>* without removing it from the *<property list>*, then leaves the *<true code>* in the input stream. The *<token list variable>* is assigned locally.

```
\prop_pop:NnNTF
```

```
\prop_pop:cnNTF
```

New: 2011-08-18

Updated: 2012-05-19

```
\prop_pop:NnNTF <property list> {<key>} <token list variable> {<true code>}
{<false code>}
```

If the *<key>* is not present in the *<property list>*, leaves the *<false code>* in the input stream. The value of the *<token list variable>* is not defined in this case and should not be relied upon. If the *<key>* is present in the *<property list>*, pops the corresponding *<value>* in the *<token list variable>*, *i.e.* removes the item from the *<property list>*. Both the *<property list>* and the *<token list variable>* are assigned locally.

```
\prop_gpop:NnNTF
```

```
\prop_gpop:cnNTF
```

New: 2011-08-18

Updated: 2012-05-19

```
\prop_gpop:NnNTF <property list> {<key>} <token list variable> {<true code>}
{<false code>}
```

If the *<key>* is not present in the *<property list>*, leaves the *<false code>* in the input stream. The value of the *<token list variable>* is not defined in this case and should not be relied upon. If the *<key>* is present in the *<property list>*, pops the corresponding *<value>* in the *<token list variable>*, *i.e.* removes the item from the *<property list>*. The *<property list>* is modified globally, while the *<token list variable>* is assigned locally.

7 Mapping to property lists

```
\prop_map_function>NN ★
```

```
\prop_map_function:CN ★
```

Updated: 2012-06-29

```
\prop_map_function:NN <property list> <function>
```

Applies *<function>* to every *<entry>* stored in the *<property list>*. The *<function>* will receive two argument for each iteration: the *<key>* and associated *<value>*. The order in which *<entries>* are returned is not defined and should not be relied upon.

```
\prop_map_inline:Nn
```

```
\prop_map_inline:cn
```

Updated: 2012-06-29

```
\prop_map_inline:Nn <property list> {<inline function>}
```

Applies *<inline function>* to every *<entry>* stored within the *<property list>*. The *<inline function>* should consist of code which will receive the *<key>* as #1 and the *<value>* as #2. The order in which *<entries>* are returned is not defined and should not be relied upon.

\prop_map_break: ☆

Updated: 2012-06-29

\prop_map_break:

Used to terminate a \prop_map_... function before all entries in the *property list* have been processed. This will normally take place within a conditional statement, for example

```
\prop_map_inline:Nn \l_my_prop
{
    \str_if_eq:nnTF { #1 } { bingo }
        { \prop_map_break: }
    {
        % Do something useful
    }
}
```

Use outside of a \prop_map_... scenario will lead to low level T_EX errors.

\prop_map_break:n ☆

Updated: 2012-06-29

\prop_map_break:n {<tokens>}

Used to terminate a \prop_map_... function before all entries in the *property list* have been processed, inserting the <tokens> after the mapping has ended. This will normally take place within a conditional statement, for example

```
\prop_map_inline:Nn \l_my_prop
{
    \str_if_eq:nnTF { #1 } { bingo }
        { \prop_map_break:n { <tokens> } }
    {
        % Do something useful
    }
}
```

Use outside of a \prop_map_... scenario will lead to low level T_EX errors.

8 Viewing property lists

\prop_show:N**\prop_show:c**

Updated: 2012-09-09

\prop_show:N <property list>

Displays the entries in the <property list> in the terminal.

9 Scratch property lists

\l_tmpa_prop

\l_tmpb_prop

New: 2012-06-23

Scratch property lists for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

\g_tmpa_prop

\g_tmpb_prop

New: 2012-06-23

Scratch property lists for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

10 Constants

\c_empty_prop

A permanently-empty property list used for internal comparisons.

11 Internal property list functions

\q_prop

The internal token used to separate out property list entries, separating both the *<key>* from the *<value>* and also one entry from another.

_prop_split:NnTF *property list* {*key*} {*true code*} {*false code*}

Splits the *<property list>* at the *<key>*, giving three groups: the *<extract>* of *<property list>* before the *<key>*, the *<value>* associated with the *<key>* and the *<extract>* of the *<property list>* after the *<value>*. The first *<extract>* retains the internal structure of a property list. The second is only missing the leading separator \q_prop. This ensures that the concatenation of the two *<extracts>* is a property list. If the *<key>* is present in the *<property list>* then the *<true code>* is left in the input stream, followed by the three groups: thus the *<true code>* should properly absorb three arguments. If the *<key>* is not present in the *<property list>* then the *<false code>* is left in the input stream, with no trailing material. The *<key>* comparison takes place as described for \str_if_eq:nn.

Part XV

The **I3box** package

Boxes

There are three kinds of box operations: horizontal mode denoted with prefix `\hbox_`, vertical mode with prefix `\vbox_`, and the generic operations working in both modes with prefix `\box_`.

1 Creating and initialising boxes

`\box_new:N` *<box>*

`\box_new:c`

Creates a new *<box>* or raises an error if the name is already taken. The declaration is global. The *<box>* will initially be void.

`\box_clear:N` *<box>*

`\box_clear:c`

`\box_gclear:N`

`\box_gclear:c`

Clears the content of the *<box>* by setting the box equal to `\c_void_box`.

`\box_clear_new:N` *<box>*

`\box_clear_new:c`

`\box_gclear_new:N`

`\box_gclear_new:c`

Ensures that the *<box>* exists globally by applying `\box_new:N` if necessary, then applies `\box_(g)clear:N` to leave the *<box>* empty.

`\box_set_eq:NN`

`\box_set_eq:(cN|Nc|cc)`

`\box_gset_eq:NN`

`\box_gset_eq:(cN|Nc|cc)`

`\box_set_eq:NN` *<box₁>* *<box₂>*

Sets the content of *<box₁>* equal to that of *<box₂>*.

`\box_set_eq_clear:NN`

`\box_set_eq_clear:(cN|Nc|cc)`

`\box_set_eq_clear:NN` *<box₁>* *<box₂>*

Sets the content of *<box₁>* within the current TeX group equal to that of *<box₂>*, then clears *<box₂>* globally.

`\box_gset_eq_clear:NN`

`\box_gset_eq_clear:(cN|Nc|cc)`

`\box_gset_eq_clear:NN` *<box₁>* *<box₂>*

Sets the content of *<box₁>* equal to that of *<box₂>*, then clears *<box₂>*. These assignments are global.

`\box_if_exist_p:N` * `\box_if_exist_p:N <box>`
`\box_if_exist_p:c` * `\box_if_exist:NTF <box> {\<true code>} {\<false code>}`
`\box_if_exist:NTF` * Tests whether the `<box>` is currently defined. This does not check that the `<box>` really is a box.
`\box_if_exist:cTF` *

New: 2012-03-03

2 Using boxes

`\box_use:N` `\box_use:N <box>`

`\box_use:c` Inserts the current content of the `<box>` onto the current list for typesetting.

TeXhackers note: This is the TeX primitive `\copy`.

`\box_use_clear:N`

`\box_use_clear:c` `\box_use_clear:N <box>`

Inserts the current content of the `<box>` onto the current list for typesetting, then globally clears the content of the `<box>`.

TeXhackers note: This is the TeX primitive `\box`.

`\box_move_right:nn`

`\box_move_left:nn`

`\box_move_right:nn {\<dimexpr>} {\<box function>}`

This function operates in vertical mode, and inserts the material specified by the `<box function>` such that its reference point is displaced horizontally by the given `<dimexpr>` from the reference point for typesetting, to the right or left as appropriate. The `<box function>` should be a box operation such as `\box_use:N <box>` or a “raw” box specification such as `\vbox:n { xyz }`.

`\box_move_up:nn`

`\box_move_down:nn`

`\box_move_up:nn {\<dimexpr>} {\<box function>}`

This function operates in horizontal mode, and inserts the material specified by the `<box function>` such that its reference point is displaced vertical by the given `<dimexpr>` from the reference point for typesetting, up or down as appropriate. The `<box function>` should be a box operation such as `\box_use:N <box>` or a “raw” box specification such as `\vbox:n { xyz }`.

3 Measuring and setting box dimensions

`\box_dp:N`

`\box_dp:c`

`\box_dp:N <box>`

Calculates the depth (below the baseline) of the `<box>` in a form suitable for use in a `<dimension expression>`.

TeXhackers note: This is the TeX primitive `\dp`.

`\box_ht:N` `\box_ht:c` `\box_ht:N <box>`
Calculates the height (above the baseline) of the `<box>` in a form suitable for use in a *(dimension expression)*.

TeXhackers note: This is the TeX primitive `\ht`.

`\box_wd:N` `\box_wd:c` `\box_wd:N <box>`
Calculates the width of the `<box>` in a form suitable for use in a *(dimension expression)*.

TeXhackers note: This is the TeX primitive `\wd`.

`\box_set_dp:Nn` `\box_set_dp:cn` `\box_set_dp:Nn <box> {<dimension expression>}`
Set the depth (below the baseline) of the `<box>` to the value of the `{<dimension expression>}`. This is a global assignment.
Updated: 2011-10-22

`\box_set_ht:Nn` `\box_set_ht:cn` `\box_set_ht:Nn <box> {<dimension expression>}`
Set the height (above the baseline) of the `<box>` to the value of the `{<dimension expression>}`. This is a global assignment.
Updated: 2011-10-22

`\box_set_wd:Nn` `\box_set_wd:cn` `\box_set_wd:Nn <box> {<dimension expression>}`
Set the width of the `<box>` to the value of the `{<dimension expression>}`. This is a global assignment.
Updated: 2011-10-22

4 Box conditionals

`\box_if_empty_p:N *` `\box_if_empty_p:N <box>`
`\box_if_empty_p:c *` `\box_if_empty:NTF <box> {<true code>} {<false code>}`
`\box_if_empty:NTF *` Tests if `<box>` is a empty (equal to `\c_empty_box`).
`\box_if_empty:cTF *`

`\box_if_horizontal_p:N *` `\box_if_horizontal_p:N <box>`
`\box_if_horizontal_p:c *` `\box_if_horizontal:NTF <box> {<true code>} {<false code>}`
`\box_if_horizontal:NTF *` Tests if `<box>` is a horizontal box.
`\box_if_horizontal:cTF *`

`\box_if_vertical_p:N *` `\box_if_vertical_p:N <box>`
`\box_if_vertical_p:c *` `\box_if_vertical:NTF <box> {<true code>} {<false code>}`
`\box_if_vertical:NTF *` Tests if `<box>` is a vertical box.
`\box_if_vertical:cTF *`

5 The last box inserted

\box_set_to_last:N
\box_set_to_last:c
\box_gset_to_last:N
\box_gset_to_last:c

\box_set_to_last:N *box*

Sets the *box* equal to the last item (box) added to the current partial list, removing the item from the list at the same time. When applied to the main vertical list, the *box* will always be void as it is not possible to recover the last added item.

6 Constant boxes

\c_empty_box

This is a permanently empty box, which is neither set as horizontal nor vertical.

7 Scratch boxes

\l_tmpa_box
\l_tmpb_box

Scratch boxes for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

\g_tmpa_box
\g_tmpb_box

Scratch boxes for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

8 Viewing box contents

\box_show:N
\box_show:c

Updated: 2012-05-11

\box_show:N *box*

Shows full details of the content of the *box* in the terminal.

\box_show:Nnn
\box_show:cnn

New: 2012-05-11

\box_show:Nnn *box* *intexpr*₁ *intexpr*₂

Display the contents of *box* in the terminal, showing the first *intexpr*₁ items of the box, and descending into *intexpr*₂ group levels.

\box_log:N
\box_log:c

New: 2012-05-11

\box_log:N *box*

Writes full details of the content of the *box* to the log.

\box_log:Nnn
\box_log:cnn

New: 2012-05-11

\box_log:Nnn *box* *intexpr*₁ *intexpr*₂

Writes the contents of *box* to the log, showing the first *intexpr*₁ items of the box, and descending into *intexpr*₂ group levels.

9 Horizontal mode boxes

\hbox:n \hbox:n {*contents*}

Typesets the *contents* into a horizontal box of natural width and then includes this box in the current list for typesetting.

TeXhackers note: This is the TeX primitive \hbox.

\hbox_to_wd:nn \hbox_to_wd:nn {*dimexpr*} {*contents*}

Typesets the *contents* into a horizontal box of width *dimexpr* and then includes this box in the current list for typesetting.

\hbox_to_zero:n \hbox_to_zero:n {*contents*}

Typesets the *contents* into a horizontal box of zero width and then includes this box in the current list for typesetting.

\hbox_set:Nn
\hbox_set:cN
\hbox_gset:Nn
\hbox_gset:cN

\hbox_set:Nn *box* {*contents*}

Typesets the *contents* at natural width and then stores the result inside the *box*.

\hbox_set_to_wd:Nnn
\hbox_set_to_wd:cnn
\hbox_gset_to_wd:Nnn
\hbox_gset_to_wd:cnn

\hbox_set_to_wd:Nnn *box* {*dimexpr*} {*contents*}

Typesets the *contents* to the width given by the *dimexpr* and then stores the result inside the *box*.

\hbox_overlap_right:n \hbox_overlap_right:n {*contents*}

Typesets the *contents* into a horizontal box of zero width such that material will protrude to the right of the insertion point.

\hbox_overlap_left:n \hbox_overlap_left:n {*contents*}

Typesets the *contents* into a horizontal box of zero width such that material will protrude to the left of the insertion point.

\hbox_set:Nw
\hbox_set:cW
\hbox_set_end:
\hbox_gset:Nw
\hbox_gset:cW
\hbox_gset_end:

\hbox_set:Nw *box* {*contents*} \hbox_set_end:

Typesets the *contents* at natural width and then stores the result inside the *box*. In contrast to \hbox_set:Nn this function does not absorb the argument when finding the *content*, and so can be used in circumstances where the *content* may not be a simple argument.

`\hbox_unpack:N`
`\hbox_unpack:c`

`\hbox_unpack:N <box>`

Unpacks the content of the horizontal $\langle box \rangle$, retaining any stretching or shrinking applied when the $\langle box \rangle$ was set.

TeXhackers note: This is the TeX primitive `\unhcopy`.

`\hbox_unpack_clear:N`
`\hbox_unpack_clear:c`

`\hbox_unpack_clear:N <box>`

Unpacks the content of the horizontal $\langle box \rangle$, retaining any stretching or shrinking applied when the $\langle box \rangle$ was set. The $\langle box \rangle$ is then cleared globally.

TeXhackers note: This is the TeX primitive `\unhbox`.

10 Vertical mode boxes

Vertical boxes inherit their baseline from their contents. The standard case is that the baseline of the box is at the same position as that of the last item added to the box. This means that the box will have no depth unless the last item added to it had depth. As a result most vertical boxes have a large height value and small or zero depth. The exception are `_top` boxes, where the reference point is that of the first item added. These tend to have a large depth and small height, although the latter will typically be non-zero.

`\vbox:n`

Updated: 2011-12-18

`\vbox:n {\<contents>}`

Typesets the $\langle contents \rangle$ into a vertical box of natural height and includes this box in the current list for typesetting.

TeXhackers note: This is the TeX primitive `\vbox`.

`\vbox_top:n`

Updated: 2011-12-18

`\vbox_top:n {\<contents>}`

Typesets the $\langle contents \rangle$ into a vertical box of natural height and includes this box in the current list for typesetting. The baseline of the box will be equal to that of the *first* item added to the box.

TeXhackers note: This is the TeX primitive `\vtop`.

`\vbox_to_ht:nn`

Updated: 2011-12-18

`\vbox_to_ht:nn {\<dimexpr>} {\<contents>}`

Typesets the $\langle contents \rangle$ into a vertical box of height $\langle dimexpr \rangle$ and then includes this box in the current list for typesetting.

`\vbox_to_zero:n`

Updated: 2011-12-18

`\vbox_to_zero:n {\<contents>}`

Typesets the $\langle contents \rangle$ into a vertical box of zero height and then includes this box in the current list for typesetting.

```
\vbox_set:Nn
\vbox_set:cn
\vbox_gset:Nn
\vbox_gset:cn
```

Updated: 2011-12-18

```
\vbox_set:Nn <box> {{contents}}
```

Typesets the *contents* at natural height and then stores the result inside the *box*.

```
\vbox_set_top:Nn
\vbox_set_top:cn
\vbox_gset_top:Nn
\vbox_gset_top:cn
```

Updated: 2011-12-18

```
\vbox_set_top:Nn <box> {{contents}}
```

Typesets the *contents* at natural height and then stores the result inside the *box*. The baseline of the box will be equal to that of the *first* item added to the box.

```
\vbox_set_to_ht:Nnn
\vbox_set_to_ht:cnn
\vbox_gset_to_ht:Nnn
\vbox_gset_to_ht:cnn
```

Updated: 2011-12-18

```
\vbox_set_to_ht:Nnn <box> {<dimexpr>} {{contents}}
```

Typesets the *contents* to the height given by the *dimexpr* and then stores the result inside the *box*.

```
\vbox_set:Nw
\vbox_set:cw
\vbox_set_end:
\vbox_gset:Nw
\vbox_gset:cw
\vbox_gset_end:
```

Updated: 2011-12-18

```
\vbox_set:Nw <box> <contents> \vbox_set_end:
```

Typesets the *contents* at natural height and then stores the result inside the *box*. In contrast to `\vbox_set:Nn` this function does not absorb the argument when finding the *content*, and so can be used in circumstances where the *content* may not be a simple argument.

```
\vbox_set_split_to_ht>NNn
```

Updated: 2011-10-22

```
\vbox_set_split_to_ht>NNn <box1> <box2> {<dimexpr>}
```

Sets *box₁* to contain material to the height given by the *dimexpr* by removing content from the top of *box₂* (which must be a vertical box).

TeXhackers note: This is the TeX primitive `\vsplit`.

```
\vbox_unpack:N
\vbox_unpack:c
```

```
\vbox_unpack:N <box>
```

Unpacks the content of the vertical *box*, retaining any stretching or shrinking applied when the *box* was set.

TeXhackers note: This is the TeX primitive `\unvcopy`.

```
\vbox_unpack_clear:N
\vbox_unpack_clear:c
```

```
\vbox_unpack:N <box>
```

Unpacks the content of the vertical *box*, retaining any stretching or shrinking applied when the *box* was set. The *box* is then cleared globally.

TeXhackers note: This is the TeX primitive `\unvbox`.

11 Primitive box conditionals

\if_hbox:N \star \if_hbox:N $\langle box \rangle$
 ⟨true code⟩
 \else:
 ⟨false code⟩
 \fi:

Tests is $\langle box \rangle$ is a horizontal box.

TeXhackers note: This is the TeX primitive \ifhbox.

\if_vbox:N \star \if_vbox:N $\langle box \rangle$
 ⟨true code⟩
 \else:
 ⟨false code⟩
 \fi:

Tests is $\langle box \rangle$ is a vertical box.

TeXhackers note: This is the TeX primitive \ifvbox.

\if_box_empty:N \star \if_box_empty:N $\langle box \rangle$
 ⟨true code⟩
 \else:
 ⟨false code⟩
 \fi:

Tests is $\langle box \rangle$ is an empty (void) box.

TeXhackers note: This is the TeX primitive \ifvoid.

Part XVI

The l3coffins package

Coffin code layer

The material in this module provides the low-level support system for coffins. For details about the design concept of a coffin, see the `xcoffins` module (in the `l3experimental` bundle).

1 Creating and initialising coffins

`\coffin_new:N` `\coffin_new:c`

New: 2011-08-17

`\coffin_new:N <coffin>`

Creates a new `<coffin>` or raises an error if the name is already taken. The declaration is global. The `<coffin>` will initially be empty.

`\coffin_clear:N` `\coffin_clear:c`

New: 2011-08-17

`\coffin_clear:N <coffin>`

Clears the content of the `<coffin>` within the current TeX group level.

`\coffin_set_eq:NN` `\coffin_set_eq:(Nc|cN|cc)`

New: 2011-08-17

`\coffin_set_eq:NN <coffin1> <coffin2>`

Sets both the content and poles of `<coffin1>` equal to those of `<coffin2>` within the current TeX group level.

`\coffin_if_exist_p:N` * `\coffin_if_exist_p:c` *

`\coffin_if_exist:NTF` * `\coffin_if_exist:cTF` *

New: 2012-06-20

`\coffin_if_exist_p:N <box>`

`\coffin_if_exist:NTF <box> {<true code>} {<false code>}`

Tests whether the `<coffin>` is currently defined.

2 Setting coffin content and poles

All coffin functions create and manipulate coffins locally within the current TeX group level.

`\hcoffin_set:Nn` `\hcoffin_set:cn`

New: 2011-08-17

Updated: 2011-09-03

`\hcoffin_set:Nn <coffin> {<material>}`

Typesets the `<material>` in horizontal mode, storing the result in the `<coffin>`. The standard poles for the `<coffin>` are then set up based on the size of the typeset material.

```
\hcoffin_set:Nw
\hcoffin_set:cw
\hcoffin_set_end:
```

New: 2011-09-10

```
\hcoffin_set:Nw <coffin> <material> \hcoffin_set_end:
```

Typesets the *<material>* in horizontal mode, storing the result in the *<coffin>*. The standard poles for the *<coffin>* are then set up based on the size of the typeset material. These functions are useful for setting the entire contents of an environment in a coffin.

```
\vcoffin_set:Nnn
\vcoffin_set:cnn
```

New: 2011-08-17
Updated: 2012-05-22

```
\vcoffin_set:Nnn <coffin> {<width>} {<material>}
```

Typesets the *<material>* in vertical mode constrained to the given *<width>* and stores the result in the *<coffin>*. The standard poles for the *<coffin>* are then set up based on the size of the typeset material.

```
\vcoffin_set:Nnw
\vcoffin_set:cnw
\vcoffin_set_end:
```

New: 2011-09-10
Updated: 2012-05-22

```
\vcoffin_set:Nnw <coffin> {<width>} <material> \vcoffin_set_end:
```

Typesets the *<material>* in vertical mode constrained to the given *<width>* and stores the result in the *<coffin>*. The standard poles for the *<coffin>* are then set up based on the size of the typeset material. These functions are useful for setting the entire contents of an environment in a coffin.

```
\coffin_set_horizontal_pole:Nnn \coffin_set_horizontal_pole:Nnn <coffin>
\coffin_set_horizontal_pole:cnn   {<pole>} {<offset>}
```

New: 2012-07-20

Sets the *<pole>* to run horizontally through the *<coffin>*. The *<pole>* will be located at the *<offset>* from the bottom edge of the bounding box of the *<coffin>*. The *<offset>* should be given as a dimension expression.

```
\coffin_set_vertical_pole:Nnn \coffin_set_vertical_pole:Nnn <coffin> {<pole>} {<offset>}
\coffin_set_vertical_pole:cnn
```

New: 2012-07-20

Sets the *<pole>* to run vertically through the *<coffin>*. The *<pole>* will be located at the *<offset>* from the left-hand edge of the bounding box of the *<coffin>*. The *<offset>* should be given as a dimension expression.

3 Joining and using coffins

<pre>\coffin_attach:NnnNnnnn \coffin_attach:(cnnNnnnn Nnnccnnnn cnncnnnn)</pre>	<pre>\coffin_attach:NnnNnnnn <coffin₁> {<coffin₁-pole₁>} {<coffin₁-pole₂>} <coffin₂> {<coffin₂-pole₁>} {<coffin₂-pole₂>} {<x-offset>} {<y-offset>}</pre>
---	--

This function attaches $\langle \text{coffin}_2 \rangle$ to $\langle \text{coffin}_1 \rangle$ such that the bounding box of $\langle \text{coffin}_1 \rangle$ is not altered, *i.e.* $\langle \text{coffin}_2 \rangle$ can protrude outside of the bounding box of the coffin. The alignment is carried out by first calculating $\langle \text{handle}_1 \rangle$, the point of intersection of $\langle \text{coffin}_1\text{-pole}_1 \rangle$ and $\langle \text{coffin}_1\text{-pole}_2 \rangle$, and $\langle \text{handle}_2 \rangle$, the point of intersection of $\langle \text{coffin}_2\text{-pole}_1 \rangle$ and $\langle \text{coffin}_2\text{-pole}_2 \rangle$. $\langle \text{coffin}_2 \rangle$ is then attached to $\langle \text{coffin}_1 \rangle$ such that the relationship between $\langle \text{handle}_1 \rangle$ and $\langle \text{handle}_2 \rangle$ is described by the $\langle x\text{-offset} \rangle$ and $\langle y\text{-offset} \rangle$. The two offsets should be given as dimension expressions.

<pre>\coffin_join:NnnNnnnn \coffin_join:(cnnNnnnn Nnnccnnnn cnncnnnn)</pre>	<pre>\coffin_join:NnnNnnnn <coffin₁> {<coffin₁-pole₁>} {<coffin₁-pole₂>} <coffin₂> {<coffin₂-pole₁>} {<coffin₂-pole₂>} {<x-offset>} {<y-offset>}</pre>
---	--

This function joins $\langle \text{coffin}_2 \rangle$ to $\langle \text{coffin}_1 \rangle$ such that the bounding box of $\langle \text{coffin}_1 \rangle$ may expand. The new bounding box will cover the area containing the bounding boxes of the two original coffins. The alignment is carried out by first calculating $\langle \text{handle}_1 \rangle$, the point of intersection of $\langle \text{coffin}_1\text{-pole}_1 \rangle$ and $\langle \text{coffin}_1\text{-pole}_2 \rangle$, and $\langle \text{handle}_2 \rangle$, the point of intersection of $\langle \text{coffin}_2\text{-pole}_1 \rangle$ and $\langle \text{coffin}_2\text{-pole}_2 \rangle$. $\langle \text{coffin}_2 \rangle$ is then attached to $\langle \text{coffin}_1 \rangle$ such that the relationship between $\langle \text{handle}_1 \rangle$ and $\langle \text{handle}_2 \rangle$ is described by the $\langle x\text{-offset} \rangle$ and $\langle y\text{-offset} \rangle$. The two offsets should be given as dimension expressions.

<pre>\coffin_typeset:Nnnnn \coffin_typeset:cnnnn</pre>	<pre>\coffin_typeset:Nnnnn <coffin> {<pole₁>} {<pole₂>} {<x-offset>} {<y-offset>}</pre>
--	---

Updated: 2012-07-20

Typesetting is carried out by first calculating $\langle \text{handle} \rangle$, the point of intersection of $\langle \text{pole}_1 \rangle$ and $\langle \text{pole}_2 \rangle$. The coffin is then typeset in horizontal mode such that the relationship between the current reference point in the document and the $\langle \text{handle} \rangle$ is described by the $\langle x\text{-offset} \rangle$ and $\langle y\text{-offset} \rangle$. The two offsets should be given as dimension expressions. Typesetting a coffin is therefore analogous to carrying out an alignment where the “parent” coffin is the current insertion point.

4 Measuring coffins

<pre>\coffin_dp:N \coffin_dp:c</pre>	<pre>\coffin_dp:N <coffin></pre>
--------------------------------------	--

Calculates the depth (below the baseline) of the $\langle \text{coffin} \rangle$ in a form suitable for use in a $\langle \text{dimension expression} \rangle$.

```
\coffin_ht:N  
\coffin_ht:c
```

```
\coffin_ht:N <coffin>
```

Calculates the height (above the baseline) of the *<coffin>* in a form suitable for use in a *(dimension expression)*.

```
\coffin_wd:N  
\coffin_wd:c
```

```
\coffin_wd:N <coffin>
```

Calculates the width of the *<coffin>* in a form suitable for use in a *(dimension expression)*.

5 Coffin diagnostics

```
\coffin_display_handles:Nn  
\coffin_display_handles:cn
```

Updated: 2011-09-02

```
\coffin_display_handles:Nn <coffin> {{<colour>}}
```

This function first calculates the intersections between all of the *(poles)* of the *<coffin>* to give a set of *(handles)*. It then prints the *<coffin>* at the current location in the source, with the position of the *(handles)* marked on the coffin. The *(handles)* will be labelled as part of this process: the locations of the *(handles)* and the labels are both printed in the *(colour)* specified.

```
\coffin_mark_handle:Nnnn  
\coffin_mark_handle:cnnn
```

Updated: 2011-09-02

```
\coffin_mark_handle:Nnnn <coffin> {{<pole1>}} {{<pole2>}} {{<colour>}}
```

This function first calculates the *(handle)* for the *<coffin>* as defined by the intersection of *<pole₁>* and *<pole₂>*. It then marks the position of the *(handle)* on the *<coffin>*. The *(handle)* will be labelled as part of this process: the location of the *(handle)* and the label are both printed in the *(colour)* specified.

```
\coffin_show_structure:N  
\coffin_show_structure:c
```

Updated: 2012-09-09

```
\coffin_show_structure:N <coffin>
```

This function shows the structural information about the *<coffin>* in the terminal. The width, height and depth of the typeset material are given, along with the location of all of the poles of the coffin.

Notice that the poles of a coffin are defined by four values: the *x* and *y* co-ordinates of a point that the pole passes through and the *x*- and *y*-components of a vector denoting the direction of the pole. It is the ratio between the later, rather than the absolute values, which determines the direction of the pole.

5.1 Constants and variables

```
\c_empty_coffin
```

A permanently empty coffin.

```
\l_tmpa_coffin
```

```
\l_tmpb_coffin
```

New: 2012-06-19

Scratch coffins for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

Part XVII

The l3color package

Colour support

This module provides support for color in L^AT_EX3. At present, the material here is mainly intended to support a small number of low-level requirements in other l3kernel modules.

1 Colour in boxes

Controlling the color of text in boxes requires a small number of control functions, so that the boxed material uses the color at the point where it is set, rather than where it is used.

```
\color_group_begin:  
\color_group_end:  
_____
```

New: 2011-09-03

`\color_group_begin:`
`\color_group_end:`
`...`
`\color_group_end:`

Creates a color group: one used to “trap” color settings.

```
\color_ensure_current:  
_____
```

New: 2011-09-03

`\color_ensure_current:`

Ensures that material inside a box will use the foreground color at the point where the box is set, rather than that in force when the box is used. This function should usually be used within a `\color_group_begin: ... \color_group_end:` group.

Part XVIII

The `I3msg` package

Messages

Messages need to be passed to the user by modules, either when errors occur or to indicate how the code is proceeding. The `I3msg` module provides a consistent method for doing this (as opposed to writing directly to the terminal or log).

The system used by `I3msg` to create messages divides the process into two distinct parts. Named messages are created in the first part of the process; at this stage, no decision is made about the type of output that the message will produce. The second part of the process is actually producing a message. At this stage a choice of message *class* has to be made, for example `error`, `warning` or `info`.

By separating out the creation and use of messages, several benefits are available. First, the messages can be altered later without needing details of where they are used in the code. This makes it possible to alter the language used, the detail level and so on. Secondly, the output which results from a given message can be altered. This can be done on a message class, module or message name basis. In this way, message behaviour can be altered and messages can be entirely suppressed.

1 Creating new messages

All messages have to be created before they can be used. The text of messages will automatically be wrapped to the length available in the console. As a result, formatting is only needed where it will help to show meaning. In particular, `\n` may be used to force a new line and `\u` forces an explicit space. Additionally, `\{`, `\#`, `\}`, `\%` and `\~` can be used to produce the corresponding character.

Messages may be subdivided *by one level* using the `/` character. This is used within the message filtering system to allow for example the L^AT_EX kernel messages to belong to the module L^AT_EX while still being filterable at a more granular level. Thus for example

```
\msg_new:nnnn { mymodule } { submodule / message } ...
```

will allow only those messages from the `submodule` to be filtered out.

`\msg_new:nnnn`

`\msg_new:nnn`

Updated: 2011-08-16

`\msg_new:nnnn {\langle module \rangle} {\langle message \rangle} {\langle text \rangle} {\langle more text \rangle}`

Creates a *message* for a given *module*. The message will be defined to first give *text* and then *more text* if the user requests it. If no *more text* is available then a standard text is given instead. Within *text* and *more text* four parameters (#1 to #4) can be used: these will be supplied at the time the message is used. An error will be raised if the *message* already exists.

\msg_set:nnnn
\msg_set:nn
\msg_gset:nnnn
\msg_gset:nn

`\msg_set:nnnn {⟨module⟩} {⟨message⟩} {⟨text⟩} {⟨more text⟩}`

Sets up the text for a *⟨message⟩* for a given *⟨module⟩*. The message will be defined to first give *⟨text⟩* and then *⟨more text⟩* if the user requests it. If no *⟨more text⟩* is available then a standard text is given instead. Within *⟨text⟩* and *⟨more text⟩* four parameters (#1 to #4) can be used: these will be supplied at the time the message is used.

\msg_if_exist_p:mn ★
\msg_if_exist:nnTF ★

New: 2012-03-03

`\msg_if_exist_p:mn {⟨module⟩} {⟨message⟩}`

`\msg_if_exist:nnTF {⟨module⟩} {⟨message⟩} {⟨true code⟩} {⟨false code⟩}`

Tests whether the *⟨message⟩* for the *⟨module⟩* is currently defined.

2 Contextual information for messages

\msg_line_context: ★

`\msg_line_context:`

Prints the current line number when a message is given, and thus suitable for giving context to messages. The number itself is proceeded by the text `on line`.

\msg_line_number: ★

`\msg_line_number:`

Prints the current line number when a message is given.

\msg_fatal_text:n ★

`\msg_fatal_text:n {⟨module⟩}`

Produces the standard text

`Fatal ⟨module⟩ error`

This function can be redefined to alter the language in which the message is given, using #1 as the name of the *⟨module⟩* to be included.

\msg_critical_text:n ★

`\msg_critical_text:n {⟨module⟩}`

Produces the standard text

`Critical ⟨module⟩ error`

This function can be redefined to alter the language in which the message is given, using #1 as the name of the *⟨module⟩* to be included.

\msg_error_text:n ★

`\msg_error_text:n {⟨module⟩}`

Produces the standard text

`⟨module⟩ error`

This function can be redefined to alter the language in which the message is given, using #1 as the name of the *⟨module⟩* to be included.

\msg_warning_text:n *

\msg_warning_text:n {<module>}

Produces the standard text

<module> warning

This function can be redefined to alter the language in which the message is given, using #1 as the name of the **<module>** to be included.

\msg_info_text:n *

\msg_info_text:n {<module>}

Produces the standard text:

<module> info

This function can be redefined to alter the language in which the message is given, using #1 as the name of the **<module>** to be included.

\msg_see_documentation_text:n *

\msg_see_documentation_text:n {<module>}

Produces the standard text

See the <module> documentation for further information.

This function can be redefined to alter the language in which the message is given, using #1 as the name of the **<module>** to be included.

3 Issuing messages

Messages behave differently depending on the message class. In all cases, the message may be issued supplying 0 to 4 arguments. If the number of arguments supplied here does not match the number in the definition of the message, extra arguments will be ignored, or empty arguments added (of course the sense of the message may be impaired). The four arguments will be converted to strings before being added to the message text: the x-type variants should be used to expand material.

\msg_fatal:nnnnnn

\msg_fatal:(nnnnn|nnnn|nnn|nn|nnxxxx|nnxxx|nnxx|nnx)

\msg_fatal:nnnnnn {<module>} {<message>} {<arg one>}

{<arg two>} {<arg three>} {<arg four>}

Updated: 2012-08-11

Issues **<module>** error **<message>**, passing **<arg one>** to **<arg four>** to the text-creating functions. After issuing a fatal error the TeX run will halt.

```
\msg_critical:nnnnnn
```

```
\msg_critical:(nnnn|nnnn|nnn|nn|nnxxxx|nnxxx|nnxx|nnx)
```

Updated: 2012-08-11

```
\msg_critical:nnnnnn {\<module>} {\<message>} {\<arg one>} {\<arg two>} {\<arg three>} {\<arg four>}
```

Issues *<module>* error *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. After issuing a critical error, TeX will stop reading the current input file. This may halt the TeX run (if the current file is the main file) or may abort reading a sub-file.

TeXhackers note: The TeX \endinput primitive is used to exit the file. In particular, the rest of the current line remains in the input stream.

```
\msg_error:nnnnnn
```

```
\msg_error:(nnnn|nnnn|nnn|nn|nnxxxx|nnxxx|nnxx|nnx)
```

Updated: 2012-08-11

```
\msg_error:nnnnnn {\<module>} {\<message>} {\<arg one>} {\<arg two>} {\<arg three>} {\<arg four>}
```

Issues *<module>* error *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. The error will interrupt processing and issue the text at the terminal. After user input, the run will continue.

```
\msg_warning:nnnnnn
```

```
\msg_warning:(nnnn|nnnn|nnn|nn|nnxxxx|nnxxx|nnxx|nnx)
```

Updated: 2012-08-11

```
\msg_warning:nnxxxx {\<module>} {\<message>} {\<arg one>} {\<arg two>} {\<arg three>} {\<arg four>}
```

Issues *<module>* warning *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. The warning text will be added to the log file and the terminal, but the TeX run will not be interrupted.

```
\msg_info:nnnnnn
```

```
\msg_info:(nnnn|nnnn|nnn|nn|nnxxxx|nnxxx|nnxx|nnx)
```

Updated: 2012-08-11

```
\msg_info:nnnnnn {\<module>} {\<message>} {\<arg one>} {\<arg two>} {\<arg three>} {\<arg four>}
```

Issues *<module>* information *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. The information text will be added to the log file.

```
\msg_log:nnnnnn
```

```
\msg_log:(nnnn|nnnn|nnn|nn|nnxxxx|nnxxx|nnxx|nnx)
```

Updated: 2012-08-11

```
\msg_log:nnnnnn {\<module>} {\<message>} {\<arg one>} {\<arg two>} {\<arg three>} {\<arg four>}
```

Issues *<module>* information *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. The information text will be added to the log file: the output is briefer than \msg_info:nnnnnn.

```
\msg_none:nnnnn  
\msg_none:(nnnnn|nnnn|nnn|nn|nnxxxx|nnxx|nnx|nn)
```

```
\msg_none:nnnnnn {\(module)} {\(message)} {\(arg one)}  
{\(arg two)} {\(arg three)} {\(arg four)}
```

Updated: 2012-08-11

Does nothing: used as a message class to prevent any output at all (see the discussion of message redirection).

4 Redirecting messages

Each message has a “name”, which can be used to alter the behaviour of the message when it is given. Thus we might have

```
\msg_new:nnnn { module } { my-message } { Some~text } { Some~more~text }
```

to define a message, with

```
\msg_error:nn { module } { my-message }
```

when it is used. With no filtering, this will raise an error. However, we could alter the behaviour with

```
\msg_redirect_class:nn { error } { warning }
```

to turn all errors into warnings, or with

```
\msg_redirect_module:nnn { module } { error } { warning }
```

to alter only messages from that module, or even

```
\msg_redirect_name:nnn { module } { my-message } { warning }
```

to target just one message. Redirection applies first to individual messages, then to messages from one module and finally to messages of one class. Thus it is possible to select out an individual message for special treatment even if the entire class is already redirected.

Multiple redirections are possible. Redirections can be cancelled by providing an empty argument for the target class. Redirection to a missing class will raise errors immediately. Infinite loops are prevented by eliminating the redirection starting from the target of the redirection that caused the loop to appear. Namely, if redirections are requested as $A \rightarrow B$, $B \rightarrow C$ and $C \rightarrow A$ in this order, then the $A \rightarrow B$ redirection is cancelled.

```
\msg_redirect_class:nn
```

Updated: 2012-04-27

```
\msg_redirect_class:nn {\(class one)} {\(class two)}
```

Changes the behaviour of messages of $\langle class\ one\rangle$ so that they are processed using the code for those of $\langle class\ two\rangle$.

\msg_redirect_module:nnn

Updated: 2012-04-27

```
\msg_redirect_module:nnn {\<module>} {\<class one>} {\<class two>}
```

Redirects message of *<class one>* for *<module>* to act as though they were from *<class two>*. Messages of *<class one>* from sources other than *<module>* are not affected by this redirection. This function can be used to make some messages “silent” by default. For example, all of the `warning` messages of *<module>* could be turned off with:

```
\msg_redirect_module:nnn { module } { warning } { none }
```

\msg_redirect_name:nnn

Updated: 2012-04-27

```
\msg_redirect_name:nnn {\<module>} {\<message>} {\<class>}
```

Redirects a specific *<message>* from a specific *<module>* to act as a member of *<class>* of messages. No further redirection is performed. This function can be used to make a selected message “silent” without changing global parameters:

```
\msg_redirect_name:nnn { module } { annoying-message } { none }
```

5 Low-level message functions

The lower-level message functions should usually be accessed from the higher-level system. However, there are occasions where direct access to these functions is desirable.

\msg_interrupt:nnn

New: 2012-06-28

```
\msg_interrupt:nnn {\<first line>} {\<text>} {\<extra text>}
```

Interrupts the TeX run, issuing a formatted message comprising *<first line>* and *<text>* laid out in the format

```
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!
! <first line>
!
! <text>
!
.....
```

where the *<text>* will be wrapped to fit within the current line length. The user may then request more information, at which stage the *<extra text>* will be shown in the terminal in the format

```
| , , , , , , , , , , , , , , , , ,
| <extra text>
| .....
```

where the *<extra text>* will be wrapped within the current line length. Wrapping of both *<text>* and *<more text>* takes place using `\iow_wrap:nnnN`; the documentation for the latter should be consulted for full details.

`\msg_log:n` `\msg_log:n {<text>}`

New: 2012-06-28

Writes to the log file with the `<text>` laid out in the format

```
.....  
. <text>  
.....
```

where the `<text>` will be wrapped to fit within the current line length. Wrapping takes place using `\iow_wrap:nnnN`; the documentation for the latter should be consulted for full details.

`\msg_term:n` `\msg_term:n {<text>}`

New: 2012-06-28

Writes to the terminal and log file with the `<text>` laid out in the format

```
*****  
* <text>  
*****
```

where the `<text>` will be wrapped to fit within the current line length. Wrapping takes place using `\iow_wrap:nnnN`; the documentation for the latter should be consulted for full details.

6 Kernel-specific functions

Messages from LATEX3 itself are handled by the general message system, but have their own functions. This allows some text to be pre-defined, and also ensures that serious errors can be handled properly.

`_msg_kernel_new:nnnn` `_msg_kernel_new:nnn`

Updated: 2011-08-16

`_msg_kernel_new:nnnn {<module>} {<message>} {<text>} {<more text>}`

Creates a kernel `<message>` for a given `<module>`. The message will be defined to first give `<text>` and then `<more text>` if the user requests it. If no `<more text>` is available then a standard text is given instead. Within `<text>` and `<more text>` four parameters (#1 to #4) can be used: these will be supplied and expanded at the time the message is used. An error will be raised if the `<message>` already exists.

`_msg_kernel_set:nnnn` `_msg_kernel_set:nnn`

`_msg_kernel_set:nnnn {<module>} {<message>} {<text>} {<more text>}`

Sets up the text for a kernel `<message>` for a given `<module>`. The message will be defined to first give `<text>` and then `<more text>` if the user requests it. If no `<more text>` is available then a standard text is given instead. Within `<text>` and `<more text>` four parameters (#1 to #4) can be used: these will be supplied and expanded at the time the message is used.

```
\__msg_kernel_fatal:nnnnnn
\__msg_kernel_fatal:(nnnn|nnnn|nnn|nn|nnxxxx|nnxxx|nnxx|nnx)
```

Updated: 2012-08-11

```
\__msg_kernel_fatal:nnnnnn {\<module>}
{\<message>} {\<arg one>} {\<arg two>} {\<arg
three>} {\<arg four>}
```

Issues kernel *<module>* error *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. After issuing a fatal error the TeX run will halt. Cannot be redirected.

```
\__msg_kernel_error:nnnnnn
\__msg_kernel_error:(nnnn|nnnn|nnn|nn|nnxxxx|nnxxx|nnxx|nnx)
```

Updated: 2012-08-11

```
\__msg_kernel_error:nnnnnn {\<module>}
{\<message>} {\<arg one>} {\<arg two>} {\<arg
three>} {\<arg four>}
```

Issues kernel *<module>* error *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. The error will stop processing and issue the text at the terminal. After user input, the run will continue. Cannot be redirected.

```
\__msg_kernel_warning:nnnnnn
\__msg_kernel_warning:(nnnn|nnnn|nnn|nn|nnxxxx|nnxxx|nnxx|nnx)
```

Updated: 2012-08-11

```
\__msg_kernel_warning:nnnnnn {\<module>}
{\<message>} {\<arg one>} {\<arg two>} {\<arg
three>} {\<arg four>}
```

Issues kernel *<module>* warning *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. The warning text will be added to the log file, but the TeX run will not be interrupted.

```
\__msg_kernel_info:nnnnnn
\__msg_kernel_info:(nnnn|nnnn|nnn|nn|nnxxxx|nnxxx|nnxx|nnx)
```

Updated: 2012-08-11

```
\__msg_kernel_info:nnnnnn {\<module>}
{\<message>} {\<arg one>} {\<arg two>} {\<arg
three>} {\<arg four>}
```

Issues kernel *<module>* information *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. The information text will be added to the log file.

7 Expandable errors

In a few places, the LATEX3 kernel needs to produce errors in an expansion only context. This must be handled internally very differently from normal error messages, as none of the tools to print to the terminal or the log file are expandable. However, the interface is similar, with the important caveat that the message text and arguments are not expanded, and messages should be very short.

```
\__msg_kernel_expandable_error:nnnnnn      *
\__msg_kernel_expandable_error:(nnnn|nnnn|nnn|nn) *
```

New: 2011-11-23

```
\__msg_kernel_expandable_error:nnnnnn {\<module>}
{\<message>} {\<arg one>} {\<arg two>} {\<arg three>}
{\<arg four>}
```

Issues an error, passing *<arg one>* to *<arg four>* to the text-creating functions. The resulting string must be shorter than a line, otherwise it will be cropped.

`__msg_expandable_error:n *` `__msg_expandable_error:n {<error message>}`

New: 2011-08-11

Updated: 2011-08-13

Issues an “Undefined error” message from TeX itself, and prints the *<error message>*. The *<error message>* must be short: it is cropped at the end of one line.

TeXhackers note: This function expands to an empty token list after two steps. Tokens inserted in response to TeX’s prompt are read with the current category code setting, and inserted just after the place where the error message was issued.

8 Internal l3msg functions

The following functions are used in several kernel modules.

`__msg_term:nnnnnn` `__msg_term:nnnnnn {<module>} {<message>}` {<arg one>} {<arg two>} {<arg three>} {<arg four>}

Prints the *<message>* from *<module>* in the terminal without formatting. Used in messages which print complex variable contents completely.

`__msg_show_variable:Nnn` `__msg_show_variable:Nnn {<variable>} {<type>}` {<formatted content>}

Updated: 2012-09-09

Displays the *<formatted content>* of the *<variable>* of *<type>* in the terminal. The *<formatted content>* will be processed as the first argument in a call to `\iow_wrap:nnN`, hence `\\\`, `_` and other formatting sequences can be used. Once expanded and processed, the *<formatted content>* must either be empty or contain `>`; everything until the first `>` will be removed.

`__msg_show_variable:n` `__msg_show_variable:n {<formatted text>}`

Updated: 2012-09-09

Shows the *<formatted text>* on the terminal. After expansion, unless it is empty, the *<formatted text>* must contain `>`, and the part of *<formatted text>* before the first `>` is removed. Failure to do so causes low-level TeX errors.

`__msg_show_item:n` `__msg_show_item:n {<item>}`

`__msg_show_item:nn` `__msg_show_item:nn {<item-key>} {<item-value>}`

`__msg_show_item_unbraced:nn`

Updated: 2012-09-09

Auxiliary functions used within the argument of `__msg_show_variable:Nnn` to format variable items correctly for display. The `__msg_show_item:n` version is used for simple lists, the `__msg_show_item:nn` and `__msg_show_item_unbraced:nn` versions for key-value like data structures.

Part XIX

The **l3keys** package

Key–value interfaces

The key–value method is a popular system for creating large numbers of settings for controlling function or package behaviour. For the user, the system normally results in input of the form

```
\PackageControlMacro{  
    key-one = value one,  
    key-two = value two  
}
```

or

```
\PackageMacro[  
    key-one = value one,  
    key-two = value two  
]{argument}.
```

The high level functions here are intended as a method to create key–value controls. Keys are themselves created using a key–value interface, minimising the number of functions and arguments required. Each key is created by setting one or more *properties* of the key:

```
\keys_define:nn { module }  
{  
    key-one .code:n = code including parameter #1,  
    key-two .tl_set:N = \l_module_store_tl  
}
```

These values can then be set as with other key–value approaches:

```
\keys_set:nn { module }  
{  
    key-one = value one,  
    key-two = value two  
}
```

At a document level, `\keys_set:nn` will be used within a document function, for example

```
\DeclareDocumentCommand \SomePackageSetup { m }  
  { \keys_set:nn { module } { #1 } }  
\DeclareDocumentCommand \SomePackageMacro { o m }  
{  
    \group_begin:
```

```

\keys_set:nn { module } { #1 }
% Main code for \SomePackageMacro
\group_end:
}

```

Key names may contain any tokens, as they are handled internally using `\tl_to_str:n`. As will be discussed in section 2, it is suggested that the character / is reserved for sub-division of keys into logical groups. Functions and variables are *not* expanded when creating key names, and so

```

\tl_set:Nn \l_module_tmp_tl { key }
\keys_define:nn { module }
{
    \l_module_tmp_tl .code:n = code
}

```

will create a key called `\l_module_tmp_tl`, and not one called `key`.

1 Creating keys

`\keys_define:nn`

Parses the `\keys_define:nn` and defines the keys listed there for `\keys_define:nn`. The `\keys_define:nn` name should be a text value, but there are no restrictions on the nature of the text. In practice the `\keys_define:nn` should be chosen to be unique to the module in question (unless deliberately adding keys to an existing module).

The `\keys_define:nn` should consist of one or more key names along with an associated key *property*. The properties of a key determine how it acts. The individual properties are described in the following text; a typical use of `\keys_define:nn` might read

```

\keys_define:nn { mymodule }
{
    keyname .code:n = Some~code~using~#1,
    keyname .value_required:
}

```

where the properties of the key begin from the `.` after the key name.

The various properties available take either no arguments at all, or require exactly one argument. This is indicated in the name of the property using an argument specification. In the following discussion, each property is illustrated attached to an arbitrary `\key`, which when used may be supplied with a `\value`. All key *definitions* are local.

`.bool_set:N` `\key .bool_set:N = \boolean`

`.bool_gset:N` Defines `\key` to set `\boolean` to `\value` (which must be either `true` or `false`). If the variable does not exist, it will be created at the point that the key is set up.

.bool_set_inverse:N
.bool_gset_inverse:N

New: 2011-08-28

`<key> .bool_set_inverse:N = <boolean>`

Defines `<key>` to set `<boolean>` to the logical inverse of `<value>` (which must be either `true` or `false`). If the `<boolean>` does not exist, it will be created at the point that the key is set up.

.choice:

`<key> .choice:`

Sets `<key>` to act as a choice key. Each valid choice for `<key>` must then be created, as discussed in section 3.

.choices:nn

New: 2011-08-21

`<key> .choices:nn <choices> <code>`

Sets `<key>` to act as a choice key, and defines a series `<choices>` which are implemented using the `<code>`. Inside `<code>`, `\l_keys_choice_t1` will be the name of the choice made, and `\l_keys_choice_int` will be the position of the choice in the list of `<choices>` (indexed from 1). Choices are discussed in detail in section 3.

.choice_code:n

.choice_code:x

`<key> .choice_code:n = <code>`

Stores `<code>` for use when `.generate_choices:n` creates one or more choice sub-keys of the current key. Inside `<code>`, `\l_keys_choice_t1` will expand to the name of the choice made, and `\l_keys_choice_int` will be the position of the choice in the list given to `.generate_choices:n`. Choices are discussed in detail in section 3.

.clist_set:N

.clist_set:c

.clist_gset:N

.clist_gset:c

New: 2011/09/11

`<key> .clist_set:N = <comma list variable>`

Defines `<key>` to set `<comma list variable>` to `<value>`. Spaces around commas and empty items will be stripped. If the variable does not exist, it will be created at the point that the key is set up.

.code:n

.code:x

`<key> .code:n = <code>`

Stores the `<code>` for execution when `<key>` is used. The `<code>` can include one parameter (#1), which will be the `<value>` given for the `<key>`. The x-type variant will expand `<code>` at the point where the `<key>` is created.

.default:n $\langle key \rangle .\text{default:n} = \langle default \rangle$

Creates a $\langle default \rangle$ value for $\langle key \rangle$, which is used if no value is given. This will be used if only the key name is given, but not if a blank $\langle value \rangle$ is given:

```
\keys_define:nn { module }
{
    key .code:n      = Hello~#1,
    key .default:n = World
}
\keys_set:nn { module }
{
    key = Fred, % Prints 'Hello Fred'
    key,          % Prints 'Hello World'
    key = ,       % Prints 'Hello '
}
```

.dim_set:N $\langle key \rangle .\text{dim_set:N} = \langle dimension \rangle$

Defines $\langle key \rangle$ to set $\langle dimension \rangle$ to $\langle value \rangle$ (which must a dimension expression). If the variable does not exist, it will be created at the point that the key is set up.

.fp_set:N $\langle key \rangle .\text{fp_set:N} = \langle floating\ point \rangle$

Defines $\langle key \rangle$ to set $\langle floating\ point \rangle$ to $\langle value \rangle$ (which must a floating point number). If the variable does not exist, it will be created at the point that the key is set up.

.generate_choices:n $\langle key \rangle .\text{generate_choices:n} = \{\langle list \rangle\}$

This property will mark $\langle key \rangle$ as a multiple choice key, and will use the $\langle list \rangle$ to define the choices. The $\langle list \rangle$ should consist of a comma-separated list of choice names. Each choice will be set up to execute $\langle code \rangle$ as set using .choice_code:n (or .choice_code:x). Choices are discussed in detail in section 3.

.initial:n $\langle key \rangle .\text{initial:n} = \langle value \rangle$

Initialises the $\langle key \rangle$ with the $\langle value \rangle$, equivalent to

```
\keys_set:nn {<module>} { <key> = <value> }
```

.int_set:N $\langle key \rangle .\text{int_set:N} = \langle integer \rangle$

Defines $\langle key \rangle$ to set $\langle integer \rangle$ to $\langle value \rangle$ (which must be an integer expression). If the variable does not exist, it will be created at the point that the key is set up.

.meta:n `<key> .meta:n = {<keyval list>}`

.meta:x

Makes `<key>` a meta-key, which will set `<keyval list>` in one go. If `<key>` is given with a value at the time the key is used, then the value will be passed through to the subsidiary `<keys>` for processing (as #1).

.multichoice: `<key> .multichoice:`

New: 2011-08-21

Sets `<key>` to act as a multiple choice key. Each valid choice for `<key>` must then be created, as discussed in section 3.

This property is experimental.

.multichoices:nn `<key> .multichoices:nn <choices> <code>`

New: 2011-08-21

Sets `<key>` to act as a multiple choice key, and defines a series `<choices>` which are implemented using the `<code>`. Inside `<code>`, `\l_keys_choice_t1` will be the name of the choice made, and `\l_keys_choice_int` will be the position of the choice in the list of `<choices>` (indexed from 1). Choices are discussed in detail in section 3.

This property is experimental.

.skip_set:N `<key> .skip_set:N = <skip>`

.skip_set:c

.skip_gset:N

.skip_gset:c

Defines `<key>` to set `<skip>` to `<value>` (which must be a skip expression). If the variable does not exist, it will be created at the point that the key is set up.

.tl_set:N `<key> .tl_set:N = <token list variable>`

.tl_set:c

.tl_gset:N

.tl_gset:c

Defines `<key>` to set `<token list variable>` to `<value>`. If the variable does not exist, it will be created at the point that the key is set up.

.tl_set_x:N `<key> .tl_set_x:N = <token list variable>`

.tl_set_x:c

.tl_gset_x:N

.tl_gset_x:c

Defines `<key>` to set `<token list variable>` to `<value>`, which will be subjected to an x-type expansion (*i.e.* using `\tl_set:Nx`). If the variable does not exist, it will be created at the point that the key is set up.

.value_forbidden: `<key> .value_forbidden:`

Specifies that `<key>` cannot receive a `<value>` when used. If a `<value>` is given then an error will be issued.

.value_required: `<key> .value_required:`

Specifies that `<key>` must receive a `<value>` when used. If a `<value>` is not given then an error will be issued.

2 Sub-dividing keys

When creating large numbers of keys, it may be desirable to divide them into several sub-groups for a given module. This can be achieved either by adding a sub-division to the module name:

```
\keys_define:nn { module / subgroup }
  { key .code:n = code }
```

or to the key name:

```
\keys_define:nn { module }
  { subgroup / key .code:n = code }
```

As illustrated, the best choice of token for sub-dividing keys in this way is `/`. This is because of the method that is used to represent keys internally. Both of the above code fragments set the same key, which has full name `module/subgroup/key`.

As will be illustrated in the next section, this subdivision is particularly relevant to making multiple choices.

3 Choice and multiple choice keys

The `l3keys` system supports two types of choice key, in which a series of pre-defined input values are linked to varying implementations. Choice keys are usually created so that the various values are mutually-exclusive: only one can apply at any one time. “Multiple” choice keys are also supported: these allow a selection of values to be chosen at the same time.

Mutually-exclusive choices are created by setting the `.choice:` property:

```
\keys_define:nn { module }
  { key .choice: }
```

For keys which are set up as choices, the valid choices are generated by creating sub-keys of the choice key. This can be carried out in two ways.

In many cases, choices execute similar code which is dependant only on the name of the choice or the position of the choice in the list of choices. Here, the keys can share the same code, and can be rapidly created using the `.choice_code:n` and `.generate_choices:n` properties:

```
\keys_define:nn { module }
  {
    key .choice_code:n =
    {
      You~gave~choice~'\int_use:N \l_keys_choice_tl',~
      which~is~in~position~\int_use:N \l_keys_choice_int \c_space_tl
      in~the~list.
    },
  }
```

```

key .generate_choices:n =
{ choice-a, choice-b, choice-c }
}

```

Following common computing practice, `\l_keys_choice_int` is indexed from 1.

The same approach is also implemented by the *experimental* property `.choices:nn`. This combines the functionality of `.choice_code:n` and `.generate_choices:n` into one property:

```

\keys_define:nn { module }
{
  key .choices:nn =
  { choice-a, choice-b, choice-c }
  {
    You~gave~choice~'\int_use:N \l_keys_choice_tl',~
    which~is~in~position~
    \int_use:N \l_keys_choice_int \c_space_tl
    in~the~list.
  }
}

```

Note that the `.choices:nn` property should *not* be mixed with use of `.generate_choices:n`.

\l_keys_choice_int \l_keys_choice_tl

Inside the code block for a choice generated using `.generate_choice:` or `.choices:nn`, the variables `\l_keys_choice_tl` and `\l_keys_choice_int` are available to indicate the name of the current choice, and its position in the comma list. The position is indexed from 0.

On the other hand, it is sometimes useful to create choices which use entirely different code from one another. This can be achieved by setting the `.choice:` property of a key, then manually defining sub-keys.

```

\keys_define:nn { module }
{
  key .choice:,,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
}

```

It is possible to mix the two methods, but manually-created choices should *not* use `\l_keys_choice_tl` or `\l_keys_choice_int`. These variables do not have defined behaviour when used outside of code created using `.generate_choices:n` (*i.e.* anything might happen).

Multiple choices are created in a very similar manner to mutually-exclusive choices, using the properties `.multichoice:` and `.multichoices:nn`. As with mutually exclusive choices, multiple choices are define as sub-keys. Thus both

```
\keys_define:nn { module }
{
  key .multichoices:nn =
    { choice-a, choice-b, choice-c }
  {
    You~gave~choice~'\int_use:N \l_keys_choice_tl',~
    which~is~in~position~
    \int_use:N \l_keys_choice_int \c_space_tl
    in~the~list.
  }
}
```

and

```
\keys_define:nn { module }
{
  key .multichoice:,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
}
```

are valid. The `.multichoices:nn` property causes `\l_keys_choice_tl` and `\l_keys_choice_int` to be set in exactly the same way as described for `.choices:nn`.

When multiple choice keys are set, the value is treated as a comma-separated list:

```
\keys_set:nn { module }
{
  key = { a , b , c } % 'key' defined as a multiple choice
}
```

Each choice will be applied in turn, with the usual handling of unknown values.

4 Setting keys

`\keys_set:nn`
`\keys_set:(nV|nv|no)`

`\keys_set:nn {<module>} {<keyval list>}`

Parses the `<keyval list>`, and sets those keys which are defined for `<module>`. The behaviour on finding an unknown key can be set by defining a special `unknown` key: this will be illustrated later.

If a key is not known, `\keys_set:nn` will look for a special `unknown` key for the same module. This mechanism can be used to create new keys from user input.

```
\keys_define:nn { module }
{
  unknown .code:n =
    You~tried~to~set~key~'\l_keys_key_tl'~to~'#1'.
}
```

\l_keys_key_tl

When processing an unknown key, the name of the key is available as `\l_keys_key_tl`. Note that this will have been processed using `\tl_to_str:n`.

\l_keys_path_tl

When processing an unknown key, the path of the key used is available as `\l_keys_path_tl`. Note that this will have been processed using `\tl_to_str:n`.

\l_keys_value_tl

When processing an unknown key, the value of the key is available as `\l_keys_value_tl`. Note that this will be empty if no value was given for the key.

5 Setting known keys only

```
\keys_set_known:nnN
\keys_set_known:(nVN|nvN|noN)

```

New: 2011-08-23

```
\keys_set_known:nn {<module>} {<keyval list>} <clist>
```

Parses the `<keyval list>`, and sets those keys which are defined for `<module>`. Any keys which are unknown are not processed further by the parser. The key–value pairs for each *unknown* key name will be stored in the `<clist>`.

6 Utility functions for keys

```
\keys_if_exist_p:nn *
\keys_if_exist:nnTF *
```

```
\keys_if_exist_p:nn <module> <key>
\keys_if_exist:nnTF <module> <key> {<true code>} {<false code>}
```

Tests if the `<key>` exists for `<module>`, *i.e.* if any code has been defined for `<key>`.

```
\keys_if_choice_exist_p:nnn *
\keys_if_choice_exist:nnnTF *
```

New: 2011-08-21

```
\keys_if_choice_exist_p:nnn <module> <key> <choice>
\keys_if_choice_exist:nnnTF <module> <key> <choice> {<true code>} {<false code>}
```

Tests if the `<choice>` is defined for the `<key>` within the `<module>`, *i.e.* if any code has been defined for `<key>/<choice>`. The test is **false** if the `<key>` itself is not defined.

\keys_show:nn

```
\keys_show:nn {<module>} {<key>}
```

Shows the function which is used to actually implement a `<key>` for a `<module>`.

7 Low-level interface for parsing key–val lists

To re-cap from earlier, a key–value list is input of the form

```
KeyOne = ValueOne ,  
KeyTwo = ValueTwo ,  
KeyThree
```

where each key–value pair is separated by a comma from the rest of the list, and each key–value pair does not necessarily contain an equals sign or a value! Processing this type of input correctly requires a number of careful steps, to correctly account for braces, spaces and the category codes of separators.

While the functions described earlier are used as a high-level interface for processing such input, in especial circumstances you may wish to use a lower-level approach. The low-level parsing system converts a $\langle key-value\ list \rangle$ into $\langle keys \rangle$ and associated $\langle values \rangle$. After the parsing phase is completed, the resulting keys and values (or keys alone) are available for further processing. This processing is not carried out by the low-level parser itself, and so the parser requires the names of two functions along with the key–value list. One function is needed to process key–value pairs (*i.e.* two arguments), and a second function if required for keys given without arguments (*i.e.* a single argument).

The parser does not double # tokens or expand any input. The tokens = and , are corrected so that the parser does not “miss” any due to category code changes. Spaces are removed from the ends of the keys and values. Values which are given in braces will have exactly one set removed, thus

```
key = {value here},
```

and

```
key = value here,
```

are treated identically.

\keyval_parse:NNn

Updated: 2011-09-08

```
\keyval_parse:NNn <function1> <function2> {<key-value list>}
```

Parses the *<key-value list>* into a series of *<keys>* and associated *<values>*, or keys alone (if no *<value>* was given). *<function₁>* should take one argument, while *<function₂>* should absorb two arguments. After \keyval_parse:NNn has parsed the *<key-value list>*, *<function₁>* will be used to process keys given with no value and *<function₂>* will be used to process keys given with a value. The order of the *<keys>* in the *<key-value list>* will be preserved. Thus

```
\keyval_parse:NNn \function:n \function:nn
  { key1 = value1 , key2 = value2, key3 = , key4 }
```

will be converted into an input stream

```
\function:nn { key1 } { value1 }
\function:nn { key2 } { value2 }
\function:nn { key3 } { }
\function:n { key4 }
```

Note that there is a difference between an empty value (an equals sign followed by nothing) and a missing value (no equals sign at all). Spaces are trimmed from the ends of the *<key>* and *<value>*, and any *outer* set of braces are removed from the *<value>* as part of the processing.

Part XX

The `I3file` package

File and I/O operations

This module provides functions for working with external files. Some of these functions apply to an entire file, and have prefix `\file_...`, while others are used to work with files on a line by line basis and have prefix `\ior_...` (reading) or `\iow_...` (writing).

It is important to remember that when reading external files `TeX` will attempt to locate them both the operating system path and entries in the `TeX` file database (most `TeX` systems use such a database). Thus the “current path” for `TeX` is somewhat broader than that for other programs.

For functions which expect a `\langle file name \rangle` argument, this argument may contain both literal items and expandable content, which should on full expansion be the desired file name. Any active characters (as declared in `\l_char_active_seq`) will *not* be expanded, allowing the direct use of these in file names. Spaces are not allowed in file names.

1 File operation functions

`\g_file_current_name_tl`

Contains the name of the current `LATEX` file. This variable should not be modified: it is intended for information only. It will be equal to `\c_job_name_tl` at the start of a `LATEX` run and will be modified each time a file is read using `\file_input:n`.

`\file_if_exist:nTF`

Updated: 2012-02-10

```
\file_if_exist:nTF {\langle file name \rangle} {\langle true code \rangle} {\langle false code \rangle}
```

Searches for `\langle file name \rangle` using the current `TeX` search path and the additional paths controlled by `\file_path_include:n`.

`\file_add_path:nN`

Updated: 2012-02-10

```
\file_add_path:nN {\langle file name \rangle} {tl var}
```

Searches for `\langle file name \rangle` in the path as detailed for `\file_if_exist:nTF`, and if found sets the `\langle tl var \rangle` the fully-qualified name of the file, *i.e.* the path and file name. If the file is not found then the `\langle tl var \rangle` will contain the marker `\q_no_value`.

`\file_input:n`

Updated: 2012-02-17

```
\file_input:n {\langle file name \rangle}
```

Searches for `\langle file name \rangle` in the path as detailed for `\file_if_exist:nTF`, and if found reads in the file as additional `LATEX` source. All files read are recorded for information and the file name stack is updated by this function. An error will be raised if the file is not found.

`\file_path_include:n`

Updated: 2012-07-04

`\file_path_include:n {\path}`

Adds $\langle path \rangle$ to the list of those used to search when reading files. The assignment is local. The $\langle path \rangle$ is processed in the same way as a $\langle file\ name \rangle$, i.e., with x-type expansion except active characters. Spaces are not allowed in the $\langle path \rangle$.

`\file_path_remove:n`

Updated: 2012-07-04

`\file_path_remove:n {\path}`

Removes $\langle path \rangle$ from the list of those used to search when reading files. The assignment is local. The $\langle path \rangle$ is processed in the same way as a $\langle file\ name \rangle$, i.e., with x-type expansion except active characters. Spaces are not allowed in the $\langle path \rangle$.

`\file_list:`

This function will list all files loaded using `\file_input:n` in the log file.

1.1 Input–output stream management

As TeX is limited to 16 input streams and 16 output streams, direct use of the streams by the programmer is not supported in L^AT_EX3. Instead, an internal pool of streams is maintained, and these are allocated and deallocated as needed by other modules. As a result, the programmer should close streams when they are no longer needed, to release them for other processes.

Note that I/O operations are global: streams should all be declared with global names and treated accordingly.

`\ior_new:N`

`\ior_new:c`

`\iow_new:N`

`\iow_new:c`

New: 2011-09-26

Updated: 2011-12-27

`\ior_new:N \stream`

`\iow_new:N \stream`

Globally reserves the name of the $\langle stream \rangle$, either for reading or for writing as appropriate. The $\langle stream \rangle$ is not opened until the appropriate `\..._open:Nn` function is used. Attempting to use a $\langle stream \rangle$ which has not been opened is an error, and the $\langle stream \rangle$ will behave as the corresponding `\c_term_...`

`\ior_open:Nn`

`\ior_open:cn`

Updated: 2012-02-10

`\ior_open:Nn \stream {\file\ name}`

Opens $\langle file\ name \rangle$ for reading using $\langle stream \rangle$ as the control sequence for file access. If the $\langle stream \rangle$ was already open it is closed before the new operation begins. The $\langle stream \rangle$ is available for access immediately and will remain allocated to $\langle file\ name \rangle$ until a `\ior_close:N` instruction is given or the TeX run ends.

`\iow_open:Nn`

`\iow_open:cn`

Updated: 2012-02-09

`\iow_open:Nn \stream {\file\ name}`

Opens $\langle file\ name \rangle$ for writing using $\langle stream \rangle$ as the control sequence for file access. If the $\langle stream \rangle$ was already open it is closed before the new operation begins. The $\langle stream \rangle$ is available for access immediately and will remain allocated to $\langle file\ name \rangle$ until a `\iow_close:N` instruction is given or the TeX run ends. Opening a file for writing will clear any existing content in the file (i.e. writing is *not* additive).

```
\ior_close:N <stream>
\ior_close:c
```

Closes the *<stream>*. Streams should always be closed when they are finished with as this ensures that they remain available to other programmers.

Updated: 2012-07-31

```
\ior_list_streams:
\iow_list_streams:
```

Displays a list of the file names associated with each open stream: intended for tracking down problems.

Updated: 2012-09-09

1.2 Reading from files

```
\ior_get:NN <stream> <token list variable>
```

New: 2012-06-24

Function that reads one or more lines (until an equal number of left and right braces are found) from the input *<stream>* and stores the result locally in the *<token list>* variable. If the *<stream>* is not open, input is requested from the terminal. The material read from the *<stream>* will be tokenized by \TeX according to the category codes in force when the function is used.

\TeX hackers note: This protected macro expands to the \TeX primitive `\read` along with the `to` keyword.

```
\ior_get_str:NN <stream> <token list variable>
```

New: 2012-06-24

Updated: 2012-07-31

Function that reads one line from the input *<stream>* and stores the result locally in the *<token list>* variable. If the *<stream>* is not open, input is requested from the terminal. The material is read from the *<stream>* as a series of tokens with category code 12 (other), with the exception of space characters which are given category code 10 (space).

\TeX hackers note: This protected macro is a wrapper around the ε - \TeX primitive `\readline`. However, the end-line character normally added by this primitive is not included in the result of `\ior_get_str:NN`.

```
\ior_if_eof_p:N *
\ior_if_eof:NTF *
```

Updated: 2012-02-10

Tests if the end of a *<stream>* has been reached during a reading operation. The test will also return a `true` value if the *<stream>* is not open.

2 Writing to files

\iow_now:Nn

\iow_now:Nx

Updated: 2012-06-05

\iow_now:Nn *stream* {\iokens}

This functions writes *tokens* to the specified *stream* immediately (*i.e.* the write operation is called on expansion of \iow_now:Nn).

\iow_log:n

\iow_log:x

\iow_log:n {\iokens}

This function writes the given *tokens* to the log (transcript) file immediately: it is a dedicated version of \iow_now:Nn.

\iow_term:n

\iow_term:x

\iow_term:n {\iokens}

This function writes the given *tokens* to the terminal file immediately: it is a dedicated version of \iow_now:Nn.

\iow_shipout:Nn

\iow_shipout:Nx

\iow_shipout:Nn *stream* {\iokens}

This functions writes *tokens* to the specified *stream* when the current page is finalised (*i.e.* at shipout). The x-type variants expand the *tokens* at the point where the function is used but *not* when the resulting tokens are written to the *stream* (*cf.* \iow_shipout_x:Nn).

\iow_shipout_x:Nn

\iow_shipout_x:Nx

Updated: 2012-09-08

\iow_shipout_x:Nn *stream* {\iokens}

This functions writes *tokens* to the specified *stream* when the current page is finalised (*i.e.* at shipout). The *tokens* are expanded at the time of writing in addition to any expansion when the function is used. This makes these functions suitable for including material finalised during the page building process (such as the page number integer).

TeXhackers note: This is a wrapper around the TeX primitive \write.

\iow_char:N *

\iow_char:N \char

Inserts *char* into the output stream. Useful when trying to write difficult characters such as %, {, }, etc. in messages, for example:

```
\iow_now:Nx \g_my_iow { \iow_char:N \{ text \iow_char:N \} }
```

The function has no effect if writing is taking place without expansion (*e.g.* in the second argument of \iow_now:Nn).

\iow_newline: *

\iow_newline:

Function to add a new line within the *tokens* written to a file. The function has no effect if writing is taking place without expansion (*e.g.* in the second argument of \iow_now:Nn).

2.1 Wrapping lines in output

\iow_wrap:nnnN

New: 2012-06-28

\iow_wrap:nnnN {<text>} {<run-on text>} {<set up>} <function>

This function will wrap the *<text>* to a fixed number of characters per line. At the start of each line which is wrapped, the *<run-on text>* will be inserted. The line character count targeted will be the value of `\l_iow_line_count_int` minus the number of characters in the *<run-on text>*. The *<text>* and *<run-on text>* are exhaustively expanded by the function, with the following substitutions:

- `\\\` may be used to force a new line,
- `_` may be used to represent a forced space (for example after a control sequence),
- `\#, \%, \{, \}`, `\~` may be used to represent the corresponding character,
- `\iow_indent:n` may be used to indent a part of the message.

Additional functions may be added to the wrapping by using the *<set up>*, which is executed before the wrapping takes place: this may include overriding the substitutions listed.

Any expandable material in the *<text>* which is not to be expanded on wrapping should be converted to a string using `\token_to_str:N`, `\tl_to_str:n`, `\tl_to_str:N`, etc.

The result of the wrapping operation is passed as a braced argument to the *<function>*, which will typically be a wrapper around a write operation. The output of `\iow_wrap:nnnN` (*i.e.* the argument passed to the *<function>*) will consist of characters of category “other” (category code 12), with the exception of spaces which will have category “space” (category code 10). This means that the output will *not* expand further when written to a file.

TeXhackers note: Internally, `\iow_wrap:nnnN` carries out an `x`-type expansion on the *<text>* to expand it. This is done in such a way that `\exp_not:N` or `\exp_not:n` could be used to prevent expansion of material. However, this is less conceptually clear than conversion to a string, which is therefore the supported method for handling expandable material in the *<text>*.

\iow_indent:n

New: 2011-09-21

\iow_indent:n {<text>}

In the context of `\iow_wrap:nnnN` (for instance in messages), indents *<text>* by four spaces. This function will not cause a line break, and only affects lines which start within the scope of the *<text>*. In case the indented *<text>* should appear on separate lines from the surrounding text, use `\\\` to force line breaks.

\l_iow_line_count_int

New: 2012-06-24

The maximum number of characters in a line to be written by the `\iow_wrap:nnnN` function. This value depends on the TeX system in use: the standard value is 78, which is typically correct for unmodified TeXlive and MiKTeX systems.

`\c_catcode_other_space_tl`

New: 2011-09-05

Token list containing one character with category code 12, (“other”), and character code 32 (space).

2.2 Constant input–output streams

`\c_term_iор`

Constant input stream for reading from the terminal. Reading from this stream using `\ior_get:NN` or similar will result in a prompt from TeX of the form

`<tl>=`

`\c_log_iow`
`\c_term_iow`

Constant output streams for writing to the log and to the terminal (plus the log), respectively.

2.3 Primitive conditionals

`\if_eof:w *`

```
\if_eof:w <stream>
  <true code>
\else:
  <false code>
\fi:
```

Tests if the `<stream>` returns “end of file”, which is true for non-existent files. The `\else:` branch is optional.

TeXhackers note: This is the TeX primitive `\ifeof`.

2.4 Internal file functions and variables

`\l_file_internal_name_iор`

Used to test for the existence of files when opening.

`\l_file_internal_name_tl`

Used to return the full name of a file for internal use.

`_file_name_sanitize:nn`

New: 2012-02-09

```
\_file_name_sanitize:nn {\name} {\tokens}
```

Exhaustively-expands the `\name` with the exception of any category `\active` (catcode 13) tokens, which are not expanded. The list of `\active` tokens is taken from `\l_char_active_seq`. The `\sanitized name` is then inserted (in braces) after the `\tokens`, which should further process the file name. If any spaces are found in the name after expansion, an error is raised.

2.5 Internal input–output functions

__ior_open:Nn

__ior_open:No

New: 2012-01-23

__ior_open:Nn *stream* {⟨file name⟩}

This function has identical syntax to the public version. However, it does not take precautions against active characters in the ⟨file name⟩, and it does not attempt to add a ⟨path⟩ to the ⟨file name⟩: it is therefore intended to be used by higher-level functions which have already fully expanded the ⟨file name⟩ and which need to perform multiple open or close operations. See for example the implementation of \file_add_path:nN,

Part XXI

The **l3fp** package: floating points

A decimal floating point number is one which is stored as a significand and a separate exponent. The module implements expandably a wide set of arithmetic, trigonometric, and other operations on decimal floating point numbers, to be used within floating point expressions. Floating point expressions support the following operations with their usual precedence.

- Basic arithmetic: addition $x + y$, subtraction $x - y$, multiplication $x * y$, division x/y , and parentheses.
- Comparison operators: $x < y$, $x \leq y$, $x >? y$, $x != y$ etc.
- Boolean logic: negation $!x$, conjunction $x \&& y$, disjunction $x || y$, ternary operator $x ? y : z$.
- Exponentials: $\exp x$, $\ln x$, x^y .
- Trigonometry: $\sin x$, $\cos x$, $\tan x$, $\cot x$, $\sec x$, $\csc x$.

(*not yet*) Inverse trigonometric functions: $\arcsin x$, $\arccos x$, $\arctan x$, $\text{acot } x$, $\text{asec } x$, $\text{acsc } x$.

(*not yet*) Hyperbolic functions and their inverse functions: $\sinh x$, $\cosh x$, $\tanh x$, $\coth x$, $\sech x$, $\csch x$, and $\text{asinh } x$, $\text{acosh } x$, $\text{atanh } x$, $\text{acoth } x$, $\text{asech } x$, $\text{acsch } x$.

- Extrema: $\max(x, y, \dots)$, $\min(x, y, \dots)$, $\abs(x)$.
- Rounding functions: $\text{round}(x, n)$ round to closest, $\text{round0}(x, n)$ round towards zero, $\text{round}\pm(x, n)$ round towards $\pm\infty$. And (*not yet*) modulo, and “quantize”.
- Constants: `pi`, `deg` (one degree in radians).
- Dimensions, automatically expressed in points, e.g., `pc` is 12.
- Automatic conversion (no need for `\(type)_use:N`) of integer, dimension, and skip variables to floating points, expressing dimensions in points and ignoring the stretch and shrink components of skips.

Floating point numbers can be given either explicitly (in a form such as `1.234e-34`, or `-.0001`), or as a stored floating point variable, which is automatically replaced by its current value. See section 9.1 for a description of what a floating point is, section 9.2 for details about how an expression is parsed, and section 9.3 to know what the various operations do. Some operations may raise exceptions (error messages), described in section 7.

An example of use could be the following.

```
\LaTeX{} can now compute: $ \frac{\sin (3.5)}{2} + 2\cdot 10^{-3}
= \ExplSyntaxOn \fp_to_decimal:n {sin 3.5 /2 + 2e-3} $.
```

But in all fairness, this module is mostly meant as an underlying tool for higher-level commands. For example, one could provide a function to typeset nicely the result of floating point computations.

```
\usepackage{xparse, siunitx}
\ExplSyntaxOn
\NewDocumentCommand { \calcnum } { m }
  { \num { \fp_to_scientific:n {#1} } }
\ExplSyntaxOff
\calcnum { 2 pi * sin ( 2.3 ^ 5 ) }
```

1 Creating and initialising floating point variables

`\fp_new:N`

`\fp_new:c`

Updated: 2012-05-08

`\fp_new:N <fp var>`

Creates a new `<fp var>` or raises an error if the name is already taken. The declaration is global. The `<fp var>` will initially be +0.

`\fp_const:Nn`

`\fp_const:cn`

Updated: 2012-05-08

`\fp_const:Nn <fp var> {<floating point expression>}`

Creates a new constant `<fp var>` or raises an error if the name is already taken. The `<fp var>` will be set globally equal to the result of evaluating the `<floating point expression>`.

`\fp_zero:N`

`\fp_zero:c`

`\fp_gzero:N`

`\fp_gzero:c`

Updated: 2012-05-08

`\fp_zero:N <fp var>`

Sets the `<fp var>` to +0.

`\fp_zero_new:N`

`\fp_zero_new:c`

`\fp_gzero_new:N`

`\fp_gzero_new:c`

Updated: 2012-05-08

`\fp_zero_new:N <fp var>`

Ensures that the `<fp var>` exists globally by applying `\fp_new:N` if necessary, then applies `\fp_(g)zero:N` to leave the `<fp var>` set to zero.

2 Setting floating point variables

`\fp_set:Nn`

`\fp_set:cn`

`\fp_gset:Nn`

`\fp_gset:cn`

Updated: 2012-05-08

`\fp_set:Nn <fp var> {<floating point expression>}`

Sets `<fp var>` equal to the result of computing the `<floating point expression>`.

```
\fp_set_eq:NN
\fp_set_eq:(cN|Nc|cc)
\fp_gset_eq:NN
\fp_gset_eq:(cN|Nc|cc)
```

Updated: 2012-05-08

```
\fp_add:Nn
\fp_add:cn
\fp_gadd:Nn
\fp_gadd:cn
```

Updated: 2012-05-08

```
\fp_sub:Nn
\fp_sub:cn
\fp_gsub:Nn
\fp_gsub:cn
```

Updated: 2012-05-08

```
\fp_set_eq:NN <fp var1 > <fp var2 >
```

Sets the floating point variable $\langle fp \ var_1 \rangle$ equal to the current value of $\langle fp \ var_2 \rangle$.

```
\fp_add:Nn <fp var> {{floating point expression}}
```

Adds the result of computing the $\langle floating \ point \ expression \rangle$ to the $\langle fp \ var \rangle$.

```
\fp_sub:Nn <fp var> {{floating point expression}}
```

Subtracts the result of computing the $\langle floating \ point \ expression \rangle$ from the $\langle fp \ var \rangle$.

3 Using floating point numbers

```
\fp_eval:n ★
```

New: 2012-05-08

Updated: 2012-07-08

```
\fp_eval:n {{floating point expression}}
```

Evaluates the $\langle floating \ point \ expression \rangle$ and expresses the result as a decimal number with 16 significant figures and no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed, and integers are expressed without a decimal separator. The values $\pm\infty$ and nan trigger an “invalid operation” exception. This function is identical to `\fp_to_decimal:n`.

```
\fp_to_decimal:N ★
\fp_to_decimal:(c|n) ★
```

New: 2012-05-08

Updated: 2012-07-08

```
\fp_to_decimal:N <fp var>
\fp_to_decimal:n {{floating point expression}}
```

Evaluates the $\langle floating \ point \ expression \rangle$ and expresses the result as a decimal number with 16 significant figures and no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed, and integers are expressed without a decimal separator. The values $\pm\infty$ and nan trigger an “invalid operation” exception.

```
\fp_to_dim:N ★
\fp_to_dim:(c|n) ★
```

Updated: 2012-07-08

```
\fp_to_dim:N <fp var>
```

```
\fp_to_dim:n {{floating point expression}}
```

Evaluates the $\langle floating \ point \ expression \rangle$ and expresses the result as a dimension (in pt) suitable for use in dimension expressions. The output is identical to `\fp_to_decimal:n`, with an additional trailing pt. In particular, the result may be outside the range $[-2^{14} + 2^{-17}, 2^{14} - 2^{-17}]$ of valid TeX dimensions, leading to overflow errors if used as a dimension. The values $\pm\infty$ and nan trigger an “invalid operation” exception.

\fp_to_int:N ★
\fp_to_int:(c|n) ★

Updated: 2012-07-08

\fp_to_int:N *fp var*
\fp_to_int:n {{floating point expression}}

Evaluates the *floating point expression*, and rounds the result to the closest integer, with ties rounded to an even integer. The result may be outside the range $[-2^{31} + 1, 2^{31} - 1]$ of valid TeX integers, triggering TeX errors if used in an integer expression. The values $\pm\infty$ and `nan` trigger an “invalid operation” exception.

\fp_to_scientific:N ★
\fp_to_scientific:(c|n) ★

New: 2012-05-08

Updated: 2012-07-08

\fp_to_scientific:N *fp var*
\fp_to_scientific:n {{floating point expression}}

Evaluates the *floating point expression* and expresses the result in scientific notation with 16 significant figures:

optional -⟨digit⟩.⟨15 digits⟩e⟨optional sign⟩⟨exponent⟩

The leading ⟨digit⟩ is non-zero except in the case of ± 0 . The values $\pm\infty$ and `nan` trigger an “invalid operation” exception.

\fp_to_tl:N ★
\fp_to_tl:(c|n) ★

Updated: 2012-07-08

\fp_to_tl:N *fp var*
\fp_to_tl:n {{floating point expression}}

Evaluates the *floating point expression* and expresses the result in (almost) the shortest possible form. Numbers in the ranges $(0, 10^{-3})$ and $[10^{16}, \infty)$ are expressed in scientific notation with trailing zeros trimmed (see `\fp_to_scientific:n`). Numbers in the range $[10^{-3}, 10^{16})$ are expressed in a decimal notation without exponent, with trailing zeros trimmed, and no decimal separator for integer values (see `\fp_to_decimal:n`). Negative numbers start with `-`. The special values ± 0 , `±inf` and `nan` are rendered as `0`, `-0`, `inf`, `-inf`, and `nan` respectively.

\fp_use:N ★
\fp_use:c ★

Updated: 2012-07-08

\fp_use:N *fp var*

Inserts the value of the *fp var* into the input stream as a decimal number with 16 significant figures and no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed. Integers are expressed without a decimal separator. The values $\pm\infty$ and `nan` trigger an “invalid operation” exception. This function is identical to `\fp_to_decimal:N`.

4 Floating point conditionals

\fp_if_exist_p:N ★
\fp_if_exist_p:c ★
\fp_if_exist:NTF ★
\fp_if_exist:cTF ★

Updated: 2012-05-08

\fp_if_exist_p:N *fp var*
\fp_if_exist:NTF *fp var* {{true code}} {{false code}}

Tests whether the *fp var* is currently defined. This does not check that the *fp var* really is a floating point variable.

```
\fp_compare_p:nNn ★
\fp_compare_p:n ★
\fp_compare:nNnTF ★
\fp_compare:nTF ★
```

Updated: 2012-05-08

```
\fp_compare_p:nNn {⟨fpexpr₁⟩} ⟨relation⟩ {⟨fpexpr₂⟩}
\fp_compare:nNnTF {⟨fpexpr₁⟩} ⟨relation⟩ {⟨fpexpr₂⟩} {⟨true code⟩} {⟨false code⟩}
\fp_compare_p:n {⟨fpexpr₁⟩} ⟨relation⟩ {⟨fpexpr₂⟩} ?
\fp_compare:nTF {⟨fpexpr₁⟩} ⟨relation⟩ {⟨fpexpr₂⟩} ? {⟨true code⟩} {⟨false code⟩}
```

Compares the *⟨fpexpr₁⟩* and the *⟨fpexpr₂⟩*, and returns **true** if the *⟨relation⟩* is obeyed. Two floating point numbers *x* and *y* may obey four mutually exclusive relations: *x*⟨y, *x*=*y*, *x*⟩*y*, or *x* and *y* are not ordered. The latter case occurs exactly when one of the operands is **nan**, and this relations is denoted by the symbol **?**. The **nNn** functions support the *⟨relations⟩* <, =, >, and **?**. The **n** functions support as a *⟨relation⟩* any combination of those four symbols, plus an optional leading ! (which negates the *⟨relation⟩*), with the restriction that the *⟨relation⟩* may not start with **?**. Common choices of *⟨relation⟩* include **>=** (greater or equal), **!=** (not equal), **!?** (comparable). Note that a **nan** is distinct from any value, even another **nan**, hence *x* = *x* is not true for a **nan**. Thus to test if a value is **nan**, use

```
\fp_compare:nNnTF {⟨value⟩} != {⟨value⟩}
{ } % <value> is nan
{ } % <value> is not nan
```

5 Floating point expression loops

```
\fp_do_until:nNnn ★

```

New: 2012-08-16

```
\fp_do_until:nNnn {⟨fpexpr₁⟩} ⟨relation⟩ {⟨fpexpr₂⟩} {⟨code⟩}
```

Places the *⟨code⟩* in the input stream for TeX to process, and then evaluates the relationship between the two *(floating point expressions)* as described for **\fp_compare:nNnTF**. If the test is **false** then the *⟨code⟩* will be inserted into the input stream again and a loop will occur until the *⟨relation⟩* is **true**.

```
\fp_do_while:nNnn ★

```

New: 2012-08-16

```
\fp_do_while:nNnn {⟨fpexpr₁⟩} ⟨relation⟩ {⟨fpexpr₂⟩} {⟨code⟩}
```

Places the *⟨code⟩* in the input stream for TeX to process, and then evaluates the relationship between the two *(floating point expressions)* as described for **\fp_compare:nNnTF**. If the test is **true** then the *⟨code⟩* will be inserted into the input stream again and a loop will occur until the *⟨relation⟩* is **false**.

```
\fp_until_do:nNnn ★

```

New: 2012-08-16

```
\fp_until_do:nNnn {⟨fpexpr₁⟩} ⟨relation⟩ {⟨fpexpr₂⟩} {⟨code⟩}
```

Evaluates the relationship between the two *(floating point expressions)* as described for **\fp_compare:nNnTF**, and then places the *⟨code⟩* in the input stream if the *⟨relation⟩* is **false**. After the *⟨code⟩* has been processed by TeX the test will be repeated, and a loop will occur until the test is **true**.

\fp_while_do:nNnn ☆New: 2012-08-16

\fp_while_do:nNnn {*fexpr*₁} {*relation*} {*fexpr*₂} {*code*}

Evaluates the relationship between the two *floating point expressions* as described for \fp_compare:nNnTF, and then places the *code* in the input stream if the *relation* is true. After the *code* has been processed by TeX the test will be repeated, and a loop will occur until the test is false.

\fp_do_until:nn ☆New: 2012-08-16

\fp_do_until:nn {*fexpr*₁} {*relation*} {*fexpr*₂} {*code*}

Places the *code* in the input stream for TeX to process, and then evaluates the relationship between the two *floating point expressions* as described for \fp_compare:nTF. If the test is false then the *code* will be inserted into the input stream again and a loop will occur until the *relation* is true.

\fp_do_while:nn ☆New: 2012-08-16

\fp_do_while:nn {*fexpr*₁} {*relation*} {*fexpr*₂} {*code*}

Places the *code* in the input stream for TeX to process, and then evaluates the relationship between the two *floating point expressions* as described for \fp_compare:nTF. If the test is true then the *code* will be inserted into the input stream again and a loop will occur until the *relation* is false.

\fp_until_do:nn ☆New: 2012-08-16

\fp_until_do:nn {*fexpr*₁} {*relation*} {*fexpr*₂} {*code*}

Evaluates the relationship between the two *floating point expressions* as described for \fp_compare:nTF, and then places the *code* in the input stream if the *relation* is false. After the *code* has been processed by TeX the test will be repeated, and a loop will occur until the test is true.

\fp_while_do:nn ☆New: 2012-08-16

\fp_while_do:nn {*fexpr*₁} {*relation*} {*fexpr*₂} {*code*}

Evaluates the relationship between the two *floating point expressions* as described for \fp_compare:nTF, and then places the *code* in the input stream if the *relation* is true. After the *code* has been processed by TeX the test will be repeated, and a loop will occur until the test is false.

6 Some useful constants, and scratch variables

**\c_zero_fp
\c_minus_zero_fp**New: 2012-05-08

Zero, with either sign.

**\c_inf_fp
\c_minus_inf_fp**New: 2012-05-08

Infinity, with either sign. These can be input directly in a floating point expression as inf and -inf.

\c_e_fp

Updated: 2012-05-08

The value of the base of the natural logarithm, $e = \exp(1)$.

\c_pi_fp

Updated: 2012-05-08

The value of π . This can be input directly in a floating point expression as `pi`. The value is rounded in a slightly odd way, to ensure for instance that `sin(pi)` yields an exact 0.

\c_one_degree_fp

New: 2012-05-08

The value of 1° in radians. Multiply an angle given in degrees by this value to obtain a result in radians, suitable to be used for trigonometric functions. Within floating point expressions, this can be accessed as `deg`. Note that $180 \deg = \pi$ exactly.

\l_tmpa_fp

\l_tmpb_fp

Scratch floating points for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

\g_tmpa_fp

\g_tmpb_fp

Scratch floating points for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

7 Floating point exceptions

The functions defined in this section are experimental, and their functionality may be altered or removed altogether.

“Exceptions” may occur when performing some floating point operations, such as $0 / 0$, or $10 ** 1e9999$. The IEEE standard defines 5 types of exceptions.

- *Overflow* occurs whenever the result of an operation is too large to be represented as a normal floating point number. This results in $\pm\infty$.
- *Underflow* occurs whenever the result of an operation is too close to 0 to be represented as a normal floating point number. This results in ± 0 .
- *Invalid operation* occurs for operations with no defined outcome, for instance $0/0$, or $\sin(\infty)$, and almost any operation involving a `nan`. This normally results in a `nan`, except for conversion functions whose target type does not have a notion of `nan` (*e.g.*, `\fp_to_dim:n`).
- *Division by zero* occurs when dividing a non-zero number by 0, or when evaluating *e.g.*, $\ln(0)$ or $\cot(0)$. This results in $\pm\infty$.
- *Inexact* occurs whenever the result of a computation is not exact, in other words, almost always. At the moment, this exception is entirely ignored in L^AT_EX3.

To each exception is associated a “flag”, which can be either *on* or *off*. By default, the “invalid operation” exception triggers an (expandable) error, and raises the corresponding flag. Other exceptions only raise the corresponding flag. The state of the flag can be tested and modified. The behaviour when an exception occurs can be modified (using `\fp_trap:nn`) to either produce an error and turn the flag on, or only turn the flag on, or do nothing at all.

`\fp_if_flag_on_p:n *`
`\fp_if_flag_on:nTF *`

New: 2012-08-08

`\fp_if_flag_on_p:n {<exception>}`
`\fp_if_flag_on:nTF {<exception>} {<true code>} {<false code>}`

Tests if the flag for the *<exception>* is on, which normally means the given *<exception>* has occurred. *This function is experimental, and may be altered or removed.*

`\fp_flag_off:n`

New: 2012-08-08

`\fp_flag_off:n {<exception>}`

Locally turns off the flag which indicates whether the *<exception>* has occurred. *This function is experimental, and may be altered or removed.*

`\fp_flag_on:n *`

New: 2012-08-08

`\fp_flag_on:n {<exception>}`

Locally turns on the flag to indicate (or pretend) that the *<exception>* has occurred. Note that this function is expandable: it is used internally by l3fp to signal when exceptions do occur. *This function is experimental, and may be altered or removed.*

`\fp_trap:nn`

New: 2012-07-19

Updated: 2012-08-08

`\fp_trap:nn {<exception>} {<trap type>}`

All occurrences of the *<exception>* (`invalid_operation`, `division_by_zero`, `overflow`, or `underflow`) within the current group are treated as *<trap type>*, which can be

- `none`: the *<exception>* will be entirely ignored, and leave no trace;
- `flag`: the *<exception>* will turn the corresponding flag on when it occurs;
- `error`: additionally, the *<exception>* will halt the T_EX run and display some information about the current operation in the terminal.

This function is experimental, and may be altered or removed.

8 Viewing floating points

`\fp_show:N`
`\fp_show:(c|n)`

New: 2012-05-08

Updated: 2012-08-14

`\fp_show:N {fp var}`
`\fp_show:n {floating point expression}`

Evaluates the *<floating point expression>* and displays the result in the terminal.

9 Floating point expressions

9.1 Input of floating point numbers

We support four types of floating point numbers:

- $\pm 0.d_1d_2\dots d_{16} \cdot 10^n$, a normal floating point number, with $d_i \in [0, 9]$, $d_1 \neq 0$, and $|n| \leq 10000$;
- ± 0 , zero, with a given sign;
- $\pm\infty$, infinity, with a given sign;
- `nan`, is “not a number”, and can be either quiet or signalling (*not yet*: this distinction is currently unsupported);

(*not yet*) subnormal numbers $\pm 0.d_1d_2\dots d_{16} \cdot 10^{-10000}$ with $d_1 = 0$.

Normal floating point numbers are stored in base 10, with 16 significant figures.

On input, a normal floating point number consists of:

- $\langle sign \rangle$: a possibly empty string of + and - characters;
- $\langle significand \rangle$: a non-empty string of digits together with zero or one dot;
- $\langle exponent \rangle$ optionally: the character e, followed by a possibly empty string of + and - tokens, and a non-empty string of digits.

The sign of the resulting number is + if $\langle sign \rangle$ contains an even number of -, and - otherwise, hence, an empty $\langle sign \rangle$ denotes a non-negative input. The stored significand is obtained from $\langle significand \rangle$ by omitting the decimal separator and leading zeros, and rounding to 16 significant digits, filling with trailing zeros if necessary. In particular, the value stored is exact if the input $\langle significand \rangle$ has at most 16 digits. The stored $\langle exponent \rangle$ is obtained by combining the input $\langle exponent \rangle$ (0 if absent) with a shift depending on the position of the significand and the number of leading zeros.

A special case arises if the resulting $\langle exponent \rangle$ is either too large or too small for the floating point number to be represented. This results either in an overflow (the number is then replaced by $\pm\infty$), or an underflow (resulting in ± 0).

The result is thus ± 0 if and only if $\langle significand \rangle$ contains no non-zero digit (*i.e.*, consists only in 0 characters, and an optional . character), or if there is an underflow. Note that a single dot is currently a valid floating point number, equal to +0, but that is not guaranteed to remain true.

Special numbers are input as follows:

- `inf` represents $+\infty$, and can be preceded by any $\langle sign \rangle$, yielding $\pm\infty$ as appropriate.
- `nan` represents a (quiet) non-number. It can be preceded by any sign, but that will be ignored.
- Any unrecognizable string triggers an error, and produces a `nan`.

Note that `e-1` is not a representation of 10^{-1} , because it could be mistaken with the difference of “`e`” and `1`. This is consistent with several other programming languages. However, in order to avoid confusions, `e-1` is not considered to be this difference either. To input the base of natural logarithms, use `exp(1)` or `\c_e_fp`.

9.2 Precedence of operators

We list here all the operations supported in floating point expressions, in order of decreasing precedence: operations listed earlier bind more tightly than operations listed below them.

- Implicit multiplication by juxtaposition (`2pi`, *etc*).
- Function calls (`sin`, `ln`, *etc*).
- Binary `**` and `^` (right associative).
- Unary `+`, `-`, `!`.
- Binary `*`, `/` and `%`.
- Binary `+` and `-`.
- Comparisons `>=`, `!=`, `<?`, *etc*.
- Logical `and`, denoted by `&&`.
- Logical `or`, denoted by `||`.
- Ternary operator `?:` (right associative).

The precedence of operations can be overridden using parentheses. In particular, those precedences imply that

$$\begin{aligned}\sin 2\pi &= \sin(2\pi) = 0, \\ 2^{2\max(3,4)} &= 2^{2\max(3,4)} = 256.\end{aligned}$$

Functions are called on the value of their argument, contrarily to TeX macros.

9.3 Operations

We now present the various operations allowed in floating point expressions, from the lowest precedence to the highest. When used as a truth value, a floating point expression is `false` if it is ± 0 , and `true` otherwise, including when it is `nan`.

?: `\fp_eval:n { <operand1> ? <operand2> : <operand3> }`

The ternary operator `?:` results in $\langle operand_2 \rangle$ if $\langle operand_1 \rangle$ is true, and $\langle operand_3 \rangle$ if it is false (equal to ± 0). All three $\langle operands \rangle$ are evaluated in all cases. The operator is right associative, hence

```
\fp_eval:n
{
  1 + 3 > 4 ? 1 :
  2 + 4 > 5 ? 2 :
  3 + 5 > 6 ? 3 : 4
}
```

first tests whether $1 + 3 > 4$; since this isn't true, the branch following `:` is taken, and $2 + 4 > 5$ is compared; since this is true, the branch before `:` is taken, and everything else is (evaluated then) ignored. That allows testing for various cases in a concise manner, with the drawback that all computations are made in all cases.

TWOBARS `\fp_eval:n { <operand1> || <operand2> }`

If $\langle operand_1 \rangle$ is true (non-zero), use that value, otherwise the value of $\langle operand_2 \rangle$. Both $\langle operands \rangle$ are evaluated in all cases.

&& `\fp_eval:n { <operand1> && <operand2> }`

If $\langle operand_1 \rangle$ is false (equal to ± 0), use that value, otherwise the value of $\langle operand_2 \rangle$. Both $\langle operands \rangle$ are evaluated in all cases.

< `\fp_eval:n { <operand1> <comparison> <operand2> }`

= The $\langle comparison \rangle$ consists of a non-empty string of `<`, `=`, `>`, and `?`, optionally preceded by `!`. It may not start with `?`. This evaluates to `+1` if the $\langle comparison \rangle$ between the $\langle operand_1 \rangle$ and $\langle operand_2 \rangle$ is true, and `+0` otherwise.

+ `\fp_eval:n { <operand1> + <operand2> }`

- `\fp_eval:n { <operand1> - <operand2> }`

Computes the sum or the difference of its two $\langle operands \rangle$. The “invalid operation” exception occurs for $\infty - \infty$. “Underflow” and “overflow” occur when appropriate.

***** `\fp_eval:n { <operand1> * <operand2> }`

/ `\fp_eval:n { <operand1> / <operand2> }`

Computes the product or the ratio of its two $\langle operands \rangle$. The “invalid operation” exception occurs for ∞/∞ , $0/0$, or $0 * \infty$. “Division by zero” occurs when dividing a finite non-zero number by ± 0 . “Underflow” and “overflow” occur when appropriate.

<u>+</u>	<code>\fp_eval:n { + <operand> }</code>
<u>-</u>	<code>\fp_eval:n { - <operand> }</code>
<u>!</u>	<code>\fp_eval:n { ! <operand> }</code>
<u>-</u>	The unary <code>+</code> does nothing, the unary <code>-</code> changes the sign of the <code><operand></code> , and <code>! <operand></code> evaluates to 1 if <code><operand></code> is false and 0 otherwise (this is the <code>not</code> boolean function). Those operations never raise exceptions.
<u>**</u>	<code>\fp_eval:n { <operand>1 ** <operand>2 }</code>
<u>^</u>	<code>\fp_eval:n { <operand>1 ^ <operand>2 }</code>
<u>-</u>	Raises <code><operand>1</code> to the power <code><operand>2</code> . This operation is right associative, hence <code>2 ** 2 ** 3</code> equals $2^2^3 = 256$. The “invalid operation” exception occurs if <code><operand>1</code> is negative or -0 , and <code><operand>2</code> is not an integer, unless the result is zero (in that case, the sign is chosen arbitrarily to be <code>+0</code>). “Division by zero” occurs when raising ± 0 to a strictly negative power. “Underflow” and “overflow” occur when appropriate.
<u>abs</u>	<code>\fp_eval:n { abs(<fpexpr>) }</code>
<u>-</u>	Computes the absolute value of the <code><fpexpr></code> . This function does not raise any exception beyond those raised when computing its operand <code><fpexpr></code> . See also <code>\fp_abs:n</code> .
<u>exp</u>	<code>\fp_eval:n { exp(<fpexpr>) }</code>
<u>-</u>	Computes the exponential of the <code><fpexpr></code> . “Underflow” and “overflow” occur when appropriate.
<u>ln</u>	<code>\fp_eval:n { ln(<fpexpr>) }</code>
<u>-</u>	Computes the natural logarithm of the <code><fpexpr></code> . Negative numbers have no (real) logarithm, hence the “invalid operation” is raised in that case, including for $\ln(-0)$. “Division by zero” occurs when evaluating $\ln(+0) = -\infty$. “Underflow” and “overflow” occur when appropriate.
<u>max</u>	<code>\fp_eval:n { max(<fpexpr>1 , <fpexpr>2 , ...) }</code>
<u>min</u>	<code>\fp_eval:n { min(<fpexpr>1 , <fpexpr>2 , ...) }</code>
<u>-</u>	Evaluates each <code><fpexpr></code> and computes the largest (smallest) of those. If any of the <code><fpexpr></code> is a <code>nan</code> , the result is <code>nan</code> . Those operations do not raise exceptions.

round \fp_eval:n { round <option> (<fpexpr>) }
round0 \fp_eval:n { round <option> (<fpexpr1> , <fpexpr2>) }
round+ Rounds <fpexpr₁> to <fpexpr₂> places. When <fpexpr₂> is omitted, it is assumed to be 0,
round- *i.e.*, <fpexpr₁> is rounded to an integer. The <option> controls the rounding direction:

- by default, the operation rounds to the closest allowed number (rounding ties to even);
- with 0, the operation rounds towards 0, *i.e.*, truncates;
- with +, the operation rounds towards $+\infty$;
- with -, the operation rounds towards $-\infty$.

If <fpexpr₂> does not yield an integer less than 10^8 in absolute value, then an “invalid operation” exception is raised. “Overflow” may occur if the result is infinite (this cannot happen unless <fpexpr₂> < -9984).

sin \fp_eval:n { sin(<fpexpr>) }
cos \fp_eval:n { cos(<fpexpr>) }
tan \fp_eval:n { tan(<fpexpr>) }
cot \fp_eval:n { cot(<fpexpr>) }
csc \fp_eval:n { csc(<fpexpr>) }
sec \fp_eval:n { sec(<fpexpr>) }

Computes the sine, cosine, tangent, cotangent, cosecant, or secant of the <fpexpr>. The trigonometric functions are undefined for an argument of $\pm\infty$, leading to the “invalid operation” exception. Additionally, evaluating tangent, cotangent, cosecant, or secant at one of their poles leads to a “division by zero” exception. “Underflow” and “overflow” occur when appropriate.

inf The special values $+\infty$, $-\infty$, and **nan** are represented as **inf**, **-inf** and **nan** (see \c_-inf_fp, \c_minus_inf_fp and \c_nan_fp).

pi The value of π (see \c_pi_fp).

deg The value of 1° in radians (see \c_one_degree_fp).

<u>em</u>	Those units of measurement are equal to their values in <code>pt</code> , namely
<u>ex</u>	
<u>in</u>	$1\text{in} = 72.27\text{pt}$
<u>pt</u>	$1\text{pt} = 1\text{pt}$
<u>pc</u>	$1\text{pc} = 12\text{pt}$
<u>cm</u>	$1\text{cm} = \frac{1}{2.54}\text{in} = 28.45275590551181\text{pt}$
<u>mm</u>	$1\text{mm} = \frac{1}{25.4}\text{in} = 2.845275590551181\text{pt}$
<u>dd</u>	$1\text{dd} = 0.376065\text{mm} = 1.07000856496063\text{pt}$
<u>cc</u>	$1\text{cc} = 12\text{dd} = 12.84010277952756\text{pt}$
<u>nd</u>	$1\text{nd} = 0.375\text{mm} = 1.066978346456693\text{pt}$
<u>nc</u>	$1\text{nc} = 12\text{nd} = 12.80374015748031\text{pt}$
<u>bp</u>	$1\text{bp} = \frac{1}{72}\text{in} = 1.00375\text{pt}$
<u>sp</u>	$1\text{sp} = 2^{-16}\text{pt} = 1.52587890625e - 5\text{pt}.$

The values of the (font-dependent) units `em` and `ex` are gathered from T_EX when the surrounding floating point expression is evaluated.

<u>true</u>	Other names for 1 and +0.
<u>false</u>	

\dim_to_fp:n ★

New: 2012-05-08

Expands to an internal floating point number equal to the value of the $\langle dimexpr \rangle$ in `pt`. Since dimension expressions are evaluated much faster than their floating point equivalent, `\dim_to_fp:n` can be used to speed up parts of a computation where a low precision is acceptable.

\fp_abs:n ★

New: 2012-05-14

Updated: 2012-07-08

`\fp_abs:n {<floating point expression>}`

Evaluates the $\langle floating\ point\ expression \rangle$ as described for `\fp_eval:n` and leaves the absolute value of the result in the input stream. This function does not raise any exception beyond those raised when evaluating its argument. Within floating point expressions, `abs()` can be used.

\fp_max:nn ★

\fp_min:nn ★

New: 2012-09-26

`\fp_max:nn {<fp expression 1>} {<fp expression 2>}`

Evaluates the $\langle floating\ point\ expressions \rangle$ as described for `\fp_eval:n` and leaves the resulting larger (`max`) or smaller (`min`) value in the input stream. This function does not raise any exception beyond those raised when evaluating its argument. Within floating point expressions, `max()` and `min()` can be used.

10 Disclaimer and roadmap

The package may break down if:

- the escape character is either a digit, or an underscore,
- the `\uccodes` are changed: the test for whether a character is a letter actually tests if the upper-case code of the character is between A and Z.

The following need to be done. I'll try to time-order the items.

- Decide what exponent range to consider.
- Change the internal representation of fp, by replacing braced groups of 4 digits by delimited arguments. Also consider changing the fp structure a bit to allow using `\pdftex_strcmp:D` to compare (not in LuaTEX: it is too slow)?
- Modulo and remainder, and rounding functions `quantize`, `quantize0`, `quantize+`, `quantize-`, `quantize=`, `round=`. Should the modulo also be provided as (catcode 12) %?
- `\fp_format:nn {\<fpexpr\>} {\<format\>}`, but what should `\<format\>` be? More general pretty printing?
- Add `and`, `or`, `xor`? Perhaps under the names `all`, `any`, and `xor`?
- Add `csc` and `sec`.
- Add $\log(x, b)$ for logarithm of x in base b .
- `hypot` (Euclidean length) and $\text{atan}(x, y) = \text{atan}(x/y)$, also called `atan2` in other math packages. Cartesian-to-polar transform. Other inverse trigonometric functions `acos`, `asin`, `atan` (one and two arguments). Also `asec`, `acsc`?
- Hyperbolic functions `cosh`, `sinh`, `tanh`.
- Inverse hyperbolics.
- Base conversion, input such as `0xAB.CDEF`.
- Random numbers (pgfmath provides `rnd`, `rand`, `random`), with seed reset at every `\fp_set:Nn`.
- Factorial (not with !), gamma function.
- Improve coefficients of the `sin` and `tan` series.
- Treat upper and lower case letters identically in identifiers, and ignore underscores.
- Parse $-3 < -2 < -1$ as it should, not $(-3 < -2) < -1$.
- Add an `array(1,2,3)` and `i=complex(0,1)`.

- Provide an experimental `map` function? Perhaps easier to implement if it is a single character, `@sin(1,2)`?
- Provide `\fp_if_nan:nTF`, and an `isnan` function?

`Pgfmath` also provides box-measurements (depth, height, width), but boxes are not possible expandably.

Bugs. (Exclamation points mark important bugs.)

- ! Some functions are not monotonic when they should. For instance, $\sin(1 - 10^{-16})$ is wrongly greater than $\sin(1)$.
- Add exceptions to `?:`, `!<=>?`, `&&`, `||`, and `!`.
- `round` should accept any integer as its second argument.
- Logarithms of numbers very close to 1 are inaccurate.
- `tan` and `cot` give very slightly wrong results for arguments near 10^{-8} .
- When rounding towards $-\infty$, `\dim_to_fp:n {0pt}` should return -0 , not $+0$.
- The result of $(\pm 0) + (\pm 0)$ should depend on the rounding mode.
- `0e9999999999` gives a `TEX` “number too large” error.
- Conversion to integers with `\fp_to_int:n` does not check for overflow.
- Subnormals are not implemented.
- `max(-inf)` will lose any information attached to this `-inf`.
- The overflow trap receives the wrong argument in `l3fp-expo` (see `exp(1e5678)` in `m3fp-traps001`).

Possible optimizations/improvements.

- Optimize argument reduction for trigonometric functions: we don’t need 6×4 digits here, only 4×4 .
- In subsection 9.1, write a grammar.
- Fix the `TWO BARS` business with the index.
- It would be nice if the `parse` auxiliaries for each operation were set up in the corresponding module, rather than centralizing in `l3fp-parse`.
- Some functions should get an `_o` ending to indicate that they expand after their result.
- More care should be given to distinguish expandable/restricted expandable (auxiliary and internal) functions.
- The code for the `ternary` set of functions is ugly.

- There are many `\sim` missing in the doc to avoid bad line-breaks.
- The algorithm for computing the logarithm of the significand could be made to use a 5 terms Taylor series instead of 10 terms by taking $c = 2000/(\lfloor 200x \rfloor + 1) \in [10, 95]$ instead of $c \in [1, 10]$. Also, it would then be possible to simplify the computation of t , using methods similar to `\@@_fixed_div_to_float:ww`. However, we would then have to hard-code the logarithms of 44 small integers instead of 9.
- Improve notations in the explanations of the division algorithm (`l3fp-basics`).
- Understand and document `\@@_basis_pack_weird_low>NNNNw` and `\@@_basis_pack_weird_high>NNNNNNNNw` better. Move the other `basics_pack` auxiliaries to `l3fp-aux` under a better name.
- Find out if underflow can really occur for trigonometric functions, and redoc as appropriate.
- Add bibliography. Some of Kahan's articles, some previous `TeX fp` packages, the international standards,...
- Also take into account the “inexact” exception?

Part XXII

The **l3luatex** package

LuaTeX-specific functions

1 Breaking out to Lua

The LuaTeX engine provides access to the Lua programming language, and with it access to the “internals” of TeX. In order to use this within the framework provided here, a family of functions is available. When used with pdfTeX or XeTeX these will raise an error: use `\luatex_if_engine:T` to avoid this. Details of coding the LuaTeX engine are detailed in the LuaTeX manual.

`\lua_now:n` ★
`\lua_now:x` ★
Updated: 2012-08-02

`\lua_now:n {<token list>}`

The $\langle token\ list\rangle$ is first tokenized by TeX, which will include converting line ends to spaces in the usual TeX manner and which respects currently-applicable TeX category codes. The resulting $\langle Lua\ input\rangle$ is passed to the Lua interpreter for processing. Each `\lua_now:n` block is treated by Lua as a separate chunk. The Lua interpreter will execute the $\langle Lua\ input\rangle$ immediately, and in an expandable manner.

`\lua_now_x:n` ★
`\lua_now_x:x` ★
New: 2012-08-02

`\lua_now_x:n {<token list>}`

The $\langle token\ list\rangle$ is first tokenized and expanded by TeX, which will include converting line ends to spaces in the usual TeX manner and which respects currently-applicable TeX category codes. The resulting $\langle Lua\ input\rangle$ is passed to the Lua interpreter for processing. Each `\lua_now_x:n` block is treated by Lua as a separate chunk. The Lua interpreter will execute the $\langle Lua\ input\rangle$ immediately, and in an expandable manner.

TeXhackers note: `\lua_now_x:n` is the LuaTeX primitive `\directlua` renamed.

`\lua_shipout:n`
`\lua_shipout:x`

`\lua_shipout:n {<token list>}`

The $\langle token\ list\rangle$ is first tokenized by TeX, which will include converting line ends to spaces in the usual TeX manner and which respects currently-applicable TeX category codes. The resulting $\langle Lua\ input\rangle$ is passed to the Lua interpreter when the current page is finalised (*i.e.* at shipout). Each `\lua_shipout:n` block is treated by Lua as a separate chunk. The Lua interpreter will execute the $\langle Lua\ input\rangle$ during the page-building routine: no TeX expansion of the $\langle Lua\ input\rangle$ will occur at this stage.

TeXhackers note: At a TeX level, the $\langle Lua\ input\rangle$ is stored as a “whatsit”.

`\lua_shipout_x:n`
`\lua_shipout_x:x`

`\lua_shipout:n {<token list>}`

The *<token list>* is first tokenized by TeX, which will include converting line ends to spaces in the usual TeX manner and which respects currently-applicable TeX category codes. The resulting *<Lua input>* is passed to the Lua interpreter when the current page is finalised (*i.e.* at shipout). Each `\lua_shipout:n` block is treated by Lua as a separate chunk. The Lua interpreter will execute the *<Lua input>* during the page-building routine: the *<Lua input>* is expanded during this process in addition to any expansion when the argument was read. This makes these functions suitable for including material finalised during the page building process (such as the page number).

TeXhackers note: `\lua_shipout_x:n` is the LuaTeX primitive `\latelua` named using the L^AT_EX3 scheme.

At a TeX level, the *<Lua input>* is stored as a “whatsit”.

2 Category code tables

As well as providing methods to break out into Lua, there are places where additional L^AT_EX3 functions are provided by the LuaTeX engine. In particular, LuaTeX provides category code tables. These can be used to ensure that a set of category codes are in force in a more robust way than is possible with other engines. These are therefore used by `\ExplSyntaxOn` and `\ExplSyntaxOff` when using the LuaTeX engine.

`\cctab_new:N`

`\cctab_new:N <category code table>`

Creates a new category code table, initially with the codes as used by iniTeX.

`\cctab_gset:Nn`

`\cctab_gset:Nn <category code table> {<category code set up>}`

Sets the *<category code table>* to apply the category codes which apply when the prevailing régime is modified by the *<category code set up>*. Thus within a standard code block the starting point will be the code applied by `\c_code_cctab`. The assignment of the table is global: the underlying primitive does not respect grouping.

`\cctab_begin:N`

`\cctab_begin:N <category code table>`

Switches the category codes in force to those stored in the *<category code table>*. The prevailing codes before the function is called are added to a stack, for use with `\cctab_end::`.

`\cctab_end:`

Ends the scope of a *<category code table>* started using `\cctab_begin:N`, returning the codes to those in force before the matching `\cctab_begin:N` was used.

`\c_code_cctab`

Category code table for the code environment. This does not include setting the behaviour of the line-end character, which is only altered by `\ExplSyntaxOn`.

<u>\c_document_cctab</u>	Category code table for a standard L ^A T _E X document. This does not include setting the behaviour of the line-end character, which is only altered by \ExplSyntaxOff.
<u>\c_initex_cctab</u>	Category code table as set up by iniT _E X.
<u>\c_other_cctab</u>	Category code table where all characters have category code 12 (other).
<u>\c_str_cctab</u>	Category code table where all characters have category code 12 (other) with the exception of spaces, which have category code 10 (space).

Part XXIII

The `I3candidates` package

Experimental additions to `I3kernel`

This module provides a space in which functions can be added to `I3kernel` (`expl3`) while still being experimental. As such, the functions here may not remain in their current form, or indeed at all, in `I3kernel` in the future. In contrast to the material in `I3experimental`, the functions here are all *small* additions to the kernel. We encourage programmers to test them out and report back on the `LaTeX-L` mailing list.

1 Additions to `I3basics`

`\cs_if_exist_use:NTF` * `\cs_if_exist_use:NTF <control sequence> {<true code>} {<false code>}`
`\cs_if_exist_use:cTF` * If the `<control sequence>` exists, leave it in the input stream, followed by the `<true code>` (unbraced). Otherwise, leave the `<false>` code in the input stream. For example,

```
\cs_set:Npn \mypkg_use_character:N #1
  { \cs_if_exist_use:cF { \mypkg_#1:n } { \mypkg_default:N #1 } }
```

calls the function `\mypkg_#1:n` if it exists, and falls back to a default action otherwise. This could also be done (more slowly) using `\str_case_x:nnn`.

TeXhackers note: The `c` variants do not introduce the `<control sequence>` in the hash table if it is not there.

2 Additions to `I3box`

2.1 Affine transformations

Affine transformations are changes which (informally) preserve straight lines. Simple translations are affine transformations, but are better handled in `TeX` by doing the translation first, then inserting an unmodified box. On the other hand, rotation and resizing of boxed material can best be handled by modifying boxes. These transformations are described here.

`\box_resize:Nnn` `\box_resize:cnn` `\box_resize:Nnn <box> {<x-size>} {<y-size>}`

Resize the `<box>` to `<x-size>` horizontally and `<y-size>` vertically (both of the sizes are dimension expressions). The `<y-size>` is the vertical size (height plus depth) of the box. The updated `<box>` will be an hbox, irrespective of the nature of the `<box>` before the resizing is applied. Negative sizes will cause the material in the `<box>` to be reversed in direction, but the reference point of the `<box>` will be unchanged. The resizing applies within the current `TeX` group level.

```
\box_resize_to_ht_plus_dp:Nn  \box_resize_to_ht_plus_dp:Nn <box> {<y-size>}
\box_resize_to_ht_plus_dp:cn
```

Resize the $\langle box \rangle$ to $\langle y-size \rangle$ vertically, scaling the horizontal size by the same amount ($\langle y-size \rangle$ is a dimension expression). The $\langle y-size \rangle$ is the vertical size (height plus depth) of the box. The updated $\langle box \rangle$ will be an hbox, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. A negative size will cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ will be unchanged. The resizing applies within the current TeX group level.

```
\box_resize_to_wd:Nn  \box_resize_to_wd:Nn <box> {<x-size>}
\box_resize_to_wd:cn
```

Resize the $\langle box \rangle$ to $\langle x-size \rangle$ horizontally, scaling the vertical size by the same amount ($\langle x-size \rangle$ is a dimension expression). The updated $\langle box \rangle$ will be an hbox, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. A negative size will cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ will be unchanged. The resizing applies within the current TeX group level.

```
\box_rotate:Nn <box> {<angle>}
\box_rotate:cn
```

Rotates the $\langle box \rangle$ by $\langle angle \rangle$ (in degrees) anti-clockwise about its reference point. The reference point of the updated box will be moved horizontally such that it is at the left side of the smallest rectangle enclosing the rotated material. The updated $\langle box \rangle$ will be an hbox, irrespective of the nature of the $\langle box \rangle$ before the rotation is applied. The rotation applies within the current TeX group level.

```
\box_scale:Nnn <box> {<x-scale>} {<y-scale>}
\box_scale:cnn
```

Scales the $\langle box \rangle$ by factors $\langle x-scale \rangle$ and $\langle y-scale \rangle$ in the horizontal and vertical directions, respectively (both scales are integer expressions). The updated $\langle box \rangle$ will be an hbox, irrespective of the nature of the $\langle box \rangle$ before the scaling is applied. Negative scalings will cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ will be unchanged. The scaling applies within the current TeX group level.

2.2 Viewing part of a box

```
\box_clip:N <box>
\box_clip:c
```

Clips the $\langle box \rangle$ in the output so that only material inside the bounding box is displayed in the output. The updated $\langle box \rangle$ will be an hbox, irrespective of the nature of the $\langle box \rangle$ before the clipping is applied. The clipping applies within the current TeX group level.

These functions require the L^AT_EX3 native drivers: they will not work with the L^AT_EX 2_& graphics drivers!

TeXhackers note: Clipping is implemented by the driver, and as such the full content of the box is placed in the output file. Thus clipping does not remove any information from the raw output, and hidden material can therefore be viewed by direct examination of the file.

`\box_trim:Nnnnn`
`\box_trim:cnnnn`

`\box_trim:Nnnnn <box> {\<left>} {\<bottom>} {\<right>} {\<top>}`

Adjusts the bounding box of the `<box>` `<left>` is removed from the left-hand edge of the bounding box, `<right>` from the right-hand edge and so fourth. All adjustments are *dimension expressions*. Material output of the bounding box will still be displayed in the output unless `\box_clip:N` is subsequently applied. The updated `<box>` will be an hbox, irrespective of the nature of the `<box>` before the viewport operation is applied. The adjustment applies within the current T_EX group level.

`\box_viewport:Nnnnn`
`\box_viewport:cnnnn`

`\box_viewport:Nnnnn <box> {\<llx>} {\<lly>} {\<urx>} {\<ury>}`

Adjusts the bounding box of the `<box>` such that it has lower-left co-ordinates (`<llx>`, `<lly>`) and upper-right co-ordinates (`<urx>`, `<ury>`). All four co-ordinate positions are *dimension expressions*. Material output of the bounding box will still be displayed in the output unless `\box_clip:N` is subsequently applied. The updated `<box>` will be an hbox, irrespective of the nature of the `<box>` before the viewport operation is applied. The adjustment applies within the current T_EX group level.

2.3 Internal variables

`\l_box_angle_fp`

The angle through which a box is rotated by `\box_rotate:Nn`, given in degrees counter-clockwise. This value is required by the underlying driver code in l3driver to carry out the driver-dependent part of box rotation.

`\l_box_cos_fp`
`\l_box_sin_fp`

The sine and cosine of the angle through which a box is rotated by `\box_rotate:Nn`: the values refer to the angle counter-clockwise. These values are required by the underlying driver code in l3driver to carry out the driver-dependent part of box rotation.

`\l_box_scale_x_fp`
`\l_box_scale_y_fp`

The scaling factors by which a box is scaled by `\box_scale:Nnn` or `\box_resize:Nnn`. These values are required by the underlying driver code in l3driver to carry out the driver-dependent part of box rotation.

`\l_box_internal_box`

Box used for affine transformations, which is used to contain rotated material when applying `\box_rotate:Nn`. This box must be correctly constructed for the driver-dependent code in l3driver to function correctly.

3 Additions to **I3clist**

<code>\clist_item:Nn</code>	<code>\clist_item:Nn <comma list> {<integer expression>}</code>
<code>\clist_item:(cn nn)</code>	Indexing items in the $\langle \text{comma list} \rangle$ from 1 at the top (left), this function will evaluate the $\langle \text{integer expression} \rangle$ and leave the appropriate item from the comma list in the input stream. If the $\langle \text{integer expression} \rangle$ is negative, indexing occurs from the bottom (right) of the comma list. When the $\langle \text{integer expression} \rangle$ is larger than the number of items in the $\langle \text{comma list} \rangle$ (as calculated by <code>\clist_count:N</code>) then the function will expand to nothing.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle \text{item} \rangle$ will not expand further when appearing in an x-type argument expansion.

<code>\clist_set_from_seq:NN</code>	<code>\clist_set_from_seq:NN <comma list> <sequence></code>
<code>\clist_set_from_seq:(cN Nc cc)</code>	
<code>\clist_gset_from_seq:NN</code>	
<code>\clist_gset_from_seq:(cN Nc cc)</code>	

Sets the $\langle \text{comma list} \rangle$ to be equal to the content of the $\langle \text{sequence} \rangle$. Items which contain either spaces or commas are surrounded by braces.

<code>\clist_const:Nn</code>	<code>\clist_const:Nn <clist var> {<comma list>}</code>
<code>\clist_const:(Nx cn cx)</code>	Creates a new constant $\langle \text{clist var} \rangle$ or raises an error if the name is already taken. The value of the $\langle \text{clist var} \rangle$ will be set globally to the $\langle \text{comma list} \rangle$.

<code>\clist_if_empty_p:n *</code>	<code>\clist_if_empty_p:n {<comma list>}</code>
<code>\clist_if_empty:nTF *</code>	<code>\clist_if_empty:nTF {<comma list>} {<true code>} {<false code>}</code>

Tests if the $\langle \text{comma list} \rangle$ is empty (containing no items). The rules for space trimming are as for other n-type comma-list functions, hence the comma list $\{\sim, \sim, \sim\}$ (without outer braces) is empty, while $\{\sim, \{\}, \sim\}$ (without outer braces) contains one element, which happens to be empty: the comma-list is not empty.

\clist_use:Nnnn *

New: 2012-06-26

```
\clist_use:Nnnn <clist var> {<separator between two>}  
  {<separator between more than two>} {<separator between final two>}
```

Places the contents of the *<clist var>* in the input stream, with the appropriate *<separator between more than two>* placed between each pair of items except the last, for which the *<separator between final two>* is used. If the comma list has 2 items, then they are placed in the input stream separated by the *<separator between two>*. If the comma list has 1 item, it is placed in the input stream, and a comma list with no items produces no output. An error will be raised if the variable does not exist or if it is invalid.

For example,

```
\clist_set:Nn \l_tmpa_clist { a , b , , c , {de} , f }  
\clist_use:Nnnn \l_tmpa_clist { ~and~ } { ,~ } { ,~and~ }
```

will insert “a, b, c, de, and f” in the input stream. The first separator argument is not used in this case because the comma list has more than 2 items.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<items>* will not expand further when appearing in an x-type argument expansion.

4 Additions to l3coffins

\coffin_resize:Nnn
\coffin_resize:cnn

```
\coffin_resize:Nnn <coffin> {<width>} {<total-height>}
```

Resized the *<coffin>* to *<width>* and *<total-height>*, both of which should be given as dimension expressions.

\coffin_rotate:Nn
\coffin_rotate:cN

```
\coffin_rotate:Nn <coffin> {<angle>}
```

Rotates the *<coffin>* by the given *<angle>* (given in degrees counter-clockwise). This process will rotate both the coffin content and poles. Multiple rotations will not result in the bounding box of the coffin growing unnecessarily.

\coffin_scale:Nnn
\coffin_scale:cnn

```
\coffin_scale:Nnn <coffin> {<x-scale>} {<y-scale>}
```

Scales the *<coffin>* by a factors *<x-scale>* and *<y-scale>* in the horizontal and vertical directions, respectively. The two scale factors should be given as real numbers.

5 Additions to **I3file**

\ior_map_inline:Nn

New: 2012-02-11

\ior_map_inline:Nn *stream* {*inline function*}

Applies the *inline function* to *lines* obtained by reading one or more lines (until an equal number of left and right braces are found) from the *stream*. The *inline function* should consist of code which will receive the *line* as #1. Note that TeX removes trailing space and tab characters (character codes 32 and 9) from every line upon input. TeX also ignores any trailing new-line marker from the file it reads.

\ior_str_map_inline:Nn

New: 2012-02-11

\ior_str_map_inline:Nn {*stream*} {*inline function*}

Applies the *inline function* to every *line* in the *stream*. The material is read from the *stream* as a series of tokens with category code 12 (other), with the exception of space characters which are given category code 10 (space). The *inline function* should consist of code which will receive the *line* as #1. Note that TeX removes trailing space and tab characters (character codes 32 and 9) from every line upon input. TeX also ignores any trailing new-line marker from the file it reads.

\ior_map_break:

New: 2012-06-29

\ior_map_break:

Used to terminate a \ior_map_... function before all lines from the *stream* have been processed. This will normally take place within a conditional statement, for example

```
\ior_map_inline:Nn \l_my_iор
{
  \str_if_eq:nnTF {#1} {bingo}
    { \ior_map_break:
    {
      % Do something useful
    }
  }
}
```

Use outside of a \ior_map_... scenario will lead to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted by the internal macro __prg_break_point:Nn before further items are taken from the input stream. This will depend on the design of the mapping function.

`\ior_map_break:n`

New: 2012-06-29

`\ior_map_break:n {<tokens>}`

Used to terminate a `\ior_map_...` function before all lines in the `<stream>` have been processed, inserting the `<tokens>` after the mapping has ended. This will normally take place within a conditional statement, for example

```
\ior_map_inline:Nn \l_my_iор
{
  \str_if_eq:nnTF { #1 } { bingo }
    { \ior_map_break:n { <tokens> } }
    {
      % Do something useful
    }
}
```

Use outside of a `\ior_map_...` scenario will lead to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted by the internal macro `__prg_break_point:Nn` before the `<tokens>` are inserted into the input stream. This will depend on the design of the mapping function.

6 Additions to l3fp

`\fp_set_from_dim:Nn`
`\fp_set_from_dim:cn`
`\fp_gset_from_dim:Nn`
`\fp_gset_from_dim:cn`

`\fp_set_from_dim:Nn <floating point variable> {<dimexpr>}`

Sets the `<floating point variable>` to the distance represented by the `<dimension expression>` in the units points. This means that distances given in other units are first converted to points before being assigned to the `<floating point variable>`.

7 Additions to l3prop

`\prop_map_tokens:Nn ☆`
`\prop_map_tokens:cn ☆`

`\prop_map_tokens:Nn <property list> {<code>}`

Analogue of `\prop_map_function:NN` which maps several tokens instead of a single function. The `<code>` receives each key–value pair in the `<property list>` as two trailing brace groups. For instance,

```
\prop_map_tokens:Nn \l_my_prop { \str_if_eq:nnT { mykey } }
```

will expand to the value corresponding to `mykey`: for each pair in `\l_my_prop` the function `\str_if_eq:nnT` receives `mykey`, the `<key>` and the `<value>` as its three arguments. For that specific task, `\prop_get:Nn` is faster.

`\prop_get:Nn` ★ `\prop_get:Nn {property list} {\langle key \rangle}`

Expands to the $\langle value \rangle$ corresponding to the $\langle key \rangle$ in the $\langle property\ list \rangle$. If the $\langle key \rangle$ is missing, this has an empty expansion.

TeXhackers note: This function is slower than the non-expandable analogue `\prop_get:NnN`. The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle value \rangle$ will not expand further when appearing in an x-type argument expansion.

8 Additions to `I3seq`

`\seq_item:Nn` ★ `\seq_item:Nn {sequence} {\langle integer expression \rangle}`
`\seq_item:cn` ★ `\seq_item:cn {sequence} {\langle integer expression \rangle}`

Indexing items in the $\langle sequence \rangle$ from 1 at the top (left), this function will evaluate the $\langle integer\ expression \rangle$ and leave the appropriate item from the sequence in the input stream. If the $\langle integer\ expression \rangle$ is negative, indexing occurs from the bottom (right) of the sequence. When the $\langle integer\ expression \rangle$ is larger than the number of items in the $\langle sequence \rangle$ (as calculated by `\seq_count:N`) then the function will expand to nothing.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ will not expand further when appearing in an x-type argument expansion.

`\seq_mapthread_function:NNN` ★ `\seq_mapthread_function:NNN {seq1} {seq2} {function}`
`\seq_mapthread_function:(NcN|cNN|ccN)` ★ `\seq_mapthread_function:(NcN|cNN|ccN) {seq1} {seq2} {function}`

Applies $\langle function \rangle$ to every pair of items $\langle seq_1-item \rangle - \langle seq_2-item \rangle$ from the two sequences, returning items from both sequences from left to right. The $\langle function \rangle$ will receive two n-type arguments for each iteration. The mapping will terminate when the end of either sequence is reached (*i.e.* whichever sequence has fewer items determines how many iterations occur).

`\seq_set_from_clist:NN` ★ `\seq_set_from_clist:NN {sequence} {comma-list}`
`\seq_set_from_clist:(cN|Nc|cc|Nn|cn)`
`\seq_gset_from_clist:NN`
`\seq_gset_from_clist:(cN|Nc|cc|Nn|cn)`

Sets the $\langle sequence \rangle$ within the current TeX group to be equal to the content of the $\langle comma-list \rangle$.

`\seq_reverse:N` ★ `\seq_reverse:N {sequence}`
`\seq_greverse:N` ★ `\seq_greverse:N {sequence}`

Reverses the order of items in the $\langle sequence \rangle$, and assigns the result to $\langle sequence \rangle$, locally or globally according to the variant chosen.

```
\seq_set_filter:NNn
\seq_gset_filter:NNn
```

```
\seq_set_filter:NNn <sequence1> <sequence2> {<inline boolexpr>}
```

Evaluates the *<inline boolexpr>* for every *<item>* stored within the *<sequence₂>*. The *<inline boolexpr>* will receive the *<item>* as #1. The sequence of all *<items>* for which the *<inline boolexpr>* evaluated to **true** is assigned to *<sequence₁>*.

TeXhackers note: Contrarily to other mapping functions, `\seq_map_break:` cannot be used in this function, and will lead to low-level TeX errors.

```
\seq_set_map:NNn
\seq_gset_map:NNn
```

New: 2011-12-22

```
\seq_set_map:NNn <sequence1> <sequence2> {<inline function>}
```

Applies *<inline function>* to every *<item>* stored within the *<sequence₂>*. The *<inline function>* should consist of code which will receive the *<item>* as #1. The sequence resulting from x-expanding *<inline function>* applied to each *<item>* is assigned to *<sequence₁>*. As such, the code in *<inline function>* should be expandable.

TeXhackers note: Contrarily to other mapping functions, `\seq_map_break:` cannot be used in this function, and will lead to low-level TeX errors.

```
\seq_use:Nnnn *
```

New: 2012-06-26

```
\seq_use:Nnnn <seq var> {<separator between two>}
{<separator between more than two>} {<separator between final two>}
```

Places the contents of the *<seq var>* in the input stream, with the appropriate *<separator>* between the items. Namely, if the sequence has more than 2 items, the *<separator between more than two>* is placed between each pair of items except the last, for which the *<separator between final two>* is used. If the sequence has 2 items, then they are placed in the input stream separated by the *<separator between two>*. If the sequence has 1 item, it is placed in the input stream, and an empty sequence produces no output. An error will be raised if the variable does not exist or if it is invalid.

For example,

```
\seq_set_split:Nnn \l_tmpa_seq { | } { a | b | c | {de} | f }
\seq_use:Nnnn \l_tmpa_seq { ~and~ } { ,~ } { ,~and~ }
```

will insert “a, b, c, de, and f” in the input stream. The first separator argument is not used in this case because the sequence has more than 2 items.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<items>* will not expand further when appearing in an x-type argument expansion.

9 Additions to `\3skip`

```
\skip_split_finite_else_action:nnNN  \skip_split_finite_else_action:nnNN {<skipexpr>} {<action>}
                                         <dimen1> <dimen2>
```

Checks if the `<skipexpr>` contains finite glue. If it does then it assigns `<dimen1>` the stretch component and `<dimen2>` the shrink component. If it contains infinite glue set `<dimen1>` and `<dimen2>` to 0pt and place #2 into the input stream: this is usually an error or warning message of some sort.

10 Additions to `\3tl`

```
\tl_if_single_token_p:n ★      \tl_if_single_token_p:n {<token list>}
\tl_if_single_token:nTF ★       \tl_if_single_token:nTF {<token list>} {<true code>} {<false code>}
```

Tests if the token list consists of exactly one token, *i.e.* is either a single space character or a single “normal” token. Token groups (`{...}`) are not single tokens.

```
\tl_reverse_tokens:n ★          \tl_reverse_tokens:n {<tokens>}
```

This function, which works directly on `\TeX` tokens, reverses the order of the `<tokens>`: the first will be the last and the last will become first. Spaces are preserved. The reversal also operates within brace groups, but the braces themselves are not exchanged, as this would lead to an unbalanced token list. For instance, `\tl_reverse_tokens:n {a~{b()}}` leaves `{()}~{b}~{a}` in the input stream. This function requires two steps of expansion.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the token list will not expand further when appearing in an `x`-type argument expansion.

```
\tl_count_tokens:n ★            \tl_count_tokens:n {<tokens>}
```

Counts the number of `\TeX` tokens in the `<tokens>` and leaves this information in the input stream. Every token, including spaces and braces, contributes one to the total; thus for instance, the token count of `a~{bc}` is 6. This function requires three expansions, giving an `<integer denotation>`.

```
\tl_expandable_uppercase:n * \tl_expandable_uppercase:n {\langle tokens\rangle}
\tl_expandable_lowercase:n * \tl_expandable_lowercase:n {\langle tokens\rangle}
```

The `\tl_expandable_uppercase:n` function works through all of the `\langle tokens\rangle`, replacing characters in the range `a–z` (with arbitrary category code) by the corresponding letter in the range `A–Z`, with category code 11 (letter). Similarly, `\tl_expandable_lowercase:n` replaces characters in the range `A–Z` by letters in the range `a–z`, and leaves other tokens unchanged. This function requires two steps of expansion.

TeXhackers note: Begin-group and end-group characters are normalized and become `{` and `}`, respectively. The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the token list will not expand further when appearing in an x-type argument expansion.

```
\tl_item:nn * \tl_item:nn {\langle token list\rangle} {\langle integer expression\rangle}
\tl_item:(Nn|cn) *
```

Indexing items in the `\langle token list\rangle` from 1 on the left, this function will evaluate the `\langle integer expression\rangle` and leave the appropriate item from the `\langle token list\rangle` in the input stream. If the `\langle integer expression\rangle` is negative, indexing occurs from the right of the token list, starting at `-1` for the right-most item. If the index is out of bounds, then the function expands to nothing.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the `\langle item\rangle` will not expand further when appearing in an x-type argument expansion.

11 Additions to `I3tokens`

```
\char_set_active:Npn
\char_set_active:Npx
```

Makes `\langle char\rangle` an active character to expand to `\langle code\rangle` as replacement text. Within the `\langle code\rangle`, the `\langle parameters\rangle` (`#1, #2, etc.`) will be replaced by those absorbed. The `\langle char\rangle` is made active within the current TeX group level, and the definition is also local.

```
\char_gset_active:Npn
\char_gset_active:Npx
```

Makes `\langle char\rangle` an active character to expand to `\langle code\rangle` as replacement text. Within the `\langle code\rangle`, the `\langle parameters\rangle` (`#1, #2, etc.`) will be replaced by those absorbed. The `\langle char\rangle` is made active within the current TeX group level, but the definition is global. This function is therefore suited to cases where an active character definition should be applied only in some context (where the `\langle char\rangle` is again made active).

```
\char_set_active_eq:NN
```

Makes `\langle char\rangle` an active character equivalent in meaning to the `\langle function\rangle` (which may itself be an active character). The `\langle char\rangle` is made active within the current TeX group level, and the definition is also local.

\char_gset_active_eq:NN

```
\char_gset_active_eq:NN <char> <function>
```

Makes *<char>* an active character equivalent in meaning to the *<function>* (which may itself be an active character). The *<char>* is made active within the current *TEX* group level, but the definition is global. This function is therefore suited to cases where an active character definition should be applied only in some context (where the *<char>* is again made active).

\peek_N_type:TF

```
\peek_N_type:TF {<true code>} {<false code>}
```

Tests if the next *<token>* in the input stream can be safely grabbed as an N-type argument. The test will be *<false>* if the next *<token>* is either an explicit or implicit begin-group or end-group token (with any character code), or an explicit or implicit space character (with character code 32 and category code 10), and *<true>* in all other cases. Note that a *<true>* result ensures that the next *<token>* is a valid N-type argument. However, if the next *<token>* is for instance *\c_space_token*, the test will take the *<false>* branch, even though the next *<token>* is in fact a valid N-type argument. The *<token>* will be left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

Part XXIV

Implementation

1 l3bootstrap implementation

```
1  {*initex | package}
2  <@@=expl>
```

1.1 Format-specific code

The very first thing to do is to bootstrap the iniTEX system so that everything else will actually work. *TEX* does not start with some pretty basic character codes set up.

```
3  {*initex}
4  \catcode '\{ = 1 \relax
5  \catcode '\} = 2 \relax
6  \catcode '\# = 6 \relax
7  \catcode '\^ = 7 \relax
8  </initex>
```

Tab characters should not show up in the code, but to be on the safe side.

```
9  {*initex}
10 \catcode '\^I = 10 \relax
11 </initex>
```

For LuA*TEX* the extra primitives need to be enabled before they can be used. No *\ifdefined* yet, so do it the old-fashioned way. The primitive *\strcmp* is simulated using some Lua code, which currently has to be applied to every job as the Lua code is not

part of the format. Thanks to Taco Hoekwater for this code. The odd `\csname` business is needed so that the later deletion code will work.

```

12  {*initex}
13  \begingroup\expandafter\expandafter\expandafter\endgroup
14  \expandafter\ifx\csname directlua\endcsname\relax
15  \else
16    \directlua
17    {
18      tex.enableprimitives('',tex.extraprimitives ())
19      lua.bytecode[1] = function ()
20        function strcmp (A, B)
21          if A == B then
22            tex.write("0")
23          elseif A < B then
24            tex.write("-1")
25          else
26            tex.write("1")
27          end
28        end
29      end
30      lua.bytecode[1]()
31    }
32  \everyjob\expandafter
33  {\csname\detokenize{luatex_directlua:D}\endcsname{lua.bytecode[1]()}}
34  \long\edef\pdfstrcmp#1#2%
35  {%
36    \expandafter\noexpand\csname\detokenize{luatex_directlua:D}\endcsname
37    #%
38    strcmp%
39    (#%
40      "\noexpand\luaescapestring{\#1}",%
41      "\noexpand\luaescapestring{\#2}"%
42    )%
43  }%
44}
45 \fi
46 
```

1.2 Package-specific code part one

The package starts by identifying itself: the information itself is taken from the SVN Id string at the start of the source file.

```

47  {*package}
48  \ProvidesPackage{l3bootstrap}
49  [%
50    \ExplFileVersion\space v\ExplFileVersion\space
51    L3 Experimental bootstrap code%
52  ]
53 
```

For LuaTeX the functionality of the `\pdfstrcmp` primitive needs to be provided: the `pdftexcmds` package is used to do this if necessary. At present, there is also a need to deal with some low-level allocation stuff that could usefully be added to `lualatex.ini`. As it is currently not, load Heiko Oberdiek's `luatex` package instead.

```

54 <*package>
55 \def\@tempa%
56   {%
57     \def\@tempa{}%
58     \RequirePackage{luatex}%
59     \RequirePackage{pdftexcmds}%
60     \let\pdfstrcmp\pdfstrcmp
61   }
62 \begingroup\expandafter\expandafter\expandafter\endgroup
63 \expandafter\ifx\csname directlua\endcsname\relax
64 \else
65   \expandafter\@tempa
66 \fi
67 </package>
```

1.3 The `\pdfstrcmp` primitive in X_ET_EX

Only pdfTeX has a primitive called `\pdfstrcmp`. The X_ET_EX version is just `\strcmp`, so there is some shuffling to do.

```

68 \begingroup\expandafter\expandafter\expandafter\endgroup
69   \expandafter\ifx\csname pdfstrcmp\endcsname\relax
70   \let\pdfstrcmp\strcmp
71 \fi
```

1.4 Engine requirements

The code currently requires functionality equivalent to `\pdfstrcmp` in addition to ε -TeX. The former is therefore used as a test for a suitable engine.

```

72 \begingroup\expandafter\expandafter\expandafter\endgroup
73 \expandafter\ifx\csname pdfstrcmp\endcsname\relax
74 <*package>
75   \PackageError{expl3}{Required primitives not found}
76   {%
77     LaTeX3 requires the e-TeX primitives and \string\pdfstrcmp.\MessageBreak
78     \MessageBreak
79     These are available in engine versions:\MessageBreak
80     - pdfTeX 1.30\MessageBreak
81     - XeTeX 0.9994\MessageBreak
82     - LuaTeX 0.40\MessageBreak
83     or later.\MessageBreak
84     \MessageBreak
85     Loading of expl3 will abort!%
86   }
87 \expandafter\endinput
```

```

88  </package>
89  {*initex}
90  \newlinechar`^^J\relax
91  \errhelp{%
92      LaTeX3 requires the e-TeX primitives and \pdfstrcmp.^^J%
93      ^^J%
94      These are available in engine versions:^^J%
95      - pdfTeX 1.30^^J%
96      - XeTeX 0.9994^^J%
97      - LuaTeX 0.40^^J%
98      or later.^^J%
99      ^^J%
100     For pdfTeX and XeTeX the '-etex' command-line switch is also
101     needed.^^J%
102     ^^J%
103     Format building will abort!%
104 }
105 \errmessage{Required primitives not found}%
106 \expandafter\end
107 </initex>
108 \fi

```

1.5 Package-specific code part two

\ExplSyntaxOff
\ExplSyntaxOn

Experimental syntax switching is set up here for the package-loading process. These are redefined in expl3 for the package and in l3final for the format.

```

109  {*package}
110 \protected\edef\ExplSyntaxOff
111 {
112     \catcode 9 = \the\catcode 9\relax
113     \catcode 32 = \the\catcode 32\relax
114     \catcode 34 = \the\catcode 34\relax
115     \catcode 38 = \the\catcode 38\relax
116     \catcode 58 = \the\catcode 58\relax
117     \catcode 94 = \the\catcode 94\relax
118     \catcode 95 = \the\catcode 95\relax
119     \catcode 124 = \the\catcode 124\relax
120     \catcode 126 = \the\catcode 126\relax
121     \endlinechar = \the\endlinechar\relax
122     \chardef\csname\detokenize{l_kernel_expl_bool}\endcsname = 0 \relax
123 }
124 \protected\edef\ExplSyntaxOn
125 {
126     \catcode 9 = 9 \relax
127     \catcode 32 = 9 \relax
128     \catcode 34 = 12 \relax
129     \catcode 58 = 11 \relax
130     \catcode 94 = 7 \relax
131     \catcode 95 = 11 \relax

```

```

132     \catcode 124 = 12 \relax
133     \catcode 126 = 10 \relax
134     \endlinechar = 32 \relax
135     \chardef\csname\detokenize{l__kernel_expl_bool}\endcsname = 1 \relax
136   }
137 
```

(End definition for `\ExplSyntaxOff` and `\ExplSyntaxOn`. These functions are documented on page 6.)

`\l__kernel_expl_bool`

The status for experimental code syntax: this is off at present. This code is used by both the package and the format.

```

138 \expandafter\chardef\csname\detokenize{l__kernel_expl_bool}\endcsname = 0 \relax
(End definition for \l__kernel_expl_bool. This variable is documented on page 7.)
```

1.6 Dealing with package-mode meta-data

`\GetIdInfo`

This is implemented right at the start of `13bootstrap.dtx`.

(End definition for `\GetIdInfo`. This function is documented on page 6.)

`\ProvidesExplPackage`

`\ProvidesExplClass`

`\ProvidesExplFile`

For other packages and classes building on this one it is convenient not to need `\ExplSyntaxOn` each time.

```

139  {*package}
140  \protected\def\ProvidesExplPackage
141  {%
142    \@ifpackageloaded{expl3}%
143    {}%
144    {%
145      \PackageError{expl3}%
146      {Cannot load the expl3 modules separately}%
147      {%
148        The expl3 modules cannot be loaded separately; \MessageBreak
149        please \string\usepackage\string{expl3\string} instead.%%
150      }%
151    }%
152  \protected\def\ProvidesExplPackage##1##2##3##4%
153  {%
154    \ProvidesPackage{##1}[##2 v##3 ##4]%
155    \ExplSyntaxOn
156  }%
157  \ProvidesExplPackage
158 }
159 \protected\def\ProvidesExplClass##1##2##3##4%
160 {%
161   \ProvidesClass{##1}[##2 v##3 ##4]%
162   \ExplSyntaxOn
163 }
164 \protected\def\ProvidesExplFile##1##2##3##4%
165 {%
166   \ProvidesFile{##1}[##2 v##3 ##4]%
167   \ExplSyntaxOn

```

```

168    }
169  </package>

```

(End definition for \ProvidesExplPackage , \ProvidesExplClass , and \ProvidesExplFile These functions are documented on page 6.)

\@pushfilename The idea here is to use L^AT_EX 2 _{ε} 's \@pushfilename and \@popfilename to track the current syntax status. This can be achieved by saving the current status flag at each push to a stack, then recovering it at the pop stage and checking if the code environment should still be active.

```

170  {*package}
171  \edef\@pushfilename
172  {%
173   \edef\expandafter\noexpand
174   \csname\detokenize{l__expl_status_stack_t1}\endcsname
175   {%
176     \noexpand\ifodd\expandafter\noexpand
177     \csname\detokenize{l__kernel_expl_bool}\endcsname
178     1%
179   \noexpand\else
180     0%
181   \noexpand\fi
182   \expandafter\noexpand
183   \csname\detokenize{l__expl_status_stack_t1}\endcsname
184   }%
185   \ExplSyntaxOff
186   \unexpanded\expandafter{\@pushfilename}%
187 }
188 \edef\@popfilename
189 {%
190   \unexpanded\expandafter{\@popfilename}%
191   \noexpand\if a\expandafter\noexpand\csname
192   \detokenize{l__expl_status_stack_t1}\endcsname a%
193   \ExplSyntaxOff
194   \noexpand\else
195   \noexpand\expandafter
196   \expandafter\noexpand\csname
197   \detokenize{_\_expl_status_pop:w}\endcsname
198   \expandafter\noexpand\csname
199   \detokenize{l__expl_status_stack_t1}\endcsname
200   \noexpand@nil
201   \noexpand\fi
202 }
203 </package>

```

(End definition for \@pushfilename and \@popfilename These functions are documented on page ??.)

\l__expl_status_stack_t1 As expl3 itself cannot be loaded with the code environment already active, at the end of the package \ExplSyntaxOff can safely be called.

```

204  {*package}
205  \namedef{\detokenize{l__expl_status_stack_t1}}{0}

```

```

206  </package>
(End definition for \l_ expl_status_stack_t1 This function is documented on page ??.)
```

\l_ expl_status_pop:w The pop auxiliary function removes the first item from the stack, saves the rest of the stack and then does the test. As \ExplSyntaxOff is already defined as a protected macro, there is no need for \noexpand here.

```

207  {*package}
208  \expandafter\edef\csname\detokenize{\l_ expl_status_pop:w}\endcsname#1#2\@nil
209  {%
210   \def\expandafter\noexpand
211   {\csname\detokenize{l_ expl_status_stack_t1}\endcsname{\#2}%
212   \noexpand\ifodd#1\space
213   \noexpand\expandafter\noexpand\ExplSyntaxOn
214   \noexpand\else
215   \noexpand\expandafter\ExplSyntaxOff
216   \noexpand\fi
217 }
218 </package>
(End definition for \l_ expl_status_pop:w)
```

\l_ expl_package_check: We want the expl3 bundle to be loaded “as one”; this command is used to ensure that one of the 13 packages isn’t loaded on its own.

```

219  {*package}
220  \expandafter\protected\expandafter\def
221  {\csname\detokenize{\l_ expl_package_check:}\endcsname
222  {%
223   \@ifpackageloaded{expl3}
224   {}
225   {%
226   \PackageError{expl3}
227   {Cannot load the expl3 modules separately}
228   {%
229   The expl3 modules cannot be loaded separately; \MessageBreak
230   please \string\usepackage\string{expl3\string} instead.%
231   }%
232   }%
233 }
234 </package>
(End definition for \l_ expl_package_check:)
```

1.7 The L^AT_EX3 code environment

The code environment is now set up for the format: the package deals with this using \ProvidesExplPackage.

```

235  {*initex}
236  \catcode 9 = 9 \relax
237  \catcode 32 = 9 \relax
238  \catcode 34 = 12 \relax
```

```

239 \catcode 58 = 11 \relax
240 \catcode 94 = 7 \relax
241 \catcode 95 = 11 \relax
242 \catcode 124 = 12 \relax
243 \catcode 126 = 10 \relax
244 \endlinechar = 32 \relax
245 
```

\ExplSyntaxOn
\ExplSyntaxOff The idea here is that multiple `\ExplSyntaxOn` calls are not going to mess up category codes, and that multiple calls to `\ExplSyntaxOff` are also not wasting time.

```

246 
```

`*initex`

```

247 \protected \def \ExplSyntaxOn
248 {
249   \bool_if:NF \l_kernel_expl_bool
250   {
251     \cs_set_protected_nopar:Npx \ExplSyntaxOff
252     {
253       \char_set_catcode:nn { 9 } { \char_value_catcode:n { 9 } }
254       \char_set_catcode:nn { 32 } { \char_value_catcode:n { 32 } }
255       \char_set_catcode:nn { 34 } { \char_value_catcode:n { 34 } }
256       \char_set_catcode:nn { 38 } { \char_value_catcode:n { 38 } }
257       \char_set_catcode:nn { 58 } { \char_value_catcode:n { 58 } }
258       \char_set_catcode:nn { 94 } { \char_value_catcode:n { 94 } }
259       \char_set_catcode:nn { 95 } { \char_value_catcode:n { 95 } }
260       \char_set_catcode:nn { 124 } { \char_value_catcode:n { 124 } }
261       \char_set_catcode:nn { 126 } { \char_value_catcode:n { 126 } }
262       \tex_endlinechar:D =
263         \tex_the:D \tex_endlinechar:D \scan_stop:
264       \bool_set_false:N \l_kernel_expl_bool
265       \cs_set_protected_nopar:Npn \ExplSyntaxOff { }
266     }
267   }
268   \char_set_catcode_ignore:n { 9 } % tab
269   \char_set_catcode_ignore:n { 32 } % space
270   \char_set_catcode_other:n { 34 } % double quote
271   \char_set_catcode_alignment:n { 38 } % ampersand
272   \char_set_catcode_letter:n { 58 } % colon
273   \char_set_catcode_math_superscript:n { 94 } % circumflex
274   \char_set_catcode_letter:n { 95 } % underscore
275   \char_set_catcode_other:n { 124 } % pipe
276   \char_set_catcode_space:n { 126 } % tilde
277   \tex_endlinechar:D = 32 \scan_stop:
278   \bool_set_true:N \l_kernel_expl_bool
279 }
280 \protected \def \ExplSyntaxOff { }
281 
```

(End definition for `\ExplSyntaxOn` and `\ExplSyntaxOff`. These functions are documented on page 6.)

\l_kernel_expl_bool A flag to show the current syntax status.

```

282  {*initex}
283  \chardef \l_kernel_expl_bool = 0 ~
284  
```

(End definition for `\l_kernel_expl_bool`. This variable is documented on page 7.)

1.8 Deprecated functions

Deprecated 2012-06-19 for removal after 2012-12-31.

`\ExplSyntaxNamesOn` These can be set up early, as they are not used anywhere in the package or format itself.
`\ExplSyntaxNamesOff` Using an `\edef` here makes the definitions that bit clearer later.

```

285  \protected\edef\ExplSyntaxNamesOn
286  {%
287  \expandafter\noexpand
288  \csname\detokenize{char_set_catcode_letter:n}\endcsname{58}%
289  \expandafter\noexpand
290  \csname\detokenize{char_set_catcode_letter:n}\endcsname{95}%
291  }
292  \protected\edef\ExplSyntaxNamesOff
293  {%
294  \expandafter\noexpand
295  \csname\detokenize{char_set_catcode_other:n}\endcsname{58}%
296  \expandafter\noexpand
297  \csname\detokenize{char_set_catcode_math_subscript:n}\endcsname{95}%
298  }

(End definition for \ExplSyntaxNamesOn and \ExplSyntaxNamesOff. These functions are documented on
page ??.)
```

299

2 l3names implementation

```

300  {*initex | package}
301  (*package)
302  \ProvidesExplPackage
303  {\ExplFileName}{\ExplFileVersion}{\ExplFileDescription}
304  
```

The code here simply renames all of the primitives to new, internal, names. In format mode, it also deletes all of the existing names (although some do come back later).

`\tex_undefined:D` This function does not exist at all, but is the name used by the plain T_EX format for an undefined function. So it should be marked here as “taken”.

(End definition for `\tex_undefined:D`. This function is documented on page ??.)

The `\let` primitive is renamed by hand first as it is essential for the entire process to follow. This also uses `\global`, as that way we avoid leaving an unneeded csname in the hash table.

```

305  \let \tex_global:D \global
306  \let \tex_let:D     \let
```

Everything is inside a (rather long) group, which keeps `__expl_primitive:NN` trapped.

```
307 \begingroup
```

`__expl_primitive:NN` A temporary function to actually do the renaming. This also allows the original names to be removed in format mode.

```
308 \long \def \__expl_primitive:NN #1#2
309 {
310   \tex_global:D \tex_let:D #2 #1
311   {*initex}
312   \tex_global:D \tex_let:D #1 \tex_undefined:D
313   {/initex}
314 }
```

(End definition for `__expl_primitive:NN`)

In the current incarnation of this package, all TeX primitives are given a new name of the form `\tex_<oldname>:D`. But first three special cases which have symbolic original names. These are given modified new names, so that they may be entered without catcode tricks.

315	<code>__expl_primitive:NN \</code>	<code>\tex_space:D</code>
316	<code>__expl_primitive:NN \v</code>	<code>\tex_italiccorrection:D</code>
317	<code>__expl_primitive:NN \-</code>	<code>\tex_hyphen:D</code>

Now all the other primitives.

318	<code>__expl_primitive:NN \let</code>	<code>\tex_let:D</code>
319	<code>__expl_primitive:NN \def</code>	<code>\tex_def:D</code>
320	<code>__expl_primitive:NN \edef</code>	<code>\tex_edef:D</code>
321	<code>__expl_primitive:NN \gdef</code>	<code>\tex_gdef:D</code>
322	<code>__expl_primitive:NN \xdef</code>	<code>\tex_xdef:D</code>
323	<code>__expl_primitive:NN \chardef</code>	<code>\tex_chardef:D</code>
324	<code>__expl_primitive:NN \countdef</code>	<code>\tex_countdef:D</code>
325	<code>__expl_primitive:NN \dimendef</code>	<code>\tex_dimendef:D</code>
326	<code>__expl_primitive:NN \skipdef</code>	<code>\tex_skipdef:D</code>
327	<code>__expl_primitive:NN \muskipdef</code>	<code>\tex_muskipdef:D</code>
328	<code>__expl_primitive:NN \mathchardef</code>	<code>\tex_mathchardef:D</code>
329	<code>__expl_primitive:NN \toksdef</code>	<code>\tex_toksdef:D</code>
330	<code>__expl_primitive:NN \futurelet</code>	<code>\tex_futurelet:D</code>
331	<code>__expl_primitive:NN \advance</code>	<code>\tex_advance:D</code>
332	<code>__expl_primitive:NN \divide</code>	<code>\tex_divide:D</code>
333	<code>__expl_primitive:NN \multiply</code>	<code>\tex_multiply:D</code>
334	<code>__expl_primitive:NN \font</code>	<code>\tex_font:D</code>
335	<code>__expl_primitive:NN \fam</code>	<code>\tex_fam:D</code>
336	<code>__expl_primitive:NN \global</code>	<code>\tex_global:D</code>
337	<code>__expl_primitive:NN \long</code>	<code>\tex_long:D</code>
338	<code>__expl_primitive:NN \outer</code>	<code>\tex_outer:D</code>
339	<code>__expl_primitive:NN \setlanguage</code>	<code>\tex_setlanguage:D</code>
340	<code>__expl_primitive:NN \globaldefs</code>	<code>\tex_globaldefs:D</code>
341	<code>__expl_primitive:NN \afterassignment</code>	<code>\tex_afterassignment:D</code>
342	<code>__expl_primitive:NN \aftergroup</code>	<code>\tex_aftergroup:D</code>
343	<code>__expl_primitive:NN \expandafter</code>	<code>\tex_expandafter:D</code>

```

344  \_\_expl_primitive:NN \noexpand           \tex_noexpand:D
345  \_\_expl_primitive:NN \begingroup         \tex_begingroup:D
346  \_\_expl_primitive:NN \endgroup          \tex_endgroup:D
347  \_\_expl_primitive:NN \halign             \tex_halign:D
348  \_\_expl_primitive:NN \valign            \tex_valign:D
349  \_\_expl_primitive:NN \cr                \tex_cr:D
350  \_\_expl_primitive:NN \crcr              \tex_crcr:D
351  \_\_expl_primitive:NN \noalign            \tex_noalign:D
352  \_\_expl_primitive:NN \omit               \tex OMIT:D
353  \_\_expl_primitive:NN \span               \tex span:D
354  \_\_expl_primitive:NN \tabskip            \tex tabskip:D
355  \_\_expl_primitive:NN \everycr            \tex everycr:D
356  \_\_expl_primitive:NN \if                 \tex_if:D
357  \_\_expl_primitive:NN \ifcase             \tex_ifcase:D
358  \_\_expl_primitive:NN \ifcat              \tex_ifcat:D
359  \_\_expl_primitive:NN \ifnum              \tex_ifnum:D
360  \_\_expl_primitive:NN \ifodd              \tex_ifodd:D
361  \_\_expl_primitive:NN \ifdim              \tex_ifdim:D
362  \_\_expl_primitive:NN \ifeof              \tex_ifeof:D
363  \_\_expl_primitive:NN \ifhbox             \tex_ifhbox:D
364  \_\_expl_primitive:NN \ifvbox             \tex_ifvbox:D
365  \_\_expl_primitive:NN \ifvoid             \tex_ifvoid:D
366  \_\_expl_primitive:NN \ifx                \tex_ifx:D
367  \_\_expl_primitive:NN \iffalse            \tex_iffalse:D
368  \_\_expl_primitive:NN \iftrue             \tex_iftrue:D
369  \_\_expl_primitive:NN \ifhmode            \tex_ifhmode:D
370  \_\_expl_primitive:NN \ifmmode            \tex_ifmmode:D
371  \_\_expl_primitive:NN \ifvmode            \tex_ifvmode:D
372  \_\_expl_primitive:NN \ifinner            \tex_ifinner:D
373  \_\_expl_primitive:NN \else               \tex_else:D
374  \_\_expl_primitive:NN \fi                 \tex_fi:D
375  \_\_expl_primitive:NN \or                \tex_or:D
376  \_\_expl_primitive:NN \immediate          \tex_immediate:D
377  \_\_expl_primitive:NN \closeout           \tex_closeout:D
378  \_\_expl_primitive:NN \openin             \tex_openin:D
379  \_\_expl_primitive:NN \openout            \tex_openout:D
380  \_\_expl_primitive:NN \read               \tex_read:D
381  \_\_expl_primitive:NN \write              \tex_write:D
382  \_\_expl_primitive:NN \closein            \tex_closein:D
383  \_\_expl_primitive:NN \newlinechar        \tex_newlinechar:D
384  \_\_expl_primitive:NN \input               \tex_input:D
385  \_\_expl_primitive:NN \endinput            \tex_endinput:D
386  \_\_expl_primitive:NN \inputlineno        \tex_inputlineno:D
387  \_\_expl_primitive:NN \errmessage         \tex_errmessage:D
388  \_\_expl_primitive:NN \message            \tex_message:D
389  \_\_expl_primitive:NN \show               \tex_show:D
390  \_\_expl_primitive:NN \showthe            \tex_showthe:D
391  \_\_expl_primitive:NN \showbox            \tex_showbox:D
392  \_\_expl_primitive:NN \showlists          \tex_showlists:D
393  \_\_expl_primitive:NN \errhelp            \tex_errhelp:D

```

```

394  \__expl_primitive:NN \errorcontextlines      \tex_errorcontextlines:D
395  \__expl_primitive:NN \tracingcommands       \tex_tracingcommands:D
396  \__expl_primitive:NN \tracinglostchars     \tex_tracinglostchars:D
397  \__expl_primitive:NN \tracingmacros        \tex_tracingmacros:D
398  \__expl_primitive:NN \tracingonline         \tex_tracingonline:D
399  \__expl_primitive:NN \tracingoutput        \tex_tracingoutput:D
400  \__expl_primitive:NN \tracingpages         \tex_tracingpages:D
401  \__expl_primitive:NN \tracingparagraphs    \tex_tracingparagraphs:D
402  \__expl_primitive:NN \tracingrestores      \tex_tracingrestores:D
403  \__expl_primitive:NN \tracingstats         \tex_tracingstats:D
404  \__expl_primitive:NN \pausing              \tex_pausing:D
405  \__expl_primitive:NN \showboxbreadth      \tex_showboxbreadth:D
406  \__expl_primitive:NN \showboxdepth         \tex_showboxdepth:D
407  \__expl_primitive:NN \batchmode            \tex_batchmode:D
408  \__expl_primitive:NN \errorstopmode       \tex_errorstopmode:D
409  \__expl_primitive:NN \nonstopmode         \tex_nonstopmode:D
410  \__expl_primitive:NN \scrollmode          \tex_scrollmode:D
411  \__expl_primitive:NN \end                 \tex_end:D
412  \__expl_primitive:NN \csname              \tex_csname:D
413  \__expl_primitive:NN \endcsname           \tex_endcsname:D
414  \__expl_primitive:NN \ignorespaces        \tex_ignorespaces:D
415  \__expl_primitive:NN \relax               \tex_relax:D
416  \__expl_primitive:NN \the                 \tex_the:D
417  \__expl_primitive:NN \mag                 \tex_mag:D
418  \__expl_primitive:NN \language            \tex_language:D
419  \__expl_primitive:NN \mark                \tex_mark:D
420  \__expl_primitive:NN \topmark             \tex_topmark:D
421  \__expl_primitive:NN \firstmark           \tex_firstmark:D
422  \__expl_primitive:NN \botmark             \tex_botmark:D
423  \__expl_primitive:NN \splitfirstmark     \tex_splitfirstmark:D
424  \__expl_primitive:NN \splitbotmark        \tex_splitbotmark:D
425  \__expl_primitive:NN \fontname            \tex_fontname:D
426  \__expl_primitive:NN \escapechar          \tex_escapechar:D
427  \__expl_primitive:NN \endlinechar         \tex_endlinechar:D
428  \__expl_primitive:NN \mathchoice          \tex_mathchoice:D
429  \__expl_primitive:NN \delimiter           \tex_delimiter:D
430  \__expl_primitive:NN \mathaccent          \tex_mathaccent:D
431  \__expl_primitive:NN \mathchar             \tex_mathchar:D
432  \__expl_primitive:NN \mskip               \tex_mskip:D
433  \__expl_primitive:NN \radical              \tex_radical:D
434  \__expl_primitive:NN \vcenter              \tex_vcenter:D
435  \__expl_primitive:NN \mkern               \tex_mkern:D
436  \__expl_primitive:NN \above                \tex_above:D
437  \__expl_primitive:NN \abovewithdelims    \tex_abovewithdelims:D
438  \__expl_primitive:NN \atop                \tex_atop:D
439  \__expl_primitive:NN \atopwithdelims     \tex_atopwithdelims:D
440  \__expl_primitive:NN \over                \tex_over:D
441  \__expl_primitive:NN \overwithdelims      \tex_overwithdelims:D
442  \__expl_primitive:NN \displaystyle        \tex_displaystyle:D
443  \__expl_primitive:NN \textstyle            \tex_textstyle:D

```

```

444  \__expl_primitive:NN \scriptstyle           \tex_scriptstyle:D
445  \__expl_primitive:NN \scriptscriptstyle     \tex_scriptscriptstyle:D
446  \__expl_primitive:NN \nonscript          \tex_nonscript:D
447  \__expl_primitive:NN \eqno               \tex_eqno:D
448  \__expl_primitive:NN \leqno              \tex_leqno:D
449  \__expl_primitive:NN \abovedisplayshortskip \tex_abovedisplayshortskip:D
450  \__expl_primitive:NN \abovedisplayskip    \tex_abovedisplayskip:D
451  \__expl_primitive:NN \belowdisplayshortskip \tex_belowdisplayshortskip:D
452  \__expl_primitive:NN \belowdisplayskip   \tex_belowdisplayskip:D
453  \__expl_primitive:NN \displaywidowpenalty \tex_displaywidowpenalty:D
454  \__expl_primitive:NN \displayindent       \tex_displayindent:D
455  \__expl_primitive:NN \displaywidth        \tex_displaywidth:D
456  \__expl_primitive:NN \everydisplay       \tex_everydisplay:D
457  \__expl_primitive:NN \predisplaysize     \tex_predisplaysize:D
458  \__expl_primitive:NN \predisplaypenalty   \tex_predisplaypenalty:D
459  \__expl_primitive:NN \postdisplaypenalty  \tex_postdisplaypenalty:D
460  \__expl_primitive:NN \mathbin             \tex_mathbin:D
461  \__expl_primitive:NN \mathclose          \tex_mathclose:D
462  \__expl_primitive:NN \mathinner          \tex_mathinner:D
463  \__expl_primitive:NN \mathop              \tex_mathop:D
464  \__expl_primitive:NN \displaylimits      \tex_displaylimits:D
465  \__expl_primitive:NN \limits              \tex_limits:D
466  \__expl_primitive:NN \nolimits            \tex_nolimits:D
467  \__expl_primitive:NN \mathopen            \tex_mathopen:D
468  \__expl_primitive:NN \mathord             \tex_mathord:D
469  \__expl_primitive:NN \mathpunct          \tex_mathpunct:D
470  \__expl_primitive:NN \mathrel             \tex_mathrel:D
471  \__expl_primitive:NN \overline           \tex_overline:D
472  \__expl_primitive:NN \underline          \tex_underline:D
473  \__expl_primitive:NN \left               \tex_left:D
474  \__expl_primitive:NN \right              \tex_right:D
475  \__expl_primitive:NN \binoppenalty      \tex_binoppenalty:D
476  \__expl_primitive:NN \relpenalty         \tex_relpenalty:D
477  \__expl_primitive:NN \delimitershortfall \tex_delimitershortfall:D
478  \__expl_primitive:NN \delimiterfactor    \tex_delimiterfactor:D
479  \__expl_primitive:NN \nulldelimiterspace \tex_nulldelimiterspace:D
480  \__expl_primitive:NN \everymath          \tex_everymath:D
481  \__expl_primitive:NN \mathsurround       \tex_mathsurround:D
482  \__expl_primitive:NN \medmuskip         \tex_medmuskip:D
483  \__expl_primitive:NN \thinmuskip        \tex_thinmuskip:D
484  \__expl_primitive:NN \thickmuskip       \tex_thickmuskip:D
485  \__expl_primitive:NN \scriptspace       \tex_scriptspace:D
486  \__expl_primitive:NN \noboundary        \tex_noboundary:D
487  \__expl_primitive:NN \accent            \tex_accent:D
488  \__expl_primitive:NN \char               \tex_char:D
489  \__expl_primitive:NN \discretionary     \tex_discretionary:D
490  \__expl_primitive:NN \hfil               \tex_hfil:D
491  \__expl_primitive:NN \hfilneg           \tex_hfilneg:D
492  \__expl_primitive:NN \hfill              \tex_hfill:D
493  \__expl_primitive:NN \hskip              \tex_hskip:D

```

```

494  \__expl_primitive:NN \hss          \tex_hss:D
495  \__expl_primitive:NN \vfil          \tex_vfil:D
496  \__expl_primitive:NN \vfilneg       \tex_vfilneg:D
497  \__expl_primitive:NN \vfill         \tex_vfill:D
498  \__expl_primitive:NN \vskip         \tex_vskip:D
499  \__expl_primitive:NN \vss          \tex_vss:D
500  \__expl_primitive:NN \unskip        \tex_unskip:D
501  \__expl_primitive:NN \kern          \tex_kern:D
502  \__expl_primitive:NN \unkern        \tex_unkern:D
503  \__expl_primitive:NN \hrule         \tex_hrule:D
504  \__expl_primitive:NN \vrule          \tex_vrule:D
505  \__expl_primitive:NN \leaders        \tex_leaders:D
506  \__expl_primitive:NN \cleaders      \tex_cleaders:D
507  \__expl_primitive:NN \xleaders       \tex_xleaders:D
508  \__expl_primitive:NN \lastkern       \tex_lastkern:D
509  \__expl_primitive:NN \lastskip        \tex_lastskip:D
510  \__expl_primitive:NN \indent         \tex_indent:D
511  \__expl_primitive:NN \par           \tex_par:D
512  \__expl_primitive:NN \noindent       \tex_noindent:D
513  \__expl_primitive:NN \vadjust        \tex_vadjust:D
514  \__expl_primitive:NN \baselineskip   \tex_baselineskip:D
515  \__expl_primitive:NN \lineskip        \tex_lineskip:D
516  \__expl_primitive:NN \lineskiplimit  \tex_lineskiplimit:D
517  \__expl_primitive:NN \clubpenalty     \tex_clubpenalty:D
518  \__expl_primitive:NN \widowpenalty    \tex_widowpenalty:D
519  \__expl_primitive:NN \exhyphenpenalty \tex_exhyphenpenalty:D
520  \__expl_primitive:NN \hyphenpenalty    \tex_hyphenpenalty:D
521  \__expl_primitive:NN \linepenalty      \tex_linepenalty:D
522  \__expl_primitive:NN \doublehyphendemerits \tex_doublehyphendemerits:D
523  \__expl_primitive:NN \finalhyphendemerits \tex_finalhyphendemerits:D
524  \__expl_primitive:NN \adjdemerits     \tex_adjdemerits:D
525  \__expl_primitive:NN \hangafter        \tex_hangafter:D
526  \__expl_primitive:NN \hangindent       \tex_hangindent:D
527  \__expl_primitive:NN \parshape         \tex_parshape:D
528  \__expl_primitive:NN \hspace          \tex_hsize:D
529  \__expl_primitive:NN \lefthyphenmin   \tex_lefthyphenmin:D
530  \__expl_primitive:NN \righthyphenmin  \tex_righthyphenmin:D
531  \__expl_primitive:NN \leftskip         \tex_leftskip:D
532  \__expl_primitive:NN \rightskip        \tex_rightskip:D
533  \__expl_primitive:NN \looseness        \tex_looseness:D
534  \__expl_primitive:NN \parskip          \tex_parskip:D
535  \__expl_primitive:NN \parindent        \tex_parindent:D
536  \__expl_primitive:NN \uchyph          \tex_uchyph:D
537  \__expl_primitive:NN \emergencystretch \tex_emergencystretch:D
538  \__expl_primitive:NN \pretolerance     \tex_pretolerance:D
539  \__expl_primitive:NN \tolerance        \tex_tolerance:D
540  \__expl_primitive:NN \spaceskip        \tex_spaceskip:D
541  \__expl_primitive:NN \xspaceskip      \tex_xspaceskip:D
542  \__expl_primitive:NN \parfillskip      \tex_parfillskip:D
543  \__expl_primitive:NN \everypar         \tex_everypar:D

```

```

544  \__expl_primitive:NN \prevgraf          \tex_prevgraf:D
545  \__expl_primitive:NN \spacefactor       \tex_spacefactor:D
546  \__expl_primitive:NN \shipout          \tex_shipout:D
547  \__expl_primitive:NN \vsize            \tex_vsize:D
548  \__expl_primitive:NN \interlinepenalty   \tex_interlinepenalty:D
549  \__expl_primitive:NN \brokenpenalty     \tex_brokenpenalty:D
550  \__expl_primitive:NN \topskip           \tex_topskip:D
551  \__expl_primitive:NN \maxdeadcycles    \tex_maxdeadcycles:D
552  \__expl_primitive:NN \maxdepth          \tex_maxdepth:D
553  \__expl_primitive:NN \output            \tex_output:D
554  \__expl_primitive:NN \deadcycles        \tex_deadcycles:D
555  \__expl_primitive:NN \pagedepth          \tex_pagedepth:D
556  \__expl_primitive:NN \pagestretch        \tex_pagestretch:D
557  \__expl_primitive:NN \pagefilstretch     \tex_pagefilstretch:D
558  \__expl_primitive:NN \pagefillstretch     \tex_pagefillstretch:D
559  \__expl_primitive:NN \pagefullstretch    \tex_pagefullstretch:D
560  \__expl_primitive:NN \pageshrink         \tex_pageshrink:D
561  \__expl_primitive:NN \pagegoal           \tex_pagegoal:D
562  \__expl_primitive:NN \pagetotal          \tex_pagetotal:D
563  \__expl_primitive:NN \outputpenalty      \tex_outputpenalty:D
564  \__expl_primitive:NN \hoffset             \tex_hoffset:D
565  \__expl_primitive:NN \voffset             \tex_voffset:D
566  \__expl_primitive:NN \insert              \tex_insert:D
567  \__expl_primitive:NN \holdinginserts     \tex_holdinginserts:D
568  \__expl_primitive:NN \floatingpenalty     \tex_floatingpenalty:D
569  \__expl_primitive:NN \insertpenalties     \tex_insertpenalties:D
570  \__expl_primitive:NN \lower               \tex_lower:D
571  \__expl_primitive:NN \moveleft           \tex_moveleft:D
572  \__expl_primitive:NN \moveright          \tex_moveright:D
573  \__expl_primitive:NN \raise               \tex_raise:D
574  \__expl_primitive:NN \copy                \tex_copy:D
575  \__expl_primitive:NN \lastbox             \tex_lastbox:D
576  \__expl_primitive:NN \vsplit              \tex_vsplit:D
577  \__expl_primitive:NN \unhbox              \tex_unhbox:D
578  \__expl_primitive:NN \unhcopystretch     \tex_unhcopystretch:D
579  \__expl_primitive:NN \unvbox              \tex_unvbox:D
580  \__expl_primitive:NN \unvcopystretch     \tex_unvcopystretch:D
581  \__expl_primitive:NN \setbox              \tex_setbox:D
582  \__expl_primitive:NN \hbox                \tex_hbox:D
583  \__expl_primitive:NN \vbox                \tex_vbox:D
584  \__expl_primitive:NN \vtop                \tex_vtop:D
585  \__expl_primitive:NN \prevdepth          \tex_prevdepth:D
586  \__expl_primitive:NN \badness             \tex_badness:D
587  \__expl_primitive:NN \hbadness            \tex_hbadness:D
588  \__expl_primitive:NN \vbadness            \tex_vbadness:D
589  \__expl_primitive:NN \hfuzz               \tex_hfuzz:D
590  \__expl_primitive:NN \vfuzz               \tex_vfuzz:D
591  \__expl_primitive:NN \overfullrule       \tex_overfullrule:D
592  \__expl_primitive:NN \boxmaxdepth        \tex_boxmaxdepth:D
593  \__expl_primitive:NN \splitmaxdepth      \tex_splitmaxdepth:D

```

```

594  \__expl_primitive:NN \splittopskip          \tex_splittopskip:D
595  \__expl_primitive:NN \everyhbox              \tex_everyhbox:D
596  \__expl_primitive:NN \everyvbox              \tex_everyvbox:D
597  \__expl_primitive:NN \nullfont              \tex_nullfont:D
598  \__expl_primitive:NN \textfont              \tex_textfont:D
599  \__expl_primitive:NN \scriptfont            \tex_scriptfont:D
600  \__expl_primitive:NN \scriptscriptfont      \tex_scriptscriptfont:D
601  \__expl_primitive:NN \fontdimen             \tex_fontdimen:D
602  \__expl_primitive:NN \hyphenchar            \tex_hyphenchar:D
603  \__expl_primitive:NN \skewchar              \tex_skewchar:D
604  \__expl_primitive:NN \defaulthyphenchar     \tex_defaulthyphenchar:D
605  \__expl_primitive:NN \defaultskewchar       \tex_defaultskewchar:D
606  \__expl_primitive:NN \number                \tex_number:D
607  \__expl_primitive:NN \romannumeral          \tex_roman numeral:D
608  \__expl_primitive:NN \string                \tex_string:D
609  \__expl_primitive:NN \lowercase             \tex_lowercase:D
610  \__expl_primitive:NN \uppercase             \tex_uppercase:D
611  \__expl_primitive:NN \meaning               \tex_meaning:D
612  \__expl_primitive:NN \penalty               \tex_penalty:D
613  \__expl_primitive:NN \unpenalty             \tex_unpenalty:D
614  \__expl_primitive:NN \lastpenalty           \tex_lastpenalty:D
615  \__expl_primitive:NN \special               \tex_special:D
616  \__expl_primitive:NN \dump                  \tex_dump:D
617  \__expl_primitive:NN \patterns              \tex_patterns:D
618  \__expl_primitive:NN \hyphenation           \tex_hyphenation:D
619  \__expl_primitive:NN \time                 \tex_time:D
620  \__expl_primitive:NN \day                  \tex_day:D
621  \__expl_primitive:NN \month                \tex_month:D
622  \__expl_primitive:NN \year                 \tex_year:D
623  \__expl_primitive:NN \jobname              \tex_jobname:D
624  \__expl_primitive:NN \everyjob              \tex_everyjob:D
625  \__expl_primitive:NN \count                \tex_count:D
626  \__expl_primitive:NN \dimen                \tex_dimen:D
627  \__expl_primitive:NN \skip                 \tex_skip:D
628  \__expl_primitive:NN \toks                 \tex_toks:D
629  \__expl_primitive:NN \muskip               \tex_muskip:D
630  \__expl_primitive:NN \box                  \tex_box:D
631  \__expl_primitive:NN \wd                   \tex_wd:D
632  \__expl_primitive:NN \ht                   \tex_ht:D
633  \__expl_primitive:NN \dp                   \tex_dp:D
634  \__expl_primitive:NN \catcode              \tex_catcode:D
635  \__expl_primitive:NN \delcode              \tex_delcode:D
636  \__expl_primitive:NN \sfcode               \tex_sfcode:D
637  \__expl_primitive:NN \lccode               \tex_lccode:D
638  \__expl_primitive:NN \uccode               \tex_uccode:D
639  \__expl_primitive:NN \mathcode              \tex_mathcode:D

```

Since L^AT_EX3 requires at least the ε -T_EX extensions, we also rename the additional primitives. These are all given the prefix `\etex_`.

640 __expl_primitive:NN \ifdefined	\etex_ifdefined:D
--	-------------------

```

641  \__expl_primitive:NN \ifcsname          \etex_ifcsname:D
642  \__expl_primitive:NN \unless           \etex_unless:D
643  \__expl_primitive:NN \eTeXversion      \etex_eTeXversion:D
644  \__expl_primitive:NN \eTeXrevision     \etex_eTeXrevision:D
645  \__expl_primitive:NN \marks            \etex_marks:D
646  \__expl_primitive:NN \topmarks         \etex_topmarks:D
647  \__expl_primitive:NN \firstmarks       \etex_firstmarks:D
648  \__expl_primitive:NN \botmarks         \etex_botmarks:D
649  \__expl_primitive:NN \splitfirstmarks \etex_splitfirstmarks:D
650  \__expl_primitive:NN \splitbotmarks   \etex_splitbotmarks:D
651  \__expl_primitive:NN \unexpanded       \etex_unexpanded:D
652  \__expl_primitive:NN \detokenize       \etex_detokenize:D
653  \__expl_primitive:NN \scantokens       \etex_scantokens:D
654  \__expl_primitive:NN \showtokens        \etex_showtokens:D
655  \__expl_primitive:NN \readline          \etex_readline:D
656  \__expl_primitive:NN \tracingassigns   \etex_tracingassigns:D
657  \__expl_primitive:NN \tracingscantokens \etex_tracingscantokens:D
658  \__expl_primitive:NN \tracingnesting    \etex_tracingnesting:D
659  \__expl_primitive:NN \tracingifs        \etex_tracingifs:D
660  \__expl_primitive:NN \currentiflevel   \etex_currentiflevel:D
661  \__expl_primitive:NN \currentifbranch  \etex_currentifbranch:D
662  \__expl_primitive:NN \currentiftype    \etex_currentiftype:D
663  \__expl_primitive:NN \tracinggroups    \etex_tracinggroups:D
664  \__expl_primitive:NN \currentgrouplevel \etex_currentgrouplevel:D
665  \__expl_primitive:NN \currentgrouptype  \etex_currentgrouptype:D
666  \__expl_primitive:NN \showgroups        \etex_showgroups:D
667  \__expl_primitive:NN \showifs           \etex_showifs:D
668  \__expl_primitive:NN \interactionmode   \etex_interactionmode:D
669  \__expl_primitive:NN \lastnodetype      \etex_lastnodetype:D
670  \__expl_primitive:NN \iffontchar        \etex_iffontchar:D
671  \__expl_primitive:NN \fontcharht         \etex_fontcharht:D
672  \__expl_primitive:NN \fontchardp        \etex_fontchardp:D
673  \__expl_primitive:NN \fontcharwd        \etex_fontcharwd:D
674  \__expl_primitive:NN \fontcharic        \etex_fontcharic:D
675  \__expl_primitive:NN \parshapeindent    \etex_parshapeindent:D
676  \__expl_primitive:NN \parshapelen      \etex_parshapelen:D
677  \__expl_primitive:NN \parshapedimen    \etex_parshapedimen:D
678  \__expl_primitive:NN \numexpr           \etex_numexpr:D
679  \__expl_primitive:NN \dimexpr           \etex_dimexpr:D
680  \__expl_primitive:NN \glueexpr          \etex_glueexpr:D
681  \__expl_primitive:NN \muexpr            \etex_muexpr:D
682  \__expl_primitive:NN \gluestretch       \etex_gluestretch:D
683  \__expl_primitive:NN \glueshrink        \etex_glueshrink:D
684  \__expl_primitive:NN \gluestretchorder  \etex_gluestretchorder:D
685  \__expl_primitive:NN \glueshrinkorder   \etex_glueshrinkorder:D
686  \__expl_primitive:NN \gluetomu          \etex_gluetomu:D
687  \__expl_primitive:NN \mutoglue          \etex_mutoglue:D
688  \__expl_primitive:NN \lastlinefit       \etex_lastlinefit:D
689  \__expl_primitive:NN \interlinepenalties \etex_interlinepenalties:D
690  \__expl_primitive:NN \clubpenalties      \etex_clubpenalties:D

```

```

691  \__expl_primitive:NN \widowpenalties           \etex_widowpenalties:D
692  \__expl_primitive:NN \displaywidowpenalties   \etex_displaywidowpenalties:D
693  \__expl_primitive:NN \middle                  \etex_middle:D
694  \__expl_primitive:NN \savinghyphcodes        \etex_savinghyphcodes:D
695  \__expl_primitive:NN \savingvdiscards         \etex_savingvdiscards:D
696  \__expl_primitive:NN \pagediscards          \etex_pagediscards:D
697  \__expl_primitive:NN \splitdiscards          \etex_splitdiscards:D
698  \__expl_primitive:NN \TeXeTstate             \etex_TeXXeTstate:D
699  \__expl_primitive:NN \beginL                 \etex_beginL:D
700  \__expl_primitive:NN \endL                  \etex_endL:D
701  \__expl_primitive:NN \beginR                 \etex_beginR:D
702  \__expl_primitive:NN \endR                  \etex_endR:D
703  \__expl_primitive:NN \predisplaydirection    \etex_predisplaydirection:D
704  \__expl_primitive:NN \everyeof               \etex_everyeof:D
705  \__expl_primitive:NN \protected              \etex_protected:D

```

The newer primitives are more complex: there are an awful lot of them, and we don't use them all at the moment. So the following is selective. In the case of the pdf_TE_X primitives, we retain pdf at the start of the names *only* for directly PDF-related primitives, as there are a lot of pdf_TE_X primitives that start \pdf... but are not related to PDF output. These ones related to PDF output.

```

706  \__expl_primitive:NN \pdfcreationdate        \pdftex_pdfcreationdate:D
707  \__expl_primitive:NN \pdfcolorstack          \pdftex_pdfcolorstack:D
708  \__expl_primitive:NN \pdfcompresslevel       \pdftex_pdfcompresslevel:D
709  \__expl_primitive:NN \pdfdecimaldigits      \pdftex_pdfdecimaldigits:D
710  \__expl_primitive:NN \pdfhorigin            \pdftex_pdfhorigin:D
711  \__expl_primitive:NN \pdfinfo                \pdftex_pdfinfo:D
712  \__expl_primitive:NN \pdflastxform         \pdftex_pdflastxform:D
713  \__expl_primitive:NN \pdfliteral             \pdftex_pdfliteral:D
714  \__expl_primitive:NN \pdfminorversion        \pdftex_pdfminorversion:D
715  \__expl_primitive:NN \pdfobjcompresslevel    \pdftex_pdfobjcompresslevel:D
716  \__expl_primitive:NN \pdfoutput              \pdftex_pdfoutput:D
717  \__expl_primitive:NN \pdfrefxform          \pdftex_pdfrefxform:D
718  \__expl_primitive:NN \pdfrestore              \pdftex_pdfrestore:D
719  \__expl_primitive:NN \pdfsave                \pdftex_pdfsave:D
720  \__expl_primitive:NN \pdfsetmatrix          \pdftex_pdfsetmatrix:D
721  \__expl_primitive:NN \pdfpkresolution       \pdftex_pdfpkresolution:D
722  \__expl_primitive:NN \pdftextrevision       \pdftex_pdftextrevision:D
723  \__expl_primitive:NN \pdfvorigin            \pdftex_pdfvorigin:D
724  \__expl_primitive:NN \pdfxform               \pdftex_pdfxform:D

```

While these are not.

```

725  \__expl_primitive:NN \pdfstrcmp              \pdftex_strcmp:D
XTEX-specific primitives. Note that XTEX's \strcmp is handled earlier and is "rolled up" into \pdfstrcmp.
726  \__expl_primitive:NN \XeTeXversion          \xetex_XeTeXversion:D
Primitives from LuaTEX.
727  \__expl_primitive:NN \catcodetable          \luatex_catcodetable:D
728  \__expl_primitive:NN \directlua            \luatex_directlua:D

```

```

729  \__expl_primitive:NN \initcatcodetable    \luatex_initcatcodetable:D
730  \__expl_primitive:NN \latelua           \luatex_latelua:D
731  \__expl_primitive:NN \luatexversion     \luatex_luatexversion:D
732  \__expl_primitive:NN \savecatcodetable \luatex_savecatcodetable:D

```

The job is done: close the group (using the primitive renamed!).

```
733 \tex_endgroup:D
```

LATEX 2_ε will have moved a few primitives, so these are sorted out.

```

734 <*package>
735 \tex_let:D \tex_end:D          \@@end
736 \tex_let:D \tex_everydisplay:D \frozen@everydisplay
737 \tex_let:D \tex_everymath:D   \frozen@everymath
738 \tex_let:D \tex_hyphen:D      \@@hyph
739 \tex_let:D \tex_input:D       \@@input
740 \tex_let:D \tex_italiccorr:D \@@italiccorr
741 \tex_let:D \tex_underline:D  \@@underline

```

That is also true for the luatex package for LATEX 2_ε.

```

742 \tex_let:D \luatex_catcodetable:D \luatexcatcodetable
743 \tex_let:D \luatex_initcatcodetable:D \luatexinitcatcodetable
744 \tex_let:D \luatex_latelua:D      \luatexlatelua
745 \tex_let:D \luatex_savecatcodetable:D \luatexsavecatcodetable
746 </package>
747 </initex | package>

```

3 I3basics implementation

```

748 <*initex | package>
749 <*package>
750 \ProvidesExplPackage
751   {\ExplFileName}{\ExplFileVersion}{\ExplFileDescription}
752 \__expl_package_check:
753 </package>

```

3.1 Renaming some TEX primitives (again)

Having given all the TEX primitives a consistent name, we need to give sensible names to the ones we actually want to use. These will be defined as needed in the appropriate modules, but do a few now, just to get started.²

```

\if_true: Then some conditionals.
\if_false: \tex_let:D \if_true:      \tex_iftrue:D
\or:        \tex_let:D \if_false:    \tex_iffalse:D
\else:      \tex_let:D \or:        \tex_or:D
\fi:        \tex_let:D \else:       \tex_else:D
\reverse_if:N \tex_let:D \fi:        \tex_fi:D
\if:w
\if_charcode:w
\if_catcode:w
\if_meaning:w

```

²This renaming gets expensive in terms of csname usage, an alternative scheme would be to just use the \tex...:D name in the cases where no good alternative exists.

```

759 \tex_let:D \reverse_if:N      \etex_unless:D
760 \tex_let:D \if:w             \tex_if:D
761 \tex_let:D \if_charcode:w    \tex_if:D
762 \tex_let:D \if_catcode:w     \tex_ifcat:D
763 \tex_let:D \if_meaning:w    \tex_ifx:D

```

(End definition for `\if_true:` and others. These functions are documented on page 23.)

`\if_mode_math:` TeX lets us detect some if its modes.

```

\if_mode_horizontal: 764 \tex_let:D \if_mode_math:      \tex_ifemode:D
\if_mode_vertical:   765 \tex_let:D \if_mode_horizontal: \tex_ifhmode:D
\if_mode_inner:      766 \tex_let:D \if_mode_vertical: \tex_ifvmode:D
                      767 \tex_let:D \if_mode_inner:  \tex_ifinner:D

```

(End definition for `\if_mode_math:` and others. These functions are documented on page 23.)

`\if_cs_exist:N` Building csnames and testing if control sequences exist.

```

\if_cs_exist:w 768 \tex_let:D \if_cs_exist:N      \etex_ifdefined:D
\cs:w          769 \tex_let:D \if_cs_exist:w    \etex_ifcsname:D
\cs_end:       770 \tex_let:D \cs:w            \tex_csname:D
                771 \tex_let:D \cs_end:        \tex_endcsname:D

```

(End definition for `\if_cs_exist:N` and others. These functions are documented on page 16.)

`\exp_after:wN` The three `\exp_` functions are used in the l3expan module where they are described.

```

\exp_not:N 772 \tex_let:D \exp_after:wN      \tex_expandafter:D
\exp_not:n  773 \tex_let:D \exp_not:N      \tex_noexpand:D
\exp_not:n  774 \tex_let:D \exp_not:n      \etex_unexpanded:D

```

(End definition for `\exp_after:wN`, `\exp_not:N`, and `\exp_not:n`. These functions are documented on page 32.)

`\token_to_meaning:N` Examining a control sequence or token.

```

\token_to_str:N 775 \tex_let:D \token_to_meaning:N \tex_meaning:D
\cs_meaning:N   776 \tex_let:D \token_to_str:N  \tex_string:D
\cs_meaning:N   777 \tex_let:D \cs_meaning:N   \tex_meaning:D

```

(End definition for `\token_to_meaning:N`, `\token_to_str:N`, and `\cs_meaning:N`. These functions are documented on page 16.)

`\scan_stop:` The next three are basic functions for which there also exist versions that are safe inside alignments. These safe versions are defined in the l3prg module.

```

\group_begin: 778 \tex_let:D \scan_stop:      \tex_relax:D
\group_end:   779 \tex_let:D \group_begin:   \tex_begingroup:D
\group_end:   780 \tex_let:D \group_end:    \tex_endgroup:D

```

(End definition for `\scan_stop:`, `\group_begin:`, and `\group_end:`. These functions are documented on page 9.)

`\if_int_compare:w` For integers.

```

\__int_to_roman:w 781 \tex_let:D \if_int_compare:w \tex_ifnum:D
                  782 \tex_let:D \__int_to_roman:w \tex_roman numeral:D

```

(End definition for `\if_int_compare:w` and `__int_to_roman:w`. These functions are documented on page 72.)

<code>\group_insert_after:N</code>	Adding material after the end of a group. 783 <code>\tex_let:D \group_insert_after:N \tex_aftergroup:D</code> (End definition for <code>\group_insert_after:N</code> This function is documented on page 9.)
<code>\exp_args:Nc</code> <code>\exp_args:cc</code>	Discussed in l3expan, but needed much earlier. 784 <code>\tex_long:D \tex_def:D \exp_args:Nc #1#2</code> 785 { <code>\exp_after:wN #1 \cs:w #2 \cs_end:</code> } 786 <code>\tex_long:D \tex_def:D \exp_args:cc #1#2</code> 787 { <code>\cs:w #1 \exp_after:wN \cs_end: \cs:w #2 \cs_end:</code> } (End definition for <code>\exp_args:Nc</code> and <code>\exp_args:cc</code> These functions are documented on page ??.)
<code>\token_to_meaning:c</code> <code>\token_to_str:c</code> <code>\cs_meaning:c</code>	A small number of variants defined by hand. Some of the necessary functions (<code>\use_i:nn</code> , <code>\use_ii:nn</code> , and <code>\exp_args:NNc</code>) are not defined at that point yet, but will be defined before those variants are used. The <code>\cs_meaning:c</code> command must check for an undefined control sequence to avoid defining it mistakenly. 788 <code>\tex_def:D \token_to_str:c { \exp_args:Nc \token_to_str:N }</code> 789 <code>\tex_long:D \tex_def:D \cs_meaning:c #1</code> 790 { 791 <code>\if_cs_exist:w #1 \cs_end:</code> 792 <code>\exp_after:wN \use_i:nn</code> 793 <code>\else:</code> 794 <code>\exp_after:wN \use_ii:nn</code> 795 <code>\fi:</code> 796 { <code>\exp_args:Nc \cs_meaning:N {#1}</code> } 797 { <code>\tl_to_str:n {undefined}</code> } 798 } 799 <code>\tex_let:D \token_to_meaning:c = \cs_meaning:c</code> (End definition for <code>\token_to_meaning:c</code> , <code>\token_to_str:c</code> , and <code>\cs_meaning:c</code> These functions are documented on page ??.)

3.2 Defining some constants

<code>\c_minus_one</code> <code>\c_zero</code> <code>\c_sixteen</code> <code>\c_six</code> <code>\c_seven</code> <code>\c_twelve</code>	We need the constants <code>\c_minus_one</code> and <code>\c_sixteen</code> now for writing information to the log and the terminal and <code>\c_zero</code> which is used by some functions in the l3alloc module. The rest are defined in the l3int module – at least for the ones that can be defined with <code>\tex_chardef:D</code> or <code>\tex_mathchardef:D</code> . For other constants the l3int module is required but it can't be used until the allocation has been set up properly! The actual allocation mechanism is in l3alloc and as TeX wants to reserve count registers 0–9, the first available one is 10 so we use that for <code>\c_minus_one</code> .
--	---

```
800 <*package>
801 \tex_let:D \c_minus_one \m@ne
802 </package>
803 <*initex>
804 \tex_countdef:D \c_minus_one = 10 ~
805 \c_minus_one = -1 ~
806 </initex>
807 \tex_chardef:D \c_sixteen = 16 ~
808 \tex_chardef:D \c_zero = 0 ~
```

```

809 \tex_chardef:D \c_six      = 6 ~
810 \tex_chardef:D \c_seven    = 7 ~
811 \tex_chardef:D \c_twelve   = 12 ~
(End definition for \c_minus_one, \c_zero, and \c_sixteen These functions are documented on page
71.)
```

\c_max_register_int

This is here as this particular integer is needed both in package mode and to bootstrap `\alloc`, and is documented in `\int`.

```

812 \etex_ifdefined:D \luatex_luatexversion:D
813   \tex_chardef:D \c_max_register_int = 65 535 ~
814 \tex_else:D
815   \tex_mathchardef:D \c_max_register_int = 32 767 ~
816 \tex_fi:D
```

(End definition for `\c_max_register_int` This variable is documented on page 71.)

3.3 Defining functions

We start by providing functions for the typical definition functions. First the local ones.

All assignment functions in L^AT_EX3 should be naturally protected; after all, the T_EX primitives for assignments are and it can be a cause of problems if others aren't.

```

817 \tex_let:D \cs_set_nopar:Npn           \tex_def:D
818 \tex_let:D \cs_set_nopar:Npx          \tex_eodef:D
819 \etex_protected:D \cs_set_nopar:Npn \cs_set:Npn
820 { \tex_long:D \cs_set_nopar:Npn }
821 \etex_protected:D \cs_set_nopar:Npn \cs_set:Npx
822 { \tex_long:D \cs_set_nopar:Npx }
823 \etex_protected:D \cs_set_nopar:Npn \cs_set_protected_nopar:Npn
824 { \etex_protected:D \cs_set_nopar:Npn }
825 \etex_protected:D \cs_set_nopar:Npn \cs_set_protected_nopar:Npx
826 { \etex_protected:D \cs_set_nopar:Npx }
827 \cs_set_protected_nopar:Npn \cs_set_protected:Npn
828 { \etex_protected:D \tex_long:D \cs_set_nopar:Npn }
829 \cs_set_protected_nopar:Npn \cs_set_protected:Npx
830 { \etex_protected:D \tex_long:D \cs_set_nopar:Npx }
```

(End definition for `\cs_set_nopar:Npn` and others. These functions are documented on page ??.)

\cs_gset_nopar:Npn

Global versions of the above functions.

```

831 \tex_let:D \cs_gset_nopar:Npn           \tex_gdef:D
832 \tex_let:D \cs_gset_nopar:Npx          \tex_xdef:D
833 \cs_set_protected_nopar:Npn \cs_gset:Npn
834 { \tex_long:D \cs_gset_nopar:Npn }
835 \cs_set_protected_nopar:Npn \cs_gset:Npx
836 { \tex_long:D \cs_gset_nopar:Npx }
837 \cs_set_protected_nopar:Npn \cs_gset_protected_nopar:Npn
838 { \etex_protected:D \cs_gset_nopar:Npn }
839 \cs_set_protected_nopar:Npn \cs_gset_protected_nopar:Npx
840 { \etex_protected:D \cs_gset_nopar:Npx }
841 \cs_set_protected_nopar:Npn \cs_gset_protected:Npn
```

```

842 { \etex_protected:D \tex_long:D \cs_gset_nopar:Npn }
843 \cs_set_protected_nopar:Npn \cs_gset_protected:Npx
844 { \etex_protected:D \tex_long:D \cs_gset_nopar:Npx }
(End definition for \cs_gset_nopar:Npn and others. These functions are documented on page ??.)
```

3.4 Selecting tokens

\l__exp_internal_t1 Scratch token list variable for `\3exp`, used by `\use:x`, used in defining conditionals. We don't use `t1` methods because `\3basics` is loaded earlier.

```

845 \cs_set_nopar:Npn \l__exp_internal_t1 { }
(End definition for \l__exp_internal_t1 This variable is documented on page 33.)
```

\use:c This macro grabs its argument and returns a csname from it.

```

846 \cs_set:Npn \use:c #1 { \cs:w #1 \cs_end: }
(End definition for \use:c This function is documented on page 16.)
```

\use:x Fully expands its argument and passes it to the input stream. Uses the reserved `\l__exp_internal_t1` which will be set up in `\3exp`.

```

847 \cs_set_protected:Npn \use:x #1
848 {
849   \cs_set_nopar:Npx \l__exp_internal_t1 {#1}
850   \l__exp_internal_t1
851 }
```

(End definition for `\use:x` This function is documented on page 19.)

\use:n These macros grab their arguments and returns them back to the input (with outer braces removed).

```

852 \cs_set:Npn \use:n    #1      {#1}
853 \cs_set:Npn \use:nn   #1#2     {#1#2}
854 \cs_set:Npn \use:nnn  #1#2#3   {#1#2#3}
855 \cs_set:Npn \use:nnnn #1#2#3#4 {#1#2#3#4}
```

(End definition for `\use:n` and others. These functions are documented on page ??.)

\use_i:nn The equivalent to L^AT_EX 2 _{ε} 's `\@firstoftwo` and `\@secondoftwo`.

```

856 \cs_set:Npn \use_i:nn  #1#2 {#1}
857 \cs_set:Npn \use_ii:nn #1#2 {#2}
(End definition for \use_i:nn and \use_ii:nn These functions are documented on page 18.)
```

We also need something for picking up arguments from a longer list.

```

858 \cs_set:Npn \use_i:nnn   #1#2#3 {#1}
859 \cs_set:Npn \use_ii:nnn  #1#2#3 {#2}
860 \cs_set:Npn \use_iii:nnn #1#2#3 {#3}
861 \cs_set:Npn \use_i_ii:nnn #1#2#3 {#1#2}
862 \cs_set:Npn \use_i_i:nnnn #1#2#3#4 {#1}
863 \cs_set:Npn \use_ii_i:nnnn #1#2#3#4 {#2}
864 \cs_set:Npn \use_iii_i:nnnn #1#2#3#4 {#3}
865 \cs_set:Npn \use_iv_i:nnnn #1#2#3#4 {#4}
```

(End definition for `\use_i:nnn` and others. These functions are documented on page 18.)

```
\use_none_delimit_by_q_nil:w  
  \use_none_delimit_by_q_stop:w  
\use_none_delimit_by_q_recursion_stop:w
```

Functions that gobble everything until they see either `\q_nil`, `\q_stop`, or `\q_recursion_stop`, respectively.

```
866 \cs_set:Npn \use_none_delimit_by_q_nil:w #1 \q_nil { }  
867 \cs_set:Npn \use_none_delimit_by_q_stop:w #1 \q_stop { }  
868 \cs_set:Npn \use_none_delimit_by_q_recursion_stop:w #1 \q_recursion_stop { }
```

(End definition for `\use_none_delimit_by_q_nil:w`, `\use_none_delimit_by_q_stop:w`, and `\use_none_delimit_by_q_recursion_stop:w`. These functions are documented on page 46.)

```
\use_i_delimit_by_q_nil:nw  
\use_i_delimit_by_q_stop:nw  
\use_i_delimit_by_q_recursion_stop:nw
```

Same as above but execute first argument after gobbling. Very useful when you need to skip the rest of a mapping sequence but want an easy way to control what should be expanded next.

```
869 \cs_set:Npn \use_i_delimit_by_q_nil:nw #1#2 \q_nil {#1}  
870 \cs_set:Npn \use_i_delimit_by_q_stop:nw #1#2 \q_stop {#1}  
871 \cs_set:Npn \use_i_delimit_by_q_recursion_stop:nw #1#2 \q_recursion_stop {#1}
```

(End definition for `\use_i_delimit_by_q_nil:nw`, `\use_i_delimit_by_q_stop:nw`, and `\use_i_delimit_by_q_recursion_stop:nw`. These functions are documented on page 46.)

3.5 Gobbling tokens from input

```
\use_none:n  
\use_none:nn  
\use_none:nnn  
\use_none:nnnn  
\use_none:nnnnn  
\use_none:nnnnnn  
\use_none:nnnnnnn  
\use_none:nnnnnnnn
```

To gobble tokens from the input we use a standard naming convention: the number of tokens gobbled is given by the number of n's following the : in the name. Although we could define functions to remove ten arguments or more using separate calls of `\use_none:nnnnnn`, this is very non-intuitive to the programmer who will assume that expanding such a function once will take care of gobbling all the tokens in one go.

```
872 \cs_set:Npn \use_none:n #1 { }  
873 \cs_set:Npn \use_none:nn #1#2 { }  
874 \cs_set:Npn \use_none:nnn #1#2#3 { }  
875 \cs_set:Npn \use_none:nnnn #1#2#3#4 { }  
876 \cs_set:Npn \use_none:nnnnn #1#2#3#4#5 { }  
877 \cs_set:Npn \use_none:nnnnnn #1#2#3#4#5#6 { }  
878 \cs_set:Npn \use_none:nnnnnnn #1#2#3#4#5#6#7 { }  
879 \cs_set:Npn \use_none:nnnnnnnn #1#2#3#4#5#6#7#8 { }  
880 \cs_set:Npn \use_none:nnnnnnnnn #1#2#3#4#5#6#7#8#9 { }
```

(End definition for `\use_none:n` and others. These functions are documented on page ??.)

3.6 Conditional processing and definitions

Underneath any predicate function (`_p`) or other conditional forms (TF, etc.) is a built-in logic saying that it after all of the testing and processing must return the `(state)` this leaves TeX in. Therefore, a simple user interface could be something like

```
\if_meaning:w #1#2  
  \prg_return_true:  
\else:  
  \if_meaning:w #1#3  
  \prg_return_true:
```

```

\else:
    \prg_return_false:
\fi:
\fi:

```

Usually, a TeX programmer would have to insert a number of `\exp_after:wN`s to ensure the state value is returned at exactly the point where the last conditional is finished. However, that obscures the code and forces the TeX programmer to prove that he/she knows the $2^n - 1$ table. We therefore provide the simpler interface.

`\prg_return_true:` The idea here is that `_int_to_roman:w` will expand fully any `\else:` and the `\fi:` that are waiting to be discarded, before reaching the `\c_zero` which will leave the expansion null. The code can then leave either the first or second argument in the input stream. This means that all of the branching code has to contain at least two tokens: see how the logical tests are actually implemented to see this.

```

881 \cs_set_nopar:Npn \prg_return_true:
882   { \exp_after:wN \use_i:nn \_int_to_roman:w }
883 \cs_set_nopar:Npn \prg_return_false:
884   { \exp_after:wN \use_ii:nn \_int_to_roman:w}

```

An extended state space could be implemented by including a more elaborate function in place of `\use_i:nn`/`\use_ii:nn`. Provided two arguments are absorbed then the code will work.

(End definition for `\prg_return_true:` and `\prg_return_false:`. These functions are documented on page 36.)

`\prg_set_conditional:Npnn`
`\prg_new_conditional:Npnn`
`\prg_set_protected_conditional:Npnn`
`\prg_new_protected_conditional:Npnn`
`_prg_generate_conditional_parm:nnNpnn`

The user functions for the types using parameter text from the programmer. The various functions only differ by which function is used for the assignment. For those `Npnn` type functions, we must grab the parameter text, reading everything up to a left brace before continuing. Then split the base function into name and signature, and feed `{<name>}` `{<signature>}` `{<boolean>}` `{<set or new>}` `{<maybe protected>}` `{<parameters>}` `{TF,...}` `{<code>}` to the auxiliary function responsible for defining all conditionals.

```

885 \cs_set_protected_nopar:Npn \prg_set_conditional:Npnn
886   { \_prg_generate_conditional_parm:nnNpnn { set } { } }
887 \cs_set_protected_nopar:Npn \prg_new_conditional:Npnn
888   { \_prg_generate_conditional_parm:nnNpnn { new } { } }
889 \cs_set_protected_nopar:Npn \prg_set_protected_conditional:Npnn
890   { \_prg_generate_conditional_parm:nnNpnn { set } { _protected } }
891 \cs_set_protected_nopar:Npn \prg_new_protected_conditional:Npnn
892   { \_prg_generate_conditional_parm:nnNpnn { new } { _protected } }
893 \cs_set_protected:Npn \_prg_generate_conditional_parm:nnNpnn #1#2#3#4#
894   {
895     \_cs_split_function>NN #3 \_prg_generate_conditional:nnNnnnnn
896     {#1} {#2} {#4}
897   }

```

(End definition for `\prg_set_conditional:Npnn` and others. These functions are documented on page 34.)

```
\prg_set_conditional:Nnn
\prg_new_conditional:Nnn
  \prg_set_protected_conditional:Nnn
  \prg_new_protected_conditional:Nnn
  \__prg_generate_conditional_count:nnNnn
  \__prg_generate_conditional_count:nnNnnn
```

The user functions for the types automatically inserting the correct parameter text based on the signature. The various functions only differ by which function is used for the assignment. Split the base function into name and signature. The second auxiliary generates the parameter text from the number of letters in the signature. Then feed $\{\langle name \rangle\} \{\langle signature \rangle\} \langle boolean \rangle \{\langle set or new \rangle\} \{\langle maybe protected \rangle\} \{\langle parameters \rangle\} \{\text{TF}, \dots\} \{\langle code \rangle\}$ to the auxiliary function responsible for defining all conditionals. If the $\langle signature \rangle$ has more than 9 letters, the definition is aborted since TeX macros have at most 9 arguments. The erroneous case where the function name contains no colon is captured later.

```
988 \cs_set_protected_nopar:Npn \prg_set_conditional:Nnn
989   { \__prg_generate_conditional_count:nnNnn { set } { } }
990 \cs_set_protected_nopar:Npn \prg_new_conditional:Nnn
991   { \__prg_generate_conditional_count:nnNnn { new } { } }
992 \cs_set_protected_nopar:Npn \prg_set_protected_conditional:Nnn
993   { \__prg_generate_conditional_count:nnNnn { set } { _protected } }
994 \cs_set_protected_nopar:Npn \prg_new_protected_conditional:Nnn
995   { \__prg_generate_conditional_count:nnNnn { new } { _protected } }
996 \cs_set_protected:Npn \__prg_generate_conditional_count:nnNnn #1#2#3
997   {
998     \__cs_split_function>NN #3 \__prg_generate_conditional_count:nnNnnnn
999     {#1} {#2}
1000   }
1001 \cs_set_protected:Npn \__prg_generate_conditional_count:nnNnnnn #1#2#3#4#5
1002   {
1003     \__cs_parm_from_arg_count:nnF
1004     { \__prg_generate_conditional:nnNnnnnn {#1} {#2} #3 {#4} {#5} }
1005     { \tl_count:n {#2} }
1006     {
1007       \__msg_kernel_error:nnxx { kernel } { bad-number-of-arguments }
1008       { \token_to_str:c { #1 : #2 } }
1009       { \tl_count:n {#2} }
1010       \use_none:nn
1011     }
1012   }
```

(End definition for $\text{\prg_set_conditional:Nnn}$ and others. These functions are documented on page ??.)

```
\__prg_generate_conditional:nnNnnnn
\__prg_generate_conditional:nnnnnnw
```

The workhorse here is going through a list of desired forms, *i.e.*, p, TF, T and F. The first three arguments come from splitting up the base form of the conditional, which gives the name, signature and a boolean to signal whether or not there was a colon in the name. In the absence of a colon, we throw an error and don't define any conditional. The fourth and fifth arguments build up the defining function. The sixth is the parameters to use (possibly empty), the seventh is the list of forms to define, the eighth is the replacement text which we will augment when defining the forms. The use of $\text{\etex_detokenize:D}$ makes the later loop more robust.

```
923 \cs_set_protected:Npn \__prg_generate_conditional:nnNnnnnn #1#2#3#4#5#6#7#8
924   {
925     \if_meaning:w \c_false_bool #3
```

```

926   \_\_msg_kernel_error:nnx { kernel } { missing-colon }
927     { \token_to_str:c {#1} }
928     \exp_after:wN \use_none:nn
929   \fi:
930   \use:x
931   {
932     \exp_not:N \_\_prg_generate_conditional:nnnnnnw
933     \exp_not:n { {#4} {#5} {#1} {#2} {#6} {#8} }
934     \etex_detokenize:D {#7}
935     \exp_not:n { , \q_recursion_tail , \q_recursion_stop }
936   }
937 }
```

Looping through the list of desired forms. First are six arguments and seventh is the form. Use the form to call the correct type. If the form does not exist, the `\use:c` construction results in `\relax`, and the error message is displayed (unless the form is empty, to allow for {T, , F}), then `\use_none:nnnnnnn` cleans up. Otherwise, the error message is removed by the variant form.

```

938 \cs_set_protected:Npn \_\_prg_generate_conditional:nnnnnnw #1#2#3#4#5#6#7 ,
939   {
940     \if_meaning:w \q_recursion_tail #7
941       \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
942     \fi:
943     \use:c { __prg_generate_ #7 _form:wnnnnnn }
944       \tl_if_empty:nF {#7}
945       {
946         \_\_msg_kernel_error:nnxx
947           { kernel } { conditional-form-unknown }
948           {#7} { \token_to_str:c { #3 : #4 } }
949       }
950     \use_none:nnnnnnn
951     \q_stop
952       {#1} {#2} {#3} {#4} {#5} {#6}
953   \_\_prg_generate_conditional:nnnnnnw {#1} {#2} {#3} {#4} {#5} {#6}
954 }
```

(End definition for `__prg_generate_conditional:nnNnnnnn` and `__prg_generate_conditional:nnnnnnw`)

```

\_\_prg_generate_p_form:wnnnnnn
\_\_prg_generate_TF_form:wnnnnnn
\_\_prg_generate_T_form:wnnnnnn
\_\_prg_generate_F_form:wnnnnnn
```

How to generate the various forms. Those functions take the following arguments: 1: `set` or `new`, 2: empty or `_protected`, 3: function name 4: signature, 5: parameter text (or empty), 6: replacement. Remember that the logic-returning functions expect two arguments to be present after `\c_zero`: notice the construction of the different variants relies on this, and that the TF variant will be slightly faster than the T version. The p form is only valid for expandable tests, we check for that by making sure that the second argument is empty.

```

955 \cs_set_protected:Npn \_\_prg_generate_p_form:wnnnnnn #1 \q_stop #2#3#4#5#6#7
956   {
957     \if_meaning:w \scan_stop: #3 \scan_stop:
958       \exp_after:wN \use_i:nn
959     \else:
```

```

960     \exp_after:wN \use_i:nn
961 \fi:
962 {
963     \exp_args:cc { cs_ #2 #3 :Npn } { #4 _p: #5 } #6
964         { #7 \c_zero \c_true_bool \c_false_bool }
965     }
966     {
967         \__msg_kernel_error:n { kernel } { protected-predicate }
968             { \token_to_str:c { #4 _p: #5 } }
969     }
970 }
971 \cs_set_protected:Npn \__prg_generate_T_form:wnnnnnn #1 \q_stop #2#3#4#5#6#7
972 {
973     \exp_args:cc { cs_ #2 #3 :Npn } { #4 : #5 T } #6
974         { #7 \c_zero \use:n \use_none:n }
975 }
976 \cs_set_protected:Npn \__prg_generate_F_form:wnnnnnn #1 \q_stop #2#3#4#5#6#7
977 {
978     \exp_args:cc { cs_ #2 #3 :Npn } { #4 : #5 F } #6
979         { #7 \c_zero { } }
980 }
981 \cs_set_protected:Npn \__prg_generate_TF_form:wnnnnnn #1 \q_stop #2#3#4#5#6#7
982 {
983     \exp_args:cc { cs_ #2 #3 :Npn } { #4 : #5 TF } #6
984         { #7 \c_zero }
985 }

```

(End definition for `__prg_generate_p_form:wnnnnnn` and others.)

`\prg_set_eq_conditional:NNn`
`\prg_new_eq_conditional:NNn`
`__prg_set_eq_conditional:NNNn`

```

986 \cs_set_protected:Npn \prg_set_eq_conditional:NNn
987     { \__prg_set_eq_conditional:NNNn \cs_set_eq:cc }
988 \cs_set_protected:Npn \prg_new_eq_conditional:NNn
989     { \__prg_set_eq_conditional:NNNn \cs_new_eq:cc }
990 \cs_set_protected:Npn \__prg_set_eq_conditional:NNNn #1#2#3#4
991     {
992         \use:x
993         {
994             \exp_not:N \__prg_set_eq_conditional:nnNnnNNw
995                 \__cs_split_function:NN #2 \prg_do_nothing:
996                 \__cs_split_function:NN #3 \prg_do_nothing:
997                 \exp_not:N #1
998                 \etex_detokenize:D {#4}
999                 \exp_not:n { , \q_recursion_tail , \q_recursion_stop }
1000             }
1001 }

```

(End definition for `\prg_set_eq_conditional:NNn` and `\prg_new_eq_conditional:NNn`. These functions are documented on page 36.)

`_prg_set_eq_conditional:nNnnNNw`
`_prg_set_eq_conditional_loop:nnnnNw`
`_prg_set_eq_conditional_p_form:nnn`
`_prg_set_eq_conditional_TF_form:nnn`
`_prg_set_eq_conditional_T_form:nnn`
`_prg_set_eq_conditional_F_form:nnn`

Split the function to be defined, and setup a manual clist loop over argument #6 of the first auxiliary. The second auxiliary receives twice three arguments coming from splitting the function to be defined and the function to copy. Make sure that both functions contained a colon, otherwise we don't know how to build conditionals, hence abort. Call the looping macro, with arguments `{<name1>} {<signature1>} {<name2>} {<signature2>}` *(copying function)* and followed by the comma list. At each step in the loop, make sure that the conditional form we copy is defined, and copy it, otherwise abort.

```

1002 \cs_set_protected:Npn \_prg_set_eq_conditional:nnNnnNNw #1#2#3#4#5#6
1003 {
1004     \if_meaning:w \c_false_bool #3
1005         \_msg_kernel_error:nnx { kernel } { missing-colon }
1006         { \token_to_str:c {#1} }
1007         \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1008     \fi:
1009     \if_meaning:w \c_false_bool #6
1010         \_msg_kernel_error:nnx { kernel } { missing-colon }
1011         { \token_to_str:c {#4} }
1012         \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1013     \fi:
1014     \_prg_set_eq_conditional_loop:nnnnNw {#1} {#2} {#4} {#5}
1015 }
1016 \cs_set_protected:Npn \_prg_set_eq_conditional_loop:nnnnNw #1#2#3#4#5#6 ,
1017 {
1018     \if_meaning:w \q_recursion_tail #6
1019         \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1020     \fi:
1021     \use:c { __prg_set_eq_conditional_ #6 _form:wNnnnn }
1022         \tl_if_empty:nF {#6}
1023         {
1024             \_msg_kernel_error:nnxx
1025                 { kernel } { conditional-form-unknown }
1026                 {#6} { \token_to_str:c { #1 : #2 } }
1027         }
1028         \use_none:nnnnnn
1029         \q_stop
1030         #5 {#1} {#2} {#3} {#4}
1031         \_prg_set_eq_conditional_loop:nnnnNw {#1} {#2} {#3} {#4} #5
1032     }
1033 \cs_set:Npn \_prg_set_eq_conditional_p_form:wNnnnn #1 \q_stop #2#3#4#5#6
1034 {
1035     \__chk_if_exist_cs:c { #5 _p : #6      }
1036     #2 { #3 _p : #4      } { #5 _p : #6      }
1037 }
1038 \cs_set:Npn \_prg_set_eq_conditional_TF_form:wNnnnn #1 \q_stop #2#3#4#5#6
1039 {
1040     \__chk_if_exist_cs:c { #5      : #6 TF }
1041     #2 { #3      : #4 TF } { #5      : #6 TF }
1042 }
1043 \cs_set:Npn \_prg_set_eq_conditional_T_form:wNnnnn #1 \q_stop #2#3#4#5#6

```

```

1044  {
1045    \__chk_if_exist_cs:c { #5      : #6 T  }
1046    #2 { #3      : #4 T  } { #5      : #6 T  }
1047  }
1048 \cs_set:Npn \__prg_set_eq_conditional_F_form:wNnnnn #1 \q_stop #2#3#4#5#6
1049  {
1050    \__chk_if_exist_cs:c { #5      : #6 F  }
1051    #2 { #3      : #4 F  } { #5      : #6 F  }
1052  }

```

(End definition for `__prg_set_eq_conditional:nNnnnNw` and `__prg_set_eq_conditional_loop:nnnnNw`.
These functions are documented on page 36.)

All that is left is to define the canonical boolean true and false. I think Michael originated the idea of expandable boolean tests. At first these were supposed to expand into either TT or TF to be tested using `\if:w` but this was later changed to 00 and 01, so they could be used in logical operations. Later again they were changed to being numerical constants with values of 1 for true and 0 for false. We need this from the get-go.

\c_true_bool Here are the canonical boolean values.
\c_false_bool

```

1053 \tex_chardef:D \c_true_bool = 1 ~
1054 \tex_chardef:D \c_false_bool = 0 ~

```

(End definition for `\c_true_bool` and `\c_false_bool`. These variables are documented on page 20.)

3.7 Dissecting a control sequence

\cs_to_str:N This converts a control sequence into the character string of its name, removing the leading escape character. This turns out to be a non-trivial matter as there are different cases:

- The usual case of a printable escape character;
- the case of a non-printable escape characters, e.g., when the value of the `\escapechar` is negative;
- when the escape character is a space.

One approach to solve this is to test how many tokens result from `\token_to_str:N \a`. If there are two tokens, then the escape character is printable, while if it is non-printable then only one is present.

However, there is an additional complication: the control sequence itself may start with a space. Clearly that should *not* be lost in the process of converting to a string. So the approach adopted is a little more intricate still. When the escape character is printable, `\token_to_str:N \a` yields the escape character itself and a space. The character codes are different, thus the `\if:w` test is false, and TeX reads `__cs_to_str:N` after turning the following control sequence into a string; this auxiliary removes the escape character, and stops the expansion of the initial `__int_to_roman:w`. The second case is that the escape character is not printable. Then the `\if:w` test is unfinished after reading a the space from `\token_to_str:N \a`, and the auxiliary `__cs_to_str:w`

is expanded, feeding - as a second character for the test; the test is false, and T_EX skips to \fi:, then performs \token_to_str:N, and stops the __int_to_roman:w with \c_zero. The last case is that the escape character is itself a space. In this case, the \if:w test is true, and the auxiliary __cs_to_str:w comes into play, inserting -__int_value:w, which expands \c_zero to the character 0. The initial __int_to_roman:w then sees 0, which is not a terminated number, followed by the escape character, a space, which is removed, terminating the argument of __int_to_roman:w. In all three cases, \cs_to_-str:N takes two expansion steps to be fully expanded.

```

1055 \cs_set_nopar:Npn \cs_to_str:N
1056 {
1057   \__int_to_roman:w
1058   \if:w \token_to_str:N \ \__cs_to_str:w \fi:
1059   \exp_after:wN \__cs_to_str:N \token_to_str:N
1060 }
1061 \cs_set:Npn \__cs_to_str:N #1 { \c_zero }
1062 \cs_set:Npn \__cs_to_str:w #1 \__cs_to_str:N
1063 { - \__int_value:w \fi: \exp_after:wN \c_zero }

```

(End definition for \cs_to_str:N This function is documented on page 17.)

__cs_split_function>NN
__cs_split_function_i:w
__cs_split_function_ii:w

This function takes a function name and splits it into name with the escape char removed and argument specification. In addition to this, a third argument, a boolean *true* or *false* is returned with *true* for when there is a colon in the function and *false* if there is not. Lastly, the second argument of __cs_split_function>NN is supposed to be a function taking three variables, one for name, one for signature, and one for the boolean. For example, __cs_split_function>NN \foo_bar:cw \use_i:nnn as input becomes \use_i:nnn {foo_bar} {cnx} \c_true_bool.

We can't use a literal : because it has the wrong catcode here, so it's transformed from @ with \tex_lowercase:D.

First ensure that we actually get a properly evaluated string by expanding \cs_-to_str:N twice. If the function contained a colon, the auxiliary takes as #1 the function name, delimited by the first colon, then the signature #2, delimited by \q_mark, then \c_true_bool as #3, and #4 cleans up until \q_stop. Otherwise, the #1 contains the function name and \q_mark \c_true_bool, #2 is empty, #3 is \c_false_bool, and #4 cleans up. In both cases, #5 is the *processor*. The second auxiliary trims the trailing \q_mark from the function name if present (that is, if the original function had no colon).

```

1064 \group_begin:
1065 \tex_lccode:D '\@ = '\: \scan_stop:
1066 \tex_catcode:D '\@ = 12 ~
1067 \tex_lowercase:D
1068 {
1069   \group_end:
1070   \cs_set:Npn \__cs_split_function>NN #1
1071   {
1072     \exp_after:wN \exp_after:wN
1073     \exp_after:wN \__cs_split_function_i:w
1074     \cs_to_str:N #1 \q_mark \c_true_bool
1075     @ \q_mark \c_false_bool

```

```

1076           \q_stop
1077       }
1078   \cs_set:Npn \__cs_split_function_i:w #1 @ #2 \q_mark #3#4 \q_stop #5
1079   { \__cs_split_function_ii:w #5 #1 \q_mark \q_stop {#2} #3 }
1080   \cs_set:Npn \__cs_split_function_ii:w #1#2 \q_mark #3 \q_stop
1081   { #1 {#2} }
1082 }

```

(End definition for `__cs_split_function>NN`. This function is documented on page 24.)

`__cs_get_function_name:N`
`__cs_get_function_signature:N`

```

1083 \cs_set:Npn \__cs_get_function_name:N #1
1084 { \__cs_split_function:NN #1 \use_i:nnn }
1085 \cs_set:Npn \__cs_get_function_signature:N #1
1086 { \__cs_split_function:NN #1 \use_ii:nnn }

```

(End definition for `__cs_get_function_name:N` and `__cs_get_function_signature:N`)

3.8 Exist or free

A control sequence is said to *exist* (to be used) if has an entry in the hash table and its meaning is different from the primitive `\relax` token. A control sequence is said to be *free* (to be defined) if it does not already exist.

`\cs_if_exist_p:N`
`\cs_if_exist_p:c`
`\cs_if_exist:NTF`
`\cs_if_exist:cTF`

Two versions for checking existence. For the N form we firstly check for `\scan_stop:` and then if it is in the hash table. There is no problem when inputting something like `\else:` or `\fi:` as TeX will only ever skip input in case the token tested against is `\scan_stop:`.

```

1087 \prg_set_conditional:Npnn \cs_if_exist:N #1 { p , T , F , TF }
1088 {
1089     \if_meaning:w #1 \scan_stop:
1090     \prg_return_false:
1091     \else:
1092         \if_cs_exist:N #1
1093         \prg_return_true:
1094     \else:
1095         \prg_return_false:
1096     \fi:
1097     \fi:
1098 }

```

For the c form we firstly check if it is in the hash table and then for `\scan_stop:` so that we do not add it to the hash table unless it was already there. Here we have to be careful as the text to be skipped if the first test is false may contain tokens that disturb the scanner. Therefore, we ensure that the second test is performed after the first one has concluded completely.

```

1099 \prg_set_conditional:Npnn \cs_if_exist:c #1 { p , T , F , TF }
1100 {
1101     \if_cs_exist:w #1 \cs_end:
1102     \exp_after:wN \use_i:nn
1103     \else:
1104     \exp_after:wN \use_ii:nn

```

```

1105   \fi:
1106   {
1107     \exp_after:wN \if_meaning:w \cs:w #1 \cs_end: \scan_stop:
1108       \prg_return_false:
1109     \else:
1110       \prg_return_true:
1111     \fi:
1112   }
1113   \prg_return_false:
1114 }
```

(End definition for `\cs_if_exist:N` and `\cs_if_exist:c` These functions are documented on page ??.)

`\cs_if_free_p:N`

`\cs_if_free_p:c`

`\cs_if_free:NTF`

`\cs_if_free:cTF`

The logical reversal of the above.

```

1115 \prg_set_conditional:Npnn \cs_if_free:N #1 { p , T , F , TF }
1116   {
1117     \if_meaning:w #1 \scan_stop:
1118       \prg_return_true:
1119     \else:
1120       \if_cs_exist:N #1
1121         \prg_return_false:
1122       \else:
1123         \prg_return_true:
1124       \fi:
1125     \fi:
1126   }
1127 \prg_set_conditional:Npnn \cs_if_free:c #1 { p , T , F , TF }
1128   {
1129     \if_cs_exist:w #1 \cs_end:
1130       \exp_after:wN \use_i:nn
1131     \else:
1132       \exp_after:wN \use_ii:nn
1133     \fi:
1134   {
1135     \exp_after:wN \if_meaning:w \cs:w #1 \cs_end: \scan_stop:
1136       \prg_return_true:
1137     \else:
1138       \prg_return_false:
1139     \fi:
1140   }
1141   { \prg_return_true: }
1142 }
```

(End definition for `\cs_if_free:N` and `\cs_if_free:c` These functions are documented on page ??.)

`\cs_if_exist_use:NTF`

`\cs_if_exist_use:cTF`

`\cs_if_exist_use:N`

`\cs_if_exist_use:c`

The `\cs_if_exist_use:...` functions cannot be implemented as conditionals because the true branch must leave both the control sequence itself and the true code in the input stream. For the `c` variants, we are careful not to put the control sequence in the hash table if it does not exist.

```

1143 \cs_set:Npn \cs_if_exist_use:NTF #1#2
1144   { \cs_if_exist:NTF #1 { #1 #2 } }
```

```

1145 \cs_set:Npn \cs_if_exist_use:NF #1
1146   { \cs_if_exist:NTF #1 { #1 } }
1147 \cs_set:Npn \cs_if_exist_use:NT #1 #2
1148   { \cs_if_exist:NTF #1 { #1 #2 } { } }
1149 \cs_set:Npn \cs_if_exist_use:N #1
1150   { \cs_if_exist:NTF #1 { #1 } { } }
1151 \cs_set:Npn \cs_if_exist_use:cTF #1#2
1152   { \cs_if_exist:cTF {#1} { \use:c {#1} #2 } }
1153 \cs_set:Npn \cs_if_exist_use:cF #1
1154   { \cs_if_exist:cTF {#1} { \use:c {#1} } }
1155 \cs_set:Npn \cs_if_exist_use:cT #1#2
1156   { \cs_if_exist:cTF {#1} { \use:c {#1} #2 } { } }
1157 \cs_set:Npn \cs_if_exist_use:c #1
1158   { \cs_if_exist:cTF {#1} { \use:c {#1} } { } }

(End definition for \cs_if_exist_use:N and \cs_if_exist_use:c These functions are documented on
page ??.)
```

3.9 Defining and checking (new) functions

We provide two kinds of functions that can be used to define control sequences. On the one hand we have functions that check if their argument doesn't already exist, they are called \..._new. The second type of defining functions doesn't check if the argument is already defined.

Before we can define them, we need some auxiliary macros that allow us to generate error messages. The definitions here are only temporary, they will be redefined later on.

`\iow_log:x` We define a routine to write only to the log file. And a similar one for writing to both
`\iow_term:x` the log file and the terminal. These will be redefined later by l3io.

```

1159 \cs_set_protected_nopar:Npn \iow_log:x
1160   { \tex_immediate:D \tex_write:D \c_minus_one }
1161 \cs_set_protected_nopar:Npn \iow_term:x
1162   { \tex_immediate:D \tex_write:D \c_sixteen }
(End definition for \iow_log:x and \iow_term:x These functions are documented on page ???.)

```

`_msg_kernel_error:nxxx`
`_msg_kernel_error:nnx`
`_msg_kernel_error:nn`

If an internal error occurs before LATEX3 has loaded l3msg then the code should issue a usable if terse error message and halt. This can only happen if a coding error is made by the team, so this is a reasonable response.

```
1163 \cs_set_protected:Npn \__msg_kernel_error:nxxx #1#2#3#4
1164 {
1165     \tex_errmessage:D
1166     {
1167         !!!!!!!Argh,-internal-TeX3-error! ^J ^J
1168         Module ~ #1 , ~ message-name~"#2": ^J
1169         Arguments~'#3~and~'#4' ^J ^J
1170         This-is-one-for-The-TeX3-Project:~bailing-out
1171     }
1172 }
1173 \tex_end:D
```

```

1174   }
1175 \cs_set_protected:Npn \__msg_kernel_error:nnx #1#2#3
1176   { \__msg_kernel_error:nnxx {#1} {#2} {#3} { } }
1177 \cs_set_protected:Npn \__msg_kernel_error:nn #1#2
1178   { \__msg_kernel_error:nnxx {#1} {#2} { } { } }
(End definition for \__msg_kernel_error:nnxx, \__msg_kernel_error:nnx, and \__msg_kernel_error:nn)

```

\msg_line_context: Another one from l3msg which will be altered later.

```

1179 \cs_set_nopar:Npn \msg_line_context:
1180   { on-line~ \tex_the:D \tex_inputlineno:D }
(End definition for \msg_line_context: This function is documented on page 138.)

```

__chk_if_free_cs:N This command is called by \cs_new_nopar:Npn and \cs_new_eq:NN etc. to make sure that the argument sequence is not already in use. If it is, an error is signalled. It checks if *{csname}* is undefined or \scan_stop:. Otherwise an error message is issued. We have to make sure we don't put the argument into the conditional processing since it may be an \if... type function!

```

1181 \cs_set_protected:Npn \__chk_if_free_cs:N #1
1182   {
1183     \cs_if_free:NF #1
1184     {
1185       \__msg_kernel_error:nnxx { kernel } { command-already-defined }
1186       { \token_to_str:N #1 } { \token_to_meaning:N #1 }
1187     }
1188   }
1189 {*package}
1190 \tex_ifodd:D \l@expl@log@functions@bool
1191 \cs_set_protected:Npn \__chk_if_free_cs:N #1
1192   {
1193     \cs_if_free:NF #1
1194     {
1195       \__msg_kernel_error:nnxx { kernel } { command-already-defined }
1196       { \token_to_str:N #1 } { \token_to_meaning:N #1 }
1197     }
1198     \iow_log:x { Defining-\token_to_str:N #1~ \msg_line_context: }
1199   }
1200 \fi:
1201 /package
1202 \cs_set_protected_nopar:Npn \__chk_if_free_cs:c
1203   { \exp_args:Nc \__chk_if_free_cs:N }
(End definition for \__chk_if_free_cs:N and \__chk_if_free_cs:c)

```

__chk_if_exist_cs:N This function issues an error message when the control sequence in its argument does not exist.

```

1204 \cs_set_protected:Npn \__chk_if_exist_cs:N #1
1205   {
1206     \cs_if_exist:NF #1
1207     {

```

```

1208         \_\_msg_kernel_error:nnx { kernel } { command-not-defined }
1209         { \token_to_str:N #1 }
1210     }
1211 }
1212 \cs_set_protected_nopar:Npn \_\_chk_if_exist_cs:c
1213 { \exp_args:Nc \_\_chk_if_exist_cs:N }
(End definition for \_\_chk_if_exist_cs:N and \_\_chk_if_exist_cs:c)

```

3.10 More new definitions

\cs_new_nopar:Npn Function which check that the control sequence is free before defining it.

```

1214 \cs_set:Npn \_\_cs_tmp:w #1#2
1215 {
1216     \cs_set_protected:Npn #1 ##1
1217     {
1218         \_\_chk_if_free_cs:N ##1
1219         #2 ##1
1220     }
1221 }
1222 \_\_cs_tmp:w \cs_new_nopar:Npn           \cs_gset_nopar:Npn
1223 \_\_cs_tmp:w \cs_new_nopar:Npx          \cs_gset_nopar:Npx
1224 \_\_cs_tmp:w \cs_new:Npn                \cs_gset:Npn
1225 \_\_cs_tmp:w \cs_new:Npx                \cs_gset:Npx
1226 \_\_cs_tmp:w \cs_new_protected_nopar:Npn \cs_gset_protected_nopar:Npn
1227 \_\_cs_tmp:w \cs_new_protected_nopar:Npx \cs_gset_protected_nopar:Npx
1228 \_\_cs_tmp:w \cs_new_protected:Npn       \cs_gset_protected:Npn
1229 \_\_cs_tmp:w \cs_new_protected:Npx       \cs_gset_protected:Npx
(End definition for \cs_new_nopar:Npn and others. These functions are documented on page ??.)

```

\cs_set_nopar:cpn Like \cs_set_nopar:Npn and \cs_new_nopar:Npn, except that the first argument consists of the sequence of characters that should be used to form the name of the desired control sequence (the c stands for csname argument, see the expansion module). Global versions are also provided.

\cs_set_nopar:cpn<string><rep-text> will turn <string> into a csname and then assign <rep-text> to it by using \cs_set_nopar:Npn. This means that there might be a parameter string between the two arguments.

```

1230 \cs_set:Npn \_\_cs_tmp:w #1#2
1231 { \cs_new_protected_nopar:Npn #1 { \exp_args:Nc #2 } }
1232 \_\_cs_tmp:w \cs_set_nopar:cpn \cs_set_nopar:Npn
1233 \_\_cs_tmp:w \cs_set_nopar:cpx \cs_set_nopar:Npx
1234 \_\_cs_tmp:w \cs_gset_nopar:cpn \cs_gset_nopar:Npn
1235 \_\_cs_tmp:w \cs_gset_nopar:cpx \cs_gset_nopar:Npx
1236 \_\_cs_tmp:w \cs_new_nopar:cpn \cs_new_nopar:Npn
1237 \_\_cs_tmp:w \cs_new_nopar:cpx \cs_new_nopar:Npx
(End definition for \cs_set_nopar:cpn and others. These functions are documented on page ??.)

```

\cs_set:cpn Variants of the \cs_set:Npn versions which make a csname out of the first arguments. We may also do this globally.

\cs_set:cpx
\cs_gset:cpn
\cs_gset:cpx
\cs_new:cpn
\cs_new:cpx

```

1238 \__cs_tmp:w \cs_set:cpn \cs_set:Npn
1239 \__cs_tmp:w \cs_set:cpx \cs_set:Npx
1240 \__cs_tmp:w \cs_gset:cpn \cs_gset:Npn
1241 \__cs_tmp:w \cs_gset:cpx \cs_gset:Npx
1242 \__cs_tmp:w \cs_new:cpn \cs_new:Npn
1243 \__cs_tmp:w \cs_new:cpx \cs_new:Npx

```

(End definition for `\cs_set:cpn` and others. These functions are documented on page ??.)

```

\cs_set_protected_nopar:cpn
\cs_set_protected_nopar:cpx
\cs_gset_protected_nopar:cpn
\cs_gset_protected_nopar:cpx
\cs_new_protected_nopar:cpn
\cs_new_protected_nopar:cpx

```

Variants of the `\cs_set_protected_nopar:Npn` versions which make a csname out of the first arguments. We may also do this globally.

```

1244 \__cs_tmp:w \cs_set_protected_nopar:cpn \cs_set_protected_nopar:Npn
1245 \__cs_tmp:w \cs_set_protected_nopar:cpx \cs_set_protected_nopar:Npx
1246 \__cs_tmp:w \cs_gset_protected_nopar:cpn \cs_gset_protected_nopar:Npn
1247 \__cs_tmp:w \cs_gset_protected_nopar:cpx \cs_gset_protected_nopar:Npx
1248 \__cs_tmp:w \cs_new_protected_nopar:cpn \cs_new_protected_nopar:Npn
1249 \__cs_tmp:w \cs_new_protected_nopar:cpx \cs_new_protected_nopar:Npx

```

(End definition for `\cs_set_protected_nopar:cpn` and others. These functions are documented on page ??.)

```

\cs_set_protected:cpn
\cs_set_protected:cpx
\cs_gset_protected:cpn
\cs_gset_protected:cpx
\cs_new_protected:cpn
\cs_new_protected:cpx

```

Variants of the `\cs_set_protected:Npn` versions which make a csname out of the first arguments. We may also do this globally.

```

1250 \__cs_tmp:w \cs_set_protected:cpn \cs_set_protected:Npn
1251 \__cs_tmp:w \cs_set_protected:cpx \cs_set_protected:Npx
1252 \__cs_tmp:w \cs_gset_protected:cpn \cs_gset_protected:Npn
1253 \__cs_tmp:w \cs_gset_protected:cpx \cs_gset_protected:Npx
1254 \__cs_tmp:w \cs_new_protected:cpn \cs_new_protected:Npn
1255 \__cs_tmp:w \cs_new_protected:cpx \cs_new_protected:Npx

```

(End definition for `\cs_set_protected:cpn` and others. These functions are documented on page ??.)

3.11 Copying definitions

```

\cs_set_eq:NN
\cs_set_eq:cN
\cs_set_eq:Nc
\cs_set_eq:cc
\cs_gset_eq:NN
\cs_gset_eq:cN
\cs_gset_eq:Nc
\cs_gset_eq:cc
\cs_new_eq:NN
\cs_new_eq:cN
\cs_new_eq:Nc
\cs_new_eq:cc

```

These macros allow us to copy the definition of a control sequence to another control sequence.

The = sign allows us to define funny char tokens like = itself or ↳ with this function. For the definition of `\c_space_char{~}` to work we need the ~ after the =.

`\cs_set_eq:NN` is long to avoid problems with a literal argument of `\par`. While `\cs_new_eq:NN` will probably never be correct with a first argument of `\par`, define it long in order to throw an “already defined” error rather than “runaway argument”.

```

1256 \cs_new_protected:Npn \cs_set_eq:NN #1 { \tex_let:D #1 =~ }
1257 \cs_new_protected_nopar:Npn \cs_set_eq:cN { \exp_args:Nc \cs_set_eq:NN }
1258 \cs_new_protected_nopar:Npn \cs_set_eq:Nc { \exp_args:NNc \cs_set_eq:NN }
1259 \cs_new_protected_nopar:Npn \cs_set_eq:cc { \exp_args:Ncc \cs_set_eq:NN }
1260 \cs_new_protected_nopar:Npn \cs_gset_eq:NN { \tex_global:D \cs_set_eq:NN }
1261 \cs_new_protected_nopar:Npn \cs_gset_eq:Nc { \exp_args:NNc \cs_gset_eq:NN }
1262 \cs_new_protected_nopar:Npn \cs_gset_eq:cN { \exp_args:Nc \cs_gset_eq:NN }
1263 \cs_new_protected_nopar:Npn \cs_gset_eq:cc { \exp_args:Ncc \cs_gset_eq:NN }
1264 \cs_new_protected:Npn \cs_new_eq:NN #1
1265 {

```

```

1266     \__chk_if_free_cs:N #1
1267     \tex_global:D \cs_set_eq:NN #1
1268 }
1269 \cs_new_protected_nopar:Npn \cs_new_eq:cN { \exp_args:Nc \cs_new_eq:NN }
1270 \cs_new_protected_nopar:Npn \cs_new_eq:Nc { \exp_args:NNc \cs_new_eq:NN }
1271 \cs_new_protected_nopar:Npn \cs_new_eq:cc { \exp_args:Ncc \cs_new_eq:NN }
(End definition for \cs_set_eq:NN and others. These functions are documented on page ??.)
```

3.12 Undefining functions

\cs_undefine:N The following function is used to free the main memory from the definition of some function that isn't in use any longer. The **c** variant is careful not to add the control sequence to the hash table if it isn't there yet, and it also avoids nesting **TEX** conditionals in case **#1** is unbalanced in this matter.

```

1272 \cs_new_protected:Npn \cs_undefine:N #1
1273   { \cs_gset_eq:NN #1 \c_undefined:D }
1274 \cs_new_protected:Npn \cs_undefine:c #1
1275   {
1276     \if_cs_exist:w #1 \cs_end:
1277       \exp_after:wN \use:n
1278     \else:
1279       \exp_after:wN \use_none:n
1280     \fi:
1281   { \cs_gset_eq:cN {#1} \c_undefined:D }
1282 }
```

(End definition for \cs_undefine:N and \cs_undefine:c These functions are documented on page ??.)

3.13 Generating parameter text from argument count

__cs_parm_from_arg_count:nnF **__cs_parm_from_arg_count_test:nnF** **LATEX3** provides shorthands to define control sequences and conditionals with a simple parameter text, derived directly from the signature, or more generally from knowing the number of arguments, between 0 and 9. This function expands to its first argument, untouched, followed by a brace group containing the parameter text **{#1...#n}**, where **n** is the result of evaluating the second argument (as described in **\int_eval:n**). If the second argument gives a result outside the range [0, 9], the third argument is returned instead, normally an error message. Some of the functions use here are not defined yet, but will be defined before this function is called.

```

1283 \cs_set_protected:Npn \__cs_parm_from_arg_count:nnF #1#2
1284   {
1285     \exp_args:Nx \__cs_parm_from_arg_count_test:nnF
1286     {
1287       \exp_after:wN \exp_not:n
1288       \if_case:w \__int_eval:w #2 \__int_eval_end:
1289         { }
1290       \or: { ##1 }
1291       \or: { ##1##2 }
1292       \or: { ##1##2##3 }
1293       \or: { ##1##2##3##4 }
```

```

1294     \or: { ##1##2##3##4##5 }
1295     \or: { ##1##2##3##4##5##6 }
1296     \or: { ##1##2##3##4##5##6##7 }
1297     \or: { ##1##2##3##4##5##6##7##8 }
1298     \or: { ##1##2##3##4##5##6##7##8##9 }
1299     \else: { \c_false_bool }
1300     \fi:
1301   }
1302   {#1}
1303 }
1304 \cs_set_protected:Npn \__cs_parm_from_arg_count_test:nnF #1#2
1305 {
1306   \if_meaning:w \c_false_bool #1
1307     \exp_after:wN \use_ii:nn
1308   \else:
1309     \exp_after:wN \use_i:nn
1310   \fi:
1311   { #2 {#1} }
1312 }

```

(End definition for `__cs_parm_from_arg_count:nnF` This function is documented on page ??.)

3.14 Defining functions from a given number of arguments

`__cs_count_signature:N`
`__cs_count_signature:c`
`__cs_count_signature:nnN`

Counting the number of tokens in the signature, *i.e.*, the number of arguments the function should take. Since this is not used in any time-critical function, we simply use `\tl_count:n` if there is a signature, otherwise `-1` arguments to signal an error. We need a variant form right away.

```

1313 \cs_new:Npn \__cs_count_signature:N #1
1314   { \int_eval:n { \__cs_split_function:NN #1 \__cs_count_signature:nnN } }
1315 \cs_new:Npn \__cs_count_signature:nnN #1#2#3
1316   {
1317     \if_meaning:w \c_true_bool #3
1318       \tl_count:n {#2}
1319     \else:
1320       \c_minus_one
1321     \fi:
1322   }
1323 \cs_new_nopar:Npn \__cs_count_signature:c
1324   { \exp_args:Nc \__cs_count_signature:N }

```

(End definition for `__cs_count_signature:N` and `__cs_count_signature:c` These functions are documented on page ??.)

`\cs_generate_from_arg_count:NNnn`
`\cs_generate_from_arg_count:cNnn`
`\cs_generate_from_arg_count:Ncnn`

We provide a constructor function for defining functions with a given number of arguments. For this we need to choose the correct parameter text and then use that when defining. Since \TeX supports from zero to nine arguments, we use a simple switch to choose the correct parameter text, ensuring the result is returned after finishing the conditional. If it is not between zero and nine, we throw an error.

1: function to define, 2: with what to define it, 3: the number of args it requires and 4: the replacement text

```

1325 \cs_new_protected:Npn \cs_generate_from_arg_count:NNnn #1#2#3#4
1326 {
1327     \__cs_parm_from_arg_count:nnF { \use:n nn #2 #1 } {#3}
1328     {
1329         \__msg_kernel_error:nnxx { kernel } { bad-number-of-arguments }
1330         { \token_to_str:N #1 } { \int_eval:n {#3} }
1331     }
1332     {#4}
1333 }
```

A variant form we need right away, plus one which is used elsewhere but which is most logically created here.

```

1334 \cs_new_protected_nopar:Npn \cs_generate_from_arg_count:cNnn
1335     { \exp_args:Nc \cs_generate_from_arg_count:NNnn }
1336 \cs_new_protected_nopar:Npn \cs_generate_from_arg_count:Ncnn
1337     { \exp_args:Nnc \cs_generate_from_arg_count:NNnn }
(End definition for \cs_generate_from_arg_count:NNnn, \cs_generate_from_arg_count:cNnn, and
\cs_generate_from_arg_count:Ncnn These functions are documented on page ??.)
```

3.15 Using the signature to define functions

We can now combine some of the tools we have to provide a simple interface for defining functions. We define some simpler functions with user interface `\cs_set:Nn \foo_bar:nn {#1,#2}`, i.e., the number of arguments is read from the signature.

We want to define `\cs_set:Nn` as

```

\cs_set:Nn
\cs_set:Nx
\cs_set_nopar:Nn
\cs_set_nopar:Nx
\cs_set_protected:Nn
\cs_set_protected:Nx
\cs_set_protected_nopar:Nn
\cs_set_protected_nopar:Nx
    \cs_gset:Nn
    \cs_gset:Nx
\cs_gset_nopar:Nn
\cs_gset_nopar:Nx
\cs_gset_protected:Nn
\cs_gset_protected:Nx
\cs_gset_protected_nopar:Nn
\cs_gset_protected_nopar:Nx
    \cs_new:Nn
    \cs_new:Nx
\cs_new_nopar:Nn
\cs_new_nopar:Nx
\cs_new_protected:Nn
\cs_new_protected:Nx
\cs_new_protected_nopar:Nn
\cs_new_protected_nopar:Nx
```

In short, to define `\cs_set:Nn` we need just use `\cs_set:Npn`, everything else is the same for each variant. Therefore, we can make it simpler by temporarily defining a function to do this for us.

```

1338 \cs_set:Npn \__cs_tmp:w #1#2#3
1339 {
1340     \cs_new_protected_nopar:cp { cs_ #1 : #2 }
1341     {
1342         \exp_not:N \__cs_generate_from_signature:NNn
1343         \exp_after:wN \exp_not:N \cs:w cs_ #1 : #3 \cs_end:
1344     }
1345 }
1346 \cs_new_protected:Npn \__cs_generate_from_signature:NNn #1#2
1347 {
1348     \__cs_split_function>NN #2 \__cs_generate_from_signature:nnNNn
```

```

1349      #1 #2
1350    }
1351 \cs_new_protected:Npn \__cs_generate_from_signature:nnNNNn #1#2#3#4#5#6
1352 {
1353   \bool_if:NTF #3
1354   {
1355     \cs_generate_from_arg_count>NNnn
1356     #5 #4 { \tl_count:n {#2} } {#6}
1357   }
1358   {
1359     \__msg_kernel_error:nnx { kernel } { missing-colon }
1360     { \token_to_str:N #5 }
1361   }
1362 }
```

Then we define the 24 variants beginning with N.

```

1363 \__cs_tmp:w { set }           { Nn } { Npn }
1364 \__cs_tmp:w { set }           { Nx } { Npx }
1365 \__cs_tmp:w { set_nopar }     { Nn } { Npn }
1366 \__cs_tmp:w { set_nopar }     { Nx } { Npx }
1367 \__cs_tmp:w { set_protected } { Nn } { Npn }
1368 \__cs_tmp:w { set_protected } { Nx } { Npx }
1369 \__cs_tmp:w { set_protected_nopar } { Nn } { Npn }
1370 \__cs_tmp:w { set_protected_nopar } { Nx } { Npx }
1371 \__cs_tmp:w { gset }          { Nn } { Npn }
1372 \__cs_tmp:w { gset }          { Nx } { Npx }
1373 \__cs_tmp:w { gset_nopar }    { Nn } { Npn }
1374 \__cs_tmp:w { gset_nopar }    { Nx } { Npx }
1375 \__cs_tmp:w { gset_protected } { Nn } { Npn }
1376 \__cs_tmp:w { gset_protected } { Nx } { Npx }
1377 \__cs_tmp:w { gset_protected_nopar } { Nn } { Npn }
1378 \__cs_tmp:w { gset_protected_nopar } { Nx } { Npx }
1379 \__cs_tmp:w { new }           { Nn } { Npn }
1380 \__cs_tmp:w { new }           { Nx } { Npx }
1381 \__cs_tmp:w { new_nopar }     { Nn } { Npn }
1382 \__cs_tmp:w { new_nopar }     { Nx } { Npx }
1383 \__cs_tmp:w { new_protected } { Nn } { Npn }
1384 \__cs_tmp:w { new_protected } { Nx } { Npx }
1385 \__cs_tmp:w { new_protected_nopar } { Nn } { Npn }
1386 \__cs_tmp:w { new_protected_nopar } { Nx } { Npx }
```

(End definition for \cs_set:Nn and others. These functions are documented on page ??.)

\cs_set:cn \cs_set:cx \cs_set_nopar:cn \cs_set_nopar:cx \cs_set_protected:cn \cs_set_protected:cx \cs_set_protected_nopar:cn \cs_set_protected_nopar:cx \cs_gset:cn \cs_gset:cx \cs_gset_nopar:cn \cs_gset_nopar:cx \cs_gset_protected:cn \cs_gset_protected:cx \cs_gset_protected_nopar:cn \cs_gset_protected_nopar:cx \cs_new:cn \cs_new:cx	The 24 c variants simply use \exp_args:Nc. 1387 \cs_set:Npn __cs_tmp:w #1#2 1388 { 1389 \cs_new_protected_nopar:cpx { cs_ #1 : c #2 } 1390 { 1391 \exp_not:N \exp_args:Nc 1392 \exp_after:wN \exp_not:N \cs:w cs_ #1 : N #2 \cs_end: 1393 }
--	--

```

1394   }
1395   \_\_cs\_tmp:w { set }           { n }
1396   \_\_cs\_tmp:w { set }           { x }
1397   \_\_cs\_tmp:w { set\_nopar }    { n }
1398   \_\_cs\_tmp:w { set\_nopar }    { x }
1399   \_\_cs\_tmp:w { set\_protected } { n }
1400   \_\_cs\_tmp:w { set\_protected } { x }
1401   \_\_cs\_tmp:w { set\_protected\_nopar } { n }
1402   \_\_cs\_tmp:w { set\_protected\_nopar } { x }
1403   \_\_cs\_tmp:w { gset }          { n }
1404   \_\_cs\_tmp:w { gset }          { x }
1405   \_\_cs\_tmp:w { gset\_nopar }   { n }
1406   \_\_cs\_tmp:w { gset\_nopar }   { x }
1407   \_\_cs\_tmp:w { gset\_protected } { n }
1408   \_\_cs\_tmp:w { gset\_protected } { x }
1409   \_\_cs\_tmp:w { gset\_protected\_nopar } { n }
1410   \_\_cs\_tmp:w { gset\_protected\_nopar } { x }
1411   \_\_cs\_tmp:w { new }          { n }
1412   \_\_cs\_tmp:w { new }          { x }
1413   \_\_cs\_tmp:w { new\_nopar }    { n }
1414   \_\_cs\_tmp:w { new\_nopar }    { x }
1415   \_\_cs\_tmp:w { new\_protected } { n }
1416   \_\_cs\_tmp:w { new\_protected } { x }
1417   \_\_cs\_tmp:w { new\_protected\_nopar } { n }
1418   \_\_cs\_tmp:w { new\_protected\_nopar } { x }

(End definition for \cs_set:cn and others. These functions are documented on page ??.)
```

3.16 Checking control sequence equality

\cs_if_eq_p:NN

Check if two control sequences are identical.

```

1419 \prg_new_conditional:Npnn \cs_if_eq:NN #1#2 { p , T , F , TF }
1420   {
1421     \if_meaning:w #1#2
1422       \prg_return_true: \else: \prg_return_false: \fi:
1423   }
1424 \cs_new_nopar:Npn \cs_if_eq_p:cN { \exp_args:Nc \cs_if_eq_p:NN }
1425 \cs_new_nopar:Npn \cs_if_eq:cNTF { \exp_args:Nc \cs_if_eq:NNTF }
1426 \cs_new_nopar:Npn \cs_if_eq:cNT { \exp_args:Nc \cs_if_eq:NNT }
1427 \cs_new_nopar:Npn \cs_if_eq:cNF { \exp_args:Nc \cs_if_eq:NNF }
1428 \cs_new_nopar:Npn \cs_if_eq_p:Nc { \exp_args:NNc \cs_if_eq_p:NN }
1429 \cs_new_nopar:Npn \cs_if_eq:NcTF { \exp_args:NNc \cs_if_eq:NNTF }
1430 \cs_new_nopar:Npn \cs_if_eq:NcT { \exp_args:NNc \cs_if_eq:NNT }
1431 \cs_new_nopar:Npn \cs_if_eq:NcF { \exp_args:NNc \cs_if_eq:NNF }
1432 \cs_new_nopar:Npn \cs_if_eq_p:cc { \exp_args:Ncc \cs_if_eq_p:NN }
1433 \cs_new_nopar:Npn \cs_if_eq:cctF { \exp_args:Ncc \cs_if_eq:NNTF }
1434 \cs_new_nopar:Npn \cs_if_eq:cct { \exp_args:Ncc \cs_if_eq:NNT }
1435 \cs_new_nopar:Npn \cs_if_eq:ccF { \exp_args:Ncc \cs_if_eq:NNF }
```

(End definition for \cs_if_eq:NN and others. These functions are documented on page ??.)

3.17 Diagnostic functions

`__kernel_register_show:N` Check that the variable exists, then apply the `\showthe` primitive to the variable. The odd-looking `\use:n` gives a nicer output.

```

1436 \cs_new_protected:Npn \__kernel_register_show:N #1
1437 {
1438   \cs_if_exist:NTF #1
1439   {
1440     \tex_showthe:D \use:n {#1}
1441   }
1442   \__msg_kernel_error:nnx { kernel } { variable-not-defined }
1443   {
1444     \token_to_str:N #1
1445   }
1446 \cs_new_protected_nopar:Npn \__kernel_register_show:c
1447 {
1448   \exp_args:Nc \__kernel_register_show:N
(End definition for \__kernel_register_show:N and \__kernel_register_show:c)

```

`\cs_show:N` Some control sequences have a very long name or meaning. Thus, simply using TeX's primitive `\show` could lead to overlong lines. The output of this primitive is mimicked to some extent: a line-break is added after the first colon in the meaning (this is what TeX does for macros and five `\...mark` primitives). Then the re-built string is given to `\iow_wrap:nnN` for line-wrapping. The `\cs_show:c` command converts its argument to a control sequence within a group to avoid showing `\relax` for undefined control sequences.

```

1447 \group_begin:
1448   \tex_lccode:D ‘? = ‘: \scan_stop:
1449   \tex_catcode:D ‘? = 12 \scan_stop:
1450   \tex_lowercase:D
1451   {
1452     \group_end:
1453     \cs_new_protected:Npn \cs_show:N #1
1454     {
1455       \__msg_show_variable:n
1456       {
1457         > ~ \token_to_str:N #1 =
1458         \exp_after:wN \__cs_show:www \cs_meaning:N #1
1459         \use_none:nn ? \prg_do_nothing:
1460       }
1461     }
1462     \cs_new:Npn \__cs_show:www #1 ? { #1 ? \\ }
1463   }
1464 \cs_new_protected_nopar:Npn \cs_show:c
1465 {
1466   \group_begin: \exp_args:NNc \group_end: \cs_show:N
(End definition for \cs_show:N and \cs_show:c These functions are documented on page ??.)
```

3.18 Engine specific definitions

`\xetex_if_engine_p:` In some cases it will be useful to know which engine we're running. This can all be hard-coded for speed.

`\luatex_if_engine_p:`
`\pdftex_if_engine_p:`
`\xetex_if_engine:TF`
`\luatex_if_engine:TF`
`\pdftex_if_engine:TF`

```

1466 \cs_new_eq:NN \lualatex_if_engine:T \use:none:n
1467 \cs_new_eq:NN \lualatex_if_engine:F \use:n
1468 \cs_new_eq:NN \lualatex_if_engine:TF \use:ii:nn
1469 \cs_new_eq:NN \pdfTeX_if_engine:T \use:n
1470 \cs_new_eq:NN \pdfTeX_if_engine:F \use:none:n
1471 \cs_new_eq:NN \pdfTeX_if_engine:TF \use:i:nn
1472 \cs_new_eq:NN \xetex_if_engine:T \use:none:n
1473 \cs_new_eq:NN \xetex_if_engine:F \use:n
1474 \cs_new_eq:NN \xetex_if_engine:TF \use:ii:nn
1475 \cs_new_eq:NN \lualatex_if_engine_p: \c_false_bool
1476 \cs_new_eq:NN \pdfTeX_if_engine_p: \c_true_bool
1477 \cs_new_eq:NN \xetex_if_engine_p: \c_false_bool
1478 \cs_if_exist:NT \xetex_XeTeXversion:D
1479 {
1480     \cs_gset_eq:NN \pdfTeX_if_engine:T \use:none:n
1481     \cs_gset_eq:NN \pdfTeX_if_engine:F \use:n
1482     \cs_gset_eq:NN \pdfTeX_if_engine:TF \use:ii:nn
1483     \cs_gset_eq:NN \xetex_if_engine:T \use:n
1484     \cs_gset_eq:NN \xetex_if_engine:F \use:none:n
1485     \cs_gset_eq:NN \xetex_if_engine:TF \use:i:nn
1486     \cs_gset_eq:NN \pdfTeX_if_engine_p: \c_false_bool
1487     \cs_gset_eq:NN \xetex_if_engine_p: \c_true_bool
1488 }
1489 \cs_if_exist:NT \lualatex_directlua:D
1490 {
1491     \cs_gset_eq:NN \lualatex_if_engine:T \use:n
1492     \cs_gset_eq:NN \lualatex_if_engine:F \use:none:n
1493     \cs_gset_eq:NN \lualatex_if_engine:TF \use:i:nn
1494     \cs_gset_eq:NN \pdfTeX_if_engine:T \use:none:n
1495     \cs_gset_eq:NN \pdfTeX_if_engine:F \use:n
1496     \cs_gset_eq:NN \pdfTeX_if_engine:TF \use:ii:nn
1497     \cs_gset_eq:NN \lualatex_if_engine_p: \c_true_bool
1498     \cs_gset_eq:NN \pdfTeX_if_engine_p: \c_false_bool
1499 }
(End definition for \xetex_if_engine:, \lualatex_if_engine:, and \pdfTeX_if_engine: These functions are documented on page 22.)
```

3.19 Doing nothing functions

\prg_do_nothing: This does not fit anywhere else!

```
1500 \cs_new_nopar:Npn \prg_do_nothing: { }
```

(End definition for \prg_do_nothing: This function is documented on page 9.)

3.20 String comparisons

```

\str_if_eq_p:nn
\str_if_eq_x_p:nn
\str_if_eq:nnTF
\str_if_eq_x:nnTF
```

Modern engines provide a direct way of comparing two token lists, but returning a number. This set of conditionals therefore make life a bit clearer. The nn and xx versions are created directly as this is most efficient. These should eventually move somewhere else.

```

1501 \prg_new_if:n {#1} {#2} { p , T , F , TF }
1502 {
1503   \if_int_compare:w \pdftex_strcmp:D { \exp_not:n {#1} } { \exp_not:n {#2} }
1504     = \c_zero
1505   \prg_return_true: \else: \prg_return_false: \fi:
1506 }
1507 \prg_new_if:x {#1} {#2} { p , T , F , TF }
1508 {
1509   \if_int_compare:w \pdftex_strcmp:D {#1} {#2} = \c_zero
1510   \prg_return_true: \else: \prg_return_false: \fi:
1511 }

```

(End definition for `\str_if_eq:nn` and `\str_if_eq_x:nn`. These functions are documented on page 21.)

`__str_if_eq_x_return:nn`

It turns out that we often need to compare a token list with the result of applying some function to it, and return with `\prg_return_true/false:`. This test is similar to `\str_if_eq:nnTF`, but hard-coded for speed.

```

1512 \cs_new:Npn \__str_if_eq_x_return:nn {#1} {#2}
1513 {
1514   \if_int_compare:w \pdftex_strcmp:D {#1} {#2} = \c_zero
1515   \prg_return_true:
1516 \else:
1517   \prg_return_false:
1518 \fi:
1519 }

```

(End definition for `__str_if_eq_x_return:nn`)

`\str_case:nnn`

`\str_case_x:nnn`

`__prg_case_end:nw`

`__str_case:nw`

`__str_case_x:nw`

`__str_case_end:nw`

No calculations for strings, otherwise no surprises.

```

1520 \cs_new:Npn \str_case:nnn {#1} {#2} {#3}
1521 {
1522   \tex_roman numeral:D
1523   \__str_case:nw {#1} {#2} {#3} \q_recursion_stop
1524 }
1525 \cs_new:Npn \__str_case:nw {#1} {#2} {#3}
1526 {
1527   \str_if_eq:nnTF {#1} {#2}
1528   { \__str_case_end:nw {#3} }
1529   { \__str_case:nw {#1} }
1530 }
1531 \cs_new:Npn \str_case_x:nnn {#1} {#2} {#3}
1532 {
1533   \tex_roman numeral:D
1534   \__str_case_x:nw {#1} {#2} {#3} \q_recursion_stop
1535 }
1536 \cs_new:Npn \__str_case_x:nw {#1} {#2} {#3}
1537 {
1538   \str_if_eq_x:nnTF {#1} {#2}
1539   { \__str_case_end:nw {#3} }
1540   { \__str_case_x:nw {#1} }
1541 }

```

Here, #1 will be the code needed, #2 will be any remaining case or cases, and the `\c_zero` stops the `\romannumeral`.

```
1542 \cs_new:Npn \__prg_case_end:nw #1#2 \q_recursion_stop { \c_zero #1 }
1543 \cs_new_eq:NN \__str_case_end:nw \__prg_case_end:nw
(End definition for \str_case:nnn and \str_case_x:nnn These functions are documented on page 24.)
```

3.21 Breaking out of mapping functions

`__prg_break_point:Nn`
`__prg_map_break:Nn`

In inline mappings, the nesting level must be reset at the end of the mapping, even when the user decides to break out. This is done by putting the code that must be performed as an argument of `__prg_break_point:Nn`. The breaking functions are then defined to jump to that point and perform the argument of `__prg_break_point:Nn`, before the user's code (if any). There is a check that we close the correct loop, otherwise we continue breaking.

```
1544 \cs_new_eq:NN \__prg_break_point:Nn \use_ii:nn
1545 \cs_new:Npn \__prg_map_break:Nn #1#2#3 \__prg_break_point:Nn #4#5
1546 {
1547   #5
1548   \if_meaning:w #1 #4
1549     \exp_after:wN \use_iii:nn
1550   \fi:
1551   \__prg_map_break:Nn #1 {#2}
1552 }
```

(End definition for `__prg_break_point:Nn` and `__prg_map_break:Nn` These functions are documented on page 42.)

`__prg_break_point:`
`__prg_break:`
`__prg_break:n`

Very simple analogues of `__prg_break_point:Nn` and `__prg_map_break:Nn`, for use in fast short-term recursions which are not mappings, do not need to support nesting, and in which nothing has to be done at the end of the loop.

```
1553 \cs_new_eq:NN \__prg_break_point: \prg_do_nothing:
1554 \cs_new:Npn \__prg_break: #1 \__prg_break_point: { }
1555 \cs_new:Npn \__prg_break:n #1#2 \__prg_break_point: {#1}
(End definition for \__prg_break_point: This function is documented on page ??.)
```

3.22 Deprecated functions

Deprecated on 2011-05-27, for removal by 2011-08-31.

```
1556 {*deprecated}
1557 \cs_new_eq:NN \cs_gnew_nopar:Npn \cs_new_nopar:Npn
1558 \cs_new_eq:NN \cs_gnew:Npn \cs_new:Npn
1559 \cs_new_eq:NN \cs_gnew_protected_nopar:Npn \cs_new_protected_nopar:Npn
1560 \cs_new_eq:NN \cs_gnew_protected:Npn \cs_new_protected:Npn
1561 \cs_new_eq:NN \cs_gnew_nopar:Npx \cs_new_nopar:Npx
1562 \cs_new_eq:NN \cs_gnew:Npx \cs_new:Npx
1563 \cs_new_eq:NN \cs_gnew_protected_nopar:Npx \cs_new_protected_nopar:Npx
1564 \cs_new_eq:NN \cs_gnew_protected:Npx \cs_new_protected:Npx
1565 \cs_new_eq:NN \cs_gnew_nopar:cpn \cs_new_nopar:cpn
```

```

1566 \cs_new_eq:NN          \cs_gnew:cpn          \cs_new:cpn
1567 \cs_new_eq:NN \cs_gnew_protected_nopar:cpn \cs_new_protected_nopar:cpn \cs_new_protected:cpn
1568 \cs_new_eq:NN          \cs_gnew_protected:cpn \cs_new_protected:cpx
1569 \cs_new_eq:NN          \cs_gnew_nopar:cpx \cs_new_nopar:cpx
1570 \cs_new_eq:NN          \cs_gnew:cpx          \cs_new:cpx
1571 \cs_new_eq:NN \cs_gnew_protected_nopar:cpx \cs_new_protected_nopar:cpx \cs_new_protected:cpx
1572 \cs_new_eq:NN          \cs_gnew_protected:cpx \cs_new_protected:cpx
1573 </deprecated>

1574 <*deprecated>
1575 \cs_new_eq:NN \cs_gnew_eq:NN \cs_new_eq:NN \cs_new:cnpn
1576 \cs_new_eq:NN \cs_gnew_eq:cN \cs_new_eq:cN \cs_new:cnpn
1577 \cs_new_eq:NN \cs_gnew_eq:Nc \cs_new_eq:Nc \cs_new:cnpn
1578 \cs_new_eq:NN \cs_gnew_eq:cc \cs_new_eq:cc \cs_new:cnpn
1579 </deprecated>

1580 <*deprecated>
1581 \cs_new_eq:NN \cs_gundefine:N \cs_undefine:N \cs_new:cnpn
1582 \cs_new_eq:NN \cs_gundefine:c \cs_undefine:c \cs_new:cnpn
1583 </deprecated>

1584 <*deprecated>
1585 \cs_new_eq:NN \group_execute_after:N \group_insert_after:N \cs_new:cnpn
1586 </deprecated>

```

Deprecated 2011-09-06, for removal by 2011-12-31.

\c_pdftex_is_engine_bool
\c_luatex_is_engine_bool
\c_xetex_is_engine_bool

Predicates are better

```

1587 <*deprecated>
1588 \cs_new_eq:NN \c_luatex_is_engine_bool \luatex_if_engine_p:
1589 \cs_new_eq:NN \c_pdftex_is_engine_bool \pdftex_if_engine_p:
1590 \cs_new_eq:NN \c_xetex_is_engine_bool \xetex_if_engine_p:
1591 </deprecated>

```

(End definition for \c_pdftex_is_engine_bool, \c_luatex_is_engine_bool, and \c_xetex_is_engine_bool
These variables are documented on page ??.)

\use_i_after_fi:nw
\use_i_after_else:nw
\use_i_after_or:nw
\use_i_after_orelse:nw

These functions return the first argument after ending the conditional. This is rather specialized, and we want to de-emphasize the use of primitive T_EX conditionals.

```

1592 <*deprecated>
1593 \cs_set:Npn \use_i_after_fi:nw #1 \fi: { \fi: #1 }
1594 \cs_set:Npn \use_i_after_else:nw #1 \else: #2 \fi: { \fi: #1 }
1595 \cs_set:Npn \use_i_after_or:nw #1 \or: #2 \fi: { \fi: #1 }
1596 \cs_set:Npn \use_i_after_orelse:nw #1#2#3 \fi: { \fi: #1 }
1597 </deprecated>

```

(End definition for \use_i_after_fi:nw and others. These functions are documented on page ??.)

Deprecated 2011-09-07, for removal by 2011-12-31.

```

\cs_set_eq:NwN
1598 <*deprecated>
1599 \tex_let:D \cs_set_eq:NwN \tex_let:D
1600 </deprecated>

```

(End definition for \cs_set_eq:NwN This function is documented on page ??.)
Deprecated 2012-06-05 for removal after 2012-12-31.

```
\str_if_eq_p:xx Not really true x-type expansion
\str_if_eq:xxTF
 1601 \cs_new_eq:NN \str_if_eq_p:xx \str_if_eq_x_p:nn
 1602 \cs_new_eq:NN \str_if_eq:xxT \str_if_eq_x:nnT
 1603 \cs_new_eq:NN \str_if_eq:xxF \str_if_eq_x:nnF
 1604 \cs_new_eq:NN \str_if_eq:xxTF \str_if_eq_x:nnTF
(End definition for \str_if_eq:xx These functions are documented on page ??.)
```

```
\chk_if_free_cs:N
 1605 \cs_new_eq:NN \chk_if_free_cs:N \__chk_if_free_cs:N
(End definition for \chk_if_free_cs:N This function is documented on page ??.)
 1606 ⟨/initex | package⟩
```

4 l3expansion implementation

```
1607 ⟨*initex | package⟩
1608 ⟨@@=exp⟩
```

We start by ensuring that the required packages are loaded.

```
1609 ⟨*package⟩
1610 \ProvidesExplPackage
1611   { \ExplFileName } { \ExplFileVersion } { \ExplFileDescription }
1612 \__expl_package_check:
1613 ⟨/package⟩
```

\exp_after:wN
These are defined in l3basics.
(End definition for \exp_after:wN This function is documented on page 32.)
\exp_not:N
\exp_not:n

4.1 General expansion

In this section a general mechanism for defining functions to handle argument handling is defined. These general expansion functions are expandable unless x is used. (Any version of x is going to have to use one of the L^AT_EX3 names for \cs_set_nopar:Npx at some point, and so is never going to be expandable.)

The definition of expansion functions with this technique happens in section 4.3. In section 4.2 some common cases are coded by a more direct method for efficiency, typically using calls to \exp_after:wN.

\l__exp_internal_t1
This scratch token list variable is defined in l3basics, as it is needed “early”. This is just a reminder that that is the case!
(End definition for \l__exp_internal_t1 This variable is documented on page 33.)

This code uses internal functions with names that start with \::: to perform the expansions. All macros are long as this turned out to be desirable since the tokens undergoing expansion may be arbitrary user input.

An argument manipulator \:::(Z) always has signature #1\:::#2#3 where #1 holds the remaining argument manipulations to be performed, \::: serves as an end marker

for the list of manipulations, #2 is the carried over result of the previous expansion steps and #3 is the argument about to be processed. One exception to this rule is `\:::p`, which has to grab an argument delimited by a left brace.

`_exp_arg_next:nnn` `_exp_arg_next:Nnn` #1 is the result of an expansion step, #2 is the remaining argument manipulations and #3 is the current result of the expansion chain. This auxiliary function moves #1 back after #3 in the input stream and checks if any expansion is left to be done by calling #2. In by far the most cases we will require to add a set of braces to the result of an argument manipulation so it is more effective to do it directly here. Actually, so far only the c of the final argument manipulation variants does not require a set of braces.

```
1614 \cs_new:Npn \_exp_arg_next:nnn #1#2#3 { #2 \::: { #3 {#1} } }
1615 \cs_new:Npn \_exp_arg_next:Nnn #1#2#3 { #2 \::: { #3 #1 } }
(End definition for \_exp_arg_next:nnn) This function is documented on page 33.)
```

`\:::` The end marker is just another name for the identity function.

```
1616 \cs_new:Npn \::: #1 {#1}
(End definition for \:::)
```

`\:::n` This function is used to skip an argument that doesn't need to be expanded.

```
1617 \cs_new:Npn \:::n #1 \::: #2#3 { #1 \::: { #2 {#3} } }
(End definition for \:::n)
```

`\:::N` This function is used to skip an argument that consists of a single token and doesn't need to be expanded.

```
1618 \cs_new:Npn \:::N #1 \::: #2#3 { #1 \::: {#2#3} }
(End definition for \:::N)
```

`\:::p` This function is used to skip an argument that is delimited by a left brace and doesn't need to be expanded. It should not be wrapped in braces in the result.

```
1619 \cs_new:Npn \:::p #1 \::: #2#3# { #1 \::: {#2#3} }
(End definition for \:::p)
```

`\:::c` This function is used to skip an argument that is turned into a control sequence without expansion.

```
1620 \cs_new:Npn \:::c #1 \::: #2#3
1621 { \exp_after:wN \_exp_arg_next:Nnn \cs:w #3 \cs_end: {#1} {#2} }
(End definition for \:::c)
```

`\:::o` This function is used to expand an argument once.

```
1622 \cs_new:Npn \:::o #1 \::: #2#3
1623 { \exp_after:wN \_exp_arg_next:nnn \exp_after:wN {#3} {#1} {#2} }
(End definition for \:::o)
```

\:::f This function is used to expand a token list until the first unexpandable token is found. The underlying `\romannumeral -'0` expands everything in its way to find something terminating the number and thereby expands the function in front of it. This scanning procedure is terminated once the expansion hits something non-expandable or a space. We introduce `\exp_stop_f`: to mark such an end of expansion marker; in case the scanner hits a number, this number also terminates the scanning and is left untouched. In the example shown earlier the scanning was stopped once TeX had fully expanded `\cs_set_eq:Nc \aaa { b \l_tmpa_tl b }` into `\cs_set_eq:NN \aaa = \blurb` which then turned out to contain the non-expandable token `\cs_set_eq:NN`. Since the expansion of `\romannumeral -'0` is `<null>`, we wind up with a fully expanded list, only TeX has not tried to execute any of the non-expandable tokens. This is what differentiates this function from the `x` argument type.

```

1624 \cs_new:Npn \:::f #1 \::: #2#3
1625 {
1626   \exp_after:wN \__exp_arg_next:nnn
1627     \exp_after:wN { \tex_roman numeral:D -'0 #3 }
1628     {#1} {#2}
1629 }
1630 \use:nn { \cs_new_eq:NN \exp_stop_f: } { ~ }
(End definition for \:::f This function is documented on page 32.)
```

\:::x This function is used to expand an argument fully.

```

1631 \cs_new_protected:Npn \:::x #1 \::: #2#3
1632 {
1633   \cs_set_nopar:Npx \l__exp_internal_tl { {#3} }
1634   \exp_after:wN \__exp_arg_next:nnn \l__exp_internal_tl {#1} {#2}
1635 }
(End definition for \:::x)
```

\:::v These functions return the value of a register, i.e., one of `tl`, `clist`, `int`, `skip`, `dim` and `muskip`. The `V` version expects a single token whereas `v` like `c` creates a csname from its argument given in braces and then evaluates it as if it was a `V`. The primitive `\romannumeral` sets off an expansion similar to an `f` type expansion, which we will terminate using `\c_zero`. The argument is returned in braces.

```

1636 \cs_new:Npn \:::V #1 \::: #2#3
1637 {
1638   \exp_after:wN \__exp_arg_next:nnn
1639     \exp_after:wN { \tex_roman numeral:D \__exp_eval_register:N #3 }
1640     {#1} {#2}
1641 }
1642 \cs_new:Npn \:::v # 1\::: #2#3
1643 {
1644   \exp_after:wN \__exp_arg_next:nnn
1645     \exp_after:wN { \tex_roman numeral:D \__exp_eval_register:c {#3} }
1646     {#1} {#2}
1647 }
(End definition for \:::v This function is documented on page 33.)
```

`__exp_eval_register:N` This function evaluates a register. Now a register might exist as one of two things: A parameter-less macro or a built-in TeX register such as `\count`. For the TeX registers we have to utilize a `\the` whereas for the macros we merely have to expand them once. The trick is to find out when to use `\the` and when not to. What we do here is try to find out whether the token will expand to something else when hit with `\exp_after:wN`. The technique is to compare the meaning of the register in question when it has been prefixed with `\exp_not:N` and the register itself. If it is a macro, the prefixed `\exp_not:N` will temporarily turn it into the primitive `\scan_stop:`.

```

1648 \cs_new:Npn \__exp_eval_register:N #1
1649 {
1650   \exp_after:wN \if_meaning:w \exp_not:N #1 #1

```

If the token was not a macro it may be a malformed variable from a `c` expansion in which case it is equal to the primitive `\scan_stop:`. In that case we throw an error. We could let TeX do it for us but that would result in the rather obscure

```
! You can't use '\relax' after \the.
```

which while quite true doesn't give many hints as to what actually went wrong. We provide something more sensible.

```

1651   \if_meaning:w \scan_stop: #1
1652     \__exp_eval_error_msg:w
1653   \fi:

```

The next bit requires some explanation. The function must be initiated by the primitive `\romannumeral` and we want to terminate this expansion chain by inserting the `\c_zero` integer constant. However, we have to expand the register `#1` before we do that. If it is a TeX register, we need to execute the sequence `\exp_after:wN \c_zero \tex_the:D #1` and if it is a macro we need to execute `\exp_after:wN \c_zero #1`. We therefore issue the longer of the two sequences and if the register is a macro, we remove the `\tex_the:D`.

```

1654   \else:
1655     \exp_after:wN \use_i_i:nnn
1656   \fi:
1657   \exp_after:wN \c_zero \tex_the:D #1
1658 }
1659 \cs_new:Npn \__exp_eval_register:c #1
1660   { \exp_after:wN \__exp_eval_register:N \cs:w #1 \cs_end: }

```

Clean up nicely, then call the undefined control sequence. The result is an error message looking like this:

```

! Undefined control sequence.
<argument> \LaTeX3 error:
                                              Erroneous variable used!
1.55 \tl_set:Nv \l_tmpa_tl {undefined_t1}

1661 \cs_new:Npn \__exp_eval_error_msg:w #1 \tex_the:D #2
1662 {
1663   \fi:
1664 \fi:

```

```

1665     \__msg_kernel_expandable_error:nnn { kernel } { bad-variable } {#2}
1666     \c_zero
1667 }
(End definition for \_exp_eval_register:N and \_exp_eval_register:c These functions are documented on page ??.)
```

4.2 Hand-tuned definitions

One of the most important features of these functions is that they are fully expandable and therefore allow to prefix them with \tex_global:D for example.

```

\exp_args:N
\exp_args:NNo
\exp_args:NNNo
Those lovely runs of expansion!
1668 \cs_new:Npn \exp_args:N #1#2 { \exp_after:wN #1 \exp_after:wN {#2} }
1669 \cs_new:Npn \exp_args:NNo #1#2#3
1670   { \exp_after:wN #1 \exp_after:wN #2 \exp_after:wN {#3} }
1671 \cs_new:Npn \exp_args:NNNo #1#2#3#4
1672   { \exp_after:wN #1 \exp_after:wN#2 \exp_after:wN #3 \exp_after:wN {#4} }
(End definition for \exp_args:N This function is documented on page 30.)
```

```

\exp_args:Nc
\exp_args:cc
In \3basics.
(End definition for \exp_args:Nc and \exp_args:cc These functions are documented on page ??.)
```

\exp_args:NNc Here are the functions that turn their argument into csnames but are expandable.

```

\exp_args:Ncc
\exp_args:Nccc
1673 \cs_new:Npn \exp_args:NNc #1#2#3
1674   { \exp_after:wN #1 \exp_after:wN #2 \cs:w # 3\cs_end: }
1675 \cs_new:Npn \exp_args:Ncc #1#2#3
1676   { \exp_after:wN #1 \cs:w #2 \exp_after:wN \cs_end: \cs:w #3 \cs_end: }
1677 \cs_new:Npn \exp_args:Nccc #1#2#3#4
1678   {
1679     \exp_after:wN #1
1680     \cs:w #2 \exp_after:wN \cs_end:
1681     \cs:w #3 \exp_after:wN \cs_end:
1682     \cs:w #4 \cs_end:
1683   }
(End definition for \exp_args:NNc, \exp_args:Ncc, and \exp_args:Nccc These functions are documented on page ??.)
```

```

\exp_args:Nf
\exp_args:NV
\exp_args:Nv
1684 \cs_new:Npn \exp_args:Nf #1#2
1685   { \exp_after:wN #1 \exp_after:wN { \tex_roman numeral:D -'0 #2 } }
1686 \cs_new:Npn \exp_args:NV #1#2
1687   {
1688     \exp_after:wN #1 \exp_after:wN
1689     { \tex_roman numeral:D \_exp_eval_register:c {#2} }
1690   }
1691 \cs_new:Npn \exp_args:Nv #1#2
1692   {
1693     \exp_after:wN #1 \exp_after:wN
1694     { \tex_roman numeral:D \_exp_eval_register:N #2 }
1695 }
```

(End definition for `\exp_args:Nf`, `\exp_args:NV`, and `\exp_args:Nv`. These functions are documented on page 29.)

`\exp_args>NNV` Some more hand-tuned function with three arguments. If we forced that an o argument always has braces, we could implement `\exp_args:Nco` with less tokens and only two arguments.

```

1696 \cs_new:Npn \exp_args>NNf #1#2#3
1697 {
1698     \exp_after:wN #1
1699     \exp_after:wN #2
1700     \exp_after:wN { \tex_roman numeral:D -'0 #3 }
1701 }
1702 \cs_new:Npn \exp_args>NNv #1#2#3
1703 {
1704     \exp_after:wN #1
1705     \exp_after:wN #2
1706     \exp_after:wN { \tex_roman numeral:D \__exp_eval_register:c {#3} }
1707 }
1708 \cs_new:Npn \exp_args>NNV #1#2#3
1709 {
1710     \exp_after:wN #1
1711     \exp_after:wN #2
1712     \exp_after:wN { \tex_roman numeral:D \__exp_eval_register:N #3 }
1713 }
1714 \cs_new:Npn \exp_args:Nco #1#2#3
1715 {
1716     \exp_after:wN #1
1717     \cs:w #2 \exp_after:wN \cs_end:
1718     \exp_after:wN {#3}
1719 }
1720 \cs_new:Npn \exp_args:Ncf #1#2#3
1721 {
1722     \exp_after:wN #1
1723     \cs:w #2 \exp_after:wN \cs_end:
1724     \exp_after:wN { \tex_roman numeral:D -'0 #3 }
1725 }
1726 \cs_new:Npn \exp_args:NNV #1#2#3
1727 {
1728     \exp_after:wN #1
1729     \exp_after:wN { \tex_roman numeral:D \exp_after:wN
1730         \__exp_eval_register:N \exp_after:wN #2 \exp_after:wN }
1731     \exp_after:wN { \tex_roman numeral:D \__exp_eval_register:N #3 }
1732 }
```

(End definition for `\exp_args:NNV` and others. These functions are documented on page ??.)

`\exp_args:Ncco` A few more that we can hand-tune.

```

1733 \cs_new:Npn \exp_args:NNNV #1#2#3#4
1734 {
1735     \exp_after:wN #1
```

```

1736   \exp_after:wN #2
1737   \exp_after:wN #3
1738   \exp_after:wN { \tex_roman numeral:D \__exp_eval_register:N #4 }
1739 }
1740 \cs_new:Npn \exp_args:NcNc #1#2#3#4
1741 {
1742   \exp_after:wN #1
1743   \cs:w #2 \exp_after:wN \cs_end:
1744   \exp_after:wN #3
1745   \cs:w #4 \cs_end:
1746 }
1747 \cs_new:Npn \exp_args:NcNo #1#2#3#4
1748 {
1749   \exp_after:wN #1
1750   \cs:w #2 \exp_after:wN \cs_end:
1751   \exp_after:wN #3
1752   \exp_after:wN {#4}
1753 }
1754 \cs_new:Npn \exp_args:Ncco #1#2#3#4
1755 {
1756   \exp_after:wN #1
1757   \cs:w #2 \exp_after:wN \cs_end:
1758   \cs:w #3 \exp_after:wN \cs_end:
1759   \exp_after:wN {#4}
1760 }

```

(End definition for `\exp_args:Ncc` and others. These functions are documented on page ??.)

4.3 Definitions with the automated technique

Some of these could be done more efficiently, but the complexity of coding then becomes an issue. Notice that the auto-generated functions are all not long: they don't actually take any arguments themselves.

```
\exp_args:Nx
1761 \cs_new_protected_nopar:Npn \exp_args:Nx { \:::x \::: }
```

(End definition for `\exp_args:Nx`. This function is documented on page ??.)

`\exp_args:Nnc` Here are the actual function definitions, using the helper functions above.

```

\exp_args:Nfo
\exp_args:Nff
\exp_args:Nnf
\exp_args:Nno
\exp_args:Nnv
\exp_args:Noo
\exp_args:Nof
\exp_args:Noc
\exp_args:NNx
\exp_args:Ncx
\exp_args:Nnx
\exp_args:Nox
\exp_args:Nxo
\exp_args:Nxx
1762 \cs_new_nopar:Npn \exp_args:Nnc { \:::n \:::c \::: }
1763 \cs_new_nopar:Npn \exp_args:Nfo { \:::f \:::o \::: }
1764 \cs_new_nopar:Npn \exp_args:Nff { \:::f \:::f \::: }
1765 \cs_new_nopar:Npn \exp_args:Nnf { \:::n \:::f \::: }
1766 \cs_new_nopar:Npn \exp_args:Nno { \:::n \:::o \::: }
1767 \cs_new_nopar:Npn \exp_args:Nnv { \:::n \:::v \::: }
1768 \cs_new_nopar:Npn \exp_args:Noo { \:::o \:::o \::: }
1769 \cs_new_nopar:Npn \exp_args:Nof { \:::o \:::f \::: }
1770 \cs_new_nopar:Npn \exp_args:Noc { \:::o \:::c \::: }
1771 \cs_new_protected_nopar:Npn \exp_args:NNx { \:::N \:::x \::: }
1772 \cs_new_protected_nopar:Npn \exp_args:Ncx { \:::c \:::x \::: }
```

```

1773 \cs_new_protected_nopar:Npn \exp_args:Nnx { ::n ::x :: }
1774 \cs_new_protected_nopar:Npn \exp_args:Nox { ::o ::x :: }
1775 \cs_new_protected_nopar:Npn \exp_args:Nxo { ::x ::o :: }
1776 \cs_new_protected_nopar:Npn \exp_args:Nxx { ::x ::x :: }

(End definition for \exp_args:Nnc and others. These functions are documented on page ??.)
```

```

\exp_args:NNno
\exp_args:NNoo
\exp_args:Nnnc
\exp_args:Nnno
\exp_args:Nooo
\exp_args:NNnx
\exp_args:NNox
\exp_args:Nnnx
\exp_args:Nnox
\exp_args:Nccx
\exp_args:Ncnx
\exp_args:Noox

1777 \cs_new_nopar:Npn \exp_args:NNno { ::N ::n ::o :: }
1778 \cs_new_nopar:Npn \exp_args:NNoo { ::N ::o ::o :: }
1779 \cs_new_nopar:Npn \exp_args:Nnnc { ::n ::n ::c :: }
1780 \cs_new_nopar:Npn \exp_args:Nnno { ::n ::n ::o :: }
1781 \cs_new_nopar:Npn \exp_args:Nooo { ::o ::o ::o :: }
1782 \cs_new_protected_nopar:Npn \exp_args:NNnx { ::N ::n ::x :: }
1783 \cs_new_protected_nopar:Npn \exp_args:NNox { ::N ::o ::x :: }
1784 \cs_new_protected_nopar:Npn \exp_args:Nnnx { ::n ::n ::x :: }
1785 \cs_new_protected_nopar:Npn \exp_args:Nnox { ::n ::o ::x :: }
1786 \cs_new_protected_nopar:Npn \exp_args:Nccx { ::c ::c ::x :: }
1787 \cs_new_protected_nopar:Npn \exp_args:Ncnx { ::c ::n ::x :: }
1788 \cs_new_protected_nopar:Npn \exp_args:Noox { ::o ::o ::x :: }

(End definition for \exp_args:NNno and others. These functions are documented on page ??.)
```

4.4 Last-unbraced versions

There are a few places where the last argument needs to be available unbraced. First some helper macros.

```

\__exp_arg_last_unbraced:nn
  ::f_unbraced
  ::o_unbraced
  ::V_unbraced
  ::v_unbraced
  ::x_unbraced

1789 \cs_new:Npn \__exp_arg_last_unbraced:nn #1#2 { #2#1 }
1790 \cs_new:Npn ::f_unbraced :: #1#2
1791 {
1792   \exp_after:wN \__exp_arg_last_unbraced:nn
1793     \exp_after:wN { \tex_roman numeral:D -'0 #2 } {#1}
1794 }
1795 \cs_new:Npn ::o_unbraced :: #1#2
1796   { \exp_after:wN \__exp_arg_last_unbraced:nn \exp_after:wN {#2} {#1} }
1797 \cs_new:Npn ::V_unbraced :: #1#2
1798 {
1799   \exp_after:wN \__exp_arg_last_unbraced:nn
1800     \exp_after:wN { \tex_roman numeral:D \__exp_eval_register:N #2 } {#1}
1801 }
1802 \cs_new:Npn ::v_unbraced :: #1#2
1803 {
1804   \exp_after:wN \__exp_arg_last_unbraced:nn
1805     \exp_after:wN { \tex_roman numeral:D \__exp_eval_register:c {#2} } {#1}
1806 }
1807 \cs_new_protected:Npn ::x_unbraced :: #1#2
1808 {
1809   \cs_set_nopar:Npx \l__exp_internal_t1 { \exp_not:n {#1} #2 }
1810   \l__exp_internal_t1
1811 }
```

(End definition for __exp_arg_last_unbraced:nn This function is documented on page ??.)

```

\exp_last_unbraced:NV
\exp_last_unbraced:Nv
\exp_last_unbraced:Nf
\exp_last_unbraced:N
\exp_last_unbraced:Nco
\exp_last_unbraced:NcV
\exp_last_unbraced:NNV
\exp_last_unbraced:NNNo
\exp_last_unbraced:NNNV
\exp_last_unbraced:NNNNo
\exp_last_unbraced:Nno
\exp_last_unbraced:Noo
\exp_last_unbraced:Nfo
\exp_last_unbraced:NnNo
\exp_last_unbraced:Nx

1812 \cs_new:Npn \exp_last_unbraced:NV #1#2
1813   { \exp_after:wN #1 \tex_roman numeral:D \__exp_eval_register:N #2 }
1814 \cs_new:Npn \exp_last_unbraced:Nv #1#2
1815   { \exp_after:wN #1 \tex_roman numeral:D \__exp_eval_register:c {#2} }
1816 \cs_new:Npn \exp_last_unbraced:Nf #1#2
1817   { \exp_after:wN #1 \tex_roman numeral:D -'0 #2 }
1818 \cs_new:Npn \exp_last_unbraced:N #1#2#3
1819   { \exp_after:wN #1 \cs:w #2 \exp_after:wN \cs_end: #3 }
1820 \cs_new:Npn \exp_last_unbraced:Nco #1#2#3
1821   { \exp_after:wN #1 \cs:w #2 \exp_after:wN \cs_end: #3 }
1822   {
1823     \exp_after:wN #
1824     \cs:w #2 \exp_after:wN \cs_end:
1825     \tex_roman numeral:D \__exp_eval_register:N #
1826   }
1827 \cs_new:Npn \exp_last_unbraced:NNV #1#2#3
1828   {
1829     \exp_after:wN #
1830     \exp_after:wN #
1831     \tex_roman numeral:D \__exp_eval_register:N #
1832   }
1833 \cs_new:Npn \exp_last_unbraced:NNNo #1#2#3
1834   { \exp_after:wN #1 \exp_after:wN #2 #3 }
1835 \cs_new:Npn \exp_last_unbraced:NNNV #1#2#3#4
1836   {
1837     \exp_after:wN #
1838     \exp_after:wN #
1839     \exp_after:wN #
1840     \tex_roman numeral:D \__exp_eval_register:N #
1841   }
1842 \cs_new:Npn \exp_last_unbraced:NNNo #1#2#3#4
1843   { \exp_after:wN #1 \exp_after:wN #2 \exp_after:wN #3 #4 }
1844 \cs_new_nopar:Npn \exp_last_unbraced:Nno { \:::n \:::o_unbraced \::: }
1845 \cs_new_nopar:Npn \exp_last_unbraced:Noo { \:::o \:::o_unbraced \::: }
1846 \cs_new_nopar:Npn \exp_last_unbraced:Nfo { \:::f \:::o_unbraced \::: }
1847 \cs_new_nopar:Npn \exp_last_unbraced:NnNo { \:::n \:::N \:::o_unbraced \::: }
1848 \cs_new_protected_nopar:Npn \exp_last_unbraced:Nx { \:::x_unbraced \::: }

(End definition for \exp_last_unbraced:NV This function is documented on page 31.)
```

\exp_last_two_unbraced:Noo
 $__exp_last_two_unbraced:n0N$

If #2 is a single token then this can be implemented as

```

\cs_new:Npn \exp_last_two_unbraced:Noo #1 #2 #3
  { \exp_after:wN \exp_after:wN \exp_after:wN #1 \exp_after:wN #2 #3 }
```

However, for robustness this is not suitable. Instead, a bit of a shuffle is used to ensure that #2 can be multiple tokens.

```

1849 \cs_new:Npn \exp_last_two_unbraced:Noo #1#2#3
```

```

1850   { \exp_after:wN \__exp_last_two_unbraced:nN \exp_after:wN {#3} {#2} #1 }
1851 \cs_new:Npn \__exp_last_two_unbraced:nN #1#2#3
1852   { \exp_after:wN #3 #2 #1 }

```

(End definition for `\exp_last_two_unbraced:Noo`. This function is documented on page 31.)

4.5 Preventing expansion

```

\exp_not:o
\exp_not:c
\exp_not:f
\exp_not:V
\exp_not:v
1853 \cs_new:Npn \exp_not:o #1 { \etex_unexpanded:D \exp_after:wN {#1} }
1854 \cs_new:Npn \exp_not:c #1 { \exp_after:wN \exp_not:N \cs:w #1 \cs_end: }
1855 \cs_new:Npn \exp_not:f #1
1856   { \etex_unexpanded:D \exp_after:wN { \tex_roman numeral:D -'0 #1 } }
1857 \cs_new:Npn \exp_not:V #1
1858   {
1859     \etex_unexpanded:D \exp_after:wN
1860       { \tex_roman numeral:D \__exp_eval_register:N #1 }
1861   }
1862 \cs_new:Npn \exp_not:v #1
1863   {
1864     \etex_unexpanded:D \exp_after:wN
1865       { \tex_roman numeral:D \__exp_eval_register:c {#1} }
1866   }

```

(End definition for `\exp_not:o`. This function is documented on page 32.)

4.6 Defining function variants

1867 `(@@=cs)`

`\cs_generate_variant:Nn` #1 : Base form of a function; e.g., `\tl_set:Nn`
#2 : One or more variant argument specifiers; e.g., `{Nx,c,cx}`

After making sure that the base form exists, test whether it is protected or not and define `__cs_tmp:w` as either `\cs_new_nopar:Npx` or `\cs_new_protected_nopar:Npx`, which is then used to define all the variants (except those involving x-expansion, always protected). Split up the original base function only once, to grab its name and signature. Then we wish to iterate through the comma list of variant argument specifiers, which we first convert to a string: the reason is explained later.

```

1868 \cs_new_protected:Npn \cs_generate_variant:Nn #1#2
1869   {
1870     \__chk_if_exist_cs:N #1
1871     \__cs_generate_variant:N #1
1872     \exp_after:wN \__cs_split_function>NN
1873     \exp_after:wN #
1874     \exp_after:wN \__cs_generate_variant:nnNN
1875     \exp_after:wN #
1876     \etex_detokenize:D {#2} , \scan_stop: , \q_recursion_stop
1877   }

```

(End definition for `\cs_generate_variant:Nn`. This function is documented on page 27.)

```
\__cs_generate_variant:N  
\__cs_generate_variant:ww  
\__cs_generate_variant:wwNw
```

The goal here is to pick up protected parent functions. There are four cases: the parent function can be a primitive or a macro, and can be expandable or not. For non-expandable primitives, all variants should be protected; skipping the `\else:` branch is safe because all primitive TeX conditionals are expandable.

The other case where variants should be protected is when the parent function is a protected macro: then `protected` appears in the meaning before the first occurrence of `macro`. The `ww` auxiliary removes everything in the meaning string after the first `ma`. We use `ma` rather than the full `macro` because the meaning of the `\firstmark` primitive (and four others) can contain an arbitrary string after a leading `firstmark::`. Then, look for `pr` in the part we extracted: no need to look for anything longer: the only strings we can have are an empty string, `\long\`, `\protected\`, `\protected\long\`, `\first`, `\top`, `\bot`, `\splittop`, or `\splitbot`, with `\` replaced by the appropriate escape character. If `pr` appears in the part before `ma`, the first `\q_mark` is taken as an argument of the `wwNw` auxiliary, and #3 is `\cs_new_protected_nopar:Npx`, otherwise it is `\cs_new_nopar:Npx`.

```
1878 \group_begin:  
1879   \tex_catcode:D '\M = 12 \scan_stop:  
1880   \tex_catcode:D '\A = 12 \scan_stop:  
1881   \tex_catcode:D '\P = 12 \scan_stop:  
1882   \tex_catcode:D '\R = 12 \scan_stop:  
1883 \tex_lowercase:D  
1884 {  
1885   \group_end:  
1886   \cs_new_protected:Npn \__cs_generate_variant:N #1  
1887   {  
1888     \exp_after:wN \if_meaning:w \exp_not:N #1 #1  
1889     \cs_set_eq:NN \__cs_tmp:w \cs_new_protected_nopar:Npx  
1890   \else:  
1891     \exp_after:wN \__cs_generate_variant:ww  
1892     \token_to_meaning:N #1 MA \q_mark  
1893     \q_mark \cs_new_protected_nopar:Npx  
1894     PR  
1895     \q_mark \cs_new_nopar:Npx  
1896     \q_stop  
1897     \fi:  
1898   }  
1899   \cs_new_protected:Npn \__cs_generate_variant:ww #1 MA #2 \q_mark  
1900   { \__cs_generate_variant:wwNw #1 }  
1901   \cs_new_protected:Npn \__cs_generate_variant:wwNw  
1902   #1 PR #2 \q_mark #3 #4 \q_stop  
1903   {  
1904     \cs_set_eq:NN \__cs_tmp:w #3  
1905   }  
1906 }
```

(End definition for `__cs_generate_variant:N` This function is documented on page 27.)

```
\__cs_generate_variant:nnNN #1 : Base name.  
#2 : Base signature.  
#3 : Boolean.
```

#4 : Base function.

If the boolean is `\c_false_bool`, the base function has no colon and we abort with an error; otherwise, set off a loop through the desired variant forms. The original function is retained as #4 for efficiency.

```
1907 \cs_new_protected:Npn \__cs_generate_variant:nnNN #1#2#3#4
1908 {
1909     \if_meaning:w \c_false_bool #3
1910         \__msg_kernel_error:nnx { kernel } { missing-colon }
1911         { \token_to_str:c {#1} }
1912         \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1913     \fi:
1914     \__cs_generate_variant:Nnnw #4 {#1}{#2}
1915 }
```

(End definition for `__cs_generate_variant:nnNN`)

`__cs_generate_variant:Nnnw` #1 : Base function.

#2 : Base name.

#3 : Base signature.

#4 : Beginning of variant signature.

First check whether to terminate the loop over variant forms. Then, for each variant form, construct a new function name using the original base name, the variant signature consisting of l letters and the last $k - l$ letters of the base signature (of length k). For example, for a base function `\prop_put:Nnn` which needs a `cV` variant form, we want the new signature to be `cVn`.

There are further subtleties:

- In `\cs_generate_variant:Nn \foo:nnTF {xxTF}`, it would be better to define `\foo:xxTF` using `\exp_args:Nxx`, rather than a hypothetical `\exp_args:NxxTF`. Thus, we wish to trim a common trailing part from the base signature and the variant signature.
- In `\cs_generate_variant:Nn \foo:on {ox}`, the function `\foo:ox` should be defined using `\exp_args:Nnx`, not `\exp_args:Nox`, to avoid double `o` expansion.
- Lastly, `\cs_generate_variant:Nn \foo:on {xn}` should trigger an error, because we do not have a means to replace `o`-expansion by `x`-expansion.

All this boils down to a few rules. Only `n` and `N`-type arguments can be replaced by `\cs_generate_variant:Nn`. Other argument types are allowed to be passed unchanged from the base form to the variant: in the process they are changed to `n` (except for two cases: `N` and `p`-type arguments). A common trailing part is ignored.

We compare the base and variant signatures one character at a time within `x`-expansion. The result is given to `__cs_generate_variant:wwNN` in the form `<processed variant signature> \q_mark <errors> \q_stop <base function> <new function>`. If all went well, `<errors>` is empty; otherwise, it is a kernel error message, followed by some clean-up code (`\use_none:nnnn`).

Note the space after #3 and after the following brace group. Those are ignored by TeX when fetching the last argument for `__cs_generate_variant_loop:nNwN`, but can be used as a delimiter for `__cs_generate_variant_loop_end:nwwwNNnn`.

```

1916 \cs_new_protected:Npn \__cs_generate_variant:Nnnw #1#2#3#4 ,
1917 {
1918   \if_meaning:w \scan_stop: #4
1919     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1920   \fi:
1921   \use:x
1922   {
1923     \exp_not:N \__cs_generate_variant:wwNN
1924     \__cs_generate_variant_loop:nNwN { }
1925     #4
1926     \__cs_generate_variant_loop_end:nwwwNNnn
1927     \q_mark
1928     #3 ~
1929     { ~ { } \fi: \__cs_generate_variant_loop_long:wNNnn } ~
1930     { }
1931     \q_stop
1932     \exp_not:N #1 {#2} {#4}
1933   }
1934   \__cs_generate_variant:Nnnw #1 {#2} {#3}
1935 }
```

(End definition for `__cs_generate_variant:Nnnw`)

```

\__cs_generate_variant_loop:nNwN
\__cs_generate_variant_loop_same:w
\__cs_generate_variant_loop_end:nwwwNNnn
\__cs_generate_variant_loop_long:wNNnn
\__cs_generate_variant_loop_invalid:NNwNNnn
```

#1 : Last few (consecutive) letters common between the base and variant (in fact, `__cs_generate_variant_same:N <letter>` for each letter).
#2 : Next variant letter.
#3 : Remainder of variant form.
#4 : Next base letter.

The first argument is populated by `__cs_generate_variant_loop_same:w` when a variant letter and a base letter match. It is flushed into the input stream whenever the two letters are different: if the loop ends before, the argument is dropped, which means that trailing common letters are ignored.

The case where the two letters are different is only allowed with a base letter of `N` or `n`. Otherwise, call `__cs_generate_variant_loop_invalid>NNwNNnn` to remove the end of the loop, get arguments at the end of the loop, and place an appropriate error message as a second argument of `__cs_generate_variant:wwNN`. If the letters are distinct and the base letter is indeed `n` or `N`, leave in the input stream whatever argument was collected, and the next variant letter #2, then loop by calling `__cs_generate_variant_loop:nNwN`.

The loop can stop in three ways.

- If the end of the variant form is encountered first, #2 is `__cs_generate_variant_loop_end:nwwwNNnn` (expanded by the conditional `\if:w`), which inserts some tokens to end the conditional; grabs the `<base name>` as #7, the `<variant signature>` #8, the `<next base letter>` #1 and the part #3 of the base signature that wasn't read yet; and combines those into the `<new function>` to be defined.

- If the end of the base form is encountered first, #4 is $\sim\{\}\backslash fi$: which ends the conditional (with an empty expansion), followed by $\backslash _cs_generate_variant_loop_long:wNNnn$, which places an error as the second argument of $\backslash _cs_generate_variant:wwNN$.
- The loop can be interrupted early if the requested expansion is unavailable, namely when the variant and base letters differ and the base is neither n nor N. Again, an error is placed as the second argument of $\backslash _cs_generate_variant:wwNN$.

Note that if the variant form has the same length as the base form, #2 is as described in the first point, and #4 as described in the second point above. The $\backslash _cs_generate_variant_loop_end:nwwwNNnn$ breaking function takes the empty brace group in #4 as its first argument: this empty brace group produces the correct signature for the full variant.

```

1936 \cs_new:Npn \_cs_generate_variant_loop:nNwN #1#2#3 \q_mark #4
1937 {
1938   \if:w #2 #4
1939     \exp_after:wN \_cs_generate_variant_loop_same:w
1940   \else:
1941     \if:w N #4 \else:
1942       \if:w n #4 \else:
1943         \_cs_generate_variant_loop_invalid:NNwNNnn #4#2
1944       \fi:
1945     \fi:
1946   \fi:
1947   #1
1948   \prg_do_nothing:
1949   #2
1950   \_cs_generate_variant_loop:nNwN { } #3 \q_mark
1951 }
1952 \cs_new:Npn \_cs_generate_variant_loop_same:w
1953   #1 \prg_do_nothing: #2#3#4
1954 {
1955   #3 { #1 \_cs_generate_variant_same:N #2 }
1956 }
1957 \cs_new:Npn \_cs_generate_variant_loop_end:nwwwNNnn
1958   #1#2 \q_mark #3 ~ #4 \q_stop #5#6#7#8
1959 {
1960   \scan_stop: \scan_stop: \fi:
1961   \exp_not:N \q_mark
1962   \exp_not:N \q_stop
1963   \exp_not:N #6
1964   \exp_not:c { #7 : #8 #1 #3 }
1965 }
1966 \cs_new:Npn \_cs_generate_variant_loop_long:wNNnn #1 \q_stop #2#3#4#5
1967 {
1968   \exp_not:n
1969   {
1970     \q_mark

```

```

1971     \_msg_kernel_error:nxxx { kernel } { variant-too-long }
1972         {#5} { \token_to_str:N #3 }
1973     \use_none:nnnn
1974     \q_stop
1975         #3
1976         #3
1977     }
1978 }
1979 \cs_new:Npn \__cs_generate_variant_loop_invalid:NNwNNnn
1980     #1#2 \fi: \fi: \fi: #3 \q_stop #4#5#6#7
1981 {
1982     \fi: \fi: \fi:
1983     \exp_not:n
1984     {
1985         \q_mark
1986         \_msg_kernel_error:nxxxxx { kernel } { invalid-variant }
1987             {#7} { \token_to_str:N #5 } {#1} {#2}
1988         \use_none:nnnn
1989         \q_stop
1990             #5
1991             #5
1992     }
1993 }
```

(End definition for `__cs_generate_variant_loop:nNwN` and others.)

`__cs_generate_variant_same:N`

When the base and variant letters are identical, don't do any expansion. For most argument types, we can use the `n`-type no-expansion, but the `N` and `p` types require a slightly different behaviour with respect to braces.

```

1994 \cs_new:Npn \__cs_generate_variant_same:N #1
1995 {
1996     \if:w N #1
1997         N
1998     \else:
1999         \if:w p #1
2000             p
2001         \else:
2002             n
2003         \fi:
2004     \fi:
2005 }
```

(End definition for `__cs_generate_variant_same:N`)

`__cs_generate_variant:wwNN`

If the variant form has already been defined, log its existence. Otherwise, make sure that the `\exp_args:N #3` form is defined, and if it contains `x`, change `__cs_tmp:w` locally to `\cs_new_protected_nopar:Npx`. Then define the variant by combining the `\exp_args:N #3` variant and the base function.

```

2006 \cs_new_protected:Npn \__cs_generate_variant:wwNN
2007     #1 \q_mark #2 \q_stop #3#4
2008 {
```

```

2009 #2
2010 \cs_if_free:NTF #4
2011 {
2012   \group_begin:
2013     \__cs_generate_internal_variant:n {#1}
2014     \__cs_tmp:w #4 { \exp_not:c { exp_args:N #1 } \exp_not:N #3 }
2015   \group_end:
2016 }
2017 {
2018   \iow_log:x
2019   {
2020     Variant~\token_to_str:N #4~%
2021     already-defined;~ not~ changing~ it-on-line-%
2022     \tex_the:D \tex_inputlineno:D
2023   }
2024 }
2025 }

(End definition for \__cs_generate_variant:wwNN)

```

__cs_generate_internal_variant:n
__cs_generate_internal_variant:wwNw
__cs_generate_internal_variant_loop:n

Test if \exp_args:N #1 is already defined and if not define it via the \:: commands using the chars in #1. If #1 contains an x (this is the place where having converted the original comma-list argument to a string is very important), the result should be protected, and the next variant to be defined using that internal variant should be protected.

```

2026 \group_begin:
2027   \tex_catcode:D ‘X = 12 \scan_stop:
2028   \tex_lccode:D ‘N = ‘N \scan_stop:
2029 \tex_lowercase:D
2030 {
2031   \group_end:
2032   \cs_new_protected:Npn \__cs_generate_internal_variant:n #1
2033   {
2034     \__cs_generate_internal_variant:wwNwnn
2035     #1 \q_mark
2036     { \cs_set_eq:NN \__cs_tmp:w \cs_new_protected_nopar:Npx }
2037     \cs_new_protected_nopar:cpx
2038     X \q_mark
2039     { }
2040     \cs_new_nopar:cpx
2041   \q_stop
2042     { \exp_args:N #1 }
2043     { \__cs_generate_internal_variant_loop:n #1 { : \use_i:nn } }
2044   }
2045 \cs_new_protected:Npn \__cs_generate_internal_variant:wwNwnn
2046   #1 X #2 \q_mark #3 #4 #5 \q_stop #6 #7
2047 {
2048   #3
2049   \cs_if_free:cT {#6} { #4 {#6} {#7} }
2050 }
2051

```

This command grabs char by char outputting `\:::#1` (not expanded further). We avoid tests by putting a trailing : `\use_i:nn`, which leaves `\cs_end:` and removes the looping macro. The colon is in fact also turned into `\:::` so that the required structure for `\exp_args:N...` commands is correctly terminated.

```
2052 \cs_new:Npn \__cs_generate_internal_variant_loop:n #1
2053 {
2054     \exp_after:wN \exp_not:N \cs:w :: #1 \cs_end:
2055     \__cs_generate_internal_variant_loop:n
2056 }
```

(End definition for `__cs_generate_internal_variant:n` This function is documented on page ??.)

4.7 Variants which cannot be created earlier

`\str_if_eq_p:Vn` These cannot come earlier as they need `\cs_generate_variant:Nn`.

```
2057 \cs_generate_variant:Nn \str_if_eq_p:nn { V , o }
2058 \cs_generate_variant:Nn \str_if_eq_p:nn { nV , no , VV }
2059 \cs_generate_variant:Nn \str_if_eq:nnT { V , o }
2060 \cs_generate_variant:Nn \str_if_eq:nnT { nV , no , VV }
2061 \cs_generate_variant:Nn \str_if_eq:nnF { V , o }
2062 \cs_generate_variant:Nn \str_if_eq:nnF { nV , no , VV }
2063 \cs_generate_variant:Nn \str_if_eq:nnTF { V , o }
2064 \cs_generate_variant:Nn \str_if_eq:nnTF { nV , no , VV }
2065 \cs_generate_variant:Nn \str_case:nnn { o }
```

(End definition for `\str_if_eq:Vn` and others. These functions are documented on page ??.)

```
2066 </initex | package>
```

5 l3prg implementation

The following test files are used for this code: `m3prg001.lvt,m3prg002.lvt,m3prg003.lvt`.

```
2067 <*initex | package>
2068 <*package>
2069 \ProvidesExplPackage
2070   {\ExplFileName}{\ExplFileVersion}{\ExplFileDescription}
2071 \__expl_package_check:
2072 </package>
```

5.1 Primitive conditionals

`\if_bool:N` Those two primitive TeX conditionals are synonyms. They should not be used outside
`\if_predicate:w` the kernel code.

```
2073 \tex_let:D \if_bool:N           \tex_ifodd:D
2074 \tex_let:D \if_predicate:w     \tex_ifodd:D
(End definition for \if_bool:N This function is documented on page 41.)
```

5.2 Defining a set of conditional functions

These are all defined in `l3basics`, as they are needed “early”. This is just a reminder that that is the case!

(*End definition for `\prg_set_conditional:Npnn` and others. These functions are documented on page 36.*)

5.3 The boolean data type

2075 `<@@=bool>`

Boolean variables have to be initiated when they are created. Other than that there is not much to say here.

2076 `\cs_new_protected:Npn \bool_new:N #1 { \cs_new_eq:NN #1 \c_false_bool }`
 2077 `\cs_generate_variant:Nn \bool_new:N { c }`

(*End definition for `\bool_new:N` and `\bool_new:c`. These functions are documented on page ??.*)

Setting is already pretty easy.

2078 `\cs_new_protected:Npn \bool_set_true:N #1 { \cs_set_eq:NN #1 \c_true_bool }`
 2079 `{ \cs_new_protected:Npn \bool_set_false:N #1 { \cs_set_eq:NN #1 \c_false_bool }`
 2080 `\cs_new_protected:Npn \bool_gset_true:c { \cs_set_eq:NN #1 \c_true_bool }`
 2081 `\cs_new_protected:Npn \bool_gset_false:c { \cs_set_eq:NN #1 \c_false_bool }`
 2082 `\cs_new_protected:Npn \bool_gset_true:N #1 { \cs_gset_eq:NN #1 \c_true_bool }`
 2083 `\cs_new_protected:Npn \bool_gset_false:N #1 { \cs_gset_eq:NN #1 \c_false_bool }`
 2084 `\cs_new_protected:Npn \bool_gset_true:c { \cs_gset_eq:NN #1 \c_true_bool }`
 2085 `\cs_new_protected:Npn \bool_gset_false:c { \cs_gset_eq:NN #1 \c_false_bool }`
 2086 `\cs_generate_variant:Nn \bool_set_true:N { c }`
 2087 `\cs_generate_variant:Nn \bool_set_false:N { c }`
 2088 `\cs_generate_variant:Nn \bool_gset_true:N { c }`
 2089 `\cs_generate_variant:Nn \bool_gset_false:N { c }`

(*End definition for `\bool_set_true:N` and others. These functions are documented on page ??.*)

`\bool_set_eq:NN`

2090 `\cs_new_eq:NN \bool_set_eq:NN \cs_set_eq:NN`
 2091 `\cs_new_eq:NN \bool_set_eq:Nc \cs_set_eq:Nc`
 2092 `\cs_new_eq:NN \bool_set_eq:cN \cs_set_eq:cN`
 2093 `\cs_new_eq:NN \bool_set_eq:cc \cs_set_eq:cc`
 2094 `\cs_new_eq:NN \bool_gset_eq:NN \cs_gset_eq:NN`
 2095 `\cs_new_eq:NN \bool_gset_eq:Nc \cs_gset_eq:Nc`
 2096 `\cs_new_eq:NN \bool_gset_eq:cN \cs_gset_eq:cN`
 2097 `\cs_new_eq:NN \bool_gset_eq:cc \cs_gset_eq:cc`

(*End definition for `\bool_set_eq:NN` and others. These functions are documented on page ??.*)

`\bool_set:Nn`

`\bool_set:cn`

`\bool_gset:Nn`

`\bool_gset:cn`

This function evaluates a boolean expression and assigns the first argument the meaning `\c_true_bool` or `\c_false_bool`.

2098 `\cs_new_protected:Npn \bool_set:Nn #1#2 { \tex_chardef:D #1 = \bool_if_p:n {#2} }`
 2099 `\cs_new_protected:Npn \bool_gset:Nn #1#2 { \tex_global:D \tex_chardef:D #1 = \bool_if_p:n {#2} }`
 2100 `\cs_new_protected:Npn \bool_gset:cn #1#2 { \tex_global:D \tex_chardef:D #1 = \bool_if_p:n {#2} }`
 2101 `\cs_new_protected:Npn \bool_gset:cc #1#2 { \tex_global:D \tex_chardef:D #1 = \bool_if_p:n {#2} }`

```

2102 \cs_generate_variant:Nn \bool_set:Nn { c }
2103 \cs_generate_variant:Nn \bool_gset:Nn { c }
(End definition for \bool_set:Nn and \bool_set:cn These functions are documented on page ??.)
```

\bool_if_p:N Straight forward here. We could optimize here if we wanted to as the boolean can just be input directly.

```

2104 \prg_new_conditional:Npnn \bool_if:N #1 { p , T , F , TF }
2105 {
2106     \if_meaning:w \c_true_bool #1
2107         \prg_return_true:
2108     \else:
2109         \prg_return_false:
2110     \fi:
2111 }
2112 \cs_generate_variant:Nn \bool_if_p:N { c }
2113 \cs_generate_variant:Nn \bool_if:NT { c }
2114 \cs_generate_variant:Nn \bool_if:NF { c }
2115 \cs_generate_variant:Nn \bool_if:NTF { c }
```

(End definition for \bool_if:N and \bool_if:c These functions are documented on page ??.)

\bool_show:N Show the truth value of the boolean, as `true` or `false`. We use `_msg_show_variable:n` to get a better output; this function requires its argument to start with `>~`.

```

2116 \cs_new_protected:Npn \bool_show:N #1
2117 {
2118     \bool_if_exist:NTF #1
2119     { \bool_show:n {#1} }
2120     {
2121         \_msg_kernel_error:n { kernel } { variable-not-defined }
2122         { \token_to_str:N #1 }
2123     }
2124 }
2125 \cs_new_protected:Npn \bool_show:n #1
2126 {
2127     \bool_if:nTF {#1}
2128     { \_msg_show_variable:n { > ~ true } }
2129     { \_msg_show_variable:n { > ~ false } }
2130 }
```

(End definition for \bool_show:N, \bool_show:c, and \bool_show:n These functions are documented on page 37.)

\l_tmpa_bool A few booleans just if you need them.

```

2132 \bool_new:N \l_tmpa_bool
2133 \bool_new:N \l_tmpb_bool
2134 \bool_new:N \g_tmpa_bool
2135 \bool_new:N \g_tmpb_bool
```

(End definition for \l_tmpa_bool and others. These variables are documented on page 37.)

```

\bool_if_exist_p:N Copies of the cs functions defined in l3basics.
\bool_if_exist_p:c
\bool_if_exist:NTF
\bool_if_exist:cTF
2136 \cs_new_eq:NN \bool_if_exist:NTF \cs_if_exist:NTF
2137 \cs_new_eq:NN \bool_if_exist:NT \cs_if_exist:NT
2138 \cs_new_eq:NN \bool_if_exist:NF \cs_if_exist:NF
2139 \cs_new_eq:NN \bool_if_exist_p:N \cs_if_exist_p:N
2140 \cs_new_eq:NN \bool_if_exist:cTF \cs_if_exist:cTF
2141 \cs_new_eq:NN \bool_if_exist:cT \cs_if_exist:cT
2142 \cs_new_eq:NN \bool_if_exist:cF \cs_if_exist:cF
2143 \cs_new_eq:NN \bool_if_exist_p:c \cs_if_exist_p:c

(End definition for \bool_if_exist:N and \bool_if_exist:c These functions are documented on page ??.)

```

5.4 Boolean expressions

\bool_if_p:n Evaluating the truth value of a list of predicates is done using an input syntax somewhat similar to the one found in other programming languages with (and) for grouping, ! for logical “Not”, && for logical “And” and || for logical “Or”. We shall use the terms Not, And, Or, Open and Close for these operations.

Any expression is terminated by a Close operation. Evaluation happens from left to right in the following manner using a GetNext function:

- If an Open is seen, start evaluating a new expression using the Eval function and call GetNext again.
- If a Not is seen, remove the ! and call a GetNotNext function, which eventually reverses the logic compared to GetNext.
- If none of the above, reinsert the token found (this is supposed to be a predicate function) in front of an Eval function, which evaluates it to the boolean value *true* or *false*.

The Eval function then contains a post-processing operation which grabs the instruction following the predicate. This is either And, Or or Close. In each case the truth value is used to determine where to go next. The following situations can arise:

<true>And Current truth value is true, logical And seen, continue with GetNext to examine truth value of next boolean (sub-)expression.

<false>And Current truth value is false, logical And seen, stop evaluating the predicates within this sub-expression and break to the nearest Close. Then return *<false>*.

<true>Or Current truth value is true, logical Or seen, stop evaluating the predicates within this sub-expression and break to the nearest Close. Then return *<true>*.

<false>Or Current truth value is false, logical Or seen, continue with GetNext to examine truth value of next boolean (sub-)expression.

<true>Close Current truth value is true, Close seen, return *<true>*.

<false>Close Current truth value is false, Close seen, return *<false>*.

We introduce an additional Stop operation with the same semantics as the Close operation.

$\langle \text{true} \rangle \text{Stop}$ Current truth value is true, return $\langle \text{true} \rangle$.

$\langle \text{false} \rangle \text{Stop}$ Current truth value is false, return $\langle \text{false} \rangle$.

The reasons for this follow below.

```

2144 \prg_new_conditional:Npn \bool_if:n #1 { T , F , TF }
2145 {
2146   \if_predicate:w \bool_if_p:n {#1}
2147     \prg_return_true:
2148   \else:
2149     \prg_return_false:
2150   \fi:
2151 }
```

(End definition for $\backslash \text{bool_if_n}$ These functions are documented on page 38.)

```

\bool_if_p:n
\__bool_if_left_parentheses:www
\__bool_if_right_parentheses:www
\__bool_if_or:www
```

First issue a $\backslash \text{group_align_safe_begin}$: as we are using $\&&$ as syntax shorthand for the And operation and we need to hide it for TeX. This will be closed at the end of the expression parsing (see S below).

Minimal (“short-circuit”) evaluation of boolean expressions requires skipping to the end of the current parenthesized group when $\langle \text{true} \rangle \&&$ is seen, but to the next $\&&$ or closing parenthesis when $\langle \text{false} \rangle \&&$ is seen. To avoid having separate functions for the two cases, we transform the boolean expression by doubling each parenthesis and adding parenthesis around each $\&&$. This ensures that $\&&$ will bind tighter than $\|$.

The replacement is done in three passes, for left and right parentheses and for $\|$. At each pass, the part of the expression that has been transformed is stored before $\backslash \text{q_nil}$, the rest lies until the first $\backslash \text{q_mark}$, followed by an empty brace group. A trailing marker ensures that the auxiliaries’ delimited arguments will not run-away. As long as the delimiter matches inside the expression, material is moved before $\backslash \text{q_nil}$ and we continue. Afterwards, the trailing marker is taken as a delimiter, #4 is the next auxiliary, immediately followed by a new $\backslash \text{q_nil}$ delimiter, which indicates that nothing has been treated at this pass. The last step calls $\backslash \text{__bool_if_parse}:NNNww$ which cleans up and triggers the evaluation of the expression itself.

```

2152 \cs_new:Npn \bool_if_p:n #1
2153 {
2154   \group_align_safe_begin:
2155   \__bool_if_left_parentheses:www \q_nil
2156   #1 \q_mark { }
2157   ( \q_mark { \__bool_if_right_parentheses:www \q_nil }
2158   ) \q_mark { \__bool_if_or:www \q_nil }
2159   \| \q_mark \__bool_if_parse:NNNww
2160   \q_stop
2161 }
2162 \cs_new:Npn \__bool_if_left_parentheses:www #1 \q_nil #2 ( #3 \q_mark #4
2163   { #4 \__bool_if_left_parentheses:www #1 #2 (( \q_nil #3 \q_mark {#4} )
2164   \cs_new:Npn \__bool_if_right_parentheses:www #1 \q_nil #2 ) #3 \q_mark #4
```

```

2165 { #4 \__bool_if_right_parentheses:wwn #1 #2 )) \q_nil #3 \q_mark {#4} }
2166 \cs_new:Npn \__bool_if_or:wwn #1 \q_nil #2 || #3 \q_mark #4
2167 { #4 \__bool_if_or:wwn #1 #2 )||( \q_nil #3 \q_mark {#4} }

```

(End definition for `\bool_if_p:n` This function is documented on page 38.)

`__bool_if_parse:NNNww`

After removing extra tokens from the transformation phase, start evaluating. At the end, we will need to finish the special `align_safe` group before finally returning a `\c_true_bool` or `\c_false_bool` as there might otherwise be something left in front in the input stream. For this we call the Stop operation, denoted simply by a `S` following the last Close operation.

```

2168 \cs_new:Npn \__bool_if_parse:NNNww #1#2#3#4 \q_mark #5 \q_stop
2169 {
2170     \__bool_get_next:NN \use_i:nn (( #4 )) S
2171 }

```

(End definition for `__bool_if_parse:NNNww`)

`__bool_get_next>NN`

The GetNext operation. This is a switch: if what follows is neither `!` nor `(`, we assume it is a predicate. The first argument is `\use_ii:nn` if the logic must eventually be reversed (after a `!`), otherwise it is `\use_i:nn`. This function eventually expand to the truth value `\c_true_bool` or `\c_false_bool` of the expression which follows until the next unmatched closing parenthesis.

```

2172 \cs_new:Npn \__bool_get_next>NN #1#2
2173 {
2174     \use:c
2175     {
2176         __bool_
2177         \if_meaning:w !#2 ! \else: \if_meaning:w (#2 ( \else: p \fi: \fi:
2178         :Nw
2179     }
2180     #1 #2
2181 }

```

(End definition for `__bool_get_next>NN`)

`__bool_! :Nw`

The Not operation reverses the logic: discard the `!` token and call the GetNext operation with its first argument reversed.

```

2182 \cs_new:cpn { __bool_! :Nw } #1#2
2183 { \exp_after:wN \__bool_get_next>NN #1 \use_ii:nn \use_i:nn }

```

(End definition for `__bool_! :Nw`)

`__bool_(:Nw`

The Open operation starts a sub-expression after discarding the token. This is done by calling GetNext, with a post-processing step which looks for And, Or or Close afterwards.

```

2184 \cs_new:cpn { __bool_( :Nw } #1#2
2185 {
2186     \exp_after:wN \__bool_choose:NNN \exp_after:wN #1
2187     \__int_value:w \__bool_get_next>NN \use_i:nn
2188 }

```

(End definition for `__bool_(:Nw`)

__bool_p:Nw If what follows GetNext is neither ! nor (), evaluate the predicate using the primitive __int_value:w. The canonical true and false values have numerical values 1 and 0 respectively. Look for And, Or or Close afterwards.

```

2189 \cs_new:cpn { __bool_p:Nw } #1
2190   { \exp_after:wn \_\_bool_choose:NNN \exp_after:wN #1 \_\_int_value:w }
(End definition for \_\_bool_p:Nw)
```

__bool_choose:NNN Branching the eight-way switch. The arguments are 1: \use_i:nn or \use_ii:nn, 2: 0 or 1 encoding the current truth value, 3: the next operation, And, Or, Close or Stop. If #1 is \use_ii:nn, the logic of #2 must be reversed.

```

2191 \cs_new:Npn \_\_bool_choose:NNN #1#2#3
2192   {
2193     \use:c
2194       {
2195         __bool_ #3 -
2196         #1 #2 { \if_meaning:w 0 #2 1 \else: 0 \fi: }
2197         :w
2198       }
2199   }
(End definition for \_\_bool_choose:NNN)
```

__bool_)_0:w __bool_)_1:w Closing a group is just about returning the result. The Stop operation is similar except it closes the special alignment group before returning the boolean.

```

2200 \cs_new_nopar:cpn { __bool_)_0:w } { \c_false_bool }
2201 \cs_new_nopar:cpn { __bool_)_1:w } { \c_true_bool }
2202 \cs_new_nopar:cpn { __bool_S_0:w } { \group_align_safe_end: \c_false_bool }
2203 \cs_new_nopar:cpn { __bool_S_1:w } { \group_align_safe_end: \c_true_bool }
(End definition for \_\_bool_)_0:w and others.)
```

__bool_&_1:w __bool_|_0:w Two cases where we simply continue scanning. We must remove the second & or |.

```

2204 \cs_new_nopar:cpn { __bool_&_1:w } & { \_\_bool_get_next:NN \use_i:nn }
2205 \cs_new_nopar:cpn { __bool_|_0:w } | { \_\_bool_get_next:NN \use_i:nn }
(End definition for \_\_bool_&_1:w This function is documented on page 38.)
```

__bool_&_0:w __bool_|_1:w __bool_eval_skip_to_end:Nw When the truth value has already been decided, we have to throw away the remainder of the current group as we are doing minimal evaluation. This is slightly tricky as there are no braces so we have to play match the () manually.

```

2206 \cs_new_nopar:cpn { __bool_&_0:w } & { \_\_bool_eval_skip_to_end:Nw \c_false_bool }
2207 \cs_new_nopar:cpn { __bool_|_1:w } | { \_\_bool_eval_skip_to_end:Nw \c_true_bool }
```

__bool_eval_skip_to_end:Nw There is always at least one) waiting, namely the outer one. However, we are facing the problem that there may be more than one that need to be finished off and we have to detect the correct number of them. Here is a complicated example showing how this is done. After evaluating the following, we realize we must skip everything after the first And. Note the extra Close at the end.

```
\c_false_bool && ((abc) && xyz) && ((xyz) && (def)))
```

First read up to the first Close. This gives us the list we first read up until the first right parenthesis so we are looking at the token list

```
((abc
```

This contains two Open markers so we must remove two groups. Since no evaluation of the contents is to be carried out, it doesn't matter how we remove the groups as long as we wind up with the correct result. We therefore first remove a () pair and what preceded the Open – but leave the contents as it may contain Open tokens itself – leaving

```
(abc && xyz) && ((xyz) && (def)))
```

Another round of this gives us

```
(abc && xyz
```

which still contains an Open so we remove another () pair, giving us

```
abc && xyz && ((xyz) && (def)))
```

Again we read up to a Close and again find Open tokens:

```
abc && xyz && ((xyz
```

Further reduction gives us

```
(xyz && (def)))
```

and then

```
(xyz && (def
```

with reduction to

```
xyz && (def))
```

and ultimately we arrive at no Open tokens being skipped and we can finally close the group nicely.

```
2208 %% (
2209 \cs_new:Npn \__bool_eval_skip_to_end:Nw #1#2 )
2210 {
2211   \__bool_eval_skip_to_end_ii:Nw #1#2 ( % )
2212   \q_no_value \q_stop
2213   {#2}
2214 }
```

If no right parenthesis, then #3 is no_value and we are done, return the boolean #1. If there is, we need to grab a () pair and then recurse

```
2215 \cs_new:Npn \__bool_eval_skip_to_end_ii:Nw #1#2 ( #3#4 \q_stop #5 % )
2216 {
2217   \quark_if_no_value:NTF #3
2218   {#1}
2219   { \__bool_eval_skip_to_end_iii:Nw #1 #5 }
2220 }
```

Keep the boolean, throw away anything up to the (as it is irrelevant, remove a () pair but remember to reinsert #3 as it may contain (tokens!

```
2221 \cs_new:Npn \__bool_eval_skip_to_end_iii:Nw #1#2 ( #3 )
2222   { % (
2223     \__bool_eval_skip_to_end:Nw #1#3 )
2224 }
```

(End definition for `__bool_&_0:w` This function is documented on page 38.)

\bool_not_p:n The Not variant just reverses the outcome of `\bool_if_p:n`. Can be optimized but this is nice and simple and according to the implementation plan. Not even particularly useful to have it when the infix notation is easier to use.

```
2225 \cs_new:Npn \bool_not_p:n #1 { \bool_if_p:n { ! ( #1 ) } }
```

(End definition for `\bool_not_p:n` This function is documented on page 39.)

\bool_xor_p:nn Exclusive or. If the boolean expressions have same truth value, return false, otherwise return true.

```
2226 \cs_new:Npn \bool_xor_p:nn #1#2
2227 {
2228   \int_compare:nNnTF { \bool_if_p:n {#1} } = { \bool_if_p:n {#2} }
2229     \c_false_bool
2230   \c_true_bool
2231 }
```

(End definition for `\bool_xor_p:nn` This function is documented on page 39.)

5.5 Logical loops

\bool_while_do:Nn **\bool_while_do:cn** A `while` loop where the boolean is tested before executing the statement. The “while” version executes the code as long as the boolean is true; the “until” version executes the code as long as the boolean is false.

```
2232 \cs_new:Npn \bool_while_do:Nn #1#2
2233   { \bool_if:NT #1 { #2 \bool_while_do:Nn #1 {#2} } }
2234 \cs_new:Npn \bool_until_do:Nn #1#2
2235   { \bool_if:NF #1 { #2 \bool_until_do:Nn #1 {#2} } }
2236 \cs_generate_variant:Nn \bool_while_do:Nn { c }
2237 \cs_generate_variant:Nn \bool_until_do:Nn { c }
```

(End definition for `\bool_while_do:Nn` and `\bool_while_do:cn` These functions are documented on page ??.)

\bool_do_while:Nn **\bool_do_while:cn** A do-while loop where the body is performed at least once and the boolean is tested after executing the body. Otherwise identical to the above functions.

```
2238 \cs_new:Npn \bool_do_while:Nn #1#2
2239   { #2 \bool_if:NT #1 { \bool_do_while:Nn #1 {#2} } }
2240 \cs_new:Npn \bool_do_until:Nn #1#2
2241   { #2 \bool_if:NF #1 { \bool_do_until:Nn #1 {#2} } }
2242 \cs_generate_variant:Nn \bool_do_while:Nn { c }
2243 \cs_generate_variant:Nn \bool_do_until:Nn { c }
```

(End definition for `\bool_do_while:Nn` and `\bool_do_while:cn` These functions are documented on page ??.)

```

\bool_while_do:nn
\bool_do_while:nn
\bool_until_do:nn
\bool_do_until:nn

Loop functions with the test either before or after the first body expansion.

2244 \cs_new:Npn \bool_while_do:nn #1#2
2245 {
2246     \bool_if:nT {#1}
2247     {
2248         #2
2249         \bool_while_do:nn {#1} {#2}
2250     }
2251 }
2252 \cs_new:Npn \bool_do_while:nn #1#2
2253 {
2254     #2
2255     \bool_if:nT {#1} { \bool_do_while:nn {#1} {#2} }
2256 }
2257 \cs_new:Npn \bool_until_do:nn #1#2
2258 {
2259     \bool_if:nF {#1}
2260     {
2261         #2
2262         \bool_until_do:nn {#1} {#2}
2263     }
2264 }
2265 \cs_new:Npn \bool_do_until:nn #1#2
2266 {
2267     #2
2268     \bool_if:nF {#1} { \bool_do_until:nn {#1} {#2} }
2269 }

(End definition for \bool_while_do:nn and others. These functions are documented on page 39.)

```

5.6 Producing n copies

2270 `(@@=prg)`

`\prg_replicate:nn`

```

\__prg_replicate:N
\__prg_replicate:first:N
    \__prg_replicate_
    \__prg_replicate_0:n
    \__prg_replicate_1:n
    \__prg_replicate_2:n
    \__prg_replicate_3:n
    \__prg_replicate_4:n
    \__prg_replicate_5:n
    \__prg_replicate_6:n
    \__prg_replicate_7:n
    \__prg_replicate_8:n
    \__prg_replicate_9:n
\__prg_replicate:first_--n
\__prg_replicate:first_0:n
\__prg_replicate:first_1:n
\__prg_replicate:first_2:n
\__prg_replicate:first_3:n
\__prg_replicate:first_4:n
\__prg_replicate:first_5:n
\__prg_replicate:first_6:n
\__prg_replicate:first_7:n
\__prg_replicate:first_8:n
\__prg_replicate:first_9:n

```

This function uses a cascading csname technique by David Kastrup (who else :-)

The idea is to make the input 25 result in first adding five, and then 20 copies of the code to be replicated. The technique uses cascading csnames which means that we start building several csnames so we end up with a list of functions to be called in reverse order. This is important here (and other places) because it means that we can for instance make the function that inserts five copies of something to also hand down ten to the next function in line. This is exactly what happens here: in the example with 25 then the next function is the one that inserts two copies but it sees the ten copies handed down by the previous function. In order to avoid the last function to insert say, 100 copies of the original argument just to gobble them again we define separate functions to be inserted first. These functions also close the expansion of `__int_to_roman:w`, which ensures that `\prg_replicate:nn` only requires two steps of expansion.

This function has one flaw though: Since it constantly passes down ten copies of its previous argument it will severely affect the main memory once you start demanding hundreds of thousands of copies. Now I don't think this is a real limitation for any ordinary

use, and if necessary, it is possible to write `\prg_replicate:nn{1000}{\prg_replicate:nn{1000}{(code)}}`. An alternative approach is to create a string of m's with `_int_to_roman:w` which can be done with just four macros but that method has its own problems since it can exhaust the string pool. Also, it is considerably slower than what we use here so the few extra csnames are well spent I would say.

```

2271 \cs_new:Npn \prg_replicate:nn #1
2272 {
2273     \_int_to_roman:w
2274     \exp_after:wN \_prg_replicate_first:N
2275     \_int_value:w \_int_eval:w #1 \_int_eval_end:
2276     \cs_end:
2277 }
2278 \cs_new:Npn \_prg_replicate:N #1
2279 { \cs:w __prg_replicate_#1 :n \_prg_replicate:N }
2280 \cs_new:Npn \_prg_replicate_first:N #1
2281 { \cs:w __prg_replicate_first_ #1 :n \_prg_replicate:N }

```

Then comes all the functions that do the hard work of inserting all the copies. The first function takes `:n` as a parameter.

```

2282 \cs_new:Npn \_prg_replicate_ :n #1 { \cs_end: }
2283 \cs_new:cpn { __prg_replicate_0:n } #1 { \cs_end: {#1#1#1#1#1#1#1#1#1} }
2284 \cs_new:cpn { __prg_replicate_1:n } #1 { \cs_end: {#1#1#1#1#1#1#1#1#1} #1 }
2285 \cs_new:cpn { __prg_replicate_2:n } #1 { \cs_end: {#1#1#1#1#1#1#1#1#1} #1#1 }
2286 \cs_new:cpn { __prg_replicate_3:n } #1
2287 { \cs_end: {#1#1#1#1#1#1#1#1} #1#1#1 }
2288 \cs_new:cpn { __prg_replicate_4:n } #1
2289 { \cs_end: {#1#1#1#1#1#1#1#1} #1#1#1#1 }
2290 \cs_new:cpn { __prg_replicate_5:n } #1
2291 { \cs_end: {#1#1#1#1#1#1#1#1} #1#1#1#1#1 }
2292 \cs_new:cpn { __prg_replicate_6:n } #1
2293 { \cs_end: {#1#1#1#1#1#1#1#1} #1#1#1#1#1#1 }
2294 \cs_new:cpn { __prg_replicate_7:n } #1
2295 { \cs_end: {#1#1#1#1#1#1#1#1} #1#1#1#1#1#1#1 }
2296 \cs_new:cpn { __prg_replicate_8:n } #1
2297 { \cs_end: {#1#1#1#1#1#1#1#1} #1#1#1#1#1#1#1 }
2298 \cs_new:cpn { __prg_replicate_9:n } #1
2299 { \cs_end: {#1#1#1#1#1#1#1#1} #1#1#1#1#1#1#1#1 }

```

Users shouldn't ask for something to be replicated once or even not at all but...

```

2300 \cs_new:cpn { __prg_replicate_first_-:n } #1
2301 {
2302     \c_zero
2303     \__msg_kernel_expandable_error:nn { kernel } { negative-replication }
2304 }
2305 \cs_new:cpn { __prg_replicate_first_0:n } #1 { \c_zero }
2306 \cs_new:cpn { __prg_replicate_first_1:n } #1 { \c_zero #1 }
2307 \cs_new:cpn { __prg_replicate_first_2:n } #1 { \c_zero #1#1 }
2308 \cs_new:cpn { __prg_replicate_first_3:n } #1 { \c_zero #1#1#1 }
2309 \cs_new:cpn { __prg_replicate_first_4:n } #1 { \c_zero #1#1#1#1 }
2310 \cs_new:cpn { __prg_replicate_first_5:n } #1 { \c_zero #1#1#1#1#1 }

```

```

2311 \cs_new:cpn { __prg_replicate_first_6:n } #1 { \c_zero #1#1#1#1#1#1 }
2312 \cs_new:cpn { __prg_replicate_first_7:n } #1 { \c_zero #1#1#1#1#1#1#1 }
2313 \cs_new:cpn { __prg_replicate_first_8:n } #1 { \c_zero #1#1#1#1#1#1#1#1 }
2314 \cs_new:cpn { __prg_replicate_first_9:n } #1 { \c_zero #1#1#1#1#1#1#1#1#1 }

(End definition for \prg_replicate:nn This function is documented on page 40.)

```

5.7 Detecting TeX's mode

\mode_if_vertical_p: For testing vertical mode. Strikes me here on the bus with David, that as long as we are just talking about returning true and false states, we can just use the primitive conditionals for this and gobbling the `\c_zero` in the input stream. However this requires knowledge of the implementation so we keep things nice and clean and use the return statements.

```

2315 \prg_new_conditional:Npnn \mode_if_vertical: { p , T , F , TF }
2316   { \if_mode_vertical: \prg_return_true: \else: \prg_return_false: \fi: }

(End definition for \mode_if_vertical: These functions are documented on page 40.)

```

\mode_if_horizontal_p: For testing horizontal mode.

\mode_if_horizontal:TF

```

2317 \prg_new_conditional:Npnn \mode_if_horizontal: { p , T , F , TF }
2318   { \if_mode_horizontal: \prg_return_true: \else: \prg_return_false: \fi: }

(End definition for \mode_if_horizontal: These functions are documented on page 40.)

```

\mode_if_inner_p: For testing inner mode.

\mode_if_inner:TF

```

2319 \prg_new_conditional:Npnn \mode_if_inner: { p , T , F , TF }
2320   { \if_mode_inner: \prg_return_true: \else: \prg_return_false: \fi: }

(End definition for \mode_if_inner: These functions are documented on page 40.)

```

\mode_if_math_p: For testing math mode. At the beginning of an alignment cell, the programmer should insert `\scan_align_safe_stop:` before the test.

```

2321 \prg_new_conditional:Npnn \mode_if_math: { p , T , F , TF }
2322   { \if_mode_math: \prg_return_true: \else: \prg_return_false: \fi: }

(End definition for \mode_if_math: These functions are documented on page 40.)

```

5.8 Internal programming functions

\group_align_safe_begin: TeX's alignment structures present many problems. As Knuth says himself in *TeX: The Program*: "It's sort of a miracle whenever `\halign` or `\valign` work, [...]" One problem relates to commands that internally issues a `\cr` but also peek ahead for the next character for use in, say, an optional argument. If the next token happens to be a `&` with category code 4 we will get some sort of weird error message because the underlying `\futurelet` will store the token at the end of the alignment template. This could be a `&4` giving a message like `! Misplaced \cr.` or even worse: it could be the `\endtemplate` token causing even more trouble! To solve this we have to open a special group so that TeX still thinks it's on safe ground but at the same time we don't want to introduce any brace group that may find its way to the output. The following functions help with this by using code documented only in Appendix D of *The TeXbook*... We

place the `\if_false: { \fi:` part at that place so that the successive expansions of `\group_align_safe_begin/end:` are always brace balanced.

```

2323 \cs_new_nopar:Npn \group_align_safe_begin:
2324   { \if_int_compare:w \if_false: { \fi: ' } = \c_zero \fi: }
2325 \cs_new_nopar:Npn \group_align_safe_end:
2326   { \if_int_compare:w '{ = \c_zero } \fi: }
(End definition for \group_align_safe_begin: and \group_align_safe_end:)

```

\scan_align_safe_stop: When TeX is in the beginning of an align cell (right after the `\cr` or `&`) it is in a somewhat strange mode as it is looking ahead to find an `\omit` or `\noalign` and hasn't looked at the preamble yet. Thus an `\ifmmode` test at the start of an array cell (where math mode is introduced by the preamble, not in the cell itself) will always fail unless we stop TeX from scanning ahead. With ε -TeX's first version, this required inserting `\scan_stop:`, but not in all cases (see below). This is no longer needed with a newer ε -TeX, since protected macros are not expanded anymore at the beginning of an alignment cell. We can thus use an empty protected macro to stop TeX.

```
2327 \cs_new_protected_nopar:Npn \scan_align_safe_stop: { }
```

Let us now explain the earlier version. We don't want to insert a `\scan_stop:` every time as that will destroy kerning between letters³. Unfortunately there is no way to detect if we're in the beginning of an alignment cell as they have different characteristics depending on column number, *etc.* However we *can* detect if we're in an alignment cell by checking the current group type and we can also check if the previous node was a character or ligature. What is done here is that `\scan_stop:` is only inserted if a) we're in the outer part of an alignment cell and b) the last node *wasn't* a char node or a ligature node. Thus an older definition here was

```

\cs_new_nopar:Npn \scan_align_safe_stop:
{
  \int_compare:nNnT \etex_currentgroup:type:D = \c_six
  {
    \int_compare:nNnF \etex_lastnode:type:D = \c_zero
    {
      \int_compare:nNnF \etex_lastnode:type:D = \c_seven
      { \scan_stop: }
    }
  }
}

```

However, this is not truly expandable, as there are places where the `\scan_stop:` ends up in the result.

(End definition for `\scan_align_safe_stop:`)

```
2328 <@=prg>
```

³Unless we enforce an extra pass with an appropriate value of `\pretolerance`.

`__prg_variable_get_scope:N`
`__prg_variable_get_scope:w`
`__prg_variable_get_type:N`
`__prg_variable_get_type:w`

Expandable functions to find the type of a variable, and to return g if the variable is global. The trick for `__prg_variable_get_scope:N` is the same as that in `__cs-split_function>NN`, but it can be simplified as the requirements here are less complex.

```
2329 \group_begin:
2330   \tex_lccode:D `* = 'g \scan_stop:
2331   \tex_catcode:D `* = \c_twelve
2332 \tl_to_lowercase:n
2333 {
2334   \group_end:
2335   \cs_new:Npn \__prg_variable_get_scope:N #1
2336   {
2337     \exp_after:wN \exp_after:wn
2338     \exp_after:wN \__prg_variable_get_scope:w
2339       \cs_to_str:N #1 \exp_stop_f: \q_stop
2340   }
2341   \cs_new:Npn \__prg_variable_get_scope:w #1#2 \q_stop
2342   { \token_if_eq_meaning:NNT * #1 { g } }
2343 }
2344 \group_begin:
2345   \tex_lccode:D `* = '_ \scan_stop:
2346   \tex_catcode:D `* = \c_twelve
2347 \tl_to_lowercase:n
2348 {
2349   \group_end:
2350   \cs_new:Npn \__prg_variable_get_type:N #1
2351   {
2352     \exp_after:wN \__prg_variable_get_type:w
2353       \token_to_str:N #1 * a \q_stop
2354   }
2355   \cs_new:Npn \__prg_variable_get_type:w #1 * #2#3 \q_stop
2356   {
2357     \token_if_eq_meaning:NNTF a #2
2358       {#1}
2359       { \__prg_variable_get_type:w #2#3 \q_stop }
2360   }
2361 }
```

(End definition for `__prg_variable_get_scope:N` This function is documented on page 41.)

`\g__prg_map_int`

A nesting counter for mapping.

```
2362 \int_new:N \g__prg_map_int
```

(End definition for `\g__prg_map_int` This variable is documented on page 42.)

`__prg_break_point:Nn`
`__prg_map_break:Nn`

These are defined in `l3basics`, as they are needed “early”. This is just a reminder that that is the case!

(End definition for `__prg_break_point:Nn` This function is documented on page 42.)

`__prg_break_point:`
 `__prg_break:`
`__prg_break:n`

Also done in `l3basics` as in format mode these are needed within `l3alloc`.

(End definition for `__prg_break_point:` This function is documented on page ??.)

5.9 Deprecated functions

These were deprecated on 2012-02-08, and will be removed entirely by 2012-05-31.

```
\prg_define_quicksort:nnn #1 is the name, #2 and #3 are the tokens enclosing the argument. For the somewhat strange clist type which doesn't enclose the items but uses a separator we define it by hand afterwards. When doing the first pass, the algorithm wraps all elements in braces and then uses a generic quicksort which works on token lists.
```

As an example

```
\prg_define_quicksort:nnn{seq}{\seq_elt:w}{\seq_elt_end:w}
```

defines the user function `\seq_quicksort:n` and furthermore expects to use the two functions `\seq_quicksort_compare:nnTF` which compares the items and `\seq_quicksort_function:n` which is placed before each sorted item. It is up to the programmer to define these functions when needed. For the `seq` type a sequence is a token list variable, so one additionally has to define

```
\cs_set_nopar:Npn \seq_quicksort:N{\exp_args:No\seq_quicksort:n}
```

For details on the implementation see “Sorting in T_EX’s Mouth” by Bernd Raichle. Firstly we define the function for parsing the initial list and then the braced list afterwards.

```
2363  {*deprecated}
2364  \cs_new_protected:Npn \prg_define_quicksort:nnn #1#2#3 {
2365    \cs_set:cpx{\#1_quicksort:n}##1{
2366      \exp_not:c{\#1_quicksort_start_partition:w} ##1
2367      \exp_not:n{\#2\q_nil#3\q_stop}
2368    }
2369    \cs_set:cpx{\#1_quicksort_braced:n}##1{
2370      \exp_not:c{\#1_quicksort_start_partition_braced:n} ##1
2371      \exp_not:N\q_nil\exp_not:N\q_stop
2372    }
2373    \cs_set:cpx {\#1_quicksort_start_partition:w} #2 ##1 #3{
2374      \exp_not:N \quark_if_nil:nT {\#1}\exp_not:N \use_none_delimit_by_q_stop:w
2375      \exp_not:c{\#1_quicksort_do_partition_i:nnnw} {\#1}{}{}}
2376    }
2377    \cs_set:cpx {\#1_quicksort_start_partition_braced:n} ##1 {
2378      \exp_not:N \quark_if_nil:nT {\#1}\exp_not:N \use_none_delimit_by_q_stop:w
2379      \exp_not:c{\#1_quicksort_do_partition_i_braced:nnnn} {\#1}{}{}}
2380    }
2381  
```

Now for doing the partitions.

```
2382  {*deprecated}
2383  \cs_set:cpx {\#1_quicksort_do_partition_i:nnnw} ##1##2##3 #2 ##4 #3 {
2384    \exp_not:N \quark_if_nil:nTF {\#4} \exp_not:c {\#1_do_quicksort_braced:nnnnw}
2385    {
2386      \exp_not:c{\#1_quicksort_compare:nnTF}{{\#1}{\#4}}
2387      \exp_not:c{\#1_quicksort_partition_greater_ii:nnnn}
```

```

2388     \exp_not:c{#1_quicksort_partition_less_ii:nnnn}
2389 }
2390 {##1}{##2}{##3}{##4}
2391 }
2392 \cs_set:cp{ #1_quicksort_do_partition_i_braced:nnnn} ##1##2##3##4 {
2393     \exp_not:N \quark_if_nil:nTF {##4} \exp_not:c {#1_do_quicksort_braced:nnnnw}
2394 {
2395     \exp_not:c{#1_quicksort_compare:nnTF}{##1}{##4}
2396     \exp_not:c{#1_quicksort_partition_greater_ii_braced:nnnn}
2397     \exp_not:c{#1_quicksort_partition_less_ii_braced:nnnn}
2398 }
2399 {##1}{##2}{##3}{##4}
2400 }
2401 \cs_set:cp{ #1_quicksort_do_partition_ii:nnnw} ##1##2##3 #2 ##4 #3 {
2402     \exp_not:N \quark_if_nil:nTF {##4} \exp_not:c {#1_do_quicksort_braced:nnnnw}
2403 {
2404     \exp_not:c{#1_quicksort_compare:nnTF}{##4}{##1}
2405     \exp_not:c{#1_quicksort_partition_less_i:nnnn}
2406     \exp_not:c{#1_quicksort_partition_greater_i:nnnn}
2407 }
2408 {##1}{##2}{##3}{##4}
2409 }
2410 \cs_set:cp{ #1_quicksort_do_partition_ii_braced:nnnn} ##1##2##3##4 {
2411     \exp_not:N \quark_if_nil:nTF {##4} \exp_not:c {#1_do_quicksort_braced:nnnnw}
2412 {
2413     \exp_not:c{#1_quicksort_compare:nnTF}{##4}{##1}
2414     \exp_not:c{#1_quicksort_partition_less_i_braced:nnnn}
2415     \exp_not:c{#1_quicksort_partition_greater_i_braced:nnnn}
2416 }
2417 {##1}{##2}{##3}{##4}
2418 }
2419 </deprecated>

```

This part of the code handles the two branches in each sorting. Again we will also have to do it braced.

```

2420 <*deprecated>
2421 \cs_set:cp{ #1_quicksort_partition_less_i:nnnn} ##1##2##3##4{
2422     \exp_not:c{#1_quicksort_do_partition_i:nnnw}{##1}{##2}{##4}{##3}
2423 \cs_set:cp{ #1_quicksort_partition_less_ii:nnnn} ##1##2##3##4{
2424     \exp_not:c{#1_quicksort_do_partition_ii:nnnw}{##1}{##2}{##3}{##4}
2425 \cs_set:cp{ #1_quicksort_partition_greater_i:nnnn} ##1##2##3##4{
2426     \exp_not:c{#1_quicksort_do_partition_i:nnnw}{##1}{##4}{##2}{##3}
2427 \cs_set:cp{ #1_quicksort_partition_greater_ii:nnnn} ##1##2##3##4{
2428     \exp_not:c{#1_quicksort_do_partition_ii:nnnw}{##1}{##2}{##4}{##3}
2429 \cs_set:cp{ #1_quicksort_partition_less_i_braced:nnnn} ##1##2##3##4{
2430     \exp_not:c{#1_quicksort_do_partition_i_braced:nnnn}{##1}{##2}{##4}{##3}
2431 \cs_set:cp{ #1_quicksort_partition_less_ii_braced:nnnn} ##1##2##3##4{
2432     \exp_not:c{#1_quicksort_do_partition_ii_braced:nnnn}{##1}{##2}{##3}{##4}
2433 \cs_set:cp{ #1_quicksort_partition_greater_i_braced:nnnn} ##1##2##3##4{
2434     \exp_not:c{#1_quicksort_do_partition_i_braced:nnnn}{##1}{##4}{##2}{##3}

```

```

2435   \cs_set:cpx {#1_quicksort_partition_greater_ii_braced:nnnn} ##1##2##3##4{
2436     \exp_not:c{#1_quicksort_do_partition_ii_braced:nnnn}{##1}{##2{##4}}{##3}
2437   
```

Finally, the big kahuna! This is where the sub-lists are sorted.

```

2438   {*deprecated}
2439     \cs_set:cpx {#1_do_quicksort_braced:nnnw} ##1##2##3##4\q_stop {
2440       \exp_not:c{#1_quicksort_braced:n}{##2}
2441       \exp_not:c{#1_quicksort_function:n}{##1}
2442       \exp_not:c{#1_quicksort_braced:n}{##3}
2443     }
2444   }
2445 
```

(End definition for `\prg_define_quicksort:nnn`)

`\prg_quicksort:n` A simple version. Sorts a list of tokens, uses the function `\prg_quicksort_compare:nnTF` to compare items, and places the function `\prg_quicksort_function:n` in front of each of them.

```

2446   {*deprecated}
2447   \prg_define_quicksort:nnn {prg}{}{}
2448 
```

(End definition for `\prg_quicksort:n` This function is documented on page ??.)

`\prg_quicksort_function:n`

`\prg_quicksort_compare:nnTF`

```

2449   {*deprecated}
2450   \cs_set:Npn \prg_quicksort_function:n {\ERROR}
2451   \cs_set:Npn \prg_quicksort_compare:nnTF {\ERROR}
2452 
```

(End definition for `\prg_quicksort_function:n` This function is documented on page ??.)

These were deprecated on 2011-05-27 and will be removed entirely by 2011-08-31.

`\prg_new_map_functions:Nn` As we have restructured the structured variables, these are no longer needed.

`\prg_set_map_functions:Nn`

```

2453   {*deprecated}
2454   \cs_new_protected:Npn \prg_new_map_functions:Nn #1#2 { \deprecated }
2455   \cs_new_protected:Npn \prg_set_map_functions:Nn #1#2 { \deprecated }
2456 
```

(End definition for `\prg_new_map_functions:Nn` This function is documented on page ??.)

Deprecated 2012-06-03 for removal after 2012-12-31.

`\prg_case_int:nnn` Moved to more sensible modules.

```

2457   \cs_new_eq:NN \prg_case_int:nnn \int_case:nnn
2458   \cs_new_eq:NN \prg_case_str:nnn \str_case:nnn
2459   \cs_new_eq:NN \prg_case_str:onn \str_case:onn
2460   \cs_new_eq:NN \prg_case_str:xxn \str_case_x:nnn
2461   \cs_new_eq:NN \prg_case_t1:Nnn \t1_case:Nnn
2462   \cs_new_eq:NN \prg_case_t1:cnn \t1_case:cnn

```

(End definition for `\prg_case_int:nnn` and others. These functions are documented on page ??.)

Deprecated 2012-06-04 for removal after 2012-12-31.

```

\prg_stepwise_function:nnnN
  \prg_stepwise_inline:nnnn
  \prg_stepwise_variable:nnnNn
2463  \cs_new_eq:NN \prg_stepwise_function:nnnN  \int_step_function:nnnN
2464  \cs_new_eq:NN \prg_stepwise_inline:nnnn  \int_step_inline:nnnn
2465  \cs_new_eq:NN \prg_stepwise_variable:nnnNn \int_step_variable:nnnNn
(End definition for \prg_stepwise_function:nnnN, \prg_stepwise_inline:nnnn, and \prg_stepwise_variable:nnnNn
These functions are documented on page ??.)
2466  </initex | package>

```

6 l3quark implementation

The following test files are used for this code: *m3quark001.lvt*.

```

2467  <*initex | package>
2468  <*package>
2469  \ProvidesExplPackage
2470  {\ExplFileName}{\ExplFileVersion}{\ExplFileDescription}
2471  \__expl_package_check:
2472  </package>

```

6.1 Quarks

\quark_new:N Allocate a new quark.

```

2473  \cs_new_protected:Npn \quark_new:N #1 { \tl_const:Nn #1 {#1} }
(End definition for \quark_new:N This function is documented on page 44.)

```

\q_nil
\q_mark
\q_no_value
\q_stop Some “public” quarks. **\q_stop** is an “end of argument” marker, **\q_nil** is a empty value and **\q_no_value** marks an empty argument.

```

2474  \quark_new:N \q_nil
2475  \quark_new:N \q_mark
2476  \quark_new:N \q_no_value
2477  \quark_new:N \q_stop
(End definition for \q_nil and others. These variables are documented on page 44.)

```

\q_recursion_tail
\q_recursion_stop Quarks for ending recursions. Only ever used there! **\q_recursion_tail** is appended to whatever list structure we are doing recursion on, meaning it is added as a proper list item with whatever list separator is in use. **\q_recursion_stop** is placed directly after the list.

```

2478  \quark_new:N \q_recursion_tail
2479  \quark_new:N \q_recursion_stop
(End definition for \q_recursion_tail and \q_recursion_stop These variables are documented on page
45.)

```

```
\quark_if_recursion_tail_stop:N  
\quark_if_recursion_tail_stop:do:Nn
```

When doing recursions, it is easy to spend a lot of time testing if the end marker has been found. To avoid this, a dedicated end marker is used each time a recursion is set up. Thus if the marker is found everything can be wrapped up and finished off. The simple case is when the test can guarantee that only a single token is being tested. In this case, there is just a dedicated copy of the standard quark test. Both a gobbling version and one inserting end code are provided.

```
2480 \cs_new:Npn \quark_if_recursion_tail_stop:N #1  
2481 {  
2482   \if_meaning:w \q_recursion_tail #1  
2483     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w  
2484   \fi:  
2485 }  
2486 \cs_new:Npn \quark_if_recursion_tail_stop:do:Nn #1  
2487 {  
2488   \if_meaning:w \q_recursion_tail #1  
2489     \exp_after:wN \use_i_delimit_by_q_recursion_stop:nw  
2490   \else:  
2491     \exp_after:wN \use_none:n  
2492   \fi:  
2493 }
```

(End definition for \quark_if_recursion_tail_stop:N This function is documented on page 45.)

```
\quark_if_recursion_tail_stop:n  
\quark_if_recursion_tail_stop:o  
\quark_if_recursion_tail_stop:nn  
\quark_if_recursion_tail_stop:on
```

The same idea applies when testing multiple tokens, but here we just compare the token list to \q_recursion_tail as a string.

```
2494 \cs_new:Npn \quark_if_recursion_tail_stop:n #1  
2495 {  
2496   \if_int_compare:w \pdftex_strcmp:D  
2497     { \exp_not:N \q_recursion_tail } { \exp_not:n {#1} } = \c_zero  
2498     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w  
2499   \fi:  
2500 }  
2501 \cs_new:Npn \quark_if_recursion_tail_stop:do:nn #1  
2502 {  
2503   \if_int_compare:w \pdftex_strcmp:D  
2504     { \exp_not:N \q_recursion_tail } { \exp_not:n {#1} } = \c_zero  
2505     \exp_after:wN \use_i_delimit_by_q_recursion_stop:nw  
2506   \else:  
2507     \exp_after:wN \use_none:n  
2508   \fi:  
2509 }  
2510 \cs_generate_variant:Nn \quark_if_recursion_tail_stop:n { o }  
2511 \cs_generate_variant:Nn \quark_if_recursion_tail_stop:do:nn { o }  
(End definition for \quark_if_recursion_tail_stop:n and \quark_if_recursion_tail_stop:o These functions are documented on page ??.)
```

```
\_quark_if_recursion_tail_break:NN  
\_quark_if_recursion_tail_break:nN
```

Analogs of the \quark_if_recursion_tail_stop... functions. Break the mapping using #2.

```
2512 \cs_new:Npn \_quark_if_recursion_tail_break:NN #1#2
```

```

2513   {
2514     \if_meaning:w \q_recursion_tail #1
2515       \exp_after:wN #2
2516     \fi:
2517   }
2518 \cs_new:Npn \__quark_if_recursion_tail_break:nN #1#2
2519   {
2520     \if_int_compare:w \pdftex_strcmp:D
2521       { \exp_not:N \q_recursion_tail } { \exp_not:n {#1} } = \c_zero
2522       \exp_after:wN #2
2523     \fi:
2524   }
(End definition for \__quark_if_recursion_tail_break:NN This function is documented on page ??.)
```

\quark_if_nil_p:N
\quark_if_nil:NTF
\quark_if_no_value_p:N
\quark_if_no_value_p:c
\quark_if_no_value:NTF
\quark_if_no_value:cTF

Here we test if we found a special quark as the first argument. We better start with \q_no_value as the first argument since the whole thing may otherwise loop if #1 is wrongly given a string like aabc instead of a single token.⁴

```

2525 \prg_new_conditional:Nnn \quark_if_nil:N { p, T , F , TF }
2526   {
2527     \if_meaning:w \q_nil #1
2528       \prg_return_true:
2529     \else:
2530       \prg_return_false:
2531     \fi:
2532   }
2533 \prg_new_conditional:Nnn \quark_if_no_value:N { p, T , F , TF }
2534   {
2535     \if_meaning:w \q_no_value #1
2536       \prg_return_true:
2537     \else:
2538       \prg_return_false:
2539     \fi:
2540   }
2541 \cs_generate_variant:Nn \quark_if_no_value_p:N { c }
2542 \cs_generate_variant:Nn \quark_if_no_value:NT { c }
2543 \cs_generate_variant:Nn \quark_if_no_value:NF { c }
2544 \cs_generate_variant:Nn \quark_if_no_value:NTF { c }
```

(End definition for \quark_if_nil:N These functions are documented on page ??.)

\quark_if_nil_p:n
\quark_if_nil_p:V
\quark_if_nil_p:o
\quark_if_nil:nTF
\quark_if_nil:VTF
\quark_if_nil:oTF
\quark_if_no_value_p:n
\quark_if_no_value:nTF

These are essentially \str_if_eq:nn tests but done directly.

```

2545 \prg_new_conditional:Nnn \quark_if_nil:n { p, T , F , TF }
2546   {
2547     \if_int_compare:w \pdftex_strcmp:D
2548       { \exp_not:N \q_nil } { \exp_not:n {#1} } = \c_zero
2549       \prg_return_true:
2550     \else:
2551       \prg_return_false:
```

⁴It may still loop in special circumstances however!

```

2552     \fi:
2553 }
2554 \prg_new_conditional:Nnn \quark_if_no_value:n { p, T , F , TF }
2555 {
2556     \if_int_compare:w \pdftex_strcmp:D
2557         { \exp_not:N \q_no_value } { \exp_not:n {#1} } = \c_zero
2558         \prg_return_true:
2559     \else:
2560         \prg_return_false:
2561     \fi:
2562 }
2563 \cs_generate_variant:Nn \quark_if_nil_p:n { V , o }
2564 \cs_generate_variant:Nn \quark_if_nil:nTF { V , o }
2565 \cs_generate_variant:Nn \quark_if_nil:nT { V , o }
2566 \cs_generate_variant:Nn \quark_if_nil:nF { V , o }
(End definition for \quark_if_nil:n, \quark_if_nil:V, and \quark_if_nil:o These functions are documented on page 44.)

```

\q__tl_act_mark These private quarks are needed by l3tl, but that is loaded before the quark module, hence their definition is deferred.

```

2567 \quark_new:N \q__tl_act_mark
2568 \quark_new:N \q__tl_act_stop
(End definition for \q__tl_act_mark and \q__tl_act_stop These variables are documented on page ??.)

```

6.2 Scan marks

2569 <@=scan>

\g__scan_marks_tl The list of all scan marks currently declared.

```

2570 \tl_new:N \g__scan_marks_tl
(End definition for \g__scan_marks_tl This variable is documented on page ??.)

```

__scan_new:N Check whether the variable is already a scan mark, then declare it to be equal to \scan_stop: globally.

```

2571 \cs_new_protected:Npn \__scan_new:N #1
2572 {
2573     \tl_if_in:NnTF \g__scan_marks_tl { #1 }
2574     {
2575         \__msg_kernel_error:nnx { kernel } { scanmark-already-defined }
2576         { \token_to_str:N #1 }
2577     }
2578     {
2579         \tl_gput_right:Nn \g__scan_marks_tl {#1}
2580         \cs_new_eq:NN #1 \scan_stop:
2581     }
2582 }
(End definition for \__scan_new:N)

```

\s__stop We only declare one scan mark here, more can be defined by specific modules.

2583 __scan_new:N \s__stop

(End definition for \s__stop This variable is documented on page 47.)

_use_none_delimit_by_s__stop:w Similar to \use_none_delimit_by_q_stop:w.

2584 \cs_new:Npn _use_none_delimit_by_s__stop:w #1 \s__stop { }

(End definition for _use_none_delimit_by_s__stop:w)

6.3 Deprecated quark functions

\quark_if_recursion_tail_break:N It's not clear what breaking function we should be using here, so I'm picking one somewhat arbitrarily.

2585 \cs_new:Npn \quark_if_recursion_tail_break:N #1
2586 { __quark_if_recursion_tail_break:NN #1 \prg_break: }
2587 \cs_new:Npn \quark_if_recursion_tail_break:n #1
2588 { __quark_if_recursion_tail_break:nN {#1} \prg_break: }

(End definition for \quark_if_recursion_tail_break:N and \quark_if_recursion_tail_break:n These functions are documented on page ??.)

2589 ⟨/initex | package⟩

7 l3token implementation

2590 ⟨*initex | package⟩
2591 ⟨@=token⟩
2592 ⟨*package⟩
2593 \ProvidesExplPackage
2594 { \ExplFileName } { \ExplFileVersion } { \ExplFileDescription }
2595 __expl_package_check:
2596 ⟨/package⟩

7.1 Character tokens

\char_set_catcode:nn Category code changes.

2597 \cs_new_protected:Npn \char_set_catcode:nn #1#2
2598 { \tex_catcode:D #1 = \int_eval:w #2 \int_eval_end: }
2599 \cs_new:Npn \char_value_catcode:n #1
2600 { \tex_the:D \tex_catcode:D \int_eval:w #1 \int_eval_end: }
2601 \cs_new_protected:Npn \char_show_value_catcode:n #1
2602 { \tex_showthe:D \tex_catcode:D \int_eval:w #1 \int_eval_end: }
(End definition for \char_set_catcode:nn This function is documented on page 50.)

\char_set_catcode_escape:N
\char_set_catcode_group_begin:N
\char_set_catcode_group_end:N
\char_set_catcode_math_toggle:N
\char_set_catcode_alignment:N

\char_set_catcode_end_line:N

\char_set_catcode_parameter:N

\char_set_catcode_math_superscript:N

\char_set_catcode_math_subscript:N

\char_set_catcode_ignore:N

\char_set_catcode_space:N

\char_set_catcode_letter:N

\char_set_catcode_other:N

\char_set_catcode_active:N

\char_set_catcode_comment:N

```

2607 \cs_new_protected:Npn \char_set_catcode_group_end:N #1
2608   { \char_set_catcode:nn { '#1 } \c_two }
2609 \cs_new_protected:Npn \char_set_catcode_math_toggle:N #1
2610   { \char_set_catcode:nn { '#1 } \c_three }
2611 \cs_new_protected:Npn \char_set_catcode_alignment:N #1
2612   { \char_set_catcode:nn { '#1 } \c_four }
2613 \cs_new_protected:Npn \char_set_catcode_end_line:N #1
2614   { \char_set_catcode:nn { '#1 } \c_five }
2615 \cs_new_protected:Npn \char_set_catcode_parameter:N #1
2616   { \char_set_catcode:nn { '#1 } \c_six }
2617 \cs_new_protected:Npn \char_set_catcode_math_superscript:N #1
2618   { \char_set_catcode:nn { '#1 } \c_seven }
2619 \cs_new_protected:Npn \char_set_catcode_math_subscript:N #1
2620   { \char_set_catcode:nn { '#1 } \c_eight }
2621 \cs_new_protected:Npn \char_set_catcode_ignore:N #1
2622   { \char_set_catcode:nn { '#1 } \c_nine }
2623 \cs_new_protected:Npn \char_set_catcode_space:N #1
2624   { \char_set_catcode:nn { '#1 } \c_ten }
2625 \cs_new_protected:Npn \char_set_catcode_letter:N #1
2626   { \char_set_catcode:nn { '#1 } \c_eleven }
2627 \cs_new_protected:Npn \char_set_catcode_other:N #1
2628   { \char_set_catcode:nn { '#1 } \c_twelve }
2629 \cs_new_protected:Npn \char_set_catcode_active:N #1
2630   { \char_set_catcode:nn { '#1 } \c_thirteen }
2631 \cs_new_protected:Npn \char_set_catcode_comment:N #1
2632   { \char_set_catcode:nn { '#1 } \c_fourteen }
2633 \cs_new_protected:Npn \char_set_catcode_invalid:N #1
2634   { \char_set_catcode:nn { '#1 } \c_fifteen }

(End definition for \char_set_catcode_escape:N and others. These functions are documented on page
49.)

```

```

\char_set_catcode_escape:n
\char_set_catcode_group_begin:n
\char_set_catcode_group_end:n
\char_set_catcode_math_toggle:n
\char_set_catcode_alignment:n
\char_set_catcode_end_line:n
\char_set_catcode_parameter:n
\char_set_catcode_math_superscript:n
\char_set_catcode_math_subscript:n
\char_set_catcode_ignore:n
\char_set_catcode_space:n
\char_set_catcode_letter:n
\char_set_catcode_other:n
\char_set_catcode_active:n
\char_set_catcode_comment:n
\char_set_catcode_invalid:n

```

```

2635 \cs_new_protected:Npn \char_set_catcode_escape:n #1
2636   { \char_set_catcode:nn {#1} \c_zero }
2637 \cs_new_protected:Npn \char_set_catcode_group_begin:n #1
2638   { \char_set_catcode:nn {#1} \c_one }
2639 \cs_new_protected:Npn \char_set_catcode_group_end:n #1
2640   { \char_set_catcode:nn {#1} \c_two }
2641 \cs_new_protected:Npn \char_set_catcode_math_toggle:n #1
2642   { \char_set_catcode:nn {#1} \c_three }
2643 \cs_new_protected:Npn \char_set_catcode_alignment:n #1
2644   { \char_set_catcode:nn {#1} \c_four }
2645 \cs_new_protected:Npn \char_set_catcode_end_line:n #1
2646   { \char_set_catcode:nn {#1} \c_five }
2647 \cs_new_protected:Npn \char_set_catcode_parameter:n #1
2648   { \char_set_catcode:nn {#1} \c_six }
2649 \cs_new_protected:Npn \char_set_catcode_math_superscript:n #1
2650   { \char_set_catcode:nn {#1} \c_seven }
2651 \cs_new_protected:Npn \char_set_catcode_math_subscript:n #1
2652   { \char_set_catcode:nn {#1} \c_eight }

```

```

2653 \cs_new_protected:Npn \char_set_catcode_ignore:n #1
2654 { \char_set_catcode:nn {#1} \c_nine }
2655 \cs_new_protected:Npn \char_set_catcode_space:n #1
2656 { \char_set_catcode:nn {#1} \c_ten }
2657 \cs_new_protected:Npn \char_set_catcode_letter:n #1
2658 { \char_set_catcode:nn {#1} \c_eleven }
2659 \cs_new_protected:Npn \char_set_catcode_other:n #1
2660 { \char_set_catcode:nn {#1} \c_twelve }
2661 \cs_new_protected:Npn \char_set_catcode_active:n #1
2662 { \char_set_catcode:nn {#1} \c_thirteen }
2663 \cs_new_protected:Npn \char_set_catcode_comment:n #1
2664 { \char_set_catcode:nn {#1} \c_fourteen }
2665 \cs_new_protected:Npn \char_set_catcode_invalid:n #1
2666 { \char_set_catcode:nn {#1} \c_fifteen }

(End definition for \char_set_catcode_escape:n and others. These functions are documented on page 49.)

```

Pretty repetitive, but necessary!

```

2667 \cs_new_protected:Npn \char_set_mathcode:nn #1#2
2668 { \tex_mathcode:D #1 = \__int_eval:w #2 \__int_eval_end: }
2669 \cs_new:Npn \char_value_mathcode:n #1
2670 { \tex_the:D \tex_mathcode:D \__int_eval:w #1\__int_eval_end: }
2671 \cs_new_protected:Npn \char_show_value_mathcode:n #1
2672 { \tex_showthe:D \tex_mathcode:D \__int_eval:w #1\__int_eval_end: }
2673 \cs_new_protected:Npn \char_set_lccode:nn #1#2
2674 { \tex_lccode:D #1 = \__int_eval:w #2 \__int_eval_end: }
2675 \cs_new:Npn \char_value_lccode:n #1
2676 { \tex_the:D \tex_lccode:D \__int_eval:w #1\__int_eval_end: }
2677 \cs_new_protected:Npn \char_show_value_lccode:n #1
2678 { \tex_showthe:D \tex_lccode:D \__int_eval:w #1\__int_eval_end: }
2679 \cs_new_protected:Npn \char_set_uccode:nn #1#2
2680 { \tex_uccode:D #1 = \__int_eval:w #2 \__int_eval_end: }
2681 \cs_new:Npn \char_value_uccode:n #1
2682 { \tex_the:D \tex_uccode:D \__int_eval:w #1\__int_eval_end: }
2683 \cs_new_protected:Npn \char_show_value_uccode:n #1
2684 { \tex_showthe:D \tex_uccode:D \__int_eval:w #1\__int_eval_end: }
2685 \cs_new_protected:Npn \char_set_sfcode:nn #1#2
2686 { \tex_sfcode:D #1 = \__int_eval:w #2 \__int_eval_end: }
2687 \cs_new:Npn \char_value_sfcode:n #1
2688 { \tex_the:D \tex_sfcode:D \__int_eval:w #1\__int_eval_end: }
2689 \cs_new_protected:Npn \char_show_value_sfcode:n #1
2690 { \tex_showthe:D \tex_sfcode:D \__int_eval:w #1\__int_eval_end: }

(End definition for \char_set_mathcode:nn This function is documented on page 52.)

```

7.2 Generic tokens

```

\token_to_meaning:N
\token_to_meaning:c
\token_to_str:N
\token_to_str:c

```

These are all defined in l3basics, as they are needed “early”. This is just a reminder that that is the case!

(End definition for \token_to_meaning:N and \token_to_meaning:c These functions are documented on page ??.)

`\token_new:Nn` Creates a new token.

```
2691 \cs_new_protected:Npn \token_new:Nn #1#2 { \cs_new_eq:NN #1 #2 }
```

(End definition for `\token_new:Nn`. This function is documented on page 52.)

`\c_group_begin_token`
`\c_group_end_token`
`\c_math_toggle_token`
`\c_alignment_token`
`\c_parameter_token`
`\c_math_superscript_token`
`\c_math_subscript_token`
`\c_space_token`
`\c_catcode_letter_token`
`\c_catcode_other_token`

```
2692 \cs_new_eq:NN \c_group_begin_token {
2693   \cs_new_eq:NN \c_group_end_token {
2694     \group_begin:
2695       \char_set_catcode_math_toggle:N \*
2696       \token_new:Nn \c_math_toggle_token { * }
2697       \char_set_catcode_alignment:N \*
2698       \token_new:Nn \c_alignment_token { * }
2699       \token_new:Nn \c_parameter_token { # }
2700       \token_new:Nn \c_math_superscript_token { ^ }
2701       \char_set_catcode_math_subscript:N \*
2702       \token_new:Nn \c_math_subscript_token { * }
2703       \token_new:Nn \c_space_token { ~ }
2704       \token_new:Nn \c_catcode_letter_token { a }
2705       \token_new:Nn \c_catcode_other_token { 1 }
2706     \group_end:
```

(End definition for `\c_group_begin_token` and others. These functions are documented on page 52.)

`\c_catcode_active_tl` Not an implicit token!

```
2707 \group_begin:
2708   \char_set_catcode_active:N \*
2709   \tl_const:Nn \c_catcode_active_tl { \exp_not:N * }
2710 \group_end:
```

(End definition for `\c_catcode_active_tl`. This variable is documented on page 52.)

`\l_char_active_seq`
`\l_char_special_seq` Two sequences for dealing with special characters. The first is characters which may be active, and contains the active characters themselves to allow easy redefinition. The second longer list is for “special” characters more generally, and these are escaped so that for example bulk code assignments can be carried out. In both cases, the order is by ASCII character code (as is done in for example `\ExplSyntaxOn`). The only complication is dealing with `_`, which requires the use of `\use:n` and `\use:nn`.

```
2711 \seq_new:N \l_char_active_seq
2712 \use:n
2713 {
2714   \group_begin:
2715   \char_set_catcode_active:N \
2716   \char_set_catcode_active:N \$
2717   \char_set_catcode_active:N \&
amp;2718   \char_set_catcode_active:N ^
2719   \char_set_catcode_active:N \
2720   \char_set_catcode_active:N \
2721   \use:nn
2722 }
```

```

2723     \group_end:
2724     \seq_set_split:Nnn \l_char_active_seq { }
2725   }
2726 }
2727 { { " $ & ^ _ ~ } } %$ 
2728 \seq_new:N \l_char_special_seq
2729 \seq_set_split:Nnn \l_char_special_seq { }
2730 { \ \" # \$ % & \\ ^ _ { } ~ }
(End definition for \l_char_active_seq and \l_char_special_seq These variables are documented on page 52.)
```

7.3 Token conditionals

`\token_if_group_begin_p:N`
`\token_if_group_begin:NTF`

Check if token is a begin group token. We use the constant `\c_group_begin_token` for this.

```

2731 \prg_new_conditional:Npnn \token_if_group_begin:N #1 { p , T , F , TF }
2732 {
2733   \if_catcode:w \exp_not:N #1 \c_group_begin_token
2734     \prg_return_true: \else: \prg_return_false: \fi:
2735 }
(End definition for \token_if_group_begin:N These functions are documented on page 53.)
```

`\token_if_group_end_p:N`
`\token_if_group_end:NTF`

Check if token is a end group token. We use the constant `\c_group_end_token` for this.

```

2736 \prg_new_conditional:Npnn \token_if_group_end:N #1 { p , T , F , TF }
2737 {
2738   \if_catcode:w \exp_not:N #1 \c_group_end_token
2739     \prg_return_true: \else: \prg_return_false: \fi:
2740 }
(End definition for \token_if_group_end:N These functions are documented on page 53.)
```

`\token_if_math_toggle_p:N`
`\token_if_math_toggle:NTF`

Check if token is a math shift token. We use the constant `\c_math_toggle_token` for this.

```

2741 \prg_new_conditional:Npnn \token_if_math_toggle:N #1 { p , T , F , TF }
2742 {
2743   \if_catcode:w \exp_not:N #1 \c_math_toggle_token
2744     \prg_return_true: \else: \prg_return_false: \fi:
2745 }
(End definition for \token_if_math_toggle:N These functions are documented on page 53.)
```

`\token_if_alignment_p:N`
`\token_if_alignment:NTF`

Check if token is an alignment tab token. We use the constant `\c_alignment_token` for this.

```

2746 \prg_new_conditional:Npnn \token_if_alignment:N #1 { p , T , F , TF }
2747 {
2748   \if_catcode:w \exp_not:N #1 \c_alignment_token
2749     \prg_return_true: \else: \prg_return_false: \fi:
2750 }
(End definition for \token_if_alignment:N These functions are documented on page 53.)
```

`\token_if_parameter_p:N` Check if token is a parameter token. We use the constant `\c_parameter_token` for this.
`\token_if_parameter:NTF` We have to trick TeX a bit to avoid an error message: within a group we prevent `\c_parameter_token` from behaving like a macro parameter character. The definitions of `\prg_new_conditional:Npnn` are global, so they will remain after the group.

```

2751 \group_begin:
2752 \cs_set_eq:NN \c_parameter_token \scan_stop:
2753 \prg_new_conditional:Npnn \token_if_parameter:N #1 { p , T , F , TF }
2754 {
2755   \if_catcode:w \exp_not:N #1 \c_parameter_token
2756     \prg_return_true: \else: \prg_return_false: \fi:
2757 }
2758 \group_end:

```

(End definition for `\token_if_parameter:N` These functions are documented on page 54.)

`\token_if_math_superscript_p:N` Check if token is a math superscript token. We use the constant `\c_math_superscript_token` for this.
`\token_if_math_superscript:NTF`

```

2759 \prg_new_conditional:Npnn \token_if_math_superscript:N #1 { p , T , F , TF }
2760 {
2761   \if_catcode:w \exp_not:N #1 \c_math_superscript_token
2762     \prg_return_true: \else: \prg_return_false: \fi:
2763 }

```

(End definition for `\token_if_math_superscript:N` These functions are documented on page 54.)

`\token_if_math_subscript_p:N` Check if token is a math subscript token. We use the constant `\c_math_subscript_token` for this.
`\token_if_math_subscript:NTF`

```

2764 \prg_new_conditional:Npnn \token_if_math_subscript:N #1 { p , T , F , TF }
2765 {
2766   \if_catcode:w \exp_not:N #1 \c_math_subscript_token
2767     \prg_return_true: \else: \prg_return_false: \fi:
2768 }

```

(End definition for `\token_if_math_subscript:N` These functions are documented on page 54.)

`\token_if_space_p:N` Check if token is a space token. We use the constant `\c_space_token` for this.
`\token_if_space:NTF`

```

2769 \prg_new_conditional:Npnn \token_if_space:N #1 { p , T , F , TF }
2770 {
2771   \if_catcode:w \exp_not:N #1 \c_space_token
2772     \prg_return_true: \else: \prg_return_false: \fi:
2773 }

```

(End definition for `\token_if_space:N` These functions are documented on page 54.)

`\token_if_letter_p:N` Check if token is a letter token. We use the constant `\c_catcode_letter_token` for this.
`\token_if_letter:NTF`

```

2774 \prg_new_conditional:Npnn \token_if_letter:N #1 { p , T , F , TF }
2775 {
2776   \if_catcode:w \exp_not:N #1 \c_catcode_letter_token
2777     \prg_return_true: \else: \prg_return_false: \fi:
2778 }

```

(End definition for `\token_if_letter:N` These functions are documented on page 54.)

`\token_if_other_p:N` Check if token is an other char token. We use the constant `\c_catcode_other_token` for this.
`\token_if_other:NTF`

```
2779 \prg_new_conditional:Npnn \token_if_other:N #1 { p , T , F , TF }
2780 {
2781   \if_catcode:w \exp_not:N #1 \c_catcode_other_token
2782     \prg_return_true: \else: \prg_return_false: \fi:
2783 }
```

(End definition for `\token_if_other:N` These functions are documented on page 54.)

`\token_if_active_p:N` Check if token is an active char token. We use the constant `\c_catcode_active_tl` for this. A technical point is that `\c_catcode_active_tl` is in fact a macro expanding to `\exp_not:N *`, where * is active.
`\token_if_active:NTF`

```
2784 \prg_new_conditional:Npnn \token_if_active:N #1 { p , T , F , TF }
2785 {
2786   \if_catcode:w \exp_not:N #1 \c_catcode_active_tl
2787     \prg_return_true: \else: \prg_return_false: \fi:
2788 }
```

(End definition for `\token_if_active:N` These functions are documented on page 54.)

`\token_if_eq_meaning_p:NN` Check if the tokens #1 and #2 have same meaning.
`\token_if_eq_meaning:NNTF`

```
2789 \prg_new_conditional:Npnn \token_if_eq_meaning:NN #1#2 { p , T , F , TF }
2790 {
2791   \if_meaning:w #1 #2
2792     \prg_return_true: \else: \prg_return_false: \fi:
2793 }
```

(End definition for `\token_if_eq_meaning:NN` These functions are documented on page 55.)

`\token_if_eq_catcode_p:NN` Check if the tokens #1 and #2 have same category code.
`\token_if_eq_catcode:NNTF`

```
2794 \prg_new_conditional:Npnn \token_if_eq_catcode:NN #1#2 { p , T , F , TF }
2795 {
2796   \if_catcode:w \exp_not:N #1 \exp_not:N #2
2797     \prg_return_true: \else: \prg_return_false: \fi:
2798 }
```

(End definition for `\token_if_eq_catcode:NN` These functions are documented on page 54.)

`\token_if_eq_charcode_p:NN` Check if the tokens #1 and #2 have same character code.
`\token_if_eq_charcode:NNTF`

```
2799 \prg_new_conditional:Npnn \token_if_eq_charcode:NN #1#2 { p , T , F , TF }
2800 {
2801   \if_charcode:w \exp_not:N #1 \exp_not:N #2
2802     \prg_return_true: \else: \prg_return_false: \fi:
2803 }
```

(End definition for `\token_if_eq_charcode:NN` These functions are documented on page 54.)

`\token_if_macro_p:N` When a token is a macro, `\token_to_meaning:N` will always output something like
`\long macro:#1->#1` so we could naively check to see if the meaning contains `->`.
`\token_if_macro:NTF` However, this can fail the five `\...mark` primitives, whose meaning has the form
`...mark:<user material>`. The problem is that the `<user material>` can contain `->`.
`_token_if_macro_p:w`

However, only characters, macros, and marks can contain the colon character. The idea is thus to grab until the first :, and analyse what is left. However, macros can have any combination of \long, \protected or \outer (not used in L^AT_EX3) before the string `macro:`. We thus only select the part of the meaning between the first `ma` and the first following :. If this string is `cro`, then we have a macro. If the string is `rk`, then we have a mark. The string can also be `cro parameter character` for a colon with a weird category code (namely the usual category code of #). Otherwise, it is empty.

This relies on the fact that \long, \protected, \outer cannot contain `ma`, regardless of the escape character, even if the escape character is `\m...`

Both `ma` and `:` must be of category code 12 (other), and we achieve using the standard lowercasing technique.

```

2804 \group_begin:
2805 \char_set_catcode_other:N \M
2806 \char_set_catcode_other:N \A
2807 \char_set_lccode:nn { '\; } { '\: }
2808 \char_set_lccode:nn { '\T } { '\T }
2809 \char_set_lccode:nn { '\F } { '\F }
2810 \tl_to_lowercase:n
2811 {
2812     \group_end:
2813     \prg_new_conditional:Npnn \token_if_macro:N #1 { p , T , F , TF }
2814     {
2815         \exp_after:wN \__token_if_macro_p:w
2816         \token_to_meaning:N #1 MA; \q_stop
2817     }
2818     \cs_new:Npn \__token_if_macro_p:w #1 MA #2 ; #3 \q_stop
2819     {
2820         \if_int_compare:w \pdftex_strcmp:D { #2 } { cro } = \c_zero
2821             \prg_return_true:
2822         \else:
2823             \prg_return_false:
2824         \fi:
2825     }
2826 }
```

(End definition for `\token_if_macro:N` These functions are documented on page 55.)

`\token_if_cs_p:N` Check if token has same catcode as a control sequence. This follows the same pattern as
`\token_if_cs:NTF` for `\token_if_letter:N` etc. We use `\scan_stop:` for this.

```

2827 \prg_new_conditional:Npnn \token_if_cs:N #1 { p , T , F , TF }
2828 {
2829     \if_catcode:w \exp_not:N #1 \scan_stop:
2830         \prg_return_true: \else: \prg_return_false: \fi:
2831 }
```

(End definition for `\token_if_cs:N` These functions are documented on page 55.)

`\token_if_expandable_p:N` Check if token is expandable. We use the fact that T_EX will temporarily convert `\exp_`-
`\token_if_expandable:NTF` `\not:N` `\langle token \rangle` into `\scan_stop:` if `\langle token \rangle` is expandable. An undefined token is not

considered as expandable. No problem nesting the conditionals, since the third #1 is only skipped if it is non-expandable (hence not part of TeX's conditional apparatus).

```

2832 \prg_new_conditional:Npnn \token_if_expandable:N #1 { p , T , F , TF }
2833 {
2834   \exp_after:wN \if_meaning:w \exp_not:N #1 #1
2835   \prg_return_false:
2836 \else:
2837   \if_cs_exist:N #1
2838   \prg_return_true:
2839 \else:
2840   \prg_return_false:
2841   \fi:
2842 \fi:
2843 }
```

(End definition for \token_if_expandable:N These functions are documented on page 55.)

Most of these functions have to check the meaning of the token in question so we need to do some checkups on which characters are output by \token_to_meaning:N. As usual, these characters have catcode 12 so we must do some serious substitutions in the code below...

```

2844 \group_begin:
2845   \char_set_lccode:nn { 'T } { 'T }
2846   \char_set_lccode:nn { 'F } { 'F }
2847   \char_set_lccode:nn { 'X } { 'n }
2848   \char_set_lccode:nn { 'Y } { 't }
2849   \char_set_lccode:nn { 'Z } { 'd }
2850   \tl_map_inline:nn { A C E G H I K L M O P R S U X Y Z R " }
2851   { \char_set_catcode:nn { '#1 } \c_twelve }
```

We convert the token list to lower case and restore the catcode and lowercase code changes.

```

2852 \tl_to_lowercase:n
2853 {
2854   \group_end:
```

First up is checking if something has been defined with \chardef or \mathchardef. This is easy since TeX thinks of such tokens as hexadecimal so it stores them as \char"*hex number*" or \mathchar"*hex number*". Grab until the first occurrence of \char", and compare what precedes with \ or \math. In fact, the escape character may not be a backslash, so we compare with the result of converting some other control sequence to a string, namely \char or \mathchar (the auxiliary adds the \char back).

```

2855   \prg_new_conditional:Npnn \token_if_chardef:N #1 { p , T , F , TF }
2856   {
2857     \__str_if_eq_x_return:nn
2858     {
2859       \exp_after:wN \__token_if_chardef:w
2860       \token_to_meaning:N #1 CHAR" \q_stop
2861     }
2862   { \token_to_str:N \char }
```

```

2863 }
2864 \prg_new_conditional:Npnn \token_if_mathchardef:N #1 { p , T , F , TF }
2865 {
2866   \__str_if_eq_x_return:nn
2867   {
2868     \exp_after:wN \__token_if_chardef:w
2869     \token_to_meaning:N #1 CHAR" \q_stop
2870   }
2871   { \token_to_str:N \mathchar }
2872 }
2873 \cs_new:Npn \__token_if_chardef:w #1 CHAR" \q_stop { #1 CHAR }

```

Dim registers are a little more difficult since their \meaning has the form \dimen⟨number⟩, and we must take care of the two primitives \dimen and \dimendef.

```

2874 \prg_new_conditional:Npnn \token_if_dim_register:N #1 { p , T , F , TF }
2875 {
2876   \if_meaning:w \tex_dimen:D #1
2877     \prg_return_false:
2878   \else:
2879     \if_meaning:w \tex_dimendef:D #1
2880       \prg_return_false:
2881     \else:
2882       \__str_if_eq_x_return:nn
2883       {
2884         \exp_after:wN \__token_if_dim_register:w
2885         \token_to_meaning:N #1 ZIMEX \q_stop
2886       }
2887       { \token_to_str:N \ }
2888     \fi:
2889   \fi:
2890 }
2891 \cs_new:Npn \__token_if_dim_register:w #1 ZIMEX #2 \q_stop { #1 ~ }

```

Integer registers are one step harder since constants are implemented differently from variables, and we also have to take care of the primitives \count and \countdef.

```

2892 \prg_new_conditional:Npnn \token_if_int_register:N #1 { p , T , F , TF }
2893 {
2894   % \token_if_chardef:NTF #1 { \prg_return_true: }
2895   % {
2896   %   \token_if_mathchardef:NTF #1 { \prg_return_true: }
2897   %   {
2898   \if_meaning:w \tex_count:D #1
2899     \prg_return_false:
2900   \else:
2901     \if_meaning:w \tex_countdef:D #1
2902       \prg_return_false:
2903     \else:
2904       \__str_if_eq_x_return:nn
2905       {
2906         \exp_after:wN \__token_if_int_register:w

```

```

2907           \token_to_meaning:N #1 COUXY \q_stop
2908       }
2909       { \token_to_str:N \
2910     \fi:
2911     \fi:
2912     %
2913     %
2914   }
2915 \cs_new:Npn \__token_if_int_register:w #1 COUXY #2 \q_stop { #1 ~ }

```

Muskip registers are done the same way as the dimension registers.

```

2916 \prg_new_conditional:Npnn \token_if_muskip_register:N #1 { p , T , F , TF }
2917 {
2918   \if_meaning:w \tex_muskip:D #1
2919     \prg_return_false:
2920   \else:
2921     \if_meaning:w \tex_muskipdef:D #1
2922       \prg_return_false:
2923     \else:
2924       \__str_if_eq_x_return:nn
2925       {
2926         \exp_after:wN \__token_if_muskip_register:w
2927           \token_to_meaning:N #1 MUSKIP \q_stop
2928         }
2929       { \token_to_str:N \
2930     \fi:
2931     \fi:
2932   }
2933 \cs_new:Npn \__token_if_muskip_register:w #1 MUSKIP #2 \q_stop { #1 ~ }

```

Skip registers.

```

2934 \prg_new_conditional:Npnn \token_if_skip_register:N #1 { p , T , F , TF }
2935 {
2936   \if_meaning:w \tex_skip:D #1
2937     \prg_return_false:
2938   \else:
2939     \if_meaning:w \tex_skipdef:D #1
2940       \prg_return_false:
2941     \else:
2942       \__str_if_eq_x_return:nn
2943       {
2944         \exp_after:wN \__token_if_skip_register:w
2945           \token_to_meaning:N #1 SKIP \q_stop
2946         }
2947       { \token_to_str:N \
2948     \fi:
2949     \fi:
2950   }
2951 \cs_new:Npn \__token_if_skip_register:w #1 SKIP #2 \q_stop { #1 ~ }

```

Toks registers.

```

2952 \prg_new_conditional:Npnn \token_if_toks_register:N #1 { p , T , F , TF }
2953 {
2954     \if_meaning:w \tex_toks:D #1
2955         \prg_return_false:
2956     \else:
2957         \if_meaning:w \tex_toksdef:D #1
2958             \prg_return_false:
2959         \else:
2960             \__str_if_eq_x_return:nn
2961             {
2962                 \exp_after:wN \__token_if_toks_register:w
2963                     \token_to_meaning:N #1 YOKS \q_stop
2964                 }
2965                 { \token_to_str:N \ }
2966             \fi:
2967         \fi:
2968     }
2969 \cs_new:Npn \__token_if_toks_register:w #1 YOKS #2 \q_stop { #1 ~ }
```

Protected macros.

```

2970 \prg_new_conditional:Npnn \token_if_protected_macro:N #1
2971     { p , T , F , TF }
2972 {
2973     \__str_if_eq_x_return:nn
2974     {
2975         \exp_after:wN \__token_if_protected_macro:w
2976             \token_to_meaning:N #1 PROYECYEZ-MACRO \q_stop
2977         }
2978         { \token_to_str:N \ }
2979     }
2980 \cs_new:Npn \__token_if_protected_macro:w
2981     #1 PROYECYEZ-MACRO #2 \q_stop { #1 ~ }
```

Long macros and protected long macros share an auxiliary.

```

2982 \prg_new_conditional:Npnn \token_if_long_macro:N #1 { p , T , F , TF }
2983 {
2984     \__str_if_eq_x_return:nn
2985     {
2986         \exp_after:wN \__token_if_long_macro:w
2987             \token_to_meaning:N #1 LOXG-MACRO \q_stop
2988         }
2989         { \token_to_str:N \ }
2990     }
2991 \prg_new_conditional:Npnn \token_if_protected_long_macro:N #1
2992     { p , T , F , TF }
2993 {
2994     \__str_if_eq_x_return:nn
2995     {
2996         \exp_after:wN \__token_if_long_macro:w
2997             \token_to_meaning:N #1 LOXG-MACRO \q_stop
2998     }
```

```

2999     { \token_to_str:N \protected \token_to_str:N \  }
3000   }
3001 \cs_new:Npn \__token_if_long_macro:w #1 LOXG~MACRO #2 \q_stop { #1 ~ }
Finally the \tl_to_lowercase:n ends!
3002 }
```

(End definition for `\token_if_chardef:N` and others. These functions are documented on page 55.)

```

\token_if_primitive_p:N
\token_if_primitive:NTF
\__token_if_primitive:NNw
  \__token_if_primitive_space:w
  \__token_if_primitive_nullfont:N
\__token_if_primitive_loop:N
  \__token_if_primitive:Nw
  \__token_if_primitive_undefined:N
```

We filter out macros first, because they cause endless trouble later otherwise.

Primitives are almost distinguished by the fact that the result of `\token_to_meaning:N` is formed from letters only. Every other token has either a space (e.g., the letter A), a digit (e.g., `\count123`) or a double quote (e.g., `\char"A"`).

Ten exceptions: on the one hand, `\c_undefined:D` is not a primitive, but its meaning is `undefined`, only letters; on the other hand, `\space`, `\italiccorr`, `\hyphen`, `\firstmark`, `\topmark`, `\botmark`, `\splitfirstmark`, `\splitbotmark`, and `\nullfont` are primitives, but have non-letters in their meaning.

We start by removing the two first (non-space) characters from the meaning. This removes the escape character (which may be nonexistent depending on `\endlinechar`), and takes care of three of the exceptions: `\space`, `\italiccorr` and `\hyphen`, whose meaning is at most two characters. This leaves a string terminated by some `:`, and `\q_stop`.

The meaning of each one of the five `\...mark` primitives has the form `<letters>:<user material>`. In other words, the first non-letter is a colon. We remove everything after the first colon.

We are now left with a string, which we must analyze. For primitives, it contains only letters. For non-primitives, it contains either `"`, or a space, or a digit. Two exceptions remain: `\c_undefined:D`, which is not a primitive, and `\nullfont`, which is a primitive.

Spaces cannot be grabbed in an undelimited way, so we check them separately. If there is a space, we test for `\nullfont`. Otherwise, we go through characters one by one, and stop at the first character less than ‘A’ (this is not quite a test for “only letters”, but is close enough to work in this context). If this first character is `:` then we have a primitive, or `\c_undefined:D`, and if it is `"` or a digit, then the token is not a primitive.

```

3003 \tex_chardef:D \c_token_A_int = 'A ~ %
3004 \group_begin:
3005 \char_set_catcode_other:N \;
3006 \char_set_lccode:nn { '\; } { '\: }
3007 \char_set_lccode:nn { '\T } { '\T }
3008 \char_set_lccode:nn { '\F } { '\F }
3009 \tl_to_lowercase:n {
3010   \group_end:
3011   \prg_new_conditional:Npnn \token_if_primitive:N #1 { p , T , F , TF }
3012   {
3013     \token_if_macro:NTF #1
3014     \prg_return_false:
3015     {
3016       \exp_after:wN \__token_if_primitive:NNw
3017       \token_to_meaning:N #1 ; ; \q_stop #1
3018     }
3019 }
```

```

3020 \cs_new:Npn \__token_if_primitive:NNw #1#2 #3 ; #4 \q_stop
3021 {
3022     \tl_if_empty:oTF { \__token_if_primitive_space:w #3 ~ }
3023     { \__token_if_primitive_loop:N #3 ; \q_stop }
3024     { \__token_if_primitive_nullfont:N }
3025 }
3026 }
3027 \cs_new:Npn \__token_if_primitive_space:w #1 ~ { }
3028 \cs_new:Npn \__token_if_primitive_nullfont:N #1
3029 {
3030     \if_meaning:w \tex_nullfont:D #1
3031         \prg_return_true:
3032     \else:
3033         \prg_return_false:
3034     \fi:
3035 }
3036 \cs_new:Npn \__token_if_primitive_loop:N #1
3037 {
3038     \if_int_compare:w '#1 < \c_token_A_int %
3039         \exp_after:wN \__token_if_primitive:Nw
3040         \exp_after:wN #1
3041     \else:
3042         \exp_after:wN \__token_if_primitive_loop:N
3043     \fi:
3044 }
3045 \cs_new:Npn \__token_if_primitive:Nw #1 #2 \q_stop
3046 {
3047     \if:w : #1
3048         \exp_after:wN \__token_if_primitive_undefined:N
3049     \else:
3050         \prg_return_false:
3051         \exp_after:wN \use_none:n
3052     \fi:
3053 }
3054 \cs_new:Npn \__token_if_primitive_undefined:N #1
3055 {
3056     \if_cs_exist:N #1
3057         \prg_return_true:
3058     \else:
3059         \prg_return_false:
3060     \fi:
3061 }

```

(End definition for `\token_if_primitive:N` These functions are documented on page 56.)

7.4 Peeking ahead at the next token

3062 `<@@=peek>`

Peeking ahead is implemented using a two part mechanism. The outer level provides a defined interface to the lower level material. This allows a large amount of code to be

shared. There are four cases:

1. peek at the next token;
2. peek at the next non-space token;
3. peek at the next token and remove it;
4. peek at the next non-space token and remove it.

\l_peek_token Storage tokens which are publicly documented: the token peeked.

\g_peek_token
3063 \cs_new_eq:NN \l_peek_token ?
3064 \cs_new_eq:NN \g_peek_token ?

(End definition for **\l_peek_token** This function is documented on page 57.)

\l_peek_search_token The token to search for as an implicit token: cf. **\l_peek_search_t1**.

3065 \cs_new_eq:NN \l_peek_search_token ?

(End definition for **\l_peek_search_token** This variable is documented on page ??.)

\l_peek_search_t1 The token to search for as an explicit token: cf. **\l_peek_search_token**.

3066 \tl_new:N \l_peek_search_t1

(End definition for **\l_peek_search_t1** This variable is documented on page ??.)

_peek_true:w Functions used by the branching and space-stripping code.

_peek_true_aux:w
_peek_false:w
_peek_tmp:w
3067 \cs_new_nopar:Npn _peek_true:w { }
3068 \cs_new_nopar:Npn _peek_true_aux:w { }
3069 \cs_new_nopar:Npn _peek_false:w { }
3070 \cs_new:Npn _peek_tmp:w { }

(End definition for **_peek_true:w** and others.)

\peek_after:Nw Simple wrappers for \futurelet: no arguments absorbed here.

\peek_gafter:Nw
3071 \cs_new_protected_nopar:Npn \peek_after:Nw
3072 { \tex_futurelet:D \l_peek_token }
3073 \cs_new_protected_nopar:Npn \peek_gafter:Nw
3074 { \tex_global:D \tex_futurelet:D \g_peek_token }
(End definition for **\peek_after:Nw** This function is documented on page 57.)

_peek_true_remove:w A function to remove the next token and then regain control.

3075 \cs_new_protected:Npn _peek_true_remove:w
3076 {
3077 \group_align_safe_end:
3078 \tex_afterassignment:D _peek_true_aux:w
3079 \cs_set_eq:NN _peek_tmp:w
3080 }

(End definition for **_peek_true_remove:w**)

__peek_token_generic:NNTF The generic function stores the test token in both implicit and explicit modes, and the `true` and `false` code as token lists, more or less. The two branches have to be absorbed here as the input stream needs to be cleared for the peek function itself.

```

3081 \cs_new_protected:Npn \_\_peek_token_generic:NNTF #1#2#3#4
3082 {
3083     \cs_set_eq:NN \l__peek_search_token #2
3084     \tl_set:Nn \l__peek_search_tl {#2}
3085     \cs_set_nopar:Npx \_\_peek_true:w
3086     {
3087         \exp_not:N \group_align_safe_end:
3088         \exp_not:n {#3}
3089     }
3090     \cs_set_nopar:Npx \_\_peek_false:w
3091     {
3092         \exp_not:N \group_align_safe_end:
3093         \exp_not:n {#4}
3094     }
3095     \group_align_safe_begin:
3096         \peek_after:Nw #1
3097     }
3098 \cs_new_protected:Npn \_\_peek_token_generic:NNT #1#2#3
3099     { \_\_peek_token_generic:NNTF #1 #2 {#3} { } }
3100 \cs_new_protected:Npn \_\_peek_token_generic:NNF #1#2#3
3101     { \_\_peek_token_generic:NNTF #1 #2 { } {#3} }
(End definition for \_\_peek_token_generic:NNTF This function is documented on page ??.)
```

__peek_token_remove_generic:NNTF For token removal there needs to be a call to the auxiliary function which does the work.

```

3102 \cs_new_protected:Npn \_\_peek_token_remove_generic:NNTF #1#2#3#4
3103 {
3104     \cs_set_eq:NN \l__peek_search_token #2
3105     \tl_set:Nn \l__peek_search_tl {#2}
3106     \cs_set_eq:NN \_\_peek_true:w \_\_peek_true_remove:w
3107     \cs_set_nopar:Npx \_\_peek_true_aux:w { \exp_not:n {#3} }
3108     \cs_set_nopar:Npx \_\_peek_false:w
3109     {
3110         \exp_not:N \group_align_safe_end:
3111         \exp_not:n {#4}
3112     }
3113     \group_align_safe_begin:
3114         \peek_after:Nw #1
3115     }
3116 \cs_new_protected:Npn \_\_peek_token_remove_generic:NNT #1#2#3
3117     { \_\_peek_token_remove_generic:NNTF #1 #2 {#3} { } }
3118 \cs_new_protected:Npn \_\_peek_token_remove_generic:NNF #1#2#3
3119     { \_\_peek_token_remove_generic:NNTF #1 #2 { } {#3} }
(End definition for \_\_peek_token_remove_generic:NNTF This function is documented on page ??.)
```

__peek_execute_branches_catcode: The category code and meaning tests are straight forward.

__peek_execute_branches_meaning:

```
3120 \cs_new_nopar:Npn \_\_peek_execute_branches_catcode:
```

```

3121 {
3122   \if_catcode:w
3123     \exp_not:N \l_peek_token \exp_not:N \l__peek_search_token
3124     \exp_after:wN \__peek_true:w
3125   \else:
3126     \exp_after:wN \__peek_false:w
3127   \fi:
3128 }
3129 \cs_new_nopar:Npn \__peek_execute_branches_meaning:
3130 {
3131   \if_meaning:w \l_peek_token \l__peek_search_token
3132     \exp_after:wN \__peek_true:w
3133   \else:
3134     \exp_after:wN \__peek_false:w
3135   \fi:
3136 }
(End definition for \__peek_execute_branches_catcode: and \__peek_execute_branches_meaning:
These functions are documented on page ??.)
```

__peek_execute_branches_catcode: First the character code test there is a need to worry about TeX grabbing brace group or skipping spaces. These are all tested for using a category code check before grabbing what must be a real single token and doing the comparison.

```

3137 \cs_new_nopar:Npn \__peek_execute_branches_catcode:
3138 {
3139   \bool_if:nTF
3140   {
3141     \token_if_eq_catcode_p:NN \l_peek_token \c_group_begin_token
3142     || \token_if_eq_catcode_p:NN \l_peek_token \c_group_end_token
3143     || \token_if_eq_meaning_p:NN \l_peek_token \c_space_token
3144   }
3145   { \__peek_false:w }
3146   {
3147     \exp_after:wN \__peek_execute_branches_catcode_aux:NN
3148     \l__peek_search_tl
3149   }
3150 }
3151 \cs_new:Npn \__peek_execute_branches_catcode_aux:NN #1#2
3152 {
3153   \if:w \exp_not:N #1 \exp_not:N #2
3154     \exp_after:wN \__peek_true:w
3155   \else:
3156     \exp_after:wN \__peek_false:w
3157   \fi:
3158   #2
3159 }
```

(End definition for __peek_execute_branches_catcode: This function is documented on page ??.)

__peek_ignore_spaces_execute_branches: This function removes one token at a time with a mechanism that can be applied to things other than spaces.

```

3160 \cs_new_protected_nopar:Npn \__peek_ignore_spaces_execute_branches:
3161 {
3162     \token_if_eq_meaning:NNTF \l_peek_token \c_space_token
3163     {
3164         \tex_afterassignment:D \__peek_ignore_spaces_execute_branches_aux:
3165         \cs_set_eq:NN \__peek_tmp:w
3166     }
3167     { \__peek_execute_branches: }
3168 }
3169 \cs_new_protected_nopar:Npn \__peek_ignore_spaces_execute_branches_aux:
3170 { \peek_after:Nw \__peek_ignore_spaces_execute_branches: }
(End definition for \__peek_ignore_spaces_execute_branches: This function is documented on page ??.)

```

The public functions themselves cannot be defined using `\prg_new_conditional:Npnn` and so a couple of auxiliary functions are used. As a result, everything is done inside a group. As a result things are a bit complicated.

```

3171 \group_begin:
3172     \cs_set:Npn \__peek_def:nnnn #1#2#3#4
3173     {
3174         \__peek_def:nnnnn {#1} {#2} {#3} {#4} { TF }
3175         \__peek_def:nnnnn {#1} {#2} {#3} {#4} { T }
3176         \__peek_def:nnnnn {#1} {#2} {#3} {#4} { F }
3177     }
3178 \cs_set:Npn \__peek_def:nnnnn #1#2#3#4#5
3179     {
3180         \cs_new_nopar:cpx { #1 #5 }
3181         {
3182             \tl_if_empty:nF {#2}
3183             { \exp_not:n { \cs_set_eq:NN \__peek_execute_branches: #2 } }
3184             \exp_not:c { #3 #5 }
3185             \exp_not:n {#4}
3186         }
3187     }
(End definition for \__peek_def:nnnn This function is documented on page ??.)

```

With everything in place the definitions can take place. First for category codes.

```

\peek_catcode:NTF With everything in place the definitions can take place. First for category codes.
\peek_catcode_ignore_spaces:NTF
\peek_catcode_remove:NTF
\peek_catcode_remove_ignore_spaces:NTF
3188 \__peek_def:nnnn { peek_catcode:N }
3189     {
3190     \__peek_token_generic:NN
3191     { \__peek_execute_branches_catcode: }
3192 \__peek_def:nnnn { peek_catcode_ignore_spaces:N }
3193     { \__peek_execute_branches_catcode: }
3194     \__peek_token_generic:NN
3195     { \__peek_ignore_spaces_execute_branches: }
3196 \__peek_def:nnnn { peek_catcode_remove:N }
3197     {
3198     \__peek_token_remove_generic:NN
3199     { \__peek_execute_branches_catcode: }

```

```

3200  \__peek_def:nnnn { peek_catcode_remove_ignore_spaces:N }
3201    { \__peek_execute_branches_catcode: }
3202    { __peek_token_remove_generic:NN }
3203    { \__peek_ignore_spaces_execute_branches: }
(End definition for \peek_catcode:NTF and others. These functions are documented on page 58.)
```

\peek_charcode:NTF Then for character codes.

```

3204  \__peek_def:nnnn { peek_charcode:N }
3205    { }
3206    { __peek_token_generic:NN }
3207    { \__peek_execute_branches_charcode: }
3208  \__peek_def:nnnn { peek_charcode_ignore_spaces:N }
3209    { \__peek_execute_branches_charcode: }
3210    { __peek_token_generic:NN }
3211    { \__peek_ignore_spaces_execute_branches: }
3212  \__peek_def:nnnn { peek_charcode_remove:N }
3213    { }
3214    { __peek_token_remove_generic:NN }
3215    { \__peek_execute_branches_charcode: }
3216  \__peek_def:nnnn { peek_charcode_remove_ignore_spaces:N }
3217    { \__peek_execute_branches_charcode: }
3218    { __peek_token_remove_generic:NN }
3219    { \__peek_ignore_spaces_execute_branches: }
(End definition for \peek_charcode:NTF and others. These functions are documented on page 58.)
```

\peek_meaning:NTF Finally for meaning, with the group closed to remove the temporary definition functions.

```

3220  \__peek_def:nnnn { peek_meaning:N }
3221    { }
3222    { __peek_token_generic:NN }
3223    { \__peek_execute_branches_meaning: }
3224  \__peek_def:nnnn { peek_meaning_ignore_spaces:N }
3225    { \__peek_execute_branches_meaning: }
3226    { __peek_token_generic:NN }
3227    { \__peek_ignore_spaces_execute_branches: }
3228  \__peek_def:nnnn { peek_meaning_remove:N }
3229    { }
3230    { __peek_token_remove_generic:NN }
3231    { \__peek_execute_branches_meaning: }
3232  \__peek_def:nnnn { peek_meaning_remove_ignore_spaces:N }
3233    { \__peek_execute_branches_meaning: }
3234    { __peek_token_remove_generic:NN }
3235    { \__peek_ignore_spaces_execute_branches: }
3236 \group_end:
```

(End definition for \peek_meaning:NTF and others. These functions are documented on page 59.)

7.5 Decomposing a macro definition

\token_get_prefix_spec:N We sometimes want to test if a control sequence can be expanded to reveal a hidden value.
 \token_get_arg_spec:N However, we cannot just expand the macro blindly as it may have arguments and none
 \token_get_replacement_spec:N
 _peek_get_prefix_arg_replacement:wN

might be present. Therefore we define these functions to pick either the prefix(es), the argument specification, or the replacement text from a macro. All of this information is returned as characters with catcode 12. If the token in question isn't a macro, the token `\scan_stop:` is returned instead.

```

3237 \exp_args:Nno \use:nn
3238 { \cs_new:Npn \__peek_get_prefix_arg_replacement:wN #1 }
3239 { \tl_to_str:n { macro : } #2 -> #3 \q_stop #4 }
3240 { #4 {#1} {#2} {#3} }
3241 \cs_new:Npn \token_get_prefix_spec:N #1
3242 {
3243     \token_if_macro:NTF #1
3244     {
3245         \exp_after:wN \__peek_get_prefix_arg_replacement:wN
3246             \token_to_meaning:N #1 \q_stop \use_i:nnn
3247     }
3248     { \scan_stop: }
3249 }
3250 \cs_new:Npn \token_get_arg_spec:N #1
3251 {
3252     \token_if_macro:NTF #1
3253     {
3254         \exp_after:wN \__peek_get_prefix_arg_replacement:wN
3255             \token_to_meaning:N #1 \q_stop \use_ii:nnn
3256     }
3257     { \scan_stop: }
3258 }
3259 \cs_new:Npn \token_get_replacement_spec:N #1
3260 {
3261     \token_if_macro:NTF #1
3262     {
3263         \exp_after:wN \__peek_get_prefix_arg_replacement:wN
3264             \token_to_meaning:N #1 \q_stop \use_iii:nnn
3265     }
3266     { \scan_stop: }
3267 }
```

(End definition for `\token_get_prefix_spec:N` This function is documented on page 60.)

7.6 Deprecated functions

Deprecated on 2011-05-27, for removal by 2011-08-31.

<code>\char_set_catcode:w</code>	Primitives renamed.
<code>\char_set_mathcode:w</code>	
<code>\char_set_lccode:w</code>	
<code>\char_set_uccode:w</code>	
<code>\char_set_sfcode:w</code>	
3268 <code>(*deprecated)</code>	
3269 <code>\cs_new_eq:NN \char_set_catcode:w \tex_catcode:D</code>	
3270 <code>\cs_new_eq:NN \char_set_mathcode:w \tex_mathcode:D</code>	
3271 <code>\cs_new_eq:NN \char_set_lccode:w \tex_lccode:D</code>	
3272 <code>\cs_new_eq:NN \char_set_uccode:w \tex_uccode:D</code>	
3273 <code>\cs_new_eq:NN \char_set_sfcode:w \tex_sfcode:D</code>	
3274 <code>(</deprecated>)</code>	

(End definition for \char_set_catcode:w This function is documented on page ??.)

\char_value_catcode:w More w functions we should not have.

```
3275  {*deprecated}
3276  \cs_new_nopar:Npn \char_value_catcode:w { \tex_the:D \char_set_catcode:w }
3277  \cs_new_nopar:Npn \char_show_value_catcode:w
3278  { \tex_showthe:D \char_set_catcode:w }
3279  \cs_new_nopar:Npn \char_value_mathcode:w { \tex_the:D \char_set_mathcode:w }
3280  \cs_new_nopar:Npn \char_show_value_mathcode:w
3281  { \tex_showthe:D \char_set_mathcode:w }
3282  \cs_new_nopar:Npn \char_value_lccode:w { \tex_the:D \char_set_lccode:w }
3283  \cs_new_nopar:Npn \char_show_value_lccode:w
3284  { \tex_showthe:D \char_set_lccode:w }
3285  \cs_new_nopar:Npn \char_value_uccode:w { \tex_the:D \char_set_uccode:w }
3286  \cs_new_nopar:Npn \char_show_value_uccode:w
3287  { \tex_showthe:D \char_set_uccode:w }
3288  \cs_new_nopar:Npn \char_value_sfcode:w { \tex_the:D \char_set_sfcode:w }
3289  \cs_new_nopar:Npn \char_show_value_sfcode:w
3290  { \tex_showthe:D \char_set_sfcode:w }
3291  {/deprecated}
```

(End definition for \char_value_catcode:w This function is documented on page ??.)

\peek_after:NN The second argument here must be w.

```
3292  {*deprecated}
3293  \cs_new_eq:NN \peek_after:NN \peek_after:Nw
3294  \cs_new_eq:NN \peek_gafter:NN \peek_gafter:Nw
3295  {/deprecated}
```

(End definition for \peek_after:NN This function is documented on page ??.)

Functions deprecated 2011-05-28 for removal by 2011-08-31.

\c_alignment_tab_token

```
3296  {*deprecated}
3297  \cs_new_eq:NN \c_alignment_tab_token \c_alignment_token
3298  \cs_new_eq:NN \c_math_shift_token \c_math_toggle_token
3299  \cs_new_eq:NN \c_letter_token \c_catcode_letter_token
3300  \cs_new_eq:NN \c_other_char_token \c_catcode_other_token
3301  {/deprecated}
```

(End definition for \c_alignment_tab_token This function is documented on page ??.)

\c_active_char_token An odd one: this was never a token!

```
3302  {*deprecated}
3303  \cs_new_eq:NN \c_active_char_token \c_catcode_active_t1
3304  {/deprecated}
```

(End definition for \c_active_char_token This function is documented on page ??.)

\char_make_escape:N Two renames in one block!

```
3305  {*deprecated}
3306  \cs_new_eq:NN \char_make_escape:N
3307  \cs_new_eq:NN \char_make_begin_group:N
3308  \cs_new_eq:NN \char_make_end_group:N
3309  \cs_new_eq:NN \char_make_math_shift:N
3310  \cs_new_eq:NN \char_make_alignment_tab:N
3311  \cs_new_eq:NN \char_make_end_line:N
3312  \cs_new_eq:NN \char_make_parameter:N
3313  \cs_new_eq:NN \char_make_math_superscript:N
3314      \char_set_catcode_math_superscript:N
3315  \cs_new_eq:NN \char_make_math_subscript:N
3316      \char_set_catcode_math_subscript:N
3317  \cs_new_eq:NN \char_make_ignore:N
3318  \cs_new_eq:NN \char_make_space:N
3319  \cs_new_eq:NN \char_make_letter:N
3320  \cs_new_eq:NN \char_make_other:N
3321  \cs_new_eq:NN \char_make_active:N
3322  \cs_new_eq:NN \char_make_comment:N
3323  \cs_new_eq:NN \char_make_invalid:N
3324  \cs_new_eq:NN \char_make_escape:n
3325  \cs_new_eq:NN \char_make_begin_group:n
3326  \cs_new_eq:NN \char_make_end_group:n
3327  \cs_new_eq:NN \char_make_math_shift:n
3328  \cs_new_eq:NN \char_make_alignment_tab:n
3329  \cs_new_eq:NN \char_make_end_line:n
3330  \cs_new_eq:NN \char_make_parameter:n
3331  \cs_new_eq:NN \char_make_math_superscript:n
3332      \char_set_catcode_math_superscript:n
3333  \cs_new_eq:NN \char_make_math_subscript:n
3334      \char_set_catcode_math_subscript:n
3335  \cs_new_eq:NN \char_make_ignore:n
3336  \cs_new_eq:NN \char_make_space:n
3337  \cs_new_eq:NN \char_make_letter:n
3338  \cs_new_eq:NN \char_make_other:n
3339  \cs_new_eq:NN \char_make_active:n
3340  \cs_new_eq:NN \char_make_comment:n
3341  \cs_new_eq:NN \char_make_invalid:n
3342  //deprecated
```

\char_set_catcode_escape:N
\char_set_catcode_group_begin:N
\char_set_catcode_group_end:N
\char_set_catcode_math_toggle:N
\char_set_catcode_alignment:N
\char_set_catcode_end_line:N
\char_set_catcode_parameter:N

\char_set_catcode_ignore:N
\char_set_catcode_space:N
\char_set_catcode_letter:N
\char_set_catcode_other:N
\char_set_catcode_active:N
\char_set_catcode_comment:N
\char_set_catcode_invalid:N
\char_set_catcode_escape:n
\char_set_catcode_group_begin:n
\char_set_catcode_group_end:n
\char_set_catcode_math_toggle:n
\char_set_catcode_alignment:n
\char_set_catcode_end_line:n
\char_set_catcode_parameter:n

\char_set_catcode_ignore:n
\char_set_catcode_space:n
\char_set_catcode_letter:n
\char_set_catcode_other:n
\char_set_catcode_active:n
\char_set_catcode_comment:n
\char_set_catcode_invalid:n

(End definition for \char_make_escape:N and others. These functions are documented on page ??.)

```
\token_if_alignment_tab_p:N
\token_if_alignment_tab:NTF
\token_if_math_shift_p:N
\token_if_math_shift:NTF
\token_if_other_char_p:N
\token_if_other_char:NTF
\token_if_active_char_p:N
\token_if_active_char:NTF
3343  {*deprecated}
3344  \cs_new_eq:NN \token_if_alignment_tab_p:N \token_if_alignment_p:N
3345  \cs_new_eq:NN \token_if_alignment_tab:NT \token_if_alignment:NT
3346  \cs_new_eq:NN \token_if_alignment_tab:NF \token_if_alignment:NF
3347  \cs_new_eq:NN \token_if_alignment_tab:NTF \token_if_alignment:NTF
3348  \cs_new_eq:NN \token_if_math_shift_p:N \token_if_math_toggle_p:N
3349  \cs_new_eq:NN \token_if_math_shift:NT \token_if_math_toggle:NT
```

```

3350 \cs_new_eq:NN \token_if_math_shift:NF \token_if_math_toggle:NF
3351 \cs_new_eq:NN \token_if_math_shift:NTF \token_if_math_toggle:NTF
3352 \cs_new_eq:NN \token_if_other_char_p:N \token_if_other_p:N
3353 \cs_new_eq:NN \token_if_other_char_p:NT \token_if_other_p:NT
3354 \cs_new_eq:NN \token_if_other_char:NF \token_if_other_p:NF
3355 \cs_new_eq:NN \token_if_other_char:NTF \token_if_other_p:NTF
3356 \cs_new_eq:NN \token_if_active_char_p:N \token_if_active_p:N
3357 \cs_new_eq:NN \token_if_active_char:NT \token_if_active_p:NT
3358 \cs_new_eq:NN \token_if_active_char:NF \token_if_active_p:NF
3359 \cs_new_eq:NN \token_if_active_char:NTF \token_if_active_p:NTF
3360 ⟨/deprecated⟩
(End definition for \token_if_alignment_tab:N These functions are documented on page ??.)
3361 ⟨/initex | package⟩

```

8 l3int implementation

```

3362 ⟨*initex | package⟩
3363 ⟨@@=int⟩
The following test files are used for this code: m3int001,m3int002,m3int03.
3364 ⟨*package⟩
3365 \ProvidesExplPackage
3366 {\ExplFileName}{\ExplFileVersion}{\ExplFileDescription}
3367 \_expl_package_check:
3368 ⟨/package⟩

```

`_int_to_roman:w` Done in l3basics.

(End definition for `_int_to_roman:w` This function is documented on page 72.)

```

\_\_int\_value:w Here are the remaining primitives for number comparisons and expressions.
\_\_int\_eval:w   3369 \cs_new_eq:NN \_\_int_value:w      \tex_number:D
\_\_int\_eval_end: 3370 \cs_new_eq:NN \_\_int_eval:w     \etex_numexpr:D
\if_int_odd:w    3371 \cs_new_eq:NN \_\_int_eval_end: \tex_relax:D
\if_case:w        3372 \cs_new_eq:NN \if_int_odd:w   \tex_ifodd:D
                  3373 \cs_new_eq:NN \if_case:w     \tex_ifcase:D
(End definition for \_\_int_value:w This function is documented on page 72.)

```

8.1 Integer expressions

`\int_eval:n` Wrapper for `__int_eval:w`. Can be used in an integer expression or directly in the input stream. In format mode, there is already a definition in l3alloc for bookstrapping, which is therefore corrected to the “real” version here.

```

3374 ⟨*initex⟩
3375 \cs_set:Npn \int_eval:n #1 { \_\_int_value:w \_\_int_eval:w #1 \_\_int_eval_end: }
3376 ⟨/initex⟩
3377 ⟨*package⟩
3378 \cs_new:Npn \int_eval:n #1 { \_\_int_value:w \_\_int_eval:w #1 \_\_int_eval_end: }
3379 ⟨/package⟩

```

(End definition for `\int_eval:n` This function is documented on page 61.)

```

\int_abs:n
\__int_abs:N
\int_max:nn
\int_min:nn
\__int_maxmin:wwN
3380 \cs_new:Npn \int_abs:n #1
3381 {
3382     \__int_value:w \exp_after:wN \__int_abs:N
3383         \int_use:N \__int_eval:w #1 \__int_eval_end:
3384         \exp_stop_f:
3385     }
3386 \cs_new:Npn \__int_abs:N #1
3387 { \if_meaning:w - #1 \else: \exp_after:wN #1 \fi: }
3388 \cs_set:Npn \int_max:nn #1#2
3389 {
3390     \__int_value:w \exp_after:wN \__int_maxmin:wwN
3391         \int_use:N \__int_eval:w #1 \exp_after:wN ;
3392         \int_use:N \__int_eval:w #2 ;
3393     >
3394     \exp_stop_f:
3395 }
3396 \cs_set:Npn \int_min:nn #1#2
3397 {
3398     \__int_value:w \exp_after:wN \__int_maxmin:wwN
3399         \int_use:N \__int_eval:w #1 \exp_after:wN ;
3400         \int_use:N \__int_eval:w #2 ;
3401     <
3402     \exp_stop_f:
3403 }
3404 \cs_new:Npn \__int_maxmin:wwN #1 ; #2 ; #3
3405 {
3406     \if_int_compare:w #1 #3 #2 ~
3407         #1
3408     \else:
3409         #2
3410     \fi:
3411 }

```

(End definition for `\int_abs:n` This function is documented on page 62.)

```

\int_div_truncate:nn
\int_div_round:nn
\int_mod:nn
\__int_div_truncate:NwNw
\__int_mod:ww
As \__int_eval:w rounds the result of a division we also provide a version that truncates the result. We use an auxiliary to make sure numerator and denominator are only evaluated once: this comes in handy when those are more expensive to evaluate (e.g., \tl_count:n). If the numerator #1#2 is 0, then we divide 0 by the denominator (this ensures that 0/0 is correctly reported as an error). Otherwise, shift the numerator #1#2 towards 0 by  $(|#3#4| - 1)/2$ , which we round away from zero. It turns out that this quantity exactly compensates the difference between  $\varepsilon$ -TEX's rounding and the truncating behaviour that we want. The details are thanks to Heiko Oberdiek: getting things right in all cases is not so easy.
```

```

3412 \cs_new:Npn \int_div_truncate:nn #1#2
3413 {

```

```

3414   \int_use:N \__int_eval:w
3415     \exp_after:wN \__int_div_truncate:NwNw
3416     \int_use:N \__int_eval:w #1 \exp_after:wN ;
3417     \int_use:N \__int_eval:w #2 ;
3418   \__int_eval_end:
3419 }
3420 \cs_new:Npn \__int_div_truncate:NwNw #1#2; #3#4;
3421 {
3422   \if_meaning:w 0 #1
3423     \c_zero
3424   \else:
3425   (
3426     #1#2
3427     \if_meaning:w - #1 + \else: - \fi:
3428     ( \if_meaning:w - #3 - \fi: #3#4 - \c_one ) / \c_two
3429   )
3430   \fi:
3431   / #3#4
3432 }

```

For the sake of completeness:

```

3433 \cs_new:Npn \int_div_round:nn #1#2
3434   { \__int_value:w \__int_eval:w ( #1 ) / ( #2 ) \__int_eval_end: }

```

Finally there's the modulus operation.

```

3435 \cs_new:Npn \int_mod:nn #1#2
3436 {
3437   \__int_value:w \__int_eval:w \exp_after:wN \__int_mod:ww
3438   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
3439   \__int_value:w \__int_eval:w #2 ;
3440 \__int_eval_end:
3441 }
3442 \cs_new:Npn \__int_mod:ww #1; #2;
3443   { #1 - ( \__int_div_truncate:NwNw #1 ; #2 ; ) * #2 }

```

(End definition for `\int_div_truncate:nn` This function is documented on page 62.)

8.2 Creating and initialising integers

`\int_new:N` Two ways to do this: one for the format and one for the L^AT_EX 2 _{ε} package.

```

\int_new:c 3444 {*package}
3445 \cs_new_protected:Npn \int_new:N #1
3446 {
3447   \__chk_if_free_cs:N #1
3448   \newcount #1
3449 }
3450 
```

(End definition for `\int_new:N` and `\int_new:c` These functions are documented on page ??.)

```

\int_const:Nn
\int_const:cN
\__int_constdef:Nw
\c_max_constdef_int
3452 \cs_new_protected:Npn \int_const:Nn #1#2
3453 {
3454     \int_compare:nNnTF {#2} > \c_minus_one
3455     {
3456         \int_compare:nNnTF {#2} > \c_max_constdef_int
3457         {
3458             \int_new:N #1
3459             \int_gset:Nn #1 {#2}
3460         }
3461         {
3462             \__chk_if_free_cs:N #1
3463             \tex_global:D \__int_constdef:Nw #1 =
3464                 \__int_eval:w #2 \__int_eval_end:
3465         }
3466     }
3467     {
3468         \int_new:N #1
3469         \int_gset:Nn #1 {#2}
3470     }
3471 }
3472 \cs_generate_variant:Nn \int_const:Nn { c }
3473 \pdftex_if_engine:TF
3474 {
3475     \cs_new_eq:NN \__int_constdef:Nw \tex_mathchardef:D
3476     \tex_mathchardef:D \c_max_constdef_int 32 767 ~
3477 }
3478 {
3479     \cs_new_eq:NN \__int_constdef:Nw \tex_chardef:D
3480     \tex_chardef:D \c_max_constdef_int 1 114 111 ~
3481 }

```

(End definition for `\int_const:Nn` and `\int_const:cN`. These functions are documented on page ??.)

`\int_zero:N` Functions that reset an `<integer>` register to zero.

```

\int_zero:c
\int_gzero:N
\int_gzero:c
3482 \cs_new_protected:Npn \int_zero:N #1 { #1 = \c_zero }
3483 \cs_new_protected:Npn \int_gzero:N #1 { \tex_global:D #1 = \c_zero }
3484 \cs_generate_variant:Nn \int_zero:N { c }
3485 \cs_generate_variant:Nn \int_gzero:N { c }

```

(End definition for `\int_zero:N` and `\int_zero:c`. These functions are documented on page ??.)

`\int_zero_new:N` Create a register if needed, otherwise clear it.

```

\int_zero_new:c
\int_gzero_new:N
\int_gzero_new:c
3486 \cs_new_protected:Npn \int_zero_new:N #1
3487     { \int_if_exist:NTF #1 { \int_zero:N #1 } { \int_new:N #1 } }
3488 \cs_new_protected:Npn \int_gzero_new:N #1
3489     { \int_if_exist:NTF #1 { \int_gzero:N #1 } { \int_new:N #1 } }
3490 \cs_generate_variant:Nn \int_zero_new:N { c }
3491 \cs_generate_variant:Nn \int_gzero_new:N { c }

```

(End definition for `\int_zero_new:N` and others. These functions are documented on page ??.)

```

\int_set_eq:NN
\int_set_eq:cN
\int_set_eq:Nc
\int_set_eq:cc
\int_gset_eq:NN
\int_gset_eq:cN
\int_gset_eq:Nc
\int_gset_eq:cc

```

Setting equal means using one integer inside the set function of another.

```

3492 \cs_new_protected:Npn \int_set_eq:NN #1#2 { #1 = #2 }
3493 \cs_generate_variant:Nn \int_set_eq:NN { c }
3494 \cs_generate_variant:Nn \int_set_eq:NN { Nc , cc }
3495 \cs_new_protected:Npn \int_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
3496 \cs_generate_variant:Nn \int_gset_eq:NN { c }
3497 \cs_generate_variant:Nn \int_gset_eq:NN { Nc , cc }

```

(End definition for `\int_set_eq:NN` and others. These functions are documented on page ??.)

```

\int_if_exist_p:N
\int_if_exist_p:c
\int_if_exist:NTF
\int_if_exist:cTF

```

Copies of the cs functions defined in l3basics.

```

3498 \cs_new_eq:NN \int_if_exist:NTF \cs_if_exist:NTF
3499 \cs_new_eq:NN \int_if_exist:NT \cs_if_exist:NT
3500 \cs_new_eq:NN \int_if_exist:NF \cs_if_exist:NF
3501 \cs_new_eq:NN \int_if_exist_p:N \cs_if_exist_p:N
3502 \cs_new_eq:NN \int_if_exist:cTF \cs_if_exist:cTF
3503 \cs_new_eq:NN \int_if_exist:cT \cs_if_exist:cT
3504 \cs_new_eq:NN \int_if_exist:cF \cs_if_exist:cF
3505 \cs_new_eq:NN \int_if_exist_p:c \cs_if_exist_p:c

```

(End definition for `\int_if_exist:N` and `\int_if_exist:c`. These functions are documented on page ??.)

8.3 Setting and incrementing integers

```

\int_add:Nn
\int_add:cn
\int_gadd:Nn
\int_gadd:cn
\int_sub:Nn
\int_sub:cn
\int_gsub:Nn
\int_gsub:cn

```

Adding and subtracting to and from a counter ...

```

3506 \cs_new_protected:Npn \int_add:Nn #1#2
3507 { \tex_advance:D #1 by \__int_eval:w #2 \__int_eval_end: }
3508 \cs_new_protected:Npn \int_sub:cn #1#2
3509 { \tex_advance:D #1 by - \__int_eval:w #2 \__int_eval_end: }
3510 \cs_new_protected_nopar:Npn \int_gadd:Nn
3511 { \tex_global:D \int_add:Nn }
3512 \cs_new_protected_nopar:Npn \int_gsub:Nn
3513 { \tex_global:D \int_sub:cn }
3514 \cs_generate_variant:Nn \int_add:Nn { c }
3515 \cs_generate_variant:Nn \int_gadd:Nn { c }
3516 \cs_generate_variant:Nn \int_sub:cn { c }
3517 \cs_generate_variant:Nn \int_gsub:Nn { c }

```

(End definition for `\int_add:Nn` and `\int_add:cn`. These functions are documented on page ??.)

```

\int_incr:N
\int_incr:c
\int_gincr:N
\int_gincr:c
\int_decr:N
\int_decr:c
\int_gdecr:N
\int_gdecr:c

```

Incrementing and decrementing of integer registers is done with the following functions.

```

3518 \cs_new_protected:Npn \int_incr:N #1
3519 { \tex_advance:D #1 \c_one }
3520 \cs_new_protected:Npn \int_decr:N #1
3521 { \tex_advance:D #1 \c_minus_one }
3522 \cs_new_protected_nopar:Npn \int_gincr:N
3523 { \tex_global:D \int_incr:N }
3524 \cs_new_protected_nopar:Npn \int_gdecr:N
3525 { \tex_global:D \int_decr:N }
3526 \cs_generate_variant:Nn \int_incr:N { c }

```

```

3527 \cs_generate_variant:Nn \int_decr:N { c }
3528 \cs_generate_variant:Nn \int_gincr:N { c }
3529 \cs_generate_variant:Nn \int_gdecr:N { c }
(End definition for \int_incr:N and \int_incr:c These functions are documented on page ??.)
```

\int_set:Nn As integers are register-based TeX will issue an error if they are not defined. Thus there is no need for the checking code seen with token list variables.

```

\int_gset:Nn
\int_gset:cn
3530 \cs_new_protected:Npn \int_set:Nn #1#2
3531 { #1 ~ \__int_eval:w #2\__int_eval_end: }
3532 \cs_new_protected_nopar:Npn \int_gset:Nn { \tex_global:D \int_set:Nn }
3533 \cs_generate_variant:Nn \int_set:Nn { c }
3534 \cs_generate_variant:Nn \int_gset:Nn { c }
(End definition for \int_set:Nn and \int_set:cn These functions are documented on page ??.)
```

8.4 Using integers

\int_use:N Here is how counters are accessed:

```

\int_use:c
3535 \cs_new_eq:NN \int_use:N \tex_the:D
3536 \cs_new:Npn \int_use:c #1 { \int_use:N \cs:w #1 \cs_end: }
(End definition for \int_use:N and \int_use:c These functions are documented on page ??.)
```

8.5 Integer expression conditionals

Those functions are used for comparison tests which use a simple syntax where only one set of braces is required and additional operators such as `!=` and `>=` are supported. The tests first evaluate their left-hand side, with a trailing `__prg_compare_error:`. This marker is normally not expanded, but if the relation symbol is missing from the test's argument, then the marker inserts `=` (and itself) after triggering the relevant TeX error. If the first token which appears after evaluating and removing the left-hand side is not a known relation symbol, then a judiciously placed `__prg_compare_error:Nw` gets expanded, cleaning up the end of the test and telling the user what the problem was.

```

3537 \cs_new_protected_nopar:Npn \__prg_compare_error:
3538 {
3539     \if_int_compare:w \c_zero \c_zero \fi:
3540     =
3541     \__prg_compare_error:
3542 }
3543 \cs_new:Npn \__prg_compare_error:Nw
3544     #1#2 \prg_return_true: \else: \prg_return_false: \fi:
3545 {
3546     \__msg_kernel_expandable_error:nnn
3547         { kernel } { unknown-comparison } {#1}
3548     \prg_return_false:
3549 }
```

(End definition for __prg_compare_error: and __prg_compare_error:Nw)

```

\int_compare_p:n
\int_compare:nTF
\_\_int_compare_aux:Nw
\_\_int_compare_aux>NNw
\_\_int_compare_=:NNw
\_\_int_compare_<:NNw
\_\_int_compare_>:NNw
\_\_int_compare_==:NNw
\_\_int_compare_!=:NNw
\_\_int_compare_<=:NNw
\_\_int_compare_>=:NNw

```

Comparison tests using a simple syntax where only one set of braces is required and additional operators such as `!=` and `>=` are supported. We can start evaluating from the left using `__int_eval:w`, and we know that since the relation symbols `<`, `>`, `=` and `!` are not allowed in such expressions, they will terminate the expression. Therefore, we first let TeX evaluate this left hand side of the (in)equality. We also insert at that stage the end of the test: `__int_eval_end:` will end the evaluation of the right-hand side.

```

3550 \prg_new_conditional:Npnn \int_compare:n #1 { p , T , F , TF }
3551 {
3552   \exp_after:WN \_\_int_compare_aux:Nw \int_use:N \_\_int_eval:w #1
3553     \_\_prg_compare_error: \_\_int_eval_end:
3554   \prg_return_true:
3555 \else:
3556   \prg_return_false:
3557 \fi:
3558 }

```

We have just evaluated the left-hand side. To access the relation symbol, we remove the number by applying `__int_to_roman:w`, after making sure that the argument becomes non-positive: its roman numeral representation is then empty. The `__int_compare_aux:NNw` auxiliary then probes the first two tokens to determine the relation symbol, building a control sequence from it. All the extended forms have an extra `=` hence the test for that as a second token. If the relation symbol is unknown, then the control sequence is turned by TeX into `\scan_stop:`, and `__prg_compare_error:Nw` raises an error.

```

3559 \cs_new:Npn \_\_int_compare_aux:Nw #1#2 \_\_prg_compare_error:
3560 {
3561   \exp_after:WN \_\_int_compare_aux>NNw
3562     \_\_int_to_roman:w - 0 #2 ?? \q_mark
3563   #1#2
3564 }
3565 \cs_new:Npn \_\_int_compare_aux>NNw #1#2#3 \q_mark
3566 {
3567   \use:c { \_\_int_compare_ #1 \if_meaning:w = #2 = \fi: :NNw }
3568   \_\_prg_compare_error:Nw #1
3569 }

```

The actual comparisons are then simple function calls, using the relation as delimiter for a delimited argument and discarding `__prg_compare_error:Nw` (*token*) responsible for error detection.

```

3570 \cs_new:cpn { \_\_int_compare_=:NNw } #1#2#3 =
3571   { \if_int_compare:w #3 = \_\_int_eval:w }
3572 \cs_new:cpn { \_\_int_compare_<:NNw } #1#2#3 <
3573   { \if_int_compare:w #3 < \_\_int_eval:w }
3574 \cs_new:cpn { \_\_int_compare_>:NNw } #1#2#3 >
3575   { \if_int_compare:w #3 > \_\_int_eval:w }
3576 \cs_new:cpn { \_\_int_compare_==:NNw } #1#2#3 ==
3577   { \if_int_compare:w #3 = \_\_int_eval:w }
3578 \cs_new:cpn { \_\_int_compare_!=:NNw } #1#2#3 !=
3579   { \reverse_if:N \if_int_compare:w #3 = \_\_int_eval:w }

```

```

3580 \cs_new:cpn { __int_compare_<=:NNw } #1#2#3 <=
3581   { \reverse_if:N \if_int_compare:w #3 > \__int_eval:w }
3582 \cs_new:cpn { __int_compare_>=:NNw } #1#2#3 >=
3583   { \reverse_if:N \if_int_compare:w #3 < \__int_eval:w }
(End definition for \int_compare:n These functions are documented on page 64.)
```

\int_compare_p:nNn
More efficient but less natural in typing.

```

3584 \prg_new_conditional:Npnn \int_compare:nNn #1#2#3 { p , T , F , TF }
3585   {
3586     \if_int_compare:w \__int_eval:w #1 #2 \__int_eval:w #3 \__int_eval_end:
3587       \prg_return_true:
3588     \else:
3589       \prg_return_false:
3590     \fi:
3591   }
(End definition for \int_compare:nNn These functions are documented on page 64.)
```

\int_case:nnn
__int_case:nnn
__int_case:nw
__int_case_end:nw

For integer cases, the first task to fully expand the check condition. After that, a loop is started to compare each possible value and stop if the test is true. The tested value is put at the end to ensure that there is necessarily a match, which will fire the “else” pathway. The leading \romannumeral triggers an expansion which is then stopped in __int_case_end:nw.

```

3592 \cs_new:Npn \int_case:nnn #1
3593   {
3594     \tex_romannumeral:D
3595     \exp_args:Nf \__int_case:nnn { \int_eval:n {#1} }
3596   }
3597 \cs_new:Npn \__int_case:nnn #1#2#3
3598   { \__int_case:nw {#1} #2 {#1} {#3} \q_recursion_stop }
3599 \cs_new:Npn \__int_case:nw #1#2#3
3600   {
3601     \int_compare:nNnTF {#1} = {#2}
3602       { \__int_case_end:nw {#3} }
3603       { \__int_case:nw {#1} }
3604   }
3605 \cs_new_eq:NN \__int_case_end:nw \__prg_case_end:nw
(End definition for \int_case:nnn This function is documented on page 65.)
```

\int_if_odd_p:n
\int_if_odd:nTF
\int_if_even_p:n
\int_if_even:nTF

A predicate function.

```

3606 \prg_new_conditional:Npnn \int_if_odd:n #1 { p , T , F , TF }
3607   {
3608     \if_int_odd:w \__int_eval:w #1 \__int_eval_end:
3609       \prg_return_true:
3610     \else:
3611       \prg_return_false:
3612     \fi:
3613   }
3614 \prg_new_conditional:Npnn \int_if_even:n #1 { p , T , F , TF }
3615   {
```

```

3616 \if_int_odd:w \_int_eval:w #1 \_int_eval_end:
3617   \prg_return_false:
3618 \else:
3619   \prg_return_true:
3620 \fi:
3621 }

```

(End definition for `\int_if_odd:n` These functions are documented on page 65.)

8.6 Integer expression loops

`\int_while_do:nn`

`\int_until_do:nn`

`\int_do_while:nn`

`\int_do_until:nn`

These are quite easy given the above functions. The `while` versions test first and then execute the body. The `do_while` does it the other way round.

```

3622 \cs_new:Npn \int_while_do:nn #1#2
3623 {
3624   \int_compare:nT {#1}
3625   {
3626     #2
3627     \int_while_do:nn {#1} {#2}
3628   }
3629 }
3630 \cs_new:Npn \int_until_do:nn #1#2
3631 {
3632   \int_compare:nF {#1}
3633   {
3634     #2
3635     \int_until_do:nn {#1} {#2}
3636   }
3637 }
3638 \cs_new:Npn \int_do_while:nn #1#2
3639 {
3640   #2
3641   \int_compare:nT {#1}
3642   {
3643     \int_do_while:nn {#1} {#2}
3644   }
3645 \cs_new:Npn \int_do_until:nn #1#2
3646 {
3647   #2
3648   \int_compare:nF {#1}
3649   {
3650     \int_do_until:nn {#1} {#2}
3651   }
3652   #2
3653   \int_compare:nNnT {#1} #2 {#3}
3654   {
3655     #4
3656     \int_while_do:nNnn {#1} #2 {#3} {#4}
3657   }
3658 }
3659 }

```

(End definition for `\int_while_do:nn` This function is documented on page 66.)

`\int_while_do:nNnn`

`\int_until_do:nNnn`

`\int_do_while:nNnn`

`\int_do_until:nNnn`

As above but not using the more natural syntax.

```

3650 \cs_new:Npn \int_while_do:nNnn #1#2#3#4
3651 {
3652   \int_compare:nNnT {#1} #2 {#3}
3653   {
3654     #4
3655     \int_while_do:nNnn {#1} #2 {#3} {#4}
3656   }
3657 }

```

```

3656     }
3657   }
3658 \cs_new:Npn \int_until_do:nNnn #1#2#3#4
3659 {
3660   \int_compare:nNnF {#1} #2 {#3}
3661   {
3662     #4
3663     \int_until_do:nNnn {#1} #2 {#3} {#4}
3664   }
3665 }
3666 \cs_new:Npn \int_do_while:nNnn #1#2#3#4
3667 {
3668   #4
3669   \int_compare:nNnT {#1} #2 {#3}
3670   { \int_do_while:nNnn {#1} #2 {#3} {#4} }
3671 }
3672 \cs_new:Npn \int_do_until:nNnn #1#2#3#4
3673 {
3674   #4
3675   \int_compare:nNnF {#1} #2 {#3}
3676   { \int_do_until:nNnn {#1} #2 {#3} {#4} }
3677 }

```

(End definition for `\int_while_do:nNnn`. This function is documented on page 65.)

8.7 Integer step functions

`\int_step_function:nnnN`
`_int_step:NnnnN`

Repeating a function by steps first needs a check on the direction of the steps. After that, do the function for the start value then step and loop around. It would be more symmetrical to test for a step size of zero before checking the sign, but we optimize for the most frequent case (positive step).

```

3678 \cs_new:Npn \int_step_function:nnnN #1#2#3#4
3679 {
3680   \int_compare:nNnTF {#2} > \c_zero
3681   { \exp_args:NNf \_int_step:NnnnN > }
3682   {
3683     \int_compare:nNnTF {#2} = \c_zero
3684     {
3685       \_msg_kernel_expandable_error:nnn { kernel } { zero-step } {#4}
3686       \use_none:nnnn
3687     }
3688     { \exp_args:NNf \_int_step:NnnnN < }
3689   }
3690   { \int_eval:n {#1} } {#2} {#3} #4
3691 }
3692 \cs_new:Npn \_int_step:NnnnN #1#2#3#4#5
3693 {
3694   \int_compare:nNnF {#2} #1 {#4}
3695   {
3696     #5 {#2}

```

```

3697           \exp_args:NNf \__int_step:NnnnN
3698             #1 { \int_eval:n { #2 + #3 } } {#3} {#4} #5
3699         }
3700     }
(End definition for \int_step_function:nnnN This function is documented on page 67.)
```

`\int_step_inline:nnnn`
`\int_step_variable:nnnNn`
`__int_step>NNnnnn`

The approach here is to build a function, with a global integer required to make the nesting safe (as seen in other in line functions), and map that function using `\int_step_function:nnnN`. We put a `__prg_break_point:Nn` so that `map_break` functions from other modules correctly decrement `\g__prg_map_int` before looking for their own break point. The first argument is `\scan_stop:`, so no breaking function will recognize this break point as its own.

```

3701 \cs_new_protected_nopar:Npn \int_step_inline:nnnn
3702   {
3703     \int_gincr:N \g__prg_map_int
3704     \exp_args:NNc \__int_step:NNnnnn
3705       \cs_gset_nopar:Npn
3706         { __prg_map_ \int_use:N \g__prg_map_int :w }
3707   }
3708 \cs_new_protected:Npn \int_step_variable:nnnNn #1#2#3#4#5
3709   {
3710     \int_gincr:N \g__prg_map_int
3711     \exp_args:NNc \__int_step:NNnnnn
3712       \cs_gset_nopar:Npx
3713         { __prg_map_ \int_use:N \g__prg_map_int :w }
3714         {#1}{#2}{#3}
3715         {
3716           \tl_set:Nn \exp_not:N #4 {##1}
3717           \exp_not:n {#5}
3718         }
3719   }
3720 \cs_new_protected:Npn \__int_step:NNnnnn #1#2#3#4#5#6
3721   {
3722     #1 #2 ##1 {#6}
3723     \int_step_function:nnnN {#3} {#4} {#5} #2
3724     \__prg_break_point:Nn \scan_stop: { \int_gdecr:N \g__prg_map_int }
3725   }
```

(End definition for `\int_step_inline:nnnn` This function is documented on page 67.)

8.8 Formatting integers

`\int_to_arabic:n`

Nothing exciting here.

```
3726 \cs_new:Npn \int_to_arabic:n #1 { \int_eval:n {#1} }
```

(End definition for `\int_to_arabic:n` This function is documented on page 67.)

`\int_to_symbols:nn`
`__int_to_symbols:nnnn`

For conversion of integers to arbitrary symbols the method is in general as follows. The input number (#1) is compared to the total number of symbols available at each place (#2). If the input is larger than the total number of symbols available then the modulus

is needed, with one added so that the positions don't have to number from zero. Using an f-type expansion, this is done so that the system is recursive. The actual conversion function therefore gets a 'nice' number at each stage. Of course, if the initial input was small enough then there is no problem and everything is easy.

```

3727 \cs_new:Npn \int_to_symbols:n {#1} {#2} {#3}
3728 {
3729   \int_compare:nNnTF {#1} > {#2}
3730   {
3731     \exp_args:NNo \exp_args:No \__int_to_symbols:nnnn
3732     {
3733       \int_case:nnn
3734       { 1 + \int_mod:nn {#1 - 1} {#2} } {#3} { }
3735     }
3736   }
3737   {#1} {#2} {#3}
3738 }
3739 { \int_case:nnn {#1} {#3} { } }
3740 }
3741 \cs_new:Npn \__int_to_symbols:nnnn {#1} {#2} {#3} {#4}
3742 {
3743   \exp_args:Nf \int_to_symbols:nnn
3744   { \int_div_truncate:nn {#2 - 1} {#3} } {#3} {#4}
3745   #1
3746 }
```

(End definition for `\int_to_symbols:n`. This function is documented on page 68.)

`\int_to_alpha:n` These both use the above function with input functions that make sense for the alphabet
`\int_to_Alph:n` in English.

```

3747 \cs_new:Npn \int_to_alpha:n {#1}
3748 {
3749   \int_to_symbols:nnn {#1} { 26 }
3750   {
3751     { 1 } { a }
3752     { 2 } { b }
3753     { 3 } { c }
3754     { 4 } { d }
3755     { 5 } { e }
3756     { 6 } { f }
3757     { 7 } { g }
3758     { 8 } { h }
3759     { 9 } { i }
3760     { 10 } { j }
3761     { 11 } { k }
3762     { 12 } { l }
3763     { 13 } { m }
3764     { 14 } { n }
3765     { 15 } { o }
3766     { 16 } { p }
3767     { 17 } { q }
```

```

3768      { 18 } { r }
3769      { 19 } { s }
3770      { 20 } { t }
3771      { 21 } { u }
3772      { 22 } { v }
3773      { 23 } { w }
3774      { 24 } { x }
3775      { 25 } { y }
3776      { 26 } { z }
3777    }
3778  }
3779 \cs_new:Npn \int_to_Alph:n #1
3780 {
3781   \int_to_symbols:nnn {#1} { 26 }
3782   {
3783     { 1 } { A }
3784     { 2 } { B }
3785     { 3 } { C }
3786     { 4 } { D }
3787     { 5 } { E }
3788     { 6 } { F }
3789     { 7 } { G }
3790     { 8 } { H }
3791     { 9 } { I }
3792     { 10 } { J }
3793     { 11 } { K }
3794     { 12 } { L }
3795     { 13 } { M }
3796     { 14 } { N }
3797     { 15 } { O }
3798     { 16 } { P }
3799     { 17 } { Q }
3800     { 18 } { R }
3801     { 19 } { S }
3802     { 20 } { T }
3803     { 21 } { U }
3804     { 22 } { V }
3805     { 23 } { W }
3806     { 24 } { X }
3807     { 25 } { Y }
3808     { 26 } { Z }
3809   }
3810 }

```

(End definition for `\int_to_alpha:n` and `\int_to_Alph:n`. These functions are documented on page 68.)

```

\int_to_base:nn
\__int_to_base:nn
\__int_to_base:nnN
\__int_to_base:nnnN
\__int_to_letter:n

```

Converting from base ten (#1) to a second base (#2) starts with computing #1: if it is a complicated calculation, we shouldn't perform it twice. Then check the sign, store it, either - or `\c_empty_t1`, and feed the absolute value to the next auxiliary function.

```
3811 \cs_new:Npn \int_to_base:nn #1
```

```

3812 { \exp_args:Nf \__int_to_base:nn { \int_eval:n {#1} } }
3813 \cs_new:Npn \__int_to_base:nn #1#2
3814 {
3815     \int_compare:nNnTF {#1} < \c_zero
3816         { \exp_args:No \__int_to_base:nnN { \use_none:n #1 } {#2} - }
3817         { \__int_to_base:nnN {#1} {#2} \c_empty_tl }
3818 }

```

Here, the idea is to provide a recursive system to deal with the input. The output is built up after the end of the function. At each pass, the value in #1 is checked to see if it is less than the new base (#2). If it is, then it is converted directly, putting the sign back in front. On the other hand, if the value to convert is greater than or equal to the new base then the modulus and remainder values are found. The modulus is converted to a symbol and put on the right, and the remainder is carried forward to the next round.

```

3819 \cs_new:Npn \__int_to_base:nnN #1#2#3
3820 {
3821     \int_compare:nNnTF {#1} < {#2}
3822         { \exp_last_unbraced:Nf #3 { \__int_to_letter:n {#1} } }
3823         {
3824             \exp_args:Nf \__int_to_base:nnnN
3825                 { \__int_to_letter:n { \int_mod:nn {#1} {#2} } }
3826                 {#1}
3827                 {#2}
3828                 #3
3829         }
3830     }
3831 \cs_new:Npn \__int_to_base:nnnN #1#2#3#4
3832 {
3833     \exp_args:Nf \__int_to_base:nnN
3834         { \int_div_truncate:nn {#2} {#3} }
3835         {#3}
3836         #4
3837     #1
3838 }

```

Convert to a letter only if necessary, otherwise simply return the value unchanged. It would be cleaner to use `\int_case:nnn`, but in our case, the cases are contiguous, so it is forty times faster to use the `\if_case:w` primitive. The first `\exp_after:wN` expands the conditional, jumping to the correct case, the second one expands after the resulting character to close the conditional. Since #1 might be an expression, and not directly a single digit, we need to evaluate it properly, and expand the trailing `\fi:`.

```

3839 \cs_new:Npn \__int_to_letter:n #1
3840 {
3841     \exp_after:wN \exp_after:wN
3842     \if_case:w \__int_eval:w #1 - \c_ten \__int_eval_end:
3843         A
3844         \or: B
3845         \or: C
3846         \or: D
3847         \or: E

```

```

3848      \or: F
3849      \or: G
3850      \or: H
3851      \or: I
3852      \or: J
3853      \or: K
3854      \or: L
3855      \or: M
3856      \or: N
3857      \or: O
3858      \or: P
3859      \or: Q
3860      \or: R
3861      \or: S
3862      \or: T
3863      \or: U
3864      \or: V
3865      \or: W
3866      \or: X
3867      \or: Y
3868      \or: Z
3869      \else: \__int_value:w \__int_eval:w #1 \exp_after:wN \__int_eval_end:
3870      \fi:
3871  }

```

(End definition for `\int_to_base:nn` This function is documented on page 69.)

`\int_to_binary:n`

```
\int_to_hexadecimal:n
\int_to_octal:n
```

Wrappers around the generic function.

```

3872 \cs_new:Npn \int_to_binary:n #1
3873   { \int_to_base:nn {#1} { 2 } }
3874 \cs_new:Npn \int_to_hexadecimal:n #1
3875   { \int_to_base:nn {#1} { 16 } }
3876 \cs_new:Npn \int_to_octal:n #1
3877   { \int_to_base:nn {#1} { 8 } }

```

(End definition for `\int_to_binary:n`, `\int_to_hexadecimal:n`, and `\int_to_octal:n` These functions are documented on page 69.)

`\int_to_roman:n`

`\int_to_Roman:n`

```
\__int_to_roman:N
```

```
\__int_to_roman:N
```

```
\__int_to_roman_i:w
```

```
\__int_to_roman_v:w
```

```
\__int_to_roman_x:w
```

```
\__int_to_roman_l:w
```

```
\__int_to_roman_c:w
```

```
\__int_to_roman_d:w
```

```
\__int_to_roman_m:w
```

```
\__int_to_roman_Q:w
```

```
\__int_to_Roman_i:w
```

```
\__int_to_Roman_v:w
```

```
\__int_to_Roman_x:w
```

```
\__int_to_Roman_l:w
```

```
\__int_to_Roman_c:w
```

```
\__int_to_Roman_d:w
```

```
\__int_to_Roman_m:w
```

```
\__int_to_Roman_Q:w
```

The `__int_to_roman:w` primitive creates tokens of category code 12 (other). Usually, what is actually wanted is letters. The approach here is to convert the output of the primitive into letters using appropriate control sequence names. That keeps everything expandable. The loop will be terminated by the conversion of the Q.

```

3878 \cs_new:Npn \int_to_roman:n #1
3879   {
3880     \exp_after:wN \__int_to_roman:N
3881       \__int_to_roman:w \int_eval:n {#1} Q
3882   }
3883 \cs_new:Npn \__int_to_roman:N #1
3884   {
3885     \use:c { __int_to_roman_ #1 :w }
3886     \__int_to_roman:N

```

```

3887   }
3888 \cs_new:Npn \int_to_Roman:n #1
3889 {
3890   \exp_after:wN \__int_to_Roman_aux:N
3891   \__int_to_roman:w \int_eval:n {#1} Q
3892 }
3893 \cs_new:Npn \__int_to_Roman_aux:N #1
3894 {
3895   \use:c { __int_to_Roman_ #1 :w }
3896   \__int_to_Roman_aux:N
3897 }
3898 \cs_new_nopar:Npn \__int_to_roman_i:w { i }
3899 \cs_new_nopar:Npn \__int_to_roman_v:w { v }
3900 \cs_new_nopar:Npn \__int_to_roman_x:w { x }
3901 \cs_new_nopar:Npn \__int_to_roman_l:w { l }
3902 \cs_new_nopar:Npn \__int_to_roman_c:w { c }
3903 \cs_new_nopar:Npn \__int_to_roman_d:w { d }
3904 \cs_new_nopar:Npn \__int_to_roman_m:w { m }
3905 \cs_new_nopar:Npn \__int_to_roman_Q:w #1 { }
3906 \cs_new_nopar:Npn \__int_to_Roman_i:w { I }
3907 \cs_new_nopar:Npn \__int_to_Roman_v:w { V }
3908 \cs_new_nopar:Npn \__int_to_Roman_x:w { X }
3909 \cs_new_nopar:Npn \__int_to_Roman_l:w { L }
3910 \cs_new_nopar:Npn \__int_to_Roman_c:w { C }
3911 \cs_new_nopar:Npn \__int_to_Roman_d:w { D }
3912 \cs_new_nopar:Npn \__int_to_Roman_m:w { M }
3913 \cs_new:Npn \__int_to_Roman_Q:w #1 { }
(End definition for \int_to_roman:n and \int_to_Roman:n These functions are documented on page
69.)

```

8.9 Converting from other formats to integers

`__int_get_sign:n` Finding a number and its sign requires dealing with an arbitrary list of + and - symbols.
`__int_get_digits:n` This is done by working through token by token until there is something else at the start
`__int_get_sign_and_digits:nNNN` of the input. The sign of the input is tracked by the first Boolean used by the auxiliary
`__int_get_sign_and_digits:oNNN` function.

```

3914 \cs_new:Npn \__int_get_sign:n #1
3915 {
3916   \__int_get_sign_and_digits:nNNN {#1}
3917   \c_true_bool \c_true_bool \c_false_bool
3918 }
3919 \cs_new:Npn \__int_get_digits:n #1
3920 {
3921   \__int_get_sign_and_digits:nNNN {#1}
3922   \c_true_bool \c_false_bool \c_true_bool
3923 }

```

The auxiliary loops through, finding sign tokens and removing them. The sign itself is carried through as a flag.

```

3924 \cs_new:Npn \__int_get_sign_and_digits:nNNN #1#2#3#4
3925 {
3926     \exp_args:Nf \tl_if_head_eqCharCode:nNTF {#1} -
3927     {
3928         \bool_if:NTF #2
3929         {
3930             \__int_get_sign_and_digits:oNNN
3931             { \use_none:n #1 } \c_false_bool #3#4
3932         }
3933         {
3934             \__int_get_sign_and_digits:oNNN
3935             { \use_none:n #1 } \c_true_bool #3#4
3936         }
3937     }
3938     {
3939         \exp_args:Nf \tl_if_head_eqCharCode:nNTF {#1} +
3940         { \__int_get_sign_and_digits:oNNN { \use_none:n #1 } #2#3#4 }
3941         {
3942             \bool_if:NT #3 { \bool_if:NF #2 - }
3943             \bool_if:NT #4 {#1}
3944         }
3945     }
3946 }
3947 \cs_generate_variant:Nn \__int_get_sign_and_digits:nNNN { o }
(End definition for \__int_get_sign:n This function is documented on page ??.)
```

\int_from_alpha:n
\int_from_alpha:n
\int_from_alpha:nN
\int_from_alpha:N

The aim here is to iterate through the input, converting one letter at a time to a number. The same approach is also used for base conversion, but this needs a different final auxiliary.

```

3948 \cs_new:Npn \int_from_alpha:n #1
3949 {
3950     \int_eval:n
3951     {
3952         \__int_get_sign:n {#1}
3953         \exp_args:Nf \__int_from_alpha:n { \__int_get_digits:n {#1} }
3954     }
3955 }
3956 \cs_new:Npn \__int_from_alpha:n #1
3957 { \__int_from_alpha:nN { 0 } #1 \q_nil }
3958 \cs_new:Npn \__int_from_alpha:nN #1#
3959 {
3960     \quark_if_nil:NTF #2
3961     {#1}
3962     {
3963         \exp_args:Nf \__int_from_alpha:nN
3964         { \int_eval:n { #1 * 26 + \__int_from_alpha:N #2 } }
3965     }
3966 }
3967 \cs_new:Npn \__int_from_alpha:N #1
```

```

3968 { \int_eval:n { '#1 - \int_compare:nNnTF { '#1 } < { 91 } { 64 } { 96 } } }
(End definition for \int_from_alpha:n This function is documented on page 69.)
```

\int_from_base:nn
__int_from_base:nn
__int_from_base:nnN
__int_from_base:N

Conversion to base ten means stripping off the sign then iterating through the input one token at a time. The total number is then added up as the code loops.

```

3969 \cs_new:Npn \int_from_base:nn #1#2
3970 {
3971     \int_eval:n
3972     {
3973         \__int_get_sign:n {#1}
3974         \exp_args:Nf \__int_from_base:nn
3975             { \__int_get_digits:n {#1} } {#2}
3976     }
3977 }
3978 \cs_new:Npn \__int_from_base:nn #1#2
3979 { \__int_from_base:nnN { 0 } { #2 } #1 \q_nil }
3980 \cs_new:Npn \__int_from_base:nnN #1#2#3
3981 {
3982     \quark_if_nil:NTF #3
3983     {#1}
3984     {
3985         \exp_args:Nf \__int_from_base:nnN
3986             { \int_eval:n { #1 * #2 + \__int_from_base:N #3 } }
3987             {#2}
3988     }
3989 }
```

The conversion here will take lower or upper case letters and turn them into the appropriate number, hence the two-part nature of the function.

```

3990 \cs_new:Npn \__int_from_base:N #1
3991 {
3992     \int_compare:nNnTF { '#1 } < { 58 }
3993     {#1}
3994     {
3995         \int_eval:n
3996             { '#1 - \int_compare:nNnTF { '#1 } < { 91 } { 55 } { 87 } }
3997     }
3998 }
```

(End definition for \int_from_base:nn This function is documented on page 70.)

\int_from_binary:n
\int_from_hexadecimal:n
\int_from_octal:n

Wrappers around the generic function.

```

3999 \cs_new:Npn \int_from_binary:n #1
4000 { \int_from_base:nn {#1} \c_two }
4001 \cs_new:Npn \int_from_hexadecimal:n #1
4002 { \int_from_base:nn {#1} \c_sixteen }
4003 \cs_new:Npn \int_from_octal:n #1
4004 { \int_from_base:nn {#1} \c_eight }
```

(End definition for \int_from_binary:n, \int_from_hexadecimal:n, and \int_from_octal:n These functions are documented on page 70.)

```

\c__int_from_roman_i_int
\c__int_from_roman_v_int
\c__int_from_roman_x_int
\c__int_from_roman_l_int
\c__int_from_roman_c_int
\c__int_from_roman_d_int
\c__int_from_roman_m_int
\c__int_from_roman_I_int
\c__int_from_roman_V_int
\c__int_from_roman_X_int
\c__int_from_roman_L_int
\c__int_from_roman_C_int
\c__int_from_roman_D_int
\c__int_from_roman_M_int

4005 \int_const:cn { c__int_from_roman_i_int } { 1 }
4006 \int_const:cn { c__int_from_roman_v_int } { 5 }
4007 \int_const:cn { c__int_from_roman_x_int } { 10 }
4008 \int_const:cn { c__int_from_roman_l_int } { 50 }
4009 \int_const:cn { c__int_from_roman_c_int } { 100 }
4010 \int_const:cn { c__int_from_roman_d_int } { 500 }
4011 \int_const:cn { c__int_from_roman_m_int } { 1000 }
4012 \int_const:cn { c__int_from_roman_I_int } { 1 }
4013 \int_const:cn { c__int_from_roman_V_int } { 5 }
4014 \int_const:cn { c__int_from_roman_X_int } { 10 }
4015 \int_const:cn { c__int_from_roman_L_int } { 50 }
4016 \int_const:cn { c__int_from_roman_C_int } { 100 }
4017 \int_const:cn { c__int_from_roman_D_int } { 500 }
4018 \int_const:cn { c__int_from_roman_M_int } { 1000 }

(End definition for \c__int_from_roman_i_int and others. These variables are documented on page
??.)

```

\int_from_roman:n

```

\_\_int_from_roman:NN
\_\_int_from_roman_end:w
\_\_int_from_roman_clean_up:w

```

The method here is to iterate through the input, finding the appropriate value for each letter and building up a sum. This is then evaluated by TeX.

```

4019 \cs_new:Npn \int_from_roman:n #1
4020 {
4021     \tl_if_blank:nF {#1}
4022     {
4023         \exp_after:wN \_\_int_from_roman_end:w
4024             \_\_int_value:w \_\_int_eval:w
4025                 \_\_int_from_roman:NN #1 Q \q_stop
4026             }
4027     }
4028 \cs_new:Npn \_\_int_from_roman:NN #1#2
4029 {
4030     \str_if_eq:nnTF {#1} { Q }
4031         {#1#2}
4032     {
4033         \str_if_eq:nnTF {#2} { Q }
4034         {
4035             \int_if_exist:cF { c__int_from_roman_ #1 _int }
4036                 { \_\_int_from_roman_clean_up:w }
4037                 +
4038                 \use:c { c__int_from_roman_ #1 _int }
4039                 #2
4040             }
4041         {
4042             \int_if_exist:cF { c__int_from_roman_ #1 _int }
4043                 { \_\_int_from_roman_clean_up:w }
4044                 \int_if_exist:cF { c__int_from_roman_ #2 _int }
4045                     { \_\_int_from_roman_clean_up:w }
4046                     \int_compare:nNnTF
4047                         { \use:c { c__int_from_roman_ #1 _int } }

```

```

4048 <
4049 { \use:c { c__int_from_roman_ #2 _int } }
4050 {
4051     + \use:c { c__int_from_roman_ #2 _int }
4052     - \use:c { c__int_from_roman_ #1 _int }
4053     \_int_from_roman:NN
4054 }
4055 {
4056     + \use:c { c__int_from_roman_ #1 _int }
4057     \_int_from_roman:NN #2
4058 }
4059 }
4060 }
4061 }
4062 \cs_new:Npn \_int_from_roman_end:w #1 Q #2 \q_stop
4063   { \tl_if_empty:nTF {#2} {#1} {#2} }
4064 \cs_new:Npn \_int_from_roman_clean_up:w #1 Q { + 0 Q -1 }
(End definition for \int_from_roman:n This function is documented on page 70.)

```

8.10 Viewing integer

\int_show:N
\int_show:c 4065 \cs_new_eq:NN \int_show:N _kernel_register_show:N
4066 \cs_new_eq:NN \int_show:c _kernel_register_show:c
(End definition for \int_show:N and \int_show:c These functions are documented on page ??.)

\int_show:n We don't use the TeX primitive `\showthe` to show integer expressions: this gives a more unified output, since the closing brace is read by the integer expression in all cases.

```

4067 \cs_new_protected:Npn \int_show:n #1
4068   { \etex_showtokens:D \exp_after:wN { \int_use:N \_int_eval:w #1 } }
(End definition for \int_show:n This function is documented on page 70.)

```

8.11 Constant integers

\c_minus_one This is needed early, and so is in `l3basics`
(End definition for \c_minus_one This variable is documented on page 71.)

\c_zero Again, one in `l3basics` for obvious reasons.
(End definition for \c_zero This variable is documented on page 71.)

\c_six Once again, in `l3basics`.
\c_seven (End definition for \c_six and \c_seven These functions are documented on page 71.)

\c_twelve Low-number values not previously defined.

```

4069 \int_const:Nn \c_one      { 1 }
4070 \int_const:Nn \c_two      { 2 }
4071 \int_const:Nn \c_three    { 3 }
4072 \int_const:Nn \c_four     { 4 }
4073 \int_const:Nn \c_five     { 5 }
\c_six
\c_seven
\c_eight
\c_nine
\c_ten
\c_eleven
\c_twelve
\c_thirteen
\c_fourteen
\c_fifteen

```

```

4074 \int_const:Nn \c_eight { 8 }
4075 \int_const:Nn \c_nine { 9 }
4076 \int_const:Nn \c_ten { 10 }
4077 \int_const:Nn \c_eleven { 11 }
4078 \int_const:Nn \c_thirteen { 13 }
4079 \int_const:Nn \c_fourteen { 14 }
4080 \int_const:Nn \c_fifteen { 15 }

```

(End definition for `\c_one` and others. These variables are documented on page 71.)

`\c_thirty_two` One middling value.

```
4081 \int_const:Nn \c_thirty_two { 32 }
```

(End definition for `\c_thirty_two`. This variable is documented on page 71.)

`\c_two_hundred_fifty_five` Two classic mid-range integer constants.

```

4082 \int_const:Nn \c_two_hundred_fifty_five { 255 }
4083 \int_const:Nn \c_two_hundred_fifty_six { 256 }

```

(End definition for `\c_two_hundred_fifty_five` and `\c_two_hundred_fifty_six`. These variables are documented on page 71.)

`\c_one_hundred` Simple runs of powers of ten.

```

4084 \int_const:Nn \c_one_hundred { 100 }
4085 \int_const:Nn \c_one_thousand { 1000 }
4086 \int_const:Nn \c_ten_thousand { 10000 }

```

(End definition for `\c_one_hundred`, `\c_one_thousand`, and `\c_ten_thousand`. These variables are documented on page 71.)

`\c_max_int` The largest number allowed is $2^{31} - 1$

```
4087 \int_const:Nn \c_max_int { 2 147 483 647 }
```

(End definition for `\c_max_int`. This variable is documented on page 71.)

8.12 Scratch integers

`\l_tmpa_int` We provide two local and two global scratch counters, maybe we need more or less.

```

4088 \int_new:N \l_tmpa_int
4089 \int_new:N \l_tmpb_int
4090 \int_new:N \g_tmpa_int
4091 \int_new:N \g_tmpb_int

```

(End definition for `\l_tmpa_int` and `\l_tmpb_int`. These functions are documented on page 71.)

8.13 Deprecated functions

Deprecated on 2011-05-27, for removal by 2011-08-31.

Some simple renames.

```
4092  {*deprecated}
4093  \cs_new_eq:NN \int_convert_from_base_ten:nn \int_to_base:nn
4094  \cs_new_eq:NN \int_convert_to_symbols:nnn  \int_to_symbols:nnn
4095  \cs_new_eq:NN \int_convert_to_base_ten:nn  \int_from_base:nn
4096  {/deprecated}
```

(End definition for `\int_convert_from_base_ten:nn` This function is documented on page ??.)

This is rather too tied to L^AT_EX 2 _{ϵ} .

```
4097  {*deprecated}
4098  \cs_new_nopar:Npn \int_to_symbol:n
4099  {
4100    \scan_align_safe_stop:
4101    \mode_if_math:TF
4102      { \int_to_symbol_math:n }
4103      { \int_to_symbol_text:n }
4104  }
4105  \cs_new:Npn \int_to_symbol_math:n #1
4106  {
4107    \int_to_symbols:nnn {#1} { 9 }
4108    {
4109      { 1 } { * }
4110      { 2 } { \dagger }
4111      { 3 } { \ddagger }
4112      { 4 } { \mathsection }
4113      { 5 } { \mathparagraph }
4114      { 6 } { \textbar }
4115      { 7 } { ** }
4116      { 8 } { \dagger \dagger }
4117      { 9 } { \ddagger \ddagger }
4118    }
4119  }
4120  \cs_new:Npn \int_to_symbol_text:n #1
4121  {
4122    \int_to_symbols:nnn {#1} { 9 }
4123    {
4124      { 1 } { \textasteriskcentered }
4125      { 2 } { \textdagger }
4126      { 3 } { \textdaggerdbl }
4127      { 4 } { \textsection }
4128      { 5 } { \textparagraph }
4129      { 6 } { \textbardbl }
4130      { 7 } { \textasteriskcentered \textasteriskcentered }
4131      { 8 } { \textdagger \textdagger }
4132      { 9 } { \textdaggerdbl \textdaggerdbl }
4133    }
```

```

4134   }
4135 </deprecated>
(End definition for \int_to_symbol:n This function is documented on page ??.)

\if_num:w Deprecated 2012-05-30 for removal after 2012-11-30.
4136 \cs_new_eq:NN \if_num:w \if_int_compare:w
(End definition for \if_num:w This function is documented on page ??.)

\l_tmpc_int Deprecated 2012-07-04 for removal after 2012-12-31.
4137 \int_new:N \l_tmpc_int
(End definition for \l_tmpc_int This variable is documented on page ??.)

\int_eval:w Deprecated 2012-07-13 for removal after 2012-12-31.
\int_eval_end:
4138 \cs_new_eq:NN \int_eval:w \__int_eval:w
4139 \cs_new_eq:NN \int_eval_end: \__int_eval_end:
(End definition for \int_eval:w and \int_eval_end: These functions are documented on page ??.)

\int_value:w Deprecated 2012-07-14 for removal after 2012-12-31.
4140 \cs_new_eq:NN \int_value:w \__int_value:w
(End definition for \int_value:w This function is documented on page ??.)
4141 </initex | package>

```

9 l3skip implementation

```

4142 <*initex | package>
4143 <@@=dim>
4144 <*package>
4145 \ProvidesExplPackage
4146 {\ExplFileName}{\ExplFileVersion}{\ExplFileDescription}
4147 \__expl_package_check:
4148 </package>

```

9.1 Length primitives renamed

`\if_dim:w` Primitives renamed.

`__dim_eval:w` 4149 $\cs_new_eq:NN \if_dim:w \tex_ifdim:D$

`__dim_eval_end:` 4150 $\cs_new_eq:NN __dim_eval:w \tex_dimexpr:D$

4151 $\cs_new_eq:NN __dim_eval_end: \tex_relax:D$

(End definition for \if_dim:w This function is documented on page 86.)

9.2 Creating and initialising dim variables

\dim_new:N Allocating $\langle dim \rangle$ registers ...

```

4152  {*package}
4153  \cs_new_protected:Npn \dim_new:N #1
4154  {
4155    \__chk_if_free_cs:N #1
4156    \newdimen #1
4157  }
4158  {/package}
4159  \cs_generate_variant:Nn \dim_new:N { c }
(End definition for \dim_new:N and \dim_new:c These functions are documented on page ??.)
```

\dim_const:Nn Contrarily to integer constants, we cannot avoid using a register, even for constants.

```

4160  \cs_new_protected:Npn \dim_const:Nn #1
4161  {
4162    \dim_new:N #1
4163    \dim_gset:Nn #1
4164  }
4165  \cs_generate_variant:Nn \dim_const:Nn { c }
(End definition for \dim_const:Nn and \dim_const:cn These functions are documented on page ??.)
```

\dim_zero:N Reset the register to zero.

```

4166  \cs_new_protected:Npn \dim_zero:N #1 { #1 \c_zero_dim }
4167  \cs_new_protected:Npn \dim_gzero:N { \tex_global:D \dim_zero:N }
4168  \cs_generate_variant:Nn \dim_zero:N { c }
4169  \cs_generate_variant:Nn \dim_gzero:N { c }
(End definition for \dim_zero:N and \dim_zero:c These functions are documented on page ??.)
```

\dim_zero_new:N Create a register if needed, otherwise clear it.

```

4170  \cs_new_protected:Npn \dim_zero_new:N #1
4171  { \dim_if_exist:NTF #1 { \dim_zero:N #1 } { \dim_new:N #1 } }
4172  \cs_new_protected:Npn \dim_gzero_new:N #1
4173  { \dim_if_exist:NTF #1 { \dim_gzero:N #1 } { \dim_new:N #1 } }
4174  \cs_generate_variant:Nn \dim_zero_new:N { c }
4175  \cs_generate_variant:Nn \dim_gzero_new:N { c }
(End definition for \dim_zero_new:N and others. These functions are documented on page ??.)
```

\dim_if_exist_p:N Copies of the cs functions defined in l3basics.

```

4176  \cs_new_eq:NN \dim_if_exist:NTF \cs_if_exist:NTF
4177  \cs_new_eq:NN \dim_if_exist:NT \cs_if_exist:NT
4178  \cs_new_eq:NN \dim_if_exist:NF \cs_if_exist:NF
4179  \cs_new_eq:NN \dim_if_exist_p:N \cs_if_exist_p:N
4180  \cs_new_eq:NN \dim_if_exist:cTF \cs_if_exist:cTF
4181  \cs_new_eq:NN \dim_if_exist:cT \cs_if_exist:cT
4182  \cs_new_eq:NN \dim_if_exist:cF \cs_if_exist:cF
4183  \cs_new_eq:NN \dim_if_exist_p:c \cs_if_exist_p:c
(End definition for \dim_if_exist:N and \dim_if_exist:c These functions are documented on page ??.)
```

9.3 Setting dim variables

`\dim_set:Nn`

`\dim_set:cn`

`\dim_gset:Nn`

`\dim_gset:cn`

```
4184 \cs_new_protected:Npn \dim_set:Nn #1#2
4185   { #1 ~ \_dim_eval:w #2 \_dim_eval_end: }
4186 \cs_new_protected:Npn \dim_gset:Nn { \tex_global:D \dim_set:Nn }
4187 \cs_generate_variant:Nn \dim_set:Nn { c }
4188 \cs_generate_variant:Nn \dim_gset:Nn { c }

(End definition for \dim_set:Nn and \dim_set:cn These functions are documented on page ??.)
```

`\dim_set_eq:NN`

`\dim_set_eq:cN`

`\dim_set_eq:Nc`

`\dim_set_eq:cc`

`\dim_gset_eq:NN`

`\dim_gset_eq:cN`

`\dim_gset_eq:Nc`

`\dim_gset_eq:cc`

```
4189 \cs_new_protected:Npn \dim_set_eq:NN #1#2 { #1 = #2 }
4190 \cs_generate_variant:Nn \dim_set_eq:NN { c }
4191 \cs_generate_variant:Nn \dim_set_eq:NN { Nc , cc }
4192 \cs_new_protected:Npn \dim_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
4193 \cs_generate_variant:Nn \dim_gset_eq:NN { c }
4194 \cs_generate_variant:Nn \dim_gset_eq:NN { Nc , cc }

(End definition for \dim_set_eq:NN and others. These functions are documented on page ??.)
```

`\dim_add:Nn`

`\dim_add:cn`

`\dim_gadd:Nn`

`\dim_gadd:cn`

`\dim_sub:Nn`

`\dim_sub:cn`

`\dim_gsub:Nn`

`\dim_gsub:cn`

```
4195 \cs_new_protected:Npn \dim_add:Nn #1#2
4196   { \tex_advance:D #1 by \_dim_eval:w #2 \_dim_eval_end: }
4197 \cs_new_protected:Npn \dim_gadd:Nn { \tex_global:D \dim_add:Nn }
4198 \cs_generate_variant:Nn \dim_add:Nn { c }
4199 \cs_generate_variant:Nn \dim_gadd:Nn { c }
4200 \cs_new_protected:Npn \dim_sub:Nn #1#2
4201   { \tex_advance:D #1 by - \_dim_eval:w #2 \_dim_eval_end: }
4202 \cs_new_protected:Npn \dim_gsub:Nn { \tex_global:D \dim_sub:Nn }
4203 \cs_generate_variant:Nn \dim_sub:Nn { c }
4204 \cs_generate_variant:Nn \dim_gsub:Nn { c }

(End definition for \dim_add:Nn and \dim_add:cn These functions are documented on page ??.)
```

9.4 Utilities for dimension calculations

`\dim_abs:n`

`_dim_abs:N`

`\dim_max:nn`

`\dim_min:nn`

`_dim_maxmin:wwN`

```
4205 \cs_new:Npn \dim_abs:n #1
4206   {
4207     \exp_after:wN \_dim_abs:N
4208     \dim_use:N \_dim_eval:w #1 \_dim_eval_end:
4209   }
4210 \cs_new:Npn \_dim_abs:N #1
4211   { \if_meaning:w - #1 \else: \exp_after:wN #1 \fi: }
4212 \cs_set:Npn \dim_max:nn #1#2
4213   {
4214     \dim_use:N \_dim_eval:w \exp_after:wN \_dim_maxmin:wwN
4215     \dim_use:N \_dim_eval:w #1 \exp_after:wN ;
4216     \dim_use:N \_dim_eval:w #2 ;
```

```

4217      >
4218      \__dim_eval_end:
4219  }
4220 \cs_set:Npn \dim_min:nn #1#2
4221 {
4222     \dim_use:N \__dim_eval:w \exp_after:wN \__dim_maxmin:wwN
4223         \dim_use:N \__dim_eval:w #1 \exp_after:wN ;
4224         \dim_use:N \__dim_eval:w #2 ;
4225     <
4226     \__dim_eval_end:
4227 }
4228 \cs_new:Npn \__dim_maxmin:wwN #1 ; #2 ; #3
4229 {
4230     \if_dim:w #1 #3 #2 ~
4231         #1
4232     \else:
4233         #2
4234     \fi:
4235 }

```

(End definition for `\dim_abs:n` This function is documented on page 75.)

\dim_ratio:nn
__dim_ratio:n

With dimension expressions, something like `10 pt * (5 pt / 10 pt)` will not work. Instead, the ratio part needs to be converted to an integer expression. Using `__int_value:w` forces everything into sp, avoiding any decimal parts.

```

4236 \cs_new:Npn \dim_ratio:nn #1#2
4237     { \__dim_ratio:n {#1} / \__dim_ratio:n {#2} }
4238 \cs_new:Npn \__dim_ratio:n #1
4239     { \__int_value:w \__dim_eval:w #1 \__dim_eval_end: }

```

(End definition for `\dim_ratio:nn` This function is documented on page 76.)

9.5 Dimension expression conditionals

\dim_compare_p:nNn
\dim_compare:nNnTF

Simple comparison.

```

4240 \prg_new_conditional:Npnn \dim_compare:nNn #1#2#3 { p , T , F , TF }
4241 {
4242     \if_dim:w \__dim_eval:w #1 #2 \__dim_eval:w #3 \__dim_eval_end:
4243         \prg_return_true: \else: \prg_return_false: \fi:
4244 }

```

(End definition for `\dim_compare:nNn` These functions are documented on page 76.)

\dim_compare_p:n
\dim_compare:nTF
__dim_compare_aux:w
__dim_compare_aux:NNw
__dim_compare_=:NNw
__dim_compare_<:NNw
__dim_compare_>:NNw
__dim_compare_==:NNw
__dim_compare_!=:NNw
__dim_compare_<=:NNw
__dim_compare_>=:NNw

This code is adapted from the `\int_compare:nTF` function. First evaluate the left-hand side. Then access the relation symbol by grabbing until pt (with category other), and pursue otherwise just as for `\int_compare:nTF`.

```

4245 \prg_new_conditional:Npnn \dim_compare:n #1 { p , T , F , TF }
4246 {
4247     \exp_after:wN \__dim_compare_aux:w \dim_use:N \__dim_eval:w #1
4248         \__prg_compare_error: \__dim_eval_end:
4249         \prg_return_true:

```

```

4250     \else:
4251         \prg_return_false:
4252     \fi:
4253 }
4254 \exp_args:Nno \use:nn
4255 { \cs_new:Npn \__dim_compare_aux:w #1 }
4256 { \tl_to_str:n { pt } }
4257 #2 \__prg_compare_error:
4258 {
4259     \exp_after:wn \__dim_compare_aux:NNw #2 ?? \q_mark
4260     #1 pt #2
4261 }
4262 \cs_new:Npn \__dim_compare_aux:NNw #1#2#3 \q_mark
4263 {
4264     \use:c { __dim_compare_ #1 \if_meaning:w = #2 = \fi: :NNw }
4265         \__prg_compare_error:Nw #1
4266 }
4267 \cs_new:cpn { __dim_compare_=:NNw } #1#2#3 =
4268 { \if_dim:w #3 = \__dim_eval:w }
4269 \cs_new:cpn { __dim_compare_<:NNw } #1#2#3 <
4270 { \if_dim:w #3 < \__dim_eval:w }
4271 \cs_new:cpn { __dim_compare_>:NNw } #1#2#3 >
4272 { \if_dim:w #3 > \__dim_eval:w }
4273 \cs_new:cpn { __dim_compare_==:NNw } #1#2#3 ==
4274 { \if_dim:w #3 = \__dim_eval:w }
4275 \cs_new:cpn { __dim_compare_!=:NNw } #1#2#3 !=
4276 { \reverse_if:N \if_dim:w #3 = \__dim_eval:w }
4277 \cs_new:cpn { __dim_compare_<=:NNw } #1#2#3 <=
4278 { \reverse_if:N \if_dim:w #3 > \__dim_eval:w }
4279 \cs_new:cpn { __dim_compare_>=:NNw } #1#2#3 >=
4280 { \reverse_if:N \if_dim:w #3 < \__dim_eval:w }
(End definition for \dim_compare:n These functions are documented on page 76.)
```

\dim_case:nnn

The dimension function is the same as the `int` version, so there is not much to say here.

```

4281 \cs_new:Npn \dim_case:nnm #1
4282 {
4283     \tex_roman numeral:D
4284     \exp_args:Nf \__dim_case_aux:nnn { \dim_eval:n {#1} }
4285 }
4286 \cs_new:Npn \__dim_case_aux:nnn #1#2#3
4287 { \__dim_case_aux:nw {#1} #2 {#1} {#3} \q_recursion_stop }
4288 \cs_new:Npn \__dim_case_aux:nw #1#2#3
4289 {
4290     \dim_compare:nNnTF {#1} = {#2}
4291     { \__dim_case_end:nw {#3} }
4292     { \__dim_case_aux:nw {#1} }
4293 }
4294 \cs_new_eq:NN \__dim_case_end:nw \__prg_case_end:nw
(End definition for \dim_case:nnn This function is documented on page 77.)
```

9.6 Dimension expression loops

\dim_while_do:nn
\dim_until_do:nn
\dim_do_while:nn
\dim_do_until:nn

```

4295 \cs_set:Npn \dim_while_do:nn #1#2
4296 {
4297     \dim_compare:nT {#1}
4298     {
4299         #2
4300         \dim_while_do:nn {#1} {#2}
4301     }
4302 }
4303 \cs_set:Npn \dim_until_do:nn #1#2
4304 {
4305     \dim_compare:nF {#1}
4306     {
4307         #2
4308         \dim_until_do:nn {#1} {#2}
4309     }
4310 }
4311 \cs_set:Npn \dim_do_while:nn #1#2
4312 {
4313     #2
4314     \dim_compare:nT {#1}
4315     { \dim_do_while:nn {#1} {#2} }
4316 }
4317 \cs_set:Npn \dim_do_until:nn #1#2
4318 {
4319     #2
4320     \dim_compare:nF {#1}
4321     { \dim_do_until:nn {#1} {#2} }
4322 }
```

(End definition for \dim_while_do:nn This function is documented on page 78.)

\dim_while_do:nNnn
\dim_until_do:nNnn
\dim_do_while:nNnn
\dim_do_until:nNnn

```

4323 \cs_set:Npn \dim_while_do:nNnn #1#2#3#4
4324 {
4325     \dim_compare:nNnT {#1} #2 {#3}
4326     {
4327         #4
4328         \dim_while_do:nNnn {#1} #2 {#3} {#4}
4329     }
4330 }
4331 \cs_set:Npn \dim_until_do:nNnn #1#2#3#4
4332 {
4333     \dim_compare:nNnF {#1} #2 {#3}
4334     {
4335         #4
4336 }
```

```

4336     \dim_until_do:nNnn {#1} #2 {#3} {#4}
4337   }
4338 }
4339 \cs_set:Npn \dim_do_while:nNnn #1#2#3#4
4340 {
4341   #4
4342   \dim_compare:nNnT {#1} #2 {#3}
4343   { \dim_do_while:nNnn {#1} #2 {#3} {#4} }
4344 }
4345 \cs_set:Npn \dim_do_until:nNnn #1#2#3#4
4346 {
4347   #4
4348   \dim_compare:nNnF {#1} #2 {#3}
4349   { \dim_do_until:nNnn {#1} #2 {#3} {#4} }
4350 }

```

(End definition for `\dim_while:nNnn` This function is documented on page 77.)

9.7 Using dim expressions and variables

`\dim_eval:n` Evaluating a dimension expression expandably.

```

4351 \cs_new:Npn \dim_eval:n #1
4352   { \dim_use:N \__dim_eval:w #1 \__dim_eval_end: }

```

(End definition for `\dim_eval:n` This function is documented on page 78.)

`__dim_strip_bp:n`

```

4353 \cs_new:Npn \__dim_strip_bp:n #1
4354   { \__dim_strip_pt:n { 0.996 26 \__dim_eval:w #1 \__dim_eval_end: } }

```

(End definition for `__dim_strip_bp:n`)

`__dim_strip_pt:n` A function which comes up often enough to deserve a place in the kernel. The idea here is that the input is assumed to be in pt, but can be given in other units, while the output is the value of the dimension in pt but with no units given. This is used a lot by low-level manipulations.

```

4355 \cs_new:Npn \__dim_strip_pt:n #1
4356   {
4357     \exp_after:wN
4358     \__dim_strip_pt:w \dim_use:N \__dim_eval:w #1 \__dim_eval_end: \q_stop
4359   }
4360 \use:x
4361   {
4362     \cs_new:Npn \exp_not:N \__dim_strip_pt:w
4363       ##1 . ##2 \tl_to_str:n { pt } ##3 \exp_not:N \q_stop
4364     {
4365       ##1
4366       \exp_not:N \int_compare:nNnT {##2} > \c_zero
4367       { . ##2 }
4368     }
4369   }

```

(End definition for `_dim_strip_pt:n` This function is documented on page 86.)

`\dim_use:N` Accessing a `(dim)`.

```
4370 \cs_new_eq:NN \dim_use:N \tex_the:D  
4371 \cs_generate_variant:Nn \dim_use:N { c }
```

(End definition for `\dim_use:N` and `\dim_use:c` These functions are documented on page ??.)

9.8 Viewing dim variables

`\dim_show:N` Diagnostics.

```
4372 \cs_new_eq:NN \dim_show:N \__kernel_register_show:N  
4373 \cs_generate_variant:Nn \dim_show:N { c }
```

(End definition for `\dim_show:N` and `\dim_show:c` These functions are documented on page ??.)

`\dim_show:n` Diagnostics. We don't use the TeX primitive `\showthe` to show dimension expressions: this gives a more unified output, since the closing brace is read by the dimension expression in all cases.

```
4374 \cs_new_protected:Npn \dim_show:n #1  
4375 { \etex_showtokens:D \exp_after:wN { \dim_use:N \__dim_eval:w #1 } }
```

(End definition for `\dim_show:n` This function is documented on page 79.)

9.9 Constant dimensions

`\c_zero_dim` The source for these depends on whether we are in package mode.

`\c_max_dim`

```
4376 {*initex}  
4377 \dim_new:N \c_zero_dim  
4378 \dim_new:N \c_max_dim  
4379 \dim_set:Nn \c_max_dim { 16383.99999 pt }  
4380 {/initex}  
4381 {*package}  
4382 \cs_new_eq:NN \c_zero_dim \z@  
4383 \cs_new_eq:NN \c_max_dim \maxdimen  
4384 {/package}
```

(End definition for `\c_zero_dim` This function is documented on page 79.)

9.10 Scratch dimensions

`\l_tmpa_dim` We provide two local and two global scratch registers, maybe we need more or less.

`\l_tmpb_dim`

```
4385 \dim_new:N \l_tmpa_dim
```

`\g_tmpa_dim`

```
4386 \dim_new:N \l_tmpb_dim
```

`\g_tmpb_dim`

```
4387 \dim_new:N \g_tmpa_dim
```

```
4388 \dim_new:N \g_tmpb_dim
```

(End definition for `\l_tmpa_dim` and `\l_tmpb_dim` These functions are documented on page 79.)

9.11 Creating and initialising skip variables

\skip_new:N Allocation of a new internal registers.

```

4389  <package>
4390  \cs_new_protected:Npn \skip_new:N #1
4391  {
4392      \__chk_if_free_cs:N #1
4393      \newskip #1
4394  }
4395  </package>
4396  \cs_generate_variant:Nn \skip_new:N { c }
(End definition for \skip_new:N and \skip_new:c These functions are documented on page ??.)
```

\skip_const:Nn Contrarily to integer constants, we cannot avoid using a register, even for constants.

```

4397  \cs_new_protected:Npn \skip_const:Nn #1
4398  {
4399      \skip_new:N #1
4400      \skip_gset:Nn #1
4401  }
4402  \cs_generate_variant:Nn \skip_const:Nn { c }
(End definition for \skip_const:Nn and \skip_const:cn These functions are documented on page ??.)
```

\skip_zero:N Reset the register to zero.

```

4403  \cs_new_protected:Npn \skip_zero:N #1 { #1 \c_zero_skip }
4404  \cs_new_protected:Npn \skip_gzero:N { \tex_global:D \skip_zero:N }
4405  \cs_generate_variant:Nn \skip_zero:N { c }
4406  \cs_generate_variant:Nn \skip_gzero:N { c }
(End definition for \skip_zero:N and \skip_zero:c These functions are documented on page ??.)
```

\skip_zero_new:N Create a register if needed, otherwise clear it.

```

4407  \cs_new_protected:Npn \skip_zero_new:N #1
4408  { \skip_if_exist:NTF #1 { \skip_zero:N #1 } { \skip_new:N #1 } }
4409  \cs_new_protected:Npn \skip_gzero_new:N #1
4410  { \skip_if_exist:NTF #1 { \skip_gzero:N #1 } { \skip_new:N #1 } }
4411  \cs_generate_variant:Nn \skip_zero_new:N { c }
4412  \cs_generate_variant:Nn \skip_gzero_new:N { c }
(End definition for \skip_zero_new:N and others. These functions are documented on page ??.)
```

\skip_if_exist_p:N Copies of the cs functions defined in l3basics.

```

4413  \cs_new_eq:NN \skip_if_exist:NTF \cs_if_exist:NTF
4414  \cs_new_eq:NN \skip_if_exist:NT \cs_if_exist:NT
4415  \cs_new_eq:NN \skip_if_exist:NF \cs_if_exist:NF
4416  \cs_new_eq:NN \skip_if_exist_p:N \cs_if_exist_p:N
4417  \cs_new_eq:NN \skip_if_exist:cTF \cs_if_exist:cTF
4418  \cs_new_eq:NN \skip_if_exist:cT \cs_if_exist:cT
4419  \cs_new_eq:NN \skip_if_exist:cF \cs_if_exist:cF
4420  \cs_new_eq:NN \skip_if_exist_p:c \cs_if_exist_p:c
(End definition for \skip_if_exist:N and \skip_if_exist:c These functions are documented on page ??.)
```

9.12 Setting skip variables

`\skip_set:Nn`

Much the same as for dimensions.

```

4421 \cs_new_protected:Npn \skip_set:Nn #1#2
4422 { #1 ~ \etex_glueexpr:D #2 \scan_stop: }
4423 \cs_new_protected:Npn \skip_gset:Nn { \tex_global:D \skip_set:Nn }
4424 \cs_generate_variant:Nn \skip_set:Nn { c }
4425 \cs_generate_variant:Nn \skip_gset:Nn { c }
(End definition for \skip_set:Nn and \skip_set:cn These functions are documented on page ??.)
```

`\skip_set_eq:NN`
`\skip_set_eq:cN`
`\skip_set_eq:Nc`
`\skip_set_eq:cc`
`\skip_gset_eq:NN`
`\skip_gset_eq:cN`
`\skip_gset_eq:Nc`
`\skip_gset_eq:cc`

All straightforward.

```

4426 \cs_new_protected:Npn \skip_set_eq:NN #1#2 { #1 = #2 }
4427 \cs_generate_variant:Nn \skip_set_eq:NN { c }
4428 \cs_generate_variant:Nn \skip_set_eq:NN { Nc , cc }
4429 \cs_new_protected:Npn \skip_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
4430 \cs_generate_variant:Nn \skip_gset_eq:NN { c }
4431 \cs_generate_variant:Nn \skip_gset_eq:NN { Nc , cc }
(End definition for \skip_set_eq:NN and others. These functions are documented on page ??.)
```

`\skip_add:Nn`
`\skip_add:cn`
`\skip_gadd:Nn`
`\skip_gadd:cn`
`\skip_sub:Nn`
`\skip_sub:cn`
`\skip_gsub:Nn`
`\skip_gsub:cn`

Using `by` here deals with the (incorrect) case `\skip123`.

```

4432 \cs_new_protected:Npn \skip_add:Nn #1#2
4433 { \tex_advance:D #1 by \etex_glueexpr:D #2 \scan_stop: }
4434 \cs_new_protected:Npn \skip_gadd:Nn { \tex_global:D \skip_add:Nn }
4435 \cs_generate_variant:Nn \skip_add:Nn { c }
4436 \cs_generate_variant:Nn \skip_gadd:Nn { c }
4437 \cs_new_protected:Npn \skip_sub:Nn #1#2
4438 { \tex_advance:D #1 by - \etex_glueexpr:D #2 \scan_stop: }
4439 \cs_new_protected:Npn \skip_gsub:Nn { \tex_global:D \skip_sub:Nn }
4440 \cs_generate_variant:Nn \skip_sub:Nn { c }
4441 \cs_generate_variant:Nn \skip_gsub:Nn { c }
(End definition for \skip_add:Nn and \skip_add:cn These functions are documented on page ??.)
```

9.13 Skip expression conditionals

`\skip_if_eq_p:nn`
`\skip_if_eq:nnTF`

Comparing skips means doing two expansions to make strings, and then testing them.
As a result, only equality is tested.

```

4442 \prg_new_conditional:Npnn \skip_if_eq:nn #1#2 { p , T , F , TF }
4443 {
4444     \if_int_compare:w
4445         \pdftex_strcmp:D { \skip_eval:n { #1 } } { \skip_eval:n { #2 } }
4446         = \c_zero
4447         \prg_return_true:
4448     \else:
4449         \prg_return_false:
4450     \fi:
4451 }
```

(End definition for `\skip_if_eq:nn` These functions are documented on page 81.)

```
\skip_if_finite:n  
\skip_if_finite:nTF  
\_skip_if_finite:wwNw
```

With ε -TEX, we have an easy access to the order of infinities of the stretch and shrink components of a skip. However, to access both, we either need to evaluate the expression twice, or evaluate it, then call an auxiliary to extract both pieces of information from the result. Since we are going to need an auxiliary anyways, it is quicker to make it search for the string `fil` which characterizes infinite glue.

```
4452 \cs_set_protected:Npn \_cs_tmp:w #1  
4453 {  
4454   \prg_new_conditional:Npnn \skip_if_finite:n ##1 { p , T , F , TF }  
4455   {  
4456     \exp_after:wN \_skip_if_finite:wwNw  
4457     \skip_use:N \etex_glueexpr:D ##1 ; \prg_return_false:  
4458       #1 ; \prg_return_true: \q_stop  
4459   }  
4460   \cs_new:Npn \_skip_if_finite:wwNw ##1 #1 ##2 ; ##3 ##4 \q_stop {##3}  
4461 }  
4462 \exp_args:No \_cs_tmp:w { \tl_to_str:n { fil } }  
(End definition for \skip_if_finite:n These functions are documented on page 81.)
```

9.14 Using skip expressions and variables

`\skip_eval:n` Evaluating a skip expression expandably.

```
4463 \cs_new:Npn \skip_eval:n #1  
4464   { \skip_use:N \etex_glueexpr:D #1 \scan_stop: }  
(End definition for \skip_eval:n This function is documented on page 81.)
```

`\skip_use:N` Accessing a `<skip>`.

```
\skip_use:c  
4465 \cs_new_eq:NN \skip_use:N \tex_the:D  
4466 \cs_generate_variant:Nn \skip_use:N { c }  
(End definition for \skip_use:N and \skip_use:c These functions are documented on page ??.)
```

9.15 Inserting skips into the output

`\skip_horizontal:N` Inserting skips.

```
\skip_horizontal:c  
\skip_horizontal:n  
  \skip_vertical:N  
\skip_vertical:c  
\skip_vertical:n  
4467 \cs_new_eq:NN \skip_horizontal:N \tex_hskip:D  
4468 \cs_new:Npn \skip_horizontal:n #1  
4469   { \skip_horizontal:N \etex_glueexpr:D #1 \scan_stop: }  
4470 \cs_new_eq:NN \skip_vertical:N \tex_vskip:D  
4471 \cs_new:Npn \skip_vertical:n #1  
4472   { \skip_vertical:N \etex_glueexpr:D #1 \scan_stop: }  
4473 \cs_generate_variant:Nn \skip_horizontal:N { c }  
4474 \cs_generate_variant:Nn \skip_vertical:N { c }  
(End definition for \skip_horizontal:N, \skip_horizontal:c, and \skip_horizontal:n These functions are documented on page ??.)
```

9.16 Viewing skip variables

`\skip_show:N` Diagnostics.
`\skip_show:c` 4475 `\cs_new_eq:NN \skip_show:N _kernel_register_show:N`
4476 `\cs_generate_variant:Nn \skip_show:N { c }`
(End definition for `\skip_show:N` and `\skip_show:c` These functions are documented on page ??.)

`\skip_show:n` Diagnostics. We don't use the TeX primitive `\showthe` to show skip expressions: this gives a more unified output, since the closing brace is read by the skip expression in all cases.

4477 `\cs_new_protected:Npn \skip_show:n #1`
4478 `{ \etex_showtokens:D \exp_after:wN { \tex_the:D \etex_glueexpr:D #1 } }`
(End definition for `\skip_show:n` This function is documented on page 82.)

9.17 Constant skips

`\c_zero_skip` Skips with no rubber component are just dimensions
`\c_max_skip` 4479 `\cs_new_eq:NN \c_zero_skip \c_zero_dim`
4480 `\cs_new_eq:NN \c_max_skip \c_max_dim`
(End definition for `\c_zero_skip` This function is documented on page 82.)

9.18 Scratch skips

We provide two local and two global scratch registers, maybe we need more or less.
`\l_tmpa_skip` 4481 `\skip_new:N \l_tmpa_skip`
`\l_tmpb_skip` 4482 `\skip_new:N \l_tmpb_skip`
`\g_tmpa_skip` 4483 `\skip_new:N \g_tmpa_skip`
`\g_tmpb_skip` 4484 `\skip_new:N \g_tmpb_skip`
(End definition for `\l_tmpa_skip` and `\l_tmpb_skip` These functions are documented on page 82.)

9.19 Creating and initialising muskip variables

`\muskip_new:N` And then we add muskips.
`\muskip_new:c` 4485 `(*package)`
4486 `\cs_new_protected:Npn \muskip_new:N #1`
4487 `{`
4488 `__chk_if_free_cs:N #1`
4489 `\newmuskip #1`
4490 `}`
4491 `(/package)`
4492 `\cs_generate_variant:Nn \muskip_new:N { c }`
(End definition for `\muskip_new:N` and `\muskip_new:c` These functions are documented on page ??.)

\muskip_const:Nn

Contrarily to integer constants, we cannot avoid using a register, even for constants.

```

4493 \cs_new_protected:Npn \muskip_const:Nn #1
4494 {
4495   \muskip_new:N #1
4496   \muskip_gset:Nn #1
4497 }
4498 \cs_generate_variant:Nn \muskip_const:Nn { c }
(End definition for \muskip_const:Nn and \muskip_const:cn These functions are documented on page ??.)
```

\muskip_zero:N

Reset the register to zero.

```

4499 \cs_new_protected:Npn \muskip_zero:N #1
4500 { #1 \c_zero_muskip }
4501 \cs_new_protected:Npn \muskip_gzero:N { \tex_global:D \muskip_zero:N }
4502 \cs_generate_variant:Nn \muskip_zero:N { c }
4503 \cs_generate_variant:Nn \muskip_gzero:N { c }
(End definition for \muskip_zero:N and \muskip_zero:c These functions are documented on page ??.)
```

\muskip_zero_new:N

Create a register if needed, otherwise clear it.

```

4504 \cs_new_protected:Npn \muskip_zero_new:N #1
4505 { \muskip_if_exist:NTF #1 { \muskip_zero:N #1 } { \muskip_new:N #1 } }
4506 \cs_new_protected:Npn \muskip_gzero_new:N #1
4507 { \muskip_if_exist:NTF #1 { \muskip_gzero:N #1 } { \muskip_new:N #1 } }
4508 \cs_generate_variant:Nn \muskip_zero_new:N { c }
4509 \cs_generate_variant:Nn \muskip_gzero_new:N { c }
(End definition for \muskip_zero_new:N and others. These functions are documented on page ??.)
```

\muskip_if_exist_p:c

Copies of the `cs` functions defined in `l3basics`.

```

4510 \cs_new_eq:NN \muskip_if_exist:NTF \cs_if_exist:NTF
4511 \cs_new_eq:NN \muskip_if_exist:NT \cs_if_exist:NT
4512 \cs_new_eq:NN \muskip_if_exist:NF \cs_if_exist:NF
4513 \cs_new_eq:NN \muskip_if_exist_p:N \cs_if_exist_p:N
4514 \cs_new_eq:NN \muskip_if_exist:cTF \cs_if_exist:cTF
4515 \cs_new_eq:NN \muskip_if_exist:cT \cs_if_exist:cT
4516 \cs_new_eq:NN \muskip_if_exist:cF \cs_if_exist:cF
4517 \cs_new_eq:NN \muskip_if_exist_p:c \cs_if_exist_p:c
(End definition for \muskip_if_exist:N and \muskip_if_exist:c These functions are documented on page ??.)
```

9.20 Setting `muskip` variables

\muskip_set:Nn

This should be pretty familiar.

```

4518 \cs_new_protected:Npn \muskip_set:Nn #1#2
4519 { #1 ~ \etex_muexpr:D #2 \scan_stop: }
4520 \cs_new_protected:Npn \muskip_gset:Nn { \tex_global:D \muskip_set:Nn }
4521 \cs_generate_variant:Nn \muskip_set:Nn { c }
4522 \cs_generate_variant:Nn \muskip_gset:Nn { c }
(End definition for \muskip_set:Nn and \muskip_set:cn These functions are documented on page ??.)
```

`\muskip_set_eq:NN`

All straightforward.

```

4523 \cs_new_protected:Npn \muskip_set_eq:NN #1#2 { #1 = #2 }
4524 \cs_generate_variant:Nn \muskip_set_eq:NN { c }
4525 \cs_generate_variant:Nn \muskip_set_eq:NN { Nc , cc }
4526 \cs_new_protected:Npn \muskip_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
4527 \cs_generate_variant:Nn \muskip_gset_eq:NN { c }
4528 \cs_generate_variant:Nn \muskip_gset_eq:NN { Nc , cc }
(End definition for \muskip_set_eq:NN and others. These functions are documented on page ??.)
```

`\muskip_add:Nn`

Using `\etex_muexpr` here deals with the (incorrect) case `\muskip123`.

```

4529 \cs_new_protected:Npn \muskip_add:Nn #1#2
4530 { \tex_advance:D #1 by \etex_muexpr:D #2 \scan_stop: }
4531 \cs_new_protected:Npn \muskip_gadd:Nn { \tex_global:D \muskip_add:Nn }
4532 \cs_generate_variant:Nn \muskip_add:Nn { c }
4533 \cs_generate_variant:Nn \muskip_gadd:Nn { c }
4534 \cs_new_protected:Npn \muskip_sub:Nn #1#2
4535 { \tex_advance:D #1 by - \etex_muexpr:D #2 \scan_stop: }
4536 \cs_new_protected:Npn \muskip_gsub:Nn { \tex_global:D \muskip_sub:Nn }
4537 \cs_generate_variant:Nn \muskip_sub:Nn { c }
4538 \cs_generate_variant:Nn \muskip_gsub:Nn { c }
(End definition for \muskip_add:Nn and \muskip_add:cn These functions are documented on page ??.)
```

9.21 Using muskip expressions and variables

`\muskip_eval:n`

Evaluating a muskip expression expandably.

```

4539 \cs_new:Npn \muskip_eval:n #1
4540 { \muskip_use:N \etex_muexpr:D #1 \scan_stop: }
(End definition for \muskip_eval:n This function is documented on page 84.)
```

`\muskip_use:N`

Accessing a *(muskip)*.

```

4541 \cs_new_eq:NN \muskip_use:N \tex_the:D
4542 \cs_generate_variant:Nn \muskip_use:N { c }
(End definition for \muskip_use:N and \muskip_use:c These functions are documented on page ??.)
```

9.22 Viewing muskip variables

`\muskip_show:N`

Diagnostics.

```

4543 \cs_new_eq:NN \muskip_show:N \__kernel_register_show:N
4544 \cs_generate_variant:Nn \muskip_show:N { c }
(End definition for \muskip_show:N and \muskip_show:c These functions are documented on page ??.)
```

`\muskip_show:n`

Diagnostics. We don't use the TeX primitive `\showthe` to show muskip expressions: this gives a more unified output, since the closing brace is read by the muskip expression in all cases.

```

4545 \cs_new_protected:Npn \muskip_show:n #1
4546 { \etex_showtokens:D \exp_after:wN { \tex_the:D \etex_muexpr:D #1 } }
(End definition for \muskip_show:n This function is documented on page 85.)
```

9.23 Constant muskips

```
\c_zero_muskip  
\c_max_muskip  
4547 \muskip_const:Nn \c_zero_muskip { 0 mu }  
4548 \muskip_const:Nn \c_max_muskip { 16383.99999 mu }  
(End definition for \c_zero_muskip This function is documented on page 85.)
```

9.24 Scratch muskips

```
\l_tmpa_muskip  
\l_tmpb_muskip  
\g_tmpa_muskip  
\g_tmpb_muskip  
4549 \muskip_new:N \l_tmpa_muskip  
4550 \muskip_new:N \l_tmpb_muskip  
4551 \muskip_new:N \g_tmpa_muskip  
4552 \muskip_new:N \g_tmpb_muskip  
(End definition for \l_tmpa_muskip and \l_tmpb_muskip These functions are documented on page 85.)
```

9.25 Deprecated functions

Deprecated on 2012-05-10, for removal by 2012-08-31.

```
\skip_if_infinite_glue_p:n  
\skip_if_infinite_glue:nTF  
4553 \prg_new_conditional:Npnn \skip_if_infinite_glue:n #1 { p , T , F , TF }  
4554 { \skip_if_finite:nTF {#1} \prg_return_false: \prg_return_true: }  
(End definition for \skip_if_infinite_glue:n These functions are documented on page ??.)  
Deprecated 2012-06-03 for removal after 2012-12-31.
```

```
\prg_case_dim:nnn Moved here, was in l3prg but load order means we define it here now.  
4555 \cs_new_eq:NN \prg_case_dim:nnn \dim_case:nnn  
(End definition for \prg_case_dim:nnn This function is documented on page ??.)
```

```
\dim_eval:w  
\dim_eval_end:  
4556 \cs_new_eq:NN \dim_eval:w \__dim_eval:w  
4557 \cs_new_eq:NN \dim_eval_end: \__dim_eval_end:  
(End definition for \dim_eval:w and \dim_eval_end: These functions are documented on page ??.)
```

```
\dim_set_max:Nn  
\dim_set_max:cn  
\dim_set_min:Nn  
\dim_set_min:cn  
\dim_gset_max:Nn  
\dim_gset_max:cn  
\dim_gset_min:Nn  
\dim_gset_min:cn  
\__dim_set_max:NNNn  
4558 \cs_new_protected_nopar:Npn \dim_set_max:Nn  
4559 { \__dim_set_max:NNNn < \dim_set:Nn }  
4560 \cs_new_protected_nopar:Npn \dim_gset_max:Nn  
4561 { \__dim_set_max:NNNn < \dim_gset:Nn }  
4562 \cs_new_protected_nopar:Npn \dim_set_min:Nn  
4563 { \__dim_set_max:NNNn > \dim_set:Nn }  
4564 \cs_new_protected_nopar:Npn \dim_gset_min:Nn  
4565 { \__dim_set_max:NNNn > \dim_gset:Nn }  
4566 \cs_new_protected:Npn \__dim_set_max:NNNn #1#2#3#4  
4567 { \dim_compare:nNnT {#3} #1 {#4} { #2 #3 {#4} } }  
4568 \cs_generate_variant:Nn \dim_set_max:Nn { c }  
4569 \cs_generate_variant:Nn \dim_gset_max:Nn { c }
```

```

4570 \cs_generate_variant:Nn \dim_set_min:Nn { c }
4571 \cs_generate_variant:Nn \dim_gset_min:Nn { c }
(End definition for \dim_set_max:Nn and \dim_set_max:cn These functions are documented on page ??.)
4572 </initex | package>

```

10 l3tl implementation

```

4573 <*initex | package>
4574 <@@=tl>
4575 <*package>
4576 \ProvidesExplPackage
4577 {\ExplFileName}{\ExplFileVersion}{\ExplFileDescription}
4578 \__expl_package_check:
4579 </package>

```

A token list variable is a TeX macro that holds tokens. By using the ε -TeX primitive `\unexpanded` inside a TeX `\edef` it is possible to store any tokens, including #, in this way.

10.1 Functions

\tl_new:N Creating new token list variables is a case of checking for an existing definition and doing the definition.

```

4580 \cs_new_protected:Npn \tl_new:N #
4581 {
4582     \__chk_if_free_cs:N #1
4583     \cs_gset_eq:NN #1 \c_empty_tl
4584 }
4585 \cs_generate_variant:Nn \tl_new:N { c }
(End definition for \tl_new:N and \tl_new:c These functions are documented on page ??.)

```

\tl_const:Nn Constants are also easy to generate.

```

4586 \cs_new_protected:Npn \tl_const:Nn #1#2
4587 {
4588     \__chk_if_free_cs:N #1
4589     \cs_gset_nopar:Npx #1 { \exp_not:n {#2} }
4590 }
4591 \cs_new_protected:Npn \tl_const:Nx #1#2
4592 {
4593     \__chk_if_free_cs:N #1
4594     \cs_gset_nopar:Npx #1 {#2}
4595 }
4596 \cs_generate_variant:Nn \tl_const:Nn { c }
4597 \cs_generate_variant:Nn \tl_const:Nx { c }
(End definition for \tl_const:Nn and others. These functions are documented on page ??.)

```

\tl_clear:N Clearing a token list variable means setting it to an empty value. Error checking will be sorted out by the parent function.

```
4598 \cs_new_protected:Npn \tl_clear:N #1
4599   { \tl_set_eq:NN #1 \c_empty_tl }
4600 \cs_new_protected:Npn \tl_gclear:N #1
4601   { \tl_gset_eq:NN #1 \c_empty_tl }
4602 \cs_generate_variant:Nn \tl_clear:N { c }
4603 \cs_generate_variant:Nn \tl_gclear:N { c }
```

(End definition for **\tl_clear:N** and **\tl_clear:c** These functions are documented on page ??.)

\tl_clear_new:N Clearing a token list variable means setting it to an empty value. Error checking will be sorted out by the parent function.

```
4604 \cs_new_protected:Npn \tl_clear_new:N #1
4605   { \tl_if_exist:NTF #1 { \tl_clear:N #1 } { \tl_new:N #1 } }
4606 \cs_new_protected:Npn \tl_gclear_new:N #1
4607   { \tl_if_exist:NTF #1 { \tl_gclear:N #1 } { \tl_new:N #1 } }
4608 \cs_generate_variant:Nn \tl_clear_new:N { c }
4609 \cs_generate_variant:Nn \tl_gclear_new:N { c }
```

(End definition for **\tl_clear_new:N** and **\tl_clear_new:c** These functions are documented on page ??.)

For setting token list variables equal to each other.

```
4610 \cs_new_eq:NN \tl_set_eq:NN \cs_set_eq:NN
4611 \cs_new_eq:NN \tl_set_eq:cN \cs_set_eq:cN
4612 \cs_new_eq:NN \tl_set_eq:Nc \cs_set_eq:Nc
4613 \cs_new_eq:NN \tl_set_eq:cc \cs_set_eq:cc
4614 \cs_new_eq:NN \tl_gset_eq:NN \cs_gset_eq:NN
4615 \cs_new_eq:NN \tl_gset_eq:cN \cs_gset_eq:cN
4616 \cs_new_eq:NN \tl_gset_eq:Nc \cs_gset_eq:Nc
4617 \cs_new_eq:NN \tl_gset_eq:cc \cs_gset_eq:cc
```

(End definition for **\tl_set_eq:NN** and others. These functions are documented on page ??.)

Concatenating token lists is easy.

```
4618 \cs_new_protected:Npn \tl_concat:NNN #1#2#3
4619   { \tl_set:Nx #1 { \exp_not:o {#2} \exp_not:o {#3} } }
4620 \cs_new_protected:Npn \tl_gconcat:NNN #1#2#3
4621   { \tl_gset:Nx #1 { \exp_not:o {#2} \exp_not:o {#3} } }
4622 \cs_generate_variant:Nn \tl_concat:NNN { ccc }
4623 \cs_generate_variant:Nn \tl_gconcat:NNN { ccc }
```

(End definition for **\tl_concat:NNN** and **\tl_concat:ccc** These functions are documented on page ??.)

Copies of the **cs** functions defined in **l3basics**.

```
4624 \cs_new_eq:NN \tl_if_exist:NTF \cs_if_exist:NTF
4625 \cs_new_eq:NN \tl_if_exist:NT \cs_if_exist:NT
4626 \cs_new_eq:NN \tl_if_exist:NF \cs_if_exist:NF
4627 \cs_new_eq:NN \tl_if_exist_p:N \cs_if_exist_p:N
4628 \cs_new_eq:NN \tl_if_exist:cTF \cs_if_exist:cTF
4629 \cs_new_eq:NN \tl_if_exist:cT \cs_if_exist:cT
4630 \cs_new_eq:NN \tl_if_exist:cF \cs_if_exist:cF
4631 \cs_new_eq:NN \tl_if_exist_p:c \cs_if_exist_p:c
```

(End definition for `\tl_if_exist:N` and `\tl_if_exist:c` These functions are documented on page ??.)

10.2 Constant token lists

`\c_empty_tl` Never full. We need to define that constant before using `\tl_new:N`.

```
4632 \tl_const:Nn \c_empty_tl { }
```

(End definition for `\c_empty_tl` This variable is documented on page 99.)

`\c_job_name_tl` Inherited from the L^AT_EX3 name for the primitive: this needs to actually contain the text of the job name rather than the name of the primitive, of course. Luat_EX does not quote file names containing spaces, whereas pdfT_EX and X_FT_EX do. So there may be a correction to make in the Luat_EX case.

```
4633 <*initex>
4634 \luatex_if_engine:T
4635 {
4636   \tex_everyjob:D \exp_after:wN
4637   {
4638     \tex_the:D \tex_everyjob:D
4639     \lua_now_x:n
4640       { dofile ( assert ( kpse.find_file ("lualatexquotejobname.lua" ) ) ) }
4641   }
4642 }
4643 \tex_everyjob:D \exp_after:wN
4644 {
4645   \tex_the:D \tex_everyjob:D
4646   \tl_const:Nx \c_job_name_tl { \tex_jobname:D }
4647 }
4648 </initex>
4649 <*package>
4650 \tl_const:Nx \c_job_name_tl { \tex_jobname:D }
4651 </package>
```

(End definition for `\c_job_name_tl` This variable is documented on page 99.)

`\c_space_tl` A space as a token list (as opposed to as a character).

```
4652 \tl_const:Nn \c_space_tl { ~ }
```

(End definition for `\c_space_tl` This variable is documented on page 99.)

10.3 Adding to token list variables

`\tl_set:Nn` By using `\exp_not:n` token list variables can contain # tokens, which makes the token list registers provided by T_EX more or less redundant. The `\tl_set:N` version is done “by hand” as it is used quite a lot.

```
4653 \cs_new_protected:Npn \tl_set:Nn #1#2
4654   { \cs_set_nopar:Npx #1 { \exp_not:n {#2} } }
4655 \cs_new_protected:Npn \tl_set:Nx #1#2
4656   { \cs_set_nopar:Npx #1 { \exp_not:o {#2} } }
4657 \cs_new_protected:Npn \tl_set:cV #1#2
4658   { \cs_set_nopar:Npx #1 {#2} }
\tl_set:cv
\tl_set:co
\tl_set:cf
\tl_set:cx
\tl_gset:Nn
\tl_gset:NV
\tl_gset:Nv
\tl_gset:No
\tl_gset:Nf
\tl_gset:Nx
\tl_gset:Nm
```

```

4659 \cs_new_protected:Npn \tl_gset:Nn #1#2
4660   { \cs_gset_nopar:Npx #1 { \exp_not:n {#2} } }
4661 \cs_new_protected:Npn \tl_gset:No #1#2
4662   { \cs_gset_nopar:Npx #1 { \exp_not:o {#2} } }
4663 \cs_new_protected:Npn \tl_gset:Nx #1#2
4664   { \cs_gset_nopar:Npx #1 {#2} }
4665 \cs_generate_variant:Nn \tl_set:Nn { NV , Nv , Nf }
4666 \cs_generate_variant:Nn \tl_set:Nx { c }
4667 \cs_generate_variant:Nn \tl_set:Nn { c, co , cV , cv , cf }
4668 \cs_generate_variant:Nn \tl_gset:Nn { NV , Nv , Nf }
4669 \cs_generate_variant:Nn \tl_gset:Nx { c }
4670 \cs_generate_variant:Nn \tl_gset:Nn { c, co , cV , cv , cf }

(End definition for \tl_set:Nn and others. These functions are documented on page ??.)
```

\tl_put_left:Nn

Adding to the left is done directly to gain a little performance.

```

4671 \cs_new_protected:Npn \tl_put_left:Nn #1#2
4672   { \cs_set_nopar:Npx #1 { \exp_not:n {#2} \exp_not:o #1 } }
4673 \cs_new_protected:Npn \tl_put_left:NV #1#2
4674   { \cs_set_nopar:Npx #1 { \exp_not:V #2 \exp_not:o #1 } }
4675 \cs_new_protected:Npn \tl_put_left:No #1#2
4676   { \cs_set_nopar:Npx #1 { \exp_not:o {#2} \exp_not:o #1 } }
4677 \cs_new_protected:Npn \tl_put_left:Nx #1#2
4678   { \cs_set_nopar:Npx #1 { #2 \exp_not:o #1 } }
4679 \cs_new_protected:Npn \tl_gput_left:Nn #1#2
4680   { \cs_gset_nopar:Npx #1 { \exp_not:n {#2} \exp_not:o #1 } }
4681 \cs_new_protected:Npn \tl_gput_left:NV #1#2
4682   { \cs_gset_nopar:Npx #1 { \exp_not:V #2 \exp_not:o #1 } }
4683 \cs_new_protected:Npn \tl_gput_left:No #1#2
4684   { \cs_gset_nopar:Npx #1 { \exp_not:o {#2} \exp_not:o #1 } }
4685 \cs_new_protected:Npn \tl_gput_left:Nx #1#2
4686   { \cs_gset_nopar:Npx #1 { #2 \exp_not:o {#1} } }
4687 \cs_generate_variant:Nn \tl_put_left:Nn { c }
4688 \cs_generate_variant:Nn \tl_put_left:NV { c }
4689 \cs_generate_variant:Nn \tl_put_left:No { c }
4690 \cs_generate_variant:Nn \tl_put_left:Nx { c }
4691 \cs_generate_variant:Nn \tl_gput_left:Nn { c }
4692 \cs_generate_variant:Nn \tl_gput_left:NV { c }
4693 \cs_generate_variant:Nn \tl_gput_left:No { c }
4694 \cs_generate_variant:Nn \tl_gput_left:Nx { c }

(End definition for \tl_put_left:Nn and others. These functions are documented on page ??.)
```

\tl_put_right:Nn

The same on the right.

```

4695 \cs_new_protected:Npn \tl_put_right:Nn #1#2
4696   { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:n {#2} } }
4697 \cs_new_protected:Npn \tl_put_right:NV #1#2
4698   { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:V #2 } }
4699 \cs_new_protected:Npn \tl_put_right:No #1#2
4700   { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:o {#2} } }
4701 \cs_new_protected:Npn \tl_put_right:Nx #1#2

\tl_gput_right:Nn
\tl_gput_right:NV
\tl_gput_right:No
\tl_gput_right:Nx
\tl_gput_right:NV
\tl_gput_right:No
\tl_gput_right:Nx
\tl_gput_right:NV
\tl_gput_right:No
\tl_gput_right:Nx
```

```

4702 { \cs_set_nopar:Npx #1 { \exp_not:o #1 #2 } }
4703 \cs_new_protected:Npn \tl_gput_right:Nn #1#2
4704 { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:n {#2} } }
4705 \cs_new_protected:Npn \tl_gput_right:NV #1#2
4706 { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:V #2 } }
4707 \cs_new_protected:Npn \tl_gput_right:No #1#2
4708 { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:o {#2} } }
4709 \cs_new_protected:Npn \tl_gput_right:Nx #1#2
4710 { \cs_gset_nopar:Npx #1 { \exp_not:o {#1} #2 } }
4711 \cs_generate_variant:Nn \tl_put_right:Nn { c }
4712 \cs_generate_variant:Nn \tl_put_right:NV { c }
4713 \cs_generate_variant:Nn \tl_put_right:No { c }
4714 \cs_generate_variant:Nn \tl_put_right:Nx { c }
4715 \cs_generate_variant:Nn \tl_gput_right:Nn { c }
4716 \cs_generate_variant:Nn \tl_gput_right:NV { c }
4717 \cs_generate_variant:Nn \tl_gput_right:No { c }
4718 \cs_generate_variant:Nn \tl_gput_right:Nx { c }

(End definition for \tl_put_right:Nn and others. These functions are documented on page ??.)
```

10.4 Reassigning token list category codes

\c__tl_rescan_marker_tl

The rescanning code needs a special token list containing the same character with two different category codes. This is set up here, while the detail is described below.

```

4719 \group_begin:
4720   \tex_lccode:D '\A = '\@ \scan_stop:
4721   \tex_lccode:D '\B = '\@ \scan_stop:
4722   \tex_catcode:D '\A = 8 \scan_stop:
4723   \tex_catcode:D '\B = 3 \scan_stop:
4724   \tex_lowercase:D
4725   {
4726     \group_end:
4727     \tl_const:Nn \c__tl_rescan_marker_tl { A B }
4728   }
```

(End definition for \c__tl_rescan_marker_tl This variable is documented on page ??.)

\tl_set_rescan:Nnn

\tl_set_rescan:Nno

\tl_set_rescan:Nnx

\tl_set_rescan:cnn

\tl_set_rescan:cno

\tl_set_rescan:cnx

\tl_gset_rescan:Nnn

\tl_gset_rescan:Nno

\tl_gset_rescan:Nnx

\tl_gset_rescan:cnn

\tl_gset_rescan:cno

\tl_gset_rescan:cnx

 \tl_rescan:nn

_tl_set_rescan>NNnn

 __tl_rescan:w

The idea here is to deal cleanly with the problem that \scantokens treats the argument as a file, and without the correct settings a T_EX error occurs:

! File ended while scanning definition of ...

When expanding a token list this can be handled using \exp_not:N but this fails if the token list is not being expanded. So instead a delimited argument is used with an end marker which cannot appear within the token list which is scanned: two @ symbols with different category codes. The rescanned token list cannot contain the end marker, because all @ present in the token list are read with the same category code. As every character with charcode \newlinechar is replaced by the \endlinechar, and an extra \endlinechar is added at the end, we need to set both of those to -1, “unprintable”.

```

4729 \cs_new_protected:Npn \tl_set_rescan:Nnn
4730 { \_tl_set_rescan>NNnn \tl_set:Nn }
```

```

4731 \cs_new_protected_nopar:Npn \tl_gset_rescan:Nnn
4732 { __tl_set_rescan:NNnn \tl_gset:Nn }
4733 \cs_new_protected_nopar:Npn \tl_rescan:nn
4734 { __tl_set_rescan:NNnn \prg_do_nothing: \use:n }
4735 \cs_new_protected:Npn __tl_set_rescan:NNnn #1#2#3#4
4736 {
4737     \group_begin:
4738         \exp_args:No \etex_everyeof:D { \c__tl_rescan_marker_tl \exp_not:N }
4739         \tex_endlinechar:D \c_minus_one
4740         \tex_newlinechar:D \c_minus_one
4741         #3
4742         \use:x
4743         {
4744             \group_end:
4745             #1 \exp_not:N #2
4746             {
4747                 \exp_after:wN __tl_rescan:w
4748                 \exp_after:wN \prg_do_nothing:
4749                 \etex_scantokens:D {#4}
4750             }
4751         }
4752     }
4753 \use:x
4754 {
4755     \cs_new:Npn \exp_not:N __tl_rescan:w ##1
4756         \c__tl_rescan_marker_tl
4757         { \exp_not:N \exp_not:o { ##1 } }
4758     }
4759 \cs_generate_variant:Nn \tl_set_rescan:Nnn { Nno , Nnx }
4760 \cs_generate_variant:Nn \tl_set_rescan:Nnn { c , cno , cnx }
4761 \cs_generate_variant:Nn \tl_gset_rescan:Nnn { Nno , Nnx }
4762 \cs_generate_variant:Nn \tl_gset_rescan:Nnn { c , cno }

```

(End definition for `\tl_set_rescan:Nnn` and others. These functions are documented on page 90.)

10.5 Reassigning token list character codes

`\tl_to_lowercase:n` Just some names for a few primitives: we take care or wrapping the argument in braces.

```

4763 \cs_new_protected:Npn \tl_to_lowercase:n #1
4764 { \tex_lowercase:D {#1} }
4765 \cs_new_protected:Npn \tl_to_uppercase:n #1
4766 { \tex_uppercase:D {#1} }

```

(End definition for `\tl_to_lowercase:n`. This function is documented on page 91.)

10.6 Modifying token list variables

All of the replace functions are based on `__tl_replace>NNNnn`, whose arguments are: *<function>*, `\tl_(g)set:Nx`, *<tl var>*, *<search tokens>*, *<replacement tokens>*.

```
4767 \cs_new_protected_nopar:Npn \tl_replace_once:Nnn
```

```

\tl_replace_all:Nnn
\tl_replace_all:cnn
\tl_greplace_all:Nnn
\tl_greplace_all:cnn
\tl_replace_once:Nnn
\tl_replace_once:cnn
\tl_greplace_once:Nnn
\tl_greplace_once:cnn
\__tl_replace:NNNnn
    \__tl_replace:w
\__tl_replace_all:
\__tl_replace_once:
\__tl_replace_once_end:w

```

```

4768 { \__tl_replace:NNNnn \__tl_replace_once: \tl_set:Nx }
4769 \cs_new_protected_nopar:Npn \tl_greplace_once:Nnn
4770 { \__tl_replace:NNNnn \__tl_replace_once: \tl_gset:Nx }
4771 \cs_new_protected_nopar:Npn \tl_replace_all:Nnn
4772 { \__tl_replace:NNNnn \__tl_replace_all: \tl_set:Nx }
4773 \cs_new_protected_nopar:Npn \tl_greplace_all:Nnn
4774 { \__tl_replace:NNNnn \__tl_replace_all: \tl_gset:Nx }
4775 \cs_generate_variant:Nn \tl_replace_once:Nnn { c }
4776 \cs_generate_variant:Nn \tl_greplace_once:Nnn { c }
4777 \cs_generate_variant:Nn \tl_replace_all:Nnn { c }
4778 \cs_generate_variant:Nn \tl_greplace_all:Nnn { c }

```

The idea is easier to understand by considering the case of `\tl_replace_all:Nnn`. The replacement happens within an x-type expansion. We use an auxiliary function `__tl_tmp:w`, which essentially replaces the next *<search tokens>* by *<replacement tokens>*. To avoid runaway arguments, we expand something like `__tl_tmp:w <token list> \q_mark <search tokens> \q_stop`, repeating until the end. How do we detect that we have reached the last occurrence of *<search tokens>*? The last replacement is characterized by the fact that the argument of `__tl_tmp:w` contains `\q_mark`. In the code below, `__tl_replace:w` takes an argument delimited by `\q_mark`, and removes the following token. Before we reach the end, this gobbles `\q_mark \use_none_delimit_by_q_stop:w` which appear in the definition of `__tl_tmp:w`, and leaves the *<replacement tokens>*, passed to `\exp_not:n`, to be included in the x-expanding definition. At the end, the first `\q_mark` is within the argument of `__tl_tmp:w`, and `__tl_replace:w` gobbles the second `\q_mark` as well, leaving `\use_none_delimit_by_q_stop:w`, which ends the recursion cleanly.

```

4779 \cs_new_protected:Npn \__tl_replace:NNNnn #1#2#3#4#5
4780 {
4781     \tl_if_empty:nTF {#4}
4782     {
4783         \_msg_kernel_error:nnx { kernel } { empty-search-pattern }
4784         { \tl_to_str:n {#5} }
4785     }
4786     {
4787         \group_align_safe_begin:
4788         \cs_set:Npx \__tl_tmp:w ##1##2 #4
4789         {
4790             ##2
4791             \exp_not:N \q_mark
4792             \exp_not:N \use_none_delimit_by_q_stop:w
4793             \exp_not:n { \exp_not:n {#5} }
4794             ##1
4795         }
4796         \group_align_safe_end:
4797         #2 #3
4798         {
4799             \exp_after:wN #1
4800             #3 \q_mark #4 \q_stop
4801         }

```

```

4802     }
4803   }
4804 \cs_new:Npn \__tl_replace:w #1 \q_mark #2 { \exp_not:o {#1} }

```

The first argument of `__tl_tmp:w` is responsible for repeating the replacement in the case of `replace_all`, and stopping it early for `replace_once`. Note also that we build `__tl_tmp:w` within an x-expansion so that the *(replacement tokens)* can contain `#`. The second `\exp_not:o` ensures that the *(replacement tokens)* are not expanded by `\tl-(g)set:Nx`.

Now on to the difference between “once” and “all”. The `\prg_do_nothing:` and accompanying o-expansion ensure that we don’t lose braces in case the tokens between two occurrences of the *(search tokens)* form a brace group.

```

4805 \cs_new_nopar:Npn \__tl_replace_all:
4806   {
4807     \exp_after:wN \__tl_replace:w
4808     \__tl_tmp:w \__tl_replace_all: \prg_do_nothing:
4809   }
4810 \cs_new_nopar:Npn \__tl_replace_once:
4811   {
4812     \exp_after:wN \__tl_replace:w
4813     \__tl_tmp:w { \__tl_replace_once_end:w \prg_do_nothing: } \prg_do_nothing:
4814   }
4815 \cs_new:Npn \__tl_replace_once_end:w #1 \q_mark #2 \q_stop
4816   { \exp_not:o {#1} }

```

(End definition for `\tl_replace_all:Nnn` and `\tl_replace_all:cnn` These functions are documented on page ??.)

\tl_remove_once:Nn

```

\tl_remove_once:cn
\tl_gremove_once:Nn
\tl_gremove_once:cn

```

```

4817 \cs_new_protected:Npn \tl_remove_once:Nn #1#2
4818   { \tl_replace_once:Nnn #1 {#2} { } }
4819 \cs_new_protected:Npn \tl_gremove_once:Nn #1#2
4820   { \tl_greplace_once:Nnn #1 {#2} { } }
4821 \cs_generate_variant:Nn \tl_remove_once:Nn { c }
4822 \cs_generate_variant:Nn \tl_gremove_once:Nn { c }

```

(End definition for `\tl_remove_once:Nn` and `\tl_remove_once:cn` These functions are documented on page ??.)

\tl_remove_all:Nn

```

\tl_remove_all:cn
\tl_gremove_all:Nn
\tl_gremove_all:cn

```

```

4823 \cs_new_protected:Npn \tl_remove_all:Nn #1#2
4824   { \tl_replace_all:Nnn #1 {#2} { } }
4825 \cs_new_protected:Npn \tl_gremove_all:Nn #1#2
4826   { \tl_greplace_all:Nnn #1 {#2} { } }
4827 \cs_generate_variant:Nn \tl_remove_all:Nn { c }
4828 \cs_generate_variant:Nn \tl_gremove_all:Nn { c }

```

10.7 Token list conditionals

```
\tl_if_blank_p:n
\tl_if_blank_p:v
\tl_if_blank_p:o
\tl_if_blank:nTF
\tl_if_blank:VTF
\tl_if_blank:oTF
\_tl_if_blank_p>NNw
```

TeX skips spaces when reading a non-delimited arguments. Thus, a *<token list>* is blank if and only if `\use_none:n <token list>` is empty. For performance reasons, we hard-code the emptiness test done in `\tl_if_empty:n(TF)`: convert to harmless characters with `\tl_to_str:n`, and then use `\if_meaning:w \q_nil ... \q_nil`. Note that converting to a string is done after reading the delimited argument for `\use_none:n`. The similar construction `\exp_after:wN \use_none:n \tl_to_str:n {<token list>}` would fail if the token list contains the control sequence `\`, while `\escapechar` is a space or is unprintable.

```
4829 \prg_new_conditional:Npnn \tl_if_blank:n #1 { p , T , F , TF }
4830   { \_tl_if_empty_return:o { \use_none:n #1 ? } }
4831 \cs_generate_variant:Nn \tl_if_blank_p:n { V }
4832 \cs_generate_variant:Nn \tl_if_blank:nT { V }
4833 \cs_generate_variant:Nn \tl_if_blank:nF { V }
4834 \cs_generate_variant:Nn \tl_if_blank:nTF { V }
4835 \cs_generate_variant:Nn \tl_if_blank_p:n { o }
4836 \cs_generate_variant:Nn \tl_if_blank:nT { o }
4837 \cs_generate_variant:Nn \tl_if_blank:nF { o }
4838 \cs_generate_variant:Nn \tl_if_blank:nTF { o }

(End definition for \tl_remove_all:Nn and \tl_remove_all:cn These functions are documented on page ??.)
```

```
\tl_if_empty_p:N
\tl_if_empty_p:c
\tl_if_empty:NTF
\tl_if_empty:cTF
```

These functions check whether the token list in the argument is empty and execute the proper code from their argument(s).

```
4839 \prg_new_conditional:Npnn \tl_if_empty:N #1 { p , T , F , TF }
4840   {
4841     \if_meaning:w #1 \c_empty_tl
4842       \prg_return_true:
4843     \else:
4844       \prg_return_false:
4845     \fi:
4846   }
4847 \cs_generate_variant:Nn \tl_if_empty_p:N { c }
4848 \cs_generate_variant:Nn \tl_if_empty:NT { c }
4849 \cs_generate_variant:Nn \tl_if_empty:NF { c }
4850 \cs_generate_variant:Nn \tl_if_empty:NTF { c }

(End definition for \tl_if_empty:N and \tl_if_empty:c These functions are documented on page ??.)
```

```
\tl_if_empty_p:n
\tl_if_empty_p:v
\tl_if_empty:nTF
\tl_if_empty:VTF
```

It would be tempting to just use `\if_meaning:w \q_nil #1 \q_nil` as a test since this works really well. However, it fails on a token list starting with `\q_nil` of course but more troubling is the case where argument is a complete conditional such as `\if_true:` a `\else:` b `\fi:` because then `\if_true:` is used by `\if_meaning:w`, the test turns out `false`, the `\else:` executes the `false` branch, the `\fi:` ends it and the `\q_nil` at the end starts executing... A safer route is to convert the entire token list into harmless characters first and then compare that. This way the test will even accept `\q_nil` as the first token.

```
4851 \prg_new_conditional:Npnn \tl_if_empty:n #1 { p , TF , T , F }
```

```

4852 {
4853   \exp_after:wN \if_meaning:w \exp_after:wN \q_nil \tl_to_str:n {#1} \q_nil
4854     \prg_return_true:
4855   \else:
4856     \prg_return_false:
4857   \fi:
4858 }
4859 \cs_generate_variant:Nn \tl_if_empty_p:n { V }
4860 \cs_generate_variant:Nn \tl_if_empty:nTF { V }
4861 \cs_generate_variant:Nn \tl_if_empty:nT { V }
4862 \cs_generate_variant:Nn \tl_if_empty:nF { V }
(End definition for \tl_if_empty:n and \tl_if_empty:V These functions are documented on page ??.)
```

\tl_if_empty_p:o
\tl_if_empty:oTF
__tl_if_empty_return:o

The auxiliary function __tl_if_empty_return:o is for use in conditionals on token lists, which mostly reduce to testing if a given token list is empty after applying a simple function to it. The test for emptiness is based on \tl_if_empty:n(TF), but the expansion is hard-coded for efficiency, as this auxiliary function is used in many places. Note that this works because \tl_to_str:n expands tokens that follow until reading a catcode 1 (begin-group) token.

```

4863 \cs_new:Npn \__tl_if_empty_return:o #1
4864 {
4865   \exp_after:wN \if_meaning:w \exp_after:wN \q_nil
4866     \tl_to_str:n \exp_after:wN {#1} \q_nil
4867     \prg_return_true:
4868   \else:
4869     \prg_return_false:
4870   \fi:
4871 }
4872 \prg_new_conditional:Npnn \tl_if_empty:o #1 { p , TF , T , F }
4873 { \__tl_if_empty_return:o {#1} }
(End definition for \tl_if_empty:o These functions are documented on page ??.)
```

\tl_if_eq_p:NN
\tl_if_eq_p:Nc
\tl_if_eq_p:cN
\tl_if_eq_p:cc
\tl_if_eq:NNTF
\tl_if_eq:NcTF
\tl_if_eq:cNTF
\tl_if_eq:ccTF

Returns \c_true_bool if and only if the two token list variables are equal.

```

4874 \prg_new_conditional:Npnn \tl_if_eq:NN #1#2 { p , T , F , TF }
4875 {
4876   \if_meaning:w #1 #2
4877     \prg_return_true:
4878   \else:
4879     \prg_return_false:
4880   \fi:
4881 }
4882 \cs_generate_variant:Nn \tl_if_eq_p:NN { Nc , c , cc }
4883 \cs_generate_variant:Nn \tl_if_eq:NNTF { Nc , c , cc }
4884 \cs_generate_variant:Nn \tl_if_eq:NNT { Nc , c , cc }
4885 \cs_generate_variant:Nn \tl_if_eq>NNF { Nc , c , cc }
(End definition for \tl_if_eq:NN and others. These functions are documented on page ??.)
```

\tl_if_eq:nnTF

A simple store and compare routine.

\l__tl_internal_a_tl
\l__tl_internal_b_tl

```

4886 \prg_new_protected_conditional:Npnn \tl_if_eq:nn #1#2 { T , F , TF }
4887 {
4888   \group_begin:
4889     \tl_set:Nn \l__tl_internal_a_tl {#1}
4890     \tl_set:Nn \l__tl_internal_b_tl {#2}
4891     \if_meaning:w \l__tl_internal_a_tl \l__tl_internal_b_tl
4892       \group_end:
4893       \prg_return_true:
4894     \else:
4895       \group_end:
4896       \prg_return_false:
4897     \fi:
4898   }
4899   \tl_new:N \l__tl_internal_a_tl
4900   \tl_new:N \l__tl_internal_b_tl

```

(End definition for \tl_if_eq:nn This function is documented on page ??.)

\tl_if_in:NnTF See \tl_if_in:nn(TF) for further comments. Here we simply expand the token list variable and pass it to \tl_if_in:nn(TF).

```

4901 \cs_new_protected_nopar:Npn \tl_if_in:NnT { \exp_args:No \tl_if_in:NnT }
4902 \cs_new_protected_nopar:Npn \tl_if_in:NnF { \exp_args:No \tl_if_in:NnF }
4903 \cs_new_protected_nopar:Npn \tl_if_in:NnTF { \exp_args:No \tl_if_in:NnTF }
4904 \cs_generate_variant:Nn \tl_if_in:NnT { c }
4905 \cs_generate_variant:Nn \tl_if_in:NnF { c }
4906 \cs_generate_variant:Nn \tl_if_in:NnTF { c }

```

(End definition for \tl_if_in:NnTF and \tl_if_in:cnTF These functions are documented on page ??.)

\tl_if_in:nnTF Once more, the test relies on \tl_to_str:n for robustness. The function __tl_tmp:w removes tokens until the first occurrence of #2. If this does not appear in #1, then the final #2 is removed, leaving an empty token list. Otherwise some tokens remain, and the test is **false**. See \tl_if_empty:n(TF) for details on the emptiness test.

Special care is needed to treat correctly cases like \tl_if_in:nnTF {a state}{states}, where #1#2 contains #2 before the end. To cater for this case, we insert {}{} between the two token lists. This marker may not appear in #2 because of TeX limitations on what can delimit a parameter, hence we are safe. Using two brace groups makes the test work also for empty arguments.

```

4907 \prg_new_protected_conditional:Npnn \tl_if_in:nn #1#2 { T , F , TF }
4908 {
4909   \cs_set:Npn \__tl_tmp:w ##1 #2 { }
4910   \tl_if_empty:oTF { \__tl_tmp:w #1 {} {} #2 }
4911   { \prg_return_false: } { \prg_return_true: }
4912 }
4913 \cs_generate_variant:Nn \tl_if_in:nnT { V , o , no }
4914 \cs_generate_variant:Nn \tl_if_in:nnF { V , o , no }
4915 \cs_generate_variant:Nn \tl_if_in:nnTF { V , o , no }

```

(End definition for \tl_if_in:nnTF and others. These functions are documented on page ??.)

```
\tl_if_single_p:N          Expand the token list and feed it to \tl_if_single:n.
\tl_if_single:NTF
4916 \cs_new:Npn \tl_if_single_p:N { \exp_args:No \tl_if_single_p:n }
4917 \cs_new:Npn \tl_if_single:NT { \exp_args:No \tl_if_single:nT }
4918 \cs_new:Npn \tl_if_single:NF { \exp_args:No \tl_if_single:nF }
4919 \cs_new:Npn \tl_if_single:NTF { \exp_args:No \tl_if_single:nTF }
```

(End definition for \tl_if_single:N These functions are documented on page 92.)

\tl_if_single_p:n A token list has exactly one item if it is a single token or a single brace group, surrounded by optional explicit spaces. The naive version of this test would do \use_none:n #1, and test if the result is empty. However, this will fail when the token list is empty. Furthermore, it does not allow optional trailing spaces.

```
4920 \prg_new_conditional:Npnn \tl_if_single:n #1 { p , T , F , TF }
4921   { \__str_if_eq_x_return:nn { \exp_not:o { \use_none:nn #1 ?? } } {?} }
```

(End definition for \tl_if_single:n These functions are documented on page 92.)

```
\tl_case:Nnn
\tl_case:cnn
\__tl_case:Nw
\__tl_case_end:nw
4922 \cs_new:Npn \tl_case:Nnn #1#2#3
4923 {
4924   \tex_roman numeral:D
4925   \__tl_case:Nw #1 #2 #1 {#3} \q_recursion_stop
4926 }
4927 \cs_new:Npn \__tl_case:Nw #1#2#3
4928 {
4929   \tl_if_eq:NNTF #1 #2
4930   { \__tl_case_end:nw {#3} }
4931   { \__tl_case:Nw #1 }
4932 }
4933 \cs_generate_variant:Nn \tl_case:Nnn { c }
4934 \cs_new_eq:NN \__tl_case_end:nw \__prg_case_end:nw
```

(End definition for \tl_case:Nnn and \tl_case:cnn These functions are documented on page ??.)

10.8 Mapping to token lists

Expandable loop macro for token lists. These have the advantage of not needing to test if the argument is empty, because if it is, the stop marker will be read immediately and the loop terminated.

```
\__tl_map_function:Nn
\__tl_map_function:NN
\__tl_map_function:cN
\__tl_map_function:Nn
4935 \cs_new:Npn \tl_map_function:nN #1#2
4936 {
4937   \__tl_map_function:Nn #2 #1
4938   \q_recursion_tail
4939   \__prg_break_point:Nn \tl_map_break: { }
4940 }
4941 \cs_new_nopar:Npn \tl_map_function:NN
4942 { \exp_args:No \tl_map_function:nN }
4943 \cs_new:Npn \__tl_map_function:Nn #1#2
4944 {
4945   \__quark_if_recursion_tail_break:nN {#2} \tl_map_break:
4946   #1 {#2} \__tl_map_function:Nn #1
```

```

4947   }
4948 \cs_generate_variant:Nn \tl_map_function:NN { c }
(End definition for \tl_map_function:nN This function is documented on page ??.)
```

\tl_map_inline:nn
\tl_map_inline:Nn
\tl_map_inline:cn

The inline functions are straight forward by now. We use a little trick with the counter \g_prg_map_int to make them nestable. We can also make use of __tl_map_function:Nn from before.

```

4949 \cs_new_protected:Npn \tl_map_inline:nn #1#2
4950 {
4951   \int_gincr:N \g_prg_map_int
4952   \cs_gset:cpn { __prg_map_ \int_use:N \g_prg_map_int :w } ##1 {#2}
4953   \exp_args:Nc \__tl_map_function:Nn
4954   { __prg_map_ \int_use:N \g_prg_map_int :w }
4955   #1 \q_recursion_tail
4956   \__prg_break_point:Nn \tl_map_break: { \int_gdecr:N \g_prg_map_int }
4957 }
4958 \cs_new_protected:Npn \tl_map_inline:Nn
4959 { \exp_args:No \tl_map_inline:nn }
4960 \cs_generate_variant:Nn \tl_map_inline:Nn { c }
(End definition for \tl_map_inline:nn This function is documented on page ??.)
```

\tl_map_variable:nNn
\tl_map_variable>NNn

\tl_map_variable:cNn
__tl_map_variable:Nnn

\tl_map_variable:nNn *<token list>* *<temp>* *<action>* assigns *<temp>* to each element and executes *<action>*.

```

4961 \cs_new_protected:Npn \tl_map_variable:nNn #1#2#3
4962 {
4963   \__tl_map_variable:Nnn #2 {#3} #1
4964   \q_recursion_tail
4965   \__prg_break_point:Nn \tl_map_break: { }
4966 }
4967 \cs_new_protected_nopar:Npn \tl_map_variable:NNn
4968 { \exp_args:No \tl_map_variable:nNn }
4969 \cs_new_protected:Npn \__tl_map_variable:Nnn #1#2#3
4970 {
4971   \tl_set:Nn #1 {#3}
4972   \__quark_if_recursion_tail_break:NN #1 \tl_map_break:
4973   \use:n {#2}
4974   \__tl_map_variable:Nnn #1 {#2}
4975 }
4976 \cs_generate_variant:Nn \tl_map_variable:NNn { c }
(End definition for \tl_map_variable:nNn This function is documented on page ??.)
```

\tl_map_break:
\tl_map_break:n

The break statements use the general __prg_map_break:Nn.

```

4977 \cs_new_nopar:Npn \tl_map_break:
4978 { \__prg_map_break:Nn \tl_map_break: { } }
4979 \cs_new_nopar:Npn \tl_map_break:n
4980 { \__prg_map_break:Nn \tl_map_break: }
```

(End definition for \tl_map_break: This function is documented on page 94.)

10.9 Using token lists

\tl_to_str:n Another name for a primitive.

```
4981 \cs_new_eq:NN \tl_to_str:n \etex_detokenize:D
```

(End definition for **\tl_to_str:n**. This function is documented on page 94.)

\tl_to_str:N These functions return the replacement text of a token list as a string.

```
4982 \cs_new:Npn \tl_to_str:N #1 { \etex_detokenize:D \exp_after:WN {#1} }
```

```
4983 \cs_generate_variant:Nn \tl_to_str:N { c }
```

(End definition for **\tl_to_str:N** and **\tl_to_str:c**. These functions are documented on page ??.)

\tl_use:N Token lists which are simply not defined will give a clear TeX error here. No such luck for ones equal to **\scan_stop**: so instead a test is made and if there is an issue an error is forced.

```
4984 \cs_new:Npn \tl_use:N #1
```

```
4985 {
```

```
4986   \tl_if_exist:NTF #1 {#1}
```

```
4987   { \__msg_kernel_expandable_error:nnn { kernel } { bad-variable } {#1} }
```

```
4988 }
```

```
4989 \cs_generate_variant:Nn \tl_use:N { c }
```

(End definition for **\tl_use:N** and **\tl_use:c**. These functions are documented on page ??.)

10.10 Working with the contents of token lists

\tl_count:n Count number of elements within a token list or token list variable. Brace groups within the list are read as a single element. Spaces are ignored. **_tl_count:n** grabs the element and replaces it by **+1**. The **0** to ensure it works on an empty list.

\tl_count:N **\tl_count:c**

```
4990 \cs_new:Npn \tl_count:n #1
```

```
4991 {
```

```
4992   \int_eval:n
```

```
4993   { 0 \tl_map_function:nN {#1} \_tl_count:n }
```

```
4994 }
```

```
4995 \cs_new:Npn \tl_count:N #1
```

```
4996 {
```

```
4997   \int_eval:n
```

```
4998   { 0 \tl_map_function:NN #1 \_tl_count:n }
```

```
4999 }
```

```
5000 \cs_new:Npn \_tl_count:n #1 { + \c_one }
```

```
5001 \cs_generate_variant:Nn \tl_count:n { V , o }
```

```
5002 \cs_generate_variant:Nn \tl_count:N { c }
```

(End definition for **\tl_count:n**, **\tl_count:V**, and **\tl_count:o**. These functions are documented on page ??.)

\tl_reverse_items:n Reversal of a token list is done by taking one item at a time and putting it after **\q_stop**.

```
5003 \cs_new:Npn \tl_reverse_items:n #1
```

```
5004 {
```

```
5005   \_tl_reverse_items:nwNwn #1 ?
```

```
5006     \q_mark \_tl_reverse_items:nwNwn
```

```

5007     \q_mark \__tl_reverse_items:wn
5008     \q_stop { }
5009   }
5010 \cs_new:Npn \__tl_reverse_items:nwNwn #1 #2 \q_mark #3 #4 \q_stop #5
5011   {
5012     #3 #2
5013     \q_mark \__tl_reverse_items:nwNwn
5014     \q_mark \__tl_reverse_items:wn
5015     \q_stop { [#1] #5 }
5016   }
5017 \cs_new:Npn \__tl_reverse_items:wn #1 \q_stop #2
5018   { \exp_not:o { \use_none:n #2 } }

```

(End definition for `\tl_reverse_items:n`. This function is documented on page 95.)

`\tl_trim_spaces:n`
`\tl_trim_spaces:N`
`\tl_trim_spaces:c`
`\tl_gtrim_spaces:N`
`\tl_gtrim_spaces:c`

Trimming spaces from around the input is deferred to an internal function whose first argument is the token list to trim, augmented by an initial `\q_mark`, and whose second argument is a *<continuation>*, which will receive as a braced argument `\use_none:n \q_mark` (*trimmed token list*). In the case at hand, we take `\exp_not:o` as our continuation, so that space trimming will behave correctly within an x-type expansion.

```

5019 \cs_new:Npn \tl_trim_spaces:n #1
5020   { \__tl_trim_spaces:nn { \q_mark #1 } \exp_not:o }
5021 \cs_new_protected:Npn \tl_trim_spaces:N #1
5022   { \tl_set:Nx #1 { \exp_args:No \tl_trim_spaces:n {#1} } }
5023 \cs_new_protected:Npn \tl_gtrim_spaces:N #1
5024   { \tl_gset:Nx #1 { \exp_args:No \tl_trim_spaces:n {#1} } }
5025 \cs_generate_variant:Nn \tl_trim_spaces:N { c }
5026 \cs_generate_variant:Nn \tl_gtrim_spaces:N { c }

```

(End definition for `\tl_trim_spaces:n`. This function is documented on page ??.)

`__tl_trim_spaces:nn`
`__tl_trim_spaces_i:w`
`__tl_trim_spaces_ii:w__tl_trim_spaces_iii:w`
`__tl_trim_spaces_iv:w`

Trimming spaces from around the input is done using delimited arguments and quarks, and to get spaces at odd places in the definitions, we nest those in `__tl_tmp:w`, which then receives a single space as its argument: #1 is `\q_nil`. Removing leading spaces is done with `__tl_trim_spaces_i:w`, which loops until `\q_mark\q_nil` matches the end of the token list: then #1 is the token list and ##3 is `__tl_trim_spaces_ii:w`. This hands the relevant tokens to the loop `__tl_trim_spaces_iii:w`, responsible for trimming trailing spaces. The end is reached when `\q_nil` matches the one present in the definition of `\tl_trim_spaces:n`. Then `__tl_trim_spaces_iv:w` puts the token list into a group, with `\use_none:n` placed there to gobble a lingering `\q_mark`, and feeds this to the *<continuation>*.

```

5027 \cs_set:Npn \__tl_tmp:w #1
5028   {
5029     \cs_new:Npn \__tl_trim_spaces:nn ##1
5030     {
5031       \__tl_trim_spaces_i:w
5032         ##1
5033         \q_nil
5034         \q_mark #1 { }
5035         \q_mark \__tl_trim_spaces_ii:w

```

```

5036      \_tl_trim_spaces_iii:w
5037      #1 \q_nil
5038      \_tl_trim_spaces_iv:w
5039      \q_stop
5040      }
5041      \cs_new:Npn \_tl_trim_spaces_i:w ##1 \q_mark #1 ##2 \q_mark ##3
5042      {
5043      ##3
5044      \_tl_trim_spaces_i:w
5045      \q_mark
5046      ##2
5047      \q_mark #1 {##1}
5048      }
5049      \cs_new:Npn \_tl_trim_spaces_ii:w
5050      \_tl_trim_spaces_i:w \q_mark \q_mark ##1
5051      {
5052      \_tl_trim_spaces_iii:w
5053      ##1
5054      }
5055      \cs_new:Npn \_tl_trim_spaces_iii:w ##1 #1 \q_nil ##2
5056      {
5057      ##2
5058      ##1 \q_nil
5059      \_tl_trim_spaces_iii:w
5060      }
5061      \cs_new:Npn \_tl_trim_spaces_iv:w ##1 \q_nil ##2 \q_stop ##3
5062      { ##3 { \use_none:n ##1 } }
5063      }
5064      \_tl_tmp:w { ~ }
(End definition for \_tl_trim_spaces:nn This function is documented on page 100.)

```

10.11 Token by token changes

\q_tl_act_mark
\q_tl_act_stop

The \tl_act functions may be applied to any token list. Hence, we use two private quarks, to allow any token, even quarks, in the token list. Only \q_tl_act_mark and \q_tl_act_stop may not appear in the token lists manipulated by \tl_act:NNNnn functions. The quarks are effectively defined in \q_tl_act.

(End definition for \q_tl_act_mark and \q_tl_act_stop These variables are documented on page ??.)

_tl_act:NNNnn
_tl_act_output:n
_tl_act_reverse_output:n
_tl_act_loop:w
_tl_act_normal:NwnNNN
_tl_act_group:nwnNNN
_tl_act_space:wwnNNN
_tl_act_end:w

To help control the expansion, _tl_act:NNNnn should always be proceeded by \romannumeral and ends by producing \c_zero once the result has been obtained. Then loop over tokens, groups, and spaces in #5. The marker \q_tl_act_mark is used both to avoid losing outer braces and to detect the end of the token list more easily. The result is stored as an argument for the dummy function _tl_act_result:n.

```

5065 \cs_new:Npn \_tl_act:NNNnn #1#2#3#4#5
5066 {
5067     \group_align_safe_begin:
5068     \_tl_act_loop:w #5 \q\_tl_act_mark \q\_tl_act_stop

```

```

5069      {#4} #1 #2 #3
5070      \__tl_act_result:n { }
5071  }

```

In the loop, we check how the token list begins and act accordingly. In the “normal” case, we may have reached `\q__tl_act_mark`, the end of the list. Then leave `\c_zero` and the result in the input stream, to terminate the expansion of `\romannumeral`. Otherwise, apply the relevant function to the “arguments”, #3 and to the head of the token list. Then repeat the loop. The scheme is the same if the token list starts with a group or with a space. Some extra work is needed to make `__tl_act_space:wwNNN` gobble the space.

```

5072 \cs_new:Npn \__tl_act_loop:w #1 \q__tl_act_stop
5073 {
5074     \tl_if_head_is_N_type:nTF {#1}
5075         { \__tl_act_normal:NwnNNN }
5076         {
5077             \tl_if_head_is_group:nTF {#1}
5078                 { \__tl_act_group:nwnNNN }
5079                 { \__tl_act_space:wwnNNN }
5080             }
5081             #1 \q__tl_act_stop
5082         }
5083 \cs_new:Npn \__tl_act_normal:NwnNNN #1 #2 \q__tl_act_stop #3#4
5084 {
5085     \if_meaning:w \q__tl_act_mark #1
5086         \exp_after:wN \__tl_act_end:wn
5087     \fi:
5088     #4 {#3} #1
5089     \__tl_act_loop:w #2 \q__tl_act_stop
5090     {#3} #4
5091 }
5092 \cs_new:Npn \__tl_act_end:wn #1 \__tl_act_result:n #2
5093     { \group_align_safe_end: \c_zero #2 }
5094 \cs_new:Npn \__tl_act_group:nwnNNN #1 #2 \q__tl_act_stop #3#4#5
5095 {
5096     #5 {#3} {#1}
5097     \__tl_act_loop:w #2 \q__tl_act_stop
5098     {#3} #4 #5
5099 }
5100 \exp_last_unbraced:NNo
5101     \cs_new:Npn \__tl_act_space:wwnNNN \c_space_tl #1 \q__tl_act_stop #2#3#4#5
5102 {
5103     #5 {#2}
5104     \__tl_act_loop:w #1 \q__tl_act_stop
5105     {#2} #3 #4 #5
5106 }

```

Typically, the output is done to the right of what was already output, using `__tl_act_output:n`, but for the `__tl_act_reverse` functions, it should be done to the left.

```
5107 \cs_new:Npn \__tl_act_output:n #1 #2 \__tl_act_result:n #3
```

```

5108 { #2 \__tl_act_result:n { #3 #1 } }
5109 \cs_new:Npn \__tl_act_reverse_output:n #1 #2 \__tl_act_result:n #3
5110 { #2 \__tl_act_result:n { #1 #3 } }
(End definition for \__tl_act:NNNnn This function is documented on page ??.)
```

\tl_reverse:n The goal here is to reverse without losing spaces nor braces. This is done using the general internal function `__tl_act:NNNnn`. Spaces and “normal” tokens are output on the left of the current output. Grouped tokens are output to the left but without any reversal within the group. All of the internal functions here drop one argument: this is needed by `__tl_act:NNNnn` when changing case (to record which direction the change is in), but not when reversing the tokens.

```

5111 \cs_new:Npn \tl_reverse:n #1
5112 {
5113   \etex_unexpanded:D \exp_after:wN
5114   {
5115     \tex_roman numeral:D
5116     \__tl_act:NNNnn
5117     \__tl_reverse_normal:nN
5118     \__tl_reverse_group_preserve:nn
5119     \__tl_reverse_space:n
5120     {
5121       {#1}
5122     }
5123   }
5124 \cs_generate_variant:Nn \tl_reverse:n { o , V }
5125 \cs_new:Npn \__tl_reverse_normal:nN #1#2
5126 { \__tl_act_reverse_output:n {#2} }
5127 \cs_new:Npn \__tl_reverse_group_preserve:nn #1#2
5128 { \__tl_act_reverse_output:n { {#2} } }
5129 \cs_new:Npn \__tl_reverse_space:n #1
5130 { \__tl_act_reverse_output:n { ~ } }
(End definition for \tl_reverse:n, \tl_reverse:o, and \tl_reverse:V These functions are documented on page ??.)
```

\tl_reverse:N This reverses the list, leaving `\exp_stop_f:` in front, which stops the f-expansion.

```

5131 \cs_new_protected:Npn \tl_reverse:N #1
5132 { \tl_set:Nx #1 { \exp_args:No \tl_reverse:n { #1 } } }
5133 \cs_new_protected:Npn \tl_greverse:N #1
5134 { \tl_gset:Nx #1 { \exp_args:No \tl_reverse:n { #1 } } }
5135 \cs_generate_variant:Nn \tl_reverse:N { c }
5136 \cs_generate_variant:Nn \tl_greverse:N { c }
(End definition for \tl_reverse:N and others. These functions are documented on page ??.)
```

10.12 The first token from a token list

Finding the head of a token list expandably will always strip braces, which is fine as this is consistent with for example mapping to a list. The empty brace groups in `\tl_head:n` ensure that a blank argument gives an empty result. The result is returned

```

\__tl_head_i:nw
\__tl_head_ii:nw
\__tl_head:w
\__tl_tail:N
\__tl_tail:n
\__tl_tail:V
\__tl_tail:v
\__tl_tail:f
```

within the `\unexpanded` primitive. The approach here is to use `\if_false:` to allow us to use } as the closing delimiter: this is the only safe choice, as any other token would not be able to parse its own code. Using a marker, we can see if what we are grabbing is exactly the marker, or there is anything else to deal with. Is there is, there is a loop. If not, tidy up and leave the item in the output stream. More detail in <http://tex.stackexchange.com/a/70168>.

```

5137 \cs_new:Npn \tl_head:n #1
5138 {
5139   \etex_unexpanded:D
5140     \if_false: { \fi: \__tl_head_i:nw #1 { } \q_stop }
5141   }
5142 \cs_new:Npn \__tl_head_i:nw #1#2 \q_stop
5143   { \exp_after:wN \__tl_head_i:nw \exp_after:wN { \if_false: } \fi: {#1} }
5144 \cs_new:Npn \__tl_head_i:nw #1
5145   {
5146     \exp_after:wN \if_meaning:w \exp_after:wN \q_nil
5147       \tl_to_str:n \exp_after:wN { \use_none:n #1 } \q_nil
5148       \exp_after:wN \use_i:nn
5149     \else:
5150       \exp_after:wN \use_i:nn
5151     \fi:
5152       {#1}
5153       { \if_false: { \fi: \__tl_head_i:nw #1 } }
5154   }
5155 \cs_generate_variant:Nn \tl_head:n { V , v , f }
5156 \cs_new:Npn \tl_head:w #1#2 \q_stop {#1}
5157 \cs_new_nopar:Npn \tl_head:N { \exp_args:No \tl_head:n }
```

To correctly leave the tail of a token list, it's important *not* to absorb any of the tail part as an argument. For example, the simple definition

```

\cs_new:Npn \tl_tail:n #1 { \tl_tail:w #1 \q_stop }
\cs_new:Npn \tl_tail:w #1#2 \q_stop
```

will give the wrong result for `\tl_tail:n { a { bc } }` (the braces will be stripped). Thus the only safe way to proceed is to first check that there is an item to grab (*i.e.* that the argument is not blank) and assuming there is to dispose of the first item. As with `\tl_head:n`, the result is protected from further expansion by `\etex_unexpanded:D`. While we could optimise the test here, this would leave some tokens “banned” in the input, which we do not have with this definition.

```

5158 \cs_new:Npn \tl_tail:n #1
5159 {
5160   \etex_unexpanded:D
5161   \tl_if_blank:nTF {#1}
5162     { { } }
5163     { \exp_after:wN { \use_none:n #1 } }
5164   }
5165 \cs_generate_variant:Nn \tl_tail:n { V , v , f }
5166 \cs_new_nopar:Npn \tl_tail:N { \exp_args:No \tl_tail:n }
```

(End definition for `\tl_head:N` and others. These functions are documented on page ??.)

`\str_head:n` After `\tl_to_str:n`, we have a list of character tokens, all with category code 12, except the space, which has category code 10. Directly using `\tl_head:w` would thus lose leading spaces. Instead, we take an argument delimited by an explicit space, and then only use `\tl_head:w`. If the string started with a space, then the argument of `_str_head:w` is empty, and the function correctly returns a space character. Otherwise, it returns the first token of #1, which is the first token of the string. If the string is empty, we return an empty result.

To remove the first character of `\tl_to_str:n {#1}`, we test it using `\if_charcode:w \scan_stop:`, always `false` for characters. If the argument was non-empty, then `_str_tail:w` returns everything until the first X (with category code letter, no risk of confusing with the user input). If the argument was empty, the first X is taken by `\if_charcode:w`, and nothing is returned. We use X as a `<marker>`, rather than a quark because the test `\if_charcode:w \scan_stop: <marker>` has to be `false`.

```

5167 \cs_new:Npn \str_head:n #1
5168 {
5169   \exp_after:wN \_str_head:w
5170   \tl_to_str:n {#1}
5171   { { } } ~ \q_stop
5172 }
5173 \cs_new:Npn \_str_head:w #1 ~ %
5174 { \tl_head:w #1 { ~ } }
5175 \cs_new:Npn \str_tail:n #1
5176 {
5177   \exp_after:wN \_str_tail:w
5178   \reverse_if:N \if_charcode:w
5179     \scan_stop: \tl_to_str:n {#1} X X \q_stop
5180 }
5181 \cs_new:Npn \_str_tail:w #1 X #2 \q_stop { \fi: #1 }
```

(End definition for `\str_head:n` and `\str_tail:n`. These functions are documented on page 97.)

`\tl_if_head_eq_meaning_p:nN`
`\tl_if_head_eq_meaning:nNTF`
`\tl_if_head_eq_charcode_p:nN`
`\tl_if_head_eq_charcode:nNTF`
`\tl_if_head_eq_charcode_p:fN`
`\tl_if_head_eq_charcode:fNTF`

Accessing the first token of a token list is tricky in three cases: when it has category code 1 (begin-group token), when it is an explicit space, with category code 10 and character code 32, or when the token list is empty (obviously).

Forgetting temporarily about this issue we would use the following test in `\tl_if_head_eq_charcode:nN`. Here, `\tl_head:w` yields the first token of the token list, then passed to `\exp_not:N`.

```
\if_charcode:w
  \exp_after:wN \exp_not:N \tl_head:w #1 \q_nil \q_stop
  \exp_not:N #2
```

The two first special cases are detected by testing if the token list starts with an N-type token (the extra ? sends empty token lists to the `true` branch of this test). In those cases, the first token is a character, and since we only care about its character code, we can use `\str_head:n` to access it (this works even if it is a space character). An empty argument:w will result in `\tl_head:w` leaving two tokens: ? which is taken in the `\if_charcode:w`

test, and `\use_none:nn`, which ensures that `\prg_return_false:` is returned regardless of whether the charcode test was `true` or `false`.

```

5182 \prg_new_conditional:Npnn \tl_if_head_eq_charcode:nN #1#2 { p , T , F , TF }
5183 {
5184   \if_charcode:w
5185     \exp_not:N #2
5186     \tl_if_head_is_N_type:nTF { #1 ? }
5187     {
5188       \exp_after:wN \exp_not:N
5189       \tl_head:w #1 { ? \use_none:nn } \q_stop
5190     }
5191     { \str_head:n {#1} }
5192     \prg_return_true:
5193   \else:
5194     \prg_return_false:
5195   \fi:
5196 }
5197 \cs_generate_variant:Nn \tl_if_head_eq_charcode_p:nN { f }
5198 \cs_generate_variant:Nn \tl_if_head_eq_charcode:nNTF { f }
5199 \cs_generate_variant:Nn \tl_if_head_eq_charcode:nNT { f }
5200 \cs_generate_variant:Nn \tl_if_head_eq_charcode:nNF { f }

```

For `\tl_if_head_eq_catcode:nN`, again we detect special cases with a `\tl_if_head_is_N_type:n`. Then we need to test if the first token is a begin-group token or an explicit space token, and produce the relevant token, either `\c_group_begin_token` or `\c_space_token`. Again, for an empty argument, a hack is used, removing `\prg_return_true:` and `\else:` with `\use_none:nn` in case the catcode test with the (arbitrarily chosen) `? is true.`

```

5201 \prg_new_conditional:Npnn \tl_if_head_eq_catcode:nN #1 #2 { p , T , F , TF }
5202 {
5203   \if_catcode:w
5204     \exp_not:N #2
5205     \tl_if_head_is_N_type:nTF { #1 ? }
5206     {
5207       \exp_after:wN \exp_not:N
5208       \tl_head:w #1 { ? \use_none:nn } \q_stop
5209     }
5210     {
5211       \tl_if_head_is_group:nTF {#1}
5212       { \c_group_begin_token }
5213       { \c_space_token }
5214     }
5215     \prg_return_true:
5216   \else:
5217     \prg_return_false:
5218   \fi:
5219 }

```

For `\tl_if_head_eq_meaning:nN`, again, detect special cases. In the normal case, use `\tl_head:w`, with no `\exp_not:N` this time, since `\if_meaning:w` causes no expansion.

With an empty argument, the test is `true`, and `\use_none:nnn` removes #2 and the usual `\prg_return_true:` and `\else:`. In the special cases, we know that the first token is a character, hence `\if_charcode:w` and `\if_catcode:w` together are enough. We combine them in some order, hopefully faster than the reverse. Tests are not nested because the arguments may contain unmatched primitive conditionals.

```

5220 \prg_new_conditional:Npnn \tl_if_head_eq_meaning:nN #1#2 { p , T , F , TF }
5221 {
5222     \tl_if_head_is_N_type:nTF { #1 ? }
5223     { \__tl_if_head_eq_meaning_normal:nN }
5224     { \__tl_if_head_eq_meaning_special:nN }
5225     {#1} #2
5226 }
5227 \cs_new:Npn \__tl_if_head_eq_meaning_normal:nN #1 #2
5228 {
5229     \exp_after:wN \if_meaning:w
5230         \tl_head:w #1 { ?? \use_none:nnn } \q_stop #2
5231         \prg_return_true:
5232     \else:
5233         \prg_return_false:
5234     \fi:
5235 }
5236 \cs_new:Npn \__tl_if_head_eq_meaning_special:nN #1 #2
5237 {
5238     \if_charcode:w \str_head:n {#1} \exp_not:N #2
5239         \exp_after:wN \use:n
5240     \else:
5241         \prg_return_false:
5242         \exp_after:wN \use_none:n
5243     \fi:
5244 {
5245     \if_catcode:w \exp_not:N #2
5246         \tl_if_head_is_group:nTF {#1}
5247             { \c_group_begin_token }
5248             { \c_space_token }
5249         \prg_return_true:
5250     \else:
5251         \prg_return_false:
5252     \fi:
5253 }
5254 }
```

(End definition for `\tl_if_head_eq_meaning:nN` These functions are documented on page 97.)

`\tl_if_head_is_N_type:p:n`
`\tl_if_head_is_N_type:nTF`

The first token of a token list can be either an N-type argument, a begin-group token (catcode 1), or an explicit space token (catcode 10 and charcode 32). The latter two cases are characterized by the fact that `\use:n` removes some tokens from #1, hence changing its string representation (no token can have an empty string representation). The extra brace group covers the case of an empty argument, whose head is not “normal”.

```
5255 \prg_new_conditional:Npnn \tl_if_head_is_N_type:n #1 { p , T , F , TF }
```

```

5256   {
5257     \__str_if_eq_x_return:nn
5258     { \exp_not:o { \use:n #1 { } } }
5259     { \exp_not:n { #1 { } } }
5260   }

```

(End definition for `\tl_if_head_is_N_type:n` These functions are documented on page 98.)

`\tl_if_head_is_group_p:n` Pass the first token of #1 through `\token_to_str:N`, then check for the brace balance.
`\tl_if_head_is_group:nTF` The extra ? caters for an empty argument.⁵

```

5261 \prg_new_conditional:Npnn \tl_if_head_is_group:n #1 { p , T , F , TF }
5262   {
5263     \if_catcode:w *
5264       \exp_after:wN \use_none:n
5265       \exp_after:wN {
5266         \exp_after:wN {
5267           \token_to_str:N #1 ?
5268         }
5269       }
5270     *
5271     \prg_return_false:
5272   \else:
5273     \prg_return_true:
5274   \fi:
5275 }

```

(End definition for `\tl_if_head_is_group:n` These functions are documented on page 98.)

`\tl_if_head_is_space_p:n` If the first token of the token list is an explicit space, i.e., a character token with character code 32 and category code 10, then this test will be `true`. It is `false` if the token list is empty, if the first token is an implicit space token, such as `\c_space_token`, or any token other than an explicit space. The slightly convoluted approach with `\romannumeral` ensures that each expansion step gives a balanced token list.
`\tl_if_head_is_space:nTF`
`__tl_if_head_is_space:w`

```

5276 \prg_new_conditional:Npnn \tl_if_head_is_space:n #1 { p , T , F , TF }
5277   {
5278     \tex_romannumeral:D \if_false: { \fi:
5279       \__tl_if_head_is_space:w ? #1 ? ~ }
5280   }
5281 \cs_new:Npn \__tl_if_head_is_space:w #1 ~
5282   {
5283     \tl_if_empty:oTF { \use_none:n #1 }
5284     { \exp_after:wN \c_zero \exp_after:wN \prg_return_true: }
5285     { \exp_after:wN \c_zero \exp_after:wN \prg_return_false: }
5286     \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:
5287   }

```

(End definition for `\tl_if_head_is_space:n` These functions are documented on page 98.)

⁵Bruno: this could be made faster, but we don't: if we hope to ever have an e-type argument, we need all brace "tricks" to happen in one step of expansion, keeping the token list brace balanced at all times.

10.13 Viewing token lists

\tl_show:N Showing token list variables is done after checking that the variable is defined (see __-
\tl_show:c `kernel_register_show:N.`

```
5288 \cs_new_protected:Npn \tl_show:N #1
5289 {
5290     \cs_if_exist:NTF #1
5291     { \cs_show:N #1 }
5292     {
5293         \__msg_kernel_error:n { kernel } { variable-not-defined }
5294         { \token_to_str:N #1 }
5295     }
5296 }
5297 \cs_generate_variant:Nn \tl_show:N { c }
```

(End definition for \tl_show:N and \tl_show:c These functions are documented on page ??.)

\tl_show:n The __msg_show_variable:n internal function performs line-wrapping, removes a leading >_L, then shows the result using the \etex_showtokens:D primitive. Since \tl_to_str:n is expanded within the line-wrapping code, the escape character is always a backslash.

```
5298 \cs_new_protected:Npn \tl_show:n #1
5299 { \__msg_show_variable:n { > ~ \tl_to_str:n {#1} } }
```

(End definition for \tl_show:n This function is documented on page 99.)

10.14 Scratch token lists

\g_tmpa_tl Global temporary token list variables. They are supposed to be set and used immediately, with no delay between the definition and the use because you can't count on other macros not to redefine them from under you.

```
5300 \tl_new:N \g_tmpa_tl
5301 \tl_new:N \g_tmpb_tl
```

(End definition for \g_tmpa_tl and \g_tmpb_tl These variables are documented on page 99.)

\l_tmpa_tl These are local temporary token list variables. Be sure not to assume that the value you put into them will survive for long—see discussion above.

```
5302 \tl_new:N \l_tmpa_tl
5303 \tl_new:N \l_tmpb_tl
```

(End definition for \l_tmpa_tl and \l_tmpb_tl These variables are documented on page 99.)

10.15 Deprecated functions

\tl_new:Nn Use either \tl_const:Nn or \tl_new:N.

```
5304 {*deprecated}
5305 \cs_new_protected:Npn \tl_new:Nn #1#2
5306 {
5307     \tl_new:N #1
5308     \tl_gset:Nn #1 {#2}
```

```

5309   }
5310 \cs_generate_variant:Nn \tl_new:Nn { c }
5311 \cs_generate_variant:Nn \tl_new:Nn { Nx }
5312 </deprecated>
(End definition for \tl_new:Nn, \tl_new:cn, and \tl_new:Nx These functions are documented on page ??.)

```

\tl_gset:Nc This was useful once, but nowadays does not make much sense.

```

\tl_set:Nc <*deprecated>
5314 \cs_new_protected_nopar:Npn \tl_gset:Nc
5315 { \tex_global:D \tl_set:Nc }
5316 \cs_new_protected:Npn \tl_set:Nc #1#2
5317 { \tl_set:No #1 { \cs:w #2 \cs_end: } }
5318 </deprecated>
(End definition for \tl_gset:Nc This function is documented on page ??.)

```

These are renamed.

```

\tl_replace_in:Nnn <*deprecated>
5320 \cs_new_eq:NN \tl_replace_in:Nnn \tl_replace_once:Nnn
5321 \cs_new_eq:NN \tl_replace_in:cnn \tl_replace_once:cnn
5322 \cs_new_eq:NN \tl_greplace_in:Nnn \tl_greplace_once:Nnn
5323 \cs_new_eq:NN \tl_greplace_in:cnn \tl_greplace_once:cnn
5324 \cs_new_eq:NN \tl_replace_all_in:Nnn \tl_replace_all:Nnn
5325 \cs_new_eq:NN \tl_replace_all_in:cnn \tl_replace_all:cnn
5326 \cs_new_eq:NN \tl_greplace_all_in:Nnn \tl_greplace_all:Nnn
5327 \cs_new_eq:NN \tl_greplace_all_in:cnn \tl_greplace_all:cnn
5328 </deprecated>
(End definition for \tl_replace_in:Nnn and \tl_replace_in:cnn These functions are documented on page ??.)

```

Also renamed.

```

\tl_remove_in:Nn <*deprecated>
5329 \cs_new_eq:NN \tl_remove_in:Nn \tl_remove_once:Nn
5330 \cs_new_eq:NN \tl_remove_in:cn \tl_remove_once:cn
5331 \cs_new_eq:NN \tl_gremove_in:Nn \tl_gremove_once:Nn
5332 \cs_new_eq:NN \tl_gremove_in:cn \tl_gremove_once:cn
5333 \cs_new_eq:NN \tl_gremove_all_in:Nn \tl_gremove_all:Nn
5334 \cs_new_eq:NN \tl_gremove_all_in:cn \tl_gremove_all:cn
5335 \cs_new_eq:NN \tl_gremove_all_in:Nn \tl_gremove_all:Nn
5336 \cs_new_eq:NN \tl_gremove_all_in:cn \tl_gremove_all:cn
5337 \cs_new_eq:NN \tl_gremove_all_in:cn \tl_gremove_all:cn
5338 </deprecated>
(End definition for \tl_remove_in:Nn and \tl_remove_in:cn These functions are documented on page ??.)

```

\tl_elt_count:n Another renaming job.

```

\tl_elt_count:V <*deprecated>
5339 \cs_new_eq:NN \tl_elt_count:n \tl_count:n
5340 \cs_new_eq:NN \tl_elt_count:V \tl_count:V
5341 \cs_new_eq:NN \tl_elt_count:o \tl_count:o
5342 \cs_new_eq:NN \tl_elt_count:c \tl_count:c

```

```

5343 \cs_new_eq:NN \tl_elt_count:N \tl_count:N
5344 \cs_new_eq:NN \tl_elt_count:c \tl_count:c
5345 ⟨/deprecated⟩
(End definition for \tl_elt_count:n, \tl_elt_count:v, and \tl_elt_count:o These functions are documented on page ??.)
```

\tl_head_i:n Two renames, and a few that are rather too specialised.

```

5346 /*deprecated*/
5347 \cs_new_eq:NN \tl_head_i:n \tl_head:n
5348 \cs_new_eq:NN \tl_head_i:w \tl_head:w
5349 \cs_new:Npn \tl_head_iii:n #1 { \tl_head_iii:w #1 \q_stop }
5350 \cs_generate_variant:Nn \tl_head_iii:n { f }
5351 \cs_new:Npn \tl_head_iii:w #1#2#3#4 \q_stop {#1#2#3}
5352 ⟨/deprecated⟩
(End definition for \tl_head_i:n This function is documented on page ??.)
```

Deprecated on 2012-05-13 for removal by 2012-08-31.

\tl_length_tokens:n

```

5353 \cs_new_eq:NN \tl_length_tokens:n \tl_count_tokens:n
(End definition for \tl_length_tokens:n This function is documented on page ??.)
```

Deprecated 2012-05-13 for removal by 2012-11-31.

\tl_length:N Renames.

```

5354 \cs_new_eq:NN \tl_length:N \tl_count:N
5355 \cs_new_eq:NN \tl_length:c \tl_count:c
5356 \cs_new_eq:NN \tl_length:n \tl_count:n
5357 \cs_new_eq:NN \tl_length:V \tl_count:V
5358 \cs_new_eq:NN \tl_length:o \tl_count:o
(End definition for \tl_length:N and others. These functions are documented on page ??.)
```

Deprecated 2012-06-05 for removal after 2012-12-31.

\tl_if_empty_p:x
\tl_if_empty:xTF

We can test expandably the emptiness of an expanded token list thanks to the primitive \pdfstrcmp which expands its argument: a token list is empty if and only if its string representation is empty.

```

5359 \prg_new_conditional:Npnn \tl_if_empty:x #1 { p , T , F , TF }
5360 { \__str_if_eq_x_return:nn { } {#1} }
(End definition for \tl_if_empty:x These functions are documented on page ??.)
```

Deprecated 2012-07-08 for removal after 2012-10-31.

\tl_if_head_group_p:n
\tl_if_head_group:nTF
\tl_if_head_N_type_p:n
\tl_if_head_N_type:nTF
\tl_if_head_space_p:n
\tl_if_head_space:nTF

```

5361 \prg_new_eq_conditional:NNn \tl_if_head_group:n \tl_if_head_is_group:n
5362 { p , T , F , TF }
5363 \prg_new_eq_conditional:NNn \tl_if_head_N_type:n \tl_if_head_is_N_type:n
5364 { p , T , F , TF }
5365 \prg_new_eq_conditional:NNn \tl_if_head_space:n \tl_if_head_is_space:n
5366 { p , T , F , TF }
(End definition for \tl_if_head_group:n These functions are documented on page ??.)
```

`\tl_tail:w` Deprecated 2012-09-01 for removal after 2012-12-31. This is broken as it will strip braces from a case such as `a{bc}`.

```
5367 \cs_new:Npn \tl_tail:w #1#2 \q_stop {#2}
(End definition for \tl_tail:w This function is documented on page ??.)
5368 ⟨/initex | package⟩
```

11 l3seq implementation

The following test files are used for this code: `m3seq002,m3seq003`.

```
5369 ⟨*initex | package⟩
5370 ⟨@=seq⟩
5371 ⟨*package⟩
5372 \ProvidesExplPackage
5373   {\ExplFileName}{\ExplFileVersion}{\ExplFileDescription}
5374 \_expl_package_check:
5375 ⟨/package⟩
```

A sequence is a control sequence whose top-level expansion is of the form “`__seq_item:n {⟨item1n”. An earlier implementation used the structure “\seq_elt:w ⟨item1n”. This allows rapid searching using a delimited function, but is not suitable for items containing {, } and # tokens, and also leads to the loss of surrounding braces around items.`

`__seq_item:n` The delimiter is always defined, but when used incorrectly simply removes its argument and hits an undefined control sequence to raise an error.

```
5376 \cs_new:Npn \__seq_item:n
5377 {
5378   \__msg_kernel_expandable_error:nn { kernel } { misused-sequence }
5379   \use_none:n
5380 }
(End definition for \__seq_item:n)
```

`\l__seq_internal_a_tl` Scratch space for various internal uses.

`\l__seq_internal_b_tl` `\tl_new:N \l__seq_internal_a_tl`

```
5381 \tl_new:N \l__seq_internal_a_tl
5382 \tl_new:N \l__seq_internal_b_tl
(End definition for \l__seq_internal_a_tl and \l__seq_internal_b_tl These variables are documented on page ??.)
```

`\c_empty_seq` Simply copy the empty token list.

```
5383 \cs_new_eq:NN \c_empty_seq \c_empty_tl
(End definition for \c_empty_seq This variable is documented on page 108.)
```

11.1 Allocation and initialisation

\seq_new:N Internally, sequences are just token lists.
\seq_new:c

```
5384 \cs_new_eq:NN \seq_new:N \tl_new:N
5385 \cs_new_eq:NN \seq_new:c \tl_new:c
```

(End definition for \seq_new:N and \seq_new:c These functions are documented on page ??.)

\seq_clear:N Clearing sequences is just the same as clearing token lists.
\seq_clear:c

```
5386 \cs_new_eq:NN \seq_clear:N \tl_clear:N
5387 \cs_new_eq:NN \seq_clear:c \tl_clear:c
5388 \cs_new_eq:NN \seq_gclear:N \tl_gclear:N
5389 \cs_new_eq:NN \seq_gclear:c \tl_gclear:c
```

(End definition for \seq_clear:N and \seq_clear:c These functions are documented on page ??.)

\seq_clear_new:N Once again a copy from the token list functions.
\seq_clear_new:c

```
5390 \cs_new_eq:NN \seq_clear_new:N \tl_clear_new:N
5391 \cs_new_eq:NN \seq_clear_new:c \tl_clear_new:c
5392 \cs_new_eq:NN \seq_gclear_new:N \tl_gclear_new:N
5393 \cs_new_eq:NN \seq_gclear_new:c \tl_gclear_new:c
```

(End definition for \seq_clear_new:N and \seq_clear_new:c These functions are documented on page ??.)

\seq_set_eq:NN Once again, these are simple copies from the token list functions.
\seq_set_eq:cN
\seq_set_eq:Nc
\seq_set_eq:cc
\seq_gset_eq:NN
\seq_gset_eq:cN
\seq_gset_eq:Nc
\seq_gset_eq:cc

```
5394 \cs_new_eq:NN \seq_set_eq:NN \tl_set_eq:NN
5395 \cs_new_eq:NN \seq_set_eq:Nc \tl_set_eq:Nc
5396 \cs_new_eq:NN \seq_set_eq:cc \tl_set_eq:cc
5397 \cs_new_eq:NN \seq_set_eq:cc \tl_set_eq:cc
5398 \cs_new_eq:NN \seq_gset_eq:NN \tl_gset_eq:NN
5399 \cs_new_eq:NN \seq_gset_eq:Nc \tl_gset_eq:Nc
5400 \cs_new_eq:NN \seq_gset_eq:cc \tl_gset_eq:cc
5401 \cs_new_eq:NN \seq_gset_eq:cc \tl_gset_eq:cc
```

(End definition for \seq_set_eq:NN and others. These functions are documented on page ??.)

\seq_set_split:Nnn The goal is to split a given token list at a marker, strip spaces from each item, and remove one set of outer braces if after removing leading and trailing spaces the item is enclosed within braces. After \tl_replace_all:Nnn, the token list \l_seq_internal_a_tl is a repetition of the pattern \seq_set_split_i:w \prg_do_nothing: <item with spaces> \seq_set_split_end:. Then, x-expansion causes \seq_set_split_i:w to trim spaces, and leaves its result as \seq_set_split_ii:w <trimmed item> \seq_set_split_end:. This is then converted to the l3seq internal structure by another x-expansion. In the first step, we insert \prg_do_nothing: to avoid losing braces too early: that would cause space trimming to act within those lost braces. The second step is solely there to strip braces which are outermost after space trimming.
\seq_set_split:NnV
\seq_gset_split:Nnn
\seq_gset_split:NnV
_seq_set_split:Nnnn
_seq_set_split_i:w
_seq_set_split_ii:w
_seq_set_split_end:

```
5402 \cs_new_protected_nopar:Npn \seq_set_split:Nnn
5403 { \seq_set_split>NNnn \tl_set:Nx }
5404 \cs_new_protected_nopar:Npn \seq_gset_split:Nnn
5405 { \seq_set_split>NNnn \tl_gset:Nx }
5406 \cs_new_protected:Npn \seq_set_split>NNnn #1 #2 #3 #4
```

```

5407  {
5408    \tl_if_empty:nTF {#3}
5409      { #1 #2 { \tl_map_function:nN {#4} \__seq_wrap_item:n } }
5410      {
5411        \tl_set:Nn \l__seq_internal_a_tl
5412        {
5413          \__seq_set_split_i:w \prg_do_nothing:
5414          #4
5415          \__seq_set_split_end:
5416        }
5417        \tl_replace_all:Nnn \l__seq_internal_a_tl { #3 }
5418        {
5419          \__seq_set_split_end:
5420          \__seq_set_split_i:w \prg_do_nothing:
5421        }
5422        \tl_set:Nx \l__seq_internal_a_tl { \l__seq_internal_a_tl }
5423        #1 #2 { \l__seq_internal_a_tl }
5424      }
5425    }
5426  \cs_new:Npn \__seq_set_split_i:w #1 \__seq_set_split_end:
5427  {
5428    \exp_not:N \__seq_set_split_ii:w
5429    \exp_args:No \tl_trim_spaces:n {#1}
5430    \exp_not:N \__seq_set_split_end:
5431  }
5432  \cs_new:Npn \__seq_set_split_ii:w #1 \__seq_set_split_end:
5433  {
5434    \__seq_wrap_item:n {#1} }
5435  \cs_generate_variant:Nn \seq_set_split:Nnn { NnV }
5435  \cs_generate_variant:Nn \seq_gset_split:Nnn { NnV }

(End definition for \seq_set_split:Nnn and others. These functions are documented on page ??.)
```

\seq_concat:NNN

\seq_concat:ccc

\seq_gconcat:NNN

\seq_gconcat:ccc

Concatenating sequences is easy.

```

5436  \cs_new_protected:Npn \seq_concat:NNN #1#2#3
5437  { \tl_set:Nx #1 { \exp_not:o {#2} \exp_not:o {#3} } }
5438  \cs_new_protected:Npn \seq_gconcat:NNN #1#2#3
5439  { \tl_gset:Nx #1 { \exp_not:o {#2} \exp_not:o {#3} } }
5440  \cs_generate_variant:Nn \seq_concat:NNN { ccc }
5441  \cs_generate_variant:Nn \seq_gconcat:NNN { ccc }

(End definition for \seq_concat:NNN and \seq_gconcat:ccc These functions are documented on page ??.)
```

\seq_if_exist_p:N

\seq_if_exist_p:c

\seq_if_exist:NTF

\seq_if_exist:cTF

Copies of the cs functions defined in l3basics.

```

5442  \cs_new_eq:NN \seq_if_exist:NTF \cs_if_exist:NTF
5443  \cs_new_eq:NN \seq_if_exist:NT \cs_if_exist:NT
5444  \cs_new_eq:NN \seq_if_exist:NF \cs_if_exist:NF
5445  \cs_new_eq:NN \seq_if_exist_p:N \cs_if_exist_p:N
5446  \cs_new_eq:NN \seq_if_exist:cTF \cs_if_exist:cTF
5447  \cs_new_eq:NN \seq_if_exist:cT \cs_if_exist:cT
5448  \cs_new_eq:NN \seq_if_exist:cF \cs_if_exist:cF
5449  \cs_new_eq:NN \seq_if_exist_p:c \cs_if_exist_p:c
```

(End definition for `\seq_if_exist:N` and `\seq_if_exist:c` These functions are documented on page ??.)

11.2 Appending data to either end

`\seq_put_left:Nn`

```
\seq_put_left:NV
\seq_put_left:Nv
\seq_put_left:No
\seq_put_left:Nx
\seq_put_left:cn
\seq_put_left:cV
\seq_put_left:cv
\seq_put_left:co
\seq_put_left:cx
```

(End definition for `\seq_put_left:Nn` and others. These functions are documented on page ??.)

`\seq_gput_right:Nn`

```
\seq_gput_right:NV
\seq_gput_right:Nv
\seq_gput_right:No
\seq_gput_right:Nx
\seq_gput_right:cn
\seq_gput_right:cV
\seq_gput_right:cv
\seq_gput_right:co
\seq_gput_right:cx
```

(End definition for `\seq_gput_left:Nn` and others. These functions are documented on page ??.)

`\seq_gput_right:Nn`

```
\seq_gput_right:NV
\seq_gput_right:Nv
\seq_gput_right:No
\seq_gput_right:Nx
\seq_gput_right:cn
\seq_gput_right:cV
\seq_gput_right:cv
\seq_gput_right:co
\seq_gput_right:cx
```

`\seq_remove_duplicates:N`

```
\seq_remove_duplicates:c
\seq_gremove_duplicates:N
\seq_gremove_duplicates:c
\__seq_remove_duplicates>NN
```

Removing duplicates means making a new list then copying it.

```
5468 \cs_new_protected:Npn \seq_remove_duplicates:N
5469   { \__seq_remove_duplicates:NN \seq_set_eq:NN }
5470 \cs_new_protected:Npn \seq_gremove_duplicates:N
5471   { \__seq_remove_duplicates:NN \seq_gset_eq:NN }
5472 \cs_new_protected:Npn \__seq_remove_duplicates>NN #1#2
5473   {
5474     \seq_clear:N \l__seq_remove_seq
5475     \seq_map_inline:Nn #2
5476   {
5477     \seq_if_in:NnF \l__seq_remove_seq {##1}
```

```

5478     { \seq_put_right:Nn \l__seq_remove_seq {##1} }
5479   }
5480   #1 #2 \l__seq_remove_seq
5481 }
5482 \cs_generate_variant:Nn \seq_remove_duplicates:N { c }
5483 \cs_generate_variant:Nn \seq_gremove_duplicates:N { c }
(End definition for \seq_remove_duplicates:N and \seq_gremove_duplicates:c These functions are documented on page ??.)
```

\seq_remove_all:Nn
\seq_remove_all:cn
\seq_gremove_all:Nn
\seq_gremove_all:cn
__seq_remove_all_aux:NNn

The idea of the code here is to avoid a relatively expensive addition of items one at a time to an intermediate sequence. The approach taken is therefore similar to that in __-seq_pop_right_aux_i:NNN, using a “flexible” x-type expansion to do most of the work. As \tl_if_eq:nnT is not expandable, a two-part strategy is needed. First, the x-type expansion uses \str_if_eq:nnT to find potential matches. If one is found, the expansion is halted and the necessary set up takes place to use the \tl_if_eq:NNT test. The x-type is started again, including all of the items copied already. This will happen repeatedly until the entire sequence has been scanned. The code is set up to avoid needing an intermediate scratch list: the lead-off x-type expansion (#1 #2 {#2}) will ensure that nothing is lost.

```

5484 \cs_new_protected:Npn \seq_remove_all:Nn
5485   { \__seq_remove_all_aux:NNn \tl_set:Nx }
5486 \cs_new_protected:Npn \seq_gremove_all:Nn
5487   { \__seq_remove_all_aux:NNn \tl_gset:Nx }
5488 \cs_new_protected:Npn \__seq_remove_all_aux:NNn #1#2#3
5489   {
5490     \__seq_push_item_def:n
5491   {
5492     \str_if_eq:nnT {##1} {#3}
5493     {
5494       \if_false: { \fi: }
5495       \tl_set:Nn \l__seq_internal_b_tl {##1}
5496       #1 #2
5497       { \if_false: } \fi:
5498       \exp_not:o {#2}
5499       \tl_if_eq:NNT \l__seq_internal_a_tl \l__seq_internal_b_tl
5500       { \use_none:nn }
5501     }
5502     \__seq_wrap_item:n {##1}
5503   }
5504   \tl_set:Nn \l__seq_internal_a_tl {#3}
5505   #1 #2 {#2}
5506   \__seq_pop_item_def:
5507 }
5508 \cs_generate_variant:Nn \seq_remove_all:Nn { c }
5509 \cs_generate_variant:Nn \seq_gremove_all:Nn { c }
(End definition for \seq_remove_all:Nn and \seq_gremove_all:Nn These functions are documented on page ??.)
```

11.4 Sequence conditionals

```
\seq_if_empty:N
\seq_if_empty:p:c
\seq_if_empty:NTF
\seq_if_empty:cTF
5510 \prg_new_eq_conditional:Nnn \seq_if_empty:N \tl_if_empty:N
5511 { p , T , F , TF }
5512 \prg_new_eq_conditional:Nnn \seq_if_empty:c \tl_if_empty:c
5513 { p , T , F , TF }
(End definition for \seq_if_empty:N and \seq_if_empty:c These functions are documented on page ??.)
```

\seq_if_in:Nn~~TF~~ The approach here is to define `__seq_item:n` to compare its argument with the test sequence. If the two items are equal, the mapping is terminated and `\group_end: \prg_return_true:` is inserted after skipping over the rest of the recursion. On the other hand, if there is no match then the loop will break returning `\prg_return_false:`. Everything is inside a group so that `__seq_item:n` is preserved in nested situations.

```
\seq_if_in:cnT
\seq_if_in:cNvTF
\seq_if_in:cNvTF
\seq_if_in:cNoTF
\seq_if_in:cNxTF
\seq_if_in:ccoTF
\seq_if_in:ccxTF
\__seq_if_in:
5514 \prg_new_protected_conditional:Npn \seq_if_in:Nn #1#2
5515 { T , F , TF }
5516 {
5517   \group_begin:
5518     \tl_set:Nn \l__seq_internal_a_tl {#2}
5519     \cs_set_protected:Npn \__seq_item:n ##1
5520     {
5521       \tl_set:Nn \l__seq_internal_b_tl {##1}
5522       \if_meaning:w \l__seq_internal_a_tl \l__seq_internal_b_tl
5523         \exp_after:wN \__seq_if_in:
5524       \fi:
5525     }
5526   #1
5527   \group_end:
5528   \prg_return_false:
5529   \__prg_break_point:
5530 }
5531 \cs_new_nopar:Npn \__seq_if_in:
5532 { \__prg_break:n { \group_end: \prg_return_true: } }
5533 \cs_generate_variant:Nn \seq_if_in:NnT { NV , Nv , No , Nx }
5534 \cs_generate_variant:Nn \seq_if_in:NnT { c , cv , cv , co , cx }
5535 \cs_generate_variant:Nn \seq_if_in:NnF { NV , Nv , No , Nx }
5536 \cs_generate_variant:Nn \seq_if_in:NnF { c , cv , cv , co , cx }
5537 \cs_generate_variant:Nn \seq_if_in:NnTF { NV , Nv , No , Nx }
5538 \cs_generate_variant:Nn \seq_if_in:NnTF { c , cv , cv , co , cx }
(End definition for \seq_if_in:Nn and others. These functions are documented on page ??.)
```

11.5 Recovering data from sequences

```
\__seq_pop:NNNN
\__seq_pop_TF:NNNN
```

The two `pop` functions share their emptiness tests. We also use a common emptiness test for all branching `get` and `pop` functions.

```
5539 \cs_new_protected:Npn \__seq_pop:NNNN #1#2#3#4
5540 {
5541   \if_meaning:w #3 \c_empty_seq
```

```

5542     \tl_set:Nn #4 { \q_no_value }
5543 \else:
5544     #1#2#3#4
5545 \fi:
5546 }
5547 \cs_new_protected:Npn \__seq_pop_TF:NNNN #1#2#3#4
5548 {
5549     \if_meaning:w #3 \c_empty_seq
5550         % \tl_set:Nn #4 { \q_no_value }
5551         \prg_return_false:
5552     \else:
5553         #1#2#3#4
5554         \prg_return_true:
5555     \fi:
5556 }

```

(End definition for `__seq_pop:NNNN` and `__seq_pop_TF:NNNN`)

\seq_get_left:NN Getting an item from the left of a sequence is pretty easy: just trim off the first item after removing the `__seq_item:n` at the start. We first append a `\q_no_value` item to cover the case of an empty sequence

```

5557 \cs_new_protected:Npn \seq_get_left:NN #1#2
5558 {
5559     \tl_set:Nx #2
5560     {
5561         \exp_after:wN \__seq_get_left:Nnw
5562         #1 \__seq_item:n { \q_no_value } \q_stop
5563     }
5564 }
5565 \cs_new:Npn \__seq_get_left:Nnw \__seq_item:n #1#2 \q_stop
5566 { \exp_not:n {#1} }
5567 \cs_generate_variant:Nn \seq_get_left:NN { c }

```

(End definition for `\seq_get_left:NN` and `\seq_get_left:cN` These functions are documented on page ??.)

\seq_pop_left:NN The approach to popping an item is pretty similar to that to get an item, with the only difference being that the sequence itself has to be redefined. This makes it more sensible to use an auxiliary function for the local and global cases.

```

5568 \cs_new_protected_nopar:Npn \seq_pop_left:NN
5569 { \__seq_pop>NNNN \__seq_pop_left>NNN \tl_set:Nn }
5570 \cs_new_protected_nopar:Npn \seq_gpop_left:NN
5571 { \__seq_pop>NNNN \__seq_pop_left>NNN \tl_gset:Nn }
5572 \cs_new_protected:Npn \__seq_pop_left>NNN #1#2#3
5573 { \exp_after:wN \__seq_pop_left:NnwNNN #2 \q_stop #1#2#3 }
5574 \cs_new_protected:Npn \__seq_pop_left:NnwNNN \__seq_item:n #1#2 \q_stop #3#4#5
5575 {
5576     #3 #4 {#2}
5577     \tl_set:Nn #5 {#1}
5578 }
5579 \cs_generate_variant:Nn \seq_pop_left:NN { c }

```

```

5580 \cs_generate_variant:Nn \seq_gpop_left:NN { c }
(End definition for \seq_pop_left:NN and \seq_pop_left:cN These functions are documented on page
??.)

```

\seq_get_right:NN
\seq_get_right:cN
__seq_get_right_loop:nn

First prepend \q_no_value, then take two arguments at a time. Apart from the right-hand end of the sequence, this be a brace group followed by __seq_item:n. The \use_none:nn removes both of those. At the end of the sequence, the two question marks are taken by \use_none:nn, and the assignment is placed before the right-most item. The \afterassignment primitive places \use_none:n to get rid of a trailing __seq_get_right_loop:nn.

```

5581 \cs_new_protected:Npn \seq_get_right:NN #1#2
5582 {
5583   \exp_after:wN \__seq_get_right_loop:nn
5584   \exp_after:wN \q_no_value
5585   #1
5586   {
5587     ??
5588     \tex_afterassignment:D \use_none:n
5589     \tl_set:Nn #2
5590   }
5591 }
5592 \cs_new_protected:Npn \__seq_get_right_loop:nn #1#2
5593 {
5594   \use_none:nn #2 {#1}
5595   \__seq_get_right_loop:nn
5596 }
5597 \cs_generate_variant:Nn \seq_get_right:NN { c }
(End definition for \seq_get_right:NN and \seq_get_right:cN These functions are documented on page
??.)

```

\seq_pop_right:NN
\seq_pop_right:cN
\seq_gpop_right:NN
\seq_gpop_right:cN
__seq_pop_right_aux:NNN
__seq_pop_right_loop:nn

The approach to popping from the right is a bit more involved, but does use some of the same ideas as getting from the right. What is needed is a “flexible length” way to set a token list variable. This is supplied by the { \if_false: } \fi: ... \if_false: { \fi: } construct. Using an x-type expansion and a “non-expanding” definition for __seq_item:n, the left-most $n - 1$ entries in a sequence of n items will be stored back in the sequence. That needs a loop of unknown length, hence using the strange \if_false: way of including brackets. When the last item of the sequence is reached, the closing bracket for the assignment is inserted, and \tl_set:Nn #3 is inserted in front of the final entry. This therefore does the pop assignment. The trailing looping macro is removed by placing a \use_none:n using the \afterassignment primitive.

```

5598 \cs_new_protected:Npn \seq_pop_right:NN
5599   { \__seq_pop:NNNN \__seq_pop_right_aux:NNN \tl_set:Nx }
5600 \cs_new_protected:Npn \seq_gpop_right:NN
5601   { \__seq_pop:NNNN \__seq_pop_right_aux:NNN \tl_gset:Nx }
5602 \cs_new_protected:Npn \__seq_pop_right_aux:NNN #1#2#3
5603   {
5604     \cs_set_eq:NN \seq_tmp:w \__seq_item:n
5605     \cs_set_eq:NN \__seq_item:n \scan_stop:

```

```

5606 #1 #2
5607 { \if_false: } \fi:
5608   \exp_after:wN \exp_after:WN
5609   \exp_after:wN \__seq_pop_right_loop:nn
5610   \exp_after:wN \use_none:n
5611 #2
5612 {
5613   \if_false: { \fi:
5614     \tex_afterassignment:D \use_none:n
5615     \tl_set:Nx #3
5616   }
5617   \cs_set_eq:NN \__seq_item:n \seq_tmp:w
5618 }
5619 \cs_new:Npn \__seq_pop_right_loop:nn #1#2
5620 {
5621   #2 { \exp_not:n {#1} }
5622   \__seq_pop_right_loop:nn
5623 }
5624 \cs_generate_variant:Nn \seq_pop_right:NN { c }
5625 \cs_generate_variant:Nn \seq_gpop_right:NN { c }
(End definition for \seq_pop_right:NN and \seq_pop_right:cN These functions are documented on page ??.)

```

\seq_get_left:NNTF **\seq_get_left:cNTF** Getting from the left or right with a check on the results. The first argument to __-seq_pop_TF:NNNN is left unused.

```

5626 \prg_new_protected_conditional:Npnn \seq_get_left:NN #1#2 { T , F , TF }
5627 { \__seq_pop_TF:NNNN \prg_do_nothing: \seq_get_left:NN #1#2 }
5628 \prg_new_protected_conditional:Npnn \seq_get_right:NN #1#2 { T , F , TF }
5629 { \__seq_pop_TF:NNNN \prg_do_nothing: \seq_get_right:NN #1#2 }
5630 \cs_generate_variant:Nn \seq_get_left:NNT { c }
5631 \cs_generate_variant:Nn \seq_get_left:NNF { c }
5632 \cs_generate_variant:Nn \seq_get_left:NNTF { c }
5633 \cs_generate_variant:Nn \seq_get_right:NNT { c }
5634 \cs_generate_variant:Nn \seq_get_right:NNF { c }
5635 \cs_generate_variant:Nn \seq_get_right:NNTF { c }
(End definition for \seq_get_left:NN and \seq_get_left:cN These functions are documented on page ??.)

```

\seq_pop_left:NNTF More or less the same for popping.

```

5636 \prg_new_protected_conditional:Npnn \seq_pop_left:NN #1#2 { T , F , TF }
5637 { \__seq_pop_TF:NNNN \__seq_pop_left:NNN \tl_set:Nn #1 #2 }
5638 \prg_new_protected_conditional:Npnn \seq_gpop_left:NN #1#2 { T , F , TF }
5639 { \__seq_pop_TF:NNNN \__seq_pop_left:NNN \tl_gset:Nn #1 #2 }
5640 \prg_new_protected_conditional:Npnn \seq_pop_right:NN #1#2 { T , F , TF }
5641 { \__seq_pop_TF:NNNN \__seq_pop_right_aux:NNN \tl_set:Nx #1 #2 }
5642 \prg_new_protected_conditional:Npnn \seq_gpop_right:NN #1#2 { T , F , TF }
5643 { \__seq_pop_TF:NNNN \__seq_pop_right_aux:NNN \tl_gset:Nx #1 #2 }
5644 \cs_generate_variant:Nn \seq_pop_left:NNT { c }
5645 \cs_generate_variant:Nn \seq_pop_left:NNF { c }

```

```

5646 \cs_generate_variant:Nn \seq_pop_left:NNTF { c }
5647 \cs_generate_variant:Nn \seq_gpop_left:NNT { c }
5648 \cs_generate_variant:Nn \seq_gpop_left:NNF { c }
5649 \cs_generate_variant:Nn \seq_gpop_left:NNTF { c }
5650 \cs_generate_variant:Nn \seq_pop_right:NNT { c }
5651 \cs_generate_variant:Nn \seq_pop_right:NNF { c }
5652 \cs_generate_variant:Nn \seq_pop_right:NNTF { c }
5653 \cs_generate_variant:Nn \seq_gpop_right:NNT { c }
5654 \cs_generate_variant:Nn \seq_gpop_right:NNF { c }
5655 \cs_generate_variant:Nn \seq_gpop_right:NNTF { c }

(End definition for \seq_pop_left:NN and \seq_pop_left:cN These functions are documented on page ??.)

```

11.6 Mapping to sequences

`\seq_map_break:`
`\seq_map_break:n`

To break a function, the special token `__prg_break_point:Nn` is used to find the end of the code. Any ending code is then inserted before the return value of `\seq_map_break:n` is inserted.

```

5656 \cs_new_nopar:Npn \seq_map_break:
5657   { \__prg_map_break:Nn \seq_map_break: { } }
5658 \cs_new_nopar:Npn \seq_map_break:n
5659   { \__prg_map_break:Nn \seq_map_break: }

```

(End definition for `\seq_map_break:` This function is documented on page 106.)

`\seq_map_function>NN`
`\seq_map_function:cN`
`__seq_map_function>NNn`

The idea here is to apply the code of #2 to each item in the sequence without altering the definition of `__seq_item:n`. This is done as by noting that every odd token in the sequence must be `__seq_item:n`, which can be gobbled by `\use_none:n`. At the end of the loop, #2 is instead `? \seq_map_break:`, which therefore breaks the loop without needing to do a (relatively-expensive) quark test.

```

5660 \cs_new:Npn \seq_map_function:NN #1#2
5661   {
5662     \exp_after:wN \__seq_map_function:NNn \exp_after:wN #2 #1
5663     { ? \seq_map_break: } { }
5664     \__prg_break_point:Nn \seq_map_break: { }
5665   }
5666 \cs_new:Npn \__seq_map_function>NNn #1#2#3
5667   {
5668     \use_none:n #2
5669     #1 {#3}
5670     \__seq_map_function:NNn #1
5671   }
5672 \cs_generate_variant:Nn \seq_map_function:NN { c }

(End definition for \seq_map_function>NN and \seq_map_function:cN These functions are documented on page ??.)

```

`__seq_push_item_def:n`
`__seq_push_item_def:x`
`__seq_push_item_def:`
`__seq_pop_item_def:`

The definition of `__seq_item:n` needs to be saved and restored at various points within the mapping and manipulation code. That is handled here: as always, this approach uses global assignments.

```

5673 \cs_new_protected:Npn \__seq_push_item_def:n
5674 {
5675     \__seq_push_item_def:
5676     \cs_gset:Npn \__seq_item:n ##1
5677 }
5678 \cs_new_protected:Npn \__seq_push_item_def:x
5679 {
5680     \__seq_push_item_def:
5681     \cs_gset:Npx \__seq_item:n ##1
5682 }
5683 \cs_new_protected:Npn \__seq_push_item_def:
5684 {
5685     \int_gincr:N \g__prg_map_int
5686     \cs_gset_eq:cN { __prg_map_ \int_use:N \g__prg_map_int :w }
5687     \__seq_item:n
5688 }
5689 \cs_new_protected_nopar:Npn \__seq_pop_item_def:
5690 {
5691     \cs_gset_eq:Nc \__seq_item:n
5692     { __prg_map_ \int_use:N \g__prg_map_int :w }
5693     \int_gdecr:N \g__prg_map_int
5694 }
(End definition for \__seq_push_item_def:n and \__seq_push_item_def:x These functions are documented on page 109.)
```

\seq_map_inline:Nn
\seq_map_inline:cn

The idea here is that __seq_item:n is already “applied” to each item in a sequence, and so an in-line mapping is just a case of redefining __seq_item:n.

```

5695 \cs_new_protected:Npn \seq_map_inline:Nn #1#2
5696 {
5697     \__seq_push_item_def:n {#2}
5698     #1
5699     \__prg_break_point:Nn \seq_map_break: { \__seq_pop_item_def: }
5700 }
5701 \cs_generate_variant:Nn \seq_map_inline:Nn { c }
(End definition for \seq_map_inline:Nn and \seq_map_inline:cn These functions are documented on page ??.)
```

\seq_map_variable>NNn
\seq_map_variable:Ncn
\seq_map_variable:cNn
\seq_map_variable:ccn

This is just a specialised version of the in-line mapping function, using an x-type expansion for the code set up so that the number of # tokens required is as expected.

```

5702 \cs_new_protected:Npn \seq_map_variable>NNn #1#2#3
5703 {
5704     \__seq_push_item_def:x
5705     {
5706         \tl_set:Nn \exp_not:N #2 {##1}
5707         \exp_not:n {#3}
5708     }
5709     #1
5710     \__prg_break_point:Nn \seq_map_break: { \__seq_pop_item_def: }
5711 }
```

```

5712 \cs_generate_variant:Nn \seq_map_variable:NNn { Nc }
5713 \cs_generate_variant:Nn \seq_map_variable:NNn { c , cc }
(End definition for \seq_map_variable:NNn and others. These functions are documented on page ??.)
```

\seq_count:N Counting the items in a sequence is done using the same approach as for other count functions: turn each entry into a `+1` then use integer evaluation to actually do the mathematics.

```

5714 \cs_new:Npn \seq_count:N #1
5715 {
5716   \int_eval:n
5717   {
5718     0
5719     \seq_map_function:NN #1 \__seq_count:n
5720   }
5721 }
5722 \cs_new:Npn \__seq_count:n #1 { + \c_one }
5723 \cs_generate_variant:Nn \seq_count:N { c }
```

(End definition for \seq_count:N and \seq_count:c These functions are documented on page ??.)

11.7 Sequence stacks

The same functions as for sequences, but with the correct naming.

\seq_push:Nn Pushing to a sequence is the same as adding on the left.

```

5724 \cs_new_eq:NN \seq_push:Nn \seq_put_left:Nn
5725 \cs_new_eq:NN \seq_push:NV \seq_put_left:NV
5726 \cs_new_eq:NN \seq_push:Nv \seq_put_left:Nv
5727 \cs_new_eq:NN \seq_push:No \seq_put_left:No
5728 \cs_new_eq:NN \seq_push:Nx \seq_put_left:Nx
5729 \cs_new_eq:NN \seq_push:cn \seq_put_left:cn
5730 \cs_new_eq:NN \seq_push:cV \seq_put_left:cV
5731 \cs_new_eq:NN \seq_push:cv \seq_put_left:cv
5732 \cs_new_eq:NN \seq_push:co \seq_put_left:co
5733 \cs_new_eq:NN \seq_push:cX \seq_put_left:cX
5734 \cs_new_eq:NN \seq_gpush:Nn \seq_gput_left:Nn
5735 \cs_new_eq:NN \seq_gpush:NV \seq_gput_left:NV
5736 \cs_new_eq:NN \seq_gpush:Nv \seq_gput_left:Nv
5737 \cs_new_eq:NN \seq_gpush:No \seq_gput_left:No
5738 \cs_new_eq:NN \seq_gpush:Nx \seq_gput_left:Nx
5739 \cs_new_eq:NN \seq_gpush:cn \seq_gput_left:cn
5740 \cs_new_eq:NN \seq_gpush:cV \seq_gput_left:cV
5741 \cs_new_eq:NN \seq_gpush:cv \seq_gput_left:cv
5742 \cs_new_eq:NN \seq_gpush:co \seq_gput_left:co
5743 \cs_new_eq:NN \seq_gpush:cX \seq_gput_left:cX
```

(End definition for \seq_push:Nn and others. These functions are documented on page ??.)

\seq_get>NN In most cases, getting items from the stack does not need to specify that this is from the left. So alias are provided.

\seq_pop>NN
\seq_pop:cN
\seq_gpop>NN
\seq_gpop:cN

```

5744 \cs_new_eq:NN \seq_get>NN \seq_get_left>NN
5745 \cs_new_eq:NN \seq_get:cN \seq_get_left:cN
5746 \cs_new_eq:NN \seq_pop>NN \seq_pop_left>NN
5747 \cs_new_eq:NN \seq_pop:cN \seq_pop_left:cN
5748 \cs_new_eq:NN \seq_gpop>NN \seq_gpop_left>NN
5749 \cs_new_eq:NN \seq_gpop:cN \seq_gpop_left:cN
(End definition for \seq_get>NN and \seq_get:cN These functions are documented on page ??.)
```

\seq_get:NNTF More copies.

```

5750 \prg_new_eq_conditional:Nnn \seq_get>NN \seq_get_left>NN { T , F , TF }
5751 \prg_new_eq_conditional:Nnn \seq_get:cN \seq_get_left:cN { T , F , TF }
5752 \prg_new_eq_conditional:Nnn \seq_pop>NN \seq_pop_left>NN { T , F , TF }
5753 \prg_new_eq_conditional:Nnn \seq_pop:cN \seq_pop_left:cN { T , F , TF }
5754 \prg_new_eq_conditional:Nnn \seq_gpop>NN \seq_gpop_left>NN { T , F , TF }
5755 \prg_new_eq_conditional:Nnn \seq_gpop:cN \seq_gpop_left:cN { T , F , TF }
(End definition for \seq_get>NN and \seq_get:cN These functions are documented on page ??.)
```

11.8 Viewing sequences

\seq_show:N Apply the general `__msg_show_variable:Nnn`.

```

5756 \cs_new_protected:Npn \seq_show:N #1
5757 {
5758   \__msg_show_variable:Nnn #1 { seq }
5759   { \seq_map_function:NN #1 \__msg_show_item:n }
5760 }
5761 \cs_generate_variant:Nn \seq_show:N { c }
(End definition for \seq_show:N and \seq_show:c These functions are documented on page ??.)
```

11.9 Scratch sequences

\l_tmpa_seq Temporary comma list variables.

```

5762 \seq_new:N \l_tmpa_seq
5763 \seq_new:N \l_tmpb_seq
5764 \seq_new:N \g_tmpa_seq
5765 \seq_new:N \g_tmpb_seq
(End definition for \l_tmpa_seq and others. These variables are documented on page 108.)
```

11.10 Deprecated interfaces

A few functions which are no longer documented: these were moved here on or before 2011-04-20, and will be removed entirely by 2011-07-20.

\seq_top>NN These are old stack functions.

```

5766 {*deprecated}
5767 \cs_new_eq:NN \seq_top>NN \seq_get_left>NN
5768 \cs_new_eq:NN \seq_top:cN \seq_get_left:cN
5769 //deprecated)
(End definition for \seq_top>NN and \seq_top:cN These functions are documented on page ??.)
```

```

\seq_display:N An older name for \seq_show:N.
\seq_display:c 5770 {*deprecated}
                5771 \cs_new_eq:NN \seq_display:N \seq_show:N
                5772 \cs_new_eq:NN \seq_display:c \seq_show:c
                5773 //deprecated
(End definition for \seq_display:N and \seq_display:c These functions are documented on page ??.)
Deprecation 2012-05-13 for removal by 2012-11-30.

\seq_length:N
\seq_length:c 5774 \cs_new_eq:NN \seq_length:N \seq_count:N
                5775 \cs_new_eq:NN \seq_length:c \seq_count:c
(End definition for \seq_length:N and \seq_length:c These functions are documented on page ??.)
Deprecation 2012-05-23 for removal by 2012-08-30.

\seq_use:N A simple short cut for a mapping.
\seq_use:c 5776 \cs_new:Npn \seq_use:N #1 { \seq_map_function:NN #1 \use:n }
                5777 \cs_generate_variant:Nn \seq_use:N { c }
(End definition for \seq_use:N and \seq_use:c These functions are documented on page ??.)
5778 //initex | package

```

12 l3clist implementation

The following test files are used for this code: m3clist002.

```

5779 /*initex | package
5780 @@=clist
5781 *package
5782 \ProvidesExplPackage
5783 {\ExplFileName}{\ExplFileDate}{\ExplFileVersion}{\ExplFileDescription}
5784 \__expl_package_check:
5785 //package

```

\c_empty_clist An empty comma list is simply an empty token list.

```

5786 \cs_new_eq:NN \c_empty_clist \c_empty_tl
(End definition for \c_empty_clist This variable is documented on page 117.)

```

\l__clist_internal_clist Scratch space for various internal uses. This comma list variable cannot be declared as such because it comes before \clist_new:N

```

5787 \tl_new:N \l__clist_internal_clist
(End definition for \l__clist_internal_clist This variable is documented on page ??.)

```

__clist_tmp:w A temporary function for various purposes.

```

5788 \cs_new_protected:Npn \__clist_tmp:w { }
(End definition for \__clist_tmp:w)

```

12.1 Allocation and initialisation

`\clist_new:N`

Internally, comma lists are just token lists.

`\clist_new:c`

```
5789 \cs_new_eq:NN \clist_new:N \tl_new:N
5790 \cs_new_eq:NN \clist_new:c \tl_new:c
```

(End definition for `\clist_new:N` and `\clist_new:c`. These functions are documented on page ??.)

`\clist_clear:N`

Clearing comma lists is just the same as clearing token lists.

`\clist_clear:c`

```
5791 \cs_new_eq:NN \clist_clear:N \tl_clear:N
5792 \cs_new_eq:NN \clist_clear:c \tl_clear:c
5793 \cs_new_eq:NN \clist_gclear:N \tl_gclear:N
5794 \cs_new_eq:NN \clist_gclear:c \tl_gclear:c
```

(End definition for `\clist_clear:N` and `\clist_clear:c`. These functions are documented on page ??.)

`\clist_clear_new:N`

`\clist_clear_new:c`

`\clist_gclear_new:N`

`\clist_gclear_new:c`

Once again a copy from the token list functions.

```
5795 \cs_new_eq:NN \clist_clear_new:N \tl_clear_new:N
5796 \cs_new_eq:NN \clist_clear_new:c \tl_clear_new:c
5797 \cs_new_eq:NN \clist_gclear_new:N \tl_gclear_new:N
5798 \cs_new_eq:NN \clist_gclear_new:c \tl_gclear_new:c
```

(End definition for `\clist_clear_new:N` and `\clist_clear_new:c`. These functions are documented on page ??.)

`\clist_set_eq:NN`

`\clist_set_eq:cN`

`\clist_set_eq:Nc`

`\clist_gset_eq:NN`

`\clist_gset_eq:cN`

`\clist_gset_eq:Nc`

`\clist_gset_eq:cc`

Once again, these are simple copies from the token list functions.

```
5799 \cs_new_eq:NN \clist_set_eq:NN \tl_set_eq:NN
5800 \cs_new_eq:NN \clist_set_eq:Nc \tl_set_eq:Nc
5801 \cs_new_eq:NN \clist_set_eq:cN \tl_set_eq:cN
5802 \cs_new_eq:NN \clist_set_eq:cc \tl_set_eq:cc
5803 \cs_new_eq:NN \clist_gset_eq:NN \tl_gset_eq:NN
5804 \cs_new_eq:NN \clist_gset_eq:Nc \tl_gset_eq:Nc
5805 \cs_new_eq:NN \clist_gset_eq:cN \tl_gset_eq:cN
5806 \cs_new_eq:NN \clist_gset_eq:cc \tl_gset_eq:cc
```

(End definition for `\clist_set_eq:NN` and others. These functions are documented on page ??.)

`\clist_concat:NNN`

`\clist_concat:ccc`

`\clist_gconcat:NNN`

`\clist_gconcat:ccc`

`_clist_concat:NNNN`

Concatenating comma lists is not quite as easy as it seems, as there needs to be the correct addition of a comma to the output. So a little work to do.

```
5807 \cs_new_protected_nopar:Npn \clist_concat:NNN
5808 { \_clist_concat:NNNN \tl_set:Nx }
5809 \cs_new_protected_nopar:Npn \clist_gconcat:NNN
5810 { \_clist_concat:NNNN \tl_gset:Nx }
5811 \cs_new_protected:Npn \_clist_concat:NNNN #1#2#3#4
5812 {
5813 #1 #2
5814 {
5815 \exp_not:o #3
5816 \clist_if_empty:NF #3 { \clist_if_empty:NF #4 { , } }
5817 \exp_not:o #4
5818 }
5819 }
5820 \cs_generate_variant:Nn \clist_concat:NNN { ccc }
5821 \cs_generate_variant:Nn \clist_gconcat:NNN { ccc }
```

(End definition for \clist_concat:NNN and \clist_concat:ccc These functions are documented on page ??.)

\clist_if_exist_p:N Copies of the cs functions defined in l3basics.
5822 \cs_new_eq:NN \clist_if_exist:NTF \cs_if_exist:NTF
5823 \cs_new_eq:NN \clist_if_exist:NT \cs_if_exist:NT
5824 \cs_new_eq:NN \clist_if_exist:NF \cs_if_exist:NF
5825 \cs_new_eq:NN \clist_if_exist_p:N \cs_if_exist_p:N
5826 \cs_new_eq:NN \clist_if_exist:cTF \cs_if_exist:cTF
5827 \cs_new_eq:NN \clist_if_exist:cT \cs_if_exist:cT
5828 \cs_new_eq:NN \clist_if_exist:cF \cs_if_exist:cF
5829 \cs_new_eq:NN \clist_if_exist_p:c \cs_if_exist_p:c
(End definition for \clist_if_exist:N and \clist_if_exist:c These functions are documented on page ??.)

12.2 Removing spaces around items

_clist_trim_spaces_generic:nw
_clist_trim_spaces_generic:nn This expands to the ⟨code⟩, followed by a brace group containing the ⟨item⟩, with leading and trailing spaces removed. The calling function is responsible for inserting \q_mark in front of the ⟨item⟩, as well as testing for the end of the list. We reuse a l3tl internal function, whose first argument must start with \q_mark. That trims the item #2, then feeds the result (after having to do an o-type expansion) to _clist_trim_spaces_-generic:nn which places the ⟨code⟩ in front of the ⟨trimmed item⟩.

5830 \cs_new:Npn _clist_trim_spaces_generic:nw #1#2 ,
5831 {
5832 _tl_trim_spaces:nn {#2}
5833 { \exp_args:No _clist_trim_spaces_generic:nn } {#1}
5834 }
5835 \cs_new:Npn _clist_trim_spaces_generic:nn #1#2 { #2 {#1} }
(End definition for _clist_trim_spaces_generic:nw This function is documented on page ??.)

_clist_trim_spaces:n
_clist_trim_spaces_ii:nn The first argument of _clist_trim_spaces_ii:nn is initially empty, and later a comma, namely, as soon as we have added an item to the resulting list. The auxiliary tests for the end of the list, and also prevents empty arguments from finding their way into the output.

5836 \cs_new:Npn _clist_trim_spaces:n #1
5837 {
5838 _clist_trim_spaces_generic:nw
5839 { _clist_trim_spaces_ii:nn { } }
5840 \q_mark #1 ,
5841 \q_recursion_tail, \q_recursion_stop
5842 }
5843 \cs_new:Npn _clist_trim_spaces_ii:nn #1 #2
5844 {
5845 \quark_if_recursion_tail_stop:n {#2}
5846 \tl_if_empty:nTF {#2}
5847 {
5848 _clist_trim_spaces_generic:nw

```

5849     { \__clist_trim_spaces_ii:nn {#1} } \q_mark
5850   }
5851   {
5852     #1 \exp_not:n {#2}
5853     \__clist_trim_spaces_generic:nw
5854     { \__clist_trim_spaces_ii:nn { , } } \q_mark
5855   }
5856 }
(End definition for \__clist_trim_spaces:n This function is documented on page ??.)
```

12.3 Adding data to comma lists

```

\clist_set:Nn
\clist_set:NV
\clist_set:No
\clist_set:Nx
\clist_set:cn
\clist_set:cV
\clist_set:co
\clist_set:cx
\clist_gset:Nn
\clist_put_left:Nn
\clist_gset:NV
\clist_put_left:NV
\clist_gset:No
\clist_put_left:No
\clist_gset:Nx
\clist_put_left:Nx
\clist_gset:cn
\clist_put_left:cn
\clist_gset:cV
\clist_gset:co
\clist_put_left:co
\clist_gset:cx
\clist_put_left:cx
\clist_gput_left:Nn
\clist_gput_left:NV
\clist_gput_left:No
\clist_gput_left:Nx
\clist_gput_left:cn
\clist_gput_left:cV
\clist_gput_left:co
\clist_gput_left:cx
\__\clist_put_right:Nn
\clist_put_right:NV
\clist_put_right:No
\clist_put_right:Nx
\clist_put_right:cn
\clist_put_right:cV
\clist_put_right:co
\clist_put_right:cx
\clist_gput_right:Nn
\clist_gput_right:NV
\clist_gput_right:No
\clist_gput_right:Nx
\clist_gput_right:cn
\clist_gput_right:cV
\clist_gput_right:co
\clist_gput_right:cx
\__\clist_put_right:NNNn
```

Comma lists cannot hold empty values: there are therefore a couple of sanity checks to avoid accumulating commas.

```

5863 \cs_new_protected:Npn \clist_put_left:Nn
5864   { \__clist_put_left:NNNn \clist_concat:NNN \clist_set:Nn }
5865 \cs_new_protected_nopar:Npn \clist_gput_left:Nn
5866   { \__clist_put_left:NNNn \clist_gconcat:NNN \clist_set:Nn }
5867 \cs_new_protected:Npn \__clist_put_left:NNNn #1#2#3#4
5868   {
5869     #2 \l__clist_internal_clist {#4}
5870     #1 #3 \l__clist_internal_clist #3
5871   }
5872 \cs_generate_variant:Nn \clist_put_left:Nn { NV , No , Nx }
5873 \cs_generate_variant:Nn \clist_put_left:Nn { c , cV , co , cx }
5874 \cs_generate_variant:Nn \clist_gput_left:Nn { NV , No , Nx }
5875 \cs_generate_variant:Nn \clist_gput_left:Nn { c , cV , co , cx }
(End definition for \clist_put_left:Nn and others. These functions are documented on page ??.)
```

```

5876 \cs_new_protected_nopar:Npn \clist_put_right:Nn
5877   { \__clist_put_right:NNNn \clist_concat:NNN \clist_set:Nn }
5878 \cs_new_protected_nopar:Npn \clist_gput_right:Nn
5879   { \__clist_put_right:NNNn \clist_gconcat:NNN \clist_set:Nn }
5880 \cs_new_protected:Npn \__clist_put_right:NNNn #1#2#3#4
5881   {
5882     #2 \l__clist_internal_clist {#4}
5883     #1 #3 #3 \l__clist_internal_clist
5884 }
```

```

5885 \cs_generate_variant:Nn \clist_put_right:Nn { NV , No , Nx }
5886 \cs_generate_variant:Nn \clist_put_right:Nn { c , cV , co , cx }
5887 \cs_generate_variant:Nn \clist_gput_right:Nn { NV , No , Nx }
5888 \cs_generate_variant:Nn \clist_gput_right:Nn { c , cV , co , cx }
(End definition for \clist_put_right:Nn and others. These functions are documented on page ??.)
```

12.4 Comma lists as stacks

`\clist_get:NN`
`\clist_get:cN`
`_clist_get:wN`

```

5889 \cs_new_protected:Npn \clist_get:NN #1#2
5890 {
5891   \if_meaning:w #1 \c_empty_clist
5892     \tl_set:Nn #2 { \q_no_value }
5893   \else:
5894     \exp_after:wN \_clist_get:wN #1 , \q_stop #2
5895   \fi:
5896 }
5897 \cs_new_protected:Npn \_clist_get:wN #1 , #2 \q_stop #3
5898   { \tl_set:Nn #3 {#1} }
5899 \cs_generate_variant:Nn \clist_get:NN { c }
```

(End definition for \clist_get:NN and \clist_get:cN These functions are documented on page ??.)

`\clist_pop:NN`
`\clist_pop:cN`
`\clist_gpop:NN`
`\clist_gpop:cN`
`_clist_pop:NNN`
`_clist_pop:wwNNN`
`_clist_pop:wN`

An empty clist leads to `\q_no_value`, otherwise grab until the first comma and assign to the variable. The second argument of `_clist_pop:wwNNN` is a comma list ending in a comma and `\q_mark`, unless the original clist contained exactly one item: then the argument is just `\q_mark`. The next auxiliary picks either `\exp_not:n` or `\use_none:n` as #2, ensuring that the result can safely be an empty comma list.

```

5900 \cs_new_protected_nopar:Npn \clist_pop:NN
5901   { \_clist_pop:NNN \tl_set:Nx }
5902 \cs_new_protected_nopar:Npn \clist_gpop:NN
5903   { \_clist_pop:NNN \tl_gset:Nx }
5904 \cs_new_protected:Npn \_clist_pop:NNN #1#2#3
5905 {
5906   \if_meaning:w #2 \c_empty_clist
5907     \tl_set:Nn #3 { \q_no_value }
5908   \else:
5909     \exp_after:wN \_clist_pop:wwNNN #2 , \q_mark \q_stop #1#2#3
5910   \fi:
5911 }
5912 \cs_new_protected:Npn \_clist_pop:wwNNN #1 , #2 \q_stop #3#4#5
5913 {
5914   \tl_set:Nn #5 {#1}
5915   #3 #4
5916   {
5917     \_clist_pop:wN \prg_do_nothing:
5918       #2 \exp_not:o
5919       , \q_mark \use_none:n
```

```

5920           \q_stop
5921       }
5922   }
5923 \cs_new:Npn \__clist_pop:wN #1 , \q_mark #2 #3 \q_stop { #2 {#1} }
5924 \cs_generate_variant:Nn \clist_pop:NN { c }
5925 \cs_generate_variant:Nn \clist_gpop:NN { c }
(End definition for \clist_pop:NN and \clist_pop:cN These functions are documented on page ??.)
```

The same, as branching code: very similar to the above.

```

\clist_get:NNTF
\clist_get:cNTF
\clist_pop:NNTF
\clist_pop:cNTF
\clist_gpop:NNTF
\clist_gpop:cNTF
\__clist_pop_TF:NNN
5926 \prg_new_protected_conditional:Npnn \clist_get:NN #1#2 { T , F , TF }
5927 {
5928     \if_meaning:w #1 \c_empty_clist
5929         \prg_return_false:
5930     \else:
5931         \exp_after:wN \__clist_get:wN #1 , \q_stop #2
5932         \prg_return_true:
5933     \fi:
5934 }
5935 \cs_generate_variant:Nn \clist_get:NNT { c }
5936 \cs_generate_variant:Nn \clist_get:NNF { c }
5937 \cs_generate_variant:Nn \clist_get:NNTF { c }
5938 \prg_new_protected_conditional:Npnn \clist_pop:NN #1#2 { T , F , TF }
5939 { \__clist_pop_TF:NNN \tl_set:Nx #1 #2 }
5940 \prg_new_protected_conditional:Npnn \clist_gpop:NN #1#2 { T , F , TF }
5941 { \__clist_pop_TF:NNN \tl_gset:Nx #1 #2 }
5942 \cs_new_protected:Npn \__clist_pop_TF:NNN #1#2#3
5943 {
5944     \if_meaning:w #2 \c_empty_clist
5945         \prg_return_false:
5946     \else:
5947         \exp_after:wN \__clist_pop:wwNNN #2 , \q_mark \q_stop #1#2#3
5948         \prg_return_true:
5949     \fi:
5950 }
5951 \cs_generate_variant:Nn \clist_pop:NNT { c }
5952 \cs_generate_variant:Nn \clist_pop:NNF { c }
5953 \cs_generate_variant:Nn \clist_pop:NNTF { c }
5954 \cs_generate_variant:Nn \clist_gpop:NNT { c }
5955 \cs_generate_variant:Nn \clist_gpop:NNF { c }
5956 \cs_generate_variant:Nn \clist_gpop:NNTF { c }
(End definition for \clist_get:NN and \clist_get:cN These functions are documented on page ??.)
```

\clist_push:Nn

```

\clist_push:NV
\clist_push:No
\clist_push:Nx
\clist_push:cn
\clist_push:cV
\clist_push:co
\clist_push:cx
\clist_gpush:Nn
\clist_gpush:NV
\clist_gpush:No
\clist_gpush:Nx
\clist_gpush:cn
\clist_gpush:cV
\clist_gpush:co
\clist_gpush:cx
5957 \cs_new_eq:NN \clist_push:Nn \clist_put_left:Nn
5958 \cs_new_eq:NN \clist_push:NV \clist_put_left:NV
5959 \cs_new_eq:NN \clist_push:No \clist_put_left:No
5960 \cs_new_eq:NN \clist_push:Nx \clist_put_left:Nx
5961 \cs_new_eq:NN \clist_push:cn \clist_put_left:cn
5962 \cs_new_eq:NN \clist_push:cV \clist_put_left:cV
```

```

5963 \cs_new_eq:NN \clist_push:co \clist_put_left:co
5964 \cs_new_eq:NN \clist_push:cx \clist_put_left:cx
5965 \cs_new_eq:NN \clist_gpush:Nn \clist_gput_left:Nn
5966 \cs_new_eq:NN \clist_gpush:NV \clist_gput_left:NV
5967 \cs_new_eq:NN \clist_gpush:No \clist_gput_left:No
5968 \cs_new_eq:NN \clist_gpush:Nx \clist_gput_left:Nx
5969 \cs_new_eq:NN \clist_gpush:cn \clist_gput_left:cn
5970 \cs_new_eq:NN \clist_gpush:cV \clist_gput_left:cV
5971 \cs_new_eq:NN \clist_gpush:co \clist_gput_left:co
5972 \cs_new_eq:NN \clist_gpush:cx \clist_gput_left:cx

```

(End definition for `\clist_push:Nn` and others. These functions are documented on page ??.)

12.5 Modifying comma lists

`\l__clist_internal_remove_clist` An internal comma list for the removal routines.

```
5973 \clist_new:N \l__clist_internal_remove_clist
```

(End definition for `\l__clist_internal_remove_clist` This variable is documented on page ??.)

`\clist_remove_duplicates:N` Removing duplicates means making a new list then copying it.

```

5974 \cs_new_protected:Npn \clist_remove_duplicates:N
5975 { \__clist_remove_duplicates>NN \clist_set_eq:NN }
5976 \cs_new_protected:Npn \clist_gremove_duplicates:N
5977 { \__clist_remove_duplicates>NN \clist_gset_eq:NN }
5978 \cs_new_protected:Npn \__clist_remove_duplicates>NN #1#2
5979 {
5980     \clist_clear:N \l__clist_internal_remove_clist
5981     \clist_map_inline:Nn #2
5982     {
5983         \clist_if_in:NnF \l__clist_internal_remove_clist {##1}
5984         { \clist_put_right:Nn \l__clist_internal_remove_clist {##1} }
5985     }
5986     #1 #2 \l__clist_internal_remove_clist
5987 }
5988 \cs_generate_variant:Nn \clist_remove_duplicates:N { c }
5989 \cs_generate_variant:Nn \clist_gremove_duplicates:N { c }

```

(End definition for `\clist_remove_duplicates:N` and `\clist_remove_duplicates:c` These functions are documented on page ??.)

`\clist_remove_all:Nn` The method used here is very similar to `\tl_replace_all:Nnn`. Build a function delimited by the `\item` that should be removed, surrounded with commas, and call that function followed by the expanded comma list, and another copy of the `\item`. The loop is controlled by the argument grabbed by `__clist_remove_all:w`: when the item was found, the `\q_mark` delimiter used is the one inserted by `__clist_tmp:w`, and `\use_none_delimit_by_q_stop:w` is deleted. At the end, the final `\item` is grabbed, and the argument of `__clist_tmp:w` contains `\q_mark`: in that case, `__clist_remove_all:w` removes the second `\q_mark` (inserted by `__clist_tmp:w`), and lets `\use_none_delimit_by_q_stop:w` act.

No brace is lost because items are always grabbed with a leading comma. The result of the first assignment has an extra leading comma, which we remove in a second assignment. Two exceptions: if the clist lost all of its elements, the result is empty, and we shouldn't remove anything; if the clist started up empty, the first step happens to turn it into a single comma, and the second step removes it.

```

5990 \cs_new_protected:Npn \clist_remove_all:Nn
5991   { \__clist_remove_all:NNn \tl_set:Nx }
5992 \cs_new_protected:Npn \clist_gremove_all:Nn
5993   { \__clist_remove_all:NNn \tl_gset:Nx }
5994 \cs_new_protected:Npn \__clist_remove_all:NNn #1#2#3
5995   {
5996     \cs_set:Npn \__clist_tmp:w ##1 , #3 ,
5997     {
5998       ##1
5999       , \q_mark , \use_none_delimit_by_q_stop:w ,
6000       \__clist_remove_all:
6001     }
6002   #1 #2
6003   {
6004     \exp_after:wN \__clist_remove_all:
6005     #2 , \q_mark , #3 , \q_stop
6006   }
6007 \clist_if_empty:NF #2
6008   {
6009     #1 #2
6010     {
6011       \exp_args:No \exp_not:o
6012       { \exp_after:wN \use_none:n #2 }
6013     }
6014   }
6015 }
6016 \cs_new:Npn \__clist_remove_all:
6017   { \exp_after:wN \__clist_remove_all:w \__clist_tmp:w , }
6018 \cs_new:Npn \__clist_remove_all:w #1 , \q_mark , #2 , { \exp_not:n {#1} }
6019 \cs_generate_variant:Nn \clist_remove_all:Nn { c }
6020 \cs_generate_variant:Nn \clist_gremove_all:Nn { c }
(End definition for \clist_remove_all:Nn and \clist_remove_all:cn These functions are documented on page ??.)
```

12.6 Comma list conditionals

<code>\clist_if_empty_p:N</code>	Simple copies from the token list variable material.
<code>\clist_if_empty_p:c</code>	
<code>\clist_if_empty:NTF</code>	
<code>\clist_if_empty:cTF</code>	
<code>\clist_if_empty:N</code>	(End definition for \clist_if_empty:N and \clist_if_empty:c These functions are documented on page ??.)
<code>\clist_if_in:NnTF</code>	See description of the \tl_if_in:Nn function for details. We simply surround the comma list, and the item, with commas.
<code>\clist_if_in:NVT</code>	
<code>\clist_if_in:NcTF</code>	
<code>\clist_if_in:cNVT</code>	
<code>\clist_if_in:cNTF</code>	
<code>\clist_if_in:nTF</code>	
<code>\clist_if_in:nVTF</code>	
<code>\clist_if_in:ncoTF</code>	
<code>\clist_if_in:nNTF</code>	
<code>\clist_if_in:nVNTF</code>	
<code>\clist_if_in:nnoTF</code>	
<code>__clist_if_in_return:nN</code>	

```

6023 \prg_new_protected_conditional:Npnn \clist_if_in:Nn #1#2 { T , F , TF }
6024 {
6025   \exp_args:No \__clist_if_in_return:nn #1 {#2}
6026 }
6027 \prg_new_protected_conditional:Npnn \clist_if_in:nn #1#2 { T , F , TF }
6028 {
6029   \clist_set:Nn \l__clist_internal_clist {#1}
6030   \exp_args:No \__clist_if_in_return:nn \l__clist_internal_clist {#2}
6031 }
6032 \cs_new_protected:Npn \__clist_if_in_return:nn #1#2
6033 {
6034   \cs_set:Npn \__clist_tmp:w ##1 ,#2, { }
6035   \tl_if_empty:oTF
6036     { \__clist_tmp:w ,#1, {} {} ,#2, }
6037     { \prg_return_false: } { \prg_return_true: }
6038 }
6039 \cs_generate_variant:Nn \clist_if_in:NnT { NV , No }
6040 \cs_generate_variant:Nn \clist_if_in:NnT { c , cV , co }
6041 \cs_generate_variant:Nn \clist_if_in:NnF { NV , No }
6042 \cs_generate_variant:Nn \clist_if_in:NnF { c , cV , co }
6043 \cs_generate_variant:Nn \clist_if_in:NnTF { NV , No }
6044 \cs_generate_variant:Nn \clist_if_in:NnTF { c , cV , co }
6045 \cs_generate_variant:Nn \clist_if_in:nnT { nV , no }
6046 \cs_generate_variant:Nn \clist_if_in:nnF { nV , no }
6047 \cs_generate_variant:Nn \clist_if_in:nnTF { nV , no }

(End definition for \clist_if_in:Nn and others. These functions are documented on page ??.)
```

12.7 Mapping to comma lists

\clist_map_function:NN
\clist_map_function:cN
__clist_map_function:Nw

If the variable is empty, the mapping is skipped (otherwise, that comma-list would be seen as consisting of one empty item). Then loop over the comma-list, grabbing one comma-delimited item at a time. The end is marked by \q_recursion_tail. The auxiliary function __clist_map_function:Nw is used directly in \clist_map_inline:Nn. Change with care.

```

6048 \cs_new:Npn \clist_map_function:NN #1#2
6049 {
6050   \clist_if_empty:NF #1
6051   {
6052     \exp_last_unbraced:NNo \__clist_map_function:Nw #2 #1
6053     , \q_recursion_tail ,
6054     \__prg_break_point:Nn \clist_map_break: { }
6055   }
6056 }
6057 \cs_new:Npn \__clist_map_function:Nw #1#2 ,
6058 {
6059   \__quark_if_recursion_tail_break:nN {#2} \clist_map_break:
6060   #1 {#2}
6061   \__clist_map_function:Nw #1
6062 }
```

```

6063 \cs_generate_variant:Nn \clist_map_function:NN { c }
(End definition for \clist_map_function:NN and \clist_map_function:cN These functions are documented on page ??.)
```

```
\clist_map_function:nN
\__clist_map_function_n:Nn
\__clist_map_unbrace:Nw
```

The `n`-type mapping function is a bit more awkward, since spaces must be trimmed from each item. Space trimming is again based on `__clist_trim_spaces_generic:nw`. The auxiliary `__clist_map_function_n:Nn` receives as arguments the function, and the result of removing leading and trailing spaces from the item which lies until the next comma. Empty items are ignored, then one level of braces is removed by `__clist_map_unbrace:Nw`.

```

6064 \cs_new:Npn \clist_map_function:nN #1#2
6065 {
6066   \__clist_trim_spaces_generic:nw { \__clist_map_function_n:Nn #2 }
6067   \q_mark #1, \q_recursion_tail,
6068   \__prg_break_point:Nn \clist_map_break: { }
6069 }
6070 \cs_new:Npn \__clist_map_function_n:Nn #1 #2
6071 {
6072   \__quark_if_recursion_tail_break:nN {#2} \clist_map_break:
6073   \tl_if_empty:nF {#2} { \__clist_map_unbrace:Nw #1 #2, }
6074   \__clist_trim_spaces_generic:nw { \__clist_map_function_n:Nn #1 }
6075   \q_mark
6076 }
6076 \cs_new:Npn \__clist_map_unbrace:Nw #1 #2, { #1 {#2} }
```

(End definition for \clist_map_function:nN This function is documented on page ??.)

```
\clist_map_inline:Nn
\clist_map_inline:cn
\clist_map_inline:nn
```

Inline mapping is done by creating a suitable function “on the fly”: this is done globally to avoid any issues with TeX’s groups. We use a different function for each level of nesting.

Since the mapping is non-expandable, we can perform the space-trimming needed by the `n` version simply by storing the comma-list in a variable. We don’t need a different comma-list for each nesting level: the comma-list is expanded before the mapping starts.

```

6078 \cs_new_protected:Npn \clist_map_inline:Nn #1#2
6079 {
6080   \clist_if_empty:NF #1
6081   {
6082     \int_gincr:N \g__prg_map_int
6083     \cs_gset:cpn { __prg_map_ \int_use:N \g__prg_map_int :w } ##1 {#2}
6084     \exp_last_unbraced:Nco \__clist_map_function:Nw
6085     { __prg_map_ \int_use:N \g__prg_map_int :w }
6086     #1 , \q_recursion_tail ,
6087     \__prg_break_point:Nn \clist_map_break:
6088     { \int_gdecr:N \g__prg_map_int }
6089   }
6090 }
6091 \cs_new_protected:Npn \clist_map_inline:nn #1
6092 {
6093   \clist_set:Nn \l__clist_internal_clist {#1}
```

```

6094     \clist_map_inline:Nn \l__clist_internal_clist
6095   }
6096 \cs_generate_variant:Nn \clist_map_inline:Nn { c }
(End definition for \clist_map_inline:Nn and \clist_map_inline:cn These functions are documented
on page ??.)
```

\clist_map_variable:NNn
\clist_map_variable:cNn
\clist_map_variable:nNn
__clist_map_variable:Nnw

As for other comma-list mappings, filter out the case of an empty list. Same approach as \clist_map_function:Nn, additionally we store each item in the given variable. As for inline mappings, space trimming for the n variant is done by storing the comma list in a variable.

```

6097 \cs_new_protected:Npn \clist_map_variable:NNn #1#2#3
6098 {
6099   \clist_if_empty:NF #1
6100   {
6101     \exp_args:Nno \use:nn
6102     { \__clist_map_variable:Nnw #2 {#3} }
6103     #1
6104     , \q_recursion_tail , \q_recursion_stop
6105     \__prg_break_point:Nn \clist_map_break: { }
6106   }
6107 }
6108 \cs_new_protected:Npn \clist_map_variable:nNn #1
6109 {
6110   \clist_set:Nn \l__clist_internal_clist {#1}
6111   \clist_map_variable:NNn \l__clist_internal_clist
6112 }
6113 \cs_new_protected:Npn \__clist_map_variable:Nnw #1#2#3,
6114 {
6115   \tl_set:Nn #1 {#3}
6116   \quark_if_recursion_tail_stop:N #1
6117   \use:n {#2}
6118   \__clist_map_variable:Nnw #1 {#2}
6119 }
6120 \cs_generate_variant:Nn \clist_map_variable:NNn { c }
(End definition for \clist_map_variable:NNn and \clist_map_variable:cNn These functions are documented
on page ??.)
```

\clist_map_break:

\clist_map_break:n

The break statements use the general __prg_map_break:Nn mechanism.

```

6121 \cs_new_nopar:Npn \clist_map_break:
6122   { \__prg_map_break:Nn \clist_map_break: { } }
6123 \cs_new_nopar:Npn \clist_map_break:n
6124   { \__prg_map_break:Nn \clist_map_break: }
(End definition for \clist_map_break: and \clist_map_break:n These functions are documented on
page 115.)
```

\clist_count:N

\clist_count:c

\clist_count:n

__clist_count:n

__clist_count:w

Counting the items in a comma list is done using the same approach as for other token count functions: turn each entry into a +1 then use integer evaluation to actually do the

mathematics. In the case of an n-type comma-list, we could of course use `\clist_map_function:nN`, but that is very slow, because it carefully removes spaces. Instead, we loop manually, and skip blank items (but not {}, hence the extra spaces).

```

6125 \cs_new:Npn \clist_count:N #1
6126 {
6127   \int_eval:n
6128   {
6129     0
6130     \clist_map_function:NN #1 \__clist_count:n
6131   }
6132 }
6133 \cs_generate_variant:Nn \clist_count:N { c }
6134 \cs_new:Npx \clist_count:n #1
6135 {
6136   \exp_not:N \int_eval:n
6137   {
6138     0
6139     \exp_not:N \__clist_count:w \c_space_tl
6140     #1 \exp_not:n { , \q_recursion_tail , \q_recursion_stop }
6141   }
6142 }
6143 \cs_new:Npn \__clist_count:n #1 { + \c_one }
6144 \cs_new:Npx \__clist_count:w #1 ,
6145 {
6146   \exp_not:n { \exp_args:Nf \quark_if_recursion_tail_stop:n } {#1}
6147   \exp_not:N \tl_if_blank:nF {#1} { + \c_one }
6148   \exp_not:N \__clist_count:w \c_space_tl
6149 }
```

(End definition for `\clist_count:N`, `\clist_count:c`, and `\clist_count:n`. These functions are documented on page ??.)

12.8 Viewing comma lists

`\clist_show:N` Apply the general `__msg_show_variable:Nnn`. In the case of an n-type comma-list, first store it in a scratch variable, then show that variable: The message takes care of omitting its name.

```

6150 \cs_new_protected:Npn \clist_show:N #1
6151 {
6152   \__msg_show_variable:Nnn #1 { clist }
6153   { \clist_map_function:NN #1 \__msg_show_item:n }
6154 }
6155 \cs_new_protected:Npn \clist_show:n #1
6156 {
6157   \clist_set:Nn \l__clist_internal_clist {#1}
6158   \clist_show:N \l__clist_internal_clist
6159 }
6160 \cs_generate_variant:Nn \clist_show:N { c }
(End definition for \clist_show:N and \clist_show:c. These functions are documented on page 116.)
```

12.9 Scratch comma lists

```
\l_tmpa_clist
\l_tmpb_clist
\g_tmpa_clist
\g_tmpb_clist
6161 \clist_new:N \l_tmpa_clist
6162 \clist_new:N \l_tmpb_clist
6163 \clist_new:N \g_tmpa_clist
6164 \clist_new:N \g_tmpb_clist
```

(End definition for `\l_tmpa_clist` and `\l_tmpb_clist`. These functions are documented on page 117.)

12.10 Deprecated interfaces

Deprecated on 2011-05-27, for removal by 2011-08-31.

`\clist_top>NN` These are old stack functions.

```
6165 {*deprecated}
6166 \cs_new_eq:NN \clist_top>NN \clist_get>NN
6167 \cs_new_eq:NN \clist_top:cN \clist_get:cN
6168 //deprecated
```

(End definition for `\clist_top>NN` and `\clist_top:cN`. These functions are documented on page ??.)

`\clist_remove_element:Nn` An older name for `\clist_remove_all:Nn`.

```
6169 {*deprecated}
6170 \cs_new_eq:NN \clist_remove_element:Nn \clist_remove_all:Nn
6171 \cs_new_eq:NN \clist_gremove_element:Nn \clist_gremove_all:Nn
6172 //deprecated
```

(End definition for `\clist_remove_element:Nn` and `\clist_gremove_element:Nn`. These functions are documented on page ??.)

`\clist_display:N` An older name for `\clist_show:N`.

```
6173 {*deprecated}
6174 \cs_new_eq:NN \clist_display:N \clist_show:N
6175 \cs_new_eq:NN \clist_display:c \clist_show:c
6176 //deprecated
```

(End definition for `\clist_display:N` and `\clist_display:c`. These functions are documented on page ??.)

Deprecated on 2011-09-05, for removal by 2011-12-31.

`\clist_trim_spaces:N` Since `clist` items are now always stripped from their surrounding spaces, it is redundant to provide these functions. The `_clist_trim_spaces:n` function is now internal, deprecated for use outside the kernel.

```
6177 {*deprecated}
6178 \cs_new_protected:Npn \clist_trim_spaces:N #1 { \clist_set:No #1 {\#1} }
6179 \cs_new_protected:Npn \clist_gtrim_spaces:N #1 { \clist_gset:No #1 {\#1} }
6180 \cs_generate_variant:Nn \clist_trim_spaces:N { c }
6181 \cs_generate_variant:Nn \clist_gtrim_spaces:N { c }
6182 //deprecated
```

(End definition for `\clist_trim_spaces:N` and others. These functions are documented on page ??.)

Deprecated on 2012-05-10, for removal by 2012-08-31.

```

\clist_if_eq_p:NN Simple copies from the token list variable material.
\clist_if_eq_p:Nc
\clist_if_eq_p:cN
\clist_if_eq_p:cc
\clist_if_eq:NNTF
\clist_if_eq:NcTF
\clist_if_eq:cNTF
\clist_if_eq:ccTF
\clist_length:N
\clist_length:c
\clist_length:n
6183 \prg_new_eq_conditional:NNn \clist_if_eq:NN \tl_if_eq:NN { p , T , F , TF }
6184 \prg_new_eq_conditional:NNn \clist_if_eq:Nc \tl_if_eq:Nc { p , T , F , TF }
6185 \prg_new_eq_conditional:NNn \clist_if_eq:cN \tl_if_eq:cN { p , T , F , TF }
6186 \prg_new_eq_conditional:NNn \clist_if_eq:cc \tl_if_eq:cc { p , T , F , TF }
(End definition for \clist_if_eq:NN and others. These functions are documented on page ??.)
Deprecation 2012-05-13 for removal by 2012-11-31.

\clist_if_eq:ccTF
\clist_length:N
\clist_length:c
\clist_length:n
6187 \cs_new_eq:NN \clist_length:N \clist_count:N
6188 \cs_new_eq:NN \clist_length:n \clist_count:c
6189 \cs_new_eq:NN \clist_length:c \clist_count:n
(End definition for \clist_length:N, \clist_length:c, and \clist_length:n These functions are documented on page ??.)
Deprecation 2012-05-19 for removal by 2012-11-31.

\clist_use:N
\clist_use:c
6190 \cs_new_eq:NN \clist_use:N \tl_use:N
6191 \cs_new_eq:NN \clist_use:c \tl_use:c
(End definition for \clist_use:N and \clist_use:c These functions are documented on page ??.)
6192 ⟨/initex | package⟩

```

13 l3prop implementation

The following test files are used for this code: *m3prop001*, *m3prop002*, *m3prop003*, *m3prop004*, *m3show001*.

```

6193 ⟨*initex | package⟩
6194 ⟨@@=prop⟩
6195 ⟨*package⟩
6196 \ProvidesExplPackage
6197 {\ExplFileName}{\ExplFileVersion}{\ExplFileDescription}
6198 \__expl_package_check:
6199 ⟨/package⟩

```

A property list is a macro whose top-level expansion is for the form

```

\q__prop ⟨key1⟩ \q__prop {⟨value1⟩}
...
\q__prop ⟨keyn⟩ \q__prop {⟨valuen⟩}
\q__prop

```

where the trailing \q__prop is always present for performance reasons: this means that empty property lists are not actually empty.

\q__prop A private quark is used as a marker between entries.

```

6200 \quark_new:N \q__prop

```

(End definition for `\q_prop`)

`\c_empty_prop` An empty prop contains exactly one `\q_prop`.

6201 `\tl_const:Nn \c_empty_prop { \q_prop }`

(End definition for `\c_empty_prop` This variable is documented on page 123.)

13.1 Allocation and initialisation

`\prop_new:N` Internally, property lists are token lists, but an empty prop is not an empty tl, so we
`\prop_new:c` need to do things by hand.

6202 `\cs_new_protected:Npn \prop_new:N #1 { \cs_new_eq:NN #1 \c_empty_prop }`
6203 `\cs_new_protected:Npn \prop_new:c #1 { \cs_new_eq:cN {#1} \c_empty_prop }`

(End definition for `\prop_new:N` and `\prop_new:c` These functions are documented on page ??.)

`\prop_clear:N` The same idea for clearing

6204 `\cs_new_protected:Npn \prop_clear:N #1 { \cs_set_eq:NN #1 \c_empty_prop }`
6205 `\cs_generate_variant:Nn \prop_clear:N { c }`
6206 `\cs_new_protected:Npn \prop_gclear:N #1 { \cs_gset_eq:NN #1 \c_empty_prop }`
6207 `\cs_generate_variant:Nn \prop_gclear:N { c }`

(End definition for `\prop_clear:N` and `\prop_clear:c` These functions are documented on page ??.)

`\prop_clear_new:N` Once again a simple copy from the token list functions.

6208 `\cs_new_protected:Npn \prop_clear_new:N #1`
6209 `{ \prop_if_exist:NTF #1 { \prop_clear:N #1 } { \prop_new:N #1 } }`
6210 `\cs_generate_variant:Nn \prop_clear_new:N { c }`
6211 `\cs_new_protected:Npn \prop_gclear_new:N #1`
6212 `{ \prop_if_exist:NTF #1 { \prop_gclear:N #1 } { \prop_new:N #1 } }`
6213 `\cs_generate_variant:Nn \prop_gclear_new:N { c }`

(End definition for `\prop_clear_new:N` and `\prop_clear_new:c` These functions are documented on page ??.)

`\prop_set_eq:NN` Once again, these are simply copies from the token list functions.

6214 `\cs_new_eq:NN \prop_set_eq:NN \tl_set_eq:NN`
6215 `\cs_new_eq:NN \prop_set_eq:Nc \tl_set_eq:Nc`
6216 `\cs_new_eq:NN \prop_set_eq:cN \tl_set_eq:cN`
6217 `\cs_new_eq:NN \prop_set_eq:cc \tl_set_eq:cc`
6218 `\cs_new_eq:NN \prop_gset_eq:NN \tl_gset_eq:NN`
6219 `\cs_new_eq:NN \prop_gset_eq:Nc \tl_gset_eq:Nc`
6220 `\cs_new_eq:NN \prop_gset_eq:cN \tl_gset_eq:cN`
6221 `\cs_new_eq:NN \prop_gset_eq:cc \tl_gset_eq:cc`

(End definition for `\prop_set_eq:NN` and others. These functions are documented on page ??.)

We can now initialize the scratch variables.

6222 `\prop_new:N \l_tmpa_prop`
6223 `\prop_new:N \l_tmpb_prop`
6224 `\prop_new:N \g_tmpa_prop`
6225 `\prop_new:N \g_tmpb_prop`

(End definition for `\l_tmpa_prop` and `\l_tmpb_prop` These functions are documented on page 123.)

13.2 Accessing data in property lists

```
\__prop_split:NnTF
\__prop_split_aux:NnTF
\__prop_split_aux:nnnn
\__prop_split_aux:w
```

This function is used by most of the module, and hence must be fast. The aim here is to split a property list at a given key into the part before the key–value pair, the value associated with the key and the part after the key–value pair. To do this, the key is first detokenized (to avoid repeatedly doing this), then a delimited function is constructed to match the key. It will match $\backslash q_prop \langle \text{detokenized key} \rangle \backslash q_prop \{ \langle \text{value} \rangle \} \langle \text{extra argument} \rangle$, effectively separating an $\langle \text{extract}_1 \rangle$ before the key in the property list and an $\langle \text{extract}_2 \rangle$ after the key.

If the key is present in the property list, then $\langle \text{extra argument} \rangle$ is simply $\backslash q_prop$, and $__prop_split_aux:nnnn$ will gobble this and the false branch (#4), leaving the correct code on the input stream. More precisely, it leaves the user code (true branch), followed by three groups, $\{ \langle \text{extract}_1 \rangle \} \{ \langle \text{value} \rangle \} \{ \langle \text{extract}_2 \rangle \}$. In order for $\langle \text{extract}_1 \rangle \langle \text{extract}_2 \rangle$ to be a well-formed property list, $\langle \text{extract}_1 \rangle$ has a leading and trailing $\backslash q_prop$, retaining exactly the structure of a property list, while $\langle \text{extract}_2 \rangle$ omits the leading $\backslash q_prop$.

If the key is not there, then $\langle \text{extra argument} \rangle$ is $? \use_{ii}:nn \{ \}$, and $__prop_split_aux:nnnn ? \use_{ii}:nn \{ \}$ removes the three brace groups that just follow. Then $\use_{ii}:nn$ removes the true branch, leaving the false branch, with no trailing material.

```
6226 \cs_new_protected:Npn \__prop_split:NnTF #1#2
6227   { \exp_args:NNo \__prop_split_aux:NnTF #1 { \tl_to_str:n {#2} } }
6228 \cs_new_protected:Npn \__prop_split_aux:NnTF #1#2
6229   {
6230     \cs_set_protected:Npn \__prop_split_aux:w
6231       ##1 \q_prop ##2 ##3 ##4 \q_mark ##5 \q_stop
6232       { \__prop_split_aux:nnnn ##3 { ##1 \q_prop } {##2} {##4} } }
6233     \exp_after:WN \__prop_split_aux:w #1 \q_mark
6234       \q_prop #2 \q_prop { } { ? \use_{ii}:nn { } } \q_mark \q_stop
6235   }
6236 \cs_new:Npn \__prop_split_aux:nnnn #1#2#3#4 { #3 #2 }
6237 \cs_new_protected:Npn \__prop_split_aux:w { }
```

(End definition for $__prop_split:NnTF$. This function is documented on page 123.)

```
\prop_remove:Nn
\prop_remove:NV
\prop_remove:cn
\prop_remove:cV
\prop_gremove:Nn
\prop_gremove:NV
\prop_gremove:cn
\prop_gremove:cV
\__prop_remove>NNnnn
```

Deleting from a property starts by splitting the list. If the key is present in the property list, the returned value is ignored. If the key is missing, nothing happens.

```
6238 \cs_new_protected:Npn \prop_remove:Nn #1#2
6239   { \__prop_split:NnTF #1 {#2} { \__prop_remove:NNnnn \tl_set:Nn #1 } { } }
6240 \cs_new_protected:Npn \prop_gremove:Nn #1#2
6241   { \__prop_split:NnTF #1 {#2} { \__prop_remove:NNnnn \tl_gset:Nn #1 } { } }
6242 \cs_new_protected:Npn \__prop_remove:NNnn #1#2#3#4#5
6243   { #1 #2 { #3 #5 } }
6244 \cs_generate_variant:Nn \prop_remove:Nn { NV }
6245 \cs_generate_variant:Nn \prop_remove:Nn { c , cV }
6246 \cs_generate_variant:Nn \prop_gremove:Nn { NV }
6247 \cs_generate_variant:Nn \prop_gremove:Nn { c , cV }
```

(End definition for $\prop_remove:Nn$ and others. These functions are documented on page ??.)

\prop_get:NnN
\prop_get:NVN
\prop_get:NoN
\prop_get:cnN
\prop_get:cVN
\prop_get:coN
_prop_get:Nnnn

Getting an item from a list is very easy: after splitting, if the key is in the property list, just set the token list variable to the return value, otherwise to `\q_no_value`.

```

6248 \cs_new_protected:Npn \prop_get:NnN #1#2#3
6249 {
6250     \__prop_split:NnTF #1 {#2}
6251     { \__prop_get:Nnnn #3 }
6252     { \tl_set:Nn #3 { \q_no_value } }
6253 }
6254 \cs_new_protected:Npn \_prop_get:Nnnn #1#2#3#4
6255 { \tl_set:Nn #1 {#3} }
6256 \cs_generate_variant:Nn \prop_get:NnN { NV , No }
6257 \cs_generate_variant:Nn \prop_get:NnN { c , cV , co }
(End definition for \prop_get:NnN and others. These functions are documented on page ??.)

```

\prop_pop:NnN
\prop_pop:NoN
\prop_pop:cnN
\prop_pop:coN
\prop_gpop:NnN
\prop_gpop:NoN
\prop_gpop:cnN
\prop_gpop:coN
_prop_pop>NNNnnn

Popping a value also starts by doing the split. If the key is present, save the value in the token list and update the property list as when deleting. If the key is missing, save `\q_no_value` in the token list.

```

6258 \cs_new_protected:Npn \prop_pop:NnN #1#2#3
6259 {
6260     \__prop_split:NnTF #1 {#2}
6261     { \__prop_pop:NNNnnn \tl_set:Nn #1 #3 }
6262     { \tl_set:Nn #3 { \q_no_value } }
6263 }
6264 \cs_new_protected:Npn \prop_gpop:NnN #1#2#3
6265 {
6266     \__prop_split:NnTF #1 {#2}
6267     { \__prop_pop:NNNnnn \tl_gset:Nn #1 #3 }
6268     { \tl_set:Nn #3 { \q_no_value } }
6269 }
6270 \cs_new_protected:Npn \_prop_pop:NNNnnn #1#2#3#4#5#6
6271 {
6272     \tl_set:Nn #3 {#5}
6273     #1 #2 { #4 #6 }
6274 }
6275 \cs_generate_variant:Nn \prop_pop:NnN { No }
6276 \cs_generate_variant:Nn \prop_pop:NnN { c , co }
6277 \cs_generate_variant:Nn \prop_gpop:NnN { No }
6278 \cs_generate_variant:Nn \prop_gpop:NnN { c , co }
(End definition for \prop_pop:NnN and others. These functions are documented on page ??.)

```

\prop_pop:NnNTF
\prop_pop:cnNTF
\prop_gpop:NnNTF
\prop_gpop:cnNTF
_prop_pop_true>NNNnnn

Popping an item from a property list, keeping track of whether the key was present or not, is implemented as a conditional. If the key was missing, neither the property list, nor the token list are altered. Otherwise, `\prg_return_true:` is used after the assignments.

```

6279 \prg_new_protected_conditional:Npnn \prop_pop:NnN #1#2#3 { T , F , TF }
6280 {
6281     \__prop_split:NnTF #1 {#2}
6282     { \__prop_pop_true>NNNnnn \tl_set:Nn #1 #3 }
6283     { \prg_return_false: }

```

```

6284   }
6285 \prg_new_protected_conditional:Npnn \prop_gpop:NnN #1#2#3 { T , F , TF }
6286 {
6287   \__prop_split:NnTF #1 {#2}
6288   { \__prop_pop_true:NNNnnn \tl_gset:Nn #1 #3 }
6289   { \prg_return_false: }
6290 }
6291 \cs_new_protected:Npn \__prop_pop_true:NNNnnn #1#2#3#4#5#6
6292 {
6293   \tl_set:Nn #3 {#5}
6294   #1 #2 { #4 #6 }
6295   \prg_return_true:
6296 }
6297 \cs_generate_variant:Nn \prop_pop:NnNT { c }
6298 \cs_generate_variant:Nn \prop_pop:NnNF { c }
6299 \cs_generate_variant:Nn \prop_pop:NnNTF { c }
6300 \cs_generate_variant:Nn \prop_gpop:NnNT { c }
6301 \cs_generate_variant:Nn \prop_gpop:NnNF { c }
6302 \cs_generate_variant:Nn \prop_gpop:NnNTF { c }

```

(End definition for `\prop_pop:NnN` and others. These functions are documented on page ??.)

\prop_put:Nnn Putting a key–value pair in a property list starts by splitting to remove any existing value. If the `<key>` was absent, append the new key–value pair. Otherwise, the property list is reconstructed from the two remaining parts #5 and #7, and the updated entry. The updated entry is placed at the same spot as the original `<key>` in the property list, preserving the order of entries.

\prop_put:NnV

\prop_put:Nno

\prop_put:Nnx

\prop_put:NVn

\prop_put:NVV

\prop_put:Non

\prop_put:Noo

\prop_put:cnn

\prop_put:cnV

\prop_put:cno

\prop_put:cnx

\prop_put:cVn

\prop_put:cVV

\prop_put:con

\prop_put:coo

\prop_gput:Nnn

\prop_gput:NnV

\prop_gput:Nno

\prop_gput:Nnx

\prop_gput:NVn

\prop_gput:NVV

\prop_gput:Non

\prop_gput:Noo

\prop_gput:cnn

\prop_gput:cnV

\prop_gput:cno

\prop_gput:cnx

\prop_gput:cVn

\prop_gput:cVV

\prop_gput:con

\prop_gput:coo

__prop_put:NNNnnn

__prop_put:NNnnnnnn

```

6326 \cs_generate_variant:Nn \prop_gput:Nnn
6327 { NnV , Nno , Nnx , NV , NVV , No , Noo }
6328 \cs_generate_variant:Nn \prop_gput:Nnn
6329 { c , cnV , cno , cnx , cV , cVV , co , coo }
(End definition for \prop_put:Nnn and others. These functions are documented on page ??.)
```

\prop_put_if_new:Nnn
\prop_put_if_new:cnn
\prop_gput_if_new:Nnn

\prop_gput_if_new:cnn

_prop_put_if_new:NNnn

Adding conditionally also splits. If the key is already present, the three brace groups given by _prop_split:NnTF are removed. If the key is new, then the value is added, being careful to convert the key to a string using \tl_to_str:n.

```

6330 \cs_new_protected_nopar:Npn \prop_put_if_new:Nnn
6331 { \_prop_put_if_new>NNnn \tl_put_right:Nx }
6332 \cs_new_protected_nopar:Npn \prop_gput_if_new:Nnn
6333 { \_prop_put_if_new>NNnn \tl_gput_right:Nx }
6334 \cs_new_protected:Npn \_prop_put_if_new>NNnn #1#2#3#4
6335 {
6336 \_prop_split:NnTF #2 {#3}
6337 { \use_none:nnn }
6338 {
6339 #1 #2
6340 { \tl_to_str:n {#3} \exp_not:n { \q__prop {#4} \q__prop } }
6341 }
6342 }
6343 \cs_generate_variant:Nn \prop_put_if_new:Nnn { c }
6344 \cs_generate_variant:Nn \prop_gput_if_new:Nnn { c }
(End definition for \prop_put_if_new:Nnn and \prop_put_if_new:cnn These functions are documented on page ??.)
```

13.3 Property list conditionals

\prop_if_exist:p:N

\prop_if_exist_p:c

\prop_if_exist:NTF

\prop_if_exist:cTF

Copies of the cs functions defined in l3basics.

```

6345 \cs_new_eq:NN \prop_if_exist:NTF \cs_if_exist:NTF
6346 \cs_new_eq:NN \prop_if_exist:NT \cs_if_exist:NT
6347 \cs_new_eq:NN \prop_if_exist:NF \cs_if_exist:NF
6348 \cs_new_eq:NN \prop_if_exist_p:N \cs_if_exist_p:N
6349 \cs_new_eq:NN \prop_if_exist:cTF \cs_if_exist:cTF
6350 \cs_new_eq:NN \prop_if_exist:cT \cs_if_exist:cT
6351 \cs_new_eq:NN \prop_if_exist:cF \cs_if_exist:cF
6352 \cs_new_eq:NN \prop_if_exist_p:c \cs_if_exist_p:c
```

(End definition for \prop_if_exist:N and \prop_if_exist:c These functions are documented on page ??.)

\prop_if_empty_p:N

\prop_if_empty_p:c

\prop_if_empty:NTF

\prop_if_empty:cTF

The test here uses \c_empty_prop as it is not really empty!

```

6353 \prg_new_conditional:Npnn \prop_if_empty:N #1 { p, T , F , TF }
6354 {
6355 \if_meaning:w #1 \c_empty_prop
6356 \prg_return_true:
6357 \else:
6358 \prg_return_false:
6359 \fi:
```

```

6360    }
6361 \cs_generate_variant:Nn \prop_if_empty_p:N {c}
6362 \cs_generate_variant:Nn \prop_if_empty:NTF {c}
6363 \cs_generate_variant:Nn \prop_if_empty:NT {c}
6364 \cs_generate_variant:Nn \prop_if_empty:NF {c}
(End definition for \prop_if_empty:N and \prop_if_empty:c These functions are documented on page
??.)

```

\prop_if_in_p:Nn
\prop_if_in_p:NV
\prop_if_in_p:No
\prop_if_in_p:cn
\prop_if_in_p:cV
\prop_if_in_p:co
\prop_if_in:NnTF
\prop_if_in:NVTF
\prop_if_in:NoTF
\prop_if_in:cnTF
\prop_if_in:cVTF
\prop_if_in:coTF

__prop_if_in:nwn
__prop_if_in:N

```

\prg_new_protected_conditional:Npnn \prop_if_in:Nn #1 #2
{
  \@@_split:NnTF #1 {#2}
  {
    \prg_return_true:
    \use_none:nnn
  }
  { \prg_return_false: }
}

```

but **__prop_split:NnTF** is non-expandable.

Instead, the key is compared to each key in turn using **\str_if_eq_x:nn**, which is expandable. To terminate the mapping, we add the key that is search for at the end of the property list. This second **\tl_to_str:n** is not expanded at the start, but only when included in the **\str_if_eq_x:nn**. It cannot make the breaking mechanism choke, because the arbitrary token list material is enclosed in braces. When ending, we test the next token: it is either **\q_prop** or **\q_recursion_tail** in the case of a missing key. Here, **\prop_map_function:NN** is not sufficient for the mapping, since it can only map a single token, and cannot carry the key that is searched for.

```

6365 \prg_new_conditional:Npnn \prop_if_in:Nn #1#2 { p , T , F , TF }
6366 {
  \exp_last_unbraced:Noo \_\_prop_if_in:nwn
  { \tl_to_str:n {#2} } #1
  \tl_to_str:n {#2} \q\_prop { }
6369 \q_recursion_tail % could be any cs != \q\_prop
  \_\_prg_break_point:
6370 }
6371 \cs_new:Npn \_\_prop_if_in:nwn #1 \q\_prop #2 \q\_prop #3
6372 {
  \str_if_eq_x:nnTF {#1} {#2}
  { \_\_prop_if_in:N }
  { \_\_prop_if_in:nwn {#1} }
6373 }
6374 \cs_new:Npn \_\_prop_if_in:N #1
6375 {
  \if_meaning:w \q\_prop #1
  \prg_return_true:
6376 \else:
6377 
```

```

6384     \prg_return_false:
6385     \fi:
6386     \__prg_break:
6387 }
6388 \cs_generate_variant:Nn \prop_if_in_p:Nn { NV , No }
6389 \cs_generate_variant:Nn \prop_if_in_p:Nn { c , cV , co }
6390 \cs_generate_variant:Nn \prop_if_in:NnT { NV , No }
6391 \cs_generate_variant:Nn \prop_if_in:NnT { c , cV , co }
6392 \cs_generate_variant:Nn \prop_if_in:NnF { NV , No }
6393 \cs_generate_variant:Nn \prop_if_in:NnF { c , cV , co }
6394 \cs_generate_variant:Nn \prop_if_in:NnTF { NV , No }
6395 \cs_generate_variant:Nn \prop_if_in:NnTF { c , cV , co }

(End definition for \prop_if_in:Nn and others. These functions are documented on page ??.)
```

13.4 Recovering values from property lists with branching

`\prop_get:NnNTF` Getting the value corresponding to a key, keeping track of whether the key was present or not, is implemented as a conditional (with side effects). If the key was absent, the token list is not altered.

```

\prop_get:NVNTF
\prop_get:NoNTF
\prop_get:cNNTF
\prop_get:cVNTF
\prop_get:c0NTF
\__prop_get_true:Nnnn

6396 \prg_new_protected_conditional:Npnn \prop_get:NnN #1#2#3 { T , F , TF }
6397 {
6398     \__prop_split:NnTF #1 {#2}
6399     { \__prop_get_true:Nnnn #3 }
6400     { \prg_return_false: }
6401 }
6402 \cs_new_protected:Npn \__prop_get_true:Nnnn #1#2#3#4
6403 {
6404     \tl_set:Nn #1 {#3}
6405     \prg_return_true:
6406 }
6407 \cs_generate_variant:Nn \prop_get:NnNT { NV , No }
6408 \cs_generate_variant:Nn \prop_get:NnNF { NV , No }
6409 \cs_generate_variant:Nn \prop_get:NnNTF { NV , No }
6410 \cs_generate_variant:Nn \prop_get:NnNT { c , cV , co }
6411 \cs_generate_variant:Nn \prop_get:NnNF { c , cV , co }
6412 \cs_generate_variant:Nn \prop_get:NnNTF { c , cV , co }

(End definition for \prop_get:NnN and others. These functions are documented on page ??.)
```

13.5 Mapping to property lists

`\prop_map_function>NN` The fastest way to do a recursion here would be to use an `\if_meaning:w` test: the keys are strings, and thus cannot match the marker `\q_recursion_tail`.

```

\prop_map_function:Nc
\prop_map_function:cN
\prop_map_function:cc
\__prop_map_function:Nw

6413 \cs_new:Npn \prop_map_function:NN #1#2
6414 {
6415     \exp_last_unbraced:NNo \__prop_map_function:Nwn #2
6416     #1 \q_recursion_tail \q_prop { }
6417     \__prg_break_point:Nn \prop_map_break: { }
6418 }
```

```

6419 \cs_new:Npn \__prop_map_function:Nwn #1 \q_ prop #2 \q_ prop #3
6420 {
6421     \__quark_if_recursion_tail_break:nN {#2} \prop_map_break:
6422     #1 {#2} {#3}
6423     \__prop_map_function:Nwn #1
6424 }
6425 \cs_generate_variant:Nn \prop_map_function:NN { Nc }
6426 \cs_generate_variant:Nn \prop_map_function:NN { c , cc }
(End definition for \prop_map_function:NN and others. These functions are documented on page ??.)
```

\prop_map_inline:Nn Mapping in line requires a nesting level counter.

```

6427 \cs_new_protected:Npn \prop_map_inline:Nn #1#2
6428 {
6429     \int_gincr:N \g__prg_map_int
6430     \cs_gset:cpn { __prg_map_ \int_use:N \g__prg_map_int :w } ##1##2 {#2}
6431     \exp_last_unbraced:Nco \__prop_map_function:Nwn
6432     { __prg_map_ \int_use:N \g__prg_map_int :w }
6433     #1
6434     \q_recursion_tail \q_ prop { }
6435     \__prg_break_point:Nn \prop_map_break: { \int_gdecr:N \g__prg_map_int }
6436 }
6437 \cs_generate_variant:Nn \prop_map_inline:Nn { c }
(End definition for \prop_map_inline:Nn and \prop_map_inline:cn These functions are documented on page ??.)
```

\prop_map_break: The break statements are based on the general __prg_map_break:Nn.

\prop_map_break:n

```

6438 \cs_new_nopar:Npn \prop_map_break:
6439     { \__prg_map_break:Nn \prop_map_break: { } }
6440 \cs_new_nopar:Npn \prop_map_break:n
6441     { \__prg_map_break:Nn \prop_map_break: }
(End definition for \prop_map_break: This function is documented on page 122.)
```

13.6 Viewing property lists

\prop_show:N Apply the general __msg_show_variable:Nnn. Contrarily to sequences and comma lists, we use __msg_show_item:nn to format both the key and the value for each pair.

```

6442 \cs_new_protected:Npn \prop_show:N #1
6443 {
6444     \__msg_show_variable:Nnn #1 { prop }
6445     { \prop_map_function:NN #1 \__msg_show_item:nn }
6446 }
6447 \cs_generate_variant:Nn \prop_show:N { c }
(End definition for \prop_show:N and \prop_show:c These functions are documented on page ??.)
```

13.7 Deprecated interfaces

Deprecated on 2011-05-27, for removal by 2011-08-31.

\prop_display:N An older name for \prop_show:N.

\prop_display:c

```
6448 {*deprecated}
6449 \cs_new_eq:NN \prop_display:N \prop_show:N
6450 \cs_new_eq:NN \prop_display:c \prop_show:c
6451 /*deprecated)
(End definition for \prop_display:N and \prop_display:c These functions are documented on page ??.)
```

\prop_gget:NnN Getting globally is no longer supported: this is a conceptual change, so the necessary code for the transition is provided directly.

```
6452 {*deprecated}
6453 \tl_new:N \l__prop_internal_tl
6454 \cs_new_protected:Npn \prop_gget:NnN #1#2#3
6455 {
  \prop_get:NnN #1 {#2} \l__prop_internal_tl
  \tl_gset_eq:NN #3 \l__prop_internal_tl
}
6459 \cs_generate_variant:Nn \prop_gget:NnN { NV }
6460 \cs_generate_variant:Nn \prop_gget:NnN { c , cV }
6461 /*deprecated)
(End definition for \prop_gget:NnN and others. These functions are documented on page ??.)
```

\prop_get_gdel:NnN This name seems very odd.

```
6462 {*deprecated}
6463 \cs_new_eq:NN \prop_get_gdel:NnN \prop_gpop:NnN
6464 /*deprecated)
```

(End definition for \prop_get_gdel:NnN This function is documented on page ??.)

\prop_if_in:ccTF A hang-over from an ancient implementation

```
6465 {*deprecated}
6466 \cs_generate_variant:Nn \prop_if_in:NnT { cc }
6467 \cs_generate_variant:Nn \prop_if_in:NnF { cc }
6468 \cs_generate_variant:Nn \prop_if_in:NnTF { cc }
6469 /*deprecated)
```

(End definition for \prop_if_in:ccTF This function is documented on page ??.)

\prop_gput:ccx Another one.

```
6470 {*deprecated}
6471 \cs_generate_variant:Nn \prop_gput:Nnn { ccx }
6472 /*deprecated)
```

(End definition for \prop_gput:ccx This function is documented on page ??.)

```
\prop_if_eq_p:NN These ones do no even make sense!
\prop_if_eq_p:Nc
\prop_if_eq_p:cN
\prop_if_eq_p:cc
\prop_if_eq:NNTF
\prop_if_eq:NcTF
\prop_if_eq:cNTF
\prop_if_eq:ccTF
```

(End definition for \prop_if_eq:NN and others. These functions are documented on page ??.)

Deprecated on 2012-05-12, for removal by 2012-11-30.

```
\prop_del:Nn
\prop_del:NV
\prop_del:cn
\prop_del:cV
\prop_gdel:Nn
\prop_gdel:NV
\prop_gdel:cn
\prop_gdel:cV
```

(End definition for \prop_del:Nn and others. These functions are documented on page ??.)

6487 ⟨/initex | package⟩

14 l3box implementation

```
6488 ⟨*initex | package⟩
6489 ⟨@@=box⟩
6490 ⟨*package⟩
6491 \ProvidesExplPackage
6492 {\ExplFileName}{\ExplFileVersion}{\ExplFileDescription}
6493 \__expl_package_check:
6494 ⟨/package⟩
```

The code in this module is very straight forward so I'm not going to comment it very extensively.

14.1 Creating and initialising boxes

The following test files are used for this code: m3box001.lvt.

\box_new:N Defining a new ⟨box⟩ register: remember that box 255 is not generally available.

```
\box_new:c
6495 ⟨*package⟩
6496 \cs_new_protected:Npn \box_new:N #1
6497 {
6498     \__chk_if_free_cs:N #1
6499     \newbox #1
6500 }
6501 ⟨/package⟩
6502 \cs_generate_variant:Nn \box_new:N { c }
```

\box_clear:N Clear a *⟨box⟩* register.
\box_clear:c
\box_gclear:N
\box_gclear:c

```

6503 \cs_new_protected:Npn \box_clear:N #1
6504 { \box_set_eq:NN #1 \c_empty_box }
6505 \cs_new_protected:Npn \box_gclear:N #1
6506 { \box_gset_eq:NN #1 \c_empty_box }
6507 \cs_generate_variant:Nn \box_clear:N { c }
6508 \cs_generate_variant:Nn \box_gclear:N { c }

```

\box_clear_new:N Clear or new.
\box_clear_new:c
\box_gclear_new:N
\box_gclear_new:c

```

6509 \cs_new_protected:Npn \box_clear_new:N #1
6510 { \box_if_exist:NTF #1 { \box_clear:N #1 } { \box_new:N #1 } }
6511 \cs_new_protected:Npn \box_gclear_new:N #1
6512 { \box_if_exist:NTF #1 { \box_gclear:N #1 } { \box_new:N #1 } }
6513 \cs_generate_variant:Nn \box_clear_new:N { c }
6514 \cs_generate_variant:Nn \box_gclear_new:N { c }

```

\box_set_eq:NN Assigning the contents of a box to be another box.
\box_set_eq:cN
\box_set_eq:Nc
\box_set_eq:cc
\box_gset_eq:NN
\box_gset_eq:cN
\box_gset_eq:Nc
\box_gset_eq:cc
\box_set_eq_clear:NN
\box_set_eq_clear:cN
\box_set_eq_clear:Nc
\box_set_eq_clear:cc

```

6515 \cs_new_protected:Npn \box_set_eq:NN #1#2
6516 { \tex_setbox:D #1 \tex_copy:D #2 }
6517 \cs_new_protected:Npn \box_gset_eq:NN
6518 { \tex_global:D \box_set_eq:NN }
6519 \cs_generate_variant:Nn \box_set_eq:NN { c , Nc , cc }
6520 \cs_generate_variant:Nn \box_gset_eq:NN { c , Nc , cc }

```

\box_set_eq_clear:NN Assigning the contents of a box to be another box. This clears the second box globally (that's how TeX does it).
\box_set_eq_clear:cN
\box_set_eq_clear:Nc
\box_set_eq_clear:cc

```

6521 \cs_new_protected:Npn \box_set_eq_clear:NN #1#2
6522 { \tex_setbox:D #1 \tex_box:D #2 }
6523 \cs_new_protected:Npn \box_gset_eq_clear:NN
6524 { \tex_global:D \box_set_eq_clear:NN }
6525 \cs_generate_variant:Nn \box_set_eq_clear:NN { c , Nc , cc }
6526 \cs_generate_variant:Nn \box_gset_eq_clear:NN { c , Nc , cc }

```

\box_if_exist_p:N Copies of the cs functions defined in l3basics.
\box_if_exist_p:c
\box_if_exist:NTF
\box_if_exist:cTF

```

6527 \cs_new_eq:NN \box_if_exist:NTF \cs_if_exist:NTF
6528 \cs_new_eq:NN \box_if_exist:NT \cs_if_exist:NT
6529 \cs_new_eq:NN \box_if_exist:NF \cs_if_exist:NF
6530 \cs_new_eq:NN \box_if_exist_p:N \cs_if_exist_p:N
6531 \cs_new_eq:NN \box_if_exist:cTF \cs_if_exist:cTF
6532 \cs_new_eq:NN \box_if_exist:cT \cs_if_exist:cT
6533 \cs_new_eq:NN \box_if_exist:cF \cs_if_exist:cF
6534 \cs_new_eq:NN \box_if_exist_p:c \cs_if_exist_p:c

```

14.2 Measuring and setting box dimensions

`\box_ht:N` Accessing the height, depth, and width of a $\langle box \rangle$ register.

```
6535 \cs_new_eq:NN \box_ht:N \tex_ht:D
6536 \cs_new_eq:NN \box_dp:N \tex_dp:D
6537 \cs_new_eq:NN \box_wd:N \tex_wd:D
6538 \cs_generate_variant:Nn \box_ht:N { c }
6539 \cs_generate_variant:Nn \box_dp:N { c }
6540 \cs_generate_variant:Nn \box_wd:N { c }
```

`\box_set_ht:Nn` Measuring is easy: all primitive work. These primitives are not expandable, so the derived functions are not either.

```
6541 \cs_new_protected:Npn \box_set_dp:Nn #1#2
6542   { \box_dp:N #1 \_dim_eval:w #2 \_dim_eval_end: }
6543 \cs_new_protected:Npn \box_set_ht:Nn #1#2
6544   { \box_ht:N #1 \_dim_eval:w #2 \_dim_eval_end: }
6545 \cs_new_protected:Npn \box_set_wd:Nn #1#2
6546   { \box_wd:N #1 \_dim_eval:w #2 \_dim_eval_end: }
6547 \cs_generate_variant:Nn \box_set_ht:Nn { c }
6548 \cs_generate_variant:Nn \box_set_dp:Nn { c }
6549 \cs_generate_variant:Nn \box_set_wd:Nn { c }
```

14.3 Using boxes

`\box_use_clear:N` Using a $\langle box \rangle$. These are just TeX primitives with meaningful names.

```
6550 \cs_new_eq:NN \box_use_clear:N \tex_box:D
6551 \cs_new_eq:NN \box_use:N \tex_copy:D
6552 \cs_generate_variant:Nn \box_use_clear:N { c }
6553 \cs_generate_variant:Nn \box_use:N { c }
```

`\box_move_left:nn` Move box material in different directions.

```
6554 \cs_new_protected:Npn \box_move_left:nn #1#2
6555   { \tex_moveleft:D \_dim_eval:w #1 \_dim_eval_end: #2 }
6556 \cs_new_protected:Npn \box_move_right:nn #1#2
6557   { \tex_moveright:D \_dim_eval:w #1 \_dim_eval_end: #2 }
6558 \cs_new_protected:Npn \box_move_up:nn #1#2
6559   { \tex_raise:D \_dim_eval:w #1 \_dim_eval_end: #2 }
6560 \cs_new_protected:Npn \box_move_down:nn #1#2
6561   { \tex_lower:D \_dim_eval:w #1 \_dim_eval_end: #2 }
```

14.4 Box conditionals

`\if_hbox:N` The primitives for testing if a $\langle box \rangle$ is empty/void or which type of box it is.

```
6562 \cs_new_eq:NN \if_hbox:N \tex_ifhbox:D
6563 \cs_new_eq:NN \if_vbox:N \tex_ifvbox:D
6564 \cs_new_eq:NN \if_box_empty:N \tex_ifvoid:D
```

```

\box_if_horizontal_p:N
\box_if_horizontal_p:c
\box_if_horizontal:NTF
\box_if_horizontal:cTF
\box_if_vertical_p:N
\box_if_vertical_p:c
\box_if_vertical:NTF
\box_if_vertical:cTF

6565 \prg_new_conditional:Npnn \box_if_horizontal:N #1 { p , T , F , TF }
6566   { \if_hbox:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
6567 \prg_new_conditional:Npnn \box_if_vertical:N #1 { p , T , F , TF }
6568   { \if_vbox:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
6569 \cs_generate_variant:Nn \box_if_horizontal_p:N { c }
6570 \cs_generate_variant:Nn \box_if_horizontal:NTF { c }
6571 \cs_generate_variant:Nn \box_if_horizontal:NTF { c }
6572 \cs_generate_variant:Nn \box_if_horizontal:NTF { c }
6573 \cs_generate_variant:Nn \box_if_vertical_p:N { c }
6574 \cs_generate_variant:Nn \box_if_vertical:NTF { c }
6575 \cs_generate_variant:Nn \box_if_vertical:NTF { c }
6576 \cs_generate_variant:Nn \box_if_vertical:NTF { c }

```

\box_if_empty_p:N Testing if a *box* is empty/void.

```

\box_if_empty_p:c
\box_if_empty:NTF
\box_if_empty:cTF

6577 \prg_new_conditional:Npnn \box_if_empty:N #1 { p , T , F , TF }
6578   { \if_box_empty:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
6579 \cs_generate_variant:Nn \box_if_empty_p:N { c }
6580 \cs_generate_variant:Nn \box_if_empty:NTF { c }
6581 \cs_generate_variant:Nn \box_if_empty:NTF { c }
6582 \cs_generate_variant:Nn \box_if_empty:NTF { c }

```

(End definition for \box_new:N and \box_new:c These functions are documented on page ??.)

14.5 The last box inserted

\box_set_to_last:N Set a box to the previous box.

```

\box_set_to_last:c
\box_gset_to_last:N
\box_gset_to_last:c

6583 \cs_new_protected:Npn \box_set_to_last:N #1
6584   { \tex_setbox:D #1 \tex_lastbox:D }
6585 \cs_new_protected:Npn \box_gset_to_last:N
6586   { \tex_global:D \box_set_to_last:N }
6587 \cs_generate_variant:Nn \box_set_to_last:N { c }
6588 \cs_generate_variant:Nn \box_gset_to_last:N { c }

```

(End definition for \box_set_to_last:N and \box_set_to_last:c These functions are documented on page ??.)

14.6 Constant boxes

\c_empty_box

```

6589 <*package>
6590 \cs_new_eq:NN \c_empty_box \voidb@x
6591 </package>
6592 <*initex>
6593 \box_new:N \c_empty_box
6594 </initex>

```

(End definition for \c_empty_box This variable is documented on page 127.)

14.7 Scratch boxes

```
\l_tmpa_box Reuse the LATEX 2 $\varepsilon$  scratch box in package mode.  
\l_tmpb_box  
6595 {*package}  
6596 \cs_new_eq:NN \l_tmpa_box \@tempboxa  
6597 {/package}  
6598 {*initex}  
6599 \box_new:N \l_tmpa_box  
6600 {/initex}  
6601 \box_new:N \l_tmpb_box  
6602 \box_new:N \g_tmpa_box  
6603 \box_new:N \g_tmpb_box  
(End definition for \l_tmpa_box and others. These variables are documented on page 127.)
```

14.8 Viewing box contents

T_EX's \tex_showbox:D is not really that helpful in many cases, and it is also inconsistent with other L^AT_EX3 show functions as it does not actually shows material in the terminal. So we provide a richer set of functionality.

```
\box_show:N Essentially a wrapper around the internal function.  
\box_show:c  
\box_show:Nnn  
\box_show:cnn  
6604 \cs_new_protected:Npn \box_show:N #1  
6605 { \box_show:Nnn #1 \c_max_int \c_max_int }  
6606 \cs_generate_variant:Nn \box_show:N { c }  
6607 \cs_new_protected_nopar:Npn \box_show:Nnn  
6608 { \__box_show>NNnn \c_one }  
6609 \cs_generate_variant:Nn \box_show:Nnn { c }  
(End definition for \box_show:N and \box_show:c These functions are documented on page ??.)
```

```
\box_log:N Getting TEX to write to the log without interruption the run is done by altering the interaction mode. For that, the  $\varepsilon$ -TEX extensions are needed.  
\box_log:c  
\box_log:Nnn  
\box_log:cnn  
6610 \cs_new_protected:Npn \box_log:N #1  
6611 { \box_log:Nnn #1 \c_max_int \c_max_int }  
6612 \cs_generate_variant:Nn \box_log:N { c }  
6613 \cs_new_protected:Npn \box_log:Nnn #1#2#3  
6614 {  
6615 \use:x  
6616 {  
6617 \etex_interactionmode:D \c_zero  
6618 \__box_show>NNnn \c_zero \exp_not:N #1  
6619 { \int_eval:n {#2} } { \int_eval:n {#3} }  
6620 \etex_interactionmode:D  
6621 = \tex_the:D \etex_interactionmode:D \scan_stop:  
6622 }  
6623 }  
6624 \cs_generate_variant:Nn \box_log:Nnn { c }  
(End definition for \box_log:N and \box_log:c These functions are documented on page ??.)
```

__box_show:NNnn

The internal auxiliary to actually do the output uses a group to deal with breadth and depth values. The \use:n here gives better output appearance. Setting \tex_tracingonline:D is used to control what appears in the terminal.

```
6625 \cs_new_protected:Npn \__box_show:NNnn #1#2#3#4
6626 {
6627   \group_begin:
6628     \int_set:Nn \tex_showboxbreadth:D {#3}
6629     \int_set:Nn \tex_showboxdepth:D {#4}
6630     \int_set_eq:NN \tex_tracingonline:D #1
6631     \box_if_exist:NTF #2
6632       { \tex_showbox:D \use:n {#2} }
6633     {
6634       \__msg_kernel_error:nnx { kernel } { variable-not-defined }
6635         { \token_to_str:N #2 }
6636     }
6637   \group_end:
6638 }
```

(End definition for __box_show:NNnn)

14.9 Horizontal mode boxes

\hbox:n

(The test suite for this command, and others in this file, is m3box002.lvt.)

Put a horizontal box directly into the input stream.

```
6639 \cs_new_protected:Npn \hbox:n { \tex_hbox:D \scan_stop: }
```

(End definition for \hbox:n This function is documented on page 128.)

\hbox_set:Nn

\hbox_set:cn

\hbox_gset:Nn

\hbox_gset:cn

```
6640 \cs_new_protected:Npn \hbox_set:Nn #1#2 { \tex_setbox:D #1 \tex_hbox:D {#2} }
6641 \cs_new_protected:Npn \hbox_gset:Nn { \tex_global:D \hbox_set:Nn }
6642 \cs_generate_variant:Nn \hbox_set:Nn { c }
6643 \cs_generate_variant:Nn \hbox_gset:Nn { c }
```

(End definition for \hbox_set:Nn and \hbox_set:cn These functions are documented on page ??.)

\hbox_set_to_wd:Nnn

\hbox_set_to_wd:cnn

\hbox_gset_to_wd:Nnn

\hbox_gset_to_wd:cnn

Storing material in a horizontal box with a specified width.

```
6644 \cs_new_protected:Npn \hbox_set_to_wd:Nnn #1#2#3
6645   { \tex_setbox:D #1 \tex_hbox:D to \__dim_eval:w #2 \__dim_eval_end: {#3} }
6646 \cs_new_protected:Npn \hbox_gset_to_wd:Nnn
6647   { \tex_global:D \hbox_set_to_wd:Nnn }
6648 \cs_generate_variant:Nn \hbox_set_to_wd:Nnn { c }
6649 \cs_generate_variant:Nn \hbox_gset_to_wd:Nnn { c }
```

(End definition for \hbox_set_to_wd:Nnn and \hbox_set_to_wd:cnn These functions are documented on page ??.)

\hbox_set:Nw

\hbox_set:cw

\hbox_gset:Nw

\hbox_gset:cw

\hbox_set_end:

\hbox_gset_end:

Storing material in a horizontal box. This type is useful in environment definitions.

```
6650 \cs_new_protected:Npn \hbox_set:Nw #1
6651   { \tex_setbox:D #1 \tex_hbox:D \c_group_begin_token }
6652 \cs_new_protected:Npn \hbox_gset:Nw
6653   { \tex_global:D \hbox_set:Nw }
```

```

6654 \cs_generate_variant:Nn \hbox_set:Nw { c }
6655 \cs_generate_variant:Nn \hbox_gset:Nw { c }
6656 \cs_new_eq:NN \hbox_set_end: \c_group_end_token
6657 \cs_new_eq:NN \hbox_gset_end: \c_group_end_token
(End definition for \hbox_set:Nw and \hbox_set:cw These functions are documented on page 128.)
```

\hbox_set_inline_begin:N Renamed September 2011.

```

6658 \cs_new_eq:NN \hbox_set_inline_begin:N \hbox_set:Nw
6659 \cs_new_eq:NN \hbox_set_inline_begin:c \hbox_set:cw
6660 \cs_new_eq:NN \hbox_set_inline_end: \hbox_set_end:
6661 \cs_new_eq:NN \hbox_gset_inline_begin:N \hbox_gset:Nw
6662 \cs_new_eq:NN \hbox_gset_inline_begin:c \hbox_gset:cw
6663 \cs_new_eq:NN \hbox_gset_inline_end: \hbox_gset_end:
(End definition for \hbox_set_inline_begin:N and \hbox_set_inline_begin:c These functions are documented on page ??.)
```

\hbox_to_wd:nn Put a horizontal box directly into the input stream.

```

6664 \cs_new_protected:Npn \hbox_to_wd:nn #1#2
6665 { \tex_hbox:D to \__dim_eval:w #1 \__dim_eval_end: {#2} }
6666 \cs_new_protected:Npn \hbox_to_zero:n #1 { \tex_hbox:D to \c_zero_skip {#1} }
(End definition for \hbox_to_wd:nn This function is documented on page 128.)
```

\hbox_overlap_left:n Put a zero-sized box with the contents pushed against one side (which makes it stick out on the other) directly into the input stream.

```

6667 \cs_new_protected:Npn \hbox_overlap_left:n #1
6668 { \hbox_to_zero:n { \tex_hss:D #1 } }
6669 \cs_new_protected:Npn \hbox_overlap_right:n #1
6670 { \hbox_to_zero:n { #1 \tex_hss:D } }
(End definition for \hbox_overlap_left:n and \hbox_overlap_right:n These functions are documented on page 128.)
```

\hbox_unpack:N Unpacking a box and if requested also clear it.

```

6671 \cs_new_eq:NN \hbox_unpack:N \tex_unhcopy:D
6672 \cs_new_eq:NN \hbox_unpack_clear:N \tex_unhbox:D
6673 \cs_generate_variant:Nn \hbox_unpack:N { c }
6674 \cs_generate_variant:Nn \hbox_unpack_clear:N { c }
(End definition for \hbox_unpack:N and \hbox_unpack:c These functions are documented on page ??.)
```

14.10 Vertical mode boxes

TeX ends these boxes directly with the internal *end_graf* routine. This means that there is no \par at the end of vertical boxes unless we insert one.

\vbox:n The following test files are used for this code: *m3box003.lvt*.

\vbox_top:n The following test files are used for this code: *m3box003.lvt*.

Put a vertical box directly into the input stream.

```

6675 \cs_new_protected:Npn \vbox:n #1 { \tex_vbox:D { #1 \par } }
6676 \cs_new_protected:Npn \vbox_top:n #1 { \tex_vtop:D { #1 \par } }
```

(End definition for `\vbox:n` This function is documented on page 129.)

```
\vbox_to_ht:nn  
\vbox_to_zero:n  
  \vbox_to_ht:nn  
\vbox_to_zero:n
```

Put a vertical box directly into the input stream.

```
6677 \cs_new_protected:Npn \vbox_to_ht:nn #1#2  
6678 { \tex_vbox:D to \__dim_eval:w #1 \__dim_eval_end: { #2 \par } }  
6679 \cs_new_protected:Npn \vbox_to_zero:n #1  
6680 { \tex_vbox:D to \c_zero_dim { #1 \par } }
```

(End definition for `\vbox_to_ht:nn` and `\vbox_to_zero:n` These functions are documented on page 129.)

```
\vbox_set:Nn  
\vbox_set:cn  
  \vbox_gset:Nn  
\vbox_gset:cn
```

Storing material in a vertical box with a natural height.

```
6681 \cs_new_protected:Npn \vbox_set:Nn #1#2  
6682 { \tex_setbox:D #1 \tex_vbox:D { #2 \par } }  
6683 \cs_new_protected:Npn \vbox_gset:Nn { \tex_global:D \vbox_set:Nn }  
6684 \cs_generate_variant:Nn \vbox_set:Nn { c }  
6685 \cs_generate_variant:Nn \vbox_gset:Nn { c }
```

(End definition for `\vbox_set:Nn` and `\vbox_set:cn` These functions are documented on page ??.)

```
\vbox_set_top:Nn  
\vbox_set_top:cn  
  \vbox_gset_top:Nn  
\vbox_gset_top:cn
```

Storing material in a vertical box with a natural height and reference point at the baseline of the first object in the box.

```
6686 \cs_new_protected:Npn \vbox_set_top:Nn #1#2  
6687 { \tex_setbox:D #1 \tex_vtop:D { #2 \par } }  
6688 \cs_new_protected:Npn \vbox_gset_top:Nn  
6689 { \tex_global:D \vbox_set_top:Nn }  
6690 \cs_generate_variant:Nn \vbox_set_top:Nn { c }  
6691 \cs_generate_variant:Nn \vbox_gset_top:Nn { c }
```

(End definition for `\vbox_set_top:Nn` and `\vbox_set_top:cn` These functions are documented on page ??.)

```
\vbox_set_to_ht:Nnn  
\vbox_set_to_ht:cnn  
  \vbox_gset_to_ht:Nnn  
\vbox_gset_to_ht:cnn
```

Storing material in a vertical box with a specified height.

```
6692 \cs_new_protected:Npn \vbox_set_to_ht:Nnn #1#2#3  
6693 { \tex_setbox:D #1 \tex_vbox:D to \__dim_eval:w #2 \__dim_eval_end: { #3 \par } }  
6694 \cs_new_protected:Npn \vbox_gset_to_ht:Nnn  
6695 { \tex_global:D \vbox_set_to_ht:Nnn }  
6696 \cs_generate_variant:Nn \vbox_set_to_ht:Nnn { c }  
6697 \cs_generate_variant:Nn \vbox_gset_to_ht:Nnn { c }
```

(End definition for `\vbox_set_to_ht:Nnn` and `\vbox_set_to_ht:cnn` These functions are documented on page ??.)

```
\vbox_set:Nw  
\vbox_set:cw  
  \vbox_gset:Nw  
\vbox_gset:cw  
  \vbox_set_end:  
\vbox_gset_end:
```

Storing material in a vertical box. This type is useful in environment definitions.

```
6698 \cs_new_protected:Npn \vbox_set:Nw #1  
6699 { \tex_setbox:D #1 \tex_vbox:D \c_group_begin_token }  
6700 \cs_new_protected:Npn \vbox_gset:Nw  
6701 { \tex_global:D \vbox_set:Nw }  
6702 \cs_generate_variant:Nn \vbox_set:Nw { c }  
6703 \cs_generate_variant:Nn \vbox_gset:Nw { c }  
6704 \cs_new_protected:Npn \vbox_set_end:  
6705 {  
6706 \par  
6707 \c_group_end_token
```

```

6708   }
6709 \cs_new_eq:NN \vbox_gset_end: \vbox_set_end:
(End definition for \vbox_set:Nw and \vbox_set:cw These functions are documented on page 130.)
```

\vbox_set_inline_begin:N
\vbox_set_inline_begin:c
\vbox_gset_inline_begin:N
\vbox_gset_inline_begin:c
 \vbox_set_inline_end:
\vbox_gset_inline_end:

Renamed September 2011.

```

6710 \cs_new_eq:NN \vbox_set_inline_begin:N \vbox_set:Nw
6711 \cs_new_eq:NN \vbox_set_inline_begin:c \vbox_set:cw
6712 \cs_new_eq:NN \vbox_set_inline_end: \vbox_set_end:
6713 \cs_new_eq:NN \vbox_gset_inline_begin:N \vbox_gset:Nw
6714 \cs_new_eq:NN \vbox_gset_inline_begin:c \vbox_gset:cw
6715 \cs_new_eq:NN \vbox_gset_inline_end: \vbox_gset_end:
(End definition for \vbox_set_inline_begin:N and \vbox_set_inline_begin:c These functions are documented on page ??.)
```

\vbox_unpack:N
\vbox_unpack:c
\vbox_unpack_clear:N
\vbox_unpack_clear:c

Unpacking a box and if requested also clear it.

```

6716 \cs_new_eq:NN \vbox_unpack:N \tex_unvcopy:D
6717 \cs_new_eq:NN \vbox_unpack_clear:N \tex_unvbox:D
6718 \cs_generate_variant:Nn \vbox_unpack:N { c }
6719 \cs_generate_variant:Nn \vbox_unpack_clear:N { c }
(End definition for \vbox_unpack:N and \vbox_unpack:c These functions are documented on page ??.)
```

\vbox_set_split_to_ht>NNn

Splitting a vertical box in two.

```

6720 \cs_new_protected:Npn \vbox_set_split_to_ht>NNn #1#2#3
6721   { \tex_setbox:D #1 \tex_vsplit:D #2 to \__dim_eval:w #3 \__dim_eval_end: }
(End definition for \vbox_set_split_to_ht>NNn This function is documented on page 130.)
```

14.11 Deprecated functions

\l_last_box Deprecated 2011-11-13, for removal by 2012-02-28.

```

6722 {*deprecated}
6723 \cs_new_eq:NN \l_last_box \tex_lastbox:D
6724 {/deprecated}
(End definition for \l_last_box This variable is documented on page ??.)
```

6725 ⟨/initex | package⟩

15 l3coffins Implementation

```

6726 {*initex | package}
6727 @@=coffin
6728 {*package}
6729 \ProvidesExplPackage
6730 {\ExplFileName}{\ExplFileVersion}{\ExplFileDescription}{\ExplFileDescription}
6731 \__expl_package_check:
6732 {/package}
```

15.1 Coffins: data structures and general variables

\l__coffin_internal_box

\l__coffin_internal_dim

\l__coffin_internal_tl

Scratch variables.

```
6733 \box_new:N \l__coffin_internal_box
6734 \dim_new:N \l__coffin_internal_dim
6735 \tl_new:N \l__coffin_internal_tl
```

(End definition for \l__coffin_internal_box This function is documented on page ??.)

\c__coffin_corners_prop

The “corners”; of a coffin define the real content, as opposed to the TeX bounding box. They all start off in the same place, of course.

```
6736 \prop_new:N \c__coffin_corners_prop
6737 \prop_put:Nnn \c__coffin_corners_prop { tl } { { 0 pt } { 0 pt } }
6738 \prop_put:Nnn \c__coffin_corners_prop { tr } { { 0 pt } { 0 pt } }
6739 \prop_put:Nnn \c__coffin_corners_prop { bl } { { 0 pt } { 0 pt } }
6740 \prop_put:Nnn \c__coffin_corners_prop { br } { { 0 pt } { 0 pt } }
```

(End definition for \c__coffin_corners_prop This variable is documented on page ??.)

\c__coffin_poles_prop

Pole positions are given for horizontal, vertical and reference-point based values.

```
6741 \prop_new:N \c__coffin_poles_prop
6742 \tl_set:Nn \l__coffin_internal_tl { { 0 pt } { 0 pt } { 0 pt } { 1000 pt } }
6743 \prop_put:Nno \c__coffin_poles_prop { l } { \l__coffin_internal_tl }
6744 \prop_put:Nno \c__coffin_poles_prop { hc } { \l__coffin_internal_tl }
6745 \prop_put:Nno \c__coffin_poles_prop { r } { \l__coffin_internal_tl }
6746 \tl_set:Nn \l__coffin_internal_tl { { 0 pt } { 0 pt } { 1000 pt } { 0 pt } }
6747 \prop_put:Nno \c__coffin_poles_prop { b } { \l__coffin_internal_tl }
6748 \prop_put:Nno \c__coffin_poles_prop { vc } { \l__coffin_internal_tl }
6749 \prop_put:Nno \c__coffin_poles_prop { t } { \l__coffin_internal_tl }
6750 \prop_put:Nno \c__coffin_poles_prop { B } { \l__coffin_internal_tl }
6751 \prop_put:Nno \c__coffin_poles_prop { H } { \l__coffin_internal_tl }
6752 \prop_put:Nno \c__coffin_poles_prop { T } { \l__coffin_internal_tl }
```

(End definition for \c__coffin_poles_prop This variable is documented on page ??.)

\l__coffin_slope_x_fp

Used for calculations of intersections.

\l__coffin_slope_y_fp

```
6753 \fp_new:N \l__coffin_slope_x_fp
6754 \fp_new:N \l__coffin_slope_y_fp
```

(End definition for \l__coffin_slope_x_fp This function is documented on page ??.)

\l__coffin_error_bool

For propagating errors so that parts of the code can work around them.

```
6755 \bool_new:N \l__coffin_error_bool
```

(End definition for \l__coffin_error_bool This variable is documented on page ??.)

\l__coffin_offset_x_dim

The offset between two sets of coffin handles when typesetting. These values are corrected from those requested in an alignment for the positions of the handles.

```
6756 \dim_new:N \l__coffin_offset_x_dim
6757 \dim_new:N \l__coffin_offset_y_dim
```

(End definition for \l__coffin_offset_x_dim This function is documented on page ??.)

```

\l__coffin_pole_a_t1 Needed for finding the intersection of two poles.
\l__coffin_pole_b_t1
6758 \tl_new:N \l__coffin_pole_a_t1
6759 \tl_new:N \l__coffin_pole_b_t1
(End definition for \l__coffin_pole_a_t1 This function is documented on page ??.)

\l__coffin_x_dim For calculating intersections and so forth.
\l__coffin_y_dim
\l__coffin_x_prime_dim
\l__coffin_y_prime_dim
6760 \dim_new:N \l__coffin_x_dim
6761 \dim_new:N \l__coffin_y_dim
6762 \dim_new:N \l__coffin_x_prime_dim
6763 \dim_new:N \l__coffin_y_prime_dim
(End definition for \l__coffin_x_dim This function is documented on page ??.)

```

15.2 Basic coffin functions

There are a number of basic functions needed for creating coffins and placing material in them. This all relies on the following data structures.

```

\coffin_if_exist_p:N Several of the higher-level coffin functions will give multiple errors if the coffin does not
\coffin_if_exist_p:c exist. A cleaner way to handle this is provided here: both the box and the coffin structure
\coffin_if_exist:NTF are checked.
\coffin_if_exist:cTF
6764 \prg_new_conditional:Npnn \coffin_if_exist:N #1 { p , T , F , TF }
6765 {
6766   \cs_if_exist:NTF #1
6767   {
6768     \cs_if_exist:cTF { l__coffin_poles_ \__int_value:w #1 _prop }
6769     { \prg_return_true: }
6770     { \prg_return_false: }
6771   }
6772   { \prg_return_false: }
6773 }
6774 \cs_generate_variant:Nn \coffin_if_exist_p:N { c }
6775 \cs_generate_variant:Nn \coffin_if_exist:NT { c }
6776 \cs_generate_variant:Nn \coffin_if_exist:NF { c }
6777 \cs_generate_variant:Nn \coffin_if_exist:NTF { c }
(End definition for \coffin_if_exist:N and \coffin_if_exist:c These functions are documented on
page ??.)

```

__coffin_if_exist:NT Several of the higher-level coffin functions will give multiple errors if the coffin does not exist. So a wrapper is provided to deal with this correctly, issuing an error on erroneous use.

```

6778 \cs_new_protected:Npn \__coffin_if_exist:NT #1#2
6779 {
6780   \coffin_if_exist:NTF #1
6781   { #2 }
6782   {
6783     \__msg_kernel_error:nmx { kernel } { unknown-coffin }
6784     { \token_to_str:N #1 }
6785   }
6786 }

```

(End definition for `__coffin_if_exist:NT` This function is documented on page ??.)

\coffin_clear:N

Clearing coffins means emptying the box and resetting all of the structures.

\coffin_clear:c

```
6787 \cs_new_protected:Npn \coffin_clear:N #1
6788 {
6789     \__coffin_if_exist:NT #1
6790     {
6791         \box_clear:N #1
6792         \__coffin_reset_structure:N #1
6793     }
6794 }
6795 \cs_generate_variant:Nn \coffin_clear:N { c }
```

(End definition for `\coffin_clear:N` and `\coffin_clear:c` These functions are documented on page ??.)

\coffin_new:N

Creating a new coffin means making the underlying box and adding the data structures.

\coffin_new:c

These are created globally, as there is a need to avoid any strange effects if the coffin is created inside a group. This means that the usual rule about `\l_...` variables has to be broken.

```
6796 \cs_new_protected:Npn \coffin_new:N #1
6797 {
6798     \box_new:N #1
6799     \prop_clear_new:c { l__coffin_corners_ \__int_value:w #1 _prop }
6800     \prop_clear_new:c { l__coffin_poles_ \__int_value:w #1 _prop }
6801     \prop_gset_eq:cN { l__coffin_corners_ \__int_value:w #1 _prop }
6802         \c__coffin_corners_prop
6803     \prop_gset_eq:cN { l__coffin_poles_ \__int_value:w #1 _prop }
6804         \c__coffin_poles_prop
6805 }
6806 \cs_generate_variant:Nn \coffin_new:N { c }
```

(End definition for `\coffin_new:N` and `\coffin_new:c` These functions are documented on page ??.)

\hcoffin_set:Nn

Horizontal coffins are relatively easy: set the appropriate box, reset the structures then update the handle positions.

```
6807 \cs_new_protected:Npn \hcoffin_set:Nn #1#2
6808 {
6809     \__coffin_if_exist:NT #1
6810     {
6811         \hbox_set:Nn #1
6812         {
6813             \color_group_begin:
6814             \color_ensure_current:
6815             #2
6816             \color_group_end:
6817         }
6818         \__coffin_reset_structure:N #1
6819         \__coffin_update_poles:N #1
6820         \__coffin_update_corners:N #1
6821     }
```

```

6822   }
6823 \cs_generate_variant:Nn \hcoffin_set:Nn { c }
(End definition for \hcoffin_set:Nn and \hcoffin_set:cN These functions are documented on page
??.)
```

\vcoffin_set:Nnn \vcoffin_set:cnn

Setting vertical coffins is more complex. First, the material is typeset with a given width. The default handles and poles are set as for a horizontal coffin, before finding the top baseline using a temporary box. No `\color_ensure_current:` here as that would add a whatsit to the start of the vertical box and mess up the location of the T pole (see *TEX by Topic* for discussion of the `\vtop` primitive, used to do the measuring).

```

6824 \cs_new_protected:Npn \vcoffin_set:Nnn #1#2#3
6825 {
6826   \__coffin_if_exist:NT #1
6827   {
6828     \vbox_set:Nn #1
6829     {
6830       \dim_set:Nn \tex_hsize:D {#2}
6831     (*package)
6832       \dim_set_eq:NN \linewidth \tex_hsize:D
6833       \dim_set_eq:NN \columnwidth \tex_hsize:D
6834   (/package)
6835     \color_group_begin:
6836     #3
6837     \color_group_end:
6838   }
6839   \__coffin_reset_structure:N #1
6840   \__coffin_update_poles:N #1
6841   \__coffin_update_corners:N #1
6842   \vbox_set_top:Nn \l__coffin_internal_box { \vbox_unpack:N #1 }
6843   \__coffin_set_pole:Nnx #1 { T }
6844   {
6845     { 0 pt }
6846     { \dim_eval:n { \box_ht:N #1 - \box_ht:N \l__coffin_internal_box } }
6847     { 1000 pt }
6848     { 0 pt }
6849   }
6850   \box_clear:N \l__coffin_internal_box
6851 }
6852 }
6853 \cs_generate_variant:Nn \vcoffin_set:Nnn { c }
(End definition for \vcoffin_set:Nnn and \vcoffin_set:cnn These functions are documented on page
??.)
```

\hcoffin_set:Nw

\hcoffin_set:cw

\hcoffin_set_end:

These are the “begin”/“end” versions of the above: watch the grouping!

```

6854 \cs_new_protected:Npn \hcoffin_set:Nw #1
6855 {
6856   \__coffin_if_exist:NT #1
6857   {
6858     \hbox_set:Nw #1 \color_group_begin: \color_ensure_current:
```

```

6859     \cs_set_protected_nopar:Npn \hcoffin_set_end:
6860     {
6861         \color_group_end:
6862         \hbox_set_end:
6863         \__coffin_reset_structure:N #1
6864         \__coffin_update_poles:N #1
6865         \__coffin_update_corners:N #1
6866     }
6867 }
6868 }
6869 \cs_new_protected_nopar:Npn \hcoffin_set_end: { }
6870 \cs_generate_variant:Nn \hcoffin_set:Nw { c }
(End definition for \hcoffin_set:Nw and \hcoffin_set:cw These functions are documented on page
133.)
```

\vcoffin_set:Nnw The same for vertical coffins.

```

6871 \cs_new_protected:Npn \vcoffin_set:Nnw #1#2
6872 {
6873     \__coffin_if_exist:NT #1
6874     {
6875         \vbox_set:Nw #1
6876         \dim_set:Nn \tex_hsize:D {#2}
6877     {*package}
6878         \dim_set_eq:NN \linewidth \tex_hsize:D
6879         \dim_set_eq:NN \columnwidth \tex_hsize:D
6880 
```

 $\langle/\text{package}\rangle$

```

6881     \color_group_begin: \color_ensure_current:
6882     \cs_set_protected:Npn \vcoffin_set_end:
6883     {
6884         \color_group_end:
6885         \vbox_set_end:
6886         \__coffin_reset_structure:N #1
6887         \__coffin_update_poles:N #1
6888         \__coffin_update_corners:N #1
6889         \vbox_set_top:Nn \l__coffin_internal_box { \vbox_unpack:N #1 }
6890         \__coffin_set_pole:Nnx #1 { T }
6891         {
6892             { 0 pt }
6893             {
6894                 \dim_eval:n { \box_ht:N #1 - \box_ht:N \l__coffin_internal_box }
6895             }
6896             { 1000 pt }
6897             { 0 pt }
6898         }
6899         \box_clear:N \l__coffin_internal_box
6900     }
6901 }
6902 }
6903 \cs_new_protected_nopar:Npn \vcoffin_set_end: { }
6904 \cs_generate_variant:Nn \vcoffin_set:Nnw { c }
```

(End definition for `\vcoffin_set:Nnw` and `\vcoffin_set:cnw`. These functions are documented on page 133.)

`\coffin_set_eq:NN` Setting two coffins equal is just a wrapper around other functions.

```
6905 \cs_new_protected:Npn \coffin_set_eq:NN #1#2
6906 {
6907     \__coffin_if_exist:NT #1
6908     {
6909         \box_set_eq:NN #1 #2
6910         \__coffin_set_eq_structure:NN #1 #2
6911     }
6912 }
6913 \cs_generate_variant:Nn \coffin_set_eq:NN { c , Nc , cc }
```

(End definition for `\coffin_set_eq:NN` and others. These functions are documented on page ??.)

`\c_empty_coffin`

`\l__coffin_aligned_coffin`
`\l__coffin_aligned_internal_coffin`

Special coffins: these cannot be set up earlier as they need `\coffin_new:N`. The empty coffin is set as a box as the full coffin-setting system needs some material which is not yet available.

```
6914 \coffin_new:N \c_empty_coffin
6915 \hbox_set:Nn \c_empty_coffin { }
6916 \coffin_new:N \l__coffin_aligned_coffin
6917 \coffin_new:N \l__coffin_aligned_internal_coffin
```

(End definition for `\c_empty_coffin`. This function is documented on page ??.)

`\l_tmpa_coffin`

`\l_tmpb_coffin`

The usual scratch space.

```
6918 \coffin_new:N \l_tmpa_coffin
6919 \coffin_new:N \l_tmpb_coffin
```

(End definition for `\l_tmpa_coffin` and `\l_tmpb_coffin`. These variables are documented on page 135.)

15.3 Measuring coffins

`\coffin_dp:N`

`\coffin_dp:c`

`\coffin_ht:N`

`\coffin_ht:c`

`\coffin_wd:N`

`\coffin_wd:c`

Coffins are just boxes when it comes to measurement. However, semantically a separate set of functions are required.

```
6920 \cs_new_eq:NN \coffin_dp:N \box_dp:N
6921 \cs_new_eq:NN \coffin_dp:c \box_dp:c
6922 \cs_new_eq:NN \coffin_ht:N \box_ht:N
6923 \cs_new_eq:NN \coffin_ht:c \box_ht:c
6924 \cs_new_eq:NN \coffin_wd:N \box_wd:N
6925 \cs_new_eq:NN \coffin_wd:c \box_wd:c
```

(End definition for `\coffin_dp:N` and others. These functions are documented on page ??.)

15.4 Coffins: handle and pole management

`__coffin_get_pole:NnN` A simple wrapper around the recovery of a coffin pole, with some error checking and recovery built-in.

```

6926 \cs_new_protected:Npn \__coffin_get_pole:NnN #1#2#3
6927 {
6928     \prop_get:cnNF
6929     { l__coffin_poles_ \__int_value:w #1 _prop } {#2} #3
6930     {
6931         \__msg_kernel_error:nxxx { kernel } { unknown-coffin-pole }
6932         {#2} { \token_to_str:N #1 }
6933         \tl_set:Nn #3 { { 0 pt } { 0 pt } { 0 pt } { 0 pt } }
6934     }
6935 }
```

(End definition for `__coffin_get_pole:NnN` This function is documented on page ??.)

`__coffin_reset_structure:N` Resetting the structure is a simple copy job.

```

6936 \cs_new_protected:Npn \__coffin_reset_structure:N #1
6937 {
6938     \prop_set_eq:cN { l__coffin_corners_ \__int_value:w #1 _prop }
6939     \c__coffin_corners_prop
6940     \prop_set_eq:cN { l__coffin_poles_ \__int_value:w #1 _prop }
6941     \c__coffin_poles_prop
6942 }
```

(End definition for `__coffin_reset_structure:N` This function is documented on page ??.)

`__coffin_set_eq_structure>NN` Setting coffin structures equal simply means copying the property list.

```

6943 \cs_new_protected:Npn \__coffin_set_eq_structure:NN #1#2
6944 {
6945     \prop_set_eq:cc { l__coffin_corners_ \__int_value:w #1 _prop }
6946     { l__coffin_corners_ \__int_value:w #2 _prop }
6947     \prop_set_eq:cc { l__coffin_poles_ \__int_value:w #1 _prop }
6948     { l__coffin_poles_ \__int_value:w #2 _prop }
6949 }
6950 \cs_new_protected:Npn \__coffin_gset_eq_structure:NN #1#2
6951 {
6952     \prop_gset_eq:cc { l__coffin_corners_ \__int_value:w #1 _prop }
6953     { l__coffin_corners_ \__int_value:w #2 _prop }
6954     \prop_gset_eq:cc { l__coffin_poles_ \__int_value:w #1 _prop }
6955     { l__coffin_poles_ \__int_value:w #2 _prop }
6956 }
```

(End definition for `__coffin_set_eq_structure:NN` and `__coffin_gset_eq_structure:NN` These functions are documented on page ??.)

`\coffin_set_horizontal_pole:Nnn`
`\coffin_set_horizontal_pole:cnn`
`\coffin_set_vertical_pole:Nnn`

`\coffin_set_vertical_pole:cnn`

`__coffin_set_pole:Nnn`
`__coffin_set_pole:Nnx`

Setting the pole of a coffin at the user/designer level requires a bit more care. The idea here is to provide a reasonable interface to the system, then to do the setting with full expansion. The three-argument version is used internally to do a direct setting.

```

6957 \cs_new_protected:Npn \coffin_set_horizontal_pole:Nnn #1#2#3
6958 {
```

```

6959   \__coffin_if_exist:NT #1
6960   {
6961     \__coffin_set_pole:Nnx #1 {#2}
6962     {
6963       { 0 pt } { \dim_eval:n {#3} }
6964       { 1000 pt } { 0 pt }
6965     }
6966   }
6967 }
6968 \cs_new_protected:Npn \coffin_set_vertical_pole:Nnn #1#2#3
6969 {
6970   \__coffin_if_exist:NT #1
6971   {
6972     \__coffin_set_pole:Nnx #1 {#2}
6973     {
6974       { \dim_eval:n {#3} } { 0 pt }
6975       { 0 pt } { 1000 pt }
6976     }
6977   }
6978 }
6979 \cs_new_protected:Npn \__coffin_set_pole:Nnn #1#2#3
6980   { \prop_put:cnn { l__coffin_poles_ \__int_value:w #1 _prop } {#2} {#3} }
6981 \cs_generate_variant:Nn \coffin_set_horizontal_pole:Nnn { c }
6982 \cs_generate_variant:Nn \coffin_set_vertical_pole:Nnn { c }
6983 \cs_generate_variant:Nn \__coffin_set_pole:Nnn { Nnx }

(End definition for \coffin_set_horizontal_pole:Nnn and \coffin_set_horizontal_pole:cnn These
functions are documented on page ??.)
```

__coffin_update_corners:N Updating the corners of a coffin is straight-forward as at this stage there can be no rotation. So the corners of the content are just those of the underlying TeX box.

```

6984 \cs_new_protected:Npn \__coffin_update_corners:N #1
6985 {
6986   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } { tl }
6987   { { 0 pt } { \dim_use:N \box_ht:N #1 } }
6988   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } { tr }
6989   { { \dim_use:N \box_wd:N #1 } { \dim_use:N \box_ht:N #1 } }
6990   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } { bl }
6991   { { 0 pt } { \dim_eval:n { - \box_dp:N #1 } } }
6992   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } { br }
6993   { { \dim_use:N \box_wd:N #1 } { \dim_eval:n { - \box_dp:N #1 } } }
6994 }
```

(End definition for __coffin_update_corners:N This function is documented on page ??.)

__coffin_update_poles:N This function is called when a coffin is set, and updates the poles to reflect the nature of size of the box. Thus this function only alters poles where the default position is dependent on the size of the box. It also does not set poles which are relevant only to vertical coffins.

```

6995 \cs_new_protected:Npn \__coffin_update_poles:N #1
6996 {
```

```

6997 \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { hc }
6998 {
6999   { \dim_eval:n { 0.5 \box_wd:N #1 } }
7000   { 0 pt } { 0 pt } { 1000 pt }
7001 }
7002 \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { r }
7003 {
7004   { \dim_use:N \box_wd:N #1 }
7005   { 0 pt } { 0 pt } { 1000 pt }
7006 }
7007 \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { vc }
7008 {
7009   { 0 pt }
7010   { \dim_eval:n { ( \box_ht:N #1 - \box_dp:N #1 ) / 2 } }
7011   { 1000 pt }
7012   { 0 pt }
7013 }
7014 \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { t }
7015 {
7016   { 0 pt }
7017   { \dim_use:N \box_ht:N #1 }
7018   { 1000 pt }
7019   { 0 pt }
7020 }
7021 \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { b }
7022 {
7023   { 0 pt }
7024   { \dim_eval:n { - \box_dp:N #1 } }
7025   { 1000 pt }
7026   { 0 pt }
7027 }
7028 }

(End definition for \__coffin_update_poles:N This function is documented on page ??.)
```

15.5 Coffins: calculation of pole intersections

The lead off in finding intersections is to recover the two poles and then hand off to the auxiliary for the actual calculation. There may of course not be an intersection, for which an error trap is needed.

```

7029 \cs_new_protected:Npn \__coffin_calculate_intersection:Nnn #1#2#3
7030 {
7031   \__coffin_get_pole:NnN #1 {#2} \l__coffin_pole_a_tl
7032   \__coffin_get_pole:NnN #1 {#3} \l__coffin_pole_b_tl
7033   \bool_set_false:N \l__coffin_error_bool
7034   \exp_last_two_unbraced:Noo
7035     \__coffin_calculate_intersection:nnnnnnnn
7036     \l__coffin_pole_a_tl \l__coffin_pole_b_tl
7037   \bool_if:NT \l__coffin_error_bool
7038 }
```

```

7039      \__msg_kernel_error:nn { kernel } { no-pole-intersection }
7040      \dim_zero:N \l__coffin_x_dim
7041      \dim_zero:N \l__coffin_y_dim
7042    }
7043  }

```

The two poles passed here each have four values (as dimensions), (a, b, c, d) and (a', b', c', d') . These are arguments 1–4 and 5–8, respectively. In both cases a and b are the co-ordinates of a point on the pole and c and d define the direction of the pole. Finding the intersection depends on the directions of the poles, which are given by d/c and d'/c' . However, if one of the poles is either horizontal or vertical then one or more of c , d , c' and d' will be zero and a special case is needed.

```

7044 \cs_new_protected:Npn \__coffin_calculate_intersection:nnnnnnnn
7045   #1#2#3#4#5#6#7#8
7046   {
7047     \dim_compare:nNnTF {#3} = { \c_zero_dim }

```

The case where the first pole is vertical. So the x -component of the interaction will be at a . There is then a test on the second pole: if it is also vertical then there is an error.

```

7048   {
7049     \dim_set:Nn \l__coffin_x_dim {#1}
7050     \dim_compare:nNnTF {#7} = \c_zero_dim
7051       { \bool_set_true:N \l__coffin_error_bool }

```

The second pole may still be horizontal, in which case the y -component of the intersection will be b' . If not,

$$y = \frac{d'}{c'}(x - a') + b'$$

with the x -component already known to be #1. This calculation is done as a generalised auxiliary.

```

7052   {
7053     \dim_compare:nNnTF {#8} = \c_zero_dim
7054       { \dim_set:Nn \l__coffin_y_dim {#6} }
7055     {
7056       \__coffin_calculate_intersection_aux:nnnnN
7057         {#1} {#5} {#6} {#7} {#8} \l__coffin_y_dim
7058     }
7059   }
7060 }

```

If the first pole is not vertical then it may be horizontal. If so, then the procedure is essentially the same as that already done but with the x - and y -components interchanged.

```

7061   {
7062     \dim_compare:nNnTF {#4} = \c_zero_dim
7063     {
7064       \dim_set:Nn \l__coffin_y_dim {#2}
7065       \dim_compare:nNnTF {#8} = { \c_zero_dim }
7066         { \bool_set_true:N \l__coffin_error_bool }
7067       {
7068         \dim_compare:nNnTF {#7} = \c_zero_dim
7069           { \dim_set:Nn \l__coffin_x_dim {#5} }

```

The formula for the case where the second pole is neither horizontal nor vertical is

$$x = \frac{c'}{d'}(y - b') + a'$$

which is again handled by the same auxiliary.

```

7070      {
7071          \__coffin_calculate_intersection_aux:nnnnnN
7072              {#2} {#6} {#5} {#8} {#7} \l__coffin_x_dim
7073      }
7074  }
7075 }
```

The first pole is neither horizontal nor vertical. This still leaves the second pole, which may be a special case. For those possibilities, the calculations are the same as above with the first and second poles interchanged.

```

7076      {
7077          \dim_compare:nNnTF {#7} = \c_zero_dim
7078      {
7079          \dim_set:Nn \l__coffin_x_dim {#5}
7080          \__coffin_calculate_intersection_aux:nnnnnN
7081              {#5} {#1} {#2} {#3} {#4} \l__coffin_y_dim
7082      }
7083  {
7084      \dim_compare:nNnTF {#8} = \c_zero_dim
7085      {
7086          \dim_set:Nn \l__coffin_x_dim {#6}
7087          \__coffin_calculate_intersection_aux:nnnnnN
7088              {#6} {#2} {#1} {#4} {#3} \l__coffin_x_dim
7089      }
7090 }
```

If none of the special cases apply then there is still a need to check that there is a unique intersection between the two pole. This is the case if they have different slopes.

```

7090      {
7091          \fp_set:Nn \l__coffin_slope_x_fp
7092              { \dim_to_fp:n {#4} / \dim_to_fp:n {#3} }
7093          \fp_set:Nn \l__coffin_slope_y_fp
7094              { \dim_to_fp:n {#8} / \dim_to_fp:n {#7} }
7095          \fp_compare:nNnTF
7096              \l__coffin_slope_x_fp = \l__coffin_slope_y_fp
7097                  { \bool_set_true:N \l__coffin_error_bool }
```

All of the tests pass, so there is the full complexity of the calculation:

$$x = \frac{a(d/c) - a'(d'/c') - b + b'}{(d/c) - (d'/c')}$$

and noting that the two ratios are already worked out from the test just performed. There is quite a bit of shuffling from dimensions to floating points in order to do the work. The y -values is then worked out using the standard auxiliary starting from the x -position.

```

7098 {
7099   \dim_set:Nn \l__coffin_x_dim
7100   {
7101     \fp_to_dim:n
7102     {
7103       (
7104         \dim_to_fp:n {#1} * \l__coffin_slope_x_fp
7105         - ( \dim_to_fp:n {#5} * \l__coffin_slope_y_fp )
7106         - \dim_to_fp:n {#2}
7107         + \dim_to_fp:n {#6}
7108       )
7109       /
7110       ( \l__coffin_slope_x_fp - \l__coffin_slope_y_fp )
7111     }
7112   }
7113   \__coffin_calculate_intersection_aux:nnnnN
7114   { \l__coffin_x_dim }
7115   {#5} {#6} {#8} {#7} \l__coffin_y_dim
7116 }
7117 }
7118 }
7119 }
7120 }
7121 }

```

The formula for finding the intersection point is in most cases the same. The formula here is

$$\#6 = \#4 \cdot \left(\frac{\#1 - \#2}{\#5} \right) \#3$$

Thus #4 and #5 should be the directions of the pole while #2 and #3 are co-ordinates.

```

7122 \cs_new_protected:Npn \__coffin_calculate_intersection_aux:nnnnN #1#2#3#4#5#6
7123 {
7124   \dim_set:Nn #6
7125   {
7126     \fp_to_dim:n
7127     {
7128       \dim_to_fp:n {#4} *
7129       ( \dim_to_fp:n {#1} - \dim_to_fp:n {#2} ) /
7130       \dim_to_fp:n {#5}
7131       + \dim_to_fp:n {#3}
7132     }
7133   }
7134 }
```

(End definition for `__coffin_calculate_intersection:Nnn` This function is documented on page ??.)

15.6 Aligning and typesetting of coffins

```
\coffin_join:NnnNnnnn
\coffin_join:cnnNnnnn
\coffin_join:Nnncnnnn
\coffin_join:cnnccnnnn
```

This command joins two coffins, using a horizontal and vertical pole from each coffin and making an offset between the two. The result is stored as the as a third coffin, which will

have all of its handles reset to standard values. First, the more basic alignment function is used to get things started.

```

7135 \cs_new_protected:Npn \coffin_join:NnnNnnnn #1#2#3#4#5#6#7#8
7136 {
7137   \__coffin_align:NnnNnnnnN
7138   #1 {#2} {#3} {#4} {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin

```

Correct the placement of the reference point. If the x -offset is negative then the reference point of the second box is to the left of that of the first, which is corrected using a kern. On the right side the first box might stick out, which will show up if it is wider than the sum of the x -offset and the width of the second box. So a second kern may be needed.

```

7139 \hbox_set:Nn \l__coffin_aligned_coffin
7140 {
7141   \dim_compare:nNnT { \l__coffin_offset_x_dim } < \c_zero_dim
7142     { \tex_kern:D -\l__coffin_offset_x_dim }
7143   \hbox_unpack:N \l__coffin_aligned_coffin
7144   \dim_set:Nn \l__coffin_internal_dim
7145     { \l__coffin_offset_x_dim - \box_wd:N #1 + \box_wd:N #4 }
7146   \dim_compare:nNnT \l__coffin_internal_dim < \c_zero_dim
7147     { \tex_kern:D -\l__coffin_internal_dim }
7148 }

```

The coffin structure is reset, and the corners are cleared: only those from the two parent coffins are needed.

```

7149 \__coffin_reset_structure:N \l__coffin_aligned_coffin
7150 \prop_clear:c
7151   { \l__coffin_corners_ \__int_value:w \l__coffin_aligned_coffin _ prop }
7152 \__coffin_update_poles:N \l__coffin_aligned_coffin

```

The structures of the parent coffins are now transferred to the new coffin, which requires that the appropriate offsets are applied. That will then depend on whether any shift was needed.

```

7153 \dim_compare:nNnTF \l__coffin_offset_x_dim < \c_zero_dim
7154 {
7155   \__coffin_offset_poles:Nnn #1 { -\l__coffin_offset_x_dim } { 0 pt }
7156   \__coffin_offset_poles:Nnn #4 { 0 pt } { \l__coffin_offset_y_dim }
7157   \__coffin_offset_corners:Nnn #1 { -\l__coffin_offset_x_dim } { 0 pt }
7158   \__coffin_offset_corners:Nnn #4 { 0 pt } { \l__coffin_offset_y_dim }
7159 }
7160 {
7161   \__coffin_offset_poles:Nnn #1 { 0 pt } { 0 pt }
7162   \__coffin_offset_poles:Nnn #4
7163     { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
7164   \__coffin_offset_corners:Nnn #1 { 0 pt } { 0 pt }
7165   \__coffin_offset_corners:Nnn #4
7166     { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
7167 }
7168 \__coffin_update_vertical_poles:NNN #1 #4 \l__coffin_aligned_coffin
7169 \coffin_set_eq:NN #1 \l__coffin_aligned_coffin
7170 }

```

```

7171 \cs_generate_variant:Nn \coffin_join:NnnNnnnn { c , Nnnc , cnnc }
(End definition for \coffin_join:NnnNnnnn and others. These functions are documented on page ??.)
```

\coffin_attach:NnnNnnnn

\coffin_attach:cnnNnnnn

\coffin_attach:Nnncnmnn

\coffin_attach:cnnccnnn

\coffin_attach_mark:NnnNnnnn

A more simple version of the above, as it simply uses the size of the first coffin for the new one. This means that the work here is rather simplified compared to the above code. The function used when marking a position is hear also as it is similar but without the structure updates.

```

7172 \cs_new_protected:Npn \coffin_attach:NnnNnnnn #1#2#3#4#5#6#7#8
7173 {
7174     \__coffin_align:NnnNnnnnN
7175         #1 {#2} {#3} #4 {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin
7176         \box_set_ht:Nn \l__coffin_aligned_coffin { \box_ht:N #1 }
7177         \box_set_dp:Nn \l__coffin_aligned_coffin { \box_dp:N #1 }
7178         \box_set_wd:Nn \l__coffin_aligned_coffin { \box_wd:N #1 }
7179         \__coffin_reset_structure:N \l__coffin_aligned_coffin
7180         \prop_set_eq:cc
7181             { l__coffin_corners_ \__int_value:w \l__coffin_aligned_coffin _prop }
7182             { l__coffin_corners_ \__int_value:w #1 _prop }
7183         \__coffin_update_poles:N \l__coffin_aligned_coffin
7184         \__coffin_offset_poles:Nnn #1 { 0 pt } { 0 pt }
7185         \__coffin_offset_poles:Nnn #4
7186             { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
7187         \__coffin_update_vertical_poles:NNN #1 #4 \l__coffin_aligned_coffin
7188         \coffin_set_eq:NN #1 \l__coffin_aligned_coffin
7189     }
7190 \cs_new_protected:Npn \coffin_attach_mark:NnnNnnnn #1#2#3#4#5#6#7#8
7191 {
7192     \__coffin_align:NnnNnnnnN
7193         #1 {#2} {#3} #4 {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin
7194         \box_set_ht:Nn \l__coffin_aligned_coffin { \box_ht:N #1 }
7195         \box_set_dp:Nn \l__coffin_aligned_coffin { \box_dp:N #1 }
7196         \box_set_wd:Nn \l__coffin_aligned_coffin { \box_wd:N #1 }
7197         \box_set_eq:NN #1 \l__coffin_aligned_coffin
7198     }
7199 \cs_generate_variant:Nn \coffin_attach:NnnNnnnn { c , Nnnc , cnnc }
(End definition for \coffin_attach:NnnNnnnn and others. These functions are documented on page ??.)
```

__coffin_align:NnnNnnnnN

The internal function aligns the two coffins into a third one, but performs no corrections on the resulting coffin poles. The process begins by finding the points of intersection for the poles for each of the input coffins. Those for the first coffin are worked out after those for the second coffin, as this allows the ‘primed’ storage area to be used for the second coffin. The ‘real’ box offsets are then calculated, before using these to re-box the input coffins. The default poles are then set up, but the final result will depend on how the bounding box is being handled.

```

7200 \cs_new_protected:Npn \__coffin_align:NnnNnnnnN #1#2#3#4#5#6#7#8#9
7201 {
7202     \__coffin_calculate_intersection:Nnn #4 {#5} {#6}
7203     \dim_set:Nn \l__coffin_x_prime_dim { \l__coffin_x_dim }
```

```

7204 \dim_set:Nn \l__coffin_y_prime_dim { \l__coffin_y_dim }
7205 \__coffin_calculate_intersection:Nnn #1 {#2} {#3}
7206 \dim_set:Nn \l__coffin_offset_x_dim
7207   { \l__coffin_x_dim - \l__coffin_x_prime_dim + #7 }
7208 \dim_set:Nn \l__coffin_offset_y_dim
7209   { \l__coffin_y_dim - \l__coffin_y_prime_dim + #8 }
7210 \hbox_set:Nn \l__coffin_aligned_internal_coffin
7211 {
7212   \box_use:N #1
7213   \tex_kern:D -\box_wd:N #1
7214   \tex_kern:D \l__coffin_offset_x_dim
7215   \box_move_up:nn { \l__coffin_offset_y_dim } { \box_use:N #4 }
7216 }
7217 \coffin_set_eq:NN #9 \l__coffin_aligned_internal_coffin
7218 }

```

(End definition for `__coffin_align:NnnNnnnnN` This function is documented on page ??.)

`__coffin_offset_poles:Nnn`
`__coffin_offset_pole:Nnnnnnn`

Transferring structures from one coffin to another requires that the positions are updated by the offset between the two coffins. This is done by mapping to the property list of the source coffins, moving as appropriate and saving to the new coffin data structures. The test for a - means that the structures from the parent coffins are uniquely labelled and do not depend on the order of alignment. The pay off for this is that - should not be used in coffin pole or handle names, and that multiple alignments do not result in a whole set of values.

```

7219 \cs_new_protected:Npn \__coffin_offset_poles:Nnn #1#2#3
7220 {
7221   \prop_map_inline:cn { l__coffin_poles_ \__int_value:w #1 _prop }
7222     { \__coffin_offset_pole:Nnnnnnn #1 {##1} ##2 {#2} {#3} }
7223 }
7224 \cs_new_protected:Npn \__coffin_offset_pole:Nnnnnnn #1#2#3#4#5#6#7#8
7225 {
7226   \dim_set:Nn \l__coffin_x_dim { #3 + #7 }
7227   \dim_set:Nn \l__coffin_y_dim { #4 + #8 }
7228   \tl_if_in:nNTF {#2} { - }
7229     { \tl_set:Nn \l__coffin_internal_tl { {#2} } }
7230     { \tl_set:Nn \l__coffin_internal_tl { { #1 - #2 } } }
7231   \exp_last_unbraced:NNo \__coffin_set_pole:Nnx \l__coffin_aligned_coffin
7232     { \l__coffin_internal_tl }
7233   {
7234     { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
7235     {#5} {#6}
7236   }
7237 }

```

(End definition for `__coffin_offset_poles:Nnn` This function is documented on page ??.)

`__coffin_offset_corners:Nnn`
`__coffin_offset_corner:Nnnn`

Saving the offset corners of a coffin is very similar, except that there is no need to worry about naming: every corner can be saved here as order is unimportant.

```

7238 \cs_new_protected:Npn \__coffin_offset_corners:Nnn #1#2#3
7239 {

```

```

7240   \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
7241     { \__coffin_offset_corner:Nnnnn #1 {##1} ##2 {#3} }
7242   }
7243 \cs_new_protected:Npn \__coffin_offset_corner:Nnnnn #1#2#3#4#5#6
7244   {
7245     \prop_put:cnx
7246       { l__coffin_corners_ \__int_value:w \l__coffin_aligned_coffin _prop }
7247       { #1 - #2 }
7248     {
7249       { \dim_eval:n { #3 + #5 } }
7250       { \dim_eval:n { #4 + #6 } }
7251     }
7252   }
(End definition for \__coffin_offset_corners:Nnn This function is documented on page ??.)
```

`__coffin_update_vertical_poles:NNN`
`__coffin_update_T:nnnnnnnnN`
`__coffin_update_B:nnnnnnnnN`

The T and B poles will need to be recalculated after alignment. These functions find the larger absolute value for the poles, but this is of course only logical when the poles are horizontal.

```

7253 \cs_new_protected:Npn \__coffin_update_vertical_poles:NNN #1#2#3
7254   {
7255     \__coffin_get_pole:NnN #3 { #1 -T } \l__coffin_pole_a_tl
7256     \__coffin_get_pole:NnN #3 { #2 -T } \l__coffin_pole_b_tl
7257     \exp_last_two_unbraced:Noo \__coffin_update_T:nnnnnnnnN
7258       \l__coffin_pole_a_tl \l__coffin_pole_b_tl #3
7259     \__coffin_get_pole:NnN #3 { #1 -B } \l__coffin_pole_a_tl
7260     \__coffin_get_pole:NnN #3 { #2 -B } \l__coffin_pole_b_tl
7261     \exp_last_two_unbraced:Noo \__coffin_update_B:nnnnnnnnN
7262       \l__coffin_pole_a_tl \l__coffin_pole_b_tl #3
7263   }
7264 \cs_new_protected:Npn \__coffin_update_T:nnnnnnnnN #1#2#3#4#5#6#7#8#9
7265   {
7266     \dim_compare:nNnTF {#2} < {#6}
7267     {
7268       \__coffin_set_pole:Nnx #9 { T }
7269         { { 0 pt } {#6} { 1000 pt } { 0 pt } }
7270     }
7271     {
7272       \__coffin_set_pole:Nnx #9 { T }
7273         { { 0 pt } {#2} { 1000 pt } { 0 pt } }
7274     }
7275   }
7276 \cs_new_protected:Npn \__coffin_update_B:nnnnnnnnN #1#2#3#4#5#6#7#8#9
7277   {
7278     \dim_compare:nNnTF {#2} < {#6}
7279     {
7280       \__coffin_set_pole:Nnx #9 { B }
7281         { { 0 pt } {#2} { 1000 pt } { 0 pt } }
7282     }
7283   }
```

```

7284     \__coffin_set_pole:Nnx #9 { B }
7285     { { 0 pt } {#6} { 1000 pt } { 0 pt } }
7286   }
7287 }
(End definition for \__coffin_update_vertical_poles:NNN This function is documented on page ??.)
```

\coffin_typeset:Nnnnn Typesetting a coffin means aligning it with the current position, which is done using a coffin with no content at all. As well as aligning to the empty coffin, there is also a need to leave vertical mode, if necessary.

```

7288 \cs_new_protected:Npn \coffin_typeset:Nnnnn #1#2#3#4#5
7289 {
7290   \hbox_unpack:N \c_empty_box
7291   \__coffin_align:NnnNnnnn \c_empty_coffin { H } { 1 }
7292   #1 {#2} {#3} {#4} {#5} \l__coffin_aligned_coffin
7293   \box_use:N \l__coffin_aligned_coffin
7294 }
7295 \cs_generate_variant:Nn \coffin_typeset:Nnnnn { c }
(End definition for \coffin_typeset:Nnnnn and \coffin_typeset:cnnnn These functions are documented on page ??.)
```

15.7 Coffin diagnostics

\l__coffin_display_coffin Used for printing coffins with data structures attached.

```

7296 \coffin_new:N \l__coffin_display_coffin
7297 \coffin_new:N \l__coffin_display_coord_coffin
7298 \coffin_new:N \l__coffin_display_pole_coffin
(End definition for \l__coffin_display_coffin This function is documented on page ??.)
```

\l__coffin_display_handles_prop This property list is used to print coffin handles at suitable positions. The offsets are expressed as multiples of the basic offset value, which therefore acts as a scale-factor.

```

7299 \prop_new:N \l__coffin_display_handles_prop
7300 \prop_put:Nnn \l__coffin_display_handles_prop { tl }
7301   { { b } { r } { -1 } { 1 } }
7302 \prop_put:Nnn \l__coffin_display_handles_prop { thc }
7303   { { b } { hc } { 0 } { 1 } }
7304 \prop_put:Nnn \l__coffin_display_handles_prop { tr }
7305   { { b } { 1 } { 1 } { 1 } }
7306 \prop_put:Nnn \l__coffin_display_handles_prop { vcl }
7307   { { vc } { r } { -1 } { 0 } }
7308 \prop_put:Nnn \l__coffin_display_handles_prop { vchc }
7309   { { vc } { hc } { 0 } { 0 } }
7310 \prop_put:Nnn \l__coffin_display_handles_prop { vcr }
7311   { { vc } { 1 } { 1 } { 0 } }
7312 \prop_put:Nnn \l__coffin_display_handles_prop { bl }
7313   { { t } { r } { -1 } { -1 } }
7314 \prop_put:Nnn \l__coffin_display_handles_prop { bhc }
7315   { { t } { hc } { 0 } { -1 } }
7316 \prop_put:Nnn \l__coffin_display_handles_prop { br }
```

```

7317   { { t } { 1 } { 1 } { -1 } }
7318 \prop_put:Nnn \l__coffin_display_handles_prop { Tl }
7319   { { t } { r } { -1 } { -1 } }
7320 \prop_put:Nnn \l__coffin_display_handles_prop { Thc }
7321   { { t } { hc } { 0 } { -1 } }
7322 \prop_put:Nnn \l__coffin_display_handles_prop { Tr }
7323   { { t } { 1 } { 1 } { -1 } }
7324 \prop_put:Nnn \l__coffin_display_handles_prop { Hl }
7325   { { vc } { r } { -1 } { 1 } }
7326 \prop_put:Nnn \l__coffin_display_handles_prop { Hhc }
7327   { { vc } { hc } { 0 } { 1 } }
7328 \prop_put:Nnn \l__coffin_display_handles_prop { Hr }
7329   { { vc } { 1 } { 1 } { 1 } }
7330 \prop_put:Nnn \l__coffin_display_handles_prop { Bl }
7331   { { b } { r } { -1 } { -1 } }
7332 \prop_put:Nnn \l__coffin_display_handles_prop { Bhc }
7333   { { b } { hc } { 0 } { -1 } }
7334 \prop_put:Nnn \l__coffin_display_handles_prop { Br }
7335   { { b } { 1 } { 1 } { -1 } }

(End definition for \l__coffin_display_handles_prop This variable is documented on page ??.)
```

\l__coffin_display_offset_dim The standard offset for the label from the handle position when displaying handles.

```

7336 \dim_new:N \l__coffin_display_offset_dim
7337 \dim_set:Nn \l__coffin_display_offset_dim { 2 pt }

(End definition for \l__coffin_display_offset_dim This variable is documented on page ??.)
```

\l__coffin_display_x_dim As the intersections of poles have to be calculated to find which ones to print, there is a need to avoid repetition. This is done by saving the intersection into two dedicated values.

```

7338 \dim_new:N \l__coffin_display_x_dim
7339 \dim_new:N \l__coffin_display_y_dim

(End definition for \l__coffin_display_x_dim This function is documented on page ??.)
```

\l__coffin_display_poles_prop A property list for printing poles: various things need to be deleted from this to get a “nice” output.

```

7340 \prop_new:N \l__coffin_display_poles_prop

(End definition for \l__coffin_display_poles_prop This variable is documented on page ??.)
```

\l__coffin_display_font_t1 Stores the settings used to print coffin data: this keeps things flexible.

```

7341 \tl_new:N \l__coffin_display_font_t1
7342 {*initex}
7343 \tl_set:Nn \l__coffin_display_font_t1 { } % TODO
7344 (*initex)
7345 (*package)
7346 \tl_set:Nn \l__coffin_display_font_t1 { \sffamily \tiny }
7347 (*package)

(End definition for \l__coffin_display_font_t1 This variable is documented on page ??.)
```

```
\coffin_mark_handle:Nnnn
\coffin_mark_handle:cnnn
\_\_coffin_mark_handle_aux:nnnnNnn
```

Marking a single handle is relatively easy. The standard attachment function is used, meaning that there are two calculations for the location. However, this is likely to be okay given the load expected. Contrast with the more optimised version for showing all handles which comes next.

```
7348 \cs_new_protected:Npn \coffin_mark_handle:Nnnn #1#2#3#4
7349 {
7350     \hcoffin_set:Nn \l__coffin_display_pole_coffin
7351     {
7352         (*initex)
7353             \hbox:n { \tex_vrule:D width 1 pt height 1 pt \scan_stop: } % TODO
7354     
7355     (*package)
7356         \color {#4}
7357         \rule { 1 pt } { 1 pt }
7358 
7359     }
7360     \coffin_attach_mark:NnnNnnnn #1 {#2} {#3}
7361         \l__coffin_display_pole_coffin { hc } { vc } { 0 pt } { 0 pt }
7362     \hcoffin_set:Nn \l__coffin_display_coord_coffin
7363     {
7364         (*initex)
7365             % TODO
7366     
7367     (*package)
7368         \color {#4}
7369 
7370         \l__coffin_display_font_tl
7371         ( \tl_to_str:n { #2 , #3 } )
7372     }
7373     \prop_get:NnN \l__coffin_display_handles_prop
7374         { #2 #3 } \l__coffin_internal_tl
7375     \quark_if_no_value:NTF \l__coffin_internal_tl
7376     {
7377         \prop_get:NnN \l__coffin_display_handles_prop
7378             { #3 #2 } \l__coffin_internal_tl
7379         \quark_if_no_value:NTF \l__coffin_internal_tl
7380         {
7381             \coffin_attach_mark:NnnNnnnn #1 {#2} {#3}
7382                 \l__coffin_display_coord_coffin { 1 } { vc }
7383                     { 1 pt } { 0 pt }
7384         }
7385     }
7386     \exp_last_unbraced:No \_\_coffin_mark_handle_aux:nnnnNnn
7387         \l__coffin_internal_tl #1 {#2} {#3}
7388     }
7389 }
7390 {
7391     \exp_last_unbraced:No \_\_coffin_mark_handle_aux:nnnnNnn
7392         \l__coffin_internal_tl #1 {#2} {#3}
```

```

7393     }
7394   }
7395 \cs_new_protected:Npn \__coffin_mark_handle_aux:nnnnNnn #1#2#3#4#5#6#7
7396   {
7397     \coffin_attach_mark:NnnNnnn #5 {#6} {#7}
7398       \l__coffin_display_coord_coffin {#1} {#2}
7399       { #3 \l__coffin_display_offset_dim }
7400       { #4 \l__coffin_display_offset_dim }
7401   }
7402 \cs_generate_variant:Nn \coffin_mark_handle:Nnnn { c }
(End definition for \coffin_mark_handle:Nnnn and \coffin_mark_handle:cnnn These functions are documented on page ??.)
```

\coffin_display_handles:Nn
\coffin_display_handles:cnn
__coffin_display_handles_aux:nmmmn
__coffin_display_handles_aux:nnnn
__coffin_display_attach:Nnnnn

Printing the poles starts by removing any duplicates, for which the H poles is used as the definitive version for the baseline and bottom. Two loops are then used to find the combinations of handles for all of these poles. This is done such that poles are removed during the loops to avoid duplication.

```

7403 \cs_new_protected:Npn \coffin_display_handles:Nn #1#2
7404   {
7405     \hcoffin_set:Nn \l__coffin_display_pole_coffin
7406     {
7407       {*initex}
7408         \hbox:n { \tex_vrule:D width 1 pt height 1 pt \scan_stop: } % TODO
7409     {*}initex
7410   {*}package}
7411     \color {#2}
7412     \rule { 1 pt } { 1 pt }
7413 {*}package}
7414   }
7415   \prop_set_eq:Nc \l__coffin_display_poles_prop
7416     { l__coffin_poles_ \__int_value:w #1 _prop }
7417   \__coffin_get_pole:NnN #1 { H } \l__coffin_pole_a_tl
7418   \__coffin_get_pole:NnN #1 { T } \l__coffin_pole_b_tl
7419   \tl_if_eq:NNT \l__coffin_pole_a_tl \l__coffin_pole_b_tl
7420     { \prop_remove:Nn \l__coffin_display_poles_prop { T } }
7421   \__coffin_get_pole:NnN #1 { B } \l__coffin_pole_b_tl
7422   \tl_if_eq:NNT \l__coffin_pole_a_tl \l__coffin_pole_b_tl
7423     { \prop_remove:Nn \l__coffin_display_poles_prop { B } }
7424   \coffin_set_eq>NN \l__coffin_display_coffin #1
7425   \prop_map_inline:Nn \l__coffin_display_poles_prop
7426   {
7427     \prop_remove:Nn \l__coffin_display_poles_prop {##1}
7428       \__coffin_display_handles_aux:nnnnnn {##1} ##2 {#2}
7429   }
7430   \box_use:N \l__coffin_display_coffin
7431 }
```

For each pole there is a check for an intersection, which here does not give an error if none is found. The successful values are stored and used to align the pole coffin with the main coffin for output. The positions are recovered from the preset list if available.

```

7432 \cs_new_protected:Npn \__coffin_display_handles_aux:nnnnn #1#2#3#4#5#6
7433 {
7434   \prop_map_inline:Nn \l__coffin_display_poles_prop
7435   {
7436     \bool_set_false:N \l__coffin_error_bool
7437     \__coffin_calculate_intersection:nnnnnnnn {#2} {#3} {#4} {#5} ##2
7438     \bool_if:NF \l__coffin_error_bool
7439     {
7440       \dim_set:Nn \l__coffin_display_x_dim { \l__coffin_x_dim }
7441       \dim_set:Nn \l__coffin_display_y_dim { \l__coffin_y_dim }
7442       \__coffin_display_attach:Nnnn
7443         \l__coffin_display_pole_coffin { hc } { vc }
7444         { 0 pt } { 0 pt }
7445       \hcoffin_set:Nn \l__coffin_display_coord_coffin
7446       {
7447         /*initex}
7448           % TODO
7449       /*initex
7450     *package
7451       \color {#6}
7452     /package
7453       \l__coffin_display_font_tl
7454       ( \tl_to_str:n { #1 , ##1 } )
7455     }
7456     \prop_get:NnN \l__coffin_display_handles_prop
7457       { #1 ##1 } \l__coffin_internal_tl
7458     \quark_if_no_value:NTF \l__coffin_internal_tl
7459     {
7460       \prop_get:NnN \l__coffin_display_handles_prop
7461         { ##1 #1 } \l__coffin_internal_tl
7462       \quark_if_no_value:NTF \l__coffin_internal_tl
7463       {
7464         \__coffin_display_attach:Nnnn
7465           \l__coffin_display_coord_coffin { 1 } { vc }
7466           { 1 pt } { 0 pt }
7467       }
7468     }
7469     \exp_last_unbraced:No
7470       \__coffin_display_handles_aux:nnnn
7471       \l__coffin_internal_tl
7472     }
7473   }
7474   {
7475     \exp_last_unbraced:No \__coffin_display_handles_aux:nnnn
7476       \l__coffin_internal_tl
7477     }
7478   }
7479 }
7480 }
```

7481 \cs_new_protected:Npn __coffin_display_handles_aux:nnnn #1#2#3#4

```

7482   {
7483     \__coffin_display_attach:Nnnnn
7484       \l__coffin_display_coord_coffin {#1} {#2}
7485       { #3 \l__coffin_display_offset_dim }
7486       { #4 \l__coffin_display_offset_dim }
7487   }
7488 \cs_generate_variant:Nn \coffin_display_handles:Nn { c }

This is a dedicated version of \coffin_attach:NnnNnnnn with a hard-wired first coffin.
As the intersection is already known and stored for the display coffin the code simply
uses it directly, with no calculation.

7489 \cs_new_protected:Npn \__coffin_display_attach:Nnnnn #1#2#3#4#5
7490   {
7491     \__coffin_calculate_intersection:Nnn #1 {#2} {#3}
7492     \dim_set:Nn \l__coffin_x_prime_dim { \l__coffin_x_dim }
7493     \dim_set:Nn \l__coffin_y_prime_dim { \l__coffin_y_dim }
7494     \dim_set:Nn \l__coffin_offset_x_dim
7495       { \l__coffin_display_x_dim - \l__coffin_x_prime_dim + #4 }
7496     \dim_set:Nn \l__coffin_offset_y_dim
7497       { \l__coffin_display_y_dim - \l__coffin_y_prime_dim + #5 }
7498     \hbox_set:Nn \l__coffin_aligned_coffin
7499     {
7500       \box_use:N \l__coffin_display_coffin
7501       \tex_kern:D -\box_wd:N \l__coffin_display_coffin
7502       \tex_kern:D \l__coffin_offset_x_dim
7503       \box_move_up:nn { \l__coffin_offset_y_dim } { \box_use:N #1 }
7504     }
7505     \box_set_ht:Nn \l__coffin_aligned_coffin
7506       { \box_ht:N \l__coffin_display_coffin }
7507     \box_set_dp:Nn \l__coffin_aligned_coffin
7508       { \box_dp:N \l__coffin_display_coffin }
7509     \box_set_wd:Nn \l__coffin_aligned_coffin
7510       { \box_wd:N \l__coffin_display_coffin }
7511     \box_set_eq:NN \l__coffin_display_coffin \l__coffin_aligned_coffin
7512   }

(End definition for \coffin_display_handles:Nn and \coffin_display_handles:cn These functions are
documented on page ??..)

```

\coffin_show_structure:N For showing the various internal structures attached to a coffin in a way that keeps things relatively readable. If there is no apparent structure then the code complains.

```

7513 \cs_new_protected:Npn \coffin_show_structure:N #1
7514   {
7515     \__coffin_if_exist:NT #1
7516     {
7517       \__msg_show_variable:Nnn #1 { coffins }
7518       {
7519         \prop_map_function:cN
7520           { \l__coffin_poles_ \__int_value:w #1 _prop }
7521           \__msg_show_item_unbraced:nn
7522     }

```

```

7523     }
7524   }
7525 \cs_generate_variant:Nn \coffin_show_structure:N { c }
(End definition for \coffin_show_structure:N and \coffin_show_structure:c These functions are documented on page ??.)
```

7526 __msg_kernel_new:nnnn { kernel } { no-pole-intersection }
7527 { No~intersection~between~coffin~poles. }
7528 {
7529 \c_msg_coding_error_text_tl
7530 LaTeX-was-asked-to-find-the-intersection-between-two-poles,~
7531 but-they-do-not-have-a-unique-meeting-point:~
7532 the-value-(0-pt,~0-pt)-will-be-used.
7533 }
7534 __msg_kernel_new:nnnn { kernel } { unknown-coffin }
7535 { Unknown-coffin-'#1'. }
7536 { The-coffin-'#1'-was-never-defined. }
7537 __msg_kernel_new:nnnn { kernel } { unknown-coffin-pole }
7538 { Pole-'#1'-unknown-for-coffin-'#2'. }
7539 {
7540 \c_msg_coding_error_text_tl
7541 LaTeX-was-asked-to-find-a-typesetting-pole-for-a-coffin,~
7542 but-either-the-coffin-does-not-exist-or-the-pole-name-is-wrong.
7543 }
7544 __msg_kernel_new:nnn { kernel } { show-coffins }
7545 {
7546 Size-of-coffin-\token_to_str:N #1 : \\
7547 > ~ ht\dim_use:N \box_ht:N #1 \\
7548 > ~ dp\dim_use:N \box_dp:N #1 \\
7549 > ~ wd\dim_use:N \box_wd:N #1 \\
7550 Poles-of-coffin-\token_to_str:N #1 :
7551 }
7552

16 l3color Implementation

```

7553 <*initex | package>
7554 <*package>
7555 \ProvidesExplPackage
7556   {\ExplFileName}{\ExplFileVersion}{\ExplFileDescription}
7557 \__expl_package_check:
7558 
```

\color_group_begin: Grouping for color is almost the same as using the basic \group_begin: and \group_end: functions. However, in vertical mode the end-of-group needs a \par, which in horizontal mode does nothing.

```

7559 \cs_new_eq:NN \color_group_begin: \group_begin:
```

```

7560 \cs_new_protected_nopar:Npn \color_group_end:
7561 {
7562     \tex_par:D
7563     \group_end:
7564 }
(End definition for \color_group_begin: and \color_group_end: These functions are documented on
page 136.)
```

\color_ensure_current: A driver-independent wrapper for setting the foreground color to the current color “now”.

```

7565 {*initex}
7566 \cs_new_protected_nopar:Npn \color_ensure_current:
7567 {
7568     \__driver_color_ensure_current:
7569 }
```

In package mode, the driver code may not be loaded. To keep down dependencies, if there is no driver code available and no \set@color then color is not in use and this function can be a no-op.

```

7569 {*package}
7570 \cs_new_protected_nopar:Npn \color_ensure_current: { }
7571 \AtBeginDocument
7572 {
7573     \cs_if_exist:NTF \__driver_color_ensure_current:
7574     {
7575         \cs_set_protected_nopar:Npn \color_ensure_current:
7576         {
7577             \__driver_color_ensure_current:
7578         }
7579     }
7580     \cs_if_exist:NT \set@color
7581     {
7582         \cs_set_protected_nopar:Npn \color_ensure_current: { \set@color }
7583     }
7584 }
```

(End definition for \color_ensure_current: This function is documented on page 136.)

17 l3msg implementation

```

7585 {*initex | package}
7586 <@=msg>
7587 {*package}
7588 \ProvidesExplPackage
7589 {\ExplFileName}{\ExplFileVersion}{\ExplFileDescription}
7590 \__expl_package_check:
7591 
```

\l_msg_internal_tl A general scratch for the module.

```

7592 \tl_new:N \l_msg_internal_tl
(End definition for \l_msg_internal_tl This variable is documented on page ??.)
```

17.1 Creating messages

Messages are created and used separately, so there are two parts to the code here. First, a mechanism for creating message text. This is pretty simple, as there is not actually a lot to do.

\c__msg_text_prefix_tl Locations for the text of messages.

```
7593 \tl_const:Nn \c__msg_text_prefix_tl      { msg-text->~ }
7594 \tl_const:Nn \c__msg_more_text_prefix_tl { msg-extra-text->~ }
(End definition for \c__msg_text_prefix_tl and \c__msg_more_text_prefix_tl These variables are documented on page ??.)
```

\msg_if_exist:p:nn Test whether the control sequence containing the message text exists or not.

```
7595 \prg_new_conditional:Npnn \msg_if_exist:nn #1#2 { p , T , F , TF }
7596 {
7597   \cs_if_exist:cTF { \c__msg_text_prefix_tl #1 / #2 }
7598   { \prg_return_true: } { \prg_return_false: }
7599 }
```

(End definition for \msg_if_exist:nn These functions are documented on page 138.)

__chk_if_free_msg:nn This auxiliary is similar to __chk_if_free_cs:N, and is used when defining messages with \msg_new:nnnn. It could be inlined in \msg_new:nnnn, but the experimental l3trace module needs to disable this check when reloading a package with the extra tracing information.

```
7600 \cs_new_protected:Npn \__chk_if_free_msg:nn #1#2
7601 {
7602   \msg_if_exist:nnT {#1} {#2}
7603   {
7604     \__msg_kernel_error:nnxx { kernel } { message-already-defined }
7605     {#1} {#2}
7606   }
7607 }
7608 {*package}
7609 \tex_ifodd:D \l@expl@log@functions@bool
7610 \cs_gset_protected:Npn \__chk_if_free_msg:nn #1#2
7611 {
7612   \msg_if_exist:nnT {#1} {#2}
7613   {
7614     \__msg_kernel_error:nnxx { kernel } { message-already-defined }
7615     {#1} {#2}
7616   }
7617   \iow_log:x { Defining-message- #1 / #2 ~\msg_line_context: }
7618 }
7619 \fi:
7620 
```

(End definition for __chk_if_free_msg:nn)

```

\msg_new:nnn
\msg_new:nn
\msg_gset:nnn
\msg_gset:nn
\msg_set:nnn
\msg_set:nn

7621 \cs_new_protected:Npn \msg_new:nnnn #1#2
7622 {
7623   \__chk_if_free_msg:nn {#1} {#2}
7624   \msg_gset:nnnn {#1} {#2}
7625 }
7626 \cs_new_protected:Npn \msg_new:nn #1#2#3
7627 { \msg_new:nnnn {#1} {#2} {#3} { } }
7628 \cs_new_protected:Npn \msg_set:nnnn #1#2#3#4
7629 {
7630   \cs_set:cpn { \c_msg_text_prefix_tl #1 / #2 }
7631     ##1##2##3##4 {#3}
7632   \cs_set:cpn { \c_msg_more_text_prefix_tl #1 / #2 }
7633     ##1##2##3##4 {#4}
7634 }
7635 \cs_new_protected:Npn \msg_set:nnn #1#2#3
7636 { \msg_set:nnnn {#1} {#2} {#3} { } }
7637 \cs_new_protected:Npn \msg_gset:nnnn #1#2#3#4
7638 {
7639   \cs_gset:cpn { \c_msg_text_prefix_tl #1 / #2 }
7640     ##1##2##3##4 {#3}
7641   \cs_gset:cpn { \c_msg_more_text_prefix_tl #1 / #2 }
7642     ##1##2##3##4 {#4}
7643 }
7644 \cs_new_protected:Npn \msg_gset:nnn #1#2#3
7645 { \msg_gset:nnnn {#1} {#2} {#3} { } }

(End definition for \msg_new:nnnn and \msg_new:nn These functions are documented on page ??.)
```

17.2 Messages: support functions and text

Simple pieces of text for messages.

```

\c_msg_coding_error_text_tl
\c_msg_continue_text_tl
\c_msg_critical_text_tl
\c_msg_fatal_text_tl
\c_msg_help_text_tl
\c_msg_no_info_text_tl
\c_msg_on_line_text_tl
\c_msg_return_text_tl
\c_msg_trouble_text_tl

7646 \tl_const:Nn \c_msg_coding_error_text_tl
7647 {
7648   This-is-a-coding-error.
7649   \\ \\
7650 }
7651 \tl_const:Nn \c_msg_continue_text_tl
7652 { Type-<return>-to-continue }
7653 \tl_const:Nn \c_msg_critical_text_tl
7654 { Reading-the-current-file-will-stop }
7655 \tl_const:Nn \c_msg_fatal_text_tl
7656 { This-is-a-fatal-error:-LaTeX-will-abort }
7657 \tl_const:Nn \c_msg_help_text_tl
7658 { For-immediate-help-type-H-<return> }
7659 \tl_const:Nn \c_msg_no_info_text_tl
7660 {
7661   LaTeX-does-not-know-anything-more-about-this-error,-sorry.
7662   \c_msg_return_text_tl
```

```

7663   }
7664 \tl_const:Nn \c_msg_on_line_text_tl { on-line }
7665 \tl_const:Nn \c_msg_return_text_tl
7666 {
7667   \\ \\
7668 Try~typing~<return>~to~proceed.
7669 \\
7670 If~that~doesn't~work,~type~X~<return>~to~quit.
7671 }
7672 \tl_const:Nn \c_msg_trouble_text_tl
7673 {
7674   \\ \\
7675 More~errors~will~almost~certainly~follow: \\
7676   the~LaTeX~run~should~be~aborted.
7677 }
(End definition for \c_msg_coding_error_text_tl and others. These variables are documented on page ??.)
```

\msg_line_number: For writing the line number nicely. **\msg_line_context:** was set up earlier, so this is not new.

```

7678 \cs_new_nopar:Npn \msg_line_number: { \int_use:N \tex_inputlineno:D }
7679 \cs_gset_nopar:Npn \msg_line_context:
7680 {
7681   \c_msg_on_line_text_tl
7682   \c_space_tl
7683   \msg_line_number:
7684 }
(End definition for \msg_line_number: and \msg_line_context: These functions are documented on page 138.)
```

17.3 Showing messages: low level mechanism

\msg_interrupt:nnn The low-level interruption macro is rather opaque, unfortunately. Depending on the availability of more information there is a choice of how to set up the further help. We feed the extra help text and the message itself to a wrapping auxiliary, in this order because we must first setup TeX's \errhelp register before issuing an \errmessage.

```

7685 \cs_new_protected:Npn \msg_interrupt:nnn #1#2#3
7686 {
7687   \tl_if_empty:nTF {#3}
7688   {
7689     \__msg_interrupt_wrap:nn { \\ \c_msg_no_info_text_tl }
7690     {#1 \\ \\ #2 \\ \\ \c_msg_continue_text_tl }
7691   }
7692   {
7693     \__msg_interrupt_wrap:nn { \\ #3 }
7694     {#1 \\ \\ #2 \\ \\ \c_msg_help_text_tl }
7695   }
7696 }
```

(End definition for \msg_interrupt:nnn This function is documented on page 142.)

```
\_\_msg_interrupt_wrap:nn
\_\_msg_interrupt_more_text:n
```

First setup TeX's `\errhelp` register with the extra help #1, then build a nice-looking error message with #2. Everything is done using x-type expansion as the new line markers are different for the two type of text and need to be correctly set up. The auxiliary `__msg_interrupt_more_text:n` receives its argument as a line-wrapped string, which is thus unaffected by expansion.

```
7697 \cs_new_protected:Npn \_\_msg_interrupt_wrap:nn #1#2
7698 {
7699   \iow_wrap:nnnN {#1} { | ~ } { } \_\_msg_interrupt_more_text:n
7700   \iow_wrap:nnnN {#2} { ! ~ } { } \_\_msg_interrupt_text:n
7701 }
7702 \cs_new_protected:Npn \_\_msg_interrupt_more_text:n #1
7703 {
7704   \exp_args:Nx \tex_errhelp:D
7705   {
7706     | , , , , , , , , , , , , , , , , , , , , ,
7707     #1 \iow_newline:
7708     | ..... .
7709   }
7710 }
```

(End definition for `__msg_interrupt_wrap:nn`. This function is documented on page 142.)

```
\_\_msg_interrupt_text:n
```

The business end of the process starts by producing some visual separation of the message from the main part of the log. The error message needs to be printed with everything made “invisible”: TeX's own information involves the macro in which `\errmessage` is called, and the end of the argument of the `\errmessage`, including the closing brace. We use an active ! to call the `\errmessage` primitive, and end its argument with `\use_none:n {⟨dots⟩}` which fills the output with dots. Two trailing closing braces are turned into spaces to hide them as well. The group in which we alter the definition of the active ! is closed before producing the message: this ensures that tokens inserted by typing I in the command-line will be inserted after the message is entirely cleaned up.

```
7711 \group_begin:
7712   \char_set_lccode:nn {'\{} {'\}
7713   \char_set_lccode:nn {'\}} {'\}
7714   \char_set_lccode:nn {'\&} {'\!}
7715   \char_set_catcode_active:N \&
7716 \tl_to_lowercase:n
7717 {
7718   \group_end:
7719   \cs_new_protected:Npn \_\_msg_interrupt_text:n #1
7720   {
7721     \iow_term:x
7722     {
7723       \iow_newline:
7724       !!!!!!!!
7725       \iow_newline:
7726       !
7727     }
7728   \group_begin:
```

```

7729         \cs_set_protected_nopar:Npn &
7730         {
7731             \tex_errmessage:D
7732             {
7733                 #1
7734                 \use_none:n
7735                 { ..... }
7736             }
7737         }
7738         \exp_after:wN
7739         \group_end:
7740         &
7741     }
7742 }
```

(End definition for `_msg_interrupt_text:n`)

`\msg_log:n` Printing to the log or terminal without a stop is rather easier. A bit of simple visual work sets things off nicely.

```

7743 \cs_new_protected:Npn \msg_log:n #1
7744 {
7745     \iow_log:n { ..... }
7746     \iow_wrap:nnnN { . ~ #1} { . ~ } { } \iow_log:n
7747     \iow_log:n { ..... }
7748 }
7749 \cs_new_protected:Npn \msg_term:n #1
7750 {
7751     \iow_term:n { **** }
7752     \iow_wrap:nnnN { * ~ #1} { * ~ } { } \iow_term:n
7753     \iow_term:n { **** }
7754 }
```

(End definition for `\msg_log:n` This function is documented on page 143.)

17.4 Displaying messages

L^AT_EX is handling error messages and so the T_EX ones are disabled. This is already done by the L^AT_EX 2_ε kernel, so to avoid messing up any deliberate change by a user this is only set in format mode.

```

7755 <*initex>
7756 \int_gset_eq:NN \tex_errorcontextlines:D \c_minus_one
7757 </initex>
```

`\msg_fatal_text:n` A function for issuing messages: both the text and order could in principle vary.

```

7758 \cs_new:Npn \msg_fatal_text:n #1 { Fatal~#1~error }
7759 \cs_new:Npn \msg_critical_text:n #1 { Critical~#1~error }
7760 \cs_new:Npn \msg_error_text:n #1 { #1~error }
7761 \cs_new:Npn \msg_warning_text:n #1 { #1~warning }
7762 \cs_new:Npn \msg_info_text:n #1 { #1~info }
```

(End definition for `\msg_fatal_text:n` and others. These functions are documented on page 139.)

\msg_see_documentation_text:n

Contextual footer information. The L^AT_EX module only comprises L^AT_EX3 code, so we refer to the L^AT_EX3 documentation rather than simply “L^AT_EX”.

```
7763 \cs_new:Npn \msg_see_documentation_text:n #1
7764 {
7765   \\ \\ See-the-
7766   \str_if_eq:nnTF {#1} { LaTeX } { LaTeX3 } {#1} ~
7767   documentation-for-further-information.
7768 }
```

(End definition for \msg_see_documentation_text:n This function is documented on page 139.)

__msg_class_new:nn

```
7769 \group_begin:
7770   \cs_set_protected:Npn \__msg_class_new:nn #1#2
7771   {
7772     \prop_new:c { l__msg_redirect_ #1 _prop }
7773     \cs_new_protected:cpx { __msg_ #1 _code:nnnnnn } ##1##2##3##4##5##6 {#2}
7774     \cs_new_protected:cpx { msg_ #1 :nnnnnn } ##1##2##3##4##5##6
7775     {
7776       \use:x
7777       {
7778         \exp_not:n { \__msg_use:nnnnnnn {#1} {##1} {##2} }
7779         { \tl_to_str:n {##3} } { \tl_to_str:n {##4} }
7780         { \tl_to_str:n {##5} } { \tl_to_str:n {##6} }
7781       }
7782     }
7783     \cs_new_protected:cpx { msg_ #1 :nnnnn } ##1##2##3##4##5
7784     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} {##5} { } }
7785     \cs_new_protected:cpx { msg_ #1 :nnnn } ##1##2##3##4
7786     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} { } { } }
7787     \cs_new_protected:cpx { msg_ #1 :nnn } ##1##2##3
7788     { \exp_not:c { msg_ #1 :nnnnnnn } {##1} {##2} {##3} { } { } { } }
7789     \cs_new_protected:cpx { msg_ #1 :nn } ##1##2##3
7790     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} { } { } { } { } }
7791     \cs_new_protected:cpx { msg_ #1 :nnxxxx } ##1##2##3##4##5##6
7792     {
7793       \use:x
7794       {
7795         \exp_not:N \exp_not:n
7796         { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} }
7797         {##3} {##4} {##5} {##6}
7798       }
7799     }
7800     \cs_new_protected:cpx { msg_ #1 :nnxxxx } ##1##2##3##4##5
7801     { \exp_not:c { msg_ #1 :nnxxxxx } {##1} {##2} {##3} {##4} {##5} { } }
7802     \cs_new_protected:cpx { msg_ #1 :nnxx } ##1##2##3##4
7803     { \exp_not:c { msg_ #1 :nnxxxxx } {##1} {##2} {##3} {##4} { } { } }
7804     \cs_new_protected:cpx { msg_ #1 :nnx } ##1##2##3
7805     { \exp_not:c { msg_ #1 :nnxxxxx } {##1} {##2} {##3} { } { } { } }
7806 }
```

(End definition for `__msg_class_new:nn`. This function is documented on page ??.)

`\msg_fatal:nnnnn`

For fatal errors, after the error message TeX bails out.

```
7807   \__msg_class_new:nn { fatal }
7808   {
7809     \msg_interrupt:nnn
7810     { \msg_fatal_text:n {#1} : ~ "#2" }
7811     {
7812       \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
7813       \msg_see_documentation_text:n {#1}
7814     }
7815     { \c_msg_fatal_text_tl }
7816     \tex_end:D
7817 }
```

(End definition for `\msg_fatal:nnnnn` and others. These functions are documented on page ??.)

`\msg_critical:nnnnnn`

Not quite so bad: just end the current file.

```
7818   \__msg_class_new:nn { critical }
7819   {
7820     \msg_interrupt:nnn
7821     { \msg_critical_text:n {#1} : ~ "#2" }
7822     {
7823       \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
7824       \msg_see_documentation_text:n {#1}
7825     }
7826     { \c_msg_critical_text_tl }
7827     \tex_endinput:D
7828 }
```

(End definition for `\msg_critical:nnnnnn` and others. These functions are documented on page ??.)

`\msg_error:nnnnnn`

For an error, the interrupt routine is called. We check if there is a “more text” by comparing that control sequence with a permanently empty text.

```
7829   \__msg_class_new:nn { error }
7830   {
7831     \__msg_error:cnnnnn
7832     { \c__msg_more_text_prefix_tl #1 / #2 }
7833     {#3} {#4} {#5} {#6}
7834     {
7835       \msg_interrupt:nnn
7836       { \msg_error_text:n {#1} : ~ "#2" }
7837       {
7838         \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
7839         \msg_see_documentation_text:n {#1}
7840       }
7841     }
7842   }
7843 \cs_new_protected:Npn \__msg_error:cnnnnn #1#2#3#4#5#6
7844   {
7845     \cs_if_eq:cNTF {#1} \__msg_no_more_text:nnnn
```

```

7846      { #6 { } }
7847      { #6 { \use:c {#1} {#2} {#3} {#4} {#5} } }
7848    }
7849  \cs_new:Npn \__msg_no_more_text:nnnn #1#2#3#4 { }
(End definition for \msg_error:nnnnnn and others. These functions are documented on page ??.)
```

\msg_warning:nnnnnn Warnings are printed to the terminal.

```

7850  \__msg_class_new:nn { warning }
7851  {
7852    \msg_term:n
7853    {
7854      \msg_warning_text:n {#1} : ~ "#2" \\ \\
7855      \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
7856    }
7857  }
(End definition for \msg_warning:nnnnnn and others. These functions are documented on page ??.)
```

\msg_info:nnnnnn Information only goes into the log.

```

7858  \__msg_class_new:nn { info }
7859  {
7860    \msg_log:n
7861    {
7862      \msg_info_text:n {#1} : ~ "#2" \\ \\
7863      \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
7864    }
7865  }
(End definition for \msg_info:nnnnnn and others. These functions are documented on page ??.)
```

\msg_log:nnnnnn “Log” data is very similar to information, but with no extras added.

```

7866  \__msg_class_new:nn { log }
7867  {
7868    \iow_wrap:nnnN
7869    { \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6} }
7870    { } { } \iow_log:n
7871  }
(End definition for \msg_log:nnnnnn and others. These functions are documented on page ??.)
```

The none message type is needed so that input can be gobbled.

```

7872  \__msg_class_new:nn { none } { }
(End definition for \msg_none:nnnnnn and others. These functions are documented on page ??.)
```

End the group to eliminate __msg_class_new:nn.

```
7873 \group_end:
```

Checking that a message class exists. We build this from \cs_if_free:cTF rather than \cs_if_exist:cTF because that avoids reading the second argument earlier than necessary.

```

7874 \cs_new:Npn \__msg_class_chk_exist:nT #1
7875 {
```

```

7876     \cs_if_free:cTF { __msg_ #1 _code:nnnnnn }
7877     { __msg_kernel_error:n { kernel } { message-class-unknown } {#1} }
7878   }
(End definition for \__msg_class_chk_exist:nT)

\l__msg_class_tl Support variables needed for the redirection system.
\l__msg_current_class_tl
7879 \tl_new:N \l__msg_class_tl
7880 \tl_new:N \l__msg_current_class_tl
(End definition for \l__msg_class_tl and \l__msg_current_class_tl These variables are documented
on page ??.)

\l__msg_redirect_prop For redirection of individually-named messages
7881 \prop_new:N \l__msg_redirect_prop
(End definition for \l__msg_redirect_prop This variable is documented on page ??.)

\l__msg_hierarchy_seq During redirection, split the message name into a sequence with items{/module/submodule},
{/module}, and {}.
7882 \seq_new:N \l__msg_hierarchy_seq
(End definition for \l__msg_hierarchy_seq This variable is documented on page ??.)

\l__msg_class_loop_seq Classes encountered when following redirections to check for loops.
7883 \seq_new:N \l__msg_class_loop_seq
(End definition for \l__msg_class_loop_seq This variable is documented on page ??.)

\__msg_use:nnnnnnn Actually using a message is a multi-step process. First, some safety checks on the message
\__msg_use_redirect_name:n and class requested. The code and arguments are then stored to avoid passing them
\__msg_use_hierarchy:nwwN around. The assignment to \__msg_use_code: is similar to \tl_set:Nn. The message
\__msg_use_redirect_module:n is eventually produced with whatever \l__msg_class_tl is when \__msg_use_code: is
\__msg_use_code: called.

7884 \cs_new_protected:Npn \__msg_use:nnnnnnn #1#2#3#4#5#6#7
7885   {
7886     \msg_if_exist:nnTF {#2} {#3}
7887     {
7888       \__msg_class_chk_exist:nT {#1}
7889       {
7890         \tl_set:Nn \l__msg_current_class_tl {#1}
7891         \cs_set_protected_nopar:Npx \__msg_use_code:
7892         {
7893           \exp_not:n
7894           {
7895             \use:c { __msg_ \l__msg_class_tl _code:nnnnnn }
7896             {#2} {#3} {#4} {#5} {#6} {#7}
7897           }
7898         }
7899       \__msg_use_redirect_name:n { #2 / #3 }
7900     }
7901   }
7902   { \__msg_kernel_error:n { kernel } { message-unknown } {#2} {#3} }
7903 }
7904 \cs_new_protected_nopar:Npn \__msg_use_code: { }


```

The first check is for a individual message redirection. If this applies then no further redirection is attempted. Otherwise, split the message name into `module/submodule/message` (with an arbitrary number of slashes), and store `{/module/submodule}`, `{/module}` and `{}` into `\l__msg_hierarchy_seq`. We will then map through this sequence, applying the most specific redirection.

```

7905 \cs_new_protected:Npn \__msg_use_redirect_name:n #1
7906 {
7907     \prop_get:NnNTF \l__msg_redirect_prop { / #1 } \l__msg_class_tl
7908         { \__msg_use_code: }
7909         {
7910             \seq_clear:N \l__msg_hierarchy_seq
7911             \__msg_use_hierarchy:nwwN { }
7912                 #1 \q_mark \__msg_use_hierarchy:nwwN
7913                 / \q_mark \use_none_delimit_by_q_stop:w
7914                 \q_stop
7915             \__msg_use_redirect_module:n { }
7916         }
7917     }
7918 \cs_new_protected:Npn \__msg_use_hierarchy:nwwN #1#2 / #3 \q_mark #4
7919 {
7920     \seq_put_left:Nn \l__msg_hierarchy_seq {#1}
7921     #4 { #1 / #2 } #3 \q_mark #4
7922 }

```

At this point, the items of `\l__msg_hierarchy_seq` are the various levels at which we should look for a redirection. Redirections which are less specific than the argument of `__msg_use_redirect_module:n` are not attempted. This argument is empty for a class redirection, `/module` for a module redirection, *etc.* Loop through the sequence to find the most specific redirection, with module `##1`. The loop is interrupted after testing for a redirection for `##1` equal to the argument `#1` (least specific redirection allowed). When a redirection is found, break the mapping, then if the redirection targets the same class, output the code with that class, and otherwise set the target as the new current class, and search for further redirections. Those redirections should be at least as specific as `##1`.

```

7923 \cs_new_protected:Npn \__msg_use_redirect_module:n #1
7924 {
7925     \seq_map_inline:Nn \l__msg_hierarchy_seq
7926     {
7927         \prop_get:cnNTF { l__msg_redirect_ \l__msg_current_class_tl _prop }
7928             {##1} \l__msg_class_tl
7929             {
7930                 \seq_map_break:n
7931                 {
7932                     \tl_if_eq:NNTF \l__msg_current_class_tl \l__msg_class_tl
7933                         { \__msg_use_code: }
7934                         {
7935                             \tl_set_eq:NN \l__msg_current_class_tl \l__msg_class_tl
7936                             \__msg_use_redirect_module:n {##1}
7937                         }
7938                 }
7939             }
7940         }
7941     }
7942 }
7943 
```

```

7938     }
7939   }
7940   {
7941     \str_if_eq:nnt {##1} {#1}
7942     {
7943       \tl_set_eq:NN \l__msg_class_tl \l__msg_current_class_tl
7944       \seq_map_break:n { \__msg_use_code: }
7945     }
7946   }
7947 }
7948 }
```

(End definition for `__msg_use:nnnnnnn` This function is documented on page ??.)

`\msg_redirect_name:nnn`

Named message will always use the given class even if that class is redirected further. An empty target class cancels any existing redirection for that message.

```

7949 \cs_new_protected:Npn \msg_redirect_name:nnn #1#2#3
7950   {
7951     \tl_if_empty:nTF {#3}
7952       { \prop_remove:Nn \l__msg_redirect_prop { / #1 / #2 } }
7953     {
7954       \__msg_class_chk_exist:nT {#3}
7955         { \prop_put:Nnn \l__msg_redirect_prop { / #1 / #2 } {#3} }
7956     }
7957 }
```

(End definition for `\msg_redirect_name:nnn` This function is documented on page 142.)

`\msg_redirect_class:nn \msg_redirect_module:nnn`

If the target class is empty, eliminate the corresponding redirection. Otherwise, add the redirection. We must then check for a loop: as an initialization, we start by storing the initial class in `\l__msg_current_class_tl`.

```

7958 \cs_new_protected_nopar:Npn \msg_redirect_class:nn
7959   { \__msg_redirect:nnn { } }
7960 \cs_new_protected:Npn \msg_redirect_module:nnn #1
7961   { \__msg_redirect:nnn { / #1 } }
7962 \cs_new_protected:Npn \__msg_redirect:nnn #1#2#3
7963   {
7964     \__msg_class_chk_exist:nT {#2}
7965     {
7966       \tl_if_empty:nTF {#3}
7967         { \prop_remove:cN { l__msg_redirect_ #2 _prop } {#1} }
7968       {
7969         \__msg_class_chk_exist:nT {#3}
7970           {
7971             \prop_put:cnn { l__msg_redirect_ #2 _prop } {#1} {#3}
7972             \tl_set:Nn \l__msg_current_class_tl {#2}
7973             \seq_clear:N \l__msg_class_loop_seq
7974             \__msg_redirect_loop_chk:nnn {#2} {#3} {#1}
7975           }
7976         }
7977 }
```

```
7978 }
```

Since multiple redirections can only happen with increasing specificity, a loop requires that all steps are of the same specificity. The new redirection can thus only create a loop with other redirections for the exact same module, #1, and not submodules. After some initialization above, follow redirections with \l__msg_class_t1, and keep track in \l__msg_class_loop_seq of the various classes encountered. A redirection from a class to itself, or the absence of redirection both mean that there is no loop. A redirection to the initial class marks a loop. To break it, we must decide which redirection to cancel. The user most likely wants the newly added redirection to hold with no further redirection. We thus remove the redirection starting from #2, target of the new redirection. Note that no message is emitted by any of the underlying functions: otherwise we may get an infinite loop because of a message from the message system itself.

```
7979 \cs_new_protected:Npn \__msg_redirect_loop_chk:nnn #1#2#3
7980 {
7981     \seq_put_right:Nn \l__msg_class_loop_seq {#1}
7982     \prop_get:cnnT { l__msg_redirect_ #1 _prop } {#3} \l__msg_class_t1
7983     {
7984         \str_if_eq_x:nnF { \l__msg_class_t1 } {#1}
7985         {
7986             \tl_if_eq:NNTF \l__msg_class_t1 \l__msg_current_class_t1
7987             {
7988                 \prop_put:cnn { l__msg_redirect_ #2 _prop } {#3} {#2}
7989                 \__msg_kernel_warning:nnxxxx { kernel } { message-redirect-loop }
7990                 { \seq_item:Nn \l__msg_class_loop_seq { \c_one } }
7991                 { \seq_item:Nn \l__msg_class_loop_seq { \c_two } }
7992                 {#3}
7993                 {
7994                     \seq_map_function:NN \l__msg_class_loop_seq
7995                         \__msg_redirect_loop_list:n
7996                         { \seq_item:Nn \l__msg_class_loop_seq { \c_one } }
7997                     }
7998                 }
7999                 { \__msg_redirect_loop_chk:onn \l__msg_class_t1 {#2} {#3} }
8000             }
8001         }
8002     }
8003 \cs_generate_variant:Nn \__msg_redirect_loop_chk:nnn { o }
8004 \cs_new:Npn \__msg_redirect_loop_list:n #1 { {#1} ~ => ~ }
(End definition for \msg_redirect_class:nn and \msg_redirect_module:nnn These functions are documented on page 142.)
```

17.5 Kernel-specific functions

__msg_kernel_new:nnnn
__msg_kernel_new:nnn
__msg_kernel_set:nnnn
__msg_kernel_set:nnn

```
8005 \cs_new_protected:Npn \__msg_kernel_new:nnnn #1#2
8006     { \msg_new:nnnn { LaTeX } { #1 / #2 } }
```

```

8007 \cs_new_protected:Npn \__msg_kernel_new:nnn #1#2
8008 { \msg_new:nnn { LaTeX } { #1 / #2 } }
8009 \cs_new_protected:Npn \__msg_kernel_set:nnnn #1#2
8010 { \msg_set:nnnn { LaTeX } { #1 / #2 } }
8011 \cs_new_protected:Npn \__msg_kernel_set:nnn #1#2
8012 { \msg_set:nnn { LaTeX } { #1 / #2 } }

(End definition for \__msg_kernel_new:nnnn and \__msg_kernel_new:nnn These functions are documented on page ???.)

```

__msg_kernel_class_new:nN
__msg_kernel_class_new_aux:nN

All the functions for kernel messages come in variants ranging from 0 to 4 arguments. Those with less than 4 arguments are defined in terms of the 4-argument variant, in a way very similar to __msg_class_new:nn. This auxiliary is destroyed at the end of the group.

```

8013 \group_begin:
8014   \cs_set_protected:Npn \__msg_kernel_class_new:nN #1
8015   { \__msg_kernel_class_new_aux:nN { kernel_ #1 } }
8016 \cs_set_protected:Npn \__msg_kernel_class_new_aux:nN #1#2
8017   {
8018     \cs_new_protected:cpx { __msg_ #1 :nnnnnn } ##1##2##3##4##5##6
8019     {
8020       \use:x
8021       {
8022         \exp_not:n { #2 { LaTeX } { ##1 / ##2 } }
8023         { \tl_to_str:n {##3} } { \tl_to_str:n {##4} }
8024         { \tl_to_str:n {##5} } { \tl_to_str:n {##6} }
8025       }
8026     }
8027     \cs_new_protected:cpx { __msg_ #1 :nnnnnn } ##1##2##3##4##5
8028     { \exp_not:c { __msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} {##5} { } }
8029   \cs_new_protected:cpx { __msg_ #1 :nnnn } ##1##2##3##4
8030   { \exp_not:c { __msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} { } { } }
8031   \cs_new_protected:cpx { __msg_ #1 :nnn } ##1##2##3
8032   { \exp_not:c { __msg_ #1 :nnnnnn } {##1} {##2} {##3} { } { } { } }
8033   \cs_new_protected:cpx { __msg_ #1 :nn } ##1##2
8034   { \exp_not:c { __msg_ #1 :nnnnnn } {##1} {##2} { } { } { } { } }
8035   \cs_new_protected:cpx { __msg_ #1 :nnxxxx } ##1##2##3##4##5##6
8036   {
8037     \use:x
8038     {
8039       \exp_not:N \exp_not:n
8040       { \exp_not:c { __msg_ #1 :nnnnnn } {##1} {##2} }
8041       {##3} {##4} {##5} {##6}
8042     }
8043   }
8044   \cs_new_protected:cpx { __msg_ #1 :nnxxxx } ##1##2##3##4##5
8045   { \exp_not:c { __msg_ #1 :nnxxxx } {##1} {##2} {##3} {##4} {##5} { } }
8046   \cs_new_protected:cpx { __msg_ #1 :nnxx } ##1##2##3##4
8047   { \exp_not:c { __msg_ #1 :nnxxxx } {##1} {##2} {##3} {##4} { } { } }
8048   \cs_new_protected:cpx { __msg_ #1 :nnx } ##1##2##3

```

```
8049     { \exp_not:c { __msg_ #1 :nxxxxx } {##1} {##2} {##3} { } { } { } }
8050 }
```

(End definition for `__msg_kernel_class_new:nN`. This function is documented on page ??.)

(End definition for \msg kernel class new:nN This function is documented on page ??.)

Neither fatal kernel errors nor kernel errors can be redirected. We directly use the code for (non-kernel) fatal errors and errors, adding the “`LATEX`” module name. Three functions are already defined by `l3basics`; we need to undefine them to avoid errors.

```
8051 \_\_msg_kernel_class_new:nN { fatal } \_\_msg_fatal_code:nnnnnn  
8052 \cs_undefine:N \_\_msg_kernel_error:nxxx  
8053 \cs_undefine:N \_\_msg_kernel_error:nnx  
8054 \cs_undefine:N \_\_msg_kernel_error:nn  
8055 \_\_msg_kernel_class_new:nN { error } \_\_msg_error_code:nnnnnn
```

(End definition for `_msg_kernel_fatal:nnnnn` and others. These functions are documented on page ??.)

Kernel messages which can be redirected simply use the machinery for normal messages, with the module name “`LTEX`”.

```
8056 \_\_msg_kernel_class_new:nN { warning } \msg_warning:nnxxxx  
8057 \_\_msg_kernel_class_new:nN { info } \msg_info:nnxxxx
```

(End definition for `_msg_kernel_warning:nnnnnn` and others. These functions are documented on page ??.)

End the group to eliminate __msg_kernel_class_new:nN.

8058 \group end;

Error messages needed to actually implement the message system itself.

```
8059 \__msg_kernel_new:nnnn { kernel } { message-already-defined }
8060   { Message~'#2'~for~module~'#1'~already~defined. }
8061   {
8062     \c_msg_coding_error_text_tl
8063     LaTeX-was-asked-to-define-a-new-message-called-'#2'\ \
8064     by-the-module-'#1':-this-message-already-exists.
8065     \c_msg_return_text_tl
8066   }
8067 \__msg_kernel_new:nnnn { kernel } { message-unknown }
8068   { Unknown~message~'#2'~for~module~'#1'. }
8069   {
8070     \c_msg_coding_error_text_tl
8071     LaTeX-was-asked-to-display-a-message-called-'#2'\\\
8072     by-the-module-'#1':-this-message-does-not-exist.
8073     \c_msg_return_text_tl
8074   }
8075 \__msg_kernel_new:nnnn { kernel } { message-class-unknown }
8076   { Unknown~message~class~'#1'. }
8077   {
8078     LaTeX-has-been-asked-to-redirect-messages-to-a-class-'#1'
8079     this-was-never-defined.
8080     \c_msg_return_text_tl
8081   }
8082 \__msg_kernel_new:nnnn { kernel } { message-redirect-loop }
```

```

8083 {
8084   Message~redirection~loop~caused~by~ {#1} ~=>~ {#2}
8085   \tl_if_empty:nF {#3} { ~for~module~' \use_none:n #3 ' } .
8086 }
8087 {
8088   Adding~the~message~redirection~ {#1} ~=>~ {#2}
8089   \tl_if_empty:nF {#3} { ~for~the~module~' \use_none:n #3 ' } ~
8090   created~an~infinite~loop\\\\
8091   \iow_indent:n { #4 \\\\ }
8092 }

8093 Messages for earlier kernel modules.
8094
8095 \__msg_kernel_new:nnnn { kernel } { bad-number-of-arguments }
8096   { Function~'#1'~cannot~be~defined~with~#2~arguments. }
8097   {
8098     \c_msg_error_text_tl
8099     LaTeX-has~been~asked~to~define~a~function~'#1'~with~
8100     #2~arguments. ~
8101     TeX-allows~between~0~and~9~arguments~for~a~single~function.
8102   }
8103 \__msg_kernel_new:nnnn { kernel } { command-already-defined }
8104   { Control~sequence~#1~already~defined. }
8105   {
8106     \c_msg_error_text_tl
8107     LaTeX-has~been~asked~to~create~a~new~control~sequence~'#1'~
8108     but~this~name~has~already~been~used~elsewhere. \\ \\
8109     The~current~meaning~is:\\
8110     \\ \\ #2
8111   }
8112 \__msg_kernel_new:nnnn { kernel } { command-not-defined }
8113   { Control~sequence~#1~undefined. }
8114   {
8115     \c_msg_error_text_tl
8116     LaTeX-has~been~asked~to~use~a~command~#1,~but~this~has~not~
8117     been~defined~yet.
8118   }
8119 \__msg_kernel_new:nnnn { kernel } { empty-search-pattern }
8120   { Empty~search~pattern. }
8121   {
8122     \c_msg_error_text_tl
8123     LaTeX-has~been~asked~to~replace~an~empty~pattern~by~'#1':~that~
8124     would~lead~to~an~infinite~loop!
8125   }
8126 \__msg_kernel_new:nnnn { kernel } { out-of-registers }
8127   { No~room~for~a~new~#1. }
8128   {
8129     TeX-only~supports~\int_use:N \c_max_register_int \
8130     of~each~type.~All~the~#1~registers~have~been~used.~
8131     This~run~will~be~aborted~now.
8132   }

```

```

8131 \_\_msg_kernel_new:nnnn { kernel } { missing-colon }
8132   { Function~'#1'~contains~no~':'. }
8133   {
8134     \c_msg_coding_error_text_tl
8135     Code-level~functions~must~contain~':~to~separate~the~
8136     argument~specification~from~the~function~name.~This~is~
8137     needed~when~defining~conditionals~or~variants,~or~when~building~a~
8138     parameter~text~from~the~number~of~arguments~of~the~function.
8139   }
8140 \_\_msg_kernel_new:nnnn { kernel } { protected-predicate }
8141   { Predicate~'#1'~must~be~expandable. }
8142   {
8143     \c_msg_coding_error_text_tl
8144     LaTeX~has~been~asked~to~define~'#1'~as~a~protected~predicate.~
8145     Only~expandable~tests~can~have~a~predicate~version.
8146   }
8147 \_\_msg_kernel_new:nnnn { kernel } { conditional-form-unknown }
8148   { Conditional~form~'#1'~for~function~'#2'~unknown. }
8149   {
8150     \c_msg_coding_error_text_tl
8151     LaTeX~has~been~asked~to~define~the~conditional~form~'#1'~of~
8152     the~function~'#2',~but~only~'TF',~'T',~'F',~and~'p'~forms~exist.
8153   }
8154 \_\_msg_kernel_new:nnnn { kernel } { scanmark-already-defined }
8155   { Scan-mark~#1~already~defined. }
8156   {
8157     \c_msg_coding_error_text_tl
8158     LaTeX~has~been~asked~to~create~a~new~scan~mark~'#1'~
8159     but~this~name~has~already~been~used~for~a~scan~mark.
8160   }
8161 \_\_msg_kernel_new:nnnn { kernel } { variable-not-defined }
8162   { Variable~#1~undefined. }
8163   {
8164     \c_msg_coding_error_text_tl
8165     LaTeX~has~been~asked~to~show~a~variable~#1,~but~this~has~not~
8166     been~defined~yet.
8167   }
8168 \_\_msg_kernel_new:nnnn { kernel } { variant-too-long }
8169   { Variant~form~'#1'~longer~than~base~signature~of~'#2'. }
8170   {
8171     \c_msg_coding_error_text_tl
8172     LaTeX~has~been~asked~to~create~a~variant~of~the~function~'#2'~
8173     with~a~signature~starting~with~'#1',~but~that~is~longer~than~
8174     the~signature~(part~after~the~colon)~of~'#2'.
8175   }
8176 \_\_msg_kernel_new:nnnn { kernel } { invalid-variant }
8177   { Variant~form~'#1'~invalid~for~base~form~'#2'. }
8178   {
8179     \c_msg_coding_error_text_tl
8180     LaTeX~has~been~asked~to~create~a~variant~of~the~function~'#2'~

```

```

8181     with-a-signature-starting-with-'#1', ~but~cannot~change~an~argument~
8182     from-type-'#3'~to~type-'#4'.
8183 }
```

Some errors only appear in expandable settings, hence don't need a "more-text" argument.

```

8184 \__msg_kernel_new:nnn { kernel } { bad-variable }
8185   { Erroneous~variable~#1 used! }
8186 \__msg_kernel_new:nnn { kernel } { misused-sequence }
8187   { A~sequence~was~misused. }
8188 \__msg_kernel_new:nnn { kernel } { negative-replication }
8189   { Negative~argument~for~\prg_replicate:nn. }
8190 \__msg_kernel_new:nnn { kernel } { unknown-comparison }
8191   { Relation~symbol~'#1'~unknown:~use~=,~<,~>,~==,~!=,~<=,~>=. }
8192 \__msg_kernel_new:nnn { kernel } { zero-step }
8193   { Zero~step~size~for~step~function~#1. }
```

Messages used by the "show" functions.

```

8194 \__msg_kernel_new:nnn { kernel } { show-clist }
8195 {
8196   The~comma~list~
8197   \str_if_eq:nnF {#1} { \l__clist_internal_clist } { \token_to_str:N #1~}
8198   \clist_if_empty:NTF #1
8199   { is~empty }
8200   { contains~the~items~(without~outer~braces): }
8201 }
8202 \__msg_kernel_new:nnn { kernel } { show-prop }
8203 {
8204   The~property~list~\token_to_str:N #1~
8205   \prop_if_empty:NTF #1
8206   { is~empty }
8207   { contains~the~pairs~(without~outer~braces): }
8208 }
8209 \__msg_kernel_new:nnn { kernel } { show-seq }
8210 {
8211   The~sequence~\token_to_str:N #1~
8212   \seq_if_empty:NTF #1
8213   { is~empty }
8214   { contains~the~items~(without~outer~braces): }
8215 }
8216 \__msg_kernel_new:nnn { kernel } { show-no-stream }
8217 { No~ #1 ~streams~are~open }
8218 \__msg_kernel_new:nnn { kernel } { show-open-streams }
8219 { The~following~ #1 ~streams~are~in~use: }
```

17.6 Expandable errors

`__msg_expandable_error:n`
`__msg_expandable_error:w`

In expansion only context, we cannot use the normal means of reporting errors. Instead, we feed TEX an undefined control sequence, `\LaTeX3 error:`. It is thus interrupted, and shows the context, which thanks to the odd-looking `\use:n` is

```
<argument> \LaTeX3 error:  
The error message.
```

In other words, \TeX is processing the argument of $\use:n$, which is $\text{\LaTeX3 error:} \langle\text{error message}\rangle$. Then $\text{_msg_expandable_error:w}$ cleans up. In fact, there is an extra subtlety: if the user inserts tokens for error recovery, they should be kept. Thus we also use an odd space character (with category code 7) and keep tokens until that space character, dropping everything else until \q_stop . The \c_zero prevents losing braces around the user-inserted text if any, and stops the expansion of \romannumeral .

```
8220 \group_begin:  
8221 \char_set_catcode_math_superscript:N ^  
8222 \char_set_lccode:nn { `^ } { `\\` }  
8223 \char_set_lccode:nn { `L } { `L }  
8224 \char_set_lccode:nn { `T } { `T }  
8225 \char_set_lccode:nn { `X } { `X }  
8226 \tl_to_lowercase:n  
8227 {  
8228   \cs_new:Npx \_msg_expandable_error:n #1  
8229   {  
8230     \exp_not:n  
8231     {  
8232       \tex_romannumeral:D  
8233       \exp_after:wN \exp_after:wN  
8234       \exp_after:wN \_msg_expandable_error:w  
8235       \exp_after:wN \exp_after:wN  
8236       \exp_after:wN \c_zero  
8237     }  
8238     \exp_not:N \use:n { \exp_not:c { \LaTeX3~error: } ^ #1 } ^  
8239   }  
8240   \cs_new:Npn \_msg_expandable_error:w #1 ^ #2 ^ { #1 }  
8241 }  
8242 \group_end:  
(End definition for  $\text{\_msg_expandable_error:n}$  This function is documented on page 145.)
```

$\text{_msg_kernel_expandable_error:nnnnnn}$
 $\text{_msg_kernel_expandable_error:nnnn}$
 $\text{_msg_kernel_expandable_error:nnnn}$
 $\text{_msg_kernel_expandable_error:nnn}$
 $\text{_msg_kernel_expandable_error:nn}$

```
8243 \cs_new:Npn \_msg_kernel_expandable_error:nnnnnn #1#2#3#4#5#6  
8244 {  
8245   \exp_args:Nf \_msg_expandable_error:n  
8246   {  
8247     \exp_args:NNc \exp_after:wN \exp_stop_f:  
8248     { \c_msg_text_prefix_tl \LaTeX / #1 / #2 }  
8249     {#3} {#4} {#5} {#6}  
8250   }  
8251 }  
8252 \cs_new:Npn \_msg_kernel_expandable_error:nnnnn #1#2#3#4#5  
8253 {  
8254   \_msg_kernel_expandable_error:nnnnnn  
8255   {#1} {#2} {#3} {#4} {#5} { }  
8256 }
```

```

8256   }
8257 \cs_new:Npn \__msg_kernel_expandable_error:nnnn #1#2#3#4
8258 {
8259   \__msg_kernel_expandable_error:nnnnnn
8260   {#1} {#2} {#3} {#4} { } { }
8261 }
8262 \cs_new:Npn \__msg_kernel_expandable_error:nnn #1#2#3
8263 {
8264   \__msg_kernel_expandable_error:nnnnnn
8265   {#1} {#2} {#3} { } { } { }
8266 }
8267 \cs_new:Npn \__msg_kernel_expandable_error:nn #1#2
8268 {
8269   \__msg_kernel_expandable_error:nnnnnn
8270   {#1} {#2} { } { } { } { }
8271 }

(End definition for \__msg_kernel_expandable_error:nnnnnn and others. These functions are documented on page ??.)

```

17.7 Showing variables

Functions defined in this section are used for diagnostic functions in `\clist`, `\file`, `\prop`, `\seq`, `\template`

`__msg_term:nnnnnn`
`__msg_term:nnnnnV`

`__msg_term:nnnnn`
`__msg_term:nnn`
`__msg_term:nn`

```

8272 \cs_new_protected:Npn \__msg_term:nnnnnn #1#2#3#4#5#6
8273 {
8274   \iow_wrap:nnnN
8275   { \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6} }
8276   { } { } \iow_term:
8277 }
8278 \cs_generate_variant:Nn \__msg_term:nnnnnn { nnnnnV }
8279 \cs_new_protected:Npn \__msg_term:nnnnn #1#2#3#4#5
8280 { \__msg_term:nnnnnn {#1} {#2} {#3} {#4} {#5} { } }
8281 \cs_new_protected:Npn \__msg_term:nnn #1#2#3
8282 { \__msg_term:nnnnnn {#1} {#2} {#3} { } { } { } }
8283 \cs_new_protected:Npn \__msg_term:nn #1#2
8284 { \__msg_term:nnnnnn {#1} {#2} { } { } { } { } }

(End definition for \__msg_term:nnnnnn and \__msg_term:nnnnnV These functions are documented on page ??.)

```

The arguments of `__msg_show_variable:Nnn` are

- The $\langle variable \rangle$ to be shown.
- The type of the variable.
- A mapping of the form `\seq_map_function:NN` $\langle variable \rangle$ `__msg_show_item:n`, which produces the formatted string.

As for `__kernel_register_show:N`, check that the variable is defined. If it is, output the introductory message, then show the contents #3 using `__msg_show_variable:n`. This wraps the contents (with leading `>_L`) to a fixed number of characters per line. The expansion of #3 may either be empty or start with `>_L`. A leading `>`, if present, is removed using a w-type auxiliary, as well as a space following it (via f-expansion). Note that we cannot remove the space as a delimiter for the w-type auxiliary, because a line-break may be taken there, and the space would then disappear. Finally, the resulting token list `\l__msg_internal_tl` is displayed to the terminal, with an odd `\exp_after:wN` which expands the closing brace to improve the output slightly.

```

8285 \cs_new_protected:Npn \__msg_show_variable:Nnn #1#2#3
8286 {
8287     \cs_if_exist:NTF #1
8288     {
8289         \__msg_term:nnn { LaTeX / kernel } { show- #2 } {#1}
8290         \__msg_show_variable:n {#3}
8291     }
8292     {
8293         \__msg_kernel_error:nnx { kernel } { variable-not-defined }
8294         { \token_to_str:N #1 }
8295     }
8296 }
8297 \cs_new_protected:Npn \__msg_show_variable:n #1
8298 { \iow_wrap:nnnN {#1} { } { } \__msg_show_variable_aux:n }
8299 \cs_new_protected:Npn \__msg_show_variable_aux:n #1
8300 {
8301     \tl_if_empty:nTF {#1}
8302     { \tl_clear:N \l__msg_internal_tl }
8303     { \tl_set:Nf \l__msg_internal_tl { \__msg_show_variable_aux:w #1 } }
8304     \etex_showtokens:D \exp_after:wN \exp_after:wN \exp_after:wN
8305     { \exp_after:wN \l__msg_internal_tl }
8306 }
8307 \cs_new:Npn \__msg_show_variable_aux:w #1 > { }

```

(End definition for `__msg_show_variable:Nnn` This function is documented on page 145.)

Each item in the variable is formatted using one of the following functions.

```

8308 \cs_new:Npn \__msg_show_item:n #1
8309 {
8310     \\ > \\ \\ \{ \tl_to_str:n {#1} \\ }
8311 }
8312 \cs_new:Npn \__msg_show_item:nn #1#2
8313 {
8314     \\ > \\ \\ \{ \tl_to_str:n {#1} \\ }
8315     \\ => \\ \\ \{ \tl_to_str:n {#2} \\ }
8316 }
8317 \cs_new:Npn \__msg_show_item_unbraced:nn #1#2
8318 {
8319     \\ > \\ \\ \tl_to_str:n {#1}
8320     \\ \\ => \\ \\ \\ \tl_to_str:n {#2}
8321 }

```

(End definition for `_msg_show_item:n` This function is documented on page 145.)

17.8 Deprecated functions

Deprecated on 2011-05-27, for removal by 2011-08-31.

`\msg_class_new:nn` This is only ever used in a `set` fashion.

```
8322 {*deprecated}
8323 \cs_new_eq:NN \msg_class_new:nn \msg_class_set:nn
8324 
```

(End definition for `\msg_class_new:nn` This function is documented on page ??.)

`\msg_trace:nnxxxx` `\msg_trace:nnxx` The performance here is never going to be good enough for tracing code, so let's be realistic.

```
8325 {*deprecated}
8326 \cs_new_eq:NN \msg_trace:nnxxxx \msg_log:nnxxxx
8327 \cs_new_eq:NN \msg_trace:nnxx \msg_log:nnxx
8328 \cs_new_eq:NN \msg_trace:nnx \msg_log:nnx
8329 \cs_new_eq:NN \msg_trace:nn \msg_log:nn
8330 
```

8331

(End definition for `\msg_trace:nnxxxx` and others. These functions are documented on page ??.)

`\msg_generic_new:nnn` These were all too low-level.

```
8332 {*deprecated}
8333 \cs_new_protected:Npn \msg_generic_new:nnn #1#2#3 { \deprecated }
8334 \cs_new_protected:Npn \msg_generic_new:nn #1#2 { \deprecated }
8335 \cs_new_protected:Npn \msg_generic_set:nnn #1#2#3 { \deprecated }
8336 \cs_new_protected:Npn \msg_generic_set:nn #1#2 { \deprecated }
8337 \cs_new_protected:Npn \msg_direct_interrupt:xxxxx #1#2#3#4#5 { \deprecated }
8338 \cs_new_protected:Npn \msg_direct_log:xx #1#2 { \deprecated }
8339 \cs_new_protected:Npn \msg_direct_term:xx #1#2 { \deprecated }
8340 
```

(End definition for `\msg_generic_new:nnn` This function is documented on page ??.)

`_msg_kernel_bug:x`

```
\c__msg_kernel_bug_text_tl
\c__msg_kernel_bug_more_text_tl
8341 {*deprecated}
8342 \cs_set_protected:Npn \_msg_kernel_bug:x #1
8343 {
8344     \msg_interrupt:nnn { \c__msg_kernel_bug_text_tl }
8345     {
8346         #1
8347         \msg_see_documentation_text:n { LaTeX3 }
8348     }
8349     { \c__msg_kernel_bug_more_text_tl }
8350 }
8351 \tl_const:Nn \c__msg_kernel_bug_text_tl
8352 { This-is-a-LaTeX-bug:-check-coding! }
```

```

8353 \tl_const:Nn \c_msg_kernel_bug_more_text_tl
8354 {
8355   There-is-a-coding-bug-somewhere-around-here. \\
8356   This-probably-needs-examining-by-an-expert.
8357   \c_msg_return_text_tl
8358 }
8359 (/deprecated)
(End definition for \_msg_kernel_bug:x This function is documented on page ??.)
Deprecation note: This function was deprecated on 2012-06-28, for removal by 2012-12-31.

\msg_newline: New lines are printed in the same way as for low-level file writing.
\msg_two_newlines: 
8360 \cs_new_nopar:Npn \msg_newline: { ^J }
8361 \cs_new_nopar:Npn \msg_two_newlines: { ^J ^J }
(End definition for \msg_newline: and \msg_two_newlines: These functions are documented on page ??.)

\msg_log:x These were all misnamed.
\msg_term:x 
\msg_interrupt:xxx 
8362 \cs_generate_variant:Nn \msg_log:n { x }
8363 \cs_generate_variant:Nn \msg_term:n { x }
8364 \cs_generate_variant:Nn \msg_interrupt:nnn { xxx }
(End definition for \msg_log:x and \msg_term:x These functions are documented on page ??.)
Deprecation note: These functions were deprecated on 2012-06-29, for removal by 2012-12-31.

\msg_class_set:nn Setting up a message class does two tasks. Any existing redirection is cleared, and the various message functions are created to simply use the code stored for the message.
8365 \cs_new_protected:Npn \msg_class_set:nn #1#2
8366 {
8367   \cs_if_exist:cTF { __msg_ #1 _code:nnnnnn }
8368     \cs_set_protected:cpn
8369     \cs_new_protected:cpn
8370       { __msg_ #1 _code:nnnnnn } ##1##2##3##4##5##6 {#2}
8371     \prop_clear_new:c { l__msg_redirect_ #1 _prop }
8372     \cs_set_protected_nopar:cpn { msg_ #1 :nnxxxx }
8373       { __msg_use:nnnnnn {#1} }
8374     \cs_set_protected:cp { msg_ #1 :nnxxxx } ##1##2##3##4##5
8375       { \exp_not:c { msg_ #1 :nnxxxx } {##1} {##2} {##3} {##4} {##5} { } }
8376     \cs_set_protected:cp { msg_ #1 :nnxx } ##1##2##3##4
8377       { \exp_not:c { msg_ #1 :nnxxxx } {##1} {##2} {##3} {##4} { } { } }
8378     \cs_set_protected:cp { msg_ #1 :nnx } ##1##2##3
8379       { \exp_not:c { msg_ #1 :nnxxxx } {##1} {##2} {##3} { } { } { } }
8380     \cs_set_protected:cp { msg_ #1 :nn } ##1##2
8381       { \exp_not:c { msg_ #1 :nnxxxx } {##1} {##2} { } { } { } { } }
8382 }

(End definition for \msg_class_set:nn This function is documented on page ??.)
8383 (/initex | package)

```

18 l3keys Implementation

```
8384  {*initex | package}
8385  {*package}
8386  \ProvidesExplPackage
8387  {\ExplFileName}{\ExplFileVersion}{\ExplFileDescription}{\ExplFileDescription}
8388  \_expl_package_check:
8389  
```

18.1 Low-level interface

<@@@=keyval>

For historical reasons this code uses the ‘keyval’ module prefix.

\g_@@_level_int For nesting purposes an integer is needed for the current level.

```
8390  \int_new:N \g_@@_level_int
```

(End definition for \g_@@_level_int This variable is documented on page ??.)

\l_@@_key_tl The current key name and value.

```
8391  \tl_new:N \l_@@_key_tl
```

```
8392  \tl_new:N \l_@@_value_tl
```

(End definition for \l_@@_key_tl and \l_@@_value_tl These variables are documented on page ??.)

\l_@@_sanitise_tl Token list variables for dealing with awkward category codes in the input.

\l_@@_parse_tl

```
8393  \tl_new:N \l_@@_sanitise_tl
```

```
8394  \tl_new:N \l_@@_parse_tl
```

(End definition for \l_@@_sanitise_tl This function is documented on page ??.)

\@@_parse:n The parsing function first deals with the category codes for = and , so that there are no odd events. The input is then handed off to the element by element system.

```
8395  \group_begin:
8396  \char_set_catcode_active:n { '=' }
8397  \char_set_catcode_active:n { '\, }
8398  \char_set_lccode:nn { '\8 } { '=' }
8399  \char_set_lccode:nn { '\9 } { '\, }
8400  \tl_to_lowercase:n
8401  {
8402  \group_end:
8403  \cs_new_protected:Npn \@@_parse:n #1
8404  {
8405  \group_begin:
8406  \tl_clear:N \l_@@_sanitise_tl
8407  \tl_set:Nn \l_@@_sanitise_tl {#1}
8408  \tl_replace_all:Nnn \l_@@_sanitise_tl { = } { 8 }
8409  \tl_replace_all:Nnn \l_@@_sanitise_tl { , } { 9 }
8410  \tl_clear:N \l_@@_parse_tl
8411  \exp_after:wN \@@_parse_elt:w \exp_after:wN
8412  \q_nil \l_@@_sanitise_tl 9 \q_recursion_tail 9 \q_recursion_stop
8413  \exp_after:wN \group_end:
```

```

8414         \l_@@_parse_tl
8415     }
8416 }

```

(End definition for `\@@_parse:n` This function is documented on page ??.)

- `\@@_parse_elt:w` Each item to be parsed will have `\q_nil` added to the front. Hence the blank test here can always be used to find a totally empty argument. If this is the case, the system loops round. If there is something to parse, there is a check for the end of the input before handing off.

```

8417 \cs_new_protected:Npn \@@_parse_elt:w #1 ,
8418 {
8419     \tl_if_blank:oTF { \use_none:n #1 }
8420     { \@@_parse_elt:w \q_nil }
8421     {
8422         \quark_if_recursion_tail_stop:o { \use_i:nn #1 }
8423         \@@_split_key_value:w #1 = = \q_stop
8424         \@@_parse_elt:w \q_nil
8425     }
8426 }

```

(End definition for `\@@_parse_elt:w` This function is documented on page ??.)

- `\@@_split_key_value:w` The key and value are handled separately. First the key is grabbed and saved as `\l_@@_key_tl`. Then a check is need to see if there is a value at all: if not then the key name is simply added to the output. If there is a value then there is a check to ensure that there was only one `=` in the input (remembering some extra ones are around at the moment to prevent errors). All being well, there is an hand-off to find the value: the `\q_nil` is there to prevent loss of braces.

```

8427 \cs_new_protected:Npn \@@_split_key_value:w #1 = #2 \q_stop
8428 {
8429     \@@_split_key:n {#1}
8430     \str_if_eq:nnTF {#2} { = }
8431     {
8432         \tl_put_right:Nx \l_@@_parse_tl
8433         {
8434             \exp_not:c
8435             { \@@_key_no_value_elt_ \int_use:N \g_@@_level_int :n }
8436             { \exp_not:o \l_@@_key_tl }
8437         }
8438     }
8439     {
8440         \@@_split_key_value:wTF #2 \q_no_value \q_stop
8441         { \@@_split_value:w \q_nil #2 }
8442         { \__msg_kernel_error:nn { kernel } { misplaced-equals-sign } }
8443     }
8444 }
8445 \cs_new:Npn \@@_split_key_value:wTF #1 = #2#3 \q_stop
8446     { \tl_if_head_eq_meaning:nNTF {#3} \q_no_value }

```

(End definition for `\@@_split_key_value:w` This function is documented on page ??.)

\@_split_key:n There are two possible cases here. The first case is that #1 is surrounded by braces, in which case the \use_none:nnn #1 \q_nil \q_nil will yield \q_nil. There, we can remove the leading \q_nil, the braces and any spaces around the outside with \use_-ii:nnn. On the other hand, if there are no braces then the second branch removes the leading \q_nil and any surrounding spaces. (This code does not have to cover the case with no key, as that's already taken out above.)

```

8447 \cs_new_protected:Npn \@_split_key:n #1
8448 {
8449     \str_if_eq_x:nnTF
8450         { \exp_not:N \q_nil } { \exp_not:o { \use_none:nnn #1 \q_nil \q_nil } }
8451         { \tl_set:Nx \l @_key_tl { \exp_not:o { \use_ii:nnn #1 \q_nil } } }
8452         { \q_stop }
8453     }
8454 \cs_new_protected:Npn \@_split_key:w \q_nil #1 \q_stop
8455     { \tl_set:Nx \l @_key_tl { \tl_trim_spaces:n {#1} } }
(End definition for \@_split_key:n This function is documented on page ??.)
```

\@_split_value:w Here the value has to be separated from the equals signs and the leading \q_nil added in to keep the brace levels. First the processing function can be added to the output list. If there is no value, setting \l @_value_tl with three groups removed will leave nothing at all, and so an empty group can be added to the parsed list. On the other hand, if the value is entirely contained within a set of braces then \l @_value_tl will contain \q_nil only. In that case, strip off the leading quark using \use_ii:nnn, which also deals with any spaces.

```

8456 \cs_new_protected:Npn \@_split_value:w #1 =
8457 {
8458     \tl_put_right:Nx \l @_parse_tl
8459     {
8460         \exp_not:c
8461         { @_key_value_elt_ \int_use:N \g @_level_int :nn }
8462         { \exp_not:o \l @_key_tl }
8463     }
8464     \tl_set:Nx \l @_value_tl
8465     { \exp_not:o { \use_none:nnn #1 \q_nil \q_nil } }
8466     \tl_if_empty:NTF \l @_value_tl
8467     { \tl_put_right:Nn \l @_parse_tl { {} } }
8468     {
8469         \quark_if_nil:NTF \l @_value_tl
8470         {
8471             \tl_put_right:Nx \l @_parse_tl
8472             { { \exp_not:o { \use_ii:nnn #1 \q_nil } } }
8473         }
8474         { \q_stop }
8475     }
8476 }
```

A similar idea to the key code: remove the spaces from each end and deal with one set of braces.

```

8477 \cs_new_protected:Npn \@@_split_value_aux:w \q_nil #1 \q_stop
8478 {
8479   \tl_set:Nx \l_@@_value_tl { \tl_trim_spaces:n {#1} }
8480   \tl_put_right:Nx \l_@@_parse_tl
8481     { { \exp_not:o \l_@@_value_tl } }
8482 }

```

(End definition for `\@@_split_value:w` This function is documented on page ??.)

\keyval_parse:NNn

The outer parsing routine just sets up the processing functions and hands off.

```

8483 \cs_new_protected:Npn \keyval_parse:NNn #1#2#3
8484 {
8485   \int_gincr:N \g_@@_level_int
8486   \cs_gset_eq:cN
8487     { @@_key_no_value_elt_ \int_use:N \g_@@_level_int :n } #1
8488   \cs_gset_eq:cN
8489     { @@_key_value_elt_ \int_use:N \g_@@_level_int :nn } #2
8490   \@@_parse:n {#3}
8491   \int_gdecr:N \g_@@_level_int
8492 }

```

(End definition for `\keyval_parse:NNn` This function is documented on page 156.)

One message for the low level parsing system.

```

8493 \msg_kernel_new:nnnn { kernel } { misplaced-equals-sign }
8494   { Misplaced~equals~sign~in~key~value~input~\msg_line_number: }
8495   {
8496     LaTeX~is~attempting~to~parse~some~key~value~input~but~found~
8497     two~equals~signs~not~separated~by~a~comma.
8498 }

```

18.2 Constants and variables

8499 ⟨@=keys⟩

\c_keys_code_root_tl The prefixes for the code and variables of the keys themselves.

```

8500 \tl_const:Nn \c_keys_code_root_tl { key~code~>~ }
8501 \tl_const:Nn \c_keys_vars_root_tl { key~var~>~ }

```

(End definition for `\c_keys_code_root_tl` and `\c_keys_vars_root_tl` These variables are documented on page ??.)

\c_keys_props_root_tl

The prefix for storing properties.

```

8502 \tl_const:Nn \c_keys_props_root_tl { key~prop~>~ }

```

(End definition for `\c_keys_props_root_tl` This variable is documented on page ??.)

\c_keys_value_forbidden_tl Two marker token lists.

```

8503 \tl_const:Nn \c_keys_value_forbidden_tl { forbidden }
8504 \tl_const:Nn \c_keys_value_required_tl { required }

```

(End definition for `\c_keys_value_forbidden_tl` and `\c_keys_value_required_tl` These variables are documented on page ??.)

\l_keys_choice_int	Publicly accessible data on which choice is being used when several are generated as a set.
	8505 \int_new:N \l_keys_choice_int 8506 \tl_new:N \l_keys_choice_tl
	<i>(End definition for \l_keys_choice_int and \l_keys_choice_tl These variables are documented on page 152.)</i>
\l_keys_key_tl	The name of a key itself: needed when setting keys.
	8507 \tl_new:N \l_keys_key_tl
	<i>(End definition for \l_keys_key_tl This variable is documented on page 154.)</i>
\l__keys_module_tl	The module for an entire set of keys.
	8508 \tl_new:N \l__keys_module_tl
	<i>(End definition for \l__keys_module_tl This variable is documented on page ??.)</i>
\l__keys_no_value_bool	A marker is needed internally to show if only a key or a key plus a value was seen: this is recorded here.
	8509 \bool_new:N \l__keys_no_value_bool
	<i>(End definition for \l__keys_no_value_bool This variable is documented on page ??.)</i>
\l_keys_path_tl	The “path” of the current key is stored here: this is available to the programmer and so is public.
	8510 \tl_new:N \l_keys_path_tl
	<i>(End definition for \l_keys_path_tl This variable is documented on page 154.)</i>
\l__keys_property_tl	The “property” begin set for a key at definition time is stored here.
	8511 \tl_new:N \l__keys_property_tl
	<i>(End definition for \l__keys_property_tl This variable is documented on page ??.)</i>
\l__keys_unknown_clist	Used when setting only known keys to store those left over.
	8512 \tl_new:N \l__keys_unknown_clist
	<i>(End definition for \l__keys_unknown_clist This variable is documented on page ??.)</i>
\l_keys_value_tl	The value given for a key: may be empty if no value was given.
	8513 \tl_new:N \l_keys_value_tl
	<i>(End definition for \l_keys_value_tl This variable is documented on page 154.)</i>

18.3 The key defining mechanism

```
\keys_define:nn
\__keys_define:nnn
\__keys_define:onn
```

The public function for definitions is just a wrapper for the lower level mechanism, more or less. The outer function is designed to keep a track of the current module, to allow safe nesting. The module is set removing any leading / (which is not needed here).

```
8514 \cs_new_protected:Npn \keys_define:nn
8515   { \__keys_define:onn \l__keys_module_tl }
8516 \cs_new_protected:Npn \__keys_define:nnn #1#2#3
8517   {
8518     \tl_set:Nx \l__keys_module_tl { \tl_to_str:n {#2} }
8519     \keyval_parse:NNn \__keys_define_elt:n \__keys_define_elt:nn {#3}
8520     \tl_set:Nn \l__keys_module_tl {#1}
8521   }
8522 \cs_generate_variant:Nn \__keys_define:nnn { o }
```

(End definition for `\keys_define:nn` This function is documented on page 147.)

```
\__keys_define_elt:n
\__keys_define_elt:nn
\__keys_define_elt_aux:nn
```

The outer functions here record whether a value was given and then converge on a common internal mechanism. There is first a search for a property in the current key name, then a check to make sure it is known before the code hands off to the next step.

```
8523 \cs_new_protected:Npn \__keys_define_elt:n #1
8524   {
8525     \bool_set_true:N \l__keys_no_value_bool
8526     \__keys_define_elt_aux:nn {#1} { }
8527   }
8528 \cs_new_protected:Npn \__keys_define_elt:nn #1#2
8529   {
8530     \bool_set_false:N \l__keys_no_value_bool
8531     \__keys_define_elt_aux:nn {#1} {#2}
8532   }
8533 \cs_new_protected:Npn \__keys_define_elt_aux:nn #1#2
8534   {
8535     \__keys_property_find:n {#1}
8536     \cs_if_exist:cTF { \c__keys_props_root_tl } \l__keys_property_tl }
8537     { \__keys_define_key:n {#2} }
8538   {
8539     \__msg_kernel_error:nnxx { kernel } { property-unknown }
8540     { \l__keys_property_tl } { \l__keys_path_tl }
8541   }
8542 }
```

(End definition for `__keys_define_elt:n` This function is documented on page ??.)

```
\__keys_property_find:n
\__keys_property_find:w
```

Searching for a property means finding the last . in the input, and storing the text before and after it. Everything is turned into strings, so there is no problem using an x-type expansion.

```
8543 \cs_new_protected:Npn \__keys_property_find:n #1
8544   {
8545     \tl_set:Nx \l__keys_path_tl { \l__keys_module_tl / }
8546     \tl_if_in:nnTF {#1} { . }
8547     { \__keys_property_find:w #1 \q_stop }
```

```

8548     { \__msg_kernel_error:nmx { kernel } { key-no-property } {#1} }
8549   }
8550 \cs_new_protected:Npn \__keys_property_find:w #1 . #2 \q_stop
8551   {
8552     \tl_set:Nx \l__keys_path_tl { \l__keys_path_tl \tl_to_str:n {#1} }
8553     \tl_if_in:nnTF {#2} { . }
8554     {
8555       \tl_set:Nx \l__keys_path_tl { \l__keys_path_tl . }
8556       \__keys_property_find:w #2 \q_stop
8557     }
8558     { \tl_set:Nn \l__keys_property_tl { . #2 } }
8559   }

```

(End definition for `__keys_property_find:n` This function is documented on page ??.)

`__keys_define_key:n` Two possible cases. If there is a value for the key, then just use the function. If not, then a check to make sure there is no need for a value with the property. If there should be one then complain, otherwise execute it. There is no need to check for a : as if it is missing the earlier tests will have failed.

```

8560 \cs_new_protected:Npn \__keys_define_key:n #1
8561   {
8562     \bool_if:NTF \l__keys_no_value_bool
8563     {
8564       \exp_after:wN \__keys_define_key:w
8565         \l__keys_property_tl \q_stop
8566         { \use:c { \c__keys_props_root_tl \l__keys_property_tl } }
8567         {
8568           \__msg_kernel_error:nnxx { kernel }
8569             { property-requires-value } { \l__keys_property_tl }
8570             { \l__keys_path_tl }
8571         }
8572       }
8573       { \use:c { \c__keys_props_root_tl \l__keys_property_tl } {#1} }
8574     }
8575 \cs_new_protected:Npn \__keys_define_key:w #1 : #2 \q_stop
8576   { \tl_if_empty:nTF {#2} }

```

(End definition for `__keys_define_key:n` This function is documented on page ??.)

18.4 Turning properties into actions

`__keys_bool_set:NN` Boolean keys are really just choices, but all done by hand. The second argument here is the scope: either empty or g for global.

```

8577 \cs_new:Npn \__keys_bool_set:NN #1#2
8578   {
8579     \bool_if_exist:NF #1 { \bool_new:N #1 }
8580     \__keys_choice_make:
8581     \__keys_cmd_set:nx { \l__keys_path_tl / true }
8582       { \exp_not:c { bool_ #2 set_true:N } \exp_not:N #1 }
8583     \__keys_cmd_set:nx { \l__keys_path_tl / false }

```

```

8584      { \exp_not:c { bool_ #2 set_false:N } \exp_not:N #1 }
8585      \__keys_cmd_set:nn { \l_keys_path_tl / unknown }
8586      {
8587          \__msg_kernel_error:nnx { kernel } { boolean-values-only }
8588          { \l_keys_key_tl }
8589      }
8590      \__keys_default_set:n { true }
8591  }
(End definition for \__keys_bool_set:NN)

```

__keys_bool_set_inverse:NN Inverse boolean setting is much the same.

```

8592 \cs_new:Npn \__keys_bool_set_inverse:NN #1#2
8593 {
8594     \bool_if_exist:NF #1 { \bool_new:N #1 }
8595     \__keys_choice_make:
8596     \__keys_cmd_set:nx { \l_keys_path_tl / true }
8597     { \exp_not:c { bool_ #2 set_false:N } \exp_not:N #1 }
8598     \__keys_cmd_set:nx { \l_keys_path_tl / false }
8599     { \exp_not:c { bool_ #2 set_true:N } \exp_not:N #1 }
8600     \__keys_cmd_set:nn { \l_keys_path_tl / unknown }
8601     {
8602         \__msg_kernel_error:nnx { kernel } { boolean-values-only }
8603         { \l_keys_key_tl }
8604     }
8605     \__keys_default_set:n { true }
8606 }
(End definition for \__keys_bool_set_inverse:NN)

```

__keys_choice_make: To make a choice from a key, two steps: set the code, and set the unknown key.

```

8607 \cs_new_protected_nopar:Npn \__keys_choice_make:
8608 {
8609     \__keys_cmd_set:nn { \l_keys_path_tl }
8610     { \__keys_choice_find:n {##1} }
8611     \__keys_cmd_set:nn { \l_keys_path_tl / unknown }
8612     {
8613         \__msg_kernel_error:nnxx { kernel } { key-choice-unknown }
8614         { \l_keys_path_tl } {##1}
8615     }
8616 }
(End definition for \__keys_choice_make:)

```

__keys_choices_make:nn Auto-generating choices means setting up the root key as a choice, then defining each choice in turn.

```

8617 \cs_new_protected:Npn \__keys_choices_make:nn #1#2
8618 {
8619     \__keys_choice_make:
8620     \int_zero:N \l_keys_choice_int
8621     \clist_map_inline:nn {#1}
8622     {

```

```

8623     \int_incr:N \l_keys_choice_int
8624     \_keys_cmd_set:nx { \l_keys_path_tl / ##1 }
8625     {
8626         \tl_set:Nn \exp_not:N \l_keys_choice_tl {##1}
8627         \int_set:Nn \exp_not:N \l_keys_choice_int
8628             { \int_use:N \l_keys_choice_int }
8629             \exp_not:n {#2}
8630     }
8631 }
8632 }

(End definition for \_keys_choices_make:nn)

```

_keys_choices_generate:n
_keys_choices_generate_aux:n

Creating multiple-choices means setting up the “indicator” code, then applying whatever the user wanted.

```

8633 \cs_new_protected:Npn \_keys_choices_generate:n #1
8634 {
8635     \cs_if_exist:cTF
8636         { \c_keys_vars_root_tl \l_keys_path_tl .choice~code }
8637         {
8638             \_keys_choice_make:
8639             \int_zero:N \l_keys_choice_int
8640             \clist_map_function:nN {#1} \_keys_choices_generate_aux:n
8641         }
8642         {
8643             \_msg_kernel_error:nnx { kernel }
8644                 { generate-choices-before-code } { \l_keys_path_tl }
8645         }
8646     }
8647 \cs_new_protected:Npn \_keys_choices_generate_aux:n #1
8648 {
8649     \int_incr:N \l_keys_choice_int
8650     \_keys_cmd_set:nx { \l_keys_path_tl / #1 }
8651     {
8652         \tl_set:Nn \exp_not:N \l_keys_choice_tl {#1}
8653         \int_set:Nn \exp_not:N \l_keys_choice_int
8654             { \int_use:N \l_keys_choice_int }
8655             \exp_not:v
8656                 { \c_keys_vars_root_tl \l_keys_path_tl .choice~code }
8657     }
8658 }

(End definition for \_keys_choices_generate:n This function is documented on page ??.)

```

_keys_choice_code_store:n
_keys_choice_code_store:x

The code for making multiple choices is stored in a token list.

```

8659 \cs_new_protected:Npn \_keys_choice_code_store:n #1
8660 {
8661     \cs_if_exist:cF
8662         { \c_keys_vars_root_tl \l_keys_path_tl .choice~code }
8663         {
8664             \tl_new:c

```

```

8665     { \c__keys_vars_root_tl \l_keys_path_tl .choice~code }
8666   }
8667   \tl_set:cn { \c__keys_vars_root_tl \l_keys_path_tl .choice~code }
8668   {#1}
8669 }
8670 \cs_generate_variant:Nn \_keys_choice_code_store:n { x }
(End definition for \_keys_choice_code_store:n and \_keys_choice_code_store:x)

```

_keys_cmd_set:nn
_keys_cmd_set:nx
_keys_cmd_set:Vo
_keys_cmd_set:n

Creating a new command means tidying up the properties and then making the internal function which actually does the work.

```

8671 \cs_new_protected:Npn \_keys_cmd_set:nn #1#2
8672 {
8673   \_keys_cmd_set:n {#1}
8674   \cs_set:cpn { \c__keys_code_root_tl #1 } ##1 {#2}
8675 }
8676 \cs_new_protected:Npn \_keys_cmd_set:nx #1#2
8677 {
8678   \_keys_cmd_set:n {#1}
8679   \cs_set:cpn { \c__keys_code_root_tl #1 } ##1 {#2}
8680 }
8681 \cs_generate_variant:Nn \_keys_cmd_set:nn { Vo }
8682 \cs_new_protected:Npn \_keys_cmd_set:n #1
8683 {
8684   \tl_clear_new:c { \c__keys_vars_root_tl #1 .default }
8685   \tl_set:cn { \c__keys_vars_root_tl #1 .default } { \q_no_value }
8686   \tl_clear_new:c { \c__keys_vars_root_tl #1 .req }
8687 }
(End definition for \_keys_cmd_set:nn, \_keys_cmd_set:nx, and \_keys_cmd_set:Vo These functions are documented on page ??.)

```

_keys_default_set:n
_keys_default_set:V

Setting a default value is easy.

```

8688 \cs_new_protected:Npn \_keys_default_set:n #1
8689   { \tl_set:cn { \c__keys_vars_root_tl \l_keys_path_tl .default } {#1} }
8690 \cs_generate_variant:Nn \_keys_default_set:n { V }
(End definition for \_keys_default_set:n and \_keys_default_set:V)

```

_keys_initialise:n
_keys_initialise:V
_keys_initialise:wn

A set up for initialisation from which the key system requires that the path is split up into a module and a key name. At this stage, \l_keys_path_tl will contain / so a split is easy to do.

```

8691 \cs_new_protected:Npn \_keys_initialise:n #1
8692 {
8693   \use:x
8694   { \exp_after:wN \_keys_initialise:wn \l_keys_path_tl \q_stop {#1} }
8695 }
8696 \cs_generate_variant:Nn \_keys_initialise:n { V }
8697 \cs_new:Npn \_keys_initialise:wn #1 / #2 \q_stop #3
8698   { \keys_set:nn {#1} { #2 = \exp_not:n { {#3} } } }
(End definition for \_keys_initialise:n and \_keys_initialise:V These functions are documented on page ??.)

```

`__keys_meta_make:n` To create a meta-key, simply set up to pass data through.
`__keys_meta_make:x`

```

8699 \cs_new_protected:Npn \__keys_meta_make:n #1
8700 {
8701   \__keys_cmd_set:Vo \l_keys_path_tl
8702   { \exp_after:wN \keys_set:nn \exp_after:wN { \l__keys_module_tl } {#1} }
8703 }
8704 \cs_new_protected:Npn \__keys_meta_make:x #1
8705 {
8706   \__keys_cmd_set:nx { \l_keys_path_tl }
8707   { \exp_not:N \keys_set:nn { \l__keys_module_tl } {#1} }
8708 }
```

(End definition for `__keys_meta_make:n` and `__keys_meta_make:x`. These functions are documented on page ??.)

`__keys_multichoice_find:n` Choices where several values can be selected are very similar to normal exclusive choices.
`__keys_multichoice_make:` There is just a slight change in implementation to map across a comma-separated list.
`__keys_multichoices_make:nn` This then requires that the appropriate set up takes place elsewhere.

```

8709 \cs_new:Npn \__keys_multichoice_find:n #1
8710 { \clist_map_function:nN {#1} \__keys_choice_find:n }
8711 \cs_new_protected_nopar:Npn \__keys_multichoice_make:
8712 {
8713   \__keys_cmd_set:nn { \l_keys_path_tl }
8714   { \__keys_multichoice_find:n {##1} }
8715   \__keys_cmd_set:nn { \l_keys_path_tl / unknown }
8716   {
8717     \__msg_kernel_error:nnxx { kernel } { key-choice-unknown }
8718     { \l_keys_path_tl } {##1}
8719   }
8720 }
8721 \cs_new_protected:Npn \__keys_multichoices_make:nn #1#2
8722 {
8723   \__keys_multichoice_make:
8724   \int_zero:N \l_keys_choice_int
8725   \clist_map_inline:nn {#1}
8726   {
8727     \int_incr:N \l_keys_choice_int
8728     \__keys_cmd_set:nx { \l_keys_path_tl / ##1 }
8729     {
8730       \tl_set:Nn \exp_not:N \l_keys_choice_tl {##1}
8731       \int_set:Nn \exp_not:N \l_keys_choice_int
8732       { \int_use:N \l_keys_choice_int }
8733       \exp_not:n {#2}
8734     }
8735   }
8736 }
```

(End definition for `__keys_multichoice_find:n`. This function is documented on page ??.)

`__keys_value_requirement:n` Values can be required or forbidden by having the appropriate marker set.

```
8737 \cs_new_protected:Npn \__keys_value_requirement:n #1
```

```

8738   {
8739     \tl_set_eq:cc
8740       { \c_keys_vars_root_tl \l_keys_path_tl .req }
8741       { \c_keys_value_ #1 _tl }
8742   }
(End definition for \__keys_value_requirement:n)

```

__keys_variable_set:NnNN Setting a variable takes the type and scope separately so that it is easy to make a new variable if needed. The three-argument version is set up so that the use of {} as an N-type variable is only done once!

```

8743 \cs_new_protected:Npn \__keys_variable_set:NnNN #1#2#3#4
8744   {
8745     \use:c { #2_if_exist:NF } #1 { \use:c { #2_new:N } #1 }
8746     \__keys_cmd_set:nx { \l_keys_path_tl }
8747       { \exp_not:c { #2 _ #3 set:N #4 } \exp_not:N #1 {##1} }
8748   }
8749 \cs_new_protected:Npn \__keys_variable_set:NnN #1#2#3
8750   { \__keys_variable_set:NnNN #1 {#2} { } #3 }
8751 \cs_generate_variant:Nn \__keys_variable_set:NnNN { c }
8752 \cs_generate_variant:Nn \__keys_variable_set:NnN { c }
(End definition for \__keys_variable_set:NnNN and \__keys_variable_set:cnNN These functions are documented on page ??.)

```

18.5 Creating key properties

The key property functions are all wrappers for internal functions, meaning that things stay readable and can also be altered later on.

.bool_set:N One function for this.

```

8753 \cs_new_protected:cpn { \c_keys_props_root_tl .bool_set:N } #1
8754   { \__keys_bool_set>NN #1 { } }
8755 \cs_new_protected:cpn { \c_keys_props_root_tl .bool_gset:N } #1
8756   { \__keys_bool_set>NN #1 g }
(End definition for .bool_set:N This function is documented on page 147.)

```

.bool_set_inverse:N One function for this.

```

8757 \cs_new_protected:cpn { \c_keys_props_root_tl .bool_set_inverse:N } #1
8758   { \__keys_bool_set_inverse>NN #1 { } }
8759 \cs_new_protected:cpn { \c_keys_props_root_tl .bool_gset_inverse:N } #1
8760   { \__keys_bool_set_inverse>NN #1 g }
(End definition for .bool_set_inverse:N This function is documented on page 148.)

```

.choice: Making a choice is handled internally, as it is also needed by .generate_choices:n.

```

8761 \cs_new_protected_nopar:cpn { \c_keys_props_root_tl .choice: }
8762   { \__keys_choice_make: }
(End definition for .choice: This function is documented on page 148.)

```

.choices:nn For auto-generation of a series of mutually-exclusive choices. Here, #1 will consist of two separate arguments, hence the slightly odd-looking implementation.

```
8763 \cs_new_protected:cpn { \c_keys_props_root_t1 .choices:nn } #1
```

```
8764   { \__keys_choices_make:nn #1 }
```

(End definition for **.choices:nn** This function is documented on page 148.)

.code:n Creating code is simply a case of passing through to the underlying **set** function.

.code:x

```
8765 \cs_new_protected:cpn { \c_keys_props_root_t1 .code:n } #1
```

```
8766   { \__keys_cmd_set:nn { \l_keys_path_t1 } {#1} }
```

```
8767 \cs_new_protected:cpn { \c_keys_props_root_t1 .code:x } #1
```

```
8768   { \__keys_cmd_set:nx { \l_keys_path_t1 } {#1} }
```

(End definition for **.code:n** and **.code:x** These functions are documented on page 148.)

.choice_code:n Storing the code for choices

.choice_code:x

```
8769 \cs_new_protected:cpn { \c_keys_props_root_t1 .choice_code:n } #1
```

```
8770   { \__keys_choice_code_store:n {#1} }
```

```
8771 \cs_new_protected:cpn { \c_keys_props_root_t1 .choice_code:x } #1
```

```
8772   { \__keys_choice_code_store:x {#1} }
```

(End definition for **.choice_code:n** and **.choice_code:x** These functions are documented on page 148.)

.clist_set:N

.clist_set:c

.clist_gset:N

.clist_gset:c

```
8773 \cs_new_protected:cpn { \c_keys_props_root_t1 .clist_set:N } #1
```

```
8774   { \__keys_variable_set:NnN #1 { clist } n }
```

```
8775 \cs_new_protected:cpn { \c_keys_props_root_t1 .clist_set:c } #1
```

```
8776   { \__keys_variable_set:cnN {#1} { clist } n }
```

```
8777 \cs_new_protected:cpn { \c_keys_props_root_t1 .clist_gset:N } #1
```

```
8778   { \__keys_variable_set:NnNN #1 { clist } g n }
```

```
8779 \cs_new_protected:cpn { \c_keys_props_root_t1 .clist_gset:c } #1
```

```
8780   { \__keys_variable_set:cnNN {#1} { clist } g n }
```

(End definition for **.clist_set:N** and **.clist_set:c** These functions are documented on page 148.)

.default:n Expansion is left to the internal functions.

.default:V

```
8781 \cs_new_protected:cpn { \c_keys_props_root_t1 .default:n } #1
```

```
8782   { \__keys_default_set:n {#1} }
```

```
8783 \cs_new_protected:cpn { \c_keys_props_root_t1 .default:V } #1
```

```
8784   { \__keys_default_set:V #1 }
```

(End definition for **.default:n** and **.default:V** These functions are documented on page 149.)

.dim_set:N Setting a variable is very easy: just pass the data along.

.dim_set:c

.dim_gset:N

.dim_gset:c

```
8785 \cs_new_protected:cpn { \c_keys_props_root_t1 .dim_set:N } #1
```

```
8786   { \__keys_variable_set:NnN #1 { dim } n }
```

```
8787 \cs_new_protected:cpn { \c_keys_props_root_t1 .dim_set:c } #1
```

```
8788   { \__keys_variable_set:cnN {#1} { dim } n }
```

```
8789 \cs_new_protected:cpn { \c_keys_props_root_t1 .dim_gset:N } #1
```

```
8790   { \__keys_variable_set:NnNN #1 { dim } g n }
```

```
8791 \cs_new_protected:cpn { \c_keys_props_root_t1 .dim_gset:c } #1
```

```
8792   { \__keys_variable_set:cnNN {#1} { dim } g n }
```

(End definition for **.dim_set:N** and **.dim_set:c** These functions are documented on page 149.)

.fp_set:N Setting a variable is very easy: just pass the data along.

```

8793 \cs_new_protected:cpn { \c_keys_props_root_tl .fp_set:N } #1
8794   { \__keys_variable_set:NnN #1 { fp } n }
8795 \cs_new_protected:cpn { \c_keys_props_root_tl .fp_set:c } #1
8796   { \__keys_variable_set:cnn {#1} { fp } n }
8797 \cs_new_protected:cpn { \c_keys_props_root_tl .fp_gset:N } #1
8798   { \__keys_variable_set:NnNN #1 { fp } g n }
8799 \cs_new_protected:cpn { \c_keys_props_root_tl .fp_gset:c } #1
8800   { \__keys_variable_set:cnnN {#1} { fp } g n }

```

(End definition for **.fp_set:N** and **.fp_set:c** These functions are documented on page 149.)

.generate_choices:n Making choices is easy.

```

8801 \cs_new_protected:cpn { \c_keys_props_root_tl .generate_choices:n } #1
8802   { \__keys_choices_generate:n {#1} }

```

(End definition for **.generate_choices:n** This function is documented on page 149.)

.initial:n The standard hand-off approach.

```

8803 \cs_new_protected:cpn { \c_keys_props_root_tl .initial:n } #1
8804   { \__keys_initialise:n {#1} }
8805 \cs_new_protected:cpn { \c_keys_props_root_tl .initial:V } #1
8806   { \__keys_initialise:V #1 }

```

(End definition for **.initial:n** and **.initial:V** These functions are documented on page 149.)

.int_set:N Setting a variable is very easy: just pass the data along.

```

8807 \cs_new_protected:cpn { \c_keys_props_root_tl .int_set:N } #1
8808   { \__keys_variable_set:NnN #1 { int } n }
8809 \cs_new_protected:cpn { \c_keys_props_root_tl .int_set:c } #1
8810   { \__keys_variable_set:cnn {#1} { int } n }
8811 \cs_new_protected:cpn { \c_keys_props_root_tl .int_gset:N } #1
8812   { \__keys_variable_set:NnNN #1 { int } g n }
8813 \cs_new_protected:cpn { \c_keys_props_root_tl .int_gset:c } #1
8814   { \__keys_variable_set:cnnN {#1} { int } g n }

```

(End definition for **.int_set:N** and **.int_set:c** These functions are documented on page 149.)

.meta:n Making a meta is handled internally.

```

8815 \cs_new_protected:cpn { \c_keys_props_root_tl .meta:n } #1
8816   { \__keys_meta_make:n {#1} }
8817 \cs_new_protected:cpn { \c_keys_props_root_tl .meta:x } #1
8818   { \__keys_meta_make:x {#1} }

```

(End definition for **.meta:n** and **.meta:x** These functions are documented on page 150.)

.multichoice: The same idea as **.choice:** and **.choices:nn**, but where more than one choice is allowed.

```

8819 \cs_new_protected_nopar:cpn { \c_keys_props_root_tl .multichoice: }
8820   { \__keys_multichoice_make: }
8821 \cs_new_protected:cpn { \c_keys_props_root_tl .multichoice:nn } #1
8822   { \__keys_multichoice:nn #1 }

```

(End definition for **.multichoice:** This function is documented on page 150.)

```

.skip_set:N      Setting a variable is very easy: just pass the data along.
.skip_set:c
.skip_gset:N
.skip_gset:c
 8823 \cs_new_protected:cpn { \c_keys_props_root_tl .skip_set:N } #1
 8824 { \__keys_variable_set:NnN #1 { skip } n }
 8825 \cs_new_protected:cpn { \c_keys_props_root_tl .skip_set:c } #1
 8826 { \__keys_variable_set:cnN {#1} { skip } n }
 8827 \cs_new_protected:cpn { \c_keys_props_root_tl .skip_gset:N } #1
 8828 { \__keys_variable_set:NnNN #1 { skip } g n }
 8829 \cs_new_protected:cpn { \c_keys_props_root_tl .skip_gset:c } #1
 8830 { \__keys_variable_set:cnNN {#1} { skip } g n }

(End definition for .skip_set:N and .skip_set:c These functions are documented on page 150.)

```

```

.tl_set:N      Setting a variable is very easy: just pass the data along.
.tl_set:c
.tl_gset:N
.tl_gset:c
.tl_set_x:N
.tl_set_x:c
.tl_gset_x:N
.tl_gset_x:c
 8831 \cs_new_protected:cpn { \c_keys_props_root_tl .tl_set:N } #1
 8832 { \__keys_variable_set:NnN #1 { tl } n }
 8833 \cs_new_protected:cpn { \c_keys_props_root_tl .tl_set:c } #1
 8834 { \__keys_variable_set:cnN {#1} { tl } n }
 8835 \cs_new_protected:cpn { \c_keys_props_root_tl .tl_set_x:N } #1
 8836 { \__keys_variable_set:NnN #1 { tl } x }
 8837 \cs_new_protected:cpn { \c_keys_props_root_tl .tl_set_x:c } #1
 8838 { \__keys_variable_set:cnN {#1} { tl } x }
 8839 \cs_new_protected:cpn { \c_keys_props_root_tl .tl_gset:N } #1
 8840 { \__keys_variable_set:NnNN #1 { tl } g n }
 8841 \cs_new_protected:cpn { \c_keys_props_root_tl .tl_gset:c } #1
 8842 { \__keys_variable_set:cnNN {#1} { tl } g n }
 8843 \cs_new_protected:cpn { \c_keys_props_root_tl .tl_gset_x:N } #1
 8844 { \__keys_variable_set:NnNN #1 { tl } g x }
 8845 \cs_new_protected:cpn { \c_keys_props_root_tl .tl_gset_x:c } #1
 8846 { \__keys_variable_set:cnNN {#1} { tl } g x }

(End definition for .tl_set:N and .tl_set:c These functions are documented on page 150.)

```

```

.value_forbidden: These are very similar, so both call the same function.
.value_required:
 8847 \cs_new_protected_nopar:cpn { \c_keys_props_root_tl .value_forbidden: }
 8848 { \__keys_value_requirement:n { forbidden } }
 8849 \cs_new_protected_nopar:cpn { \c_keys_props_root_tl .value_required: }
 8850 { \__keys_value_requirement:n { required } }

(End definition for .value_forbidden: This function is documented on page 150.)

```

18.6 Setting keys

```

\keys_set:nn      A simple wrapper again.
\keys_set:nV
\keys_set:nv
\keys_set:no
\__keys_set:nnn
\__keys_set:onn
 8851 \cs_new_protected:Npn \keys_set:nn
 8852 { \__keys_set:onn { \l_keys_module_tl } }
 8853 \cs_new_protected:Npn \__keys_set:nnn #1#2#3
 8854 {
 8855   \tl_set:Nx \l_keys_module_tl { \tl_to_str:n {#2} }
 8856   \keyval_parse:NNn \__keys_set_elt:n \__keys_set_elt:nn {#3}
 8857   \tl_set:Nn \l_keys_module_tl {#1}
 8858 }


```

```

8859 \cs_generate_variant:Nn \keys_set:nn { nV , nv , no }
8860 \cs_generate_variant:Nn \__keys_set:nnn { o }
(End definition for \keys_set:nn and others. These functions are documented on page ??.)
```

```

\keys_set_known:nnN
\keys_set_known:nVN
\keys_set_known:nVN
\keys_set_known:noN
\__keys_set_known:nnnN
\__keys_set_known:onnN
8861 \cs_new_protected:Npn \keys_set_known:nnN
8862   { \__keys_set_known:onnN { \l__keys_module_tl } }
8863 \cs_new_protected:Npn \__keys_set_known:nnnN #1#2#3#4
8864   {
8865     \tl_set:Nx \l__keys_module_tl { \tl_to_str:n {#2} }
8866     \clist_clear:N \l__keys_unknown_clist
8867     \cs_set_eq:NN \__keys_execute_unknown: \__keys_execute_unknown_alt:
8868     \keyval_parse:NNn \__keys_set_elt:n \__keys_set_elt:nn {#3}
8869     \cs_set_eq:NN \__keys_execute_unknown: \__keys_execute_unknown_std:
8870     \tl_set:Nn \l__keys_module_tl {#1}
8871     \clist_set_eq:NN #4 \l__keys_unknown_clist
8872   }
8873 \cs_generate_variant:Nn \keys_set_known:nnN { nV , nv , no }
8874 \cs_generate_variant:Nn \__keys_set_known:nnnN { o }
(End definition for \keys_set_known:nnN and others. These functions are documented on page ??.)
```

__keys_set_elt:n A shared system once again. First, set the current path and add a default if needed.
__keys_set_elt:nn
__keys_set_elt_aux:nn
There are then checks to see if the a value is required or forbidden. If everything passes, move on to execute the code.

```

8875 \cs_new_protected:Npn \__keys_set_elt:n #1
8876   {
8877     \bool_set_true:N \l__keys_no_value_bool
8878     \__keys_set_elt_aux:nn {#1} { }
8879   }
8880 \cs_new_protected:Npn \__keys_set_elt:nn #1#2
8881   {
8882     \bool_set_false:N \l__keys_no_value_bool
8883     \__keys_set_elt_aux:nn {#1} {#2}
8884   }
8885 \cs_new_protected:Npn \__keys_set_elt_aux:nn #1#2
8886   {
8887     \tl_set:Nx \l_keys_key_tl { \tl_to_str:n {#1} }
8888     \tl_set:Nx \l_keys_path_tl { \l__keys_module_tl / \l_keys_key_tl }
8889     \__keys_value_or_default:n {#2}
8890     \bool_if:nTF
8891       {
8892         \__keys_if_value_p:n { required } &&
8893         \l__keys_no_value_bool
8894       }
8895       {
8896         \__msg_kernel_error:nnx { kernel } { value-required }
8897         { \l_keys_path_tl }
8898       }
8899   }
```

```

8900          \bool_if:nTF
8901          {
8902              \__keys_if_value_p:n { forbidden } &&
8903              ! \l__keys_no_value_bool
8904          }
8905          {
8906              \__msg_kernel_error:nnxx { kernel } { value-forbidden }
8907              { \l_keys_path_tl } { \l_keys_value_tl }
8908          }
8909          { \__keys_execute: }
8910      }
8911  }

```

(End definition for `__keys_set_elt:n` and `__keys_set_elt:nn`. These functions are documented on page ??.)

`__keys_value_or_default:n` If a value is given, return it as #1, otherwise send a default if available.

```

8912  \cs_new_protected:Npn \__keys_value_or_default:n #1
8913  {
8914      \tl_set:Nn \l_keys_value_tl {#1}
8915      \bool_if:NT \l__keys_no_value_bool
8916      {
8917          \quark_if_no_value:cF { \c__keys_vars_root_tl \l_keys_path_tl .default }
8918          {
8919              \cs_if_exist:cT { \c__keys_vars_root_tl \l_keys_path_tl .default }
8920              {
8921                  \tl_set_eq:Nc \l_keys_value_tl
8922                  { \c__keys_vars_root_tl \l_keys_path_tl .default }
8923              }
8924          }
8925      }
8926  }

```

(End definition for `__keys_value_or_default:n`)

`__keys_if_value_p:n` To test if a value is required or forbidden. A simple check for the existence of the appropriate marker.

```

8927  \prg_new_conditional:Npnn \__keys_if_value:n #1 { p }
8928  {
8929      \tl_if_eq:cctF { \c__keys_value_ #1 _tl }
8930      { \c__keys_vars_root_tl \l_keys_path_tl .req }
8931      { \prg_return_true: }
8932      { \prg_return_false: }
8933  }

```

(End definition for `__keys_if_value_p:n`)

`__keys_execute:` Actually executing a key is done in two parts. First, look for the key itself, then look for the `unknown` key with the same path. If both of these fail, complain.

```

\__keys_execute_unknown:
\__keys_execute_unknown_std:
\__keys_execute_unknown_alt:
\__keys_execute:nn

```

```

8934  \cs_new_nopar:Npn \__keys_execute:
8935      { \__keys_execute:nn { \l_keys_path_tl } { \__keys_execute_unknown: } }
8936  \cs_new_nopar:Npn \__keys_execute_unknown:

```

```

8937   {
8938     \__keys_execute:nn { \l_keys_module_tl / unknown }
8939     {
8940       \__msg_kernel_error:nxxx { kernel } { key-unknown }
8941         { \l_keys_path_tl } { \l_keys_module_tl }
8942     }
8943   }
8944 \cs_new_eq:NN \__keys_execute_unknown_std: \__keys_execute_unknown:
8945 \cs_new_nopar:Npn \__keys_execute_unknown_alt:
8946   {
8947     \clist_put_right:Nx \l_keys_unknown_clist
8948     {
8949       \exp_not:o \l_keys_key_tl
8950       \bool_if:NF \l_keys_no_value_bool
8951         { = { \exp_not:o \l_keys_value_tl } }
8952     }
8953   }
8954 \cs_new:Npn \__keys_execute:nn #1#2
8955   {
8956     \cs_if_exist:cTF { \c_keys_code_root_tl #1 }
8957     {
8958       \exp_args:Nc \exp_args:No { \c_keys_code_root_tl #1 }
8959         \l_keys_value_tl
8960     }
8961   {#2}
8962 }

```

(End definition for `__keys_execute:` This function is documented on page ??.)

- `__keys_choice_find:n` Executing a choice has two parts. First, try the choice given, then if that fails call the unknown key. That will exist, as it is created when a choice is first made. So there is no need for any escape code.

```

8963 \cs_new:Npn \__keys_choice_find:n #1
8964   {
8965     \__keys_execute:nn { \l_keys_path_tl / \tl_to_str:n {#1} }
8966       { \__keys_execute:nn { \l_keys_path_tl / unknown } { } }
8967   }

```

(End definition for `__keys_choice_find:n`)

18.7 Utilities

A utility for others to see if a key exists.

```

\keys_if_exist_p:nn
\keys_if_exist:nnTF
8968 \prg_new_conditional:Npnn \keys_if_exist:nn #1#2 { p , T , F , TF }
8969   {
8970     \cs_if_exist:cTF { \c_keys_code_root_tl #1 / #2 }
8971       { \prg_return_true: }
8972       { \prg_return_false: }
8973   }

```

(End definition for `\keys_if_exist:nn` These functions are documented on page 154.)

\keys_if_choice_exist_p:nnn
\keys_if_choice_exist:nnnTF

```

8974 \prg_new_conditional:Npnn \keys_if_choice_exist:nnn #1#2#3 { p , T , F , TF }
8975 {
8976   \cs_if_exist:cTF { \c__keys_code_root_tl #1 / #2 / #3 }
8977   { \prg_return_true: }
8978   { \prg_return_false: }
8979 }
```

(End definition for \keys_if_choice_exist:nnn These functions are documented on page 154.)

\keys_show:nn

Showing a key is just a question of using the correct name.

```

8980 \cs_new:Npn \keys_show:nn #1#2
8981 { \cs_show:c { \c__keys_code_root_tl #1 / \tl_to_str:n {#2} } }
```

(End definition for \keys_show:nn This function is documented on page 154.)

18.8 Messages

For when there is a need to complain.

```

8982 \__msg_kernel_new:nnnn { kernel } { boolean-values-only }
8983 { Key~'#1'~accepts~boolean~values~only. }
8984 { The~key~'#1'~only~accepts~the~values~'true'~and~'false'. }
8985 \__msg_kernel_new:nnnn { kernel } { choice-unknown }
8986 { Choice~'#2'~unknown~for~key~'#1'. }
8987 {
8988   The~key~'#1'~takes~a~limited~number~of~values.\\
8989   The~input~given,~'#2',~is~not~on~the~list~accepted.
8990 }
8991 \__msg_kernel_new:nnnn { kernel } { generate-choices-before-code }
8992 { No~code~available~to~generate~choices~for~key~'#1'. }
8993 {
8994   \c_msg_coding_error_text_tl
8995   Before~using~.generate_choices:n~the~code~should~be~defined~
8996   with~'.choice_code:n'~or~'.choice_code:x'.
8997 }
8998 \__msg_kernel_new:nnnn { kernel } { key-no-property }
8999 { No~property~given~in~definition~of~key~'#1'. }
9000 {
9001   \c_msg_coding_error_text_tl
9002   Inside~\keys_define:nn each~key~name
9003   needs~a~property: \\
9004   ~ ~ #1 .<property> \\
9005   LaTeX~did~not~find~a~.'~to~indicate~the~start~of~a~property.
9006 }
9007 \__msg_kernel_new:nnnn { kernel } { key-unknown }
9008 { The~key~'#1'~is~unknown~and~is~being~ignored. }
9009 {
9010   The~module~'#2'~does~not~have~a~key~called~'#1'.\\
9011   Check~that~you~have~spelled~the~key~name~correctly.
9012 }
9013 \__msg_kernel_new:nnnn { kernel } { property-requires-value }
```

```

9014 { The~property~'#1'~requires~a~value. }
9015 {
9016   \c_msg_coding_error_text_tl
9017   LaTeX~was~asked~to~set~property~'#2'~for~key~'#1'. \\
9018   No~value~was~given~for~the~property,~and~one~is~required.
9019 }
9020 \_\_msg_kernel_new:nnnn { kernel } { property-unknown }
9021 { The~key~property~'#1'~is~unknown. }
9022 {
9023   \c_msg_coding_error_text_tl
9024   LaTeX~has~been~asked~to~set~the~property~'#1'~for~key~'#2':~
9025   this~property~is~not~defined.
9026 }
9027 \_\_msg_kernel_new:nnnn { kernel } { value-forbidden }
9028 { The~key~'#1'~does~not~taken~a~value. }
9029 {
9030   The~key~'#1'~should~be~given~without~a~value.\\
9031   LaTeX~will~ignore~the~given~value~'#2'.
9032 }
9033 \_\_msg_kernel_new:nnnn { kernel } { value-required }
9034 { The~key~'#1'~requires~a~value. }
9035 {
9036   The~key~'#1'~must~have~a~value.\\
9037   No~value~was~present:~the~key~will~be~ignored.
9038 }

```

18.9 Deprecated functions

Deprecated on 2011-05-27, for removal by 2011-08-31.

There is just one function for this now.

```

9039 <*deprecated>
9040 \cs_new_eq:NN \KV_process_space_removal_sanitze:NNn      \keyval_parse:NNn
9041 \cs_new_eq:NN \KV_process_space_removal_no_sanitze:NNn    \keyval_parse:NNn
9042 \cs_new_eq:NN \KV_process_no_space_removal_no_sanitze:NNn \keyval_parse:NNn
9043 </deprecated>
(End definition for \KV_process_space_removal_sanitze:NNn This function is documented on page ??.)
Internal material for removal by 2012-12-31.
9044 \cs_new_eq:NN \c_keys_code_root_tl \c__keys_code_root_tl
9045 </initex | package>

```

19 l3file implementation

The following test files are used for this code: m3file001.

```

9046 <*initex | package>
9047 <@@=file>

```

```

9048 {*package}
9049 \ProvidesExplPackage
9050 {\ExplFileName}{\ExplFileVersion}{\ExplFileDescription}
9051 \_expl_package_check:
9052 
```

19.1 File operations

\g_file_current_name_tl

The name of the current file should be available at all times. For the format the file name needs to be picked up at the start of the file. In package mode the current file name is collected from $\text{\LaTeX} 2_{\varepsilon}$.

```

9053 \tl_new:N \g_file_current_name_tl
9054 {*initex}
9055 \tex_everyjob:D \exp_after:wN
9056 {
9057   \tex_the:D \tex_everyjob:D
9058   \tl_gset:Nx \g_file_current_name_tl { \tex_jobname:D }
9059 }
9060 
```

(End definition for `\g_file_current_name_tl` This variable is documented on page 157.)

\g__file_stack_seq

The input list of files is stored as a sequence stack.

```
9064 \seq_new:N \g__file_stack_seq
```

(End definition for `\g__file_stack_seq` This variable is documented on page ??.)

\g__file_record_seq

The total list of files used is recorded separately from the current file stack, as nothing is ever popped from this list. The current file name should be included in the file list! In format mode, this is done at the very start of the \TeX run. In package mode we will eventually copy the contents of `\@filelist`.

```

9065 \seq_new:N \g__file_record_seq
9066 {*initex}
9067 \tex_everyjob:D \exp_after:wN
9068 {
9069   \tex_the:D \tex_everyjob:D
9070   \seq_gput_right:NV \g__file_record_seq \g_file_current_name_tl
9071 }
9072 
```

(End definition for `\g__file_record_seq` This variable is documented on page ??.)

\l__file_internal_tl

Used as a short-term scratch variable. It may be possible to reuse `\l__file_internal_name_tl` there.

```
9073 \tl_new:N \l__file_internal_tl
```

(End definition for `\l__file_internal_tl` This variable is documented on page ??.)

\l_file_internal_name_t1 Used to return the fully-qualified name of a file.

```
9074 \tl_new:N \l_file_internal_name_t1
(End definition for \l_file_internal_name_t1 This variable is documented on page 162.)
```

\l_file_search_path_seq The current search path.

```
9075 \seq_new:N \l_file_search_path_seq
(End definition for \l_file_search_path_seq This variable is documented on page ??.)
```

\l_file_saved_search_path_seq The current search path has to be saved for package use.

```
9076 {*package}
9077 \seq_new:N \l_file_saved_search_path_seq
9078 {/package}
(End definition for \l_file_saved_search_path_seq This variable is documented on page ??.)
```

\l_file_internal_seq Scratch space for comma list conversion in package mode.

```
9079 {*package}
9080 \seq_new:N \l_file_internal_seq
9081 {/package}
(End definition for \l_file_internal_seq This variable is documented on page ??.)
```

__file_name_sanitize:nn For converting a token list to a string where active characters are treated as strings from the start.

```
9082 \cs_new_protected:Npn \_\_file\_name\_sanitize:nn #1#2
  {
    \group_begin:
    \seq_map_inline:Nn \l_char_active_seq
      { \cs_set_nopar:Npx ##1 { \token_to_str:N ##1 } }
    \tl_set:Nx \l_file_internal_name_t1 {##1}
    \tl_set:Nx \l_file_internal_name_t1
      { \tl_to_str:N \l_file_internal_name_t1 }
    \tl_if_in:NnT \l_file_internal_name_t1 { ~ }
    {
      \msg_kernel_error:nnx { kernel } { space-in-file-name }
        { \l_file_internal_name_t1 }
      \tl_remove_all:Nn \l_file_internal_name_t1 { ~ }
    }
    \use:x
    {
      \group_end:
      \exp_not:n {##2} { \l_file_internal_name_t1 }
    }
  }
(End definition for \_\_file\_name\_sanitize:nn)
```

```
\file_add_path:nN
\__file_add_path:nN
\__file_add_path_search:nN
```

The way to test if a file exists is to try to open it: if it does not exist then TeX will report end-of-file. For files which are in the current directory, this is straight-forward. For other locations, a search has to be made looking at each potential path in turn. The first location is of course treated as the correct one. If nothing is found, #2 is returned empty.

```
9102 \cs_new_protected:Npn \file_add_path:nN #1
9103   { \__file_name_sanitize:nn {#1} { \__file_add_path:nN } }
9104 \cs_new_protected:Npn \__file_add_path:nN #1#2
9105   {
9106     \__ior_open:Nn \g__file_internal_ior {#1}
9107     \ior_if_eof:NTF \g__file_internal_ior
9108       { \__file_add_path_search:nN {#1} #2 }
9109       { \tl_set:Nn #2 {#1} }
9110     \ior_close:N \g__file_internal_ior
9111   }
9112 \cs_new_protected:Npn \__file_add_path_search:nN #1#2
9113   {
9114     \tl_set:Nn #2 { \q_no_value }
9115   {*package}
9116     \cs_if_exist:NT \input@path
9117     {
9118       \seq_set_eq:NN \l__file_saved_search_path_seq \l__file_search_path_seq
9119       \seq_set_split:NNV \l__file_internal_seq { , } \input@path
9120       \seq_concat:NNN \l__file_search_path_seq
9121         \l__file_search_path_seq \l__file_internal_seq
9122     }
9123   {*}package
9124     \seq_map_inline:Nn \l__file_search_path_seq
9125     {
9126       \__ior_open:Nn \g__file_internal_ior { ##1 #1 }
9127       \ior_if_eof:NTF \g__file_internal_ior
9128         {
9129           \tl_set:Nx #2 { ##1 #1 }
9130           \seq_map_break:
9131         }
9132     }
9133   {*}package
9134     \cs_if_exist:NT \input@path
9135       { \seq_set_eq:NN \l__file_search_path_seq \l__file_saved_search_path_seq }
9136   {*}package
9137 }
```

(End definition for \file_add_path:nN This function is documented on page 157.)

\file_if_exist:nTF

The test for the existence of a file is a wrapper around the function to add a path to a file. If the file was found, the path will contain something, whereas if the file was not located then the return value will be \q_no_value.

```
9138 \prg_new_protected_conditional:Npnn \file_if_exist:n { T , F , TF }
9139   {
9140     \file_add_path:nN {#1} \l__file_internal_name_tl
```

```

9141   \quark_if_no_value:NTF \l__file_internal_name_tl
9142     { \prg_return_false: }
9143     { \prg_return_true: }
9144   }
(End definition for \file_if_exist:nTF This function is documented on page 157.)
```

\file_input:n
`_file_input:n _file_input:w
__file_input_aux:w
__file_input_aux:n
__file_input_aux:o`

```

9145 \cs_new_protected:Npn \file_input:n #1
9146   {
9147     \file_add_path:nN {#1} \l__file_internal_name_tl
9148     \quark_if_no_value:NTF \l__file_internal_name_tl
9149     {
9150       \__file_name_sanitize:nn {#1}
9151         { \__msg_kernel_error:nnx { kernel } { file-not-found } }
9152     }
9153     { \__file_input:V \l__file_internal_name_tl }
9154   }
9155 \cs_new_protected:Npn \_\_file_input:n #1
9156   {
9157     \quark_if_nil:oTF { \_\_file_input_aux:w #1 . \q_nil . \q_stop }
9158       { \_\_file_input_aux:o { \tl_to_str:n { #1 .tex } } }
9159       { \_\_file_input_aux:n {#1} }
9160   }
9161 \cs_generate_variant:Nn \_\_file_input:n { V }
9162 \cs_new:Npn \_\_file_input_aux:w #1 . #2 . #3 \q_stop { #2 }
9163 \cs_new_protected:Npn \_\_file_input_aux:n #1
9164   {
9165     {*initex}
9166       \seq_gput_right:Nn \g__file_record_seq {#1}
9167     {*}initex}
9168     {*package}
9169       \clist_if_exist:NTF \@filelist
9170         { \@addtofilelist {#1} }
9171         { \seq_gput_right:Nn \g__file_record_seq {#1} }
9172   {*}package}
9173   \seq_gpush:No \g__file_stack_seq \g_file_current_name_tl
9174   \tl_gset:Nn \g_file_current_name_tl {#1}
9175   \tex_input:D #1 \c_space_tl
9176   \seq_gpop:NN \g__file_stack_seq \l__file_internal_tl
9177   \tl_gset_eq:NN \g_file_current_name_tl \l__file_internal_tl
9178 }
9179 \cs_generate_variant:Nn \_\_file_input_aux:n { o }
```

(End definition for \file_input:n This function is documented on page 157.)

\file_path_include:n
\file_path_remove:n
`__file_path_include:n`

Wrapper functions to manage the search path.

```

9180 \cs_new_protected:Npn \file_path_include:n #1
9181   { \__file_name_sanitize:nn {#1} { \_\_file_path_include:n } }
```

```

9182 \cs_new_protected:Npn \__file_path_include:n #1
9183 {
9184     \seq_if_in:NnF \l__file_search_path_seq {#1}
9185     { \seq_put_right:Nn \l__file_search_path_seq {#1} }
9186 }
9187 \cs_new_protected:Npn \file_path_remove:n #1
9188 {
9189     \__file_name_sanitize:nn {#1}
9190     { \seq_remove_all:Nn \l__file_search_path_seq }
9191 }

```

(End definition for `\file_path_include:n`. This function is documented on page 158.)

`\file_list:` A function to list all files used to the log, without duplicates. In package mode, if `\@filelist` is still defined, we need to take it into account (we capture it `\AtBeginDocument` into `\g__file_record_seq`), turning each file name into a string.

```

9192 \cs_new_protected_nopar:Npn \file_list:
9193 {
9194     \seq_set_eq:NN \l__file_internal_seq \g__file_record_seq
9195 <*package>
9196     \clist_if_exist:NT \@filelist
9197     {
9198         \clist_map_inline:Nn \@filelist
9199         {
9200             \seq_put_right:No \l__file_internal_seq
9201             { \tl_to_str:n {##1} }
9202         }
9203     }
9204 </package>
9205     \seq_remove_duplicates:N \l__file_internal_seq
9206     \iow_log:n { *~File~List~* }
9207     \seq_map_inline:Nn \l__file_internal_seq { \iow_log:n {##1} }
9208     \iow_log:n { ****}
9209 }

```

(End definition for `\file_list:`. This function is documented on page 158.)

When used as a package, there is a need to hold onto the standard file list as well as the new one here. File names recorded in `\@filelist` must be turned to strings before being added to `\g__file_record_seq`.

```

9210 <*package>
9211 \AtBeginDocument
9212 {
9213     \clist_map_inline:Nn \@filelist
9214     {
9215         \seq_gput_right:No \g__file_record_seq { \tl_to_str:n {#1} }
9216     }
9217 </package>

```

19.2 Input operations

9217 `<@@=ior>`

19.2.1 Variables and constants

\c_term_ior Reading from the terminal (with a prompt) is done using a positive but non-existent stream number. Unlike writing, there is no concept of reading from the log.

```
9218 \cs_new_eq:NN \c_term_ior \c_sixteen
```

(End definition for `\c_term_ior` This variable is documented on page 162.)

\c__ior_streams_tl The list of streams available, by number.

```
9219 \tl_const:Nn \c__ior_streams_tl
9220 {
9221   \c_zero
9222   \c_one
9223   \c_two
9224   \c_three
9225   \c_four
9226   \c_five
9227   \c_six
9228   \c_seven
9229   \c_eight
9230   \c_nine
9231   \c_ten
9232   \c_eleven
9233   \c_twelve
9234   \c_thirteen
9235   \c_fourteen
9236   \c_fifteen
9237 }
```

(End definition for `\c__ior_streams_tl` This variable is documented on page ??.)

\g__ior_streams_prop The allocations for streams are stored in property lists, which are set up to have a “full” set of allocations from the start. In package mode, a few slots are always taken, so these are blocked off from use.

```
9238 \prop_new:N \g__ior_streams_prop
9239 {*package}
9240 \prop_put:Nnn \g__ior_streams_prop { 0 } { LaTeX2e~reserved }
9241 
```

(End definition for `\g__ior_streams_prop` This variable is documented on page ??.)

\l__ior_stream_int Used to track the number allocated to the stream being created: this is taken from the property list but does alter.

```
9242 \int_new:N \l__ior_stream_int
```

(End definition for `\l__ior_stream_int` This variable is documented on page ??.)

19.2.2 Stream management

`__ior_new:N` The lowest level for stream management is actually creating raw TeX streams. As these are very limited (even with ε -TeX), this should not be addressed directly.

```

9243  {*initex}
9244  \__alloc_setup_type:nnn { ior } \c_zero \c_sixteen
9245  \cs_new_protected:Npn \__ior_new:N #1
9246  { \__alloc_reg:nNN { ior } \tex_chardef:D #1 }
9247  {/initex}
9248  {*package}
9249  \cs_set_eq:NN \__ior_new:N \newread
9250  {/package}
9251  \cs_generate_variant:Nn \__ior_new:N { c }
(End definition for \__ior_new:N and \__ior_new:c)
```

`\ior_new:N` Reserving a new stream is done by defining the name as equal to using the terminal.

```

\ior_new:c
9252  \cs_new_protected:Npn \ior_new:N #1 { \cs_new_eq:NN #1 \c_term_ior }
9253  \cs_generate_variant:Nn \ior_new:N { c }
(End definition for \ior_new:N and \ior_new:c These functions are documented on page ??.)
```

`\g_file_internal_ior` Delayed from the file section so that the mechanisms are in place.

```

9254  \ior_new:N \g_file_internal_ior
(End definition for \g_file_internal_ior This variable is documented on page ??.)
```

`\ior_open:Nn` Opening a stream starts with a call to the closing function: this is safest. There is then a loop through the allocation number list to find the first free stream number. When one is found the allocation can take place, the information can be stored and finally the file can actually be opened. Before any actual file operations there is a precaution against special characters in file names. There is an intermediate auxiliary to allow path addition, keeping the internal function fast and avoiding an infinite loop.

```

\ior_open:cn
\ior_open:NnTF
\__ior_open_aux:Nn
\__ior_open_aux:NnTF
\__ior_open:Nn
\__ior_open:No
9255  \cs_new_protected:Npn \ior_open:Nn #1#2
9256  { \__file_name_sanitize:nn {#2} { \__ior_open_aux:Nn #1 } }
9257  \cs_generate_variant:Nn \ior_open:Nn { c }
9258  \cs_new_protected:Npn \__ior_open_aux:Nn #1#2
9259  {
9260    \file_add_path:nN {#2} \l_file_internal_name_tl
9261    \quark_if_no_value:NTF \l_file_internal_name_tl
9262    { \__msg_kernel_error:nnx { kernel } { file-not-found } {#2} }
9263    { \__ior_open:No #1 \l_file_internal_name_tl }
9264  }
9265  \prg_new_protected_conditional:Npnn \ior_open:Nn #1#2 { T , F , TF }
9266  { \__file_name_sanitize:nn {#2} { \__ior_open_aux:NnTF #1 } }
9267  \cs_new_protected:Npn \__ior_open_aux:NnTF #1#2
9268  {
9269    \file_add_path:nN {#2} \l_file_internal_name_tl
9270    \quark_if_no_value:NTF \l_file_internal_name_tl
9271    { \prg_return_false: }
9272 }
```

```

9273     \__ior_open:No #1 \l__file_internal_name_tl
9274     \prg_return_true:
9275   }
9276 }
9277 \cs_generate_variant:Nn \ior_open:NnT { c }
9278 \cs_generate_variant:Nn \ior_open:NnF { c }
9279 \cs_generate_variant:Nn \ior_open:NnTF { c }
9280 \cs_new_protected:Npn \__ior_open:Nn #1#2
9281 {
9282   \ior_close:N #1
9283   \int_set_eq:NN \l__ior_stream_int \c_sixteen
9284   \tl_map_function:NN \c__ior_streams_tl \__ior_alloc:n
9285   \int_compare:nNnTF \l__ior_stream_int = \c_sixteen
9286     { \__msg_kernel_fatal:nn { kernel } { input-streams-exhausted } }
9287   {
9288     \__ior_alloc:N #1
9289     \prop_gput:NVn \g__ior_streams_prop \l__ior_stream_int {#2}
9290     \tex_openin:D #1#2 \scan_stop:
9291   }
9292 }
9293 \cs_generate_variant:Nn \__ior_open:Nn { No }
(End definition for \ior_open:Nn and \ior_open:cn These functions are documented on page 158.)
```

`__ior_alloc:n` See if a particular stream is available: the property list contains file names for streams in use, so any unused ones are for the taking.

```

9294 \cs_new_protected:Npn \__ior_alloc:n #1
9295 {
9296   \prop_if_in:NnF \g__ior_streams_prop {#1}
9297   {
9298     \int_set:Nn \l__ior_stream_int {#1}
9299     \tl_map_break:
9300   }
9301 }
```

(End definition for __ior_alloc:n)

`__ior_alloc:N` `__ior_alloc:` `\g__ior_internal_ior` Allocating a raw stream is much easier in iniTeX mode than for the package. For the format, all streams will be allocated by `\l3file` and so there is a simple check to see if a raw stream is actually available. On the other hand, for the package there will be non-managed streams. So if the managed one is not open, a check is made to see if some other managed stream is available before deciding to open a new one. If a new one is needed, we get the number allocated by L^AT_EX 2 _{ϵ} to get “back on track” with allocation.

```

9302 \ior_new:N \g__ior_internal_ior
9303 \cs_new_protected:Npn \__ior_alloc:N #1
9304 {
9305   \cs_if_exist:cF { g_ior_ \int_use:N \l__ior_stream_int _ior }
9306   {
9307     (*package)
9308       \__ior_alloc:
9309       \int_compare:nNnT \l__ior_stream_int = \c_sixteen
```

```

9310      {
9311          \__ior_new:N \g__ior_internal_ior
9312          \int_set:Nn \l__ior_stream_int { \g__ior_internal_ior }
9313          \cs_gset_eq:cN
9314              { g_ior_ \int_use:N \l__ior_stream_int _ior } \g__ior_internal_ior
9315      }
9316  
```

`</package>`

`*initex`

`__ior_new:c { g_ior_ \int_use:N \l__ior_stream_int _ior }`

`</initex>`

`}`

`\int_use:N \l__ior_stream_int _ior }`

`}`

`*package`

`\cs_new_protected_nopar:Npn __ior_alloc:`

`{`

`\int_incr:N \l__ior_stream_int`

`\int_compare:nNnT \l__ior_stream_int < \c_sixteen`

`{`

`\cs_if_exist:cTF { g_ior_ \int_use:N \l__ior_stream_int _ior }`

`{`

`\prop_if_in:NVT \g__ior_streams_prop \l__ior_stream_int`

`{ __ior_alloc: }`

`}`

`{ __ior_alloc: }`

`}`

`}`

`</package>`

(End definition for `__ior_alloc:N` This function is documented on page ??.)

\ior_close:N Closing a stream is not quite the reverse of opening one. First, the close operation is easier than the open one, and second as the stream is actually a number we can use it directly to show that the slot has been freed up.

```

9338 \cs_new_protected:Npn \ior_close:N #1
9339 {
9340     \__chk_if_exist_cs:N #1
9341     \int_compare:nNnF #1 < \c_zero
9342     {
9343         \int_compare:nNnF #1 > \c_fifteen
9344         {
9345             \tex_closein:D #1
9346             \prop_gremove:NV \g__ior_streams_prop #1
9347             \cs_gset_eq:NN #1 \c_term_ior
9348         }
9349     }
9350 }
9351 \cs_generate_variant:Nn \ior_close:N { c }

```

(End definition for `\ior_close:N` and `\ior_close:c` These functions are documented on page ??.)

\ior_list_streams: Show the property lists, but with some “pretty printing”. See the `l3msg` module. If there are no open read streams, issue the message `show-no-stream`, and show an empty token list. If there are open read streams, format them with `_msg_show_item_unbraced:nn`, and with the message `show-open-streams`.

```

9352 \cs_new_protected:Npn \ior_list_streams:
9353   { \__ior_list_streams:Nn \g__ior_streams_prop { input } }
9354 \cs_new_protected:Npn \__ior_list_streams:Nn #1#2
9355   {
9356     \__msg_term:nnn { LaTeX / kernel }
9357     { \prop_if_empty:NTF #1 { show-no-stream } { show-open-streams } }
9358     {#2}
9359     \__msg_show_variable:n
9360     { \prop_map_function:NN #1 \__msg_show_item_unbraced:nn }
9361   }

```

(End definition for `\ior_list_streams`: This function is documented on page 159.)

19.2.3 Reading input

\if_eof:w The primitive conditional

```

9362 \cs_new_eq:NN \if_eof:w \tex_ifeof:D
(End definition for \if_eof:w)

```

\ior_if_eof:p:N To test if some particular input stream is exhausted the following conditional is provided.

```

9363 \prg_new_conditional:Nnn \ior_if_eof:N { p , T , F , TF }
9364   {
9365     \cs_if_exist:NTF #1
9366     {
9367       \if_int_compare:w #1 = \c_sixteen
9368         \prg_return_true:
9369       \else:
9370         \if_eof:w #1
9371           \prg_return_true:
9372         \else:
9373           \prg_return_false:
9374         \fi:
9375       \fi:
9376     }
9377   { \prg_return_true: }
9378 }

```

(End definition for `\ior_if_eof:N` These functions are documented on page 159.)

\ior_get:NN And here we read from files.

```

9379 \cs_new_protected:Npn \ior_get:NN #1#2
9380   { \tex_read:D #1 to #2 }

```

(End definition for `\ior_get:NN` This function is documented on page 159.)

\ior_get_str:NN Reading as strings is a more complicated wrapper, as we wish to remove the endline character.

```

9381 \cs_new_protected:Npn \ior_get_str:NN #1#2
9382 {
9383   \use:x
9384   {
9385     \int_set_eq:NN \tex_endlinechar:D \c_minus_one
9386     \exp_not:n { \etex_readline:D #1 to #2 }
9387     \int_set:Nn \tex_endlinechar:D { \int_use:N \tex_endlinechar:D }
9388   }
9389 }
```

(End definition for `\ior_get_str:NN` This function is documented on page 159.)

19.3 Output operations

9390 ⟨@=iow⟩

There is a lot of similarity here to the input operations, at least for many of the basics. Thus quite a bit is copied from the earlier material.

19.3.1 Variables and constants

\c_log_iow Here we allocate two output streams for writing to the transcript file only (`\c_log_iow`) and to both the terminal and transcript file (`\c_term_iow`).

```

9391 \cs_new_eq:NN \c_log_iow \c_minus_one
9392 \cs_new_eq:NN \c_term_iow \c_sixteen
```

(End definition for `\c_log_iow` and `\c_term_iow` These variables are documented on page 162.)

\c__iow_streams_tl The list of streams available, by number: copied from the input operations.

```
9393 \cs_new_eq:NN \c__iow_streams_tl \c__ior_streams_tl
```

(End definition for `\c__iow_streams_tl` This variable is documented on page ??.)

\g__iow_streams_prop As for reads, but with more reserved as L^AT_EX 2_E takes up a few here.

```

9394 \prop_new:N \g__iow_streams_prop
9395 {*package}
9396 \prop_put:Nnn \g__iow_streams_prop { 0 } { LaTeX2e~reserved }
9397 \prop_put:Nnn \g__iow_streams_prop { 1 } { LaTeX2e~reserved }
9398 \prop_put:Nnn \g__iow_streams_prop { 2 } { LaTeX2e~reserved }
9399 
```

(End definition for `\g__iow_streams_prop` This variable is documented on page ??.)

\l__iow_stream_int Used to track the number allocated to the stream being created: this is taken from the property list but does alter. The two allocation routines only need one register, so we save one here.

```
9400 \cs_new_eq:NN \l__iow_stream_int \l__ior_stream_int
```

(End definition for `\l__iow_stream_int` This variable is documented on page ??.)

19.4 Stream management

`__iow_new:N` The same idea as for input, but with a separate set of functions.

```

\__iow_new:c
 9401  {*initex}
 9402  \_alloc_setup_type:nnn { iow } \c_zero \c_sixteen
 9403  \cs_new_protected:Npn \__iow_new:N #1
 9404  { \_alloc_reg:nNN { iow } \tex_chardef:D #1 }
 9405  {/initex}
 9406  {*package}
 9407  \cs_set_eq:NN \__iow_new:N \newwrite
 9408  {/package}
 9409  \cs_generate_variant:Nn \__iow_new:N { c }
(End definition for \__iow_new:N and \__iow_new:c)
```

`\iow_new:N` Reserving a new stream is done by defining the name as equal to writing to the terminal:
`\iow_new:c` odd but at least consistent.

```

 9410  \cs_new_protected:Npn \iow_new:N #1 { \cs_new_eq:NN #1 \c_term_iow }
 9411  \cs_generate_variant:Nn \iow_new:N { c }
(End definition for \iow_new:N and \iow_new:c These functions are documented on page ??.)
```

`\iow_open:Nn` The same idea as for reading, but without the path.

```

\iow_open:cn
\__iow_open:Nn
 9412  \cs_new_protected:Npn \iow_open:Nn #1#2
 9413  { \__file_name_sanitize:nn {#2} { \__iow_open:Nn #1 } }
 9414  \cs_generate_variant:Nn \iow_open:Nn { c }
 9415  \cs_new_protected:Npn \__iow_open:Nn #1#2
 9416  {
 9417    \iow_close:N #1
 9418    \int_set_eq:NN \l__iow_stream_int \c_sixteen
 9419    \tl_map_function:NN \c__iow_streams_tl \__iow_alloc:n
 9420    \int_compare:nNnTF \l__iow_stream_int = \c_sixteen
 9421    { \__msg_kernel_fatal:nn { kernel } { output-streams-exhausted } }
 9422    {
 9423      \__iow_alloc:N #1
 9424      \prop_gput:NVn \g__iow_streams_prop \l__iow_stream_int {#2}
 9425      \tex_immediate:D \tex_openout:D #1#2 \scan_stop:
 9426    }
 9427  }
```

(End definition for \iow_open:Nn and \iow_open:cn These functions are documented on page ??.)

`__iow_alloc:n` Identical to the input routine, but with the appropriate names used (when l3docstrip has done it's job!).

```

 9428  \cs_new_protected:Npn \__iow_alloc:n #1
 9429  {
 9430    \prop_if_in:NnF \g__iow_streams_prop {#1}
 9431    {
 9432      \int_set:Nn \l__iow_stream_int {#1}
 9433      \tl_map_break:
 9434    }
 9435 }
```

(End definition for `__iow_alloc:n`)

```
\_\_iow\_alloc:N Exactly the same as for reading!
\_\_iow\_alloc:
9436 \iow\_new:N \g\_\_iow\_internal\_iow
9437 \cs\_new\_protected:Npn \_\_iow\_alloc:N #1
9438 {
9439     \cs\_if\_exist:cF { g\_iow\_ \int\_use:N \l\_\_iow\_stream\_int \_iow }
9440     {
9441         /*package*/
9442             \_\_iow\_alloc:
9443                 \int\_compare:nNnT \l\_\_iow\_stream\_int = \c\_sixteen
9444                 {
9445                     \_\_iow\_new:N \g\_\_iow\_internal\_iow
9446                     \int\_set:Nn \l\_\_iow\_stream\_int { \g\_\_iow\_internal\_iow }
9447                     \cs\_gset\_eq:cN
9448                         { g\_iow\_ \int\_use:N \l\_\_iow\_stream\_int \_iow } \g\_\_iow\_internal\_iow
9449                 }
9450     
```

9451 /*initex*/
9452 __iow_new:c { g_iow_ \int_use:N \l__iow_stream_int _iow }
9453

```
9454     
```

9455 \cs_gset_eq:Nc #1 { g_iow_ \int_use:N \l__iow_stream_int _iow }
9456 }
9457 /*package*/
9458 \cs_new_protected_nopar:Npn __iow_alloc:
9459 {
9460 \int_incr:N \l__iow_stream_int
9461 \int_compare:nNnT \l__iow_stream_int < \c_sixteen
9462 {
9463 \cs_if_exist:cTF { g_iow_ \int_use:N \l__iow_stream_int _iow }
9464 {
9465 \prop_if_in:NVT \g__iow_streams_prop \l__iow_stream_int
9466 { __iow_alloc: }
9467 }
9468 { __iow_alloc: }
9469 }
9470 }
9471

9471

(End definition for `__iow_alloc:N` This function is documented on page ??.)

\iow_close:N Closing a stream is not quite the reverse of opening one. First, the close operation is easier than the open one, and second as the stream is actually a number we can use it directly to show that the slot has been freed up.

```
9472 \cs\_new\_protected:Npn \iow\_close:N #1
9473 {
9474     \_\_chk\_if\_exist\_cs:N #1
9475     \int\_compare:nNnF #1 < \c\_zero
9476     {
```

```

9477     \int_compare:nNnF #1 > \c_fifteen
9478     {
9479         \tex_immediate:D \tex_closeout:D #1
9480         \prop_gremove:NV \g__iow_streams_prop #1
9481         \cs_gset_eq:NN #1 \c_term_iow
9482     }
9483 }
9484 }
9485 \cs_generate_variant:Nn \iow_close:N { c }
(End definition for \iow_close:N and \iow_close:c These functions are documented on page ??.)
```

\iow_list_streams: Done as for input, but with a copy of the auxiliary so the name is correct.

```

\__iow_list_streams:Nn
9486 \cs_new_protected:Npn \iow_list_streams:
9487     { \__iow_list_streams:Nn \g__iow_streams_prop { output } }
9488 \cs_new_eq:NN \__iow_list_streams:Nn \__ior_list_streams:Nn
(End definition for \iow_list_streams: This function is documented on page ??.)
```

19.4.1 Deferred writing

\iow_shipout_x:Nn First the easy part, this is the primitive, which expects its argument to be braced.

```

\iow_shipout_x:Nx
9489 \cs_new_protected:Npn \iow_shipout_x:Nn #1#2
9490     { \tex_write:D #1 {#2} }
9491 \cs_generate_variant:Nn \iow_shipout_x:Nn { Nx }
(End definition for \iow_shipout_x:Nn and \iow_shipout_x:Nx These functions are documented on page ??.)
```

\iow_shipout:Nn With ε -TEX available deferred writing without expansion is easy.

```

\iow_shipout:Nx
9492 \cs_new_protected:Npn \iow_shipout:Nn #1#2
9493     { \tex_write:D #1 { \exp_not:n {#2} } }
9494 \cs_generate_variant:Nn \iow_shipout:Nn { Nx }
(End definition for \iow_shipout:Nn and \iow_shipout:Nx These functions are documented on page ??.)
```

19.4.2 Immediate writing

\iow_now:Nn This routine writes the second argument onto the output stream without expansion. If this stream isn't open, the output goes to the terminal instead. If the first argument is no output stream at all, we get an internal error. We don't use the expansion done by \write to get the Nx variant, because it differs in subtle ways from x-expansion, namely, macro parameter characters would not need to be doubled.

```

\iow_now:Nx
9495 \cs_new_protected:Npn \iow_now:Nn #1#2
9496     { \tex_immediate:D \tex_write:D #1 { \exp_not:n {#2} } }
9497 \cs_generate_variant:Nn \iow_now:Nn { Nx }
(End definition for \iow_now:Nn and \iow_now:Nx These functions are documented on page ??.)
```

```

\iow_log:n Writing to the log and the terminal directly are relatively easy.
\iow_log:x   9498 \cs_set_protected_nopar:Npn \iow_log:x { \iow_now:Nx \c_log_iow }
\iow_term:n  9499 \cs_new_protected_nopar:Npn \iow_log:n { \iow_now:Nn \c_log_iow }
\iow_term:x  9500 \cs_set_protected_nopar:Npn \iow_term:x { \iow_now:Nx \c_term_iow }
\iow_term:n  9501 \cs_new_protected_nopar:Npn \iow_term:n { \iow_now:Nn \c_term_iow }

(End definition for \iow_log:n and \iow_log:x These functions are documented on page ??.)

```

19.4.3 Special characters for writing

\iow_newline: Global variable holding the character that forces a new line when something is written to an output stream

```

9502 \cs_new_nopar:Npn \iow_newline: { ^J }
(End definition for \iow_newline: This function is documented on page 160.)

```

\iow_char:N Function to write any escaped char to an output stream.

```

9503 \cs_new_eq:NN \iow_char:N \cs_to_str:N
(End definition for \iow_char:N This function is documented on page 160.)

```

19.4.4 Hard-wrapping lines to a character count

The code here implements a generic hard-wrapping function. This is used by the messaging system, but is designed such that it is available for other uses.

\l_iow_line_count_int This is the “raw” number of characters in a line which can be written to the terminal. The standard value is the line length typically used by TeXLive and MikTeX.

```

9504 \int_new:N \l_iow_line_count_int
9505 \int_set:Nn \l_iow_line_count_int { 78 }
(End definition for \l_iow_line_count_int This variable is documented on page 161.)

```

\l__iow_target_count_int This stores the target line count: the full number of characters in a line, minus any part for a leader at the start of each line.

```

9506 \int_new:N \l__iow_target_count_int
(End definition for \l__iow_target_count_int)

```

\l__iow_current_line_int **\l__iow_current_word_int** **\l__iow_current_indentation_int** These store the number of characters in the line and word currently being constructed, and the current indentation, respectively.

```

9507 \int_new:N \l__iow_current_line_int
9508 \int_new:N \l__iow_current_word_int
9509 \int_new:N \l__iow_current_indentation_int
(End definition for \l__iow_current_line_int, \l__iow_current_word_int, and \l__iow_current_indentation_int)

```

\l__iow_current_line_t1 **\l__iow_current_word_t1** **\l__iow_current_indentation_t1** These hold the current line of text and current word, and a number of spaces for indentation, respectively.

```

9510 \tl_new:N \l__iow_current_line_t1
9511 \tl_new:N \l__iow_current_word_t1
9512 \tl_new:N \l__iow_current_indentation_t1
(End definition for \l__iow_current_line_t1, \l__iow_current_word_t1, and \l__iow_current_indentation_t1)

```

\l_iow_wrap_tl Used for the expansion step before detokenizing, and for the output from wrapping text: fully expanded and with lines which are not overly long.

```
9513 \tl_new:N \l_iow_wrap_tl  
(End definition for \l_iow_wrap_tl)
```

\l_iow_newline_tl The token list inserted to produce the new line, with the *<run-on text>*.

```
9514 \tl_new:N \l_iow_newline_tl  
(End definition for \l_iow_newline_tl)
```

\l_iow_line_start_bool Boolean to avoid adding a space at the beginning of forced newlines, and to know when to add the indentation.

```
9515 \bool_new:N \l_iow_line_start_bool  
(End definition for \l_iow_line_start_bool)
```

\c_catcode_other_space_tl Lowercase a character with category code 12 to produce an “other” space. We can do everything within the group, because \tl_const:Nn defines its argument globally.

```
9516 \group_begin:  
9517   \char_set_catcode_other:N \*  
9518   \char_set_lccode:nn {'\*} {'\ }  
9519   \tl_to_lowercase:n { \tl_const:Nn \c_catcode_other_space_tl { * } }  
9520 \group_end:  
(End definition for \c_catcode_other_space_tl This function is documented on page 162.)
```

Every special action of the wrapping code is preceded by the same recognizable string, \c_iow_wrap_marker_tl. Upon seeing that “word”, the wrapping code reads one space-delimited argument to know what operation to perform. The setting of \escapechar here is not very important, but makes \c_iow_wrap_marker_tl look nicer.

```
9521 \group_begin:  
9522   \int_set_eq:NN \tex_escapechar:D \c_minus_one  
9523   \tl_const:Nx \c_iow_wrap_marker_tl  
9524   { \tl_to_str:n { \^I \^O \^W \^_ \^W \^R \^A \^P } }  
9525 \group_end:  
9526 \tl_map_inline:nn  
9527   { { end } { newline } { indent } { unindent } }  
9528   {  
9529     \tl_const:cx { c_iow_wrap_#1_marker_tl }  
9530     {  
9531       \c_catcode_other_space_tl  
9532       \c_iow_wrap_marker_tl  
9533       \c_catcode_other_space_tl  
9534       #1  
9535       \c_catcode_other_space_tl  
9536     }  
9537   }  
(End definition for \c_iow_wrap_marker_tl This function is documented on page 162.)
```

`\iow_indent:n
_iow_indent:n`

We give a dummy (protected) definition to `\iow_indent:n` when outside messages. Within wrapped message, it places the instruction for increasing the indentation before its argument, and the instruction for unindenting afterwards. Note that there will be no forced line-break, so the indentation only changes when the next line is started.

```
9538 \cs_new_protected:Npn \iow_indent:n #1 { }  
9539 \cs_new:Npx \_iow_indent:n #1  
9540 {  
9541   \c__iow_wrap_indent_marker_tl  
9542   #1  
9543   \c__iow_wrap_unindent_marker_tl  
9544 }
```

(End definition for `\iow_indent:n` This function is documented on page 161.)

`\iow_wrap:nnnN`

The main wrapping function works as follows. First give `\``, `_` and other formatting commands the correct definition for messages, before fully-expanding the input. In package mode, the expansion uses L^AT_EX 2_ε's `\protect` mechanism. Afterwards, set the newline marker (two assignments to fully expand, then convert to a string) and its length, and initialize some registers. There is then a loop over each word in the input, which will do the actual wrapping. After the loop, the resulting text is passed on to the function which has been given as a post-processor. The argument `#4` is available for additional set up steps for the output. The definition of `\`` and `_` use an “other” space rather than a normal space, because the latter might be absorbed by T_EX to end a number or other f-type expansions. The `\tl_to_str:N` step converts the “other” space back to a normal space.

```
9545 \cs_new_protected:Npn \iow_wrap:nnnN #1#2#3#4  
9546 {  
9547   \group_begin:  
9548     \int_set_eq:NN \tex_escapechar:D \c_minus_one  
9549     \cs_set_nopar:Npx \{ { \token_to_str:N \{ }  
9550     \cs_set_nopar:Npx \# { \token_to_str:N \# }  
9551     \cs_set_nopar:Npx \} { \token_to_str:N \} }  
9552     \cs_set_nopar:Npx \% { \token_to_str:N \% }  
9553     \cs_set_nopar:Npx \~ { \token_to_str:N \~ }  
9554     \int_set:Nn \tex_escapechar:D { 92 }  
9555     \cs_set_eq:NN \` \c__iow_wrap_newline_marker_tl  
9556     \cs_set_eq:NN \_ \c_catcode_other_space_tl  
9557     \cs_set_eq:NN \iow_indent:n \_iow_indent:n  
9558     #3  
9559   {*initex}  
9560     \tl_set:Nx \l__iow_wrap_tl {#1}  
9561   
```

```
9562   {*package}  
9563     \protected@edef \l__iow_wrap_tl {#1}  
9564   
```

This is a bit of a hack to measure the string length of the run on text without the `I3str` module (which is still experimental). This should be replaced once the string module is finalised with something a little cleaner.

```

9565   \tl_set:Nx \l__iow_newline_tl { \iow_newline: #2 }
9566   \tl_set:Nx \l__iow_newline_tl { \tl_to_str:N \l__iow_newline_tl }
9567   \tl_replace_all:Nnn \l__iow_newline_tl { ~ } { \c_space_tl }
9568   \int_set:Nn \l__iow_target_count_int
9569     { \l_iow_line_count_int - \tl_count:N \l__iow_newline_tl + \c_one }
9570   \int_zero:N \l__iow_current_indentation_int
9571   \tl_clear:N \l__iow_current_indentation_tl
9572   \int_zero:N \l__iow_current_line_int
9573   \tl_clear:N \l__iow_current_line_tl
9574   \bool_set_true:N \l__iow_line_start_bool
9575   \use:x
9576   {
9577     \exp_not:n { \tl_clear:N \l__iow_wrap_tl }
9578     \l__iow_wrap_loop:w
9579     \tl_to_str:N \l__iow_wrap_tl
9580     \tl_to_str:N \c__iow_wrap_end_marker_tl
9581     \c_space_tl \c_space_tl
9582     \exp_not:N \q_stop
9583   }
9584   \exp_args:NNo \group_end:
9585   #4 \l__iow_wrap_tl
9586 }

```

(End definition for `\iow_wrap:nnnN` This function is documented on page 161.)

`\l__iow_wrap_loop:w` The loop grabs one word in the input, and checks whether it is the special marker, or a normal word.

```

9587 \cs_new_protected:Npn \l__iow_wrap_loop:w #1 ~ %
9588 {
9589   \tl_set:Nn \l__iow_current_word_tl {#1}
9590   \tl_if_eq:NNTF \l__iow_current_word_tl \c__iow_wrap_marker_tl
9591     { \l__iow_wrap_special:w }
9592     { \l__iow_wrap_word: }
9593 }

```

(End definition for `\l__iow_wrap_loop:w`)

`\l__iow_wrap_word:` For a normal word, update the line count, then test if the current word would fit in the current line, and call the appropriate function. If the word fits in the current line, add it to the line, preceded by a space unless it is the first word of the line. Otherwise, the current line is added to the result, with the run-on text. The current word (and its character count) are then put in the new line.

```

9594 \cs_new_protected_nopar:Npn \l__iow_wrap_word:
9595 {
9596   \int_set:Nn \l__iow_current_word_int
9597     { \l__str_count_ignore_spaces:N \l__iow_current_word_tl }
9598   \int_add:Nn \l__iow_current_line_int { \l__iow_current_word_int }
9599   \int_compare:nNnTF \l__iow_current_line_int < \l__iow_target_count_int
9600     { \l__iow_wrap_word_fits: }
9601     { \l__iow_wrap_word_newline: }
9602 \l__iow_wrap_loop:w

```

```

9603   }
9604 \cs_new_protected_nopar:Npn \__iow_wrap_word_fits:
9605 {
9606   \bool_if:NTF \l__iow_line_start_bool
9607   {
9608     \bool_set_false:N \l__iow_line_start_bool
9609     \tl_put_right:Nx \l__iow_current_line_tl
9610     { \l__iow_current_indentation_tl \l__iow_current_word_tl }
9611     \int_add:Nn \l__iow_current_line_int
9612     { \l__iow_current_indentation_int }
9613   }
9614   {
9615     \tl_put_right:Nx \l__iow_current_line_tl
9616     { ~ \l__iow_current_word_tl }
9617     \int_incr:N \l__iow_current_line_int
9618   }
9619 }
9620 \cs_new_protected_nopar:Npn \__iow_wrap_word_newline:
9621 {
9622   \tl_put_right:Nx \l__iow_wrap_tl
9623   { \l__iow_current_line_tl \l__iow_newline_tl }
9624   \int_set:Nn \l__iow_current_line_int
9625   {
9626     \l__iow_current_word_int
9627     + \l__iow_current_indentation_int
9628   }
9629   \tl_set:Nx \l__iow_current_line_tl
9630   { \l__iow_current_indentation_tl \l__iow_current_word_tl }
9631 }

```

(End definition for `__iow_wrap_word`: This function is documented on page 161.)

```

\__iow_wrap_special:w
\__iow_wrap_newline:w
\__iow_wrap_indent:w
\__iow_wrap_unindent:w
\__iow_wrap_end:w

```

When the “special” marker is encountered, read what operation to perform, as a space-delimited argument, perform it, and remember to loop. In fact, to avoid spurious spaces when two special actions follow each other, we look ahead for another copy of the marker. Forced newlines are almost identical to those caused by overflow, except that here the word is empty. To indent more, add four spaces to the start of the indentation token list. To reduce indentation, rebuild the indentation token list using `\prg_replicate:nn`. At the end, we simply save the last line (without the run-on text), and prevent the loop.

```

9632 \cs_new_protected:Npn \__iow_wrap_special:w #1 ~ #2 ~ #3 ~ %
9633 {
9634   \use:c { __iow_wrap_#1: }
9635   \str_if_eq_x:nnTF { #2~#3 } { ~ \c__iow_wrap_marker_tl }
9636   { \__iow_wrap_special:w }
9637   { \__iow_wrap_loop:w #2 ~ #3 ~ }
9638 }
9639 \cs_new_protected_nopar:Npn \__iow_wrap_newline:
9640 {
9641   \tl_put_right:Nx \l__iow_wrap_tl
9642   { \l__iow_current_line_tl \l__iow_newline_tl }

```

```

9643   \int_zero:N \l__iow_current_line_int
9644   \tl_clear:N \l__iow_current_line_tl
9645   \bool_set_true:N \l__iow_line_start_bool
9646 }
9647 \cs_new_protected_nopar:Npx \__iow_wrap_indent:
9648 {
9649   \int_add:Nn \l__iow_current_indentation_int \c_four
9650   \tl_put_right:Nx \exp_not:N \l__iow_current_indentation_tl
9651     { \c_space_tl \c_space_tl \c_space_tl \c_space_tl }
9652 }
9653 \cs_new_protected_nopar:Npn \__iow_wrap_unindent:
9654 {
9655   \int_sub:Nn \l__iow_current_indentation_int \c_four
9656   \tl_set:Nx \l__iow_current_indentation_tl
9657     { \prg_replicate:nn \l__iow_current_indentation_int { ~ } }
9658 }
9659 \cs_new_protected_nopar:Npn \__iow_wrap_end:
9660 {
9661   \tl_put_right:Nx \l__iow_wrap_tl
9662     { \l__iow_current_line_tl }
9663   \use_none_delimit_by_q_stop:w
9664 }

```

(End definition for `__iow_wrap_special:w` This function is documented on page 161.)

The wrapping code requires to measure the number of character in each word. This could be done with `\tl_count:n`, but it is ten times faster (literally) to use the code below.

```

9665 \cs_new_nopar:Npn \__str_count_ignore_spaces:N
9666   { \exp_args:No \__str_count_ignore_spaces:n }
9667 \cs_new:Npn \__str_count_ignore_spaces:n #1
9668 {
9669   \__int_value:w \__int_eval:w
9670   \exp_after:wN \__str_count_loop:NNNNNNNN \tl_to_str:n {#1}
9671     { X8 } { X7 } { X6 } { X5 } { X4 } { X3 } { X2 } { X1 } { X0 } \q_stop
9672   \__int_eval_end:
9673 }
9674 \cs_new:Npn \__str_count_loop:NNNNNNNN #1#2#3#4#5#6#7#8#9
9675 {
9676   \if_catcode:w X #9
9677     \exp_after:wN \use_none_delimit_by_q_stop:w
9678   \else:
9679     9 +
9680     \exp_after:wN \__str_count_loop:NNNNNNNN
9681   \fi:
9682 }

```

(End definition for `__str_count_ignore_spaces:N` This function is documented on page 161.)

19.5 Messages

```
9683 \__msg_kernel_new:nnn { kernel } { file-not-found }
```

```

9684 { File-'#1'~not~found. }
9685 {
9686   The~requested~file~could~not~be~found~in~the~current~directory,~
9687   in~the~TeX~search~path~or~in~the~LaTeX~search~path.
9688 }
9689 \_\_msg_kernel_new:nnnn { kernel } { input-streams-exhausted }
9690 { Input~streams~exhausted }
9691 {
9692   TeX~can~only~open~up~to~16~input~streams~at~one~time.\\
9693   All~16~are~currently~in~use,~and~something~wanted~to~open~
9694   another~one.
9695 }
9696 \_\_msg_kernel_new:nnnn { kernel } { output-streams-exhausted }
9697 { Output~streams~exhausted }
9698 {
9699   TeX~can~only~open~up~to~16~output~streams~at~one~time.\\
9700   All~16~are~currently~in~use,~and~something~wanted~to~open~
9701   another~one.
9702 }
9703 \_\_msg_kernel_new:nnnn { kernel } { space-in-file-name }
9704 { Space~in~file~name~'#1'. }
9705 {
9706   Spaces~are~not~permitted~in~files~loaded~by~LaTeX: \\
9707   Further~errors~may~follow!
9708 }

```

19.6 Deprecated functions

Deprecated on 2012-06-28, for removal by 2012-12-31.

`\iow_wrap:xnnnN` This was renamed and one unneed argument was removed.

```

9709 \cs_new_protected:Npn \iow_wrap:xnnnN #1#2#3#4#5
9710 { \iow_wrap:nnnN {#1} {#2} {#4} #5 }

```

(End definition for `\iow_wrap:xnnnN` This function is documented on page ??.)

Deprecated on 2012-06-24, for removal by 2012-12-31.

`\l_iow_line_length_int` Simple rename. Here we copy the TeX register.

```

9711 \cs_new_eq:NN \l_iow_line_length_int \l_iow_line_count_int
(End definition for \l_iow_line_length_int This variable is documented on page ??.)

```

`\ior_to:NN` The local variants are renames, while the global variants are deprecated and add the TeX primitive `\global`.

```

\ior_gto:NN
\ior_str_to:NN
\ior_str_gto:NN
9712 \cs_new_eq:NN \ior_to:NN \ior_get:NN
9713 \cs_new_protected_nopar:Npn \ior_gto:NN { \tex_global:D \ior_to:NN }
9714 \cs_new_eq:NN \ior_str_to:NN \ior_get_str:NN
9715 \cs_new_protected_nopar:Npn \ior_str_gto:NN { \tex_global:D \ior_str_to:NN }

```

(End definition for `\ior_to:NN` and others. These functions are documented on page ??.)

Deprecated on 2012-02-10, for removal by 2012-05-31.

\iow_now_when_avail:Nn For writing only if the stream requested is open at all.
\iow_now_when_avail:Nx

```

9716  {*deprecated}
9717  \cs_new_protected:Npn \iow_now_when_avail:Nn #1
9718    { \cs_if_free:NTF #1 { \use_none:n } { \iow_now:Nn #1 } }
9719  \cs_new_protected:Npn \iow_now_when_avail:Nx #1
9720    { \cs_if_free:NTF #1 { \use_none:n } { \iow_now:Nx #1 } }
9721  
```

(End definition for \iow_now_when_avail:Nn and \iow_now_when_avail:Nx These functions are documented on page ??.)

Deprecated on 2011-05-27, for removal by 2011-08-31.

\iow_now_buffer_safe:Nn This is much more easily done using the wrapping system: there is an expansion there, so a bit of a hack is needed.
\iow_now_buffer_safe:Nx

```

9722  {*deprecated}
9723  \cs_new_protected:Npn \iow_now_buffer_safe:Nn #1#2
9724    { \iow_wrap:xnnN { \exp_not:n {#2} } { } \c_zero { } \iow_now:Nn #1 }
9725  \cs_new_protected:Npn \iow_now_buffer_safe:Nx #1#2
9726    { \iow_wrap:xnnN {#2} { } \c_zero { } \iow_now:Nn #1 }
9727  
```

(End definition for \iow_now_buffer_safe:Nn and \iow_now_buffer_safe:Nx These functions are documented on page ??.)

\ior_open_streams: Slightly misleading names.

\iow_open_streams:

```

9728  {*deprecated}
9729  \cs_new_eq:NN \ior_open_streams: \ior_list_streams:
9730  \cs_new_eq:NN \iow_open_streams: \iow_list_streams:
9731  
```

(End definition for \iow_open_streams: This function is documented on page ??.)

9732

20 l3fp implementation

```

9733  {*package}
9734  \ProvidesExplPackage
9735    {\ExplFileName}{\ExplFileDate}{\ExplFileVersion}{\ExplFileDescription}
9736  \_expl_package_check:
9737  
```

21 l3fp-aux implementation

```

9738  {*initex | package}
9739  
```

22 Internal storage of floating points numbers

A floating point number $\langle X \rangle$ is stored as

```
\s__fp \__fp_chk:w ⟨case⟩ ⟨sign⟩ ⟨body⟩ ;
```

Here, ⟨case⟩ is 0 for ± 0 , 1 for normal numbers, 2 for $\pm\infty$, and 3 for `nan`, and ⟨sign⟩ is 0 for positive numbers, 1 for `nans`, and 2 for negative numbers. The ⟨body⟩ of normal numbers is {⟨exponent⟩} {⟨X₁⟩} {⟨X₂⟩} {⟨X₃⟩} {⟨X₄⟩}, with

$$\langle X \rangle = (-1)^{\langle sign \rangle} 10^{-\langle exponent \rangle} \sum_i \langle X_i \rangle 10^{-4i}.$$

Calculations are done in base 10000, *i.e.* one myriad. The ⟨exponent⟩ lies between $\pm \text{c_fp_max_exponent_int} = \pm 10000$ inclusive.

Additionally, positive and negative floating point numbers may only be stored with $1000 \leq \langle X_1 \rangle < 10000$. This requirement is necessary in order to preserve accuracy and speed.

22.1 Using arguments and semicolons

`__fp_use_none_stop_f:n` This function removes an argument (typically a digit) and replaces it by `\exp_stop_f:`, a marker which stops f-type expansion.

```
9740 \cs_new:Npn \__fp_use_none_stop_f:n #1 { \exp_stop_f: }
(End definition for \__fp_use_none_stop_f:n)
```

`__fp_use_s:n` Those functions place a semicolon after one or two arguments (typically digits).

```
9741 \cs_new:Npn \__fp_use_s:n #1 { #1; }
9742 \cs_new:Npn \__fp_use_s:nn #1#2 { #1#2; }
(End definition for \__fp_use_s:n and \__fp_use_s:nn)
```

`__fp_use_none_until_s:w` Those functions select specific arguments among a set of arguments delimited by a semi-colon.

```
9743 \cs_new:Npn \__fp_use_none_until_s:w #1; { }
9744 \cs_new:Npn \__fp_use_i_until_s:nw #1#2; {#1}
9745 \cs_new:Npn \__fp_use_ii_until_s:nnw #1#2#3; {#2}
(End definition for \__fp_use_none_until_s:w, \__fp_use_i_until_s:nw, and \__fp_use_ii_until_s:nnw)
```

`__fp_reverse_args:Nww` Many internal functions take arguments delimited by semicolons, and it is occasionally useful to swap two such arguments.

```
9746 \cs_new:Npn \__fp_reverse_args:Nww #1 #2; #3; { #1 #3; #2; }
(End definition for \__fp_reverse_args:Nww)
```

22.2 Constants, and structure of floating points

`\s_fp` Floating points numbers all start with `\s_fp _fp_chk:w`, where `\s_fp` is equal to the TeX primitive `\relax`, and `_fp_chk:w` is protected. The rest of the floating point number is made of characters (or `\relax`). This ensures that nothing expands under f-expansion, nor under x-expansion. However, when typeset, `\s_fp` does nothing, and `_fp_chk:w` is expanded. We define `_fp_chk:w` to produce an error.

```

9747 \_scan_new:N \s_fp
9748 \cs_new_protected:Npn \_fp_chk:w #1 ;
9749 {
9750     \_msg_kernel_error:nnx { kernel } { misused-fp }
9751     { \fp_to_tl:n { \s_fp \_fp_chk:w #1 ; } }
9752 }
(End definition for \s_fp and \_fp_chk:w)
```

`\s_fp_mark` Aliases of `\tex_relax:D`, used to terminate expressions.

`\s_fp_stop`

```

9753 \_scan_new:N \s_fp_mark
9754 \_scan_new:N \s_fp_stop
```

(End definition for `\s_fp_mark` and `\s_fp_stop`)

`\s_fp_invalid` A couple of scan marks used to indicate where special floating point numbers come from.

```

9755 \_scan_new:N \s_fp_invalid
9756 \_scan_new:N \s_fp_underflow
9757 \_scan_new:N \s_fp_overflow
9758 \_scan_new:N \s_fp_division
9759 \_scan_new:N \s_fp_exact
```

(End definition for `\s_fp_invalid` and others.)

`\c_zero_fp` The special floating points. All of them have the form

`\s_fp _fp_chk:w <case> <sign> \s_fp_... ;`

where the dots in `\s_fp_...` are one of `invalid`, `underflow`, `overflow`, `division`, `exact`, describing how the floating point was created. We define the floating points here as “exact”.

```

9760 \tl_const:Nn \c_zero_fp      { \s_fp \_fp_chk:w 0 0 \s_fp_exact ; }
9761 \tl_const:Nn \c_minus_zero_fp { \s_fp \_fp_chk:w 0 2 \s_fp_exact ; }
9762 \tl_const:Nn \c_inf_fp       { \s_fp \_fp_chk:w 2 0 \s_fp_exact ; }
9763 \tl_const:Nn \c_minus_inf_fp { \s_fp \_fp_chk:w 2 2 \s_fp_exact ; }
9764 \tl_const:Nn \c_nan_fp       { \s_fp \_fp_chk:w 3 1 \s_fp_exact ; }
```

(End definition for `\c_zero_fp` and others. These variables are documented on page ??.)

`\c_fp_max_exponent_int` Normal floating point numbers have an exponent at most `max_exponent` in absolute value. Larger numbers are rounded to $\pm\infty$. Smaller numbers are subnormal (not implemented yet), and digits beyond $10^{-\text{max_exponent}}$ are rounded away, hence the true minimum exponent is $-\text{max_exponent} - 16$; beyond this, numbers are rounded to zero. Why this choice of limits? When computing $(a \cdot 10^n)(b \cdot 10^p)$, we need to evaluate $\log(a \cdot 10^n) = \log(a) + n \log(10)$ as a fixed point number, which we manipulate as blocks

of 4 digits. Multiplying such a fixed point number by $n < 10000$ is much cheaper than larger n , because we can multiply n with each block safely.

```
9765 \int_const:Nn \c_fp_max_exponent_int { 10000 }
(End definition for \c_fp_max_exponent_int)
```

_fp_zero_fp:N In case of overflow or underflow, we have to output a zero or infinity with a given sign.

```
9766 \cs_new:Npn \_fp_zero_fp:N #1 { \s_fp \_fp_chk:w 0 #1 \s_fp_underflow ; }
9767 \cs_new:Npn \_fp_inf_fp:N #1 { \s_fp \_fp_chk:w 2 #1 \s_fp_overflow ; }
(End definition for \_fp_zero_fp:N and \_fp_inf_fp:N)
```

_fp_max_fp:N In some cases, we need to output the smallest or biggest positive or negative finite numbers.

```
9768 \cs_new:Npn \_fp_min_fp:N #1
9769 {
9770   \s_fp \_fp_chk:w 1 #1
9771   { \int_eval:n { - \c_fp_max_exponent_int } }
9772   {1000} {0000} {0000} {0000} ;
9773 }
9774 \cs_new:Npn \_fp_max_fp:N #1
9775 {
9776   \s_fp \_fp_chk:w 1 #1
9777   { \int_use:N \c_fp_max_exponent_int }
9778   {9999} {9999} {9999} {9999} ;
9779 }
```

(End definition for _fp_max_fp:N and _fp_min_fp:N)

_fp_exponent:w For normal numbers, the function expands to the exponent, otherwise to 0.

```
9780 \cs_new:Npn \_fp_exponent:w \s_fp \_fp_chk:w #1
9781 {
9782   \if_meaning:w 1 #1
9783     \exp_after:wN \_fp_use_i_until_s:nnw
9784   \else:
9785     \exp_after:wN \_fp_use_i_until_s:nw
9786     \exp_after:wN 0
9787   \fi:
9788 }
```

(End definition for _fp_exponent:w)

_fp_neg_sign:N When appearing in an integer expression or after _int_value:w, this expands to the sign opposite to #1, namely 0 (positive) is turned to 2 (negative), 1 (nan) to 1, and 2 to 0.

```
9789 \cs_new:Npn \_fp_neg_sign:N #1
9790   { \_int_eval:w \c_two - #1 \_int_eval_end: }
(End definition for \_fp_neg_sign:N)
```

22.3 Overflow, underflow, and exact zero

`_fp_sanitize:Nw` Expects the sign and the exponent in some order, then the significand (which we don't touch). Outputs the corresponding floating point number, possibly underflowed to ± 0 or overflowed to $\pm\infty$. The functions `_fp_underflow:w` and `_fp_overflow:w` are defined in l3fp-traps.

```

9791 \cs_new:Npn \_fp_sanitize:Nw #1 #2;
9792 {
9793     \if_case:w \if_int_compare:w #2 > \c_fp_max_exponent_int \c_one \else:
9794         \if_int_compare:w #2 < - \c_fp_max_exponent_int \c_two \else:
9795             \if_meaning:w 1 #1 \c_three \else: \c_zero \fi: \fi: \fi:
9796             \or: \exp_after:wN \_fp_overflow:w
9797             \or: \exp_after:wN \_fp_underflow:w
9798             \or: \exp_after:wN \_fp_sanitize_zero:w
9799             \fi:
9800             \s_fp \_fp_chk:w 1 #1 {#2}
9801 }
9802 \cs_new:Npn \_fp_sanitize:wN #1; #2 { \_fp_sanitize:Nw #2 #1; }
9803 \cs_new:Npn \_fp_sanitize_zero:w \s_fp \_fp_chk:w #1 #2 #3; { \c_zero_fp }
(End definition for \_fp_sanitize:Nw and \_fp_sanitize:wN These functions are documented on page ??.)
```

22.4 Expanding after a floating point number

`_fp_exp_after_o:w` Places $\langle tokens \rangle$ (empty in the case of `_fp_exp_after_o:w`) between the $\langle floating\ point \rangle$ and the $\langle more\ tokens \rangle$, then hits those tokens with either o-expansion (one `\exp_after:wN`) or f-expansion, and leaves the floating point number unchanged.

We first distinguish normal floating points, which have a significand, from the much simpler special floating points.

```

9804 \cs_new:Npn \_fp_exp_after_o:w \s_fp \_fp_chk:w #1
9805 {
9806     \if_meaning:w 1 #1
9807         \exp_after:wN \_fp_exp_after_normal:nNNw
9808     \else:
9809         \exp_after:wN \_fp_exp_after_special:nNNw
9810         \fi:
9811         { }
9812         #1
9813     }
9814 \cs_new:Npn \_fp_exp_after_o:nw #1 \s_fp \_fp_chk:w #2
9815 {
9816     \if_meaning:w 1 #2
9817         \exp_after:wN \_fp_exp_after_normal:nNNw
9818     \else:
9819         \exp_after:wN \_fp_exp_after_special:nNNw
9820         \fi:
9821         { #1 }
9822         #2
9823 }
```

```

9824 \cs_new:Npn \__fp_exp_after_f:nw #1 \s_ fp \__fp_chk:w #2
9825 {
9826   \if_meaning:w 1 #2
9827     \exp_after:wN \__fp_exp_after_normal:nNNw
9828   \else:
9829     \exp_after:wN \__fp_exp_after_special:nNNw
9830   \fi:
9831   { \tex_roman numeral:D -'0 #1 }
9832   #2
9833 }

```

(End definition for `__fp_exp_after_o:w` This function is documented on page ??.)

`__fp_exp_after_special:nNNw`

Special floating point numbers are easy to jump over since they contain few tokens.

```

9834 \cs_new:Npn \__fp_exp_after_special:nNNw #1#2#3#4;
9835 {
9836   \exp_after:wN \s_ fp
9837   \exp_after:wN \__fp_chk:w
9838   \exp_after:wN #2
9839   \exp_after:wN #3
9840   \exp_after:wN #4
9841   \exp_after:wN ;
9842   #1
9843 }

```

(End definition for `__fp_exp_after_special:nNNw`)

`__fp_exp_after_normal:nNNw`

For normal floating point numbers, life is slightly harder, since we have many tokens to jump over. Here it would be slightly better if the digits were not braced but instead were delimited arguments (for instance delimited by ,). That may be changed some day.

```

9844 \cs_new:Npn \__fp_exp_after_normal:nNNw #1 1 #2 #3 #4#5#6#7;
9845 {
9846   \exp_after:wN \__fp_exp_after_normal:Nwwww
9847   \exp_after:wN #
9848   \__int_value:w #3 \exp_after:wN ;
9849   \__int_value:w 1 #4 \exp_after:wN ;
9850   \__int_value:w 1 #5 \exp_after:wN ;
9851   \__int_value:w 1 #6 \exp_after:wN ;
9852   \__int_value:w 1 #7 \exp_after:wN ; #1
9853 }
9854 \cs_new:Npn \__fp_exp_after_normal:Nwwww
9855   #1 #2; 1 #3 ; 1 #4 ; 1 #5 ; 1 #6 ;
9856   { \s_ fp \__fp_chk:w 1 #1 {#2} {#3} {#4} {#5} {#6} ; }

```

(End definition for `__fp_exp_after_normal:nNNw`)

`__fp_exp_after_array_f:w`

`__fp_exp_after_stop_f:nw`

```

9857 \cs_new:Npn \__fp_exp_after_array_f:w #1
9858 {
9859   \cs:w __fp_exp_after \__fp_type_from_scan:N #1 _f:nw \cs_end:
9860   { \__fp_exp_after_array_f:w }
9861   #1

```

```

9862   }
9863 \cs_new_eq:NN \__fp_exp_after_stop_f:nw \use_none:nn
(End definition for \__fp_exp_after_array_f:w This function is documented on page ??.)
```

22.5 Packing digits

When a positive integer #1 is known to be less than 10^8 , the following trick will split it into two blocks of 4 digits, padding with zeros on the left.

```
\cs_new:Npn \pack:NNNNw #1 #2#3#4#5 #6; { {#2#3#4#5} {#6} }
\exp_after:wN \pack:NNNNw
\int_use:N \__int_eval:w 1 0000 0000 + #1 ;
```

The idea is that adding 10^8 to the number ensures that it has exactly 9 digits, and can then easily find which digits correspond to what position in the number. Of course, this can be modified for any number of digits less or equal to 9 (we are limited by TeX's integers). This method is very heavily relied upon in *l3fp-basics*.

More specifically, the auxiliary inserts `+ #1#2#3#4#5 ; {#6}`, which allows us to compute several blocks of 4 digits in a nested manner, performing carries on the fly. Say we want to compute 12345×66778899 . With simplified names, we would do

```
\exp_after:wN \post_processing:w
\int_use:N \__int_eval:w - 5 0000
\exp_after:wN \pack:NNNNw
\int_use:N \__int_eval:w 4 9995 0000
+ 12345 * 6677
\exp_after:wN \pack:NNNNw
\int_use:N \__int_eval:w 5 0000 0000
+ 12345 * 8899 ;
```

The `\exp_after:wN` triggers `\int_use:N __int_eval:w`, which starts a first computation, whose initial value is -50000 (the “leading shift”). In that computation appears an `\exp_after:wN`, which triggers the nested computation `\int_use:N __int_eval:w` with starting value 499950000 (the “middle shift”). That, in turn, expands `\exp_-after:wN` which triggers the third computation. The third computation's value is $500000000 + 12345 \times 8899$, which has 9 digits. Adding $5 \cdot 10^8$ to the product allowed us to know how many digits to expect as long as the numbers to multiply are not too big; it will also work to some extent with negative results. The `pack` function puts the last 4 of those 9 digits into a brace group, moves the semi-colon delimiter, and inserts a `+`, which combines the carry with the previous computation. The shifts nicely combine into $500000000/10^4 + 499950000 = 500000000$. As long as the operands are in some range, the result of this second computation will have 9 digits. The corresponding `pack` function, expanded after the result is computed, braces the last 4 digits, and leaves `+ {5 digits}` for the initial computation. The “leading shift” cancels the combination of the other shifts, and the `\post_processing:w` takes care of packing the last few digits.

Admittedly, this is quite intricate. It is probably the key in making *l3fp* as fast as other pure TeX floating point units despite its increased precision. In fact, this is used so

much that we provide different sets of packing functions and shifts, depending on ranges of input.

```
\_\_fp\_pack:NNNNNw
\_\_fp\_pack:NNNNNwn
\c\_fp\_trailing\_shift\_int
```

```
\c\_fp\_middle\_shift\_int
\c\_fp\_leading\_shift\_int
```

This set of shifts allows for computations involving results in the range $[-4 \cdot 10^8, 5 \cdot 10^8 - 1]$. Shifted values all have exactly 9 digits. The `__fp_pack:NNNNNwn` function brings a braced *continuation* up through the levels of expansion.

```
9864 \int\_const:Nn \c\_fp\_leading\_shift\_int { - 5 0000 }
9865 \int\_const:Nn \c\_fp\_middle\_shift\_int { 5 0000 * 9999 }
9866 \int\_const:Nn \c\_fp\_trailing\_shift\_int { 5 0000 * 10000 }
9867 \cs\_new:Npn \_\_fp\_pack:NNNNNw #1 #2#3#4#5 #6; { + #1#2#3#4#5 ; {#6} }
9868 \cs\_new:Npn \_\_fp\_pack:NNNNNwn #1 #2#3#4#5 #6; #7
9869 { + #1#2#3#4#5 ; {#7} {#6} }
```

(End definition for `__fp_pack:NNNNNw` and `__fp_pack:NNNNNwn` These functions are documented on page ??.)

This set of shifts allows for computations involving results in the range $[-5 \cdot 10^8, 6 \cdot 10^8 - 1]$ (actually a bit more). Shifted values all have exactly 10 digits. Note that the upper bound is due to TeX's limit of $2^{31} - 1$ on integers. The shifts are chosen to be roughly the mid-point of 10^9 and 2^{31} , the two bounds on 10-digit integers in TeX.

```
9870 \int\_const:Nn \c\_fp\_big\_leading\_shift\_int { - 15 2374 }
9871 \int\_const:Nn \c\_fp\_big\_middle\_shift\_int { 15 2374 * 9999 }
9872 \int\_const:Nn \c\_fp\_big\_trailing\_shift\_int { 15 2374 * 10000 }
9873 \cs\_new:Npn \_\_fp\_pack\_big:NNNNNNw #1#2 #3#4#5#6 #7;
9874 { + #1#2#3#4#5#6 ; {#7} }
9875 \cs\_new:Npn \_\_fp\_pack\_big:NNNNNNwn #1#2 #3#4#5#6 #7; #8
9876 { + #1#2#3#4#5#6 ; {#8} {#7} }
```

(End definition for `__fp_pack_big:NNNNNNw` and `__fp_pack_big:NNNNNNwn` These functions are documented on page ??.)

```
\_\_fp\_pack\_Bigg:NNNNNNw
```

```
\c\_fp\_Bigg\_trailing\_shift\_int
```

```
\c\_fp\_Bigg\_middle\_shift\_int
```

```
\c\_fp\_Bigg\_leading\_shift\_int
```

This set of shifts allows for computations involving results in the range $[-1 \cdot 10^9, 147483647]$; the end-point is $2^{31} - 1 - 2 \cdot 10^9 \simeq 1.47 \cdot 10^8$. Shifted values all have exactly 10 digits.

```
9877 \int\_const:Nn \c\_fp\_Bigg\_leading\_shift\_int { - 20 0000 }
9878 \int\_const:Nn \c\_fp\_Bigg\_middle\_shift\_int { 20 0000 * 9999 }
9879 \int\_const:Nn \c\_fp\_Bigg\_trailing\_shift\_int { 20 0000 * 10000 }
9880 \cs\_new:Npn \_\_fp\_pack\_Bigg:NNNNNNw #1#2 #3#4#5#6 #7;
9881 { + #1#2#3#4#5#6 ; {#7} }
```

(End definition for `__fp_pack_Bigg:NNNNNNw` This function is documented on page ??.)

```
\_\_fp\_pack\_twice\_four:wNNNNNNNN
```

Grabs two sets of 4 digits and places them before the semi-colon delimiter. Putting several copies of this function before a semicolon will pack more digits since each will take the digits packed by the others in its first argument.

```
9882 \cs\_new:Npn \_\_fp\_pack\_twice\_four:wNNNNNNNN #1; #2#3#4#5 #6#7#8#9
9883 { #1 {#2#3#4#5} {#6#7#8#9} ; }
```

(End definition for `__fp_pack_twice_four:wNNNNNNNN`)

_fp_pack_eight:wNNNNNNNN Grabs one set of 8 digits and places them before the semi-colon delimiter as a single group. Putting several copies of this function before a semicolon will pack more digits since each will take the digits packed by the others in its first argument.

```
9884 \cs_new:Npn \_fp_pack_eight:wNNNNNNNN #1; #2#3#4#5 #6#7#8#9
9885 { #1 {#2#3#4#5#6#7#8#9} ; }
(End definition for \_fp_pack_eight:wNNNNNNNN)
```

22.6 Decimate (dividing by a power of 10)

_fp_decimate:nNnnn Each $\langle X_i \rangle$ consists in 4 digits exactly, and $1000 \leq \langle X_1 \rangle < 9999$. The first argument determines by how much we shift the digits. $\langle f_1 \rangle$ is called as follows: where $0 \leq \langle X'_1 \rangle < 10^8 - 1$ are 8 digit numbers, forming the truncation of our number. In other words,

$$\left(\sum_{i=1}^4 \langle X_i \rangle \cdot 10^{-4i} \cdot 10^{-\langle shift \rangle} - \langle X'_1 \rangle \cdot 10^{-8} + \langle X'_2 \rangle \cdot 10^{-16} \right) \in [0, 10^{-16}).$$

To round properly later, we need to remember some information about the difference. The $\langle rounding \rangle$ digit is 0 if and only if the difference is exactly 0, and 5 if and only if the difference is exactly $0.5 \cdot 10^{-16}$. Otherwise, it is the (non-0, non-5) digit closest to 10^{17} times the difference. In particular, if the shift is 17 or more, all the digits are dropped, $\langle rounding \rangle$ is 1 (not 0), and $\langle X'_1 \rangle$ $\langle X'_2 \rangle$ are both zero.

If the shift is 1, the $\langle rounding \rangle$ digit is simply the only digit that was pushed out of the brace groups (this is important for subtraction). It would be more natural for the $\langle rounding \rangle$ digit to be placed after the $\langle X_i \rangle$, but the choice we make involves less reshuffling.

Note that this function fails for negative $\langle shift \rangle$.

```
9886 \cs_new:Npn \_fp_decimate:nNnnn #1
9887 {
9888   \cs:w
9889     __fp_decimate_
9890     \if_int_compare:w \_int_eval:w #1 > \c_sixteen
9891       tiny
9892     \else:
9893       \tex_roman numeral:D \_int_eval:w #1
9894     \fi:
9895     :Nnnnn
9896   \cs_end:
9897 }
```

Each of the auxiliaries see the function $\langle f_1 \rangle$, followed by 4 blocks of 4 digits.
(End definition for _fp_decimate:nNnnn)

If the $\langle shift \rangle$ is zero, or too big, life is very easy.

```
9898 \cs_new:Npn \_fp_decimate_:Nnnnn #1 #2#3#4#5
9899 { #1 0 {#2#3} {#4#5} ; }
9900 \cs_new:Npn \_fp_decimate_tiny:Nnnnn #1 #2#3#4#5
9901 { #1 1 { 0000 0000 } { 0000 0000 } 0 #2#3#4#5 ; }
(End definition for \_fp_decimate_:Nnnnn and \_fp_decimate_tiny:Nnnnn)
```

```

\__fp_decimate_i:Nnnnn
\__fp_decimate_ii:Nnnnn
\__fp_decimate_iii:Nnnnn
\__fp_decimate_iv:Nnnnn
\__fp_decimate_v:Nnnnn
\__fp_decimate_vi:Nnnnn
\__fp_decimate_vii:Nnnnn
\__fp_decimate_viii:Nnnnn
\__fp_decimate_ix:Nnnnn
\__fp_decimate_x:Nnnnn
\__fp_decimate_xi:Nnnnn
\__fp_decimate_xii:Nnnnn
\__fp_decimate_xiii:Nnnnn
\__fp_decimate_xiv:Nnnnn
\__fp_decimate_xv:Nnnnn
\__fp_decimate_xvi:Nnnnn

```

Shifting happens in two steps: compute the $\langle \text{rounding} \rangle$ digit, and repack digits into two blocks of 8. The sixteen functions are very similar, and defined through `__fp_tmp:w`. The arguments are as follows: #1 indicates which function is being defined; after one step of expansion, #2 yields the “extra digits” which are then converted by `__fp_round_digit:Nw` to the $\langle \text{rounding} \rangle$ digit. This triggers the f-expansion of `__fp_decimate_pack:nnnnnnnnnnnw`⁶, responsible for building two blocks of 8 digits, and removing the rest. For this to work, #3 alternates between braced and unbraced blocks of 4 digits, in such a way that the 5 first and 5 next token groups yield the correct blocks of 8 digits.

```

9902 \cs_new:Npn \__fp_tmp:w #1 #2 #3
9903 {
9904   \cs_new:cpx { __fp_decimate_ #1 :Nnnnn } ##1 ##2##3##4##5
9905   {
9906     \exp_after:wN ##1
9907     \int_value:w
9908     \exp_after:wN \__fp_round_digit:Nw #2 ;
9909     \__fp_decimate_pack:nnnnnnnnnnnw #3 ;
9910   }
9911 }
9912 \__fp_tmp:w {i} {\use_none:nnn} #50} { 0{#2}#3{#4}#5
9913 \__fp_tmp:w {ii} {\use_none:nn} #5 } { 00{#2}#3{#4}#5
9914 \__fp_tmp:w {iii} {\use_none:n} #5 } { 000{#2}#3{#4}#5
9915 \__fp_tmp:w {iv} { } #5 } { {0000}#2{#3}#4 #5
9916 \__fp_tmp:w {v} {\use_none:nnn} #4#5 } { 0{0000}#2{#3}#4 #5
9917 \__fp_tmp:w {vi} {\use_none:nn} #4#5 } { 00{0000}#2{#3}#4 #5
9918 \__fp_tmp:w {vii} {\use_none:n} #4#5 } { 000{0000}#2{#3}#4 #5
9919 \__fp_tmp:w {viii}{ } #4#5 } { {0000}0000{#2}#3 #4 #5
9920 \__fp_tmp:w {ix} {\use_none:nnn} #3#4+##5} { 0{0000}0000{#2}#3 #4 #5
9921 \__fp_tmp:w {x} {\use_none:nn} #3#4+##5} { 00{0000}0000{#2}#3 #4 #5
9922 \__fp_tmp:w {xi} {\use_none:n} #3#4+##5} { 000{0000}0000{#2}#3 #4 #5
9923 \__fp_tmp:w {xii} { } #3#4+##5} { {0000}00000000{#2}#3 #4 #5
9924 \__fp_tmp:w {xiii}{\use_none:nnn#2#3+##4#5} { 0{0000}00000000{#2}#3 #4 #5
9925 \__fp_tmp:w {xiv} {\use_none:nn} #2#3+##4#5} { 00{0000}00000000{#2}#3 #4 #5
9926 \__fp_tmp:w {xv} {\use_none:n} #2#3+##4#5} { 000{0000}00000000{#2}#3 #4 #5
9927 \__fp_tmp:w {xvi} { } #2#3+##4#5} { {{0000}000000000000{#2}#3 #4 #5 }

(End definition for \__fp_decimate_i:Nnnnn and others.)

```

`__fp_round_digit:Nw` will receive the “extra digits” as its argument, and its expansion is triggered by `\int_value:w`. If the first digit is neither 0 nor 5, then it is the $\langle \text{rounding} \rangle$ digit. Otherwise, if the remaining digits are not all zero, we need to add 1 to that leading digit to get the rounding digit. Some caution is required, though, because there may be more than 10 “extra digits”, and this may overflow TeX’s integers. Instead of feeding the digits directly to `__fp_round_digit:Nw`, they come split into several blocks, separated by +. Hence the first `\int_eval:w` here.

The computation of the $\langle \text{rounding} \rangle$ digit leaves an unfinished `\int_value:w`, which expands the following functions. This allows us to repack nicely the digits we keep. Those digits come as an alternation of unbraced and braced blocks of 4 digits, such that

⁶No, the argument spec is not a mistake: the function calls an auxiliary to do half of the job.

the first 5 groups of token consist in 4 single digits, and one brace group (in some order), and the next 5 have the same structure. This is followed by some digits and a semicolon.

```

9928 \cs_new:Npn \_fp_decimate_pack:nnnnnnnnnw #1#2#3#4#5
9929   { \_fp_decimate_pack_ii:nnnnnw { #1#2#3#4#5 } }
9930 \cs_new:Npn \_fp_decimate_pack_ii:nnnnnw #1 #2#3#4#5#6
9931   { {#1} {#2#3#4#5#6} }
(End definition for \_fp_round_digit:Nw and \_fp_decimate_pack:nnnnnnnnnw)

```

22.7 Functions for use within primitive conditional branches

The functions described in this section are not pretty and can easily be misused. When correctly used, each of them removes one `\fi:` as part of its parameter text, and puts one back as part of its replacement text.

Many computation functions in l3fp must perform tests on the type of floating points that they receive. This is often done in an `\if_case:w` statement or another conditional statement, and only a few cases lead to actual computations: most of the special cases are treated using a few standard functions which we define now. A typical use context for those functions would be In this example, the case 0 will return the floating point `fp var`, expanding once after that floating point. Case 1 will do `some computation` using the `floating point` (presumably compute the operation requested by the user in that non-trivial case). Case 2 will return the `floating point` without modifying it, removing the `junk` and expanding once after. Case 3 will close the conditional, remove the `junk` and the `floating point`, and expand `something` next. In other cases, the “`junk`” is expanded, performing some other operation on the `floating point`. We provide similar functions with two trailing `floating points`.

`_fp_case_use:nw` This function ends a TeX conditional, removes junk until the next floating point, and places its first argument before that floating point, to perform some operation on the floating point.

```

9932 \cs_new:Npn \_fp_case_use:nw #1#2 \fi: #3 \s_fp { \fi: #1 \s_fp }
(End definition for \_fp_case_use:nw)

```

`_fp_case_return:nw` This function ends a TeX conditional, removes junk and a floating point, and places its first argument in the input stream. A quirk is that we don't define this function requiring a floating point to follow, simply anything ending in a semicolon. This, in turn, means that the `junk` may not contain semicolons.

```

9933 \cs_new:Npn \_fp_case_return:nw #1#2 \fi: #3 ; { \fi: #1 }
(End definition for \_fp_case_return:nw)

```

`_fp_case_return_o:Nw` This function ends a TeX conditional, removes junk and a floating point, and returns its first argument (an `fp var`) then expands once after it.

```

9934 \cs_new:Npn \_fp_case_return_o:Nw #1#2 \fi: #3 \s_fp #4 ;
9935   { \fi: \exp_after:wN #1 }
(End definition for \_fp_case_return_o:Nw)

```

__fp_case_return_same_o:w This function ends a TeX conditional, removes junk, and returns the following floating point, expanding once after it.

```
9936 \cs_new:Npn \_\_fp_case_return_same_o:w #1 \fi: #2 \s_fp
9937   { \fi: \_\_fp_exp_after_o:w \s_fp }
(End definition for \_\_fp_case_return_same_o:w)
```

__fp_case_return_o:Nww Same as __fp_case_return_o:Nw but with two trailing floating points.

```
9938 \cs_new:Npn \_\_fp_case_return_o:Nww #1#2 \fi: #3 \s_fp #4 ; #5 ;
9939   { \fi: \exp_after:wN #1 }
(End definition for \_\_fp_case_return_o:Nww)
```

__fp_case_return_i_o:ww __fp_case_return_ii_o:ww Similar to __fp_case_return_same_o:w, but this returns the first or second of two trailing floating point numbers, expanding once after the result.

```
9940 \cs_new:Npn \_\_fp_case_return_i_o:ww #1 \fi: #2 \s_fp #3 ; \s_fp #4 ;
9941   { \fi: \_\_fp_exp_after_o:w \s_fp #3 ; }
9942 \cs_new:Npn \_\_fp_case_return_ii_o:ww #1 \fi: #2 \s_fp #3 ;
9943   { \fi: \_\_fp_exp_after_o:w }
(End definition for \_\_fp_case_return_i_o:ww and \_\_fp_case_return_ii_o:ww)
```

22.8 Small integer floating points

This function tests if its floating point argument is an integer in the range $[-99999999, 99999999]$. If it is, the result of the conversion is fed as a braced argument to the *true code*. Otherwise, the *false code* is performed. First filter special cases: neither `nan` nor infinities are integers. Normal numbers with a non-positive exponent are never integers. When the exponent is greater than 8, the number is too large for the range. Otherwise, decimate, and test the digits after the decimal separator. The `\use_iii:nnn` remove a trailing ; and the true branch, leaving only the false branch. The `\int_value:w` appearing in the case where the normal floating point is an integer takes care of expanding all the conditionals until the trailing ;. That integer is fed to `__fp_small_int_true:wTF` which places it as a braced argument of the true branch. The `\use_i:nn` in `__fp_small_int_test:NnnwNTF` removes the top-level `\else:` coming from `__fp_small_int_normal:NnwTF`, hence will call the `\use_iii:nnn` which follows, taking the false branch.

```
9944 \cs_new:Npn \_\_fp_small_int:wTF \s_fp \_\_fp_chk:w #1
9945   {
9946     \if_case:w #1 \exp_stop_f:
9947       \_\_fp_case_return:nw { \_\_fp_small_int_true:wTF 0 ; }
9948     \or: \exp_after:wN \_\_fp_small_int_normal:NnwTF
9949     \else: \_\_fp_case_return:nw \use_ii:nn
9950     \fi:
9951   }
9952 \cs_new:Npn \_\_fp_small_int_true:wTF #1; #2#3 { #2 {#1} }
9953 \cs_new:Npn \_\_fp_small_int_normal:NnwTF #1#2#3;
9954   {
9955     \if_int_compare:w #2 > \c_zero
9956       \if_int_compare:w #2 > \c_eight
9957         \exp_after:wN \exp_after:wN
```

```

9958   \exp_after:wN \use_iii:nnn
9959   \else:
9960     \fp_decimate:nNnnn { \c_sixteen - #2 }
9961       \fp_small_int_test:NnnwNTF
9962         #3 #1
9963       \fi:
9964   \else:
9965     \exp_after:wN \use_iii:nnn
9966   \fi:
9967   ;
9968 }
9969 \cs_new:Npn \fp_small_int_test:NnnwNTF #1#2#3#4; #5
9970 {
9971   \if_meaning:w 0 #1
9972     \exp_after:wN \fp_small_int_true:wTF
9973       \int_value:w \if_meaning:w 2 #5 - \fi: #3
9974   \else:
9975     \exp_after:wN \use_i:nn
9976   \fi:
9977 }
(End definition for \fp_small_int:wTF This function is documented on page ??.)
```

22.9 Length of a floating point array

`\fp_array_count:n`
`\fp_array_count_loop:Nw`

Count the number of items in an array of floating points. The technique is very similar to `\tl_count:n`, but with the loop built-in. Checking for the end of the loop is done with the `\use_none:n #1` construction.

```

9978 \cs_new:Npn \fp_array_count:n #1
9979 {
9980   \int_use:N \int_eval:w \c_zero
9981     \fp_array_count_loop:Nw #1 { ? \prg_break: } ;
9982     \prg_break_point:
9983   \int_eval_end:
9984 }
9985 \cs_new:Npn \fp_array_count_loop:Nw #1#2;
9986   { \use_none:n #1 + \c_one \fp_array_count_loop:Nw }
```

(End definition for `\fp_array_count:n` This function is documented on page ??.)

22.10 x-like expansion expandably

`\fp_expand:n`
`\fp_expand_loop:nwnN`

This expandable function behaves in a way somewhat similar to `\use:x`, but much less robust. The argument is f-expanded, then the leading item (often a single character token) is moved to a storage area after `\s_fp_mark`, and f-expansion is applied again, repeating until the argument is empty. The result built one piece at a time is then inserted in the input stream. Note that spaces are ignored by this procedure, unless surrounded with braces. Multiple tokens which do not need expansion can be inserted within braces.

```
9987 \cs_new:Npn \fp_expand:n #1
```

```

9988  {
9989    \__fp_expand_loop:nwnN { }
9990    #1 \prg_do_nothing:
9991    \s__fp_mark { } \__fp_expand_loop:nwnN
9992    \s__fp_mark { } \__fp_use_i_until_s:nw ;
9993  }
9994 \cs_new:Npn \__fp_expand_loop:nwnN #1#2 \s__fp_mark #3 #4
9995  {
9996    \exp_after:wn #4 \tex_roman numeral:D -`0
9997    #2
9998    \s__fp_mark { #3 #1 } #4
9999  }

```

(End definition for `__fp_expand:n` This function is documented on page ??.)

22.11 Messages

Using a floating point directly is an error.

```

10000 \__msg_kernel_new:nnnn { kernel } { misused-fp }
10001  { A~floating~point~with~value~'#1'~was~misused. }
10002  {
10003    To~obtain~the~value~of~a~floating~point~variable,~use~
10004    '\token_to_str:N \fp_to_decimal:N',~
10005    '\token_to_str:N \fp_to_scientific:N',~or~other~
10006    conversion~functions.
10007  }
10008 </initex | package>

```

23 l3fp-traps Implementation

```

10009 <*initex | package>
10010 <@=fp>

```

Exceptions should be accessed by an n-type argument, among

- `invalid_operation`
- `division_by_zero`
- `overflow`
- `underflow`
- `inexact` (actually never used).

23.1 Flags

`\fp_flag_off:n` Function to turn a flag off. Simply undefine it.

```
10011 \cs_new_protected:Npn \fp_flag_off:n #1
10012   { \cs_set_eq:cN { l_fp_#1_flag_token } \c_undefined:D }
(End definition for \fp_flag_off:n This function is documented on page 171.)
```

`\fp_flag_on:n` Function to turn a flag on expandably: use TeX's automatic assignment to `\scan_stop:`.

```
10013 \cs_new:Npn \fp_flag_on:n #1
10014   { \exp_args:Nc \use_none:n { l_fp_#1_flag_token } }
(End definition for \fp_flag_on:n This function is documented on page 171.)
```

`\fp_if_flag_on_p:n` Returns true if the flag is on, false otherwise.

`\fp_if_flag_on:nTF`

```
10015 \prg_new_conditional:Npnn \fp_if_flag_on:n #1 { p , T , F , TF }
10016   {
10017     \ifcsexist:w l_fp_#1_flag_token \cs_end:
10018       \prg_return_true:
10019     \else:
10020       \prg_return_false:
10021     \fi:
10022   }
(End definition for \fp_if_flag_on:n These functions are documented on page 171.)
```

The IEEE standard defines five exceptions. We currently don't support the "inexact" exception.

```
10023 \cs_new_eq:NN \l_fp_invalid_operation_flag_token \c_undefined:D
10024 \cs_new_eq:NN \l_fp_division_by_zero_flag_token \c_undefined:D
10025 \cs_new_eq:NN \l_fp_overflow_flag_token \c_undefined:D
10026 \cs_new_eq:NN \l_fp_underflow_flag_token \c_undefined:D
(End definition for \l_fp_invalid_operation_flag_token and others.)
```

23.2 Traps

Exceptions can be trapped to obtain custom behaviour. When an invalid operation or a division by zero is trapped, the trap receives as arguments the result as an N -type floating point number, the function name (multiple letters for prefix operations, or a single symbol for infix operations), and the operand(s). When an overflow or underflow is trapped, the trap receives the resulting overly large or small floating point number if it is not too big, otherwise it receives $+\infty$. Currently, the inexact exception is entirely ignored.

The behaviour when an exception occurs is controlled by the definitions of the functions

- `__fp_invalid_operation:nnw,`
- `__fp_invalid_operation_o:Nww,`
- `__fp_invalid_operation_tl_o:nf,`

- `_fp_division_by_zero_o:Nnw`,
- `_fp_division_by_zero_o>NNww`,
- `_fp_overflow:w`,
- `_fp_underflow:w`.

Rather than changing them directly, we provide a user interface as `\fp_trap:nn` $\{\langle\text{exception}\rangle\} \{\langle\text{way of trapping}\rangle\}$, where the $\langle\text{way of trapping}\rangle$ is one of `error`, `flag`, or `none`.

We also provide `_fp_invalid_operation_o:nw`, defined in terms of `_fp_invalid_operation:nnw`.

```
\fp_trap:nn
10027 \cs_new_protected:Npn \fp_trap:nn #1#2
10028 {
10029   \cs_if_exist_use:cF { \_fp_trap:#1_set:#2: }
10030   {
10031     \clist_if_in:nnTF
10032       { invalid_operation , division_by_zero , overflow , underflow }
10033       {#1}
10034       {
10035         \_msg_kernel_error:nnxx { kernel }
10036         { unknown-fpu-trap-type } {#1} {#2}
10037       }
10038       { \_msg_kernel_error:nnx { kernel } { unknown-fpu-exception } {#1} }
10039     }
10040   }
10041 }
```

(End definition for `\fp_trap:nn` This function is documented on page 171.)

`_fp_trap_invalid_operation_set_error`:
`_fp_trap_invalid_operation_set_flag`:
`_fp_trap_invalid_operation_set_none`:

```
\_fp_trap_invalid_operation_set:N
10041 \cs_new_protected_nopar:Npn \_fp_trap_invalid_operation_set_error:
10042   { \_fp_trap_invalid_operation_set:N \prg_do_nothing: }
10043 \cs_new_protected_nopar:Npn \_fp_trap_invalid_operation_set_flag:
10044   { \_fp_trap_invalid_operation_set:N \use_none:nnnnn }
10045 \cs_new_protected_nopar:Npn \_fp_trap_invalid_operation_set_none:
10046   { \_fp_trap_invalid_operation_set:N \use_none:nnnnnnn }
10047 \cs_new_protected:Npn \_fp_trap_invalid_operation_set:N #1
10048   {
10049     \exp_args:Nno \use:n
10050     { \cs_set:Npn \_fp_invalid_operation:nnw ##1##2##3; }
10051   {
10052     #1
10053     \_fp_error:nfn { invalid } {##2} { \fp_to_tl:n { ##3; } } { }
10054     \fp_flag_on:n { invalid_operation }
10055     ##1
10056   }
```

```

10057 \exp_args:Nno \use:n
10058   { \cs_set:Npn \_fp_invalid_operation_o:Nww ##1##2; ##3; }
10059   {
10060     #1
10061     \_fp_error:nffn { invalid-ii }
10062       { \fp_to_tl:n { ##2; } } { \fp_to_tl:n { ##3; } } {##1}
10063     \fp_flag_on:n { invalid_operation }
10064     \exp_after:wN \c_nan_fp
10065   }
10066 \exp_args:Nno \use:n
10067   { \cs_set:Npn \_fp_invalid_operation_tl_o:nf ##1##2 }
10068   {
10069     #1
10070     \_fp_error:nfn { invalid } {##1} {##2} { }
10071     \fp_flag_on:n { invalid_operation }
10072     \exp_after:wN \c_nan_fp
10073   }
10074 }
```

(End definition for `_fp_trap_invalid_operation_set_error: and others.`)

`_fp_trap_division_by_zero_set_error:`
`_fp_trap_division_by_zero_set_flag:`
`_fp_trap_division_by_zero_set_none:`
`_fp_trap_division_by_zero_set:N`

```

10075 \cs_new_protected_nopar:Npn \_fp_trap_division_by_zero_set_error:
10076   { \_fp_trap_division_by_zero_set:N \prg_do_nothing: }
10077 \cs_new_protected_nopar:Npn \_fp_trap_division_by_zero_set_flag:
10078   { \_fp_trap_division_by_zero_set:N \use_none:nnnn }
10079 \cs_new_protected_nopar:Npn \_fp_trap_division_by_zero_set_none:
10080   { \_fp_trap_division_by_zero_set:N \use_none:nnnnnn }
10081 \cs_new_protected:Npn \_fp_trap_division_by_zero_set:N #1
10082   {
10083     \exp_args:Nno \use:n
10084       { \cs_set:Npn \_fp_division_by_zero_o:Nnw ##1##2##3; }
10085     {
10086       #1
10087       \_fp_error:nfn { zero-div } {##2} { \fp_to_tl:n { ##3; } } { }
10088       \fp_flag_on:n { division_by_zero }
10089       \exp_after:wN ##1
10090     }
10091   \exp_args:Nno \use:n
10092     { \cs_set:Npn \_fp_division_by_zero_o:NNww ##1##2##3; ##4; }
10093     {
10094       #1
10095       \_fp_error:nffn { zero-div-ii }
10096         { \fp_to_tl:n { ##3; } } { \fp_to_tl:n { ##4; } } {##2}
10097       \fp_flag_on:n { division_by_zero }
10098       \exp_after:wN ##1
10099     }
```

```

10100    }
(End definition for \__fp_trap_division_by_zero_set_error: and others.)
```

```

\__fp_trap_overflow_set_error:
\__fp_trap_overflow_set_flag:
\__fp_trap_overflow_set_none:
\__fp_trap_overflow_set:N
\__fp_trap_underflow_set_error:
\__fp_trap_underflow_set_flag:
\__fp_trap_underflow_set_none:
\__fp_trap_underflow_set:N
\__fp_trap_overflow_set:NnNn
```

Just as for invalid operations and division by zero, the three different behaviours are obtained by feeding \prg_do_nothing:, \use_none:nnnnn or \use_none:nnnnnnn to an auxiliary, with a further auxiliary common to overflow and underflow functions. In most cases, the argument of the __fp_overflow:w and __fp_underflow:w functions will be an (almost) normal number (with an exponent outside the allowed range), and the error message thus displays that number together with the result to which it overflowed or underflowed. For extreme cases such as $10^{**} 1e9999$, the exponent would be too large for T_EX, and __fp_overflow:w receives $\pm\infty$ (__fp_underflow:w would receive ± 0); then we cannot do better than simply say an overflow or underflow occurred.

```

10101 \cs_new_protected_nopar:Npn \__fp_trap_overflow_set_error:
10102   { \__fp_trap_overflow_set:N \prg_do_nothing: }
10103 \cs_new_protected_nopar:Npn \__fp_trap_overflow_set_flag:
10104   { \__fp_trap_overflow_set:N \use_none:nnnnn }
10105 \cs_new_protected_nopar:Npn \__fp_trap_overflow_set_none:
10106   { \__fp_trap_overflow_set:N \use_none:nnnnnnn }
10107 \cs_new_protected:Npn \__fp_trap_overflow_set:N #1
10108   { \__fp_trap_overflow_set:NnNn #1 { overflow } \__fp_inf_fp:N { inf } }
10109 \cs_new_protected_nopar:Npn \__fp_trap_underflow_set_error:
10110   { \__fp_trap_underflow_set:N \prg_do_nothing: }
10111 \cs_new_protected_nopar:Npn \__fp_trap_underflow_set_flag:
10112   { \__fp_trap_underflow_set:N \use_none:nnnnn }
10113 \cs_new_protected_nopar:Npn \__fp_trap_underflow_set_none:
10114   { \__fp_trap_underflow_set:N \use_none:nnnnnnn }
10115 \cs_new_protected:Npn \__fp_trap_underflow_set:N #1
10116   { \__fp_trap_overflow_set:NnNn #1 { underflow } \__fp_zero_fp:N { 0 } }
10117 \cs_new_protected:Npn \__fp_trap_overflow_set:NnNn #1#2#3#4
10118   {
10119     \exp_args:Nno \use:n
10120       { \cs_set:cpn { __fp_ #2 :w } \s_fp \__fp_chk:w ##1##2##3; }
10121     {
10122       #1
10123       \__fp_error:nffn
10124         { flow \if_meaning:w 1 ##1 -to \fi: }
10125         { \fp_to_tl:n { \s_fp \__fp_chk:w ##1##2##3; } }
10126         { \token_if_eq_meaning:NNF 0 ##2 { - } #4 }
10127         {##2}
10128       \fp_flag_on:n {##2}
10129       #3 ##2
10130     }
10131   }
(End definition for \__fp_trap_overflow_set_error: and others. These functions are documented on page 171.)
```

```

\__fp_invalid_operation:nw
\__fp_invalid_operation_o:Nww
\__fp_invalid_operation_tlo:nf
\__fp_division_by_zero_o:Nnw
\__fp_division_by_zero_o:NNww
\__fp_overflow:w
\__fp_underflow:w
```

Initialize the two control sequences (to log properly their existence). Then set invalid operations to trigger an error, and division by zero, overflow, and underflow to act silently on their flag.

```

10132 \cs_new:Npn \__fp_invalid_operation:nw #1#2#3; { }
10133 \cs_new:Npn \__fp_invalid_operation_o:Nww #1#2; #3; { }
10134 \cs_new:Npn \__fp_invalid_operation_tl_o:nf #1 #2 { }
10135 \cs_new:Npn \__fp_division_by_zero_o:Nnw #1#2#3; { }
10136 \cs_new:Npn \__fp_division_by_zero_o:NNww #1#2#3; #4; { }
10137 \cs_new:Npn \__fp_overflow:w { }
10138 \cs_new:Npn \__fp_underflow:w { }
10139 \fp_trap:nn { invalid_operation } { error }
10140 \fp_trap:nn { division_by_zero } { flag }
10141 \fp_trap:nn { overflow } { flag }
10142 \fp_trap:nn { underflow } { flag }
(End definition for \__fp_invalid_operation:nw and others.)

```

`__fp_invalid_operation_o:nw` Convenient short-hands for returning `\c_nan_fp` for a unary or binary operation, and expanding after.

```

10143 \cs_new_nopar:Npn \__fp_invalid_operation_o:nw
  { \__fp_invalid_operation:nw { \exp_after:wN \c_nan_fp } }
(End definition for \__fp_invalid_operation_o:nw)

```

23.3 Errors

```

\__fp_error:nnnn
\__fp_error:nnfn
\__fp_error:nffn
10145 \cs_new:Npn \__fp_error:nnnn #1
10146   { \__msg_kernel_expandable_error:nnnnn { kernel } { fp - #1 } }
10147 \cs_generate_variant:Nn \__fp_error:nnnn { nnf, nff }
(End definition for \__fp_error:nnnn, \__fp_error:nnfn, and \__fp_error:nffn)

```

23.4 Messages

Some messages.

```

10148 \__msg_kernel_new:nnnn { kernel } { unknown-fpu-exception }
10149   { The~FPU~exception~'#1'~is~not~known:~that~trap~will~never~be~triggered. }
10150   {
10151     The~only~exceptions~to~which~traps~can~be~attached~are \\
10152     \iow_indent:n
10153     {
10154       * ~ invalid_operation \\
10155       * ~ division_by_zero \\
10156       * ~ overflow \\
10157       * ~ underflow
10158     }
10159   }
10160 \__msg_kernel_new:nnnn { kernel } { unknown-fpu-trap-type }
10161   { The~FPU~trap~type~'#2'~is~not~known. }
10162   {
10163     The~trap~type~must~be~one~of \\
10164     \iow_indent:n
10165     {

```

```

10166      * ~ error \\
10167      * ~ flag \\
10168      * ~ none
10169      }
10170  }
10171 \_\_msg_kernel_new:nnn { kernel } { fp-flow }
10172   { An ~ #3 ~ occurred. }
10173 \_\_msg_kernel_new:nnn { kernel } { fp-flow-to }
10174   { #1 ~ #3 ed ~ to ~ #2 . }
10175 \_\_msg_kernel_new:nnn { kernel } { fp-zero-div }
10176   { Division~by~zero~in~ #1 (#2) }
10177 \_\_msg_kernel_new:nnn { kernel } { fp-zero-div-ii }
10178   { Division~by~zero~in~ (#1) #3 (#2) }
10179 \_\_msg_kernel_new:nnn { kernel } { fp-invalid }
10180   { Invalid~operation~ #1 (#2) }
10181 \_\_msg_kernel_new:nnn { kernel } { fp-invalid-ii }
10182   { Invalid~operation~ (#1) #3 (#2) }
10183 </initex | package>

```

24 l3fp-round implementation

```

10184 <*initex | package>
10185 <@@=fp>

```

24.1 Rounding tools

Floating point operations often yield a result that cannot be exactly represented in a significand with 16 digits. In that case, we need to round the exact result to a representable number. The IEEE standard defines four rounding modes:

- Round to nearest: round to the representable floating point number whose absolute difference with the exact result is the smallest. If the exact result lies exactly at the mid-point between two consecutive representable floating point numbers, round to the floating point number whose last digit is even.
- Round towards negative infinity: round to the greatest floating point number not larger than the exact result.
- Round towards zero: round to a floating point number with the same sign as the exact result, with the largest absolute value not larger than the absolute value of the exact result.
- Round towards positive infinity: round to the least floating point number not smaller than the exact result.

This is not fully implemented in l3fp yet, and transcendental functions fall back on the “round to nearest” mode. All rounding for basic algebra is done through the functions defined in this module, which can be redefined to change their rounding behaviour (but there is not interface for that yet).

The rounding tools available in this module are many variations on a base function `_fp_round:NNN`, which expands to `\c_zero` or `\c_one` depending on whether the final result should be rounded up or down.

- `_fp_round:NNN <sign> <digit1> <digit2>` can expand to `\c_zero` or `\c_one`.
- `_fp_round_s:NNNw <sign> <digit1> <digit2> <more digits>`; can expand to `\c_zero` ; or `\c_one` ;.
- `_fp_round_neg:NNN <sign> <digit1> <digit2>` can expand to `\c_zero` or `\c_one`.

See implementation comments for details on the syntax.

```
\_fp_round:NNN
\fp_round_to_nearest:NNN
\fp_round_to_ninf:NNN
\fp_round_to_zero:NNN
\fp_round_to_pinf:NNN
```

If rounding the number $\langle \text{final sign} \rangle \langle \text{digit}_1 \rangle \langle \text{digit}_2 \rangle$ to an integer rounds it towards zero (truncates it), this function expands to `\c_zero`, and otherwise to `\c_one`. Typically used within the scope of an `\int_eval:w`, to add 1 if needed, and thereby round correctly. The result depends on the rounding mode.

It is very important that $\langle \text{final sign} \rangle$ be the final sign of the result. Otherwise, the result will be incorrect in the case of rounding towards $-\infty$ or towards $+\infty$. Also recall that $\langle \text{final sign} \rangle$ is 0 for positive, and 2 for negative.

By default, the functions below return `\c_zero`, but this is superseded by `_fp_round_return_one:`, which instead returns `\c_one`, expanding everything and removing `\c_zero` in the process. In the case of rounding towards $\pm\infty$ or towards 0, this is not really useful, but it prepares us for the “round to nearest, ties to even” mode.

The “round to nearest” mode is the default. If the $\langle \text{digit}_2 \rangle$ is larger than 5, then round up. If it is less than 5, round down. If it is exactly 5, then round such that $\langle \text{digit}_1 \rangle$ plus the result is even. In other words, round up if $\langle \text{digit}_1 \rangle$ is odd.

```
10186 \cs_new:Npn \fp_round_return_one:
10187   { \exp_after:wn \c_one \tex_roman numeral:D }
10188 \cs_new:Npn \fp_round_to_ninf:NNN #1 #2 #3
10189   {
10190     \if_meaning:w 2 #1
10191       \if_int_compare:w #3 > \c_zero
10192         \fp_round_return_one:
10193       \fi:
10194     \fi:
10195     \c_zero
10196   }
10197 \cs_new:Npn \fp_round_to_zero:NNN #1 #2 #3 { \c_zero }
10198 \cs_new:Npn \fp_round_to_pinf:NNN #1 #2 #3
10199   {
10200     \if_meaning:w 0 #1
10201       \if_int_compare:w #3 > \c_zero
10202         \fp_round_return_one:
10203       \fi:
10204     \fi:
10205     \c_zero
10206   }
10207 \cs_new:Npn \fp_round_to_nearest:NNN #1 #2 #3
```

```

10208 {
10209   \if_int_compare:w #3 > \c_five
10210     \_fp_round_return_one:
10211   \else:
10212     \if_meaning:w 5 #3
10213       \if_int_odd:w #2 \exp_stop_f:
10214         \_fp_round_return_one:
10215       \fi:
10216     \fi:
10217   \fi:
10218   \c_zero
10219 }
10220 \cs_new_eq:NN \_fp_round:NNN \_fp_round_to_nearest:NNN
(End definition for \_fp_round:NNN This function is documented on page ??.)
```

_fp_round_s:NNNw Similar to _fp_round:NNN, but with an extra semicolon, this function expands to \c_zero ; if rounding *<final sign>**<digit>*.*<more digits>* to an integer truncates, and to \c_one ; otherwise. The *<more digits>* part must be a digit, followed by something that does not overflow a \int_use:N _int_eval:w construction. The only relevant information about this piece is whether it is zero or not.

```

10221 \cs_new:Npn \_fp_round_s:NNNw #1 #2 #3 #4;
10222 {
10223   \exp_after:WN \_fp_round:NNN
10224   \exp_after:WN #1
10225   \exp_after:WN #2
10226   \int_use:N \_int_eval:w
10227     \if_int_odd:w 0 \if_meaning:w 0 #3 1 \fi:
10228       \if_meaning:w 5 #3 1 \fi:
10229       \exp_stop_f:
10230       \if_int_compare:w \_int_eval:w #4 > \c_zero
10231         1 +
10232       \fi:
10233     \fi:
10234     #3
10235   ;
10236 }
```

(End definition for _fp_round_s:NNNw)

_fp_round_digit:Nw This function should always be called within an _int_value:w or _int_eval:w expansion; it may add an extra _int_eval:w, which means that the integer or integer expression should not be ended with a synonym of \relax, but with a semi-colon for instance.

```

10237 \cs_new:Npn \_fp_round_digit:Nw #1 #2;
10238 {
10239   \if_int_odd:w \if_meaning:w 0 #1 \c_one \else:
10240     \if_meaning:w 5 #1 \c_one \else:
10241       \c_zero \fi: \fi:
10242   \if_int_compare:w \_int_eval:w #2 > \c_zero
10243     \_int_eval:w \c_one +
```

```

10244     \fi:
10245     \fi:
10246     #1
10247 }
(End definition for \__fp_round_digit:Nw)

```

This expands to `\c_zero` or `\c_one`. Consider a number of the form $\langle\text{final sign}\rangle.X\dots X\langle\text{digit}_1\rangle$ with exactly 15 (non-all-zero) digits before $\langle\text{digit}_1\rangle$, and subtract from it $\langle\text{final sign}\rangle.0\dots 0\langle\text{digit}_2\rangle$, where there are 16 zeros. If in the current rounding mode the result should be rounded down, then this function returns `\c_one`. Otherwise, *i.e.*, if the result is rounded back to the first operand, then this function returns `\c_zero`.

It turns out that this negative “round to nearest” is identical to the positive one. And this is the default mode.

```

10248 \cs_new:Npn \__fp_round_to_ninf_neg:NNN #1 #2 #3
10249 {
10250     \if_meaning:w 0 #1
10251         \if_int_compare:w #3 > \c_zero
10252             \__fp_round_return_one:
10253             \fi:
10254         \fi:
10255         \c_zero
10256     }
10257 \cs_new:Npn \__fp_round_to_zero_neg:NNN #1 #2 #3
10258 {
10259     \if_int_compare:w #3 > \c_zero
10260         \__fp_round_return_one:
10261         \fi:
10262         \c_zero
10263     }
10264 \cs_new:Npn \__fp_round_to_pinf_neg:NNN #1 #2 #3
10265 {
10266     \if_meaning:w 2 #1
10267         \if_int_compare:w #3 > \c_zero
10268             \__fp_round_return_one:
10269             \fi:
10270         \fi:
10271         \c_zero
10272     }
10273 \cs_new_eq:NN \__fp_round_to_nearest_neg:NNN \__fp_round_to_nearest:NNN
10274 \cs_new_eq:NN \__fp_round_neg:NNN \__fp_round_to_nearest_neg:NNN
(End definition for \__fp_round_neg:NNN This function is documented on page ??.)

```

24.2 The round function

```

\__fp_round:Nww
\__fp_round:Nwn
\__fp_round_normal:NwNnwNnw
\__fp_round_normal_ii:NnnwNnn
\__fp_round_pack:Nw
\__fp_round_normal_iii:NnnNnn
\__fp_round_normal_end:wwNnn
\__fp_round_special:NwwNnn
\__fp_round_special_aux:Nw

```

```

10278 {
10279     \__fp_invalid_operation_tl_o:nf
10280         { round } { \__fp_array_to_clist:n { #2; #3; } }
10281     }
10282 }
10283 \cs_new:Npn \__fp_round:Nwn #1 \s__fp \__fp_chk:w #2#3#4; #5
10284 {
10285     \if_meaning:w 1 #2
10286         \exp_after:wN \__fp_round_normal:NwNNnw
10287         \exp_after:wN #1
10288         \__int_value:w #5
10289     \else:
10290         \exp_after:wN \__fp_exp_after_o:w
10291     \fi:
10292     \s__fp \__fp_chk:w #2#3#4;
10293 }
10294 \cs_new:Npn \__fp_round_normal:NwNNnw #1#2 \s__fp \__fp_chk:w 1#3#4#5;
10295 {
10296     \__fp_decimate:nNnnnn { \c_sixteen - #4 - #2 }
10297         \__fp_round_normal_ii:NnnwNNnn #5 #1 #3 {#4} {#2}
10298 }
10299 \cs_new:Npn \__fp_round_normal_ii:NnnwNNnn #1#2#3#4; #5#6
10300 {
10301     \exp_after:wN \__fp_round_normal_iii>NNwNnn
10302     \int_use:N \__int_eval:w
10303         \if_int_compare:w #2 > \c_zero
10304             1 \__int_value:w #2
10305             \exp_after:wN \__fp_round_pack:Nw
10306             \int_use:N \__int_eval:w 1#3 +
10307         \else:
10308             \if_int_compare:w #3 > \c_zero
10309                 1 \__int_value:w #3 +
10310             \fi:
10311         \fi:
10312         \exp_after:wN #5
10313         \exp_after:wN #6
10314         \use_none:nnnnnnn #3
10315         #1
10316         \__int_eval_end:
10317         0000 0000 0000 0000 ; #6
10318 }
10319 \cs_new:Npn \__fp_round_pack:Nw #1
10320     { \if_meaning:w 2 #1 + \c_one \fi: \__int_eval_end: }
10321 \cs_new:Npn \__fp_round_normal_iii>NNwNnn #1 #2
10322 {
10323     \if_meaning:w 0 #2
10324         \exp_after:wN \__fp_round_special:NwwNnn
10325         \exp_after:wN #1
10326     \fi:
10327     \__fp_pack_twice_four:wNNNNNNNN

```

```

10328   \__fp_pack_twice_four:wNNNNNNNNN
10329   \__fp_round_normal_end:wwNnn
10330   ; #2
10331 }
10332 \cs_new:Npn \__fp_round_normal_end:wwNnn #1;#2;#3#4#5
10333 {
10334   \exp_after:wN \__fp_exp_after_o:w \tex_roman numeral:D -`0
10335   \__fp_sanitize:Nw #3 #4 ; #1 ;
10336 }
10337 \cs_new:Npn \__fp_round_special:NwwNnn #1#2;#3;#4#5#6
10338 {
10339   \if_meaning:w 0 #1
10340     \__fp_case_return:nw
10341       { \exp_after:wN \__fp_zero_fp:N \exp_after:wn #4 }
10342   \else:
10343     \exp_after:wN \__fp_round_special_aux:Nw
10344     \exp_after:wN #4
10345     \int_use:N \__int_eval:w \c_one
10346       \if_meaning:w 1 #1 -#6 \else: +#5 \fi:
10347     \fi:
10348   ;
10349 }
10350 \cs_new:Npn \__fp_round_special_aux:Nw #1#2;
10351 {
10352   \exp_after:wN \__fp_exp_after_o:w \tex_roman numeral:D -`0
10353   \__fp_sanitize:Nw #1#2; {1000}{0000}{0000}{0000};
10354 }
(End definition for \__fp_round:Nww and \__fp_round:Nwn These functions are documented on page ??.)
10355 </initex | package>

```

25 l3fp-parse implementation

```

10356 <*initex | package>
10357 <@@=fp>

```

26 Precedences

In order of evaluation (some distinctions are irrelevant for the order of evaluation, but serve as signals).

32 Juxtaposition for implicit multiplication.

16 Function calls with multiple arguments.

15 Function calls expecting exactly one argument.

14 Binary `**` and `^` (right to left).

- 12 Unary +, -, ! (right to left).
- 10 Binary *, / and %.
- 9 Binary + and -.
- 7 Comparisons.
- 5 Logical and, denoted by `&&`.
- 4 Logical or, denoted by `||`.
- 3 Ternary operator `?:`, piece `?`.
- 2 Ternary operator `??:`, piece `::`.
- 1 Commas, and parentheses accepting commas.
- 0 Parentheses expecting exactly one argument.
- 1 Start and end of the expression.

27 Evaluating an expression

`__fp_parse:n` This f-expands to the internal floating point number obtained by evaluating the *(floating point expression)*. During this evaluation, each token is fully f-expanded.

TeXhackers note: Registers (integers, toks, etc.) are automatically unpacked, without requiring a function such as `\int_use:N`. Invalid tokens remaining after f-expansion will lead to unrecoverable low-level TeX errors.⁷

(End definition for `__fp_parse:n`)

28 Work plan

The task at hand is non-trivial, and some previous failed attempts have shown me that the code ends up giving unreadable logs, so we'd better get it (almost) right the first time. Let us thus first discuss precisely the design before starting to write the code. To simplify matters, we first consider expressions with integers only.

28.1 Storing results

The main issue in parsing expressions expandably is: “where in the input stream should the result be put?”

One option is to place the result at the end of the expression, but this has several drawbacks:

⁷Bruno: describe what happens in cases like `2\c_three = 6`.

- firstly it means that for long expressions we would be reaching all the way to the end of the expression at every step of the calculation, which can be rather expensive;
- secondly, when parsing parenthesized sub-expressions, we would naturally place the result after the corresponding closing parenthesis. But since `__fp_parse:n` does not assume that its argument is expanded, this closing parenthesis may be hidden in a macro, and not present yet, causing havoc.

The other natural option is to store the result at the start of the expression, and carry it as an argument of each macro. This does not really work either: in order to expand what follows on the input stream, we need to skip at each step over all the tokens in the result using `\exp_after:wN`. But this requires adding many `\exp_after:wN` to the result at each step, also an expensive process.

Hence, we need to go for some fine expansion control: the result is stored *before* the start... A toy model that illustrates this idea is to try and add some positive integers which may be hidden within macros, or registers. Assume that one number has already been found, and that we want to parse the next number. The current status of the code may look as follows.

```
\exp_after:wN \add:ww \__int_value:w 12345 \exp_after:wN ;
\tex_roman numeral:D -'0 \clean:w {stuff}
```

Hitting this construction by one step of expansion expands `\exp_after:wN`, which triggers the primitive `__int_value:w`, which reads an integer, 12345. This integer is unfinished, causing the second `\exp_after:wN` to expand, and trigger the construction `\tex_roman numeral:D -'0`, which f-expands `\clean:w` (see `l3expan.dtx` for an explanation). Assume then that `\clean:w` is such that it expands `{stuff}` to *e.g.*, 333444;. Once `\clean:w` is done expanding, we will obtain essentially

```
\exp_after:wN \add:ww \__int_value:w 12345 ; 333444 ;
```

where in fact `\exp_after:wN` has already been expanded, and `__int_value:w` has already seen 12345. Now, `__int_value:w` sees the ;, and stops expanding, and we are left with

```
\add:ww 12345 ; 333444 ;
```

which can safely perform the addition by grabbing two arguments delimited by ;.

On this toy example, we could note that if we were to continue parsing the expression, then the following number should also be cleaned up before the next use of a binary operation such as `\add:ww`. Just like `__int_value:w 12345 \exp_after:wN ;` expanded what follows once, we need `\add:ww` to do the calculation, and in the process to expand the following once. This is also true in our real application: all the functions of the form `__fp_..._o:ww` expand what follows once. This comes at the cost of leaving tokens in the input stack, and we will need to be careful to waste as little as possible of this precious memory.

28.2 Precedence

A major point to keep in mind when parsing expressions is that different operators have different precedence. The true analog of our toy `\clean:w` macro must thus take care of that. For definiteness, let us assume that the operation which prompted `\clean:w` was a multiplication. Then `\clean:w` (expand and) read digits until the number is ended by some operation. If this is `+` or `-`, then the multiplication should be calculated next, so `\clean:w` can simply decide that its job is done. However, if the operator we find is `^`, then this operation must be performed before returning control to the multiplication. This means that we need to `\clean:w` the number following `^`, and perform the calculation, then just end our job.

Hence, each time a number is cleaned, the precedence of the following operation must be compared to that of the previous operation. The process of course has to happen recursively. For instance, `1+2^3*4` would involve the following steps.

- 1 is cleaned up.
- 2 is cleaned up.
- The precedences of `+` and `^` are compared. Since the latter is higher, the second operand of `^` should be cleaned.
- 3 is cleaned up.
- The precedences of `^` and `*` are compared. Since the former is higher, the cleaning step stops.
- Compute $2^3 = 8$.
- We now have `1+8*4`, and the operation `+` is still looking for a second operand. Clean 8.
- The precedences of `+` and `*` are compared. Since the latter is higher, the second operand of `*` should be cleaned.
- 4 is cleaned up, and the end of the expression is reached.
- Compute $8*4 = 32$.
- We now have `1+8*4`, and the operation `+` is still looking for a second operand. Clean 32, and reach the end of the expression.
- Compute $1+32 = 33$.

Here, there is some (expensive) redundant work: the results of computations should not need to be cleaned again. Thus the true definition is slightly more elaborate.

The precedence of `(` and `)` are defined to be equal, and smaller than the precedence of `+` and `-`, itself smaller than `*` and `/`, smaller, finally, than the power operator `**` (or `^`).

28.3 Infix operators

The implementation that was chosen is slightly wasteful: it causes more nesting than necessary. However, it is simpler to implement and to explain than a slightly optimized variant.

The cornerstone of that method is a pair of functions, `\until` and `\one`, which both take as their first argument the precedence (an integer) of the last operation. The f-expansion of

```
\until <prec> \one <prec> <stuff>
```

is the internal floating point obtained by “cleaning” numbers which follow in the input stream, and performing computations until reaching an operation with a precedence less than or equal to $\langle prec \rangle$. This is followed by a control sequence of the form `\infix_?`, namely,

```
<floating point> \infix_?
```

where $?$ is the operation following that number in the input stream (we thus know that this operation has at most the precedence $\langle prec \rangle$, otherwise it would have been performed already).

How is that expansion achieved? First, `\one <prec>` reads one $\langle floating\ point \rangle$ number, and converts it to an internal form, then the following operation, say $*$, is packed in the form `\infix_*`, which is fed the $\langle prec \rangle$. This function (one per infix operator) compares $\langle prec \rangle$ with the precedence of the operator we just read (here $*$). If $\langle prec \rangle$ is higher, our job is finished, and `\one` leaves `__fp_parse_stop_until:N` so that `\until` knows to stop. Otherwise, `\infix_*` triggers a new pair `\until <prec(*)> \one <prec(*)>`, which produces the second operand $\langle floating\ point_2 \rangle$ for the multiplication:

```
\until <prec> <floating point>
... <floating point_2> ; \infix_?
```

The dots are `__fp_parse_apply_binary:NwNwN *`. The boolean tells `\until` that it is not done, and it expands (essentially) to

```
\until <prec> \__fp_*_o:ww <floating point> <floating point_2> \tex_roman numeral:D
-'0 \infix_? <prec>
```

making \TeX expand `__fp_*_o:ww` before `\until`. As implemented in `l3fp-basics`, this operation expands what follows its result exactly once. This triggers `\tex_roman numeral:D`, which fully expands `\infix_? <prec>`. This compares the precedence of the next operation, $?$, and $\langle prec \rangle$, and leaves a boolean (and possibly more things), which is then checked by `\until <prec>` to know if the result of the multiplication is the end of the story, or if $?$ should be computed as well before `\until <prec>` ends.

This should be easier to see on an example. To each infix operator, for instance, $*$, is associated the following data:

- a test function, `\infix_*`, which conditionally continues the calculation or waits to be hit again by expansion;

- a function `*` (notation for `__fp_*_o:ww`) which performs the actual calculation;
- an integer, `*`, which encodes the precedence of the operator.

The token that is currently being expanded is underlined, and in red. Tokens that have not yet been read (and could still be hidden in macros) are in gray.

In a first reading, the distinction between the $\langle\text{precedence}\rangle^+$, the operation `+`, and the character token `+` should not matter. It is only required to accommodate for multi-token infix operators such as `**`: indeed, when controlling expansion, we need to skip over those tokens using `\exp_after:wN`, and this only skips one token. Thus `**` needs to be replaced by a single token (either its precedence or its calculating function, depending on the place).

To end the computation cleanly, we add a trailing right parenthesis, and give `(` and `)` the lowest precedence, so that `\until(\one` reads numbers and performs operations until meeting a right parenthesis. This is discussed more precisely in the next section.

```

\uuntil( \one( 11 + 2**3 * 5 - 9 )
\uuntil( 1 \one( 1 + 2**3 * 5 - 9 )
\uuntil( 11 \one( + 2**3 * 5 - 9 )
\uuntil( 11; \infix_+( 2**3 * 5 - 9 )
\uuntil( 11; F + \until+ \one+ 2**3 * 5 - 9 )
\uuntil( 11; F + \until+ 2 \one+ **3 * 5 - 9 )
\uuntil( 11; F + \until+ 2; \infix_**+ 3 * 5 - 9 )
\uuntil( 11; F + \until+ 2; F ** \until** \one** 3 * 5 - 9 )
\uuntil( 11; F + \until+ 2; F ** \until** 3 \one** * 5 - 9 )
\uuntil( 11; F + \until+ 2; F ** \until** 3; \infix_**+ 5 - 9 )
\uuntil( 11; F + \until+ 2; F ** \until** 3; T \infix_* 5 - 9 )
\uuntil( 11; F + \until+ 2; F ** 3; \infix_* 5 - 9 )
\uuntil( 11; F + \until+ ** 2; 3; \infix_*+ 5 - 9 )
\uuntil( 11; F + \until+ 8; \infix_*+ 5 - 9 )
\uuntil( 11; F + \until+ 8; F * \until* \one* 5 - 9 )
\uuntil( 11; F + \until+ 8; F * \until* 5 \one* - 9 )
\uuntil( 11; F + \until+ 8; F * \until* 5; \infix_-* 9 )
\uuntil( 11; F + \until+ 8; F * \until* 5; T \infix_- 9 )
\uuntil( 11; F + \until+ 8; F * 5; \infix_- 9 )
\uuntil( 11; F + \until+ *_ 8; 5; \infix_-+ 9 )
\uuntil( 11; F + \until+ 40; \infix_-+ 9 )
\uuntil( 11; F + \until+ 40; T \infix_- 9 )
\uuntil( 11; F + 40; \infix_- 9 )

```

```

\until( + 11; 40; \infix_-( 9 )
\until( 51; \infix_-( 9 )
\until( 51; F - \until- \one- 9 )
\until( 51; F - \until- 9 \one- )
\until( 51; F - \until- 9; \infix_)-
\until( 51; F - \until- 9; T \infix_)
\underline{\until}( 51; F - 9; \infix_)
\until( - 51; 9; \infix_)(
\until( 42; \infix_)(
\underline{\until}( 42; T \infix_)
42; \infix_)

```

The only missing step is to clean the output by removing `\infix_()`, and possibly checking that nothing else remains.

28.4 Prefix operators, parentheses, and functions

Prefix operators (typically the unary `-`) and parentheses are taken care of by the same mechanism, and functions (`sin`, `exp`, etc.) as well. Finding the argument of the unary `-`, for instance, is very similar to grabbing the second operand of a binary infix operator, with a small subtlety on precedence explained below. Once that argument is found, its sign can be flipped. A left parenthesis is just a prefix operator which removes the closing parenthesis (with some extra checks).

Detecting prefix operators is done by `\one`. Before looking for a number, it tests the first character. If it is a digit, a dot, or a register, then we have a number. Otherwise, it is put in a function, `\prefix_?` (where `?` is roughly that first character), which is expanded. For instance, with a left parenthesis we would have the following.

```

\underline{\one}* ( 2 + 3 )
\underline{\prefix}_?(* 2 + 3 )
(* \until( \one( 2 + 3 )
...
(* 5; \infix_)

```

As usual, the `\until-\one` pair reads and compute until reaching an operator of precedence at most `(`. Then `(` removes `\infix_()` and looks ahead for the next operation, comparing its precedence `*` of the previous operation (in fact, this comparison is done by the relevant `\infix_?` built from the next operation).

To support multi-character function (and constant) names, we may need to put more than one character in the `\prefix_?` construction. See implementation for details.

Note that contrarily to `\infix_?` functions, the `\prefix_?` functions perform no test on their argument (which is once more the previous precedence), since we know that we need a number, and must never stop there.

Functions are implemented as prefix operators with infinitely high precedence, so that their argument is the first number that can possibly be built. For instance, something like the following could happen in a computation

```
\one* sqrt 4 + 3 )
\prefix_sqrt* 4 + 3 )
sqrt* \until{\one} 4 + 3 )
...
sqrt* 4; \infix_+ 3 )
2; \infix_+ 3 )
```

Lonely example, to be put somewhere: $2+\sin 1 * 3$ is $2 + (\sin(1) \times 3)$.

A further complication arises in the case of the unary $-$ sign: -3^{**2} should be $-(3^2) = -9$, and not $(-3)^2 = 9$. Easy, just give $-$ a lower precedence, equal to that of the infix $+$ and $-$. Unfortunately, this fails in subtle cases such as 3^{**-2*4} , yielding $3^{-2 \times 4}$ instead of the correct $3^{-2} \times 4$. In fact, a unary $-$ should only perform operations whose precedence is greater than that of the last operation, as well as $-$.⁸ Thus, $\prefix_{-} \langle prec \rangle$ expands to something like

```
- \langle prec \rangle \until? \one ?
```

where $?$ is the maximum of $\langle prec \rangle$ and the precedence of $-$. Once the argument of $-$ is found, $-$ gets its opposite, and leaves it for the previous operation to use.

An example with parentheses.

```
\until( \one( 11 * ( 2 + 3 ) - 9 )
\until( 1 \one( 1 * ( 2 + 3 ) - 9 )
\until( 11 \one( * ( 2 + 3 ) - 9 )
\until( 11; \infix_* ( ( 2 + 3 ) - 9 )
\until( 11; F * \until* \one* ( 2 + 3 ) - 9 )
\until( 11; F * \until* \prefix_*( 2 + 3 ) - 9 )
\until( 11; F * \until* (* \until( \one( 2 + 3 ) - 9 )
\until( 11; F * \until* (* \until( 2 \one( + 3 ) - 9 )
\until( 11; F * \until* (* \until( 2; \infix_+ ( 3 ) - 9 )
\until( 11; F * \until* (* \until( 2; F + \until{+} \one+ 3 ) - 9 )
\until( 11; F * \until* (* \until( 2; F + \until{+} 3 \one+ ) - 9 )
\until( 11; F * \until* (* \until( 2; F + \until{+} 3; \infix_+ ) - 9 )
\until( 11; F * \until* (* \until( 2; F + \until{+} 3; T \infix_ ) - 9 )
\until( 11; F * \until* (* \until( 2; F + 3; \infix_ ) - 9 )
```

⁸Taking into account the precedence of $-$ itself only matters when it follows a left parenthesis: $(-2*4+3)$ should give $((-8)+3)$, not $(-(8+3))$.

```

\until( 11; F * \until* (* \until( + 2; 3; \infix_)( - 9 )
\until( 11; F * \until* (* \until( 5; \infix_)( - 9 )
\until( 11; F * \until* (* \until( 5; T \infix_) - 9 )
\until( 11; F * \until* (_* 5; \infix_) - 9 )
\until( 11; F * \until* 5; \infix_* 9 )
\until( 11; F * \until* 5; T \infix_- 9 )
\underline{\until}( 11; F * 5; \infix_- 9 )
\until( *_ 11; 5; \infix_- 9 )
\until( 55; \infix_-( 9 )
\until( 55; F - \until- \one- 9 )
\until( 55; F - \until- 9 \one- )
\until( 55; F - \until- 9; \infix_)-
\until( 55; F - \until- 9; T \infix_)
\underline{\until}( 55; F - 9; \infix_)
\until( _ 55; 9; \infix_)(
\underline{\until}( 47; \infix_)(
\underline{\until}( 47; T \infix_)
47; \infix_)

```

The end of this (sub)section was not revised yet

- If it is a sign (- or +), then any following sign will be combined with this initial sign, forming \prefix_+ or \prefix_-.
- If it is a letter, then any following letter is grabbed, forming for instance \prefix_-sin or \prefix_sinh.
- Otherwise, only one token⁹ is grabbed, for instance \prefix_.

Functions may take several arguments, possibly an unknown number¹⁰, for instance `round(1.23456,2)`.

- `round` is made into \prefix_round, which tries to grab one number using \one.
- This builds \prefix_(), which uses \one to grab one number, calculating as necessary. The comma is given the same precedence as parentheses, and thus ends the calculation of the argument of `round`.
- `round` now has its first argument. It can check whether the argument was closed by , or), and branch accordingly.

⁹Some support for multi-character prefix operator may be added in the future, but right now, I don't see a use for it. Perhaps, for including comments inside the computation itself??

¹⁰Keyword argument support may be added later.

- If it was a comma, then the first argument is skipped over, through an expensive set of `\exp_after:wN`, and the second argument can be grabbed. Here it is simply an integer, easier to parse by building upon `\etex_numexpr:D`.
- The closing parenthesis (or another comma) is seen, and the control is given back to `\prefix_round`.

28.5 Type detection

The type of data should be detected by reading the first few tokens, before calling a type-specific function to parse it. Or should the type be obtained after the semicolon which indicates the end of the thing? And placed there?

Also to grab exponents correctly, build `__fp_<abc>:w` when seeing some non-numeric `abc` while still looking to complete a number (or other data). Then, if `__fp_postfix_<type>_<abc>:w` exists, use it.

The internal representation of floating point numbers is quite untypable, and we provide here the tools to convert from a more user-friendly representation to internal floating point numbers, and for various other conversions. Every floating point operation calls those functions to normalize the input, so they must be optimized.

29 Internal representation

Internally, a floating point number $\langle X \rangle$ is a token list containing

```
\s_fp \__fp_chk:w ⟨case⟩ ⟨sign⟩ ⟨body⟩ ;
```

Let us explain each piece separately.

Internal floating point numbers will be used in expressions, and in this context will be subject to f-expansion. They must leave a recognizable mark after f-expansion, to prevent the floating point number from being re-parsed. Thus, `\s_fp` is simply another name for `\relax`.

Since floating point numbers are always accessed by the various operations using f-expansion, we can safely let them be protected: x-expansion will then leave them untouched. However, when used directly without an accessor function, floating points should produce an error. `\s_fp` will do nothing, and `__fp_chk:w` produces an error.

The (decimal part of the) IEEE-754-2008 standard requires the format to be able to represent special floating point numbers besides the usual positive and negative cases. The various possibilities will be distinguished by their $\langle \text{case} \rangle$, which is a single digit:¹¹

- 0 zeros: `+0` and `-0`,
- 1 “normal” numbers (positive and negative),
- 2 infinities: `+inf` and `-inf`,
- 3 quiet and signalling `nan`.

¹¹Bruno: I need to implement subnormal numbers. Also, quiet and signalling `nan` must be better distinguished.

Table 1: Internal representation of floating point numbers.

Representation	Meaning
0 0 \s_fp_... ;	Positive zero.
0 2 \s_fp_... ;	Negative zero.
1 0 {\langle exponent \rangle} {\langle X_1 \rangle} {\langle X_2 \rangle} {\langle X_3 \rangle} {\langle X_4 \rangle} ;	Positive floating point.
1 2 {\langle exponent \rangle} {\langle X_1 \rangle} {\langle X_2 \rangle} {\langle X_3 \rangle} {\langle X_4 \rangle} ;	Negative floating point.
2 0 \s_fp_... ;	Positive infinity.
2 2 \s_fp_... ;	Negative infinity.
3 1 \s_fp_... ;	Quiet nan.
3 1 \s_fp_... ;	Signalling nan.

The $\langle sign \rangle$ is 0 (positive) or 2 (negative), except in the case of `nan`, which have $\langle sign \rangle = 1$. This ensures that changing the $\langle sign \rangle$ digit to $2 - \langle sign \rangle$ is exactly equivalent to changing the sign of the number.

Special floating point numbers have the form

`\s_fp __fp_chk:w \langle case \rangle \langle sign \rangle \s_fp_... ;`

where `\s_fp_...` is a scan mark carrying information about how the number was formed (useful for debugging).

Normal floating point numbers ($\langle case \rangle = 1$) have the form

`\s_fp __fp_chk:w 1 \langle sign \rangle {\langle exponent \rangle} {\langle X_1 \rangle} {\langle X_2 \rangle} {\langle X_3 \rangle} {\langle X_4 \rangle} ;`

Here, the $\langle exponent \rangle$ is an integer, at most `\c_fp_max_exponent_int = 10000` in absolute value. The body consists in four blocks of exactly 4 digits, $0000 \leq \langle X_i \rangle \leq 9999$, such that

$$\langle X \rangle = (-1)^{\langle sign \rangle} 10^{-\langle exponent \rangle} \sum_{i=1}^4 \langle X_i \rangle 10^{-4i}$$

and such that the $\langle exponent \rangle$ is minimal. This implies $1000 \leq \langle X_1 \rangle \leq 9999$.

30 Internal parsing functions

- `__fp_parse_until:Nw` Reads the $\langle tokens \rangle$, performing every computation with a precedence higher than $\langle precedence \rangle$, then expands to where the $\langle op \rangle$ is the first operation with a lower precedence, possibly `end`.
(End definition for __fp_parse_until:Nw)
- `__fp_parse_operand:Nw` If the following $\langle operation \rangle$ has a precedence higher than $\langle precedence \rangle$, expands to and otherwise expands to
(End definition for __fp_parse_operand:Nw)
- `__fp_parse_infix_\meta{operation}:N` If the $\langle op \rangle$ has a precedence higher than $\langle precedence \rangle$, expands to Otherwise expands to
(End definition for __fp_parse_infix_\meta{operation}:N)

30.1 Expansion control

At each step in reading a floating point expression, we wish to perform `f`-expansion. Normally, spaces stop this `f`-expansion. This can be problematic: for instance, the macro `\X` below will not be expanded if we simply do `f`-expansion.

```
\DeclareDocumentCommand {\test} {m} { \fp_eval:n {#1} }
\ExplSyntaxOff
\test { 1 + \X }
```

To avoid this problem, at every step, we do essentially what `\use:f` would do: take an argument, put it back in the input stream, then `f`-expand it. This is not a complete solution, since a macro's expansion could contain leading spaces which will stop the `f`-expansion before further macro calls are performed. However, in practice it should be enough: in particular, floating point numbers will correctly be expanded to the underlying `\s_fp ...` structure.

Floating point expressions should behave as much as possible like ε - \TeX -based integer expressions and dimension expressions. In particular, full-expansion should be performed as the expression is read, token by token, forcing the expansion of protected macros, and ignoring spaces.

Full expansion can be done with `\tex_roman numeral:D -'0`. Unfortunately, this expansion is stopped by spaces. Thus using simply this will fail on `\fp_eval:n { 1 + ~ \l_tmpa_fp }` since the floating point variable will not be expanded. Of course, spaces will not appear in a code setting, but may very easily come in document-level input, from which some expressions may come. We can avoid being stopped by such explicit space characters (and by some braces) if we add `\use:n` after `'0`.

Testing if a character token `#1` is a digit can be done using

```
\if_int_compare:w \c_nine < 1 \token_to_str:N #1 \exp_stop_f:
  true code
\else:
  false code
\fi:
```

To exclude 0, replace `\c_nine` by `\c_ten`. The use of `\token_to_str:N` ensures that a digit with any catcode is detected.

`_fp_parse_expand:w` This function must always come within a `\romannumeral` expansion. The `(tokens)` should be the part of the expression that we have not yet read. This requires in particular closing all conditionals properly before expanding.

```
10358 \cs_new:Npn \_fp_parse_expand:w #1 { -'0 #1 }
(End definition for \_fp_parse_expand:w)
```

`_fp_parse_return_semicolon:w` This very odd function swaps its position with the following `\fi:` and removes `_fp_parse_expand:w` normally responsible for expansion. That turns out to be useful.

```
10359 \cs_new:Npn \_fp_parse_return_semicolon:w
10360   #1 \fi: \_fp_parse_expand:w { \fi: ; #1 }
(End definition for \_fp_parse_return_semicolon:w)
```

30.2 Fp object type

__fp_type_from_scan:N
__fp_type_from_scan:w

```

10361 \group_begin:
10362 \char_set_catcode_other:N \S
10363 \char_set_catcode_other:N \F
10364 \char_set_catcode_other:N \P
10365 \char_set_lccode:nn { '\- } { '\_ }
10366 \tl_to_lowercase:n
10367 {
10368 \group_end:
10369 \cs_new:Npn \_\_fp_type_from_scan:N #1
10370 {
10371   \exp_after:wN \_\_fp_type_from_scan:w
10372     \token_to_str:N #1 \q_mark S--FP-? \q_mark \q_stop
10373   }
10374 \cs_new:Npn \_\_fp_type_from_scan:w #1 S--FP #2 \q_mark #3 \q_stop {#2}
10375 }
```

(End definition for __fp_type_from_scan:N and __fp_type_from_scan:w)

30.3 Reading digits

__fp_parse_digits_vii:N
__fp_parse_digits_vi:N
__fp_parse_digits_v:N
__fp_parse_digits_iv:N
__fp_parse_digits_iii:N
__fp_parse_digits_ii:N
__fp_parse_digits_i:N

These functions must be called within an __int_value:w or __int_eval:w construction. The first token which follows must be f-expanded prior to calling those functions. The functions read tokens one by one, and output digits into the input stream, until meeting a non-digit, or up to a number of digits equal to their index. The full expansion is

$\langle digits \rangle ; \langle filling \ 0 \rangle ; \langle length \rangle$

where $\langle filling \ 0 \rangle$ is a string of zeros such that $\langle digits \rangle \langle filling \ 0 \rangle$ has the length given by the index of the function, and $\langle length \rangle$ is the number of zeros in the $\langle filling \ 0 \rangle$ string. Each function puts a digit into the input stream and calls the next function, until we find a non-digit. We are careful to pass the tested tokens through \token_to_str:N to normalize their category code.

```

10376 \cs_set_protected:Npn \_\_fp_tmp:w #1 #2 #3
10377 {
10378   \cs_new:cpn { \_\_fp_parse_digits_ #1 :N } ##1
10379   {
10380     \if_int_compare:w \c_nine < 1 \token_to_str:N ##1 \exp_stop_f:
10381       \token_to_str:N ##1 \exp_after:wN #2 \tex_roman numeral:D
10382     \else:
10383       \_\_fp_parse_return_semicolon:w #3 ##1
10384     \fi:
10385     \_\_fp_parse_expand:w
10386   }
10387 }
10388 \_\_fp_tmp:w {vii} \_\_fp_parse_digits_vi:N { 0000000 ; 7 }
```

```

10389 \__fp_tmp:w {vi}   \__fp_parse_digits_v:N   { 000000 ; 6 }
10390 \__fp_tmp:w {v}    \__fp_parse_digits_iv:N   { 00000 ; 5 }
10391 \__fp_tmp:w {iv}   \__fp_parse_digits_iii:N  { 0000 ; 4 }
10392 \__fp_tmp:w {iii}  \__fp_parse_digits_ii:N   { 000 ; 3 }
10393 \__fp_tmp:w {ii}   \__fp_parse_digits_i:N    { 00 ; 2 }
10394 \__fp_tmp:w {i}    \__fp_parse_digits_:N     { 0 ; 1 }
10395 \cs_new_nopar:Npn \__fp_parse_digits_:N { ; ; 0 }

(End definition for \__fp_parse_digits_vii:N and others.)

```

30.4 Parsing one operand

At the start of an expression, or just following a binary operation or a function call, we are looking for an operand. This can be an explicit floating point number, a floating point variable, a TeX register, a function call such as `sin(3)`, a parenthesized expression, etc. We distinguish the various cases by their first token after f-expansion:

- `\tex_relax:D` in some form. That can be an internal floating point, a premature end, or an uninitialized register.
- A register. We interpret this as the significand of a floating point number. This is subtly different from unpacking it, for instance, `\c_minus_one**2` gives 1, while `-1**2` gives -1.
- A digit, or a dot. That marks the start of the significand for a floating point number.
- A letter (lower or upper-case), which starts an identifier, either a constant or a function (possibly unknown).
- `+, -, or !`, unary operators, which resume looking for a floating point number before acting on it.
- `(`, which makes us parse a subexpression until the matching `)`.
- Other characters such as `'` or `"` may be given a meaning later. Characters such as `*` or `/` have a meaning as infix operators but are not valid when we are looking for an operand: for instance, `3+*4` is not valid.

A category code test separates the first two cases from the others, and they are further distinguished with a meaning test. We then single out digits. Letters are detected using their character code. All other characters are taken care of by building a csname from that character and using it to continue parsing. Unknown characters lead to an error.

`__fp_parse_operand:Nw` Function called `\one` at other places. It grabs one operand, and packs the symbol that follows in an `\infix_ csname`. #1 is the previous *(precedence)*, and #2 the first character of the operand (already f-expanded).

```

10396 \cs_new:Npn \__fp_parse_operand:Nw #1 #2
10397   {
10398     \if_catcode:w \tex_relax:D #2

```

```

10399 \if_meaning:w \tex_relax:D #2
10400   \exp_after:wN \exp_after:wN
10401   \exp_after:wN \__fp_parse_operand_relax:NN
10402 \else:
10403   \exp_after:wN \exp_after:wN
10404   \exp_after:wN \__fp_parse_operand_register:NN
10405 \fi:
10406 \else:
10407   \if_int_compare:w \c_nine < 1 \token_to_str:N #2 \exp_stop_f:
10408     \exp_after:wN \exp_after:wN
10409     \exp_after:wN \__fp_parse_operand_digit:NN
10410 \else:
10411   \exp_after:wN \exp_after:wN
10412   \exp_after:wN \__fp_parse_operand_other:NN
10413 \fi:
10414 \fi:
10415 #1 #2
10416 }

```

(End definition for `__fp_parse_operand:Nw`)

Find the exponent following the register #2, then combine the value of #2 (mapping 1pt to 1) with the exponent to produce a floating point number.

```

10417 \group_begin:
10418 \char_set_catcode_other:N \P
10419 \char_set_catcode_other:N \T
10420 \tl_to_lowercase:n
10421 {
10422   \group_end:
10423   \cs_new:Npn \__fp_parse_operand_register:NN #1#2
10424   {
10425     \exp_after:wN \__fp_parse_infix_after_operand:NwN
10426     \exp_after:wN #1
10427     \tex_roman numeral:D -'0
10428     \exp_after:wN \__fp_parse_operand_register_aux:www
10429     \tex_the:D
10430       \exp_after:wN #2
10431       \exp_after:wN P
10432       \exp_after:wN T
10433       \exp_after:wN \q_stop
10434       \__int_value:w \__fp_parse_exponent:N
10435   }
10436   \cs_new:Npn \__fp_parse_operand_register_aux:www #1 PT #2 \q_stop #3 ;
10437   { \__fp_parse:n { #1 e #3 } }
10438 }

```

(End definition for `__fp_parse_operand_register:NN` and `__fp_parse_operand_register_aux:www`)

The second argument is a control sequence equal to `\tex_relax:D`. There are three cases, dispatched using `__fp_type_from_scan:N`.

```

\__fp_parse_operand_relax:NN
\__fp_parse_exp_after_f:nw
  \__fp_parse_exp_after_mark_f:nw
\__fp_parse_exp_after_?_f:nw

```

- `\s__fp` starts a floating point number, and we call `_fp_parse_exp_after_f:nw`, which `f`-expands after the floating point.
- `\s__fp_mark` is a premature end, we call `_fp_parse_exp_after_mark_f:nw`, which triggers the appropriate error.
- For a control sequence not containing `\s__fp`, we call `_fp_parse_exp_after_-?_f:nw`, causing a `bad-variable` error.

This scheme is extensible: additional types can be added by starting the variables with a scan mark of the form `\s__fp_{type}` and defining `_fp_parse_exp_after_{type}_f:nw`. In all cases, we make sure that the last argument of `_fp_parse_infix:NN` is correctly expanded.

```

10439 \cs_new:Npn \_fp_parse_operand_relax:NN #1#2
10440 {
10441   \cs:w __fp_parse_exp_after \_fp_type_from_scan:N #2 _f:nw \cs_end:
10442   {
10443     \exp_after:wN \_fp_parse_infix:NN
10444     \exp_after:wN #1 \tex_roman numeral:D \_fp_parse_expand:w
10445   }
10446   #2
10447 }
10448 \cs_new_eq:NN \_fp_parse_exp_after_f:nw \_fp_exp_after_f:nw
10449 \cs_new:Npn \_fp_parse_exp_after_mark_f:nw #1
10450 {
10451   \_msg_kernel_expandable_error:nn { kernel } { fp-early-end }
10452   \exp_after:wN \c_nan_fp
10453   \tex_roman numeral:D -'0 #1
10454 }
10455 \cs_new:cpn { __fp_parse_exp_after_-?_f:nw } #1#2
10456 {
10457   \_msg_kernel_expandable_error:nnn
10458   { kernel } { bad-variable } {#2}
10459   \exp_after:wN \c_nan_fp
10460   \tex_roman numeral:D -'0 #1
10461 }

```

(End definition for `_fp_parse_operand_relax:NN` and others.)

`_fp_parse_operand_other:NN` The interesting bit is `_fp_parse_operand_other:NN`. It separates letters from non-letters and builds the appropriate `\prefix` function. If it is not defined (is `\tex_relax:D`), make it a signalling `nan`. We don't look for an argument, as the unknown "prefix" can also be a (mistyped) constant such as `Inf`.

```

10462 \cs_new:Npn \_fp_parse_operand_other:NN #1 #2
10463 {
10464   \if_int_compare:w
10465     \_int_eval:w \tex_uccode:D '#2 / 26 = \c_three
10466     \exp_after:wN \_fp_parse_operand_other_word_aux:Nw
10467     \exp_after:wN #1
10468     \tex_roman numeral:D

```

```

10469     \exp_after:wN \__fp_parse_letters>NN
10470     \exp_after:wN #2
10471     \tex_roman numeral:D
10472 \else:
10473     \exp_after:wN \__fp_parse_operand_other_prefix_aux>NNN
10474     \exp_after:wN #1
10475     \exp_after:wN #2
10476     \cs:w __fp_parse_prefix_#2:Nw \exp_after:wN \cs_end:
10477     \tex_roman numeral:D
10478 \fi:
10479 \__fp_parse_expand:w
10480 }
10481
10482 \cs_new:Npn \__fp_parse_letters>NN #1#2
10483 {
10484     \exp_after:wN \c_zero
10485     \exp_after:wN #1
10486     \tex_roman numeral:D
10487     \if_int_compare:w
10488         \if_catcode:w \tex_relax:D #2
10489         \c_zero
10490     \else:
10491         \__int_eval:w \tex_uccode:D '#2 / 26
10492     \fi:
10493     = \c_three
10494     \exp_after:wN \__fp_parse_letters>NN
10495     \exp_after:wN #2
10496     \tex_roman numeral:D
10497     \exp_after:wN \__fp_parse_expand:w
10498 \else:
10499     \exp_after:wN \c_zero
10500     \exp_after:wN ;
10501     \exp_after:wN #2
10502 \fi:
10503 }
10504 \cs_new:Npn \__fp_parse_operand_other_word_aux:Nw #1 #2;
10505 {
10506     \cs_if_exist_use:cF { __fp_parse_word_#2:N }
10507     {
10508         \__msg_kernel_expandable_error:nnn
10509             { kernel } { unknown-fp-word } { #2 }
10510         \exp_after:wN \c_nan_fp
10511         \tex_roman numeral:D -'0
10512         \__fp_parse_infix>NN
10513     }
10514     #1
10515 }
10516 \cs_new_eq:NN \s_fp_unknown \tex_relax:D
10517 \cs_new:Npn \__fp_parse_operand_other_prefix_aux>NNN #1#2#3
10518 {

```

```

10519 \if_meaning:w \tex_relax:D #3
10520   \exp_after:wN \__fp_parse_operand_other_prefix_unknown:NNN
10521   \exp_after:wN #2
10522 \fi:
10523 #3 #1
10524 }
10525 \cs_new:Npn \__fp_parse_operand_other_prefix_unknown:NNN #1#2#3
10526 {
10527   \cs_if_exist:cTF { __fp_parse_infix_#1:N }
10528   {
10529     \__msg_kernel_expandable_error:nnn
10530       { kernel } { fp-missing-number } {#1}
10531     \exp_after:wN \c_nan_fp
10532     \tex_roman numeral:D -'0
10533     \__fp_parse_infix>NN #3 #1
10534   }
10535   {
10536     \__msg_kernel_expandable_error:nnn
10537       { kernel } { fp-unknown-symbol } {#1}
10538     \__fp_parse_operand:Nw #3
10539   }
10540 }

```

(End definition for `__fp_parse_operand_other:NN`)

The following forms are accepted:

-
- *(floating point)*
- *(integer)* . *(decimal)* e *(exponent)*

In both cases, *(signs)* is a (possibly empty) string of + and - (with any category code^{12,13}).

In the second form, the *(integer)* is a sequence of digits, whose length is not limited by constraints TeX's integer registers. It stops at the first non-digit character. The *(decimal)* part is formed by all digits from the dot (if it exists) until the first non-digit character. The *(exponent)* part has the form *(exponent sign)* *(exponent body)*, where *(exponent sign)* is any string of + or -, and *(exponent body)* is a string of digits, stopping, as usual, at the first non-digit.

Any missing part will take the appropriate default value.

- A missing *(exponent)* is considered to be zero.
- A number with no dot has zero decimal part.
- An empty *(integer)* part or decimal part is zero.

Border cases:

¹²Bruno: except 1, 2, 4, 10, 13, and those which cannot be tokens (0, 5, 9), so really, just 3, 6, 7, 8, 11, 12.

¹³Bruno: test (and implement) non-other digits.

- `e1` is considered as invalid input, and gives `qnan`.¹⁴ This will be important once parsing expressions is implemented, since `e-1` would be ambiguous otherwise.
- `.e3` and `.` are zero.

Bruno: expansion, not yet. Only f-expansion at the start, and unpacking of registers after signs.

Work-plan.

- Remove any leading sign and build the $\langle sign \rangle$ as we go. If the next character is a letter, go to the “special” branch, discussed later.
- Drop leading zeros.
- If the next character is a dot, drop some more zeros, keeping track of how many were dropped after the dot. Counting those gives $\langle exp_1 \rangle < 0$. Then read the decimal part with the `_fp_from_str_small` functions.
- Otherwise, $\langle exp_1 \rangle = 0$, and first read the integer part, then the decimal part. This is implemented through the more elaborate `_fp_from_str_large` functions.
- Continuing in the same line of expansion, read the exponent $\langle exp_2 \rangle$.
- Finally check that nothing is left.¹⁵

```
\_fp_parse_operand_digit>NN
10541 \cs_new:Npn \_fp_parse_operand_digit>NN #1
10542 {
10543   \exp_after:wN \_fp_parse_infix_after_operand:NwN
10544   \exp_after:wN #
10545   \tex_roman numeral:D -'0
10546   \exp_after:wN \_fp_sanitize:wN
10547   \int_use:N \int_eval:w \c_zero \_fp_parse_trim_zeros:N
10548 }
```

(End definition for `_fp_parse_operand_digit>NN`)

30.4.1 Trimming leading zeros

`_fp_parse_trim_zeros:N`
`_fp_parse_trim_end:w`

This function expects an already expanded token. It removes any leading zero, then distinguishes three cases: if the first non-zero token is a digit, then call `_fp_parse_large:N` (the significand is ≥ 1); if it is `.`, then continue trimming zeros with `_fp_parse_strim_zeros:N`; otherwise, our number is exactly zero, and we call `_fp_parse_zero:` to take care of that case.

```
10549 \cs_new:Npn \_fp_parse_trim_zeros:N #1
10550 {
10551   \if:w 0 #1
10552     \exp_after:wN \_fp_parse_trim_zeros:N
```

¹⁴Bruno: now just gives an error.

¹⁵Bruno: not done yet.

```

10553   \tex_roman numeral:D
10554 \else:
10555   \if:w . #1
10556     \exp_after:wN \__fp_parse_strim_zeros:N
10557     \tex_roman numeral:D
10558   \else:
10559     \__fp_parse_trim_end:w #1
10560   \fi:
10561   \fi:
10562   \__fp_parse_expand:w
10563 }
10564 \cs_new:Npn \__fp_parse_trim_end:w #1 \fi: \fi: \__fp_parse_expand:w
10565 {
10566   \fi:
10567   \fi:
10568   \if_int_compare:w \c_nine < 1 \token_to_str:N #1 \exp_stop_f:
10569     \exp_after:wN \__fp_parse_large:N
10570   \else:
10571     \exp_after:wN \__fp_parse_zero:
10572   \fi:
10573 #1
10574 }
```

(End definition for `__fp_parse_strim_zeros:N` and `__fp_parse_trim_end:w`)

`__fp_parse_strim_zeros:N`
`__fp_parse_strim_end:w`

If we have removed all digits until a period (or if the body started with a period), then enter the “`small_trim`” loop which outputs -1 for each removed 0. Those -1 are added to an integer expression waiting for the exponent. If the first non-zero token is a digit, call `__fp_parse_small:N` (our significand is smaller than 1), and otherwise, the number is an exact zero.

```

10575 \cs_new:Npn \__fp_parse_strim_zeros:N #1
10576 {
10577   \if:w 0 #1
10578     - \c_one
10579     \exp_after:wN \__fp_parse_strim_zeros:N
10580     \tex_roman numeral:D
10581   \else:
10582     \__fp_parse_strim_end:w #1
10583   \fi:
10584   \__fp_parse_expand:w
10585 }
10586 \cs_new:Npn \__fp_parse_strim_end:w #1 \fi: \__fp_parse_expand:w
10587 {
10588   \fi:
10589   \if_int_compare:w \c_nine < 1 \token_to_str:N #1 \exp_stop_f:
10590     \exp_after:wN \__fp_parse_small:N
10591   \else:
10592     \exp_after:wN \__fp_parse_zero:
10593   \fi:
10594 #1
```

```

10595     }
(End definition for \__fp_parse_strim_zeros:N and \__fp_parse_strim_end:w)
```

30.4.2 Exact zero

__fp_parse_zero: After reading a significand of 0, we need to remove any exponent, then put a sign of 1 for __fp_sanitize:wN, denoting an exact zero.

```

10596 \cs_new:Npn \__fp_parse_zero:
10597 {
10598     \exp_after:wN ; \exp_after:wN 1
10599     \int_value:w \__fp_parse_exponent:N
10600 }
```

(End definition for __fp_parse_zero:)

30.4.3 Small significand

__fp_parse_small:N This function is called after we have passed the decimal separator and removed all leading zeros from the significand. It is followed by a non-zero digit (with any catcode). The goal is to read up to 16 digits. But we can't do that all at once, because __int_value:w (which allows us to collect digits and continue expanding) can only go up to 9 digits. Hence we grab digits in two steps of 8 digits. Since #1 is a digit, read seven more digits using __fp_parse_digits_vii:N. The small_leading auxiliary will leave those digits in the __int_value:w, and grab some more, or stop if there are no more digits. Then the pack_leading auxiliary puts the various parts in the appropriate order for the processing further up.

```

10601 \cs_new:Npn \__fp_parse_small:N #
10602 {
10603     \exp_after:wN \__fp_parse_pack_leading:NNNNNww
10604     \int_use:N \__int_eval:w 1 \token_to_str:N #1
10605     \exp_after:wN \__fp_parse_small_leading:wwNN
10606     \int_value:w 1
10607     \exp_after:wN \__fp_parse_digits_vii:N
10608     \tex_roman numeral:D \__fp_parse_expand:w
10609 }
```

(End definition for __fp_parse_small:N)

__fp_parse_small_leading:wwNN We leave $\langle digits \rangle \langle zeros \rangle$ in the input stream: the functions used to grab digits are such that this constitutes digits 1 through 8 of the significand. Then prepare to pack 8 more digits, with an exponent shift of \c_zero (this shift is used in the case of a large significand). If #4 is a digit, leave it behind for the packing function, and read 6 more digits to reach a total of 15 digits: further digits are involved in the rounding. Otherwise put 8 zeros in to complete the significand, then look for an exponent.

```

10610 \cs_new:Npn \__fp_parse_small_leading:wwNN 1 #1 ; #2; #3 #4
10611 {
10612     #1 #2
10613     \exp_after:wN \__fp_parse_pack_trailing:NNNNNNww
10614     \exp_after:wN \c_zero
```

```

10615 \int_use:N \_int_eval:w 1
10616   \if_int_compare:w \c_nine < 1 \token_to_str:N #4 \exp_stop_f:
10617     \token_to_str:N #4
10618     \exp_after:wN \_fp_parse_small_trailing:wwNN
10619     \_int_value:w 1
10620       \exp_after:wN \_fp_parse_digits_vi:N
10621       \tex_roman numeral:D
10622   \else:
10623     0000 0000 \_fp_parse_exponent:Nw #4
10624   \fi:
10625   \_fp_parse_expand:w
10626 }
(End definition for \_fp_parse_small_leading:wwNN)

```

_fp_parse_small_trailing:wwNN Leave digits 10 to 15 (arguments #1 and #2) in the input stream. If the *<next token>* is a digit, it is the 16th digit, we keep it, then the `small_round` auxiliary considers this digit and all further digits to perform the rounding: the function expands to nothing or to `+1`. Otherwise, there is no 16-th digit, so we put a 0, and look for an exponent.

```

10627 \cs_new:Npn \_fp_parse_small_trailing:wwNN 1 #1 ; #2; #3 #4
10628 {
10629   #1 #2
10630   \if_int_compare:w \c_nine < 1 \token_to_str:N #4 \exp_stop_f:
10631     \token_to_str:N #4
10632     \exp_after:wN \_fp_parse_small_round:NN
10633     \exp_after:wN #4
10634     \tex_roman numeral:D
10635   \else:
10636     0 \_fp_parse_exponent:Nw #4
10637   \fi:
10638   \_fp_parse_expand:w
10639 }
(End definition for \_fp_parse_small_trailing:wwNN)

```

_fp_parse_pack_trailing:NNNNNNww
_fp_parse_pack_leading:NNNNNNww
_fp_parse_pack_carry:w Those functions are expanded after all the digits are found, we took care of the rounding, as well as the exponent. The last argument is the exponent. The previous five arguments are 8 digits which we pack in groups of 4, and the argument before that is 1, except in the rare case where rounding lead to a carry, in which case the argument is 2. The `trailing` function has an exponent shift as its first argument, which we add to the exponent found in the `e...` syntax. If the trailing digits cause a carry, the integer expression for the leading digits is incremented (`+ \c_one` in the code below). If the leading digits propagate this carry all the way up, the function `_fp_parse_pack_carry:w` increments the exponent, and changes the significand from `0000...` to `1000...`: this is simple because such a carry can only occur to give rise to a power of 10.

```

10640 \cs_new:Npn \_fp_parse_pack_trailing:NNNNNNww #1 #2 #3#4#5#6 #7; #8 ;
10641 {
10642   \if_meaning:w 2 #2 + \c_one \fi:
10643   ; #8 + #1 ; {#3#4#5#6} {#7};
10644 }

```

```

10645 \cs_new:Npn \__fp_parse_pack_leading:NNNNNww #1 #2#3#4#5 #6; #7;
10646 {
10647     + #7
10648     \if_meaning:w 2 #1 \__fp_parse_pack_carry:w \fi:
10649     ; 0 {#2#3#4#5} {#6}
10650 }
10651 \cs_new:Npn \__fp_parse_pack_carry:w \fi: ; 0 #1
10652 { \fi: + \c_one ; 0 {1000} }
(End definition for \__fp_parse_pack_trailing:NNNNNNww, \__fp_parse_pack_leading:NNNNNww, and
\__fp_parse_pack_carry:w)

```

30.4.4 Large significand

Parsing a significand larger than 1 is a little bit more difficult than parsing small significands. We need to count the number of digits before the decimal separator, and add that to the final exponent. We also need to test for the presence of a dot each time we run out of digits, and branch to the appropriate `parse_small` function in those cases.

`__fp_parse_large:N` This function is followed by the first non-zero digit of a “large” significand (≥ 1). It is called within an integer expression for the exponent. Grab up to 7 more digits, for a total of 8 digits.

```

10653 \cs_new:Npn \__fp_parse_large:N #1
10654 {
10655     \exp_after:wN \__fp_parse_large_leading:wwNN
10656     \__int_value:w 1 \token_to_str:N #1
10657     \exp_after:wN \__fp_parse_digits_vii:N
10658     \tex_roman numeral:D \__fp_parse_expand:w
10659 }
(End definition for \__fp_parse_large:N)

```

`__fp_parse_large_leading:wwNN` We shift the exponent by the number of digits in `#1`, namely the target number, 8, minus the *⟨number of zeros⟩* (number of digits missing). Then prepare to pack the 8 first digits. If the *⟨next token⟩* is a digit, read up to 6 more digits (digits 10 to 15). If it is a period, try to grab the end of our 8 first digits, branching to the `small` functions since the number of digit does not affect the exponent anymore. Finally, if this is the end of the significand, insert the *⟨zeros⟩* to complete the 8 first digits, insert 8 more, and look for an exponent.

```

10660 \cs_new:Npn \__fp_parse_large_leading:wwNN 1 #1 ; #2; #3 #4
10661 {
10662     + \c_eight - #3
10663     \exp_after:wN \__fp_parse_pack_leading:NNNNNww
10664     \int_use:N \__int_eval:w 1 #1
10665     \if_int_compare:w \c_nine < 1 \token_to_str:N #4 \exp_stop_f:
10666     \exp_after:wN \__fp_parse_large_trailing:wwNN
10667     \__int_value:w 1 \token_to_str:N #4
10668     \exp_after:wN \__fp_parse_digits_vii:N
10669     \tex_roman numeral:D
10670 \else:
10671     \if:w . #4

```

```

10672           \exp_after:wN \_fp_parse_small_leading:wwNN
10673           \_int_value:w 1
10674             \cs:w
10675               __fp_parse_digits_
10676               \tex_roman numeral:D #3
10677                 :N \exp_after:wN
10678                   \cs_end:
10679                     \tex_roman numeral:D
10680           \else:
10681             #2
10682               \exp_after:wN \_fp_parse_pack_trailing:NNNNNNww
10683               \exp_after:wN \c_zero
10684               \_int_value:w 1 0000 0000
10685               \_fp_parse_exponent:Nw #4
10686             \fi:
10687           \fi:
10688           \_fp_parse_expand:w
10689       }

```

(End definition for `_fp_parse_large_leading:wwNN`)

We have just read 15 digits. If the `<next token>` is a digit, then the exponent shift caused by this block of 8 digits is 8, first argument to the `pack_trailing` function. We keep the `<digits>` and this 16-th digit, and find how this should be rounded using `_fp_parse_large_round:NN`. Otherwise, the exponent shift is the number of `<digits>`, 7 minus the `<number of zeros>`, and we test for a decimal point. This case happens in 123451234512345.67 with exactly 15 digits before the decimal separator. Then branch to the appropriate `small` auxiliary, grabbing a few more digits to complement the digits we already grabbed. Finally, if this is truly the end of the significand, look for an exponent after using the `<zeros>` and providing a 16-th digit of 0.

```

10690   \cs_new:Npn \_fp_parse_large_trailing:wwNN 1 #1 ; #2; #3 #4
10691   {
10692     \if_int_compare:w \c_nine < 1 \token_to_str:N #4 \exp_stop_f:
10693       \exp_after:wN \_fp_parse_pack_trailing:NNNNNNww
10694       \exp_after:wN \c_eight
10695       \int_use:N \_int_eval:w 1 #1 \token_to_str:N #4
10696       \exp_after:wN \_fp_parse_large_round:NN
10697       \exp_after:wN #4
10698       \tex_roman numeral:D
10699   \else:
10700     \exp_after:wN \_fp_parse_pack_trailing:NNNNNNww
10701     \int_use:N \_int_eval:w \c_seven - #3 \exp_stop_f:
10702     \int_use:N \_int_eval:w 1 #
10703       \if:w . #4
10704         \exp_after:wN \_fp_parse_small_trailing:wwNN
10705         \_int_value:w 1
10706           \cs:w
10707             __fp_parse_digits_
10708             \tex_roman numeral:D #3
10709               :N \exp_after:wN

```

```

10710           \cs_end:
10711           \tex_roman numeral:D
10712 \else:
10713     #2 0 \__fp_parse_exponent:Nw #4
10714   \fi:
10715 \fi:
10716 \__fp_parse_expand:w
10717 }
(End definition for \__fp_parse_large_trailing:wwNN)

```

30.4.5 Finding the exponent

Expansion is a little bit tricky here, in part because we accept input where multiplication is implicit.

```
\@@_parse:n { 3.2 erf(0.1) }
\@@_parse:n { 3.2 e\l_my_int }
\@@_parse:n { 3.2 \c_pi_fp }
```

The first case indicates that just looking one character ahead for an “e” is not enough, since we would mistake the function `erf` for an exponent of “rf”. An alternative would be to look two tokens ahead and check if what follows is a sign or a digit, considering in that case that we must be finding an exponent. But taking care of the second case requires that we unpack registers after `e`. However, blindly expanding the two tokens ahead completely would break the third example (unpacking is even worse). Indeed, in the course of reading 3.2, `\c_pi_fp` is expanded to `\s__fp __fp_chk:w 1 0 {-1} {3141} ... ;` and `\s__fp` stops the expansion. Expanding two tokens ahead would then force the expansion of `__fp_chk:w` (despite it being protected), and that function tries to produce an error.

What can we do? Really, the reason why this last case breaks is that just as \TeX does, we should read ahead as little as possible. Here, the only case where there may be an exponent is if the first token ahead is `e`. Then we expand (and possibly unpack) the second token — and hopefully that is safe.

`__fp_parse_exponent:Nw`

This auxiliary is convenient to smuggle some material through `\fi:` ending conditional processing. We place those `\fi:` (argument #2) at a very odd place because this allows us to insert `__int_eval:w ...` there if needed.

```

10718 \cs_new:Npn \__fp_parse_exponent:Nw #1 #2 \__fp_parse_expand:w
10719 {
10720   \exp_after:wn ;
10721   \__int_value:w #2 \__fp_parse_exponent:N #1
10722 }
(End definition for \__fp_parse_exponent:Nw)
```

`__fp_parse_exponent:N` This function should be called within an `__int_value:w` expansion (or within an integer expression. It leaves digits of the exponent behind it in the input stream, and terminates the expansion with a semicolon. If there is no `e`, leave an exponent of 0. If there is an `e`, expand the next token to run some tests on it. Namely, if the character code of #1

is greater than that of 9 (largest code valid for an exponent, less than any code valid for an identifier), there was in fact no exponent; otherwise, we search for the sign of the exponent.

```

10723 \cs_new:Npn \__fp_parse_exponent:N #1
10724 {
10725   \if:w e #1
10726     \exp_after:wN \__fp_parse_exponent_ii:N
10727     \tex_roman numeral:D
10728   \else:
10729     0 \__fp_parse_return_semicolon:w #1
10730   \fi:
10731   \__fp_parse_expand:w
10732 }
10733 \cs_new:Npn \__fp_parse_exponent_ii:N #1
10734 {
10735   \if_int_compare:w \if_catcode:w \tex_relax:D #1
10736     \c_zero \else: '#1 \fi: > '9 \exp_stop_f:
10737     0 \exp_after:wN ; \exp_after:wN e
10738   \else:
10739     \exp_after:wN \__fp_parse_exponent_sign:N
10740   \fi:
10741   #1
10742 }
(End definition for \__fp_parse_exponent:N and \__fp_parse_exponent_ii:N)

```

__fp_parse_exponent_sign:N Read signs one by one (if there is any).

```

10743 \cs_new:Npn \__fp_parse_exponent_sign:N #1
10744 {
10745   \if:w + \if:w - #1 + \fi: \token_to_str:N #1
10746     \exp_after:wN \__fp_parse_exponent_sign:N
10747     \tex_roman numeral:D \exp_after:wN \__fp_parse_expand:w
10748   \else:
10749     \exp_after:wN \__fp_parse_exponent_body:N
10750     \exp_after:wN #1
10751   \fi:
10752 }
(End definition for \__fp_parse_exponent_sign:N)

```

__fp_parse_exponent_body:N An exponent can be an explicit integer (most common case), or various other things (most of which are invalid).

```

10753 \cs_new:Npn \__fp_parse_exponent_body:N #1
10754 {
10755   \if_int_compare:w \c_nine < 1 \token_to_str:N #1 \exp_stop_f:
10756     \token_to_str:N #1
10757     \exp_after:wN \__fp_parse_exponent_digits:N
10758     \tex_roman numeral:D
10759   \else:
10760     \__fp_parse_exponent_keep:NTF #1
10761     { \__fp_parse_return_semicolon:w #1 }

```

```

10762     {
10763         \exp_after:wN ;
10764         \tex_roman numeral:D
10765     }
10766     \fi:
10767     \__fp_parse_expand:w
10768 }
```

(End definition for `__fp_parse_exponent_body:N`)

`__fp_parse_exponent_digits:N`

Read digits one by one, and leave them behind in the input stream. When finding a non-digit, stop, and insert a semicolon. Note that we don't check for overflow of the exponent, hence there can be a TeX error. It is mostly harmless, except when parsing `0e9876543210`, which should be a valid representation of 0, but is not.

```

10769 \cs_new:Npn \__fp_parse_exponent_digits:N #1
10770 {
10771     \if_int_compare:w \c_nine < 1 \token_to_str:N #1 \exp_stop_f:
10772         \token_to_str:N #1
10773         \exp_after:wN \__fp_parse_exponent_digits:N
10774         \tex_roman numeral:D
10775     \else:
10776         \__fp_parse_return_semicolon:w #1
10777     \fi:
10778     \__fp_parse_expand:w
10779 }
```

(End definition for `__fp_parse_exponent_digits:N`)

`__fp_parse_exponent_keep:NTF`

This is the last building block for parsing exponents. The argument `#1` is already fully expanded, and neither `+` nor `-` nor a digit. It can be:

- `\s__fp`, marking the start of an internal floating point, invalid here;
- another control sequence equal to `\relax`, probably a bad variable;
- a register: in this case we make sure that it is an integer register, not a dimension;
- a character other than `+`, `-` or digits, again, an error.

```

10780 \prg_new_conditional:Npnn \__fp_parse_exponent_keep:N #1 { TF }
10781 {
10782     \if_catcode:w \tex_relax:D #1
10783     \if_meaning:w \tex_relax:D #1
10784         \if_int_compare:w \pdftex_strcmp:D { \s__fp } { #1 } = \c_zero
10785         0
10786         \__msg_kernel_expandable_error:nnn
10787             { kernel } { fp-after-e } { floating-point- }
10788         \prg_return_true:
10789     \else:
10790         0
10791         \__msg_kernel_expandable_error:nnn
10792             { kernel } { bad-variable } { #1 }
```

```

10793           \prg_return_false:
10794           \fi:
10795           \else:
10796               \if_int_compare:w
10797                   \pdfstrcmp:D { \__int_value:w #1 } { \tex_the:D #1 }
10798                       = \c_zero
10799                   \__int_value:w #1
10800           \else:
10801               0
10802               \__msg_kernel_expandable_error:nnn
10803                   { kernel } { fp-after-e } { dimension~#1 }
10804           \fi:
10805           \prg_return_false:
10806           \fi:
10807           \else:
10808               0
10809               \__msg_kernel_expandable_error:nnn
10810                   { kernel } { fp-missing } { exponent }
10811               \prg_return_true:
10812           \fi:
10813       }

```

(End definition for `__fp_parse_exponent_keep:NTF`)

30.4.6 Beyond 16 digits: rounding

`__fp_cfs_round_loop:N` Used both for `__fp_parse_small_round>NN` and `__fp_parse_large_round>NN`. Should appear after a `__int_eval:w 0`. Reads digits one by one, until reaching a non-digit. Adds `+1` for each digit. If all digits found are 0, ends the `__int_eval:w` by `; \c_zero`, otherwise by `; \c_one`. This is done by switching the loop to `round_up` at the first non-zero digit.

```

10814 \cs_new:Npn \__fp_cfs_round_loop:N #1
10815 {
10816     \if_int_compare:w \c_nine < 1 \token_to_str:N #1 \exp_stop_f:
10817         + \c_one
10818         \if:w 0 #1
10819             \exp_after:wN \__fp_cfs_round_loop:N
10820             \tex_roman numeral:D
10821         \else:
10822             \exp_after:wN \__fp_cfs_round_up:N
10823             \tex_roman numeral:D
10824         \fi:
10825     \else:
10826         \__fp_parse_return_semicolon:w \c_zero #1
10827     \fi:
10828     \__fp_parse_expand:w
10829 }
10830 \cs_new:Npn \__fp_cfs_round_up:N #1
10831 {
10832     \if_int_compare:w \c_nine < 1 \token_to_str:N #1 \exp_stop_f:

```

```

10833     + 1
10834     \exp_after:wN \__fp_cfs_round_up:N
10835     \tex_roman numeral:D
10836 \else:
10837     \__fp_parse_return_semicolon:w \c_one #1
10838 \fi:
10839 \__fp_parse_expand:w
10840 }
(End definition for \__fp_cfs_round_loop:N)

```

__fp_parse_large_round:NN $\langle digit \rangle$ is the digit that we are currently rounding (we only care whether it is even or odd).

The goal is to get \c_zero or \c_one, check for an exponent afterwards, and combine it to the number of digits before the decimal point (which we thus need to keep track of).

```

10841 \cs_new:Npn \__fp_parse_large_round:NN #1#2
10842 {
10843     \if_int_compare:w \c_nine < 1 \token_to_str:N #2 \exp_stop_f:
10844     +
10845     \exp_after:wN \__fp_round_s>NNNw
10846     \exp_after:wN 0
10847     \exp_after:wN #1
10848     \exp_after:wN #2
10849     \int_use:N \__int_eval:w
10850     \exp_after:wN \__fp_parse_large_round_after:wNN
10851     \int_use:N \__int_eval:w \c_one
10852     \exp_after:wN \__fp_cfs_round_loop:N
10853 \else: %^^A could be dot, or e, or other
10854     \exp_after:wN \__fp_parse_large_round_dot_test:NNw
10855     \exp_after:wN #1
10856     \exp_after:wN #2
10857 \fi:
10858 }
10859 \cs_new:Npn \__fp_parse_large_round_dot_test:NNw #1#2
10860 {
10861     \if:w . #2
10862     \exp_after:wN \__fp_parse_small_round:NN
10863     \exp_after:wN #1
10864     \tex_roman numeral:D
10865 \else:
10866     \__fp_parse_exponent:Nw #2
10867 \fi:
10868 \__fp_parse_expand:w
10869 }

10870 \cs_new:Npn \__fp_parse_large_round_after:wNN #1 ; #2 #3
10871 {
10872     \if:w . #3
10873     \exp_after:wN \__fp_parse_large_round_after_ii:wN
10874     \int_use:N \__int_eval:w #1 +
10875     \c_zero * \__int_eval:w \c_zero

```

```

10876           \exp_after:wN \__fp_cfs_round_loop:N
10877           \tex_roman numeral:D \exp_after:wN \__fp_parse_expand:w
10878 \else:
10879   + #2
10880   \exp_after:wN ;
10881   \int_use:N \__int_eval:w #1 +
10882     \exp_after:wN \__fp_parse_exponent:N
10883     \exp_after:wN #3
10884   \fi:
10885 }
10886 \cs_new:Npn \__fp_parse_large_round_after_ii:wN #1 ; #2
10887 {
10888   + #2
10889   \exp_after:wN ;
10890   \int_use:N \__int_eval:w #1 +
10891     \__fp_parse_exponent:N
10892 }

(End definition for \__fp_parse_large_round:NN)

```

__fp_parse_small_round>NN $\langle digit \rangle$ is the digit that we are currently rounding (we only care whether it is even or odd).

The goal is to get \c_zero or \c_one

```

10893 \cs_new:Npn \__fp_parse_small_round>NN #1#2
10894 {
10895   \if_int_compare:w \c_nine < 1 \token_to_str:N #2 \exp_stop_f:
10896     +
10897     \exp_after:wN \__fp_round_s>NNNw
10898     \exp_after:wN 0
10899     \exp_after:wN #1
10900     \exp_after:wN #2
10901     \int_use:N \__int_eval:w
10902       \exp_after:wN \__fp_parse_small_round_after:wN
10903       \int_use:N \__int_eval:w \c_zero
10904         \exp_after:wN \__fp_cfs_round_loop:N
10905         \tex_roman numeral:D
10906 \else:
10907   \__fp_parse_exponent:Nw #2
10908 \fi:
10909   \__fp_parse_expand:w
10910 }
10911 \cs_new:Npn \__fp_parse_small_round_after:wN #1; #2
10912 {
10913   + #2 \exp_after:wN ;
10914   \__int_value:w \__fp_parse_exponent:N
10915 }

(End definition for \__fp_parse_small_round:NN)

```

30.5 Main functions

`__fp_parse:n` Start a `\romannumeral` expansion so that `__fp_parse:n` expands in two steps. The `__fp_parse_until:Nw` function will perform computations until reaching an operation with precedence `\c_minus_one` or less. Then check that there was indeed nothing left (this cannot happen), and stop the initial expansion with `\c_zero`.

```

10916 \cs_new:Npn \__fp_parse:n #1
10917 {
10918   \tex_roman numeral:D
10919     \exp_after:wN \__fp_parse_after:ww
10920     \tex_roman numeral:D
10921       \__fp_parse_until:Nw \c_minus_one
10922       \__fp_parse_expand:w #1 \s_fp_mark
10923       \s_fp_stop
10924   }
10925 \cs_new:Npn \__fp_parse_after:ww #10 #2 \s_fp_stop
10926 {
10927   \assert{ \assert_str_eq:nn { #2 } { \__fp_parse_infix_end:N \s_fp_mark } }
10928   \c_zero #1
10929 }
```

(End definition for `__fp_parse:n` This function is documented on page ??.)

`__fp_parse_until:Nw` The `__fp_parse_until` This is just a shorthand which sets up both `__fp_parse_until` and `__fp_parse_operand` with the same precedence. Note the trailing `\tex_roman numeral:D`. This function should be used with much care.

```

10930 \cs_new:Npn \__fp_parse_until:Nw #1
10931 {
10932   -'0
10933   \exp_after:wN \__fp_parse_until_test:NwN
10934   \exp_after:wN #1
10935   \tex_roman numeral:D -'0
10936   \exp_after:wN \__fp_parse_operand:Nw
10937   \exp_after:wN #1
10938   \tex_roman numeral:D
10939 }
10940 \cs_new:Npn \__fp_parse_until_test:NwN #1 #2 @ #3 { #3 #1 #2 @ }
10941 \cs_new_eq:NN \__fp_parse_stop_until:N \use_none:n
```

(End definition for `__fp_parse_until:Nw` This function is documented on page ??.)

`__fp_parse_until_test:NwN` If $\langle \text{bool} \rangle$ is true, then $\langle fp \rangle$ is the floating point number that we are looking for (it ends with ;), and this expands to $\langle fp \rangle$. If $\langle \text{bool} \rangle$ is false, then the input stream actually looks like

`__fp_parse_until_test:NwN ⟨prec⟩ ⟨fp12`

and we must feed $\langle \text{prec} \rangle$ to `\infix_?`, and perform $\langle \text{oper} \rangle$ on $\langle fp_1 \rangle$ and $\langle fp_2 \rangle$: this triggers the expansion of `\infix_? ⟨prec⟩`, continuing the computation (or stopping). In that case, the function `\until` yields

```
\_\_fp\_parse\_until\_test:NwN <prec> <oper> <fp1> <fp2> \tex\_romannumeral:D
-'0 \infix\_? <prec>
```

expanding $\langle oper \rangle$ next.

(End definition for $__fp_parse_until_test:NwN$)

30.6 Main functions

```
\_\_fp\_parse\_infix\_after\_operand:NwN
10942 \cs_new:Npn \_\_fp\_parse\_infix\_after\_operand:NwN #1 #2;
10943 {
10944     \_\_fp\_exp\_after\_f:nw { \_\_fp\_parse\_infix:NN #1 }
10945     #2;
10946 }
10947 \group_begin:
10948     \char_set_catcode_letter:N \*
10949     \cs_new:Npn \_\_fp\_parse\_infix:NN #1 #2
10950     {
10951         \if_catcode:w \tex_relax:D #2
10952             \if_int_compare:w
10953                 \pdfstrcmp:D { \s_fp_mark } { #2 }
10954                 = \c_zero
10955                 \exp_after:wN \exp_after:wN
10956                 \exp_after:wN \_\_fp\_parse\_infix\_end:N
10957         \else:
10958             \exp_after:wN \exp_after:wN
10959             \exp_after:wN \_\_fp\_parse\_infix\_juxtapose:N
10960         \fi:
10961     \else:
10962         \if_int_compare:w
10963             \int_eval:w \tex_uccode:D '#2 / 26
10964             = \c_three
10965             \exp_after:wN \exp_after:wN
10966             \exp_after:wN \_\_fp\_parse\_infix\_juxtapose:N
10967     \else:
10968         \exp_after:wN \_\_fp\_parse\_infix\_check:NNN
10969         \cs:w
10970             \_\_fp\_parse\_infix\_#2:N
10971             \exp_after:wN \exp_after:wN \exp_after:wN
10972         \cs_end:
10973     \fi:
10974 \fi:
10975 #1
10976 #2
10977 }
10978 \cs_new:Npn \_\_fp\_parse\_infix\_check:NNN #1#2#3
10979 {
10980     \if_meaning:w \tex_relax:D #1
10981         \msg_kernel_expandable_error:nnn { kernel } { fp-missing } { * }
```

```

10982     \exp_after:wN \__fp_parse_infix_*:N
10983     \exp_after:wN #2
10984     \exp_after:wN #3
10985 \else:
10986     \exp_after:wN #1
10987     \exp_after:wN #2
10988     \tex_roman numeral:D \exp_after:wN \__fp_parse_expand:w
10989 \fi:
10990 }
10991 \group_end:
(End definition for \__fp_parse_infix_after_operand:NwN)

```

__fp_parse_apply_binary:NwNwN Receives $\langle precedence \rangle$ $\langle operand_1 \rangle @ \langle operation \rangle \langle operand_2 \rangle @ \langle infix command \rangle$. Builds the appropriate call to the $\langle operation \rangle$ #4, given the types of the two $\langle operands \rangle$.

```

10992 \cs_new:Npn \__fp_parse_apply_binary:NwNwN #1 #2#3@ #4 #5#6@ #7
10993 {
10994     \exp_after:wN \__fp_parse_until_test:NwN
10995     \exp_after:wN #1
10996     \tex_roman numeral:D -'0
10997     \cs:w
10998         __fp
10999         \__fp_type_from_scan:N #2
11000         _ #4
11001         \__fp_type_from_scan:N #5
11002         _o:ww
11003     \cs_end:
11004     #2#3 #5#6
11005     \tex_roman numeral:D -'0 #7 #1
11006 }
(End definition for \__fp_parse_apply_binary:NwNwN)

```

__fp_parse_apply_unary_array>NNwN Here, #2 is *e.g.*, __fp_sin_o:w, and expands once after the calculation.¹⁶ The argument __fp_parse_apply_unary>NNwN #3 may be an array, so either we map through all its items, or we feed all items at once to the custom function.

```

11007 \cs_new:Npn \__fp_parse_apply_unary_array:NNwN #1#2#3@#4
11008 {
11009     #2 #3 @
11010     \tex_roman numeral:D -'0 #4 #1
11011 }
11012 \cs_new:Npn \__fp_parse_apply_unary:NNwN #1#2#3@#4
11013 {
11014     #2 #3
11015     \tex_roman numeral:D -'0 #4 #1
11016 }
11017 \cs_new:Npn \__fp_parse_unary_type:N #1
11018     { \__fp_type_from_scan:N #1 _o:w \cs_end: #1 }
(End definition for \__fp_parse_apply_unary_array:NNwN and \__fp_parse_apply_unary:NNwN)

```

¹⁶Bruno: explain.

30.7 Prefix operators

30.7.1 Identifiers

```

\__fp_parse_word_inf:N
\__fp_parse_word_nan:N
\__fp_parse_word_pi:N
\__fp_parse_word_deg:N
\__fp_parse_word_em:N
\__fp_parse_word_ex:N
\__fp_parse_word_in:N
\__fp_parse_word_pt:N
\__fp_parse_word_pc:N
\__fp_parse_word_cm:N
\__fp_parse_word_mm:N
\__fp_parse_word_dd:N
\__fp_parse_word_cc:N
\__fp_parse_word_nd:N
\__fp_parse_word_nc:N
\__fp_parse_word_bp:N
\__fp_parse_word_sp:N
\__fp_parse_word_true:N
\__fp_parse_word_false:N

A whole bunch of floating point numbers.

11019 \cs_set_protected:Npn \__fp_tmp:w #1 #2
11020 {
11021   \cs_new_nopar:cpn { __fp_parse_word_#1:N }
11022   { \exp_after:wN #2 \tex_roman numeral:D -'0 \__fp_parse_infix:NN }
11023 }
11024 \__fp_tmp:w { inf } \c_inf_fp
11025 \__fp_tmp:w { nan } \c_nan_fp
11026 \__fp_tmp:w { pi } \c_pi_fp
11027 \__fp_tmp:w { deg } \c_one_degree_fp
11028 \__fp_tmp:w { true } \c_one_fp
11029 \__fp_tmp:w { false } \c_zero_fp
11030 \__fp_tmp:w { pt } \c_one_fp
11031 \cs_set_protected:Npn \__fp_tmp:w #1 #2
11032 {
11033   \cs_new_nopar:cpn { __fp_parse_word_#1:N }
11034   {
11035     \__fp_exp_after_f:nw { \__fp_parse_infix:NN }
11036     \s_fp \__fp_chk:w 10 #2 ;
11037   }
11038 }
11039 \__fp_tmp:w {in} { {2} {7227} {0000} {0000} {0000} }
11040 \__fp_tmp:w {pc} { {2} {1200} {0000} {0000} {0000} }
11041 \__fp_tmp:w {cm} { {2} {2845} {2755} {9055} {1181} }
11042 \__fp_tmp:w {mm} { {1} {2845} {2755} {9055} {1181} }
11043 \__fp_tmp:w {dd} { {1} {1070} {0085} {6496} {0630} }
11044 \__fp_tmp:w {cc} { {2} {1284} {0102} {7795} {2756} }
11045 \__fp_tmp:w {nd} { {1} {1066} {9783} {4645} {6693} }
11046 \__fp_tmp:w {nc} { {2} {1280} {3740} {1574} {8031} }
11047 \__fp_tmp:w {bp} { {1} {1003} {7500} {0000} {0000} }
11048 \__fp_tmp:w {sp} { {-4} {1525} {8789} {0625} {0000} }
11049 \tl_map_inline:nn { {em} {ex} }
11050 {
11051   \cs_new_nopar:cpn { __fp_parse_word_#1:N }
11052   {
11053     \exp_after:wN \dim_to_fp:n \exp_after:wN
11054     { \dim_use:N \__dim_eval:w 1 #1 \exp_after:wN }
11055     \tex_roman numeral:D -'0 \__fp_parse_infix:NN
11056   }
11057 }

(End definition for \__fp_parse_word_inf:N and others.)

```

```

\__fp_parse_word_abs:N
\__fp_parse_word_cos:N
\__fp_parse_word_cot:N
\__fp_parse_word_csc:N
\__fp_parse_word_exp:N
\__fp_parse_word_ln:N
\__fp_parse_word_sec:N
\__fp_parse_word_sin:N
\__fp_parse_word_tan:N

Unary functions, which are applied to all of their arguments when receiving an array.

11058 \tl_map_inline:nn
11059 { {abs} {cos} {cot} {csc} {exp} {ln} {sec} {sin} {tan} }
11060 {

```

```

11061 \cs_new:cpn { __fp_parse_word_#1:N } ##1
11062 {
11063   \exp_after:wN \__fp_parse_apply_unary:NNwN
11064   \exp_after:wN ##1
11065   \cs:w __fp_ #1 \exp_after:wN \__fp_parse_unary_type:N
11066   \tex_roman numeral:D
11067   \__fp_parse_until:Nw \c_fifteen
11068   \__fp_parse_expand:w
11069 }
11070 }
11071 (End definition for \__fp_parse_word_abs:N and others.)

```

__fp_parse_word_max:N Those functions are also unary, but need to mix all of their arguments together.

```

\__fp_parse_word_min:N
11071 \cs_set_protected:Npn \__fp_tmp:w #1#2
11072 {
11073   \cs_new:Npn #1 ##1
11074   {
11075     \exp_after:wN \__fp_parse_apply_unary_array:NNwN
11076     \exp_after:wN ##1
11077     \exp_after:wN #2
11078     \tex_roman numeral:D
11079     \__fp_parse_until:Nw \c_sixteen \__fp_parse_expand:w
11080   }
11081 }
11082 \__fp_tmp:w \__fp_parse_word_max:N \__fp_max_o:w
11083 \__fp_tmp:w \__fp_parse_word_min:N \__fp_min_o:w
(End definition for \__fp_parse_word_max:N and \__fp_parse_word_min:N)

```

__fp_parse_word_round:N This function expects one or two arguments.

```

11084 \cs_new:Npn \__fp_parse_word_round:N #1#2
11085 {
11086   \if_meaning:w + #2
11087     \__fp_parse_round:Nw \__fp_round_to_pinf:NNN
11088   \else:
11089     \if_meaning:w 0 #2
11090       \__fp_parse_round:Nw \__fp_round_to_zero:NNN
11091     \else:
11092       \if_meaning:w - #2
11093         \__fp_parse_round:Nw \__fp_round_to_ninf:NNN
11094     \fi:
11095   \fi:
11096   \exp_after:wN \__fp_parse_apply_round:NNwN
11097   \exp_after:wN #1
11098   \exp_after:wN \__fp_round_to_nearest:NNN
11099   \tex_roman numeral:D
11100   \__fp_parse_until:Nw \c_sixteen \__fp_parse_expand:w #2
11101 }
11102 \cs_new:Npn \__fp_parse_round:Nw
11103 
```

```

11104      #1 #2 \__fp_round_to_nearest>NNN #3 \__fp_parse_expand:w #4
11105      { #2 #1 #3 \__fp_parse_expand:w }
11106      \cs_new:Npn \__fp_parse_apply_round:NNwN #1#2#3@#4
11107      {
11108          \if_case:w \__int_eval:w \__fp_array_count:n {#3} - \c_one \__int_eval_end:
11109              \__fp_round:Nnw #2 #3 {0} \tex_roman numeral:D
11110          \or: \__fp_round:Nww #2 #3 \tex_roman numeral:D
11111          \else:
11112              \__msg_kernel_expandable_error:nnnnn
11113                  { kernel } { fp-num-args } { round() } { 1 } { 2 }
11114                  \exp_after:wN \c_nan_fp \tex_roman numeral:D
11115          \fi:
11116          -'0 #4 #1
11117      }

```

(End definition for `__fp_parse_word_round:N`)

30.7.2 Unary minus, plus, not

`__fp_parse_prefix_+:Nw` A unary + does nothing.

```

11118 \cs_new_eq:cN { __fp_parse_prefix_+:Nw } \__fp_parse_operand:Nw
(End definition for \__fp_parse_prefix_+:Nw)

```

`__fp_parse_prefix_-:Nw` Unary - is harder. Boolean not.

```

11119 \cs_set_protected:Npn \__fp_tmp:w #1#2
11120      {
11121          \cs_new:cpn { __fp_parse_prefix_#1:Nw } ##1
11122          {
11123              \exp_after:wN \__fp_parse_apply_unary:NNwN
11124              \exp_after:wN ##1
11125              \cs:w __fp_ #2 \exp_after:wN \__fp_parse_unary_type:N
11126              \tex_roman numeral:D
11127              \if_int_compare:w \c_twelve < ##1
11128                  \__fp_parse_until:Nw ##1
11129              \else:
11130                  \__fp_parse_until:Nw \c_twelve
11131              \fi:
11132              \__fp_parse_expand:w
11133          }
11134      }
11135      \__fp_tmp:w - { - }
11136      \__fp_tmp:w ! { ! }

```

(End definition for `__fp_parse_prefix_-:Nw` and `__fp_parse_prefix_!:Nw`)

30.7.3 Other prefixes

```

\__fp_parse_prefix_(:Nw
11137 \group_begin:
11138     \char_set_catcode_letter:N \
11139     \cs_new:cpn { __fp_parse_prefix_(:Nw } #1

```

```

11140 {
11141   \exp_after:wN \__fp_parse_lparen_after:NwN
11142   \exp_after:wN #1
11143   \tex_roman numeral:D
11144   \if_int_compare:w #1 = \c_sixteen
11145     \__fp_parse_until:Nw \c_one
11146   \else:
11147     \__fp_parse_until:Nw \c_zero
11148   \fi:
11149   \__fp_parse_expand:w
11150 }
11151 \cs_new:Npn \__fp_parse_lparen_after:NwN #1#2@#3
11152 {
11153   \token_if_eq_meaning:NNTF #3 \__fp_parse_infix_):N
11154   {
11155     \__fp_exp_after_array_f:w #2 \s_fp_stop
11156     \exp_after:wN \__fp_parse_infix:NN
11157     \exp_after:wN #1
11158     \tex_roman numeral:D \__fp_parse_expand:w
11159   }
11160   {
11161     \__msg_kernel_expandable_error:nnn { kernel } { fp-missing } { }
11162     #2 @ \__fp_parse_stop_until:N #3
11163   }
11164 }
11165 \group_end:
(End definition for \__fp_parse_prefix_(:Nw))

```

__fp_parse_prefix_.:Nw This function is called when a number starts with a dot.

```

11166 \cs_new:cpn {\__fp_parse_prefix_.:Nw} #1
11167 {
11168   \exp_after:wN \__fp_parse_infix_after_operand:NwN
11169   \exp_after:wN #1
11170   \tex_roman numeral:D -'0
11171   \exp_after:wN \__fp_SANITIZE:wN
11172   \int_use:N \__int_eval:w \c_zero \__fp_parse_strim_zeros:N
11173 }
(End definition for \__fp_parse_prefix_.:Nw)

```

30.8 Infix operators

As described in the “work plan”, each infix operator has an associated \infix function, a computing function, and precedence, given as arguments to __fp_tmp:w. The latter two are only needed when defining the \infix function.

```

11174 \cs_set_protected:Npn \__fp_tmp:w #1#2#3#4
11175 {
11176   \cs_new:Npn #1 ##1
11177   {
11178     \if_int_compare:w ##1 < #3

```

```

11179           \exp_after:wN @
11180           \exp_after:wN \__fp_parse_apply_binary:NwNwN
11181           \exp_after:wN #2
11182           \tex_roman numeral:D
11183           \__fp_parse_until:Nw #4
11184           \exp_after:wN \__fp_parse_expand:w
11185       \else:
11186           \exp_after:wN @
11187           \exp_after:wN \__fp_parse_stop_until:N
11188           \exp_after:wN #1
11189       \fi:
11190   }
11191 }
```

__fp_parse_infix_+:N Using the general mechanism for arithmetic operations.

```

11192 \group_begin:
11193   \char_set_catcode_other:N \&
11194   \__fp_tmp:w \__fp_parse_infix_juxtapose:N * \c_thirty_two \c_thirty_two
11195   \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_ / :N } / \c_ten \c_ten
11196   \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_mul:N } * \c_ten \c_ten
11197   \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_ - :N } - \c_nine \c_nine
11198   \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_ + :N } + \c_nine \c_nine
11199   \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_and:N } & \c_five \c_five
11200   \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_or:N } | \c_four \c_four
11201 \group_end:
```

(End definition for __fp_parse_infix_+:N and others.)

__fp_parse_infix_*:N The power operation must be associative in the opposite order from all others. For this, we reverse the test, hence treating a “previous precedence” of \c_fourteen as less binding than \wedge .

```

11202 \group_begin:
11203   \char_set_catcode_letter:N ^
11204   \__fp_tmp:w \__fp_parse_infix_ ^:N ^ \c_fifteen \c_fourteen
11205   \cs_new:cpn { \__fp_parse_infix_*:N } #1#2
11206   {
11207     \if:w * #2
11208       \exp_after:wN \__fp_parse_infix_ ^:N
11209       \exp_after:wN #1
11210     \else:
11211       \exp_after:wN \__fp_parse_infix_mul:N
11212       \exp_after:wN #1
11213       \exp_after:wN #2
11214     \fi:
11215   }
11216 \group_end:
```

(End definition for __fp_parse_infix_*:N This function is documented on page ??.)

```

\__fp_parse_infix_|:Nw
\__fp_parse_infix_&:Nw
11217 \group_begin:
```

```

11218 \char_set_catcode_letter:N ||
11219 \char_set_catcode_letter:N \&
11220 \cs_new:Npn \__fp_parse_infix_|:N #1#2
11221 {
11222   \if:w | #2
11223     \exp_after:wN \__fp_parse_infix_|:N
11224     \exp_after:wN #1
11225     \tex_roman numeral:D \exp_after:wN \__fp_parse_expand:w
11226   \else:
11227     \exp_after:wN \__fp_parse_infix_or:N
11228     \exp_after:wN #1
11229     \exp_after:wN #2
11230   \fi:
11231 }
11232 \cs_new:Npn \__fp_parse_infix_&:N #1#2
11233 {
11234   \if:w & #2
11235     \exp_after:wN \__fp_parse_infix_&:N
11236     \exp_after:wN #1
11237     \tex_roman numeral:D \exp_after:wN \__fp_parse_expand:w
11238   \else:
11239     \exp_after:wN \__fp_parse_infix_and:N
11240     \exp_after:wN #1
11241     \exp_after:wN #2
11242   \fi:
11243 }
11244 \group_end:
(End definition for \__fp_parse_infix_|:Nw This function is documented on page ??.)
```

```

\__fp_parse_infix_<:N
\__fp_parse_infix_=:N
\__fp_parse_infix_>:N
\__fp_parse_infix_!:>N
  \__fp_parse_infix_excl_aux>NN
  \__fp_parse_infix_excl_error:
\__fp_infix_compare:N
\__fp_parse_compare:NNNNNNw
  \__fp_parse_compare_expand:NNNNNw
\__fp_parse_compare_end:NNNN
  \__fp_compare:wNNNNw
11245 \cs_new:cpn { __fp_parse_infix_<:N } #1
11246 {
11247   \__fp_infix_compare:N #1 \c_one_fp
11248   \c_zero_fp \c_zero_fp \c_zero_fp \c_zero_fp <
11249 }
11250 \cs_new:cpn { __fp_parse_infix_=:N } #1
11251 {
11252   \__fp_infix_compare:N #1 \c_one_fp
11253   \c_zero_fp \c_zero_fp \c_zero_fp \c_zero_fp =
11254 }
11255 \cs_new:cpn { __fp_parse_infix_>:N } #1
11256 {
11257   \__fp_infix_compare:N #1 \c_one_fp
11258   \c_zero_fp \c_zero_fp \c_zero_fp \c_zero_fp >
11259 }
11260 \cs_new:cpn { __fp_parse_infix_!:>N } #1
11261 {
11262   \exp_after:wN \__fp_parse_infix_excl_aux>NN
11263   \exp_after:wN #1 \tex_roman numeral:D \__fp_parse_expand:w
11264 }
```

```

11265 \cs_new:Npn \__fp_parse_infix_excl_aux:NN #1#2
11266 {
11267     \__fp_infix_compare:N #1 \c_zero_fp
11268     \c_one_fp \c_one_fp \c_one_fp \c_one_fp #2
11269 }
11270 \cs_new:Npn \__fp_parse_infix_excl_error:
11271 {
11272     \__msg_kernel_expandable_error:nnnn
11273     { kernel } { fp-missing } { = } { ~after~!. }
11274 }
11275 \cs_new:Npn \__fp_infix_compare:N #1
11276 {
11277     \if_int_compare:w #1 < \c_seven
11278         \exp_after:wN \__fp_parse_compare:NNNNNNw
11279         \exp_after:wN \__fp_parse_infix_excl_error:
11280     \else:
11281         \exp_after:wN @
11282         \exp_after:wN \__fp_parse_stop_until:N
11283         \exp_after:wN \__fp_infix_compare:N
11284     \fi:
11285 }
11286 \cs_new:Npn \__fp_parse_compare:NNNNNNw #1#2#3#4#5#6#7
11287 {
11288     \if_case:w
11289         \if_catcode:w \tex_relax:D #7
11290         \c_minus_one
11291     \else:
11292         \__int_eval:w '#7 - '< \__int_eval_end:
11293         \fi:
11294         \__fp_parse_compare_expand:NNNNNNw #2#2#4#5#6
11295     \or: \__fp_parse_compare_expand:NNNNNNw #2#3#2#5#6
11296     \or: \__fp_parse_compare_expand:NNNNNNw #2#3#4#2#6
11297     \or: \__fp_parse_compare_expand:NNNNNNw #2#3#4#5#2
11298     \else: #1 \__fp_parse_compare_end:NNNN #3#4#5#6#7
11299     \fi:
11300 }
11301 \cs_new:Npn \__fp_parse_compare_expand:NNNNNNw #1#2#3#4#5
11302 {
11303     \exp_after:wN \__fp_parse_compare:NNNNNNw
11304     \exp_after:wN \prg_do_nothing:
11305     \exp_after:wN #1
11306     \exp_after:wN #2
11307     \exp_after:wN #3
11308     \exp_after:wN #4
11309     \exp_after:wN #5
11310     \tex_roman numeral:D \exp_after:wN \__fp_parse_expand:w
11311 }
11312 \cs_new:Npn \__fp_parse_compare_end:NNNN #1#2#3#4#5 \fi:
11313 {
11314     \fi:

```

```

11315   \exp_after:wN @
11316   \exp_after:wN \__fp_parse_apply_compare:NwNNNNwN
11317   \exp_after:wN #1
11318   \exp_after:wN #2
11319   \exp_after:wN #3
11320   \exp_after:wN #4
11321   \tex_roman numeral:D
11322   \__fp_parse_until:Nw \c_seven \__fp_parse_expand:w #5
11323 }
11324 \cs_new:Npn \__fp_parse_apply_compare:NwNNNNwN #1 #20 #3#4#5#6 #70 #8
11325 {
11326   \exp_after:wN \__fp_parse_until_test:NwN
11327   \exp_after:wN #1
11328   \tex_roman numeral:D -'0
11329     \exp_after:wN \exp_after:wN
11330     \exp_after:wN \exp_after:wN
11331     \exp_after:wN \exp_after:wN
11332     \if_case:w \__fp_compare_back:ww #7 #2 \exp_stop_f:
11333       #4
11334     \or: #5
11335     \or: #6
11336     \else: #3
11337     \fi:
11338   \tex_roman numeral:D -'0 #8 #1
11339 }

```

(End definition for `__fp_parse_infix_<:N` and others. These functions are documented on page ??.)

```

\__fp_parse_infix_?:N
\__fp_parse_infix_::N
11340 \group_begin:
11341   \char_set_catcode_letter:N \?
11342   \cs_new:Npn \__fp_parse_infix_?:N #1
11343   {
11344     \if_int_compare:w #1 < \c_three
11345       \exp_after:wN @
11346       \exp_after:wN \__fp_ternary:NwwN
11347       \tex_roman numeral:D
11348       \__fp_parse_until:Nw \c_three
11349       \exp_after:wN \__fp_parse_expand:w
11350     \else:
11351       \exp_after:wN @
11352       \exp_after:wN \__fp_parse_stop_until:N
11353       \exp_after:wN \__fp_parse_infix_?:N
11354     \fi:
11355   }
11356   \cs_new:Npn \__fp_parse_infix_::N #1
11357   {
11358     \if_int_compare:w #1 < \c_three
11359       \__msg_kernel_expandable_error:nnnn
11360         { kernel } { fp-missing } { ? } { ~for~?: }
11361     \exp_after:wN @

```

```

11362      \exp_after:wN \__fp_ternary_ii:NwwN
11363      \tex_roman numeral:D
11364      \__fp_parse_until:Nw \c_two
11365      \exp_after:wN \__fp_parse_expand:w
11366      \else:
11367          \exp_after:wN @
11368          \exp_after:wN \__fp_parse_stop_until:N
11369          \exp_after:wN \__fp_parse_infix_::N
11370      \fi:
11371  }
11372 \group_end:
(End definition for \__fp_parse_infix_?:N and \__fp_parse_infix_::N)

\__fp_parse_infix_):N This one is a little bit odd: force every previous operator to end, regardless of the precedence. This is very similar to \__fp_parse_infix_end:N.

11373 \group_begin:
11374     \char_set_catcode_letter:N \
11375     \cs_new:Npn \__fp_parse_infix_):N #1
11376     {
11377         \if_int_compare:w #1 < \c_zero
11378             \__msg_kernel_expandable_error:nnn { kernel } { fp-extra } { }
11379             \exp_after:wN \__fp_parse_infix:NN
11380             \exp_after:wN #1
11381             \tex_roman numeral:D \exp_after:wN \__fp_parse_expand:w
11382         \else:
11383             \exp_after:wN @
11384             \exp_after:wN \__fp_parse_stop_until:N
11385             \exp_after:wN \__fp_parse_infix_):N
11386         \fi:
11387     }
11388 \group_end:
11389 \cs_new:Npn \__fp_parse_infix_end:N #1
11390 { @ \__fp_parse_stop_until:N \__fp_parse_infix_end:N }
(End definition for \__fp_parse_infix_):N)

\__fp_parse_infix_
:N
11391 \group_begin:
11392     \char_set_catcode_letter:N ,
11393     \cs_new:Npn \__fp_parse_infix_,:N #1
11394     {
11395         \if_int_compare:w #1 > \c_one
11396             \exp_after:wN @
11397             \exp_after:wN \__fp_parse_stop_until:N
11398             \exp_after:wN \__fp_parse_infix_,:N
11399         \else:
11400             \if_int_compare:w #1 = \c_one
11401                 \exp_after:wN \__fp_parse_infix_comma:w
11402                 \tex_roman numeral:D
11403             \else:

```

```

11404      \exp_after:wN \__fp_parse_infix_comma_gobble:w
11405      \tex_roman numeral:D
11406      \fi:
11407      \__fp_parse_until:Nw \c_one
11408      \exp_after:wN \__fp_parse_expand:w
11409      \fi:
11410      }
11411 \cs_new:Npn \__fp_parse_infix_comma:w #1 @
11412   { #1 @ \__fp_parse_stop_until:N }
11413 \cs_new:Npn \__fp_parse_infix_comma_gobble:w #1 @
11414   {
11415     \__msg_kernel_expandable_error:nn { kernel } { fp-extra-comma }
11416     @ \__fp_parse_stop_until:N
11417   }
11418 \group_end:
(End definition for \__fp_parse_infix_ and :N)

```

31 Messages

```

11419 \__msg_kernel_new:nnn { kernel } { unknown-fp-word }
11420   { Unknown~fp~word~#1. }
11421 \__msg_kernel_new:nnn { kernel } { fp-missing }
11422   { Missing~#1~inserted~#2. }
11423 \__msg_kernel_new:nnn { kernel } { fp-extra }
11424   { Extra~#1~ignored. }
11425 \__msg_kernel_new:nnn { kernel } { fp-early-end }
11426   { Premature~end~in~fp~expression. }
11427 \__msg_kernel_new:nnn { kernel } { fp-after-e }
11428   { Cannot~use~#1~after~'e'. }
11429 \__msg_kernel_new:nnn { kernel } { fp-missing-number }
11430   { Missing~number~before~#1. }
11431 \__msg_kernel_new:nnn { kernel } { fp-unknown-symbol }
11432   { Unknown~symbol~#1~ignored. }
11433 \__msg_kernel_new:nnn { kernel } { fp-extra-comma }
11434   { Unexpected~comma:~extra~arguments~ignored. }
11435 \__msg_kernel_new:nnn { kernel } { fp-num-args }
11436   { #1~expects~between~#2~and~#3~arguments. }
11437 
```

32 l3fp-logic Implementation

```

11438 {*initex | package}
11439 <@=fp>

```

32.1 Syntax of internal functions

- __fp_compare_npos:nwnw {*expo₁*} {*body₁*} ; {*expo₂*} {*body₂*} ;
- __fp_max_o:w {*floating point array*}

- `__fp_min_o:w` *(floating point array)*
- `__fp_!_o:w` *(floating point)*
- `__fp_&_o:ww` *(floating point)* *(floating point)*
- `__fp_|_o:ww` *(floating point)* *(floating point)*
- `__fp_ternary:NwwN`, `__fp_ternary_i:NwwN`, `__fp_ternary_ii:NwwN` have to be understood.

32.2 Existence test

`\fp_if_exist_p:N`

`\fp_if_exist_p:c`

`\fp_if_exist:NTF`

`\fp_if_exist:cTF`

Copies of the `cs` functions defined in `I3basics`.

```

11440 \cs_new_eq:NN \fp_if_exist:NTF \cs_if_exist:NTF
11441 \cs_new_eq:NN \fp_if_exist:NT \cs_if_exist:NT
11442 \cs_new_eq:NN \fp_if_exist:NF \cs_if_exist:NF
11443 \cs_new_eq:NN \fp_if_exist_p:N \cs_if_exist_p:N
11444 \cs_new_eq:NN \fp_if_exist:cTF \cs_if_exist:cTF
11445 \cs_new_eq:NN \fp_if_exist:cT \cs_if_exist:cT
11446 \cs_new_eq:NN \fp_if_exist:cF \cs_if_exist:cF
11447 \cs_new_eq:NN \fp_if_exist_p:c \cs_if_exist_p:c

```

(End definition for `\fp_if_exist:N` and `\fp_if_exist:c`. These functions are documented on page ??.)

32.3 Comparison

`\fp_compare_p:n`

`\fp_compare:nTF`

`__fp_compare_return:w`

Within floating point expressions, comparison operators are treated as operations, so we evaluate #1, then compare with 0.

```

11448 \prg_new_conditional:Npnn \fp_compare:n #1 { p , T , F , TF }
11449 {
11450   \exp_after:wN \__fp_compare_return:w
11451   \tex_roman numeral:D -`0 \__fp_parse:n {#1}
11452 }
11453 \cs_new:Npn \__fp_compare_return:w \s__fp \__fp_chk:w #1#2;
11454 {
11455   \if_meaning:w 0 #1
11456     \prg_return_false:
11457   \else:
11458     \prg_return_true:
11459   \fi:
11460 }

```

(End definition for `\fp_compare:n`. These functions are documented on page ??.)

`\fp_compare_p:nNn`

`\fp_compare:nNnTF`

`__fp_compare_aux:wn`

Evaluate #1 and #3, using an auxiliary to expand both, and feed the two floating point numbers swapped to `__fp_compare_back:ww`, defined below. Compare the result with '`#2-`=`', which is -1 for <, 0 for =, 1 for > and 2 for ?.

```

11461 \prg_new_conditional:Npnn \fp_compare:nNn #1#2#3 { p , T , F , TF }
11462 {
11463   \if_int_compare:w

```

```

11464     \exp_after:wN \__fp_compare_aux:wn
11465         \tex_roman numeral:D -'0 \__fp_parse:n {#1} {#3}
11466 = \__int_eval:w '#2 - '=' \__int_eval_end:
11467 \prg_return_true:
11468 \else:
11469     \prg_return_false:
11470 \fi:
11471 }
11472 \cs_new:Npn \__fp_compare_aux:wn #1; #2
11473 {
11474     \exp_after:wN \__fp_compare_back:ww
11475         \tex_roman numeral:D -'0 \__fp_parse:n {#2} #1;
11476 }

```

(End definition for `\fp_compare:nNn` These functions are documented on page 168.)

`__fp_compare_back:ww`
`__fp_compare_nan:w`

Expands (in the same way as `\int_eval:n`) to -1 if $x < y$, 0 if $x = y$, 1 if $x > y$, and 2 otherwise (denoted as $x?y$). If either operand is `nan`, stop the comparison with `__fp_compare_nan:w` returning 2 . If x is negative, swap the outputs 1 and -1 (*i.e.*, $>$ and $<$); we can henceforth assume that $x \geq 0$. If $y \geq 0$, and they have the same type, either they are normal and we compare them with `__fp_compare_npos:nwnw`, or they are equal. If $y \geq 0$, but of a different type, the highest type is a larger number. Finally, if $y \leq 0$, then $x > y$, unless both are zero.

```

11477 \cs_new:Npn \__fp_compare_back:ww
11478     \s_fp \__fp_chk:w #1 #2 #3;
11479     \s_fp \__fp_chk:w #4 #5 #6;
11480 {
11481     \__int_value:w
11482     \if_meaning:w 3 #1 \exp_after:wN \__fp_compare_nan:w \fi:
11483     \if_meaning:w 3 #4 \exp_after:wN \__fp_compare_nan:w \fi:
11484     \if_meaning:w 2 #5 - \fi:
11485     \if_meaning:w #2 #5
11486         \if_meaning:w #1 #4
11487             \if_meaning:w 1 #1
11488                 \__fp_compare_npos:nwnw #6; #3;
11489             \else:
11490                 0
11491             \fi:
11492         \else:
11493             \if_int_compare:w #4 < #1 - \fi: 1
11494         \fi:
11495     \else:
11496         \if_int_compare:w #1#4 = \c_zero
11497             0
11498         \else:
11499             1
11500         \fi:
11501     \fi:
11502 \exp_stop_f:

```

```

11503   }
11504 \cs_new:Npn \__fp_compare_nan:w #1 \exp_stop_f: { \c_two }
(End definition for \__fp_compare_back:ww and \__fp_compare_nan:w)

```

__fp_compare_npos:nwnw
__fp_compare_significand:nnnnnnnn

__fp_compare_npos:nwnw { $\langle expo_1 \rangle$ } { $\langle body_1 \rangle$ } ; { $\langle expo_2 \rangle$ } { $\langle body_2 \rangle$ } ;

Within an `__int_value:w ... \exp_stop_f:` construction, this expands to 0 if the two numbers are equal, -1 if the first is smaller, and 1 if the first is bigger. First compare the exponents: the larger one denotes the larger number. If they are equal, we must compare significands. If both the first 8 digits and the next 8 digits coincide, the numbers are equal. If only the first 8 digits coincide, the next 8 decide. Otherwise, the first 8 digits are compared.

```

11505 \cs_new:Npn \__fp_compare_npos:nwnw #1#2; #3#4;
11506 {
11507   \if_int_compare:w #1 = #3 \exp_stop_f:
11508     \__fp_compare_significand:nnnnnnnn #2 #4
11509   \else:
11510     \if_int_compare:w #1 < #3 - \fi: 1
11511     \fi:
11512   }
11513 \cs_new:Npn \__fp_compare_significand:nnnnnnnn #1#2#3#4#5#6#7#8
11514 {
11515   \if_int_compare:w #1#2 = #5#6 \exp_stop_f:
11516     \if_int_compare:w #3#4 = #7#8 \exp_stop_f:
11517       0
11518     \else:
11519       \if_int_compare:w #3#4 < #7#8 - \fi: 1
11520     \fi:
11521   \else:
11522     \if_int_compare:w #1#2 < #5#6 - \fi: 1
11523   \fi:
11524 }

```

(End definition for __fp_compare_npos:nwnw This function is documented on page ??.)

32.4 Floating point expression loops

\fp_do_until:nn
\fp_do_while:nn
\fp_until_do:nn
\fp_while_do:nn

These are quite easy given the above functions. The `do_until` and `do_while` versions execute the body, then test. The `until_do` and `while_do` do it the other way round.

```

11525 \cs_new:Npn \fp_do_until:nn #1#2
11526 {
11527   #2
11528   \fp_compare:nF {#1}
11529     { \fp_do_until:nn {#1} {#2} }
11530   }
11531 \cs_new:Npn \fp_do_while:nn #1#2
11532 {
11533   #2
11534   \fp_compare:nT {#1}
11535     { \fp_do_while:nn {#1} {#2} }

```

```

11536   }
11537 \cs_new:Npn \fp_until_do:nn #1#2
11538 {
11539   \fp_compare:nF {#1}
11540   {
11541     #2
11542     \fp_until_do:nn {#1} {#2}
11543   }
11544 }
11545 \cs_new:Npn \fp_while_do:nn #1#2
11546 {
11547   \fp_compare:nT {#1}
11548   {
11549     #2
11550     \fp_while_do:nn {#1} {#2}
11551   }
11552 }

```

(End definition for `\fp_do_until:nn` and others. These functions are documented on page 169.)

`\fp_do_until:nNn`

As above but not using the nNn syntax.

```

11553 \cs_new:Npn \fp_do_until:nNnn #1#2#3#4
11554 {
11555   #4
11556   \fp_compare:nNnF {#1} #2 {#3}
11557   { \fp_do_until:nNnn {#1} #2 {#3} {#4} }
11558 }
11559 \cs_new:Npn \fp_do_while:nNnn #1#2#3#4
11560 {
11561   #4
11562   \fp_compare:nNnT {#1} #2 {#3}
11563   { \fp_do_while:nNnn {#1} #2 {#3} {#4} }
11564 }
11565 \cs_new:Npn \fp_until_do:nNnn #1#2#3#4
11566 {
11567   \fp_compare:nNnF {#1} #2 {#3}
11568   {
11569     #4
11570     \fp_until_do:nNnn {#1} #2 {#3} {#4}
11571   }
11572 }
11573 \cs_new:Npn \fp_while_do:nNnn #1#2#3#4
11574 {
11575   \fp_compare:nNnT {#1} #2 {#3}
11576   {
11577     #4
11578     \fp_while_do:nNnn {#1} #2 {#3} {#4}
11579   }
11580 }

```

(End definition for `\fp_do_until:nNnn` and others. These functions are documented on page 169.)

32.5 Extrema

`_fp_max_o:w` The maximum (minimum) of an array of floating point numbers is computed by reading them sequentially, keeping track of the largest (smallest) number found so far. We start with $-\infty$ (∞) since every number is larger (smaller) than that. The weird fp-like trailing marker breaks the loop correctly: see the precise definition of `_fp_minmax_loop:Nww`.

```

11581 \cs_new:Npn \_fp_max_o:w #1 @
11582 {
11583     \exp_after:wn \_fp_minmax_loop:Nww
11584     \exp_after:wn \c_minus_one
11585     \c_minus_inf_fp
11586     #1
11587     \s_fp \_fp_chk:w { 3 \_fp_minmax_break_o:w } ;
11588 }
11589 \cs_new:Npn \_fp_min_o:w #1 @
11590 {
11591     \exp_after:wn \_fp_minmax_loop:Nww
11592     \exp_after:wn \c_one
11593     \c_inf_fp
11594     #1
11595     \s_fp \_fp_chk:w { 3 \_fp_minmax_break_o:w } ;
11596 }
```

(End definition for `_fp_max_o:w` and `_fp_min_o:w`)

`_fp_minmax_loop:Nww` The first argument is -1 or 1 to denote the case where the currently largest (smallest) number found (first floating point argument) should be replaced by the new number (second floating point argument). If the new number is `nan`, keep that as the extremum, unless that extremum is already a `nan`. Otherwise, compare the two numbers. If the new number is larger (in the case of `max`) or smaller (in the case of `min`), the test yields `true`, and we keep the second number as a new maximum; otherwise we keep the first number. Then loop.

```

11597 \cs_new:Npn \_fp_minmax_loop:Nww
11598     #1 \s_fp \_fp_chk:w #2#3; \s_fp \_fp_chk:w #4#5;
11599 {
11600     \if_meaning:w 3 #4
11601         \if_meaning:w 3 #2
11602             \_fp_minmax_i:ww
11603         \else:
11604             \_fp_minmax_ii:ww
11605         \fi:
11606     \else:
11607         \if_int_compare:w
11608             \_fp_compare_back:ww
11609                 \s_fp \_fp_chk:w #4#5;
11610                 \s_fp \_fp_chk:w #2#3;
11611                 = #1
11612             \_fp_minmax_ii:ww
11613         \else:
11614             \_fp_minmax_i:ww
```

```

11615     \fi:
11616     \fi:
11617     \__fp_minmax_loop:Nww #1
11618     \s_fp \__fp_chk:w #2#3;
11619     \s_fp \__fp_chk:w #4#5;
11620 }
(End definition for \__fp_minmax_loop:Nww)

```

Keep the first/second number, and remove the other.

```

11621 \cs_new:Npn \__fp_minmax_i:ww #1 \fi: \fi: #2 \s_fp #3 ; \s_fp #4;
11622   { \fi: \fi: #2 \s_fp #3 ; }
11623 \cs_new:Npn \__fp_minmax_ii:ww #1 \fi: \fi: #2 \s_fp #3 ;
11624   { \fi: \fi: #2 }
(End definition for \__fp_minmax_i:ww and \__fp_minmax_ii:ww)

```

__fp_minmax_break_o:w

This function is called from within an \if_meaning:w test. Skip to the end of the tests, close the current test with \fi:, clean up, and return the appropriate number with one post-expansion.

```

11625 \cs_new:Npn \__fp_minmax_break_o:w #1 \fi: \fi: #2 \s_fp #3; #4;
11626   { \fi: \__fp_exp_after_o:w \s_fp #3; }
(End definition for \__fp_minmax_break_o:w)

```

32.6 Boolean operations

__fp_!_o:w Return `true` or `false`, with two expansions, one to exit the conditional, and one to please l3fp-parse.

```

11627 \cs_new:cpn { __fp_!_o:w } \s_fp \__fp_chk:w #1#2;
11628   {
11629     \if_meaning:w 0 #1
11630       \exp_after:wN \exp_after:wN \exp_after:wN \c_one_fp
11631     \else:
11632       \exp_after:wN \exp_after:wN \exp_after:wN \c_zero_fp
11633     \fi:
11634   }
(End definition for \__fp_!_o:w)

```

__fp_&_o:ww
__fp_|_o:ww
__fp_and_return:wNw

For `and`, if the first number is zero, return it (with the same sign). Otherwise, return the second one. For `or`, the logic is reversed: if the first number is non-zero, return it, otherwise return the second number: we achieve that by hi-jacking __fp_&_o:ww, inserting an extra argument, \else:, before \s_fp. In all cases, expand after the floating point number.

```

11635 \group_begin:
11636   \char_set_catcode_letter:N &
11637   \char_set_catcode_letter:N |
11638   \cs_new:Npn \__fp_&_o:ww #1 \s_fp \__fp_chk:w #2#3;
11639   {
11640     \if_meaning:w 0 #2 #1
11641       \__fp_and_return:wNw \s_fp \__fp_chk:w #2#3;

```

```

11642     \fi:
11643     \__fp_exp_after_o:w
11644   }
11645   \cs_new_nopar:Npn \__fp_!_o:ww { \__fp_&_o:ww \else: }
11646 \group_end:
11647 \cs_new:Npn \__fp_and_return:wNw #1; \fi: #2#3; { \fi: #2 #1; }
(End definition for \__fp_&_o:ww This function is documented on page ??.)
```

32.7 Ternary operator

The first function receives the test and the true branch of the ?: ternary operator. It returns the true branch, unless the test branch is zero. In that case, the function returns a very specific `nan`. The second function receives the output of the first function, and the false branch. It returns the previous input, unless that is the special `nan`, in which case we return the false branch.

```

11648 \cs_new:Npn \__fp_ternary:NwwN #1 #20 #30 #4
11649 {
11650   \if_meaning:w \__fp_parse_infix_::N #4
11651     \__fp_ternary_loop:Nw
11652       #2
11653       \s__fp \__fp_chk:w { \__fp_ternary_loop_break:w } ;
11654     \__fp_ternary_break_point:n { \exp_after:wN \__fp_ternary_i:NwwN }
11655     \exp_after:wN #1
11656     \tex_roman numeral:D -'0
11657     \__fp_exp_after_array_f:w #3 \s__fp_stop
11658     \exp_after:wN @
11659     \tex_roman numeral:D
11660       \__fp_parse_until:Nw \c_two
11661       \__fp_parse_expand:w
11662   \else:
11663     \__msg_kernel_expandable_error:nnnn
11664       { kernel } { fp-missing } { : } { ~for~? : }
11665     \exp_after:wN \__fp_parse_until_test:NwN
11666     \exp_after:wN #1
11667     \tex_roman numeral:D -'0
11668     \__fp_exp_after_array_f:w #3 \s__fp_stop
11669     \exp_after:wN #4
11670     \exp_after:wN #1
11671   \fi:
11672 }
11673 \cs_new:Npn \__fp_ternary_loop_break:w #1 \fi: #2 \__fp_ternary_break_point:n #3
11674 {
11675   \c_zero = \c_zero \fi:
11676   \exp_after:wN \__fp_ternary_ii:NwwN
11677 }
11678 \cs_new:Npn \__fp_ternary_loop:Nw \s__fp \__fp_chk:w #1#2;
11679 {
11680   \if_int_compare:w #1 > \c_zero
11681     \exp_after:wN \__fp_ternary_map_break:
```

```

11682     \fi:
11683     \__fp_ternary_loop:Nw
11684   }
11685 \cs_new:Npn \__fp_ternary_map_break: #1 \__fp_ternary_break_point:n #2 {#2}
11686 \cs_new:Npn \__fp_ternary_i:NwwN #1#2@#3@#4
11687   {
11688     \exp_after:wn \__fp_parse_until_test:NwN
11689     \exp_after:wn #1
11690     \tex_roman numeral:D -`0
11691     \__fp_exp_after_array_f:w #2 \s__fp_stop
11692     #4 #1
11693   }
11694 \cs_new:Npn \__fp_ternary_ii:NwwN #1#2@#3@#4
11695   {
11696     \exp_after:wn \__fp_parse_until_test:NwN
11697     \exp_after:wn #1
11698     \tex_roman numeral:D -`0
11699     \__fp_exp_after_array_f:w #3 \s__fp_stop
11700     #4 #1
11701   }
(End definition for \__fp_ternary:NwwN, \__fp_ternary_i:NwwN, and \__fp_ternary_ii:NwwN These
functions are documented on page ??.)
11702 </initex | package>

```

33 l3fp-basics Implementation

```

11703 <*initex | package>
11704 <@=fp>

```

The l3fp-basics module implements addition, subtraction, multiplication, and division of two floating points, and the absolute value and sign-changing operations on one floating point. All operations implemented in this module yield the outcome of rounding the infinitely precise result of the operation to the nearest floating point.

Some algorithms used below end up being quite similar to some described in “What Every Computer Scientist Should Know About Floating Point Arithmetic”, by David Goldberg, which can be found at <http://cr.yp.to/2005-590/goldberg.pdf>.

33.1 Common to several operations

Addition and multiplication of significands are done in two steps: first compute a (more or less) exact result, then round and pack digits in the final (braced) form. These functions take care of the packing, with special attention given to the case where rounding has caused a carry. Since rounding can only shift the final digit by 1, a carry always produces an exact power of 10. Thus, __fp_basics_pack_high_carry:w is always followed by four times {0000}.

```

11705 \cs_new:Npn \__fp_basics_pack_low:NNNNNw #1 #2#3#4#5 #6;
11706   {
11707     \if_meaning:w 2 #1

```

```

11708     + \c_one
11709     \fi:
11710     ; {#2#3#4#5} {#6} ;
11711   }
11712 \cs_new:Npn \_fp_basics_pack_high:NNNNNw #1 #2#3#4#5 #6;
11713 {
11714   \if_meaning:w 2 #1
11715     \_fp_basics_pack_high_carry:w
11716   \fi:
11717   ; {#2#3#4#5} {#6}
11718 }
11719 \cs_new:Npn \_fp_basics_pack_high_carry:w \fi: ; #1
11720   { \fi: + \c_one ; {1000} }
(End definition for \_fp_basics_pack_low:NNNNNw, \_fp_basics_pack_high:NNNNNw, and \_fp_basics_pack_high_carry:w)

```

`_fp_basics_pack_weird_low:NNNNw`
`_fp_basics_pack_weird_high:NNNNNNNw`

I don't fully understand those functions, used for additions and divisions. Hence the name.

```

11721 \cs_new:Npn \_fp_basics_pack_weird_low:NNNNw #1 #2#3#4 #5;
11722 {
11723   \if_meaning:w 2 #1
11724     + \c_one
11725   \fi:
11726   \_int_eval_end:
11727   #2#3#4; {#5} ;
11728 }
11729 \cs_new:Npn \_fp_basics_pack_weird_high:NNNNNNNw
11730   1 #1#2#3#4 #5#6#7#8 #9; { ; {#1#2#3#4} {#5#6#7#8} {#9} }
(End definition for \_fp_basics_pack_weird_low:NNNNw and \_fp_basics_pack_weird_high:NNNNNNNw)

```

33.2 Addition and subtraction

We define here two functions, `_fp_-_o:ww` and `_fp+_o:ww`, which perform the subtraction and addition of their two floating point operands, and expand the tokens following the result once.

A more obscure function, `_fp_add_big_i_o:wNww`, is used in l3fp-expo.

The logic goes as follows:

- `_fp_-_o:ww` calls `_fp+_o:ww` to do the work, with the sign of the second operand flipped;
- `_fp+_o:ww` dispatches depending on the type of floating point, calling specialized auxiliaries;
- in all cases except summing two normal floating point numbers, we return one or the other operands depending on the signs, or detect an invalid operation in the case of $\infty - \infty$;
- for normal floating point numbers, compare the signs;

- to add two floating point numbers of the same sign or of opposite signs, shift the significand of the smaller one to match the bigger one, perform the addition or subtraction of significands, check for a carry, round, and pack using the `_fp_basics_pack_...` functions.

The trickiest part is to round correctly when adding or subtracting normal floating point numbers.

33.2.1 Sign, exponent, and special numbers

`_fp_-o:ww` A previous version of this function grabbed its two operands, changed the sign of the second, and called `_fp_+o:ww`. However, for efficiency reasons, the operands were swapped in the process, which means that error messages ended up wrong. Now, the `_fp_+o:ww` auxiliary has a hook: it takes one argument between the first `\s_fp` and `_fp_chk:w`, which is applied to the sign of the second operand. Positioning the hook there means that `_fp_+o:ww` can still check that it was followed by `\s_fp` and not arbitrary junk.

```

11731 \cs_new_nopar:cpx { __fp_-o:ww } \s_fp
11732 {
11733   \exp_not:c { __fp_+o:ww }
11734   \exp_not:n { \s_fp \_fp_neg_sign:N }
11735 }
```

(End definition for `_fp_-o:ww`)

`_fp_+o:ww` This function is either called directly with an empty #1 to compute an addition, or it is called by `_fp_-o:ww` with `_fp_neg_sign:N` as #1 to compute a subtraction (equivalent to changing the $\langle sign_2 \rangle$ of the second operand). If the $\langle types \rangle$ #2 and #4 are the same, dispatch to case #2 (0, 1, 2, or 3), where we call specialized functions: thanks to `_int_value:w`, those receive the tweaked $\langle sign_2 \rangle$ (expansion of #1#5) as an argument. If the $\langle types \rangle$ are distinct, the result is simply the floating point number with the highest $\langle type \rangle$. Since case 3 (used for two `nan`) also picks the first operand, we can also use it when $\langle type_1 \rangle$ is greater than $\langle type_2 \rangle$. Also note that we don't need to worry about $\langle sign_2 \rangle$ in that case since the second operand is discarded.

```

11736 \cs_new:cpn { __fp_+o:ww }
11737   \s_fp #1 \_fp_chk:w #2 #3 ; \s_fp \_fp_chk:w #4 #5
11738 {
11739   \if_case:w
11740     \if_meaning:w #2 #4
11741       #2 \exp_stop_f:
11742     \else:
11743       \if_int_compare:w #2 > #4 \exp_stop_f:
11744         \c_three
11745       \else:
11746         \c_minus_one
11747       \fi:
11748     \fi:
11749     \exp_after:wN \_fp_add_zeros_o:Nww \_int_value:w
11750 \or: \exp_after:wN \_fp_add_normal_o:Nww \_int_value:w
```

```

11751   \or:  \exp_after:wN \_fp_add_inf_o:Nww \_int_value:w
11752   \or:  \_fp_case_return_i_o:ww
11753   \else: \exp_after:wN \_fp_add_return_ii_o:Nww \_int_value:w
11754   \fi:
11755   #1 #5
11756   \s_fp \_fp_chk:w #2 #3 ;
11757   \s_fp \_fp_chk:w #4 #5
11758 }
(End definition for \_fp+_o:ww)

```

_fp_add_return_ii_o:Nww Ignore the first operand, and return the second, but using the sign #1 rather than #4. As usual, expand after the floating point.

```

11759 \cs_new:Npn \_fp_add_return_ii_o:Nww #1 #2 ; \s_fp \_fp_chk:w #3 #4
11760 { \_fp_exp_after_o:w \s_fp \_fp_chk:w #3 #1 }
(End definition for \_fp_add_return_ii_o:Nww)

```

_fp_add_zeros_o:Nww Adding two zeros yields \c_zero_fp, except if both zeros were -0.

```

11761 \cs_new:Npn \_fp_add_zeros_o:Nww #1 \s_fp \_fp_chk:w 0 #2
11762 {
11763   \if_int_compare:w #2 #1 = 20 \exp_stop_f:
11764     \exp_after:wN \_fp_add_return_ii_o:Nww
11765   \else:
11766     \_fp_case_return_i_o:ww
11767   \fi:
11768   #1
11769   \s_fp \_fp_chk:w 0 #2
11770 }
(End definition for \_fp_add_zeros_o:Nww)

```

_fp_add_inf_o:Nww If both infinities have the same sign, just return that infinity, otherwise, it is an invalid operation. We find out if that invalid operation is an addition or a subtraction by testing whether the tweaked $\langle sign_2 \rangle$ (#1) and the $\langle sign_2 \rangle$ (#4) are identical.

```

11771 \cs_new:Npn \_fp_add_inf_o:Nww
11772   #1 \s_fp \_fp_chk:w 2 #2 #3; \s_fp \_fp_chk:w 2 #4
11773 {
11774   \if_meaning:w #1 #2
11775     \_fp_case_return_i_o:ww
11776   \else:
11777     \_fp_case_use:nw
11778   {
11779     \if_meaning:w #1 #4
11780       \exp_after:wN \_fp_invalid_operation_o:Nww
11781       \exp_after:wN +
11782     \else:
11783       \exp_after:wN \_fp_invalid_operation_o:Nww
11784       \exp_after:wN -
11785     \fi:
11786   }
11787 \fi:

```

```

11788     \s_fp \__fp_chk:w 2 #2 #3;
11789     \s_fp \__fp_chk:w 2 #4
11790 }
(End definition for \__fp_add_inf_o:Nww)

```

```
\__fp_add_normal_o:Nww \__fp_add_normal_o:Nww <sign2> \s_fp \__fp_chk:w 1 <sign1> <exp1>
<body1> ; \s_fp \__fp_chk:w 1 <initial sign2> <exp2> <body2> ;

```

We now have two normal numbers to add, and we have to check signs and exponents more carefully before performing the addition.

```

11791 \cs_new:Npn \__fp_add_normal_o:Nww #1 \s_fp \__fp_chk:w 1 #2
11792 {
11793     \if_meaning:w #1#2
11794         \exp_after:wN \__fp_add_npos_o:NnwNnw
11795     \else:
11796         \exp_after:wN \__fp_sub_npos_o:NnwNnw
11797     \fi:
11798     #2
11799 }

```

```
(End definition for \__fp_add_normal_o:Nww)
```

33.2.2 Absolute addition

In this subsection, we perform the addition of two positive normal numbers.

```
\__fp_add_npos_o:NnwNnw \__fp_add_npos_o:NnwNnw <sign1> <exp1> <body1> ; \s_fp \__fp_chk:w 1
<initial sign2> <exp2> <body2> ;

```

Since we are doing an addition, the final sign is $\langle sign_1 \rangle$. Start an __int_eval:w , responsible for computing the exponent: the result, and the $\langle final sign \rangle$ are then given to __fp_sanitize:Nw which checks for overflow. The exponent is computed as the largest exponent #2 or #5, incremented if there is a carry. To add the significands, we decimate the smaller number by the difference between the exponents. This is done by $\text{__fp_add_big_i:wNww}$ or $\text{__fp_add_big_ii:wNww}$. We need to bring the final sign with us in the midst of the calculation to round properly at the end.

```

11800 \cs_new:Npn \__fp_add_npos_o:NnwNnw #1#2#3 ; \s_fp \__fp_chk:w 1 #4 #5
11801 {
11802     \exp_after:wN \__fp_sanitize:Nw
11803     \exp_after:wN #1
11804     \int_use:N \__int_eval:w
11805     \if_int_compare:w #2 > #5 \exp_stop_f:
11806         #2
11807         \exp_after:wN \__fp_add_big_i_o:wNww \__int_value:w -
11808     \else:
11809         #5
11810         \exp_after:wN \__fp_add_big_ii_o:wNww \__int_value:w
11811     \fi:
11812     \__int_eval:w #5 - #2 ; #1 #3;
11813 }

```

```
(End definition for \__fp_add_npos_o:NnwNnw)
```

```

\__fp_add_big_i_o:wNww      \__fp_add_big_i_o:wNww <shift> ; <final sign> <body1> ; <body2> ;
\__fp_add_big_ii_o:wNww      Shift the significand of the small number, then add with \__fp_add_significand-
o:NnnwnnnnN.

11814 \cs_new:Npn \__fp_add_big_i_o:wNww #1; #2 #3; #4;
11815 {
11816   \__fp_decimate:nNnnnn {#1}
11817     \__fp_add_significand_o:NnnwnnnnN
11818     #4
11819   #3
11820   #2
11821 }
11822 \cs_new:Npn \__fp_add_big_ii_o:wNww #1; #2 #3; #4;
11823 {
11824   \__fp_decimate:nNnnnn {#1}
11825     \__fp_add_significand_o:NnnwnnnnN
11826     #3
11827   #4
11828   #2
11829 }

(End definition for \__fp_add_big_i_o:wNww This function is documented on page ??.)
```

```

\__fp_add_significand_o:NnnwnnnnN
\__fp_add_significand_pack:NNNNNNN
\__fp_add_significand_test_o:N
\__fp_add_significand_o:NnnwnnnnN <rounding digit> {<Y1>} {<Y2>} <extra-digits>
; {<X1>} {<X2>} {<X3>} {<X4>} <final sign>
```

To round properly, we must know at which digit the rounding should occur. This requires to know whether the addition produces an overall carry or not. Thus, we do the computation now and check for a carry, then go back and do the rounding. The rounding may cause a carry in very rare cases such as $0.99\dots 95 \rightarrow 1.00\dots 0$, but this situation always give an exact power of 10, for which it is easy to correct the result at the end.

```

11830 \cs_new:Npn \__fp_add_significand_o:NnnwnnnnN #1 #2#3 #4; #5#6#7#8
11831 {
11832   \exp_after:wN \__fp_add_significand_test_o:N
11833   \int_use:N \__int_eval:w 1#5#6 + #2
11834     \exp_after:wN \__fp_add_significand_pack:NNNNNNN
11835     \int_use:N \__int_eval:w 1#7#8 + #3 ; #1
11836 }
11837 \cs_new:Npn \__fp_add_significand_pack:NNNNNNN #1 #2#3#4#5#6#7
11838 {
11839   \if_meaning:w 2 #1
11840     + \c_one
11841   \fi:
11842   ; #2 #3 #4 #5 #6 #7 ;
11843 }
11844 \cs_new:Npn \__fp_add_significand_test_o:N #1
11845 {
11846   \if_meaning:w 2 #1
11847     \exp_after:wN \__fp_add_significand_carry_o:wwwNN
11848   \else:
11849     \exp_after:wN \__fp_add_significand_no_carry_o:wwwNN
```

```

11850      \fi:
11851  }
(End definition for \_\_fp\_add\_significand\_o:NnnwnnnN This function is documented on page ??.)
```

__fp_add_significand_no_carry_o:wwwNN
__fp_add_significand_no_carry_o:wwwNN $\langle 8d \rangle ; \langle 6d \rangle ; \langle 2d \rangle ; \langle \text{rounding digit} \rangle \langle \text{sign} \rangle$

If there's no carry, grab all the digits again and round. The packing function __fp_basics_pack_high:NNNNNw takes care of the case where rounding brings a carry.

```

11852 \cs_new:Npn \_\_fp\_add\_significand\_no\_carry\_o:wwwNN
11853   #1; #2; #3#4 ; #5#6
11854  {
11855    \exp_after:wN \_\_fp\_basics\_pack\_high:NNNNNw
11856    \int_use:N \_\_int_eval:w 1 #1
11857    \exp_after:wN \_\_fp\_basics\_pack\_low:NNNNNw
11858    \int_use:N \_\_int_eval:w 1 #2 #3#4
11859    + \_\_fp\_round:NNN #6 #4 #5
11860    \exp_after:wN ;
11861  }
(End definition for \_\_fp\_add\_significand\_no\_carry\_o:wwwNN)
```

__fp_add_significand_carry_o:wwwNN
__fp_add_significand_carry_o:wwwNN $\langle 8d \rangle ; \langle 6d \rangle ; \langle 2d \rangle ; \langle \text{rounding digit} \rangle \langle \text{sign} \rangle$

The case where there is a carry is very similar. Rounding can even raise the first digit from 1 to 2, but we don't care.

```

11862 \cs_new:Npn \_\_fp\_add\_significand\_carry\_o:wwwNN
11863   #1; #2; #3#4; #5#6
11864  {
11865    + \c_one
11866    \exp_after:wN \_\_fp\_basics\_pack\_weird\_high:NNNNNNNNw
11867    \int_use:N \_\_int_eval:w 1 1 #1
11868    \exp_after:wN \_\_fp\_basics\_pack\_weird\_low:NNNNw
11869    \int_use:N \_\_int_eval:w 1 #2#3 +
11870    \exp_after:wN \_\_fp\_round:NNN
11871    \exp_after:wN #6
11872    \exp_after:wN #3
11873    \int_value:w \_\_fp\_round\_digit:Nw #4 #5 ;
11874    \exp_after:wN ;
11875  }
(End definition for \_\_fp\_add\_significand\_carry\_o:wwwNN)
```

33.2.3 Absolute subtraction

__fp_sub_npos_o:NnwNnw
__fp_sub_eq_o:NnwNnw
__fp_sub_npos_ii_o:NnwNnw
__fp_sub_npos_o:NnwNnw $\langle \text{sign}_1 \rangle \langle \text{exp}_1 \rangle \langle \text{body}_1 \rangle ; \text{\s_fp } __fp_chk:w 1 \langle \text{initial sign}_2 \rangle \langle \text{exp}_2 \rangle \langle \text{body}_2 \rangle ;$
Rounding properly in some modes requires to know what the sign of the result will be. Thus, we start by comparing the exponents and significands. If the numbers coincide, return zero. If the second number is larger, swap the numbers and call __fp_sub_npos_i_o:NnwNnw with the opposite of $\langle \text{sign}_1 \rangle$.

```

11876 \cs_new:Npn \__fp_sub_npos_o:NnwNnw #1#2#3; \s__fp \__fp_chk:w 1 #4#5#6;
11877 {
11878   \if_case:w \__fp_compare_npos:nwnw {#2} #3; {#5} #6; \exp_stop_f:
11879     \exp_after:wN \__fp_sub_eq_o:NnwNnw
11880   \or:
11881     \exp_after:wN \__fp_sub_npos_i_o:NnwNnw
11882   \else:
11883     \exp_after:wN \__fp_sub_npos_ii_o:NnwNnw
11884   \fi:
11885   #1 {#2} #3; {#5} #6;
11886 }
11887 \cs_new:Npn \__fp_sub_eq_o:NnwNnw #1#2; #3; { \exp_after:wN \c_zero_fp }
11888 \cs_new:Npn \__fp_sub_npos_ii_o:NnwNnw #1 #2; #3;
11889 {
11890   \exp_after:wN \__fp_sub_npos_i_o:NnwNnw
11891   \int_use:N \__int_eval:w \c_two - #1 \__int_eval_end:
11892   #3; #2;
11893 }

```

(End definition for `__fp_sub_npos_o:NnwNnw` This function is documented on page ??.)

`__fp_sub_npos_i_o:NnwNnw`

After the computation is done, `__fp_sanitize:Nw` checks for overflow/underflow. It expects the *(final sign)* and the *(exponent)* (delimited by ;). Start an integer expression for the exponent, which starts with the exponent of the largest number, and may be decreased if the two numbers are very close. If the two numbers have the same exponent, call the `near` auxiliary. Otherwise, decimate y , then call the `far` auxiliary to evaluate the difference between the two significands. Note that we decimate by 1 less than one could expect.

```

11894 \cs_new:Npn \__fp_sub_npos_i_o:NnwNnw #1 #2#3; #4#5;
11895 {
11896   \exp_after:wN \__fp_sanitize:Nw
11897   \exp_after:wN #1
11898   \int_use:N \__int_eval:w
11899   #2
11900   \if_int_compare:w #2 = #4 \exp_stop_f:
11901     \exp_after:wN \__fp_sub_back_near_o:nnnnnnnnN
11902   \else:
11903     \exp_after:wN \__fp_decimate:nNnnnn \exp_after:wN
11904       { \int_use:N \__int_eval:w #2 - #4 - \c_one \exp_after:wN }
11905     \exp_after:wN \__fp_sub_back_far_o:NnnwnnnnN
11906   \fi:
11907   #5
11908   #3
11909   #1
11910 }

```

(End definition for `__fp_sub_npos_i_o:NnwNnw`)

```

\__fp_sub_back_near_o:nnnnnnnnN
\__fp_sub_back_near_pack:NNNNNNNw
\__fp_sub_back_near_after:wNNNNNw

```

`__fp_sub_back_near_o:nnnnnnnnN` $\{ \langle Y_1 \rangle \} \{ \langle Y_2 \rangle \} \{ \langle Y_3 \rangle \} \{ \langle Y_4 \rangle \}$ $\{ \langle X_1 \rangle \}$
 $\{ \langle X_2 \rangle \} \{ \langle X_3 \rangle \} \{ \langle X_4 \rangle \}$ *(final sign)*

In this case, the subtraction is exact, so we discard the *final sign* #9. The very large shifts of 10^9 and $1.1 \cdot 10^9$ are unnecessary here, but allow the auxiliaries to be reused later. Each integer expression produces a 10 digit result. If the resulting 16 digits start with a 0, then we need to shift the group, padding with trailing zeros.

```

11911 \cs_new:Npn \__fp_sub_back_near_o:nnnnnnnnnN #1#2#3#4 #5#6#7#8 #9
11912 {
11913   \exp_after:wN \__fp_sub_back_near_after:wNNNNw
11914   \int_use:N \__int_eval:w 10#5#6 - #1#2 - \c_eleven
11915   \exp_after:wN \__fp_sub_back_near_pack:NNNNNNw
11916   \int_use:N \__int_eval:w 11#7#8 - #3#4 \exp_after:wN ;
11917 }
11918 \cs_new:Npn \__fp_sub_back_near_pack:NNNNNNw #1#2#3#4#5#6#7 ;
11919 { + #1#2 ; {#3#4#5#6} {#7} ; }
11920 \cs_new:Npn \__fp_sub_back_near_after:wNNNNw 10 #1#2#3#4 #5 ;
11921 {
11922   \if_meaning:w 0 #1
11923     \exp_after:wN \__fp_sub_back_shift:wnnnn
11924   \fi:
11925   ; {#1#2#3#4} {#5}
11926 }
```

(End definition for `__fp_sub_back_near_o:nnnnnnnnnN` This function is documented on page ??.)

```
\__fp_sub_back_shift:wnnnn
\__fp_sub_back_shift_ii:ww
  \__fp_sub_back_shift_iii:NNNNNNNNw
    \__fp_sub_back_shift_iv:nnnnw
```

This function is called with $\langle Z_1 \rangle \leq 999$. Act with `\number` to trim leading zeros from $\langle Z_1 \rangle \langle Z_2 \rangle$ (we don't do all four blocks at once, since non-zero blocks would then overflow TeX's integers). If the first two blocks are zero, the auxiliary receives an empty #1 and trims #2#30 from leading zeros, yielding a total shift between 7 and 16 to the exponent. Otherwise we get the shift from #1 alone, yielding a result between 1 and 6. Once the exponent is taken care of, trim leading zeros from #1#2#3 (when #1 is empty, the space before #2#3 is ignored), get four blocks of 4 digits and finally clean up. Trailing zeros are added so that digits can be grabbed safely.

```

11927 \cs_new:Npn \__fp_sub_back_shift:wnnnn ; #1#2
11928 {
11929   \exp_after:wN \__fp_sub_back_shift_ii:ww
11930   \__int_value:w #1 #2 0 ;
11931 }
11932 \cs_new:Npn \__fp_sub_back_shift_ii:ww #1 0 ; #2#3 ;
11933 {
11934   \if_meaning:w @ #1 @
11935     - \c_seven
11936     - \exp_after:wN \use_i:nnn
11937     \exp_after:wN \__fp_sub_back_shift_iii:NNNNNNNNw
11938     \__int_value:w #2#3 0 ~ 123456789;
11939 \else:
11940   - \__fp_sub_back_shift_iii:NNNNNNNNw #1 123456789;
11941 \fi:
11942 \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
11943 \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
```

```

11944 \exp_after:wN \_fp_sub_back_shift_iv:nnnnw
11945 \exp_after:wN ;
11946 \__int_value:w
11947 #1 ~ #2#3 0 ~ 0000 0000 0000 000 ;
11948 }
11949 \cs_new:Npn \_fp_sub_back_shift_iiii:NNNNNNNNw #1#2#3#4#5#6#7#8#9; {#8}
11950 \cs_new:Npn \_fp_sub_back_shift_iv:nnnnw #1 ; #2 ; { ; #1 ; }
(End definition for \_fp_sub_back_shift:wnnnn This function is documented on page ??.)
```

_fp_sub_back_far_o:NnnnnnnN _fp_sub_back_far_o:NnnnnnnN $\langle rounding \rangle \{ \langle Y'_1 \rangle \} \{ \langle Y'_2 \rangle \} \langle extra-digits \rangle$
 $; \{ \langle X_1 \rangle \} \{ \langle X_2 \rangle \} \{ \langle X_3 \rangle \} \{ \langle X_4 \rangle \} \langle final sign \rangle$

If the difference is greater than $10^{\langle exp_o_x \rangle}$, call the `very_far` auxiliary. If the result is less than $10^{\langle exp_o_x \rangle}$, call the `not_far` auxiliary. If it is too close a call to know yet, namely if $1\langle Y'_1 \rangle \langle Y'_2 \rangle = \langle X_1 \rangle \langle X_2 \rangle \langle X_3 \rangle \langle X_4 \rangle 0$, then call the `quite_far` auxiliary. We use the odd combination of space and semi-colon delimiters to allow the `not_far` auxiliary to grab each piece individually, the `very_far` auxiliary to use `_fp_pack_eight:wNNNNNNNN`, and the `quite_far` to ignore the significands easily (using the ; delimiter).

```

11951 \cs_new:Npn \_fp_sub_back_far_o:NnnnnnnN #1 #2#3 #4; #5#6#7#8
11952 {
11953 \if_case:w
11954 \if_int_compare:w 1 #2 = #5#6 \use_i:nnnn #7 \exp_stop_f:
11955 \if_int_compare:w #3 = \use_none:n #7#8 0 \exp_stop_f:
11956 \c_zero
11957 \else:
11958 \if_int_compare:w #3 > \use_none:n #7#8 0 - \fi: \c_one
11959 \fi:
11960 \else:
11961 \if_int_compare:w 1 #2 > #5#6 \use_i:nnnn #7 - \fi: \c_one
11962 \fi:
11963 \exp_after:wN \_fp_sub_back_quite_far_o:wwNN
11964 \or: \exp_after:wN \_fp_sub_back_very_far_o:wwwNN
11965 \else: \exp_after:wN \_fp_sub_back_not_far_o:wwwNN
11966 \fi:
11967 #2 ~ #3 ; #5 #6 ~ #7 #8 ; #1
11968 }
```

(End definition for _fp_sub_back_far_o:NnnnnnnN)

_fp_sub_back Quite far_o:wwNN
_fp_sub_back Quite far_ii>NN

The easiest case is when $x - y$ is extremely close to a power of 10, namely the first digit of x is 1, and all others vanish when subtracting y . Then the $\langle rounding \rangle$ #3 and the $\langle final sign \rangle$ #4 control whether we get 1 or 0.999999999999999. In the usual round-to-nearest mode, we will get 1 whenever the $\langle rounding \rangle$ digit is less than or equal to 5 (remember that the $\langle rounding \rangle$ digit is only equal to 5 if there was no further non-zero digit).

```

11969 \cs_new:Npn \_fp_sub_back_quite_far_o:wwNN #1; #2; #3#4
11970 {
11971 \exp_after:wN \_fp_sub_back_quite_far_ii:NN
11972 \exp_after:wN #3
11973 \exp_after:wN #4
11974 }
```

```

11975 \cs_new:Npn \__fp_sub_back Quite_far_ii>NN #1#2
11976 {
11977   \if_case:w \__fp_round_neg:NNN #2 0 #1
11978     \exp_after:wN \use_i:nn
11979   \else:
11980     \exp_after:wN \use_ii:nn
11981   \fi:
11982   { ; {1000} {0000} {0000} {0000} ; }
11983   { - \c_one ; {9999} {9999} {9999} {9999} ; }
11984 }
(End definition for \__fp_sub_back Quite_far_ii>NN This function is documented on page ??.)
```

`__fp_sub_back_not_far_o:wwwNN`

In the present case, x and y have different exponents, but y is large enough that $x - y$ has a smaller exponent than x . Decrement the exponent (with `- \c_one`). Then proceed in a way similar to the `near` auxiliaries seen earlier, but multiplying x by 10 (#30 and #40 below), and with the added quirk that the `(rounding)` digit has to be taken into account. Namely, we may have to decrease the result by one unit if `__fp_round_neg:NNN` returns 1. This function expects the `(final sign)` #6, the last digit of `1100000000+#40-#2`, and the `(rounding)` digit. Instead of redoing the computation for the second argument, we note that `__fp_round_neg:NNN` only cares about its parity, which is identical to that of the last digit of #2.

```

11985 \cs_new:Npn \__fp_sub_back_not_far_o:wwwNN #1 ~ #2; #3 ~ #4; #5#6
11986 {
11987   - \c_one
11988   \exp_after:wN \__fp_sub_back_near_after:wNNNNw
11989   \int_use:N \__int_eval:w 1#30 - #1 - \c_eleven
11990   \exp_after:wN \__fp_sub_back_near_pack:NNNNNNw
11991   \int_use:N \__int_eval:w 11 0000 0000 + #40 - #2
11992   - \exp_after:wN \__fp_round_neg:NNN
11993   \exp_after:wN #6
11994   \use_none:nnnnnn #2 #5
11995   \exp_after:wN ;
11996 }
```

(End definition for __fp_sub_back_not_far_o:wwwNN)

`__fp_sub_back_very_far_o:wwwNN`
`__fp_sub_back_very_far_ii_o:nnNwwNN`

The case where $x - y$ and x have the same exponent is a bit more tricky, mostly because it cannot reuse the same auxiliaries. Shift the y significand by adding a leading 0. Then the logic is similar to the `not_far` functions above. Rounding is a bit more complicated: we have two `(rounding)` digits #3 and #6 (from the decimation, and from the new shift) to take into account, and getting the parity of the main result requires a computation. The first `__int_value:w` triggers the second one because the number is unfinished; we can thus not use 0 in place of 2 there.

```

11997 \cs_new:Npn \__fp_sub_back_very_far_o:wwwNN #1#2#3#4#5#6#7
11998 {
11999   \__fp_pack_eight:wNNNNNNNNN
12000   \__fp_sub_back_very_far_ii_o:nnNwwNN
12001   { 0 #1#2#3 #4#5#6#7 }
12002 ;
```

```

12003   }
12004 \cs_new:Npn \__fp_sub_back_very_far_i_o:nnNwwNN #1#2 ; #3 ; #4 ~ #5; #6#7
12005 {
12006   \exp_after:wN \__fp_basics_pack_high>NNNNNw
12007   \int_use:N \__int_eval:w 1#4 - #1 - \c_one
12008   \exp_after:wN \__fp_basics_pack_low>NNNNNw
12009   \int_use:N \__int_eval:w 2#5 - #2
12010   - \exp_after:wN \__fp_round_neg:NNN
12011   \exp_after:wN #7
12012   \__int_value:w
12013   \if_int_odd:w \__int_eval:w #5 - #2 \__int_eval_end:
12014     1 \else: 2 \fi:
12015   \__int_value:w \__fp_round_digit:Nw #3 #6 ;
12016   \exp_after:wN ;
12017 }

```

(End definition for `__fp_sub_back_very_far_i_o:wwwNN` This function is documented on page ??.)

33.3 Multiplication

33.3.1 Signs, and special numbers

`__fp_*_o:ww` We go through an auxiliary, which is common with `__fp/_o:ww`. The first argument is the operation, used for the invalid operation exception. The second is inserted in a formula to dispatch cases slightly differently between multiplication and division. The third is the operation for normal floating points. The fourth is there for extra cases needed in `__fp/_o:ww`.

```

12018 \cs_new_nopar:cpn { __fp_*_o:ww }
12019 {
12020   \__fp_mul_cases_o:NnNww
12021   *
12022   { - \c_two + }
12023   \__fp_mul_npos_o:Nww
12024   { }
12025 }

```

(End definition for `__fp_*_o:ww`)

`__fp_mul_cases_o:nNnnww` Split into 10 cases (12 for division). If both numbers are normal, go to case 0 (same sign) or case 1 (opposite signs): in both cases, call `__fp_mul_npos_o:Nww` to do the work. If the first operand is `nan`, go to case 2, in which the second operand is discarded; if the second operand is `nan`, go to case 3, in which the first operand is discarded (note the weird interaction with the final test on signs). Then we separate the case where the first number is normal and the second is zero: this goes to cases 4 and 5 for multiplication, 10 and 11 for division. Otherwise, we do a computation which dispatches the products $0 \times 0 = 0 \times 1 = 1 \times 0 = 0$ to case 4 or 5 depending on the combined sign, the products $0 \times \infty$ and $\infty \times 0$ to case 6 or 7 (invalid operation), and the products $1 \times \infty = \infty \times 1 = \infty \times \infty = \infty$ to cases 8 and 9. Note that the code for these two cases (which return $\pm\infty$) is inserted as argument #4, because it differs in the case of divisions.

```
12026 \cs_new:Npn \__fp_mul_cases_o:NnNww
```

```

12027 #1#2#3#4 \s_fp \_\_fp_chk:w #5#6#7; \s_fp \_\_fp_chk:w #8#9
12028 {
12029 \if_case:w \_\_int_eval:w
12030   \if_int_compare:w #5 #8 = \c_eleven
12031     \c_one
12032   \else:
12033     \if_meaning:w 3 #8
12034       \c_three
12035     \else:
12036       \if_meaning:w 3 #5
12037         \c_two
12038       \else:
12039         \if_int_compare:w #5 #8 = \c_ten
12040           \c_nine #2 - \c_two
12041         \else:
12042           (#5 #2 #8) / \c_two * \c_two + \c_seven
12043         \fi:
12044       \fi:
12045     \fi:
12046     \fi:
12047     \if_meaning:w #6 #9 - \c_one \fi:
12048   \_\_int_eval_end:
12049     \_\_fp_case_use:nw { #3 0 }
12050   \or: \_\_fp_case_use:nw { #3 2 }
12051   \or: \_\_fp_case_return_i_o:ww
12052   \or: \_\_fp_case_return_ii_o:ww
12053   \or: \_\_fp_case_return_o:Nww \c_zero_fp
12054   \or: \_\_fp_case_return_o:Nww \c_minus_zero_fp
12055   \or: \_\_fp_case_use:nw { \_\_fp_invalid_operation_o:Nww #1 }
12056   \or: \_\_fp_case_use:nw { \_\_fp_invalid_operation_o:Nww #1 }
12057   \or: \_\_fp_case_return_o:Nww \c_inf_fp
12058   \or: \_\_fp_case_return_o:Nww \c_minus_inf_fp
12059   #4
12060   \fi:
12061   \s_fp \_\_fp_chk:w #5 #6 #7;
12062   \s_fp \_\_fp_chk:w #8 #9
12063 }

(End definition for \_\_fp\_mul\_cases_o:nNnnww)

```

33.3.2 Absolute multiplication

In this subsection, we perform the multiplication of two positive normal numbers.

```
\_\_fp\_mul\_npos_o:Nww \_\_fp\_mul\_npos_o:Nww <final sign> \s_fp \_\_fp_chk:w 1 <sign1> {<exp1>}
<body1> ; \s_fp \_\_fp_chk:w 1 <sign2> {<exp2>} <body2>
```

After the computation, __fp_sanitize:Nw checks for overflow or underflow. As we did for addition, __int_eval:w computes the exponent, catching any shift coming from the computation in the significand. The <final sign> is needed to do the rounding

properly in the significand computation. We setup the post-expansion here, triggered by `_fp_mul_significand_o:nnnnNnnnn`.

```

12064 \cs_new:Npn \_fp_mul_npos_o:Nww
12065     #1 \s_fp \_fp_chk:w #2 #3 #4 #5 ; \s_fp \_fp_chk:w #6 #7 #8 #9 ;
12066 {
12067     \exp_after:wN \_fp_sanitize:Nw
12068     \exp_after:wN #1
12069     \int_use:N \_int_eval:w
12070         #4 + #8
12071     \_fp_mul_significand_o:nnnnNnnnn #5 #1 #9
12072 }
(End definition for \_fp_mul_npos_o:Nww)
```

```
\_fp_mul_significand_o:nnnnNnnnn
\fp mul significand drop:NNNNNw
\fp mul significand keep:NNNNNw
```

Note the three semicolons at the end of the definition. One is for the last `_fp_mul_significand_drop:NNNNNw`; one is for `_fp_round_digit:Nw` later on; and one, preceded by `\exp_after:wN`, which is correctly expanded (within an `_int_eval:w`), is used by `_fp_basics_pack_low:NNNNNw`.

The product of two 16 digit integers has 31 or 32 digits, but it is impossible to know which one before computing. The place where we round depends on that number of digits, and may depend on all digits until the last in some rare cases. The approach is thus to compute the 5 first blocks of 4 digits (the first one is between 100 and 9999 inclusive), and a compact version of the remaining 3 blocks. Afterwards, the number of digits is known, and we can do the rounding within yet another set of `_int_eval:w`.

```

12073 \cs_new:Npn \_fp_mul_significand_o:nnnnNnnnn #1#2#3#4 #5 #6#7#8#9
12074 {
12075     \exp_after:wN \_fp_mul_significand_test_f:NNN
12076     \exp_after:wN #5
12077     \int_use:N \_int_eval:w 99990000 + #1*#6 +
12078     \exp_after:wN \_fp_mul_significand_keep:NNNNNw
12079     \int_use:N \_int_eval:w 99990000 + #1*#7 + #2*#6 +
12080     \exp_after:wN \_fp_mul_significand_keep:NNNNNw
12081     \int_use:N \_int_eval:w 99990000 + #1*#8 + #2*#7 + #3*#6 +
12082     \exp_after:wN \_fp_mul_significand_drop:NNNNNw
12083     \int_use:N \_int_eval:w 99990000 + #1*#9 + #2*#8 + #3*#7 + #4*#6 +
12084     \exp_after:wN \_fp_mul_significand_drop:NNNNNw
12085     \int_use:N \_int_eval:w 99990000 + #2*#9 + #3*#8 + #4*#7 +
12086     \exp_after:wN \_fp_mul_significand_drop:NNNNNw
12087     \int_use:N \_int_eval:w 99990000 + #3*#9 + #4*#8 +
12088     \exp_after:wN \_fp_mul_significand_drop:NNNNNw
12089     \int_use:N \_int_eval:w 100000000 + #4*#9 ;
12090     ; \exp_after:wN ;
12091 }
12092 \cs_new:Npn \_fp_mul_significand_drop:NNNNNw #1#2#3#4#5 #6;
12093 { #1#2#3#4#5 ; + #6 }
12094 \cs_new:Npn \_fp_mul_significand_keep:NNNNNw #1#2#3#4#5 #6;
12095 { #1#2#3#4#5 ; #6 ; }
```

(End definition for `_fp_mul_significand_o:nnnnNnnnn` This function is documented on page ??.)

```
\_fp_mul_significand_test_f:NNN
    \_fp_mul_significand_test_f:NNN <sign> 1 <digits 1-8> ; <digits 9-12> ;
    <digits 13-16> ; + <digits 17-20> + <digits 21-24> + <digits 25-28> + <digits
    29-32> ; \exp_after:wN ;
```

If the $\langle digit 1 \rangle$ is non-zero, then for rounding we only care about the digits 16 and 17, and whether further digits are zero or not (check for exact ties). On the other hand, if $\langle digit 1 \rangle$ is zero, we care about digits 17 and 18, and whether further digits are zero.

```
12096 \cs_new:Npn \_fp_mul_significand_test_f:NNN #1 #2 #3
12097 {
12098     \if_meaning:w 0 #3
12099         \exp_after:wN \_fp_mul_significand_small_f:NNwwwN
12100     \else:
12101         \exp_after:wN \_fp_mul_significand_large_f:NwwNNNN
12102     \fi:
12103     #1 #3
12104 }
```

(End definition for `_fp_mul_significand_test_f:NNN`)

`_fp_mul_significand_large_f:NwwNNNN` In this branch, $\langle digit 1 \rangle$ is non-zero. The result is thus $\langle digits 1-16 \rangle$, plus some rounding which depends on the digits 16, 17, and whether all subsequent digits are zero or not. Here, `_fp_round_digit:Nw` takes digits 17 and further (as an integer expression), and replaces it by a $\langle rounding digit \rangle$, suitable for `_fp_round:NNN`.

```
12105 \cs_new:Npn \_fp_mul_significand_large_f:NwwNNNN #1 #2; #3; #4#5#6#7; +
12106 {
12107     \exp_after:wN \_fp_basics_pack_high>NNNNNw
12108     \int_use:N \_int_eval:w 1#2
12109     \exp_after:wN \_fp_basics_pack_low>NNNNNw
12110     \int_use:N \_int_eval:w 1#3#4#5#6#7
12111     + \exp_after:wN \_fp_round:NNN
12112     \exp_after:wN #1
12113     \exp_after:wN #7
12114     \int_value:w \_fp_round_digit:Nw
12115 }
```

(End definition for `_fp_mul_significand_large_f:NwwNNNN`)

`_fp_mul_significand_small_f>NNwwwN` In this branch, $\langle digit 1 \rangle$ is zero. Our result will thus be $\langle digits 2-17 \rangle$, plus some rounding which depends on the digits 17, 18, and whether all subsequent digits are zero or not. The 8 digits 1#3 are followed, after expansion of the `small_pack` auxiliary, by the next digit, to form a 9 digit number.

```
12116 \cs_new:Npn \_fp_mul_significand_small_f>NNwwwN #1 #2#3; #4#5; #6; + #7
12117 {
12118     - \c_one
12119     \exp_after:wN \_fp_basics_pack_high>NNNNNw
12120     \int_use:N \_int_eval:w 1#3#4
12121     \exp_after:wN \_fp_basics_pack_low>NNNNNw
12122     \int_use:N \_int_eval:w 1#5#6#7
12123     + \exp_after:wN \_fp_round:NNN
```

```

12124           \exp_after:wN #1
12125           \exp_after:wN #7
12126           \_int_value:w \_fp_round_digit:Nw
12127       }
(End definition for \_fp_mul_significand_small_f:NNwwN)

```

33.4 Division

33.4.1 Signs, and special numbers

Time is now ripe to tackle the hardest of the four elementary operations: division.

`_fp/_o:ww` Filtering special floating point is very similar to what we did for multiplications, with a few variations. Invalid operation exceptions display `/` rather than `*`. In the formula for dispatch, we replace `- \c_two +` by `-`. The case of normal numbers is treated using `_fp_div_npos_o:Nww` rather than `_fp_mul_npos_o:Nww`. There are two additionnal cases: if the first operand is normal and the second is a zero, then the division by zero exception is raised: cases 10 and 11 of the `\if_case:w` construction in `_fp_mul_cases_o:NnNww` are provided as the fourth argument here.

```

12128 \cs_new_nopar:cpn { _fp/_o:ww }
12129 {
12130   \_fp_mul_cases_o:NnNww
12131   /
12132   { - }
12133   \_fp_div_npos_o:Nww
12134   {
12135     \or:
12136       \_fp_case_use:nw
12137       { \_fp_division_by_zero_o:NNww \c_inf_fp / }
12138     \or:
12139       \_fp_case_use:nw
12140       { \_fp_division_by_zero_o:NNww \c_minus_inf_fp / }
12141   }
12142 }
(End definition for \_fp/_o:ww)

```

```

\_fp_div_npos_o:Nww
  \_fp_div_npos_o:Nww \langle final sign\rangle \s_fp \_fp_chk:w 1 \langle sign_A\rangle \{\langle exp A\rangle\}
  \{\langle A_1\rangle\} \{\langle A_2\rangle\} \{\langle A_3\rangle\} \{\langle A_4\rangle\} ; \s_fp \_fp_chk:w 1 \langle sign_Z\rangle \{\langle exp Z\rangle\}
  \{\langle Z_1\rangle\} \{\langle Z_2\rangle\} \{\langle Z_3\rangle\} \{\langle Z_4\rangle\} ;

```

We want to compute A/Z . As for multiplication, `_fp_sanitize:Nw` checks for overflow or underflow; we provide it with the `\langle final sign\rangle`, and an integer expression in which we compute the exponent. We set up the arguments of `_fp_div_significand_i_o:wnnw`, namely an integer $\langle y \rangle$ obtained by adding 1 to the first 5 digits of Z (explanation given soon below), then the four $\{\langle A_i \rangle\}$, then the four $\{\langle Z_i \rangle\}$, a semi-colon, and the `\langle final sign\rangle`, used for rounding at the end.

```

12143 \cs_new:Npn \_fp_div_npos_o:Nww
12144   #1 \s_fp \_fp_chk:w 1 #2 #3 #4 ; \s_fp \_fp_chk:w 1 #5 #6 #7#8#9;
12145 {

```

```

12146   \exp_after:wN \__fp_sanitize:Nw
12147   \exp_after:wN #1
12148   \int_use:N \__int_eval:w
12149     #3 - #6
12150   \exp_after:wN \__fp_div_significand_i_o:wnnw
12151     \int_use:N \__int_eval:w #7 \use_i:nnnn #8 + \c_one ;
12152     #4
12153     {#7}{#8}#9 ;
12154     #1
12155   }
(End definition for \__fp_div_npos_o:Nww)

```

33.4.2 Work plan

In this subsection, we explain how to avoid overflowing T_EX's integers when performing the division of two positive normal numbers.

We are given two numbers, $A = 0.A_1A_2A_3A_4$ and $Z = 0.Z_1Z_2Z_3Z_4$, in blocks of 4 digits, and we know that the first digits of A_1 and of Z_1 are non-zero. To compute A/Z , we proceed as follows.

- Find an integer $Q_A \simeq 10^4 A/Z$.
- Replace A by $B = 10^4 A - Q_A Z$.
- Find an integer $Q_B \simeq 10^4 B/Z$.
- Replace B by $C = 10^4 B - Q_B Z$.
- Find an integer $Q_C \simeq 10^4 C/Z$.
- Replace C by $D = 10^4 C - Q_C Z$.
- Find an integer $Q_D \simeq 10^4 D/Z$.
- Consider $E = 10^4 D - Q_D Z$, and ensure correct rounding.

The result is then $Q = 10^{-4}Q_A + 10^{-8}Q_B + 10^{-12}Q_C + 10^{-16}Q_D + \text{rounding}$. Since the Q_i are integers, B , C , D , and E are all exact multiples of 10^{-16} , in other words, computing with 16 digits after the decimal separator yields exact results. The problem will be overflow: in general B , C , D , and E may be greater than 1.

Unfortunately, things are not as easy as they seem. In particular, we want all intermediate steps to be positive, since negative results would require extra calculations at the end. This requires that $Q_A \leq 10^4 A/Z$ etc. A reasonable attempt would be to define Q_A as

$$\text{\int_eval:n}\left\{\frac{A_1A_2}{Z_1+1}-1\right\} \leq 10^4 \frac{A}{Z}$$

Subtracting 1 at the end takes care of the fact that ε -T_EX's `__int_eval:w` rounds divisions instead of truncating (really, 1/2 would be sufficient, but we work with integers). We add 1 to Z_1 because $Z_1 \leq 10^4 Z < Z_1 + 1$ and we need Q_A to be an underestimate.

However, we are now underestimating Q_A too much: it can be wrong by up to 100, for instance when $Z = 0.1$ and $A \simeq 1$. Then B could take values up to 10 (maybe more), and a few steps down the line, we would run into arithmetic overflow, since TeX can only handle integers less than roughly $2 \cdot 10^9$.

A better formula is to take

$$Q_A = \text{\texttt{\backslash int_eval:n}} \left\{ \frac{10 \cdot A_1 A_2}{\lfloor 10^{-3} \cdot Z_1 Z_2 \rfloor + 1} - 1 \right\}.$$

This is always less than $10^9 A / (10^5 Z)$, as we wanted. In words, we take the 5 first digits of Z into account, and the 8 first digits of A , using 0 as a 9-th digit rather than the true digit for efficiency reasons. We shall prove that using this formula to define all the Q_i avoids any overflow. For convenience, let us denote

$$y = \lfloor 10^{-3} \cdot Z_1 Z_2 \rfloor + 1,$$

so that, taking into account the fact that ε -TeX rounds ties away from zero,

$$\begin{aligned} Q_A &= \left\lfloor \frac{A_1 A_2 0}{y} - \frac{1}{2} \right\rfloor \\ &> \frac{A_1 A_2 0}{y} - \frac{3}{2}. \end{aligned}$$

Note that $10^4 < y \leq 10^5$, and $999 \leq Q_A \leq 99989$. Also note that this formula does not cause an overflow as long as $A < (2^{31} - 1)/10^9 \simeq 2.147 \dots$, since the numerator involves an integer slightly smaller than $10^9 A$.

Let us bound B :

$$\begin{aligned} 10^5 B &= A_1 A_2 0 + 10 \cdot 0.A_3 A_4 - 10 \cdot Z_1.Z_2 Z_3 Z_4 \cdot Q_A \\ &< A_1 A_2 0 \cdot \left(1 - 10 \cdot \frac{Z_1.Z_2 Z_3 Z_4}{y} \right) + \frac{3}{2} \cdot 10 \cdot Z_1.Z_2 Z_3 Z_4 + 10 \\ &\leq \frac{A_1 A_2 0 \cdot (y - 10 \cdot Z_1.Z_2 Z_3 Z_4)}{y} + \frac{3}{2} y + 10 \\ &\leq \frac{A_1 A_2 0 \cdot 1}{y} + \frac{3}{2} y + 10 \leq \frac{10^9 A}{y} + 1.6 \cdot y. \end{aligned}$$

At the last step, we hide 10 into the second term for later convenience. The same reasoning yields

$$\begin{aligned} 10^5 B &< 10^9 A/y + 1.6y, \\ 10^5 C &< 10^9 B/y + 1.6y, \\ 10^5 D &< 10^9 C/y + 1.6y, \\ 10^5 E &< 10^9 D/y + 1.6y. \end{aligned}$$

The goal is now to prove that none of B , C , D , and E can go beyond $(2^{31} - 1)/10^9 = 2.147 \dots$

Combining the various inequalities together with $A < 1$, we get

$$\begin{aligned} 10^5 B &< 10^9/y + 1.6y, \\ 10^5 C &< 10^{13}/y^2 + 1.6(y + 10^4), \\ 10^5 D &< 10^{17}/y^3 + 1.6(y + 10^4 + 10^8/y), \\ 10^5 E &< 10^{21}/y^4 + 1.6(y + 10^4 + 10^8/y + 10^{12}/y^2). \end{aligned}$$

All of those bounds are convex functions of y (since every power of y involved is convex, and the coefficients are positive), and thus maximal at one of the end-points of the allowed range $10^4 < y \leq 10^5$. Thus,

$$\begin{aligned} 10^5 B &< \max(1.16 \cdot 10^5, 1.7 \cdot 10^5), \\ 10^5 C &< \max(1.32 \cdot 10^5, 1.77 \cdot 10^5), \\ 10^5 D &< \max(1.48 \cdot 10^5, 1.777 \cdot 10^5), \\ 10^5 E &< \max(1.64 \cdot 10^5, 1.7777 \cdot 10^5). \end{aligned}$$

All of those bounds are less than $2.147 \cdot 10^5$, and we are thus within T_EX's bounds in all cases!

We will later need to have a bound on the Q_i . Their definitions imply that $Q_A < 10^9 A/y - 1/2 < 10^5 A$ and similarly for the other Q_i . Thus, all of them are less than 177770.

The last step is to ensure correct rounding. We have

$$A/Z = \sum_{i=1}^4 (10^{-4i} Q_i) + 10^{-16} E/Z$$

exactly. Furthermore, we know that the result will be in $[0.1, 10)$, hence will be rounded to a multiple of 10^{-16} or of 10^{-15} , so we only need to know the integer part of E/Z , and a “rounding” digit encoding the rest. Equivalently, we need to find the integer part of $2E/Z$, and determine whether it was an exact integer or not (this serves to detect ties). Since

$$\frac{2E}{Z} = 2 \frac{10^5 E}{10^5 Z} \leq 2 \frac{10^5 E}{10^4} < 36,$$

this integer part is between 0 and 35 inclusive. We let ε-T_EX round

$$P = \text{\textbackslash int_eval:n} \left\{ \frac{2 \cdot E_1 E_2}{Z_1 Z_2} \right\},$$

which differs from $2E/Z$ by at most

$$\frac{1}{2} + 2 \left| \frac{E}{Z} - \frac{E}{10^{-8} Z_1 Z_2} \right| + 2 \left| \frac{10^8 E - E_1 E_2}{Z_1 Z_2} \right| < 1,$$

($1/2$ comes from ε - \TeX 's rounding) because each absolute value is less than 10^{-7} . Thus P is either the correct integer part, or is off by 1; furthermore, if $2E/Z$ is an integer, $P = 2E/Z$. We will check the sign of $2E - PZ$. If it is negative, then $E/Z \in ((P-1)/2, P/2)$. If it is zero, then $E/Z = P/2$. If it is positive, then $E/Z \in (P/2, (P-1)/2)$. In each case, we know how to round to an integer, depending on the parity of P , and the rounding mode.

33.4.3 Implementing the significand division

```
\_\_fp\_div\_significand\_i\_o:wnnw
    \_\_fp\_div\_significand\_i\_o:wnnw \langle y \rangle ; {\langle A_1 \rangle} {\langle A_2 \rangle} {\langle A_3 \rangle} {\langle A_4 \rangle}
    {\langle Z_1 \rangle} {\langle Z_2 \rangle} {\langle Z_3 \rangle} {\langle Z_4 \rangle} ; \langle sign \rangle
Compute  $10^6 + Q_A$  (a 7 digit number thanks to the shift), unbrace  $\langle A_1 \rangle$  and  $\langle A_2 \rangle$ , and prepare the  $\langle continuation \rangle$  arguments for 4 consecutive calls to  $\_\_fp\_div\_significand\_calc:wwnnnnnnnn$ . Each of these calls will need  $\langle y \rangle$  (#1), and it turns out that we need post-expansion there, hence the  $\_\_int\_value:w$ . Here, #4 is six brace groups, which give the six first n-type arguments of the calc function.
12156 \cs_new:Npn \_\_fp\_div\_significand\_i\_o:wnnw #1 ; #2#3 #4 ;
12157 {
12158     \exp_after:wn \_\_fp\_div\_significand\_test_o:w
12159     \int_use:N \_\_int_eval:w
12160     \exp_after:wN \_\_fp\_div\_significand\_calc:wwnnnnnnnn
12161     \int_use:N \_\_int_eval:w 999999 + #2 #3 0 / #1 ;
12162     #2 #3 ;
12163     #4
12164     { \exp_after:wN \_\_fp\_div\_significand\_ii:wwn \_\_int_value:w #1 }
12165     { \exp_after:wN \_\_fp\_div\_significand\_ii:wwn \_\_int_value:w #1 }
12166     { \exp_after:wN \_\_fp\_div\_significand\_ii:wwn \_\_int_value:w #1 }
12167     { \exp_after:wN \_\_fp\_div\_significand\_iii:wwnnnnn \_\_int_value:w #1 }
12168 }
```

(End definition for $__fp_div_significand_i_o:wnnw$)

```
\_\_fp\_div\_significand\_calc:wwnnnnnn
\_\_fp\_div\_significand\_calc\_i:wwnnnnnn
\_\_fp\_div\_significand\_calc\_ii:wwnnnnnn
```

$__fp_div_significand_calc:wwnnnnnn \langle 10^6 + Q_A \rangle ; \langle A_1 \rangle \langle A_2 \rangle ; {\langle A_3 \rangle} {\langle A_4 \rangle} {\langle Z_1 \rangle} {\langle Z_2 \rangle} {\langle Z_3 \rangle} {\langle Z_4 \rangle} {\langle continuation \rangle}$

expands to

$$\langle 10^6 + Q_A \rangle \langle continuation \rangle ; \langle B_1 \rangle \langle B_2 \rangle ; {\langle B_3 \rangle} {\langle B_4 \rangle} {\langle Z_1 \rangle} {\langle Z_2 \rangle} {\langle Z_3 \rangle} {\langle Z_4 \rangle}$$

where $B = 10^4 A - Q_A \cdot Z$. This function is also used to compute C , D , E (with the input shifted accordingly), and is used in $\mathbf{l3fp}\text{-}\mathbf{expo}$.

We know that $0 < Q_A < 1.8 \cdot 10^5$, so the product of Q_A with each Z_i is within \TeX 's bounds. However, it is a little bit too large for our purposes: we would not be able to use the usual trick of adding a large power of 10 to ensure that the number of digits is fixed.

The bound on Q_A , implies that $10^6 + Q_A$ starts with the digit 1, followed by 0 or 1. We test, and call different auxiliaries for the two cases. An earlier implementation did the tests within the computation, but since we added a $\langle continuation \rangle$, this is not possible because the macro has 9 parameters.

The result we want is then (the overall power of 10 is arbitrary):

$$10^{-4}(\#2 - \#1 \cdot \#5 - 10 \cdot \langle i \rangle \cdot \#5\#6) + 10^{-8}(\#3 - \#1 \cdot \#6 - 10 \cdot \langle i \rangle \cdot \#7) \\ + 10^{-12}(\#4 - \#1 \cdot \#7 - 10 \cdot \langle i \rangle \cdot \#8) + 10^{-16}(-\#1 \cdot \#8),$$

where $\langle i \rangle$ stands for the 10^5 digit of Q_A , which is 0 or 1, and $\#1$, $\#2$, etc. are the parameters of either auxiliary. The factors of 10 come from the fact that $Q_A = 10 \cdot 10^4 \cdot \langle i \rangle + \#1$. As usual, to combine all the terms, we need to choose some shifts which must ensure that the number of digits of the second, third, and fourth terms are each fixed. Here, the positive contributions are at most 10^8 and the negative contributions can go up to 10^9 . Indeed, for the auxiliary with $\langle i \rangle = 1$, $\#1$ is at most 80000, leading to contributions of at worse $-8 \cdot 10^4$, while the other negative term is very small $< 10^6$ (except in the first expression, where we don't care about the number of digits); for the auxiliary with $\langle i \rangle = 0$, $\#1$ can go up to 99999, but there is no other negative term. Hence, a good choice is $2 \cdot 10^9$, which produces totals in the range $[10^9, 2.1 \cdot 10^9]$. We are flirting with TeX's limits once more.

```

12169 \cs_new:Npn \__fp_div_significand_calc:wwnnnnnnn 1#1
12170 {
12171   \if_meaning:w 1 #1
12172     \exp_after:wN \__fp_div_significand_calc_i:wwnnnnnnn
12173   \else:
12174     \exp_after:wN \__fp_div_significand_calc_ii:wwnnnnnnn
12175   \fi:
12176 }
12177 \cs_new:Npn \__fp_div_significand_calc_i:wwnnnnnnn #1; #2;#3#4 #5#6#7#8 #9
12178 {
12179   1 1 #1
12180   #9 \exp_after:wN ;
12181   \int_use:N \__int_eval:w \c_fp_Bigg_leading_shift_int
12182     + #2 - #1 * #5 - #5#60
12183   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
12184   \int_use:N \__int_eval:w \c_fp_Bigg_middle_shift_int
12185     + #3 - #1 * #6 - #70
12186   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
12187   \int_use:N \__int_eval:w \c_fp_Bigg_middle_shift_int
12188     + #4 - #1 * #7 - #80
12189   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
12190   \int_use:N \__int_eval:w \c_fp_Bigg_trailing_shift_int
12191     - #1 * #8 ;
12192   {#5}{#6}{#7}{#8}
12193 }
12194 \cs_new:Npn \__fp_div_significand_calc_ii:wwnnnnnnn #1; #2;#3#4 #5#6#7#8 #9
12195 {
12196   1 0 #1
12197   #9 \exp_after:wN ;
12198   \int_use:N \__int_eval:w \c_fp_Bigg_leading_shift_int
12199     + #2 - #1 * #5
12200   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
12201   \int_use:N \__int_eval:w \c_fp_Bigg_middle_shift_int

```

```

12202      + #3 - #1 * #6
12203      \exp_after:wN \__fp_pack_Bigg:NNNNNNw
12204      \int_use:N \__int_eval:w \c__fp_Bigg_middle_shift_int
12205          + #4 - #1 * #7
12206          \exp_after:wN \__fp_pack_Bigg:NNNNNNw
12207          \int_use:N \__int_eval:w \c__fp_Bigg_trailing_shift_int
12208          - #1 * #8 ;
12209      {#5}{#6}{#7}{#8}
12210  }

```

(End definition for `__fp_div_significand_calc:wwnnnnnnn` This function is documented on page ??.)

`__fp_div_significand_ii:wwn`

```

\__fp_div_significand_ii:wwn <y> ; <B1> ; {<B2>} {<B3>} {<B4>} {<Z1>}
{<Z2>} {<Z3>} {<Z4>} <continuations> <sign>

```

Compute Q_B by evaluating $\langle B_1 \rangle \langle B_2 \rangle 0/y - 1$. The result will be output to the left, in an `__int_eval:w` which we start now. Once that is evaluated (and the other Q_i also, since later expansions are triggered by this one), a packing auxiliary takes care of placing the digits of Q_B in an appropriate way for the final addition to obtain Q . This auxiliary is also used to compute Q_C and Q_D with the inputs C and D instead of B .

```

12211 \cs_new:Npn \__fp_div_significand_ii:wwn #1; #2;#3
12212 {
12213     \exp_after:wN \__fp_div_significand_pack:NNN
12214     \int_use:N \__int_eval:w
12215         \exp_after:wN \__fp_div_significand_calc:wwnnnnnnn
12216         \int_use:N \__int_eval:w 999999 + #2 #3 0 / #1 ; #2 #3 ;
12217 }

```

(End definition for `__fp_div_significand_ii:wwn`)

`__fp_div_significand_iii:wwnnnnn`

```

\__fp_div_significand_iii:wwnnnnn <y> ; <E1> ; {<E2>} {<E3>} {<E4>}
{<Z1>} {<Z2>} {<Z3>} {<Z4>} <sign>

```

We compute $P \simeq 2E/Z$ by rounding $2E_1 E_2 / Z_1 Z_2$. Note the first 0, which multiplies Q_D by 10: we will later add (roughly) $5 \cdot P$, which amounts to adding $P/2 \simeq E/Z$ to Q_D , the appropriate correction from a hypothetical Q_E .

```

12218 \cs_new:Npn \__fp_div_significand_iii:wwnnnnn #1; #2;#3#4#5 #6#7
12219 {
12220     0
12221     \exp_after:wN \__fp_div_significand_iv:wwnnnnnnn
12222     \int_use:N \__int_eval:w (\c_two * #2 #3) / #6 #7 ; % <- P
12223     #2 ; {#3} {#4} {#5}
12224     {#6} {#7}
12225 }

```

(End definition for `__fp_div_significand_iii:wwnnnnn`)

```

\__fp_div_significand_iv:wwnnnnnnn <P> ; <E1> ; {<E2>} {<E3>} {<E4>}
{<Z1>} {<Z2>} {<Z3>} {<Z4>} <sign>

```

This adds to the current expression $(10^7 + 10 \cdot Q_D)$ a contribution of $5 \cdot P + \text{sign}(T)$ with $T = 2E - PZ$. This amounts to adding $P/2$ to Q_D , with an extra `<rounding>` digit. This `<rounding>` digit is 0 or 5 if T does not contribute, i.e., if $0 = T = 2E - PZ$, in

other words if $10^{16}A/Z$ is an integer or half-integer. Otherwise it is in the appropriate range, [1, 4] or [6, 9]. This is precise enough for rounding purposes (in any mode).

It seems an overkill to compute T exactly as I do here, but I see no faster way right now.

Once more, we need to be careful and show that the calculation $\#1 \cdot \#6\#7$ below does not cause an overflow: naively, P can be up to 35, and $\#6\#7$ up to 10^8 , but both cannot happen simultaneously. To show that things are fine, we split in two (non-disjoint) cases.

- For $P < 10$, the product obeys $P \cdot \#6\#7 < 10^8 \cdot P < 10^9$.
- For large $P \geq 3$, the rounding error on P , which is at most 1, is less than a factor of 2, hence $P \leq 4E/Z$. Also, $\#6\#7 \leq 10^8 \cdot Z$, hence $P \cdot \#6\#7 \leq 4E \cdot 10^8 < 10^9$.

Both inequalities could be made tighter if needed.

Note however that $P \cdot \#8\#9$ may overflow, since the two factors are now independent, and the result may reach $3.5 \cdot 10^9$. Thus we compute the two lower levels separately. The rest is standard, except that we use `+` as a separator (ending integer expressions explicitly). T is negative if the first character is `-`, it is positive if the first character is neither `0` nor `-`. It is also positive if the first character is `0` and second argument of `_fp_div_significand_vi:Nw`, a sum of several terms, is also zero. Otherwise, there was an exact agreement: $T = 0$.

```

12226 \cs_new:Npn \_fp_div_significand_iv:wwnnnnnn #1; #2;#3#4#5 #6#7#8#9
12227 {
12228   + \c_five * #1
12229   \exp_after:wN \_fp_div_significand_vi:Nw
12230   \int_use:N \_int_eval:w -20 + 2*#2#3 - #1*#6#7 +
12231   \exp_after:wN \_fp_div_significand_v:NN
12232   \int_use:N \_int_eval:w 199980 + 2*#4 - #1*#8 +
12233   \exp_after:wN \_fp_div_significand_v:NN
12234   \int_use:N \_int_eval:w 200000 + 2*#5 - #1*#9 ;
12235 }
12236 \cs_new:Npn \_fp_div_significand_v:NN #1#2 { #1#2 \_int_eval_end: + }
12237 \cs_new:Npn \_fp_div_significand_vi:Nw #1#2;
12238 {
12239   \if_meaning:w 0 #1
12240     \if_int_compare:w \_int_eval:w #2 > \c_zero + \c_one \fi:
12241   \else:
12242     \if_meaning:w - #1 - \else: + \fi: \c_one
12243   \fi:
12244   ;
12245 }
```

(End definition for `_fp_div_significand_iv:wwnnnnnn`, `_fp_div_significand_v:NNw`, and `_fp_div_significand_vi:Nw`)

`_fp_div_significand_pack:NNN` At this stage, we are in the following situation: TeX is in the process of expanding several integer expressions, thus functions at the bottom expand before those above.

```

\fp_div_significand_test_o:w 106 + QA \fp_div_significand_
pack:NNN 106 + QB \fp_div_significand_pack:NNN 106 + QC \fp_
div_significand_pack:NNN 107 + 10 · QD + 5 · P + ε ; ⟨sign⟩
```

Here, $\varepsilon = \text{sign}(T)$ is 0 in case $2E = PZ$, 1 in case $2E > PZ$, which means that P was the correct value, but not with an exact quotient, and -1 if $2E < PZ$, i.e., P was an overestimate. The packing function we define now does nothing special: it removes the 10^6 and carries two digits (for the 10^5 's and the 10^4 's).

```
12246 \cs_new:Npn \_fp_div_significand_pack:NNN 1 #1 #2 { + #1 #2 ; }
```

(End definition for `_fp_div_significand_pack:NNN`)

```
\_fp_div_significand_test_o:w \_fp_div_significand_test_o:w 10 ⟨5d⟩ ; ⟨4d⟩ ; ⟨4d⟩ ; ⟨5d⟩ ; ⟨sign⟩
```

The reason we know that the first two digits are 1 and 0 is that the final result is known to be between 0.1 (inclusive) and 10, hence \tilde{Q}_A (the tilde denoting the contribution from the other Q_i) is at most 99999, and $10^6 + \tilde{Q}_A = 10\cdots$.

It is now time to round. This depends on how many digits the final result will have.

```
12247 \cs_new:Npn \_fp_div_significand_test_o:w 10 #1
12248 {
12249   \if_meaning:w 0 #1
12250     \exp_after:wN \_fp_div_significand_small_o:wwwNNNNwN
12251   \else:
12252     \exp_after:wN \_fp_div_significand_large_o:wwwNNNNwN
12253   \fi:
12254   #1
12255 }
```

(End definition for `_fp_div_significand_test_o:w`)

```
\_fp_div_significand_small_o:wwwNNNNwN \_fp_div_significand_small_o:wwwNNNNwN 0 ⟨4d⟩ ; ⟨4d⟩ ; ⟨4d⟩ ; ⟨5d⟩ ;
; ⟨final sign⟩
```

Standard use of `_fp_basics_pack_low:NNNNw` and `_fp_basics_pack_high:NNNNw`. We finally get to use the `⟨final sign⟩` which has been sitting there for a while.

```
12256 \cs_new:Npn \_fp_div_significand_small_o:wwwNNNNwN
12257   0 #1; #2; #3; #4#5#6#7#8; #9
12258 {
12259   \exp_after:wN \_fp_basics_pack_high:NNNNw
12260   \int_use:N \_int_eval:w 1 #1#2
12261   \exp_after:wN \_fp_basics_pack_low:NNNNw
12262   \int_use:N \_int_eval:w 1 #3#4#5#6#7
12263   + \_fp_round:NNN #9 #7 #8
12264   \exp_after:wN ;
12265 }
```

(End definition for `_fp_div_significand_small_o:wwwNNNNwN`)

```
\_fp_div_significand_large_o:wwwNNNNwN \_fp_div_significand_large_o:wwwNNNNwN ⟨5d⟩ ; ⟨4d⟩ ; ⟨4d⟩ ; ⟨5d⟩ ;
⟨sign⟩
```

We know that the final result cannot reach 10, hence $1\#1\#2$, together with contributions from the level below, cannot reach $2 \cdot 10^9$. For rounding, we build the `⟨rounding digit⟩` from the last two of our 18 digits.

```
12266 \cs_new:Npn \_fp_div_significand_large_o:wwwNNNNwN
12267   #1; #2; #3; #4#5#6#7#8; #9
12268 {
```

```

12269 + \c_one
12270 \exp_after:wN \__fp_basics_pack_weird_high:NNNNNNNNw
12271 \int_use:N \__int_eval:w 1 #1 #2
12272   \exp_after:wN \__fp_basics_pack_weird_low:NNNNw
12273   \int_use:N \__int_eval:w 1 #3 #4 #5 #6 +
12274     \exp_after:wN \__fp_round:NNN
12275     \exp_after:wN #9
12276     \exp_after:wN #6
12277     \__int_value:w \__fp_round_digit:Nw #7 #8 ;
12278   \exp_after:wN ;
12279 }
(End definition for \__fp_div_significand_large_o:wwwNNNNwN)

```

33.5 Unary operations

__fp_-_o:w This function flips the sign of the *floating point* and expands after it in the input stream, just like __fp_+_o:ww etc. We add a hook used by l3fp-expo: anything before \s_fp is ignored.

```

12280 \cs_new:cpn { __fp_-_o:w } #1 \s_fp \__fp_chk:w #2 #3
12281 {
12282   \exp_after:wN \__fp_exp_after_o:w
12283   \exp_after:wN \s_fp
12284   \exp_after:wN \__fp_chk:w
12285   \exp_after:wN #2
12286   \int_use:N \__int_eval:w \c_two - #3 \__int_eval_end:
12287 }
(End definition for \__fp_-_o:w)

```

__fp_abs_o:w This function sets the sign of the *floating point* to be positive, and expands after itself in the input stream, just like __fp_-_o:w. We must leave the sign of nan invariant.

```

12288 \cs_new:Npn \__fp_abs_o:w \s_fp \__fp_chk:w #1 #2
12289 {
12290   \exp_after:wN \__fp_exp_after_o:w
12291   \exp_after:wN \s_fp
12292   \exp_after:wN \__fp_chk:w
12293   \exp_after:wN #1
12294   \__int_value:w \if_meaning:w 1 #2 1 \else: 0 \fi: \exp_stop_f:
12295 }
(End definition for \__fp_abs_o:w)
12296 
```

34 l3fp-extended implementation

```

12297 (*initex | package)
12298 (@@=fp)

```

34.1 Description of extended fixed points

In this module, we work on (almost) fixed-point numbers with extended (24 digits) precision. This is used in the computation of Taylor series for the logarithm, exponential, and trigonometric functions. Since we eventually only care about the 16 first digits of the final result, some of the calculations are not performed with the full 24-digit precision. In other words, the last two blocks of each fixed point number may be wrong as long as the error is small enough to be rounded away when converting back to a floating point number. The fixed point numbers are expressed as

```
{⟨a1⟩} {⟨a2⟩} {⟨a3⟩} {⟨a4⟩} {⟨a5⟩} {⟨a6⟩} ;
```

where each ⟨a_i⟩ is exactly 4 digits (ranging from 0000 to 9999), except ⟨a₁⟩, which may be any “not-too-large” non-negative integer, with or without trailing zeros. Here, “not-too-large” depends on the specific function (see the corresponding comments for details). Checking for overflow is the responsibility of the code calling those functions. The fixed point number a corresponding to the representation above is $a = \sum_{i=1}^6 \langle a_i \rangle \cdot 10^{-4i}$.

Most functions we define here have the form They perform the ⟨calculation⟩ on the two ⟨operands⟩, then feed the result (6 brace groups followed by a semicolon) to the ⟨continuation⟩, responsible for the next step of the calculation. Some functions only accept an N-type ⟨continuation⟩. This allows constructions such as

```
\__fp_fixed_add:wwn ⟨X1⟩ ; ⟨X2⟩ ;
\__fp_fixed_mul:wwn ⟨X3⟩ ;
\__fp_fixed_add:wwn ⟨X4⟩ ;
```

to compute $(X_1 + X_2) \cdot X_3 + X_4$. This turns out to be very appropriate for computing continued fractions and Taylor series.

At the end of the calculation, the result is turned back to a floating point number using __fp_fixed_to_float:Nw. This function has to change the exponent of the floating point number: it must be used after starting an integer expression for the overall exponent of the result.

34.2 Helpers for extended fixed points

\c_fp_one_fixed_t1 The extended fixed-point number 1, used in \3fp-expo.

```
12299 \tl_const:Nn \c_fp_one_fixed_t1
12300 { {10000} {0000} {0000} {0000} {0000} {0000} }
(End definition for \c_fp_one_fixed_t1)
```

__fp_fixed_continue:wn This function does nothing. Of course, there is no bound on a₁ (except TeX’s own $2^{31}-1$).

```
12301 \cs_new:Npn \__fp_fixed_continue:wn #1; #2 { #2 #1; }
(End definition for \__fp_fixed_continue:wn)
```

`_fp_fixed_add_one:wn` This function adds 1 to the fixed point $\langle a \rangle$, by changing a_1 to $10000 + a_1$, then calls the $\langle \text{continuation} \rangle$. This requires $a_1 \leq 2^{31} - 10001$.

```

12302 \cs_new:Npn \_fp_fixed_add_one:wn #1#2; #3
12303 {
12304   \exp_after:wn #3 \exp_after:wn
12305   { \int_use:N \int_eval:w \c_ten_thousand + #1 } #2 ;
12306 }
(End definition for \_fp_fixed_add_one:wn)

```

`_fp_fixed_mul_after:wn` The fixed point operations which involve multiplication end by calling this auxiliary. It braces the last block of digits, and places the $\langle \text{continuation} \rangle$ #2 in front. The $\langle \text{continuation} \rangle$ was brought up through the expansions by the packing functions.

```

12307 \cs_new:Npn \_fp_fixed_mul_after:wn #1; #2 { #2 {#1} }
(End definition for \_fp_fixed_mul_after:wn)

```

34.3 Dividing a fixed point number by a small integer

```

\_fp_fixed_div_int:wwN
\_fp_fixed_div_int_i:wnN
\_fp_fixed_div_int_ii:wnn
\_fp_fixed_div_int_iii:wnn
\_fp_fixed_div_int_pack:Nw
\_fp_fixed_div_int_after:Nw

```

Divides the fixed point number $\langle a \rangle$ by the (small) integer $0 < \langle n \rangle < 10^4$ and feeds the result to the $\langle \text{continuation} \rangle$. There is no bound on a_1 .

The arguments of the `i` auxiliary are 1: one of the a_i , 2: n , 3: the `ii` or the `iii` auxiliary. It computes a (somewhat tight) lower bound Q_i for the ratio a_i/n .

The `ii` auxiliary receives Q_i , n , and a_i as arguments. It adds Q_i to a surrounding integer expression, and starts a new one with the initial value 9999, which ensures that the result of this expression will have 5 digits. The auxiliary also computes $a_i - n \cdot Q_i$, placing the result in front of the 4 digits of a_{i+1} . The resulting $a'_{i+1} = 10^4(a_i - n \cdot Q_i) + a_{i+1}$ serves as the first argument for a new call to the `i` auxiliary.

When the `iii` auxiliary is called, the situation looks like this:

```

\_fp_fixed_div_int_after:Nw <continuation>
-1 + Q1
\_fp_fixed_div_int_pack:Nw 9999 + Q2
\_fp_fixed_div_int_pack:Nw 9999 + Q3
\_fp_fixed_div_int_pack:Nw 9999 + Q4
\_fp_fixed_div_int_pack:Nw 9999 + Q5
\_fp_fixed_div_int_pack:Nw 9999
\_fp_fixed_div_int_iii:wnn Q6 ; {⟨n⟩} {⟨a6⟩}

```

where expansion is happening from the last line up. The `iii` auxiliary adds $Q_6 + 2 \simeq a_6/n + 1$ to the last 9999, giving the integer closest to $10000 + a_6/n$.

Each pack auxiliary receives 5 digits followed by a semicolon. The first digit is added as a carry to the integer expression above, and the 4 other digits are braced. Each call to the pack auxiliary thus produces one brace group. The last brace group is produced by the `after` auxiliary, which places the $\langle \text{continuation} \rangle$ as appropriate.

```

12308 \cs_new:Npn \_fp_fixed_div_int:wwN #1#2#3#4#5#6 ; #7 ; #8
12309 {
12310   \exp_after:wn \_fp_fixed_div_int_after:Nw
12311   \exp_after:wn #8

```

```

12312 \int_use:N \_int_eval:w \c_minus_one
12313   \_fp_fixed_div_int_i:wnN
12314   #1; {#7} \_fp_fixed_div_int_ii:wnn
12315   #2; {#7} \_fp_fixed_div_int_ii:wnn
12316   #3; {#7} \_fp_fixed_div_int_ii:wnn
12317   #4; {#7} \_fp_fixed_div_int_ii:wnn
12318   #5; {#7} \_fp_fixed_div_int_ii:wnn
12319   #6; {#7} \_fp_fixed_div_int_iii:wnn ;
12320 }
12321 \cs_new:Npn \_fp_fixed_div_int_i:wnN #1; #2 #3
12322 {
12323   \exp_after:wN #3
12324   \int_use:N \_int_eval:w #1 / #2 - \c_one ;
12325   {#2}
12326   {#1}
12327 }
12328 \cs_new:Npn \_fp_fixed_div_int_ii:wnn #1; #2 #3
12329 {
12330   + #1
12331   \exp_after:wN \_fp_fixed_div_int_pack:Nw
12332   \int_use:N \_int_eval:w 9999
12333   \exp_after:wN \_fp_fixed_div_int_i:wnN
12334   \int_use:N \_int_eval:w #3 - #1*#2 \_int_eval_end:
12335 }
12336 \cs_new:Npn \_fp_fixed_div_int_iii:wnn #1; #2 #3 { + #1 + \c_two ; }
12337 \cs_new:Npn \_fp_fixed_div_int_pack:Nw #1 #2; { + #1; {#2} }
12338 \cs_new:Npn \_fp_fixed_div_int_after:Nw #1 #2; { #1 {#2} }
(End definition for \_fp_fixed_div_int:wwN This function is documented on page ??.)
```

34.4 Adding and subtracting fixed points

```

\_fp_fixed_add:wwn
\_fp_fixed_sub:wwn
\_fp_fixed_add_i:Nnnnnwnn
\_fp_fixed_add_ii:nnNnnnwN
\_fp_fixed_add_pack:NNNNNwn
\_fp_fixed_add_after:NNNNNwn
```

Computes $a + b$ (resp. $a - b$) and feeds the result to the *<continuation>*. This function requires $0 \leq a_1, b_1 < 50000$, and requires the result to be positive (this happens automatically for addition). The two functions only differ a sign, hence use a common auxiliary. It would be nice to grab the 12 brace groups in one go; only 9 parameters are allowed. Start by grabbing the two signs, a_1, \dots, a_4 , the rest of a , and b_1 and b_2 . The second auxiliary receives the rest of a , the sign multiplying b , the rest of b , and the *<continuation>* as arguments. After going down through the various level, we go back up, packing digits and bringing the *<continuation>* (#8, then #7) from the end of the argument list to its start.

```

12339 \cs_new_nopar:Npn \_fp_fixed_add:wwn { \_fp_fixed_add_i:Nnnnnwnn + }
12340 \cs_new_nopar:Npn \_fp_fixed_sub:wwn { \_fp_fixed_add_i:Nnnnnwnn - }
12341 \cs_new:Npn \_fp_fixed_add_i:Nnnnnwnn #1 #2#3#4#5 #6; #7#8
12342 {
12343   \exp_after:wN \_fp_fixed_add_after:NNNNNwn
12344   \int_use:N \_int_eval:w 9 9999 9998 + #2#3 #1 #7#8
12345   \exp_after:wN \_fp_fixed_add_pack:NNNNNwn
12346   \int_use:N \_int_eval:w 1 9999 9998 + #4#5
```

```

12347      \_fp_fixed_add_i:nnNnnwn #6 #1
12348  }
12349 \cs_new:Npn \_fp_fixed_add_i:nnNnnwn #1#2 #3 #4#5 #6#7 ; #8
12350 {
12351 #3 #4#5
12352 \exp_after:wN \_fp_fixed_add_pack:NNNNwn
12353 \int_use:N \_int_eval:w 2 0000 0000 #3 #6#7 + #1#2 ; {#8} ;
12354 }
12355 \cs_new:Npn \_fp_fixed_add_pack:NNNNwn #1 #2#3#4#5 #6; #7
12356 { + #1 ; {#7} {#2#3#4#5} {#6} }
12357 \cs_new:Npn \_fp_fixed_add_after:NNNNwn 1 #1 #2#3#4#5 #6; #7
12358 { #7 {#1#2#3#4#5} {#6} }

(End definition for \_fp_fixed_add:wwn and \_fp_fixed_sub:wwn These functions are documented on
page ??.)
```

34.5 Multiplying fixed points

`_fp_fixed_mul:wwn`
`_fp_fixed_mul_i:nnnnnnwn`

Computes $a \times b$ and feeds the result to *(continuation)*. This function requires $0 \leq a_1, b_1 < 10000$. Once more, we need to play around the limit of 9 arguments for TeX macros. Note that we don't need to obtain an exact rounding, contrarily to the `*` operator, so things could be harder. We wish to perform carries in

$$\begin{aligned} a \times b = & a_1 \cdot b_1 \cdot 10^{-8} \\ & + (a_1 \cdot b_2 + a_2 \cdot b_1) \cdot 10^{-12} \\ & + (a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1) \cdot 10^{-16} \\ & + (a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1) \cdot 10^{-20} \\ & + \left(a_2 \cdot b_4 + a_3 \cdot b_3 + a_4 \cdot b_2 + \frac{a_3 \cdot b_4 + a_4 \cdot b_3 + a_1 \cdot b_6 + a_2 \cdot b_5 + a_5 \cdot b_2 + a_6 \cdot b_1}{10^4} + a_1 \cdot b_5 + a_5 \cdot b_1 \right. \end{aligned}$$

where the $O(10^{-24})$ stands for terms which are at most $5 \cdot 10^{-24}$; ignoring those leads to an error of at most 5 ulp. Note how the first 15 terms only depend on a_1, \dots, a_4 and b_1, \dots, b_4 , while the last 6 terms only depend on a_1, a_2, a_5, a_6 , and the corresponding parts of b . Hence, the first function grabs a_1, \dots, a_4 , the rest of a , and b_1, \dots, b_4 , and writes the 15 first terms of the expression, including a left parenthesis for the fraction. The `i` auxiliary receives $a_5, a_6, b_1, b_2, a_1, a_2, b_5, b_6$ and finally the *(continuation)* as arguments. It writes the end of the expression, including the right parenthesis and the denominator of the fraction. The packing auxiliaries bring the *(continuation)* up through the expansion chain, as `#7`, and it is finally placed in front of the 6 brace groups by `_fp_fixed_mul_after:wn`.

```

12359 \cs_new:Npn \_fp_fixed_mul:wwn #1#2#3#4 #5; #6#7#8#9
12360 {
12361 \exp_after:wN \_fp_fixed_mul_after:wn
12362 \int_use:N \_int_eval:w \c_fp_leading_shift_int
12363 \exp_after:wN \_fp_pack:NNNNwn
12364 \int_use:N \_int_eval:w \c_fp_middle_shift_int
12365 + #1*#6
```

```

12366   \exp_after:wN \_fp_pack>NNNNNwn
12367   \int_use:N \_int_eval:w \c_fp_middle_shift_int
12368     + #1*#7 + #2*#6
12369   \exp_after:wN \_fp_pack>NNNNNwn
12370   \int_use:N \_int_eval:w \c_fp_middle_shift_int
12371     + #1*#8 + #2*#7 + #3*#6
12372   \exp_after:wN \_fp_pack>NNNNNwn
12373   \int_use:N \_int_eval:w \c_fp_middle_shift_int
12374     + #1*#9 + #2*#8 + #3*#7 + #4*#6
12375   \exp_after:wN \_fp_pack>NNNNNwn
12376   \int_use:N \_int_eval:w \c_fp_trailing_shift_int
12377     + #2*#9 + #3*#8 + #4*#7
12378     + ( #3*#9 + #4*#8
12379       + \fp_fixed_mul_i:nnnnnnnwn #5 {#6}{#7} {#1}{#2}
12380     )
12381 \cs_new:Npn \fp_fixed_mul_i:nnnnnnnwn #1#2 #3#4 #5#6 #7#8 ; #9
12382 {
12383   #1*#4 + #2*#3 + #5*#8 + #6*#7 ) / \c_ten_thousand
12384   + #1*#3 + #5*#7 ;
12385   {#9} ;
12386 }
(End definition for \fp_fixed_mul:wnn This function is documented on page ??.)
```

34.6 Combining product and sum of fixed points

```
\fp_fixed_mul_add:wwn
\fp_fixed_mul_sub_back:wwn
\fp_fixed_one_minus_mul:wwn
```

Compute $a \times b + c$, $c - a \times b$, and $1 - a \times b$ and feed the result to the *(continuation)*. Those functions require $0 \leq a_1, b_1, c_1 \leq 10000$. Since those functions are at the heart of the computation of Taylor expansions, we over-optimize them a bit, and in particular we do not factor out the common parts of the three functions.

For definiteness, consider the task of computing $a \times b + c$. We will perform carries in

$$\begin{aligned} a \times b + c = & (a_1 \cdot b_1 + c_1 c_2) \cdot 10^{-8} \\ & + (a_1 \cdot b_2 + a_2 \cdot b_1) \cdot 10^{-12} \\ & + (a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1 + c_3 c_4) \cdot 10^{-16} \\ & + (a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1) \cdot 10^{-20} \\ & + \left(a_2 \cdot b_4 + a_3 \cdot b_3 + a_4 \cdot b_2 + \frac{a_3 \cdot b_4 + a_4 \cdot b_3 + a_1 \cdot b_6 + a_2 \cdot b_5 + a_5 \cdot b_2 + a_6 \cdot b_1}{10^4} + a_1 \cdot b_5 + a_5 \right. \end{aligned}$$

where $c_1 c_2$, $c_3 c_4$, $c_5 c_6$ denote the 8-digit number obtained by juxtaposing the two blocks of digits of c , and \cdot denotes multiplication. The task is obviously tough because we have 18 brace groups in front of us.

Each of the three function starts the first two levels (the first, corresponding to 10^{-4} , is empty), with $c_1 c_2$ in the first level, calls the *i* auxiliary with arguments described later, and adds a trailing $+ c_5 c_6 ; \{ \text{(continuation)} \} ;$. The $+ c_5 c_6$ piece, which is omitted for $\fp_fixed_one_minus_mul:wnn$, will be taken in the integer expression for the 10^{-24} level. The *(continuation)* is placed correctly to be taken upstream by packing auxiliaries.

```
12387 \cs_new:Npn \fp_fixed_mul_add:wwn #1; #2; #3#4#5#6#7#8; #9
```

```

12388 {
12389   \exp_after:wN \_fp_fixed_mul_after:wn
12390   \int_use:N \_int_eval:w \c_fp_big_leading_shift_int
12391     \exp_after:wN \_fp_pack_big:NNNNNNwn
12392     \int_use:N \_int_eval:w \c_fp_big_middle_shift_int + #3 #4
12393       \_fp_fixed_mul_add_i:Nwnnnwnnn +
12394         + #5 #6 ; #2 ; #1 ; #2 ; +
12395         + #7 #8 ; {#9} ;
12396   }
12397 \cs_new:Npn \_fp_fixed_mul_sub_back:wwn #1; #2; #3#4#5#6#7#8; #9
12398 {
12399   \exp_after:wN \_fp_fixed_mul_after:wn
12400   \int_use:N \_int_eval:w \c_fp_big_leading_shift_int
12401     \exp_after:wN \_fp_pack_big:NNNNNNwn
12402     \int_use:N \_int_eval:w \c_fp_big_middle_shift_int + #3 #4
12403       \_fp_fixed_mul_add_i:Nwnnnwnnn -
12404         + #5 #6 ; #2 ; #1 ; #2 ; -
12405         + #7 #8 ; {#9} ;
12406   }
12407 \cs_new:Npn \_fp_fixed_one_minus_mul:wwn #1; #2; #3
12408 {
12409   \exp_after:wN \_fp_fixed_mul_after:wn
12410   \int_use:N \_int_eval:w \c_fp_big_leading_shift_int
12411     \exp_after:wN \_fp_pack_big:NNNNNNwn
12412     \int_use:N \_int_eval:w \c_fp_big_middle_shift_int + 1 0000 0000
12413       \_fp_fixed_mul_add_i:Nwnnnwnnn -
12414         ; #2 ; #1 ; #2 ; -
12415         ; {#3} ;
12416   }
(End definition for \_fp_fixed_mul_add:wwn, \_fp_fixed_mul_sub_back:wwn, and \_fp_fixed_one_minus_mul:wwn)

```

`_fp_fixed_mul_add_i:Nwnnnwnnn` Here, $\langle op \rangle$ is either $+$ or $-$. Arguments $\#3, \#4, \#5$ are $\langle b_1 \rangle, \langle b_2 \rangle, \langle b_3 \rangle$; arguments $\#7, \#8, \#9$ are $\langle a_1 \rangle, \langle a_2 \rangle, \langle a_3 \rangle$. We can build three levels: $a_1 \cdot b_1$ for 10^{-8} , $(a_1 \cdot b_2 + a_2 \cdot b_1)$ for 10^{-12} , and $(a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1 + c_3 c_4)$ for 10^{-16} . The $a-b$ products huse the sign $\#1$. Note that $\#2$ is empty for `_fp_fixed_one_minus_mul:wwn`. We call the `ii` auxiliary for levels 10^{-20} and 10^{-24} , keeping the pieces of $\langle a \rangle$ we've read, but not $\langle b \rangle$, since there is another copy later in the input stream.

```

12417 \cs_new:Npn \_fp_fixed_mul_add_i:Nwnnnwnnn #1 #2; #3#4#5#6; #7#8#9
12418 {
12419   #1 #7*#3
12420   \exp_after:wN \_fp_pack_big:NNNNNNwn
12421   \int_use:N \_int_eval:w \c_fp_big_middle_shift_int
12422     #1 #7*#4 #1 #8*#3
12423   \exp_after:wN \_fp_pack_big:NNNNNNwn
12424   \int_use:N \_int_eval:w \c_fp_big_middle_shift_int
12425     #1 #7*#5 #1 #8*#4 #1 #9*#3 #2
12426   \exp_after:wN \_fp_pack_big:NNNNNNwn
12427   \int_use:N \_int_eval:w \c_fp_big_middle_shift_int
12428     #1 \_fp_fixed_mul_add_ii:nnnnwnnnn {#7}{#8}{#9}

```

```

12429   }
(End definition for \_\_fp\_fixed\_mul\_add\_i:Nnnnnnnnnn)
```

__fp_fixed_mul_add_ii:nnnnnnnnnn Level 10^{-20} is $(a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1)$, multiplied by the sign, which was inserted by the *i* auxiliary. Then we prepare level 10^{-24} . We don't have access to all parts of $\langle a \rangle$ and $\langle b \rangle$ needed to make all products. Instead, we prepare the partial expressions

$$\begin{aligned} & b_1 + a_4 \cdot b_2 + a_3 \cdot b_3 + a_2 \cdot b_4 + a_1 \\ & b_2 + a_4 \cdot b_3 + a_3 \cdot b_4 + a_2. \end{aligned}$$

Obviously, those expressions make no mathematical sense: we will complete them with $a_5 \cdot$ and $\cdot b_5$, and with $a_6 \cdot b_1 + a_5 \cdot$ and $\cdot b_5 + a_1 \cdot b_6$, and of course with the trailing $+ c_5 c_6$. To do all this, we keep a_1, a_5, a_6 , and the corresponding pieces of $\langle b \rangle$.

```

12430 \cs_new:Npn \_\_fp_fixed_mul_add_ii:nnnnnnnnnn #1#2#3#4#5; #6#7#8#9
12431 {
12432   ( #1*#9 + #2*#8 + #3*#7 + #4*#6 )
12433   \exp_after:wN \_\_fp_pack_big:NNNNNNNwn
12434   \int_use:N \_\_int_eval:w \c_\_fp_big_trailing_shift_int
12435     \_\_fp_fixed_mul_add_iii:nnnnnnnnwN
12436     { #6 + #4*#7 + #3*#8 + #2*#9 + #1 }
12437     { #7 + #4*#8 + #3*#9 + #2 }
12438     {#1} #5;
12439     {#6}
12440 }
```

(End definition for __fp_fixed_mul_add_ii:nnnnnnnnnn)

__fp_fixed_mul_add_iii:nnnnnnnnwN Complete the $\langle \text{partial}_1 \rangle$ and $\langle \text{partial}_2 \rangle$ expressions as explained for the *ii* auxiliary. The second one is divided by 10000: this is the carry from level 10^{-28} . The trailing $+ c_5 c_6$ is taken into the expression for level 10^{-24} . Note that the total of level 10^{-24} is in the interval $[-5 \cdot 10^8, 6 \cdot 10^8]$ (give or take a couple of 10000), hence adding it to the shift gives a 10-digit number, as expected by the packing auxiliaries. See l3fp-aux for the definition of the shifts and packing auxiliaries.

```

12441 \cs_new:Npn \_\_fp_fixed_mul_add_iii:nnnnnnnnwN #1#2 #3#4#5; #6#7#8; #9
12442 {
12443   #9 (#4* #1 *#7)
12444   #9 (#5*#6+#4* #2 *#7+/#3*#8) / \c_ten_thousand
12445 }
```

(End definition for __fp_fixed_mul_add_iii:nnnnnnnnwN)

34.7 Converting from fixed point to floating point

__fp_fixed_to_float:wN yields

__fp_fixed_to_float:Nw $\langle \text{exponent}' \rangle ; \{ \langle a'_1 \rangle \} \{ \langle a'_2 \rangle \} \{ \langle a'_3 \rangle \} \{ \langle a'_4 \rangle \} ;$

And the `to_fixed` version gives six brace groups instead of 4, ensuring that $1000 \leq \langle a'_1 \rangle \leq 9999$. At this stage, we know that $\langle a_1 \rangle$ is positive (otherwise, it is sign of an error before), and we assume that it is less than 10^8 .¹⁷

```

12446 \cs_new:Npn \__fp_fixed_to_float:Nw #1#2; { \__fp_fixed_to_float:wN #2; #1 }
12447 \cs_new:Npn \__fp_fixed_to_float:wn #1#2#3#4#5#6; #
12448 {
12449     + \c_four % for the 8-digit-at-the-start thing.
12450     \exp_after:wN \exp_after:wN
12451     \exp_after:wN \__fp_fixed_to_loop:N
12452     \exp_after:wN \use_none:n
12453     \int_use:N \__int_eval:w
12454     1 0000 0000 + #1 \exp_after:wN \__fp_use_none_stop_f:n
12455     \__int_value:w 1#2 \exp_after:wN \__fp_use_none_stop_f:n
12456     \__int_value:w 1#3#4 \exp_after:wN \__fp_use_none_stop_f:n
12457     \__int_value:w 1#5#6
12458     \exp_after:wN ;
12459     \exp_after:wN ;
12460 }
12461 \cs_new:Npn \__fp_fixed_to_loop:N #1
12462 {
12463     \if_meaning:w 0 #1
12464         - \c_one
12465         \exp_after:wN \__fp_fixed_to_loop:N
12466     \else:
12467         \exp_after:wN \__fp_fixed_to_loop_end:w
12468         \exp_after:wN #1
12469     \fi:
12470 }
12471 \cs_new:Npn \__fp_fixed_to_loop_end:w #1 #2 ;
12472 {
12473     \if_meaning:w ; #1
12474         \exp_after:wN \__fp_fixed_to_float_zero:w
12475     \else:
12476         \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
12477         \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
12478         \exp_after:wN \__fp_fixed_to_float_pack:ww
12479         \exp_after:wN ;
12480     \fi:
12481     #1 #2 0000 0000 0000 0000 ;
12482 }
12483 \cs_new:Npn \__fp_fixed_to_float_zero:w ; 0000 0000 0000 0000 ;
12484 {
12485     - \c_two * \c_fp_max_exponent_int ;
12486     {0000} {0000} {0000} {0000} ;
12487 }
12488 \cs_new:Npn \__fp_fixed_to_float_pack:ww #1 ; #2#3 ;
12489 {
12490     \if_int_compare:w #2 > \c_four

```

¹⁷Bruno: I must double check this assumption.

```

12491     \exp_after:wN \__fp_fixed_to_float_round_up:wnnnnw
12492     \fi:
12493     ; #1 ;
12494 }
12495 \cs_new:Npn \__fp_fixed_to_float_round_up:wnnnnw ; #1#2#3#4 ;
12496 {
12497     \exp_after:wN \__fp_basics_pack_high>NNNNNw
12498     \int_use:N \__int_eval:w 1 #1#2
12499     \exp_after:wN \__fp_basics_pack_low>NNNNNw
12500     \int_use:N \__int_eval:w 1 #3#4 + \c_one ;
12501 }

(End definition for \__fp_fixed_to_float:wN and \__fp_fixed_to_float:Nw)

```

`__fp_fixed_inv_to_float:wN` Starting from `fixed_dtf A ; B` ; we want to compute A/B , and express it as a floating point number. Normalize both numbers by removing leading brace groups of zeros and leaving the appropriate exponent shift in the input stream.

```

12502 \cs_new:Npn \__fp_fixed_inv_to_float:wN #1#2; #3
12503 {
12504     + \__int_eval:w % ^^A todo: remove the +?
12505     \if_int_compare:w #1 < \c_one_thousand
12506         \__fp_fixed_dtf_zeros:wNnnnnnn
12507     \fi:
12508     \__fp_fixed_dtf_no_zero:Nwn + {#1} #2 \s__fp
12509     \__fp_fixed_dtf_approx:n
12510     {10000} {0000} {0000} {0000} {0000} ;
12511 }
12512 \cs_new:Npn \__fp_fixed_div_to_float:ww #1#2; #3#4;
12513 {
12514     \if_int_compare:w #1 < \c_one_thousand
12515         \__fp_fixed_dtf_zeros:wNnnnnnn
12516     \fi:
12517     \__fp_fixed_dtf_no_zero:Nwn - {#1} #2 \s__fp
12518 {
12519     \if_int_compare:w #3 < \c_one_thousand
12520         \__fp_fixed_dtf_zeros:wNnnnnnn
12521     \fi:
12522     \__fp_fixed_dtf_no_zero:Nwn + {#3} #4 \s__fp
12523     \__fp_fixed_dtf_approx:n
12524 }
12525 }
12526 \cs_new:Npn \__fp_fixed_dtf_no_zero:Nwn #1#2 \s__fp #3 { #3 #2; }
12527 \cs_new:Npn \__fp_fixed_dtf_zeros:wNnnnnnn
12528     \fi: \__fp_fixed_dtf_no_zero:Nwn #1#2#3#4#5#6#7
12529 {
12530     \fi:
12531     #1 \c_minus_one
12532     \exp_after:wN \use_i_i:nnn
12533     \exp_after:wN \__fp_fixed_dtf_zeros:NN
12534     \exp_after:wN #1

```

```

12535   \int_use:N \__int_eval:w 10 0000 + #2 \__int_eval_end: #3#4#5#6#7
12536   ; 1 ;
12537 }
12538 \cs_new:Npn \__fp_fixed_dtf_zeros>NN #1#2
12539 {
12540   \if_meaning:w 0 #2
12541     #1 \c_one
12542   \else:
12543     \__fp_fixed_dtf_zeros_end:wNww #2
12544   \fi:
12545   \__fp_fixed_dtf_zeros>NN #1
12546 }
12547 \cs_new:Npn \__fp_fixed_dtf_zeros_end:wNww
12548   #1 \fi: \__fp_fixed_dtf_zeros>NN #2 #3; #4 \s_fp
12549 {
12550   \fi:
12551   \if_meaning:w ; #1
12552     #2 \c_two * \c_fp_max_exponent_int
12553       \use_i_i:nnn
12554   \fi:
12555   \__fp_fixed_dtf_zeros_ii:ww
12556   #1#3 0000 0000 0000 0000 0000 0000 ;
12557 }
12558 \cs_new:Npn \__fp_fixed_dtf_zeros_ii:ww
12559 {
12560   \__fp_pack_twice_four:wNNNNNNNN
12561   \__fp_pack_twice_four:wNNNNNNNN
12562   \__fp_pack_twice_four:wNNNNNNNN
12563   \__fp_fixed_dtf_zeros_iii:ww
12564   ;
12565 }
12566 \cs_new:Npn \__fp_fixed_dtf_zeros_iii:ww #1; #2; #3 { #3 #1; }

```

We get

$$__fp_fixed_dtf_approx:n \langle B' \rangle ; \langle A' \rangle ;$$

where $\langle B' \rangle$ and $\langle A' \rangle$ are each 6 brace groups, representing fixed point numbers in the range $[0.1, 1)$. Denote by $x \in [1000, 9999]$ and $y \in [0, 9999]$ the first two groups of $\langle B' \rangle$. We first find an estimate a for the inverse of B' by computing

$$\begin{aligned} \alpha &= \left[\frac{10^9}{x+1} \right] \\ \beta &= \left[\frac{10^9}{x} \right] \\ a &= 10^3 \alpha + (\beta - \alpha) \cdot \left(10^3 - \left[\frac{y}{10} \right] \right) - 1750, \end{aligned}$$

where $\left[\frac{\bullet}{\bullet} \right]$ denotes ε -TeX's rounding division. The idea is to interpolate between α and β with a parameter $y/10^4$. The shift by 1750 helps to ensure that a is an underestimate

of the correct value. We will prove that

$$1 - 2.255 \cdot 10^{-5} < \frac{B'a}{10^8} < 1.$$

We can then compute the inverse $B'a/10^8$ using $1/(1 - \epsilon) \simeq (1 + \epsilon)(1 + \epsilon^2)$, which is correct up to a relative error of $\epsilon^4 < 2.6 \cdot 10^{-19}$. Since we target a 16-digit value, this is small enough.

Let us prove the upper bound first.

$$10^7 B'a < \left(10^3 x + \left[\frac{y}{10}\right] + \frac{3}{2}\right) \left(\left(10^3 - \left[\frac{y}{10}\right]\right) \beta + \left[\frac{y}{10}\right] \alpha - 1750\right) \quad (1)$$

$$< \left(10^3 x + \left[\frac{y}{10}\right] + \frac{3}{2}\right) \left(\left(10^3 - \left[\frac{y}{10}\right]\right) \left(\frac{10^9}{x} + \frac{1}{2}\right) + \left[\frac{y}{10}\right] \left(\frac{10^9}{x+1} + \frac{1}{2}\right) - 1750\right) \quad (2)$$

$$< \left(10^3 x + \left[\frac{y}{10}\right] + \frac{3}{2}\right) \left(\frac{10^{12}}{x} - \left[\frac{y}{10}\right] \frac{10^9}{x(x+1)} - 1250\right) \quad (3)$$

We recognize a quadratic polynomial in $[y/10]$ with a negative leading coefficient, $([y/10] + a)(b - c[y/10]) \leq (b + ca)^2/(4c)$. Hence,

$$10^7 B'a < \frac{10^{15}}{x(x+1)} \left(x + \frac{1}{2} + \frac{3}{4}10^{-3} - 6.25 \cdot 10^{-10}x(x+1)\right)^2$$

We want to prove that the squared expression is less than $x(x+1)$, which we do by simplifying the difference, and checking its sign,

$$x(x+1) - \left(x + \frac{1}{2} + \frac{3}{4}10^{-3} - 6.25 \cdot 10^{-10}x(x+1)\right)^2 > -\frac{1}{4}(1+1.5 \cdot 10^{-3})^2 - 10^{-3}x + 1.25 \cdot 10^{-9}x(x+1)(x+0.5)$$

Now, the lower bound. The same computation as (1) imply

$$10^7 B'a > \left(10^3 x + \left[\frac{y}{10}\right] - \frac{1}{2}\right) \left(\frac{10^{12}}{x} - \left[\frac{y}{10}\right] \frac{10^9}{x(x+1)} - 2250\right)$$

This time, we want to find the minimum of this quadratic polynomial. Since the leading coefficient is still negative, the minimum is reached for one of the extreme values $y = 0$ or $y = 9999$, and we easily check the bound for those values.

We have proven that the algorithm will give us a precise enough answer. Incidentally, the upper bound that we derived tells us that $a < 10^8/B \leq 10^9$, hence we can compute a safely as a TeX integer, and even add 10^9 to it to ease grabbing of all the digits.

```

12567 \cs_new:Npn \__fp_fixed_dtf_approx:n #1
12568 {
12569   \exp_after:wN \__fp_fixed_dtf_approx_ii:wnn
12570   \int_use:N \__int_eval:w 10 0000 0000 / ( #1 + \c_one ) ;
12571   {#1}
12572 }
```

```

12573 \cs_new:Npn \__fp_fixed_dtf_approx_ii:wnn #1; #2#3
12574 {
12575   \assert{ \assert{n { \tl_count:n } = 6 } }
12576   \exp_after:wn \__fp_fixed_dtf_approx_iii:NNNNNw
12577   \int_use:N \__int_eval:w 10 0000 0000 - 1750
12578   + #1000 + (10 0000 0000/#2-#1) * (1000-#3/10) ;
12579   {#2}{#3}
12580 }
12581 \cs_new:Npn \__fp_fixed_dtf_approx_iii:NNNNNw 1#1#2#3#4#5#6; #7; #8;
12582 {
12583   + \c_four % because of the line below "dtf_epsilon" here.
12584   \__fp_fixed_mul:wnn {000#1}{#2#3#4#5}{#6}{0000}{0000} ; #7;
12585   \__fp_fixed_dtf_epsilon:wn
12586   \__fp_fixed_mul:wnn {000#1}{#2#3#4#5}{#6}{0000}{0000} ;
12587   \__fp_fixed_mul:wnn #8;
12588   \__fp_fixed_to_float:wn ?
12589 }
12590 \cs_new:Npn \__fp_fixed_dtf_epsilon:wn #1#2#3#4#5#6;
12591 {
12592   \assert{ #1 = 0000 }
12593   \assert{ #2 = 9999 }
12594   \exp_after:wn \__fp_fixed_dtf_epsilon_ii:NNNNNww
12595   \int_use:N \__int_eval:w 1 9999 9998 - #3#4 +
12596   \exp_after:wn \__fp_fixed_dtf_epsilon_pack:NNNNNw
12597   \int_use:N \__int_eval:w 2 0000 0000 - #5#6 ; {0000} ;
12598 }
12599 \cs_new:Npn \__fp_fixed_dtf_epsilon_pack:NNNNNw #1#2#3#4#5#6;
12600 { #1 ; {#2#3#4#5} {#6} }
12601 \cs_new:Npn \__fp_fixed_dtf_epsilon_ii:NNNNNww #1#2#3#4#5#6; #7;
12602 {
12603   \__fp_fixed_mul:wnn %^^A todo: optimize to use \__fp_mul_significand.
12604   {0000} {#2#3#4#5} {#6} #7 ;
12605   {0000} {#2#3#4#5} {#6} #7 ;
12606   \__fp_fixed_add_one:wn
12607   \__fp_fixed_mul:wnn {10000} {#2#3#4#5} {#6} #7 ;
12608 }

(End definition for \__fp_fixed_inv_to_float:wn and \__fp_fixed_div_to_float:ww)

12609 </initex | package>

```

35 l3fp-expo implementation

```

12610 <*initex | package>
12611 <@@=fp>

```

35.1 Logarithm

35.1.1 Work plan

As for many other functions, we filter out special cases in `_fp_ln_o:w`. Then `_fp_ln_npos_o:w` receives a positive normal number, which we write in the form $a \cdot 10^b$ with $a \in [0.1, 1]$.

The rest of this section is actually not in sync with the code. Or is the code not in sync with the section?

We are given a positive normal number, of the form $a \cdot 10^b$ with $a \in [0.1, 1)$. To compute its logarithm, we find a small integer $5 \leq c < 50$ such that $0.91 \leq ac/5 < 1.1$, and use the relation

$$\ln(a \cdot 10^b) = b \cdot \ln(10) - \ln(c/5) + \ln(ac/5).$$

The logarithms $\ln(10)$ and $\ln(c/5)$ are looked up in a table. The last term is computed using the following Talor series of \ln near 1:

$$\ln\left(\frac{ac}{5}\right) = \ln\left(\frac{1+t}{1-t}\right) = 2t \left(1 + t^2 \left(\frac{1}{3} + t^2 \left(\frac{1}{5} + t^2 \left(\frac{1}{7} + t^2 \left(\frac{1}{9} + \dots\right)\right)\right)\right)\right)$$

where $t = 1 - 10/(ac + 5)$. We can now see one reason for the choice of $ac \sim 5$: then $ac + 5 = 10(1 - \epsilon)$ with $-0.05 < \epsilon \leq 0.045$, hence

$$t = \frac{\epsilon}{1 - \epsilon} = \epsilon(1 + \epsilon)(1 + \epsilon^2)(1 + \epsilon^4) \dots,$$

is not too difficult to compute.

35.1.2 Some constants

A few values of the logarithm as extended fixed point numbers. Those are needed in the implementation. It turns out that we don't need the value of $\ln(5)$.

```

12612 \tl_const:Nn \c_fp_ln_i_fixed_tl  { {0000}{0000}{0000}{0000}{0000} }
12613 \tl_const:Nn \c_fp_ln_ii_fixed_tl  { {6931}{4718}{0559}{9453}{0941}{7232} }
12614 \tl_const:Nn \c_fp_ln_iii_fixed_tl  {{10986}{1228}{8668}{1096}{9139}{5245} }
12615 \tl_const:Nn \c_fp_ln_iv_fixed_tl  {{13862}{9436}{1119}{8906}{1883}{4464} }
12616 \tl_const:Nn \c_fp_ln_vi_fixed_tl  {{17917}{5946}{9228}{0550}{0081}{2477} }
12617 \tl_const:Nn \c_fp_ln_vii_fixed_tl {{19459}{1014}{9055}{3133}{0510}{5353} }
12618 \tl_const:Nn \c_fp_ln_viii_fixed_tl{{20794}{4154}{1679}{8359}{2825}{1696} }
12619 \tl_const:Nn \c_fp_ln_ix_fixed_tl  {{21972}{2457}{7336}{2193}{8279}{0490} }
12620 \tl_const:Nn \c_fp_ln_x_fixed_tl  {{23025}{8509}{2994}{0456}{8401}{7991} }

(End definition for \c_fp_ln_i_fixed_tl and others.)
```

35.1.3 Sign, exponent, and special numbers

`_fp_ln_o:w` The logarithm of negative numbers (including $-\infty$ and -0) raises the “invalid” exception. The logarithm of $+0$ is $-\infty$, raising a division by zero exception. The logarithm of $+\infty$ or a `nan` is itself. Positive normal numbers call `_fp_ln_npos_o:w`.

```

12621 \cs_new:Npn \__fp_ln_o:w \s__fp \__fp_chk:w #1 #2
12622 {
12623   \if_meaning:w 2 #2
12624     \__fp_case_use:nw { \__fp_invalid_operation_o:nw { ln } }
12625   \fi:
12626   \if_case:w #1 \exp_stop_f:
12627     \__fp_case_use:nw
12628       { \__fp_division_by_zero_o:Nnw \c_minus_inf_fp { ln } }
12629   \or:
12630   \else:
12631     \__fp_case_return_same_o:w
12632   \fi:
12633   \__fp_ln_npos_o:w \s__fp \__fp_chk:w #1#2
12634 }
```

(End definition for `__fp_ln_o:w`)

35.1.4 Absolute ln

`__fp_ln_npos_o:w` We catch the case of a significand very close to 0.1 or to 1. In all other cases, the final result is at least 10^{-4} , and then an error of $0.5 \cdot 10^{-20}$ is acceptable.

```

12635 \cs_new:Npn \__fp_ln_npos_o:w \s__fp \__fp_chk:w 10#1#2#3;
12636   { %^A todo: ln(1) should be "exact zero", not "underflow"
12637     \exp_after:WN \__fp_sanitize:Nw
12638     \__int_value:w % for the overall sign
12639     \if_int_compare:w #1 < \c_one
12640       2
12641     \else:
12642       0
12643     \fi:
12644     \exp_after:wN \exp_stop_f:
12645     \int_use:N \__int_eval:w % for the exponent
12646     \__fp_ln_significand:NNNNnnnN #2#3
12647     \__fp_ln_exponent:wn {#1}
12648 }
```

(End definition for `__fp_ln_npos_o:w`)

`__fp_ln_significand:NNNNnnnN` $\langle X_1 \rangle \{ \langle X_2 \rangle \} \{ \langle X_3 \rangle \} \{ \langle X_4 \rangle \} \langle \text{continuation} \rangle$

This function expands to

$\langle \text{continuation} \rangle \{ \langle Y_1 \rangle \} \{ \langle Y_2 \rangle \} \{ \langle Y_3 \rangle \} \{ \langle Y_4 \rangle \} \{ \langle Y_5 \rangle \} \{ \langle Y_6 \rangle \} ;$

where $Y = -\ln(X)$ as an extended fixed point.

```

12649 \cs_new:Npn \__fp_ln_significand:NNNNnnnN #1#2#3#4
12650 {
12651   \exp_after:WN \__fp_ln_x_i:wnnnn
12652   \__int_value:w
12653   \if_case:w #1 \exp_stop_f:
12654   \or:
12655     \if_int_compare:w #2 < \c_four
```

```

12656           \__int_eval:w \c_ten - #2
12657     \else:
12658       6
12659     \fi:
12660   \or: 4
12661   \or: 3
12662   \or: 2
12663   \or: 2
12664   \or: 2
12665   \else: 1
12666   \fi:
12667 ; { #1 #2 #3 #4 }
12668 }
```

(End definition for `_fp_ln_significand:NNNNnnnN`)

`_fp_ln_x_ii:wnnnn` We have thus found c . It is chosen such that $0.7 \leq ac < 1.4$ in all cases. Compute $1 + x = 1 + ac \in [1.7, 2.4)$.

```

12669 \cs_new:Npn \_fp_ln_x_ii:wnnnn #1; #2#3#4#5
12670 {
12671   \exp_after:wN \_fp_ln_div_after:Nw
12672   \cs:w c_fp_ln_ \tex_roman numeral:D #1 _fixed_tl \exp_after:wN \cs_end:
12673   \__int_value:w
12674     \exp_after:wN \_fp_ln_x_iv:wnnnnnnnn
12675     \int_use:N \__int_eval:w
12676     \exp_after:wN \_fp_ln_x_iii_var:NNNNNw
12677     \int_use:N \__int_eval:w 9999 9999 + #1*#2#3 +
12678     \exp_after:wN \_fp_ln_x_iii:NNNNNw
12679     \int_use:N \__int_eval:w 1 0000 0000 + #1*#4#5 ;
12680     {20000} {0000} {0000} {0000}
12681 } %^A todo: reoptimize (a generalization attempt failed).
12682 \cs_new:Npn \_fp_ln_x_iii:NNNNNw #1 #2#3#4#5 #6; { #1; {#2#3#4#5} {#6} }
12683 \cs_new:Npn \_fp_ln_x_iii_var:NNNNNw #1 #2#3#4#5 #6;
12684 {
12685   #1#2#3#4#5 + \c_one ;
12686   {#1#2#3#4#5} {#6}
12687 }
```

The Taylor series will be expressed in terms of $t = (x-1)/(x+1) = 1-2/(x+1)$. We now compute the quotient with extended precision, reusing some code from `_fp/_o:ww`. Note that $1+x$ is known exactly.

To reuse notations from `l3fp-basics`, we want to compute A/Z with $A = 2$ and $Z = x+1$. In `l3fp-basics`, we considered the case where both A and Z are arbitrary, in the range $[0.1, 1)$, and we had to monitor the growth of the sequence of remainders A, B, C , etc. to ensure that no overflow occurred during the computation of the next quotient. The main source of risk was our choice to define the quotient as roughly $10^9 \cdot A / 10^5 \cdot Z$: then A was bound to be below $2.147\cdots$, and this limit was never far.

In our case, we can simply work with $10^8 \cdot A$ and $10^4 \cdot Z$, because our reason to work with higher powers has gone: we needed the integer $y \simeq 10^5 \cdot Z$ to be at least 10^4 , and now, the definition $y \simeq 10^4 \cdot Z$ suffices.

Let us thus define $y = \lfloor 10^4 \cdot Z \rfloor + 1 \in (1.7 \cdot 10^4, 2.4 \cdot 10^4]$, and

$$Q_1 = \left\lfloor \frac{\lfloor 10^8 \cdot A \rfloor}{y} - \frac{1}{2} \right\rfloor.$$

(The $1/2$ comes from how eTEX rounds.) As for division, it is easy to see that $Q_1 \leq 10^4 A/Z$, i.e., Q_1 is an underestimate.

Exactly as we did for division, we set $B = 10^4 A - Q_1 Z$. Then

$$10^4 B \leq A_1 A_2 \cdot A_3 A_4 - \left(\frac{A_1 A_2}{y} - \frac{3}{2} \right) 10^4 Z \leq A_1 A_2 \left(1 - \frac{10^4 Z}{y} \right) + 1 + \frac{3}{2} y \leq 10^8 \frac{A}{y} + 1 + \frac{3}{2} y$$

In the same way, and using $1.7 \cdot 10^4 \leq y \leq 2.4 \cdot 10^4$, and convexity, we get

$$\begin{aligned} 10^4 A &= 2 \cdot 10^4 \\ 10^4 B &\leq 10^8 \frac{A}{y} + 1.6y \leq 4.7 \cdot 10^4 \\ 10^4 C &\leq 10^8 \frac{B}{y} + 1.6y \leq 5.8 \cdot 10^4 \\ 10^4 D &\leq 10^8 \frac{C}{y} + 1.6y \leq 6.3 \cdot 10^4 \\ 10^4 E &\leq 10^8 \frac{D}{y} + 1.6y \leq 6.5 \cdot 10^4 \\ 10^4 F &\leq 10^8 \frac{E}{y} + 1.6y \leq 6.6 \cdot 10^4 \end{aligned}$$

Note that we compute more steps than for division: since t is not the end result, we need to know it with more accuracy (on the other hand, the ending is much simpler, as we don't need an exact rounding for transcendental functions, but just a faithful rounding).¹⁸

`__fp_ln_x_iv:wnnnnnnnnn {1 or 2} {8d} ; {\{4d\}} {\{4d\}} {fixed-tl}`

The number is x . Compute y by adding 1 to the five first digits.

```

12688 \cs_new:Npn \_\_fp\_ln\_x\_iv:wnnnnnnnnn #1; #2#3#4#5 #6#7#8#9
12689 {
12690   \exp_after:wN \_\_fp\_div\_significand\_pack:NNN
12691   \int_use:N \_\_int\_eval:w
12692   \_\_fp\_ln\_div\_i:w #1 ;
12693   #6 #7 ; {#8} {#9}
12694   {#2} {#3} {#4} {#5}
12695   { \exp_after:wN \_\_fp\_ln\_div\_ii:wwn \_\_int\_value:w #1 }
12696   { \exp_after:wN \_\_fp\_ln\_div\_ii:wwn \_\_int\_value:w #1 }
12697   { \exp_after:wN \_\_fp\_ln\_div\_ii:wwn \_\_int\_value:w #1 }
12698   { \exp_after:wN \_\_fp\_ln\_div\_ii:wwn \_\_int\_value:w #1 }
```

¹⁸Bruno: to be completed.

```

12699     { \exp_after:wN \__fp_ln_div_vi:wwn \__int_value:w #1 }
12700   }
12701 \cs_new:Npn \__fp_ln_div_i:w #1;
12702 {
12703   \exp_after:wN \__fp_div_significand_calc:wwnnnnnn
12704   \int_use:N \__int_eval:w 999999 + 2 0000 0000 / #1 ; % Q1
12705 }
12706 \cs_new:Npn \__fp_ln_div_ii:wwn #1; #2;#3 % y; B1;B2 <- for k=1
12707 {
12708   \exp_after:wN \__fp_div_significand_pack:NNN
12709   \int_use:N \__int_eval:w
12710   \exp_after:wN \__fp_div_significand_calc:wwnnnnnn
12711   \int_use:N \__int_eval:w 999999 + #2 #3 / #1 ; % Q2
12712   #2 #3 ;
12713 }
12714 \cs_new:Npn \__fp_ln_div_vi:wwn #1; #2;#3#4#5 #6#7#8#9 %y;F1;F2F3F4x1x2x3x4
12715 {
12716   \exp_after:wN \__fp_div_significand_pack:NNN
12717   \int_use:N \__int_eval:w 1000000 + #2 #3 / #1 ; % Q6
12718 }

```

We now have essentially¹⁹

$$\begin{aligned} & __fp_ln_div_after:Nw \langle \text{fixed } tl \rangle __fp_div_significand_pack:NNN 10^6 + \\ & Q_1 __fp_div_significand_pack:NNN 10^6 + Q_2 __fp_div_significand_- \\ & pack:NNN 10^6 + Q_3 __fp_div_significand_pack:NNN 10^6 + Q_4 __fp_- \\ & div_significand_pack:NNN 10^6 + Q_5 __fp_div_significand_pack:NNN \\ & 10^6 + Q_6 ; \langle \text{exponent} \rangle ; \langle \text{continuation} \rangle \end{aligned}$$

where $\langle \text{fixed } tl \rangle$ holds the logarithm of a number in $[1, 10]$, and $\langle \text{exponent} \rangle$ is the exponent. Also, the expansion is done backwards. Then $__fp_div_significand_pack:NNN$ puts things in the correct order to add the Q_i together and put semicolons between each piece. Once those have been expanded, we get

$$\begin{aligned} & __fp_ln_div_after:Nw \langle \text{fixed-tl} \rangle \langle 1d \rangle ; \langle 4d \rangle ; \\ & \langle 4d \rangle ; \langle \text{exponent} \rangle ; \end{aligned}$$

Just as with division, we know that the first two digits are 1 and 0 because of bounds on the final result of the division $2/(x+1)$, which is between roughly 0.8 and 1.2. We then compute $1 - 2/(x+1)$, after testing whether $2/(x+1)$ is greater than or smaller than 1.

```

12719 \cs_new:Npn \__fp_ln_div_after:Nw #1#2;
12720 {
12721   \if_meaning:w 0 #2
12722     \exp_after:wN \__fp_ln_t_small:Nw
12723   \else:
12724     \exp_after:wN \__fp_ln_t_large>NNw
12725     \exp_after:wN -
12726   \fi:

```

¹⁹Bruno: add a mention that the error on Q_6 is bounded by 10 (probably 6.7), and thus corresponds to an error of 10^{-23} on the final result, small enough in all cases.

```

12727      #1
12728  }
12729 \cs_new:Npn \__fp_ln_t_small:Nw #1 #2; #3; #4; #5; #6; #7;
12730 {
12731   \exp_after:wN \__fp_ln_t_large>NNw
12732   \exp_after:wN + % <sign>
12733   \exp_after:wN #1
12734   \int_use:N \__int_eval:w 9999 - #2 \exp_after:wN ;
12735   \int_use:N \__int_eval:w 9999 - #3 \exp_after:wN ;
12736   \int_use:N \__int_eval:w 9999 - #4 \exp_after:wN ;
12737   \int_use:N \__int_eval:w 9999 - #5 \exp_after:wN ;
12738   \int_use:N \__int_eval:w 9999 - #6 \exp_after:wN ;
12739   \int_use:N \__int_eval:w 1 0000 - #7 ;
12740 }

\__fp_ln_t_large>NNw <sign><fixed tl> <t1>; <t2>; <t3>; <t4>; <t5>; <t6>;
<exponent>; <continuation>

```

Compute the square t^2 , and keep t at the end with its sign. We know that $t < 0.1765$, so every piece has at most 4 digits. However, since we were not careful in `__fp_ln_t_small:w`, they can have less than 4 digits.

```

12741 \cs_new:Npn \__fp_ln_t_large>NNw #1 #2 #3; #4; #5; #6; #7; #8;
12742 {
12743   \exp_after:wN \__fp_ln_square_t_after:w
12744   \int_use:N \__int_eval:w 9999 0000 + #3*#3
12745   \exp_after:wN \__fp_ln_square_t_pack:NNNNNw
12746   \int_use:N \__int_eval:w 9999 0000 + 2*#3*#4
12747   \exp_after:wN \__fp_ln_square_t_pack:NNNNNw
12748   \int_use:N \__int_eval:w 9999 0000 + 2*#3*#5 + #4*#4
12749   \exp_after:wN \__fp_ln_square_t_pack:NNNNNw
12750   \int_use:N \__int_eval:w 9999 0000 + 2*#3*#6 + 2*#4*#5
12751   \exp_after:wN \__fp_ln_square_t_pack:NNNNNw
12752   \int_use:N \__int_eval:w 1 0000 0000 + 2*#3*#7 + 2*#4*#6 + #5*#5
12753   + (2*#3*#8 + 2*#4*#7 + 2*#5*#6) / 1 0000
12754   % ; ; ;
12755   \exp_after:wN \__fp_ln_twice_t_after:w
12756   \int_use:N \__int_eval:w -1 + 2*#3
12757   \exp_after:wN \__fp_ln_twice_t_pack:Nw
12758   \int_use:N \__int_eval:w 9999 + 2*#4
12759   \exp_after:wN \__fp_ln_twice_t_pack:Nw
12760   \int_use:N \__int_eval:w 9999 + 2*#5
12761   \exp_after:wN \__fp_ln_twice_t_pack:Nw
12762   \int_use:N \__int_eval:w 9999 + 2*#6
12763   \exp_after:wN \__fp_ln_twice_t_pack:Nw
12764   \int_use:N \__int_eval:w 9999 + 2*#7
12765   \exp_after:wN \__fp_ln_twice_t_pack:Nw
12766   \int_use:N \__int_eval:w 10000 + 2*#8 ; ;
12767 { \__fp_ln_c:NwNw #1 }
12768 #2

```

```

12769 }
12770 \cs_new:Npn \__fp_ln_twice_t_pack:Nw #1 #2; { + #1 ; {#2} }
12771 \cs_new:Npn \__fp_ln_twice_t_after:w #1; { ;; {#1} }
12772 \cs_new:Npn \__fp_ln_square_t_pack:NNNNNw #1 #2#3#4#5 #6;
12773 { + #1#2#3#4#5 ; {#6} }
12774 \cs_new:Npn \__fp_ln_square_t_after:w 1 0 #1#2#3 #4;
12775 { \__fp_ln_Taylor:wwNw {0#1#2#3} {#4} }
(End definition for \__fp_ln_x_ii:wnnnn)

```

__fp_ln_Taylor:wwNw Denoting $T = t^2$, we get

```

\__fp_ln_Taylor:wwNw {\langle T_1\rangle} {\langle T_2\rangle} {\langle T_3\rangle} {\langle T_4\rangle} {\langle T_5\rangle} {\langle T_6\rangle} ; ;
{\langle (2t)_1\rangle} {\langle (2t)_2\rangle} {\langle (2t)_3\rangle} {\langle (2t)_4\rangle} {\langle (2t)_5\rangle} {\langle (2t)_6\rangle} ; { \__fp_ln-
c:NwNn \langle sign\rangle } \langle fixed tl\rangle \langle exponent\rangle ; \langle continuation\rangle

```

And we want to compute

$$\ln\left(\frac{1+t}{1-t}\right) = 2t \left(1 + T\left(\frac{1}{3} + T\left(\frac{1}{5} + T\left(\frac{1}{7} + T\left(\frac{1}{9} + \dots\right)\right)\right)\right)\right)$$

The process looks as follows

```

\loop 5; A;
\div_int 5; 1.0; \add A; \mul T; {\loop \eval 5-2;}
\add 0.2; A; \mul T; {\loop \eval 5-2;}
\mul B; T; {\loop 3;}
\loop 3; C;

```

²⁰

This uses the routine for dividing a number by a small integer ($< 10^4$).

```

12776 \cs_new:Npn \__fp_ln_Taylor:wwNw
12777 { \__fp_ln_Taylor_loop:www 21 ; {0000}{0000}{0000}{0000}{0000}{0000} ; }
12778 \cs_new:Npn \__fp_ln_Taylor_loop:www #1; #2; #3;
12779 {
12780     \if_int_compare:w #1 = \c_one
12781         \__fp_ln_Taylor_break:w
12782     \fi:
12783     \exp_after:wn \__fp_fixed_div_int:wnN \c_fp_one_fixed_tl ; #1;
12784     \__fp_fixed_add:wn #2;
12785     \__fp_fixed_mul:wn #3;
12786     {
12787         \exp_after:wn \__fp_ln_Taylor_loop:www
12788         \int_use:N \__int_eval:w #1 - \c_two ;
12789     }
12790     #3;
12791 }
12792 \cs_new:Npn \__fp_ln_Taylor_break:w \fi: #1 \__fp_fixed_add:wn #2#3; #4 ;;
12793 {

```

²⁰Bruno: add explanations.

```

12794     \fi:
12795     \exp_after:wN \_fp_fixed_mul:wwn
12796     \exp_after:wN { \int_use:N \int_eval:w 10000 + #2 } #3;
12797 }
(End definition for \_fp_ln_Taylor:wwNw This function is documented on page ??.)
```

_fp_ln_c:NwNw $_fp_ln_c:NwNw \langle sign \rangle \{ \langle r_1 \rangle \} \{ \langle r_2 \rangle \} \{ \langle r_3 \rangle \} \{ \langle r_4 \rangle \} \{ \langle r_5 \rangle \} \{ \langle r_6 \rangle \} ; \langle fixed \; tl \rangle \langle exponent \rangle ; \langle continuation \rangle$

We are now reduced to finding $\ln(c)$ and $\langle exponent \rangle \ln(10)$ in a table, and adding it to the mixture. The first step is to get $\ln(c) - \ln(x) = -\ln(a)$, then we get $b \ln(10)$ and add or subtract.

For now, $\ln(x)$ is given as $\cdot 10^0$. Unless both the exponent is 1 and $c = 1$, we shift to working in units of $\cdot 10^4$, since the final result will be at least $\ln(10/7) \simeq 0.35$.²¹

```

12798 \cs_new:Npn \_fp_ln_c:NwNw #1 #2; #3
12799 {
12800     \if_meaning:w + #1
12801         \exp_after:wN \exp_after:wN \exp_after:wN \_fp_fixed_sub:wwn
12802     \else:
12803         \exp_after:wN \exp_after:wN \exp_after:wN \_fp_fixed_add:wwn
12804     \fi:
12805     #3 ; #2 ;
12806 }
```

²²

(End definition for _fp_ln_c:NwNw This function is documented on page ??.)

_fp_ln_exponent:wn $_fp_ln_exponent:wn \{ \langle s_1 \rangle \} \{ \langle s_2 \rangle \} \{ \langle s_3 \rangle \} \{ \langle s_4 \rangle \} \{ \langle s_5 \rangle \} \{ \langle s_6 \rangle \} ; \{ \langle exponent \rangle \}$

Compute $\langle exponent \rangle$ times $\ln(10)$. Apart from the cases where $\langle exponent \rangle$ is 0 or 1, the result will necessarily be at least $\ln(10) \simeq 2.3$ in magnitude. We can thus drop the least significant 4 digits. In the case of a very large (positive or negative) exponent, we can (and we need to) drop 4 additional digits, since the result is of order 10^4 . Naively, one would think that in both cases we can drop 4 more digits than we do, but that would be slightly too tight for rounding to happen correctly. Besides, we already have addition and subtraction for 24 digits fixed point numbers.

```

12807 \cs_new:Npn \_fp_ln_exponent:wn #1; #2
12808 {
12809     \if_case:w #2 \exp_stop_f:
12810         \c_zero \fp_case_return:nw { \fp_fixed_to_float:Nw 2 }
12811     \or:
12812         \exp_after:wN \_fp_ln_exponent_one:ww \int_value:w
12813     \else:
12814         \if_int_compare:w #2 > \c_zero
12815             \exp_after:wN \_fp_ln_exponent_small:NNww
12816             \exp_after:wN 0
12817             \exp_after:wN \_fp_fixed_sub:wwn \int_value:w
12818     \else:
```

²¹Bruno: that was wrong at some point, I must check.

²²Bruno: this **must** be updated with correct values!

```

12819      \exp_after:wN \__fp_ln_exponent_small:NNww
12820      \exp_after:wN 2
12821      \exp_after:wN \__fp_fixed_add:wwn \__int_value:w -
12822      \fi:
12823      \fi:
12824      #2; #1;
12825  }

```

Now we painfully write all the cases.²³ No overflow nor underflow can happen, except when computing $\ln(1)$.

```

12826 \cs_new:Npn \__fp_ln_exponent_one:ww 1; #1;
12827 {
12828   \c_zero
12829   \exp_after:wN \__fp_fixed_sub:wwn \c__fp_ln_x_fixed_tl ; #1;
12830   \__fp_fixed_to_float:wN 0
12831 }

```

For small exponents, we just drop one block of digits, and set the exponent of the log to 4 (minus any shift coming from leading zeros in the conversion from fixed point to floating point). Note that here the exponent has been made positive.

```

12832 \cs_new:Npn \__fp_ln_exponent_small:NNww #1#2#3; #4#5#6#7#8#9;
12833 {
12834   \c_four
12835   \exp_after:wN \__fp_fixed_mul:wwn
12836     \c__fp_ln_x_fixed_tl ;
12837     {#3}{0000}{0000}{0000}{0000} ;
12838   #2
12839   {0000}{#4}{#5}{#6}{#7}{#8};
12840   \__fp_fixed_to_float:wN #1
12841 }

```

(End definition for $__fp_ln_exponent:wn$. This function is documented on page ??.)

35.2 Exponential

35.2.1 Sign, exponent, and special numbers

```

\__fp_exp_o:w
12842 \cs_new:Npn \__fp_exp_o:w \s__fp \__fp_chk:w #1#2
12843 {
12844   \if_case:w #1 \exp_stop_f:
12845     \__fp_case_return_o:Nw \c_one_fp
12846   \or:
12847     \exp_after:wN \__fp_exp_normal:w
12848   \or:
12849     \if_meaning:w 0 #2
12850       \exp_after:wN \__fp_case_return_o:Nw
12851       \exp_after:wN \c_inf_fp
12852   \else:

```

²³Bruno: do rounding.

```

12853           \exp_after:wN \__fp_case_return_o:Nw
12854           \exp_after:wN \c_zero_fp
12855       \fi:
12856   \or:
12857       \__fp_case_return_same_o:w
12858   \fi:
12859   \s_fp \__fp_chk:w #1#2
12860 }
(End definition for \__fp_exp_o:w)

\__fp_exp_normal:w
\__fp_exp_pos:Nnwnw
12861 \cs_new:Npn \__fp_exp_normal:w \s_fp \__fp_chk:w 1#1
12862 {
12863     \if_meaning:w 0 #1
12864         \__fp_exp_pos>NNnw + \__fp_fixed_to_float:wN
12865     \else:
12866         \__fp_exp_pos>NNnw - \__fp_fixed_inv_to_float:wN
12867     \fi:
12868 }
12869 \cs_new:Npn \__fp_exp_pos>NNnw #1#2#3 \fi: #4#5;
12870 {
12871     \fi:
12872     \exp_after:wN \__fp_sanitize:Nw
12873     \exp_after:wN 0
12874     \__int_value:w #1 \__int_eval:
12875         \if_int_compare:w #4 < - \c_eight
12876             \c_one
12877             \exp_after:wN \__fp_add_big_i_o:wNww
12878             \int_use:N \__int_eval:w \c_one - #4 ;
12879             0 {1000}{0000}{0000}{0000} ; #5;
12880             \tex_roman numeral:D
12881         \else:
12882             \if_int_compare:w #4 > \c_five % cf \c_fp_max_exponent_int
12883                 \exp_after:wN \__fp_exp_overflow:
12884                 \tex_roman numeral:D
12885             \else:
12886                 \if_int_compare:w #4 < \c_zero
12887                     \exp_after:wN \use_i:nn
12888                 \else:
12889                     \exp_after:wN \use_ii:nn
12890                 \fi:
12891                 {
12892                     \c_zero
12893                     \__fp_decimate:nNnnnn { - #4 }
12894                     \__fp_exp_Taylor:Nnnwn
12895                 }
12896                 {
12897                     \__fp_decimate:nNnnnn { \c_sixteen - #4 }
12898                     \__fp_exp_pos_large:NnnNwn
12899                 }

```

```

12900      #5
12901      {#4}
12902      #1 #2 0
12903      \tex_roman numeral:D
12904      \fi:
12905      \fi:
12906      \exp_after:wN \c_zero
12907      }
12908 \cs_new:Npn \_fp_exp_overflow:
12909   { + \c_two * \c_fp_max_exponent_int ; {1000} {0000} {0000} {0000} ; }
(End definition for \_fp_exp_normal:w and \_fp_exp_pos:Nnwnw)

```

This function is called for numbers in the range $[10^{-9}, 10^{-1}]$. Our only task is to compute the Taylor series. The first argument is irrelevant (rounding digit used by some other functions). The next three arguments, at least 16 digits, delimited by a semicolon, form a fixed point number, so we pack it in blocks of 4 digits.

```

12910 \cs_new:Npn \_fp_exp_Taylor:Nnnwn #1#2#3 #4; #5 #6
12911 {
12912   #6
12913   \_fp_pack_twice_four:wNNNNNNNN
12914   \_fp_pack_twice_four:wNNNNNNNN
12915   \_fp_pack_twice_four:wNNNNNNNN
12916   \_fp_exp_Taylor_ii:ww
12917   ; #2#3#4 0000 0000 ;
12918 }
12919 \cs_new:Npn \_fp_exp_Taylor_ii:ww #1; #2;
12920   { \_fp_exp_Taylor_loop:www 10 ; #1 ; #1 ; \s_stop }
12921 \cs_new:Npn \_fp_exp_Taylor_loop:www #1; #2; #3;
12922 {
12923   \if_int_compare:w #1 = \c_one
12924     \exp_after:wN \_fp_exp_Taylor_break:Nww
12925   \fi:
12926   \_fp_fixed_div_int:wwN #3 ; #1 ;
12927   \_fp_fixed_add_one:wn
12928   \_fp_fixed_mul:wn #2 ;
12929 {
12930   \exp_after:wN \_fp_exp_Taylor_loop:www
12931   \int_use:N \_int_eval:w #1 - 1 ;
12932   #2 ;
12933 }
12934 }
12935 \cs_new:Npn \_fp_exp_Taylor_break:Nww #1 #2; #3 \s_stop
12936   { \_fp_fixed_add_one:wn #2 ; }
(End definition for \_fp_exp_Taylor:Nnnwn This function is documented on page ??.)
```

The first two arguments are irrelevant (a rounding digit, and a brace group with 8 zeros). The third argument is the integer part of our number, then we have the decimal part delimited by a semicolon, and finally the exponent, in the range $[0, 5]$. Remove leading zeros from the integer part: putting #4 in there too ensures that an integer part of 0 is

also removed. Then read digits one by one, looking up $\exp(\langle digit \rangle \cdot 10^{\langle exponent \rangle})$ in a table, and multiplying that to the current total. The loop is done by having the auxiliary for one exponent call the auxiliary for the next exponent. The current total is expressed by leaving the exponent behind in the input stream (we are currently within an `_int_eval:w`), and keeping track of a fixed point number, #1 for the numbered auxiliaries. Our usage of `\if_case:w` is somewhat dirty for optimization: TeX jumps to the appropriate case, but we then close the `\if_case:w` “by hand”, using `\or:` and `\fi:` as delimiters.

```

12937 \cs_new:Npn \_fp_exp_pos_large:NnnNwn #1#2#3 #4#5; #6
12938 {
12939   \exp_after:wN \exp_after:wN
12940   \cs:w __fp_exp_large_\tex_roman numeral:D #6:wN \exp_after:wN \cs_end:
12941   \exp_after:wN \c__fp_one_fixed_tl
12942   \exp_after:wN ;
12943   \_int_value:w #3 #4 \exp_stop_f:
12944   #5 00000 ;
12945 }
12946 \cs_new:Npn \_fp_exp_large:w #1 \or: #2 \fi:
12947 { \fi: \_fp_fixed_mul:wwn #1; }
12948 \cs_new:Npn \_fp_exp_large_v:wN #1; #2
12949 {
12950   \if_case:w #2 ~ \exp_after:wN \_fp_fixed_continue:wn \or:
12951   + 4343 \_fp_exp_large:w {8806}{8182}{2566}{2921}{5872}{6150} \or:
12952   + 8686 \_fp_exp_large:w {7756}{0047}{2598}{6861}{0458}{3204} \or:
12953   + 13029 \_fp_exp_large:w {6830}{5723}{7791}{4884}{1932}{7351} \or:
12954   + 17372 \_fp_exp_large:w {6015}{5609}{3095}{3052}{3494}{7574} \or:
12955   + 21715 \_fp_exp_large:w {5297}{7951}{6443}{0315}{3251}{3576} \or:
12956   + 26058 \_fp_exp_large:w {4665}{6719}{0099}{3379}{5527}{2929} \or:
12957   + 30401 \_fp_exp_large:w {4108}{9724}{3326}{3186}{5271}{5665} \or:
12958   + 34744 \_fp_exp_large:w {3618}{6973}{3140}{0875}{3856}{4102} \or:
12959   + 39087 \_fp_exp_large:w {3186}{9209}{6113}{3900}{6705}{9685} \or:
12960   \fi:
12961   #1;
12962   \_fp_exp_large_iv:wN
12963 }
12964 \cs_new:Npn \_fp_exp_large_iv:wN #1; #2
12965 {
12966   \if_case:w #2 ~ \exp_after:wN \_fp_fixed_continue:wn \or:
12967   + 435 \_fp_exp_large:w {1970}{0711}{1401}{7046}{9938}{8888} \or:
12968   + 869 \_fp_exp_large:w {3881}{1801}{9428}{4368}{5764}{8232} \or:
12969   + 1303 \_fp_exp_large:w {7646}{2009}{8905}{4704}{8893}{1073} \or:
12970   + 1738 \_fp_exp_large:w {1506}{3559}{7005}{0524}{9009}{7592} \or:
12971   + 2172 \_fp_exp_large:w {2967}{6283}{8402}{3667}{0689}{6630} \or:
12972   + 2606 \_fp_exp_large:w {5846}{4389}{5650}{2114}{7278}{5046} \or:
12973   + 3041 \_fp_exp_large:w {1151}{7900}{5080}{6878}{2914}{4154} \or:
12974   + 3475 \_fp_exp_large:w {2269}{1083}{0850}{6857}{8724}{4002} \or:
12975   + 3909 \_fp_exp_large:w {4470}{3047}{3316}{5442}{6408}{6591} \or:
12976   \fi:
12977   #1;
12978   \_fp_exp_large_iii:wN

```

```

12979    }
12980 \cs_new:Npn \__fp_exp_large_iii:wN #1; #2
12981 {
12982     \if_case:w #2 ~ \exp_after:wN \__fp_fixed_continue:wn \or:
12983         + 44 \__fp_exp_large:w {2688}{1171}{4181}{6135}{4484}{1263} \or:
12984         + 87 \__fp_exp_large:w {7225}{9737}{6812}{5749}{2581}{7748} \or:
12985         + 131 \__fp_exp_large:w {1942}{4263}{9524}{1255}{9365}{8421} \or:
12986         + 174 \__fp_exp_large:w {5221}{4696}{8976}{4143}{9505}{8876} \or:
12987         + 218 \__fp_exp_large:w {1403}{5922}{1785}{2837}{4107}{3977} \or:
12988         + 261 \__fp_exp_large:w {3773}{0203}{0092}{9939}{8234}{0143} \or:
12989         + 305 \__fp_exp_large:w {1014}{2320}{5473}{5004}{5094}{5533} \or:
12990         + 348 \__fp_exp_large:w {2726}{3745}{7211}{2566}{5673}{6478} \or:
12991         + 391 \__fp_exp_large:w {7328}{8142}{2230}{7421}{7051}{8866} \or:
12992     \fi:
12993     #1;
12994     \__fp_exp_large_ii:wN
12995 }
12996 \cs_new:Npn \__fp_exp_large_ii:wN #1; #2
12997 {
12998     \if_case:w #2 ~ \exp_after:wN \__fp_fixed_continue:wn \or:
12999         + 5 \__fp_exp_large:w {2202}{6465}{7948}{0671}{6516}{9579} \or:
13000         + 9 \__fp_exp_large:w {4851}{6519}{5409}{7902}{7796}{9107} \or:
13001         + 14 \__fp_exp_large:w {1068}{6474}{5815}{2446}{2146}{9905} \or:
13002         + 18 \__fp_exp_large:w {2353}{8526}{6837}{0199}{8540}{7900} \or:
13003         + 22 \__fp_exp_large:w {5184}{7055}{2858}{7072}{4640}{8745} \or:
13004         + 27 \__fp_exp_large:w {1142}{0073}{8981}{5684}{2836}{6296} \or:
13005         + 31 \__fp_exp_large:w {2515}{4386}{7091}{9167}{0062}{6578} \or:
13006         + 35 \__fp_exp_large:w {5540}{6223}{8439}{3510}{0525}{7117} \or:
13007         + 40 \__fp_exp_large:w {1220}{4032}{9431}{7840}{8020}{0271} \or:
13008     \fi:
13009     #1;
13010     \__fp_exp_large_i:wN
13011 }
13012 \cs_new:Npn \__fp_exp_large_i:wN #1; #2
13013 {
13014     \if_case:w #2 ~ \exp_after:wN \__fp_fixed_continue:wn \or:
13015         + 1 \__fp_exp_large:w {2718}{2818}{2845}{9045}{2353}{6029} \or:
13016         + 1 \__fp_exp_large:w {7389}{0560}{9893}{0650}{2272}{3043} \or:
13017         + 2 \__fp_exp_large:w {2008}{5536}{9231}{8766}{7740}{9285} \or:
13018         + 2 \__fp_exp_large:w {5459}{8150}{0331}{4423}{9078}{1103} \or:
13019         + 3 \__fp_exp_large:w {1484}{1315}{9102}{5766}{0342}{1116} \or:
13020         + 3 \__fp_exp_large:w {4034}{2879}{3492}{7351}{2260}{8387} \or:
13021         + 4 \__fp_exp_large:w {1096}{6331}{5842}{8458}{5992}{6372} \or:
13022         + 4 \__fp_exp_large:w {2980}{9579}{8704}{1728}{2747}{4359} \or:
13023         + 4 \__fp_exp_large:w {8103}{0839}{2757}{5384}{0077}{1000} \or:
13024     \fi:
13025     #1;
13026     \__fp_exp_large_:_wN
13027 }
13028 \cs_new:Npn \__fp_exp_large_:_wN #1; #2

```

```

13029 {
13030   \if_case:w #2 ~ \exp_after:wN \_fp_fixed_continue:wn \or:
13031     + 1 \_fp_exp_large:w {1105}{1709}{1807}{5647}{6248}{1171} \or:
13032     + 1 \_fp_exp_large:w {1221}{4027}{5816}{0169}{8339}{2107} \or:
13033     + 1 \_fp_exp_large:w {1349}{8588}{0757}{6003}{1039}{8374} \or:
13034     + 1 \_fp_exp_large:w {1491}{8246}{9764}{1270}{3178}{2485} \or:
13035     + 1 \_fp_exp_large:w {1648}{7212}{7070}{0128}{1468}{4865} \or:
13036     + 1 \_fp_exp_large:w {1822}{1188}{0039}{0508}{9748}{7537} \or:
13037     + 1 \_fp_exp_large:w {2013}{7527}{0747}{0476}{5216}{2455} \or:
13038     + 1 \_fp_exp_large:w {2225}{5409}{2849}{2467}{6045}{7954} \or:
13039     + 1 \_fp_exp_large:w {2459}{6031}{1115}{6949}{6638}{0013} \or:
13040   \fi:
13041   #1;
13042   \_fp_exp_large_after:wwn
13043 }
13044 \cs_new:Npn \_fp_exp_large_after:wwn #1; #2; #3
13045 {
13046   \_fp_exp_Taylor:Nnnwn ? { } { } 0 #2; {} #3
13047   \_fp_fixed_mul:wwn #1;
13048 }
(End definition for \_fp_exp_pos_large:NnnNwn and others.)
```

35.3 Power

Raising a number a to a power b leads to many distinct situations.

a^b	$-\infty$	$-y$	$-n$	± 0	$+n$	$+y$	$+\infty$	nan
$+\infty$	$+0$	$+0$	$+0$	$+1$	$+\infty$	$+\infty$	$+\infty$	nan
$1 < x$	$+0$	$+x^{-y}$	$+x^{-n}$	$+1$	$+x^n$	$+x^y$	$+\infty$	nan
$+1$	$+1$	$+1$	$+1$	$+1$	$+1$	$+1$	$+1$	$+1$
$0 < x < 1$	$+\infty$	$+x^{-y}$	$+x^{-n}$	$+1$	$+x^n$	$+x^y$	$+0$	nan
$+0$	$+\infty$	$+\infty$	$+\infty$	$+1$	$+0$	$+0$	$+0$	nan
-0	nan	nan	$\pm\infty$	$+1$	± 0	$+0$	$+0$	nan
$-1 < -x < 0$	nan	nan	$\pm x^{-n}$	$+1$	$\pm x^n$	nan	$+0$	nan
-1	nan	nan	± 1	$+1$	± 1	nan	nan	nan
$-x < -1$	$+0$	nan	$\pm x^{-n}$	$+1$	$\pm x^n$	nan	nan	nan
$-\infty$	$+0$	$+0$	± 0	$+1$	$\pm\infty$	nan	nan	nan
nan	nan	nan	nan	$+1$	nan	nan	nan	nan

One peculiarity of this operation is that $\text{nan}^0 = 1^{\text{nan}} = 1$, because this relation is obeyed for any number, even $\pm\infty$.

fp~o:ww We cram a most of the tests into a single function to save csnames. First treat the case $b = 0$: $a^0 = 1$ for any a , even nan . Then test the sign of a .

- If it is positive, and a is a normal number, call $_fp_pow_normal:ww$ followed by the two $\text{fp } a$ and b . For $a = +0$ or $+\infty$, call $_fp_pow_zero_or_inf:ww$ instead, to return either $+0$ or $+\infty$ as appropriate.

- If a is a `nan`, then skip to the next semicolon (which happens to be conveniently the end of b) and return `nan`.
- Finally, if a is negative, compute a^b (`__fp_pow_normal:ww` which ignores the sign of its first operand), and keep an extra copy of a and b (the second brace group, containing $\{ b a \}$, is inserted between a and b). Then do some tests to find the final sign of the result if it exists.

```

13049 \cs_new:cpn { __fp_ \iow_char:N \^ _o:ww }
13050   \s_fp \__fp_chk:w #1#2#3; \s_fp \__fp_chk:w #4#5#6;
13051 {
13052   \if_meaning:w 0 #4
13053     \__fp_case_return_o:Nw \c_one_fp
13054   \fi:
13055   \if_case:w #2 \exp_stop_f:
13056     \exp_after:wN \use_i:nn
13057   \or:
13058     \__fp_case_return_o:Nw \c_nan_fp
13059   \else:
13060     \exp_after:wN \__fp_pow_neg:www
13061     \tex_roman numeral:D -'0 \exp_after:wN \use:nn
13062   \fi:
13063 {
13064   \if_meaning:w 1 #1
13065     \exp_after:wN \__fp_pow_normal:ww
13066   \else:
13067     \exp_after:wN \__fp_pow_zero_or_inf:ww
13068   \fi:
13069   \s_fp \__fp_chk:w #1#2#3;
13070 }
13071 { \s_fp \__fp_chk:w #4#5#6; \s_fp \__fp_chk:w #1#2#3; }
13072 \s_fp \__fp_chk:w #4#5#6;
13073 }

(End definition for \__fp_ ^ _o:ww)

```

`__fp_pow_zero_or_inf:ww`

Raising -0 or $-\infty$ to `nan` yields `nan`. For other powers, the result is $+0$ if 0 is raised to a positive power or ∞ to a negative power, and $+\infty$ otherwise. Thus, if the type of a and the sign of b coincide, the result is 0 , since those conveniently take the same possible values, 0 and 2 . Otherwise, either $a = \pm 0$ with $b < 0$ and we have a division by zero, or $a = \pm\infty$ and $b > 0$ and the result is also $+\infty$, but without any exception.

```

13074 \cs_new:Npn \__fp_pow_zero_or_inf:ww \s_fp \__fp_chk:w #1#2; \s_fp \__fp_chk:w #3#4
13075 {
13076   \if_meaning:w 1 #4
13077     \__fp_case_return_same_o:w
13078   \fi:
13079   \if_meaning:w #1 #4
13080     \__fp_case_return_o:Nw \c_zero_fp
13081   \fi:
13082   \if_meaning:w 0 #1

```

```

13083   \__fp_case_use:nw
13084   {
13085     \__fp_division_by_zero_o>NNww \c_inf_fp ^
13086     \s_fp \__fp_chk:w #1 #2 ;
13087   }
13088 \else:
13089   \__fp_case_return_o:Nw \c_inf_fp
13090 \fi:
13091   \s_fp \__fp_chk:w #3#4
13092 }

(End definition for \__fp_pow_zero_or_inf:ww)

```

__fp_pow_normal:ww

We have in front of us a , and $b \neq 0$, we know that a is a normal number, and we wish to compute $|a|^b$. If $|a| = 1$, we return 1, unless $a = -1$ and b is nan. Indeed, returning 1 at this point would wrongly raise “invalid” when the sign is considered. If $|a| \neq 1$, test the type of b :

- 0 Impossible, we already filtered $b = \pm 0$.
- 1 Call __fp_pow_npos:ww.
- 2 Return $+\infty$ or $+0$ depending on the sign of b and whether the exponent of a is positive or not.
- 3 Return b .

```

13093 \cs_new:Npn \__fp_pow_normal:ww \s_fp \__fp_chk:w 1 #1#2#3; \s_fp \__fp_chk:w #4#5
13094 {
13095   \if_int_compare:w \pdftex_strcmp:D { #2 #3 }
13096     { 1 {1000} {0000} {0000} {0000} } = \c_zero
13097     \if_int_compare:w #4 #1 = 32 \exp_stop_f:
13098       \exp_after:wN \__fp_case_return_ii_o:ww
13099     \fi:
13100     \__fp_case_return_o:Nww \c_one_fp
13101   \fi:
13102   \if_case:w #4 \exp_stop_f:
13103     \or:
13104       \exp_after:wN \__fp_pow_npos:Nww
13105       \exp_after:wN #5
13106     \or:
13107       \if_meaning:w 2 #5 \exp_after:wN \reverse_if:N \fi:
13108       \if_int_compare:w #2 > \c_zero
13109         \exp_after:wN \__fp_case_return_o:Nww
13110         \exp_after:wN \c_inf_fp
13111       \else:
13112         \exp_after:wN \__fp_case_return_o:Nww
13113         \exp_after:wN \c_zero_fp
13114       \fi:
13115     \or:
13116       \__fp_case_return_ii_o:ww

```

```

13117     \fi:
13118     \s_fp \fp_chk:w 1 #1 {#2} #3 ;
13119     \s_fp \fp_chk:w #4 #5
13120 }

```

(End definition for `\fp_pow_normal:ww`)

`\fp_pow_npos:Nww` We now know that $a \neq \pm 1$ is a normal number, and b is a normal number too. We want to compute $|a|^b = (|x| \cdot 10^n)^{y \cdot 10^p} = \exp((\ln|x| + n \ln(10)) \cdot y \cdot 10^p) = \exp(z)$. To compute the exponential accurately, we need to know the digits of z up to the 16-th position. Since the exponential of 10^5 is infinite, we only need at most 21 digits, hence the fixed point result of `\fp_ln_o:w` is precise enough for our needs. Start an integer expression for the decimal exponent of $e^{|z|}$. If z is negative, negate that decimal exponent, and prepare to take the inverse when converting from the fixed point to the floating point result.

```

13121 \cs_new:Npn \fp_pow_npos:Nww #1 \s_fp \fp_chk:w 1#2#3
13122 {
13123     \exp_after:wN \fp_sanitize:Nw
13124     \exp_after:wN 0
13125     \int_value:w
13126     \if:w #1 \if_int_compare:w #3 > \c_zero 0 \else: 2 \fi:
13127         \exp_after:wN \fp_pow_npos_aux>NNnww
13128         \exp_after:wN +
13129         \exp_after:wN \fp_fixed_to_float:wN
13130     \else:
13131         \exp_after:wN \fp_pow_npos_aux>NNnww
13132         \exp_after:wN -
13133         \exp_after:wN \fp_fixed_inv_to_float:wN
13134     \fi:
13135     {#3}
13136 }

```

(End definition for `\fp_pow_npos:Nww`)

`\fp_pow_npos_aux>NNnww` The first argument is the conversion function from fixed point to float. Then comes an exponent and the 4 brace groups of x , followed by b . Compute $-\ln(x)$.

```

13137 \cs_new:Npn \fp_pow_npos_aux>NNnww #1#2#3#4#5; \s_fp \fp_chk:w 1#6#7#8;
13138 {
13139     #1
13140     \int_eval:w
13141         \fp_ln_significand>NNNNnnnn #4#5
13142         \fp_pow_exponent:wnN {#3}
13143         \fp_fixed_mul:wwn #8 {0000}{0000} ;
13144         \fp_pow_B:wwN #7;
13145         #1 #2 0 % fixed_to_float:wN
13146     }
13147 \cs_new:Npn \fp_pow_exponent:wnN #1; #2
13148 {
13149     \if_int_compare:w #2 > \c_zero
13150         \exp_after:wN \fp_pow_exponent:Nwnnnnnwn % n\ln(10) - (-\ln(x))
13151         \exp_after:wN +

```

```

13152 \else:
13153     \exp_after:wN \_fp_pow_exponent:Nwnnnnnwn % -( |n|\ln(10) + (-\ln(x)) )
13154     \exp_after:wN -
13155 \fi:
13156 #2; #1;
13157 }
13158 \cs_new:Npn \_fp_pow_exponent:Nwnnnnnwn #1#2; #3#4#5#6#7#8; #9
13159 { %^A todo: use that in ln.
13160     \exp_after:wN \_fp_fixed_mul_after:wn
13161     \int_use:N \_int_eval:w \c_fp_leading_shift_int
13162         \exp_after:wN \_fp_pack>NNNNNwn
13163         \int_use:N \_int_eval:w \c_fp_middle_shift_int
13164             #1#2*23025 - #1 #3
13165             \exp_after:wN \_fp_pack>NNNNNwn
13166             \int_use:N \_int_eval:w \c_fp_middle_shift_int
13167                 #1 #2*8509 - #1 #4
13168             \exp_after:wN \_fp_pack>NNNNNwn
13169             \int_use:N \_int_eval:w \c_fp_middle_shift_int
13170                 #1 #2*2994 - #1 #5
13171             \exp_after:wN \_fp_pack>NNNNNwn
13172             \int_use:N \_int_eval:w \c_fp_middle_shift_int
13173                 #1 #2*0456 - #1 #6
13174             \exp_after:wN \_fp_pack>NNNNNwn
13175             \int_use:N \_int_eval:w \c_fp_trailing_shift_int
13176                 #1 #2*8401 - #1 #7
13177                 #1 ( #2*7991 - #8 ) / 1 0000 ; {#9} ;
13178 }
13179 \cs_new:Npn \_fp_pow_B:wwN #1#2#3#4#5#6; #7;
13180 {
13181     \if_int_compare:w #7 < \c_zero
13182         \exp_after:wN \_fp_pow_C_neg:w \_int_value:w -
13183     \else:
13184         \if_int_compare:w #7 < 22 \exp_stop_f:
13185             \exp_after:wN \_fp_pow_C_pos:w \_int_value:w
13186         \else:
13187             \exp_after:wN \_fp_pow_C_overflow:w \_int_value:w
13188         \fi:
13189     \fi:
13190     #7 \exp_after:wN ;
13191     \int_use:N \_int_eval:w 10 0000 + #1 \_int_eval_end:
13192     #2#3#4#5#6 0000 0000 0000 0000 0000 0000 ; %^A todo: how many 0?
13193 }
13194 \cs_new:Npn \_fp_pow_C_overflow:w #1; #2; #3
13195 {
13196     + \c_two * \c_fp_max_exponent_int
13197     \exp_after:wN \_fp_fixed_continue:wn \c_fp_one_fixed_tl ;
13198 }
13199 \cs_new:Npn \_fp_pow_C_neg:w #1 ; 1
13200 {
13201     \exp_after:wN \exp_after:wN \exp_after:wN \_fp_pow_C_pack:w

```

```

13202     \prg_replicate:nn {#1} {0}
13203 }
13204 \cs_new:Npn \__fp_pow_C_pos:w #1; 1
13205 { \__fp_pow_C_pos_loop:wN #1; }
13206 \cs_new:Npn \__fp_pow_C_pos_loop:wN #1; #2
13207 {
13208     \if_meaning:w 0 #1
13209         \exp_after:wN \__fp_pow_C_pack:w
13210         \exp_after:wN #2
13211     \else:
13212         \if_meaning:w 0 #2
13213             \exp_after:wN \__fp_pow_C_pos_loop:wN \__int_value:w
13214         \else:
13215             \exp_after:wN \__fp_pow_C_overflow:w \__int_value:w
13216         \fi:
13217             \__int_eval:w #1 - \c_one \exp_after:wN ;
13218         \fi:
13219     }
13220 \cs_new:Npn \__fp_pow_C_pack:w
13221 { \exp_after:wN \__fp_exp_large_v:wN \c_fp_one_fixed_tl ; }
(End definition for \__fp_pow_npos_aux:NNnww)

```

__fp_pow_neg:www This function is followed by three floating point numbers: a^b , $a \in [-\infty, -0]$, and b . If b is an even integer (case -1), $a^b = a^b$. If b is an odd integer (case 0), $a^b = -a^b$, obtained by a call to __fp_-o:w. Otherwise, the sign is undefined. This is invalid, unless a^b turns out to be +0 or nan, in which case we return that as a^b . In particular, since the underflow detection occurs before __fp_pow_neg:www is called, $(-0.1)^{**}(12345.6)$ will give +0 rather than complaining that the sign is not defined.

```

13222 \cs_new:Npn \__fp_pow_neg:www \s_fp \__fp_chk:w #1#2; #3; #4;
13223 {
13224     \if_case:w \__fp_pow_neg_case:w #4 ;
13225         \cs:w __fp_-_o:w \exp_after:wN \cs_end:
13226     \or:
13227         \if_int_compare:w \__int_eval:w #1 / \c_two = \c_one
13228             \__fp_invalid_operation_o:Nww ^ #3; #4;
13229             \tex_roman numeral:D -'0
13230             \exp_after:wN \exp_after:wN
13231             \exp_after:wN \__fp_use_none_until_s:w
13232         \fi:
13233     \fi:
13234     \__fp_exp_after_o:w
13235     \s_fp \__fp_chk:w #1#2;
13236 }
(End definition for \__fp_pow_neg:www)

```

__fp_pow_neg_case:w __fp_pow_neg_case_aux:nnnnn __fp_pow_neg_case_aux:nnnnnnnn This function expects a floating point number, and “returns” -1 if it is an even integer, 0 if it is an odd integer, and 1 if it is not an integer. Zeros are even, $\pm\infty$ and nan are non-integers. The sign of normal numbers is irrelevant to parity. If the exponent is greater than sixteen, then the number is even. If the exponent is non-positive, the number cannot

be an integer. We also separate the ranges of exponent [1, 8] and [9, 16]. In the former case, check that the last 8 digits are zero (otherwise we don't have an integer). In both cases, consider the appropriate 8 digits, either #4#5 or #2#3, remove the first few: we are then left with $\langle digit \rangle \langle digits \rangle$; which would be the digits surrounding the decimal period. If the $\langle digits \rangle$ are non-zero, the number is not an integer. Otherwise, check the parity of the $\langle digit \rangle$ and return $\backslash c_zero$ or $\backslash c_minus_one$.

```

13237 \cs_new:Npn \__fp_pow_neg_case:w \s__fp \__fp_chk:w #1#2#3;
13238 {
13239     \if_case:w #1 \exp_stop_f:
13240         \c_minus_one
13241     \or: \__fp_pow_neg_case_aux:nnnnn #3
13242     \else: \c_one
13243     \fi:
13244 }
13245 \cs_new:Npn \__fp_pow_neg_case_aux:nnnnn #1#2#3#4#5
13246 {
13247     \if_int_compare:w #1 > \c_eight
13248     \if_int_compare:w #1 > \c_sixteen
13249         \c_minus_one
13250     \else:
13251         \exp_after:wN \exp_after:wN
13252         \exp_after:wN \__fp_pow_neg_case_aux:NNNNNNNNw
13253         \prg_replicate:nn { \c_sixteen - #1 } { 0 } #4#5 ;
13254     \fi:
13255 \else:
13256     \if_int_compare:w #1 > \c_zero
13257     \if_int_compare:w #4#5 = \c_zero
13258         \exp_after:wN \exp_after:wN
13259         \exp_after:wN \__fp_pow_neg_case_aux:NNNNNNNNw
13260         \prg_replicate:nn { \c_eight - #1 } { 0 } #2#3 ;
13261     \else:
13262         \c_one
13263     \fi:
13264 \else:
13265     \c_one
13266 \fi:
13267 \fi:
13268 }
13269 \cs_new:Npn \__fp_pow_neg_case_aux:NNNNNNNNw #1#2#3#4#5#6#7#8#9;
13270 {
13271     \if_int_compare:w 0 #9 = \c_zero
13272     \if_int_odd:w #8 \exp_stop_f:
13273         \c_zero
13274     \else:
13275         \c_minus_one
13276     \fi:
13277 \else:
13278     \c_one
13279 \fi:

```

```

13280    }
(End definition for \_fp_pow_neg_case:w, \_fp_pow_neg_case_aux:nnnn, and \_fp_pow_neg_case_aux:NNNNNNNNw)
13281  </initex | package>

```

36 Implementation

```
13282  <*initex | package>
```

```
13283  <@@=fp>
```

36.1 Direct trigonometric functions

The approach for all trigonometric functions (sine, cosine, tangent, cotangent, cosecant, and secant) is the same.

- Filter out special cases (± 0 , $\pm \infty$ and `nan`).
- Keep the sign for later, and work with the absolute value `x` of the argument.
- For numbers less than 1, shift the significand to convert them to fixed point numbers. Very small numbers take a slightly different route.
- For numbers ≥ 1 , subtract a multiple of $\pi/2$ to bring them to the range to $[0, \pi/2]$. (This is called argument reduction.)
- Reduce further to $[0, \pi/4]$ using $\sin x = \cos(\pi/2 - x)$.
- Use the appropriate power series depending on the octant $\lfloor \frac{x}{\pi/4} \rfloor \bmod 8$, the sign, and the function to compute.

36.1.1 Sign and special numbers

`_fp_sin_o:w` The sine of ± 0 or `nan` is the same floating point number. The sine of $\pm \infty$ raises an invalid operation exception. Otherwise, `_fp_trig_exponent:NNNNNwn` checks the exponent: if the number is tiny, use `_fp_trig_epsilon_o:w` which returns $\sin \epsilon = \epsilon$. For larger inputs, use the series `_fp_sin_series>NNwww` after argument reduction. In this second case, we will use a sign #2, an initial octant of 0, and convert the result of the series to a floating point directly, since $\sin(x) = \#2 \sin|x|$.

```

13284  \cs_new:Npn \_fp_sin_o:w \s_fp \_fp_chk:w #1#2
13285  {
13286  \if_case:w #1 \exp_stop_f:
13287      \_fp_case_return_same_o:w
13288  \or:
13289      \_fp_case_use:nw
13290      {
13291          \_fp_trig_exponent:NNNNNwn \_fp_trig_epsilon_o:w
13292          \_fp_sin_series>NNwww \_fp_fixed_to_float:wN #2 \c_zero
13293      }
13294  \or: \_fp_case_use:nw { \_fp_invalid_operation_o:nw { sin } }

```

```

13295     \else: \__fp_case_return_same_o:w
13296     \fi:
13297     \s__fp \__fp_chk:w #1#2
13298 }
(End definition for \__fp_sin_o:w)

```

- __fp_cos_o:w The cosine of ± 0 is 1. The cosine of $\pm\infty$ raises an invalid operation exception. The cosine of `nan` is itself. Otherwise, `__fp_trig_exponent>NNNNNwn` checks the exponent: if the number is tiny, use `__fp_trig_epsilon_one_o:w` which returns $\cos \epsilon = 1$. For larger inputs, use the same series as for sine, but using a positive sign 0 and with an initial octant of 2, because $\cos(x) = +\sin(\pi/2 + |x|)$.

```

13299 \cs_new:Npn \__fp_cos_o:w \s__fp \__fp_chk:w #1#2
13300 {
13301     \if_case:w #1 \exp_stop_f:
13302         \__fp_case_return_o:Nw \c_one_fp
13303     \or:
13304         \__fp_case_use:nw
13305         {
13306             \__fp_trig_exponent:NNNNNwn \__fp_trig_epsilon_one_o:w
13307             \__fp_sin_series:NNwww \__fp_fixed_to_float:wN 0 \c_two
13308         }
13309     \or: \__fp_case_use:nw { \__fp_invalid_operation_o:nw { cos } }
13310     \else: \__fp_case_return_same_o:w
13311     \fi:
13312     \s__fp \__fp_chk:w #1#2
13313 }
(End definition for \__fp_cos_o:w)

```

- __fp_csc_o:w The cosecant of ± 0 is $\pm\infty$ with the same sign, with a division by zero exception (see `__fp_cot_zero_o:Nnw` defined below). The cosecant of $\pm\infty$ raises an invalid operation exception. The cosecant of `nan` is itself. Otherwise, `__fp_trig_exponent>NNNNNwn` checks the exponent: if the number is tiny, use `__fp_trig_epsilon_inv_o:w` which returns $\csc \epsilon = 1/\epsilon$. For larger inputs, use the same series as for sine, using the sign #2, a starting octant of 0, and inverting during the conversion from the fixed point sine to the floating point result, because $\csc(x) = \#2(\sin|x|)^{-1}$.

```

13314 \cs_new:Npn \__fp_csc_o:w \s__fp \__fp_chk:w #1#2
13315 {
13316     \if_case:w #1 \exp_stop_f:
13317         \__fp_cot_zero_o:Nnw #2 { csc }
13318     \or:
13319         \__fp_case_use:nw
13320         {
13321             \__fp_trig_exponent:NNNNNwn \__fp_trig_epsilon_inv_o:w
13322             \__fp_sin_series:NNwww \__fp_fixed_inv_to_float:wN #2 \c_zero
13323         }
13324     \or: \__fp_case_use:nw { \__fp_invalid_operation_o:nw { csc } }
13325     \else: \__fp_case_return_same_o:w
13326     \fi:

```

```

13327     \s_fp \__fp_chk:w #1#2
13328 }

```

(End definition for $__fp_csc_o:w$)

- $__fp_sec_o:w$ The secant of ± 0 is 1. The secant of $\pm\infty$ raises an invalid operation exception. The secant of nan is itself. Otherwise, $__fp_trig_exponent:NNNNNwn$ checks the exponent: if the number is tiny, use $__fp_trig_epsilon_one_o:w$ which returns $\sec \epsilon = 1$. For larger inputs, use the same series as for sine, using a positive sign 0, a starting octant of 2, and inverting upon conversion, because $\sec(x) = +1/\sin(\pi/2 + |x|)$.

```

13329 \cs_new:Npn \__fp_sec_o:w \s_fp \__fp_chk:w #1#2
13330 {
13331     \if_case:w #1 \exp_stop_f:
13332         \__fp_case_return_o:Nw \c_one_fp
13333     \or:
13334         \__fp_case_use:nw
13335         {
13336             \__fp_trig_exponent:NNNNNwn \__fp_trig_epsilon_one_o:w
13337                 \__fp_sin_series>NNwww \__fp_fixed_inv_to_float:WN 0 \c_two
13338         }
13339     \or: \__fp_case_use:nw { \__fp_invalid_operation_o:nw { sec } }
13340     \else: \__fp_case_return_same_o:w
13341     \fi:
13342     \s_fp \__fp_chk:w #1#2
13343 }

```

(End definition for $__fp_sec_o:w$)

- $__fp_tan_o:w$ The tangent of ± 0 or nan is the same floating point number. The tangent of $\pm\infty$ raises an invalid operation exception. Otherwise, $__fp_trig_exponent:NNNNNwn$ checks the exponent: if the number is tiny, use $__fp_trig_epsilon_o:w$ which returns $\tan \epsilon = \epsilon$. For larger inputs, use $__fp_tan_series_o>NNwww$ for the calculation after argument reduction, with a sign #2 and an initial octant of 1 (this shift is somewhat arbitrary). See $__fp_cot_o:w$ for an explanation of the 0 argument.

```

13344 \cs_new:Npn \__fp_tan_o:w \s_fp \__fp_chk:w #1#2
13345 {
13346     \if_case:w #1 \exp_stop_f:
13347         \__fp_case_return_same_o:w
13348     \or:
13349         \__fp_case_use:nw
13350         {
13351             \__fp_trig_exponent:NNNNNwn \__fp_trig_epsilon_o:w
13352                 \__fp_tan_series_o>NNwww 0 #2 \c_one
13353         }
13354     \or: \__fp_case_use:nw { \__fp_invalid_operation_o:nw { tan } }
13355     \else: \__fp_case_return_same_o:w
13356     \fi:
13357     \s_fp \__fp_chk:w #1#2
13358 }

```

(End definition for $__fp_tan_o:w$)

`_fp_cot_o:w`
`_fp_cot_zero_o:Nnw` The cotangent of ± 0 is $\pm\infty$ with the same sign, with a division by zero exception (see `_fp_cot_zero_o:Nnw`). The cotangent of $\pm\infty$ raises an invalid operation exception. The cotangent of `nan` is itself. We use $\cot x = -\tan(\pi/2 + x)$, and the initial octant for the tangent was chosen to be 1, so the octant here starts at 3. The change in sign is obtained by feeding `_fp_tan_series_o>NNwww` two signs rather than just the sign of the argument: the first of those indicates whether we compute tangent or cotangent. Those signs are eventually combined.

```

13359 \cs_new:Npn \_fp_cot_o:w \s_fp \_fp_chk:w #1#2
1360 {
1361   \if_case:w #1 \exp_stop_f:
1362     \_fp_cot_zero_o:Nnw #2 { cot }
1363   \or:
1364     \_fp_case_use:nw
1365     {
1366       \_fp_trig_exponent:NNNNNwn \_fp_trig_epsilon_inv_o:w
1367       \_fp_tan_series_o:NNwww 2 #2 \c_three
1368     }
1369   \or: \_fp_case_use:nw { \_fp_invalid_operation_o:nw { cot } }
1370   \else: \_fp_case_return_same_o:w
1371   \fi:
1372   \s_fp \_fp_chk:w #1#2
1373 }
1374 \cs_new:Npn \_fp_cot_zero_o:Nnw #1 #2 #3 \fi:
1375 {
1376   \fi:
1377   \if_meaning:w 0 #1
1378     \exp_after:wN \_fp_division_by_zero_o:Nnw \exp_after:wN \c_inf_fp
1379   \else:
1380     \exp_after:wN \_fp_division_by_zero_o:Nnw \exp_after:wN \c_minus_inf_fp
1381   \fi:
1382   {#2}
1383 }
```

(End definition for `_fp_cot_o:w`. This function is documented on page ??.)

36.1.2 Small and tiny arguments

The first five arguments control what trigonometric function we compute, then follows a normal floating point number. If the floating point is smaller than 10^{-8} , then call the `_epsilon` auxiliary #1. Otherwise, call the function #2, with arguments #3; #4; the octant, computed in an integer expression starting with #5 and stopped by a period; and a fixed point number obtained from the floating point number by argument reduction. Argument reduction leaves a shift into the integer expression for the octant. Numbers less than 1 are converted using `_fp_trig_small:w` which simply shifts the significand, while large numbers need argument reduction.

```

1384 \cs_new:Npn \_fp_trig_exponent:NNNNNwn #1#2#3#4#5 \s_fp \_fp_chk:w 1#6#7
1385 {
1386   \if_int_compare:w #7 > - \c_eight
1387   \exp_after:wN #2
```

```

13388 \exp_after:wN #3
13389 \exp_after:wN #4
13390 \int_use:N \__int_eval:w #5
13391   \if_int_compare:w #7 > \c_zero
13392     \exp_after:wN \__fp_trig_large:ww \__int_value:w
13393   \else:
13394     \exp_after:wN \__fp_trig_small:ww \__int_value:w
13395   \fi:
13396 \else:
13397   \exp_after:wN #1
13398   \exp_after:wN #6
13399 \fi:
13400 #7 ;
13401 }

```

(End definition for `__fp_trig_exponent>NNNNNwn`)

`__fp_trig_epsilon_o:w` Sine and tangent of tiny numbers give the number itself: the relative error is less than $5 \cdot 10^{-17}$, which is appropriate. Cosine and secant simply give 1. Cotangent and cosecant compute $1/\epsilon$. This is actually slightly wrong because further terms in the power series could affect the rounding for cotangent.

```

13402 \cs_new:Npn \__fp_trig_epsilon_o:w #1 #2 ;
13403   { \__fp_exp_after_o:w \s_fp \__fp_chk:w 1 #1 {#2} }
13404 \cs_new:Npn \__fp_trig_epsilon_one_o:w #1 ; #2 ;
13405   { \exp_after:wN \c_one_fp }
13406 \group_begin:
13407   \char_set_catcode_letter:N /
13408   \cs_new:Npn \__fp_trig_epsilon_inv_o:w #1 #2 ;
13409   {
13410     \exp_after:wN \__fp/_o:ww
13411     \c_one_fp
13412     \s_fp \__fp_chk:w 1 #1 {#2}
13413   }
13414 \group_end:

```

(End definition for `__fp_trig_epsilon_o:w`, `__fp_trig_epsilon_one_o:w`, and `__fp_trig_epsilon_inv_o:w`)

`__fp_trig_small:ww` Floating point numbers less than 1 are converted to fixed point numbers by prepending a number of zeroes to the significand. Since we have already filtered out numbers less than 10^{-8} , we add at most 7 zeroes, hence no digit is lost in converting to a fixed point number.

```

13415 \cs_new:Npn \__fp_trig_small:ww #1; #2#3#4#5;
13416   {
13417     \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
13418     \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
13419     \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
13420     \exp_after:wN .
13421     \exp_after:wN ;
13422     \tex_roman numeral:D -`0
13423     \prg_replicate:nn { - #1 } { 0 } #2#3#4#5 0000 0000 ;
13424   }

```

(End definition for `_fp_trig_small:ww`)

36.1.3 Reduction of large arguments

In the case of a floating point argument greater or equal to 1, we need to perform argument reduction.

We shift the significand by one digit at a time, subtracting a multiple of 2π at each step. We use a value of 2π rounded up, consistent with the choice of `\c_pi_fp`. This is not quite correct from an accuracy perspective, but has the nice property that $\sin(180\text{deg}) = 0$ exactly. The arguments of `_fp_trig_large_i:www` are a leading block of up to 5 digits, three brace groups of 4 digits each, and the exponent, decremented at each step. The multiple of 2π to subtract is estimated as $\lceil \#1/6283 \rceil$ (the formula chosen always gives a non-negative integer). The subtraction has a form similar to our usual multiplications (see `I3fp-basics` or `I3fp-extended`). Once the exponent reaches 0, we are done subtracting 2π , and we call `_fp_trig_octant_loop:nnnnnw` to do the reduction by $\pi/2$.

```

13425 \cs_new:Npn \_fp_trig_large:ww #1; #2#3;
13426   { \_fp_trig_large_i:www #2; #3 ; #1; }
13427 \cs_new:Npn \_fp_trig_large_i:www #1; #2; #3;
13428 {
13429   \if_meaning:w 0 #3 \_fp_trig_large_break:w \fi:
13430   \exp_after:wN \_fp_trig_large_i_o:wnnnn
13431   \int_use:N \_int_eval:w ( #1 - 3141 ) / 6283 ;
13432   {#1} #2
13433   \exp_after:wN ;
13434   \int_use:N \_int_eval:w \c_minus_one + #3;
13435 }
13436 \cs_new:Npn \_fp_trig_large_i_o:wnnnn #1; #2#3#4#5
13437 {
13438   \exp_after:wN \_fp_trig_large_i:www
13439   \int_use:N \_int_eval:w \c_fp_leading_shift_int + #20 - #1*62831
13440   \exp_after:wN \_fp_pack:NNNNNw
13441   \int_use:N \_int_eval:w \c_fp_middle_shift_int + #30 - #1*8530
13442   \exp_after:wN \_fp_pack:NNNNNw
13443   \int_use:N \_int_eval:w \c_fp_middle_shift_int + #40 - #1*7179
13444   \exp_after:wN \_fp_pack:NNNNNw
13445   \int_use:N \_int_eval:w \c_fp_trailing_shift_int + #50 - #1*5880
13446   \exp_after:wN ;
13447 }
13448 \cs_new:Npn \_fp_trig_large_break:w \fi: #1; #2;
13449   { \fi: \_fp_trig_octant_loop:nnnnnw #2 {0000} {0000} ; }
(End definition for \_fp_trig_large:ww and others.)

```

We receive a fixed point number as argument. As long as it is greater than half of `\c_pi_fp`, namely 1.5707963267948970, subtract that fixed-point approximation of $\pi/2$, and leave $+\c_two$ in the integer expression for the octant. Once the argument becomes smaller, break the initial loop. If the number is greater than 0.7854 (overestimate of

$\pi/4$), then compute $\pi/2 - x$ and increment the octant. The result is in all cases in the range $[0, 0.7854]$, appropriate for the series expansions.

```

13450 \cs_new:Npn \__fp_trig_octant_loop:nnnnw #1#2#3#4#5#6;
13451 {
13452     \if_int_compare:w #1#2 < 157079633 \exp_stop_f:
13453         \if_int_compare:w #1#2 = 157079632 \exp_stop_f:
13454             \if_int_compare:w #3#4 > 67948969 \exp_stop_f:
13455                 \use_i_i:nnn
13456             \fi:
13457         \fi:
13458         \__fp_trig_octant_break:w
13459     \fi:
13460     + \c_two
13461     \__fp_fixed_sub:wwn
13462         {#1} {#2} {#3} {#4} {0000} {0000} ;
13463         {15707} {9632} {6794} {8970} {0000} {0000} ;
13464     \__fp_trig_octant_loop:nnnnw
13465 }
13466 \cs_new:Npn \__fp_trig_octant_break:w #1 \fi: + #2#3 #4#5; #6; #7;
13467 {
13468     \fi:
13469     \if_int_compare:w #4 < 7854 \exp_stop_f:
13470         \exp_after:wN \__fp_use_i_until_s:nw
13471         \exp_after:wN .
13472     \fi:
13473     + \c_one
13474     \__fp_fixed_sub:wwn #6 ; {#4} #5 ; . ;
13475 }
```

(End definition for `__fp_trig_octant_loop:nnnnw` and `__fp_trig_octant_break:w`)

36.2 Computing the power series

Here we receive a conversion function `__fp_fixed_to_float:wN` or `__fp_fixed_inv_to_float:wN`, a $\langle sign \rangle$ (0 or 2), a (non-negative) $\langle octant \rangle$ delimited by a dot, a $\langle fixed point \rangle$ number, and junk delimited by a semicolon. The auxiliary receives:

- The final sign, which depends on the octant #3 and the original sign #2,
- The octant #3, which will control the series we use.
- The square $#4 * #4$ of the argument, computed with `__fp_fixed_mul:wwn`.
- The number itself.

If the octant is in $\{1, 2, 5, 6, \dots\}$, we are near an extremum of the function and we use the series

$$\cos(x) = 1 - x^2 \left(\frac{1}{2!} - x^2 \left(\frac{1}{4!} - x^2 \left(\dots \right) \right) \right).$$

Otherwise, the series

$$\sin(x) = x \left(1 - x^2 \left(\frac{1}{3!} - x^2 \left(\frac{1}{5!} - x^2 \left(\dots \right) \right) \right) \right)$$

is used. Finally, the fixed point number is converted to a floating point number with the given sign, and `_fp_sanitize:Nw` checks for overflow and underflow.

```

13476 \cs_new:Npn \_fp_sin_series:NNwww #1#2#3 . #4; #5;
13477 {
13478   \_fp_fixed_mul:wwn #4; #4;
13479   {
13480     \exp_after:wN \_fp_sin_series_aux:NNnww
13481     \exp_after:wN #1
13482     \_int_value:w
13483       \if_int_odd:w \_int_eval:w ( #3 + \c_two ) / \c_four \_int_eval_end:
13484         #2
13485       \else:
13486         \if_meaning:w #2 0 2 \else: 0 \fi:
13487       \fi:
13488     {#3}
13489   }
13490   #4 ;
13491 }
13492 \cs_new:Npn \_fp_sin_series_aux:NNnww #1#2#3 #4; #5;
13493 {
13494   \if_int_odd:w \_int_eval:w #3 / \c_two \_int_eval_end:
13495     \exp_after:wN \use_i:nn
13496   \else:
13497     \exp_after:wN \use_ii:nn
13498   \fi:
13499   { % 1/18!
13500     \_fp_fixed_mul_sub_back:wwnn      {0000}{0000}{0000}{0001}{5619}{2070};
13501           #4; {0000}{0000}{0000}{0477}{9477}{3324};
13502     \_fp_fixed_mul_sub_back:wwnn #4; {0000}{0000}{0011}{4707}{4559}{7730};
13503     \_fp_fixed_mul_sub_back:wwnn #4; {0000}{0000}{2087}{6756}{9878}{6810};
13504     \_fp_fixed_mul_sub_back:wwnn #4; {0000}{0027}{5573}{1922}{3985}{8907};
13505     \_fp_fixed_mul_sub_back:wwnn #4; {0000}{2480}{1587}{3015}{8730}{1587};
13506     \_fp_fixed_mul_sub_back:wwnn #4; {0013}{8888}{8888}{8888}{8888}{8889};
13507     \_fp_fixed_mul_sub_back:wwnn #4; {0416}{6666}{6666}{6666}{6666}{6667};
13508     \_fp_fixed_mul_sub_back:wwnn #4; {5000}{0000}{0000}{0000}{0000}{0000};
13509     \_fp_fixed_mul_sub_back:wwnn #4; {10000}{0000}{0000}{0000}{0000}{0000};
13510   }
13511   { % 1/17!
13512     \_fp_fixed_mul_sub_back:wwnn      {0000}{0000}{0000}{0028}{1145}{7254};
13513           #4; {0000}{0000}{0000}{7647}{1637}{3182};
13514     \_fp_fixed_mul_sub_back:wwnn #4; {0000}{0000}{0160}{5904}{3836}{8216};
13515     \_fp_fixed_mul_sub_back:wwnn #4; {0000}{0002}{5052}{1083}{8544}{1719};
13516     \_fp_fixed_mul_sub_back:wwnn #4; {0000}{0275}{5731}{9223}{9858}{9065};
13517     \_fp_fixed_mul_sub_back:wwnn #4; {0001}{9841}{2698}{4126}{9841}{2698};
13518     \_fp_fixed_mul_sub_back:wwnn #4; {0083}{3333}{3333}{3333}{3333}{3333};

```

```

13519     \__fp_fixed_mul_sub_back:www #4; {1666}{6666}{6666}{6666}{6667};
13520     \__fp_fixed_mul_sub_back:www #4; {10000}{0000}{0000}{0000}{0000};
13521     \__fp_fixed_mul:wwn #5;
13522 }
13523 {
13524     \exp_after:wN \__fp_sanitize:Nw
13525     \exp_after:wN #2
13526     \int_use:N \__int_eval:w #1
13527 }
13528 #2
13529 }

(End definition for \__fp_sin_series:NNwww and \__fp_sin_series_aux:NNnww)

```

Contrarily to `__fp_sin_series:NNwww` which received the conversion auxiliary as #1, here #1 is 0 for tangent, and 2 for cotangent. Consider first the case of the tangent. The octant #3 starts at 1, which means that it is 1 or 2 for $|x| \in [0, \pi/2]$, it is 3 or 4 for $|x| \in [\pi/2, \pi]$, and so on: the intervals on which $\tan|x| \geq 0$ coincide with those for which $\lfloor(\#3+1)/2\rfloor$ is odd. We also have to take into account the original sign of x to get the sign of the final result; it is straightforward to check that the first `__int_value:w` expansion produces 0 for a positive final result, and 2 otherwise. A similar story holds for $\cot(x)$.

The auxiliary receives the sign, the octant, the square of the (reduced) input, and the (reduced) input as arguments. It then computes the numerator and denominator of

$$\tan(x) \simeq \frac{x(1 - x^2(a_1 - x^2(a_2 - x^2(a_3 - x^2(a_4 - x^2a_5)))))}{1 - x^2(b_1 - x^2(b_2 - x^2(b_3 - x^2(b_4 - x^2b_5))))}.$$

The ratio itself is computed by `__fp_fixed_div_to_float:ww`, which converts it directly to a floating point number to avoid rounding issues. For octants #2 (really, quadrants) next to a pole of the functions, the fixed point numerator and denominator are exchanged before computing the ratio. Note that this `\if_int_odd:w` test relies on the fact that the octant is at least 1.

```

13530 \cs_new:Npn \__fp_tan_series_o:NNwww #1#2#3. #4; #5;
13531 {
13532     \__fp_fixed_mul:wwn #4; #4;
13533 {
13534     \exp_after:wN \__fp_tan_series_aux_o:Nnww
13535     \__int_value:w
13536     \if_int_odd:w \__int_eval:w #3 / \c_two \__int_eval_end:
13537         \exp_after:wN \reverse_if:N
13538     \fi:
13539     \if_meaning:w #1#2 2 \else: 0 \fi:
13540     {#3}
13541 }
13542 #4 ;
13543 }
13544 \cs_new:Npn \__fp_tan_series_aux_o:Nnww #1 #2 #3; #4;
13545 {

```

```

13546   \__fp_fixed_mul_sub_back:wwwn    {0000}{0000}{1527}{3493}{0856}{7059};
13547                           #3; {0000}{0159}{6080}{0274}{5257}{6472};
13548   \__fp_fixed_mul_sub_back:wwwn #3; {0002}{4571}{2320}{0157}{2558}{8481};
13549   \__fp_fixed_mul_sub_back:wwwn #3; {0115}{5830}{7533}{5397}{3168}{2147};
13550   \__fp_fixed_mul_sub_back:wwwn #3; {1929}{8245}{6140}{3508}{7719}{2982};
13551   \__fp_fixed_mul_sub_back:wwwn #3; {10000}{0000}{0000}{0000}{0000}{0000};
13552   \__fp_fixed_mul:wwn #4;
13553   {
13554     \__fp_fixed_mul_sub_back:wwwn    {0000}{0007}{0258}{0681}{9408}{4706};
13555                           #3; {0000}{2343}{7175}{1399}{6151}{7670};
13556   \__fp_fixed_mul_sub_back:wwwn #3; {0019}{2638}{4588}{9232}{8861}{3691};
13557   \__fp_fixed_mul_sub_back:wwwn #3; {0536}{6357}{0691}{4344}{6852}{4252};
13558   \__fp_fixed_mul_sub_back:wwwn #3; {5263}{1578}{9473}{6842}{1052}{6315};
13559   \__fp_fixed_mul_sub_back:wwwn #3; {10000}{0000}{0000}{0000}{0000}{0000};
13560   {
13561     \exp_after:wN \__fp_sanitize:Nw
13562     \exp_after:wN #1
13563     \int_use:N \__int_eval:w
13564       \reverse_if:N \if_int_odd:w
13565         \__int_eval:w (#2 - \c_one) / \c_two \__int_eval_end:
13566         \exp_after:wN \__fp_reverse_args:Nww
13567         \fi:
13568         \__fp_fixed_div_to_float:ww
13569       }
13570   }
13571 }

(End definition for \__fp_tan_series_o:NNwww and \__fp_tan_series_aux_o:Nnww)

13572 </initex | package>
```

37 l3fp-convert implementation

```

13573 <*initex | package>
13574 <@@=fp>
```

37.1 Trimming trailing zeros

If #1 ends with a 0, the loop auxiliary takes that zero as an end-delimiter for its first argument, and the second argument is the same loop auxiliary. Once the last trailing zero is reached, the second argument will be the dot auxiliary, which removes a trailing dot if any. We then clean-up with the end auxiliary, keeping only the number.

```

13575 \cs_new:Npn \__fp_trim_zeros:w #1 ;
13576   {
13577     \__fp_trim_zeros_loop:w #1
13578     ; \__fp_trim_zeros_loop:w 0; \__fp_trim_zeros_dot:w .; \s_stop
13579   }
13580 \cs_new:Npn \__fp_trim_zeros_loop:w #1 0; #2 { #2 #1 ; #2 }
13581 \cs_new:Npn \__fp_trim_zeros_dot:w #1 .; { \__fp_trim_zeros_end:w #1 ; }
13582 \cs_new:Npn \__fp_trim_zeros_end:w #1 ; #2 \s_stop { #1 }
```

(End definition for `_fp_trim_zeros:w` This function is documented on page ??.)

37.2 Scientific notation

`\fp_to_scientific:N` The three public functions evaluate their argument, then pass it to `_fp_to_scientific_dispatch:w`.

```
13583 \cs_new:Npn \fp_to_scientific:N #1
13584   { \exp_after:wn \_fp_to_scientific_dispatch:w #1 }
13585 \cs_generate_variant:Nn \fp_to_scientific:N { c }
13586 \cs_new_nopar:Npn \fp_to_scientific:n
13587   {
13588     \exp_after:wn \_fp_to_scientific_dispatch:w
13589     \tex_roman numeral:D -'0 \_fp_parse:n
13590   }
```

(End definition for `\fp_to_scientific:N`, `\fp_to_scientific:c`, and `\fp_to_scientific:n` These functions are documented on page ??.)

`_fp_to_scientific_dispatch:w`
`_fp_to_scientific_normal:wnnnnn`
`_fp_to_scientific_normal:wNw`

Expressing an internal floating point number in scientific notation is quite easy: no rounding, and the format is very well defined. First cater for the sign: negative numbers (#2 = 2) start with `-`; we then only need to care about positive numbers and `nan`. Then filter the special cases: ± 0 are represented as 0; infinities are converted to a number slightly larger than the largest after an “invalid_operation” exception; `nan` is represented as 0 after an “invalid_operation” exception. In the normal case, decrement the exponent and unbrace the 4 brace groups, then in a second step grab the first digit (previously hidden in braces) to order the various parts correctly. Finally trim zeros. The whole construction is within a call to `\tl_to_lowercase:n`, responsible for creating `e` with category “other”.

```
13591 \group_begin:
13592 \char_set_catcode_other:N E
13593 \tl_to_lowercase:n
13594   {
13595     \group_end:
13596     \cs_new:Npn \_fp_to_scientific_dispatch:w \s_fp \_fp_chk:w #1#2
13597     {
13598       \if_meaning:w 2 #2 \exp_after:wn - \tex_roman numeral:D -'0 \fi:
13599       \if_case:w #1 \exp_stop_f:
13600         \_fp_case_return:nw { 0 }
13601       \or: \exp_after:wn \_fp_to_scientific_normal:wnnnnn
13602       \or:
13603         \_fp_case_use:nw
13604         {
13605           \_fp_invalid_operation:nnw
13606           {
13607             \exp_after:wn 1
13608             \exp_after:wn E
13609             \int_use:N \c_fp_max_exponent_int
13610           }
13611         { fp_to_scientific }
```

```

13612         }
13613     \or:
13614     \_\_fp\_case\_use:nw
13615     {
13616         \_\_fp\_invalid\_operation:nnw
13617         { 0 }
13618         { fp\_to\_scientific }
13619     }
13620     \fi:
13621     \s\_fp \_\_fp\_chk:w #1 #2
13622 }
13623 \cs_new:Npn \_\_fp\_to\_scientific\_normal:wnnnnn
13624     \s\_fp \_\_fp\_chk:w 1 #1 #2 #3#4#5#6 ;
13625 {
13626     \if_int_compare:w #2 = \c_one
13627         \exp_after:wN \_\_fp\_to\_scientific\_normal:wNw
13628     \else:
13629         \exp_after:wN \_\_fp\_to\_scientific\_normal:wNw
13630         \exp_after:wN E
13631         \int_use:N \_\_int_eval:w #2 - \c_one
13632     \fi:
13633     ; #3 #4 #5 #6 ;
13634 }
13635 }
13636 \cs_new:Npn \_\_fp\_to\_scientific\_normal:wNw #1 ; #2#3;
13637 { \_\_fp\_trim\_zeros:w #2.#3 ; #1 }
(End definition for \_\_fp\_to\_scientific\_dispatch:w, \_\_fp\_to\_scientific\_normal:wnnnnn, and \_\_fp\_to\_scientific\_nor

```

37.3 Decimal representation

\fp_to_decimal:N
\fp_to_decimal:c
\fp_to_decimal:n

All three public variants are based on the same __fp_to_decimal_dispatch:w after evaluating their argument to an internal floating point.

```

13638 \cs_new:Npn \fp_to_decimal:N #1
13639 { \exp_after:wn \_\_fp_to_decimal_dispatch:w #1 }
13640 \cs_generate_variant:Nn \fp_to_decimal:N { c }
13641 \cs_new_nopar:Npn \fp_to_decimal:n
13642 {
13643     \exp_after:wn \_\_fp_to_decimal_dispatch:w
13644     \tex_roman numeral:D -'0 \_\_fp_parse:n
13645 }

```

(End definition for \fp_to_decimal:N, \fp_to_decimal:c, and \fp_to_decimal:n These functions are documented on page ??.)

\

__fp_to_decimal_dispatch:w

__fp_to_decimal_normal:wnnnn

__fp_to_decimal_large:Nnnw

__fp_to_decimal_huge:wnnnn

The structure is similar to __fp_to_scientific_dispatch:w. Insert - for negative numbers. Zero gives 0, $\pm\infty$ and nan yield an “invalid operation” exception; note that $\pm\infty$ produces a very large output, which we don’t expand now since it most likely won’t be needed. Normal numbers with an exponent in the range [1, 15] have that number of digits before the decimal separator: “decimate” them, and remove leading zeros with __int_value:w, then trim trailing zeros and dot. Normal numbers with an exponent

16 or larger have no decimal separator, we only need to add trailing zeros. When the exponent is non-positive, the result should be $0.\langle\text{zeros}\rangle\langle\text{digits}\rangle$, trimmed.

```

13646 \cs_new:Npn \__fp_to_decimal_dispatch:w \s_fp \__fp_chk:w #1#2
13647 {
13648   \if_meaning:w 2 #2 \exp_after:wN - \tex_roman numeral:D -'0 \fi:
13649   \if_case:w #1 \exp_stop_f:
13650     \__fp_case_return:nw { 0 }
13651   \or: \exp_after:wN \__fp_to_decimal_normal:wnnnnn
13652   \or:
13653     \__fp_case_use:nw
13654     {
13655       \__fp_invalid_operation:nnw
13656       {
13657         \exp_after:wN \exp_after:wN \exp_after:wN 1
13658         \prg_replicate:nn \c_fp_max_exponent_int 0
13659       }
13660       { fp_to_decimal }
13661     }
13662   \or:
13663     \__fp_case_use:nw
13664     {
13665       \__fp_invalid_operation:nnw
13666       { 0 }
13667       { fp_to_decimal }
13668     }
13669   \fi:
13670   \s_fp \__fp_chk:w #1 #2
13671 }
13672 \cs_new:Npn \__fp_to_decimal_normal:wnnnnn
13673   \s_fp \__fp_chk:w 1 #1 #2 #3#4#5#6 ;
13674 {
13675   \int_compare:nNnTF {#2} > \c_zero
13676   {
13677     \int_compare:nNnTF {#2} < \c_sixteen
13678     {
13679       \__fp_decimate:nNnnnn { \c_sixteen - #2 }
13680       \__fp_to_decimal_large:Nnnw
13681     }
13682   {
13683     \exp_after:wN \exp_after:wN
13684     \exp_after:wN \__fp_to_decimal_huge:wnnnn
13685     \prg_replicate:nn { #2 - \c_sixteen } { 0 } ;
13686   }
13687   {#3} {#4} {#5} {#6}
13688 }
13689 {
13690   \exp_after:wN \__fp_trim_zeros:w
13691   \exp_after:wN 0
13692   \exp_after:wN .

```

```

13693     \tex_roman numeral:D -'0 \prg_replicate:nn { - #2 } { 0 }
13694     #3#4#5#6 ;
13695   }
13696 }
13697 \cs_new:Npn \__fp_to_decimal_large:Nnnw #1#2#3#4;
13698 {
13699   \exp_after:wN \__fp_trim_zeros:w \__int_value:w
13700   \if_int_compare:w #2 > \c_zero
13701     #2
13702   \fi:
13703   \exp_stop_f:
13704   #3.#4 ;
13705 }
13706 \cs_new:Npn \__fp_to_decimal_huge:wnnnn #1; #2#3#4#5 { #2#3#4#5 #1 }
(End definition for \__fp_to_decimal_dispatch:w and others.)

```

37.4 Token list representation

\fp_to_tl:N

These three public functions evaluate their argument, then pass it to __fp_to_tl_dispatch:w.

\fp_to_tl:c

13707 \cs_new:Npn \fp_to_tl:N #1 { \exp_after:wN __fp_to_tl_dispatch:w #1 }

\fp_to_tl:n

13708 \cs_generate_variant:Nn \fp_to_tl:N { c }

13709 \cs_new_nopar:Npn \fp_to_tl:n

13710 {

13711 \exp_after:wN __fp_to_tl_dispatch:w

13712 \tex_roman numeral:D -'0 __fp_parse:n

13713 }

(End definition for \fp_to_tl:N, \fp_to_tl:c, and \fp_to_tl:n These functions are documented on page ??.)

__fp_to_tl_dispatch:w
__fp_to_tl_normal:nnnnn

A structure similar to __fp_to_scientific_dispatch:w and __fp_to_decimal_dispatch:w, but without the “invalid operation” exception. First filter special cases. We express normal numbers in decimal notation if the exponent is in the range $[-2, 16]$, and otherwise use scientific notation.

```

13714 \cs_new:Npn \__fp_to_tl_dispatch:w \s__fp \__fp_chk:w #1#2
13715 {
13716   \if_meaning:w 2 #2 \exp_after:wN - \tex_roman numeral:D -'0 \fi:
13717   \if_case:w #1 \exp_stop_f:
13718     \__fp_case_return:nw { 0 }
13719   \or: \exp_after:wN \__fp_to_tl_normal:nnnnn
13720   \or: \__fp_case_return:nw { \tl_to_str:n {inf} }
13721   \else: \__fp_case_return:nw { \tl_to_str:n {nan} }
13722   \fi:
13723 }
13724 \cs_new:Npn \__fp_to_tl_normal:nnnnn #1
13725 {
13726   \if_int_compare:w #1 > \c_sixteen
13727     \exp_after:wN \__fp_to_scientific_normal:wnnnnn
13728   \else:

```

```

13729   \if_int_compare:w #1 < - \c_two
13730     \exp_after:wN \exp_after:wN
13731     \exp_after:wN \__fp_to_scientific_normal:wnnnnn
13732   \else:
13733     \exp_after:wN \exp_after:wN
13734     \exp_after:wN \__fp_to_decimal_normal:wnnnnn
13735   \fi:
13736 \fi:
13737 \s_fp \__fp_chk:w 1 0 {#1}
13738 }

```

(End definition for `__fp_to_tl_dispatch:w` and `__fp_to_tl_normal:nnnn`)

37.5 Formatting

This is not implemented yet, as it is not yet clear what a correct interface would be, for this kind of structured conversion from a floating point (or other types of variables) to a string. Ideas welcome.

37.6 Convert to dimension or integer

`\fp_to_dim:N` These three public functions rely on `\fp_to_decimal:n` internally. We make sure to produce pt with category other.

```

\fp_to_dim:c
\fp_to_dim:n
13739 \cs_new:Npx \fp_to_dim:N #1
13740   { \exp_not:N \fp_to_decimal:N #1 \tl_to_str:n {pt} }
13741 \cs_generate_variant:Nn \fp_to_dim:N { c }
13742 \cs_new:Npx \fp_to_dim:n #1
13743   { \exp_not:N \fp_to_decimal:n {#1} \tl_to_str:n {pt} }

```

(End definition for `\fp_to_dim:N`, `\fp_to_dim:c`, and `\fp_to_dim:n`. These functions are documented on page ??.)

`\fp_to_int:N` These three public functions evaluate their argument, then pass it to `\fp_to_int_- dispatch:w`.

```

\fp_to_int:c
\fp_to_int:n
13744 \cs_new:Npn \fp_to_int:N #1 { \exp_after:wN \__fp_to_int_dispatch:w #1 }
13745 \cs_generate_variant:Nn \fp_to_int:N { c }
13746 \cs_new_nopar:Npn \fp_to_int:n
13747   {
13748     \exp_after:wN \__fp_to_int_dispatch:w
13749     \tex_roman numeral:D -'0 \__fp_parse:n
13750   }

```

(End definition for `\fp_to_int:N`, `\fp_to_int:c`, and `\fp_to_int:n`. These functions are documented on page ??.)

`__fp_to_int_dispatch:w` To convert to an integer, first round to 0 places (to the nearest integer), then express the result as a decimal number: the definition of `__fp_to_decimal_dispatch:w` is such that there will be no trailing dot nor zero.

```

13751 \cs_new:Npn \__fp_to_int_dispatch:w #1;
13752   {
13753     \exp_after:wN \__fp_to_decimal_dispatch:w \tex_roman numeral:D -'0

```

```

13754     \__fp_round:Nwn \__fp_round_to_nearest:NNN #1; { 0 }
13755   }
(End definition for \__fp_to_int_dispatch:w)
```

37.7 Convert from a dimension

The dimension expression (which can in fact be a glue expression) is evaluated, converted to a number (*i.e.*, expressed in scaled points), then multiplied by $2^{-16} = 0.0000152587890625$ to give a value expressed in points. The auxiliary `__fp_mul_npos_o:Nww` expects the desired *<final sign>* and two floating point operands (of the form `\s_fp ... ;`) as arguments.

```

13756 \cs_new:Npn \dim_to_fp:n #1
13757 {
13758   \exp_after:WN \__fp_from_dim_test:N
13759   \__int_value:w \etex_glueexpr:D #1 ;
13760 }
13761 \cs_new:Npn \__fp_from_dim_test:N #1
13762 {
13763   \if_meaning:w 0 #1
13764     \__fp_case_return:nw \c_zero_fp
13765   \else:
13766     \if_meaning:w - #1
13767       \exp_after:WN \__fp_from_dim:Nw
13768       \exp_after:WN 2
13769       \__int_value:w
13770     \else:
13771       \exp_after:WN \__fp_from_dim:Nw
13772       \exp_after:WN 0
13773       \__int_value:w #1
13774     \fi:
13775   \fi:
13776 }
13777 \cs_new:Npn \__fp_from_dim:Nw #1 #2;
13778 {
13779   \__fp_pack_twice_four:wNNNNNNNN \__fp_from_dim_i:i:wNNnnnnnn ;
13780   #2 000 0000 00 {10}987654321; #1
13781 }
13782 \cs_new:Npn \__fp_from_dim_i:i:wNNnnnnnn #1; #2#3#4#5#6#7#8#9
13783   { \__fp_from_dim_iii:wnnnnwN #1 {#2#300} {0000} ; }
13784 \cs_new:Npn \__fp_from_dim_iii:wnnnnwN #1; #2#3#4#5#6; #7
13785 {
13786   \__fp_mul_npos_o:Nww #7
13787   \s_fp \__fp_chk:w 1 #7 {#5} #1 ;
13788   \s_fp \__fp_chk:w 1 0 {-4} {1525} {8789} {0625} {0000} ;
13789 }
```

(End definition for `\dim_to_fp:n`. This function is documented on page 177.)

37.8 Use and eval

\fp_use:N Those public functions are simple copies of the decimal conversions.
\fp_use:c 13790 `\cs_new_eq:NN \fp_use:N \fp_to_decimal:N`
\fp_eval:n 13791 `\cs_generate_variant:Nn \fp_use:N { c }`
13792 `\cs_new_eq:NN \fp_eval:n \fp_to_decimal:n`
(End definition for \fp_use:N, \fp_use:c, and \fp_eval:n These functions are documented on page 166.)

\fp_abs:n Trivial but useful. See the implementation of \fp_add:Nn for an explanation of why to use __fp_parse:n, namely, for better error reporting.

```
13793 \cs_new:Npn \fp_abs:n #1
13794   { \fp_to_decimal:n { abs \__fp_parse:n {#1} } }
(End definition for \fp_abs:n This function is documented on page 177.)
```

\fp_max:nn Similar to \fp_abs:n, for consistency with \int_max:nn, etc.

\fp_min:nn 13795 `\cs_new:Npn \fp_max:nn #1#2`
13796 { \fp_to_decimal:n { max (__fp_parse:n {#1} , __fp_parse:n {#2}) } }
13797 `\cs_new:Npn \fp_min:nn #1#2`
13798 { \fp_to_decimal:n { min (__fp_parse:n {#1} , __fp_parse:n {#2}) } }
(End definition for \fp_max:nn and \fp_min:nn These functions are documented on page 177.)

37.9 Convert an array of floating points to a comma list

__fp_array_to_clist:n Converts an array of floating point numbers to a comma-list. If speed here ends up irrelevant, we can simplify the code for the auxiliary to become
__fp_array_to_clist_loop:Nw

```
\cs_new:Npn \__fp_array_to_clist_loop:Nw #1#2;
{
  \use_none:n #1
  { , ~ } \fp_to_tl:n { #1 #2 ; }
  \__fp_array_to_clist_loop:Nw
}
```

The \use_ii:nn function is expanded after __fp_expand:n is done, and it removes ,~ from the start of the representation.

```
13799 \cs_new:Npn \__fp_array_to_clist:n #1
13800   {
13801     \tl_if_empty:nF {#1}
13802     {
13803       \__fp_expand:n
13804       {
13805         { \use_ii:nn }
13806         \__fp_array_to_clist_loop:Nw #1 { ? \__prg_break: } ;
13807         \__prg_break_point:
13808       }
13809     }
13810 }
```

```

13811 \cs_new:Npx \__fp_array_to_clist_loop:Nw #1#2;
13812 {
13813   \exp_not:N \use_none:n #1
13814   \exp_not:N \exp_after:wN
13815     {
13816       \exp_not:N \exp_after:wN ,
13817       \exp_not:N \exp_after:wN \c_space_tl
13818       \exp_not:N \tex_roman numeral:D -'0
13819       \exp_not:N \__fp_to_tl_dispatch:w #1 #2 ;
13820     }
13821   \exp_not:N \__fp_array_to_clist_loop:Nw
13822 }
(End definition for \__fp_array_to_clist:n This function is documented on page ??.)
13823 </initex | package>

```

38 l3fp-assign implementation

```

13824 <*initex | package>
13825 <@=fp>

```

38.1 Assigning values

\fp_new:N Floating point variables are initialized to be +0.

```

13826 \cs_new_protected:Npn \fp_new:N #1
13827   { \cs_new_eq:NN #1 \c_zero_fp }
13828 \cs_generate_variant:Nn \fp_new:N {c}
(End definition for \fp_new:N This function is documented on page 165.)

```

\fp_set:Nn Simply use __fp_parse:n within various x-expanding assignments.

```

13829 \cs_new_protected:Npn \fp_set:Nn #1#2
13830   { \tl_set:Nx #1 { \__fp_parse:n {#2} } }
13831 \cs_new_protected:Npn \fp_gset:Nn #1#2
13832   { \tl_gset:Nx #1 { \__fp_parse:n {#2} } }
13833 \cs_new_protected:Npn \fp_const:Nn #1#2
13834   { \tl_const:Nx #1 { \__fp_parse:n {#2} } }
13835 \cs_generate_variant:Nn \fp_set:Nn {c}
13836 \cs_generate_variant:Nn \fp_gset:Nn {c}
13837 \cs_generate_variant:Nn \fp_const:Nn {c}
(End definition for \fp_set:Nn and others. These functions are documented on page ??.)

```

\fp_set_eq:NN Copying a floating point is the same as copying the underlying token list.

```

13838 \cs_new_eq:NN \fp_set_eq:NN \tl_set_eq:NN
13839 \cs_new_eq:NN \fp_gset_eq:NN \tl_gset_eq:NN
13840 \cs_generate_variant:Nn \fp_set_eq:NN { c , Nc , cc }
13841 \cs_generate_variant:Nn \fp_gset_eq:NN { c , Nc , cc }
(End definition for \fp_set_eq:NN and others. These functions are documented on page ??.)
\fp_gset_eq:cN
\fp_gset_eq:Nc
\fp_gset_eq:cc

```

```

\fp_zero:N      Setting a floating point to zero: copy \c_zero_fp.
\fp_zero:c
\fp_gzero:N
\fp_gzero:c
13842 \cs_new_protected:Npn \fp_zero:N #1 { \fp_set_eq:NN #1 \c_zero_fp }
13843 \cs_new_protected:Npn \fp_gzero:N #1 { \fp_gset_eq:NN #1 \c_zero_fp }
13844 \cs_generate_variant:Nn \fp_zero:N { c }
13845 \cs_generate_variant:Nn \fp_gzero:N { c }

(End definition for \fp_zero:N and others. These functions are documented on page ??.)

```

```

\fp_zero_new:N   Set the floating point to zero, or define it if needed.
\fp_zero_new:c
\fp_gzero_new:N
\fp_gzero_new:c
13846 \cs_new_protected:Npn \fp_zero_new:N #1
13847 { \fp_if_exist:NTF #1 { \fp_zero:N #1 } { \fp_new:N #1 } }
13848 \cs_new_protected:Npn \fp_gzero_new:N #1
13849 { \fp_if_exist:NTF #1 { \fp_gzero:N #1 } { \fp_new:N #1 } }
13850 \cs_generate_variant:Nn \fp_zero_new:N { c }
13851 \cs_generate_variant:Nn \fp_gzero_new:N { c }

(End definition for \fp_zero_new:N and others. These functions are documented on page ??.)

```

38.2 Updating values

These match the equivalent functions in `\3int` and `\3skip`.

```

\fp_add:Nn      For the sake of error recovery we should not simply set #1 to  $\#1 \pm (\#2)$ : for instance, if #2
\fp_add:cn      is 0)+2, the parsing error would be raised at the last closing parenthesis rather than at
\fp_gadd:Nn      the closing parenthesis in the user argument. Thus we evaluate #2 instead of just putting
\fp_gadd:cn      parentheses. As an optimization we use \_fp_parse:n rather than \fp_eval:n, which
\fp_sub:Nn      would convert the result away from the internal representation and back.
\fp_sub:cn
\fp_gsub:Nn
\fp_gsub:cn
\fp_add:NNNn
13852 \cs_new_protected_nopar:Npn \fp_add:Nn { \_fp_add:NNNn \fp_set:Nn + }
13853 \cs_new_protected_nopar:Npn \fp_gadd:Nn { \_fp_add:NNNn \fp_gset:Nn + }
13854 \cs_new_protected_nopar:Npn \fp_sub:Nn { \_fp_add:NNNn \fp_set:Nn - }
13855 \cs_new_protected_nopar:Npn \fp_gsub:Nn { \_fp_add:NNNn \fp_gset:Nn - }
13856 \cs_new_protected:Npn \_fp_add:NNNn #1#2#3#4
13857 { #1 #3 { #3 #2 \_fp_parse:n {#4} } }
13858 \cs_generate_variant:Nn \fp_add:Nn { c }
13859 \cs_generate_variant:Nn \fp_gadd:Nn { c }
13860 \cs_generate_variant:Nn \fp_sub:Nn { c }
13861 \cs_generate_variant:Nn \fp_gsub:Nn { c }

(End definition for \fp_add:Nn and others. These functions are documented on page ??.)

```

38.3 Showing values

`\fp_show:N` This shows the result of computing its argument. The `_msg_show_variable:n` auxiliary expects its input in a slightly odd form, starting with `>~`, and displays the rest.

```

\fp_show:c
\fp_show:n
13862 \cs_new_protected:Npn \fp_show:N #1
13863 {
13864 \fp_if_exist:NTF #1
13865 { \_msg_show_variable:n { > ~ \fp_to_tl:N #1 } }
13866 {
13867 \_msg_kernel_error:nmx { kernel } { variable-not-defined }
13868 { \token_to_str:N #1 }


```

```

13869      }
13870  }
13871 \cs_new_protected:Npn \fp_show:n #1
13872 { \__msg_show_variable:n { > ~ \fp_to_tl:n {#1} } }
13873 \cs_generate_variant:Nn \fp_show:N { c }
(End definition for \fp_show:N, \fp_show:c, and \fp_show:n These functions are documented on page ??.)
```

38.4 Some useful constants and scratch variables

\c_one_fp Some constants.

```

\c_e_fp 13874 \fp_const:Nn \c_e_fp           { 2.718 2818 2845 9045 }
13875 \fp_const:Nn \c_one_fp          { 1 }
```

(End definition for \c_one_fp and \c_e_fp These variables are documented on page 170.)

\c_pi_fp We do not round π to the closest multiple of 10^{-15} , which would underestimate it by roughly $2.4 \cdot 10^{-16}$, but instead round it up to the next nearest multiple, which is an overestimate by roughly $7.7 \cdot 10^{-16}$. This particular choice of rounding has very nice properties: it is exactly divisible by 4 and by 180 as a 16-digit precision floating point number, hence ensuring that $\sin(180\text{deg}) = \sin(\pi) = 0$ exactly, with no rounding artifact.

```

13876 \fp_const:Nn \c_pi_fp           { 3.141 5926 5358 9794 }
13877 \fp_const:Nn \c_one_degree_fp { 0.0 1745 3292 5199 4330 }
```

(End definition for \c_pi_fp and \c_one_degree_fp These variables are documented on page 170.)

\l_tmpa_fp Scratch variables are simply initialized there.

```

\l_tmpb_fp 13878 \fp_new:N \l_tmpa_fp
\g_tmpa_fp 13879 \fp_new:N \l_tmpb_fp
\g_tmpb_fp 13880 \fp_new:N \g_tmpa_fp
13881 \fp_new:N \g_tmpb_fp
```

(End definition for \l_tmpa_fp and others. These variables are documented on page 170.)

```
13882 ⟨/initex | package⟩
```

39 l3fp-old implementation

```
13883 ⟨*initex | package⟩
```

```
13884 ⟨@@=fp⟩
```

39.1 Compatibility

\c_undefined_fp The old floating point number \c_undefined_fp is now implemented as a nan.

```
13885 \fp_const:Nn \c_undefined_fp { nan }
```

(End definition for \c_undefined_fp This variable is documented on page ??.)

<code>\fp_if_undefined_p:N</code>	An old floating point is undefined if it is <code>inf</code> or <code>nan</code> , <i>i.e.</i> , if its type is 2 or 3.
<code>\fp_if_undefined:NTF</code>	<pre> 13886 \prg_new_conditional:Npnn \fp_if_undefined:N #1 { p , T , F , TF } 13887 { \exp_after:wN __fp_if_undefined:w #1 } 13888 \cs_new:Npn __fp_if_undefined:w \s__fp __fp_chk:w #1#2; 13889 { 13890 \if_int_compare:w #1 > \c_one 13891 \prg_return_true: \else: \prg_return_false: \fi: 13892 } </pre> <p>(End definition for <code>\fp_if_undefined:N</code> These functions are documented on page ??.)</p>
<code>\fp_if_zero_p:N</code>	An old floating point is zero if it is ± 0 , <i>i.e.</i> , its type is 0.
<code>\fp_if_zero:NTF</code>	<pre> 13893 \prg_new_conditional:Npnn \fp_if_zero:N #1 { p , T , F , TF } 13894 { \exp_after:wN __fp_if_zero:w #1 } 13895 \cs_new:Npn __fp_if_zero:w \s__fp __fp_chk:w #1#2; 13896 { \if_meaning:w #1 0 \prg_return_true: \else: \prg_return_false: \fi: } </pre> <p>(End definition for <code>\fp_if_zero:N</code> These functions are documented on page ??.)</p>
<code>\fp_abs:N</code> <code>\fp_abs:c</code> <code>\fp_gabs:N</code> <code>\fp_gabs:c</code> <code>\fp_neg:N</code> <code>\fp_neg:c</code> <code>\fp_gneg:N</code> <code>\fp_gneg:c</code> <code>__fp_abs:NNN</code>	Simply expand the floating point variable to feed it to <code>__fp_abs_o:w</code> or <code>__fp_-o:w</code> , expanded within an expanding token list assignment. The <code>\prg_do_nothing:</code> is not necessary, but it reminds us more clearly that <code>__fp_abs_o:w</code> and <code>__fp_-o:w</code> expand after their result.
	<pre> 13897 \cs_new_protected_nopar:Npn \fp_abs:N { __fp_abs:NNN \tl_set:Nx __fp_abs_o:w } 13898 \cs_new_protected_nopar:Npn \fp_gabs:N { __fp_abs:NNN \tl_gset:Nx __fp_abs_o:w } 13899 \cs_new_protected_nopar:Npx \fp_neg:N 13900 { 13901 \exp_not:N __fp_abs:NNN 13902 \exp_not:N \tl_set:Nx 13903 \exp_not:c { __fp_-o:w } 13904 } 13905 \cs_new_protected_nopar:Npx \fp_gneg:N 13906 { 13907 \exp_not:N __fp_abs:NNN 13908 \exp_not:N \tl_gset:Nx 13909 \exp_not:c { __fp_-o:w } 13910 } 13911 \cs_new_protected:Npn __fp_abs:NNN #1#2#3 13912 { #1 #3 { \exp_after:wN #2 #3 \prg_do_nothing: } } 13913 \cs_generate_variant:Nn \fp_abs:N { c } 13914 \cs_generate_variant:Nn \fp_gabs:N { c } 13915 \cs_generate_variant:Nn \fp_neg:N { c } 13916 \cs_generate_variant:Nn \fp_gneg:N { c } </pre> <p>(End definition for <code>\fp_abs:N</code> and others. These functions are documented on page ??.)</p>
<code>\fp_mul:Nn</code> <code>\fp_mul:cn</code> <code>\fp_gmul:Nn</code> <code>\fp_gmul:cn</code> <code>\fp_div:Nn</code> <code>\fp_div:cn</code> <code>\fp_gdiv:Nn</code> <code>\fp_gdiv:cn</code> <code>\fp_pow:Nn</code> <code>\fp_pow:cn</code> <code>\fp_gpow:Nn</code> <code>\fp_gpow:cn</code> <code>__fp_mul>NNNn</code>	See <code>\fp_add:Nn</code> for details.
	<pre> 13917 \cs_new_protected_nopar:Npn \fp_mul:Nn { __fp_mul:NNNn \fp_set:Nn * } 13918 \cs_new_protected_nopar:Npn \fp_gmul:Nn { __fp_mul:NNNn \fp_gset:Nn * } 13919 \cs_new_protected_nopar:Npn \fp_div:Nn { __fp_mul:NNNn \fp_set:Nn / } 13920 \cs_new_protected_nopar:Npn \fp_gdiv:Nn { __fp_mul:NNNn \fp_gset:Nn / } </pre>

```

13921 \cs_new_protected_nopar:Npn \fp_pow:Nn { \__fp_mul:NNNn \fp_set:Nn ^ }
13922 \cs_new_protected_nopar:Npn \fp_gpow:Nn { \__fp_mul:NNNn \fp_gset:Nn ^ }
13923 \cs_new_protected:Npn \__fp_mul:NNNn #1#2#3#4
13924 { #1 #3 { #3 #2 \__fp_parse:n {#4} } }
13925 \cs_generate_variant:Nn \fp_mul:Nn { c }
13926 \cs_generate_variant:Nn \fp_gmul:Nn { c }
13927 \cs_generate_variant:Nn \fp_div:Nn { c }
13928 \cs_generate_variant:Nn \fp_gdiv:Nn { c }
13929 \cs_generate_variant:Nn \fp_pow:Nn { c }
13930 \cs_generate_variant:Nn \fp_gpow:Nn { c }

```

(End definition for `\fp_mul:Nn` and others. These functions are documented on page ??.)

`\fp_exp:Nn` Here, an added twist is that each value computed by these expensive unary operations is
`\fp_exp:cn` stored as a constant floating point number.

```

\fp_gexp:Nn
\fp_gexp:cn
\fp_gln:Nn
\fp_gln:cn
\fp_sin:Nn
\fp_sin:cn
\fp_gsin:Nn
\fp_gsin:cn
\fp_cos:Nn
\fp_cos:cn
\fp_gcos:Nn
\fp_gcos:cn
\fp_tan:Nn
\fp_tan:cn
\fp_gtan:Nn
\fp_gtan:cn
\__fp_assign_to:nNNNn
\__fp_assign_to_i:wNNNn
\__fp_assign_to_ii:NnNNN
13931 \cs_set_protected:Npn \__fp_tmp:w #1#2#3#4#5
13932 {
13933     \cs_new_protected_nopar:Npn #1 { #5 {#4} \tl_set_eq:NN #3 }
13934     \cs_new_protected_nopar:Npn #2 { #5 {#4} \tl_gset_eq:NN #3 }
13935     \cs_generate_variant:Nn #1 { c }
13936     \cs_generate_variant:Nn #2 { c }
13937 }
13938 \__fp_tmp:w \fp_exp:Nn \fp_gexp:Nn \__fp_exp_o:w {exp} \__fp_assign_to:nNNNn
13939 \__fp_tmp:w \fp_ln:Nn \fp_gln:Nn \__fp_ln_o:w {ln} \__fp_assign_to:nNNNn
13940 \__fp_tmp:w \fp_sin:Nn \fp_gsin:Nn \__fp_sin_o:w {sin} \__fp_assign_to:nNNNn
13941 \__fp_tmp:w \fp_cos:Nn \fp_gcos:Nn \__fp_cos_o:w {cos} \__fp_assign_to:nNNNn
13942 \__fp_tmp:w \fp_tan:Nn \fp_gtan:Nn \__fp_tan_o:w {tan} \__fp_assign_to:nNNNn
13943 \cs_new_protected:Npn \__fp_assign_to:nNNNn #1#2#3#4#5
13944 {
13945     \exp_after:wn \__fp_assign_to_i:wNNNn
13946     \tex_roman numeral:D -'0 \__fp_parse:n {#5} {#1} #2#3#4
13947 }
13948 \cs_new_protected:Npn \__fp_assign_to_i:wNNNn \s_fp \__fp_chk:w #1#2#3; #4
13949 {
13950     \exp_args:Nc \__fp_assign_to_ii:NnNNN
13951     { c_fp_ #4 [ #1 # 2 \if_meaning:w 1 #1 #3 \fi: ] _fp }
13952     { #1#2#3 }
13953 }
13954 \cs_new_protected:Npn \__fp_assign_to_ii:NnNNN #1#2#3#4#5
13955 {
13956     \cs_if_exist:NF #1
13957     { \tl_const:Nx #1 { #4 \s_fp \__fp_chk:w #2; } }
13958     #3 #5 #1
13959 }

```

(End definition for `\fp_exp:Nn` and others. These functions are documented on page ??.)

`\fp_compare:NNNTF` Comparisons used to be easier between floating points stored in variables. No more.

```

13960 \cs_new_protected_nopar:Npn \fp_compare:NNNTF { \fp_compare:nNnTF }
13961 \cs_new_protected_nopar:Npn \fp_compare:NNNT { \fp_compare:nNnT }
13962 \cs_new_protected_nopar:Npn \fp_compare:NNNF { \fp_compare:nNnF }

```

(End definition for \fp_compare:NNNTF This function is documented on page ??.)

\fp_round_places:Nn Rounding to a given number of places is easy, since it is provided by the l3fp-round module.

```
13963 \cs_new_protected:Npn \fp_round_places:Nn
13964   { \__fp_round_places>NNN \tl_set:Nx }
13965 \cs_new_protected:Npn \fp_ground_places:Nn
13966   { \__fp_round_places>NNN \tl_gset:Nx }
13967 \cs_new_protected:Npn \__fp_round_places>NNN #1#2#3
13968   {
13969     #1 #2
13970   {
13971     \exp_after:wN \exp_after:wN
13972     \exp_after:wN \__fp_round:Nnn
13973     \exp_after:wN \exp_after:wN
13974     \exp_after:wN \__fp_round_to_nearest>NNN
13975     \exp_after:wN #2
13976     \exp_after:wN { \int_use:N \__int_eval:w #3 }
13977   }
13978 }
13979 \cs_generate_variant:Nn \fp_round_places:Nn { c }
13980 \cs_generate_variant:Nn \fp_ground_places:Nn { c }
(End definition for \fp_round_places:Nn and \fp_ground_places:Nn These functions are documented on page ??.)
```

\fp_round_figures:Nn Rounding to a given number of figures is the same as rounding to a number of places, after shifting by the exponent of the argument.

```
13981 \cs_new_protected:Npn \fp_round_figures:Nn #1#2
13982   {
13983     \__fp_round_places>NNN \tl_set:Nx #1
13984     { #2 - \exp_after:wN \__fp_exponent:w #1 }
13985   }
13986 \cs_new_protected:Npn \fp_ground_figures:Nn #1#2
13987   {
13988     \__fp_round_places>NNN \tl_gset:Nx #1
13989     { #2 - \exp_after:wN \__fp_exponent:w #1 }
13990   }
13991 \cs_generate_variant:Nn \fp_round_figures:Nn { c }
13992 \cs_generate_variant:Nn \fp_ground_figures:Nn { c }
(End definition for \fp_round_figures:Nn and \fp_ground_figures:Nn These functions are documented on page ??.)
```

13993 </initex | package>

40 l3luatex implementation

13994 <*initex | package>

Announce and ensure that the required packages are loaded.

```

13995  {*package}
13996  \ProvidesExplPackage
13997  {\ExplFileName}{\ExplFileVersion}{\ExplFileDescription}
13998  \_expl_package_check:
13999  
```

\lua_now_x:n When LuaTeX is in use, this is all a question of primitives with new names. On the other hand, for pdfTeX and XeTeX the argument should be removed from the input stream before issuing an error. This is expandable, using `_msg_kernel_expandable_error:nnn` as done for V-type expansion in `\3exp`.

```

\begingroup
\cs_new:Npn \lua_now_x:n #1
  {
    \_msg_kernel_expandable_error:nnn
      { kernel } { bad-engine } { \lua_now_x:n }
  }
\endgroup

```

\lua_shipout_x:n

```

14000 \lualatex_if_engine:TF
14001  {
14002    \cs_new_eq:NN \lua_now_x:n \lualatex_directlua:D
14003    \cs_new_eq:NN \lua_shipout_x:n \lualatex_latelua:D
14004  }
14005  {
14006    \cs_new:Npn \lua_now_x:n #1
14007    {
14008      \_msg_kernel_expandable_error:nnn
14009        { kernel } { bad-engine } { \lua_now_x:n }
14010    }
14011    \cs_new_protected:Npn \lua_shipout_x:n #1
14012    {
14013      \_msg_kernel_expandable_error:nnn
14014        { kernel } { bad-engine } { \lua_shipout_x:n }
14015    }
14016  }
14017 \cs_generate_variant:Nn \lua_now_x:n { x }
14018 \cs_new:Npn \lua_now:n #1
14019  { \lua_now_x:n { \exp_not:n {#1} } }
14020 \cs_generate_variant:Nn \lua_now:n { x }
14021 \cs_generate_variant:Nn \lua_shipout_x:n { x }
14022 \cs_new_protected:Npn \lua_shipout:n #1
14023  { \lua_shipout_x:n { \exp_not:n {#1} } }
14024 \cs_generate_variant:Nn \lua_shipout:n { x }

```

(End definition for `\lua_now_x:n` and `\lua_now_x:x`. These functions are documented on page ??.)

40.1 Category code tables

```

14025 
```

\g__cctab_allocate_int To allocate category code tables, both the read-only and stack tables need to be followed. There is also a sequence stack for the dynamic tables themselves.

```

\g__cctab_stack_int
\g__cctab_stack_seq
14026 \int_new:N \g__cctab_allocate_int
14027 \int_set:Nn \g__cctab_allocate_int { \c_minus_one }
14028 \int_new:N \g__cctab_stack_int
14029 \seq_new:N \g__cctab_stack_seq

```

(End definition for `\g__cctab_allocate_int`. This function is documented on page ??.)

\cctab_new:N Creating a new category code table is done slightly differently from other registers. Low-numbered tables are more efficiently-stored than high-numbered ones. There is also a need to have a stack of flexible tables as well as the set of read-only ones. To satisfy both of these requirements, odd numbered tables are used for read-only tables, and even ones for the stack. Here, therefore, the odd numbers are allocated.

```

14030 \cs_new_protected:Npn \cctab_new:N #1
14031 {
14032     \__chk_if_free_cs:N #1
14033     \int_gadd:Nn \g__cctab_allocate_int { \c_two }
14034     \int_compare:nNnTF
14035         \g__cctab_allocate_int < { \c_max_register_int + \c_one }
14036         {
14037             \tex_global:D \tex_chardef:D #1 \g__cctab_allocate_int
14038             \luatex_initcatcodetable:D #1
14039         }
14040         { \__msg_kernel_fatal:nnx { kernel } { out-of-registers } { cctab } }
14041     }
14042 \luatex_if_engine:F
14043 {
14044     \cs_set_protected:Npn \cctab_new:N #1
14045     {
14046         \__msg_kernel_error:nnx { kernel } { bad-engine }
14047         { \exp_not:N \cctab_new:N }
14048     }
14049 }
14050 {*package}
14051 \luatex_if_engine:T
14052 {
14053     \cs_set_protected:Npn \cctab_new:N #1
14054     {
14055         \__chk_if_free_cs:N #1
14056         \newcatcodetable #1
14057         \luatex_initcatcodetable:D #1
14058     }
14059 }
14060 
```

(End definition for `\cctab_new:N` This function is documented on page 182.)

\cctab_begin:N
\cctab_end: The aim here is to ensure that the saved tables are read-only. This is done by using a stack of tables which are not read only, and actually having them as “in use” copies.

```

\l__cctab_internal_tl
14061 \cs_new_protected:Npn \cctab_begin:N #1
14062 {
14063     \seq_gpush:Nx \g__cctab_stack_seq { \tex_the:D \luatex_catcodetable:D }
14064     \luatex_catcodetable:D #1
14065     \int_gadd:Nn \g__cctab_stack_int { \c_two }
14066     \int_compare:nNnT \g__cctab_stack_int > \c_max_register_int
14067         { \__msg_kernel_fatal:nn { kernel } { cctab-stack-full } }
14068     \luatex_savecatcodetable:D \g__cctab_stack_int
14069     \luatex_catcodetable:D \g__cctab_stack_int

```

```

14070    }
14071 \cs_new_protected_nopar:Npn \cctab_end:
14072 {
14073     \int_gsub:Nn \g__cctab_stack_int { \c_two }
14074     \seq_if_empty:NTF \g__cctab_stack_seq
14075         { \tl_set:Nn \l__cctab_internal_tl { 0 } }
14076         { \seq_gpop>NN \g__cctab_stack_seq \l__cctab_internal_tl }
14077     \luatex_catcodetable:D \l__cctab_internal_tl \scan_stop:
14078 }
14079 \luatex_if_engine:F
14080 {
14081     \cs_set_protected:Npn \cctab_begin:N #1
14082     {
14083         \__msg_kernel_error:nxxx { kernel } { bad-engine }
14084         { \exp_not:N \cctab_begin:N } {#1}
14085     }
14086     \cs_set_protected_nopar:Npn \cctab_end:
14087     {
14088         \__msg_kernel_error:nnx { kernel } { bad-engine }
14089         { \exp_not:N \cctab_end: }
14090     }
14091 }
14092 {*package}
14093 \luatex_if_engine:T
14094 {
14095     \cs_set_protected:Npn \cctab_begin:N #1 { \BeginCatcodeRegime #1 }
14096     \cs_set_protected_nopar:Npn \cctab_end: { \EndCatcodeRegime }
14097 }
14098 /package
14099 \tl_new:N \l__cctab_internal_tl
(End definition for \cctab_begin:N This function is documented on page ??.)
```

\cctab_gset:Nn Category code tables are always global, so only one version is needed. The set up here is simple, and means that at the point of use there is no need to worry about escaping category codes.

```

14100 \cs_new_protected:Npn \cctab_gset:Nn #1#2
14101 {
14102     \group_begin:
14103         #2
14104         \luatex_savecatcodetable:D #1
14105     \group_end:
14106 }
14107 \luatex_if_engine:F
14108 {
14109     \cs_set_protected:Npn \cctab_gset:Nn #1#2
14110     {
14111         \__msg_kernel_error:nxxx { kernel } { bad-engine }
14112         { \exp_not:N \cctab_gset:Nn } { #1 {#2} }
14113 }
```

14114 }

(End definition for `\cctab_gset:Nn` This function is documented on page 182.)

`\c_code_cctab` Creating category code tables is easy using the function above. The `other` and `string` ones are done by completely ignoring the existing codes as this makes life a lot less complex. The table for `expl3` category codes is always needed, whereas when in package mode the rest can be copied from the existing L^AT_EX 2_< package `luatex`.

`\c_document_cctab`

`\c_initex_cctab`

`\c_other_cctab`

`\c_str_cctab`

```
14115 \luatex_if_engine:T
14116 {
14117   \cctab_new:N \c_code_cctab
14118   \cctab_gset:Nn \c_code_cctab { }
14119 }
14120 {*package}
14121 \luatex_if_engine:T
14122 {
14123   \cs_new_eq:NN \c_document_cctab \CatcodeTableLaTeX
14124   \cs_new_eq:NN \c_initex_cctab \CatcodeTableInitTeX
14125   \cs_new_eq:NN \c_other_cctab \CatcodeTableOther
14126   \cs_new_eq:NN \c_str_cctab \CatcodeTableString
14127 }
14128 {*} /package
14129 {*initex}
14130 \luatex_if_engine:T
14131 {
14132   \cctab_new:N \c_document_cctab
14133   \cctab_new:N \c_other_cctab
14134   \cctab_new:N \c_str_cctab
14135   \cctab_gset:Nn \c_document_cctab
14136   {
14137     \char_set_catcode_space:n { 9 }
14138     \char_set_catcode_space:n { 32 }
14139     \char_set_catcode_other:n { 58 }
14140     \char_set_catcode_math_subscript:n { 95 }
14141     \char_set_catcode_active:n { 126 }
14142   }
14143   \cctab_gset:Nn \c_other_cctab
14144   {
14145     \int_step_inline:nnnn { 0 } { 1 } { 127 }
14146       { \char_set_catcode_other:n {#1} }
14147   }
14148   \cctab_gset:Nn \c_str_cctab
14149   {
14150     \int_step_inline:nnnn { 0 } { 1 } { 127 }
14151       { \char_set_catcode_other:n {#1} }
14152     \char_set_catcode_space:n { 32 }
14153   }
14154 }
```

(End definition for `\c_code_cctab` This function is documented on page 183.)

40.2 Messages

```
14156 \__msg_kernel_new:nnnn { kernel } { bad-engine }
14157   { LuaTeX~engine-not-in-use!~Ignoring~#1. }
14158   {
14159     The~feature~you~are~using~is~only~available~
14160     with~the~LuaTeX~engine.~LaTeX3~ignored~‘#1#2’.
14161   }
14162 \__msg_kernel_new:nnnn { kernel } { cctab-stack-full }
14163   { The~category~code~table~stack~is~exhausted. }
14164   {
14165     LaTeX~has~been~asked~to~switch~to~a~new~category~code~table,~
14166     but~there~is~no~more~space~to~do~this!
14167 }
```

40.3 Deprecated functions

Deprecated 2011-12-21, for removal by 2012-03-31.

```
\c_string_cctab
14168  {*deprecated}
14169  \cs_new_eq:NN \c_string_cctab \c_str_cctab
14170  {/deprecated}
(End definition for \c_string_cctab This variable is documented on page ??.)
14171  {/initex | package}
```

41 l3candidates Implementation

```
14172  {*initex | package}
14173  {*package}
14174  \ProvidesExplPackage
14175    {\ExplFileName}{\ExplFileVersion}{\ExplFileDescription}
14176  \__expl_package_check:
14177  {/package}
```

41.1 Additions to l3box

```
14178  (@=box)
```

41.2 Affine transformations

\l_box_angle_fp When rotating boxes, the angle itself may be needed by the engine-dependent code. This is done using the fp module so that the value is tidied up properly.

```
14179 \fp_new:N \l_box_angle_fp
(End definition for \l_box_angle_fp This variable is documented on page 186.)
```

\l_box_cos_fp These are used to hold the calculated sine and cosine values while carrying out a rotation.

```
\l_box_sin_fp
14180 \fp_new:N \l_box_cos_fp
14181 \fp_new:N \l_box_sin_fp
```

(End definition for `\l_box_cos_fp` and `\l_box_sin_fp` These variables are documented on page 186.)

`\l_box_top_dim` These are the positions of the four edges of a box before manipulation.
`\l_box_bottom_dim`
`\l_box_left_dim`
`\l_box_right_dim`

14182 `\dim_new:N \l_box_top_dim`
14183 `\dim_new:N \l_box_bottom_dim`
14184 `\dim_new:N \l_box_left_dim`
14185 `\dim_new:N \l_box_right_dim`

(End definition for `\l_box_top_dim` and others. These variables are documented on page ??.)

`\l_box_top_new_dim` These are the positions of the four edges of a box after manipulation.
`\l_box_bottom_new_dim`
`\l_box_left_new_dim`
`\l_box_right_new_dim`

14186 `\dim_new:N \l_box_top_new_dim`
14187 `\dim_new:N \l_box_bottom_new_dim`
14188 `\dim_new:N \l_box_left_new_dim`
14189 `\dim_new:N \l_box_right_new_dim`

(End definition for `\l_box_top_new_dim` and others. These variables are documented on page ??.)

`\l_box_internal_box` Scratch space, but also needed by some parts of the driver.

14190 `\box_new:N \l_box_internal_box`

(End definition for `\l_box_internal_box` This variable is documented on page 186.)

`\box_rotate:Nn`
`_box_rotate:N`
`_box_rotate_x:nnN`
`_box_rotate_y:nnN`
`_box_rotate_quadrant_one:`
`_box_rotate_quadrant_two:`
`_box_rotate_quadrant_three:`
`_box_rotate_quadrant_four:`

Rotation of a box starts with working out the relevant sine and cosine. The actual rotation is in an auxiliary to keep the flow slightly clearer

14191 `\cs_new_protected:Npn \box_rotate:Nn #1#2`
14192 `{`
14193 `\hbox_set:Nn #1`
14194 `{`
14195 `\group_begin:`
14196 `\fp_set:Nn \l_box_angle_fp {#2}`
14197 `\fp_set:Nn \l_box_sin_fp { sin (\l_box_angle_fp * deg) }`
14198 `\fp_set:Nn \l_box_cos_fp { cos (\l_box_angle_fp * deg) }`
14199 `\l_box_rotate:N #1`
14200 `\group_end:`
14201 `}`
14202 `}`

The edges of the box are then recorded: the left edge will always be at zero. Rotation of the four edges then takes place: this is most efficiently done on a quadrant by quadrant basis.

14203 `\cs_new_protected:Npn _box_rotate:N #1`
14204 `{`
14205 `\dim_set:Nn \l_box_top_dim { \box_ht:N #1 }`
14206 `\dim_set:Nn \l_box_bottom_dim { -\box_dp:N #1 }`
14207 `\dim_set:Nn \l_box_right_dim { \box_wd:N #1 }`
14208 `\dim_zero:N \l_box_left_dim`




Figure 1: Co-ordinates of a box prior to rotation.

The next step is to work out the x and y coordinates of vertices of the rotated box in relation to its original coordinates. The box can be visualized with vertices B , C , D and E is illustrated (Figure 1). The vertex O is the reference point on the baseline, and in this implementation is also the centre of rotation. The formulae are, for a point P and angle α :

$$\begin{aligned} P'_x &= P_x - O_x \\ P'_y &= P_y - O_y \\ P''_x &= (P'_x \cos(\alpha)) - (P'_y \sin(\alpha)) \\ P''_y &= (P'_x \sin(\alpha)) + (P'_y \cos(\alpha)) \\ P'''_x &= P''_x + O_x + L_x \\ P'''_y &= P''_y + O_y \end{aligned}$$

The “extra” horizontal translation L_x at the end is calculated so that the leftmost point of the resulting box has x -coordinate 0. This is desirable as TeX boxes must have the reference point at the left edge of the box. (As O is always $(0,0)$, this part of the calculation is omitted here.)

```

14209 \fp_compare:nNnTF \l__box_sin_fp > \c_zero_fp
14210 {
14211   \fp_compare:nNnTF \l__box_cos_fp > \c_zero_fp
14212   { \__box_rotate_quadrant_one: }
14213   { \__box_rotate_quadrant_two: }
14214 }
14215 {
14216   \fp_compare:nNnTF \l__box_cos_fp < \c_zero_fp
14217   { \__box_rotate_quadrant_three: }
14218   { \__box_rotate_quadrant_four: }
14219 }
```

The position of the box edges are now known, but the box at this stage be misplaced relative to the current TeX reference point. So the content of the box is moved such that the reference point of the rotated box will be in the same place as the original.

```

14220 \hbox_set:Nn \l__box_internal_box { \box_use:N #1 }
14221 \hbox_set:Nn \l__box_internal_box
14222 {
14223   \tex_kern:D -\l__box_left_new_dim
```

```

14224     \hbox:n
14225     {
14226         \__driver_box_rotate_begin:
14227         \box_use:N \l__box_internal_box
14228         \__driver_box_rotate_end:
14229     }
14230 }
```

Tidy up the size of the box so that the material is actually inside the bounding box. The result can then be used to reset the original box.

```

14231     \box_set_ht:Nn \l__box_internal_box { \l__box_top_new_dim }
14232     \box_set_dp:Nn \l__box_internal_box { -\l__box_bottom_new_dim }
14233     \box_set_wd:Nn \l__box_internal_box
14234     { \l__box_right_new_dim - \l__box_left_new_dim }
14235     \box_use:N \l__box_internal_box
14236 }
```

These functions take a general point (#1,#2) and rotate its location about the origin, using the previously-set sine and cosine values. Each function gives only one component of the location of the updated point. This is because for rotation of a box each step needs only one value, and so performance is gained by avoiding working out both x' and y' at the same time. Contrast this with the equivalent function in the `l3coffins` module, where both parts are needed.

```

14237 \cs_new_protected:Npn \__box_rotate_x:nnN #1#2#3
14238 {
14239     \dim_set:Nn #3
14240     {
14241         \fp_to_dim:n
14242         {
14243             \l__box_cos_fp * \dim_to_fp:n {#1}
14244             - ( \l__box_sin_fp * \dim_to_fp:n {#2} )
14245         }
14246     }
14247 }
14248 \cs_new_protected:Npn \__box_rotate_y:nnN #1#2#3
14249 {
14250     \dim_set:Nn #3
14251     {
14252         \fp_to_dim:n
14253         {
14254             \l__box_sin_fp * \dim_to_fp:n {#1}
14255             + \l__box_cos_fp * \dim_to_fp:n {#2}
14256         }
14257     }
14258 }
```

Rotation of the edges is done using a different formula for each quadrant. In every case, the top and bottom edges only need the resulting y -values, whereas the left and right edges need the x -values. Each case is a question of picking out which corner ends up at

with the maximum top, bottom, left and right value. Doing this by hand means a lot less calculating and avoids lots of comparisons.

```

14259 \cs_new_protected:Npn \__box_rotate_quadrant_one:
14260 {
14261   \__box_rotate_y:nnN \l_box_right_dim \l_box_top_dim
14262     \l_box_top_new_dim
14263   \__box_rotate_y:nnN \l_box_left_dim \l_box_bottom_dim
14264     \l_box_bottom_new_dim
14265   \__box_rotate_x:nnN \l_box_left_dim \l_box_top_dim
14266     \l_box_left_new_dim
14267   \__box_rotate_x:nnN \l_box_right_dim \l_box_bottom_dim
14268     \l_box_right_new_dim
14269 }
14270 \cs_new_protected:Npn \__box_rotate_quadrant_two:
14271 {
14272   \__box_rotate_y:nnN \l_box_right_dim \l_box_bottom_dim
14273     \l_box_top_new_dim
14274   \__box_rotate_y:nnN \l_box_left_dim \l_box_top_dim
14275     \l_box_bottom_new_dim
14276   \__box_rotate_x:nnN \l_box_right_dim \l_box_top_dim
14277     \l_box_left_new_dim
14278   \__box_rotate_x:nnN \l_box_left_dim \l_box_bottom_dim
14279     \l_box_right_new_dim
14280 }
14281 \cs_new_protected:Npn \__box_rotate_quadrant_three:
14282 {
14283   \__box_rotate_y:nnN \l_box_left_dim \l_box_bottom_dim
14284     \l_box_top_new_dim
14285   \__box_rotate_y:nnN \l_box_right_dim \l_box_top_dim
14286     \l_box_bottom_new_dim
14287   \__box_rotate_x:nnN \l_box_right_dim \l_box_bottom_dim
14288     \l_box_left_new_dim
14289   \__box_rotate_x:nnN \l_box_left_dim \l_box_top_dim
14290     \l_box_right_new_dim
14291 }
14292 \cs_new_protected:Npn \__box_rotate_quadrant_four:
14293 {
14294   \__box_rotate_y:nnN \l_box_left_dim \l_box_top_dim
14295     \l_box_top_new_dim
14296   \__box_rotate_y:nnN \l_box_right_dim \l_box_bottom_dim
14297     \l_box_bottom_new_dim
14298   \__box_rotate_x:nnN \l_box_left_dim \l_box_bottom_dim
14299     \l_box_left_new_dim
14300   \__box_rotate_x:nnN \l_box_right_dim \l_box_top_dim
14301     \l_box_right_new_dim
14302 }

(End definition for \box_rotate:Nn This function is documented on page 185.)
```

\l_box_scale_x_fp Scaling is potentially-different in the two axes.
\l_box_scale_y_fp

```

14303 \fp_new:N \l__box_scale_x_fp
14304 \fp_new:N \l__box_scale_y_fp
(End definition for \l__box_scale_x_fp and \l__box_scale_y_fp These variables are documented on
page 186.)

```

\box_resize:Nnn

\box_resize:cnn

_box_resize:Nnn

Resizing a box starts by working out the various dimensions of the existing box.

```

14305 \cs_new_protected:Npn \box_resize:Nnn #1#2#3
14306 {
14307     \hbox_set:Nn #1
14308     {
14309         \group_begin:
14310             \dim_set:Nn \l__box_top_dim { \box_ht:N #1 }
14311             \dim_set:Nn \l__box_bottom_dim { -\box_dp:N #1 }
14312             \dim_set:Nn \l__box_right_dim { \box_wd:N #1 }
14313             \dim_zero:N \l__box_left_dim

```

The *x*-scaling and resulting box size is easy enough to work out: the dimension is that given as #2, and the scale is simply the new width divided by the old one.

```

14314     \fp_set:Nn \l__box_scale_x_fp
14315         { \dim_to_fp:n {#2} / ( \dim_to_fp:n \l__box_right_dim ) }

```

The *y*-scaling needs both the height and the depth of the current box.

```

14316     \fp_set:Nn \l__box_scale_y_fp
14317     {
14318         \dim_to_fp:n {#3} /
14319             ( \dim_to_fp:n { \l__box_top_dim - \l__box_bottom_dim } )
14320     }

```

Hand off to the auxiliary which does the work.

```

14321     \_box_resize:Nnn #1 {#2} {#3}
14322     \group_end:
14323     }
14324 }
14325 \cs_generate_variant:Nn \box_resize:Nnn { c }

```

With at least one real scaling to do, the next phase is to find the new edge co-ordinates. In the *x* direction this is relatively easy: just scale the right edge. This is done using the absolute value of the scale so that the new edge is in the correct place. In the *y* direction, both dimensions have to be scaled, and this again needs the absolute scale value. Once that is all done, the common resize/rescale code can be employed.

```

14326 \cs_new_protected:Npn \_box_resize:Nnn #1#2#3
14327 {
14328     \dim_set:Nn \l__box_right_new_dim { \dim_abs:n {#2} }
14329     \dim_set:Nn \l__box_bottom_new_dim
14330         { \fp_abs:n { \l__box_scale_y_fp } \l__box_bottom_dim }
14331     \dim_set:Nn \l__box_top_new_dim
14332         { \fp_abs:n { \l__box_scale_y_fp } \l__box_top_dim }
14333     \_box_resize_common:N #
14334 }

```

(End definition for \box_resize:Nnn and \box_resize:cnn These functions are documented on page ??.)

```
\box_resize_to_ht_plus_dp:Nn
\box_resize_to_ht_plus_dp:cn
  \box_resize_to_wd:Nn
    \box_resize_to_wd:cn
```

Scaling to a total height or to a width is a simplified version of the main resizing operation, with the scale simply copied between the two parts. The internal auxiliary is called using the scaling value twice, as the sign for both parts is needed (as this allows the same internal code to be used as for the general case).

```
14335 \cs_new_protected:Npn \box_resize_to_ht_plus_dp:Nn #1#2
14336 {
14337   \hbox_set:Nn #1
14338   {
14339     \group_begin:
14340       \dim_set:Nn \l__box_top_dim { \box_ht:N #1 }
14341       \dim_set:Nn \l__box_bottom_dim { -\box_dp:N #1 }
14342       \dim_set:Nn \l__box_right_dim { \box_wd:N #1 }
14343       \dim_zero:N \l__box_left_dim
14344       \fp_set:Nn \l__box_scale_y_fp
14345       {
14346         \dim_to_fp:n {#2} /
14347           ( \dim_to_fp:n { \l__box_top_dim - \l__box_bottom_dim } )
14348       }
14349       \fp_set_eq:NN \l__box_scale_x_fp \l__box_scale_y_fp
14350       \l__box_resize:Nnn #1 {#2} {#2}
14351     \group_end:
14352   }
14353 }
14354 \cs_generate_variant:Nn \box_resize_to_ht_plus_dp:Nn { c }
14355 \cs_new_protected:Npn \box_resize_to_wd:Nn #1#2
14356 {
14357   \hbox_set:Nn #1
14358   {
14359     \group_begin:
14360       \dim_set:Nn \l__box_top_dim { \box_ht:N #1 }
14361       \dim_set:Nn \l__box_bottom_dim { -\box_dp:N #1 }
14362       \dim_set:Nn \l__box_right_dim { \box_wd:N #1 }
14363       \dim_zero:N \l__box_left_dim
14364       \fp_set:Nn \l__box_scale_x_fp
14365       { \dim_to_fp:n {#2} / ( \dim_to_fp:n \l__box_right_dim ) }
14366       \fp_set_eq:NN \l__box_scale_y_fp \l__box_scale_x_fp
14367       \l__box_resize:Nnn #1 {#2} {#2}
14368     \group_end:
14369   }
14370 }
14371 \cs_generate_variant:Nn \box_resize_to_wd:Nn { c }
(End definition for \box_resize_to_ht_plus_dp:Nn and \box_resize_to_ht_plus_dp:cn These functions are documented on page ??.)
```

```
\box_scale:Nnn
\box_scale:cnn
```

When scaling a box, setting the scaling itself is easy enough. The new dimensions are also relatively easy to find, allowing only for the need to keep them positive in all cases. Once that is done then after a check for the trivial scaling a hand-off can be made to the common code. The dimension scaling operations are carried out using the TEX mechanism as it avoids needing to use too many fp operations.

```

14372 \cs_new_protected:Npn \box_scale:Nnn #1#2#3
14373 {
14374   \hbox_set:Nn #1
14375   {
14376     \group_begin:
14377       \fp_set:Nn \l__box_scale_x_fp {#2}
14378       \fp_set:Nn \l__box_scale_y_fp {#3}
14379       \dim_set:Nn \l__box_top_dim { \box_ht:N #1 }
14380       \dim_set:Nn \l__box_bottom_dim { -\box_dp:N #1 }
14381       \dim_set:Nn \l__box_right_dim { \box_wd:N #1 }
14382       \dim_zero:N \l__box_left_dim
14383       \dim_set:Nn \l__box_top_new_dim
14384         { \fp_abs:n { \l__box_scale_y_fp } \l__box_top_dim }
14385       \dim_set:Nn \l__box_bottom_new_dim
14386         { \fp_abs:n { \l__box_scale_y_fp } \l__box_bottom_dim }
14387       \dim_set:Nn \l__box_right_new_dim
14388         { \fp_abs:n { \l__box_scale_x_fp } \l__box_right_dim }
14389       \__box_resize_common:N #1
14390     \group_end:
14391   }
14392 }
14393 \cs_generate_variant:Nn \box_scale:Nnn { c }
(End definition for \box_scale:Nnn and \box_scale:cnn These functions are documented on page ??.)
```

__box_resize_common:N The main resize function places in input into a box which will start of with zero width, and includes the handles for engine rescaling.

```

14394 \cs_new_protected:Npn \__box_resize_common:N #
14395 {
14396   \hbox_set:Nn \l__box_internal_box
14397   {
14398     \__driver_box_scale_begin:
14399     \hbox_overlap_right:n { \box_use:N #1 }
14400     \__driver_box_scale_end:
14401   }
```

The new height and depth can be applied directly.

```

14402   \box_set_ht:Nn \l__box_internal_box { \l__box_top_new_dim }
14403   \box_set_dp:Nn \l__box_internal_box { \l__box_bottom_new_dim }
```

Things are not quite as obvious for the width, as the reference point needs to remain unchanged. For positive scaling factors resizing the box is all that is needed. However, for case of a negative scaling the material must be shifted such that the reference point ends up in the right place.

```

14404   \fp_compare:nNnTF \l__box_scale_x_fp < \c_zero_fp
14405   {
14406     \hbox_to_wd:nn { \l__box_right_new_dim }
14407     {
14408       \tex_kern:D \l__box_right_new_dim
14409       \box_use:N \l__box_internal_box
14410       \tex_hss:D
```

```

14411         }
14412     }
14413     {
14414         \box_set_wd:Nn \l__box_internal_box { \l__box_right_new_dim }
14415         \box_use:N \l__box_internal_box
14416     }
14417 }
(End definition for \__box_resize_common:N)

```

41.3 Viewing part of a box

\box_clip:N A wrapper around the driver-dependent code.

```

14418 \cs_new_protected:Npn \box_clip:N #1
14419   { \hbox_set:Nn #1 { \__driver_box_use_clip:N #1 } }
14420 \cs_generate_variant:Nn \box_clip:N { c }
(End definition for \box_clip:N and \box_clip:c These functions are documented on page ??.)

```

\box_trim:Nnnnn Trimming from the left- and right-hand edges of the box is easy. The total width is set to remove from the right, and a skip will shift the material to remove from the left.

```

14421 \cs_new_protected:Npn \box_trim:Nnnnn #1#2#3#4#5
14422   {
14423     \box_set_wd:Nn #1 { \box_wd:N #1 - (#4) - (#2) }
14424     \hbox_set:Nn #1
14425     {
14426       \skip_horizontal:n { - \dim_eval:n {#2} }
14427       \box_use:N #1
14428     }

```

For the height and depth, there is a need to watch the baseline is respected. Material always has to stay on the correct side, so trimming has to check that there is enough material to trim.

```

14429 \dim_compare:nNnTF { \box_dp:N #1 } > {#3}
14430   { \box_set_dp:Nn #1 { \box_dp:N #1 - (#3) } }
14431   {
14432     \hbox_set:Nn #1
14433       { \box_move_down:nn { #3 - \box_dp:N #1 } { \box_use:N #1 } }
14434     \box_set_dp:Nn #1 \c_zero_dim
14435   }
14436 \dim_compare:nNnTF { \box_ht:N #1 } > {#5}
14437   { \box_set_ht:Nn #1 { \box_ht:N #1 - (#5) } }
14438   {
14439     \hbox_set:Nn #1
14440       { \box_move_up:nn { #5 - \box_ht:N #1 } { \box_use:N #1 } }
14441     \box_set_ht:Nn #1 \c_zero_dim
14442   }
14443 }
14444 \cs_generate_variant:Nn \box_trim:Nnnnn { c }
(End definition for \box_trim:Nnnnn and \box_trim:cnnnn These functions are documented on page ??.)

```

\box_viewport:Nnnnn
\box_viewport:cnnnn

The same general logic as for clipping, but with absolute dimensions. Thus again width is easy and height is harder.

```

14445 \cs_new_protected:Npn \box_viewport:Nnnnn #1#2#3#4#5
14446 {
14447   \box_set_wd:Nn #1 { (#4) - (#2) }
14448   \hbox_set:Nn #1
14449   {
14450     \skip_horizontal:n { - \dim_eval:n {#2} }
14451     \box_use:N #1
14452   }
14453   \dim_compare:nNnTF {#3} > \c_zero_dim
14454   {
14455     \hbox_set:Nn #1 { \box_move_down:nn {#3} { \box_use:N #1 } }
14456     \box_set_dp:Nn #1 \c_zero_dim
14457   }
14458   { \box_set_dp:Nn #1 { - \dim_eval:n {#3} } }
14459   \dim_compare:nNnTF {#5} > \c_zero_dim
14460   { \box_set_ht:Nn #1 {#5} }
14461   {
14462     \hbox_set:Nn #1
14463     { \box_move_up:nn { -\dim_eval:n {#5} } { \box_use:N #1 } }
14464     \box_set_ht:Nn #1 \c_zero_dim
14465   }
14466 }
14467 \cs_generate_variant:Nn \box_viewport:Nnnnn { c }
(End definition for \box_viewport:Nnnnn and \box_viewport:cnnnn These functions are documented on
page ??.)
```

41.4 Additions to **I3clist**

14468 ⟨@=clist⟩

\clist_item:Nn
\clist_item:cn
_clist_item:nnNn
_clist_item_N_loop:nw

To avoid needing to test the end of the list at each step, we first compute the $\langle length \rangle$ of the list. If the item number is 0, less than $-\langle length \rangle$, or more than $\langle length \rangle$, the result is empty. If it is negative, but not less than $-\langle length \rangle$, add $\langle length \rangle + 1$ to the item number before performing the loop. The loop itself is very simple, return the item if the counter reached 1, otherwise, decrease the counter and repeat.

```

14469 \cs_new:Npn \clist_item:Nn #1#2
14470 {
14471   \exp_args:Nfo \_clist_item:nnNn
14472   { \clist_count:N #1 }
14473   #1
14474   \_clist_item_N_loop:nw
14475   {#2}
14476 }
14477 \cs_new:Npn \_clist_item:nnNn #1#2#3#4
14478 {
14479   \int_compare:nNnTF {#4} < \c_zero
14480 }
```

```

14481   \int_compare:nNnTF {#4} < { - #1 }
14482     { \use_none_delimit_by_q_stop:w }
14483     { \exp_args:Nf #3 { \int_eval:n { #4 + \c_one + #1 } } }
14484   }
14485   {
14486     \int_compare:nNnTF {#4} > {#1}
14487       { \use_none_delimit_by_q_stop:w }
14488       { #3 {#4} }
14489     }
14490   { } , #2 , \q_stop
14491 }
14492 \cs_new:Npn \__clist_item_N_loop:nw #1 #2,
14493 {
14494   \int_compare:nNnTF {#1} = \c_zero
14495     { \use_i_delimit_by_q_stop:nw { \exp_not:n {#2} } }
14496     { \exp_args:Nf \__clist_item_N_loop:nw { \int_eval:n { #1 - 1 } } }
14497   }
14498 \cs_generate_variant:Nn \clist_item:Nn { c }
(End definition for \clist_item:Nn and \clist_item:cn These functions are documented on page ??.)
```

```
\clist_item:nn
\__clist_item_n:nw
\__clist_item_n_loop:nw
\__clist_item_n_end:n
\__clist_item_n_strip:w
```

This starts in the same way as \clist_item:Nn by counting the items of the comma list. The final item should be space-trimmed before being brace-stripped, hence we insert a couple of odd-looking \prg_do_nothing: to avoid losing braces. Blank items are ignored.

```

14499 \cs_new:Npn \clist_item:nn #1#2
14500 {
14501   \exp_args:Nf \__clist_item:nnNn
14502     { \clist_count:n {#1} }
14503     {#1}
14504     \__clist_item_n:nw
14505     {#2}
14506   }
14507 \cs_new:Npn \__clist_item_n:nw #1
14508   { \__clist_item_n_loop:nw {#1} \prg_do_nothing: }
14509 \cs_new:Npn \__clist_item_n_loop:nw #1 #2,
14510 {
14511   \exp_args:No \tl_if_blank:nTF {#2}
14512     { \__clist_item_n_loop:nw {#1} \prg_do_nothing: }
14513   {
14514     \int_compare:nNnTF {#1} = \c_zero
14515       { \exp_args:No \__clist_item_n_end:n {#2} }
14516       {
14517         \exp_args:Nf \__clist_item_n_loop:nw
14518           { \int_eval:n { #1 - 1 } }
14519         \prg_do_nothing:
14520       }
14521   }
14522 }
14523 \cs_new:Npn \__clist_item_n_end:n #1 #2 \q_stop
14524 {
```

```

14525   \__tl_trim_spaces:nn { \q_mark #1 }
14526   { \exp_last_unbraced:Nn \__clist_item_n_strip:w } ,
14527 }
14528 \cs_new:Npn \__clist_item_n_strip:w #1 , { \exp_not:n {#1} }
(End definition for \clist_item:nn This function is documented on page ??.)
```

\clist_set_from_seq:NN
\clist_set_from_seq:cN
\clist_set_from_seq:Nc
\clist_set_from_seq:cc

\clist_gset_from_seq:NN
\clist_gset_from_seq:cN
\clist_gset_from_seq:Nc
\clist_gset_from_seq:cc
__clist_set_from_seq:NNNN
 __clist_wrap_item:n
__clist_set_from_seq:w

Setting a comma list from a comma-separated list is done using a simple mapping. We wrap most items with \exp_not:n, and a comma. Items which contain a comma or a space are surrounded by an extra set of braces. The first comma must be removed, except in the case of an empty comma-list.

```

14529 \cs_new_protected:Npn \clist_set_from_seq:NN
14530 { \__clist_set_from_seq:NNNN \clist_clear:N \tl_set:Nx }
14531 \cs_new_protected:Npn \clist_gset_from_seq:NN
14532 { \__clist_set_from_seq:NNNN \clist_gclear:N \tl_gset:Nx }
14533 \cs_new_protected:Npn \__clist_set_from_seq:NNNN #1#2#3#4
14534 {
14535     \seq_if_empty:NTF #4
14536     { #1 #3 }
14537     {
14538         #2 #3
14539         {
14540             \exp_last_unbraced:Nf \use_none:n
14541             { \seq_map_function:NN #4 \__clist_wrap_item:n }
14542         }
14543     }
14544 }
14545 \cs_new:Npn \__clist_wrap_item:n #1
14546 {
14547     ,
14548     \tl_if_empty:oTF { \__clist_set_from_seq:w #1 ~ , #1 ~ }
14549     { \exp_not:n {#1} }
14550     { \exp_not:n { {#1} } }
14551 }
14552 \cs_new:Npn \__clist_set_from_seq:w #1 , #2 ~ { }
14553 \cs_generate_variant:Nn \clist_set_from_seq:NN { Nc }
14554 \cs_generate_variant:Nn \clist_set_from_seq:NN { c , cc }
14555 \cs_generate_variant:Nn \clist_gset_from_seq:NN { Nc }
14556 \cs_generate_variant:Nn \clist_gset_from_seq:NN { c , cc }
(End definition for \clist_set_from_seq:NN and others. These functions are documented on page ??.)
```

\clist_const:Nn
\clist_const:cN
\clist_const:Nx
\clist_const:cx

Creating and initializing a constant comma list is done in a way similar to \clist_set:Nn and \clist_gset:Nn, being careful to strip spaces.

```

14557 \cs_new_protected:Npn \clist_const:Nn #1#2
14558 { \tl_const:Nx #1 { \__clist_trim_spaces:n {#2} } }
14559 \cs_generate_variant:Nn \clist_const:Nn { c , Nx , cx }
(End definition for \clist_const:Nn and others. These functions are documented on page ??.)
```

\clist_if_empty_p:n
\clist_if_empty:nTF
__clist_if_empty_n:w
__clist_if_empty_n:wNw

As usual, we insert a token (here ?) before grabbing any argument: this avoids losing braces. The argument of \tl_if_empty:oTF is empty if #1 is ? followed by blank spaces

(besides, this particular variant of the emptiness test is optimized). If the item of the comma list is blank, grab the next one. As soon as one item is non-blank, exit: the second auxiliary will grab `\prg_return_false:` as #2, unless every item in the comma list was blank and the loop actually got broken by the trailing `\q_mark \prg_return_false:` item.

```

14560 \prg_new_conditional:Npnn \clist_if_empty:n #1 { p , T , F , TF }
14561 {
14562   \__clist_if_empty_n:w ? #1
14563   , \q_mark \prg_return_false:
14564   , \q_mark \prg_return_true:
14565   \q_stop
14566 }
14567 \cs_new:Npn \__clist_if_empty_n:w #1 ,
14568 {
14569   \tl_if_empty:oTF { \use_none:nn #1 ? }
14570   { \__clist_if_empty_n:w ? }
14571   { \__clist_if_empty_n:wNw }
14572 }
14573 \cs_new:Npn \__clist_if_empty_n:wNw #1 \q_mark #2#3 \q_stop {#2}
(End definition for \clist_if_empty:n These functions are documented on page 187.)
```

`\clist_use:Nnnn`

```
\__clist_use:wwn
\__clist_use_i:nnnnnnn
\__clist_use_iii:nnn
```

First check that the variable exists. Then count the items in the comma list. If it has none, output nothing. If it has one item, output that item, brace stripped (note that space-trimming has already been done when the comma list was assigned). If it has two, place the *<separator between two>* in the middle.

Otherwise, `__clist_use_i:nnnnnnn` takes the following arguments; 1: a *<separator>*, 2, 3, 4: three items from the comma list (or quarks), 5: the rest of the comma list, 6: a *<continuation>* function (`use_ii` or `use_iii` with its *<separator>* argument), 7: junk, and 8: the temporary result, which is built in a brace group following `\q_stop`. The *<separator>* and the first of the three items are placed in the result, then we use the *<continuation>*, placing the remaining two items after it. When we begin this loop, the three items really belong to the comma list, the first `\q_mark` is taken as a delimiter to the `use_ii` function, and the continuation is `use_ii` itself. When we reach the last two items of the original token list, `\q_mark` is taken as a third item, and now the seconf `\q_mark` serves as a delimiter to `use_ii`, switching to the other *<continuation>*, `use_iii`, which uses the *<separator between final two>*.

```

14574 \cs_new:Npn \clist_use:Nnnn #1#2#3#4
14575 {
14576   \clist_if_exist:NTF #1
14577   {
14578     \int_case:nnn { \clist_count:N #1 }
14579     {
14580       { 0 } { }
14581       { 1 } { \exp_after:wn \__clist_use:wwn #1 , , { } }
14582       { 2 } { \exp_after:wn \__clist_use:wwn #1 , {#2} }
14583     }
14584   {
14585     \exp_after:wn \__clist_use_ii:nnnnnnn
```

```

14586           \exp_after:wN { \exp_after:wN } #1 ,
14587           \q_mark , { \__clist_use_ii:nwwwnwn {#3} }
14588           \q_mark , { \__clist_use_iii:nwwn {#4} }
14589           \q_stop { }
14590       }
14591   }
14592   { \__msg_kernel_expandable_error:nnn { kernel } { bad-variable } {#1} }
14593 }
14594 \cs_new:Npn \__clist_use:wwn #1 , #2 , #3 { \exp_not:n { #1 #3 #2 } }
14595 \cs_new:Npn \__clist_use_ii:nwwwnwn
14596     #1#2 , #3 , #4 , #5 \q_mark , #6#7 \q_stop #8
14597     { #6 {#3} , {#4} , #5 \q_mark , {#6} #7 \q_stop { #8 #1 #2 } }
14598 \cs_new:Npn \__clist_use_iii:nwwn #1#2 , #3 \q_stop #4
14599     { \exp_not:n { #4 #1 #2 } }

```

(End definition for `\clist_use:Nnnn` This function is documented on page 188.)

41.5 Additions to l3coffins

14600 `<@=coffin>`

41.6 Rotating coffins

`\l__coffin_sin_fp` Used for rotations to get the sine and cosine values.

`\l__coffin_cos_fp`

(End definition for `\l__coffin_sin_fp` This function is documented on page ??.)

`\l__coffin_bounding_prop` A property list for the bounding box of a coffin. This is only needed during the rotation, so there is just the one.

14603 `\prop_new:N \l__coffin_bounding_prop`

(End definition for `\l__coffin_bounding_prop` This variable is documented on page ??.)

`\l__coffin_bounding_shift_dim` The shift of the bounding box of a coffin from the real content.

14604 `\dim_new:N \l__coffin_bounding_shift_dim`

(End definition for `\l__coffin_bounding_shift_dim` This variable is documented on page ??.)

`\l__coffin_left_corner_dim` These are used to hold maxima for the various corner values: these thus define the minimum size of the bounding box after rotation.

`\l__coffin_right_corner_dim`

`\l__coffin_bottom_corner_dim`

`\l__coffin_top_corner_dim`

(End definition for `\l__coffin_left_corner_dim` This function is documented on page ??.)

```
\coffin_rotate:Nn  
\coffin_rotate:cn
```

Rotating a coffin requires several steps which can be conveniently run together. The first step is to convert the angle given in degrees to one in radians. This is then used to set `\l_coffin_sin_fp` and `\l_coffin_cos_fp`, which are carried through unchanged for the rest of the procedure.

```
14609 \cs_new_protected:Npn \coffin_rotate:Nn #1#2  
14610 {  
14611   \fp_set:Nn \l_coffin_sin_fp { sin ( ( #2 ) * deg ) }  
14612   \fp_set:Nn \l_coffin_cos_fp { cos ( ( #2 ) * deg ) }
```

The corners and poles of the coffin can now be rotated around the origin. This is best achieved using mapping functions.

```
14613 \prop_map_inline:cn { l_coffin_corners_ \__int_value:w #1 _prop }  
14614   { \__coffin_rotate_corner:Nnnn #1 {##1} ##2 }  
14615 \prop_map_inline:cn { l_coffin_poles_ \__int_value:w #1 _prop }  
14616   { \__coffin_rotate_pole:Nnnnn #1 {##1} ##2 }
```

The bounding box of the coffin needs to be rotated, and to do this the corners have to be found first. They are then rotated in the same way as the corners of the coffin material itself.

```
14617 \__coffin_set_bounding:N #1  
14618 \prop_map_inline:Nn \l_coffin_bounding_prop  
14619   { \__coffin_rotate_bounding:nnn {##1} ##2 }
```

At this stage, there needs to be a calculation to find where the corners of the content and the box itself will end up.

```
14620 \__coffin_find_corner_maxima:N #1  
14621 \__coffin_find_bounding_shift:  
14622 \box_rotate:Nn #1 {#2}
```

The correction of the box position itself takes place here. The idea is that the bounding box for a coffin is tight up to the content, and has the reference point at the bottom-left. The *x*-direction is handled by moving the content by the difference in the positions of the bounding box and the content left edge. The *y*-direction is dealt with by moving the box down by any depth it has acquired.

```
14623 \hbox_set:Nn #1  
14624 {  
14625   \tex_kern:D \l_coffin_bounding_shift_dim  
14626   \tex_kern:D -\l_coffin_left_corner_dim  
14627   \box_move_down:nn { \l_coffin_bottom_corner_dim }  
14628     { \box_use:N #1 }  
14629 }
```

If there have been any previous rotations then the size of the bounding box will be bigger than the contents. This can be corrected easily by setting the size of the box to the height and width of the content.

```
14630 \box_set_ht:Nn #1  
14631   { \l_coffin_top_corner_dim - \l_coffin_bottom_corner_dim }  
14632 \box_set_dp:Nn #1 { 0 pt }  
14633 \box_set_wd:Nn #1  
14634   { \l_coffin_right_corner_dim - \l_coffin_left_corner_dim }
```

The final task is to move the poles and corners such that they are back in alignment with the box reference point.

```

14635   \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
14636     { \__coffin_shift_corner:Nnnn #1 {##1} ##2 }
14637   \prop_map_inline:cn { l__coffin_poles_ \__int_value:w #1 _prop }
14638     { \__coffin_shift_pole:Nnnnnn #1 {##1} ##2 }
14639   }
14640 \cs_generate_variant:Nn \coffin_rotate:Nn { c }
(End definition for \coffin_rotate:Nn and \coffin_rotate:cn These functions are documented on page ??.)

```

__coffin_set_bounding:N The bounding box corners for a coffin are easy enough to find: this is the same code as for the corners of the material itself, but using a dedicated property list.

```

14641 \cs_new_protected:Npn \__coffin_set_bounding:N #1
14642 {
14643   \prop_put:Nnx \l__coffin_bounding_prop { tl }
14644     { { 0 pt } { \dim_use:N \box_ht:N #1 } }
14645   \prop_put:Nnx \l__coffin_bounding_prop { tr }
14646     { { \dim_use:N \box_wd:N #1 } { \dim_use:N \box_ht:N #1 } }
14647   \dim_set:Nn \l__coffin_internal_dim { - \box_dp:N #1 }
14648   \prop_put:Nnx \l__coffin_bounding_prop { bl }
14649     { { 0 pt } { \dim_use:N \l__coffin_internal_dim } }
14650   \prop_put:Nnx \l__coffin_bounding_prop { br }
14651     { { \dim_use:N \box_wd:N #1 } { \dim_use:N \l__coffin_internal_dim } }
14652 }
(End definition for \__coffin_set_bounding:N This function is documented on page ??.)

```

__coffin_rotate_bounding:nnn Rotating the position of the corner of the coffin is just a case of treating this as a vector from the reference point. The same treatment is used for the corners of the material itself and the bounding box.

```

14653 \cs_new_protected:Npn \__coffin_rotate_bounding:nnn #1#2#3
14654 {
14655   \__coffin_rotate_vector:nnNN {#2} {#3} \l__coffin_x_dim \l__coffin_y_dim
14656   \prop_put:Nnx \l__coffin_bounding_prop {#1}
14657     { { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim } }
14658 }
14659 \cs_new_protected:Npn \__coffin_rotate_corner:Nnnn #1#2#3#4
14660 {
14661   \__coffin_rotate_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
14662   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } {#2}
14663     { { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim } }
14664 }
(End definition for \__coffin_rotate_bounding:nnn This function is documented on page ??.)

```

__coffin_rotate_pole:Nnnnnn Rotating a single pole simply means shifting the co-ordinate of the pole and its direction. The rotation here is about the bottom-left corner of the coffin.

```

14665 \cs_new_protected:Npn \__coffin_rotate_pole:Nnnnnn #1#2#3#4#5#6
14666 {

```

```

14667   \__coffin_rotate_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
14668   \__coffin_rotate_vector:nnNN {#5} {#6}
14669     \l__coffin_x_prime_dim \l__coffin_y_prime_dim
14670   \__coffin_set_pole:Nnx #1 {#2}
14671   {
14672     { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
14673     { \dim_use:N \l__coffin_x_prime_dim }
14674     { \dim_use:N \l__coffin_y_prime_dim }
14675   }
14676 }
14677
(End definition for \__coffin_rotate_pole:Nnnnnn This function is documented on page ??.)
```

`__coffin_rotate_vector:nnNN` A rotation function, which needs only an input vector (as dimensions) and an output space. The values `\l__coffin_cos_fp` and `\l__coffin_sin_fp` should previously have been set up correctly. Working this way means that the floating point work is kept to a minimum: for any given rotation the sin and cosine values do no change, after all.

```

14677 \cs_new_protected:Npn \__coffin_rotate_vector:nnNN #1#2#3#4
14678 {
14679   \dim_set:Nn #3
14680   {
14681     \fp_to_dim:n
14682     {
14683       \dim_to_fp:n {#1} * \l__coffin_cos_fp
14684       - ( \dim_to_fp:n {#2} * \l__coffin_sin_fp )
14685     }
14686   }
14687   \dim_set:Nn #4
14688   {
14689     \fp_to_dim:n
14690     {
14691       \dim_to_fp:n {#1} * \l__coffin_sin_fp
14692       + ( \dim_to_fp:n {#2} * \l__coffin_cos_fp )
14693     }
14694   }
14695 }
```

(End definition for __coffin_rotate_vector:nnNN This function is documented on page ??.)

`__coffin_find_corner_maxima:N` The idea here is to find the extremities of the content of the coffin. This is done by looking for the smallest values for the bottom and left corners, and the largest values for the top and right corners. The values start at the maximum dimensions so that the case where all are positive or all are negative works out correctly.

```

14696 \cs_new_protected:Npn \__coffin_find_corner_maxima:N #1
14697 {
14698   \dim_set:Nn \l__coffin_top_corner_dim { -\c_max_dim }
14699   \dim_set:Nn \l__coffin_right_corner_dim { -\c_max_dim }
14700   \dim_set:Nn \l__coffin_bottom_corner_dim { \c_max_dim }
14701   \dim_set:Nn \l__coffin_left_corner_dim { \c_max_dim }
14702   \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
14703   { \__coffin_find_corner_maxima_aux:nn ##2 }
```

```

14704   }
14705 \cs_new_protected:Npn \__coffin_find_corner_maxima_aux:nn #1#2
14706 {
14707   \dim_set:Nn \l__coffin_left_corner_dim
14708   { \dim_min:nn { \l__coffin_left_corner_dim } {#1} }
14709   \dim_set:Nn \l__coffin_right_corner_dim
14710   { \dim_max:nn { \l__coffin_right_corner_dim } {#1} }
14711   \dim_set:Nn \l__coffin_bottom_corner_dim
14712   { \dim_min:nn { \l__coffin_bottom_corner_dim } {#2} }
14713   \dim_set:Nn \l__coffin_top_corner_dim
14714   { \dim_max:nn { \l__coffin_top_corner_dim } {#2} }
14715 }

(End definition for \__coffin_find_corner_maxima:N This function is documented on page ??.)
```

`__coffin_find_bounding_shift:` The approach to finding the shift for the bounding box is similar to that for the corners. However, there is only one value needed here and a fixed input property list, so things are a bit clearer.

```

14716 \cs_new_protected_nopar:Npn \__coffin_find_bounding_shift:
14717 {
14718   \dim_set:Nn \l__coffin_bounding_shift_dim { \c_max_dim }
14719   \prop_map_inline:Nn \l__coffin_bounding_prop
14720   { \__coffin_find_bounding_shift_aux:nn ##2 }
14721 }
14722 \cs_new_protected:Npn \__coffin_find_bounding_shift_aux:nn #1#2
14723 {
14724   \dim_set:Nn \l__coffin_bounding_shift_dim
14725   { \dim_min:nn { \l__coffin_bounding_shift_dim } {#1} }
14726 }

(End definition for \__coffin_find_bounding_shift: This function is documented on page ??.)
```

`__coffin_shift_corner:Nnnn` Shifting the corners and poles of a coffin means subtracting the appropriate values from the x - and y -components. For the poles, this means that the direction vector is unchanged.

```

14727 \cs_new_protected:Npn \__coffin_shift_corner:Nnnn #1#2#3#4
14728 {
14729   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _ prop } {#2}
14730   {
14731     { \dim_eval:n { #3 - \l__coffin_left_corner_dim } }
14732     { \dim_eval:n { #4 - \l__coffin_bottom_corner_dim } }
14733   }
14734 }
14735 \cs_new_protected:Npn \__coffin_shift_pole:Nnnnnn #1#2#3#4#5#6
14736 {
14737   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _ prop } {#2}
14738   {
14739     { \dim_eval:n { #3 - \l__coffin_left_corner_dim } }
14740     { \dim_eval:n { #4 - \l__coffin_bottom_corner_dim } }
14741     {#5} {#6}
14742 }
```

14743 }

(End definition for `__coffin_shift_corner:Nnnn` This function is documented on page ??.)

41.7 Resizing coffins

`\l_coffin_scale_x_fp` Storage for the scaling factors in x and y , respectively.

`\l_coffin_scale_y_fp`

14744 `\fp_new:N \l_coffin_scale_x_fp`

14745 `\fp_new:N \l_coffin_scale_y_fp`

(End definition for `\l_coffin_scale_x_fp` This function is documented on page ??.)

`\l_coffin_scaled_total_height_dim` When scaling, the values given have to be turned into absolute values.

`\l_coffin_scaled_width_dim`

14746 `\dim_new:N \l_coffin_scaled_total_height_dim`

14747 `\dim_new:N \l_coffin_scaled_width_dim`

(End definition for `\l_coffin_scaled_total_height_dim` This function is documented on page ??.)

`\coffin_resize:Nnn` Resizing a coffin begins by setting up the user-friendly names for the dimensions of the coffin box. The new sizes are then turned into scale factor. This is the same operation as takes place for the underlying box, but that operation is grouped and so the same calculation is done here.

14748 `\cs_new_protected:Npn \coffin_resize:Nnn #1#2#3`

14749 {

14750 `\fp_set:Nn \l_coffin_scale_x_fp`

14751 { `\dim_to_fp:n {#2} / \dim_to_fp:n { \coffin_wd:N #1 }` }

14752 `\fp_set:Nn \l_coffin_scale_y_fp`

14753 {

14754 `\dim_to_fp:n {#3} / \dim_to_fp:n { \coffin_ht:N #1 + \coffin_dp:N #1 }`

14755 }

14756 `\box_resize:Nnn #1 {#2} {#3}`

14757 `__coffin_resize_common:Nnn #1 {#2} {#3}`

14758 }

14759 `\cs_generate_variant:Nn \coffin_resize:Nnn { c }`

(End definition for `\coffin_resize:Nnn` and `\coffin_resize:cnn` These functions are documented on page ??.)

`__coffin_resize_common:Nnn` The poles and corners of the coffin are scaled to the appropriate places before actually resizing the underlying box.

14760 `\cs_new_protected:Npn __coffin_resize_common:Nnn #1#2#3`

14761 {

14762 `\prop_map_inline:cn { __coffin_corners_ __int_value:w #1 _prop }`

14763 { `__coffin_scale_corner:Nnnn #1 {##1} ##2` }

14764 `\prop_map_inline:cn { __coffin_poles_ __int_value:w #1 _prop }`

14765 { `__coffin_scale_pole:Nnnnn #1 {##1} ##2` }

Negative x -scaling values will place the poles in the wrong location: this is corrected here.

14766 `\fp_compare:nNnT \l_coffin_scale_x_fp < \c_zero_fp`

14767 {

14768 `\prop_map_inline:cn { __coffin_corners_ __int_value:w #1 _prop }`

```

14769     { \__coffin_x_shift_corner:Nnnn #1 {##1} ##2 }
14770     \prop_map_inline:cn { l__coffin_poles_ \__int_value:w #1 _prop }
14771         { \__coffin_x_shift_pole:Nnnnnn #1 {##1} ##2 }
14772     }
14773 }

```

(End definition for `__coffin_resize_common:Nnn` This function is documented on page ??.)

\coffin_scale:Nnn For scaling, the opposite calculation is done to find the new dimensions for the coffin. Only the total height is needed, as this is the shift required for corners and poles. The scaling is done the TeX way as this works properly with floating point values without needing to use the fp module.

```

14774 \cs_new_protected:Npn \coffin_scale:Nnn #1#2#3
14775 {
14776     \fp_set:Nn \l__coffin_scale_x_fp {#2}
14777     \fp_set:Nn \l__coffin_scale_y_fp {#3}
14778     \box_scale:Nnn #1 { \l__coffin_scale_x_fp } { \l__coffin_scale_y_fp }
14779     \dim_set:Nn \l__coffin_internal_dim
14780         { \coffin_ht:N #1 + \coffin_dp:N #1 }
14781     \dim_set:Nn \l__coffin_scaled_total_height_dim
14782         { \fp_abs:n { \l__coffin_scale_y_fp } \l__coffin_internal_dim }
14783     \dim_set:Nn \l__coffin_scaled_width_dim
14784         { -\fp_abs:n { \l__coffin_scale_x_fp } \coffin_wd:N #1 }
14785     \__coffin_resize_common:Nnn #1
14786         { \l__coffin_scaled_width_dim } { \l__coffin_scaled_total_height_dim }
14787 }

```

```

14788 \cs_generate_variant:Nn \coffin_scale:Nnn { c }
(End definition for \coffin_scale:Nnn and \coffin_scale:cnn These functions are documented on page ??.)

```

__coffin_scale_vector:nnNN This functions scales a vector from the origin using the pre-set scale factors in *x* and *y*. This is a much less complex operation than rotation, and as a result the code is a lot clearer.

```

14789 \cs_new_protected:Npn \__coffin_scale_vector:nnNN #1#2#3#4
14790 {
14791     \dim_set:Nn #3
14792         { \fp_to_dim:n { \dim_to_fp:n {#1} * \l__coffin_scale_x_fp } }
14793     \dim_set:Nn #4
14794         { \fp_to_dim:n { \dim_to_fp:n {#2} * \l__coffin_scale_y_fp } }
14795 }

```

(End definition for `__coffin_scale_vector:nnNN` This function is documented on page ??.)

__coffin_scale_corner:Nnnn Scaling both corners and poles is a simple calculation using the preceding vector scaling.

```

14796 \cs_new_protected:Npn \__coffin_scale_corner:Nnnn #1#2#3#4
14797 {
14798     \__coffin_scale_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
14799     \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } {#2}
14800         { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
14801 }
14802 \cs_new_protected:Npn \__coffin_scale_pole:Nnnnnn #1#2#3#4#5#6

```

```

14803 {
14804   \__coffin_scale_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
14805   \__coffin_set_pole:Nnx #1 {#2}
14806   {
14807     { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
14808     {#5} {#6}
14809   }
14810 }
(End definition for \__coffin_scale_corner:Nnnn This function is documented on page ??.)
```

__coffin_x_shift_corner:Nnnn
__coffin_x_shift_pole:Nnnnnn These functions correct for the x displacement that takes place with a negative horizontal scaling.

```

14811 \cs_new_protected:Npn \__coffin_x_shift_corner:Nnnn #1#2#3#4
14812 {
14813   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } {#2}
14814   {
14815     { \dim_eval:n { #3 + \box_wd:N #1 } } {#4}
14816   }
14817 }
14818 \cs_new_protected:Npn \__coffin_x_shift_pole:Nnnnnn #1#2#3#4#5#6
14819 {
14820   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } {#2}
14821   {
14822     { \dim_eval:n {#3 + \box_wd:N #1 } } {#4}
14823     {#5} {#6}
14824   }
14825 }
```

(End definition for __coffin_x_shift_corner:Nnnn This function is documented on page ??.)

41.8 Additions to l3file

14826 (@=ior)

\ior_map_break:
\ior_map_break:n Usual map breaking functions. Those are not yet in l3kernel proper since the mapping below is the first of its kind.

```

14827 \cs_new_nopar:Npn \ior_map_break:
14828   { \__prg_map_break:N \ior_map_break: { } }
14829 \cs_new_nopar:Npn \ior_map_break:n
14830   { \__prg_map_break:N \ior_map_break: }
(End definition for \ior_map_break: and \ior_map_break:n These functions are documented on page 190.)
```

\ior_map_inline:Nn
\ior_str_map_inline:Nn
__ior_map_inline>NNn
__ior_map_inline:NNNn
__ior_map_inline_loop:NNN
__ior_internal_tl Mapping to an input stream can be done on either a token or a string basis, hence the set up. Within that, there is a check to avoid reading past the end of a file, hence the two applications of \ior_if_eof:N. This mapping cannot be nested as the stream has only one “current line”.

```

14831 \cs_new_protected_nopar:Npn \ior_map_inline:Nn
14832   { \__ior_map_inline>NNn \ior_get:NN }
14833 \cs_new_protected_nopar:Npn \ior_str_map_inline:Nn
```

```

14834 { \__ior_map_inline:NNn \ior_get_str:NN }
14835 \cs_new_protected_nopar:Npn \__ior_map_inline:NNn
14836 {
14837     \int_gincr:N \g__prg_map_int
14838     \exp_args:Nc \__ior_map_inline:NNNn
14839         { __prg_map_ \int_use:N \g__prg_map_int :n }
14840     }
14841 \cs_new_protected:Npn \__ior_map_inline:NNNn #1#2#3#4
14842 {
14843     \cs_set:Npn #1 ##1 {#4}
14844     \ior_if_eof:NF #3 { \__ior_map_inline_loop:NNN #1#2#3 }
14845     \__prg_break_point:Mn \ior_map_break:
14846         { \int_gdecr:N \g__prg_map_int }
14847     }
14848 \cs_new_protected:Npn \__ior_map_inline_loop:NNN #1#2#3
14849 {
14850     #2 #3 \l__ior_internal_tl
14851     \ior_if_eof:NF #3
14852     {
14853         \exp_args:No #1 \l__ior_internal_tl
14854         \__ior_map_inline_loop:NNN #1#2#3
14855     }
14856 }
14857 \tl_new:N \l__ior_internal_tl
(End definition for \ior_map_inline:Nn and \ior_str_map_inline:Nn These functions are documented
on page ??.)
```

41.9 Additions to l3fp

14858 ⟨@@=fp⟩

\fp_set_from_dim:Nn
\fp_set_from_dim:cn
\fp_gset_from_dim:Nn
\fp_gset_from_dim:cn

Use the appropriate function from l3fp-convert.

```

14859 \cs_new_protected:Npn \fp_set_from_dim:Nn #1#2
14860     { \tl_set:Nx #1 { \dim_to_fp:n {#2} } }
14861 \cs_new_protected:Npn \fp_gset_from_dim:Nn #1#2
14862     { \tl_gset:Nx #1 { \dim_to_fp:n {#2} } }
14863 \cs_generate_variant:Nn \fp_set_from_dim:Nn { c }
14864 \cs_generate_variant:Nn \fp_gset_from_dim:Nn { c }
```

(End definition for \fp_set_from_dim:Nn and others. These functions are documented on page ??.)

41.10 Additions to l3prop

14865 ⟨@@=prop⟩

\prop_map_tokens:Nn
\prop_map_tokens:cn
__prop_map_tokens:nwn

The mapping grabs one key-value pair at a time, and stops when reaching the marker key \q_recursion_tail, which cannot appear in normal keys since those are strings. The odd construction \use:n {#1} allows #1 to contain any token.

```

14866 \cs_new:Npn \prop_map_tokens:Nn #1#2
14867 {
14868     \exp_last_unbraced:Nno \__prop_map_tokens:nwn {#2} #1
```

```

14869   \q_recursion_tail \q_prop { }
14870   \__prg_break_point:Nn \prop_map_break: { }
14871   }
14872 \cs_new:Npn \__prop_map_tokens:nwn #1 \q_prop #2 \q_prop #3
14873   {
14874     \__quark_if_recursion_tail_break:NN #2 \prop_map_break:
14875     \use:n {#1} {#2} {#3}
14876     \__prop_map_tokens:nwn {#1}
14877   }
14878 \cs_generate_variant:Nn \prop_map_tokens:Nn { c }
(End definition for \prop_map_tokens:Nn and \prop_map_tokens:cn These functions are documented on
page ??.)
```

\prop_get:Nn
\prop_get:cn
__prop_get_Nn:nwn

Getting the value corresponding to a key in a property list in an expandable fashion is a simple instance of mapping some tokens. Map the function \prop_get:nnn which takes as its three arguments the *key* that we are looking for, the current *key* and the current *value*. If the *keys* match, the *value* is returned. If none of the keys match, this expands to nothing.

```

14879 \cs_new:Npn \prop_get:Nn #1#2
14880   {
14881     \exp_last_unbraced:Noo \__prop_get_Nn:nwn
14882     { \tl_to_str:n {#2} } #1
14883     \tl_to_str:n {#2} \q_prop { }
14884     \__prg_break_point:
14885   }
14886 \cs_new:Npn \__prop_get_Nn:nwn #1 \q_prop #2 \q_prop #3
14887   {
14888     \str_if_eq_x:nnTF {#1} {#2}
14889     { \__prg_break:n { \exp_not:n {#3} } }
14890     { \__prop_get_Nn:nwn {#1} }
14891   }
14892 \cs_generate_variant:Nn \prop_get:Nn { c }
(End definition for \prop_get:Nn and \prop_get:cn These functions are documented on page ??.)
```

41.11 Additions to l3seq

14893 <@@=seq>

\seq_item:Nn
\seq_item:cn
__seq_item:nnn

The idea here is to find the offset of the item from the left, then use a loop to grab the correct item. If the resulting offset is too large, then the stop code { ? __prg_break: } { } will be used by the auxiliary, terminating the loop and returning nothing at all.

```

14894 \cs_new:Npn \seq_item:Nn #1#2
14895   {
14896     \exp_last_unbraced:Nfo \__seq_item:nnn
14897     {
14898       \int_eval:n
14899       {
14900         \int_compare:nNnT {#2} < \c_zero
```

```

14901           { \seq_count:N #1 + \c_one + }
14902           #2
14903       }
14904   }
14905   #1
14906   { ? \__prg_break: }
14907   { }
14908   \__prg_break_point:
14909   }
14910 \cs_new:Npn \__seq_item:nnn #1#2#3
14911 {
14912     \use_none:n #2
14913     \int_compare:nNnTF {#1} = \c_one
14914         { \__prg_break:n { \exp_not:n {#3} } }
14915         { \exp_args:Nf \__seq_item:nnn { \int_eval:n {#1 - 1} } }
14916     }
14917 \cs_generate_variant:Nn \seq_item:Nn { c }
(End definition for \seq_item:Nn and \seq_item:cn These functions are documented on page ??.)
```

\seq_mapthread_function:NNN
\seq_mapthread_function:NcN
\seq_mapthread_function:cNN
\seq_mapthread_function:ccN
__seq_mapthread_function>NN
__seq_mapthread_function:Nnnwnn

The idea here is to first expand both of the sequences, adding the usual { ? __prg_break: } { } to the end of each one. This is most conveniently done in two steps using an auxiliary function. The mapping then throws away the first token of #2 and #5, which for items in the sequences will both be __seq_item:n. The function to be mapped will then be applied to the two entries. When the code hits the end of one of the sequences, the break material will stop the entire loop and tidy up. This avoids needing to find the count of the two sequences, or worrying about which is longer.

```

14918 \cs_new:Npn \seq_mapthread_function:NNN #1#2#3
14919 {
14920     \exp_after:wN \__seq_mapthread_function:NN
14921     \exp_after:wN #3
14922     \exp_after:wN #1
14923     #2
14924     { ? \__prg_break: } { }
14925     \__prg_break_point:
14926   }
14927 \cs_new:Npn \__seq_mapthread_function:NN #1#2
14928 {
14929     \exp_after:wN \__seq_mapthread_function:Nnnwnn
14930     \exp_after:wN #1
14931     #2
14932     { ? \__prg_break: } { }
14933     \q_stop
14934   }
14935 \cs_new:Npn \__seq_mapthread_function:Nnnwnn #1#2#3#4 \q_stop #5#6
14936 {
14937     \use_none:n #2
14938     \use_none:n #5
14939     #1 {#3} {#6}
14940     \__seq_mapthread_function:Nnnwnn #1 #4 \q_stop
```

```

14941   }
14942 \cs_generate_variant:Nn \seq_mapthread_function:NNN {      Nc }
14943 \cs_generate_variant:Nn \seq_mapthread_function:NNN { c , cc }
(End definition for \seq_mapthread_function:NNN and others. These functions are documented on page ??.)

```

\seq_set_from_clist:NN Setting a sequence from a comma-separated list is done using a simple mapping.

```

14944 \cs_new_protected:Npn \seq_set_from_clist:NN #1#2
14945 {
14946   \tl_set:Nx #1
14947   { \clist_map_function:NN #2 \__seq_wrap_item:n }
14948 }
14949 \cs_new_protected:Npn \seq_set_from_clist:Nn #1#2
14950 {
14951   \tl_set:Nx #1
14952   { \clist_map_function:nN {#2} \__seq_wrap_item:n }
14953 }
14954 \cs_new_protected:Npn \seq_gset_from_clist:NN #1#2
14955 {
14956   \tl_gset:Nx #1
14957   { \clist_map_function:NN #2 \__seq_wrap_item:n }
14958 }
14959 \cs_new_protected:Npn \seq_gset_from_clist:Nn #1#2
14960 {
14961   \tl_gset:Nx #1
14962   { \clist_map_function:nN {#2} \__seq_wrap_item:n }
14963 }
14964 \cs_generate_variant:Nn \seq_set_from_clist:NN {      Nc }
14965 \cs_generate_variant:Nn \seq_set_from_clist:NN { c , cc }
14966 \cs_generate_variant:Nn \seq_set_from_clist:Nn { c      }
14967 \cs_generate_variant:Nn \seq_gset_from_clist:NN {      Nc }
14968 \cs_generate_variant:Nn \seq_gset_from_clist:NN { c , cc }
14969 \cs_generate_variant:Nn \seq_gset_from_clist:Nn { c      }
(End definition for \seq_set_from_clist:NN and others. These functions are documented on page ??.)

```

\seq_reverse:N Previously, \seq_reverse:N was coded by collecting the items in reverse order after an \exp_stop_f: marker.

```

\seq_reverse:c
\seq_greverse:N
\seq_greverse:c
  \__seq_tmp:w
\__seq_reverse>NN
\__seq_reverse_item:nwn
\cs_new_protected:Npn \seq_reverse:N #1
{
  \cs_set_eq:NN \@@_item:n \@@_reverse_item:nw
  \tl_set:Nf #2 { #2 \exp_stop_f: }
}
\cs_new:Npn \@@_reverse_item:nw #1 #2 \exp_stop_f:
{
  #2 \exp_stop_f:
  \@@_item:n {#1}
}

```

At first, this seems optimal, since we can forget about each item as soon as it is placed after `\exp_stop_f`. Unfortunately, TeX's usual tail recursion does not take place in this case: since the following `_seq_reverse_item:nw` only reads tokens until `\exp_stop_f`, and never reads the `\@@_item:n {#1}` left by the previous call, TeX cannot remove that previous call from the stack, and in particular must retain the various macro parameters in memory, until the end of the replacement text is reached. The stack is thus only flushed after all the `_seq_reverse_item:nw` are expanded. Keeping track of the arguments of all those calls uses up a memory quadratic in the length of the sequence. TeX can then not cope with more than a few thousand items.

Instead, we collect the items in the argument of `\exp_not:n`. The previous calls are cleanly removed from the stack, and the memory consumption becomes linear.

```

14970 \cs_new_protected_nopar:Npn \_seq_tmp:w { }
14971 \cs_new_protected_nopar:Npn \seq_reverse:N
14972 { \_seq_reverse:NN \tl_set:Nx }
14973 \cs_new_protected_nopar:Npn \seq_greverse:N
14974 { \_seq_reverse:NN \tl_gset:Nx }
14975 \cs_new_protected:Npn \_seq_reverse:NN #1 #2
14976 {
14977   \cs_set_eq:NN \_seq_tmp:w \_seq_item:n
14978   \cs_set_eq:NN \_seq_item:n \_seq_reverse_item:nwn
14979   #1 #2 { #2 \exp_not:n { } }
14980   \cs_set_eq:NN \_seq_item:n \_seq_tmp:w
14981 }
14982 \cs_new:Npn \_seq_reverse_item:nwn #1 #2 \exp_not:n #3
14983 {
14984   #2
14985   \exp_not:n { \_seq_item:n {#1} #3 }
14986 }
14987 \cs_generate_variant:Nn \seq_reverse:N { c }
14988 \cs_generate_variant:Nn \seq_greverse:N { c }

```

(End definition for `\seq_reverse:N` and others. These functions are documented on page ??.)

`\seq_set_filter:NNn`
`\seq_gset_filter:NNn`
`_seq_set_filter:NNNn`

Similar to `\seq_map_inline:Nn`, without a `_prg_break_point`: because the user's code is performed within the evaluation of a boolean expression, and skipping out of that would break horribly. The `_seq_wrap_item:n` function inserts the relevant `_seq-item:n` without expansion in the input stream, hence in the x-expanding assignment.

```

14989 \cs_new_protected_nopar:Npn \seq_set_filter:NNn
14990 { \_seq_set_filter:NNNn \tl_set:Nx }
14991 \cs_new_protected_nopar:Npn \seq_gset_filter:NNn
14992 { \_seq_set_filter:NNNn \tl_gset:Nx }
14993 \cs_new_protected:Npn \_seq_set_filter:NNNn #1#2#3#4
14994 {
14995   \_seq_push_item_def:n { \bool_if:nT {#4} { \_seq_wrap_item:n {##1} } }
14996   #1 #2 { #3 }
14997   \_seq_pop_item_def:
14998 }

```

(End definition for `\seq_set_filter:NNn` and `\seq_gset_filter:NNn`. These functions are documented on page 192.)

```
\seq_set_map:Nnn
\seq_gset_map:Nnn
```

_seq_set_map:NNNn

Very similar to \seq_set_filter:NNn. We could actually merge the two within a single function, but it would have weird semantics.

```
14999 \cs_new_protected_nopar:Npn \seq_set_map:Nnn
15000 { \_seq_set_map:NNNn \tl_set:Nx }
15001 \cs_new_protected_nopar:Npn \seq_gset_map:Nnn
15002 { \_seq_set_map:NNNn \tl_gset:Nx }
15003 \cs_new_protected:Npn \_seq_set_map:NNNn #1#2#3#4
15004 {
15005     \_seq_push_item_def:n { \exp_not:N \_seq_item:n {#4} }
15006     #1 #2 { #3 }
15007     \_seq_pop_item_def:
15008 }
```

(End definition for \seq_set_map:NNn and \seq_gset_map:NNn These functions are documented on page 192.)

```
\seq_use:Nnnn
\seq_use:NnNn
\seq_use_ii:nwwwnwn
\seq_use_iii:nwwn
```

See \clist_use:Nnnn for a general explanation. The main difference is that we use _seq_item:n as a delimiter rather than commas. We also need to add _seq_item:n at various places.

```
15009 \cs_new:Npn \seq_use:Nnnn #1#2#3#4
15010 {
15011     \seq_if_exist:NTF #1
15012     {
15013         \int_case:nnn { \seq_count:N #1 }
15014         {
15015             { 0 } { }
15016             { 1 } { \exp_after:wN \seq_use:NnNn #1 \_seq_item:n { } { } }
15017             { 2 } { \exp_after:wN \seq_use:NnNn #1 {#2} }
15018         }
15019         {
15020             \exp_after:wN \seq_use_ii:nwwwnwn
15021             \exp_after:wN { \exp_after:wN } #1 \_seq_item:n
15022             \q_mark { \seq_use_ii:nwwwnwn {#3} }
15023             \q_mark { \seq_use_iii:nwwn {#4} }
15024             \q_stop { }
15025         }
15026     }
15027     { \msg_kernel_expandable_error:nnn { kernel } { bad-variable } {#1} }
15028 }
15029 \cs_new:Npn \seq_use:NnNn \_seq_item:n #1 \_seq_item:n #2#3
15030 { \exp_not:n { #1 #3 #2 } }
15031 \cs_new:Npn \seq_use_ii:nwwwnwn
15032 #1 \_seq_item:n #2 \_seq_item:n #3 \_seq_item:n #4#5
15033 \q_mark #6#7 \q_stop #8
15034 {
15035     #6 \_seq_item:n {#3} \_seq_item:n {#4} #5
15036     \q_mark {#6} #7 \q_stop { #8 #1 #2 }
15037 }
15038 \cs_new:Npn \seq_use_iii:nwwn #1 \_seq_item:n #2 #3 \q_stop #4
15039 { \exp_not:n { #4 #1 #2 } }
```

(End definition for `\seq_use:Nnnn` This function is documented on page 192.)

41.12 Additions to l3skip

15040 `\cs_new:Npn \skip_split_finite_else_action:nnNN #1#2#3#4`

This macro is useful when performing error checking in certain circumstances. If the `\skip` register holds finite glue it sets #3 and #4 to the stretch and shrink component, resp. If it holds infinite glue set #3 and #4 to zero and issue the special action #2 which is probably an error message. Assignments are local.

```
15041 \cs_new:Npn \skip_split_finite_else_action:nnNN #1#2#3#4
15042 {
15043     \skip_if_finite:nTF {#1}
15044     {
15045         #3 = \etex_gluestretch:D #1 \scan_stop:
15046         #4 = \etex_glueshrink:D #1 \scan_stop:
15047     }
15048     {
15049         #3 = \c_zero_skip
15050         #4 = \c_zero_skip
15051         #2
15052     }
15053 }
```

(End definition for `\skip_split_finite_else_action:nnNN` This function is documented on page 193.)

41.13 Additions to l3tl

15054 `\cs_new:Npn \tl_if_single_token:n { p , T , F , TF }`

`\tl_if_single_token:nTF`

There are four cases: empty token list, token list starting with a normal token, with a brace group, or with a space token. If the token list starts with a normal token, remove it and check for emptiness. Otherwise, compare with a single space, only case where we have a single token.

```
15055 \prg_new_conditional:Npnn \tl_if_single_token:n #1 { p , T , F , TF }
15056 {
15057     \tl_if_head_is_N_type:nTF {#1}
15058     {
15059         \__str_if_eq_x_return:nn { \exp_not:o { \use_none:n #1 } } { } }
15060     {
15061 }
```

(End definition for `\tl_if_single_token:n` These functions are documented on page 193.)

`\tl_reverse_tokens:n`

The same as `\tl_reverse:n` but with recursion within brace groups.

```
15061 \cs_new:Npn \tl_reverse_tokens:n #1
15062 {
15063     \etex_unexpanded:D \exp_after:wN
15064     {
15065         \tex_roman numeral:D
15066         \__tl_act:NNNnn
15067             \__tl_reverse_normal:nN
```

```

15068     \__tl_reverse_group:nn
15069     \__tl_reverse_space:n
15070     { }
15071     {#1}
15072     }
15073   }
15074 \cs_new:Npn \__tl_reverse_group:nn #1
15075   {
15076     \__tl_act_group_recurse:Nnn
15077     \__tl_act_reverse_output:n
15078     { \tl_reverse_tokens:n }
15079   }

```

__tl_act_group_recurse:Nnn

In many applications of `__tl_act:NNNnn`, we need to recursively apply some transformation within brace groups, then output. In this code, #1 is the output function, #2 is the transformation, which should expand in two steps, and #3 is the group.

```

15080 \cs_new:Npn \__tl_act_group_recurse:Nnn #1#2#3
15081   {
15082     \exp_args:Nf #1
15083     { \exp_after:wN \exp_after:wN \exp_after:wN { #2 {#3} } }
15084   }

```

(End definition for `\tl_reverse_tokens:n`. This function is documented on page 193.)

\tl_count_tokens:n

```

\__tl_act_count_normal:nN
\__tl_act_count_group:nn
\__tl_act_count_space:n

```

The token count is computed through an `\int_eval:n` construction. Each `1+` is output to the *left*, into the integer expression, and the sum is ended by the `\c_zero` inserted by `__tl_act_end:wn`. Somewhat a hack.

```

15085 \cs_new:Npn \tl_count_tokens:n #1
15086   {
15087     \int_eval:n
15088     {
15089       \__tl_act:NNNnn
15090       \__tl_act_count_normal:nN
15091       \__tl_act_count_group:nn
15092       \__tl_act_count_space:n
15093       { }
15094       {#1}
15095     }
15096   }
15097 \cs_new:Npn \__tl_act_count_normal:nN #1 #2 { 1 + }
15098 \cs_new:Npn \__tl_act_count_space:n #1 { 1 + }
15099 \cs_new:Npn \__tl_act_count_group:nn #1 #2
15100   { 2 + \tl_count_tokens:n {#2} + }

```

(End definition for `\tl_count_tokens:n`. This function is documented on page 193.)

```

\c__tl_act_uppercase_tl
\c__tl_act_lowercase_tl

```

These constants contain the correspondence between lowercase and uppercase letters, in the form `aAbBcC...` and `AaBbCc...` respectively.

```

15101 \tl_const:Nn \c__tl_act_uppercase_tl
15102   {
15103     aA bB cC dD eE fF gG hH iI jJ kK lL mM

```

```

15104     nN oO pP qQ rR sS tT uU vV wW xX yY zZ
15105   }
15106 \tl_const:Nn \c__tl_act_lowercase_tl
15107 {
15108   Aa Bb Cc Dd Ee Ff Gg Hh Ii Jj Kk Ll Mm
15109   Nn Oo Pp Qq Rr Ss Tt Uu Vv Ww Xx Yy Zz
15110 }
(End definition for \c__tl_act_uppercase_tl and \c__tl_act_lowercase_tl These variables are documented on page ??.)
```

\tl_expandable_uppercase:n
\tl_expandable_lowercase:n

__tl_act_case_normal:nN
__tl_act_case_group:nn
__tl_act_case_space:n

The only difference between uppercasing and lowercasing is the table of correspondance that is used. As for other token list actions, we feed __tl_act:NNNnn three functions, and this time, we use the *<parameters>* argument to carry which case-changing we are applying. A space is simply output. A normal token is compared to each letter in the alphabet using \str_if_eq:nn tests, and converted if necessary to upper/lowercase, before being output. For a group, we must perform the conversion within the group (the \exp_after:wN trigger \romannumeral, which expands fully to give the converted group), then output.

```

15111 \cs_new:Npn \tl_expandable_uppercase:n #
15112 {
15113   \etex_unexpanded:D \exp_after:wN
15114   {
15115     \tex_roman numeral:D
15116       \_\_tl_act_case_aux:nn { \c__tl_act_uppercase_tl } {#1}
15117   }
15118 }
15119 \cs_new:Npn \tl_expandable_lowercase:n #
15120 {
15121   \etex_unexpanded:D \exp_after:wN
15122   {
15123     \tex_roman numeral:D
15124       \_\_tl_act_case_aux:nn { \c__tl_act_lowercase_tl } {#1}
15125   }
15126 }
15127 \cs_new:Npn \_\_tl_act_case_aux:nn
15128 {
15129   \_\_tl_act:NNNnn
15130     \_\_tl_act_case_normal:nN
15131     \_\_tl_act_case_group:nn
15132     \_\_tl_act_case_space:n
15133 }
15134 \cs_new:Npn \_\_tl_act_case_space:n #1 { \_\_tl_act_output:n {~} }
15135 \cs_new:Npn \_\_tl_act_case_normal:nN #1 #
15136 {
15137   \exp_args:Nf \_\_tl_act_output:n
15138   {
15139     \exp_args:NNo \str_case:nnn #2 {#1}
15140     { \exp_stop_f: #2 }
15141 }
```

```

15142 }
15143 \cs_new:Npn \__tl_act_case_group:nn #1 #2
15144 {
15145     \exp_after:wN \__tl_act_output:n \exp_after:wN
15146         { \exp_after:wN { \tex_roman numeral:D \__tl_act_case_aux:nn {#1} {#2} } }
15147 }
(End definition for \tl_expandable_uppercase:n and \tl_expandable_lowercase:n These functions are
documented on page 194.)
```

\tl_item:nn **\tl_item:Nn** **\tl_item:cn** The idea here is to find the offset of the item from the left, then use a loop to grab the correct item. If the resulting offset is too large, then `\quark_if_recursion_tail_stop:n` terminates the loop, and returns nothing at all.

```

\__tl_item:nn 15148 \cs_new:Npn \tl_item:nn #1#2
15149 {
15150     \exp_args:Nf \__tl_item:nn
15151 {
15152     \int_eval:n
15153     {
15154         \int_compare:nNnT {#2} < \c_zero
15155             { \tl_count:n {#1} + \c_one + }
15156             #2
15157     }
15158 }
15159 #1
15160 \q_recursion_tail
15161 \__prg_break_point:
15162 }
15163 \cs_new:Npn \__tl_item:nn #1#2
15164 {
15165     \__quark_if_recursion_tail_break:nN {#2} \__prg_break:
15166     \int_compare:nNnTF {#1} = \c_one
15167         { \__prg_break:n { \exp_not:n {#2} } }
15168         { \exp_args:Nf \__tl_item:nn { \int_eval:n { #1 - 1 } } }
15169 }
15170 \cs_new_nopar:Npn \tl_item:Nn { \exp_args:No \tl_item:nn }
15171 \cs_generate_variant:Nn \tl_item:Nn { c }
(End definition for \tl_item:nn, \tl_item:Nn, and \tl_item:cn These functions are documented on
page ??.)
```

41.14 Additions to `I3tokens`

```

15172 <@=char>
\char_set_active:Npn
\char_set_active:Npx
\char_gset_active:Npn
\char_gset_active:Npx
\char_set_active_eq:NN
\char_gset_active_eq:NN
15173 \group_begin:
15174     \char_set_catcode_active:N \^@^
15175     \cs_set:Npn \char_tmp:NN #1#2
15176     {
15177         \cs_new:Npn #1 ##1
15178     }
```

```

15179      \char_set_catcode_active:n { '##1 }
15180      \group_begin:
15181      \char_set_lccode:nn { `^^@ } { '##1 }
15182      \tl_to_lowercase:n { \group_end: #2 ^^@ }
15183      }
15184      }
15185      \char_tmp:NN \char_set_active:Npn      \cs_set:Npn
15186      \char_tmp:NN \char_set_active:Npx      \cs_set:Npx
15187      \char_tmp:NN \char_gset_active:Npn     \cs_gset:Npn
15188      \char_tmp:NN \char_gset_active:Npx     \cs_gset:Npx
15189      \char_tmp:NN \char_set_active_eq:NN    \cs_set_eq:NN
15190      \char_tmp:NN \char_gset_active_eq:NN   \cs_gset_eq:NN
15191      \group_end:
(End definition for \char_set_active:Npn and \char_set_active:Npx These functions are documented
on page 195.)
15192      <@=peek>

```

\peek_N_type:TF The next token is normal if it is neither a begin-group token, nor an end-group token, nor a charcode-32 space token. Note that implicit begin-group tokens, end-group tokens, and spaces are also recognized as non-N-type. Here, there is no *(search token)*, so we feed a dummy `\scan_stop:` to the `\peek_token_generic::NN` functions.

```

15193 \cs_new_protected_nopar:Npn \_peek_execute_branches_N_type:
15194 {
15195   \bool_if:nTF
15196   {
15197     \token_if_eq_catcode_p:NN \l_peek_token \c_group_begin_token ||
15198     \token_if_eq_catcode_p:NN \l_peek_token \c_group_end_token ||
15199     \token_if_eq_meaning_p:NN \l_peek_token \c_space_token
15200   }
15201   { \_peek_false:w }
15202   { \_peek_true:w }
15203 }
15204 \cs_new_protected_nopar:Npn \peek_N_type:TF
15205   { \_peek_token_generic:NNTF \_peek_execute_branches_N_type: \scan_stop: }
15206 \cs_new_protected_nopar:Npn \peek_N_type:T
15207   { \_peek_token_generic:NNT \_peek_execute_branches_N_type: \scan_stop: }
15208 \cs_new_protected_nopar:Npn \peek_N_type:F
15209   { \_peek_token_generic:NNF \_peek_execute_branches_N_type: \scan_stop: }
(End definition for \peek_N_type: This function is documented on page ??.)
15210 </initex | package>

```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols	
\!	<u>7714</u>
\"	<u>2715</u> , <u>2730</u>
\#	<u>6</u> , <u>2730</u> , <u>9550</u>
\\$	<u>2716</u> , <u>2730</u>
\%	<u>2730</u> , <u>9552</u>
	<u>174</u>
\	<u>2717</u> , <u>2730</u> , <u>7714</u> , <u>7715</u> , <u>11193</u> , <u>11219</u>
\()	<u>11138</u> , <u>11374</u>
**	<u>175</u>
*	<u>2695</u> , <u>2697</u> , <u>2701</u> , <u>2708</u> , <u>9517</u> , <u>9518</u> , <u>10948</u>
\,	<u>8397</u> , <u>8399</u> , <u>11392</u>
\-	<u>317</u> , <u>10365</u>
\.bool_gset:N	<u>8753</u>
\.bool_gset_inverse:N	<u>8757</u>
\.bool_set:N	<u>8753</u>
\.bool_set_inverse:N	<u>8757</u>
\.choice:	<u>8761</u>
\.choice_code:n	<u>8769</u>
\.choice_code:x	<u>8769</u>
\.choices:nn	<u>8763</u>
\.clist_gset:N	<u>8773</u>
\.clist_gset:c	<u>8773</u>
\.clist_set:N	<u>8773</u>
\.clist_set:c	<u>8773</u>
\.code:n	<u>8765</u>
\.code:x	<u>8765</u>
\.default:V	<u>8781</u>
\.default:n	<u>8781</u>
\.dim_gset:N	<u>8785</u>
\.dim_gset:c	<u>8785</u>
\.dim_set:N	<u>8785</u>
\.dim_set:c	<u>8785</u>
\.fp_gset:N	<u>8793</u>
\.fp_gset:c	<u>8793</u>
\.fp_set:N	<u>8793</u>
\.fp_set:c	<u>8793</u>
\.generate_choices:n	<u>8801</u>
\.initial:V	<u>8803</u>
\.initial:n	<u>8803</u>
\.int_gset:N	<u>8807</u>
\.int_gset:c	<u>8807</u>
\.int_set:N	<u>8807</u>
\.int_set:c	<u>8807</u>
\.meta:n	<u>8815</u>
\.meta:x	<u>8815</u>
\.multichoice:	<u>8819</u>
\.multichoice:nn	<u>8819</u>
\.skip_gset:N	<u>8823</u>
\.skip_gset:c	<u>8823</u>
\.skip_set:N	<u>8823</u>
\.skip_set:c	<u>8823</u>
\.tl_gset:N	<u>8831</u>
\.tl_gset:c	<u>8831</u>
\.tl_gset_x:N	<u>8831</u>
\.tl_gset_x:c	<u>8831</u>
\.tl_set:N	<u>8831</u>
\.tl_set:c	<u>8831</u>
\.tl_set_x:N	<u>8831</u>
\.tl_set_x:c	<u>8831</u>
\.value_forbidden:	<u>8847</u>
\.value_required:	<u>8847</u>
\vee	<u>316</u>
?:	<u>174</u>
\:	<u>1065</u> , <u>2807</u> , <u>3006</u>
\:::	<u>33</u> , <u>1614</u> , <u>1615</u> , <u>1616</u> , <u>1616</u> , <u>1617</u> , <u>1618</u> , <u>1619</u> , <u>1620</u> , <u>1622</u> , <u>1624</u> , <u>1631</u> , <u>1636</u> , <u>1642</u> , <u>1761</u> , <u>1762</u> , <u>1763</u> , <u>1764</u> , <u>1765</u> , <u>1766</u> , <u>1767</u> , <u>1768</u> , <u>1769</u> , <u>1770</u> , <u>1771</u> , <u>1772</u> , <u>1773</u> , <u>1774</u> , <u>1775</u> , <u>1776</u> , <u>1777</u> , <u>1778</u> , <u>1779</u> , <u>1780</u> , <u>1781</u> , <u>1782</u> , <u>1783</u> , <u>1784</u> , <u>1785</u> , <u>1786</u> , <u>1787</u> , <u>1788</u> , <u>1790</u> , <u>1795</u> , <u>1797</u> , <u>1802</u> , <u>1807</u> , <u>1844</u> , <u>1845</u> , <u>1846</u> , <u>1847</u> , <u>1848</u>
\:::N	<u>33</u> , <u>1618</u> , <u>1618</u> , <u>1771</u> , <u>1777</u> , <u>1778</u> , <u>1782</u> , <u>1783</u> , <u>1847</u>
\:::V	<u>33</u> , <u>1636</u> , <u>1636</u> , <u>1767</u>
\:::V_unbraced	<u>1789</u> , <u>1797</u>
\:::c	<u>33</u> , <u>1620</u> , <u>1620</u> , <u>1762</u> , <u>1770</u> , <u>1772</u> , <u>1779</u> , <u>1786</u> , <u>1787</u>
\:::f	<u>33</u> , <u>1624</u> , <u>1624</u> , <u>1763</u> , <u>1764</u> , <u>1765</u> , <u>1769</u> , <u>1846</u>
\:::f_unbraced	<u>1789</u> , <u>1790</u>
\:::n	<u>33</u> , <u>1617</u> , <u>1617</u> , <u>1762</u> , <u>1765</u> , <u>1766</u> , <u>1767</u> , <u>1773</u> , <u>1777</u> , <u>1779</u> , <u>1780</u> , <u>1782</u> , <u>1784</u> , <u>1785</u> , <u>1787</u> , <u>1844</u> , <u>1847</u>

\:::o . . . 33, 1622, 1622, 1763, 1766, 1768, 1769, 1770, 1774, 1775, 1777, 1778, 1780, 1781, 1783, 1785, 1788, 1845
\:::o_unbraced 1789, 1795, 1844, 1845, 1846, 1847
\:::p 33, 1619, 1619
\:::v 33, 1636, 1642
\:::v_unbraced 1789, 1802
\:::x 33, 1631, 1631, 1761, 1771, 1772, 1773, 1774, 1775, 1776, 1782, 1783, 1784, 1785, 1786, 1787, 1788
\:::x_unbraced 1789, 1807, 1848
\::N 11391
\; 2807, 3005, 3006
\= 8396, 8398
\? 11341
\@ 1065, 1066, 4720, 4721
\@_parse:n 8395, 8403, 8490
\@_parse_elt:w 8411, 8417, 8417, 8420, 8424
\@_split_key:n 8429, 8447, 8447
\@_split_key:w 8447, 8452, 8454
\@_split_key_value:w 8423, 8427, 8427
\@_split_key_value:wTF 8427, 8440, 8445
\@_split_value:w 8441, 8456, 8456
\@_split_value_aux:w 8474, 8477
\@_end 735
\@_hyph 738
\@_input 739
\@_italiccorr 740
\@_underline 741
\@_addtofilelist 9170
\@_currname 9062
\@_filelist 9169, 9196, 9198, 9213
\@_ifpackageloaded 142, 223
\@_namedef 205
\@_nil 200, 208
\@_popfilename 170, 188, 190
\@_pushfilename 170, 171, 186
\@_tempa 55, 57, 65
\@_tempboxa 6596
\@ 1462, 2730, 7546, 7547, 7548, 7549, 7649, 7667, 7669, 7674, 7675, 7689, 7690, 7693, 7694, 7765, 7854, 7862, 8071, 8078, 8090, 8091, 8106, 8107, 8310, 8314, 8319, 8355, 8988, 9003, 9004, 9010, 9017, 9030, 9036, 9555, 9692, 9699, 9706, 10151, 10154, 10155, 10156, 10163, 10166, 10167
\{ 4, 2730, 7712, 8310, 8314, 8315, 9549
\} 5, 2730, 7713, 8310, 8314, 8315, 9551
\^ 7, 10, 90, 2718, 2730, 8221, 9524, 13049, 15174, 15181
_ 2719, 2730, 10365
_alloc_reg:nNN 9246, 9404
_alloc_setup_type:nnn 9244, 9402
_bool_0:w 2206
_bool_1:w 2204
bool(:Nw 2184
bool)_0:w 2200
bool)_1:w 2200
bool:Nw 2182
_bool_S_0:w 2200
_bool_S_1:w 2200
_bool_choose:NNN 2186, 2190, 2191, 2191
_bool_eval_skip_to_end:Nw 2206, 2206, 2207, 2209, 2223
_bool_eval_skip_to_end_ii:Nw 2206, 2211, 2215
_bool_eval_skip_to_end_iii:Nw 2206, 2219, 2221
_bool_get_next>NN 2170, 2172, 2172, 2183, 2187, 2204, 2205
_bool_if_left_parentheses:wwn 2152, 2155, 2162, 2163
_bool_if_or:wwn 2152, 2158, 2166, 2167
_bool_if_parse:NNNww 2159, 2168, 2168
_bool_if_right_parentheses:wwn 2152, 2157, 2164, 2165
_bool_p:Nw 2189
_box_resize:Nnn 14305, 14321, 14326, 14350, 14367
_box_resize_common:N 14333, 14389, 14394, 14394
_box_rotate:N 14191, 14199, 14203
_box_rotate_quadrant_four: 14191, 14218, 14292
_box_rotate_quadrant_one: 14191, 14212, 14259
_box_rotate_quadrant_three: 14191, 14217, 14281
_box_rotate_quadrant_two: 14191, 14213, 14270
_box_rotate_x:nnN 14191, 14237, 14265, 14267, 14276, 14278, 14287, 14289, 14298, 14300
_box_rotate_y:nnN 14191, 14248, 14261, 14263, 14272, 14274, 14283, 14285, 14294, 14296
_box_show>NNnn 6608, 6618, 6625, 6625

```

\__chk_if_exist_cs:N ..... 23, 1204, 1204, 1213, 1870, 9340, 9474
\__chk_if_exist_cs:c ..... 1035, 1040, 1045, 1050, 1204, 1212
\__chk_if_free_cs:N ..... 24, 1181, 1181, 1191, 1203, 1218, 1266, 1605, 3447, 3462, 4155, 4392, 4488, 4582, 4588, 4593, 6498, 14032, 14055
\__chk_if_free_cs:c ..... 1181, 1202
\__chk_if_free_msg:nn ..... 7600, 7600, 7610, 7623
\__clist_concat:NNNN 5807, 5808, 5810, 5811
\__clist_count:n ..... 6125, 6130, 6143
\__clist_count:w .. 6125, 6139, 6144, 6148
\__clist_get:wn .. 5889, 5894, 5897, 5931
\__clist_if_empty_n:w ..... 14560, 14562, 14567, 14570
\__clist_if_empty_n:wNw ..... 14560, 14571, 14573
\__clist_if_in_return:nn ..... 6023, 6025, 6030, 6032
\__clist_item:nnNn ..... 14469, 14471, 14477, 14501
\__clist_item_N_loop:nw ..... 14469, 14474, 14492, 14496
\__clist_item_n:nw .. 14499, 14504, 14507
\__clist_item_n_end:n 14499, 14515, 14523
\__clist_item_n_loop:nw ..... 14499, 14508, 14509, 14512, 14517
\__clist_item_n_strip:w ..... 14499, 14526, 14528
\__clist_map_function:Nw ..... 6048, 6052, 6057, 6061, 6084
\__clist_map_function_n:Nn ..... 6064, 6066, 6070, 6074
\__clist_map_unbrace:Nw 6064, 6073, 6077
\__clist_map_variable:Nnw ..... 6097, 6102, 6113, 6118
\__clist_pop:NNN .. 5900, 5901, 5903, 5904
\__clist_pop:wN ..... 5900, 5917, 5923
\__clist_pop:wwNNN 5900, 5909, 5912, 5947
\__clist_pop_TF:NNN 5926, 5939, 5941, 5942
\__clist_put_left:NNNN ..... 5863, 5864, 5866, 5867
\__clist_put_right:NNNn ..... 5876, 5877, 5879, 5880
\__clist_remove_all: 5990, 6000, 6004, 6016
\__clist_remove_all:NNn ..... 5990, 5991, 5993, 5994
\__clist_remove_all:w .. 5990, 6017, 6018
\__clist_remove_duplicates:NN ..... 5974, 5975, 5977, 5978
\__clist_set_from_seq:NNNN ..... 14529, 14530, 14532, 14533
\__clist_set_from_seq:w ..... 14529, 14548, 14552
\__clist_tmp:w ..... 5788, 5788, 5996, 6017, 6034, 6036
\__clist_trim_spaces:n ..... 5836, 5836, 5858, 5860, 14558
\__clist_trim_spaces_generic:nn ..... 5830, 5833, 5835
\__clist_trim_spaces_generic:nw 5830, 5838, 5848, 5853, 6066, 6074
\__clist_trim_spaces_ii:nn ..... 5836, 5839, 5843, 5849, 5854
\__clist_use:www 14574, 14581, 14582, 14594
\__clist_use_ii:nnnnnnn ..... 14574, 14585, 14587, 14595
\__clist_use_iii:nnnn 14574, 14588, 14598
\__clist_wrap_item:n 14529, 14541, 14545
\__coffin_align:NnnNnnnnN ..... 7137, 7174, 7192, 7200, 7200, 7291
\__coffin_calculate_intersection:Nnn ..... 7029, 7029, 7202, 7205, 7491
\__coffin_calculate_intersection:nnnnnnnn ..... 7029, 7035, 7044, 7437
\__coffin_calculate_intersection_aux:nnnnnn ..... 7029, 7056, 7071, 7080, 7087, 7113, 7122
\__coffin_display_attach:Nnnnn ..... 7403, 7442, 7464, 7483, 7489
\__coffin_display_handles_aux:nnnn ..... 7403, 7470, 7475, 7481
\__coffin_display_handles_aux:nnnnnn ..... 7403, 7428, 7432
\__coffin_find_bounding_shift: ..... 14621, 14716, 14716
\__coffin_find_bounding_shift_aux:nn ..... 14716, 14720, 14722
\__coffin_find_corner_maxima:N ..... 14620, 14696, 14696
\__coffin_find_corner_maxima_aux:nn ..... 14696, 14703, 14705
\__coffin_get_pole:NnN ..... 6926, 6926, 7031, 7032, 7255, 7256, 7259, 7260, 7417, 7418, 7421
\__coffin_gset_eq_structure:NN ..... 6943, 6950

```

```

\__coffin_if_exist:N ..... \__coffin_update_poles:N . 6819, 6840,
... 6778, 6778, 6789, 6809, 6826, 6864, 6887, 6995, 6995, 7152, 7183
6856, 6873, 6907, 6959, 6970, 7515 \__coffin_update_vertical_poles:Nnn
\__coffin_mark_handle_aux:nnnnNnn ..... 7168, 7187, 7253, 7253
\__coffin_offset_corner:Nnnnn ..... \__coffin_x_shift_corner:Nnnn .....
... 7348, 7386, 7391, 7395 ... 14769, 14811, 14811
\__coffin_offset_corner:Nnnn ..... \__coffin_x_shift_pole:Nnnnnn .....
... 7238, 7241, 7243 ... 14771, 14811, 14818
\__coffin_offset_corners:Mnn ..... \__cs_count_signature:N .....
... 7157, 7158, 7164, 7165, 7238, 7238 ... 24, 1313, 1313, 1324
\__coffin_offset_pole:Nnnnnn ..... \__cs_count_signature:c .... 1313, 1323
... 7219, 7222, 7224 \__cs_count_signature:nnN 1313, 1314, 1315
\__coffin_offset_poles:Nnn 7155, 7156, 7161, 7162, 7184, 7185, 7219, 7219 \__cs_generate_from_signature:NNn ...
\__coffin_reset_structure:N ..... 6792, 6818, 6839, 6863, 6886, 6936, 6936, 7149, 7179 ... 1342, 1346
\__coffin_resize_common:Nnn ..... \__cs_generate_from_signature:nnNNn
... 14757, 14760, 14760, 14785 ... 1348, 1351
\__coffin_rotate_bounding:nnn ..... \__cs_generate_internal_variant:n ...
... 14619, 14653, 14653 ... 2013, 2026, 2032
\__coffin_rotate_corner:Nnnn ..... \__cs_generate_internal_variant:wnnWnnn
... 14614, 14653, 14659 ... 2034, 2045
\__coffin_rotate_pole:Nnnnn ..... \__cs_generate_internal_variant:wwn
... 14616, 14665, 14665 ... 2026
\__coffin_rotate_vector:nnNN 14655, 14661, 14667, 14668, 14677, 14677 \__cs_generate_internal_variant_loop:n
\__coffin_scale_corner:Nnnn ..... 14763, 14796, 14796 ... 2026, 2043, 2052, 2055
\__coffin_scale_pole:Nnnnnn ..... \__cs_generate_variant:N 1871, 1878, 1886
... 14765, 14796, 14802 \__cs_generate_variant:Nnnw ...
\__coffin_scale_vector:nnNN ..... 1914, 1916, 1916, 1934
... 14789, 14789, 14798, 14804 \__cs_generate_variant:nnNN ...
\__coffin_set_bounding:N ..... 1874, 1907, 1907
... 14617, 14641, 14641 \__cs_generate_variant:ww 1878, 1891, 1899
\__coffin_set_eq_structure:NN ..... \__cs_generate_variant:wwNN ...
... 6910, 6943, 6943 ... 1923, 2006, 2006
\__coffin_set_pole:Nnn . 6957, 6979, 6983 \__cs_generate_variant:wwNw ...
\__coffin_set_pole:Nnx ..... 1878, 1900, 1901
... 6843, 6890, 6957, 6961, 6972, 7231, 7268, 7272, 7280, 7284, 14670, 14805 \__cs_generate_variant_loop:nNwN ...
\__coffin_shift_corner:Nnnn ..... 1924, 1936, 1936, 1950
... 14636, 14727, 14727 \__cs_generate_variant_loop_end:wwwNNnn
\__coffin_shift_pole:Nnnnnn ..... 1926, 1936, 1957
... 14638, 14727, 14735 \__cs_generate_variant_loop_invalid:NNwNNnn
\__coffin_update_B:nnnnnnnnN ..... 1936, 1943, 1979
... 7253, 7261, 7276 \__cs_generate_variant_loop_long:wNNnn
\__coffin_update_T:nnnnnnnnN ..... 1929, 1936, 1966
... 7253, 7257, 7264 \__cs_generate_variant_loop_same:w ...
\__coffin_update_corners:N ..... 1936, 1939, 1952
... 6820, 6841, 6865, 6888, 6984, 6984 \__cs_generate_variant_same:N ...
... 1955, 1994, 1994
\__cs_get_function_name:N 24, 1083, 1083 \__cs_get_function_signature:N ...
... 24, 1083, 1085

```

```

\__cs_parm_from_arg_count:nnF .....
    ..... 913, 1283, 1283, 1327
\__cs_parm_from_arg_count_test:nnF .
    ..... 1283, 1285, 1304
\__cs_show:www .....
    1447, 1458, 1462
\__cs_split_function:NN .....
    ... 24, 895, 908, 995, 996, 1064,
        1070, 1084, 1086, 1314, 1348, 1872
\__cs_split_function_i:w 1064, 1073, 1078
\__cs_split_function_ii:w 1064, 1079, 1080
\__cs_tmp:w .....
    24,
        1214, 1222, 1223, 1224, 1225, 1226,
        1227, 1228, 1229, 1230, 1232, 1233,
        1234, 1235, 1236, 1237, 1238, 1239,
        1240, 1241, 1242, 1243, 1244, 1245,
        1246, 1247, 1248, 1249, 1250, 1251,
        1252, 1253, 1254, 1255, 1338, 1363,
        1364, 1365, 1366, 1367, 1368, 1369,
        1370, 1371, 1372, 1373, 1374, 1375,
        1376, 1377, 1378, 1379, 1380, 1381,
        1382, 1383, 1384, 1385, 1386, 1387,
        1395, 1396, 1397, 1398, 1399, 1400,
        1401, 1402, 1403, 1404, 1405, 1406,
        1407, 1408, 1409, 1410, 1411, 1412,
        1413, 1414, 1415, 1416, 1417, 1418,
        1889, 1904, 2014, 2036, 4452, 4462
\__cs_to_str:N ...
    1055, 1059, 1061, 1062
\__cs_to_str:w .....
    1055, 1058, 1062
\__dim_abs:N .....
    4205, 4207, 4210
\__dim_case_aux:nnn .....
    4281, 4284, 4286
\__dim_case_aux:nw 4281, 4287, 4288, 4292
\__dim_case_end:nw .....
    4281, 4291, 4294
\__dim_compare_<:NNw .....
    4245
\__dim_compare_=:NNw .....
    4245
\__dim_compare_>:NNw .....
    4245
\__dim_compare_aux:NNw ...
    4245, 4259, 4262
\__dim_compare_aux:w ...
    4245, 4247, 4255
\__dim_eval:w 86, 4149, 4150, 4185, 4196,
    4201, 4208, 4214, 4215, 4216, 4222,
    4223, 4224, 4239, 4242, 4247, 4268,
    4270, 4272, 4274, 4276, 4278, 4280,
    4352, 4354, 4358, 4375, 4556, 6542,
    6544, 6546, 6555, 6557, 6559, 6561,
    6645, 6665, 6678, 6693, 6721, 11054
\__dim_eval_end: 86, 4149, 4151, 4185,
    4196, 4201, 4208, 4218, 4226, 4239,
    4242, 4248, 4352, 4354, 4358, 4557,
    6542, 6544, 6546, 6555, 6557, 6559,
    6561, 6645, 6665, 6678, 6693, 6721
\__dim_maxmin:wwN ...
    4205, 4214, 4222, 4228
\__dim_ratio:n .....
    4236, 4237, 4238
\__dim_set_max:NNNn .....
    ... 4558, 4559, 4561, 4563, 4565, 4566
\__dim_strip_bp:n .....
    86, 4353, 4353
\__dim_strip_pt:n ...
    86, 4354, 4355, 4355
\__dim_strip_pt:w .....
    4355, 4358, 4362
\__driver_box_rotate_begin: .....
    14226
\__driver_box_rotate_end: .....
    14228
\__driver_box_scale_begin: .....
    14398
\__driver_box_scale_end: .....
    14400
\__driver_box_use_clip:N .....
    14419
\__driver_color_ensure_current: .....
    ... 7567, 7573, 7576
\__exp_arg_last_unbraced:nn .....
    ... 1789, 1789, 1792, 1796, 1799, 1804
\__exp_arg_next:Nnn ...
    1614, 1615, 1621
\__exp_arg_next:nnn .....
    ... 1614,
        1614, 1623, 1626, 1634, 1638, 1644
\__exp_eval_error_msg:w ...
    1648, 1652, 1661
\__exp_eval_register:N .....
    ... 1639, 1648, 1648,
        1660, 1694, 1712, 1730, 1731, 1738,
        1800, 1813, 1825, 1831, 1840, 1860
\__exp_eval_register:c ...
    1645, 1648,
        1659, 1689, 1706, 1805, 1815, 1865
\__exp_last_two_unbraced:noN .....
    ... 1849, 1850, 1851
\__expl_package_check: .....
    ... 7, 219, 752, 1612,
        2071, 2471, 2595, 3367, 4147, 4578,
        5374, 5784, 6198, 6493, 6731, 7557,
        7590, 8388, 9051, 9736, 13998, 14176
\__expl_primitive:NN .....
    ... 308, 308, 315, 316, 317, 318,
        319, 320, 321, 322, 323, 324, 325,
        326, 327, 328, 329, 330, 331, 332,
        333, 334, 335, 336, 337, 338, 339,
        340, 341, 342, 343, 344, 345, 346,
        347, 348, 349, 350, 351, 352, 353,
        354, 355, 356, 357, 358, 359, 360,
        361, 362, 363, 364, 365, 366, 367,
        368, 369, 370, 371, 372, 373, 374,
        375, 376, 377, 378, 379, 380, 381,
        382, 383, 384, 385, 386, 387, 388,
        389, 390, 391, 392, 393, 394, 395,
        396, 397, 398, 399, 400, 401, 402,
        403, 404, 405, 406, 407, 408, 409,
        410, 411, 412, 413, 414, 415, 416,
        417, 418, 419, 420, 421, 422, 423,
        424, 425, 426, 427, 428, 429, 430,
```

431, 432, 433, 434, 435, 436, 437,
438, 439, 440, 441, 442, 443, 444,
445, 446, 447, 448, 449, 450, 451,
452, 453, 454, 455, 456, 457, 458,
459, 460, 461, 462, 463, 464, 465,
466, 467, 468, 469, 470, 471, 472,
473, 474, 475, 476, 477, 478, 479,
480, 481, 482, 483, 484, 485, 486,
487, 488, 489, 490, 491, 492, 493,
494, 495, 496, 497, 498, 499, 500,
501, 502, 503, 504, 505, 506, 507,
508, 509, 510, 511, 512, 513, 514,
515, 516, 517, 518, 519, 520, 521,
522, 523, 524, 525, 526, 527, 528,
529, 530, 531, 532, 533, 534, 535,
536, 537, 538, 539, 540, 541, 542,
543, 544, 545, 546, 547, 548, 549,
550, 551, 552, 553, 554, 555, 556,
557, 558, 559, 560, 561, 562, 563,
564, 565, 566, 567, 568, 569, 570,
571, 572, 573, 574, 575, 576, 577,
578, 579, 580, 581, 582, 583, 584,
585, 586, 587, 588, 589, 590, 591,
592, 593, 594, 595, 596, 597, 598,
599, 600, 601, 602, 603, 604, 605,
606, 607, 608, 609, 610, 611, 612,
613, 614, 615, 616, 617, 618, 619,
620, 621, 622, 623, 624, 625, 626,
627, 628, 629, 630, 631, 632, 633,
634, 635, 636, 637, 638, 639, 640,
641, 642, 643, 644, 645, 646, 647,
648, 649, 650, 651, 652, 653, 654,
655, 656, 657, 658, 659, 660, 661,
662, 663, 664, 665, 666, 667, 668,
669, 670, 671, 672, 673, 674, 675,
676, 677, 678, 679, 680, 681, 682,
683, 684, 685, 686, 687, 688, 689,
690, 691, 692, 693, 694, 695, 696,
697, 698, 699, 700, 701, 702, 703,
704, 705, 706, 707, 708, 709, 710,
711, 712, 713, 714, 715, 716, 717,
718, 719, 720, 721, 722, 723, 724,
725, 726, 727, 728, 729, 730, 731, 732
_expl_status_pop:w 207
_file_add_path:nN 9102, 9103, 9104
_file_add_path_search:nN
..... 9102, 9108, 9112
_file_input:V 9153
_file_input:n 9155, 9161
_file_input:n__file_input:V .. 9145
_file_input_aux:n 9145, 9159, 9163, 9179
_file_input_aux:o 9145, 9158
_file_input_aux:w 9145, 9157, 9162
_file_name_sanitize:nn
..... 162, 9082, 9082, 9103,
9150, 9181, 9189, 9256, 9266, 9413
_file_path_include:n . 9180, 9181, 9182
_fp 11638, 11645, 13410
_fp_o:ww 11635
fp*o:ww 12018
_fp+_o:ww 11736
_fp-_o:w 12280
_fp-_o:ww 11731
_fp/_o:ww 12128
_fp^_o:ww 13049
_fp_o:w 11627
_fp_abs:NNN 13897,
13897, 13898, 13901, 13907, 13911
_fp_abs_o:w . 12288, 12288, 13897, 13898
_fp_add:NNNn 13852,
13852, 13853, 13854, 13855, 13856
_fp_add_big_i_o:wNww
..... 11807, 11814, 11814, 12877
_fp_add_big_i_o:wNww
..... 11810, 11814, 11822
_fp_add_inf_o:Nww . 11751, 11771, 11771
_fp_add_normal_o:Nww 11750, 11791, 11791
_fp_add_npos_o:NnwNnw
..... 11794, 11800, 11800
_fp_add_return_i_o:Nww
..... 11753, 11759, 11759, 11764
_fp_add_significand_carry_o:wwwNN
..... 11847, 11862, 11862
_fp_add_significand_no_carry_o:wwwNN
..... 11849, 11852, 11852
_fp_add_significand_o:NnnwnnnnN ..
..... 11817, 11825, 11830, 11830
_fp_add_significand_pack:NNNNNNNN ..
..... 11830, 11834, 11837
_fp_add_significand_test_o:N ..
..... 11830, 11832, 11844
_fp_add_zeros_o:Nww 11749, 11761, 11761
_fp_and_return:wNw 11635, 11641, 11647
_fp_array_count:n ... 9978, 9978, 11108
_fp_array_count_loop:Nw
..... 9978, 9981, 9985, 9986
_fp_array_to_clist:n 10280, 13799, 13799
_fp_array_to_clist_loop:Nw
..... 13799, 13806, 13811, 13821

```

\__fp_assign_to:nNNNn . 13931, 13938,
    13939, 13940, 13941, 13942, 13943
\__fp_assign_to_i:wNNNn . . . . .
    . . . . . 13931, 13945, 13948
\__fp_assign_to_ii:NnNNN . . . . .
    . . . . . 13931, 13950, 13954
\__fp_basics_pack_high:NNNNNw . . .
    . . . . . 11705, 11712, 11855,
    12006, 12107, 12119, 12259, 12497
\__fp_basics_pack_high_carry:w . . .
    . . . . . 11705, 11715, 11719
\__fp_basics_pack_low:NNNNNw . . .
    . . . . . 11705, 11705, 11857,
    12008, 12109, 12121, 12261, 12499
\__fp_basics_pack_weird_high:NNNNNNNNw
    . . . . . 11721, 11729, 11866, 12270
\__fp_basics_pack_weird_low:NNNNw . .
    . . . . . 11721, 11721, 11868, 12272
\__fp_case_return:nw . . . 9933, 9933,
    9947, 9949, 10340, 12810, 13600,
    13650, 13718, 13720, 13721, 13764
\__fp_case_return_i_o:ww . . . .
    9940, 9940, 11752, 11766, 11775, 12051
\__fp_case_return_ii_o:ww . . . .
    . . . 9940, 9942, 12052, 13098, 13116
\__fp_case_return_o:Nw . . . . 9934,
    9934, 12845, 12850, 12853, 13053,
    13058, 13080, 13089, 13302, 13332
\__fp_case_return_o:Nww . . . .
    . . . . 9938, 9938, 12053, 12054,
    12057, 12058, 13100, 13109, 13112
\__fp_case_return_same_o:w . . . .
    . . . . . 9936, 9936, 12631,
    12857, 13077, 13287, 13295, 13310,
    13325, 13340, 13347, 13355, 13370
\__fp_case_use:nw . 9932, 9932, 11777,
    12049, 12050, 12055, 12056, 12136,
    12139, 12624, 12627, 13083, 13289,
    13294, 13304, 13309, 13319, 13324,
    13334, 13339, 13349, 13354, 13364,
    13369, 13603, 13614, 13653, 13663
\__fp_cfs_round_loop:N . . . 10814,
    10814, 10819, 10852, 10876, 10904
\__fp_cfs_round_up:N 10822, 10830, 10834
\__fp_chk:w . . . . . 9747,
    9748, 9751, 9760, 9761, 9762, 9763,
    9764, 9766, 9767, 9770, 9776, 9780,
    9800, 9803, 9804, 9814, 9824, 9837,
    9856, 9944, 10120, 10125, 10283,
    10292, 10294, 11036, 11453, 11478,
    11479, 11587, 11595, 11598, 11609,
    11610, 11618, 11619, 11627, 11638,
    11641, 11653, 11678, 11737, 11756,
    11757, 11759, 11760, 11761, 11769,
    11772, 11788, 11789, 11791, 11800,
    11876, 12027, 12061, 12062, 12065,
    12144, 12280, 12284, 12288, 12292,
    12621, 12633, 12635, 12842, 12859,
    12861, 13050, 13069, 13071, 13072,
    13074, 13086, 13091, 13093, 13118,
    13119, 13121, 13121, 13137, 13222, 13235,
    13237, 13284, 13297, 13299, 13312,
    13314, 13327, 13329, 13342, 13344,
    13357, 13359, 13372, 13384, 13403,
    13412, 13596, 13621, 13624, 13646,
    13670, 13673, 13714, 13737, 13787,
    13788, 13888, 13895, 13948, 13957
\__fp_compare:wNNNw . . . . . 11245
\__fp_compare_aux:wn 11461, 11464, 11472
\__fp_compare_back:ww . . . .
    . . . 11332, 11474, 11477, 11477, 11608
\__fp_compare_nan:w . . . .
    . . . . . 11477, 11482, 11483, 11504
\__fp_compare_npos:nwnw . . . .
    . . . . . 11488, 11505, 11505, 11878
\__fp_compare_return:w 11448, 11450, 11453
\__fp_compare_significand:nnnnnnnn . .
    . . . . . 11505, 11508, 11513
\__fp_cos_o:w . . . . 13299, 13299, 13941
\__fp_cot_o:w . . . . . 13359, 13359
\__fp_cot_zero_o:Nnw . . . .
    . . . . . 13317, 13359, 13362, 13374
\__fp_csc_o:w . . . . . 13314, 13314
\__fp_decimate:nNnnn . . . .
    . . . . . 9886, 9886, 9960, 10296, 11816,
    11824, 11903, 12893, 12897, 13679
\__fp_decimate:_Nnnnn . . . . . 9898, 9898
\__fp_decimate_i:Nnnnn . . . . . 9902
\__fp_decimate_ii:Nnnnn . . . . . 9902
\__fp_decimate_iii:Nnnnn . . . . . 9902
\__fp_decimate_iv:Nnnnn . . . . . 9902
\__fp_decimate_ix:Nnnnn . . . . . 9902
\__fp_decimate_pack:nnnnnnnnnw . .
    . . . . . 9909, 9928, 9928
\__fp_decimate_pack_ii:nnnnnw . .
    . . . . . 9929, 9930
\__fp_decimate_tiny:Nnnnn . . . . . 9898, 9900
\__fp_decimate_v:Nnnnn . . . . . 9902
\__fp_decimate_vi:Nnnnn . . . . . 9902
\__fp_decimate_vii:Nnnnn . . . . . 9902

```

$\backslash\text{--fp_decimate_viii:Nnnnn}$ [9902](#) $\backslash\text{--fp_exp_Taylor_loop:www}$
 $\backslash\text{--fp_decimate_x:Nnnnn}$ [9902](#) [12910](#), [12920](#), [12921](#), [12930](#)
 $\backslash\text{--fp_decimate_xi:Nnnnn}$ [9902](#) $\backslash\text{--fp_exp_after_array_f:w}$
 $\backslash\text{--fp_decimate_xii:Nnnnn}$ [9902](#) [9857](#), [9857](#), [9860](#),
 $\backslash\text{--fp_decimate_xiii:Nnnnn}$ [9902](#) [11155](#), [11657](#), [11668](#), [11691](#), [11699](#)
 $\backslash\text{--fp_decimate_xiv:Nnnnn}$ [9902](#) $\backslash\text{--fp_exp_after_f:nw}$
 $\backslash\text{--fp_decimate_xv:Nnnnn}$ [9902](#) [9804](#), [9824](#), [10448](#), [10944](#), [11035](#)
 $\backslash\text{--fp_decimate_xvi:Nnnnn}$ [9902](#) $\backslash\text{--fp_exp_after_normal:Nwwww}$ [9846](#), [9854](#)
 $\backslash\text{--fp_div_npos_o:Nww}$ [12133](#), [12143](#), [12143](#) $\backslash\text{--fp_exp_after_normal:nNNw}$
 $\backslash\text{--fp_div_significand_calc:wnnnnnnnn}$
. [12160](#), [12169](#), [12169](#), [12215](#), [12703](#), [12710](#) $\backslash\text{--fp_exp_after_o:nw}$ [9804](#), [9814](#)
 $\backslash\text{--fp_div_significand_calc_i:wnnnnnnnn}$
. [12169](#), [12172](#), [12177](#) $\backslash\text{--fp_exp_after_o:w}$
 $\backslash\text{--fp_div_significand_calc_ii:wnnnnnnnn}$
. [12169](#), [12174](#), [12194](#) [9804](#), [9804](#), [9937](#), [9941](#), [9943](#),
 $\backslash\text{--fp_div_significand_i_o:wnnw}$
. [12150](#), [12156](#), [12156](#) [10290](#), [10334](#), [10352](#), [11626](#), [11643](#),
 $\backslash\text{--fp_div_significand_ii:wwn}$
. [12164](#), [12165](#), [12166](#), [12211](#), [12211](#) [11760](#), [12282](#), [12290](#), [13234](#), [13403](#)
 $\backslash\text{--fp_div_significand_iii:wwnnnnn}$
. [12167](#), [12218](#), [12218](#) $\backslash\text{--fp_exp_after_special:nNNw}$
 $\backslash\text{--fp_div_significand_iv:wwnnnnnnn}$
. [12221](#), [12226](#), [12226](#) [9809](#), [9819](#), [9829](#), [9834](#), [9834](#)
 $\backslash\text{--fp_div_significand_large_o:wwwNNNNwN}$
. [12252](#), [12266](#), [12266](#) $\backslash\text{--fp_exp_after_stop_f:nw}$ [9857](#), [9863](#)
 $\backslash\text{--fp_div_significand_pack:NNN}$ [12213](#),
. [12246](#), [12246](#), [12690](#), [12708](#), [12716](#) $\backslash\text{--fp_exp_large:w}$ [12937](#),
 $\backslash\text{--fp_div_significand_small_o:wwwNNNNwN}$
. [12250](#), [12256](#), [12256](#) [12946](#), [12951](#), [12952](#), [12953](#), [12954](#),
 $\backslash\text{--fp_div_significand_test_o:w}$
. [12158](#), [12247](#), [12247](#) [12955](#), [12956](#), [12957](#), [12958](#), [12959](#),
 $\backslash\text{--fp_div_significand_v:NN}$
. [12231](#), [12233](#), [12236](#) [12967](#), [12968](#), [12969](#), [12970](#), [12971](#),
 $\backslash\text{--fp_div_significand_v:NNw}$ [12226](#) [12972](#), [12973](#), [12974](#), [12975](#), [12983](#),
 $\backslash\text{--fp_div_significand_vi:Nw}$
. [12226](#), [12229](#), [12237](#) [12984](#), [12985](#), [12986](#), [12987](#), [12988](#),
 $\backslash\text{--fp_division_by_zero_o:NNww}$ [10092](#),
. [10132](#), [10136](#), [12137](#), [12140](#), [13085](#) [12989](#), [12990](#), [12991](#), [12999](#), [13000](#),
 $\backslash\text{--fp_division_by_zero_o:Nnw}$ [10084](#),
. [10132](#), [10135](#), [12628](#), [13378](#), [13380](#) [13001](#), [13002](#), [13003](#), [13004](#), [13005](#),
 $\backslash\text{--fp_error:nffn}$ [10061](#), [10095](#), [10123](#), [10145](#) [13006](#), [13007](#), [13015](#), [13016](#), [13017](#),
 $\backslash\text{--fp_error:nnfn}$ [10053](#), [10070](#), [10087](#), [10145](#) [13018](#), [13019](#), [13020](#), [13021](#), [13022](#),
 $\backslash\text{--fp_error:nnnn}$. . . [10145](#), [10145](#), [10147](#) [13023](#), [13031](#), [13032](#), [13033](#), [13034](#),
 $\backslash\text{--fp_exp_Taylor:Nnnwn}$
. [12894](#), [12910](#), [12910](#), [13046](#) [13035](#), [13036](#), [13037](#), [13038](#), [13039](#)
 $\backslash\text{--fp_exp_Taylor_break:Nww}$
. [12910](#), [12924](#), [12935](#) $\backslash\text{--fp_exp_large:wN}$ [12937](#), [13028](#)
 $\backslash\text{--fp_exp_Taylor_ii:ww}$ [12916](#), [12919](#) $\backslash\text{--fp_exp_large_after:wwn}$
. [12937](#), [13042](#), [13044](#) $\backslash\text{--fp_exp_large_i:wN}$ [12937](#), [13010](#), [13012](#)
 $\backslash\text{--fp_exp_large_ii:wN}$ [12937](#), [12994](#), [12996](#) $\backslash\text{--fp_exp_large_iii:wN}$ [12937](#), [12978](#), [12980](#)
 $\backslash\text{--fp_exp_large_iv:wN}$ [12937](#), [12962](#), [12964](#) $\backslash\text{--fp_exp_large_v:wN}$ [12937](#), [12948](#), [13221](#)
 $\backslash\text{--fp_exp_normal:w}$ [12847](#), [12861](#), [12861](#) $\backslash\text{--fp_exp_o:w}$ [12842](#), [12842](#), [13938](#)
 $\backslash\text{--fp_exp_overflow:}$ [12883](#), [12908](#) $\backslash\text{--fp_exp_pos:NNww}$ [12864](#), [12866](#), [12869](#)
 $\backslash\text{--fp_exp_pos:NnwN}$ [12861](#) $\backslash\text{--fp_exp_pos_large:NnnNwn}$
. [12898](#), [12937](#), [12937](#) $\backslash\text{--fp_expand:n}$ [9987](#), [9987](#), [13803](#)
 $\backslash\text{--fp_expand_loop:nwnN}$
. [9987](#), [9989](#), [9991](#), [9994](#) $\backslash\text{--fp_exponent:w}$ [9780](#), [9780](#), [13984](#), [13989](#)

`_fp_fixed_add:wwn` [12339](#),
[12339](#), [12784](#), [12792](#), [12803](#), [12821](#)
`_fp_fixed_add_after:NNNNNwn` [12339](#), [12343](#), [12357](#)
`_fp_fixed_add_i:Nnnnnwnn` [12339](#), [12339](#), [12340](#), [12341](#)
`_fp_fixed_add_ii:nnNnnwn` [12339](#), [12347](#), [12349](#)
`_fp_fixed_add_one:wn` [12302](#), [12302](#), [12606](#), [12927](#), [12936](#)
`_fp_fixed_add_pack:NNNNNwn` [12339](#), [12345](#), [12352](#), [12355](#)
`_fp_fixed_continue:wn` [12301](#), [12301](#), [12950](#), [12966](#),
[12982](#), [12998](#), [13014](#), [13030](#), [13197](#)
`_fp_fixed_div_int:wnN` [12308](#), [12308](#), [12783](#), [12926](#)
`_fp_fixed_div_int_after:Nw` [12308](#), [12310](#), [12338](#)
`_fp_fixed_div_int_i:wnN` [12308](#), [12313](#), [12321](#), [12333](#)
`_fp_fixed_div_int_ii:wnn` [12308](#), [12314](#),
[12315](#), [12316](#), [12317](#), [12318](#), [12328](#)
`_fp_fixed_div_int_iii:wnm` [12308](#), [12319](#), [12336](#)
`_fp_fixed_div_int_pack:Nw` [12308](#), [12331](#), [12337](#)
`_fp_fixed_div_to_float:ww` [12502](#), [12512](#), [13568](#)
`_fp_fixed_dtf_approx:n` [12509](#), [12523](#), [12567](#)
`_fp_fixed_dtf_approx_ii:wnn` [12569](#), [12573](#)
`_fp_fixed_dtf_approx_iii:NNNNNw` [12576](#), [12581](#)
`_fp_fixed_dtf_epsilon:wN` [12585](#), [12590](#)
`_fp_fixed_dtf_epsilon_ii:NNNNNww` [12594](#), [12601](#)
`_fp_fixed_dtf_epsilon_pack:NNNNNw` [12596](#), [12599](#)
`_fp_fixed_dtf_no_zero:Nwn` [12508](#), [12517](#), [12522](#), [12526](#), [12528](#)
`_fp_fixed_dtf_zeros:NN` [12533](#), [12538](#), [12545](#), [12548](#)
`_fp_fixed_dtf_zeros:wNnnnnnn` [12506](#), [12515](#), [12520](#), [12527](#)
`_fp_fixed_dtf_zeros_end:wNww` [12543](#), [12547](#)
`_fp_fixed_dtf_zeros_ii:ww` [12555](#), [12558](#)
`_fp_fixed_dtf_zeros_iii:ww` [12563](#), [12566](#)
`_fp_fixed_inv_to_float:wN` [12502](#),
[12866](#), [13133](#), [13322](#), [13337](#)
`_fp_fixed_mul:wwn` [12359](#), [12359](#), [12584](#),
[12586](#), [12587](#), [12603](#), [12607](#), [12785](#),
[12795](#), [12835](#), [12928](#), [12947](#), [13047](#),
[13143](#), [13478](#), [13521](#), [13532](#), [13552](#)
`_fp_fixed_mul_add:wwnn` [12387](#), [12387](#)
`_fp_fixed_mul_add_i:Nnnnnwnnn` [12393](#), [12403](#), [12413](#), [12417](#), [12417](#)
`_fp_fixed_mul_add_ii:nnnnwnnnn` [12428](#), [12430](#), [12430](#)
`_fp_fixed_mul_add_iii:nnnnwnnwN` [12435](#), [12441](#), [12441](#)
`_fp_fixed_mul_after:wn` [12307](#), [12307](#),
[12361](#), [12389](#), [12399](#), [12409](#), [13160](#)
`_fp_fixed_mul_i:nnnnnnnn` [12359](#), [12379](#), [12381](#)
`_fp_fixed_mul_one_minus_mul:wwn` [12387](#)
`_fp_fixed_mul_sub:wwn` [12387](#), [12397](#), [13500](#), [13502](#),
[13503](#), [13504](#), [13505](#), [13506](#), [13507](#),
[13508](#), [13509](#), [13512](#), [13514](#), [13515](#),
[13516](#), [13517](#), [13518](#), [13519](#), [13520](#),
[13546](#), [13548](#), [13549](#), [13550](#), [13551](#),
[13554](#), [13556](#), [13557](#), [13558](#), [13559](#)
`_fp_fixed_one_minus_mul:wwn` [12407](#)
`_fp_fixed_sub:wwn` [12339](#), [12340](#),
[12801](#), [12817](#), [12829](#), [13461](#), [13474](#)
`_fp_fixed_to_float:Nw` [12446](#), [12446](#), [12810](#)
`_fp_fixed_to_float:wN` [12446](#), [12446](#), [12447](#), [12588](#), [12830](#),
[12840](#), [12864](#), [13129](#), [13292](#), [13307](#)
`_fp_fixed_to_float_pack:ww` [12478](#), [12488](#)
`_fp_fixed_to_float_round_up:wnnnnw` [12491](#), [12495](#)
`_fp_fixed_to_float_zero:w` [12474](#), [12483](#)
`_fp_fixed_to_loop:N` [12451](#), [12461](#), [12465](#)
`_fp_fixed_to_loop_end:w` [12467](#), [12471](#)
`_fp_from_dim:Nw` [13756](#), [13767](#), [13771](#), [13777](#)
`_fp_from_dim_ii:wNNnnnnnn` [13756](#), [13779](#), [13782](#)
`_fp_from_dim_iii:wnnnnwN` [13756](#), [13783](#), [13784](#)
`_fp_from_dim_test:N` [13756](#), [13758](#), [13761](#)
`_fp_if_undefined:w` [13887](#), [13888](#)
`_fp_if_zero:w` [13894](#), [13895](#)

```

\__fp_inf_fp:N ..... 9766, 9767, 10108
\__fp_infix_compare:N . 11245, 11247,
   11252, 11257, 11267, 11275, 11283
\__fp_invalid_operation:nnw .....
   ..... 10050, 10132, 10132,
   10144, 13605, 13616, 13655, 13665
\__fp_invalid_operation_o:Nww .....
   ..... 10058, 10132, 10133,
   11780, 11783, 12055, 12056, 13228
\__fp_invalid_operation_o:nw .....
   ..... 10143, 10143, 12624, 13294,
   13309, 13324, 13339, 13354, 13369
\__fp_invalid_operation_tl_o:nf .....
   ..... 10067, 10132, 10134, 10279
\__fp_ln_Taylor:wwNw 12775, 12776, 12776
\__fp_ln_Taylor_break:w .. 12781, 12792
\__fp_ln_Taylor_loop:www .....
   ..... 12777, 12778, 12787
\__fp_ln_c:NwNw ... 12767, 12798, 12798
\__fp_ln_div_after:Nw .... 12671, 12719
\__fp_ln_div_i:w .... 12692, 12701
\__fp_ln_div_ii:wwn .....
   ..... 12695, 12696, 12697, 12698, 12706
\__fp_ln_div_vi:wwn .... 12699, 12714
\__fp_ln_exponent:wn 12647, 12807, 12807
\__fp_ln_exponent_one:ww .. 12812, 12826
\__fp_ln_exponent_small:NNww .....
   ..... 12815, 12819, 12832
\__fp_ln_npos_o:w .. 12633, 12635, 12635
\__fp_ln_o:w ..... 12621, 12621, 13939
\__fp_ln_significand:NNNNnnnN .....
   ..... 12646, 12649, 12649, 13141
\__fp_ln_square_t_after:w .. 12743, 12774
\__fp_ln_square_t_pack:NNNNNw .....
   ..... 12745, 12747, 12749, 12751, 12772
\__fp_ln_t_large>NNw 12724, 12731, 12741
\__fp_ln_t_small:Nw .... 12722, 12729
\__fp_ln_twice_t_after:w .. 12755, 12771
\__fp_ln_twice_t_pack:Nw .... 12757,
   12759, 12761, 12763, 12765, 12770
\__fp_ln_x_ii:wnnnn . 12651, 12669, 12669
\__fp_ln_x_iii:NNNNNw .... 12678, 12682
\__fp_ln_x_iii_var:NNNNNw . 12676, 12683
\__fp_ln_x_iv:wnnnnnnnn .. 12674, 12688
\__fp_max_fp:N ..... 9768, 9774
\__fp_max_o:w ..... 11082, 11581, 11581
\__fp_min_fp:N ..... 9768, 9768
\__fp_min_o:w ..... 11083, 11581, 11589
\__fp_minmax_break_o:w .....
   ..... 11587, 11595, 11625, 11625
\__fp_minmax_i:ww .....
   ..... 11602, 11614, 11621, 11621
\__fp_minmax_ii:ww .....
   ..... 11604, 11612, 11621, 11623
\__fp_minmax_loop:Nww .....
   ..... 11583, 11591, 11597, 11597, 11617
\__fp_mul:NNNn .. 13917, 13917, 13918,
   13919, 13920, 13921, 13922, 13923
\__fp_mul_cases_o:NnNnww .....
   ..... 12020, 12026, 12130
\__fp_mul_cases_o:nNnnww .... 12026
\__fp_mul_npos_o:Nww .....
   ..... 12023, 12064, 12064, 13786
\__fp_mul_significand ..... 12603
\__fp_mul_significand_drop:NNNNNw ..
   ..... 12073,
   12082, 12084, 12086, 12088, 12092
\__fp_mul_significand_keep:NNNNNw ..
   ..... 12073, 12078, 12080, 12094
\__fp_mul_significand_large_f:NwwNNNN
   ..... 12101, 12105, 12105
\__fp_mul_significand_o:nnnnNnnnn .. .
   ..... 12071, 12073, 12073
\__fp_mul_significand_small_f:NNwwN
   ..... 12099, 12116, 12116
\__fp_mul_significand_test_f:NNN ...
   ..... 12075, 12096, 12096
\__fp_neg_sign:N ..... 9789, 9789, 11734
\__fp_overflow:w ..... 9796, 10132, 10137
\__fp_pack:NNNNNw .....
   ..... 9864, 9867, 13440, 13442, 13444
\__fp_pack:NNNNNwn .... 9864, 9868,
   12363, 12366, 12369, 12372, 12375,
   13162, 13165, 13168, 13171, 13174
\__fp_pack_Bigg:NNNNNNw .....
   ..... 9877, 9880, 12183,
   12186, 12189, 12200, 12203, 12206
\__fp_pack_big:NNNNNNNw .... 9870, 9873
\__fp_pack_big:NNNNNNNwn .....
   ..... 9870, 9875, 12391, 12401,
   12411, 12420, 12423, 12426, 12433
\__fp_pack_eight:wNNNNNNNN .. .
   ..... 9884, 9884, 11999
\__fp_pack_twice_four:wNNNNNNNNN .. .
   ..... 9882, 9882, 10327,
   10328, 11942, 11943, 12476, 12477,
   12560, 12561, 12562, 12913, 12914,
   12915, 13417, 13418, 13419, 13779
\__fp_parse:n .....
   ..... 10358, 10437, 10916, 10916, 11451,

```

11465, 11475, 13589, 13644, 13712, *_fp_parse_exponent:Nw*
 13749, 13794, 13796, 13798, 13830, *..... 10623, 10636, 10685,*
 13832, 13834, 13857, 13924, 13946 *10713, 10718, 10718, 10866, 10907*
_fp_parse_after:ww 10916, 10919, 10925 *_fp_parse_exponent_body:N*
_fp_parse_apply_binary:NwNwN *..... 10749, 10753, 10753*
..... 10992, 10992, 11180 *_fp_parse_exponent_digits:N*
_fp_parse_apply_compare:NwNNNNwN *..... 10757, 10769, 10769, 10773*
..... 11316, 11324 *_fp_parse_exponent_ii:N*
_fp_parse_apply_round:NNwN 11097, 11106 *..... 10723, 10726, 10733*
_fp_parse_apply_unary:NNwN *_fp_parse_exponent_keep:N* 10780
..... 11007, 11012, 11063, 11123 *_fp_parse_exponent_keep:NTF*
_fp_parse_apply_unary_array:NNwN *..... 10760, 10780*
..... 11007, 11007, 11075 *_fp_parse_exponent_sign:N*
_fp_parse_compare:NNNNNNw *..... 10739, 10743, 10743, 10746*
..... 11245, 11278, 11286, 11303 *_fp_parse_infix:NN*
_fp_parse_compare_end:NNNN *10443, 10512, 10533, 10944, 10949,*
..... 11245, 11298, 11312 *11022, 11035, 11055, 11156, 11379*
_fp_parse_compare_expand:NNNNNw *_fp_parse_infix_*
..... 11245, 11294, 11295, 11296, 11297, 11301 *10982, 11153, 11204, 11208, 11220,*
_fp_parse_digits_:N 10394, 10395 *11223, 11232, 11235, 11342, 11353,*
_fp_parse_digits_i:N 10376, 10393 *11375, 11385, 11391, 11393, 11398*
_fp_parse_digits_ii:N 10376, 10392 *_fp_parse_infix_Nw* 11217
_fp_parse_digits_iii:N 10376, 10391 *_fp_parse_infix_)N* 11373
_fp_parse_digits_iv:N 10376, 10390 *_fp_parse_infix_*:N* 11202
_fp_parse_digits_v:N 10376, 10389 *_fp_parse_infix_+:N* 11192
_fp_parse_digits_vi:N 10376, 10388, 10620, 10668 *_fp_parse_infix_-:N* 11192
_fp_parse_digits_vii:N 10376, 10607, 10657 *_fp_parse_infix_/:N* 11192
_fp_parse_exp_after_?_f:nw 10439 *_fp_parse_infix_::N* 11340
_fp_parse_exp_after_f:nw 10439, 10448 *_fp_parse_infix_N* 11245
_fp_parse_exp_after_mark_f:nw 10439, 10449 *_fp_parse_infix_<:N* 11245
_fp_parse_expand:w 10358, 10358, 10360, *_fp_parse_infix_>:N* 11245
 10385, 10444, 10479, 10497, 10562, *_fp_parse_infix_?:N* 11340
 10564, 10584, 10586, 10608, 10625, *_fp_parse_infix_\meta{operation}:N* 10358
 10638, 10658, 10688, 10716, 10718, *_fp_parse_infix^:N* 11202
 10731, 10747, 10767, 10778, 10828, *_fp_parse_infix_after_operand:NwN*
 10839, 10868, 10877, 10909, 10922, *..... 10425, 10543, 10942, 10942, 11168*
 10988, 11068, 11079, 11101, 11104, *_fp_parse_infix_and:N* 11192, 11239
 11105, 11132, 11149, 11158, 11184, *_fp_parse_infix_check:NNN* 10968, 10978
 11225, 11237, 11263, 11310, 11322, *_fp_parse_infix_comma:w* 11401, 11411
 11349, 11365, 11381, 11408, 11661 *_fp_parse_infix_comma_gobble:w* 11404, 11413
_fp_parse_exponent:N 10434, 10599, 10721, *_fp_parse_infix_end:N*
 10723, 10723, 10882, 10891, 10914 *..... 10927, 10956, 11389, 11390*
_fp_parse_excl_aux:NN 11245, 11262, 11265 *_fp_parse_infix_excl_error:*
_fp_parse_excl_error: 11245, 11270, 11279

```

\__fp_parse_infix_juxtapose:N .....
    ..... 10959, 10966, 11194
\__fp_parse_infix_mul:N .. 11192, 11211
\__fp_parse_infix_or:N ... 11192, 11227
\__fp_parse_large:N . 10569, 10653, 10653
\__fp_parse_large_leading:wwNN .....
    ..... 10655, 10660, 10660
\__fp_parse_large_round:NN .....
    ..... 10696, 10841, 10841
\__fp_parse_large_round_after:wNN ...
    ..... 10850, 10870
\__fp_parse_large_round_after_ii:wN
    ..... 10873, 10886
\__fp_parse_large_round_dot_test:NNw
    ..... 10854, 10859
\__fp_parse_large_trailing:wwNN .....
    ..... 10666, 10690, 10690
\__fp_parse_letters:NN 10469, 10482, 10494
\__fp_parse_lparen_after:NwN 11141, 11151
\__fp_parse_operand:Nw .....
    ..... 10358,
        10396, 10396, 10538, 10936, 11118
\__fp_parse_operand_digit:NN .....
    ..... 10409, 10541, 10541
\__fp_parse_operand_other:NN .....
    ..... 10412, 10462, 10462
\__fp_parse_operand_other_prefix_aux:NNN
    ..... 10473, 10517
\__fp_parse_operand_other_prefix_unknown:NNN
    ..... 10520, 10525
\__fp_parse_operand_other_word_aux:Nw
    ..... 10466, 10504
\__fp_parse_operand_register:NN .....
    ..... 10404, 10417, 10423
\__fp_parse_operand_register_aux:www
    ..... 10417, 10428, 10436
\__fp_parse_operand_relax:NN .....
    ..... 10401, 10439, 10439
\__fp_parse_pack_carry:w .....
    ..... 10640, 10648, 10651
\__fp_parse_pack_leading:NNNNNww ...
    ..... 10603, 10640, 10645, 10663
\__fp_parse_pack_trailing:NNNNNNww .
    ..... 10613,
        10640, 10640, 10682, 10693, 10700
\__fp_parse_prefix_(:Nw .....
    ..... 11137
\__fp_parse_prefix_+:Nw .....
    ..... 11118
\__fp_parse_prefix_-:Nw .....
    ..... 11119
\__fp_parse_prefix_.:Nw .....
    ..... 11166
\__fp_parse_prefix_:Nw .....
    ..... 11119
\__fp_parse_return_semicolon:w .....
    ..... 10359, 10359, 10383,
        10729, 10761, 10776, 10826, 10837
\__fp_parse_round:Nw .....
    ..... 11087, 11090, 11093, 11103
\__fp_parse_small:N . 10590, 10601, 10601
\__fp_parse_small_leading:wwNN .....
    ..... 10605, 10610, 10610, 10672
\__fp_parse_small_round:NN .....
    ..... 10632, 10862, 10893, 10893
\__fp_parse_small_round_after:wN ...
    ..... 10902, 10911
\__fp_parse_small_trailing:wwNN .....
    ..... 10618, 10627, 10627, 10704
\__fp_parse_stop_until:N .....
    ..... 10941,
        11162, 11187, 11282, 11352, 11368,
        11384, 11390, 11397, 11412, 11416
\__fp_parse_strim_end:w .....
    ..... 10575, 10582, 10586
\__fp_parse_strim_zeros:N .....
    ..... 10556, 10575, 10575, 10579, 11172
\__fp_parse_trim_end:w 10549, 10559, 10564
\__fp_parse_trim_zeros:N .....
    ..... 10547, 10549, 10549, 10552
\__fp_parse_unary_type:N .....
    ..... 11017, 11065, 11125
\__fp_parse_until:Nw .. 10358, 10921,
    ..... 10930, 10930, 11067, 11079, 11101,
        11128, 11130, 11145, 11147, 11183,
        11322, 11348, 11364, 11407, 11660
\__fp_parse_until_test:NwN .....
    ..... 10930, 10933, 10940, 10942,
        10994, 11326, 11665, 11688, 11696
\__fp_parse_word_abs:N .....
    ..... 11058
\__fp_parse_word_bp:N .....
    ..... 11019
\__fp_parse_word_cc:N .....
    ..... 11019
\__fp_parse_word_cm:N .....
    ..... 11019
\__fp_parse_word_cos:N .....
    ..... 11058
\__fp_parse_word_cot:N .....
    ..... 11058
\__fp_parse_word_csc:N .....
    ..... 11058
\__fp_parse_word_dd:N .....
    ..... 11019
\__fp_parse_word_deg:N .....
    ..... 11019
\__fp_parse_word_em:N .....
    ..... 11019
\__fp_parse_word_ex:N .....
    ..... 11019
\__fp_parse_word_exp:N .....
    ..... 11058
\__fp_parse_word_false:N .....
    ..... 11019
\__fp_parse_word_in:N .....
    ..... 11019
\__fp_parse_word_inf:N .....
    ..... 11019
\__fp_parse_word_ln:N .....
    ..... 11058
\__fp_parse_word_max:N ... 11071, 11082

```

```

\__fp_parse_word_min:N . . . . . 11071, 11083 \__fp_round_normal:NwNNnw . . . . .
\__fp_parse_word_mm:N . . . . . 11019 . . . . . 10275, 10286, 10294
\__fp_parse_word_nan:N . . . . . 11019 \__fp_round_normal_end:wwNnn . . . .
\__fp_parse_word_nc:N . . . . . 11019 . . . . . 10275, 10329, 10332
\__fp_parse_word_nd:N . . . . . 11019 \__fp_round_normal_ii:NnnwNNnn . . .
\__fp_parse_word_pc:N . . . . . 11019 . . . . . 10275, 10297, 10299
\__fp_parse_word_pi:N . . . . . 11019 \__fp_round_normal_iii:NNwNnn . . .
\__fp_parse_word_pt:N . . . . . 11019 . . . . . 10275, 10301, 10321
\__fp_parse_word_round:N . . . . . 11084, 11084 \__fp_round_pack:Nw . 10275, 10305, 10319
\__fp_parse_word_sec:N . . . . . 11058 \__fp_round_places>NNn . . . . . 13963,
\__fp_parse_word_sin:N . . . . . 11058 . . . . . 13964, 13966, 13967, 13983, 13988
\__fp_parse_word_sp:N . . . . . 11019 \__fp_round_return_one: . . . . .
\__fp_parse_word_tan:N . . . . . 11058 . . . . . 10186, 10192, 10202,
\__fp_parse_word_true:N . . . . . 11019 . . . . . 10210, 10214, 10252, 10260, 10268
\__fp_parse_zero: . . . . . 10571, 10592, 10596, 10596 \__fp_round_s:NNNw . . . . .
\__fp_pow_B:wwN . . . . . 13144, 13179 . . . . . 10221, 10221, 10845, 10897
\__fp_pow_C_neg:w . . . . . 13182, 13199 \__fp_round_special:NwwNnn . . . .
\__fp_pow_C_overflow:w 13187, 13194, 13215 . . . . . 10275, 10324, 10337
\__fp_pow_C_pack:w . . . . . 13201, 13209, 13220 \__fp_round_special_aux:Nw . . .
\__fp_pow_C_pos:w . . . . . 13185, 13204 . . . . . 10275, 10343, 10350
\__fp_pow_C_pos_loop:wN . . . . . 13205, 13206, 13213 \__fp_round_to_nearest:NNN . . .
\__fp_pow_exponent:Nwnnnnnwn . . . . . 13150, 13153, 13158 . . . . . 10186, 10207, 10220,
\__fp_pow_exponent:wnN . . . . . 13142, 13147 . . . . . 10273, 11099, 11104, 13754, 13974
\__fp_pow_neg:www . . . . . 13060, 13222, 13222 \__fp_round_to_nearest_neg:NNN . . .
\__fp_pow_neg_case:w 13224, 13237, 13237 . . . . . 10248, 10273, 10274
\__fp_pow_neg_case_aux:NNNNNNNNw . . . . . 13237, 13252, 13259, 13269 \__fp_round_to_ninf:NNN . . .
\__fp_pow_neg_case_aux:nmmnm . . . . . 13237, 13241, 13245 . . . . . 10186, 10188, 11093
\__fp_pow_normal:ww . . . . . 13065, 13093, 13093 \__fp_round_to_ninf_neg:NNN 10248, 10248
\__fp_pow_npos:Nww . . . . . 13104, 13121, 13121 \__fp_round_to_pinf:NNN . . .
\__fp_pow_npos_aux:NNnww . . . . . 13127, 13131, 13137, 13137 . . . . . 10186, 10198, 11087
\__fp_pow_zero_or_inf:ww . . . . . 13067, 13074, 13074 \__fp_round_to_pinf_neg:NNN 10248, 10264
\__fp_reverse_args:Nww 9746, 9746, 13566 \__fp_round_to_zero:NNN . . .
\__fp_round:NNN . . . . . 10186, 10220, 10223, 11859, 11870, 12111, 12123, 12263, 12274 . . . . . 10186, 10197, 11090
\__fp_round:Nwn . . . . . 10275, 10277, 10283, 11109, 13754, 13972 \__fp_round_to_zero_neg:NNN 10248, 10257
\__fp_round:Nww . . . . . 10275, 10275, 11110 \__fp_SANITIZE:Nw . . .
\__fp_round_digit:Nw . . . . . 9908, 9928, 10237, 10237, 11873, 12015, 12114, 12126, 12277 . . . . . 9791, 9791, 9802, 10335, 10353, 11802, 11896, 12067, 12146, 12637, 12872, 13123, 13524, 13561
\__fp_SANITIZE:wN 9791, 9802, 10546, 11171 \__fp_SANITIZE:w . . .
\__fp_SANITIZE_zero:w . . . . . 9791, 9798, 9803
\__fp_sec_o:w . . . . . 13329, 13329 \__fp_sin_o:w . . . . . 13284, 13284, 13940
\__fp_sin_series>NNwww . . . . . 13292, 13307, 13322, 13337, 13476, 13476 \__fp_sin_series_aux:NNnww . . .
\__fp_sin_series_aux:NNnww . . . . . 13476, 13480, 13492
\__fp_small_int:wTF . . . . . 9944, 9944, 10277 \__fp_small_int_normal:NnwTF . . .
\__fp_small_int_normal:NnwTF . . . . . 9944, 9948, 9953

```

```

\__fp_small_int_test:NnnwNTF . . .
    ..... 9944, 9961, 9969
\__fp_small_int_true:wTF . . .
    ..... 9944, 9947, 9952, 9972
\__fp_sub_back_far_o:NnnwnnnnN . .
    ..... 11905, 11951, 11951
\__fp_sub_back_near_after:wNNNNw . .
    ..... 11911, 11913, 11920, 11988
\__fp_sub_back_near_o:nnnnnnnnN . .
    ..... 11901, 11911, 11911
\__fp_sub_back_near_pack:NNNNNw . .
    ..... 11911, 11915, 11918, 11990
\__fp_sub_back_not_far_o:wwwNN . .
    ..... 11965, 11985, 11985
\__fp_sub_back_quite_far_ii:NN . .
    ..... 11969, 11971, 11975
\__fp_sub_back_quite_far_o:wwNN . .
    ..... 11963, 11969, 11969
\__fp_sub_back_shift:wnnnn . .
    ..... 11923, 11927, 11927
\__fp_sub_back_shift_ii:ww . .
    ..... 11927, 11929, 11932
\__fp_sub_back_shift_iii:NNNNNNNNw . .
    ..... 11927, 11937, 11940, 11949
\__fp_sub_back_shift_iv:nnnnw . .
    ..... 11927, 11944, 11950
\__fp_sub_back_very_far_ii_o:nnNwwNN . .
    ..... 11997, 12000, 12004
\__fp_sub_back_very_far_o:wwwNNN . .
    ..... 11964, 11997, 11997
\__fp_sub_eq_o:Nnwnw 11876, 11879, 11887
\__fp_sub_npos_i_o:Nnwnw . .
    ..... 11881, 11890, 11894, 11894
\__fp_sub_npos_ii_o:Nnwnw . .
    ..... 11876, 11883, 11888
\__fp_sub_npos_o:NnwNnw . .
    ..... 11796, 11876, 11876
\__fp_tan_o:w 13344, 13344, 13942
\__fp_tan_series_aux_o:Nnww . .
    ..... 13530, 13534, 13544
\__fp_tan_series_o:NNwww . .
    ..... 13352, 13367, 13530, 13530
\__fp_ternary:NwwN .. 11346, 11648, 11648
\__fp_ternary_break_point:n . .
    ..... 11648, 11654, 11673, 11685
\__fp_ternary_i:NwwN 11648, 11654, 11686
\__fp_ternary_ii:NwwN . .
    ..... 11362, 11648, 11676, 11694
\__fp_ternary_loop:Nw . .
    ..... 11648, 11651, 11678, 11683
\__fp_ternary_loop_break:w . .
    ..... 11648, 11653, 11673
\__fp_ternary_map_break: . .
    ..... 11648, 11681, 11685
\__fp_tmp:w . .
    ..... 9902, 9912, 9913,
        9914, 9915, 9916, 9917, 9918, 9919,
        9920, 9921, 9922, 9923, 9924, 9925,
        9926, 9927, 10376, 10388, 10389,
        10390, 10391, 10392, 10393, 10394,
        11019, 11024, 11025, 11026, 11027,
        11028, 11029, 11030, 11031, 11039,
        11040, 11041, 11042, 11043, 11044,
        11045, 11046, 11047, 11048, 11071,
        11082, 11083, 11119, 11135, 11136,
        11174, 11194, 11195, 11196, 11197,
        11198, 11199, 11200, 11204, 13931,
        13938, 13939, 13940, 13941, 13942
\__fp_to_decimal_dispatch:w . .
    .. 13639, 13643, 13646, 13646, 13753
\__fp_to_decimal_huge:wnnnn . .
    ..... 13646, 13684, 13706
\__fp_to_decimal_large:Nnnw . .
    ..... 13646, 13680, 13697
\__fp_to_decimal_normal:wnnnnn . .
    ..... 13646, 13651, 13672, 13734
\__fp_to_int_dispatch:w . .
    ..... 13744, 13748, 13751, 13751
\__fp_to_scientific_dispatch:w . .
    ..... 13584, 13588, 13591, 13596
\__fp_to_scientific_normal:wNw . .
    ..... 13591, 13627, 13629, 13636
\__fp_to_scientific_normal:wnnnn . .
    .. 13591, 13601, 13623, 13727, 13731
\__fp_to_tl_dispatch:w . .
    .. 13707, 13711, 13714, 13714, 13819
\__fp_to_tl_normal:nnnnn . .
    ..... 13714, 13719, 13724
\__fp_trap_division_by_zero_set:N ..
    .. 10075, 10076, 10078, 10080, 10081
\__fp_trap_division_by_zero_set_error: .
    ..... 10075, 10075
\__fp_trap_division_by_zero_set_flag: .
    ..... 10075, 10077
\__fp_trap_division_by_zero_set_none: .
    ..... 10075, 10079
\__fp_trap_invalid_operation_set:N ..
    .. 10041, 10042, 10044, 10046, 10047
\__fp_trap_invalid_operation_set_error: .
    ..... 10041, 10041

```

```

\__fp_trap_invalid_operation_set_flag:
    ..... 10041, 10043
\__fp_trap_invalid_operation_set_none:
    ..... 10041, 10045
\__fp_trap_overflow_set:N .....
    .. 10101, 10102, 10104, 10106, 10107
\__fp_trap_overflow_set:NnNn .....
    .. 10101, 10108, 10116, 10117
\__fp_trap_overflow_set_error: .....
    .. 10101, 10101
\__fp_trap_overflow_set_flag: .....
    .. 10101, 10103
\__fp_trap_overflow_set_none: .....
    .. 10101, 10105
\__fp_trap_underflow_set:N .....
    .. 10101, 10110, 10112, 10114, 10115
\__fp_trap_underflow_set_error: .....
    .. 10101, 10109
\__fp_trap_underflow_set_flag: .....
    .. 10101, 10111
\__fp_trap_underflow_set_none: .....
    .. 10101, 10113
\__fp_trig_epsilon_inv_o:w .....
    .. 13321, 13366, 13402, 13408
\__fp_trig_epsilon_o:w .....
    .. 13291, 13351, 13402, 13402
\__fp_trig_epsilon_one_o:w .....
    .. 13306, 13336, 13402, 13404
\__fp_trig_exponent:NNNNNwn .....
    .. 13291, 13306, 13321,
        13336, 13351, 13366, 13384, 13384
\__fp_trig_large:ww . 13392, 13425, 13425
\__fp_trig_large_break:w .....
    .. 13425, 13429, 13448
\__fp_trig_large_i:www .....
    .. 13425, 13426, 13427, 13438
\__fp_trig_large_ii_o:wnnnm .....
    .. 13425, 13430, 13436
\__fp_trig_octant_break:w .....
    .. 13450, 13458, 13466
\__fp_trig_octant_loop:nmnnnw .....
    .. 13449, 13450, 13450, 13464
\__fp_trig_small:ww . 13394, 13415, 13415
\__fp_trim_zeros:w .....
    .. 13575, 13575, 13637, 13690, 13699
\__fp_trim_zeros_dot:w 13575, 13578, 13581
\__fp_trim_zeros_end:w 13575, 13581, 13582
\__fp_trim_zeros_loop:w .....
    .. 13575, 13577, 13578, 13580
\__fp_type_from_scan:N . 9859, 10361,
    10369, 10441, 10999, 11001, 11018
\__fp_type_from_scan:w 10361, 10371, 10374
\__fp_underflow:w ... 9797, 10132, 10138
\__fp_use_i_until_s:nw .....
    .. 9743, 9744, 9785, 9992, 13470
\__fp_use_iuntil_s:nw 9743, 9745, 9783
\__fp_use_none_stop_f:n .....
    .. 9740, 9740, 12454, 12455, 12456
\__fp_use_none_until_s:w 9743, 9743, 13231
\__fp_use_s:n .....
    .. 9741, 9741
\__fp_use_s:nn .....
    .. 9741, 9742
\__fp_zero_fp:N . 9766, 9766, 10116, 10341
\__int_abs:N .....
    .. 3380, 3382, 3386
\__int_case:nnn .....
    .. 3592, 3595, 3597
\__int_case:nw .....
    .. 3592, 3598, 3599, 3603
\__int_case_end:nw .....
    .. 3592, 3602, 3605
\__int_compare_<:NNw .....
    .. 3550
\__int_compare_=:NNw .....
    .. 3550
\__int_compare_>:NNw .....
    .. 3550
\__int_compare_aux:NNw .....
    .. 3550, 3561, 3565
\__int_compare_aux:Nw .....
    .. 3550, 3552, 3559
\__int_constdef:Nw 3452, 3463, 3475, 3479
\__int_div_truncate:NwNw .....
    .. 3412, 3415, 3420, 3443
\__int_eval:w .....
    .. 73, 1288, 2275, 2598,
        2600, 2602, 2668, 2670, 2672, 2674,
        2676, 2678, 2680, 2682, 2684, 2686,
        2688, 2690, 3369, 3370, 3375, 3378,
        3383, 3391, 3392, 3399, 3400, 3414,
        3416, 3417, 3434, 3437, 3438, 3439,
        3464, 3507, 3509, 3531, 3552, 3571,
        3573, 3575, 3577, 3579, 3581, 3583,
        3586, 3608, 3616, 3842, 3869, 4024,
        4068, 4138, 9669, 9790, 9890, 9893,
        9980, 10226, 10230, 10242, 10243,
        10302, 10306, 10345, 10465, 10491,
        10547, 10604, 10615, 10664, 10695,
        10701, 10702, 10849, 10851, 10874,
        10875, 10881, 10890, 10901, 10903,
        10963, 11108, 11172, 11292, 11466,
        11804, 11812, 11833, 11835, 11856,
        11858, 11867, 11869, 11891, 11898,
        11904, 11914, 11916, 11989, 11991,
        12007, 12009, 12013, 12029, 12069,
        12077, 12079, 12081, 12083, 12085,
        12087, 12089, 12108, 12110, 12120,
        12122, 12148, 12151, 12159, 12161,
        12181, 12184, 12187, 12190, 12198,
        12201, 12204, 12207, 12214, 12216,
```

12222, 12230, 12232, 12234, 12240,
 12260, 12262, 12271, 12273, 12286,
 12305, 12312, 12324, 12332, 12334,
 12344, 12346, 12353, 12362, 12364,
 12367, 12370, 12373, 12376, 12390,
 12392, 12400, 12402, 12410, 12412,
 12421, 12424, 12427, 12434, 12453,
 12498, 12500, 12504, 12535, 12570,
 12577, 12595, 12597, 12645, 12656,
 12675, 12677, 12679, 12691, 12704,
 12709, 12711, 12717, 12734, 12735,
 12736, 12737, 12738, 12739, 12744,
 12746, 12748, 12750, 12752, 12756,
 12758, 12760, 12762, 12764, 12766,
 12788, 12796, 12874, 12878, 12931,
 13140, 13161, 13163, 13166, 13169,
 13172, 13175, 13191, 13217, 13227,
 13390, 13431, 13434, 13439, 13441,
 13443, 13445, 13483, 13494, 13526,
 13536, 13563, 13565, 13631, 13976
 $\backslash\text{__int_eval_end:}$ 73, 1288,
 2275, 2598, 2600, 2602, 2668, 2670,
 2672, 2674, 2676, 2678, 2680, 2682,
 2684, 2686, 2688, 2690, 3369, 3371,
 3375, 3378, 3383, 3418, 3434, 3440,
 3464, 3507, 3509, 3531, 3553, 3586,
 3608, 3616, 3842, 3869, 4139, 9672,
 9790, 9983, 10316, 10320, 11108,
 11292, 11466, 11726, 11891, 12013,
 12048, 12236, 12286, 12334, 12535,
 13191, 13483, 13494, 13536, 13565
 $\backslash\text{__int_from_alph:N}$ 3948, 3964, 3967
 $\backslash\text{__int_from_alph:n}$ 3948, 3953, 3956
 $\backslash\text{__int_from_alph:nN}$ 3948, 3957, 3958, 3963
 $\backslash\text{__int_from_base:N}$ 3969, 3986, 3990
 $\backslash\text{__int_from_base:nn}$ 3969, 3974, 3978
 $\backslash\text{__int_from_base:nnN}$ 3969, 3979, 3980, 3985
 $\backslash\text{__int_from_roman>NN}$
 4019, 4025, 4028, 4053, 4057
 $\backslash\text{__int_from_roman_clean_up:w}$
 4019, 4036, 4043, 4045, 4064
 $\backslash\text{__int_from_roman_end:w}$ 4019, 4023, 4062
 $\backslash\text{__int_get_digits:n}$ 3914, 3919, 3953, 3975
 $\backslash\text{__int_get_sign:n}$ 3914, 3914, 3952, 3973
 $\backslash\text{__int_get_sign_and_digits:nNNN}$
 3914, 3916, 3921, 3924, 3947
 $\backslash\text{__int_get_sign_and_digits:oNNN}$
 3914, 3930, 3934, 3940
 $\backslash\text{__int_maxmin:wwN}$ 3380, 3390, 3398, 3404
 $\backslash\text{__int_mod:ww}$ 3412, 3437, 3442
 $\backslash\text{__int_step:NNnnnn}$ 3701, 3704, 3711, 3720
 $\backslash\text{__int_step:NnnnN}$ 3678, 3681, 3688, 3692, 3697
 $\backslash\text{__int_to_Roman_Q:w}$ 3878, 3913
 $\backslash\text{__int_to_Roman_aux:N}$ 3890, 3893, 3896
 $\backslash\text{__int_to_Roman_c:w}$ 3878, 3910
 $\backslash\text{__int_to_Roman_d:w}$ 3878, 3911
 $\backslash\text{__int_to_Roman_i:w}$ 3878, 3906
 $\backslash\text{__int_to_Roman_l:w}$ 3878, 3909
 $\backslash\text{__int_to_Roman_m:w}$ 3878, 3912
 $\backslash\text{__int_to_Roman_v:w}$ 3878, 3907
 $\backslash\text{__int_to_Roman_x:w}$ 3878, 3908
 $\backslash\text{__int_to_base:nn}$ 3811, 3812, 3813
 $\backslash\text{__int_to_base:nnN}$
 3811, 3816, 3817, 3819, 3833
 $\backslash\text{__int_to_base:nnN}$ 3811, 3824, 3831
 $\backslash\text{__int_to_letter:n}$ 3811, 3822, 3825, 3839
 $\backslash\text{__int_to_roman:N}$
 3878, 3878, 3880, 3883, 3886
 $\backslash\text{__int_to_roman:w}$ 72, 781, 782, 882,
 884, 1057, 2273, 3369, 3562, 3881, 3891
 $\backslash\text{__int_to_roman_Q:w}$ 3878, 3905
 $\backslash\text{__int_to_roman_c:w}$ 3878, 3902
 $\backslash\text{__int_to_roman_d:w}$ 3878, 3903
 $\backslash\text{__int_to_roman_i:w}$ 3878, 3898
 $\backslash\text{__int_to_roman_l:w}$ 3878, 3901
 $\backslash\text{__int_to_roman_m:w}$ 3878, 3904
 $\backslash\text{__int_to_roman_v:w}$ 3878, 3899
 $\backslash\text{__int_to_roman_x:w}$ 3878, 3900
 $\backslash\text{__int_to_symbols:nnnn}$ 3727, 3731, 3741
 $\backslash\text{__int_value:w}$
 73, 1063, 2187, 2190, 2275,
 3369, 3369, 3375, 3378, 3382, 3390,
 3398, 3434, 3437, 3438, 3439, 3869,
 4024, 4140, 4239, 6768, 6799, 6800,
 6801, 6803, 6929, 6938, 6940, 6945,
 6946, 6947, 6948, 6952, 6953, 6954,
 6955, 6980, 6986, 6988, 6990, 6992,
 6997, 7002, 7007, 7014, 7021, 7151,
 7181, 7182, 7221, 7240, 7246, 7416,
 7520, 9669, 9848, 9849, 9850, 9851,
 9852, 9907, 9973, 10288, 10304,
 10309, 10434, 10599, 10606, 10619,
 10656, 10667, 10673, 10684, 10705,
 10721, 10797, 10799, 10914, 11481,
 11749, 11750, 11751, 11753, 11807,
 11810, 11873, 11930, 11938, 11946,
 12012, 12015, 12114, 12126, 12164,
 12165, 12166, 12167, 12277, 12294,
 12455, 12456, 12457, 12638, 12652,

12673, 12695, 12696, 12697, 12698,
12699, 12812, 12817, 12821, 12874,
12943, 13125, 13182, 13185, 13187,
13213, 13215, 13392, 13394, 13482,
13535, 13699, 13759, 13769, 13773,
14613, 14615, 14635, 14637, 14662,
14702, 14729, 14737, 14762, 14764,
14768, 14770, 14799, 14813, 14820
__ior_alloc: 9302, 9308, 9324, 9332, 9334
__ior_alloc:N 9288, 9302, 9303
__ior_alloc:n 9284, 9294, 9294
__ior_list_streams:Nn
..... 9352, 9353, 9354, 9488
__ior_map_inline:NNNn 14831, 14838, 14841
__ior_map_inline:NNn
..... 14831, 14832, 14834, 14835
__ior_map_inline_loop:NNN
..... 14831, 14844, 14848, 14854
__ior_new:N . 9243, 9245, 9249, 9251, 9311
__ior_new:c 9243, 9318
__ior_open:Nn
... 163, 9106, 9126, 9255, 9280, 9293
__ior_open:No 9255, 9263, 9273
__ior_open_aux:Nn 9255, 9256, 9258
__ior_open_aux:NnTF ... 9255, 9266, 9267
__iow_alloc: 9436, 9442, 9458, 9466, 9468
__iow_alloc:N 9423, 9436, 9437
__iow_alloc:n 9419, 9428, 9428
__iow_indent:n 9538, 9539, 9557
__iow_list_streams:Nn .. 9486, 9487, 9488
__iow_new:N . 9401, 9403, 9407, 9409, 9445
__iow_new:c 9401, 9452
__iow_open:Nn 9412, 9413, 9415
__iow_wrap_end: 9659
__iow_wrap_end:w 9632
__iow_wrap_indent: 9647
__iow_wrap_indent:w 9632
__iow_wrap_loop:w
..... 9578, 9587, 9587, 9602, 9637
__iow_wrap_newline: 9639
__iow_wrap_newline:w 9632
__iow_wrap_special:w
..... 9591, 9632, 9632, 9636
__iow_wrap_unindent: 9653
__iow_wrap_unindent:w 9632
__iow_wrap_word: 9592, 9594, 9594
__iow_wrap_word_fits: .. 9594, 9600, 9604
__iow_wrap_word_newline: 9594, 9601, 9620
__kernel_register_show:N .. 24, 1436,
1436, 1446, 4065, 4372, 4475, 4543
__kernel_register_show:c 1436, 1445, 4066
__keys_bool_set>NN 8577, 8577, 8754, 8756
__keys_bool_set_inverse>NN
..... 8592, 8592, 8758, 8760
__keys_choice_code_store:n
..... 8659, 8659, 8670, 8770
__keys_choice_code_store:x .. 8659, 8772
__keys_choice_find:n
..... 8610, 8710, 8963, 8963
__keys_choice_make: 8580,
8595, 8607, 8607, 8619, 8638, 8762
__keys_choices_generate:n
..... 8633, 8633, 8802
__keys_choices_generate_aux:n
..... 8633, 8640, 8647
__keys_choices_make:nn 8617, 8617, 8764
__keys_cmd_set:Vo 8671, 8701
__keys_cmd_set:n 8671, 8673, 8678, 8682
__keys_cmd_set:nn
..... 8585, 8600, 8609, 8611,
8671, 8671, 8681, 8713, 8715, 8766
__keys_cmd_set:nx
8581, 8583, 8596, 8598, 8624, 8650,
8671, 8676, 8706, 8728, 8746, 8768
__keys_default_set:V 8688, 8784
__keys_default_set:n
.. 8590, 8605, 8688, 8688, 8690, 8782
__keys_define:nnn 8514, 8516, 8522
__keys_define:onn 8514, 8515
__keys_define_elt:n .. 8519, 8523, 8523
__keys_define_elt:nn .. 8519, 8523, 8528
__keys_define_elt_aux:nn
..... 8523, 8526, 8531, 8533
__keys_define_key:n .. 8537, 8560, 8560
__keys_define_key:w .. 8560, 8564, 8575
__keys_execute: 8909, 8934, 8934
__keys_execute:nn
... 8934, 8935, 8938, 8954, 8965, 8966
__keys_execute_unknown:
... 8867, 8869, 8934, 8935, 8936, 8944
__keys_execute_unknown_alt:
..... 8867, 8934, 8945
__keys_execute_unknown_std:
..... 8869, 8934, 8944
__keys_if_value:n 8927
__keys_if_value_p:n .. 8892, 8902, 8927
__keys_initialise:V 8691, 8806
__keys_initialise:n 8691, 8691, 8696, 8804
__keys_initialise:wn .. 8691, 8694, 8697
__keys_meta_make:n .. 8699, 8699, 8816

```

\__keys_meta_make:x .... 8699, 8704, 8818 \__msg_kernel_class_new_aux:nN ....
\__keys_multichoice_find:n ..... 8709, 8709, 8714 ..... 8013, 8015, 8016
\__keys_multichoice_make: ..... 8709, 8711, 8723, 8820 ... 1163, 1177, 7039, 8051, 8054, 8442
\__keys_multichoices_make:nn ..... 8709, 8721, 8822 \__msg_kernel_error:nnn ..... 8051
\__keys_property_find:n 8535, 8543, 8543 \__msg_kernel_error:nnnn ..... 8051
\__keys_property_find:w ..... 8543, 8547, 8550, 8556 \__msg_kernel_error:nnnnn ..... 8051
\__keys_set:nnn ..... 8851, 8853, 8860 \__msg_kernel_error:nnnnnn ..... 144, 8051
\__keys_set:onn ..... 8851, 8852 \__msg_kernel_error:nnxx 926, 967, 1005,
\__keys_set_elt:n 8856, 8868, 8875, 8875 1010, 1163, 1175, 1208, 1359, 1441,
\__keys_set_elt:nn 8856, 8868, 8875, 8880 1910, 2121, 2575, 4783, 5293, 6634,
\__keys_set_elt_aux:nn ..... 8875, 8878, 8883, 8885 6783, 7877, 8051, 8053, 8293, 8548,
\__keys_set_known:nnnn . 8861, 8863, 8874 8587, 8602, 8643, 8896, 9092, 9151,
\__keys_set_known:onnN ..... 8861, 8862 9262, 9750, 10038, 13867, 14046, 14088
\__keys_value_or_default:n ..... 8889, 8912, 8912 \__msg_kernel_error:nnxxx ... 917, 946,
\__keys_value_requirement:n ..... 8737, 8737, 8848, 8850 1024, 1163, 1163, 1176, 1178, 1185,
\__keys_variable_set:NnN ..... 8743, 8749, 8752, 8774, 1195, 1329, 1971, 6931, 7604, 7614,
\__keys_variable_set:NnNN ..... 8743, 8743, 8750, 8751, 8778, 7902, 8051, 8052, 8539, 8568, 8613,
\__keys_variable_set:cNn . 8743, 8776, 8790, 8798, 8812, 8828, 8840, 8844 8717, 8906, 8940, 10035, 14083, 14111
\__keys_variable_set:cnN . 8743, 8776, 8788, 8796, 8810, 8826, 8834, 8838 \__msg_kernel_error:nnxxxx ..... 8051
\__keys_variable_set:cnNN 8743, 8780, 8792, 8800, 8814, 8830, 8842, 8846 \__msg_kernel_error:nnxxxxx .. 1986, 8051
\__msg_class_chk_exist:nT ..... 7874, 7874, 7888, 7954, 7964, 7969 \__msg_kernel_expandable_error:nn ...
\__msg_class_new:nn . 7769, 7770, 7807, 7818, 7829, 7850, 7858, 7866, 7872 . 2303, 5378, 8243, 8267, 10451, 11415
\__msg_error:cnnnnn .... 7829, 7831, 7843 \__msg_kernel_expandable_error:nnn . 1665, 3546, 3685, 4987, 8243, 8262,
\__msg_error_code:nnnnnn ..... 8055 10457, 10508, 10529, 10536, 10786,
\__msg_expandable_error:n ..... 145, 8220, 8228, 8245 10791, 10802, 10809, 10981, 11161,
\__msg_expandable_error:w 8220, 8234, 8240 11378, 14008, 14013, 14592, 15027
\__msg_fatal_code:nnnnnn ..... 8051 \__msg_kernel_expandable_error:nnnn . 8243, 8257, 11272, 11359, 11663
\__msg_interrupt_more_text:n ..... 7697, 7699, 7702 \__msg_kernel_expandable_error:nnnnn ...
\__msg_interrupt_text:n 7700, 7711, 7719 ..... 8243, 8252, 10146, 11112
\__msg_interrupt_wrap:nn ..... 7689, 7693, 7697, 7697 \__msg_kernel_expandable_error:nnnnnn . 144, 8243, 8243, 8254, 8259, 8264, 8269
\__msg_kernel_bug:x ..... 8341, 8342 \__msg_kernel_fatal:nn ..... 8051, 9286, 9421, 14067
\__msg_kernel_class_new:nN ..... 8013, 8014, 8051, 8055, 8056, 8057 \__msg_kernel_fatal:nnn ..... 8051
\__msg_kernel_fatal:nnn ..... 8051 \__msg_kernel_fatal:nnnn ..... 8051
\__msg_kernel_fatal:nnnn ..... 8051 \__msg_kernel_fatal:nnnnn ..... 8051
\__msg_kernel_fatal:nnnnn ..... 144, 8051 \__msg_kernel_fatal:nnnnnn . 144, 8051
\__msg_kernel_fatal:nnx ... 8051, 14040 \__msg_kernel_fatal:nnxx ..... 8051
\__msg_kernel_fatal:nnxx ..... 8051 \__msg_kernel_fatal:nnxxx ..... 8051
\__msg_kernel_fatal:nnxxx ..... 8051 \__msg_kernel_fatal:nnxxxx ..... 8051
\__msg_kernel_info:mn ..... 8056 \__msg_kernel_info:mn ..... 8056
\__msg_kernel_info:mnn ..... 8056 \__msg_kernel_info:mnnn ..... 8056
\__msg_kernel_info:nnn ..... 8056 \__msg_kernel_info:nnnn ..... 8056
\__msg_kernel_info:nnnn ..... 8056 \__msg_kernel_info:nnnnnn ..... 144, 8056
\__msg_kernel_info:nnx ..... 8056 \__msg_kernel_info:nnnx ..... 8056

```

```

\__msg_kernel_info:nxxx ..... 8056 \__msg_term:nnn ... 8272, 8281, 8289, 9356
\__msg_kernel_info:nxxxx ..... 8056 \__msg_term:nnnnn ..... 8272, 8279
\__msg_kernel_info:nxxxxx ..... 8056 \__msg_term:nnnnnV ..... 8272
\__msg_kernel_new:nnn ..... 7544, \__msg_term:nnnnnn ..... .
   8005, 8007, 8184, 8186, 8188, 8190,   145, 8272, 8272, 8278, 8280, 8282, 8284
   8192, 8194, 8202, 8209, 8216, 8218, \__msg_use:nnnnnnn 7778, 7884, 7884, 8373
   10171, 10173, 10175, 10177, 10179, \__msg_use_code: ..... .
   10181, 11419, 11421, 11423, 11425,   7884, 7891, 7904, 7908, 7933, 7944
   11427, 11429, 11431, 11433, 11435 \__msg_use_hierarchy:nwwN ..... .
\__msg_kernel_new:nnn ..... .   7884, 7911, 7912, 7918
   143, 7526, 7534, 7537, 8005, 8005, \__msg_use_redirect_module:n ..... .
   8059, 8067, 8075, 8082, 8093, 8101,   7884, 7915, 7923, 7936
   8110, 8117, 8124, 8131, 8140, 8147, \__msg_use_redirect_name:n ..... .
   8154, 8161, 8168, 8176, 8493, 8982,   7884, 7899, 7905
   8985, 8991, 8998, 9007, 9013, 9020, \__my_map dbl:nn ..... 4, 6, 11
   9027, 9033, 9683, 9689, 9696, 9703, \__my_map dbl_fn:nn ..... 3, 10
   10000, 10148, 10160, 14156, 14162 \__peek_def:nnnn ..... 3171, 3172,
\__msg_kernel_set:nnn ..... 8005, 8011   3188, 3192, 3196, 3200, 3204, 3208,
\__msg_kernel_set:nnnn ..... 143, 8005, 8009   3212, 3216, 3220, 3224, 3228, 3232
\__msg_kernel_warning:nn ..... 8056 \__peek_def:nnnnn ..... .
\__msg_kernel_warning:nnn ..... 8056   3171, 3174, 3175, 3176, 3178
\__msg_kernel_warning:nnnn ..... 8056 \__peek_execute_branches: ... 3167, 3183
\__msg_kernel_warning:nnnnn ..... 8056 \__peek_execute_branches_N_type: ... .
\__msg_kernel_warning:nnnnnn ..... 144, 8056   15193, 15193, 15205, 15207, 15209
\__msg_kernel_warning:nnx ..... 8056 \__peek_execute_branches_catcode: ... .
\__msg_kernel_warning:nnxx ..... 8056   3120, 3120, 3191, 3193, 3199, 3201
\__msg_kernel_warning:nnxxx ..... 8056 \__peek_execute_branches_charcode: ... .
\__msg_kernel_warning:nnxxxx ..... 7989, 8056   3137, 3137, 3207, 3209, 3215, 3217
\__msg_no_more_text:nnnn ..... 7829, 7845, 7849 \__peek_execute_branches_charcode:NN ..... 3137
\__msg_redirect:nnn ..... 7958, 7959, 7961, 7962 \__peek_execute_branches_charcode_aux:NN ..... .
\__msg_redirect_loop_chk:nnn ..... .   3147, 3151
   7958, 7974, 7979, 8003 \__peek_execute_branches_meaning: ... .
\__msg_redirect_loop_chk:onn ..... 7999   3120, 3129, 3223, 3225, 3231, 3233
\__msg_redirect_loop_list:n ..... . \__peek_false:w ... 3067, 3069, 3090,
   7958, 7995, 8004   3108, 3126, 3134, 3145, 3156, 15201
\__msg_show_item:n ..... . \__peek_get_prefix_arg_replacement:wN ..... .
   145, 5759, 6153, 8308, 8308   3237, 3238, 3245, 3254, 3263
\__msg_show_item:nn ..... 6445, 8308, 8312 \__peek_ignore_spaces_execute_branches: ... .
\__msg_show_item_unbraced:nn ..... .   3160, 3160, 3170,
   145, 7521, 8308, 8317, 9360   3195, 3203, 3211, 3219, 3227, 3235
\__msg_show_variable:Nnn ..... . \__peek_ignore_spaces_execute_branches_aux: ... .
   145, 5758, 6152, 6444, 7517, 8285, 8285   3160, 3164, 3169
\__msg_show_variable:n ..... . \__peek_tmp:w ... 3067, 3070, 3079, 3165
   145, 1455, 2128, 2129, 5299,   8285, 8290, 8297, 9359, 13865, 13872 \__peek_token_generic:NNF .. 3100, 15209
\__msg_show_variable_aux:n ..... .   8285, 8298, 8299 \__peek_token_generic:NNT .. 3098, 15207
\__msg_show_variable_aux:w ..... . \__peek_token_generic:NNTF ..... .
   8285, 8303, 8307   3081, 3081, 3099, 3101, 15205
\__msg_term:nn ..... 8272, 8283 \__peek_token_remove_generic:NNF .. 3118
\__msg_term:nnn ..... . \__peek_token_remove_generic:NNT .. 3116

```

_peek_token_remove_generic:NNTF	3102 , 3102 , 3117 , 3119	_prg_replicate_7:n	2271
_peek_true:w	3067 , 3067 , 3085 , 3106 , 3124 , 3132 , 3154 , 15202	_prg_replicate_8:n	2271
_peek_true_aux:w	3067 , 3068 , 3078 , 3107	_prg_replicate_9:n	2271
_peek_true_remove:w	3075 , 3075 , 3106	_prg_replicate_first:N 2271 , 2274 , 2280	
_prg_break:	42 , 1553 , 1554 , 2363 , 6386 , 9981 , 13806 , 14906 , 14924 , 14932 , 15165	_prg_replicate_first_--:n	2271
_prg_break:n	1553 , 1555 , 2363 , 5532 , 14889 , 14914 , 15167	_prg_replicate_first_0:n	2271
_prg_break_point:	42 , 1553 , 1553 , 1554 , 1555 , 2363 , 5529 , 6371 , 9982 , 13807 , 14884 , 14908 , 14925 , 15161	_prg_replicate_first_1:n	2271
_prg_break_point:Nn	42 , 1544 , 1544 , 1545 , 2363 , 3724 , 4939 , 4956 , 4965 , 5664 , 5699 , 5710 , 6054 , 6068 , 6087 , 6105 , 6417 , 6435 , 14845 , 14870	_prg_replicate_first_2:n	2271
_prg_case_end:nw	24 , 1520 , 1542 , 1543 , 3605 , 4294 , 4934	_prg_replicate_first_3:n	2271
_prg_compare_error:	73 , 3537 , 3537 , 3541 , 3553 , 3559 , 4248 , 4257	_prg_replicate_first_4:n	2271
_prg_compare_error:NNw	3537	_prg_replicate_first_5:n	2271
_prg_compare_error:Nw	3543 , 3568 , 4265	_prg_replicate_first_6:n	2271
_prg_generate_F_form:wnnnnnn	955 , 976	_prg_replicate_first_7:n	2271
_prg_generate_TF_form:wnnnnnn	955 , 981	_prg_replicate_first_8:n	2271
_prg_generate_T_form:wnnnnnn	955 , 971	_prg_replicate_first_9:n	2271
_prg_generate_conditional:nnNnnnnn	895 , 914 , 923 , 923	_prg_set_eq_conditional>NNNn	986 , 987 , 989 , 990
_prg_generate_conditional:nnnnnnw	923 , 932 , 938 , 953	_prg_set_eq_conditional:nnNnnNNw	994 , 1002 , 1002
_prg_generate_conditional_count:nnNnn	898 , 899 , 901 , 903 , 905 , 906	_prg_set_eq_conditional_F_form:nnn	1002
_prg_generate_conditional_count:nnNnnnn	898 , 908 , 911	_prg_set_eq_conditional_F_form:wNnnnn	1048
_prg_generate_conditional_parm:nnNpn	885 , 886 , 888 , 890 , 892 , 893	_prg_set_eq_conditional_TF_form:nnn	1002
_prg_generate_p_form:wnnnnnn	955 , 955	_prg_set_eq_conditional_TF_form:wNnnnn	1038
_prg_map_break:Nn	42 , 1544 , 1545 , 1551 , 2363 , 4978 , 4980 , 5657 , 5659 , 6122 , 6124 , 6439 , 6441 , 14828 , 14830	_prg_set_eq_conditional_T_form:nnn	1002
_prg_replicate:N	2271 , 2278 , 2279 , 2281	_prg_set_eq_conditional_T_form:wNnnnn	1043
_prg_replicate_	2271 , 2282	_prg_set_eq_conditional_loop:nnnnNw	1002 , 1014 , 1016 , 1031
_prg_replicate_0:n	2271	_prg_set_eq_conditional_p_form:nnn	1002
_prg_replicate_1:n	2271	_prg_set_eq_conditional_p_form:wNnnnn	1033
_prg_replicate_2:n	2271	_prg_variable_get_scope:N	
_prg_replicate_3:n	2271	_prg_variable_get_scope:W	41 , 2329 , 2335
_prg_replicate_4:n	2271	_prg_variable_get_type:N 41 , 2329 , 2350	
_prg_replicate_5:n	2271	_prg_variable_get_type:W	2329 , 2352 , 2355 , 2359
_prg_replicate_6:n	2271	_prop_get:Nnnn	6248 , 6251 , 6254
		_prop_get_Nn:nwn	
		_prop_get	14879 , 14881 , 14886 , 14890
		_prop_get_true:Nnnn	6396 , 6399 , 6402
		_prop_if_in:N	6365 , 6376 , 6379
		_prop_if_in:nwn	6365 , 6367 , 6373 , 6377

```

\__prop_map_function:Nwn . . . . .
    . . . . . 6413, 6415, 6419, 6423, 6431
\__prop_map_tokens:nwn . . . .
    . . . . . 14866, 14868, 14872, 14876
\__prop_pop:NNNnnn 6258, 6261, 6267, 6270
\__prop_pop_true:NNNnnn . . .
    . . . . . 6279, 6282, 6288, 6291
\__prop_put:NNNnm 6303, 6304, 6306, 6307
\__prop_put:NNnnnnn . . . 6303, 6310, 6313
\__prop_put_if_new:NNnn . . .
    . . . . . 6330, 6331, 6333, 6334
\__prop_remove:NNnnn 6238, 6239, 6241, 6242
\__prop_split:NnTF . . . . . 123,
    6226, 6226, 6239, 6241, 6250, 6260,
    6266, 6281, 6287, 6309, 6336, 6398
\__prop_split_aux:NnTF . 6226, 6227, 6228
\__prop_split_aux:nnnn . 6226, 6232, 6236
\__prop_split_aux:w 6226, 6230, 6233, 6237
\__quark_if_recursion_tail_break:NN
    . . . . . 47, 2512, 2512, 2586, 4972, 14874
\__quark_if_recursion_tail_break:nN
    . . . . . 2512, 2518,
    2588, 4945, 6059, 6072, 6421, 15165
\__scan_new:N . . . . .
    . . . . . 47, 2571, 2571, 2583, 9747, 9753,
    9754, 9755, 9756, 9757, 9758, 9759
\__seq_count:n . . . . . 5714, 5719, 5722
\__seq_get_left:Nnw . . . . . 5561, 5565
\__seq_get_left:NnwN . . . . . 5557
\__seq_get_right_loop:nn . . .
    . . . . . 5581, 5583, 5592, 5595
\__seq_if_in: . . . . . 5514, 5523, 5531
\__seq_item:n . . . . . 108, 5376,
    5376, 5451, 5453, 5459, 5461, 5466,
    5519, 5562, 5565, 5574, 5604, 5605,
    5617, 5676, 5681, 5687, 5691, 14977,
    14978, 14980, 14985, 15005, 15016,
    15021, 15029, 15032, 15035, 15038
\__seq_item:nnn 14894, 14896, 14910, 14915
\__seq_map_function:NNn . . .
    . . . . . 5660, 5662, 5666, 5670
\__seq_mapthread_function:NN . . .
    . . . . . 14918, 14920, 14927
\__seq_mapthread_function:Nnnwwn . . .
    . . . . . 14918, 14929, 14935, 14940
\__seq_pop:NNNN . . .
    . . . . . 5539, 5539, 5569, 5571, 5599, 5601
\__seq_pop_TF:NNNN . . . . . 5539, 5547,
    5627, 5629, 5637, 5639, 5641, 5643
\__seq_pop_item_def: . . . . . 109, 5506,
    5673, 5689, 5699, 5710, 14997, 15007
\__seq_pop_left:NNN . . .
    . . . . . 5568, 5569, 5571, 5572, 5637, 5639
\__seq_pop_left:NnwNNN . . . . . 5568, 5573, 5574
\__seq_pop_right_aux:NNN . . .
    . . . . . 5598, 5599, 5601, 5602, 5641, 5643
\__seq_pop_right_loop:nn . . .
    . . . . . 5598, 5609, 5619, 5622
\__seq_push_item_def: . . .
    . . . . . 5673, 5675, 5680, 5683
\__seq_push_item_def:n . . . . . 108,
    5490, 5673, 5673, 5697, 14995, 15005
\__seq_push_item_def:x . . . . . 5673, 5678, 5704
\__seq_remove_all_aux:NNn . . .
    . . . . . 5484, 5485, 5487, 5488
\__seq_remove_duplicates:NN . . .
    . . . . . 5468, 5469, 5471, 5472
\__seq_reverse:NN . . .
    . . . . . 14970, 14972, 14974, 14975
\__seq_reverse_item:nw . . .
    . . . . . 14970, 14978, 14982
\__seq_set_filter:NNNn . . .
    . . . . . 14989, 14990, 14992, 14993
\__seq_set_map:NNNn . . .
    . . . . . 14999, 15000, 15002, 15003
\__seq_set_split:NNnn . . .
    . . . . . 5402, 5403, 5405, 5406
\__seq_set_split_end: . . .
    . . . . . 5402, 5415, 5419, 5426, 5430, 5432
\__seq_set_split_i:w 5402, 5413, 5420, 5426
\__seq_set_split_ii:w . . . . . 5402, 5428, 5432
\__seq_tmp:w . . . . . 14970, 14970, 14977, 14980
\__seq_use:NnNnn 15009, 15016, 15017, 15029
\__seq_use_ii:nnwwnn . . .
    . . . . . 15009, 15020, 15022, 15031
\__seq_use_iii:nwnn . . . . . 15009, 15023, 15038
\__seq_wrap_item:n . . .
    . . . . . 5409, 5433, 5466, 5466, 5502,
    14947, 14952, 14957, 14962, 14995
\__skip_if_finite:wwNw . . . . . 4452, 4456, 4460
\__str_case:nw . . . . . 1520, 1523, 1525, 1529
\__str_case_end:nw . . . . . 1520, 1528, 1539, 1543
\__str_case_x:nw . . . . . 1520, 1534, 1536, 1540
\__str_count_ignore_spaces:N . . .
    . . . . . 9597, 9665, 9665
\__str_count_ignore_spaces:n . . .
    . . . . . 9665, 9666, 9667
\__str_count_loop:NNNNNNNN . . .
    . . . . . 9665, 9670, 9674, 9680

```

```

\__str_head:w ..... 5167, 5169, 5173
\__str_if_eq_x_return:nn .....
. 25, 1512, 1512, 2857, 2866, 2882,
2904, 2924, 2942, 2960, 2973, 2984,
2994, 4921, 5257, 5360, 15058, 15059
\__str_tail:w ..... 5167, 5177, 5181
\__tl_act:NNNnn .....
. 5065, 5065, 5116, 15066, 15089, 15129
\__tl_act_case_aux:nn .....
. 15116, 15124, 15127, 15146
\__tl_act_case_group:nn .....
. 15111, 15131, 15143
\__tl_act_case_normal:nN .....
. 15111, 15130, 15135
\__tl_act_case_space:n 15111, 15132, 15134
\__tl_act_count_group:nn .....
. 15085, 15091, 15099
\__tl_act_count_normal:nN .....
. 15085, 15090, 15097
\__tl_act_count_space:n .....
. 15085, 15092, 15098
\__tl_act_end:w ..... 5065
\__tl_act_end:wn ..... 5086, 5092
\__tl_act_group:nwnNNN . 5065, 5078, 5094
\__tl_act_group_recurse:Nnn .....
. 15076, 15080, 15080
\__tl_act_loop:w .....
. 5065, 5068, 5072, 5089, 5097, 5104
\__tl_act_normal:NwnNNN 5065, 5075, 5083
\__tl_act_output:n .....
. 5065, 5107, 15134, 15137, 15145
\__tl_act_result:n .....
. 5070, 5092, 5107, 5108, 5109, 5110
\__tl_act_reverse_output:n .....
. 5065, 5109, 5126, 5128, 5130, 15077
\__tl_act_space:wwnNNN . 5065, 5079, 5101
\__tl_case:Nw .... 4922, 4925, 4927, 4931
\__tl_case_end:nw .... 4922, 4930, 4934
\__tl_count:n .... 4990, 4993, 4998, 5000
\__tl_head_i:nw ... 5137, 5140, 5142, 5153
\__tl_head_i:nw .... 5137, 5143, 5144
\__tl_if_blank_p:NNw .... 4829
\__tl_if_empty_return:o .....
. 4830, 4863, 4863, 4873
\__tl_if_head_eq_meaning_normal:nN .....
. 5223, 5227
\__tl_if_head_eq_meaning_special:nN .....
. 5224, 5236
\__tl_if_head_is_space:w 5276, 5279, 5281
\__tl_item:nn . 15148, 15150, 15163, 15168
\__tl_map_function:Nn .....
. 4935, 4937, 4943, 4946, 4953
\__tl_map_variable:Nnn .....
. 4961, 4963, 4969, 4974
\__tl_replace:NNNnn .....
. 4767, 4768, 4770, 4772, 4774, 4779
\__tl_replace:w .. 4767, 4804, 4807, 4812
\__tl_replace_all: .....
. 4767, 4772, 4774, 4805, 4808
\__tl_replace_once: 4767, 4768, 4770, 4810
\__tl_replace_once_end:w 4767, 4813, 4815
\__tl_rescan:w ..... 4729, 4747, 4755
\__tl_reverse_group:nn 15061, 15068, 15074
\__tl_reverse_group_preserve:nn .....
. 5111, 5118, 5127
\__tl_reverse_items:nwNnw .....
. 5003, 5005, 5006, 5010, 5013
\__tl_reverse_items:wn .....
. 5003, 5007, 5014, 5017
\__tl_reverse_normal:nN .....
. 5111, 5117, 5125, 15067
\__tl_reverse_space:n .....
. 5111, 5119, 5129, 15069
\__tl_set_rescan:NNnn .....
. 4729, 4730, 4732, 4734, 4735
\__tl_tmp:w ..... 4788,
4808, 4813, 4909, 4910, 5027, 5064
\__tl_trim_spaces:nn .....
. 100, 5020, 5027, 5029, 5832, 14525
\__tl_trim_spaces_i:w .....
. 5027, 5031, 5041, 5044, 5050
\__tl_trim_spaces_ii:w .... 5035, 5049
\__tl_trim_spaces_ii:w\__tl_trim_spaces_iii:w .....
. 5027
\__tl_trim_spaces_iii:w .....
. 5036, 5052, 5055, 5059
\__tl_trim_spaces_iv:w . 5027, 5038, 5061
\__token_if_chardef:w .....
. 2844, 2859, 2868, 2873
\__token_if_dim_register:w .....
. 2844, 2884, 2891
\__token_if_int_register:w .....
. 2844, 2906, 2915
\__token_if_long_macro:w .....
. 2844, 2986, 2996, 3001
\__token_if_macro_p:w .. 2804, 2815, 2818
\__token_if_muskip_register:w .....
. 2844, 2926, 2933
\__token_if_primitive:NNw 3003, 3016, 3020
\__token_if_primitive:Nw 3003, 3039, 3045

```

	B
__token_if_primitive_loop:N	4721, 4723
..... 3003, 3023, 3036, 3042	
__token_if_primitive_nullfont:N	586
..... 3003, 3024, 3028	
__token_if_primitive_space:w	514
..... 3003, 3022, 3027	
__token_if_primitive_undefined:N	407
..... 3003, 3048, 3054	
__token_if_protected_macro:w	14095
..... 2844, 2975, 2980	
__token_if_skip_register:w	701
..... 2844, 2944, 2951	
__token_if_toks_register:w	451
..... 2844, 2962, 2969	
__use_none_delimit_by_s_stop:w	452
..... 47, 2584, 2584	
\l	471, 4723
\l	4114, 11218
\~	699
..... 2720, 2730, 9553	
Numbers	
\8	2238
\9	2238
\u	2243
315, 1058, 2730, 2887, 2909, 2929,	
2947, 2965, 2978, 2989, 2999, 7712,	
7713, 8063, 8108, 8127, 8222, 8310,	
8314, 8315, 8319, 8320, 9518, 9556	
A	
\A	147
\above	2098, 2100, 2103
\abovedisplayshortskip	2098
\abovedisplayskip	2098
\abovewithdelims	2098
\accent	2098
\adjdemerits	2098
\advance	2098
\afterassignment	2098
\aftergroup	2098
false	2098
nan	2098
tan	2098
\assert:n	2098
\assert_str_eq:nn	2098
\AtBeginDocument	2098
\atop	2098
\atopwithdelims	2098
max	2098
B	
\B	147
\badness	586
\baselineskip	514
\batchmode	407
\BeginCatcodeRegime	14095
\begingroup	345
\beginL	699
\beginR	701
\belowdisplayshortskip	451
\belowdisplayskip	452
\binoppenalty	475
\bool_do_until:cn	2238
\bool_do_until:Nn	2238
\bool_do_until:nn	2238
\bool_do_while:cn	2238
\bool_do_while:Nn	2238
\bool_do_while:nn	2238
\bool_gset:cn	2098
\bool_gset:N	147
\bool_gset:Nn	37, 2098, 2100, 2103
\bool_gset_eq:cc	2098, 2097
\bool_gset_eq:cN	2098, 2096
\bool_gset_eq:Nc	2098, 2095
\bool_gset_eq>NN	37, 2098, 2094
\bool_gset_false:c	2078
\bool_gset_false:N	36, 2078, 2084, 2089
.bool_gset_inverse:N	148
\bool_gset_true:c	2078
\bool_gset_true:N	36, 2078, 2082, 2088
\bool_if:cTF	2104
\bool_if:N	2104
\bool_if:n	2144
\bool_if:NF	2144
249, 2114, 2235, 2241, 3942, 7438, 8950	
\bool_if:nF	2259, 2268
\bool_if:NT	2113,
2233, 2239, 3942, 3943, 7037, 8915	
\bool_if:nT	2246, 2255, 14995
\bool_if:NTF	37, 1353, 2104, 2115, 3928, 8562, 9606
\bool_if:nTF	38,
2127, 2144, 3139, 8890, 8900, 15195	
\bool_if_exist:cF	2142
\bool_if_exist:cT	2141
\bool_if_exist:cTF	2136, 2140
\bool_if_exist:NF	2138, 8579, 8594
\bool_if_exist:NT	2137
\bool_if_exist:NTF	37, 2118, 2136, 2136
\bool_if_exist_p:c	2136, 2143

\bool_if_exist_p:N 37, 2136, 2139
 \bool_if_p:c 2104
 \bool_if_p:N 37, 2104, 2112
 \bool_if_p:n 38, 2099, 2101,
 2144, 2146, 2152, 2152, 2225, 2228
 \bool_new:c 2076
 \bool_new:N 36,
 2076, 2076, 2077, 2132, 2133, 2134,
 2135, 6755, 8509, 8579, 8594, 9515
 \bool_not_p:n 39, 2225, 2225
 \bool_set:cn 2098
 .bool_set:N 147
 \bool_set:Nn 37, 2098, 2098, 2102
 \bool_set_eq:cc 2090, 2093
 \bool_set_eq:cN 2090, 2092
 \bool_set_eq:Nc 2090, 2091
 \bool_set_eq:NN 37, 2090, 2090
 \bool_set_false:c 2078
 \bool_set_false:N 36, 264, 2078, 2080,
 2087, 7033, 7436, 8530, 8882, 9608
 .bool_set_inverse:N 148
 \bool_set_true:c 2078
 \bool_set_true:N
 36, 278, 2078, 2078, 2086, 7051,
 7066, 7097, 8525, 8877, 9574, 9645
 \bool_show:c 2116
 \bool_show:N 37, 2116, 2116, 2131
 \bool_show:n 37, 2116, 2119, 2125
 \bool_until_do:cn 2232
 \bool_until_do:Nn 39, 2232, 2234, 2235, 2237
 \bool_until_do:nn 40, 2244, 2257, 2262
 \bool_while_do:cn 2232
 \bool_while_do:Nn 39, 2232, 2232, 2233, 2236
 \bool_while_do:nn 40, 2244, 2244, 2249
 \bool_xor_p:nn 39, 2226, 2226
 \botmark 422
 \botmarks 648
 \box 630
 \box_clear:c 6503
 \box_clear:N 124, 6503,
 6503, 6507, 6510, 6791, 6850, 6899
 \box_clear_new:c 6509
 \box_clear_new:N 124, 6509, 6509, 6513
 \box_clip:c 14418
 \box_clip:N 185, 14418, 14418, 14420
 \box_dp:c 6535, 6921
 \box_dp:N 125,
 6535, 6536, 6539, 6542, 6920, 6991,
 6993, 7010, 7024, 7177, 7195, 7508,
 7548, 14206, 14311, 14341, 14361,
 14380, 14429, 14430, 14433, 14647
 \box_gclear:c 6503
 \box_gclear:N 124, 6503, 6505, 6508, 6512
 \box_gclear_new:c 6509
 \box_gclear_new:N 124, 6509, 6511, 6514
 \box_gset_eq:cc 6515
 \box_gset_eq:cN 6515
 \box_gset_eq:Nc 6515
 \box_gset_eq:NN 124, 6506, 6515, 6517, 6520
 \box_gset_eq_clear:cc 6521
 \box_gset_eq_clear:cN 6521
 \box_gset_eq_clear:Nc 6521
 \box_gset_eq_clear:NN 124, 6521, 6523, 6526
 \box_gset_to_last:c 6583
 \box_gset_to_last:N 127, 6583, 6585, 6588
 \box_ht:c 6535, 6923
 \box_ht:N 126, 6535, 6535, 6538,
 6544, 6846, 6894, 6922, 6987, 6989,
 7010, 7017, 7176, 7194, 7506, 7547,
 14205, 14310, 14340, 14360, 14379,
 14436, 14437, 14440, 14644, 14646
 \box_if_empty:cTF 6577
 \box_if_empty:N 6577
 \box_if_empty:NF 6581
 \box_if_empty:NT 6580
 \box_if_empty:NTF 126, 6577, 6582
 \box_if_empty_p:c 6577
 \box_if_empty_p:N 126, 6577, 6579
 \box_if_exist:cF 6533
 \box_if_exist:cT 6532
 \box_if_exist:cTF 6527, 6531
 \box_if_exist:NF 6529
 \box_if_exist:NT 6528
 \box_if_exist:NTF
 125, 6510, 6512, 6527, 6527, 6631
 \box_if_exist_p:c 6527, 6534
 \box_if_exist_p:N 125, 6527, 6530
 \box_if_horizontal:cTF 6565
 \box_if_horizontal:N 6565
 \box_if_horizontal:NF 6571
 \box_if_horizontal:NT 6570
 \box_if_horizontal:NTF 126, 6565, 6572
 \box_if_horizontal_p:c 6565
 \box_if_horizontal_p:N 126, 6565, 6569
 \box_if_vertical:cTF 6565
 \box_if_vertical:N 6567
 \box_if_vertical:NF 6575
 \box_if_vertical:NT 6574
 \box_if_vertical:NTF 126, 6565, 6576

\box_if_vertical_p:c	6565	\box_set_wd:cn	6541
\box_if_vertical_p:N	126, 6565, 6573	\box_set_wd:Nn	126,
\box_log:c	6610	6541, 6545, 6549, 7178, 7196, 7509,	
\box_log:cnn	6610	14233, 14414, 14423, 14447, 14633	
\box_log:N	127, 6610, 6610, 6612	\box_show:c	6604
\box_log:Nnn	127, 6610, 6611, 6613, 6624	\box_show:cnn	6604
\box_move_down:nn	125, 6554, 6560, 14433, 14455, 14627	\box_show:N	127, 6604, 6604, 6606
\box_move_left:nn	125, 6554, 6554	\box_show:Nnn	127, 6604, 6605, 6607, 6609
\box_move_right:nn	125, 6554, 6556	\box_trim:cnnnn	14421
\box_move_up:nn	125, 6554, 6558, 7215, 7503, 14440, 14463	\box_trim:Nnnnn	186, 14421, 14421, 14444
\box_new:c	6495	\box_use:c	6550
\box_new:N	124, 6495, 6496, 6502, 6510, 6512, 6593, 6599, 6601, 6602, 6603, 6733, 6798, 14190	\box_use:N	125, 6550, 6551, 6553, 7212, 7215, 7293, 7430, 7500, 7503, 14220, 14227, 14235, 14399, 14409, 14415, 14427, 14433, 14440, 14451, 14455, 14463, 14628
\box_resize:cnn	14305	\box_use_clear:c	6550
\box_resize:Nnn	184, 14305, 14305, 14325, 14756	\box_use_clear:N	125, 6550, 6550, 6552
\box_resize_to_ht_plus_dp:cn	14335	\box_viewport:cnnnn	14445
\box_resize_to_ht_plus_dp:Nn	185, 14335, 14335, 14354	\box_viewport:Nnnnn	186, 14445, 14445, 14467
\box_resize_to_wd:cn	14335	\box_wd:c	6535, 6925
\box_resize_to_wd:Nn	185, 14335, 14355, 14371	\box_wd:N	126, 6535, 6537, 6540, 6546, 6924, 6989, 6993, 6999, 7004, 7145, 7178, 7196, 7213, 7501, 7510, 7549, 14207, 14312, 14342, 14362, 14381, 14423, 14646, 14651, 14815, 14822
\box_rotate:Nn	185, 14191, 14191, 14622	\boxmaxdepth	592
\box_scale:cnn	14372	\brokenpenalty	549
\box_scale:Nnn	185, 14372, 14372, 14393, 14778	abs	175
\box_set_dp:cn	6541		
\box_set_dp:Nn	126, 6541, 6541, 6548, 7177, 7195, 7507, 14232, 14403, 14430, 14434, 14456, 14458, 14632		
\box_set_eq:cc	6515		
\box_set_eq:cN	6515		
\box_set_eq:Nc	6515		
\box_set_eq>NN	124, 6504, 6515, 6515, 6518, 6519, 6909, 7197, 7511	C	
\box_set_eq_clear:cc	6521	cc	177
\box_set_eq_clear:cN	6521	nc	177
\box_set_eq_clear:Nc	6521	pc	177
\box_set_eq_clear:NN	124, 6521, 6521, 6524, 6525	\c_coffin_corners_prop	6736, 6736, 6737, 6738, 6739, 6740, 6802, 6939
\box_set_ht:cn	6541	\c_coffin_poles_prop	6741, 6741, 6743, 6744, 6745, 6747, 6748, 6749, 6750, 6751, 6752, 6804, 6941
\box_set_ht:Nn	126, 6541, 6543, 6547, 7176, 7194, 7505, 14231, 14402, 14437, 14441, 14460, 14464, 14630	\c_fp_big_leading_shift_int	9870, 9870, 12390, 12400, 12410
\box_set_to_last:c	6583	\c_fp_big_middle_shift_int	9870, 9871, 12392, 12402, 12412, 12421, 12424, 12427
\box_set_to_last:N	127, 6583, 6583, 6586, 6587	\c_fp_big_trailing_shift_int	9870, 9872, 12434
		\c_fp_Bigg_leading_shift_int	9877, 9877, 12181, 12198

\c_fp_Bigg_middle_shift_int
 9877, 9878, 12184, 12187, 12201, 12204
\c_fp_Bigg_trailing_shift_int
 9877, 9879, 12190, 12207
\c_fp_leading_shift_int
 9864, 9864, 12362, 13161, 13439
\c_fp_ln_i_fixed_tl 12612, 12612
\c_fp_ln_ii_fixed_tl 12612, 12613
\c_fp_ln_iii_fixed_tl 12612, 12614
\c_fp_ln_iv_fixed_tl 12612, 12615
\c_fp_ln_ix_fixed_tl 12612, 12619
\c_fp_ln_vi_fixed_tl 12612, 12616
\c_fp_ln_vii_fixed_tl ... 12612, 12617
\c_fp_ln_viii_fixed_tl ... 12612, 12618
\c_fp_ln_x_fixed_tl
 12612, 12620, 12829, 12836
\c_fp_max_exponent_int
 9765, 9765, 9771,
 9777, 9793, 9794, 12485, 12552,
 12882, 12909, 13196, 13609, 13658
\c_fp_middle_shift_int . 9864, 9865,
 12364, 12367, 12370, 12373, 13163,
 13166, 13169, 13172, 13441, 13443
\c_fp_one_fixed_tl 12299,
 12299, 12783, 12941, 13197, 13221
\c_fp_trailing_shift_int
 9864, 9866, 12376, 13175, 13445
\c_int_from_roman_C_int 4005
\c_int_from_roman_c_int 4005
\c_int_from_roman_D_int 4005
\c_int_from_roman_d_int 4005
\c_int_from_roman_I_int 4005
\c_int_from_roman_i_int 4005
\c_int_from_roman_L_int 4005
\c_int_from_roman_l_int 4005
\c_int_from_roman_M_int 4005
\c_int_from_roman_m_int 4005
\c_int_from_roman_V_int 4005
\c_int_from_roman_v_int 4005
\c_int_from_roman_X_int 4005
\c_int_from_roman_x_int 4005
\c_ior_streams_tl 9219, 9219, 9284, 9393
\c_iow_streams_tl 9393, 9393, 9419
\c_iow_wrap_end_marker_tl .. 9521, 9580
\c_iow_wrap_indent_marker_tl 9521, 9541
\c_iow_wrap_marker_tl
 9521, 9523, 9532, 9590, 9635
\c_iow_wrap_newline_marker_tl
 9521, 9555
\c_iow_wrap_unindent_marker_tl
 9521, 9543
\c_keys_code_root_tl
 8500, 8500, 8674, 8679,
 8956, 8958, 8970, 8976, 8981, 9044
\c_keys_props_root_tl
 8502, 8502, 8536, 8566, 8573, 8753,
 8755, 8757, 8759, 8761, 8763, 8765,
 8767, 8769, 8771, 8773, 8775, 8777,
 8779, 8781, 8783, 8785, 8787, 8789,
 8791, 8793, 8795, 8797, 8799, 8801,
 8803, 8805, 8807, 8809, 8811, 8813,
 8815, 8817, 8819, 8821, 8823, 8825,
 8827, 8829, 8831, 8833, 8835, 8837,
 8839, 8841, 8843, 8845, 8847, 8849
\c_keys_value_forbidden_tl .. 8503, 8503
\c_keys_value_required_tl .. 8503, 8504
\c_keys_vars_root_tl
 8500, 8501, 8636, 8656,
 8662, 8665, 8667, 8684, 8685, 8686,
 8689, 8740, 8917, 8919, 8922, 8930
\c_max_constdef_int 3452, 3456, 3476, 3480
\c_msg_kernel_bug_more_text_tl
 8341, 8349, 8353
\c_msg_kernel_bug_text_tl
 8341, 8344, 8351
\c_msg_more_text_prefix_tl
 7593, 7594, 7632, 7641, 7832
\c_msg_text_prefix_tl 7593,
 7593, 7597, 7630, 7639, 7812, 7823,
 7838, 7855, 7863, 7869, 8248, 8275
\c_t1_act_lowercase_tl
 15101, 15106, 15124
\c_t1_act_uppercase_tl
 15101, 15101, 15116
\c_t1_rescan_marker_tl
 4719, 4727, 4738, 4756
\c_active_char_token 3302, 3303
\c_alignment_tab_token 3296, 3297
\c_alignment_token
 52, 2692, 2698, 2748, 3297
\c_catcode_active_tl
 52, 2707, 2709, 2786, 3303
\c_catcode_letter_token
 52, 2692, 2704, 2776, 3299
\c_catcode_other_space_tl
 162, 9516, 9519, 9531, 9533, 9535, 9556
\c_catcode_other_token
 52, 2692, 2705, 2781, 3300
\c_code_cctab ... 182, 14115, 14117, 14118

```

\c_document_cctab ..... 183, 14115, 14123, 14132, 14135
\c_e_fp ..... 170, 13874, 13874
\c_eight ..... 71, 2620, 2652,
    4004, 4069, 4074, 9229, 9956, 10662,
    10694, 12875, 13247, 13260, 13386
\c_eleven ..... 71, 2626, 2658,
    4069, 4077, 9232, 11914, 11989, 12030
\c_empty_box ..... 127, 6504, 6506, 6589, 6590, 6593, 7290
\c_empty_list ..... 117, 5786, 5786, 5891, 5906, 5928, 5944
\c_empty_coffin 135, 6914, 6914, 6915, 7291
\c_empty_prop ..... 123, 6201,
    6201, 6202, 6203, 6204, 6206, 6355
\c_empty_seq .. 108, 5383, 5383, 5541, 5549
\c_empty_tl ..... 99, 3817, 4583, 4599,
    4601, 4632, 4632, 4841, 5383, 5786
\c_false_bool ..... 20,
    925, 964, 1004, 1009, 1053, 1054,
    1075, 1299, 1306, 1475, 1477, 1486,
    1498, 1909, 2076, 2081, 2085, 2200,
    2202, 2206, 2229, 3917, 3922, 3931
\c_fifteen ..... 71, 2634, 2666, 4069,
    4080, 9236, 9343, 9477, 11067, 11204
\c_five ..... 71, 2614, 2646, 4069,
    4073, 9226, 10209, 11199, 12228, 12882
\c_four ... 71, 2612, 2644, 4069, 4072,
    9225, 9649, 9655, 11200, 12449,
    12490, 12583, 12655, 12834, 13483
\c_fourteen ..... 71,
    2632, 2664, 4069, 4079, 9235, 11204
\c_group_begin_token ..... 52, 2692, 2692, 2733,
    3141, 5212, 5247, 6651, 6699, 15197
\c_group_end_token ... 52, 2692, 2693,
    2738, 3142, 6656, 6657, 6707, 15198
\c_inf_fp ..... 169, 9760,
    9762, 11024, 11593, 12057, 12137,
    12851, 13085, 13089, 13110, 13378
\c_initex_cctab ..... 183, 14115, 14124
\c_job_name_tl .... 99, 4633, 4646, 4650
\c_keys_code_root_tl ..... 9044
\c_letter_token ..... 3296, 3299
\c_log_iow ... 162, 9391, 9391, 9498, 9499
\c_luatex_is_engine_bool ... 1587, 1588
\c_math_shift_token ..... 3296, 3298
\c_math_subscript_token ..... 52, 2692, 2702, 2766
\c_math_superscript_token ..... 52, 2692, 2700, 2761
\c_math_toggle_token ..... 52, 2692, 2696, 2743, 3298
\c_max_dim ..... 79, 4376, 4378, 4379, 4383, 4480,
    14698, 14699, 14700, 14701, 14718
\c_max_int .... 71, 4087, 4087, 6605, 6611
\c_max_muskip ..... 85, 4547, 4548
\c_max_register_int ..... 71, 812, 813, 815, 8127, 14035, 14066
\c_max_skip ..... 82, 4479, 4480
\c_minus_inf_fp .... 169, 9760, 9763,
    11585, 12058, 12140, 12628, 13380
\c_minus_one 71, 800, 801, 804, 805, 1160,
    1320, 3454, 3521, 4069, 4739, 4740,
    7756, 9385, 9391, 9522, 9548, 10921,
    11290, 11584, 11746, 12312, 12531,
    13240, 13249, 13275, 13434, 14027
\c_minus_zero_fp . 169, 9760, 9761, 12054
\c_msg_continue_text_tl 7646, 7651, 7690
\c_msg_critical_text_tl 7646, 7653, 7826
\c_msg_fatal_text_tl ... 7646, 7655, 7815
\c_msg_help_text_tl ... 7646, 7657, 7694
\c_msg_no_info_text_tl . 7646, 7659, 7689
\c_msg_on_line_text_tl . 7646, 7664, 7681
\c_msg_return_text_tl ..... 7646,
    7662, 7665, 8065, 8073, 8080, 8357
\c_msg_trouble_text_tl ..... 7646, 7672
\c_nan_fp ..... 9760, 9764,
    10064, 10072, 10144, 10452, 10459,
    10510, 10531, 11025, 11114, 13058
\c_nine ..... 71, 2622, 2654,
    4069, 4075, 9230, 10380, 10407,
    10568, 10589, 10616, 10630, 10665,
    10692, 10755, 10771, 10816, 10832,
    10843, 10895, 11197, 11198, 12040
\c_one 71, 2606, 2638, 3428, 3519, 4069,
    4069, 5000, 5722, 6143, 6147, 6608,
    7990, 7996, 9222, 9569, 9793, 9986,
    10187, 10239, 10240, 10243, 10320,
    10345, 10578, 10642, 10652, 10817,
    10837, 10851, 11108, 11145, 11395,
    11400, 11407, 11592, 11708, 11720,
    11724, 11840, 11865, 11904, 11958,

```

11961, 11983, 11987, 12007, 12031,
 12047, 12118, 12151, 12240, 12242,
 12269, 12324, 12464, 12500, 12541,
 12570, 12639, 12685, 12780, 12876,
 12878, 12923, 13217, 13227, 13242,
 13262, 13265, 13278, 13352, 13473,
 13565, 13626, 13631, 13890, 14035,
 14483, 14901, 14913, 15155, 15166
`\c_one_degree_fp` 170, 11027, 13876, 13877
`\c_one_fp` 11028,
 11030, 11247, 11252, 11257, 11268,
 11630, 12845, 13053, 13100, 13302,
 13332, 13405, 13411, 13874, 13875
`\c_one_hundred` 71, 4084, 4084
`\c_one_thousand`
 . 71, 4084, 4085, 12505, 12514, 12519
`\c_other_cctab`
 183, 14115, 14125, 14133, 14143
`\c_other_char_token` 3296, 3300
`\c_parameter_token`
 52, 2692, 2699, 2752, 2755
`\c_pdftex_is_engine_bool` 1587, 1589
`\c_pi_fp` 170, 11026, 13876, 13876
`\c_seven` 71,
 800, 810, 2618, 2650, 4069, 9228,
 10701, 11277, 11322, 11935, 12042
`\c_six` . 71, 800, 809, 2616, 2648, 4069, 9227
`\c_sixteen` 71, 800, 807, 1162,
 4002, 4069, 9218, 9244, 9283, 9285,
 9309, 9327, 9367, 9392, 9402, 9418,
 9420, 9443, 9461, 9890, 9960, 10296,
 11079, 11101, 11144, 12897, 13248,
 13253, 13677, 13679, 13685, 13726
`\c_space_tl`
 . 99, 4652, 4652, 5101, 6139, 6148,
 7682, 9175, 9567, 9581, 9651, 13817
`\c_space_token` 52, 2692, 2703,
 2771, 3143, 3162, 5213, 5248, 15199
`\c_str_cctab`
 183, 14115, 14126, 14134, 14148, 14169
`\c_string_cctab` 14168, 14169
`\c_ten` 71, 2624, 2656, 3842, 4069,
 4076, 9231, 11195, 11196, 12039, 12656
`\c_ten_thousand`
 . 71, 4084, 4086, 12305, 12383, 12444
`\c_term_ior` ... 162, 9218, 9218, 9252, 9347
`\c_term_iow`
 162, 9391, 9392, 9410, 9481, 9500, 9501
`\c_thirteen` 71, 2630, 2662, 4069, 4078, 9234
`\c_thirty_two` 71, 4081, 4081, 11194
`\c_three` 71, 2610, 2642, 4069, 4071, 9224,
 9795, 10465, 10493, 10964, 11344,
 11348, 11358, 11744, 12034, 13367
`\c_token_A_int` 3003, 3038
`\c_true_bool` 20,
 964, 1053, 1053, 1074, 1317, 1476,
 1487, 1497, 2079, 2083, 2106, 2201,
 2203, 2207, 2230, 3917, 3922, 3935
`\c_twelve` 71, 800, 811, 2331, 2346, 2628,
 2660, 2851, 4069, 9233, 11127, 11130
`\c_two` 71, 2608, 2640,
 3428, 4000, 4069, 4070, 7991, 9223,
 9790, 9794, 11364, 11504, 11660,
 11891, 12022, 12037, 12040, 12042,
 12222, 12286, 12336, 12485, 12552,
 12788, 12909, 13196, 13227, 13307,
 13337, 13460, 13483, 13494, 13536,
 13565, 13729, 14033, 14065, 14073
`\c_two_hundred_fifty_five` 71, 4082, 4082
`\c_two_hundred_fifty_six` . 71, 4082, 4083
`\c_undefined:D` 1273, 1281,
 10012, 10023, 10024, 10025, 10026
`\c_undefined_fp` 13885, 13885
`\c_xetex_is_engine_bool` 1587, 1590
`\c_zero` 71, 800, 808, 964, 974, 979, 984,
 1061, 1063, 1504, 1509, 1514, 1542,
 1657, 1666, 2302, 2305, 2306, 2307,
 2308, 2309, 2310, 2311, 2312, 2313,
 2314, 2324, 2326, 2497, 2504, 2521,
 2548, 2557, 2604, 2636, 2820, 3423,
 3482, 3483, 3539, 3680, 3683, 3815,
 4069, 4366, 4446, 5093, 5284, 5285,
 6617, 6618, 8236, 9221, 9244, 9341,
 9402, 9475, 9724, 9726, 9795, 9955,
 9980, 10191, 10195, 10197, 10201,
 10205, 10218, 10230, 10241, 10242,
 10251, 10255, 10259, 10262, 10267,
 10271, 10303, 10308, 10484, 10489,
 10499, 10547, 10614, 10683, 10736,
 10784, 10798, 10826, 10875, 10903,
 10928, 10954, 11147, 11172, 11377,
 11496, 11675, 11680, 11956, 12240,
 12810, 12814, 12828, 12886, 12892,
 12906, 13096, 13108, 13126, 13149,
 13181, 13256, 13257, 13271, 13273,
 13292, 13322, 13391, 13675, 13700,
 14479, 14494, 14514, 14900, 15154
`\c_zero_dim` 79,
 4166, 4376, 4377, 4382, 4479, 6680,
 7047, 7050, 7053, 7062, 7065, 7068,

7077, 7084, 7141, 7146, 7153, 14434,
 14441, 14453, 14456, 14459, 14464
`\c_zero_fp` 169, 9760, 9760, 9803,
 11029, 11248, 11253, 11258, 11267,
 11632, 11887, 12053, 12854, 13080,
 13113, 13764, 13827, 13842, 13843,
 14209, 14211, 14216, 14404, 14766
`\c_zero_muskip` 85, 4500, 4547, 4547
`\c_zero_skip` 82,
 4403, 4479, 4479, 6666, 15049, 15050
`\catcode` 4, 5, 6, 7, 10, 112, 113, 114, 115,
 116, 117, 118, 119, 120, 126, 127,
 128, 129, 130, 131, 132, 133, 236,
 237, 238, 239, 240, 241, 242, 243, 634
`\catcodetable` 727
`\CatcodeTableIniTeX` 14124
`\CatcodeTableLaTeX` 14123
`\CatcodeTableOther` 14125
`\CatcodeTableString` 14126
`\cctab_begin:N`
 182, 14061, 14061, 14081, 14084, 14095
`\cctab_end:`
 182, 14061, 14071, 14086, 14089, 14096
`\cctab_gset:Nn` 182, 14100, 14100, 14109,
 14112, 14118, 14135, 14143, 14148
`\cctab_new:N`
 . 182, 14030, 14030, 14044, 14047,
 14053, 14117, 14132, 14133, 14134
`\char` 488, 2862
`\char_gset_active:Npn` . 194, 15173, 15187
`\char_gset_active:Npx` 15173, 15188
`\char_gset_active_eq:NN` 195, 15173, 15190
`\char_make_active:N` 3305, 3321
`\char_make_active:n` 3305, 3339
`\char_make_alignment:N` 3305
`\char_make_alignment:n` 3305
`\char_make_alignment_tab:N` 3310
`\char_make_alignment_tab:n` 3328
`\char_make_begin_group:N` 3307
`\char_make_begin_group:n` 3325
`\char_make_comment:N` 3305, 3322
`\char_make_comment:n` 3305, 3340
`\char_make_end_group:N` 3308
`\char_make_end_group:n` 3326
`\char_make_end_line:N` 3305, 3311
`\char_make_end_line:n` 3305, 3329
`\char_make_escape:N` 3305, 3306
`\char_make_escape:n` 3305, 3324
`\char_make_group_begin:N` 3305
`\char_make_group_begin:n` 3305
`\char_make_group_end:N` 3305
`\char_make_group_end:n` 3305
`\char_make_ignore:N` 3305, 3317
`\char_make_ignore:n` 3305, 3335
`\char_make_invalid:N` 3305, 3323
`\char_make_invalid:n` 3305, 3341
`\char_make_letter:N` 3305, 3319
`\char_make_letter:n` 3305, 3337
`\char_make_math_shift:N` 3309
`\char_make_math_shift:n` 3327
`\char_make_math_subscript:N` . 3305, 3315
`\char_make_math_subscript:n` . 3305, 3333
`\char_make_math_superscript:N` 3305, 3313
`\char_make_math_superscript:n` 3305, 3331
`\char_make_math_toggle:N` 3305
`\char_make_math_toggle:n` 3305
`\char_make_other:N` 3305, 3320
`\char_make_other:n` 3305, 3338
`\char_make_parameter:N` 3305, 3312
`\char_make_parameter:n` 3305, 3330
`\char_make_space:N` 3305, 3318
`\char_make_space:n` 3305, 3336
`\char_set_active:Npn` .. 194, 15173, 15185
`\char_set_active:Npx` 15173, 15186
`\char_set_active_eq:NN` 194, 15173, 15189
`\char_set_catcode:nn` 50, 253,
 254, 255, 256, 257, 258, 259, 260,
 261, 2597, 2597, 2604, 2606, 2608,
 2610, 2612, 2614, 2616, 2618, 2620,
 2622, 2624, 2626, 2628, 2630, 2632,
 2634, 2636, 2638, 2640, 2642, 2644,
 2646, 2648, 2650, 2652, 2654, 2656,
 2658, 2660, 2662, 2664, 2666, 2851
`\char_set_catcode:w` 3268, 3269, 3276, 3278
`\char_set_catcode_active:N` 49,
 2603, 2629, 2708, 2715, 2716, 2717,
 2718, 2719, 2720, 3321, 7715, 15174
`\char_set_catcode_active:n` . 49, 2635,
 2661, 3339, 8396, 8397, 14141, 15179
`\char_set_catcode_alignment:N`
 49, 2603, 2611, 2697, 3310
`\char_set_catcode_alignment:n`
 49, 271, 2635, 2643, 3328
`\char_set_catcode_comment:N`
 49, 2603, 2631, 3322
`\char_set_catcode_comment:n`
 49, 2635, 2663, 3340
`\char_set_catcode_end_line:N`
 49, 2603, 2613, 3311

\char_set_catcode_end_line:n
 49, 2635, 2645, 3329
\char_set_catcode_escape:N
 49, 2603, 2603, 3306
\char_set_catcode_escape:n
 49, 2635, 2635, 3324
\char_set_catcode_group_begin:N
 49, 2603, 2605, 3307
\char_set_catcode_group_begin:n
 49, 2635, 2637, 3325
\char_set_catcode_group_end:N
 49, 2603, 2607, 3308
\char_set_catcode_group_end:n
 49, 2635, 2639, 3326
\char_set_catcode_ignore:N
 49, 2603, 2621, 3317
\char_set_catcode_ignore:n
 49, 268, 269, 2635, 2653, 3335
\char_set_catcode_invalid:N
 49, 2603, 2633, 3323
\char_set_catcode_invalid:n
 49, 2635, 2665, 3341
\char_set_catcode_letter:N
 49, 2603, 2625, 3319, 10948,
 11138, 11203, 11218, 11219, 11341,
 11374, 11392, 11636, 11637, 13407
\char_set_catcode_letter:n
 49, 272, 274, 2635, 2657, 3337
\char_set_catcode_math_subscript:N
 49, 2603, 2619, 2701, 3316
\char_set_catcode_math_subscript:n
 49, 2635, 2651, 3334, 14140
\char_set_catcode_math_superscript:N
 49, 2603, 2617, 3314, 8221
\char_set_catcode_math_superscript:n
 49, 273, 2635, 2649, 3332
\char_set_catcode_math_toggle:N
 49, 2603, 2609, 2695, 3309
\char_set_catcode_math_toggle:n
 49, 2635, 2641, 3327
\char_set_catcode_other:N
 49, 2603, 2627, 2805, 2806,
 3005, 3320, 9517, 10362, 10363,
 10364, 10418, 10419, 11193, 13592
\char_set_catcode_other:n 49, 270, 275,
 2635, 2659, 3338, 14139, 14146, 14151
\char_set_catcode_parameter:N
 49, 2603, 2615, 3312
\char_set_catcode_parameter:n
 49, 2635, 2647, 3330
\char_set_catcode_space:N
 49, 2603, 2623, 3318
\char_set_catcode_space:n 49, 276,
 2635, 2655, 3336, 14137, 14138, 14152
\char_set_lccode:nn 50, 2667,
 2673, 2807, 2808, 2809, 2845, 2846,
 2847, 2848, 2849, 3006, 3007, 3008,
 7712, 7713, 7714, 8222, 8223, 8224,
 8225, 8398, 8399, 9518, 10365, 15181
\char_set_lccode:w 3268, 3271, 3282, 3284
\char_set_mathcode:nn 51, 2667, 2667
\char_set_mathcode:w 3268, 3270, 3279, 3281
\char_set_sfcode:nn 51, 2667, 2685
\char_set_sfcode:w 3268, 3273, 3288, 3290
\char_set_uccode:nn 51, 2667, 2679
\char_set_uccode:w 3268, 3272, 3285, 3287
\char_show_value_catcode:n 50, 2597, 2601
\char_show_value_catcode:w 3275, 3277
\char_show_value_lccode:n 50, 2667, 2677
\char_show_value_lccode:w 3275, 3283
\char_show_value_mathcode:n
 51, 2667, 2671
\char_show_value_mathcode:w 3275, 3280
\char_show_value_sfcode:n 52, 2667, 2689
\char_show_value_sfcode:w 3275, 3289
\char_show_value_uccode:n 51, 2667, 2683
\char_show_value_uccode:w 3275, 3286
\char_tmp>NN 15175, 15185,
 15186, 15187, 15188, 15189, 15190
\char_value_catcode:n 50, 253, 254, 255,
 256, 257, 258, 259, 260, 261, 2597, 2599
\char_value_catcode:w 3275, 3276
\char_value_lccode:n 50, 2667, 2675
\char_value_lccode:w 3275, 3282
\char_value_mathcode:n 51, 2667, 2669
\char_value_mathcode:w 3275, 3279
\char_value_sfcode:n 51, 2667, 2687
\char_value_sfcode:w 3275, 3288
\char_value_uccode:n 51, 2667, 2681
\char_value_uccode:w 3275, 3285
\chardef 122, 135, 138, 283, 323
\chk_if_free_cs:N 1605, 1605
.choice: 148
.choice_code:n 148
.choice_code:x 148
.choices:nn 148
\cleaders 506
\clist__if_eq>NN 6183
\clist_clear:c 5791, 5792

```

\clist_clear:N ..... 110, 5791, 5791, 5980, 8866, 14530
\clist_clear_new:c ..... 5795, 5796
\clist_clear_new:N ..... 110, 5795, 5795
\clist_concat:ccc ..... 5807
\clist_concat:NNN ..... 111, 5807, 5807, 5820, 5864, 5877
\clist_const:cn ..... 14557
\clist_const:cx ..... 14557
\clist_const:Nn ..... 187, 14557, 14557, 14559
\clist_const:Nx ..... 14557
\clist_count:c ..... 6125, 6188
\clist_count:N ..... 115, 6125, 6125, 6133, 6187, 14472, 14578
\clist_count:n ..... 6125, 6134, 6189, 14502
\clist_display:c ..... 6173, 6175
\clist_display:N ..... 6173, 6174
\clist_gclear:c ..... 5791, 5794
\clist_gclear:N ..... 110, 5791, 5793, 14532
\clist_gclear_new:c ..... 5795, 5798
\clist_gclear_new:N ..... 110, 5795, 5797
\clist_gconcat:ccc ..... 5807
\clist_gconcat:NNN ..... 111, 5807, 5809, 5821, 5866, 5879
\clist_get:cN ..... 5889, 6167
\clist_get:cNTF ..... 5926
\clist_get:NN ..... 115, 5889, 5899, 5926, 6166
\clist_get>NNF ..... 5936
\clist_get:NNT ..... 5935
\clist_get:NNTF ..... 115, 5926, 5937
\clist_gpop:cN ..... 5900
\clist_gpop:cNTF ..... 5926
\clist_gpop>NN ..... 116, 5900, 5902, 5925, 5940
\clist_gpop>NNF ..... 5955
\clist_gpop>NNT ..... 5954
\clist_gpop>NNTF ..... 116, 5926, 5956
\clist_gpush:cn ..... 5957, 5969
\clist_gpush:co ..... 5957, 5971
\clist_gpush:cV ..... 5957, 5970
\clist_gpush:cx ..... 5957, 5972
\clist_gpush:Nn ..... 116, 5957, 5965
\clist_gpush>No ..... 5957, 5967
\clist_gpush:NV ..... 5957, 5966
\clist_gpush:Nx ..... 5957, 5968
\clist_gput_left:cn ..... 5863, 5969
\clist_gput_left:co ..... 5863, 5971
\clist_gput_left:cV ..... 5863, 5970
\clist_gput_left:cx ..... 5863, 5972
\clist_gput_left:Nn ..... 111, 5863, 5865, 5874, 5875, 5965
\clist_gput_left:No ..... 5863, 5967
\clist_gput_left:NV ..... 5863, 5966
\clist_gput_left:Nx ..... 5863, 5968
\clist_gput_right:cn ..... 5876
\clist_gput_right:co ..... 5876
\clist_gput_right:cV ..... 5876
\clist_gput_right:cx ..... 5876
\clist_gput_right:Nn ..... 111, 5876, 5878, 5887, 5888
\clist_gput_right:No ..... 5876
\clist_gput_right:NV ..... 5876
\clist_gput_right:Nx ..... 5876
\clist_gremove_all:cN ..... 5990
\clist_gremove_all:Nn ..... 112, 5990, 5992, 6020, 6171
\clist_gremove_duplicates:c ..... 5974
\clist_gremove_duplicates:N ..... 112, 5974, 5976, 5989
\clist_gremove_element:Nn ..... 6169, 6171
\clist_gset:c ..... 148
\clist_gset:cn ..... 5857
\clist_gset:co ..... 5857
\clist_gset:cV ..... 5857
\clist_gset:cx ..... 5857
\clist_gset:N ..... 148
\clist_gset:Nn ..... 111, 5857, 5859, 5862
\clist_gset:No ..... 5857, 6179
\clist_gset:NV ..... 5857
\clist_gset:Nx ..... 5857
\clist_gset_eq:cc ..... 5799, 5806
\clist_gset_eq:cN ..... 5799, 5805
\clist_gset_eq:Nc ..... 5799, 5804
\clist_gset_eq>NN ..... 111, 5799, 5803, 5977
\clist_gset_from_seq:cc ..... 14529
\clist_gset_from_seq:cN ..... 14529
\clist_gset_from_seq:Nc ..... 14529
\clist_gset_from_seq>NN ..... 187, 14529, 14531, 14555, 14556
\clist_gtrim_spaces:c ..... 6177
\clist_gtrim_spaces:N ..... 6177, 6179, 6181
\clist_if_empty:c ..... 6022
\clist_if_empty:cTF ..... 6021
\clist_if_empty:N ..... 6021
\clist_if_empty:n ..... 14560
\clist_if_empty:NF ..... 5816, 6007, 6050, 6080, 6099
\clist_if_empty:NTF ..... 112, 6021, 8198
\clist_if_empty:nTF ..... 187, 14560

```

```

\clist_if_empty_p:c ..... 6021 \clist_map_function:NN ... 113, 6048,
\clist_if_empty_p:N ..... 112, 6021 6048, 6063, 6130, 6153, 14947, 14957
\clist_if_empty_p:n ..... 187, 14560 \clist_map_function:nN ..... .
\clist_if_eq:cc ..... 6186 . 6064, 6064, 8640, 8710, 14952, 14962
\clist_if_eq:ccTF ..... 6183 \clist_map_inline:cn ..... 6078
\clist_if_eq:cN ..... 6185 \clist_map_inline:Nn ..... 113, 5981,
\clist_if_eq:cNTF ..... 6183 6078, 6078, 6094, 6096, 9198, 9213
\clist_if_eq:Nc ..... 6184 \clist_map_inline:nn 6078, 6091, 8621, 8725
\clist_if_eq:NcTF ..... 6183 \clist_map_variable:cNn ..... 6097
\clist_if_eq:NNTF ..... 6183 \clist_map_variable:NNn ..... .
\clist_if_eq_p:cc ..... 6183 ..... 114, 6097, 6097, 6111, 6120
\clist_if_eq_p:cN ..... 6183 \clist_map_variable:nNn ..... 6097, 6108
\clist_if_eq_p:Nc ..... 6183 \clist_new:c ..... 5789, 5790
\clist_if_eq_p:NN ..... 6183 \clist_new:N ..... 110, 5789,
\clist_if_exist:cF ..... 5828 5789, 5973, 6161, 6162, 6163, 6164
\clist_if_exist:cT ..... 5827 \clist_pop:cN ..... 5900
\clist_if_exist:cTF ..... 5822, 5826 \clist_pop:cNTF ..... 5926
\clist_if_exist:NF ..... 5824 \clist_pop>NN . 116, 5900, 5900, 5924, 5938
\clist_if_exist:NT ..... 5823, 9196 \clist_pop>NNF ..... 5952
\clist_if_exist:NTF ..... . 5951
..... 111, 5822, 5822, 9169, 14576 \clist_pop:NNTF ..... 116, 5926, 5953
\clist_if_exist_p:c ..... 5822, 5829 \clist_push:cn ..... 5957, 5961
\clist_if_exist_p:N ..... 111, 5822, 5825 \clist_push:co ..... 5957, 5963
\clist_if_in:cnTF ..... 6023 \clist_push:cV ..... 5957, 5962
\clist_if_in:coTF ..... 6023 \clist_push:cx ..... 5957, 5964
\clist_if_in:cVTF ..... 6023 \clist_push:Nn ..... 116, 5957, 5957
\clist_if_in:Nn ..... 6023 \clist_push:No ..... 5957, 5959
\clist_if_in:nn ..... 6027 \clist_push:NV ..... 5957, 5958
\clist_if_in:NnF ..... 5983, 6041, 6042 \clist_push:Nx ..... 5957, 5960
\clist_if_in:nnF ..... 6046 \clist_put_left:cn ..... 5863, 5961
\clist_if_in:NnT ..... 6039, 6040 \clist_put_left:co ..... 5863, 5963
\clist_if_in:nnT ..... 6045 \clist_put_left:cV ..... 5863, 5962
\clist_if_in:NnTF ..... 113, 6023, 6043, 6044 \clist_put_left:cx ..... 5863, 5964
\clist_if_in:nnTF ..... 6023, 6047, 10031 \clist_put_left:Nn ..... .
..... 111, 5863, 5863, 5872, 5873, 5957
\clist_if_in:NoTF ..... 6023 \clist_put_left:No ..... 5863, 5959
\clist_if_in:noTF ..... 6023 \clist_put_left:NV ..... 5863, 5958
\clist_if_in:NVTF ..... 6023 \clist_put_left:Nx ..... 5863, 5960
\clist_if_in:nVTF ..... 6023 \clist_put_right:cn ..... 5876
\clist_item:cn ..... 14469 \clist_put_right:co ..... 5876
\clist_item:Nn ..... 187, 14469, 14469, 14498 \clist_put_right:cV ..... 5876
\clist_item:nn ..... 14499, 14499 \clist_put_right:cx ..... 5876
\clist_length:c ..... 6187, 6189 \clist_put_right:Nn ..... .
\clist_length:N ..... 6187, 6187 ..... 111, 5876, 5876, 5885, 5886, 5984
\clist_length:n ..... 6187, 6188 \clist_put_right:No ..... 5876
\clist_map_break: ..... 6087, 6105, 6121, 6121, 6122, 6124 \clist_put_right:NV ..... 5876
\clist_map_break:n ..... 115, 6121, 6123 \clist_put_right:Nx ..... 5876, 8947
\clist_map_function:cN ..... 6048 \clist_remove_all:cn ..... 5990
..... 112, 5990, 5990, 6019, 6170

```


\color 7356, 7368, 7411, 7451
\color_ensure_current: 136, 6814, 6858,
6881, 7565, 7566, 7570, 7575, 7580
\color_group_begin:
136, 6813, 6835, 6858, 6881, 7559, 7559
\color_group_end:
136, 6816, 6837, 6861, 6884, 7559, 7560
\columnwidth 6833, 6879
\copy 574
\count 625
\countdef 324
\cr 349
\crcr 350
\cs:w 16, 768, 770, 785, 787,
846, 1107, 1135, 1343, 1392, 1621,
1660, 1674, 1676, 1680, 1681, 1682,
1717, 1723, 1743, 1745, 1750, 1757,
1758, 1820, 1824, 1854, 2054, 2279,
2281, 3536, 5317, 9859, 9888, 10441,
10476, 10674, 10706, 10969, 10997,
11065, 11125, 12672, 12940, 13225
\cs_end: 16, 768, 771, 785, 787, 791, 846,
1101, 1107, 1129, 1135, 1276, 1343,
1392, 1621, 1660, 1674, 1676, 1680,
1681, 1682, 1717, 1723, 1743, 1745,
1750, 1757, 1758, 1820, 1824, 1854,
2054, 2276, 2282, 2283, 2284, 2285,
2287, 2289, 2291, 2293, 2295, 2297,
2299, 3536, 5317, 9859, 9896, 10017,
10441, 10476, 10678, 10710, 10972,
11003, 11018, 12672, 12940, 13225
\cs_generate_from_arg_count:cNnn ...
..... 1325, 1334
\cs_generate_from_arg_count:Ncnn ...
..... 1325, 1336
\cs_generate_from_arg_count:NNnn ...
.... 15, 1325, 1325, 1335, 1337, 1355
\cs_generate_variant:Nn
.... 27, 1868, 1868, 2057, 2058,
2059, 2060, 2061, 2062, 2063, 2064,
2065, 2077, 2086, 2087, 2088, 2089,
2102, 2103, 2112, 2113, 2114, 2115,
2131, 2236, 2237, 2242, 2243, 2510,
2511, 2541, 2542, 2543, 2544, 2563,
2564, 2565, 2566, 3451, 3472, 3484,
3485, 3490, 3491, 3493, 3494, 3496,
3497, 3514, 3515, 3516, 3517, 3526,
3527, 3528, 3529, 3533, 3534, 3947,
4159, 4165, 4168, 4169, 4174, 4175,
4187, 4188, 4190, 4191, 4193, 4194,
4198, 4199, 4203, 4204, 4371, 4373,
4396, 4402, 4405, 4406, 4411, 4412,
4424, 4425, 4427, 4428, 4430, 4431,
4435, 4436, 4440, 4441, 4466, 4473,
4474, 4476, 4492, 4498, 4502, 4503,
4508, 4509, 4521, 4522, 4524, 4525,
4527, 4528, 4532, 4533, 4537, 4538,
4542, 4544, 4568, 4569, 4570, 4571,
4585, 4596, 4597, 4602, 4603, 4608,
4609, 4622, 4623, 4665, 4666, 4667,
4668, 4669, 4670, 4687, 4688, 4689,
4690, 4691, 4692, 4693, 4694, 4711,
4712, 4713, 4714, 4715, 4716, 4717,
4718, 4759, 4760, 4761, 4762, 4775,
4776, 4777, 4778, 4821, 4822, 4827,
4828, 4831, 4832, 4833, 4834, 4835,
4836, 4837, 4838, 4847, 4848, 4849,
4850, 4859, 4860, 4861, 4862, 4882,
4883, 4884, 4885, 4904, 4905, 4906,
4913, 4914, 4915, 4933, 4948, 4960,
4976, 4983, 4989, 5001, 5002, 5025,
5026, 5124, 5135, 5136, 5155, 5165,
5197, 5198, 5199, 5200, 5297, 5310,
5311, 5350, 5434, 5435, 5440, 5441,
5454, 5455, 5456, 5457, 5462, 5463,
5464, 5465, 5482, 5483, 5508, 5509,
5533, 5534, 5535, 5536, 5537, 5538,
5567, 5579, 5580, 5597, 5624, 5625,
5630, 5631, 5632, 5633, 5634, 5635,
5644, 5645, 5646, 5647, 5648, 5649,
5650, 5651, 5652, 5653, 5654, 5655,
5672, 5701, 5712, 5713, 5723, 5761,
5777, 5820, 5821, 5861, 5862, 5872,
5873, 5874, 5875, 5885, 5886, 5887,
5888, 5899, 5924, 5925, 5935, 5936,
5937, 5951, 5952, 5953, 5954, 5955,
5956, 5988, 5989, 6019, 6020, 6039,
6040, 6041, 6042, 6043, 6044, 6045,
6046, 6047, 6063, 6096, 6120, 6133,
6160, 6180, 6181, 6205, 6207, 6210,
6213, 6244, 6245, 6246, 6247, 6256,
6257, 6275, 6276, 6277, 6278, 6297,
6298, 6299, 6300, 6301, 6302, 6322,
6324, 6326, 6328, 6343, 6344, 6361,
6362, 6363, 6364, 6388, 6389, 6390,
6391, 6392, 6393, 6394, 6395, 6407,
6408, 6409, 6410, 6411, 6412, 6425,
6426, 6437, 6447, 6459, 6460, 6466,
6467, 6468, 6471, 6502, 6507, 6508,
6513, 6514, 6519, 6520, 6525, 6526,

6538, 6539, 6540, 6547, 6548, 6549,
6552, 6553, 6569, 6570, 6571, 6572,
6573, 6574, 6575, 6576, 6579, 6580,
6581, 6582, 6587, 6588, 6606, 6609,
6612, 6624, 6642, 6643, 6648, 6649,
6654, 6655, 6673, 6674, 6684, 6685,
6690, 6691, 6696, 6697, 6702, 6703,
6718, 6719, 6774, 6775, 6776, 6777,
6795, 6806, 6823, 6853, 6870, 6904,
6913, 6981, 6982, 6983, 7171, 7199,
7295, 7402, 7488, 7525, 8003, 8278,
8362, 8363, 8364, 8522, 8670, 8681,
8690, 8696, 8751, 8752, 8859, 8860,
8873, 8874, 9161, 9179, 9251, 9253,
9257, 9277, 9278, 9279, 9293, 9351,
9409, 9411, 9414, 9485, 9491, 9494,
9497, 10147, 13585, 13640, 13708,
13741, 13745, 13791, 13828, 13835,
13836, 13837, 13840, 13841, 13844,
13845, 13850, 13851, 13858, 13859,
13860, 13861, 13873, 13913, 13914,
13915, 13916, 13925, 13926, 13927,
13928, 13929, 13930, 13935, 13936,
13979, 13980, 13991, 13992, 14017,
14020, 14021, 14024, 14325, 14354,
14371, 14393, 14420, 14444, 14467,
14498, 14553, 14554, 14555, 14556,
14559, 14640, 14759, 14788, 14863,
14864, 14878, 14892, 14917, 14942,
14943, 14964, 14965, 14966, 14967,
14968, 14969, 14987, 14988, 15171
\cs_gnew:cpn 1566
\cs_gnew:cpx 1570
\cs_gnew:Npn 1558
\cs_gnew:Npx 1562
\cs_gnew_eq:cc 1578
\cs_gnew_eq:cN 1576
\cs_gnew_eq:Nc 1577
\cs_gnew_eq:NN 1575
\cs_gnew_nopar:cpn 1565
\cs_gnew_nopar:cpx 1569
\cs_gnew_nopar:Npn 1557
\cs_gnew_nopar:Npx 1561
\cs_gnew_protected:cpn 1568
\cs_gnew_protected:cpx 1572
\cs_gnew_protected:Npn 1560
\cs_gnew_protected:Npx 1564
\cs_gnew_protected_nopar:cpn 1567
\cs_gnew_protected_nopar:cpx 1571
\cs_gnew_protected_nopar:Npn 1559
\cs_gnew_protected_nopar:Npx 1563
\cs_gset:cn 1387
\cs_gset:cpx 1238, 1241
\cs_gset:cpx 1387
\cs_gset:Nn 14, 1338
\cs_gset:Npn 12, 831, 833, 1224, 1240, 5676, 15187
\cs_gset:Npx
... 831, 835, 1225, 1241, 5681, 15188
\cs_gset:Nx 1338
\cs_gset_eq:cc 1256, 1263, 2097, 4617
\cs_gset_eq:cN 1256, 1262, 1281, 2096,
4615, 5686, 8486, 8488, 9313, 9447
\cs_gset_eq:Nc 1256,
1261, 2095, 4616, 5691, 9321, 9455
\cs_gset_eq:NN 15, 1256,
1260, 1261, 1262, 1263, 1273, 1480,
1481, 1482, 1483, 1484, 1485, 1486,
1487, 1491, 1492, 1493, 1494, 1495,
1496, 1497, 1498, 2083, 2085, 2094,
4583, 4614, 6206, 9347, 9481, 15190
\cs_gset_nopar:cn 1387
\cs_gset_nopar:cpx 1230, 1234
\cs_gset_nopar:cpx 1230, 1235
\cs_gset_nopar:cpx 1387
\cs_gset_nopar:Nn 14, 1338
\cs_gset_nopar:Npn 12, 831, 831,
834, 838, 842, 1222, 1234, 3705, 7679
\cs_gset_nopar:Npx 831, 832, 836,
840, 844, 1223, 1235, 3712, 4589,
4594, 4660, 4662, 4664, 4680, 4682,
4684, 4686, 4704, 4706, 4708, 4710
\cs_gset_nopar:Nx 1338
\cs_gset_protected:cn 1387
\cs_gset_protected:cpx 1250, 1252
\cs_gset_protected:cpx 1250, 1253
\cs_gset_protected:cpx 1387
\cs_gset_protected:Nn 14, 1338
\cs_gset_protected:Npn
... 12, 831, 841, 1228, 1252, 7610
\cs_gset_protected:Npx 831, 843, 1229, 1253
\cs_gset_protected:Nx 1338
\cs_gset_protected_nopar:cpx 1387
\cs_gset_protected_nopar:cpx 1244, 1246
\cs_gset_protected_nopar:cpx 1244, 1247
\cs_gset_protected_nopar:cpx 1387
\cs_gset_protected_nopar:Nn 14, 1338

\cs_gset_protected_nopar:Npn
 12, 831, 837, 1226, 1246
\cs_gset_protected_nopar:Npx
 831, 839, 1227, 1247
\cs_gset_protected_nopar:Nx 1338
\cs_gundefine:c 1582
\cs_gundefine:N 1581
\cs_if_eq:ccF 1435
\cs_if_eq:ccT 1434
\cs_if_eq:ccTF 1419, 1433
\cs_if_eq:cNF 1427
\cs_if_eq:cNT 1426
\cs_if_eq:cNTF 1419, 1425, 7845
\cs_if_eq:NcF 1431
\cs_if_eq:Nct 1430
\cs_if_eq:NctF 1419, 1429
\cs_if_eq:NN 1419
\cs_if_eq:NNF 1427, 1431, 1435
\cs_if_eq:NNT 1426, 1430, 1434
\cs_if_eq:NNTF 20, 1419, 1425, 1429, 1433
\cs_if_eq_p:cc 1419, 1432
\cs_if_eq_p:cN 1419, 1424
\cs_if_eq_p:Nc 1419, 1428
\cs_if_eq_p:NN 20, 1419, 1424, 1428, 1432
\cs_if_exist:c 1099
\cs_if_exist:cF 2142, 3504,
 4182, 4419, 4516, 4630, 5448, 5828,
 6351, 6533, 8661, 9305, 9439, 11446
\cs_if_exist:cT
 2141, 3503, 4181, 4418, 4515, 4629,
 5447, 5827, 6350, 6532, 8919, 11445
\cs_if_exist:cTF 1087, 1152, 1154,
 1156, 1158, 2140, 3502, 4180, 4417,
 4514, 4628, 5446, 5826, 6349, 6531,
 6768, 7597, 8367, 8536, 8635, 8956,
 8970, 8976, 9329, 9463, 10527, 11444
\cs_if_exist:N 1087
\cs_if_exist:NF 1206,
 2138, 3500, 4178, 4415, 4512, 4626,
 5444, 5824, 6347, 6529, 11442, 13956
\cs_if_exist:NT 1478, 1489, 2137, 3499,
 4177, 4414, 4511, 4625, 5443, 5823,
 6346, 6528, 7579, 9116, 9134, 11441
\cs_if_exist:NTF
 20, 1087, 1144, 1146, 1148,
 1150, 1438, 2136, 3498, 4176, 4413,
 4510, 4624, 5290, 5442, 5822, 6345,
 6527, 6766, 7573, 8287, 9365, 11440
\cs_if_exist_p:c
 1087, 2143, 3505, 4183, 4420, 4517,
 4631, 5449, 5829, 6352, 6534, 11447
\cs_if_exist_p:N 20,
 1087, 2139, 3501, 4179, 4416, 4513,
 4627, 5445, 5825, 6348, 6530, 11443
\cs_if_exist_use:c 1143, 1157
\cs_if_exist_use:cF 1153, 10029, 10506
\cs_if_exist_use:cT 1155
\cs_if_exist_use:cTF 1143, 1151
\cs_if_exist_use:N 1143, 1149
\cs_if_exist_use:NF 1145
\cs_if_exist_use:NT 1147
\cs_if_exist_use:NTF 184, 1143, 1143
\cs_if_free:c 1127
\cs_if_free:cT 2049
\cs_if_free:cTF 1115, 7876
\cs_if_free:N 1115
\cs_if_free:NF 1183, 1193
\cs_if_free:NTF 21, 1115, 2010, 9718, 9720
\cs_if_free_p:c 1115
\cs_if_free_p:N 21, 1115
\cs_meaning:c 788, 789, 799
\cs_meaning:N 16, 775, 777, 796, 1458
\cs_new:cn 1387
\cs_new:cpn
 1238, 1242, 1566, 2182, 2184, 2189,
 2283, 2284, 2285, 2286, 2288, 2290,
 2292, 2294, 2296, 2298, 2300, 2305,
 2306, 2307, 2308, 2309, 2310, 2311,
 2312, 2313, 2314, 3570, 3572, 3574,
 3576, 3578, 3580, 3582, 4267, 4269,
 4271, 4273, 4275, 4277, 4279, 9904,
 10378, 10455, 11061, 11121, 11139,
 11166, 11205, 11245, 11250, 11255,
 11260, 11627, 11736, 12280, 13049
\cs_new:cpx 1238, 1243, 1570
\cs_new:cx 1387
\cs_new:Nn 6, 12, 1338
\cs_new:Npn 1, 10, 1214, 1224,
 1242, 1313, 1315, 1462, 1512, 1520,
 1525, 1531, 1536, 1542, 1545, 1554,
 1555, 1558, 1614, 1615, 1616, 1617,
 1618, 1619, 1620, 1622, 1624, 1636,
 1642, 1648, 1659, 1661, 1668, 1669,
 1671, 1673, 1675, 1677, 1684, 1686,
 1691, 1696, 1702, 1708, 1714, 1720,
 1726, 1733, 1740, 1747, 1754, 1789,
 1790, 1795, 1797, 1802, 1812, 1814,
 1816, 1817, 1819, 1821, 1827, 1833,

1835, 1842, 1849, 1851, 1853, 1854,
1855, 1857, 1862, 1936, 1952, 1957,
1966, 1979, 1994, 2052, 2152, 2162,
2164, 2166, 2168, 2172, 2191, 2209,
2215, 2221, 2225, 2226, 2232, 2234,
2238, 2240, 2244, 2252, 2257, 2265,
2271, 2278, 2280, 2282, 2335, 2341,
2350, 2355, 2480, 2486, 2494, 2501,
2512, 2518, 2584, 2585, 2587, 2599,
2669, 2675, 2681, 2687, 2818, 2873,
2891, 2915, 2933, 2951, 2969, 2980,
3001, 3020, 3027, 3028, 3036, 3045,
3054, 3070, 3151, 3238, 3241, 3250,
3259, 3378, 3380, 3386, 3404, 3412,
3420, 3433, 3435, 3442, 3536, 3543,
3559, 3565, 3592, 3597, 3599, 3622,
3630, 3638, 3644, 3650, 3658, 3666,
3672, 3678, 3692, 3726, 3727, 3741,
3747, 3779, 3811, 3813, 3819, 3831,
3839, 3872, 3874, 3876, 3878, 3883,
3888, 3893, 3913, 3914, 3919, 3924,
3948, 3956, 3958, 3967, 3969, 3978,
3980, 3990, 3999, 4001, 4003, 4019,
4028, 4062, 4064, 4105, 4120, 4205,
4210, 4228, 4236, 4238, 4255, 4262,
4281, 4286, 4288, 4351, 4353, 4355,
4362, 4460, 4463, 4468, 4471, 4539,
4755, 4804, 4815, 4863, 4916, 4917,
4918, 4919, 4922, 4927, 4935, 4943,
4982, 4984, 4990, 4995, 5000, 5003,
5010, 5017, 5019, 5029, 5041, 5049,
5055, 5061, 5065, 5072, 5083, 5092,
5094, 5101, 5107, 5109, 5111, 5125,
5127, 5129, 5137, 5142, 5144, 5156,
5158, 5167, 5173, 5175, 5181, 5227,
5236, 5281, 5349, 5351, 5367, 5376,
5426, 5432, 5466, 5565, 5619, 5660,
5666, 5714, 5722, 5776, 5830, 5835,
5836, 5843, 5923, 6016, 6018, 6048,
6057, 6064, 6070, 6077, 6125, 6143,
6236, 6373, 6379, 6413, 6419, 7758,
7759, 7760, 7761, 7762, 7763, 7849,
7874, 8004, 8240, 8243, 8252, 8257,
8262, 8267, 8307, 8308, 8312, 8317,
8445, 8577, 8592, 8697, 8709, 8954,
8963, 8980, 9162, 9667, 9674, 9740,
9741, 9742, 9743, 9744, 9745, 9746,
9766, 9767, 9768, 9774, 9780, 9789,
9791, 9802, 9803, 9804, 9814, 9824,
9834, 9844, 9854, 9857, 9867, 9868,
9873, 9875, 9880, 9882, 9884, 9886,
9898, 9900, 9902, 9928, 9930, 9932,
9933, 9934, 9936, 9938, 9940, 9942,
9944, 9952, 9953, 9969, 9978, 9985,
9987, 9994, 10013, 10132, 10133,
10134, 10135, 10136, 10137, 10138,
10145, 10186, 10188, 10197, 10198,
10207, 10221, 10237, 10248, 10257,
10264, 10275, 10283, 10294, 10299,
10319, 10321, 10332, 10337, 10350,
10358, 10359, 10369, 10374, 10396,
10423, 10436, 10439, 10449, 10462,
10482, 10504, 10517, 10525, 10541,
10549, 10564, 10575, 10586, 10596,
10601, 10610, 10627, 10640, 10645,
10651, 10653, 10660, 10690, 10718,
10723, 10733, 10743, 10753, 10769,
10814, 10830, 10841, 10859, 10870,
10886, 10893, 10911, 10916, 10925,
10930, 10940, 10942, 10949, 10978,
10992, 11007, 11012, 11017, 11073,
11084, 11103, 11106, 11151, 11176,
11220, 11232, 11265, 11270, 11275,
11286, 11301, 11312, 11324, 11342,
11356, 11375, 11389, 11393, 11411,
11413, 11453, 11472, 11477, 11504,
11505, 11513, 11525, 11531, 11537,
11545, 11553, 11559, 11565, 11573,
11581, 11589, 11597, 11621, 11623,
11625, 11638, 11647, 11648, 11673,
11678, 11685, 11686, 11694, 11705,
11712, 11719, 11721, 11729, 11759,
11761, 11771, 11791, 11800, 11814,
11822, 11830, 11837, 11844, 11852,
11862, 11876, 11887, 11888, 11894,
11911, 11918, 11920, 11927, 11932,
11949, 11950, 11951, 11969, 11975,
11985, 11997, 12004, 12026, 12064,
12073, 12092, 12094, 12096, 12105,
12116, 12143, 12156, 12169, 12177,
12194, 12211, 12218, 12226, 12236,
12237, 12246, 12247, 12256, 12266,
12288, 12301, 12302, 12307, 12308,
12321, 12328, 12336, 12337, 12338,
12341, 12349, 12355, 12357, 12359,
12381, 12387, 12397, 12407, 12417,
12430, 12441, 12446, 12447, 12461,
12471, 12483, 12488, 12495, 12502,
12512, 12526, 12527, 12538, 12547,
12558, 12566, 12567, 12573, 12581,

12590, 12599, 12601, 12621, 12635,
12649, 12669, 12682, 12683, 12688,
12701, 12706, 12714, 12719, 12729,
12741, 12770, 12771, 12772, 12774,
12776, 12778, 12792, 12798, 12807,
12826, 12832, 12842, 12861, 12869,
12908, 12910, 12919, 12921, 12935,
12937, 12946, 12948, 12964, 12980,
12996, 13012, 13028, 13044, 13074,
13093, 13121, 13137, 13147, 13158,
13179, 13194, 13199, 13204, 13206,
13220, 13222, 13237, 13245, 13269,
13284, 13299, 13314, 13329, 13344,
13359, 13374, 13384, 13402, 13404,
13408, 13415, 13425, 13427, 13436,
13448, 13450, 13466, 13476, 13492,
13530, 13544, 13575, 13580, 13581,
13582, 13583, 13596, 13623, 13636,
13638, 13646, 13672, 13697, 13706,
13707, 13714, 13724, 13744, 13751,
13756, 13761, 13777, 13782, 13784,
13793, 13795, 13797, 13799, 13888,
13895, 14006, 14018, 14469, 14477,
14492, 14499, 14507, 14509, 14523,
14528, 14545, 14552, 14567, 14573,
14574, 14594, 14595, 14598, 14866,
14872, 14879, 14886, 14894, 14910,
14918, 14927, 14935, 14982, 15009,
15029, 15031, 15038, 15041, 15061,
15074, 15080, 15085, 15097, 15098,
15099, 15111, 15119, 15127, 15134,
15135, 15143, 15148, 15163, 15177
\cs_new:Npx 1214, 1225, 1243, 1562, 6134,
6144, 8228, 9539, 13739, 13742, 13811
\cs_new:Nx 1338
\cs_new_eq:cc 989, 1256, 1271, 1578
\cs_new_eq:cN 1256, 1269, 1576, 6203, 11118
\cs_new_eq:Nc 1256, 1270, 1577
\cs_new_eq:NN 15,
1256, 1264, 1269, 1270, 1271, 1466,
1467, 1468, 1469, 1470, 1471, 1472,
1473, 1474, 1475, 1476, 1477, 1543,
1544, 1553, 1557, 1558, 1559, 1560,
1561, 1562, 1563, 1564, 1565, 1566,
1567, 1568, 1569, 1570, 1571, 1572,
1575, 1576, 1577, 1578, 1581, 1582,
1585, 1588, 1589, 1590, 1601, 1602,
1603, 1604, 1605, 1630, 2076, 2090,
2091, 2092, 2093, 2094, 2095, 2096,
2097, 2136, 2137, 2138, 2139, 2140,
2141, 2142, 2143, 2457, 2458, 2459,
2460, 2461, 2462, 2463, 2464, 2465,
2580, 2691, 2692, 2693, 3063, 3064,
3065, 3269, 3270, 3271, 3272, 3273,
3293, 3294, 3297, 3298, 3299, 3300,
3303, 3306, 3307, 3308, 3309, 3310,
3311, 3312, 3313, 3315, 3317, 3318,
3319, 3320, 3321, 3322, 3323, 3324,
3325, 3326, 3327, 3328, 3329, 3330,
3331, 3333, 3335, 3336, 3337, 3338,
3339, 3340, 3341, 3344, 3345, 3346,
3347, 3348, 3349, 3350, 3351, 3352,
3353, 3354, 3355, 3356, 3357, 3358,
3359, 3369, 3370, 3371, 3372, 3373,
3475, 3479, 3498, 3499, 3500, 3501,
3502, 3503, 3504, 3505, 3535, 3605,
4065, 4066, 4093, 4094, 4095, 4136,
4138, 4139, 4140, 4149, 4150, 4151,
4176, 4177, 4178, 4179, 4180, 4181,
4182, 4183, 4294, 4370, 4372, 4382,
4383, 4413, 4414, 4415, 4416, 4417,
4418, 4419, 4420, 4465, 4467, 4470,
4475, 4479, 4480, 4510, 4511, 4512,
4513, 4514, 4515, 4516, 4517, 4541,
4543, 4555, 4556, 4557, 4610, 4611,
4612, 4613, 4614, 4615, 4616, 4617,
4624, 4625, 4626, 4627, 4628, 4629,
4630, 4631, 4934, 4981, 5320, 5321,
5322, 5323, 5324, 5325, 5326, 5327,
5330, 5331, 5332, 5333, 5334, 5335,
5336, 5337, 5340, 5341, 5342, 5343,
5344, 5347, 5348, 5353, 5354, 5355,
5356, 5357, 5358, 5383, 5384, 5385,
5386, 5387, 5388, 5389, 5390, 5391,
5392, 5393, 5394, 5395, 5396, 5397,
5398, 5399, 5400, 5401, 5442, 5443,
5444, 5445, 5446, 5447, 5448, 5449,
5724, 5725, 5726, 5727, 5728, 5729,
5730, 5731, 5732, 5733, 5734, 5735,
5736, 5737, 5738, 5739, 5740, 5741,
5742, 5743, 5744, 5745, 5746, 5747,
5748, 5749, 5767, 5768, 5771, 5772,
5774, 5775, 5786, 5789, 5790, 5791,
5792, 5793, 5794, 5795, 5796, 5797,
5798, 5799, 5800, 5801, 5802, 5803,
5804, 5805, 5806, 5822, 5823, 5824,
5825, 5826, 5827, 5828, 5829, 5957,
5958, 5959, 5960, 5961, 5962, 5963,
5964, 5965, 5966, 5967, 5968, 5969,
5970, 5971, 5972, 6166, 6167, 6170,

6171, 6174, 6175, 6187, 6188, 6189,
6190, 6191, 6202, 6214, 6215, 6216,
6217, 6218, 6219, 6220, 6221, 6345,
6346, 6347, 6348, 6349, 6350, 6351,
6352, 6449, 6450, 6463, 6479, 6480,
6481, 6482, 6483, 6484, 6485, 6486,
6527, 6528, 6529, 6530, 6531, 6532,
6533, 6534, 6535, 6536, 6537, 6550,
6551, 6562, 6563, 6564, 6590, 6596,
6656, 6657, 6658, 6659, 6660, 6661,
6662, 6663, 6671, 6672, 6709, 6710,
6711, 6712, 6713, 6714, 6715, 6716,
6717, 6723, 6920, 6921, 6922, 6923,
6924, 6925, 7559, 8323, 8326, 8327,
8328, 8329, 8330, 8944, 9040, 9041,
9042, 9044, 9218, 9252, 9362, 9391,
9392, 9393, 9400, 9410, 9488, 9503,
9711, 9712, 9714, 9729, 9730, 9863,
10023, 10024, 10025, 10026, 10220,
10273, 10274, 10448, 10516, 10941,
11440, 11441, 11442, 11443, 11444,
11445, 11446, 11447, 13790, 13792,
13827, 13838, 13839, 14002, 14003,
14123, 14124, 14125, 14126, 14169
\cs_new_nopar:cn 1387
\cs_new_nopar:cpx
 1230, 1236, 1565, 2200, 2201,
 2202, 2203, 2204, 2205, 2206, 2207,
 11021, 11033, 11051, 12018, 12128
\cs_new_nopar:cpx
 1230, 1237, 1569, 2040, 3180, 11731
\cs_new_nopar:cx 1387
\cs_new_nopar:Nn 13, 1338
\cs_new_nopar:Npn
 11, 1214, 1222, 1236, 1323, 1424,
 1425, 1426, 1427, 1428, 1429, 1430,
 1431, 1432, 1433, 1434, 1435, 1500,
 1557, 1762, 1763, 1764, 1765, 1766,
 1767, 1768, 1769, 1770, 1777, 1778,
 1779, 1780, 1781, 1844, 1845, 1846,
 1847, 2323, 2325, 3067, 3068, 3069,
 3120, 3129, 3137, 3276, 3277, 3279,
 3280, 3282, 3283, 3285, 3286, 3288,
 3289, 3898, 3899, 3900, 3901, 3902,
 3903, 3904, 3905, 3906, 3907, 3908,
 3909, 3910, 3911, 3912, 4098, 4805,
 4810, 4941, 4977, 4979, 5157, 5166,
 5531, 5656, 5658, 6121, 6123, 6438,
 6440, 7678, 8360, 8361, 8934, 8936,
 8945, 9502, 9665, 10143, 10395,
 11645, 12339, 12340, 13586, 13641,
 13709, 13746, 14827, 14829, 15170
\cs_new_nopar:Npx
 1214, 1223, 1237, 1561, 1895
\cs_new_nopar:Nx 1338
\cs_new_protected:cn 1387
\cs_new_protected:cpx
 1250, 1254, 1568, 7773,
 7774, 8018, 8369, 8753, 8755, 8757,
 8759, 8763, 8765, 8767, 8769, 8771,
 8773, 8775, 8777, 8779, 8781, 8783,
 8785, 8787, 8789, 8791, 8793, 8795,
 8797, 8799, 8801, 8803, 8805, 8807,
 8809, 8811, 8813, 8815, 8817, 8821,
 8823, 8825, 8827, 8829, 8831, 8833,
 8835, 8837, 8839, 8841, 8843, 8845
\cs_new_protected:cpx 1250,
 1255, 1572, 7783, 7785, 7787, 7789,
 7791, 7800, 7802, 7804, 8027, 8029,
 8031, 8033, 8035, 8044, 8046, 8048
\cs_new_protected:cx 1387
\cs_new_protected:Nn 13, 1338
\cs_new_protected:Npn
 11, 1214, 1228,
 1254, 1256, 1264, 1272, 1274, 1325,
 1346, 1351, 1436, 1453, 1560, 1631,
 1807, 1868, 1886, 1899, 1901, 1907,
 1916, 2006, 2032, 2045, 2076, 2078,
 2080, 2082, 2084, 2098, 2100, 2116,
 2125, 2364, 2454, 2455, 2473, 2571,
 2597, 2601, 2603, 2605, 2607, 2609,
 2611, 2613, 2615, 2617, 2619, 2621,
 2623, 2625, 2627, 2629, 2631, 2633,
 2635, 2637, 2639, 2641, 2643, 2645,
 2647, 2649, 2651, 2653, 2655, 2657,
 2659, 2661, 2663, 2665, 2667, 2671,
 2673, 2677, 2679, 2683, 2685, 2689,
 2691, 3075, 3081, 3098, 3100, 3102,
 3116, 3118, 3445, 3452, 3482, 3483,
 3486, 3488, 3492, 3495, 3506, 3508,
 3518, 3520, 3530, 3708, 3720, 4067,
 4153, 4160, 4166, 4167, 4170, 4172,
 4184, 4186, 4189, 4192, 4195, 4197,
 4200, 4202, 4374, 4390, 4397, 4403,
 4404, 4407, 4409, 4421, 4423, 4426,
 4429, 4432, 4434, 4437, 4439, 4477,
 4486, 4493, 4499, 4501, 4504, 4506,
 4518, 4520, 4523, 4526, 4529, 4531,
 4534, 4536, 4545, 4566, 4580, 4586,
 4591, 4598, 4600, 4604, 4606, 4618,
 4620, 4653, 4655, 4657, 4659, 4661,

- 10045, 10075, 10077, 10079, 10101,
10103, 10105, 10109, 10111, 10113,
13852, 13853, 13854, 13855, 13897,
13898, 13917, 13918, 13919, 13920,
13921, 13922, 13933, 13934, 13960,
13961, 13962, 13963, 13965, 14071,
14716, 14831, 14833, 14835, 14970,
14971, 14973, 14989, 14991, 14999,
15001, 15193, 15204, 15206, 15208
- \cs_new_protected_nopar:Npx
..... 1214, 1227, 1249, 1563,
1889, 1893, 2036, 9647, 13899, 13905
- \cs_new_protected_nopar:Nx 1338
- \cs_set:cn 1387
- \cs_set:cpx 1238, 1239,
2365, 2369, 2373, 2377, 2383, 2392,
2401, 2410, 2421, 2423, 2425, 2427,
2429, 2431, 2433, 2435, 2439, 8679
- \cs_set:cx 1387
- \cs_set:Nn 13, 1338
- \cs_set:Npn 3, 11, 817, 819, 846,
852, 853, 854, 855, 856, 857, 858,
859, 860, 861, 862, 863, 864, 865,
866, 867, 868, 869, 870, 871, 872,
873, 874, 875, 876, 877, 878, 879,
880, 1033, 1038, 1043, 1048, 1061,
1062, 1070, 1078, 1080, 1083, 1085,
1143, 1145, 1147, 1149, 1151, 1153,
1155, 1157, 1214, 1230, 1238, 1338,
1387, 1593, 1594, 1595, 1596, 2450,
2451, 3172, 3178, 3375, 3388, 3396,
4212, 4220, 4295, 4303, 4311, 4317,
4323, 4331, 4339, 4345, 4909, 5027,
5996, 6034, 10050, 10058, 10067,
10084, 10092, 14843, 15175, 15185
- \cs_set:Npx 817, 821, 1239, 4788, 15186
- \cs_set:Nx 1338
- \cs_set_eq:cc 987, 1256, 1259, 2093, 4613
- \cs_set_eq:cN 1256, 1257, 2092, 4611, 10012
- \cs_set_eq:Nc 1256, 1258, 2091, 4612
- \cs_set_eq>NN 15,
1256, 1256, 1257, 1258, 1259, 1260,
1267, 1889, 1904, 2036, 2079, 2081,
2090, 2752, 3079, 3083, 3104, 3106,
3165, 3183, 4610, 5604, 5605, 5617,
6204, 8867, 8869, 9249, 9407, 9555,
9556, 9557, 14977, 14978, 14980, 15189
- \cs_set_eq:NwN 1598, 1599
- \cs_set_nopar:cn 1387
- \cs_set_nopar:cpx 1230, 1232
- \cs_set_nopar:cpx 1230, 1233
- \cs_set_nopar:cx 1387
- \cs_set_nopar:Nn 13, 1338
- \cs_set_nopar:Npn 11, 817,
817, 819, 820, 821, 823, 824, 825,
828, 845, 881, 883, 1055, 1179, 1232
- \cs_set_nopar:Npx
..... 817, 818, 822, 826, 830, 849,
1233, 1633, 1809, 3085, 3090, 3107,
3108, 4654, 4656, 4658, 4672, 4674,
4676, 4678, 4696, 4698, 4700, 4702,
9086, 9549, 9550, 9551, 9552, 9553
- \cs_set_nopar:Nx 1338
- \cs_set_protected:cn 1387
- \cs_set_protected:cpx 1250, 1250, 8368
- \cs_set_protected:cpx
.. 1250, 1251, 8374, 8376, 8378, 8380
- \cs_set_protected:cx 1387
- \cs_set_protected:Nn 13, 1338
- \cs_set_protected:Npn
..... 11, 817, 827, 847, 893, 906,
911, 923, 938, 955, 971, 976, 981,
990, 1002, 1016, 1163, 1175, 1177,
1181, 1191, 1204, 1216, 1250, 1283,
1304, 4452, 5519, 6230, 6882, 7770,
8014, 8016, 8342, 10376, 11019,
11031, 11071, 11119, 11174, 13931,
14044, 14053, 14081, 14095, 14109
- \cs_set_protected:Npx 817, 829, 1251
- \cs_set_protected:Nx 1338
- \cs_set_protected_nopar:cn 1387
- \cs_set_protected_nopar:cpx
..... 1244, 1244, 8372
- \cs_set_protected_nopar:cpx 1244, 1245
- \cs_set_protected_nopar:cx 1387
- \cs_set_protected_nopar:Nn 14, 1338
- \cs_set_protected_nopar:Npn 12, 265,
817, 823, 827, 829, 833, 835, 837,
839, 841, 843, 885, 887, 889, 891,
898, 900, 902, 904, 986, 988, 1159,
1161, 1202, 1212, 1244, 6859, 7575,
7580, 7729, 9498, 9500, 14086, 14096
- \cs_set_protected_nopar:Npx
..... 251, 817, 825, 1245, 7891
- \cs_set_protected_nopar:Nx 1338
- \cs_show:c 1447, 1464, 8981
- \cs_show:N 16, 1447, 1453, 1465, 5291

\cs_to_str:N	4297, 4314
.. 4, 17, 1055, 1055, 1074, 2339, 9503	
\cs_undefine:c	76, 4245
.. 1272, 1274, 1582	
\cs_undefine:N	76, 4245
.. 15, 1272, 1272, 1581, 8052, 8053, 8054	
\csname .. 14, 33, 36, 63, 69, 73, 122, 135,	4160
138, 174, 177, 183, 191, 196, 198,	4165
208, 211, 221, 288, 290, 295, 297, 412	4295, 4317, 4321
\currentgrouplevel	664
\currentgroupstype	665
\currentifbranch	661
\currentiflevel	660
\currentiftype	662
D	
dd	177
nd	177
\dagger	4110, 4116
\day	620
\ddagger	4111, 4117
\deadcycles	554
\def	55, 57, 140, 152,
159, 164, 210, 220, 247, 280, 308, 319	4284, 4351,
.default:n	149
.default:V	149
\defaulthyphenchar	604
\defaultskewchar	605
\delcode	635
\delimiter	429
\delimiterfactor	478
\delimitershortfall	477
\deprecated	2454, 2455, 8333,
8334, 8335, 8336, 8337, 8338, 8339	4195, 4197, 4199
\detokenize	33, 36, 122, 135, 138,
174, 177, 183, 192, 197, 199, 205,	4184, 4186, 4188, 4561, 4565
208, 211, 221, 288, 290, 295, 297, 652	4556, 4557
\dim_abs:n	75, 4205, 4205, 14328
\dim_add:cn	4195
\dim_add:Nn	75, 4195, 4195, 4197, 4198
\dim_case:nmn	77, 4281, 4281, 4555
\dim_compare:n	4245
\dim_compare:nF	4305, 4320
\dim_compare:nNn	4240
\dim_compare:nNnF	4333, 4348
\dim_compare:nNt	4325, 4342, 4567, 7141, 7146
\dim_compare:nNnTF	76, 4240, 4290, 7047, 7050, 7053,
7062, 7065, 7068, 7077, 7084, 7153,	4170, 4172, 4175
7266, 7278, 14429, 14436, 14453, 14459	4182, 4181
\dim_const:cn	4160
\dim_const:Nn	74, 4160, 4160, 4165
\dim_do_until:nn	78, 4295, 4317, 4321
\dim_do_until:nNnn	77, 4323, 4345, 4349
\dim_do_while:nn	78, 4295, 4311, 4315
\dim_do_while:nNnn	77, 4323, 4339, 4343
\dim_eval:n	78, 4284, 4351,
4351, 6846, 6894, 6963, 6974, 6991,	4195, 4197, 4199
6993, 6999, 7010, 7024, 7249, 7250,	41426, 14450, 14458, 14463, 14731,
14732, 14739, 14740, 14815, 14822	14731, 14732, 14739, 14740, 14815,
\dim_eval:w	4556
\dim_eval_end:	4556
\dim_gadd:cn	4195
\dim_gadd:Nn	75, 4195, 4197, 4199
.dim_gset:c	149
\dim_gset:cn	4184
.dim_gset:N	149
\dim_gset:Nn	75, 4163, 4184, 4186, 4188, 4561, 4565
\dim_gset_eq:cc	4189
\dim_gset_eq:cN	4189
\dim_gset_eq:Nc	4189
\dim_gset_eq:NN	75, 4189, 4192, 4193, 4194
\dim_gset_max:cn	4558
\dim_gset_max:Nn	4558, 4560, 4569
\dim_gset_min:cn	4558
\dim_gset_min:Nn	4558, 4564, 4571
\dim_gsub:cn	4195
\dim_gsub:Nn	75, 4195, 4202, 4204
\dim_gzero:c	4166
\dim_gzero:N	74, 4166, 4167, 4169, 4173
\dim_gzero_new:c	4170
\dim_gzero_new:N	74, 4170, 4172, 4175
\dim_if_exist:cF	4182
\dim_if_exist:cT	4181
\dim_if_exist:cTF	4176, 4180
\dim_if_exist:NF	4178
\dim_if_exist:NT	4177
\dim_if_exist:NTF	74, 4171, 4173, 4176, 4176
\dim_if_exist_p:c	4176, 4183
\dim_if_exist_p:N	74, 4176, 4179
\dim_max:nn	75, 4205, 4212, 14710, 14714
\dim_min:nn	75, 4205, 4220, 14708, 14712, 14725
\dim_new:c	4152

```

\dim_new:N    74, 4152, 4153, 4159, 4162,
               4171, 4173, 4377, 4378, 4385, 4386,
               4387, 4388, 6734, 6756, 6757, 6760,
               6761, 6762, 6763, 7336, 7338, 7339,
               14182, 14183, 14184, 14185, 14186,
               14187, 14188, 14189, 14604, 14605,
               14606, 14607, 14608, 14746, 14747
\dim_ratio:nn ..... 76, 4236, 4236
.dim_set:c ..... 149
\dim_set:cn ..... 4184
.dim_set:N ..... 149
\dim_set:Nn ..... 75, 4184, 4184,
               4186, 4187, 4379, 4559, 4563, 6830,
               6876, 7049, 7054, 7064, 7069, 7079,
               7086, 7099, 7124, 7144, 7203, 7204,
               7206, 7208, 7226, 7227, 7337, 7440,
               7441, 7492, 7493, 7494, 7496, 14205,
               14206, 14207, 14239, 14250, 14310,
               14311, 14312, 14328, 14329, 14331,
               14340, 14341, 14342, 14360, 14361,
               14362, 14379, 14380, 14381, 14383,
               14385, 14387, 14647, 14679, 14687,
               14698, 14699, 14700, 14701, 14707,
               14709, 14711, 14713, 14718, 14724,
               14779, 14781, 14783, 14791, 14793
\dim_set_eq:cc ..... 4189
\dim_set_eq:cN ..... 4189
\dim_set_eq:Nc ..... 4189
\dim_set_eq>NN ..... 75, 4189, 4189,
               4190, 4191, 6832, 6833, 6878, 6879
\dim_set_max:cn ..... 4558
\dim_set_max:Nn ..... 4558, 4558, 4568
\dim_set_min:cn ..... 4558
\dim_set_min:Nn ..... 4558, 4562, 4570
\dim_show:c ..... 4372
\dim_show:N ..... 79, 4372, 4372, 4373
\dim_show:n ..... 79, 4374, 4374
\dim_sub:cn ..... 4195
\dim_sub:Nn ..... 75, 4195, 4200, 4202, 4203
\dim_to_fp:n ..... 177, 7092, 7094,
               7104, 7105, 7106, 7107, 7128, 7129,
               7130, 7131, 11053, 13756, 13756,
               14243, 14244, 14254, 14255, 14315,
               14318, 14319, 14346, 14347, 14365,
               14683, 14684, 14691, 14692, 14751,
               14754, 14792, 14794, 14860, 14862
\dim_until_do:nn ... 78, 4295, 4303, 4308
\dim_until_do:nNnn .. 77, 4323, 4331, 4336
\dim_use:c ..... 4370
\dim_use:N ..... 79, 4208, 4214,
               4215, 4216, 4222, 4223, 4224, 4247,
               4352, 4358, 4370, 4370, 4371, 4375,
               6987, 6989, 6993, 7004, 7017, 7234,
               7547, 7548, 7549, 11054, 14644,
               14646, 14649, 14651, 14657, 14663,
               14672, 14673, 14674, 14800, 14807
\dim_while_do:nn ... 78, 4295, 4295, 4300
\dim_while_do:nNnn ... 78, 4323, 4323, 4328
\dim_zero:c ..... 4166
\dim_zero:N ..... 74, 4166,
               4166, 4167, 4168, 4171, 7040, 7041,
               14208, 14313, 14343, 14363, 14382
\dim_zero_new:c ..... 4170
\dim_zero_new:N ..... 74, 4170, 4170, 4174
\dimen ..... 626
\dimendef ..... 325
\dimexpr ..... 679
\directlua ..... 16, 728
\discretionary ..... 489
\displayindent ..... 454
\displaylimits ..... 464
\displaystyle ..... 442
\displaywidowpenalties ..... 692
\displaywidowpenalty ..... 453
\displaywidth ..... 455
\divide ..... 332
\doublehyphendemerits ..... 522
\dp ..... 633
\dump ..... 616

```

E

```

sec ..... 176
\edef ..... 34, 110,
               124, 171, 173, 188, 208, 285, 292, 320
deg ..... 176
\else ..... 15, 64, 179, 194, 214, 373
\else: ..... 23, 754,
               757, 793, 959, 1091, 1094, 1103,
               1109, 1119, 1122, 1131, 1137, 1278,
               1299, 1308, 1319, 1422, 1505, 1510,
               1516, 1594, 1654, 1890, 1940, 1941,
               1942, 1998, 2001, 2108, 2148, 2177,
               2196, 2316, 2318, 2320, 2322, 2490,
               2506, 2529, 2537, 2550, 2559, 2734,
               2739, 2744, 2749, 2756, 2762, 2767,
               2772, 2777, 2782, 2787, 2792, 2797,
               2802, 2822, 2830, 2836, 2839, 2878,
               2881, 2900, 2903, 2920, 2923, 2938,
               2941, 2956, 2959, 3032, 3041, 3049,
```

3058, 3125, 3133, 3155, 3387, 3408,	\endL	700
3424, 3427, 3544, 3555, 3588, 3610,	\endlinechar	121, 134, 244, 427
3618, 3869, 4211, 4232, 4243, 4250,	\endR	702
4448, 4843, 4855, 4868, 4878, 4894,	\eqno	447
5149, 5193, 5216, 5232, 5240, 5250,	\errhelp	91, 393
5272, 5543, 5552, 5893, 5908, 5930,	\errmessage	105, 387
5946, 6357, 6383, 6566, 6568, 6578,	\ERROR	2450, 2451
9369, 9372, 9678, 9784, 9793, 9794,	\errorcontextlines	394
9795, 9808, 9818, 9828, 9892, 9949,	\errorstopmode	408
9959, 9964, 9974, 10019, 10211,	\escapechar	426
10239, 10240, 10289, 10307, 10342,	\etex_beginL:D	699
10346, 10382, 10402, 10406, 10410,	\etex_beginR:D	701
10472, 10490, 10498, 10554, 10558,	\etex_botmarks:D	648
10570, 10581, 10591, 10622, 10635,	\etex_clubpenalties:D	690
10670, 10680, 10699, 10712, 10728,	\etex_currentgrouplevel:D	664
10736, 10738, 10748, 10759, 10775,	\etex_currentgroupype:D	665
10789, 10795, 10800, 10807, 10821,	\etex_currentifbranch:D	661
10825, 10836, 10853, 10865, 10878,	\etex_currentiflevel:D	660
10906, 10957, 10961, 10967, 10985,	\etex_currentiftype:D	662
11088, 11091, 11111, 11129, 11146,	\etex_detokenize:D	
11185, 11210, 11226, 11238, 11280,	652, 934, 998, 1876, 4981, 4982	
11291, 11298, 11336, 11350, 11366,	\etex_dimexpr:D	679, 4150
11382, 11399, 11403, 11457, 11468,	\etex_displaywidowpenalties:D	692
11489, 11492, 11495, 11498, 11509,	\etex_endL:D	700
11518, 11521, 11603, 11606, 11613,	\etex_endR:D	702
11631, 11645, 11662, 11742, 11745,	\etex_eTeXrevision:D	644
11753, 11765, 11776, 11782, 11795,	\etex_eTeXversion:D	643
11808, 11848, 11882, 11902, 11939,	\etex_everyeof:D	704, 4738
11957, 11960, 11965, 11979, 12014,	\etex_firstmarks:D	647
12032, 12035, 12038, 12041, 12100,	\etex_fontchardp:D	672
12173, 12241, 12242, 12251, 12294,	\etex_fontcharht:D	671
12466, 12475, 12542, 12630, 12641,	\etex_fontcharic:D	674
12657, 12665, 12723, 12802, 12813,	\etex_fontcharwd:D	673
12818, 12852, 12865, 12881, 12885,	\etex_glueexpr:D	680, 4422, 4433, 4438,
12888, 13059, 13066, 13088, 13111,	4457, 4464, 4469, 4472, 4478, 13759	
13126, 13130, 13152, 13183, 13186,	\etex_glueshrink:D	683, 15046
13211, 13214, 13242, 13250, 13255,	\etex_glueshrinkorder:D	685
13261, 13264, 13274, 13277, 13295,	\etex_gluestretch:D	682, 15045
13310, 13325, 13340, 13355, 13370,	\etex_gluestretchorder:D	684
13379, 13393, 13396, 13485, 13486,	\etex_gluetomu:D	686
13496, 13539, 13628, 13721, 13728,	\etex_ifcsname:D	641, 769
13732, 13765, 13770, 13891, 13896	\etex_ifdefined:D	640, 768, 812
\emergencystretch	\etex_iffontchar:D	670
\end	\etex_interactionmode:D	
\EndCatcodeRegime	668, 6617, 6620, 6621	
\endcsname 14, 33, 36, 63, 69, 73, 122, 135,	\etex_interlinepenalties:D	689
138, 174, 177, 183, 192, 197, 199,	\etex_lastlinefit:D	688
208, 211, 221, 288, 290, 295, 297, 413	\etex_lastnodetype:D	669
\endgroup	\etex_marks:D	645
\endinput	\etex_middle:D	693

\etex_muexpr:D
 ... 681, 4519, 4530, 4535, 4540, 4546
\etex_mutoglue:D 687
\etex_numexpr:D 678, 3370
\etex_pagediscards:D 696
\etex_parshapedimen:D 677
\etex_parshapeindent:D 675
\etex_parshapeheight:D 676
\etex_predisplaydirection:D 703
\etex_protected:D
 ... 705, 819, 821, 823, 824,
 825, 826, 828, 830, 838, 840, 842, 844
\etex_readline:D 655, 9386
\etex_savinghyphcodes:D 694
\etex_savingvdiscards:D 695
\etex_scantokens:D 653, 4749
\etex_showgroups:D 666
\etex_showifs:D 667
\etex_showtokens:D
 ... 654, 4068, 4375, 4478, 4546, 8304
\etex_splitbotmarks:D 650
\etex_splitlegends:D 697
\etex_splitfirstmarks:D 649
\etex_TeXXeTstate:D 698
\etex_topmarks:D 646
\etex_tracingassigns:D 656
\etex_tracinggroups:D 663
\etex_tracingifs:D 659
\etex_tracingnesting:D 658
\etex_tracingscantokens:D 657
\etex_unexpanded:D
 . 651, 774, 1853, 1856, 1859, 1864,
 5113, 5139, 5160, 15063, 15113, 15121
\etex_unless:D 642, 759
\etex_widowpenalties:D 691
\eTeXrevision 644
\eTeXversion 643
\everycr 355
\everydisplay 456
\everyeof 704
\everyhbox 595
\everyjob 32, 624
\everymath 480
\everypar 543
\everyvbox 596
\exhyphenpenalty 519
\exp_after:wN 31, 772, 772, 785, 787, 792,
 794, 882, 884, 928, 941, 958, 960,
 1007, 1012, 1019, 1059, 1063, 1072,
 1073, 1102, 1104, 1107, 1130, 1132,
 1135, 1277, 1279, 1287, 1307, 1309,
 1343, 1392, 1458, 1549, 1614, 1621,
 1623, 1626, 1627, 1634, 1638, 1639,
 1644, 1645, 1650, 1655, 1657, 1660,
 1668, 1670, 1672, 1674, 1676, 1679,
 1680, 1681, 1685, 1688, 1693, 1698,
 1699, 1700, 1704, 1705, 1706, 1710,
 1711, 1712, 1716, 1717, 1718, 1722,
 1723, 1724, 1728, 1729, 1730, 1731,
 1735, 1736, 1737, 1738, 1742, 1743,
 1744, 1749, 1750, 1751, 1752, 1756,
 1757, 1758, 1759, 1792, 1793, 1796,
 1799, 1800, 1804, 1805, 1813, 1815,
 1816, 1818, 1820, 1823, 1824, 1829,
 1830, 1834, 1837, 1838, 1839, 1843,
 1850, 1852, 1853, 1854, 1856, 1859,
 1864, 1872, 1873, 1874, 1875, 1888,
 1891, 1912, 1919, 1939, 2054, 2183,
 2186, 2190, 2274, 2337, 2338, 2352,
 2483, 2489, 2491, 2498, 2505, 2507,
 2515, 2522, 2815, 2834, 2859, 2868,
 2884, 2906, 2926, 2944, 2962, 2975,
 2986, 2996, 3016, 3039, 3040, 3042,
 3048, 3051, 3124, 3126, 3132, 3134,
 3147, 3154, 3156, 3245, 3254, 3263,
 3382, 3387, 3390, 3391, 3398, 3399,
 3415, 3416, 3437, 3438, 3552, 3561,
 3841, 3869, 3880, 3890, 4023, 4068,
 4207, 4211, 4214, 4215, 4222, 4223,
 4247, 4259, 4357, 4375, 4456, 4478,
 4546, 4636, 4643, 4747, 4748, 4799,
 4807, 4812, 4853, 4865, 4866, 4982,
 5086, 5113, 5143, 5146, 5147, 5148,
 5150, 5163, 5169, 5177, 5188, 5207,
 5229, 5239, 5242, 5264, 5265, 5266,
 5284, 5285, 5286, 5523, 5561, 5573,
 5583, 5584, 5608, 5609, 5610, 5662,
 5894, 5909, 5931, 5947, 6004, 6012,
 6017, 6233, 7738, 8233, 8234, 8235,
 8236, 8247, 8304, 8305, 8411, 8413,
 8564, 8694, 8702, 9055, 9067, 9670,
 9677, 9680, 9783, 9785, 9786, 9796,
 9797, 9798, 9807, 9809, 9817, 9819,
 9827, 9829, 9836, 9837, 9838, 9839,
 9840, 9841, 9846, 9847, 9848, 9849,
 9850, 9851, 9852, 9906, 9908, 9935,
 9939, 9948, 9957, 9958, 9965, 9972,
 9975, 9996, 10064, 10072, 10089,
 10098, 10144, 10187, 10223, 10224,
 10225, 10286, 10287, 10290, 10301,

- 10305, 10312, 10313, 10324, 10325,
10334, 10341, 10343, 10344, 10352,
10371, 10381, 10400, 10401, 10403,
10404, 10408, 10409, 10411, 10412,
10425, 10426, 10428, 10430, 10431,
10432, 10433, 10443, 10444, 10452,
10459, 10466, 10467, 10469, 10470,
10473, 10474, 10475, 10476, 10484,
10485, 10494, 10495, 10497, 10499,
10500, 10501, 10510, 10520, 10521,
10531, 10543, 10544, 10546, 10552,
10556, 10569, 10571, 10579, 10590,
10592, 10598, 10603, 10605, 10607,
10613, 10614, 10618, 10620, 10632,
10633, 10655, 10657, 10663, 10666,
10668, 10672, 10677, 10682, 10683,
10693, 10694, 10696, 10697, 10700,
10704, 10709, 10720, 10726, 10737,
10739, 10746, 10747, 10749, 10750,
10757, 10763, 10773, 10819, 10822,
10834, 10845, 10846, 10847, 10848,
10850, 10852, 10854, 10855, 10856,
10862, 10863, 10873, 10876, 10877,
10880, 10882, 10883, 10889, 10897,
10898, 10899, 10900, 10902, 10904,
10913, 10919, 10933, 10934, 10936,
10937, 10955, 10956, 10958, 10959,
10965, 10966, 10968, 10971, 10982,
10983, 10984, 10986, 10987, 10988,
10994, 10995, 11022, 11053, 11054,
11063, 11064, 11065, 11075, 11076,
11077, 11097, 11098, 11099, 11114,
11123, 11124, 11125, 11141, 11142,
11156, 11157, 11168, 11169, 11171,
11179, 11180, 11181, 11184, 11186,
11187, 11188, 11208, 11209, 11211,
11212, 11213, 11223, 11224, 11225,
11227, 11228, 11229, 11235, 11236,
11237, 11239, 11240, 11241, 11262,
11263, 11278, 11279, 11281, 11282,
11283, 11303, 11304, 11305, 11306,
11307, 11308, 11309, 11310, 11315,
11316, 11317, 11318, 11319, 11320,
11326, 11327, 11329, 11330, 11331,
11345, 11346, 11349, 11351, 11352,
11353, 11361, 11362, 11365, 11367,
11368, 11369, 11379, 11380, 11381,
11383, 11384, 11385, 11396, 11397,
11398, 11401, 11404, 11408, 11450,
11464, 11474, 11482, 11483, 11583,
11584, 11591, 11592, 11630, 11632,
11654, 11655, 11658, 11665, 11666,
11669, 11670, 11676, 11681, 11688,
11689, 11696, 11697, 11749, 11750,
11751, 11753, 11764, 11780, 11781,
11783, 11784, 11794, 11796, 11802,
11803, 11807, 11810, 11832, 11834,
11847, 11849, 11855, 11857, 11860,
11866, 11868, 11870, 11871, 11872,
11874, 11879, 11881, 11883, 11887,
11890, 11896, 11897, 11901, 11903,
11904, 11905, 11913, 11915, 11916,
11923, 11929, 11936, 11937, 11942,
11943, 11944, 11945, 11963, 11964,
11965, 11971, 11972, 11973, 11978,
11980, 11988, 11990, 11992, 11993,
11995, 12006, 12008, 12010, 12011,
12016, 12067, 12068, 12075, 12076,
12078, 12080, 12082, 12084, 12086,
12088, 12090, 12099, 12101, 12107,
12109, 12111, 12112, 12113, 12119,
12121, 12123, 12124, 12125, 12146,
12147, 12150, 12158, 12160, 12164,
12165, 12166, 12167, 12172, 12174,
12180, 12183, 12186, 12189, 12197,
12200, 12203, 12206, 12213, 12215,
12221, 12229, 12231, 12233, 12250,
12252, 12259, 12261, 12264, 12270,
12272, 12274, 12275, 12276, 12278,
12282, 12283, 12284, 12285, 12290,
12291, 12292, 12293, 12304, 12310,
12311, 12323, 12331, 12333, 12343,
12345, 12352, 12361, 12363, 12366,
12369, 12372, 12375, 12389, 12391,
12399, 12401, 12409, 12411, 12420,
12423, 12426, 12433, 12450, 12451,
12452, 12454, 12455, 12456, 12458,
12459, 12465, 12467, 12468, 12474,
12476, 12477, 12478, 12479, 12491,
12497, 12499, 12532, 12533, 12534,
12569, 12576, 12594, 12596, 12637,
12644, 12651, 12671, 12672, 12674,
12676, 12678, 12690, 12695, 12696,
12697, 12698, 12699, 12703, 12708,
12710, 12716, 12722, 12724, 12725,
12731, 12732, 12733, 12734, 12735,
12736, 12737, 12738, 12743, 12745,
12747, 12749, 12751, 12755, 12757,
12759, 12761, 12763, 12765, 12783,
12787, 12795, 12796, 12801, 12803,

12812, 12815, 12816, 12817, 12819,
 12820, 12821, 12829, 12835, 12847,
 12850, 12851, 12853, 12854, 12872,
 12873, 12877, 12883, 12887, 12889,
 12906, 12924, 12930, 12939, 12940,
 12941, 12942, 12950, 12966, 12982,
 12998, 13014, 13030, 13056, 13060,
 13061, 13065, 13067, 13098, 13104,
 13105, 13107, 13109, 13110, 13112,
 13113, 13123, 13124, 13127, 13128,
 13129, 13131, 13132, 13133, 13150,
 13151, 13153, 13154, 13160, 13162,
 13165, 13168, 13171, 13174, 13182,
 13185, 13187, 13190, 13197, 13201,
 13209, 13210, 13213, 13215, 13217,
 13221, 13225, 13230, 13231, 13251,
 13252, 13258, 13259, 13378, 13380,
 13387, 13388, 13389, 13392, 13394,
 13397, 13398, 13405, 13410, 13417,
 13418, 13419, 13420, 13421, 13430,
 13433, 13438, 13440, 13442, 13444,
 13446, 13470, 13471, 13480, 13481,
 13495, 13497, 13524, 13525, 13534,
 13537, 13561, 13562, 13566, 13584,
 13588, 13598, 13601, 13607, 13608,
 13627, 13629, 13630, 13639, 13643,
 13648, 13651, 13657, 13683, 13684,
 13690, 13691, 13692, 13699, 13707,
 13711, 13716, 13719, 13727, 13730,
 13731, 13733, 13734, 13744, 13748,
 13753, 13758, 13767, 13768, 13771,
 13772, 13814, 13816, 13817, 13887,
 13894, 13912, 13945, 13971, 13972,
 13973, 13974, 13975, 13976, 13984,
 13989, 14581, 14582, 14585, 14586,
 14920, 14921, 14922, 14929, 14930,
 15016, 15017, 15020, 15021, 15063,
 15083, 15113, 15121, 15145, 15146
`\exp_args:cc`
 ... [784](#), [786](#), [963](#), [973](#), [978](#), [983](#), [1673](#)
`\exp_args:Nc` [28](#), [784](#), [784](#),
 [788](#), [796](#), [1203](#), [1213](#), [1231](#), [1257](#),
 [1262](#), [1269](#), [1324](#), [1335](#), [1391](#), [1424](#),
 [1425](#), [1426](#), [1427](#), [1446](#), [1673](#), [4953](#),
 [8958](#), [10014](#), [11195](#), [11196](#), [11197](#),
 [11198](#), [11199](#), [11200](#), [13950](#), [14838](#)
`\exp_args:Ncc` [1259](#), [1263](#), [1271](#),
 [1432](#), [1433](#), [1434](#), [1435](#), [1673](#), [1675](#)
`\exp_args:Nccc` [1673](#), [1677](#)
`\exp_args:Ncco` [1733](#), [1754](#)
`\exp_args:Nccx` [1777](#), [1786](#)
`\exp_args:Ncf` [1696](#), [1720](#)
`\exp_args:NcNc` [1733](#), [1740](#)
`\exp_args:NcNo` [1733](#), [1747](#)
`\exp_args:Ncnx` [1777](#), [1787](#)
`\exp_args:Nco` [1696](#), [1714](#)
`\exp_args:Ncx` [1762](#), [1772](#)
`\exp_args:Nf` [29](#), [1684](#), [1684](#), [3595](#),
 [3743](#), [3812](#), [3824](#), [3833](#), [3926](#), [3939](#),
 [3953](#), [3963](#), [3974](#), [3985](#), [4284](#), [6146](#),
 [8245](#), [14483](#), [14496](#), [14501](#), [14517](#),
 [14915](#), [15082](#), [15137](#), [15150](#), [15168](#)
`\exp_args:Nff` [1762](#), [1764](#)
`\exp_args:Nfo` [1762](#), [1763](#), [14471](#)
`\exp_args:NNc` [1258](#), [1261](#),
 [1270](#), [1337](#), [1428](#), [1429](#), [1430](#), [1431](#),
 [1465](#), [1673](#), [1673](#), [3704](#), [3711](#), [8247](#)
`\exp_args:Nnc` [1762](#), [1762](#)
`\exp_args:NNf` [1696](#), [1696](#), [3681](#), [3688](#), [3697](#)
`\exp_args:Nnf` [1762](#), [1765](#)
`\exp_args:Nnnc` [1777](#), [1779](#)
`\exp_args:NNNo` [30](#), [1668](#), [1671](#)
`\exp_args:NNno` [1777](#), [1777](#)
`\exp_args:Nnno` [1777](#), [1780](#)
`\exp_args:NNNV` [1733](#), [1733](#)
`\exp_args:NNnx` [30](#), [1777](#), [1782](#)
`\exp_args:Nnnx` [1777](#), [1784](#)
`\exp_args:NNo` [29](#),
 [1668](#), [1669](#), [3731](#), [6227](#), [9584](#), [15139](#)
`\exp_args:Nno` [29](#),
 [1762](#), [1766](#), [3237](#), [4254](#), [6101](#), [10049](#),
 [10057](#), [10066](#), [10083](#), [10091](#), [10119](#)
`\exp_args:NNoo` [30](#), [1777](#), [1778](#)
`\exp_args:NNox` [1777](#), [1783](#)
`\exp_args:Nnox` [1777](#), [1785](#)
`\exp_args:NNV` [1696](#), [1708](#)
`\exp_args:NNv` [1696](#), [1702](#)
`\exp_args:NnV` [1762](#), [1767](#)
`\exp_args:NNx` [30](#), [1762](#), [1771](#)
`\exp_args:Nnx` [1762](#), [1773](#)
`\exp_args:No` [28](#), [1668](#), [1668](#), [3731](#),
 [3816](#), [4462](#), [4738](#), [4901](#), [4902](#), [4903](#),
 [4916](#), [4917](#), [4918](#), [4919](#), [4942](#), [4959](#),
 [4968](#), [5022](#), [5024](#), [5132](#), [5134](#), [5157](#),
 [5166](#), [5429](#), [5833](#), [6011](#), [6025](#), [6030](#),
 [8958](#), [9666](#), [14511](#), [14515](#), [14853](#), [15170](#)
`\exp_args:Noc` [1762](#), [1770](#)
`\exp_args:Nof` [1762](#), [1769](#)
`\exp_args:Noo` [1762](#), [1768](#)
`\exp_args:Nooo` [1777](#), [1781](#)

\exp_args:Noox 1777, 1788
 \exp_args:Nox 1762, 1774
 \exp_args:NV 29, 1684, 1691
 \exp_args:Nv 29, 1684, 1686
 \exp_args:NVV 1696, 1726
 \exp_args:Nx 29, 1285, 1761, 1761, 7704
 \exp_args:Nxo 1762, 1775
 \exp_args:Nxx 1762, 1776
 \exp_last_two_unbraced:Noo
 31, 1849, 1849, 7034, 7257, 7261
 \exp_last_unbraced:Nco
 1812, 1819, 6084, 6431
 \exp_last_unbraced:NcV 1812, 1821
 \exp_last_unbraced:Nf
 31, 1812, 1817, 3822, 14540
 \exp_last_unbraced:Nfo 1812, 1846, 14896
 \exp_last_unbraced>NNNNo 1812, 1842
 \exp_last_unbraced:NnNo 1812, 1847
 \exp_last_unbraced>NNNV 1812, 1835
 \exp_last_unbraced:NNo
 1812, 1833, 5100, 6052, 6415, 7231
 \exp_last_unbraced:Nno 1812, 1844, 14868
 \exp_last_unbraced:NNV 1812, 1827
 \exp_last_unbraced:No 1812,
 1816, 7386, 7391, 7469, 7475, 14526
 \exp_last_unbraced:Noo
 1812, 1845, 6367, 14881
 \exp_last_unbraced:NV 1812, 1812
 \exp_last_unbraced:Nv 1812, 1814
 \exp_last_unbraced:Nx 31, 1812, 1848
 \exp_not:c 32, 1853,
 1854, 1964, 2014, 2366, 2370, 2375,
 2379, 2384, 2386, 2387, 2388, 2393,
 2395, 2396, 2397, 2402, 2404, 2405,
 2406, 2411, 2413, 2414, 2415, 2422,
 2424, 2426, 2428, 2430, 2432, 2434,
 2436, 2440, 2441, 2442, 3184, 7784,
 7786, 7788, 7790, 7796, 7801, 7803,
 7805, 8028, 8030, 8032, 8034, 8040,
 8045, 8047, 8049, 8238, 8375, 8377,
 8379, 8381, 8434, 8460, 8582, 8584,
 8597, 8599, 8747, 11733, 13903, 13909
 \exp_not:f 32, 1853, 1855
 \exp_not:N 32, 772, 773, 932,
 994, 997, 1342, 1343, 1391, 1392,
 1614, 1650, 1854, 1888, 1923, 1932,
 1961, 1962, 1963, 2014, 2054, 2371,
 2374, 2378, 2384, 2393, 2402, 2411,
 2497, 2504, 2521, 2548, 2557, 2709,
 2733, 2738, 2743, 2748, 2755, 2761,
 2766, 2771, 2776, 2781, 2786, 2796,
 2801, 2829, 2834, 3087, 3092, 3110,
 3123, 3153, 3716, 4362, 4363, 4366,
 4738, 4745, 4755, 4757, 4791, 4792,
 5185, 5188, 5204, 5207, 5238, 5245,
 5428, 5430, 5706, 6136, 6139, 6147,
 6148, 6618, 7795, 8039, 8238, 8450,
 8582, 8584, 8597, 8599, 8626, 8627,
 8652, 8653, 8707, 8730, 8731, 8747,
 9582, 9650, 13740, 13743, 13813,
 13814, 13816, 13817, 13818, 13819,
 13821, 13901, 13902, 13907, 13908,
 14047, 14084, 14089, 14112, 15005
 \exp_not:n 32, 772, 774, 933, 935, 999,
 1287, 1503, 1614, 1809, 1968, 1983,
 2367, 2497, 2504, 2521, 2548, 2557,
 3088, 3093, 3107, 3111, 3183, 3185,
 3717, 4589, 4654, 4660, 4672, 4680,
 4696, 4704, 4793, 5259, 5466, 5566,
 5621, 5707, 5852, 6018, 6140, 6146,
 6311, 6317, 6318, 6319, 6340, 7778,
 7795, 7893, 8022, 8039, 8230, 8629,
 8698, 8733, 9099, 9386, 9493, 9496,
 9577, 9724, 11734, 14019, 14023,
 14495, 14528, 14549, 14550, 14594,
 14599, 14889, 14914, 14979, 14982,
 14985, 15030, 15039, 15059, 15167
 \exp_not:o 32, 1853, 1853, 4619, 4621,
 4656, 4662, 4672, 4674, 4676, 4678,
 4680, 4682, 4684, 4686, 4696, 4698,
 4700, 4702, 4704, 4706, 4708, 4710,
 4757, 4804, 4816, 4921, 5018, 5020,
 5258, 5437, 5439, 5498, 5815, 5817,
 5918, 6011, 8436, 8450, 8451, 8462,
 8465, 8472, 8481, 8949, 8951, 15058
 \exp_not:v
 32, 1853, 1857, 4674, 4682, 4698, 4706
 \exp_not:v 32, 1853, 1862, 8655
 \exp_stop_f: 32, 1624, 1630, 2339,
 3384, 3394, 3402, 8247, 9740, 9946,
 10213, 10229, 10380, 10407, 10568,
 10589, 10616, 10630, 10665, 10692,
 10701, 10736, 10755, 10771, 10816,
 10832, 10843, 10895, 11332, 11502,
 11504, 11507, 11515, 11516, 11741,
 11743, 11763, 11805, 11878, 11900,
 11954, 11955, 12294, 12626, 12644,
 12653, 12809, 12844, 12943, 13055,
 13097, 13102, 13184, 13239, 13272,
 13286, 13301, 13316, 13331, 13346,

- 13361, 13452, 13453, 13454, 13469,
13599, 13649, 13703, 13717, 15140
\expandafter 13,
14, 32, 36, 62, 63, 65, 68, 69, 72,
73, 87, 106, 138, 173, 176, 182, 186,
190, 191, 195, 196, 198, 208, 210,
213, 215, 220, 287, 289, 294, 296, 343
\ExplFileDate 50, 303, 751, 1611,
2070, 2470, 2594, 3366, 4146, 4577,
5373, 5783, 6197, 6492, 6730, 7556,
7589, 8387, 9050, 9735, 13997, 14175
\ExplFileDescription 303, 751, 1611,
2070, 2470, 2594, 3366, 4146, 4577,
5373, 5783, 6197, 6492, 6730, 7556,
7589, 8387, 9050, 9735, 13997, 14175
\ExplFileName 303, 751, 1611,
2070, 2470, 2594, 3366, 4146, 4577,
5373, 5783, 6197, 6492, 6730, 7556,
7589, 8387, 9050, 9735, 13997, 14175
\ExplFileVersion 50, 303, 751, 1611,
2070, 2470, 2594, 3366, 4146, 4577,
5373, 5783, 6197, 6492, 6730, 7556,
7589, 8387, 9050, 9735, 13997, 14175
\ExplSyntaxNamesOff 285, 292
\ExplSyntaxNamesOn 285, 285
\ExplSyntaxOff 4, 6, 109,
110, 185, 193, 215, 246, 251, 265, 280
\ExplSyntaxOn 4, 6,
109, 124, 155, 162, 167, 213, 246, 247
- F**
- \F 2809, 3008, 10363
\fam 335
\fi 45, 66, 71, 108, 181, 201, 216, 374
\fi: 23, 754, 758, 795, 929, 942, 961,
1008, 1013, 1020, 1058, 1063, 1096,
1097, 1105, 1111, 1124, 1125, 1133,
1139, 1200, 1280, 1300, 1310, 1321,
1422, 1505, 1510, 1518, 1550, 1593,
1594, 1595, 1596, 1653, 1656, 1663,
1664, 1897, 1913, 1920, 1929, 1944,
1945, 1946, 1960, 1980, 1982, 2003,
2004, 2110, 2150, 2177, 2196, 2316,
2318, 2320, 2322, 2324, 2326, 2484,
2492, 2499, 2508, 2516, 2523, 2531,
2539, 2552, 2561, 2734, 2739, 2744,
2749, 2756, 2762, 2767, 2772, 2777,
2782, 2787, 2792, 2797, 2802, 2824,
2830, 2841, 2842, 2888, 2889, 2910,
2911, 2930, 2931, 2948, 2949, 2966,
2967, 3034, 3043, 3052, 3060, 3127,
3135, 3157, 3387, 3410, 3427, 3428,
3430, 3539, 3544, 3557, 3567, 3590,
3612, 3620, 3870, 4211, 4234, 4243,
4252, 4264, 4450, 4845, 4857, 4870,
4880, 4897, 5087, 5140, 5143, 5151,
5153, 5181, 5195, 5218, 5234, 5243,
5252, 5274, 5278, 5286, 5494, 5497,
5524, 5545, 5555, 5607, 5613, 5895,
5910, 5933, 5949, 6359, 6385, 6566,
6568, 6578, 7619, 9374, 9375, 9681,
9787, 9795, 9799, 9810, 9820, 9830,
9894, 9932, 9933, 9934, 9935, 9936,
9937, 9938, 9939, 9940, 9941, 9942,
9943, 9950, 9963, 9966, 9973, 9976,
10021, 10124, 10193, 10194, 10203,
10204, 10215, 10216, 10217, 10227,
10228, 10232, 10233, 10241, 10244,
10245, 10253, 10254, 10261, 10269,
10270, 10291, 10310, 10311, 10320,
10326, 10346, 10347, 10360, 10384,
10405, 10413, 10414, 10478, 10492,
10502, 10522, 10560, 10561, 10564,
10566, 10567, 10572, 10583, 10586,
10588, 10593, 10624, 10637, 10642,
10648, 10651, 10652, 10686, 10687,
10714, 10715, 10730, 10736, 10740,
10745, 10751, 10766, 10777, 10794,
10804, 10806, 10812, 10824, 10827,
10838, 10857, 10867, 10884, 10908,
10960, 10973, 10974, 10989, 11094,
11095, 11096, 11115, 11131, 11148,
11189, 11214, 11230, 11242, 11284,
11293, 11299, 11312, 11314, 11337,
11354, 11370, 11386, 11406, 11409,
11459, 11470, 11482, 11483, 11484,
11491, 11493, 11494, 11500, 11501,
11510, 11511, 11519, 11520, 11522,
11523, 11605, 11615, 11616, 11621,
11622, 11623, 11624, 11625, 11626,
11633, 11642, 11647, 11671, 11673,
11675, 11682, 11709, 11716, 11719,
11720, 11725, 11747, 11748, 11754,
11767, 11785, 11787, 11797, 11811,
11841, 11850, 11884, 11906, 11924,
11941, 11958, 11959, 11961, 11962,
11966, 11981, 12014, 12043, 12044,
12045, 12046, 12047, 12060, 12102,
12175, 12240, 12242, 12243, 12253,
12294, 12469, 12480, 12492, 12507,

12516, 12521, 12528, 12530, 12544,
12548, 12550, 12554, 12625, 12632,
12643, 12659, 12666, 12726, 12782,
12792, 12794, 12804, 12822, 12823,
12855, 12858, 12867, 12869, 12871,
12890, 12904, 12905, 12925, 12946,
12947, 12960, 12976, 12992, 13008,
13024, 13040, 13054, 13062, 13068,
13078, 13081, 13090, 13099, 13101,
13107, 13114, 13117, 13126, 13134,
13155, 13188, 13189, 13216, 13218,
13232, 13233, 13243, 13254, 13263,
13266, 13267, 13276, 13279, 13296,
13311, 13326, 13341, 13356, 13371,
13374, 13376, 13381, 13395, 13399,
13429, 13448, 13449, 13456, 13457,
13459, 13466, 13468, 13472, 13486,
13487, 13498, 13538, 13539, 13567,
13598, 13620, 13632, 13648, 13669,
13702, 13716, 13722, 13735, 13736,
13774, 13775, 13891, 13896, 13951
\file_add_path:nN
 157, 9102, 9102, 9140, 9147, 9260, 9269
\file_if_exist:n 9138
\file_if_exist:nTF 157, 9138
\file_input:n 157, 9145, 9145
\file_list: 158, 9192, 9192
\file_path_include:n 158, 9180, 9180
\file_path_remove:n 158, 9180, 9187
\finalhyphendemerits 523
\firstmark 421
\firstmarks 647
\floatingpenalty 568
\font 334
\fontchardp 672
\fontcharht 671
\fontcharic 674
\fontcharwd 673
\fontdimen 601
\fontname 425
\fp_abs:c 13897
\fp_abs:N 13897, 13897, 13913
\fp_abs:n
 . 177, 13793, 13793, 14330, 14332,
 14384, 14386, 14388, 14782, 14784
\fp_add:cn 13852
\fp_add:Nn 166, 13852, 13852, 13858
\fp_compare:n 11448
\fp_compare:nF 11528, 11539
\fp_compare:nNn 11461
\fp_compare:NNNF 13962
\fp_compare:nNnF 11556, 11567, 13962
\fp_compare:NNNT 13961
\fp_compare:nNnT 11562, 11575, 13961, 14766
\fp_compare:NNNTF 13960, 13960
\fp_compare:nNnTF
 168, 7095, 11461,
 13960, 14209, 14211, 14216, 14404
\fp_compare:nT 11534, 11547
\fp_compare:nTF 11448
\fp_compare_p:n 11448
\fp_compare_p:nNn 168, 11461
\fp_const:cn 13829
\fp_const:Nn
 165, 13829, 13833, 13837,
 13874, 13875, 13876, 13877, 13885
\fp_cos:cn 13931
\fp_cos:Nn 13931, 13941
\fp_div:cn 13917
\fp_div:Nn 13917, 13919, 13927
\fp_do_until:nn 169, 11525, 11525, 11529
\fp_do_until:nNnn 168, 11553, 11553, 11557
\fp_do_while:nn 169, 11525, 11531, 11535
\fp_do_while:nNnn 168, 11553, 11559, 11563
\fp_eval:n 166, 13790, 13792
\fp_exp:cn 13931
\fp_exp:Nn 13931, 13938
\fp_flag_off:n 171, 10011, 10011
\fp_flag_on:n 171, 10013, 10013, 10054,
 10063, 10071, 10088, 10097, 10128
\fp_gabs:c 13897
\fp_gabs:N 13897, 13898, 13914
\fp_gadd:cn 13852
\fp_gadd:Nn 166, 13852, 13853, 13859
\fp_gcos:cn 13931
\fp_gcos:Nn 13931, 13941
\fp_gdiv:cn 13917
\fp_gdiv:Nn 13917, 13920, 13928
\fp_gexp:cn 13931
\fp_gexp:Nn 13931, 13938
\fp_gln:cn 13931
\fp_gln:Nn 13931, 13939
\fp_gmul:cn 13917
\fp_gmul:Nn 13917, 13918, 13926
\fp_gneg:c 13897
\fp_gneg:N 13897, 13905, 13916
\fp_gpow:cn 13917
\fp_gpow:Nn 13917, 13922, 13930
\fp_ground_figures:Nn 13981, 13986, 13992
\fp_ground_places:Nn 13963, 13965, 13980
.fp_gset:c 149
\fp_gset:cn 13829

.fp_gset:N 149
 \fp_gset:Nn 165, 13829, 13831, 13836,
 13853, 13855, 13918, 13920, 13922
 \fp_gset_eq:cc 13838
 \fp_gset_eq:cN 13838
 \fp_gset_eq:Nc 13838
 \fp_gset_eq>NN
 166, 13838, 13839, 13841, 13843
 \fp_gset_from_dim:cn 14859
 \fp_gset_from_dim:Nn
 190, 14859, 14861, 14864
 \fp_gsin:cn 13931
 \fp_gsin:Nn 13931, 13940
 \fp_gsub:cn 13852
 \fp_gsub:Nn 166, 13852, 13855, 13861
 \fp_gtan:cn 13931
 \fp_gtan:Nn 13931, 13942
 \fp_gzero:c 13842
 \fp_gzero:N 165, 13842, 13843, 13845, 13849
 \fp_gzero_new:c 13846
 \fp_gzero_new:N 165, 13846, 13848, 13851
 \fp_if_exist:cF 11446
 \fp_if_exist:cT 11445
 \fp_if_exist:cTF 11440, 11444
 \fp_if_exist:NF 11442
 \fp_if_exist:NT 11441
 \fp_if_exist:NTF
 167, 11440, 11440, 13847, 13849, 13864
 \fp_if_exist_p:c 11440, 11447
 \fp_if_exist_p:N 167, 11440, 11443
 \fp_if_flag_on:n 10015
 \fp_if_flag_on:nTF 171, 10015
 \fp_if_flag_on_p:n 171, 10015
 \fp_if_undefined:N 13886
 \fp_if_undefined:NTF 13886
 \fp_if_undefined_p:N 13886
 \fp_if_zero:N 13893
 \fp_if_zero:NTF 13893
 \fp_if_zero_p:N 13893
 \fp_ln:cn 13931
 \fp_ln:Nn 13931, 13939
 \fp_max:nn 177, 13795, 13795
 \fp_min:nn 177, 13795, 13797
 \fp_mul:cn 13917
 \fp_mul:Nn 13917, 13917, 13925
 \fp_neg:c 13897
 \fp_neg:N 13897, 13899, 13915
 \fp_new:N
 165,
 6753, 6754, 13826, 13826, 13828,
 13847, 13849, 13878, 13879, 13880,
 13881, 14179, 14180, 14181, 14303,
 14304, 14601, 14602, 14744, 14745
 \fp_pow:cn 13917
 \fp_pow:Nn 13917, 13921, 13929
 \fp_round_figures:Nn 13981, 13981, 13991
 \fp_round_places:Nn 13963, 13963, 13979
 .fp_set:c 149
 \fp_set:cn 13829
 .fp_set:N 149
 \fp_set:Nn
 165,
 7091, 7093, 13829, 13829, 13835,
 13852, 13854, 13917, 13919, 13921,
 14196, 14197, 14198, 14314, 14316,
 14344, 14364, 14377, 14378, 14611,
 14612, 14750, 14752, 14776, 14777
 \fp_set_eq:cc 13838
 \fp_set_eq:cN 13838
 \fp_set_eq:Nc 13838
 \fp_set_eq:NN
 166, 13838,
 13838, 13840, 13842, 14349, 14366
 \fp_set_from_dim:cn 14859
 \fp_set_from_dim:Nn
 190, 14859, 14859, 14863
 \fp_show:c 13862
 \fp_show:N 171, 13862, 13862, 13873
 \fp_show:n 13862, 13871
 \fp_sin:cn 13931
 \fp_sin:Nn 13931, 13940
 \fp_sub:cn 13852
 \fp_sub:Nn 166, 13852, 13854, 13860
 \fp_tan:cn 13931
 \fp_tan:Nn 13931, 13942
 \fp_to_decimal:c 13638
 \fp_to_decimal:N 166, 10004,
 13638, 13638, 13640, 13740, 13790
 \fp_to_decimal:n 13638, 13641,
 13743, 13792, 13794, 13796, 13798
 \fp_to_dim:c 13739
 \fp_to_dim:N 166, 13739, 13739, 13741
 \fp_to_dim:n
 7101, 7126, 13739, 13742, 14241,
 14252, 14681, 14689, 14792, 14794
 \fp_to_int:c 13744
 \fp_to_int:N 167, 13744, 13744, 13745
 \fp_to_int:n 13744, 13746
 \fp_to_scientific:c 13583
 \fp_to_scientific:N
 167, 10005, 13583, 13583, 13585
 \fp_to_scientific:n 13583, 13586
 \fp_to_tl:c 13707

```

\fp_to_tl:N 167, 13707, 13707, 13708, 13865
\fp_to_tl:n . 9751, 10053, 10062, 10087,
    10096, 10125, 13707, 13709, 13872
\fp_trap:nn ..... 171, 10027,
    10027, 10139, 10140, 10141, 10142
\fp_until_do:nn . 169, 11525, 11537, 11542
\fp_until_do:nNn 168, 11553, 11565, 11570
\fp_use:c ..... 13790
\fp_use:N ..... 167, 13790, 13790, 13791
\fp_while_do:nn . 169, 11525, 11545, 11550
\fp_while_do:nNn 169, 11553, 11573, 11578
\fp_zero:c ..... 13842
\fp_zero:N 165, 13842, 13842, 13844, 13847
\fp_zero_new:c ..... 13846
\fp_zero_new:N .. 165, 13846, 13846, 13850
\frozen@everydisplay ..... 736
\frozen@everymath ..... 737
\futurelet ..... 330

G
\g_@@_level_int ..... 8390, 8390,
    8435, 8461, 8485, 8487, 8489, 8491
\g_cctab_allocate_int ..... 14026,
    14026, 14027, 14033, 14035, 14037
\g_cctab_stack_int ... 14026, 14028,
    14065, 14066, 14068, 14069, 14073
\g_cctab_stack_seq ..... .
    . 14026, 14029, 14063, 14074, 14076
\g_file_internal_ior ..... 9106,
    9107, 9110, 9126, 9127, 9254, 9254
\g_file_record_seq ..... 9065,
    9065, 9070, 9166, 9171, 9194, 9214
\g_file_stack_seq 9064, 9064, 9173, 9176
\g_ior_internal_ior ..... .
    . 9302, 9302, 9311, 9312, 9314
\g_ior_streams_prop ... 9238, 9238,
    9240, 9289, 9296, 9331, 9346, 9353
\g_iow_internal_iow ..... .
    . 9436, 9436, 9445, 9446, 9448
\g_iow_streams_prop ..... .
    . 9394, 9394, 9396, 9397,
    9398, 9424, 9430, 9465, 9480, 9487
\g_prg_map_int .... 42, 2362, 2362,
    3703, 3706, 3710, 3713, 3724, 4951,
    4952, 4954, 4956, 5685, 5686, 5692,
    5693, 6082, 6083, 6085, 6088, 6429,
    6430, 6432, 6435, 14837, 14839, 14846
\g_scan_marks_t1 2570, 2570, 2573, 2579
\g_file_current_name_t1 ..... .
    . 157, 9053, 9053,
    9058, 9062, 9070, 9173, 9174, 9177
\g_peek_token ..... 57, 3063, 3064, 3074
\g_tmpa_bool ..... 37, 2132, 2134
\g_tmpa_box ..... 127, 6595, 6602
\g_tmpa_clist ..... 117, 6161, 6163
\g_tmpa_dim ..... 79, 4385, 4387
\g_tmpa_fp ..... 170, 13878, 13880
\g_tmpa_int ..... 71, 4088, 4090
\g_tmpa_muskip ..... 85, 4549, 4551
\g_tmpa_prop ..... 123, 6222, 6224
\g_tmpa_seq ..... 108, 5762, 5764
\g_tmpa_skip ..... 82, 4481, 4483
\g_tmpa_t1 ..... 99, 5300, 5300
\g_tmpb_bool ..... 37, 2132, 2135
\g_tmpb_box ..... 127, 6595, 6603
\g_tmpb_clist ..... 117, 6161, 6164
\g_tmpb_dim ..... 79, 4385, 4388
\g_tmpb_fp ..... 170, 13878, 13881
\g_tmpb_int ..... 71, 4088, 4091
\g_tmpb_muskip ..... 85, 4549, 4552
\g_tmpb_prop ..... 123, 6222, 6225
\g_tmpb_seq ..... 108, 5762, 5765
\g_tmpb_skip ..... 82, 4481, 4484
\g_tmpb_t1 ..... 99, 5300, 5301
\gdef ..... 321
.generate_choices:n ..... 149
\GetIdInfo ..... 6, 139
\global ..... 305, 336
\globaldefs ..... 340
\glueexpr ..... 680
\glueshrink ..... 683
\glueshrinkorder ..... 685
\gluestretch ..... 682
\gluestretchorder ..... 684
\gluetomu ..... 686
\group_align_safe_begin: ... 41, 2154,
    2323, 2323, 3095, 3113, 4787, 5067
\group_align_safe_end: ..... .
    . 41, 2202, 2203, 2323, 2325,
    3077, 3087, 3092, 3110, 4796, 5093
\group_begin: ..... 9,
    778, 779, 1064, 1447, 1465, 1878,
    2012, 2026, 2329, 2344, 2694, 2707,
    2714, 2751, 2804, 2844, 3004, 3171,
    4719, 4737, 4888, 5517, 6627, 7559,
    7711, 7728, 7769, 8013, 8220, 8395,
    8405, 9084, 9516, 9521, 9547, 10361,
    10417, 10947, 11137, 11192, 11202,
```

\group_end:	<i>9</i> , 778 , 780	11217 , 11340 , 11373 , 11391 , 11635 , 13406 , 13591 , 14102 , 14195 , 14309 , 14339 , 14359 , 14376 , 15173 , 15180
\group_execute_after:N	1585	
\group_insert_after:N	<i>9</i> , 783 , 783 , 1585	
H		
\halign	347	
\hangafter	525	
\hangindent	526	
\hbadness	587	
\hbox	582	
\hbox:n	128 , 6639 , 6639 , 7353 , 7408 , 14224	
\hbox_gset:cn	6640	
\hbox_gset:cw	6650 , 6662	
\hbox_gset:Nn	128 , 6640 , 6641 , 6643	
\hbox_gset:Nw	128 , 6650 , 6652 , 6655 , 6661	
\hbox_gset_end:	128 , 6650 , 6657 , 6663	
\hbox_gset_inline_begin:c	6658 , 6662	
\hbox_gset_inline_begin:N	6658 , 6661	
\hbox_gset_inline_end:	6658 , 6663	
\hbox_gset_to_wd:cnn	6644	
\hbox_gset_to_wd:Nnn	128 , 6644 , 6646 , 6649	
\hbox_overlap_left:N	128 , 6667 , 6667	
\hbox_overlap_right:N	128 , 6667 , 6669 , 14399	
\hbox_set:cn	6640	
\hbox_set:cw	6650 , 6659	
\hbox_set:Nn	128 , 6640 , 6640 , 6641 , 6642 , 6811 , 6915 , 7139 , 7210 , 7498 , 14193 , 14220 , 14221 , 14307 , 14337 , 14357 , 14374 , 14396 , 14419 , 14424 , 14432 , 14439 , 14448 , 14455 , 14462 , 14623	
\hbox_set:Nw	128 , 6650 , 6650 , 6653 , 6654 , 6658 , 6858	
\hbox_set_end:	128 , 6650 , 6656 , 6660 , 6862	
\hbox_set_inline_begin:c	6658 , 6659	
\hbox_set_inline_begin:N	6658 , 6658	
\hbox_set_inline_end:	6658 , 6660	
I		
pi	176	
\if	191 , 356	
\if:w	23 , 754 , 760 , 1058 , 1938 , 1941 , 1942 , 1996 , 1999 , 3047 , 3153 , 10551 , 10555 , 10577 , 10671 , 10703 , 10725 , 10745 , 10818 , 10861 , 10872 , 11207 , 11222 , 11234 , 13126	
\if_bool:N	41 , 2073 , 2073	
\if_box_empty:N	131 , 6562 , 6564 , 6578	
\if_case:w	72 , 1288 , 3369 , 3373 , 3842 , 9793 , 9946 , 11108 , 11288 , 11332 , 11739 , 11878 , 11953 , 11977 , 12029 , 12626 , 12653 , 12809 , 12844 , 12950 , 12966 , 12982 , 12998 , 13014 , 13030 , 13055 , 13102 , 13224 , 13239 , 13286 , 13301 , 13316 , 13331 , 13346 , 13361 , 13599 , 13649 , 13717	

\if_catcode:w 23, 754, 762, 2733,
2738, 2743, 2748, 2755, 2761, 2766,
2771, 2776, 2781, 2786, 2796, 2829,
3122, 5203, 5245, 5263, 9676, 10398,
10488, 10735, 10782, 10951, 11289
\if_charcode:w
. 23, 754, 761, 2801, 5178, 5184, 5238
\if_cs_exist:N
. 23, 768, 768, 1092, 1120, 2837, 3056
\if_cs_exist:w
768, 769, 791, 1101, 1129, 1276, 10017
\if_dim:w
. 85, 4149, 4149, 4230, 4242, 4268,
4270, 4272, 4274, 4276, 4278, 4280
\if_eof:w 162, 9362, 9362, 9370
\if_false: 23,
754, 755, 2324, 5140, 5143, 5153,
5278, 5286, 5494, 5497, 5607, 5613
\if_hbox:N 131, 6562, 6562, 6566
\if_int_compare:w 72, 781,
781, 1503, 1509, 1514, 2324, 2326,
2496, 2503, 2520, 2547, 2556, 2820,
3038, 3369, 3406, 3539, 3571, 3573,
3575, 3577, 3579, 3581, 3583, 3586,
4136, 4444, 9367, 9793, 9794, 9890,
9955, 9956, 10191, 10201, 10209,
10230, 10242, 10251, 10259, 10267,
10303, 10308, 10380, 10407, 10464,
10487, 10568, 10589, 10616, 10630,
10665, 10692, 10735, 10755, 10771,
10784, 10796, 10816, 10832, 10843,
10895, 10952, 10962, 11127, 11144,
11178, 11277, 11344, 11358, 11377,
11395, 11400, 11463, 11493, 11496,
11507, 11510, 11515, 11516, 11519,
11522, 11607, 11680, 11743, 11763,
11805, 11900, 11954, 11955, 11958,
11961, 12030, 12039, 12240, 12490,
12505, 12514, 12519, 12639, 12655,
12780, 12814, 12875, 12882, 12886,
12923, 13095, 13097, 13108, 13126,
13149, 13181, 13184, 13227, 13247,
13248, 13256, 13257, 13271, 13386,
13391, 13452, 13453, 13454, 13469,
13626, 13700, 13726, 13729, 13890
\if_int_odd:w 72, 3369, 3372, 3608,
3616, 10213, 10227, 10239, 12013,
13272, 13483, 13494, 13536, 13564
\if_meaning:w 23,
754, 763, 925, 940, 957, 1004, 1009,
1018, 1089, 1107, 1117, 1135, 1306,
1317, 1421, 1548, 1650, 1651, 1888,
1909, 1918, 2106, 2177, 2196, 2482,
2488, 2514, 2527, 2535, 2791, 2834,
2876, 2879, 2898, 2901, 2918, 2921,
2936, 2939, 2954, 2957, 3030, 3131,
3387, 3422, 3427, 3428, 3567, 4211,
4264, 4841, 4853, 4865, 4876, 4891,
5085, 5146, 5229, 5522, 5541, 5549,
5891, 5906, 5928, 5944, 6355, 6381,
9782, 9795, 9806, 9816, 9826, 9971,
9973, 10124, 10190, 10200, 10212,
10227, 10228, 10239, 10240, 10250,
10266, 10285, 10320, 10323, 10339,
10346, 10399, 10519, 10642, 10648,
10783, 10980, 11086, 11089, 11092,
11455, 11482, 11483, 11484, 11485,
11486, 11487, 11600, 11601, 11629,
11640, 11650, 11707, 11714, 11723,
11740, 11774, 11779, 11793, 11839,
11846, 11922, 11934, 12033, 12036,
12047, 12098, 12171, 12239, 12242,
12249, 12294, 12463, 12473, 12540,
12551, 12623, 12721, 12800, 12849,
12863, 13052, 13064, 13076, 13079,
13082, 13107, 13208, 13212, 13377,
13429, 13486, 13539, 13598, 13648,
13716, 13763, 13766, 13896, 13951
\if_mode_horizontal: 23, 764, 765, 2318
\if_mode_inner: 23, 764, 767, 2320
\if_mode_math: 23, 764, 764, 2322
\if_mode_vertical: 23, 764, 766, 2316
\if_num:w 4136, 4136
\if_predicate:w 41, 2073, 2074, 2146
\if_true: 23, 754, 754
\if_vbox:N 131, 6562, 6563, 6568
\ifcase 357
\ifcat 358
\ifcsname 641
\ifdefined 640
\ifdim 361
\ifeof 362
\iffalse 367
\iffontchar 670
\ifhbox 363
\ifhmode 369
\ifinner 372
\ifmmode 370
\ifnum 359
\ifodd 176, 212, 360

```

\iftrue ..... 368
\ifvbox ..... 364
\ifvmode ..... 371
\ifvoid ..... 365
\ifx ..... 14, 63, 69, 73, 366
\ignorespaces ..... 414
\immediate ..... 376
min ..... 175
sin ..... 176
\indent ..... 510
\initcatcodetable ..... 729
.initial:n ..... 149
.initial:V ..... 149
\input ..... 384
\input@path ..... 9116, 9119, 9134
\inputlineno ..... 386
\insert ..... 566
\insertpenalties ..... 569
\int_abs:n ..... 61, 3380, 3380
\int_add:cn ..... 3506
\int_add:Nn ..... 63, 3506,
                 3506, 3511, 3514, 9598, 9611, 9649
\int_case:nnn ..... 65, 2457,
                  3592, 3592, 3733, 3739, 14578, 15013
\int_compare:n ..... 3550
\int_compare:nF ..... 3632, 3647
\int_compare:nNn ..... 3584
\int_compare:nNnf ..... 3660,
                     3675, 3694, 9341, 9343, 9475, 9477
\int_compare:nNt ..... 3652, 3669, 4366, 9309,
                     9327, 9443, 9461, 14066, 14900, 15154
\int_compare:nNtf ..... 64, 2228, 3454, 3456, 3584, 3601,
                     3680, 3683, 3729, 3815, 3821, 3968,
                     3992, 3996, 4046, 9285, 9420, 9599,
                     13675, 13677, 14034, 14479, 14481,
                     14486, 14494, 14514, 14913, 15166
\int_compare:nT ..... 3624, 3641
\int_compare:nTf ..... 64, 3550
\int_compare_p:n ..... 64, 3550
\int_compare_p:nNn ..... 64, 3584
\int_const:cn ..... 3452, 4005, 4006,
                  4007, 4008, 4009, 4010, 4011, 4012,
                  4013, 4014, 4015, 4016, 4017, 4018
\int_const:Nn ..... 62, 3452, 3452,
                  3472, 4069, 4070, 4071, 4072, 4073,
                  4074, 4075, 4076, 4077, 4078, 4079,
                  4080, 4081, 4082, 4083, 4084, 4085,
                  4086, 4087, 9765, 9864, 9865, 9866,
                  9870, 9871, 9872, 9877, 9878, 9879
\int_convert_from_base_ten:nn ..... 4092, 4093
\int_convert_to_base_ten:nn ..... 4092, 4095
\int_convert_to_symbols:nnn ..... 4092, 4094
\int_decr:c ..... 3518
\int_decr:N ..... 63, 3518, 3520, 3525, 3527
\int_div_round:nn ..... 61, 3412, 3433
\int_div_truncate:nn ..... 62, 3412, 3412, 3744, 3834
\int_do_until:nn ..... 66, 3622, 3644, 3648
\int_do_until:nNn ..... 65, 3650, 3672, 3676
\int_do_while:nn ..... 66, 3622, 3638, 3642
\int_do_while:nNn ..... 65, 3650, 3666, 3670
\int_eval:n ..... 61, 1314, 1330, 3374, 3375, 3378,
                 3595, 3690, 3698, 3726, 3812, 3881,
                 3891, 3950, 3964, 3968, 3971, 3986,
                 3995, 4992, 4997, 5716, 6127, 6136,
                 6619, 9771, 14483, 14496, 14518,
                 14898, 14915, 15087, 15152, 15168
\int_eval:w ..... 4138, 4138
\int_eval_end: ..... 4138, 4139
\int_from_alpha:n ..... 69, 3948, 3948
\int_from_base:nn ..... 70, 3969, 3969, 4000, 4002, 4004, 4095
\int_from_binary:n ..... 69, 3999, 3999
\int_from_hexadecimal:n ..... 69, 3999, 4001
\int_from_octal:n ..... 70, 3999, 4003
\int_from_roman:n ..... 70, 4019, 4019
\int_gadd:cn ..... 3506
\int_gadd:Nn ..... 63, 3506, 3510, 3515, 14033, 14065
\int_gdecr:c ..... 3518
\int_gdecr:N ..... 63, 3518, 3524, 3529, 3724,
                  4956, 5693, 6088, 6435, 8491, 14846
\int_gincr:c ..... 3518
\int_gincr:N ..... 63, 3518, 3522, 3528, 3703, 3710,
                  4951, 5685, 6082, 6429, 8485, 14837
.int_gset:c ..... 149
\int_gset:cn ..... 3530
.int_gset:N ..... 149
\int_gset:Nn ..... 63, 3459, 3469, 3530, 3532, 3534
\int_gset_eq:cc ..... 3492
\int_gset_eq:cN ..... 3492
\int_gset_eq:Nc ..... 3492
\int_gset_eq>NN ..... 62, 3492, 3495, 3496, 3497, 7756
\int_gsub:cn ..... 3506

```

```

\int_gsub:Nn . . . 63, 3506, 3512, 3517, 14073
\int_gzero:c . . . . . 3482
\int_gzero:N . . . 62, 3482, 3483, 3485, 3489
\int_gzero_new:c . . . . . 3486
\int_gzero_new:N . . . 62, 3486, 3488, 3491
\int_if_even:n . . . . . 3614
\int_if_even:nTF . . . . . 65, 3606
\int_if_even_p:n . . . . . 65, 3606
\int_if_exist:cF . . . 3504, 4035, 4042, 4044
\int_if_exist:cT . . . . . 3503
\int_if_exist:cTF . . . . . 3498, 3502
\int_if_exist:NF . . . . . 3500
\int_if_exist:NT . . . . . 3499
\int_if_exist:NTF 63, 3487, 3489, 3498, 3498
\int_if_exist_p:c . . . . . 3498, 3505
\int_if_exist_p:N . . . . . 63, 3498, 3501
\int_if_odd:n . . . . . 3606
\int_if_odd:nTF . . . . . 65, 3606
\int_if_odd_p:n . . . . . 65, 3606
\int_incr:c . . . . . . 3518
\int_incr:N 63, 3518, 3518, 3523, 3526,
             8623, 8649, 8727, 9326, 9460, 9617
\int_max:nn . . . . . 62, 3380, 3388
\int_min:nn . . . . . 62, 3380, 3396
\int_mod:nn . . . . . 62, 3412, 3435, 3734, 3825
\int_new:c . . . . . . 3444
\int_new:N . . . . . .
             . 62, 2362, 3444, 3445, 3451, 3458,
             3468, 3487, 3489, 4088, 4089, 4090,
             4091, 4137, 8390, 8505, 9242, 9504,
             9506, 9507, 9508, 9509, 14026, 14028
.int_set:c . . . . . . 149
\int_set:cn . . . . . . 3530
.int_set:N . . . . . . 149
\int_set:Nn . . . . . 63, 3530, 3530,
             3532, 3533, 6628, 6629, 8627, 8653,
             8731, 9298, 9312, 9387, 9432, 9446,
             9505, 9554, 9568, 9596, 9624, 14027
\int_set_eq:cc . . . . . . 3492
\int_set_eq:cN . . . . . . 3492
\int_set_eq:Nc . . . . . . 3492
\int_set_eq>NN . . . . . .
             . 62, 3492, 3492, 3493, 3494,
             6630, 9283, 9385, 9418, 9522, 9548
\int_show:c . . . . . . 4065, 4066
\int_show:N . . . . . . 70, 4065, 4065
\int_show:n . . . . . . 70, 4067, 4067
\int_step_function:nnnN . . . . .
             . 67, 2463, 3678, 3678, 3723
\int_step_inline:nnnn . . . .
             . . 67, 2464, 3701, 3701, 14145, 14150
\int_step_variable:nnnNn . . . .
             . . . 67, 2465, 3701, 3708
\int_sub:cn . . . . . . . 3506
\int_sub:Nn 63, 3506, 3508, 3513, 3516, 9655
\int_to_Alph:n . . . . . 68, 3747, 3779
\int_to_alpha:n . . . . . 68, 3747, 3747
\int_to_arabic:n . . . . . 67, 3726, 3726
\int_to_base:nn . . . .
             . . . . . 69, 3811, 3811, 3873, 3875, 3877, 4093
\int_to_binary:n . . . . . 68, 3872, 3872
\int_to_hexadecimal:n . . . . . 69, 3872, 3874
\int_to_octal:n . . . . . 69, 3872, 3876
\int_to_Roman:n . . . . . 69, 3878, 3888
\int_to_roman:n . . . . . 69, 3878, 3878
\int_to_symbol:n . . . . . . 4097, 4098
\int_to_symbol_math:n . . . . . 4097, 4102, 4105
\int_to_symbol_text:n . . . . . 4097, 4103, 4120
\int_to_symbols:nnn . . . . . 68, 3727, 3727,
             3743, 3749, 3781, 4094, 4107, 4122
\int_until_do:nn . . . . . 66, 3622, 3630, 3635
\int_until_do:nNn . . . . . 66, 3650, 3658, 3663
\int_use:c . . . . . . . 3535, 3536
\int_use:N . . . . . . . 64,
             3383, 3391, 3392, 3399, 3400, 3414,
             3416, 3417, 3535, 3535, 3536, 3552,
             3706, 3713, 4068, 4952, 4954, 5686,
             5692, 6083, 6085, 6430, 6432, 7678,
             8127, 8435, 8461, 8487, 8489, 8628,
             8654, 8732, 9305, 9314, 9318, 9321,
             9329, 9387, 9439, 9448, 9452, 9455,
             9463, 9777, 9980, 10226, 10302,
             10306, 10345, 10547, 10604, 10615,
             10664, 10695, 10701, 10702, 10849,
             10851, 10874, 10881, 10890, 10901,
             10903, 11172, 11804, 11833, 11835,
             11856, 11858, 11867, 11869, 11891,
             11898, 11904, 11914, 11916, 11989,
             11991, 12007, 12009, 12069, 12077,
             12079, 12081, 12083, 12085, 12087,
             12089, 12108, 12110, 12120, 12122,
             12148, 12151, 12159, 12161, 12181,
             12184, 12187, 12190, 12198, 12201,
             12204, 12207, 12214, 12216, 12222,
             12230, 12232, 12234, 12260, 12262,
             12271, 12273, 12286, 12305, 12312,
             12324, 12332, 12334, 12344, 12346,
             12353, 12362, 12364, 12367, 12370,
             12373, 12376, 12390, 12392, 12400,
```

12402, 12410, 12412, 12421, 12424,
 12427, 12434, 12453, 12498, 12500,
 12535, 12570, 12577, 12595, 12597,
 12645, 12675, 12677, 12679, 12691,
 12704, 12709, 12711, 12717, 12734,
 12735, 12736, 12737, 12738, 12739,
 12744, 12746, 12748, 12750, 12752,
 12756, 12758, 12760, 12762, 12764,
 12766, 12788, 12796, 12878, 12931,
 13161, 13163, 13166, 13169, 13172,
 13175, 13191, 13390, 13431, 13434,
 13439, 13441, 13443, 13445, 13526,
 13563, 13609, 13631, 13976, 14839
`\int_value:w` 4140, 4140
`\int_while_do:nn` ... 66, 3622, 3622, 3627
`\int_while_do:nNn` ... 66, 3650, 3650, 3655
`\int_zero:c` 3482
`\int_zero:N` 62, 3482, 3482, 3484, 3487,
 8620, 8639, 8724, 9570, 9572, 9643
`\int_zero_new:c` 3486
`\int_zero_new:N` ... 62, 3486, 3486, 3490
`\interactionmode` 668
`\interlinepenalties` 689
`\interlinepenalty` 548
`\ior_close:c` 9338
`\ior_close:N`
 ... 159, 9110, 9282, 9338, 9338, 9351
`\ior_get:NN` ... 159, 9379, 9379, 9712, 14832
`\ior_get_str:NN` 159, 9381, 9381, 9714, 14834
`\ior_gto:NN` 9712, 9713
`\ior_if_eof:N` 9363
`\ior_if_eof:NF` 9127, 14844, 14851
`\ior_if_eof:NTF` 159, 9107, 9363
`\ior_if_eof:p:N` 159, 9363
`\ior_list_streams:` ... 159, 9352, 9352, 9729
`\ior_map_break:`
 189, 14827, 14827, 14828, 14830, 14845
`\ior_map_break:n` 190, 14827, 14829
`\ior_map_inline:Nn` ... 189, 14831, 14831
`\ior_new:c` 9252
`\ior_new:N` 158, 9252, 9252, 9253, 9254, 9302
`\ior_open:cn` 9255
`\ior_open:Nn` ... 158, 9255, 9255, 9257, 9265
`\ior_open:NnF` 9278
`\ior_open:NnT` 9277
`\ior_open:NnTF` 9255, 9279
`\ior_open_streams:` 9728, 9729
`\ior_str_gto:NN` 9712, 9715
`\ior_str_map_inline:Nn` 189, 14831, 14833
`\ior_str_to:NN` 9712, 9714, 9715

J

`\jobname` 623

K

`\kern` 501
`\keys_define:nn` ... 147, 8514, 8514, 9002
`\keys_if_choice_exist:nnn` 8974
`\keys_if_choice_exist:nnnTF` ... 154, 8974
`\keys_if_choice_exist_p:nnn` ... 154, 8974
`\keys_if_exist:nn` 8968
`\keys_if_exist:nnTF` 154, 8968
`\keys_if_exist_p:nn` 154, 8968

\keys_set:nn
 153, 8698, 8702, 8707, 8851, 8851, 8859
 \keys_set:no
 8851
 \keys_set:nV
 8851
 \keys_set:nv
 8851
 \keys_set_known:nnN 154, 8861, 8861, 8873
 \keys_set_known:noN
 8861
 \keys_set_known:nVN
 8861
 \keys_set_known:nvN
 8861
 \keys_show:nn
 154, 8980, 8980
 \keyval_parse>NNn . .
 156, 8483, 8483,
 8519, 8856, 8868, 9040, 9041, 9042
 \KV_process_no_space_removal_no_sanitise:NNn

 9039, 9042
 \KV_process_space_removal_no_sanitise:NNn

 9039, 9041
 \KV_process_space_removal_sanitise:NNn

 9039, 9040

L

\l@expl@log@functions@bool .. 1190, 7609
 \l@@key_tl

 8391, 8391, 8436, 8451, 8455, 8462
 \l@@parse_tl
 8393, 8394, 8410,
 8414, 8432, 8458, 8467, 8471, 8480
 \l@@sanitise_tl
 8393,
 8393, 8406, 8407, 8408, 8409, 8412
 \l@@value_tl
 8391,
 8392, 8464, 8466, 8469, 8479, 8481
 \l_box_angle_fp
 186, 14179, 14179, 14196, 14197, 14198
 \l_box_bottom_dim

 14182, 14183, 14206, 14263,
 14267, 14272, 14278, 14283, 14287,
 14296, 14298, 14311, 14319, 14330,
 14341, 14347, 14361, 14380, 14386
 \l_box_bottom_new_dim

 14186, 14187, 14232, 14264, 14275,
 14286, 14297, 14329, 14385, 14403
 \l_box_cos_fp
 186, 14180, 14180,
 14198, 14211, 14216, 14243, 14255
 \l_box_internal_box
 186,
 14190, 14190, 14220, 14221, 14227,
 14231, 14232, 14233, 14235, 14396,
 14402, 14403, 14409, 14414, 14415
 \l_box_left_dim
 14182, 14184, 14208, 14263, 14265,
 14274, 14278, 14283, 14289, 14294,
 14298, 14313, 14343, 14363, 14382
 \l_box_left_new_dim

 14186, 14188, 14223,
 14234, 14266, 14277, 14288, 14299
 \l_box_right_dim 14182, 14185, 14207,
 14261, 14267, 14272, 14276, 14285,
 14287, 14296, 14300, 14312, 14315,
 14342, 14362, 14365, 14381, 14388
 \l_box_right_new_dim . 14186, 14189,
 14234, 14268, 14279, 14290, 14301,
 14328, 14387, 14406, 14408, 14414
 \l_box_scale_x_fp

 186, 14303, 14303, 14314, 14349,
 14364, 14366, 14377, 14388, 14404
 \l_box_scale_y_fp
 186, 14303,
 14304, 14316, 14330, 14332, 14344,
 14349, 14366, 14378, 14384, 14386
 \l_box_sin_fp
 186, 14180,
 14181, 14197, 14209, 14244, 14254
 \l_box_top_dim

 14182, 14182, 14205, 14261,
 14265, 14274, 14276, 14285, 14289,
 14294, 14300, 14310, 14319, 14332,
 14340, 14347, 14360, 14379, 14384
 \l_box_top_new_dim

 14186, 14186, 14231, 14262, 14273,
 14284, 14295, 14331, 14383, 14402
 \l_cctab_internal_tl

 14061, 14075, 14076, 14077, 14099
 \l_clist_internal_clist

 5787, 5787, 5869,
 5870, 5882, 5883, 6029, 6030, 6093,
 6094, 6110, 6111, 6157, 6158, 8197
 \l_clist_internal_remove_clist

 5973, 5973, 5980, 5983, 5984, 5986
 \l_coffin_aligned_coffin

 6914, 6916, 7138,
 7139, 7143, 7149, 7151, 7152, 7168,
 7169, 7175, 7176, 7177, 7178, 7179,
 7181, 7183, 7187, 7188, 7193, 7194,
 7195, 7196, 7197, 7231, 7246, 7292,
 7293, 7498, 7505, 7507, 7509, 7511
 \l_coffin_aligned_internal_coffin

 6914, 6917, 7210, 7217
 \l_coffin_bottom_corner_dim

 14605, 14607, 14627, 14631,
 14700, 14711, 14712, 14732, 14740
 \l_coffin_bounding_prop

 14603, 14603, 14618, 14643,
 14645, 14648, 14650, 14656, 14719

\l_coffin_bounding_shift_dim
 14604, 14625, 14718, 14724, 14725
\l_coffin_cos_fp

 14601, 14602, 14612, 14683, 14692
\l_coffin_display_coffin

 7296, 7296, 7424, 7430,
 7500, 7501, 7506, 7508, 7510, 7511
\l_coffin_display_coord_coffin

 7296, 7297,
 7362, 7382, 7398, 7445, 7465, 7484
\l_coffin_display_font_tl

 7341, 7341, 7343, 7346, 7370, 7453
\l_coffin_display_handles_prop
 7299, 7299, 7300, 7302, 7304, 7306,
 7308, 7310, 7312, 7314, 7316, 7318,
 7320, 7322, 7324, 7326, 7328, 7330,
 7332, 7334, 7373, 7377, 7456, 7460
\l_coffin_display_offset_dim
 7336, 7336, 7337, 7399, 7400, 7485, 7486
\l_coffin_display_pole_coffin

 7296, 7298, 7350, 7361, 7405, 7443
\l_coffin_display_poles_prop

 7340, 7340,
 7415, 7420, 7423, 7425, 7427, 7434
\l_coffin_display_x_dim

 7338, 7338, 7440, 7495
\l_coffin_display_y_dim

 7338, 7339, 7441, 7497
\l_coffin_error_bool
 6755, 6755, 7033,
 7037, 7051, 7066, 7097, 7436, 7438
\l_coffin_internal_box
 6733, 6733,
 6842, 6846, 6850, 6889, 6894, 6899
\l_coffin_internal_dim

 6733, 6734, 7144, 7146, 7147,
 14647, 14649, 14651, 14779, 14782
\l_coffin_internal_tl

 6733, 6735, 6742, 6743,
 6744, 6745, 6746, 6747, 6748, 6749,
 6750, 6751, 6752, 7229, 7230, 7232,
 7374, 7375, 7378, 7379, 7387, 7392,
 7457, 7458, 7461, 7462, 7471, 7476
\l_coffin_left_corner_dim

 14605, 14605, 14626, 14634,
 14701, 14707, 14708, 14731, 14739
\l_coffin_offset_x_dim

 6756, 6756, 7141,
 7142, 7145, 7153, 7155, 7157, 7163,
 7166, 7186, 7206, 7214, 7494, 7502
\l_coffin_offset_y_dim

 6756, 6757, 7156, 7158, 7163,
 7166, 7186, 7208, 7215, 7496, 7503
\l_coffin_pole_a_tl

 6758, 6758, 7031, 7036, 7255,
 7258, 7259, 7262, 7417, 7419, 7422
\l_coffin_pole_b_tl

 6758, 6759, 7032, 7036, 7256, 7258,
 7260, 7262, 7418, 7419, 7421, 7422
\l_coffin_right_corner_dim
 14605,
 14606, 14634, 14699, 14709, 14710
\l_coffin_scale_x_fp

 14744, 14744, 14750,
 14766, 14776, 14778, 14784, 14792
\l_coffin_scale_y_fp

 14744, 14745,
 14752, 14777, 14778, 14782, 14794
\l_coffin_scaled_total_height_dim

 14746, 14746, 14781, 14786
\l_coffin_scaled_width_dim

 14746, 14747, 14783, 14786
\l_coffin_sin_fp

 14601, 14601, 14611, 14684, 14691
\l_coffin_slope_x_fp

 6753, 6753, 7091, 7096, 7104, 7110
\l_coffin_slope_y_fp

 6753, 6754, 7093, 7096, 7105, 7110
\l_coffin_top_corner_dim
 14605,
 14608, 14631, 14698, 14713, 14714
\l_coffin_x_dim

 6760, 6760, 7040, 7049, 7069,
 7072, 7079, 7086, 7088, 7099, 7114,
 7203, 7207, 7226, 7234, 7440, 7492,
 14655, 14657, 14661, 14663, 14667,
 14672, 14798, 14800, 14804, 14807
\l_coffin_x_prime_dim
 6760, 6762,
 7203, 7207, 7492, 7495, 14669, 14673
\l_coffin_y_dim

 6760, 6761,
 7041, 7054, 7057, 7064, 7081, 7115,
 7204, 7209, 7227, 7234, 7441, 7493,
 14655, 14657, 14661, 14663, 14667,
 14672, 14798, 14800, 14804, 14807
\l_coffin_y_prime_dim
 6760, 6763,
 7204, 7209, 7493, 7497, 14669, 14674
\l_exp_internal_tl
 33, 845, 845,
 849, 850, 1614, 1633, 1634, 1809, 1810
\l_expl_status_stack_tl
 204
\l_file_internal_name_ior
 162
\l_file_internal_name_tl

 162, 9074, 9074,
 9087, 9088, 9089, 9090, 9093, 9094,
 9099, 9140, 9141, 9147, 9148, 9153,
 9260, 9261, 9263, 9269, 9270, 9273

\l_file_internal_seq
 9079, 9080,
 9119, 9121, 9194, 9200, 9205, 9207
\l_file_internal_t1 9073, 9073, 9176, 9177
\l_file_saved_search_path_seq
 9076, 9077, 9118, 9135
\l_file_search_path_seq
 9075, 9075, 9118, 9120,
 9121, 9124, 9135, 9184, 9185, 9190
\l_fp_division_by_zero_flag_token
 10023, 10024
\l_fp_invalid_operation_flag_token
 10023, 10023
\l_fp_overflow_flag_token 10023, 10025
\l_fp_underflow_flag_token 10023, 10026
\l_ior_internal_t1
 14831, 14850, 14853, 14857
\l_ior_stream_int
 9242, 9242, 9283, 9285, 9289,
 9298, 9305, 9309, 9312, 9314, 9318,
 9321, 9326, 9327, 9329, 9331, 9400
\l_iow_current_indentation_int
 9507, 9509,
 9570, 9612, 9627, 9649, 9655, 9657
\l_iow_current_indentation_t1 9510,
 9512, 9571, 9610, 9630, 9650, 9656
\l_iow_current_line_int
 9507, 9507, 9572,
 9598, 9599, 9611, 9617, 9624, 9643
\l_iow_current_line_t1
 9510, 9510, 9573, 9609,
 9615, 9623, 9629, 9642, 9644, 9662
\l_iow_current_word_int
 9507, 9508, 9596, 9598, 9626
\l_iow_current_word_t1 . 9510, 9511,
 9589, 9590, 9597, 9610, 9616, 9630
\l_iow_line_start_bool
 9515, 9515, 9574, 9606, 9608, 9645
\l_iow_newline_t1 9514, 9514,
 9565, 9566, 9567, 9569, 9623, 9642
\l_iow_stream_int
 9400, 9400, 9418, 9420,
 9424, 9432, 9439, 9443, 9446, 9448,
 9452, 9455, 9460, 9461, 9463, 9465
\l_iow_target_count_int
 9506, 9506, 9568, 9599
\l_iow_wrap_t1 9513, 9513, 9560, 9563,
 9577, 9579, 9585, 9622, 9641, 9661
\l_kernel_expl_bool
 7, 138, 249, 264, 278, 282, 283
\l_keys_module_t1
 8508, 8508, 8515, 8518, 8520,
 8545, 8702, 8707, 8852, 8855, 8857,
 8862, 8865, 8870, 8888, 8938, 8941
\l_keys_no_value_bool
 8509, 8509, 8525, 8530, 8562,
 8877, 8882, 8893, 8903, 8915, 8950
\l_keys_property_t1 8511, 8511, 8536,
 8540, 8558, 8565, 8566, 8569, 8573
\l_keys_unknown_clist
 8512, 8512, 8866, 8871, 8947
\l_msg_class_loop_seq 7883, 7883,
 7973, 7981, 7990, 7991, 7994, 7996
\l_msg_class_t1
 7879, 7895, 7907, 7928, 7932,
 7935, 7943, 7982, 7984, 7986, 7999
\l_msg_current_class_t1
 7879, 7880, 7890,
 7927, 7932, 7935, 7943, 7972, 7986
\l_msg_hierarchy_seq
 7882, 7882, 7910, 7920, 7925
\l_msg_internal_t1
 7592, 7592, 8302, 8303, 8305
\l_msg_redirect_prop
 7881, 7881, 7907, 7952, 7955
\l_peek_search_t1
 3066, 3066, 3084, 3105, 3148
\l_peek_search_token
 3065, 3065, 3083, 3104, 3123, 3131
\l_prop_internal_t1 6453, 6456, 6457
\l_seq_internal_a_t1
 5381, 5381, 5411, 5417,
 5422, 5423, 5499, 5504, 5518, 5522
\l_seq_internal_b_t1
 5381, 5382, 5495, 5499, 5521, 5522
\l_seq_remove_seq
 5467, 5467, 5474, 5477, 5478, 5480
\l_t1_internal_a_t1 4886, 4889, 4891, 4899
\l_t1_internal_b_t1 4886, 4890, 4891, 4900
\l_char_active_seq
 52, 2711, 2711, 2724, 9085
\l_char_special_seq . 52, 2711, 2728, 2729
\l_iow_line_count_int
 161, 9504, 9504, 9505, 9569, 9711
\l_iow_line_length_int 9711, 9711
\l_keys_choice_int 152, 8505, 8505,
 8620, 8623, 8627, 8628, 8639, 8649,
 8653, 8654, 8724, 8727, 8731, 8732
\l_keys_choice_t1
 152, 8505, 8506, 8626, 8652, 8730

\l_keys_key_tl	154, 8507, 8507, 8588, 8603, 8887, 8888, 8949	\lccode	637
\l_keys_path_tl	154, 8510, 8510, 8540, 8545, 8552, 8555, 8570, 8581, 8583, 8585, 8596, 8598, 8600, 8609, 8611, 8614, 8624, 8636, 8644, 8650, 8656, 8662, 8665, 8667, 8689, 8694, 8701, 8706, 8713, 8715, 8718, 8728, 8740, 8746, 8766, 8768, 8888, 8897, 8907, 8917, 8919, 8922, 8930, 8935, 8941, 8965, 8966	\leaders	505
\l_keys_value_tl	154, 8513, 8513, 8907, 8914, 8921, 8951, 8959	\left	473
\l_last_box	6722, 6723	\lefthyphenmin	529
\l_peek_token	57, 3063, 3063, 3072, 3123, 3131, 3141, 3142, 3143, 3162, 15197, 15198, 15199	\leftskip	531
\l_tmpa_bool	37, 2132, 2132	\leqno	448
\l_tmpa_box	127, 6595, 6596, 6599	\let	60, 70, 305, 306, 318
\l_tmpa_clist	117, 6161, 6161	\limits	465
\l_tmpa_coffin	135, 6918, 6918	\linepenalty	521
\l_tmpa_dim	79, 4385, 4385	\lineskip	515
\l_tmpa_fp	170, 13878, 13878	\lineskiplimit	516
\l_tmpa_int	71, 4088, 4088	\linewidth	6832, 6878
\l_tmpa_muskip	85, 4549, 4549	\ln	13150, 13153
\l_tmpa_prop	123, 6222, 6222	\long	34, 308, 337
\l_tmpa_seq	108, 5762, 5762	\looseness	533
\l_tmpa_skip	82, 4481, 4481	\lower	570
\l_tmpa_tl	5, 99, 5302, 5302	\lowercase	609
\l_tmpb_bool	37, 2132, 2133	\lua_now:n	181, 14000, 14018, 14020
\l_tmpb_box	127, 6595, 6601	\lua_now:x	14000
\l_tmpb_clist	117, 6161, 6162	\lua_now_x:n	181, 4639, 14000, 14002, 14006, 14009, 14017, 14019
\l_tmpb_coffin	135, 6918, 6919	\lua_now_x:x	14000
\l_tmpb_dim	79, 4385, 4386	\lua_shipout:n	181, 14000, 14022, 14024
\l_tmpb_fp	170, 13878, 13879	\lua_shipout:x	14000
\l_tmpb_int	71, 4088, 4089	\lua_shipout_x:n	182, 14000, 14003, 14011, 14014, 14021, 14023
\l_tmpb_muskip	85, 4549, 4550	\lua_shipout_x:x	14000
\l_tmpb_prop	123, 6222, 6223	\luaescapestring	40, 41
\l_tmpb_seq	108, 5762, 5763	\luatex_catcodetable:D
\l_tmpb_skip	82, 4481, 4482	727, 742, 14063, 14064, 14069, 14077	
\l_tmpb_tl	99, 5302, 5303	\luatex_directlua:D	728, 1489, 14002
\l_tmpc_int	4137, 4137	\luatex_if_engine:F	
\language	418	1467, 1492, 14042, 14079, 14107	
\lastbox	575	\luatex_if_engine:T	1466, 1491, 4634, 14051, 14093, 14115, 14121, 14130
\lastkern	508	\luatex_if_engine:TF	
\lastlinefit	688	22, 1466, 1468, 1493, 14000	
\lastnodetype	669	\luatex_if_engine_p:	
\lastpenalty	614	22, 1466, 1475, 1497, 1588	
\lastskip	509	\luatex_initcatcodetable:D	
\latelua	730	729, 743, 14038, 14057	
		\luatex_latelua:D	730, 744, 14003
		\luatex_luatexversion:D	731, 812
		\luatex_savecatcodetable:D	
		732, 745, 14068, 14104	
		\luatexcatcodetable	742
		\luatexinitcatcodetable	743
		\luatexlatelua	744
		\luatexsavecatcodetable	745
		\luatexversion	731

M		
\M	1879, 2805	\moveleft 571 \moveright 572
cm	177	\msg_class_new:nn 8322, 8323
em	177	\msg_class_set:nn 8323, 8365, 8365
mm	177	\msg_critical:nn 7818
\m@ne	801	\msg_critical:nnn 7818
\mag	417	\msg_critical:nnnn 7818
\mark	419	\msg_critical:nnnnn 7818
\marks	645	\msg_critical:nnnnnn 140, 7818
\mathaccent	430	\msg_critical:nnx 7818
\mathbin	460	\msg_critical:nnxx 7818
\mathchar	431, 2871	\msg_critical:nnxxx 7818
\mathchardef	328	\msg_critical:nnxxxx 7818
\mathchoice	428	\msg_critical_text:n 138, 7758, 7759, 7821
\mathclose	461	\msg_direct_interrupt:xxxxx 8332, 8337
\mathcode	639	\msg_direct_log:xx 8332, 8338
\mathinner	462	\msg_direct_term:xx 8332, 8339
\mathop	463	\msg_error:nn 7829
\mathopen	467	\msg_error:nnn 7829
\mathord	468	\msg_error:nnnn 7829
\mathparagraph	4113	\msg_error:nnnnn 7829
\mathpunct	469	\msg_error:nnnnnn 140, 7829
\mathrel	470	\msg_error:nnx 7829
\mathsection	4112	\msg_error:nnxx 7829
\mathsurround	481	\msg_error:nnxxx 7829
\maxdeadcycles	551	\msg_error:nnxxxx 7829
\maxdepth	552	\msg_error_text:n 138, 7758, 7760, 7836
\maxdimen	4383	\msg_fatal:nn 7807
\meaning	611	\msg_fatal:nnn 7807
\medmuskip	482	\msg_fatal:nnnn 7807
\message	388	\msg_fatal:nnnnn 7807
\MessageBreak	77, 78, 79, 80, 81, 82, 83, 84, 148, 229	\msg_fatal:nnnnnn 139, 7807 \msg_fatal:nnx 7807
.meta:n	150	\msg_fatal:nnxx 7807
.meta:x	150	\msg_fatal:nnxxx 7807
\middle	693	\msg_fatal:nnxxxx 7807
\mkern	435	\msg_fatal:nnxxxxx 7807
\mode_if_horizontal:	2317	\msg_generic_new:nn 8332, 8334
\mode_if_horizontal:TF	40, 2317	\msg_generic_new:nnn 8332, 8333
\mode_if_horizontal_p:	40, 2317	\msg_generic_set:nn 8332, 8336
\mode_if_inner:	2319	\msg_generic_set:nnn 8332, 8335
\mode_if_inner:TF	40, 2319	\msg_gset:nnn 7621, 7644
\mode_if_inner_p:	40, 2319	\msg_gset:nnnn 138, 7621, 7624, 7637, 7645
\mode_if_math:	2321	\msg_if_exist:nn 7595
\mode_if_math:TF	40, 2321, 4101	\msg_if_exist:nnT 7602, 7612
\mode_if_math_p:	40, 2321	\msg_if_exist:nnTF 138, 7595, 7886
\mode_if_vertical:	2315	\msg_if_exist_p:nn 138, 7595
\mode_if_vertical:TF	40, 2315	\msg_info:nn 7858
\mode_if_vertical_p:	40, 2315	\msg_info:nnn 7858
\month	621	\msg_info:nnnn 7858

\msg_info:nnnnn	7858	\msg_trace:nnxxxx	8325, 8326
\msg_info:nnnnnn	140, 7858	\msg_two_newlines:	8360, 8361
\msg_info:nnx	7858	\msg_warning:nn	7850
\msg_info:nnxx	7858	\msg_warning:nnn	7850
\msg_info:nnxxx	7858	\msg_warning:nnnn	7850
\msg_info:nnxxxx	7858, 8057	\msg_warning:nnnnn	7850
\msg_info_text:n	139, 7758, 7762, 7862	\msg_warning:nnnnnn	140, 7850
\msg_interrupt:nnn	142, 7685,	\msg_warning:nnx	7850
7685, 7809, 7820, 7835, 8344, 8364		\msg_warning:nnxx	7850
\msg_interrupt:xxx	8362	\msg_warning:nnxxx	7850
\msg_line_context:	138, 1179, 1179, 1198, 7617, 7678, 7679	\msg_warning:nnxxxx	7850, 8056
\msg_line_number:	138, 7678, 7678, 7683, 8494	\msg_warning_text:n	139, 7758, 7761, 7854
\msg_log:n	143, 7743, 7743, 7860, 8362	\mskip	432
\msg_log:nn	7866, 8330	\muexpr	681
\msg_log:nnn	7866	.multichoice:	150
\msg_log:nnnn	7866	.multichoices:nn	150
\msg_log:nnnnn	7866	\multiply	333
\msg_log:nnnnnn	140, 7866	\muskip	629
\msg_log:nnnnnn	7866, 8329	\muskip_add:cn	4529
\msg_log:nnnx	7866, 8328	\muskip_add:Nn	84, 4529, 4529, 4531, 4532
\msg_log:nnxx	7866, 8327	\muskip_const:cn	4493
\msg_log:nnxxx	7866, 8326	\muskip_const:Nn	
\msg_log:x	8362	83, 4493, 4493, 4498, 4547, 4548	
\msg_new:nnn	7621, 7626, 8008	\muskip_eval:n	84, 4539, 4539
\msg_new:nnnn	137, 7621, 7621, 7627, 8006	\muskip_gadd:cn	4529
\msg_newline:	8360, 8360	\muskip_gadd:Nn	84, 4529, 4531, 4533
\msg_none:nn	7872	\muskip_gset:cn	4518
\msg_none:nnn	7872	\muskip_gset:Nn	84, 4496, 4518, 4520, 4522
\msg_none:nnnn	7872	\muskip_gset_eq:cc	4523
\msg_none:nnnnn	7872	\muskip_gset_eq:cN	4523
\msg_none:nnnnnn	141, 7872	\muskip_gset_eq:Nc	4523
\msg_none:nnx	7872	\muskip_gset_eq:NN	
\msg_none:nnxx	7872	84, 4523, 4526, 4527, 4528	
\msg_none:nnxxx	7872	\muskip_gsub:cn	4529
\msg_none:nnxxxx	7872	\muskip_gsub:Nn	84, 4529, 4536, 4538
\msg_redirect_class:nn	141, 7958, 7958	\muskip_gzero:c	4499
\msg_redirect_module:nnn	142, 7958, 7960	\muskip_gzero:N	83, 4499, 4501, 4503, 4507
\msg_redirect_name:nnn	142, 7949, 7949	\muskip_gzero_new:c	4504
\msg_see_documentation_text:n	139, 7763, 7763, 7813, 7824, 7839, 8347	\muskip_gzero_new:N	83, 4504, 4506, 4509
\msg_set:nnn	7621, 7635, 8012	\muskip_if_exist:cF	4516
\msg_set:nnnn	138, 7621, 7628, 7636, 8010	\muskip_if_exist:cT	4515
\msg_term:n	143, 7743, 7749, 7852, 8363	\muskip_if_exist:cTF	4510, 4514
\msg_term:x	8362	\muskip_if_exist:NF	4512
\msg_trace:nn	8325, 8330	\muskip_if_exist:NT	4511
\msg_trace:nnx	8325, 8329	\muskip_if_exist:NTF	
\msg_trace:nnxx	8325, 8328	83, 4505, 4507, 4510, 4510	
\msg_trace:nnxxx	8325, 8327	\muskip_if_exist_p:c	4510, 4517
		\muskip_if_exist_p:N	83, 4510, 4513
		\muskip_new:c	4485

\muskip_new:N	83, 4485, 4486, 4492, 4495,	\number	606
4505, 4507, 4549, 4550, 4551, 4552		\numexpr	678
\muskip_set:cn	4518		
\muskip_set:Nn	84, 4518, 4518, 4520, 4521	O	
\muskip_set_eq:cc	4523	\omit	352
\muskip_set_eq:cN	4523	\openin	378
\muskip_set_eq:Nc	4523	\openout	379
\muskip_set_eq>NN	84, 4523, 4523, 4524, 4525	\or	375
\muskip_show:c	4543	\or:	23, 72, 754, 756, 1290, 1291, 1292,
\muskip_show:N	85, 4543, 4543, 4544	1293, 1294, 1295, 1296, 1297, 1298,	
\muskip_show:n	85, 4545, 4545	1595, 3844, 3845, 3846, 3847, 3848,	
\muskip_sub:cn	4529	3849, 3850, 3851, 3852, 3853, 3854,	
\muskip_sub:Nn	84, 4529, 4534, 4536, 4537	3855, 3856, 3857, 3858, 3859, 3860,	
\muskip_use:c	4541	3861, 3862, 3863, 3864, 3865, 3866,	
\muskip_use:N	84, 4540, 4541, 4541, 4542	3867, 3868, 9796, 9797, 9798, 9948,	
\muskip_zero:c	4499	11110, 11295, 11296, 11297, 11334,	
\muskip_zero:N	83, 4499, 4499, 4501, 4502, 4505	11335, 11750, 11751, 11752, 11880,	
\muskip_zero_new:c	4504	11964, 12050, 12051, 12052, 12053,	
\muskip_zero_new:N	83, 4504, 4504, 4508	12054, 12055, 12056, 12057, 12058,	
\muskipdef	327	12135, 12138, 12629, 12654, 12660,	
\mutoglue	687	12661, 12662, 12663, 12664, 12811,	
\my_map dbl:nn	1	12846, 12848, 12856, 12946, 12950,	
		12951, 12952, 12953, 12954, 12955,	
		12956, 12957, 12958, 12959, 12966,	
		12967, 12968, 12969, 12970, 12971,	
		12972, 12973, 12974, 12975, 12982,	
N		12983, 12984, 12985, 12986, 12987,	
\N	2028	12988, 12989, 12990, 12991, 12998,	
in	177	12999, 13000, 13001, 13002, 13003,	
ln	175	13004, 13005, 13006, 13007, 13014,	
\newbox	6499	13015, 13016, 13017, 13018, 13019,	
\newcatcodetable	14056	13020, 13021, 13022, 13023, 13030,	
\newcount	3448	13031, 13032, 13033, 13034, 13035,	
\newdimen	4156	13036, 13037, 13038, 13039, 13057,	
\newlinechar	90, 383	13103, 13106, 13115, 13226, 13241,	
\newmuskip	4489	13288, 13294, 13303, 13309, 13318,	
\newread	9249	13324, 13333, 13339, 13348, 13354,	
\newskip	4393	13363, 13369, 13601, 13602, 13613,	
\newwrite	9407	13651, 13652, 13662, 13719, 13720	
inf	176	cos	176
\noalign	351	cot	176
\noboundary	486	round	176
\noexpand	36, 40, 41, 173,	round+	176
	176, 179, 181, 182, 191, 194, 195,	round-	176
	196, 198, 200, 201, 210, 212, 213,	round0	176
	214, 215, 216, 287, 289, 294, 296, 344	\outer	338
\noindent	512	\output	553
\nolimits	466	\outputpenalty	563
\nonscript	446	\over	440
\nonstopmode	409	\overfullrule	591
\nulldelimiterspace	479		
\nullfont	597		

\overline	471	\pdftex_if_engine_p:
\overwithdelims	441	22, 1466, 1476, 1486, 1498, 1589
		\pdftex_pdfcolorstack:D
		707
		\pdftex_pdfcompresslevel:D
		708
		\pdftex_pdfcreationdate:D
		706
		\pdftex_pdfdecimaldigits:D
		709
		\pdftex_pdfhorigin:D
		710
		\pdftex_pdfinfo:D
		711
		\pdftex_pdflastxform:D
		712
		\pdftex_pdfliteral:D
		713
		\pdftex_pdfminorversion:D
		714
		\pdftex_pdfobjcompresslevel:D
		715
		\pdftex_pdfoutput:D
		716
		\pdftex_pdpkresolution:D
		721
		\pdftex_pdfsavexform:D
		717
		\pdftex_pdfrestore:D
		718
		\pdftex_pdfsavematrix:D
		719
		\pdftex_pdtextrerevision:D
		720
		\pdftex_pfdvorigin:D
		723
		\pdftex_pfdxftransform:D
		724
		\pdftex_strcmp:D
		725, 1503, 1509,
		1514, 2496, 2503, 2520, 2547, 2556,
		2820, 4445, 10784, 10797, 10953, 13095
		\pdftexrevision
		722
		\pdfvorigin
		723
		\pdfxftransform
		724
		\peek_after>NN
		3292, 3293
		\peek_afterNw
		57, 3071, 3071, 3096, 3114, 3170, 3293
		\peek_catcodeNTF
		57, 3188
		\peek_catcode_ignore_spacesNTF .
		57, 3188
		\peek_catcode_removeNTF
		58, 3188
		\peek_catcode_remove_ignore_spacesNTF .
		58, 3188
		\peek_charcodeNTF
		58, 3204
		\peek_charcode_ignore_spacesNTF .
		58, 3204
		\peek_charcode_removeNTF
		58, 3204
		\peek_charcode_remove_ignore_spacesNTF .
		58, 3204
		\peek_gafterNN
		3292, 3294
		\peek_gafterNw
		57, 3071, 3073, 3294
		\peek_meaningNTF
		59, 3220
		\peek_meaning_ignore_spacesNTF .
		59, 3220
		\peek_meaning_removeNTF
		59, 3220
		\peek_meaning_remove_ignore_spacesNTF .
		59, 3220
		\peek_N_typeF
		15208
		\peek_N_typeT
		15206

\peek_N_type:TF 195, 15193, 15204
 \penalty 612
 \postdisplaypenalty 459
 \predisplaydirection 703
 \predisplaypenalty 458
 \predisplaysize 457
 \pretolerance 538
 \prevdepth 585
 \prevgraf 544
 \prg_break: 2586, 2588
 \prg_case_dim:nnn 4555, 4555
 \prg_case_int:nnn 2457, 2457
 \prg_case_str:nnn 2457, 2458
 \prg_case_str:onn 2457, 2459
 \prg_case_str:xxn 2457, 2460
 \prg_case_tl:cnn 2457, 2462
 \prg_case_tl:Nnn 2457, 2461
 \prg_define_quicksort:nnn 2363, 2364, 2447
 \prg_do_nothing:
 ... 9, 995, 996, 1459, 1500, 1500,
 1553, 1948, 1953, 4734, 4748, 4808,
 4813, 5413, 5420, 5627, 5629, 5917,
 9990, 10042, 10076, 10102, 10110,
 11304, 13912, 14508, 14512, 14519
 \prg_new_conditional:Nnn 898,
 900, 2075, 2525, 2533, 2545, 2554, 9363
 \prg_new_conditional:Npnn
 ... 34, 885, 887, 1419, 1501,
 1507, 2075, 2104, 2144, 2315, 2317,
 2319, 2321, 2731, 2736, 2741, 2746,
 2753, 2759, 2764, 2769, 2774, 2779,
 2784, 2789, 2794, 2799, 2813, 2827,
 2832, 2855, 2864, 2874, 2892, 2916,
 2934, 2952, 2970, 2982, 2991, 3011,
 3550, 3584, 3606, 3614, 4240, 4245,
 4442, 4454, 4553, 4829, 4839, 4851,
 4872, 4874, 4920, 5182, 5201, 5220,
 5255, 5261, 5276, 5359, 6353, 6365,
 6565, 6567, 6577, 6764, 7595, 8927,
 8968, 8974, 10015, 10780, 11448,
 11461, 13886, 13893, 14560, 15055
 \prg_new_eq_conditional:NNn ... 36,
 986, 988, 2075, 5361, 5363, 5365,
 5510, 5512, 5750, 5751, 5752, 5753,
 5754, 5755, 6021, 6022, 6183, 6184,
 6185, 6186, 6474, 6475, 6476, 6477
 \prg_new_map_functions:Nn ... 2453, 2454
 \prg_new_protected_conditional:Nnn .
 ... 898, 904, 2075
 ... 34, 885, 891, 2075, 4886,
 4907, 5514, 5626, 5628, 5636, 5638,
 5640, 5642, 5926, 5938, 5940, 6023,
 6027, 6279, 6285, 6396, 9138, 9265
 \prg_quicksort:n 2446
 \prg_quicksort_compare:nnTF . 2449, 2451
 \prg_quicksort_function:n ... 2449, 2450
 \prg_replicate:nn 40, 2271,
 2271, 8189, 9657, 13202, 13253,
 13260, 13423, 13658, 13685, 13693
 \prg_return_false: ... 36, 881, 883, 1090,
 1095, 1113, 1121, 1138, 1422,
 1505, 1510, 1517, 2075, 2109, 2149,
 2316, 2318, 2320, 2322, 2530, 2538,
 2551, 2560, 2734, 2739, 2744, 2749,
 2756, 2762, 2767, 2772, 2777, 2782,
 2787, 2792, 2797, 2802, 2823, 2830,
 2835, 2840, 2877, 2880, 2899, 2902,
 2919, 2922, 2937, 2940, 2955, 2958,
 3014, 3033, 3050, 3059, 3544, 3548,
 3556, 3589, 3611, 3617, 4243, 4251,
 4449, 4457, 4554, 4844, 4856, 4869,
 4879, 4896, 4911, 5194, 5217, 5233,
 5241, 5251, 5271, 5285, 5528, 5551,
 5929, 5945, 6037, 6283, 6289, 6358,
 6384, 6400, 6566, 6568, 6578, 6770,
 6772, 7598, 8932, 8972, 8978, 9142,
 9271, 9373, 10020, 10793, 10805,
 11456, 11469, 13891, 13896, 14563
 \prg_return_true: ... 36, 881, 881,
 1093, 1110, 1118, 1123, 1136, 1141,
 1422, 1505, 1510, 1515, 2075, 2107,
 2147, 2316, 2318, 2320, 2322, 2528,
 2536, 2549, 2558, 2734, 2739, 2744,
 2749, 2756, 2762, 2767, 2772, 2777,
 2782, 2787, 2792, 2797, 2802, 2821,
 2830, 2838, 2894, 2896, 3031, 3057,
 3544, 3554, 3587, 3609, 3619, 4243,
 4249, 4447, 4458, 4554, 4842, 4854,
 4867, 4877, 4893, 4911, 5192, 5215,
 5231, 5249, 5273, 5284, 5532, 5554,
 5932, 5948, 6037, 6295, 6356, 6382,
 6405, 6566, 6568, 6578, 6769, 7598,
 8931, 8971, 8977, 9143, 9274, 9368,
 9371, 9377, 10018, 10788, 10811,
 11458, 11467, 13891, 13896, 14564
 \prg_set_conditional:Nnn . 898, 898, 2075
 \prg_set_conditional:Npnn 34,
 885, 885, 1087, 1099, 1115, 1127, 2075

\prg_set_eq_conditional:NNn	36, 986, 986, 2075	\prop_gget:cVN	6452
\prg_set_map_functions:Nn	2453, 2455	\prop_gget:NnN	6452, 6454, 6459, 6460
\prg_set_protected_conditional:Nnn	898, 902, 2075	\prop_gget:NVN	6452
\prg_set_protected_conditional:Npnn	34, 885, 889, 2075	\prop_gget_aux:Nnnn	6452
\prg_stepwise_function:nnnN	2463, 2463	\prop_gpop:cnN	6258
\prg_stepwise_inline:nnnn	2463, 2464	\prop_gpop:cnNTF	6279
\prg_stepwise_variable:nnnNn	2463, 2465	\prop_gpop:coN	6258
\prop_clear:c	6204, 7150	\prop_gpop:NnN	6463
\prop_clear:N	118, 6204, 6204, 6205, 6209	119, 6258, 6264, 6277, 6278, 6285, 6463	
\prop_clear_new:c	6208, 6799, 6800, 8371	\prop_gpop:NnNF	6301
\prop_clear_new:N	118, 6208, 6208, 6210	\prop_gpop:NnNT	6300
\prop_del:cn	6479, 6481	\prop_gpop:NnNTF	121, 6279, 6302
\prop_del:cV	6479, 6482	\prop_gpop:NoN	6258
\prop_del:Nn	6479, 6479	\prop_gput:ccx	6470
\prop_del:NV	6479, 6480	\prop_gput:cnn	6303
\prop_display:c	6448, 6450	\prop_gput:cno	6303
\prop_display:N	6448, 6449	\prop_gput:coo	6303
\prop_gclear:c	6204	\prop_gput:cVn	6303
\prop_gclear:N	118, 6204, 6206, 6207, 6212	\prop_gput:cVV	6303
\prop_gclear_new:c	6208	\prop_gput:Nnn	6471
\prop_gclear_new:N	118, 6208, 6211, 6213	119, 6303, 6305, 6326, 6328, 6471	
\prop_gdel:cn	6479, 6485	\prop_gput:Nno	6303
\prop_gdel:cV	6479, 6486	\prop_gput:NnV	6303
\prop_gdel:Nn	6479, 6483	\prop_gput:Nnx	6303
\prop_gdel:NV	6479, 6484	\prop_gput:Non	6303
\prop_get:cn	14879	\prop_gput:Noo	6303
\prop_get:cNn	6248	\prop_gput:NVn	6303, 9289, 9424
\prop_get:cNf	6928	\prop_gput:NVv	6303
\prop_get:cNt	7982	\prop_gput_if_new:cnn	6330
\prop_get:cNtf	6396, 7927	\prop_gput_if_new:Nnn	119, 6330, 6332, 6344
\prop_get:coN	6248	\prop_gremove:cn	6238, 6485
\prop_get:coNtf	6396	\prop_gremove:cV	6238, 6486
\prop_get:cVn	6248	\prop_gremove:Nn	
\prop_get:cVntf	6396	120, 6238, 6240, 6246, 6247, 6483	
\prop_get:Nn	191, 14879, 14879, 14892	\prop_gremove:NV	6238, 6484, 9346, 9480
\prop_get:Nnn	119, 6248, 6248, 6256, 6257,	\prop_gset_eq:cc	6214, 6221, 6952, 6954
6396, 6456, 7373, 7377, 7456, 7460		\prop_gset_eq:cN	6214, 6219
\prop_get:NnNF	6408, 6411	\prop_gset_eq:NN	118, 6214, 6218
\prop_get:NnNT	6407, 6410	\prop_if_empty:cTF	6353
\prop_get:NnNTf	121, 6396, 6409, 6412, 7907	\prop_if_empty:N	6353
\prop_get:NoN	6248	\prop_if_empty:Nf	6364
\prop_get:NoNtf	6396	\prop_if_empty:NT	6363
\prop_get:Nvn	6248	\prop_if_empty:NTF	
\prop_get:Nvntf	6396	120, 6353, 6362, 8205, 9357	
\prop_get_gdel:Nnn	6462, 6463	\prop_if_empty_p:c	6353
\prop_gget:cNn	6452	\prop_if_empty_p:N	120, 6353, 6361

\prop_if_eq:cc 6477
 \prop_if_eq:ccTF 6473
 \prop_if_eq:cN 6475
 \prop_if_eq:cNTF 6473
 \prop_if_eq:Nc 6476
 \prop_if_eq:NcTF 6473
 \prop_if_eq>NN 6474
 \prop_if_eq:NNTF 6473
 \prop_if_eq_p:cc 6473
 \prop_if_eq_p:cN 6473
 \prop_if_eq_p:Nc 6473
 \prop_if_eq_p>NN 6473
 \prop_if_exist:cF 6351
 \prop_if_exist:cT 6350
 \prop_if_exist:cTF 6345, 6349
 \prop_if_exist:NF 6347
 \prop_if_exist:NT 6346
 \prop_if_exist:NTF
 120, 6209, 6212, 6345, 6345
 \prop_if_exist_p:c 6345, 6352
 \prop_if_exist_p:N 120, 6345, 6348
 \prop_if_in:ccTF 6465
 \prop_if_in:cnTF 6365
 \prop_if_in:coTF 6365
 \prop_if_in:cVTF 6365
 \prop_if_in:Nn 6365
 \prop_if_in:NnF 6392, 6393, 6467, 9296, 9430
 \prop_if_in:NnT 6390, 6391, 6466
 \prop_if_in:NnTF 120, 6365, 6394, 6395, 6468
 \prop_if_in:NoTF 6365
 \prop_if_in:NVT 9331, 9465
 \prop_if_in:NVTF 6365
 \prop_if_in_p:cn 6365
 \prop_if_in_p:co 6365
 \prop_if_in_p:cV 6365
 \prop_if_in_p:Nn 120, 6365, 6388, 6389
 \prop_if_in_p:No 6365
 \prop_if_in_p:NV 6365
 \prop_map_break:
 122, 6417, 6421, 6435,
 6438, 6438, 6439, 6441, 14870, 14874
 \prop_map_break:n 122, 6438, 6440
 \prop_map_function:cc 6413
 \prop_map_function:cN 6413, 7519
 \prop_map_function:Nc 6413
 \prop_map_function>NN
 121, 6413, 6413, 6425, 6426, 6445, 9360
 \prop_map_inline:cn 6427, 7221,
 7240, 14613, 14615, 14635, 14637,
 14702, 14762, 14764, 14768, 14770
 \prop_map_inline:Nn
 121, 6427,
 6427, 6437, 7425, 7434, 14618, 14719
 \prop_map_tokens:cn 14866
 \prop_map_tokens:Nn
 190, 14866, 14866, 14878
 \prop_new:c 6202, 6203, 7772
 \prop_new:N 118, 6202, 6202, 6209, 6212,
 6222, 6223, 6224, 6225, 6736, 6741,
 7299, 7340, 7881, 9238, 9394, 14603
 \prop_pop:cnN 6258
 \prop_pop:cnNTF 6279
 \prop_pop:coN 6258
 \prop_pop:NnN
 119, 6258, 6258, 6275, 6276, 6279
 \prop_pop:NnNF 6298
 \prop_pop:NnNT 6297
 \prop_pop:NnNTF 121, 6279, 6299
 \prop_pop:NoN 6258
 \prop_put:cnn 6303, 6980, 7971, 7988
 \prop_put:cno 6303
 \prop_put:cnV 6303
 \prop_put:cnx
 6303, 6986, 6988, 6990, 6992, 6997,
 7002, 7007, 7014, 7021, 7245, 14662,
 14729, 14737, 14799, 14813, 14820
 \prop_put:con 6303
 \prop_put:coo 6303
 \prop_put:cVn 6303
 \prop_put:cVV 6303
 \prop_put:Nnn
 119, 6303,
 6303, 6322, 6324, 6737, 6738, 6739,
 6740, 7300, 7302, 7304, 7306, 7308,
 7310, 7312, 7314, 7316, 7318, 7320,
 7322, 7324, 7326, 7328, 7330, 7332,
 7334, 7955, 9240, 9306, 9306, 9307, 9308
 \prop_put:Nno 6303, 6743, 6744, 6745,
 6747, 6748, 6749, 6750, 6751, 6752
 \prop_put:NnV 6303
 \prop_put:Nnx
 6303,
 14643, 14645, 14648, 14650, 14656
 \prop_put:Non 6303
 \prop_put:Noo 6303
 \prop_put:NVn 6303
 \prop_put:NVV 6303
 \prop_put_if_new:cnn 6330
 \prop_put_if_new:Nnn 119, 6330, 6330, 6343
 \prop_remove:cn 6238, 6481, 7967
 \prop_remove:cV 6238, 6482
 \prop_remove:Nn
 120, 6238, 6238, 6244,
 6245, 6479, 7420, 7423, 7427, 7952

```

\prop_remove:NV ..... 6238, 6480
\prop_set_eq:cc 6214, 6217, 6945, 6947, 7180
\prop_set_eq:cN .. 6214, 6216, 6938, 6940
\prop_set_eq:Nc ..... 6214, 6215, 7415
\prop_set_eq:NN ..... 118, 6214, 6214
\prop_show:c ..... 6442, 6450
\prop_show:N .. 122, 6442, 6442, 6447, 6449
\protected ... 110, 124, 140, 152, 159,
              164, 220, 247, 280, 285, 292, 705, 2999
\protected@edef ..... 9563
\ProvidesClass ..... 161
\ProvidesExplClass ..... 6, 139, 159
\ProvidesExplFile ..... 6, 139, 164
\ProvidesExplPackage ..... 6,
                         139, 140, 152, 157, 302, 750, 1610,
                         2069, 2469, 2593, 3365, 4145, 4576,
                         5372, 5782, 6196, 6491, 6729, 7555,
                         7588, 8386, 9049, 9734, 13996, 14174
\ProvidesFile ..... 166
\ProvidesPackage ..... 48, 154

Q
\q__tl_act_mark ..... 5065, 5068, 5085
\q__tl_act_stop 5065, 5068, 5072, 5081,
                  5083, 5089, 5094, 5097, 5101, 5104
\q_prop ..... 123, 6200, 6200,
             6201, 6231, 6232, 6234, 6311, 6318,
             6340, 6369, 6370, 6373, 6381, 6416,
             6419, 6434, 14869, 14872, 14883, 14886
\q__tl_act_mark ..... 2567, 2567
\q__tl_act_stop ..... 2567, 2568
\q_mark ..... 44,
             1074, 1075, 1078, 1079, 1080, 1892,
             1893, 1895, 1899, 1902, 1927, 1936,
             1950, 1958, 1961, 1970, 1985, 2007,
             2035, 2038, 2046, 2156, 2157, 2158,
             2159, 2162, 2163, 2164, 2165, 2166,
             2167, 2168, 2474, 2475, 3562, 3565,
             4259, 4262, 4791, 4800, 4804, 4815,
             5006, 5007, 5010, 5013, 5014, 5020,
             5034, 5035, 5041, 5045, 5047, 5050,
             5840, 5849, 5854, 5909, 5919, 5923,
             5947, 5999, 6005, 6018, 6067, 6075,
             6231, 6233, 6234, 7912, 7913, 7918,
             7921, 10372, 10374, 14525, 14563,
             14564, 14573, 14587, 14588, 14596,
             14597, 15022, 15023, 15033, 15036
\q_nil ..... 866, 869, 2155, 2157,
            2158, 2162, 2163, 2164, 2165, 2166,
            2167, 2367, 2371, 2474, 2474, 2527,
            2548, 3957, 3979, 4853, 4865, 4866,
            5033, 5037, 5055, 5058, 5061, 5146,
            5147, 8412, 8420, 8424, 8441, 8450,
            8451, 8454, 8465, 8472, 8477, 9157
\q_no_value ..... 44,
                  2212, 2474, 2476, 2535, 2557, 5542,
                  5550, 5562, 5584, 5892, 5907, 6252,
                  6262, 6268, 8440, 8446, 8685, 9114
\q_recursion_stop ..... 4, 45, 868, 871, 935, 999, 1523,
                      1534, 1542, 1876, 2478, 2479, 3598,
                      4287, 4925, 5841, 6104, 6140, 8412
\q_recursion_tail ..... 45
\q_recursion_tail .. 4, 935, 940, 999,
                     1018, 2478, 2478, 2482, 2488, 2497,
                     2504, 2514, 2521, 4938, 4955, 4964,
                     5841, 6053, 6067, 6086, 6104, 6140,
                     6370, 6416, 6434, 8412, 14869, 15160
\q_stop ..... 44, 867, 870, 951, 955,
             971, 976, 981, 1029, 1033, 1038,
             1043, 1048, 1076, 1078, 1079, 1080,
             1896, 1902, 1931, 1958, 1962, 1966,
             1974, 1980, 1989, 2007, 2041, 2046,
             2160, 2168, 2212, 2215, 2339, 2341,
             2353, 2355, 2359, 2367, 2371, 2439,
             2474, 2477, 2816, 2818, 2860, 2869,
             2873, 2885, 2891, 2907, 2915, 2927,
             2933, 2945, 2951, 2963, 2969, 2976,
             2981, 2987, 2997, 3001, 3017, 3020,
             3023, 3045, 3239, 3246, 3255, 3264,
             4025, 4062, 4358, 4363, 4458, 4460,
             4800, 4815, 5008, 5010, 5015, 5017,
             5039, 5061, 5140, 5142, 5156, 5171,
             5179, 5181, 5189, 5208, 5230, 5349,
             5351, 5367, 5562, 5565, 5573, 5574,
             5894, 5897, 5909, 5912, 5920, 5923,
             5931, 5947, 6005, 6231, 6234, 7914,
             8423, 8427, 8440, 8445, 8452, 8454,
             8474, 8477, 8547, 8550, 8556, 8565,
             8575, 8694, 8697, 9157, 9162, 9582,
             9671, 10372, 10374, 10433, 10436,
             14490, 14523, 14565, 14573, 14589,
             14596, 14597, 14598, 14933, 14935,
             14940, 15024, 15033, 15036, 15038
\quark_if_nil:N ..... 2525
\quark_if_nil:n ..... 2545
\quark_if_nil:nF ..... 2566
\quark_if_nil:nT ..... 2374, 2378, 2565
\quark_if_nil:NTF 44, 2525, 3960, 3982, 8469

```

\quark_if_nil:nTF	122, 126, 127, 128, 129, 130, 131,
44, 2384, 2393, 2402, 2411, 2545, 2564	132, 133, 134, 135, 138, 236, 237,
\quark_if_nil:oTF	238, 239, 240, 241, 242, 243, 244, 415
\quark_if_nil:VTF	\relpenalty 476
\quark_if_nil_p:N	\RequirePackage 58, 59
\quark_if_nil_p:n	\reverse_if:N 23,
\quark_if_nil_p:o	754, 759, 3579, 3581, 3583, 4276,
\quark_if_nil_p:V	4278, 4280, 5178, 13107, 13537, 13564
\quark_if_no_value:cF	\right 474
\quark_if_no_value:cTF	\righthyphenmin 530
\quark_if_no_value:N	\rightskip 532
\quark_if_no_value:n	\romannumeral 607
\quark_if_no_value:NF	true 177
\quark_if_no_value:NT	\rule 7357, 7412
\quark_if_no_value:NTF	
. 44, 2217, 2525, 2544, 7375, 7379,	
7458, 7462, 9141, 9148, 9261, 9270	S
\quark_if_no_value:nTF	\S 10362
\quark_if_no_value_p:c	\s_fp 9747, 9747, 9751, 9760, 9761, 9762,
\quark_if_no_value_p:N	9763, 9764, 9766, 9767, 9770, 9776,
\quark_if_no_value_p:n	9780, 9800, 9803, 9804, 9814, 9824,
\quark_if_recursion_tail_break:N	9836, 9856, 9932, 9934, 9936, 9937,
	9938, 9940, 9941, 9942, 9944, 10120,
	10125, 10283, 10292, 10294, 10784,
\quark_if_recursion_tail_break:n	11036, 11453, 11478, 11479, 11587,
	11595, 11598, 11609, 11610, 11618,
\quark_if_recursion_tail_stop:N	11619, 11621, 11622, 11623, 11625,
	11626, 11627, 11638, 11641, 11653,
\quark_if_recursion_tail_stop:n	11678, 11731, 11734, 11737, 11756,
8, 9, 45, 2494, 2494, 2510, 5845, 6146	11757, 11759, 11760, 11761, 11769,
\quark_if_recursion_tail_stop:o	11772, 11788, 11789, 11791, 11800,
	11876, 12027, 12061, 12062, 12065,
\quark_if_recursion_tail_stop_do:Nn	12144, 12280, 12283, 12288, 12291,
	12508, 12517, 12522, 12526, 12548,
\quark_if_recursion_tail_stop_do:nn	12621, 12633, 12635, 12842, 12859,
	12861, 13050, 13069, 13071, 13072,
\quark_if_recursion_tail_stop_do:on	13074, 13086, 13091, 13093, 13118,
	13119, 13121, 13137, 13222, 13235,
\quark_new:N	13237, 13284, 13297, 13299, 13312,
. 44, 2473, 2473, 2474, 2475, 2476,	13314, 13327, 13329, 13342, 13344,
2477, 2478, 2479, 2567, 2568, 6200	13357, 13359, 13372, 13384, 13403,
	13412, 13596, 13621, 13624, 13646,
	13670, 13673, 13714, 13737, 13787,
	13788, 13888, 13895, 13948, 13957
R	
\R	\s_fp_division 9755, 9758
\radical	\s_fp_exact 9755,
\raise	9759, 9760, 9761, 9762, 9763, 9764
\read	\s_fp_invalid 9755, 9755
\readline	\s_fp_mark 9753, 9753, 9991,
\relax	9992, 9994, 9998, 10922, 10927, 10953
4, 5, 6, 7,	\s_fp_overflow 9755, 9757, 9767
10, 14, 63, 69, 73, 90, 112, 113, 114,	
115, 116, 117, 118, 119, 120, 121,	

```

\s_fp_stop .. 9753, 9754, 10923, 10925,
    11155, 11657, 11668, 11691, 11699
\s_fp_underflow ..... 9755, 9756, 9766
\s_fp_unknown ..... 10516
\s_stop ..... 47, 2583,
    2583, 2584, 12920, 12935, 13578, 13582
\savecatcodetable ..... 732
\savinghyphcodes ..... 694
\savingvdiscards ..... 695
csc ..... 176
\scan_align_safe_stop: 41, 2327, 2327, 4100
\scan_stop:
    . 9, 263, 277, 778, 778, 957, 1065,
    1089, 1107, 1117, 1135, 1448, 1449,
    1651, 1876, 1879, 1880, 1881, 1882,
    1918, 1960, 2027, 2028, 2330, 2345,
    2580, 2752, 2829, 3248, 3257, 3266,
    3724, 4422, 4433, 4438, 4464, 4469,
    4472, 4519, 4530, 4535, 4540, 4720,
    4721, 4722, 4723, 5179, 5605, 6621,
    6639, 7353, 7408, 9290, 9425, 14077,
    15045, 15046, 15205, 15207, 15209
\scantokens ..... 653
\scriptfont ..... 599
\scriptscriptfont ..... 600
\scriptscriptstyle ..... 445
\scriptspace ..... 485
\scriptstyle ..... 444
\scrollmode ..... 410
\seq_clear:c ..... 5386, 5387
\seq_clear:N
    . . 101, 5386, 5386, 5474, 7910, 7973
\seq_clear_new:c ..... 5390, 5391
\seq_clear_new:N ..... 101, 5390, 5390
\seq_concat:ccc ..... 5436
\seq_concat:NNN 102, 5436, 5436, 5440, 9120
\seq_count:c ..... 5714, 5775
\seq_count:N
    . . 106,
    5714, 5714, 5723, 5774, 14901, 15013
\seq_display:c ..... 5770, 5772
\seq_display:N ..... 5770, 5771
\seq_gclear:c ..... 5386, 5389
\seq_gclear:N ..... 101, 5386, 5388
\seq_gclear_new:c ..... 5390, 5393
\seq_gclear_new:N ..... 101, 5390, 5392
\seq_gconcat:ccc ..... 5436
\seq_gconcat:NNN . . 102, 5436, 5436, 5441
\seq_get:cN ..... 5744, 5745, 5751
\seq_get:cNTF ..... 5750
\seq_get:NN ..... 107, 5744, 5744, 5750
\seq_get:NNTF ..... 107, 5750
\seq_get_left:cN . . 5557, 5745, 5751, 5768
\seq_get_left:cNTF ..... 5626
\seq_get_left>NN ..... 102, 5557, 5557,
    5567, 5626, 5627, 5744, 5750, 5767
\seq_get_left>NNF ..... 5631
\seq_get_left:NNT ..... 5630
\seq_get_left:NNTF ..... 103, 5626, 5632
\seq_get_right:cN ..... 5581
\seq_get_right:cNTF ..... 5626
\seq_get_right>NN
    . . 102, 5581, 5581, 5597, 5628, 5629
\seq_get_right>NNF ..... 5634
\seq_get_right:NNT ..... 5633
\seq_get_right:NNTF ..... 103, 5626, 5635
\seq_gpop:cN ..... 5744, 5749, 5755
\seq_gpop:cNTF ..... 5750
\seq_gpop>NN
    . . 107, 5744, 5748, 5754, 9176, 14076
\seq_gpop:NNTF ..... 107, 5750
\seq_gpop_left:cN ..... 5568, 5749, 5755
\seq_gpop_left:cNTF ..... 5636
\seq_gpop_left>NN
    . . 103, 5568, 5570, 5580, 5638, 5748, 5754
\seq_gpop_left>NNF ..... 5648
\seq_gpop_left:NNT ..... 5647
\seq_gpop_left:NNTF ..... 104, 5636, 5649
\seq_gpop_right:cN ..... 5598
\seq_gpop_right:cNTF ..... 5636
\seq_gpop_right>NN
    . . 103, 5598, 5600, 5625, 5642
\seq_gpop_right>NNF ..... 5654
\seq_gpop_right:NNT ..... 5653
\seq_gpop_right:NNTF ..... 104, 5636, 5655
\seq_gpush:cn ..... 5724, 5739
\seq_gpush:co ..... 5724, 5742
\seq_gpush:cV ..... 5724, 5740
\seq_gpush:cV ..... 5724, 5741
\seq_gpush:cx ..... 5724, 5743
\seq_gpush:Nn ..... 108, 5724, 5734
\seq_gpush>No ..... 5724, 5737, 9173
\seq_gpush:NV ..... 5724, 5735
\seq_gpush:Nv ..... 5724, 5736
\seq_gpush:Nx ..... 5724, 5738, 14063
\seq_gput_left:cN ..... 5458, 5739
\seq_gput_left:co ..... 5458, 5742
\seq_gput_left:cV ..... 5458, 5740
\seq_gput_left:cV ..... 5458, 5741
\seq_gput_left:cx ..... 5458, 5743

```

```

\seq_gput_left:Nn ..... 5444
... 102, 5458, 5458, 5462, 5463, 5734
\seq_gput_left:No ..... 5458, 5737
\seq_gput_left:NV ..... 5458, 5735
\seq_gput_left:Nv ..... 5458, 5736
\seq_gput_left:Nx ..... 5458, 5738
\seq_gput_right:cN ..... 5458
\seq_gput_right:co ..... 5458
\seq_gput_right:cV ..... 5458
\seq_gput_right:cV ..... 5458
\seq_gput_right:cX ..... 5458
\seq_gput_right:Nn ..... 5477, 5535, 5536, 9184
... 102, 5458, 5460, 5464, 5465, 9166, 9171
\seq_gput_right:No ..... 5458, 9214
\seq_gput_right:NV ..... 5458, 9070
\seq_gput_right:Nv ..... 5458
\seq_gput_right:Nx ..... 5458
\seq_gremove_all:cN ..... 5484
\seq_gremove_all:Nn 105, 5484, 5486, 5509
\seq_gremove_duplicates:c ..... 5468
\seq_gremove_duplicates:N ..... 191,
... 104, 5468, 5470, 5483
\seq_greverse:c ..... 14970
\seq_greverse:N ... 191, 14970, 14973, 14988
\seq_gset_eq:cc ..... 5394, 5401
\seq_gset_eq:cN ..... 5394, 5400
\seq_gset_eq:Nc ..... 5394, 5399
\seq_gset_eq>NN ... 101, 5394, 5398, 5471
\seq_gset_filter>NNn ... 192, 14989, 14991
\seq_gset_from_clist:cc ..... 14944
\seq_gset_from_clist:cN ..... 14944
\seq_gset_from_clist:cN ..... 14944
\seq_gset_from_clist:Nc ..... 14944
\seq_gset_from_clist>NN ..... 191, 14944, 14954, 14967, 14968
\seq_gset_from_clist:Nn ..... 14944, 14959, 14969
\seq_gset_map>NNn ... 192, 14999, 15001
\seq_gset_split:Nnn 101, 5402, 5404, 5435
\seq_gset_split:NnV ..... 5402
\seq_if_empty:c ..... 5512
\seq_if_empty:cTF ..... 5510
\seq_if_empty:N ..... 5510
\seq_if_empty:NTF ..... 105, 5510, 8212, 14074, 14535
\seq_if_empty_p:c ..... 5510
\seq_if_empty_p:N ..... 105, 5510
\seq_if_exist:cF ..... 5448
\seq_if_exist:cT ..... 5447
\seq_if_exist:cTF ..... 5442, 5446
\seq_if_exist:NF ..... 5444
\seq_if_exist:NT ..... 5443
\seq_if_exist:NTF 102, 5442, 5442, 15011
\seq_if_exist_p:c ..... 5442, 5449
\seq_if_exist_p:N ..... 102, 5442, 5445
\seq_if_in:cnTF ..... 5514
\seq_if_in:coTF ..... 5514
\seq_if_in:cVTF ..... 5514
\seq_if_in:cvTF ..... 5514
\seq_if_in:cxTF ..... 5514
\seq_if_in:Nn ..... 5514
\seq_if_in:NnF ..... 5477, 5535, 5536, 9184
\seq_if_in:NnT ..... 5533, 5534
\seq_if_in:NnTF ... 105, 5514, 5537, 5538
\seq_if_in:NoTF ..... 5514
\seq_if_in:NvTF ..... 5514
\seq_if_in:NxTF ..... 5514
\seq_item:cN ..... 14894
\seq_item:Nn ..... 191,
... 7990, 7991, 7996, 14894, 14894, 14917
\seq_length:c ..... 5774, 5775
\seq_length:N ..... 5774, 5774
\seq_map_break: 106, 5656, 5656, 5657,
... 5659, 5663, 5664, 5699, 5710, 9130
\seq_map_break:n 106, 5656, 5658, 7930, 7944
\seq_map_function:cN ..... 5660
\seq_map_function>NN 4, 105, 5660, 5660,
... 5672, 5719, 5759, 5776, 7994, 14541
\seq_map_inline:cN ..... 5695
\seq_map_inline:Nn ... 105, 5475, 5695,
... 5695, 5701, 7925, 9085, 9124, 9207
\seq_map_variable:ccn ..... 5702
\seq_map_variable:cNn ..... 5702
\seq_map_variable:Ncn ..... 5702
\seq_map_variable>NNn ..... 105, 5702, 5702, 5712, 5713
\seq_mapthread_function:ccN ..... 14918
\seq_mapthread_function:cNN ..... 14918
\seq_mapthread_function:NcN ..... 14918
\seq_mapthread_function>NNN ..... 191, 14918, 14918, 14942, 14943
\seq_new:c ..... 5384, 5385
\seq_new:N ..... 4,
... 101, 2711, 2728, 5384, 5384, 5467,
... 5762, 5763, 5764, 5765, 7882, 7883,
... 9064, 9065, 9075, 9077, 9080, 14029
\seq_pop:cN ..... 5744, 5747, 5753
\seq_pop:cNTF ..... 5750
\seq_pop>NN ..... 107, 5744, 5746, 5752

```

\seq_pop:NNTF	107, 5750	\seq_remove_duplicates:c	5468
\seq_pop_left:cN	5568, 5747, 5753	\seq_remove_duplicates:N	
\seq_pop_left:cNTF	5636	\seq_reverse:c	14970
\seq_pop_left>NN		\seq_reverse:N	191, 14970, 14971, 14987
103, 5568, 5568, 5579, 5636, 5746, 5752		\seq_set_eq:cc	5394, 5397
\seq_pop_left:NNF	5645	\seq_set_eq:cN	5394, 5396
\seq_pop_left:NNT	5644	\seq_set_eq:Nc	5394, 5395
\seq_pop_left:NNTF	104, 5636, 5646	\seq_set_eq:NN	
\seq_pop_right:cN	5598	101, 5394, 5394, 5469, 9118, 9135, 9194	
\seq_pop_right:cNTF	5636	\seq_set_filter:Nnn	192, 14989, 14989
\seq_pop_right>NN		\seq_set_from_clist:cc	14944
103, 5598, 5598, 5624, 5640		\seq_set_from_clist:cN	14944
\seq_pop_right:NNF	5651	\seq_set_from_clist:cn	14944
\seq_pop_right:NNT	5650	\seq_set_from_clist:Nc	14944
\seq_pop_right:NNTF	104, 5636, 5652	\seq_set_from_clist>NN	
\seq_push:cn	5724, 5729	191, 14944, 14944, 14964, 14965	
\seq_push:co	5724, 5732	\seq_set_from_clist:Nn	14944, 14949, 14966
\seq_push:cV	5724, 5724, 5730	\seq_set_map:Nnn	192, 14999, 14999
\seq_push:cv	5731	\seq_set_split:Nnn	
\seq_push:cx	5724, 5733	101, 2724, 2729, 5402, 5402, 5434	
\seq_push:Nn	108, 5724, 5724	\seq_set_split:NnV	5402, 9119
\seq_push:No	5724, 5727	\seq_show:c	5756, 5772
\seq_push:NV	5724, 5725	\seq_show:N	108, 5756, 5756, 5761, 5771
\seq_push:Nv	5724, 5726	\seq_tmp:w	5604, 5617
\seq_push:Nx	5724, 5728	\seq_top:cN	5766, 5768
\seq_put_left:cn	5450, 5729	\seq_top:NN	5766, 5767
\seq_put_left:co	5450, 5732	\seq_use:c	5776
\seq_put_left:cV	5450, 5730	\seq_use:N	5776, 5776, 5777
\seq_put_left:cv	5450, 5731	\seq_use:Nnnn	192, 15009, 15009
\seq_put_left:cx	5450, 5733	\set@color	7579, 7580
\seq_put_left:Nn		\setbox	581
102, 5450, 5450, 5454, 5455, 5724, 7920		\setlanguage	339
\seq_put_left>No	5450, 5727	\sfcode	636
\seq_put_left:NV	5450, 5725	\sffamily	7346
\seq_put_left:Nv	5450, 5726	\shipout	546
\seq_put_left:Nx	5450, 5728	\show	389
\seq_put_right:cn	5450	\showbox	391
\seq_put_right:co	5450	\showboxbreadth	405
\seq_put_right:cV	5450	\showboxdepth	406
\seq_put_right:cv	5450	\showgroups	666
\seq_put_right:cx	5450	\showifs	667
\seq_put_right:Nn	102, 5450,	\showlists	392
5452, 5456, 5457, 5478, 7981, 9185		\showthe	390
\seq_put_right>No	5450, 9200	\showtokens	654
\seq_put_right:NV	5450	\skewchar	603
\seq_put_right:Nv	5450	\skip	627
\seq_put_right:Nx	5450	\skip_add:cn	4432
\seq_remove_all:cn	5484	\skip_add:Nn	80, 4432, 4432, 4434, 4435
\seq_remove_all:Nn		\skip_const:cn	4397
105, 5484, 5484, 5508, 9190			

\skip_const:Nn	80, 4397, 4397, 4402	\skip_set_eq:NN	81, 4426, 4426, 4427, 4428
\skip_eval:n	81, 4445, 4463, 4463	\skip_show:c	4475
\skip_gadd:cn	4432	\skip_show:N	82, 4475, 4475, 4476
\skip_gadd:Nn	80, 4432, 4434, 4436	\skip_show:n	82, 4477, 4477
.skip_gset:c	150	\skip_split_finite_else_action:nnNN	193, 15041, 15041
\skip_gset:cn	4421	\skip_sub:cn	4432
.skip_gset:N	150	\skip_sub:Nn	81, 4432, 4437, 4439, 4440
\skip_gset:Nn	80, 4400, 4421, 4423, 4425	\skip_use:c	4465
\skip_gset_eq:cc	4426	\skip_use:N	82, 4457, 4464, 4465, 4465, 4466
\skip_gset_eq:cN	4426	\skip_vertical:c	4467
\skip_gset_eq:Nc	4426	\skip_vertical:N	83, 4467, 4470, 4472, 4474
\skip_gset_eq:NN	81, 4426, 4429, 4430, 4431	\skip_vertical:n	4467, 4471
\skip_gsub:cn	4432	\skip_zero:c	4403
\skip_gsub:Nn	81, 4432, 4439, 4441	\skip_zero:N	80, 4403, 4403, 4404, 4404, 4405, 4408
\skip_gzero:c	4403	\skip_zero_new:c	4407
\skip_gzero:N	80, 4403, 4404, 4406, 4410	\skip_zero_new:N	80, 4407, 4407, 4411
\skip_gzero_new:c	4407	\skipdef	326
\skip_gzero_new:N	80, 4407, 4409, 4412	\space	50, 212
\skip_horizontal:c	4467	\spacefactor	545
\skip_horizontal:N	83, 4467, 4467, 4469, 4473	\spaceskip	540
\skip_horizontal:n	4467, 4468, 14426, 14450	\span	353
\skip_if_eq:nn	4442	\special	615
\skip_if_eq:nnTF	81, 4442	\splitbotmark	424
\skip_if_eq_p:nn	81, 4442	\splitbotmarks	650
\skip_if_exist:cF	4419	\splittdiscards	697
\skip_if_exist:cT	4418	\splitfirstmark	423
\skip_if_exist:cTF	4413, 4417	\splitfirstmarks	649
\skip_if_exist:NF	4415	\splitmaxdepth	593
\skip_if_exist:NT	4414	\splittopskip	594
\skip_if_exist:NTF	80, 4408, 4410, 4413, 4413	\str_case:nnn	21, 1520, 1520, 2065, 2458, 15139
\skip_if_exist_p:c	4413, 4420	\str_case:onn	2057, 2459
\skip_if_exist_p:N	80, 4413, 4416	\str_case_x:nnn	22, 1520, 1531, 2460
\skip_if_finite:n	4454	\str_head:n	97, 5167, 5167, 5191, 5238
\skip_if_finite:nTF	81, 4452, 4554, 15043	\str_if_eq:nn	1501
\skip_if_finite_p:n	81, 4452	\str_if_eq:nnF	2061, 2062, 8197
\skip_if_infinite_glue:n	4553	\str_if_eq:nnT	2059, 2060, 5492, 7941
\skip_if_infinite_glue:nTF	4553	\str_if_eq:nnTF	21, 1501, 1527,
\skip_if_infinite_glue_p:n	4553	2063, 2064, 4030, 4033, 7766, 8430	
\skip_new:c	4389	\str_if_eq:noTF	2057
\skip_new:N	80, 4389, 4390, 4396, 4399,	\str_if_eq:nVTF	2057
4408, 4410, 4481, 4482, 4483, 4484		\str_if_eq:onTF	2057
.skip_set:c	150	\str_if_eq:VnTF	2057
\skip_set:cn	4421	\str_if_eq:VVTF	2057
.skip_set:N	150	\str_if_eq:xxF	1603
\skip_set:Nn	80, 4421, 4421, 4423, 4424	\str_if_eq:xxT	1602
\skip_set_eq:cc	4426	\str_if_eq:xxTF	1601, 1604
\skip_set_eq:cN	4426	\str_if_eq_p:nn	21, 1501, 2057, 2058
\skip_set_eq:Nc	4426	\str_if_eq_p:no	2057

\str_if_eq_p:nV	2057	\tex_chardef:D	323, 807, 808, 809, 810,
\str_if_eq_p:on	2057		811, 813, 1053, 1054, 2099, 2101,
\str_if_eq_p:Vn	2057		3003, 3479, 3480, 9246, 9404, 14037
\str_if_eq_p:VV	2057	\tex_cleaders:D	506
\str_if_eq_p:xx	1601, 1601	\tex_closein:D	382, 9345
\str_if_eq_x:nn	1507	\tex_closeout:D	377, 9479
\str_if_eq_x:nnF	1603, 7984	\tex_clubpenalty:D	517
\str_if_eq_x:nnT	1602	\tex_copy:D	574, 6516, 6551
\str_if_eq_x:nnTF	21, 1501, 1538, 1604, 6375, 8449, 9635, 14888	\tex_count:D	625, 2898
\str_if_eq_x_p:nn	21, 1501, 1601	\tex_countdef:D	324, 804, 2901
\str_tail:n	97, 5167, 5175	\tex_cr:D	349
\strcmp	70	\tex_crcr:D	350
\string	77, 149, 230, 608	\tex_curname:D	412, 770
T			
\T	2808, 3007, 10419	\tex_day:D	620
pt	177	\tex_deadcycles:D	554
\tabskip	354	\tex_def:D	319, 784, 786, 788, 789, 817
\tex_above:D	436	\tex_defaulthyphenchar:D	604
\tex_abovedisplayshortskip:D	449	\tex_defaultskewchar:D	605
\tex_abovedisplayskip:D	450	\tex_delcode:D	635
\tex_abovewithdelims:D	437	\tex_delimiter:D	429
\tex_accent:D	487	\tex_delimiterfactor:D	478
\tex_adjdemerits:D	524	\tex_delimitershortfall:D	477
\tex_advance:D	331, 3507, 3509, 3519, 3521, 4196, 4201, 4433, 4438, 4530, 4535	\tex_dimen:D	626, 2876
\tex_afterassignment:D	341, 3078, 3164, 5588, 5614	\tex_dimendef:D	325, 2879
\tex_aftergroup:D	342, 783	\tex_discretionary:D	489
\tex_atop:D	438	\tex_displayindent:D	454
\tex_atopwithdelims:D	439	\tex_displaylimits:D	464
\tex_badness:D	586	\tex_displaystyle:D	442
\tex_baselineskip:D	514	\tex_displaywidowpenalty:D	453
\tex_batchmode:D	407	\tex_displaywidth:D	455
\tex_begingroup:D	345, 779	\tex_divide:D	332
\tex_belowdisplayshortskip:D	451	\tex_doublehyphendemerits:D	522
\tex_belowdisplayskip:D	452	\tex_dp:D	633, 6536
\tex_binoppenalty:D	475	\tex_dump:D	616
\tex_botmark:D	422	\tex_eodef:D	320, 818
\tex_box:D	630, 6522, 6550	\tex_else:D	373, 757, 814
\tex_boxmaxdepth:D	592	\tex_emergencystretch:D	537
\tex_brokenpenalty:D	549	\tex_end:D	411, 735, 1173, 7816
\tex_catcode:D	634, 1066, 1449, 1879, 1880, 1881, 1882, 2027, 2331, 2346, 2598, 2600, 2602, 3269, 4722, 4723	\tex_endcsname:D	413, 771
\tex_char:D	488	\tex_endgroup:D	346, 733, 780
		\tex_endinput:D	385, 7827
		\tex_endlinechar:D	
			262, 263, 277, 427, 4739, 9385, 9387
		\tex_eqno:D	447
		\tex_errhelp:D	393, 7704
		\tex_errmessage:D	387, 1165, 7731
		\tex_errorcontextlines:D	394, 7756
		\tex_errorstopmode:D	408
		\tex_escapechar:D	426, 9522, 9548, 9554
		\tex_everycr:D	355

\tex_everydisplay:D 456, 736
\tex_everyhbox:D 595
\tex_everyjob:D 624, 4636, 4638,
4643, 4645, 9055, 9057, 9067, 9069
\tex_everymath:D 480, 737
\tex_everypar:D 543
\tex_everyvbox:D 596
\tex_exhyphenpenalty:D 519
\tex_expandafter:D 343, 772
\tex_fam:D 335
\tex_fi:D 374, 758, 816
\tex_finalhyphendemerits:D 523
\tex_firstmark:D 421
\tex_floatingpenalty:D 568
\tex_font:D 334
\tex_fondim:D 601
\tex_fontname:D 425
\tex_futurelet:D 330, 3072, 3074
\tex_gdef:D 321, 831
\tex_global:D 305, 310, 312,
336, 1260, 1267, 2101, 3074, 3463,
3483, 3495, 3511, 3513, 3523, 3525,
3532, 4167, 4186, 4192, 4197, 4202,
4404, 4423, 4429, 4434, 4439, 4501,
4520, 4526, 4531, 4536, 5315, 6518,
6524, 6586, 6641, 6647, 6653, 6683,
6689, 6695, 6701, 9713, 9715, 14037
\tex_globaldefs:D 340
\tex_halign:D 347
\tex_hangafter:D 525
\tex_hangindent:D 526
\tex_hbadness:D 587
\tex_hbox:D 582, 6639, 6640, 6645, 6651, 6665, 6666
\tex_hfil:D 490
\tex_hfill:D 492
\tex_hfilneg:D 491
\tex_hfuzz:D 589
\tex_hoffset:D 564
\tex_holdinginserts:D 567
\tex_hrule:D 503
\tex_hsize:D 528, 6830, 6832, 6833, 6876, 6878, 6879
\tex_hskip:D 493, 4467
\tex_hss:D 494, 6668, 6670, 14410
\tex_ht:D 632, 6535
\tex_hyphen:D 317, 738
\tex_hyphenation:D 618
\tex_hyphenchar:D 602
\tex_hyphenpenalty:D 520
\tex_if:D 356, 760, 761
\tex_ifcase:D 357, 3373
\tex_ifcat:D 358, 762
\tex_ifdim:D 361, 4149
\tex_ifeof:D 362, 9362
\tex_iffalse:D 367, 755
\tex_ifhbox:D 363, 6562
\tex_ifhmode:D 369, 765
\tex_ifinner:D 372, 767
\tex_ifmmode:D 370, 764
\tex_ifnum:D 359, 781
\tex_ifodd:D
... 360, 1190, 2073, 2074, 3372, 7609
\tex_iftrue:D 368, 754
\tex_ifvbox:D 364, 6563
\tex_ifvmode:D 371, 766
\tex_ifvoid:D 365, 6564
\tex_ifx:D 366, 763
\tex_ignorespaces:D 414
\tex_immediate:D
... 376, 1160, 1162, 9425, 9479, 9496
\tex_indent:D 510
\tex_input:D 384, 739, 9175
\tex_inputlineno:D 386, 1180, 2022, 7678
\tex_insert:D 566
\tex_insertpenalties:D 569
\tex_interlinepenalty:D 548
\tex_italiccorrection:D 316, 740
\tex_jobname:D 623, 4646, 4650, 9058
\tex_kern:D 501, 7142, 7147, 7213, 7214,
7501, 7502, 14223, 14408, 14625, 14626
\tex_language:D 418
\tex_lastbox:D 575, 6584, 6723
\tex_lastkern:D 508
\tex_lastpenalty:D 614
\tex_lastskip:D 509
\tex_lccode:D
637, 1065, 1448, 2028, 2330, 2345,
2674, 2676, 2678, 3271, 4720, 4721
\tex_leaders:D 505
\tex_left:D 473
\tex_lefthyphenmin:D 529
\tex_leftskip:D 531
\tex_leqno:D 448
\tex_let:D 306, 310, 312, 318, 735, 736,
737, 738, 739, 740, 741, 742, 743,
744, 745, 754, 755, 756, 757, 758,
759, 760, 761, 762, 763, 764, 765,
766, 767, 768, 769, 770, 771, 772,
773, 774, 775, 776, 777, 778, 779,

780, 781, 782, 783, 799, 801, 817, 818, 831, 832, 1256, 1599, 2073, 2074	\tex_nullfont:D	597, 3030
\tex_limits:D	\tex_number:D	606, 3369
\tex_linepenalty:D	\tex_omit:D	352
\tex_lineskip:D	\tex_openin:D	378, 9290
\tex_lineskiplimit:D	\tex_openout:D	379, 9425
\tex_long:D	\tex_or:D	375, 756
337, 784, 786, 789, 820, 822, 828, 830, 834, 836, 842, 844	\tex_outer:D	338
\tex_looseness:D	\tex_output:D	553
\tex_lower:D	\tex_outputpenalty:D	563
\tex_lowercase:D	\tex_over:D	440
609, 1067, 1450, 1883, 2029, 4724, 4764	\tex_overfullrule:D	591
\tex_mag:D	\tex_overline:D	471
\tex_mark:D	\tex_overwithdelims:D	441
\tex_mathaccent:D	\tex_pagedepth:D	555
\tex_mathbin:D	\tex_pagefillstretch:D	559
\tex_mathchar:D	\tex_pagefillstretch:D	558
\tex_mathchardef:D	\tex_pagegoal:D	557
328, 815, 3475, 3476	\tex_pagegoal:D	561
\tex_mathchoice:D	\tex_pageshrink:D	560
\tex_mathclose:D	\tex_pagestretch:D	556
\tex_mathcode:D	\tex_pagetotal:D	562
639, 2668, 2670, 2672, 3270	\tex_par:D	511, 7562
\tex_mathinner:D	\tex_parfillskip:D	542
\tex_mathop:D	\tex_parindent:D	535
\tex_mathopen:D	\tex_parshape:D	527
\tex_mathord:D	\tex_parskip:D	534
\tex_mathpunct:D	\tex_patterns:D	617
\tex_mathrel:D	\tex_pausing:D	404
\tex_mathsurround:D	\tex_penalty:D	612
\tex_maxdeadcycles:D	\tex_postdisplaypenalty:D	459
\tex_maxdepth:D	\tex_predisplaypenalty:D	458
611, 775, 777	\tex_predisplaysize:D	457
\tex_meaning:D	\tex_pretolerance:D	538
\tex_medmuskip:D	\tex_prevdepth:D	585
\tex_message:D	\tex_prevgraf:D	544
\tex_mkern:D	\tex_radical:D	433
\tex_month:D	\tex_raise:D	573, 6559
\tex_moveleft:D	\tex_read:D	380, 9380
\tex_moveright:D	\tex_relax:D	415, 778, 3371, 4151, 10398, 10399, 10488, 10516, 10519, 10735, 10782, 10783, 10951, 10980, 11289
\tex_mskip:D	\tex_relpriority:D	476
\tex_multiply:D	\tex_right:D	474
333	\tex_rightskip:D	530
\tex_muskip:D	\tex_righthyphenmin:D	532
629, 2918	\tex_roman numeral:D	607, 782,
\tex_muskipdef:D	1522, 1533, 1627, 1639, 1645, 1685,	
327, 2921	1689, 1694, 1700, 1706, 1712, 1724,	
\tex_newlinechar:D	1729, 1731, 1738, 1793, 1800, 1805,	
383, 4740	1813, 1815, 1818, 1825, 1831, 1840,	
\tex_noalign:D		
\tex_noboundary:D		
\tex_noexpand:D		
344, 773		
\tex_noindent:D		
512		
\tex_nolimits:D		
466		
\tex_nonscript:D		
446		
\tex_nonstopmode:D		
409		
\tex_nulldelimiterspace:D		
479		

\tex_special:D	615
\tex_splitbotmark:D	424
\tex_splitfirstmark:D	423
\tex_splitmaxdepth:D	593
\tex_splittopskip:D	594
\tex_string:D	608, 776
\tex_tabskip:D	354
\tex_textfont:D	598
\tex_textstyle:D	443
\tex_the:D	
	. 263, 416, 1180, 1657, 1661, 2022,
	2600, 2670, 2676, 2682, 2688, 3276,
	3279, 3282, 3285, 3288, 3535, 4370,
	4465, 4478, 4541, 4546, 4638, 4645,
	6621, 9057, 9069, 10429, 10797, 14063
\tex_thickmuskip:D	484
\tex_thinmuskip:D	483
\tex_time:D	619
\tex_toks:D	628, 2954
\tex_toksdef:D	329, 2957
\tex_tolerance:D	539
\tex_topmark:D	420
\tex_topskip:D	550
\tex_tracingcommands:D	395
\tex_tracinglostchars:D	396
\tex_tracingmacros:D	397
\tex_tracingonline:D	398, 6630
\tex_tracingoutput:D	399
\tex_tracingpages:D	400
\tex_tracingparagraphs:D	401
\tex_tracingrestores:D	402
\tex_tracingstats:D	403
\tex_uccode:D	638, 2680,
	2682, 2684, 3272, 10465, 10491, 10963
\tex_uchyph:D	536
\tex_undefined:D	305, 312
\tex_underline:D	472, 741
\tex_unhbox:D	577, 6672
\tex_unhcopy:D	578, 6671
\tex_unkern:D	502
\tex_unpenalty:D	613
\tex_unskip:D	500
\tex_unvbox:D	579, 6717
\tex_unvcopy:D	580, 6716
\tex_uppercase:D	610, 4766
\tex_vadjust:D	513
\tex_valign:D	348
\tex_vbadness:D	588
\tex_vbox:D	
	583, 6675, 6678, 6680, 6682, 6693, 6699
\tex_span:D	353

\tex_vcenter:D 434
 \tex_vfil:D 495
 \tex_vfill:D 497
 \tex_vfilneg:D 496
 \tex_vfuzz:D 590
 \tex_voffset:D 565
 \tex_vrule:D 504, 7353, 7408
 \tex_vsize:D 547
 \tex_vskip:D 498, 4470
 \tex_vsplit:D 576, 6721
 \tex_vss:D 499
 \tex_vtop:D 584, 6676, 6687
 \tex_wd:D 631, 6537
 \tex_widowpenalty:D 518
 \tex_write:D
 ... 381, 1160, 1162, 9490, 9493, 9496
 \tex_xdef:D 322, 832
 \tex_xleaders:D 507
 \tex_xspaceskip:D 541
 \tex_year:D 622
 \textasteriskcentered 4124, 4130
 \textbardbl 4129
 \textdagger 4125, 4131
 \textdaggerdbl 4126, 4132
 \textfont 598
 \textparagraph 4128
 \textsection 4127
 \textstyle 443
 \TeXeTstate 698
 \the 112, 113, 114,
 115, 116, 117, 118, 119, 120, 121, 416
 \thickmuskip 484
 \thinmuskip 483
 \time 619
 \tiny 7346
 \tl_case:cnn 2462, 4922
 \tl_case:Nnn 92, 2461, 4922, 4922, 4933
 \tl_clear:c 4598, 5387, 5792
 \tl_clear:N 88, 4598,
 4598, 4602, 4605, 5386, 5791, 8302,
 8406, 8410, 9571, 9573, 9577, 9644
 \tl_clear_new:c 4604, 5391, 5796, 8684, 8686
 \tl_clear_new:N
 ... 88, 4604, 4604, 4608, 5390, 5795
 \tl_concat:ccc 4618
 \tl_concat:NNN 88, 4618, 4618, 4622
 \tl_const:cn 4586
 \tl_const:cx 4586, 9529
 \tl_const:Nn 88, 2473,
 2709, 4586, 4586, 4596, 4632, 4652,
 4727, 6201, 7593, 7594, 7646, 7651,
 7653, 7655, 7657, 7659, 7664, 7665,
 7672, 8351, 8353, 8500, 8501, 8502,
 8503, 8504, 9219, 9519, 9760, 9761,
 9762, 9763, 9764, 12299, 12612,
 12613, 12614, 12615, 12616, 12617,
 12618, 12619, 12620, 15101, 15106
 \tl_const:Nx 4586, 4591, 4597,
 4646, 4650, 9523, 13834, 13957, 14558
 \tl_count:c 4990, 5344, 5355
 \tl_count:N
 ... 95, 4990, 4995, 5002, 5343, 5354, 9569
 \tl_count:n
 ... 95, 915, 919, 1318, 1356, 4990,
 4990, 5001, 5340, 5356, 12575, 15155
 \tl_count:o 4990, 5342, 5358
 \tl_count:V 4990, 5341, 5357
 \tl_count_tokens:n
 ... 193, 5353, 15085, 15085, 15100
 \tl_elt_count:c 5339, 5344
 \tl_elt_count:N 5339, 5343
 \tl_elt_count:n 5339, 5340
 \tl_elt_count:o 5339, 5342
 \tl_elt_count:V 5339, 5341
 \tl_expandable_lowercase:n
 ... 194, 15111, 15119
 \tl_expandable_uppercase:n
 ... 194, 15111, 15111
 \tl_gclear:c 4598, 5389, 5794
 \tl_gclear:N
 ... 88, 4598, 4600, 4603, 4607, 5388, 5793
 \tl_gclear_new:c 4604, 5393, 5798
 \tl_gclear_new:N
 ... 88, 4604, 4606, 4609, 5392, 5797
 \tl_gconcat:ccc 4618
 \tl_gconcat:NNN 88, 4618, 4620, 4623
 \tl_gput_left:cn 4671
 \tl_gput_left:co 4671
 \tl_gput_left:cV 4671
 \tl_gput_left:cx 4671
 \tl_gput_left:Nn 89, 4671, 4679, 4691, 5459
 \tl_gput_left:No 4671, 4683, 4693
 \tl_gput_left:NV 4671, 4681, 4692
 \tl_gput_left:Nx 4671, 4685, 4694
 \tl_gput_right:cn 4695
 \tl_gput_right:co 4695
 \tl_gput_right:cV 4695
 \tl_gput_right:cx 4695
 \tl_gput_right:Nn
 ... 89, 2579, 4695, 4703, 4715, 5461

\tl_gput_right:No 4695, 4707, 4717 \tl_gset_eq:Nc 4610, 4616, 5399, 5804, 6219
 \tl_gput_right:NV 4695, 4705, 4716 \tl_gset_eq:NN
 \tl_gput_right:Nx 4695, 4709, 4718, 6306, 6333 88, 4601, 4610, 4614, 5398, 5803,
 \tl_gremove_all:cN 4823, 5337 \tl_gset_rescan:cnn 4729
 \tl_gremove_all:Nn 90, 4823, 4825, 4828, 5336 \tl_gset_rescan:cno 4729
 90, 4823, 4825, 4828, 5336 \tl_gset_rescan:cnx 4729
 \tl_gremove_all_in:cN 5329, 5337 \tl_gset_rescan:Nnn
 \tl_gremove_all_in:Nn 5329, 5336 90, 4729, 4731, 4761, 4762
 \tl_gremove_in:cN 5329, 5333 \tl_gset_rescan:Nno 4729
 \tl_gremove_in:Nn 5329, 5332 \tl_gset_rescan:Nnx 4729
 \tl_gremove_once:cN 4817, 5333 .tl_gset_x:c 150
 \tl_gremove_once:Nn 89, 4817, 4819, 4822, 5332 .tl_gset_x:N 150
 \tl_greplace_all:cnn 4767, 5327 \tl_gtrim_spaces:c 5019
 \tl_greplace_all:Nnn 89, 4767, 4773, 4778, 4826, 5326 \tl_gtrim_spaces:N ... 96, 5019, 5023, 5026
 89, 4767, 4773, 4778, 4826, 5326 \tl_head:f 5137
 \tl_greplace_all_in:cnn 5319, 5327 \tl_head:N 96, 5137, 5157
 \tl_greplace_all_in:Nnn 5319, 5326 \tl_head:n ... 5137, 5137, 5155, 5157, 5347
 \tl_greplace_in:cnn 5319, 5323 \tl_head:V 5137
 \tl_greplace_in:Nnn 5319, 5322 \tl_head:v 5137
 \tl_greplace_once:cnn 4767, 5323 \tl_head:w 97, 5137,
 89, 4767, 4769, 4776, 4820, 5322 5156, 5174, 5189, 5208, 5230, 5348
 \tl_greplace_once:Nnn 89, 4767, 4769, 4776, 4820, 5322 \tl_head_i:n 5346, 5347
 89, 4767, 4769, 4776, 4820, 5322 \tl_head_i:w 5346, 5348
 \tl_greverse:c 5131 \tl_head_iii:f 5346
 \tl_greverse:N 95, 5131, 5133, 5136 \tl_head_iii:n 5346, 5349, 5350
 .tl_gset:c 150 \tl_head_iii:w 5346, 5349, 5351
 \tl_gset:cf 4653 \tl_if_blank:n 4829
 \tl_gset:cn 4653 \tl_if_blank:nF ... 4021, 4833, 4837, 6147
 \tl_gset:co 4653 \tl_if_blank:nT 4832, 4836
 \tl_gset:cV 4653 \tl_if_blank:nTF
 \tl_gset:cv 4653 91, 4829, 4834, 4838, 5161, 14511
 \tl_gset:cx 4653 \tl_if_blank:oTF 4829, 8419
 .tl_gset:N 150 \tl_if_blank:VTF 4829
 \tl_gset:Nc 5313, 5314 \tl_if_blank_p:n 91, 4829, 4831, 4835
 \tl_gset:Nf 4653 \tl_if_blank_p:o 4829
 \tl_gset:Nn 89, \tl_if_blank_p:V 4829
 4653, 4659, 4668, 4670, 4732, 5308, \tl_if_empty:c 5512, 6022
 5571, 5639, 6241, 6267, 6288, 9174 \tl_if_empty:cTF 4839
 \tl_gset:No 4653, 4661 \tl_if_empty:N 4839, 5510, 6021
 \tl_gset:NV 4653 \tl_if_empty:n 4851
 \tl_gset:Nv 4653 \tl_if_empty:NF 4849
 \tl_gset:Nx 4621, 4653, 4663, 4669, 4770, \tl_if_empty:nF 944, 1022,
 4774, 5024, 5134, 5405, 5439, 5487, 3182, 4862, 6073, 8085, 8089, 13801
 5601, 5643, 5810, 5860, 5903, 5941, \tl_if_empty:NT 4848
 5993, 6306, 9058, 13832, 13898, \tl_if_empty:nT 4861
 13908, 13966, 13988, 14532, 14862, \tl_if_empty:NTF ... 91, 4839, 4850, 8466
 14956, 14961, 14974, 14992, 15002 \tl_if_empty:nTF
 \tl_gset_eq:cc 4610, 4617, 5401, 5806, 6221 91, 4063, 4781, 4851, 4860, 5408,
 \tl_gset_eq:cN 4610, 4615, 5400, 5805, 6220 5846, 7687, 7951, 7966, 8301, 8576

\tl_if_empty:o	4872	\tl_if_head_eq_meaning:nN	5220
\tl_if_empty:oTF	3022, 4863, 4910, 5283, 6035, 14548, 14569	\tl_if_head_eq_meaning:nNTF	98, 5182, 8446
\tl_if_empty:VTF	4851	\tl_if_head_eq_meaning_p:nN	98, 5182
\tl_if_empty:x	5359	\tl_if_head_group:n	5361
\tl_if_empty:xTF	5359	\tl_if_head_group:nTF	5361
\tl_if_empty_p:c	4839	\tl_if_head_group_p:n	5361
\tl_if_empty_p:N	91, 4839, 4847	\tl_if_head_is_group:n	5261, 5361
\tl_if_empty_p:n	91, 4851, 4859	\tl_if_head_is_group:nTF	98,
\tl_if_empty_p:o	4863 5077, 5211, 5246, 5261	
\tl_if_empty_p:V	4851	\tl_if_head_is_group_p:n	98, 5261
\tl_if_empty_p:x	5359	\tl_if_head_is_N_type:n	5255, 5363
\tl_if_eq:cc	6186, 6477	\tl_if_head_is_N_type:nTF	98,
\tl_if_eq:cCTF	4874, 8929 5074, 5186, 5205, 5222, 5255, 15057	
\tl_if_eq:cN	6185, 6475	\tl_if_head_is_N_type_p:n	98, 5255
\tl_if_eq:cNTF	4874	\tl_if_head_is_space:n	5276, 5365
\tl_if_eq:Nc	6184, 6476	\tl_if_head_is_space:nTF	98, 5276
\tl_if_eq:NcTF	4874	\tl_if_head_is_space_p:n	98, 5276
\tl_if_eq>NN	4874, 6183, 6474	\tl_if_head_N_type:n	5363
\tl_if_eq:nn	4886	\tl_if_head_N_type:nTF	5361
\tl_if_eq:NNF	4885	\tl_if_head_N_type_p:n	5361
\tl_if_eq:NNT	4884, 5499, 7419, 7422	\tl_if_head_space:n	5365
\tl_if_eq:NNTF	91, 4874, 4883, 4929, 7932, 7986, 9590	\tl_if_head_space:nTF	5361
\tl_if_eq:nnTF	91, 4886	\tl_if_head_space_p:n	5361
\tl_if_eq_p:cc	4874	\tl_if_in:cnTF	4901
\tl_if_eq_p:cN	4874	\tl_if_in:nn	4907
\tl_if_eq_p:Nc	4874	\tl_if_in:NnF	4902, 4905
\tl_if_eq_p:NN	91, 4874, 4882	\tl_if_in:nnF	4902, 4914
\tl_if_exist:cF	4630	\tl_if_in:NnT	4901, 4904, 9090
\tl_if_exist:cT	4629	\tl_if_in:nnT	4901, 4913
\tl_if_exist:cTF	4624, 4628	\tl_if_in:NnTF	92, 2573, 4901, 4903, 4906
\tl_if_exist:NF	4626	\tl_if_in:nnTF	92, 4903, 4907, 4915, 7228, 8546, 8553
\tl_if_exist:NT	4625	\tl_if_in:noTF	4907
\tl_if_exist:NTF	88, 4605, 4607, 4624, 4624, 4986	\tl_if_in:onTF	4907
\tl_if_exist_p:c	4624, 4631	\tl_if_in:VnTF	4907
\tl_if_exist_p:N	88, 4624, 4627	\tl_if_single:n	4920
\tl_if_head_eq_catcode:nN	5201	\tl_if_single:NF	4918
\tl_if_head_eq_catcode:nNTF	97, 5182	\tl_if_single:nF	4918
\tl_if_head_eq_catcode_p:nN	97, 5182	\tl_if_single:NT	4917
\tl_if_head_eq_charcode:fNTF	5182	\tl_if_single:nT	4917
\tl_if_head_eq_charcode:nN	5182	\tl_if_single:NTF	92, 4916, 4919
\tl_if_head_eq_charcode:nNF	5200	\tl_if_single:nTF	92, 4919, 4920
\tl_if_head_eq_charcode:nNT	5199	\tl_if_single_p:N	92, 4916, 4916
\tl_if_head_eq_charcode:nNTF	98, 3926, 3939, 5182, 5198	\tl_if_single_p:n	92, 4916, 4920
\tl_if_head_eq_charcode_p:fN	5182	\tl_if_single_token:n	15055
\tl_if_head_eq_charcode_p:nN	98, 5182, 5197	\tl_if_single_token:nTF	193, 15055
		\tl_if_single_token_p:n	193, 15055
		\tl_item:cn	15148
		\tl_item:Nn	15170, 15171

```

\tl_item:nn ..... 194, 15148, 15148, 15170 \tl_put_right:No ..... 4695, 4699, 4713
\tl_length:c ..... 5354, 5355 \tl_put_right:NV ..... 4695, 4697, 4712
\tl_length:N ..... 5354, 5354 \tl_put_right:Nx ..... 4695, 4701, 4714,
\tl_length:n ..... 5354, 5356 6304, 6331, 8432, 8458, 8471, 8480,
\tl_length:o ..... 5354, 5358 9609, 9615, 9622, 9641, 9650, 9661
\tl_length:V ..... 5354, 5357 \tl_remove_all:cn ..... 4823, 5335
\tl_length_tokens:n ..... 5353, 5353 \tl_remove_all:Nn ..... .
\tl_map_break: ..... . 90, 4823, 4823, 4827, 5334, 9094
. 93, 4939, 4945, 4956, 4965, 4972, \tl_remove_all_in:cn ..... 5329, 5335
4977, 4977, 4978, 4980, 9299, 9433 \tl_remove_all_in:Nn ..... 5329, 5334
\tl_map_break:n ..... 94, 4977, 4979 \tl_remove_in:cn ..... 5329, 5331
\tl_map_function:cN ..... 4935 \tl_remove_in:Nn ..... 5329, 5330
\tl_map_function>NN ..... . \tl_remove_once:cn ..... 4817, 5331
. 92, 4935, 4941, 4948, 4998, 9284, 9419 \tl_remove_once:Nn ..... .
\tl_map_function:nN ..... . 89, 4817, 4817, 4821, 5330
. 93, 4935, 4935, 4942, 4993, 5409 \tl_replace_all:cnn ..... 4767, 5325
\tl_map_inline:cn ..... 4949 \tl_replace_all:Nnn ..... .
\tl_map_inline:Nn ..... 93, 4949, 4958, 4960 89, 4767, 4771, 4777,
\tl_map_inline:nn ..... 93, 2850, 4824, 5324, 5417, 8408, 8409, 9567
. 4949, 4949, 4959, 9526, 11049, 11058 \tl_replace_all_in:cnn ..... 5319, 5325
\tl_map_variable:cNn ..... 4961 \tl_replace_all_in:Nnn ..... 5319, 5324
\tl_map_variable>NNn ..... 93, 4961, 4967, 4976 \tl_replace_in:cnn ..... 5319, 5321
\tl_map_variable:nNn ..... 93, 4961, 4961, 4968 \tl_replace_in:Nnn ..... 5319, 5320
\tl_new:c ..... 4580, 5385, 5790, 8664 \tl_replace_once:cnn ..... 4767, 5321
\tl_new:cN ..... 5304 \tl_replace_once:Nnn ..... .
\tl_new:N ..... 88, 89, 4767, 4767, 4775, 4818, 5320
. 2570, 3066, 4580, 4580, 4585, 4605, \tl_rescan:nn ..... 90, 4729, 4733
4607, 4899, 4900, 5300, 5301, 5302, \tl_reverse:c ..... 5131
5303, 5307, 5381, 5382, 5384, 5787, \tl_reverse:N ..... 95, 5131, 5131, 5135
5789, 6453, 6735, 6758, 6759, 7341, \tl_reverse:n ..... .
7592, 7879, 7880, 8391, 8392, 8393, . 95, 5111, 5111, 5124, 5132, 5134
8394, 8506, 8507, 8508, 8510, 8511, \tl_reverse:o ..... 5111
8512, 8513, 9053, 9073, 9074, 9510, \tl_reverse:V ..... 5111
9511, 9512, 9513, 9514, 14099, 14857 \tl_reverse_items:n ..... 95, 5003, 5003
\tl_new:Nn ..... 5304, 5305, 5310, 5311 \tl_reverse_tokens:n ..... .
\tl_new:Nx ..... 5304 . 193, 15061, 15061, 15078
\tl_put_left:cN ..... 4671 . tl_set:c ..... 150
\tl_put_left:co ..... 4671 \tl_set:cf ..... 4653
\tl_put_left:cV ..... 4671 \tl_set:cn ..... 4653, 8667, 8685, 8689
\tl_put_left:cx ..... 4671 \tl_set:co ..... 4653
\tl_put_left:Nn ..... 89, 4671, 4671, 4687, 5451 \tl_set:cV ..... 4653
\tl_put_left:No ..... 4671, 4675, 4689 \tl_set:cv ..... 4653
\tl_put_left:NV ..... 4671, 4673, 4688 \tl_set:cx ..... 4653
\tl_put_left:Nx ..... 4671, 4677, 4690 . tl_set:N ..... 150
\tl_put_right:cN ..... 4695 \tl_set:Nc ..... 5313, 5315, 5316
\tl_put_right:co ..... 4695 \tl_set:Nf ..... 4653, 8303
\tl_put_right:cV ..... 4695 \tl_set:Nn ..... 89,
\tl_put_right:cx ..... 4695 3084, 3105, 3716, 4653, 4653, 4665,
\tl_put_right:Nn ..... . 4667, 4730, 4889, 4890, 4971, 5411,
. 89, 4695, 4695, 4711, 5453, 8467 5495, 5504, 5518, 5521, 5542, 5550,

```

5569, 5577, 5589, 5637, 5706, 5892,
 5898, 5907, 5914, 6115, 6239, 6252,
 6255, 6261, 6262, 6268, 6272, 6282,
 6293, 6404, 6742, 6746, 6933, 7229,
 7230, 7343, 7346, 7890, 7972, 8407,
 8520, 8558, 8626, 8652, 8730, 8857,
 8870, 8914, 9109, 9114, 9589, 14075
`\tl_set:N` 4653, 4655, 5317
`\tl_set:NV` 4653
`\tl_set:Nv` 4653
`\tl_set:Nx` 4619, 4653, 4657,
 4666, 4768, 4772, 5022, 5132, 5403,
 5422, 5437, 5485, 5559, 5599, 5615,
 5641, 5808, 5858, 5901, 5939, 5991,
 6304, 8451, 8455, 8464, 8479, 8518,
 8545, 8552, 8555, 8855, 8865, 8887,
 8888, 9087, 9088, 9129, 9560, 9565,
 9566, 9629, 9656, 13830, 13897,
 13902, 13964, 13983, 14530, 14860,
 14946, 14951, 14972, 14990, 15000
`\tl_set_eq:cc`
 ... 4610, 4613, 5397, 5802, 6217, 8739
`\tl_set_eq:cN` 4610, 4611, 5396, 5801, 6216
`\tl_set_eq:Nc`
 ... 4610, 4612, 5395, 5800, 6215, 8921
`\tl_set_eq>NN` 88, 4599, 4610, 4610, 5394,
 5799, 6214, 7935, 7943, 13838, 13933
`\tl_set_rescan:cnn` 4729
`\tl_set_rescan:cno` 4729
`\tl_set_rescan:cnx` 4729
`\tl_set_rescan:Nnn`
 ... 90, 4729, 4729, 4759, 4760
`\tl_set_rescan:Nno` 4729
`\tl_set_rescan:Nnx` 4729
`.tl_set_x:c` 150
`.tl_set_x:N` 150
`\tl_show:c` 5288
`\tl_show:N` 99, 5288, 5288, 5297
`\tl_show:n` 99, 5298, 5298
`\tl_tail:f` 5137
`\tl_tail:N` 97, 5137, 5166
`\tl_tail:n` 5137, 5158, 5165, 5166
`\tl_tail:V` 5137
`\tl_tail:v` 5137
`\tl_tail:w` 5367, 5367
`\tl_to_lowercase:n` 90, 2332, 2347, 2810,
 2852, 3009, 4763, 4763, 7716, 8226,
 8400, 9519, 10366, 10420, 13593, 15182
`\tl_to_str:c` 4982
`\tl_to_str:N` 94, 4982,
 4982, 4983, 9089, 9566, 9579, 9580
`\tl_to_str:n` 94, 797, 3239,
 4256, 4363, 4462, 4784, 4853, 4866,
 4981, 4981, 5147, 5170, 5179, 5299,
 6227, 6311, 6318, 6340, 6368, 6369,
 7371, 7454, 7779, 7780, 8023, 8024,
 8310, 8314, 8315, 8319, 8320, 8518,
 8552, 8855, 8865, 8887, 8965, 8981,
 9158, 9201, 9214, 9524, 9670, 13720,
 13721, 13740, 13743, 14882, 14883
`\tl_to_uppercase:n` 91, 4763, 4765
`\tl_trim_spaces:c` 5019
`\tl_trim_spaces:N` ... 96, 5019, 5021, 5025
`\tl_trim_spaces:n` 96, 5019,
 5019, 5022, 5024, 5429, 8455, 8479
`\tl_use:c` 4984, 6191
`\tl_use:N` 94, 4984, 4984, 4989, 6190
`\token_get_arg_spec:N` ... 60, 3237, 3250
`\token_get_prefix_spec:N` ... 60, 3237, 3241
`\token_get_replacement_spec:N`
 ... 60, 3237, 3259
`\token_if_active:N` 2784
`\token_if_active:NF` 3358
`\token_if_active:NT` 3357
`\token_if_active:NTF` ... 54, 2784, 3359
`\token_if_active_char:NF` 3358
`\token_if_active_char:NT` 3357
`\token_if_active_char:NTF` ... 3343, 3359
`\token_if_active_char_p:N` ... 3343, 3356
`\token_if_active_p:N` ... 54, 2784, 3356
`\token_if_alignment:N` 2746
`\token_if_alignment:NF` 3346
`\token_if_alignment:NT` 3345
`\token_if_alignment:NTF` ... 53, 2746, 3347
`\token_if_alignment_p:N` ... 53, 2746, 3344
`\token_if_alignment_tab:NF` 3346
`\token_if_alignment_tab:NT` 3345
`\token_if_alignment_tab:NTF` ... 3343, 3347
`\token_if_alignment_tab_p:N` ... 3343, 3344
`\token_if_chardef:N` 2855
`\token_if_chardef:NTF` ... 55, 2844, 2894
`\token_if_chardef_p:N` 55, 2844
`\token_if_cs:N` 2827
`\token_if_cs:NTF` 55, 2827
`\token_if_cs_p:N` 55, 2827
`\token_if_dim_register:N` 2874
`\token_if_dim_register:NTF` ... 56, 2844
`\token_if_dim_register_p:N` ... 56, 2844
`\token_if_eq_catcode>NN` 2794

\token_if_eq_catcode:NNTF 54, 2794
\token_if_eq_catcode_p:NN
.. 54, 2794, 3141, 3142, 15197, 15198
\token_if_eq_charcode:NN 2799
\token_if_eq_charcode:NNTF 54, 2799
\token_if_eq_charcode_p:NN 54, 2799
\token_if_eq_meaning:NN 2789
\token_if_eq_meaning:NNF 10126
\token_if_eq_meaning:NNT 2342
\token_if_eq_meaning:NNTF
..... 55, 2357, 2789, 3162, 11153
\token_if_eq_meaning_p:NN
..... 55, 2789, 3143, 15199
\token_if_expandable:N 2832
\token_if_expandable:NTF 55, 2832
\token_if_expandable_p:N 55, 2832
\token_if_group_begin:N 2731
\token_if_group_begin:NTF 53, 2731
\token_if_group_begin_p:N 53, 2731
\token_if_group_end:N 2736
\token_if_group_end:NTF 53, 2736
\token_if_group_end_p:N 53, 2736
\token_if_int_register:N 2892
\token_if_int_register:NTF 56, 2844
\token_if_int_register_p:N 56, 2844
\token_if_letter:N 2774
\token_if_letter:NTF 54, 2774
\token_if_letter_p:N 54, 2774
\token_if_long_macro:N 2982
\token_if_long_macro:NTF 55, 2844
\token_if_long_macro_p:N 55, 2844
\token_if_macro:N 2813
\token_if_macro:NTF
.... 55, 2804, 3013, 3243, 3252, 3261
\token_if_macro_p:N 55, 2804
\token_if_math_shift:NF 3350
\token_if_math_shift:NT 3349
\token_if_math_shift:NTF 3343, 3351
\token_if_math_shift_p:N 3343, 3348
\token_if_math_subscript:N 2764
\token_if_math_subscript:NTF 54, 2764
\token_if_math_subscript_p:N 54, 2764
\token_if_math_superscript:N 2759
\token_if_math_superscript:NTF 54, 2759
\token_if_math_superscript_p:N 54, 2759
\token_if_math_toggle:N 2741
\token_if_math_toggle:NF 3350
\token_if_math_toggle:NT 3349
\token_if_math_toggle:NTF 53, 2741, 3351
\token_if_math_toggle_p:N 53, 2741, 3348
\token_if_mathchardef:N 2864
\token_if_mathchardef:NTF 56, 2844, 2896
\token_if_mathchardef_p:N 56, 2844
\token_if_muskip_register:N 2916
\token_if_muskip_register:NTF 56, 2844
\token_if_muskip_register_p:N 56, 2844
\token_if_other:N 2779
\token_if_other:NF 3354
\token_if_other:NT 3353
\token_if_other:NTF 54, 2779, 3355
\token_if_other_char:NF 3354
\token_if_other_char:NT 3353
\token_if_other_char:NTF 3343, 3355
\token_if_other_char_p:N 3343, 3352
\token_if_other_p:N 54, 2779, 3352
\token_if_parameter:N 2753
\token_if_parameter:NTF 54, 2751
\token_if_parameter_p:N 54, 2751
\token_if_primitive:N 3011
\token_if_primitive:NTF 56, 3003
\token_if_primitive_p:N 56, 3003
\token_if_protected_long_macro:N 2991
\token_if_protected_long_macro:NTF
..... 55, 2844
\token_if_protected_long_macro_p:N
..... 55, 2844
\token_if_space:N 2769
\token_if_space:NTF 54, 2769
\token_if_space_p:N 54, 2769
\token_if_toks_register:N 2952
\token_if_toks_register:NTF 56, 2844
\token_if_toks_register_p:N 56, 2844
\token_new:Nn 52, 2691, 2691, 2696, 2698,
2699, 2700, 2702, 2703, 2704, 2705
\token_to_meaning:c 788, 799, 2691
\token_to_meaning:N 53, 775, 775, 1186,
1196, 1892, 2691, 2816, 2860, 2869,
2885, 2907, 2927, 2945, 2963, 2976,
2987, 2997, 3017, 3246, 3255, 3264
\token_to_str:c 788, 788, 918, 927,
948, 968, 1006, 1011, 1026, 1911, 2691
\token_to_str:N 5, 53, 775, 776, 788,
1058, 1059, 1186, 1196, 1198, 1209,
1330, 1360, 1442, 1457, 1972, 1987,

- 2020, 2122, 2353, 2576, 2691, 2862,
 2871, 2887, 2909, 2929, 2947, 2965,
 2978, 2989, 2999, 5267, 5294, 6635,
 6784, 6932, 7546, 7550, 8197, 8204,
 8211, 8294, 9086, 9549, 9550, 9551,
 9552, 9553, 10004, 10005, 10372,
 10380, 10381, 10407, 10568, 10589,
 10604, 10616, 10617, 10630, 10631,
 10656, 10665, 10667, 10692, 10695,
 10745, 10755, 10756, 10771, 10772,
 10816, 10832, 10843, 10895, 13868
`\toks` 628
`\toksdef` 329
`\tolerance` 539
`\topmark` 420
`\topmarks` 646
`\topskip` 550
`\tracingassigns` 656
`\tracingcommands` 395
`\tracinggroups` 663
`\tracingifs` 659
`\tracinglostchars` 396
`\tracingmacros` 397
`\tracingnesting` 658
`\tracingonline` 398
`\tracingoutput` 399
`\tracingpages` 400
`\tracingparagraphs` 401
`\tracingrestores` 402
`\tracingscantokens` 657
`\tracingstats` 403
- U**
- `\uccode` 638
`\uchyph` 536
`\underline` 472
`\unexpanded` 186, 190, 651
`\unhbox` 577
`\unhcopy` 578
`\unkern` 502
`\unless` 642
`\unpenalty` 613
`\unskip` 500
`\unvbox` 579
`\unvcopy` 580
`\uppercase` 610
`\use:c` 16, 846, 846, 943,
 1021, 1152, 1154, 1156, 1158, 2174,
 2193, 3567, 3885, 3895, 4038, 4047,
 4049, 4051, 4052, 4056, 4264, 7812,
 7823, 7838, 7847, 7855, 7863, 7869,
 7895, 8275, 8566, 8573, 8745, 9634
`\use:n` 17, 852, 852, 974, 1277, 1439, 1467,
 1469, 1473, 1481, 1483, 1491, 1495,
 2712, 4734, 4973, 5239, 5258, 5776,
 6117, 6632, 8238, 10049, 10057,
 10066, 10083, 10091, 10119, 14875
`\use:nn` 852, 853,
 1630, 2721, 3237, 4254, 6101, 13061
`\use:nnn` 852, 854, 1327
`\use:nnnn` 852, 855
`\use:x` 19, 847, 847, 930, 992, 1921,
 4360, 4742, 4753, 6615, 7776, 7793,
 8020, 8037, 8693, 9096, 9383, 9575
`\use_i:nn` 18, 792, 856, 856, 882, 958,
 1102, 1130, 1309, 1471, 1485, 1493,
 2043, 2170, 2183, 2187, 2204, 2205,
 5148, 9975, 11978, 12887, 13056, 13495
`\use_i:nnm` 18, 858, 858, 1084, 3246, 11936
`\use_i:nnnn` 18, 858, 862, 11954, 11961, 12151
`\use_i_after_else:nw` 1592, 1594
`\use_i_after_fi:nw` 1592, 1593
`\use_i_after_or:nw` 1592, 1595
`\use_i_after_orelse:nw` 1592, 1596
`\use_i_delimit_by_q_nil:nw` 19, 869, 869
`\use_i_delimit_by_q_recursion_stop:nw` 19, 46, 869, 871, 2489, 2505
`\use_i_delimit_by_q_stop:nw` 19, 869, 870, 14495
`\use_i_i:nn` 18, 858, 861, 1655, 12532, 12553, 13455
`\use_i_i:nnm` 18, 794, 856, 857, 884,
 960, 1104, 1132, 1307, 1468, 1474,
 1482, 1496, 1544, 2183, 5150, 6234,
 8422, 9949, 11980, 12889, 13497, 13805
`\use_i_i:nnnn` 18, 858, 859, 1086, 3255, 8451, 8472
`\use_i_i:nnm` 18, 858, 863
`\use_i_ii:nn` 18, 858, 860, 1549, 3264, 9958, 9965
`\use_i_ii:nnnn` 18, 858, 864
`\use_iv:nnnn` 18, 858, 865
`\use_none:n` 18, 872, 872, 974,
 1279, 1466, 1470, 1472, 1480, 1484,
 1492, 1494, 2491, 2507, 3051, 3816,
 3931, 3935, 3940, 4830, 5062, 5147,
 5163, 5242, 5264, 5283, 5286, 5379,
 5588, 5610, 5614, 5668, 5919, 6012,
 7734, 8085, 8089, 8419, 9718, 9720,
 9914, 9918, 9922, 9926, 9986, 10014,

\use_none:nn .	872 , 873 , 920 , 928 , 1459 , 4921 , 5018 , 5189 , 5208 , 5500 , 5594 , 9863 , 9913 , 9917 , 9921 , 9925 , 14569	130 , 6698 , 6704 , 6709 , 6712 , 6885
\use_none:nnn .	872 , 874 , 5230 , 6337 , 8450 , 8465 , 9912 , 9916 , 9920 , 9924	6710 , 6711
\use_none:nnnn .	872 , 875 , 1973 , 1988 , 3686	6710 , 6712
\use_none:nnnnn .	872 , 876 , 10044 , 10078 , 10104 , 10112	130 , 6692 , 6692 , 6695 , 6696
\use_none:nnnnnn .	872 , 877 , 1028	6686
\use_none:nnnnnnn .	872 , 878 , 950 , 10046 , 10080 , 10106 , 10114 , 10314 , 11994	130 , 6686 , 6686 , 6689 , 6690 , 6842 , 6889
\use_none:nnnnnnnn .	872 , 879	6677 , 6677 , 6677
\use_none:nnnnnnnnn .	872 , 880	6677 , 6677 , 6679
\use_none_delimit_by_q_nil:w .	19 , 866 , 866	129 , 6675 , 6676
\use_none_delimit_by_q_recursion_stop:w .	19 , 46 , 866 , 868 , 941 , 1007 , 1012 , 1019 , 1912 , 1919 , 2483 , 2498	6716 , 6716 , 6718 , 6842 , 6889
\use_none_delimit_by_q_stop:w .	19 , 866 , 867 , 2374 , 2378 , 4792 , 5999 , 7913 , 9663 , 9677 , 14482 , 14487	130 , 6716 , 6717 , 6719
\usepackage .	149 , 230	
V		
\vadjust .	513	
\valign .	348	
.value_forbidden: .	150	
.value_required: .	150	
\vbadness .	588	
\vbox .	583	
\vbox:n .	129 , 6675 , 6675	
\vbox_gset:cn .	6681	
\vbox_gset:cw .	6698 , 6714	
\vbox_gset:Nn .	130 , 6681 , 6683 , 6685	
\vbox_gset:Nw .	130 , 6698 , 6700 , 6703 , 6713	
\vbox_gset_end: .	130 , 6698 , 6709 , 6715	
\vbox_gset_inline:c .	6710 , 6714	
\vbox_gset_inline:N .	6710 , 6713	
\vbox_gset_inline:c .	6710 , 6715	
\vbox_gset_to:cnn .	6692	
\vbox_gset_to:ht:Nnn .	130 , 6692 , 6694 , 6697	
\vbox_gset_top:cn .	6686	
\vbox_gset_top:Nn .	130 , 6686 , 6688 , 6691	
\vbox_set:cn .	6681	
\vbox_set:cw .	6698 , 6711	
\vbox_set:Nn .	130 , 6681 , 6681 , 6683 , 6684 , 6828	
\vbox_set:Nw .	130 , 6698 , 6698 , 6701 , 6702 , 6710 , 6875	
W		
\wd .		631
\widowpenalties .		691
\widowpenalty .		518
TWOBARS .		174
\write .		381
X		
\X .		2027
\ex .		177
\xdef .		322

\xetex_if_engine:F	1473, 1484	exp	175
\xetex_if_engine:T	1472, 1483	\xspaceskip	541
\xetex_if_engine:TF	5, 22, 1466,	1474, 1485	
\xetex_if_engine_p:		Y
.....	22, 1466, 1477,	1487, 1590	
\xetex_XeTeXversion:D	726, 1478	\year	622
\XeTeXversion	726		Z
\xleaders	507	\z@	4382