

# The L<sup>A</sup>T<sub>E</sub>X3 Sources

The L<sup>A</sup>T<sub>E</sub>X3 Project\*

May 20, 2016

## Abstract

This is the reference documentation for the `expl3` programming environment. The `expl3` modules set up an experimental naming scheme for L<sup>A</sup>T<sub>E</sub>X commands, which allow the L<sup>A</sup>T<sub>E</sub>X programmer to systematically name functions and variables, and specify the argument types of functions.

The T<sub>E</sub>X and  $\epsilon$ -T<sub>E</sub>X primitives are all given a new name according to these conventions. However, in the main direct use of the primitives is not required or encouraged: the `expl3` modules define an independent low-level L<sup>A</sup>T<sub>E</sub>X3 programming language.

At present, the `expl3` modules are designed to be loaded on top of L<sup>A</sup>T<sub>E</sub>X 2 $\epsilon$ . In time, a L<sup>A</sup>T<sub>E</sub>X3 format will be produced based on this code. This allows the code to be used in L<sup>A</sup>T<sub>E</sub>X 2 $\epsilon$  packages *now* while a stand-alone L<sup>A</sup>T<sub>E</sub>X3 is developed.

**While `expl3` is still experimental, the bundle is now regarded as broadly stable. The syntax conventions and functions provided are now ready for wider use. There may still be changes to some functions, but these will be minor when compared to the scope of `expl3`.**

**New modules will be added to the distributed version of `expl3` as they reach maturity.**

---

\*E-mail: [latex-team@latex-project.org](mailto:latex-team@latex-project.org)

# Contents

<b>I</b>	<b>Introduction to <code>expl3</code> and this document</b>	<b>1</b>
<b>1</b>	<b>Naming functions and variables</b>	<b>1</b>
1.1	Terminological inexactitude . . . . .	3
<b>2</b>	<b>Documentation conventions</b>	<b>3</b>
<b>3</b>	<b>Formal language conventions which apply generally</b>	<b>5</b>
<b>4</b>	<b><code>TeX</code> concepts not supported by <code>LaTeX3</code></b>	<b>5</b>
<b>II</b>	<b>The <code>l3bootstrap</code> package: Bootstrap code</b>	<b>6</b>
<b>1</b>	<b>Using the <code>LaTeX3</code> modules</b>	<b>6</b>
1.1	Internal functions and variables . . . . .	7
<b>III</b>	<b>The <code>l3names</code> package: Namespace for primitives</b>	<b>8</b>
<b>1</b>	<b>Setting up the <code>LaTeX3</code> programming language</b>	<b>8</b>
<b>IV</b>	<b>The <code>l3basics</code> package: Basic definitions</b>	<b>9</b>
<b>1</b>	<b>No operation functions</b>	<b>9</b>
<b>2</b>	<b>Grouping material</b>	<b>9</b>
<b>3</b>	<b>Control sequences and functions</b>	<b>10</b>
3.1	Defining functions . . . . .	10
3.2	Defining new functions using parameter text . . . . .	11
3.3	Defining new functions using the signature . . . . .	12
3.4	Copying control sequences . . . . .	15
3.5	Deleting control sequences . . . . .	15
3.6	Showing control sequences . . . . .	15
3.7	Converting to and from control sequences . . . . .	16
<b>4</b>	<b>Using or removing tokens and arguments</b>	<b>17</b>
4.1	Selecting tokens from delimited arguments . . . . .	19
<b>5</b>	<b>Predicates and conditionals</b>	<b>19</b>
5.1	Tests on control sequences . . . . .	20
5.2	Primitive conditionals . . . . .	21
<b>6</b>	<b>Internal kernel functions</b>	<b>22</b>
<b>V</b>	<b>The <code>l3expan</code> package: Argument expansion</b>	<b>24</b>

1	Defining new variants	24
2	Methods for defining variants	25
3	Introducing the variants	25
4	Manipulating the first argument	26
5	Manipulating two arguments	28
6	Manipulating three arguments	28
7	Unbraced expansion	29
8	Preventing expansion	30
9	Controlled expansion	31
10	Internal functions and variables	32
<b>VI</b>	<b>The <code>l3tl</code> package: Token lists</b>	<b>34</b>
1	Creating and initialising token list variables	34
2	Adding data to token list variables	35
3	Modifying token list variables	36
4	Reassigning token list category codes	36
5	Token list conditionals	37
6	Mapping to token lists	39
7	Using token lists	41
8	Working with the content of token lists	41
9	The first token from a token list	43
10	Using a single item	45
11	Viewing token lists	45
12	Constant token lists	46
13	Scratch token lists	46
14	Internal functions	46
<b>VII</b>	<b>The <code>l3str</code> package: Strings</b>	<b>47</b>

1	Building strings	47
2	Adding data to string variables	48
2.1	String conditionals . . . . .	49
3	Working with the content of strings	50
4	String manipulation	53
5	Viewing strings	54
6	Constant token lists	55
7	Scratch strings	55
7.1	Internal string functions . . . . .	55
<b>VIII</b>	<b>The l3seq package: Sequences and stacks</b>	<b>57</b>
1	Creating and initialising sequences	57
2	Appending data to sequences	58
3	Recovering items from sequences	58
4	Recovering values from sequences with branching	59
5	Modifying sequences	60
6	Sequence conditionals	61
7	Mapping to sequences	61
8	Using the content of sequences directly	63
9	Sequences as stacks	64
10	Sequences as sets	65
11	Constant and scratch sequences	66
12	Viewing sequences	67
13	Internal sequence functions	67
<b>IX</b>	<b>The l3int package: Integers</b>	<b>68</b>
1	Integer expressions	68
2	Creating and initialising integers	69
3	Setting and incrementing integers	70

4	Using integers	70
5	Integer expression conditionals	71
6	Integer expression loops	72
7	Integer step functions	74
8	Formatting integers	74
9	Converting from other formats to integers	76
10	Viewing integers	77
11	Constant integers	78
12	Scratch integers	78
13	Primitive conditionals	79
14	Internal functions	79
<b>X</b>	<b>The <code>l3intarray</code> package: low-level arrays of small integers</b>	<b>81</b>
1	<b><code>l3intarray</code> documentation</b>	<b>81</b>
	1.1 Internal functions . . . . .	81
<b>XI</b>	<b>The <code>l3flag</code> package: expandable flags</b>	<b>82</b>
1	Setting up flags	82
2	Expandable flag commands	83
<b>XII</b>	<b>The <code>l3quark</code> package: Quarks</b>	<b>84</b>
1	Introduction to quarks and scan marks	84
	1.1 Quarks . . . . .	84
2	Defining quarks	84
3	Quark tests	85
4	Recursion	85
5	An example of recursion with quarks	86
6	Internal quark functions	87
7	Scan marks	87

<b>XIII</b>	<b>The <code>l3prg</code> package: Control structures</b>	<b>89</b>
1	Defining a set of conditional functions	89
2	The boolean data type	91
3	Boolean expressions	93
4	Logical loops	95
5	Producing multiple copies	96
6	Detecting $\TeX$ 's mode	96
7	Primitive conditionals	96
8	Internal programming functions	97
<b>XIV</b>	<b>The <code>l3clist</code> package: Comma separated lists</b>	<b>98</b>
1	Creating and initialising comma lists	98
2	Adding data to comma lists	99
3	Modifying comma lists	100
4	Comma list conditionals	101
5	Mapping to comma lists	101
6	Using the content of comma lists directly	103
7	Comma lists as stacks	104
8	Using a single item	105
9	Viewing comma lists	105
10	Constant and scratch comma lists	106
<b>XV</b>	<b>The <code>l3token</code> package: Token manipulation</b>	<b>107</b>
1	Creating character tokens	107
2	Manipulating and interrogating character tokens	108
3	Generic tokens	111
4	Converting tokens	112
5	Token conditionals	112

6	Peeking ahead at the next token	115
7	Decomposing a macro definition	118
8	Description of all possible tokens	119
9	Internal functions	121
<b>XVI</b>	<b>The <code>l3prop</code> package: Property lists</b>	<b>122</b>
1	Creating and initialising property lists	122
2	Adding entries to property lists	123
3	Recovering values from property lists	123
4	Modifying property lists	124
5	Property list conditionals	124
6	Recovering values from property lists with branching	125
7	Mapping to property lists	125
8	Viewing property lists	126
9	Scratch property lists	127
10	Constants	127
11	Internal property list functions	127
<b>XVII</b>	<b>The <code>l3msg</code> package: Messages</b>	<b>128</b>
1	Creating new messages	128
2	Contextual information for messages	129
3	Issuing messages	130
4	Redirecting messages	132
5	Low-level message functions	133
6	Kernel-specific functions	134
7	Expandable errors	136
8	Internal <code>l3msg</code> functions	136
<b>XVIII</b>	<b>The <code>l3file</code> package: File and I/O operations</b>	<b>138</b>

<b>1</b>	<b>File operation functions</b>	<b>138</b>
1.1	Input-output stream management . . . . .	139
1.2	Reading from files . . . . .	141
<b>2</b>	<b>Writing to files</b>	<b>143</b>
2.1	Wrapping lines in output . . . . .	145
2.2	Constant input-output streams . . . . .	146
2.3	Primitive conditionals . . . . .	146
2.4	Internal file functions and variables . . . . .	146
2.5	Internal input-output functions . . . . .	147
<b>XIX</b>	<b>The l3skip package: Dimensions and skips</b>	<b>148</b>
<b>1</b>	<b>Creating and initialising dim variables</b>	<b>148</b>
<b>2</b>	<b>Setting dim variables</b>	<b>149</b>
<b>3</b>	<b>Utilities for dimension calculations</b>	<b>149</b>
<b>4</b>	<b>Dimension expression conditionals</b>	<b>150</b>
<b>5</b>	<b>Dimension expression loops</b>	<b>152</b>
<b>6</b>	<b>Using dim expressions and variables</b>	<b>153</b>
<b>7</b>	<b>Viewing dim variables</b>	<b>155</b>
<b>8</b>	<b>Constant dimensions</b>	<b>155</b>
<b>9</b>	<b>Scratch dimensions</b>	<b>155</b>
<b>10</b>	<b>Creating and initialising skip variables</b>	<b>156</b>
<b>11</b>	<b>Setting skip variables</b>	<b>156</b>
<b>12</b>	<b>Skip expression conditionals</b>	<b>157</b>
<b>13</b>	<b>Using skip expressions and variables</b>	<b>157</b>
<b>14</b>	<b>Viewing skip variables</b>	<b>157</b>
<b>15</b>	<b>Constant skips</b>	<b>158</b>
<b>16</b>	<b>Scratch skips</b>	<b>158</b>
<b>17</b>	<b>Inserting skips into the output</b>	<b>158</b>
<b>18</b>	<b>Creating and initialising muskip variables</b>	<b>159</b>
<b>19</b>	<b>Setting muskip variables</b>	<b>159</b>
<b>20</b>	<b>Using muskip expressions and variables</b>	<b>160</b>



21	Viewing muskip variables	160
22	Constant muskips	161
23	Scratch muskips	161
24	Primitive conditional	161
25	Internal functions	162
<b>XX</b>	<b>The l3keys package: Key–value interfaces</b>	<b>163</b>
1	Creating keys	164
2	Sub-dividing keys	168
3	Choice and multiple choice keys	168
4	Setting keys	171
5	Handling of unknown keys	171
6	Selective key setting	172
7	Utility functions for keys	173
8	Low-level interface for parsing key–val lists	174
<b>XXI</b>	<b>The l3fp package: floating points</b>	<b>176</b>
1	Creating and initialising floating point variables	177
2	Setting floating point variables	177
3	Using floating point numbers	178
4	Floating point conditionals	179
5	Floating point expression loops	181
6	Some useful constants, and scratch variables	182
7	Floating point exceptions	183
8	Viewing floating points	184
9	Floating point expressions	184
9.1	Input of floating point numbers . . . . .	184
9.2	Precedence of operators . . . . .	185
9.3	Operations . . . . .	186

10	Disclaimer and roadmap	192
XXII	The <b>l3sort</b> package: Sorting functions	195
1	Controlling sorting	195
XXIII	The <b>l3tl-analysis</b> package: analysing token lists	196
1	<b>l3tl-analysis</b> documentation	196
XXIV	The <b>l3tl-build</b> package: building token lists	197
1	<b>l3tl-build</b> documentation	197
1.1	Internal functions . . . . .	197
XXV	The <b>l3regex</b> package: regular expressions in <b>T<sub>E</sub>X</b>	198
1	Regular expressions	198
1.1	Syntax of regular expressions . . . . .	198
1.2	Syntax of the replacement text . . . . .	203
1.3	Pre-compiling regular expressions . . . . .	205
1.4	Matching . . . . .	205
1.5	Submatch extraction . . . . .	206
1.6	Replacement . . . . .	207
1.7	Bugs, misfeatures, future work, and other possibilities . . . . .	207
XXVI	The <b>l3box</b> package: Boxes	211
1	Creating and initialising boxes	211
2	Using boxes	212
3	Measuring and setting box dimensions	212
4	Box conditionals	213
5	The last box inserted	213
6	Constant boxes	214
7	Scratch boxes	214
8	Viewing box contents	214
9	Boxes and color	214
10	Horizontal mode boxes	215

11	Vertical mode boxes	216
11.1	Affine transformations . . . . .	218
12	Primitive box conditionals	220
XXVII	The <b>l3coffins</b> package: Coffin code layer	221
1	Creating and initialising coffins	221
2	Setting coffin content and poles	221
3	Joining and using coffins	222
4	Measuring coffins	223
5	Coffin diagnostics	223
5.1	Constants and variables . . . . .	224
XXVIII	The <b>l3color</b> package: Color support	225
1	Color in boxes	225
1.1	Internal functions . . . . .	225
XXIX	The <b>l3sys</b> package: System/runtime functions	226
1	The name of the job	226
2	Date and time	226
3	Engine	226
4	Output format	227
XXX	The <b>l3deprecation</b> package: Deprecation errors	228
1	<b>l3deprecation</b> documentation	228
XXXI	The <b>l3candidates</b> package: Experimental additions to <b>l3kernel</b>	229
1	Important notice	229
2	Additions to <b>l3basics</b>	229
3	Additions to <b>l3box</b>	230
3.1	Viewing part of a box . . . . .	230
4	Additions to <b>l3clist</b>	231

5	Additions to <b>l3coffins</b>	231
6	Additions to <b>l3file</b>	231
7	Additions to <b>l3int</b>	232
8	Additions to <b>l3msg</b>	232
9	Additions to <b>l3prop</b>	233
10	Additions to <b>l3seq</b>	234
11	Additions to <b>l3skip</b>	234
12	Additions to <b>l3sys</b>	235
13	Additions to <b>l3tl</b>	236
14	Additions to <b>l3tokens</b>	241
<b>XXXII</b>	<b>The <b>l3luatex</b> package: LuaTeX-specific functions</b>	<b>242</b>
1	Breaking out to Lua	242
1.1	TeX code interfaces . . . . .	242
1.2	Lua interfaces . . . . .	243
<b>XXXIII</b>	<b>The <b>l3drivers</b> package: Drivers</b>	<b>244</b>
1	Box clipping	244
2	Box rotation and scaling	244
3	Color support	245
4	Drawing	245
4.1	Path construction . . . . .	246
4.2	Stroking and filling . . . . .	246
4.3	Stroke options . . . . .	247
4.4	Color . . . . .	248
4.5	Inserting TeX material . . . . .	249
4.6	Coordinate system transformations . . . . .	249
<b>XXXIV</b>	<b>Implementation</b>	<b>249</b>

<b>1</b>	<b>l3bootstrap implementation</b>	<b>249</b>
1.1	Format-specific code . . . . .	249
1.2	The <code>\pdfstrcmp</code> primitive in $\text{\LaTeX}$ . . . . .	250
1.3	Loading support Lua code . . . . .	250
1.4	Engine requirements . . . . .	251
1.5	Extending allocators . . . . .	252
1.6	Character data . . . . .	253
1.7	The $\text{\LaTeX}$ 3 code environment . . . . .	255
<b>2</b>	<b>l3names implementation</b>	<b>256</b>
<b>3</b>	<b>l3basics implementation</b>	<b>278</b>
3.1	Renaming some $\text{\TeX}$ primitives (again) . . . . .	278
3.2	Defining some constants . . . . .	280
3.3	Defining functions . . . . .	280
3.4	Selecting tokens . . . . .	281
3.5	Gobbling tokens from input . . . . .	282
3.6	Conditional processing and definitions . . . . .	282
3.7	Dissecting a control sequence . . . . .	288
3.8	Exist or free . . . . .	290
3.9	Checking and patching (new) functions . . . . .	291
3.10	Defining new functions . . . . .	296
3.11	Copying definitions . . . . .	297
3.12	Undefining functions . . . . .	298
3.13	Generating parameter text from argument count . . . . .	298
3.14	Defining functions from a given number of arguments . . . . .	299
3.15	Using the signature to define functions . . . . .	300
3.16	Checking control sequence equality . . . . .	302
3.17	Diagnostic functions . . . . .	302
3.18	Doing nothing functions . . . . .	303
3.19	Breaking out of mapping functions . . . . .	303
<b>4</b>	<b>l3expan implementation</b>	<b>304</b>
4.1	General expansion . . . . .	304
4.2	Hand-tuned definitions . . . . .	307
4.3	Definitions with the automated technique . . . . .	310
4.4	Last-unbraced versions . . . . .	311
4.5	Preventing expansion . . . . .	312
4.6	Controlled expansion . . . . .	313
4.7	Defining function variants . . . . .	313

<b>5</b>	<b>l3tl implementation</b>	<b>320</b>
5.1	Functions	320
5.2	Constant token lists	322
5.3	Adding to token list variables	322
5.4	Reassigning token list category codes	324
5.5	Modifying token list variables	327
5.6	Token list conditionals	331
5.7	Mapping to token lists	335
5.8	Using token lists	336
5.9	Working with the contents of token lists	337
5.10	Token by token changes	339
5.11	The first token from a token list	341
5.12	Using a single item	346
5.13	Viewing token lists	346
5.14	Scratch token lists	347
5.15	Deprecated functions	347
<b>6</b>	<b>l3str implementation</b>	<b>348</b>
6.1	Creating and setting string variables	348
6.2	String comparisons	349
6.3	Accessing specific characters in a string	352
6.4	Counting characters	356
6.5	The first character in a string	358
6.6	String manipulation	359
6.7	Viewing strings	361
6.8	Unicode data for case changing	361
<b>7</b>	<b>l3seq implementation</b>	<b>364</b>
7.1	Allocation and initialisation	365
7.2	Appending data to either end	368
7.3	Modifying sequences	369
7.4	Sequence conditionals	371
7.5	Recovering data from sequences	372
7.6	Mapping to sequences	376
7.7	Using sequences	378
7.8	Sequence stacks	378
7.9	Viewing sequences	379
7.10	Scratch sequences	380

<b>8</b>	<b>l3int implementation</b>	<b>380</b>
8.1	Integer expressions . . . . .	381
8.2	Creating and initialising integers . . . . .	382
8.3	Setting and incrementing integers . . . . .	384
8.4	Using integers . . . . .	385
8.5	Integer expression conditionals . . . . .	385
8.6	Integer expression loops . . . . .	389
8.7	Integer step functions . . . . .	390
8.8	Formatting integers . . . . .	391
8.9	Converting from other formats to integers . . . . .	397
8.10	Viewing integer . . . . .	400
8.11	Constant integers . . . . .	400
8.12	Scratch integers . . . . .	402
8.13	Deprecated . . . . .	402
<b>9</b>	<b>l3intarray implementation</b>	<b>402</b>
9.1	Allocating arrays . . . . .	402
9.2	Array items . . . . .	403
<b>10</b>	<b>l3flag implementation</b>	<b>404</b>
10.1	Non-expandable flag commands . . . . .	404
10.2	Expandable flag commands . . . . .	405
<b>11</b>	<b>l3quark implementation</b>	<b>406</b>
11.1	Quarks . . . . .	406
11.2	Scan marks . . . . .	409
<b>12</b>	<b>l3prg implementation</b>	<b>410</b>
12.1	Primitive conditionals . . . . .	410
12.2	Defining a set of conditional functions . . . . .	410
12.3	The boolean data type . . . . .	411
12.4	Boolean expressions . . . . .	413
12.5	Logical loops . . . . .	419
12.6	Producing multiple copies . . . . .	420
12.7	Detecting T <sub>E</sub> X's mode . . . . .	421
12.8	Internal programming functions . . . . .	422
<b>13</b>	<b>l3clist implementation</b>	<b>422</b>
13.1	Allocation and initialisation . . . . .	423
13.2	Removing spaces around items . . . . .	425
13.3	Adding data to comma lists . . . . .	426
13.4	Comma lists as stacks . . . . .	426
13.5	Modifying comma lists . . . . .	428
13.6	Comma list conditionals . . . . .	431
13.7	Mapping to comma lists . . . . .	432
13.8	Using comma lists . . . . .	435
13.9	Using a single item . . . . .	436
13.10	Viewing comma lists . . . . .	437
13.11	Scratch comma lists . . . . .	438

<b>14</b>	<b>l3token implementation</b>	<b>438</b>
14.1	Manipulating and interrogating character tokens . . . . .	438
14.2	Creating character tokens . . . . .	441
14.3	Generic tokens . . . . .	445
14.4	Token conditionals . . . . .	446
14.5	Peeking ahead at the next token . . . . .	453
14.6	Decomposing a macro definition . . . . .	458
<b>15</b>	<b>l3prop implementation</b>	<b>459</b>
15.1	Allocation and initialisation . . . . .	460
15.2	Accessing data in property lists . . . . .	461
15.3	Property list conditionals . . . . .	464
15.4	Recovering values from property lists with branching . . . . .	466
15.5	Mapping to property lists . . . . .	466
15.6	Viewing property lists . . . . .	467
<b>16</b>	<b>l3msg implementation</b>	<b>468</b>
16.1	Creating messages . . . . .	468
16.2	Messages: support functions and text . . . . .	469
16.3	Showing messages: low level mechanism . . . . .	470
16.4	Displaying messages . . . . .	473
16.5	Kernel-specific functions . . . . .	480
16.6	Expandable errors . . . . .	486
16.7	Showing variables . . . . .	487
<b>17</b>	<b>l3file implementation</b>	<b>491</b>
17.1	File operations . . . . .	491
17.2	Input operations . . . . .	497
17.2.1	Variables and constants . . . . .	497
17.2.2	Stream management . . . . .	498
17.2.3	Reading input . . . . .	501
17.3	Output operations . . . . .	502
17.3.1	Variables and constants . . . . .	502
17.4	Stream management . . . . .	504
17.4.1	Deferred writing . . . . .	505
17.4.2	Immediate writing . . . . .	505
17.4.3	Special characters for writing . . . . .	506
17.4.4	Hard-wrapping lines to a character count . . . . .	506
17.5	Messages . . . . .	515
17.6	Deprecated functions . . . . .	515



<b>18</b>	<b>l3skip implementation</b>	<b>518</b>
18.1	Length primitives renamed	518
18.2	Creating and initialising <code>dim</code> variables	518
18.3	Setting <code>dim</code> variables	519
18.4	Utilities for dimension calculations	520
18.5	Dimension expression conditionals	520
18.6	Dimension expression loops	522
18.7	Using <code>dim</code> expressions and variables	523
18.8	Viewing <code>dim</code> variables	525
18.9	Constant dimensions	525
18.10	Scratch dimensions	525
18.11	Creating and initialising <code>skip</code> variables	526
18.12	Setting <code>skip</code> variables	527
18.13	<code>Skip</code> expression conditionals	527
18.14	Using <code>skip</code> expressions and variables	528
18.15	Inserting skips into the output	528
18.16	Viewing <code>skip</code> variables	529
18.17	Constant skips	529
18.18	Scratch skips	529
18.19	Creating and initialising <code>muskip</code> variables	529
18.20	Setting <code>muskip</code> variables	530
18.21	Using <code>muskip</code> expressions and variables	531
18.22	Viewing <code>muskip</code> variables	531
18.23	Constant muskips	532
18.24	Scratch muskips	532
<b>19</b>	<b>l3keys Implementation</b>	<b>532</b>
19.1	Low-level interface	532
19.2	Constants and variables	536
19.3	The key defining mechanism	538
19.4	Turning properties into actions	540
19.5	Creating key properties	545
19.6	Setting keys	549
19.7	Utilities	554
19.8	Messages	556
<b>20</b>	<b>l3fp implementation</b>	<b>558</b>
<b>21</b>	<b>l3fp-aux implementation</b>	<b>558</b>
21.1	Internal representation	558
21.2	Using arguments and semicolons	559
21.3	Constants, and structure of floating points	560
21.4	Overflow, underflow, and exact zero	562
21.5	Expanding after a floating point number	562
21.6	Packing digits	564
21.7	Decimate (dividing by a power of 10)	566
21.8	Functions for use within primitive conditional branches	568
21.9	Integer floating points	569
21.10	Small integer floating points	569
21.11	Length of a floating point array	570

	21.12x-like expansion expandably . . . . .	571
	21.13Messages . . . . .	571
<b>22</b>	<b>l3fp-traps Implementation</b>	<b>571</b>
	22.1 Flags . . . . .	572
	22.2 Traps . . . . .	572
	22.3 Errors . . . . .	575
	22.4 Messages . . . . .	576
<b>23</b>	<b>l3fp-round implementation</b>	<b>576</b>
	23.1 Rounding tools . . . . .	577
	23.2 The round function . . . . .	581
<b>24</b>	<b>l3fp-parse implementation</b>	<b>584</b>
	24.1 Work plan . . . . .	584
	24.1.1 Storing results . . . . .	586
	24.1.2 Precedence and infix operators . . . . .	587
	24.1.3 Prefix operators, parentheses, and functions . . . . .	590
	24.1.4 Numbers and reading tokens one by one . . . . .	590
	24.2 Main auxiliary functions . . . . .	592
	24.3 Helpers . . . . .	593
	24.4 Parsing one number . . . . .	594
	24.4.1 Numbers: trimming leading zeros . . . . .	599
	24.4.2 Number: small significand . . . . .	601
	24.4.3 Number: large significand . . . . .	603
	24.4.4 Number: beyond 16 digits, rounding . . . . .	605
	24.4.5 Number: finding the exponent . . . . .	607
	24.5 Constants, functions and prefix operators . . . . .	610
	24.5.1 Prefix operators . . . . .	610
	24.5.2 Constants . . . . .	612
	24.5.3 Functions . . . . .	614
	24.6 Main functions . . . . .	614
	24.7 Infix operators . . . . .	615
	24.7.1 Closing parentheses and commas . . . . .	616
	24.7.2 Usual infix operators . . . . .	618
	24.7.3 Juxtaposition . . . . .	619
	24.7.4 Multi-character cases . . . . .	619
	24.7.5 Ternary operator . . . . .	620
	24.7.6 Comparisons . . . . .	621
	24.8 Candidate: defining new l3fp functions . . . . .	623
	24.9 Messages . . . . .	624
<b>25</b>	<b>l3fp-logic Implementation</b>	<b>625</b>
	25.1 Syntax of internal functions . . . . .	625
	25.2 Existence test . . . . .	626
	25.3 Comparison . . . . .	626
	25.4 Floating point expression loops . . . . .	628
	25.5 Extrema . . . . .	631
	25.6 Boolean operations . . . . .	632
	25.7 Ternary operator . . . . .	633

<b>26</b>	<b>l3fp-basics Implementation</b>	<b>634</b>
26.1	Addition and subtraction . . . . .	635
26.1.1	Sign, exponent, and special numbers . . . . .	635
26.1.2	Absolute addition . . . . .	637
26.1.3	Absolute subtraction . . . . .	639
26.2	Multiplication . . . . .	644
26.2.1	Signs, and special numbers . . . . .	644
26.2.2	Absolute multiplication . . . . .	645
26.3	Division . . . . .	647
26.3.1	Signs, and special numbers . . . . .	647
26.3.2	Work plan . . . . .	648
26.3.3	Implementing the significand division . . . . .	651
26.4	Square root . . . . .	656
26.5	About the sign . . . . .	663
<b>27</b>	<b>l3fp-extended implementation</b>	<b>664</b>
27.1	Description of fixed point numbers . . . . .	664
27.2	Helpers for numbers with extended precision . . . . .	664
27.3	Multiplying a fixed point number by a short one . . . . .	665
27.4	Dividing a fixed point number by a small integer . . . . .	666
27.5	Adding and subtracting fixed points . . . . .	667
27.6	Multiplying fixed points . . . . .	668
27.7	Combining product and sum of fixed points . . . . .	669
27.8	Extended-precision floating point numbers . . . . .	671
27.9	Dividing extended-precision numbers . . . . .	673
27.10	Inverse square root of extended precision numbers . . . . .	676
27.11	Converting from fixed point to floating point . . . . .	678
<b>28</b>	<b>l3fp-expo implementation</b>	<b>680</b>
28.1	Logarithm . . . . .	681
28.1.1	Work plan . . . . .	681
28.1.2	Some constants . . . . .	681
28.1.3	Sign, exponent, and special numbers . . . . .	681
28.1.4	Absolute ln . . . . .	682
28.2	Exponential . . . . .	689
28.2.1	Sign, exponent, and special numbers . . . . .	689
28.3	Power . . . . .	693
<b>29</b>	<b>l3fp-trig Implementation</b>	<b>699</b>
29.1	Direct trigonometric functions . . . . .	700
29.1.1	Filtering special cases . . . . .	700
29.1.2	Distinguishing small and large arguments . . . . .	703
29.1.3	Small arguments . . . . .	704
29.1.4	Argument reduction in degrees . . . . .	704
29.1.5	Argument reduction in radians . . . . .	706
29.1.6	Computing the power series . . . . .	711
29.2	Inverse trigonometric functions . . . . .	714
29.2.1	Arctangent and arccotangent . . . . .	715
29.2.2	Arcsine and arccosine . . . . .	720
29.2.3	Arccosecant and arcsecant . . . . .	722

<b>30</b>	<b>l3fp-convert implementation</b>	<b>724</b>
30.1	Trimming trailing zeros . . . . .	724
30.2	Scientific notation . . . . .	724
30.3	Decimal representation . . . . .	725
30.4	Token list representation . . . . .	727
30.5	Formatting . . . . .	728
30.6	Convert to dimension or integer . . . . .	728
30.7	Convert from a dimension . . . . .	728
30.8	Use and eval . . . . .	729
30.9	Convert an array of floating points to a comma list . . . . .	730
<b>31</b>	<b>l3fp-random Implementation</b>	<b>730</b>
31.1	Engine support . . . . .	731
31.2	Random floating point . . . . .	732
31.3	Random integer . . . . .	733
<b>32</b>	<b>l3fp-assign implementation</b>	<b>735</b>
32.1	Assigning values . . . . .	735
32.2	Updating values . . . . .	736
32.3	Showing values . . . . .	736
32.4	Some useful constants and scratch variables . . . . .	737
<b>33</b>	<b>l3sort implementation</b>	<b>737</b>
33.1	Variables . . . . .	737
33.2	Finding available \toks registers . . . . .	738
33.3	Protected user commands . . . . .	740
33.4	Merge sort . . . . .	743
33.5	Expandable sorting . . . . .	746
33.6	Messages . . . . .	750
33.7	Deprecated functions . . . . .	752
<b>34</b>	<b>l3tl-analysis implementation</b>	<b>752</b>
34.1	Internal functions . . . . .	752
34.2	Internal format . . . . .	753
34.3	Variables and helper functions . . . . .	753
34.4	Plan of attack . . . . .	755
34.5	Setup . . . . .	756
34.6	First pass . . . . .	757
34.7	Second pass . . . . .	762
34.8	Mapping through the analysis . . . . .	765
34.9	Showing the results . . . . .	765
34.10	Messages . . . . .	768
<b>35</b>	<b>l3tl-build implementation</b>	<b>768</b>
35.1	Variables and helper functions . . . . .	768
35.2	Building the token list . . . . .	769

<b>36</b>	<b>l3regex implementation</b>	<b>770</b>
36.1	Plan of attack	770
36.2	Helpers	772
36.2.1	Constants and variables	773
36.2.2	Testing characters	774
36.2.3	Character property tests	778
36.2.4	Simple character escape	780
36.3	Compiling	785
36.3.1	Variables used when compiling	786
36.3.2	Generic helpers used when compiling	787
36.3.3	Mode	788
36.3.4	Framework	790
36.3.5	Quantifiers	793
36.3.6	Raw characters	795
36.3.7	Character properties	797
36.3.8	Anchoring and simple assertions	798
36.3.9	Character classes	799
36.3.10	Groups and alternations	802
36.3.11	Catcodes and csnames	804
36.3.12	Raw token lists with \u	808
36.3.13	Other	810
36.3.14	Showing regexes	810
36.4	Building	814
36.4.1	Variables used while building	814
36.4.2	Framework	815
36.4.3	Helpers for building an NFA	816
36.4.4	Building classes	818
36.4.5	Building groups	819
36.4.6	Others	824
36.5	Matching	825
36.5.1	Variables used when matching	826
36.5.2	Matching: framework	828
36.5.3	Using states of the NFA	831
36.5.4	Actions when matching	832
36.6	Replacement	834
36.6.1	Variables and helpers used in replacement	834
36.6.2	Query and brace balance	835
36.6.3	Framework	836
36.6.4	Submatches	838
36.6.5	Csnames in replacement	839
36.6.6	Characters in replacement	841
36.6.7	An error	844
36.7	User functions	844
36.7.1	Variables and helpers for user functions	846
36.7.2	Matching	847
36.7.3	Extracting submatches	848
36.7.4	Replacement	851
36.7.5	Storing and showing compiled patterns	853
36.8	Messages	853
36.9	Code for tracing	859

<b>37</b>	<b>l3box implementation</b>	<b>859</b>
37.1	Creating and initialising boxes . . . . .	859
37.2	Measuring and setting box dimensions . . . . .	860
37.3	Using boxes . . . . .	861
37.4	Box conditionals . . . . .	861
37.5	The last box inserted . . . . .	862
37.6	Constant boxes . . . . .	862
37.7	Scratch boxes . . . . .	862
37.8	Viewing box contents . . . . .	862
37.9	Horizontal mode boxes . . . . .	863
37.10	Vertical mode boxes . . . . .	865
37.11	Affine transformations . . . . .	867
37.12	Deprecated functions . . . . .	875
<b>38</b>	<b>l3coffins Implementation</b>	<b>875</b>
38.1	Coffins: data structures and general variables . . . . .	875
38.2	Basic coffin functions . . . . .	877
38.3	Measuring coffins . . . . .	881
38.4	Coffins: handle and pole management . . . . .	881
38.5	Coffins: calculation of pole intersections . . . . .	884
38.6	Aligning and typesetting of coffins . . . . .	887
38.7	Coffin diagnostics . . . . .	891
38.8	Messages . . . . .	896
<b>39</b>	<b>l3color Implementation</b>	<b>897</b>
<b>40</b>	<b>l3sys implementation</b>	<b>898</b>
40.1	The name of the job . . . . .	898
40.2	Time and date . . . . .	898
40.3	Detecting the engine . . . . .	898
40.4	Detecting the output . . . . .	899
<b>41</b>	<b>l3deprecation implementation</b>	<b>900</b>
<b>42</b>	<b>l3candidates Implementation</b>	<b>902</b>
42.1	Additions to l3basics . . . . .	902
42.2	Additions to l3box . . . . .	902
42.3	Viewing part of a box . . . . .	902
42.4	Additions to l3clist . . . . .	904
42.5	Additions to l3coffins . . . . .	905
42.6	Rotating coffins . . . . .	905
42.7	Resizing coffins . . . . .	909
42.8	Additions to l3file . . . . .	912
42.9	Additions to l3int . . . . .	914
42.10	Additions to l3msg . . . . .	915
42.11	Additions to l3prop . . . . .	916
42.12	Additions to l3seq . . . . .	917
42.13	Additions to l3skip . . . . .	919
42.14	Additions to l3sys . . . . .	919
42.15	Additions to l3tl . . . . .	922

42.15.1 Unicode case changing . . . . .	924
42.15.2 Other additions to <code>l3tl</code> . . . . .	945
42.16 Additions to <code>l3tokens</code> . . . . .	947
<b>43 <code>l3luatex</code> implementation . . . . .</b>	<b>948</b>
43.1 Breaking out to Lua . . . . .	948
43.2 Messages . . . . .	949
43.3 Lua functions for internal use . . . . .	949
43.4 Generic Lua and font support . . . . .	952
<b>44 <code>l3drivers</code> Implementation . . . . .</b>	<b>953</b>
44.1 Color support . . . . .	953
44.1.1 <code>dvips-style</code> . . . . .	954
44.1.2 <code>pdfmode</code> . . . . .	954
44.2 <code>dvips</code> driver . . . . .	956
44.2.1 Basics . . . . .	956
44.3 Driver-specific auxiliaries . . . . .	956
44.3.1 Box operations . . . . .	957
44.4 Images . . . . .	958
44.5 Drawing . . . . .	958
44.6 <code>pdfmode</code> driver . . . . .	965
44.6.1 Basics . . . . .	965
44.6.2 Box operations . . . . .	966
44.7 Images . . . . .	967
44.8 <code>dvipdfmx</code> driver . . . . .	969
44.8.1 Basics . . . . .	969
44.8.2 Box operations . . . . .	970
44.9 Images . . . . .	971
44.10 <code>xdvipdfmx</code> driver . . . . .	973
44.11 Images . . . . .	973
44.12 Drawing commands: <code>pdfmode</code> and <code>(x)dvipdfmx</code> . . . . .	974
44.13 Drawing . . . . .	975
44.14 <code>dvisvgm</code> driver . . . . .	979
44.14.1 Basics . . . . .	979
44.15 Driver-specific auxiliaries . . . . .	980
44.15.1 Box operations . . . . .	980
44.16 Images . . . . .	982
44.17 Drawing . . . . .	982

## Part I

# Introduction to expl3 and this document

This document is intended to act as a comprehensive reference manual for the expl3 language. A general guide to the L<sup>A</sup>T<sub>E</sub>X3 programming language is found in [expl3.pdf](#).

## 1 Naming functions and variables

L<sup>A</sup>T<sub>E</sub>X3 does not use `@` as a “letter” for defining internal macros. Instead, the symbols `_` and `:` are used in internal macro names to provide structure. The name of each *function* is divided into logical units using `_`, while `:` separates the *name* of the function from the *argument specifier* (“arg-spec”). This describes the arguments expected by the function. In most cases, each argument is represented by a single letter. The complete list of arg-spec letters for a function is referred to as the *signature* of the function.

Each function name starts with the *module* to which it belongs. Thus apart from a small number of very basic functions, all expl3 function names contain at least one underscore to divide the module name from the descriptive name of the function. For example, all functions concerned with comma lists are in module `clist` and begin `\clist_`.

Every function must include an argument specifier. For functions which take no arguments, this will be blank and the function name will end `:`. Most functions take one or more arguments, and use the following argument specifiers:

- D** The **D** specifier means *do not use*. All of the T<sub>E</sub>X primitives are initially `\let` to a **D** name, and some are then given a second name. Only the kernel team should use anything with a **D** specifier!
- N and n** These mean *no manipulation*, of a single token for **N** and of a set of tokens given in braces for **n**. Both pass the argument through exactly as given. Usually, if you use a single token for an **n** argument, all will be well.
- c** This means *csname*, and indicates that the argument will be turned into a csname before being used. So `\foo:c {ArgumentOne}` will act in the same way as `\foo:N \ArgumentOne`.
- V and v** These mean *value of variable*. The **V** and **v** specifiers are used to get the content of a variable without needing to worry about the underlying T<sub>E</sub>X structure containing the data. A **V** argument will be a single token (similar to **N**), for example `\foo:V \MyVariable`; on the other hand, using **v** a csname is constructed first, and then the value is recovered, for example `\foo:v {MyVariable}`.
- o** This means *expansion once*. In general, the **V** and **v** specifiers are favoured over **o** for recovering stored information. However, **o** is useful for correctly processing information with delimited arguments.
- x** The **x** specifier stands for *exhaustive expansion*: every token in the argument is fully expanded until only unexpandable ones remain. The T<sub>E</sub>X `\edef` primitive carries out this type of expansion. Functions which feature an **x**-type argument are in general *not* expandable, unless specifically noted.



- f** The **f** specifier stands for *full expansion*, and in contrast to **x** stops at the first non-expandable item (reading the argument from left to right) without trying to expand it. For example, when setting a token list variable (a macro used for storage), the sequence

```
\tl_set:Nn \l_my_a_tl { A }
\tl_set:Nn \l_my_b_tl { B }
\tl_set:Nf \l_my_a_tl { \l_my_a_tl \l_my_b_tl }
```

will leave `\l_my_a_tl` with the content `A\l_my_b_tl`, as `A` cannot be expanded and so terminates expansion before `\l_my_b_tl` is considered.

- T and F** For logic tests, there are the branch specifiers **T** (*true*) and **F** (*false*). Both specifiers treat the input in the same way as **n** (no change), but make the logic much easier to see.

- p** The letter **p** indicates *TeX parameters*. Normally this will be used for delimited functions as `expl3` provides better methods for creating simple sequential arguments.

- w** Finally, there is the **w** specifier for *weird* arguments. This covers everything else, but mainly applies to delimited values (where the argument must be terminated by some arbitrary string).

Notice that the argument specifier describes how the argument is processed prior to being passed to the underlying function. For example, `\foo:c` will take its argument, convert it to a control sequence and pass it to `\foo:N`.

Variables are named in a similar manner to functions, but begin with a single letter to define the type of variable:

- c** Constant: global parameters whose value should not be changed.

- g** Parameters whose value should only be set globally.

- l** Parameters whose value should only be set locally.

Each variable name is then build up in a similar way to that of a function, typically starting with the module<sup>1</sup> name and then a descriptive part. Variables end with a short identifier to show the variable type:

**bool** Either true or false.

**box** Box register.

**clist** Comma separated list.

**coffin** a “box with handles” — a higher-level data type for carrying out **box** alignment operations.

**dim** “Rigid” lengths.

**fp** floating-point values;

---

<sup>1</sup>The module names are not used in case of generic scratch registers defined in the data type modules, e.g., the `int` module contains some scratch variables called `\l_tmpa_int`, `\l_tmpb_int`, and so on. In such a case adding the module name up front to denote the module and in the back to indicate the type, as in `\l_int_tmpa_int` would be very unreadable.

**int** Integer-valued count register.

**prop** Property list.

**seq** “Sequence”: a data-type used to implement lists (with access at both ends) and stacks.

**skip** “Rubber” lengths.

**stream** An input or output stream (for reading from or writing to, respectively).

**tl** Token list variables: placeholder for a token list.

## 1.1 Terminological inexactitude

A word of warning. In this document, and others referring to the `expl3` programming modules, we often refer to “variables” and “functions” as if they were actual constructs from a real programming language. In truth, `TeX` is a macro processor, and functions are simply macros that may or may not take arguments and expand to their replacement text. Many of the common variables are *also* macros, and if placed into the input stream will simply expand to their definition as well — a “function” with no arguments and a “token list variable” are in truth one and the same. On the other hand, some “variables” are actually registers that must be initialised and their values set and retrieved with specific functions.

The conventions of the `expl3` code are designed to clearly separate the ideas of “macros that contain data” and “macros that contain code”, and a consistent wrapper is applied to all forms of “data” whether they be macros or actually registers. This means that sometimes we will use phrases like “the function returns a value”, when actually we just mean “the macro expands to something”. Similarly, the term “execute” might be used in place of “expand” or it might refer to the more specific case of “processing in `TeX`’s stomach” (if you are familiar with the `TeXbook` parlance).

If in doubt, please ask; chances are we’ve been hasty in writing certain definitions and need to be told to tighten up our terminology.

## 2 Documentation conventions

This document is typeset with the experimental `l3doc` class; several conventions are used to help describe the features of the code. A number of conventions are used here to make the documentation clearer.

Each group of related functions is given in a box. For a function with a “user” name, this might read:

---

```
\ExplSyntaxOn
\ExplSyntaxOff
```

---

```
\ExplSyntaxOn ... \ExplSyntaxOff
```

The textual description of how the function works would appear here. The syntax of the function is shown in mono-spaced text to the right of the box. In this example, the function takes no arguments and so the name of the function is simply reprinted.

For programming functions, which use `_` and `:` in their name there are a few additional conventions: If two related functions are given with identical names but different argument specifiers, these are termed *variants* of each other, and the latter functions are printed in grey to show this more clearly. They will carry out the same function but will take different types of argument:

---

<code>\seq_new:N</code>	<code>\seq_new:N</code> $\langle sequence \rangle$
<code>\seq_new:c</code>	

---

When a number of variants are described, the arguments are usually illustrated only for the base function. Here,  $\langle sequence \rangle$  indicates that `\seq_new:N` expects the name of a sequence. From the argument specifier, `\seq_new:c` also expects a sequence name, but as a name rather than as a control sequence. Each argument given in the illustration should be described in the following text.

**Fully expandable functions** Some functions are fully expandable, which allows them to be used within an **x**-type argument (in plain  $\text{\TeX}$  terms, inside an `\edef`), as well as within an **f**-type argument. These fully expandable functions are indicated in the documentation by a star:

---

<code>\cs_to_str:N</code> ☆	<code>\cs_to_str:N</code> $\langle cs \rangle$
-----------------------------	--

---

As with other functions, some text should follow which explains how the function works. Usually, only the star will indicate that the function is expandable. In this case, the function expects a  $\langle cs \rangle$ , shorthand for a  $\langle control\ sequence \rangle$ .

**Restricted expandable functions** A few functions are fully expandable but cannot be fully expanded within an **f**-type argument. In this case a hollow star is used to indicate this:

---

<code>\seq_map_function:NN</code> ☆	<code>\seq_map_function:NN</code> $\langle seq \rangle$ $\langle function \rangle$
-------------------------------------	--

---

**Conditional functions** Conditional (**if**) functions are normally defined in three variants, with **T**, **F** and **TF** argument specifiers. This allows them to be used for different “true”/“false” branches, depending on which outcome the conditional is being used to test. To indicate this without repetition, this information is given in a shortened form:

---

<code>\sys_if_engine_xetex:TF</code> ☆	<code>\sys_if_engine_xetex:TF</code> $\{\langle true\ code \rangle\} \{\langle false\ code \rangle\}$
--	---

---

The underlining and italic of **TF** indicates that `\sys_if_engine_xetex:T`, `\sys_if_engine_xetex:F` and `\sys_if_engine_xetex:TF` are all available. Usually, the illustration will use the **TF** variant, and so both  $\langle true\ code \rangle$  and  $\langle false\ code \rangle$  will be shown. The two variant forms **T** and **F** take only  $\langle true\ code \rangle$  and  $\langle false\ code \rangle$ , respectively. Here, the star also shows that this function is expandable. With some minor exceptions, *all* conditional functions in the `expl3` modules should be defined in this way.

Variables, constants and so on are described in a similar manner:

---

<code>\l_tmpa_tl</code>
-------------------------

---

A short piece of text will describe the variable: there is no syntax illustration in this case.

In some cases, the function is similar to one in  $\text{\LaTeX 2}_{\epsilon}$  or plain  $\text{\TeX}$ . In these cases, the text will include an extra “ **$\text{\TeX}$ hackers note**” section:

---

<code>\token_to_str:N</code> ☆	<code>\token_to_str:N</code> $\langle token \rangle$
--------------------------------	--

---

The normal description text.

**$\text{\TeX}$ hackers note:** Detail for the experienced  $\text{\TeX}$  or  $\text{\LaTeX 2}_{\epsilon}$  programmer. In this case, it would point out that this function is the  $\text{\TeX}$  primitive `\string`.

**Changes to behaviour** When new functions are added to `expl3`, the date of first inclusion is given in the documentation. Where the documented behaviour of a function changes after it is first introduced, the date of the update will also be given. This means that the programmer can be sure that any release of `expl3` after the date given will contain the function of interest with expected behaviour as described. Note that changes to code internals, including bug fixes, are not recorded in this way *unless* they impact on the expected behaviour.

### 3 Formal language conventions which apply generally

As this is a formal reference guide for  $\text{\LaTeX}3$  programming, the descriptions of functions are intended to be reasonably “complete”. However, there is also a need to avoid repetition. Formal ideas which apply to general classes of function are therefore summarised here.

For tests which have a `TF` argument specification, the test is evaluated to give a logically `TRUE` or `FALSE` result. Depending on this result, either the  $\langle true\ code \rangle$  or the  $\langle false\ code \rangle$  will be left in the input stream. In the case where the test is expandable, and a predicate (`_p`) variant is available, the logical value determined by the test is left in the input stream: this will typically be part of a larger logical construct.

### 4 $\text{\TeX}$ concepts not supported by $\text{\LaTeX}3$

The  $\text{\TeX}$  concept of an “`\outer`” macro is *not supported* at all by  $\text{\LaTeX}3$ . As such, the functions provided here may break when used on top of  $\text{\LaTeX}2_\epsilon$  if `\outer` tokens are used in the arguments.

## Part II

# The l3bootstrap package

## Bootstrap code

### 1 Using the L<sup>A</sup>T<sub>E</sub>X3 modules

The modules documented in `source3` are designed to be used on top of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> and are loaded all as one with the usual `\usepackage{expl3}` or `\RequirePackage{expl3}` instructions. These modules will also form the basis of the L<sup>A</sup>T<sub>E</sub>X3 format, but work in this area is incomplete and not included in this documentation at present.

As the modules use a coding syntax different from standard L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> it provides a few functions for setting it up.

---

`\ExplSyntaxOn`  
`\ExplSyntaxOff`  
 Updated: 2011-08-13

---

`\ExplSyntaxOn` *<code>* `\ExplSyntaxOff`

The `\ExplSyntaxOn` function switches to a category code régime in which spaces are ignored and in which the colon (:) and underscore (\_) are treated as “letters”, thus allowing access to the names of code functions and variables. Within this environment, ~ is used to input a space. The `\ExplSyntaxOff` reverts to the document category code régime.

---

`\ProvidesExplPackage`  
`\ProvidesExplClass`  
`\ProvidesExplFile`  
 Updated: 2017-03-19

---

`\RequirePackage{expl3}`  
`\ProvidesExplPackage` {*<package>*} {*<date>*} {*<version>*} {*<description>*}

These functions act broadly in the same way as the corresponding L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> kernel functions `\ProvidesPackage`, `\ProvidesClass` and `\ProvidesFile`. However, they also implicitly switch `\ExplSyntaxOn` for the remainder of the code with the file. At the end of the file, `\ExplSyntaxOff` will be called to reverse this. (This is the same concept as L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> provides in turning on `\makeatletter` within package and class code.) The *<date>* should be given in the format *<year>/<month>/<day>*. If the *<version>* is given then it will be prefixed with v in the package identifier line.

---

`\GetIdInfo`  
 Updated: 2012-06-04

---

`\RequirePackage{l3bootstrap}`  
`\GetIdInfo` \$Id: *<SVN info field>* \$ {*<description>*}

Extracts all information from a SVN field. Spaces are not ignored in these fields. The information pieces are stored in separate control sequences with `\ExplFileName` for the part of the file name leading up to the period, `\ExplFileDate` for date, `\ExplFileVersion` for version and `\ExplFileDescription` for the description.

To summarize: Every single package using this syntax should identify itself using one of the above methods. Special care is taken so that every package or class file loaded with `\RequirePackage` or similar are loaded with usual L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> category codes and the L<sup>A</sup>T<sub>E</sub>X3 category code scheme is reloaded when needed afterwards. See implementation for details. If you use the `\GetIdInfo` command you can use the information when loading a package with

```
\ProvidesExplPackage{\ExplFileName}
  {\ExplFileDate}{\ExplFileVersion}{\ExplFileDescription}
```

## 1.1 Internal functions and variables

---

\l\_kernel\_expl\_bool

A boolean which records the current code syntax status: **true** if currently inside a code environment. This variable should only be set by `\ExplSyntaxOn/\ExplSyntaxOff`.

## Part III

# The l3names package

## Namespace for primitives

### 1 Setting up the L<sup>A</sup>T<sub>E</sub>X3 programming language

This module is at the core of the L<sup>A</sup>T<sub>E</sub>X3 programming language. It performs the following tasks:

- defines new names for all T<sub>E</sub>X primitives;
- switches to the category code régime for programming;
- provides support settings for building the code as a T<sub>E</sub>X format.

This module is entirely dedicated to primitives, which should not be used directly within L<sup>A</sup>T<sub>E</sub>X3 code (outside of “kernel-level” code). As such, the primitives are not documented here: *The T<sub>E</sub>Xbook*, *T<sub>E</sub>X by Topic* and the manuals for pdfT<sub>E</sub>X, X<sub>Y</sub>T<sub>E</sub>X and LuaT<sub>E</sub>X should be consulted for details of the primitives. These are named based on the engine which first introduced them:

`\tex_...` Introduced by T<sub>E</sub>X itself;  
`\etex_...` Introduced by the  $\epsilon$ -T<sub>E</sub>X extensions;  
`\pdftex_...` Introduced by pdfT<sub>E</sub>X;  
`\xetex_...` Introduced by X<sub>Y</sub>T<sub>E</sub>X;  
`\luatex_...` Introduced by LuaT<sub>E</sub>X;  
`\utex_...` Introduced by X<sub>Y</sub>T<sub>E</sub>X and LuaT<sub>E</sub>X;  
`\ptex_...` Introduced by pT<sub>E</sub>X;  
`\uptex_...` Introduced by upT<sub>E</sub>X.

## Part IV

# The l3basics package

## Basic definitions

As the name suggest this package holds some basic definitions which are needed by most or all other packages in this set.

Here we describe those functions that are used all over the place. With that we mean functions dealing with the construction and testing of control sequences. Furthermore the basic parts of conditional processing are covered; conditional processing dealing with specific data types is described in the modules specific for the respective data types.

### 1 No operation functions

---

**`\prg_do_nothing:`** ★**`\prg_do_nothing:`**

An expandable function which does nothing at all: leaves nothing in the input stream after a single expansion.

---

**`\scan_stop:`****`\scan_stop:`**

A non-expandable function which does nothing. Does not vanish on expansion but produces no typeset output.

### 2 Grouping material

---

**`\group_begin:`**  
**`\group_end:`****`\group_begin:`**  
**`\group_end:`**

These functions begin and end a group for definition purposes. Assignments are local to groups unless carried out in a global manner. (A small number of exceptions to this rule will be noted as necessary elsewhere in this document.) Each **`\group_begin:`** must be matched by a **`\group_end:`**, although this does not have to occur within the same function. Indeed, it is often necessary to start a group within one function and finish it within another, for example when seeking to use non-standard category codes.

---

**`\group_insert_after:N`****`\group_insert_after:N`** *⟨token⟩*

Adds *⟨token⟩* to the list of *⟨tokens⟩* to be inserted when the current group level ends. The list of *⟨tokens⟩* to be inserted is empty at the beginning of a group: multiple applications of **`\group_insert_after:N`** may be used to build the inserted list one *⟨token⟩* at a time. The current group level may be closed by a **`\group_end:`** function or by a token with category code 2 (close-group), namely a `}` if standard category codes apply.



### 3 Control sequences and functions

As  $\text{\TeX}$  is a macro language, creating new functions means creating macros. At point of use, a function is replaced by the replacement text (“code”) in which each parameter in the code ( $\#1$ ,  $\#2$ , *etc.*) is replaced the appropriate arguments absorbed by the function. In the following, *code* is therefore used as a shorthand for “replacement text”.

Functions which are not “protected” are fully expanded inside an  $\mathbf{x}$  expansion. In contrast, “protected” functions are not expanded within  $\mathbf{x}$  expansions.

#### 3.1 Defining functions

Functions can be created with no requirement that they are declared first (in contrast to variables, which must always be declared). Declaring a function before setting up the code means that the name chosen is checked and an error raised if it is already in use. The name of a function can be checked at the point of definition using the `\cs_new...` functions: this is recommended for all functions which are defined for the first time.

There are three ways to define new functions. All classes define a function to expand to the substitution text. Within the substitution text the actual parameters are substituted for the formal parameters ( $\#1$ ,  $\#2$ , ...).

**new** Create a new function with the **new** scope, such as `\cs_new:Npn`. The definition is global and results in an error if it is already defined.

**set** Create a new function with the **set** scope, such as `\cs_set:Npn`. The definition is restricted to the current  $\text{\TeX}$  group and does not result in an error if the function is already defined.

**gset** Create a new function with the **gset** scope, such as `\cs_gset:Npn`. The definition is global and does not result in an error if the function is already defined.

Within each set of scope there are different ways to define a function. The differences depend on restrictions on the actual parameters and the expandability of the resulting function.

**nopar** Create a new function with the **nopar** restriction, such as `\cs_set_nopar:Npn`. The parameter may not contain `\par` tokens.

**protected** Create a new function with the **protected** restriction, such as `\cs_set_protected:Npn`. The parameter may contain `\par` tokens but the function will not expand within an  $\mathbf{x}$ -type expansion.

Finally, the functions in Subsections 3.2 and 3.3 are primarily meant to define *base functions* only. Base functions can only have the following argument specifiers:

**N and n** No manipulation.

**T and F** Functionally equivalent to **n** (you are actually encouraged to use the family of `\prg_new_conditional:` functions described in Section 1).

**p and w** These are special cases.

The `\cs_new:` functions below (and friends) do not stop you from using other argument specifiers in your function names, but they do not handle expansion for you. You should define the base function and then use `\cs_generate_variant:Nn` to generate custom variants as described in Section 2.

### 3.2 Defining new functions using parameter text

---

<code>\cs_new:Npn</code>	<code>\cs_new:Npn &lt;function&gt; &lt;parameters&gt; {&lt;code&gt;}</code>
<code>\cs_new:cpn</code>	Creates <code>&lt;function&gt;</code> to expand to <code>&lt;code&gt;</code> as replacement text. Within the <code>&lt;code&gt;</code> , the
<code>\cs_new:Npx</code>	<code>&lt;parameters&gt;</code> (#1, #2, etc.) will be replaced by those absorbed by the function. The
<code>\cs_new:cpx</code>	definition is global and an error results if the <code>&lt;function&gt;</code> is already defined.

---



---

<code>\cs_new_nopar:Npn</code>	<code>\cs_new_nopar:Npn &lt;function&gt; &lt;parameters&gt; {&lt;code&gt;}</code>
<code>\cs_new_nopar:cpn</code>	Creates <code>&lt;function&gt;</code> to expand to <code>&lt;code&gt;</code> as replacement text. Within the <code>&lt;code&gt;</code> , the
<code>\cs_new_nopar:Npx</code>	<code>&lt;parameters&gt;</code> (#1, #2, etc.) will be replaced by those absorbed by the function. When the
<code>\cs_new_nopar:cpx</code>	<code>&lt;function&gt;</code> is used the <code>&lt;parameters&gt;</code> absorbed cannot contain <code>\par</code> tokens. The definition

---

is global and an error results if the `<function>` is already defined.

---

<code>\cs_new_protected:Npn</code>	<code>\cs_new_protected:Npn &lt;function&gt; &lt;parameters&gt; {&lt;code&gt;}</code>
<code>\cs_new_protected:cpn</code>	Creates <code>&lt;function&gt;</code> to expand to <code>&lt;code&gt;</code> as replacement text. Within the <code>&lt;code&gt;</code> , the
<code>\cs_new_protected:Npx</code>	<code>&lt;parameters&gt;</code> (#1, #2, etc.) will be replaced by those absorbed by the function. The
<code>\cs_new_protected:cpx</code>	<code>&lt;function&gt;</code> will not expand within an x-type argument. The definition is global and an

---

error results if the `<function>` is already defined.

---

<code>\cs_new_protected_nopar:Npn</code>	<code>\cs_new_protected_nopar:Npn &lt;function&gt; &lt;parameters&gt; {&lt;code&gt;}</code>
<code>\cs_new_protected_nopar:cpn</code>	
<code>\cs_new_protected_nopar:Npx</code>	
<code>\cs_new_protected_nopar:cpx</code>	

---

Creates `<function>` to expand to `<code>` as replacement text. Within the `<code>`, the `<parameters>` (#1, #2, etc.) will be replaced by those absorbed by the function. When the `<function>` is used the `<parameters>` absorbed cannot contain `\par` tokens. The `<function>` will not expand within an x-type argument. The definition is global and an error results if the `<function>` is already defined.

---

<code>\cs_set:Npn</code>	<code>\cs_set:Npn &lt;function&gt; &lt;parameters&gt; {&lt;code&gt;}</code>
<code>\cs_set:cpn</code>	Sets <code>&lt;function&gt;</code> to expand to <code>&lt;code&gt;</code> as replacement text. Within the <code>&lt;code&gt;</code> , the
<code>\cs_set:Npx</code>	<code>&lt;parameters&gt;</code> (#1, #2, etc.) will be replaced by those absorbed by the function. The
<code>\cs_set:cpx</code>	assignment of a meaning to the <code>&lt;function&gt;</code> is restricted to the current $\text{\TeX}$ group level.

---



---

<code>\cs_set_nopar:Npn</code>	<code>\cs_set_nopar:Npn &lt;function&gt; &lt;parameters&gt; {&lt;code&gt;}</code>
<code>\cs_set_nopar:cpn</code>	Sets <code>&lt;function&gt;</code> to expand to <code>&lt;code&gt;</code> as replacement text. Within the <code>&lt;code&gt;</code> , the
<code>\cs_set_nopar:Npx</code>	<code>&lt;parameters&gt;</code> (#1, #2, etc.) will be replaced by those absorbed by the function. When the
<code>\cs_set_nopar:cpx</code>	<code>&lt;function&gt;</code> is used the <code>&lt;parameters&gt;</code> absorbed cannot contain <code>\par</code> tokens. The assignment

---

of a meaning to the `<function>` is restricted to the current  $\text{\TeX}$  group level.

---

<code>\cs_set_protected:Npn</code>	<code>\cs_set_protected:Npn &lt;function&gt; &lt;parameters&gt; {&lt;code&gt;}</code>
<code>\cs_set_protected:cpn</code>	Sets <code>&lt;function&gt;</code> to expand to <code>&lt;code&gt;</code> as replacement text. Within the <code>&lt;code&gt;</code> , the
<code>\cs_set_protected:Npx</code>	<code>&lt;parameters&gt;</code> (#1, #2, etc.) will be replaced by those absorbed by the function. The
<code>\cs_set_protected:cpx</code>	assignment of a meaning to the <code>&lt;function&gt;</code> is restricted to the current $\text{\TeX}$ group level.

---

The `<function>` will not expand within an x-type argument.

---

<code>\cs_set_protected_nopar:Npn</code>	<code>\cs_set_protected_nopar:Npn &lt;function&gt; &lt;parameters&gt; {&lt;code&gt;}</code>
<code>\cs_set_protected_nopar:cpn</code>	
<code>\cs_set_protected_nopar:Npx</code>	
<code>\cs_set_protected_nopar:cpx</code>	

---

Sets  $\langle function \rangle$  to expand to  $\langle code \rangle$  as replacement text. Within the  $\langle code \rangle$ , the  $\langle parameters \rangle$  ( $\#1$ ,  $\#2$ , etc.) will be replaced by those absorbed by the function. When the  $\langle function \rangle$  is used the  $\langle parameters \rangle$  absorbed cannot contain `\par` tokens. The assignment of a meaning to the  $\langle function \rangle$  is restricted to the current T<sub>E</sub>X group level. The  $\langle function \rangle$  will not expand within an x-type argument.

---

<code>\cs_gset:Npn</code>	<code>\cs_gset:Npn &lt;function&gt; &lt;parameters&gt; {&lt;code&gt;}</code>
<code>\cs_gset:cpn</code>	
<code>\cs_gset:Npx</code>	
<code>\cs_gset:cpx</code>	

---

Globally sets  $\langle function \rangle$  to expand to  $\langle code \rangle$  as replacement text. Within the  $\langle code \rangle$ , the  $\langle parameters \rangle$  ( $\#1$ ,  $\#2$ , etc.) will be replaced by those absorbed by the function. The assignment of a meaning to the  $\langle function \rangle$  is *not* restricted to the current T<sub>E</sub>X group level: the assignment is global.

---

<code>\cs_gset_nopar:Npn</code>	<code>\cs_gset_nopar:Npn &lt;function&gt; &lt;parameters&gt; {&lt;code&gt;}</code>
<code>\cs_gset_nopar:cpn</code>	
<code>\cs_gset_nopar:Npx</code>	
<code>\cs_gset_nopar:cpx</code>	

---

Globally sets  $\langle function \rangle$  to expand to  $\langle code \rangle$  as replacement text. Within the  $\langle code \rangle$ , the  $\langle parameters \rangle$  ( $\#1$ ,  $\#2$ , etc.) will be replaced by those absorbed by the function. When the  $\langle function \rangle$  is used the  $\langle parameters \rangle$  absorbed cannot contain `\par` tokens. The assignment of a meaning to the  $\langle function \rangle$  is *not* restricted to the current T<sub>E</sub>X group level: the assignment is global.

---

<code>\cs_gset_protected:Npn</code>	<code>\cs_gset_protected:Npn &lt;function&gt; &lt;parameters&gt; {&lt;code&gt;}</code>
<code>\cs_gset_protected:cpn</code>	
<code>\cs_gset_protected:Npx</code>	
<code>\cs_gset_protected:cpx</code>	

---

Globally sets  $\langle function \rangle$  to expand to  $\langle code \rangle$  as replacement text. Within the  $\langle code \rangle$ , the  $\langle parameters \rangle$  ( $\#1$ ,  $\#2$ , etc.) will be replaced by those absorbed by the function. The assignment of a meaning to the  $\langle function \rangle$  is *not* restricted to the current T<sub>E</sub>X group level: the assignment is global. The  $\langle function \rangle$  will not expand within an x-type argument.

---

<code>\cs_gset_protected_nopar:Npn</code>	<code>\cs_gset_protected_nopar:Npn &lt;function&gt; &lt;parameters&gt; {&lt;code&gt;}</code>
<code>\cs_gset_protected_nopar:cpn</code>	
<code>\cs_gset_protected_nopar:Npx</code>	
<code>\cs_gset_protected_nopar:cpx</code>	

---

Globally sets  $\langle function \rangle$  to expand to  $\langle code \rangle$  as replacement text. Within the  $\langle code \rangle$ , the  $\langle parameters \rangle$  ( $\#1$ ,  $\#2$ , etc.) will be replaced by those absorbed by the function. When the  $\langle function \rangle$  is used the  $\langle parameters \rangle$  absorbed cannot contain `\par` tokens. The assignment of a meaning to the  $\langle function \rangle$  is *not* restricted to the current T<sub>E</sub>X group level: the assignment is global. The  $\langle function \rangle$  will not expand within an x-type argument.

### 3.3 Defining new functions using the signature

---

<code>\cs_new:Nn</code>	<code>\cs_new:Nn &lt;function&gt; {&lt;code&gt;}</code>
<code>\cs_new:(cn Nx cx)</code>	

---

Creates  $\langle function \rangle$  to expand to  $\langle code \rangle$  as replacement text. Within the  $\langle code \rangle$ , the number of  $\langle parameters \rangle$  is detected automatically from the function signature. These  $\langle parameters \rangle$  ( $\#1$ ,  $\#2$ , etc.) will be replaced by those absorbed by the function. The definition is global and an error results if the  $\langle function \rangle$  is already defined.

---

`\cs_new_nopar:Nn`  
`\cs_new_nopar:(cn|Nx|cx)`

---

`\cs_new_nopar:Nn <function> {<code>}`

Creates  $\langle function \rangle$  to expand to  $\langle code \rangle$  as replacement text. Within the  $\langle code \rangle$ , the number of  $\langle parameters \rangle$  is detected automatically from the function signature. These  $\langle parameters \rangle$  ( $\#1$ ,  $\#2$ , *etc.*) will be replaced by those absorbed by the function. When the  $\langle function \rangle$  is used the  $\langle parameters \rangle$  absorbed cannot contain `\par` tokens. The definition is global and an error results if the  $\langle function \rangle$  is already defined.

---

`\cs_new_protected:Nn`  
`\cs_new_protected:(cn|Nx|cx)`

---

`\cs_new_protected:Nn <function> {<code>}`

Creates  $\langle function \rangle$  to expand to  $\langle code \rangle$  as replacement text. Within the  $\langle code \rangle$ , the number of  $\langle parameters \rangle$  is detected automatically from the function signature. These  $\langle parameters \rangle$  ( $\#1$ ,  $\#2$ , *etc.*) will be replaced by those absorbed by the function. The  $\langle function \rangle$  will not expand within an x-type argument. The definition is global and an error results if the  $\langle function \rangle$  is already defined.

---

`\cs_new_protected_nopar:Nn`  
`\cs_new_protected_nopar:(cn|Nx|cx)`

---

`\cs_new_protected_nopar:Nn <function> {<code>}`

Creates  $\langle function \rangle$  to expand to  $\langle code \rangle$  as replacement text. Within the  $\langle code \rangle$ , the number of  $\langle parameters \rangle$  is detected automatically from the function signature. These  $\langle parameters \rangle$  ( $\#1$ ,  $\#2$ , *etc.*) will be replaced by those absorbed by the function. When the  $\langle function \rangle$  is used the  $\langle parameters \rangle$  absorbed cannot contain `\par` tokens. The  $\langle function \rangle$  will not expand within an x-type argument. The definition is global and an error results if the  $\langle function \rangle$  is already defined.

---

`\cs_set:Nn`  
`\cs_set:(cn|Nx|cx)`

---

`\cs_set:Nn <function> {<code>}`

Sets  $\langle function \rangle$  to expand to  $\langle code \rangle$  as replacement text. Within the  $\langle code \rangle$ , the number of  $\langle parameters \rangle$  is detected automatically from the function signature. These  $\langle parameters \rangle$  ( $\#1$ ,  $\#2$ , *etc.*) will be replaced by those absorbed by the function. The assignment of a meaning to the  $\langle function \rangle$  is restricted to the current  $\text{\TeX}$  group level.

---

`\cs_set_nopar:Nn`  
`\cs_set_nopar:(cn|Nx|cx)`

---

`\cs_set_nopar:Nn <function> {<code>}`

Sets  $\langle function \rangle$  to expand to  $\langle code \rangle$  as replacement text. Within the  $\langle code \rangle$ , the number of  $\langle parameters \rangle$  is detected automatically from the function signature. These  $\langle parameters \rangle$  ( $\#1$ ,  $\#2$ , *etc.*) will be replaced by those absorbed by the function. When the  $\langle function \rangle$  is used the  $\langle parameters \rangle$  absorbed cannot contain `\par` tokens. The assignment of a meaning to the  $\langle function \rangle$  is restricted to the current  $\text{\TeX}$  group level.

---

`\cs_set_protected:Nn`  
`\cs_set_protected:(cn|Nx|cx)`

---

`\cs_set_protected:Nn <function> {<code>}`

Sets  $\langle function \rangle$  to expand to  $\langle code \rangle$  as replacement text. Within the  $\langle code \rangle$ , the number of  $\langle parameters \rangle$  is detected automatically from the function signature. These  $\langle parameters \rangle$  ( $\#1$ ,  $\#2$ , *etc.*) will be replaced by those absorbed by the function. The  $\langle function \rangle$  will not expand within an x-type argument. The assignment of a meaning to the  $\langle function \rangle$  is restricted to the current  $\text{\TeX}$  group level.

---

<code>\cs_set_protected_nopar:Nn</code>	<code>\cs_set_protected_nopar:Nn &lt;function&gt; {&lt;code&gt;}</code>
<code>\cs_set_protected_nopar:(cn Nx cx)</code>	

---

Sets  $\langle function \rangle$  to expand to  $\langle code \rangle$  as replacement text. Within the  $\langle code \rangle$ , the number of  $\langle parameters \rangle$  is detected automatically from the function signature. These  $\langle parameters \rangle$  ( $\#1$ ,  $\#2$ , *etc.*) will be replaced by those absorbed by the function. When the  $\langle function \rangle$  is used the  $\langle parameters \rangle$  absorbed cannot contain `\par` tokens. The  $\langle function \rangle$  will not expand within an x-type argument. The assignment of a meaning to the  $\langle function \rangle$  is restricted to the current TeX group level.

---

<code>\cs_gset:Nn</code>	<code>\cs_gset:Nn &lt;function&gt; {&lt;code&gt;}</code>
<code>\cs_gset:(cn Nx cx)</code>	

---

Sets  $\langle function \rangle$  to expand to  $\langle code \rangle$  as replacement text. Within the  $\langle code \rangle$ , the number of  $\langle parameters \rangle$  is detected automatically from the function signature. These  $\langle parameters \rangle$  ( $\#1$ ,  $\#2$ , *etc.*) will be replaced by those absorbed by the function. The assignment of a meaning to the  $\langle function \rangle$  is global.

---

<code>\cs_gset_nopar:Nn</code>	<code>\cs_gset_nopar:Nn &lt;function&gt; {&lt;code&gt;}</code>
<code>\cs_gset_nopar:(cn Nx cx)</code>	

---

Sets  $\langle function \rangle$  to expand to  $\langle code \rangle$  as replacement text. Within the  $\langle code \rangle$ , the number of  $\langle parameters \rangle$  is detected automatically from the function signature. These  $\langle parameters \rangle$  ( $\#1$ ,  $\#2$ , *etc.*) will be replaced by those absorbed by the function. When the  $\langle function \rangle$  is used the  $\langle parameters \rangle$  absorbed cannot contain `\par` tokens. The assignment of a meaning to the  $\langle function \rangle$  is global.

---

<code>\cs_gset_protected:Nn</code>	<code>\cs_gset_protected:Nn &lt;function&gt; {&lt;code&gt;}</code>
<code>\cs_gset_protected:(cn Nx cx)</code>	

---

Sets  $\langle function \rangle$  to expand to  $\langle code \rangle$  as replacement text. Within the  $\langle code \rangle$ , the number of  $\langle parameters \rangle$  is detected automatically from the function signature. These  $\langle parameters \rangle$  ( $\#1$ ,  $\#2$ , *etc.*) will be replaced by those absorbed by the function. The  $\langle function \rangle$  will not expand within an x-type argument. The assignment of a meaning to the  $\langle function \rangle$  is global.

---

<code>\cs_gset_protected_nopar:Nn</code>	<code>\cs_gset_protected_nopar:Nn &lt;function&gt; {&lt;code&gt;}</code>
<code>\cs_gset_protected_nopar:(cn Nx cx)</code>	

---

Sets  $\langle function \rangle$  to expand to  $\langle code \rangle$  as replacement text. Within the  $\langle code \rangle$ , the number of  $\langle parameters \rangle$  is detected automatically from the function signature. These  $\langle parameters \rangle$  ( $\#1$ ,  $\#2$ , *etc.*) will be replaced by those absorbed by the function. When the  $\langle function \rangle$  is used the  $\langle parameters \rangle$  absorbed cannot contain `\par` tokens. The  $\langle function \rangle$  will not expand within an x-type argument. The assignment of a meaning to the  $\langle function \rangle$  is global.

---

<code>\cs_generate_from_arg_count:NNnn</code>	<code>\cs_generate_from_arg_count:NNnn &lt;function&gt; &lt;creator&gt; &lt;number&gt;</code>
<code>\cs_generate_from_arg_count:(cNnn Ncnn)</code>	<code>&lt;code&gt;</code>

---

Updated: 2012-01-14

---

Uses the  $\langle creator \rangle$  function (which should have signature  $\text{Npn}$ , for example `\cs_new:Npn`) to define a  $\langle function \rangle$  which takes  $\langle number \rangle$  arguments and has  $\langle code \rangle$  as replacement text. The  $\langle number \rangle$  of arguments is an integer expression, evaluated as detailed for `\int_eval:n`.

### 3.4 Copying control sequences

Control sequences (not just functions as defined above) can be set to have the same meaning using the functions described here. Making two control sequences equivalent means that the second control sequence is a *copy* of the first (rather than a pointer to it). Thus the old and new control sequence are not tied together: changes to one are not reflected in the other.

In the following text “cs” is used as an abbreviation for “control sequence”.

---

```
\cs_new_eq:NN
\cs_new_eq:(Nc|cN|cc)
```

---

```
\cs_new_eq:NN <cs1> <cs2>
\cs_new_eq:NN <cs1> <token>
```

Globally creates  $\langle control\ sequence_1 \rangle$  and sets it to have the same meaning as  $\langle control\ sequence_2 \rangle$  or  $\langle token \rangle$ . The second control sequence may subsequently be altered without affecting the copy.

---

```
\cs_set_eq:NN
\cs_set_eq:(Nc|cN|cc)
```

---

```
\cs_set_eq:NN <cs1> <cs2>
\cs_set_eq:NN <cs1> <token>
```

Sets  $\langle control\ sequence_1 \rangle$  to have the same meaning as  $\langle control\ sequence_2 \rangle$  (or  $\langle token \rangle$ ). The second control sequence may subsequently be altered without affecting the copy. The assignment of a meaning to the  $\langle control\ sequence_1 \rangle$  is restricted to the current  $\text{\TeX}$  group level.

---

```
\cs_gset_eq:NN
\cs_gset_eq:(Nc|cN|cc)
```

---

```
\cs_gset_eq:NN <cs1> <cs2>
\cs_gset_eq:NN <cs1> <token>
```

Globally sets  $\langle control\ sequence_1 \rangle$  to have the same meaning as  $\langle control\ sequence_2 \rangle$  (or  $\langle token \rangle$ ). The second control sequence may subsequently be altered without affecting the copy. The assignment of a meaning to the  $\langle control\ sequence_1 \rangle$  is *not* restricted to the current  $\text{\TeX}$  group level: the assignment is global.

### 3.5 Deleting control sequences

There are occasions where control sequences need to be deleted. This is handled in a very simple manner.

---

```
\cs_undefine:N
\cs_undefine:c
```

---

Updated: 2011-09-15

---

```
\cs_undefine:N <control\ sequence>
```

Sets  $\langle control\ sequence \rangle$  to be globally undefined.

### 3.6 Showing control sequences

---

```
\cs_meaning:N ★
\cs_meaning:c ★
```

---

Updated: 2011-12-22

---

```
\cs_meaning:N <control\ sequence>
```

This function expands to the *meaning* of the  $\langle control\ sequence \rangle$  control sequence. For a macro, this includes the  $\langle replacement\ text \rangle$ .

**$\text{\TeX}$ hackers note:** This is  $\text{\TeX}$ ’s `\meaning` primitive. The `c` variant correctly reports undefined arguments.

---

`\cs_show:N`  
`\cs_show:c`  


---

Updated: 2017-02-14

`\cs_show:N`  $\langle control\ sequence \rangle$   
Displays the definition of the  $\langle control\ sequence \rangle$  on the terminal.

**T<sub>E</sub>Xhackers note:** This is similar to the T<sub>E</sub>X primitive `\show`, wrapped to a fixed number of characters per line.

---

`\cs_log:N`  
`\cs_log:c`  


---

New: 2014-08-22  
Updated: 2017-02-14

`\cs_log:N`  $\langle control\ sequence \rangle$   
Writes the definition of the  $\langle control\ sequence \rangle$  in the log file. See also `\cs_show:N` which displays the result in the terminal.

### 3.7 Converting to and from control sequences

---

`\use:c` ★

`\use:c`  $\{\langle control\ sequence\ name \rangle\}$

Converts the given  $\langle control\ sequence\ name \rangle$  into a single control sequence token. This process requires two expansions. The content for  $\langle control\ sequence\ name \rangle$  may be literal material or from other expandable functions. The  $\langle control\ sequence\ name \rangle$  must, when fully expanded, consist of character tokens which are not active: typically of category code 10 (space), 11 (letter) or 12 (other), or a mixture of these.

As an example of the `\use:c` function, both

`\use:c { a b c }`

and

`\tl_new:N \l_my_tl`  
`\tl_set:Nn \l_my_tl { a b c }`  
`\use:c { \tl_use:N \l_my_tl }`

would be equivalent to

`\abc`

after two expansions of `\use:c`.

---

`\cs_if_exist_use:N` ★  
`\cs_if_exist_use:c` ★  
`\cs_if_exist_use:NTF` ★  
`\cs_if_exist_use:cTF` ★  


---

New: 2012-11-10

`\cs_if_exist_use:N`  $\langle control\ sequence \rangle$   
`\cs_if_exist_use:NTF`  $\langle control\ sequence \rangle$   $\{\langle true\ code \rangle\}$   $\{\langle false\ code \rangle\}$

Tests whether the  $\langle control\ sequence \rangle$  is currently defined (whether as a function or another control sequence type), and if it is inserts the  $\langle control\ sequence \rangle$  into the input stream followed by the  $\langle true\ code \rangle$ . Otherwise the  $\langle false\ code \rangle$  is used.

---

`\cs:w` ★  
`\cs_end:` ★  


---

`\cs:w`  $\langle control\ sequence\ name \rangle$  `\cs_end:`

Converts the given  $\langle control\ sequence\ name \rangle$  into a single control sequence token. This process requires one expansion. The content for  $\langle control\ sequence\ name \rangle$  may be literal material or from other expandable functions. The  $\langle control\ sequence\ name \rangle$  must, when fully expanded, consist of character tokens which are not active: typically of category code 10 (space), 11 (letter) or 12 (other), or a mixture of these.

**T<sub>E</sub>Xhackers note:** These are the T<sub>E</sub>X primitives `\csname` and `\endcsname`.

As an example of the `\cs:w` and `\cs_end:` functions, both

```
\cs:w a b c \cs_end:
```

and

```
\tl_new:N \l_my_tl
\tl_set:Nn \l_my_tl { a b c }
\cs:w \tl_use:N \l_my_tl \cs_end:
```

would be equivalent to

```
\abc
```

after one expansion of `\cs:w`.

---

```
\cs_to_str:N ★ \cs_to_str:N <control sequence>
```

---

Converts the given *<control sequence>* into a series of characters with category code 12 (other), except spaces, of category code 10. The result does *not* include the current escape token, contrarily to `\token_to_str:N`. Full expansion of this function requires exactly 2 expansion steps, and so an x-type expansion, or two o-type expansions are required to convert the *<control sequence>* to a sequence of characters in the input stream. In most cases, an f-expansion is correct as well, but this loses a space at the start of the result.

## 4 Using or removing tokens and arguments

Tokens in the input can be read and used or read and discarded. If one or more tokens are wrapped in braces then when absorbing them the outer set is removed. At the same time, the category code of each token is set when the token is read by a function (if it is read more than once, the category code is determined by the situation in force when first function absorbs the token).

---

```
\use:n ★ \use:n {<group1>}
\use:nn ★ \use:nn {<group1>} {<group2>}
\use:nnn ★ \use:nnn {<group1>} {<group2>} {<group3>}
\use:nnnn ★ \use:nnnn {<group1>} {<group2>} {<group3>} {<group4>}
```

---

As illustrated, these functions absorb between one and four arguments, as indicated by the argument specifier. The braces surrounding each argument are removed and the remaining tokens are left in the input stream. The category code of these tokens is also fixed by this process (if it has not already been by some other absorption). All of these functions require only a single expansion to operate, so that one expansion of

```
\use:nn { abc } { { def } }
```

results in the input stream containing

```
abc { def }
```

*i.e.* only the outer braces are removed.



---

<code>\use_i:nn</code>	★	<code>\use_i:nn {⟨arg<sub>1</sub>⟩} {⟨arg<sub>2</sub>⟩}</code>
------------------------	---	--

---

<code>\use_ii:nn</code>	★	These functions absorb two arguments from the input stream. The function <code>\use_i:nn</code> discards the second argument, and leaves the content of the first argument in the input stream. <code>\use_ii:nn</code> discards the first argument and leaves the content of the second argument in the input stream. The category code of these tokens is also fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect.
-------------------------	---	--

---

<code>\use_i:nnn</code>	★	<code>\use_i:nnn {⟨arg<sub>1</sub>⟩} {⟨arg<sub>2</sub>⟩} {⟨arg<sub>3</sub>⟩}</code>
-------------------------	---	---

---

<code>\use_ii:nnn</code>	★	These functions absorb three arguments from the input stream. The function <code>\use_i:nnn</code> discards the second and third arguments, and leaves the content of the first argument in the input stream. <code>\use_ii:nnn</code> and <code>\use_iii:nnn</code> work similarly, leaving the content of second or third arguments in the input stream, respectively. The category code of these tokens is also fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect.
<code>\use_iii:nnn</code>	★	

---

<code>\use_i:nnnn</code>	★	<code>\use_i:nnnn {⟨arg<sub>1</sub>⟩} {⟨arg<sub>2</sub>⟩} {⟨arg<sub>3</sub>⟩} {⟨arg<sub>4</sub>⟩}</code>
--------------------------	---	--

---

<code>\use_ii:nnnn</code>	★	These functions absorb four arguments from the input stream. The function <code>\use_i:nnnn</code> discards the second, third and fourth arguments, and leaves the content of the first argument in the input stream. <code>\use_ii:nnnn</code> , <code>\use_iii:nnnn</code> and <code>\use_iv:nnnn</code> work similarly, leaving the content of second, third or fourth arguments in the input stream, respectively. The category code of these tokens is also fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect.
<code>\use_iii:nnnn</code>	★	
<code>\use_iv:nnnn</code>	★	

---

<code>\use_i_ii:nnn</code>	★	<code>\use_i_ii:nnn {⟨arg<sub>1</sub>⟩} {⟨arg<sub>2</sub>⟩} {⟨arg<sub>3</sub>⟩}</code>
----------------------------	---	--

---

This function absorbs three arguments and leaves the content of the first and second in the input stream. The category code of these tokens is also fixed (if it has not already been by some other absorption). A single expansion is needed for the function to take effect. An example:

`\use_i_ii:nnn { abc } { { def } } { ghi }`

results in the input stream containing

`abc { def }`

*i.e.* the outer braces are removed and the third group is removed.

---

<code>\use_none:n</code>	★	<code>\use_none:n {⟨group<sub>1</sub>⟩}</code>
--------------------------	---	--

---

<code>\use_none:nn</code>	★	These functions absorb between one and nine groups from the input stream, leaving nothing on the resulting input stream. These functions work after a single expansion. One or more of the <code>n</code> arguments may be an unbraced single token ( <i>i.e.</i> an <code>N</code> argument).
<code>\use_none:nnn</code>	★	
<code>\use_none:nnnn</code>	★	
<code>\use_none:nnnnn</code>	★	
<code>\use_none:nnnnnn</code>	★	

---

<code>\use_none:nnnnnnn</code>	★
--------------------------------	---

---

<code>\use_none:nnnnnnnn</code>	★
---------------------------------	---

---

<code>\use_none:nnnnnnnnn</code>	★
----------------------------------	---

---

<code>\use_none:nnnnnnnnnn</code>	★
-----------------------------------	---

---

---

<code>\use:x</code>	<code>\use:x {⟨expandable tokens⟩}</code>
---------------------	---

---

Updated: 2011-12-31	Fully expands the <i>⟨expandable tokens⟩</i> and inserts the result into the input stream at the current location. Any hash characters (#) in the argument must be doubled.
---------------------	---

---

## 4.1 Selecting tokens from delimited arguments

A different kind of function for selecting tokens from the token stream are those that use delimited arguments.

---

<code>\use_none_delimit_by_q_nil:w</code>	★	<code>\use_none_delimit_by_q_nil:w ⟨balanced text⟩ \q_nil</code>
<code>\use_none_delimit_by_q_stop:w</code>	★	<code>\use_none_delimit_by_q_stop:w ⟨balanced text⟩ \q_stop</code>
<code>\use_none_delimit_by_q_recursion_stop:w</code>	★	<code>\use_none_delimit_by_q_recursion_stop:w ⟨balanced text⟩</code> <code>\q_recursion_stop</code>

---

Absorb the *⟨balanced text⟩* from the input stream delimited by the marker given in the function name, leaving nothing in the input stream.

---

<code>\use_i_delimit_by_q_nil:nw</code>	★	<code>\use_i_delimit_by_q_nil:nw {⟨inserted tokens⟩} ⟨balanced text⟩</code>
<code>\use_i_delimit_by_q_stop:nw</code>	★	<code>\q_nil</code>
<code>\use_i_delimit_by_q_recursion_stop:nw</code>	★	<code>\use_i_delimit_by_q_stop:nw {⟨inserted tokens⟩} ⟨balanced</code> <code>text⟩ \q_stop</code> <code>\use_i_delimit_by_q_recursion_stop:nw {⟨inserted tokens⟩}</code> <code>⟨balanced text⟩ \q_recursion_stop</code>

---

Absorb the *⟨balanced text⟩* from the input stream delimited by the marker given in the function name, leaving *⟨inserted tokens⟩* in the input stream for further processing.

## 5 Predicates and conditionals

L<sup>A</sup>T<sub>E</sub>X3 has three concepts for conditional flow processing:

**Branching conditionals** Functions that carry out a test and then execute, depending on its result, either the code supplied as the *⟨true code⟩* or the *⟨false code⟩*. These arguments are denoted with T and F, respectively. An example would be

`\cs_if_free:cTF {abc} {⟨true code⟩} {⟨false code⟩}`

a function that turns the first argument into a control sequence (since it's marked as c) then checks whether this control sequence is still free and then depending on the result carries out the code in the second argument (true case) or in the third argument (false case).

These type of functions are known as “conditionals”; whenever a TF function is defined it is usually accompanied by T and F functions as well. These are provided for convenience when the branch only needs to go a single way. Package writers are free to choose which types to define but the kernel definitions always provide all three versions.

Important to note is that these branching conditionals with *⟨true code⟩* and/or *⟨false code⟩* are always defined in a way that the code of the chosen alternative can operate on following tokens in the input stream.

These conditional functions may or may not be fully expandable, but if they are expandable they are accompanied by a “predicate” for the same test as described below.

**Predicates** “Predicates” are functions that return a special type of boolean value which can be tested by the boolean expression parser. All functions of this type are expandable and have names that end with `_p` in the description part. For example,

`\cs_if_free_p:N`

would be a predicate function for the same type of test as the conditional described above. It would return “true” if its argument (a single token denoted by `N`) is still free for definition. It would be used in constructions like

```
\bool_if:nTF {
  \cs_if_free_p:N \l_tmpz_tl || \cs_if_free_p:N \g_tmpz_tl
} {\true code} {\false code}
```

For each predicate defined, a “branching conditional” also exists that behaves like a conditional described above.

**Primitive conditionals** There is a third variety of conditional, which is the original concept used in plain  $\text{\TeX}$  and  $\text{\LaTeX 2}_{\epsilon}$ . Their use is discouraged in `expl3` (although still used in low-level definitions) because they are more fragile and in many cases require more expansion control (hence more code) than the two types of conditionals described above.

---

`\c_true_bool`  
`\c_false_bool`

---

Constants that represent `true` and `false`, respectively. Used to implement predicates.

## 5.1 Tests on control sequences

---

<code>\cs_if_eq_p:NN</code> ★	<code>\cs_if_eq_p:NN</code> $\langle cs_1 \rangle$ $\langle cs_2 \rangle$
<code>\cs_if_eq:NNTF</code> ★	<code>\cs_if_eq:NNTF</code> $\langle cs_1 \rangle$ $\langle cs_2 \rangle$ $\langle true code \rangle$ $\langle false code \rangle$

---

Compares the definition of two  $\langle control sequence \rangle$  and is logically `true` if they are the same, *i.e.* if they have exactly the same definition when examined with `\cs_show:N`.

---

<code>\cs_if_exist_p:N</code> ★	<code>\cs_if_exist_p:N</code> $\langle control sequence \rangle$
<code>\cs_if_exist_p:c</code> ★	<code>\cs_if_exist:NNTF</code> $\langle control sequence \rangle$ $\langle true code \rangle$ $\langle false code \rangle$
<code>\cs_if_exist:NNTF</code> ★	Tests whether the $\langle control sequence \rangle$ is currently defined (whether as a function or another control sequence type). Any valid definition of $\langle control sequence \rangle$ evaluates as <code>true</code> .
<code>\cs_if_exist:cTF</code> ★	

---



---

<code>\cs_if_free_p:N</code> ★	<code>\cs_if_free_p:N</code> $\langle control sequence \rangle$
<code>\cs_if_free_p:c</code> ★	<code>\cs_if_free:NNTF</code> $\langle control sequence \rangle$ $\langle true code \rangle$ $\langle false code \rangle$
<code>\cs_if_free:NNTF</code> ★	Tests whether the $\langle control sequence \rangle$ is currently free to be defined. This test is <code>false</code> if the $\langle control sequence \rangle$ currently exists (as defined by <code>\cs_if_exist:N</code> ).
<code>\cs_if_free:cTF</code> ★	

---

## 5.2 Primitive conditionals

The  $\varepsilon$ -TeX engine itself provides many different conditionals. Some expand whatever comes after them and others don't. Hence the names for these underlying functions often contains a :w part but higher level functions are often available. See for instance `\int_compare_p:nNn` which is a wrapper for `\if_int_compare:w`.

Certain conditionals deal with specific data types like boxes and fonts and are described there. The ones described below are either the universal conditionals or deal with control sequences. We prefix primitive conditionals with `\if_`.

---

<code>\if_true:</code>	★	<code>\if_true: &lt;true code&gt; \else: &lt;false code&gt; \fi:</code>
<code>\if_false:</code>	★	<code>\if_false: &lt;true code&gt; \else: &lt;false code&gt; \fi:</code>
<code>\else:</code>	★	<code>\reverse_if:N &lt;primitive conditional&gt;</code>
<code>\fi:</code>	★	<code>\if_true:</code> always executes <code>&lt;true code&gt;</code> , while <code>\if_false:</code> always executes <code>&lt;false code&gt;</code> .
<code>\reverse_if:N</code>	★	<code>\reverse_if:N</code> reverses any two-way primitive conditional. <code>\else:</code> and <code>\fi:</code> delimit the branches of the conditional. The function <code>\or:</code> is documented in <code>l3int</code> and used in case switches.

---

**TeXhackers note:** These are equivalent to their corresponding TeX primitive conditionals; `\reverse_if:N` is  $\varepsilon$ -TeX's `\unless`.

---

<code>\if_meaning:w</code>	★	<code>\if_meaning:w &lt;arg<sub>1</sub>&gt; &lt;arg<sub>2</sub>&gt; &lt;true code&gt; \else: &lt;false code&gt; \fi:</code>
----------------------------	---	---

---

`\if_meaning:w` executes `<true code>` when `<arg1>` and `<arg2>` are the same, otherwise it executes `<false code>`. `<arg1>` and `<arg2>` could be functions, variables, tokens; in all cases the *unexpanded* definitions are compared.

**TeXhackers note:** This is TeX's `\ifx`.

---

<code>\if:w</code>	★	<code>\if:w &lt;token<sub>1</sub>&gt; &lt;token<sub>2</sub>&gt; &lt;true code&gt; \else: &lt;false code&gt; \fi:</code>
<code>\if_charcode:w</code>	★	<code>\if_catcode:w &lt;token<sub>1</sub>&gt; &lt;token<sub>2</sub>&gt; &lt;true code&gt; \else: &lt;false code&gt; \fi:</code>
<code>\if_catcode:w</code>	★	These conditionals expand any following tokens until two unexpandable tokens are left. If you wish to prevent this expansion, prefix the token in question with <code>\exp_not:N</code> . <code>\if_catcode:w</code> tests if the category codes of the two tokens are the same whereas <code>\if:w</code> tests if the character codes are identical. <code>\if_charcode:w</code> is an alternative name for <code>\if:w</code> .

---



---

<code>\if_cs_exist:N</code>	★	<code>\if_cs_exist:N &lt;cs&gt; &lt;true code&gt; \else: &lt;false code&gt; \fi:</code>
<code>\if_cs_exist:w</code>	★	<code>\if_cs_exist:w &lt;tokens&gt; \cs_end: &lt;true code&gt; \else: &lt;false code&gt; \fi:</code>

---

Check if `<cs>` appears in the hash table or if the control sequence that can be formed from `<tokens>` appears in the hash table. The latter function does not turn the control sequence in question into `\scan_stop:!` This can be useful when dealing with control sequences which cannot be entered as a single token.

---

<code>\if_mode_horizontal:</code>	★	<code>\if_mode_horizontal: &lt;true code&gt; \else: &lt;false code&gt; \fi:</code>
<code>\if_mode_vertical:</code>	★	
<code>\if_mode_math:</code>	★	Execute <code>&lt;true code&gt;</code> if currently in horizontal mode, otherwise execute <code>&lt;false code&gt;</code> . Similar for the other functions.
<code>\if_mode_inner:</code>	★	

---

## 6 Internal kernel functions

<hr/> <code>\__chk_if_exist_cs:N</code> <hr/> <code>\__chk_if_exist_cs:c</code> <hr/>	<code>\__chk_if_exist_cs:N &lt;cs&gt;</code>  This function checks that <i>&lt;cs&gt;</i> exists according to the criteria for <code>\cs_if_exist_p:N</code> , and if not raises a kernel-level error.
<hr/> <code>\__chk_if_free_cs:N</code> <hr/> <code>\__chk_if_free_cs:c</code> <hr/>	<code>\__chk_if_free_cs:N &lt;cs&gt;</code>  This function checks that <i>&lt;cs&gt;</i> is free according to the criteria for <code>\cs_if_free_p:N</code> , and if not raises a kernel-level error.
<hr/> <code>\__chk_if_exist_var:N</code> <hr/>	<code>\__chk_if_exist_var:N &lt;var&gt;</code>  This function checks that <i>&lt;var&gt;</i> is defined according to the criteria for <code>\cs_if_free_p:N</code> , and if not raises a kernel-level error. This function is only created if the package option <code>check-declarations</code> is active.
<hr/> <code>\__debug_log:x</code> <hr/>	<code>\__debug_log:x {&lt;message text&gt;}</code>  Only defined when debugging is enabled (hence only in package mode with the right options). If the <code>log-functions</code> option is active, this function writes the <i>&lt;message text&gt;</i> to the log file using <code>\iow_log:x</code> . Otherwise, the <i>&lt;message text&gt;</i> is ignored using <code>\use_none:n</code> .
<hr/> <code>\__debug_suspend_log:</code> <hr/> <code>\__debug_resume_log:</code> <hr/>	<code>\__debug_suspend_log: ... \__debug_log:x ... \__debug_resume_log:</code>  Any <code>\__debug_log:x</code> command between <code>\__debug_suspend_log:</code> and <code>\__debug_resume_log:</code> is suppressed. These two commands can be nested and do nothing when debugging is disabled.
<hr/> <code>\__debug_patch:nnNw</code> <hr/>	<code>\__debug_patch:nnNw {&lt;before&gt;} {&lt;after&gt;} &lt;definition&gt; ...</code>  If debugging is enabled (by one of few <code>expl3</code> options that imply <code>enable-debug</code> ), adds the <i>&lt;before&gt;</i> and <i>&lt;after&gt;</i> tokens (which can involve <code>#1</code> and so on) in the <i>&lt;definition&gt;</i> that follows. Otherwise ignore the <i>&lt;before&gt;</i> and <i>&lt;after&gt;</i> code and perform the <i>&lt;definition&gt;</i> with no patching. The <i>&lt;definition&gt;</i> must start with <code>\cs_new:Npn</code> or <code>\cs_set:Npn</code> or <code>\cs_gset:Npn</code> or <code>\prg_new_conditional:Npnn</code> or their protected counterparts. Other cases could be added as needed.
<hr/> <code>\__cs_count_signature:N</code> ★ <hr/> <code>\__cs_count_signature:c</code> ★ <hr/>	<code>\__cs_count_signature:N &lt;function&gt;</code>  Splits the <i>&lt;function&gt;</i> into the <i>&lt;name&gt;</i> ( <i>i.e.</i> the part before the colon) and the <i>&lt;signature&gt;</i> ( <i>i.e.</i> after the colon). The <i>&lt;number&gt;</i> of tokens in the <i>&lt;signature&gt;</i> is then left in the input stream. If there was no <i>&lt;signature&gt;</i> then the result is the marker value <code>-1</code> .
<hr/> <code>\__cs_split_function:NN</code> ★ <hr/>	<code>\__cs_split_function:NN &lt;function&gt; &lt;processor&gt;</code>  Splits the <i>&lt;function&gt;</i> into the <i>&lt;name&gt;</i> ( <i>i.e.</i> the part before the colon) and the <i>&lt;signature&gt;</i> ( <i>i.e.</i> after the colon). This information is then placed in the input stream after the <i>&lt;processor&gt;</i> function in three parts: the <i>&lt;name&gt;</i> , the <i>&lt;signature&gt;</i> and a logic token indicating if a colon was found (to differentiate variables from function names). The <i>&lt;name&gt;</i> does not include the escape character, and both the <i>&lt;name&gt;</i> and <i>&lt;signature&gt;</i> are made up of tokens with category code 12 (other). The <i>&lt;processor&gt;</i> should be a function with argument specification <code>:nnN</code> (plus any trailing arguments needed).

---

`\_cs_get_function_name:N` ★ `\_cs_get_function_name:N`  $\langle function \rangle$

---

Splits the  $\langle function \rangle$  into the  $\langle name \rangle$  (*i.e.* the part before the colon) and the  $\langle signature \rangle$  (*i.e.* after the colon). The  $\langle name \rangle$  is then left in the input stream without the escape character present made up of tokens with category code 12 (other).

---

`\_cs_get_function_signature:N` ★ `\_cs_get_function_signature:N`  $\langle function \rangle$

---

Splits the  $\langle function \rangle$  into the  $\langle name \rangle$  (*i.e.* the part before the colon) and the  $\langle signature \rangle$  (*i.e.* after the colon). The  $\langle signature \rangle$  is then left in the input stream made up of tokens with category code 12 (other).

---

`\_cs_tmp:w`

---

Function used for various short-term usages, for instance defining functions whose definition involves tokens which are hard to insert normally (spaces, characters with category other).

---

`\_kernel_register_show:N`  
`\_kernel_register_show:c`

---

`\_kernel_register_show:N`  $\langle register \rangle$

Used to show the contents of a T<sub>E</sub>X register at the terminal, formatted such that internal parts of the mechanism are not visible.

---

`\_kernel_register_log:N`  
`\_kernel_register_log:c`

---

`\_kernel_register_log:N`  $\langle register \rangle$

Used to write the contents of a T<sub>E</sub>X register to the log file in a form similar to `\_kernel_register_show:N`.

Updated: 2015-08-03

---

`\_prg_case_end:nw` ★ `\_prg_case_end:nw`  $\{\langle code \rangle\}$   $\langle tokens \rangle$  `\q_mark`  $\{\langle true code \rangle\}$  `\q_mark`  $\{\langle false code \rangle\}$   
`\q_stop`

---

Used to terminate case statements (`\int_case:nnTF`, *etc.*) by removing trailing  $\langle tokens \rangle$  and the end marker `\q_stop`, inserting the  $\langle code \rangle$  for the successful case (if one is found) and either the `true code` or `false code` for the over all outcome, as appropriate.

## Part V

# The l3expan package

## Argument expansion

This module provides generic methods for expanding T<sub>E</sub>X arguments in a systematic manner. The functions in this module all have prefix `exp`.

Not all possible variations are implemented for every base function. Instead only those that are used within the L<sup>A</sup>T<sub>E</sub>X3 kernel or otherwise seem to be of general interest are implemented. Consult the module description to find out which functions are actually defined. The next section explains how to define missing variants.

### 1 Defining new variants

The definition of variant forms for base functions may be necessary when writing new functions or when applying a kernel function in a situation that we haven't thought of before.

Internally preprocessing of arguments is done with functions from the `\exp_` module. They all look alike, an example would be `\exp_args:NNo`. This function has three arguments, the first and the second are a single tokens, while the third argument should be given in braces. Applying `\exp_args:NNo` expands the content of third argument once before any expansion of the first and second arguments. If `\seq_gpush:No` was not defined it could be coded in the following way:

```
\exp_args:NNo \seq_gpush:Nn
  \g_file_name_stack
  \l_tmpa_tl
```

In other words, the first argument to `\exp_args:NNo` is the base function and the other arguments are preprocessed and then passed to this base function. In the example the first argument to the base function should be a single token which is left unchanged while the second argument is expanded once. From this example we can also see how the variants are defined. They just expand into the appropriate `\exp_` function followed by the desired base function, *e.g.*

```
\cs_generate_variant:Nn \seq_gpush:Nn { No }
```

results in the definition of `\seq_gpush:No`

```
\cs_new:Npn \seq_gpush:No { \exp_args:NNo \seq_gpush:Nn }
```

Providing variants in this way in style files is uncritical as the `\cs_generate_variant:Nn` function will only create new definitions if there is not already one available. Therefore adding such definition to later releases of the kernel will not make such style files obsolete.

The steps above may be automated by using the function `\cs_generate_variant:Nn`, described next.

## 2 Methods for defining variants

---

`\cs_generate_variant:Nn`

---

Updated: 2015-08-06

---

`\cs_generate_variant:Nn`  $\langle$ parent control sequence $\rangle$   $\{$  $\langle$ variant argument specifiers $\rangle$  $\}$

This function is used to define argument-specifier variants of the  $\langle$ parent control sequence $\rangle$  for L<sup>A</sup>T<sub>E</sub>X3 code-level macros. The  $\langle$ parent control sequence $\rangle$  is first separated into the  $\langle$ base name $\rangle$  and  $\langle$ original argument specifier $\rangle$ . The comma-separated list of  $\langle$ variant argument specifiers $\rangle$  is then used to define variants of the  $\langle$ original argument specifier $\rangle$  where these are not already defined. For each  $\langle$ variant $\rangle$  given, a function is created which expands its arguments as detailed and passes them to the  $\langle$ parent control sequence $\rangle$ . So for example

```
\cs_set:Npn \foo:Nn #1#2 { code here }
\cs_generate_variant:Nn \foo:Nn { c }
```

creates a new function `\foo:cn` which expands its first argument into a control sequence name and passes the result to `\foo:Nn`. Similarly

```
\cs_generate_variant:Nn \foo:Nn { NV ,cV }
```

generates the functions `\foo:NV` and `\foo:cV` in the same way. The `\cs_generate_variant:Nn` function can only be applied if the  $\langle$ parent control sequence $\rangle$  is already defined. Only `n` and `N` arguments can be changed to other types. If the  $\langle$ parent control sequence $\rangle$  is protected or if the  $\langle$ variant $\rangle$  involves `x` arguments, then the  $\langle$ variant control sequence $\rangle$  is also protected. The  $\langle$ variant $\rangle$  is created globally, as is any `\exp_args:N`( $\langle$ variant $\rangle$ ) function needed to carry out the expansion.

## 3 Introducing the variants

The available internal functions for argument expansion come in two flavours, some of them are faster than others. Therefore (when speed is important) it is usually best to follow the following guidelines when defining new functions that are supposed to come with variant forms:

- Arguments that might need expansion should come first in the list of arguments to make processing faster.
- Arguments that should consist of single tokens should come first.
- Arguments that need full expansion (*i.e.*, are denoted with `x`) should be avoided if possible as they can not be processed expandably, *i.e.*, functions of this type cannot work correctly in arguments that are themselves subject to `x` expansion.
- In general, unless in the last position, multi-token arguments `n`, `f`, and `o` need special processing when more than one argument is being expanded. This special processing is not fast. Therefore it is best to use the optimized functions, namely those that contain only `N`, `c`, `V`, and `v`, and, in the last position, `o`, `f`, with possible trailing `N` or `n`, which are not expanded.

The `V` type returns the value of a register, which can be one of `tl`, `int`, `skip`, `dim`, `toks`, or built-in T<sub>E</sub>X registers. The `v` type is the same except it first creates a control sequence out of its argument before returning the value.



In general, the programmer should not need to be concerned with expansion control. When simply using the content of a variable, functions with a `V` specifier should be used. For those referred to by `(cs)name`, the `v` specifier is available for the same purpose. Only when specific expansion steps are needed, such as when using delimited arguments, should the lower-level functions with `o` specifiers be employed.

The `f` type is so special that it deserves an example. It is typically used in contexts where only expandable commands are allowed. Then `x`-expansion cannot be used, and `f`-expansion provides an alternative that expands as much as can be done in such contexts. For instance, say that we want to evaluate the integer expression `3+4` and pass the result 7 as an argument to an expandable function `\example:n`. For this, one should define a variant using `\cs_generate_variant:Nn \example:n { f }`, then do

```
\example:f { \int_eval:n { 3 + 4 } }
```

Note that `x`-expansion would also expand `\int_eval:n` fully to its result 7, but the variant `\example:x` cannot be expandable. Note also that `o`-expansion would not expand `\int_eval:n` fully to its result since that function requires several expansions. Besides the fact that `x`-expansion is protected rather than expandable, another difference between `f`-expansion and `x`-expansion is that `f`-expansion expands tokens from the beginning and stops as soon as a non-expandable token is encountered, while `x`-expansion continues expanding further tokens. Thus, for instance

```
\example:f { \int_eval:n { 1 + 2 } , \int_eval:n { 3 + 4 } }
```

results in the call `\example:n { 3 , \int_eval:n { 3 + 4 } }` while using `\example:x` instead results in `\example:n { 3 , 7 }` at the cost of being protected. If you use this type of expansion in conditional processing then you should stick to using `TF` type functions only as it does not try to finish any `\if... \fi`: itself!

It is important to note that both `f`- and `o`-type expansion are concerned with the expansion of tokens from left to right in their arguments. In particular, `o`-type expansion applies to the first *token* in the argument it receives: it is conceptually similar to

```
\exp_after:wN <base function> \exp_after:wN { <argument> }
```

At the same time, `f`-type expansion stops at the *emph*first non-expandable token. This means for example that both

```
\tl_set:N0 \l_tmpa_tl { { \g_tmpb_tl } }
```

and

```
\tl_set:Nf \l_tmpa_tl { { \g_tmpb_tl } }
```

leave `\g_tmpb_tl` unchanged: `{` is the first token in the argument and is non-expandable.

## 4 Manipulating the first argument

These functions are described in detail: expansion of multiple tokens follows the same rules but is described in a shorter fashion.

<hr/> <code>\exp_args:No</code> ★ <hr/>	<code>\exp_args:No</code> $\langle function \rangle$ $\{\langle tokens \rangle\}$ ...
	This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$ ). The $\langle tokens \rangle$ are expanded once, and the result is inserted in braces into the input stream <i>after</i> reinsertion of the $\langle function \rangle$ . Thus the $\langle function \rangle$ may take more than one argument: all others are left unchanged.
<hr/> <code>\exp_args:Nc</code> ★ <hr/> <code>\exp_args:cc</code> ★ <hr/>	<code>\exp_args:Nc</code> $\langle function \rangle$ $\{\langle tokens \rangle\}$
	This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$ ). The $\langle tokens \rangle$ are expanded until only characters remain, and are then turned into a control sequence. (An internal error occurs if such a conversion is not possible). The result is inserted into the input stream <i>after</i> reinsertion of the $\langle function \rangle$ . Thus the $\langle function \rangle$ may take more than one argument: all others are left unchanged.
	The <code>:cc</code> variant constructs the $\langle function \rangle$ name in the same manner as described for the $\langle tokens \rangle$ .
<hr/> <code>\exp_args:Nv</code> ★ <hr/>	<code>\exp_args:Nv</code> $\langle function \rangle$ $\langle variable \rangle$
	This function absorbs two arguments (the names of the $\langle function \rangle$ and the $\langle variable \rangle$ ). The content of the $\langle variable \rangle$ are recovered and placed inside braces into the input stream <i>after</i> reinsertion of the $\langle function \rangle$ . Thus the $\langle function \rangle$ may take more than one argument: all others are left unchanged.
<hr/> <code>\exp_args:Nv</code> ★ <hr/>	<code>\exp_args:Nv</code> $\langle function \rangle$ $\{\langle tokens \rangle\}$
	This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$ ). The $\langle tokens \rangle$ are expanded until only characters remain, and are then turned into a control sequence. (An internal error occurs if such a conversion is not possible). This control sequence should be the name of a $\langle variable \rangle$ . The content of the $\langle variable \rangle$ are recovered and placed inside braces into the input stream <i>after</i> reinsertion of the $\langle function \rangle$ . Thus the $\langle function \rangle$ may take more than one argument: all others are left unchanged.
<hr/> <code>\exp_args:Nf</code> ★ <hr/>	<code>\exp_args:Nf</code> $\langle function \rangle$ $\{\langle tokens \rangle\}$
	This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$ ). The $\langle tokens \rangle$ are fully expanded until the first non-expandable token or space is found, and the result is inserted in braces into the input stream <i>after</i> reinsertion of the $\langle function \rangle$ . Thus the $\langle function \rangle$ may take more than one argument: all others are left unchanged.
<hr/> <code>\exp_args:Nx</code> <hr/>	<code>\exp_args:Nx</code> $\langle function \rangle$ $\{\langle tokens \rangle\}$
	This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$ ) and exhaustively expands the $\langle tokens \rangle$ second. The result is inserted in braces into the input stream <i>after</i> reinsertion of the $\langle function \rangle$ . Thus the $\langle function \rangle$ may take more than one argument: all others are left unchanged.

## 5 Manipulating two arguments

<hr/>	
<code>\exp_args:NNo</code> *	<code>\exp_args:NNo &lt;token&gt; {&lt;tokens&gt;}</code>
<code>\exp_args:Nnc</code> *	
<code>\exp_args:Nnv</code> *	These optimized functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments.
<code>\exp_args:NNf</code> *	
<code>\exp_args:Nco</code> *	
<code>\exp_args:Ncf</code> *	
<code>\exp_args:Ncc</code> *	
<code>\exp_args:NVV</code> *	
<hr/>	
<code>\exp_args:Nno</code> *	<code>\exp_args:Nno &lt;token&gt; {&lt;tokens&gt;}</code>
<code>\exp_args:NnV</code> *	
<code>\exp_args:Nnf</code> *	These functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments. These functions need special (slower) processing.
<code>\exp_args:Noo</code> *	
<code>\exp_args:Nof</code> *	
<code>\exp_args:Noc</code> *	
<code>\exp_args:Nff</code> *	
<code>\exp_args:Nfo</code> *	
<code>\exp_args:Nnc</code> *	
<hr/>	
Updated: 2012-01-14	
<hr/>	
<code>\exp_args:NNx</code>	<code>\exp_args:NNx &lt;token&gt; {&lt;tokens&gt;}</code>
<code>\exp_args:Nnx</code>	
<code>\exp_args:Ncx</code>	These functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments. These functions are not expandable.
<code>\exp_args:Nox</code>	
<code>\exp_args:Nxo</code>	
<code>\exp_args:Nxx</code>	
<hr/>	

## 6 Manipulating three arguments

<hr/>	
<code>\exp_args:NNNo</code> *	<code>\exp_args:NNNo &lt;token&gt; {&lt;tokens&gt;}</code>
<code>\exp_args:NNNV</code> *	
<code>\exp_args:Nccc</code> *	These optimized functions absorb four arguments and expand the second, third and fourth as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second argument, <i>etc.</i>
<code>\exp_args:NcNc</code> *	
<code>\exp_args:NcNo</code> *	
<code>\exp_args:Ncco</code> *	
<hr/>	
<code>\exp_args:NNoo</code> *	<code>\exp_args:NNoo &lt;token&gt; {&lt;tokens&gt;}</code>
<code>\exp_args:NNno</code> *	
<code>\exp_args:Nnno</code> *	These functions absorb four arguments and expand the second, third and fourth as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second argument, <i>etc.</i> These functions need special (slower) processing.
<code>\exp_args:Nnnc</code> *	
<code>\exp_args:Nooo</code> *	
<hr/>	

---

<code>\exp_args:NNNx</code>	<code>\exp_args:NNnx</code>	<code>\langle token_1 \rangle \langle token_2 \rangle \{\langle tokens_1 \rangle\} \{\langle tokens_2 \rangle\}</code>
<code>\exp_args:NNnx</code>		
<code>\exp_args:NNox</code>		
<code>\exp_args:Nnnx</code>		
<code>\exp_args:Nnox</code>		
<code>\exp_args:Noox</code>		
<code>\exp_args:Ncnx</code>		
<code>\exp_args:Nccx</code>		

---

New: 2015-08-12

## 7 Unbraced expansion

---

<code>\exp_last_unbraced:Nv</code>	★	<code>\exp_last_unbraced:Nno</code>	<code>\langle token \rangle \langle tokens_1 \rangle \langle tokens_2 \rangle</code>
<code>\exp_last_unbraced:(Nf No Nv)</code>	★		
<code>\exp_last_unbraced:Nco</code>	★		
<code>\exp_last_unbraced:(NcV NNV NNo)</code>	★		
<code>\exp_last_unbraced:Nno</code>	★		
<code>\exp_last_unbraced:(Noo Nfo)</code>	★		
<code>\exp_last_unbraced:NNNV</code>	★		
<code>\exp_last_unbraced:NNNo</code>	★		
<code>\exp_last_unbraced:NnNo</code>	★		

---

Updated: 2012-02-12

These functions absorb the number of arguments given by their specification, carry out the expansion indicated and leave the results in the input stream, with the last argument not surrounded by the usual braces. Of these, the `:Nno`, `:Noo`, and `:Nfo` variants need special (slower) processing.

**TeXhackers note:** As an optimization, the last argument is unbraced by some of those functions before expansion. This can cause problems if the argument is empty: for instance, `\exp_last_unbraced:Nf \foo_bar:w { } \q_stop` leads to an infinite loop, as the quark is `f`-expanded.

---

<code>\exp_last_unbraced:Nx</code>	<code>\exp_last_unbraced:Nx</code>	<code>\langle function \rangle \{\langle tokens \rangle\}</code>
------------------------------------	------------------------------------	--

---

This functions fully expands the `\langle tokens \rangle` and leaves the result in the input stream after reinsertion of `\langle function \rangle`. This function is not expandable.

---

<code>\exp_last_two_unbraced:Noo</code>	★	<code>\exp_last_two_unbraced:Noo</code>	<code>\langle token \rangle \langle tokens_1 \rangle \{\langle tokens_2 \rangle\}</code>
---	---	---	--

---

This function absorbs three arguments and expand the second and third once. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments, which are not wrapped in braces. This function needs special (slower) processing.

<hr/> <hr/> <code>\exp_after:wN</code> ★	<code>\exp_after:wN</code> $\langle token_1 \rangle$ $\langle token_2 \rangle$
	Carries out a single expansion of $\langle token_2 \rangle$ (which may consume arguments) prior to the expansion of $\langle token_1 \rangle$ . If $\langle token_2 \rangle$ has no expansion (for example, if it is a character) then it is left unchanged. It is important to notice that $\langle token_1 \rangle$ may be <i>any</i> single token, including group-opening and -closing tokens ( <code>{</code> or <code>}</code> assuming normal $\text{\TeX}$ category codes). Unless specifically required, expansion should be carried out using an appropriate argument specifier variant or the appropriate <code>\exp_arg:N</code> function.

**$\text{\TeX}$ hackers note:** This is the  $\text{\TeX}$  primitive `\expandafter` renamed.

## 8 Preventing expansion

Despite the fact that the following functions are all about preventing expansion, they're designed to be used in an expandable context and hence are all marked as being 'expandable' since they themselves disappear after the expansion has completed.

<hr/> <hr/> <code>\exp_not:N</code> ★	<code>\exp_not:N</code> $\langle token \rangle$
	Prevents expansion of the $\langle token \rangle$ in a context where it would otherwise be expanded, for example an <code>x</code> -type argument.

**$\text{\TeX}$ hackers note:** This is the  $\text{\TeX}$  `\noexpand` primitive.

<hr/> <hr/> <code>\exp_not:c</code> ★	<code>\exp_not:c</code> $\{\langle tokens \rangle\}$
	Expands the $\langle tokens \rangle$ until only unexpandable content remains, and then converts this into a control sequence. Further expansion of this control sequence is then inhibited.

<hr/> <hr/> <code>\exp_not:n</code> ★	<code>\exp_not:n</code> $\{\langle tokens \rangle\}$
	Prevents expansion of the $\langle tokens \rangle$ in a context where they would otherwise be expanded, for example an <code>x</code> -type argument.

**$\text{\TeX}$ hackers note:** This is the  $\varepsilon$ - $\text{\TeX}$  `\unexpanded` primitive. Hence its argument *must* be surrounded by braces.

<hr/> <hr/> <code>\exp_not:V</code> ★	<code>\exp_not:V</code> $\langle variable \rangle$
	Recovers the content of the $\langle variable \rangle$ , then prevents expansion of this material in a context where it would otherwise be expanded, for example an <code>x</code> -type argument.

<hr/> <hr/> <code>\exp_not:v</code> ★	<code>\exp_not:v</code> $\{\langle tokens \rangle\}$
	Expands the $\langle tokens \rangle$ until only unexpandable content remains, and then converts this into a control sequence (which should be a $\langle variable \rangle$ name). The content of the $\langle variable \rangle$ is recovered, and further expansion is prevented in a context where it would otherwise be expanded, for example an <code>x</code> -type argument.

<hr/> <hr/> <code>\exp_not:o</code> ★	<code>\exp_not:o</code> $\{\langle tokens \rangle\}$
	Expands the $\langle tokens \rangle$ once, then prevents any further expansion in a context where they would otherwise be expanded, for example an <code>x</code> -type argument.

---

<code>\exp_not:f</code> ★	<code>\exp_not:f {&lt;tokens&gt;}</code>
---------------------------	--

---

Expands *<tokens>* fully until the first unexpandable token is found. Expansion then stops, and the result of the expansion (including any tokens which were not expanded) is protected from further expansion.

---

<code>\exp_stop_f:</code> ★	<code>\foo_bar:f { &lt;tokens&gt; \exp_stop_f: &lt;more tokens&gt; }</code>
-----------------------------	---

---

Updated: 2011-06-03

This function terminates an *f*-type expansion. Thus if a function `\foo_bar:f` starts an *f*-type expansion and all of *<tokens>* are expandable `\exp_stop_f:` terminates the expansion of tokens even if *<more tokens>* are also expandable. The function itself is an implicit space token. Inside an *x*-type expansion, it retains its form, but when typeset it produces the underlying space (␣).

## 9 Controlled expansion

The `expl3` language makes all efforts to hide the complexity of  $\text{\TeX}$  expansion from the programmer by providing concepts that evaluate/expand arguments of functions prior to calling the “base” functions. Thus, instead of using many `\expandafter` calls and other trickery it is usually a matter of choosing the right variant of a function to achieve a desired result.

Of course, deep down  $\text{\TeX}$  is using expansion as always and there are cases where a programmer needs to control that expansion directly; typical situations are basic data manipulation tools. This section documents the functions for that level. These commands are used throughout the kernel code, but we hope that outside the kernel there will be little need to resort to them. Instead the argument manipulation methods document above should usually be sufficient.

While `\exp_after:wN` expands one token (out of order) it is sometimes necessary to expand several tokens in one go. The next set of commands provide this functionality. Be aware that it is absolutely required that the programmer has full control over the tokens to be expanded, i.e., it is not possible to use these functions to expand unknown input as part of *<expandable-tokens>* as that will break badly if unexpandable tokens are encountered in that place!

---

<code>\exp:w</code> ★	<code>\exp:w &lt;expandable-tokens&gt; \exp_end:</code>
-----------------------	---

---

`\exp_end:` ★

New: 2015-08-23

Expands *<expandable-tokens>* until reaching `\exp_end:` at which point expansion stops. The full expansion of *<expandable-tokens>* has to be empty. If any token in *<expandable-tokens>* or any token generated by expanding the tokens therein is not expandable the expansion will end prematurely and as a result `\exp_end:` will be misinterpreted later on.<sup>2</sup>

In typical use cases the `\exp_end:` is hidden somewhere in the replacement text of *<expandable-tokens>* rather than being on the same expansion level than `\exp:w`, e.g., you may see code such as

```
\exp:w \@@_case:NnTF #1 {#2} { } { }
```

where somewhere during the expansion of `\@@_case:NnTF` the `\exp_end:` gets generated.

---

<sup>2</sup>Due to the implementation you might get the character in position 0 in the current font (typically “”) in the output without any error message!

---

<code>\exp:w</code>	★
<code>\exp_end_continue_f:w</code>	★

---

New: 2015-08-23

---

`\exp:w`  $\langle expandable-tokens \rangle$  `\exp_end_continue_f:w`  $\langle further-tokens \rangle$

Expands  $\langle expandable-tokens \rangle$  until reaching `\exp_end_continue_f:w` at which point expansion continues as an f-type expansion expanding  $\langle further-tokens \rangle$  until an unexpandable token is encountered (or the f-type expansion is explicitly terminated by `\exp_stop_f:`). As with all f-type expansions a space ending the expansion gets removed.

The full expansion of  $\langle expandable-tokens \rangle$  has to be empty. If any token in  $\langle expandable-tokens \rangle$  or any token generated by expanding the tokens therein is not expandable the expansion will end prematurely and as a result `\exp_end_continue_f:w` will be misinterpreted later on.<sup>3</sup>

In typical use cases  $\langle expandable-tokens \rangle$  contains no tokens at all, e.g., you will see code such as

`\exp_after:wN { \exp:w \exp_end_continue_f:w #2 }`

where the `\exp_after:wN` triggers an f-expansion of the tokens in #2. For technical reasons this has to happen using two tokens (if they would be hidden inside another command `\exp_after:wN` would only expand the command but not trigger any additional f-expansion).

You might wonder why there are two different approaches available, after all the effect of

`\exp:w`  $\langle expandable-tokens \rangle$  `\exp_end:`

can be alternatively achieved through an f-type expansion by using `\exp_stop_f:`, i.e.

`\exp:w \exp_end_continue_f:w`  $\langle expandable-tokens \rangle$  `\exp_stop_f:`

The reason is simply that the first approach is slightly faster (one less token to parse and less expansion internally) so in places where such performance really matters and where we want to explicitly stop the expansion at a defined point the first form is preferable.

---

<code>\exp:w</code>	★
<code>\exp_end_continue_f:nw</code>	★

---

New: 2015-08-23

---

`\exp:w`  $\langle expandable-tokens \rangle$  `\exp_end_continue_f:nw`  $\langle further-tokens \rangle$

The difference to `\exp_end_continue_f:w` is that we first we pick up an argument which is then returned to the input stream. If  $\langle further-tokens \rangle$  starts with a brace group then the braces are removed. If on the other hand it starts with space tokens then these space tokens are removed while searching for the argument. Thus such space tokens will not terminate the f-type expansion.

## 10 Internal functions and variables

---

`\l__exp_internal_tl`

---

The `\exp_` module has its private variables to temporarily store results of the argument expansion. This is done to avoid interference with other functions using temporary variables.

---

<sup>3</sup>In this particular case you may get a character into the output as well as an error message.

---

```

\::n \cs_set:Npn \exp_args:Ncof { \::c \::o \::f \::: }
\::N
\::p Internal forms for the base expansion types. These names do not conform to the general
\::c LATEX3 approach as this makes them more readily visible in the log and so forth.
\::o
\::f
\::x
\::v
\::V
\:::

```

---



## Part VI

# The l3tl package

## Token lists

T<sub>E</sub>X works with tokens, and L<sup>A</sup>T<sub>E</sub>X3 therefore provides a number of functions to deal with lists of tokens. Token lists may be present directly in the argument to a function:

```
\foo:n { a collection of \tokens }
```

or may be stored in a so-called “token list variable”, which have the suffix `tl`: a token list variable can also be used as the argument to a function, for example

```
\foo:N \l_some_tl
```

In both cases, functions are available to test and manipulate the lists of tokens, and these have the module prefix `tl`. In many cases, function which can be applied to token list variables are paired with similar functions for application to explicit lists of tokens: the two “views” of a token list are therefore collected together here.

A token list (explicit, or stored in a variable) can be seen either as a list of “items”, or a list of “tokens”. An item is whatever `\use:n` would grab as its argument: a single non-space token or a brace group, with optional leading explicit space characters (each item is thus itself a token list). A token is either a normal `N` argument, or `␣`, `{`, or `}` (assuming normal T<sub>E</sub>X category codes). Thus for example

```
{ Hello } ~ world
```

contains six items (Hello, w, o, r, l and d), but thirteen tokens (`{`, H, e, l, l, o, `}`, `␣`, w, o, r, l and d). Functions which act on items are often faster than their analogue acting directly on tokens.

## 1 Creating and initialising token list variables

---

```
\tl_new:N \tl_new:c
```

---

Creates a new  $\langle tl\ var \rangle$  or raises an error if the name is already taken. The declaration is global. The  $\langle tl\ var \rangle$  is initially empty.

---

```
\tl_const:Nn \tl_const:(Nx|cn|cx)
```

---

Creates a new constant  $\langle tl\ var \rangle$  or raises an error if the name is already taken. The value of the  $\langle tl\ var \rangle$  is set globally to the  $\langle token\ list \rangle$ .

---

```
\tl_clear:N \tl_clear:c \tl_gclear:N \tl_gclear:c
```

---

Clears all entries from the  $\langle tl\ var \rangle$ .

<hr/>	
<code>\tl_clear_new:N</code>	<code>\tl_clear_new:N &lt;tl var&gt;</code>
<code>\tl_clear_new:c</code>	
<code>\tl_gclear_new:N</code>	Ensures that the $\langle tl\ var \rangle$ exists globally by applying <code>\tl_new:N</code> if necessary, then applies
<code>\tl_gclear_new:c</code>	<code>\tl_(g)clear:N</code> to leave the $\langle tl\ var \rangle$ empty.
<hr/>	
<code>\tl_set_eq:NN</code>	<code>\tl_set_eq:NN &lt;tl var<sub>1</sub>&gt; &lt;tl var<sub>2</sub>&gt;</code>
<code>\tl_set_eq:(cN Nc cc)</code>	Sets the content of $\langle tl\ var_1 \rangle$ equal to that of $\langle tl\ var_2 \rangle$ .
<code>\tl_gset_eq:NN</code>	
<code>\tl_gset_eq:(cN Nc cc)</code>	
<hr/>	
<code>\tl_concat:NNN</code>	<code>\tl_concat:NNN &lt;tl var<sub>1</sub>&gt; &lt;tl var<sub>2</sub>&gt; &lt;tl var<sub>3</sub>&gt;</code>
<code>\tl_concat:ccc</code>	
<code>\tl_gconcat:NNN</code>	Concatenates the content of $\langle tl\ var_2 \rangle$ and $\langle tl\ var_3 \rangle$ together and saves the result in
<code>\tl_gconcat:ccc</code>	$\langle tl\ var_1 \rangle$ . The $\langle tl\ var_2 \rangle$ is placed at the left side of the new token list.
<hr/>	
New: 2012-05-18	
<hr/>	
<code>\tl_if_exist_p:N *</code>	<code>\tl_if_exist_p:N &lt;tl var&gt;</code>
<code>\tl_if_exist_p:c *</code>	<code>\tl_if_exist:NTF &lt;tl var&gt; {\true code} {\false code}</code>
<code>\tl_if_exist:NTF *</code>	
<code>\tl_if_exist:cTF *</code>	Tests whether the $\langle tl\ var \rangle$ is currently defined. This does not check that the $\langle tl\ var \rangle$ really is a token list variable.
<hr/>	
New: 2012-03-03	

## 2 Adding data to token list variables

<hr/>	
<code>\tl_set:Nn</code>	<code>\tl_set:Nn &lt;tl var&gt; {\tokens}</code>
<code>\tl_set:(NV Nv No Nf Nx cn cV cv co cf cx)</code>	
<code>\tl_gset:Nn</code>	
<code>\tl_gset:(NV Nv No Nf Nx cn cV cv co cf cx)</code>	
<hr/>	
Sets $\langle tl\ var \rangle$ to contain $\langle tokens \rangle$ , removing any previous content from the variable.	
<hr/>	
<code>\tl_put_left:Nn</code>	<code>\tl_put_left:Nn &lt;tl var&gt; {\tokens}</code>
<code>\tl_put_left:(NV No Nx cn cV co cx)</code>	
<code>\tl_gput_left:Nn</code>	
<code>\tl_gput_left:(NV No Nx cn cV co cx)</code>	
<hr/>	
Appends $\langle tokens \rangle$ to the left side of the current content of $\langle tl\ var \rangle$ .	
<hr/>	
<code>\tl_put_right:Nn</code>	<code>\tl_put_right:Nn &lt;tl var&gt; {\tokens}</code>
<code>\tl_put_right:(NV No Nx cn cV co cx)</code>	
<code>\tl_gput_right:Nn</code>	
<code>\tl_gput_right:(NV No Nx cn cV co cx)</code>	
<hr/>	
Appends $\langle tokens \rangle$ to the right side of the current content of $\langle tl\ var \rangle$ .	

### 3 Modifying token list variables

---

```
\tl_replace_once:Nnn
\tl_replace_once:cnn
\tl_greplace_once:Nnn
\tl_greplace_once:cnn
```

---

Updated: 2011-08-11

---

```
\tl_replace_once:Nnn <tl var> {{<old tokens>}} {{<new tokens>}}
```

Replaces the first (leftmost) occurrence of *<old tokens>* in the *<tl var>* with *<new tokens>*. *<Old tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

---

```
\tl_replace_all:Nnn
\tl_replace_all:cnn
\tl_greplace_all:Nnn
\tl_greplace_all:cnn
```

---

Updated: 2011-08-11

---

```
\tl_replace_all:Nnn <tl var> {{<old tokens>}} {{<new tokens>}}
```

Replaces all occurrences of *<old tokens>* in the *<tl var>* with *<new tokens>*. *<Old tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6). As this function operates from left to right, the pattern *<old tokens>* may remain after the replacement (see `\tl_remove_all:Nn` for an example).

---

```
\tl_remove_once:Nn
\tl_remove_once:cn
\tl_gremove_once:Nn
\tl_gremove_once:cn
```

---

Updated: 2011-08-11

---

```
\tl_remove_once:Nn <tl var> {{<tokens>}}
```

Removes the first (leftmost) occurrence of *<tokens>* from the *<tl var>*. *<Tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

---

```
\tl_remove_all:Nn
\tl_remove_all:cn
\tl_gremove_all:Nn
\tl_gremove_all:cn
```

---

Updated: 2011-08-11

---

```
\tl_remove_all:Nn <tl var> {{<tokens>}}
```

Removes all occurrences of *<tokens>* from the *<tl var>*. *<Tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6). As this function operates from left to right, the pattern *<tokens>* may remain after the removal, for instance,

```
\tl_set:Nn \l_tmpa_tl {abbccd} \tl_remove_all:Nn \l_tmpa_tl {bc}
```

results in `\l_tmpa_tl` containing `abcd`.

### 4 Reassigning token list category codes

These functions allow the rescanning of tokens: re-apply T<sub>E</sub>X's tokenization process to apply category codes different from those in force when the tokens were absorbed. Whilst this functionality is supported, it is often preferable to find alternative approaches to achieving outcomes rather than rescanning tokens (for example construction of token lists token-by-token with intervening category code changes).

---

<code>\tl_set_rescan:Nnn</code>	<code>\tl_set_rescan:Nnn &lt;tl var&gt; {&lt;setup&gt;} {&lt;tokens&gt;}</code>
<code>\tl_set_rescan:(Nno Nnx cnn cno cnx)</code>	
<code>\tl_gset_rescan:Nnn</code>	
<code>\tl_gset_rescan:(Nno Nnx cnn cno cnx)</code>	

---

Updated: 2015-08-11

Sets `<tl var>` to contain `<tokens>`, applying the category code régime specified in the `<setup>` before carrying out the assignment. (Category codes applied to tokens not explicitly covered by the `<setup>` are those in force at the point of use of `\tl_set_rescan:Nnn`.) This allows the `<tl var>` to contain material with category codes other than those that apply when `<tokens>` are absorbed. The `<setup>` is run within a group and may contain any valid input, although only changes in category codes are relevant. See also `\tl_rescan:nn`.

**TeXhackers note:** The `<tokens>` are first turned into a string (using `\tl_to_str:n`). If the string contains one or more characters with character code `\newlinechar` (set equal to `\endlinechar` unless that is equal to 32, before the user `<setup>`), then it is split into lines at these characters, then read as if reading multiple lines from a file, ignoring spaces (catcode 10) at the beginning and spaces and tabs (character code 32 or 9) at the end of every line. Otherwise, spaces (and tabs) are retained at both ends of the single-line string, as if it appeared in the middle of a line read from a file. Only the case of a single line is supported in LuaTeX because of a bug in this engine.

---

<code>\tl_rescan:nn</code>	<code>\tl_rescan:nn {&lt;setup&gt;} {&lt;tokens&gt;}</code>
----------------------------	---

---

Updated: 2015-08-11

Rescans `<tokens>` applying the category code régime specified in the `<setup>`, and leaves the resulting tokens in the input stream. (Category codes applied to tokens not explicitly covered by the `<setup>` are those in force at the point of use of `\tl_rescan:nn`.) The `<setup>` is run within a group and may contain any valid input, although only changes in category codes are relevant. See also `\tl_set_rescan:Nnn`, which is more robust than using `\tl_set:Nn` in the `<tokens>` argument of `\tl_rescan:nn`.

**TeXhackers note:** The `<tokens>` are first turned into a string (using `\tl_to_str:n`). If the string contains one or more characters with character code `\newlinechar` (set equal to `\endlinechar` unless that is equal to 32, before the user `<setup>`), then it is split into lines at these characters, then read as if reading multiple lines from a file, ignoring spaces (catcode 10) at the beginning and spaces and tabs (character code 32 or 9) at the end of every line. Otherwise, spaces (and tabs) are retained at both ends of the single-line string, as if it appeared in the middle of a line read from a file. Only the case of a single line is supported in LuaTeX because of a bug in this engine.

## 5 Token list conditionals

---

<code>\tl_if_blank_p:n</code>	★	<code>\tl_if_blank_p:n {&lt;token list&gt;}</code>
<code>\tl_if_blank_p:(V o)</code>	★	<code>\tl_if_blank:nTF {&lt;token list&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\tl_if_blank:nTF</code>	★	
<code>\tl_if_blank:(V o)TF</code>	★	

---

Tests if the `<token list>` consists only of blank spaces (*i.e.* contains no item). The test is **true** if `<token list>` is zero or more explicit space characters (explicit tokens with character code 32 and category code 10), and is **false** otherwise.

---

<code>\tl_if_empty_p:N</code>	★	<code>\tl_if_empty_p:N &lt;tl var&gt;</code>
<code>\tl_if_empty_p:c</code>	★	<code>\tl_if_empty:NNTF &lt;tl var&gt; {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\tl_if_empty:nTF</code>	★	Tests if the <i>&lt;token list variable&gt;</i> is entirely empty ( <i>i.e.</i> contains no tokens at all).
<code>\tl_if_empty:cTF</code>	★	

---



---

<code>\tl_if_empty_p:n</code>	★	<code>\tl_if_empty_p:n {&lt;token list&gt;}</code>
<code>\tl_if_empty_p:(V o)</code>	★	<code>\tl_if_empty:nNTF {&lt;token list&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\tl_if_empty:nTF</code>	★	Tests if the <i>&lt;token list&gt;</i> is entirely empty ( <i>i.e.</i> contains no tokens at all).
<code>\tl_if_empty:(V o)TF</code>	★	

---

New: 2012-05-24  
Updated: 2012-06-05

---



---

<code>\tl_if_eq_p:NN</code>	★	<code>\tl_if_eq_p:NN &lt;tl var<sub>1</sub>&gt; &lt;tl var<sub>2</sub>&gt;</code>
<code>\tl_if_eq_p:(Nc cN cc)</code>	★	<code>\tl_if_eq:NNTF &lt;tl var<sub>1</sub>&gt; &lt;tl var<sub>2</sub>&gt; {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\tl_if_eq:NNTF</code>	★	Compares the content of two <i>&lt;token list variables&gt;</i> and is logically <b>true</b> if the two contain the same list of tokens ( <i>i.e.</i> identical in both the list of characters they contain and the category codes of those characters). Thus for example
<code>\tl_if_eq:(Nc cN cc)TF</code>	★	

---

```

\tl_set:Nn \l_tmpa_tl { abc }
\tl_set:Nx \l_tmpb_tl { \tl_to_str:n { abc } }
\tl_if_eq:NNTF \l_tmpa_tl \l_tmpb_tl { true } { false }

```

yields **false**.

---

<code>\tl_if_eq:nnTF</code>	★	<code>\tl_if_eq:nnTF {&lt;token list<sub>1</sub>&gt;} {&lt;token list<sub>2</sub>&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>
-----------------------------	---	--

Tests if *<token list<sub>1</sub>>* and *<token list<sub>2</sub>>* contain the same list of tokens, both in respect of character codes and category codes.

---

<code>\tl_if_in:NnTF</code>	★	<code>\tl_if_in:NnTF &lt;tl var&gt; {&lt;token list&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\tl_if_in:cnTF</code>	★	Tests if the <i>&lt;token list&gt;</i> is found in the content of the <i>&lt;tl var&gt;</i> . The <i>&lt;token list&gt;</i> cannot contain the tokens <code>{</code> , <code>}</code> or <code>#</code> (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

---



---

<code>\tl_if_in:nnTF</code>	★	<code>\tl_if_in:nnTF {&lt;token list<sub>1</sub>&gt;} {&lt;token list<sub>2</sub>&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\tl_if_in:(Vn on no)TF</code>	★	Tests if <i>&lt;token list<sub>2</sub>&gt;</i> is found inside <i>&lt;token list<sub>1</sub>&gt;</i> . The <i>&lt;token list<sub>2</sub>&gt;</i> cannot contain the tokens <code>{</code> , <code>}</code> or <code>#</code> (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

---



---

<code>\tl_if_single_p:N</code>	★	<code>\tl_if_single_p:N &lt;tl var&gt;</code>
<code>\tl_if_single_p:c</code>	★	<code>\tl_if_single:NNTF &lt;tl var&gt; {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\tl_if_single:NNTF</code>	★	Tests if the content of the <i>&lt;tl var&gt;</i> consists of a single item, <i>i.e.</i> is a single normal token (neither an explicit space character nor a begin-group character) or a single brace group, surrounded by optional spaces on both sides. In other words, such a token list has token count 1 according to <code>\tl_count:N</code> .
<code>\tl_if_single:cTF</code>	★	

---

Updated: 2011-08-13

---

---

<code>\tl_if_single_p:n</code> ★	<code>\tl_if_single_p:n {⟨token list⟩}</code>
<code>\tl_if_single:nTF</code> ★	<code>\tl_if_single:nTF {⟨token list⟩} {⟨true code⟩} {⟨false code⟩}</code>

---

Updated: 2011-08-13

Tests if the *⟨token list⟩* has exactly one item, *i.e.* is a single normal token (neither an explicit space character nor a begin-group character) or a single brace group, surrounded by optional spaces on both sides. In other words, such a token list has token count 1 according to `\tl_count:n`.

---

<code>\tl_case:Nn</code> ★	<code>\tl_case:NnTF ⟨test token list variable⟩</code>
<code>\tl_case:cn</code> ★	<code>{</code>
<code>\tl_case:NnTF</code> ★	<code>  ⟨token list variable case<sub>1</sub>⟩ {⟨code case<sub>1</sub>⟩}</code>
<code>\tl_case:cnTF</code> ★	<code>  ⟨token list variable case<sub>2</sub>⟩ {⟨code case<sub>2</sub>⟩}</code>
	<code>  ...</code>
	<code>  ⟨token list variable case<sub>n</sub>⟩ {⟨code case<sub>n</sub>⟩}</code>
	<code>}</code>
	<code>{⟨true code⟩}</code>
	<code>{⟨false code⟩}</code>

---

New: 2013-07-24

This function compares the *⟨test token list variable⟩* in turn with each of the *⟨token list variable cases⟩*. If the two are equal (as described for `\tl_if_eq:NNTF`) then the associated *⟨code⟩* is left in the input stream and other cases are discarded. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\tl_case:Nn`, which does nothing if there is no match, is also available.

## 6 Mapping to token lists

---

<code>\tl_map_function:NN</code> ☆	<code>\tl_map_function:NN ⟨tl var⟩ ⟨function⟩</code>
<code>\tl_map_function:cN</code> ☆	

---

Updated: 2012-06-29

Applies *⟨function⟩* to every *⟨item⟩* in the *⟨tl var⟩*. The *⟨function⟩* receives one argument for each iteration. This may be a number of tokens if the *⟨item⟩* was stored within braces. Hence the *⟨function⟩* should anticipate receiving n-type arguments. See also `\tl_map_function:nN`.

---

<code>\tl_map_function:nN</code> ☆	<code>\tl_map_function:nN ⟨token list⟩ ⟨function⟩</code>
------------------------------------	--

---

Updated: 2012-06-29

Applies *⟨function⟩* to every *⟨item⟩* in the *⟨token list⟩*, The *⟨function⟩* receives one argument for each iteration. This may be a number of tokens if the *⟨item⟩* was stored within braces. Hence the *⟨function⟩* should anticipate receiving n-type arguments. See also `\tl_map_function:NN`.

---

<code>\tl_map_inline:Nn</code>	<code>\tl_map_inline:Nn ⟨tl var⟩ {⟨inline function⟩}</code>
<code>\tl_map_inline:cn</code>	

---

Updated: 2012-06-29

Applies the *⟨inline function⟩* to every *⟨item⟩* stored within the *⟨tl var⟩*. The *⟨inline function⟩* should consist of code which receives the *⟨item⟩* as #1. One in line mapping can be nested inside another. See also `\tl_map_function:NN`.

---

<code>\tl_map_inline:nn</code>	<code>\tl_map_inline:nn ⟨token list⟩ {⟨inline function⟩}</code>
--------------------------------	---

---

Updated: 2012-06-29

Applies the *⟨inline function⟩* to every *⟨item⟩* stored within the *⟨token list⟩*. The *⟨inline function⟩* should consist of code which receives the *⟨item⟩* as #1. One in line mapping can be nested inside another. See also `\tl_map_function:nN`.

<code>\tl_map_variable:NNn</code>	<code>\tl_map_variable:NNn &lt;tl var&gt; &lt;variable&gt; {&lt;function&gt;}</code>
<code>\tl_map_variable:cNn</code>	Applies the <i>&lt;function&gt;</i> to every <i>&lt;item&gt;</i> stored within the <i>&lt;tl var&gt;</i> . The <i>&lt;function&gt;</i> should consist of code which receives the <i>&lt;item&gt;</i> stored in the <i>&lt;variable&gt;</i> . One variable mapping can be nested inside another. See also <code>\tl_map_inline:Nn</code> .
Updated: 2012-06-29	

<code>\tl_map_variable:nNn</code>	<code>\tl_map_variable:nNn &lt;token list&gt; &lt;variable&gt; {&lt;function&gt;}</code>
Updated: 2012-06-29	Applies the <i>&lt;function&gt;</i> to every <i>&lt;item&gt;</i> stored within the <i>&lt;token list&gt;</i> . The <i>&lt;function&gt;</i> should consist of code which receives the <i>&lt;item&gt;</i> stored in the <i>&lt;variable&gt;</i> . One variable mapping can be nested inside another. See also <code>\tl_map_inline:nn</code> .

<code>\tl_map_break: ☆</code>	<code>\tl_map_break:</code>
Updated: 2012-06-29	Used to terminate a <code>\tl_map...</code> function before all entries in the <i>&lt;token list variable&gt;</i> have been processed. This normally takes place within a conditional statement, for example

```

\tl_map_inline:Nn \l_my_tl
{
  \str_if_eq:nnT { #1 } { bingo } { \tl_map_break: }
  % Do something useful
}

```

See also `\tl_map_break:n`. Use outside of a `\tl_map...` scenario leads to low level TeX errors.

**TeXhackers note:** When the mapping is broken, additional tokens may be inserted by the internal macro `\__prg_break_point:Nn` before the *<tokens>* are inserted into the input stream. This depends on the design of the mapping function.

<code>\tl_map_break:n ☆</code>	<code>\tl_map_break:n {&lt;tokens&gt;}</code>
Updated: 2012-06-29	Used to terminate a <code>\tl_map...</code> function before all entries in the <i>&lt;token list variable&gt;</i> have been processed, inserting the <i>&lt;tokens&gt;</i> after the mapping has ended. This normally takes place within a conditional statement, for example

```

\tl_map_inline:Nn \l_my_tl
{
  \str_if_eq:nnT { #1 } { bingo }
  { \tl_map_break:n { <tokens> } }
  % Do something useful
}

```

Use outside of a `\tl_map...` scenario leads to low level TeX errors.

**TeXhackers note:** When the mapping is broken, additional tokens may be inserted by the internal macro `\__prg_break_point:Nn` before the *<tokens>* are inserted into the input stream. This depends on the design of the mapping function.

## 7 Using token lists

---

<code>\tl_to_str:n</code>	★	<code>\tl_to_str:n {⟨token list⟩}</code>
<code>\tl_to_str:V</code>	★	

---

Converts the  $\langle token\ list \rangle$  to a  $\langle string \rangle$ , leaving the resulting character tokens in the input stream. A  $\langle string \rangle$  is a series of tokens with category code 12 (other) with the exception of spaces, which retain category code 10 (space).

**TeXhackers note:** Converting a  $\langle token\ list \rangle$  to a  $\langle string \rangle$  yields a concatenation of the string representations of every token in the  $\langle token\ list \rangle$ . The string representation of a control sequence is

- an escape character, whose character code is given by the internal parameter `\escapechar`, absent if the `\escapechar` is negative or greater than the largest character code;
- the control sequence name, as defined by `\cs_to_str:N`;
- a space, unless the control sequence name is a single character whose category at the time of expansion of `\tl_to_str:n` is not “letter”.

The string representation of an explicit character token is that character, doubled in the case of (explicit) macro parameter characters (normally #). In particular, the string representation of a token list may depend on the category codes in effect when it is evaluated, and the value of the `\escapechar`: for instance `\tl_to_str:n {\a}` normally produces the three character “backslash”, “lower-case a”, “space”, but it may also produce a single “lower-case a” if the escape character is negative and `a` is currently not a letter.

---

<code>\tl_to_str:N</code>	★	<code>\tl_to_str:N ⟨tl var⟩</code>
<code>\tl_to_str:c</code>	★	

---

Converts the content of the  $\langle tl\ var \rangle$  into a series of characters with category code 12 (other) with the exception of spaces, which retain category code 10 (space). This  $\langle string \rangle$  is then left in the input stream. For low-level details, see the notes given for `\tl_to_str:n`.

---

<code>\tl_use:N</code>	★	<code>\tl_use:N ⟨tl var⟩</code>
<code>\tl_use:c</code>	★	

---

Recovers the content of a  $\langle tl\ var \rangle$  and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Note that it is possible to use a  $\langle tl\ var \rangle$  directly without an accessor function.

## 8 Working with the content of token lists

---

<code>\tl_count:n</code>	★	<code>\tl_count:n {⟨tokens⟩}</code>
<code>\tl_count:(V o)</code>	★	

---

New: 2012-05-13

Counts the number of  $\langle items \rangle$  in  $\langle tokens \rangle$  and leaves this information in the input stream. Unbraced tokens count as one element as do each token group ( $\{ \dots \}$ ). This process ignores any unprotected spaces within  $\langle tokens \rangle$ . See also `\tl_count:N`. This function requires three expansions, giving an  $\langle integer\ denotation \rangle$ .



---

<code>\tl_count:N</code>	★
<code>\tl_count:c</code>	★
New: 2012-05-13	

---

`\tl_count:N`  $\langle tl\ var \rangle$

Counts the number of token groups in the  $\langle tl\ var \rangle$  and leaves this information in the input stream. Unbraced tokens count as one element as do each token group  $\{...\}$ . This process ignores any unprotected spaces within the  $\langle tl\ var \rangle$ . See also `\tl_count:n`. This function requires three expansions, giving an *integer denotation*.

---

<code>\tl_reverse:n</code>	★
<code>\tl_reverse:(V o)</code>	★
Updated: 2012-01-08	

---

`\tl_reverse:n`  $\{\langle token\ list \rangle\}$

Reverses the order of the  $\langle items \rangle$  in the  $\langle token\ list \rangle$ , so that  $\langle item_1 \rangle \langle item_2 \rangle \langle item_3 \rangle \dots \langle item_n \rangle$  becomes  $\langle item_n \rangle \dots \langle item_3 \rangle \langle item_2 \rangle \langle item_1 \rangle$ . This process preserves unprotected space within the  $\langle token\ list \rangle$ . Tokens are not reversed within braced token groups, which keep their outer set of braces. In situations where performance is important, consider `\tl_reverse_items:n`. See also `\tl_reverse:N`.

**TeXhackers note:** The result is returned within `\unexpanded`, which means that the token list does not expand further when appearing in an **x**-type argument expansion.

---

<code>\tl_reverse:N</code>	
<code>\tl_reverse:c</code>	
<code>\tl_greverse:N</code>	
<code>\tl_greverse:c</code>	
Updated: 2012-01-08	

---

`\tl_reverse:N`  $\langle tl\ var \rangle$

Reverses the order of the  $\langle items \rangle$  stored in  $\langle tl\ var \rangle$ , so that  $\langle item_1 \rangle \langle item_2 \rangle \langle item_3 \rangle \dots \langle item_n \rangle$  becomes  $\langle item_n \rangle \dots \langle item_3 \rangle \langle item_2 \rangle \langle item_1 \rangle$ . This process preserves unprotected spaces within the  $\langle token\ list\ variable \rangle$ . Braced token groups are copied without reversing the order of tokens, but keep the outer set of braces. See also `\tl_reverse:n`, and, for improved performance, `\tl_reverse_items:n`.

---

<code>\tl_reverse_items:n</code>	★
New: 2012-01-08	

---

`\tl_reverse_items:n`  $\{\langle token\ list \rangle\}$

Reverses the order of the  $\langle items \rangle$  stored in  $\langle tl\ var \rangle$ , so that  $\{\langle item_1 \rangle\} \{\langle item_2 \rangle\} \{\langle item_3 \rangle\} \dots \{\langle item_n \rangle\}$  becomes  $\{\langle item_n \rangle\} \dots \{\langle item_3 \rangle\} \{\langle item_2 \rangle\} \{\langle item_1 \rangle\}$ . This process removes any unprotected space within the  $\langle token\ list \rangle$ . Braced token groups are copied without reversing the order of tokens, and keep the outer set of braces. Items which are initially not braced are copied with braces in the result. In cases where preserving spaces is important, consider the slower function `\tl_reverse:n`.

**TeXhackers note:** The result is returned within `\unexpanded`, which means that the token list does not expand further when appearing in an **x**-type argument expansion.

---

<code>\tl_trim_spaces:n</code>	★
New: 2011-07-09	
Updated: 2012-06-25	

---

`\tl_trim_spaces:n`  $\{\langle token\ list \rangle\}$

Removes any leading and trailing explicit space characters (explicit tokens with character code 32 and category code 10) from the  $\langle token\ list \rangle$  and leaves the result in the input stream.

**TeXhackers note:** The result is returned within `\unexpanded`, which means that the token list does not expand further when appearing in an **x**-type argument expansion.

---

<code>\tl_trim_spaces:N</code>	
<code>\tl_trim_spaces:c</code>	
<code>\tl_gtrim_spaces:N</code>	
<code>\tl_gtrim_spaces:c</code>	
New: 2011-07-09	

---

`\tl_trim_spaces:N`  $\langle tl\ var \rangle$

Removes any leading and trailing explicit space characters (explicit tokens with character code 32 and category code 10) from the content of the  $\langle tl\ var \rangle$ . Note that this therefore *resets* the content of the variable.

<code>\tl_sort:Nn</code>	<code>\tl_sort:Nn &lt;tl var&gt; {&lt;comparison code&gt;}</code>
<code>\tl_sort:cn</code>	Sorts the items in the <i>&lt;tl var&gt;</i> according to the <i>&lt;comparison code&gt;</i> , and assigns the result to <i>&lt;tl var&gt;</i> . The details of sorting comparison are described in Section 1.
<code>\tl_gsort:Nn</code>	
<code>\tl_gsort:cn</code>	
New: 2017-02-06	

<code>\tl_sort:nN</code> ★	<code>\tl_sort:nN {&lt;token list&gt;} &lt;conditional&gt;</code>
New: 2017-02-06	Sorts the items in the <i>&lt;token list&gt;</i> , using the <i>&lt;conditional&gt;</i> to compare items, and leaves the result in the input stream. The <i>&lt;conditional&gt;</i> should have signature <code>:nnTF</code> , and return <b>true</b> if the two items being compared should be left in the same order, and <b>false</b> if the items should be swapped. The details of sorting comparison are described in Section 1.

**TeXhackers note:** The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an *x*-type argument expansion.

## 9 The first token from a token list

Functions which deal with either only the very first item (balanced text or single normal token) in a token list, or the remaining tokens.

<code>\tl_head:N</code> ★	<code>\tl_head:n {&lt;token list&gt;}</code>
<code>\tl_head:n</code> ★	Leaves in the input stream the first <i>&lt;item&gt;</i> in the <i>&lt;token list&gt;</i> , discarding the rest of the <i>&lt;token list&gt;</i> . All leading explicit space characters (explicit tokens with character code 32 and category code 10) are discarded; for example
<code>\tl_head:(V v f)</code> ★	
Updated: 2012-09-09	

`\tl_head:n { abc }`

and

`\tl_head:n { ~ abc }`

both leave **a** in the input stream. If the “head” is a brace group, rather than a single token, the braces are removed, and so

`\tl_head:n { ~ { ~ ab } c }`

yields `␣ab`. A blank *<token list>* (see `\tl_if_blank:nTF`) results in `\tl_head:n` leaving nothing in the input stream.

**TeXhackers note:** The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an *x*-type argument expansion.

---

<code>\tl_head:w</code>	★	<code>\tl_head:w &lt;token list&gt; { } \q_stop</code>
-------------------------	---	--

---

Leaves in the input stream the first *<token>* in the *<token list>*, discarding the rest of the *<token list>*. All leading explicit space characters (explicit tokens with character code 32 and category code 10) are discarded. A blank *<token list>* (which consists only of space characters) results in a low-level T<sub>E</sub>X error, which may be avoided by the inclusion of an empty group in the input (as shown), without the need for an explicit test. Alternatively, `\tl_if_blank:nF` may be used to avoid using the function with a “blank” argument. This function requires only a single expansion, and thus is suitable for use within an o-type expansion. In general, `\tl_head:n` should be preferred if the number of expansions is not critical.

---

<code>\tl_tail:N</code>	★	<code>\tl_tail:n &lt;{token list}&gt;</code>
<code>\tl_tail:n</code>	★	
<code>\tl_tail:(V v f)</code>	★	

---

Updated: 2012-09-01

Discards all leading explicit space characters (explicit tokens with character code 32 and category code 10) and the first *<token>* in the *<token list>*, and leaves the remaining tokens in the input stream. Thus for example

`\tl_tail:n { a ~ {bc} d }`

and

`\tl_tail:n { ~ a ~ {bc} d }`

both leave `\tl_tail:n` leaving nothing in the input stream. A blank *<token list>* (see `\tl_if_blank:nTF`) results in `\tl_tail:n` leaving nothing in the input stream.

**T<sub>E</sub>Xhackers note:** The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an x-type argument expansion.

---

<code>\tl_if_head_eq_catcode_p:nN</code>	★	<code>\tl_if_head_eq_catcode_p:nN &lt;{token list}&gt; &lt;test token&gt;</code>
<code>\tl_if_head_eq_catcode:nNTF</code>	★	<code>\tl_if_head_eq_catcode:nNTF &lt;{token list}&gt; &lt;test token&gt;</code>
		<code>{&lt;true code&gt;} {&lt;false code&gt;}</code>

---

Updated: 2012-07-09

Tests if the first *<token>* in the *<token list>* has the same category code as the *<test token>*. In the case where the *<token list>* is empty, the test is always **false**.

---

<code>\tl_if_head_eq_charcode_p:nN</code>	★	<code>\tl_if_head_eq_charcode_p:nN &lt;{token list}&gt; &lt;test token&gt;</code>
<code>\tl_if_head_eq_charcode_p:fN</code>	★	<code>\tl_if_head_eq_charcode:nNTF &lt;{token list}&gt; &lt;test token&gt;</code>
<code>\tl_if_head_eq_charcode:nNTF</code>	★	<code>{&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\tl_if_head_eq_charcode:fNTF</code>	★	

---

Updated: 2012-07-09

Tests if the first *<token>* in the *<token list>* has the same character code as the *<test token>*. In the case where the *<token list>* is empty, the test is always **false**.

---

<code>\tl_if_head_eq_meaning_p:nN</code>	★	<code>\tl_if_head_eq_meaning_p:nN &lt;{token list}&gt; &lt;test token&gt;</code>
<code>\tl_if_head_eq_meaning:nNTF</code>	★	<code>\tl_if_head_eq_meaning:nNTF &lt;{token list}&gt; &lt;test token&gt;</code>
		<code>{&lt;true code&gt;} {&lt;false code&gt;}</code>

---

Updated: 2012-07-09

Tests if the first *<token>* in the *<token list>* has the same meaning as the *<test token>*. In the case where *<token list>* is empty, the test is always **false**.

---

<code>\tl_if_head_is_group_p:n</code>	★	<code>\tl_if_head_is_group_p:n {⟨token list⟩}</code>
<code>\tl_if_head_is_group:nTF</code>	★	<code>\tl_if_head_is_group:nTF {⟨token list⟩} {⟨true code⟩} {⟨false code⟩}</code>

---

New: 2012-07-08

Tests if the first *⟨token⟩* in the *⟨token list⟩* is an explicit begin-group character (with category code 1 and any character code), in other words, if the *⟨token list⟩* starts with a brace group. In particular, the test is **false** if the *⟨token list⟩* starts with an implicit token such as `\c_group_begin_token`, or if it is empty. This function is useful to implement actions on token lists on a token by token basis.

---

<code>\tl_if_head_is_N_type_p:n</code>	★	<code>\tl_if_head_is_N_type_p:n {⟨token list⟩}</code>
<code>\tl_if_head_is_N_type:nTF</code>	★	<code>\tl_if_head_is_N_type:nTF {⟨token list⟩} {⟨true code⟩} {⟨false code⟩}</code>

---

New: 2012-07-08

Tests if the first *⟨token⟩* in the *⟨token list⟩* is a normal N-type argument. In other words, it is neither an explicit space character (explicit token with character code 32 and category code 10) nor an explicit begin-group character (with category code 1 and any character code). An empty argument yields **false**, as it does not have a “normal” first token. This function is useful to implement actions on token lists on a token by token basis.

---

<code>\tl_if_head_is_space_p:n</code>	★	<code>\tl_if_head_is_space_p:n {⟨token list⟩}</code>
<code>\tl_if_head_is_space:nTF</code>	★	<code>\tl_if_head_is_space:nTF {⟨token list⟩} {⟨true code⟩} {⟨false code⟩}</code>

---

Updated: 2012-07-08

Tests if the first *⟨token⟩* in the *⟨token list⟩* is an explicit space character (explicit token with character code 12 and category code 10). In particular, the test is **false** if the *⟨token list⟩* starts with an implicit token such as `\c_space_token`, or if it is empty. This function is useful to implement actions on token lists on a token by token basis.

## 10 Using a single item

---

<code>\tl_item:nn</code>	★	<code>\tl_item:nn {⟨token list⟩} {⟨integer expression⟩}</code>
<code>\tl_item:Nn</code>	★	
<code>\tl_item:cn</code>	★	

---

New: 2014-07-17

Indexing items in the *⟨token list⟩* from 1 on the left, this function evaluates the *⟨integer expression⟩* and leaves the appropriate item from the *⟨token list⟩* in the input stream. If the *⟨integer expression⟩* is negative, indexing occurs from the right of the token list, starting at  $-1$  for the right-most item. If the index is out of bounds, then the function expands to nothing.

**TeXhackers note:** The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *⟨item⟩* does not expand further when appearing in an x-type argument expansion.

## 11 Viewing token lists

---

<code>\tl_show:N</code>	<code>\tl_show:N ⟨tl var⟩</code>
<code>\tl_show:c</code>	

---

Updated: 2015-08-01

Displays the content of the *⟨tl var⟩* on the terminal.

**TeXhackers note:** This is similar to the TeX primitive `\show`, wrapped to a fixed number of characters per line.

<hr/> <code>\tl_show:n</code> <hr/>	<code>\tl_show:n &lt;token list&gt;</code>
<code>Updated: 2015-08-07</code>	Displays the <i>&lt;token list&gt;</i> on the terminal.

**TeXhackers note:** This is similar to the  $\epsilon$ -TeX primitive `\showtokens`, wrapped to a fixed number of characters per line.

<hr/> <code>\tl_log:N</code> <code>\tl_log:c</code> <hr/>	<code>\tl_log:N &lt;tl var&gt;</code>
<code>New: 2014-08-22</code> <code>Updated: 2015-08-01</code>	Writes the content of the <i>&lt;tl var&gt;</i> in the log file. See also <code>\tl_show:N</code> which displays the result in the terminal.

<hr/> <code>\tl_log:n</code> <hr/>	<code>\tl_log:n {\&lt;token list&gt;}</code>
<code>New: 2014-08-22</code> <code>Updated: 2015-08-07</code>	Writes the <i>&lt;token list&gt;</i> in the log file. See also <code>\tl_show:n</code> which displays the result in the terminal.

## 12 Constant token lists

<hr/> <code>\c_empty_tl</code> <hr/>	Constant that is always empty.
--------------------------------------	--------------------------------

<hr/> <code>\c_space_tl</code> <hr/>	An explicit space character contained in a token list (compare this with <code>\c_space_token</code> ). For use where an explicit space is required.
--------------------------------------	--

## 13 Scratch token lists

<hr/> <code>\l_tmpa_tl</code> <code>\l_tmpb_tl</code> <hr/>	Scratch token lists for local assignment. These are never used by the kernel code, and so are safe for use with any L <sup>A</sup> T <sub>E</sub> X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	---

<hr/> <code>\g_tmpa_tl</code> <code>\g_tmpb_tl</code> <hr/>	Scratch token lists for global assignment. These are never used by the kernel code, and so are safe for use with any L <sup>A</sup> T <sub>E</sub> X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	--

## 14 Internal functions

<hr/> <code>\__tl_trim_spaces:nn</code> <hr/>	<code>\__tl_trim_spaces:nn { \q_mark &lt;token list&gt; } {\&lt;continuation&gt;}</code>
	This function removes all leading and trailing explicit space characters from the <i>&lt;token list&gt;</i> , and expands to the <i>&lt;continuation&gt;</i> , followed by a brace group containing <code>\use_none:n \q_mark &lt;trimmed token list&gt;</code> . For instance, <code>\tl_trim_spaces:n</code> is implemented by taking the <i>&lt;continuation&gt;</i> to be <code>\exp_not:o</code> , and the o-type expansion removes the <code>\q_mark</code> . This function is also used in <code>l3clist</code> and <code>l3candidates</code> .

## Part VII

# The l3str package

## Strings

TeX associates each character with a category code: as such, there is no concept of a “string” as commonly understood in many other programming languages. However, there are places where we wish to manipulate token lists while in some sense “ignoring” category codes: this is done by treating token lists as strings in a TeX sense.

A TeX string (and thus an expl3 string) is a series of characters which have category code 12 (“other”) with the exception of space characters which have category code 10 (“space”). Thus at a technical level, a TeX string is a token list with the appropriate category codes. In this documentation, these are simply referred to as strings.

String variables are simply specialised token lists, but by convention should be named with the suffix `...str`. Such variables should contain characters with category code 12 (other), except spaces, which have category code 10 (blank space). All the functions in this module which accept a token list argument first convert it to a string using `\tl_to_str:n` for internal processing, and do not treat a token list or the corresponding string representation differently.

As a string is a subset of the more general token list, it is sometimes unclear when one should be used over the other. Use a string variable for data that isn’t primarily intended for typesetting and for which a level of protection from unwanted expansion is suitable. This data type simplifies comparison of variables since there are no concerns about expansion of their contents.

Note that as string variables are a special case of token list variables the coverage of `\str_...:N` functions is somewhat smaller than `\tl_...:N`.

The functions `\cs_to_str:N`, `\tl_to_str:n`, `\tl_to_str:N` and `\token_to_str:N` (and variants) generate strings from the appropriate input: these are documented in `l3basics`, `l3tl` and `l3token`, respectively.

Most expandable functions in this module come in three flavours:

- `\str_...:N`, which expect a token list or string variable as their argument;
- `\str_...:n`, taking any token list (or string) as an argument;
- `\str_..._ignore_spaces:n`, which ignores any space encountered during the operation: these functions are typically faster than those which take care of escaping spaces appropriately.

## 1 Building strings

---

`\str_new:N`

`\str_new:c`

---

New: 2015-09-18

`\str_new:N <str var>`

Creates a new `<str var>` or raises an error if the name is already taken. The declaration is global. The `<str var>` is initially empty.

<hr/> <code>\str_const:Nn</code> <code>\str_const:(Nx cn cx)</code> <hr/> New: 2015-09-18 <hr/>	<code>\str_const:Nn &lt;str var&gt; {&lt;token list&gt;}</code> Creates a new constant $\langle str var \rangle$ or raises an error if the name is already taken. The value of the $\langle str var \rangle$ is set globally to the $\langle token list \rangle$ , converted to a string.
<hr/> <code>\str_clear:N</code> <code>\str_clear:c</code> <code>\str_gclear:N</code> <code>\str_gclear:c</code> <hr/> New: 2015-09-18 <hr/>	<code>\str_clear:N &lt;str var&gt;</code> Clears the content of the $\langle str var \rangle$ .
<hr/> <code>\str_clear_new:N</code> <code>\str_clear_new:c</code> <hr/> New: 2015-09-18 <hr/>	<code>\str_clear_new:N &lt;str var&gt;</code> Ensures that the $\langle str var \rangle$ exists globally by applying <code>\str_new:N</code> if necessary, then applies <code>\str_(g)clear:N</code> to leave the $\langle str var \rangle$ empty.
<hr/> <code>\str_set_eq:NN</code> <code>\str_set_eq:(cN Nc cc)</code> <code>\str_gset_eq:NN</code> <code>\str_gset_eq:(cN Nc cc)</code> <hr/> New: 2015-09-18 <hr/>	<code>\str_set_eq:NN &lt;str var&gt;_1 &lt;str var&gt;_2</code> Sets the content of $\langle str var_1 \rangle$ equal to that of $\langle str var_2 \rangle$ .

## 2 Adding data to string variables

<hr/> <code>\str_set:Nn</code> <code>\str_set:(Nx cn cx)</code> <code>\str_gset:Nn</code> <code>\str_gset:(Nx cn cx)</code> <hr/> New: 2015-09-18 <hr/>	<code>\str_set:Nn &lt;str var&gt; {&lt;token list&gt;}</code> Converts the $\langle token list \rangle$ to a $\langle string \rangle$ , and stores the result in $\langle str var \rangle$ .
<hr/> <code>\str_put_left:Nn</code> <code>\str_put_left:(Nx cn cx)</code> <code>\str_gput_left:Nn</code> <code>\str_gput_left:(Nx cn cx)</code> <hr/> New: 2015-09-18 <hr/>	<code>\str_put_left:Nn &lt;str var&gt; {&lt;token list&gt;}</code> Converts the $\langle token list \rangle$ to a $\langle string \rangle$ , and prepends the result to $\langle str var \rangle$ . The current contents of the $\langle str var \rangle$ are not automatically converted to a string.
<hr/> <code>\str_put_right:Nn</code> <code>\str_put_right:(Nx cn cx)</code> <code>\str_gput_right:Nn</code> <code>\str_gput_right:(Nx cn cx)</code> <hr/> New: 2015-09-18 <hr/>	<code>\str_put_right:Nn &lt;str var&gt; {&lt;token list&gt;}</code> Converts the $\langle token list \rangle$ to a $\langle string \rangle$ , and appends the result to $\langle str var \rangle$ . The current contents of the $\langle str var \rangle$ are not automatically converted to a string.

## 2.1 String conditionals

---

<code>\str_if_exist_p:N</code>	★	<code>\str_if_exist_p:N</code>	$\langle str\ var \rangle$
<code>\str_if_exist_p:c</code>	★	<code>\str_if_exist:NTF</code>	$\langle str\ var \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$
<code>\str_if_exist:NTF</code>	★	Tests whether the $\langle str\ var \rangle$ is currently defined. This does not check that the $\langle str\ var \rangle$ really is a string.	
<code>\str_if_exist:cTF</code>	★		

---

New: 2015-09-18

---



---

<code>\str_if_empty_p:N</code>	★	<code>\str_if_empty_p:N</code>	$\langle str\ var \rangle$
<code>\str_if_empty_p:c</code>	★	<code>\str_if_empty:NTF</code>	$\langle str\ var \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$
<code>\str_if_empty:NTF</code>	★	Tests if the $\langle string\ variable \rangle$ is entirely empty ( <i>i.e.</i> contains no characters at all).	
<code>\str_if_empty:cTF</code>	★		

---

New: 2015-09-18

---



---

<code>\str_if_eq_p:NN</code>	★	<code>\str_if_eq_p:NN</code>	$\langle str\ var_1 \rangle$ $\langle str\ var_2 \rangle$
<code>\str_if_eq_p:(Nc cN cc)</code>	★	<code>\str_if_eq:NNTF</code>	$\langle str\ var_1 \rangle$ $\langle str\ var_2 \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$
<code>\str_if_eq:NNTF</code>	★	Compares the content of two $\langle str\ variables \rangle$ and is logically <b>true</b> if the two contain the same characters.	
<code>\str_if_eq:(Nc cN cc)TF</code>	★		

---

New: 2015-09-18

---



---

<code>\str_if_eq_p:nn</code>	★	<code>\str_if_eq_p:nn</code>	$\{\langle t_1 \rangle\}$ $\{\langle t_2 \rangle\}$
<code>\str_if_eq_p:(Vn on no nV VV)</code>	★	<code>\str_if_eq:nnTF</code>	$\{\langle t_1 \rangle\}$ $\{\langle t_2 \rangle\}$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$
<code>\str_if_eq:nnTF</code>	★	Compares the two $\langle token\ lists \rangle$ on a character by character basis, and is <b>true</b> if the two lists contain the same characters in the same order. Thus for example	
<code>\str_if_eq:(Vn on no nV VV)TF</code>	★		

---

Compares the two  $\langle token\ lists \rangle$  on a character by character basis, and is **true** if the two lists contain the same characters in the same order. Thus for example

`\str_if_eq_p:no { abc } { \tl_to_str:n { abc } }`

is logically **true**.

---

<code>\str_if_eq_x_p:nn</code>	★	<code>\str_if_eq_x_p:nn</code>	$\{\langle t_1 \rangle\}$ $\{\langle t_2 \rangle\}$
<code>\str_if_eq_x:nnTF</code>	★	<code>\str_if_eq_x:nnTF</code>	$\{\langle t_1 \rangle\}$ $\{\langle t_2 \rangle\}$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

---

New: 2012-06-05

---

Compares the full expansion of two  $\langle token\ lists \rangle$  on a character by character basis, and is **true** if the two lists contain the same characters in the same order. Thus for example

`\str_if_eq_x_p:nn { abc } { \tl_to_str:n { abc } }`

is logically **true**.



---

<code>\str_case:nn</code>	★	<code>\str_case:nnTF {⟨test string⟩}</code>
<code>\str_case:(on nV nv)</code>	★	{
<code>\str_case:nnTF</code>	★	{⟨string case <sub>1</sub> ⟩} {⟨code case <sub>1</sub> ⟩}
<code>\str_case:(on nV nv)TF</code>	★	{⟨string case <sub>2</sub> ⟩} {⟨code case <sub>2</sub> ⟩}
		...
		{⟨string case <sub>n</sub> ⟩} {⟨code case <sub>n</sub> ⟩}
		}
		{⟨true code⟩}
		{⟨false code⟩}

---

New: 2013-07-24  
Updated: 2015-02-28

---

This function compares the *⟨test string⟩* in turn with each of the *⟨string cases⟩*. If the two are equal (as described for `\str_if_eq:nnTF` then the associated *⟨code⟩* is left in the input stream and other cases are discarded. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\str_case:nn`, which does nothing if there is no match, is also available.

---

<code>\str_case_x:nnTF</code>	★	<code>\str_case_x:nnTF {⟨test string⟩}</code>
		{
		{⟨string case <sub>1</sub> ⟩} {⟨code case <sub>1</sub> ⟩}
		{⟨string case <sub>2</sub> ⟩} {⟨code case <sub>2</sub> ⟩}
		...
		{⟨string case <sub>n</sub> ⟩} {⟨code case <sub>n</sub> ⟩}
		}
		{⟨true code⟩}
		{⟨false code⟩}

---

New: 2013-07-24

---

This function compares the full expansion of the *⟨test string⟩* in turn with the full expansion of the *⟨string cases⟩*. If the two full expansions are equal (as described for `\str_if_eq:nnTF` then the associated *⟨code⟩* is left in the input stream and other cases are discarded. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\str_case_x:nn`, which does nothing if there is no match, is also available. The *⟨test string⟩* is expanded in each comparison, and must always yield the same result: for example, random numbers must not be used within this string.

### 3 Working with the content of strings

---

<code>\str_use:N</code>	★	<code>\str_use:N ⟨str var⟩</code>
<code>\str_use:c</code>	★	

---

New: 2015-09-18

---

Recovers the content of a *⟨str var⟩* and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Note that it is possible to use a *⟨str⟩* directly without an accessor function.

---

<code>\str_count:N</code>	★	<code>\str_count:n {⟨token list⟩}</code>
<code>\str_count:c</code>	★	
<code>\str_count:n</code>	★	
<code>\str_count_ignore_spaces:n</code>	★	

---

New: 2015-09-18

Leaves in the input stream the number of characters in the string representation of  $\langle token list \rangle$ , as an integer denotation. The functions differ in their treatment of spaces. In the case of `\str_count:N` and `\str_count:n`, all characters including spaces are counted. The `\str_count_ignore_spaces:n` function leaves the number of non-space characters in the input stream.

---

<code>\str_count_spaces:N</code>	★	<code>\str_count_spaces:n {⟨token list⟩}</code>
<code>\str_count_spaces:c</code>	★	
<code>\str_count_spaces:n</code>	★	

---

New: 2015-09-18

Leaves in the input stream the number of space characters in the string representation of  $\langle token list \rangle$ , as an integer denotation. Of course, this function has no `_ignore_spaces` variant.

---

<code>\str_head:N</code>	★	<code>\str_head:n {⟨token list⟩}</code>
<code>\str_head:c</code>	★	
<code>\str_head:n</code>	★	
<code>\str_head_ignore_spaces:n</code>	★	

---

New: 2015-09-18

Converts the  $\langle token list \rangle$  into a  $\langle string \rangle$ . The first character in the  $\langle string \rangle$  is then left in the input stream, with category code “other”. The functions differ if the first character is a space: `\str_head:N` and `\str_head:n` return a space token with category code 10 (blank space), while the `\str_head_ignore_spaces:n` function ignores this space character and leaves the first non-space character in the input stream. If the  $\langle string \rangle$  is empty (or only contains spaces in the case of the `_ignore_spaces` function), then nothing is left on the input stream.

---

<code>\str_tail:N</code>	★	<code>\str_tail:n {⟨token list⟩}</code>
<code>\str_tail:c</code>	★	
<code>\str_tail:n</code>	★	
<code>\str_tail_ignore_spaces:n</code>	★	

---

New: 2015-09-18

Converts the  $\langle token list \rangle$  to a  $\langle string \rangle$ , removes the first character, and leaves the remaining characters (if any) in the input stream, with category codes 12 and 10 (for spaces). The functions differ in the case where the first character is a space: `\str_tail:N` and `\str_tail:n` only trim that space, while `\str_tail_ignore_spaces:n` removes the first non-space character and any space before it. If the  $\langle token list \rangle$  is empty (or blank in the case of the `_ignore_spaces` variant), then nothing is left on the input stream.

---

<code>\str_item:Nn</code>	★	<code>\str_item:nn {⟨token list⟩} {⟨integer expression⟩}</code>
<code>\str_item:nn</code>	★	
<code>\str_item_ignore_spaces:nn</code>	★	

---

New: 2015-09-18

---

Converts the *⟨token list⟩* to a *⟨string⟩*, and leaves in the input stream the character in position *⟨integer expression⟩* of the *⟨string⟩*, starting at 1 for the first (left-most) character. In the case of `\str_item:Nn` and `\str_item:nn`, all characters including spaces are taken into account. The `\str_item_ignore_spaces:nn` function skips spaces when counting characters. If the *⟨integer expression⟩* is negative, characters are counted from the end of the *⟨string⟩*. Hence,  $-1$  is the right-most character, *etc.*

---

<code>\str_range:Nnn</code>	★	<code>\str_range:nnn {⟨token list⟩} {⟨start index⟩} {⟨end index⟩}</code>
<code>\str_range:cnn</code>	★	
<code>\str_range:nnn</code>	★	
<code>\str_range_ignore_spaces:nnn</code>	★	

---

New: 2015-09-18

---

Converts the *⟨token list⟩* to a *⟨string⟩*, and leaves in the input stream the characters from the *⟨start index⟩* to the *⟨end index⟩* inclusive. Positive *⟨indices⟩* are counted from the start of the string, 1 being the first character, and negative *⟨indices⟩* are counted from the end of the string,  $-1$  being the last character. If either of *⟨start index⟩* or *⟨end index⟩* is 0, the result is empty. For instance,

```
\iow_term:x { \str_range:nnn { abcdef } { 2 } { 5 } }
\iow_term:x { \str_range:nnn { abcdef } { -4 } { -1 } }
\iow_term:x { \str_range:nnn { abcdef } { -2 } { -1 } }
\iow_term:x { \str_range:nnn { abcdef } { 0 } { -1 } }
```

prints `bcde`, `cdef`, `ef`, and an empty line to the terminal. The *⟨start index⟩* must always be smaller than or equal to the *⟨end index⟩*: if this is not the case then no output is generated. Thus

```
\iow_term:x { \str_range:nnn { abcdef } { 5 } { 2 } }
\iow_term:x { \str_range:nnn { abcdef } { -1 } { -4 } }
```

both yield empty strings.

## 4 String manipulation

---

<code>\str_lower_case:n</code>	★	<code>\str_lower_case:n {⟨tokens⟩}</code>
<code>\str_lower_case:f</code>	★	<code>\str_upper_case:n {⟨tokens⟩}</code>
<code>\str_upper_case:n</code>	★	
<code>\str_upper_case:f</code>	★	

---

New: 2015-03-01

Converts the input  $\langle tokens \rangle$  to their string representation, as described for `\tl_to_str:n`, and then to the lower or upper case representation using a one-to-one mapping as described by the Unicode Consortium file `UnicodeData.txt`.

These functions are intended for case changing programmatic data in places where upper/lower case distinctions are meaningful. One example would be automatically generating a function name from user input where some case changing is needed. In this situation the input is programmatic, not textual, case does have meaning and a language-independent one-to-one mapping is appropriate. For example

```
\cs_new_protected:Npn \myfunc:nn #1#2
{
  \cs_set_protected:cpn
  {
    user
    \str_upper_case:f { \tl_head:n {#1} }
    \str_lower_case:f { \tl_tail:n {#1} }
  }
  { #2 }
}
```

would be used to generate a function with an auto-generated name consisting of the upper case equivalent of the supplied name followed by the lower case equivalent of the rest of the input.

These functions should *not* be used for

- Caseless comparisons: use `\str_fold_case:n` for this situation (case folding is distinct from lower casing).
- Case changing text for typesetting: see the `\tl_lower_case:n(n)`, `\tl_upper_case:n(n)` and `\tl_mixed_case:n(n)` functions which correctly deal with context-dependence and other factors appropriate to text case changing.

**T<sub>E</sub>Xhackers note:** As with all `expl3` functions, the input supported by `\str_fold_case:n` is *engine-native* characters which are or interoperate with UTF-8. As such, when used with pdfT<sub>E</sub>X *only* the Latin alphabet characters A–Z are case-folded (*i.e.* the ASCII range which coincides with UTF-8). Full UTF-8 support is available with both X<sub>Ǝ</sub>T<sub>E</sub>X and LuaT<sub>E</sub>X, subject only to the fact that X<sub>Ǝ</sub>T<sub>E</sub>X in particular has issues with characters of code above hexadecimal 0xFFFF when interacting with `\tl_to_str:n`.

---

`\str_fold_case:n` ★  
`\str_fold_case:V` ★

---

New: 2014-06-19  
Updated: 2016-03-07

---

`\str_fold_case:n`  $\{(tokens)\}$

Converts the input  $\langle tokens \rangle$  to their string representation, as described for `\tl_to_str:n`, and then folds the case of the resulting  $\langle string \rangle$  to remove case information. The result of this process is left in the input stream.

String folding is a process used for material such as identifiers rather than for “text”. The folding provided by `\str_fold_case:n` follows the mappings provided by the [Unicode Consortium](#), who [state](#):

Case folding is primarily used for caseless comparison of text, such as identifiers in a computer program, rather than actual text transformation. Case folding in Unicode is based on the lowercase mapping, but includes additional changes to the source text to help make it language-insensitive and consistent. As a result, case-folded text should be used solely for internal processing and generally should not be stored or displayed to the end user.

The folding approach implemented by `\str_fold_case:n` follows the “full” scheme defined by the Unicode Consortium (*e.g.* `SS` folds to `ss`). As case-folding is a language-insensitive process, there is no special treatment of Turkic input (*i.e.* `I` always folds to `i` and not to `ı`).

**TeXhackers note:** As with all `expl3` functions, the input supported by `\str_fold_case:n` is *engine-native* characters which are or interoperate with UTF-8. As such, when used with pdfTeX *only* the Latin alphabet characters A–Z are case-folded (*i.e.* the ASCII range which coincides with UTF-8). Full UTF-8 support is available with both XeTeX and LuaTeX, subject only to the fact that XeTeX in particular has issues with characters of code above hexadecimal 0xFFFF when interacting with `\tl_to_str:n`.

## 5 Viewing strings

---

`\str_show:N`  
`\str_show:c`  
`\str_show:n`

---

New: 2015-09-18

---

`\str_show:N`  $\langle str\ var \rangle$

Displays the content of the  $\langle str\ var \rangle$  on the terminal.

## 6 Constant token lists

---

```

\c_ampersand_str
\c_atsign_str
\c_backslash_str
\c_left_brace_str
\c_right_brace_str
\c_circumflex_str
\c_colon_str
\c_dollar_str
\c_hash_str
\c_percent_str
\c_tilde_str
\c_underscore_str

```

---

New: 2015-09-19

---

Constant strings, containing a single character token, with category code 12.

## 7 Scratch strings

---

```

\l_tmpa_str
\l_tmpb_str

```

---

Scratch strings for local assignment. These are never used by the kernel code, and so are safe for use with any L<sup>A</sup>T<sub>E</sub>X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

---

```

\g_tmpa_str
\g_tmpb_str

```

---

Scratch strings for global assignment. These are never used by the kernel code, and so are safe for use with any L<sup>A</sup>T<sub>E</sub>X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

### 7.1 Internal string functions

---

```

\__str_if_eq_x:nn ★ \__str_if_eq_x:nn {\t1} {\t2}

```

---

Compares the full expansion of two *<token lists>* on a character by character basis, and is `true` if the two lists contain the same characters in the same order. Leaves 0 in the input stream if the condition is true, and +1 or -1 otherwise.

---

```

\__str_if_eq_x_return:nn \__str_if_eq_x_return:nn {\t1} {\t2}

```

---

Compares the full expansion of two *<token lists>* on a character by character basis, and is `true` if the two lists contain the same characters in the same order. Either `\prg_return_true:` or `\prg_return_false:` is then left in the input stream. This is a version of `\str_if_eq_x:nnTF` coded for speed.

---

```

\__str_to_other:n ★ \__str_to_other:n {\token list}

```

---

Converts the *<token list>* to a *<other string>*, where spaces have category code “other”. This function can be f-expanded without fear of losing a leading space, since spaces do not have category code 10 in its result. It takes a time quadratic in the character count of the string.

<hr/> <hr/>	<code>\__str_to_other_fast:n</code> ☆	<code>\__str_to_other_fast:n {⟨token list⟩}</code>	Same behaviour <code>\__str_to_other:n</code> but only restricted-expandable. It takes a time linear in the character count of the string. It is used for <code>\iow_wrap:nnnN</code> .
<hr/> <hr/>	<code>\__str_count:n</code> ★	<code>\__str_count:n {⟨other string⟩}</code>	This function expects an argument that is entirely made of characters with category “other”, as produced by <code>\__str_to_other:n</code> . It leaves in the input stream the number of character tokens in the <i>⟨other string⟩</i> , faster than the analogous <code>\str_count:n</code> function.
<hr/> <hr/>	<code>\__str_range:nnn</code> ★	<code>\__str_range:nnn {⟨other string⟩} {⟨start index⟩} {⟨end index⟩}</code>	Identical to <code>\str_range:nnn</code> except that the first argument is expected to be entirely made of characters with category “other”, as produced by <code>\__str_to_other:n</code> , and the result is also an <i>⟨other string⟩</i> .

## Part VIII

# The l3seq package

## Sequences and stacks

L<sup>A</sup>T<sub>E</sub>X3 implements a “sequence” data type, which contain an ordered list of entries which may contain any *balanced text*. It is possible to map functions to sequences such that the function is applied to every item in the sequence.

Sequences are also used to implement stack functions in L<sup>A</sup>T<sub>E</sub>X3. This is achieved using a number of dedicated stack functions.

### 1 Creating and initialising sequences

---

<code>\seq_new:N</code>	<code>\seq_new:N &lt;sequence&gt;</code>
<code>\seq_new:c</code>	

---

Creates a new *<sequence>* or raises an error if the name is already taken. The declaration is global. The *<sequence>* initially contains no items.

---

<code>\seq_clear:N</code>	<code>\seq_clear:N &lt;sequence&gt;</code>
<code>\seq_clear:c</code>	
<code>\seq_gclear:N</code>	
<code>\seq_gclear:c</code>	

---

Clears all items from the *<sequence>*.

---

<code>\seq_clear_new:N</code>	<code>\seq_clear_new:N &lt;sequence&gt;</code>
<code>\seq_clear_new:c</code>	
<code>\seq_gclear_new:N</code>	
<code>\seq_gclear_new:c</code>	

---

Ensures that the *<sequence>* exists globally by applying `\seq_new:N` if necessary, then applies `\seq_(g)clear:N` to leave the *<sequence>* empty.

---

<code>\seq_set_eq:NN</code>	<code>\seq_set_eq:NN &lt;sequence<sub>1</sub>&gt; &lt;sequence<sub>2</sub>&gt;</code>
<code>\seq_set_eq:(cN Nc cc)</code>	
<code>\seq_gset_eq:NN</code>	
<code>\seq_gset_eq:(cN Nc cc)</code>	

---

Sets the content of *<sequence<sub>1</sub>>* equal to that of *<sequence<sub>2</sub>>*.

---

<code>\seq_set_from_clist:NN</code>	<code>\seq_set_from_clist:NN &lt;sequence&gt; &lt;comma-list&gt;</code>
<code>\seq_set_from_clist:(cN Nc cc)</code>	
<code>\seq_set_from_clist:Nn</code>	
<code>\seq_set_from_clist:cn</code>	
<code>\seq_gset_from_clist:NN</code>	
<code>\seq_gset_from_clist:(cN Nc cc)</code>	
<code>\seq_gset_from_clist:Nn</code>	
<code>\seq_gset_from_clist:cn</code>	

---

New: 2014-07-17

Converts the data in the *<comma list>* into a *<sequence>*: the original *<comma list>* is unchanged.



---

```

\seq_set_split:Nnn
\seq_set_split:NnV
\seq_gset_split:Nnn
\seq_gset_split:NnV

```

---

New: 2011-08-15  
Updated: 2012-07-02

---

```
\seq_set_split:Nnn <sequence> {<delimiter>} {<token list>}
```

Splits the  $\langle token list \rangle$  into  $\langle items \rangle$  separated by  $\langle delimiter \rangle$ , and assigns the result to the  $\langle sequence \rangle$ . Spaces on both sides of each  $\langle item \rangle$  are ignored, then one set of outer braces is removed (if any); this space trimming behaviour is identical to that of `l3clist` functions. Empty  $\langle items \rangle$  are preserved by `\seq_set_split:Nnn`, and can be removed afterwards using `\seq_remove_all:Nn <sequence> {<>}`. The  $\langle delimiter \rangle$  may not contain `{`, `}` or `#` (assuming  $\text{\TeX}$ 's normal category code régime). If the  $\langle delimiter \rangle$  is empty, the  $\langle token list \rangle$  is split into  $\langle items \rangle$  as a  $\langle token list \rangle$ .

---

```

\seq_concat:Nnn
\seq_concat:ccc
\seq_gconcat:Nnn
\seq_gconcat:ccc

```

---

```
\seq_concat:Nnn <sequence1> <sequence2> <sequence3>
```

Concatenates the content of  $\langle sequence_2 \rangle$  and  $\langle sequence_3 \rangle$  together and saves the result in  $\langle sequence_1 \rangle$ . The items in  $\langle sequence_2 \rangle$  are placed at the left side of the new sequence.

---

```

\seq_if_exist_p:N *
\seq_if_exist_p:c *
\seq_if_exist:NTF *
\seq_if_exist:cTF *

```

---

New: 2012-03-03

---

```
\seq_if_exist_p:N <sequence>
```

```
\seq_if_exist:NNTF <sequence> {<true code>} {<false code>}
```

Tests whether the  $\langle sequence \rangle$  is currently defined. This does not check that the  $\langle sequence \rangle$  really is a sequence variable.

## 2 Appending data to sequences

---

```

\seq_put_left:Nn
\seq_put_left:(NV|Nv|No|Nx|cn|cV|cv|co|cx)
\seq_gput_left:Nn
\seq_gput_left:(NV|Nv|No|Nx|cn|cV|cv|co|cx)

```

---

```
\seq_put_left:Nn <sequence> {<item>}
```

Appends the  $\langle item \rangle$  to the left of the  $\langle sequence \rangle$ .

---

```

\seq_put_right:Nn
\seq_put_right:(NV|Nv|No|Nx|cn|cV|cv|co|cx)
\seq_gput_right:Nn
\seq_gput_right:(NV|Nv|No|Nx|cn|cV|cv|co|cx)

```

---

```
\seq_put_right:Nn <sequence> {<item>}
```

Appends the  $\langle item \rangle$  to the right of the  $\langle sequence \rangle$ .

## 3 Recovering items from sequences

Items can be recovered from either the left or the right of sequences. For implementation reasons, the actions at the left of the sequence are faster than those acting on the right. These functions all assign the recovered material locally, *i.e.* setting the  $\langle token list variable \rangle$  used with `\tl_set:Nn` and *never* `\tl_gset:Nn`.

---

```

\seq_get_left:NN
\seq_get_left:cN

```

---

Updated: 2012-05-14

---

```
\seq_get_left:NN <sequence> <token list variable>
```

Stores the left-most item from a  $\langle sequence \rangle$  in the  $\langle token list variable \rangle$  without removing it from the  $\langle sequence \rangle$ . The  $\langle token list variable \rangle$  is assigned locally. If  $\langle sequence \rangle$  is empty the  $\langle token list variable \rangle$  is set to the special marker `\q_no_value`.

<hr/> <code>\seq_get_right:NN</code> <code>\seq_get_right:cN</code> <hr/> Updated: 2012-05-19	<code>\seq_get_right:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Stores the right-most item from a $\langle sequence \rangle$ in the $\langle token list variable \rangle$ without removing it from the $\langle sequence \rangle$ . The $\langle token list variable \rangle$ is assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
<hr/> <code>\seq_pop_left:NN</code> <code>\seq_pop_left:cN</code> <hr/> Updated: 2012-05-14	<code>\seq_pop_left:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the left-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$ , <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$ . Both of the variables are assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
<hr/> <code>\seq_gpop_left:NN</code> <code>\seq_gpop_left:cN</code> <hr/> Updated: 2012-05-14	<code>\seq_gpop_left:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the left-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$ , <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$ . The $\langle sequence \rangle$ is modified globally, while the assignment of the $\langle token list variable \rangle$ is local. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
<hr/> <code>\seq_pop_right:NN</code> <code>\seq_pop_right:cN</code> <hr/> Updated: 2012-05-19	<code>\seq_pop_right:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the right-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$ , <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$ . Both of the variables are assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
<hr/> <code>\seq_gpop_right:NN</code> <code>\seq_gpop_right:cN</code> <hr/> Updated: 2012-05-19	<code>\seq_gpop_right:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the right-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$ , <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$ . The $\langle sequence \rangle$ is modified globally, while the assignment of the $\langle token list variable \rangle$ is local. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
<hr/> <code>\seq_item:Nn</code> ★ <code>\seq_item:cn</code> ★ <hr/> New: 2014-07-17	<code>\seq_item:Nn</code> $\langle sequence \rangle$ $\{ \langle integer expression \rangle \}$ Indexing items in the $\langle sequence \rangle$ from 1 at the top (left), this function evaluates the $\langle integer expression \rangle$ and leaves the appropriate item from the sequence in the input stream. If the $\langle integer expression \rangle$ is negative, indexing occurs from the bottom (right) of the sequence. If the $\langle integer expression \rangle$ is larger than the number of items in the $\langle sequence \rangle$ (as calculated by <code>\seq_count:N</code> ) then the function expands to nothing.

**T<sub>E</sub>Xhackers note:** The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the  $\langle item \rangle$  does not expand further when appearing in an x-type argument expansion.

## 4 Recovering values from sequences with branching

The functions in this section combine tests for non-empty sequences with recovery of an item from the sequence. They offer increased readability and performance over separate testing and recovery phases.

---

`\seq_get_left:NNTF`  
`\seq_get_left:cNTF`

---

New: 2012-05-14  
Updated: 2012-05-19

---

`\seq_get_left:NNTF <sequence> <token list variable> {\true code} {\false code}`

If the `<sequence>` is empty, leaves the `<false code>` in the input stream. The value of the `<token list variable>` is not defined in this case and should not be relied upon. If the `<sequence>` is non-empty, stores the left-most item from a `<sequence>` in the `<token list variable>` without removing it from a `<sequence>`. The `<token list variable>` is assigned locally.

---

`\seq_get_right:NNTF`  
`\seq_get_right:cNTF`

---

New: 2012-05-19

---

`\seq_get_right:NNTF <sequence> <token list variable> {\true code} {\false code}`

If the `<sequence>` is empty, leaves the `<false code>` in the input stream. The value of the `<token list variable>` is not defined in this case and should not be relied upon. If the `<sequence>` is non-empty, stores the right-most item from a `<sequence>` in the `<token list variable>` without removing it from a `<sequence>`. The `<token list variable>` is assigned locally.

---

`\seq_pop_left:NNTF`  
`\seq_pop_left:cNTF`

---

New: 2012-05-14  
Updated: 2012-05-19

---

`\seq_pop_left:NNTF <sequence> <token list variable> {\true code} {\false code}`

If the `<sequence>` is empty, leaves the `<false code>` in the input stream. The value of the `<token list variable>` is not defined in this case and should not be relied upon. If the `<sequence>` is non-empty, pops the left-most item from a `<sequence>` in the `<token list variable>`, *i.e.* removes the item from a `<sequence>`. Both the `<sequence>` and the `<token list variable>` are assigned locally.

---

`\seq_gpop_left:NNTF`  
`\seq_gpop_left:cNTF`

---

New: 2012-05-14  
Updated: 2012-05-19

---

`\seq_gpop_left:NNTF <sequence> <token list variable> {\true code} {\false code}`

If the `<sequence>` is empty, leaves the `<false code>` in the input stream. The value of the `<token list variable>` is not defined in this case and should not be relied upon. If the `<sequence>` is non-empty, pops the left-most item from a `<sequence>` in the `<token list variable>`, *i.e.* removes the item from a `<sequence>`. The `<sequence>` is modified globally, while the `<token list variable>` is assigned locally.

---

`\seq_pop_right:NNTF`  
`\seq_pop_right:cNTF`

---

New: 2012-05-19

---

`\seq_pop_right:NNTF <sequence> <token list variable> {\true code} {\false code}`

If the `<sequence>` is empty, leaves the `<false code>` in the input stream. The value of the `<token list variable>` is not defined in this case and should not be relied upon. If the `<sequence>` is non-empty, pops the right-most item from a `<sequence>` in the `<token list variable>`, *i.e.* removes the item from a `<sequence>`. Both the `<sequence>` and the `<token list variable>` are assigned locally.

---

`\seq_gpop_right:NNTF`  
`\seq_gpop_right:cNTF`

---

New: 2012-05-19

---

`\seq_gpop_right:NNTF <sequence> <token list variable> {\true code} {\false code}`

If the `<sequence>` is empty, leaves the `<false code>` in the input stream. The value of the `<token list variable>` is not defined in this case and should not be relied upon. If the `<sequence>` is non-empty, pops the right-most item from a `<sequence>` in the `<token list variable>`, *i.e.* removes the item from a `<sequence>`. The `<sequence>` is modified globally, while the `<token list variable>` is assigned locally.

## 5 Modifying sequences

While sequences are normally used as ordered lists, it may be necessary to modify the content. The functions here may be used to update sequences, while retaining the order of the unaffected entries.

---

```
\seq_remove_duplicates:N
\seq_remove_duplicates:c
\seq_gremove_duplicates:N
\seq_gremove_duplicates:c
```

---

```
\seq_remove_duplicates:N <sequence>
```

Removes duplicate items from the  $\langle sequence \rangle$ , leaving the left most copy of each item in the  $\langle sequence \rangle$ . The  $\langle item \rangle$  comparison takes place on a token basis, as for `\tl_if_eq:nnTF`.

**TeXhackers note:** This function iterates through every item in the  $\langle sequence \rangle$  and does a comparison with the  $\langle items \rangle$  already checked. It is therefore relatively slow with large sequences.

---

```
\seq_remove_all:Nn
\seq_remove_all:cn
\seq_gremove_all:Nn
\seq_gremove_all:cn
```

---

```
\seq_remove_all:Nn <sequence> {<item>}
```

Removes every occurrence of  $\langle item \rangle$  from the  $\langle sequence \rangle$ . The  $\langle item \rangle$  comparison takes place on a token basis, as for `\tl_if_eq:nnTF`.

---

```
\seq_reverse:N
\seq_reverse:c
\seq_greverse:N
\seq_greverse:c
```

---

```
\seq_reverse:N <sequence>
```

Reverses the order of the items stored in the  $\langle sequence \rangle$ .

New: 2014-07-18

---



---

```
\seq_sort:Nn
\seq_sort:cn
\seq_gsort:Nn
\seq_gsort:cn
```

---

```
\seq_sort:Nn <sequence> {<comparison code>}
```

Sorts the items in the  $\langle sequence \rangle$  according to the  $\langle comparison code \rangle$ , and assigns the result to  $\langle sequence \rangle$ . The details of sorting comparison are described in Section 1.

New: 2017-02-06

---

## 6 Sequence conditionals

---

```
\seq_if_empty_p:N ★
\seq_if_empty_p:c ★
\seq_if_empty:NnTF ★
\seq_if_empty:cnTF ★
```

---

```
\seq_if_empty_p:N <sequence>
```

```
\seq_if_empty:NnTF <sequence> {<true code>} {<false code>}
```

Tests if the  $\langle sequence \rangle$  is empty (containing no items).

---

```
\seq_if_in:NnTF
\seq_if_in:(Nv|Nv|No|Nx|cn|cV|cv|co|cx)TF
```

---

```
\seq_if_in:NnTF <sequence> {<item>} {<true code>} {<false code>}
```

Tests if the  $\langle item \rangle$  is present in the  $\langle sequence \rangle$ .

## 7 Mapping to sequences

---

```
\seq_map_function:NN ★
\seq_map_function:cn ★
```

---

```
\seq_map_function:NN <sequence> <function>
```

Applies  $\langle function \rangle$  to every  $\langle item \rangle$  stored in the  $\langle sequence \rangle$ . The  $\langle function \rangle$  will receive one argument for each iteration. The  $\langle items \rangle$  are returned from left to right. The function `\seq_map_inline:Nn` is faster than `\seq_map_function:NN` for sequences with more than about 10 items. One mapping may be nested inside another.

Updated: 2012-06-29

---

<hr/> <code>\seq_map_inline:Nn</code> <hr/>	<code>\seq_map_inline:Nn &lt;sequence&gt; {&lt;inline function&gt;}</code>
<code>\seq_map_inline:cn</code> <hr/>	Applies <i>&lt;inline function&gt;</i> to every <i>&lt;item&gt;</i> stored within the <i>&lt;sequence&gt;</i> . The <i>&lt;inline function&gt;</i> should consist of code which will receive the <i>&lt;item&gt;</i> as #1. One in line mapping can be nested inside another. The <i>&lt;items&gt;</i> are returned from left to right.
Updated: 2012-06-29	

<hr/> <code>\seq_map_variable:NNn</code> <hr/>	<code>\seq_map_variable:NNn &lt;sequence&gt; &lt;tl var.&gt; {&lt;function using tl var.&gt;}</code>
<code>\seq_map_variable:(Ncn cNn ccn)</code> <hr/>	
Updated: 2012-06-29	
	Stores each entry in the <i>&lt;sequence&gt;</i> in turn in the <i>&lt;tl var.&gt;</i> and applies the <i>&lt;function using tl var.&gt;</i> The <i>&lt;function&gt;</i> will usually consist of code making use of the <i>&lt;tl var.&gt;</i> , but this is not enforced. One variable mapping can be nested inside another. The <i>&lt;items&gt;</i> are returned from left to right.

<hr/> <code>\seq_map_break: ☆</code> <hr/>	<code>\seq_map_break:</code>
Updated: 2012-06-29	Used to terminate a <code>\seq_map...</code> function before all entries in the <i>&lt;sequence&gt;</i> have been processed. This normally takes place within a conditional statement, for example

```

\seq_map_inline:Nn \l_my_seq
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \seq_map_break: }
  {
    % Do something useful
  }
}

```

Use outside of a `\seq_map...` scenario leads to low level  $\mathrm{T}_{\mathrm{E}}\mathrm{X}$  errors.

**$\mathrm{T}_{\mathrm{E}}\mathrm{X}$ hackers note:** When the mapping is broken, additional tokens may be inserted by the internal macro `\__prg_break_point:Nn` before further items are taken from the input stream. This depends on the design of the mapping function.

---

`\seq_map_break:n` ☆

---

Updated: 2012-06-29

---

`\seq_map_break:n` {*tokens*}

Used to terminate a `\seq_map...` function before all entries in the *sequence* have been processed, inserting the *tokens* after the mapping has ended. This normally takes place within a conditional statement, for example

```
\seq_map_inline:Nn \l_my_seq
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \seq_map_break:n { <tokens> } }
  {
    % Do something useful
  }
}
```

Use outside of a `\seq_map...` scenario leads to low level TeX errors.

**TeXhackers note:** When the mapping is broken, additional tokens may be inserted by the internal macro `\__prg_break_point:Nn` before the *tokens* are inserted into the input stream. This depends on the design of the mapping function.

---

`\seq_count:N` ☆

---

`\seq_count:c` ☆

---

New: 2012-07-13

---

`\seq_count:N` *sequence*

Leaves the number of items in the *sequence* in the input stream as an *integer denotation*. The total number of items in a *sequence* includes those which are empty and duplicates, *i.e.* every item in a *sequence* is unique.

## 8 Using the content of sequences directly

---

`\seq_use:Nnnn` ☆

---

`\seq_use:cnnn` ☆

---

New: 2013-05-26

---

`\seq_use:Nnnn` *seq var* {*separator between two*}

{*separator between more than two*} {*separator between final two*}

Places the contents of the *seq var* in the input stream, with the appropriate *separator* between the items. Namely, if the sequence has more than two items, the *separator between more than two* is placed between each pair of items except the last, for which the *separator between final two* is used. If the sequence has exactly two items, then they are placed in the input stream separated by the *separator between two*. If the sequence has a single item, it is placed in the input stream, and an empty sequence produces no output. An error is raised if the variable does not exist or if it is invalid.

For example,

```
\seq_set_split:Nnn \l_tmpa_seq { | } { a | b | c | {de} | f }
\seq_use:Nnnn \l_tmpa_seq { ~and~ } { ,~ } { ,~and~ }
```

inserts “a, b, c, de, and f” in the input stream. The first separator argument is not used in this case because the sequence has more than 2 items.

**TeXhackers note:** The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *items* do not expand further when appearing in an x-type argument expansion.

---

`\seq_use:Nn` ★

`\seq_use:cn` ★

---

New: 2013-05-26

---

`\seq_use:Nn`  $\langle seq\ var \rangle$   $\{\langle separator \rangle\}$

Places the contents of the  $\langle seq\ var \rangle$  in the input stream, with the  $\langle separator \rangle$  between the items. If the sequence has a single item, it is placed in the input stream with no  $\langle separator \rangle$ , and an empty sequence produces no output. An error is raised if the variable does not exist or if it is invalid.

For example,

```
\seq_set_split:Nnn \l_tmpa_seq { | } { a | b | c | {de} | f }
\seq_use:Nn \l_tmpa_seq { ~and~ }
```

inserts “a and b and c and de and f” in the input stream.

**TeXhackers note:** The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the  $\langle items \rangle$  do not expand further when appearing in an `x`-type argument expansion.

## 9 Sequences as stacks

Sequences can be used as stacks, where data is pushed to and popped from the top of the sequence. (The left of a sequence is the top, for performance reasons.) The stack functions for sequences are not intended to be mixed with the general ordered data functions detailed in the previous section: a sequence should either be used as an ordered data type or as a stack, but not in both ways.

---

`\seq_get:NN`

`\seq_get:cn`

---

Updated: 2012-05-14

---

`\seq_get:NN`  $\langle sequence \rangle$   $\langle token\ list\ variable \rangle$

Reads the top item from a  $\langle sequence \rangle$  into the  $\langle token\ list\ variable \rangle$  without removing it from the  $\langle sequence \rangle$ . The  $\langle token\ list\ variable \rangle$  is assigned locally. If  $\langle sequence \rangle$  is empty the  $\langle token\ list\ variable \rangle$  is set to the special marker `\q_no_value`.

---

`\seq_pop:NN`

`\seq_pop:cn`

---

Updated: 2012-05-14

---

`\seq_pop:NN`  $\langle sequence \rangle$   $\langle token\ list\ variable \rangle$

Pops the top item from a  $\langle sequence \rangle$  into the  $\langle token\ list\ variable \rangle$ . Both of the variables are assigned locally. If  $\langle sequence \rangle$  is empty the  $\langle token\ list\ variable \rangle$  is set to the special marker `\q_no_value`.

---

`\seq_gpop:NN`

`\seq_gpop:cn`

---

Updated: 2012-05-14

---

`\seq_gpop:NN`  $\langle sequence \rangle$   $\langle token\ list\ variable \rangle$

Pops the top item from a  $\langle sequence \rangle$  into the  $\langle token\ list\ variable \rangle$ . The  $\langle sequence \rangle$  is modified globally, while the  $\langle token\ list\ variable \rangle$  is assigned locally. If  $\langle sequence \rangle$  is empty the  $\langle token\ list\ variable \rangle$  is set to the special marker `\q_no_value`.

---

`\seq_get:NNTF`

`\seq_get:cNTF`

---

New: 2012-05-14

Updated: 2012-05-19

---

`\seq_get:NNTF`  $\langle sequence \rangle$   $\langle token\ list\ variable \rangle$   $\{\langle true\ code \rangle\}$   $\{\langle false\ code \rangle\}$

If the  $\langle sequence \rangle$  is empty, leaves the  $\langle false\ code \rangle$  in the input stream. The value of the  $\langle token\ list\ variable \rangle$  is not defined in this case and should not be relied upon. If the  $\langle sequence \rangle$  is non-empty, stores the top item from a  $\langle sequence \rangle$  in the  $\langle token\ list\ variable \rangle$  without removing it from the  $\langle sequence \rangle$ . The  $\langle token\ list\ variable \rangle$  is assigned locally.

---

`\seq_pop:NNTF`  
`\seq_pop:cNTF`

---

New: 2012-05-14  
Updated: 2012-05-19

---

`\seq_pop:NNTF <sequence> <token list variable> {\true code} {\false code}`

If the `<sequence>` is empty, leaves the `<false code>` in the input stream. The value of the `<token list variable>` is not defined in this case and should not be relied upon. If the `<sequence>` is non-empty, pops the top item from the `<sequence>` in the `<token list variable>`, *i.e.* removes the item from the `<sequence>`. Both the `<sequence>` and the `<token list variable>` are assigned locally.

---

`\seq_gpop:NNTF`  
`\seq_gpop:cNTF`

---

New: 2012-05-14  
Updated: 2012-05-19

---

`\seq_gpop:NNTF <sequence> <token list variable> {\true code} {\false code}`

If the `<sequence>` is empty, leaves the `<false code>` in the input stream. The value of the `<token list variable>` is not defined in this case and should not be relied upon. If the `<sequence>` is non-empty, pops the top item from the `<sequence>` in the `<token list variable>`, *i.e.* removes the item from the `<sequence>`. The `<sequence>` is modified globally, while the `<token list variable>` is assigned locally.

---

`\seq_push:Nn`  
`\seq_push:(NV|Nv|No|Nx|cn|cV|cv|co|cx)`  
`\seq_gpush:Nn`  
`\seq_gpush:(NV|Nv|No|Nx|cn|cV|cv|co|cx)`

---

`\seq_push:Nn <sequence> {\item}`

Adds the `{\item}` to the top of the `<sequence>`.

## 10 Sequences as sets

Sequences can also be used as sets, such that all of their items are distinct. Usage of sequences as sets is not currently widespread, hence no specific set function is provided. Instead, it is explained here how common set operations can be performed by combining several functions described in earlier sections. When using sequences to implement sets, one should be careful not to rely on the order of items in the sequence representing the set.

Sets should not contain several occurrences of a given item. To make sure that a `<sequence variable>` only has distinct items, use `\seq_remove_duplicates:N <sequence variable>`. This function is relatively slow, and to avoid performance issues one should only use it when necessary.

Some operations on a set `<seq var>` are straightforward. For instance, `\seq_count:N <seq var>` expands to the number of items, while `\seq_if_in:NnTF <seq var> {\item}` tests if the `<item>` is in the set.

Adding an `<item>` to a set `<seq var>` can be done by appending it to the `<seq var>` if it is not already in the `<seq var>`:

```
\seq_if_in:NnF <seq var> {\item}
{ \seq_put_right:Nn <seq var> {\item} }
```

Removing an `<item>` from a set `<seq var>` can be done using `\seq_remove_all:Nn`,

```
\seq_remove_all:Nn <seq var> {\item}
```

The intersection of two sets `<seq var1 and <seq var2 can be stored into <seq var3 by collecting items of <seq var1 which are in <seq var2.`



```

\seq_clear:N <seq var3>
\seq_map_inline:Nn <seq var1>
{
\seq_if_in:NnT <seq var2> {#1}
{ \seq_put_right:Nn <seq var3> {#1} }
}

```

The code as written here only works if  $\langle seq\ var_3 \rangle$  is different from the other two sequence variables. To cover all cases, items should first be collected in a sequence  $\backslash l\_ \langle pkg \rangle\_internal\_seq$ , then  $\langle seq\ var_3 \rangle$  should be set equal to this internal sequence. The same remark applies to other set functions.

The union of two sets  $\langle seq\ var_1 \rangle$  and  $\langle seq\ var_2 \rangle$  can be stored into  $\langle seq\ var_3 \rangle$  through

```

\seq_concat:NNN <seq var3> <seq var1> <seq var2>
\seq_remove_duplicates:N <seq var3>

```

or by adding items to (a copy of)  $\langle seq\ var_1 \rangle$  one by one

```

\seq_set_eq:NN <seq var3> <seq var1>
\seq_map_inline:Nn <seq var2>
{
\seq_if_in:NnF <seq var3> {#1}
{ \seq_put_right:Nn <seq var3> {#1} }
}

```

The second approach is faster than the first when the  $\langle seq\ var_2 \rangle$  is short compared to  $\langle seq\ var_1 \rangle$ .

The difference of two sets  $\langle seq\ var_1 \rangle$  and  $\langle seq\ var_2 \rangle$  can be stored into  $\langle seq\ var_3 \rangle$  by removing items of the  $\langle seq\ var_2 \rangle$  from (a copy of) the  $\langle seq\ var_1 \rangle$  one by one.

```

\seq_set_eq:NN <seq var3> <seq var1>
\seq_map_inline:Nn <seq var2>
{ \seq_remove_all:Nn <seq var3> {#1} }

```

The symmetric difference of two sets  $\langle seq\ var_1 \rangle$  and  $\langle seq\ var_2 \rangle$  can be stored into  $\langle seq\ var_3 \rangle$  by computing the difference between  $\langle seq\ var_1 \rangle$  and  $\langle seq\ var_2 \rangle$  and storing the result as  $\backslash l\_ \langle pkg \rangle\_internal\_seq$ , then the difference between  $\langle seq\ var_2 \rangle$  and  $\langle seq\ var_1 \rangle$ , and finally concatenating the two differences to get the symmetric differences.

```

\seq_set_eq:NN \l\_ \langle pkg \rangle\_internal\_seq <seq var1>
\seq_map_inline:Nn <seq var2>
{ \seq_remove_all:Nn \l\_ \langle pkg \rangle\_internal\_seq {#1} }
\seq_set_eq:NN <seq var3> <seq var2>
\seq_map_inline:Nn <seq var1>
{ \seq_remove_all:Nn <seq var3> {#1} }
\seq_concat:NNN <seq var3> <seq var3> \l\_ \langle pkg \rangle\_internal\_seq

```

## 11 Constant and scratch sequences

---

$\backslash c\_empty\_seq$  Constant that is always empty.

---

New: 2012-07-02

---

---

`\l_tmpa_seq`  
`\l_tmpb_seq`  


---

New: 2012-04-26

Scratch sequences for local assignment. These are never used by the kernel code, and so are safe for use with any L<sup>A</sup>T<sub>E</sub>X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

---

`\g_tmpa_seq`  
`\g_tmpb_seq`  


---

New: 2012-04-26

Scratch sequences for global assignment. These are never used by the kernel code, and so are safe for use with any L<sup>A</sup>T<sub>E</sub>X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

## 12 Viewing sequences

---

`\seq_show:N`  
`\seq_show:c`  


---

Updated: 2015-08-01

`\seq_show:N`  $\langle sequence \rangle$   
Displays the entries in the  $\langle sequence \rangle$  in the terminal.

---

`\seq_log:N`  
`\seq_log:c`  


---

New: 2014-08-12  
Updated: 2015-08-01

`\seq_log:N`  $\langle sequence \rangle$   
Writes the entries in the  $\langle sequence \rangle$  in the log file.

## 13 Internal sequence functions

---

`\s__seq`

This scan mark (equal to `\scan_stop:`) marks the beginning of a sequence variable.

---

`\__seq_item:n` ★

`\__seq_item:n`  $\{\langle item \rangle\}$

The internal token used to begin each sequence entry. If expanded outside of a mapping or manipulation function, an error is raised. The definition should always be set globally.

---

`\__seq_push_item_def:n`  
`\__seq_push_item_def:x`

`\__seq_push_item_def:n`  $\{\langle code \rangle\}$

Saves the definition of `\__seq_item:n` and redefines it to accept one parameter and expand to  $\langle code \rangle$ . This function should always be balanced by use of `\__seq_pop_item_def:`.

---

`\__seq_pop_item_def:`

`\__seq_pop_item_def:`

Restores the definition of `\__seq_item:n` most recently saved by `\__seq_push_item_def:n`. This function should always be used in a balanced pair with `\__seq_push_item_def:n`.

## Part IX

# The l3int package

## Integers

Calculation and comparison of integer values can be carried out using literal numbers, `int` registers, constants and integers stored in token list variables. The standard operators `+`, `-`, `/` and `*` and parentheses can be used within such expressions to carry arithmetic operations. This module carries out these functions on *integer expressions* (“`intexpr`”).

### 1 Integer expressions

---

`\int_eval:n` ★ `\int_eval:n {⟨integer expression⟩}`

---

Evaluates the *⟨integer expression⟩*, expanding any integer and token list variables within the *⟨expression⟩* to their content (without requiring `\int_use:N/\tl_use:N`) and applying the standard mathematical rules. For example both

```
\int_eval:n { 5 + 4 * 3 - ( 3 + 4 * 5 ) }
```

and

```
\tl_new:N \l_my_tl
\tl_set:Nn \l_my_tl { 5 }
\int_new:N \l_my_int
\int_set:Nn \l_my_int { 4 }
\int_eval:n { \l_my_tl + \l_my_int * 3 - ( 3 + 4 * 5 ) }
```

both evaluate to  $-6$ . The *⟨integer expression⟩* may contain the operators `+`, `-`, `*` and `/`, along with parenthesis `(` and `)`. Any functions within the expressions should expand to an *⟨integer denotation⟩*: a sequence of a sign and digits matching the regex `\-?[0-9]+`. After expansion `\int_eval:n` yields an *⟨integer denotation⟩* which is left in the input stream.

**T<sub>E</sub>Xhackers note:** Exactly two expansions are needed to evaluate `\int_eval:n`. The result is *not* an *⟨internal integer⟩*, and therefore requires suitable termination if used in a T<sub>E</sub>X-style integer assignment.

---

`\int_abs:n` ★ `\int_abs:n {⟨integer expression⟩}`

---

Updated: 2012-09-26

Evaluates the *⟨integer expression⟩* as described for `\int_eval:n` and leaves the absolute value of the result in the input stream as an *⟨integer denotation⟩* after two expansions.

---

`\int_div_round:nn` ★ `\int_div_round:nn {⟨intexpr1⟩} {⟨intexpr2⟩}`

---

Updated: 2012-09-26

Evaluates the two *⟨integer expressions⟩* as described earlier, then divides the first value by the second, and rounds the result to the closest integer. Ties are rounded away from zero. Note that this is identical to using `/` directly in an *⟨integer expression⟩*. The result is left in the input stream as an *⟨integer denotation⟩* after two expansions.

<hr/> <code>\int_div_truncate:nn</code> ★ <hr/>	<code>\int_div_truncate:nn {\langle integer_1 \rangle} {\langle integer_2 \rangle}</code>
Updated: 2012-02-09	Evaluates the two $\langle integer expressions \rangle$ as described earlier, then divides the first value by the second, and rounds the result towards zero. Note that division using <code>/</code> rounds to the closest integer instead. The result is left in the input stream as an $\langle integer denotation \rangle$ after two expansions.

<hr/> <code>\int_max:nn</code> ★	<code>\int_max:nn {\langle integer_1 \rangle} {\langle integer_2 \rangle}</code>
<hr/> <code>\int_min:nn</code> ★	<code>\int_min:nn {\langle integer_1 \rangle} {\langle integer_2 \rangle}</code>
Updated: 2012-09-26	Evaluates the $\langle integer expressions \rangle$ as described for <code>\int_eval:n</code> and leaves either the larger or smaller value in the input stream as an $\langle integer denotation \rangle$ after two expansions.

<hr/> <code>\int_mod:nn</code> ★	<code>\int_mod:nn {\langle integer_1 \rangle} {\langle integer_2 \rangle}</code>
Updated: 2012-09-26	Evaluates the two $\langle integer expressions \rangle$ as described earlier, then calculates the integer remainder of dividing the first expression by the second. This is obtained by subtracting <code>\int_div_truncate:nn {\langle integer_1 \rangle} {\langle integer_2 \rangle}</code> times $\langle integer_2 \rangle$ from $\langle integer_1 \rangle$ . Thus, the result has the same sign as $\langle integer_1 \rangle$ and its absolute value is strictly less than that of $\langle integer_2 \rangle$ . The result is left in the input stream as an $\langle integer denotation \rangle$ after two expansions.

## 2 Creating and initialising integers

<hr/> <code>\int_new:N</code>	<code>\int_new:N \langle integer \rangle</code>
<hr/> <code>\int_new:c</code>	Creates a new $\langle integer \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle integer \rangle$ is initially equal to 0.

<hr/> <code>\int_const:Nn</code>	<code>\int_const:Nn \langle integer \rangle {\langle integer expression \rangle}</code>
<hr/> <code>\int_const:cn</code>	Creates a new constant $\langle integer \rangle$ or raises an error if the name is already taken. The value of the $\langle integer \rangle$ is set globally to the $\langle integer expression \rangle$ .
Updated: 2011-10-22	

<hr/> <code>\int_zero:N</code>	<code>\int_zero:N \langle integer \rangle</code>
<hr/> <code>\int_zero:c</code>	Sets $\langle integer \rangle$ to 0.
<hr/> <code>\int_gzero:N</code>	
<hr/> <code>\int_gzero:c</code>	

<hr/> <code>\int_zero_new:N</code>	<code>\int_zero_new:N \langle integer \rangle</code>
<hr/> <code>\int_zero_new:c</code>	Ensures that the $\langle integer \rangle$ exists globally by applying <code>\int_new:N</code> if necessary, then applies <code>\int_(g)zero:N</code> to leave the $\langle integer \rangle$ set to zero.
<hr/> <code>\int_gzero_new:N</code>	
<hr/> <code>\int_gzero_new:c</code>	
New: 2011-12-13	

<hr/> <code>\int_set_eq:NN</code>	<code>\int_set_eq:NN \langle integer_1 \rangle \langle integer_2 \rangle</code>
<hr/> <code>\int_set_eq:(cN Nc cc)</code>	Sets the content of $\langle integer_1 \rangle$ equal to that of $\langle integer_2 \rangle$ .
<hr/> <code>\int_gset_eq:NN</code>	
<hr/> <code>\int_gset_eq:(cN Nc cc)</code>	

---

<code>\int_if_exist_p:N</code>	★	<code>\int_if_exist_p:N</code>	$\langle integer \rangle$
<code>\int_if_exist_p:c</code>	★	<code>\int_if_exist:NTF</code>	$\langle integer \rangle$ <code>{\true code}</code> <code>{\false code}</code>
<code>\int_if_exist:NTF</code>	★	Tests whether the $\langle integer \rangle$ is currently defined. This does not check that the $\langle integer \rangle$ really is an integer variable.	
<code>\int_if_exist:cTF</code>	★		

---

New: 2012-03-03

---

### 3 Setting and incrementing integers

---

<code>\int_add:Nn</code>	<code>\int_add:Nn</code>	$\langle integer \rangle$	<code>{\integer expression}</code>
<code>\int_add:cn</code>	Adds the result of the $\langle integer expression \rangle$ to the current content of the $\langle integer \rangle$ .		
<code>\int_gadd:Nn</code>			
<code>\int_gadd:cn</code>			

---

Updated: 2011-10-22

---



---

<code>\int_decr:N</code>	<code>\int_decr:N</code>	$\langle integer \rangle$
<code>\int_decr:c</code>	Decreases the value stored in $\langle integer \rangle$ by 1.	
<code>\int_gdecr:N</code>		
<code>\int_gdecr:c</code>		

---



---

<code>\int_incr:N</code>	<code>\int_incr:N</code>	$\langle integer \rangle$
<code>\int_incr:c</code>	Increases the value stored in $\langle integer \rangle$ by 1.	
<code>\int_gincr:N</code>		
<code>\int_gincr:c</code>		

---



---

<code>\int_set:Nn</code>	<code>\int_set:Nn</code>	$\langle integer \rangle$	<code>{\integer expression}</code>
<code>\int_set:cn</code>	Sets $\langle integer \rangle$ to the value of $\langle integer expression \rangle$ , which must evaluate to an integer (as described for <code>\int_eval:n</code> ).		
<code>\int_gset:Nn</code>			
<code>\int_gset:cn</code>			

---

Updated: 2011-10-22

---



---

<code>\int_sub:Nn</code>	<code>\int_sub:Nn</code>	$\langle integer \rangle$	<code>{\integer expression}</code>
<code>\int_sub:cn</code>	Subtracts the result of the $\langle integer expression \rangle$ from the current content of the $\langle integer \rangle$ .		
<code>\int_gsub:Nn</code>			
<code>\int_gsub:cn</code>			

---

Updated: 2011-10-22

---

### 4 Using integers

<code>\int_use:N</code>	★	<code>\int_use:N</code> $\langle integer \rangle$
<code>\int_use:c</code>	★	Recovers the content of an $\langle integer \rangle$ and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Can be omitted in places where an $\langle integer \rangle$ is required (such as in the first and third arguments of <code>\int_compare:nNTF</code> ).
Updated: 2011-10-22		

**TeXhackers note:** `\int_use:N` is the TeX primitive `\the`: this is one of several L<sup>A</sup>T<sub>E</sub>X3 names for this primitive.

## 5 Integer expression conditionals

---

```
\int_compare_p:nNn ★ \int_compare_p:nNn {\langle intexpr_1 \rangle} \langle relation \rangle {\langle intexpr_2 \rangle}
\int_compare:nNnTF ★ \int_compare:nNnTF
                        {\langle intexpr_1 \rangle} \langle relation \rangle {\langle intexpr_2 \rangle}
                        {\langle true code \rangle} {\langle false code \rangle}
```

---

This function first evaluates each of the  $\langle integer expressions \rangle$  as described for `\int_eval:n`. The two results are then compared using the  $\langle relation \rangle$ :

Equal	=
Greater than	>
Less than	<

---

```
\int_compare_p:n ★ \int_compare_p:n
\int_compare:nTF ★ {
                    \langle intexpr_1 \rangle \langle relation_1 \rangle
                    ...
                    \langle intexpr_N \rangle \langle relation_N \rangle
                    \langle intexpr_{N+1} \rangle
                }
\int_compare:nTF
{
    \langle intexpr_1 \rangle \langle relation_1 \rangle
    ...
    \langle intexpr_N \rangle \langle relation_N \rangle
    \langle intexpr_{N+1} \rangle
}
{\langle true code \rangle} {\langle false code \rangle}
```

---

Updated: 2013-01-13

---

This function evaluates the  $\langle integer expressions \rangle$  as described for `\int_eval:n` and compares consecutive result using the corresponding  $\langle relation \rangle$ , namely it compares  $\langle intexpr_1 \rangle$  and  $\langle intexpr_2 \rangle$  using the  $\langle relation_1 \rangle$ , then  $\langle intexpr_2 \rangle$  and  $\langle intexpr_3 \rangle$  using the  $\langle relation_2 \rangle$ , until finally comparing  $\langle intexpr_N \rangle$  and  $\langle intexpr_{N+1} \rangle$  using the  $\langle relation_N \rangle$ . The test yields **true** if all comparisons are **true**. Each  $\langle integer expression \rangle$  is evaluated only once, and the evaluation is lazy, in the sense that if one comparison is **false**, then no other  $\langle integer expression \rangle$  is evaluated and no other comparison is performed. The  $\langle relations \rangle$  can be any of the following:

Equal	= or ==
Greater than or equal to	>=
Greater than	>
Less than or equal to	<=
Less than	<
Not equal	!=

---

<code>\int_case:nn</code> ★	<code>\int_case:nnTF {⟨test integer expression⟩}</code>
<code>\int_case:nnTF</code> ★	<code>{</code>
	<code>{⟨intexpr case<sub>1</sub>⟩} {⟨code case<sub>1</sub>⟩}</code>
	<code>{⟨intexpr case<sub>2</sub>⟩} {⟨code case<sub>2</sub>⟩}</code>
	<code>...</code>
	<code>{⟨intexpr case<sub>n</sub>⟩} {⟨code case<sub>n</sub>⟩}</code>
	<code>}</code>
	<code>{⟨true code⟩}</code>
	<code>{⟨false code⟩}</code>

---

New: 2013-07-24

---

This function evaluates the *⟨test integer expression⟩* and compares this in turn to each of the *⟨integer expression cases⟩*. If the two are equal then the associated *⟨code⟩* is left in the input stream and other cases are discarded. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\int_case:nn`, which does nothing if there is no match, is also available. For example

```
\int_case:nnF
{ 2 * 5 }
{
  { 5 }      { Small }
  { 4 + 6 }   { Medium }
  { -2 * 10 } { Negative }
}
{ No idea! }
```

leaves “Medium” in the input stream.

---

<code>\int_if_even_p:n</code> ★	<code>\int_if_odd_p:n {⟨integer expression⟩}</code>
<code>\int_if_even:nTF</code> ★	<code>\int_if_odd:nTF {⟨integer expression⟩}</code>
<code>\int_if_odd_p:n</code> ★	<code>{⟨true code⟩} {⟨false code⟩}</code>
<code>\int_if_odd:nTF</code> ★	

---

This function first evaluates the *⟨integer expression⟩* as described for `\int_eval:n`. It then evaluates if this is odd or even, as appropriate.

## 6 Integer expression loops

---

<code>\int_do_until:nNnn</code> ☆	<code>\int_do_until:nNnn {⟨intexpr<sub>1</sub>⟩} ⟨relation⟩ {⟨intexpr<sub>2</sub>⟩} {⟨code⟩}</code>
-----------------------------------	---

---

Places the *⟨code⟩* in the input stream for T<sub>E</sub>X to process, and then evaluates the relationship between the two *⟨integer expressions⟩* as described for `\int_compare:nNnTF`. If the test is **false** then the *⟨code⟩* is inserted into the input stream again and a loop occurs until the *⟨relation⟩* is **true**.

---

<code>\int_do_while:nNnn</code> ☆	<code>\int_do_while:nNnn {⟨intexpr<sub>1</sub>⟩} ⟨relation⟩ {⟨intexpr<sub>2</sub>⟩} {⟨code⟩}</code>
-----------------------------------	---

---

Places the *⟨code⟩* in the input stream for T<sub>E</sub>X to process, and then evaluates the relationship between the two *⟨integer expressions⟩* as described for `\int_compare:nNnTF`. If the test is **true** then the *⟨code⟩* is inserted into the input stream again and a loop occurs until the *⟨relation⟩* is **false**.

<hr/> <code>\int_until_do:nNnn</code> ☆ <hr/>	<code>\int_until_do:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code>
	Evaluates the relationship between the two <i>⟨integer expressions⟩</i> as described for <code>\int_compare:nNnTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is <b>false</b> . After the <i>⟨code⟩</i> has been processed by T <sub>E</sub> X the test is repeated, and a loop occurs until the test is <b>true</b> .
<hr/> <code>\int_while_do:nNnn</code> ☆ <hr/>	<code>\int_while_do:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code>
	Evaluates the relationship between the two <i>⟨integer expressions⟩</i> as described for <code>\int_compare:nNnTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is <b>true</b> . After the <i>⟨code⟩</i> has been processed by T <sub>E</sub> X the test is repeated, and a loop occurs until the test is <b>false</b> .
<hr/> <code>\int_do_until:nn</code> ☆ <hr/>	<code>\int_do_until:nn {⟨integer relation⟩} {⟨code⟩}</code>
Updated: 2013-01-13	Places the <i>⟨code⟩</i> in the input stream for T <sub>E</sub> X to process, and then evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> . If the test is <b>false</b> then the <i>⟨code⟩</i> is inserted into the input stream again and a loop occurs until the <i>⟨relation⟩</i> is <b>true</b> .
<hr/> <code>\int_do_while:nn</code> ☆ <hr/>	<code>\int_do_while:nn {⟨integer relation⟩} {⟨code⟩}</code>
Updated: 2013-01-13	Places the <i>⟨code⟩</i> in the input stream for T <sub>E</sub> X to process, and then evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> . If the test is <b>true</b> then the <i>⟨code⟩</i> is inserted into the input stream again and a loop occurs until the <i>⟨relation⟩</i> is <b>false</b> .
<hr/> <code>\int_until_do:nn</code> ☆ <hr/>	<code>\int_until_do:nn {⟨integer relation⟩} {⟨code⟩}</code>
Updated: 2013-01-13	Evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is <b>false</b> . After the <i>⟨code⟩</i> has been processed by T <sub>E</sub> X the test is repeated, and a loop occurs until the test is <b>true</b> .
<hr/> <code>\int_while_do:nn</code> ☆ <hr/>	<code>\int_while_do:nn {⟨integer relation⟩} {⟨code⟩}</code>
Updated: 2013-01-13	Evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is <b>true</b> . After the <i>⟨code⟩</i> has been processed by T <sub>E</sub> X the test is repeated, and a loop occurs until the test is <b>false</b> .



## 7 Integer step functions

---

`\int_step_function:nnnN` ★

---

New: 2012-06-04

Updated: 2014-05-30

---

`\int_step_function:nnnN`  $\langle initial\ value \rangle$   $\langle step \rangle$   $\langle final\ value \rangle$   $\langle function \rangle$

This function first evaluates the  $\langle initial\ value \rangle$ ,  $\langle step \rangle$  and  $\langle final\ value \rangle$ , all of which should be integer expressions. The  $\langle function \rangle$  is then placed in front of each  $\langle value \rangle$  from the  $\langle initial\ value \rangle$  to the  $\langle final\ value \rangle$  in turn (using  $\langle step \rangle$  between each  $\langle value \rangle$ ). The  $\langle step \rangle$  must be non-zero. If the  $\langle step \rangle$  is positive, the loop stops when the  $\langle value \rangle$  becomes larger than the  $\langle final\ value \rangle$ . If the  $\langle step \rangle$  is negative, the loop stops when the  $\langle value \rangle$  becomes smaller than the  $\langle final\ value \rangle$ . The  $\langle function \rangle$  should absorb one numerical argument. For example

```
\cs_set:Npn \my_func:n #1 { [I~saw~#1] \quad }
\int_step_function:nnnN { 1 } { 1 } { 5 } \my_func:n
```

would print

```
[I saw 1] [I saw 2] [I saw 3] [I saw 4] [I saw 5]
```

---

`\int_step_inline:nnnn`

---

New: 2012-06-04

Updated: 2014-05-30

---

`\int_step_inline:nnnn`  $\langle initial\ value \rangle$   $\langle step \rangle$   $\langle final\ value \rangle$   $\langle code \rangle$

This function first evaluates the  $\langle initial\ value \rangle$ ,  $\langle step \rangle$  and  $\langle final\ value \rangle$ , all of which should be integer expressions. Then for each  $\langle value \rangle$  from the  $\langle initial\ value \rangle$  to the  $\langle final\ value \rangle$  in turn (using  $\langle step \rangle$  between each  $\langle value \rangle$ ), the  $\langle code \rangle$  is inserted into the input stream with `#1` replaced by the current  $\langle value \rangle$ . Thus the  $\langle code \rangle$  should define a function of one argument (`#1`).

---

`\int_step_variable:nnnNn`

---

New: 2012-06-04

Updated: 2014-05-30

---

`\int_step_variable:nnnNn`  
 $\langle initial\ value \rangle$   $\langle step \rangle$   $\langle final\ value \rangle$   $\langle tl\ var \rangle$   $\langle code \rangle$

This function first evaluates the  $\langle initial\ value \rangle$ ,  $\langle step \rangle$  and  $\langle final\ value \rangle$ , all of which should be integer expressions. Then for each  $\langle value \rangle$  from the  $\langle initial\ value \rangle$  to the  $\langle final\ value \rangle$  in turn (using  $\langle step \rangle$  between each  $\langle value \rangle$ ), the  $\langle code \rangle$  is inserted into the input stream, with the  $\langle tl\ var \rangle$  defined as the current  $\langle value \rangle$ . Thus the  $\langle code \rangle$  should make use of the  $\langle tl\ var \rangle$ .

## 8 Formatting integers

Integers can be placed into the output stream with formatting. These conversions apply to any integer expressions.

---

`\int_to_arabic:n` ★

---

Updated: 2011-10-22

---

`\int_to_arabic:n`  $\langle integer\ expression \rangle$

Places the value of the  $\langle integer\ expression \rangle$  in the input stream as digits, with category code 12 (other).

---

<code>\int_to_alph:n</code> ★	<code>\int_to_alph:n {⟨integer expression⟩}</code>
-------------------------------	--

---

<code>\int_to_Alph:n</code> ★
-------------------------------

---



---

Updated: 2011-09-17
---------------------

---

Evaluates the *⟨integer expression⟩* and converts the result into a series of letters, which are then left in the input stream. The conversion rule uses the 26 letters of the English alphabet, in order, adding letters when necessary to increase the total possible range of representable numbers. Thus

```
\int_to_alph:n { 1 }
```

places **a** in the input stream,

```
\int_to_alph:n { 26 }
```

is represented as **z** and

```
\int_to_alph:n { 27 }
```

is converted to **aa**. For conversions using other alphabets, use `\int_to_symbols:nnn` to define an alphabet-specific function. The basic `\int_to_alph:n` and `\int_to_Alph:n` functions should not be modified. The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter).

---

<code>\int_to_symbols:nnn</code> ★
------------------------------------

---



---

Updated: 2011-09-17
---------------------

---

```
\int_to_symbols:nnn
  {⟨integer expression⟩} {⟨total symbols⟩}
  ⟨value to symbol mapping⟩
```

This is the low-level function for conversion of an *⟨integer expression⟩* into a symbolic form (often letters). The *⟨total symbols⟩* available should be given as an integer expression. Values are actually converted to symbols according to the *⟨value to symbol mapping⟩*. This should be given as *⟨total symbols⟩* pairs of entries, a number and the appropriate symbol. Thus the `\int_to_alph:n` function is defined as

```
\cs_new:Npn \int_to_alph:n #1
{
  \int_to_symbols:nnn {#1} { 26 }
  {
    { 1 } { a }
    { 2 } { b }
    ...
    { 26 } { z }
  }
}
```

---

<code>\int_to_bin:n</code> ★
------------------------------

---



---

New: 2014-02-11
-----------------

---

```
\int_to_bin:n {⟨integer expression⟩}
```

Calculates the value of the *⟨integer expression⟩* and places the binary representation of the result in the input stream.

<code>\int_to_hex:n</code> ★	<code>\int_to_hex:n {⟨integer expression⟩}</code>
<code>\int_to_Hex:n</code> ★	Calculates the value of the <i>⟨integer expression⟩</i> and places the hexadecimal (base 16) representation of the result in the input stream. Letters are used for digits beyond 9: lower case letters for <code>\int_to_hex:n</code> and upper case ones for <code>\int_to_Hex:n</code> . The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter).
New: 2014-02-11	

<code>\int_to_oct:n</code> ★	<code>\int_to_oct:n {⟨integer expression⟩}</code>
New: 2014-02-11	Calculates the value of the <i>⟨integer expression⟩</i> and places the octal (base 8) representation of the result in the input stream. The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter).

<code>\int_to_base:nn</code> ★	<code>\int_to_base:nn {⟨integer expression⟩} {⟨base⟩}</code>
<code>\int_to_Base:nn</code> ★	Calculates the value of the <i>⟨integer expression⟩</i> and converts it into the appropriate representation in the <i>⟨base⟩</i> ; the later may be given as an integer expression. For bases greater than 10 the higher “digits” are represented by letters from the English alphabet: lower case letters for <code>\int_to_base:n</code> and upper case ones for <code>\int_to_Base:n</code> . The maximum <i>⟨base⟩</i> value is 36. The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter).
Updated: 2014-02-11	

**TeXhackers note:** This is a generic version of `\int_to_bin:n`, etc.

<code>\int_to_roman:n</code> ☆	<code>\int_to_roman:n {⟨integer expression⟩}</code>
<code>\int_to_Roman:n</code> ☆	Places the value of the <i>⟨integer expression⟩</i> in the input stream as Roman numerals, either lower case ( <code>\int_to_roman:n</code> ) or upper case ( <code>\int_to_Roman:n</code> ). The Roman numerals are letters with category code 11 (letter).
Updated: 2011-10-22	

## 9 Converting from other formats to integers

<code>\int_from_alph:n</code> ★	<code>\int_from_alph:n {⟨letters⟩}</code>
Updated: 2014-08-25	Converts the <i>⟨letters⟩</i> into the integer (base 10) representation and leaves this in the input stream. The <i>⟨letters⟩</i> are first converted to a string, with no expansion. Lower and upper case letters from the English alphabet may be used, with “a” equal to 1 through to “z” equal to 26. The function also accepts a leading sign, made of + and -. This is the inverse function of <code>\int_to_alph:n</code> and <code>\int_to_Alph:n</code> .

<code>\int_from_bin:n</code> ★	<code>\int_from_bin:n {⟨binary number⟩}</code>
New: 2014-02-11 Updated: 2014-08-25	Converts the <i>⟨binary number⟩</i> into the integer (base 10) representation and leaves this in the input stream. The <i>⟨binary number⟩</i> is first converted to a string, with no expansion. The function accepts a leading sign, made of + and -, followed by binary digits. This is the inverse function of <code>\int_to_bin:n</code> .

<hr/> <code>\int_from_hex:n</code> ★ <hr/>	<code>\int_from_hex:n {⟨hexadecimal number⟩}</code>
New: 2014-02-11 Updated: 2014-08-25 <hr/>	Converts the <i>⟨hexadecimal number⟩</i> into the integer (base 10) representation and leaves this in the input stream. Digits greater than 9 may be represented in the <i>⟨hexadecimal number⟩</i> by upper or lower case letters. The <i>⟨hexadecimal number⟩</i> is first converted to a string, with no expansion. The function also accepts a leading sign, made of + and -. This is the inverse function of <code>\int_to_hex:n</code> and <code>\int_to_Hex:n</code> .
<hr/> <code>\int_from_oct:n</code> ★ <hr/>	<code>\int_from_oct:n {⟨octal number⟩}</code>
New: 2014-02-11 Updated: 2014-08-25 <hr/>	Converts the <i>⟨octal number⟩</i> into the integer (base 10) representation and leaves this in the input stream. The <i>⟨octal number⟩</i> is first converted to a string, with no expansion. The function accepts a leading sign, made of + and -, followed by octal digits. This is the inverse function of <code>\int_to_oct:n</code> .
<hr/> <code>\int_from_roman:n</code> ★ <hr/>	<code>\int_from_roman:n {⟨roman numeral⟩}</code>
Updated: 2014-08-25 <hr/>	Converts the <i>⟨roman numeral⟩</i> into the integer (base 10) representation and leaves this in the input stream. The <i>⟨roman numeral⟩</i> is first converted to a string, with no expansion. The <i>⟨roman numeral⟩</i> may be in upper or lower case; if the numeral contains characters besides <code>mdclxvi</code> or <code>MDCLXVI</code> then the resulting value is -1. This is the inverse function of <code>\int_to_roman:n</code> and <code>\int_to_Roman:n</code> .
<hr/> <code>\int_from_base:nn</code> ★ <hr/>	<code>\int_from_base:nn {⟨number⟩} {⟨base⟩}</code>
Updated: 2014-08-25 <hr/>	Converts the <i>⟨number⟩</i> expressed in <i>⟨base⟩</i> into the appropriate value in base 10. The <i>⟨number⟩</i> is first converted to a string, with no expansion. The <i>⟨number⟩</i> should consist of digits and letters (either lower or upper case), plus optionally a leading sign. The maximum <i>⟨base⟩</i> value is 36. This is the inverse function of <code>\int_to_base:nn</code> and <code>\int_to_Base:nn</code> .

## 10 Viewing integers

<hr/> <code>\int_show:N</code> <code>\int_show:c</code> <hr/>	<code>\int_show:N ⟨integer⟩</code>
	Displays the value of the <i>⟨integer⟩</i> on the terminal.
<hr/> <code>\int_show:n</code> <hr/>	<code>\int_show:n {⟨integer expression⟩}</code>
New: 2011-11-22 Updated: 2015-08-07 <hr/>	Displays the result of evaluating the <i>⟨integer expression⟩</i> on the terminal.
<hr/> <code>\int_log:N</code> <code>\int_log:c</code> <hr/>	<code>\int_log:N ⟨integer⟩</code>
New: 2014-08-22 Updated: 2015-08-03 <hr/>	Writes the value of the <i>⟨integer⟩</i> in the log file.
<hr/> <code>\int_log:n</code> <hr/>	<code>\int_log:n {⟨integer expression⟩}</code>
New: 2014-08-22 Updated: 2015-08-07 <hr/>	Writes the result of evaluating the <i>⟨integer expression⟩</i> in the log file.

## 11 Constant integers

---

`\c_zero`  
`\c_one`  
`\c_two`  
`\c_three`  
`\c_four`  
`\c_five`  
`\c_six`  
`\c_seven`  
`\c_eight`  
`\c_nine`  
`\c_ten`  
`\c_eleven`  
`\c_twelve`  
`\c_thirteen`  
`\c_fourteen`  
`\c_fifteen`  
`\c_sixteen`  
`\c_thirty_two`  
`\c_one_hundred`  
`\c_two_hundred_fifty_five`  
`\c_two_hundred_fifty_six`  
`\c_one_thousand`  
`\c_ten_thousand`

---

Integer values used with primitive tests and assignments: self-terminating nature makes these more convenient and faster than literal numbers.

---

`\c_max_int`

---

The maximum value that can be stored as an integer.

---

`\c_max_register_int`

---

Maximum number of registers.

---

`\c_max_char_int`

---

Maximum character code completely supported by the engine.

## 12 Scratch integers

---

`\l_tmpa_int`  
`\l_tmpb_int`

---

Scratch integer for local assignment. These are never used by the kernel code, and so are safe for use with any L<sup>A</sup>T<sub>E</sub>X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

---

`\g_tmpa_int`  
`\g_tmpb_int`

---

Scratch integer for global assignment. These are never used by the kernel code, and so are safe for use with any L<sup>A</sup>T<sub>E</sub>X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

## 13 Primitive conditionals

---

<code>\if_int_compare:w</code> ★	<code>\if_int_compare:w &lt;integer&gt; &lt;relation&gt; &lt;integer&gt;</code> <code>  &lt;true code&gt;</code> <code>\else:</code> <code>  &lt;false code&gt;</code> <code>\fi:</code>
----------------------------------	--

---

Compare two integers using `<relation>`, which must be one of =, < or > with category code 12. The `\else:` branch is optional.

**T<sub>E</sub>Xhackers note:** These are both names for the T<sub>E</sub>X primitive `\ifnum`.

---

<code>\if_case:w</code> ★	<code>\if_case:w &lt;integer&gt; &lt;case<sub>0</sub>&gt;</code> <code>\or:           ★</code> <code>  &lt;case<sub>1</sub>&gt;</code> <code>  ...           </code> <code>  &lt;default&gt;</code> <code>\fi:</code>
---------------------------	--

---

Selects a case to execute based on the value of the `<integer>`. The first case (`<case0>`) is executed if `<integer>` is 0, the second (`<case1>`) if the `<integer>` is 1, *etc.* The `<integer>` may be a literal, a constant or an integer expression (*e.g.* using `\int_eval:n`).

**T<sub>E</sub>Xhackers note:** These are the T<sub>E</sub>X primitives `\ifcase` and `\or`.

---

<code>\if_int_odd:w</code> ★	<code>\if_int_odd:w &lt;tokens&gt; &lt;optional space&gt;</code> <code>  &lt;true code&gt;</code> <code>\else:</code> <code>  &lt;true code&gt;</code> <code>\fi:</code>
------------------------------	--

---

Expands `<tokens>` until a non-numeric token or a space is found, and tests whether the resulting `<integer>` is odd. If so, `<true code>` is executed. The `\else:` branch is optional.

**T<sub>E</sub>Xhackers note:** This is the T<sub>E</sub>X primitive `\ifodd`.

## 14 Internal functions

---

<code>\__int_to_roman:w</code> ★	<code>\__int_to_roman:w &lt;integer&gt; &lt;space&gt; or &lt;non-expandable token&gt;</code>
----------------------------------	--

---

Converts `<integer>` to its lower case Roman representation. Expansion ends when a space or non-expandable token is found. Note that this function produces a string of letters with category code 12 and that protected functions *are* expanded by this process. Negative `<integer>` values result in no output, although the function does not terminate expansion until a suitable endpoint is found in the same way as for positive numbers.

**T<sub>E</sub>Xhackers note:** This is the T<sub>E</sub>X primitive `\romannumeral` renamed.

---

<code>\_int_value:w</code>	★	<code>\_int_value:w</code> $\langle integer \rangle$
<code>\_int_value:w</code>		<code>\_int_value:w</code> $\langle tokens \rangle$ $\langle optional\ space \rangle$

---

Expands  $\langle tokens \rangle$  until an  $\langle integer \rangle$  is formed. One space may be gobbled in the process.

**TeXhackers note:** This is the TeX primitive `\number`.

---

<code>\_int_eval:w</code>	★	<code>\_int_eval:w</code> $\langle intexpr \rangle$ <code>\_int_eval_end:</code>
<code>\_int_eval_end:</code>	★	

---

Evaluates  $\langle integer\ expression \rangle$  as described for `\int_eval:n`. The evaluation stops when an unexpandable token which is not a valid part of an integer is read or when `\_int_eval_end:` is reached. The latter is gobbled by the scanner mechanism: `\_int_eval_end:` itself is unexpandable but used correctly the entire construct is expandable.

**TeXhackers note:** This is the  $\varepsilon$ -TeX primitive `\numexpr`.

---

<code>\_prg_compare_error:</code>	<code>\_prg_compare_error:</code>
<code>\_prg_compare_error:Nw</code>	<code>\_prg_compare_error:Nw</code> $\langle token \rangle$

---

These are used within `\int_compare:nTF`, `\dim_compare:nTF` and so on to recover correctly if the n-type argument does not contain a properly-formed relation.

## Part X

# The l3intarray package: low-level arrays of small integers

## 1 l3intarray documentation

This module provides no user function: at present it is meant for kernel use only.

It is a wrapper around the `\fontdimen` primitive, used to store arrays of integers (with a restricted range: absolute value at most  $2^{30} - 1$ ). In contrast to `l3seq` sequences the access to individual entries is done in constant time rather than linear time, but only integers can be stored. More precisely, the primitive `\fontdimen` stores dimensions but the `l3intarray` package transparently converts these from/to integers. Assignments are always global.

While LuaTeX’s memory is extensible, other engines can “only” deal with a bit less than  $4 \times 10^6$  entries in all `\fontdimen` arrays combined (with default TeXLive settings).

### 1.1 Internal functions

---

<code>\__intarray_new:Nn</code>	<code>\__intarray_new:Nn &lt;intarray var&gt; {&lt;size&gt;}</code>
---------------------------------	---

---

Evaluates the integer expression `<size>` and allocates an `<integer array variable>` with that number of (zero) entries.

---

<code>\__intarray_count:N</code> ★	<code>\__intarray_count:N &lt;intarray var&gt;</code>
------------------------------------	---

---

Expands to the number of entries in the `<integer array variable>`. Contrarily to `\seq_count:N` this is performed in constant time.

---

<code>\__intarray_gset:Nnn</code>	<code>\__intarray_gset:Nnn &lt;intarray var&gt; {&lt;position&gt;} {&lt;value&gt;}</code>
<code>\__intarray_gset_fast:Nnn</code>	<code>\__intarray_gset_fast:Nnn &lt;intarray var&gt; {&lt;position&gt;} {&lt;value&gt;}</code>

---

Stores the result of evaluating the integer expression `<value>` into the `<integer array variable>` at the (integer expression) `<position>`. While `\__intarray_gset:Nnn` checks that the `<position>` is between 1 and the `\__intarray_count:N` and that the `<value>`’s absolute value is at most  $2^{30} - 1$ , the “fast” function performs no such bound check. Assignments are always global.

---

<code>\__intarray_item:Nn</code> ★	<code>\__intarray_item:Nn &lt;intarray var&gt; {&lt;position&gt;}</code>
<code>\__intarray_item_fast:Nn</code> ★	<code>\__intarray_item_fast:Nn &lt;intarray var&gt; {&lt;position&gt;}</code>

---

Expands to the integer entry stored at the (integer expression) `<position>` in the `<integer array variable>`. While `\__intarray_item:Nn` checks that the `<position>` is between 1 and the `\__intarray_count:N`, the “fast” function performs no such bound check.



## Part XI

# The l3flag package: expandable flags

Flags are the only data-type that can be modified in expansion-only contexts. This module is meant mostly for kernel use: in almost all cases, booleans or integers should be preferred to flags because they are very significantly faster.

A flag can hold any non-negative value, which we call its *height*. In expansion-only contexts, a flag can only be “raised”: this increases the *height* by 1. The *height* can also be queried expandably. However, decreasing it, or setting it to zero requires non-expandable assignments.

Flag variables are always local. They are referenced by a *flag name* such as `str_missing`. The *flag name* is used as part of `\use:c` constructions hence is expanded at point of use. It must expand to character tokens only, with no spaces.

A typical use case of flags would be to keep track of whether an exceptional condition has occurred during expandable processing, and produce a meaningful (non-expandable) message after the end of the expandable processing. This is exemplified by `l3str-convert`, which for performance reasons performs conversions of individual characters expandably and for readability reasons produces a single error message describing incorrect inputs that were encountered.

Flags should not be used without carefully considering the fact that raising a flag takes a time and memory proportional to its height. Flags should not be used unless unavoidable.

## 1 Setting up flags

---

---

<code>\flag_new:n</code>	<code>\flag_new:n {&lt;flag name&gt;}</code>
--------------------------	--

Creates a new flag with a name given by *flag name*, or raises an error if the name is already taken. The *flag name* may not contain spaces. The declaration is global, but flags are always local variables. The *flag* initially has zero height.

---

---

<code>\flag_clear:n</code>	<code>\flag_clear:n {&lt;flag name&gt;}</code>
----------------------------	--

The *flag*’s height is set to zero. The assignment is local.

---

---

<code>\flag_clear_new:n</code>	<code>\flag_clear_new:n {&lt;flag name&gt;}</code>
--------------------------------	--

Ensures that the *flag* exists globally by applying `\flag_new:n` if necessary, then applies `\flag_clear:n`, setting the height to zero locally.

---

---

<code>\flag_show:n</code>	<code>\flag_show:n {&lt;flag name&gt;}</code>
---------------------------	---

Displays the *flag*’s height in the terminal.

---

---

<code>\flag_log:n</code>	<code>\flag_log:n {&lt;flag name&gt;}</code>
--------------------------	--

Writes the *flag*’s height to the log file.

## 2 Expandable flag commands

<hr/> <code>\flag_if_exist:n</code> ★	<code>\flag_if_exist:n {⟨flag name⟩}</code>
<hr/> <code>\flag_if_exist:n</code> <u><code>TF</code></u> ★	This function returns <code>true</code> if the <code>⟨flag name⟩</code> references a flag that has been defined previously, and <code>false</code> otherwise.
<hr/> <code>\flag_if_raised:n</code> ★	<code>\flag_if_raised:n {⟨flag name⟩}</code>
<hr/> <code>\flag_if_raised:n</code> <u><code>TF</code></u> ★	This function returns <code>true</code> if the <code>⟨flag⟩</code> has non-zero height, and <code>false</code> if the <code>⟨flag⟩</code> has zero height.
<hr/> <code>\flag_height:n</code> ★	<code>\flag_height:n {⟨flag name⟩}</code>
	Expands to the height of the <code>⟨flag⟩</code> as an integer denotation.
<hr/> <code>\flag_raise:n</code> ★	<code>\flag_raise:n {⟨flag name⟩}</code>
	The <code>⟨flag⟩</code> 's height is increased by 1 locally.

## Part XII

# The l3quark package

## Quarks

### 1 Introduction to quarks and scan marks

Two special types of constants in L<sup>A</sup>T<sub>E</sub>X3 are “quarks” and “scan marks”. By convention all constants of type quark start out with `\q_`, and scan marks start with `\s_`. Scan marks are for internal use by the kernel: they are not intended for more general use.

#### 1.1 Quarks

Quarks are control sequences that expand to themselves and should therefore *never* be executed directly in the code. This would result in an endless loop!

They are meant to be used as delimiter in weird functions, with the most command use case as the ‘stop token’ (*i.e.* `\q_stop`). For example, when writing a macro to parse a user-defined date

```
\date_parse:n {19/June/1981}
```

one might write a command such as

```
\cs_new:Npn \date_parse:n #1 { \date_parse_aux:w #1 \q_stop }
\cs_new:Npn \date_parse_aux:w #1 / #2 / #3 \q_stop
{ <do something with the date> }
```

Quarks are sometimes also used as error return values for functions that receive erroneous input. For example, in the function `\prop_get:NnN` to retrieve a value stored in some key of a property list, if the key does not exist then the return value is the quark `\q_no_value`. As mentioned above, such quarks are extremely fragile and it is imperative when using such functions that code is carefully written to check for pathological cases to avoid leakage of a quark into an uncontrolled environment.

Quarks also permit the following ingenious trick when parsing tokens: when you pick up a token in a temporary variable and you want to know whether you have picked up a particular quark, all you have to do is compare the temporary variable to the quark using `\tl_if_eq:NNTF`. A set of special quark testing functions is set up below. All the quark testing functions are expandable although the ones testing only single tokens are much faster. An example of the quark testing functions and their use in recursion can be seen in the implementation of `\clist_map_function:NN`.

### 2 Defining quarks

---

```
\quark_new:N \quark_new:N <quark>
```

Creates a new `<quark>` which expands only to `<quark>`. The `<quark>` is defined globally, and an error message is raised if the name was already taken.

<u><code>\q_stop</code></u>	Used as a marker for delimited arguments, such as  <code>\cs_set:Npn \tmp:w #1#2 \q_stop {#1}</code>
<u><code>\q_mark</code></u>	Used as a marker for delimited arguments when <code>\q_stop</code> is already in use.
<u><code>\q_nil</code></u>	Quark to mark a null value in structured variables or functions. Used as an end delimiter when this may itself may need to be tested (in contrast to <code>\q_stop</code> , which is only ever used as a delimiter).
<u><code>\q_no_value</code></u>	A canonical value for a missing value, when one is requested from a data structure. This is therefore used as a “return” value by functions such as <code>\prop_get:NnN</code> if there is no data to return.

### 3 Quark tests

The method used to define quarks means that the single token (N) tests are faster than the multi-token (n) tests. The later should therefore only be used when the argument can definitely take more than a single token.

<u><code>\quark_if_nil_p:N</code> ★</u>	<code>\quark_if_nil_p:N &lt;token&gt;</code>
<u><code>\quark_if_nil:NTF</code> ★</u>	<code>\quark_if_nil:NTF &lt;token&gt; {&lt;true code&gt;} {&lt;false code&gt;}</code>
	Tests if the <i>&lt;token&gt;</i> is equal to <code>\q_nil</code> .
<u><code>\quark_if_nil_p:n</code> ★</u>	<code>\quark_if_nil_p:n {&lt;token list&gt;}</code>
<u><code>\quark_if_nil_p:(o V)</code> ★</u>	<code>\quark_if_nil:nTF {&lt;token list&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>
<u><code>\quark_if_nil:nTF</code> ★</u>	Tests if the <i>&lt;token list&gt;</i> contains only <code>\q_nil</code> (distinct from <i>&lt;token list&gt;</i> being empty or containing <code>\q_nil</code> plus one or more other tokens).
<u><code>\quark_if_nil:(o V)TF</code> ★</u>	
<u><code>\quark_if_no_value_p:N</code> ★</u>	<code>\quark_if_no_value_p:N &lt;token&gt;</code>
<u><code>\quark_if_no_value_p:c</code> ★</u>	<code>\quark_if_no_value:NTF &lt;token&gt; {&lt;true code&gt;} {&lt;false code&gt;}</code>
<u><code>\quark_if_no_value:NTF</code> ★</u>	Tests if the <i>&lt;token&gt;</i> is equal to <code>\q_no_value</code> .
<u><code>\quark_if_no_value:cTF</code> ★</u>	
<u><code>\quark_if_no_value_p:n</code> ★</u>	<code>\quark_if_no_value_p:n {&lt;token list&gt;}</code>
<u><code>\quark_if_no_value:nTF</code> ★</u>	<code>\quark_if_no_value:nTF {&lt;token list&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>
	Tests if the <i>&lt;token list&gt;</i> contains only <code>\q_no_value</code> (distinct from <i>&lt;token list&gt;</i> being empty or containing <code>\q_no_value</code> plus one or more other tokens).

### 4 Recursion

This module provides a uniform interface to intercepting and terminating loops as when one is doing tail recursion. The building blocks follow below and an example is shown in Section 5.

---

<code>\q_recursion_tail</code>	This quark is appended to the data structure in question and appears as a real element there. This means it gets any list separators around it.
--------------------------------	---

---



---

<code>\q_recursion_stop</code>	This quark is added <i>after</i> the data structure. Its purpose is to make it possible to terminate the recursion at any point easily.
--------------------------------	---

---



---

<code>\quark_if_recursion_tail_stop:N</code>	<code>\quark_if_recursion_tail_stop:N &lt;token&gt;</code>
--	--

---

Tests if `<token>` contains only the marker `\q_recursion_tail`, and if so uses `\use_none_delimit_by_q_recursion_stop:w` to terminate the recursion that this belongs to. The recursion input must include the marker tokens `\q_recursion_tail` and `\q_recursion_stop` as the last two items.

---



---

<code>\quark_if_recursion_tail_stop:n</code>	<code>\quark_if_recursion_tail_stop:n {&lt;token list&gt;}</code>
--	---

---

`\quark_if_recursion_tail_stop:o`

---

Updated: 2011-09-06

---

Tests if the `<token list>` contains only `\q_recursion_tail`, and if so uses `\use_none_delimit_by_q_recursion_stop:w` to terminate the recursion that this belongs to. The recursion input must include the marker tokens `\q_recursion_tail` and `\q_recursion_stop` as the last two items.

---



---

<code>\quark_if_recursion_tail_stop_do:Nn</code>	<code>\quark_if_recursion_tail_stop_do:Nn &lt;token&gt; {&lt;insertion&gt;}</code>
--	--

---

Tests if `<token>` contains only the marker `\q_recursion_tail`, and if so uses `\use_none_delimit_by_q_recursion_stop:w` to terminate the recursion that this belongs to. The recursion input must include the marker tokens `\q_recursion_tail` and `\q_recursion_stop` as the last two items. The `<insertion>` code is then added to the input stream after the recursion has ended.

---



---

<code>\quark_if_recursion_tail_stop_do:nn</code>	<code>\quark_if_recursion_tail_stop_do:nn {&lt;token list&gt;} {&lt;insertion&gt;}</code>
--	---

---

`\quark_if_recursion_tail_stop_do:on`

---

Updated: 2011-09-06

---

Tests if the `<token list>` contains only `\q_recursion_tail`, and if so uses `\use_none_delimit_by_q_recursion_stop:w` to terminate the recursion that this belongs to. The recursion input must include the marker tokens `\q_recursion_tail` and `\q_recursion_stop` as the last two items. The `<insertion>` code is then added to the input stream after the recursion has ended.

---

## 5 An example of recursion with quarks

Quarks are mainly used internally in the `expl3` code to define recursion functions such as `\tl_map_inline:nn` and so on. Here is a small example to demonstrate how to use quarks in this fashion. We shall define a command called `\my_map_dbl:nn` which takes a token list and applies an operation to every *pair* of tokens. For example, `\my_map_dbl:nn {abcd} {[--#1--#2--]~}` would produce “`[-a-b-] [-c-d-]` ”. Using quarks to define such functions simplifies their logic and ensures robustness in many cases.

Here's the definition of `\my_map_dbl:nn`. First of all, define the function that does the processing based on the inline function argument `#2`. Then initiate the recursion using an internal function. The token list `#1` is terminated using `\q_recursion_tail`, with delimiters according to the type of recursion (here a pair of `\q_recursion_tail`), concluding with `\q_recursion_stop`. These quarks are used to mark the end of the token list being operated upon.

```
\cs_new:Npn \my_map_dbl:nn #1#2
{
  \cs_set:Npn \__my_map_dbl_fn:nn ##1 ##2 {#2}
  \__my_map_dbl:nn #1 \q_recursion_tail \q_recursion_tail
  \q_recursion_stop
}
```

The definition of the internal recursion function follows. First check if either of the input tokens are the termination quarks. Then, if not, apply the inline function to the two arguments.

```
\cs_new:Nn \__my_map_dbl:nn
{
  \quark_if_recursion_tail_stop:n {#1}
  \quark_if_recursion_tail_stop:n {#2}
  \__my_map_dbl_fn:nn {#1} {#2}
}
```

Finally, recurse:

```
\__my_map_dbl:nn
}
```

Note that contrarily to L<sup>A</sup>T<sub>E</sub>X3 built-in mapping functions, this mapping function cannot be nested, since the second map would overwrite the definition of `\__my_map_dbl_fn:nn`.

## 6 Internal quark functions

---

```
\__quark_if_recursion_tail_break:NN \__quark_if_recursion_tail_break:nN {<token list>}
\__quark_if_recursion_tail_break:nN \<type>_map_break:
```

---

Tests if `<token list>` contains only `\q_recursion_tail`, and if so terminates the recursion using `\<type>_map_break:.` The recursion end should be marked by `\prg_break_point:Nn \<type>_map_break:.`

## 7 Scan marks

Scan marks are control sequences set equal to `\scan_stop:`, hence never expand in an expansion context and are (largely) invisible if they are encountered in a typesetting context.

Like quarks, they can be used as delimiters in weird functions and are often safer to use for this purpose. Since they are harmless when executed by T<sub>E</sub>X in non-expandable contexts, they can be used to mark the end of a set of instructions. This allows to skip to that point if the end of the instructions should not be performed (see l3regex).

The scan marks system is only for internal use by the kernel team in a small number of very specific places. These functions should not be used more generally.

---

<code>\_scan\_new:N</code>	<code>\_scan\_new:N</code> $\langle scan\ mark \rangle$
----------------------------	---

Creates a new  $\langle scan\ mark \rangle$  which is set equal to `\scan\_stop:`. The  $\langle scan\ mark \rangle$  is defined globally, and an error message is raised if the name was already taken by another scan mark.

---

<code>\s\_stop</code>	Used at the end of a set of instructions, as a marker that can be jumped to using <code>\_use\_none\_delimit\_by\_s\_stop:w</code> .
-----------------------	--

---

<code>\_use\_none\_delimit\_by\_s\_stop:w</code>	<code>\_use\_none\_delimit\_by\_s\_stop:w</code> $\langle tokens \rangle$ <code>\s\_stop</code>
--	---

Removes the  $\langle tokens \rangle$  and `\s\_stop` from the input stream. This leads to a low-level TeX error if `\s\_stop` is absent.

## Part XIII

# The l3prg package

## Control structures

Conditional processing in L<sup>A</sup>T<sub>E</sub>X3 is defined as something that performs a series of tests, possibly involving assignments and calling other functions that do not read further ahead in the input stream. After processing the input, a *state* is returned. The states returned are *⟨true⟩* and *⟨false⟩*.

L<sup>A</sup>T<sub>E</sub>X3 has two forms of conditional flow processing based on these states. The first form is predicate functions that turn the returned state into a boolean *⟨true⟩* or *⟨false⟩*. For example, the function `\cs_if_free_p:N` checks whether the control sequence given as its argument is free and then returns the boolean *⟨true⟩* or *⟨false⟩* values to be used in testing with `\if_predicate:w` or in functions to be described below. The second form is the kind of functions choosing a particular argument from the input stream based on the result of the testing as in `\cs_if_free:NTF` which also takes one argument (the *N*) and then executes either **true** or **false** depending on the result.

**T<sub>E</sub>Xhackers note:** The arguments are executed after exiting the underlying `\if... \fi` structure.

## 1 Defining a set of conditional functions

---

```
\prg_new_conditional:Npnn
\prg_set_conditional:Npnn
\prg_new_conditional:Nnn
\prg_set_conditional:Nnn
```

---

Updated: 2012-02-06

---

```
\prg_new_conditional:Npnn \<name>:<arg spec> <parameters> {\<conditions>} {\<code>}
\prg_new_conditional:Nnn \<name>:<arg spec> {\<conditions>} {\<code>}
```

These functions create a family of conditionals using the same *{⟨code⟩}* to perform the test created. Those conditionals are expandable if *⟨code⟩* is. The **new** versions check for existing definitions and perform assignments globally (cf. `\cs_new:Npn`) whereas the **set** versions do no check and perform assignments locally (cf. `\cs_set:Npn`). The conditionals created are dependent on the comma-separated list of *⟨conditions⟩*, which should be one or more of **p**, **T**, **F** and **TF**.

---

```
\prg_new_protected_conditional:Npnn \prg_new_protected_conditional:Npnn \<name>:<arg spec> <parameters>
\prg_set_protected_conditional:Npnn {\<conditions>} {\<code>}
\prg_new_protected_conditional:Nnn \prg_new_protected_conditional:Nnn \<name>:<arg spec>
\prg_set_protected_conditional:Nnn {\<conditions>} {\<code>}
```

---

Updated: 2012-02-06

---

These functions create a family of protected conditionals using the same *{⟨code⟩}* to perform the test created. The *⟨code⟩* does not need to be expandable. The **new** version check for existing definitions and perform assignments globally (cf. `\cs_new:Npn`) whereas the **set** version do not (cf. `\cs_set:Npn`). The conditionals created are depended on the comma-separated list of *⟨conditions⟩*, which should be one or more of **T**, **F** and **TF** (not **p**).

The conditionals are defined by `\prg_new_conditional:Npnn` and friends as:



- `\<name>_p:<arg spec>` — a predicate function which will supply either a logical `true` or logical `false`. This function is intended for use in cases where one or more logical tests are combined to lead to a final outcome. This function cannot be defined for `protected` conditionals.
- `\<name>:<arg spec>T` — a function with one more argument than the original `<arg spec>` demands. The `<true branch>` code in this additional argument will be left on the input stream only if the test is `true`.
- `\<name>:<arg spec>F` — a function with one more argument than the original `<arg spec>` demands. The `<false branch>` code in this additional argument will be left on the input stream only if the test is `false`.
- `\<name>:<arg spec>TF` — a function with two more argument than the original `<arg spec>` demands. The `<true branch>` code in the first additional argument will be left on the input stream if the test is `true`, while the `<false branch>` code in the second argument will be left on the input stream if the test is `false`.

The `<code>` of the test may use `<parameters>` as specified by the second argument to `\prg_set_conditional:Npnn`: this should match the `<argument specification>` but this is not enforced. The `Nnn` versions infer the number of arguments from the argument specification given (cf. `\cs_new:Nn`, etc.). Within the `<code>`, the functions `\prg_return_true:` and `\prg_return_false:` are used to indicate the logical outcomes of the test.

An example can easily clarify matters here:

```
\prg_set_conditional:Npnn \foo_if_bar:NN #1#2 { p , T , TF }
{
  \if_meaning:w \l_tmpa_tl #1
  \prg_return_true:
\else:
  \if_meaning:w \l_tmpa_tl #2
  \prg_return_true:
\else:
  \prg_return_false:
\fi:
\fi:
}
```

This defines the function `\foo_if_bar_p:NN`, `\foo_if_bar:NNTF` and `\foo_if_bar:NNT` but not `\foo_if_bar:NNF` (because `F` is missing from the `<conditions>` list). The return statements take care of resolving the remaining `\else:` and `\fi:` before returning the state. There must be a return statement for each branch; failing to do so will result in erroneous output if that branch is executed.

---

<code>\prg_new_eq_conditional:Nnn</code>	<code>\prg_new_eq_conditional:Nnn \&lt;name1&gt;:&lt;arg spec1&gt; \&lt;name2&gt;:&lt;arg spec2&gt;</code>
<code>\prg_set_eq_conditional:Nnn</code>	<code>{&lt;conditions&gt;}</code>

---

These functions copy a family of conditionals. The `new` version checks for existing definitions (cf. `\cs_new_eq:NN`) whereas the `set` version does not (cf. `\cs_set_eq:NN`). The conditionals copied are depended on the comma-separated list of `<conditions>`, which should be one or more of `p`, `T`, `F` and `TF`.

---

<code>\prg_return_true:</code>	★	<code>\prg_return_true:</code>
<code>\prg_return_false:</code>	★	<code>\prg_return_false:</code>

---

These “return” functions define the logical state of a conditional statement. They appear within the code for a conditional function generated by `\prg_set_conditional:Npnn`, *etc.*, to indicate when a true or false branch should be taken. While they may appear multiple times each within the code of such conditionals, the execution of the conditional must result in the expansion of one of these two functions *exactly once*.

The return functions trigger what is internally an **f**-expansion process to complete the evaluation of the conditional. Therefore, after `\prg_return_true:` or `\prg_return_false:` there must be no non-expandable material in the input stream for the remainder of the expansion of the conditional code. This includes other instances of either of these functions.

## 2 The boolean data type

This section describes a boolean data type which is closely connected to conditional processing as sometimes you want to execute some code depending on the value of a switch (*e.g.*, draft/final) and other times you perhaps want to use it as a predicate function in an `\if_predicate:w` test. The problem of the primitive `\if_false:` and `\if_true:` tokens is that it is not always safe to pass them around as they may interfere with scanning for termination of primitive conditional processing. Therefore, we employ two canonical booleans: `\c_true_bool` or `\c_false_bool`. Besides preventing problems as described above, it also allows us to implement a simple boolean parser supporting the logical operations And, Or, Not, *etc.* which can then be used on both the boolean type and predicate functions.

All conditional `\bool_` functions except assignments are expandable and expect the input to also be fully expandable (which generally means being constructed from predicate functions and booleans, possibly nested).

**TeXhackers note:** The `bool` data type is not implemented using the `\iffalse/\iftrue` primitives, in contrast to `\newif`, *etc.*, in plain TeX, L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> and so on. Programmers should not base use of `bool` switches on any particular expectation of the implementation.

---

<code>\bool_new:N</code>	<code>\bool_new:N &lt;boolean&gt;</code>
<code>\bool_new:c</code>	

---

Creates a new `<boolean>` or raises an error if the name is already taken. The declaration is global. The `<boolean>` is initially **false**.

---

<code>\bool_set_false:N</code>	<code>\bool_set_false:N &lt;boolean&gt;</code>
<code>\bool_set_false:c</code>	
<code>\bool_gset_false:N</code>	Sets <code>&lt;boolean&gt;</code> logically <b>false</b> .
<code>\bool_gset_false:c</code>	

---



---

<code>\bool_set_true:N</code>	<code>\bool_set_true:N &lt;boolean&gt;</code>
<code>\bool_set_true:c</code>	
<code>\bool_gset_true:N</code>	Sets <code>&lt;boolean&gt;</code> logically <b>true</b> .
<code>\bool_gset_true:c</code>	

---

<hr/>	
<code>\bool_set_eq:NN</code>	<code>\bool_set_eq:NN &lt;boolean<sub>1</sub>&gt; &lt;boolean<sub>2</sub>&gt;</code>
<code>\bool_set_eq:(cN Nc cc)</code>	Sets $\langle boolean_1 \rangle$ to the current value of $\langle boolean_2 \rangle$ .
<code>\bool_gset_eq:NN</code>	
<code>\bool_gset_eq:(cN Nc cc)</code>	
<hr/>	
<code>\bool_set:Nn</code>	<code>\bool_set:Nn &lt;boolean&gt; {\&lt;boolexpr&gt;}</code>
<code>\bool_set:cn</code>	Evaluates the $\langle boolean \text{ expression} \rangle$ as described for <code>\bool_if:nTF</code> , and sets the $\langle boolean \rangle$
<code>\bool_gset:Nn</code>	variable to the logical truth of this evaluation.
<code>\bool_gset:cn</code>	
<hr/>	
Updated: 2012-07-08	
<hr/>	
<code>\bool_if_p:N</code> ★	<code>\bool_if_p:N &lt;boolean&gt;</code>
<code>\bool_if_p:c</code> ★	<code>\bool_if:NTF &lt;boolean&gt; {\&lt;true code&gt;} {\&lt;false code&gt;}</code>
<code>\bool_if:NTF</code> ★	Tests the current truth of $\langle boolean \rangle$ , and continues expansion based on this result.
<code>\bool_if:cTF</code> ★	
<hr/>	
<code>\bool_show:N</code>	<code>\bool_show:N &lt;boolean&gt;</code>
<code>\bool_show:c</code>	Displays the logical truth of the $\langle boolean \rangle$ on the terminal.
New: 2012-02-09	
Updated: 2015-08-01	
<hr/>	
<code>\bool_show:n</code>	<code>\bool_show:n {\&lt;boolean expression&gt;}</code>
New: 2012-02-09	Displays the logical truth of the $\langle boolean \text{ expression} \rangle$ on the terminal.
Updated: 2015-08-07	
<hr/>	
<code>\bool_log:N</code>	<code>\bool_log:N &lt;boolean&gt;</code>
<code>\bool_log:c</code>	Writes the logical truth of the $\langle boolean \rangle$ in the log file.
New: 2014-08-22	
Updated: 2015-08-03	
<hr/>	
<code>\bool_log:n</code>	<code>\bool_log:n {\&lt;boolean expression&gt;}</code>
New: 2014-08-22	Writes the logical truth of the $\langle boolean \text{ expression} \rangle$ in the log file.
Updated: 2015-08-07	
<hr/>	
<code>\bool_if_exist_p:N</code> ★	<code>\bool_if_exist_p:N &lt;boolean&gt;</code>
<code>\bool_if_exist_p:c</code> ★	<code>\bool_if_exist:NTF &lt;boolean&gt; {\&lt;true code&gt;} {\&lt;false code&gt;}</code>
<code>\bool_if_exist:NTF</code> ★	Tests whether the $\langle boolean \rangle$ is currently defined. This does not check that the $\langle boolean \rangle$
<code>\bool_if_exist:cTF</code> ★	really is a boolean variable.
New: 2012-03-03	
<hr/>	
<code>\l_tmpa_bool</code>	A scratch boolean for local assignment. It is never used by the kernel code, and so is
<code>\l_tmpb_bool</code>	safe for use with any L <sup>A</sup> T <sub>E</sub> X3-defined function. However, it may be overwritten by other
	non-kernel code and so should only be used for short-term storage.
<hr/>	
<code>\g_tmpa_bool</code>	A scratch boolean for global assignment. It is never used by the kernel code, and so is
<code>\g_tmpb_bool</code>	safe for use with any L <sup>A</sup> T <sub>E</sub> X3-defined function. However, it may be overwritten by other
	non-kernel code and so should only be used for short-term storage.

### 3 Boolean expressions

As we have a boolean datatype and predicate functions returning boolean  $\langle true \rangle$  or  $\langle false \rangle$  values, it seems only fitting that we also provide a parser for  $\langle boolean\ expressions \rangle$ .

A boolean expression is an expression which given input in the form of predicate functions and boolean variables, return boolean  $\langle true \rangle$  or  $\langle false \rangle$ . It supports the logical operations And, Or and Not as the well-known infix operators `&&` and `||` and prefix `!` with their usual precedences (namely, `&&` binds more tightly than `||`). In addition to this, parentheses can be used to isolate sub-expressions. For example,

```
\int_compare_p:n { 1 = 1 } &&
(
  \int_compare_p:n { 2 = 3 } ||
  \int_compare_p:n { 4 <= 4 } ||
  \str_if_eq_p:nn { abc } { def }
) &&
! \int_compare_p:n { 2 = 4 }
```

is a valid boolean expression.

At present, the infix operators `&&` and `||` perform lazy evaluation, but this will change in the near future. Contrarily to some other programming languages, the operators `&&` and `||` will evaluate both operands in all cases, even when the first operand is enough to determine the result. This “eager” evaluation should be contrasted with the “lazy” evaluation of `\bool_lazy_...` functions.

**TeXhackers note:** The eager evaluation of boolean expressions is unfortunately necessary. Indeed, a lazy parser can get confused if `&&` and `||` appear as (unbraced) arguments of some predicates.

Minimal (lazy) evaluation can be obtained using the conditionals `\bool_lazy_all:nTF`, `\bool_lazy_and:nnTF`, `\bool_lazy_any:nTF`, or `\bool_lazy_or:nnTF`, which only evaluate their boolean expression arguments when they are needed to determine the resulting truth value. For example, when evaluating the boolean expression

```
\bool_lazy_and_p:nn
{
  \bool_lazy_any_p:n
  {
    { \int_compare_p:n { 2 = 3 } }
    { \int_compare_p:n { 4 <= 4 } }
    { \int_compare_p:n { 1 = \error } } % skipped
  }
}
{ ! \int_compare_p:n { 2 = 4 } }
```

the line marked with `skipped` is not expanded because the result of `\bool_lazy_any_p:n` is known once the second boolean expression is found to be logically `true`. On the other hand, the last line is expanded because its logical value is needed to determine the result of `\bool_lazy_and_p:nn`.

---

\bool_if_p:n ★	\bool_if_p:n {<boolean expression>}
\bool_if:nTF ★	\bool_if:nTF {<boolean expression>} {<true code>} {<false code>}

---

Updated: 2012-07-08

Tests the current truth of *<boolean expression>*, and continues expansion based on this result. The *<boolean expression>* should consist of a series of predicates or boolean variables with the logical relationship between these defined using && (“And”), || (“Or”), ! (“Not”) and parentheses. The logical Not applies to the next predicate or group.

---

\bool_lazy_all_p:n ★	\bool_lazy_all_p:n { {<boolexpr <sub>1</sub> >} {<boolexpr <sub>2</sub> >} ... {<boolexpr <sub>N</sub> >} }
\bool_lazy_all:nTF ★	\bool_lazy_all:nTF { {<boolexpr <sub>1</sub> >} {<boolexpr <sub>2</sub> >} ... {<boolexpr <sub>N</sub> >} } {<true code>} {<false code>}

---

New: 2015-11-15

Implements the “And” operation on the *<boolean expressions>*, hence is **true** if all of them are **true** and **false** if any of them is **false**. Contrarily to the infix operator &&, only the *<boolean expressions>* which are needed to determine the result of \bool\_lazy\_all:nTF are evaluated. See also \bool\_lazy\_and:nnTF when there are only two *<boolean expressions>*.

---

\bool_lazy_and_p:nn ★	\bool_lazy_and_p:nn {<boolexpr <sub>1</sub> >} {<boolexpr <sub>2</sub> >}
\bool_lazy_and:nnTF ★	\bool_lazy_and:nnTF {<boolexpr <sub>1</sub> >} {<boolexpr <sub>2</sub> >} {<true code>} {<false code>}

---

New: 2015-11-15

Implements the “And” operation between two boolean expressions, hence is **true** if both are **true**. Contrarily to the infix operator &&, the *<boolexpr<sub>2</sub>>* is only evaluated if it is needed to determine the result of \bool\_lazy\_and:nnTF. See also \bool\_lazy\_all:nTF when there are more than two *<boolean expressions>*.

---

\bool_lazy_any_p:n ★	\bool_lazy_any_p:n { {<boolexpr <sub>1</sub> >} {<boolexpr <sub>2</sub> >} ... {<boolexpr <sub>N</sub> >} }
\bool_lazy_any:nTF ★	\bool_lazy_any:nTF { {<boolexpr <sub>1</sub> >} {<boolexpr <sub>2</sub> >} ... {<boolexpr <sub>N</sub> >} } {<true code>} {<false code>}

---

New: 2015-11-15

Implements the “Or” operation on the *<boolean expressions>*, hence is **true** if any of them is **true** and **false** if all of them are **false**. Contrarily to the infix operator ||, only the *<boolean expressions>* which are needed to determine the result of \bool\_lazy\_any:nTF are evaluated. See also \bool\_lazy\_or:nnTF when there are only two *<boolean expressions>*.

---

\bool_lazy_or_p:nn ★	\bool_lazy_or_p:nn {<boolexpr <sub>1</sub> >} {<boolexpr <sub>2</sub> >}
\bool_lazy_or:nnTF ★	\bool_lazy_or:nnTF {<boolexpr <sub>1</sub> >} {<boolexpr <sub>2</sub> >} {<true code>} {<false code>}

---

New: 2015-11-15

Implements the “Or” operation between two boolean expressions, hence is **true** if either one is **true**. Contrarily to the infix operator ||, the *<boolexpr<sub>2</sub>>* is only evaluated if it is needed to determine the result of \bool\_lazy\_or:nnTF. See also \bool\_lazy\_any:nTF when there are more than two *<boolean expressions>*.

---

\bool_not_p:n ★	\bool_not_p:n {<boolean expression>}
-----------------	--------------------------------------

---

Updated: 2012-07-08

Function version of !(*<boolean expression>*) within a boolean expression.

---

\bool_xor_p:nn ★	\bool_xor_p:nn {<boolexpr <sub>1</sub> >} {<boolexpr <sub>2</sub> >}
------------------	--

---

Updated: 2012-07-08

Implements an “exclusive or” operation between two boolean expressions. There is no infix operation for this logical operator.

## 4 Logical loops

Loops using either boolean expressions or stored boolean values.

<hr/>	
<code>\bool_do_until:Nn</code> ☆	<code>\bool_do_until:Nn &lt;boolean&gt; {&lt;code&gt;}</code>
<code>\bool_do_until:cn</code> ☆	
<hr/>	Places the <code>&lt;code&gt;</code> in the input stream for T <sub>E</sub> X to process, and then checks the logical value of the <code>&lt;boolean&gt;</code> . If it is <code>false</code> then the <code>&lt;code&gt;</code> is inserted into the input stream again and the process loops until the <code>&lt;boolean&gt;</code> is <code>true</code> .
<hr/>	
<code>\bool_do_while:Nn</code> ☆	<code>\bool_do_while:Nn &lt;boolean&gt; {&lt;code&gt;}</code>
<code>\bool_do_while:cn</code> ☆	
<hr/>	Places the <code>&lt;code&gt;</code> in the input stream for T <sub>E</sub> X to process, and then checks the logical value of the <code>&lt;boolean&gt;</code> . If it is <code>true</code> then the <code>&lt;code&gt;</code> is inserted into the input stream again and the process loops until the <code>&lt;boolean&gt;</code> is <code>false</code> .
<hr/>	
<code>\bool_until_do:Nn</code> ☆	<code>\bool_until_do:Nn &lt;boolean&gt; {&lt;code&gt;}</code>
<code>\bool_until_do:cn</code> ☆	
<hr/>	This function firsts checks the logical value of the <code>&lt;boolean&gt;</code> . If it is <code>false</code> the <code>&lt;code&gt;</code> is placed in the input stream and expanded. After the completion of the <code>&lt;code&gt;</code> the truth of the <code>&lt;boolean&gt;</code> is re-evaluated. The process then loops until the <code>&lt;boolean&gt;</code> is <code>true</code> .
<hr/>	
<code>\bool_while_do:Nn</code> ☆	<code>\bool_while_do:Nn &lt;boolean&gt; {&lt;code&gt;}</code>
<code>\bool_while_do:cn</code> ☆	
<hr/>	This function firsts checks the logical value of the <code>&lt;boolean&gt;</code> . If it is <code>true</code> the <code>&lt;code&gt;</code> is placed in the input stream and expanded. After the completion of the <code>&lt;code&gt;</code> the truth of the <code>&lt;boolean&gt;</code> is re-evaluated. The process then loops until the <code>&lt;boolean&gt;</code> is <code>false</code> .
<hr/>	
<code>\bool_do_until:nn</code> ☆	<code>\bool_do_until:nn {&lt;boolean expression&gt;} {&lt;code&gt;}</code>
Updated: 2012-07-08	
<hr/>	Places the <code>&lt;code&gt;</code> in the input stream for T <sub>E</sub> X to process, and then checks the logical value of the <code>&lt;boolean expression&gt;</code> as described for <code>\bool_if:nTF</code> . If it is <code>false</code> then the <code>&lt;code&gt;</code> is inserted into the input stream again and the process loops until the <code>&lt;boolean expression&gt;</code> evaluates to <code>true</code> .
<hr/>	
<code>\bool_do_while:nn</code> ☆	<code>\bool_do_while:nn {&lt;boolean expression&gt;} {&lt;code&gt;}</code>
Updated: 2012-07-08	
<hr/>	Places the <code>&lt;code&gt;</code> in the input stream for T <sub>E</sub> X to process, and then checks the logical value of the <code>&lt;boolean expression&gt;</code> as described for <code>\bool_if:nTF</code> . If it is <code>true</code> then the <code>&lt;code&gt;</code> is inserted into the input stream again and the process loops until the <code>&lt;boolean expression&gt;</code> evaluates to <code>false</code> .
<hr/>	
<code>\bool_until_do:nn</code> ☆	<code>\bool_until_do:nn {&lt;boolean expression&gt;} {&lt;code&gt;}</code>
Updated: 2012-07-08	
<hr/>	This function firsts checks the logical value of the <code>&lt;boolean expression&gt;</code> (as described for <code>\bool_if:nTF</code> ). If it is <code>false</code> the <code>&lt;code&gt;</code> is placed in the input stream and expanded. After the completion of the <code>&lt;code&gt;</code> the truth of the <code>&lt;boolean expression&gt;</code> is re-evaluated. The process then loops until the <code>&lt;boolean expression&gt;</code> is <code>true</code> .
<hr/>	
<code>\bool_while_do:nn</code> ☆	<code>\bool_while_do:nn {&lt;boolean expression&gt;} {&lt;code&gt;}</code>
Updated: 2012-07-08	
<hr/>	This function firsts checks the logical value of the <code>&lt;boolean expression&gt;</code> (as described for <code>\bool_if:nTF</code> ). If it is <code>true</code> the <code>&lt;code&gt;</code> is placed in the input stream and expanded. After the completion of the <code>&lt;code&gt;</code> the truth of the <code>&lt;boolean expression&gt;</code> is re-evaluated. The process then loops until the <code>&lt;boolean expression&gt;</code> is <code>false</code> .

## 5 Producing multiple copies

---

<code>\prg_replicate:nn</code> ★	<code>\prg_replicate:nn {&lt;integer expression&gt;} {&lt;tokens&gt;}</code>
----------------------------------	--

---

Updated: 2011-07-04

Evaluates the *<integer expression>* (which should be zero or positive) and creates the resulting number of copies of the *<tokens>*. The function is both expandable and safe for nesting. It yields its result after two expansion steps.

## 6 Detecting T<sub>E</sub>X's mode

---

<code>\mode_if_horizontal_p:</code> ★	<code>\mode_if_horizontal_p:</code>
<code>\mode_if_horizontal:TF</code> ★	<code>\mode_if_horizontal:TF {&lt;true code&gt;} {&lt;false code&gt;}</code>

---

Detects if T<sub>E</sub>X is currently in horizontal mode.

---

<code>\mode_if_inner_p:</code> ★	<code>\mode_if_inner_p:</code>
<code>\mode_if_inner:TF</code> ★	<code>\mode_if_inner:TF {&lt;true code&gt;} {&lt;false code&gt;}</code>

---

Detects if T<sub>E</sub>X is currently in inner mode.

---

<code>\mode_if_math_p:</code> ★	<code>\mode_if_math:TF {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\mode_if_math:TF</code> ★	

---

Detects if T<sub>E</sub>X is currently in maths mode.

Updated: 2011-09-05

---

<code>\mode_if_vertical_p:</code> ★	<code>\mode_if_vertical_p:</code>
<code>\mode_if_vertical:TF</code> ★	<code>\mode_if_vertical:TF {&lt;true code&gt;} {&lt;false code&gt;}</code>

---

Detects if T<sub>E</sub>X is currently in vertical mode.

## 7 Primitive conditionals

---

<code>\if_predicate:w</code> ★	<code>\if_predicate:w &lt;predicate&gt; &lt;true code&gt; \else: &lt;false code&gt; \fi:</code>
--------------------------------	---

---

This function takes a predicate function and branches according to the result. (In practice this function would also accept a single boolean variable in place of the *<predicate>* but to make the coding clearer this should be done through `\if_bool:N`.)

---

<code>\if_bool:N</code> ★	<code>\if_bool:N &lt;boolean&gt; &lt;true code&gt; \else: &lt;false code&gt; \fi:</code>
---------------------------	--

---

This function takes a boolean variable and branches according to the result.

## 8 Internal programming functions

---

<code>\group_align_safe_begin:</code>	★
<code>\group_align_safe_end:</code>	★

---

Updated: 2011-08-11

---

`\group_align_safe_begin:`  
`...`  
`\group_align_safe_end:`

These functions are used to enclose material in a T<sub>E</sub>X alignment environment within a specially-constructed group. This group is designed in such a way that it does not add brace groups to the output but does act as a group for the `&` token inside `\halign`. This is necessary to allow grabbing of tokens for testing purposes, as T<sub>E</sub>X uses group level to determine the effect of alignment tokens. Without the special grouping, the use of a function such as `\peek_after:Nw` would result in a forbidden comparison of the internal `\endtemplate` token, yielding a fatal error. Each `\group_align_safe_begin:` must be matched by a `\group_align_safe_end:`, although this does not have to occur within the same function.

---

<code>\__prg_break_point:Nn</code>	★
------------------------------------	---

---

`\__prg_break_point:Nn \<type>_map_break: <tokens>`

Used to mark the end of a recursion or mapping: the functions `\<type>_map_break:` and `\<type>_map_break:n` use this to break out of the loop. After the loop ends, the *<tokens>* are inserted into the input stream. This occurs even if the break functions are *not* applied: `\__prg_break_point:Nn` is functionally-equivalent in these cases to `\use_ii:nn`.

---

<code>\__prg_map_break:Nn</code>	★
----------------------------------	---

---

`\__prg_map_break:Nn \<type>_map_break: {<user code>}`

`...`

`\__prg_break_point:Nn \<type>_map_break: {<ending code>}`

Breaks a recursion in mapping contexts, inserting in the input stream the *<user code>* after the *<ending code>* for the loop. The function breaks loops, inserting their *<ending code>*, until reaching a loop with the same *<type>* as its first argument. This `\<type>_map_break:` argument is simply used as a recognizable marker for the *<type>*.

---

<code>\g__prg_map_int</code>	
------------------------------	--

---

This integer is used by non-expandable mapping functions to track the level of nesting in force. The functions `\__prg_map_1:w`, `\__prg_map_2:w`, *etc.*, labelled by `\g__prg_map_int` hold functions to be mapped over various list datatypes in inline and variable mappings.

---

<code>\__prg_break_point:</code>	★
----------------------------------	---

---

This copy of `\prg_do_nothing:` is used to mark the end of a fast short-term recursion: the function `\__prg_break:n` uses this to break out of the loop.

---

<code>\__prg_break:</code>	★
<code>\__prg_break:n</code>	★

---

`\__prg_break:n {<tokens>} ... \__prg_break_point:`

Breaks a recursion which has no *<ending code>* and which is not a user-breakable mapping (see for instance `\prop_get:Nn`), and inserts *<tokens>* in the input stream.



## Part XIV

# The `l3clist` package

## Comma separated lists

Comma lists contain ordered data where items can be added to the left or right end of the list. The resulting ordered list can then be mapped over using `\clist_map_function:NN`. Several items can be added at once, and spaces are removed from both sides of each item on input. Hence,

```
\clist_new:N \l_my_clist
\clist_put_left:Nn \l_my_clist { ~ a ~ , ~ {b} ~ }
\clist_put_right:Nn \l_my_clist { ~ { c ~ } , d }
```

results in `\l_my_clist` containing `a,{b},{c~},d`. Comma lists cannot contain empty items, thus

```
\clist_clear_new:N \l_my_clist
\clist_put_right:Nn \l_my_clist { , ~ , , }
\clist_if_empty:NTF \l_my_clist { true } { false }
```

leaves `true` in the input stream. To include an item which contains a comma, or starts or ends with a space, surround it with braces. The sequence data type should be preferred to comma lists if items are to contain `{`, `}`, or `#` (assuming the usual  $\TeX$  category codes apply).

## 1 Creating and initialising comma lists

---

```
\clist_new:N
\clist_new:c
```

---

`\clist_new:N`  $\langle$ comma list $\rangle$

Creates a new  $\langle$ comma list $\rangle$  or raises an error if the name is already taken. The declaration is global. The  $\langle$ comma list $\rangle$  initially contains no items.

---

```
\clist_const:Nn
\clist_const:(Nx|cn|cx)
```

---

`\clist_const:Nn`  $\langle$ clist var $\rangle$   $\{\langle$ comma list $\rangle\}$

Creates a new constant  $\langle$ clist var $\rangle$  or raises an error if the name is already taken. The value of the  $\langle$ clist var $\rangle$  is set globally to the  $\langle$ comma list $\rangle$ .

New: 2014-07-05

---

```
\clist_clear:N
\clist_clear:c
\clist_gclear:N
\clist_gclear:c
```

---

`\clist_clear:N`  $\langle$ comma list $\rangle$

Clears all items from the  $\langle$ comma list $\rangle$ .

---

```
\clist_clear_new:N
\clist_clear_new:c
\clist_gclear_new:N
\clist_gclear_new:c
```

---

`\clist_clear_new:N`  $\langle$ comma list $\rangle$

Ensures that the  $\langle$ comma list $\rangle$  exists globally by applying `\clist_new:N` if necessary, then applies `\clist_(g)clear:N` to leave the list empty.

---

<code>\clist_set_eq:NN</code>	<code>\clist_set_eq:NN &lt;comma list<sub>1</sub>&gt; &lt;comma list<sub>2</sub>&gt;</code>
<code>\clist_set_eq:(cN Nc cc)</code>	Sets the content of <code>&lt;comma list<sub>1</sub>&gt;</code> equal to that of <code>&lt;comma list<sub>2</sub>&gt;</code> .
<code>\clist_gset_eq:NN</code>	
<code>\clist_gset_eq:(cN Nc cc)</code>	

---



---

<code>\clist_set_from_seq:NN</code>	<code>\clist_set_from_seq:NN &lt;comma list&gt; &lt;sequence&gt;</code>
<code>\clist_set_from_seq:(cN Nc cc)</code>	
<code>\clist_gset_from_seq:NN</code>	
<code>\clist_gset_from_seq:(cN Nc cc)</code>	

---

New: 2014-07-17

Converts the data in the `<sequence>` into a `<comma list>`: the original `<sequence>` is unchanged. Items which contain either spaces or commas are surrounded by braces.

---

<code>\clist_concat:NNN</code>	<code>\clist_concat:NNN &lt;comma list<sub>1</sub>&gt; &lt;comma list<sub>2</sub>&gt; &lt;comma list<sub>3</sub>&gt;</code>
<code>\clist_concat:ccc</code>	Concatenates the content of <code>&lt;comma list<sub>2</sub>&gt;</code> and <code>&lt;comma list<sub>3</sub>&gt;</code> together and saves the result in <code>&lt;comma list<sub>1</sub>&gt;</code> . The items in <code>&lt;comma list<sub>2</sub>&gt;</code> are placed at the left side of the new comma list.
<code>\clist_gconcat:NNN</code>	
<code>\clist_gconcat:ccc</code>	

---



---

<code>\clist_if_exist_p:N *</code>	<code>\clist_if_exist_p:N &lt;comma list&gt;</code>
<code>\clist_if_exist_p:c *</code>	<code>\clist_if_exist:NTF &lt;comma list&gt; {\true code} {\false code}</code>
<code>\clist_if_exist:NTF *</code>	Tests whether the <code>&lt;comma list&gt;</code> is currently defined. This does not check that the <code>&lt;comma list&gt;</code> really is a comma list.
<code>\clist_if_exist:cTF *</code>	

---

New: 2012-03-03

## 2 Adding data to comma lists

---

<code>\clist_set:Nn</code>	<code>\clist_set:Nn &lt;comma list&gt; {\&lt;item<sub>1</sub>&gt;, ..., &lt;item<sub>n</sub>&gt;}</code>
<code>\clist_set:(NV No Nx cn cV co cx)</code>	
<code>\clist_gset:Nn</code>	
<code>\clist_gset:(NV No Nx cn cV co cx)</code>	

---

New: 2011-09-06

Sets `<comma list>` to contain the `<items>`, removing any previous content from the variable. Spaces are removed from both sides of each item.

---

<code>\clist_put_left:Nn</code>	<code>\clist_put_left:Nn &lt;comma list&gt; {\&lt;item<sub>1</sub>&gt;, ..., &lt;item<sub>n</sub>&gt;}</code>
<code>\clist_put_left:(NV No Nx cn cV co cx)</code>	
<code>\clist_gput_left:Nn</code>	
<code>\clist_gput_left:(NV No Nx cn cV co cx)</code>	

---

Updated: 2011-09-05

Appends the `<items>` to the left of the `<comma list>`. Spaces are removed from both sides of each item.

---

<code>\clist_put_right:Nn</code>	<code>\clist_put_right:Nn &lt;comma list&gt; {\&lt;item_1&gt;, ..., \&lt;item_n&gt;}</code>
<code>\clist_put_right:(NV No Nx cn cV co cx)</code>	
<code>\clist_gput_right:Nn</code>	
<code>\clist_gput_right:(NV No Nx cn cV co cx)</code>	

---

Updated: 2011-09-05

Appends the  $\langle items \rangle$  to the right of the  $\langle comma list \rangle$ . Spaces are removed from both sides of each item.

### 3 Modifying comma lists

While comma lists are normally used as ordered lists, it may be necessary to modify the content. The functions here may be used to update comma lists, while retaining the order of the unaffected entries.

---

<code>\clist_remove_duplicates:N</code>	<code>\clist_remove_duplicates:N &lt;comma list&gt;</code>
<code>\clist_remove_duplicates:c</code>	
<code>\clist_gremove_duplicates:N</code>	
<code>\clist_gremove_duplicates:c</code>	

---

Removes duplicate items from the  $\langle comma list \rangle$ , leaving the left most copy of each item in the  $\langle comma list \rangle$ . The  $\langle item \rangle$  comparison takes place on a token basis, as for `\tl_if_eq:nn(TF)`.

**T<sub>E</sub>Xhackers note:** This function iterates through every item in the  $\langle comma list \rangle$  and does a comparison with the  $\langle items \rangle$  already checked. It is therefore relatively slow with large comma lists. Furthermore, it does not work if any of the items in the  $\langle comma list \rangle$  contains `{`, `}`, or `#` (assuming the usual T<sub>E</sub>X category codes apply).

---

<code>\clist_remove_all:Nn</code>	<code>\clist_remove_all:Nn &lt;comma list&gt; {\&lt;item&gt;}</code>
<code>\clist_remove_all:cn</code>	
<code>\clist_gremove_all:Nn</code>	
<code>\clist_gremove_all:cn</code>	

---

Updated: 2011-09-06

Removes every occurrence of  $\langle item \rangle$  from the  $\langle comma list \rangle$ . The  $\langle item \rangle$  comparison takes place on a token basis, as for `\tl_if_eq:nn(TF)`.

**T<sub>E</sub>Xhackers note:** The  $\langle item \rangle$  may not contain `{`, `}`, or `#` (assuming the usual T<sub>E</sub>X category codes apply).

---

<code>\clist_reverse:N</code>	<code>\clist_reverse:N &lt;comma list&gt;</code>
<code>\clist_reverse:c</code>	
<code>\clist_greverse:N</code>	
<code>\clist_greverse:c</code>	

---

New: 2014-07-18

Reverses the order of items stored in the  $\langle comma list \rangle$ .

---

<code>\clist_reverse:n</code>	<code>\clist_reverse:n {\&lt;comma list&gt;}</code>
-------------------------------	---

---

New: 2014-07-18

Leaves the items in the  $\langle comma list \rangle$  in the input stream in reverse order. Braces and spaces are preserved by this process.

**T<sub>E</sub>Xhackers note:** The result is returned within `\unexpanded`, which means that the comma list does not expand further when appearing in an x-type argument expansion.

---

<code>\clist_sort:Nn</code>	<code>\clist_sort:Nn &lt;clist var&gt; {&lt;comparison code&gt;}</code>
<code>\clist_sort:cn</code>	
<code>\clist_gsort:Nn</code>	Sorts the items in the <i>&lt;clist var&gt;</i> according to the <i>&lt;comparison code&gt;</i> , and assigns the result to <i>&lt;clist var&gt;</i> . The details of sorting comparison are described in Section 1.
<code>\clist_gsort:cn</code>	

---

New: 2017-02-06

---

## 4 Comma list conditionals

---

<code>\clist_if_empty_p:N</code> *	<code>\clist_if_empty_p:N &lt;comma list&gt;</code>
<code>\clist_if_empty_p:c</code> *	<code>\clist_if_empty:NtF &lt;comma list&gt; {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\clist_if_empty:NtF</code> *	Tests if the <i>&lt;comma list&gt;</i> is empty (containing no items).
<code>\clist_if_empty:cTf</code> *	

---



---

<code>\clist_if_empty_p:n</code> *	<code>\clist_if_empty_p:n {&lt;comma list&gt;}</code>
<code>\clist_if_empty:nTf</code> *	<code>\clist_if_empty:nTf {&lt;comma list&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>

---

New: 2014-07-05

---

Tests if the *<comma list>* is empty (containing no items). The rules for space trimming are as for other n-type comma-list functions, hence the comma list *{~,~,~}* (without outer braces) is empty, while *{~,{ },}* (without outer braces) contains one element, which happens to be empty: the comma-list is not empty.

---

<code>\clist_if_in:NnTf</code>	<code>\clist_if_in:NnTf &lt;comma list&gt; {&lt;item&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\clist_if_in:(NV No cn cV co)Tf</code>	
<code>\clist_if_in:nnTf</code>	
<code>\clist_if_in:(nV no)Tf</code>	

---

Updated: 2011-09-06

---

Tests if the *<item>* is present in the *<comma list>*. In the case of an n-type *<comma list>*, spaces are stripped from each item, but braces are not removed. Hence,

`\clist_if_in:nnTf { a , {b}~ , {b} , c } { b } {true} {false}`

yields false.

**TeXhackers note:** The *<item>* may not contain `{`, `}`, or `#` (assuming the usual TeX category codes apply), and should not contain `,` nor start or end with a space.

## 5 Mapping to comma lists

The functions described in this section apply a specified function to each item of a comma list.

When the comma list is given explicitly, as an n-type argument, spaces are trimmed around each item. If the result of trimming spaces is empty, the item is ignored. Otherwise, if the item is surrounded by braces, one set is removed, and the result is passed to the mapped function. Thus, if your comma list that is being mapped is *{a, {b}, { }, {c}, }* then the arguments passed to the mapped function are ‘a’, ‘{b}’, an empty argument, and ‘c’.

When the comma list is given as an N-type argument, spaces have already been trimmed on input, and items are simply stripped of one set of braces if any. This case is more efficient than using n-type comma lists.

---

<code>\clist_map_function:NN</code> ☆	<code>\clist_map_function:NN</code> $\langle comma\ list \rangle$ $\langle function \rangle$
<code>\clist_map_function:cN</code> ☆	
<code>\clist_map_function:nN</code> ☆	Applies $\langle function \rangle$ to every $\langle item \rangle$ stored in the $\langle comma\ list \rangle$ . The $\langle function \rangle$ receives one argument for each iteration. The $\langle items \rangle$ are returned from left to right. The function <code>\clist_map_inline:Nn</code> is in general more efficient than <code>\clist_map_function:NN</code> . One mapping may be nested inside another.
Updated: 2012-06-29	

---



---

<code>\clist_map_inline:Nn</code>	<code>\clist_map_inline:Nn</code> $\langle comma\ list \rangle$ $\{ \langle inline\ function \rangle \}$
<code>\clist_map_inline:cN</code>	
<code>\clist_map_inline:nn</code>	Applies $\langle inline\ function \rangle$ to every $\langle item \rangle$ stored within the $\langle comma\ list \rangle$ . The $\langle inline\ function \rangle$ should consist of code which receives the $\langle item \rangle$ as #1. One in line mapping can be nested inside another. The $\langle items \rangle$ are returned from left to right.
Updated: 2012-06-29	

---



---

<code>\clist_map_variable:NNn</code>	<code>\clist_map_variable:NNn</code> $\langle comma\ list \rangle$ $\langle tl\ var. \rangle$ $\{ \langle function\ using\ tl\ var. \rangle \}$
<code>\clist_map_variable:cNn</code>	
<code>\clist_map_variable:nNn</code>	Stores each entry in the $\langle comma\ list \rangle$ in turn in the $\langle tl\ var. \rangle$ and applies the $\langle function\ using\ tl\ var. \rangle$ . The $\langle function \rangle$ usually consists of code making use of the $\langle tl\ var. \rangle$ , but this is not enforced. One variable mapping can be nested inside another. The $\langle items \rangle$ are returned from left to right.
Updated: 2012-06-29	

---



---

<code>\clist_map_break:</code> ☆	<code>\clist_map_break:</code>
Updated: 2012-06-29	

---

Used to terminate a `\clist_map_...` function before all entries in the  $\langle comma\ list \rangle$  have been processed. This normally takes place within a conditional statement, for example

```
\clist_map_inline:Nn \l_my_clist
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \clist_map_break: }
  {
    % Do something useful
  }
}
```

Use outside of a `\clist_map_...` scenario leads to low level T<sub>E</sub>X errors.

**T<sub>E</sub>Xhackers note:** When the mapping is broken, additional tokens may be inserted by the internal macro `\__prg_break_point:Nn` before further items are taken from the input stream. This depends on the design of the mapping function.

---

`\clist_map_break:n` ☆

---

Updated: 2012-06-29

---

`\clist_map_break:n` {<tokens>}

Used to terminate a `\clist_map...` function before all entries in the <comma list> have been processed, inserting the <tokens> after the mapping has ended. This normally takes place within a conditional statement, for example

```
\clist_map_inline:Nn \l_my_clist
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \clist_map_break:n { <tokens> } }
  {
    % Do something useful
  }
}
```

Use outside of a `\clist_map...` scenario leads to low level T<sub>E</sub>X errors.

**T<sub>E</sub>Xhackers note:** When the mapping is broken, additional tokens may be inserted by the internal macro `\__prg_break_point:Nn` before the <tokens> are inserted into the input stream. This depends on the design of the mapping function.

---

`\clist_count:N` ☆

---

`\clist_count:c` ☆

`\clist_count:n` ☆

---

New: 2012-07-13

---

`\clist_count:N` <comma list>

Leaves the number of items in the <comma list> in the input stream as an <integer denotation>. The total number of items in a <comma list> includes those which are duplicates, *i.e.* every item in a <comma list> is unique.

## 6 Using the content of comma lists directly

---

`\clist_use:Nnnn` ☆

---

`\clist_use:cnnn` ☆

---

New: 2013-05-26

---

`\clist_use:Nnnn` <clist var> {<separator between two>}  
{<separator between more than two>} {<separator between final two>}

Places the contents of the <clist var> in the input stream, with the appropriate <separator> between the items. Namely, if the comma list has more than two items, the <separator between more than two> is placed between each pair of items except the last, for which the <separator between final two> is used. If the comma list has exactly two items, then they are placed in the input stream separated by the <separator between two>. If the comma list has a single item, it is placed in the input stream, and a comma list with no items produces no output. An error is raised if the variable does not exist or if it is invalid.

For example,

```
\clist_set:Nn \l_tmpa_clist { a , b , , c , {de} , f }
\clist_use:Nnnn \l_tmpa_clist { ~and~ } { ,~ } { ,~and~ }
```

inserts “a, b, c, de, and f” in the input stream. The first separator argument is not used in this case because the comma list has more than 2 items.

**T<sub>E</sub>Xhackers note:** The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the <items> do not expand further when appearing in an x-type argument expansion.

---

`\clist_use:Nn` ★

`\clist_use:cn` ★

---

New: 2013-05-26

---

`\clist_use:Nn`  $\langle\textit{clist var}\rangle$   $\{\langle\textit{separator}\rangle\}$

Places the contents of the  $\langle\textit{clist var}\rangle$  in the input stream, with the  $\langle\textit{separator}\rangle$  between the items. If the comma list has a single item, it is placed in the input stream, and a comma list with no items produces no output. An error is raised if the variable does not exist or if it is invalid.

For example,

```
\clist_set:Nn \l_tmpa_clist { a , b , , c , {de} , f }
\clist_use:Nn \l_tmpa_clist { ~and~ }
```

inserts “a and b and c and de and f” in the input stream.

**TeXhackers note:** The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the  $\langle\textit{items}\rangle$  do not expand further when appearing in an `x`-type argument expansion.

## 7 Comma lists as stacks

Comma lists can be used as stacks, where data is pushed to and popped from the top of the comma list. (The left of a comma list is the top, for performance reasons.) The stack functions for comma lists are not intended to be mixed with the general ordered data functions detailed in the previous section: a comma list should either be used as an ordered data type or as a stack, but not in both ways.

---

`\clist_get:NN`

`\clist_get:cN`

---

Updated: 2012-05-14

---

`\clist_get:NN`  $\langle\textit{comma list}\rangle$   $\langle\textit{token list variable}\rangle$

Stores the left-most item from a  $\langle\textit{comma list}\rangle$  in the  $\langle\textit{token list variable}\rangle$  without removing it from the  $\langle\textit{comma list}\rangle$ . The  $\langle\textit{token list variable}\rangle$  is assigned locally. If the  $\langle\textit{comma list}\rangle$  is empty the  $\langle\textit{token list variable}\rangle$  is set to the marker value `\q_no_value`.

---

`\clist_get:NNTF`

`\clist_get:cNTF`

---

New: 2012-05-14

---

`\clist_get:NNTF`  $\langle\textit{comma list}\rangle$   $\langle\textit{token list variable}\rangle$   $\{\langle\textit{true code}\rangle\}$   $\{\langle\textit{false code}\rangle\}$

If the  $\langle\textit{comma list}\rangle$  is empty, leaves the  $\langle\textit{false code}\rangle$  in the input stream. The value of the  $\langle\textit{token list variable}\rangle$  is not defined in this case and should not be relied upon. If the  $\langle\textit{comma list}\rangle$  is non-empty, stores the top item from the  $\langle\textit{comma list}\rangle$  in the  $\langle\textit{token list variable}\rangle$  without removing it from the  $\langle\textit{comma list}\rangle$ . The  $\langle\textit{token list variable}\rangle$  is assigned locally.

---

`\clist_pop:NN`

`\clist_pop:cN`

---

Updated: 2011-09-06

---

`\clist_pop:NN`  $\langle\textit{comma list}\rangle$   $\langle\textit{token list variable}\rangle$

Pops the left-most item from a  $\langle\textit{comma list}\rangle$  into the  $\langle\textit{token list variable}\rangle$ , *i.e.* removes the item from the comma list and stores it in the  $\langle\textit{token list variable}\rangle$ . Both of the variables are assigned locally.

---

`\clist_gpop:NN`

`\clist_gpop:cN`

---

`\clist_gpop:NN`  $\langle\textit{comma list}\rangle$   $\langle\textit{token list variable}\rangle$

Pops the left-most item from a  $\langle\textit{comma list}\rangle$  into the  $\langle\textit{token list variable}\rangle$ , *i.e.* removes the item from the comma list and stores it in the  $\langle\textit{token list variable}\rangle$ . The  $\langle\textit{comma list}\rangle$  is modified globally, while the assignment of the  $\langle\textit{token list variable}\rangle$  is local.

<code>\clist_pop:NNTF</code>	<code>\clist_pop:NNTF &lt;comma list&gt; &lt;token list variable&gt; {\true code} {\false code}</code>
<code>\clist_pop:cNTF</code>	If the <i>&lt;comma list&gt;</i> is empty, leaves the <i>&lt;false code&gt;</i> in the input stream. The value of the <i>&lt;token list variable&gt;</i> is not defined in this case and should not be relied upon. If the <i>&lt;comma list&gt;</i> is non-empty, pops the top item from the <i>&lt;comma list&gt;</i> in the <i>&lt;token list variable&gt;</i> , <i>i.e.</i> removes the item from the <i>&lt;comma list&gt;</i> . Both the <i>&lt;comma list&gt;</i> and the <i>&lt;token list variable&gt;</i> are assigned locally.
New: 2012-05-14	

<code>\clist_gpop:NNTF</code>	<code>\clist_gpop:NNTF &lt;comma list&gt; &lt;token list variable&gt; {\true code} {\false code}</code>
<code>\clist_gpop:cNTF</code>	If the <i>&lt;comma list&gt;</i> is empty, leaves the <i>&lt;false code&gt;</i> in the input stream. The value of the <i>&lt;token list variable&gt;</i> is not defined in this case and should not be relied upon. If the <i>&lt;comma list&gt;</i> is non-empty, pops the top item from the <i>&lt;comma list&gt;</i> in the <i>&lt;token list variable&gt;</i> , <i>i.e.</i> removes the item from the <i>&lt;comma list&gt;</i> . The <i>&lt;comma list&gt;</i> is modified globally, while the <i>&lt;token list variable&gt;</i> is assigned locally.
New: 2012-05-14	

<code>\clist_push:Nn</code>	<code>\clist_push:Nn &lt;comma list&gt; {\items}</code>
<code>\clist_push:(NV No Nx cn cV co cx)</code>	
<code>\clist_gpush:Nn</code>	
<code>\clist_gpush:(NV No Nx cn cV co cx)</code>	
Adds the <i>{\items}</i> to the top of the <i>&lt;comma list&gt;</i> . Spaces are removed from both sides of each item.	

## 8 Using a single item

<code>\clist_item:Nn</code> ★	<code>\clist_item:Nn &lt;comma list&gt; {\integer expression}</code>
<code>\clist_item:cn</code> ★	
<code>\clist_item:nn</code> ★	Indexing items in the <i>&lt;comma list&gt;</i> from 1 at the top (left), this function evaluates the <i>&lt;integer expression&gt;</i> and leaves the appropriate item from the comma list in the input stream. If the <i>&lt;integer expression&gt;</i> is negative, indexing occurs from the bottom (right) of the comma list. When the <i>&lt;integer expression&gt;</i> is larger than the number of items in the <i>&lt;comma list&gt;</i> (as calculated by <code>\clist_count:N</code> ) then the function expands to nothing.
New: 2014-07-17	

**TeXhackers note:** The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<item>* does not expand further when appearing in an *x*-type argument expansion.

## 9 Viewing comma lists

<code>\clist_show:N</code>	<code>\clist_show:N &lt;comma list&gt;</code>
<code>\clist_show:c</code>	Displays the entries in the <i>&lt;comma list&gt;</i> in the terminal.
Updated: 2015-08-03	
<code>\clist_show:n</code>	<code>\clist_show:n {\tokens}</code>
<code>\clist_show:n</code>	Displays the entries in the comma list in the terminal.
Updated: 2013-08-03	



<hr/> <code>\clist_log:N</code> <hr/>	<code>\clist_log:N</code> $\langle comma list \rangle$
<code>\clist_log:c</code> <hr/>	Writes the entries in the $\langle comma list \rangle$ in the log file. See also <code>\clist_show:N</code> which displays the result in the terminal.
New: 2014-08-22 Updated: 2015-08-03 <hr/>	

<hr/> <code>\clist_log:n</code> <hr/>	<code>\clist_log:n</code> $\{\langle tokens \rangle\}$
<code>\clist_log:n</code> <hr/>	Writes the entries in the comma list in the log file. See also <code>\clist_show:n</code> which displays the result in the terminal.
New: 2014-08-22 <hr/>	

## 10 Constant and scratch comma lists

<hr/> <code>\c_empty_clist</code> <hr/>	Constant that is always empty.
New: 2012-07-02 <hr/>	

<hr/> <code>\l_tmpa_clist</code> <hr/>	Scratch comma lists for local assignment. These are never used by the kernel code, and so are safe for use with any L <sup>A</sup> T <sub>E</sub> X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<code>\l_tmpb_clist</code> <hr/>	
New: 2011-09-06 <hr/>	

<code>\g_tmpa_clist</code>	Scratch comma lists for global assignment. These are never used by the kernel code, and so are safe for use with any L <sup>A</sup> T <sub>E</sub> X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<code>\g_tmpb_clist</code>	
New: 2011-09-06	

## Part XV

# The l3token package

## Token manipulation

This module deals with tokens. Now this is perhaps not the most precise description so let's try with a better description: When programming in T<sub>E</sub>X, it is often desirable to know just what a certain token is: is it a control sequence or something else. Similarly one often needs to know if a control sequence is expandable or not, a macro or a primitive, how many arguments it takes etc. Another thing of great importance (especially when it comes to document commands) is looking ahead in the token stream to see if a certain character is present and maybe even remove it or disregard other tokens while scanning. This module provides functions for both and as such has two primary function categories: `\token_` for anything that deals with tokens and `\peek_` for looking ahead in the token stream.

Most functions we describe here can be used on control sequences, as those are tokens as well.

It is important to distinguish two aspects of a token: its “shape” (for lack of a better word), which affects the matching of delimited arguments and the comparison of token lists containing this token, and its “meaning”, which affects whether the token expands or what operation it performs. One can have tokens of different shapes with the same meaning, but not the converse.

For instance, `\if:w`, `\if_charcode:w`, and `\tex_if:D` are three names for the same internal operation of T<sub>E</sub>X, namely the primitive testing the next two characters for equality of their character code. They have the same meaning hence behave identically in many situations. However, T<sub>E</sub>X distinguishes them when searching for a delimited argument. Namely, the example function `\show_until_if:w` defined below takes everything until `\if:w` as an argument, despite the presence of other copies of `\if:w` under different names.

```
\cs_new:Npn \show_until_if:w #1 \if:w { \tl_show:n {#1} }
\show_until_if:w \tex_if:D \if_charcode:w \if:w
```

A list of all possible shapes and a list of all possible meanings are given in section 8.

## 1 Creating character tokens

---

```
\char_set_active_eq:NN
\char_set_active_eq:Nc
\char_gset_active_eq:NN
\char_gset_active_eq:Nc
```

---

Updated: 2015-11-12

---

```
\char_set_active_eq:NN <char> <function>
```

Sets the behaviour of the `<char>` in situations where it is active (category code 13) to be equivalent to that of the `<function>`. The category code of the `<char>` is *unchanged* by this process. The `<function>` may itself be an active character.

---

```
\char_set_active_eq:nN
\char_set_active_eq:nc
\char_gset_active_eq:nN
\char_gset_active_eq:nc
```

---

New: 2015-11-12

---

```
\char_set_active_eq:nN {<integer expression>} <function>
```

Sets the behaviour of the `<char>` which has character code as given by the `<integer expression>` in situations where it is active (category code 13) to be equivalent to that of the `<function>`. The category code of the `<char>` is *unchanged* by this process. The `<function>` may itself be an active character.

---

`\char_generate:nn` ★

---

New: 2015-09-09

---

`\char_generate:nn` { $\langle charcode \rangle$ } { $\langle catcode \rangle$ }

Generates a character token of the given  $\langle charcode \rangle$  and  $\langle catcode \rangle$  (both of which may be integer expressions). The  $\langle catcode \rangle$  may be one of

- 1 (begin group)
- 2 (end group)
- 3 (math toggle)
- 4 (alignment)
- 6 (parameter)
- 7 (math superscript)
- 8 (math subscript)
- 11 (letter)
- 12 (other)

and other values raise an error.

The  $\langle charcode \rangle$  may be any one valid for the engine in use. Note however that for X<sub>Y</sub>TeX releases prior to 0.99992 only the 8-bit range (0 to 255) is accepted due to engine limitations.

## 2 Manipulating and interrogating character tokens

---

<code>\char_set_catcode_escape:N</code>	<code>\char_set_catcode_letter:N</code> { <i>character</i> }
<code>\char_set_catcode_group_begin:N</code>	
<code>\char_set_catcode_group_end:N</code>	
<code>\char_set_catcode_math_toggle:N</code>	
<code>\char_set_catcode_alignment:N</code>	
<code>\char_set_catcode_end_line:N</code>	
<code>\char_set_catcode_parameter:N</code>	
<code>\char_set_catcode_math_superscript:N</code>	
<code>\char_set_catcode_math_subscript:N</code>	
<code>\char_set_catcode_ignore:N</code>	
<code>\char_set_catcode_space:N</code>	
<code>\char_set_catcode_letter:N</code>	
<code>\char_set_catcode_other:N</code>	
<code>\char_set_catcode_active:N</code>	
<code>\char_set_catcode_comment:N</code>	
<code>\char_set_catcode_invalid:N</code>	

---

Updated: 2015-11-11

---

Sets the category code of the  $\langle character \rangle$  to that indicated in the function name. Depending on the current category code of the  $\langle token \rangle$  the escape token may also be needed:

`\char_set_catcode_other:N` %

The assignment is local.

---

<code>\char_set_catcode_escape:n</code>	<code>\char_set_catcode_letter:n {⟨integer expression⟩}</code>
<code>\char_set_catcode_group_begin:n</code>	
<code>\char_set_catcode_group_end:n</code>	
<code>\char_set_catcode_math_toggle:n</code>	
<code>\char_set_catcode_alignment:n</code>	
<code>\char_set_catcode_end_line:n</code>	
<code>\char_set_catcode_parameter:n</code>	
<code>\char_set_catcode_math_superscript:n</code>	
<code>\char_set_catcode_math_subscript:n</code>	
<code>\char_set_catcode_ignore:n</code>	
<code>\char_set_catcode_space:n</code>	
<code>\char_set_catcode_letter:n</code>	
<code>\char_set_catcode_other:n</code>	
<code>\char_set_catcode_active:n</code>	
<code>\char_set_catcode_comment:n</code>	
<code>\char_set_catcode_invalid:n</code>	

---

Updated: 2015-11-11

Sets the category code of the  $\langle character \rangle$  which has character code as given by the  $\langle integer expression \rangle$ . This version can be used to set up characters which cannot otherwise be given (*cf.* the N-type variants). The assignment is local.

---

<code>\char_set_catcode:nn</code>	<code>\char_set_catcode:nn {⟨intexpr<sub>1</sub>⟩} {⟨intexpr<sub>2</sub>⟩}</code>
-----------------------------------	---

---

Updated: 2015-11-11

These functions set the category code of the  $\langle character \rangle$  which has character code as given by the  $\langle integer expression \rangle$ . The first  $\langle integer expression \rangle$  is the character code and the second is the category code to apply. The setting applies within the current  $\text{\TeX}$  group. In general, the symbolic functions `\char_set_catcode_⟨type⟩` should be preferred, but there are cases where these lower-level functions may be useful.

---

<code>\char_value_catcode:n</code> ★	<code>\char_value_catcode:n {⟨integer expression⟩}</code>
--------------------------------------	---

---

Expands to the current category code of the  $\langle character \rangle$  with character code given by the  $\langle integer expression \rangle$ .

---

<code>\char_show_value_catcode:n</code>	<code>\char_show_value_catcode:n {⟨integer expression⟩}</code>
---	--

---

Displays the current category code of the  $\langle character \rangle$  with character code given by the  $\langle integer expression \rangle$  on the terminal.

---

<code>\char_set_lccode:nn</code>	<code>\char_set_lccode:nn {⟨intexpr<sub>1</sub>⟩} {⟨intexpr<sub>2</sub>⟩}</code>
----------------------------------	--

---

Updated: 2015-08-06

Sets up the behaviour of the  $\langle character \rangle$  when found inside `\tl_lower_case:n`, such that  $\langle character_1 \rangle$  will be converted into  $\langle character_2 \rangle$ . The two  $\langle characters \rangle$  may be specified using an  $\langle integer expression \rangle$  for the character code concerned. This may include the  $\text{\TeX}$  ‘ $\langle character \rangle$ ’ method for converting a single character into its character code:

```
\char_set_lccode:nn { ‘\A } { ‘\a } % Standard behaviour
\char_set_lccode:nn { ‘\A } { ‘\A + 32 }
\char_set_lccode:nn { 50 } { 60 }
```

The setting applies within the current  $\text{\TeX}$  group.

<hr/> <hr/>	<hr/>
<code>\char_value_lccode:n</code> ★	<code>\char_value_lccode:n {⟨integer expression⟩}</code>
	Expands to the current lower case code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$ .
<hr/> <hr/>	<hr/>
<code>\char_show_value_lccode:n</code>	<code>\char_show_value_lccode:n {⟨integer expression⟩}</code>
	Displays the current lower case code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$ on the terminal.
<hr/> <hr/>	<hr/>
<code>\char_set_uccode:nn</code>	<code>\char_set_uccode:nn {⟨intexpr<sub>1</sub>⟩} {⟨intexpr<sub>2</sub>⟩}</code>
Updated: 2015-08-06	Sets up the behaviour of the $\langle character \rangle$ when found inside <code>\tl_upper_case:n</code> , such that $\langle character_1 \rangle$ will be converted into $\langle character_2 \rangle$ . The two $\langle characters \rangle$ may be specified using an $\langle integer expression \rangle$ for the character code concerned. This may include the T <sub>E</sub> X ‘ $\langle character \rangle$ ’ method for converting a single character into its character code:
	<pre> \char_set_uccode:nn { ‘\a } { ‘\A } % Standard behaviour \char_set_uccode:nn { ‘\A } { ‘\A - 32 } \char_set_uccode:nn { 60 } { 50 } </pre>
	The setting applies within the current T <sub>E</sub> X group.
<hr/> <hr/>	<hr/>
<code>\char_value_uccode:n</code> ★	<code>\char_value_uccode:n {⟨integer expression⟩}</code>
	Expands to the current upper case code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$ .
<hr/> <hr/>	<hr/>
<code>\char_show_value_uccode:n</code>	<code>\char_show_value_uccode:n {⟨integer expression⟩}</code>
	Displays the current upper case code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$ on the terminal.
<hr/> <hr/>	<hr/>
<code>\char_set_mathcode:nn</code>	<code>\char_set_mathcode:nn {⟨intexpr<sub>1</sub>⟩} {⟨intexpr<sub>2</sub>⟩}</code>
Updated: 2015-08-06	This function sets up the math code of $\langle character \rangle$ . The $\langle character \rangle$ is specified as an $\langle integer expression \rangle$ which will be used as the character code of the relevant character. The setting applies within the current T <sub>E</sub> X group.
<hr/> <hr/>	<hr/>
<code>\char_value_mathcode:n</code> ★	<code>\char_value_mathcode:n {⟨integer expression⟩}</code>
	Expands to the current math code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$ .
<hr/> <hr/>	<hr/>
<code>\char_show_value_mathcode:n</code>	<code>\char_show_value_mathcode:n {⟨integer expression⟩}</code>
	Displays the current math code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$ on the terminal.
<hr/> <hr/>	<hr/>
<code>\char_set_sfcode:nn</code>	<code>\char_set_sfcode:nn {⟨intexpr<sub>1</sub>⟩} {⟨intexpr<sub>2</sub>⟩}</code>
Updated: 2015-08-06	This function sets up the space factor for the $\langle character \rangle$ . The $\langle character \rangle$ is specified as an $\langle integer expression \rangle$ which will be used as the character code of the relevant character. The setting applies within the current T <sub>E</sub> X group.

<hr/> <code>\char_value_sfcode:n</code> ★ <hr/>	<code>\char_value_sfcode:n {⟨integer expression⟩}</code> Expands to the current space factor for the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$ .
<hr/> <code>\char_show_value_sfcode:n</code> <hr/>	<code>\char_show_value_sfcode:n {⟨integer expression⟩}</code> Displays the current space factor for the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$ on the terminal.
<hr/> <code>\l_char_active_seq</code> New: 2012-01-23 Updated: 2015-11-11 <hr/>	Used to track which tokens may require special handling at the document level as they are (or have been at some point) of category $\langle active \rangle$ (catcode 13). Each entry in the sequence consists of a single escaped token, for example <code>\~</code> . Active tokens should be added to the sequence when they are defined for general document use.
<hr/> <code>\l_char_special_seq</code> New: 2012-01-23 Updated: 2015-11-11 <hr/>	Used to track which tokens will require special handling when working with verbatim-like material at the document level as they are not of categories $\langle letter \rangle$ (catcode 11) or $\langle other \rangle$ (catcode 12). Each entry in the sequence consists of a single escaped token, for example <code>\</code> for the backslash or <code>\{</code> for an opening brace. Escaped tokens should be added to the sequence when they are defined for general document use.

### 3 Generic tokens

<hr/> <code>\token_new:Nn</code> <hr/>	<code>\token_new:Nn ⟨token<sub>1</sub>⟩ {⟨token<sub>2</sub>⟩}</code> Defines $\langle token_1 \rangle$ to globally be a snapshot of $\langle token_2 \rangle$ . This is an implicit representation of $\langle token_2 \rangle$ .
<hr/> <code>\c_group_begin_token</code> <code>\c_group_end_token</code> <code>\c_math_toggle_token</code> <code>\c_alignment_token</code> <code>\c_parameter_token</code> <code>\c_math_superscript_token</code> <code>\c_math_subscript_token</code> <code>\c_space_token</code> <hr/>	These are implicit tokens which have the category code described by their name. They are used internally for test purposes but are also available to the programmer for other uses.
<hr/> <code>\c_catcode_letter_token</code> <code>\c_catcode_other_token</code> <hr/>	These are implicit tokens which have the category code described by their name. They are used internally for test purposes and should not be used other than for category code tests.
<hr/> <code>\c_catcode_active_tl</code> <hr/>	A token list containing an active token. This is used internally for test purposes and should not be used other than in appropriately-constructed category code tests.

## 4 Converting tokens

---

<code>\token_to_meaning:N</code>	★	<code>\token_to_meaning:N &lt;token&gt;</code>
<code>\token_to_meaning:c</code>	★	

---

Inserts the current meaning of the  $\langle token \rangle$  into the input stream as a series of characters of category code 12 (other). This is the primitive  $\text{\TeX}$  description of the  $\langle token \rangle$ , thus for example both functions defined by `\cs_set_nopar:Npn` and token list variables defined using `\tl_new:N` are described as macros.

**$\text{\TeX}$ hackers note:** This is the  $\text{\TeX}$  primitive `\meaning`.

---

<code>\token_to_str:N</code>	★	<code>\token_to_str:N &lt;token&gt;</code>
<code>\token_to_str:c</code>	★	

---

Converts the given  $\langle token \rangle$  into a series of characters with category code 12 (other). If the  $\langle token \rangle$  is a control sequence, this will start with the current escape character with category code 12 (the escape character is part of the  $\langle token \rangle$ ). This function requires only a single expansion.

**$\text{\TeX}$ hackers note:** `\token_to_str:N` is the  $\text{\TeX}$  primitive `\string` renamed.

## 5 Token conditionals

---

<code>\token_if_group_begin_p:N</code>	★	<code>\token_if_group_begin_p:N &lt;token&gt;</code>
<code>\token_if_group_begin:NTF</code>	★	<code>\token_if_group_begin:NTF &lt;token&gt; {\true code} {\false code}</code>

---

Tests if  $\langle token \rangle$  has the category code of a begin group token (`{` when normal  $\text{\TeX}$  category codes are in force). Note that an explicit begin group token cannot be tested in this way, as it is not a valid N-type argument.

---

<code>\token_if_group_end_p:N</code>	★	<code>\token_if_group_end_p:N &lt;token&gt;</code>
<code>\token_if_group_end:NTF</code>	★	<code>\token_if_group_end:NTF &lt;token&gt; {\true code} {\false code}</code>

---

Tests if  $\langle token \rangle$  has the category code of an end group token (`}` when normal  $\text{\TeX}$  category codes are in force). Note that an explicit end group token cannot be tested in this way, as it is not a valid N-type argument.

---

<code>\token_if_math_toggle_p:N</code>	★	<code>\token_if_math_toggle_p:N &lt;token&gt;</code>
<code>\token_if_math_toggle:NTF</code>	★	<code>\token_if_math_toggle:NTF &lt;token&gt; {\true code} {\false code}</code>

---

Tests if  $\langle token \rangle$  has the category code of a math shift token (`$` when normal  $\text{\TeX}$  category codes are in force).

---

<code>\token_if_alignment_p:N</code>	★	<code>\token_if_alignment_p:N &lt;token&gt;</code>
<code>\token_if_alignment:NTF</code>	★	<code>\token_if_alignment:NTF &lt;token&gt; {\true code} {\false code}</code>

---

Tests if  $\langle token \rangle$  has the category code of an alignment token (`&` when normal  $\text{\TeX}$  category codes are in force).

---

<code>\token_if_parameter_p:N</code>	★	<code>\token_if_parameter_p:N</code>	$\langle token \rangle$
<code>\token_if_parameter:NTF</code>	★	<code>\token_if_alignment:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

---

Tests if  $\langle token \rangle$  has the category code of a macro parameter token (# when normal T<sub>E</sub>X category codes are in force).

---

<code>\token_if_math_superscript_p:N</code>	★	<code>\token_if_math_superscript_p:N</code>	$\langle token \rangle$
<code>\token_if_math_superscript:NTF</code>	★	<code>\token_if_math_superscript:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

---

Tests if  $\langle token \rangle$  has the category code of a superscript token (^ when normal T<sub>E</sub>X category codes are in force).

---

<code>\token_if_math_subscript_p:N</code>	★	<code>\token_if_math_subscript_p:N</code>	$\langle token \rangle$
<code>\token_if_math_subscript:NTF</code>	★	<code>\token_if_math_subscript:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

---

Tests if  $\langle token \rangle$  has the category code of a subscript token (\_ when normal T<sub>E</sub>X category codes are in force).

---

<code>\token_if_space_p:N</code>	★	<code>\token_if_space_p:N</code>	$\langle token \rangle$
<code>\token_if_space:NTF</code>	★	<code>\token_if_space:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

---

Tests if  $\langle token \rangle$  has the category code of a space token. Note that an explicit space token with character code 32 cannot be tested in this way, as it is not a valid N-type argument.

---

<code>\token_if_letter_p:N</code>	★	<code>\token_if_letter_p:N</code>	$\langle token \rangle$
<code>\token_if_letter:NTF</code>	★	<code>\token_if_letter:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

---

Tests if  $\langle token \rangle$  has the category code of a letter token.

---

<code>\token_if_other_p:N</code>	★	<code>\token_if_other_p:N</code>	$\langle token \rangle$
<code>\token_if_other:NTF</code>	★	<code>\token_if_other:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

---

Tests if  $\langle token \rangle$  has the category code of an “other” token.

---

<code>\token_if_active_p:N</code>	★	<code>\token_if_active_p:N</code>	$\langle token \rangle$
<code>\token_if_active:NTF</code>	★	<code>\token_if_active:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

---

Tests if  $\langle token \rangle$  has the category code of an active character.

---

<code>\token_if_eq_catcode_p:NN</code>	★	<code>\token_if_eq_catcode_p:NN</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$
<code>\token_if_eq_catcode:NNTF</code>	★	<code>\token_if_eq_catcode:NNTF</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

---

Tests if the two  $\langle tokens \rangle$  have the same category code.

---

<code>\token_if_eq_charcode_p:NN</code>	★	<code>\token_if_eq_charcode_p:NN</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$
<code>\token_if_eq_charcode:NNTF</code>	★	<code>\token_if_eq_charcode:NNTF</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

---

Tests if the two  $\langle tokens \rangle$  have the same character code.

---

<code>\token_if_eq_meaning_p:NN</code>	★	<code>\token_if_eq_meaning_p:NN</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$
<code>\token_if_eq_meaning:NNTF</code>	★	<code>\token_if_eq_meaning:NNTF</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

---

Tests if the two  $\langle tokens \rangle$  have the same meaning when expanded.



---

<code>\token_if_macro_p:N</code>	★	<code>\token_if_macro_p:N &lt;token&gt;</code>
<code>\token_if_macro:NTF</code>	★	<code>\token_if_macro:NTF &lt;token&gt; {\true code} {\false code}</code>

---

Updated: 2011-05-23 Tests if the  $\langle token \rangle$  is a  $\text{\TeX}$  macro.

---



---

<code>\token_if_cs_p:N</code>	★	<code>\token_if_cs_p:N &lt;token&gt;</code>
<code>\token_if_cs:NTF</code>	★	<code>\token_if_cs:NTF &lt;token&gt; {\true code} {\false code}</code>

---

Tests if the  $\langle token \rangle$  is a control sequence.

---



---

<code>\token_if_expandable_p:N</code>	★	<code>\token_if_expandable_p:N &lt;token&gt;</code>
<code>\token_if_expandable:NTF</code>	★	<code>\token_if_expandable:NTF &lt;token&gt; {\true code} {\false code}</code>

---

Tests if the  $\langle token \rangle$  is expandable. This test returns  $\langle false \rangle$  for an undefined token.

---



---

<code>\token_if_long_macro_p:N</code>	★	<code>\token_if_long_macro_p:N &lt;token&gt;</code>
<code>\token_if_long_macro:NTF</code>	★	<code>\token_if_long_macro:NTF &lt;token&gt; {\true code} {\false code}</code>

---

Updated: 2012-01-20 Tests if the  $\langle token \rangle$  is a long macro.

---



---

<code>\token_if_protected_macro_p:N</code>	★	<code>\token_if_protected_macro_p:N &lt;token&gt;</code>
<code>\token_if_protected_macro:NTF</code>	★	<code>\token_if_protected_macro:NTF &lt;token&gt; {\true code} {\false code}</code>

---

Updated: 2012-01-20

---

Tests if the  $\langle token \rangle$  is a protected macro: for a macro which is both protected and long this returns  $\langle false \rangle$ .

---



---

<code>\token_if_protected_long_macro_p:N</code>	★	<code>\token_if_protected_long_macro_p:N &lt;token&gt;</code>
<code>\token_if_protected_long_macro:NTF</code>	★	<code>\token_if_protected_long_macro:NTF &lt;token&gt; {\true code} {\false code}</code>

---

Updated: 2012-01-20

---

Tests if the  $\langle token \rangle$  is a protected long macro.

---



---

<code>\token_if_chardef_p:N</code>	★	<code>\token_if_chardef_p:N &lt;token&gt;</code>
<code>\token_if_chardef:NTF</code>	★	<code>\token_if_chardef:NTF &lt;token&gt; {\true code} {\false code}</code>

---

Updated: 2012-01-20 Tests if the  $\langle token \rangle$  is defined to be a chardef.

---

**$\text{\TeX}$ hackers note:** Booleans, boxes and small integer constants are implemented as  $\backslash$ chardefs.

---



---

<code>\token_if_mathchardef_p:N</code>	★	<code>\token_if_mathchardef_p:N &lt;token&gt;</code>
<code>\token_if_mathchardef:NTF</code>	★	<code>\token_if_mathchardef:NTF &lt;token&gt; {\true code} {\false code}</code>

---

Updated: 2012-01-20

---

Tests if the  $\langle token \rangle$  is defined to be a mathchardef.

---



---

<code>\token_if_dim_register_p:N</code>	★	<code>\token_if_dim_register_p:N &lt;token&gt;</code>
<code>\token_if_dim_register:NTF</code>	★	<code>\token_if_dim_register:NTF &lt;token&gt; {\true code} {\false code}</code>

---

Updated: 2012-01-20

---

Tests if the  $\langle token \rangle$  is defined to be a dimension register.

---

---

```
\token_if_int_register_p:N ★ \token_if_int_register_p:N <token>
\token_if_int_register:NTF ★ \token_if_int_register:NTF <token> {\true code} {\false code}
```

---

Updated: 2012-01-20

---

Tests if the  $\langle token \rangle$  is defined to be a integer register.

**T<sub>E</sub>Xhackers note:** Constant integers may be implemented as integer registers, `\chardefs`, or `\mathchardefs` depending on their value.

---

```
\token_if_muskip_register_p:N ★ \token_if_muskip_register_p:N <token>
\token_if_muskip_register:NTF ★ \token_if_muskip_register:NTF <token> {\true code} {\false code}
```

---

New: 2012-02-15

---

Tests if the  $\langle token \rangle$  is defined to be a muskip register.

---

```
\token_if_skip_register_p:N ★ \token_if_skip_register_p:N <token>
\token_if_skip_register:NTF ★ \token_if_skip_register:NTF <token> {\true code} {\false code}
```

---

Updated: 2012-01-20

---

Tests if the  $\langle token \rangle$  is defined to be a skip register.

---

```
\token_if_toks_register_p:N ★ \token_if_toks_register_p:N <token>
\token_if_toks_register:NTF ★ \token_if_toks_register:NTF <token> {\true code} {\false code}
```

---

Updated: 2012-01-20

---

Tests if the  $\langle token \rangle$  is defined to be a toks register (not used by L<sup>A</sup>T<sub>E</sub>X3).

---

```
\token_if_primitive_p:N ★ \token_if_primitive_p:N <token>
\token_if_primitive:NTF ★ \token_if_primitive:NTF <token> {\true code} {\false code}
```

---

Updated: 2011-05-23

---

Tests if the  $\langle token \rangle$  is an engine primitive.

## 6 Peeking ahead at the next token

There is often a need to look ahead at the next token in the input stream while leaving it in place. This is handled using the “peek” functions. The generic `\peek_after:Nw` is provided along with a family of predefined tests for common cases. As peeking ahead does *not* skip spaces the predefined tests include both a space-respecting and space-skipping version.

---

```
\peek_after:Nw \peek_after:Nw <function> <token>
```

---

Locally sets the test variable `\l_peek_token` equal to  $\langle token \rangle$  (as an implicit token, *not* as a token list), and then expands the  $\langle function \rangle$ . The  $\langle token \rangle$  remains in the input stream as the next item after the  $\langle function \rangle$ . The  $\langle token \rangle$  here may be `␣`, `{` or `}` (assuming normal T<sub>E</sub>X category codes), *i.e.* it is not necessarily the next argument which would be grabbed by a normal function.

---

**\peek\_gafter:Nw****\peek\_gafter:Nw**  $\langle function \rangle$   $\langle token \rangle$ 

Globally sets the test variable `\g_peek_token` equal to  $\langle token \rangle$  (as an implicit token, *not* as a token list), and then expands the  $\langle function \rangle$ . The  $\langle token \rangle$  remains in the input stream as the next item after the  $\langle function \rangle$ . The  $\langle token \rangle$  here may be  $\sqcup$ ,  $\{$  or  $\}$  (assuming normal  $\text{\TeX}$  category codes), *i.e.* it is not necessarily the next argument which would be grabbed by a normal function.

---

**\l\_peek\_token**Token set by `\peek_after:Nw` and available for testing as described above.

---

**\g\_peek\_token**Token set by `\peek_gafter:Nw` and available for testing as described above.

---

**\peek\_catcode:NTF****\peek\_catcode:NTF**  $\langle test\ token \rangle$   $\{\langle true\ code \rangle\}$   $\{\langle false\ code \rangle\}$ 

---

Updated: 2012-12-20

Tests if the next  $\langle token \rangle$  in the input stream has the same category code as the  $\langle test\ token \rangle$  (as defined by the test `\token_if_eq_catcode:NNTF`). Spaces are respected by the test and the  $\langle token \rangle$  is left in the input stream after the  $\langle true\ code \rangle$  or  $\langle false\ code \rangle$  (as appropriate to the result of the test).

---

**\peek\_catcode\_ignore\_spaces:NTF****\peek\_catcode\_ignore\_spaces:NTF**  $\langle test\ token \rangle$   $\{\langle true\ code \rangle\}$   $\{\langle false\ code \rangle\}$ 

---

Updated: 2012-12-20

Tests if the next non-space  $\langle token \rangle$  in the input stream has the same category code as the  $\langle test\ token \rangle$  (as defined by the test `\token_if_eq_catcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the  $\langle token \rangle$  is left in the input stream after the  $\langle true\ code \rangle$  or  $\langle false\ code \rangle$  (as appropriate to the result of the test).

---

**\peek\_catcode\_remove:NTF****\peek\_catcode\_remove:NTF**  $\langle test\ token \rangle$   $\{\langle true\ code \rangle\}$   $\{\langle false\ code \rangle\}$ 

---

Updated: 2012-12-20

Tests if the next  $\langle token \rangle$  in the input stream has the same category code as the  $\langle test\ token \rangle$  (as defined by the test `\token_if_eq_catcode:NNTF`). Spaces are respected by the test and the  $\langle token \rangle$  is removed from the input stream if the test is true. The function then places either the  $\langle true\ code \rangle$  or  $\langle false\ code \rangle$  in the input stream (as appropriate to the result of the test).

---

**\peek\_catcode\_remove\_ignore\_spaces:NTF****\peek\_catcode\_remove\_ignore\_spaces:NTF**  $\langle test\ token \rangle$   $\{\langle true\ code \rangle\}$   $\{\langle false\ code \rangle\}$ 

---

Updated: 2012-12-20

Tests if the next non-space  $\langle token \rangle$  in the input stream has the same category code as the  $\langle test\ token \rangle$  (as defined by the test `\token_if_eq_catcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the  $\langle token \rangle$  is removed from the input stream if the test is true. The function then places either the  $\langle true\ code \rangle$  or  $\langle false\ code \rangle$  in the input stream (as appropriate to the result of the test).

---

**\peek\_charcode:NTF****\peek\_charcode:NTF**  $\langle test\ token \rangle$   $\{\langle true\ code \rangle\}$   $\{\langle false\ code \rangle\}$ 

---

Updated: 2012-12-20

Tests if the next  $\langle token \rangle$  in the input stream has the same character code as the  $\langle test\ token \rangle$  (as defined by the test `\token_if_eq_charcode:NNTF`). Spaces are respected by the test and the  $\langle token \rangle$  is left in the input stream after the  $\langle true\ code \rangle$  or  $\langle false\ code \rangle$  (as appropriate to the result of the test).

---

<u>\peek_charcode_ignore_spaces:NTF</u>	\peek_charcode_ignore_spaces:NTF <i>&lt;test token&gt;</i> <i>{&lt;true code&gt;}</i> <i>{&lt;false code&gt;}</i>
---	---

---

Updated: 2012-12-20

Tests if the next non-space *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

---

<u>\peek_charcode_remove:NTF</u>	\peek_charcode_remove:NTF <i>&lt;test token&gt;</i> <i>{&lt;true code&gt;}</i> <i>{&lt;false code&gt;}</i>
----------------------------------	--

---

Updated: 2012-12-20

Tests if the next *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Spaces are respected by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

---

<u>\peek_charcode_remove_ignore_spaces:NTF</u>	\peek_charcode_remove_ignore_spaces:NTF <i>&lt;test token&gt;</i> <i>{&lt;true code&gt;}</i> <i>{&lt;false code&gt;}</i>
--	--

---

Updated: 2012-12-20

Tests if the next non-space *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

---

<u>\peek_meaning:NTF</u>	\peek_meaning:NTF <i>&lt;test token&gt;</i> <i>{&lt;true code&gt;}</i> <i>{&lt;false code&gt;}</i>
--------------------------	--

---

Updated: 2011-07-02

Tests if the next *<token>* in the input stream has the same meaning as the *<test token>* (as defined by the test `\token_if_eq_meaning:NNTF`). Spaces are respected by the test and the *<token>* is left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

---

<u>\peek_meaning_ignore_spaces:NTF</u>	\peek_meaning_ignore_spaces:NTF <i>&lt;test token&gt;</i> <i>{&lt;true code&gt;}</i> <i>{&lt;false code&gt;}</i>
--	--

---

Updated: 2012-12-05

Tests if the next non-space *<token>* in the input stream has the same meaning as the *<test token>* (as defined by the test `\token_if_eq_meaning:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

---

<u>\peek_meaning_remove:NTF</u>	\peek_meaning_remove:NTF <i>&lt;test token&gt;</i> <i>{&lt;true code&gt;}</i> <i>{&lt;false code&gt;}</i>
---------------------------------	---

---

Updated: 2011-07-02

Tests if the next *<token>* in the input stream has the same meaning as the *<test token>* (as defined by the test `\token_if_eq_meaning:NNTF`). Spaces are respected by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

---

<code>\peek_meaning_remove_ignore_spaces:NTF</code>	<code>\peek_meaning_remove_ignore_spaces:NTF &lt;test token&gt;</code>
	<code>{&lt;true code&gt;} {&lt;false code&gt;}</code>

---

Updated: 2012-12-05

Tests if the next non-space  $\langle token \rangle$  in the input stream has the same meaning as the  $\langle test token \rangle$  (as defined by the test `\token_if_eq_meaning:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the  $\langle token \rangle$  is removed from the input stream if the test is true. The function then places either the  $\langle true code \rangle$  or  $\langle false code \rangle$  in the input stream (as appropriate to the result of the test).

## 7 Decomposing a macro definition

These functions decompose T<sub>E</sub>X macros into their constituent parts: if the  $\langle token \rangle$  passed is not a macro then no decomposition can occur. In the later case, all three functions leave `\scan_stop:` in the input stream.

---

<code>\token_get_arg_spec:N</code> ★	<code>\token_get_arg_spec:N &lt;token&gt;</code>
--------------------------------------	--

---

If the  $\langle token \rangle$  is a macro, this function leaves the primitive T<sub>E</sub>X argument specification in input stream as a string of tokens of category code 12 (with spaces having category code 10). Thus for example for a token `\next` defined by

`\cs_set:Npn \next #1#2 { x #1 y #2 }`

leaves `#1#2` in the input stream. If the  $\langle token \rangle$  is not a macro then `\scan_stop:` is left in the input stream.

**T<sub>E</sub>Xhackers note:** If the arg spec. contains the string `->`, then the `spec` function produces incorrect results.

---

<code>\token_get_replacement_spec:N</code> ★	<code>\token_get_replacement_spec:N &lt;token&gt;</code>
--	--

---

If the  $\langle token \rangle$  is a macro, this function leaves the replacement text in input stream as a string of tokens of category code 12 (with spaces having category code 10). Thus for example for a token `\next` defined by

`\cs_set:Npn \next #1#2 { x #1~y #2 }`

leaves `x#1 y#2` in the input stream. If the  $\langle token \rangle$  is not a macro then `\scan_stop:` is left in the input stream.

**T<sub>E</sub>Xhackers note:** If the arg spec. contains the string `->`, then the `spec` function produces incorrect results.

---

`\token_get_prefix_spec:N` ★

---

`\token_get_prefix_spec:N`  $\langle token \rangle$

If the  $\langle token \rangle$  is a macro, this function leaves the  $\text{\TeX}$  prefixes applicable in input stream as a string of tokens of category code 12 (with spaces having category code 10). Thus for example for a token `\next` defined by

```
\cs_set:Npn \next #1#2 { x #1~y #2 }
```

leaves `\long` in the input stream. If the  $\langle token \rangle$  is not a macro then `\scan_stop:` is left in the input stream

## 8 Description of all possible tokens

Let us end by reviewing every case that a given token can fall into. This section is quite technical and some details are only meant for completeness. We distinguish the meaning of the token, which controls the expansion of the token and its effect on  $\text{\TeX}$ 's state, and its shape, which is used when comparing token lists such as for delimited arguments. Two tokens of the same shape must have the same meaning, but the converse does not hold.

A token has one of the following shapes.

- A control sequence, characterized by the sequence of characters that constitute its name: for instance, `\use:n` is a five-letter control sequence.
- An active character token, characterized by its character code (between 0 and 1114111 for  $\text{\LuaTeX}$  and  $\text{\XeTeX}$  and less for other engines) and category code 13.
- A character token, characterized by its character code and category code (one of 1, 2, 3, 4, 6, 7, 8, 10, 11 or 12 whose meaning is described below).<sup>4</sup>

There are also a few internal tokens. The following list may be incomplete in some engines.

- Expanding `\the\font` results in a token that looks identical to the command that was used to select the current font (such as `\tenrm`) but it differs from it in shape.
- A “frozen” `\relax`, which differs from the primitive in shape (but has the same meaning), is inserted when the closing `\fi` of a conditional is encountered before the conditional is evaluated.
- Expanding `\noexpand`  $\langle token \rangle$  (when the  $\langle token \rangle$  is expandable) results in an internal token, displayed (temporarily) as `\notexpanded:  $\langle token \rangle$` , whose shape coincides with the  $\langle token \rangle$  and whose meaning differs from `\relax`.
- An `\outer endtemplate:` (expanding to another internal token, `end of alignment template`) can be encountered when peeking ahead at the next token.
- Tricky programming might access a frozen `\endwrite`.
- Some frozen tokens can only be accessed in interactive sessions: `\cr`, `\right`, `\endgroup`, `\fi`, `\inaccessible`.

---

<sup>4</sup>In  $\text{\LuaTeX}$ , there is also the case of “bytes”, which behave as character tokens of category code 12 (other) and character code between 1114112 and 1114366. They are used to output individual bytes to files, rather than UTF-8.

The meaning of a (non-active) character token is fixed by its category code (and character code) and cannot be changed. We call these tokens *explicit* character tokens. Category codes that a character token can have are listed below by giving a sample output of the  $\TeX$  primitive `\meaning`, together with their  $\LaTeX$ 3 names and most common example:

- 1 begin-group character (`group_begin`, often `{`),
- 2 end-group character (`group_end`, often `}`),
- 3 math shift character (`math_toggle`, often `$`),
- 4 alignment tab character (`alignment`, often `&`),
- 6 macro parameter character (`parameter`, often `#`),
- 7 superscript character (`math_superscript`, often `^`),
- 8 subscript character (`math_subscript`, often `_`),
- 10 blank space (`space`, often character code 32),
- 11 the letter (`letter`, such as `A`),
- 12 the character (`other`, such as `0`).

Category code 13 (`active`) is discussed below. Input characters can also have several other category codes which do not lead to character tokens for later processing: 0 (`escape`), 5 (`end_line`), 9 (`ignore`), 14 (`comment`), and 15 (`invalid`).

The meaning of a control sequence or active character can be identical to that of any character token listed above (with any character code), and we call such tokens *implicit* character tokens. The meaning is otherwise in the following list:

- a macro, used in  $\LaTeX$ 3 for most functions and some variables (`tl`, `fp`, `seq`, ...),
- a primitive such as `\def` or `\topmark`, used in  $\LaTeX$ 3 for some functions,
- a register such as `\count123`, used in  $\LaTeX$ 3 for the implementation of some variables (`int`, `dim`, ...),
- a constant integer such as `\char"56` or `\mathchar"121`,
- a font selection command,
- undefined.

Macros be `\protected` or not, `\long` or not (the opposite of what  $\LaTeX$ 3 calls `nopar`), and `\outer` or not (unused in  $\LaTeX$ 3). Their `\meaning` takes the form

$\langle properties \rangle$  **macro**:  $\langle parameters \rangle \rightarrow \langle replacement \rangle$

where  $\langle properties \rangle$  is among `\protected\long\outer`,  $\langle parameters \rangle$  describes parameters that the macro expects, such as `#1#2#3`, and  $\langle replacement \rangle$  describes how the parameters are manipulated, such as `#2/#1/#3`.

Now is perhaps a good time to mention some subtleties relating to tokens with category code 10 (space). Any input character with this category code (normally, space and tab characters) becomes a normal space, with character code 32 and category code 10.

When a macro takes an undelimited argument, explicit space characters (with character code 32 and category code 10) are ignored. If the following token is an explicit character token with category code 1 (begin-group) and an arbitrary character code, then  $\text{\TeX}$  scans ahead to obtain an equal number of explicit character tokens with category code 1 (begin-group) and 2 (end-group), and the resulting list of tokens (with outer braces removed) becomes the argument. Otherwise, a single token is taken as the argument for the macro: we call such single tokens “N-type”, as they are suitable to be used as an argument for a function with the signature `:N`.

## 9 Internal functions

---

`\_char_generate:nn` ★

---

New: 2016-03-25

---

`\_char_generate:nn`  $\{\langle charcode \rangle\}$   $\{\langle catcode \rangle\}$

This function is identical in operation to the public `\char_generate:nn` but omits various sanity tests. In particular, this means it is used in certain places where engine variations need to be accounted for by the kernel. The  $\langle catcode \rangle$  must give an explicit integer after a single expansion.



## Part XVI

# The l3prop package

## Property lists

L<sup>A</sup>T<sub>E</sub>X3 implements a “property list” data type, which contain an unordered list of entries each of which consists of a  $\langle key \rangle$  and an associated  $\langle value \rangle$ . The  $\langle key \rangle$  and  $\langle value \rangle$  may both be any  $\langle balanced\ text \rangle$ . It is possible to map functions to property lists such that the function is applied to every key–value pair within the list.

Each entry in a property list must have a unique  $\langle key \rangle$ : if an entry is added to a property list which already contains the  $\langle key \rangle$  then the new entry overwrites the existing one. The  $\langle keys \rangle$  are compared on a string basis, using the same method as `\str_if_eq:nn`.

Property lists are intended for storing key-based information for use within code. This is in contrast to key–value lists, which are a form of *input* parsed by the `keys` module.

### 1 Creating and initialising property lists

---

```
\prop_new:N
\prop_new:c
```

---

```
\prop_new:N <property list>
```

Creates a new  $\langle property\ list \rangle$  or raises an error if the name is already taken. The declaration is global. The  $\langle property\ list \rangle$  initially contains no entries.

---

```
\prop_clear:N
\prop_clear:c
\prop_gclear:N
\prop_gclear:c
```

---

```
\prop_clear:N <property list>
```

Clears all entries from the  $\langle property\ list \rangle$ .

---

```
\prop_clear_new:N
\prop_clear_new:c
\prop_gclear_new:N
\prop_gclear_new:c
```

---

```
\prop_clear_new:N <property list>
```

Ensures that the  $\langle property\ list \rangle$  exists globally by applying `\prop_new:N` if necessary, then applies `\prop_(g)clear:N` to leave the list empty.

---

```
\prop_set_eq:NN
\prop_set_eq:(cN|Nc|cc)
\prop_gset_eq:NN
\prop_gset_eq:(cN|Nc|cc)
```

---

```
\prop_set_eq:NN <property list1> <property list2>
```

Sets the content of  $\langle property\ list_1 \rangle$  equal to that of  $\langle property\ list_2 \rangle$ .

## 2 Adding entries to property lists

---

<code>\prop_put:Nnn</code> <code>\prop_put: (NnV Nno Nnx NVn NVV Non Noo cnn cnV cno cnx cVn cVV con coo)</code> <code>\prop_gput:Nnn</code> <code>\prop_gput: (NnV Nno Nnx NVn NVV Non Noo cnn cnV cno cnx cVn cVV con coo)</code>	<code>\prop_put:Nnn &lt;property list&gt;</code> <code>{&lt;key&gt;} {&lt;value&gt;}</code>
--	--

---

Updated: 2012-07-09

Adds an entry to the *<property list>* which may be accessed using the *<key>* and which has *<value>*. Both the *<key>* and *<value>* may contain any *<balanced text>*. The *<key>* is stored after processing with `\tl_to_str:n`, meaning that category codes are ignored. If the *<key>* is already present in the *<property list>*, the existing entry is overwritten by the new *<value>*.

---

<code>\prop_put_if_new:Nnn</code> <code>\prop_put_if_new:cnn</code> <code>\prop_gput_if_new:Nnn</code> <code>\prop_gput_if_new:cnn</code>	<code>\prop_put_if_new:Nnn &lt;property list&gt; {&lt;key&gt;} {&lt;value&gt;}</code>
--	---

---

If the *<key>* is present in the *<property list>* then no action is taken. If the *<key>* is not present in the *<property list>* then a new entry is added. Both the *<key>* and *<value>* may contain any *<balanced text>*. The *<key>* is stored after processing with `\tl_to_str:n`, meaning that category codes are ignored.

## 3 Recovering values from property lists

---

<code>\prop_get:NnN</code> <code>\prop_get: (NVN NoN cnN cVN coN)</code>	<code>\prop_get:NnN &lt;property list&gt; {&lt;key&gt;} &lt;tl var&gt;</code>
---	---

---

Updated: 2011-08-28

Recovers the *<value>* stored with *<key>* from the *<property list>*, and places this in the *<token list variable>*. If the *<key>* is not found in the *<property list>* then the *<token list variable>* is set to the special marker `\q_no_value`. The *<token list variable>* is set within the current TeX group. See also `\prop_get:NnNTF`.

---

<code>\prop_pop:NnN</code> <code>\prop_pop: (NoN cnN coN)</code>	<code>\prop_pop:NnN &lt;property list&gt; {&lt;key&gt;} &lt;tl var&gt;</code>
---	---

---

Updated: 2011-08-18

Recovers the *<value>* stored with *<key>* from the *<property list>*, and places this in the *<token list variable>*. If the *<key>* is not found in the *<property list>* then the *<token list variable>* is set to the special marker `\q_no_value`. The *<key>* and *<value>* are then deleted from the property list. Both assignments are local. See also `\prop_pop:NnNTF`.

---

<code>\prop_gpop:NnN</code> <code>\prop_gpop: (NoN cnN coN)</code>	<code>\prop_gpop:NnN &lt;property list&gt; {&lt;key&gt;} &lt;tl var&gt;</code>
---	--

---

Updated: 2011-08-18

Recovers the *<value>* stored with *<key>* from the *<property list>*, and places this in the *<token list variable>*. If the *<key>* is not found in the *<property list>* then the *<token list variable>* is set to the special marker `\q_no_value`. The *<key>* and *<value>* are then deleted from the property list. The *<property list>* is modified globally, while the assignment of the *<token list variable>* is local. See also `\prop_gpop:NnNTF`.

---

<code>\prop_item:Nn</code> ★	<code>\prop_item:Nn</code> $\langle property list \rangle$ $\{\langle key \rangle\}$
------------------------------	--

---

<code>\prop_item:cn</code> ★
------------------------------

---

New: 2014-07-17

---

Expands to the  $\langle value \rangle$  corresponding to the  $\langle key \rangle$  in the  $\langle property list \rangle$ . If the  $\langle key \rangle$  is missing, this has an empty expansion.

**TeXhackers note:** This function is slower than the non-expandable analogue `\prop_get:NnN`. The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the  $\langle value \rangle$  does not expand further when appearing in an x-type argument expansion.

## 4 Modifying property lists

---

<code>\prop_remove:Nn</code>
------------------------------

---

<code>\prop_remove:(NV cn cV)</code>
--------------------------------------

---

<code>\prop_gremove:Nn</code>
-------------------------------

---

<code>\prop_gremove:(NV cn cV)</code>
---------------------------------------

---

New: 2012-05-12

---

<code>\prop_remove:Nn</code> $\langle property list \rangle$ $\{\langle key \rangle\}$
--

---

Removes the entry listed under  $\langle key \rangle$  from the  $\langle property list \rangle$ . If the  $\langle key \rangle$  is not found in the  $\langle property list \rangle$  no change occurs, *i.e* there is no need to test for the existence of a key before deleting it.

## 5 Property list conditionals

---

<code>\prop_if_exist_p:N</code> ★
-----------------------------------

---

<code>\prop_if_exist_p:c</code> ★
-----------------------------------

---

<code>\prop_if_exist:NTF</code> ★
-----------------------------------

---

<code>\prop_if_exist:cTF</code> ★
-----------------------------------

---

New: 2012-03-03

---

<code>\prop_if_exist_p:N</code> $\langle property list \rangle$
---

---

<code>\prop_if_exist:NTF</code> $\langle property list \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$
--

---

Tests whether the  $\langle property list \rangle$  is currently defined. This does not check that the  $\langle property list \rangle$  really is a property list variable.

---

<code>\prop_if_empty_p:N</code> ★
-----------------------------------

---

<code>\prop_if_empty_p:c</code> ★
-----------------------------------

---

<code>\prop_if_empty:NTF</code> ★
-----------------------------------

---

<code>\prop_if_empty:cTF</code> ★
-----------------------------------

---

<code>\prop_if_empty_p:N</code> $\langle property list \rangle$
---

---

<code>\prop_if_empty:NTF</code> $\langle property list \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$
--

---

Tests if the  $\langle property list \rangle$  is empty (containing no entries).

---

<code>\prop_if_in_p:Nn</code>	★	<code>\prop_if_in:NnTF</code> $\langle property list \rangle$ $\{\langle key \rangle\}$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$
-------------------------------	---	--

---

<code>\prop_if_in_p:(NV No cn cV co)</code>	★
---	---

---

<code>\prop_if_in:NnTF</code>	★
-------------------------------	---

---

<code>\prop_if_in:(NV No cn cV co)TF</code>	★
---	---

---

Updated: 2011-09-15

---

Tests if the  $\langle key \rangle$  is present in the  $\langle property list \rangle$ , making the comparison using the method described by `\str_if_eq:nnTF`.

**TeXhackers note:** This function iterates through every key–value pair in the  $\langle property list \rangle$  and is therefore slower than using the non-expandable `\prop_get:NnNTF`.

## 6 Recovering values from property lists with branching

The functions in this section combine tests for the presence of a key in a property list with recovery of the associated valued. This makes them useful for cases where different cases follow dependent on the presence or absence of a key in a property list. They offer increased readability and performance over separate testing and recovery phases.

<u>\prop_get:NnNTF</u>	<u>\prop_get:NnNTF</u> $\langle \text{property list} \rangle$ $\{\langle \text{key} \rangle\}$ $\langle \text{token list variable} \rangle$
<u>\prop_get:(NVN NoN cnN cVN coN)TF</u>	<u>\prop_get:(NVN NoN cnN cVN coN)TF</u> $\{\langle \text{true code} \rangle\}$ $\{\langle \text{false code} \rangle\}$
Updated: 2012-05-19	

If the  $\langle \text{key} \rangle$  is not present in the  $\langle \text{property list} \rangle$ , leaves the  $\langle \text{false code} \rangle$  in the input stream. The value of the  $\langle \text{token list variable} \rangle$  is not defined in this case and should not be relied upon. If the  $\langle \text{key} \rangle$  is present in the  $\langle \text{property list} \rangle$ , stores the corresponding  $\langle \text{value} \rangle$  in the  $\langle \text{token list variable} \rangle$  without removing it from the  $\langle \text{property list} \rangle$ , then leaves the  $\langle \text{true code} \rangle$  in the input stream. The  $\langle \text{token list variable} \rangle$  is assigned locally.

<u>\prop_pop:NnNTF</u>	<u>\prop_pop:NnNTF</u> $\langle \text{property list} \rangle$ $\{\langle \text{key} \rangle\}$ $\langle \text{token list variable} \rangle$ $\{\langle \text{true code} \rangle\}$
<u>\prop_pop:cnNTF</u>	<u>\prop_pop:cnNTF</u> $\{\langle \text{false code} \rangle\}$
New: 2011-08-18	If the $\langle \text{key} \rangle$ is not present in the $\langle \text{property list} \rangle$ , leaves the $\langle \text{false code} \rangle$ in the input stream. The value of the $\langle \text{token list variable} \rangle$ is not defined in this case and should not be relied upon. If the $\langle \text{key} \rangle$ is present in the $\langle \text{property list} \rangle$ , pops the corresponding $\langle \text{value} \rangle$ in the $\langle \text{token list variable} \rangle$ , <i>i.e.</i> removes the item from the $\langle \text{property list} \rangle$ . Both the $\langle \text{property list} \rangle$ and the $\langle \text{token list variable} \rangle$ are assigned locally.
Updated: 2012-05-19	

<u>\prop_gpop:NnNTF</u>	<u>\prop_gpop:NnNTF</u> $\langle \text{property list} \rangle$ $\{\langle \text{key} \rangle\}$ $\langle \text{token list variable} \rangle$ $\{\langle \text{true code} \rangle\}$
<u>\prop_gpop:cnNTF</u>	<u>\prop_gpop:cnNTF</u> $\{\langle \text{false code} \rangle\}$
New: 2011-08-18	If the $\langle \text{key} \rangle$ is not present in the $\langle \text{property list} \rangle$ , leaves the $\langle \text{false code} \rangle$ in the input stream. The value of the $\langle \text{token list variable} \rangle$ is not defined in this case and should not be relied upon. If the $\langle \text{key} \rangle$ is present in the $\langle \text{property list} \rangle$ , pops the corresponding $\langle \text{value} \rangle$ in the $\langle \text{token list variable} \rangle$ , <i>i.e.</i> removes the item from the $\langle \text{property list} \rangle$ . The $\langle \text{property list} \rangle$ is modified globally, while the $\langle \text{token list variable} \rangle$ is assigned locally.
Updated: 2012-05-19	

## 7 Mapping to property lists

<u>\prop_map_function:NN</u> ☆	<u>\prop_map_function:NN</u> $\langle \text{property list} \rangle$ $\langle \text{function} \rangle$
<u>\prop_map_function:cN</u> ☆	Applies $\langle \text{function} \rangle$ to every $\langle \text{entry} \rangle$ stored in the $\langle \text{property list} \rangle$ . The $\langle \text{function} \rangle$ receives two argument for each iteration: the $\langle \text{key} \rangle$ and associated $\langle \text{value} \rangle$ . The order in which $\langle \text{entries} \rangle$ are returned is not defined and should not be relied upon.
Updated: 2013-01-28	

<u>\prop_map_inline:Nn</u>	<u>\prop_map_inline:Nn</u> $\langle \text{property list} \rangle$ $\{\langle \text{inline function} \rangle\}$
<u>\prop_map_inline:cn</u>	Applies $\langle \text{inline function} \rangle$ to every $\langle \text{entry} \rangle$ stored within the $\langle \text{property list} \rangle$ . The $\langle \text{inline function} \rangle$ should consist of code which receives the $\langle \text{key} \rangle$ as #1 and the $\langle \text{value} \rangle$ as #2. The order in which $\langle \text{entries} \rangle$ are returned is not defined and should not be relied upon.
Updated: 2013-01-08	

---

**\prop\_map\_break:** ☆

---

Updated: 2012-06-29

---

**\prop\_map\_break:**

Used to terminate a `\prop_map...` function before all entries in the *⟨property list⟩* have been processed. This normally takes place within a conditional statement, for example

```
\prop_map_inline:Nn \l_my_prop
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \prop_map_break: }
  {
    % Do something useful
  }
}
```

Use outside of a `\prop_map...` scenario leads to low level T<sub>E</sub>X errors.

---

**\prop\_map\_break:n** ☆

---

Updated: 2012-06-29

---

**\prop\_map\_break:n** {*⟨tokens⟩*}

Used to terminate a `\prop_map...` function before all entries in the *⟨property list⟩* have been processed, inserting the *⟨tokens⟩* after the mapping has ended. This normally takes place within a conditional statement, for example

```
\prop_map_inline:Nn \l_my_prop
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \prop_map_break:n { <tokens> } }
  {
    % Do something useful
  }
}
```

Use outside of a `\prop_map...` scenario leads to low level T<sub>E</sub>X errors.

## 8 Viewing property lists

---

**\prop\_show:N****\prop\_show:c**

---

Updated: 2015-08-01

---

**\prop\_show:N** *⟨property list⟩*

Displays the entries in the *⟨property list⟩* in the terminal.

---

**\prop\_log:N****\prop\_log:c**

---

New: 2014-08-12

---

Updated: 2015-08-01

---

**\prop\_log:N** *⟨property list⟩*

Writes the entries in the *⟨property list⟩* in the log file.

## 9 Scratch property lists

<u>\l_tmpa_prop</u>	Scratch property lists for local assignment. These are never used by the kernel code, and so are safe for use with any L <sup>A</sup> T <sub>E</sub> X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<u>\l_tmpb_prop</u>	
New: 2012-06-23	

<u>\g_tmpa_prop</u>	Scratch property lists for global assignment. These are never used by the kernel code, and so are safe for use with any L <sup>A</sup> T <sub>E</sub> X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<u>\g_tmpb_prop</u>	
New: 2012-06-23	

## 10 Constants

<u>\c_empty_prop</u>	A permanently-empty property list used for internal comparisons.
----------------------	--

## 11 Internal property list functions

<u>\s__prop</u>	The internal token used at the beginning of property lists. This is also used after each $\langle key \rangle$ (see \__prop_pair:wn).
-----------------	---

<u>\__prop_pair:wn</u>	<u>\__prop_pair:wn</u> $\langle key \rangle$ \s__prop $\{ \langle item \rangle \}$
	The internal token used to begin each key–value pair in the property list. If expanded outside of a mapping or manipulation function, an error is raised. The definition should always be set globally.

<u>\l_prop_internal_tl</u>	Token list used to store new key–value pairs to be inserted by functions of the \prop_put:Nnn family.
----------------------------	---

<u>\__prop_split:NnTF</u>	<u>\__prop_split:NnTF</u> $\langle property\ list \rangle$ $\{ \langle key \rangle \}$ $\{ \langle true\ code \rangle \}$ $\{ \langle false\ code \rangle \}$
Updated: 2013-01-08	Splits the $\langle property\ list \rangle$ at the $\langle key \rangle$ , giving three token lists: the $\langle extract \rangle$ of $\langle property\ list \rangle$ before the $\langle key \rangle$ , the $\langle value \rangle$ associated with the $\langle key \rangle$ and the $\langle extract \rangle$ of the $\langle property\ list \rangle$ after the $\langle value \rangle$ . Both $\langle extracts \rangle$ retain the internal structure of a property list, and the concatenation of the two $\langle extracts \rangle$ is a property list. If the $\langle key \rangle$ is present in the $\langle property\ list \rangle$ then the $\langle true\ code \rangle$ is left in the input stream, with #1, #2, and #3 replaced by the first $\langle extract \rangle$ , the $\langle value \rangle$ , and the second $\langle extract \rangle$ . If the $\langle key \rangle$ is not present in the $\langle property\ list \rangle$ then the $\langle false\ code \rangle$ is left in the input stream, with no trailing material. Both $\langle true\ code \rangle$ and $\langle false\ code \rangle$ are used in the replacement text of a macro defined internally, hence macro parameter characters should be doubled, except #1, #2, and #3 which stand in the $\langle true\ code \rangle$ for the three extracts from the property list. The $\langle key \rangle$ comparison takes place as described for \str_if_eq:nn.

## Part XVII

# The l3msg package

## Messages

Messages need to be passed to the user by modules, either when errors occur or to indicate how the code is proceeding. The `l3msg` module provides a consistent method for doing this (as opposed to writing directly to the terminal or log).

The system used by `l3msg` to create messages divides the process into two distinct parts. Named messages are created in the first part of the process; at this stage, no decision is made about the type of output that the message will produce. The second part of the process is actually producing a message. At this stage a choice of message *class* has to be made, for example `error`, `warning` or `info`.

By separating out the creation and use of messages, several benefits are available. First, the messages can be altered later without needing details of where they are used in the code. This makes it possible to alter the language used, the detail level and so on. Secondly, the output which results from a given message can be altered. This can be done on a message class, module or message name basis. In this way, message behaviour can be altered and messages can be entirely suppressed.

### 1 Creating new messages

All messages have to be created before they can be used. The text of messages is automatically wrapped to the length available in the console. As a result, formatting is only needed where it helps to show meaning. In particular, `\\` may be used to force a new line and `\_` forces an explicit space. Additionally, `\{`, `\#`, `\}`, `\%` and `\~` can be used to produce the corresponding character.

Messages may be subdivided *by one level* using the `/` character. This is used within the message filtering system to allow for example the L<sup>A</sup>T<sub>E</sub>X kernel messages to belong to the module `LaTeX` while still being filterable at a more granular level. Thus for example

```
\msg_new:nnnn { mymodule } { submodule / message } ...
```

will allow to filter out specifically messages from the `submodule`.

---

```
\msg_new:nnnn
\msg_new:nnn
```

---

Updated: 2011-08-16

---

```
\msg_new:nnnn {<module>} {<message>} {<text>} {<more text>}
```

Creates a *<message>* for a given *<module>*. The message is defined to first give *<text>* and then *<more text>* if the user requests it. If no *<more text>* is available then a standard text is given instead. Within *<text>* and *<more text>* four parameters (**#1** to **#4**) can be used: these will be supplied at the time the message is used. An error is raised if the *<message>* already exists.

---

```
\msg_set:nnnn
\msg_set:nnn
\msg_gset:nnnn
\msg_gset:nnn
```

---

```
\msg_set:nnnn {<module>} {<message>} {<text>} {<more text>}
```

Sets up the text for a *<message>* for a given *<module>*. The message is defined to first give *<text>* and then *<more text>* if the user requests it. If no *<more text>* is available then a standard text is given instead. Within *<text>* and *<more text>* four parameters (**#1** to **#4**) can be used: these will be supplied at the time the message is used.

---

<code>\msg_if_exist_p:nn</code> ★	<code>\msg_if_exist_p:nn {&lt;module&gt;} {&lt;message&gt;}</code>
<code>\msg_if_exist:nnTF</code> ★	<code>\msg_if_exist:nnTF {&lt;module&gt;} {&lt;message&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>

---

New: 2012-03-03

Tests whether the *<message>* for the *<module>* is currently defined.

## 2 Contextual information for messages

---

<code>\msg_line_context:</code> ☆	<code>\msg_line_context:</code>
-----------------------------------	---------------------------------

---

Prints the current line number when a message is given, and thus suitable for giving context to messages. The number itself is proceeded by the text `on line`.

---

<code>\msg_line_number:</code> ★	<code>\msg_line_number:</code>
----------------------------------	--------------------------------

---

Prints the current line number when a message is given.

---

<code>\msg_fatal_text:n</code> ★	<code>\msg_fatal_text:n {&lt;module&gt;}</code>
----------------------------------	---

---

Produces the standard text

**Fatal *<module>* error**

This function can be redefined to alter the language in which the message is given, using #1 as the name of the *<module>* to be included.

---

<code>\msg_critical_text:n</code> ★	<code>\msg_critical_text:n {&lt;module&gt;}</code>
-------------------------------------	--

---

Produces the standard text

**Critical *<module>* error**

This function can be redefined to alter the language in which the message is given, using #1 as the name of the *<module>* to be included.

---

<code>\msg_error_text:n</code> ★	<code>\msg_error_text:n {&lt;module&gt;}</code>
----------------------------------	---

---

Produces the standard text

***<module>* error**

This function can be redefined to alter the language in which the message is given, using #1 as the name of the *<module>* to be included.

---

<code>\msg_warning_text:n</code> ★	<code>\msg_warning_text:n {&lt;module&gt;}</code>
------------------------------------	---

---

Produces the standard text

***<module>* warning**

This function can be redefined to alter the language in which the message is given, using #1 as the name of the *<module>* to be included.



---

`\msg_info_text:n` ★ `\msg_info_text:n {<module>}`

---

Produces the standard text:

`<module>` info

This function can be redefined to alter the language in which the message is given, using #1 as the name of the `<module>` to be included.

---

`\msg_see_documentation_text:n` ★ `\msg_see_documentation_text:n {<module>}`

---

Produces the standard text

See the `<module>` documentation for further information.

This function can be redefined to alter the language in which the message is given, using #1 as the name of the `<module>` to be included.

### 3 Issuing messages

Messages behave differently depending on the message class. In all cases, the message may be issued supplying 0 to 4 arguments. If the number of arguments supplied here does not match the number in the definition of the message, extra arguments are ignored, or empty arguments added (of course the sense of the message may be impaired). The four arguments are converted to strings before being added to the message text: the x-type variants should be used to expand material.

---

`\msg_fatal:nnnnnn` `\msg_fatal:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}`  
`\msg_fatal:nnxxxx`  
`\msg_fatal:nnnnn` Issues `<module>` error `<message>`, passing `<arg one>` to `<arg four>` to the text-creating  
`\msg_fatal:nnxxx` functions. After issuing a fatal error the `TEX` run halts.  
`\msg_fatal:nnnn`  
`\msg_fatal:nnxx`  
`\msg_fatal:nnn`  
`\msg_fatal:nnx`  
`\msg_fatal:nn`

---

Updated: 2012-08-11

---

`\msg_critical:nnnnnn` `\msg_critical:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}`  
`\msg_critical:nnxxxx`

`\msg_critical:nnnnn` Issues `<module>` error `<message>`, passing `<arg one>` to `<arg four>` to the text-creating  
`\msg_critical:nnxxx` functions. After issuing a critical error, `TEX` stops reading the current input file. This  
`\msg_critical:nnnn` may halt the `TEX` run (if the current file is the main file) or may abort reading a sub-file.  
`\msg_critical:nnxx`

`\msg_critical:nnn`  
`\msg_critical:nnx`  
`\msg_critical:nn`

---

Updated: 2012-08-11

---

<code>\msg_error:nnnnnn</code>	<code>\msg_error:nnnnnn {&lt;module&gt;} {&lt;message&gt;} {&lt;arg one&gt;} {&lt;arg two&gt;} {&lt;arg three&gt;} {&lt;arg four&gt;}</code>
<code>\msg_error:nnxxxx</code>	
<code>\msg_error:nnnnn</code>	Issues <i>&lt;module&gt;</i> error <i>&lt;message&gt;</i> , passing <i>&lt;arg one&gt;</i> to <i>&lt;arg four&gt;</i> to the text-creating functions. The error interrupts processing and issues the text at the terminal. After user input, the run continues.
<code>\msg_error:nnxxx</code>	
<code>\msg_error:nnnn</code>	
<code>\msg_error:nnxx</code>	
<code>\msg_error:nnn</code>	
<code>\msg_error:nnx</code>	
<code>\msg_error:nn</code>	

---

Updated: 2012-08-11

---



---

<code>\msg_warning:nnnnnn</code>	<code>\msg_warning:nnxxxx {&lt;module&gt;} {&lt;message&gt;} {&lt;arg one&gt;} {&lt;arg two&gt;} {&lt;arg three&gt;} {&lt;arg four&gt;}</code>
<code>\msg_warning:nnxxxx</code>	
<code>\msg_warning:nnnnn</code>	Issues <i>&lt;module&gt;</i> warning <i>&lt;message&gt;</i> , passing <i>&lt;arg one&gt;</i> to <i>&lt;arg four&gt;</i> to the text-creating functions. The warning text is added to the log file and the terminal, but the $\TeX$ run is not interrupted.
<code>\msg_warning:nnxxx</code>	
<code>\msg_warning:nnnn</code>	
<code>\msg_warning:nnxx</code>	
<code>\msg_warning:nnn</code>	
<code>\msg_warning:nnx</code>	
<code>\msg_warning:nn</code>	

---

Updated: 2012-08-11

---



---

<code>\msg_info:nnnnnn</code>	<code>\msg_info:nnnnnn {&lt;module&gt;} {&lt;message&gt;} {&lt;arg one&gt;} {&lt;arg two&gt;} {&lt;arg three&gt;} {&lt;arg four&gt;}</code>
<code>\msg_info:nnxxxx</code>	
<code>\msg_info:nnnnn</code>	Issues <i>&lt;module&gt;</i> information <i>&lt;message&gt;</i> , passing <i>&lt;arg one&gt;</i> to <i>&lt;arg four&gt;</i> to the text-creating functions. The information text is added to the log file.
<code>\msg_info:nnxxx</code>	
<code>\msg_info:nnnn</code>	
<code>\msg_info:nnxx</code>	
<code>\msg_info:nnn</code>	
<code>\msg_info:nnx</code>	
<code>\msg_info:nn</code>	

---

Updated: 2012-08-11

---



---

<code>\msg_log:nnnnnn</code>	<code>\msg_log:nnnnnn {&lt;module&gt;} {&lt;message&gt;} {&lt;arg one&gt;} {&lt;arg two&gt;} {&lt;arg three&gt;} {&lt;arg four&gt;}</code>
<code>\msg_log:nnxxxx</code>	
<code>\msg_log:nnnnn</code>	Issues <i>&lt;module&gt;</i> information <i>&lt;message&gt;</i> , passing <i>&lt;arg one&gt;</i> to <i>&lt;arg four&gt;</i> to the text-creating functions. The information text is added to the log file: the output is briefer than <code>\msg_info:nnnnnn</code> .
<code>\msg_log:nnxxx</code>	
<code>\msg_log:nnnn</code>	
<code>\msg_log:nnxx</code>	
<code>\msg_log:nnn</code>	
<code>\msg_log:nnx</code>	
<code>\msg_log:nn</code>	

---

Updated: 2012-08-11

---

---

<pre> \msg_none:nnnnnn \msg_none:nnxxxx \msg_none:nnnnn \msg_none:nnxxx \msg_none:nnnn \msg_none:nnxx \msg_none:nnn \msg_none:nnx \msg_none:nn </pre>	<pre> \msg_none:nnnnnn {&lt;module&gt;} {&lt;message&gt;} {&lt;arg one&gt;} {&lt;arg two&gt;} {&lt;arg three&gt;} {&lt;arg four&gt;}} </pre> <p>Does nothing: used as a message class to prevent any output at all (see the discussion of message redirection).</p>
---	---

---

Updated: 2012-08-11

---

## 4 Redirecting messages

Each message has a “name”, which can be used to alter the behaviour of the message when it is given. Thus we might have

```
\msg_new:nnnn { module } { my-message } { Some-text } { Some-more-text }
```

to define a message, with

```
\msg_error:nn { module } { my-message }
```

when it is used. With no filtering, this raises an error. However, we could alter the behaviour with

```
\msg_redirect_class:nn { error } { warning }
```

to turn all errors into warnings, or with

```
\msg_redirect_module:nnn { module } { error } { warning }
```

to alter only messages from that module, or even

```
\msg_redirect_name:nnn { module } { my-message } { warning }
```

to target just one message. Redirection applies first to individual messages, then to messages from one module and finally to messages of one class. Thus it is possible to select out an individual message for special treatment even if the entire class is already redirected.

Multiple redirections are possible. Redirections can be cancelled by providing an empty argument for the target class. Redirection to a missing class raises an error immediately. Infinite loops are prevented by eliminating the redirection starting from the target of the redirection that caused the loop to appear. Namely, if redirections are requested as  $A \rightarrow B$ ,  $B \rightarrow C$  and  $C \rightarrow A$  in this order, then the  $A \rightarrow B$  redirection is cancelled.

---

<pre> \msg_redirect_class:nn </pre>	<pre> \msg_redirect_class:nn {&lt;class one&gt;} {&lt;class two&gt;} </pre>
-------------------------------------	---

---

Updated: 2012-04-27

---

Changes the behaviour of messages of  $\langle class one \rangle$  so that they are processed using the code for those of  $\langle class two \rangle$ .



---

<code>\msg_log:n</code>	<code>\msg_log:n {&lt;text&gt;}</code>
-------------------------	--

---

New: 2012-06-28	Writes to the log file with the <i>&lt;text&gt;</i> laid out in the format
-----------------	--

---

```

.....
. <text>
.....

```

where the *<text>* is wrapped to fit within the current line length. Wrapping takes place using `\iow_wrap:nnnN`; the documentation for the latter should be consulted for full details.

---

<code>\msg_term:n</code>	<code>\msg_term:n {&lt;text&gt;}</code>
--------------------------	---

---

New: 2012-06-28	Writes to the terminal and log file with the <i>&lt;text&gt;</i> laid out in the format
-----------------	---

---

```

*****
* <text>
*****

```

where the *<text>* is wrapped to fit within the current line length. Wrapping takes place using `\iow_wrap:nnnN`; the documentation for the latter should be consulted for full details.

## 6 Kernel-specific functions

Messages from L<sup>A</sup>T<sub>E</sub>X3 itself are handled by the general message system, but have their own functions. This allows some text to be pre-defined, and also ensures that serious errors can be handled properly.

---

<code>\_msg_kernel_new:nnnn</code>	<code>\_msg_kernel_new:nnnn {&lt;module&gt;} {&lt;message&gt;} {&lt;text&gt;} {&lt;more text&gt;}</code>
------------------------------------	--

---

<code>\_msg_kernel_new:nnn</code>	
-----------------------------------	--

---

Updated: 2011-08-16	
---------------------	--

---

Creates a kernel *<message>* for a given *<module>*. The message is defined to first give *<text>* and then *<more text>* if the user requests it. If no *<more text>* is available then a standard text is given instead. Within *<text>* and *<more text>* four parameters (**#1** to **#4**) can be used: these will be supplied and expanded at the time the message is used. An error is raised if the *<message>* already exists.

---

<code>\_msg_kernel_set:nnnn</code>	<code>\_msg_kernel_set:nnnn {&lt;module&gt;} {&lt;message&gt;} {&lt;text&gt;} {&lt;more text&gt;}</code>
------------------------------------	--

---

<code>\_msg_kernel_set:nnn</code>	
-----------------------------------	--

---

Sets up the text for a kernel *<message>* for a given *<module>*. The message is defined to first give *<text>* and then *<more text>* if the user requests it. If no *<more text>* is available then a standard text is given instead. Within *<text>* and *<more text>* four parameters (**#1** to **#4**) can be used: these will be supplied and expanded at the time the message is used.

---

```

\_msg_kernel_fatal:nnnnnn
\_msg_kernel_fatal:nnxxxx
\_msg_kernel_fatal:nnnnn
\_msg_kernel_fatal:nnxxx
\_msg_kernel_fatal:nnnn
\_msg_kernel_fatal:nnxx
\_msg_kernel_fatal:nnn
\_msg_kernel_fatal:nnx
\_msg_kernel_fatal:nn

```

---

Updated: 2012-08-11

---

```

\_msg_kernel_fatal:nnnnnn {\module} {\message} {\arg one} {\arg two} {\arg
three}} {\arg four}}

```

Issues kernel *<module>* error *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. After issuing a fatal error the T<sub>E</sub>X run halts. Cannot be redirected.

---

```

\_msg_kernel_error:nnnnnn
\_msg_kernel_error:nnxxxx
\_msg_kernel_error:nnnnn
\_msg_kernel_error:nnxxx
\_msg_kernel_error:nnnn
\_msg_kernel_error:nnxx
\_msg_kernel_error:nnn
\_msg_kernel_error:nnx
\_msg_kernel_error:nn

```

---

Updated: 2012-08-11

---

```

\_msg_kernel_error:nnnnnn {\module} {\message} {\arg one} {\arg two} {\arg
three}} {\arg four}}

```

Issues kernel *<module>* error *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. The error stops processing and issues the text at the terminal. After user input, the run continues. Cannot be redirected.

---

```

\_msg_kernel_warning:nnnnnn
\_msg_kernel_warning:nnxxxx
\_msg_kernel_warning:nnnnn
\_msg_kernel_warning:nnxxx
\_msg_kernel_warning:nnnn
\_msg_kernel_warning:nnxx
\_msg_kernel_warning:nnn
\_msg_kernel_warning:nnx
\_msg_kernel_warning:nn

```

---

Updated: 2012-08-11

---

```

\_msg_kernel_warning:nnnnnn {\module} {\message} {\arg one} {\arg
two}} {\arg three}} {\arg four}}

```

Issues kernel *<module>* warning *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. The warning text is added to the log file, but the T<sub>E</sub>X run is not interrupted.

---

```

\_msg_kernel_info:nnnnnn
\_msg_kernel_info:nnxxxx
\_msg_kernel_info:nnnnn
\_msg_kernel_info:nnxxx
\_msg_kernel_info:nnnn
\_msg_kernel_info:nnxx
\_msg_kernel_info:nnn
\_msg_kernel_info:nnx
\_msg_kernel_info:nn

```

---

Updated: 2012-08-11

---

```

\_msg_kernel_info:nnnnnn {\module} {\message} {\arg one} {\arg two} {\arg
three}} {\arg four}}

```

Issues kernel *<module>* information *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. The information text is added to the log file.

## 7 Expandable errors

In a few places, the L<sup>A</sup>T<sub>E</sub>X3 kernel needs to produce errors in an expansion only context. This must be handled internally very differently from normal error messages, as none of the tools to print to the terminal or the log file are expandable. However, the interface is similar, with the important caveat that the message text and arguments are not expanded, and messages should be very short.

---

```

\__msg_kernel_expandable_error:nnnnnn ★ \__msg_kernel_expandable_error:nnnnnn {<module>} {<message>}
\__msg_kernel_expandable_error:nnnnnn ★ {<arg one>} {<arg two>} {<arg three>} {<arg four>}
\__msg_kernel_expandable_error:nnnn ★
\__msg_kernel_expandable_error:nnnn ★
\__msg_kernel_expandable_error:nnnn ★
\__msg_kernel_expandable_error:nnnn ★

```

---

New: 2011-11-23

Issues an error, passing *<arg one>* to *<arg four>* to the text-creating functions. The resulting string must be much shorter than a line, otherwise it is cropped.

---

```

\__msg_expandable_error:n ★ \__msg_expandable_error:n {<error message>}

```

---

New: 2011-08-11

Updated: 2011-08-13

Issues an “Undefined error” message from T<sub>E</sub>X itself, and prints the *<error message>*. The *<error message>* must be short: it is cropped at the end of one line.

**T<sub>E</sub>Xhackers note:** This function expands to an empty token list after two steps. Tokens inserted in response to T<sub>E</sub>X’s prompt are read with the current category code setting, and inserted just after the place where the error message was issued.

## 8 Internal l3msg functions

The following functions are used in several kernel modules.

---

```

\__msg_log_next: \__msg_log_next: <show-command>

```

---

New: 2015-08-05

Causes the next *<show-command>* to send its output to the log file instead of the terminal. This allows for instance `\cs_log:N` to be defined as `\__msg_log_next:\cs_show:N`. The effect of this command lasts until the next use of `\__msg_show_wrap:Nn` or `\__msg_show_wrap:n` or `\__msg_show_variable:NNNnn`, in other words until the next time the  $\varepsilon$ -T<sub>E</sub>X primitive `\showtokens` would have been used for showing to the terminal or until the next `variable-not-defined` error.

---

```

\__msg_show_pre:nnnnnn \__msg_show_pre:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>}
\__msg_show_pre:(nnxxxx|nnnnnV) {<arg three>} {<arg four>}

```

---

New: 2015-08-05

Prints the *<message>* from *<module>* in the terminal (or log file if `\__msg_log_next:` was issued) without formatting. Used in messages which print complex variable contents completely.

<hr/> <code>\_msg\_show\_variable:NNNnn</code> <hr/> New: 2015-08-04	<code>\_msg\_show\_variable:NNNnn</code> $\langle variable \rangle$ $\langle if-exist \rangle$ $\langle if-empty \rangle$ $\{ \langle msg \rangle \}$ $\{ \langle formatted content \rangle \}$ <p>If the <math>\langle variable \rangle</math> does not exist according to <math>\langle if-exist \rangle</math> (typically <code>\cs\_if\_exist:NTF</code>) then throw an error and do nothing more. Otherwise, if <math>\langle msg \rangle</math> is not empty, display the message <code>LaTeX/kernel/show-<math>\langle msg \rangle</math></code> with <code>\token\_to\_str:N</code> <math>\langle variable \rangle</math> as a first argument, and a second argument that is ? or empty depending on the result of <math>\langle if-empty \rangle</math> (typically <code>\tl\_if\_empty:NTF</code>) on the <math>\langle variable \rangle</math>. Then display the <math>\langle formatted content \rangle</math> by giving it as an argument to <code>\_msg\_show\_wrap:n</code>.</p>
<hr/> <code>\_msg\_show\_wrap:Nn</code> <hr/> New: 2015-08-03 Updated: 2015-08-07	<code>\_msg\_show\_wrap:Nn</code> $\langle function \rangle$ $\{ \langle expression \rangle \}$ <p>Shows or logs the <math>\langle expression \rangle</math> (turned into a string), an equal sign, and the result of applying the <math>\langle function \rangle</math> to the <math>\{ \langle expression \rangle \}</math>. For instance, if the <math>\langle function \rangle</math> is <code>\int\_eval:n</code> and the <math>\langle expression \rangle</math> is <code>1+2</code> then this logs <code>&gt; 1+2=3</code>. The case where the <math>\langle function \rangle</math> is <code>\tl\_to\_str:n</code> is special: then the string representation of the <math>\langle expression \rangle</math> is only logged once.</p>
<hr/> <code>\_msg\_show\_wrap:n</code> <hr/> New: 2015-08-03	<code>\_msg\_show\_wrap:n</code> $\{ \langle formatted text \rangle \}$ <p>Shows or logs the <math>\langle formatted text \rangle</math>. After expansion, unless it is empty, the <math>\langle formatted text \rangle</math> must contain <code>&gt;</code>, and the part of <math>\langle formatted text \rangle</math> before the first <code>&gt;</code> is removed. Failure to do so causes low-level TeX errors.</p>
<hr/> <code>\_msg\_show\_item:n</code> <code>\_msg\_show\_item:nn</code> <code>\_msg\_show\_item\_unbraced:nn</code> <hr/> Updated: 2012-09-09	<code>\_msg\_show\_item:n</code> $\langle item \rangle$ <code>\_msg\_show\_item:nn</code> $\langle item-key \rangle$ $\langle item-value \rangle$ <p>Auxiliary functions used within the last argument of <code>\_msg\_show\_variable:NNNnn</code> or <code>\_msg\_show\_wrap:n</code> to format variable items correctly for display. The <code>\_msg\_show\_item:n</code> version is used for simple lists, the <code>\_msg\_show\_item:nn</code> and <code>\_msg\_show\_item\_unbraced:nn</code> versions for key-value like data structures.</p>
<hr/> <code>\c\_msg\_coding\_error\_text\_tl</code> <hr/>	<p>The text</p> <p style="text-align: center;"><b>This is a coding error.</b></p> <p>used by kernel functions when erroneous programming input is encountered.</p>



## Part XVIII

# The l3file package

## File and I/O operations

This module provides functions for working with external files. Some of these functions apply to an entire file, and have prefix `\file_...`, while others are used to work with files on a line by line basis and have prefix `\ior_...` (reading) or `\iow_...` (writing).

It is important to remember that when reading external files  $\text{\TeX}$  attempts to locate them both the operating system path and entries in the  $\text{\TeX}$  file database (most  $\text{\TeX}$  systems use such a database). Thus the “current path” for  $\text{\TeX}$  is somewhat broader than that for other programs.

For functions which expect a  $\langle file\ name \rangle$  argument, this argument may contain both literal items and expandable content, which should on full expansion be the desired file name. Active characters (as declared in `\l_char_active_seq`) are *not* be expanded, allowing the direct use of these in file names. File names are quoted using `"` tokens if they contain spaces: as a result, `"` tokens are *not* permitted in file names.

### 1 File operation functions

---

```
\g_file_curr_dir_str
\g_file_curr_name_str
\g_file_curr_ext_str
```

---

New: 2017-06-21

---

Contain the directory, name and extension of the current file. The directory is empty if the file was loaded without an explicit path (*i.e.* if it is in the  $\text{\TeX}$  search path), and does *not* end in `/` other than the case that it is exactly equal to the root directory. The  $\langle name \rangle$  and  $\langle ext \rangle$  parts together make up the file name, thus the  $\langle name \rangle$  part may be thought of as the “job name” for the current file. Note that  $\text{\TeX}$  does not provide information on the  $\langle ext \rangle$  part for the main (top level) file and that this file always has an empty  $\langle dir \rangle$  component. Also, the  $\langle name \rangle$  here will be equal to `\c_sys_jobname_str`, which may be different from the real file name (if set using `--jobname`, for example).

---

```
\l_file_search_path_seq
```

---

New: 2017-06-18

---

Each entry is the path to a directory which should be searched when seeking a file. Each path can be relative or absolute, and should not include the trailing slash. The entries are not expanded when used so may contain active characters but should not feature any variable content. Spaces need not be quoted.

**$\text{\TeX}$ hackers note:** When working as a package in  $\text{\LaTeX} 2_{\epsilon}$ , `expl3` will automatically append the current `\input@path` to the set of values from `\l_file_search_path_seq`.

---

```
\file_if_exist:nTF \file_if_exist:nTF {\file name} {\true code} {\false code}
```

---

Updated: 2012-02-10

---

Searches for  $\langle file\ name \rangle$  using the current  $\text{\TeX}$  search path and the additional paths controlled by `\l_file_search_path_seq`.

---

`\file_get_full_name:nN`  
`\file_get_full_name:VN`  


---

Updated: 2017-06-26

---

`\file_get_full_name:nN`  $\{\langle file\ name\rangle\}$   $\langle str\ var\rangle$

Searches for  $\langle file\ name\rangle$  in the path as detailed for `\file_if_exist:nTF`, and if found sets the  $\langle str\ var\rangle$  the fully-qualified name of the file, *i.e.* the path and file name. This includes an extension `.tex` when the given  $\langle file\ name\rangle$  has no extension but the file found has that extension. If the file is not found then the  $\langle str\ var\rangle$  is empty.

---

`\file_parse_full_name:nNNN`  
New: 2017-06-23  
Updated: 2017-06-26

---

`\file_parse_full_name:nNNN`  $\{\langle full\ name\rangle\}$   $\langle dir\rangle$   $\langle name\rangle$   $\langle ext\rangle$

Parses the  $\langle full\ name\rangle$  and splits it into three parts, each of which is returned by setting the appropriate local string variable:

- The  $\langle dir\rangle$ : everything up to the last `/` (path separator) in the  $\langle file\ path\rangle$ . As with system `PATH` variables and related functions, the  $\langle dir\rangle$  does *not* include the trailing `/` unless it points to the root directory. If there is no path (only a file name),  $\langle dir\rangle$  is empty.
- The  $\langle name\rangle$ : everything after the last `/` up to the last `.`, where both of those characters are optional. The  $\langle name\rangle$  may contain multiple `.` characters. It is empty if  $\langle full\ name\rangle$  consists only of a directory name.
- The  $\langle ext\rangle$ : everything after the last `.` (including the dot). The  $\langle ext\rangle$  is empty if there is no `.` after the last `/`.

This function does not expand the  $\langle full\ name\rangle$  before turning it to a string. It assume that the  $\langle full\ name\rangle$  either contains no quote (`"`) characters or is surrounded by a pair of quotes.

---

`\file_input:n`  
Updated: 2017-06-26

---

`\file_input:n`  $\{\langle file\ name\rangle\}$

Searches for  $\langle file\ name\rangle$  in the path as detailed for `\file_if_exist:nTF`, and if found reads in the file as additional L<sup>A</sup>T<sub>E</sub>X source. All files read are recorded for information and the file name stack is updated by this function. An error is raised if the file is not found.

---

`\file_show_list:`  
`\file_log_list:`

---

`\file_show_list:`

`\file_log_list:`

These functions list all files loaded by L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> commands that populate `\@filelist` or by `\file_input:n`. While `\file_show_list:` displays the list in the terminal, `\file_log_list:` outputs it to the log file only.

## 1.1 Input–output stream management

As T<sub>E</sub>X engines have a limited number of input and output streams, direct use of the streams by the programmer is not supported in L<sup>A</sup>T<sub>E</sub>X 3. Instead, an internal pool of streams is maintained, and these are allocated and deallocated as needed by other modules. As a result, the programmer should close streams when they are no longer needed, to release them for other processes.

Note that I/O operations are global: streams should all be declared with global names and treated accordingly.

<hr/> <code>\ior_new:N</code> <code>\ior_new:c</code> <code>\iow_new:N</code> <code>\iow_new:c</code> <hr/> New: 2011-09-26 Updated: 2011-12-27 <hr/>	<code>\ior_new:N</code> $\langle stream \rangle$ <code>\iow_new:N</code> $\langle stream \rangle$ <p>Globally reserves the name of the <math>\langle stream \rangle</math>, either for reading or for writing as appropriate. The <math>\langle stream \rangle</math> is not opened until the appropriate <code>\..._open:Nn</code> function is used. Attempting to use a <math>\langle stream \rangle</math> which has not been opened is an error, and the <math>\langle stream \rangle</math> will behave as the corresponding <code>\c_term_....</code></p>
<hr/> <code>\ior_open:Nn</code> <code>\ior_open:cn</code> <hr/> Updated: 2012-02-10 <hr/>	<code>\ior_open:Nn</code> $\langle stream \rangle$ $\{ \langle file\ name \rangle \}$ <p>Opens <math>\langle file\ name \rangle</math> for reading using <math>\langle stream \rangle</math> as the control sequence for file access. If the <math>\langle stream \rangle</math> was already open it is closed before the new operation begins. The <math>\langle stream \rangle</math> is available for access immediately and will remain allocated to <math>\langle file\ name \rangle</math> until a <code>\ior_close:N</code> instruction is given or the T<sub>E</sub>X run ends. If the file is not found, an error is raised.</p>
<hr/> <code>\ior_open:NnTF</code> <code>\ior_open:cnTF</code> <hr/> New: 2013-01-12 <hr/>	<code>\ior_open:NnTF</code> $\langle stream \rangle$ $\{ \langle file\ name \rangle \}$ $\{ \langle true\ code \rangle \}$ $\{ \langle false\ code \rangle \}$ <p>Opens <math>\langle file\ name \rangle</math> for reading using <math>\langle stream \rangle</math> as the control sequence for file access. If the <math>\langle stream \rangle</math> was already open it is closed before the new operation begins. The <math>\langle stream \rangle</math> is available for access immediately and will remain allocated to <math>\langle file\ name \rangle</math> until a <code>\ior_close:N</code> instruction is given or the T<sub>E</sub>X run ends. The <math>\langle true\ code \rangle</math> is then inserted into the input stream. If the file is not found, no error is raised and the <math>\langle false\ code \rangle</math> is inserted into the input stream.</p>
<hr/> <code>\iow_open:Nn</code> <code>\iow_open:cn</code> <hr/> Updated: 2012-02-09 <hr/>	<code>\iow_open:Nn</code> $\langle stream \rangle$ $\{ \langle file\ name \rangle \}$ <p>Opens <math>\langle file\ name \rangle</math> for writing using <math>\langle stream \rangle</math> as the control sequence for file access. If the <math>\langle stream \rangle</math> was already open it is closed before the new operation begins. The <math>\langle stream \rangle</math> is available for access immediately and will remain allocated to <math>\langle file\ name \rangle</math> until a <code>\iow_close:N</code> instruction is given or the T<sub>E</sub>X run ends. Opening a file for writing clears any existing content in the file (<i>i.e.</i> writing is <i>not</i> additive).</p>
<hr/> <code>\ior_close:N</code> <code>\ior_close:c</code> <code>\iow_close:N</code> <code>\iow_close:c</code> <hr/> Updated: 2012-07-31 <hr/>	<code>\ior_close:N</code> $\langle stream \rangle$ <code>\iow_close:N</code> $\langle stream \rangle$ <p>Closes the <math>\langle stream \rangle</math>. Streams should always be closed when they are finished with as this ensures that they remain available to other programmers.</p>
<hr/> <code>\ior_show_list:</code> <code>\ior_log_list:</code> <code>\iow_show_list:</code> <code>\iow_log_list:</code> <hr/> New: 2017-06-27 <hr/>	<code>\ior_show_list:</code> <code>\ior_log_list:</code> <code>\iow_show_list:</code> <code>\iow_log_list:</code> <p>Display (to the terminal or log file) a list of the file names associated with each open (read or write) stream. This is intended for tracking down problems.</p>

## 1.2 Reading from files

---

<code>\ior_get:NN</code>	<code>\ior_get:NN &lt;stream&gt; &lt;token list variable&gt;</code>
--------------------------	---

---

New: 2012-06-24

Function that reads one or more lines (until an equal number of left and right braces are found) from the input *<stream>* and stores the result locally in the *<token list>* variable. If the *<stream>* is not open, input is requested from the terminal. The material read from the *<stream>* is tokenized by  $\text{\TeX}$  according to the category codes and `\endlinechar` in force when the function is used. Assuming normal settings, any lines which do not end in a comment character `%` have the line ending converted to a space, so for example input

```
a b c
```

results in a token list `a_b_c_`. Any blank line is converted to the token `\par`. Therefore, blank lines can be skipped by using a test such as

```
\ior_get:NN \l_my_stream \l_tmpa_tl
\tl_set:Nn \l_tmpb_tl { \par }
\tl_if_eq:NNF \l_tmpa_tl \l_tmpb_tl
...
```

Also notice that if multiple lines are read to match braces then the resulting token list can contain `\par` tokens.

**$\text{\TeX}$ hackers note:** This protected macro is a wrapper around the  $\text{\TeX}$  primitive `\read`. Regardless of settings,  $\text{\TeX}$  replaces trailing space and tab characters (character codes 32 and 9) in each line by an end-of-line character (character code `\endlinechar`, omitted if `\endlinechar` is negative or too large) before turning characters into tokens according to current category codes. With default settings, spaces appearing at the beginning of lines are also ignored.

---

<code>\ior_str_get:NN</code>	<code>\ior_str_get:NN &lt;stream&gt; &lt;token list variable&gt;</code>
------------------------------	---

---

New: 2016-12-04

Function that reads one line from the input *<stream>* and stores the result locally in the *<token list>* variable. If the *<stream>* is not open, input is requested from the terminal. The material is read from the *<stream>* as a series of tokens with category code 12 (other), with the exception of space characters which are given category code 10 (space). Multiple whitespace characters are retained by this process. It always only reads one line and any blank lines in the input result in the *<token list variable>* being empty. Unlike `\ior_get:NN`, line ends do not receive any special treatment. Thus input

```
a b c
```

results in a token list `a b c` with the letters `a`, `b`, and `c` having category code 12.

**$\text{\TeX}$ hackers note:** This protected macro is a wrapper around the  $\varepsilon\text{\TeX}$  primitive `\readline`. Regardless of settings,  $\text{\TeX}$  removes trailing space and tab characters (character codes 32 and 9). However, the end-line character normally added by this primitive is not included in the result of `\ior_str_get:NN`.

<hr/> <code>\ior_map_inline:Nn</code> <hr/>	<code>\ior_map_inline:Nn &lt;stream&gt; {&lt;inline function&gt;}</code>
<hr/> New: 2012-02-11 <hr/>	Applies the <i>&lt;inline function&gt;</i> to each set of <i>&lt;lines&gt;</i> obtained by calling <code>\ior_get:NN</code> until reaching the end of the file. $\text{\TeX}$ ignores any trailing new-line marker from the file it reads. The <i>&lt;inline function&gt;</i> should consist of code which receives the <i>&lt;line&gt;</i> as <b>#1</b> .
<hr/> <code>\ior_str_map_inline:Nn</code> <hr/>	<code>\ior_str_map_inline:Nn {&lt;stream&gt;} {&lt;inline function&gt;}</code>
<hr/> New: 2012-02-11 <hr/>	Applies the <i>&lt;inline function&gt;</i> to every <i>&lt;line&gt;</i> in the <i>&lt;stream&gt;</i> . The material is read from the <i>&lt;stream&gt;</i> as a series of tokens with category code 12 (other), with the exception of space characters which are given category code 10 (space). The <i>&lt;inline function&gt;</i> should consist of code which receives the <i>&lt;line&gt;</i> as <b>#1</b> . Note that $\text{\TeX}$ removes trailing space and tab characters (character codes 32 and 9) from every line upon input. $\text{\TeX}$ also ignores any trailing new-line marker from the file it reads.
<hr/> <code>\ior_map_break:</code> <hr/>	<code>\ior_map_break:</code>
<hr/> New: 2012-06-29 <hr/>	Used to terminate a <code>\ior_map...</code> function before all lines from the <i>&lt;stream&gt;</i> have been processed. This normally takes place within a conditional statement, for example <pre> \ior_map_inline:Nn \l_my_ior {   \str_if_eq:nnTF { #1 } { bingo }   { \ior_map_break: }   {     % Do something useful   } } </pre> <p>Use outside of a <code>\ior_map...</code> scenario leads to low level <math>\text{\TeX}</math> errors.</p> <p><b><math>\text{\TeX}</math>hackers note:</b> When the mapping is broken, additional tokens may be inserted by the internal macro <code>\__prg_break_point:Nn</code> before further items are taken from the input stream. This depends on the design of the mapping function.</p>

---

**\ior\_map\_break:n**

---

New: 2012-06-29

---

**\ior\_map\_break:n** {*tokens*}

Used to terminate a **\ior\_map...** function before all lines in the *stream* have been processed, inserting the *tokens* after the mapping has ended. This normally takes place within a conditional statement, for example

```
\ior_map_inline:Nn \l_my_ior
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \ior_map_break:n { <tokens> } }
  {
    % Do something useful
  }
}
```

Use outside of a **\ior\_map...** scenario leads to low level TeX errors.

**TeXhackers note:** When the mapping is broken, additional tokens may be inserted by the internal macro **\\_\_prg\_break\_point:Nn** before the *tokens* are inserted into the input stream. This depends on the design of the mapping function.

---

**\ior\_if\_eof\_p:N** ★**\ior\_if\_eof:NTF** ★

---

Updated: 2012-02-10

---

**\ior\_if\_eof\_p:N** *stream***\ior\_if\_eof:NTF** *stream* {*true code*} {*false code*}

Tests if the end of a *stream* has been reached during a reading operation. The test also returns a true value if the *stream* is not open.

## 2 Writing to files

---

**\iow\_now:Nn****\iow\_now:(Nx|cn|cx)**

---

Updated: 2012-06-05

---

**\iow\_now:Nn** *stream* {*tokens*}

This functions writes *tokens* to the specified *stream* immediately (*i.e.* the write operation is called on expansion of **\iow\_now:Nn**).

---

**\iow\_log:n****\iow\_log:x****\iow\_log:n** {*tokens*}

This function writes the given *tokens* to the log (transcript) file immediately: it is a dedicated version of **\iow\_now:Nn**.

---

**\iow\_term:n****\iow\_term:x****\iow\_term:n** {*tokens*}

This function writes the given *tokens* to the terminal file immediately: it is a dedicated version of **\iow\_now:Nn**.

<hr/> <code>\iow_shipout:Nn</code> <code>\iow_shipout:(Nx cn cx)</code> <hr/>	<code>\iow_shipout:Nn &lt;stream&gt; {&lt;tokens&gt;}</code>  This functions writes $\langle tokens \rangle$ to the specified $\langle stream \rangle$ when the current page is finalised ( <i>i.e.</i> at shipout). The $x$ -type variants expand the $\langle tokens \rangle$ at the point where the function is used but <i>not</i> when the resulting tokens are written to the $\langle stream \rangle$ ( <i>cf.</i> <code>\iow_shipout_x:Nn</code> ).  <p><b>T<sub>E</sub>Xhackers note:</b> When using <code>expl3</code> with a format other than L<sup>A</sup>T<sub>E</sub>X, new line characters inserted using <code>\iow_newline:</code> or using the line-wrapping code <code>\iow_wrap:nnnN</code> are not recognized in the argument of <code>\iow_shipout:Nn</code>. This may lead to the insertion of additional unwanted line-breaks.</p>
<hr/> <code>\iow_shipout_x:Nn</code> <code>\iow_shipout_x:(Nx cn cx)</code> <hr/> <div>Updated: 2012-09-08</div> <hr/>	<code>\iow_shipout_x:Nn &lt;stream&gt; {&lt;tokens&gt;}</code>  This functions writes $\langle tokens \rangle$ to the specified $\langle stream \rangle$ when the current page is finalised ( <i>i.e.</i> at shipout). The $\langle tokens \rangle$ are expanded at the time of writing in addition to any expansion when the function is used. This makes these functions suitable for including material finalised during the page building process (such as the page number integer).  <p><b>T<sub>E</sub>Xhackers note:</b> This is a wrapper around the T<sub>E</sub>X primitive <code>\write</code>. When using <code>expl3</code> with a format other than L<sup>A</sup>T<sub>E</sub>X, new line characters inserted using <code>\iow_newline:</code> or using the line-wrapping code <code>\iow_wrap:nnnN</code> are not recognized in the argument of <code>\iow_shipout:Nn</code>. This may lead to the insertion of additional unwanted line-breaks.</p>
<hr/> <code>\iow_char:N</code> ★ <hr/>	<code>\iow_char:N \&lt;char&gt;</code>  Inserts $\langle char \rangle$ into the output stream. Useful when trying to write difficult characters such as %, {, }, <i>etc.</i> in messages, for example:  <code>\iow_now:Nx \g_my_iow { \iow_char:N \{ text \iow_char:N \} }</code>  The function has no effect if writing is taking place without expansion ( <i>e.g.</i> in the second argument of <code>\iow_now:Nn</code> ).
<hr/> <code>\iow_newline:</code> ★ <hr/>	<code>\iow_newline:</code>  Function to add a new line within the $\langle tokens \rangle$ written to a file. The function has no effect if writing is taking place without expansion ( <i>e.g.</i> in the second argument of <code>\iow_now:Nn</code> ).  <p><b>T<sub>E</sub>Xhackers note:</b> When using <code>expl3</code> with a format other than L<sup>A</sup>T<sub>E</sub>X, the character inserted by <code>\iow_newline:</code> is not recognized by T<sub>E</sub>X, which may lead to the insertion of additional unwanted line-breaks. This issue only affects <code>\iow_shipout:Nn</code>, <code>\iow_shipout_x:Nn</code> and direct uses of primitive operations.</p>

## 2.1 Wrapping lines in output

---

`\iow_wrap:nnnN`

---

New: 2012-06-28  
Updated: 2015-08-05

---

`\iow_wrap:nnnN`  $\langle text \rangle$   $\langle run-on\ text \rangle$   $\langle set\ up \rangle$   $\langle function \rangle$

This function wraps the  $\langle text \rangle$  to a fixed number of characters per line. At the start of each line which is wrapped, the  $\langle run-on\ text \rangle$  is inserted. The line character count targeted is the value of `\l_iow_line_count_int` minus the number of characters in the  $\langle run-on\ text \rangle$  for all lines except the first, for which the target number of characters is simply `\l_iow_line_count_int` since there is no run-on text. The  $\langle text \rangle$  and  $\langle run-on\ text \rangle$  are exhaustively expanded by the function, with the following substitutions:

- `\` may be used to force a new line,
- `\_` may be used to represent a forced space (for example after a control sequence),
- `\#`, `\%`, `\{`, `\}`, `\~` may be used to represent the corresponding character,
- `\iow_indent:n` may be used to indent a part of the  $\langle text \rangle$  (not the  $\langle run-on\ text \rangle$ ).

Additional functions may be added to the wrapping by using the  $\langle set\ up \rangle$ , which is executed before the wrapping takes place: this may include overriding the substitutions listed.

Any expandable material in the  $\langle text \rangle$  which is not to be expanded on wrapping should be converted to a string using `\token_to_str:N`, `\tl_to_str:n`, `\tl_to_str:N`, *etc.*

The result of the wrapping operation is passed as a braced argument to the  $\langle function \rangle$ , which is typically a wrapper around a write operation. The output of `\iow_wrap:nnnN` (*i.e.* the argument passed to the  $\langle function \rangle$ ) consists of characters of category “other” (category code 12), with the exception of spaces which have category “space” (category code 10). This means that the output does *not* expand further when written to a file.

**T<sub>E</sub>Xhackers note:** Internally, `\iow_wrap:nnnN` carries out an `x`-type expansion on the  $\langle text \rangle$  to expand it. This is done in such a way that `\exp_not:N` or `\exp_not:n` *could* be used to prevent expansion of material. However, this is less conceptually clear than conversion to a string, which is therefore the supported method for handling expandable material in the  $\langle text \rangle$ .

---

`\iow_indent:n`

---

New: 2011-09-21

---

`\iow_indent:n`  $\langle text \rangle$

In the first argument of `\iow_wrap:nnnN` (for instance in messages), indents  $\langle text \rangle$  by four spaces. This function does not cause a line break, and only affects lines which start within the scope of the  $\langle text \rangle$ . In case the indented  $\langle text \rangle$  should appear on separate lines from the surrounding text, use `\` to force line breaks.

---

`\l_iow_line_count_int`

---

New: 2012-06-24

---

The maximum number of characters in a line to be written by the `\iow_wrap:nnnN` function. This value depends on the T<sub>E</sub>X system in use: the standard value is 78, which is typically correct for unmodified T<sub>E</sub>Xlive and MiK<sub>T</sub>E<sub>X</sub> systems.

---

`\c_catcode_other_space_tl`

---

New: 2011-09-05

---

Token list containing one character with category code 12, (“other”), and character code 32 (space).



## 2.2 Constant input–output streams

---

<code>\c_term_ior</code>	Constant input stream for reading from the terminal. Reading from this stream using <code>\ior_get:NN</code> or similar results in a prompt from T <sub>E</sub> X of the form
--------------------------	---

---

`<tl>=`

---

<code>\c_log_iow</code> <code>\c_term_iow</code>	Constant output streams for writing to the log and to the terminal (plus the log), respectively.
---	--

---

## 2.3 Primitive conditionals

---

<code>\if_eof:w</code> ★	<code>\if_eof:w &lt;stream&gt;</code> <code>  &lt;true code&gt;</code> <code>\else:</code> <code>  &lt;false code&gt;</code> <code>\fi:</code> Tests if the <code>&lt;stream&gt;</code> returns “end of file”, which is true for non-existent files. The <code>\else:</code> branch is optional.
--------------------------	---

---

**T<sub>E</sub>Xhackers note:** This is the T<sub>E</sub>X primitive `\ifeof`.

## 2.4 Internal file functions and variables

---

<code>\g__file_internal_ior</code>	Used to test for the existence of files when opening.
------------------------------------	---

---



---

<code>\l__file_base_name_str</code> <code>\l__file_full_name_str</code>	Used to store and transfer the file name (including extension) and (partial) file path whilst reading files. (The file base is the base name plus any preceding directory name.)
--	--

---



---

<code>\__file_missing:n</code>	<code>\__file_missing:n {&lt;name&gt;}</code>
New: 2017-06-25	Expands the <code>&lt;name&gt;</code> as per <code>\__file_name_sanitize:nN</code> then produces an error message indicating that that file was not found.

---



---

<code>\__file_name_sanitize:nN</code>	<code>\__file_name_sanitize:nN {&lt;name&gt;} &lt;str var&gt;</code>
New: 2017-06-19	Exhaustively-expands the <code>&lt;name&gt;</code> with the exception of any category <code>&lt;active&gt;</code> (catcode 13) tokens, which are not expanded. The list of <code>&lt;active&gt;</code> tokens is taken from <code>\l_char_active_seq</code> . The <code>&lt;str var&gt;</code> is then set to the <code>&lt;sanitized name&gt;</code> .

---



---

<code>\__file_name_quote:nN</code>	<code>\__file_name_quote:nN {&lt;name&gt;} &lt;str var&gt;</code>
New: 2017-06-19 Updated: 2017-06-25	Expands the <code>&lt;name&gt;</code> (without special-casing active tokens), then sets the <code>&lt;str var&gt;</code> to the <code>&lt;name&gt;</code> quoted using " at each end if required by the presence of spaces in the <code>&lt;name&gt;</code> . Any existing " tokens is removed and if their number is odd an error is raised.

---

## 2.5 Internal input–output functions

<code>\_ior\_open:Nn</code>	<code>\_ior\_open:Nn &lt;stream&gt; {&lt;file name&gt;}</code>
<code>\_ior\_open:No</code>	
New: 2012-01-23	<p>This function has identical syntax to the public version. However, it does not take precautions against active characters in the <i>&lt;file name&gt;</i>, and it does not attempt to add a <i>&lt;path&gt;</i> to the <i>&lt;file name&gt;</i>: it is therefore intended to be used by higher-level functions which have already fully expanded the <i>&lt;file name&gt;</i> and which need to perform multiple open or close operations. See for example the implementation of <code>\file\_get\_full\_name:nN</code>,</p>
<code>\_iow\_with:Nnn</code>	<code>\_iow\_with:Nnn &lt;integer&gt; {&lt;value&gt;} {&lt;code&gt;}</code>
New: 2014-08-23	<p>If the <i>&lt;integer&gt;</i> is equal to the <i>&lt;value&gt;</i> then this function simply runs the <i>&lt;code&gt;</i>. Otherwise it saves the current value of the <i>&lt;integer&gt;</i>, sets it to the <i>&lt;value&gt;</i>, runs the <i>&lt;code&gt;</i>, and restores the <i>&lt;integer&gt;</i> to its former value. This is used to ensure that the <code>\newlinechar</code> is 10 when writing to a stream, which lets <code>\iow\_newline:</code> work, and that <code>\errorcontextlines</code> is <code>-1</code> when displaying a message.</p>

## Part XIX

# The l3skip package

## Dimensions and skips

L<sup>A</sup>T<sub>E</sub>X3 provides two general length variables: `dim` and `skip`. Lengths stored as `dim` variables have a fixed length, whereas `skip` lengths have a rubber (stretch/shrink) component. In addition, the `muskip` type is available for use in math mode: this is a special form of `skip` where the lengths involved are determined by the current math font (in  $\mu$ ). There are common features in the creation and setting of length variables, but for clarity the functions are grouped by variable type.

### 1 Creating and initialising `dim` variables

---

<code>\dim_new:N</code>
<code>\dim_new:c</code>

---

`\dim_new:N`  $\langle dimension \rangle$

Creates a new  $\langle dimension \rangle$  or raises an error if the name is already taken. The declaration is global. The  $\langle dimension \rangle$  is initially equal to 0pt.

---

<code>\dim_const:Nn</code>
<code>\dim_const:cn</code>

---

`\dim_const:Nn`  $\langle dimension \rangle$   $\{ \langle dimension expression \rangle \}$

Creates a new constant  $\langle dimension \rangle$  or raises an error if the name is already taken. The value of the  $\langle dimension \rangle$  is set globally to the  $\langle dimension expression \rangle$ .

New: 2012-03-05

---

<code>\dim_zero:N</code>
<code>\dim_zero:c</code>
<code>\dim_gzero:N</code>
<code>\dim_gzero:c</code>

---

`\dim_zero:N`  $\langle dimension \rangle$

Sets  $\langle dimension \rangle$  to 0pt.

---

<code>\dim_zero_new:N</code>
<code>\dim_zero_new:c</code>
<code>\dim_gzero_new:N</code>
<code>\dim_gzero_new:c</code>

---

`\dim_zero_new:N`  $\langle dimension \rangle$

Ensures that the  $\langle dimension \rangle$  exists globally by applying `\dim_new:N` if necessary, then applies `\dim_(g)zero:N` to leave the  $\langle dimension \rangle$  set to zero.

New: 2012-01-07

---

<code>\dim_if_exist_p:N</code>
<code>\dim_if_exist_p:c</code>
<code>\dim_if_exist:NTF</code>
<code>\dim_if_exist:cTF</code>

---

`\dim_if_exist_p:N`  $\langle dimension \rangle$

`\dim_if_exist:NTF`  $\langle dimension \rangle$   $\{ \langle true code \rangle \} \{ \langle false code \rangle \}$

Tests whether the  $\langle dimension \rangle$  is currently defined. This does not check that the  $\langle dimension \rangle$  really is a dimension variable.

New: 2012-03-03

## 2 Setting dim variables

---

<code>\dim_add:Nn</code>	<code>\dim_add:Nn &lt;dimension&gt; {&lt;dimension expression&gt;}</code>
<code>\dim_add:cn</code>	
<code>\dim_gadd:Nn</code>	Adds the result of the $\langle dimension\ expression \rangle$ to the current content of the $\langle dimension \rangle$ .
<code>\dim_gadd:cn</code>	

---

Updated: 2011-10-22

---



---

<code>\dim_set:Nn</code>	<code>\dim_set:Nn &lt;dimension&gt; {&lt;dimension expression&gt;}</code>
<code>\dim_set:cn</code>	
<code>\dim_gset:Nn</code>	Sets $\langle dimension \rangle$ to the value of $\langle dimension\ expression \rangle$ , which must evaluate to a length with units.
<code>\dim_gset:cn</code>	

---

Updated: 2011-10-22

---



---

<code>\dim_set_eq:NN</code>	<code>\dim_set_eq:NN &lt;dimension<sub>1</sub>&gt; &lt;dimension<sub>2</sub>&gt;</code>
<code>\dim_set_eq:(cN Nc cc)</code>	
<code>\dim_gset_eq:NN</code>	Sets the content of $\langle dimension_1 \rangle$ equal to that of $\langle dimension_2 \rangle$ .
<code>\dim_gset_eq:(cN Nc cc)</code>	

---



---

<code>\dim_sub:Nn</code>	<code>\dim_sub:Nn &lt;dimension&gt; {&lt;dimension expression&gt;}</code>
<code>\dim_sub:cn</code>	
<code>\dim_gsub:Nn</code>	Subtracts the result of the $\langle dimension\ expression \rangle$ from the current content of the $\langle dimension \rangle$ .
<code>\dim_gsub:cn</code>	

---

Updated: 2011-10-22

---

## 3 Utilities for dimension calculations

---

<code>\dim_abs:n</code>	★ <code>\dim_abs:n {&lt;dimexpr&gt;}</code>
Updated: 2012-09-26	Converts the $\langle dimexpr \rangle$ to its absolute value, leaving the result in the input stream as a $\langle dimension\ denotation \rangle$ .

---



---

<code>\dim_max:nn</code>	★ <code>\dim_max:nn {&lt;dimexpr<sub>1</sub>&gt;} {&lt;dimexpr<sub>2</sub>&gt;}</code>
<code>\dim_min:nn</code>	★ <code>\dim_min:nn {&lt;dimexpr<sub>1</sub>&gt;} {&lt;dimexpr<sub>2</sub>&gt;}</code>
New: 2012-09-09	
Updated: 2012-09-26	Evaluates the two $\langle dimension\ expressions \rangle$ and leaves either the maximum or minimum value in the input stream as appropriate, as a $\langle dimension\ denotation \rangle$ .

---

---

`\dim_ratio:nn` ☆

---

Updated: 2011-10-22

---

`\dim_ratio:nn {⟨dimexpr1⟩} {⟨dimexpr2⟩}`

Parses the two *⟨dimension expressions⟩* and converts the ratio of the two to a form suitable for use inside a *⟨dimension expression⟩*. This ratio is then left in the input stream, allowing syntax such as

```
\dim_set:Nn \l_my_dim
{ 10 pt * \dim_ratio:nn { 5 pt } { 10 pt } }
```

The output of `\dim_ratio:nn` on full expansion is a ration expression between two integers, with all distances converted to scaled points. Thus

```
\tl_set:Nx \l_my_tl { \dim_ratio:nn { 5 pt } { 10 pt } }
\tl_show:N \l_my_tl
```

displays 327680/655360 on the terminal.

## 4 Dimension expression conditionals

---

`\dim_compare_p:nNn` ☆

`\dim_compare:nNnTF` ☆

---

`\dim_compare_p:nNn {⟨dimexpr1⟩} ⟨relation⟩ {⟨dimexpr2⟩}`

`\dim_compare:nNnTF`

`{⟨dimexpr1⟩} ⟨relation⟩ {⟨dimexpr2⟩}`

`{⟨true code⟩} {⟨false code⟩}`

This function first evaluates each of the *⟨dimension expressions⟩* as described for `\dim_eval:n`. The two results are then compared using the *⟨relation⟩*:

Equal	=
Greater than	>
Less than	<

---

<code>\dim_compare_p:n</code> ★ <code>\dim_compare:nTF</code> ★	<code>\dim_compare_p:n</code> { $\langle dimexpr_1 \rangle$ $\langle relation_1 \rangle$ ... $\langle dimexpr_N \rangle$ $\langle relation_N \rangle$ $\langle dimexpr_{N+1} \rangle$ } <code>\dim_compare:nTF</code> { $\langle dimexpr_1 \rangle$ $\langle relation_1 \rangle$ ... $\langle dimexpr_N \rangle$ $\langle relation_N \rangle$ $\langle dimexpr_{N+1} \rangle$ } { $\langle true\ code \rangle$ } { $\langle false\ code \rangle$ }
--	--

---

Updated: 2013-01-13

This function evaluates the  $\langle dimension\ expressions \rangle$  as described for `\dim_eval:n` and compares consecutive result using the corresponding  $\langle relation \rangle$ , namely it compares  $\langle dimexpr_1 \rangle$  and  $\langle dimexpr_2 \rangle$  using the  $\langle relation_1 \rangle$ , then  $\langle dimexpr_2 \rangle$  and  $\langle dimexpr_3 \rangle$  using the  $\langle relation_2 \rangle$ , until finally comparing  $\langle dimexpr_N \rangle$  and  $\langle dimexpr_{N+1} \rangle$  using the  $\langle relation_N \rangle$ . The test yields `true` if all comparisons are `true`. Each  $\langle dimension\ expression \rangle$  is evaluated only once, and the evaluation is lazy, in the sense that if one comparison is `false`, then no other  $\langle dimension\ expression \rangle$  is evaluated and no other comparison is performed. The  $\langle relations \rangle$  can be any of the following:

Equal	= or ==
Greater than or equal to	>=
Greater than	>
Less than or equal to	<=
Less than	<
Not equal	!=

---

<code>\dim_case:nn</code> ★	<code>\dim_case:nnTF {⟨test dimension expression⟩}</code>
<code>\dim_case:nnTF</code> ★	<code>{</code> <code>  {⟨dimexpr case<sub>1</sub>⟩} {⟨code case<sub>1</sub>⟩}</code> <code>  {⟨dimexpr case<sub>2</sub>⟩} {⟨code case<sub>2</sub>⟩}</code> <code>  ...</code> <code>  {⟨dimexpr case<sub>n</sub>⟩} {⟨code case<sub>n</sub>⟩}</code> <code>}</code> <code>{⟨true code⟩}</code> <code>{⟨false code⟩}</code>

---

New: 2013-07-24

---

This function evaluates the *⟨test dimension expression⟩* and compares this in turn to each of the *⟨dimension expression cases⟩*. If the two are equal then the associated *⟨code⟩* is left in the input stream and other cases are discarded. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\dim_case:nn`, which does nothing if there is no match, is also available. For example

```

\dim_set:Nn \l_tmpa_dim { 5 pt }
\dim_case:nnF
{ 2 \l_tmpa_dim }
{
  { 5 pt }      { Small }
  { 4 pt + 6 pt } { Medium }
  { - 10 pt }   { Negative }
}
{ No idea! }
```

leaves “Medium” in the input stream.

## 5 Dimension expression loops

---

<code>\dim_do_until:nNnn</code> ☆	<code>\dim_do_until:nNnn {⟨dimexpr<sub>1</sub>⟩} ⟨relation⟩ {⟨dimexpr<sub>2</sub>⟩} {⟨code⟩}</code>
-----------------------------------	---

---

Places the *⟨code⟩* in the input stream for T<sub>E</sub>X to process, and then evaluates the relationship between the two *⟨dimension expressions⟩* as described for `\dim_compare:nNnTF`. If the test is **false** then the *⟨code⟩* is inserted into the input stream again and a loop occurs until the *⟨relation⟩* is **true**.

---

<code>\dim_do_while:nNnn</code> ☆	<code>\dim_do_while:nNnn {⟨dimexpr<sub>1</sub>⟩} ⟨relation⟩ {⟨dimexpr<sub>2</sub>⟩} {⟨code⟩}</code>
-----------------------------------	---

---

Places the *⟨code⟩* in the input stream for T<sub>E</sub>X to process, and then evaluates the relationship between the two *⟨dimension expressions⟩* as described for `\dim_compare:nNnTF`. If the test is **true** then the *⟨code⟩* is inserted into the input stream again and a loop occurs until the *⟨relation⟩* is **false**.

---

<code>\dim_until_do:nNnn</code> ☆	<code>\dim_until_do:nNnn {⟨dimexpr<sub>1</sub>⟩} ⟨relation⟩ {⟨dimexpr<sub>2</sub>⟩} {⟨code⟩}</code>
-----------------------------------	---

---

Evaluates the relationship between the two *⟨dimension expressions⟩* as described for `\dim_compare:nNnTF`, and then places the *⟨code⟩* in the input stream if the *⟨relation⟩* is **false**. After the *⟨code⟩* has been processed by T<sub>E</sub>X the test is repeated, and a loop occurs until the test is **true**.

<hr/> <code>\dim_while_do:nNnn</code> ☆ <hr/>	<code>\dim_while_do:nNnn {&lt;dimexpr<sub>1</sub>&gt;} &lt;relation&gt; {&lt;dimexpr<sub>2</sub>&gt;} {&lt;code&gt;}</code>
	Evaluates the relationship between the two <i>&lt;dimension expressions&gt;</i> as described for <code>\dim_compare:nNnTF</code> , and then places the <i>&lt;code&gt;</i> in the input stream if the <i>&lt;relation&gt;</i> is <b>true</b> . After the <i>&lt;code&gt;</i> has been processed by T <sub>E</sub> X the test is repeated, and a loop occurs until the test is <b>false</b> .
<hr/> <code>\dim_do_until:nn</code> ☆ <hr/> <div>Updated: 2013-01-13</div>	<code>\dim_do_until:nn {&lt;dimension relation&gt;} {&lt;code&gt;}</code>
	Places the <i>&lt;code&gt;</i> in the input stream for T <sub>E</sub> X to process, and then evaluates the <i>&lt;dimension relation&gt;</i> as described for <code>\dim_compare:nTF</code> . If the test is <b>false</b> then the <i>&lt;code&gt;</i> is inserted into the input stream again and a loop occurs until the <i>&lt;relation&gt;</i> is <b>true</b> .
<hr/> <code>\dim_do_while:nn</code> ☆ <hr/> <div>Updated: 2013-01-13</div>	<code>\dim_do_while:nn {&lt;dimension relation&gt;} {&lt;code&gt;}</code>
	Places the <i>&lt;code&gt;</i> in the input stream for T <sub>E</sub> X to process, and then evaluates the <i>&lt;dimension relation&gt;</i> as described for <code>\dim_compare:nTF</code> . If the test is <b>true</b> then the <i>&lt;code&gt;</i> is inserted into the input stream again and a loop occurs until the <i>&lt;relation&gt;</i> is <b>false</b> .
<hr/> <code>\dim_until_do:nn</code> ☆ <hr/> <div>Updated: 2013-01-13</div>	<code>\dim_until_do:nn {&lt;dimension relation&gt;} {&lt;code&gt;}</code>
	Evaluates the <i>&lt;dimension relation&gt;</i> as described for <code>\dim_compare:nTF</code> , and then places the <i>&lt;code&gt;</i> in the input stream if the <i>&lt;relation&gt;</i> is <b>false</b> . After the <i>&lt;code&gt;</i> has been processed by T <sub>E</sub> X the test is repeated, and a loop occurs until the test is <b>true</b> .
<hr/> <code>\dim_while_do:nn</code> ☆ <hr/> <div>Updated: 2013-01-13</div>	<code>\dim_while_do:nn {&lt;dimension relation&gt;} {&lt;code&gt;}</code>
	Evaluates the <i>&lt;dimension relation&gt;</i> as described for <code>\dim_compare:nTF</code> , and then places the <i>&lt;code&gt;</i> in the input stream if the <i>&lt;relation&gt;</i> is <b>true</b> . After the <i>&lt;code&gt;</i> has been processed by T <sub>E</sub> X the test is repeated, and a loop occurs until the test is <b>false</b> .

## 6 Using dim expressions and variables

<hr/> <code>\dim_eval:n</code> ☆ <hr/> <div>Updated: 2011-10-22</div>	<code>\dim_eval:n {&lt;dimension expression&gt;}</code>
	Evaluates the <i>&lt;dimension expression&gt;</i> , expanding any dimensions and token list variables within the <i>&lt;expression&gt;</i> to their content (without requiring <code>\dim_use:N/\tl_use:N</code> ) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a <i>&lt;dimension denotation&gt;</i> after two expansions. This is expressed in points ( <b>pt</b> ), and requires suitable termination if used in a T <sub>E</sub> X-style assignment as it is <i>not</i> an <i>&lt;internal dimension&gt;</i> .
<hr/> <code>\dim_use:N</code> ☆ <hr/> <code>\dim_use:c</code> ☆ <hr/>	<code>\dim_use:N &lt;dimension&gt;</code>
	Recovers the content of a <i>&lt;dimension&gt;</i> and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Can be omitted in places where a <i>&lt;dimension&gt;</i> is required (such as in the argument of <code>\dim_eval:n</code> ).

**T<sub>E</sub>Xhackers note:** `\dim_use:N` is the T<sub>E</sub>X primitive `\the`: this is one of several L<sup>A</sup>T<sub>E</sub>X3 names for this primitive.



---

<code>\dim_to_decimal:n</code> ★	<code>\dim_to_decimal:n {⟨dimexpr⟩}</code>
----------------------------------	--

---

New: 2014-07-15

Evaluates the *⟨dimension expression⟩*, and leaves the result, expressed in points (**pt**) in the input stream, with *no units*. The result is rounded by T<sub>E</sub>X to four or five decimal places. If the decimal part of the result is zero, it is omitted, together with the decimal marker.

For example

`\dim_to_decimal:n { 1bp }`

leaves 1.00374 in the input stream, *i.e.* the magnitude of one “big point” when converted to (T<sub>E</sub>X) points.

---

<code>\dim_to_decimal_in_bp:n</code> ★	<code>\dim_to_decimal_in_bp:n {⟨dimexpr⟩}</code>
--	--

---

New: 2014-07-15

Evaluates the *⟨dimension expression⟩*, and leaves the result, expressed in big points (**bp**) in the input stream, with *no units*. The result is rounded by T<sub>E</sub>X to four or five decimal places. If the decimal part of the result is zero, it is omitted, together with the decimal marker.

For example

`\dim_to_decimal_in_bp:n { 1pt }`

leaves 0.99628 in the input stream, *i.e.* the magnitude of one (T<sub>E</sub>X) point when converted to big points.

---

<code>\dim_to_decimal_in_sp:n</code> ★	<code>\dim_to_decimal_in_sp:n {⟨dimexpr⟩}</code>
--	--

---

New: 2015-05-18

Evaluates the *⟨dimension expression⟩*, and leaves the result, expressed in scaled points (**sp**) in the input stream, with *no units*. The result is necessarily an integer.

---

<code>\dim_to_decimal_in_unit:nn</code> ★	<code>\dim_to_decimal_in_unit:nn {⟨dimexpr<sub>1</sub>⟩} {⟨dimexpr<sub>2</sub>⟩}</code>
---	---

---

New: 2014-07-15

Evaluates the *⟨dimension expressions⟩*, and leaves the value of *⟨dimexpr<sub>1</sub>⟩*, expressed in a unit given by *⟨dimexpr<sub>2</sub>⟩*, in the input stream. The result is a decimal number, rounded by T<sub>E</sub>X to four or five decimal places. If the decimal part of the result is zero, it is omitted, together with the decimal marker.

For example

`\dim_to_decimal_in_unit:nn { 1bp } { 1mm }`

leaves 0.35277 in the input stream, *i.e.* the magnitude of one big point when converted to millimetres.

Note that this function is not optimised for any particular output and as such may give different results to `\dim_to_decimal_in_bp:n` or `\dim_to_decimal_in_sp:n`. In particular, the latter is able to take a wider range of input values as it is not limited by the ability to calculate a ratio using  $\varepsilon$ -T<sub>E</sub>X primitives, which is required internally by `\dim_to_decimal_in_unit:nn`.

<hr/> <code>\dim_to_fp:n</code> ★ <hr/>	<code>\dim_to_fp:n {⟨<i>dimexpr</i>⟩}</code>
New: 2012-05-08 <hr/>	Expands to an internal floating point number equal to the value of the $\langle \textit{dimexpr} \rangle$ in pt. Since dimension expressions are evaluated much faster than their floating point equivalent, <code>\dim_to_fp:n</code> can be used to speed up parts of a computation where a low precision and a smaller range are acceptable.

## 7 Viewing dim variables

<hr/> <code>\dim_show:N</code> <code>\dim_show:c</code> <hr/>	<code>\dim_show:N ⟨<i>dimension</i>⟩</code> Displays the value of the $\langle \textit{dimension} \rangle$ on the terminal.
<hr/> <code>\dim_show:n</code> <hr/>	<code>\dim_show:n {⟨<i>dimension expression</i>⟩}</code>
New: 2011-11-22 Updated: 2015-08-07 <hr/>	Displays the result of evaluating the $\langle \textit{dimension expression} \rangle$ on the terminal.
<hr/> <code>\dim_log:N</code> <code>\dim_log:c</code> <hr/>	<code>\dim_log:N ⟨<i>dimension</i>⟩</code> Writes the value of the $\langle \textit{dimension} \rangle$ in the log file.
New: 2014-08-22 Updated: 2015-08-03 <hr/>	
<hr/> <code>\dim_log:n</code> <hr/>	<code>\dim_log:n {⟨<i>dimension expression</i>⟩}</code>
New: 2014-08-22 Updated: 2015-08-07 <hr/>	Writes the result of evaluating the $\langle \textit{dimension expression} \rangle$ in the log file.

## 8 Constant dimensions

<hr/> <code>\c_max_dim</code> <hr/>	The maximum value that can be stored as a dimension. This can also be used as a component of a skip.
<hr/> <code>\c_zero_dim</code> <hr/>	A zero length as a dimension. This can also be used as a component of a skip.

## 9 Scratch dimensions

<hr/> <code>\l_tmpa_dim</code> <code>\l_tmpb_dim</code> <hr/>	Scratch dimension for local assignment. These are never used by the kernel code, and so are safe for use with any L <sup>A</sup> T <sub>E</sub> X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<hr/> <code>\g_tmpa_dim</code> <code>\g_tmpb_dim</code> <hr/>	Scratch dimension for global assignment. These are never used by the kernel code, and so are safe for use with any L <sup>A</sup> T <sub>E</sub> X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

## 10 Creating and initialising skip variables

---

`\skip_new:N`  
`\skip_new:c`

---

`\skip_new:N`  $\langle skip \rangle$

Creates a new  $\langle skip \rangle$  or raises an error if the name is already taken. The declaration is global. The  $\langle skip \rangle$  is initially equal to 0pt.

---

`\skip_const:Nn`  
`\skip_const:cn`

---

`\skip_const:Nn`  $\langle skip \rangle$   $\{\langle skip \text{ expression} \rangle\}$

Creates a new constant  $\langle skip \rangle$  or raises an error if the name is already taken. The value of the  $\langle skip \rangle$  is set globally to the  $\langle skip \text{ expression} \rangle$ .

New: 2012-03-05

---



---

`\skip_zero:N`  
`\skip_zero:c`  
`\skip_gzero:N`  
`\skip_gzero:c`

---

`\skip_zero:N`  $\langle skip \rangle$

Sets  $\langle skip \rangle$  to 0pt.

---

`\skip_zero_new:N`  
`\skip_zero_new:c`  
`\skip_gzero_new:N`  
`\skip_gzero_new:c`

---

`\skip_zero_new:N`  $\langle skip \rangle$

Ensures that the  $\langle skip \rangle$  exists globally by applying `\skip_new:N` if necessary, then applies `\skip_(g)zero:N` to leave the  $\langle skip \rangle$  set to zero.

New: 2012-01-07

---



---

`\skip_if_exist_p:N` ★  
`\skip_if_exist_p:c` ★  
`\skip_if_exist:NTF` ★  
`\skip_if_exist:cTF` ★

---

`\skip_if_exist_p:N`  $\langle skip \rangle$

`\skip_if_exist:NTF`  $\langle skip \rangle$   $\{\langle true \text{ code} \rangle\}$   $\{\langle false \text{ code} \rangle\}$

Tests whether the  $\langle skip \rangle$  is currently defined. This does not check that the  $\langle skip \rangle$  really is a skip variable.

New: 2012-03-03

---

## 11 Setting skip variables

---

`\skip_add:Nn`  
`\skip_add:cn`  
`\skip_gadd:Nn`  
`\skip_gadd:cn`

---

`\skip_add:Nn`  $\langle skip \rangle$   $\{\langle skip \text{ expression} \rangle\}$

Adds the result of the  $\langle skip \text{ expression} \rangle$  to the current content of the  $\langle skip \rangle$ .

Updated: 2011-10-22

---



---

`\skip_set:Nn`  
`\skip_set:cn`  
`\skip_gset:Nn`  
`\skip_gset:cn`

---

`\skip_set:Nn`  $\langle skip \rangle$   $\{\langle skip \text{ expression} \rangle\}$

Sets  $\langle skip \rangle$  to the value of  $\langle skip \text{ expression} \rangle$ , which must evaluate to a length with units and may include a rubber component (for example 1 cm plus 0.5 cm).

Updated: 2011-10-22

---



---

`\skip_set_eq:NN`  
`\skip_set_eq:(cN|Nc|cc)`  
`\skip_gset_eq:NN`  
`\skip_gset_eq:(cN|Nc|cc)`

---

`\skip_set_eq:NN`  $\langle skip_1 \rangle$   $\langle skip_2 \rangle$

Sets the content of  $\langle skip_1 \rangle$  equal to that of  $\langle skip_2 \rangle$ .

---

<code>\skip_sub:Nn</code>	<code>\skip_sub:Nn &lt;skip&gt; {&lt;skip expression&gt;}</code>
<code>\skip_sub:cn</code>	
<code>\skip_gsub:Nn</code>	Subtracts the result of the <i>&lt;skip expression&gt;</i> from the current content of the <i>&lt;skip&gt;</i> .
<code>\skip_gsub:cn</code>	

---

Updated: 2011-10-22

---

## 12 Skip expression conditionals

---

<code>\skip_if_eq_p:nn</code> ★	<code>\skip_if_eq_p:nn {&lt;skipexpr<sub>1</sub>&gt;} {&lt;skipexpr<sub>2</sub>&gt;}</code>
<code>\skip_if_eq:nnTF</code> ★	<code>\dim_compare:nTF</code> <code>{&lt;skipexpr<sub>1</sub>&gt;}{&lt;skipexpr<sub>2</sub>&gt;}</code> <code>{&lt;true code&gt;}{&lt;false code&gt;}</code>

---

This function first evaluates each of the *<skip expressions>* as described for `\skip_eval:n`. The two results are then compared for exact equality, *i.e.* both the fixed and rubber components must be the same for the test to be true.

---

<code>\skip_if_finite_p:n</code> ★	<code>\skip_if_finite_p:n {&lt;skipexpr&gt;}</code>
<code>\skip_if_finite:nTF</code> ★	<code>\skip_if_finite:nTF {&lt;skipexpr&gt;}{&lt;true code&gt;}{&lt;false code&gt;}</code>

---

New: 2012-03-05

Evaluates the *<skip expression>* as described for `\skip_eval:n`, and then tests if all of its components are finite.

## 13 Using skip expressions and variables

---

<code>\skip_eval:n</code> ★	<code>\skip_eval:n {&lt;skip expression&gt;}</code>
-----------------------------	---

---

Updated: 2011-10-22

Evaluates the *<skip expression>*, expanding any skips and token list variables within the *<expression>* to their content (without requiring `\skip_use:N/\tl_use:N`) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a *<glue denotation>* after two expansions. This is expressed in points (**pt**), and requires suitable termination if used in a **T<sub>E</sub>X**-style assignment as it is *not* an *<internal glue>*.

---

<code>\skip_use:N</code> ★	<code>\skip_use:N &lt;skip&gt;</code>
<code>\skip_use:c</code> ★	

---

Recovers the content of a *<skip>* and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Can be omitted in places where a *<dimension>* is required (such as in the argument of `\skip_eval:n`).

**T<sub>E</sub>Xhackers note:** `\skip_use:N` is the **T<sub>E</sub>X** primitive `\the`: this is one of several L<sup>A</sup>T<sub>E</sub>X3 names for this primitive.

## 14 Viewing skip variables

---

<code>\skip_show:N</code>	<code>\skip_show:N &lt;skip&gt;</code>
<code>\skip_show:c</code>	

---

Updated: 2015-08-03

Displays the value of the *<skip>* on the terminal.

<hr/> <code>\skip_show:n</code> <hr/>	<code>\skip_show:n {\langle skip expression \rangle}</code>
New: 2011-11-22 Updated: 2015-08-07	Displays the result of evaluating the $\langle skip expression \rangle$ on the terminal.

<hr/> <code>\skip_log:N</code> <code>\skip_log:c</code> <hr/>	<code>\skip_log:N \langle skip \rangle</code>
New: 2014-08-22 Updated: 2015-08-03	Writes the value of the $\langle skip \rangle$ in the log file.

<hr/> <code>\skip_log:n</code> <hr/>	<code>\skip_log:n {\langle skip expression \rangle}</code>
New: 2014-08-22 Updated: 2015-08-07	Writes the result of evaluating the $\langle skip expression \rangle$ in the log file.

## 15 Constant skips

<hr/> <code>\c_max_skip</code> <hr/>	The maximum value that can be stored as a skip (equal to <code>\c_max_dim</code> in length), with no stretch nor shrink component.
Updated: 2012-11-02	

<hr/> <code>\c_zero_skip</code> <hr/>	A zero length as a skip, with no stretch nor shrink component.
Updated: 2012-11-01	

## 16 Scratch skips

<hr/> <code>\l_tmpa_skip</code> <code>\l_tmpb_skip</code> <hr/>	Scratch skip for local assignment. These are never used by the kernel code, and so are safe for use with any L <sup>A</sup> T <sub>E</sub> X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	--

<hr/> <code>\g_tmpa_skip</code> <code>\g_tmpb_skip</code> <hr/>	Scratch skip for global assignment. These are never used by the kernel code, and so are safe for use with any L <sup>A</sup> T <sub>E</sub> X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	---

## 17 Inserting skips into the output

<hr/> <code>\skip_horizontal:N</code> <code>\skip_horizontal:c</code> <code>\skip_horizontal:n</code> <hr/>	<code>\skip_horizontal:N \langle skip \rangle</code> <code>\skip_horizontal:n {\langle skipexpr \rangle}</code>
Updated: 2011-10-22	Inserts a horizontal $\langle skip \rangle$ into the current list.

**T<sub>E</sub>Xhackers note:** `\skip_horizontal:N` is the T<sub>E</sub>X primitive `\hskip` renamed.

---

<code>\skip_vertical:N</code>	<code>\skip_vertical:N &lt;skip&gt;</code>
<code>\skip_vertical:c</code>	<code>\skip_vertical:n {&lt;skipexpr&gt;}</code>
<code>\skip_vertical:n</code>	

---

Inserts a vertical `<skip>` into the current list.

Updated: 2011-10-22

---

**T<sub>E</sub>Xhackers note:** `\skip_vertical:N` is the T<sub>E</sub>X primitive `\vskip` renamed.

## 18 Creating and initialising muskip variables

---

<code>\muskip_new:N</code>	<code>\muskip_new:N &lt;muskip&gt;</code>
<code>\muskip_new:c</code>	

---

Creates a new `<muskip>` or raises an error if the name is already taken. The declaration is global. The `<muskip>` is initially equal to 0 mu.

---

<code>\muskip_const:Nn</code>	<code>\muskip_const:Nn &lt;muskip&gt; {&lt;muskip expression&gt;}</code>
<code>\muskip_const:cn</code>	

---

Creates a new constant `<muskip>` or raises an error if the name is already taken. The value of the `<muskip>` is set globally to the `<muskip expression>`.

New: 2012-03-05

---



---

<code>\muskip_zero:N</code>	<code>\skip_zero:N &lt;muskip&gt;</code>
<code>\muskip_zero:c</code>	
<code>\muskip_gzero:N</code>	
<code>\muskip_gzero:c</code>	

---

Sets `<muskip>` to 0 mu.

---

<code>\muskip_zero_new:N</code>	<code>\muskip_zero_new:N &lt;muskip&gt;</code>
<code>\muskip_zero_new:c</code>	
<code>\muskip_gzero_new:N</code>	
<code>\muskip_gzero_new:c</code>	

---

Ensures that the `<muskip>` exists globally by applying `\muskip_new:N` if necessary, then applies `\muskip_(g)zero:N` to leave the `<muskip>` set to zero.

New: 2012-01-07

---



---

<code>\muskip_if_exist_p:N</code> ★	<code>\muskip_if_exist_p:N &lt;muskip&gt;</code>
<code>\muskip_if_exist_p:c</code> ★	<code>\muskip_if_exist:NTF &lt;muskip&gt; {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\muskip_if_exist:NTF</code> ★	
<code>\muskip_if_exist:cTF</code> ★	

---

Tests whether the `<muskip>` is currently defined. This does not check that the `<muskip>` really is a muskip variable.

New: 2012-03-03

---

## 19 Setting muskip variables

---

<code>\muskip_add:Nn</code>	<code>\muskip_add:Nn &lt;muskip&gt; {&lt;muskip expression&gt;}</code>
<code>\muskip_add:cn</code>	
<code>\muskip_gadd:Nn</code>	
<code>\muskip_gadd:cn</code>	

---

Adds the result of the `<muskip expression>` to the current content of the `<muskip>`.

Updated: 2011-10-22

---

<code>\muskip_set:Nn</code>	<code>\muskip_set:Nn &lt;muskip&gt; {&lt;muskip expression&gt;}</code>
<code>\muskip_set:cn</code>	Sets <i>&lt;muskip&gt;</i> to the value of <i>&lt;muskip expression&gt;</i> , which must evaluate to a math length with units and may include a rubber component (for example 1 mu plus 0.5 mu).
<code>\muskip_gset:Nn</code>	
<code>\muskip_gset:cn</code>	
Updated: 2011-10-22	

<code>\muskip_set_eq:NN</code>	<code>\muskip_set_eq:NN &lt;muskip<sub>1</sub>&gt; &lt;muskip<sub>2</sub>&gt;</code>
<code>\muskip_set_eq:(cN Nc cc)</code>	Sets the content of <i>&lt;muskip<sub>1</sub>&gt;</i> equal to that of <i>&lt;muskip<sub>2</sub>&gt;</i> .
<code>\muskip_gset_eq:NN</code>	
<code>\muskip_gset_eq:(cN Nc cc)</code>	

<code>\muskip_sub:Nn</code>	<code>\muskip_sub:Nn &lt;muskip&gt; {&lt;muskip expression&gt;}</code>
<code>\muskip_sub:cn</code>	Subtracts the result of the <i>&lt;muskip expression&gt;</i> from the current content of the <i>&lt;skip&gt;</i> .
<code>\muskip_gsub:Nn</code>	
<code>\muskip_gsub:cn</code>	
Updated: 2011-10-22	

## 20 Using muskip expressions and variables

<code>\muskip_eval:n</code> ★	<code>\muskip_eval:n {&lt;muskip expression&gt;}</code>
Updated: 2011-10-22	Evaluates the <i>&lt;muskip expression&gt;</i> , expanding any skips and token list variables within the <i>&lt;expression&gt;</i> to their content (without requiring <code>\muskip_use:N/\tl_use:N</code> ) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a <i>&lt;mu glue denotation&gt;</i> after two expansions. This is expressed in <b>mu</b> , and requires suitable termination if used in a T <sub>E</sub> X-style assignment as it is <i>not</i> an <i>&lt;internal mu glue&gt;</i> .

<code>\muskip_use:N</code> ★	<code>\muskip_use:N &lt;muskip&gt;</code>
<code>\muskip_use:c</code> ★	Recovers the content of a <i>&lt;skip&gt;</i> and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Can be omitted in places where a <i>&lt;dimension&gt;</i> is required (such as in the argument of <code>\muskip_eval:n</code> ).

**T<sub>E</sub>Xhackers note:** `\muskip_use:N` is the T<sub>E</sub>X primitive `\the`: this is one of several L<sup>A</sup>T<sub>E</sub>X3 names for this primitive.

## 21 Viewing muskip variables

<code>\muskip_show:N</code>	<code>\muskip_show:N &lt;muskip&gt;</code>
<code>\muskip_show:c</code>	Displays the value of the <i>&lt;muskip&gt;</i> on the terminal.

Updated: 2015-08-03

<code>\muskip_show:n</code>	<code>\muskip_show:n {&lt;muskip expression&gt;}</code>
New: 2011-11-22	Displays the result of evaluating the <i>&lt;muskip expression&gt;</i> on the terminal.

Updated: 2015-08-07

---

<code>\muskip_log:N</code>	<code>\muskip_log:N &lt;muskip&gt;</code>
<code>\muskip_log:c</code>	Writes the value of the <code>&lt;muskip&gt;</code> in the log file.

---

New: 2014-08-22  
Updated: 2015-08-03

---



---

<code>\muskip_log:n</code>	<code>\muskip_log:n {&lt;muskip expression&gt;}</code>
	Writes the result of evaluating the <code>&lt;muskip expression&gt;</code> in the log file.

---

New: 2014-08-22  
Updated: 2015-08-07

---

## 22 Constant muskips

---

<code>\c_max_muskip</code>	The maximum value that can be stored as a muskip, with no stretch nor shrink component.
----------------------------	---

---



---

<code>\c_zero_muskip</code>	A zero length as a muskip, with no stretch nor shrink component.
-----------------------------	--

---

## 23 Scratch muskips

---

<code>\l_tmpa_muskip</code> <code>\l_tmpb_muskip</code>	Scratch muskip for local assignment. These are never used by the kernel code, and so are safe for use with any L <sup>A</sup> T <sub>E</sub> X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	--

---



---

<code>\g_tmpa_muskip</code> <code>\g_tmpb_muskip</code>	Scratch muskip for global assignment. These are never used by the kernel code, and so are safe for use with any L <sup>A</sup> T <sub>E</sub> X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	---

---

## 24 Primitive conditional

---

<code>\if_dim:w</code>	<code>\if_dim:w &lt;dimen<sub>12  <code>  &lt;true code&gt;</code>  <code>\else:</code>  <code>  &lt;false&gt;</code>  <code>\fi:</code></sub></code>
------------------------	---

---

Compare two dimensions. The `<relation>` is one of `<`, `=` or `>` with category code 12.

**T<sub>E</sub>Xhackers note:** This is the T<sub>E</sub>X primitive `\ifdim`.



## 25 Internal functions

<hr/>	
<code>\_dim\_eval:w</code>	★
<code>\_dim\_eval\_end:</code>	★
<hr/>	

Evaluates *<dimension expression>* as described for `\dim\_eval:n`. The evaluation stops when an unexpandable token which is not a valid part of a dimension is read or when `\_dim\_eval\_end:` is reached. The latter is gobbled by the scanner mechanism: `\_dim\_eval\_end:` itself is unexpandable but used correctly the entire construct is expandable.

**TeXhackers note:** This is the  $\varepsilon$ -TeX primitive `\dimexpr`.

## Part XX

# The l3keys package

## Key–value interfaces

The key–value method is a popular system for creating large numbers of settings for controlling function or package behaviour. The system normally results in input of the form

```
\MyModuleSetup{
  key-one = value one,
  key-two = value two
}
```

or

```
\MyModuleMacro[
  key-one = value one,
  key-two = value two
]{argument}
```

for the user.

The high level functions here are intended as a method to create key–value controls. Keys are themselves created using a key–value interface, minimising the number of functions and arguments required. Each key is created by setting one or more *properties* of the key:

```
\keys_define:nn { mymodule }
{
  key-one .code:n = code including parameter #1,
  key-two .tl_set:N = \l_mymodule_store_tl
}
```

These values can then be set as with other key–value approaches:

```
\keys_set:nn { mymodule }
{
  key-one = value one,
  key-two = value two
}
```

At a document level, `\keys_set:nn` is used within a document function, for example

```
\DeclareDocumentCommand \MyModuleSetup { m }
{ \keys_set:nn { mymodule } { #1 } }
\DeclareDocumentCommand \MyModuleMacro { o m }
{
  \group_begin:
    \keys_set:nn { mymodule } { #1 }
    % Main code for \MyModuleMacro
  \group_end:
}
```

Key names may contain any tokens, as they are handled internally using `\tl_to_str:n`; spaces are *ignored* in key names. As discussed in section 2, it is suggested that the character `/` is reserved for sub-division of keys into logical groups. Functions and variables are *not* expanded when creating key names, and so

```
\tl_set:Nn \l_mymodule_tmp_tl { key }
\keys_define:nn { mymodule }
{
  \l_mymodule_tmp_tl .code:n = code
}
```

creates a key called `\l_mymodule_tmp_tl`, and not one called `key`.

## 1 Creating keys

---

`\keys_define:nn`

Updated: 2015-11-07

---

`\keys_define:nn {<module>} {<keyval list>}`

Parses the *<keyval list>* and defines the keys listed there for *<module>*. The *<module>* name should be a text value, but there are no restrictions on the nature of the text. In practice the *<module>* should be chosen to be unique to the module in question (unless deliberately adding keys to an existing module).

The *<keyval list>* should consist of one or more key names along with an associated key *property*. The properties of a key determine how it acts. The individual properties are described in the following text; a typical use of `\keys_define:nn` might read

```
\keys_define:nn { mymodule }
{
  keyname .code:n = Some~code~using~#1,
  keyname .value_required:n = true
}
```

where the properties of the key begin from the `.` after the key name.

The various properties available take either no arguments at all, or require one or more arguments. This is indicated in the name of the property using an argument specification. In the following discussion, each property is illustrated attached to an arbitrary *<key>*, which when used may be supplied with a *<value>*. All key *definitions* are local.

Key properties are applied in the reading order and so the ordering is significant. Key properties which define “actions”, such as `.code:n`, `.tl_set:N`, *etc.*, override one another. Some other properties are mutually exclusive, notably `.value_required:n` and `.value_forbidden:n`, and so they replace one another. However, properties covering non-exclusive behaviours may be given in any order. Thus for example the following definitions are equivalent.

```
\keys_define:nn { mymodule }
{
  keyname .code:n          = Some~code~using~#1,
  keyname .value_required:n = true
}
\keys_define:nn { mymodule }
```

```

{
  keyname .value_required:n = true,
  keyname .code:n           = Some~code~using~#1
}

```

Note that with the exception of the special `.undefine:` property, all key properties define the key within the current  $\text{\TeX}$  scope.

---

```

.bool_set:N
.bool_set:c
.bool_gset:N
.bool_gset:c

```

---

Updated: 2013-07-08

$\langle key \rangle$  .bool\_set:N =  $\langle boolean \rangle$

Defines  $\langle key \rangle$  to set  $\langle boolean \rangle$  to  $\langle value \rangle$  (which must be either `true` or `false`). If the variable does not exist, it will be created globally at the point that the key is set up.

---

```

.bool_set_inverse:N
.bool_set_inverse:c
.bool_gset_inverse:N
.bool_gset_inverse:c

```

---

New: 2011-08-28

Updated: 2013-07-08

$\langle key \rangle$  .bool\_set\_inverse:N =  $\langle boolean \rangle$

Defines  $\langle key \rangle$  to set  $\langle boolean \rangle$  to the logical inverse of  $\langle value \rangle$  (which must be either `true` or `false`). If the  $\langle boolean \rangle$  does not exist, it will be created globally at the point that the key is set up.

---

```

.choice:

```

---

$\langle key \rangle$  .choice:

Sets  $\langle key \rangle$  to act as a choice key. Each valid choice for  $\langle key \rangle$  must then be created, as discussed in section 3.

---

```

.choices:nn
.choices:(Vn|on|xn)

```

---

New: 2011-08-21

Updated: 2013-07-10

$\langle key \rangle$  .choices:nn =  $\{\langle choices \rangle\}$   $\{\langle code \rangle\}$

Sets  $\langle key \rangle$  to act as a choice key, and defines a series  $\langle choices \rangle$  which are implemented using the  $\langle code \rangle$ . Inside  $\langle code \rangle$ , `\l_keys_choice_tl` will be the name of the choice made, and `\l_keys_choice_int` will be the position of the choice in the list of  $\langle choices \rangle$  (indexed from 1). Choices are discussed in detail in section 3.

---

```

.clist_set:N
.clist_set:c
.clist_gset:N
.clist_gset:c

```

---

New: 2011-09-11

$\langle key \rangle$  .clist\_set:N =  $\langle comma list variable \rangle$

Defines  $\langle key \rangle$  to set  $\langle comma list variable \rangle$  to  $\langle value \rangle$ . Spaces around commas and empty items will be stripped. If the variable does not exist, it is created globally at the point that the key is set up.

---

```

.code:n

```

---

Updated: 2013-07-10

$\langle key \rangle$  .code:n =  $\{\langle code \rangle\}$

Stores the  $\langle code \rangle$  for execution when  $\langle key \rangle$  is used. The  $\langle code \rangle$  can include one parameter (#1), which will be the  $\langle value \rangle$  given for the  $\langle key \rangle$ . The x-type variant expands  $\langle code \rangle$  at the point where the  $\langle key \rangle$  is created.

---

`.default:n`  
`.default:(V|o|x)`  
Updated: 2013-07-09

---

`<key> .default:n = {<default>}`

Creates a *<default>* value for *<key>*, which is used if no value is given. This will be used if only the key name is given, but not if a blank *<value>* is given:

```
\keys_define:nn { mymodule }
{
  key .code:n      = Hello~#1,
  key .default:n = World
}
\keys_set:nn { mymodule }
{
  key = Fred, % Prints 'Hello Fred'
  key,      % Prints 'Hello World'
  key = ,    % Prints 'Hello '
}
```

The default does not affect keys where values are required or forbidden. Thus a required value cannot be supplied by a default value, and giving a default value for a key which cannot take a value does not trigger an error.

---

`.dim_set:N`  
`.dim_set:c`  
`.dim_gset:N`  
`.dim_gset:c`

---

`<key> .dim_set:N = <dimension>`

Defines *<key>* to set *<dimension>* to *<value>* (which must a dimension expression). If the variable does not exist, it is created globally at the point that the key is set up.

---

`.fp_set:N`  
`.fp_set:c`  
`.fp_gset:N`  
`.fp_gset:c`

---

`<key> .fp_set:N = <floating point>`

Defines *<key>* to set *<floating point>* to *<value>* (which must a floating point expression). If the variable does not exist, it is created globally at the point that the key is set up.

---

`.groups:n`  
New: 2013-07-14

---

`<key> .groups:n = {<groups>}`

Defines *<key>* as belonging to the *<groups>* declared. Groups provide a “secondary axis” for selectively setting keys, and are described in Section 6.

---

`.inherit:n`  
New: 2016-11-22

---

`<key> .inherit:n = {<parents>}`

Specifies that the *<key>* path should inherit the keys listed as *<parents>*. For example, after setting

```
\keys_define:n { foo } { test .code:n = \tl_show:n {#1} }
\keys_define:n { } { bar .inherit:n = foo }
```

setting

```
\keys_set:n { bar } { test = a }
```

will be equivalent to

```
\keys_set:n { foo } { test = a }
```

<hr/> <code>.initial:n</code> <hr/>	<code>&lt;key&gt; .initial:n = {&lt;value&gt;}</code>
<code>.initial:(V o x)</code>	Initialises the <code>&lt;key&gt;</code> with the <code>&lt;value&gt;</code> , equivalent to
<hr/> Updated: 2013-07-09 <hr/>	<code>\keys_set:nn {&lt;module&gt;} { &lt;key&gt; = &lt;value&gt; }</code>
<hr/> <code>.int_set:N</code> <hr/>	<code>&lt;key&gt; .int_set:N = &lt;integer&gt;</code>
<code>.int_set:c</code>	Defines <code>&lt;key&gt;</code> to set <code>&lt;integer&gt;</code> to <code>&lt;value&gt;</code> (which must be an integer expression). If the
<code>.int_gset:N</code>	variable does not exist, it is created globally at the point that the key is set up.
<code>.int_gset:c</code> <hr/>	
<hr/> <code>.meta:n</code> <hr/>	<code>&lt;key&gt; .meta:n = {&lt;keyval list&gt;}</code>
<hr/> Updated: 2013-07-10 <hr/>	Makes <code>&lt;key&gt;</code> a meta-key, which will set <code>&lt;keyval list&gt;</code> in one go. If <code>&lt;key&gt;</code> is given with a
	value at the time the key is used, then the value will be passed through to the subsidiary
	<code>&lt;keys&gt;</code> for processing (as #1).
<hr/> <code>.meta:nn</code> <hr/>	<code>&lt;key&gt; .meta:nn = {&lt;path&gt;} {&lt;keyval list&gt;}</code>
<hr/> New: 2013-07-10 <hr/>	Makes <code>&lt;key&gt;</code> a meta-key, which will set <code>&lt;keyval list&gt;</code> in one go using the <code>&lt;path&gt;</code> in place of
	the current one. If <code>&lt;key&gt;</code> is given with a value at the time the key is used, then the value
	will be passed through to the subsidiary <code>&lt;keys&gt;</code> for processing (as #1).
<hr/> <code>.multichoice:</code> <hr/>	<code>&lt;key&gt; .multichoice:</code>
<hr/> New: 2011-08-21 <hr/>	Sets <code>&lt;key&gt;</code> to act as a multiple choice key. Each valid choice for <code>&lt;key&gt;</code> must then be
	created, as discussed in section 3.
<hr/> <code>.multichoices:nn</code> <hr/>	<code>&lt;key&gt; .multichoices:nn {&lt;choices&gt;} {&lt;code&gt;}</code>
<code>.multichoices:(Vn on xn)</code>	Sets <code>&lt;key&gt;</code> to act as a multiple choice key, and defines a series <code>&lt;choices&gt;</code> which are im-
<hr/> New: 2011-08-21 <hr/>	plemented using the <code>&lt;code&gt;</code> . Inside <code>&lt;code&gt;</code> , <code>\l_keys_choice_tl</code> will be the name of the
<hr/> Updated: 2013-07-10 <hr/>	choice made, and <code>\l_keys_choice_int</code> will be the position of the choice in the list of
	<code>&lt;choices&gt;</code> (indexed from 1). Choices are discussed in detail in section 3.
<hr/> <code>.skip_set:N</code> <hr/>	<code>&lt;key&gt; .skip_set:N = &lt;skip&gt;</code>
<code>.skip_set:c</code>	Defines <code>&lt;key&gt;</code> to set <code>&lt;skip&gt;</code> to <code>&lt;value&gt;</code> (which must be a skip expression). If the variable
<code>.skip_gset:N</code>	does not exist, it is created globally at the point that the key is set up.
<code>.skip_gset:c</code> <hr/>	
<hr/> <code>.tl_set:N</code> <hr/>	<code>&lt;key&gt; .tl_set:N = &lt;token list variable&gt;</code>
<code>.tl_set:c</code>	Defines <code>&lt;key&gt;</code> to set <code>&lt;token list variable&gt;</code> to <code>&lt;value&gt;</code> . If the variable does not exist, it is
<code>.tl_gset:N</code>	created globally at the point that the key is set up.
<code>.tl_gset:c</code> <hr/>	
<hr/> <code>.tl_set_x:N</code> <hr/>	<code>&lt;key&gt; .tl_set_x:N = &lt;token list variable&gt;</code>
<code>.tl_set_x:c</code>	Defines <code>&lt;key&gt;</code> to set <code>&lt;token list variable&gt;</code> to <code>&lt;value&gt;</code> , which will be subjected to an x-type
<code>.tl_gset_x:N</code>	expansion ( <i>i.e.</i> using <code>\tl_set:Nx</code> ). If the variable does not exist, it is created globally
<code>.tl_gset_x:c</code> <hr/>	at the point that the key is set up.

---

<code>.undefine:</code>	<code>&lt;key&gt; .undefine:</code>
-------------------------	-------------------------------------

---

New: 2015-07-14	Removes the definition of the <code>&lt;key&gt;</code> within the current scope.
-----------------	--

---

---

<code>.value_forbidden:n</code>	<code>&lt;key&gt; .value_forbidden:n = true false</code>
---------------------------------	--

---

New: 2015-07-14	Specifies that <code>&lt;key&gt;</code> cannot receive a <code>&lt;value&gt;</code> when used. If a <code>&lt;value&gt;</code> is given then an error will be issued. Setting the property <code>false</code> cancels the restriction.
-----------------	--

---

---

<code>.value_required:n</code>	<code>&lt;key&gt; .value_required:n = true false</code>
--------------------------------	---

---

New: 2015-07-14	Specifies that <code>&lt;key&gt;</code> must receive a <code>&lt;value&gt;</code> when used. If a <code>&lt;value&gt;</code> is not given then an error will be issued. Setting the property <code>false</code> cancels the restriction.
-----------------	--

---

## 2 Sub-dividing keys

When creating large numbers of keys, it may be desirable to divide them into several sub-groups for a given module. This can be achieved either by adding a sub-division to the module name:

```
\keys_define:nn { module / subgroup }
{ key .code:n = code }
```

or to the key name:

```
\keys_define:nn { mymodule }
{ subgroup / key .code:n = code }
```

As illustrated, the best choice of token for sub-dividing keys in this way is `/`. This is because of the method that is used to represent keys internally. Both of the above code fragments set the same key, which has full name `module/subgroup/key`.

As illustrated in the next section, this subdivision is particularly relevant to making multiple choices.

## 3 Choice and multiple choice keys

The `l3keys` system supports two types of choice key, in which a series of pre-defined input values are linked to varying implementations. Choice keys are usually created so that the various values are mutually-exclusive: only one can apply at any one time. “Multiple” choice keys are also supported: these allow a selection of values to be chosen at the same time.

Mutually-exclusive choices are created by setting the `.choice:` property:

```
\keys_define:nn { mymodule }
{ key .choice: }
```

For keys which are set up as choices, the valid choices are generated by creating sub-keys of the choice key. This can be carried out in two ways.

In many cases, choices execute similar code which is dependant only on the name of the choice or the position of the choice in the list of all possibilities. Here, the keys can share the same code, and can be rapidly created using the `.choices:nn` property.

```

\keys_define:nn { mymodule }
{
  key .choices:nn =
    { choice-a, choice-b, choice-c }
    {
      You~gave~choice~'\tl_use:N \l_keys_choice_tl',~
      which~is~in~position~\int_use:N \l_keys_choice_int \c_space_tl
      in~the~list.
    }
}

```

The index `\l_keys_choice_int` in the list of choices starts at 1.

---

`\l_keys_choice_int`  
`\l_keys_choice_tl`

---

Inside the code block for a choice generated using `.choices:nn`, the variables `\l_keys_choice_tl` and `\l_keys_choice_int` are available to indicate the name of the current choice, and its position in the comma list. The position is indexed from 1. Note that, as with standard key code generated using `.code:n`, the value passed to the key (i.e. the choice name) is also available as `#1`.

On the other hand, it is sometimes useful to create choices which use entirely different code from one another. This can be achieved by setting the `.choice:` property of a key, then manually defining sub-keys.

```

\keys_define:nn { mymodule }
{
  key .choice:,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
}

```

It is possible to mix the two methods, but manually-created choices should *not* use `\l_keys_choice_tl` or `\l_keys_choice_int`. These variables do not have defined behaviour when used outside of code created using `.choices:nn` (i.e. anything might happen).

It is possible to allow choice keys to take values which have not previously been defined by adding code for the special `unknown` choice. The general behavior of the `unknown` key is described in Section 5. A typical example in the case of a choice would be to issue a custom error message:

```

\keys_define:nn { mymodule }
{
  key .choice:,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
  key / unknown .code:n =
    \msg_error:nnxxx { mymodule } { unknown-choice }
    { key } % Name of choice key
    { choice-a , choice-b , choice-c } % Valid choices
    { \exp_not:n {#1} } % Invalid choice given
}

```



```
%
%
}
```

Multiple choices are created in a very similar manner to mutually-exclusive choices, using the properties `.multichoice:` and `.multichoices:nn`. As with mutually exclusive choices, multiple choices are define as sub-keys. Thus both

```
\keys_define:nn { mymodule }
{
  key .multichoices:nn =
    { choice-a, choice-b, choice-c }
    {
      You~gave~choice~'\tl_use:N \l_keys_choice_tl',~
      which~is~in~position~
      \int_use:N \l_keys_choice_int \c_space_tl
      in~the~list.
    }
}
```

and

```
\keys_define:nn { mymodule }
{
  key .multichoice:,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
}
```

are valid.

When a multiple choice key is set

```
\keys_set:nn { mymodule }
{
  key = { a , b , c } % 'key' defined as a multiple choice
}
```

each choice is applied in turn, equivalent to a `clist` mapping or to applying each value individually:

```
\keys_set:nn { mymodule }
{
  key = a ,
  key = b ,
  key = c ,
}
```

Thus each separate choice will have passed to it the `\l_keys_choice_tl` and `\l_keys_choice_int` in exactly the same way as described for `.choices:nn`.

## 4 Setting keys

---

```
\keys_set:nn
\keys_set:(nV|nv|no)
```

---

Updated: 2015-11-07

---

```
\keys_set:nn {<module>} {<keyval list>}
```

Parses the  $\langle keyval list \rangle$ , and sets those keys which are defined for  $\langle module \rangle$ . The behaviour on finding an unknown key can be set by defining a special **unknown** key: this is illustrated later.

---

```
\l_keys_key_tl
\l_keys_path_tl
\l_keys_value_tl
```

---

Updated: 2015-07-14

---

For each key processed, information of the full *path* of the key, the *name* of the key and the *value* of the key is available within three token list variables. These may be used within the code of the key.

The *value* is everything after the =, which may be empty if no value was given. This is stored in `\l_keys_value_tl`, and is not processed in any way by `\keys_set:nn`.

The *path* of the key is a “full” description of the key, and is unique for each key. It consists of the module and full key name, thus for example

```
\keys_set:nn { mymodule } { key-a = some-value }
```

has path `mymodule/key-a` while

```
\keys_set:nn { mymodule } { subset / key-a = some-value }
```

has path `mymodule/subset/key-a`. This information is stored in `\l_keys_path_tl`, and will have been processed by `\tl_to_str:n`.

The *name* of the key is the part of the path after the last /, and thus is not unique. In the preceding examples, both keys have name `key-a` despite having different paths. This information is stored in `\l_keys_key_tl`, and will have been processed by `\tl_to_str:n`.

## 5 Handling of unknown keys

If a key has not previously been defined (is unknown), `\keys_set:nn` looks for a special **unknown** key for the same module, and if this is not defined raises an error indicating that the key name was unknown. This mechanism can be used for example to issue custom error texts.

```
\keys_define:nn { mymodule }
{
  unknown .code:n =
    You~tried~to~set~key~'\l_keys_key_tl'~to~'#1'.
}
```

---

```

\keys_set_known:nnN      \keys_set_known:nnN {<module>} {<keyval list>} {<tl>}
\keys_set_known:(nVN|nvN|noN)
\keys_set_known:nn
\keys_set_known:(nV|nv|no)

```

---

New: 2011-08-23  
Updated: 2017-05-27

---

In some cases, the desired behavior is to simply ignore unknown keys, collecting up information on these for later processing. The `\keys_set_known:nnN` function parses the `<keyval list>`, and sets those keys which are defined for `<module>`. Any keys which are unknown are not processed further by the parser. The key-value pairs for each *unknown* key name are stored in the `<tl>` in a comma-separated form (*i.e.* an edited version of the `<keyval list>`). The `\keys_set_known:nn` version skips this stage.

Use of `\keys_set_known:nnN` can be nested, with the correct residual `<keyval list>` returned at each stage.

## 6 Selective key setting

In some cases it may be useful to be able to select only some keys for setting, even though these keys have the same path. For example, with a set of keys defined using

```

\keys define:nn { mymodule }
{
  key-one   .code:n   = { \my_func:n {#1} } ,
  key-two   .tl_set:N = \l_my_a_tl          ,
  key-three .tl_set:N = \l_my_b_tl          ,
  key-four  .fp_set:N = \l_my_a_fp          ,
}

```

the use of `\keys_set:nn` attempts to set all four keys. However, in some contexts it may only be sensible to set some keys, or to control the order of setting. To do this, keys may be assigned to *groups*: arbitrary sets which are independent of the key tree. Thus modifying the example to read

```

\keys define:nn { mymodule }
{
  key-one   .code:n   = { \my_func:n {#1} } ,
  key-one   .groups:n = { first }           ,
  key-two   .tl_set:N = \l_my_a_tl          ,
  key-two   .groups:n = { first }           ,
  key-three .tl_set:N = \l_my_b_tl          ,
  key-three .groups:n = { second }          ,
  key-four  .fp_set:N = \l_my_a_fp          ,
}

```

assigns `key-one` and `key-two` to group `first`, `key-three` to group `second`, while `key-four` is not assigned to a group.

Selective key setting may be achieved either by selecting one or more groups to be made “active”, or by marking one or more groups to be ignored in key setting.

---

<code>\keys_set_filter:nnnN</code>	<code>\keys_set_filter:nnnN {&lt;module&gt;} {&lt;groups&gt;} {&lt;keyval list&gt;} {&lt;tl&gt;}</code>
<code>\keys_set_filter:(nnVN nnvN nnoN)</code>	
<code>\keys_set_filter:nnn</code>	
<code>\keys_set_filter:(nnV nnv nno)</code>	

---

New: 2013-07-14

Updated: 2017-05-27

---

Activates key filtering in an “opt-out” sense: keys assigned to any of the  $\langle groups \rangle$  specified are ignored. The  $\langle groups \rangle$  are given as a comma-separated list. Unknown keys are not assigned to any group and are thus always set. The key-value pairs for each key which is filtered out are stored in the  $\langle tl \rangle$  in a comma-separated form (*i.e.* an edited version of the  $\langle keyval list \rangle$ ). The `\keys_set_filter:nnn` version skips this stage.

Use of `\keys_set_filter:nnnN` can be nested, with the correct residual  $\langle keyval list \rangle$  returned at each stage.

---

<code>\keys_set_groups:nnn</code>	<code>\keys_set_groups:nnn {&lt;module&gt;} {&lt;groups&gt;} {&lt;keyval list&gt;}</code>
<code>\keys_set_groups:(nnV nnv nno)</code>	

---

New: 2013-07-14

Updated: 2017-05-27

---

Activates key filtering in an “opt-in” sense: only keys assigned to one or more of the  $\langle groups \rangle$  specified are set. The  $\langle groups \rangle$  are given as a comma-separated list. Unknown keys are not assigned to any group and are thus never set.

## 7 Utility functions for keys

---

<code>\keys_if_exist_p:nn</code> ★	<code>\keys_if_exist_p:nn {&lt;module&gt;} {&lt;key&gt;}</code>
<code>\keys_if_exist:nnTF</code> ★	<code>\keys_if_exist:nnTF {&lt;module&gt;} {&lt;key&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>

---

Updated: 2015-11-07 Tests if the  $\langle key \rangle$  exists for  $\langle module \rangle$ , *i.e.* if any code has been defined for  $\langle key \rangle$ .

---



---

<code>\keys_if_choice_exist_p:nnn</code> ★	<code>\keys_if_choice_exist_p:nnn {&lt;module&gt;} {&lt;key&gt;} {&lt;choice&gt;}</code>
<code>\keys_if_choice_exist:nnnTF</code> ★	<code>\keys_if_choice_exist:nnnTF {&lt;module&gt;} {&lt;key&gt;} {&lt;choice&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>

---

New: 2011-08-21

Updated: 2015-11-07

---

Tests if the  $\langle choice \rangle$  is defined for the  $\langle key \rangle$  within the  $\langle module \rangle$ , *i.e.* if any code has been defined for  $\langle key \rangle / \langle choice \rangle$ . The test is **false** if the  $\langle key \rangle$  itself is not defined.

---

<code>\keys_show:nn</code>	<code>\keys_show:nn {&lt;module&gt;} {&lt;key&gt;}</code>
----------------------------	---

---

Updated: 2015-08-09

---

Displays in the terminal the information associated to the  $\langle key \rangle$  for a  $\langle module \rangle$ , including the function which is used to actually implement it.

---

<code>\keys_log:nn</code>	<code>\keys_log:nn {&lt;module&gt;} {&lt;key&gt;}</code>
---------------------------	--

---

New: 2014-08-22

Updated: 2015-08-09

---

Writes in the log file the information associated to the  $\langle key \rangle$  for a  $\langle module \rangle$ . See also `\keys_show:nn` which displays the result in the terminal.

## 8 Low-level interface for parsing key–val lists

To re-cap from earlier, a key–value list is input of the form

```
KeyOne = ValueOne ,  
KeyTwo = ValueTwo ,  
KeyThree
```

where each key–value pair is separated by a comma from the rest of the list, and each key–value pair does not necessarily contain an equals sign or a value! Processing this type of input correctly requires a number of careful steps, to correctly account for braces, spaces and the category codes of separators.

While the functions described earlier are used as a high-level interface for processing such input, in special circumstances you may wish to use a lower-level approach. The low-level parsing system converts a *key–value list* into *keys* and associated *values*. After the parsing phase is completed, the resulting keys and values (or keys alone) are available for further processing. This processing is not carried out by the low-level parser itself, and so the parser requires the names of two functions along with the key–value list. One function is needed to process key–value pairs (it receives two arguments), and a second function is required for keys given without any value (it is called with a single argument).

The parser does not double # tokens or expand any input. Active tokens = and , appearing at the outer level of braces are converted to category “other” (12) so that the parser does not “miss” any due to category code changes. Spaces are removed from the ends of the keys and values. Keys and values which are given in braces have exactly one set removed (after space trimming), thus

```
key = {value here},
```

and

```
key = value here,
```

are treated identically.

---

**\keyval\_parse:NNn**

---

Updated: 2011-09-08

---

**\keyval\_parse:NNn**  $\langle function_1 \rangle$   $\langle function_2 \rangle$  { $\langle key-value list \rangle$ }

Parses the  $\langle key-value list \rangle$  into a series of  $\langle keys \rangle$  and associated  $\langle values \rangle$ , or keys alone (if no  $\langle value \rangle$  was given).  $\langle function_1 \rangle$  should take one argument, while  $\langle function_2 \rangle$  should absorb two arguments. After **\keyval\_parse:NNn** has parsed the  $\langle key-value list \rangle$ ,  $\langle function_1 \rangle$  is used to process keys given with no value and  $\langle function_2 \rangle$  is used to process keys given with a value. The order of the  $\langle keys \rangle$  in the  $\langle key-value list \rangle$  is preserved. Thus

```
\keyval_parse:NNn \function:n \function:nn
{ key1 = value1 , key2 = value2, key3 = , key4 }
```

is converted into an input stream

```
\function:nn { key1 } { value1 }
\function:nn { key2 } { value2 }
\function:nn { key3 } { }
\function:n { key4 }
```

Note that there is a difference between an empty value (an equals sign followed by nothing) and a missing value (no equals sign at all). Spaces are trimmed from the ends of the  $\langle key \rangle$  and  $\langle value \rangle$ , then one *outer* set of braces is removed from the  $\langle key \rangle$  and  $\langle value \rangle$  as part of the processing.

## Part XXI

# The l3fp package: floating points

A decimal floating point number is one which is stored as a significand and a separate exponent. The module implements expandably a wide set of arithmetic, trigonometric, and other operations on decimal floating point numbers, to be used within floating point expressions. Floating point expressions support the following operations with their usual precedence.

- Basic arithmetic: addition  $x + y$ , subtraction  $x - y$ , multiplication  $x * y$ , division  $x / y$ , square root  $\sqrt{x}$ , and parentheses.
  - Comparison operators:  $x < y$ ,  $x <= y$ ,  $x >? y$ ,  $x != y$  etc.
  - Boolean logic: sign  $\text{sign } x$ , negation  $!x$ , conjunction  $x \&\& y$ , disjunction  $x || y$ , ternary operator  $x ? y : z$ .
  - Exponentials:  $\exp x$ ,  $\ln x$ ,  $x^y$ .
  - Trigonometry:  $\sin x$ ,  $\cos x$ ,  $\tan x$ ,  $\cot x$ ,  $\sec x$ ,  $\csc x$  expecting their arguments in radians, and  $\text{sind } x$ ,  $\text{cosd } x$ ,  $\text{tand } x$ ,  $\text{cotd } x$ ,  $\text{secd } x$ ,  $\text{cscd } x$  expecting their arguments in degrees.
  - Inverse trigonometric functions:  $\text{asin } x$ ,  $\text{acos } x$ ,  $\text{atan } x$ ,  $\text{acot } x$ ,  $\text{asec } x$ ,  $\text{acsc } x$  giving a result in radians, and  $\text{asind } x$ ,  $\text{acosd } x$ ,  $\text{atand } x$ ,  $\text{acotd } x$ ,  $\text{asecd } x$ ,  $\text{acscd } x$  giving a result in degrees.
- (not yet) Hyperbolic functions and their inverse functions:  $\sinh x$ ,  $\cosh x$ ,  $\tanh x$ ,  $\coth x$ ,  $\text{sech } x$ ,  $\text{csch } x$ , and  $\text{asinh } x$ ,  $\text{acosh } x$ ,  $\text{atanh } x$ ,  $\text{acoth } x$ ,  $\text{asech } x$ ,  $\text{acsch } x$ .
- Extrema:  $\max(x, y, \dots)$ ,  $\min(x, y, \dots)$ ,  $\text{abs}(x)$ .
  - Rounding functions ( $n = 0$  by default,  $t = \text{NaN}$  by default):  $\text{trunc}(x, n)$  rounds towards zero,  $\text{floor}(x, n)$  rounds towards  $-\infty$ ,  $\text{ceil}(x, n)$  rounds towards  $+\infty$ ,  $\text{round}(x, n, t)$  rounds to the closest value, with ties rounded to an even value by default, towards zero if  $t = 0$ , towards  $+\infty$  if  $t > 0$  and towards  $-\infty$  if  $t < 0$ . And (not yet) modulo, and “quantize”.
  - Random numbers:  $\text{rand}()$ ,  $\text{randint}(m, n)$  in pdfTeX and LuaTeX engines.
  - Constants: `pi`, `deg` (one degree in radians).
  - Dimensions, automatically expressed in points, e.g., `pc` is 12.
  - Automatic conversion (no need for `\langle type \rangle\_use:N`) of integer, dimension, and skip variables to floating points, expressing dimensions in points and ignoring the stretch and shrink components of skips.

Floating point numbers can be given either explicitly (in a form such as `1.234e-34`, or `-.0001`), or as a stored floating point variable, which is automatically replaced by its current value. See section 9.1 for a description of what a floating point is, section 9.2 for details about how an expression is parsed, and section 9.3 to know what the various operations do. Some operations may raise exceptions (error messages), described in section 7.

An example of use could be the following.

`\LaTeX{}` can now compute:  $\frac{\sin(3.5)}{2} + 2 \cdot 10^{-3}$   
`= \ExplSyntaxOn \fp_to_decimal:n {sin 3.5 /2 + 2e-3} $.`

But in all fairness, this module is mostly meant as an underlying tool for higher-level commands. For example, one could provide a function to typeset nicely the result of floating point computations.

```
\documentclass{article}
\usepackage{xparse, siunitx}
\ExplSyntaxOn
\NewDocumentCommand { \calculus } { m }
{ \num { \fp_to_scientific:n {#1} } }
\ExplSyntaxOff
\begin{document}
\calculus { 2 pi * sin ( 2.3 ^ 5 ) }
\end{document}
```

## 1 Creating and initialising floating point variables

<code>\fp_new:N</code>	<code>\fp_new:N &lt;fp var&gt;</code>
<code>\fp_new:c</code>	Creates a new <i>&lt;fp var&gt;</i> or raises an error if the name is already taken. The declaration is global. The <i>&lt;fp var&gt;</i> is initially +0.
Updated: 2012-05-08	
<code>\fp_const:Nn</code>	<code>\fp_const:Nn &lt;fp var&gt; {&lt;floating point expression&gt;}</code>
<code>\fp_const:cn</code>	Creates a new constant <i>&lt;fp var&gt;</i> or raises an error if the name is already taken. The <i>&lt;fp var&gt;</i> is set globally equal to the result of evaluating the <i>&lt;floating point expression&gt;</i> .
Updated: 2012-05-08	
<code>\fp_zero:N</code>	<code>\fp_zero:N &lt;fp var&gt;</code>
<code>\fp_zero:c</code>	Sets the <i>&lt;fp var&gt;</i> to +0.
<code>\fp_gzero:N</code>	
<code>\fp_gzero:c</code>	
Updated: 2012-05-08	
<code>\fp_zero_new:N</code>	<code>\fp_zero_new:N &lt;fp var&gt;</code>
<code>\fp_zero_new:c</code>	Ensures that the <i>&lt;fp var&gt;</i> exists globally by applying <code>\fp_new:N</code> if necessary, then applies <code>\fp_(g)zero:N</code> to leave the <i>&lt;fp var&gt;</i> set to +0.
<code>\fp_gzero_new:N</code>	
<code>\fp_gzero_new:c</code>	
Updated: 2012-05-08	

## 2 Setting floating point variables

<code>\fp_set:Nn</code>	<code>\fp_set:Nn &lt;fp var&gt; {&lt;floating point expression&gt;}</code>
<code>\fp_set:cn</code>	Sets <i>&lt;fp var&gt;</i> equal to the result of computing the <i>&lt;floating point expression&gt;</i> .
<code>\fp_gset:Nn</code>	
<code>\fp_gset:cn</code>	
Updated: 2012-05-08	



<code>\fp_set_eq:NN</code>	<code>\fp_set_eq:NN &lt;fp var<sub>1</sub>&gt; &lt;fp var<sub>2</sub>&gt;</code>
<code>\fp_set_eq:(cN Nc cc)</code>	
<code>\fp_gset_eq:NN</code>	Sets the floating point variable $\langle fp\ var_1 \rangle$ equal to the current value of $\langle fp\ var_2 \rangle$ .
<code>\fp_gset_eq:(cN Nc cc)</code>	
Updated: 2012-05-08	

<code>\fp_add:Nn</code>	<code>\fp_add:Nn &lt;fp var&gt; {&lt;floating point expression&gt;}</code>
<code>\fp_add:cn</code>	
<code>\fp_gadd:Nn</code>	Adds the result of computing the $\langle floating\ point\ expression \rangle$ to the $\langle fp\ var \rangle$ .
<code>\fp_gadd:cn</code>	
Updated: 2012-05-08	

<code>\fp_sub:Nn</code>	<code>\fp_sub:Nn &lt;fp var&gt; {&lt;floating point expression&gt;}</code>
<code>\fp_sub:cn</code>	
<code>\fp_gsub:Nn</code>	Subtracts the result of computing the $\langle floating\ point\ expression \rangle$ from the $\langle fp\ var \rangle$ .
<code>\fp_gsub:cn</code>	
Updated: 2012-05-08	

### 3 Using floating point numbers

<code>\fp_eval:n</code> ★	<code>\fp_eval:n {&lt;floating point expression&gt;}</code>
New: 2012-05-08	
Updated: 2012-07-08	Evaluates the $\langle floating\ point\ expression \rangle$ and expresses the result as a decimal number with no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed, and integers are expressed without a decimal separator. The values $\pm\infty$ and NaN trigger an “invalid operation” exception. This function is identical to <code>\fp_to_decimal:n</code> .

<code>\fp_to_decimal:N</code> ★	<code>\fp_to_decimal:N &lt;fp var&gt;</code>
<code>\fp_to_decimal:c</code> ★	<code>\fp_to_decimal:n {&lt;floating point expression&gt;}</code>
<code>\fp_to_decimal:n</code> ★	Evaluates the $\langle floating\ point\ expression \rangle$ and expresses the result as a decimal number with no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed, and integers are expressed without a decimal separator. The values $\pm\infty$ and NaN trigger an “invalid operation” exception.
New: 2012-05-08	
Updated: 2012-07-08	

<code>\fp_to_dim:N</code> ★	<code>\fp_to_dim:N &lt;fp var&gt;</code>
<code>\fp_to_dim:c</code> ★	<code>\fp_to_dim:n {&lt;floating point expression&gt;}</code>
<code>\fp_to_dim:n</code> ★	Evaluates the $\langle floating\ point\ expression \rangle$ and expresses the result as a dimension (in pt) suitable for use in dimension expressions. The output is identical to <code>\fp_to_decimal:n</code> , with an additional trailing <code>pt</code> (both letter tokens). In particular, the result may be outside the range $[-2^{14} + 2^{-17}, 2^{14} - 2^{-17}]$ of valid T <sub>E</sub> X dimensions, leading to overflow errors if used as a dimension. The values $\pm\infty$ and NaN trigger an “invalid operation” exception.
Updated: 2016-03-22	

---

<code>\fp_to_int:N</code>	★	<code>\fp_to_int:N &lt;fp var&gt;</code>
<code>\fp_to_int:c</code>	★	<code>\fp_to_int:n {&lt;floating point expression&gt;}</code>
<code>\fp_to_int:n</code>	★	Evaluates the <i>&lt;floating point expression&gt;</i> , and rounds the result to the closest integer, rounding exact ties to an even integer. The result may be outside the range $[-2^{31} + 1, 2^{31} - 1]$ of valid TeX integers, leading to overflow errors if used in an integer expression. The values $\pm\infty$ and NaN trigger an “invalid operation” exception.

---

Updated: 2012-07-08

---



---

<code>\fp_to_scientific:N</code>	★	<code>\fp_to_scientific:N &lt;fp var&gt;</code>
<code>\fp_to_scientific:c</code>	★	<code>\fp_to_scientific:n {&lt;floating point expression&gt;}</code>
<code>\fp_to_scientific:n</code>	★	Evaluates the <i>&lt;floating point expression&gt;</i> and expresses the result in scientific notation:

---

New: 2012-05-08  
Updated: 2016-03-22

---

*<optional -><digit>.<15 digits>e<optional sign><exponent>*

The leading *<digit>* is non-zero except in the case of  $\pm 0$ . The values  $\pm\infty$  and NaN trigger an “invalid operation” exception. Normal category codes apply: thus the *e* is category code 11 (a letter).

---

<code>\fp_to_tl:N</code>	★	<code>\fp_to_tl:N &lt;fp var&gt;</code>
<code>\fp_to_tl:c</code>	★	<code>\fp_to_tl:n {&lt;floating point expression&gt;}</code>
<code>\fp_to_tl:n</code>	★	Evaluates the <i>&lt;floating point expression&gt;</i> and expresses the result in (almost) the shortest possible form. Numbers in the ranges $(0, 10^{-3})$ and $[10^{16}, \infty)$ are expressed in scientific notation with trailing zeros trimmed and no decimal separator when there is a single significant digit (this differs from <code>\fp_to_scientific:n</code> ). Numbers in the range $[10^{-3}, 10^{16})$ are expressed in a decimal notation without exponent, with trailing zeros trimmed, and no decimal separator for integer values (see <code>\fp_to_decimal:n</code> ). Negative numbers start with <i>-</i> . The special values $\pm 0$ , $\pm\infty$ and NaN are rendered as 0, -0, <i>inf</i> , <i>-inf</i> , and <i>nan</i> respectively. Normal category codes apply and thus <i>inf</i> or <i>nan</i> , if produced, are made up of letters.

---

Updated: 2016-03-22

---



---

<code>\fp_use:N</code>	★	<code>\fp_use:N &lt;fp var&gt;</code>
<code>\fp_use:c</code>	★	Inserts the value of the <i>&lt;fp var&gt;</i> into the input stream as a decimal number with no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed. Integers are expressed without a decimal separator. The values $\pm\infty$ and NaN trigger an “invalid operation” exception. This function is identical to <code>\fp_to_decimal:N</code> .

---

Updated: 2012-07-08

---

## 4 Floating point conditionals

---

<code>\fp_if_exist_p:N</code>	★	<code>\fp_if_exist_p:N &lt;fp var&gt;</code>
<code>\fp_if_exist_p:c</code>	★	<code>\fp_if_exist:NTF &lt;fp var&gt; {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\fp_if_exist:NTF</code>	★	Tests whether the <i>&lt;fp var&gt;</i> is currently defined. This does not check that the <i>&lt;fp var&gt;</i> really is a floating point variable.
<code>\fp_if_exist:cTF</code>	★	

---

Updated: 2012-05-08

---

---

<code>\fp_compare_p:nNn</code> ★ <code>\fp_compare:nNnTF</code> ★	<code>\fp_compare_p:nNn {&lt;fpexpr<sub>1</sub>&gt;} &lt;relation&gt; {&lt;fpexpr<sub>2</sub>&gt;}</code> <code>\fp_compare:nNnTF {&lt;fpexpr<sub>1</sub>&gt;} &lt;relation&gt; {&lt;fpexpr<sub>2</sub>&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>
--	---

---

Updated: 2012-05-08

Compares the  $\langle fpexpr_1 \rangle$  and the  $\langle fpexpr_2 \rangle$ , and returns **true** if the  $\langle relation \rangle$  is obeyed. Two floating point numbers  $x$  and  $y$  may obey four mutually exclusive relations:  $x \langle y, x=y, x \rangle y$ , or  $x$  and  $y$  are not ordered. The latter case occurs exactly when one or both operands is NaN, and this relation is denoted by the symbol ?. Note that a NaN is distinct from any value, even another NaN, hence  $x = x$  is not true for a NaN. To test if a value is NaN, compare it to an arbitrary number with the “not ordered” relation.

```

\fp_compare:nNnTF { <value> } ? { 0 }
{ } % <value> is nan
{ } % <value> is not nan

```

---

<code>\fp_compare_p:n</code> ★ <code>\fp_compare:nTF</code> ★	<code>\fp_compare_p:n</code> <code>{</code> <code>  &lt;fpexpr<sub>1</sub>&gt; &lt;relation<sub>1</sub>&gt;</code> <code>  ...</code> <code>  &lt;fpexpr<sub>N</sub>&gt; &lt;relation<sub>N</sub>&gt;</code> <code>  &lt;fpexpr<sub>N+1</sub>&gt;</code> <code>}</code> <code>\fp_compare:nTF</code> <code>{</code> <code>  &lt;fpexpr<sub>1</sub>&gt; &lt;relation<sub>1</sub>&gt;</code> <code>  ...</code> <code>  &lt;fpexpr<sub>N</sub>&gt; &lt;relation<sub>N</sub>&gt;</code> <code>  &lt;fpexpr<sub>N+1</sub>&gt;</code> <code>}</code> <code>{&lt;true code&gt;} {&lt;false code&gt;}</code>
--	---

---

Updated: 2012-12-14

Evaluates the  $\langle floating point expressions \rangle$  as described for `\fp_eval:n` and compares consecutive result using the corresponding  $\langle relation \rangle$ , namely it compares  $\langle intexpr_1 \rangle$  and  $\langle intexpr_2 \rangle$  using the  $\langle relation_1 \rangle$ , then  $\langle intexpr_2 \rangle$  and  $\langle intexpr_3 \rangle$  using the  $\langle relation_2 \rangle$ , until finally comparing  $\langle intexpr_N \rangle$  and  $\langle intexpr_{N+1} \rangle$  using the  $\langle relation_N \rangle$ . The test yields **true** if all comparisons are **true**. Each  $\langle floating point expression \rangle$  is evaluated only once. Contrarily to `\int_compare:nTF`, all  $\langle floating point expressions \rangle$  are computed, even if one comparison is **false**. Two floating point numbers  $x$  and  $y$  may obey four mutually exclusive relations:  $x \langle y, x=y, x \rangle y$ , or  $x$  and  $y$  are not ordered. The latter case occurs exactly when one or both operands is NaN, and this relation is denoted by the symbol ?. Each  $\langle relation \rangle$  can be any (non-empty) combination of  $<$ ,  $=$ ,  $>$ , and  $?$ , plus an optional leading ! (which negates the  $\langle relation \rangle$ ), with the restriction that the  $\langle relation \rangle$  may not start with  $?$ , as this symbol has a different meaning (in combination with  $:$ ) within floatin point expressions. The comparison  $x \langle relation \rangle y$  is then **true** if the  $\langle relation \rangle$  does not start with ! and the actual relation ( $<$ ,  $=$ ,  $>$ , or  $?$ ) between  $x$  and  $y$  appears within the  $\langle relation \rangle$ , or on the contrary if the  $\langle relation \rangle$  starts with ! and the relation between  $x$  and  $y$  does not appear within the  $\langle relation \rangle$ . Common choices of  $\langle relation \rangle$  include  $\geq$  (greater or equal),  $\neq$  (not equal),  $!?$  or  $\leq$  (comparable).

## 5 Floating point expression loops

<code>\fp_do_until:nNnn</code> ☆	<code>\fp_do_until:nNnn {&lt;fpexpr<sub>1</sub>&gt;} &lt;relation&gt; {&lt;fpexpr<sub>2</sub>&gt;} {&lt;code&gt;}</code>
New: 2012-08-16	Places the <i>&lt;code&gt;</i> in the input stream for T <sub>E</sub> X to process, and then evaluates the relationship between the two <i>&lt;floating point expressions&gt;</i> as described for <code>\fp_compare:nNnTF</code> . If the test is <b>false</b> then the <i>&lt;code&gt;</i> is inserted into the input stream again and a loop occurs until the <i>&lt;relation&gt;</i> is <b>true</b> .
<code>\fp_do_while:nNnn</code> ☆	<code>\fp_do_while:nNnn {&lt;fpexpr<sub>1</sub>&gt;} &lt;relation&gt; {&lt;fpexpr<sub>2</sub>&gt;} {&lt;code&gt;}</code>
New: 2012-08-16	Places the <i>&lt;code&gt;</i> in the input stream for T <sub>E</sub> X to process, and then evaluates the relationship between the two <i>&lt;floating point expressions&gt;</i> as described for <code>\fp_compare:nNnTF</code> . If the test is <b>true</b> then the <i>&lt;code&gt;</i> is inserted into the input stream again and a loop occurs until the <i>&lt;relation&gt;</i> is <b>false</b> .
<code>\fp_until_do:nNnn</code> ☆	<code>\fp_until_do:nNnn {&lt;fpexpr<sub>1</sub>&gt;} &lt;relation&gt; {&lt;fpexpr<sub>2</sub>&gt;} {&lt;code&gt;}</code>
New: 2012-08-16	Evaluates the relationship between the two <i>&lt;floating point expressions&gt;</i> as described for <code>\fp_compare:nNnTF</code> , and then places the <i>&lt;code&gt;</i> in the input stream if the <i>&lt;relation&gt;</i> is <b>false</b> . After the <i>&lt;code&gt;</i> has been processed by T <sub>E</sub> X the test is repeated, and a loop occurs until the test is <b>true</b> .
<code>\fp_while_do:nNnn</code> ☆	<code>\fp_while_do:nNnn {&lt;fpexpr<sub>1</sub>&gt;} &lt;relation&gt; {&lt;fpexpr<sub>2</sub>&gt;} {&lt;code&gt;}</code>
New: 2012-08-16	Evaluates the relationship between the two <i>&lt;floating point expressions&gt;</i> as described for <code>\fp_compare:nNnTF</code> , and then places the <i>&lt;code&gt;</i> in the input stream if the <i>&lt;relation&gt;</i> is <b>true</b> . After the <i>&lt;code&gt;</i> has been processed by T <sub>E</sub> X the test is repeated, and a loop occurs until the test is <b>false</b> .
<code>\fp_do_until:nn</code> ☆	<code>\fp_do_until:nn { &lt;fpexpr<sub>1</sub>&gt; &lt;relation&gt; &lt;fpexpr<sub>2</sub>&gt; } {&lt;code&gt;}</code>
New: 2012-08-16	Places the <i>&lt;code&gt;</i> in the input stream for T <sub>E</sub> X to process, and then evaluates the relationship between the two <i>&lt;floating point expressions&gt;</i> as described for <code>\fp_compare:nTF</code> . If the test is <b>false</b> then the <i>&lt;code&gt;</i> is inserted into the input stream again and a loop occurs until the <i>&lt;relation&gt;</i> is <b>true</b> .
<code>\fp_do_while:nn</code> ☆	<code>\fp_do_while:nn { &lt;fpexpr<sub>1</sub>&gt; &lt;relation&gt; &lt;fpexpr<sub>2</sub>&gt; } {&lt;code&gt;}</code>
New: 2012-08-16	Places the <i>&lt;code&gt;</i> in the input stream for T <sub>E</sub> X to process, and then evaluates the relationship between the two <i>&lt;floating point expressions&gt;</i> as described for <code>\fp_compare:nTF</code> . If the test is <b>true</b> then the <i>&lt;code&gt;</i> is inserted into the input stream again and a loop occurs until the <i>&lt;relation&gt;</i> is <b>false</b> .
<code>\fp_until_do:nn</code> ☆	<code>\fp_until_do:nn { &lt;fpexpr<sub>1</sub>&gt; &lt;relation&gt; &lt;fpexpr<sub>2</sub>&gt; } {&lt;code&gt;}</code>
New: 2012-08-16	Evaluates the relationship between the two <i>&lt;floating point expressions&gt;</i> as described for <code>\fp_compare:nTF</code> , and then places the <i>&lt;code&gt;</i> in the input stream if the <i>&lt;relation&gt;</i> is <b>false</b> . After the <i>&lt;code&gt;</i> has been processed by T <sub>E</sub> X the test is repeated, and a loop occurs until the test is <b>true</b> .

<hr/> <code>\fp_while_do:nn</code> ☆ <hr/>	<code>\fp_while_do:nn { &lt;fpexpr<sub>1</sub>&gt; &lt;relation&gt; &lt;fpexpr<sub>2</sub>&gt; } {&lt;code&gt;}</code>
New: 2012-08-16 <hr/>	Evaluates the relationship between the two <i>&lt;floating point expressions&gt;</i> as described for <code>\fp_compare:nTF</code> , and then places the <i>&lt;code&gt;</i> in the input stream if the <i>&lt;relation&gt;</i> is true. After the <i>&lt;code&gt;</i> has been processed by TeX the test is repeated, and a loop occurs until the test is false.

<hr/> <code>\fp_step_function:nnnN</code> ☆ <code>\fp_step_function:nnnc</code> ☆ <hr/>	<code>\fp_step_function:nnnN {&lt;initial value&gt;} {&lt;step&gt;} {&lt;final value&gt;} &lt;function&gt;</code>
New: 2016-11-21 Updated: 2016-12-06 <hr/>	This function first evaluates the <i>&lt;initial value&gt;</i> , <i>&lt;step&gt;</i> and <i>&lt;final value&gt;</i> , all of which should be floating point expressions. The <i>&lt;function&gt;</i> is then placed in front of each <i>&lt;value&gt;</i> from the <i>&lt;initial value&gt;</i> to the <i>&lt;final value&gt;</i> in turn (using <i>&lt;step&gt;</i> between each <i>&lt;value&gt;</i> ). The <i>&lt;step&gt;</i> must be non-zero. If the <i>&lt;step&gt;</i> is positive, the loop stops when the <i>&lt;value&gt;</i> becomes larger than the <i>&lt;final value&gt;</i> . If the <i>&lt;step&gt;</i> is negative, the loop stops when the <i>&lt;value&gt;</i> becomes smaller than the <i>&lt;final value&gt;</i> . The <i>&lt;function&gt;</i> should absorb one numerical argument. For example

```
\cs_set:Npn \my_func:n #1 { [I~saw~#1] \quad }
\fp_step_function:nnnN { 1.0 } { 0.1 } { 1.5 } \my_func:n
```

would print

```
[I saw 1.0] [I saw 1.1] [I saw 1.2] [I saw 1.3] [I saw 1.4] [I saw 1.5]
```

**TeXhackers note:** Due to rounding, it may happen that adding the *<step>* to the *<value>* does not change the *<value>*; such cases give an error, as they would otherwise lead to an infinite loop.

<hr/> <code>\fp_step_inline:nnnn</code> <hr/>	<code>\fp_step_inline:nnnn {&lt;initial value&gt;} {&lt;step&gt;} {&lt;final value&gt;} {&lt;code&gt;}</code>
New: 2016-11-21 Updated: 2016-12-06 <hr/>	This function first evaluates the <i>&lt;initial value&gt;</i> , <i>&lt;step&gt;</i> and <i>&lt;final value&gt;</i> , all of which should be floating point expressions. Then for each <i>&lt;value&gt;</i> from the <i>&lt;initial value&gt;</i> to the <i>&lt;final value&gt;</i> in turn (using <i>&lt;step&gt;</i> between each <i>&lt;value&gt;</i> ), the <i>&lt;code&gt;</i> is inserted into the input stream with <code>#1</code> replaced by the current <i>&lt;value&gt;</i> . Thus the <i>&lt;code&gt;</i> should define a function of one argument ( <code>#1</code> ).

<hr/> <code>\fp_step_variable:nnnNn</code> <hr/>	<code>\fp_step_variable:nnnNn {&lt;initial value&gt;} {&lt;step&gt;} {&lt;final value&gt;} &lt;tl var&gt; {&lt;code&gt;}</code>
New: 2017-04-12 <hr/>	This function first evaluates the <i>&lt;initial value&gt;</i> , <i>&lt;step&gt;</i> and <i>&lt;final value&gt;</i> , all of which should be floating point expressions. Then for each <i>&lt;value&gt;</i> from the <i>&lt;initial value&gt;</i> to the <i>&lt;final value&gt;</i> in turn (using <i>&lt;step&gt;</i> between each <i>&lt;value&gt;</i> ), the <i>&lt;code&gt;</i> is inserted into the input stream, with the <i>&lt;tl var&gt;</i> defined as the current <i>&lt;value&gt;</i> . Thus the <i>&lt;code&gt;</i> should make use of the <i>&lt;tl var&gt;</i> .

## 6 Some useful constants, and scratch variables

<hr/> <code>\c_zero_fp</code> <code>\c_minus_zero_fp</code> <hr/>	Zero, with either sign.
New: 2012-05-08 <hr/>	

<hr/> <code>\c_one_fp</code> <hr/>	One as an <code>fp</code> : useful for comparisons in some places.
<hr/> New: 2012-05-08 <hr/>	
<hr/> <code>\c_inf_fp</code> <code>\c_minus_inf_fp</code> <hr/>	Infinity, with either sign. These can be input directly in a floating point expression as <code>inf</code> and <code>-inf</code> .
<hr/> New: 2012-05-08 <hr/>	
<hr/> <code>\c_e_fp</code> <hr/>	The value of the base of the natural logarithm, $e = \exp(1)$ .
<hr/> Updated: 2012-05-08 <hr/>	
<hr/> <code>\c_pi_fp</code> <hr/>	The value of $\pi$ . This can be input directly in a floating point expression as <code>pi</code> .
<hr/> Updated: 2013-11-17 <hr/>	
<hr/> <code>\c_one_degree_fp</code> <hr/>	The value of $1^\circ$ in radians. Multiply an angle given in degrees by this value to obtain a result in radians. Note that trigonometric functions expecting an argument in radians or in degrees are both available. Within floating point expressions, this can be accessed as <code>deg</code> .
<hr/> New: 2012-05-08 Updated: 2013-11-17 <hr/>	
<hr/> <code>\l_tmpa_fp</code> <code>\l_tmpb_fp</code> <hr/>	Scratch floating points for local assignment. These are never used by the kernel code, and so are safe for use with any $\text{\LaTeX}3$ -defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<hr/> <code>\g_tmpa_fp</code> <code>\g_tmpb_fp</code> <hr/>	Scratch floating points for global assignment. These are never used by the kernel code, and so are safe for use with any $\text{\LaTeX}3$ -defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

## 7 Floating point exceptions

*The functions defined in this section are experimental, and their functionality may be altered or removed altogether.*

“Exceptions” may occur when performing some floating point operations, such as `0 / 0`, or `10 ** 1e9999`. The relevant IEEE standard defines 5 types of exceptions, of which we implement 4.

- *Overflow* occurs whenever the result of an operation is too large to be represented as a normal floating point number. This results in  $\pm\infty$ .
- *Underflow* occurs whenever the result of an operation is too close to 0 to be represented as a normal floating point number. This results in  $\pm 0$ .
- *Invalid operation* occurs for operations with no defined outcome, for instance `0/0` or `sin( $\infty$ )`, and results in a NaN. It also occurs for conversion functions whose target type does not have the appropriate infinite or NaN value (*e.g.*, `\fp_to_dim:n`).
- *Division by zero* occurs when dividing a non-zero number by 0, or when evaluating functions at poles, *e.g.*, `ln(0)` or `cot(0)`. This results in  $\pm\infty$ .

(*not yet*) *Inexact* occurs whenever the result of a computation is not exact, in other words, almost always. At the moment, this exception is entirely ignored in L<sup>A</sup>T<sub>E</sub>X3.

To each exception we associate a “flag”: `fp_overflow`, `fp_underflow`, `fp_invalid_operation` and `fp_division_by_zero`. The state of these flags can be tested and modified with commands from `l3flag`

By default, the “invalid operation” exception triggers an (expandable) error, and raises the corresponding flag. Other exceptions raise the corresponding flag but do not trigger an error. The behaviour when an exception occurs can be modified (using `\fp_trap:nn`) to either produce an error and raise the flag, or only raise the flag, or do nothing at all.

<code>\fp_trap:nn</code>	<code>\fp_trap:nn {(exception)} {(trap type)}</code>
New: 2012-07-19 Updated: 2017-02-13	All occurrences of the <i>&lt;exception&gt;</i> ( <code>overflow</code> , <code>underflow</code> , <code>invalid_operation</code> or <code>division_by_zero</code> ) within the current group are treated as <i>&lt;trap type&gt;</i> , which can be <ul style="list-style-type: none"> <li>• <b>none</b>: the <i>&lt;exception&gt;</i> will be entirely ignored, and leave no trace;</li> <li>• <b>flag</b>: the <i>&lt;exception&gt;</i> will turn the corresponding flag on when it occurs;</li> <li>• <b>error</b>: additionally, the <i>&lt;exception&gt;</i> will halt the T<sub>E</sub>X run and display some information about the current operation in the terminal.</li> </ul>

*This function is experimental, and may be altered or removed.*

---

```
flag_fp_overflow
flag_fp_underflow
flag_fp_invalid_operation
flag_fp_division_by_zero
```

---

Flags denoting the occurrence of various floating-point exceptions.

## 8 Viewing floating points

<code>\fp_show:N</code>	<code>\fp_show:N {fp var}</code>
<code>\fp_show:c</code>	<code>\fp_show:n {(floating point expression)}</code>
<code>\fp_show:n</code>	Evaluates the <i>&lt;floating point expression&gt;</i> and displays the result in the terminal.
New: 2012-05-08 Updated: 2015-08-07	

<code>\fp_log:N</code>	<code>\fp_log:N {fp var}</code>
<code>\fp_log:c</code>	<code>\fp_log:n {(floating point expression)}</code>
<code>\fp_log:n</code>	Evaluates the <i>&lt;floating point expression&gt;</i> and writes the result in the log file.
New: 2014-08-22 Updated: 2015-08-07	

## 9 Floating point expressions

### 9.1 Input of floating point numbers

We support four types of floating point numbers:

- $\pm m \cdot 10^n$ , a floating point number, with integer  $1 \leq m \leq 10^{16}$ , and  $-10000 \leq n \leq 10000$ ;
- $\pm 0$ , zero, with a given sign;
- $\pm \infty$ , infinity, with a given sign;
- NaN, is “not a number”, and can be either quiet or signalling (*not yet*: this distinction is currently unsupported);

Normal floating point numbers are stored in base 10, with up to 16 significant figures.

On input, a normal floating point number consists of:

- $\langle sign \rangle$ : a possibly empty string of + and - characters;
- $\langle significand \rangle$ : a non-empty string of digits together with zero or one dot;
- $\langle exponent \rangle$  optionally: the character e, followed by a possibly empty string of + and - tokens, and a non-empty string of digits.

The sign of the resulting number is + if  $\langle sign \rangle$  contains an even number of -, and - otherwise, hence, an empty  $\langle sign \rangle$  denotes a non-negative input. The stored significand is obtained from  $\langle significand \rangle$  by omitting the decimal separator and leading zeros, and rounding to 16 significant digits, filling with trailing zeros if necessary. In particular, the value stored is exact if the input  $\langle significand \rangle$  has at most 16 digits. The stored  $\langle exponent \rangle$  is obtained by combining the input  $\langle exponent \rangle$  (0 if absent) with a shift depending on the position of the significand and the number of leading zeros.

A special case arises if the resulting  $\langle exponent \rangle$  is either too large or too small for the floating point number to be represented. This results either in an overflow (the number is then replaced by  $\pm \infty$ ), or an underflow (resulting in  $\pm 0$ ).

The result is thus  $\pm 0$  if and only if  $\langle significand \rangle$  contains no non-zero digit (*i.e.*, consists only in characters 0, and an optional period), or if there is an underflow. Note that a single dot is currently a valid floating point number, equal to +0, but that is not guaranteed to remain true.

The  $\langle significand \rangle$  must be non-empty, so e1 and e-1 are not valid floating point numbers. Note that the latter could be mistaken with the difference of “e” and 1. To avoid confusions, the base of natural logarithms cannot be input as e and should be input as `exp(1)` or `\c_e_fp`.

Special numbers are input as follows:

- `inf` represents  $+\infty$ , and can be preceded by any  $\langle sign \rangle$ , yielding  $\pm \infty$  as appropriate.
- `nan` represents a (quiet) non-number. It can be preceded by any sign, but that sign is ignored.
- Any unrecognizable string triggers an error, and produces a NaN.

## 9.2 Precedence of operators

We list here all the operations supported in floating point expressions, in order of decreasing precedence: operations listed earlier bind more tightly than operations listed below them.

- Function calls (`sin`, `ln`, *etc*).



- Binary `**` and `^` (right associative).
- Unary `+`, `-`, `!`.
- Binary `*`, `/`, and implicit multiplication by juxtaposition (`2pi`, `3(4+5)`, *etc.*).
- Binary `+` and `-`.
- Comparisons `>=`, `!=`, `<?`, *etc.*
- Logical `and`, denoted by `&&`.
- Logical `or`, denoted by `||`.
- Ternary operator `?:` (right associative).

The precedence of operations can be overridden using parentheses. In particular, those precedences imply that

$$\begin{aligned}\sin 2\pi &= \sin(2\pi) = 0, \\ 2^{2\max(3,4)} &= 2^{2\max(3,4)} = 256.\end{aligned}$$

Functions are called on the value of their argument, contrarily to  $\TeX$  macros.

### 9.3 Operations

We now present the various operations allowed in floating point expressions, from the lowest precedence to the highest. When used as a truth value, a floating point expression is `false` if it is  $\pm 0$ , and `true` otherwise, including when it is `NaN`.

---

```
?: \fp_eval:n { <operand1> ? <operand2> : <operand3> }
```

---

The ternary operator `?:` results in `<operand2>` if `<operand1>` is true, and `<operand3>` if it is false (equal to  $\pm 0$ ). All three `<operands>` are evaluated in all cases. The operator is right associative, hence

```
\fp_eval:n
{
  1 + 3 > 4 ? 1 :
  2 + 4 > 5 ? 2 :
  3 + 5 > 6 ? 3 : 4
}
```

first tests whether  $1 + 3 > 4$ ; since this isn't true, the branch following `:` is taken, and  $2 + 4 > 5$  is compared; since this is true, the branch before `:` is taken, and everything else is (evaluated then) ignored. That allows testing for various cases in a concise manner, with the drawback that all computations are made in all cases.

---

```
|| \fp_eval:n { <operand1> <operand2> }
```

---

If `<operand1>` is true (non-zero), use that value, otherwise the value of `<operand2>`. Both `<operands>` are evaluated in all cases.

<hr/>	<code>\fp_eval:n { &lt;operand1&gt; &amp;&amp; &lt;operand2&gt; }</code>	
		If $\langle operand_1 \rangle$ is false (equal to $\pm 0$ ), use that value, otherwise the value of $\langle operand_2 \rangle$ . Both $\langle operands \rangle$ are evaluated in all cases.
<hr/>		
<code>&lt;</code>	<code>\fp_eval:n</code>	
<code>=</code>	<code>{</code>	
<code>&gt;</code>	<code>  &lt;operand1&gt; &lt;relation1&gt;</code>	
<code>?</code>	<code>  ...</code>	
	<code>  &lt;operandN&gt; &lt;relationN&gt;</code>	
Updated: 2013-12-14	<code>  &lt;operandN+1&gt;</code>	
	<code>}</code>	
		Each $\langle relation \rangle$ consists of a non-empty string of <code>&lt;</code> , <code>=</code> , <code>&gt;</code> , and <code>?</code> , optionally preceded by <code>!</code> , and may not start with <code>?</code> . This evaluates to $+1$ if all comparisons $\langle operand_i \rangle \langle relation_j \rangle$ are true, and $+0$ otherwise. All $\langle operands \rangle$ are evaluated in all cases. See <code>\fp_compare:nTF</code> for details.
<hr/>		
<code>+</code>	<code>\fp_eval:n { &lt;operand1&gt; + &lt;operand2&gt; }</code>	
<code>-</code>	<code>\fp_eval:n { &lt;operand1&gt; - &lt;operand2&gt; }</code>	
		Computes the sum or the difference of its two $\langle operands \rangle$ . The “invalid operation” exception occurs for $\infty - \infty$ . “Underflow” and “overflow” occur when appropriate.
<hr/>		
<code>*</code>	<code>\fp_eval:n { &lt;operand1&gt; * &lt;operand2&gt; }</code>	
<code>/</code>	<code>\fp_eval:n { &lt;operand1&gt; / &lt;operand2&gt; }</code>	
		Computes the product or the ratio of its two $\langle operands \rangle$ . The “invalid operation” exception occurs for $\infty/\infty$ , $0/0$ , or $0 * \infty$ . “Division by zero” occurs when dividing a finite non-zero number by $\pm 0$ . “Underflow” and “overflow” occur when appropriate.
<hr/>		
<code>+</code>	<code>\fp_eval:n { + &lt;operand&gt; }</code>	
<code>-</code>	<code>\fp_eval:n { - &lt;operand&gt; }</code>	
<code>!</code>	<code>\fp_eval:n { ! &lt;operand&gt; }</code>	
		The unary <code>+</code> does nothing, the unary <code>-</code> changes the sign of the $\langle operand \rangle$ , and <code>!</code> $\langle operand \rangle$ evaluates to 1 if $\langle operand \rangle$ is false and 0 otherwise (this is the <code>not</code> boolean function). Those operations never raise exceptions.
<hr/>		
<code>**</code>	<code>\fp_eval:n { &lt;operand1&gt; ** &lt;operand2&gt; }</code>	
<code>^</code>	<code>\fp_eval:n { &lt;operand1&gt; ^ &lt;operand2&gt; }</code>	
		Raises $\langle operand_1 \rangle$ to the power $\langle operand_2 \rangle$ . This operation is right associative, hence <code>2 ** 2 ** 3</code> equals $2^{2^3} = 256$ . If $\langle operand_1 \rangle$ is negative or $-0$ then: the result’s sign is $+$ if the $\langle operand_2 \rangle$ is infinite and $(-1)^p$ if the $\langle operand_2 \rangle$ is $p/q$ with $p$ integer and $q$ odd; the result is $+0$ if <code>abs(&lt;operand1&gt;)^&lt;operand2&gt;</code> evaluates to zero; in other cases the “invalid operation” exception occurs because the sign cannot be determined. “Division by zero” occurs when raising $\pm 0$ to a finite strictly negative power. “Underflow” and “overflow” occur when appropriate.
<hr/>		
<code>abs</code>	<code>\fp_eval:n { abs( &lt;fpexpr&gt; ) }</code>	
		Computes the absolute value of the $\langle fpexpr \rangle$ . This function does not raise any exception beyond those raised when computing its operand $\langle fpexpr \rangle$ . See also <code>\fp_abs:n</code> .

<hr/> <b>exp</b> <hr/>	<code>\fp_eval:n { exp( &lt;fpexpr&gt; ) }</code>	Computes the exponential of the $\langle fpexpr \rangle$ . “Underflow” and “overflow” occur when appropriate.
<hr/> <b>ln</b> <hr/>	<code>\fp_eval:n { ln( &lt;fpexpr&gt; ) }</code>	Computes the natural logarithm of the $\langle fpexpr \rangle$ . Negative numbers have no (real) logarithm, hence the “invalid operation” is raised in that case, including for $\ln(-0)$ . “Division by zero” occurs when evaluating $\ln(+0) = -\infty$ . “Underflow” and “overflow” occur when appropriate.
<hr/> <b>max</b> <b>min</b> <hr/>	<code>\fp_eval:n { max( &lt;fpexpr<sub>1</sub>&gt; , &lt;fpexpr<sub>2</sub>&gt; , ... ) }</code> <code>\fp_eval:n { min( &lt;fpexpr<sub>1</sub>&gt; , &lt;fpexpr<sub>2</sub>&gt; , ... ) }</code>	Evaluates each $\langle fpexpr \rangle$ and computes the largest (smallest) of those. If any of the $\langle fpexpr \rangle$ is a NaN, the result is NaN. Those operations do not raise exceptions.
<hr/> <b>round</b> <b>trunc</b> <b>ceil</b> <b>floor</b> <hr/>	<code>\fp_eval:n { round ( &lt;fpexpr&gt; ) }</code> <code>\fp_eval:n { round ( &lt;fpexpr<sub>1</sub>&gt; , &lt;fpexpr<sub>2</sub>&gt; ) }</code> <code>\fp_eval:n { round ( &lt;fpexpr<sub>1</sub>&gt; , &lt;fpexpr<sub>2</sub>&gt; , &lt;fpexpr<sub>3</sub>&gt; ) }</code>	Only <b>round</b> accepts a third argument. Evaluates $\langle fpexpr_1 \rangle = x$ and $\langle fpexpr_2 \rangle = n$ and $\langle fpexpr_3 \rangle = t$ then rounds $x$ to $n$ places. If $n$ is an integer, this rounds $x$ to a multiple of $10^{-n}$ ; if $n = +\infty$ , this always yields $x$ ; if $n = -\infty$ , this yields one of $\pm 0$ , $\pm\infty$ , or NaN; if $n$ is neither $\pm\infty$ nor an integer, then an “invalid operation” exception is raised. When $\langle fpexpr_2 \rangle$ is omitted, $n = 0$ , <i>i.e.</i> , $\langle fpexpr_1 \rangle$ is rounded to an integer. The rounding direction depends on the function. <ul style="list-style-type: none"> <li>• <b>round</b> yields the multiple of <math>10^{-n}</math> closest to <math>x</math>, with ties (<math>x</math> half-way between two such multiples) rounded as follows. If <math>t</math> is <b>nan</b> or not given the even multiple is chosen (“ties to even”), if <math>t = \pm 0</math> the multiple closest to 0 is chosen (“ties to zero”), if <math>t</math> is positive/negative the multiple closest to <math>\infty/-\infty</math> is chosen (“ties towards positive/negative infinity”).</li> <li>• <b>floor</b> yields the largest multiple of <math>10^{-n}</math> smaller or equal to <math>x</math> (“round towards negative infinity”);</li> <li>• <b>ceil</b> yields the smallest multiple of <math>10^{-n}</math> greater or equal to <math>x</math> (“round towards positive infinity”);</li> <li>• <b>trunc</b> yields a multiple of <math>10^{-n}</math> with the same sign as <math>x</math> and with the largest absolute value less than that of <math>x</math> (“round towards zero”).</li> </ul> <p>“Overflow” occurs if <math>x</math> is finite and the result is infinite (this can only happen if <math>\langle fpexpr_2 \rangle &lt; -9984</math>).</p>
<hr/> <b>sign</b> <hr/>	<code>\fp_eval:n { sign( &lt;fpexpr&gt; ) }</code>	Evaluates the $\langle fpexpr \rangle$ and determines its sign: $+1$ for positive numbers and for $+\infty$ , $-1$ for negative numbers and for $-\infty$ , $\pm 0$ for $\pm 0$ , and NaN for NaN. This operation does not raise exceptions.

---

<code>sin</code>	<code>\fp_eval:n { sin( &lt;fpexpr&gt; ) }</code>
<code>cos</code>	<code>\fp_eval:n { cos( &lt;fpexpr&gt; ) }</code>
<code>tan</code>	<code>\fp_eval:n { tan( &lt;fpexpr&gt; ) }</code>
<code>cot</code>	<code>\fp_eval:n { cot( &lt;fpexpr&gt; ) }</code>
<code>csc</code>	<code>\fp_eval:n { csc( &lt;fpexpr&gt; ) }</code>
<code>sec</code>	<code>\fp_eval:n { sec( &lt;fpexpr&gt; ) }</code>

---

Updated: 2013-11-17

---

Computes the sine, cosine, tangent, cotangent, cosecant, or secant of the  $\langle fpexpr \rangle$  given in radians. For arguments given in degrees, see `sind`, `cosd`, *etc.* Note that since  $\pi$  is irrational, `sin(8pi)` is not quite zero, while its analogue `sind(8 × 180)` is exactly zero. The trigonometric functions are undefined for an argument of  $\pm\infty$ , leading to the “invalid operation” exception. Additionally, evaluating tangent, cotangent, cosecant, or secant at one of their poles leads to a “division by zero” exception. “Underflow” and “overflow” occur when appropriate.

---

<code>sind</code>	<code>\fp_eval:n { sind( &lt;fpexpr&gt; ) }</code>
<code>cosd</code>	<code>\fp_eval:n { cosd( &lt;fpexpr&gt; ) }</code>
<code>tand</code>	<code>\fp_eval:n { tand( &lt;fpexpr&gt; ) }</code>
<code>cotd</code>	<code>\fp_eval:n { cotd( &lt;fpexpr&gt; ) }</code>
<code>cscd</code>	<code>\fp_eval:n { cscd( &lt;fpexpr&gt; ) }</code>
<code>secd</code>	<code>\fp_eval:n { secd( &lt;fpexpr&gt; ) }</code>

---

New: 2013-11-02

---

Computes the sine, cosine, tangent, cotangent, cosecant, or secant of the  $\langle fpexpr \rangle$  given in degrees. For arguments given in radians, see `sin`, `cos`, *etc.* Note that since  $\pi$  is irrational, `sin(8pi)` is not quite zero, while its analogue `sind(8 × 180)` is exactly zero. The trigonometric functions are undefined for an argument of  $\pm\infty$ , leading to the “invalid operation” exception. Additionally, evaluating tangent, cotangent, cosecant, or secant at one of their poles leads to a “division by zero” exception. “Underflow” and “overflow” occur when appropriate.

---

<code>asin</code>	<code>\fp_eval:n { asin( &lt;fpexpr&gt; ) }</code>
<code>acos</code>	<code>\fp_eval:n { acos( &lt;fpexpr&gt; ) }</code>
<code>acsc</code>	<code>\fp_eval:n { acsc( &lt;fpexpr&gt; ) }</code>
<code>asec</code>	<code>\fp_eval:n { asec( &lt;fpexpr&gt; ) }</code>

---

New: 2013-11-02

---

Computes the arcsine, arccosine, arccosecant, or arcsecant of the  $\langle fpexpr \rangle$  and returns the result in radians, in the range  $[-\pi/2, \pi/2]$  for `asin` and `acsc` and  $[0, \pi]$  for `acos` and `asec`. For a result in degrees, use `asind`, *etc.* If the argument of `asin` or `acos` lies outside the range  $[-1, 1]$ , or the argument of `acsc` or `asec` inside the range  $(-1, 1)$ , an “invalid operation” exception is raised. “Underflow” and “overflow” occur when appropriate.

---

<code>asind</code>	<code>\fp_eval:n { asind( &lt;fpexpr&gt; ) }</code>
<code>acosd</code>	<code>\fp_eval:n { acosd( &lt;fpexpr&gt; ) }</code>
<code>acscd</code>	<code>\fp_eval:n { acscd( &lt;fpexpr&gt; ) }</code>
<code>asecd</code>	<code>\fp_eval:n { asecd( &lt;fpexpr&gt; ) }</code>

---

New: 2013-11-02

---

Computes the arcsine, arccosine, arccosecant, or arcsecant of the  $\langle fpexpr \rangle$  and returns the result in degrees, in the range  $[-90, 90]$  for `asin` and `acsc` and  $[0, 180]$  for `acos` and `asec`. For a result in radians, use `asin`, *etc.* If the argument of `asin` or `acos` lies outside the range  $[-1, 1]$ , or the argument of `acsc` or `asec` inside the range  $(-1, 1)$ , an “invalid operation” exception is raised. “Underflow” and “overflow” occur when appropriate.

<b>atan</b>	<code>\fp_eval:n { atan( &lt;fpexpr&gt; ) }</code>
<b>acot</b>	<code>\fp_eval:n { atan( &lt;fpexpr<sub>1</sub>&gt; , &lt;fpexpr<sub>2</sub>&gt; ) }</code>
<hr/>	
<b>New: 2013-11-02</b>	<code>\fp_eval:n { acot( &lt;fpexpr&gt; ) }</code>
	<code>\fp_eval:n { acot( &lt;fpexpr<sub>1</sub>&gt; , &lt;fpexpr<sub>2</sub>&gt; ) }</code>

Those functions yield an angle in radians: **atand** and **acotd** are their analogs in degrees. The one-argument versions compute the arctangent or arccotangent of the  $\langle fpexpr \rangle$ : arctangent takes values in the range  $[-\pi/2, \pi/2]$ , and arccotangent in the range  $[0, \pi]$ . The two-argument arctangent computes the angle in polar coordinates of the point with Cartesian coordinates  $(\langle fpexpr_2 \rangle, \langle fpexpr_1 \rangle)$ : this is the arctangent of  $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$ , possibly shifted by  $\pi$  depending on the signs of  $\langle fpexpr_1 \rangle$  and  $\langle fpexpr_2 \rangle$ . The two-argument arccotangent computes the angle in polar coordinates of the point  $(\langle fpexpr_1 \rangle, \langle fpexpr_2 \rangle)$ , equal to the arccotangent of  $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$ , possibly shifted by  $\pi$ . Both two-argument functions take values in the wider range  $[-\pi, \pi]$ . The ratio  $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$  need not be defined for the two-argument arctangent: when both expressions yield  $\pm 0$ , or when both yield  $\pm \infty$ , the resulting angle is one of  $\{\pm\pi/4, \pm 3\pi/4\}$  depending on signs. Only the “underflow” exception can occur.

<b>atand</b>	<code>\fp_eval:n { atand( &lt;fpexpr&gt; ) }</code>
<b>acotd</b>	<code>\fp_eval:n { atand( &lt;fpexpr<sub>1</sub>&gt; , &lt;fpexpr<sub>2</sub>&gt; ) }</code>
<hr/>	
<b>New: 2013-11-02</b>	<code>\fp_eval:n { acotd( &lt;fpexpr&gt; ) }</code>
	<code>\fp_eval:n { acotd( &lt;fpexpr<sub>1</sub>&gt; , &lt;fpexpr<sub>2</sub>&gt; ) }</code>

Those functions yield an angle in degrees: **atand** and **acotd** are their analogs in radians. The one-argument versions compute the arctangent or arccotangent of the  $\langle fpexpr \rangle$ : arctangent takes values in the range  $[-90, 90]$ , and arccotangent in the range  $[0, 180]$ . The two-argument arctangent computes the angle in polar coordinates of the point with Cartesian coordinates  $(\langle fpexpr_2 \rangle, \langle fpexpr_1 \rangle)$ : this is the arctangent of  $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$ , possibly shifted by 180 depending on the signs of  $\langle fpexpr_1 \rangle$  and  $\langle fpexpr_2 \rangle$ . The two-argument arccotangent computes the angle in polar coordinates of the point  $(\langle fpexpr_1 \rangle, \langle fpexpr_2 \rangle)$ , equal to the arccotangent of  $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$ , possibly shifted by 180. Both two-argument functions take values in the wider range  $[-180, 180]$ . The ratio  $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$  need not be defined for the two-argument arctangent: when both expressions yield  $\pm 0$ , or when both yield  $\pm \infty$ , the resulting angle is one of  $\{\pm 45, \pm 135\}$  depending on signs. Only the “underflow” exception can occur.

<b>sqrt</b>	<code>\fp_eval:n { sqrt( &lt;fpexpr&gt; ) }</code>
-------------	--

**New: 2013-12-14** Computes the square root of the  $\langle fpexpr \rangle$ . The “invalid operation” is raised when the  $\langle fpexpr \rangle$  is negative; no other exception can occur. Special values yield  $\sqrt{-0} = -0$ ,  $\sqrt{+0} = +0$ ,  $\sqrt{+\infty} = +\infty$  and  $\sqrt{\text{NaN}} = \text{NaN}$ .

<hr/> <b>rand</b> <hr/>	<code>\fp_eval:n { rand() }</code>
<hr/> <small>New: 2016-12-05</small> <hr/>	Produces a pseudo-random floating-point number (multiple of $10^{-16}$ ) between 0 included and 1 excluded. Available in pdfTeX and LuaTeX engines only.
<p><b>TeXhackers note:</b> This is based on pseudo-random numbers provided by the engine’s primitive <code>\pdfuniformdeviate</code> in pdfTeX and <code>\uniformdeviate</code> in LuaTeX. The underlying code in pdfTeX and LuaTeX is based on Metapost, which follows an additive scheme recommended in Section 3.6 of “The Art of Computer Programming, Volume 2”.</p> <p>While we are more careful than <code>\uniformdeviate</code> to preserve uniformity of the underlying stream of 28-bit pseudo-random integers, these pseudo-random numbers should of course not be relied upon for serious numerical computations nor cryptography.</p> <p>The random seed can be queried using <code>\pdfrandomseed</code> and set using <code>\pdfsetrandomseed</code> (in LuaTeX <code>\randomseed</code> and <code>\setrandomseed</code>). While a 32-bit (signed) integer can be given as a seed, only the absolute value is used and any number beyond <math>2^{28}</math> is divided by an appropriate power of 2. We recommend using an integer in <math>[0, 2^{28} - 1]</math>.</p>	
<hr/> <b>randint</b> <hr/>	<code>\fp_eval:n { randint( &lt;fpexpr&gt; ) }</code>
<hr/> <small>New: 2016-12-05</small> <hr/>	<code>\fp_eval:n { randint( &lt;fpexpr<sub>12</sub></code>
	Produces a pseudo-random integer between 1 and <code>&lt;fpexpr&gt;</code> or between <code>&lt;fpexpr<sub>1 and <code>&lt;fpexpr<sub>2 inclusive. The bounds must be integers in the range <math>(-10^{16}, 10^{16})</math> and the first must be smaller or equal to the second. See <b>rand</b> for important comments on how these pseudo-random numbers are generated.</sub></code></sub></code>
<hr/> <b>inf</b> <hr/>	The special values $+\infty$ , $-\infty$ , and NaN are represented as <code>inf</code> , <code>-inf</code> and <code>nan</code> (see <code>\c_inf_fp</code> , <code>\c_minus_inf_fp</code> and <code>\c_nan_fp</code> ).
<hr/> <b>nan</b> <hr/>	
<hr/> <b>pi</b> <hr/>	The value of $\pi$ (see <code>\c_pi_fp</code> ).
<hr/> <b>deg</b> <hr/>	The value of $1^\circ$ in radians (see <code>\c_one_degree_fp</code> ).

<hr/>	
<code>em</code>	Those units of measurement are equal to their values in <code>pt</code> , namely
<code>ex</code>	
<code>in</code>	$1\text{in} = 72.27\text{pt}$
<code>pt</code>	$1\text{pt} = 1\text{pt}$
<code>pc</code>	
<code>cm</code>	$1\text{pc} = 12\text{pt}$
<code>mm</code>	
<code>dd</code>	$1\text{cm} = \frac{1}{2.54}\text{in} = 28.45275590551181\text{pt}$
<code>cc</code>	
<code>nd</code>	$1\text{mm} = \frac{1}{25.4}\text{in} = 2.845275590551181\text{pt}$
<code>nc</code>	
<code>bp</code>	$1\text{dd} = 0.376065\text{mm} = 1.07000856496063\text{pt}$
<code>sp</code>	$1\text{cc} = 12\text{dd} = 12.84010277952756\text{pt}$
<hr/>	
	$1\text{nd} = 0.375\text{mm} = 1.066978346456693\text{pt}$
	$1\text{nc} = 12\text{nd} = 12.80374015748031\text{pt}$
	$1\text{bp} = \frac{1}{72}\text{in} = 1.00375\text{pt}$
	$1\text{sp} = 2^{-16}\text{pt} = 1.52587890625e - 5\text{pt}.$

The values of the (font-dependent) units `em` and `ex` are gathered from  $\text{\TeX}$  when the surrounding floating point expression is evaluated.

<hr/>	
<code>true</code>	Other names for 1 and +0.
<code>false</code>	
<hr/>	

<hr/>	
<code>\fp_abs:n</code> ★	<code>\fp_abs:n</code> $\{\langle\textit{floating point expression}\rangle\}$
New: 2012-05-14	
Updated: 2012-07-08	
<hr/>	
	Evaluates the $\langle\textit{floating point expression}\rangle$ as described for <code>\fp_eval:n</code> and leaves the absolute value of the result in the input stream. This function does not raise any exception beyond those raised when evaluating its argument. Within floating point expressions, <code>abs()</code> can be used.
<hr/>	
<code>\fp_max:nn</code> ★	<code>\fp_max:nn</code> $\{\langle\textit{fp expression 1}\rangle\} \{\langle\textit{fp expression 2}\rangle\}$
<code>\fp_min:nn</code> ★	
New: 2012-09-26	
<hr/>	
	Evaluates the $\langle\textit{floating point expressions}\rangle$ as described for <code>\fp_eval:n</code> and leaves the resulting larger ( <code>max</code> ) or smaller ( <code>min</code> ) value in the input stream. This function does not raise any exception beyond those raised when evaluating its argument. Within floating point expressions, <code>max()</code> and <code>min()</code> can be used.

## 10 Disclaimer and roadmap

The package may break down if the escape character is among `0123456789_+`, or if it receives a  $\text{\TeX}$  primitive conditional affected by `\exp_not:N`.

The following need to be done. I'll try to time-order the items.

- Decide what exponent range to consider.
- Support signalling `nan`.

- Modulo and remainder, and rounding functions `quantize`, `quantize0`, `quantize+`, `quantize-`, `quantize=`, `round=`. Should the modulo also be provided as (catcode 12) `%`?
- `\fp_format:nn`  $\{\langle fpexpr \rangle\}$   $\{\langle format \rangle\}$ , but what should  $\langle format \rangle$  be? More general pretty printing?
- Add `and`, `or`, `xor`? Perhaps under the names `all`, `any`, and `xor`?
- Add `log(x, b)` for logarithm of  $x$  in base  $b$ .
- `hypot` (Euclidean length). Cartesian-to-polar transform.
- Hyperbolic functions `cosh`, `sinh`, `tanh`.
- Inverse hyperbolics.
- Base conversion, input such as `0xAB.CDEF`.
- Factorial (not with `!`), gamma function.
- Improve coefficients of the `sin` and `tan` series.
- Treat upper and lower case letters identically in identifiers, and ignore underscores.
- Add an `array(1,2,3)` and `i=complex(0,1)`.
- Provide an experimental `map` function? Perhaps easier to implement if it is a single character, `@sin(1,2)`?
- Provide `\fp_if_nan:nTF`, and an `isnan` function?
- Support keyword arguments?

`Pgfmath` also provides box-measurements (depth, height, width), but boxes are not possible expandably.

Bugs.

- Check that functions are monotonic when they should.
- Add exceptions to `?:`, `!<=>?`, `&&`, `||`, and `!`.
- Logarithms of numbers very close to 1 are inaccurate.
- When rounding towards  $-\infty$ , `\dim_to_fp:n`  $\{0pt\}$  should return  $-0$ , not  $+0$ .
- The result of  $(\pm 0) + (\pm 0)$ , of  $x + (-x)$ , and of  $(-x) + x$  should depend on the rounding mode.
- `0e9999999999` gives a T<sub>E</sub>X “number too large” error.
- Subnormals are not implemented.

Possible optimizations/improvements.

- Document that `l3trial/l3fp-types` introduces tools for adding new types.
- In subsection 9.1, write a grammar.



- It would be nice if the `parse` auxiliaries for each operation were set up in the corresponding module, rather than centralizing in `l3fp-parse`.
- Some functions should get an `_o` ending to indicate that they expand after their result.
- More care should be given to distinguish expandable/restricted expandable (auxiliary and internal) functions.
- The code for the `ternary` set of functions is ugly.
- There are many `~` missing in the doc to avoid bad line-breaks.
- The algorithm for computing the logarithm of the significand could be made to use a 5 terms Taylor series instead of 10 terms by taking  $c = 2000/([200x]+1) \in [10, 95]$  instead of  $c \in [1, 10]$ . Also, it would then be possible to simplify the computation of  $t$ . However, we would then have to hard-code the logarithms of 44 small integers instead of 9.
- Improve notations in the explanations of the division algorithm (`l3fp-basics`).
- Understand and document `\_fp\_basics\_pack\_weird\_low:NNNNw` and `\_fp\_basics\_pack\_weird\_high:NNNNNNNNw` better. Move the other `basics\_pack` auxiliaries to `l3fp-aux` under a better name.
- Find out if underflow can really occur for trigonometric functions, and redoc as appropriate.
- Add bibliography. Some of Kahan’s articles, some previous TeX fp packages, the international standards,...
- Also take into account the “inexact” exception?
- Support multi-character prefix operators (*e.g.*, `@/` or whatever)?

## Part XXII

# The l3sort package

## Sorting functions

### 1 Controlling sorting

L<sup>A</sup>T<sub>E</sub>X3 comes with a facility to sort list variables (sequences, token lists, or comma-lists) according to some user-defined comparison. For instance,

```
\clist_set:Nn \l_foo_clist { 3 , 01 , -2 , 5 , +1 }
\clist_sort:Nn \l_foo_clist
{
  \int_compare:nNnTF { #1 } > { #2 }
  { \sort_return_swapped: }
  { \sort_return_same: }
}
```

results in `\l_foo_clist` holding the values `{ -2 , 01 , +1 , 3 , 5 }` sorted in non-decreasing order.

The code defining the comparison should call `\sort_return_swapped:` if the two items given as `#1` and `#2` are not in the correct order, and otherwise it should call `\sort_return_same:` to indicate that the order of this pair of items should not be changed.

For instance, a *comparison code* consisting only of `\sort_return_same:` with no test yields a trivial sort: the final order is identical to the original order. Conversely, using a *comparison code* consisting only of `\sort_return_swapped:` reverses the list (in a fairly inefficient way).

**T<sub>E</sub>Xhackers note:** The current implementation is limited to sorting approximately 20000 items (40000 in LuaT<sub>E</sub>X), depending on what other packages are loaded.

Internally, the code from `l3sort` stores items in `\toks` registers allocated locally. Thus, the *comparison code* should not call `\newtoks` or other commands that allocate new `\toks` registers. On the other hand, altering the value of a previously allocated `\toks` register is not a problem.

## Part XXIII

# The l3tl-analysis package: analysing token lists

## 1 l3tl-analysis documentation

This module mostly provides internal functions for use in the l3regex module. However, it provides as a side-effect a user debugging function, very similar to the \ShowTokens macro from the ted package.

---

\tl\_show\_analysis:N  
\tl\_show\_analysis:n

---

New: 2017-05-26

\tl\_show\_analysis:n {<token list>}

Displays to the terminal the detailed decomposition of the <token list> into tokens, showing the category code of each character token, the meaning of control sequences and active characters, and the value of registers.

## Part XXIV

# The l3tl-build package: building token lists

## 1 l3tl-build documentation

This module provides no user function: it is meant for kernel use only.

There are two main ways of building token lists from individual tokens. Either in one go within an `x`-expanding assignment, or by repeatedly using `\tl_put_right:Nn`. The first method takes a linear time, but only allows expandable operations. The second method takes a time quadratic in the length of the token list, but allows expandable and non-expandable operations.

The goal of this module is to provide functions to build a token list piece by piece in linear time, while allowing non-expandable operations. This is achieved by abusing `\toks`: adding some tokens to the token list is done by storing them in a free token register (time  $O(1)$  for each such operation). Those token registers are only put together at the end, within an `x`-expanding assignment, which takes a linear time.<sup>5</sup> Of course, all this must be done in a group: we can't go and clobber the values of legitimate `\toks` used by L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>.

Since none of the current applications need the ability to insert material on the left of the token list, I have not implemented that. This could be done for instance by using odd-numbered `\toks` for the left part, and even-numbered `\toks` for the right part.

### 1.1 Internal functions

---

`\__tl_build:Nw`  
`\__tl_gbuild:Nw`  
`\__tl_build_x:Nw`  
`\__tl_gbuild_x:Nw`

---

`\__tl_build:Nw <tl var> ...`  
`\__tl_build_one:n {<tokens1>} ...`  
`\__tl_build_one:n {<tokens2>} ...`  
...  
`\__tl_build_end:`

Defines the `<tl var>` to contain the contents of `<tokens1>` followed by `<tokens2>`, *etc.* This is built in such a way to be more efficient than repeatedly using `\tl_put_right:Nn`. The code in “...” does not need to be expandable. The commands `\__tl_build:Nw` and `\__tl_build_end:` start and end a group. The assignment to the `<tl var>` occurs just after the end of that group, using `\tl_set:Nn`, `\tl_gset:Nn`, `\tl_set:Nx`, or `\tl_gset:Nx`.

---

`\__tl_build_one:n`  
`\__tl_build_one:(o|x)`

---

`\__tl_build_one:n {<tokens>}`

This function may only be used within the scope of a `\__tl_build:Nw` function. It adds the `<tokens>` on the right of the current token list.

---

`\__tl_build_end:`

---

Ends the scope started by `\__tl_build:Nw`, and performs the relevant assignment.

---

<sup>5</sup>If we run out of token registers, then the currently filled-up `\toks` are put together in a temporary token list, and cleared, and we ultimately use `\tl_put_right:Nx` to put those chunks together. Hence the true asymptotic is quadratic, with a very small constant.

## Part XXV

# The `l3regex` package: regular expressions in `TEX`

## 1 Regular expressions

The `l3regex` package provides regular expression testing, extraction of submatches, splitting, and replacement, all acting on token lists. The syntax of regular expressions is mostly a subset of the PCRE syntax (and very close to POSIX), with some additions due to the fact that `TEX` manipulates tokens rather than characters. For performance reasons, only a limited set of features are implemented. Notably, back-references are not supported.

Let us give a few examples. After

```
\tl_set:Nn \l_my_tl { That~cat. }
\regex_replace_once:nnN { at } { is } \l_my_tl
```

the token list variable `\l_my_tl` holds the text “`This cat.`”, where the first occurrence of “`at`” was replaced by “`is`”. A more complicated example is a pattern to emphasize each word and add a comma after it:

```
\regex_replace_all:nnN { \w+ } { \c{emph}\cB\{ \0 \cE\} , } \l_my_tl
```

The `\w` sequence represents any “word” character, and `+` indicates that the `\w` sequence should be repeated as many times as possible (at least once), hence matching a word in the input token list. In the replacement text, `\0` denotes the full match (here, a word). The command `\emph` is inserted using `\c{emph}`, and its argument `\0` is put between braces `\cB\{` and `\cE\}`.

If a regular expression is to be used several times, it can be compiled once, and stored in a regex variable using `\regex_const:Nn`. For example,

```
\regex_const:Nn \c_foo_regex { \c{begin} \cB. (\c[~BE].*) \cE. }
```

stores in `\c_foo_regex` a regular expression which matches the starting marker for an environment: `\begin`, followed by a begin-group token (`\cB.`), then any number of tokens which are neither begin-group nor end-group character tokens (`\c[~BE].*`), ending with an end-group token (`\cE.`). As explained in the next section, the parentheses “capture” the result of `\c[~BE].*`, giving us access to the name of the environment when doing replacements.

### 1.1 Syntax of regular expressions

We start with a few examples, and encourage the reader to apply `\regex_show:n` to these regular expressions.

- `Cat` matches the word “Cat” capitalized in this way, but also matches the beginning of the word “Cattle”: use `\bCat\b` to match a complete word only.
- `[abc]` matches one letter among “a”, “b”, “c”; the pattern `(a|b|c)` matches the same three possible letters (but see the discussion of submatches below).

- `[A-Za-z]*` matches any number (due to the quantifier `*`) of Latin letters (not accented).
- `\c{[A-Za-z]*}` matches a control sequence made of Latin letters.
- `\_[^\\_]*\\_` matches an underscore, any number of characters other than underscore, and another underscore; it is equivalent to `\_.*?\_` where `.` matches arbitrary characters and the lazy quantifier `*?` means to match as few characters as possible, thus avoiding matching underscores.
- `[+-]?\\d+` matches an explicit integer with at most one sign.
- `[+-\\_]*\\d+\\_*` matches an explicit integer with any number of `+` and `-` signs, with spaces allowed except within the mantissa, and surrounded by spaces.
- `[+-\\_]*(\\d+|\\d*\\.\\d+)\\_*` matches an explicit integer or decimal number; using `[.,]` instead of `\\.`  would allow the comma as a decimal marker.
- `[+-\\_]*(\\d+|\\d*\\.\\d+)\\_*((?i)pt|in|[cem]m|ex|[bs]p|[dn]d|[pcn]c)\\_*` matches an explicit dimension with any unit that  $\text{\TeX}$  knows, where `(?i)` means to treat lowercase and uppercase letters identically.
- `[+-\\_]*((?i)nan|inf|(\\d+|\\d*\\.\\d+)(\\_.*e[+-\\_]*\\d+)?)\\_*` matches an explicit floating point number or the special values `nan` and `inf` (with signs).
- `[+-\\_]*(\\d+|\\cC.)\\_*` matches an explicit integer or control sequence (without checking whether it is an integer variable).
- `\\G.*?\\K` at the beginning of a regular expression matches and discards (due to `\\K`) everything between the end of the previous match (`\\G`) and what is matched by the rest of the regular expression; this is useful in `\\regex_replace_all:nnN` when the goal is to extract matches or submatches in a finer way than with `\\regex_extract_all:nnN`.

While it is impossible for a regular expression to match only integer expressions, `[+-\\(\\)*\\d+\\)([+-*/][+-\\(\\)*\\d+\\)]*` matches among other things all valid integer expressions (made only with explicit integers). One should follow it with further testing.

Most characters match exactly themselves, with an arbitrary category code. Some characters are special and must be escaped with a backslash (*e.g.*, `\\*` matches a star character). Some escape sequences of the form backslash–letter also have a special meaning (for instance `\\d` matches any digit). As a rule,

- every alphanumeric character (`A–Z`, `a–z`, `0–9`) matches exactly itself, and should not be escaped, because `\\A`, `\\B`, ... have special meanings;
- non-alphanumeric printable ascii characters can (and should) always be escaped: many of them have special meanings (*e.g.*, use `\\(`, `\\)`, `\\?`, `\\.`);
- spaces should always be escaped (even in character classes);
- any other character may be escaped or not, without any effect: both versions match exactly that character.

Note that these rules play nicely with the fact that many non-alphanumeric characters are difficult to input into T<sub>E</sub>X under normal category codes. For instance, `\abc%` matches the characters `\abc%` (with arbitrary category codes), but does not match the control sequence `\abc` followed by a percent character. Matching control sequences can be done using the `\c{<regex>}` syntax (see below).

Any special character which appears at a place where its special behaviour cannot apply matches itself instead (for instance, a quantifier appearing at the beginning of a string), after raising a warning.

Characters.

`\x{hh...}` Character with hex code `hh...`

`\xhh` Character with hex code `hh`.

`\a` Alarm (hex 07).

`\e` Escape (hex 1B).

`\f` Form-feed (hex 0C).

`\n` New line (hex 0A).

`\r` Carriage return (hex 0D).

`\t` Horizontal tab (hex 09).

Character types.

`.` A single period matches any token.

`\d` Any decimal digit.

`\h` Any horizontal space character, equivalent to `[\ \^^I]`: space and tab.

`\s` Any space character, equivalent to `[\ \^^I\^^J\^^L\^^M]`.

`\v` Any vertical space character, equivalent to `[\^^J\^^K\^^L\^^M]`. Note that `\^^K` is a vertical space, but not a space, for compatibility with Perl.

`\w` Any word character, *i.e.*, alpha- numerics and underscore, equivalent to `[A-Za-z0-9\_]`.

`\D` Any token not matched by `\d`.

`\H` Any token not matched by `\h`.

`\N` Any token other than the `\n` character (hex 0A).

`\S` Any token not matched by `\s`.

`\V` Any token not matched by `\v`.

`\W` Any token not matched by `\w`.

Of those, `.`, `\D`, `\H`, `\N`, `\S`, `\V`, and `\W` match arbitrary control sequences.

Character classes match exactly one token in the subject.

`[...]` Positive character class. Matches any of the specified tokens.

[**^...**] Negative character class. Matches any token other than the specified characters.

**x-y** Within a character class, this denotes a range (can be used with escaped characters).

[:**<name>**:] Within a character class (one more set of brackets), this denotes the POSIX character class **<name>**, which can be **alnum**, **alpha**, **ascii**, **blank**, **cntrl**, **digit**, **graph**, **lower**, **print**, **punct**, **space**, **upper**, **word**, or **xdigit**.

[:**~<name>**:] Negative POSIX character class.

For instance, [**a-oq-z\cC.**] matches any lowercase latin letter except **p**, as well as control sequences (see below for a description of **\c**).

Quantifiers (repetition).

**?** 0 or 1, greedy.

**??** 0 or 1, lazy.

**\*** 0 or more, greedy.

**\*?** 0 or more, lazy.

**+** 1 or more, greedy.

**+?** 1 or more, lazy.

**{n}** Exactly *n*.

**{n,}** *n* or more, greedy.

**{n,}?** *n* or more, lazy.

**{n,m}** At least *n*, no more than *m*, greedy.

**{n,m}?** At least *n*, no more than *m*, lazy.

Anchors and simple assertions.

**\b** Word boundary: either the previous token is matched by **\w** and the next by **\W**, or the opposite. For this purpose, the ends of the token list are considered as **\W**.

**\B** Not a word boundary: between two **\w** tokens or two **\W** tokens (including the boundary).

**^** or **\A** Start of the subject token list.

**\$**, **\Z** or **\z** End of the subject token list.

**\G** Start of the current match. This is only different from **^** in the case of multiple matches: for instance **\regex\_count:nnN { \G a } { aaba } \l\_tmpa\_int** yields 2, but replacing **\G** by **^** would result in **\l\_tmpa\_int** holding the value 1.

Alternation and capturing groups.

**A|B|C** Either one of **A**, **B**, or **C**.

**(...)** Capturing group.

**(?:...)** Non-capturing group.



(?<|... ) Non-capturing group which resets the group number for capturing groups in each alternative. The following group is numbered with the first unused group number.

The `\c` escape sequence allows to test the category code of tokens, and match control sequences. Each character category is represented by a single uppercase letter:

- C for control sequences;
- B for begin-group tokens;
- E for end-group tokens;
- M for math shift;
- T for alignment tab tokens;
- P for macro parameter tokens;
- U for superscript tokens (up);
- D for subscript tokens (down);
- S for spaces;
- L for letters;
- O for others; and
- A for active characters.

The `\c` escape sequence is used as follows.

`\c{<regex>}` A control sequence whose *cname* matches the *<regex>*, anchored at the beginning and end, so that `\c{begin}` matches exactly `\begin`, and nothing else.

`\cX` Applies to the next object, which can be a character, character property, class, or group, and forces this object to only match tokens with category **X** (any of CBEMTPUDSLOA). For instance, `\cL[A-Z\d]` matches uppercase letters and digits of category code letter, `\cC.` matches any control sequence, and `\cO(abc)` matches `abc` where each character has category other.

`\c[XYZ]` Applies to the next object, and forces it to only match tokens with category **X**, **Y**, or **Z** (each being any of CBEMTPUDSLOA). For instance, `\c[LSO](..)` matches two tokens of category letter, space, or other.

`\c[^XYZ]` Applies to the next object and prevents it from matching any token with category **X**, **Y**, or **Z** (each being any of CBEMTPUDSLOA). For instance, `\c[^O]\d` matches digits which have any category different from other.

The category code tests can be used inside classes; for instance, `[\cO\d \c[LO][A-F]]` matches what  $\TeX$  considers as hexadecimal digits, namely digits with category other, or uppercase letters from **A** to **F** with category either letter or other. Within a group affected by a category code test, the outer test can be overridden by a nested test: for instance, `\cL(ab\cO\*cd)` matches `ab*cd` where all characters are of category letter, except `*` which has category other.

The `\u` escape sequence allows to insert the contents of a token list directly into a regular expression or a replacement, avoiding the need to escape special characters.

Namely, `\u{<tl var name>}` matches the exact contents of the token list `<tl var>`. Within a `\c{...}` control sequence matching, the `\u` escape sequence only expands its argument once, in effect performing `\tl_to_str:v`. Quantifiers are not supported directly: use a group.

The option `(?i)` makes the match case insensitive (identifying A–Z with a–z; no Unicode support yet). This applies until the end of the group in which it appears, and can be reverted using `(?-i)`. For instance, in `(?i)(a(?-i)b|c)d`, the letters `a` and `d` are affected by the `i` option. Characters within ranges and classes are affected individually: `(?i)[Y-\]` is equivalent to `[YZ\[\]yz]`, and `(?i)[^aeiou]` matches any character which is not a vowel. Neither character properties, nor `\c{...}` nor `\u{...}` are affected by the `i` option.

In character classes, only `[`, `^`, `-`, `]`, `\` and spaces are special, and should be escaped. Other non-alphanumeric characters can still be escaped without harm. Any escape sequence which matches a single character (`\d`, `\D`, *etc.*) is supported in character classes. If the first character is `^`, then the meaning of the character class is inverted; `^` appearing anywhere else in the range is not special. If the first character (possibly following a leading `^`) is `]` then it does not need to be escaped since ending the range there would make it empty. Ranges of characters can be expressed using `-`, for instance, `[\D 0-5]` and `[^6-9]` are equivalent.

Capturing groups are a means of extracting information about the match. Parenthesized groups are labelled in the order of their opening parenthesis, starting at 1. The contents of those groups corresponding to the “best” match (leftmost longest) can be extracted and stored in a sequence of token lists using for instance `\regex_extract_once:nnTF`.

The `\K` escape sequence resets the beginning of the match to the current position in the token list. This only affects what is reported as the full match. For instance,

```
\regex_extract_all:nnN { a \K . } { a123aaxyz } \l_foo_seq
```

results in `\l_foo_seq` containing the items `{1}` and `{a}`: the true matches are `{a1}` and `{aa}`, but they are trimmed by the use of `\K`. The `\K` command does not affect capturing groups: for instance,

```
\regex_extract_once:nnN { (. \K c)+ \d } { acbc3 } \l_foo_seq
```

results in `\l_foo_seq` containing the items `{c3}` and `{bc}`: the true match is `{acbc3}`, with first submatch `{bc}`, but `\K` resets the beginning of the match to the last position where it appears.

## 1.2 Syntax of the replacement text

Most of the features described in regular expressions do not make sense within the replacement text. Backslash introduces various special constructions, described further below:

- `\0` is the whole match;
- `\1` is the submatch that was matched by the first (capturing) group `(...)`; similarly for `\2`, ..., `\9` and `\g{<number>}`;
- `\_` inserts a space (spaces are ignored when not escaped);

- `\a, \e, \f, \n, \r, \t, \xhh, \x{hhh}` correspond to single characters as in regular expressions;
- `\c{<cs name>}` inserts a control sequence;
- `\c{<category>}<character>` (see below);
- `\u{<tl var name>}` inserts the contents of the `<tl var>` (see below).

Characters other than backslash and space are simply inserted in the result (but since the replacement text is first converted to a string, one should also escape characters that are special for T<sub>E</sub>X, for instance use `\#`). Non-alphanumeric characters can always be safely escaped with a backslash.

For instance,

```
\tl_set:Nn \l_my_tl { Hello,~world! }
\regex_replace_all:nnN { ([er]?l|o) . } { (\0--\1) } \l_my_tl
```

results in `\l_my_tl` holding `H(e1l--e1)(o,--o) w(or--o)(ld--l)!`

The submatches are numbered according to the order in which the opening parenthesis of capturing groups appear in the regular expression to match. The  $n$ -th submatch is empty if there are fewer than  $n$  capturing groups or for capturing groups that appear in alternatives that were not used for the match. In case a capturing group matches several times during a match (due to quantifiers) only the last match is used in the replacement text. Submatches always keep the same category codes as in the original token list.

The characters inserted by the replacement have category code 12 (other) by default, with the exception of space characters. Spaces inserted through `\_` have category code 10, while spaces inserted through `\x20` or `\x{20}` have category code 12. The escape sequence `\c` allows to insert characters with arbitrary category codes, as well as control sequences.

`\cX(...)` Produces the characters “...” with category `X`, which must be one of `CBEMTPUDSLOA` as in regular expressions. Parentheses are optional for a single character (which can be an escape sequence). When nested, the innermost category code applies, for instance `\cL(Hello\cS\ world)!` gives this text with standard category codes.

`\c{<text>}` Produces the control sequence with csname `<text>`. The `<text>` may contain references to the submatches `\0`, `\1`, and so on, as in the example for `\u` below.

The escape sequence `\u{<tl var name>}` allows to insert the contents of the token list with name `<tl var name>` directly into the replacement, giving an easier control of category codes. When nested in `\c{...}` and `\u{...}` constructions, the `\u` and `\c` escape sequences perform `\tl_to_str:v`, namely extract the value of the control sequence and turn it into a string. Matches can also be used within the arguments of `\c` and `\u`. For instance,

```
\tl_set:Nn \l_my_one_tl { first }
\tl_set:Nn \l_my_two_tl { \emph{second} }
\tl_set:Nn \l_my_tl { one , two , one , one }
\regex_replace_all:nnN { [,]+ } { \u{1_my_\0_tl} } \l_my_tl
```

results in `\l_my_tl` holding `first,\emph{second},first,first`.

### 1.3 Pre-compiling regular expressions

If a regular expression is to be used several times, it is better to compile it once rather than doing it each time the regular expression is used. The compiled regular expression is stored in a variable. All of the `l3regex` module's functions can be given their regular expression argument either as an explicit string or as a compiled regular expression.

---

<code>\regex_new:N</code>	<code>\regex_new:N &lt;regex var&gt;</code>
---------------------------	---

---

New: 2017-05-26

Creates a new *<regex var>* or raises an error if the name is already taken. The declaration is global. The *<regex var>* is initially such that it never matches.

---

<code>\regex_set:Nn</code>	<code>\regex_set:Nn &lt;regex var&gt; {&lt;regex&gt;}</code>
----------------------------	--

---

`\regex_gset:Nn`

`\regex_const:Nn`

New: 2017-05-26

Stores a compiled version of the *<regular expression>* in the *<regex var>*. For instance, this function can be used as

```
\regex_new:N \l_my_regex
\regex_set:Nn \l_my_regex { my\ (simple\ )? reg(ex|ular\ expression) }
```

The assignment is local for `\regex_set:Nn` and global for `\regex_gset:Nn`. Use `\regex_const:Nn` for compiled expressions which never change.

---

<code>\regex_show:n</code>	<code>\regex_show:n {&lt;regex&gt;}</code>
----------------------------	--

---

`\regex_show:N`

New: 2017-05-26

Shows how `l3regex` interprets the *<regex>*. For instance, `\regex_show:n {\A X|Y}` shows

```
+--branch
  anchor at start (\A)
  char code 88
+--branch
  char code 89
```

indicating that the anchor `\A` only applies to the first branch: the second branch is not anchored to the beginning of the match.

### 1.4 Matching

All regular expression functions are available in both `:n` and `:N` variants. The former require a “standard” regular expression, while the later require a compiled expression as generated by `\regex_(g)set:Nn`.

---

<code>\regex_match:nnTF</code>	<code>\regex_match:nnTF {&lt;regex&gt;} {&lt;token list&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>
--------------------------------	--

---

`\regex_match:NnTF`

New: 2017-05-26

Tests whether the *<regular expression>* matches any part of the *<token list>*. For instance,

```
\regex_match:nnTF { b [cde]* } { abecdcx } { TRUE } { FALSE }
\regex_match:nnTF { [b-dq-w] } { example } { TRUE } { FALSE }
```

leaves `TRUE` then `FALSE` in the input stream.

---

```
\regex_count:nnN
\regex_count:NnN
```

---

New: 2017-05-26

---

```
\regex_count:nnN {<regex>} {<token list>} <int var>
```

Sets *<int var>* within the current T<sub>E</sub>X group level equal to the number of times *<regular expression>* appears in *<token list>*. The search starts by finding the left-most longest match, respecting greedy and ungreedy operators. Then the search starts again from the character following the last character of the previous match, until reaching the end of the token list. Infinite loops are prevented in the case where the regular expression can match an empty token list: then we count one match between each pair of characters. For instance,

```
\int_new:N \l_foo_int
\regex_count:nnN { (b+|c) } { abbababcb } \l_foo_int
```

results in `\l_foo_int` taking the value 5.

## 1.5 Submatch extraction

---

```
\regex_extract_once:nnNTF
\regex_extract_once:NnNTF
```

---

New: 2017-05-26

---

```
\regex_extract_once:nnN {<regex>} {<token list>} <seq var>
\regex_extract_once:nnNTF {<regex>} {<token list>} <seq var> {<true code>} {<false code>}
```

Finds the first match of the *<regular expression>* in the *<token list>*. If it exists, the match is stored as the first item of the *<seq var>*, and further items are the contents of capturing groups, in the order of their opening parenthesis. The *<seq var>* is assigned locally. If there is no match, the *<seq var>* is cleared. The testing versions insert the *<true code>* into the input stream if a match was found, and the *<false code>* otherwise.

For instance, assume that you type

```
\regex_extract_once:nnNTF { \A(La)?TeX(!*)\Z } { LaTeX!!! } \l_foo_seq
{ true } { false }
```

Then the regular expression (anchored at the start with `\A` and at the end with `\Z`) must match the whole token list. The first capturing group, `(La)?`, matches `La`, and the second capturing group, `(!*)`, matches `!!!`. Thus, `\l_foo_seq` contains as a result the items `{LaTeX!!!}`, `{La}`, and `{!!!}`, and the `true` branch is left in the input stream. Note that the  $n$ -th item of `\l_foo_seq`, as obtained using `\seq_item:Nn`, correspond to the submatch numbered  $(n - 1)$  in functions such as `\regex_replace_once:nnN`.

---

```
\regex_extract_all:nnNTF
\regex_extract_all:NnNTF
```

---

New: 2017-05-26

---

```
\regex_extract_all:nnN {<regex>} {<token list>} <seq var>
\regex_extract_all:nnNTF {<regex>} {<token list>} <seq var> {<true code>} {<false code>}
```

Finds all matches of the *<regular expression>* in the *<token list>*, and stores all the submatch information in a single sequence (concatenating the results of multiple `\regex_extract_once:nnN` calls). The *<seq var>* is assigned locally. If there is no match, the *<seq var>* is cleared. The testing versions insert the *<true code>* into the input stream if a match was found, and the *<false code>* otherwise. For instance, assume that you type

```
\regex_extract_all:nnNTF { \w+ } { Hello,~world! } \l_foo_seq
{ true } { false }
```

Then the regular expression matches twice, the resulting sequence contains the two items `{Hello}` and `{world}`, and the `true` branch is left in the input stream.

---

<code>\regex_split:nnNTF</code>	<code>\regex_split:nnN {&lt;regular expression&gt;} {&lt;token list&gt;} &lt;seq var&gt;</code>
<code>\regex_split:NnNTF</code>	<code>\regex_split:nnNTF {&lt;regular expression&gt;} {&lt;token list&gt;} &lt;seq var&gt; {&lt;true code&gt;} {&lt;false code&gt;}</code>

---

New: 2017-05-26

---

Splits the *<token list>* into a sequence of parts, delimited by matches of the *<regular expression>*. If the *<regular expression>* has capturing groups, then the token lists that they match are stored as items of the sequence as well. The assignment to *<seq var>* is local. If no match is found the resulting *<seq var>* has the *<token list>* as its sole item. If the *<regular expression>* matches the empty token list, then the *<token list>* is split into single tokens. The testing versions insert the *<true code>* into the input stream if a match was found, and the *<false code>* otherwise. For example, after

```

\seq_new:N \l_path_seq
\regex_split:nnNTF { / } { the/path/for/this/file.tex } \l_path_seq
{ true } { false }

```

the sequence `\l_path_seq` contains the items `{the}`, `{path}`, `{for}`, `{this}`, and `{file.tex}`, and the `true` branch is left in the input stream.

## 1.6 Replacement

---

<code>\regex_replace_once:nnNTF</code>	<code>\regex_replace_once:nnN {&lt;regular expression&gt;} {&lt;replacement&gt;} &lt;tl var&gt;</code>
<code>\regex_replace_once:NnNTF</code>	<code>\regex_replace_once:nnNTF {&lt;regular expression&gt;} {&lt;replacement&gt;} &lt;tl var&gt; {&lt;true code&gt;} {&lt;false code&gt;}</code>

---

New: 2017-05-26

---

Searches for the *<regular expression>* in the *<token list>* and replaces the first match with the *<replacement>*. The result is assigned locally to *<tl var>*. In the *<replacement>*, `\0` represents the full match, `\1` represent the contents of the first capturing group, `\2` of the second, *etc.*

---

<code>\regex_replace_all:nnNTF</code>	<code>\regex_replace_all:nnN {&lt;regular expression&gt;} {&lt;replacement&gt;} &lt;tl var&gt;</code>
<code>\regex_replace_all:NnNTF</code>	<code>\regex_replace_all:nnNTF {&lt;regular expression&gt;} {&lt;replacement&gt;} &lt;tl var&gt; {&lt;true code&gt;} {&lt;false code&gt;}</code>

---

New: 2017-05-26

---

Replaces all occurrences of the *\regular expression* in the *<token list>* by the *<replacement>*, where `\0` represents the full match, `\1` represent the contents of the first capturing group, `\2` of the second, *etc.* Every match is treated independently, and matches cannot overlap. The result is assigned locally to *<tl var>*.

## 1.7 Bugs, misfeatures, future work, and other possibilities

The following need to be done now.

- Rewrite the documentation in a more ordered way, perhaps add a BNF?
- Additional error-checking to come.
- Clean up the use of messages.
- Cleaner error reporting in the replacement phase.
- Add tracing information.
- Detect attempts to use back-references and other non-implemented syntax.

- Test for the maximum register `\c_max_register_int`.
- Find out whether the fact that `\W` and friends match the end-marker leads to bugs. Possibly update `\_regex_item_reverse:n`.
- The empty `cs` should be matched by `\c{}`, not by `\c{csname.?endcsname\s?}`.

Code improvements to come.

- Shift arrays so that the useful information starts at position 1.
- Only build `.,` once.
- Use arrays for the left and right state stacks when compiling a regex.
- Should `\_regex_action_free_group:n` only be used for greedy `{n,}` quantifier? (I think not.)
- Quantifiers for `\u` and assertions.
- When matching, keep track of an explicit stack of `current_state` and `current_submatches`.
- If possible, when a state is reused by the same thread, kill other subthreads.
- Use an array rather than `\l\_regex_balance_tl` to build `\_regex_replacement_balance_one_match:n`.
- Reduce the number of epsilon-transitions in alternatives.
- Optimize simple strings: use less states (`abcade` should give two states, for `abc` and `ade`). [Does that really make sense?]
- Optimize groups with no alternative.
- Optimize states with a single `\_regex_action_free:n`.
- Optimize the use of `\_regex_action_success:` by inserting it in state 2 directly instead of having an extra transition.
- Optimize the use of `\int_step...` functions.
- Groups don't capture within regexes for `csnames`; optimize and document.
- Better “show” for anchors, properties, and catcode tests.
- Does `\K` really need a new state for itself?
- When compiling, use a boolean `in_cs` and less magic numbers.
- Instead of checking whether the character is special or alphanumeric using its character code, check if it is special in regexes with `\cs_if_exist` tests.

The following features are likely to be implemented at some point in the future.

- General look-ahead/behind assertions.
- Regex matching on external files.

- Conditional subpatterns with look ahead/behind: “if what follows is [...], then [...]”.
- `(*..)` and `(?..)` sequences to set some options.
- UTF-8 mode for pdfTeX.
- Newline conventions are not done. In particular, we should have an option for `.` not to match newlines. Also, `\A` should differ from `^`, and `\Z`, `\z` and `$` should differ.
- Unicode properties: `\p{..}` and `\P{..}`; `\X` which should match any “extended” Unicode sequence. This requires to manipulate a lot of data, probably using tree-boxes.
- Provide a syntax such as `\ur{1_my_regex}` to use an already-compiled regex in a more complicated regex. This makes regexes more easily composable.
- Allowing `\u{1_my_tl}` in more places, for instance as the number of repetitions in a quantifier.

The following features of PCRE or Perl may or may not be implemented.

- Callout with `(?C...)` or other syntax: some internal code changes make that possible, and it can be useful for instance in the replacement code to stop a regex replacement when some marker has been found; this raises the question of a potential `\regex_break`: and then of playing well with `\tl_map_break`: called from within the code in a regex. It also raises the question of nested calls to the regex machinery, which is a problem since `\fontdimen` are global.
- Conditional subpatterns (other than with a look-ahead or look-behind condition): this is non-regular, isn’t it?
- Named subpatterns: TeX programmers have lived so far without any need for named macro parameters.

The following features of PCRE or Perl will definitely not be implemented.

- Back-references: non-regular feature, this requires backtracking, which is prohibitively slow.
- Recursion: this is a non-regular feature.
- Atomic grouping, possessive quantifiers: those tools, mostly meant to fix catastrophic backtracking, are unnecessary in a non-backtracking algorithm, and difficult to implement.
- Subroutine calls: this syntactic sugar is difficult to include in a non-backtracking algorithm, in particular because the corresponding group should be treated as atomic.
- Backtracking control verbs: intrinsically tied to backtracking.
- `\ddd`, matching the character with octal code `ddd`: we already have `\x{...}` and the syntax is confusingly close to what we could have used for backreferences (`\1`, `\2`, ...), making it harder to produce useful error message.
- `\cx`, similar to TeX’s own `\^^x`.



- Comments:  $\text{\TeX}$  already has its own system for comments.
- $\backslash\text{Q}\dots\backslash\text{E}$  escaping: this would require to read the argument verbatim, which is not in the scope of this module.
- $\backslash\text{C}$  single byte in UTF-8 mode:  $\text{XeTeX}$  and  $\text{LuaTeX}$  serve us characters directly, and splitting those into bytes is tricky, encoding dependent, and most likely not useful anyways.

## Part XXVI

# The l3box package

## Boxes

There are three kinds of box operations: horizontal mode denoted with prefix `\hbox_`, vertical mode with prefix `\vbox_`, and the generic operations working in both modes with prefix `\box_`.

### 1 Creating and initialising boxes

---

<code>\box_new:N</code>	<code>\box_new:N &lt;box&gt;</code>
<code>\box_new:c</code>	Creates a new $\langle box \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle box \rangle$ is initially void.

---



---

<code>\box_clear:N</code>	<code>\box_clear:N &lt;box&gt;</code>
<code>\box_clear:c</code>	Clears the content of the $\langle box \rangle$ by setting the box equal to <code>\c_void_box</code> .
<code>\box_gclear:N</code>	
<code>\box_gclear:c</code>	

---



---

<code>\box_clear_new:N</code>	<code>\box_clear_new:N &lt;box&gt;</code>
<code>\box_clear_new:c</code>	Ensures that the $\langle box \rangle$ exists globally by applying <code>\box_new:N</code> if necessary, then applies <code>\box_(g)clear:N</code> to leave the $\langle box \rangle$ empty.
<code>\box_gclear_new:N</code>	
<code>\box_gclear_new:c</code>	

---



---

<code>\box_set_eq:NN</code>	<code>\box_set_eq:NN &lt;box<sub>1</sub>&gt; &lt;box<sub>2</sub>&gt;</code>
<code>\box_set_eq:(cN Nc cc)</code>	Sets the content of $\langle box_1 \rangle$ equal to that of $\langle box_2 \rangle$ .
<code>\box_gset_eq:NN</code>	
<code>\box_gset_eq:(cN Nc cc)</code>	

---



---

<code>\box_set_eq_clear:NN</code>	<code>\box_set_eq_clear:NN &lt;box<sub>1</sub>&gt; &lt;box<sub>2</sub>&gt;</code>
<code>\box_set_eq_clear:(cN Nc cc)</code>	Sets the content of $\langle box_1 \rangle$ within the current TeX group equal to that of $\langle box_2 \rangle$ , then clears $\langle box_2 \rangle$ globally.

---



---

<code>\box_gset_eq_clear:NN</code>	<code>\box_gset_eq_clear:NN &lt;box<sub>1</sub>&gt; &lt;box<sub>2</sub>&gt;</code>
<code>\box_gset_eq_clear:(cN Nc cc)</code>	Sets the content of $\langle box_1 \rangle$ equal to that of $\langle box_2 \rangle$ , then clears $\langle box_2 \rangle$ . These assignments are global.

---



---

<code>\box_if_exist_p:N</code> ★	<code>\box_if_exist_p:N &lt;box&gt;</code>
<code>\box_if_exist_p:c</code> ★	<code>\box_if_exist:NTF &lt;box&gt; {(true code)} {(false code)}</code>
<code>\box_if_exist:NTF</code> ★	Tests whether the $\langle box \rangle$ is currently defined. This does not check that the $\langle box \rangle$ really is a box.
<code>\box_if_exist:cTF</code> ★	

---

New: 2012-03-03

---

## 2 Using boxes

---

`\box_use:N`  
`\box_use:c`

---

`\box_use:N`  $\langle box \rangle$

Inserts the current content of the  $\langle box \rangle$  onto the current list for typesetting.

**TeXhackers note:** This is the TeX primitive `\copy`.

---

`\box_use_clear:N`  
`\box_use_clear:c`

---

`\box_use_clear:N`  $\langle box \rangle$

Inserts the current content of the  $\langle box \rangle$  onto the current list for typesetting, then globally clears the content of the  $\langle box \rangle$ .

**TeXhackers note:** This is the TeX primitive `\box`.

---

`\box_move_right:nn`  
`\box_move_left:nn`

---

`\box_move_right:nn`  $\{\langle dimexpr \rangle\} \{\langle box function \rangle\}$

This function operates in vertical mode, and inserts the material specified by the  $\langle box function \rangle$  such that its reference point is displaced horizontally by the given  $\langle dimexpr \rangle$  from the reference point for typesetting, to the right or left as appropriate. The  $\langle box function \rangle$  should be a box operation such as `\box_use:N \<box>` or a “raw” box specification such as `\vbox:n { xyz }`.

---

`\box_move_up:nn`  
`\box_move_down:nn`

---

`\box_move_up:nn`  $\{\langle dimexpr \rangle\} \{\langle box function \rangle\}$

This function operates in horizontal mode, and inserts the material specified by the  $\langle box function \rangle$  such that its reference point is displaced vertical by the given  $\langle dimexpr \rangle$  from the reference point for typesetting, up or down as appropriate. The  $\langle box function \rangle$  should be a box operation such as `\box_use:N \<box>` or a “raw” box specification such as `\vbox:n { xyz }`.

## 3 Measuring and setting box dimensions

---

`\box_dp:N`  
`\box_dp:c`

---

`\box_dp:N`  $\langle box \rangle$

Calculates the depth (below the baseline) of the  $\langle box \rangle$  in a form suitable for use in a  $\langle dimension expression \rangle$ .

**TeXhackers note:** This is the TeX primitive `\dp`.

---

`\box_ht:N`  
`\box_ht:c`

---

`\box_ht:N`  $\langle box \rangle$

Calculates the height (above the baseline) of the  $\langle box \rangle$  in a form suitable for use in a  $\langle dimension expression \rangle$ .

**TeXhackers note:** This is the TeX primitive `\ht`.

---

<code>\box_wd:N</code>	<code>\box_wd:N &lt;box&gt;</code>
<code>\box_wd:c</code>	Calculates the width of the <code>&lt;box&gt;</code> in a form suitable for use in a <code>&lt;dimension expression&gt;</code> .

---

**TeXhackers note:** This is the TeX primitive `\wd`.

---

<code>\box_set_dp:Nn</code>	<code>\box_set_dp:Nn &lt;box&gt; {&lt;dimension expression&gt;}</code>
<code>\box_set_dp:cn</code>	Set the depth (below the baseline) of the <code>&lt;box&gt;</code> to the value of the <code>{&lt;dimension expression&gt;}</code> . This is a global assignment.

---



---

<code>\box_set_ht:Nn</code>	<code>\box_set_ht:Nn &lt;box&gt; {&lt;dimension expression&gt;}</code>
<code>\box_set_ht:cn</code>	Set the height (above the baseline) of the <code>&lt;box&gt;</code> to the value of the <code>{&lt;dimension expression&gt;}</code> . This is a global assignment.

---



---

<code>\box_set_wd:Nn</code>	<code>\box_set_wd:Nn &lt;box&gt; {&lt;dimension expression&gt;}</code>
<code>\box_set_wd:cn</code>	Set the width of the <code>&lt;box&gt;</code> to the value of the <code>{&lt;dimension expression&gt;}</code> . This is a global assignment.

---

## 4 Box conditionals

---

<code>\box_if_empty_p:N</code> *	<code>\box_if_empty_p:N &lt;box&gt;</code>
<code>\box_if_empty_p:c</code> *	<code>\box_if_empty:NNTF &lt;box&gt; {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\box_if_empty:NNTF</code> *	Tests if <code>&lt;box&gt;</code> is a empty (equal to <code>\c_empty_box</code> ).
<code>\box_if_empty:cTF</code> *	

---



---

<code>\box_if_horizontal_p:N</code> *	<code>\box_if_horizontal_p:N &lt;box&gt;</code>
<code>\box_if_horizontal_p:c</code> *	<code>\box_if_horizontal:NNTF &lt;box&gt; {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\box_if_horizontal:NNTF</code> *	Tests if <code>&lt;box&gt;</code> is a horizontal box.
<code>\box_if_horizontal:cTF</code> *	

---



---

<code>\box_if_vertical_p:N</code> *	<code>\box_if_vertical_p:N &lt;box&gt;</code>
<code>\box_if_vertical_p:c</code> *	<code>\box_if_vertical:NNTF &lt;box&gt; {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\box_if_vertical:NNTF</code> *	Tests if <code>&lt;box&gt;</code> is a vertical box.
<code>\box_if_vertical:cTF</code> *	

---

## 5 The last box inserted

---

<code>\box_set_to_last:N</code>	<code>\box_set_to_last:N &lt;box&gt;</code>
<code>\box_set_to_last:c</code>	Sets the <code>&lt;box&gt;</code> equal to the last item (box) added to the current partial list, removing the item from the list at the same time. When applied to the main vertical list, the <code>&lt;box&gt;</code> is always void as it is not possible to recover the last added item.
<code>\box_gset_to_last:N</code>	
<code>\box_gset_to_last:c</code>	

---

## 6 Constant boxes

---

`\c_empty_box`

Updated: 2012-11-04

---

This is a permanently empty box, which is neither set as horizontal nor vertical.

## 7 Scratch boxes

---

`\l_tmpa_box`

`\l_tmpb_box`

Updated: 2012-11-04

---

Scratch boxes for local assignment. These are never used by the kernel code, and so are safe for use with any L<sup>A</sup>T<sub>E</sub>X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

---

`\g_tmpa_box`

`\g_tmpb_box`

---

Scratch boxes for global assignment. These are never used by the kernel code, and so are safe for use with any L<sup>A</sup>T<sub>E</sub>X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

## 8 Viewing box contents

---

`\box_show:N`

`\box_show:c`

Updated: 2012-05-11

---

`\box_show:N`  $\langle box \rangle$

Shows full details of the content of the  $\langle box \rangle$  in the terminal.

---

`\box_show:Nnn`

`\box_show:cnn`

New: 2012-05-11

---

`\box_show:Nnn`  $\langle box \rangle$   $\langle intexpr_1 \rangle$   $\langle intexpr_2 \rangle$

Display the contents of  $\langle box \rangle$  in the terminal, showing the first  $\langle intexpr_1 \rangle$  items of the box, and descending into  $\langle intexpr_2 \rangle$  group levels.

---

`\box_log:N`

`\box_log:c`

New: 2012-05-11

---

`\box_log:N`  $\langle box \rangle$

Writes full details of the content of the  $\langle box \rangle$  to the log.

---

`\box_log:Nnn`

`\box_log:cnn`

New: 2012-05-11

---

`\box_log:Nnn`  $\langle box \rangle$   $\langle intexpr_1 \rangle$   $\langle intexpr_2 \rangle$

Writes the contents of  $\langle box \rangle$  to the log, showing the first  $\langle intexpr_1 \rangle$  items of the box, and descending into  $\langle intexpr_2 \rangle$  group levels.

## 9 Boxes and color

All L<sup>A</sup>T<sub>E</sub>X3 boxes are “color safe”: a color set inside the box stops applying after the end of the box has occurred.

## 10 Horizontal mode boxes

<hr/> <code>\hbox:n</code> <hr/>	<code>\hbox:n {⟨contents⟩}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of natural width and then includes this box in the current list for typesetting.
<hr/> <code>\hbox_to_wd:nn</code> <hr/>	<code>\hbox_to_wd:nn {⟨dimexpr⟩} {⟨contents⟩}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of width $\langle dimexpr \rangle$ and then includes this box in the current list for typesetting.
<hr/> <code>\hbox_to_zero:n</code> <hr/>	<code>\hbox_to_zero:n {⟨contents⟩}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of zero width and then includes this box in the current list for typesetting.
<hr/> <code>\hbox_set:Nn</code> <code>\hbox_set:cn</code> <code>\hbox_gset:Nn</code> <code>\hbox_gset:cn</code> <hr/>	<code>\hbox_set:Nn ⟨box⟩ {⟨contents⟩}</code> Typesets the $\langle contents \rangle$ at natural width and then stores the result inside the $\langle box \rangle$ .
Updated: 2017-04-05	
<hr/> <code>\hbox_set_to_wd:Nnn</code> <code>\hbox_set_to_wd:cnn</code> <code>\hbox_gset_to_wd:Nnn</code> <code>\hbox_gset_to_wd:cnn</code> <hr/>	<code>\hbox_set_to_wd:Nnn ⟨box⟩ {⟨dimexpr⟩} {⟨contents⟩}</code> Typesets the $\langle contents \rangle$ to the width given by the $\langle dimexpr \rangle$ and then stores the result inside the $\langle box \rangle$ .
Updated: 2017-04-05	
<hr/> <code>\hbox_overlap_right:n</code> <hr/>	<code>\hbox_overlap_right:n {⟨contents⟩}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of zero width such that material protrudes to the right of the insertion point.
<hr/> <code>\hbox_overlap_left:n</code> <hr/>	<code>\hbox_overlap_left:n {⟨contents⟩}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of zero width such that material protrudes to the left of the insertion point.
<hr/> <code>\hbox_set:Nw</code> <code>\hbox_set:cw</code> <code>\hbox_set_end:</code> <code>\hbox_gset:Nw</code> <code>\hbox_gset:cw</code> <code>\hbox_gset_end:</code> <hr/>	<code>\hbox_set:Nw ⟨box⟩ ⟨contents⟩ \hbox_set_end:</code> Typesets the $\langle contents \rangle$ at natural width and then stores the result inside the $\langle box \rangle$ . In contrast to <code>\hbox_set:Nn</code> this function does not absorb the argument when finding the $\langle content \rangle$ , and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument.
Updated: 2017-04-05	

<code>\hbox_set_to_wd:Nnw</code>	<code>\hbox_set_to_wd:Nnw &lt;box&gt; {&lt;dimexpr&gt;} &lt;contents&gt; \hbox_set_end:</code>
<code>\hbox_set_to_wd:cnw</code>	
<code>\hbox_gset_to_wd:Nnw</code>	Typesets the $\langle contents \rangle$ to the width given by the $\langle dimexpr \rangle$ and then stores the result inside the $\langle box \rangle$ . In contrast to <code>\hbox_set_to_wd:Nnn</code> this function does not absorb the argument when finding the $\langle content \rangle$ , and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument
<code>\hbox_gset_to_wd:cnw</code>	
New: 2017-06-08	

<code>\hbox_unpack:N</code>	<code>\hbox_unpack:N &lt;box&gt;</code>
<code>\hbox_unpack:c</code>	Unpacks the content of the horizontal $\langle box \rangle$ , retaining any stretching or shrinking applied when the $\langle box \rangle$ was set.

**TeXhackers note:** This is the TeX primitive `\unhcopy`.

<code>\hbox_unpack_clear:N</code>	<code>\hbox_unpack_clear:N &lt;box&gt;</code>
<code>\hbox_unpack_clear:c</code>	Unpacks the content of the horizontal $\langle box \rangle$ , retaining any stretching or shrinking applied when the $\langle box \rangle$ was set. The $\langle box \rangle$ is then cleared globally.

**TeXhackers note:** This is the TeX primitive `\unhbox`.

## 11 Vertical mode boxes

Vertical boxes inherit their baseline from their contents. The standard case is that the baseline of the box is at the same position as that of the last item added to the box. This means that the box has no depth unless the last item added to it had depth. As a result most vertical boxes have a large height value and small or zero depth. The exception are `_top` boxes, where the reference point is that of the first item added. These tend to have a large depth and small height, although the latter is typically non-zero.

<code>\vbox:n</code>	<code>\vbox:n {&lt;contents&gt;}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a vertical box of natural height and includes this box in the current list for typesetting.
<code>\vbox_top:n</code>	<code>\vbox_top:n {&lt;contents&gt;}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a vertical box of natural height and includes this box in the current list for typesetting. The baseline of the box is equal to that of the <i>first</i> item added to the box.
<code>\vbox_to_ht:nn</code>	<code>\vbox_to_ht:nn {&lt;dimexpr&gt;} {&lt;contents&gt;}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a vertical box of height $\langle dimexpr \rangle$ and then includes this box in the current list for typesetting.
<code>\vbox_to_zero:n</code>	<code>\vbox_to_zero:n {&lt;contents&gt;}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a vertical box of zero height and then includes this box in the current list for typesetting.

---

<code>\vbox_set:Nn</code>	<code>\vbox_set:Nn &lt;box&gt; {&lt;contents&gt;}</code>
<code>\vbox_set:cn</code>	
<code>\vbox_gset:Nn</code>	Typesets the $\langle contents \rangle$ at natural height and then stores the result inside the $\langle box \rangle$ .
<code>\vbox_gset:cn</code>	
Updated: 2017-04-05	

---



---

<code>\vbox_set_top:Nn</code>	<code>\vbox_set_top:Nn &lt;box&gt; {&lt;contents&gt;}</code>
<code>\vbox_set_top:cn</code>	
<code>\vbox_gset_top:Nn</code>	Typesets the $\langle contents \rangle$ at natural height and then stores the result inside the $\langle box \rangle$ . The baseline of the box is equal to that of the <i>first</i> item added to the box.
<code>\vbox_gset_top:cn</code>	
Updated: 2017-04-05	

---



---

<code>\vbox_set_to_ht:Nnn</code>	<code>\vbox_set_to_ht:Nnn &lt;box&gt; {&lt;dimexpr&gt;} {&lt;contents&gt;}</code>
<code>\vbox_set_to_ht:cnn</code>	
<code>\vbox_gset_to_ht:Nnn</code>	Typesets the $\langle contents \rangle$ to the height given by the $\langle dimexpr \rangle$ and then stores the result inside the $\langle box \rangle$ .
<code>\vbox_gset_to_ht:cnn</code>	
Updated: 2017-04-05	

---



---

<code>\vbox_set:Nw</code>	<code>\vbox_set:Nw &lt;box&gt; &lt;contents&gt; \vbox_set_end:</code>
<code>\vbox_set:cw</code>	
<code>\vbox_set_end:</code>	Typesets the $\langle contents \rangle$ at natural height and then stores the result inside the $\langle box \rangle$ . In contrast to <code>\vbox_set:Nn</code> this function does not absorb the argument when finding the $\langle content \rangle$ , and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument.
<code>\vbox_gset:Nw</code>	
<code>\vbox_gset:cw</code>	
<code>\vbox_gset_end:</code>	
Updated: 2017-04-058	

---



---

<code>\vbox_set_to_ht:Nnw</code>	<code>\vbox_set_to_wd:Nnw &lt;box&gt; {&lt;dimexpr&gt;} &lt;contents&gt; \vbox_set_end:</code>
<code>\vbox_set_to_ht:cnw</code>	
<code>\vbox_gset_to_ht:Nnw</code>	Typesets the $\langle contents \rangle$ to the height given by the $\langle dimexpr \rangle$ and then stores the result inside the $\langle box \rangle$ . In contrast to <code>\vbox_set_to_ht:Nnn</code> this function does not absorb the argument when finding the $\langle content \rangle$ , and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument
<code>\vbox_gset_to_ht:cnw</code>	
New: 2017-06-08	

---



---

<code>\vbox_set_split_to_ht:NNn</code>	<code>\vbox_set_split_to_ht:NNn &lt;box<sub>12</sub></code>
Updated: 2011-10-22	
	Sets $\langle box_1 \rangle$ to contain material to the height given by the $\langle dimexpr \rangle$ by removing content from the top of $\langle box_2 \rangle$ (which must be a vertical box).

---

**TeXhackers note:** This is the TeX primitive `\vsplit`.

---

<code>\vbox_unpack:N</code>	<code>\vbox_unpack:N &lt;box&gt;</code>
<code>\vbox_unpack:c</code>	Unpacks the content of the vertical $\langle box \rangle$ , retaining any stretching or shrinking applied when the $\langle box \rangle$ was set.

---

**TeXhackers note:** This is the TeX primitive `\unvcopy`.



---

```
\vbox_unpack_clear:N
\vbox_unpack_clear:c
```

---

```
\vbox_unpack:N <box>
```

Unpacks the content of the vertical  $\langle box \rangle$ , retaining any stretching or shrinking applied when the  $\langle box \rangle$  was set. The  $\langle box \rangle$  is then cleared globally.

**T<sub>E</sub>Xhackers note:** This is the T<sub>E</sub>X primitive `\unvbox`.

## 11.1 Affine transformations

Affine transformations are changes which (informally) preserve straight lines. Simple translations are affine transformations, but are better handled in T<sub>E</sub>X by doing the translation first, then inserting an unmodified box. On the other hand, rotation and resizing of boxed material can best be handled by modifying boxes. These transformations are described here.

---

```
\box_autosize_to_wd_and_ht:Nnn
\box_autosize_to_wd_and_ht:Nnn
```

---

New: 2017-04-04

Resizes the  $\langle box \rangle$  to fit within the given  $\langle x-size \rangle$  (horizontally) and  $\langle y-size \rangle$  (vertically); both of the sizes are dimension expressions. The  $\langle y-size \rangle$  is the height only: it does not include any depth. The updated  $\langle box \rangle$  is an `hbox`, irrespective of the nature of the  $\langle box \rangle$  before the resizing is applied. The final size of the  $\langle box \rangle$  is the smaller of  $\{\langle x-size \rangle\}$  and  $\{\langle y-size \rangle\}$ , *i.e.* the result fits within the dimensions specified. Negative sizes cause the material in the  $\langle box \rangle$  to be reversed in direction, but the reference point of the  $\langle box \rangle$  is unchanged. Thus a negative  $\langle y-size \rangle$  results in the  $\langle box \rangle$  having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current T<sub>E</sub>X group level.

---

```
\box_autosize_to_wd_and_ht_plus_dp:Nnn
\box_autosize_to_wd_and_ht_plus_dp:Nnn
```

---

New: 2017-04-04

Resizes the  $\langle box \rangle$  to fit within the given  $\langle x-size \rangle$  (horizontally) and  $\langle y-size \rangle$  (vertically); both of the sizes are dimension expressions. The  $\langle y-size \rangle$  is the total vertical size (height plus depth). The updated  $\langle box \rangle$  is an `hbox`, irrespective of the nature of the  $\langle box \rangle$  before the resizing is applied. The final size of the  $\langle box \rangle$  is the smaller of  $\{\langle x-size \rangle\}$  and  $\{\langle y-size \rangle\}$ , *i.e.* the result fits within the dimensions specified. Negative sizes cause the material in the  $\langle box \rangle$  to be reversed in direction, but the reference point of the  $\langle box \rangle$  is unchanged. Thus a negative  $\langle y-size \rangle$  results in the  $\langle box \rangle$  having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current T<sub>E</sub>X group level.

---

```
\box_resize_to_ht:Nn
\box_resize_to_ht:cn
```

---

```
\box_resize_to_ht:Nn <box> {\langle y-size \rangle}
```

Resizes the  $\langle box \rangle$  to  $\langle y-size \rangle$  (vertically), scaling the horizontal size by the same amount;  $\langle y-size \rangle$  is a dimension expression. The  $\langle y-size \rangle$  is the height only: it does not include any depth. The updated  $\langle box \rangle$  is an `hbox`, irrespective of the nature of the  $\langle box \rangle$  before the resizing is applied. A negative  $\langle y-size \rangle$  causes the material in the  $\langle box \rangle$  to be reversed in direction, but the reference point of the  $\langle box \rangle$  is unchanged. Thus a negative  $\langle y-size \rangle$  results in the  $\langle box \rangle$  having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current T<sub>E</sub>X group level.

---

<code>\box_resize_to_ht_plus_dp:Nn</code>	<code>\box_resize_to_ht_plus_dp:Nn &lt;box&gt; {&lt;y-size&gt;}</code>
<code>\box_resize_to_ht_plus_dp:cn</code>	

---

Resizes the  $\langle box \rangle$  to  $\langle y-size \rangle$  (vertically), scaling the horizontal size by the same amount;  $\langle y-size \rangle$  is a dimension expression. The  $\langle y-size \rangle$  is the total vertical size (height plus depth). The updated  $\langle box \rangle$  is an `hbox`, irrespective of the nature of the  $\langle box \rangle$  before the resizing is applied. A negative  $\langle y-size \rangle$  causes the material in the  $\langle box \rangle$  to be reversed in direction, but the reference point of the  $\langle box \rangle$  is unchanged. Thus a negative  $\langle y-size \rangle$  results in the  $\langle box \rangle$  having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current TeX group level.

---

<code>\box_resize_to_wd:Nn</code>	<code>\box_resize_to_wd:Nn &lt;box&gt; {&lt;x-size&gt;}</code>
<code>\box_resize_to_wd:cn</code>	

---

Resizes the  $\langle box \rangle$  to  $\langle x-size \rangle$  (horizontally), scaling the vertical size by the same amount;  $\langle x-size \rangle$  is a dimension expression. The updated  $\langle box \rangle$  is an `hbox`, irrespective of the nature of the  $\langle box \rangle$  before the resizing is applied. A negative  $\langle x-size \rangle$  causes the material in the  $\langle box \rangle$  to be reversed in direction, but the reference point of the  $\langle box \rangle$  is unchanged. Thus a negative  $\langle x-size \rangle$  results in the  $\langle box \rangle$  having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current TeX group level.

---

<code>\box_resize_to_wd_and_ht:Nnn</code>	<code>\box_resize_to_wd_and_ht:Nnn &lt;box&gt; {&lt;x-size&gt;} {&lt;y-size&gt;}</code>
<code>\box_resize_to_wd_and_ht:cnn</code>	

---

New: 2014-07-03

Resizes the  $\langle box \rangle$  to  $\langle x-size \rangle$  (horizontally) and  $\langle y-size \rangle$  (vertically): both of the sizes are dimension expressions. The  $\langle y-size \rangle$  is the height only and does not include any depth. The updated  $\langle box \rangle$  is an `hbox`, irrespective of the nature of the  $\langle box \rangle$  before the resizing is applied. Negative sizes cause the material in the  $\langle box \rangle$  to be reversed in direction, but the reference point of the  $\langle box \rangle$  is unchanged. Thus a negative  $\langle y-size \rangle$  results in the  $\langle box \rangle$  having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current TeX group level.

---

<code>\box_resize_to_wd_and_ht_plus_dp:Nnn</code>	<code>\box_resize_to_wd_and_ht_plus_dp:Nnn &lt;box&gt; {&lt;x-size&gt;} {&lt;y-size&gt;}</code>
<code>\box_resize_to_wd_and_ht_plus_dp:cnn</code>	

---

New: 2017-04-06

Resizes the  $\langle box \rangle$  to  $\langle x-size \rangle$  (horizontally) and  $\langle y-size \rangle$  (vertically): both of the sizes are dimension expressions. The  $\langle y-size \rangle$  is the total vertical size (height plus depth). The updated  $\langle box \rangle$  is an `hbox`, irrespective of the nature of the  $\langle box \rangle$  before the resizing is applied. Negative sizes cause the material in the  $\langle box \rangle$  to be reversed in direction, but the reference point of the  $\langle box \rangle$  is unchanged. Thus a negative  $\langle y-size \rangle$  results in the  $\langle box \rangle$  having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current TeX group level.

---

<code>\box_rotate:Nn</code>	<code>\box_rotate:Nn &lt;box&gt; {&lt;angle&gt;}</code>
<code>\box_rotate:cn</code>	

---

Rotates the  $\langle box \rangle$  by  $\langle angle \rangle$  (in degrees) anti-clockwise about its reference point. The reference point of the updated box is moved horizontally such that it is at the left side of the smallest rectangle enclosing the rotated material. The updated  $\langle box \rangle$  is an `hbox`, irrespective of the nature of the  $\langle box \rangle$  before the rotation is applied. The rotation applies within the current TeX group level.

---

<code>\box_scale:Nnn</code>	<code>\box_scale:Nnn &lt;box&gt; {&lt;x-scale&gt;} {&lt;y-scale&gt;}</code>
<code>\box_scale:cnn</code>	Scales the $\langle box \rangle$ by factors $\langle x-scale \rangle$ and $\langle y-scale \rangle$ in the horizontal and vertical directions, respectively (both scales are integer expressions). The updated $\langle box \rangle$ is an <b>hbox</b> , irrespective of the nature of the $\langle box \rangle$ before the scaling is applied. Negative scalings cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-scale \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and <i>vice versa</i> . The resizing applies within the current $\text{\TeX}$ group level.

---

## 12 Primitive box conditionals

---

<code>\if_hbox:N</code> ★	<code>\if_hbox:N &lt;box&gt;</code> <code>  &lt;true code&gt;</code> <code>\else:</code> <code>  &lt;false code&gt;</code> <code>\fi:</code>
	Tests if $\langle box \rangle$ is a horizontal box.

---

**$\text{\TeX}$ hackers note:** This is the  $\text{\TeX}$  primitive `\ifhbox`.

---

<code>\if_vbox:N</code> ★	<code>\if_vbox:N &lt;box&gt;</code> <code>  &lt;true code&gt;</code> <code>\else:</code> <code>  &lt;false code&gt;</code> <code>\fi:</code>
	Tests if $\langle box \rangle$ is a vertical box.

---

**$\text{\TeX}$ hackers note:** This is the  $\text{\TeX}$  primitive `\ifvbox`.

---

<code>\if_box_empty:N</code> ★	<code>\if_box_empty:N &lt;box&gt;</code> <code>  &lt;true code&gt;</code> <code>\else:</code> <code>  &lt;false code&gt;</code> <code>\fi:</code>
	Tests if $\langle box \rangle$ is an empty (void) box.

---

**$\text{\TeX}$ hackers note:** This is the  $\text{\TeX}$  primitive `\ifvoid`.

## Part XXVII

# The l3coffins package

## Coffin code layer

The material in this module provides the low-level support system for coffins. For details about the design concept of a coffin, see the xcoffins module (in the l3experimental bundle).

## 1 Creating and initialising coffins

---

<code>\coffin_new:N</code>
<code>\coffin_new:c</code>
New: 2011-08-17

---

`\coffin_new:N`  $\langle coffin \rangle$

Creates a new  $\langle coffin \rangle$  or raises an error if the name is already taken. The declaration is global. The  $\langle coffin \rangle$  is initially empty.

---

<code>\coffin_clear:N</code>
<code>\coffin_clear:c</code>
New: 2011-08-17

---

`\coffin_clear:N`  $\langle coffin \rangle$

Clears the content of the  $\langle coffin \rangle$  within the current T<sub>E</sub>X group level.

---

<code>\coffin_set_eq:NN</code>
<code>\coffin_set_eq:(Nc cN cc)</code>
New: 2011-08-17

---

`\coffin_set_eq:NN`  $\langle coffin_1 \rangle$   $\langle coffin_2 \rangle$

Sets both the content and poles of  $\langle coffin_1 \rangle$  equal to those of  $\langle coffin_2 \rangle$  within the current T<sub>E</sub>X group level.

---

<code>\coffin_if_exist_p:N</code> ★
<code>\coffin_if_exist_p:c</code> ★
<code>\coffin_if_exist:NTF</code> ★
<code>\coffin_if_exist:cTF</code> ★
New: 2012-06-20

---

`\coffin_if_exist_p:N`  $\langle box \rangle$

`\coffin_if_exist:NTF`  $\langle box \rangle$   $\{\langle true\ code \rangle\}$   $\{\langle false\ code \rangle\}$

Tests whether the  $\langle coffin \rangle$  is currently defined.

## 2 Setting coffin content and poles

All coffin functions create and manipulate coffins locally within the current T<sub>E</sub>X group level.

---

<code>\hcoffin_set:Nn</code>
<code>\hcoffin_set:cn</code>
New: 2011-08-17
Updated: 2011-09-03

---

`\hcoffin_set:Nn`  $\langle coffin \rangle$   $\{\langle material \rangle\}$

Typesets the  $\langle material \rangle$  in horizontal mode, storing the result in the  $\langle coffin \rangle$ . The standard poles for the  $\langle coffin \rangle$  are then set up based on the size of the typeset material.

---

<code>\hcoffin_set:Nw</code>
<code>\hcoffin_set:cw</code>
<code>\hcoffin_set_end:</code>
New: 2011-09-10

---

`\hcoffin_set:Nw`  $\langle coffin \rangle$   $\langle material \rangle$  `\hcoffin_set_end:`

Typesets the  $\langle material \rangle$  in horizontal mode, storing the result in the  $\langle coffin \rangle$ . The standard poles for the  $\langle coffin \rangle$  are then set up based on the size of the typeset material. These functions are useful for setting the entire contents of an environment in a coffin.

---

`\vcoffin_set:Nnn`

`\vcoffin_set:cnn`

New: 2011-08-17

Updated: 2012-05-22

---

`\vcoffin_set:Nnn <coffin> {<width>} {<material>}`

Typesets the  $\langle material \rangle$  in vertical mode constrained to the given  $\langle width \rangle$  and stores the result in the  $\langle coffin \rangle$ . The standard poles for the  $\langle coffin \rangle$  are then set up based on the size of the typeset material.

---

`\vcoffin_set:Nnw`

`\vcoffin_set:cnw`

`\vcoffin_set_end:`

New: 2011-09-10

Updated: 2012-05-22

---

`\vcoffin_set:Nnw <coffin> {<width>} <material> \vcoffin_set_end:`

Typesets the  $\langle material \rangle$  in vertical mode constrained to the given  $\langle width \rangle$  and stores the result in the  $\langle coffin \rangle$ . The standard poles for the  $\langle coffin \rangle$  are then set up based on the size of the typeset material. These functions are useful for setting the entire contents of an environment in a coffin.

---

`\coffin_set_horizontal_pole:Nnn`

`\coffin_set_horizontal_pole:cnn`

New: 2012-07-20

---

`\coffin_set_horizontal_pole:Nnn <coffin>`

`{<pole>} {<offset>}`

Sets the  $\langle pole \rangle$  to run horizontally through the  $\langle coffin \rangle$ . The  $\langle pole \rangle$  is placed at the  $\langle offset \rangle$  from the bottom edge of the bounding box of the  $\langle coffin \rangle$ . The  $\langle offset \rangle$  should be given as a dimension expression.

---

`\coffin_set_vertical_pole:Nnn`

`\coffin_set_vertical_pole:cnn`

New: 2012-07-20

---

`\coffin_set_vertical_pole:Nnn <coffin> {<pole>} {<offset>}`

Sets the  $\langle pole \rangle$  to run vertically through the  $\langle coffin \rangle$ . The  $\langle pole \rangle$  is placed at the  $\langle offset \rangle$  from the left-hand edge of the bounding box of the  $\langle coffin \rangle$ . The  $\langle offset \rangle$  should be given as a dimension expression.

### 3 Joining and using coffins

---

`\coffin_attach:NnnNnnnn`

`\coffin_attach:(cnnNnnnn|Nnnncnnnn|cnnncnnnn)`

`\coffin_attach:NnnNnnnn`

`<coffin1> {<coffin1-pole1>} {<coffin1-pole2>}`

`<coffin2> {<coffin2-pole1>} {<coffin2-pole2>}`

`{<x-offset>} {<y-offset>}`

This function attaches  $\langle coffin_2 \rangle$  to  $\langle coffin_1 \rangle$  such that the bounding box of  $\langle coffin_1 \rangle$  is not altered, *i.e.*  $\langle coffin_2 \rangle$  can protrude outside of the bounding box of the coffin. The alignment is carried out by first calculating  $\langle handle_1 \rangle$ , the point of intersection of  $\langle coffin_1-pole_1 \rangle$  and  $\langle coffin_1-pole_2 \rangle$ , and  $\langle handle_2 \rangle$ , the point of intersection of  $\langle coffin_2-pole_1 \rangle$  and  $\langle coffin_2-pole_2 \rangle$ .  $\langle coffin_2 \rangle$  is then attached to  $\langle coffin_1 \rangle$  such that the relationship between  $\langle handle_1 \rangle$  and  $\langle handle_2 \rangle$  is described by the  $\langle x-offset \rangle$  and  $\langle y-offset \rangle$ . The two offsets should be given as dimension expressions.

---

```
\coffin_join:NnnNnnnn
\coffin_join:(cnnNnnnn|Nnncnnnn|cnnccnnnn)
```

---

```
\coffin_join:NnnNnnnn
  <coffin_1> {<coffin_1-pole_1>} {<coffin_1-pole_2>}
  <coffin_2> {<coffin_2-pole_1>} {<coffin_2-pole_2>}
  {<x-offset>} {<y-offset>}
```

This function joins  $\langle coffin_2 \rangle$  to  $\langle coffin_1 \rangle$  such that the bounding box of  $\langle coffin_1 \rangle$  may expand. The new bounding box covers the area containing the bounding boxes of the two original coffins. The alignment is carried out by first calculating  $\langle handle_1 \rangle$ , the point of intersection of  $\langle coffin_1-pole_1 \rangle$  and  $\langle coffin_1-pole_2 \rangle$ , and  $\langle handle_2 \rangle$ , the point of intersection of  $\langle coffin_2-pole_1 \rangle$  and  $\langle coffin_2-pole_2 \rangle$ .  $\langle coffin_2 \rangle$  is then attached to  $\langle coffin_1 \rangle$  such that the relationship between  $\langle handle_1 \rangle$  and  $\langle handle_2 \rangle$  is described by the  $\langle x-offset \rangle$  and  $\langle y-offset \rangle$ . The two offsets should be given as dimension expressions.

---

```
\coffin_typeset:Nnnnn
\coffin_typeset:cnnnn
```

---

Updated: 2012-07-20

```
\coffin_typeset:Nnnnn <coffin> {<pole_1>} {<pole_2>}
  {<x-offset>} {<y-offset>}
```

Typesetting is carried out by first calculating  $\langle handle \rangle$ , the point of intersection of  $\langle pole_1 \rangle$  and  $\langle pole_2 \rangle$ . The coffin is then typeset in horizontal mode such that the relationship between the current reference point in the document and the  $\langle handle \rangle$  is described by the  $\langle x-offset \rangle$  and  $\langle y-offset \rangle$ . The two offsets should be given as dimension expressions. Typesetting a coffin is therefore analogous to carrying out an alignment where the “parent” coffin is the current insertion point.

## 4 Measuring coffins

---

```
\coffin_dp:N
\coffin_dp:c
```

---

```
\coffin_dp:N <coffin>
```

Calculates the depth (below the baseline) of the  $\langle coffin \rangle$  in a form suitable for use in a  $\langle dimension expression \rangle$ .

---

```
\coffin_ht:N
\coffin_ht:c
```

---

```
\coffin_ht:N <coffin>
```

Calculates the height (above the baseline) of the  $\langle coffin \rangle$  in a form suitable for use in a  $\langle dimension expression \rangle$ .

---

```
\coffin_wd:N
\coffin_wd:c
```

---

```
\coffin_wd:N <coffin>
```

Calculates the width of the  $\langle coffin \rangle$  in a form suitable for use in a  $\langle dimension expression \rangle$ .

## 5 Coffin diagnostics

---

```
\coffin_display_handles:Nn
\coffin_display_handles:cn
```

---

Updated: 2011-09-02

```
\coffin_display_handles:Nn <coffin> {<color>}
```

This function first calculates the intersections between all of the  $\langle poles \rangle$  of the  $\langle coffin \rangle$  to give a set of  $\langle handles \rangle$ . It then prints the  $\langle coffin \rangle$  at the current location in the source, with the position of the  $\langle handles \rangle$  marked on the coffin. The  $\langle handles \rangle$  are labelled as part of this process: the locations of the  $\langle handles \rangle$  and the labels are both printed in the  $\langle color \rangle$  specified.

---

`\coffin_mark_handle:Nnnn`  
`\coffin_mark_handle:cnnn`  


---

Updated: 2011-09-02

---

`\coffin_mark_handle:Nnnn`  $\langle coffin \rangle$   $\{\langle pole_1 \rangle\}$   $\{\langle pole_2 \rangle\}$   $\{\langle color \rangle\}$

This function first calculates the  $\langle handle \rangle$  for the  $\langle coffin \rangle$  as defined by the intersection of  $\langle pole_1 \rangle$  and  $\langle pole_2 \rangle$ . It then marks the position of the  $\langle handle \rangle$  on the  $\langle coffin \rangle$ . The  $\langle handle \rangle$  are labelled as part of this process: the location of the  $\langle handle \rangle$  and the label are both printed in the  $\langle color \rangle$  specified.

---

`\coffin_show_structure:N`  
`\coffin_show_structure:c`  


---

Updated: 2015-08-01

---

`\coffin_show_structure:N`  $\langle coffin \rangle$

This function shows the structural information about the  $\langle coffin \rangle$  in the terminal. The width, height and depth of the typeset material are given, along with the location of all of the poles of the coffin.

Notice that the poles of a coffin are defined by four values: the  $x$  and  $y$  co-ordinates of a point that the pole passes through and the  $x$ - and  $y$ -components of a vector denoting the direction of the pole. It is the ratio between the later, rather than the absolute values, which determines the direction of the pole.

---

`\coffin_log_structure:N`  
`\coffin_log_structure:c`  


---

New: 2014-08-22  
Updated: 2015-08-01

---

`\coffin_log_structure:N`  $\langle coffin \rangle$

This function writes the structural information about the  $\langle coffin \rangle$  in the log file. See also `\coffin_show_structure:N` which displays the result in the terminal.

## 5.1 Constants and variables

---

`\c_empty_coffin`

---

A permanently empty coffin.

---

`\l_tmpa_coffin`  
`\l_tmpb_coffin`  


---

New: 2012-06-19

---

Scratch coffins for local assignment. These are never used by the kernel code, and so are safe for use with any L<sup>A</sup>T<sub>E</sub>X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

## Part XXVIII

# The l3color package

## Color support

This module provides support for color in L<sup>A</sup>T<sub>E</sub>X3. At present, the material here is mainly intended to support a small number of low-level requirements in other l3kernel modules.

### 1 Color in boxes

Controlling the color of text in boxes requires a small number of control functions, so that the boxed material uses the color at the point where it is set, rather than where it is used.

---

```
\color_group_begin:
\color_group_end:
```

---

New: 2011-09-03

---

```
\color_group_begin:
...
\color_group_end:
```

Creates a color group: one used to “trap” color settings.

---

```
\color_ensure_current:
```

---

New: 2011-09-03

---

```
\color_ensure_current:
```

Ensures that material inside a box uses the foreground color at the point where the box is set, rather than that in force when the box is used. This function should usually be used within a `\color_group_begin: ... \color_group_end:` group.

#### 1.1 Internal functions

---

```
\l__color_current_tl
```

---

New: 2017-06-15

---

The color currently active for foreground (text, *etc.*) material. This is stored in the form of a color model followed by one or more values in the range  $[0, 1]$ : these determine the color. The model and applicable data format must be one of the following:

- `gray`  $\langle gray \rangle$  Grayscale color with the  $\langle gray \rangle$  value running from 0 (fully black) to 1 (fully white)
- `cmyk`  $\langle cyan \rangle \langle magenta \rangle \langle yellow \rangle \langle black \rangle$
- `rgb`  $\langle red \rangle \langle green \rangle \langle blue \rangle$

Notice that the value are separated by spaces.

**T<sub>E</sub>Xhackers note:** This format is the native one for `dvips` color specials: other drivers are expected to convert to their own format when writing color data to output.



## Part XXIX

# The l3sys package

## System/runtime functions

### 1 The name of the job

---

`\c_sys_jobname_str`

---

New: 2015-09-19

---

Constant that gets the “job name” assigned when T<sub>E</sub>X starts.

**T<sub>E</sub>Xhackers note:** This copies the contents of the primitive `\jobname`. It is a constant that is set by T<sub>E</sub>X and should not be overwritten by the package.

### 2 Date and time

---

`\c_sys_minute_int`  
`\c_sys_hour_int`  
`\c_sys_day_int`  
`\c_sys_month_int`  
`\c_sys_year_int`

---

New: 2015-09-22

---

The date and time at which the current job was started: these are all reported as integers.

**T<sub>E</sub>Xhackers note:** Whilst the underlying primitives can be altered by the user, this interface to the time and date is intended to be the “real” values.

### 3 Engine

---

`\sys_if_engine luatex_p:` ★  
`\sys_if_engine luatex:` *TF* ★  
`\sys_if_engine pdftex_p:` ★  
`\sys_if_engine pdftex:` *TF* ★  
`\sys_if_engine ptex_p:` ★  
`\sys_if_engine ptex:` *TF* ★  
`\sys_if_engine uptex_p:` ★  
`\sys_if_engine uptex:` *TF* ★  
`\sys_if_engine xetex_p:` ★  
`\sys_if_engine xetex:` *TF* ★

---

New: 2015-09-07

---

`\sys_if_engine pdftex:TF` *{(true code)}* *{(false code)}*

Conditionals which allow engine-specific code to be used. The names follow naturally from those of the engine binaries: note that the (u)ptex tests are for  $\varepsilon$ -pT<sub>E</sub>X and  $\varepsilon$ -upT<sub>E</sub>X as expl3 requires the  $\varepsilon$ -T<sub>E</sub>X extensions. Each conditional is true for *exactly one* supported engine. In particular, `\sys_if_engine ptex_p:` is true for  $\varepsilon$ -pT<sub>E</sub>X but false for  $\varepsilon$ -upT<sub>E</sub>X.

---

`\c_sys_engine_str`

---

New: 2015-09-19

---

The current engine given as a lower case string: one of `luatex`, `pdftex`, `ptex`, `uptex` or `xetex`.

## 4 Output format

<code>\sys_if_output_dvi_p:</code>	★	<code>\sys_if_output_dvi:TF</code>	<code>{\true code}</code>	<code>{\false code}</code>
<code>\sys_if_output_dvi:</code>	<u>TF</u> ★	Conditionals which give the current output mode the TeX run is operating in. This is always one of two outcomes, DVI mode or PDF mode. The two sets of conditionals are thus complementary and are both provided to allow the programmer to emphasise the most appropriate case.		
<code>\sys_if_output_pdf_p:</code>	★			
<code>\sys_if_output_pdf:</code>	<u>TF</u> ★			
<hr/>				
New: 2015-09-19				

---

<code>\c_sys_output_str</code>	The current output mode given as a lower case string: one of <code>dvi</code> or <code>pdf</code> .
<hr/> New: 2015-09-19 <hr/>	

## Part XXX

# The l3deprecation package

## Deprecation errors

### 1 l3deprecation documentation

A few commands have had to be deprecated over the years. This module defines deprecated and deleted commands to produce an error.

`\deprecation_error:` Defines commands that will soon become deprecated to produce errors.

*(End definition for `\deprecation_error`:. This function is documented on page ??.)*

## Part XXXI

# The l3candidates package

## Experimental additions to l3kernel

### 1 Important notice

This module provides a space in which functions can be added to l3kernel (expl3) while still being experimental.

**As such, the functions here may not remain in their current form, or indeed at all, in l3kernel in the future.**

In contrast to the material in l3experimental, the functions here are all *small* additions to the kernel. We encourage programmers to test them out and report back on the LaTeX-L mailing list.

Thus, if you intend to use any of these functions from the candidate module in a public package offered to others for productive use (e.g., being placed on CTAN) please consider the following points carefully:

- Be prepared that your public packages might require updating when such functions are being finalized.
- Consider informing us that you use a particular function in your public package, e.g., by discussing this on the LaTeX-L mailing list. This way it becomes easier to coordinate any updates necessary without issues for the users of your package.
- Discussing and understanding use cases for a particular addition or concept also helps to ensure that we provide the right interfaces in the final version so please give us feedback if you consider a certain candidate function useful (or not).

We only add functions in this space if we consider them being serious candidates for a final inclusion into the kernel. However, real use sometimes leads to better ideas, so functions from this module are **not necessarily stable** and we may have to adjust them!

### 2 Additions to l3basics

---

<code>\debug_check_declarations_on:</code>	<code>\debug_check_declarations_on:</code>
<code>\debug_check_declarations_off:</code>	<code>\debug_check_declarations_off:</code>

---

New: 2017-07-14

Turn on and off within a group the code that checks that all expl3 variables used were previously declared, as done globally by the `check-declarations` option. This can only be used if expl3 is loaded with one of the options `check-declarations`, `log-functions`, or `enable-debug`.

---

```
\debug_log_functions_on:
\debug_log_functions_off:
```

---

New: 2017-07-14

---

```
\debug_log_functions_on:
\debug_log_functions_off:
```

Turn on and off within a group the code that logs function definitions, as done globally by the `log-functions` option. This can only be used if `expl3` is loaded with one of the options `check-declarations`, `log-functions`, or `enable-debug`.

---

```
\mode_leave_vertical:
```

---

New: 2017-07-04

---

```
\mode_leave_vertical:
```

Ensures that  $\text{\TeX}$  is not in vertical (inter-paragraph) mode. In horizontal or math mode this command has no effect, in vertical mode it switches to horizontal mode, and inserts a box of width `\parindent`, followed by the `\everypar` token list.

**$\text{\TeX}$ hackers note:** This results in the contents of the `\everypar` token register being inserted, after `\mode_leave_vertical:` is complete. Notice that in contrast to the  $\text{\LaTeX 2}_{\epsilon}$  `\leavevmode` approach, no box is used by the method implemented here.

## 3 Additions to `\box`

### 3.1 Viewing part of a box

---

```
\box_clip:N
\box_clip:c
```

---

```
\box_clip:N <box>
```

Clips the `<box>` in the output so that only material inside the bounding box is displayed in the output. The updated `<box>` is an `hbox`, irrespective of the nature of the `<box>` before the clipping is applied. The clipping applies within the current  $\text{\TeX}$  group level.

**These functions require the  $\text{\LaTeX 3}$  native drivers: they do not work with the  $\text{\LaTeX 2}_{\epsilon}$  graphics drivers!**

**$\text{\TeX}$ hackers note:** Clipping is implemented by the driver, and as such the full content of the box is placed in the output file. Thus clipping does not remove any information from the raw output, and hidden material can therefore be viewed by direct examination of the file.

---

```
\box_trim:Nnnnn
\box_trim:cnnnn
```

---

```
\box_trim:Nnnnn <box> {<left>} {<bottom>} {<right>} {<top>}
```

Adjusts the bounding box of the `<box>` `<left>` is removed from the left-hand edge of the bounding box, `<right>` from the right-hand edge and so fourth. All adjustments are *<dimension expressions>*. Material outside of the bounding box is still displayed in the output unless `\box_clip:N` is subsequently applied. The updated `<box>` is an `hbox`, irrespective of the nature of the `<box>` before the trim operation is applied. The adjustment applies within the current  $\text{\TeX}$  group level. The behavior of the operation where the trims requested is greater than the size of the box is undefined.

---

```
\box_viewport:Nnnnn
\box_viewport:cnnnn
```

---

```
\box_viewport:Nnnnn <box> {<llx>} {<lly>} {<urx>} {<ury>}
```

Adjusts the bounding box of the `<box>` such that it has lower-left co-ordinates (`<llx>`, `<lly>`) and upper-right co-ordinates (`<urx>`, `<ury>`). All four co-ordinate positions are *<dimension expressions>*. Material outside of the bounding box is still displayed in the output unless `\box_clip:N` is subsequently applied. The updated `<box>` is an `hbox`, irrespective of the nature of the `<box>` before the viewport operation is applied. The adjustment applies within the current  $\text{\TeX}$  group level.

## 4 Additions to l3clist

<hr/>	
<code>\clist_rand_item:N</code> ★	<code>\clist_rand_item:N</code> $\langle\textit{clist var}\rangle$
<code>\clist_rand_item:c</code> ★	<code>\clist_rand_item:n</code> $\{\langle\textit{comma list}\rangle\}$
<code>\clist_rand_item:n</code> ★	Selects a pseudo-random item of the $\langle\textit{comma list}\rangle$ . If the $\langle\textit{comma list}\rangle$ has no item, the result is empty. This is only available in pdfTeX and LuaTeX.
<hr/>	
New: 2016-12-06	
<hr/>	

**TeXhackers note:** The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the  $\langle\textit{item}\rangle$  does not expand further when appearing in an x-type argument expansion.

## 5 Additions to l3coffins

<hr/>	
<code>\coffin_resize:Nnn</code>	<code>\coffin_resize:Nnn</code> $\langle\textit{coffin}\rangle$ $\{\langle\textit{width}\rangle\}$ $\{\langle\textit{total-height}\rangle\}$
<code>\coffin_resize:cnn</code>	Resized the $\langle\textit{coffin}\rangle$ to $\langle\textit{width}\rangle$ and $\langle\textit{total-height}\rangle$ , both of which should be given as dimension expressions.
<hr/>	
<code>\coffin_rotate:Nn</code>	<code>\coffin_rotate:Nn</code> $\langle\textit{coffin}\rangle$ $\{\langle\textit{angle}\rangle\}$
<code>\coffin_rotate:cn</code>	Rotates the $\langle\textit{coffin}\rangle$ by the given $\langle\textit{angle}\rangle$ (given in degrees counter-clockwise). This process rotates both the coffin content and poles. Multiple rotations do not result in the bounding box of the coffin growing unnecessarily.
<hr/>	
<code>\coffin_scale:Nnn</code>	<code>\coffin_scale:Nnn</code> $\langle\textit{coffin}\rangle$ $\{\langle\textit{x-scale}\rangle\}$ $\{\langle\textit{y-scale}\rangle\}$
<code>\coffin_scale:cnn</code>	Scales the $\langle\textit{coffin}\rangle$ by a factors $\langle\textit{x-scale}\rangle$ and $\langle\textit{y-scale}\rangle$ in the horizontal and vertical directions, respectively. The two scale factors should be given as real numbers.
<hr/>	

## 6 Additions to l3file

<hr/>	
<code>\file_get_md5five_hash:nN</code>	<code>\file_get_md5five_hash:nN</code> $\{\langle\textit{file name}\rangle\}$ $\langle\textit{str var}\rangle$
New: 2017-07-11	Searches for $\langle\textit{file name}\rangle$ using the current TeX search path and the additional paths controlled by <code>\file_path_include:n</code> . If found, sets the $\langle\textit{str var}\rangle$ to the MD5 sum generated from the content of the file. Where the file is not found, the $\langle\textit{str var}\rangle$ will be empty.
<hr/>	
<code>\file_get_size:nN</code>	<code>\file_get_size:nN</code> $\{\langle\textit{file name}\rangle\}$ $\langle\textit{str var}\rangle$
New: 2017-07-09	Searches for $\langle\textit{file name}\rangle$ using the current TeX search path and the additional paths controlled by <code>\file_path_include:n</code> . If found, sets the $\langle\textit{str var}\rangle$ to the size of the file in bytes. Where the file is not found, the $\langle\textit{str var}\rangle$ will be empty.
<hr/>	

**TeXhackers note:** The XeTeX engine provides no way to implement this function.

---

**\file\_get\_timestamp:nN**

---

New: 2017-07-09

---

**\file\_get\_timestamp:nN**  $\{\langle file\ name\rangle\}$   $\langle str\ var\rangle$

Searches for  $\langle file\ name\rangle$  using the current T<sub>E</sub>X search path and the additional paths controlled by **\file\_path\_include:n**. If found, sets the  $\langle str\ var\rangle$  to the modification timestamp of the file in the form D: $\langle year\rangle\langle month\rangle\langle day\rangle\langle hour\rangle\langle minute\rangle\langle second\rangle\langle offset\rangle$ , where the latter may be Z (UTC) or  $\langle plus-minus\rangle\langle hours\rangle'\langle minutes\rangle'$ . Where the file is not found, the  $\langle str\ var\rangle$  will be empty.

**T<sub>E</sub>Xhackers note:** The X<sub>Ǝ</sub>T<sub>E</sub>X engine provides no way to implement this function.

---

**\file\_if\_exist\_input:nTF**

---

New: 2014-07-02

---

**\file\_if\_exist\_input:n**  $\{\langle file\ name\rangle\}$

**\file\_if\_exist\_input:nTF**  $\{\langle file\ name\rangle\}$   $\{\langle true\ code\rangle\}$   $\{\langle false\ code\rangle\}$

Searches for  $\langle file\ name\rangle$  using the current T<sub>E</sub>X search path and the additional paths controlled by **\file\_path\_include:n**. If found, inserts the  $\langle true\ code\rangle$  then reads in the file as additional L<sup>A</sup>T<sub>E</sub>X source as described for **\file\_input:n**. Note that **\file\_if\_exist\_input:n** does not raise an error if the file is not found, in contrast to **\file\_input:n**.

---

**\file\_input\_stop:**

---

New: 2017-07-07

---

**\file\_input\_stop:**

Ends the reading of a file started by **\file\_input:n** or similar before the end of the file is reached. Where the file reading is being terminated due to an error, **\msg\_critical:nn(nn)** should be preferred.

**T<sub>E</sub>Xhackers note:** This function must be used on a line on its own: T<sub>E</sub>X reads files line-by-line and so any additional tokens in the “current” line will still be read.

This is also true if the function is hidden inside another function (which will be the normal case), i.e., all tokens on the same line in the source file are still processed. Putting it on a line by itself in the definition doesn’t help as it is the line where it is used that counts!

## 7 Additions to l3int

---

**\int\_rand:nn** ★

---

New: 2016-12-06

---

**\int\_rand:nn**  $\{\langle intexpr_1\rangle\}$   $\{\langle intexpr_2\rangle\}$

Evaluates the two  $\langle integer\ expressions\rangle$  and produces a pseudo-random number between the two (with bounds included). This is only available in pdfT<sub>E</sub>X and LuaT<sub>E</sub>X.

## 8 Additions to l3msg

In very rare cases it may be necessary to produce errors in an expansion-only context. The functions in this section should only be used if there is no alternative approach using **\msg\_error:nnnnnn** or other non-expandable commands from the previous section. Despite having a similar interface as non-expandable messages, expandable errors must be handled internally very differently from normal error messages, as none of the tools to print to the terminal or the log file are expandable. As a result, the message text and arguments are not expanded, and messages must be very short (with default settings, they are truncated after approximately 50 characters). It is advisable to ensure that the message is understandable even when truncated. Another particularity of expandable messages is that they cannot be redirected or turned off by the user.

---

<code>\msg_expandable_error:nnnnnn</code>	★	<code>\msg_expandable_error:nnnnnn {&lt;module&gt;} {&lt;message&gt;} {&lt;arg one&gt;} {&lt;arg</code>
<code>\msg_expandable_error:nnffff</code>	★	<code>two}&amp; {&lt;arg three&gt;} {&lt;arg four&gt;}</code>
<code>\msg_expandable_error:nnnnn</code>	★	
<code>\msg_expandable_error:nnfff</code>	★	
<code>\msg_expandable_error:nnnn</code>	★	
<code>\msg_expandable_error:nnff</code>	★	
<code>\msg_expandable_error:nnn</code>	★	
<code>\msg_expandable_error:nnf</code>	★	
<code>\msg_expandable_error:nn</code>	★	

---

New: 2015-08-06

Issues an “Undefined error” message from T<sub>E</sub>X itself using the undefined control sequence `\::error` then prints “! <module>: ”<error message>, which should be short. With default settings, anything beyond approximately 60 characters long (or bytes in some engines) is cropped. A leading space might be removed as well.

## 9 Additions to l3prop

---

<code>\prop_count:N</code>	★	<code>\prop_count:N &lt;property list&gt;</code>
<code>\prop_count:c</code>	★	

---

Leaves the number of key–value pairs in the <property list> in the input stream as an <integer denotation>.

---

<code>\prop_map_tokens:Nn</code>	☆	<code>\prop_map_tokens:Nn &lt;property list&gt; {&lt;code&gt;}</code>
<code>\prop_map_tokens:cn</code>	☆	

---

Analogue of `\prop_map_function:NN` which maps several tokens instead of a single function. The <code> receives each key–value pair in the <property list> as two trailing brace groups. For instance,

`\prop_map_tokens:Nn \l_my_prop { \str_if_eq:nnT { mykey } }`

expands to the value corresponding to `mykey`: for each pair in `\l_my_prop` the function `\str_if_eq:nnT` receives `mykey`, the <key> and the <value> as its three arguments. For that specific task, `\prop_item:Nn` is faster.

---

<code>\prop_rand_key_value:N</code>	★	<code>\prop_rand_key_value:N &lt;prop var&gt;</code>
<code>\prop_rand_key_value:c</code>	★	

---

New: 2016-12-06

Selects a pseudo-random key–value pair in the <property list> and returns `{<key>}{<value>}`. If the <property list> is empty the result is empty. This is only available in pdfT<sub>E</sub>X and LuaT<sub>E</sub>X.

**T<sub>E</sub>Xhackers note:** The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the <value> does not expand further when appearing in an x-type argument expansion.



## 10 Additions to l3seq

---

<code>\seq_mapthread_function:NNN</code>	☆	<code>\seq_mapthread_function:NNN &lt;seq1&gt; &lt;seq2&gt; &lt;function&gt;</code>
<code>\seq_mapthread_function:(NcN cNN ccN)</code>	☆	

---

Applies  $\langle function \rangle$  to every pair of items  $\langle seq_1-item \rangle$ – $\langle seq_2-item \rangle$  from the two sequences, returning items from both sequences from left to right. The  $\langle function \rangle$  receives two  $\mathbf{n}$ -type arguments for each iteration. The mapping terminates when the end of either sequence is reached (*i.e.* whichever sequence has fewer items determines how many iterations occur).

---

<code>\seq_set_filter:NNn</code>	<code>\seq_set_filter:NNn &lt;sequence1&gt; &lt;sequence2&gt; {\langle inline boolexpr \rangle}</code>
<code>\seq_gset_filter:NNn</code>	

---

Evaluates the  $\langle inline boolexpr \rangle$  for every  $\langle item \rangle$  stored within the  $\langle sequence_2 \rangle$ . The  $\langle inline boolexpr \rangle$  receives the  $\langle item \rangle$  as  $\#1$ . The sequence of all  $\langle items \rangle$  for which the  $\langle inline boolexpr \rangle$  evaluated to `true` is assigned to  $\langle sequence_1 \rangle$ .

**TeXhackers note:** Contrarily to other mapping functions, `\seq_map_break:` cannot be used in this function, and would lead to low-level TeX errors.

---

<code>\seq_set_map:NNn</code>	<code>\seq_set_map:NNn &lt;sequence1&gt; &lt;sequence2&gt; {\langle inline function \rangle}</code>
<code>\seq_gset_map:NNn</code>	

---

New: 2011-12-22

Applies  $\langle inline function \rangle$  to every  $\langle item \rangle$  stored within the  $\langle sequence_2 \rangle$ . The  $\langle inline function \rangle$  should consist of code which will receive the  $\langle item \rangle$  as  $\#1$ . The sequence resulting from  $\mathbf{x}$ -expanding  $\langle inline function \rangle$  applied to each  $\langle item \rangle$  is assigned to  $\langle sequence_1 \rangle$ . As such, the code in  $\langle inline function \rangle$  should be expandable.

**TeXhackers note:** Contrarily to other mapping functions, `\seq_map_break:` cannot be used in this function, and would lead to low-level TeX errors.

---

<code>\seq_rand_item:N</code>	★	<code>\seq_rand_item:N &lt;seq var&gt;</code>
<code>\seq_rand_item:c</code>	★	

---

New: 2016-12-06

Selects a pseudo-random item of the  $\langle sequence \rangle$ . If the  $\langle sequence \rangle$  is empty the result is empty. This is only available in pdfTeX and LuaTeX.

**TeXhackers note:** The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the  $\langle item \rangle$  does not expand further when appearing in an  $\mathbf{x}$ -type argument expansion.

## 11 Additions to l3skip

---

<code>\skip_split_finite_else_action:nnNN</code>	<code>\skip_split_finite_else_action:nnNN {\langle skipexpr \rangle} {\langle action \rangle}</code>
	$\langle dimen_1 \rangle$ $\langle dimen_2 \rangle$

---

Checks if the  $\langle skipexpr \rangle$  contains finite glue. If it does then it assigns  $\langle dimen_1 \rangle$  the stretch component and  $\langle dimen_2 \rangle$  the shrink component. If it contains infinite glue set  $\langle dimen_1 \rangle$  and  $\langle dimen_2 \rangle$  to 0pt and place  $\#2$  into the input stream: this is usually an error or warning message of some sort.

## 12 Additions to l3sys

<hr/> <code>\sys_if_rand_exist_p: *</code> <code>\sys_if_rand_exist:TF *</code> <hr/> New: 2017-05-27	<code>\sys_if_rand_exist_p:</code> <code>\sys_if_rand_exist:TF {\true code} {\false code}</code>  Tests if the engine has a pseudo-random number generator. Currently this is the case in pdfTeX and LuaTeX.
<hr/> <code>\sys_rand_seed: *</code> <hr/> New: 2017-05-27	<code>\sys_rand_seed:</code>  Expands to the current value of the engine's random seed, a non-negative integer. In engines without random number support this expands to 0.
<hr/> <code>\sys_gset_rand_seed:n</code> <hr/> New: 2017-05-27	<code>\sys_gset_rand_seed:n {\intexpr}</code>  Sets the seed for the engine's pseudo-random number generator to the <i>integer expression</i> . The assignment is global. This random seed affects all <code>\..._rand</code> functions (such as <code>\int_rand:nn</code> or <code>\clist_rand_item:n</code> ) as well as other packages relying on the engine's random number generator. Currently only the absolute value of the seed is used. In engines without random number support this produces an error.
<hr/> <code>\c_sys_shell_escape_int</code> <hr/> New: 2017-05-27	This variable exposes the internal triple of the shell escape status. The possible values are  0 Shell escape is disabled  1 Unrestricted shell escape is enabled  2 Restricted shell escape is enabled
<hr/> <code>\sys_if_shell_p: *</code> <code>\sys_if_shell:TF *</code> <hr/> New: 2017-05-27	<code>\sys_if_shell_p:</code> <code>\sys_if_shell:TF {\true code} {\false code}</code>  Performs a check for whether shell escape is enabled. This returns true if either of restricted or unrestricted shell escape is enabled.
<hr/> <code>\sys_if_shell_unrestricted_p: *</code> <code>\sys_if_shell_unrestricted:TF *</code> <hr/> New: 2017-05-27	<code>\sys_if_shell_unrestricted_p:</code> <code>\sys_if_shell_unrestricted:TF {\true code} {\false code}</code>  Performs a check for whether <i>unrestricted</i> shell escape is enabled.
<hr/> <code>\sys_if_shell_restricted_p: *</code> <code>\sys_if_shell_restricted:TF *</code> <hr/> New: 2017-05-27	<code>\sys_if_shell_restricted_p:</code> <code>\sys_if_shell_restricted:TF {\true code} {\false code}</code>  Performs a check for whether <i>restricted</i> shell escape is enabled. This returns false if unrestricted shell escape is enabled. Unrestricted shell escape is not considered a superset of restricted shell escape in this case. To find whether any shell escape is enabled use <code>\sys_if_shell:.</code>

---

<code>\sys_shell_now:n</code>	<code>\sys_shell_now:n {⟨tokens⟩}</code>
<code>\sys_shell_now:x</code>	Execute <i>⟨tokens⟩</i> through shell escape immediately.
New: 2017-05-27	

---



---

<code>\sys_shell_shipout:n</code>	<code>\sys_shell_shipout:n {⟨tokens⟩}</code>
<code>\sys_shell_shipout:x</code>	Execute <i>⟨tokens⟩</i> through shell escape at shipout.
New: 2017-05-27	

---

## 13 Additions to l3tl

---

<code>\tl_if_single_token_p:n</code> ★	<code>\tl_if_single_token_p:n {⟨token list⟩}</code>
<code>\tl_if_single_token:nTF</code> ★	<code>\tl_if_single_token:nTF {⟨token list⟩} {⟨true code⟩} {⟨false code⟩}</code>

---

Tests if the token list consists of exactly one token, *i.e.* is either a single space character or a single “normal” token. Token groups (`{...}`) are not single tokens.

---

<code>\tl_reverse_tokens:n</code> ★	<code>\tl_reverse_tokens:n {⟨tokens⟩}</code>
-------------------------------------	--

---

This function, which works directly on T<sub>E</sub>X tokens, reverses the order of the *⟨tokens⟩*: the first becomes the last and the last becomes first. Spaces are preserved. The reversal also operates within brace groups, but the braces themselves are not exchanged, as this would lead to an unbalanced token list. For instance, `\tl_reverse_tokens:n {a~{b()}}` leaves `{()b}~a` in the input stream. This function requires two steps of expansion.

**T<sub>E</sub>Xhackers note:** The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the token list does not expand further when appearing in an x-type argument expansion.

---

<code>\tl_count_tokens:n</code> ★	<code>\tl_count_tokens:n {⟨tokens⟩}</code>
-----------------------------------	--

---

Counts the number of T<sub>E</sub>X tokens in the *⟨tokens⟩* and leaves this information in the input stream. Every token, including spaces and braces, contributes one to the total; thus for instance, the token count of `a~{bc}` is 6. This function requires three expansions, giving an *⟨integer denotation⟩*.

---

<code>\tl_lower_case:n</code> ★	<code>\tl_upper_case:n {⟨tokens⟩}</code>
<code>\tl_upper_case:n</code> ★	<code>\tl_upper_case:nn {⟨language⟩} {⟨tokens⟩}</code>
<code>\tl_mixed_case:n</code> ★	
<code>\tl_lower_case:nn</code> ★	
<code>\tl_upper_case:nn</code> ★	
<code>\tl_mixed_case:nn</code> ★	

---

New: 2014-06-30  
Updated: 2016-01-12

---

These functions are intended to be applied to input which may be regarded broadly as “text”. They traverse the *⟨tokens⟩* and change the case of characters as discussed below. The character code of the characters replaced may be arbitrary: the replacement characters have standard document-level category codes (11 for letters, 12 for letter-like characters which can also be case-changed). Begin-group and end-group characters in the *⟨tokens⟩* are normalized and become `{` and `}`, respectively.

Importantly, notice that these functions are intended for working with user text for typesetting. For case changing programmatic data see the `l3str` module and discussion there of `\str_lower_case:n`, `\str_upper_case:n` and `\str_fold_case:n`.

The functions perform expansion on the input in most cases. In particular, input in the form of token lists or expandable functions is expanded *unless* it falls within one

of the special handling classes described below. This expansion approach means that in general the result of case changing matches the “natural” outcome expected from a “functional” approach to case modification. For example

```
\tl_set:Nn \l_tmpa_tl { hello }
\tl_upper_case:n { \l_tmpa_tl \c_space_tl world }
```

produces

```
HELLO WORLD
```

The expansion approach taken means that in package mode any L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> “robust” commands which may appear in the input should be converted to engine-protected versions using for example the `\robustify` command from the `etoolbox` package.

---

#### `\l_tl_case_change_math_tl`

---

Case changing does not take place within math mode material so for example

```
\tl_upper_case:n { Some~text~$y = mx + c$~with~{Braces} }
```

becomes

```
SOME TEXT $y = mx + c$ WITH {BRACES}
```

Material inside math mode is left entirely unchanged: in particular, no expansion is undertaken.

Detection of math mode is controlled by the list of tokens in `\l_tl_case_change_math_tl`, which should be in open-close pairs. In package mode the standard settings is

```
$ $ \ ( \)
```

Note that while expansion occurs when searching the text it does not apply to math mode material (which should be unaffected by case changing). As such, whilst the opening token for math mode may be “hidden” inside a command/macro, the closing one cannot be as this is being searched for in math mode. Typically, in the types of “text” the case changing functions are intended to apply to this should not be an issue.

---

### `\l_tl_case_change_exclude_tl`

Case changing can be prevented by using any command on the list `\l_tl_case_change_exclude_tl`. Each entry should be a function to be followed by one argument: the latter will be preserved as-is with no expansion. Thus for example following

```
\tl_put_right:Nn \l_tl_case_change_exclude_tl { \NoChangeCase }
```

the input

```
\tl_upper_case:n  
  { Some~text~$y = mx + c$~with~\NoChangeCase {Protection} }
```

will result in

```
SOME TEXT $y = mx + c$ WITH \NoChangeCase {Protection}
```

Notice that the case changing mapping preserves the inclusion of the escape functions: it is left to other code to provide suitable definitions (typically equivalent to `\use:n`). In particular, the result of case changing is returned protected by `\exp_not:n`.

When used with L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> the commands `\cite`, `\ensuremath`, `\label` and `\ref` are automatically included in the list for exclusion from case changing.

---

### `\l_tl_case_change_accents_tl`

This list specifies accent commands which should be left unexpanded in the output. This allows for example

```
\tl_upper_case:n { \" { a } }
```

to yield

```
\" { A }
```

irrespective of the expandability of `\`.

The standard contents of this variable is `\`, `\'`, `\.`, `\^`, `\'`, `\~`, `\c`, `\H`, `\k`, `\r`, `\t`, `\u` and `\v`.

“Mixed” case conversion may be regarded informally as converting the first character of the *<tokens>* to upper case and the rest to lower case. However, the process is more complex than this as there are some situations where a single lower case character maps to a special form, for example *ij* in Dutch which becomes *IJ*. As such, `\tl_mixed_case:n(n)` implement a more sophisticated mapping which accounts for this and for modifying accents on the first letter. Spaces at the start of the *<tokens>* are ignored when finding the first “letter” for conversion.

```
\tl_mixed_case:n { hello~WORLD } % => "Hello world"  
\tl_mixed_case:n { ~hello~WORLD } % => " Hello world"  
\tl_mixed_case:n { {hello}~WORLD } % => "{Hello} world"
```

When finding the first “letter” for this process, any content in math mode or covered by `\l_tl_case_change_exclude_tl` is ignored.

(Note that the Unicode Consortium describe this as “title case”, but that in English title case applies on a word-by-word basis. The “mixed” case implemented here is a lower level concept needed for both “title” and “sentence” casing of text.)

---

---

`\tl\_tl\_mixed\_case\_ignore\_tl`

---

---

The list of characters to ignore when searching for the first “letter” in mixed-casing is determined by `\tl\_tl\_mixed\_change\_ignore\_tl`. This has the standard setting

`( [ { ‘ -`

where comparisons are made on a character basis.

As is generally true for `expl3`, these functions are designed to work with Unicode input only. As such, UTF-8 input is assumed for *all* engines. When used with `XYTeX` or `LuaTeX` a full range of Unicode transformations are enabled. Specifically, the standard mappings here follow those defined by the [Unicode Consortium](#) in `UnicodeData.txt` and `SpecialCasing.txt`. In the case of 8-bit engines, mappings are provided for characters which can be represented in output typeset using the `T1` font encoding. Thus for example `Ãd` can be case-changed using `pdfTeX`. For `pTeX` only the ASCII range is covered as the engine treats input outside of this range as east Asian.

Context-sensitive mappings are enabled: language-dependent cases are discussed below. Context detection expands input but treats any unexpandable control sequences as “failures” to match a context.

Language-sensitive conversions are enabled using the `<language>` argument, and follow Unicode Consortium guidelines. Currently, the languages recognised for special handling are as follows.

- Azeri and Turkish (`az` and `tr`). The case pairs `I/i-dotless` and `I-dot/i` are activated for these languages. The combining dot mark is removed when lower casing `I-dot` and introduced when upper casing `i-dotless`.
- German (`de-alt`). An alternative mapping for German in which the lower case *Eszett* maps to a *großes Eszett*.
- Lithuanian (`lt`). The lower case letters `i` and `j` should retain a dot above when the accents grave, acute or tilde are present. This is implemented for lower casing of the relevant upper case letters both when input as single Unicode codepoints and when using combining accents. The combining dot is removed when upper casing in these cases. Note that *only* the accents used in Lithuanian are covered: the behaviour of other accents are not modified.
- Dutch (`nl`). Capitalisation of `ij` at the beginning of mixed cased input produces `IJ` rather than `Ij`. The output retains two separate letters, thus this transformation *is* available using `pdfTeX`.

Creating additional context-sensitive mappings requires knowledge of the underlying mapping implementation used here. The team are happy to add these to the kernel where they are well-documented (*e.g.* in Unicode Consortium or relevant government publications).

---

---

`\tl\_set\_from\_file:Nnn`  
`\tl\_set\_from\_file:cnn`  
`\tl\_gset\_from\_file:Nnn`  
`\tl\_gset\_from\_file:cnn`

---

---

New: 2014-06-25

`\tl\_set\_from\_file:Nnn <tl> {<setup>} {<filename>}`

Defines `<tl>` to the contents of `<filename>`. Category codes may need to be set appropriately via the `<setup>` argument.

<code>\tl_set_from_file_x:Nnn</code>	<code>\tl_set_from_file_x:Nnn &lt;tl&gt; {&lt;setup&gt;} {&lt;filename&gt;}</code>
<code>\tl_set_from_file_x:cnn</code>	Defines <i>&lt;tl&gt;</i> to the contents of <i>&lt;filename&gt;</i> , expanding the contents of the file as it is read.
<code>\tl_gset_from_file_x:Nnn</code>	Category codes and other definitions may need to be set appropriately via the <i>&lt;setup&gt;</i>
<code>\tl_gset_from_file_x:cnn</code>	argument.

New: 2014-06-25

<code>\tl_rand_item:N *</code>	<code>\tl_rand_item:N &lt;tl var&gt;</code>
<code>\tl_rand_item:c *</code>	<code>\tl_rand_item:n {&lt;token list&gt;}</code>
<code>\tl_rand_item:n *</code>	Selects a pseudo-random item of the <i>&lt;token list&gt;</i> . If the <i>&lt;token list&gt;</i> is blank, the result is empty. This is only available in pdfTeX and LuaTeX.

New: 2016-12-06

**TeXhackers note:** The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<item>* does not expand further when appearing in an x-type argument expansion.

<code>\tl_range:Nnn *</code>	<code>\tl_range:Nnn &lt;tl var&gt; {&lt;start index&gt;} {&lt;end index&gt;}</code>
<code>\tl_range:cnn *</code>	<code>\tl_range:nnn {&lt;token list&gt;} {&lt;start index&gt;} {&lt;end index&gt;}</code>
<code>\tl_range:nnn *</code>	Leaves in the input stream the items from the <i>&lt;start index&gt;</i> to the <i>&lt;end index&gt;</i> inclusive. Positive <i>&lt;indices&gt;</i> are counted from the start of the <i>&lt;token list&gt;</i> , 1 being the first item, and negative <i>&lt;indices&gt;</i> are counted from the end of the token list, -1 being the last item. If either of <i>&lt;start index&gt;</i> or <i>&lt;end index&gt;</i> is 0, the result is empty. For instance,

New: 2017-02-17

```
\iow_term:x { \tl_range:nnn { abcdef } { 2 } { 5 } }
\iow_term:x { \tl_range:nnn { abcdef } { -4 } { -1 } }
\iow_term:x { \tl_range:nnn { abcdef } { -2 } { -1 } }
\iow_term:x { \tl_range:nnn { abcdef } { 0 } { -1 } }
```

prints bcde, cdef, ef, and an empty line to the terminal. The *<start index>* must always be smaller than or equal to the *<end index>*: if this is not the case then no output is generated. Thus

```
\iow_term:x { \tl_range:nnn { abcdef } { 5 } { 2 } }
\iow_term:x { \tl_range:nnn { abcdef } { -1 } { -4 } }
```

both yield empty token lists.

**TeXhackers note:** The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<item>* does not expand further when appearing in an x-type argument expansion.

## 14 Additions to l3tokens

---

`\peek_N_type:TF`

---

Updated: 2012-12-20

---

`\peek_N_type:TF`  $\{\langle true\ code\rangle\}$   $\{\langle false\ code\rangle\}$

Tests if the next  $\langle token\rangle$  in the input stream can be safely grabbed as an N-type argument. The test is  $\langle false\rangle$  if the next  $\langle token\rangle$  is either an explicit or implicit begin-group or end-group token (with any character code), or an explicit or implicit space character (with character code 32 and category code 10), or an outer token (never used in L<sup>A</sup>T<sub>E</sub>X3) and  $\langle true\rangle$  in all other cases. Note that a  $\langle true\rangle$  result ensures that the next  $\langle token\rangle$  is a valid N-type argument. However, if the next  $\langle token\rangle$  is for instance `\c_space_token`, the test takes the  $\langle false\rangle$  branch, even though the next  $\langle token\rangle$  is in fact a valid N-type argument. The  $\langle token\rangle$  is left in the input stream after the  $\langle true\ code\rangle$  or  $\langle false\ code\rangle$  (as appropriate to the result of the test).



## Part XXXII

# The l3`luatex` package

## LuaTeX-specific functions

### 1 Breaking out to Lua

The LuaTeX engine provides access to the Lua programming language, and with it access to the “internals” of TeX. In order to use this within the framework provided here, a family of functions is available. When used with pdfTeX or XeTeX these raise an error: use `\sys_if_engine_luatex:T` to avoid this. Details on using Lua with the LuaTeX engine are given in the LuaTeX manual.

#### 1.1 TeX code interfaces

---

<code>\lua_now_x:n</code>	★	<code>\lua_now:n {⟨token list⟩}</code>
---------------------------	---	--

<code>\lua_now:n</code>	★
-------------------------	---

---

New: 2015-06-29

---

The *⟨token list⟩* is first tokenized by TeX, which includes converting line ends to spaces in the usual TeX manner and which respects currently-applicable TeX category codes. The resulting *⟨Lua input⟩* is passed to the Lua interpreter for processing. Each `\lua_now:n` block is treated by Lua as a separate chunk. The Lua interpreter executes the *⟨Lua input⟩* immediately, and in an expandable manner.

In the case of the `\lua_now_x:n` version the input is fully expanded by TeX in an x-type manner *but* the function remains fully expandable.

**TeXhackers note:** `\lua_now_x:n` is a macro wrapper around `\directlua:` when LuaTeX is in use two expansions are required to yield the result of the Lua code.

---

<code>\lua_shipout_x:n</code>		<code>\lua_shipout:n {⟨token list⟩}</code>
-------------------------------	--	--

<code>\lua_shipout:n</code>
-----------------------------

---

New: 2015-06-30

---

The *⟨token list⟩* is first tokenized by TeX, which includes converting line ends to spaces in the usual TeX manner and which respects currently-applicable TeX category codes. The resulting *⟨Lua input⟩* is passed to the Lua interpreter when the current page is finalised (*i.e.* at shipout). Each `\lua_shipout:n` block is treated by Lua as a separate chunk. The Lua interpreter will execute the *⟨Lua input⟩* during the page-building routine: no TeX expansion of the *⟨Lua input⟩* will occur at this stage.

In the case of the `\lua_shipout_x:n` version the input is fully expanded by TeX in an x-type manner during the shipout operation.

**TeXhackers note:** At a TeX level, the *⟨Lua input⟩* is stored as a “whatsit”.

---

<code>\lua_escape_x:n</code>	★	<code>\lua_escape:n {⟨token list⟩}</code>
------------------------------	---	---

<code>\lua_escape:n</code>	★
----------------------------	---

---

New: 2015-06-29
-----------------

---

Converts the  $\langle token list \rangle$  such that it can safely be passed to Lua: embedded backslashes, double and single quotes, and newlines and carriage returns are escaped. This is done by prepending an extra token consisting of a backslash with category code 12, and for the line endings, converting them to  $\backslash n$  and  $\backslash r$ , respectively.

In the case of the  $\backslash lua\_escape\_x:n$  version the input is fully expanded by  $\text{\TeX}$  in an  $x$ -type manner *but* the function remains fully expandable.

**$\text{\TeX}$ hackers note:**  $\backslash lua\_escape\_x:n$  is a macro wrapper around  $\backslash luaescapestring$ : when  $\text{\LuaTeX}$  is in use two expansions are required to yield the result of the Lua code.

## 1.2 Lua interfaces

As well as interfaces for  $\text{\TeX}$ , there are a small number of Lua functions provided here. Currently these are intended for internal use only.

---

<code>l3kernel.charcat</code>	<code>\l3kernel.charcat(⟨charcode⟩, ⟨catcode⟩)</code>
-------------------------------	---

---

Constructs a character of  $\langle charcode \rangle$  and  $\langle catcode \rangle$  and returns the result to  $\text{\TeX}$ .

---

<code>l3kernel.filemdfivesum</code>	<code>\l3kernel.filemdfivesum(⟨file⟩)</code>
-------------------------------------	--

---

Returns the of the MD5 sum of the file contents read as bytes. If the  $\langle file \rangle$  is not found, nothing is returned with *no error raised*.

---

<code>l3kernel.filemoddate</code>	<code>\l3kernel.filemoddate(⟨file⟩)</code>
-----------------------------------	--

---

Returns the of the date/time of last modification of the  $\langle file \rangle$  in the format  $D:\langle year \rangle\langle month \rangle\langle day \rangle\langle hour \rangle\langle m$  where the latter may be Z (UTC) or  $\langle plus-minus \rangle\langle hours \rangle'\langle minutes \rangle'$ . If the  $\langle file \rangle$  is not found, nothing is returned with *no error raised*.

---

<code>l3kernel.filesize</code>	<code>\l3kernel.filesize(⟨file⟩)</code>
--------------------------------	---

---

Returns the size of the  $\langle file \rangle$  in bytes. If the  $\langle file \rangle$  is not found, nothing is returned with *no error raised*.

---

<code>l3kernel.strcmp</code>	<code>\l3kernel.strcmp(⟨str one⟩, ⟨str two⟩)</code>
------------------------------	---

---

Compares the two strings and returns 0 to  $\text{\TeX}$  if the two are identical.

## Part XXXIII

# The l3drivers package

## Drivers

T<sub>E</sub>X relies on drivers in order to carry out a number of tasks, such as using color, including graphics and setting up hyper-links. The nature of the code required depends on the exact driver in use. Currently, L<sup>A</sup>T<sub>E</sub>X3 is aware of the following drivers:

- **pdfmode**: The “driver” for direct PDF output by *both* pdfT<sub>E</sub>X and LuaT<sub>E</sub>X (no separate driver is used in this case: the engine deals with PDF creation itself).
- **dvips**: The dvips program, which works in conjugation with pdfT<sub>E</sub>X or LuaT<sub>E</sub>X in DVI mode.
- **dvipdfmx**: The dvipdfmx program, which works in conjugation with pdfT<sub>E</sub>X or LuaT<sub>E</sub>X in DVI mode.
- **dvisvgm**: The dvisvgm program, which works in conjugation with pdfT<sub>E</sub>X or LuaT<sub>E</sub>X when run in DVI mode as well as with (u)pT<sub>E</sub>X and X<sub>Y</sub>T<sub>E</sub>X.
- **xdvipdfmx**: The driver used by X<sub>Y</sub>T<sub>E</sub>X.

The code here is all very low-level, and should not in general be used outside of the kernel. It is also important to note that many of the functions here are closely tied to the immediate level “up”, and they must be used in the correct contexts.

## 1 Box clipping

---

`\_driver_box_use_clip:N`

New: 2011-11-11

---

`\_driver_box_use_clip:N <box>`

Inserts the content of the *<box>* at the current insertion point such that any material outside of the bounding box is not displayed by the driver. The material in the *<box>* is still placed in the output stream: the clipping takes place at a driver level.

This function should only be used within a surrounding horizontal box construct.

## 2 Box rotation and scaling

---

`\_driver_box_use_rotate:Nn`

New: 2016-05-12

---

`\_driver_box_use_rotate:Nn <box> {<angle>}`

Inserts the content of the *<box>* at the current insertion point rotated by the *<angle>* (expressed in degrees). The material is inserted with no apparent height or width, and is rotated such the the T<sub>E</sub>X reference point of the box is the center of rotation and remains the reference point after rotation. It is the responsibly of the code using this function to adjust the apparent size of the box to be correct at the T<sub>E</sub>X side.

This function should only be used within a surrounding horizontal box construct.

---

<code>\_driver\_box\_use\_scale:Nnn</code>	<code>\_driver\_box\_use\_scale:Nnn &lt;box&gt; {&lt;x-scale&gt;} {&lt;y-scale&gt;}</code>
--	--

---

New: 2016-05-12

---

Inserts the content of the  $\langle box \rangle$  at the current insertion point scale by the  $\langle x-scale \rangle$  and  $\langle y-scale \rangle$ . The material is inserted with no apparent height or width. It is the responsibly of the code using this function to adjust the apparent size of the box to be correct at the  $\text{\TeX}$  side.

This function should only be used within a surrounding horizontal box construct.

### 3 Color support

---

<code>\_driver\_color\_ensure\_current:</code>	<code>\_driver\_color\_ensure\_current:</code>
--	--

---

New: 2011-09-03

Updated: 2012-05-18

---

Ensures that the color used to typeset material is that which was set when the material was placed in a box. This function is therefore required inside any “color safe” box to ensure that the box may be inserted in a location where the foreground color has been altered, while preserving the color used in the box.

### 4 Drawing

The drawing functions provided here are *highly* experimental. They are inspired heavily by the system layer of `pgf` (most have the same interface as the same functions in the latter’s `\pgfsys@... namespace`). They are intended to form the basis for higher level drawing interfaces, which themselves are likely to be further abstracted for user access. Again, this model is heavily inspired by `pgf` and `Tikz`.

These low level drawing interfaces abstract from the driver raw requirements but still require an appreciation of the concepts of PostScript/PDF/SVG graphic creation.

---

<code>\_driver\_draw\_begin:</code>	<code>\_driver\_draw\_begin:</code>
<code>\_driver\_draw\_end:</code>	<code>&lt;content&gt;</code>

---

`\_driver\_draw\_end:`

Defines a drawing environment. This is a scope for the purposes of the graphics state. Depending on the driver, other set up may or may not take place here. The natural size of the  $\langle content \rangle$  should be zero from the  $\text{\TeX}$  perspective: allowance for the size of the content must be made at a higher level (or indeed this can be skipped if the content is to overlap other material).

---

<code>\_driver\_draw\_scope\_begin:</code>	<code>\_driver\_draw\_scope\_begin:</code>
<code>\_driver\_draw\_scope\_end:</code>	<code>&lt;content&gt;</code>

---

`\_driver\_draw\_scope\_end:`

Defines a scope for drawing settings and so on. Changes to the graphic state and concepts such as color or linewidth are localised to a scope. This function pair must never be used if an partial path is under construction: such paths must be entirely contained at one unbroken scope level. Note that scopes do not form  $\text{\TeX}$  groups and may not be aligned with them.

## 4.1 Path construction

<u><code>\__driver_draw_moveto:nn</code></u>	<code>\__driver_draw_move:nn {&lt;x&gt;} {&lt;y&gt;}</code>	Moves the current drawing reference point to $(\langle x \rangle, \langle y \rangle)$ ; any active transformation matrix applies.
<u><code>\__driver_draw_lineto:nn</code></u>	<code>\__driver_draw_lineto:nn {&lt;x&gt;} {&lt;y&gt;}</code>	Adds a path from the current drawing reference point to $(\langle x \rangle, \langle y \rangle)$ ; any active transformation matrix applies. Note that nothing is drawn until a fill or stroke operation is applied, and that the path may be discarded or used as a clip without appearing itself.
<u><code>\__driver_draw_curveto:nnnnnn</code></u>	<code>\__driver_draw_curveto:nnnnnn {&lt;x<sub>1</sub>&gt;} {&lt;y<sub>1</sub>&gt;} {&lt;x<sub>2</sub>&gt;} {&lt;y<sub>2</sub>&gt;} {&lt;x<sub>3</sub>&gt;} {&lt;y<sub>3</sub>&gt;}</code>	Adds a Bezier curve path from the current drawing reference point to $(\langle x_3 \rangle, \langle y_3 \rangle)$ , using $(\langle x_1 \rangle, \langle y_1 \rangle)$ and $(\langle x_2 \rangle, \langle y_2 \rangle)$ as control points; any active transformation matrix applies. Note that nothing is drawn until a fill or stroke operation is applied, and that the path may be discarded or used as a clip without appearing itself.
<u><code>\__driver_draw_rectangle:nnnn</code></u>	<code>\__driver_draw_rectangle:nnnn {&lt;x&gt;} {&lt;y&gt;} {&lt;width&gt;} {&lt;height&gt;}</code>	Adds rectangular path from $(\langle x_1 \rangle, \langle y_1 \rangle)$ of $\langle height \rangle$ and $\langle width \rangle$ ; any active transformation matrix applies. Note that nothing is drawn until a fill or stroke operation is applied, and that the path may be discarded or used as a clip without appearing itself.
<u><code>\__driver_draw_closepath:</code></u>	<code>\__driver_draw_closepath:</code>	Closes an existing path, adding a line from the current point to the start of path. Note that nothing is drawn until a fill or stroke operation is applied, and that the path may be discarded or used as a clip without appearing itself.

## 4.2 Stroking and filling

<u><code>\__driver_draw_stroke:</code></u>	<code>&lt;path construction&gt;</code>	
<u><code>\__driver_draw_closestroke:</code></u>	<code>\__driver_draw_stroke:</code>	
		Draws a line along the current path, which is also closed by <code>\__driver_draw_closestroke:</code> . The nature of the line drawn is influenced by settings for
		<ul style="list-style-type: none"> <li>• Line thickness</li> <li>• Stroke color (or the current color if no specific stroke color is set)</li> <li>• Line capping (how non-closed line ends should look)</li> <li>• Join style (how a bend in the path should be rendered)</li> <li>• Dash pattern</li> </ul>

The path may also be used for clipping.

<code>\__driver_draw_fill:</code>	<code>&lt;path construction&gt;</code>
<code>\__driver_draw_fillstroke:</code>	<code>\__driver_draw_fill:</code>

Fills the area surrounded by the current path: this will be closed prior to filling if it is not already. The `fillstroke` version also strokes the path as described for `\__driver_draw_stroke:`. The fill is influenced by the setting for fill color (or the current color if no specific stroke color is set). The path may also be used for clipping. For paths which are self-intersecting or comprising multiple parts, the determination of which areas are inside the path is made using the non-zero winding number rule unless the even-odd rule is active.

<code>\__driver_draw_nonzero_rule:</code>	<code>\__driver_draw_nonzero_rule:</code>
<code>\__driver_draw_evenodd_rule:</code>	

Active either the non-zero winding number or the even-odd rule, respectively, for determining what is inside a fill or clip area. For technical reasons, these command are not influenced by scoping and apply on an ongoing basis.

<code>\__driver_draw_clip:</code>	<code>&lt;path construction&gt;</code>
<code>\__driver_draw_clip:</code>	<code>\__driver_draw_clip:</code>

Indicates that the current path should be used for clipping, such that any subsequent material outside of the path (but within the current scope) will not be shown. This command should be given once a path is complete but before it is stroked or filled (if appropriate). This command is *not* affected by scoping: it applies to exactly one path as shown.

<code>\__driver_draw_discardpath:</code>	<code>&lt;path construction&gt;</code>
<code>\__driver_draw_discardpath:</code>	<code>\__driver_draw_discardpath:</code>

Discards the current path without stroking or filling. This is primarily useful for paths constructed purely for clipping, as this alone does not end the paths existence.

### 4.3 Stroke options

<code>\__driver_draw_linewidth:n</code>	<code>\__driver_draw_linewidth:n &lt;{dimexpr}&gt;</code>
---	---

Sets the width to be used for stroking to `<dimexpr>`.

<code>\__driver_draw_dash:nn</code>	<code>\__driver_draw_dash:nn &lt;{dash pattern}&gt; &lt;{phase}&gt;</code>
-------------------------------------	--

Sets the pattern of dashing to be used when stroking a line. The `<dash pattern>` should be a comma-separated list of dimension expressions. This is then interpreted as a series of pairs of line-on and line-off lengths. For example `3pt, 4pt` means that 3pt on, 4pt off, 3pt on, and so on. A more complex pattern will also repeat: `3pt, 4pt, 1pt, 2pt` results in 3pt on, 4pt off, 1pt on, 2pt off, 3pt on, and so on. An odd number of entries means that the last is repeated, for example `3pt` is equal to `3pt, 3pt`. An empty pattern yields a solid line.

The `<phase>` specifies an offset at the start of the cycle. For example, with a pattern `3pt` a phase of `1pt` means that the output is 2pt on, 3pt off, 3pt on, 3pt on, *etc.*

---

<code>\__driver_draw_cap_but:</code>	<code>\__driver_draw_cap_but:</code>
<code>\__driver_draw_cap_rectangle:</code>	
<code>\__driver_draw_cap_round:</code>	

---

Sets the style of terminal stroke position to one of butt, rectangle or round.

---

<code>\__driver_draw_join_bevel:</code>	<code>\__driver_draw_cap_but:</code>
<code>\__driver_draw_join_miter:</code>	Sets the style of stroke joins to one of bevel, miter or round.
<code>\__driver_draw_join_round:</code>	

---



---

<code>\__driver_draw_miterlimit:n</code>	<code>\__driver_draw_miterlimit:n {&lt;dimexpr&gt;}</code>
--	--

---

Sets the miter limit of lines joined as a miter, as described in the PDF and PostScript manuals.

## 4.4 Color

---

<code>\__driver_draw_color_cmyk:nnnn</code>	<code>\__driver_draw_color_cmyk:nnnn {&lt;cyan&gt;} {&lt;magenta&gt;} {&lt;yellow&gt;}</code>
<code>\__driver_draw_color_cmyk_fill:nnnn</code>	<code>{&lt;black&gt;}</code>
<code>\__driver_draw_color_cmyk_stroke:nnnn</code>	

---

Sets the color for drawing to the CMYK values specified, all of which are fp expressions which should evaluate to between 0 and 1. The **fill** and **stroke** versions set only the color for those operations. Note that the general setting is more efficient with some drivers so should in most cases be preferred.

---

<code>\__driver_draw_color_gray:n</code>	<code>\__driver_draw_color_gray:n {&lt;gray&gt;}</code>
<code>\__driver_draw_color_gray_fill:n</code>	
<code>\__driver_draw_color_gray_stroke:n</code>	

---

Sets the color for drawing to the grayscale value specified, which is fp expressions which should evaluate to between 0 and 1. The **fill** and **stroke** versions set only the color for those operations. Note that the general setting is more efficient with some drivers so should in most cases be preferred.

---

<code>\__driver_draw_color_rgb:nnn</code>	<code>\__driver_draw_color_gray:n {&lt;red&gt;} {&lt;green&gt;} {&lt;blue&gt;}</code>
<code>\__driver_draw_color_rgb_fill:nnn</code>	
<code>\__driver_draw_color_rgb_stroke:nnn</code>	

---

Sets the color for drawing to the RGB values specified, all of which are fp expressions which should evaluate to between 0 and 1. The **fill** and **stroke** versions set only the color for those operations. Note that the general setting is more efficient with some drivers so should in most cases be preferred.

## 4.5 Inserting T<sub>E</sub>X material

---

```

\__driver_draw_hbox:Nnnnnnn \__driver_draw_hbox:Nnnnnnn <box>
                             {\a}\b}\c}\d}\x}\y}

```

---

Inserts the  $\langle box \rangle$  as an hbox with the box reference point placed at  $(x, y)$ . The transformation matrix  $[abcd]$  is applied to the box, allowing it to be in synchronisation with any scaling, rotation or skewing applying more generally. Note that T<sub>E</sub>X material should not be inserted directly into a drawing as it would not be in the correct location. Also note that as for other drawing elements the box here has no size from a T<sub>E</sub>X perspective.

## 4.6 Coordinate system transformations

---

```

\__driver_draw_transformcm:nnnnnn \__driver_draw_transformcm:nnnnnn {\a}\b}\c}\d}\
                             {\x}\y}

```

---

Applies the transformation matrix  $[abcd]$  and offset vector  $(x, y)$  to the current graphic state. This affects any subsequent items in the same scope but not those already given.

# Part XXXIV

# Implementation

## 1 l3bootstrap implementation

```

1 \<*initex | package>
2 \<@@=expl>

```

### 1.1 Format-specific code

The very first thing to do is to bootstrap the iniT<sub>E</sub>X system so that everything else will actually work. T<sub>E</sub>X does not start with some pretty basic character codes set up.

```

3 \<*initex>
4 \catcode '\{ = 1 %
5 \catcode '\} = 2 %
6 \catcode '\# = 6 %
7 \catcode '\^ = 7 %
8 \</initex>

```

Tab characters should not show up in the code, but to be on the safe side.

```

9 \<*initex>
10 \catcode '\^^I = 10 %
11 \</initex>

```

For LuaT<sub>E</sub>X, the extra primitives need to be enabled. This is not needed in package mode: common formats have the primitives enabled.

```

12 \<*initex>
13 \begingroup\expandafter\expandafter\expandafter\endgroup
14 \expandafter\ifx\curname directlua\endcurname\relax
15 \else
16 \directlua{tex.enableprimitives("", tex.extraprimitives())}%
17 \fi
18 \</initex>

```



Depending on the versions available, the L<sup>A</sup>T<sub>E</sub>X format may not have the raw `\Umath` primitive names available. We fix that globally: it should cause no issues. Older LuaT<sub>E</sub>X versions do not have a pre-built table of the primitive names here so sort one out ourselves. These end up globally-defined but at that is true with a newer format anyway and as they all start `\U` this should be reasonably safe.

```

19 \begin{package}
20 \begin{group}
21   \expandafter\ifx\csname directlua\endcsname\relax
22   \else
23     \directlua{%
24       local i
25       local t = { }
26       for _,i in pairs(tex.extraprimitives("luatex")) do
27         if string.match(i,"^U") then
28           if not string.match(i,"^Uchar$") then %$
29             table.insert(t,i)
30           end
31         end
32       end
33       tex.enableprimitives("", t)
34     }%
35   \fi
36 \end{group}
37 \end{package}

```

## 1.2 The `\pdfstrcmp` primitive in X<sub>Y</sub>T<sub>E</sub>X

Only pdfT<sub>E</sub>X has a primitive called `\pdfstrcmp`. The X<sub>Y</sub>T<sub>E</sub>X version is just `\strcmp`, so there is some shuffling to do. As this is still a real primitive, using the pdfT<sub>E</sub>X name is “safe”.

```

38 \begin{group}\expandafter\expandafter\expandafter\end{group}
39 \expandafter\ifx\csname pdfstrcmp\endcsname\relax
40   \let\pdfstrcmp\strcmp
41 \fi

```

## 1.3 Loading support Lua code

When LuaT<sub>E</sub>X is used there are various pieces of Lua code which need to be loaded. The code itself is defined in `l3luatex` and is extracted into a separate file. Thus here the task is to load the Lua code both now and (if required) at the start of each job.

```

42 \begin{group}\expandafter\expandafter\expandafter\end{group}
43 \expandafter\ifx\csname directlua\endcsname\relax
44 \else
45   \ifnum\luatexversion<70 %
46   \else

```

In package mode a category code table is needed: either use a pre-loaded allocator or provide one using the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>-based generic code. In format mode the table used here can be hard-coded into the Lua.

```

47 \begin{package}
48   \begin{group}\expandafter\expandafter\expandafter\end{group}
49   \expandafter\ifx\csname newcatcodetable\endcsname\relax

```

```

50     \input{ltluatex}%
51 \fi
52 \newcatcodetable\ucharcat@table
53 \directlua{
54     l3kernel = l3kernel or { }
55     local charcat_table = \number\ucharcat@table\space
56     l3kernel.charcat_table = charcat_table
57 }%
58 \end{package}
59 \directlua{require("expl3")}%

```

As the user might be making a custom format, no assumption is made about matching package mode with only loading the Lua code once. Instead, a query to Lua reveals what mode is in operation.

```

60 \ifnum 0%
61 \directlua{
62     if status.ini_version then
63         tex.write("1")
64     end
65 }>0 %
66 \everyjob\expandafter{%
67     \the\expandafter\everyjob
68     \csname\detokenize{lua_now_x:n}\endcsname{require("expl3")}%
69 }%
70 \fi
71 \fi
72 \fi

```

## 1.4 Engine requirements

The code currently requires  $\epsilon$ -TeX and functionality equivalent to `\pdfstrcmp`, and also driver and Unicode character support. This is available in a reasonably-wide range of engines.

```

73 \begingroup
74 \def\next{\endgroup}%
75 \def\ShortText{Required primitives not found}%
76 \def\LongText%
77 {%
78     LaTeX3 requires the e-TeX primitives and additional functionality as
79     described in the README file.
80     \LineBreak
81     These are available in the engines\LineBreak
82     - pdfTeX v1.40\LineBreak
83     - XeTeX v0.9994\LineBreak
84     - LuaTeX v0.70\LineBreak
85     - e-(u)pTeX mid-2012\LineBreak
86     or later.\LineBreak
87     \LineBreak
88 }%
89 \ifnum0%
90 \expandafter\ifx\csname pdfstrcmp\endcsname\relax
91 \else
92 \expandafter\ifx\csname pdftexversion\endcsname\relax
93     1%

```

```

94     \else
95       \ifnum\pdfTeXversion<140 \else 1\fi
96     \fi
97   \fi
98   \expandafter\ifx\csname directlua\endcsname\relax
99   \else
100     \ifnum\luaTeXversion<70 \else 1\fi
101   \fi
102   =0 %
103   \newlinechar'\^^J %
104 <*initex>
105   \def\LineBreak{^^J}%
106   \edef\next
107     {%
108     \errhelp
109     {%
110       \LongText
111       For pdfTeX and XeTeX the '-etex' command-line switch is also
112       needed.\LineBreak
113       \LineBreak
114       Format building will abort!\LineBreak
115     }%
116     \errmessage{\ShortText}%
117   \endgroup
118   \noexpand\end
119   }%
120 </initex>
121 <*package>
122   \def\LineBreak{\noexpand\MessageBreak}%
123   \expandafter\ifx\csname PackageError\endcsname\relax
124     \def\LineBreak{^^J}%
125     \def\PackageError#1#2#3%
126       {%
127         \errhelp{#3}%
128         \errmessage{#1 Error: #2}%
129       }%
130   \fi
131   \edef\next
132     {%
133     \noexpand\PackageError{expl3}{\ShortText}
134     {\LongText Loading of expl3 will abort!}%
135   \endgroup
136   \noexpand\endinput
137   }%
138 </package>
139   \fi
140 \next

```

## 1.5 Extending allocators

In format mode, allocating registers is handled by `l3alloc`. However, in package mode it's much safer to rely on more general code. For example, the ability to extend  $\TeX$ 's allocation routine to allow for  $\varepsilon\text{-}\TeX$  has been around since 1997 in the `etex` package.

Loading this support is delayed until here as we are now sure that the  $\varepsilon$ -TeX extensions and `\pdfstrcmp` or equivalent are available. Thus there is no danger of an “uncontrolled” error if the engine requirements are not met.

For  $\text{\LaTeX}2_{\varepsilon}$  we need to make sure that the extended pool is being used: `expl3` uses a lot of registers. For formats from 2015 onward there is nothing to do as this is automatic. For older formats, the `etex` package needs to be loaded to do the job. In that case, some inserts are reserved also as these have to be from the standard pool. Note that `\reserveinserts` is `\outer` and so is accessed here by `csname`. In earlier versions, loading `etex` was done directly and so `\reserveinserts` appeared in the code: this then required a `\relax` after `\RequirePackage` to prevent an error with “unsafe” definitions as seen for example with `capoptions`. The optional loading here is done using a group and `\ifx` test as we are not quite in the position to have a single name for `\pdfstrcmp` just yet.

```

141 \langle*package\rangle
142 \beginingroup
143   \def\@tempa{LaTeX2e}%
144   \def\next{}%
145   \ifx\fmtname\@tempa
146     \expandafter\ifx\csname extrafloats\endcsname\relax
147       \def\next
148         {%
149           \RequirePackage{etex}%
150           \csname reserveinserts\endcsname{32}%
151         }%
152     \fi
153   \fi
154 \expandafter\endgroup
155 \next
156 \rangle/package\rangle

```

## 1.6 Character data

TeX needs various pieces of data to be set about characters, in particular which ones to treat as letters and which `\lccode` values apply as these affect hyphenation. It makes most sense to set this and related information up in one place. Whilst for  $\text{\LaTeX}$  hyphenation patterns can be read anywhere, other engines have to build them into the format and so we *must* do this set up before reading the patterns. For the Unicode engines, there are shared loaders available to obtain the relevant information directly from the Unicode Consortium data files. These need standard (Ini)TeX category codes and primitive availability and must therefore be loaded *very* early. This has a knock-on effect on the 8-bit set up: it makes sense to do the definitions for those here as well so it is all in one place.

For  $\text{\XeTeX}$  and  $\text{\LuaTeX}$ , which are natively Unicode engines, simply load the Unicode data.

```

157 \langle*initex\rangle
158 \ifdefined\Umathcode
159   \input load-unicode-data %
160   \input load-unicode-math-classes %
161 \else

```

For the 8-bit engines a font encoding scheme must be chosen. At present, this is the EC (T1) scheme, with the assumption that languages for which this is not appropriate will be used with one of the Unicode engines.

```
162 \begingroup
```

Lower case chars: map to themselves when lower casing and down by "20 when upper casing. (The characters a–z are set up correctly by IniT<sub>E</sub>X.)

```
163 \def\temp{%
164   \ifnum\count0>\count2 %
165   \else
166     \global\lccode\count0 = \count0 %
167     \global\uccode\count0 = \numexpr\count0 - "20\relax
168     \advance\count0 by 1 %
169     \expandafter\temp
170   \fi
171 }
172 \count0 = "A0 %
173 \count2 = "BC %
174 \temp
175 \count0 = "E0 %
176 \count2 = "FF %
177 \temp
```

Upper case chars: map up by "20 when lower casing, to themselves when upper casing and require an \sfcode of 999. (The characters A–Z are set up correctly by IniT<sub>E</sub>X.)

```
178 \def\temp{%
179   \ifnum\count0>\count2 %
180   \else
181     \global\lccode\count0 = \numexpr\count0 + "20\relax
182     \global\uccode\count0 = \count0 %
183     \global\sfcode\count0 = 999 %
184     \advance\count0 by 1 %
185     \expandafter\temp
186   \fi
187 }
188 \count0 = "80 %
189 \count2 = "9C %
190 \temp
191 \count0 = "C0 %
192 \count2 = "DF %
193 \temp
```

A few special cases where things are not as one might expect using the above pattern: dotless-I, dotless-J, dotted-I and d-bar.

```
194 \global\lccode'\^Y = '\^Y %
195 \global\uccode'\^Y = '\I %
196 \global\lccode'\^Z = '\^Z %
197 \global\uccode'\^Y = '\J %
198 \global\lccode"9D = '\i %
199 \global\uccode"9D = "9D %
200 \global\lccode"9E = "9E %
201 \global\uccode"9E = "D0 %
```

Allow hyphenation at a zero-width glyph (used to break up ligatures or to place accents between characters).

```

202 \global\lccode23 = 23 %
203 \endgroup
204 \fi

```

In all cases it makes sense to set up - to map to itself: this allows hyphenation of the rest of a word following it (suggested by Lars Helström).

```

205 \global\lccode'\- = '\- %
206 \</initex>

```

## 1.7 The L<sup>A</sup>T<sub>E</sub>X3 code environment

The code environment is now set up.

**\ExplSyntaxOff** Before changing any category codes, in package mode we need to save the situation before loading. Note the set up here means that once applied \ExplSyntaxOff becomes a “do nothing” command until \ExplSyntaxOn is used. For format mode, there is no need to save category codes so that step is skipped.

```

207 \protected\def\ExplSyntaxOff{}%
208 (*package)
209 \protected\edef\ExplSyntaxOff
210 {%
211   \protected\def\ExplSyntaxOff{}%
212   \catcode 9 = \the\catcode 9\relax
213   \catcode 32 = \the\catcode 32\relax
214   \catcode 34 = \the\catcode 34\relax
215   \catcode 38 = \the\catcode 38\relax
216   \catcode 58 = \the\catcode 58\relax
217   \catcode 94 = \the\catcode 94\relax
218   \catcode 95 = \the\catcode 95\relax
219   \catcode 124 = \the\catcode 124\relax
220   \catcode 126 = \the\catcode 126\relax
221   \endlinechar = \the\endlinechar\relax
222   \chardef\csname\detokenize{l__kernel_expl_bool}\endcsname = 0\relax
223 }%
224 \</package>

```

(End definition for \ExplSyntaxOff. This function is documented on page 6.)

The code environment is now set up.

```

225 \catcode 9 = 9\relax
226 \catcode 32 = 9\relax
227 \catcode 34 = 12\relax
228 \catcode 38 = 4\relax
229 \catcode 58 = 11\relax
230 \catcode 94 = 7\relax
231 \catcode 95 = 11\relax
232 \catcode 124 = 12\relax
233 \catcode 126 = 10\relax
234 \endlinechar = 32\relax

```

**\l\_\_kernel\_expl\_bool** The status for experimental code syntax: this is on at present.

```

235 \chardef\l__kernel_expl_bool = 1\relax

```

(End definition for \l\_\_kernel\_expl\_bool.)

**\ExplSyntaxOn** The idea here is that multiple `\ExplSyntaxOn` calls are not going to mess up category codes, and that multiple calls to `\ExplSyntaxOff` are also not wasting time. Applying `\ExplSyntaxOn` alters the definition of `\ExplSyntaxOff` and so in package mode this function should not be used until after the end of the loading process!

```

236 \protected \def \ExplSyntaxOn
237 {
238   \bool_if:NF \l__kernel_expl_bool
239   {
240     \cs_set_protected:Npx \ExplSyntaxOff
241     {
242       \char_set_catcode:nn { 9 } { \char_value_catcode:n { 9 } }
243       \char_set_catcode:nn { 32 } { \char_value_catcode:n { 32 } }
244       \char_set_catcode:nn { 34 } { \char_value_catcode:n { 34 } }
245       \char_set_catcode:nn { 38 } { \char_value_catcode:n { 38 } }
246       \char_set_catcode:nn { 58 } { \char_value_catcode:n { 58 } }
247       \char_set_catcode:nn { 94 } { \char_value_catcode:n { 94 } }
248       \char_set_catcode:nn { 95 } { \char_value_catcode:n { 95 } }
249       \char_set_catcode:nn { 124 } { \char_value_catcode:n { 124 } }
250       \char_set_catcode:nn { 126 } { \char_value_catcode:n { 126 } }
251       \tex_endlinechar:D =
252         \tex_the:D \tex_endlinechar:D \scan_stop:
253       \bool_set_false:N \l__kernel_expl_bool
254       \cs_set_protected:Npn \ExplSyntaxOff { }
255     }
256   }
257   \char_set_catcode_ignore:n { 9 } % tab
258   \char_set_catcode_ignore:n { 32 } % space
259   \char_set_catcode_other:n { 34 } % double quote
260   \char_set_catcode_alignment:n { 38 } % ampersand
261   \char_set_catcode_letter:n { 58 } % colon
262   \char_set_catcode_math_superscript:n { 94 } % circumflex
263   \char_set_catcode_letter:n { 95 } % underscore
264   \char_set_catcode_other:n { 124 } % pipe
265   \char_set_catcode_space:n { 126 } % tilde
266   \tex_endlinechar:D = 32 \scan_stop:
267   \bool_set_true:N \l__kernel_expl_bool
268 }

```

(End definition for `\ExplSyntaxOn`. This function is documented on page 6.)

```

269 \</initex | package>

```

## 2 l3names implementation

```

270 \<*initex | package>

```

No prefix substitution here.

```

271 \<@@=

```

The code here simply renames all of the primitives to new, internal, names. In format mode, it also deletes all of the existing names (although some do come back later).

`\tex_undefined:D` This function does not exist at all, but is the name used by the plain T<sub>E</sub>X format for an undefined function. So it should be marked here as “taken”.

(End definition for `\tex_undefined:D`.)

The `\let` primitive is renamed by hand first as it is essential for the entire process to follow. This also uses `\global`, as that way we avoid leaving an unneeded csname in the hash table.

```
272 \let \tex_global:D \global
273 \let \tex_let:D \let
```

Everything is inside a (rather long) group, which keeps `\__kernel_primitive:NN` trapped.

```
274 \begingroup
```

`\__kernel_primitive:NN` A temporary function to actually do the renaming. This also allows the original names to be removed in format mode.

```
275 \long \def \__kernel_primitive:NN #1#2
276 {
277   \tex_global:D \tex_let:D #2 #1
278   (*initex)
279   \tex_global:D \tex_let:D #1 \tex_undefined:D
280   (/initex)
281 }
```

(End definition for `\__kernel_primitive:NN`.)

To allow extracting “just the names”, a bit of DocStrip fiddling.

```
282 (/initex | package)
283 (*initex | names | package)
```

In the current incarnation of this package, all T<sub>E</sub>X primitives are given a new name of the form `\tex_oldname:D`. But first three special cases which have symbolic original names. These are given modified new names, so that they may be entered without catcode tricks.

```
284 \__kernel_primitive:NN \tex_space:D
285 \__kernel_primitive:NN \tex_italiccorrection:D
286 \__kernel_primitive:NN \tex_hyphen:D
```

Now all the other primitives.

```
287 \__kernel_primitive:NN \tex_above:D
288 \__kernel_primitive:NN \tex_abovedisplayshortskip:D
289 \__kernel_primitive:NN \tex_abovedisplayskip:D
290 \__kernel_primitive:NN \tex_abovewithdelims:D
291 \__kernel_primitive:NN \tex_accent:D
292 \__kernel_primitive:NN \tex_adjdemerits:D
293 \__kernel_primitive:NN \tex_advance:D
294 \__kernel_primitive:NN \tex_afterassignment:D
295 \__kernel_primitive:NN \tex_aftergroup:D
296 \__kernel_primitive:NN \tex_atop:D
297 \__kernel_primitive:NN \tex_atopwithdelims:D
298 \__kernel_primitive:NN \tex_badness:D
299 \__kernel_primitive:NN \tex_baselineskip:D
300 \__kernel_primitive:NN \tex_batchmode:D
301 \__kernel_primitive:NN \tex_begingroup:D
302 \__kernel_primitive:NN \tex_belowdisplayshortskip:D
303 \__kernel_primitive:NN \tex_belowdisplayskip:D
304 \__kernel_primitive:NN \tex_binoppenalty:D
305 \__kernel_primitive:NN \tex_botmark:D
```



306	\_kernel\_primitive:NN \box	\tex\_box:D
307	\_kernel\_primitive:NN \boxmaxdepth	\tex\_boxmaxdepth:D
308	\_kernel\_primitive:NN \brokenpenalty	\tex\_brokenpenalty:D
309	\_kernel\_primitive:NN \catcode	\tex\_catcode:D
310	\_kernel\_primitive:NN \char	\tex\_char:D
311	\_kernel\_primitive:NN \chardef	\tex\_chardef:D
312	\_kernel\_primitive:NN \cleaders	\tex\_cleaders:D
313	\_kernel\_primitive:NN \closein	\tex\_closein:D
314	\_kernel\_primitive:NN \closeout	\tex\_closeout:D
315	\_kernel\_primitive:NN \clubpenalty	\tex\_clubpenalty:D
316	\_kernel\_primitive:NN \copy	\tex\_copy:D
317	\_kernel\_primitive:NN \count	\tex\_count:D
318	\_kernel\_primitive:NN \countdef	\tex\_countdef:D
319	\_kernel\_primitive:NN \cr	\tex\_cr:D
320	\_kernel\_primitive:NN \crrcr	\tex\_crrcr:D
321	\_kernel\_primitive:NN \csname	\tex\_csname:D
322	\_kernel\_primitive:NN \day	\tex\_day:D
323	\_kernel\_primitive:NN \deadcycles	\tex\_deadcycles:D
324	\_kernel\_primitive:NN \def	\tex\_def:D
325	\_kernel\_primitive:NN \defaultthyphenchar	\tex\_defaultthyphenchar:D
326	\_kernel\_primitive:NN \defaultskewchar	\tex\_defaultskewchar:D
327	\_kernel\_primitive:NN \delcode	\tex\_delcode:D
328	\_kernel\_primitive:NN \delimiter	\tex\_delimiter:D
329	\_kernel\_primitive:NN \delimiterfactor	\tex\_delimiterfactor:D
330	\_kernel\_primitive:NN \delimitershortfall	\tex\_delimitershortfall:D
331	\_kernel\_primitive:NN \dimen	\tex\_dimen:D
332	\_kernel\_primitive:NN \dimendef	\tex\_dimendef:D
333	\_kernel\_primitive:NN \discretionary	\tex\_discretionary:D
334	\_kernel\_primitive:NN \displayindent	\tex\_displayindent:D
335	\_kernel\_primitive:NN \displaylimits	\tex\_displaylimits:D
336	\_kernel\_primitive:NN \displaystyle	\tex\_displaystyle:D
337	\_kernel\_primitive:NN \displaywidowpenalty	\tex\_displaywidowpenalty:D
338	\_kernel\_primitive:NN \displaywidth	\tex\_displaywidth:D
339	\_kernel\_primitive:NN \divide	\tex\_divide:D
340	\_kernel\_primitive:NN \doublehyphendemerits	\tex\_doublehyphendemerits:D
341	\_kernel\_primitive:NN \dp	\tex\_dp:D
342	\_kernel\_primitive:NN \dump	\tex\_dump:D
343	\_kernel\_primitive:NN \edef	\tex\_edef:D
344	\_kernel\_primitive:NN \else	\tex\_else:D
345	\_kernel\_primitive:NN \emergencystretch	\tex\_emergencystretch:D
346	\_kernel\_primitive:NN \end	\tex\_end:D
347	\_kernel\_primitive:NN \endcsname	\tex\_endcsname:D
348	\_kernel\_primitive:NN \endgroup	\tex\_endgroup:D
349	\_kernel\_primitive:NN \endinput	\tex\_endinput:D
350	\_kernel\_primitive:NN \endlinechar	\tex\_endlinechar:D
351	\_kernel\_primitive:NN \eqno	\tex\_eqno:D
352	\_kernel\_primitive:NN \errhelp	\tex\_errhelp:D
353	\_kernel\_primitive:NN \errmessage	\tex\_errmessage:D
354	\_kernel\_primitive:NN \errorcontextlines	\tex\_errorcontextlines:D
355	\_kernel\_primitive:NN \errorstopmode	\tex\_errorstopmode:D
356	\_kernel\_primitive:NN \escapechar	\tex\_escapechar:D
357	\_kernel\_primitive:NN \everycr	\tex\_everycr:D
358	\_kernel\_primitive:NN \everydisplay	\tex\_everydisplay:D
359	\_kernel\_primitive:NN \everyhbox	\tex\_everyhbox:D

360	\_kernel\_primitive:NN	\everyjob	\tex\_everyjob:D
361	\_kernel\_primitive:NN	\everymath	\tex\_everymath:D
362	\_kernel\_primitive:NN	\everypar	\tex\_everypar:D
363	\_kernel\_primitive:NN	\everyvbox	\tex\_everyvbox:D
364	\_kernel\_primitive:NN	\exhyphenpenalty	\tex\_exhyphenpenalty:D
365	\_kernel\_primitive:NN	\expandafter	\tex\_expandafter:D
366	\_kernel\_primitive:NN	\fam	\tex\_fam:D
367	\_kernel\_primitive:NN	\fi	\tex\_fi:D
368	\_kernel\_primitive:NN	\finalhyphendemerits	\tex\_finalhyphendemerits:D
369	\_kernel\_primitive:NN	\firstmark	\tex\_firstmark:D
370	\_kernel\_primitive:NN	\floatingpenalty	\tex\_floatingpenalty:D
371	\_kernel\_primitive:NN	\font	\tex\_font:D
372	\_kernel\_primitive:NN	\fontdimen	\tex\_fontdimen:D
373	\_kernel\_primitive:NN	\fontname	\tex\_fontname:D
374	\_kernel\_primitive:NN	\futurelet	\tex\_futurelet:D
375	\_kernel\_primitive:NN	\gdef	\tex\_gdef:D
376	\_kernel\_primitive:NN	\global	\tex\_global:D
377	\_kernel\_primitive:NN	\globaldefs	\tex\_globaldefs:D
378	\_kernel\_primitive:NN	\halign	\tex\_halign:D
379	\_kernel\_primitive:NN	\hangafter	\tex\_hangafter:D
380	\_kernel\_primitive:NN	\hangindent	\tex\_hangindent:D
381	\_kernel\_primitive:NN	\hbadness	\tex\_hbadness:D
382	\_kernel\_primitive:NN	\hbox	\tex\_hbox:D
383	\_kernel\_primitive:NN	\hfil	\tex\_hfil:D
384	\_kernel\_primitive:NN	\hfill	\tex\_hfill:D
385	\_kernel\_primitive:NN	\hfilneg	\tex\_hfilneg:D
386	\_kernel\_primitive:NN	\hfuzz	\tex\_hfuzz:D
387	\_kernel\_primitive:NN	\hoffset	\tex\_hoffset:D
388	\_kernel\_primitive:NN	\holdinginserts	\tex\_holdinginserts:D
389	\_kernel\_primitive:NN	\hrule	\tex\_hrule:D
390	\_kernel\_primitive:NN	\hsize	\tex\_hsize:D
391	\_kernel\_primitive:NN	\hskip	\tex\_hskip:D
392	\_kernel\_primitive:NN	\hss	\tex\_hss:D
393	\_kernel\_primitive:NN	\ht	\tex\_ht:D
394	\_kernel\_primitive:NN	\hyphenation	\tex\_hyphenation:D
395	\_kernel\_primitive:NN	\hyphenchar	\tex\_hyphenchar:D
396	\_kernel\_primitive:NN	\hyphenpenalty	\tex\_hyphenpenalty:D
397	\_kernel\_primitive:NN	\if	\tex\_if:D
398	\_kernel\_primitive:NN	\ifcase	\tex\_ifcase:D
399	\_kernel\_primitive:NN	\ifcat	\tex\_ifcat:D
400	\_kernel\_primitive:NN	\ifdim	\tex\_ifdim:D
401	\_kernel\_primitive:NN	\ifeof	\tex\_ifeof:D
402	\_kernel\_primitive:NN	\iffalse	\tex\_iffalse:D
403	\_kernel\_primitive:NN	\ifhbox	\tex\_ifhbox:D
404	\_kernel\_primitive:NN	\ifhmode	\tex\_ifhmode:D
405	\_kernel\_primitive:NN	\ifinner	\tex\_ifinner:D
406	\_kernel\_primitive:NN	\ifmmode	\tex\_ifmmode:D
407	\_kernel\_primitive:NN	\ifnum	\tex\_ifnum:D
408	\_kernel\_primitive:NN	\ifodd	\tex\_ifodd:D
409	\_kernel\_primitive:NN	\iftrue	\tex\_iftrue:D
410	\_kernel\_primitive:NN	\ifvbox	\tex\_ifvbox:D
411	\_kernel\_primitive:NN	\ifvmode	\tex\_ifvmode:D
412	\_kernel\_primitive:NN	\ifvoid	\tex\_ifvoid:D
413	\_kernel\_primitive:NN	\ifx	\tex\_ifx:D

414	<code>\_kernel\_primitive:NN \ignorespaces</code>	<code>\tex\_ignorespaces:D</code>
415	<code>\_kernel\_primitive:NN \immediate</code>	<code>\tex\_immediate:D</code>
416	<code>\_kernel\_primitive:NN \indent</code>	<code>\tex\_indent:D</code>
417	<code>\_kernel\_primitive:NN \input</code>	<code>\tex\_input:D</code>
418	<code>\_kernel\_primitive:NN \inputlineno</code>	<code>\tex\_inputlineno:D</code>
419	<code>\_kernel\_primitive:NN \insert</code>	<code>\tex\_insert:D</code>
420	<code>\_kernel\_primitive:NN \insertpenalties</code>	<code>\tex\_insertpenalties:D</code>
421	<code>\_kernel\_primitive:NN \interlinepenalty</code>	<code>\tex\_interlinepenalty:D</code>
422	<code>\_kernel\_primitive:NN \jobname</code>	<code>\tex\_jobname:D</code>
423	<code>\_kernel\_primitive:NN \kern</code>	<code>\tex\_kern:D</code>
424	<code>\_kernel\_primitive:NN \language</code>	<code>\tex\_language:D</code>
425	<code>\_kernel\_primitive:NN \lastbox</code>	<code>\tex\_lastbox:D</code>
426	<code>\_kernel\_primitive:NN \lastkern</code>	<code>\tex\_lastkern:D</code>
427	<code>\_kernel\_primitive:NN \lastpenalty</code>	<code>\tex\_lastpenalty:D</code>
428	<code>\_kernel\_primitive:NN \lastskip</code>	<code>\tex\_lastskip:D</code>
429	<code>\_kernel\_primitive:NN \lccode</code>	<code>\tex\_lccode:D</code>
430	<code>\_kernel\_primitive:NN \leaders</code>	<code>\tex\_leaders:D</code>
431	<code>\_kernel\_primitive:NN \left</code>	<code>\tex\_left:D</code>
432	<code>\_kernel\_primitive:NN \lefthyphenmin</code>	<code>\tex\_lefthyphenmin:D</code>
433	<code>\_kernel\_primitive:NN \leftskip</code>	<code>\tex\_leftskip:D</code>
434	<code>\_kernel\_primitive:NN \leqno</code>	<code>\tex\_leqno:D</code>
435	<code>\_kernel\_primitive:NN \let</code>	<code>\tex\_let:D</code>
436	<code>\_kernel\_primitive:NN \limits</code>	<code>\tex\_limits:D</code>
437	<code>\_kernel\_primitive:NN \linepenalty</code>	<code>\tex\_linepenalty:D</code>
438	<code>\_kernel\_primitive:NN \lineskip</code>	<code>\tex\_lineskip:D</code>
439	<code>\_kernel\_primitive:NN \lineskiplimit</code>	<code>\tex\_lineskiplimit:D</code>
440	<code>\_kernel\_primitive:NN \long</code>	<code>\tex\_long:D</code>
441	<code>\_kernel\_primitive:NN \looseness</code>	<code>\tex\_looseness:D</code>
442	<code>\_kernel\_primitive:NN \lower</code>	<code>\tex\_lower:D</code>
443	<code>\_kernel\_primitive:NN \lowercase</code>	<code>\tex\_lowercase:D</code>
444	<code>\_kernel\_primitive:NN \mag</code>	<code>\tex\_mag:D</code>
445	<code>\_kernel\_primitive:NN \mark</code>	<code>\tex\_mark:D</code>
446	<code>\_kernel\_primitive:NN \mathaccent</code>	<code>\tex\_mathaccent:D</code>
447	<code>\_kernel\_primitive:NN \mathbin</code>	<code>\tex\_mathbin:D</code>
448	<code>\_kernel\_primitive:NN \mathchar</code>	<code>\tex\_mathchar:D</code>
449	<code>\_kernel\_primitive:NN \mathchardef</code>	<code>\tex\_mathchardef:D</code>
450	<code>\_kernel\_primitive:NN \mathchoice</code>	<code>\tex\_mathchoice:D</code>
451	<code>\_kernel\_primitive:NN \mathclose</code>	<code>\tex\_mathclose:D</code>
452	<code>\_kernel\_primitive:NN \mathcode</code>	<code>\tex\_mathcode:D</code>
453	<code>\_kernel\_primitive:NN \mathinner</code>	<code>\tex\_mathinner:D</code>
454	<code>\_kernel\_primitive:NN \mathop</code>	<code>\tex\_mathop:D</code>
455	<code>\_kernel\_primitive:NN \mathopen</code>	<code>\tex\_mathopen:D</code>
456	<code>\_kernel\_primitive:NN \mathord</code>	<code>\tex\_mathord:D</code>
457	<code>\_kernel\_primitive:NN \mathpunct</code>	<code>\tex\_mathpunct:D</code>
458	<code>\_kernel\_primitive:NN \mathrel</code>	<code>\tex\_mathrel:D</code>
459	<code>\_kernel\_primitive:NN \mathsurround</code>	<code>\tex\_mathsurround:D</code>
460	<code>\_kernel\_primitive:NN \maxdeadcycles</code>	<code>\tex\_maxdeadcycles:D</code>
461	<code>\_kernel\_primitive:NN \maxdepth</code>	<code>\tex\_maxdepth:D</code>
462	<code>\_kernel\_primitive:NN \meaning</code>	<code>\tex\_meaning:D</code>
463	<code>\_kernel\_primitive:NN \medmuskip</code>	<code>\tex\_medmuskip:D</code>
464	<code>\_kernel\_primitive:NN \message</code>	<code>\tex\_message:D</code>
465	<code>\_kernel\_primitive:NN \mkern</code>	<code>\tex\_mkern:D</code>
466	<code>\_kernel\_primitive:NN \month</code>	<code>\tex\_month:D</code>
467	<code>\_kernel\_primitive:NN \moveleft</code>	<code>\tex\_moveleft:D</code>

468	\_kernel\_primitive:NN	\moveright	\tex\_moveright:D
469	\_kernel\_primitive:NN	\mskip	\tex\_mskip:D
470	\_kernel\_primitive:NN	\multiply	\tex\_multiply:D
471	\_kernel\_primitive:NN	\muskip	\tex\_muskip:D
472	\_kernel\_primitive:NN	\muskipdef	\tex\_muskipdef:D
473	\_kernel\_primitive:NN	\newlinechar	\tex\_newlinechar:D
474	\_kernel\_primitive:NN	\noalign	\tex\_noalign:D
475	\_kernel\_primitive:NN	\noboundary	\tex\_noboundary:D
476	\_kernel\_primitive:NN	\noexpand	\tex\_noexpand:D
477	\_kernel\_primitive:NN	\noindent	\tex\_noindent:D
478	\_kernel\_primitive:NN	\nolimits	\tex\_nolimits:D
479	\_kernel\_primitive:NN	\nonscript	\tex\_nonscript:D
480	\_kernel\_primitive:NN	\nonstopmode	\tex\_nonstopmode:D
481	\_kernel\_primitive:NN	\nulldelimiterspace	\tex\_nulldelimiterspace:D
482	\_kernel\_primitive:NN	\nullfont	\tex\_nullfont:D
483	\_kernel\_primitive:NN	\number	\tex\_number:D
484	\_kernel\_primitive:NN	\omit	\tex\_omit:D
485	\_kernel\_primitive:NN	\openin	\tex\_openin:D
486	\_kernel\_primitive:NN	\openout	\tex\_openout:D
487	\_kernel\_primitive:NN	\or	\tex\_or:D
488	\_kernel\_primitive:NN	\outer	\tex\_outer:D
489	\_kernel\_primitive:NN	\output	\tex\_output:D
490	\_kernel\_primitive:NN	\outputpenalty	\tex\_outputpenalty:D
491	\_kernel\_primitive:NN	\over	\tex\_over:D
492	\_kernel\_primitive:NN	\overfullrule	\tex\_overfullrule:D
493	\_kernel\_primitive:NN	\overline	\tex\_overline:D
494	\_kernel\_primitive:NN	\overwithdelims	\tex\_overwithdelims:D
495	\_kernel\_primitive:NN	\pagedepth	\tex\_pagedepth:D
496	\_kernel\_primitive:NN	\pagefilllstretch	\tex\_pagefilllstretch:D
497	\_kernel\_primitive:NN	\pagefillstretch	\tex\_pagefillstretch:D
498	\_kernel\_primitive:NN	\pagefilstretch	\tex\_pagefilstretch:D
499	\_kernel\_primitive:NN	\pagegoal	\tex\_pagegoal:D
500	\_kernel\_primitive:NN	\pageshrink	\tex\_pageshrink:D
501	\_kernel\_primitive:NN	\pagestretch	\tex\_pagestretch:D
502	\_kernel\_primitive:NN	\pagetotal	\tex\_pagetotal:D
503	\_kernel\_primitive:NN	\par	\tex\_par:D
504	\_kernel\_primitive:NN	\parfillskip	\tex\_parfillskip:D
505	\_kernel\_primitive:NN	\parindent	\tex\_parindent:D
506	\_kernel\_primitive:NN	\parshape	\tex\_parshape:D
507	\_kernel\_primitive:NN	\parskip	\tex\_parskip:D
508	\_kernel\_primitive:NN	\patterns	\tex\_patterns:D
509	\_kernel\_primitive:NN	\pausing	\tex\_pausing:D
510	\_kernel\_primitive:NN	\penalty	\tex\_penalty:D
511	\_kernel\_primitive:NN	\postdisplaypenalty	\tex\_postdisplaypenalty:D
512	\_kernel\_primitive:NN	\predisdisplaypenalty	\tex\_predisdisplaypenalty:D
513	\_kernel\_primitive:NN	\predisplaysize	\tex\_predisplaysize:D
514	\_kernel\_primitive:NN	\pretolerance	\tex\_pretolerance:D
515	\_kernel\_primitive:NN	\prevdepth	\tex\_prevdepth:D
516	\_kernel\_primitive:NN	\prevgraf	\tex\_prevgraf:D
517	\_kernel\_primitive:NN	\radical	\tex\_radical:D
518	\_kernel\_primitive:NN	\raise	\tex\_raise:D
519	\_kernel\_primitive:NN	\read	\tex\_read:D
520	\_kernel\_primitive:NN	\relax	\tex\_relax:D
521	\_kernel\_primitive:NN	\relpenalty	\tex\_relpenalty:D

522	\_kernel\_primitive:NN \right	\tex\_right:D
523	\_kernel\_primitive:NN \righthypenmin	\tex\_righthypenmin:D
524	\_kernel\_primitive:NN \rightskip	\tex\_rightskip:D
525	\_kernel\_primitive:NN \romannumeral	\tex\_romannumeral:D
526	\_kernel\_primitive:NN \scriptfont	\tex\_scriptfont:D
527	\_kernel\_primitive:NN \scriptscriptfont	\tex\_scriptscriptfont:D
528	\_kernel\_primitive:NN \scriptscriptstyle	\tex\_scriptscriptstyle:D
529	\_kernel\_primitive:NN \scriptspace	\tex\_scriptspace:D
530	\_kernel\_primitive:NN \scriptstyle	\tex\_scriptstyle:D
531	\_kernel\_primitive:NN \scrollmode	\tex\_scrollmode:D
532	\_kernel\_primitive:NN \setbox	\tex\_setbox:D
533	\_kernel\_primitive:NN \setlanguage	\tex\_setlanguage:D
534	\_kernel\_primitive:NN \sfcode	\tex\_sfcode:D
535	\_kernel\_primitive:NN \shipout	\tex\_shipout:D
536	\_kernel\_primitive:NN \show	\tex\_show:D
537	\_kernel\_primitive:NN \showbox	\tex\_showbox:D
538	\_kernel\_primitive:NN \showboxbreadth	\tex\_showboxbreadth:D
539	\_kernel\_primitive:NN \showboxdepth	\tex\_showboxdepth:D
540	\_kernel\_primitive:NN \showlists	\tex\_showlists:D
541	\_kernel\_primitive:NN \showthe	\tex\_showthe:D
542	\_kernel\_primitive:NN \skewchar	\tex\_skewchar:D
543	\_kernel\_primitive:NN \skip	\tex\_skip:D
544	\_kernel\_primitive:NN \skipdef	\tex\_skipdef:D
545	\_kernel\_primitive:NN \spacefactor	\tex\_spacefactor:D
546	\_kernel\_primitive:NN \spaceskip	\tex\_spaceskip:D
547	\_kernel\_primitive:NN \span	\tex\_span:D
548	\_kernel\_primitive:NN \special	\tex\_special:D
549	\_kernel\_primitive:NN \splitbotmark	\tex\_splitbotmark:D
550	\_kernel\_primitive:NN \splitfirstmark	\tex\_splitfirstmark:D
551	\_kernel\_primitive:NN \splitmaxdepth	\tex\_splitmaxdepth:D
552	\_kernel\_primitive:NN \splittopskip	\tex\_splittopskip:D
553	\_kernel\_primitive:NN \string	\tex\_string:D
554	\_kernel\_primitive:NN \tabskip	\tex\_tabskip:D
555	\_kernel\_primitive:NN \textfont	\tex\_textfont:D
556	\_kernel\_primitive:NN \textstyle	\tex\_textstyle:D
557	\_kernel\_primitive:NN \the	\tex\_the:D
558	\_kernel\_primitive:NN \thickmuskip	\tex\_thickmuskip:D
559	\_kernel\_primitive:NN \thinmuskip	\tex\_thinmuskip:D
560	\_kernel\_primitive:NN \time	\tex\_time:D
561	\_kernel\_primitive:NN \toks	\tex\_toks:D
562	\_kernel\_primitive:NN \toksdef	\tex\_toksdef:D
563	\_kernel\_primitive:NN \tolerance	\tex\_tolerance:D
564	\_kernel\_primitive:NN \topmark	\tex\_topmark:D
565	\_kernel\_primitive:NN \topskip	\tex\_topskip:D
566	\_kernel\_primitive:NN \tracingcommands	\tex\_tracingcommands:D
567	\_kernel\_primitive:NN \tracinglostchars	\tex\_tracinglostchars:D
568	\_kernel\_primitive:NN \tracingmacros	\tex\_tracingmacros:D
569	\_kernel\_primitive:NN \tracingonline	\tex\_tracingonline:D
570	\_kernel\_primitive:NN \tracingoutput	\tex\_tracingoutput:D
571	\_kernel\_primitive:NN \tracingpages	\tex\_tracingpages:D
572	\_kernel\_primitive:NN \tracingparagraphs	\tex\_tracingparagraphs:D
573	\_kernel\_primitive:NN \tracingrestores	\tex\_tracingrestores:D
574	\_kernel\_primitive:NN \tracingstats	\tex\_tracingstats:D
575	\_kernel\_primitive:NN \uccode	\tex\_uccode:D

576	\__kernel_primitive:NN	\uchyph	\tex_uchyph:D
577	\__kernel_primitive:NN	\underline	\tex_underline:D
578	\__kernel_primitive:NN	\unhbox	\tex_unhbox:D
579	\__kernel_primitive:NN	\unhcopy	\tex_unhcopy:D
580	\__kernel_primitive:NN	\unkern	\tex_unkern:D
581	\__kernel_primitive:NN	\unpenalty	\tex_unpenalty:D
582	\__kernel_primitive:NN	\unskip	\tex_unskip:D
583	\__kernel_primitive:NN	\unvbox	\tex_unvbox:D
584	\__kernel_primitive:NN	\unvcopy	\tex_unvcopy:D
585	\__kernel_primitive:NN	\uppercase	\tex_uppercase:D
586	\__kernel_primitive:NN	\vadjust	\tex_vadjust:D
587	\__kernel_primitive:NN	\valign	\tex_valign:D
588	\__kernel_primitive:NN	\vbadness	\tex_vbadness:D
589	\__kernel_primitive:NN	\vbox	\tex_vbox:D
590	\__kernel_primitive:NN	\vcenter	\tex_vcenter:D
591	\__kernel_primitive:NN	\vfil	\tex_vfil:D
592	\__kernel_primitive:NN	\vfill	\tex_vfill:D
593	\__kernel_primitive:NN	\vfilneg	\tex_vfilneg:D
594	\__kernel_primitive:NN	\vfuzz	\tex_vfuzz:D
595	\__kernel_primitive:NN	\voffset	\tex_voffset:D
596	\__kernel_primitive:NN	\vrule	\tex_vrule:D
597	\__kernel_primitive:NN	\vsize	\tex_vsize:D
598	\__kernel_primitive:NN	\vskip	\tex_vskip:D
599	\__kernel_primitive:NN	\vsplit	\tex_vsplit:D
600	\__kernel_primitive:NN	\vss	\tex_vss:D
601	\__kernel_primitive:NN	\vtop	\tex_vtop:D
602	\__kernel_primitive:NN	\wd	\tex_wd:D
603	\__kernel_primitive:NN	\widowpenalty	\tex_widowpenalty:D
604	\__kernel_primitive:NN	\write	\tex_write:D
605	\__kernel_primitive:NN	\xdef	\tex_xdef:D
606	\__kernel_primitive:NN	\xleaders	\tex_xleaders:D
607	\__kernel_primitive:NN	\xspaceskip	\tex_xspaceskip:D
608	\__kernel_primitive:NN	\year	\tex_year:D

Since L<sup>A</sup>T<sub>E</sub>X3 requires at least the  $\varepsilon$ -T<sub>E</sub>X extensions, we also rename the additional primitives. These are all given the prefix `\etex_`.

609	\__kernel_primitive:NN	\beginL	\etex_beginL:D
610	\__kernel_primitive:NN	\beginR	\etex_beginR:D
611	\__kernel_primitive:NN	\botmarks	\etex_botmarks:D
612	\__kernel_primitive:NN	\clubpenalties	\etex_clubpenalties:D
613	\__kernel_primitive:NN	\currentgrouplevel	\etex_currentgrouplevel:D
614	\__kernel_primitive:NN	\currentgrouptype	\etex_currentgrouptype:D
615	\__kernel_primitive:NN	\currentifbranch	\etex_currentifbranch:D
616	\__kernel_primitive:NN	\currentiflevel	\etex_currentiflevel:D
617	\__kernel_primitive:NN	\currentifttype	\etex_currentifttype:D
618	\__kernel_primitive:NN	\detokenize	\etex_detokenize:D
619	\__kernel_primitive:NN	\dimexpr	\etex_dimexpr:D
620	\__kernel_primitive:NN	\displaywidowpenalties	\etex_displaywidowpenalties:D
621	\__kernel_primitive:NN	\endL	\etex_endL:D
622	\__kernel_primitive:NN	\endR	\etex_endR:D
623	\__kernel_primitive:NN	\eTeXrevision	\etex_eTeXrevision:D
624	\__kernel_primitive:NN	\eTeXversion	\etex_eTeXversion:D
625	\__kernel_primitive:NN	\everyeof	\etex_everyeof:D
626	\__kernel_primitive:NN	\firstmarks	\etex_firstmarks:D

627	<code>\__kernel_primitive:NN \fontchardp</code>	<code>\etex_fontchardp:D</code>
628	<code>\__kernel_primitive:NN \fontcharht</code>	<code>\etex_fontcharht:D</code>
629	<code>\__kernel_primitive:NN \fontcharic</code>	<code>\etex_fontcharic:D</code>
630	<code>\__kernel_primitive:NN \fontcharwd</code>	<code>\etex_fontcharwd:D</code>
631	<code>\__kernel_primitive:NN \glueexpr</code>	<code>\etex_glueexpr:D</code>
632	<code>\__kernel_primitive:NN \glueshrink</code>	<code>\etex_glueshrink:D</code>
633	<code>\__kernel_primitive:NN \glueshrinkorder</code>	<code>\etex_glueshrinkorder:D</code>
634	<code>\__kernel_primitive:NN \gluestretch</code>	<code>\etex_gluestretch:D</code>
635	<code>\__kernel_primitive:NN \gluestretchorder</code>	<code>\etex_gluestretchorder:D</code>
636	<code>\__kernel_primitive:NN \gluetomu</code>	<code>\etex_gluetomu:D</code>
637	<code>\__kernel_primitive:NN \ifcsname</code>	<code>\etex_ifcsname:D</code>
638	<code>\__kernel_primitive:NN \ifdefined</code>	<code>\etex_ifdefined:D</code>
639	<code>\__kernel_primitive:NN \iffontchar</code>	<code>\etex_iffontchar:D</code>
640	<code>\__kernel_primitive:NN \interactionmode</code>	<code>\etex_interactionmode:D</code>
641	<code>\__kernel_primitive:NN \interlinepenalties</code>	<code>\etex_interlinepenalties:D</code>
642	<code>\__kernel_primitive:NN \lastlinefit</code>	<code>\etex_lastlinefit:D</code>
643	<code>\__kernel_primitive:NN \lastnodetype</code>	<code>\etex_lastnodetype:D</code>
644	<code>\__kernel_primitive:NN \marks</code>	<code>\etex_marks:D</code>
645	<code>\__kernel_primitive:NN \middle</code>	<code>\etex_middle:D</code>
646	<code>\__kernel_primitive:NN \muexpr</code>	<code>\etex_muexpr:D</code>
647	<code>\__kernel_primitive:NN \mutoglua</code>	<code>\etex_mutoglua:D</code>
648	<code>\__kernel_primitive:NN \numexpr</code>	<code>\etex_numexpr:D</code>
649	<code>\__kernel_primitive:NN \pagediscards</code>	<code>\etex_pagediscards:D</code>
650	<code>\__kernel_primitive:NN \parshapedimen</code>	<code>\etex_parshapedimen:D</code>
651	<code>\__kernel_primitive:NN \parshapeindent</code>	<code>\etex_parshapeindent:D</code>
652	<code>\__kernel_primitive:NN \parshapelength</code>	<code>\etex_parshapelength:D</code>
653	<code>\__kernel_primitive:NN \predisplaydirection</code>	<code>\etex_predisplaydirection:D</code>
654	<code>\__kernel_primitive:NN \protected</code>	<code>\etex_protected:D</code>
655	<code>\__kernel_primitive:NN \readline</code>	<code>\etex_readline:D</code>
656	<code>\__kernel_primitive:NN \savingshyphcodes</code>	<code>\etex_savingshyphcodes:D</code>
657	<code>\__kernel_primitive:NN \savingsvdiscards</code>	<code>\etex_savingsvdiscards:D</code>
658	<code>\__kernel_primitive:NN \scantokens</code>	<code>\etex_scantokens:D</code>
659	<code>\__kernel_primitive:NN \showgroups</code>	<code>\etex_showgroups:D</code>
660	<code>\__kernel_primitive:NN \showifs</code>	<code>\etex_showifs:D</code>
661	<code>\__kernel_primitive:NN \showtokens</code>	<code>\etex_showtokens:D</code>
662	<code>\__kernel_primitive:NN \splitbotmarks</code>	<code>\etex_splitbotmarks:D</code>
663	<code>\__kernel_primitive:NN \splitdiscards</code>	<code>\etex_splitdiscards:D</code>
664	<code>\__kernel_primitive:NN \splitfirstmarks</code>	<code>\etex_splitfirstmarks:D</code>
665	<code>\__kernel_primitive:NN \TeXXeTstate</code>	<code>\etex_TeXeTstate:D</code>
666	<code>\__kernel_primitive:NN \topmarks</code>	<code>\etex_topmarks:D</code>
667	<code>\__kernel_primitive:NN \tracingassigns</code>	<code>\etex_tracingassigns:D</code>
668	<code>\__kernel_primitive:NN \tracinggroups</code>	<code>\etex_tracinggroups:D</code>
669	<code>\__kernel_primitive:NN \tracingifs</code>	<code>\etex_tracingifs:D</code>
670	<code>\__kernel_primitive:NN \tracingnesting</code>	<code>\etex_tracingnesting:D</code>
671	<code>\__kernel_primitive:NN \tracingscantokens</code>	<code>\etex_tracingscantokens:D</code>
672	<code>\__kernel_primitive:NN \unexpanded</code>	<code>\etex_unexpanded:D</code>
673	<code>\__kernel_primitive:NN \unless</code>	<code>\etex_unless:D</code>
674	<code>\__kernel_primitive:NN \widowpenalties</code>	<code>\etex_widowpenalties:D</code>

The newer primitives are more complex: there are an awful lot of them, and we don't use them all at the moment. So the following is selective, based on those also available in LuaTeX or used in expl3. In the case of the pdfTeX primitives, we retain `pdf` at the start of the names *only* for directly PDF-related primitives, as there are a lot of pdfTeX primitives that start `\pdf...` but are not related to PDF output. These ones related to

PDF output or only work in PDF mode.

675	\_kernel\_primitive:NN	\pdfannot	\pdfTEX\_pdfannot:D
676	\_kernel\_primitive:NN	\pdfcatalog	\pdfTEX\_pdfcatalog:D
677	\_kernel\_primitive:NN	\pdfcompresslevel	\pdfTEX\_pdfcompresslevel:D
678	\_kernel\_primitive:NN	\pdfcolorstack	\pdfTEX\_pdfcolorstack:D
679	\_kernel\_primitive:NN	\pdfcolorstackinit	\pdfTEX\_pdfcolorstackinit:D
680	\_kernel\_primitive:NN	\pdfcreationdate	\pdfTEX\_pdfcreationdate:D
681	\_kernel\_primitive:NN	\pdfdecimaldigits	\pdfTEX\_pdfdecimaldigits:D
682	\_kernel\_primitive:NN	\pdfdest	\pdfTEX\_pdfdest:D
683	\_kernel\_primitive:NN	\pdfdestmargin	\pdfTEX\_pdfdestmargin:D
684	\_kernel\_primitive:NN	\pdfendlink	\pdfTEX\_pdfendlink:D
685	\_kernel\_primitive:NN	\pdfendthread	\pdfTEX\_pdfendthread:D
686	\_kernel\_primitive:NN	\pdffontattr	\pdfTEX\_pdffontattr:D
687	\_kernel\_primitive:NN	\pdffontname	\pdfTEX\_pdffontname:D
688	\_kernel\_primitive:NN	\pdffontobjnum	\pdfTEX\_pdffontobjnum:D
689	\_kernel\_primitive:NN	\pdfgamma	\pdfTEX\_pdfgamma:D
690	\_kernel\_primitive:NN	\pdfimageapplygamma	\pdfTEX\_pdfimageapplygamma:D
691	\_kernel\_primitive:NN	\pdfimagegamma	\pdfTEX\_pdfimagegamma:D
692	\_kernel\_primitive:NN	\pdfgentounicode	\pdfTEX\_pdfgentounicode:D
693	\_kernel\_primitive:NN	\pdfglyptounicode	\pdfTEX\_pdfglyptounicode:D
694	\_kernel\_primitive:NN	\pdfhorigin	\pdfTEX\_pdfhorigin:D
695	\_kernel\_primitive:NN	\pdfimagehicolor	\pdfTEX\_pdfimagehicolor:D
696	\_kernel\_primitive:NN	\pdfimageresolution	\pdfTEX\_pdfimageresolution:D
697	\_kernel\_primitive:NN	\pdfincludechars	\pdfTEX\_pdfincludechars:D
698	\_kernel\_primitive:NN	\pdfinclusioncopyfonts	\pdfTEX\_pdfinclusioncopyfonts:D
699	\_kernel\_primitive:NN	\pdfinclusionerrorlevel	\pdfTEX\_pdfinclusionerrorlevel:D
700	\_kernel\_primitive:NN	\pdfinfo	\pdfTEX\_pdfinfo:D
701	\_kernel\_primitive:NN	\pdflastannot	\pdfTEX\_pdflastannot:D
702	\_kernel\_primitive:NN	\pdflastlink	\pdfTEX\_pdflastlink:D
703	\_kernel\_primitive:NN	\pdflastobj	\pdfTEX\_pdflastobj:D
704	\_kernel\_primitive:NN	\pdflastxform	\pdfTEX\_pdflastxform:D
705	\_kernel\_primitive:NN	\pdflastximage	\pdfTEX\_pdflastximage:D
706	\_kernel\_primitive:NN	\pdflastximagecolordepth	\pdfTEX\_pdflastximagecolordepth:D
707	\_kernel\_primitive:NN	\pdflastximagepages	\pdfTEX\_pdflastximagepages:D
708	\_kernel\_primitive:NN	\pdflinkmargin	\pdfTEX\_pdflinkmargin:D
709	\_kernel\_primitive:NN	\pdfliteral	\pdfTEX\_pdfliteral:D
710	\_kernel\_primitive:NN	\pdfminorversion	\pdfTEX\_pdfminorversion:D
711	\_kernel\_primitive:NN	\pdfnames	\pdfTEX\_pdfnames:D
712	\_kernel\_primitive:NN	\pdfobj	\pdfTEX\_pdfobj:D
713	\_kernel\_primitive:NN	\pdfobjcompresslevel	\pdfTEX\_pdfobjcompresslevel:D
714	\_kernel\_primitive:NN	\pdfoutline	\pdfTEX\_pdfoutline:D
715	\_kernel\_primitive:NN	\pdfoutput	\pdfTEX\_pdfoutput:D
716	\_kernel\_primitive:NN	\pdfpageattr	\pdfTEX\_pdfpageattr:D
717	\_kernel\_primitive:NN	\pdfpagebox	\pdfTEX\_pdfpagebox:D
718	\_kernel\_primitive:NN	\pdfpageref	\pdfTEX\_pdfpageref:D
719	\_kernel\_primitive:NN	\pdfpageresources	\pdfTEX\_pdfpageresources:D
720	\_kernel\_primitive:NN	\pdfpagesattr	\pdfTEX\_pdfpagesattr:D
721	\_kernel\_primitive:NN	\pdfrefobj	\pdfTEX\_pdfrefobj:D
722	\_kernel\_primitive:NN	\pdfrefxform	\pdfTEX\_pdfrefxform:D
723	\_kernel\_primitive:NN	\pdfrefximage	\pdfTEX\_pdfrefximage:D
724	\_kernel\_primitive:NN	\pdfrestore	\pdfTEX\_pdfrestore:D
725	\_kernel\_primitive:NN	\pdfretval	\pdfTEX\_pdfretval:D
726	\_kernel\_primitive:NN	\pdfsave	\pdfTEX\_pdfsave:D
727	\_kernel\_primitive:NN	\pdfsetmatrix	\pdfTEX\_pdfsetmatrix:D



728	\_kernel\_primitive:NN	\pdfstartlink	\pdfTeX\_pdfstartlink:D
729	\_kernel\_primitive:NN	\pdfstartthread	\pdfTeX\_pdfstartthread:D
730	\_kernel\_primitive:NN	\pdfsuppressptexinfo	\pdfTeX\_pdfsuppressptexinfo:D
731	\_kernel\_primitive:NN	\pdfthread	\pdfTeX\_pdfthread:D
732	\_kernel\_primitive:NN	\pdfthreadmargin	\pdfTeX\_pdfthreadmargin:D
733	\_kernel\_primitive:NN	\pdftrailer	\pdfTeX\_pdftrailer:D
734	\_kernel\_primitive:NN	\pdfuniqueresname	\pdfTeX\_pdfuniqueresname:D
735	\_kernel\_primitive:NN	\pdfvorigin	\pdfTeX\_pdfvorigin:D
736	\_kernel\_primitive:NN	\pdfxform	\pdfTeX\_pdfxform:D
737	\_kernel\_primitive:NN	\pdfxformattr	\pdfTeX\_pdfxformattr:D
738	\_kernel\_primitive:NN	\pdfxformname	\pdfTeX\_pdfxformname:D
739	\_kernel\_primitive:NN	\pdfxformresources	\pdfTeX\_pdfxformresources:D
740	\_kernel\_primitive:NN	\pdfximage	\pdfTeX\_pdfximage:D
741	\_kernel\_primitive:NN	\pdfximagebbox	\pdfTeX\_pdfximagebbox:D

While these are not.

742	\_kernel\_primitive:NN	\ifpdfabsdim	\pdfTeX\_ifabsdim:D
743	\_kernel\_primitive:NN	\ifpdfabsnum	\pdfTeX\_ifabsnum:D
744	\_kernel\_primitive:NN	\ifpdfprimitive	\pdfTeX\_ifprimitive:D
745	\_kernel\_primitive:NN	\pdfadjustspacing	\pdfTeX\_adjustspacing:D
746	\_kernel\_primitive:NN	\pdfcopyfont	\pdfTeX\_copyfont:D
747	\_kernel\_primitive:NN	\pdfdraftmode	\pdfTeX\_draftmode:D
748	\_kernel\_primitive:NN	\pdfeachlinedepth	\pdfTeX\_eachlinedepth:D
749	\_kernel\_primitive:NN	\pdfeachlineheight	\pdfTeX\_eachlineheight:D
750	\_kernel\_primitive:NN	\pdffilemoddate	\pdfTeX\_filemoddate:D
751	\_kernel\_primitive:NN	\pdffilesize	\pdfTeX\_filesize:D
752	\_kernel\_primitive:NN	\pdffirstlineheight	\pdfTeX\_firstlineheight:D
753	\_kernel\_primitive:NN	\pdffontexpand	\pdfTeX\_fontexpand:D
754	\_kernel\_primitive:NN	\pdffontsize	\pdfTeX\_fontsize:D
755	\_kernel\_primitive:NN	\pdfignoreddimen	\pdfTeX\_ignoreddimen:D
756	\_kernel\_primitive:NN	\pdfinsertht	\pdfTeX\_insertht:D
757	\_kernel\_primitive:NN	\pdflastlinedepth	\pdfTeX\_lastlinedepth:D
758	\_kernel\_primitive:NN	\pdflastxpos	\pdfTeX\_lastxpos:D
759	\_kernel\_primitive:NN	\pdflastypos	\pdfTeX\_lastypos:D
760	\_kernel\_primitive:NN	\pdfmapfile	\pdfTeX\_mapfile:D
761	\_kernel\_primitive:NN	\pdfmapline	\pdfTeX\_mapline:D
762	\_kernel\_primitive:NN	\pdfmdfivesum	\pdfTeX\_mdfivesum:D
763	\_kernel\_primitive:NN	\pdfnoligatures	\pdfTeX\_noligatures:D
764	\_kernel\_primitive:NN	\pdfnormaldeviate	\pdfTeX\_normaldeviate:D
765	\_kernel\_primitive:NN	\pdfpageheight	\pdfTeX\_pageheight:D
766	\_kernel\_primitive:NN	\pdfpagewidth	\pdfTeX\_pagewidth:D
767	\_kernel\_primitive:NN	\pdfpkmode	\pdfTeX\_pkmode:D
768	\_kernel\_primitive:NN	\pdfpkresolution	\pdfTeX\_pkresolution:D
769	\_kernel\_primitive:NN	\pdfprimitive	\pdfTeX\_primitive:D
770	\_kernel\_primitive:NN	\pdfprotrudechars	\pdfTeX\_protrudechars:D
771	\_kernel\_primitive:NN	\pdfpxdimen	\pdfTeX\_pxdimen:D
772	\_kernel\_primitive:NN	\pdfrandomseed	\pdfTeX\_randomseed:D
773	\_kernel\_primitive:NN	\pdfsavepos	\pdfTeX\_savepos:D
774	\_kernel\_primitive:NN	\pdfstrcmp	\pdfTeX\_strcmp:D
775	\_kernel\_primitive:NN	\pdfsetrandomseed	\pdfTeX\_setrandomseed:D
776	\_kernel\_primitive:NN	\pdfshellescape	\pdfTeX\_shellescape:D
777	\_kernel\_primitive:NN	\pdftracingfonts	\pdfTeX\_tracingfonts:D
778	\_kernel\_primitive:NN	\pdfuniformdeviate	\pdfTeX\_uniformdeviate:D

The version primitives are not related to PDF mode but are related to pdfTeX so retain

the full prefix.

```

779 \__kernel_primitive:NN \pdfetxbanner \pdfetx_pdfetxbanner:D
780 \__kernel_primitive:NN \pdfetxrevision \pdfetx_pdfetxrevision:D
781 \__kernel_primitive:NN \pdfetxversion \pdfetx_pdfetxversion:D

```

These ones appear in pdfTeX but don't have pdf in the name at all. (\synctex is odd as it's really not from pdfTeX but from SyncTeX!)

```

782 \__kernel_primitive:NN \efcode \pdfetx_efcode:D
783 \__kernel_primitive:NN \ifincsname \pdfetx_ifincsname:D
784 \__kernel_primitive:NN \leftmarginkern \pdfetx_leftmarginkern:D
785 \__kernel_primitive:NN \letterspacefont \pdfetx_letterspacefont:D
786 \__kernel_primitive:NN \lpcode \pdfetx_lpcode:D
787 \__kernel_primitive:NN \quitvmode \pdfetx_quitvmode:D
788 \__kernel_primitive:NN \rightmarginkern \pdfetx_rightmarginkern:D
789 \__kernel_primitive:NN \rpcode \pdfetx_rpcode:D
790 \__kernel_primitive:NN \synctex \pdfetx_synctex:D
791 \__kernel_primitive:NN \tagcode \pdfetx_tagcode:D

```

Post pdfTeX primitive availability gets more complex. Both XeTeX and LuaTeX have varying names for some primitives from pdfTeX. Particularly for LuaTeX tracking all of that would be hard. Instead, we now check that we only save primitives if they actually exist.

```

792 </initex | names | package>
793 <{*initex | package>
794 \tex_long:D \tex_def:D \use_ii:nn #1#2 {#2}
795 \tex_long:D \tex_def:D \use_none:n #1 { }
796 \tex_long:D \tex_def:D \__kernel_primitive:NN #1#2
797 {
798 \etex_ifdefined:D #1
799 \tex_expandafter:D \use_ii:nn
800 \tex_fi:D
801 \use_none:n { \tex_global:D \tex_let:D #2 #1 }
802 <{*initex>
803 \tex_global:D \tex_let:D #1 \tex_undefined:D
804 </initex>
805 }
806 </initex | package>
807 <{*initex | names | package>

```

XeTeX-specific primitives. Note that XeTeX's \strcmp is handled earlier and is “rolled up” into \pdfstrcmp. With the exception of the version primitives these don't carry XeTeX through into the “base” name. A few cross-compatibility names which lack the pdf of the original are handled later.

```

808 \__kernel_primitive:NN \suppressfontnotfounderror \xetex_suppressfontnotfounderror:D
809 \__kernel_primitive:NN \XeTeXcharclass \xetex_charclass:D
810 \__kernel_primitive:NN \XeTeXcharglyph \xetex_charglyph:D
811 \__kernel_primitive:NN \XeTeXcountfeatures \xetex_countfeatures:D
812 \__kernel_primitive:NN \XeTeXcountglyphs \xetex_countglyphs:D
813 \__kernel_primitive:NN \XeTeXcountselectors \xetex_countselectors:D
814 \__kernel_primitive:NN \XeTeXcountvariations \xetex_countvariations:D
815 \__kernel_primitive:NN \XeTeXdefaultencoding \xetex_defaultencoding:D
816 \__kernel_primitive:NN \XeTeXdashbreakstate \xetex_dashbreakstate:D
817 \__kernel_primitive:NN \XeTeXfeaturecode \xetex_featurecode:D
818 \__kernel_primitive:NN \XeTeXfeaturename \xetex_featurename:D

```

819	<code>\__kernel_primitive:NN \XeTeXfindfeaturebyname</code>	<code>\xetex_findfeaturebyname:D</code>
820	<code>\__kernel_primitive:NN \XeTeXfindselectorbyname</code>	<code>\xetex_findselectorbyname:D</code>
821	<code>\__kernel_primitive:NN \XeTeXfindvariationbyname</code>	<code>\xetex_findvariationbyname:D</code>
822	<code>\__kernel_primitive:NN \XeTeXfirstfontchar</code>	<code>\xetex_firstfontchar:D</code>
823	<code>\__kernel_primitive:NN \XeTeXfonttype</code>	<code>\xetex_fonttype:D</code>
824	<code>\__kernel_primitive:NN \XeTeXgenerateactualtext</code>	<code>\xetex_generateactualtext:D</code>
825	<code>\__kernel_primitive:NN \XeTeXglyph</code>	<code>\xetex_glyph:D</code>
826	<code>\__kernel_primitive:NN \XeTeXglyphbounds</code>	<code>\xetex_glyphbounds:D</code>
827	<code>\__kernel_primitive:NN \XeTeXglyphindex</code>	<code>\xetex_glyphindex:D</code>
828	<code>\__kernel_primitive:NN \XeTeXglyphname</code>	<code>\xetex_glyphname:D</code>
829	<code>\__kernel_primitive:NN \XeTeXinputencoding</code>	<code>\xetex_inputencoding:D</code>
830	<code>\__kernel_primitive:NN \XeTeXinputnormalization</code>	<code>\xetex_inputnormalization:D</code>
831	<code>\__kernel_primitive:NN \XeTeXinterchartokenstate</code>	<code>\xetex_interchartokenstate:D</code>
832	<code>\__kernel_primitive:NN \XeTeXinterchartoks</code>	<code>\xetex_interchartoks:D</code>
833	<code>\__kernel_primitive:NN \XeTeXisdefaultselector</code>	<code>\xetex_isdefaultselector:D</code>
834	<code>\__kernel_primitive:NN \XeTeXisexclusivefeature</code>	<code>\xetex_isexclusivefeature:D</code>
835	<code>\__kernel_primitive:NN \XeTeXlastfontchar</code>	<code>\xetex_lastfontchar:D</code>
836	<code>\__kernel_primitive:NN \XeTeXlinebreakskip</code>	<code>\xetex_linebreakskip:D</code>
837	<code>\__kernel_primitive:NN \XeTeXlinebreaklocale</code>	<code>\xetex_linebreaklocale:D</code>
838	<code>\__kernel_primitive:NN \XeTeXlinebreakpenalty</code>	<code>\xetex_linebreakpenalty:D</code>
839	<code>\__kernel_primitive:NN \XeTeXOTcountfeatures</code>	<code>\xetex_OTcountfeatures:D</code>
840	<code>\__kernel_primitive:NN \XeTeXOTcountlanguages</code>	<code>\xetex_OTcountlanguages:D</code>
841	<code>\__kernel_primitive:NN \XeTeXOTcountscripts</code>	<code>\xetex_OTcountscripts:D</code>
842	<code>\__kernel_primitive:NN \XeTeXOTfeaturetag</code>	<code>\xetex_OTfeaturetag:D</code>
843	<code>\__kernel_primitive:NN \XeTeXOTlanguagetag</code>	<code>\xetex_OTlanguagetag:D</code>
844	<code>\__kernel_primitive:NN \XeTeXOTscripttag</code>	<code>\xetex_OTscripttag:D</code>
845	<code>\__kernel_primitive:NN \XeTeXpdffile</code>	<code>\xetex_pdffile:D</code>
846	<code>\__kernel_primitive:NN \XeTeXpdfpagecount</code>	<code>\xetex_pdfpagecount:D</code>
847	<code>\__kernel_primitive:NN \XeTeXpicfile</code>	<code>\xetex_picfile:D</code>
848	<code>\__kernel_primitive:NN \XeTeXselectorname</code>	<code>\xetex_selectorname:D</code>
849	<code>\__kernel_primitive:NN \XeTeXtracingfonts</code>	<code>\xetex_tracingfonts:D</code>
850	<code>\__kernel_primitive:NN \XeTeXupwardsmode</code>	<code>\xetex_upwardsmode:D</code>
851	<code>\__kernel_primitive:NN \XeTeXuseglyphmetrics</code>	<code>\xetex_useglyphmetrics:D</code>
852	<code>\__kernel_primitive:NN \XeTeXvariation</code>	<code>\xetex_variation:D</code>
853	<code>\__kernel_primitive:NN \XeTeXvariationdefault</code>	<code>\xetex_variationdefault:D</code>
854	<code>\__kernel_primitive:NN \XeTeXvariationmax</code>	<code>\xetex_variationmax:D</code>
855	<code>\__kernel_primitive:NN \XeTeXvariationmin</code>	<code>\xetex_variationmin:D</code>
856	<code>\__kernel_primitive:NN \XeTeXvariationname</code>	<code>\xetex_variationname:D</code>

The version primitives retain XeTeX.

857	<code>\__kernel_primitive:NN \XeTeXrevision</code>	<code>\xetex_XeTeXrevision:D</code>
858	<code>\__kernel_primitive:NN \XeTeXversion</code>	<code>\xetex_XeTeXversion:D</code>

Primitives from pdfTeX that XeTeX renames: also helps with LuaTeX.

859	<code>\__kernel_primitive:NN \mdfivesum</code>	<code>\pdfTEX_mdfivesum:D</code>
860	<code>\__kernel_primitive:NN \ifprimitive</code>	<code>\pdfTEX_ifprimitive:D</code>
861	<code>\__kernel_primitive:NN \primitive</code>	<code>\pdfTEX_primitive:D</code>
862	<code>\__kernel_primitive:NN \shellescape</code>	<code>\pdfTEX_shellescape:D</code>

Primitives from LuaTeX, some of which have been ported back to XeTeX. Notice that `\expanded` was intended for pdfTeX 1.50 but as that was not released we call this a LuaTeX primitive.

863	<code>\__kernel_primitive:NN \alignmark</code>	<code>\luaTEX_alignmark:D</code>
864	<code>\__kernel_primitive:NN \aligntab</code>	<code>\luaTEX_aligntab:D</code>
865	<code>\__kernel_primitive:NN \attribute</code>	<code>\luaTEX_attribute:D</code>

866	\_kernel\_primitive:NN	\attributedef	\luatex\_attributedef:D
867	\_kernel\_primitive:NN	\automatichyphenpenalty	\luatex\_automatichyphenpenalty:D
868	\_kernel\_primitive:NN	\beginscname	\luatex\_beginscname:D
869	\_kernel\_primitive:NN	\catcodetable	\luatex\_catcodetable:D
870	\_kernel\_primitive:NN	\clearmarks	\luatex\_clearmarks:D
871	\_kernel\_primitive:NN	\crampeddisplaystyle	\luatex\_crampeddisplaystyle:D
872	\_kernel\_primitive:NN	\crampedscriptscriptstyle	\luatex\_crampedscriptscriptstyle:D
873	\_kernel\_primitive:NN	\crampedscriptstyle	\luatex\_crampedscriptstyle:D
874	\_kernel\_primitive:NN	\crampedtextstyle	\luatex\_crampedtextstyle:D
875	\_kernel\_primitive:NN	\directlua	\luatex\_directlua:D
876	\_kernel\_primitive:NN	\dviextension	\luatex\_dviextension:D
877	\_kernel\_primitive:NN	\dvifedback	\luatex\_dvifedback:D
878	\_kernel\_primitive:NN	\dvivariable	\luatex\_dvivariable:D
879	\_kernel\_primitive:NN	\etoksapp	\luatex\_etoksapp:D
880	\_kernel\_primitive:NN	\etokspre	\luatex\_etokspre:D
881	\_kernel\_primitive:NN	\explicithyphenpenalty	\luatex\_explicithyphenpenalty:D
882	\_kernel\_primitive:NN	\expanded	\luatex\_expanded:D
883	\_kernel\_primitive:NN	\firstvalidlanguage	\luatex\_firstvalidlanguage:D
884	\_kernel\_primitive:NN	\fontid	\luatex\_fontid:D
885	\_kernel\_primitive:NN	\formatname	\luatex\_formatname:D
886	\_kernel\_primitive:NN	\hjcode	\luatex\_hjcode:D
887	\_kernel\_primitive:NN	\hpack	\luatex\_hpack:D
888	\_kernel\_primitive:NN	\hyphenationbounds	\luatex\_hyphenationbounds:D
889	\_kernel\_primitive:NN	\hyphenationmin	\luatex\_hyphenationmin:D
890	\_kernel\_primitive:NN	\hyphenpenaltymode	\luatex\_hyphenpenaltymode:D
891	\_kernel\_primitive:NN	\gleaders	\luatex\_gleaders:D
892	\_kernel\_primitive:NN	\initcatcodetable	\luatex\_initcatcodetable:D
893	\_kernel\_primitive:NN	\lastnamedcs	\luatex\_lastnamedcs:D
894	\_kernel\_primitive:NN	\latelua	\luatex\_latelua:D
895	\_kernel\_primitive:NN	\letcharcode	\luatex\_letcharcode:D
896	\_kernel\_primitive:NN	\luaescapestring	\luatex\_luaescapestring:D
897	\_kernel\_primitive:NN	\luafunction	\luatex\_luafunction:D
898	\_kernel\_primitive:NN	\luatexbanner	\luatex\_luatexbanner:D
899	\_kernel\_primitive:NN	\luatexdatestamp	\luatex\_luatexdatestamp:D
900	\_kernel\_primitive:NN	\luatexrevision	\luatex\_luatexrevision:D
901	\_kernel\_primitive:NN	\luatexversion	\luatex\_luatexversion:D
902	\_kernel\_primitive:NN	\mathdisplayskipmode	\luatex\_mathdisplayskipmode:D
903	\_kernel\_primitive:NN	\matheqnogapstep	\luatex\_matheqnogapstep:D
904	\_kernel\_primitive:NN	\mathnolimitsmode	\luatex\_mathnolimitsmode:D
905	\_kernel\_primitive:NN	\mathoption	\luatex\_mathoption:D
906	\_kernel\_primitive:NN	\mathrulesfam	\luatex\_mathrulesfam:D
907	\_kernel\_primitive:NN	\mathscriptsmode	\luatex\_mathscriptsmode:D
908	\_kernel\_primitive:NN	\mathstyle	\luatex\_mathstyle:D
909	\_kernel\_primitive:NN	\mathsurroundmode	\luatex\_mathsurroundmode:D
910	\_kernel\_primitive:NN	\mathsurroundskip	\luatex\_mathsurroundskip:D
911	\_kernel\_primitive:NN	\nohrule	\luatex\_nohrule:D
912	\_kernel\_primitive:NN	\nokerns	\luatex\_nokerns:D
913	\_kernel\_primitive:NN	\noligs	\luatex\_noligs:D
914	\_kernel\_primitive:NN	\nospaces	\luatex\_nospaces:D
915	\_kernel\_primitive:NN	\novrule	\luatex\_novrule:D
916	\_kernel\_primitive:NN	\outputbox	\luatex\_outputbox:D
917	\_kernel\_primitive:NN	\pagebottomoffset	\luatex\_pagebottomoffset:D
918	\_kernel\_primitive:NN	\pageleftoffset	\luatex\_pageleftoffset:D
919	\_kernel\_primitive:NN	\pagerightoffset	\luatex\_pagerightoffset:D

920	<code>\__kernel_primitive:NN \pagetopoffset</code>	<code>\luatex_pagetopoffset:D</code>
921	<code>\__kernel_primitive:NN \pdfextension</code>	<code>\luatex_pdfextension:D</code>
922	<code>\__kernel_primitive:NN \pdffeedback</code>	<code>\luatex_pdffeedback:D</code>
923	<code>\__kernel_primitive:NN \pdfvariable</code>	<code>\luatex_pdfvariable:D</code>
924	<code>\__kernel_primitive:NN \postexhyphenchar</code>	<code>\luatex_postexhyphenchar:D</code>
925	<code>\__kernel_primitive:NN \posthyphenchar</code>	<code>\luatex_posthyphenchar:D</code>
926	<code>\__kernel_primitive:NN \predisplaygapfactor</code>	<code>\luatex_predisplaygapfactor:D</code>
927	<code>\__kernel_primitive:NN \preexhyphenchar</code>	<code>\luatex_preexhyphenchar:D</code>
928	<code>\__kernel_primitive:NN \prehyphenchar</code>	<code>\luatex_prehyphenchar:D</code>
929	<code>\__kernel_primitive:NN \savecatcodetable</code>	<code>\luatex_savecatcodetable:D</code>
930	<code>\__kernel_primitive:NN \scantexttokens</code>	<code>\luatex_scantexttokens:D</code>
931	<code>\__kernel_primitive:NN \setfontid</code>	<code>\luatex_setfontid:D</code>
932	<code>\__kernel_primitive:NN \shapemode</code>	<code>\luatex_shapemode:D</code>
933	<code>\__kernel_primitive:NN \suppressifcsnameerror</code>	<code>\luatex_suppressifcsnameerror:D</code>
934	<code>\__kernel_primitive:NN \suppresslongerror</code>	<code>\luatex_suppresslongerror:D</code>
935	<code>\__kernel_primitive:NN \suppressmathparerror</code>	<code>\luatex_suppressmathparerror:D</code>
936	<code>\__kernel_primitive:NN \suppressoutererror</code>	<code>\luatex_suppressoutererror:D</code>
937	<code>\__kernel_primitive:NN \toksapp</code>	<code>\luatex_toksapp:D</code>
938	<code>\__kernel_primitive:NN \tokspre</code>	<code>\luatex_tokspre:D</code>
939	<code>\__kernel_primitive:NN \tpack</code>	<code>\luatex_tpack:D</code>
940	<code>\__kernel_primitive:NN \vpack</code>	<code>\luatex_vpack:D</code>

Slightly more awkward are the directional primitives in LuaTeX. These come from Omega/Aleph, but we do not support those engines and so it seems most sensible to treat them as LuaTeX primitives for prefix purposes. One here is “new” but fits into the general set.

941	<code>\__kernel_primitive:NN \bodydir</code>	<code>\luatex_bodydir:D</code>
942	<code>\__kernel_primitive:NN \boxdir</code>	<code>\luatex_boxdir:D</code>
943	<code>\__kernel_primitive:NN \leftghost</code>	<code>\luatex_leftghost:D</code>
944	<code>\__kernel_primitive:NN \linedir</code>	<code>\luatex_linedir:D</code>
945	<code>\__kernel_primitive:NN \localbrokenpenalty</code>	<code>\luatex_localbrokenpenalty:D</code>
946	<code>\__kernel_primitive:NN \localinterlinepenalty</code>	<code>\luatex_localinterlinepenalty:D</code>
947	<code>\__kernel_primitive:NN \localleftbox</code>	<code>\luatex_localleftbox:D</code>
948	<code>\__kernel_primitive:NN \localrightbox</code>	<code>\luatex_localrightbox:D</code>
949	<code>\__kernel_primitive:NN \mathdir</code>	<code>\luatex_mathdir:D</code>
950	<code>\__kernel_primitive:NN \pagedir</code>	<code>\luatex_pagedir:D</code>
951	<code>\__kernel_primitive:NN \pardir</code>	<code>\luatex_pardir:D</code>
952	<code>\__kernel_primitive:NN \rightghost</code>	<code>\luatex_rightghost:D</code>
953	<code>\__kernel_primitive:NN \textdir</code>	<code>\luatex_textdir:D</code>

Primitives from pdfTeX that LuaTeX renames.

954	<code>\__kernel_primitive:NN \adjustspacing</code>	<code>\pdfTeX_adjustspacing:D</code>
955	<code>\__kernel_primitive:NN \copyfont</code>	<code>\pdfTeX_copyfont:D</code>
956	<code>\__kernel_primitive:NN \draftmode</code>	<code>\pdfTeX_draftmode:D</code>
957	<code>\__kernel_primitive:NN \expandglyphsinfont</code>	<code>\pdfTeX_fontexpand:D</code>
958	<code>\__kernel_primitive:NN \ifabsdim</code>	<code>\pdfTeX_ifabsdim:D</code>
959	<code>\__kernel_primitive:NN \ifabsnum</code>	<code>\pdfTeX_ifabsnum:D</code>
960	<code>\__kernel_primitive:NN \ignoreligaturesinfont</code>	<code>\pdfTeX_ignoreligaturesinfont:D</code>
961	<code>\__kernel_primitive:NN \insertht</code>	<code>\pdfTeX_insertht:D</code>
962	<code>\__kernel_primitive:NN \lastsavedboxresourceindex</code>	<code>\pdfTeX_pdflastxform:D</code>
963	<code>\__kernel_primitive:NN \lastsavedimageresourceindex</code>	<code>\pdfTeX_pdflastximage:D</code>
964	<code>\__kernel_primitive:NN \lastsavedimageresourcepages</code>	<code>\pdfTeX_pdflastximagepages:D</code>
965	<code>\__kernel_primitive:NN \lastxpos</code>	<code>\pdfTeX_lastxpos:D</code>
966	<code>\__kernel_primitive:NN \lastypos</code>	<code>\pdfTeX_lastypos:D</code>
967	<code>\__kernel_primitive:NN \normaldeviate</code>	<code>\pdfTeX_normaldeviate:D</code>

968	<code>\__kernel_primitive:NN</code>	<code>\outputmode</code>	<code>\pdftex_pdfoutput:D</code>
969	<code>\__kernel_primitive:NN</code>	<code>\pageheight</code>	<code>\pdftex_pageheight:D</code>
970	<code>\__kernel_primitive:NN</code>	<code>\pagewidth</code>	<code>\pdftex_pagewidth:D</code>
971	<code>\__kernel_primitive:NN</code>	<code>\protrudechars</code>	<code>\pdftex_protrudechars:D</code>
972	<code>\__kernel_primitive:NN</code>	<code>\pxdimen</code>	<code>\pdftex_pxdimen:D</code>
973	<code>\__kernel_primitive:NN</code>	<code>\randomseed</code>	<code>\pdftex_randomseed:D</code>
974	<code>\__kernel_primitive:NN</code>	<code>\useboxresource</code>	<code>\pdftex_pdfrefxform:D</code>
975	<code>\__kernel_primitive:NN</code>	<code>\useimageresource</code>	<code>\pdftex_pdfrefximage:D</code>
976	<code>\__kernel_primitive:NN</code>	<code>\savepos</code>	<code>\pdftex_savepos:D</code>
977	<code>\__kernel_primitive:NN</code>	<code>\saveboxresource</code>	<code>\pdftex_pdfxform:D</code>
978	<code>\__kernel_primitive:NN</code>	<code>\saveimageresource</code>	<code>\pdftex_pdfximage:D</code>
979	<code>\__kernel_primitive:NN</code>	<code>\setrandomseed</code>	<code>\pdftex_setrandomseed:D</code>
980	<code>\__kernel_primitive:NN</code>	<code>\tracingfonts</code>	<code>\pdftex_tracingfonts:D</code>
981	<code>\__kernel_primitive:NN</code>	<code>\uniformdeviate</code>	<code>\pdftex_uniformdeviate:D</code>

The set of Unicode math primitives were introduced by  $\text{XeTeX}$  and  $\text{LuaTeX}$  in a somewhat complex fashion: a few first as  $\text{\XeTeX}\dots$  which were then renamed with  $\text{LuaTeX}$  having a lot more. These names now all start  $\text{\U}\dots$  and mainly  $\text{\Umath}\dots$ . To keep things somewhat clear we therefore prefix all of these as  $\text{\utex}\dots$  (introduced by a Unicode  $\text{TeX}$  engine) and drop  $\text{\U(math)}$  from the names. Where there is a related  $\text{TeX90}$  primitive or where it really seems required we keep the  $\text{math}$  part of the name.

982	<code>\__kernel_primitive:NN</code>	<code>\Uchar</code>	<code>\utex_char:D</code>
983	<code>\__kernel_primitive:NN</code>	<code>\Ucharcat</code>	<code>\utex_charcat:D</code>
984	<code>\__kernel_primitive:NN</code>	<code>\Udelcode</code>	<code>\utex_delcode:D</code>
985	<code>\__kernel_primitive:NN</code>	<code>\Udelcodenum</code>	<code>\utex_delcodenum:D</code>
986	<code>\__kernel_primitive:NN</code>	<code>\Udelimiter</code>	<code>\utex_delimiter:D</code>
987	<code>\__kernel_primitive:NN</code>	<code>\Udelimiterover</code>	<code>\utex_delimiterover:D</code>
988	<code>\__kernel_primitive:NN</code>	<code>\Udelimiterunder</code>	<code>\utex_delimiterunder:D</code>
989	<code>\__kernel_primitive:NN</code>	<code>\Uhextensible</code>	<code>\utex_hextensible:D</code>
990	<code>\__kernel_primitive:NN</code>	<code>\Umathaccent</code>	<code>\utex_mathaccent:D</code>
991	<code>\__kernel_primitive:NN</code>	<code>\Umathaxis</code>	<code>\utex_mathaxis:D</code>
992	<code>\__kernel_primitive:NN</code>	<code>\Umathbinbinspacing</code>	<code>\utex_binbinspacing:D</code>
993	<code>\__kernel_primitive:NN</code>	<code>\Umathbinclosespacing</code>	<code>\utex_binclosespacing:D</code>
994	<code>\__kernel_primitive:NN</code>	<code>\Umathbininnerspacing</code>	<code>\utex_bininnerspacing:D</code>
995	<code>\__kernel_primitive:NN</code>	<code>\Umathbinopenspacing</code>	<code>\utex_binopenspacing:D</code>
996	<code>\__kernel_primitive:NN</code>	<code>\Umathbinopspacing</code>	<code>\utex_binopspacing:D</code>
997	<code>\__kernel_primitive:NN</code>	<code>\Umathbinordspacing</code>	<code>\utex_binordspacing:D</code>
998	<code>\__kernel_primitive:NN</code>	<code>\Umathbinpunctspacing</code>	<code>\utex_binpunctspacing:D</code>
999	<code>\__kernel_primitive:NN</code>	<code>\Umathbinrelspacing</code>	<code>\utex_binrelspacing:D</code>
1000	<code>\__kernel_primitive:NN</code>	<code>\Umathchar</code>	<code>\utex_mathchar:D</code>
1001	<code>\__kernel_primitive:NN</code>	<code>\Umathcharclass</code>	<code>\utex_mathcharclass:D</code>
1002	<code>\__kernel_primitive:NN</code>	<code>\Umathchardef</code>	<code>\utex_mathchardef:D</code>
1003	<code>\__kernel_primitive:NN</code>	<code>\Umathcharfam</code>	<code>\utex_mathcharfam:D</code>
1004	<code>\__kernel_primitive:NN</code>	<code>\Umathcharnum</code>	<code>\utex_mathcharnum:D</code>
1005	<code>\__kernel_primitive:NN</code>	<code>\Umathcharnumdef</code>	<code>\utex_mathcharnumdef:D</code>
1006	<code>\__kernel_primitive:NN</code>	<code>\Umathcharslot</code>	<code>\utex_mathcharslot:D</code>
1007	<code>\__kernel_primitive:NN</code>	<code>\Umathclosebinspacing</code>	<code>\utex_closebinspacing:D</code>
1008	<code>\__kernel_primitive:NN</code>	<code>\Umathcloseclosespacing</code>	<code>\utex_closeclosespacing:D</code>
1009	<code>\__kernel_primitive:NN</code>	<code>\Umathcloseinnerspacing</code>	<code>\utex_closeinnerspacing:D</code>
1010	<code>\__kernel_primitive:NN</code>	<code>\Umathcloseopenspacing</code>	<code>\utex_closeopenspacing:D</code>
1011	<code>\__kernel_primitive:NN</code>	<code>\Umathcloseopspacing</code>	<code>\utex_closeopspacing:D</code>
1012	<code>\__kernel_primitive:NN</code>	<code>\Umathcloseordspacing</code>	<code>\utex_closeordspacing:D</code>
1013	<code>\__kernel_primitive:NN</code>	<code>\Umathclosepunctspacing</code>	<code>\utex_closepunctspacing:D</code>
1014	<code>\__kernel_primitive:NN</code>	<code>\Umathcloserelspacing</code>	<code>\utex_closerelspacing:D</code>

1015	\_kernel\_primitive:NN	\Umathcode	\utex\_mathcode:D
1016	\_kernel\_primitive:NN	\Umathcodenum	\utex\_mathcodenum:D
1017	\_kernel\_primitive:NN	\Umathconnectoroverlapmin	\utex\_connectoroverlapmin:D
1018	\_kernel\_primitive:NN	\Umathfractiondelsize	\utex\_fractiondelsize:D
1019	\_kernel\_primitive:NN	\Umathfractiondenomdown	\utex\_fractiondenomdown:D
1020	\_kernel\_primitive:NN	\Umathfractiondenomvgap	\utex\_fractiondenomvgap:D
1021	\_kernel\_primitive:NN	\Umathfractionnumup	\utex\_fractionnumup:D
1022	\_kernel\_primitive:NN	\Umathfractionnumvgap	\utex\_fractionnumvgap:D
1023	\_kernel\_primitive:NN	\Umathfractionrule	\utex\_fractionrule:D
1024	\_kernel\_primitive:NN	\Umathinnerbinspacing	\utex\_innerbinspacing:D
1025	\_kernel\_primitive:NN	\Umathinnerclosespacing	\utex\_innerclosespacing:D
1026	\_kernel\_primitive:NN	\Umathinnerinnerspacing	\utex\_innerinnerspacing:D
1027	\_kernel\_primitive:NN	\Umathinneropenspacing	\utex\_inneropenspacing:D
1028	\_kernel\_primitive:NN	\Umathinneropspacing	\utex\_inneropspacing:D
1029	\_kernel\_primitive:NN	\Umathinnerordspacing	\utex\_innerordspacing:D
1030	\_kernel\_primitive:NN	\Umathinnerpunctspacing	\utex\_innerpunctspacing:D
1031	\_kernel\_primitive:NN	\Umathinnerrelspacing	\utex\_innerrelspacing:D
1032	\_kernel\_primitive:NN	\Umathlimitabovebgap	\utex\_limitabovebgap:D
1033	\_kernel\_primitive:NN	\Umathlimitabovekern	\utex\_limitabovekern:D
1034	\_kernel\_primitive:NN	\Umathlimitabovevgap	\utex\_limitabovevgap:D
1035	\_kernel\_primitive:NN	\Umathlimitbelowbgap	\utex\_limitbelowbgap:D
1036	\_kernel\_primitive:NN	\Umathlimitbelowkern	\utex\_limitbelowkern:D
1037	\_kernel\_primitive:NN	\Umathlimitbelowvgap	\utex\_limitbelowvgap:D
1038	\_kernel\_primitive:NN	\Umathnolimitsubfactor	\utex\_nolimitsubfactor:D
1039	\_kernel\_primitive:NN	\Umathnolimitsupfactor	\utex\_nolimitsupfactor:D
1040	\_kernel\_primitive:NN	\Umathopbinspacing	\utex\_opbinspacing:D
1041	\_kernel\_primitive:NN	\Umathopclosespacing	\utex\_opclosespacing:D
1042	\_kernel\_primitive:NN	\Umathopenbinspacing	\utex\_openbinspacing:D
1043	\_kernel\_primitive:NN	\Umathopenclosespacing	\utex\_openclosespacing:D
1044	\_kernel\_primitive:NN	\Umathopeninnerspacing	\utex\_openinnerspacing:D
1045	\_kernel\_primitive:NN	\Umathopenopenspacing	\utex\_openopenspacing:D
1046	\_kernel\_primitive:NN	\Umathopenopspacing	\utex\_openopspacing:D
1047	\_kernel\_primitive:NN	\Umathopenordspacing	\utex\_openordspacing:D
1048	\_kernel\_primitive:NN	\Umathopenpunctspacing	\utex\_openpunctspacing:D
1049	\_kernel\_primitive:NN	\Umathopenrelspacing	\utex\_openrelspacing:D
1050	\_kernel\_primitive:NN	\Umathoperatorsize	\utex\_operatorsize:D
1051	\_kernel\_primitive:NN	\Umathopinnerspacing	\utex\_opinnerspacing:D
1052	\_kernel\_primitive:NN	\Umathopopenspacing	\utex\_opopenspacing:D
1053	\_kernel\_primitive:NN	\Umathopopspacing	\utex\_opopspacing:D
1054	\_kernel\_primitive:NN	\Umathopordspacing	\utex\_opordspacing:D
1055	\_kernel\_primitive:NN	\Umathoppunctspacing	\utex\_oppunctspacing:D
1056	\_kernel\_primitive:NN	\Umathoprelspacing	\utex\_oprelspacing:D
1057	\_kernel\_primitive:NN	\Umathordbinspacing	\utex\_ordbinspacing:D
1058	\_kernel\_primitive:NN	\Umathordclosespacing	\utex\_ordclosespacing:D
1059	\_kernel\_primitive:NN	\Umathordinnerspacing	\utex\_ordinnerspacing:D
1060	\_kernel\_primitive:NN	\Umathordopenspacing	\utex\_ordopenspacing:D
1061	\_kernel\_primitive:NN	\Umathordopspacing	\utex\_ordopspacing:D
1062	\_kernel\_primitive:NN	\Umathordordspacing	\utex\_ordordspacing:D
1063	\_kernel\_primitive:NN	\Umathordpunctspacing	\utex\_ordpunctspacing:D
1064	\_kernel\_primitive:NN	\Umathordrelspacing	\utex\_ordrelspacing:D
1065	\_kernel\_primitive:NN	\Umathoverbarkern	\utex\_overbarkern:D
1066	\_kernel\_primitive:NN	\Umathoverbarrule	\utex\_overbarrule:D
1067	\_kernel\_primitive:NN	\Umathoverbarvgap	\utex\_overbarvgap:D
1068	\_kernel\_primitive:NN	\Umathoverdelimiterbgap	\utex\_overdelimiterbgap:D

1069	\_kernel\_primitive:NN	\Umathoverdelimitervgap	\utex\_overdelimitervgap:D
1070	\_kernel\_primitive:NN	\Umathpunctbinspacing	\utex\_punctbinspacing:D
1071	\_kernel\_primitive:NN	\Umathpunctclosespacing	\utex\_punctclosespacing:D
1072	\_kernel\_primitive:NN	\Umathpunctinnerspacing	\utex\_punctinnerspacing:D
1073	\_kernel\_primitive:NN	\Umathpunctopenspacing	\utex\_punctopenspacing:D
1074	\_kernel\_primitive:NN	\Umathpuncttopspacing	\utex\_puncttopspacing:D
1075	\_kernel\_primitive:NN	\Umathpunctordspacing	\utex\_punctordspacing:D
1076	\_kernel\_primitive:NN	\Umathpunctpunctspacing	\utex\_punctpunctspacing:D
1077	\_kernel\_primitive:NN	\Umathpunctrelspacing	\utex\_punctrelspacing:D
1078	\_kernel\_primitive:NN	\Umathquad	\utex\_quad:D
1079	\_kernel\_primitive:NN	\Umathradicaldegreeafter	\utex\_radicaldegreeafter:D
1080	\_kernel\_primitive:NN	\Umathradicaldegreebefore	\utex\_radicaldegreebefore:D
1081	\_kernel\_primitive:NN	\Umathradicaldegreeraise	\utex\_radicaldegreeraise:D
1082	\_kernel\_primitive:NN	\Umathradicalkern	\utex\_radicalkern:D
1083	\_kernel\_primitive:NN	\Umathradicalrule	\utex\_radicalrule:D
1084	\_kernel\_primitive:NN	\Umathradicalvgap	\utex\_radicalvgap:D
1085	\_kernel\_primitive:NN	\Umathrelbinspacing	\utex\_relbinspacing:D
1086	\_kernel\_primitive:NN	\Umathrelclosespacing	\utex\_relclosespacing:D
1087	\_kernel\_primitive:NN	\Umathrelinnerspacing	\utex\_relinnerspacing:D
1088	\_kernel\_primitive:NN	\Umathrelopenspacing	\utex\_relopenspacing:D
1089	\_kernel\_primitive:NN	\Umathreltopspacing	\utex\_reltopspacing:D
1090	\_kernel\_primitive:NN	\Umathrelordspacing	\utex\_relordspacing:D
1091	\_kernel\_primitive:NN	\Umathrelpunctspacing	\utex\_relpunctspacing:D
1092	\_kernel\_primitive:NN	\Umathrelrelspacing	\utex\_relrelspacing:D
1093	\_kernel\_primitive:NN	\Umathskewedfractionhgap	\utex\_skewedfractionhgap:D
1094	\_kernel\_primitive:NN	\Umathskewedfractionvgap	\utex\_skewedfractionvgap:D
1095	\_kernel\_primitive:NN	\Umathspaceafterscript	\utex\_spaceafterscript:D
1096	\_kernel\_primitive:NN	\Umathstackdenomdown	\utex\_stackdenomdown:D
1097	\_kernel\_primitive:NN	\Umathstacknumup	\utex\_stacknumup:D
1098	\_kernel\_primitive:NN	\Umathstackvgap	\utex\_stackvgap:D
1099	\_kernel\_primitive:NN	\Umathsubshiftdown	\utex\_subshiftdown:D
1100	\_kernel\_primitive:NN	\Umathsubshiftdrop	\utex\_subshiftdrop:D
1101	\_kernel\_primitive:NN	\Umathsubsupshiftdown	\utex\_subsupshiftdown:D
1102	\_kernel\_primitive:NN	\Umathsubsupvgap	\utex\_subsupvgap:D
1103	\_kernel\_primitive:NN	\Umathsubtopmax	\utex\_subtopmax:D
1104	\_kernel\_primitive:NN	\Umathsupbottommin	\utex\_supbottommin:D
1105	\_kernel\_primitive:NN	\Umathsupshiftdrop	\utex\_supshiftdrop:D
1106	\_kernel\_primitive:NN	\Umathsupshiftup	\utex\_supshiftup:D
1107	\_kernel\_primitive:NN	\Umathsupsubbottommax	\utex\_supsubbottommax:D
1108	\_kernel\_primitive:NN	\Umathunderbarkern	\utex\_underbarkern:D
1109	\_kernel\_primitive:NN	\Umathunderbarrule	\utex\_underbarrule:D
1110	\_kernel\_primitive:NN	\Umathunderbarvgap	\utex\_underbarvgap:D
1111	\_kernel\_primitive:NN	\Umathunderdelimiterbgap	\utex\_underdelimiterbgap:D
1112	\_kernel\_primitive:NN	\Umathunderdelimitervgap	\utex\_underdelimitervgap:D
1113	\_kernel\_primitive:NN	\Uoverdelimiter	\utex\_overdelimiter:D
1114	\_kernel\_primitive:NN	\Uradical	\utex\_radical:D
1115	\_kernel\_primitive:NN	\Uroot	\utex\_root:D
1116	\_kernel\_primitive:NN	\Uskewed	\utex\_skewed:D
1117	\_kernel\_primitive:NN	\Uskewedwithdelims	\utex\_skewedwithdelims:D
1118	\_kernel\_primitive:NN	\Ustack	\utex\_stack:D
1119	\_kernel\_primitive:NN	\Ustartdisplaymath	\utex\_startdisplaymath:D
1120	\_kernel\_primitive:NN	\Ustartmath	\utex\_startmath:D
1121	\_kernel\_primitive:NN	\Ustopdisplaymath	\utex\_stopdisplaymath:D
1122	\_kernel\_primitive:NN	\Ustopmath	\utex\_stopmath:D



1123	<code>\__kernel_primitive:NN \Usubscript</code>	<code>\utex_subscript:D</code>
1124	<code>\__kernel_primitive:NN \Usuperscript</code>	<code>\utex_superscript:D</code>
1125	<code>\__kernel_primitive:NN \Uunderdelimit</code>	<code>\utex_underdelimit:D</code>
1126	<code>\__kernel_primitive:NN \Uvextensible</code>	<code>\utex_vextensible:D</code>

Primitives from pT<sub>E</sub>X.

1127	<code>\__kernel_primitive:NN \autospace</code>	<code>\ptex_autospace:D</code>
1128	<code>\__kernel_primitive:NN \autoxspace</code>	<code>\ptex_autoxspace:D</code>
1129	<code>\__kernel_primitive:NN \dtou</code>	<code>\ptex_dtou:D</code>
1130	<code>\__kernel_primitive:NN \euc</code>	<code>\ptex_euc:D</code>
1131	<code>\__kernel_primitive:NN \ifdbx</code>	<code>\ptex_ifdbx:D</code>
1132	<code>\__kernel_primitive:NN \ifddir</code>	<code>\ptex_ifddir:D</code>
1133	<code>\__kernel_primitive:NN \ifmdir</code>	<code>\ptex_ifmdir:D</code>
1134	<code>\__kernel_primitive:NN \iftbx</code>	<code>\ptex_iftbx:D</code>
1135	<code>\__kernel_primitive:NN \iftdir</code>	<code>\ptex_iftdir:D</code>
1136	<code>\__kernel_primitive:NN \ifybx</code>	<code>\ptex_ifybx:D</code>
1137	<code>\__kernel_primitive:NN \ifydir</code>	<code>\ptex_ifydir:D</code>
1138	<code>\__kernel_primitive:NN \inhibitglue</code>	<code>\ptex_inhibitglue:D</code>
1139	<code>\__kernel_primitive:NN \inhibitxspcode</code>	<code>\ptex_inhibitxspcode:D</code>
1140	<code>\__kernel_primitive:NN \jcharwidowpenalty</code>	<code>\ptex_jcharwidowpenalty:D</code>
1141	<code>\__kernel_primitive:NN \jfam</code>	<code>\ptex_jfam:D</code>
1142	<code>\__kernel_primitive:NN \jfont</code>	<code>\ptex_jfont:D</code>
1143	<code>\__kernel_primitive:NN \jis</code>	<code>\ptex_jis:D</code>
1144	<code>\__kernel_primitive:NN \kanjiskip</code>	<code>\ptex_kanjiskip:D</code>
1145	<code>\__kernel_primitive:NN \kansuji</code>	<code>\ptex_kansuji:D</code>
1146	<code>\__kernel_primitive:NN \kansujichar</code>	<code>\ptex_kansujichar:D</code>
1147	<code>\__kernel_primitive:NN \kcatcode</code>	<code>\ptex_kcatcode:D</code>
1148	<code>\__kernel_primitive:NN \kuten</code>	<code>\ptex_kuten:D</code>
1149	<code>\__kernel_primitive:NN \noautospace</code>	<code>\ptex_noautospace:D</code>
1150	<code>\__kernel_primitive:NN \noautoxspace</code>	<code>\ptex_noautoxspace:D</code>
1151	<code>\__kernel_primitive:NN \postbreakpenalty</code>	<code>\ptex_postbreakpenalty:D</code>
1152	<code>\__kernel_primitive:NN \prebreakpenalty</code>	<code>\ptex_prebreakpenalty:D</code>
1153	<code>\__kernel_primitive:NN \showmode</code>	<code>\ptex_showmode:D</code>
1154	<code>\__kernel_primitive:NN \sjis</code>	<code>\ptex_sjis:D</code>
1155	<code>\__kernel_primitive:NN \tate</code>	<code>\ptex_tate:D</code>
1156	<code>\__kernel_primitive:NN \tbaselineshift</code>	<code>\ptex_tbaselineshift:D</code>
1157	<code>\__kernel_primitive:NN \tfont</code>	<code>\ptex_tfont:D</code>
1158	<code>\__kernel_primitive:NN \xkanjiskip</code>	<code>\ptex_xkanjiskip:D</code>
1159	<code>\__kernel_primitive:NN \xspcode</code>	<code>\ptex_xspcode:D</code>
1160	<code>\__kernel_primitive:NN \ybaselineshift</code>	<code>\ptex_ybaselineshift:D</code>
1161	<code>\__kernel_primitive:NN \yoko</code>	<code>\ptex_yoko:D</code>

Primitives from upT<sub>E</sub>X.

1162	<code>\__kernel_primitive:NN \disablecjktoken</code>	<code>\uptex_disablecjktoken:D</code>
1163	<code>\__kernel_primitive:NN \enablecjktoken</code>	<code>\uptex_enablecjktoken:D</code>
1164	<code>\__kernel_primitive:NN \forcecjktoken</code>	<code>\uptex_forcecjktoken:D</code>
1165	<code>\__kernel_primitive:NN \kchar</code>	<code>\uptex_kchar:D</code>
1166	<code>\__kernel_primitive:NN \kchardef</code>	<code>\uptex_kchardef:D</code>
1167	<code>\__kernel_primitive:NN \kuten</code>	<code>\uptex_kuten:D</code>
1168	<code>\__kernel_primitive:NN \ucs</code>	<code>\uptex_ucs:D</code>

End of the “just the names” part of the source.

1169	<code>&lt;/initex   names   package&gt;</code>
1170	<code>&lt;*initex   package&gt;</code>

The job is done: close the group (using the primitive renamed!).

```
1171 \tex_endgroup:D
```

L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> moves a few primitives, so these are sorted out. A convenient test for L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> is the \@@end saved primitive.

```
1172 <*package>
1173 \etex_ifdefined:D \@@end
1174 \tex_let:D \tex_end:D \@@end
1175 \tex_let:D \tex_everydisplay:D \frozen@everydisplay
1176 \tex_let:D \tex_everymath:D \frozen@everymath
1177 \tex_let:D \tex_hyphen:D \@@hyph
1178 \tex_let:D \tex_input:D \@@input
1179 \tex_let:D \tex_italiccorrection:D \@@italiccorr
1180 \tex_let:D \tex_underline:D \@@underline
```

Some tidying up is needed for \(\pdf)tracingfonts. Newer LuaT<sub>E</sub>X has this simply as \tracingfonts, but that is overwritten by the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> kernel. So any spurious definition has to be removed, then the real version saved either from the pdfT<sub>E</sub>X name or from LuaT<sub>E</sub>X. In the latter case, we leave \@@tracingfonts available; this might be useful and almost all L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> users will have expl3 loaded by fontspec. (We follow the usual kernel convention that @@ is used for saved primitives.)

```
1181 \tex_let:D \pdfTeX_tracingfonts:D \tex_undefined:D
1182 \etex_ifdefined:D \pdftracingfonts
1183 \tex_let:D \pdfTeX_tracingfonts:D \pdftracingfonts
1184 \tex_else:D
1185 \etex_ifdefined:D \luatex_directlua:D
1186 \luatex_directlua:D { tex.enableprimitives("@@", {"tracingfonts"}) }
1187 \tex_let:D \pdfTeX_tracingfonts:D \luatextracingfonts
1188 \tex_fi:D
1189 \tex_fi:D
1190 \tex_fi:D
```

That is also true for the LuaT<sub>E</sub>X primitives under L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> (depending on the format-building date). There are a few primitives that get the right names anyway so are missing here!

```
1191 \etex_ifdefined:D \luatexsuppressfontnotfounderror
1192 \tex_let:D \luatex_alignmark:D \luatexalignmark
1193 \tex_let:D \luatex_aligntab:D \luatexaligntab
1194 \tex_let:D \luatex_attribute:D \luatexattribute
1195 \tex_let:D \luatex_attributedef:D \luatexattributedef
1196 \tex_let:D \luatex_catcodetable:D \luatexcatcodetable
1197 \tex_let:D \luatex_clearmarks:D \luatexclearmarks
1198 \tex_let:D \luatex_crampeddisplaystyle:D \luatexcrampeddisplaystyle
1199 \tex_let:D \luatex_crampedscriptscriptstyle:D \luatexcrampedscriptscriptstyle
1200 \tex_let:D \luatex_crampedscriptstyle:D \luatexcrampedscriptstyle
1201 \tex_let:D \luatex_crampedtextstyle:D \luatexcrampedtextstyle
1202 \tex_let:D \luatex_fontid:D \luatexfontid
1203 \tex_let:D \luatex_formatname:D \luatexformatname
1204 \tex_let:D \luatex_gleaders:D \luatexgleaders
1205 \tex_let:D \luatex_initcatcodetable:D \luatexinitcatcodetable
1206 \tex_let:D \luatex_latelua:D \luatexlatelua
1207 \tex_let:D \luatex_luaescapestring:D \luatexluaescapestring
1208 \tex_let:D \luatex_luafunction:D \luatexluafunction
1209 \tex_let:D \luatex_mathstyle:D \luatexmathstyle
```

```

1210 \tex_let:D \luatex_nokerns:D \luatexnokerns
1211 \tex_let:D \luatex_noligs:D \luatexnoligs
1212 \tex_let:D \luatex_outputbox:D \luatexoutputbox
1213 \tex_let:D \luatex_pageleftoffset:D \luatexpageleftoffset
1214 \tex_let:D \luatex_pagetopoffset:D \luatexpagetopoffset
1215 \tex_let:D \luatex_postexhyphenchar:D \luatexpostexhyphenchar
1216 \tex_let:D \luatex_posthyphenchar:D \luatexposthyphenchar
1217 \tex_let:D \luatex_preexhyphenchar:D \luatexpreexhyphenchar
1218 \tex_let:D \luatex_prehyphenchar:D \luatexprehyphenchar
1219 \tex_let:D \luatex_savecatcodetable:D \luatexsavecatcodetable
1220 \tex_let:D \luatex_scantextokens:D \luatexscantextokens
1221 \tex_let:D \luatex_suppressifcsnameerror:D \luatexsuppressifcsnameerror
1222 \tex_let:D \luatex_suppresslongerror:D \luatexsuppresslongerror
1223 \tex_let:D \luatex_suppressmathparerror:D \luatexsuppressmathparerror
1224 \tex_let:D \luatex_suppressoutererror:D \luatexsuppressoutererror
1225 \tex_let:D \utex_char:D \luatexUchar
1226 \tex_let:D \xetex_suppressfontnotfounderror:D \luatexsuppressfontnotfounderror

```

Which also covers those slightly odd ones.

```

1227 \tex_let:D \luatex_bodydir:D \luatexbodydir
1228 \tex_let:D \luatex_boxdir:D \luatexboxdir
1229 \tex_let:D \luatex_leftghost:D \luatexleftghost
1230 \tex_let:D \luatex_localbrokenpenalty:D \luatexlocalbrokenpenalty
1231 \tex_let:D \luatex_localinterlinepenalty:D \luatexlocalinterlinepenalty
1232 \tex_let:D \luatex_localleftbox:D \luatexlocalleftbox
1233 \tex_let:D \luatex_localrightbox:D \luatexlocalrightbox
1234 \tex_let:D \luatex_mathdir:D \luatexmathdir
1235 \tex_let:D \luatex_pagebottomoffset:D \luatexpagebottomoffset
1236 \tex_let:D \luatex_pagedir:D \luatexpagedir
1237 \tex_let:D \pdfTeX_pageheight:D \luatexpageheight
1238 \tex_let:D \luatex_pagerightoffset:D \luatexpagerightoffset
1239 \tex_let:D \pdfTeX_pagewidth:D \luatexpagewidth
1240 \tex_let:D \luatex_pardir:D \luatexpardir
1241 \tex_let:D \luatex_rightghost:D \luatexrightghost
1242 \tex_let:D \luatex_textdir:D \luatextextdir
1243 \tex_fi:D

```

Only pdfTeX and LuaTeX define \pdfmapfile and \pdfmapline: Tidy up the fact that some format-building processes leave a couple of questionable decisions about that!

```

1244 \tex_ifnum:D 0
1245 \etex_ifdefined:D \pdfTeX_pdftexversion:D 1 \tex_fi:D
1246 \etex_ifdefined:D \luatex luatexversion:D 1 \tex_fi:D
1247 = 0 %
1248 \tex_let:D \pdfTeX_mapfile:D \tex_undefined:D
1249 \tex_let:D \pdfTeX_mapline:D \tex_undefined:D
1250 \tex_fi:D
1251 </package>

```

Older XeTeX versions use \XeTeX as the prefix for the Unicode math primitives it knows. That is tidied up here (we support XeTeX versions from 0.9994 but this change was in 0.9999).

```

1252 (*initex | package)
1253 \etex_ifdefined:D \XeTeXdelcode
1254 \tex_let:D \utex_delcode:D \XeTeXdelcode
1255 \tex_let:D \utex_delcodenum:D \XeTeXdelcodenum

```

```

1256 \tex_let:D \utex_delimiter:D \XeTeXdelimiter
1257 \tex_let:D \utex_mathaccent:D \XeTeXmathaccent
1258 \tex_let:D \utex_mathchar:D \XeTeXmathchar
1259 \tex_let:D \utex_mathchardef:D \XeTeXmathchardef
1260 \tex_let:D \utex_mathcharnum:D \XeTeXmathcharnum
1261 \tex_let:D \utex_mathcharnumdef:D \XeTeXmathcharnumdef
1262 \tex_let:D \utex_mathcode:D \XeTeXmathcode
1263 \tex_let:D \utex_mathcodenum:D \XeTeXmathcodenum
1264 \tex_fi:D

```

Up to v0.80, LuaTeX defines the pdfTeX version data: rather confusing. Removing them means that `\pdfTeX_pdfTeXversion:D` is a marker for pdfTeX alone: useful in engine-dependent code later.

```

1265 \etex_ifdefined:D \luatex luatexversion:D
1266 \tex_let:D \pdfTeX_pdfTeXbanner:D \tex_undefined:D
1267 \tex_let:D \pdfTeX_pdfTeXrevision:D \tex_undefined:D
1268 \tex_let:D \pdfTeX_pdfTeXversion:D \tex_undefined:D
1269 \tex_fi:D
1270 </initex | package>

```

For ConTeXt, two tests are needed. Both Mark II and Mark IV move several primitives: these are all covered by the first test, again using `\end` as a marker. For Mark IV, a few more primitives are moved: they are implemented using some Lua code in the current ConTeXt.

```

1271 <(*package>
1272 \etex_ifdefined:D \normalend
1273 \tex_let:D \tex_end:D \normalend
1274 \tex_let:D \tex_everyjob:D \normaleveryjob
1275 \tex_let:D \tex_input:D \normalinput
1276 \tex_let:D \tex_language:D \normallanguage
1277 \tex_let:D \tex_mathop:D \normalmathop
1278 \tex_let:D \tex_month:D \normalmonth
1279 \tex_let:D \tex_outer:D \normalouter
1280 \tex_let:D \tex_over:D \normalover
1281 \tex_let:D \tex_vcenter:D \normalvcenter
1282 \tex_let:D \etex_unexpanded:D \normalunexpanded
1283 \tex_let:D \luatex_expanded:D \normalexpanded
1284 \tex_fi:D
1285 \etex_ifdefined:D \normalitaliccorrection
1286 \tex_let:D \tex_hoffset:D \normalhoffset
1287 \tex_let:D \tex_italiccorrection:D \normalitaliccorrection
1288 \tex_let:D \tex_voffset:D \normalvoffset
1289 \tex_let:D \etex_showtokens:D \normalshowtokens
1290 \tex_let:D \luatex_bodydir:D \spac_directions_normal_body_dir
1291 \tex_let:D \luatex_pagedir:D \spac_directions_normal_page_dir
1292 \tex_fi:D
1293 \etex_ifdefined:D \normalleft
1294 \tex_let:D \tex_left:D \normalleft
1295 \tex_let:D \tex_middle:D \normalmiddle
1296 \tex_let:D \tex_right:D \normalright
1297 \tex_fi:D
1298 </package>
1299 </initex | package>

```

### 3 l3basics implementation

1300 (\*initex | package)

#### 3.1 Renaming some T<sub>E</sub>X primitives (again)

Having given all the T<sub>E</sub>X primitives a consistent name, we need to give sensible names to the ones we actually want to use. These will be defined as needed in the appropriate modules, but we do a few now, just to get started.<sup>6</sup>

```

\if_true: Then some conditionals.
\if_false: 1301 \tex_let:D \if_true:      \tex_iftrue:D
\or:       1302 \tex_let:D \if_false:    \tex_iffalse:D
\else:     1303 \tex_let:D \or:         \tex_or:D
\fi:       1304 \tex_let:D \else:       \tex_else:D
\reverse_if:N 1305 \tex_let:D \fi:       \tex_fi:D
\if:w      1306 \tex_let:D \reverse_if:N \etex_unless:D
\if_charcode:w 1307 \tex_let:D \if:w      \tex_if:D
\if_catcode:w 1308 \tex_let:D \if_charcode:w \tex_if:D
\if_meaning:w 1309 \tex_let:D \if_catcode:w \tex_ifcat:D
            1310 \tex_let:D \if_meaning:w \tex_ifx:D

```

(End definition for \if\_true: and others. These functions are documented on page 21.)

```

\if_mode_math: TEX lets us detect some if its modes.
\if_mode_horizontal: 1311 \tex_let:D \if_mode_math:    \tex_ifmmode:D
\if_mode_vertical:   1312 \tex_let:D \if_mode_horizontal: \tex_ifhmode:D
\if_mode_inner:      1313 \tex_let:D \if_mode_vertical:    \tex_ifvmode:D
                    1314 \tex_let:D \if_mode_inner:      \tex_ifinner:D

```

(End definition for \if\_mode\_math: and others. These functions are documented on page 21.)

```

\if_cs_exist:N Building csnames and testing if control sequences exist.
\if_cs_exist:w 1315 \tex_let:D \if_cs_exist:N    \etex_ifdefined:D
\cs:w         1316 \tex_let:D \if_cs_exist:w    \etex_ifcsname:D
\cs_end:      1317 \tex_let:D \cs:w         \tex_csname:D
            1318 \tex_let:D \cs_end:      \tex_endcsname:D

```

(End definition for \if\_cs\_exist:N and others. These functions are documented on page 21.)

```

\exp_after:wN The five \exp_ functions are used in the l3expan module where they are described.
\exp_not:N    1319 \tex_let:D \exp_after:wN    \tex_expandafter:D
\exp_not:n    1320 \tex_let:D \exp_not:N      \tex_noexpand:D
              1321 \tex_let:D \exp_not:n      \etex_unexpanded:D
              1322 \tex_let:D \exp:w        \tex_romannumeral:D
              1323 \tex_chardef:D \exp_end: = 0 ~

```

(End definition for \exp\_after:wN, \exp\_not:N, and \exp\_not:n. These functions are documented on page 30.)

```

\token_to_meaning:N Examining a control sequence or token.
\cs_meaning:N       1324 \tex_let:D \token_to_meaning:N \tex_meaning:D
                    1325 \tex_let:D \cs_meaning:N    \tex_meaning:D

```

<sup>6</sup>This renaming gets expensive in terms of csname usage, an alternative scheme would be to just use the \tex\_...:D name in the cases where no good alternative exists.

(End definition for `\token_to_meaning:N` and `\cs_meaning:N`. These functions are documented on page 112.)

`\tl_to_str:n` Making strings.  
`\token_to_str:N`

```

1326 \tex_let:D \tl_to_str:n      \etex_detokenize:D
1327 \tex_let:D \token_to_str:N   \tex_string:D

```

(End definition for `\tl_to_str:n` and `\token_to_str:N`. These functions are documented on page 41.)

`\scan_stop:` The next three are basic functions for which there also exist versions that are safe inside alignments. These safe versions are defined in the `l3prg` module.

`\group_begin:`  
`\group_end:`

```

1328 \tex_let:D \scan_stop:      \tex_relax:D
1329 \tex_let:D \group_begin:    \tex_begingroup:D
1330 \tex_let:D \group_end:      \tex_endgroup:D

```

(End definition for `\scan_stop:`, `\group_begin:`, and `\group_end:`. These functions are documented on page 9.)

`\if_int_compare:w` For integers.

`\__int_to_roman:w`

```

1331 \tex_let:D \if_int_compare:w \tex_ifnum:D
1332 \tex_let:D \__int_to_roman:w \tex_romannumeral:D

```

(End definition for `\if_int_compare:w` and `\__int_to_roman:w`. These functions are documented on page 79.)

`\group_insert_after:N` Adding material after the end of a group.

```

1333 \tex_let:D \group_insert_after:N \tex_aftergroup:D

```

(End definition for `\group_insert_after:N`. This function is documented on page 9.)

`\exp_args:Nc` Discussed in `l3expan`, but needed much earlier.

`\exp_args:cc`

```

1334 \tex_long:D \tex_def:D \exp_args:Nc #1#2
1335   { \exp_after:wN #1 \cs:w #2 \cs_end: }
1336 \tex_long:D \tex_def:D \exp_args:cc #1#2
1337   { \cs:w #1 \exp_after:wN \cs_end: \cs:w #2 \cs_end: }

```

(End definition for `\exp_args:Nc` and `\exp_args:cc`. These functions are documented on page 27.)

`\token_to_meaning:c` A small number of variants defined by hand. Some of the necessary functions (`\use_i:nn`, `\use_ii:nn`, and `\exp_args:NNc`) are not defined at that point yet, but will be defined before those variants are used. The `\cs_meaning:c` command must check for an undefined control sequence to avoid defining it mistakenly.

```

1338 \tex_def:D \token_to_str:c { \exp_args:Nc \token_to_str:N }
1339 \tex_long:D \tex_def:D \cs_meaning:c #1
1340   {
1341     \if_cs_exist:w #1 \cs_end:
1342       \exp_after:wN \use_i:nn
1343     \else:
1344       \exp_after:wN \use_ii:nn
1345     \fi:
1346     { \exp_args:Nc \cs_meaning:N {#1} }
1347     { \tl_to_str:n {undefined} }
1348   }
1349 \tex_let:D \token_to_meaning:c = \cs_meaning:c

```

(End definition for `\token_to_meaning:c`, `\token_to_str:c`, and `\cs_meaning:c`. These functions are documented on page 112.)

## 3.2 Defining some constants

`\c_zero` We need the constant `\c_zero` which is used by some functions in the `l3alloc` module. The rest are defined in the `l3int` module – at least for the ones that can be defined with `\tex_chardef:D` or `\tex_mathchardef:D`. For other constants the `l3int` module is required but it can't be used until the allocation has been set up properly!

```
1350 \tex_chardef:D \c_zero      = 0 ~
```

(End definition for `\c_zero`. This variable is documented on page 78.)

`\c_max_register_int` This is here as this particular integer is needed both in package mode and to bootstrap `l3alloc`, and is documented in `l3int`.

```
1351 \etex_ifdefined:D \luatex luatexversion:D
1352 \tex_chardef:D \c_max_register_int = 65 535 ~
1353 \tex_else:D
1354 \tex_mathchardef:D \c_max_register_int = 32 767 ~
1355 \tex_fi:D
```

(End definition for `\c_max_register_int`. This variable is documented on page 78.)

## 3.3 Defining functions

We start by providing functions for the typical definition functions. First the local ones.

`\cs_set_nopar:Npn` All assignment functions in L<sup>A</sup>T<sub>E</sub>X3 should be naturally protected; after all, the T<sub>E</sub>X primitives for assignments are and it can be a cause of problems if others aren't.

```
\cs_set_nopar:Npx
\cs_set:Npn
\cs_set:Npx
\cs_set_protected_nopar:Npn
\cs_set_protected_nopar:Npx
\cs_set_protected:Npn
\cs_set_protected:Npx
1356 \tex_let:D \cs_set_nopar:Npn          \tex_def:D
1357 \tex_let:D \cs_set_nopar:Npx          \tex_edef:D
1358 \etex_protected:D \tex_long:D \tex_def:D \cs_set:Npn
1359 { \tex_long:D \tex_def:D }
1360 \etex_protected:D \tex_long:D \tex_def:D \cs_set:Npx
1361 { \tex_long:D \tex_edef:D }
1362 \etex_protected:D \tex_long:D \tex_def:D \cs_set_protected_nopar:Npn
1363 { \etex_protected:D \tex_def:D }
1364 \etex_protected:D \tex_long:D \tex_def:D \cs_set_protected_nopar:Npx
1365 { \etex_protected:D \tex_edef:D }
1366 \etex_protected:D \tex_long:D \tex_def:D \cs_set_protected:Npn
1367 { \etex_protected:D \tex_long:D \tex_def:D }
1368 \etex_protected:D \tex_long:D \tex_def:D \cs_set_protected:Npx
1369 { \etex_protected:D \tex_long:D \tex_edef:D }
```

(End definition for `\cs_set_nopar:Npn` and others. These functions are documented on page 11.)

`\cs_gset_nopar:Npn` Global versions of the above functions.

```
\cs_gset_nopar:Npx
\cs_gset:Npn
\cs_gset:Npx
\cs_gset_protected_nopar:Npn
\cs_gset_protected_nopar:Npx
\cs_gset_protected:Npn
\cs_gset_protected:Npx
1370 \tex_let:D \cs_gset_nopar:Npn          \tex_gdef:D
1371 \tex_let:D \cs_gset_nopar:Npx          \tex_xdef:D
1372 \cs_set_protected:Npn \cs_gset:Npn
1373 { \tex_long:D \tex_gdef:D }
1374 \cs_set_protected:Npn \cs_gset:Npx
1375 { \tex_long:D \tex_xdef:D }
1376 \cs_set_protected:Npn \cs_gset_protected_nopar:Npn
1377 { \etex_protected:D \tex_gdef:D }
1378 \cs_set_protected:Npn \cs_gset_protected_nopar:Npx
1379 { \etex_protected:D \tex_xdef:D }
```

```

1380 \cs_set_protected:Npn \cs_gset_protected:Npn
1381   { \etex_protected:D \tex_long:D \tex_gdef:D }
1382 \cs_set_protected:Npn \cs_gset_protected:Npx
1383   { \etex_protected:D \tex_long:D \tex_xdef:D }

```

(End definition for `\cs_gset_nopar:Npn` and others. These functions are documented on page 12.)

### 3.4 Selecting tokens

`\l__exp_internal_tl` Scratch token list variable for `l3expan`, used by `\use:x`, used in defining conditionals. We don't use `tl` methods because `l3basics` is loaded earlier.

```

1384 \cs_set_nopar:Npn \l__exp_internal_tl { }

```

(End definition for `\l__exp_internal_tl`.)

`\use:c` This macro grabs its argument and returns a csname from it.

```

1385 \cs_set:Npn \use:c #1 { \cs:w #1 \cs_end: }

```

(End definition for `\use:c`. This function is documented on page 16.)

`\use:x` Fully expands its argument and passes it to the input stream. Uses the reserved `\l__exp_internal_tl` which will be set up in `l3expan`.

```

1386 \cs_set_protected:Npn \use:x #1
1387   {
1388     \cs_set_nopar:Npx \l__exp_internal_tl {#1}
1389     \l__exp_internal_tl
1390   }

```

(End definition for `\use:x`. This function is documented on page 19.)

`\use:n` These macros grab their arguments and returns them back to the input (with outer braces removed).

```

\use:nnn 1391 \cs_set:Npn \use:n #1 {#1}
\use:nnnn 1392 \cs_set:Npn \use:nn #1#2 {#1#2}
1393 \cs_set:Npn \use:nnn #1#2#3 {#1#2#3}
1394 \cs_set:Npn \use:nnnn #1#2#3#4 {#1#2#3#4}

```

(End definition for `\use:n` and others. These functions are documented on page 17.)

`\use_i:nn` The equivalent to L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>'s `\@firstoftwo` and `\@secondoftwo`.

```

\use_ii:nn 1395 \cs_set:Npn \use_i:nn #1#2 {#1}
1396 \cs_set:Npn \use_ii:nn #1#2 {#2}

```

(End definition for `\use_i:nn` and `\use_ii:nn`. These functions are documented on page 18.)

`\use_i:nnn` We also need something for picking up arguments from a longer list.

```

\use_ii:nnn 1397 \cs_set:Npn \use_i:nnn #1#2#3 {#1}
\use_iii:nnn 1398 \cs_set:Npn \use_ii:nnn #1#2#3 {#2}
\use_i_ii:nnn 1399 \cs_set:Npn \use_iii:nnn #1#2#3 {#3}
\use_i:nnnn 1400 \cs_set:Npn \use_i_ii:nnn #1#2#3 {#1#2}
\use_ii:nnnn 1401 \cs_set:Npn \use_i:nnnn #1#2#3#4 {#1}
\use_iii:nnnn 1402 \cs_set:Npn \use_ii:nnnn #1#2#3#4 {#2}
\use_iv:nnnn 1403 \cs_set:Npn \use_iii:nnnn #1#2#3#4 {#3}
1404 \cs_set:Npn \use_iv:nnnn #1#2#3#4 {#4}

```



(End definition for `\use_i:nnn` and others. These functions are documented on page 18.)

`\use_none_delimit_by_q_nil:w` Functions that gobble everything until they see either `\q_nil`, `\q_stop`, or `\q_recursion_stop`, respectively.  
`\use_none_delimit_by_q_stop:w`  
`\use_none_delimit_by_q_recursion_stop:w`

```

1405 \cs_set:Npn \use_none_delimit_by_q_nil:w #1 \q_nil { }
1406 \cs_set:Npn \use_none_delimit_by_q_stop:w #1 \q_stop { }
1407 \cs_set:Npn \use_none_delimit_by_q_recursion_stop:w #1 \q_recursion_stop { }

```

(End definition for `\use_none_delimit_by_q_nil:w`, `\use_none_delimit_by_q_stop:w`, and `\use_none_delimit_by_q_recursion_stop:w`. These functions are documented on page 19.)

`\use_i_delimit_by_q_nil:nw` Same as above but execute first argument after gobbling. Very useful when you need to skip the rest of a mapping sequence but want an easy way to control what should be expanded next.  
`\use_i_delimit_by_q_stop:nw`  
`\use_i_delimit_by_q_recursion_stop:nw`

```

1408 \cs_set:Npn \use_i_delimit_by_q_nil:nw #1#2 \q_nil {#1}
1409 \cs_set:Npn \use_i_delimit_by_q_stop:nw #1#2 \q_stop {#1}
1410 \cs_set:Npn \use_i_delimit_by_q_recursion_stop:nw #1#2 \q_recursion_stop {#1}

```

(End definition for `\use_i_delimit_by_q_nil:nw`, `\use_i_delimit_by_q_stop:nw`, and `\use_i_delimit_by_q_recursion_stop:nw`. These functions are documented on page 19.)

### 3.5 Gobbling tokens from input

`\use_none:n` To gobble tokens from the input we use a standard naming convention: the number of tokens gobbled is given by the number of `n`'s following the `:` in the name. Although we could define functions to remove ten arguments or more using separate calls of `\use_none:nnnnn`, this is very non-intuitive to the programmer who will assume that expanding such a function once takes care of gobbling all the tokens in one go.

```

1411 \cs_set:Npn \use_none:n #1 { }
1412 \cs_set:Npn \use_none:nn #1#2 { }
1413 \cs_set:Npn \use_none:nnn #1#2#3 { }
1414 \cs_set:Npn \use_none:nnnn #1#2#3#4 { }
1415 \cs_set:Npn \use_none:nnnnn #1#2#3#4#5 { }
1416 \cs_set:Npn \use_none:nnnnnn #1#2#3#4#5#6 { }
1417 \cs_set:Npn \use_none:nnnnnnn #1#2#3#4#5#6#7 { }
1418 \cs_set:Npn \use_none:nnnnnnnn #1#2#3#4#5#6#7#8 { }
1419 \cs_set:Npn \use_none:nnnnnnnnn #1#2#3#4#5#6#7#8#9 { }

```

(End definition for `\use_none:n` and others. These functions are documented on page 18.)

### 3.6 Conditional processing and definitions

Underneath any predicate function (`_p`) or other conditional forms (TF, etc.) is a built-in logic saying that it after all of the testing and processing must return the *state* this leaves T<sub>E</sub>X in. Therefore, a simple user interface could be something like

```

\if_meaning:w #1#2
  \prg_return_true:
\else:
  \if_meaning:w #1#3
    \prg_return_true:
  \else:
    \prg_return_false:

```

```

\fi:
\fi:

```

Usually, a T<sub>E</sub>X programmer would have to insert a number of `\exp_after:wN`s to ensure the state value is returned at exactly the point where the last conditional is finished. However, that obscures the code and forces the T<sub>E</sub>X programmer to prove that he/she knows the  $2^n - 1$  table. We therefore provide the simpler interface.

`\prg_return_true:` The idea here is that `\exp:w` expands fully any `\else:` and `\fi:` that are waiting to be discarded, before reaching the `\exp_end:` which leaves an empty expansion. The code can then leave either the first or second argument in the input stream. This means that all of the branching code has to contain at least two tokens: see how the logical tests are actually implemented to see this.

```

1420 \cs_set:Npn \prg_return_true:
1421   { \exp_after:wN \use_i:nn \exp:w }
1422 \cs_set:Npn \prg_return_false:
1423   { \exp_after:wN \use_ii:nn \exp:w }

```

An extended state space could be implemented by including a more elaborate function in place of `\use_i:nn/\use_ii:nn`. Provided two arguments are absorbed then the code would work.

*(End definition for \prg\_return\_true: and \prg\_return\_false:. These functions are documented on page 91.)*

`\prg_set_conditional:Npnn` The user functions for the types using parameter text from the programmer. The various functions only differ by which function is used for the assignment. For those `Npnn` type functions, we must grab the parameter text, reading everything up to a left brace before continuing. Then split the base function into name and signature, and feed `{\langle name \rangle}` `{\langle signature \rangle}` `\langle boolean \rangle` `{\langle set or new \rangle}` `{\langle maybe protected \rangle}` `{\langle parameters \rangle}` `{TF, ...}` `{\langle code \rangle}` to the auxiliary function responsible for defining all conditionals.

```

1424 \cs_set_protected:Npn \prg_set_conditional:Npnn
1425   { \prg_generate_conditional_parm:nnNpnn { set } { } }
1426 \cs_set_protected:Npn \prg_new_conditional:Npnn
1427   { \prg_generate_conditional_parm:nnNpnn { new } { } }
1428 \cs_set_protected:Npn \prg_set_protected_conditional:Npnn
1429   { \prg_generate_conditional_parm:nnNpnn { set } { _protected } }
1430 \cs_set_protected:Npn \prg_new_protected_conditional:Npnn
1431   { \prg_generate_conditional_parm:nnNpnn { new } { _protected } }
1432 \cs_set_protected:Npn \prg_generate_conditional_parm:nnNpnn #1#2#3#4#
1433   {
1434     \cs_split_function:NN #3 \prg_generate_conditional:nnNnnnnn
1435     {#1} {#2} {#4}
1436   }

```

*(End definition for \prg\_set\_conditional:Npnn and others. These functions are documented on page 89.)*

`\prg_set_conditional:Nnn` The user functions for the types automatically inserting the correct parameter text based on the signature. The various functions only differ by which function is used for the assignment. Split the base function into name and signature. The second auxiliary generates the parameter text from the number of letters in the signature. Then feed `{\langle name \rangle}` `{\langle signature \rangle}` `\langle boolean \rangle` `{\langle set or new \rangle}` `{\langle maybe protected \rangle}` `{\langle parameters \rangle}` `{TF, ...}` `{\langle code \rangle}` to the auxiliary function responsible for defining all conditionals. If

the *signature* has more than 9 letters, the definition is aborted since T<sub>E</sub>X macros have at most 9 arguments. The erroneous case where the function name contains no colon is captured later.

```

1437 \cs_set_protected:Npn \prg_set_conditional:Nnn
1438   { \prg_generate_conditional_count:nnNnn { set } { } }
1439 \cs_set_protected:Npn \prg_new_conditional:Nnn
1440   { \prg_generate_conditional_count:nnNnn { new } { } }
1441 \cs_set_protected:Npn \prg_set_protected_conditional:Nnn
1442   { \prg_generate_conditional_count:nnNnn { set } { _protected } }
1443 \cs_set_protected:Npn \prg_new_protected_conditional:Nnn
1444   { \prg_generate_conditional_count:nnNnn { new } { _protected } }
1445 \cs_set_protected:Npn \prg_generate_conditional_count:nnNnn #1#2#3
1446   {
1447     \cs_split_function:NN #3 \prg_generate_conditional_count:nnNnnnn
1448     {#1} {#2}
1449   }
1450 \cs_set_protected:Npn \prg_generate_conditional_count:nnNnnnn #1#2#3#4#5
1451   {
1452     \cs_parm_from_arg_count:nnF
1453     { \prg_generate_conditional:nnNnnnn {#1} {#2} #3 {#4} {#5} }
1454     { \tl_count:n {#2} }
1455     {
1456       \msg_kernel_error:nxx { kernel } { bad-number-of-arguments }
1457       { \token_to_str:c { #1 : #2 } }
1458       { \tl_count:n {#2} }
1459       \use_none:nn
1460     }
1461   }

```

(End definition for `\prg_set_conditional:Nnn` and others. These functions are documented on page 89.)

`\prg_generate_conditional:nnNnnnnn`  
`\prg_generate_conditional:nnnnnnnw`

The workhorse here is going through a list of desired forms, *i.e.*, p, TF, T and F. The first three arguments come from splitting up the base form of the conditional, which gives the name, signature and a boolean to signal whether or not there was a colon in the name. In the absence of a colon, we throw an error and don't define any conditional. The fourth and fifth arguments build up the defining function. The sixth is the parameters to use (possibly empty), the seventh is the list of forms to define, the eighth is the replacement text which we will augment when defining the forms. The use of `\tl_to_str:n` makes the later loop more robust.

```

1462 \cs_set_protected:Npn \prg_generate_conditional:nnNnnnnn #1#2#3#4#5#6#7#8
1463   {
1464     \if_meaning:w \c_false_bool #3
1465     \msg_kernel_error:nxx { kernel } { missing-colon }
1466     { \token_to_str:c {#1} }
1467     \exp_after:wN \use_none:nn
1468     \fi:
1469     \use:x
1470     {
1471       \exp_not:N \prg_generate_conditional:nnnnnnw
1472       \exp_not:n { {#4} {#5} {#1} {#2} {#6} {#8} }
1473       \tl_to_str:n {#7}
1474       \exp_not:n { , \q_recursion_tail , \q_recursion_stop }

```

```

1475     }
1476 }

```

Looping through the list of desired forms. First are six arguments and seventh is the form. Use the form to call the correct type. If the form does not exist, the `\use:c` construction results in `\relax`, and the error message is displayed (unless the form is empty, to allow for {T, , F}), then `\use_none:nnnnnnn` cleans up. Otherwise, the error message is removed by the variant form.

```

1477 \cs_set_protected:Npn \__prg_generate_conditional:nnnnnnw #1#2#3#4#5#6#7 ,
1478 {
1479     \if_meaning:w \q_recursion_tail #7
1480     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1481     \fi:
1482     \use:c { __prg_generate_ #7 _form:wnnnnnn }
1483     \tl_if_empty:nF {#7}
1484     {
1485         \__msg_kernel_error:nxxx
1486         { kernel } { conditional-form-unknown }
1487         {#7} { \token_to_str:c { #3 : #4 } }
1488     }
1489     \use_none:nnnnnnn
1490     \q_stop
1491     {#1} {#2} {#3} {#4} {#5} {#6}
1492     \__prg_generate_conditional:nnnnnnw {#1} {#2} {#3} {#4} {#5} {#6}
1493 }

```

(End definition for `\__prg_generate_conditional:nnNnnnnn` and `\__prg_generate_conditional:nnnnnnw`.)

```

\__prg_generate_p_form:wnnnnnn
\__prg_generate_TF_form:wnnnnnn
\__prg_generate_T_form:wnnnnnn
\__prg_generate_F_form:wnnnnnn

```

How to generate the various forms. Those functions take the following arguments: 1: **set** or **new**, 2: empty or `_protected`, 3: function name 4: signature, 5: parameter text (or empty), 6: replacement. Remember that the logic-returning functions expect two arguments to be present after `\exp_end::` notice the construction of the different variants relies on this, and that the TF and F variants will be slightly faster than the T version. The p form is only valid for expandable tests, we check for that by making sure that the second argument is empty.

```

1494 \cs_set_protected:Npn \__prg_generate_p_form:wnnnnnn
1495     #1 \q_stop #2#3#4#5#6#7
1496 {
1497     \if_meaning:w \scan_stop: #3 \scan_stop:
1498     \exp_after:wN \use_i:nn
1499     \else:
1500     \exp_after:wN \use_ii:nn
1501     \fi:
1502     {
1503         \exp_args:cc { cs_ #2 #3 :Npn } { #4 _p: #5 } #6
1504         { #7 \exp_end: \c_true_bool \c_false_bool }
1505     }
1506     {
1507         \__msg_kernel_error:nxx { kernel } { protected-predicate }
1508         { \token_to_str:c { #4 _p: #5 } }
1509     }
1510 }
1511 \cs_set_protected:Npn \__prg_generate_T_form:wnnnnnn
1512     #1 \q_stop #2#3#4#5#6#7

```

```

1513 {
1514   \exp_args:cc { cs_ #2 #3 :Npn } { #4 : #5 T } #6
1515   { #7 \exp_end: \use:n \use_none:n }
1516 }
1517 \cs_set_protected:Npn \__prg_generate_F_form:wnnnnnn
1518 #1 \q_stop #2#3#4#5#6#7
1519 {
1520   \exp_args:cc { cs_ #2 #3 :Npn } { #4 : #5 F } #6
1521   { #7 \exp_end: { } }
1522 }
1523 \cs_set_protected:Npn \__prg_generate_TF_form:wnnnnnn
1524 #1 \q_stop #2#3#4#5#6#7
1525 {
1526   \exp_args:cc { cs_ #2 #3 :Npn } { #4 : #5 TF } #6
1527   { #7 \exp_end: }
1528 }

```

(End definition for \\_\_prg\_generate\_p\_form:wnnnnnn and others.)

**\prg\_set\_eq\_conditional:NNn** The setting-equal functions. Split both functions and feed  $\{\langle name_1 \rangle\}$   $\{\langle signature_1 \rangle\}$   $\langle boolean_1 \rangle$   $\{\langle name_2 \rangle\}$   $\{\langle signature_2 \rangle\}$   $\langle boolean_2 \rangle$   $\langle copying\ function \rangle$   $\langle conditions \rangle$ ,  $\backslash q\_recursion\_tail$ ,  $\backslash q\_recursion\_stop$  to a first auxiliary.

**\prg\_new\_eq\_conditional:NNn**

$\backslash\_prg\_set\_eq\_conditional:NNNn$

```

1529 \cs_set_protected:Npn \prg_set_eq_conditional:NNn
1530 { \__prg_set_eq_conditional:NNNn \cs_set_eq:cc }
1531 \cs_set_protected:Npn \prg_new_eq_conditional:NNn
1532 { \__prg_set_eq_conditional:NNNn \cs_new_eq:cc }
1533 \cs_set_protected:Npn \__prg_set_eq_conditional:NNNn #1#2#3#4
1534 {
1535   \use:x
1536   {
1537     \exp_not:N \__prg_set_eq_conditional:nnNnnNW
1538     \__cs_split_function:NN #2 \prg_do_nothing:
1539     \__cs_split_function:NN #3 \prg_do_nothing:
1540     \exp_not:N #1
1541     \tl_to_str:n {#4}
1542     \exp_not:n { , \q_recursion_tail , \q_recursion_stop }
1543   }
1544 }

```

(End definition for \prg\_set\_eq\_conditional:NNn, \prg\_new\_eq\_conditional:NNn, and \\_\_prg\_set\_eq\_conditional:NNNn. These functions are documented on page 90.)

$\backslash\_prg\_set\_eq\_conditional:nnNnnNW$   
 $\backslash\_prg\_set\_eq\_conditional\_loop:nnnnNW$   
 $\backslash\_prg\_set\_eq\_conditional\_p\_form:nnn$   
 $\backslash\_prg\_set\_eq\_conditional\_TF\_form:nnn$   
 $\backslash\_prg\_set\_eq\_conditional\_T\_form:nnn$   
 $\backslash\_prg\_set\_eq\_conditional\_F\_form:nnn$

Split the function to be defined, and setup a manual clist loop over argument #6 of the first auxiliary. The second auxiliary receives twice three arguments coming from splitting the function to be defined and the function to copy. Make sure that both functions contained a colon, otherwise we don't know how to build conditionals, hence abort. Call the looping macro, with arguments  $\{\langle name_1 \rangle\}$   $\{\langle signature_1 \rangle\}$   $\{\langle name_2 \rangle\}$   $\{\langle signature_2 \rangle\}$   $\langle copying\ function \rangle$  and followed by the comma list. At each step in the loop, make sure that the conditional form we copy is defined, and copy it, otherwise abort.

```

1545 \cs_set_protected:Npn \__prg_set_eq_conditional:nnNnnNW #1#2#3#4#5#6
1546 {
1547   \if_meaning:w \c_false_bool #3
1548   \__msg_kernel_error:nnx { kernel } { missing-colon }
1549   { \token_to_str:c {#1} }

```

```

1550     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1551 \fi:
1552 \if_meaning:w \c_false_bool #6
1553   \_msg_kernel_error:nxx { kernel } { missing-colon }
1554   { \token_to_str:c {#4} }
1555   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1556 \fi:
1557 \__prg_set_eq_conditional_loop:nnnnNw {#1} {#2} {#4} {#5}
1558 }
1559 \cs_set_protected:Npn \__prg_set_eq_conditional_loop:nnnnNw #1#2#3#4#5#6 ,
1560 {
1561   \if_meaning:w \q_recursion_tail #6
1562   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1563 \fi:
1564 \use:c { \__prg_set_eq_conditional_ #6 _form:wNnnnn }
1565   \tl_if_empty:nF {#6}
1566   {
1567     \_msg_kernel_error:nxxx
1568     { kernel } { conditional-form-unknown }
1569     {#6} { \token_to_str:c { #1 : #2 } }
1570   }
1571   \use_none:nnnnnn
1572   \q_stop
1573   #5 {#1} {#2} {#3} {#4}
1574   \__prg_set_eq_conditional_loop:nnnnNw {#1} {#2} {#3} {#4} #5
1575 }
1576 \cs_set:Npn \__prg_set_eq_conditional_p_form:wNnnnn #1 \q_stop #2#3#4#5#6
1577 {
1578   \__chk_if_exist_cs:c { #5 _p : #6 }
1579   #2 { #3 _p : #4 } { #5 _p : #6 }
1580 }
1581 \cs_set:Npn \__prg_set_eq_conditional_TF_form:wNnnnn #1 \q_stop #2#3#4#5#6
1582 {
1583   \__chk_if_exist_cs:c { #5 : #6 TF }
1584   #2 { #3 : #4 TF } { #5 : #6 TF }
1585 }
1586 \cs_set:Npn \__prg_set_eq_conditional_T_form:wNnnnn #1 \q_stop #2#3#4#5#6
1587 {
1588   \__chk_if_exist_cs:c { #5 : #6 T }
1589   #2 { #3 : #4 T } { #5 : #6 T }
1590 }
1591 \cs_set:Npn \__prg_set_eq_conditional_F_form:wNnnnn #1 \q_stop #2#3#4#5#6
1592 {
1593   \__chk_if_exist_cs:c { #5 : #6 F }
1594   #2 { #3 : #4 F } { #5 : #6 F }
1595 }

```

(End definition for \\_\_prg\_set\_eq\_conditional:nnnnNw and others.)

All that is left is to define the canonical boolean true and false. I think Michael originated the idea of expandable boolean tests. At first these were supposed to expand into either TT or TF to be tested using \if:w but this was later changed to 00 and 01, so they could be used in logical operations. Later again they were changed to being numerical constants with values of 1 for true and 0 for false. We need this from the get-go.

```

\c_true_bool Here are the canonical boolean values.
\c_false_bool
1596 \tex_chardef:D \c_true_bool = 1 ~
1597 \tex_chardef:D \c_false_bool = 0 ~

```

(End definition for `\c_true_bool` and `\c_false_bool`. These variables are documented on page 20.)

### 3.7 Dissecting a control sequence

```

\cs_to_str:N This converts a control sequence into the character string of its name, removing the
__cs_to_str:N leading escape character. This turns out to be a non-trivial matter as there are different
__cs_to_str:w cases:

```

- The usual case of a printable escape character;
- the case of a non-printable escape characters, e.g., when the value of the `\escapechar` is negative;
- when the escape character is a space.

One approach to solve this is to test how many tokens result from `\token_to_str:N \a`. If there are two tokens, then the escape character is printable, while if it is non-printable then only one is present.

However, there is an additional complication: the control sequence itself may start with a space. Clearly that should *not* be lost in the process of converting to a string. So the approach adopted is a little more intricate still. When the escape character is printable, `\token_to_str:N \_ \_` yields the escape character itself and a space. The character codes are different, thus the `\if:w` test is false, and TeX reads `\__cs_to_str:N` after turning the following control sequence into a string; this auxiliary removes the escape character, and stops the expansion of the initial `\tex_romannumeral:D`. The second case is that the escape character is not printable. Then the `\if:w` test is unfinished after reading a the space from `\token_to_str:N \_ \_`, and the auxiliary `\__cs_to_str:w` is expanded, feeding – as a second character for the test; the test is false, and TeX skips to `\fi:`, then performs `\token_to_str:N`, and stops the `\tex_romannumeral:D` with `\c_zero`. The last case is that the escape character is itself a space. In this case, the `\if:w` test is true, and the auxiliary `\__cs_to_str:w` comes into play, inserting `-\__int_value:w`, which expands `\c_zero` to the character 0. The initial `\tex_romannumeral:D` then sees 0, which is not a terminated number, followed by the escape character, a space, which is removed, terminating the expansion of `\tex_romannumeral:D`. In all three cases, `\cs_to_str:N` takes two expansion steps to be fully expanded.

```

1598 \cs_set:Npn \cs_to_str:N
1599 {

```

We implement the expansion scheme using `\tex_romannumeral:D` terminating it with `\c_zero` rather than using `\exp:w` and `\exp_end:` as we normally do. The reason is that the code heavily depends on terminating the expansion with `\c_zero` so we make this dependency explicit.

```

1600 \tex_romannumeral:D
1601 \if:w \token_to_str:N \__cs_to_str:w \fi:
1602 \exp_after:wN \__cs_to_str:N \token_to_str:N
1603 }
1604 \cs_set:Npn \__cs_to_str:N #1 { \c_zero }
1605 \cs_set:Npn \__cs_to_str:w #1 \__cs_to_str:N
1606 { - \__int_value:w \fi: \exp_after:wN \c_zero }

```

If speed is a concern we could use `\csstring` in LuaTeX. For the empty csname that primitive gives an empty result while the current `\cs_to_str:N` gives incorrect results in all engines (this is impossible to fix without huge performance hit).

(End definition for `\cs_to_str:N`, `\_cs_to_str:N`, and `\_cs_to_str:w`. These functions are documented on page 17.)

`\_cs_split_function:NN` This function takes a function name and splits it into name with the escape char removed and argument specification. In addition to this, a third argument, a boolean  $\langle true \rangle$  or  $\langle false \rangle$  is returned with  $\langle true \rangle$  for when there is a colon in the function and  $\langle false \rangle$  if there is not. Lastly, the second argument of `\_cs_split_function:NN` is supposed to be a function taking three variables, one for name, one for signature, and one for the boolean. For example, `\_cs_split_function:NN \foo_bar:cnx \use_i:nnn` as input becomes `\use_i:nnn {foo_bar} {cnx} \c_true_bool`.

We cannot use `:` directly as it has the wrong category code so an x-type expansion is used to force the conversion.

First ensure that we actually get a properly evaluated string by expanding `\cs_to_str:N` twice. If the function contained a colon, the auxiliary takes as `#1` the function name, delimited by the first colon, then the signature `#2`, delimited by `\q_mark`, then `\c_true_bool` as `#3`, and `#4` cleans up until `\q_stop`. Otherwise, the `#1` contains the function name and `\q_mark \c_true_bool`, `#2` is empty, `#3` is `\c_false_bool`, and `#4` cleans up. In both cases, `#5` is the  $\langle processor \rangle$ . The second auxiliary trims the trailing `\q_mark` from the function name if present (that is, if the original function had no colon).

```

1607 \cs_set:Npx \_cs_split_function:NN #1
1608 {
1609   \exp_not:N \exp_after:wN \exp_not:N \exp_after:wN
1610   \exp_not:N \exp_after:wN \exp_not:N \_cs_split_function_auxi:w
1611   \exp_not:N \cs_to_str:N #1 \exp_not:N \q_mark \c_true_bool
1612   \token_to_str:N : \exp_not:N \q_mark \c_false_bool
1613   \exp_not:N \q_stop
1614 }
1615 \use:x
1616 {
1617   \cs_set:Npn \exp_not:N \_cs_split_function_auxi:w
1618     ##1 \token_to_str:N : ##2 \exp_not:N \q_mark ##3##4 \exp_not:N \q_stop ##5
1619 }
1620 { \_cs_split_function_auxii:w #5 #1 \q_mark \q_stop {#2} #3 }
1621 \cs_set:Npn \_cs_split_function_auxii:w #1#2 \q_mark #3 \q_stop
1622 { #1 {#2} }

```

(End definition for `\_cs_split_function:NN`, `\_cs_split_function_auxi:w`, and `\_cs_split_function_auxii:w`.)

`\_cs_get_function_name:N` Simple wrappers.

```

\_cs_get_function_name:N 1623 \cs_set:Npn \_cs_get_function_name:N #1
\_cs_get_function_signature:N 1624 { \_cs_split_function:NN #1 \use_i:nnn }
1625 \cs_set:Npn \_cs_get_function_signature:N #1
1626 { \_cs_split_function:NN #1 \use_ii:nnn }

```

(End definition for `\_cs_get_function_name:N` and `\_cs_get_function_signature:N`.)



### 3.8 Exist or free

A control sequence is said to *exist* (to be used) if has an entry in the hash table and its meaning is different from the primitive `\relax` token. A control sequence is said to be *free* (to be defined) if it does not already exist.

`\cs_if_exist_p:N` Two versions for checking existence. For the `N` form we firstly check for `\scan_stop:` and  
`\cs_if_exist_p:c` then if it is in the hash table. There is no problem when inputting something like `\else:`  
`\cs_if_exist:NTF` or `\fi:` as `TEX` will only ever skip input in case the token tested against is `\scan_stop:`.  
`\cs_if_exist:cTF`

```

1627 \prg_set_conditional:Npnn \cs_if_exist:N #1 { p , T , F , TF }
1628 {
1629     \if_meaning:w #1 \scan_stop:
1630     \prg_return_false:
1631     \else:
1632         \if_cs_exist:N #1
1633         \prg_return_true:
1634         \else:
1635             \prg_return_false:
1636         \fi:
1637     \fi:
1638 }
```

For the `c` form we firstly check if it is in the hash table and then for `\scan_stop:` so that we do not add it to the hash table unless it was already there. Here we have to be careful as the text to be skipped if the first test is false may contain tokens that disturb the scanner. Therefore, we ensure that the second test is performed after the first one has concluded completely.

```

1639 \prg_set_conditional:Npnn \cs_if_exist:c #1 { p , T , F , TF }
1640 {
1641     \if_cs_exist:w #1 \cs_end:
1642     \exp_after:wN \use_i:nn
1643     \else:
1644         \exp_after:wN \use_ii:nn
1645     \fi:
1646     {
1647         \exp_after:wN \if_meaning:w \cs:w #1 \cs_end: \scan_stop:
1648         \prg_return_false:
1649         \else:
1650             \prg_return_true:
1651         \fi:
1652     }
1653     \prg_return_false:
1654 }
```

(End definition for `\cs_if_exist:NTF`. This function is documented on page 20.)

`\cs_if_free_p:N` The logical reversal of the above.

```

1655 \prg_set_conditional:Npnn \cs_if_free:N #1 { p , T , F , TF }
1656 {
1657     \if_meaning:w #1 \scan_stop:
1658     \prg_return_true:
1659     \else:
1660         \if_cs_exist:N #1
1661         \prg_return_false:

```

```

1662     \else:
1663     \prg_return_true:
1664     \fi:
1665 \fi:
1666 }
1667 \prg_set_conditional:Npnn \cs_if_free:c #1 { p , T , F , TF }
1668 {
1669     \if_cs_exist:w #1 \cs_end:
1670     \exp_after:wN \use_i:nn
1671     \else:
1672     \exp_after:wN \use_ii:nn
1673     \fi:
1674     {
1675         \exp_after:wN \if_meaning:w \cs:w #1 \cs_end: \scan_stop:
1676         \prg_return_true:
1677     \else:
1678         \prg_return_false:
1679     \fi:
1680     }
1681     { \prg_return_true: }
1682 }

```

(End definition for `\cs_if_free:NTF`. This function is documented on page 20.)

`\cs_if_exist_use:N` The `\cs_if_exist_use:...` functions cannot be implemented as conditionals because the true branch must leave both the control sequence itself and the true code in the input stream. For the `c` variants, we are careful not to put the control sequence in the hash table if it does not exist. In LuaTeX we could use the `\lastnamedcs` primitive.

```

1683 \cs_set:Npn \cs_if_exist_use:NTF #1#2
1684 { \cs_if_exist:NTF #1 { #1 #2 } }
1685 \cs_set:Npn \cs_if_exist_use:NF #1
1686 { \cs_if_exist:NTF #1 { #1 } }
1687 \cs_set:Npn \cs_if_exist_use:NT #1 #2
1688 { \cs_if_exist:NTF #1 { #1 #2 } { } }
1689 \cs_set:Npn \cs_if_exist_use:N #1
1690 { \cs_if_exist:NTF #1 { #1 } { } }
1691 \cs_set:Npn \cs_if_exist_use:cTF #1#2
1692 { \cs_if_exist:cTF {#1} { \use:c {#1} #2 } }
1693 \cs_set:Npn \cs_if_exist_use:cF #1
1694 { \cs_if_exist:cTF {#1} { \use:c {#1} } }
1695 \cs_set:Npn \cs_if_exist_use:cT #1#2
1696 { \cs_if_exist:cTF {#1} { \use:c {#1} #2 } { } }
1697 \cs_set:Npn \cs_if_exist_use:c #1
1698 { \cs_if_exist:cTF {#1} { \use:c {#1} } { } }

```

(End definition for `\cs_if_exist_use:NTF`. This function is documented on page 16.)

### 3.9 Checking and patching (new) functions

We provide two kinds of functions that can be used to define control sequences. On the one hand we have functions that check if their argument doesn't already exist, they are called `\..._new`. The second type of defining functions doesn't check if the argument is already defined.

Before we can define them, we need some auxiliary macros that allow us to generate error messages. The next few definitions here are only temporary, they will be redefined later on.

<pre> \__msg_kernel_error:nxxx \__msg_kernel_error:nxx   \__msg_kernel_error:nn </pre>	<p>If an internal error occurs before L<sup>A</sup>T<sub>E</sub>X3 has loaded l3msg then the code should issue a usable if terse error message and halt. This can only happen if a coding error is made by the team, so this is a reasonable response. Setting the <code>\newlinechar</code> is needed, to turn <code>^^J</code> into a proper line break in plain T<sub>E</sub>X.</p>
--	--

```

1699 \cs_set_protected:Npn \__msg_kernel_error:nxxx #1#2#3#4
1700 {
1701   \tex_newlinechar:D = '\^^J \tex_relax:D
1702   \tex_errmessage:D
1703   {
1704     !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!~! ^^J
1705     Argh,~internal~LaTeX3-error! ^^J ^^J
1706     Module ~ #1 , ~ message~name~"#2": ^^J
1707     Arguments~'#3'~and~'#4' ^^J ^^J
1708     This~is~one~for~The~LaTeX3-Project::~bailing-out
1709   }
1710   \tex_end:D
1711 }
1712 \cs_set_protected:Npn \__msg_kernel_error:nxx #1#2#3
1713 { \__msg_kernel_error:nxxx {#1} {#2} {#3} { } }
1714 \cs_set_protected:Npn \__msg_kernel_error:nn #1#2
1715 { \__msg_kernel_error:nxxx {#1} {#2} { } { } }

```

(End definition for `__msg_kernel_error:nxxx`, `__msg_kernel_error:nxx`, and `__msg_kernel_error:nn`.)

`\msg_line_context:` Another one from `l3msg` which will be altered later.

```

1716 \cs_set:Npn \msg_line_context:
1717   { on-line~ \tex_the:D \tex_inputlineno:D }

```

(End definition for `\msg_line_context`:. This function is documented on page 129.)

```
\iow_log:x We define a routine to write only to the log file. And a similar one for writing to both
\iow_term:x the log file and the terminal. These will be redefined later by l3io.
```

```

1718 \cs_set_protected:Npn \iow_log:x
1719   { \tex_immediate:D \tex_write:D -1 }
1720 \cs_set_protected:Npn \iow_term:x
1721   { \tex_immediate:D \tex_write:D 16 }

```

(End definition for \iow\_log:x and \iow\_term:x. These functions are documented on page 143.)

<code>\debug_log_functions_on:</code>	When debugging is not enabled at all (including in the format), the <code>\debug_log-</code>
<code>\debug_log_functions_off:</code>	<code>functions_on/off:</code> functions simply produce errors, while <code>\__debug_suspend_log:</code>
<code>\__debug_log:x</code>	and <code>\__debug_resume_log:</code> do nothing.

```

1722 \cs_set_protected:Npn \debug_log_functions_on:
1723 {
1724   \__msg_kernel_error:nnx { kernel } { enable-debug }
1725   { \token_to_str:N \debug_log_functions_on: }
1726 }
1727 \cs_set_protected:Npn \debug_log_functions_off:
1728 {
1729   \__msg_kernel_error:nnx { kernel } { enable-debug }

```

```

1730     { \token_to_str:N \debug_log_functions_off: }
1731   }
1732   \cs_set_protected:Npn \__debug_suspend_log: { }
1733   \cs_set_protected:Npn \__debug_resume_log: { }

```

Otherwise, they set up `\__debug_log:x`, `\__debug_suspend_log:`, and `\__debug_resume_log:` to have the following behaviour. The function `\__debug_log:x` is used to write some information to the log file in case the `log-function` option is active and to otherwise ignore its argument. Using this function rather than directly using `\iow_log:x` allows for `\__debug_suspend_log:` which disables such messages until the matching `\__debug_resume_log:`. These two commands are used to improve the logging for datatypes with multiple parts (currently only coffins). They should come in pairs, which can be nested. The function `\exp_not:o` is defined in `l3expan` later on but `\__debug_suspend_log:` and `\__debug_resume_log:` are not used before that point. Once everything is defined, turn logging on or off depending on what option was given.

```

1734 \begin{package}
1735 \tex_ifodd:D \l@expl@enable@debug@bool
1736   \cs_set_protected:Npn \debug_log_functions_on:
1737   {
1738     \cs_set_protected:Npn \__debug_log:x { \iow_log:x }
1739     \cs_set_protected:Npn \__debug_suspend_log:
1740     {
1741       \cs_set_protected:Npx \__debug_resume_log:
1742       {
1743         \cs_set_protected:Npn \__debug_resume_log:
1744         { \exp_not:o { \__debug_resume_log: } }
1745         \cs_set_protected:Npn \__debug_log:x
1746         { \exp_not:o { \__debug_log:x } }
1747       }
1748       \cs_set_protected:Npn \__debug_log:x { \use_none:n }
1749     }
1750     \cs_set_protected:Npn \__debug_resume_log: { }
1751   }
1752   \cs_set_protected:Npn \debug_log_functions_off:
1753   {
1754     \cs_set_protected:Npn \__debug_log:x { \use_none:n }
1755     \cs_set_protected:Npn \__debug_suspend_log: { }
1756     \cs_set_protected:Npn \__debug_resume_log: { }
1757   }
1758   \tex_ifodd:D \l@expl@log@functions@bool
1759   \debug_log_functions_on:
1760   \else:
1761     \debug_log_functions_off:
1762   \fi:
1763 \end{package}
1764 \end{package}

```

(End definition for `\debug_log_functions_on:` and others. These functions are documented on page 230.)

`\__debug_patch:nnNw`

When debugging is not enabled, `\__debug_patch:nnNw` throws the patch away. Otherwise it can be followed by `\cs_new:Npn` or `\prg_new_conditional:Npnn` or their protected counterparts. In each case, grab the name of the function to be defined and its parameters using `\__debug_patch_param:w` then insert tokens before and after the

definition. Of course for a conditional one should likely not insert anything after the code.

```

1765 \cs_set_protected:Npn \__debug_patch:nnNw #1#2 { }
1766 (*package)
1767 \tex_ifodd:D \l@expl@enable@debug@bool
1768 \cs_set_protected:Npn \__debug_patch:nnNw #1#2#3
1769 {
1770   \tex_ifcase:D
1771     \if_meaning:w #3 \cs_new_protected:Npn 1~ \fi:
1772     \if_meaning:w #3 \cs_new:Npn 1~ \fi:
1773     \if_meaning:w #3 \cs_set_protected:Npn 1~ \fi:
1774     \if_meaning:w #3 \cs_set:Npn 1~ \fi:
1775     \if_meaning:w #3 \cs_gset_protected:Npn 1~ \fi:
1776     \if_meaning:w #3 \cs_gset:Npn 1~ \fi:
1777     \if_meaning:w #3 \prg_new_protected_conditional:Npnn 2~ \fi:
1778     \if_meaning:w #3 \prg_new_conditional:Npnn 2~ \fi:
1779     \_msg_kernel_error:nxx { kernel } { debug-unpatchable }
1780     { \token_to_str:N #3 }
1781   \or:
1782     \exp_after:wN \__debug_patch_param:NNnnNnp
1783     \exp_after:wN \__debug_patch_new:nnNNnn
1784   \else:
1785     \exp_after:wN \__debug_patch_param:NNnnNnp
1786     \exp_after:wN \__debug_patch_new_conditional:nnNNnnn
1787   \fi:
1788   \use_none:nn {#1} {#2} #3
1789 }
1790 \cs_set_protected:Npn \__debug_patch_param:NNnnNnp #1#2#3#4#5#6#7#
1791 { #1 {#3} {#4} #5 #6 {#7} }
1792 \cs_set_protected:Npn \__debug_patch_new:nnNNnn #1#2#3#4#5#6
1793 { #3 #4 #5 { #1 #6 #2 } }
1794 \cs_set_protected:Npn \__debug_patch_new_conditional:nnNNnnn
1795 #1#2#3#4#5#6#7
1796 { #3 #4 #5 {#6} { #1 #7 #2 } }
1797 \fi:
1798 </package>

```

(End definition for \\_\_debug\_patch:nnNw and others.)

**\\_\_chk\_if\_free\_cs:N** This command is called by \cs\_new\_nopar:Npn and \cs\_new\_eq:NN *etc.* to make sure that the argument sequence is not already in use. If it is, an error is signalled. It checks if  $\langle csname \rangle$  is undefined or \scan\_stop:. Otherwise an error message is issued. We have to make sure we don't put the argument into the conditional processing since it may be an \if... type function!

**\\_\_chk\_if\_free\_cs:c**

```

1799 \__debug_patch:nnNw { }
1800 { \__debug_log:x { Defining~\token_to_str:N #1~ \msg_line_context: } }
1801 \cs_set_protected:Npn \__chk_if_free_cs:N #1
1802 {
1803   \cs_if_free:NF #1
1804   {
1805     \_msg_kernel_error:nxx { kernel } { command-already-defined }
1806     { \token_to_str:N #1 } { \token_to_meaning:N #1 }
1807   }
1808 }

```

```

1809 \cs_set_protected:Npn \__chk_if_free_cs:c
1810 { \exp_args:Nc \__chk_if_free_cs:N }

```

(End definition for \\_\_chk\_if\_free\_cs:N.)

`\debug_check_declarations_on:` When debugging is not active these two user functions produce an error. Otherwise they  
`\debug_check_declarations_off:` set up `\__chk_if_exist_var:N`, a function which when `check-declarations` is active  
`\__chk_if_exist_var:N` tests that a given variable is defined.

```

1811 \cs_set_protected:Npn \debug_check_declarations_on:
1812 {
1813   \__msg_kernel_error:nnx { kernel } { enable-debug }
1814   { \token_to_str:N \debug_check_declarations_on: }
1815 }
1816 \cs_set_protected:Npn \debug_check_declarations_off:
1817 {
1818   \__msg_kernel_error:nnx { kernel } { enable-debug }
1819   { \token_to_str:N \debug_check_declarations_off: }
1820 }
1821 \*package
1822 \tex_ifodd:D \l@expl@enable@debug@bool
1823 \cs_set_protected:Npn \debug_check_declarations_on:
1824 {
1825   \cs_set_protected:Npn \__chk_if_exist_var:N ##1
1826   {
1827     \cs_if_exist:NF ##1
1828     {
1829       \__msg_kernel_error:nnx { check } { non-declared-variable }
1830       { \token_to_str:N ##1 }
1831     }
1832   }
1833 }
1834 \cs_set_protected:Npn \debug_check_declarations_off:
1835 { \cs_set_protected:Npn \__chk_if_exist_var:N ##1 { } }
1836 \tex_ifodd:D \l@expl@check@declarations@bool
1837 \debug_check_declarations_on:
1838 \else:
1839 \debug_check_declarations_off:
1840 \fi:
1841 \fi:
1842 \</package>

```

(End definition for `\debug_check_declarations_on:`, `\debug_check_declarations_off:`, and `\__chk_if_exist_var:N`. These functions are documented on page 229.)

`\__chk_if_exist_cs:N` This function issues an error message when the control sequence in its argument does  
`\__chk_if_exist_cs:c` not exist.

```

1843 \cs_set_protected:Npn \__chk_if_exist_cs:N #1
1844 {
1845   \cs_if_exist:NF #1
1846   {
1847     \__msg_kernel_error:nnx { kernel } { command-not-defined }
1848     { \token_to_str:N #1 }
1849   }
1850 }

```

```

1851 \cs_set_protected:Npn \__chk_if_exist_cs:c
1852 { \exp_args:Nc \__chk_if_exist_cs:N }

```

(End definition for \\_\_chk\_if\_exist\_cs:N.)

### 3.10 Defining new functions

**\cs\_new\_nopar:Npn** Function which check that the control sequence is free before defining it.

```

\cs_new_nopar:Npn
\cs_new_nopar:Npx
  \cs_new:Npn
    \cs_new:Npx
\cs_new_protected_nopar:Npn
\cs_new_protected_nopar:Npx
  \cs_new_protected:Npn
    \cs_new_protected:Npx
      \__cs_tmp:w
1853 \cs_set:Npn \__cs_tmp:w #1#2
1854 {
1855   \cs_set_protected:Npn #1 ##1
1856   {
1857     \__chk_if_free_cs:N ##1
1858     #2 ##1
1859   }
1860 }
1861 \__cs_tmp:w \cs_new_nopar:Npn      \cs_gset_nopar:Npn
1862 \__cs_tmp:w \cs_new_nopar:Npx      \cs_gset_nopar:Npx
1863 \__cs_tmp:w \cs_new:Npn             \cs_gset:Npn
1864 \__cs_tmp:w \cs_new:Npx             \cs_gset:Npx
1865 \__cs_tmp:w \cs_new_protected_nopar:Npn \cs_gset_protected_nopar:Npn
1866 \__cs_tmp:w \cs_new_protected_nopar:Npx \cs_gset_protected_nopar:Npx
1867 \__cs_tmp:w \cs_new_protected:Npn     \cs_gset_protected:Npn
1868 \__cs_tmp:w \cs_new_protected:Npx     \cs_gset_protected:Npx

```

(End definition for \cs\_new\_nopar:Npn and others. These functions are documented on page 11.)

**\cs\_set\_nopar:cpn** Like **\cs\_set\_nopar:Npn** and **\cs\_new\_nopar:Npn**, except that the first argument consists of the sequence of characters that should be used to form the name of the desired control sequence (the c stands for csname argument, see the expansion module). Global versions are also provided.

**\cs\_set\_nopar:cpn** *\cs\_set\_nopar:cpn*(string)<rep-text> turns <string> into a csname and then assigns <rep-text> to it by using **\cs\_set\_nopar:Npn**. This means that there might be a parameter string between the two arguments.

```

1869 \cs_set:Npn \__cs_tmp:w #1#2
1870 { \cs_new_protected_nopar:Npn #1 { \exp_args:Nc #2 } }
1871 \__cs_tmp:w \cs_set_nopar:cpn \cs_set_nopar:Npn
1872 \__cs_tmp:w \cs_set_nopar:cpx \cs_set_nopar:Npx
1873 \__cs_tmp:w \cs_gset_nopar:cpn \cs_gset_nopar:Npn
1874 \__cs_tmp:w \cs_gset_nopar:cpx \cs_gset_nopar:Npx
1875 \__cs_tmp:w \cs_new_nopar:cpn \cs_new_nopar:Npn
1876 \__cs_tmp:w \cs_new_nopar:cpx \cs_new_nopar:Npx

```

(End definition for \cs\_set\_nopar:cpn and others. These functions are documented on page 11.)

**\cs\_set:cpn** Variants of the **\cs\_set:Npn** versions which make a csname out of the first arguments.  
**\cs\_set:cpx** We may also do this globally.

```

\cs_gset:cpn
\cs_gset:cpx
\cs_new:cpn
\cs_new:cpx
1877 \__cs_tmp:w \cs_set:cpn \cs_set:Npn
1878 \__cs_tmp:w \cs_set:cpx \cs_set:Npx
1879 \__cs_tmp:w \cs_gset:cpn \cs_gset:Npn
1880 \__cs_tmp:w \cs_gset:cpx \cs_gset:Npx
1881 \__cs_tmp:w \cs_new:cpn \cs_new:Npn
1882 \__cs_tmp:w \cs_new:cpx \cs_new:Npx

```

(End definition for `\cs_set:cpn` and others. These functions are documented on page 11.)

<code>\cs_set_protected_nopar:cpn</code>	1883	<code>__cs_tmp:w \cs_set_protected_nopar:cpn \cs_set_protected_nopar:Npn</code>
<code>\cs_set_protected_nopar:cpx</code>	1884	<code>__cs_tmp:w \cs_set_protected_nopar:cpx \cs_set_protected_nopar:Npx</code>
<code>\cs_gset_protected_nopar:cpn</code>	1885	<code>__cs_tmp:w \cs_gset_protected_nopar:cpn \cs_gset_protected_nopar:Npn</code>
<code>\cs_gset_protected_nopar:cpx</code>	1886	<code>__cs_tmp:w \cs_gset_protected_nopar:cpx \cs_gset_protected_nopar:Npx</code>
<code>\cs_new_protected_nopar:cpn</code>	1887	<code>__cs_tmp:w \cs_new_protected_nopar:cpn \cs_new_protected_nopar:Npn</code>
<code>\cs_new_protected_nopar:cpx</code>	1888	<code>__cs_tmp:w \cs_new_protected_nopar:cpx \cs_new_protected_nopar:Npx</code>

(End definition for `\cs_set_protected_nopar:cpn` and others. These functions are documented on page 12.)

<code>\cs_set_protected:cpn</code>	1889	<code>__cs_tmp:w \cs_set_protected:cpn \cs_set_protected:Npn</code>
<code>\cs_set_protected:cpx</code>	1890	<code>__cs_tmp:w \cs_set_protected:cpx \cs_set_protected:Npx</code>
<code>\cs_gset_protected:cpn</code>	1891	<code>__cs_tmp:w \cs_gset_protected:cpn \cs_gset_protected:Npn</code>
<code>\cs_gset_protected:cpx</code>	1892	<code>__cs_tmp:w \cs_gset_protected:cpx \cs_gset_protected:Npx</code>
<code>\cs_new_protected:cpn</code>	1893	<code>__cs_tmp:w \cs_new_protected:cpn \cs_new_protected:Npn</code>
<code>\cs_new_protected:cpx</code>	1894	<code>__cs_tmp:w \cs_new_protected:cpx \cs_new_protected:Npx</code>

(End definition for `\cs_set_protected:cpn` and others. These functions are documented on page 11.)

### 3.11 Copying definitions

`\cs_set_eq:NN` These macros allow us to copy the definition of a control sequence to another control sequence.

`\cs_set_eq:cN` The = sign allows us to define funny char tokens like = itself or `\_` with this function. For the definition of `\c_space_char{~}` to work we need the ~ after the =.

`\cs_set_eq:Nc` `\cs_set_eq:cc` `\cs_gset_eq:NN` `\cs_gset_eq:cN` `\cs_gset_eq:Nc` `\cs_gset_eq:cc` `\cs_new_eq:NN` `\cs_new_eq:cN` `\cs_new_eq:Nc` `\cs_new_eq:cc` `\cs_set_eq:NN` is long to avoid problems with a literal argument of `\par`. While `\cs_new_eq:NN` will probably never be correct with a first argument of `\par`, define it long in order to throw an “already defined” error rather than “runaway argument”.

<code>\cs_gset_eq:cc</code>	1895	<code>\cs_new_protected:Npn \cs_set_eq:NN #1 { \tex_let:D #1 =~ }</code>
<code>\cs_new_eq:NN</code>	1896	<code>\cs_new_protected:Npn \cs_set_eq:cN { \exp_args:Nc \cs_set_eq:NN }</code>
<code>\cs_new_eq:cN</code>	1897	<code>\cs_new_protected:Npn \cs_set_eq:Nc { \exp_args:NNc \cs_set_eq:NN }</code>
<code>\cs_new_eq:Nc</code>	1898	<code>\cs_new_protected:Npn \cs_set_eq:cc { \exp_args:Ncc \cs_set_eq:NN }</code>
<code>\cs_new_eq:cc</code>	1899	<code>\cs_new_protected:Npn \cs_gset_eq:NN { \tex_global:D \cs_set_eq:NN }</code>
	1900	<code>\cs_new_protected:Npn \cs_gset_eq:Nc { \exp_args:NNc \cs_gset_eq:NN }</code>
	1901	<code>\cs_new_protected:Npn \cs_gset_eq:cN { \exp_args:Nc \cs_gset_eq:NN }</code>
	1902	<code>\cs_new_protected:Npn \cs_gset_eq:cc { \exp_args:Ncc \cs_gset_eq:NN }</code>
	1903	<code>\cs_new_protected:Npn \cs_new_eq:NN #1</code>
	1904	<code>{</code>
	1905	<code>  \__chk_if_free_cs:N #1</code>
	1906	<code>  \tex_global:D \cs_set_eq:NN #1</code>
	1907	<code>}</code>
	1908	<code>\cs_new_protected:Npn \cs_new_eq:cN { \exp_args:Nc \cs_new_eq:NN }</code>
	1909	<code>\cs_new_protected:Npn \cs_new_eq:Nc { \exp_args:NNc \cs_new_eq:NN }</code>
	1910	<code>\cs_new_protected:Npn \cs_new_eq:cc { \exp_args:Ncc \cs_new_eq:NN }</code>

(End definition for `\cs_set_eq:NN`, `\cs_gset_eq:NN`, and `\cs_new_eq:NN`. These functions are documented on page 15.)



### 3.12 Undefined functions

`\cs_undefine:N` The following function is used to free the main memory from the definition of some function that isn't in use any longer. The `c` variant is careful not to add the control sequence to the hash table if it isn't there yet, and it also avoids nesting TeX conditionals in case `#1` is unbalanced in this matter.

```

1911 \cs_new_protected:Npn \cs_undefine:N #1
1912 { \cs_gset_eq:NN #1 \tex_undefined:D }
1913 \cs_new_protected:Npn \cs_undefine:c #1
1914 {
1915   \if_cs_exist:w #1 \cs_end:
1916     \exp_after:wN \use:n
1917   \else:
1918     \exp_after:wN \use_none:n
1919   \fi:
1920   { \cs_gset_eq:cN {#1} \tex_undefined:D }
1921 }

```

(End definition for `\cs_undefine:N`. This function is documented on page 15.)

### 3.13 Generating parameter text from argument count

`\__cs_parm_from_arg_count:nnF` LaTeX3 provides shorthands to define control sequences and conditionals with a simple parameter text, derived directly from the signature, or more generally from knowing the number of arguments, between 0 and 9. This function expands to its first argument, untouched, followed by a brace group containing the parameter text `{#1...#n}`, where  $n$  is the result of evaluating the second argument (as described in `\int_eval:n`). If the second argument gives a result outside the range  $[0, 9]$ , the third argument is returned instead, normally an error message. Some of the functions use here are not defined yet, but will be defined before this function is called.

```

1922 \cs_set_protected:Npn \__cs_parm_from_arg_count:nnF #1#2
1923 {
1924   \exp_args:Nx \__cs_parm_from_arg_count_test:nnF
1925   {
1926     \exp_after:wN \exp_not:n
1927     \if_case:w \__int_eval:w #2 \__int_eval_end:
1928       { }
1929       \or: { ##1 }
1930       \or: { ##1##2 }
1931       \or: { ##1##2##3 }
1932       \or: { ##1##2##3##4 }
1933       \or: { ##1##2##3##4##5 }
1934       \or: { ##1##2##3##4##5##6 }
1935       \or: { ##1##2##3##4##5##6##7 }
1936       \or: { ##1##2##3##4##5##6##7##8 }
1937       \or: { ##1##2##3##4##5##6##7##8##9 }
1938       \else: { \c_false_bool }
1939     \fi:
1940   }
1941   {#1}
1942 }
1943 \cs_set_protected:Npn \__cs_parm_from_arg_count_test:nnF #1#2
1944 {

```

```

1945 \if_meaning:w \c_false_bool #1
1946 \exp_after:wN \use_ii:nn
1947 \else:
1948 \exp_after:wN \use_i:nn
1949 \fi:
1950 { #2 {#1} }
1951 }

```

(End definition for `\_cs_parm_from_arg_count:nnF` and `\_cs_parm_from_arg_count_test:nnF`.)

### 3.14 Defining functions from a given number of arguments

`\_cs_count_signature:N` Counting the number of tokens in the signature, *i.e.*, the number of arguments the function should take. Since this is not used in any time-critical function, we simply use `\tl_count:n` if there is a signature, otherwise `-1` arguments to signal an error. We need a variant form right away.

```

1952 \cs_new:Npn \_cs_count_signature:N #1
1953 { \int_eval:n { \_cs_split_function:NN #1 \_cs_count_signature:nnN } }
1954 \cs_new:Npn \_cs_count_signature:nnN #1#2#3
1955 {
1956 \if_meaning:w \c_true_bool #3
1957 \tl_count:n {#2}
1958 \else:
1959 -1
1960 \fi:
1961 }
1962 \cs_new:Npn \_cs_count_signature:c
1963 { \exp_args:Nc \_cs_count_signature:N }

```

(End definition for `\_cs_count_signature:N` and `\_cs_count_signature:nnN`.)

`\cs_generate_from_arg_count:NNnn` We provide a constructor function for defining functions with a given number of arguments. For this we need to choose the correct parameter text and then use that when defining. Since  $\text{\TeX}$  supports from zero to nine arguments, we use a simple switch to choose the correct parameter text, ensuring the result is returned after finishing the conditional. If it is not between zero and nine, we throw an error.

1: function to define, 2: with what to define it, 3: the number of args it requires and 4: the replacement text

```

1964 \cs_new_protected:Npn \cs_generate_from_arg_count:NNnn #1#2#3#4
1965 {
1966 \_cs_parm_from_arg_count:nnF { \use:nnn #2 #1 } {#3}
1967 {
1968 \_msg_kernel_error:nnxx { kernel } { bad-number-of-arguments }
1969 { \token_to_str:N #1 } { \int_eval:n {#3} }
1970 \use_none:n
1971 }
1972 {#4}
1973 }

```

A variant form we need right away, plus one which is used elsewhere but which is most logically created here.

```

1974 \cs_new_protected:Npn \cs_generate_from_arg_count:cNnn
1975 { \exp_args:Nc \cs_generate_from_arg_count:NNnn }
1976 \cs_new_protected:Npn \cs_generate_from_arg_count:Ncnn

```

```
1977 { \exp_args:Nnc \cs_generate_from_arg_count:NNnn }
```

(End definition for `\cs_generate_from_arg_count:NNnn`. This function is documented on page 14.)

### 3.15 Using the signature to define functions

We can now combine some of the tools we have to provide a simple interface for defining functions, where the number of arguments is read from the signature. For instance, `\cs_set:Nn \foo_bar:nn {#1,#2}`.

`\cs_set:Nn` We want to define `\cs_set:Nn` as

```
\cs_set:Nx
\cs_set_nopar:Nn
\cs_set_nopar:Nx
\cs_set_protected:Nn
\cs_set_protected:Nx
\cs_set_protected_nopar:Nn
\cs_set_protected_nopar:Nx
\cs_gset:Nn
\cs_gset:Nx
\cs_gset_nopar:Nn
\cs_gset_nopar:Nx
\cs_gset_protected:Nn
\cs_gset_protected:Nx
\cs_gset_protected_nopar:Nn
\cs_gset_protected_nopar:Nx
\cs_new:Nn
\cs_new:Nx
\cs_new_nopar:Nn
\cs_new_nopar:Nx
\cs_new_protected:Nn
\cs_new_protected:Nx
\cs_new_protected_nopar:Nn
\cs_new_protected_nopar:Nx
```

```
\cs_set_protected:Npn \cs_set:Nn #1#2
{
  \cs_generate_from_arg_count:NNnn #1 \cs_set:Npn
  { \__cs_count_signature:N #1 } {#2}
}
```

In short, to define `\cs_set:Nn` we need just use `\cs_set:Npn`, everything else is the same for each variant. Therefore, we can make it simpler by temporarily defining a function to do this for us.

```
1978 \cs_set:Npn \__cs_tmp:w #1#2#3
1979 {
1980   \cs_new_protected:cpx { cs_ #1 : #2 }
1981   {
1982     \exp_not:N \__cs_generate_from_signature:NNn
1983     \exp_after:wN \exp_not:N \cs:w cs_ #1 : #3 \cs_end:
1984   }
1985 }
1986 \cs_new_protected:Npn \__cs_generate_from_signature:NNn #1#2
1987 {
1988   \__cs_split_function:NN #2 \__cs_generate_from_signature:nnNNNn
1989   #1 #2
1990 }
1991 \cs_new_protected:Npn \__cs_generate_from_signature:nnNNNn #1#2#3#4#5#6
1992 {
1993   \bool_if:NTF #3
1994   {
1995     \str_if_eq_x:nnF { }
1996     { \tl_map_function:nN {#2} \__cs_generate_from_signature:n }
1997     {
1998       \__msg_kernel_error:nnx { kernel } { non-base-function }
1999       { \token_to_str:N #5 }
2000     }
2001     \cs_generate_from_arg_count:NNnn
2002     #5 #4 { \tl_count:n {#2} } {#6}
2003   }
2004   {
2005     \__msg_kernel_error:nnx { kernel } { missing-colon }
2006     { \token_to_str:N #5 }
2007   }
2008 }
2009 \cs_new:Npn \__cs_generate_from_signature:n #1
2010 {
```

```

2011     \if:w n #1 \else: \if:w N #1 \else:
2012     \if:w T #1 \else: \if:w F #1 \else: #1 \fi: \fi: \fi: \fi:
2013 }

```

Then we define the 24 variants beginning with N.

```

2014 \__cs_tmp:w { set } { Nn } { Npn }
2015 \__cs_tmp:w { set } { Nx } { Npx }
2016 \__cs_tmp:w { set_nopar } { Nn } { Npn }
2017 \__cs_tmp:w { set_nopar } { Nx } { Npx }
2018 \__cs_tmp:w { set_protected } { Nn } { Npn }
2019 \__cs_tmp:w { set_protected } { Nx } { Npx }
2020 \__cs_tmp:w { set_protected_nopar } { Nn } { Npn }
2021 \__cs_tmp:w { set_protected_nopar } { Nx } { Npx }
2022 \__cs_tmp:w { gset } { Nn } { Npn }
2023 \__cs_tmp:w { gset } { Nx } { Npx }
2024 \__cs_tmp:w { gset_nopar } { Nn } { Npn }
2025 \__cs_tmp:w { gset_nopar } { Nx } { Npx }
2026 \__cs_tmp:w { gset_protected } { Nn } { Npn }
2027 \__cs_tmp:w { gset_protected } { Nx } { Npx }
2028 \__cs_tmp:w { gset_protected_nopar } { Nn } { Npn }
2029 \__cs_tmp:w { gset_protected_nopar } { Nx } { Npx }
2030 \__cs_tmp:w { new } { Nn } { Npn }
2031 \__cs_tmp:w { new } { Nx } { Npx }
2032 \__cs_tmp:w { new_nopar } { Nn } { Npn }
2033 \__cs_tmp:w { new_nopar } { Nx } { Npx }
2034 \__cs_tmp:w { new_protected } { Nn } { Npn }
2035 \__cs_tmp:w { new_protected } { Nx } { Npx }
2036 \__cs_tmp:w { new_protected_nopar } { Nn } { Npn }
2037 \__cs_tmp:w { new_protected_nopar } { Nx } { Npx }

```

(End definition for \cs\_set:Nn and others. These functions are documented on page 13.)

\cs\_set:cn The 24 c variants simply use \exp\_args:Nc.

```

\cs_set:cx
\cs_set_nopar:cn
\cs_set_nopar:cx
\cs_set_protected:cn
\cs_set_protected:cx
\cs_set_protected_nopar:cn
\cs_set_protected_nopar:cx
\cs_gset:cn
\cs_gset:cx
\cs_gset_nopar:cn
\cs_gset_nopar:cx
\cs_gset_protected:cn
\cs_gset_protected:cx
\cs_gset_protected_nopar:cn
\cs_gset_protected_nopar:cx
\cs_new:cn
\cs_new:cx
\cs_new_nopar:cn
\cs_new_nopar:cx
\cs_new_protected:cn
\cs_new_protected:cx
\cs_new_protected_nopar:cn
\cs_new_protected_nopar:cx

```

```

2038 \cs_set:Npn \__cs_tmp:w #1#2
2039 {
2040   \cs_new_protected:cpx { cs_ #1 : c #2 }
2041   {
2042     \exp_not:N \exp_args:Nc
2043     \exp_after:wN \exp_not:N \cs:w cs_ #1 : N #2 \cs_end:
2044   }
2045 }
2046 \__cs_tmp:w { set } { n }
2047 \__cs_tmp:w { set } { x }
2048 \__cs_tmp:w { set_nopar } { n }
2049 \__cs_tmp:w { set_nopar } { x }
2050 \__cs_tmp:w { set_protected } { n }
2051 \__cs_tmp:w { set_protected } { x }
2052 \__cs_tmp:w { set_protected_nopar } { n }
2053 \__cs_tmp:w { set_protected_nopar } { x }
2054 \__cs_tmp:w { gset } { n }
2055 \__cs_tmp:w { gset } { x }
2056 \__cs_tmp:w { gset_nopar } { n }
2057 \__cs_tmp:w { gset_nopar } { x }
2058 \__cs_tmp:w { gset_protected } { n }
2059 \__cs_tmp:w { gset_protected } { x }

```

```

2060 \__cs_tmp:w { gset_protected_nopar } { n }
2061 \__cs_tmp:w { gset_protected_nopar } { x }
2062 \__cs_tmp:w { new } { n }
2063 \__cs_tmp:w { new } { x }
2064 \__cs_tmp:w { new_nopar } { n }
2065 \__cs_tmp:w { new_nopar } { x }
2066 \__cs_tmp:w { new_protected } { n }
2067 \__cs_tmp:w { new_protected } { x }
2068 \__cs_tmp:w { new_protected_nopar } { n }
2069 \__cs_tmp:w { new_protected_nopar } { x }

```

(End definition for `\cs_set:cn` and others. These functions are documented on page 13.)

### 3.16 Checking control sequence equality

```

\cs_if_eq_p:NN Check if two control sequences are identical.
\cs_if_eq_p:cN 2070 \prg_new_conditional:Npnn \cs_if_eq:NN #1#2 { p , T , F , TF }
\cs_if_eq_p:Nc 2071 {
\cs_if_eq_p:cc 2072   \if_meaning:w #1#2
\cs_if_eq:NNTF 2073   \prg_return_true: \else: \prg_return_false: \fi:
\cs_if_eq:cNTF 2074 }
\cs_if_eq:NcTF 2075 \cs_new:Npn \cs_if_eq_p:cN { \exp_args:Nc \cs_if_eq_p:NN }
\cs_if_eq:ccTF 2076 \cs_new:Npn \cs_if_eq:cNTF { \exp_args:Nc \cs_if_eq:NNTF }
2077 \cs_new:Npn \cs_if_eq:cNT { \exp_args:Nc \cs_if_eq:NNT }
2078 \cs_new:Npn \cs_if_eq:cNF { \exp_args:Nc \cs_if_eq:NNF }
2079 \cs_new:Npn \cs_if_eq_p:Nc { \exp_args:NNc \cs_if_eq_p:NN }
2080 \cs_new:Npn \cs_if_eq:NcTF { \exp_args:NNc \cs_if_eq:NNTF }
2081 \cs_new:Npn \cs_if_eq:NcT { \exp_args:NNc \cs_if_eq:NNT }
2082 \cs_new:Npn \cs_if_eq:NcF { \exp_args:NNc \cs_if_eq:NNF }
2083 \cs_new:Npn \cs_if_eq_p:cc { \exp_args:Ncc \cs_if_eq_p:NN }
2084 \cs_new:Npn \cs_if_eq:ccTF { \exp_args:Ncc \cs_if_eq:NNTF }
2085 \cs_new:Npn \cs_if_eq:ccT { \exp_args:Ncc \cs_if_eq:NNT }
2086 \cs_new:Npn \cs_if_eq:ccF { \exp_args:Ncc \cs_if_eq:NNF }

```

(End definition for `\cs_if_eq:NNTF`. This function is documented on page 20.)

### 3.17 Diagnostic functions

`\__kernel_register_show:N` Simply using the `\showthe` primitive does not allow for line-wrapping, so instead use `\__msg_show_variable:NNNnn` (defined in `l3msg`). This checks that the variable exists (using `\cs_if_exist:NTF`), then displays the third argument, namely `>~⟨variable⟩=⟨value⟩`. We expand the value before-hand as otherwise some integers (such as `\currentgrouplevel` or `\currentgrouptype`) altered by the line-wrapping code would show wrong values.

```

2087 \cs_new_protected:Npn \__kernel_register_show:N #1
2088 { \exp_args:No \__kernel_register_show_aux:nN { \tex_the:D #1 } #1 }
2089 \cs_new_protected:Npn \__kernel_register_show_aux:nN #1#2
2090 {
2091   \__msg_show_variable:NNNnn #2 \cs_if_exist:NTF ? { }
2092   { > ~ \token_to_str:N #2 = #1 }
2093 }
2094 \cs_new_protected:Npn \__kernel_register_show:c
2095 { \exp_args:Nc \__kernel_register_show:N }

```

(End definition for `\__kernel_register_show:N` and `\__kernel_register_show_aux:n`.)

`\__kernel_register_log:N` Redirect the output of `\__kernel_register_show:N` to the log.

```
\__kernel_register_log:c
2096 \cs_new_protected:Npn \__kernel_register_log:N
2097 { \__msg_log_next: \__kernel_register_show:N }
2098 \cs_new_protected:Npn \__kernel_register_log:c
2099 { \exp_args:Nc \__kernel_register_log:N }
```

*(End definition for \\_\_kernel\_register\_log:N.)*

`\cs_show:N` Some control sequences have a very long name or meaning. Thus, simply using TeX's primitive `\show` could lead to overlong lines. The output of this primitive is mimicked to some extent, then the re-built string is given to `\iow_wrap:nnnN` for line-wrapping. We must expand the meaning before passing it to the wrapping code as otherwise we would wrongly see the definitions that are in place there. To get correct escape characters, set the `\escapechar` in a group; this also localizes the assignment performed by x-expansion. The `\cs_show:c` command also converts its argument to a control sequence within a group to avoid showing `\relax` for undefined control sequences.

```
2100 \cs_new_protected:Npn \cs_show:N #1
2101 {
2102   \group_begin:
2103     \int_set:Nn \tex_escapechar:D { '\ }
2104     \exp_args:NNx
2105     \group_end:
2106     \__msg_show_wrap:n { > ~ \token_to_str:N #1 = \cs_meaning:N #1 }
2107 }
2108 \cs_new_protected:Npn \cs_show:c
2109 { \group_begin: \exp_args:NNc \group_end: \cs_show:N }
```

*(End definition for \cs\_show:N. This function is documented on page 16.)*

`\cs_log:N` Use `\cs_show:N` or `\cs_show:c` after calling `\__msg_log_next:` to redirect their output to the log file only. Note that `\cs_log:c` is not just a variant of `\cs_log:N` as the csname should be turned to a control sequence within a group (see `\cs_show:c`).

```
2110 \cs_new_protected:Npn \cs_log:N { \__msg_log_next: \cs_show:N }
2111 \cs_new_protected:Npn \cs_log:c { \__msg_log_next: \cs_show:c }
```

*(End definition for \cs\_log:N. This function is documented on page 16.)*

### 3.18 Doing nothing functions

`\prg_do_nothing:` This does not fit anywhere else!

```
2112 \cs_new_nopar:Npn \prg_do_nothing: { }
```

*(End definition for \prg\_do\_nothing:. This function is documented on page 9.)*

### 3.19 Breaking out of mapping functions

`\__prg_break_point:Nn` In inline mappings, the nesting level must be reset at the end of the mapping, even when the user decides to break out. This is done by putting the code that must be performed as an argument of `\__prg_break_point:Nn`. The breaking functions are then defined to jump to that point and perform the argument of `\__prg_break_point:Nn`, before the user's code (if any). There is a check that we close the correct loop, otherwise we continue breaking.

```
2113 \cs_new_eq:NN \__prg_break_point:Nn \use_ii:nn
```

```

2114 \cs_new:Npn \__prg_map_break:Nn #1#2#3 \__prg_break_point:Nn #4#5
2115 {
2116     #5
2117     \if_meaning:w #1 #4
2118     \exp_after:wN \use_iii:nnn
2119     \fi:
2120     \__prg_map_break:Nn #1 {#2}
2121 }

```

(End definition for `\__prg_break_point:Nn` and `\__prg_map_break:Nn`.)

`\__prg_break_point:` Very simple analogues of `\__prg_break_point:Nn` and `\__prg_map_break:Nn`, for use  
`\__prg_break:` in fast short-term recursions which are not mappings, do not need to support nesting,  
`\__prg_break:n` and in which nothing has to be done at the end of the loop.

```

2122 \cs_new_eq:NN \__prg_break_point: \prg_do_nothing:
2123 \cs_new:Npn \__prg_break: #1 \__prg_break_point: { }
2124 \cs_new:Npn \__prg_break:n #1#2 \__prg_break_point: {#1}

```

(End definition for `\__prg_break_point:`, `\__prg_break:`, and `\__prg_break:n`.)

```

2125 </initex | package>

```

## 4 l3expan implementation

```

2126 <*initex | package>

```

```

2127 <@@=exp>

```

`\exp_after:wN` These are defined in `l3basics`.

`\exp_not:N`

`\exp_not:n`

(End definition for `\exp_after:wN`, `\exp_not:N`, and `\exp_not:n`. These functions are documented on page 30.)

### 4.1 General expansion

In this section a general mechanism for defining functions to handle argument handling is defined. These general expansion functions are expandable unless `x` is used. (Any version of `x` is going to have to use one of the L<sup>A</sup>T<sub>E</sub>X3 names for `\cs_set:Npx` at some point, and so is never going to be expandable.)

The definition of expansion functions with this technique happens in section 4.3. In section 4.2 some common cases are coded by a more direct method for efficiency, typically using calls to `\exp_after:wN`.

`\l__exp_internal_tl` This scratch token list variable is defined in `l3basics`, as it is needed “early”. This is just a reminder that is the case!

(End definition for `\l__exp_internal_tl`.)

This code uses internal functions with names that start with `\::` to perform the expansions. All macros are long as this turned out to be desirable since the tokens undergoing expansion may be arbitrary user input.

An argument manipulator `\::⟨Z⟩` always has signature `#1\:::#2#3` where `#1` holds the remaining argument manipulations to be performed, `\::` serves as an end marker for the list of manipulations, `#2` is the carried over result of the previous expansion steps and `#3` is the argument about to be processed. One exception to this rule is `\::p`, which has to grab an argument delimited by a left brace.

`\_exp_arg_next:nnn` #1 is the result of an expansion step, #2 is the remaining argument manipulations and  
`\_exp_arg_next:Nnn` #3 is the current result of the expansion chain. This auxiliary function moves #1 back  
after #3 in the input stream and checks if any expansion is left to be done by calling  
#2. In by far the most cases we need to add a set of braces to the result of an argument  
manipulation so it is more effective to do it directly here. Actually, so far only the `c` of  
the final argument manipulation variants does not require a set of braces.

```
2128 \cs_new:Npn \_exp_arg_next:nnn #1#2#3 { #2 \::: { #3 {#1} } }
2129 \cs_new:Npn \_exp_arg_next:Nnn #1#2#3 { #2 \::: { #3 #1 } }
```

(End definition for `\_exp_arg_next:nnn` and `\_exp_arg_next:Nnn`.)

**`\:::`** The end marker is just another name for the identity function.

```
2130 \cs_new:Npn \::: #1 {#1}
```

(End definition for `\:::`.)

**`\::n`** This function is used to skip an argument that doesn't need to be expanded.

```
2131 \cs_new:Npn \::n #1 \::: #2#3 { #1 \::: { #2 {#3} } }
```

(End definition for `\::n`.)

**`\::N`** This function is used to skip an argument that consists of a single token and doesn't need  
to be expanded.

```
2132 \cs_new:Npn \::N #1 \::: #2#3 { #1 \::: {#2#3} }
```

(End definition for `\::N`.)

**`\::p`** This function is used to skip an argument that is delimited by a left brace and doesn't  
need to be expanded. It should not be wrapped in braces in the result.

```
2133 \cs_new:Npn \::p #1 \::: #2#3# { #1 \::: {#2#3} }
```

(End definition for `\::p`.)

**`\::c`** This function is used to skip an argument that is turned into a control sequence without  
expansion.

```
2134 \cs_new:Npn \::c #1 \::: #2#3
2135 { \exp_after:wN \_exp_arg_next:Nnn \cs:w #3 \cs_end: {#1} {#2} }
```

(End definition for `\::c`.)

**`\::o`** This function is used to expand an argument once.

```
2136 \cs_new:Npn \::o #1 \::: #2#3
2137 { \exp_after:wN \_exp_arg_next:nnn \exp_after:wN {#3} {#1} {#2} }
```

(End definition for `\::o`.)

**`\::f`** This function is used to expand a token list until the first unexpandable token is  
**`\exp_stop_f:`** found. This is achieved through `\exp:w \exp_end_continue_f:w` that expands ev-  
erything in its way following it. This scanning procedure is terminated once the ex-  
pansion hits something non-expandable or a space. We introduce `\exp_stop_f:`  
to mark such an end of expansion marker. In the example shown earlier the scanning was  
stopped once `TEX` had fully expanded `\cs_set_eq:Nc \aaa { b \l_tmpa_tl b }` into  
`\cs_set_eq:NN \aaa = \blurb` which then turned out to contain the non-expandable  
token `\cs_set_eq:NN`. Since the expansion of `\exp:w \exp_end_continue_f:w` is  $\langle null \rangle$ ,



we wind up with a fully expanded list, only  $\TeX$  has not tried to execute any of the non-expandable tokens. This is what differentiates this function from the `x` argument type.

```

2138 \cs_new:Npn \::f #1 \::: #2#3
2139 {
2140   \exp_after:wN \__exp_arg_next:nnn
2141   \exp_after:wN { \exp:w \exp_end_continue_f:w #3 }
2142   {#1} {#2}
2143 }
2144 \use:nn { \cs_new_eq:NN \exp_stop_f: } { ~ }
```

(End definition for `\::f` and `\exp_stop_f:`.)

**`\::x`** This function is used to expand an argument fully.

```

2145 \cs_new_protected:Npn \::x #1 \::: #2#3
2146 {
2147   \cs_set_nopar:Npx \l__exp_internal_tl { {#3} }
2148   \exp_after:wN \__exp_arg_next:nnn \l__exp_internal_tl {#1} {#2}
2149 }
```

(End definition for `\::x`.)

**`\::v`** These functions return the value of a register, i.e., one of `tl`, `clist`, `int`, `skip`, `dim` and **`\::V`** `muskip`. The `V` version expects a single token whereas `v` like `c` creates a `csname` from its argument given in braces and then evaluates it as if it was a `V`. The `\exp:w` sets off an expansion similar to an `f`-type expansion, which we terminate using `\exp_end:`. The argument is returned in braces.

```

2150 \cs_new:Npn \::V #1 \::: #2#3
2151 {
2152   \exp_after:wN \__exp_arg_next:nnn
2153   \exp_after:wN { \exp:w \__exp_eval_register:N #3 }
2154   {#1} {#2}
2155 }
2156 \cs_new:Npn \::v # 1\::: #2#3
2157 {
2158   \exp_after:wN \__exp_arg_next:nnn
2159   \exp_after:wN { \exp:w \__exp_eval_register:c {#3} }
2160   {#1} {#2}
2161 }
```

(End definition for `\::v` and `\::V`.)

**`\__exp_eval_register:N`** This function evaluates a register. Now a register might exist as one of two things: A parameter-less macro or a built-in  $\TeX$  register such as `\count`. For the  $\TeX$  registers we have to utilize a `\the` whereas for the macros we merely have to expand them once. The trick is to find out when to use `\the` and when not to. What we want here is to find out whether the token expands to something else when hit with `\exp_after:wN`. The technique is to compare the meaning of the token in question when it has been prefixed with `\exp_not:N` and the token itself. If it is a macro, the prefixed `\exp_not:N` temporarily turns it into the primitive `\scan_stop:`.

```

2162 \cs_new:Npn \__exp_eval_register:N #1
2163 {
2164   \exp_after:wN \if_meaning:w \exp_not:N #1 #1
```

If the token was not a macro it may be a malformed variable from a `c` expansion in which case it is equal to the primitive `\scan_stop:`. In that case we throw an error. We could let `TeX` do it for us but that would result in the rather obscure

```
! You can't use '\relax' after \the.
```

which while quite true doesn't give many hints as to what actually went wrong. We provide something more sensible.

```
2165     \if_meaning:w \scan_stop: #1
2166     \__exp_eval_error_msg:w
2167     \fi:
```

The next bit requires some explanation. The function must be initiated by `\exp:w` and we want to terminate this expansion chain by inserting the `\exp_end:` token. However, we have to expand the register `#1` before we do that. If it is a `TeX` register, we need to execute the sequence `\exp_after:wN \exp_end: \tex_the:D #1` and if it is a macro we need to execute `\exp_after:wN \exp_end: #1`. We therefore issue the longer of the two sequences and if the register is a macro, we remove the `\tex_the:D`.

```
2168     \else:
2169     \exp_after:wN \use_i_ii:nnn
2170     \fi:
2171     \exp_after:wN \exp_end: \tex_the:D #1
2172   }
2173 \cs_new:Npn \__exp_eval_register:c #1
2174 { \exp_after:wN \__exp_eval_register:N \cs:w #1 \cs_end: }
```

Clean up nicely, then call the undefined control sequence. The result is an error message looking like this:

```
! Undefined control sequence.
<argument> \LaTeX3 error:
                               Erroneous variable used!
1.55 \tl_set:Nv \l_tmpa_tl {undefined_tl}

2175 \cs_new:Npn \__exp_eval_error_msg:w #1 \tex_the:D #2
2176 {
2177     \fi:
2178     \fi:
2179     \__msg_kernel_expandable_error:nnn { kernel } { bad-variable } {#2}
2180     \exp_end:
2181 }
```

*(End definition for `\__exp_eval_register:N` and `\__exp_eval_error_msg:w`.)*

## 4.2 Hand-tuned definitions

One of the most important features of these functions is that they are fully expandable and therefore allow to prefix them with `\tex_global:D` for example.

```
\exp_args:No Those lovely runs of expansion!
\exp_args:NNo
\exp_args:NNNo
2182 \cs_new:Npn \exp_args:No #1#2 { \exp_after:wN #1 \exp_after:wN {#2} }
2183 \cs_new:Npn \exp_args:NNo #1#2#3
2184 { \exp_after:wN #1 \exp_after:wN #2 \exp_after:wN {#3} }
2185 \cs_new:Npn \exp_args:NNNo #1#2#3#4
2186 { \exp_after:wN #1 \exp_after:wN#2 \exp_after:wN #3 \exp_after:wN {#4} }
```

(End definition for `\exp_args:No`, `\exp_args:NNo`, and `\exp_args:NNNo`. These functions are documented on page 27.)

`\exp_args:Nc` In l3basics.

`\exp_args:cc`

(End definition for `\exp_args:Nc` and `\exp_args:cc`. These functions are documented on page 27.)

`\exp_args:NNc`

`\exp_args:Ncc`

`\exp_args:Nccc`

Here are the functions that turn their argument into csnames but are expandable.

```
2187 \cs_new:Npn \exp_args:NNc #1#2#3
2188 { \exp_after:wN #1 \exp_after:wN #2 \cs:w # 3\cs_end: }
2189 \cs_new:Npn \exp_args:Ncc #1#2#3
2190 { \exp_after:wN #1 \cs:w #2 \exp_after:wN \cs_end: \cs:w #3 \cs_end: }
2191 \cs_new:Npn \exp_args:Nccc #1#2#3#4
2192 {
2193   \exp_after:wN #1
2194   \cs:w #2 \exp_after:wN \cs_end:
2195   \cs:w #3 \exp_after:wN \cs_end:
2196   \cs:w #4 \cs_end:
2197 }
```

(End definition for `\exp_args:NNc`, `\exp_args:Ncc`, and `\exp_args:Nccc`. These functions are documented on page 28.)

`\exp_args:Nf`

`\exp_args:Nv`

`\exp_args:Nv`

```
2198 \cs_new:Npn \exp_args:Nf #1#2
2199 { \exp_after:wN #1 \exp_after:wN { \exp:w \exp_end_continue_f:w #2 } }
2200 \cs_new:Npn \exp_args:Nv #1#2
2201 {
2202   \exp_after:wN #1 \exp_after:wN
2203   { \exp:w \__exp_eval_register:c {#2} }
2204 }
2205 \cs_new:Npn \exp_args:Nv #1#2
2206 {
2207   \exp_after:wN #1 \exp_after:wN
2208   { \exp:w \__exp_eval_register:N #2 }
2209 }
```

(End definition for `\exp_args:Nf`, `\exp_args:Nv`, and `\exp_args:Nv`. These functions are documented on page 27.)

`\exp_args:NNV`

`\exp_args:NNv`

`\exp_args:NNf`

`\exp_args:NNV`

`\exp_args:Ncf`

`\exp_args:Nco`

Some more hand-tuned function with three arguments. If we forced that an `o` argument always has braces, we could implement `\exp_args:Nco` with less tokens and only two arguments.

```
2210 \cs_new:Npn \exp_args:NNf #1#2#3
2211 {
2212   \exp_after:wN #1
2213   \exp_after:wN #2
2214   \exp_after:wN { \exp:w \exp_end_continue_f:w #3 }
2215 }
2216 \cs_new:Npn \exp_args:NNv #1#2#3
2217 {
2218   \exp_after:wN #1
2219   \exp_after:wN #2
2220   \exp_after:wN { \exp:w \__exp_eval_register:c {#3} }
2221 }
```

```

2222 \cs_new:Npn \exp_args:NNV #1#2#3
2223 {
2224     \exp_after:wN #1
2225     \exp_after:wN #2
2226     \exp_after:wN { \exp:w \__exp_eval_register:N #3 }
2227 }
2228 \cs_new:Npn \exp_args:Nco #1#2#3
2229 {
2230     \exp_after:wN #1
2231     \cs:w #2 \exp_after:wN \cs_end:
2232     \exp_after:wN {#3}
2233 }
2234 \cs_new:Npn \exp_args:Ncf #1#2#3
2235 {
2236     \exp_after:wN #1
2237     \cs:w #2 \exp_after:wN \cs_end:
2238     \exp_after:wN { \exp:w \exp_end_continue_f:w #3 }
2239 }
2240 \cs_new:Npn \exp_args:NVV #1#2#3
2241 {
2242     \exp_after:wN #1
2243     \exp_after:wN { \exp:w \exp_after:wN
2244         \__exp_eval_register:N \exp_after:wN #2 \exp_after:wN }
2245     \exp_after:wN { \exp:w \__exp_eval_register:N #3 }
2246 }

```

(End definition for `\exp_args:NNV` and others. These functions are documented on page 28.)

`\exp_args:Ncco` A few more that we can hand-tune.

```

\exp_args:NcNc 2247 \cs_new:Npn \exp_args:NNNV #1#2#3#4
\exp_args:NcNo 2248 {
\exp_args:NNNV 2249     \exp_after:wN #1
2250     \exp_after:wN #2
2251     \exp_after:wN #3
2252     \exp_after:wN { \exp:w \__exp_eval_register:N #4 }
2253 }
2254 \cs_new:Npn \exp_args:NcNc #1#2#3#4
2255 {
2256     \exp_after:wN #1
2257     \cs:w #2 \exp_after:wN \cs_end:
2258     \exp_after:wN #3
2259     \cs:w #4 \cs_end:
2260 }
2261 \cs_new:Npn \exp_args:NcNo #1#2#3#4
2262 {
2263     \exp_after:wN #1
2264     \cs:w #2 \exp_after:wN \cs_end:
2265     \exp_after:wN #3
2266     \exp_after:wN {#4}
2267 }
2268 \cs_new:Npn \exp_args:Ncco #1#2#3#4
2269 {
2270     \exp_after:wN #1
2271     \cs:w #2 \exp_after:wN \cs_end:

```

```

2272     \cs:w #3 \exp_after:wN \cs_end:
2273     \exp_after:wN {#4}
2274   }

```

(End definition for `\exp_args:Ncco` and others. These functions are documented on page 28.)

### 4.3 Definitions with the automated technique

Some of these could be done more efficiently, but the complexity of coding then becomes an issue. Notice that the auto-generated functions are all not long: they don't actually take any arguments themselves.

`\exp_args:Nx`

```

2275 \cs_new_protected:Npn \exp_args:Nx { \::x \:: }

```

(End definition for `\exp_args:Nx`. This function is documented on page 27.)

`\exp_args:Nnc` Here are the actual function definitions, using the helper functions above.

```

\exp_args:Nnc 2276 \cs_new:Npn \exp_args:Nnc { \::n \::c \:: }
\exp_args:Nfo 2277 \cs_new:Npn \exp_args:Nfo { \::f \::o \:: }
\exp_args:Nff 2278 \cs_new:Npn \exp_args:Nff { \::f \::f \:: }
\exp_args:Nnf 2279 \cs_new:Npn \exp_args:Nnf { \::n \::f \:: }
\exp_args:Nno 2280 \cs_new:Npn \exp_args:Nno { \::n \::o \:: }
\exp_args:NnV 2281 \cs_new:Npn \exp_args:NnV { \::n \::V \:: }
\exp_args:Noo 2282 \cs_new:Npn \exp_args:Noo { \::o \::o \:: }
\exp_args:Nof 2283 \cs_new:Npn \exp_args:Nof { \::o \::f \:: }
\exp_args:Noc 2284 \cs_new:Npn \exp_args:Noc { \::o \::c \:: }
\exp_args:NNx 2285 \cs_new_protected:Npn \exp_args:NNx { \::N \::x \:: }
\exp_args:Ncx 2286 \cs_new_protected:Npn \exp_args:Ncx { \::c \::x \:: }
\exp_args:Nnx 2287 \cs_new_protected:Npn \exp_args:Nnx { \::n \::x \:: }
\exp_args:Nox 2288 \cs_new_protected:Npn \exp_args:Nox { \::o \::x \:: }
\exp_args:Nxo 2289 \cs_new_protected:Npn \exp_args:Nxo { \::x \::o \:: }
\exp_args:Nxx 2290 \cs_new_protected:Npn \exp_args:Nxx { \::x \::x \:: }

```

(End definition for `\exp_args:Nnc` and others. These functions are documented on page 28.)

`\exp_args:NNno`

```

\exp_args:NNno 2291 \cs_new:Npn \exp_args:NNno { \::N \::n \::o \:: }
\exp_args:NNoo 2292 \cs_new:Npn \exp_args:NNoo { \::N \::o \::o \:: }
\exp_args:NNnc 2293 \cs_new:Npn \exp_args:NNnc { \::n \::n \::c \:: }
\exp_args:NNno 2294 \cs_new:Npn \exp_args:NNno { \::n \::n \::o \:: }
\exp_args:NNNx 2295 \cs_new:Npn \exp_args:NNNx { \::o \::o \::o \:: }
\exp_args:NNnx 2296 \cs_new_protected:Npn \exp_args:NNnx { \::N \::N \::x \:: }
\exp_args:NNox 2297 \cs_new_protected:Npn \exp_args:NNox { \::N \::n \::x \:: }
\exp_args:NNnx 2298 \cs_new_protected:Npn \exp_args:NNnx { \::N \::o \::x \:: }
\exp_args:NNox 2299 \cs_new_protected:Npn \exp_args:NNox { \::n \::n \::x \:: }
\exp_args:NNox 2300 \cs_new_protected:Npn \exp_args:NNox { \::n \::o \::x \:: }
\exp_args:Nccx 2301 \cs_new_protected:Npn \exp_args:Nccx { \::c \::c \::x \:: }
\exp_args:Ncnx 2302 \cs_new_protected:Npn \exp_args:Ncnx { \::c \::n \::x \:: }
\exp_args:Noox 2303 \cs_new_protected:Npn \exp_args:Noox { \::o \::o \::x \:: }

```

(End definition for `\exp_args:NNno` and others. These functions are documented on page 28.)

## 4.4 Last-unbraced versions

There are a few places where the last argument needs to be available unbraced. First some helper macros.

```

\__exp_arg_last_unbraced:nn
\::f_unbraced
\::o_unbraced
\::V_unbraced
\::v_unbraced
\::x_unbraced
2304 \cs_new:Npn \__exp_arg_last_unbraced:nn #1#2 { #2#1 }
2305 \cs_new:Npn \::f_unbraced \::: #1#2
2306 {
2307   \exp_after:wN \__exp_arg_last_unbraced:nn
2308   \exp_after:wN { \exp:w \exp_end_continue_f:w #2 } {#1}
2309 }
2310 \cs_new:Npn \::o_unbraced \::: #1#2
2311 { \exp_after:wN \__exp_arg_last_unbraced:nn \exp_after:wN {#2} {#1} }
2312 \cs_new:Npn \::V_unbraced \::: #1#2
2313 {
2314   \exp_after:wN \__exp_arg_last_unbraced:nn
2315   \exp_after:wN { \exp:w \__exp_eval_register:N #2 } {#1}
2316 }
2317 \cs_new:Npn \::v_unbraced \::: #1#2
2318 {
2319   \exp_after:wN \__exp_arg_last_unbraced:nn
2320   \exp_after:wN { \exp:w \__exp_eval_register:c {#2} } {#1}
2321 }
2322 \cs_new_protected:Npn \::x_unbraced \::: #1#2
2323 {
2324   \cs_set_nopar:Npx \l__exp_internal_tl { \exp_not:n {#1} #2 }
2325   \l__exp_internal_tl
2326 }

```

(End definition for `\__exp_arg_last_unbraced:nn` and others.)

```

\exp_last_unbraced:NV
\exp_last_unbraced:Nv
\exp_last_unbraced:Nf
\exp_last_unbraced:No
\exp_last_unbraced:Nco
\exp_last_unbraced:NcV
\exp_last_unbraced:NNV
\exp_last_unbraced:NNo
\exp_last_unbraced:NNNV
\exp_last_unbraced:NNNo
\exp_last_unbraced:Nno
\exp_last_unbraced:Noo
\exp_last_unbraced:Nfo
\exp_last_unbraced:NnNo
\exp_last_unbraced:Nx
2327 \cs_new:Npn \exp_last_unbraced:NV #1#2
2328 { \exp_after:wN #1 \exp:w \__exp_eval_register:N #2 }
2329 \cs_new:Npn \exp_last_unbraced:Nv #1#2
2330 { \exp_after:wN #1 \exp:w \__exp_eval_register:c {#2} }
2331 \cs_new:Npn \exp_last_unbraced:No #1#2 { \exp_after:wN #1 #2 }
2332 \cs_new:Npn \exp_last_unbraced:Nf #1#2
2333 { \exp_after:wN #1 \exp:w \exp_end_continue_f:w #2 }
2334 \cs_new:Npn \exp_last_unbraced:Nco #1#2#3
2335 { \exp_after:wN #1 \cs:w #2 \exp_after:wN \cs_end: #3 }
2336 \cs_new:Npn \exp_last_unbraced:NcV #1#2#3
2337 {
2338   \exp_after:wN #1
2339   \cs:w #2 \exp_after:wN \cs_end:
2340   \exp:w \__exp_eval_register:N #3
2341 }
2342 \cs_new:Npn \exp_last_unbraced:NNV #1#2#3
2343 {
2344   \exp_after:wN #1
2345   \exp_after:wN #2
2346   \exp:w \__exp_eval_register:N #3
2347 }
2348 \cs_new:Npn \exp_last_unbraced:NNo #1#2#3

```

```

2349 { \exp_after:wN #1 \exp_after:wN #2 #3 }
2350 \cs_new:Npn \exp_last_unbraced:NNNV #1#2#3#4
2351 {
2352   \exp_after:wN #1
2353   \exp_after:wN #2
2354   \exp_after:wN #3
2355   \exp:w \__exp_eval_register:N #4
2356 }
2357 \cs_new:Npn \exp_last_unbraced:NNNo #1#2#3#4
2358 { \exp_after:wN #1 \exp_after:wN #2 \exp_after:wN #3 #4 }
2359 \cs_new:Npn \exp_last_unbraced:Nno { \::n \::o_unbraced \:: }
2360 \cs_new:Npn \exp_last_unbraced:Noo { \::o \::o_unbraced \:: }
2361 \cs_new:Npn \exp_last_unbraced:Nfo { \::f \::o_unbraced \:: }
2362 \cs_new:Npn \exp_last_unbraced:NnNo { \::n \::N \::o_unbraced \:: }
2363 \cs_new_protected:Npn \exp_last_unbraced:Nx { \::x_unbraced \:: }

```

(End definition for `\exp_last_unbraced:NV` and others. These functions are documented on page 29.)

`\exp_last_two_unbraced:Noo` If #2 is a single token then this can be implemented as

```

\__exp_last_two_unbraced:noN
\cs_new:Npn \exp_last_two_unbraced:Noo #1 #2 #3
{ \exp_after:wN \exp_after:wN \exp_after:wN #1 \exp_after:wN #2 #3 }

```

However, for robustness this is not suitable. Instead, a bit of a shuffle is used to ensure that #2 can be multiple tokens.

```

2364 \cs_new:Npn \exp_last_two_unbraced:Noo #1#2#3
2365 { \exp_after:wN \__exp_last_two_unbraced:noN \exp_after:wN {#3} {#2} #1 }
2366 \cs_new:Npn \__exp_last_two_unbraced:noN #1#2#3
2367 { \exp_after:wN #3 #2 #1 }

```

(End definition for `\exp_last_two_unbraced:Noo` and `\__exp_last_two_unbraced:noN`. These functions are documented on page 29.)

## 4.5 Preventing expansion

```

\exp_not:o
\exp_not:c
\exp_not:f
\exp_not:V
\exp_not:v
2368 \cs_new:Npn \exp_not:o #1 { \etex_unexpanded:D \exp_after:wN {#1} }
2369 \cs_new:Npn \exp_not:c #1 { \exp_after:wN \exp_not:N \cs:w #1 \cs_end: }
2370 \cs_new:Npn \exp_not:f #1
2371 { \etex_unexpanded:D \exp_after:wN { \exp:w \exp_end_continue_f:w #1 } }
2372 \cs_new:Npn \exp_not:V #1
2373 {
2374   \etex_unexpanded:D \exp_after:wN
2375   { \exp:w \__exp_eval_register:N #1 }
2376 }
2377 \cs_new:Npn \exp_not:v #1
2378 {
2379   \etex_unexpanded:D \exp_after:wN
2380   { \exp:w \__exp_eval_register:c {#1} }
2381 }

```

(End definition for `\exp_not:o` and others. These functions are documented on page 30.)

## 4.6 Controlled expansion

`\exp:w` To trigger a sequence of “arbitrary” many expansions we need a method to invoke T<sub>E</sub>X’s  
`\exp_end:` expansion mechanism in such a way that a) we are able to stop it in a controlled manner  
`\exp_end_continue_f:w` and b) that the result of what triggered the expansion in the first place is null, i.e., that  
`\exp_end_continue_f:nw` we do not get any unwanted side effects. There aren’t that many possibilities in T<sub>E</sub>X;  
in fact the one explained below might well be the only one (as normally the result of  
expansion is not null).

The trick here is to make use of the fact that `\tex_romannumeral:D` expands the tokens following it when looking for a number and that its expansion is null if that number turns out to be zero or negative. So we use that to start the expansion sequence.

```
2382 %\cs_new_eq:NN \exp:w \tex_romannumeral:D
```

So to stop the expansion sequence in a controlled way all we need to provide is a constant integer zero as part of expanded tokens. As this is an integer constant it immediately stops `\tex_romannumeral:D`’s search for a number.

```
2383 %\int_const:Nn \exp_end: { 0 }
```

(Note that according to our specification all tokens we expand initiated by `\exp:w` are supposed to be expandable (as well as their replacement text in the expansion) so we will not encounter a “number” that actually result in a roman numeral being generated. Or if we do then the programmer made a mistake.)

If on the other hand we want to stop the initial expansion sequence but continue with an f-type expansion we provide the alphabetic constant `^^@` that also represents 0 but this time T<sub>E</sub>X’s syntax for a *<number>* continues searching for an optional space (and it continues expansion doing that) — see T<sub>E</sub>Xbook page 269 for details.

```
2384 \tex_catcode:D ‘^^@=13
```

```
2385 \cs_new_protected:Npn \exp_end_continue_f:w {‘^^@}
```

If the above definition ever appears outside its proper context the active character `^^@` will be executed so we turn this into an error.<sup>7</sup>

```
2386 \cs_new:Npn ^^@{\expansionERROR}
```

```
2387 \cs_new:Npn \exp_end_continue_f:nw #1 { ‘^^@ #1 }
```

```
2388 \tex_catcode:D ‘^^@=15
```

(End definition for `\exp:w` and others. These functions are documented on page 31.)

## 4.7 Defining function variants

```
2389 <@@=cs>
```

`\cs_generate_variant:Nn` #1 : Base form of a function; e.g., `\tl_set:Nn`

#2 : One or more variant argument specifiers; e.g., `{Nx,c,cx}`

After making sure that the base form exists, test whether it is protected or not and define `__cs_tmp:w` as either `\cs_new:Npx` or `\cs_new_protected:Npx`, which is then used to define all the variants (except those involving x-expansion, always protected). Split up the original base function only once, to grab its name and signature. Then we wish to iterate through the comma list of variant argument specifiers, which we first convert to a string: the reason is explained later.

```
2390 \cs_new_protected:Npn \cs_generate_variant:Nn #1#2
```

```
2391 {
```

---

<sup>7</sup>Need to get a real error message.



```

2392 \__chk_if_exist_cs:N #1
2393 \__cs_generate_variant:N #1
2394 \exp_after:wN \__cs_split_function:NN
2395 \exp_after:wN #1
2396 \exp_after:wN \__cs_generate_variant:nnNN
2397 \exp_after:wN #1
2398 \tl_to_str:n {#2} , \scan_stop: , \q_recursion_stop
2399 }

```

(End definition for `\cs_generate_variant:Nn`. This function is documented on page 25.)

```

\__cs_generate_variant:N
\__cs_generate_variant:ww
\__cs_generate_variant:wwNw

```

The goal here is to pick up protected parent functions. There are four cases: the parent function can be a primitive or a macro, and can be expandable or not. For non-expandable primitives, all variants should be protected; skipping the `\else:` branch is safe because all primitive T<sub>E</sub>X conditionals are expandable.

The other case where variants should be protected is when the parent function is a protected macro: then `protected` appears in the meaning before the first occurrence of `macro`. The `ww` auxiliary removes everything in the meaning string after the first `ma`. We use `ma` rather than the full `macro` because the meaning of the `\firstmark` primitive (and four others) can contain an arbitrary string after a leading `firstmark:`. Then, look for `pr` in the part we extracted: no need to look for anything longer: the only strings we can have are an empty string, `\long_`, `\protected_`, `\protected\long_`, `\first`, `\top`, `\bot`, `\splittop`, or `\splitbot`, with `\` replaced by the appropriate escape character. If `pr` appears in the part before `ma`, the first `\q_mark` is taken as an argument of the `wwNw` auxiliary, and `#3` is `\cs_new_protected:Npx`, otherwise it is `\cs_new:Npx`.

```

2400 \cs_new_protected:Npx \__cs_generate_variant:N #1
2401 {
2402   \exp_not:N \exp_after:wN \exp_not:N \if_meaning:w
2403   \exp_not:N \exp_not:N #1 #1
2404   \cs_set_eq:NN \exp_not:N \__cs_tmp:w \cs_new_protected:Npx
2405   \exp_not:N \else:
2406   \exp_not:N \exp_after:wN \exp_not:N \__cs_generate_variant:ww
2407   \exp_not:N \token_to_meaning:N #1 \tl_to_str:n { ma }
2408   \exp_not:N \q_mark
2409   \exp_not:N \q_mark \cs_new_protected:Npx
2410   \tl_to_str:n { pr }
2411   \exp_not:N \q_mark \cs_new:Npx
2412   \exp_not:N \q_stop
2413   \exp_not:N \fi:
2414 }
2415 \use:x
2416 {
2417   \cs_new_protected:Npn \exp_not:N \__cs_generate_variant:ww
2418   ##1 \tl_to_str:n { ma } ##2 \exp_not:N \q_mark
2419 }
2420 { \__cs_generate_variant:wwNw #1 }
2421 \use:x
2422 {
2423   \cs_new_protected:Npn \exp_not:N \__cs_generate_variant:wwNw
2424   ##1 \tl_to_str:n { pr } ##2 \exp_not:N \q_mark
2425   ##3 ##4 \exp_not:N \q_stop
2426 }
2427 { \cs_set_eq:NN \__cs_tmp:w #3 }

```

(End definition for `\_cs_generate_variant:N`, `\_cs_generate_variant:ww`, and `\_cs_generate_variant:wwNw`.)

`\_cs_generate_variant:nnNN`

- #1 : Base name.
- #2 : Base signature.
- #3 : Boolean.
- #4 : Base function.

If the boolean is `\c_false_bool`, the base function has no colon and we abort with an error; otherwise, set off a loop through the desired variant forms. The original function is retained as #4 for efficiency.

```

2428 \cs_new_protected:Npn \_cs_generate_variant:nnNN #1#2#3#4
2429 {
2430   \if_meaning:w \c_false_bool #3
2431     \__msg_kernel_error:nnx { kernel } { missing-colon }
2432     { \token_to_str:c {#1} }
2433     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
2434   \fi:
2435   \_cs_generate_variant:Nnnw #4 {#1}{#2}
2436 }

```

(End definition for `\_cs_generate_variant:nnNN`.)

`\_cs_generate_variant:Nnnw`

- #1 : Base function.
- #2 : Base name.
- #3 : Base signature.
- #4 : Beginning of variant signature.

First check whether to terminate the loop over variant forms. Then, for each variant form, construct a new function name using the original base name, the variant signature consisting of  $l$  letters and the last  $k - l$  letters of the base signature (of length  $k$ ). For example, for a base function `\prop_put:Nnn` which needs a `cV` variant form, we want the new signature to be `cVn`.

There are further subtleties:

- In `\cs_generate_variant:Nn \foo:nnTF {xxTF}`, it would be better to define `\foo:xxTF` using `\exp_args:Nxx`, rather than a hypothetical `\exp_args:NxxTF`. Thus, we wish to trim a common trailing part from the base signature and the variant signature.
- In `\cs_generate_variant:Nn \foo:on {ox}`, the function `\foo:ox` should be defined using `\exp_args:Nnx`, not `\exp_args:Nox`, to avoid double `o` expansion.
- Lastly, `\cs_generate_variant:Nn \foo:on {xn}` should trigger an error, because we do not have a means to replace `o`-expansion by `x`-expansion.

All this boils down to a few rules. Only `n` and `N`-type arguments can be replaced by `\cs_generate_variant:Nn`. Other argument types are allowed to be passed unchanged from the base form to the variant: in the process they are changed to `n` (except for two cases: `N` and `p`-type arguments). A common trailing part is ignored.

We compare the base and variant signatures one character at a time within `x`-expansion. The result is given to `\_cs_generate_variant:wwNN` in the form `\processed variant signature\q_mark errors\q_stop base function new function`. If all went well, `errors` is empty; otherwise, it is a kernel error message, followed by some clean-up code (`\use_none:nnn`).

Note the space after #3 and after the following brace group. Those are ignored by  $\TeX$  when fetching the last argument for `\__cs_generate_variant_loop:nNwN`, but can be used as a delimiter for `\__cs_generate_variant_loop_end:nwwwNNnn`.

```

2437 \cs_new_protected:Npn \__cs_generate_variant:Nnnw #1#2#3#4 ,
2438 {
2439   \if_meaning:w \scan_stop: #4
2440     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
2441   \fi:
2442   \use:x
2443   {
2444     \exp_not:N \__cs_generate_variant:wwNN
2445     \__cs_generate_variant_loop:nNwN { }
2446     #4
2447     \__cs_generate_variant_loop_end:nwwwNNnn
2448     \q_mark
2449     #3 ~
2450     { ~ { } \fi: \__cs_generate_variant_loop_long:wNNnn } ~
2451     { }
2452     \q_stop
2453     \exp_not:N #1 {#2} {#4}
2454   }
2455   \__cs_generate_variant:Nnnw #1 {#2} {#3}
2456 }

```

(End definition for `\__cs_generate_variant:Nnnw`.)

<code>\__cs_generate_variant_loop:nNwN</code>	#1 :	Last few (consecutive) letters common between the base and variant (in fact, <code>\__cs_generate_variant_same:N</code> ( <i>letter</i> ) for each letter).
<code>\__cs_generate_variant_loop_same:w</code>		
<code>\__cs_generate_variant_loop_end:nwwwNNnn</code>	#2 :	Next variant letter.
<code>\__cs_generate_variant_loop_long:wNNnn</code>	#3 :	Remainder of variant form.
<code>\__cs_generate_variant_loop_invalid:NNwNNnn</code>	#4 :	Next base letter.

The first argument is populated by `\__cs_generate_variant_loop_same:w` when a variant letter and a base letter match. It is flushed into the input stream whenever the two letters are different: if the loop ends before, the argument is dropped, which means that trailing common letters are ignored.

The case where the two letters are different is only allowed with a base letter of `N` or `n`. Otherwise, call `\__cs_generate_variant_loop_invalid:NNwNNnn` to remove the end of the loop, get arguments at the end of the loop, and place an appropriate error message as a second argument of `\__cs_generate_variant:wwNN`. If the letters are distinct and the base letter is indeed `n` or `N`, leave in the input stream whatever argument was collected, and the next variant letter #2, then loop by calling `\__cs_generate_variant_loop:nNwN`.

The loop can stop in three ways.

- If the end of the variant form is encountered first, #2 is `\__cs_generate_variant_loop_end:nwwwNNnn` (expanded by the conditional `\if:w`), which inserts some tokens to end the conditional; grabs the *base name* as #7, the *variant signature* #8, the *next base letter* #1 and the part #3 of the base signature that wasn't read yet; and combines those into the *new function* to be defined.
- If the end of the base form is encountered first, #4 is `~{ }\fi:` which ends the conditional (with an empty expansion), followed by `\__cs_generate_variant_loop_-`

long:wNNnn, which places an error as the second argument of `\__cs_generate_variant:wNN`.

- The loop can be interrupted early if the requested expansion is unavailable, namely when the variant and base letters differ and the base is neither `n` nor `N`. Again, an error is placed as the second argument of `\__cs_generate_variant:wNN`.

Note that if the variant form has the same length as the base form, `#2` is as described in the first point, and `#4` as described in the second point above. The `\__cs_generate_variant_loop_end:nwwwNNnn` breaking function takes the empty brace group in `#4` as its first argument: this empty brace group produces the correct signature for the full variant.

```

2457 \cs_new:Npn \__cs_generate_variant_loop:nNwN #1#2#3 \q_mark #4
2458 {
2459   \if:w #2 #4
2460     \exp_after:wN \__cs_generate_variant_loop_same:w
2461   \else:
2462     \if:w N #4 \else:
2463       \if:w n #4 \else:
2464         \__cs_generate_variant_loop_invalid:NNwNNnn #4#2
2465       \fi:
2466     \fi:
2467   \fi:
2468   #1
2469   \prg_do_nothing:
2470   #2
2471   \__cs_generate_variant_loop:nNwN { } #3 \q_mark
2472 }
2473 \cs_new:Npn \__cs_generate_variant_loop_same:w
2474 #1 \prg_do_nothing: #2#3#4
2475 {
2476   #3 { #1 \__cs_generate_variant_same:N #2 }
2477 }
2478 \cs_new:Npn \__cs_generate_variant_loop_end:nwwwNNnn
2479 #1#2 \q_mark #3 ~ #4 \q_stop #5#6#7#8
2480 {
2481   \scan_stop: \scan_stop: \fi:
2482   \exp_not:N \q_mark
2483   \exp_not:N \q_stop
2484   \exp_not:N #6
2485   \exp_not:c { #7 : #8 #1 #3 }
2486 }
2487 \cs_new:Npn \__cs_generate_variant_loop_long:wNNnn #1 \q_stop #2#3#4#5
2488 {
2489   \exp_not:n
2490   {
2491     \q_mark
2492     \_msg_kernel_error:nxxx { kernel } { variant-too-long }
2493     {#5} { \token_to_str:N #3 }
2494     \use_none:nnn
2495     \q_stop
2496     #3
2497     #3
2498   }

```

```

2499 }
2500 \cs_new:Npn \__cs_generate_variant_loop_invalid:NNwNNnn
2501   #1#2 \fi: \fi: \fi: #3 \q_stop #4#5#6#7
2502   {
2503     \fi: \fi: \fi:
2504     \exp_not:n
2505     {
2506       \q_mark
2507       \__msg_kernel_error:nnxxxx { kernel } { invalid-variant }
2508       {#7} { \token_to_str:N #5 } {#1} {#2}
2509       \use_none:nnn
2510       \q_stop
2511       #5
2512       #5
2513     }
2514   }

```

(End definition for `\__cs_generate_variant_loop:nNwN` and others.)

`\__cs_generate_variant_same:N` When the base and variant letters are identical, don't do any expansion. For most argument types, we can use the `n`-type no-expansion, but the `N` and `p` types require a slightly different behaviour with respect to braces.

```

2515 \cs_new:Npn \__cs_generate_variant_same:N #1
2516   {
2517     \if:w N #1
2518       N
2519     \else:
2520       \if:w p #1
2521         p
2522       \else:
2523         n
2524       \fi:
2525     \fi:
2526   }

```

(End definition for `\__cs_generate_variant_same:N`.)

`\__cs_generate_variant:wwNN` If the variant form has already been defined, log its existence (provided `log-functions` is active). Otherwise, make sure that the `\exp_args:N #3` form is defined, and if it contains `x`, change `\__cs_tmp:w` locally to `\cs_new_protected:Npx`. Then define the variant by combining the `\exp_args:N #3` variant and the base function.

```

2527 \__debug_patch:nnNw
2528   {
2529     \cs_if_free:NF #4
2530     {
2531       \__debug_log:x
2532       {
2533         Variant~\token_to_str:N #4~%
2534         already-defined;~ not~ changing~ it~ \msg_line_context:
2535       }
2536     }
2537   }
2538   { }
2539 \cs_new_protected:Npn \__cs_generate_variant:wwNN

```

```

2540     #1 \q_mark #2 \q_stop #3#4
2541   {
2542     #2
2543     \cs_if_free:NT #4
2544     {
2545       \group_begin:
2546       \__cs_generate_internal_variant:n {#1}
2547       \__cs_tmp:w #4 { \exp_not:c { exp_args:N #1 } \exp_not:N #3 }
2548       \group_end:
2549     }
2550   }

```

(End definition for \\_\_cs\_generate\_variant:wwNN.)

\\_\_cs\_generate\_internal\_variant:n Test if \exp\_args:N #1 is already defined and if not define it via the \:: commands using the chars in #1. If #1 contains an x (this is the place where having converted the original comma-list argument to a string is very important), the result should be protected, and the next variant to be defined using that internal variant should be protected.

```

2551 \cs_new_protected:Npx \__cs_generate_internal_variant:n #1
2552 {
2553   \exp_not:N \__cs_generate_internal_variant:wwnNwnn
2554   #1 \exp_not:N \q_mark
2555   { \cs_set_eq:NN \exp_not:N \__cs_tmp:w \cs_new_protected:Npx }
2556   \cs_new_protected:cpx
2557   \token_to_str:N x \exp_not:N \q_mark
2558   { }
2559   \cs_new:cpx
2560   \exp_not:N \q_stop
2561   { exp_args:N #1 }
2562   {
2563     \exp_not:N \__cs_generate_internal_variant_loop:n #1
2564     { : \exp_not:N \use_i:nn }
2565   }
2566 }
2567 \use:x
2568 {
2569   \cs_new_protected:Npn \exp_not:N \__cs_generate_internal_variant:wwnNwnn
2570   ##1 \token_to_str:N x ##2 \exp_not:N \q_mark
2571   ##3 ##4 ##5 \exp_not:N \q_stop ##6 ##7
2572 }
2573 {
2574   #3
2575   \cs_if_free:cT {#6} { #4 {#6} {#7} }
2576 }

```

This command grabs char by char outputting \::#1 (not expanded further). We avoid tests by putting a trailing : \use\_i:nn, which leaves \cs\_end: and removes the looping macro. The colon is in fact also turned into \::: so that the required structure for \exp\_args:N... commands is correctly terminated.

```

2577 \cs_new:Npn \__cs_generate_internal_variant_loop:n #1
2578 {
2579   \exp_after:wN \exp_not:N \cs:w :: #1 \cs_end:
2580   \__cs_generate_internal_variant_loop:n
2581 }

```

(End definition for `\_cs_generate_internal_variant:n`, `\_cs_generate_internal_variant:wnw`, and `\_cs_generate_internal_variant_loop:n`.)

2582 `\>initex | package`

## 5 l3tl implementation

2583 `\>*initex | package`

2584 `\>@@=tl`

A token list variable is a  $\text{\TeX}$  macro that holds tokens. By using the  $\varepsilon\text{-TeX}$  primitive `\unexpanded` inside a  $\text{\TeX}$  `\edef` it is possible to store any tokens, including `#`, in this way.

### 5.1 Functions

**`\tl_new:N`** Creating new token list variables is a case of checking for an existing definition and doing the definition.

**`\tl_new:c`**

```
2585 \cs_new_protected:Npn \tl_new:N #1
2586 {
2587     \__chk_if_free_cs:N #1
2588     \cs_gset_eq:NN #1 \c_empty_tl
2589 }
2590 \cs_generate_variant:Nn \tl_new:N { c }
```

(End definition for `\tl_new:N`. This function is documented on page 34.)

**`\tl_const:Nn`** Constants are also easy to generate.

**`\tl_const:Nx`**

**`\tl_const:cn`**

**`\tl_const:cx`**

```
2591 \cs_new_protected:Npn \tl_const:Nn #1#2
2592 {
2593     \__chk_if_free_cs:N #1
2594     \cs_gset_nopar:Npx #1 { \exp_not:n {#2} }
2595 }
2596 \cs_new_protected:Npn \tl_const:Nx #1#2
2597 {
2598     \__chk_if_free_cs:N #1
2599     \cs_gset_nopar:Npx #1 {#2}
2600 }
2601 \cs_generate_variant:Nn \tl_const:Nn { c }
2602 \cs_generate_variant:Nn \tl_const:Nx { c }
```

(End definition for `\tl_const:Nn`. This function is documented on page 34.)

**`\tl_clear:N`** Clearing a token list variable means setting it to an empty value. Error checking is sorted out by the parent function.

**`\tl_clear:c`**

**`\tl_gclear:N`**

**`\tl_gclear:c`**

```
2603 \cs_new_protected:Npn \tl_clear:N #1
2604 { \tl_set_eq:NN #1 \c_empty_tl }
2605 \cs_new_protected:Npn \tl_gclear:N #1
2606 { \tl_gset_eq:NN #1 \c_empty_tl }
2607 \cs_generate_variant:Nn \tl_clear:N { c }
2608 \cs_generate_variant:Nn \tl_gclear:N { c }
```

(End definition for `\tl_clear:N` and `\tl_gclear:N`. These functions are documented on page 34.)

**\tl\_clear\_new:N** Clearing a token list variable means setting it to an empty value. Error checking is sorted out by the parent function.

**\tl\_clear\_new:c**

**\tl\_gclear\_new:N**

**\tl\_gclear\_new:c**

```

2609 \cs_new_protected:Npn \tl_clear_new:N #1
2610 { \tl_if_exist:NTF #1 { \tl_clear:N #1 } { \tl_new:N #1 } }
2611 \cs_new_protected:Npn \tl_gclear_new:N #1
2612 { \tl_if_exist:NTF #1 { \tl_gclear:N #1 } { \tl_new:N #1 } }
2613 \cs_generate_variant:Nn \tl_clear_new:N { c }
2614 \cs_generate_variant:Nn \tl_gclear_new:N { c }

```

(End definition for \tl\_clear\_new:N and \tl\_gclear\_new:N. These functions are documented on page 35.)

**\tl\_set\_eq:NN** For setting token list variables equal to each other. When checking is turned on, make sure both variables exist.

**\tl\_set\_eq:Nc**

**\tl\_set\_eq:cN**

**\tl\_set\_eq:cc**

**\tl\_gset\_eq:NN**

**\tl\_gset\_eq:Nc**

**\tl\_gset\_eq:cN**

**\tl\_gset\_eq:cc**

```

2615 \tex_ifodd:D \l@expl@enable@debug@bool
2616 \cs_new_protected:Npn \tl_set_eq:NN #1#2
2617 {
2618   \__chk_if_exist_var:N #1
2619   \__chk_if_exist_var:N #2
2620   \cs_set_eq:NN #1 #2
2621 }
2622 \cs_new_protected:Npn \tl_gset_eq:NN #1#2
2623 {
2624   \__chk_if_exist_var:N #1
2625   \__chk_if_exist_var:N #2
2626   \cs_gset_eq:NN #1 #2
2627 }
2628 \else:
2629   \cs_new_eq:NN \tl_set_eq:NN \cs_set_eq:NN
2630   \cs_new_eq:NN \tl_gset_eq:NN \cs_gset_eq:NN
2631 \fi:
2632 \cs_generate_variant:Nn \tl_set_eq:NN { cN, Nc, cc }
2633 \cs_generate_variant:Nn \tl_gset_eq:NN { cN, Nc, cc }

```

(End definition for \tl\_set\_eq:NN and \tl\_gset\_eq:NN. These functions are documented on page 35.)

**\tl\_concat:NNN** Concatenating token lists is easy. When checking is turned on, all three arguments must be checked: a token list #2 or #3 equal to \scan\_stop: would lead to problems later on.

**\tl\_concat:ccc**

**\tl\_gconcat:NNN**

**\tl\_gconcat:ccc**

```

2634 \__debug_patch:nnNw
2635 {
2636   \__chk_if_exist_var:N #1
2637   \__chk_if_exist_var:N #2
2638   \__chk_if_exist_var:N #3
2639 }
2640 { }
2641 \cs_new_protected:Npn \tl_concat:NNN #1#2#3
2642 { \tl_set:Nx #1 { \exp_not:o {#2} \exp_not:o {#3} } }
2643 \__debug_patch:nnNw
2644 {
2645   \__chk_if_exist_var:N #1
2646   \__chk_if_exist_var:N #2
2647   \__chk_if_exist_var:N #3
2648 }
2649 { }

```



```

2650 \cs_new_protected:Npn \tl_gconcat:NNN #1#2#3
2651 { \tl_gset:Nx #1 { \exp_not:o {#2} \exp_not:o {#3} } }
2652 \cs_generate_variant:Nn \tl_concat:NNN { ccc }
2653 \cs_generate_variant:Nn \tl_gconcat:NNN { ccc }

```

(End definition for `\tl_concat:NNN` and `\tl_gconcat:NNN`. These functions are documented on page 35.)

`\tl_if_exist_p:N` Copies of the `cs` functions defined in `l3basics`.

```

\tl_if_exist_p:c 2654 \prg_new_eq_conditional:NNn \tl_if_exist:N \cs_if_exist:N { TF , T , F , p }
\tl_if_exist:NTF 2655 \prg_new_eq_conditional:NNn \tl_if_exist:c \cs_if_exist:c { TF , T , F , p }
\tl_if_exist:cTF

```

(End definition for `\tl_if_exist:NTF`. This function is documented on page 35.)

## 5.2 Constant token lists

`\c_empty_tl` Never full. We need to define that constant before using `\tl_new:N`.

```

2656 \tl_const:Nn \c_empty_tl { }

```

(End definition for `\c_empty_tl`. This variable is documented on page 46.)

`\c_space_tl` A space as a token list (as opposed to as a character).

```

2657 \tl_const:Nn \c_space_tl { ~ }

```

(End definition for `\c_space_tl`. This variable is documented on page 46.)

## 5.3 Adding to token list variables

`\tl_set:Nn` By using `\exp_not:n` token list variables can contain `#` tokens, which makes the token list registers provided by `TEX` more or less redundant. The `\tl_set:No` version is done “by hand” as it is used quite a lot. Each definition is prefixed by a call to `\__debug_patch:nnNw` which adds an existence check to the definition.

```

\tl_set:Nf 2658 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
\tl_set:Nx 2659 \cs_new_protected:Npn \tl_set:Nn #1#2
\tl_set:cn 2660 { \cs_set_nopar:Npx #1 { \exp_not:n {#2} } }
\tl_set:cV 2661 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
\tl_set:cv 2662 \cs_new_protected:Npn \tl_set:No #1#2
\tl_set:co 2663 { \cs_set_nopar:Npx #1 { \exp_not:o {#2} } }
\tl_set:cf 2664 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
\tl_set:cx 2665 \cs_new_protected:Npn \tl_set:Nx #1#2
\tl_set:cx 2666 { \cs_set_nopar:Npx #1 {#2} }
\tl_gset:Nn 2667 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
\tl_gset:Nv 2668 \cs_new_protected:Npn \tl_gset:Nn #1#2
\tl_gset:Nv 2669 { \cs_gset_nopar:Npx #1 { \exp_not:n {#2} } }
\tl_gset:No 2670 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
\tl_gset:Nf 2671 \cs_new_protected:Npn \tl_gset:No #1#2
\tl_gset:Nx 2672 { \cs_gset_nopar:Npx #1 { \exp_not:o {#2} } }
\tl_gset:cn 2673 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
\tl_gset:cV 2674 \cs_new_protected:Npn \tl_gset:Nx #1#2
\tl_gset:cv 2675 { \cs_gset_nopar:Npx #1 {#2} }
\tl_gset:co 2676 \cs_generate_variant:Nn \tl_set:Nn { NV , Nv , Nf }
\tl_gset:cf 2677 \cs_generate_variant:Nn \tl_set:Nx { c }
\tl_gset:cx 2678 \cs_generate_variant:Nn \tl_set:Nn { c , co , cV , cv , cf }
2679 \cs_generate_variant:Nn \tl_gset:Nn { NV , Nv , Nf }

```

```

2680 \cs_generate_variant:Nn \tl_gset:Nx { c }
2681 \cs_generate_variant:Nn \tl_gset:Nn { c, co, cV, cv, cf }

```

(End definition for `\tl_set:Nn` and `\tl_gset:Nn`. These functions are documented on page 35.)

```

\tl_put_left:Nn Adding to the left is done directly to gain a little performance.
\tl_put_left:NV
\tl_put_left:No
\tl_put_left:Nx
\tl_put_left:cn
\tl_put_left:cV
\tl_put_left:co
\tl_put_left:cx
\tl_gput_left:Nn
\tl_gput_left:NV
\tl_gput_left:No
\tl_gput_left:Nx
\tl_gput_left:cn
\tl_gput_left:cV
\tl_gput_left:co
\tl_gput_left:cx
2682 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
2683 \cs_new_protected:Npn \tl_put_left:Nn #1#2
2684 { \cs_set_nopar:Npx #1 { \exp_not:n {#2} \exp_not:o #1 } }
2685 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
2686 \cs_new_protected:Npn \tl_put_left:NV #1#2
2687 { \cs_set_nopar:Npx #1 { \exp_not:V #2 \exp_not:o #1 } }
2688 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
2689 \cs_new_protected:Npn \tl_put_left:No #1#2
2690 { \cs_set_nopar:Npx #1 { \exp_not:o {#2} \exp_not:o #1 } }
2691 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
2692 \cs_new_protected:Npn \tl_put_left:Nx #1#2
2693 { \cs_set_nopar:Npx #1 { #2 \exp_not:o #1 } }
2694 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
2695 \cs_new_protected:Npn \tl_gput_left:Nn #1#2
2696 { \cs_gset_nopar:Npx #1 { \exp_not:n {#2} \exp_not:o #1 } }
2697 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
2698 \cs_new_protected:Npn \tl_gput_left:NV #1#2
2699 { \cs_gset_nopar:Npx #1 { \exp_not:V #2 \exp_not:o #1 } }
2700 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
2701 \cs_new_protected:Npn \tl_gput_left:No #1#2
2702 { \cs_gset_nopar:Npx #1 { \exp_not:o {#2} \exp_not:o #1 } }
2703 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
2704 \cs_new_protected:Npn \tl_gput_left:Nx #1#2
2705 { \cs_gset_nopar:Npx #1 { #2 \exp_not:o {#1} } }
2706 \cs_generate_variant:Nn \tl_put_left:Nn { c }
2707 \cs_generate_variant:Nn \tl_put_left:NV { c }
2708 \cs_generate_variant:Nn \tl_put_left:No { c }
2709 \cs_generate_variant:Nn \tl_put_left:Nx { c }
2710 \cs_generate_variant:Nn \tl_gput_left:Nn { c }
2711 \cs_generate_variant:Nn \tl_gput_left:NV { c }
2712 \cs_generate_variant:Nn \tl_gput_left:No { c }
2713 \cs_generate_variant:Nn \tl_gput_left:Nx { c }

```

(End definition for `\tl_put_left:Nn` and `\tl_gput_left:Nn`. These functions are documented on page 35.)

```

\tl_put_right:Nn The same on the right.
\tl_put_right:NV
\tl_put_right:No
\tl_put_right:Nx
\tl_put_right:cn
\tl_put_right:cV
\tl_put_right:co
\tl_put_right:cx
\tl_gput_right:Nn
\tl_gput_right:NV
\tl_gput_right:No
\tl_gput_right:Nx
\tl_gput_right:cn
\tl_gput_right:cV
\tl_gput_right:co
\tl_gput_right:cx
2714 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
2715 \cs_new_protected:Npn \tl_put_right:Nn #1#2
2716 { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:n {#2} } }
2717 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
2718 \cs_new_protected:Npn \tl_put_right:NV #1#2
2719 { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:V #2 } }
2720 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
2721 \cs_new_protected:Npn \tl_put_right:No #1#2
2722 { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:o {#2} } }
2723 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
2724 \cs_new_protected:Npn \tl_put_right:Nx #1#2
2725 { \cs_set_nopar:Npx #1 { \exp_not:o #1 #2 } }

```

```

2726 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
2727 \cs_new_protected:Npn \tl_gput_right:Nn #1#2
2728   { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:n {#2} } }
2729 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
2730 \cs_new_protected:Npn \tl_gput_right:NV #1#2
2731   { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:V #2 } }
2732 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
2733 \cs_new_protected:Npn \tl_gput_right:No #1#2
2734   { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:o {#2} } }
2735 \__debug_patch:nnNw { \__chk_if_exist_var:N #1 } { }
2736 \cs_new_protected:Npn \tl_gput_right:Nx #1#2
2737   { \cs_gset_nopar:Npx #1 { \exp_not:o {#1} #2 } }
2738 \cs_generate_variant:Nn \tl_put_right:Nn { c }
2739 \cs_generate_variant:Nn \tl_put_right:NV { c }
2740 \cs_generate_variant:Nn \tl_put_right:No { c }
2741 \cs_generate_variant:Nn \tl_put_right:Nx { c }
2742 \cs_generate_variant:Nn \tl_gput_right:Nn { c }
2743 \cs_generate_variant:Nn \tl_gput_right:NV { c }
2744 \cs_generate_variant:Nn \tl_gput_right:No { c }
2745 \cs_generate_variant:Nn \tl_gput_right:Nx { c }

```

(End definition for `\tl_put_right:Nn` and `\tl_gput_right:Nn`. These functions are documented on page 35.)

## 5.4 Reassigning token list category codes

`\c__tl_rescan_marker_tl` The rescanning code needs a special token list containing the same character (chosen here to be a colon) with two different category codes: it cannot appear in the tokens being rescanned since all colons have the same category code.

```

2746 \tl_const:Nx \c__tl_rescan_marker_tl { : \token_to_str:N : }

```

(End definition for `\c__tl_rescan_marker_tl`.)

`\tl_set_rescan:Nnn` These functions use a common auxiliary. After some initial setup explained below, and the user setup #3 (followed by `\scan_stop:` to be safe), the tokens are rescanned by `\_tl_set_rescan:n` and stored into `\l__tl_internal_a_tl`, then passed to #1#2 outside the group after expansion. The auxiliary `\_tl_set_rescan:n` is defined later: in the simplest case, this auxiliary calls `\_tl_set_rescan_multi:n`, whose code is included here to help understand the approach.

`\tl_gset_rescan:Nnn` One difficulty when rescanning is that `\scantokens` treats the argument as a file, and without the correct settings a T<sub>E</sub>X error occurs:

```

! File ended while scanning definition of ...

```

`\tl_set_rescan:cno` The standard solution is to use an x-expanding assignment and set `\everyeof` to `\exp_not:N` to suppress the error at the end of the file. Since the rescanned tokens should not be expanded, they are taken as a delimited argument of an auxiliary which wraps them in `\exp_not:n` (in fact `\exp_not:o`, as there is a `\prg_do_nothing:` to avoid losing braces). The delimiter cannot appear within the rescanned token list because it contains twice the same character, with different catcodes.

`\tl_gset_rescan:cnx` The difference between single-line and multiple-line files complicates the story, as explained below.

`\tl_rescan:nn`

```

\_tl_set_rescan:NNnn
\_tl_set_rescan_multi:n
\_tl_rescan:w

```

```

2747 \cs_new_protected:Npn \tl_set_rescan:Nnn

```

```

2748 { \_tl\_set\_rescan:NNnn \tl\_set:Nn }
2749 \cs\_new\_protected:Npn \tl\_gset\_rescan:Nnn
2750 { \_tl\_set\_rescan:NNnn \tl\_gset:Nn }
2751 \cs\_new\_protected:Npn \tl\_rescan:nn
2752 { \_tl\_set\_rescan:NNnn \prg\_do\_nothing: \use:n }
2753 \cs\_new\_protected:Npn \_tl\_set\_rescan:NNnn #1#2#3#4
2754 {
2755   \tl\_if\_empty:nTF {#4}
2756   {
2757     \group\_begin:
2758     #3
2759     \group\_end:
2760     #1 #2 { }
2761   }
2762   {
2763     \group\_begin:
2764     \exp\_args:No \etex\_everyeof:D { \c\_tl\_rescan\_marker\_tl \exp\_not:N }
2765     \int\_compare:nNnT \tex\_endlinechar:D = { 32 }
2766     { \int\_set:Nn \tex\_endlinechar:D { -1 } }
2767     \tex\_newlinechar:D \tex\_endlinechar:D
2768     #3 \scan\_stop:
2769     \exp\_args:No \_tl\_set\_rescan:n { \tl\_to\_str:n {#4} }
2770     \exp\_args:NNNo
2771     \group\_end:
2772     #1 #2 \l\_tl\_internal\_a\_tl
2773   }
2774 }
2775 \cs\_new\_protected:Npn \_tl\_set\_rescan\_multi:n #1
2776 {
2777   \tl\_set:Nx \l\_tl\_internal\_a\_tl
2778   {
2779     \exp\_after:wN \_tl\_rescan:w
2780     \exp\_after:wN \prg\_do\_nothing:
2781     \etex\_scantokens:D {#1}
2782   }
2783 }
2784 \exp\_args:Nno \use:nn
2785 { \cs\_new:Npn \_tl\_rescan:w #1 } \c\_tl\_rescan\_marker\_tl
2786 { \exp\_not:o {#1} }
2787 \cs\_generate\_variant:Nn \tl\_set\_rescan:Nnn { Nno , Nnx }
2788 \cs\_generate\_variant:Nn \tl\_set\_rescan:Nnn { c , cno , cnx }
2789 \cs\_generate\_variant:Nn \tl\_gset\_rescan:Nnn { Nno , Nnx }
2790 \cs\_generate\_variant:Nn \tl\_gset\_rescan:Nnn { c , cno }

```

(End definition for `\tl\_set\_rescan:Nnn` and others. These functions are documented on page 37.)

<pre> \_tl\_set\_rescan:n \_tl\_set\_rescan:NnTF \_tl\_set\_rescan\_single:nn \_tl\_set\_rescan\_single\_aux:nn </pre>	<p>This function calls <code>\_tl\_set\_rescan\_multiple:n</code> or <code>\_tl\_set\_rescan\_single:nn</code> { ' } depending on whether its argument is a single-line fragment of code/data or is made of multiple lines by testing for the presence of a <code>\newlinechar</code> character. If <code>\newlinechar</code> is out of range, the argument is assumed to be a single line.</p>
--	---

The case of multiple lines is a straightforward application of `\scantokens` as described above. The only subtlety is that `\newlinechar` should be equal to `\endlinechar` because `\newlinechar` characters become new lines and then become `\endlinechar` characters when writing to an abstract file and reading back. This equality is ensured by

setting `\newlinechar` equal to `\endlinechar`. Prior to this, `\endlinechar` is set to `-1` if it was `32` (in particular true after `\ExplSyntaxOn`) to avoid unreasonable line-breaks at every space for instance in error messages triggered by the user setup. Another side effect of reading back from the file is that spaces (catcode `10`) are ignored at the beginning of lines, and spaces and tabs (character code `32` and `9`) are ignored at the end of lines.

For a single line, no `\endlinechar` should be added, so it is set to `-1`, and spaces should not be removed.

Trailing spaces and tabs are a difficult matter, as `TEX` removes these at a very low level. The only way to preserve them is to rescan not the argument but the argument followed by a character with a reasonable category code. Here, `11` (letter), `12` (other) and `13` (active) are accepted, as these are suitable for delimiting an argument, and it is very unlikely that none of the ASCII characters are in one of these categories. To avoid selecting one particular character to put at the end, whose category code may have been modified, there is a loop through characters from `'` (ASCII `39`) to `~` (ASCII `127`). The choice of starting point was made because this is the start of a very long range of characters whose standard category is letter or other, thus minimizing the number of steps needed by the loop (most often just a single one). Once a valid character is found, run some code very similar to `\__tl_set_rescan_multi:n`, except that `\__tl_rescan:w` must be redefined to also remove the additional character (with the appropriate catcode). Getting the delimiter with the right catcode requires using `\scantokens` inside an `x`-expansion, hence using the previous definition of `\__tl_rescan:w` as well. The odd `\exp_not:N` `\use:n` ensures that the trailing `\exp_not:N` in `\everyeof` does not prevent the expansion of `\c__tl_rescan_marker_tl`, but rather of a closing brace (this does nothing). If no valid character is found, similar code is ran, and the only difference is that trailing spaces are not preserved (bear in mind that this only happens if no character between `39` and `127` has catcode letter, other or active).

There is also some work to preserve leading spaces: test whether the first character (given by `\str_head:n`, with an extra space to circumvent a limitation of `f`-expansion) has catcode `10` and add what `TEX` would add in the middle of a line for any sequence of such characters: a single space with catcode `10` and character code `32`.

```

2791 \group_begin:
2792   \tex_catcode:D '\^~@ = 12 \scan_stop:
2793   \cs_new_protected:Npn \__tl_set_rescan:n #1
2794     {
2795       \int_compare:nNnTF \tex_newlinechar:D < 0
2796         { \use_ii:n }
2797         {
2798           \char_set_lccode:nn { 0 } { \tex_newlinechar:D }
2799           \tex_lowercase:D { \__tl_set_rescan:NnTF ^~@ } {#1}
2800         }
2801         { \__tl_set_rescan_multi:n }
2802         { \__tl_set_rescan_single:nn { ' } }
2803       {#1}
2804     }
2805   \cs_new_protected:Npn \__tl_set_rescan:NnTF #1#2
2806     { \tl_if_in:nnTF {#2} {#1} }
2807   \cs_new_protected:Npn \__tl_set_rescan_single:nn #1
2808     {
2809       \int_compare:nNnTF
2810         { \char_value_catcode:n { '#1 } / 3 } = 4
2811         { \__tl_set_rescan_single_aux:nn {#1} }

```

```

2812 {
2813   \int_compare:nNnTF { '#1 } < { '\~ }
2814   {
2815     \char_set_lccode:nn { 0 } { '#1 + 1 }
2816     \tex_lowercase:D { \_tl_set_rescan_single:nn { ^^@ } }
2817   }
2818   { \_tl_set_rescan_single_aux:nn { } }
2819 }
2820 }
2821 \cs_new_protected:Npn \_tl_set_rescan_single_aux:nn #1#2
2822 {
2823   \int_set:Nn \tex_endlinechar:D { -1 }
2824   \use:x
2825   {
2826     \exp_not:N \use:n
2827     {
2828       \exp_not:n { \cs_set:Npn \_tl_rescan:w ##1 }
2829       \exp_after:wN \_tl_rescan:w
2830       \exp_after:wN \prg_do_nothing:
2831       \etex_scantokens:D {#1}
2832     }
2833     \c\_tl_rescan_marker_tl
2834   }
2835   { \exp_not:o {##1} }
2836   \tl_set:Nx \l\_tl_internal_a_tl
2837   {
2838     \int_compare:nNnT
2839     {
2840       \char_value_catcode:n
2841       { \exp_last_unbraced:Nf ' \str_head:n {#2} ~ }
2842     }
2843     = { 10 } { ~ }
2844     \exp_after:wN \_tl_rescan:w
2845     \exp_after:wN \prg_do_nothing:
2846     \etex_scantokens:D { #2 #1 }
2847   }
2848 }
2849 \group_end:

```

(End definition for `\_tl_set_rescan:n` and others.)

## 5.5 Modifying token list variables

`\tl_replace_all:Nnn` All of the `replace` functions call `\_tl_replace:NnNNnn` with appropriate arguments.  
`\tl_replace_all:cnn` The first two arguments are explained later. The next controls whether the replacement  
`\tl_greplace_all:Nnn` function calls itself (`\_tl_replace_next:w`) or stops (`\_tl_replace_wrap:w`) after  
`\tl_greplace_all:cnn` the first replacement. Next comes an x-type assignment function `\tl_set:Nx` or `\tl_`  
`\tl_replace_once:Nnn` `gset:Nx` for local or global replacements. Finally, the three arguments  $\langle tl\ var \rangle$   $\{ \langle pattern \rangle \}$   
`\tl_replace_once:cnn`  $\{ \langle replacement \rangle \}$  provided by the user. When describing the auxiliary functions below,  
`\tl_greplace_once:Nnn` we denote the contents of the  $\langle tl\ var \rangle$  by  $\langle token\ list \rangle$ .  
`\tl_greplace_once:cnn`

```

2850 \cs_new_protected:Npn \tl_replace_once:Nnn
2851 { \_tl_replace:NnNNnn \q_mark ? \_tl_replace_wrap:w \tl_set:Nx }
2852 \cs_new_protected:Npn \tl_greplace_once:Nnn

```

```

2853 { \_tl\_replace:NnNNNnn \q\_mark ? \_tl\_replace\_wrap:w \tl\_gset:Nx }
2854 \cs\_new\_protected:Npn \tl\_replace\_all:Nnn
2855 { \_tl\_replace:NnNNNnn \q\_mark ? \_tl\_replace\_next:w \tl\_set:Nx }
2856 \cs\_new\_protected:Npn \tl\_greplace\_all:Nnn
2857 { \_tl\_replace:NnNNNnn \q\_mark ? \_tl\_replace\_next:w \tl\_gset:Nx }
2858 \cs\_generate\_variant:Nn \tl\_replace\_once:Nnn { c }
2859 \cs\_generate\_variant:Nn \tl\_greplace\_once:Nnn { c }
2860 \cs\_generate\_variant:Nn \tl\_replace\_all:Nnn { c }
2861 \cs\_generate\_variant:Nn \tl\_greplace\_all:Nnn { c }

```

(End definition for `\tl\_replace\_all:Nnn` and others. These functions are documented on page 36.)

```

\_tl\_replace:NnNNNnn
\_tl\_replace\_auxi:NnnNNNnn
\_tl\_replace\_auxii:NnnNNn
  \_tl\_replace\_next:w
  \_tl\_replace\_wrap:w

```

To implement the actual replacement auxiliary `\_tl\_replace\_auxii:NnnNNn` we need a  $\langle \textit{delimiter} \rangle$  with the following properties:

- all occurrences of the  $\langle \textit{pattern} \rangle$  #6 in “ $\langle \textit{token list} \rangle \langle \textit{delimiter} \rangle$ ” belong to the  $\langle \textit{token list} \rangle$  and have no overlap with the  $\langle \textit{delimiter} \rangle$ ,
- the first occurrence of the  $\langle \textit{delimiter} \rangle$  in “ $\langle \textit{token list} \rangle \langle \textit{delimiter} \rangle$ ” is the trailing  $\langle \textit{delimiter} \rangle$ .

We first find the building blocks for the  $\langle \textit{delimiter} \rangle$ , namely two tokens  $\langle A \rangle$  and  $\langle B \rangle$  such that  $\langle A \rangle$  does not appear in #6 and #6 is not  $\langle B \rangle$  (this condition is trivial if #6 has more than one token). Then we consider the delimiters “ $\langle A \rangle$ ” and “ $\langle A \rangle \langle A \rangle^n \langle B \rangle \langle A \rangle^n \langle B \rangle$ ”, for  $n \geq 1$ , where  $\langle A \rangle^n$  denotes  $n$  copies of  $\langle A \rangle$ , and we choose as our  $\langle \textit{delimiter} \rangle$  the first one which is not in the  $\langle \textit{token list} \rangle$ .

Every delimiter in the set obeys the first condition: #6 does not contain  $\langle A \rangle$  hence cannot be overlapping with the  $\langle \textit{token list} \rangle$  and the  $\langle \textit{delimiter} \rangle$ , and it cannot be within the  $\langle \textit{delimiter} \rangle$  since it would have to be in one of the two  $\langle B \rangle$  hence be equal to this single token (or empty, but this is an error case filtered separately). Given the particular form of these delimiters, for which no prefix is also a suffix, the second condition is actually a consequence of the weaker condition that the  $\langle \textit{delimiter} \rangle$  we choose does not appear in the  $\langle \textit{token list} \rangle$ . Additionally, the set of delimiters is such that a  $\langle \textit{token list} \rangle$  of  $n$  tokens can contain at most  $O(n^{1/2})$  of them, hence we find a  $\langle \textit{delimiter} \rangle$  with at most  $O(n^{1/2})$  tokens in a time at most  $O(n^{3/2})$ . Bear in mind that these upper bounds are reached only in very contrived scenarios: we include the case “ $\langle A \rangle$ ” in the list of delimiters to try, so that the  $\langle \textit{delimiter} \rangle$  is simply `\q\_mark` in the most common situation where neither the  $\langle \textit{token list} \rangle$  nor the  $\langle \textit{pattern} \rangle$  contains `\q\_mark`.

Let us now ahead, optimizing for this most common case. First, two special cases: an empty  $\langle \textit{pattern} \rangle$  #6 is an error, and if #1 is absent from both the  $\langle \textit{token list} \rangle$  #5 and the  $\langle \textit{pattern} \rangle$  #6 then we can use it as the  $\langle \textit{delimiter} \rangle$  through `\_tl\_replace\_auxii:NnnNNn {#1}`. Otherwise, we end up calling `\_tl\_replace:NnNNNnn` repeatedly with the first two arguments `\q\_mark {?}`, `\? {??}`, `\?? {???}`, and so on, until #6 does not contain the control sequence #1, which we take as our  $\langle A \rangle$ . The argument #2 only serves to collect ? characters for #1. Note that the order of the tests means that the first two are done every time, which is wasteful (for instance, we repeatedly test for the emptiness of #6). However, this is rare enough not to matter. Finally, choose  $\langle B \rangle$  to be `\q\_nil` or `\q\_stop` such that it is not equal to #6.

The `\_tl\_replace\_auxi:NnnNNNnn` auxiliary receives  $\{\langle A \rangle\}$  and  $\{\langle A \rangle^n \langle B \rangle\}$  as its arguments, initially with  $n = 1$ . If “ $\langle A \rangle \langle A \rangle^n \langle B \rangle \langle A \rangle^n \langle B \rangle$ ” is in the  $\langle \textit{token list} \rangle$  then increase  $n$  and try again. Once it is not anymore in the  $\langle \textit{token list} \rangle$  we take it as our  $\langle \textit{delimiter} \rangle$  and pass this to the `auxii` auxiliary.

```

2862 \cs_new_protected:Npn \__tl_replace:NnNNNnn #1#2#3#4#5#6#7
2863 {
2864   \tl_if_empty:nTF {#6}
2865   {
2866     \_msg_kernel_error:nxx { kernel } { empty-search-pattern }
2867     { \tl_to_str:n {#7} }
2868   }
2869   {
2870     \tl_if_in:onTF { #5 #6 } {#1}
2871     {
2872       \tl_if_in:nnTF {#6} {#1}
2873       { \exp_args:Nc \__tl_replace:NnNNNnn {#2} {#2?} }
2874       {
2875         \quark_if_nil:nTF {#6}
2876         { \__tl_replace_auxi:NnnNNNnn #5 {#1} { #1 \q_stop } }
2877         { \__tl_replace_auxi:NnnNNNnn #5 {#1} { #1 \q_nil } }
2878       }
2879     }
2880     { \__tl_replace_auxii:nNNNnn {#1} }
2881     #3#4#5 {#6} {#7}
2882   }
2883 }
2884 \cs_new_protected:Npn \__tl_replace_auxi:NnnNNNnn #1#2#3
2885 {
2886   \tl_if_in:NnTF #1 { #2 #3 #3 }
2887   { \__tl_replace_auxi:NnnNNNnn #1 { #2 #3 } {#2} }
2888   { \__tl_replace_auxii:nNNNnn { #2 #3 #3 } }
2889 }

```

The auxiliary `\__tl_replace_auxii:nNNNnn` receives the following arguments:  $\{\langle\textit{delimiter}\rangle\}$   $\langle\textit{function}\rangle$   $\langle\textit{assignment}\rangle$   $\langle\textit{tl var}\rangle$   $\{\langle\textit{pattern}\rangle\}$   $\{\langle\textit{replacement}\rangle\}$ . All of its work is done between `\group_align_safe_begin:` and `\group_align_safe_end:` to avoid issues in alignments. It does the actual replacement within `#3 #4 {...}`, an x-expanding  $\langle\textit{assignment}\rangle$  `#3` to the  $\langle\textit{tl var}\rangle$  `#4`. The auxiliary `\__tl_replace_next:w` is called, followed by the  $\langle\textit{token list}\rangle$ , some tokens including the  $\langle\textit{delimiter}\rangle$  `#1`, followed by the  $\langle\textit{pattern}\rangle$  `#5`. This auxiliary finds an argument delimited by `#5` (the presence of a trailing `#5` avoids runaway arguments) and calls `\__tl_replace_wrap:w` to test whether this `#5` is found within the  $\langle\textit{token list}\rangle$  or is the trailing one.

If on the one hand it is found within the  $\langle\textit{token list}\rangle$ , then `##1` cannot contain the  $\langle\textit{delimiter}\rangle$  `#1` that we worked so hard to obtain, thus `\__tl_replace_wrap:w` gets `##1` as its own argument `##1`, and protects it against the x-expanding assignment. It also finds `\exp_not:n` as `##2` and does nothing to it, thus letting through `\exp_not:n`  $\{\langle\textit{replacement}\rangle\}$  into the assignment. Note that `\__tl_replace_next:w` and `\__tl_replace_wrap:w` are always called followed by two empty brace groups. These are safe because no delimiter can match them. They prevent losing braces when grabbing delimited arguments, but require the use of `\exp_not:o` and `\use_none:nn`, rather than simply `\exp_not:n`. Afterwards, `\__tl_replace_next:w` is called to repeat the replacement, or `\__tl_replace_wrap:w` if we only want a single replacement. In this second case, `##1` is the  $\langle\textit{remaining tokens}\rangle$  in the  $\langle\textit{token list}\rangle$  and `##2` is some  $\langle\textit{ending code}\rangle$  which ends the assignment and removes the trailing tokens `#5` using some `\if_false: { \fi: }` trickery because `#5` may contain any delimiter.

If on the other hand the argument `##1` of `\__tl_replace_next:w` is delimited by the trailing  $\langle\textit{pattern}\rangle$  `#5`, then `##1` is “ $\{ \} \{ \} \langle\textit{token list}\rangle \langle\textit{delimiter}\rangle \{\langle\textit{ending code}\rangle\}$ ”,



hence `\__tl_replace_wrap:w` finds “`{ } { }` *⟨token list⟩*” as `##1` and the *⟨ending code⟩* as `##2`. It leaves the *⟨token list⟩* into the assignment and unbraces the *⟨ending code⟩* which removes what remains (essentially the *⟨delimiter⟩* and *⟨replacement⟩*).

```

2890 \cs_new_protected:Npn \__tl_replace_auxii:nNNNnn #1#2#3#4#5#6
2891 {
2892   \group_align_safe_begin:
2893   \cs_set:Npn \__tl_replace_wrap:w ##1 #1 ##2
2894     { \exp_not:o { \use_none:nn ##1 } ##2 }
2895   \cs_set:Npx \__tl_replace_next:w ##1 #5
2896     {
2897       \exp_not:N \__tl_replace_wrap:w ##1
2898       \exp_not:n { #1 }
2899       \exp_not:n { \exp_not:n {#6} }
2900       \exp_not:n { #2 { } { } }
2901     }
2902   #3 #4
2903   {
2904     \exp_after:wN \__tl_replace_next:w
2905     \exp_after:wN { \exp_after:wN }
2906     \exp_after:wN { \exp_after:wN }
2907     #4
2908     #1
2909     {
2910       \if_false: { \fi: }
2911       \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:
2912     }
2913     #5
2914   }
2915   \group_align_safe_end:
2916 }
2917 \cs_new_eq:NN \__tl_replace_wrap:w ?
2918 \cs_new_eq:NN \__tl_replace_next:w ?

```

(End definition for `\__tl_replace:NnNNNnn` and others.)

```

\tl_remove_once:Nn Removal is just a special case of replacement.
\tl_remove_once:cn 2919 \cs_new_protected:Npn \tl_remove_once:Nn #1#2
\tl_gremove_once:Nn 2920 { \tl_replace_once:Nnn #1 {#2} { } }
\tl_gremove_once:cn 2921 \cs_new_protected:Npn \tl_gremove_once:Nn #1#2
2922 { \tl_greplace_once:Nnn #1 {#2} { } }
2923 \cs_generate_variant:Nn \tl_remove_once:Nn { c }
2924 \cs_generate_variant:Nn \tl_gremove_once:Nn { c }

```

(End definition for `\tl_remove_once:Nn` and `\tl_gremove_once:Nn`. These functions are documented on page 36.)

```

\tl_remove_all:Nn Removal is just a special case of replacement.
\tl_remove_all:cn 2925 \cs_new_protected:Npn \tl_remove_all:Nn #1#2
\tl_gremove_all:Nn 2926 { \tl_replace_all:Nnn #1 {#2} { } }
\tl_gremove_all:cn 2927 \cs_new_protected:Npn \tl_gremove_all:Nn #1#2
2928 { \tl_greplace_all:Nnn #1 {#2} { } }
2929 \cs_generate_variant:Nn \tl_remove_all:Nn { c }
2930 \cs_generate_variant:Nn \tl_gremove_all:Nn { c }

```

(End definition for `\tl_remove_all:Nn` and `\tl_gremove_all:Nn`. These functions are documented on page 36.)

## 5.6 Token list conditionals

`\tl_if_blank_p:n` TeX skips spaces when reading a non-delimited arguments. Thus, a *token list* is blank if and only if `\use_none:n <token list> ?` is empty after one expansion. The auxiliary `\__tl_if_empty_return:o` is a fast emptiness test, converting its argument to a string (after one expansion) and using the test `\if_meaning:w \q_nil ... \q_nil`.

`\tl_if_blank_p:V`

`\tl_if_blank_p:o`

`\tl_if_blank:nTF`

`\tl_if_blank:VTF`

`\tl_if_blank:oTF`

`\__tl_if_blank_p:NNw`

```

2931 \prg_new_conditional:Npnn \tl_if_blank:n #1 { p , T , F , TF }
2932 { \__tl_if_empty_return:o { \use_none:n #1 ? } }
2933 \cs_generate_variant:Nn \tl_if_blank_p:n { V }
2934 \cs_generate_variant:Nn \tl_if_blank:nT { V }
2935 \cs_generate_variant:Nn \tl_if_blank:nF { V }
2936 \cs_generate_variant:Nn \tl_if_blank:nTF { V }
2937 \cs_generate_variant:Nn \tl_if_blank_p:n { o }
2938 \cs_generate_variant:Nn \tl_if_blank:nT { o }
2939 \cs_generate_variant:Nn \tl_if_blank:nF { o }
2940 \cs_generate_variant:Nn \tl_if_blank:nTF { o }

```

(End definition for `\tl_if_blank:nTF` and `\__tl_if_blank_p:NNw`. These functions are documented on page 37.)

`\tl_if_empty_p:N` These functions check whether the token list in the argument is empty and execute the proper code from their argument(s).

`\tl_if_empty_p:c`

`\tl_if_empty:nTF`

`\tl_if_empty:cTF`

```

2941 \prg_new_conditional:Npnn \tl_if_empty:N #1 { p , T , F , TF }
2942 {
2943   \if_meaning:w #1 \c_empty_tl
2944   \prg_return_true:
2945   \else:
2946     \prg_return_false:
2947   \fi:
2948 }
2949 \cs_generate_variant:Nn \tl_if_empty_p:N { c }
2950 \cs_generate_variant:Nn \tl_if_empty:NT { c }
2951 \cs_generate_variant:Nn \tl_if_empty:NF { c }
2952 \cs_generate_variant:Nn \tl_if_empty:NTF { c }

```

(End definition for `\tl_if_empty:NTF`. This function is documented on page 38.)

`\tl_if_empty_p:n` Convert the argument to a string: this is empty if and only if the argument is. Then `\if_meaning:w \q_nil ... \q_nil` is true if and only if the string ... is empty. It could be tempting to use `\if_meaning:w \q_nil #1 \q_nil` directly. This fails on a token list starting with `\q_nil` of course but more troubling is the case where argument is a complete conditional such as `\if_true: a \else: b \fi:` because then `\if_true:` is used by `\if_meaning:w`, the test turns out false, the `\else:` executes the false branch, the `\fi:` ends it and the `\q_nil` at the end starts executing...

`\tl_if_empty_p:V`

`\tl_if_empty:nTF`

`\tl_if_empty:VTF`

```

2953 \prg_new_conditional:Npnn \tl_if_empty:n #1 { p , TF , T , F }
2954 {
2955   \exp_after:wN \if_meaning:w \exp_after:wN \q_nil
2956   \tl_to_str:n {#1} \q_nil
2957   \prg_return_true:
2958   \else:
2959     \prg_return_false:
2960   \fi:
2961 }
2962 \cs_generate_variant:Nn \tl_if_empty_p:n { V }

```

```

2963 \cs_generate_variant:Nn \tl_if_empty:nTF { V }
2964 \cs_generate_variant:Nn \tl_if_empty:nT { V }
2965 \cs_generate_variant:Nn \tl_if_empty:nF { V }

```

(End definition for `\tl_if_empty:nTF`. This function is documented on page 38.)

`\tl_if_empty_p:o` The auxiliary function `\__tl_if_empty_return:o` is for use in various token list conditionals which reduce to testing if a given token list is empty after applying a simple function to it. The test for emptiness is based on `\tl_if_empty:nTF`, but the expansion is hard-coded for efficiency, as this auxiliary function is used in many places. Note that this works because `\etex_detokenize:D` expands tokens that follow until reading a catcode 1 (begin-group) token.

```

2966 \cs_new:Npn \__tl_if_empty_return:o #1
2967 {
2968   \exp_after:wN \if_meaning:w \exp_after:wN \q_nil
2969   \etex_detokenize:D \exp_after:wN {#1} \q_nil
2970   \prg_return_true:
2971   \else:
2972     \prg_return_false:
2973   \fi:
2974 }
2975 \prg_new_conditional:Npnn \tl_if_empty:o #1 { p , TF , T , F }
2976 { \__tl_if_empty_return:o {#1} }

```

(End definition for `\tl_if_empty:oTF` and `\__tl_if_empty_return:o`. These functions are documented on page 38.)

`\tl_if_eq_p:NN` Returns `\c_true_bool` if and only if the two token list variables are equal.

```

\tl_if_eq_p:Nc 2977 \prg_new_conditional:Npnn \tl_if_eq:NN #1#2 { p , T , F , TF }
\tl_if_eq_p:cN 2978 {
\tl_if_eq_p:cc 2979   \if_meaning:w #1 #2
\tl_if_eq:NNTF 2980   \prg_return_true:
\tl_if_eq:NcTF 2981   \else:
\tl_if_eq:cNTF 2982   \prg_return_false:
\tl_if_eq:ccTF 2983   \fi:
2984 }
2985 \cs_generate_variant:Nn \tl_if_eq_p:NN { Nc , c , cc }
2986 \cs_generate_variant:Nn \tl_if_eq:NNTF { Nc , c , cc }
2987 \cs_generate_variant:Nn \tl_if_eq:NNT { Nc , c , cc }
2988 \cs_generate_variant:Nn \tl_if_eq:NNF { Nc , c , cc }

```

(End definition for `\tl_if_eq:NNTF`. This function is documented on page 38.)

`\tl_if_eq:nnTF` A simple store and compare routine.

```

\l__tl_internal_a_tl 2989 \prg_new_protected_conditional:Npnn \tl_if_eq:nn #1#2 { T , F , TF }
\l__tl_internal_b_tl 2990 {
2991   \group_begin:
2992     \tl_set:Nn \l__tl_internal_a_tl {#1}
2993     \tl_set:Nn \l__tl_internal_b_tl {#2}
2994     \if_meaning:w \l__tl_internal_a_tl \l__tl_internal_b_tl
2995     \group_end:
2996     \prg_return_true:
2997   \else:
2998     \group_end:

```

```

2999         \prg_return_false:
3000     \fi:
3001 }
3002 \tl_new:N \l__tl_internal_a_tl
3003 \tl_new:N \l__tl_internal_b_tl

```

(End definition for `\tl_if_eq:nnTF`, `\l__tl_internal_a_tl`, and `\l__tl_internal_b_tl`. These functions are documented on page 38.)

**`\tl_if_in:NnTF`** See `\tl_if_in:nnTF` for further comments. Here we simply expand the token list variable `\tl_if_in:cnTF` and pass it to `\tl_if_in:nnTF`.

```

3004 \cs_new_protected:Npn \tl_if_in:NnT { \exp_args:No \tl_if_in:nnT }
3005 \cs_new_protected:Npn \tl_if_in:NnF { \exp_args:No \tl_if_in:nnF }
3006 \cs_new_protected:Npn \tl_if_in:NnTF { \exp_args:No \tl_if_in:nnTF }
3007 \cs_generate_variant:Nn \tl_if_in:NnT { c }
3008 \cs_generate_variant:Nn \tl_if_in:NnF { c }
3009 \cs_generate_variant:Nn \tl_if_in:NnTF { c }

```

(End definition for `\tl_if_in:NnTF`. This function is documented on page 38.)

**`\tl_if_in:nnTF`** Once more, the test relies on the emptiness test for robustness. The function `\__tl_tmp:w` removes tokens until the first occurrence of `#2`. If this does not appear in `#1`, then the final `#2` is removed, leaving an empty token list. Otherwise some tokens remain, and the test is false. See `\tl_if_empty:nTF` for details on the emptiness test.

Treating correctly cases like `\tl_if_in:nnTF {a state}{states}`, where `#1#2` contains `#2` before the end, requires special care. To cater for this case, we insert `{ }{ }` between the two token lists. This marker may not appear in `#2` because of  $\TeX$  limitations on what can delimit a parameter, hence we are safe. Using two brace groups makes the test work also for empty arguments. The `\if_false:` constructions are a faster way to do `\group_align_safe_begin:` and `\group_align_safe_end:`.

```

3010 \prg_new_protected_conditional:Npnn \tl_if_in:nn #1#2 { T , F , TF }
3011 {
3012     \if_false: { \fi:
3013         \cs_set:Npn \__tl_tmp:w ##1 #2 { }
3014         \tl_if_empty:oTF { \__tl_tmp:w #1 {} {} #2 }
3015         { \prg_return_false: } { \prg_return_true: }
3016     \if_false: } \fi:
3017 }
3018 \cs_generate_variant:Nn \tl_if_in:nnT { V , o , no }
3019 \cs_generate_variant:Nn \tl_if_in:nnF { V , o , no }
3020 \cs_generate_variant:Nn \tl_if_in:nnTF { V , o , no }

```

(End definition for `\tl_if_in:nnTF`. This function is documented on page 38.)

**`\tl_if_single_p:N`** Expand the token list and feed it to `\tl_if_single:n`.

**`\tl_if_single:NnTF`**

```

3021 \cs_new:Npn \tl_if_single_p:N { \exp_args:No \tl_if_single_p:n }
3022 \cs_new:Npn \tl_if_single:NnT { \exp_args:No \tl_if_single:nT }
3023 \cs_new:Npn \tl_if_single:NnF { \exp_args:No \tl_if_single:nF }
3024 \cs_new:Npn \tl_if_single:NnTF { \exp_args:No \tl_if_single:nTF }

```

(End definition for `\tl_if_single:NnTF`. This function is documented on page 38.)

`\tl_if_single_p:n` This test is similar to `\tl_if_empty:nTF`. Expanding `\use_none:nn #1 ??` once yields an empty result if #1 is blank, a single ? if #1 has a single item, and otherwise yields some tokens ending with ??. Then, `\tl_to_str:n` makes sure there are no odd category codes.

`\tl_if_single:nTF` An earlier version would compare the result to a single ? using string comparison, but the Lua call is slow in LuaTeX. Instead, `\__tl_if_single:nnw` picks the second token in front of it. If #1 is empty, this token is the trailing ? and the catcode test yields `false`. If #1 has a single item, the token is ^ and the catcode test yields `true`. Otherwise, it is one of the characters resulting from `\tl_to_str:n`, and the catcode test yields `false`. Note that `\if_catcode:w` takes care of the expansions, and that `\tl_to_str:n` (the `\detokenize` primitive) actually expands tokens until finding a begin-group token.

```

3025 \prg_new_conditional:Npnn \tl_if_single:n #1 { p , T , F , TF }
3026 {
3027   \if_catcode:w ^ \exp_after:wN \__tl_if_single:nnw
3028   \tl_to_str:n \exp_after:wN { \use_none:nn #1 ?? } ^ ? \q_stop
3029   \prg_return_true:
3030   \else:
3031     \prg_return_false:
3032   \fi:
3033 }
3034 \cs_new:Npn \__tl_if_single:nnw #1#2#3 \q_stop {#2}

```

(End definition for `\tl_if_single:nTF` and `\__tl_if_single:nTF`. These functions are documented on page 39.)

`\tl_case:Nn` The aim here is to allow the case statement to be evaluated using a known number of expansion steps (two), and without needing to use an explicit “end of recursion” marker.

`\tl_case:cn` That is achieved by using the test input as the final case, as this is always true. The trick is then to tidy up the output such that the appropriate case code plus either the `true` or `false` branch code is inserted.

`\tl_case:NnTF`

`\tl_case:cnTF`

`\__tl_case:nnTF`

`\__tl_case:Nw`

```

3035 \cs_new:Npn \tl_case:Nn #1#2
3036 {
3037   \exp:w
3038   \__tl_case:NnTF #1 {#2} { } { }
3039 }
3040 \cs_new:Npn \tl_case:NnT #1#2#3
3041 {
3042   \exp:w
3043   \__tl_case:NnTF #1 {#2} {#3} { }
3044 }
3045 \cs_new:Npn \tl_case:NnF #1#2#3
3046 {
3047   \exp:w
3048   \__tl_case:NnTF #1 {#2} { } {#3}
3049 }
3050 \cs_new:Npn \tl_case:NnTF #1#2
3051 {
3052   \exp:w
3053   \__tl_case:NnTF #1 {#2}
3054 }
3055 \cs_new:Npn \__tl_case:NnTF #1#2#3#4
3056 { \__tl_case:Nw #1 #2 #1 { } \q_mark {#3} \q_mark {#4} \q_stop }
3057 \cs_new:Npn \__tl_case:Nw #1#2#3
3058 {

```

```

3059 \tl_if_eq:NNTF #1 #2
3060 { \__tl_case_end:nw {#3} }
3061 { \__tl_case:Nw #1 }
3062 }
3063 \cs_generate_variant:Nn \tl_case:Nn { c }
3064 \cs_generate_variant:Nn \tl_case:NnT { c }
3065 \cs_generate_variant:Nn \tl_case:NnF { c }
3066 \cs_generate_variant:Nn \tl_case:NnTF { c }

```

To tidy up the recursion, there are two outcomes. If there was a hit to one of the cases searched for, then #1 is the code to insert, #2 is the *next* case to check on and #3 is all of the rest of the cases code. That means that #4 is the **true** branch code, and #5 tidies up the spare \q\_mark and the **false** branch. On the other hand, if none of the cases matched then we arrive here using the “termination” case of comparing the search with itself. That means that #1 is empty, #2 is the first \q\_mark and so #4 is the **false** code (the **true** code is mopped up by #3).

```

3067 \cs_new:Npn \__prg_case_end:nw #1#2#3 \q_mark #4#5 \q_stop
3068 { \exp_end: #1 #4 }
3069 \cs_new_eq:NN \__tl_case_end:nw \__prg_case_end:nw

```

(End definition for \tl\_case:NnTF and others. These functions are documented on page 39.)

## 5.7 Mapping to token lists

\tl\_map\_function:nN  
\tl\_map\_function:NN  
\tl\_map\_function:cN  
\\_\_tl\_map\_function:Nn

Expandable loop macro for token lists. These have the advantage of not needing to test if the argument is empty, because if it is, the stop marker is read immediately and the loop terminated.

```

3070 \cs_new:Npn \tl_map_function:nN #1#2
3071 {
3072   \__tl_map_function:Nn #2 #1
3073   \q_recursion_tail
3074   \__prg_break_point:Nn \tl_map_break: { }
3075 }
3076 \cs_new:Npn \tl_map_function:NN
3077 { \exp_args:No \tl_map_function:nN }
3078 \cs_new:Npn \__tl_map_function:Nn #1#2
3079 {
3080   \__quark_if_recursion_tail_break:nN {#2} \tl_map_break:
3081   #1 {#2} \__tl_map_function:Nn #1
3082 }
3083 \cs_generate_variant:Nn \tl_map_function:NN { c }

```

(End definition for \tl\_map\_function:nN, \tl\_map\_function:NN, and \\_\_tl\_map\_function:Nn. These functions are documented on page 39.)

\tl\_map\_inline:nn  
\tl\_map\_inline:Nn  
\tl\_map\_inline:cn

The inline functions are straight forward by now. We use a little trick with the counter \g\_\_prg\_map\_int to make them nestable. We can also make use of \\_\_tl\_map\_function:Nn from before.

```

3084 \cs_new_protected:Npn \tl_map_inline:nn #1#2
3085 {
3086   \int_gincr:N \g__prg_map_int
3087   \cs_gset_protected:cpn
3088   { \__prg_map_ \int_use:N \g__prg_map_int :w } ##1 {#2}
3089   \exp_args:Nc \__tl_map_function:Nn

```

```

3090     { __prg_map_ \int_use:N \g__prg_map_int :w }
3091     #1 \q_recursion_tail
3092     \__prg_break_point:Nn \tl_map_break: { \int_gdecr:N \g__prg_map_int }
3093   }
3094   \cs_new_protected:Npn \tl_map_inline:Nn
3095     { \exp_args:No \tl_map_inline:nn }
3096   \cs_generate_variant:Nn \tl_map_inline:Nn { c }

```

(End definition for `\tl_map_inline:nn` and `\tl_map_inline:Nn`. These functions are documented on page 39.)

`\tl_map_variable:nNn` `\tl_map_variable:NNn` `\tl_map_variable:cNn` `\tl_map_variable:Nnn` `\tl_map_variable:nNn` `<token list>` `<temp>` `<action>` assigns `<temp>` to each element and executes `<action>`.

```

3097 \cs_new_protected:Npn \tl_map_variable:nNn #1#2#3
3098   {
3099     \__tl_map_variable:Nnn #2 {#3} #1
3100     \q_recursion_tail
3101     \__prg_break_point:Nn \tl_map_break: { }
3102   }
3103   \cs_new_protected:Npn \tl_map_variable:NNn
3104     { \exp_args:No \tl_map_variable:nNn }
3105   \cs_new_protected:Npn \__tl_map_variable:Nnn #1#2#3
3106     {
3107       \tl_set:Nn #1 {#3}
3108       \__quark_if_recursion_tail_break:NN #1 \tl_map_break:
3109       \use:n {#2}
3110       \__tl_map_variable:Nnn #1 {#2}
3111     }
3112   \cs_generate_variant:Nn \tl_map_variable:Nnn { c }

```

(End definition for `\tl_map_variable:nNn`, `\tl_map_variable:NNn`, and `\__tl_map_variable:Nnn`. These functions are documented on page 40.)

`\tl_map_break:` The break statements use the general `\__prg_map_break:Nn`.

```

3113 \cs_new:Npn \tl_map_break:
3114   { \__prg_map_break:Nn \tl_map_break: { } }
3115 \cs_new:Npn \tl_map_break:n
3116   { \__prg_map_break:Nn \tl_map_break: }

```

(End definition for `\tl_map_break:` and `\tl_map_break:n`. These functions are documented on page 40.)

## 5.8 Using token lists

`\tl_to_str:n` Another name for a primitive: defined in `l3basics`.

```

3117 \cs_generate_variant:Nn \tl_to_str:n { V }

```

(End definition for `\tl_to_str:n`. This function is documented on page 41.)

`\tl_to_str:N` These functions return the replacement text of a token list as a string.

```

3118 \cs_new:Npn \tl_to_str:N #1 { \etex_detokenize:D \exp_after:wN {#1} }
3119 \cs_generate_variant:Nn \tl_to_str:N { c }

```

(End definition for `\tl_to_str:N`. This function is documented on page 41.)

**\tl\_use:N** Token lists which are simply not defined give a clear TeX error here. No such luck for **\tl\_use:c** ones equal to `\scan_stop`: so instead a test is made and if there is an issue an error is forced.

```

3120 \cs_new:Npn \tl_use:N #1
3121 {
3122   \tl_if_exist:NTF #1 {#1}
3123   {
3124     \__msg_kernel_expandable_error:nnn
3125     { kernel } { bad-variable } {#1}
3126   }
3127 }
3128 \cs_generate_variant:Nn \tl_use:N { c }

```

(End definition for `\tl_use:N`. This function is documented on page 41.)

## 5.9 Working with the contents of token lists

**\tl\_count:n** Count number of elements within a token list or token list variable. Brace groups within the list are read as a single element. Spaces are ignored. `\__tl_count:n` grabs the element and replaces it by +1. The 0 ensures that it works on an empty list.

```

3129 \cs_new:Npn \tl_count:n #1
3130 {
3131   \int_eval:n
3132   { 0 \tl_map_function:nN {#1} \__tl_count:n }
3133 }
3134 \cs_new:Npn \tl_count:N #1
3135 {
3136   \int_eval:n
3137   { 0 \tl_map_function:NN #1 \__tl_count:n }
3138 }
3139 \cs_new:Npn \__tl_count:n #1 { + 1 }
3140 \cs_generate_variant:Nn \tl_count:n { V , o }
3141 \cs_generate_variant:Nn \tl_count:N { c }

```

(End definition for `\tl_count:n`, `\tl_count:N`, and `\__tl_count:n`. These functions are documented on page 41.)

**\tl\_reverse\_items:n** Reversal of a token list is done by taking one item at a time and putting it after `\q_stop`.

```

3142 \cs_new:Npn \tl_reverse_items:n #1
3143 {
3144   \__tl_reverse_items:nwNwn #1 ?
3145   \q_mark \__tl_reverse_items:nwNwn
3146   \q_mark \__tl_reverse_items:wn
3147   \q_stop { }
3148 }
3149 \cs_new:Npn \__tl_reverse_items:nwNwn #1 #2 \q_mark #3 #4 \q_stop #5
3150 {
3151   #3 #2
3152   \q_mark \__tl_reverse_items:nwNwn
3153   \q_mark \__tl_reverse_items:wn
3154   \q_stop { {#1} #5 }
3155 }
3156 \cs_new:Npn \__tl_reverse_items:wn #1 \q_stop #2
3157 { \exp_not:o { \use_none:nn #2 } }

```



(End definition for `\tl_reverse_items:n`, `\__tl_reverse_items:nwNwn`, and `\__tl_reverse_items:wn`. These functions are documented on page 42.)

`\tl_trim_spaces:n` Trimming spaces from around the input is deferred to an internal function whose first argument is the token list to trim, augmented by an initial `\q_mark`, and whose second argument is a *<continuation>*, which receives as a braced argument `\use_none:n \q_mark` *<trimmed token list>*. In the case at hand, we take `\exp_not:o` as our continuation, so that space trimming behaves correctly within an x-type expansion.

```

3158 \cs_new:Npn \tl_trim_spaces:n #1
3159   { \__tl_trim_spaces:nn { \q_mark #1 } \exp_not:o }
3160 \cs_new_protected:Npn \tl_trim_spaces:N #1
3161   { \tl_set:Nx #1 { \exp_args:No \tl_trim_spaces:n {#1} } }
3162 \cs_new_protected:Npn \tl_gtrim_spaces:N #1
3163   { \tl_gset:Nx #1 { \exp_args:No \tl_trim_spaces:n {#1} } }
3164 \cs_generate_variant:Nn \tl_trim_spaces:N { c }
3165 \cs_generate_variant:Nn \tl_gtrim_spaces:N { c }

```

(End definition for `\tl_trim_spaces:n`, `\tl_trim_spaces:N`, and `\tl_gtrim_spaces:N`. These functions are documented on page 42.)

`\__tl_trim_spaces:nn` Trimming spaces from around the input is done using delimited arguments and quarks, and to get spaces at odd places in the definitions, we nest those in `\__tl_tmp:w`, which then receives a single space as its argument: `#1` is `␣`. Removing leading spaces is done with `\__tl_trim_spaces_auxi:w`, which loops until `\q_mark␣` matches the end of the token list: then `##1` is the token list and `##3` is `\__tl_trim_spaces_auxii:w`. This hands the relevant tokens to the loop `\__tl_trim_spaces_auxiii:w`, responsible for trimming trailing spaces. The end is reached when `␣ \q_nil` matches the one present in the definition of `\tl_trim_spaces:n`. Then `\__tl_trim_spaces_auxiv:w` puts the token list into a group, with `\use_none:n` placed there to gobble a lingering `\q_mark`, and feeds this to the *<continuation>*.

```

3166 \cs_set:Npn \__tl_tmp:w #1
3167   {
3168     \cs_new:Npn \__tl_trim_spaces:nn ##1
3169       {
3170         \__tl_trim_spaces_auxi:w
3171         ##1
3172         \q_nil
3173         \q_mark #1 { }
3174         \q_mark \__tl_trim_spaces_auxii:w
3175         \__tl_trim_spaces_auxiii:w
3176         #1 \q_nil
3177         \__tl_trim_spaces_auxiv:w
3178         \q_stop
3179       }
3180     \cs_new:Npn \__tl_trim_spaces_auxi:w ##1 \q_mark #1 ##2 \q_mark ##3
3181       {
3182         ##3
3183         \__tl_trim_spaces_auxi:w
3184         \q_mark
3185         ##2
3186         \q_mark #1 {##1}
3187       }
3188     \cs_new:Npn \__tl_trim_spaces_auxii:w

```

```

3189     \_tl_trim_spaces_auxi:w \q_mark \q_mark ##1
3190     {
3191     \_tl_trim_spaces_auxiii:w
3192     ##1
3193     }
3194     \cs_new:Npn \_tl_trim_spaces_auxiii:w ##1 #1 \q_nil ##2
3195     {
3196     ##2
3197     ##1 \q_nil
3198     \_tl_trim_spaces_auxiii:w
3199     }
3200     \cs_new:Npn \_tl_trim_spaces_auxiv:w ##1 \q_nil ##2 \q_stop ##3
3201     { ##3 { \use_none:n ##1 } }
3202   }
3203   \_tl_tmp:w { ~ }

```

(End definition for `\_tl_trim_spaces:nn` and others.)

`\tl_sort:Nn` Implemented in `l3sort`.

`\tl_sort:cn`

`\tl_gsort:Nn` (End definition for `\tl_sort:Nn`, `\tl_gsort:Nn`, and `\tl_sort:nN`. These functions are documented on page 43.)

`\tl_gsort:cn`

`\tl_sort:nN`

## 5.10 Token by token changes

`\q__tl_act_mark` The `\tl_act` functions may be applied to any token list. Hence, we use two private quarks, to allow any token, even quarks, in the token list. Only `\q__tl_act_mark` and `\q__tl_act_stop` may not appear in the token lists manipulated by `\_tl_act:NNNnn` functions. The quarks are effectively defined in `l3quark`.

`\q__tl_act_stop`

(End definition for `\q__tl_act_mark` and `\q__tl_act_stop`.)

`\_tl_act:NNNnn`

`\_tl_act_output:n`

`\_tl_act_reverse_output:n`

`\_tl_act_loop:w`

`\_tl_act_normal:NwnNNN`

`\_tl_act_group:nwnNNN`

`\_tl_act_space:wwnNNN`

`\_tl_act_end:w`

To help control the expansion, `\_tl_act:NNNnn` should always be preceded by `\exp:w` and ends by producing `\exp_end:` once the result has been obtained. Then loop over tokens, groups, and spaces in #5. The marker `\q__tl_act_mark` is used both to avoid losing outer braces and to detect the end of the token list more easily. The result is stored as an argument for the dummy function `\_tl_act_result:n`.

```

3204 \cs_new:Npn \_tl_act:NNNnn #1#2#3#4#5
3205 {
3206   \group_align_safe_begin:
3207   \_tl_act_loop:w #5 \q__tl_act_mark \q__tl_act_stop
3208   {#4} #1 #2 #3
3209   \_tl_act_result:n { }
3210 }

```

In the loop, we check how the token list begins and act accordingly. In the “normal” case, we may have reached `\q__tl_act_mark`, the end of the list. Then leave `\exp_end:` and the result in the input stream, to terminate the expansion of `\exp:w`. Otherwise, apply the relevant function to the “arguments”, #3 and to the head of the token list. Then repeat the loop. The scheme is the same if the token list starts with a group or with a space. Some extra work is needed to make `\_tl_act_space:wwnNNN` gobble the space.

```

3211 \cs_new:Npn \_tl_act_loop:w #1 \q__tl_act_stop
3212 {
3213   \tl_if_head_is_N_type:nTF {#1}

```

```

3214     { \_tl_act_normal:NwnNNN }
3215     {
3216         \tl_if_head_is_group:nTF {#1}
3217         { \_tl_act_group:nwnNNN }
3218         { \_tl_act_space:wnnNNN }
3219     }
3220     #1 \q__tl_act_stop
3221 }
3222 \cs_new:Npn \_tl_act_normal:NwnNNN #1 #2 \q__tl_act_stop #3#4
3223 {
3224     \if_meaning:w \q__tl_act_mark #1
3225     \exp_after:wN \_tl_act_end:wn
3226     \fi:
3227     #4 {#3} #1
3228     \_tl_act_loop:w #2 \q__tl_act_stop
3229     {#3} #4
3230 }
3231 \cs_new:Npn \_tl_act_end:wn #1 \_tl_act_result:n #2
3232 { \group_align_safe_end: \exp_end: #2 }
3233 \cs_new:Npn \_tl_act_group:nwnNNN #1 #2 \q__tl_act_stop #3#4#5
3234 {
3235     #5 {#3} {#1}
3236     \_tl_act_loop:w #2 \q__tl_act_stop
3237     {#3} #4 #5
3238 }
3239 \exp_last_unbraced:NNo
3240 \cs_new:Npn \_tl_act_space:wnnNNN \c_space_tl #1 \q__tl_act_stop #2#3#4#5
3241 {
3242     #5 {#2}
3243     \_tl_act_loop:w #1 \q__tl_act_stop
3244     {#2} #3 #4 #5
3245 }

```

Typically, the output is done to the right of what was already output, using `\_tl_act_output:n`, but for the `\_tl_act_reverse` functions, it should be done to the left.

```

3246 \cs_new:Npn \_tl_act_output:n #1 #2 \_tl_act_result:n #3
3247 { #2 \_tl_act_result:n { #3 #1 } }
3248 \cs_new:Npn \_tl_act_reverse_output:n #1 #2 \_tl_act_result:n #3
3249 { #2 \_tl_act_result:n { #1 #3 } }

```

(End definition for `\_tl_act:NNNnn` and others.)

**\tl\_reverse:n** The goal here is to reverse without losing spaces nor braces. This is done using the  
**\tl\_reverse:o** general internal function `\_tl_act:NNNnn`. Spaces and “normal” tokens are output on  
**\tl\_reverse:V** the left of the current output. Grouped tokens are output to the left but without any  
`\_tl_reverse_normal:nN` reversal within the group. All of the internal functions here drop one argument: this is  
`\_tl_reverse_group_preserve:nn` needed by `\_tl_act:NNNnn` when changing case (to record which direction the change  
`\_tl_reverse_space:n` is in), but not when reversing the tokens.

```

3250 \cs_new:Npn \tl_reverse:n #1
3251 {
3252     \etex_unexpanded:D \exp_after:wN
3253     {
3254         \exp:w
3255         \_tl_act:NNNnn

```

```

3256         \tl_reverse_normal:nN
3257         \tl_reverse_group_preserve:nn
3258         \tl_reverse_space:n
3259         { }
3260         {#1}
3261     }
3262 }
3263 \cs_generate_variant:Nn \tl_reverse:n { o , V }
3264 \cs_new:Npn \tl_reverse_normal:nN #1#2
3265 { \tl_act_reverse_output:n {#2} }
3266 \cs_new:Npn \tl_reverse_group_preserve:nn #1#2
3267 { \tl_act_reverse_output:n { {#2} } }
3268 \cs_new:Npn \tl_reverse_space:n #1
3269 { \tl_act_reverse_output:n { ~ } }

```

(End definition for `\tl_reverse:n` and others. These functions are documented on page 42.)

```

\tl_reverse:N This reverses the list, leaving \exp_stop_f: in front, which stops the f-expansion.
\tl_reverse:c 3270 \cs_new_protected:Npn \tl_reverse:N #1
\tl_greverse:N 3271 { \tl_set:Nx #1 { \exp_args:No \tl_reverse:n { #1 } } }
\tl_greverse:c 3272 \cs_new_protected:Npn \tl_greverse:N #1
3273 { \tl_gset:Nx #1 { \exp_args:No \tl_reverse:n { #1 } } }
3274 \cs_generate_variant:Nn \tl_reverse:N { c }
3275 \cs_generate_variant:Nn \tl_greverse:N { c }

```

(End definition for `\tl_reverse:N` and `\tl_greverse:N`. These functions are documented on page 42.)

## 5.11 The first token from a token list

```

\tl_head:N Finding the head of a token list expandably always strips braces, which is fine as this
\tl_head:n is consistent with for example mapping to a list. The empty brace groups in \tl_
\tl_head:V head:n ensure that a blank argument gives an empty result. The result is returned
\tl_head:v within the \unexpanded primitive. The approach here is to use \if_false: to allow
\tl_head:f us to use } as the closing delimiter: this is the only safe choice, as any other token
\__tl_head_auxi:nw would not be able to parse it's own code. Using a marker, we can see if what we are
\__tl_head_auxii:n grabbing is exactly the marker, or there is anything else to deal with. Is there is, there
\tl_head:w is a loop. If not, tidy up and leave the item in the output stream. More detail in
\tl_tail:N http://tex.stackexchange.com/a/70168.
\tl_tail:n 3276 \cs_new:Npn \tl_head:n #1
\tl_tail:V 3277 {
\tl_tail:v 3278 \etex_unexpanded:D
\tl_tail:f 3279 \if_false: { \fi: \__tl_head_auxi:nw #1 { } \q_stop }
3280 }
3281 \cs_new:Npn \__tl_head_auxi:nw #1#2 \q_stop
3282 {
3283 \exp_after:wN \__tl_head_auxii:n \exp_after:wN {
3284 \if_false: } \fi: {#1}
3285 }
3286 \cs_new:Npn \__tl_head_auxii:n #1
3287 {
3288 \exp_after:wN \if_meaning:w \exp_after:wN \q_nil
3289 \tl_to_str:n \exp_after:wN { \use_none:n #1 } \q_nil
3290 \exp_after:wN \use_i:nn

```

```

3291 \else:
3292 \exp_after:wN \use_ii:nn
3293 \fi:
3294 {#1}
3295 { \if_false: { \fi: \_tl\_head\_auxi:nw #1 } }
3296 }
3297 \cs_generate_variant:Nn \tl\_head:n { V , v , f }
3298 \cs_new:Npn \tl\_head:w #1#2 \q_stop {#1}
3299 \cs_new:Npn \tl\_head:N { \exp_args:No \tl\_head:n }

```

To correctly leave the tail of a token list, it's important *not* to absorb any of the tail part as an argument. For example, the simple definition

```

\cs_new:Npn \tl\_tail:n #1 { \tl\_tail:w #1 \q_stop }
\cs_new:Npn \tl\_tail:w #1#2 \q_stop

```

would give the wrong result for `\tl\_tail:n { a { bc } }` (the braces would be stripped). Thus the only safe way to proceed is to first check that there is an item to grab (*i.e.* that the argument is not blank) and assuming there is to dispose of the first item. As with `\tl\_head:n`, the result is protected from further expansion by `\unexpanded`. While we could optimise the test here, this would leave some tokens “banned” in the input, which we do not have with this definition.

```

3300 \cs_new:Npn \tl\_tail:n #1
3301 {
3302 \etex_unexpanded:D
3303 \tl\_if_blank:nTF {#1}
3304 { { } }
3305 { \exp_after:wN { \use_none:n #1 } }
3306 }
3307 \cs_generate_variant:Nn \tl\_tail:n { V , v , f }
3308 \cs_new:Npn \tl\_tail:N { \exp_args:No \tl\_tail:n }

```

(End definition for `\tl\_head:N` and others. These functions are documented on page 43.)

```

\tl\_if\_head\_eq\_meaning\_p:nN
\tl\_if\_head\_eq\_meaning:nNTF
\tl\_if\_head\_eq\_charcode\_p:nN
\tl\_if\_head\_eq\_charcode:nNTF
\tl\_if\_head\_eq\_charcode\_p:fN
\tl\_if\_head\_eq\_charcode:fNNTF
\tl\_if\_head\_eq\_catcode\_p:nN
\tl\_if\_head\_eq\_catcode:nNNTF

```

Accessing the first token of a token list is tricky in three cases: when it has category code 1 (begin-group token), when it is an explicit space, with category code 10 and character code 32, or when the token list is empty (obviously).

Forgetting temporarily about this issue we would use the following test in `\tl\_if\_head\_eq\_charcode:nN`. Here, `\tl\_head:w` yields the first token of the token list, then passed to `\exp_not:N`.

```

\tl\_if\_charcode:w
\exp_after:wN \exp_not:N \tl\_head:w #1 \q_nil \q_stop
\exp_not:N #2

```

The two first special cases are detected by testing if the token list starts with an N-type token (the extra ? sends empty token lists to the **true** branch of this test). In those cases, the first token is a character, and since we only care about its character code, we can use `\str\_head:n` to access it (this works even if it is a space character). An empty argument results in `\tl\_head:w` leaving two tokens: ? which is taken in the `\tl\_if\_charcode:w` test, and `\use\_none:nn`, which ensures that `\prg\_return\_false:` is returned regardless of whether the charcode test was true or false.

```

3309 \prg_new_conditional:Npnn \tl\_if\_head\_eq\_charcode:nN #1#2 { p , T , F , TF }
3310 {

```

```

3311 \if_charcode:w
3312 \exp_not:N #2
3313 \tl_if_head_is_N_type:nTF { #1 ? }
3314 {
3315     \exp_after:wN \exp_not:N
3316     \tl_head:w #1 { ? \use_none:nn } \q_stop
3317 }
3318 { \str_head:n {#1} }
3319 \prg_return_true:
3320 \else:
3321 \prg_return_false:
3322 \fi:
3323 }
3324 \cs_generate_variant:Nn \tl_if_head_eq_charcode_p:nN { f }
3325 \cs_generate_variant:Nn \tl_if_head_eq_charcode:nNTF { f }
3326 \cs_generate_variant:Nn \tl_if_head_eq_charcode:nNT { f }
3327 \cs_generate_variant:Nn \tl_if_head_eq_charcode:nNF { f }

```

For `\tl_if_head_eq_catcode:nN`, again we detect special cases with a `\tl_if_head_is_N_type:n`. Then we need to test if the first token is a begin-group token or an explicit space token, and produce the relevant token, either `\c_group_begin_token` or `\c_space_token`. Again, for an empty argument, a hack is used, removing `\prg_return_true:` and `\else:` with `\use_none:nn` in case the catcode test with the (arbitrarily chosen) `?` is true.

```

3328 \prg_new_conditional:Npnn \tl_if_head_eq_catcode:nN #1 #2 { p , T , F , TF }
3329 {
3330     \if_catcode:w
3331     \exp_not:N #2
3332     \tl_if_head_is_N_type:nTF { #1 ? }
3333     {
3334         \exp_after:wN \exp_not:N
3335         \tl_head:w #1 { ? \use_none:nn } \q_stop
3336     }
3337     {
3338         \tl_if_head_is_group:nTF {#1}
3339         { \c_group_begin_token }
3340         { \c_space_token }
3341     }
3342     \prg_return_true:
3343 \else:
3344     \prg_return_false:
3345 \fi:
3346 }

```

For `\tl_if_head_eq_meaning:nN`, again, detect special cases. In the normal case, use `\tl_head:w`, with no `\exp_not:N` this time, since `\if_meaning:w` causes no expansion. With an empty argument, the test is true, and `\use_none:nnn` removes `#2` and the usual `\prg_return_true:` and `\else:`. In the special cases, we know that the first token is a character, hence `\if_charcode:w` and `\if_catcode:w` together are enough. We combine them in some order, hopefully faster than the reverse. Tests are not nested because the arguments may contain unmatched primitive conditionals.

```

3347 \prg_new_conditional:Npnn \tl_if_head_eq_meaning:nN #1#2 { p , T , F , TF }
3348 {
3349     \tl_if_head_is_N_type:nTF { #1 ? }

```

```

3350     { \_tl\_if\_head\_eq\_meaning\_normal:nN }
3351     { \_tl\_if\_head\_eq\_meaning\_special:nN }
3352     {#1} #2
3353   }
3354 \cs\_new:Npn \_tl\_if\_head\_eq\_meaning\_normal:nN #1 #2
3355 {
3356   \exp\_after:wN \if\_meaning:w
3357   \tl\_head:w #1 { ?? \use\_none:nnn } \q\_stop #2
3358   \prg\_return\_true:
3359   \else:
3360   \prg\_return\_false:
3361   \fi:
3362 }
3363 \cs\_new:Npn \_tl\_if\_head\_eq\_meaning\_special:nN #1 #2
3364 {
3365   \if\_charcode:w \str\_head:n {#1} \exp\_not:N #2
3366   \exp\_after:wN \use:n
3367   \else:
3368   \prg\_return\_false:
3369   \exp\_after:wN \use\_none:n
3370   \fi:
3371   {
3372     \if\_catcode:w \exp\_not:N #2
3373     \tl\_if\_head\_is\_group:nTF {#1}
3374     { \c\_group\_begin\_token }
3375     { \c\_space\_token }
3376     \prg\_return\_true:
3377     \else:
3378     \prg\_return\_false:
3379     \fi:
3380   }
3381 }

```

(End definition for `\tl\_if\_head\_eq\_meaning:nNTF` and others. These functions are documented on page 44.)

`\tl\_if\_head\_is\_N\_type\_p:n`  
`\tl\_if\_head\_is\_N\_type\_nTF`  
`\_tl\_if\_head\_is\_N\_type:w`

A token list can be empty, can start with an explicit space character (catcode 10 and charcode 32), can start with a begin-group token (catcode 1), or start with an N-type argument. In the first two cases, the line involving `\_tl\_if\_head\_is\_N\_type:w` produces `~` (and otherwise nothing). In the third case (begin-group token), the lines involving `\exp\_after:wN` produce a single closing brace. The category code test is thus true exactly in the fourth case, which is what we want. One cannot optimize by moving one of the `*` to the beginning: if `#1` contains primitive conditionals, all of its occurrences must be dealt with before the `\if\_catcode:w` tries to skip the `true` branch of the conditional.

```

3382 \prg\_new\_conditional:Npnn \tl\_if\_head\_is\_N\_type:n #1 { p , T , F , TF }
3383 {
3384   \if\_catcode:w
3385   \if\_false: { \fi: \_tl\_if\_head\_is\_N\_type:w ? #1 ~ }
3386   \exp\_after:wN \use\_none:n
3387   \exp\_after:wN { \exp\_after:wN { \token\_to\_str:N #1 ? } }
3388   * *
3389   \prg\_return\_true:
3390   \else:
3391   \prg\_return\_false:

```

```

3392     \fi:
3393   }
3394   \cs_new:Npn \__tl_if_head_is_N_type:w #1 ~
3395   {
3396     \tl_if_empty:oTF { \use_none:n #1 } { ^ } { }
3397     \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:
3398   }

```

(End definition for `\tl_if_head_is_N_type:nTF` and `\__tl_if_head_is_N_type:w`. These functions are documented on page 45.)

`\tl_if_head_is_group_p:n` Pass the first token of #1 through `\token_to_str:N`, then check for the brace balance.  
`\tl_if_head_is_group:nTF` The extra ? caters for an empty argument.<sup>8</sup>

```

3399   \prg_new_conditional:Npnn \tl_if_head_is_group:n #1 { p , T , F , TF }
3400   {
3401     \if_catcode:w
3402       \exp_after:wN \use_none:n
3403       \exp_after:wN { \exp_after:wN { \token_to_str:N #1 ? } }
3404     * *
3405     \prg_return_false:
3406   \else:
3407     \prg_return_true:
3408   \fi:
3409 }

```

(End definition for `\tl_if_head_is_group:nTF`. This function is documented on page 45.)

`\tl_if_head_is_space_p:n` The auxiliary’s argument is all that is before the first explicit space in `?#1?~`. If that  
`\tl_if_head_is_space:nTF` is a single ? the test yields true. Otherwise, that is more than one token, and the  
`\__tl_if_head_is_space:w` test yields false. The work is done within braces (with an `\if_false: { \fi: ... }` construction) both to hide potential alignment tab characters from T<sub>E</sub>X in a table, and to allow for removing what remains of the token list after its first space. The `\exp:w` and `\exp_end:` ensure that the result of a single step of expansion directly yields a balanced token list (no trailing closing brace).

```

3410   \prg_new_conditional:Npnn \tl_if_head_is_space:n #1 { p , T , F , TF }
3411   {
3412     \exp:w \if_false: { \fi:
3413       \__tl_if_head_is_space:w ? #1 ? ~ }
3414   }
3415   \cs_new:Npn \__tl_if_head_is_space:w #1 ~
3416   {
3417     \tl_if_empty:oTF { \use_none:n #1 }
3418     { \exp_after:wN \exp_end: \exp_after:wN \prg_return_true: }
3419     { \exp_after:wN \exp_end: \exp_after:wN \prg_return_false: }
3420     \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:
3421   }

```

(End definition for `\tl_if_head_is_space:nTF` and `\__tl_if_head_is_space:w`. These functions are documented on page 45.)

---

<sup>8</sup>Bruno: this could be made faster, but we don’t: if we hope to ever have an e-type argument, we need all brace “tricks” to happen in one step of expansion, keeping the token list brace balanced at all times.



## 5.12 Using a single item

`\tl_item:nn` The idea here is to find the offset of the item from the left, then use a loop to grab the correct item. If the resulting offset is too large, then `\quark_if_recursion_tail_stop:n` terminates the loop, and returns nothing at all.

`\tl_item:Nn`

`\tl_item:cn`

`\__tl_item_aux:nn`

`\__tl_item:nn`

```

3422 \cs_new:Npn \tl_item:nn #1#2
3423 {
3424   \exp_args:Nf \__tl_item:nn
3425     { \exp_args:Nf \__tl_item_aux:nn { \int_eval:n {#2} } {#1} }
3426   #1
3427   \quark_recursion_tail
3428   \__prg_break_point:
3429 }
3430 \cs_new:Npn \__tl_item_aux:nn #1#2
3431 {
3432   \int_compare:nNnTF {#1} < 0
3433     { \int_eval:n { \tl_count:n {#2} + 1 + #1 } }
3434     {#1}
3435 }
3436 \cs_new:Npn \__tl_item:nn #1#2
3437 {
3438   \__quark_if_recursion_tail_break:nN {#2} \__prg_break:
3439   \int_compare:nNnTF {#1} = 1
3440     { \__prg_break:n { \exp_not:n {#2} } }
3441     { \exp_args:Nf \__tl_item:nn { \int_eval:n { #1 - 1 } } }
3442 }
3443 \cs_new:Npn \tl_item:Nn { \exp_args:No \tl_item:nn }
3444 \cs_generate_variant:Nn \tl_item:Nn { c }

```

(End definition for `\tl_item:nn` and others. These functions are documented on page 45.)

## 5.13 Viewing token lists

`\tl_show:N` Showing token list variables is done after checking that the variable is defined (see `\__kernel_register_show:N`).

`\tl_show:c`

```

3445 \cs_new_protected:Npn \tl_show:N #1
3446 {
3447   \__msg_show_variable:NNNnn #1 \tl_if_exist:NTF ? { }
3448   { > ~ \token_to_str:N #1 = \tl_to_str:N #1 }
3449 }
3450 \cs_generate_variant:Nn \tl_show:N { c }

```

(End definition for `\tl_show:N`. This function is documented on page 45.)

`\tl_show:n` The `\__msg_show_wrap:n` internal function performs line-wrapping and shows the result using the `\etex_showtokens:D` primitive. Since `\tl_to_str:n` is expanded within the line-wrapping code, the escape character is always a backslash.

```

3451 \cs_new_protected:Npn \tl_show:n #1
3452 { \__msg_show_wrap:n { > ~ \tl_to_str:n {#1} } }

```

(End definition for `\tl_show:n`. This function is documented on page 46.)

**\tl\_log:N** Redirect output of \tl\_show:N and \tl\_show:n to the log.

```
\tl_log:c      3453 \cs_new_protected:Npn \tl_log:N
\tl_log:n      3454 { \__msg_log_next: \tl_show:N }
                3455 \cs_generate_variant:Nn \tl_log:N { c }
                3456 \cs_new_protected:Npn \tl_log:n
                3457 { \__msg_log_next: \tl_show:n }
```

(End definition for \tl\_log:N and \tl\_log:n. These functions are documented on page 46.)

## 5.14 Scratch token lists

**\g\_tmpa\_tl** Global temporary token list variables. They are supposed to be set and used immediately, with no delay between the definition and the use because you can't count on other macros not to redefine them from under you.

**\g\_tmpb\_tl**

```
3458 \tl_new:N \g_tmpa_tl
3459 \tl_new:N \g_tmpb_tl
```

(End definition for \g\_tmpa\_tl and \g\_tmpb\_tl. These variables are documented on page 46.)

**\l\_tmpa\_tl** These are local temporary token list variables. Be sure not to assume that the value you put into them will survive for long—see discussion above.

**\l\_tmpb\_tl**

```
3460 \tl_new:N \l_tmpa_tl
3461 \tl_new:N \l_tmpb_tl
```

(End definition for \l\_tmpa\_tl and \l\_tmpb\_tl. These variables are documented on page 46.)

## 5.15 Deprecated functions

**\tl\_to\_lowercase:n** For removal after 2017-12-31.

```
\tl_to_uppercase:n 3462 \cs_new_protected:Npn \tl_to_lowercase:n #1
                    3463 {
                    3464   \__msg_kernel_warning:nxxx { kernel } { deprecated-command }
                    3465   { 2017-12-31 }
                    3466   { \token_to_str:N \tl_to_lowercase:n }
                    3467   { }
                    3468   \cs_gset_eq:NN \tl_to_lowercase:n \tex_lowercase:D
                    3469   \tex_lowercase:D {#1}
                    3470 }
                    3471 \cs_new_protected:Npn \tl_to_uppercase:n #1
                    3472 {
                    3473   \__msg_kernel_warning:nxxx { kernel } { deprecated-command }
                    3474   { 2017-12-31 }
                    3475   { \token_to_str:N \tl_to_uppercase:n }
                    3476   { }
                    3477   \cs_gset_eq:NN \tl_to_uppercase:n \tex_uppercase:D
                    3478   \tex_uppercase:D {#1}
                    3479 }
```

(End definition for \tl\_to\_lowercase:n and \tl\_to\_uppercase:n.)

```
3480 </initex | package>
```

## 6 l3str implementation

3481  $\langle *initex | package \rangle$

3482  $\langle @@=str \rangle$

### 6.1 Creating and setting string variables

**$\backslash str\_new:N$**  A string is simply a token list. The full mapping system isn't set up yet so do things by hand.

**$\backslash str\_new:c$**

**$\backslash str\_use:N$**  3483  $\backslash group\_begin:$

**$\backslash str\_use:c$**  3484  $\backslash cs\_set\_protected:Npn \_\_str\_tmp:n \#1$

**$\backslash str\_clear:N$**  3485  $\{$

**$\backslash str\_clear:c$**  3486  $\backslash tl\_if\_blank:nF \{ \#1 \}$

**$\backslash str\_gclear:N$**  3487  $\{$

**$\backslash str\_gclear:c$**  3488  $\backslash cs\_new\_eq:cc \{ str\_ \#1 :N \} \{ tl\_ \#1 :N \}$

**$\backslash str\_clear\_new:N$**  3489  $\backslash exp\_args:Nc \backslash cs\_generate\_variant:Nn \{ str\_ \#1 :N \} \{ c \}$

**$\backslash str\_clear\_new:c$**  3490  $\backslash \_\_str\_tmp:n$

**$\backslash str\_gclear\_new:N$**  3491  $\}$

**$\backslash str\_gclear\_new:c$**  3492  $\}$

**$\backslash str\_set\_eq:NN$**  3493  $\backslash \_\_str\_tmp:n$

**$\backslash str\_set\_eq:cN$**  3494  $\{ new \}$

**$\backslash str\_set\_eq:Nc$**  3495  $\{ use \}$

**$\backslash str\_set\_eq:cc$**  3496  $\{ clear \}$

**$\backslash str\_gset\_eq:NN$**  3497  $\{ gclear \}$

**$\backslash str\_gset\_eq:cN$**  3498  $\{ clear\_new \}$

**$\backslash str\_gset\_eq:Nc$**  3499  $\{ gclear\_new \}$

**$\backslash str\_gset\_eq:cc$**  3500  $\{ \}$

3501  $\backslash group\_end:$

3502  $\backslash cs\_new\_eq:NN \backslash str\_set\_eq:NN \backslash tl\_set\_eq:NN$

3503  $\backslash cs\_new\_eq:NN \backslash str\_gset\_eq:NN \backslash tl\_gset\_eq:NN$

3504  $\backslash cs\_generate\_variant:Nn \backslash str\_set\_eq:NN \{ c , Nc , cc \}$

3505  $\backslash cs\_generate\_variant:Nn \backslash str\_gset\_eq:NN \{ c , Nc , cc \}$

(End definition for  $\backslash str\_new:N$  and others. These functions are documented on page 47.)

**$\backslash str\_set:Nn$**  Simply convert the token list inputs to  $\langle strings \rangle$ .

**$\backslash str\_set:Nx$**  3506  $\backslash group\_begin:$

**$\backslash str\_set:cn$**  3507  $\backslash cs\_set\_protected:Npn \_\_str\_tmp:n \#1$

**$\backslash str\_set:cx$**  3508  $\{$

**$\backslash str\_gset:Nn$**  3509  $\backslash tl\_if\_blank:nF \{ \#1 \}$

**$\backslash str\_gset:Nx$**  3510  $\{$

**$\backslash str\_gset:cn$**  3511  $\backslash cs\_new\_protected:cpx \{ str\_ \#1 :Nn \} \#1\#2$

**$\backslash str\_gset:cx$**  3512  $\{ \backslash exp\_not:c \{ tl\_ \#1 :Nx \} \#1 \{ \backslash exp\_not:N \backslash tl\_to\_str:n \{ \#2 \} \}$

**$\backslash str\_const:Nn$**  3513  $\backslash exp\_args:Nc \backslash cs\_generate\_variant:Nn \{ str\_ \#1 :Nn \} \{ Nx , cn , cx \}$

**$\backslash str\_const:Nx$**  3514  $\backslash \_\_str\_tmp:n$

**$\backslash str\_const:cn$**  3515  $\}$

**$\backslash str\_const:cx$**  3516  $\}$

**$\backslash str\_put\_left:Nn$**  3517  $\backslash \_\_str\_tmp:n$

**$\backslash str\_put\_left:Nx$**  3518  $\{ set \}$

**$\backslash str\_put\_left:cn$**  3519  $\{ gset \}$

**$\backslash str\_put\_left:cx$**  3520  $\{ const \}$

**$\backslash str\_gput\_left:Nn$**  3521  $\{ put\_left \}$

**$\backslash str\_gput\_left:Nx$**  3522  $\{ gput\_left \}$

**$\backslash str\_gput\_left:cn$**  3523  $\{ put\_right \}$

**$\backslash str\_gput\_left:cx$**

**$\backslash str\_put\_right:Nn$**

**$\backslash str\_put\_right:Nx$**

**$\backslash str\_put\_right:cn$**

**$\backslash str\_put\_right:cx$**

**$\backslash str\_gput\_right:Nn$**

**$\backslash str\_gput\_right:Nx$**

**$\backslash str\_gput\_right:cn$**

**$\backslash str\_gput\_right:cx$**

```

3524     { gput_right }
3525     { }
3526 \group_end:

```

(End definition for `\str_set:Nn` and others. These functions are documented on page 48.)

## 6.2 String comparisons

```

\str_if_empty_p:N More copy-paste!
\str_if_empty_p:c 3527 \prg_new_eq_conditional:NNn \str_if_exist:N \tl_if_exist:N { p , T , F , TF }
\str_if_empty:NTF 3528 \prg_new_eq_conditional:NNn \str_if_exist:c \tl_if_exist:c { p , T , F , TF }
\str_if_empty:cTF 3529 \prg_new_eq_conditional:NNn \str_if_empty:N \tl_if_empty:N { p , T , F , TF }
\str_if_exist_p:N 3530 \prg_new_eq_conditional:NNn \str_if_empty:c \tl_if_empty:c { p , T , F , TF }
\str_if_exist_p:c
\str_if_exist:NTF (End definition for \str_if_empty:NTF and \str_if_exist:NTF. These functions are documented on
\str_if_exist:cTF page 49.)
\__str_if_eq_x:nn
\__str_escape_x:n

```

String comparisons rely on the primitive `\(pdf)strcmp` if available: LuaTeX does not have it, so emulation is required. As the net result is that we do not *always* use the primitive, the correct approach is to wrap up in a function with defined behaviour. That's done by providing a wrapper and then redefining in the LuaTeX case. Note that the necessary Lua code is covered in `l3bootstrap`: long-term this may need to go into a separate Lua file, but at present it's somewhere that spaces are not skipped for ease-of-input. The need to detokenize and force expansion of input arises from the case where a `#` token is used in the input, *e.g.* `\__str_if_eq_x:nn {#} { \tl_to_str:n {#} }`, which otherwise would fail as `\luatex_luaescapestring:D` does not double such tokens.

```

3531 \cs_new:Npn \__str_if_eq_x:nn #1#2 { \pdfstrcmp:D {#1} {#2} }
3532 \cs_if_exist:NT \luatex_luaescapestring:D
3533 {
3534   \cs_set:Npn \__str_if_eq_x:nn #1#2
3535   {
3536     \luatex_directlua:D
3537     {
3538       l3kernel_strcmp
3539       (
3540         " \__str_escape_x:n {#1} " ,
3541         " \__str_escape_x:n {#2} "
3542       )
3543     }
3544   }
3545   \cs_new:Npn \__str_escape_x:n #1
3546   {
3547     \luatex_luaescapestring:D
3548     {
3549       \etex_detokenize:D \exp_after:wN { \luatex_expanded:D {#1} }
3550     }
3551   }
3552 }

```

(End definition for `\__str_if_eq_x:nn` and `\__str_escape_x:n`.)

`\__str_if_eq_x_return:nn` It turns out that we often need to compare a token list with the result of applying some function to it, and return with `\prg_return_true/false:`. This test is similar to `\str_if_eq:nnTF` (see `l3str`), but is hard-coded for speed.

```

3553 \cs_new:Npn \__str_if_eq_x_return:nn #1 #2
3554 {
3555     \if_int_compare:w \__str_if_eq_x:nn {#1} {#2} = 0 \exp_stop_f:
3556     \prg_return_true:
3557     \else:
3558     \prg_return_false:
3559     \fi:
3560 }

```

(End definition for \\_\_str\_if\_eq\_x\_return:nn.)

**\str\_if\_eq\_p:nn** Modern engines provide a direct way of comparing two token lists, but returning a number. This set of conditionals therefore make life a bit clearer. The nn and xx versions are created directly as this is most efficient.

```

3561 \prg_new_conditional:Npnn \str_if_eq:nn #1#2 { p , T , F , TF }
3562 {
3563     \if_int_compare:w
3564     \__str_if_eq_x:nn { \exp_not:n {#1} } { \exp_not:n {#2} }
3565     = 0 \exp_stop_f:
3566     \prg_return_true: \else: \prg_return_false: \fi:
3567 }
3568 \cs_generate_variant:Nn \str_if_eq_p:nn { V , o }
3569 \cs_generate_variant:Nn \str_if_eq_p:nn { nV , no , VV }
3570 \cs_generate_variant:Nn \str_if_eq:nnT { V , o }
3571 \cs_generate_variant:Nn \str_if_eq:nnT { nV , no , VV }
3572 \cs_generate_variant:Nn \str_if_eq:nnF { V , o }
3573 \cs_generate_variant:Nn \str_if_eq:nnF { nV , no , VV }
3574 \cs_generate_variant:Nn \str_if_eq:nnTF { V , o }
3575 \cs_generate_variant:Nn \str_if_eq:nnTF { nV , no , VV }
3576 \prg_new_conditional:Npnn \str_if_eq_x:nn #1#2 { p , T , F , TF }
3577 {
3578     \if_int_compare:w \__str_if_eq_x:nn {#1} {#2} = 0 \exp_stop_f:
3579     \prg_return_true: \else: \prg_return_false: \fi:
3580 }

```

(End definition for \str\_if\_eq:nnTF and \str\_if\_eq\_x:nnTF. These functions are documented on page 49.)

**\str\_if\_eq\_p:NN** Note that \str\_if\_eq:NN is different from \tl\_if\_eq:NN because it needs to ignore category codes.

```

3581 \prg_new_conditional:Npnn \str_if_eq:NN #1#2 { p , TF , T , F }
3582 {
3583     \if_int_compare:w \__str_if_eq_x:nn { \tl_to_str:N #1 } { \tl_to_str:N #2 }
3584     = 0 \exp_stop_f: \prg_return_true: \else: \prg_return_false: \fi:
3585 }
3586 \cs_generate_variant:Nn \str_if_eq:NNT { c , Nc , cc }
3587 \cs_generate_variant:Nn \str_if_eq:NNF { c , Nc , cc }
3588 \cs_generate_variant:Nn \str_if_eq:NNTF { c , Nc , cc }
3589 \cs_generate_variant:Nn \str_if_eq_p:NN { c , Nc , cc }

```

(End definition for \str\_if\_eq:NNTF. This function is documented on page 49.)

**\str\_case:nn** Much the same as \tl\_case:nn(TF) here: just a change in the internal comparison.

```

3590 \cs_new:Npn \str_case:nn #1#2
3591 {
3592     \str_case:on
3593     \str_case:nV
3594     \str_case:nv
3595     \str_case:nnTF
3596     \str_case:onTF
3597     \str_case:nVTF
3598     \str_case:nvTF
3599     \str_case_x:nn
3600     \str_case_x:nnTF
3601     \__str_case:nnTF
3602     \__str_case_x:nnTF
3603     \__str_case:nw

```

```

3592     \exp:w
3593     \__str_case:nnTF {#1} {#2} { } { }
3594 }
3595 \cs_new:Npn \str_case:nnT #1#2#3
3596 {
3597     \exp:w
3598     \__str_case:nnTF {#1} {#2} {#3} { }
3599 }
3600 \cs_new:Npn \str_case:nnF #1#2
3601 {
3602     \exp:w
3603     \__str_case:nnTF {#1} {#2} { }
3604 }
3605 \cs_new:Npn \str_case:nnTF #1#2
3606 {
3607     \exp:w
3608     \__str_case:nnTF {#1} {#2}
3609 }
3610 \cs_new:Npn \__str_case:nnTF #1#2#3#4
3611 { \__str_case:nw {#1} #2 {#1} { } \q_mark {#3} \q_mark {#4} \q_stop }
3612 \cs_generate_variant:Nn \str_case:nn { o , nV , nv }
3613 \cs_generate_variant:Nn \str_case:nnT { o , nV , nv }
3614 \cs_generate_variant:Nn \str_case:nnF { o , nV , nv }
3615 \cs_generate_variant:Nn \str_case:nnTF { o , nV , nv }
3616 \cs_new:Npn \__str_case:nw #1#2#3
3617 {
3618     \str_if_eq:nnTF {#1} {#2}
3619     { \__str_case_end:nw {#3} }
3620     { \__str_case:nw {#1} }
3621 }
3622 \cs_new:Npn \str_case_x:nn #1#2
3623 {
3624     \exp:w
3625     \__str_case_x:nnTF {#1} {#2} { } { }
3626 }
3627 \cs_new:Npn \str_case_x:nnT #1#2#3
3628 {
3629     \exp:w
3630     \__str_case_x:nnTF {#1} {#2} {#3} { }
3631 }
3632 \cs_new:Npn \str_case_x:nnF #1#2
3633 {
3634     \exp:w
3635     \__str_case_x:nnTF {#1} {#2} { }
3636 }
3637 \cs_new:Npn \str_case_x:nnTF #1#2
3638 {
3639     \exp:w
3640     \__str_case_x:nnTF {#1} {#2}
3641 }
3642 \cs_new:Npn \__str_case_x:nnTF #1#2#3#4
3643 { \__str_case_x:nw {#1} #2 {#1} { } \q_mark {#3} \q_mark {#4} \q_stop }
3644 \cs_new:Npn \__str_case_x:nw #1#2#3
3645 {

```

```

3646 \str_if_eq_x:nnTF {#1} {#2}
3647 { \__str_case_end:nw {#3} }
3648 { \__str_case_x:nw {#1} }
3649 }
3650 \cs_new_eq:NN \__str_case_end:nw \__prg_case_end:nw

```

(End definition for `\str_case:nnTF` and others. These functions are documented on page 50.)

### 6.3 Accessing specific characters in a string

```

\__str_to_other:n
\__str_to_other_loop:w
\__str_to_other_end:w

```

First apply `\tl_to_str:n`, then replace all spaces by “other” spaces, 8 at a time, storing the converted part of the string between the `\q_mark` and `\q_stop` markers. The end is detected when `\__str_to_other_loop:w` finds one of the trailing A, distinguished from any contents of the initial token list by their category. Then `\__str_to_other_end:w` is called, and finds the result between `\q_mark` and the first A (well, there is also the need to remove a space).

```

3651 \cs_new:Npn \__str_to_other:n #1
3652 {
3653   \exp_after:wN \__str_to_other_loop:w
3654   \tl_to_str:n {#1} ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ \q_mark \q_stop
3655 }
3656 \group_begin:
3657 \tex_lccode:D '\* = '\ %
3658 \tex_lccode:D '\A = '\A
3659 \tex_lowercase:D
3660 {
3661   \group_end:
3662   \cs_new:Npn \__str_to_other_loop:w
3663     #1 ~ #2 ~ #3 ~ #4 ~ #5 ~ #6 ~ #7 ~ #8 ~ #9 \q_stop
3664   {
3665     \if_meaning:w A #8
3666     \__str_to_other_end:w
3667     \fi:
3668     \__str_to_other_loop:w
3669     #9 #1 * #2 * #3 * #4 * #5 * #6 * #7 * #8 * \q_stop
3670   }
3671   \cs_new:Npn \__str_to_other_end:w \fi: #1 \q_mark #2 * A #3 \q_stop
3672   { \fi: #2 }
3673 }

```

(End definition for `\__str_to_other:n`, `\__str_to_other_loop:w`, and `\__str_to_other_end:w`.)

```

\__str_to_other_fast:n
\__str_to_other_fast_loop:w
\__str_to_other_fast_end:w

```

The difference with `\__str_to_other:n` is that the converted part is left in the input stream, making these commands only restricted-expandable.

```

3674 \cs_new:Npn \__str_to_other_fast:n #1
3675 {
3676   \exp_after:wN \__str_to_other_fast_loop:w \tl_to_str:n {#1} ~
3677   A ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ \q_stop
3678 }
3679 \group_begin:
3680 \tex_lccode:D '\* = '\ %
3681 \tex_lccode:D '\A = '\A
3682 \tex_lowercase:D
3683 {

```

```

3684 \group_end:
3685 \cs_new:Npn \__str_to_other_fast_loop:w
3686   #1 ~ #2 ~ #3 ~ #4 ~ #5 ~ #6 ~ #7 ~ #8 ~ #9 ~
3687   {
3688     \if_meaning:w A #9
3689     \__str_to_other_fast_end:w
3690     \fi:
3691     #1 * #2 * #3 * #4 * #5 * #6 * #7 * #8 * #9
3692     \__str_to_other_fast_loop:w *
3693   }
3694 \cs_new:Npn \__str_to_other_fast_end:w #1 * A #2 \q_stop {#1}
3695 }

```

(End definition for `\__str_to_other_fast:n`, `\__str_to_other_fast_loop:w`, and `\__str_to_other_fast_end:w`.)

`\str_item:Nn` The `\str_item:nn` hands its argument with spaces escaped to `\__str_item:nn`, and `\str_item:cn` makes sure to turn the result back into a proper string (with category code 10 spaces) eventually. The `\str_item_ignore_spaces:nn` function does not escape spaces, which are thus ignored by `\__str_item:nn` since everything else is done with undelimited arguments. Evaluate the  $\langle index \rangle$  argument #2 and count characters in the string, passing those two numbers to `\__str_item:w` for further analysis. If the  $\langle index \rangle$  is negative, shift it by the  $\langle count \rangle$  to know the how many character to discard, and if that is still negative give an empty result. If the  $\langle index \rangle$  is larger than the  $\langle count \rangle$ , give an empty result, and otherwise discard  $\langle index \rangle - 1$  characters before returning the following one. The shift by  $-1$  is obtained by inserting an empty brace group before the string in that case: that brace group also covers the case where the  $\langle index \rangle$  is zero.

```

3696 \cs_new:Npn \str_item:Nn { \exp_args:No \str_item:nn }
3697 \cs_generate_variant:Nn \str_item:Nn { c }
3698 \cs_new:Npn \str_item:nn #1#2
3699   {
3700     \exp_args:Nf \tl_to_str:n
3701     {
3702       \exp_args:Nf \__str_item:nn
3703       { \__str_to_other:n {#1} } {#2}
3704     }
3705   }
3706 \cs_new:Npn \str_item_ignore_spaces:nn #1
3707   { \exp_args:No \__str_item:nn { \tl_to_str:n {#1} } }
3708 \cs_new:Npn \__str_item:nn #1#2
3709   {
3710     \exp_after:wN \__str_item:w
3711     \__int_value:w \__int_eval:w #2 \exp_after:wN ;
3712     \__int_value:w \__str_count:n {#1} ;
3713     #1 \q_stop
3714   }
3715 \cs_new:Npn \__str_item:w #1; #2;
3716   {
3717     \int_compare:nNnTF {#1} < 0
3718     {
3719       \int_compare:nNnTF {#1} < {-#2}
3720       { \use_none_delimit_by_q_stop:w }
3721       {
3722         \exp_after:wN \use_i_delimit_by_q_stop:nw

```



```

3723         \exp:w \exp_after:wN \__str_skip_exp_end:w
3724         \__int_value:w \__int_eval:w #1 + #2 ;
3725     }
3726 }
3727 {
3728     \int_compare:nNnTF {#1} > {#2}
3729     { \use_none_delimit_by_q_stop:w }
3730     {
3731         \exp_after:wN \use_i_delimit_by_q_stop:nw
3732         \exp:w \__str_skip_exp_end:w #1 ; { }
3733     }
3734 }
3735 }

```

(End definition for `\str_item:Nn` and others. These functions are documented on page 52.)

```

\__str_skip_exp_end:w
\__str_skip_loop:wNNNNNNNN
\__str_skip_end:w
\__str_skip_end:NNNNNNNN

```

Removes  $\max(\#1, 0)$  characters from the input stream, and then leaves `\exp_end:.` This should be expanded using `\exp:w`. We remove characters 8 at a time until there are at most 8 to remove. Then we do a dirty trick: the `\if_case:w` construction leaves between 0 and 8 times the `\or:` control sequence, and those `\or:` become arguments of `\__str_skip_end:NNNNNNNN`. If the number of characters to remove is 6, say, then there are two `\or:` left, and the 8 arguments of `\__str_skip_end:NNNNNNNN` are the two `\or:`, and 6 characters from the input stream, exactly what we wanted to remove. Then close the `\if_case:w` conditional with `\fi:`, and stop the initial expansion with `\exp_end:` (see places where `\__str_skip_exp_end:w` is called).

```

3736 \cs_new:Npn \__str_skip_exp_end:w #1;
3737 {
3738     \if_int_compare:w #1 > 8 \exp_stop_f:
3739     \exp_after:wN \__str_skip_loop:wNNNNNNNN
3740     \else:
3741         \exp_after:wN \__str_skip_end:w
3742         \__int_value:w \__int_eval:w
3743     \fi:
3744     #1 ;
3745 }
3746 \cs_new:Npn \__str_skip_loop:wNNNNNNNN #1; #2#3#4#5#6#7#8#9
3747 { \exp_after:wN \__str_skip_exp_end:w \__int_value:w \__int_eval:w #1 - 8 ; }
3748 \cs_new:Npn \__str_skip_end:w #1 ;
3749 {
3750     \exp_after:wN \__str_skip_end:NNNNNNNN
3751     \if_case:w #1 \exp_stop_f: \or: \or: \or: \or: \or: \or: \or: \or:
3752 }
3753 \cs_new:Npn \__str_skip_end:NNNNNNNN #1#2#3#4#5#6#7#8 { \fi: \exp_end: }

```

(End definition for `\__str_skip_exp_end:w` and others.)

```

\str_range:Nnn
\str_range:nnn
\str_range_ignore_spaces:nnn
\__str_range:nnn
\__str_range:w
\__str_range:nnw

```

Sanitize the string. Then evaluate the arguments. At this stage we also decrement the  $\langle \text{start index} \rangle$ , since our goal is to know how many characters should be removed. Then limit the range to be non-negative and at most the length of the string (this avoids needing to check for the end of the string when grabbing characters), shifting negative numbers by the appropriate amount. Afterwards, skip characters, then keep some more, and finally drop the end of the string.

```

3754 \cs_new:Npn \str_range:Nnn { \exp_args:No \str_range:nnn }

```

```

3755 \cs_generate_variant:Nn \str_range:Nnn { c }
3756 \cs_new:Npn \str_range:nnn #1#2#3
3757 {
3758   \exp_args:Nf \tl_to_str:n
3759   {
3760     \exp_args:Nf \__str_range:nnn
3761     { \__str_to_other:n {#1} } {#2} {#3}
3762   }
3763 }
3764 \cs_new:Npn \str_range_ignore_spaces:nnn #1
3765 { \exp_args:No \__str_range:nnn { \tl_to_str:n {#1} } }
3766 \cs_new:Npn \__str_range:nnn #1#2#3
3767 {
3768   \exp_after:wN \__str_range:w
3769   \__int_value:w \__str_count:n {#1} \exp_after:wN ;
3770   \__int_value:w \__int_eval:w #2 - 1 \exp_after:wN ;
3771   \__int_value:w \__int_eval:w #3 ;
3772   #1 \q_stop
3773 }
3774 \cs_new:Npn \__str_range:w #1; #2; #3;
3775 {
3776   \exp_args:Nf \__str_range:nnw
3777   { \__str_range_normalize:nn {#2} {#1} }
3778   { \__str_range_normalize:nn {#3} {#1} }
3779 }
3780 \cs_new:Npn \__str_range:nnw #1#2
3781 {
3782   \exp_after:wN \__str_collect_delimit_by_q_stop:w
3783   \__int_value:w \__int_eval:w #2 - #1 \exp_after:wN ;
3784   \exp:w \__str_skip_exp_end:w #1 ;
3785 }

```

(End definition for `\str_range:Nnn` and others. These functions are documented on page 52.)

`\__str_range_normalize:nn` This function converts an *<index>* argument into an explicit position in the string (a result of 0 denoting “out of bounds”). Expects two explicit integer arguments: the *<index>* #1 and the string count #2. If #1 is negative, replace it by #1 + #2 + 1, then limit to the range [0, #2].

```

3786 \cs_new:Npn \__str_range_normalize:nn #1#2
3787 {
3788   \int_eval:n
3789   {
3790     \if_int_compare:w #1 < 0 \exp_stop_f:
3791     \if_int_compare:w #1 < -#2 \exp_stop_f:
3792     0
3793     \else:
3794       #1 + #2 + 1
3795     \fi:
3796   \else:
3797     \if_int_compare:w #1 < #2 \exp_stop_f:
3798     #1
3799     \else:
3800     #2
3801   \fi:

```

```

3802         \fi:
3803     }
3804 }

```

(End definition for `\_str_range_normalize:nn`.)

```

\_str_collect_delimit_by_q_stop:w
\_str_collect_loop:wn
  \_str_collect_loop:wnNNNNNNN
  \_str_collect_end:wn
\_str_collect_end:nnnnnnnnw

```

Collects `max(#1,0)` characters, and removes everything else until `\q_stop`. This is somewhat similar to `\_str_skip_exp_end:w`, but accepts integer expression arguments. This time we can only grab 7 characters at a time. At the end, we use an `\if_case:w` trick again, so that the 8 first arguments of `\_str_collect_end:nnnnnnnnw` are some `\or:`, followed by an `\fi:`, followed by `#1` characters from the input stream. Simply leaving this in the input stream closes the conditional properly and the `\or:` disappear.

```

3805 \cs_new:Npn \_str_collect_delimit_by_q_stop:w #1;
3806 { \_str_collect_loop:wn #1 ; { } }
3807 \cs_new:Npn \_str_collect_loop:wn #1 ;
3808 {
3809   \if_int_compare:w #1 > 7 \exp_stop_f:
3810     \exp_after:wN \_str_collect_loop:wnNNNNNNN
3811   \else:
3812     \exp_after:wN \_str_collect_end:wn
3813   \fi:
3814   #1 ;
3815 }
3816 \cs_new:Npn \_str_collect_loop:wnNNNNNNN #1; #2 #3#4#5#6#7#8#9
3817 {
3818   \exp_after:wN \_str_collect_loop:wn
3819   \_int_value:w \_int_eval:w #1 - 7 ;
3820   { #2 #3#4#5#6#7#8#9 }
3821 }
3822 \cs_new:Npn \_str_collect_end:wn #1 ;
3823 {
3824   \exp_after:wN \_str_collect_end:nnnnnnnnw
3825   \if_case:w \if_int_compare:w #1 > 0 \exp_stop_f: #1 \else: 0 \fi: \exp_stop_f:
3826   \or: \or: \or: \or: \or: \or: \or: \fi:
3827 }
3828 \cs_new:Npn \_str_collect_end:nnnnnnnnw #1#2#3#4#5#6#7#8 #9 \q_stop
3829 { #1#2#3#4#5#6#7#8 }

```

(End definition for `\_str_collect_delimit_by_q_stop:w` and others.)

## 6.4 Counting characters

```

\str_count_spaces:N
\str_count_spaces:c
\str_count_spaces:n
\_str_count_spaces_loop:w

```

To speed up this function, we grab and discard 9 space-delimited arguments in each iteration of the loop. The loop stops when the last argument is one of the trailing `X⟨number⟩`, and that `⟨number⟩` is added to the sum of 9 that precedes, to adjust the result.

```

3830 \cs_new:Npn \str_count_spaces:N
3831 { \exp_args:No \str_count_spaces:n }
3832 \cs_generate_variant:Nn \str_count_spaces:N { c }
3833 \cs_new:Npn \str_count_spaces:n #1
3834 {
3835   \int_eval:n
3836   {

```

```

3837         \exp_after:wN \_str_count_spaces_loop:w
3838         \tl_to_str:n {#1} ~
3839         X 7 ~ X 6 ~ X 5 ~ X 4 ~ X 3 ~ X 2 ~ X 1 ~ X 0 ~ X -1 ~
3840         \q_stop
3841     }
3842 }
3843 \cs_new:Npn \_str_count_spaces_loop:w #1~#2~#3~#4~#5~#6~#7~#8~#9~
3844 {
3845     \if_meaning:w X #9
3846     \use_i_delimit_by_q_stop:nw
3847     \fi:
3848     9 + \_str_count_spaces_loop:w
3849 }

```

(End definition for `\str_count_spaces:N`, `\str_count_spaces:n`, and `\_str_count_spaces_loop:w`. These functions are documented on page 51.)

`\str_count:N` To count characters in a string we could first escape all spaces using `\_str_to_other:n`, then pass the result to `\tl_count:n`. However, the escaping step would be quadratic in the number of characters in the string, and we can do better. Namely, sum the number of spaces (`\str_count_spaces:n`) and the result of `\tl_count:n`, which ignores spaces. `\str_count_ignore_spaces:n` Since strings tend to be longer than token lists, we use specialized functions to count characters ignoring spaces. Namely, `loop`, grabbing 9 non-space characters at each step, and end as soon as we reach one of the 9 trailing items. The internal function `\_str_count:n`, used in `\str_item:nn` and `\str_range:nnn`, is similar to `\str_count_ignore_spaces:n` but expects its argument to already be a string or a string with spaces escaped.

```

3850 \cs_new:Npn \str_count:N { \exp_args:No \str_count:n }
3851 \cs_generate_variant:Nn \str_count:N { c }
3852 \cs_new:Npn \str_count:n #1
3853 {
3854     \_str_count_aux:n
3855     {
3856         \str_count_spaces:n {#1}
3857         + \exp_after:wN \_str_count_loop:NNNNNNNNN \tl_to_str:n {#1}
3858     }
3859 }
3860 \cs_new:Npn \_str_count:n #1
3861 {
3862     \_str_count_aux:n
3863     { \_str_count_loop:NNNNNNNNN #1 }
3864 }
3865 \cs_new:Npn \str_count_ignore_spaces:n #1
3866 {
3867     \_str_count_aux:n
3868     { \exp_after:wN \_str_count_loop:NNNNNNNNN \tl_to_str:n {#1} }
3869 }
3870 \cs_new:Npn \_str_count_aux:n #1
3871 {
3872     \int_eval:n
3873     {
3874         #1
3875         { X 8 } { X 7 } { X 6 }
3876         { X 5 } { X 4 } { X 3 }

```

```

3877         { X 2 } { X 1 } { X 0 }
3878     \q_stop
3879 }
3880 }
3881 \cs_new:Npn \__str_count_loop:NNNNNNNNN #1#2#3#4#5#6#7#8#9
3882 {
3883     \if_meaning:w X #9
3884     \exp_after:wN \use_none_delimit_by_q_stop:w
3885     \fi:
3886     9 + \__str_count_loop:NNNNNNNNN
3887 }

```

(End definition for `\str_count:N` and others. These functions are documented on page 51.)

## 6.5 The first character in a string

`\str_head:N` The `_ignore_spaces` variant applies `\tl_to_str:n` then grabs the first item, thus skipping spaces. As usual, `\str_head:N` expands its argument and hands it to `\str_head:n`.  
`\str_head:c` To circumvent the fact that  $\TeX$  skips spaces when grabbing undelimited macro parameters, `\__str_head:w` takes an argument delimited by a space. If `#1` starts with a non-space character, `\use_i_delimit_by_q_stop:nw` leaves that in the input stream. On the other hand, if `#1` starts with a space, the `\__str_head:w` takes an empty argument, and the single (initially braced) space in the definition of `\__str_head:w` makes its way to the output. Finally, for an empty argument, the (braced) empty brace group in the definition of `\str_head:n` gives an empty result after passing through `\use_i_delimit_by_q_stop:nw`.

```

3888 \cs_new:Npn \str_head:N { \exp_args:No \str_head:n }
3889 \cs_generate_variant:Nn \str_head:N { c }
3890 \cs_new:Npn \str_head:n #1
3891 {
3892     \exp_after:wN \__str_head:w
3893     \tl_to_str:n {#1}
3894     { { } } ~ \q_stop
3895 }
3896 \cs_new:Npn \__str_head:w #1 ~ %
3897 { \use_i_delimit_by_q_stop:nw #1 { ~ } }
3898 \cs_new:Npn \str_head_ignore_spaces:n #1
3899 {
3900     \exp_after:wN \use_i_delimit_by_q_stop:nw
3901     \tl_to_str:n {#1} { } \q_stop
3902 }

```

(End definition for `\str_head:N` and others. These functions are documented on page 51.)

`\str_tail:N` Getting the tail is a little bit more convoluted than the head of a string. We hit the front of the string with `\reverse_if:N \if_charcode:w \scan_stop:.` This removes the first character, and necessarily makes the test true, since the character cannot match `\scan_stop:.` The auxiliary function then inserts the required `\fi:` to close the conditional, and leaves the tail of the string in the input stream. The details are such that an empty string has an empty tail (this requires in particular that the end-marker `X` be unexpandable and not a control sequence). The `_ignore_spaces` is rather simpler: after converting the input to a string, `\__str_tail_auxii:w` removes one undelimited argument and leaves

everything else until an end-marker `\q_mark`. One can check that an empty (or blank) string yields an empty tail.

```

3903 \cs_new:Npn \str_tail:N { \exp_args:No \str_tail:n }
3904 \cs_generate_variant:Nn \str_tail:N { c }
3905 \cs_new:Npn \str_tail:n #1
3906 {
3907   \exp_after:wN \__str_tail_auxi:w
3908   \reverse_if:N \if_charcode:w
3909     \scan_stop: \tl_to_str:n {#1} X X \q_stop
3910 }
3911 \cs_new:Npn \__str_tail_auxi:w #1 X #2 \q_stop { \fi: #1 }
3912 \cs_new:Npn \str_tail_ignore_spaces:n #1
3913 {
3914   \exp_after:wN \__str_tail_auxii:w
3915   \tl_to_str:n {#1} \q_mark \q_mark \q_stop
3916 }
3917 \cs_new:Npn \__str_tail_auxii:w #1 #2 \q_mark #3 \q_stop { #2 }

```

(End definition for `\str_tail:N` and others. These functions are documented on page 51.)

## 6.6 String manipulation

<pre> \str_fold_case:n \str_fold_case:V \str_lower_case:n \str_lower_case:f \str_upper_case:n \str_upper_case:f __str_change_case:nn __str_change_case_aux:nn __str_change_case_result:n __str_change_case_output:nw __str_change_case_output:fw __str_change_case_end:nw __str_change_case_loop:nw __str_change_case_space:n __str_change_case_char:nN __str_lookup_lower:N __str_lookup_upper:N __str_lookup_fold:N </pre>	<p>Case changing for programmatic reasons is done by first detokenizing input then doing a simple loop that only has to worry about spaces and everything else. The output is detokenized to allow data sharing with text-based case changing.</p> <pre> 3918 \cs_new:Npn \str_fold_case:n #1 { __str_change_case:nn {#1} { fold } } 3919 \cs_new:Npn \str_lower_case:n #1 { __str_change_case:nn {#1} { lower } } 3920 \cs_new:Npn \str_upper_case:n #1 { __str_change_case:nn {#1} { upper } } 3921 \cs_generate_variant:Nn \str_fold_case:n { V } 3922 \cs_generate_variant:Nn \str_lower_case:n { f } 3923 \cs_generate_variant:Nn \str_upper_case:n { f } 3924 \cs_new:Npn __str_change_case:nn #1 3925 { 3926   \exp_after:wN __str_change_case_aux:nn \exp_after:wN 3927   { \tl_to_str:n {#1} } 3928 } 3929 \cs_new:Npn __str_change_case_aux:nn #1#2 3930 { 3931   __str_change_case_loop:nw {#2} #1 \q_recursion_tail \q_recursion_stop 3932   __str_change_case_result:n { } 3933 } 3934 \cs_new:Npn __str_change_case_output:nw #1#2 __str_change_case_result:n #3 3935 { #2 __str_change_case_result:n { #3 #1 } } 3936 \cs_generate_variant:Nn __str_change_case_output:nw { f } 3937 \cs_new:Npn __str_change_case_end:wn #1 __str_change_case_result:n #2 { #2 } 3938 \cs_new:Npn __str_change_case_loop:nw #1#2 \q_recursion_stop 3939 { 3940   \tl_if_head_is_space:nTF {#2} 3941     { __str_change_case_space:n } 3942     { __str_change_case_char:nN } 3943   {#1} #2 \q_recursion_stop 3944 } 3945 \use:x </pre>
--	---

```

3946 { \cs_new:Npn \exp_not:N \__str_change_case_space:n ##1 \c_space_tl }
3947 {
3948   \__str_change_case_output:nw { ~ }
3949   \__str_change_case_loop:nw {#1}
3950 }
3951 \cs_new:Npn \__str_change_case_char:nN #1#2
3952 {
3953   \quark_if_recursion_tail_stop_do:Nn #2
3954   { \__str_change_case_end:wn }
3955   \cs_if_exist:cTF { c__unicode_ #1 _ #2 _tl }
3956   {
3957     \__str_change_case_output:fw
3958     { \tl_to_str:c { c__unicode_ #1 _ #2 _tl } }
3959   }
3960   { \__str_change_case_char_aux:nN {#1} #2 }
3961   \__str_change_case_loop:nw {#1}
3962 }

```

For Unicode engines there's a look up to see if the current character has a valid one-to-one case change mapping. That's not needed for 8-bit engines: as they don't have `\utex_char:D` all of the changes they can make are hard-coded and so already picked up above.

```

3963 \cs_if_exist:NTF \utex_char:D
3964 {
3965   \cs_new:Npn \__str_change_case_char_aux:nN #1#2
3966   {
3967     \int_compare:nNnTF { \use:c { __str_lookup_ #1 :N } #2 } = { 0 }
3968     { \__str_change_case_output:nw {#2} }
3969     {
3970       \__str_change_case_output:fw
3971       { \utex_char:D \use:c { __str_lookup_ #1 :N } #2 ~ }
3972     }
3973   }
3974   \cs_new_protected:Npn \__str_lookup_lower:N #1 { \tex_lccode:D '#1 }
3975   \cs_new_protected:Npn \__str_lookup_upper:N #1 { \tex_uccode:D '#1 }
3976   \cs_new_eq:NN \__str_lookup_fold:N \__str_lookup_lower:N
3977 }
3978 {
3979   \cs_new:Npn \__str_change_case_char_aux:nN #1#2
3980   { \__str_change_case_output:nw {#2} }
3981 }

```

(End definition for `\str_fold_case:n` and others. These functions are documented on page 54.)

<code>\c_ampersand_str</code> <code>\c_atsign_str</code> <code>\c_backslash_str</code> <code>\c_left_brace_str</code> <code>\c_right_brace_str</code> <code>\c_circumflex_str</code> <code>\c_colon_str</code> <code>\c_dollar_str</code> <code>\c_hash_str</code> <code>\c_percent_str</code> <code>\c_tilde_str</code> <code>\c_underscore_str</code>	<p>For all of those strings, use <code>\cs_to_str:N</code> to get characters with the correct category code without worries</p> <pre> 3982 \str_const:Nx \c_ampersand_str { \cs_to_str:N &amp; } 3983 \str_const:Nx \c_atsign_str { \cs_to_str:N @ } 3984 \str_const:Nx \c_backslash_str { \cs_to_str:N \ } 3985 \str_const:Nx \c_left_brace_str { \cs_to_str:N { } 3986 \str_const:Nx \c_right_brace_str { \cs_to_str:N } } 3987 \str_const:Nx \c_circumflex_str { \cs_to_str:N ^ } 3988 \str_const:Nx \c_colon_str { \cs_to_str:N : } 3989 \str_const:Nx \c_dollar_str { \cs_to_str:N \$ } </pre>
--	---

```

3990 \str_const:Nx \c_hash_str      { \cs_to_str:N \# }
3991 \str_const:Nx \c_percent_str   { \cs_to_str:N \% }
3992 \str_const:Nx \c_tilde_str     { \cs_to_str:N \~ }
3993 \str_const:Nx \c_underscore_str { \cs_to_str:N \_ }

```

(End definition for `\c_ampersand_str` and others. These variables are documented on page 55.)

```

\l_tmpa_str Scratch strings.
\l_tmpb_str
\g_tmpa_str
\g_tmpb_str
3994 \str_new:N \l_tmpa_str
3995 \str_new:N \l_tmpb_str
3996 \str_new:N \g_tmpa_str
3997 \str_new:N \g_tmpb_str

```

(End definition for `\l_tmpa_str` and others. These variables are documented on page 55.)

## 6.7 Viewing strings

```

\str_show:n Displays a string on the terminal.
\str_show:N
\str_show:c
3998 \cs_new_eq:NN \str_show:n \tl_show:n
3999 \cs_new_eq:NN \str_show:N \tl_show:N
4000 \cs_generate_variant:Nn \str_show:N { c }

```

(End definition for `\str_show:n` and `\str_show:N`. These functions are documented on page 54.)

## 6.8 Unicode data for case changing

```

4001 <@@=unicode>

```

Case changing both for strings and “text” requires data from the Unicode Consortium. Some of this is build in to the format (as `\lccode` and `\uccode` values) but this covers only the simple one-to-one situations and does not fully handle for example case folding.

The data required for cross-module manipulations is loaded here: currently this means for `str` and `tl` functions. As such, the prefix used is not `str` but rather `unicode`. For performance (as the entire data set must be read during each run) and as this code comes somewhat early in the load process, there is quite a bit of low-level code here.

As only the data needs to remain at the end of this process, everything is set up inside a group.

```

4002 \group_begin:

```

A read stream is needed. The I/O module is not yet in place *and* we do not want to use up a stream. We therefore use a known free one in format mode or look for the next free one in package mode (covers plain, L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> and ConT<sub>E</sub>Xt MkII and MkIV).

```

4003 <*:initex>
4004 \tex_chardef:D \g__unicode_data_ior = 0 \scan_stop:
4005 </initex>
4006 <*:package>
4007 \tex_chardef:D \g__unicode_data_ior
4008 \etex_numexpr:D
4009 \cs_if_exist:NTF \lastallocatedread
4010 { \lastallocatedread }
4011 {
4012 \cs_if_exist:NTF \c_syst_last_allocated_read
4013 { \c_syst_last_allocated_read }

```



```

4014         { \tex_count:D 16 ~ }
4015     }
4016     + 1
4017     \scan_stop:
4018 \endpackage

```

Set up to read each file. As they use C-style comments, there is a need to deal with #. At the same time, spaces are important so they need to be picked up as they are important. Beyond that, the current category code scheme works fine. With no I/O loop available, hard-code one that works quickly.

```

4019 \cs_set_protected:Npn \__unicode_map_inline:n #1
4020 {
4021     \group_begin:
4022     \tex_catcode:D '\# = 12 \scan_stop:
4023     \tex_catcode:D '\ = 10 \scan_stop:
4024     \tex_openin:D \g__unicode_data_ior = #1 \scan_stop:
4025     \cs_if_exist:NT \utex_char:D
4026     { \__unicode_map_loop: }
4027     \tex_closein:D \g__unicode_data_ior
4028     \group_end:
4029 }
4030 \cs_set_protected:Npn \__unicode_map_loop:
4031 {
4032     \tex_if_eof:D \g__unicode_data_ior
4033     \exp_after:wN \use_none:n
4034     \else:
4035     \exp_after:wN \use:n
4036     \fi:
4037     {
4038         \tex_read:D \g__unicode_data_ior to \l__unicode_tmp_tl
4039         \if_meaning:w \c_empty_tl \l__unicode_tmp_tl
4040         \else:
4041         \exp_after:wN \__unicode_parse:w \l__unicode_tmp_tl \q_stop
4042         \fi:
4043         \__unicode_map_loop:
4044     }
4045 }

```

The lead-off parser for each line is common for all of the files. If the line starts with a # it's a comment. There's one special comment line to look out for in `SpecialCasing.txt` as we want to ignore everything after it. As this line does not appear in any other sources and the test is quite quick (there are relatively few comment lines), it can be present in all of the passes.

```

4046 \cs_set_protected:Npn \__unicode_parse:w #1#2 \q_stop
4047 {
4048     \reverse_if:N \if:w \c_hash_str #1
4049     \__unicode_parse_auxi:w #1#2 \q_stop
4050     \else:
4051     \if_int_compare:w \__str_if_eq_x:nn
4052     { \exp_not:n {#2} } { ~Conditional~Mappings~ } = 0 \exp_stop_f:
4053     \cs_set_protected:Npn \__unicode_parse:w ##1 \q_stop { }
4054     \fi:
4055     \fi:
4056 }

```

Storing each exception is always done in the same way: create a constant token list which expands to exactly the mapping. These have the category codes “now” (so should be letters) but are later detokenized for string use.

```

4057 \cs_set_protected:Npn \__unicode_store:nnnnn #1#2#3#4#5
4058 {
4059   \tl_const:cx { c__unicode_ #2 _ \utex_char:D "#1 _tl }
4060   {
4061     \utex_char:D "#3 ~
4062     \utex_char:D "#4 ~
4063     \tl_if_blank:nF {#5}
4064     { \utex_char:D "#5 }
4065   }
4066 }

```

Parse the main Unicode data file for title case exceptions (the one-to-one lower and upper case mappings it contains are all be covered by the  $\TeX$  data).

```

4067 \cs_set_protected:Npn \__unicode_parse_auxi:w
4068   #1 ; #2 ; #3 ; #4 ; #5 ; #6 ; #7 ; #8 ; #9 ;
4069   { \__unicode_parse_auxii:w #1 ; }
4070 \cs_set_protected:Npn \__unicode_parse_auxii:w
4071   #1 ; #2 ; #3 ; #4 ; #5 ; #6 ; #7 \q_stop
4072   {
4073     \tl_if_blank:nF {#7}
4074     {
4075       \if_int_compare:w \__str_if_eq_x:nn { #5 ~ } {#7} = 0 \exp_stop_f:
4076       \else:
4077         \tl_const:cx
4078         { c__unicode_mixed_ \utex_char:D "#1 _tl }
4079         { \utex_char:D "#7 }
4080       \fi:
4081     }
4082   }
4083 \__unicode_map_inline:n { UnicodeData.txt }

```

The set up for case folding is in two parts. For the basic (core) mappings, folding is the same as lower casing in most positions so only store the differences. For the more complex foldings, always store the result, splitting up the two or three code points in the input as required.

```

4084 \cs_set_protected:Npn \__unicode_parse_auxi:w #1 ;~ #2 ;~ #3 ; #4 \q_stop
4085 {
4086   \if_int_compare:w \__str_if_eq_x:nn {#2} { C } = 0 \exp_stop_f:
4087   \if_int_compare:w \tex_lccode:D "#1 = "#3 \scan_stop:
4088   \else:
4089     \tl_const:cx
4090     { c__unicode_fold_ \utex_char:D "#1 _tl }
4091     { \utex_char:D "#3 ~ }
4092   \fi:
4093   \else:
4094     \if_int_compare:w \__str_if_eq_x:nn {#2} { F } = 0 \exp_stop_f:
4095     \__unicode_parse_auxii:w #1 ~ #3 ~ \q_stop
4096   \fi:
4097   \fi:
4098 }
4099 \cs_set_protected:Npn \__unicode_parse_auxii:w #1 ~ #2 ~ #3 ~ #4 \q_stop
4100 { \__unicode_store:nnnnn {#1} { fold } {#2} {#3} {#4} }

```

```
4101 \__unicode_map_inline:n { CaseFolding.txt }
```

For upper and lower casing special situations, there is a bit more to do as we also have title casing to consider.

```
4102 \cs_set_protected:Npn \__unicode_parse_auxii:w #1 ;~ #2 ;~ #3 ;~ #4 ; #5 \q_stop
4103 {
4104   \use:n { \__unicode_parse_auxii:w #1 ~ lower ~ #2 ~ } ~ \q_stop
4105   \use:n { \__unicode_parse_auxii:w #1 ~ upper ~ #4 ~ } ~ \q_stop
4106   \if_int_compare:w \__str_if_eq_x:nn {#3} {#4} = 0 \exp_stop_f:
4107   \else:
4108     \use:n { \__unicode_parse_auxii:w #1 ~ mixed ~ #3 ~ } ~ \q_stop
4109   \fi:
4110 }
4111 \cs_set_protected:Npn \__unicode_parse_auxii:w #1 ~ #2 ~ #3 ~ #4 ~ #5 \q_stop
4112 {
4113   \tl_if_empty:nF {#4}
4114   { \__unicode_store:nnnnn {#1} {#2} {#3} {#4} {#5} }
4115 }
4116 \__unicode_map_inline:n { SpecialCasing.txt }
```

For the 8-bit engines, the above does nothing but there is some set up needed. There is no expandable character generator primitive so some alternative is needed. As we’ve not used up hash space for the above, we can go for the fast approach here of one name per letter. Keeping folding and lower casing separate makes the use later a bit easier.

```
4117 \cs_if_exist:NF \utex_char:D
4118 {
4119   \cs_set_protected:Npn \__unicode_tmp:NN #1#2
4120   {
4121     \if_meaning:w \q_recursion_tail #2
4122     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
4123     \fi:
4124     \tl_const:cn { c__unicode_fold_ #1 _tl } {#2}
4125     \tl_const:cn { c__unicode_lower_ #1 _tl } {#2}
4126     \tl_const:cn { c__unicode_upper_ #2 _tl } {#1}
4127     \__unicode_tmp:NN
4128   }
4129   \__unicode_tmp:NN
4130   AaBbCcDdEeFfGgHhIiJjKkLlMmNnOoPpQqRrSsTtUuVvWwXxYyZz
4131   ? \q_recursion_tail \q_recursion_stop
4132 }
```

All done: tidy up.

```
4133 \group_end:
4134 </initex | package>
```

## 7 l3seq implementation

The following test files are used for this code: *m3seq002*, *m3seq003*.

```
4135 <*initex | package>
4136 <@@=seq>
```

A sequence is a control sequence whose top-level expansion is of the form “\s\_\_-seq \\_\_seq\_item:n {<item<sub>1</sub>>} ... \\_\_seq\_item:n {<item<sub>n</sub>>}”, with a leading scan mark followed by *n* items of the same form. An earlier implementation used the structure

“`\seq_elt:w <item1> \seq_elt_end: ... \seq_elt:w <itemn> \seq_elt_end:`”. This allowed rapid searching using a delimited function, but was not suitable for items containing `{`, `}` and `#` tokens, and also lead to the loss of surrounding braces around items.

**`\s__seq`** The variable is defined in the `l3quark` module, loaded later.

*(End definition for `\s__seq`.)*

**`\__seq_item:n`** The delimiter is always defined, but when used incorrectly simply removes its argument and hits an undefined control sequence to raise an error.

```
4137 \cs_new:Npn \__seq_item:n
4138 {
4139     \__msg_kernel_expandable_error:nn { kernel } { misused-sequence }
4140     \use_none:n
4141 }
```

*(End definition for `\__seq_item:n`.)*

**`\l__seq_internal_a_tl`** Scratch space for various internal uses.

**`\l__seq_internal_b_tl`**

```
4142 \tl_new:N \l__seq_internal_a_tl
4143 \tl_new:N \l__seq_internal_b_tl
```

*(End definition for `\l__seq_internal_a_tl` and `\l__seq_internal_b_tl`.)*

**`\__seq_tmp:w`** Scratch function for internal use.

```
4144 \cs_new_eq:NN \__seq_tmp:w ?
```

*(End definition for `\__seq_tmp:w`.)*

**`\c_empty_seq`** A sequence with no item, following the structure mentioned above.

```
4145 \tl_const:Nn \c_empty_seq { \s__seq }
```

*(End definition for `\c_empty_seq`. This variable is documented on page 66.)*

## 7.1 Allocation and initialisation

**`\seq_new:N`** Sequences are initialized to `\c_empty_seq`.

**`\seq_new:c`**

```
4146 \cs_new_protected:Npn \seq_new:N #1
4147 {
4148     \__chk_if_free_cs:N #1
4149     \cs_gset_eq:NN #1 \c_empty_seq
4150 }
4151 \cs_generate_variant:Nn \seq_new:N { c }
```

*(End definition for `\seq_new:N`. This function is documented on page 57.)*

**`\seq_clear:N`** Clearing a sequence is similar to setting it equal to the empty one.

**`\seq_clear:c`**

**`\seq_gclear:N`**

**`\seq_gclear:c`**

```
4152 \cs_new_protected:Npn \seq_clear:N #1
4153 { \seq_set_eq:NN #1 \c_empty_seq }
4154 \cs_generate_variant:Nn \seq_clear:N { c }
4155 \cs_new_protected:Npn \seq_gclear:N #1
4156 { \seq_gset_eq:NN #1 \c_empty_seq }
4157 \cs_generate_variant:Nn \seq_gclear:N { c }
```

*(End definition for `\seq_clear:N` and `\seq_gclear:N`. These functions are documented on page 57.)*

```

\seq_clear_new:N Once again we copy code from the token list functions.
\seq_clear_new:c 4158 \cs_new_protected:Npn \seq_clear_new:N #1
\seq_gclear_new:N 4159 { \seq_if_exist:NTF #1 { \seq_clear:N #1 } { \seq_new:N #1 } }
\seq_gclear_new:c 4160 \cs_generate_variant:Nn \seq_clear_new:N { c }
4161 \cs_new_protected:Npn \seq_gclear_new:N #1
4162 { \seq_if_exist:NTF #1 { \seq_gclear:N #1 } { \seq_new:N #1 } }
4163 \cs_generate_variant:Nn \seq_gclear_new:N { c }

```

(End definition for `\seq_clear_new:N` and `\seq_gclear_new:N`. These functions are documented on page 57.)

```

\seq_set_eq:NN Copying a sequence is the same as copying the underlying token list.
\seq_set_eq:cN 4164 \cs_new_eq:NN \seq_set_eq:NN \tl_set_eq:NN
\seq_set_eq:Nc 4165 \cs_new_eq:NN \seq_set_eq:Nc \tl_set_eq:Nc
\seq_set_eq:cc 4166 \cs_new_eq:NN \seq_set_eq:cN \tl_set_eq:cN
\seq_gset_eq:NN 4167 \cs_new_eq:NN \seq_set_eq:cc \tl_set_eq:cc
\seq_gset_eq:cN 4168 \cs_new_eq:NN \seq_gset_eq:NN \tl_gset_eq:NN
\seq_gset_eq:Nc 4169 \cs_new_eq:NN \seq_gset_eq:Nc \tl_gset_eq:Nc
\seq_gset_eq:cN 4170 \cs_new_eq:NN \seq_gset_eq:cN \tl_gset_eq:cN
\seq_gset_eq:cc 4171 \cs_new_eq:NN \seq_gset_eq:cc \tl_gset_eq:cc

```

(End definition for `\seq_set_eq:NN` and `\seq_gset_eq:NN`. These functions are documented on page 57.)

```

\seq_set_from_clist:NN Setting a sequence from a comma-separated list is done using a simple mapping.
\seq_set_from_clist:cN 4172 \cs_new_protected:Npn \seq_set_from_clist:NN #1#2
\seq_set_from_clist:Nc 4173 {
\seq_set_from_clist:cc 4174   \tl_set:Nx #1
\seq_set_from_clist:NN 4175   { \s__seq \clist_map_function:NN #2 \__seq_wrap_item:n }
\seq_set_from_clist:cN 4176 }
\seq_gset_from_clist:NN 4177 \cs_new_protected:Npn \seq_set_from_clist:Nn #1#2
\seq_gset_from_clist:cN 4178 {
\seq_gset_from_clist:Nc 4179   \tl_set:Nx #1
\seq_gset_from_clist:cc 4180   { \s__seq \clist_map_function:nN {#2} \__seq_wrap_item:n }
\seq_gset_from_clist:NN 4181 }
\seq_gset_from_clist:NN 4182 \cs_new_protected:Npn \seq_gset_from_clist:NN #1#2
\seq_gset_from_clist:cN 4183 {
4184   \tl_gset:Nx #1
4185   { \s__seq \clist_map_function:NN #2 \__seq_wrap_item:n }
4186 }
4187 \cs_new_protected:Npn \seq_gset_from_clist:Nn #1#2
4188 {
4189   \tl_gset:Nx #1
4190   { \s__seq \clist_map_function:nN {#2} \__seq_wrap_item:n }
4191 }
4192 \cs_generate_variant:Nn \seq_set_from_clist:NN { Nc }
4193 \cs_generate_variant:Nn \seq_set_from_clist:NN { c , cc }
4194 \cs_generate_variant:Nn \seq_set_from_clist:Nn { c }
4195 \cs_generate_variant:Nn \seq_gset_from_clist:NN { Nc }
4196 \cs_generate_variant:Nn \seq_gset_from_clist:NN { c , cc }
4197 \cs_generate_variant:Nn \seq_gset_from_clist:Nn { c }

```

(End definition for `\seq_set_from_clist:NN` and others. These functions are documented on page 57.)

`\seq_set_split:Nnn` When the separator is empty, everything is very simple, just map `\__seq_wrap_item:n`  
`\seq_set_split:NnV` through the items of the last argument. For non-trivial separators, the goal is to split  
`\seq_gset_split:Nnn` a given token list at the marker, strip spaces from each item, and remove one set of  
`\seq_gset_split:NnV` outer braces if after removing leading and trailing spaces the item is enclosed within  
`\__seq_set_split:NNnn` braces. After `\tl_replace_all:Nnn`, the token list `\l__seq_internal_a_tl` is a repe-  
`\__seq_set_split_auxi:w` tition of the pattern `\__seq_set_split_auxi:w \prg_do_nothing: <item with spaces>`  
`\__seq_set_split_auxii:w` `\__seq_set_split_end:.` Then, x-expansion causes `\__seq_set_split_auxi:w` to trim  
`\__seq_set_split_end:` spaces, and leaves its result as `\__seq_set_split_auxii:w <trimmed item> \__seq-`  
`\__seq_set_split_end:` `set_split_end:.` This is then converted to the `l3seq` internal structure by another x-  
expansion. In the first step, we insert `\prg_do_nothing:` to avoid losing braces too early:  
that would cause space trimming to act within those lost braces. The second step is solely  
there to strip braces which are outermost after space trimming.

```

4198 \cs_new_protected:Npn \seq_set_split:Nnn
4199 { \__seq_set_split:NNnn \tl_set:Nx }
4200 \cs_new_protected:Npn \seq_gset_split:Nnn
4201 { \__seq_set_split:NNnn \tl_gset:Nx }
4202 \cs_new_protected:Npn \__seq_set_split:NNnn #1#2#3#4
4203 {
4204   \tl_if_empty:nTF {#3}
4205   {
4206     \tl_set:Nn \l__seq_internal_a_tl
4207     { \tl_map_function:nN {#4} \__seq_wrap_item:n }
4208   }
4209   {
4210     \tl_set:Nn \l__seq_internal_a_tl
4211     {
4212       \__seq_set_split_auxi:w \prg_do_nothing:
4213       #4
4214       \__seq_set_split_end:
4215     }
4216     \tl_replace_all:Nnn \l__seq_internal_a_tl { #3 }
4217     {
4218       \__seq_set_split_end:
4219       \__seq_set_split_auxi:w \prg_do_nothing:
4220     }
4221     \tl_set:Nx \l__seq_internal_a_tl { \l__seq_internal_a_tl }
4222   }
4223   #1 #2 { \s__seq \l__seq_internal_a_tl }
4224 }
4225 \cs_new:Npn \__seq_set_split_auxi:w #1 \__seq_set_split_end:
4226 {
4227   \exp_not:N \__seq_set_split_auxii:w
4228   \exp_args:No \tl_trim_spaces:n {#1}
4229   \exp_not:N \__seq_set_split_end:
4230 }
4231 \cs_new:Npn \__seq_set_split_auxii:w #1 \__seq_set_split_end:
4232 { \__seq_wrap_item:n {#1} }
4233 \cs_generate_variant:Nn \seq_set_split:Nnn { NnV }
4234 \cs_generate_variant:Nn \seq_gset_split:Nnn { NnV }

```

(End definition for `\seq_set_split:Nnn` and others. These functions are documented on page 58.)

`\seq_concat:NNN` When concatenating sequences, one must remove the leading `\s__seq` of the second  
`\seq_concat:ccc`  
`\seq_gconcat:NNN`  
`\seq_gconcat:ccc`

sequence. The result starts with `\s__seq` (of the first sequence), which stops `f`-expansion.

```

4235 \cs_new_protected:Npn \seq_concat:NNN #1#2#3
4236 { \tl_set:Nf #1 { \exp_after:wN \use_i:nn \exp_after:wN #2 #3 } }
4237 \cs_new_protected:Npn \seq_gconcat:NNN #1#2#3
4238 { \tl_gset:Nf #1 { \exp_after:wN \use_i:nn \exp_after:wN #2 #3 } }
4239 \cs_generate_variant:Nn \seq_concat:NNN { ccc }
4240 \cs_generate_variant:Nn \seq_gconcat:NNN { ccc }

```

(End definition for `\seq_concat:NNN` and `\seq_gconcat:NNN`. These functions are documented on page 58.)

```

\seq_if_exist_p:N Copies of the cs functions defined in l3basics.
\seq_if_exist_p:c
\seq_if_exist:NTF
\seq_if_exist:cTF
4241 \prg_new_eq_conditional:NNn \seq_if_exist:N \cs_if_exist:N
4242 { TF , T , F , p }
4243 \prg_new_eq_conditional:NNn \seq_if_exist:c \cs_if_exist:c
4244 { TF , T , F , p }

```

(End definition for `\seq_if_exist:N`. This function is documented on page 58.)

## 7.2 Appending data to either end

```

\seq_put_left:Nn When adding to the left of a sequence, remove \s__seq. This is done by \__seq_put_
\seq_put_left:NV left_aux:w, which also stops f-expansion.
\seq_put_left:Nv
\seq_put_left:No
\seq_put_left:Nx
\seq_put_left:cn
\seq_put_left:cV
\seq_put_left:cv
\seq_put_left:co
\seq_put_left:cx
\seq_gput_left:Nn
\seq_gput_left:NV
\seq_gput_left:Nv
\seq_gput_left:No
\seq_gput_left:Nx
\seq_gput_left:cn
\seq_gput_left:cV
\seq_gput_left:cv
\seq_gput_left:co
\seq_gput_left:cx
\__seq_put_left_aux:w
4245 \cs_new_protected:Npn \seq_put_left:Nn #1#2
4246 {
4247   \tl_set:Nx #1
4248   {
4249     \exp_not:n { \s__seq \__seq_item:n {#2} }
4250     \exp_not:f { \exp_after:wN \__seq_put_left_aux:w #1 }
4251   }
4252 }
4253 \cs_new_protected:Npn \seq_gput_left:Nn #1#2
4254 {
4255   \tl_gset:Nx #1
4256   {
4257     \exp_not:n { \s__seq \__seq_item:n {#2} }
4258     \exp_not:f { \exp_after:wN \__seq_put_left_aux:w #1 }
4259   }
4260 }
4261 \cs_new:Npn \__seq_put_left_aux:w \s__seq { \exp_stop_f: }
4262 \cs_generate_variant:Nn \seq_put_left:Nn { NV , Nv , No , Nx }
4263 \cs_generate_variant:Nn \seq_put_left:Nn { c , cV , cv , co , cx }
4264 \cs_generate_variant:Nn \seq_gput_left:Nn { NV , Nv , No , Nx }
4265 \cs_generate_variant:Nn \seq_gput_left:Nn { c , cV , cv , co , cx }

```

(End definition for `\seq_put_left:Nn`, `\seq_gput_left:Nn`, and `\__seq_put_left_aux:w`. These functions are documented on page 58.)

```

\seq_put_right:Nn Since there is no trailing marker, adding an item to the right of a sequence simply means
\seq_put_right:NV wrapping it in \__seq_item:n.
\seq_put_right:Nv
\seq_put_right:No
\seq_put_right:Nx
\seq_put_right:cn
\seq_put_right:cV
\seq_put_right:cv
\seq_put_right:co
\seq_put_right:cx
\seq_gput_right:Nn
\seq_gput_right:NV
\seq_gput_right:Nv
\seq_gput_right:No
\seq_gput_right:Nx
\seq_gput_right:cn

```

```

4270 \cs_generate_variant:Nn \seq_gput_right:Nn { NV , Nv , No , Nx }
4271 \cs_generate_variant:Nn \seq_gput_right:Nn { c , cV , cv , co , cx }
4272 \cs_generate_variant:Nn \seq_put_right:Nn { NV , Nv , No , Nx }
4273 \cs_generate_variant:Nn \seq_put_right:Nn { c , cV , cv , co , cx }

```

(End definition for `\seq_put_right:Nn` and `\seq_gput_right:Nn`. These functions are documented on page 58.)

### 7.3 Modifying sequences

`\__seq_wrap_item:n` This function converts its argument to a proper sequence item in an x-expansion context.

```

4274 \cs_new:Npn \__seq_wrap_item:n #1 { \exp_not:n { \__seq_item:n {#1} } }

```

(End definition for `\__seq_wrap_item:n`.)

`\l__seq_remove_seq` An internal sequence for the removal routines.

```

4275 \seq_new:N \l__seq_remove_seq

```

(End definition for `\l__seq_remove_seq`.)

`\seq_remove_duplicates:N` Removing duplicates means making a new list then copying it.

```

\seq_remove_duplicates:c
\seq_gremove_duplicates:N
\seq_gremove_duplicates:c
\__seq_remove_duplicates:NN
4276 \cs_new_protected:Npn \seq_remove_duplicates:N
4277 { \__seq_remove_duplicates:NN \seq_set_eq:NN }
4278 \cs_new_protected:Npn \seq_gremove_duplicates:N
4279 { \__seq_remove_duplicates:NN \seq_gset_eq:NN }
4280 \cs_new_protected:Npn \__seq_remove_duplicates:NN #1#2
4281 {
4282   \seq_clear:N \l__seq_remove_seq
4283   \seq_map_inline:Nn #2
4284   {
4285     \seq_if_in:NnF \l__seq_remove_seq {##1}
4286     { \seq_put_right:Nn \l__seq_remove_seq {##1} }
4287   }
4288   #1 #2 \l__seq_remove_seq
4289 }
4290 \cs_generate_variant:Nn \seq_remove_duplicates:N { c }
4291 \cs_generate_variant:Nn \seq_gremove_duplicates:N { c }

```

(End definition for `\seq_remove_duplicates:N`, `\seq_gremove_duplicates:N`, and `\__seq_remove_duplicates:NN`. These functions are documented on page 61.)

`\seq_remove_all:Nn` The idea of the code here is to avoid a relatively expensive addition of items one at a time  
`\seq_remove_all:cn` to an intermediate sequence. The approach taken is therefore similar to that in `\__seq_pop_right:NNN`, using a “flexible” x-type expansion to do most of the work. As `\tl_if_eq:nnT` is not expandable, a two-part strategy is needed. First, the x-type expansion  
`\seq_gremove_all:Nn` uses `\str_if_eq:nnT` to find potential matches. If one is found, the expansion is halted  
`\seq_remove_all:cn` and the necessary set up takes place to use the `\tl_if_eq:NNT` test. The x-type is started  
`\__seq_remove_all_aux:NNn` again, including all of the items copied already. This happens repeatedly until the entire sequence has been scanned. The code is set up to avoid needing and intermediate scratch list: the lead-off x-type expansion (`#1 #2 {#2}`) ensures that nothing is lost.

```

4292 \cs_new_protected:Npn \seq_remove_all:Nn
4293 { \__seq_remove_all_aux:NNn \tl_set:Nx }
4294 \cs_new_protected:Npn \seq_gremove_all:Nn
4295 { \__seq_remove_all_aux:NNn \tl_gset:Nx }

```



```

4296 \cs_new_protected:Npn \__seq_remove_all_aux:NNn #1#2#3
4297 {
4298   \__seq_push_item_def:n
4299   {
4300     \str_if_eq:nnT {##1} {#3}
4301     {
4302       \if_false: { \fi: }
4303       \tl_set:Nn \l__seq_internal_b_tl {##1}
4304       #1 #2
4305       { \if_false: } \fi:
4306       \exp_not:o {#2}
4307       \tl_if_eq:NNT \l__seq_internal_a_tl \l__seq_internal_b_tl
4308       { \use_none:nn }
4309     }
4310     \__seq_wrap_item:n {##1}
4311   }
4312   \tl_set:Nn \l__seq_internal_a_tl {#3}
4313   #1 #2 {#2}
4314   \__seq_pop_item_def:
4315 }
4316 \cs_generate_variant:Nn \seq_remove_all:Nn { c }
4317 \cs_generate_variant:Nn \seq_gremove_all:Nn { c }

```

(End definition for `\seq_remove_all:Nn`, `\seq_gremove_all:Nn`, and `\__seq_remove_all_aux:NNn`. These functions are documented on page 61.)

<pre> \seq_reverse:N \seq_reverse:c \seq_greverse:N \seq_greverse:c \__seq_reverse:NN \__seq_reverse_item:nwn </pre>	<pre> Previously, \seq_reverse:N was coded by collecting the items in reverse order after an \exp_stop_f: marker.  \cs_new_protected:Npn \seq_reverse:N #1 {   \cs_set_eq:NN \@@_item:n \@@_reverse_item:nw   \tl_set:Nf #2 { #2 \exp_stop_f: } } \cs_new:Npn \@@_reverse_item:nw #1 #2 \exp_stop_f: {   #2 \exp_stop_f:   \@@_item:n {#1} } </pre>
--	---

At first, this seems optimal, since we can forget about each item as soon as it is placed after `\exp_stop_f:`. Unfortunately,  $\text{\TeX}$ 's usual tail recursion does not take place in this case: since the following `\__seq_reverse_item:nw` only reads tokens until `\exp_stop_f:`, and never reads the `\@@_item:n {#1}` left by the previous call,  $\text{\TeX}$  cannot remove that previous call from the stack, and in particular must retain the various macro parameters in memory, until the end of the replacement text is reached. The stack is thus only flushed after all the `\__seq_reverse_item:nw` are expanded. Keeping track of the arguments of all those calls uses up a memory quadratic in the length of the sequence.  $\text{\TeX}$  can then not cope with more than a few thousand items.

Instead, we collect the items in the argument of `\exp_not:n`. The previous calls are cleanly removed from the stack, and the memory consumption becomes linear.

```

4318 \cs_new_protected:Npn \seq_reverse:N
4319 { \__seq_reverse:NN \tl_set:Nx }

```

```

4320 \cs_new_protected:Npn \seq_greverse:N
4321 { \__seq_reverse:NN \tl_gset:Nx }
4322 \cs_new_protected:Npn \__seq_reverse:NN #1 #2
4323 {
4324   \cs_set_eq:NN \__seq_tmp:w \__seq_item:n
4325   \cs_set_eq:NN \__seq_item:n \__seq_reverse_item:nwn
4326   #1 #2 { #2 \exp_not:n { } }
4327   \cs_set_eq:NN \__seq_item:n \__seq_tmp:w
4328 }
4329 \cs_new:Npn \__seq_reverse_item:nwn #1 #2 \exp_not:n #3
4330 {
4331   #2
4332   \exp_not:n { \__seq_item:n {#1} #3 }
4333 }
4334 \cs_generate_variant:Nn \seq_reverse:N { c }
4335 \cs_generate_variant:Nn \seq_greverse:N { c }

```

(End definition for `\seq_reverse:N` and others. These functions are documented on page 61.)

`\seq_sort:Nn` Implemented in `l3sort`.

`\seq_sort:cn`

`\seq_gsort:Nn` (End definition for `\seq_sort:Nn` and `\seq_gsort:Nn`. These functions are documented on page 61.)

`\seq_gsort:cn`

## 7.4 Sequence conditionals

`\seq_if_empty_p:N` Similar to token lists, we compare with the empty sequence.

`\seq_if_empty_p:c`

`\seq_if_empty:NTF`

`\seq_if_empty:cnTF`

```

4336 \prg_new_conditional:Npnn \seq_if_empty:N #1 { p , T , F , TF }
4337 {
4338   \if_meaning:w #1 \c_empty_seq
4339   \prg_return_true:
4340   \else:
4341     \prg_return_false:
4342   \fi:
4343 }
4344 \cs_generate_variant:Nn \seq_if_empty_p:N { c }
4345 \cs_generate_variant:Nn \seq_if_empty:NT { c }
4346 \cs_generate_variant:Nn \seq_if_empty:NF { c }
4347 \cs_generate_variant:Nn \seq_if_empty:NTF { c }

```

(End definition for `\seq_if_empty:NTF`. This function is documented on page 61.)

`\seq_if_in:NnTF` The approach here is to define `\__seq_item:n` to compare its argument with the test sequence. If the two items are equal, the mapping is terminated and `\group_end: \prg_return_true:` is inserted after skipping over the rest of the recursion. On the other hand, if there is no match then the loop breaks, returning `\prg_return_false:`. Everything is inside a group so that `\__seq_item:n` is preserved in nested situations.

`\seq_if_in:cnTF`

`\seq_if_in:cVTF`

`\seq_if_in:cvTF`

`\seq_if_in:coTF`

`\seq_if_in:cxTF`

`\__seq_if_in:`

```

4348 \prg_new_protected_conditional:Npnn \seq_if_in:Nn #1#2
4349 { T , F , TF }
4350 {
4351   \group_begin:
4352     \tl_set:Nn \l__seq_internal_a_tl {#2}
4353     \cs_set_protected:Npn \__seq_item:n ##1
4354     {
4355       \tl_set:Nn \l__seq_internal_b_tl {##1}

```

```

4356         \if_meaning:w \l__seq_internal_a_tl \l__seq_internal_b_tl
4357         \exp_after:wN \__seq_if_in:
4358         \fi:
4359     }
4360     #1
4361     \group_end:
4362     \prg_return_false:
4363     \__prg_break_point:
4364 }
4365 \cs_new:Npn \__seq_if_in:
4366 { \__prg_break:n { \group_end: \prg_return_true: } }
4367 \cs_generate_variant:Nn \seq_if_in:NnT { c , cV , cv , co , cx }
4368 \cs_generate_variant:Nn \seq_if_in:NnT { c , cV , cv , co , cx }
4369 \cs_generate_variant:Nn \seq_if_in:NnF { NV , Nv , No , Nx }
4370 \cs_generate_variant:Nn \seq_if_in:NnF { c , cV , cv , co , cx }
4371 \cs_generate_variant:Nn \seq_if_in:NnTF { NV , Nv , No , Nx }
4372 \cs_generate_variant:Nn \seq_if_in:NnTF { c , cV , cv , co , cx }

```

(End definition for `\seq_if_in:NnTF` and `\__seq_if_in:.` These functions are documented on page 61.)

## 7.5 Recovering data from sequences

`\__seq_pop:NNNN`    The two `pop` functions share their emptiness tests. We also use a common emptiness test  
`\__seq_pop_TF:NNNN` for all branching `get` and `pop` functions.

```

4373 \cs_new_protected:Npn \__seq_pop:NNNN #1#2#3#4
4374 {
4375     \if_meaning:w #3 \c_empty_seq
4376     \tl_set:Nn #4 { \q_no_value }
4377     \else:
4378         #1#2#3#4
4379     \fi:
4380 }
4381 \cs_new_protected:Npn \__seq_pop_TF:NNNN #1#2#3#4
4382 {
4383     \if_meaning:w #3 \c_empty_seq
4384     % \tl_set:Nn #4 { \q_no_value }
4385     \prg_return_false:
4386     \else:
4387         #1#2#3#4
4388         \prg_return_true:
4389     \fi:
4390 }

```

(End definition for `\__seq_pop:NNNN` and `\__seq_pop_TF:NNNN`.)

`\seq_get_left:NN`    Getting an item from the left of a sequence is pretty easy: just trim off the first item  
`\seq_get_left:cN`    after `\__seq_item:n` at the start. We append a `\q_no_value` item to cover the case of  
`\__seq_get_left:wnw` an empty sequence

```

4391 \cs_new_protected:Npn \seq_get_left:NN #1#2
4392 {
4393     \tl_set:Nx #2
4394     {
4395         \exp_after:wN \__seq_get_left:wnw
4396         #1 \__seq_item:n { \q_no_value } \q_stop

```

```

4397     }
4398   }
4399   \cs_new:Npn \__seq_get_left:wnw #1 \__seq_item:n #2#3 \q_stop
4400     { \exp_not:n {#2} }
4401   \cs_generate_variant:Nn \seq_get_left:NN { c }

```

(End definition for `\seq_get_left:NN` and `\__seq_get_left:wnw`. These functions are documented on page 58.)

`\seq_pop_left:NN` The approach to popping an item is pretty similar to that to get an item, with the only difference being that the sequence itself has to be redefined. This makes it more sensible to use an auxiliary function for the local and global cases.

`\seq_pop_left:cN`

`\seq_gpop_left:NN`

`\seq_gpop_left:cN`

```

4402 \cs_new_protected:Npn \seq_pop_left:NN
4403   { \__seq_pop:NNNN \__seq_pop_left:NNN \tl_set:Nn }
4404 \cs_new_protected:Npn \seq_gpop_left:NN
4405   { \__seq_pop:NNNN \__seq_pop_left:NNN \tl_gset:Nn }
4406 \cs_new_protected:Npn \__seq_pop_left:NNN #1#2#3
4407   { \exp_after:wN \__seq_pop_left:wnwNNN #2 \q_stop #1#2#3 }
4408 \cs_new_protected:Npn \__seq_pop_left:wnwNNN
4409   #1 \__seq_item:n #2#3 \q_stop #4#5#6
4410   {
4411     #4 #5 { #1 #3 }
4412     \tl_set:Nn #6 {#2}
4413   }
4414 \cs_generate_variant:Nn \seq_pop_left:NN { c }
4415 \cs_generate_variant:Nn \seq_gpop_left:NN { c }

```

(End definition for `\seq_pop_left:NN` and others. These functions are documented on page 59.)

`\seq_get_right:NN` First remove `\s__seq` and prepend `\q_no_value`, then take two arguments at a time. Before the right-hand end of the sequence, this is a brace group followed by `\__seq_item:n`, both removed by `\use_none:nn`. At the end of the sequence, the two question marks are taken by `\use_none:nn`, and the assignment is placed before the right-most item. In the next iteration, `\__seq_get_right_loop:nn` receives two empty arguments, and `\use_none:nn` stops the loop.

`\seq_get_right:cN`

`\__seq_get_right_loop:nn`

```

4416 \cs_new_protected:Npn \seq_get_right:NN #1#2
4417   {
4418     \exp_after:wN \use_i_ii:nnn
4419     \exp_after:wN \__seq_get_right_loop:nn
4420     \exp_after:wN \q_no_value
4421     #1
4422     { ?? \tl_set:Nn #2 }
4423     { } { }
4424   }
4425 \cs_new_protected:Npn \__seq_get_right_loop:nn #1#2
4426   {
4427     \use_none:nn #2 {#1}
4428     \__seq_get_right_loop:nn
4429   }
4430 \cs_generate_variant:Nn \seq_get_right:NN { c }

```

(End definition for `\seq_get_right:NN` and `\__seq_get_right_loop:nn`. These functions are documented on page 59.)

`\seq_pop_right:NN` The approach to popping from the right is a bit more involved, but does use some  
`\seq_pop_right:cN` of the same ideas as getting from the right. What is needed is a “flexible length”  
`\seq_gpop_right:NN` way to set a token list variable. This is supplied by the `{ \if_false: } \fi:`  
`\seq_gpop_right:cN` `... \if_false: { \fi: }` construct. Using an x-type expansion and a “non-expanding”  
`\__seq_pop_right:NNN` definition for `\__seq_item:n`, the left-most  $n - 1$  entries in a sequence of  $n$  items are  
`\__seq_pop_right_loop:nn` stored back in the sequence. That needs a loop of unknown length, hence using the  
strange `\if_false:` way of including braces. When the last item of the sequence is  
reached, the closing brace for the assignment is inserted, and `\tl_set:Nn #3` is inserted  
in front of the final entry. This therefore does the pop assignment. One more iteration  
is performed, with an empty argument and `\use_none:nn`, which finally stops the loop.

```

4431 \cs_new_protected:Npn \seq_pop_right:NN
4432 { \__seq_pop:NNNN \__seq_pop_right:NNN \tl_set:Nx }
4433 \cs_new_protected:Npn \seq_gpop_right:NN
4434 { \__seq_pop:NNNN \__seq_pop_right:NNN \tl_gset:Nx }
4435 \cs_new_protected:Npn \__seq_pop_right:NNN #1#2#3
4436 {
4437   \cs_set_eq:NN \__seq_tmp:w \__seq_item:n
4438   \cs_set_eq:NN \__seq_item:n \scan_stop:
4439   #1 #2
4440   { \if_false: } \fi: \s__seq
4441     \exp_after:wN \use_i:nnn
4442     \exp_after:wN \__seq_pop_right_loop:nn
4443     #2
4444     {
4445       \if_false: { \fi: }
4446       \tl_set:Nx #3
4447     }
4448     { } \use_none:nn
4449     \cs_set_eq:NN \__seq_item:n \__seq_tmp:w
4450   }
4451   \cs_new:Npn \__seq_pop_right_loop:nn #1#2
4452   {
4453     #2 { \exp_not:n {#1} }
4454     \__seq_pop_right_loop:nn
4455   }
4456   \cs_generate_variant:Nn \seq_pop_right:NN { c }
4457   \cs_generate_variant:Nn \seq_gpop_right:NN { c }

```

(End definition for `\seq_pop_right:NN` and others. These functions are documented on page 59.)

`\seq_get_left:NNTF` Getting from the left or right with a check on the results. The first argument to `\__-`  
`\seq_get_left:cNTF` `seq_pop_TF:NNNN` is left unused.

```

4458 \prg_new_protected_conditional:Npnn \seq_get_left:NN #1#2 { T , F , TF }
4459 { \__seq_pop_TF:NNNN \prg_do_nothing: \seq_get_left:NN #1#2 }
4460 \prg_new_protected_conditional:Npnn \seq_get_right:NN #1#2 { T , F , TF }
4461 { \__seq_pop_TF:NNNN \prg_do_nothing: \seq_get_right:NN #1#2 }
4462 \cs_generate_variant:Nn \seq_get_left:NNT { c }
4463 \cs_generate_variant:Nn \seq_get_left:NNF { c }
4464 \cs_generate_variant:Nn \seq_get_left:NNTF { c }
4465 \cs_generate_variant:Nn \seq_get_right:NNT { c }
4466 \cs_generate_variant:Nn \seq_get_right:NNF { c }
4467 \cs_generate_variant:Nn \seq_get_right:NNTF { c }

```

(End definition for \seq\_get\_left:NNTF and \seq\_get\_right:NNTF. These functions are documented on page 60.)

\seq\_pop\_left:NNTF More or less the same for popping.  
 \seq\_pop\_left:cNTF 4468 \prg\_new\_protected\_conditional:Npnn \seq\_pop\_left:NN #1#2 { T , F , TF }  
 \seq\_gpop\_left:NNTF 4469 { \\_\_seq\_pop\_TF:NNTN \\_\_seq\_pop\_left:NN \tl\_set:Nn #1 #2 }  
 \seq\_gpop\_left:cNTF 4470 \prg\_new\_protected\_conditional:Npnn \seq\_gpop\_left:NN #1#2 { T , F , TF }  
 \seq\_pop\_right:NNTF 4471 { \\_\_seq\_pop\_TF:NNTN \\_\_seq\_pop\_left:NN \tl\_gset:Nn #1 #2 }  
 \seq\_pop\_right:cNTF 4472 \prg\_new\_protected\_conditional:Npnn \seq\_pop\_right:NN #1#2 { T , F , TF }  
 \seq\_gpop\_right:NNTF 4473 { \\_\_seq\_pop\_TF:NNTN \\_\_seq\_pop\_right:NN \tl\_set:Nx #1 #2 }  
 \seq\_gpop\_right:cNTF 4474 \prg\_new\_protected\_conditional:Npnn \seq\_gpop\_right:NN #1#2 { T , F , TF }  
 4475 { \\_\_seq\_pop\_TF:NNTN \\_\_seq\_pop\_right:NN \tl\_gset:Nx #1 #2 }  
 4476 \cs\_generate\_variant:Nn \seq\_pop\_left:NNT { c }  
 4477 \cs\_generate\_variant:Nn \seq\_pop\_left:NNTF { c }  
 4478 \cs\_generate\_variant:Nn \seq\_gpop\_left:NNT { c }  
 4479 \cs\_generate\_variant:Nn \seq\_gpop\_left:NNTF { c }  
 4480 \cs\_generate\_variant:Nn \seq\_gpop\_right:NNT { c }  
 4481 \cs\_generate\_variant:Nn \seq\_gpop\_right:NNTF { c }  
 4482 \cs\_generate\_variant:Nn \seq\_pop\_right:NNT { c }  
 4483 \cs\_generate\_variant:Nn \seq\_pop\_right:NNTF { c }  
 4484 \cs\_generate\_variant:Nn \seq\_gpop\_right:NNT { c }  
 4485 \cs\_generate\_variant:Nn \seq\_gpop\_right:NNTF { c }  
 4486 \cs\_generate\_variant:Nn \seq\_gpop\_right:NNTF { c }  
 4487 \cs\_generate\_variant:Nn \seq\_gpop\_right:NNTF { c }

(End definition for \seq\_pop\_left:NNTF and others. These functions are documented on page 60.)

\seq\_item:Nn The idea here is to find the offset of the item from the left, then use a loop  
 \seq\_item:cn to grab the correct item. If the resulting offset is too large, then the stop code  
 \\_\_seq\_item:wNn { ? \\_\_prg\_break: } { } is used by the auxiliary, terminating the loop and return-  
 \\_\_seq\_item:nN ing nothing at all.  
 \\_\_seq\_item:nnn 4488 \cs\_new:Npn \seq\_item:Nn #1  
 4489 { \exp\_after:wN \\_\_seq\_item:wNn #1 \q\_stop #1 }  
 4490 \cs\_new:Npn \\_\_seq\_item:wNn \s\_\_seq #1 \q\_stop #2#3  
 4491 {  
 4492 \exp\_args:Nf \\_\_seq\_item:nnn  
 4493 { \exp\_args:Nf \\_\_seq\_item:nN { \int\_eval:n {#3} } #2 }  
 4494 #1  
 4495 { ? \\_\_prg\_break: } { }  
 4496 \\_\_prg\_break\_point:  
 4497 }  
 4498 \cs\_new:Npn \\_\_seq\_item:nN #1#2  
 4499 {  
 4500 \int\_compare:nNnTF {#1} < 0  
 4501 { \int\_eval:n { \seq\_count:N #2 + 1 + #1 } }  
 4502 {#1}  
 4503 }  
 4504 \cs\_new:Npn \\_\_seq\_item:nnn #1#2#3  
 4505 {  
 4506 \use\_none:n #2  
 4507 \int\_compare:nNnTF {#1} = 1  
 4508 { \\_\_prg\_break:n { \exp\_not:n {#3} } }  
 4509 { \exp\_args:Nf \\_\_seq\_item:nnn { \int\_eval:n { #1 - 1 } } }  
 4510 }  
 4511 \cs\_generate\_variant:Nn \seq\_item:Nn { c }

(End definition for `\seq_item:Nn` and others. These functions are documented on page 59.)

## 7.6 Mapping to sequences

`\seq_map_break:` To break a function, the special token `\__prg_break_point:Nn` is used to find the end of the code. Any ending code is then inserted before the return value of `\seq_map_break:n` is inserted.

```
4512 \cs_new:Npn \seq_map_break:
4513 { \__prg_map_break:Nn \seq_map_break: { } }
4514 \cs_new:Npn \seq_map_break:n
4515 { \__prg_map_break:Nn \seq_map_break: }
```

(End definition for `\seq_map_break:` and `\seq_map_break:n`. These functions are documented on page 62.)

`\seq_map_function:NN`  
`\seq_map_function:cN`  
`\__seq_map_function:NNn` The idea here is to apply the code of #2 to each item in the sequence without altering the definition of `\__seq_item:n`. This is done as by noting that every odd token in the sequence must be `\__seq_item:n`, which can be gobbled by `\use_none:n`. At the end of the loop, #2 is instead `? \seq_map_break:`, which therefore breaks the loop without needing to do a (relatively-expensive) quark test.

```
4516 \cs_new:Npn \seq_map_function:NN #1#2
4517 {
4518   \exp_after:wN \use_i_ii:nnn
4519   \exp_after:wN \__seq_map_function:NNn
4520   \exp_after:wN #2
4521   #1
4522   { ? \seq_map_break: } { }
4523   \__prg_break_point:Nn \seq_map_break: { }
4524 }
4525 \cs_new:Npn \__seq_map_function:NNn #1#2#3
4526 {
4527   \use_none:n #2
4528   #1 {#3}
4529   \__seq_map_function:NNn #1
4530 }
4531 \cs_generate_variant:Nn \seq_map_function:NN { c }
```

(End definition for `\seq_map_function:NN` and `\__seq_map_function:NNn`. These functions are documented on page 61.)

`\__seq_push_item_def:n`  
`\__seq_push_item_def:x`  
`\__seq_push_item_def:`  
`\__seq_pop_item_def:` The definition of `\__seq_item:n` needs to be saved and restored at various points within the mapping and manipulation code. That is handled here: as always, this approach uses global assignments.

```
4532 \cs_new_protected:Npn \__seq_push_item_def:n
4533 {
4534   \__seq_push_item_def:
4535   \cs_gset:Npn \__seq_item:n ##1
4536 }
4537 \cs_new_protected:Npn \__seq_push_item_def:x
4538 {
4539   \__seq_push_item_def:
4540   \cs_gset:Npx \__seq_item:n ##1
4541 }
4542 \cs_new_protected:Npn \__seq_push_item_def:
```

```

4543 {
4544     \int_gincr:N \g__prg_map_int
4545     \cs_gset_eq:cN { __prg_map_ \int_use:N \g__prg_map_int :w }
4546     \__seq_item:n
4547 }
4548 \cs_new_protected:Npn \__seq_pop_item_def:
4549 {
4550     \cs_gset_eq:Nc \__seq_item:n
4551     { __prg_map_ \int_use:N \g__prg_map_int :w }
4552     \int_gdecr:N \g__prg_map_int
4553 }

```

(End definition for \\_\_seq\_push\_item\_def:n, \\_\_seq\_push\_item\_def:, and \\_\_seq\_pop\_item\_def:.)

**\seq\_map\_inline:Nn** The idea here is that \\_\_seq\_item:n is already “applied” to each item in a sequence, and so an in-line mapping is just a case of redefining \\_\_seq\_item:n.

**\seq\_map\_inline:cn**

```

4554 \cs_new_protected:Npn \seq_map_inline:Nn #1#2
4555 {
4556     \__seq_push_item_def:n {#2}
4557     #1
4558     \__prg_break_point:Nn \seq_map_break: { \__seq_pop_item_def: }
4559 }
4560 \cs_generate_variant:Nn \seq_map_inline:Nn { c }

```

(End definition for \seq\_map\_inline:Nn. This function is documented on page 62.)

**\seq\_map\_variable:NNn** This is just a specialised version of the in-line mapping function, using an x-type expansion for the code set up so that the number of # tokens required is as expected.

**\seq\_map\_variable:Ncn**

**\seq\_map\_variable:cNn**

**\seq\_map\_variable:ccn**

```

4561 \cs_new_protected:Npn \seq_map_variable:NNn #1#2#3
4562 {
4563     \__seq_push_item_def:x
4564     {
4565         \tl_set:Nn \exp_not:N #2 {##1}
4566         \exp_not:n {#3}
4567     }
4568     #1
4569     \__prg_break_point:Nn \seq_map_break: { \__seq_pop_item_def: }
4570 }
4571 \cs_generate_variant:Nn \seq_map_variable:NNn { Nc }
4572 \cs_generate_variant:Nn \seq_map_variable:NNn { c , cc }

```

(End definition for \seq\_map\_variable:NNn. This function is documented on page 62.)

**\seq\_count:N** Counting the items in a sequence is done using the same approach as for other count functions: turn each entry into a +1 then use integer evaluation to actually do the mathematics.

**\seq\_count:c**

**\\_\_seq\_count:n**

```

4573 \cs_new:Npn \seq_count:N #1
4574 {
4575     \int_eval:n
4576     {
4577         0
4578         \seq_map_function:NN #1 \__seq_count:n
4579     }
4580 }
4581 \cs_new:Npn \__seq_count:n #1 { + 1 }
4582 \cs_generate_variant:Nn \seq_count:N { c }

```



(End definition for `\seq_count:N` and `\_seq_count:n`. These functions are documented on page 63.)

## 7.7 Using sequences

`\seq_use:Nnnn` See `\clist_use:Nnnn` for a general explanation. The main difference is that we use `\_seq_item:n` as a delimiter rather than commas. We also need to add `\_seq_item:n` at various places, and `\s__seq`.

```

\seq_use:cnnn
\_seq_use:NNnNnn
\_seq_use_setup:w
\_seq_use:nwwwnwn
\_seq_use:nwnn
\seq_use:Nn
\seq_use:cn
4583 \cs_new:Npn \seq_use:Nnnn #1#2#3#4
4584 {
4585   \seq_if_exist:NTF #1
4586   {
4587     \int_case:nnF { \seq_count:N #1 }
4588     {
4589       { 0 } { }
4590       { 1 } { \exp_after:wN \_seq_use:NNnNnn #1 ? { } { } }
4591       { 2 } { \exp_after:wN \_seq_use:NNnNnn #1 {#2} }
4592     }
4593     {
4594       \exp_after:wN \_seq_use_setup:w #1 \_seq_item:n
4595       \q_mark { \_seq_use:nwwwnwn {#3} }
4596       \q_mark { \_seq_use:nwnn {#4} }
4597       \q_stop { }
4598     }
4599   }
4600   {
4601     \_msg_kernel_expandable_error:nnn
4602     { kernel } { bad-variable } {#1}
4603   }
4604 }
4605 \cs_generate_variant:Nn \seq_use:Nnnn { c }
4606 \cs_new:Npn \_seq_use:NNnNnn #1#2#3#4#5#6 { \exp_not:n { #3 #6 #5 } }
4607 \cs_new:Npn \_seq_use_setup:w \s__seq { \_seq_use:nwwwnwn { } }
4608 \cs_new:Npn \_seq_use:nwwwnwn
4609   #1 \_seq_item:n #2 \_seq_item:n #3 \_seq_item:n #4#5
4610   \q_mark #6#7 \q_stop #8
4611   {
4612     #6 \_seq_item:n {#3} \_seq_item:n {#4} #5
4613     \q_mark {#6} #7 \q_stop { #8 #1 #2 }
4614   }
4615 \cs_new:Npn \_seq_use:nwnn #1 \_seq_item:n #2 #3 \q_stop #4
4616   { \exp_not:n { #4 #1 #2 } }
4617 \cs_new:Npn \seq_use:Nn #1#2
4618   { \seq_use:Nnnn #1 {#2} {#2} {#2} }
4619 \cs_generate_variant:Nn \seq_use:Nn { c }

```

(End definition for `\seq_use:Nnnn` and others. These functions are documented on page 63.)

## 7.8 Sequence stacks

The same functions as for sequences, but with the correct naming.

`\seq_push:Nn` Pushing to a sequence is the same as adding on the left.

```

\seq_push:NV
\seq_push:Nv
\seq_push:No
\seq_push:Nx
\seq_push:cn
\seq_push:cV
\seq_push:cV
\seq_push:co
\seq_push:cx
\seq_gpush:Nn
\seq_gpush:NV
\seq_gpush:Nv

```

```

4621 \cs_new_eq:NN \seq_push:Nv \seq_put_left:Nv
4622 \cs_new_eq:NN \seq_push:Nv \seq_put_left:Nv
4623 \cs_new_eq:NN \seq_push:No \seq_put_left:No
4624 \cs_new_eq:NN \seq_push:Nx \seq_put_left:Nx
4625 \cs_new_eq:NN \seq_push:cn \seq_put_left:cn
4626 \cs_new_eq:NN \seq_push:cV \seq_put_left:cV
4627 \cs_new_eq:NN \seq_push:cv \seq_put_left:cv
4628 \cs_new_eq:NN \seq_push:co \seq_put_left:co
4629 \cs_new_eq:NN \seq_push:cx \seq_put_left:cx
4630 \cs_new_eq:NN \seq_gpush:Nn \seq_gput_left:Nn
4631 \cs_new_eq:NN \seq_gpush:Nv \seq_gput_left:Nv
4632 \cs_new_eq:NN \seq_gpush:No \seq_gput_left:No
4633 \cs_new_eq:NN \seq_gpush:Nx \seq_gput_left:Nx
4634 \cs_new_eq:NN \seq_gpush:cn \seq_gput_left:cn
4635 \cs_new_eq:NN \seq_gpush:cV \seq_gput_left:cV
4636 \cs_new_eq:NN \seq_gpush:cv \seq_gput_left:cv
4637 \cs_new_eq:NN \seq_gpush:co \seq_gput_left:co
4638 \cs_new_eq:NN \seq_gpush:cx \seq_gput_left:cx
4639 \cs_new_eq:NN \seq_gpush:cx \seq_gput_left:cx

```

(End definition for `\seq_push:Nn` and `\seq_gpush:Nn`. These functions are documented on page 65.)

`\seq_get:NN` In most cases, getting items from the stack does not need to specify that this is from the  
`\seq_get:cN` left. So alias are provided.

```

\seq_pop:NN 4640 \cs_new_eq:NN \seq_get:NN \seq_get_left:NN
\seq_pop:cN 4641 \cs_new_eq:NN \seq_get:cN \seq_get_left:cN
\seq_gpop:NN 4642 \cs_new_eq:NN \seq_pop:NN \seq_pop_left:NN
\seq_gpop:cN 4643 \cs_new_eq:NN \seq_pop:cN \seq_pop_left:cN
4644 \cs_new_eq:NN \seq_gpop:NN \seq_gpop_left:NN
4645 \cs_new_eq:NN \seq_gpop:cN \seq_gpop_left:cN

```

(End definition for `\seq_get:NN`, `\seq_pop:NN`, and `\seq_gpop:NN`. These functions are documented on page 64.)

`\seq_get:NNTF` More copies.  
`\seq_get:cNTF` 4646 \prg\_new\_eq\_conditional:NNn \seq\_get:NN \seq\_get\_left:NN { T , F , TF }  
`\seq_pop:NNTF` 4647 \prg\_new\_eq\_conditional:NNn \seq\_get:cN \seq\_get\_left:cN { T , F , TF }  
`\seq_pop:cNTF` 4648 \prg\_new\_eq\_conditional:NNn \seq\_pop:NN \seq\_pop\_left:NN { T , F , TF }  
`\seq_gpop:NNTF` 4649 \prg\_new\_eq\_conditional:NNn \seq\_pop:cN \seq\_pop\_left:cN { T , F , TF }  
`\seq_gpop:cNTF` 4650 \prg\_new\_eq\_conditional:NNn \seq\_gpop:NN \seq\_gpop\_left:NN { T , F , TF }  
4651 \prg\_new\_eq\_conditional:NNn \seq\_gpop:cN \seq\_gpop\_left:cN { T , F , TF }

(End definition for `\seq_get:NNTF`, `\seq_pop:NNTF`, and `\seq_gpop:NNTF`. These functions are documented on page 64.)

## 7.9 Viewing sequences

`\seq_show:N` Apply the general `\_msg_show_variable:NNNnn`.

```

\seq_show:c 4652 \cs_new_protected:Npn \seq_show:N #1
4653 {
4654   \_msg_show_variable:NNNnn #1
4655   \seq_if_exist:NNTF \seq_if_empty:NNTF { seq }
4656   { \seq_map_function:NN #1 \_msg_show_item:n }
4657 }
4658 \cs_generate_variant:Nn \seq_show:N { c }

```

(End definition for `\seq_show:N`. This function is documented on page 67.)

`\seq_log:N` Redirect output of `\seq_show:N` to the log.

```
\seq_log:c 4659 \cs_new_protected:Npn \seq_log:N
           4660 { \__msg_log_next: \seq_show:N }
           4661 \cs_generate_variant:Nn \seq_log:N { c }
```

(End definition for `\seq_log:N`. This function is documented on page 67.)

## 7.10 Scratch sequences

`\l_tmpa_seq` Temporary comma list variables.

```
\l_tmpb_seq 4662 \seq_new:N \l_tmpa_seq
\g_tmpa_seq 4663 \seq_new:N \l_tmpb_seq
\g_tmpb_seq 4664 \seq_new:N \g_tmpa_seq
           4665 \seq_new:N \g_tmpb_seq
```

(End definition for `\l_tmpa_seq` and others. These variables are documented on page 67.)

```
4666 </initex | package>
```

## 8 l3int implementation

```
4667 <*initex | package>
```

```
4668 <@@=int>
```

The following test files are used for this code: `m3int001,m3int002,m3int03`.

`\c_max_register_int` Done in l3basics.

(End definition for `\c_max_register_int`. This variable is documented on page 78.)

`\__int_to_roman:w` Done in l3basics.

`\if_int_compare:w` (End definition for `\__int_to_roman:w` and `\if_int_compare:w`.)

`\or:` Done in l3basics.

(End definition for `\or:`. This function is documented on page 79.)

`\__int_value:w` Here are the remaining primitives for number comparisons and expressions.

```
\__int_eval:w 4669 \cs_new_eq:NN \__int_value:w \tex_number:D
\__int_eval_end: 4670 \cs_new_eq:NN \__int_eval:w \etex_numexpr:D
\if_int_odd:w 4671 \cs_new_eq:NN \__int_eval_end: \tex_relax:D
\if_case:w 4672 \cs_new_eq:NN \if_int_odd:w \tex_ifodd:D
           4673 \cs_new_eq:NN \if_case:w \tex_ifcase:D
```

(End definition for `\__int_value:w` and others.)

## 8.1 Integer expressions

**\int\_eval:n** Wrapper for `\__int_eval:w`: can be used in an integer expression or directly in the input stream.

```
4674 \cs_new:Npn \int_eval:n #1
4675 { \__int_value:w \__int_eval:w #1 \__int_eval_end: }
```

(End definition for `\int_eval:n`. This function is documented on page 68.)

**\int\_abs:n** Functions for min, max, and absolute value with only one evaluation. The absolute value is obtained by removing a leading sign if any. All three functions expand in two steps.

**\\_\_int\_abs:N**

**\int\_max:nn**

**\int\_min:nn**

**\\_\_int\_maxmin:wwN**

```
4676 \cs_new:Npn \int_abs:n #1
4677 {
4678   \__int_value:w \exp_after:wN \__int_abs:N
4679   \__int_value:w \__int_eval:w #1 \__int_eval_end:
4680   \exp_stop_f:
4681 }
4682 \cs_new:Npn \__int_abs:N #1
4683 { \if_meaning:w - #1 \else: \exp_after:wN #1 \fi: }
4684 \cs_set:Npn \int_max:nn #1#2
4685 {
4686   \__int_value:w \exp_after:wN \__int_maxmin:wwN
4687   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
4688   \__int_value:w \__int_eval:w #2 ;
4689   >
4690   \exp_stop_f:
4691 }
4692 \cs_set:Npn \int_min:nn #1#2
4693 {
4694   \__int_value:w \exp_after:wN \__int_maxmin:wwN
4695   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
4696   \__int_value:w \__int_eval:w #2 ;
4697   <
4698   \exp_stop_f:
4699 }
4700 \cs_new:Npn \__int_maxmin:wwN #1 ; #2 ; #3
4701 {
4702   \if_int_compare:w #1 #3 #2 ~
4703   #1
4704   \else:
4705   #2
4706   \fi:
4707 }
```

(End definition for `\int_abs:n` and others. These functions are documented on page 68.)

**\int\_div\_truncate:nn**

**\int\_div\_round:nn**

**\int\_mod:nn**

**\\_\_int\_div\_truncate:NwNw**

**\\_\_int\_mod:ww**

As `\__int_eval:w` rounds the result of a division we also provide a version that truncates the result. We use an auxiliary to make sure numerator and denominator are only evaluated once: this comes in handy when those are more expressions are expensive to evaluate (e.g., `\tl_count:n`). If the numerator `#1#2` is 0, then we divide 0 by the denominator (this ensures that 0/0 is correctly reported as an error). Otherwise, shift the numerator `#1#2` towards 0 by  $(| \#3\#4 | - 1)/2$ , which we round away from zero. It turns out that this quantity exactly compensates the difference between  $\varepsilon$ -TeX's rounding and

the truncating behaviour that we want. The details are thanks to Heiko Oberdiek: getting things right in all cases is not so easy.

```

4708 \cs_new:Npn \int_div_truncate:nn #1#2
4709 {
4710   \__int_value:w \__int_eval:w
4711   \exp_after:wN \__int_div_truncate:NwNw
4712   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
4713   \__int_value:w \__int_eval:w #2 ;
4714   \__int_eval_end:
4715 }
4716 \cs_new:Npn \__int_div_truncate:NwNw #1#2; #3#4;
4717 {
4718   \if_meaning:w 0 #1
4719   0
4720   \else:
4721   (
4722     #1#2
4723     \if_meaning:w - #1 + \else: - \fi:
4724     ( \if_meaning:w - #3 - \fi: #3#4 - 1 ) / 2
4725   )
4726   \fi:
4727   / #3#4
4728 }

```

For the sake of completeness:

```

4729 \cs_new:Npn \int_div_round:nn #1#2
4730 { \__int_value:w \__int_eval:w ( #1 ) / ( #2 ) \__int_eval_end: }

```

Finally there's the modulus operation.

```

4731 \cs_new:Npn \int_mod:nn #1#2
4732 {
4733   \__int_value:w \__int_eval:w \exp_after:wN \__int_mod:ww
4734   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
4735   \__int_value:w \__int_eval:w #2 ;
4736   \__int_eval_end:
4737 }
4738 \cs_new:Npn \__int_mod:ww #1; #2;
4739 { #1 - ( \__int_div_truncate:NwNw #1 ; #2 ; ) * #2 }

```

(End definition for `\int_div_truncate:nn` and others. These functions are documented on page 69.)

## 8.2 Creating and initialising integers

`\int_new:N` Two ways to do this: one for the format and one for the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> package. In plain T<sub>E</sub>X, `\int_new:c` `\newcount` (and other allocators) are `\outer:` to allow the code here to work in “generic” mode this is therefore accessed by name. (The same applies to `\newbox`, `\newdimen` and so on.)

```

4740 \*package>
4741 \cs_new_protected:Npn \int_new:N #1
4742 {
4743   \__chk_if_free_cs:N #1
4744   \cs:w newcount \cs_end: #1
4745 }
4746 \*package>
4747 \cs_generate_variant:Nn \int_new:N { c }

```

(End definition for `\int_new:N`. This function is documented on page 69.)

`\int_const:Nn` As stated, most constants can be defined as `\chardef` or `\mathchardef` but that's engine dependent. As a result, there is some set up code to determine what can be done. No  
`\int_const:cn` full engine testing just yet so everything is a little awkward.  
`\__int_constdef:Nw`  
`\c__max_constdef_int`

```

4748 \cs_new_protected:Npn \int_const:Nn #1#2
4749 {
4750   \int_compare:nNnTF {#2} < \c_zero
4751   {
4752     \int_new:N #1
4753     \int_gset:Nn #1 {#2}
4754   }
4755   {
4756     \int_compare:nNnTF {#2} > \c__max_constdef_int
4757     {
4758       \int_new:N #1
4759       \int_gset:Nn #1 {#2}
4760     }
4761     {
4762       \__chk_if_free_cs:N #1
4763       \tex_global:D \__int_constdef:Nw #1 =
4764         \__int_eval:w #2 \__int_eval_end:
4765     }
4766   }
4767 }
4768 \cs_generate_variant:Nn \int_const:Nn { c }
4769 \if_int_odd:w 0
4770   \cs_if_exist:NT \luatex luatexversion:D { 1 }
4771   \cs_if_exist:NT \uptex_disablecjktoken:D
4772     { \if_int_compare:w \ptex_jis:D "2121 = "3000 ~ 1 \fi: }
4773   \cs_if_exist:NT \xetex_XeTeXversion:D { 1 } ~
4774   \cs_if_exist:NTF \uptex_disablecjktoken:D
4775     { \cs_new_eq:NN \__int_constdef:Nw \uptex_kchardef:D }
4776     { \cs_new_eq:NN \__int_constdef:Nw \tex_chardef:D }
4777   \__int_constdef:Nw \c__max_constdef_int 1114111 ~
4778 \else:
4779   \cs_new_eq:NN \__int_constdef:Nw \tex_mathchardef:D
4780   \tex_mathchardef:D \c__max_constdef_int 32767 ~
4781 \fi:

```

(End definition for `\int_const:Nn`, `\__int_constdef:Nw`, and `\c__max_constdef_int`. These functions are documented on page 69.)

`\int_zero:N` Functions that reset an *integer* register to zero.  
`\int_zero:c`  
`\int_gzero:N`  
`\int_gzero:c`

```

4782 \cs_new_protected:Npn \int_zero:N #1 { #1 = \c_zero }
4783 \cs_new_protected:Npn \int_gzero:N #1 { \tex_global:D #1 = \c_zero }
4784 \cs_generate_variant:Nn \int_zero:N { c }
4785 \cs_generate_variant:Nn \int_gzero:N { c }

```

(End definition for `\int_zero:N` and `\int_gzero:N`. These functions are documented on page 69.)

`\int_zero_new:N` Create a register if needed, otherwise clear it.  
`\int_zero_new:c`  
`\int_gzero_new:N`  
`\int_gzero_new:c`

```

4786 \cs_new_protected:Npn \int_zero_new:N #1
4787 { \int_if_exist:NTF #1 { \int_zero:N #1 } { \int_new:N #1 } }

```

```

4788 \cs_new_protected:Npn \int_gzero_new:N #1
4789 { \int_if_exist:NTF #1 { \int_gzero:N #1 } { \int_new:N #1 } }
4790 \cs_generate_variant:Nn \int_zero_new:N { c }
4791 \cs_generate_variant:Nn \int_gzero_new:N { c }

```

(End definition for `\int_zero_new:N` and `\int_gzero_new:N`. These functions are documented on page 69.)

```

\int_set_eq:NN Setting equal means using one integer inside the set function of another.
\int_set_eq:cn 4792 \cs_new_protected:Npn \int_set_eq:NN #1#2 { #1 = #2 }
\int_set_eq:Nc 4793 \cs_generate_variant:Nn \int_set_eq:NN { c }
\int_set_eq:cc 4794 \cs_generate_variant:Nn \int_set_eq:NN { Nc , cc }
\int_gset_eq:NN 4795 \cs_new_protected:Npn \int_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
\int_gset_eq:cn 4796 \cs_generate_variant:Nn \int_gset_eq:NN { c }
\int_gset_eq:Nc 4797 \cs_generate_variant:Nn \int_gset_eq:NN { Nc , cc }
\int_gset_eq:cc

```

(End definition for `\int_set_eq:NN` and `\int_gset_eq:NN`. These functions are documented on page 69.)

```

\int_if_exist_p:N Copies of the cs functions defined in l3basics.
\int_if_exist_p:c 4798 \prg_new_eq_conditional:NNn \int_if_exist:N \cs_if_exist:N
\int_if_exist:NTF 4799 { TF , T , F , p }
\int_if_exist:cTF 4800 \prg_new_eq_conditional:NNn \int_if_exist:c \cs_if_exist:c
4801 { TF , T , F , p }

```

(End definition for `\int_if_exist:NTF`. This function is documented on page 70.)

### 8.3 Setting and incrementing integers

```

\int_add:Nn Adding and subtracting to and from a counter ...
\int_add:cn 4802 \cs_new_protected:Npn \int_add:Nn #1#2
\int_gadd:Nn 4803 { \tex_advance:D #1 by \__int_eval:w #2 \__int_eval_end: }
\int_gadd:cn 4804 \cs_new_protected:Npn \int_sub:Nn #1#2
\int_sub:Nn 4805 { \tex_advance:D #1 by - \__int_eval:w #2 \__int_eval_end: }
\int_sub:cn 4806 \cs_new_protected:Npn \int_gadd:Nn
\int_gsub:Nn 4807 { \tex_global:D \int_add:Nn }
\int_gsub:cn 4808 \cs_new_protected:Npn \int_gsub:Nn
4809 { \tex_global:D \int_sub:Nn }
4810 \cs_generate_variant:Nn \int_add:Nn { c }
4811 \cs_generate_variant:Nn \int_gadd:Nn { c }
4812 \cs_generate_variant:Nn \int_sub:Nn { c }
4813 \cs_generate_variant:Nn \int_gsub:Nn { c }

```

(End definition for `\int_add:Nn` and others. These functions are documented on page 70.)

```

\int_incr:N Incrementing and decrementing of integer registers is done with the following functions.
\int_incr:c 4814 \cs_new_protected:Npn \int_incr:N #1
\int_gincr:N 4815 { \tex_advance:D #1 \c_one }
\int_gincr:c 4816 \cs_new_protected:Npn \int_decr:N #1
\int_decr:N 4817 { \tex_advance:D #1 - \c_one }
\int_decr:c 4818 \cs_new_protected:Npn \int_gincr:N
\int_gdecr:N 4819 { \tex_global:D \int_incr:N }
\int_gdecr:c 4820 \cs_new_protected:Npn \int_gdecr:N
4821 { \tex_global:D \int_decr:N }
4822 \cs_generate_variant:Nn \int_incr:N { c }

```

```

4823 \cs_generate_variant:Nn \int_decr:N { c }
4824 \cs_generate_variant:Nn \int_gincr:N { c }
4825 \cs_generate_variant:Nn \int_gdecr:N { c }

```

(End definition for `\int_incr:N` and others. These functions are documented on page 70.)

`\int_set:Nn` As integers are register-based TeX issues an error if they are not defined. Thus there is no need for the checking code seen with token list variables.

`\int_gset:Nn`

```

4826 \cs_new_protected:Npn \int_set:Nn #1#2
4827 { #1 ~ \__int_eval:w #2 \__int_eval_end: }
4828 \cs_new_protected:Npn \int_gset:Nn { \tex_global:D \int_set:Nn }
4829 \cs_generate_variant:Nn \int_set:Nn { c }
4830 \cs_generate_variant:Nn \int_gset:Nn { c }

```

(End definition for `\int_set:Nn` and `\int_gset:Nn`. These functions are documented on page 70.)

## 8.4 Using integers

`\int_use:N` Here is how counters are accessed:

`\int_use:c`

```

4831 \cs_new_eq:NN \int_use:N \tex_the:D

```

We hand-code this for some speed gain:

```

4832 %\cs_generate_variant:Nn \int_use:N { c }
4833 \cs_new:Npn \int_use:c #1 { \tex_the:D \cs:w #1 \cs_end: }

```

(End definition for `\int_use:N`. This function is documented on page 70.)

## 8.5 Integer expression conditionals

`\__prg_compare_error:` Those functions are used for comparison tests which use a simple syntax where only one set of braces is required and additional operators such as `!=` and `>=` are supported. The tests first evaluate their left-hand side, with a trailing `\__prg_compare_error:.` This marker is normally not expanded, but if the relation symbol is missing from the test's argument, then the marker inserts `=` (and itself) after triggering the relevant TeX error. If the first token which appears after evaluating and removing the left-hand side is not a known relation symbol, then a judiciously placed `\__prg_compare_error:Nw` gets expanded, cleaning up the end of the test and telling the user what the problem was.

```

4834 \cs_new_protected:Npn \__prg_compare_error:
4835 {
4836   \if_int_compare:w \c_zero \c_zero \fi:
4837   =
4838   \__prg_compare_error:
4839 }
4840 \cs_new:Npn \__prg_compare_error:Nw
4841 #1#2 \q_stop
4842 {
4843   { }
4844   \c_zero \fi:
4845   \__msg_kernel_expandable_error:nnn
4846   { kernel } { unknown-comparison } {#1}
4847   \prg_return_false:
4848 }

```

(End definition for `\__prg_compare_error:` and `\__prg_compare_error:Nw`.)



```

\int_compare_p:n Comparison tests using a simple syntax where only one set of braces is required, additional
\int_compare:nTF operators such as != and >= are supported, and multiple comparisons can be performed
\__int_compare:w at once, for instance 0 < 5 <= 1. The idea is to loop through the argument, finding one
\__int_compare:Nw operand at a time, and comparing it to the previous one. The looping auxiliary \__-
\__int_compare:NNw int_compare:Nw reads one <operand> and one <comparison> symbol, and leaves roughly
\__int_compare:nnN <operand> \prg_return_false: \fi:
\__int_compare_end=:NNw \reverse_if:N \if_int_compare:w <operand> <comparison>
\__int_compare=:NNw \__int_compare:Nw
\__int_compare<:NNw
\__int_compare>:NNw
\__int_compare=:NNw
\__int_compare=:NNw
\__int_compare=:NNw
\__int_compare=:NNw
\__int_compare=:NNw
\__int_compare=:NNw

```

in the input stream. Each call to this auxiliary provides the second operand of the last call's `\if_int_compare:w`. If one of the *<comparisons>* is `false`, the `true` branch of the TeX conditional is taken (because of `\reverse_if:N`), immediately returning `false` as the result of the test. There is no TeX conditional waiting the first operand, so we add an `\if_false:` and expand by hand with `\__int_value:w`, thus skipping `\prg_return_false:` on the first iteration.

Before starting the loop, the first step is to make sure that there is at least one relation symbol. We first let TeX evaluate this left hand side of the (in)equality using `\__int_eval:w`. Since the relation symbols `<`, `>`, `=` and `!` are not allowed in integer expressions, they would terminate the expression. If the argument contains no relation symbol, `\__prg_compare_error:` is expanded, inserting `=` and itself after an error. In all cases, `\__int_compare:w` receives as its argument an integer, a relation symbol, and some more tokens. We then setup the loop, which is ended by the two odd-looking items `e` and `{=nd_}`, with a trailing `\q_stop` used to grab the entire argument when necessary.

```

4849 \prg_new_conditional:Npnn \int_compare:n #1 { p , T , F , TF }
4850 {
4851   \exp_after:wN \__int_compare:w
4852   \__int_value:w \__int_eval:w #1 \__prg_compare_error:
4853 }
4854 \cs_new:Npn \__int_compare:w #1 \__prg_compare_error:
4855 {
4856   \exp_after:wN \if_false: \__int_value:w
4857   \__int_compare:Nw #1 e { = nd_ } \q_stop
4858 }

```

The goal here is to find an *<operand>* and a *<comparison>*. The *<operand>* is already evaluated, but we cannot yet grab it as an argument. To access the following relation symbol, we remove the number by applying `\__int_to_roman:w`, after making sure that the argument becomes non-positive: its roman numeral representation is then empty. Then probe the first two tokens with `\__int_compare:NNw` to determine the relation symbol, building a control sequence from it (`\token_to_str:N` gives better errors if #1 is not a character). All the extended forms have an extra `=` hence the test for that as a second token. If the relation symbol is unknown, then the control sequence is turned by TeX into `\scan_stop:`, ignored thanks to `\unexpanded`, and `\__prg_compare_error:Nw` raises an error.

```

4859 \cs_new:Npn \__int_compare:Nw #1#2 \q_stop
4860 {
4861   \exp_after:wN \__int_compare:NNw
4862   \__int_to_roman:w - 0 #2 \q_mark
4863   #1#2 \q_stop
4864 }
4865 \cs_new:Npn \__int_compare:NNw #1#2#3 \q_mark

```

```

4866 {
4867   \etex_unexpanded:D
4868   \use:c
4869   {
4870     __int_compare_ \token_to_str:N #1
4871     \if_meaning:w = #2 = \fi:
4872     :NNw
4873   }
4874   \__prg_compare_error:Nw #1
4875 }

```

When the last *operand* is seen, `\__int_compare:NNw` receives `e` and `=nd_` as arguments, hence calling `\__int_compare_end=:NNw` to end the loop: return the result of the last comparison (involving the operand that we just found). When a normal relation is found, the appropriate auxiliary calls `\__int_compare:nnN` where `#1` is `\if_int_compare:w` or `\reverse_if:N \if_int_compare:w`, `#2` is the *operand*, and `#3` is one of `<`, `=`, or `>`. As announced earlier, we leave the *operand* for the previous conditional. If this conditional is true the result of the test is known, so we remove all tokens and return `false`. Otherwise, we apply the conditional `#1` to the *operand* `#2` and the comparison `#3`, and call `\__int_compare:Nw` to look for additional operands, after evaluating the following expression.

```

4876 \cs_new:cpn { __int_compare_end=:NNw } #1#2#3 e #4 \q_stop
4877 {
4878   {#3} \exp_stop_f:
4879   \prg_return_false: \else: \prg_return_true: \fi:
4880 }
4881 \cs_new:Npn \__int_compare:nnN #1#2#3
4882 {
4883   {#2} \exp_stop_f:
4884   \prg_return_false: \exp_after:wN \use_none_delimit_by_q_stop:w
4885   \fi:
4886   #1 #2 #3 \exp_after:wN \__int_compare:Nw \__int_value:w \__int_eval:w
4887 }

```

The actual comparisons are then simple function calls, using the relation as delimiter for a delimited argument and discarding `\__prg_compare_error:Nw` *token* responsible for error detection.

```

4888 \cs_new:cpn { __int_compare=:NNw } #1#2#3 =
4889 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} = }
4890 \cs_new:cpn { __int_compare:<:NNw } #1#2#3 <
4891 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} < }
4892 \cs_new:cpn { __int_compare:>:NNw } #1#2#3 >
4893 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} > }
4894 \cs_new:cpn { __int_compare=:NNw } #1#2#3 ==
4895 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} = }
4896 \cs_new:cpn { __int_compare!=:NNw } #1#2#3 !=
4897 { \__int_compare:nnN { \if_int_compare:w } {#3} = }
4898 \cs_new:cpn { __int_compare<=:NNw } #1#2#3 <=
4899 { \__int_compare:nnN { \if_int_compare:w } {#3} > }
4900 \cs_new:cpn { __int_compare>=:NNw } #1#2#3 >=
4901 { \__int_compare:nnN { \if_int_compare:w } {#3} < }

```

(End definition for `\int_compare:nTF` and others. These functions are documented on page 71.)

`\int_compare_p:nNn` More efficient but less natural in typing.  
`\int_compare:nNnTF`

```

4902 \prg_new_conditional:Npnn \int_compare:nNn #1#2#3 { p , T , F , TF }
4903 {
4904     \if_int_compare:w \__int_eval:w #1 #2 \__int_eval:w #3 \__int_eval_end:
4905     \prg_return_true:
4906     \else:
4907     \prg_return_false:
4908     \fi:
4909 }

```

(End definition for `\int_compare:nNnTF`. This function is documented on page 71.)

`\int_case:nn` For integer cases, the first task to fully expand the check condition. The over all idea is  
`\int_case:nnTF` then much the same as for `\str_case:nn(TF)` as described in l3basics.

```

\__int_case:nnTF 4910 \cs_new:Npn \int_case:nnTF #1
\__int_case:nw 4911 {
\__int_case_end:nw 4912     \exp:w
4913     \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} }
4914 }
4915 \cs_new:Npn \int_case:nnT #1#2#3
4916 {
4917     \exp:w
4918     \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} } {#2} {#3} { }
4919 }
4920 \cs_new:Npn \int_case:nnF #1#2
4921 {
4922     \exp:w
4923     \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} } {#2} { }
4924 }
4925 \cs_new:Npn \int_case:nn #1#2
4926 {
4927     \exp:w
4928     \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} } {#2} { } { }
4929 }
4930 \cs_new:Npn \__int_case:nnTF #1#2#3#4
4931 { \__int_case:nw {#1} #2 {#1} { } \q_mark {#3} \q_mark {#4} \q_stop }
4932 \cs_new:Npn \__int_case:nw #1#2#3
4933 {
4934     \int_compare:nNnTF {#1} = {#2}
4935     { \__int_case_end:nw {#3} }
4936     { \__int_case:nw {#1} }
4937 }
4938 \cs_new_eq:NN \__int_case_end:nw \__prg_case_end:nw

```

(End definition for `\int_case:nnTF` and others. These functions are documented on page 72.)

`\int_if_odd_p:n` A predicate function.

```

\int_if_odd:nTF 4939 \prg_new_conditional:Npnn \int_if_odd:n #1 { p , T , F , TF}
\int_if_even_p:n 4940 {
\int_if_even:nTF 4941     \if_int_odd:w \__int_eval:w #1 \__int_eval_end:
4942     \prg_return_true:
4943     \else:
4944     \prg_return_false:
4945     \fi:

```

```

4946 }
4947 \prg_new_conditional:Npnn \int_if_even:n #1 { p , T , F , TF}
4948 {
4949   \if_int_odd:w \__int_eval:w #1 \__int_eval_end:
4950   \prg_return_false:
4951   \else:
4952   \prg_return_true:
4953   \fi:
4954 }

```

(End definition for `\int_if_odd:nTF` and `\int_if_even:nTF`. These functions are documented on page 72.)

## 8.6 Integer expression loops

`\int_while_do:nn` These are quite easy given the above functions. The `while` versions test first and then execute the body. The `do_while` does it the other way round.

```

\int_until_do:nn
\int_do_while:nn
\int_do_until:nn
4955 \cs_new:Npn \int_while_do:nn #1#2
4956 {
4957   \int_compare:nT {#1}
4958   {
4959     #2
4960     \int_while_do:nn {#1} {#2}
4961   }
4962 }
4963 \cs_new:Npn \int_until_do:nn #1#2
4964 {
4965   \int_compare:nF {#1}
4966   {
4967     #2
4968     \int_until_do:nn {#1} {#2}
4969   }
4970 }
4971 \cs_new:Npn \int_do_while:nn #1#2
4972 {
4973   #2
4974   \int_compare:nT {#1}
4975   { \int_do_while:nn {#1} {#2} }
4976 }
4977 \cs_new:Npn \int_do_until:nn #1#2
4978 {
4979   #2
4980   \int_compare:nF {#1}
4981   { \int_do_until:nn {#1} {#2} }
4982 }

```

(End definition for `\int_while_do:nn` and others. These functions are documented on page 73.)

`\int_while_do:nNnn` As above but not using the more natural syntax.

```

\int_until_do:nNnn
\int_do_while:nNnn
\int_do_until:nNnn
4983 \cs_new:Npn \int_while_do:nNnn #1#2#3#4
4984 {
4985   \int_compare:nNnT {#1} #2 {#3}
4986   {
4987     #4

```

```

4988     \int_while_do:nNnn {#1} #2 {#3} {#4}
4989   }
4990 }
4991 \cs_new:Npn \int_until_do:nNnn #1#2#3#4
4992 {
4993   \int_compare:nNnF {#1} #2 {#3}
4994   {
4995     #4
4996     \int_until_do:nNnn {#1} #2 {#3} {#4}
4997   }
4998 }
4999 \cs_new:Npn \int_do_while:nNnn #1#2#3#4
5000 {
5001   #4
5002   \int_compare:nNnT {#1} #2 {#3}
5003   { \int_do_while:nNnn {#1} #2 {#3} {#4} }
5004 }
5005 \cs_new:Npn \int_do_until:nNnn #1#2#3#4
5006 {
5007   #4
5008   \int_compare:nNnF {#1} #2 {#3}
5009   { \int_do_until:nNnn {#1} #2 {#3} {#4} }
5010 }

```

(End definition for `\int_while_do:nNnn` and others. These functions are documented on page 73.)

## 8.7 Integer step functions

`\int_step_function:nnnN`  
 `\__int_step:wwwN`  
 `\__int_step:NnnnN`

Before all else, evaluate the initial value, step, and final value. Repeating a function by steps first needs a check on the direction of the steps. After that, do the function for the start value then step and loop around. It would be more symmetrical to test for a step size of zero before checking the sign, but we optimize for the most frequent case (positive step).

```

5011 \cs_new:Npn \int_step_function:nnnN #1#2#3
5012 {
5013   \exp_after:wN \__int_step:wwwN
5014   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
5015   \__int_value:w \__int_eval:w #2 \exp_after:wN ;
5016   \__int_value:w \__int_eval:w #3 ;
5017 }
5018 \cs_new:Npn \__int_step:wwwN #1; #2; #3; #4
5019 {
5020   \int_compare:nNnTF {#2} > \c_zero
5021   { \__int_step:NnnnN > }
5022   {
5023     \int_compare:nNnTF {#2} = \c_zero
5024     {
5025       \__msg_kernel_expandable_error:nnn { kernel } { zero-step } {#4}
5026       \use_none:nnnn
5027     }
5028     { \__int_step:NnnnN < }
5029   }
5030   {#1} {#2} {#3} #4
5031 }

```

```

5032 \cs_new:Npn \__int_step:NnnnN #1#2#3#4#5
5033 {
5034   \int_compare:nNf {#2} #1 {#4}
5035   {
5036     #5 {#2}
5037     \exp_args:NNf \__int_step:NnnnN
5038     #1 { \int_eval:n { #2 + #3 } } {#3} {#4} #5
5039   }
5040 }

```

(End definition for `\int_step_function:nnnN`, `\__int_step:wwwN`, and `\__int_step:NnnnN`. These functions are documented on page 74.)

`\int_step_inline:nnnn`  
`\int_step_variable:nnnNn`  
`\__int_step:NNnnnn`

The approach here is to build a function, with a global integer required to make the nesting safe (as seen in other in line functions), and map that function using `\int_step_function:nnnN`. We put a `\__prg_break_point:Nn` so that `map_break` functions from other modules correctly decrement `\g__prg_map_int` before looking for their own break point. The first argument is `\scan_stop:`, so that no breaking function recognizes this break point as its own.

```

5041 \cs_new_protected:Npn \int_step_inline:nnnn
5042 {
5043   \int_gincr:N \g__prg_map_int
5044   \exp_args:NNc \__int_step:NNnnnn
5045   \cs_gset_protected:Npn
5046   { __prg_map_ \int_use:N \g__prg_map_int :w }
5047 }
5048 \cs_new_protected:Npn \int_step_variable:nnnNn #1#2#3#4#5
5049 {
5050   \int_gincr:N \g__prg_map_int
5051   \exp_args:NNc \__int_step:NNnnnn
5052   \cs_gset_protected:Npx
5053   { __prg_map_ \int_use:N \g__prg_map_int :w }
5054   {#1}{#2}{#3}
5055   {
5056     \tl_set:Nn \exp_not:N #4 {##1}
5057     \exp_not:n {#5}
5058   }
5059 }
5060 \cs_new_protected:Npn \__int_step:NNnnnn #1#2#3#4#5#6
5061 {
5062   #1 #2 ##1 {#6}
5063   \int_step_function:nnnN {#3} {#4} {#5} #2
5064   \__prg_break_point:Nn \scan_stop: { \int_gdecr:N \g__prg_map_int }
5065 }

```

(End definition for `\int_step_inline:nnnn`, `\int_step_variable:nnnNn`, and `\__int_step:NNnnnn`. These functions are documented on page 74.)

## 8.8 Formatting integers

`\int_to_arabic:n` Nothing exciting here.

```

5066 \cs_new_eq:NN \int_to_arabic:n \int_eval:n

```

(End definition for `\int_to_arabic:n`. This function is documented on page 74.)

`\int_to_symbols:nnn` For conversion of integers to arbitrary symbols the method is in general as follows. The input number (#1) is compared to the total number of symbols available at each place (#2). If the input is larger than the total number of symbols available then the modulus is needed, with one added so that the positions don't have to number from zero. Using an `f`-type expansion, this is done so that the system is recursive. The actual conversion function therefore gets a 'nice' number at each stage. Of course, if the initial input was small enough then there is no problem and everything is easy.

```

5067 \cs_new:Npn \int_to_symbols:nnn #1#2#3
5068 {
5069   \int_compare:nNnTF {#1} > {#2}
5070   {
5071     \exp_args:NNo \exp_args:No \__int_to_symbols:nnnn
5072     {
5073       \int_case:nn
5074       { 1 + \int_mod:nn { #1 - 1 } {#2} }
5075       {#3}
5076     }
5077     {#1} {#2} {#3}
5078   }
5079   { \int_case:nn {#1} {#3} }
5080 }
5081 \cs_new:Npn \__int_to_symbols:nnnn #1#2#3#4
5082 {
5083   \exp_args:Nf \int_to_symbols:nnn
5084   { \int_div_truncate:nn { #2 - 1 } {#3} } {#3} {#4}
5085   #1
5086 }

```

(End definition for `\int_to_symbols:nnn` and `\__int_to_symbols:nnnn`. These functions are documented on page 75.)

`\int_to_alph:n` These both use the above function with input functions that make sense for the alphabet in English.

`\int_to_Alph:n`

```

5087 \cs_new:Npn \int_to_alph:n #1
5088 {
5089   \int_to_symbols:nnn {#1} { 26 }
5090   {
5091     { 1 } { a }
5092     { 2 } { b }
5093     { 3 } { c }
5094     { 4 } { d }
5095     { 5 } { e }
5096     { 6 } { f }
5097     { 7 } { g }
5098     { 8 } { h }
5099     { 9 } { i }
5100     { 10 } { j }
5101     { 11 } { k }
5102     { 12 } { l }
5103     { 13 } { m }
5104     { 14 } { n }
5105     { 15 } { o }
5106     { 16 } { p }
5107     { 17 } { q }

```

```

5108         { 18 } { r }
5109         { 19 } { s }
5110         { 20 } { t }
5111         { 21 } { u }
5112         { 22 } { v }
5113         { 23 } { w }
5114         { 24 } { x }
5115         { 25 } { y }
5116         { 26 } { z }
5117     }
5118 }
5119 \cs_new:Npn \int_to_Alph:n #1
5120 {
5121     \int_to_symbols:nnn {#1} { 26 }
5122     {
5123         { 1 } { A }
5124         { 2 } { B }
5125         { 3 } { C }
5126         { 4 } { D }
5127         { 5 } { E }
5128         { 6 } { F }
5129         { 7 } { G }
5130         { 8 } { H }
5131         { 9 } { I }
5132         { 10 } { J }
5133         { 11 } { K }
5134         { 12 } { L }
5135         { 13 } { M }
5136         { 14 } { N }
5137         { 15 } { O }
5138         { 16 } { P }
5139         { 17 } { Q }
5140         { 18 } { R }
5141         { 19 } { S }
5142         { 20 } { T }
5143         { 21 } { U }
5144         { 22 } { V }
5145         { 23 } { W }
5146         { 24 } { X }
5147         { 25 } { Y }
5148         { 26 } { Z }
5149     }
5150 }

```

(End definition for `\int_to_alph:n` and `\int_to_Alph:n`. These functions are documented on page 75.)

`\int_to_base:nn` Converting from base ten (#1) to a second base (#2) starts with computing #1: if it is  
`\int_to_Base:nn` a complicated calculation, we shouldn't perform it twice. Then check the sign, store it,  
`\__int_to_base:nn` either - or `\c_empty_tl`, and feed the absolute value to the next auxiliary function.  
`\__int_to_Base:nn`  
`\__int_to_base:nnN`  
`\__int_to_Base:nnN`  
`\__int_to_base:nnnN`  
`\__int_to_Base:nnnN`  
`\__int_to_letter:n`  
`\__int_to_Letter:n`

```

5151 \cs_new:Npn \int_to_base:nn #1
5152 { \exp_args:Nf \__int_to_base:nn { \int_eval:n {#1} } }
5153 \cs_new:Npn \int_to_Base:nn #1
5154 { \exp_args:Nf \__int_to_Base:nn { \int_eval:n {#1} } }
5155 \cs_new:Npn \__int_to_base:nn #1#2

```



```

5156 {
5157     \int_compare:nNnTF {#1} < 0
5158     { \exp_args:No \__int_to_base:nnN { \use_none:n #1 } {#2} - }
5159     { \__int_to_base:nnN {#1} {#2} \c_empty_tl }
5160 }
5161 \cs_new:Npn \__int_to_Base:nn #1#2
5162 {
5163     \int_compare:nNnTF {#1} < 0
5164     { \exp_args:No \__int_to_Base:nnN { \use_none:n #1 } {#2} - }
5165     { \__int_to_Base:nnN {#1} {#2} \c_empty_tl }
5166 }

```

Here, the idea is to provide a recursive system to deal with the input. The output is built up after the end of the function. At each pass, the value in #1 is checked to see if it is less than the new base (#2). If it is, then it is converted directly, putting the sign back in front. On the other hand, if the value to convert is greater than or equal to the new base then the modulus and remainder values are found. The modulus is converted to a symbol and put on the right, and the remainder is carried forward to the next round.

```

5167 \cs_new:Npn \__int_to_base:nnN #1#2#3
5168 {
5169     \int_compare:nNnTF {#1} < {#2}
5170     { \exp_last_unbraced:Nf #3 { \__int_to_letter:n {#1} } }
5171     {
5172         \exp_args:Nf \__int_to_base:nnnN
5173         { \__int_to_letter:n { \int_mod:nn {#1} {#2} } }
5174         {#1}
5175         {#2}
5176         #3
5177     }
5178 }
5179 \cs_new:Npn \__int_to_base:nnnN #1#2#3#4
5180 {
5181     \exp_args:Nf \__int_to_base:nnN
5182     { \int_div_truncate:nn {#2} {#3} }
5183     {#3}
5184     #4
5185     #1
5186 }
5187 \cs_new:Npn \__int_to_Base:nnN #1#2#3
5188 {
5189     \int_compare:nNnTF {#1} < {#2}
5190     { \exp_last_unbraced:Nf #3 { \__int_to_Letter:n {#1} } }
5191     {
5192         \exp_args:Nf \__int_to_Base:nnnN
5193         { \__int_to_Letter:n { \int_mod:nn {#1} {#2} } }
5194         {#1}
5195         {#2}
5196         #3
5197     }
5198 }
5199 \cs_new:Npn \__int_to_Base:nnnN #1#2#3#4
5200 {
5201     \exp_args:Nf \__int_to_Base:nnN
5202     { \int_div_truncate:nn {#2} {#3} }

```

```

5203     {#3}
5204     #4
5205     #1
5206 }

```

Convert to a letter only if necessary, otherwise simply return the value unchanged. It would be cleaner to use `\int_case:nn`, but in our case, the cases are contiguous, so it is forty times faster to use the `\if_case:w` primitive. The first `\exp_after:wN` expands the conditional, jumping to the correct case, the second one expands after the resulting character to close the conditional. Since `#1` might be an expression, and not directly a single digit, we need to evaluate it properly, and expand the trailing `\fi:`.

```

5207 \cs_new:Npn \__int_to_letter:n #1
5208 {
5209     \exp_after:wN \exp_after:wN
5210     \if_case:w \__int_eval:w #1 - 10 \__int_eval_end:
5211     a
5212     \or: b
5213     \or: c
5214     \or: d
5215     \or: e
5216     \or: f
5217     \or: g
5218     \or: h
5219     \or: i
5220     \or: j
5221     \or: k
5222     \or: l
5223     \or: m
5224     \or: n
5225     \or: o
5226     \or: p
5227     \or: q
5228     \or: r
5229     \or: s
5230     \or: t
5231     \or: u
5232     \or: v
5233     \or: w
5234     \or: x
5235     \or: y
5236     \or: z
5237     \else: \__int_value:w \__int_eval:w #1 \exp_after:wN \__int_eval_end:
5238     \fi:
5239 }
5240 \cs_new:Npn \__int_to_Letter:n #1
5241 {
5242     \exp_after:wN \exp_after:wN
5243     \if_case:w \__int_eval:w #1 - 10 \__int_eval_end:
5244     A
5245     \or: B
5246     \or: C
5247     \or: D
5248     \or: E
5249     \or: F

```

```

5250     \or: G
5251     \or: H
5252     \or: I
5253     \or: J
5254     \or: K
5255     \or: L
5256     \or: M
5257     \or: N
5258     \or: O
5259     \or: P
5260     \or: Q
5261     \or: R
5262     \or: S
5263     \or: T
5264     \or: U
5265     \or: V
5266     \or: W
5267     \or: X
5268     \or: Y
5269     \or: Z
5270     \else: \__int_value:w \__int_eval:w #1 \exp_after:wN \__int_eval_end:
5271     \fi:
5272 }

```

(End definition for `\int_to_base:nn` and others. These functions are documented on page 76.)

`\int_to_bin:n` Wrappers around the generic function.

```

\int_to_hex:n 5273 \cs_new:Npn \int_to_bin:n #1
\int_to_Hex:n 5274 { \int_to_base:nn {#1} { 2 } }
\int_to_oct:n 5275 \cs_new:Npn \int_to_hex:n #1
5276 { \int_to_base:nn {#1} { 16 } }
5277 \cs_new:Npn \int_to_Hex:n #1
5278 { \int_to_Base:nn {#1} { 16 } }
5279 \cs_new:Npn \int_to_oct:n #1
5280 { \int_to_base:nn {#1} { 8 } }

```

(End definition for `\int_to_bin:n` and others. These functions are documented on page 75.)

`\int_to_roman:n` The `\__int_to_roman:w` primitive creates tokens of category code 12 (other). Usually, what is actually wanted is letters. The approach here is to convert the output of the primitive into letters using appropriate control sequence names. That keeps everything expandable. The loop is terminated by the conversion of the Q.

```

\__int_to_roman:N 5281 \cs_new:Npn \int_to_roman:n #1
\__int_to_roman:N 5282 {
\__int_to_roman_i:w 5283   \exp_after:wN \__int_to_roman:N
\__int_to_roman_v:w 5284   \__int_to_roman:w \int_eval:n {#1} Q
\__int_to_roman_x:w 5285   }
\__int_to_roman_l:w 5286 \cs_new:Npn \__int_to_roman:N #1
\__int_to_roman_c:w 5287 {
\__int_to_roman_d:w 5288   \use:c { __int_to_roman_ #1 :w }
\__int_to_roman_m:w 5289   \__int_to_roman:N
\__int_to_roman_Q:w 5290   }
\__int_to_Roman_i:w 5291 \cs_new:Npn \int_to_Roman:n #1
\__int_to_Roman_v:w 5292 {
\__int_to_Roman_x:w
\__int_to_Roman_l:w
\__int_to_Roman_c:w
\__int_to_Roman_d:w
\__int_to_Roman_m:w
\__int_to_Roman_Q:w

```

```

5293 \exp_after:wN \__int_to_Roman_aux:N
5294 \__int_to_roman:w \int_eval:n {#1} Q
5295 }
5296 \cs_new:Npn \__int_to_Roman_aux:N #1
5297 {
5298 \use:c { \__int_to_Roman_ #1 :w }
5299 \__int_to_Roman_aux:N
5300 }
5301 \cs_new:Npn \__int_to_roman_i:w { i }
5302 \cs_new:Npn \__int_to_roman_v:w { v }
5303 \cs_new:Npn \__int_to_roman_x:w { x }
5304 \cs_new:Npn \__int_to_roman_l:w { l }
5305 \cs_new:Npn \__int_to_roman_c:w { c }
5306 \cs_new:Npn \__int_to_roman_d:w { d }
5307 \cs_new:Npn \__int_to_roman_m:w { m }
5308 \cs_new:Npn \__int_to_roman_Q:w #1 { }
5309 \cs_new:Npn \__int_to_Roman_i:w { I }
5310 \cs_new:Npn \__int_to_Roman_v:w { V }
5311 \cs_new:Npn \__int_to_Roman_x:w { X }
5312 \cs_new:Npn \__int_to_Roman_l:w { L }
5313 \cs_new:Npn \__int_to_Roman_c:w { C }
5314 \cs_new:Npn \__int_to_Roman_d:w { D }
5315 \cs_new:Npn \__int_to_Roman_m:w { M }
5316 \cs_new:Npn \__int_to_Roman_Q:w #1 { }

```

(End definition for `\int_to_roman:n` and others. These functions are documented on page 76.)

## 8.9 Converting from other formats to integers

```

\__int_pass_signs:wn
\__int_pass_signs_end:wn

```

Called as `\__int_pass_signs:wn <signs and digits> \q_stop {<code>}`, this function leaves in the input stream any sign it finds, then inserts the `<code>` before the first non-sign token (and removes `\q_stop`). More precisely, it deletes any + and passes any - to the input stream, hence should be called in an integer expression.

```

5317 \cs_new:Npn \__int_pass_signs:wn #1
5318 {
5319 \if:w + \if:w - \exp_not:N #1 + \fi: \exp_not:N #1
5320 \exp_after:wN \__int_pass_signs:wn
5321 \else:
5322 \exp_after:wN \__int_pass_signs_end:wn
5323 \exp_after:wN #1
5324 \fi:
5325 }
5326 \cs_new:Npn \__int_pass_signs_end:wn #1 \q_stop #2 { #2 #1 }

```

(End definition for `\__int_pass_signs:wn` and `\__int_pass_signs_end:wn`.)

```

\int_from_alph:n
\__int_from_alph:nN
\__int_from_alph:N

```

First take care of signs then loop through the input using the `recursion` quarks. The `\__int_from_alph:nN` auxiliary collects in its first argument the value obtained so far, and the auxiliary `\__int_from_alph:N` converts one letter to an expression which evaluates to the correct number.

```

5327 \cs_new:Npn \int_from_alph:n #1
5328 {
5329 \int_eval:n
5330 {

```

```

5331         \exp_after:wN \__int_pass_signs:wn \tl_to_str:n {#1}
5332         \q_stop { \__int_from_alph:nN { 0 } }
5333         \q_recursion_tail \q_recursion_stop
5334     }
5335 }
5336 \cs_new:Npn \__int_from_alph:nN #1#2
5337 {
5338     \quark_if_recursion_tail_stop_do:Nn #2 {#1}
5339     \exp_args:Nf \__int_from_alph:nN
5340     { \int_eval:n { #1 * 26 + \__int_from_alph:N #2 } }
5341 }
5342 \cs_new:Npn \__int_from_alph:N #1
5343 { '#1 - \int_compare:nNnTF { '#1 } < { 91 } { 64 } { 96 } }

```

(End definition for `\int_from_alph:n`, `\__int_from_alph:nN`, and `\__int_from_alph:N`. These functions are documented on page 76.)

**`\int_from_base:nn`** Leave the signs into the integer expression, then loop through characters, collecting the value found so far in the first argument of `\__int_from_base:nnN`. To convert a single character, `\__int_from_base:N` checks first for digits, then distinguishes lower from upper case letters, turning them into the appropriate number. Note that this auxiliary does not use `\int_eval:n`, hence is not safe for general use.

```

5344 \cs_new:Npn \int_from_base:nn #1#2
5345 {
5346     \int_eval:n
5347     {
5348         \exp_after:wN \__int_pass_signs:wn \tl_to_str:n {#1}
5349         \q_stop { \__int_from_base:nnN { 0 } {#2} }
5350         \q_recursion_tail \q_recursion_stop
5351     }
5352 }
5353 \cs_new:Npn \__int_from_base:nnN #1#2#3
5354 {
5355     \quark_if_recursion_tail_stop_do:Nn #3 {#1}
5356     \exp_args:Nf \__int_from_base:nnN
5357     { \int_eval:n { #1 * #2 + \__int_from_base:N #3 } }
5358     {#2}
5359 }
5360 \cs_new:Npn \__int_from_base:N #1
5361 {
5362     \int_compare:nNnTF { '#1 } < { 58 }
5363     {#1}
5364     { '#1 - \int_compare:nNnTF { '#1 } < { 91 } { 55 } { 87 } }
5365 }

```

(End definition for `\int_from_base:nn`, `\__int_from_base:nnN`, and `\__int_from_base:N`. These functions are documented on page 77.)

**`\int_from_bin:n`** Wrappers around the generic function.

```

\int_from_hex:n
\int_from_oct:n
5366 \cs_new:Npn \int_from_bin:n #1
5367 { \int_from_base:nn {#1} { 2 } }
5368 \cs_new:Npn \int_from_hex:n #1
5369 { \int_from_base:nn {#1} { 16 } }
5370 \cs_new:Npn \int_from_oct:n #1
5371 { \int_from_base:nn {#1} { 8 } }

```

(End definition for `\int_from_bin:n`, `\int_from_hex:n`, and `\int_from_oct:n`. These functions are documented on page 76.)

<code>\c__int_from_roman_i_int</code>	Constants used to convert from Roman numerals to integers.
<code>\c__int_from_roman_v_int</code>	5372 <code>\int_const:cn { c__int_from_roman_i_int } { 1 }</code>
<code>\c__int_from_roman_x_int</code>	5373 <code>\int_const:cn { c__int_from_roman_v_int } { 5 }</code>
<code>\c__int_from_roman_l_int</code>	5374 <code>\int_const:cn { c__int_from_roman_x_int } { 10 }</code>
<code>\c__int_from_roman_c_int</code>	5375 <code>\int_const:cn { c__int_from_roman_l_int } { 50 }</code>
<code>\c__int_from_roman_d_int</code>	5376 <code>\int_const:cn { c__int_from_roman_c_int } { 100 }</code>
<code>\c__int_from_roman_m_int</code>	5377 <code>\int_const:cn { c__int_from_roman_d_int } { 500 }</code>
<code>\c__int_from_roman_I_int</code>	5378 <code>\int_const:cn { c__int_from_roman_m_int } { 1000 }</code>
<code>\c__int_from_roman_V_int</code>	5379 <code>\int_const:cn { c__int_from_roman_I_int } { 1 }</code>
<code>\c__int_from_roman_X_int</code>	5380 <code>\int_const:cn { c__int_from_roman_V_int } { 5 }</code>
<code>\c__int_from_roman_L_int</code>	5381 <code>\int_const:cn { c__int_from_roman_X_int } { 10 }</code>
<code>\c__int_from_roman_C_int</code>	5382 <code>\int_const:cn { c__int_from_roman_L_int } { 50 }</code>
<code>\c__int_from_roman_D_int</code>	5383 <code>\int_const:cn { c__int_from_roman_C_int } { 100 }</code>
<code>\c__int_from_roman_M_int</code>	5384 <code>\int_const:cn { c__int_from_roman_D_int } { 500 }</code>
	5385 <code>\int_const:cn { c__int_from_roman_M_int } { 1000 }</code>

(End definition for `\c__int_from_roman_i_int` and others.)

<code>\int_from_roman:n</code>	The method here is to iterate through the input, finding the appropriate value for each
<code>\__int_from_roman:NN</code>	letter and building up a sum. This is then evaluated by $\text{\TeX}$ . If any unknown letter is
<code>\__int_from_roman_error:w</code>	found, skip to the closing parenthesis and insert <code>*0-1</code> afterwards, to replace the value by
	<code>-1</code> .

```

5386 \cs_new:Npn \int_from_roman:n #1
5387 {
5388   \int_eval:n
5389   {
5390     (
5391       0
5392       \exp_after:wN \__int_from_roman:NN \tl_to_str:n {#1}
5393       \q_recursion_tail \q_recursion_tail \q_recursion_stop
5394     )
5395   }
5396 }
5397 \cs_new:Npn \__int_from_roman:NN #1#2
5398 {
5399   \quark_if_recursion_tail_stop:N #1
5400   \int_if_exist:cF { c__int_from_roman_ #1 _int }
5401   { \__int_from_roman_error:w }
5402   \quark_if_recursion_tail_stop_do:Nn #2
5403   { + \use:c { c__int_from_roman_ #1 _int } }
5404   \int_if_exist:cF { c__int_from_roman_ #2 _int }
5405   { \__int_from_roman_error:w }
5406   \int_compare:nNnTF
5407   { \use:c { c__int_from_roman_ #1 _int } }
5408   <
5409   { \use:c { c__int_from_roman_ #2 _int } }
5410   {
5411     + \use:c { c__int_from_roman_ #2 _int }
5412     - \use:c { c__int_from_roman_ #1 _int }
5413     \__int_from_roman:NN
5414   }

```

```

5415     {
5416       + \use:c { c__int_from_roman_ #1 _int }
5417       \__int_from_roman:NN #2
5418     }
5419   }
5420 \cs_new:Npn \__int_from_roman_error:w #1 \q_recursion_stop #2
5421   { #2 * 0 - 1 }

```

(End definition for `\int_from_roman:n`, `\__int_from_roman:NN`, and `\__int_from_roman_error:w`. These functions are documented on page 77.)

## 8.10 Viewing integer

`\int_show:N` Diagnostics.  
`\int_show:c` 5422 `\cs_new_eq:NN \int_show:N \__kernel_register_show:N`  
`\__int_show:nN` 5423 `\cs_generate_variant:Nn \int_show:N { c }`

(End definition for `\int_show:N` and `\__int_show:nN`. These functions are documented on page 77.)

`\int_show:n` We don't use the TeX primitive `\showthe` to show integer expressions: this gives a more unified output.

```

5424 \cs_new_protected:Npn \int_show:n
5425   { \__msg_show_wrap:Nn \int_eval:n }

```

(End definition for `\int_show:n`. This function is documented on page 77.)

`\int_log:N` Diagnostics.  
`\int_log:c` 5426 `\cs_new_eq:NN \int_log:N \__kernel_register_log:N`  
5427 `\cs_generate_variant:Nn \int_log:N { c }`

(End definition for `\int_log:N`. This function is documented on page 77.)

`\int_log:n` Redirect output of `\int_show:n` to the log.

```

5428 \cs_new_protected:Npn \int_log:n
5429   { \__msg_log_next: \int_show:n }

```

(End definition for `\int_log:n`. This function is documented on page 77.)

## 8.11 Constant integers

`\c_zero` Again, in `l3basics`

(End definition for `\c_zero`. This variable is documented on page 78.)

`\c_one` Low-number values not previously defined.  
`\c_two` 5430 `\int_const:Nn \c_one { 1 }`  
`\c_three` 5431 `\int_const:Nn \c_two { 2 }`  
`\c_four` 5432 `\int_const:Nn \c_three { 3 }`  
`\c_five` 5433 `\int_const:Nn \c_four { 4 }`  
`\c_six` 5434 `\int_const:Nn \c_five { 5 }`  
`\c_seven` 5435 `\int_const:Nn \c_six { 6 }`  
`\c_eight` 5436 `\int_const:Nn \c_seven { 7 }`  
`\c_nine` 5437 `\int_const:Nn \c_eight { 8 }`  
`\c_ten` 5438 `\int_const:Nn \c_nine { 9 }`  
`\c_eleven` 5439 `\int_const:Nn \c_ten { 10 }`  
`\c_twelve`  
`\c_thirteen`  
`\c_fourteen`  
`\c_fifteen`  
`\c_sixteen`

```

5440 \int_const:Nn \c_eleven { 11 }
5441 \int_const:Nn \c_twelve { 12 }
5442 \int_const:Nn \c_thirteen { 13 }
5443 \int_const:Nn \c_fourteen { 14 }
5444 \int_const:Nn \c_fifteen { 15 }
5445 \int_const:Nn \c_sixteen { 16 }

```

(End definition for `\c_one` and others. These variables are documented on page 78.)

`\c_thirty_two` One middling value.

```

5446 \int_const:Nn \c_thirty_two { 32 }

```

(End definition for `\c_thirty_two`. This variable is documented on page 78.)

`\c_two_hundred_fifty_five` Two classic mid-range integer constants.

```

5447 \int_const:Nn \c_two_hundred_fifty_five { 255 }
5448 \int_const:Nn \c_two_hundred_fifty_six { 256 }

```

(End definition for `\c_two_hundred_fifty_five` and `\c_two_hundred_fifty_six`. These variables are documented on page 78.)

`\c_one_hundred` Simple runs of powers of ten.

```

5449 \int_const:Nn \c_one_hundred { 100 }
5450 \int_const:Nn \c_one_thousand { 1000 }
5451 \int_const:Nn \c_ten_thousand { 10000 }

```

(End definition for `\c_one_hundred`, `\c_one_thousand`, and `\c_ten_thousand`. These variables are documented on page 78.)

`\c_max_int` The largest number allowed is  $2^{31} - 1$

```

5452 \int_const:Nn \c_max_int { 2 147 483 647 }

```

(End definition for `\c_max_int`. This variable is documented on page 78.)

`\c_max_char_int` The largest character code is 1114111 (hexadecimal 10FFFF) in XeTeX and LuaTeX and 255 in other engines. In many places pTeX and upTeX support larger character codes but for instance the values of `\lccode` are restricted to  $[0, 255]$ .

```

5453 \int_const:Nn \c_max_char_int
5454 {
5455   \if_int_odd:w 0
5456     \cs_if_exist:NT \luatex luatexversion:D { 1 }
5457     \cs_if_exist:NT \xetex XeTeXversion:D { 1 } ~
5458     "10FFFF
5459   \else:
5460     "FF
5461   \fi:
5462 }

```

(End definition for `\c_max_char_int`. This variable is documented on page 78.)



## 8.12 Scratch integers

`\l_tmpa_int` We provide two local and two global scratch counters, maybe we need more or less.

```
\l_tmpb_int 5463 \int_new:N \l_tmpa_int
\l_tmpa_int 5464 \int_new:N \l_tmpb_int
\g_tmpa_int 5465 \int_new:N \g_tmpa_int
\g_tmpb_int 5466 \int_new:N \g_tmpb_int
```

(End definition for `\l_tmpa_int` and others. These variables are documented on page 78.)

## 8.13 Deprecated

`\c_minus_one` The actual allocation mechanism is in `l3alloc`; it requires `\c_one` to be defined. In package mode, reuse `\m@ne`.

```
5467 <*package>
5468 \cs_new_eq:NN \c_minus_one \m@ne
5469 </package>
5470 <*initex>
5471 \int_const:Nn \c_minus_one { -1 }
5472 </initex>
```

(End definition for `\c_minus_one`.)

```
5473 </initex | package>
```

## 9 l3intarray implementation

```
5474 <*initex | package>
5475 <@@=intarray>
```

### 9.1 Allocating arrays

`\g__intarray_font_int` Used to assign one font per array.

```
5476 \int_new:N \g__intarray_font_int
```

(End definition for `\g__intarray_font_int`.)

`\__intarray_new:Nn` Declare `#1` to be a font (arbitrarily `cmr10` at a never-used size). Store the array's size as the `\hyphenchar` of that font and make sure enough `\fontdimen` are allocated, by setting the last one. Then clear any `\fontdimen` that `cmr10` starts with. It seems LuaTeX's `cmr10` has an extra `\fontdimen` parameter number 8 compared to other engines (for a math font we would replace 8 by 22 or some such).

```
5477 \cs_new_protected:Npn \__intarray_new:Nn #1#2
5478 {
5479   \__chk_if_free_cs:N #1
5480   \int_gincr:N \g__intarray_font_int
5481   \tex_global:D \tex_font:D #1 = cmr10-at~ \g__intarray_font_int sp \scan_stop:
5482   \tex_hyphenchar:D #1 = \int_eval:n {#2} \scan_stop:
5483   \int_compare:nNnT { \tex_hyphenchar:D #1 } > 0
5484     { \tex_fontdimen:D \tex_hyphenchar:D #1 #1 = 0 sp \scan_stop: }
5485   \int_step_inline:nnnn { 1 } { 1 } { 8 }
5486     { \tex_fontdimen:D ##1 #1 = 0 sp \scan_stop: }
5487 }
```

(End definition for `\_intarray_new:Nn`.)

`\_intarray_count:N` Size of an array.

```
5488 \cs_new:Npn \_intarray_count:N #1 { \tex_the:D \tex_hyphenchar:D #1 }
```

(End definition for `\_intarray_count:N`.)

## 9.2 Array items

`\_intarray_gset:Nnn` Set the appropriate `\fontdimen`. The slow version checks the position and value are within bounds.

```
\_intarray_gset_fast:Nnn
\_intarray_gset_aux:Nnn
5489 \cs_new_protected:Npn \_intarray_gset_fast:Nnn #1#2#3
5490 { \tex_fontdimen:D \int_eval:n {#2} #1 = \int_eval:n {#3} sp \scan_stop: }
5491 \cs_new_protected:Npn \_intarray_gset:Nnn #1#2#3
5492 {
5493   \exp_args:Nff \_intarray_gset_aux:Nnn #1
5494   { \int_eval:n {#2} } { \int_eval:n {#3} }
5495 }
5496 \cs_new_protected:Npn \_intarray_gset_aux:Nnn #1#2#3
5497 {
5498   \int_compare:nTF { 1 <= #2 <= \_intarray_count:N #1 }
5499   {
5500     \int_compare:nTF { - \c_max_dim <= \int_abs:n {#3} <= \c_max_dim }
5501     { \_intarray_gset_fast:Nnn #1 {#2} {#3} }
5502     {
5503       \_msg_kernel_error:nnxxxx { kernel } { overflow }
5504       { \token_to_str:N #1 } {#2} {#3}
5505       { \int_compare:nNnT {#3} < 0 { - } \_int_value:w \c_max_dim }
5506       \_intarray_gset_fast:Nnn #1 {#2}
5507       { \int_compare:nNnT {#3} < 0 { - } \c_max_dim }
5508     }
5509   }
5510   {
5511     \_msg_kernel_error:nnxxx { kernel } { out-of-bounds }
5512     { \token_to_str:N #1 } {#2} { \_intarray_count:N #1 }
5513   }
5514 }
```

(End definition for `\_intarray_gset:Nnn`, `\_intarray_gset_fast:Nnn`, and `\_intarray_gset_aux:Nnn`.)

`\_intarray_item:Nn` Get the appropriate `\fontdimen` and perform bound checks if requested.

```
\_intarray_item_fast:Nn
\_intarray_item_aux:Nn
5515 \cs_new:Npn \_intarray_item_fast:Nn #1#2
5516 { \_int_value:w \tex_fontdimen:D \int_eval:n {#2} #1 }
5517 \cs_new:Npn \_intarray_item:Nn #1#2
5518 { \exp_args:Nf \_intarray_item_aux:Nn #1 { \int_eval:n {#2} } }
5519 \cs_new:Npn \_intarray_item_aux:Nn #1#2
5520 {
5521   \int_compare:nTF { 1 <= #2 <= \_intarray_count:N #1 }
5522   { \_intarray_item_fast:Nn #1 {#2} }
5523   {
5524     \_msg_kernel_expandable_error:nnnnn { kernel } { out-of-bounds }
5525     { \token_to_str:N #1 } {#2} { \_intarray_count:N #1 }
5526     0
5527   }
5528 }
```

```

5527     }
5528 }

(End definition for \__intarray_item:Nn, \__intarray_item_fast:Nn, and \__intarray_item_aux:Nn.)

5529 </initex | package>

```

## 10 l3flag implementation

```

5530 (*initex | package)
5531 <@@=flag>

```

The following test files are used for this code: *m3flag001*.

### 10.1 Non-expandable flag commands

The height  $h$  of a flag (initially zero) is stored by setting control sequences of the form `\flag <name> <integer>` to `\relax` for  $0 \leq \langle integer \rangle < h$ . When a flag is raised, a “trap” function `\flag <name>` is called. The existence of this function is also used to test for the existence of a flag.

**\flag\_new:n** For each flag, we define a “trap” function, which by default simply increases the flag by 1 by letting the appropriate control sequence to `\relax`. This can be done expandably!

```

5532 \cs_new_protected:Npn \flag_new:n #1
5533 {
5534   \cs_new:cpn { flag~#1 } ##1 ;
5535   { \exp_after:wN \use_none:n \cs:w flag~#1~##1 \cs_end: }
5536 }

```

(End definition for `\flag_new:n`. This function is documented on page 82.)

**\flag\_clear:n** Undefine control sequences, starting from the 0 flag, upwards, until reaching an undefined control sequence. We don’t use `\cs_undefine:c` because that would act globally. When the option `check-declarations` is used, check for the function defined by `\flag_new:n`.

```

\__flag_clear:wn
5537 \__debug_patch:nnNw
5538 { \exp_args:Nc \__chk_if_exist_var:N { flag~#1 } } { }
5539 \cs_new_protected:Npn \flag_clear:n #1 { \__flag_clear:wn 0 ; {#1} }
5540 \cs_new_protected:Npn \__flag_clear:wn #1 ; #2
5541 {
5542   \if_cs_exist:w flag~#2~#1 \cs_end:
5543   \cs_set_eq:cN { flag~#2~#1 } \tex_undefined:D
5544   \exp_after:wN \__flag_clear:wn
5545   \__int_value:w \__int_eval:w 1 + #1
5546   \else:
5547     \use_i:nnn
5548   \fi:
5549   ; {#2}
5550 }

```

(End definition for `\flag_clear:n` and `\__flag_clear:wn`. These functions are documented on page 82.)

**\flag\_clear\_new:n** As for other datatypes, clear the *<flag>* or create a new one, as appropriate.

```

5551 \cs_new_protected:Npn \flag_clear_new:n #1
5552 { \flag_if_exist:nTF {#1} { \flag_clear:n } { \flag_new:n } {#1} }

```

(End definition for `\flag_clear_new:n`. This function is documented on page 82.)

`\flag_show:n` Show the height (terminal or log file) using appropriate `l3msg` auxiliaries.

```
\flag_log:n
5553 \cs_new_protected:Npn \flag_show:n #1
5554 {
5555   \exp_args:Nc \__msg_show_variable:NNNnn { flag~#1 } \cs_if_exist:NTF ? { }
5556   { > ~ flag ~ #1 ~ height = \flag_height:n {#1} }
5557 }
5558 \cs_new_protected:Npn \flag_log:n
5559 { \__msg_log_next: \flag_show:n }
```

(End definition for `\flag_show:n` and `\flag_log:n`. These functions are documented on page 82.)

## 10.2 Expandable flag commands

`\__flag_chk_exist:n` Analogue of `\__chk_if_exist_var:N` for flags, and with an expandable error. We need to add checks by hand because flags are not implemented in terms of other variables. Not all functions need to be patched since some are defined in terms of others.

```
5560 (*package)
5561 \tex_ifodd:D \l@expl@enable@debug@bool
5562 \cs_new:Npn \__flag_chk_exist:n #1
5563 {
5564   \flag_if_exist:nF {#1}
5565   {
5566     \__msg_kernel_expandable_error:nnn
5567     { kernel } { bad-variable } { flag~#1~ }
5568   }
5569 }
5570 \fi:
5571 </package>
```

(End definition for `\__flag_chk_exist:n`.)

`\flag_if_exist_p:n` A flag exist if the corresponding trap `\flag <flag name>:n` is defined.

```
\flag_if_exist:nTF
5572 \prg_new_conditional:Npnn \flag_if_exist:n #1 { p , T , F , TF }
5573 {
5574   \cs_if_exist:cTF { flag~#1 }
5575   { \prg_return_true: } { \prg_return_false: }
5576 }
```

(End definition for `\flag_if_exist:nTF`. This function is documented on page 83.)

`\flag_if_raised_p:n` Test if the flag has a non-zero height, by checking the 0 control sequence.

```
\flag_if_raised:nTF
5577 \__debug_patch:nnNw { \__flag_chk_exist:n {#1} } { }
5578 \prg_new_conditional:Npnn \flag_if_raised:n #1 { p , T , F , TF }
5579 {
5580   \if_cs_exist:w flag~#1~0 \cs_end:
5581   \prg_return_true:
5582   \else:
5583   \prg_return_false:
5584   \fi:
5585 }
```

(End definition for `\flag_if_raised:nTF`. This function is documented on page 83.)

**\flag\_height:n** Extract the value of the flag by going through all of the control sequences starting from 0.

```

5586 \__flag_height_loop:wn
5587 \__flag_height_end:wn
5588 \cs_new:Npn \flag_height:n #1 { \__flag_height_loop:wn 0; {#1} }
5589 {
5590   \if_cs_exist:w flag~#2~#1 \cs_end:
5591     \exp_after:wN \__flag_height_loop:wn \__int_value:w \__int_eval:w 1 +
5592   \else:
5593     \exp_after:wN \__flag_height_end:wn
5594   \fi:
5595   #1 ; {#2}
5596 }
5597 \cs_new:Npn \__flag_height_end:wn #1 ; #2 {#1}

```

(End definition for \flag\_height:n, \\_\_flag\_height\_loop:wn, and \\_\_flag\_height\_end:wn. These functions are documented on page 83.)

**\flag\_raise:n** Simply apply the trap to the height, after expanding the latter.

```

5598 \cs_new:Npn \flag_raise:n #1
5599 {
5600   \cs:w flag~#1 \exp_after:wN \cs_end:
5601   \__int_value:w \flag_height:n {#1} ;
5602 }

```

(End definition for \flag\_raise:n. This function is documented on page 83.)

```
5603 </initex | package>
```

## 11 l3quark implementation

The following test files are used for this code: m3quark001.lvt.

```
5604 <*initex | package>
```

### 11.1 Quarks

```
5605 <@@=quark>
```

**\quark\_new:N** Allocate a new quark.

```
5606 \cs_new_protected:Npn \quark_new:N #1 { \tl_const:Nn #1 {#1} }
```

(End definition for \quark\_new:N. This function is documented on page 84.)

**\q\_nil** Some “public” quarks. \q\_stop is an “end of argument” marker, \q\_nil is a empty value and \q\_no\_value marks an empty argument.

**\q\_mark**

**\q\_no\_value**

**\q\_stop**

```

5607 \quark_new:N \q_nil
5608 \quark_new:N \q_mark
5609 \quark_new:N \q_no_value
5610 \quark_new:N \q_stop

```

(End definition for \q\_nil and others. These variables are documented on page 85.)

`\q_recursion_tail` Quarks for ending recursions. Only ever used there! `\q_recursion_tail` is appended to whatever list structure we are doing recursion on, meaning it is added as a proper list item with whatever list separator is in use. `\q_recursion_stop` is placed directly after the list.

```
5611 \quark_new:N \q_recursion_tail
5612 \quark_new:N \q_recursion_stop
```

(End definition for `\q_recursion_tail` and `\q_recursion_stop`. These variables are documented on page 86.)

`\quark_if_recursion_tail_stop:N` When doing recursions, it is easy to spend a lot of time testing if the end marker has been found. To avoid this, a dedicated end marker is used each time a recursion is set up. Thus if the marker is found everything can be wrapper up and finished off. The simple case is when the test can guarantee that only a single token is being tested. In this case, there is just a dedicated copy of the standard quark test. Both a gobbling version and one inserting end code are provided.

```
5613 \cs_new:Npn \quark_if_recursion_tail_stop:N #1
5614 {
5615   \if_meaning:w \q_recursion_tail #1
5616   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
5617   \fi:
5618 }
5619 \cs_new:Npn \quark_if_recursion_tail_stop_do:Nn #1
5620 {
5621   \if_meaning:w \q_recursion_tail #1
5622   \exp_after:wN \use_i_delimit_by_q_recursion_stop:nw
5623   \else:
5624   \exp_after:wN \use_none:n
5625   \fi:
5626 }
```

(End definition for `\quark_if_recursion_tail_stop:N` and `\quark_if_recursion_tail_stop_do:Nn`. These functions are documented on page 86.)

`\quark_if_recursion_tail_stop:n` See `\quark_if_nil:nTF` for the details. Expanding `\__quark_if_recursion_tail:w` once in front of the tokens chosen here gives an empty result if and only if #1 is exactly `\q_recursion_tail`.

```
\quark_if_recursion_tail_stop:o
\quark_if_recursion_tail_stop_do:nn
\quark_if_recursion_tail_stop_do:on
\__quark_if_recursion_tail:w
5627 \cs_new:Npn \quark_if_recursion_tail_stop:n #1
5628 {
5629   \tl_if_empty:oTF
5630   { \__quark_if_recursion_tail:w {} #1 {} ?! \q_recursion_tail ??? }
5631   { \use_none_delimit_by_q_recursion_stop:w }
5632   { }
5633 }
5634 \cs_new:Npn \quark_if_recursion_tail_stop_do:nn #1
5635 {
5636   \tl_if_empty:oTF
5637   { \__quark_if_recursion_tail:w {} #1 {} ?! \q_recursion_tail ??? }
5638   { \use_i_delimit_by_q_recursion_stop:nw }
5639   { \use_none:n }
5640 }
5641 \cs_new:Npn \__quark_if_recursion_tail:w
5642   #1 \q_recursion_tail #2 ? #3 ?! { #1 #2 }
5643 \cs_generate_variant:Nn \quark_if_recursion_tail_stop:n { o }
```

```
5644 \cs_generate_variant:Nn \quark_if_recursion_tail_stop_do:nn { o }
```

(End definition for \quark\_if\_recursion\_tail\_stop:n, \quark\_if\_recursion\_tail\_stop\_do:nn, and \\_\_quark\_if\_recursion\_tail:w. These functions are documented on page 86.)

```
\_quark_if_recursion_tail_break:NN
\_quark_if_recursion_tail_break:nN
```

Analog of the \quark\_if\_recursion\_tail\_stop... functions. Break the mapping using #2.

```
5645 \cs_new:Npn \__quark_if_recursion_tail_break:NN #1#2
5646 {
5647   \if_meaning:w \q_recursion_tail #1
5648   \exp_after:wN #2
5649   \fi:
5650 }
5651 \cs_new:Npn \__quark_if_recursion_tail_break:nN #1#2
5652 {
5653   \tl_if_empty:oTF
5654   { \__quark_if_recursion_tail:w {} #1 {} ?! \q_recursion_tail ??! }
5655   {#2}
5656   { }
5657 }
```

(End definition for \\_\_quark\_if\_recursion\_tail\_break:NN and \\_\_quark\_if\_recursion\_tail\_break:nN.)

```
\quark_if_nil_p:N
\quark_if_nil:NTF
\quark_if_no_value_p:N
\quark_if_no_value_p:c
\quark_if_no_value:NTF
\quark_if_no_value:cTF
```

Here we test if we found a special quark as the first argument. We better start with \q\_no\_value as the first argument since the whole thing may otherwise loop if #1 is wrongly given a string like aabc instead of a single token.<sup>9</sup>

```
5658 \prg_new_conditional:Npnn \quark_if_nil:N #1 { p, T , F , TF }
5659 {
5660   \if_meaning:w \q_nil #1
5661   \prg_return_true:
5662   \else:
5663   \prg_return_false:
5664   \fi:
5665 }
5666 \prg_new_conditional:Npnn \quark_if_no_value:N #1 { p, T , F , TF }
5667 {
5668   \if_meaning:w \q_no_value #1
5669   \prg_return_true:
5670   \else:
5671   \prg_return_false:
5672   \fi:
5673 }
5674 \cs_generate_variant:Nn \quark_if_no_value_p:N { c }
5675 \cs_generate_variant:Nn \quark_if_no_value:NT { c }
5676 \cs_generate_variant:Nn \quark_if_no_value:NF { c }
5677 \cs_generate_variant:Nn \quark_if_no_value:NTF { c }
```

(End definition for \quark\_if\_nil:NNTF and \quark\_if\_no\_value:NTF. These functions are documented on page 85.)

```
\quark_if_nil_p:n
\quark_if_nil_p:V
\quark_if_nil_p:o
\quark_if_nil:nTF
\quark_if_nil:VTF
\quark_if_nil:oTF
\quark_if_no_value_p:n
\quark_if_no_value:nTF
\__quark_if_nil:w
\__quark_if_no_value:w
```

Let us explain \quark\_if\_nil:n(TF). Expanding \\_\_quark\_if\_nil:w once is safe thanks to the trailing \q\_nil ?!?. The result of expanding once is empty if and only

<sup>9</sup>It may still loop in special circumstances however!

if both delimited arguments #1 and #2 are empty and #3 is delimited by the last tokens ?!. Thanks to the leading {}, the argument #1 is empty if and only if the argument of \quark\_if\_nil:n starts with \q\_nil. The argument #2 is empty if and only if this \q\_nil is followed immediately by ? or by {}?, coming either from the trailing tokens in the definition of \quark\_if\_nil:n, or from its argument. In the first case, \\_\_quark\_if\_nil:w is followed by {} \q\_nil {}? ! \q\_nil ??!, hence #3 is delimited by the final ?!, and the test returns true as wanted. In the second case, the result is not empty since the first ?! in the definition of \quark\_if\_nil:n stop #3.

```

5678 \prg_new_conditional:Npnn \quark_if_nil:n #1 { p, T , F , TF }
5679 {
5680   \__tl_if_empty_return:o
5681   { \__quark_if_nil:w {} #1 {} ? ! \q_nil ? ? ! }
5682 }
5683 \cs_new:Npn \__quark_if_nil:w #1 \q_nil #2 ? #3 ? ! { #1 #2 }
5684 \prg_new_conditional:Npnn \quark_if_no_value:n #1 { p, T , F , TF }
5685 {
5686   \__tl_if_empty_return:o
5687   { \__quark_if_no_value:w {} #1 {} ? ! \q_no_value ? ? ! }
5688 }
5689 \cs_new:Npn \__quark_if_no_value:w #1 \q_no_value #2 ? #3 ? ! { #1 #2 }
5690 \cs_generate_variant:Nn \quark_if_nil_p:n { V , o }
5691 \cs_generate_variant:Nn \quark_if_nil:nTF { V , o }
5692 \cs_generate_variant:Nn \quark_if_nil:nT { V , o }
5693 \cs_generate_variant:Nn \quark_if_nil:nF { V , o }

```

(End definition for \quark\_if\_nil:nTF and others. These functions are documented on page 85.)

\q\_\_tl\_act\_mark These private quarks are needed by l3tl, but that is loaded before the quark module,  
\q\_\_tl\_act\_stop hence their definition is deferred.

```

5694 \quark_new:N \q__tl_act_mark
5695 \quark_new:N \q__tl_act_stop

```

(End definition for \q\_\_tl\_act\_mark and \q\_\_tl\_act\_stop.)

## 11.2 Scan marks

```

5696 <@@=scan>

```

\g\_\_scan\_marks\_tl The list of all scan marks currently declared.

```

5697 \tl_new:N \g__scan_marks_tl

```

(End definition for \g\_\_scan\_marks\_tl.)

**\\_\_scan\_new:N** Check whether the variable is already a scan mark, then declare it to be equal to \scan\_stop: globally.

```

5698 \cs_new_protected:Npn \__scan_new:N #1
5699 {
5700   \tl_if_in:NnTF \g__scan_marks_tl { #1 }
5701   {
5702     \__msg_kernel_error:nxx { kernel } { scanmark-already-defined }
5703     { \token_to_str:N #1 }
5704   }
5705   {
5706     \tl_gput_right:Nn \g__scan_marks_tl {#1}

```



```

5707         \cs_new_eq:NN #1 \scan_stop:
5708     }
5709 }

```

(End definition for \\_scan\_new:N.)

**\s\_stop** We only declare one scan mark here, more can be defined by specific modules.

```

5710 \__scan_new:N \s_stop

```

(End definition for \s\_stop.)

**\\_use\_none\_delimit\_by\_s\_stop:w** Similar to \use\_none\_delimit\_by\_q\_stop:w.

```

5711 \cs_new:Npn \_use_none_delimit_by_s_stop:w #1 \s_stop { }

```

(End definition for \\_use\_none\_delimit\_by\_s\_stop:w.)

**\s\_seq** This private scan mark is needed by l3seq, but that is loaded before the quark module, hence its definition is deferred.

```

5712 \__scan_new:N \s_seq

```

(End definition for \s\_seq.)

```

5713 </initex | package>

```

## 12 l3prg implementation

The following test files are used for this code: m3prg001.lvt,m3prg002.lvt,m3prg003.lvt.

```

5714 <*initex | package>

```

### 12.1 Primitive conditionals

**\if\_bool:N** Those two primitive TeX conditionals are synonyms.

```

\if_predicate:w
5715 \cs_new_eq:NN \if_bool:N \tex_ifodd:D
5716 \cs_new_eq:NN \if_predicate:w \tex_ifodd:D

```

(End definition for \if\_bool:N and \if\_predicate:w. These functions are documented on page 96.)

### 12.2 Defining a set of conditional functions

**\prg\_set\_conditional:Npnn** These are all defined in l3basics, as they are needed “early”. This is just a reminder!

**\prg\_new\_conditional:Npnn** (End definition for \prg\_set\_conditional:Npnn and others. These functions are documented on page 89.)

```

\prg_set_protected_conditional:Npnn
\prg_new_protected_conditional:Npnn
\prg_set_conditional:Nnn
\prg_new_conditional:Nnn
\prg_set_protected_conditional:Nnn
\prg_new_protected_conditional:Nnn
\prg_set_eq_conditional:NNn
\prg_new_eq_conditional:NNn
\prg_return_true:
\prg_return_false:

```

## 12.3 The boolean data type

5717 <@@=bool>

**\bool\_new:N** Boolean variables have to be initiated when they are created. Other than that there is  
**\bool\_new:c** not much to say here.

5718 \cs\_new\_protected:Npn \bool\_new:N #1 { \cs\_new\_eq:NN #1 \c\_false\_bool }  
5719 \cs\_generate\_variant:Nn \bool\_new:N { c }

(End definition for \bool\_new:N. This function is documented on page 91.)

**\bool\_set\_true:N** Setting is already pretty easy. When `check-declarations` is active, the definitions are  
**\bool\_set\_true:c** patched to make sure the boolean exists. This is needed because booleans are not based  
**\bool\_gset\_true:N** on token lists nor on T<sub>E</sub>X registers.

**\bool\_gset\_true:c** 5720 \\_\_debug\_patch:nnNw { \\_\_chk\_if\_exist\_var:N #1 } { }  
**\bool\_set\_false:N** 5721 \cs\_new\_protected:Npn \bool\_set\_true:N #1  
**\bool\_set\_false:c** 5722 { \cs\_set\_eq:NN #1 \c\_true\_bool }  
**\bool\_gset\_false:N** 5723 \\_\_debug\_patch:nnNw { \\_\_chk\_if\_exist\_var:N #1 } { }  
**\bool\_gset\_false:c** 5724 \cs\_new\_protected:Npn \bool\_set\_false:N #1  
5725 { \cs\_set\_eq:NN #1 \c\_false\_bool }  
5726 \\_\_debug\_patch:nnNw { \\_\_chk\_if\_exist\_var:N #1 } { }  
5727 \cs\_new\_protected:Npn \bool\_gset\_true:N #1  
5728 { \cs\_gset\_eq:NN #1 \c\_true\_bool }  
5729 \\_\_debug\_patch:nnNw { \\_\_chk\_if\_exist\_var:N #1 } { }  
5730 \cs\_new\_protected:Npn \bool\_gset\_false:N #1  
5731 { \cs\_gset\_eq:NN #1 \c\_false\_bool }  
5732 \cs\_generate\_variant:Nn \bool\_set\_true:N { c }  
5733 \cs\_generate\_variant:Nn \bool\_set\_false:N { c }  
5734 \cs\_generate\_variant:Nn \bool\_gset\_true:N { c }  
5735 \cs\_generate\_variant:Nn \bool\_gset\_false:N { c }

(End definition for \bool\_set\_true:N and others. These functions are documented on page 91.)

**\bool\_set\_eq:NN** The usual copy code. While it would be cleaner semantically to copy the `\cs_set_eq:NN`  
**\bool\_set\_eq:cN** family of functions, we copy `\tl_set_eq:NN` because that has the correct checking code.

**\bool\_set\_eq:Nc** 5736 \cs\_new\_eq:NN \bool\_set\_eq:NN \tl\_set\_eq:NN  
**\bool\_set\_eq:cc** 5737 \cs\_new\_eq:NN \bool\_gset\_eq:NN \tl\_gset\_eq:NN  
**\bool\_gset\_eq:NN** 5738 \cs\_generate\_variant:Nn \bool\_set\_eq:NN { Nc, cN, cc }  
**\bool\_gset\_eq:cN** 5739 \cs\_generate\_variant:Nn \bool\_gset\_eq:NN { Nc, cN, cc }

**\bool\_gset\_eq:Nc** (End definition for \bool\_set\_eq:NN and \bool\_gset\_eq:NN. These functions are documented on page  
**\bool\_gset\_eq:cc** 92.)

**\bool\_set:Nn** This function evaluates a boolean expression and assigns the first argument the meaning  
**\bool\_set:cn** \c\_true\_bool or \c\_false\_bool. Again, we include some checking code.

**\bool\_gset:Nn** 5740 \\_\_debug\_patch:nnNw { \\_\_chk\_if\_exist\_var:N #1 } { }  
**\bool\_gset:cn** 5741 \cs\_new\_protected:Npn \bool\_set:Nn #1#2  
5742 { \tex\_chardef:D #1 = \bool\_if\_p:n {#2} }  
5743 \\_\_debug\_patch:nnNw { \\_\_chk\_if\_exist\_var:N #1 } { }  
5744 \cs\_new\_protected:Npn \bool\_gset:Nn #1#2  
5745 { \tex\_global:D \tex\_chardef:D #1 = \bool\_if\_p:n {#2} }  
5746 \cs\_generate\_variant:Nn \bool\_set:Nn { c }  
5747 \cs\_generate\_variant:Nn \bool\_gset:Nn { c }

(End definition for \bool\_set:Nn and \bool\_gset:Nn. These functions are documented on page 92.)

`\bool_if_p:N` Straight forward here. We could optimize here if we wanted to as the boolean can just be input directly.

```

\bool_if_p:N 5748 \prg_new_conditional:Npnn \bool_if:N #1 { p , T , F , TF }
\bool_if_p:c 5749 {
\bool_if:NTF 5750 \if_meaning:w \c_true_bool #1
\bool_if:cTF 5751 \prg_return_true:
5752 \else:
5753 \prg_return_false:
5754 \fi:
5755 }
5756 \cs_generate_variant:Nn \bool_if_p:N { c }
5757 \cs_generate_variant:Nn \bool_if:NT { c }
5758 \cs_generate_variant:Nn \bool_if:NF { c }
5759 \cs_generate_variant:Nn \bool_if:NTF { c }

```

(End definition for `\bool_if:NTF`. This function is documented on page 92.)

`\bool_show:N` Show the truth value of the boolean, as true or false.

```

\bool_show:c 5760 \cs_new_protected:Npn \bool_show:N #1
\bool_show:n 5761 {
__bool_to_str:n 5762 \__msg_show_variable:NNNnn #1 \bool_if_exist:NTF ? { }
5763 { > ~ \token_to_str:N #1 = __bool_to_str:n {#1} }
5764 }
5765 \cs_new_protected:Npn \bool_show:n
5766 { \__msg_show_wrap:Nn __bool_to_str:n }
5767 \cs_new:Npn \__bool_to_str:n #1
5768 { \bool_if:nTF {#1} { true } { false } }
5769 \cs_generate_variant:Nn \bool_show:N { c }

```

(End definition for `\bool_show:N`, `\bool_show:n`, and `__bool_to_str:n`. These functions are documented on page 92.)

`\bool_log:N` Redirect output of `\bool_show:N` to the log.

```

\bool_log:c 5770 \cs_new_protected:Npn \bool_log:N
\bool_log:n 5771 { \__msg_log_next: \bool_show:N }
5772 \cs_new_protected:Npn \bool_log:n
5773 { \__msg_log_next: \bool_show:n }
5774 \cs_generate_variant:Nn \bool_log:N { c }

```

(End definition for `\bool_log:N` and `\bool_log:n`. These functions are documented on page 92.)

`\l_tmpa_bool` A few booleans just if you need them.

```

\l_tmpb_bool 5775 \bool_new:N \l_tmpa_bool
\g_tmpa_bool 5776 \bool_new:N \l_tmpb_bool
\g_tmpb_bool 5777 \bool_new:N \g_tmpa_bool
5778 \bool_new:N \g_tmpb_bool

```

(End definition for `\l_tmpa_bool` and others. These variables are documented on page 92.)

`\bool_if_exist_p:N` Copies of the `cs` functions defined in `l3basics`.

```

\bool_if_exist_p:c 5779 \prg_new_eq_conditional:NNn \bool_if_exist:N \cs_if_exist:N
\bool_if_exist:NTF 5780 { TF , T , F , p }
\bool_if_exist:cTF 5781 \prg_new_eq_conditional:NNn \bool_if_exist:c \cs_if_exist:c
5782 { TF , T , F , p }

```

(End definition for `\bool_if_exist:NTF`. This function is documented on page 92.)

## 12.4 Boolean expressions

`\bool_if_p:n` Evaluating the truth value of a list of predicates is done using an input syntax somewhat similar to the one found in other programming languages with ( and ) for grouping, ! for logical “Not”, && for logical “And” and || for logical “Or”. We shall use the terms Not, And, Or, Open and Close for these operations.

`\bool_if:nTF`

Any expression is terminated by a Close operation. Evaluation happens from left to right in the following manner using a GetNext function:

- If an Open is seen, start evaluating a new expression using the Eval function and call GetNext again.
- If a Not is seen, remove the ! and call a GetNotNext function, which eventually reverses the logic compared to GetNext.
- If none of the above, reinsert the token found (this is supposed to be a predicate function) in front of an Eval function, which evaluates it to the boolean value  $\langle true \rangle$  or  $\langle false \rangle$ .

The Eval function then contains a post-processing operation which grabs the instruction following the predicate. This is either And, Or or Close. In each case the truth value is used to determine where to go next. The following situations can arise:

$\langle true \rangle$ **And** Current truth value is true, logical And seen, continue with GetNext to examine truth value of next boolean (sub-)expression.

$\langle false \rangle$ **And** Current truth value is false, logical And seen, stop evaluating the predicates within this sub-expression and break to the nearest Close. Then return  $\langle false \rangle$ .

$\langle true \rangle$ **Or** Current truth value is true, logical Or seen, stop evaluating the predicates within this sub-expression and break to the nearest Close. Then return  $\langle true \rangle$ .

$\langle false \rangle$ **Or** Current truth value is false, logical Or seen, continue with GetNext to examine truth value of next boolean (sub-)expression.

$\langle true \rangle$ **Close** Current truth value is true, Close seen, return  $\langle true \rangle$ .

$\langle false \rangle$ **Close** Current truth value is false, Close seen, return  $\langle false \rangle$ .

We introduce an additional Stop operation with the same semantics as the Close operation.

$\langle true \rangle$ **Stop** Current truth value is true, return  $\langle true \rangle$ .

$\langle false \rangle$ **Stop** Current truth value is false, return  $\langle false \rangle$ .

The reasons for this follow below.

```

5783 \prg_new_conditional:Npnn \bool_if:n #1 { T , F , TF }
5784 {
5785   \if_predicate:w \bool_if_p:n {#1}
5786     \prg_return_true:
5787   \else:
5788     \prg_return_false:
5789   \fi:
5790 }
```

(End definition for `\bool_if:nTF`. This function is documented on page 94.)

`\bool_if_p:n` First issue a `\group_align_safe_begin:` as we are using `&&` as syntax shorthand for the And operation and we need to hide it for  $\TeX$ . This is closed at the end of the expression parsing (see S below).

Minimal (“short-circuit”) evaluation of boolean expressions requires skipping to the end of the current parenthesized group when `\true` is seen, but to the next `||` or closing parenthesis when `\false` is seen. To avoid having separate functions for the two cases, we transform the boolean expression by doubling each parenthesis and adding parenthesis around each `||`. This ensures that `&&` binds tighter than `||`.

The replacement is done in three passes, for left and right parentheses and for `||`. At each pass, the part of the expression that has been transformed is stored before `\q_nil`, the rest lies until the first `\q_mark`, followed by an empty brace group. A trailing marker ensures that the auxiliaries’ delimited arguments do not run-away. As long as the delimiter matches inside the expression, material is moved before `\q_nil` and we continue. Afterwards, the trailing marker is taken as a delimiter, #4 is the next auxiliary, immediately followed by a new `\q_nil` delimiter, which indicates that nothing has been treated at this pass. The last step calls `\__bool_if_parse:NNNww` which cleans up and triggers the evaluation of the expression itself.

```

5791 \cs_new:Npn \bool_if_p:n #1
5792 {
5793   \group_align_safe_begin:
5794   \__bool_if_left_parentheses:www \q_nil
5795   #1 \q_mark { }
5796   ( \q_mark { \__bool_if_right_parentheses:www \q_nil }
5797   ) \q_mark { \__bool_if_or:www \q_nil }
5798   || \q_mark \__bool_if_parse:NNNww
5799   \q_stop
5800 }
5801 \cs_new:Npn \__bool_if_left_parentheses:www #1 \q_nil #2 ( #3 \q_mark #4
5802 { #4 \__bool_if_left_parentheses:www #1 #2 (( \q_nil #3 \q_mark {#4} }
5803 \cs_new:Npn \__bool_if_right_parentheses:www #1 \q_nil #2 ) #3 \q_mark #4
5804 { #4 \__bool_if_right_parentheses:www #1 #2 )) \q_nil #3 \q_mark {#4} }
5805 \cs_new:Npn \__bool_if_or:www #1 \q_nil #2 || #3 \q_mark #4
5806 { #4 \__bool_if_or:www #1 #2 )||( \q_nil #3 \q_mark {#4} }

```

(End definition for `\bool_if_p:n` and others. These functions are documented on page 94.)

`\__bool_if_parse:NNNww` After removing extra tokens from the transformation phase, start evaluating. At the end, we need to finish the special `align_safe` group before finally returning a `\c_true_bool` or `\c_false_bool` as there might otherwise be something left in front in the input stream. For this we call the Stop operation, denoted simply by a S following the last Close operation.

```

5807 \cs_new:Npn \__bool_if_parse:NNNww #1#2#3#4 \q_mark #5 \q_stop
5808 {
5809   \__bool_get_next:NN \use_i:nn (( #4 )) S
5810 }

```

(End definition for `\__bool_if_parse:NNNww`.)

`\__bool_get_next:NN` The GetNext operation. This is a switch: if what follows is neither `!` nor `(`, we assume it is a predicate. The first argument is `\use_ii:nn` if the logic must eventually be reversed (after a `!`), otherwise it is `\use_i:nn`. This function eventually expand to the truth

value `\c_true_bool` or `\c_false_bool` of the expression which follows until the next unmatched closing parenthesis.

```

5811 \cs_new:Npn \__bool_get_next:NN #1#2
5812 {
5813   \use:c
5814   {
5815     __bool_
5816     \if_meaning:w !#2 ! \else: \if_meaning:w (#2 ( \else: p \fi: \fi:
5817     :Nw
5818   }
5819   #1 #2
5820 }

```

(End definition for `\__bool_get_next:NN`.)

`\__bool_!:Nw` The Not operation reverses the logic: discard the `!` token and call the `GetNext` operation with its first argument reversed.

```

5821 \cs_new:cpn { __bool_!:Nw } #1#2
5822 { \exp_after:wN \__bool_get_next:NN #1 \use_ii:nn \use_i:nn }

```

(End definition for `\__bool_!:Nw`.)

`\__bool_(:Nw` The Open operation starts a sub-expression after discarding the token. This is done by calling `GetNext`, with a post-processing step which looks for And, Or or Close afterwards.

```

5823 \cs_new:cpn { __bool_(:Nw } #1#2
5824 {
5825   \exp_after:wN \__bool_choose:NNN \exp_after:wN #1
5826   \__int_value:w \__bool_get_next:NN \use_i:nn
5827 }

```

(End definition for `\__bool_(:Nw`.)

`\__bool_p:Nw` If what follows `GetNext` is neither `!` nor `(`, evaluate the predicate using the primitive `\__int_value:w`. The canonical true and false values have numerical values 1 and 0 respectively. Look for And, Or or Close afterwards.

```

5828 \cs_new:cpn { __bool_p:Nw } #1
5829 { \exp_after:wN \__bool_choose:NNN \exp_after:wN #1 \__int_value:w }

```

(End definition for `\__bool_p:Nw`.)

`\__bool_choose:NNN` Branching the eight-way switch. The arguments are 1: `\use_i:nn` or `\use_ii:nn`, 2: 0 or 1 encoding the current truth value, 3: the next operation, And, Or, Close or Stop. If #1 is `\use_ii:nn`, the logic of #2 must be reversed.

```

5830 \cs_new:Npn \__bool_choose:NNN #1#2#3
5831 {
5832   \use:c
5833   {
5834     __bool_ #3 _
5835     #1 #2 { \if_meaning:w 0 #2 1 \else: 0 \fi: }
5836     :w
5837   }
5838 }

```

(End definition for `\__bool_choose:NNN`.)

`\_bool_)_0:w` Closing a group is just about returning the result. The Stop operation is similar except  
`\_bool_)_1:w` it closes the special alignment group before returning the boolean.

```

\__bool_S_0:w 5839 \cs_new:cpn { \__bool_)_0:w } { \c_false_bool }
\__bool_S_1:w 5840 \cs_new:cpn { \__bool_)_1:w } { \c_true_bool }
5841 \cs_new:cpn { \__bool_S_0:w } { \group_align_safe_end: \c_false_bool }
5842 \cs_new:cpn { \__bool_S_1:w } { \group_align_safe_end: \c_true_bool }

```

(End definition for `\_bool_)_0:w` and others.)

`\_bool_&_1:w` Two cases where we simply continue scanning. We must remove the second `&` or `|`.

```

\__bool_|_0:w 5843 \cs_new:cpn { \_bool_&_1:w } & { \__bool_get_next:NN \use_i:nn }
5844 \cs_new:cpn { \__bool_|_0:w } | { \__bool_get_next:NN \use_i:nn }

```

(End definition for `\_bool_&_1:w` and `\__bool_|_0:w`.)

`\_bool_&_0:w` When the truth value has already been decided, we have to throw away the remainder  
`\_bool_|_1:w` of the current group as we are doing minimal evaluation. This is slightly tricky as there  
`\_bool_eval_skip_to_end_auxi:Nw` are no braces so we have to play match the `()` manually.

```

5845 \cs_new:cpn { \_bool_&_0:w } &
5846 { \_bool_eval_skip_to_end_auxi:Nw \c_false_bool }
5847 \cs_new:cpn { \_bool_|_1:w } |
5848 { \_bool_eval_skip_to_end_auxi:Nw \c_true_bool }

```

There is always at least one `)` waiting, namely the outer one. However, we are facing the problem that there may be more than one that need to be finished off and we have to detect the correct number of them. Here is a complicated example showing how this is done. After evaluating the following, we realize we must skip everything after the first And. Note the extra Close at the end.

```
\c_false_bool && ((abc) && xyz) && ((xyz) && (def)))
```

First read up to the first Close. This gives us the list we first read up until the first right parenthesis so we are looking at the token list

```
((abc
```

This contains two Open markers so we must remove two groups. Since no evaluation of the contents is to be carried out, it doesn't matter how we remove the groups as long as we wind up with the correct result. We therefore first remove a `()` pair and what preceded the Open – but leave the contents as it may contain Open tokens itself – leaving

```
(abc && xyz) && ((xyz) && (def)))
```

Another round of this gives us

```
(abc && xyz
```

which still contains an Open so we remove another `()` pair, giving us

```
abc && xyz && ((xyz) && (def)))
```

Again we read up to a Close and again find Open tokens:

```
abc && xyz && ((xyz
```

Further reduction gives us

```
(xyz && (def)))
```

and then

```
(xyz && (def
```

with reduction to

```
xyz && (def))
```

and ultimately we arrive at no Open tokens being skipped and we can finally close the group nicely.

```
5849 %% (
5850 \cs_new:Npn \__bool_eval_skip_to_end_auxi:Nw #1#2 )
5851 {
5852   \__bool_eval_skip_to_end_auxii:Nw #1#2 ( % )
5853   \q_no_value \q_stop
5854   {#2}
5855 }
```

If no right parenthesis, then #3 is no\_value and we are done, return the boolean #1. If there is, we need to grab a () pair and then recurse

```
5856 \cs_new:Npn \__bool_eval_skip_to_end_auxii:Nw #1#2 ( #3#4 \q_stop #5 % )
5857 {
5858   \quark_if_no_value:NTF #3
5859   {#1}
5860   { \__bool_eval_skip_to_end_auxiii:Nw #1 #5 }
5861 }
```

Keep the boolean, throw away anything up to the ( as it is irrelevant, remove a () pair but remember to reinsert #3 as it may contain ( tokens!

```
5862 \cs_new:Npn \__bool_eval_skip_to_end_auxiii:Nw #1#2 ( #3 )
5863 { % (
5864   \__bool_eval_skip_to_end_auxi:Nw #1#3 )
5865 }
```

(End definition for \\_\_bool\_&\_0:w and others.)

**\bool\_lazy\_all\_p:n** Go through the list of expressions, stopping whenever an expression is false. If the end is reached without finding any false expression, then the result is true.

**\bool\_lazy\_all:nTF**

**\\_\_bool\_lazy\_all:n**

```
5866 \prg_new_conditional:Npnn \bool_lazy_all:n #1 { p , T , F , TF }
5867 { \__bool_lazy_all:n #1 \q_recursion_tail \q_recursion_stop }
5868 \cs_new:Npn \__bool_lazy_all:n #1
5869 {
5870   \quark_if_recursion_tail_stop_do:nn {#1} { \prg_return_true: }
5871   \bool_if:nF {#1}
5872   { \use_i_delimit_by_q_recursion_stop:nw { \prg_return_false: } }
5873   \__bool_lazy_all:n
5874 }
```

(End definition for \bool\_lazy\_all:nTF and \\_\_bool\_lazy\_all:n. These functions are documented on page 94.)



**\bool\_lazy\_and\_p:nn** Only evaluate the second expression if the first is true.  
**\bool\_lazy\_and:nnTF**

```

5875 \prg_new_conditional:Npnn \bool_lazy_and:nn #1#2 { p , T , F , TF }
5876 {
5877     \bool_if:nTF {#1}
5878     { \bool_if:nTF {#2} { \prg_return_true: } { \prg_return_false: } }
5879     { \prg_return_false: }
5880 }

```

(End definition for \bool\_lazy\_and:nnTF. This function is documented on page 94.)

**\bool\_lazy\_any\_p:n** Go through the list of expressions, stopping whenever an expression is true. If the end is reached without finding any true expression, then the result is false.  
**\bool\_lazy\_any:nTF**  
**\\_\_bool\_lazy\_any:n**

```

5881 \prg_new_conditional:Npnn \bool_lazy_any:n #1 { p , T , F , TF }
5882 { \__bool_lazy_any:n #1 \q_recursion_tail \q_recursion_stop }
5883 \cs_new:Npn \__bool_lazy_any:n #1
5884 {
5885     \quark_if_recursion_tail_stop_do:nn {#1} { \prg_return_false: }
5886     \bool_if:nT {#1}
5887     { \use_i_delimit_by_q_recursion_stop:nw { \prg_return_true: } }
5888     \__bool_lazy_any:n
5889 }

```

(End definition for \bool\_lazy\_any:nTF and \\_\_bool\_lazy\_any:n. These functions are documented on page 94.)

**\bool\_lazy\_or\_p:nn** Only evaluate the second expression if the first is false.  
**\bool\_lazy\_or:nnTF**

```

5890 \prg_new_conditional:Npnn \bool_lazy_or:nn #1#2 { p , T , F , TF }
5891 {
5892     \bool_if:nTF {#1}
5893     { \prg_return_true: }
5894     { \bool_if:nTF {#2} { \prg_return_true: } { \prg_return_false: } }
5895 }

```

(End definition for \bool\_lazy\_or:nnTF. This function is documented on page 94.)

**\bool\_not\_p:n** The Not variant just reverses the outcome of \bool\_if\_p:n. Can be optimized but this is nice and simple and according to the implementation plan. Not even particularly useful to have it when the infix notation is easier to use.

```

5896 \cs_new:Npn \bool_not_p:n #1 { \bool_if_p:n { ! ( #1 ) } }

```

(End definition for \bool\_not\_p:n. This function is documented on page 94.)

**\bool\_xor\_p:nn** Exclusive or. If the boolean expressions have same truth value, return false, otherwise return true.

```

5897 \cs_new:Npn \bool_xor_p:nn #1#2
5898 {
5899     \int_compare:nNnTF { \bool_if_p:n {#1} } = { \bool_if_p:n {#2} }
5900     \c_false_bool
5901     \c_true_bool
5902 }

```

(End definition for \bool\_xor\_p:nn. This function is documented on page 94.)

## 12.5 Logical loops

`\bool_while_do:Nn` A while loop where the boolean is tested before executing the statement. The “while” version executes the code as long as the boolean is true; the “until” version executes the code as long as the boolean is false.

```
\bool_while_do:cn
\bool_while_do:Nn
\bool_until_do:Nn
\bool_until_do:cn
5903 \cs_new:Npn \bool_while_do:Nn #1#2
5904   { \bool_if:NT #1 { #2 \bool_while_do:Nn #1 {#2} } }
5905 \cs_new:Npn \bool_until_do:Nn #1#2
5906   { \bool_if:NF #1 { #2 \bool_until_do:Nn #1 {#2} } }
5907 \cs_generate_variant:Nn \bool_while_do:Nn { c }
5908 \cs_generate_variant:Nn \bool_until_do:Nn { c }
```

*(End definition for \bool\_while\_do:Nn and \bool\_until\_do:Nn. These functions are documented on page 95.)*

`\bool_do_while:Nn` A do-while loop where the body is performed at least once and the boolean is tested after executing the body. Otherwise identical to the above functions.

```
\bool_do_while:cn
\bool_do_while:Nn
\bool_do_until:Nn
\bool_do_until:cn
5909 \cs_new:Npn \bool_do_while:Nn #1#2
5910   { #2 \bool_if:NT #1 { \bool_do_while:Nn #1 {#2} } }
5911 \cs_new:Npn \bool_do_until:Nn #1#2
5912   { #2 \bool_if:NF #1 { \bool_do_until:Nn #1 {#2} } }
5913 \cs_generate_variant:Nn \bool_do_while:Nn { c }
5914 \cs_generate_variant:Nn \bool_do_until:Nn { c }
```

*(End definition for \bool\_do\_while:Nn and \bool\_do\_until:Nn. These functions are documented on page 95.)*

`\bool_while_do:nn` Loop functions with the test either before or after the first body expansion.

```
\bool_do_while:nn
\bool_while_do:nn
\bool_until_do:nn
\bool_do_until:nn
5915 \cs_new:Npn \bool_while_do:nn #1#2
5916   {
5917     \bool_if:nT {#1}
5918     {
5919       #2
5920       \bool_while_do:nn {#1} {#2}
5921     }
5922   }
5923 \cs_new:Npn \bool_do_while:nn #1#2
5924   {
5925     #2
5926     \bool_if:nT {#1} { \bool_do_while:nn {#1} {#2} }
5927   }
5928 \cs_new:Npn \bool_until_do:nn #1#2
5929   {
5930     \bool_if:nF {#1}
5931     {
5932       #2
5933       \bool_until_do:nn {#1} {#2}
5934     }
5935   }
5936 \cs_new:Npn \bool_do_until:nn #1#2
5937   {
5938     #2
5939     \bool_if:nF {#1} { \bool_do_until:nn {#1} {#2} }
5940   }
```

*(End definition for \bool\_while\_do:nn and others. These functions are documented on page 95.)*

## 12.6 Producing multiple copies

5941  $\langle @@=prg \rangle$ 

`\prg_replicate:nn` This function uses a cascading csname technique by David Kastrup (who else :-)

The idea is to make the input 25 result in first adding five, and then 20 copies of the code to be replicated. The technique uses cascading cnames which means that we start building several cnames so we end up with a list of functions to be called in reverse order. This is important here (and other places) because it means that we can for instance make the function that inserts five copies of something to also hand down ten to the next function in line. This is exactly what happens here: in the example with 25 then the next function is the one that inserts two copies but it sees the ten copies handed down by the previous function. In order to avoid the last function to insert say, 100 copies of the original argument just to gobble them again we define separate functions to be inserted first. These functions also close the expansion of `\exp:w`, which ensures that `\prg_replicate:nn` only requires two steps of expansion.

This function has one flaw though: Since it constantly passes down ten copies of its previous argument it severely affects the main memory once you start demanding hundreds of thousands of copies. Now I don't think this is a real limitation for any ordinary use, and if necessary, it is possible to write `\prg_replicate:nn {1000} { \prg_replicate:nn {1000} {code } }`. An alternative approach is to create a string of `m's` with `\exp:w` which can be done with just four macros but that method has its own problems since it can exhaust the string pool. Also, it is considerably slower than what we use here so the few extra `csnames` are well spent I would say.

```

5942 \cs_new:Npn \prg_replicate:nn #1
5943 {
5944   \exp:w
5945     \exp_after:wN \__prg_replicate_first:N
5946     \__int_value:w \__int_eval:w #1 \__int_eval_end:
5947     \cs_end:
5948 }
5949 \cs_new:Npn \__prg_replicate:N #1
5950 { \cs:w \__prg_replicate_#1 :n \__prg_replicate:N }
5951 \cs_new:Npn \__prg_replicate_first:N #1
5952 { \cs:w \__prg_replicate_first_#1 :n \__prg_replicate:N }

```

Then comes all the functions that do the hard work of inserting all the copies. The first function takes `:n` as a parameter.

```

5953 \cs_new:Npn \__prg_replicate_ :n #1 { \cs_end: }
5954 \cs_new:cpn { __prg_replicate_0:n } #1
5955   { \cs_end: {#1#1#1#1#1#1#1#1#1#1} }
5956 \cs_new:cpn { __prg_replicate_1:n } #1
5957   { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1 }
5958 \cs_new:cpn { __prg_replicate_2:n } #1
5959   { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1 }
5960 \cs_new:cpn { __prg_replicate_3:n } #1
5961   { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1 }
5962 \cs_new:cpn { __prg_replicate_4:n } #1
5963   { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1 }
5964 \cs_new:cpn { __prg_replicate_5:n } #1
5965   { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1 }
5966 \cs_new:cpn { __prg_replicate_6:n } #1
5967   { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1#1 }

```

Users shouldn't ask for something to be replicated once or even not at all but...

(End definition for `\prg_replicate:nn` and others. These functions are documented on page 96.)

## 12.7 Detecting T<sub>E</sub>X's mode

`\mode_if_vertical_p:` For testing vertical mode. Strikes me here on the bus with David, that as long as we are just talking about returning true and false states, we can just use the primitive conditionals for this and gobbling the `\exp_end:` in the input stream. However this requires knowledge of the implementation so we keep things nice and clean and use the return statements.

```
5989 \prg_new_conditional:Npnn \mode_if_vertical: { p , T , F , TF }
5990 { \if mode vertical: \prg_return true: \else: \prg_return false: \fi: }
```

(End definition for \mode\_if\_vertical:TF. This function is documented on page 96.)

`\mode if horizontal p:` For testing horizontal mode.

```

\mode_if_horizontal:TF      5991 \prg_new_conditional:Npnm \mode_if_horizontal: { p , T , F , TF }
                             5992 { \if mode horizontal: \prg_return true: \else: \prg_return false: \fi: }

```

(End definition for \mode if horizontal:TF. This function is documented on page 96.)

`\mode_if_inner_p:` For testing inner mode.

```
\mode_if_inner:TF 5993 \prg_new_conditional:Npnn \mode_if_inner: { p , T , F , TF }
5994 { \if mode inner: \prg return true: \else: \prg return false: \fi: }
```

(End definition for \mode\_if\_inner:TF. This function is documented on page 96.)

`\mode_if_math_p:` For testing math mode. At the beginning of an alignment cell, this should be used only inside a non-expandable function.

```

5995 \prg_new_conditional:Npnn \mode_if_math: { p , T , F , TF }
5996 { \if_mode_math: \prg_return_true: \else: \prg_return_false: \fi: }

```

(End definition for `\mode if math:TF`. This function is documented on page 96.)

## 12.8 Internal programming functions

`\group_align_safe_begin:`  $\TeX$ 's alignment structures present many problems. As Knuth says himself in *TeX: The Program*: “It’s sort of a miracle whenever `\halign` or `\valign` work, [...]” One problem relates to commands that internally issues a `\cr` but also peek ahead for the next character for use in, say, an optional argument. If the next token happens to be a `&` with category code 4 we get some sort of weird error message because the underlying `\futurelet` stores the token at the end of the alignment template. This could be a `&_4` giving a message like `! Misplaced \cr.` or even worse: it could be the `\endtemplate` token causing even more trouble! To solve this we have to open a special group so that  $\TeX$  still thinks it’s on safe ground but at the same time we don’t want to introduce any brace group that may find its way to the output. The following functions help with this by using code documented only in Appendix D of *The TeXbook*... We place the `\if_false: { \fi:` part at that place so that the successive expansions of `\group_align_safe_begin/end:` are always brace balanced.

```
5997 \cs_new:Npn \group_align_safe_begin:
5998   { \if_int_compare:w \if_false: { \fi: ‘} = \c_zero \fi: }
5999 \cs_new:Npn \group_align_safe_end:
6000   { \if_int_compare:w ‘{ = \c_zero } \fi: }
```

(End definition for `\group_align_safe_begin:` and `\group_align_safe_end:.`)

```
6001 <@@=prg>
```

`\g__prg_map_int` A nesting counter for mapping.

```
6002 \int_new:N \g__prg_map_int
```

(End definition for `\g__prg_map_int.`)

`\__prg_break_point:Nn` These are defined in `l3basics`, as they are needed “early”. This is just a reminder that is the case!

`\__prg_map_break:Nn`

(End definition for `\__prg_break_point:Nn` and `\__prg_map_break:Nn.`)

`\__prg_break_point:` Also done in `l3basics` as in format mode these are needed within `l3alloc`.

`\__prg_break:`

`\__prg_break:n`

(End definition for `\__prg_break_point:`, `\__prg_break:`, and `\__prg_break:n.`)

```
6003 </initex | package>
```

## 13 l3clist implementation

The following test files are used for this code: `m3clist002`.

```
6004 <*initex | package>
```

```
6005 <@@=clist>
```

`\c_empty_clist` An empty comma list is simply an empty token list.

```
6006 \cs_new_eq:NN \c_empty_clist \c_empty_tl
```

(End definition for `\c_empty_clist`. This variable is documented on page 106.)

`\l__clist_internal_clist` Scratch space for various internal uses. This comma list variable cannot be declared as such because it comes before `\clist_new:N`

```
6007 \tl_new:N \l__clist_internal_clist
```

(End definition for \l\_\_clist\_internal\_clist.)

\\_\_clist\_tmp:w A temporary function for various purposes.  
6008 \cs\_new\_protected:Npn \\_\_clist\_tmp:w { }  
(End definition for \\_\_clist\_tmp:w.)

### 13.1 Allocation and initialisation

**\clist\_new:N** Internally, comma lists are just token lists.

\clist\_new:c 6009 \cs\_new\_eq:NN \clist\_new:N \tl\_new:N  
6010 \cs\_new\_eq:NN \clist\_new:c \tl\_new:c

(End definition for \clist\_new:N. This function is documented on page 98.)

**\clist\_const:Nn** Creating and initializing a constant comma list is done in a way similar to \clist\_set:Nn and \clist\_gset:Nn, being careful to strip spaces.

\clist\_const:cn 6011 \cs\_new\_protected:Npn \clist\_const:Nn #1#2  
\clist\_const:Nx 6012 { \tl\_const:Nx #1 { \\_\_clist\_trim\_spaces:n {#2} } }  
\clist\_const:cx 6013 \cs\_generate\_variant:Nn \clist\_const:Nn { c , Nx , cx }

(End definition for \clist\_const:Nn. This function is documented on page 98.)

**\clist\_clear:N** Clearing comma lists is just the same as clearing token lists.

\clist\_clear:c 6014 \cs\_new\_eq:NN \clist\_clear:N \tl\_clear:N  
\clist\_gclear:N 6015 \cs\_new\_eq:NN \clist\_clear:c \tl\_clear:c  
\clist\_gclear:c 6016 \cs\_new\_eq:NN \clist\_gclear:N \tl\_gclear:N  
6017 \cs\_new\_eq:NN \clist\_gclear:c \tl\_gclear:c

(End definition for \clist\_clear:N and \clist\_gclear:N. These functions are documented on page 98.)

**\clist\_clear\_new:N** Once again a copy from the token list functions.

\clist\_clear\_new:c 6018 \cs\_new\_eq:NN \clist\_clear\_new:N \tl\_clear\_new:N  
\clist\_gclear\_new:N 6019 \cs\_new\_eq:NN \clist\_clear\_new:c \tl\_clear\_new:c  
\clist\_gclear\_new:c 6020 \cs\_new\_eq:NN \clist\_gclear\_new:N \tl\_gclear\_new:N  
6021 \cs\_new\_eq:NN \clist\_gclear\_new:c \tl\_gclear\_new:c

(End definition for \clist\_clear\_new:N and \clist\_gclear\_new:N. These functions are documented on page 98.)

**\clist\_set\_eq:NN** Once again, these are simple copies from the token list functions.

\clist\_set\_eq:cN 6022 \cs\_new\_eq:NN \clist\_set\_eq:NN \tl\_set\_eq:NN  
\clist\_set\_eq:Nc 6023 \cs\_new\_eq:NN \clist\_set\_eq:Nc \tl\_set\_eq:Nc  
\clist\_set\_eq:cc 6024 \cs\_new\_eq:NN \clist\_set\_eq:cN \tl\_set\_eq:cN  
\clist\_gset\_eq:NN 6025 \cs\_new\_eq:NN \clist\_set\_eq:cc \tl\_set\_eq:cc  
\clist\_gset\_eq:cN 6026 \cs\_new\_eq:NN \clist\_gset\_eq:NN \tl\_gset\_eq:NN  
\clist\_gset\_eq:Nc 6027 \cs\_new\_eq:NN \clist\_gset\_eq:Nc \tl\_gset\_eq:Nc  
\clist\_gset\_eq:cN 6028 \cs\_new\_eq:NN \clist\_gset\_eq:cN \tl\_gset\_eq:cN  
\clist\_gset\_eq:cc 6029 \cs\_new\_eq:NN \clist\_gset\_eq:cc \tl\_gset\_eq:cc

(End definition for \clist\_set\_eq:NN and \clist\_gset\_eq:NN. These functions are documented on page 99.)

```

\clist_set_from_seq:NN
\clist_set_from_seq:cN
\clist_set_from_seq:Nc
\clist_set_from_seq:cc
\clist_gset_from_seq:NN
\clist_gset_from_seq:cN
\clist_gset_from_seq:Nc
\clist_gset_from_seq:cc
\__clist_set_from_seq:NNNN
\__clist_wrap_item:n
\__clist_set_from_seq:w

```

Setting a comma list from a comma-separated list is done using a simple mapping. We wrap most items with `\exp_not:n`, and a comma. Items which contain a comma or a space are surrounded by an extra set of braces. The first comma must be removed, except in the case of an empty comma-list.

```

6030 \cs_new_protected:Npn \clist_set_from_seq:NN
6031 { \__clist_set_from_seq:NNNN \clist_clear:N \tl_set:Nx }
6032 \cs_new_protected:Npn \clist_gset_from_seq:NN
6033 { \__clist_set_from_seq:NNNN \clist_gclear:N \tl_gset:Nx }
6034 \cs_new_protected:Npn \__clist_set_from_seq:NNNN #1#2#3#4
6035 {
6036   \seq_if_empty:NTF #4
6037   { #1 #3 }
6038   {
6039     #2 #3
6040     {
6041       \exp_last_unbraced:Nf \use_none:n
6042       { \seq_map_function:NN #4 \__clist_wrap_item:n }
6043     }
6044   }
6045 }
6046 \cs_new:Npn \__clist_wrap_item:n #1
6047 {
6048   ,
6049   \tl_if_empty:oTF { \__clist_set_from_seq:w #1 ~ , #1 ~ }
6050   { \exp_not:n {#1} }
6051   { \exp_not:n { {#1} } }
6052 }
6053 \cs_new:Npn \__clist_set_from_seq:w #1 , #2 ~ { }
6054 \cs_generate_variant:Nn \clist_set_from_seq:NN { Nc }
6055 \cs_generate_variant:Nn \clist_set_from_seq:NN { c , cc }
6056 \cs_generate_variant:Nn \clist_gset_from_seq:NN { Nc }
6057 \cs_generate_variant:Nn \clist_gset_from_seq:NN { c , cc }

```

(End definition for `\clist_set_from_seq:NN` and others. These functions are documented on page 99.)

```

\clist_concat:NNN
\clist_concat:ccc
\clist_gconcat:NNN
\clist_gconcat:ccc
\__clist_concat:NNNN

```

Concatenating comma lists is not quite as easy as it seems, as there needs to be the correct addition of a comma to the output. So a little work to do.

```

6058 \cs_new_protected:Npn \clist_concat:NNN
6059 { \__clist_concat:NNNN \tl_set:Nx }
6060 \cs_new_protected:Npn \clist_gconcat:NNN
6061 { \__clist_concat:NNNN \tl_gset:Nx }
6062 \cs_new_protected:Npn \__clist_concat:NNNN #1#2#3#4
6063 {
6064   #1 #2
6065   {
6066     \exp_not:o #3
6067     \clist_if_empty:NF #3 { \clist_if_empty:NF #4 { , } }
6068     \exp_not:o #4
6069   }
6070 }
6071 \cs_generate_variant:Nn \clist_concat:NNN { ccc }
6072 \cs_generate_variant:Nn \clist_gconcat:NNN { ccc }

```

(End definition for `\clist_concat:NNN`, `\clist_gconcat:NNN`, and `\__clist_concat:NNNN`. These functions are documented on page 99.)

```

\clist_if_exist_p:N Copies of the cs functions defined in l3basics.
\clist_if_exist_p:c 6073 \prg_new_eq_conditional:NNn \clist_if_exist:N \cs_if_exist:N
\clist_if_exist:NTF 6074 { TF , T , F , p }
\clist_if_exist:cTF 6075 \prg_new_eq_conditional:NNn \clist_if_exist:c \cs_if_exist:c
6076 { TF , T , F , p }

```

(End definition for `\clist_if_exist:N`. This function is documented on page 99.)

## 13.2 Removing spaces around items

`\_clist_trim_spaces_generic:nw` This expands to the `<code>`, followed by a brace group containing the `<item>`, with leading and trailing spaces removed. The calling function is responsible for inserting `\q_mark` in front of the `<item>`, as well as testing for the end of the list. We reuse a `l3tl` internal function, whose first argument must start with `\q_mark`. That trims the item `#2`, then feeds the result (after having to do an o-type expansion) to `\_clist_trim_spaces_generic:nn` which places the `<code>` in front of the `<trimmed item>`.

```

6077 \cs_new:Npn \_clist_trim_spaces_generic:nw #1#2 ,
6078 {
6079     \_tl_trim_spaces:nn {#2}
6080     { \exp_args:No \_clist_trim_spaces_generic:nn } {#1}
6081 }
6082 \cs_new:Npn \_clist_trim_spaces_generic:nn #1#2 { #2 {#1} }

```

(End definition for `\_clist_trim_spaces_generic:nw` and `\_clist_trim_spaces_generic:nn`.)

`\_clist_trim_spaces:n` The first argument of `\_clist_trim_spaces:nn` is initially empty, and later a comma, namely, as soon as we have added an item to the resulting list. The auxiliary tests for the end of the list, and also prevents empty arguments from finding their way into the output.

```

6083 \cs_new:Npn \_clist_trim_spaces:n #1
6084 {
6085     \_clist_trim_spaces_generic:nw
6086     { \_clist_trim_spaces:nn { } }
6087     \q_mark #1 ,
6088     \q_recursion_tail, \q_recursion_stop
6089 }
6090 \cs_new:Npn \_clist_trim_spaces:nn #1 #2
6091 {
6092     \quark_if_recursion_tail_stop:n {#2}
6093     \tl_if_empty:nTF {#2}
6094     {
6095         \_clist_trim_spaces_generic:nw
6096         { \_clist_trim_spaces:nn {#1} } \q_mark
6097     }
6098     {
6099         #1 \exp_not:n {#2}
6100         \_clist_trim_spaces_generic:nw
6101         { \_clist_trim_spaces:nn { , } } \q_mark
6102     }
6103 }

```

(End definition for `\_clist_trim_spaces:n` and `\_clist_trim_spaces:nn`.)



### 13.3 Adding data to comma lists

```

\clist_set:Nn
\clist_set:NV
\clist_set:No
\clist_set:Nx
\clist_set:cn
\clist_set:cV
\clist_set:co
\clist_set:cx
\clist_gset:Nn
\clist_gset:NV
\clist_gset:No
\clist_gset:Nx
\clist_gset:cn
\clist_gset:cV
\clist_gset:co
\clist_gset:cx
\clist_put_left:Nn
\clist_put_left:NV
\clist_put_left:No
\clist_put_left:Nx
\clist_put_left:cn
\clist_put_left:cV
\clist_put_left:co
\clist_put_left:cx
\clist_gput_left:Nn
\clist_gput_left:NV
\clist_gput_left:No
\clist_gput_left:Nx
\clist_gput_left:cn
\clist_gput_left:cV
\clist_gput_left:co
\clist_gput_left:cx
__clist_put_left:NNNn
\clist_put_right:Nn
\clist_put_right:NV
\clist_put_right:No
\clist_put_right:Nx
\clist_put_right:cn
\clist_put_right:cV
\clist_put_right:co
\clist_put_right:cx
\clist_gput_right:Nn
\clist_gput_right:NV
\clist_gput_right:No
\clist_gput_right:Nx
\clist_gput_right:cn
\clist_gput_right:cV
\clist_gput_right:co
\clist_gput_right:cx
__clist_put_right:NNNn

```

(End definition for `\clist_set:Nn` and `\clist_gset:Nn`. These functions are documented on page 99.)

Comma lists cannot hold empty values: there are therefore a couple of sanity checks to avoid accumulating commas.

```

6104 \cs_new_protected:Npn \clist_set:Nn #1#2
6105 { \tl_set:Nx #1 { \__clist_trim_spaces:n {#2} } }
6106 \cs_new_protected:Npn \clist_gset:Nn #1#2
6107 { \tl_gset:Nx #1 { \__clist_trim_spaces:n {#2} } }
6108 \cs_generate_variant:Nn \clist_set:Nn { NV , No , Nx , c , cV , co , cx }
6109 \cs_generate_variant:Nn \clist_gset:Nn { NV , No , Nx , c , cV , co , cx }
6110 \cs_new_protected:Npn \clist_put_left:Nn
6111 { \__clist_put_left:NNNn \clist_concat:NNN \clist_set:Nn }
6112 \cs_new_protected:Npn \clist_gput_left:Nn
6113 { \__clist_put_left:NNNn \clist_gconcat:NNN \clist_set:Nn }
6114 \cs_new_protected:Npn \__clist_put_left:NNNn #1#2#3#4
6115 {
6116   #2 \l__clist_internal_clist {#4}
6117   #1 #3 \l__clist_internal_clist #3
6118 }
6119 \cs_generate_variant:Nn \clist_put_left:Nn { NV , No , Nx }
6120 \cs_generate_variant:Nn \clist_put_left:Nn { c , cV , co , cx }
6121 \cs_generate_variant:Nn \clist_gput_left:Nn { NV , No , Nx }
6122 \cs_generate_variant:Nn \clist_gput_left:Nn { c , cV , co , cx }

```

(End definition for `\clist_put_left:Nn`, `\clist_gput_left:Nn`, and `\__clist_put_left:NNNn`. These functions are documented on page 99.)

```

6123 \cs_new_protected:Npn \clist_put_right:Nn
6124 { \__clist_put_right:NNNn \clist_concat:NNN \clist_set:Nn }
6125 \cs_new_protected:Npn \clist_gput_right:Nn
6126 { \__clist_put_right:NNNn \clist_gconcat:NNN \clist_set:Nn }
6127 \cs_new_protected:Npn \__clist_put_right:NNNn #1#2#3#4
6128 {
6129   #2 \l__clist_internal_clist {#4}
6130   #1 #3 #3 \l__clist_internal_clist
6131 }
6132 \cs_generate_variant:Nn \clist_put_right:Nn { NV , No , Nx }
6133 \cs_generate_variant:Nn \clist_put_right:Nn { c , cV , co , cx }
6134 \cs_generate_variant:Nn \clist_gput_right:Nn { NV , No , Nx }
6135 \cs_generate_variant:Nn \clist_gput_right:Nn { c , cV , co , cx }

```

(End definition for `\clist_put_right:Nn`, `\clist_gput_right:Nn`, and `\__clist_put_right:NNNn`. These functions are documented on page 100.)

### 13.4 Comma lists as stacks

```

\clist_get:Nn
\clist_get:cn
__clist_get:wN

```

Getting an item from the left of a comma list is pretty easy: just trim off the first item using the comma.

```

6136 \cs_new_protected:Npn \clist_get:Nn #1#2
6137 {

```

```

6138     \if_meaning:w #1 \c_empty_clist
6139     \tl_set:Nn #2 { \q_no_value }
6140     \else:
6141     \exp_after:wN \__clist_get:wN #1 , \q_stop #2
6142     \fi:
6143   }
6144 \cs_new_protected:Npn \__clist_get:wN #1 , #2 \q_stop #3
6145 { \tl_set:Nn #3 {#1} }
6146 \cs_generate_variant:Nn \clist_get:NN { c }

```

(End definition for `\clist_get:NN` and `\__clist_get:wN`. These functions are documented on page 104.)

```

\clist_pop:NN An empty clist leads to \q_no_value, otherwise grab until the first comma and assign
\clist_pop:cN to the variable. The second argument of \__clist_pop:wwNNN is a comma list ending
\clist_gpop:NN in a comma and \q_mark, unless the original clist contained exactly one item: then the
\clist_gpop:cN argument is just \q_mark. The next auxiliary picks either \exp_not:n or \use_none:n
\__clist_pop:NNN as #2, ensuring that the result can safely be an empty comma list.
\__clist_pop:wwNNN
\__clist_pop:wN
6147 \cs_new_protected:Npn \clist_pop:NN
6148 { \__clist_pop:NNN \tl_set:Nx }
6149 \cs_new_protected:Npn \clist_gpop:NN
6150 { \__clist_pop:NNN \tl_gset:Nx }
6151 \cs_new_protected:Npn \__clist_pop:NNN #1#2#3
6152 {
6153   \if_meaning:w #2 \c_empty_clist
6154   \tl_set:Nn #3 { \q_no_value }
6155   \else:
6156   \exp_after:wN \__clist_pop:wwNNN #2 , \q_mark \q_stop #1#2#3
6157   \fi:
6158 }
6159 \cs_new_protected:Npn \__clist_pop:wwNNN #1 , #2 \q_stop #3#4#5
6160 {
6161   \tl_set:Nn #5 {#1}
6162   #3 #4
6163   {
6164     \__clist_pop:wN \prg_do_nothing:
6165     #2 \exp_not:o
6166     , \q_mark \use_none:n
6167     \q_stop
6168   }
6169 }
6170 \cs_new:Npn \__clist_pop:wN #1 , \q_mark #2 #3 \q_stop { #2 {#1} }
6171 \cs_generate_variant:Nn \clist_pop:NN { c }
6172 \cs_generate_variant:Nn \clist_gpop:NN { c }

```

(End definition for `\clist_pop:NN` and others. These functions are documented on page 104.)

```

\clist_get:NNTF The same, as branching code: very similar to the above.
\clist_get:cNTF
\clist_pop:NNTF
\clist_pop:cNTF
\clist_gpop:NNTF
\clist_gpop:cNTF
\__clist_pop:TF:NNN
6173 \prg_new_protected_conditional:Npnn \clist_get:NN #1#2 { T , F , TF }
6174 {
6175   \if_meaning:w #1 \c_empty_clist
6176   \prg_return_false:
6177   \else:
6178   \exp_after:wN \__clist_get:wN #1 , \q_stop #2
6179   \prg_return_true:

```

```

6180     \fi:
6181   }
6182   \cs_generate_variant:Nn \clist_get:NNT { c }
6183   \cs_generate_variant:Nn \clist_get:NNF { c }
6184   \cs_generate_variant:Nn \clist_get:NNTF { c }
6185   \prg_new_protected_conditional:Npnn \clist_pop:NN #1#2 { T , F , TF }
6186   { \__clist_pop_TF:NNN \tl_set:Nx #1 #2 }
6187   \prg_new_protected_conditional:Npnn \clist_gpop:NN #1#2 { T , F , TF }
6188   { \__clist_pop_TF:NNN \tl_gset:Nx #1 #2 }
6189   \cs_new_protected:Npn \__clist_pop_TF:NNN #1#2#3
6190   {
6191     \if_meaning:w #2 \c_empty_clist
6192     \prg_return_false:
6193   \else:
6194     \exp_after:wN \__clist_pop:wwNNN #2 , \q_mark \q_stop #1#2#3
6195     \prg_return_true:
6196   \fi:
6197 }
6198 \cs_generate_variant:Nn \clist_pop:NNT { c }
6199 \cs_generate_variant:Nn \clist_pop:NNF { c }
6200 \cs_generate_variant:Nn \clist_pop:NNTF { c }
6201 \cs_generate_variant:Nn \clist_gpop:NNT { c }
6202 \cs_generate_variant:Nn \clist_gpop:NNF { c }
6203 \cs_generate_variant:Nn \clist_gpop:NNTF { c }

```

(End definition for `\clist_get:NNTF` and others. These functions are documented on page 104.)

**`\clist_push:Nn`** Pushing to a comma list is the same as adding on the left.

<code>\clist_push:Nv</code>	6204 <code>\cs_new_eq:NN \clist_push:Nn \clist_put_left:Nn</code>
<code>\clist_push:No</code>	6205 <code>\cs_new_eq:NN \clist_push:Nv \clist_put_left:Nv</code>
<code>\clist_push:Nx</code>	6206 <code>\cs_new_eq:NN \clist_push:No \clist_put_left:No</code>
<code>\clist_push:cn</code>	6207 <code>\cs_new_eq:NN \clist_push:Nx \clist_put_left:Nx</code>
<code>\clist_push:cV</code>	6208 <code>\cs_new_eq:NN \clist_push:cn \clist_put_left:cn</code>
<code>\clist_push:co</code>	6209 <code>\cs_new_eq:NN \clist_push:cV \clist_put_left:cV</code>
<code>\clist_push:cx</code>	6210 <code>\cs_new_eq:NN \clist_push:co \clist_put_left:co</code>
<b><code>\clist_gpush:Nn</code></b>	6211 <code>\cs_new_eq:NN \clist_push:cx \clist_put_left:cx</code>
<code>\clist_gpush:Nv</code>	6212 <code>\cs_new_eq:NN \clist_gpush:Nn \clist_gput_left:Nn</code>
<code>\clist_gpush:No</code>	6213 <code>\cs_new_eq:NN \clist_gpush:Nv \clist_gput_left:Nv</code>
<code>\clist_gpush:Nx</code>	6214 <code>\cs_new_eq:NN \clist_gpush:No \clist_gput_left:No</code>
<code>\clist_gpush:cn</code>	6215 <code>\cs_new_eq:NN \clist_gpush:Nx \clist_gput_left:Nx</code>
<code>\clist_gpush:cV</code>	6216 <code>\cs_new_eq:NN \clist_gpush:cn \clist_gput_left:cn</code>
<code>\clist_gpush:co</code>	6217 <code>\cs_new_eq:NN \clist_gpush:cV \clist_gput_left:cV</code>
<code>\clist_gpush:cx</code>	6218 <code>\cs_new_eq:NN \clist_gpush:co \clist_gput_left:co</code>
	6219 <code>\cs_new_eq:NN \clist_gpush:cx \clist_gput_left:cx</code>

(End definition for `\clist_push:Nn` and `\clist_gpush:Nn`. These functions are documented on page 105.)

## 13.5 Modifying comma lists

`\l__clist_internal_remove_clist` An internal comma list for the removal routines.

```
6220 \clist_new:N \l__clist_internal_remove_clist
```

(End definition for `\l__clist_internal_remove_clist`.)

`\clist_remove_duplicates:N` Removing duplicates means making a new list then copying it.

```

\clist_remove_duplicates:c 6221 \cs_new_protected:Npn \clist_remove_duplicates:N
\clist_gremove_duplicates:N 6222 { \__clist_remove_duplicates:NN \clist_set_eq:NN }
\clist_gremove_duplicates:c 6223 \cs_new_protected:Npn \clist_gremove_duplicates:N
        \__clist_remove_duplicates:NN 6224 { \__clist_remove_duplicates:NN \clist_gset_eq:NN }
        \cs_new_protected:Npn \__clist_remove_duplicates:NN #1#2 6225
        {
        6226
        6227 \clist_clear:N \l__clist_internal_remove_clist
        6228 \clist_map_inline:Nn #2
        6229 {
        6230 \clist_if_in:NnF \l__clist_internal_remove_clist {##1}
        6231 { \clist_put_right:Nn \l__clist_internal_remove_clist {##1} }
        6232 }
        6233 #1 #2 \l__clist_internal_remove_clist
        6234 }
        6235 \cs_generate_variant:Nn \clist_remove_duplicates:N { c }
        6236 \cs_generate_variant:Nn \clist_gremove_duplicates:N { c }

```

(End definition for `\clist_remove_duplicates:N`, `\clist_gremove_duplicates:N`, and `\__clist_remove_duplicates:NN`. These functions are documented on page 100.)

`\clist_remove_all:Nn` The method used here is very similar to `\tl_replace_all:Nnn`. Build a function delimited by the `<item>` that should be removed, surrounded with commas, and call that function followed by the expanded comma list, and another copy of the `<item>`. The loop is controlled by the argument grabbed by `\__clist_remove_all:w`: when the item was found, the `\q_mark` delimiter used is the one inserted by `\__clist_tmp:w`, and `\use_none_delimit_by_q_stop:w` is deleted. At the end, the final `<item>` is grabbed, and the argument of `\__clist_tmp:w` contains `\q_mark`: in that case, `\__clist_remove_all:w` removes the second `\q_mark` (inserted by `\__clist_tmp:w`), and lets `\use_none_delimit_by_q_stop:w` act.

No brace is lost because items are always grabbed with a leading comma. The result of the first assignment has an extra leading comma, which we remove in a second assignment. Two exceptions: if the clist lost all of its elements, the result is empty, and we shouldn't remove anything; if the clist started up empty, the first step happens to turn it into a single comma, and the second step removes it.

```

6237 \cs_new_protected:Npn \clist_remove_all:Nn
6238 { \__clist_remove_all:NNn \tl_set:Nx }
6239 \cs_new_protected:Npn \clist_gremove_all:Nn
6240 { \__clist_remove_all:NNn \tl_gset:Nx }
6241 \cs_new_protected:Npn \__clist_remove_all:NNn #1#2#3
6242 {
6243 \cs_set:Npn \__clist_tmp:w ##1 , #3 ,
6244 {
6245 ##1
6246 , \q_mark , \use_none_delimit_by_q_stop:w ,
6247 \__clist_remove_all:
6248 }
6249 #1 #2
6250 {
6251 \exp_after:wN \__clist_remove_all:
6252 #2 , \q_mark , #3 , \q_stop
6253 }
6254 \clist_if_empty:NF #2

```

```

6255     {
6256         #1 #2
6257         {
6258             \exp_args:No \exp_not:o
6259             { \exp_after:wN \use_none:n #2 }
6260         }
6261     }
6262 }
6263 \cs_new:Npn \__clist_remove_all:
6264 { \exp_after:wN \__clist_remove_all:w \__clist_tmp:w , }
6265 \cs_new:Npn \__clist_remove_all:w #1 , \q_mark , #2 , { \exp_not:n {#1} }
6266 \cs_generate_variant:Nn \clist_remove_all:Nn { c }
6267 \cs_generate_variant:Nn \clist_gremove_all:Nn { c }

```

(End definition for `\clist_remove_all:Nn` and others. These functions are documented on page 100.)

**`\clist_reverse:N`** Use `\clist_reverse:n` in an x-expanding assignment. The extra work that `\clist_reverse:n` does to preserve braces and spaces would not be needed for the well-controlled case of N-type comma lists, but the slow-down is not too bad.

**`\clist_reverse:c`**

**`\clist_greverse:N`**

**`\clist_greverse:c`**

```

6268 \cs_new_protected:Npn \clist_reverse:N #1
6269 { \tl_set:Nx #1 { \exp_args:No \clist_reverse:n {#1} } }
6270 \cs_new_protected:Npn \clist_greverse:N #1
6271 { \tl_gset:Nx #1 { \exp_args:No \clist_reverse:n {#1} } }
6272 \cs_generate_variant:Nn \clist_reverse:N { c }
6273 \cs_generate_variant:Nn \clist_greverse:N { c }

```

(End definition for `\clist_reverse:N` and `\clist_greverse:N`. These functions are documented on page 100.)

**`\clist_reverse:n`** The reversed token list is built one item at a time, and stored between `\q_stop` and `\q_mark`, in the form of ? followed by zero or more instances of “ $\langle item \rangle$ ,”. We start from a comma list “ $\langle item_1 \rangle, \dots, \langle item_n \rangle$ ”. During the loop, the auxiliary `\__clist_reverse:wwNww` receives “ $\langle item_i \rangle$ ” as #1, “ $\langle item_{i+1} \rangle, \dots, \langle item_n \rangle$ ” as #2, `\__clist_reverse:wwNww` as #3, what remains until `\q_stop` as #4, and “ $\langle item_{i-1} \rangle, \dots, \langle item_1 \rangle$ ,” as #5. The auxiliary moves #1 just before #5, with a comma, and calls itself (#3). After the last item is moved, `\__clist_reverse:wwNww` receives “`\q_mark \__clist_reverse:wwNww !`” as its argument #1, thus `\__clist_reverse_end:ww` as its argument #3. This second auxiliary cleans up until the marker !, removes the trailing comma (introduced when the first item was moved after `\q_stop`), and leaves its argument #1 within `\exp_not:n`. There is also a need to remove a leading comma, hence `\exp_not:o` and `\use_none:n`.

```

6274 \cs_new:Npn \clist_reverse:n #1
6275 {
6276     \__clist_reverse:wwNww ? #1 ,
6277     \q_mark \__clist_reverse:wwNww ! ,
6278     \q_mark \__clist_reverse_end:ww
6279     \q_stop ? \q_mark
6280 }
6281 \cs_new:Npn \__clist_reverse:wwNww
6282 #1 , #2 \q_mark #3 #4 \q_stop ? #5 \q_mark
6283 { #3 ? #2 \q_mark #3 #4 \q_stop #1 , #5 \q_mark }
6284 \cs_new:Npn \__clist_reverse_end:ww #1 ! #2 , \q_mark
6285 { \exp_not:o { \use_none:n #2 } }

```

(End definition for `\clist_reverse:n`, `\_clist_reverse:wwNww`, and `\_clist_reverse_end:ww`. These functions are documented on page 100.)

`\clist_sort:Nn` Implemented in `l3sort`.

`\clist_sort:cn`

`\clist_gsort:Nn` (End definition for `\clist_sort:Nn` and `\clist_gsort:Nn`. These functions are documented on page 101.)

`\clist_gsort:cn`

## 13.6 Comma list conditionals

`\clist_if_empty_p:N` Simple copies from the token list variable material.

`\clist_if_empty_p:c` 6286 `\prg_new_eq_conditional:Nn \clist_if_empty:N \tl_if_empty:N`

`\clist_if_empty:NTF` 6287 `{ p , T , F , TF }`

`\clist_if_empty:cTF` 6288 `\prg_new_eq_conditional:Nn \clist_if_empty:c \tl_if_empty:c`

6289 `{ p , T , F , TF }`

(End definition for `\clist_if_empty:NTF`. This function is documented on page 101.)

`\clist_if_empty_p:n` As usual, we insert a token (here `?`) before grabbing any argument: this avoids losing braces. The argument of `\tl_if_empty:oTF` is empty if `#1` is `?` followed by blank spaces (besides, this particular variant of the emptiness test is optimized). If the item of the comma list is blank, grab the next one. As soon as one item is non-blank, exit: the second auxiliary grabs `\prg_return_false:` as `#2`, unless every item in the comma list was blank and the loop actually got broken by the trailing `\q_mark \prg_return_false:` item.

`\clist_if_empty:nTF`  
`\_clist_if_empty_n:w`  
`\_clist_if_empty_n:wNw`

```
6290 \prg_new_conditional:Npnn \clist_if_empty:n #1 { p , T , F , TF }
6291 {
6292   \_clist_if_empty_n:w ? #1
6293   , \q_mark \prg_return_false:
6294   , \q_mark \prg_return_true:
6295   \q_stop
6296 }
6297 \cs_new:Npn \_clist_if_empty_n:w #1 ,
6298 {
6299   \tl_if_empty:oTF { \use_none:nn #1 ? }
6300   { \_clist_if_empty_n:w ? }
6301   { \_clist_if_empty_n:wNw }
6302 }
6303 \cs_new:Npn \_clist_if_empty_n:wNw #1 \q_mark #2#3 \q_stop {#2}
```

(End definition for `\clist_if_empty:nTF`, `\_clist_if_empty_n:w`, and `\_clist_if_empty_n:wNw`. These functions are documented on page 101.)

`\clist_if_in:NnTF` See description of the `\tl_if_in:Nn` function for details. We simply surround the comma list, and the item, with commas.

`\clist_if_in:NVTF`

`\clist_if_in:NoTF`

`\clist_if_in:cnTF`

`\clist_if_in:cVTF`

`\clist_if_in:coTF`

`\clist_if_in:nnTF`

`\clist_if_in:nVTF`

`\clist_if_in:noTF`

`\_clist_if_in_return:nn`

```
6304 \prg_new_protected_conditional:Npnn \clist_if_in:Nn #1#2 { T , F , TF }
6305 {
6306   \exp_args:No \_clist_if_in_return:nn #1 {#2}
6307 }
6308 \prg_new_protected_conditional:Npnn \clist_if_in:nn #1#2 { T , F , TF }
6309 {
6310   \clist_set:Nn \l__clist_internal_clist {#1}
6311   \exp_args:No \_clist_if_in_return:nn \l__clist_internal_clist {#2}
6312 }
6313 \cs_new_protected:Npn \_clist_if_in_return:nn #1#2
```

```

6314 {
6315   \cs_set:Npn \__clist_tmp:w ##1 ,#2, { }
6316   \tl_if_empty:oTF
6317     { \__clist_tmp:w ,#1, {} {} ,#2, }
6318     { \prg_return_false: } { \prg_return_true: }
6319 }
6320 \cs_generate_variant:Nn \clist_if_in:NnT { NV , No }
6321 \cs_generate_variant:Nn \clist_if_in:NnT { c , cV , co }
6322 \cs_generate_variant:Nn \clist_if_in:NnF { NV , No }
6323 \cs_generate_variant:Nn \clist_if_in:NnF { c , cV , co }
6324 \cs_generate_variant:Nn \clist_if_in:NnTF { NV , No }
6325 \cs_generate_variant:Nn \clist_if_in:NnTF { c , cV , co }
6326 \cs_generate_variant:Nn \clist_if_in:nnT { nV , no }
6327 \cs_generate_variant:Nn \clist_if_in:nnF { nV , no }
6328 \cs_generate_variant:Nn \clist_if_in:nnTF { nV , no }

```

(End definition for `\clist_if_in:NnTF`, `\clist_if_in:nnTF`, and `\__clist_if_in_return:nn`. These functions are documented on page 101.)

### 13.7 Mapping to comma lists

`\clist_map_function:NN` If the variable is empty, the mapping is skipped (otherwise, that comma-list would be seen as consisting of one empty item). Then loop over the comma-list, grabbing one comma-delimited item at a time. The end is marked by `\q_recursion_tail`. The auxiliary function `\__clist_map_function:Nw` is used directly in `\clist_map_inline:Nn`. Change with care.

```

6329 \cs_new:Npn \clist_map_function:NN #1#2
6330 {
6331   \clist_if_empty:NF #1
6332   {
6333     \exp_last_unbraced:NNo \__clist_map_function:Nw #2 #1
6334     , \q_recursion_tail ,
6335     \__prg_break_point:Nn \clist_map_break: { }
6336   }
6337 }
6338 \cs_new:Npn \__clist_map_function:Nw #1#2 ,
6339 {
6340   \__quark_if_recursion_tail_break:nN {#2} \clist_map_break:
6341   #1 {#2}
6342   \__clist_map_function:Nw #1
6343 }
6344 \cs_generate_variant:Nn \clist_map_function:NN { c }

```

(End definition for `\clist_map_function:NN` and `\__clist_map_function:Nw`. These functions are documented on page 102.)

`\clist_map_function:nN` The n-type mapping function is a bit more awkward, since spaces must be trimmed from each item. Space trimming is again based on `\__clist_trim_spaces_generic:nw`. The auxiliary `\__clist_map_function_n:Nn` receives as arguments the function, and the result of removing leading and trailing spaces from the item which lies until the next comma. Empty items are ignored, then one level of braces is removed by `\__clist_map_unbrace:Nw`.

```

6345 \cs_new:Npn \clist_map_function:nN #1#2
6346 {

```

```

6347     \__clist_trim_spaces_generic:nw { \__clist_map_function_n:Nn #2 }
6348     \q_mark #1, \q_recursion_tail,
6349     \__prg_break_point:Nn \clist_map_break: { }
6350   }
6351 \cs_new:Npn \__clist_map_function_n:Nn #1 #2
6352 {
6353   \__quark_if_recursion_tail_break:nN {#2} \clist_map_break:
6354   \tl_if_empty:nF {#2} { \__clist_map_unbrace:Nw #1 #2, }
6355   \__clist_trim_spaces_generic:nw { \__clist_map_function_n:Nn #1 }
6356   \q_mark
6357 }
6358 \cs_new:Npn \__clist_map_unbrace:Nw #1 #2, { #1 {#2} }

```

(End definition for `\clist_map_function:nN`, `\__clist_map_function_n:Nn`, and `\__clist_map_unbrace:Nw`. These functions are documented on page 102.)

`\clist_map_inline:Nn` Inline mapping is done by creating a suitable function “on the fly”: this is done globally  
`\clist_map_inline:cn` to avoid any issues with  $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ ’s groups. We use a different function for each level of  
`\clist_map_inline:nn` nesting.

Since the mapping is non-expandable, we can perform the space-trimming needed by the `n` version simply by storing the comma-list in a variable. We don’t need a different comma-list for each nesting level: the comma-list is expanded before the mapping starts.

```

6359 \cs_new_protected:Npn \clist_map_inline:Nn #1#2
6360 {
6361   \clist_if_empty:NF #1
6362   {
6363     \int_gincr:N \g__prg_map_int
6364     \cs_gset_protected:cpn
6365       { \__prg_map_ \int_use:N \g__prg_map_int :w } ##1 {#2}
6366     \exp_last_unbraced:Nco \__clist_map_function:Nw
6367       { \__prg_map_ \int_use:N \g__prg_map_int :w }
6368       #1 , \q_recursion_tail ,
6369       \__prg_break_point:Nn \clist_map_break:
6370       { \int_gdecr:N \g__prg_map_int }
6371   }
6372 }
6373 \cs_new_protected:Npn \clist_map_inline:nn #1
6374 {
6375   \clist_set:Nn \l__clist_internal_clist {#1}
6376   \clist_map_inline:Nn \l__clist_internal_clist
6377 }
6378 \cs_generate_variant:Nn \clist_map_inline:Nn { c }

```

(End definition for `\clist_map_inline:Nn` and `\clist_map_inline:nn`. These functions are documented on page 102.)

`\clist_map_variable:NNn` As for other comma-list mappings, filter out the case of an empty list. Same approach  
`\clist_map_variable:cNn` as `\clist_map_function:Nn`, additionally we store each item in the given variable. As  
`\clist_map_variable:nNn` for inline mappings, space trimming for the `n` variant is done by storing the comma list  
`\__clist_map_variable:Nnw` in a variable.

```

6379 \cs_new_protected:Npn \clist_map_variable:NNn #1#2#3
6380 {
6381   \clist_if_empty:NF #1
6382   {

```



```

6383     \exp_args:Nno \use:nn
6384     { \__clist_map_variable:Nnw #2 {#3} }
6385     #1
6386     , \q_recursion_tail , \q_recursion_stop
6387     \__prg_break_point:Nn \clist_map_break: { }
6388   }
6389 }
6390 \cs_new_protected:Npn \clist_map_variable:nNn #1
6391 {
6392   \clist_set:Nn \l__clist_internal_clist {#1}
6393   \clist_map_variable:NNn \l__clist_internal_clist
6394 }
6395 \cs_new_protected:Npn \__clist_map_variable:Nnw #1#2#3,
6396 {
6397   \tl_set:Nn #1 {#3}
6398   \quark_if_recursion_tail_stop:N #1
6399   \use:n {#2}
6400   \__clist_map_variable:Nnw #1 {#2}
6401 }
6402 \cs_generate_variant:Nn \clist_map_variable:NNn { c }

```

(End definition for `\clist_map_variable:NNn`, `\clist_map_variable:nNn`, and `\__clist_map_variable:Nnw`. These functions are documented on page 102.)

**`\clist_map_break:`** The break statements use the general `\__prg_map_break:Nn` mechanism.  
**`\clist_map_break:n`**

```

6403 \cs_new:Npn \clist_map_break:
6404 { \__prg_map_break:Nn \clist_map_break: { } }
6405 \cs_new:Npn \clist_map_break:n
6406 { \__prg_map_break:Nn \clist_map_break: }

```

(End definition for `\clist_map_break:` and `\clist_map_break:n`. These functions are documented on page 102.)

**`\clist_count:N`** Counting the items in a comma list is done using the same approach as for other token  
**`\clist_count:c`** count functions: turn each entry into a +1 then use integer evaluation to actually do the  
**`\clist_count:n`** mathematics. In the case of an n-type comma-list, we could of course use `\clist_map_`  
**`\__clist_count:n`** **`function:nN`**, but that is very slow, because it carefully removes spaces. Instead, we loop  
**`\__clist_count:w`** manually, and skip blank items (but not {}, hence the extra spaces).

```

6407 \cs_new:Npn \clist_count:N #1
6408 {
6409   \int_eval:n
6410   {
6411     0
6412     \clist_map_function:NN #1 \__clist_count:n
6413   }
6414 }
6415 \cs_generate_variant:Nn \clist_count:N { c }
6416 \cs_new:Npx \clist_count:n #1
6417 {
6418   \exp_not:N \int_eval:n
6419   {
6420     0
6421     \exp_not:N \__clist_count:w \c_space_tl
6422     #1 \exp_not:n { , \q_recursion_tail , \q_recursion_stop }

```

```

6423     }
6424   }
6425   \cs_new:Npn \__clist_count:n #1 { + 1 }
6426   \cs_new:Npx \__clist_count:w #1 ,
6427   {
6428     \exp_not:n { \exp_args:Nf \quark_if_recursion_tail_stop:n } {#1}
6429     \exp_not:N \tl_if_blank:nF {#1} { + 1 }
6430     \exp_not:N \__clist_count:w \c_space_tl
6431   }

```

(End definition for `\clist_count:N` and others. These functions are documented on page 103.)

## 13.8 Using comma lists

`\clist_use:Nmn` First check that the variable exists. Then count the items in the comma list. If it has none, output nothing. If it has one item, output that item, brace stripped (note that space-trimming has already been done when the comma list was assigned). If it has two, place the *<separator between two>* in the middle.

Otherwise, `\__clist_use:nwwwnwn` takes the following arguments; 1: a *<separator>*, 2, 3, 4: three items from the comma list (or quarks), 5: the rest of the comma list, 6: a *<continuation>* function (`use_ii` or `use_iii` with its *<separator>* argument), 7: junk, and 8: the temporary result, which is built in a brace group following `\q_stop`. The *<separator>* and the first of the three items are placed in the result, then we use the *<continuation>*, placing the remaining two items after it. When we begin this loop, the three items really belong to the comma list, the first `\q_mark` is taken as a delimiter to the `use_ii` function, and the continuation is `use_ii` itself. When we reach the last two items of the original token list, `\q_mark` is taken as a third item, and now the second `\q_mark` serves as a delimiter to `use_ii`, switching to the other *<continuation>*, `use_iii`, which uses the *<separator between final two>*.

```

6432 \cs_new:Npn \clist_use:Nmn #1#2#3#4
6433 {
6434   \clist_if_exist:NTF #1
6435   {
6436     \int_case:nnF { \clist_count:N #1 }
6437     {
6438       { 0 } { }
6439       { 1 } { \exp_after:wN \__clist_use:wnn #1 , , { } }
6440       { 2 } { \exp_after:wN \__clist_use:wnn #1 , {#2} }
6441     }
6442     {
6443       \exp_after:wN \__clist_use:nwwwnwn
6444       \exp_after:wN { \exp_after:wN } #1 ,
6445       \q_mark , { \__clist_use:nwwwnwn {#3} }
6446       \q_mark , { \__clist_use:wnn {#4} }
6447       \q_stop { }
6448     }
6449   }
6450   {
6451     \_msg_kernel_expandable_error:nnn
6452     { kernel } { bad-variable } {#1}
6453   }
6454 }
6455 \cs_generate_variant:Nn \clist_use:Nmn { c }

```

```

6456 \cs_new:Npn \__clist_use:wnn #1 , #2 , #3 { \exp_not:n { #1 #3 #2 } }
6457 \cs_new:Npn \__clist_use:nwwwnnwn
6458   #1#2 , #3 , #4 , #5 \q_mark , #6#7 \q_stop #8
6459   { #6 {#3} , {#4} , #5 \q_mark , {#6} #7 \q_stop { #8 #1 #2 } }
6460 \cs_new:Npn \__clist_use:nwnn #1#2 , #3 \q_stop #4
6461   { \exp_not:n { #4 #1 #2 } }
6462 \cs_new:Npn \clist_use:Nn #1#2
6463   { \clist_use:Nnnn #1 {#2} {#2} {#2} }
6464 \cs_generate_variant:Nn \clist_use:Nn { c }

```

(End definition for `\clist_use:Nnnn` and others. These functions are documented on page 103.)

### 13.9 Using a single item

`\clist_item:Nn` To avoid needing to test the end of the list at each step, we first compute the  $\langle length \rangle$  of the list. If the item number is 0, less than  $-\langle length \rangle$ , or more than  $\langle length \rangle$ , the result is empty. If it is negative, but not less than  $-\langle length \rangle$ , add  $\langle length \rangle + 1$  to the item number before performing the loop. The loop itself is very simple, return the item if the counter reached 1, otherwise, decrease the counter and repeat.

```

\clist_item:cn
\__clist_item:nnnN
\__clist_item:ffoN
\__clist_item:ffnN
\__clist_item_N_loop:nw
6465 \cs_new:Npn \clist_item:Nn #1#2
6466   {
6467     \__clist_item:ffoN
6468     { \clist_count:N #1 }
6469     { \int_eval:n {#2} }
6470     #1
6471     \__clist_item_N_loop:nw
6472   }
6473 \cs_new:Npn \__clist_item:nnnN #1#2#3#4
6474   {
6475     \int_compare:nNnTF {#2} < 0
6476     {
6477       \int_compare:nNnTF {#2} < { - #1 }
6478       { \use_none_delimit_by_q_stop:w }
6479       { \exp_args:Nf #4 { \int_eval:n { #2 + 1 + #1 } } }
6480     }
6481     {
6482       \int_compare:nNnTF {#2} > {#1}
6483       { \use_none_delimit_by_q_stop:w }
6484       { #4 {#2} }
6485     }
6486     { } , #3 , \q_stop
6487   }
6488 \cs_generate_variant:Nn \__clist_item:nnnN { ffo, ff }
6489 \cs_new:Npn \__clist_item_N_loop:nw #1 #2,
6490   {
6491     \int_compare:nNnTF {#1} = 0
6492     { \use_i_delimit_by_q_stop:nw { \exp_not:n {#2} } }
6493     { \exp_args:Nf \__clist_item_N_loop:nw { \int_eval:n { #1 - 1 } } }
6494   }
6495 \cs_generate_variant:Nn \clist_item:Nn { c }

```

(End definition for `\clist_item:Nn`, `\__clist_item:nnnN`, and `\__clist_item_N_loop:nw`. These functions are documented on page 105.)

`\clist_item:nn` This starts in the same way as `\clist_item:Nn` by counting the items of the comma list. The final item should be space-trimmed before being brace-stripped, hence we insert a couple of odd-looking `\prg_do_nothing:` to avoid losing braces. Blank items are ignored.

`\__clist_item_n:nw`

`\__clist_item_n_loop:nw`

`\__clist_item_n_end:n`

`\__clist_item_n_strip:w`

```

6496 \cs_new:Npn \clist_item:nn #1#2
6497 {
6498   \__clist_item:ffnN
6499   { \clist_count:n {#1} }
6500   { \int_eval:n {#2} }
6501   {#1}
6502   \__clist_item_n:nw
6503 }
6504 \cs_new:Npn \__clist_item_n:nw #1
6505 { \__clist_item_n_loop:nw {#1} \prg_do_nothing: }
6506 \cs_new:Npn \__clist_item_n_loop:nw #1 #2,
6507 {
6508   \exp_args:No \tl_if_blank:nTF {#2}
6509   { \__clist_item_n_loop:nw {#1} \prg_do_nothing: }
6510   {
6511     \int_compare:nNnTF {#1} = 0
6512     { \exp_args:No \__clist_item_n_end:n {#2} }
6513     {
6514       \exp_args:Nf \__clist_item_n_loop:nw
6515       { \int_eval:n { #1 - 1 } }
6516       \prg_do_nothing:
6517     }
6518   }
6519 }
6520 \cs_new:Npn \__clist_item_n_end:n #1 #2 \q_stop
6521 {
6522   \__tl_trim_spaces:nn { \q_mark #1 }
6523   { \exp_last_unbraced:No \__clist_item_n_strip:w } ,
6524 }
6525 \cs_new:Npn \__clist_item_n_strip:w #1 , { \exp_not:n {#1} }

```

(End definition for `\clist_item:nn` and others. These functions are documented on page 105.)

## 13.10 Viewing comma lists

`\clist_show:N` Apply the general `\__msg_show_variable:NNNnn`. In the case of an n-type comma-list, we must do things by hand, using the same message `show-clist` as for an N-type comma-list but with an empty name (first argument).

`\clist_show:c`

`\clist_show:n`

```

6526 \cs_new_protected:Npn \clist_show:N #1
6527 {
6528   \__msg_show_variable:NNNnn #1
6529   \clist_if_exist:NTF \clist_if_empty:NTF { clist }
6530   { \clist_map_function:NN #1 \__msg_show_item:n }
6531 }
6532 \cs_new_protected:Npn \clist_show:n #1
6533 {
6534   \__msg_show_pre:nnxxxx { LaTeX / kernel } { show-clist }
6535   { } { \clist_if_empty:nF {#1} { ? } } { } { }
6536   \__msg_show_wrap:n
6537   { \clist_map_function:nN {#1} \__msg_show_item:n }

```

```

6538 }
6539 \cs_generate_variant:Nn \clist_show:N { c }

```

(End definition for `\clist_show:N` and `\clist_show:n`. These functions are documented on page 105.)

```

\clist_log:N Redirect output of \clist_show:N and \clist_show:n to the log.
\clist_log:c
\clist_log:n
6540 \cs_new_protected:Npn \clist_log:N
6541 { \__msg_log_next: \clist_show:N }
6542 \cs_new_protected:Npn \clist_log:n
6543 { \__msg_log_next: \clist_show:n }
6544 \cs_generate_variant:Nn \clist_log:N { c }

```

(End definition for `\clist_log:N` and `\clist_log:n`. These functions are documented on page 106.)

### 13.11 Scratch comma lists

```

\l_tmpa_clist Temporary comma list variables.
\l_tmpb_clist
\g_tmpa_clist
\g_tmpb_clist
6545 \clist_new:N \l_tmpa_clist
6546 \clist_new:N \l_tmpb_clist
6547 \clist_new:N \g_tmpa_clist
6548 \clist_new:N \g_tmpb_clist

```

(End definition for `\l_tmpa_clist` and others. These variables are documented on page 106.)

```

6549 </initex | package>

```

## 14 l3token implementation

```

6550 <*initex | package>
6551 <@@=char>

```

### 14.1 Manipulating and interrogating character tokens

```

\char_set_catcode:nn Simple wrappers around the primitives.
\char_value_catcode:n
\char_show_value_catcode:n
6552 \cs_new_protected:Npn \char_set_catcode:nn #1#2
6553 {
6554   \tex_catcode:D \__int_eval:w #1 \__int_eval_end:
6555   = \__int_eval:w #2 \__int_eval_end:
6556 }
6557 \cs_new:Npn \char_value_catcode:n #1
6558 { \tex_the:D \tex_catcode:D \__int_eval:w #1 \__int_eval_end: }
6559 \cs_new_protected:Npn \char_show_value_catcode:n #1
6560 { \__msg_show_wrap:n { > ~ \char_value_catcode:n {#1} } }

```

(End definition for `\char_set_catcode:nn`, `\char_value_catcode:n`, and `\char_show_value_catcode:n`. These functions are documented on page 109.)

```

\char_set_catcode_escape:N
\char_set_catcode_group_begin:N
\char_set_catcode_group_end:N
\char_set_catcode_math_toggle:N
\char_set_catcode_alignment:N
\char_set_catcode_end_line:N
\char_set_catcode_parameter:N
\char_set_catcode_math_superscript:N
\char_set_catcode_math_subscript:N
\char_set_catcode_ignore:N
\char_set_catcode_space:N
\char_set_catcode_letter:N
\char_set_catcode_other:N
\char_set_catcode_active:N
\char_set_catcode_comment:N
\char_set_catcode_invalid:N
6561 \cs_new_protected:Npn \char_set_catcode_escape:N #1
6562 { \char_set_catcode:nn { '#1 } { 0 } }
6563 \cs_new_protected:Npn \char_set_catcode_group_begin:N #1
6564 { \char_set_catcode:nn { '#1 } { 1 } }
6565 \cs_new_protected:Npn \char_set_catcode_group_end:N #1
6566 { \char_set_catcode:nn { '#1 } { 2 } }

```

```

6567 \cs_new_protected:Npn \char_set_catcode_math_toggle:N #1
6568   { \char_set_catcode:nn { '#1 } { 3 } }
6569 \cs_new_protected:Npn \char_set_catcode_alignment:N #1
6570   { \char_set_catcode:nn { '#1 } { 4 } }
6571 \cs_new_protected:Npn \char_set_catcode_end_line:N #1
6572   { \char_set_catcode:nn { '#1 } { 5 } }
6573 \cs_new_protected:Npn \char_set_catcode_parameter:N #1
6574   { \char_set_catcode:nn { '#1 } { 6 } }
6575 \cs_new_protected:Npn \char_set_catcode_math_superscript:N #1
6576   { \char_set_catcode:nn { '#1 } { 7 } }
6577 \cs_new_protected:Npn \char_set_catcode_math_subscript:N #1
6578   { \char_set_catcode:nn { '#1 } { 8 } }
6579 \cs_new_protected:Npn \char_set_catcode_ignore:N #1
6580   { \char_set_catcode:nn { '#1 } { 9 } }
6581 \cs_new_protected:Npn \char_set_catcode_space:N #1
6582   { \char_set_catcode:nn { '#1 } { 10 } }
6583 \cs_new_protected:Npn \char_set_catcode_letter:N #1
6584   { \char_set_catcode:nn { '#1 } { 11 } }
6585 \cs_new_protected:Npn \char_set_catcode_other:N #1
6586   { \char_set_catcode:nn { '#1 } { 12 } }
6587 \cs_new_protected:Npn \char_set_catcode_active:N #1
6588   { \char_set_catcode:nn { '#1 } { 13 } }
6589 \cs_new_protected:Npn \char_set_catcode_comment:N #1
6590   { \char_set_catcode:nn { '#1 } { 14 } }
6591 \cs_new_protected:Npn \char_set_catcode_invalid:N #1
6592   { \char_set_catcode:nn { '#1 } { 15 } }

```

(End definition for `\char_set_catcode_escape:N` and others. These functions are documented on page 108.)

```

\char_set_catcode_escape:n
  \char_set_catcode_group_begin:n
  \char_set_catcode_group_end:n
  \char_set_catcode_math_toggle:n
  \char_set_catcode_alignment:n
\char_set_catcode_end_line:n
  \char_set_catcode_parameter:n
  \char_set_catcode_math_superscript:n
  \char_set_catcode_math_subscript:n
\char_set_catcode_ignore:n
\char_set_catcode_space:n
\char_set_catcode_letter:n
\char_set_catcode_other:n
\char_set_catcode_active:n
\char_set_catcode_comment:n
\char_set_catcode_invalid:n
6593 \cs_new_protected:Npn \char_set_catcode_escape:n #1
6594   { \char_set_catcode:nn {#1} { 0 } }
6595 \cs_new_protected:Npn \char_set_catcode_group_begin:n #1
6596   { \char_set_catcode:nn {#1} { 1 } }
6597 \cs_new_protected:Npn \char_set_catcode_group_end:n #1
6598   { \char_set_catcode:nn {#1} { 2 } }
6599 \cs_new_protected:Npn \char_set_catcode_math_toggle:n #1
6600   { \char_set_catcode:nn {#1} { 3 } }
6601 \cs_new_protected:Npn \char_set_catcode_alignment:n #1
6602   { \char_set_catcode:nn {#1} { 4 } }
6603 \cs_new_protected:Npn \char_set_catcode_end_line:n #1
6604   { \char_set_catcode:nn {#1} { 5 } }
6605 \cs_new_protected:Npn \char_set_catcode_parameter:n #1
6606   { \char_set_catcode:nn {#1} { 6 } }
6607 \cs_new_protected:Npn \char_set_catcode_math_superscript:n #1
6608   { \char_set_catcode:nn {#1} { 7 } }
6609 \cs_new_protected:Npn \char_set_catcode_math_subscript:n #1
6610   { \char_set_catcode:nn {#1} { 8 } }
6611 \cs_new_protected:Npn \char_set_catcode_ignore:n #1
6612   { \char_set_catcode:nn {#1} { 9 } }
6613 \cs_new_protected:Npn \char_set_catcode_space:n #1
6614   { \char_set_catcode:nn {#1} { 10 } }
6615 \cs_new_protected:Npn \char_set_catcode_letter:n #1

```

```

6616 { \char_set_catcode:nn {#1} { 11 } }
6617 \cs_new_protected:Npn \char_set_catcode_other:n #1
6618 { \char_set_catcode:nn {#1} { 12 } }
6619 \cs_new_protected:Npn \char_set_catcode_active:n #1
6620 { \char_set_catcode:nn {#1} { 13 } }
6621 \cs_new_protected:Npn \char_set_catcode_comment:n #1
6622 { \char_set_catcode:nn {#1} { 14 } }
6623 \cs_new_protected:Npn \char_set_catcode_invalid:n #1
6624 { \char_set_catcode:nn {#1} { 15 } }

```

(End definition for `\char_set_catcode_escape:n` and others. These functions are documented on page 109.)

```

\char_set_mathcode:nn Pretty repetitive, but necessary!
\char_value_mathcode:n
\char_show_value_mathcode:n
\char_set_lccode:nn
\char_value_lccode:n
\char_show_value_lccode:n
\char_set_uccode:nn
\char_value_uccode:n
\char_show_value_uccode:n
\char_set_sfcode:nn
\char_value_sfcode:n
\char_show_value_sfcode:n
6625 \cs_new_protected:Npn \char_set_mathcode:nn #1#2
6626 {
6627   \tex_mathcode:D \__int_eval:w #1 \__int_eval_end:
6628   = \__int_eval:w #2 \__int_eval_end:
6629 }
6630 \cs_new:Npn \char_value_mathcode:n #1
6631 { \tex_the:D \tex_mathcode:D \__int_eval:w #1 \__int_eval_end: }
6632 \cs_new_protected:Npn \char_show_value_mathcode:n #1
6633 { \__msg_show_wrap:n { > ~ \char_value_mathcode:n {#1} } }
6634 \cs_new_protected:Npn \char_set_lccode:nn #1#2
6635 {
6636   \tex_lccode:D \__int_eval:w #1 \__int_eval_end:
6637   = \__int_eval:w #2 \__int_eval_end:
6638 }
6639 \cs_new:Npn \char_value_lccode:n #1
6640 { \tex_the:D \tex_lccode:D \__int_eval:w #1 \__int_eval_end: }
6641 \cs_new_protected:Npn \char_show_value_lccode:n #1
6642 { \__msg_show_wrap:n { > ~ \char_value_lccode:n {#1} } }
6643 \cs_new_protected:Npn \char_set_uccode:nn #1#2
6644 {
6645   \tex_uccode:D \__int_eval:w #1 \__int_eval_end:
6646   = \__int_eval:w #2 \__int_eval_end:
6647 }
6648 \cs_new:Npn \char_value_uccode:n #1
6649 { \tex_the:D \tex_uccode:D \__int_eval:w #1 \__int_eval_end: }
6650 \cs_new_protected:Npn \char_show_value_uccode:n #1
6651 { \__msg_show_wrap:n { > ~ \char_value_uccode:n {#1} } }
6652 \cs_new_protected:Npn \char_set_sfcode:nn #1#2
6653 {
6654   \tex_sfcode:D \__int_eval:w #1 \__int_eval_end:
6655   = \__int_eval:w #2 \__int_eval_end:
6656 }
6657 \cs_new:Npn \char_value_sfcode:n #1
6658 { \tex_the:D \tex_sfcode:D \__int_eval:w #1 \__int_eval_end: }
6659 \cs_new_protected:Npn \char_show_value_sfcode:n #1
6660 { \__msg_show_wrap:n { > ~ \char_value_sfcode:n {#1} } }

```

(End definition for `\char_set_mathcode:nn` and others. These functions are documented on page 110.)

`\l_char_active_seq` Two sequences for dealing with special characters. The first is characters which may be active, the second longer list is for “special” characters more generally. Both lists are

`\l_char_special_seq`

escaped so that for example bulk code assignments can be carried out. In both cases, the order is by ASCII character code (as is done in for example `\ExplSyntaxOn`).

```

6661 \seq_new:N \l_char_special_seq
6662 \seq_set_split:Nnn \l_char_special_seq { }
6663 { \ \ " \# \$ \% \& \ \ ^ \_ \{ \} \~ }
6664 \seq_new:N \l_char_active_seq
6665 \seq_set_split:Nnn \l_char_active_seq { }
6666 { \ \ " \$ \& \^ \_ \~ }

```

(End definition for `\l_char_active_seq` and `\l_char_special_seq`. These variables are documented on page 111.)

## 14.2 Creating character tokens

Four simple functions with very similar definitions, so set up using an auxiliary. These are similar to LuaTeX's `\letcharcode` primitive.

```

\char_set_active_eq:NN
\char_set_active_eq:Nc
\char_gset_active_eq:NN
\char_gset_active_eq:Nc
\char_set_active_eq:nN
\char_gset_active_eq:nN
\char_set_active_eq:nc
\char_gset_active_eq:nc
6667 \group_begin:
6668 \char_set_catcode_active:N \^^@
6669 \cs_set_protected:Npn \__char_tmp:nN #1#2
6670 {
6671   \cs_new_protected:cpn { #1 :nN } ##1
6672   {
6673     \group_begin:
6674     \char_set_lccode:nn { \^^@ } { ##1 }
6675     \tex_lowercase:D { \group_end: #2 ^^@ }
6676   }
6677   \cs_new_protected:cpx { #1 :NN } ##1
6678   { \exp_not:c { #1 : nN } { '##1 } }
6679 }
6680 \__char_tmp:nN { char_set_active_eq } \cs_set_eq:NN
6681 \__char_tmp:nN { char_gset_active_eq } \cs_gset_eq:NN
6682 \group_end:
6683 \cs_generate_variant:Nn \char_set_active_eq:NN { Nc }
6684 \cs_generate_variant:Nn \char_gset_active_eq:NN { Nc }
6685 \cs_generate_variant:Nn \char_set_active_eq:nN { nc }
6686 \cs_generate_variant:Nn \char_gset_active_eq:nN { nc }

```

(End definition for `\char_set_active_eq:NN` and others. These functions are documented on page 107.)

The aim here is to generate characters of (broadly) arbitrary category code. Where possible, that is done using engine support (XeTeX, LuaTeX). There are though various issues which are covered below. At the interface layer, turn the two arguments into integers up-front so this is only done once.

```

\char_generate:nn
\__char_generate:nn
\__char_generate_aux:nn
\__char_generate_aux:nnw
  \l__char_tmp_tl
  \c__char_max_int
\__char_generate_invalid_catcode:
6687 \cs_new:Npn \char_generate:nn #1#2
6688 {
6689   \exp:w \exp_after:wN \__char_generate_aux:w
6690   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
6691   \__int_value:w \__int_eval:w #2 ;
6692 }
6693 \cs_new:Npn \__char_generate:nn #1#2
6694 {
6695   \exp:w \exp_after:wN
6696   \__char_generate_aux:nnw \exp_after:wN
6697   { \__int_value:w \__int_eval:w #1 \exp_after:wN }

```



```

6698         {#2} \exp_end:
6699     }

```

Before doing any actual conversion, first some special case filtering. The `\Ucharcat` primitive cannot make active chars, so that is turned off here: if the primitive gets altered then the code is already in place for 8-bit engines and will kick in for LuaTeX too. Spaces are also banned here as LuaTeX emulation only makes normal (charcode 32 spaces. However, `^^@` is filtered out separately as that can't be done with macro emulation either, so is flagged up separately. That done, hand off to the engine-dependent part.

```

6700 \cs_new:Npn \__char_generate_aux:w #1 ; #2 ;
6701 {
6702     \if_int_compare:w #2 = 13 \exp_stop_f:
6703     \__msg_kernel_expandable_error:nn { kernel } { char-active }
6704 \else:
6705     \if_int_compare:w #2 = 10 \exp_stop_f:
6706     \if_int_compare:w #1 = 0 \exp_stop_f:
6707     \__msg_kernel_expandable_error:nn { kernel } { char-null-space }
6708 \else:
6709     \__msg_kernel_expandable_error:nn { kernel } { char-space }
6710 \fi:
6711 \else:
6712     \if_int_odd:w 0
6713     \if_int_compare:w #2 < 1 \exp_stop_f: 1 \fi:
6714     \if_int_compare:w #2 = 5 \exp_stop_f: 1 \fi:
6715     \if_int_compare:w #2 = 9 \exp_stop_f: 1 \fi:
6716     \if_int_compare:w #2 > 13 \exp_stop_f: 1 \fi: \exp_stop_f:
6717     \__msg_kernel_expandable_error:nn { kernel }
6718     { char-invalid-catcode }
6719 \else:
6720     \if_int_odd:w 0
6721     \if_int_compare:w #1 < 0 \exp_stop_f: 1 \fi:
6722     \if_int_compare:w #1 > \c__char_max_int 1 \fi: \exp_stop_f:
6723     \__msg_kernel_expandable_error:nn { kernel }
6724     { char-out-of-range }
6725 \else:
6726     \__char_generate_aux:nnw {#1} {#2}
6727 \fi:
6728 \fi:
6729 \fi:
6730 \fi:
6731 \exp_end:
6732 }
6733 \tl_new:N \l__char_tmp_tl

```

Engine-dependent definitions are now needed for the implementation. For LuaTeX and recent XeTeX releases there is engine-level support. They can do cases that macro emulation can't. All of those are filtered out here using a primitive-based boolean expression for speed. The final level is the basic definition at the engine level: the arguments here are integers so there is no need to worry about them too much.

```

6734 \group_begin:
6735 <*package>
6736     \char_set_catcode_active:N \^^L
6737     \cs_set:Npn ^^L { }
6738 </package>

```

```

6739 \char_set_catcode_other:n { 0 }
6740 \if_int_odd:w 0
6741   \cs_if_exist:NT \luatex_directlua:D { 1 }
6742   \cs_if_exist:NT \utex_charcat:D { 1 } \exp_stop_f:
6743   \int_const:Nn \c__char_max_int { 1114111 }
6744   \cs_if_exist:NTF \luatex_directlua:D
6745   {
6746     \cs_new:Npn \__char_generate_aux:nw #1#2#3 \exp_end:
6747     {
6748       #3
6749       \exp_after:wN \exp_end:
6750       \luatex_directlua:D { l3kernel.charcat(#1, #2) }
6751     }
6752   }
6753   {
6754     \cs_new:Npn \__char_generate_aux:nw #1#2#3 \exp_end:
6755     {
6756       #3
6757       \exp_after:wN \exp_end:
6758       \utex_charcat:D #1 ~ #2 ~
6759     }
6760   }
6761 \else:

```

For engines where `\Ucharcat` isn't available (or emulated) then we have to work in macros, and cover only the 8-bit range. The first stage is to build up a `tl` containing `^^@` with each category code that can be accessed in this way, with an error set up for the other cases. This is all done such that it can be quickly accessed using a `\if_case:w` low-level conditional. There are a few things to notice here. As `^^L` is `\outer` we need to locally set it to avoid a problem. To get open/close braces into the list, they are set up using `\if_false:` pairing and are then x-type expanded together into the desired form.

```

6762   \int_const:Nn \c__char_max_int { 255 }
6763   \tl_set:Nn \l__char_tmp_tl { \exp_not:N \or: }
6764   \char_set_catcode_group_begin:n { 0 } % {
6765   \tl_put_right:Nn \l__char_tmp_tl { ^^@ \if_false: } }
6766   \char_set_catcode_group_end:n { 0 }
6767   \tl_put_right:Nn \l__char_tmp_tl { { \fi: \exp_not:N \or: ^^@ } % }
6768   \tl_set:Nx \l__char_tmp_tl { \l__char_tmp_tl }
6769   \char_set_catcode_math_toggle:n { 0 }
6770   \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }

```

As  $\TeX$  is very unhappy if it finds an alignment character inside a primitive `\halign` even when skipping false branches, some precautions are required.  $\TeX$  is happy if the token is hidden inside `\unexpanded` (which needs to be the primitive). The expansion chain here is required so that the conditional gets cleaned up correctly (other code assumes there is exactly one token to skip during the clean-up).

```

6771   \char_set_catcode_alignment:n { 0 }
6772   \tl_put_right:Nn \l__char_tmp_tl
6773   {
6774     \or:
6775     \etex_unexpanded:D \exp_after:wN
6776     { \exp_after:wN ^^@ \exp_after:wN }
6777   }
6778   \tl_put_right:Nn \l__char_tmp_tl { \or: }

```

```

6779 \char_set_catcode_parameter:n { 0 }
6780 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
6781 \char_set_catcode_math_superscript:n { 0 }
6782 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
6783 \char_set_catcode_math_subscript:n { 0 }
6784 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
6785 \tl_put_right:Nn \l__char_tmp_tl { \or: }

```

For making spaces, there needs to be an o-type expansion of a `\use:n` (or some other tokenization) to avoid dropping the space. We also set up active tokens although they are (currently) filtered out by the interface layer (`\Ucharcat` cannot make active tokens).

```

6786 \char_set_catcode_space:n { 0 }
6787 \tl_put_right:No \l__char_tmp_tl { \use:n { \or: } ^^@ }
6788 \char_set_catcode_letter:n { 0 }
6789 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
6790 \char_set_catcode_other:n { 0 }
6791 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
6792 \char_set_catcode_active:n { 0 }
6793 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }

```

Convert the above temporary list into a series of constant token lists, one for each character code, using `\tex_lowercase:D` to convert `^^@` in each case. The x-type expansion ensures that `\tex_lowercase:D` receives the contents of the token list. In package mode, `^^L` is awkward hence this is done in three parts. Notice that at this stage `^^@` is active.

```

6794 \cs_set_protected:Npn \__char_tmp:n #1
6795 {
6796   \char_set_lccode:nn { 0 } {#1}
6797   \char_set_lccode:nn { 32 } {#1}
6798   \exp_args:Nx \tex_lowercase:D
6799   {
6800     \tl_const:Nn
6801       \exp_not:c { c__char_ \__int_to_roman:w #1 _tl }
6802       { \exp_not:o \l__char_tmp_tl }
6803   }
6804 }
6805 (*package)
6806 \int_step_function:nnnN { 0 } { 1 } { 11 } \__char_tmp:n
6807 \group_begin:
6808   \tl_replace_once:Nnn \l__char_tmp_tl { ^^@ } { \ERROR }
6809   \__char_tmp:n { 12 }
6810 \group_end:
6811 \int_step_function:nnnN { 13 } { 1 } { 255 } \__char_tmp:n
6812 \end{package}
6813 \begin{initex}
6814 \int_step_function:nnnN { 0 } { 1 } { 255 } \__char_tmp:n
6815 \end{initex}
6816 \cs_new:Npn \__char_generate_aux:nnw #1#2#3 \exp_end:
6817 {
6818   #3
6819   \exp_after:wN \exp_after:wN
6820   \exp_after:wN \exp_end:
6821   \exp_after:wN \exp_after:wN
6822   \if_case:w #2
6823     \exp_last_unbraced:Nv \exp_stop_f:

```

```

6824         { c__char_ \__int_to_roman:w #1 _tl }
6825     \fi:
6826 }
6827 \fi:
6828 \group_end:

```

(End definition for `\char_generate:nn` and others. These functions are documented on page 108.)

### 14.3 Generic tokens

```

6829 (@@=token)

```

`\token_to_meaning:N` These are all defined in `l3basics`, as they are needed “early”. This is just a reminder!

`\token_to_meaning:c`

`\token_to_str:N`

`\token_to_str:c`

`\token_new:Nn`

(End definition for `\token_to_meaning:N` and `\token_to_str:N`. These functions are documented on page 112.)

Creates a new token.

```

6830 \cs_new_protected:Npn \token_new:Nn #1#2 { \cs_new_eq:NN #1 #2 }

```

(End definition for `\token_new:Nn`. This function is documented on page 111.)

`\c_group_begin_token`

`\c_group_end_token`

`\c_math_toggle_token`

`\c_alignment_token`

`\c_parameter_token`

`\c_math_superscript_token`

`\c_math_subscript_token`

`\c_space_token`

`\c_catcode_letter_token`

`\c_catcode_other_token`

We define these useful tokens. For the brace and space tokens things have to be done by hand: the formal argument spec. for `\cs_new_eq:NN` does not cover them so we do things by hand. (As currently coded it would *work* with `\cs_new_eq:NN` but that’s not really a great idea to show off: we want people to stick to the defined interfaces and that includes us.) So that these few odd names go into the log when appropriate there is a need to hand-apply the `\__chk_if_free_cs:N` check.

```

6831 \group_begin:
6832   \__chk_if_free_cs:N \c_group_begin_token
6833   \tex_global:D \tex_let:D \c_group_begin_token {
6834     \__chk_if_free_cs:N \c_group_end_token
6835     \tex_global:D \tex_let:D \c_group_end_token }
6836   \char_set_catcode_math_toggle:N \*
6837   \cs_new_eq:NN \c_math_toggle_token *
6838   \char_set_catcode_alignment:N \*
6839   \cs_new_eq:NN \c_alignment_token *
6840   \cs_new_eq:NN \c_parameter_token #
6841   \cs_new_eq:NN \c_math_superscript_token ^
6842   \char_set_catcode_math_subscript:N \*
6843   \cs_new_eq:NN \c_math_subscript_token *
6844   \__chk_if_free_cs:N \c_space_token
6845   \use:n { \tex_global:D \tex_let:D \c_space_token = ~ } ~
6846   \cs_new_eq:NN \c_catcode_letter_token a
6847   \cs_new_eq:NN \c_catcode_other_token 1
6848 \group_end:

```

(End definition for `\c_group_begin_token` and others. These functions are documented on page 111.)

`\c_catcode_active_tl` Not an implicit token!

```

6849 \group_begin:
6850   \char_set_catcode_active:N \*
6851   \tl_const:Nn \c_catcode_active_tl { \exp_not:N * }
6852 \group_end:

```

(End definition for `\c_catcode_active_tl`. This variable is documented on page 111.)

## 14.4 Token conditionals

`\token_if_group_begin_p:N` Check if token is a begin group token. We use the constant `\c_group_begin_token` for this.  
`\token_if_group_begin:NTF`

```
6853 \prg_new_conditional:Npnn \token_if_group_begin:N #1 { p , T , F , TF }
6854 {
6855     \if_catcode:w \exp_not:N #1 \c_group_begin_token
6856     \prg_return_true: \else: \prg_return_false: \fi:
6857 }
```

(End definition for `\token_if_group_begin:N`. This function is documented on page 112.)

`\token_if_group_end_p:N` Check if token is a end group token. We use the constant `\c_group_end_token` for this.  
`\token_if_group_end:NTF`

```
6858 \prg_new_conditional:Npnn \token_if_group_end:N #1 { p , T , F , TF }
6859 {
6860     \if_catcode:w \exp_not:N #1 \c_group_end_token
6861     \prg_return_true: \else: \prg_return_false: \fi:
6862 }
```

(End definition for `\token_if_group_end:N`. This function is documented on page 112.)

`\token_if_math_toggle_p:N` Check if token is a math shift token. We use the constant `\c_math_toggle_token` for this.  
`\token_if_math_toggle:NTF`

```
6863 \prg_new_conditional:Npnn \token_if_math_toggle:N #1 { p , T , F , TF }
6864 {
6865     \if_catcode:w \exp_not:N #1 \c_math_toggle_token
6866     \prg_return_true: \else: \prg_return_false: \fi:
6867 }
```

(End definition for `\token_if_math_toggle:N`. This function is documented on page 112.)

`\token_if_alignment_p:N` Check if token is an alignment tab token. We use the constant `\c_alignment_token` for this.  
`\token_if_alignment:NTF`

```
6868 \prg_new_conditional:Npnn \token_if_alignment:N #1 { p , T , F , TF }
6869 {
6870     \if_catcode:w \exp_not:N #1 \c_alignment_token
6871     \prg_return_true: \else: \prg_return_false: \fi:
6872 }
```

(End definition for `\token_if_alignment:N`. This function is documented on page 112.)

`\token_if_parameter_p:N` Check if token is a parameter token. We use the constant `\c_parameter_token` for this.  
`\token_if_parameter:NTF` We have to trick T<sub>E</sub>X a bit to avoid an error message: within a group we prevent `\c_parameter_token` from behaving like a macro parameter character. The definitions of `\prg_new_conditional:Npnn` are global, so they remain after the group.

```
6873 \group_begin:
6874 \cs_set_eq:NN \c_parameter_token \scan_stop:
6875 \prg_new_conditional:Npnn \token_if_parameter:N #1 { p , T , F , TF }
6876 {
6877     \if_catcode:w \exp_not:N #1 \c_parameter_token
6878     \prg_return_true: \else: \prg_return_false: \fi:
6879 }
6880 \group_end:
```

(End definition for `\token_if_parameter:N`. This function is documented on page 113.)

`\token_if_math_superscript_p:N` Check if token is a math superscript token. We use the constant `\c_math_superscript_token` for this.  
`\token_if_math_superscript:N $\underline{TF}$`

```
6881 \prg_new_conditional:Npnn \token_if_math_superscript:N #1
6882 { p , T , F , TF }
6883 {
6884     \if_catcode:w \exp_not:N #1 \c_math_superscript_token
6885     \prg_return_true: \else: \prg_return_false: \fi:
6886 }
```

(End definition for `\token_if_math_superscript:N $\underline{TF}$` . This function is documented on page 113.)

`\token_if_math_subscript_p:N` Check if token is a math subscript token. We use the constant `\c_math_subscript_token` for this.  
`\token_if_math_subscript:N $\underline{TF}$`

```
6887 \prg_new_conditional:Npnn \token_if_math_subscript:N #1 { p , T , F , TF }
6888 {
6889     \if_catcode:w \exp_not:N #1 \c_math_subscript_token
6890     \prg_return_true: \else: \prg_return_false: \fi:
6891 }
```

(End definition for `\token_if_math_subscript:N $\underline{TF}$` . This function is documented on page 113.)

`\token_if_space_p:N` Check if token is a space token. We use the constant `\c_space_token` for this.

`\token_if_space:N $\underline{TF}$`

```
6892 \prg_new_conditional:Npnn \token_if_space:N #1 { p , T , F , TF }
6893 {
6894     \if_catcode:w \exp_not:N #1 \c_space_token
6895     \prg_return_true: \else: \prg_return_false: \fi:
6896 }
```

(End definition for `\token_if_space:N $\underline{TF}$` . This function is documented on page 113.)

`\token_if_letter_p:N` Check if token is a letter token. We use the constant `\c_catcode_letter_token` for this.

`\token_if_letter:N $\underline{TF}$`

```
6897 \prg_new_conditional:Npnn \token_if_letter:N #1 { p , T , F , TF }
6898 {
6899     \if_catcode:w \exp_not:N #1 \c_catcode_letter_token
6900     \prg_return_true: \else: \prg_return_false: \fi:
6901 }
```

(End definition for `\token_if_letter:N $\underline{TF}$` . This function is documented on page 113.)

`\token_if_other_p:N` Check if token is an other char token. We use the constant `\c_catcode_other_token` for this.  
`\token_if_other:N $\underline{TF}$`

```
6902 \prg_new_conditional:Npnn \token_if_other:N #1 { p , T , F , TF }
6903 {
6904     \if_catcode:w \exp_not:N #1 \c_catcode_other_token
6905     \prg_return_true: \else: \prg_return_false: \fi:
6906 }
```

(End definition for `\token_if_other:N $\underline{TF}$` . This function is documented on page 113.)

`\token_if_active_p:N` Check if token is an active char token. We use the constant `\c_catcode_active_tl` for this. A technical point is that `\c_catcode_active_tl` is in fact a macro expanding to `\exp_not:N *`, where `*` is active.

`\token_if_active:N $\underline{TF}$`

```
6907 \prg_new_conditional:Npnn \token_if_active:N #1 { p , T , F , TF }
6908 {
6909     \if_catcode:w \exp_not:N #1 \c_catcode_active_tl
6910     \prg_return_true: \else: \prg_return_false: \fi:
6911 }
```

(End definition for `\token_if_active:NTF`. This function is documented on page 113.)

`\token_if_eq_meaning_p:NN` Check if the tokens #1 and #2 have same meaning.

```
\token_if_eq_meaning:NNTF
6912 \prg_new_conditional:Npnn \token_if_eq_meaning:NN #1#2 { p , T , F , TF }
6913 {
6914   \if_meaning:w #1 #2
6915   \prg_return_true: \else: \prg_return_false: \fi:
6916 }
```

(End definition for `\token_if_eq_meaning:NNTF`. This function is documented on page 113.)

`\token_if_eq_catcode_p:NN` Check if the tokens #1 and #2 have same category code.

```
\token_if_eq_catcode:NNTF
6917 \prg_new_conditional:Npnn \token_if_eq_catcode:NN #1#2 { p , T , F , TF }
6918 {
6919   \if_catcode:w \exp_not:N #1 \exp_not:N #2
6920   \prg_return_true: \else: \prg_return_false: \fi:
6921 }
```

(End definition for `\token_if_eq_catcode:NNTF`. This function is documented on page 113.)

`\token_if_eq_charcode_p:NN` Check if the tokens #1 and #2 have same character code.

```
\token_if_eq_charcode:NNTF
6922 \prg_new_conditional:Npnn \token_if_eq_charcode:NN #1#2 { p , T , F , TF }
6923 {
6924   \if_charcode:w \exp_not:N #1 \exp_not:N #2
6925   \prg_return_true: \else: \prg_return_false: \fi:
6926 }
```

(End definition for `\token_if_eq_charcode:NNTF`. This function is documented on page 113.)

`\token_if_macro_p:N` When a token is a macro, `\token_to_meaning:N` always outputs something like  
`\token_if_macro:NTF` `\long macro:#1->#1` so we could naively check to see if the meaning contains `->`.  
`\__token_if_macro_p:w` However, this can fail the five `\...mark` primitives, whose meaning has the form `\...mark:<user material>`. The problem is that the `<user material>` can contain `->`.

However, only characters, macros, and marks can contain the colon character. The idea is thus to grab until the first `:`, and analyse what is left. However, macros can have any combination of `\long`, `\protected` or `\outer` (not used in L<sup>A</sup>T<sub>E</sub>X3) before the string `macro:.` We thus only select the part of the meaning between the first `ma` and the first following `:`. If this string is `cro`, then we have a macro. If the string is `rk`, then we have a mark. The string can also be `cro parameter character` for a colon with a weird category code (namely the usual category code of `#`). Otherwise, it is empty.

This relies on the fact that `\long`, `\protected`, `\outer` cannot contain `ma`, regardless of the escape character, even if the escape character is `m...`

Both `ma` and `:` must be of category code 12 (other), so are detokenized.

```
6927 \use:x
6928 {
6929   \prg_new_conditional:Npnn \exp_not:N \token_if_macro:N ##1
6930   { p , T , F , TF }
6931   {
6932     \exp_not:N \exp_after:wN \exp_not:N \__token_if_macro_p:w
6933     \exp_not:N \token_to_meaning:N ##1 \tl_to_str:n { ma : }
6934     \exp_not:N \q_stop
6935   }
6936   \cs_new:Npn \exp_not:N \__token_if_macro_p:w
```

```

6937     ##1 \tl_to_str:n { ma } ##2 \c_colon_str ##3 \exp_not:N \q_stop
6938   }
6939   {
6940     \if_int_compare:w \__str_if_eq_x:nn { #2 } { cro } = 0 \exp_stop_f:
6941     \prg_return_true:
6942   \else:
6943     \prg_return_false:
6944   \fi:
6945   }

```

(End definition for `\token_if_macro:NTF` and `\__token_if_macro_p:w`. These functions are documented on page 114.)

`\token_if_cs_p:N` Check if token has same catcode as a control sequence. This follows the same pattern as `\token_if_letter:N` etc. We use `\scan_stop:` for this.

`\token_if_cs:NTF`

```

6946 \prg_new_conditional:Npnn \token_if_cs:N #1 { p , T , F , TF }
6947 {
6948   \if_catcode:w \exp_not:N #1 \scan_stop:
6949   \prg_return_true: \else: \prg_return_false: \fi:
6950 }

```

(End definition for `\token_if_cs:NTF`. This function is documented on page 114.)

`\token_if_expandable_p:N` Check if token is expandable. We use the fact that T<sub>E</sub>X temporarily converts `\exp_not:N`  $\langle token \rangle$  into `\scan_stop:` if  $\langle token \rangle$  is expandable. An undefined token is not considered as expandable. No problem nesting the conditionals, since the third #1 is only skipped if it is non-expandable (hence not part of T<sub>E</sub>X's conditional apparatus).

`\token_if_expandable:NTF`

```

6951 \prg_new_conditional:Npnn \token_if_expandable:N #1 { p , T , F , TF }
6952 {
6953   \exp_after:wN \if_meaning:w \exp_not:N #1 #1
6954   \prg_return_false:
6955 \else:
6956   \if_cs_exist:N #1
6957   \prg_return_true:
6958 \else:
6959   \prg_return_false:
6960 \fi:
6961 \fi:
6962 }

```

(End definition for `\token_if_expandable:NTF`. This function is documented on page 114.)

`\__token_delimit_by_char:w` These auxiliary functions are used below to define some conditionals which detect whether the `\meaning` of their argument begins with a particular string. Each auxiliary takes an argument delimited by a string, a second one delimited by `\q_stop`, and returns the first one and its delimiter. This result is eventually compared to another string.

```

6963 \group_begin:
6964 \cs_set_protected:Npn \__token_tmp:w #1
6965 {
6966   \use:x
6967   {
6968     \cs_new:Npn \exp_not:c { __token_delimit_by_ #1 :w }
6969     #####1 \tl_to_str:n {#1} #####2 \exp_not:N \q_stop
6970     { #####1 \tl_to_str:n {#1} }

```



```

6971     }
6972   }
6973   \__token_tmp:w { char" }
6974   \__token_tmp:w { count }
6975   \__token_tmp:w { dimen }
6976   \__token_tmp:w { macro }
6977   \__token_tmp:w { muskip }
6978   \__token_tmp:w { skip }
6979   \__token_tmp:w { toks }
6980 \group_end:

```

(End definition for `\__token_delimit_by_char:w` and others.)

<pre> \token_if_chardef_p:N \token_if_chardef:NTF \token_if_mathchardef_p:N \token_if_mathchardef:NTF \token_if_long_macro_p:N \token_if_long_macro:NTF \token_if_protected_macro_p:N \token_if_protected_macro:NTF \token_if_protected_long_macro_p:N \token_if_protected_long_macro:NTF \token_if_dim_register_p:N \token_if_dim_register:NTF \token_if_int_register_p:N \token_if_int_register:NTF \token_if_muskip_register_p:N \token_if_muskip_register:NTF \token_if_skip_register_p:N \token_if_skip_register:NTF \token_if_toks_register_p:N \token_if_toks_register:NTF </pre>	<p>Each of these conditionals tests whether its argument's <code>\meaning</code> starts with a given string. This is essentially done by having an auxiliary grab an argument delimited by the string and testing whether the argument was empty. Of course, a copy of this string must first be added to the end of the <code>\meaning</code> to avoid a runaway argument in case it does not contain the string. Two complications arise. First, the escape character is not fixed, and cannot be included in the delimiter of the auxiliary function (this function cannot be defined on the fly because tests must remain expandable): instead the first argument of the auxiliary (plus the delimiter to avoid complications with trailing spaces) is compared using <code>\__str_if_eq_x_return:nn</code> to the result of applying <code>\token_to_str:N</code> to a control sequence. Second, the <code>\meaning</code> of primitives such as <code>\dimen</code> or <code>\dimendef</code> starts in the same way as registers such as <code>\dimen123</code>, so they must be tested for.</p> <p>Characters used as delimiters must have catcode 12 and are obtained through <code>\tl_to_str:n</code>. This requires doing all definitions within <code>x</code>-expansion. The temporary function <code>\__token_tmp:w</code> used to define each conditional receives three arguments: the name of the conditional, the auxiliary's delimiter (also used to name the auxiliary), and the string to which one compares the auxiliary's result. Note that the <code>\meaning</code> of a protected long macro starts with <code>\protected\long macro</code>, with no space after <code>\protected</code> but a space after <code>\long</code>, hence the mixture of <code>\token_to_str:N</code> and <code>\tl_to_str:n</code>.</p>
--	---

For the first five conditionals, `\cs_if_exist:cT` turns out to be `false`, and the code boils down to a string comparison between the result of the auxiliary on the `\meaning` of the conditional's argument `####1`, and `#3`. Both are evaluated at run-time, as this is important to get the correct escape character.

The other five conditionals have additional code that compares the argument `####1` to two TeX primitives which would wrongly be recognized as registers otherwise. Despite using TeX's primitive conditional construction, this does not break when `####1` is itself a conditional, because branches of the conditionals are only skipped if `####1` is one of the two primitives that are tested for (which are not TeX conditionals).

```

6981 \group_begin:
6982 \cs_set_protected:Npn \__token_tmp:w #1#2#3
6983 {
6984   \use:x
6985   {
6986     \prg_new_conditional:Npnn \exp_not:c { token_if_ #1 :N } ####1
6987     { p , T , F , TF }
6988     {
6989       \cs_if_exist:cT { tex_ #2 :D }
6990       {
6991         \exp_not:N \if_meaning:w ####1 \exp_not:c { tex_ #2 :D }

```

```

6992         \exp_not:N \prg_return_false:
6993         \exp_not:N \else:
6994         \exp_not:N \if_meaning:w #####1 \exp_not:c { tex_ #2 def:D }
6995         \exp_not:N \prg_return_false:
6996         \exp_not:N \else:
6997     }
6998     \exp_not:N \__str_if_eq_x_return:nn
6999     {
7000         \exp_not:N \exp_after:wN
7001         \exp_not:c { __token_delimit_by_ #2 :w }
7002         \exp_not:N \token_to_meaning:N #####1
7003         ? \tl_to_str:n {#2} \exp_not:N \q_stop
7004     }
7005     { \exp_not:n {#3} }
7006     \cs_if_exist:cT { tex_ #2 :D }
7007     {
7008         \exp_not:N \fi:
7009         \exp_not:N \fi:
7010     }
7011 }
7012 }
7013 }
7014 \__token_tmp:w { chardef } { char" } { \token_to_str:N \char" }
7015 \__token_tmp:w { mathchardef } { char" } { \token_to_str:N \mathchar" }
7016 \__token_tmp:w { long_macro } { macro } { \tl_to_str:n { \long } macro }
7017 \__token_tmp:w { protected_macro } { macro }
7018     { \tl_to_str:n { \protected } macro }
7019 \__token_tmp:w { protected_long_macro } { macro }
7020     { \token_to_str:N \protected \tl_to_str:n { \long } macro }
7021 \__token_tmp:w { dim_register } { dimen } { \token_to_str:N \dimen }
7022 \__token_tmp:w { int_register } { count } { \token_to_str:N \count }
7023 \__token_tmp:w { muskip_register } { muskip } { \token_to_str:N \muskip }
7024 \__token_tmp:w { skip_register } { skip } { \token_to_str:N \skip }
7025 \__token_tmp:w { toks_register } { toks } { \token_to_str:N \toks }
7026 \group_end:

```

(End definition for `\token_if_chardef:N` and others. These functions are documented on page 114.)

`\token_if_primitive_p:N`

We filter out macros first, because they cause endless trouble later otherwise.

`\token_if_primitive:N` **TF**

Primitives are almost distinguished by the fact that the result of `\token_to_meaning:N` is formed from letters only. Every other token has either a space (e.g., the letter A), a digit (e.g., `\count123`) or a double quote (e.g., `\char"A`).

`\__token_if_primitive:NNw`

Ten exceptions: on the one hand, `\tex_undefined:D` is not a primitive, but its meaning is undefined, only letters; on the other hand, `\space`, `\italiccorr`, `\hyphen`, `\firstmark`, `\topmark`, `\botmark`, `\splitfirstmark`, `\splitbotmark`, and `\nullfont` are primitives, but have non-letters in their meaning.

`\__token_if_primitive_space:w`

`\__token_if_primitive_nullfont:N`

`\__token_if_primitive_loop:N`

`\__token_if_primitive:Nw`

`\__token_if_primitive_undefined:N`

We start by removing the two first (non-space) characters from the meaning. This removes the escape character (which may be nonexistent depending on `\endlinechar`), and takes care of three of the exceptions: `\space`, `\italiccorr` and `\hyphen`, whose meaning is at most two characters. This leaves a string terminated by some `:`, and `\q_stop`.

The meaning of each one of the five `\...mark` primitives has the form  $\langle letters \rangle : \langle user material \rangle$ . In other words, the first non-letter is a colon. We remove everything after the first colon.

We are now left with a string, which we must analyze. For primitives, it contains only letters. For non-primitives, it contains either " , or a space, or a digit. Two exceptions remain: `\tex_undefined:D`, which is not a primitive, and `\nullfont`, which is a primitive.

Spaces cannot be grabbed in an undelimited way, so we check them separately. If there is a space, we test for `\nullfont`. Otherwise, we go through characters one by one, and stop at the first character less than 'A (this is not quite a test for "only letters", but is close enough to work in this context). If this first character is : then we have a primitive, or `\tex_undefined:D`, and if it is " or a digit, then the token is not a primitive.

```

7027 \tex_chardef:D \c__token_A_int = 'A ~ %
7028 \use:x
7029 {
7030   \prg_new_conditional:Npnn \exp_not:N \token_if_primitive:N ##1
7031   { p , T , F , TF }
7032   {
7033     \exp_not:N \token_if_macro:NTF ##1
7034     \exp_not:N \prg_return_false:
7035     {
7036       \exp_not:N \exp_after:wN \exp_not:N \__token_if_primitive:NNw
7037       \exp_not:N \token_to_meaning:N ##1
7038       \tl_to_str:n { : : : } \exp_not:N \q_stop ##1
7039     }
7040   }
7041   \cs_new:Npn \exp_not:N \__token_if_primitive:NNw
7042   ##1##2 ##3 \c_colon_str ##4 \exp_not:N \q_stop
7043   {
7044     \exp_not:N \tl_if_empty:oTF
7045     { \exp_not:N \__token_if_primitive_space:w ##3 ~ }
7046     {
7047       \exp_not:N \__token_if_primitive_loop:N ##3
7048       \c_colon_str \exp_not:N \q_stop
7049     }
7050     { \exp_not:N \__token_if_primitive_nullfont:N }
7051   }
7052 }
7053 \cs_new:Npn \__token_if_primitive_space:w #1 ~ { }
7054 \cs_new:Npn \__token_if_primitive_nullfont:N #1
7055 {
7056   \if_meaning:w \tex_nullfont:D #1
7057   \prg_return_true:
7058   \else:
7059   \prg_return_false:
7060   \fi:
7061 }
7062 \cs_new:Npn \__token_if_primitive_loop:N #1
7063 {
7064   \if_int_compare:w ' #1 < \c__token_A_int %
7065   \exp_after:wN \__token_if_primitive:Nw
7066   \exp_after:wN #1
7067   \else:
7068   \exp_after:wN \__token_if_primitive_loop:N
7069   \fi:
7070 }
```

```

7071 \cs_new:Npn \__token_if_primitive:Nw #1 #2 \q_stop
7072 {
7073   \if:w : #1
7074     \exp_after:wN \__token_if_primitive_undefined:N
7075   \else:
7076     \prg_return_false:
7077     \exp_after:wN \use_none:n
7078   \fi:
7079 }
7080 \cs_new:Npn \__token_if_primitive_undefined:N #1
7081 {
7082   \if_cs_exist:N #1
7083     \prg_return_true:
7084   \else:
7085     \prg_return_false:
7086   \fi:
7087 }

```

(End definition for `\token_if_primitive:NTF` and others. These functions are documented on page 115.)

## 14.5 Peeking ahead at the next token

```
7088 <@@=peek>
```

Peeking ahead is implemented using a two part mechanism. The outer level provides a defined interface to the lower level material. This allows a large amount of code to be shared. There are four cases:

1. peek at the next token;
2. peek at the next non-space token;
3. peek at the next token and remove it;
4. peek at the next non-space token and remove it.

`\l_peek_token` Storage tokens which are publicly documented: the token peeked.

```

\g_peek_token 7089 \cs_new_eq:NN \l_peek_token ?
7090 \cs_new_eq:NN \g_peek_token ?

```

(End definition for `\l_peek_token` and `\g_peek_token`. These variables are documented on page 116.)

`\l__peek_search_token` The token to search for as an implicit token: cf. `\l__peek_search_tl`.

```
7091 \cs_new_eq:NN \l__peek_search_token ?
```

(End definition for `\l__peek_search_token`.)

`\l__peek_search_tl` The token to search for as an explicit token: cf. `\l__peek_search_token`.

```
7092 \tl_new:N \l__peek_search_tl
```

(End definition for `\l__peek_search_tl`.)

`\__peek_true:w` Functions used by the branching and space-stripping code.

```

\__peek_true_aux:w 7093 \cs_new:Npn \__peek_true:w { }
\__peek_false:w 7094 \cs_new:Npn \__peek_true_aux:w { }
\__peek_tmp:w 7095 \cs_new:Npn \__peek_false:w { }
7096 \cs_new:Npn \__peek_tmp:w { }

```

(End definition for `\_peek_true:w` and others.)

`\peek_after:Nw` Simple wrappers for `\futurelet`: no arguments absorbed here.  
`\peek_gafter:Nw`

```
7097 \cs_new_protected:Npn \peek_after:Nw
7098   { \tex_futurelet:D \l_peek_token }
7099 \cs_new_protected:Npn \peek_gafter:Nw
7100   { \tex_global:D \tex_futurelet:D \g_peek_token }
```

(End definition for `\peek_after:Nw` and `\peek_gafter:Nw`. These functions are documented on page 115.)

`\_peek_true_remove:w` A function to remove the next token and then regain control.

```
7101 \cs_new_protected:Npn \_peek_true_remove:w
7102   {
7103     \group_align_safe_end:
7104     \tex_afterassignment:D \_peek_true_aux:w
7105     \cs_set_eq:NN \_peek_tmp:w
7106   }
```

(End definition for `\_peek_true_remove:w`.)

`\_peek_token_generic:NNTF` The generic function stores the test token in both implicit and explicit modes, and the **true** and **false** code as token lists, more or less. The two branches have to be absorbed here as the input stream needs to be cleared for the peek function itself.

```
7107 \cs_new_protected:Npn \_peek_token_generic:NNTF #1#2#3#4
7108   {
7109     \cs_set_eq:NN \l__peek_search_token #2
7110     \tl_set:Nn \l__peek_search_tl {#2}
7111     \cs_set:Npx \_peek_true:w
7112     {
7113       \exp_not:N \group_align_safe_end:
7114       \exp_not:n {#3}
7115     }
7116     \cs_set:Npx \_peek_false:w
7117     {
7118       \exp_not:N \group_align_safe_end:
7119       \exp_not:n {#4}
7120     }
7121     \group_align_safe_begin:
7122     \peek_after:Nw #1
7123   }
7124 \cs_new_protected:Npn \_peek_token_generic:NNT #1#2#3
7125   { \_peek_token_generic:NNTF #1 #2 {#3} { } }
7126 \cs_new_protected:Npn \_peek_token_generic:NNF #1#2#3
7127   { \_peek_token_generic:NNTF #1 #2 { } {#3} }
```

(End definition for `\_peek_token_generic:NNTF`.)

`\_peek_token_remove_generic:NNTF` For token removal there needs to be a call to the auxiliary function which does the work.

```
7128 \cs_new_protected:Npn \_peek_token_remove_generic:NNTF #1#2#3#4
7129   {
7130     \cs_set_eq:NN \l__peek_search_token #2
7131     \tl_set:Nn \l__peek_search_tl {#2}
7132     \cs_set_eq:NN \_peek_true:w \_peek_true_remove:w
7133     \cs_set:Npx \_peek_true_aux:w { \exp_not:n {#3} }
```

```

7134 \cs_set:Npx \__peek_false:w
7135 {
7136   \exp_not:N \group_align_safe_end:
7137   \exp_not:n {#4}
7138 }
7139 \group_align_safe_begin:
7140 \peek_after:Nw #1
7141 }
7142 \cs_new_protected:Npn \__peek_token_remove_generic:NNT #1#2#3
7143 { \__peek_token_remove_generic:NNTF #1 #2 {#3} { } }
7144 \cs_new_protected:Npn \__peek_token_remove_generic:NNF #1#2#3
7145 { \__peek_token_remove_generic:NNTF #1 #2 { } {#3} }

```

(End definition for `\__peek_token_remove_generic:NNTF`.)

`\__peek_execute_branches_meaning:` The meaning test is straight forward.

```

7146 \cs_new:Npn \__peek_execute_branches_meaning:
7147 {
7148   \if_meaning:w \l_peek_token \l_peek_search_token
7149   \exp_after:wN \__peek_true:w
7150   \else:
7151     \exp_after:wN \__peek_false:w
7152   \fi:
7153 }

```

(End definition for `\__peek_execute_branches_meaning:`.)

`\__peek_execute_branches_catcode:` The catcode and charcode tests are very similar, and in order to use the same auxiliaries we do something a little bit odd, firing `\if_catcode:w` and `\if_charcode:w` before finding the operands for those tests, which are only given in the `auxii:N` and `auxiii:` auxiliaries. For our purposes, three kinds of tokens may follow the peeking function:

- control sequences which are not equal to a non-active character token (*e.g.*, macro, primitive);
- active characters which are not equal to a non-active character token (*e.g.*, macro, primitive);
- explicit non-active character tokens, or control sequences or active characters set equal to a non-active character token.

The first two cases are not distinguishable simply using TeX's `\futurelet`, because we can only access the `\meaning` of tokens in that way. In those cases, detected thanks to a comparison with `\scan_stop:`, we grab the following token, and compare it explicitly with the explicit search token stored in `\l_peek_search_tl`. The `\exp_not:N` prevents outer macros (coming from non-~~La~~TeX3 code) from blowing up. In the third case, `\l_peek_token` is good enough for the test, and we compare it again with the explicit search token. Just like the peek token, the search token may be of any of the three types above, hence the need to use the explicit token that was given to the peek function.

```

7154 \cs_new:Npn \__peek_execute_branches_catcode:
7155 { \if_catcode:w \__peek_execute_branches_catcode_aux: }
7156 \cs_new:Npn \__peek_execute_branches_charcode:
7157 { \if_charcode:w \__peek_execute_branches_catcode_aux: }
7158 \cs_new:Npn \__peek_execute_branches_catcode_aux:

```

```

7159 {
7160     \if_catcode:w \exp_not:N \l_peek_token \scan_stop:
7161     \exp_after:wN \exp_after:wN
7162     \exp_after:wN \__peek_execute_branches_catcode_auxii:N
7163     \exp_after:wN \exp_not:N
7164     \else:
7165     \exp_after:wN \__peek_execute_branches_catcode_auxiii:
7166     \fi:
7167 }
7168 \cs_new:Npn \__peek_execute_branches_catcode_auxii:N #1
7169 {
7170     \exp_not:N #1
7171     \exp_after:wN \exp_not:N \l_peek_search_tl
7172     \exp_after:wN \__peek_true:w
7173     \else:
7174     \exp_after:wN \__peek_false:w
7175     \fi:
7176     #1
7177 }
7178 \cs_new:Npn \__peek_execute_branches_catcode_auxiii:
7179 {
7180     \exp_not:N \l_peek_token
7181     \exp_after:wN \exp_not:N \l_peek_search_tl
7182     \exp_after:wN \__peek_true:w
7183     \else:
7184     \exp_after:wN \__peek_false:w
7185     \fi:
7186 }

```

(End definition for \\_\_peek\_execute\_branches\_catcode: and others.)

\\_\_peek\_ignore\_spaces\_execute\_branches: This function removes one space token at a time, and calls \\_\_peek\_execute\_branches: when encountering the first non-space token. We directly use the primitive meaning test rather than \token\_if\_eq\_meaning:NNTF because \l\_peek\_token may be an outer macro (coming from non-L<sup>A</sup>T<sub>E</sub>X3 packages). Spaces are removed using a side-effect of f-expansion: \exp:w \exp\_end\_continue\_f:w removes one space.

```

7187 \cs_new_protected:Npn \__peek_ignore_spaces_execute_branches:
7188 {
7189     \if_meaning:w \l_peek_token \c_space_token
7190     \exp_after:wN \peek_after:Nw
7191     \exp_after:wN \__peek_ignore_spaces_execute_branches:
7192     \exp:w \exp_end_continue_f:w
7193     \else:
7194     \exp_after:wN \__peek_execute_branches:
7195     \fi:
7196 }

```

(End definition for \\_\_peek\_ignore\_spaces\_execute\_branches:.)

\\_\_peek\_def:nnnn The public functions themselves cannot be defined using \prg\_new\_conditional:Npnn and so a couple of auxiliary functions are used. As a result, everything is done inside a group. As a result things are a bit complicated.

```

7197 \group_begin:
7198 \cs_set:Npn \__peek_def:nnnn #1#2#3#4

```

```

7199     {
7200         \__peek_def:nnnnn {#1} {#2} {#3} {#4} { TF }
7201         \__peek_def:nnnnn {#1} {#2} {#3} {#4} { T }
7202         \__peek_def:nnnnn {#1} {#2} {#3} {#4} { F }
7203     }
7204     \cs_set:Npn \__peek_def:nnnnn #1#2#3#4#5
7205     {
7206         \cs_new_protected:cpx { #1 #5 }
7207         {
7208             \tl_if_empty:nF {#2}
7209             { \exp_not:n { \cs_set_eq:NN \__peek_execute_branches: #2 } }
7210             \exp_not:c { #3 #5 }
7211             \exp_not:n {#4}
7212         }
7213     }

```

(End definition for \\_\_peek\_def:nnnn and \\_\_peek\_def:nnnnn.)

**\peek\_catcode:NTF** With everything in place the definitions can take place. First for category codes.  
**\peek\_catcode\_ignore\_spaces:NTF**  
**\peek\_catcode\_remove:NTF**  
**\peek\_catcode\_remove\_ignore\_spaces:NTF**

```

7214     \__peek_def:nnnn { peek_catcode:N }
7215     { }
7216     { __peek_token_generic:NN }
7217     { \__peek_execute_branches_catcode: }
7218     \__peek_def:nnnn { peek_catcode_ignore_spaces:N }
7219     { \__peek_execute_branches_catcode: }
7220     { __peek_token_generic:NN }
7221     { \__peek_ignore_spaces_execute_branches: }
7222     \__peek_def:nnnn { peek_catcode_remove:N }
7223     { }
7224     { __peek_token_remove_generic:NN }
7225     { \__peek_execute_branches_catcode: }
7226     \__peek_def:nnnn { peek_catcode_remove_ignore_spaces:N }
7227     { \__peek_execute_branches_catcode: }
7228     { __peek_token_remove_generic:NN }
7229     { \__peek_ignore_spaces_execute_branches: }

```

(End definition for \peek\_catcode:NTF and others. These functions are documented on page 116.)

**\peek\_charcode:NTF** Then for character codes.  
**\peek\_charcode\_ignore\_spaces:NTF**  
**\peek\_charcode\_remove:NTF**  
**\peek\_charcode\_remove\_ignore\_spaces:NTF**

```

7230     \__peek_def:nnnn { peek_charcode:N }
7231     { }
7232     { __peek_token_generic:NN }
7233     { \__peek_execute_branches_charcode: }
7234     \__peek_def:nnnn { peek_charcode_ignore_spaces:N }
7235     { \__peek_execute_branches_charcode: }
7236     { __peek_token_generic:NN }
7237     { \__peek_ignore_spaces_execute_branches: }
7238     \__peek_def:nnnn { peek_charcode_remove:N }
7239     { }
7240     { __peek_token_remove_generic:NN }
7241     { \__peek_execute_branches_charcode: }
7242     \__peek_def:nnnn { peek_charcode_remove_ignore_spaces:N }
7243     { \__peek_execute_branches_charcode: }
7244     { __peek_token_remove_generic:NN }
7245     { \__peek_ignore_spaces_execute_branches: }

```



(End definition for `\peek_charcode:N` and others. These functions are documented on page 116.)

Finally for meaning, with the group closed to remove the temporary definition functions.

```

\peek_meaning:N\TF
\peek_meaning_ignore_spaces:N\TF
\peek_meaning_remove:N\TF
\peek_meaning_remove_ignore_spaces:N\TF
7246 \__peek_def:nnnn { peek_meaning:N }
7247 { }
7248 { __peek_token_generic:NN }
7249 { \__peek_execute_branches_meaning: }
7250 \__peek_def:nnnn { peek_meaning_ignore_spaces:N }
7251 { \__peek_execute_branches_meaning: }
7252 { __peek_token_generic:NN }
7253 { \__peek_ignore_spaces_execute_branches: }
7254 \__peek_def:nnnn { peek_meaning_remove:N }
7255 { }
7256 { __peek_token_remove_generic:NN }
7257 { \__peek_execute_branches_meaning: }
7258 \__peek_def:nnnn { peek_meaning_remove_ignore_spaces:N }
7259 { \__peek_execute_branches_meaning: }
7260 { __peek_token_remove_generic:NN }
7261 { \__peek_ignore_spaces_execute_branches: }
7262 \group_end:

```

(End definition for `\peek_meaning:N` and others. These functions are documented on page 117.)

## 14.6 Decomposing a macro definition

We sometimes want to test if a control sequence can be expanded to reveal a hidden value. However, we cannot just expand the macro blindly as it may have arguments and none might be present. Therefore we define these functions to pick either the prefix(es), the argument specification, or the replacement text from a macro. All of this information is returned as characters with catcode 12. If the token in question isn't a macro, the token `\scan_stop:` is returned instead.

```

\token_get_prefix_spec:N
\token_get_arg_spec:N
\token_get_replacement_spec:N
\__peek_get_prefix_arg_replacement:wN
7263 \exp_args:Nno \use:nn
7264 { \cs_new:Npn \__peek_get_prefix_arg_replacement:wN #1 }
7265 { \tl_to_str:n { macro : } #2 -> #3 \q_stop #4 }
7266 { #4 {#1} {#2} {#3} }
7267 \cs_new:Npn \token_get_prefix_spec:N #1
7268 {
7269   \token_if_macro:N\TF #1
7270   {
7271     \exp_after:wN \__peek_get_prefix_arg_replacement:wN
7272     \token_to_meaning:N #1 \q_stop \use_i:nnn
7273   }
7274   { \scan_stop: }
7275 }
7276 \cs_new:Npn \token_get_arg_spec:N #1
7277 {
7278   \token_if_macro:N\TF #1
7279   {
7280     \exp_after:wN \__peek_get_prefix_arg_replacement:wN
7281     \token_to_meaning:N #1 \q_stop \use_ii:nnn
7282   }
7283   { \scan_stop: }
7284 }

```

```

7285 \cs_new:Npn \token_get_replacement_spec:N #1
7286 {
7287   \token_if_macro:NTF #1
7288   {
7289     \exp_after:wN \__peek_get_prefix_arg_replacement:wN
7290     \token_to_meaning:N #1 \q_stop \use_iii:nnn
7291   }
7292   { \scan_stop: }
7293 }

```

(End definition for `\token_get_prefix_spec:N` and others. These functions are documented on page 119.)

```

7294 </initex | package>

```

## 15 l3prop implementation

The following test files are used for this code: `m3prop001`, `m3prop002`, `m3prop003`, `m3prop004`, `m3show001`.

```

7295 <*initex | package>
7296 <@@=prop>

```

A property list is a macro whose top-level expansion is of the form

```

\__prop \__prop_pair:wn <key1> \__prop {<value1>}
...
\__prop_pair:wn <keyn> \__prop {<valuen>}

```

where `\__prop` is a scan mark (equal to `\scan_stop:`), and `\__prop_pair:wn` can be used to map through the property list.

**\\_\_prop** A private scan mark is used as a marker after each key, and at the very beginning of the property list.

```

7297 \__scan_new:N \__prop

```

(End definition for `\__prop`.)

**\\_\_prop\_pair:wn** The delimiter is always defined, but when misused simply triggers an error and removes its argument.

```

7298 \cs_new:Npn \__prop_pair:wn #1 \__prop #2
7299 { \__msg_kernel_expandable_error:nn { kernel } { misused-prop } }

```

(End definition for `\__prop_pair:wn`.)

**\l\_\_prop\_internal\_tl** Token list used to store the new key–value pair inserted by `\prop_put:Nnn` and friends.

```

7300 \tl_new:N \l__prop_internal_tl

```

(End definition for `\l__prop_internal_tl`.)

**\c\_empty\_prop** An empty prop.

```

7301 \tl_const:Nn \c_empty_prop { \__prop }

```

(End definition for `\c_empty_prop`. This variable is documented on page 127.)

## 15.1 Allocation and initialisation

**\prop\_new:N** Property lists are initialized with the value `\c_empty_prop`.

```
\prop_new:c      7302 \cs_new_protected:Npn \prop_new:N #1
                  7303 {
                  7304   \__chk_if_free_cs:N #1
                  7305   \cs_gset_eq:NN #1 \c_empty_prop
                  7306 }
                  7307 \cs_generate_variant:Nn \prop_new:N { c }
```

(End definition for `\prop_new:N`. This function is documented on page 122.)

**\prop\_clear:N** The same idea for clearing.

```
\prop_clear:c    7308 \cs_new_protected:Npn \prop_clear:N #1
\prop_gclear:N    7309 { \prop_set_eq:NN #1 \c_empty_prop }
\prop_gclear:c    7310 \cs_generate_variant:Nn \prop_clear:N { c }
                  7311 \cs_new_protected:Npn \prop_gclear:N #1
                  7312 { \prop_gset_eq:NN #1 \c_empty_prop }
                  7313 \cs_generate_variant:Nn \prop_gclear:N { c }
```

(End definition for `\prop_clear:N` and `\prop_gclear:N`. These functions are documented on page 122.)

**\prop\_clear\_new:N** Once again a simple variation of the token list functions.

```
\prop_clear_new:c 7314 \cs_new_protected:Npn \prop_clear_new:N #1
\prop_gclear_new:N 7315 { \prop_if_exist:NTF #1 { \prop_clear:N #1 } { \prop_new:N #1 } }
\prop_gclear_new:c 7316 \cs_generate_variant:Nn \prop_clear_new:N { c }
                  7317 \cs_new_protected:Npn \prop_gclear_new:N #1
                  7318 { \prop_if_exist:NTF #1 { \prop_gclear:N #1 } { \prop_new:N #1 } }
                  7319 \cs_generate_variant:Nn \prop_gclear_new:N { c }
```

(End definition for `\prop_clear_new:N` and `\prop_gclear_new:N`. These functions are documented on page 122.)

**\prop\_set\_eq:NN** These are simply copies from the token list functions.

```
\prop_set_eq:cN   7320 \cs_new_eq:NN \prop_set_eq:NN \tl_set_eq:NN
\prop_set_eq:Nc    7321 \cs_new_eq:NN \prop_set_eq:Nc \tl_set_eq:Nc
\prop_set_eq:cc    7322 \cs_new_eq:NN \prop_set_eq:cN \tl_set_eq:cN
\prop_gset_eq:NN   7323 \cs_new_eq:NN \prop_set_eq:cc \tl_set_eq:cc
\prop_gset_eq:cN   7324 \cs_new_eq:NN \prop_gset_eq:NN \tl_gset_eq:NN
\prop_gset_eq:Nc   7325 \cs_new_eq:NN \prop_gset_eq:Nc \tl_gset_eq:Nc
\prop_gset_eq:cN   7326 \cs_new_eq:NN \prop_gset_eq:cN \tl_gset_eq:cN
\prop_gset_eq:cc   7327 \cs_new_eq:NN \prop_gset_eq:cc \tl_gset_eq:cc
```

(End definition for `\prop_set_eq:NN` and `\prop_gset_eq:NN`. These functions are documented on page 122.)

**\l\_tmpa\_prop** We can now initialize the scratch variables.

```
\l_tmpb_prop      7328 \prop_new:N \l_tmpa_prop
\g_tmpa_prop       7329 \prop_new:N \l_tmpb_prop
\g_tmpb_prop       7330 \prop_new:N \g_tmpa_prop
                  7331 \prop_new:N \g_tmpb_prop
```

(End definition for `\l_tmpa_prop` and others. These variables are documented on page 127.)

## 15.2 Accessing data in property lists

`\__prop_split:NnTF`  
`\__prop_split_aux:NnTF`  
`\__prop_split_aux:w`

This function is used by most of the module, and hence must be fast. It receives a  $\langle property\ list \rangle$ , a  $\langle key \rangle$ , a  $\langle true\ code \rangle$  and a  $\langle false\ code \rangle$ . The aim is to split the  $\langle property\ list \rangle$  at the given  $\langle key \rangle$  into the  $\langle extract_1 \rangle$  before the key–value pair, the  $\langle value \rangle$  associated with the  $\langle key \rangle$  and the  $\langle extract_2 \rangle$  after the key–value pair. This is done using a delimited function, whose definition is as follows, where the  $\langle key \rangle$  is turned into a string.

```
\cs_set:Npn \__prop_split_aux:w #1
\__prop_pair:wn \langle key \rangle \s__prop #2
#3 \q_mark #4 #5 \q_stop
{ #4 { \langle true code \rangle } { \langle false code \rangle } }
```

If the  $\langle key \rangle$  is present in the property list, `\__prop_split_aux:w`'s #1 is the part before the  $\langle key \rangle$ , #2 is the  $\langle value \rangle$ , #3 is the part after the  $\langle key \rangle$ , #4 is `\use_i:nn`, and #5 is additional tokens that we do not care about. The  $\langle true\ code \rangle$  is left in the input stream, and can use the parameters #1, #2, #3 for the three parts of the property list as desired. Namely, the original property list is in this case #1 `\__prop_pair:wn \langle key \rangle \s__prop {#2} #3`.

If the  $\langle key \rangle$  is not there, then the  $\langle function \rangle$  is `\use_ii:nn`, which keeps the  $\langle false\ code \rangle$ .

```
7332 \cs_new_protected:Npn \__prop_split:NnTF #1#2
7333 { \exp_args:NNo \__prop_split_aux:NnTF #1 { \tl_to_str:n {#2} } }
7334 \cs_new_protected:Npn \__prop_split_aux:NnTF #1#2#3#4
7335 {
7336   \cs_set:Npn \__prop_split_aux:w ##1
7337     \__prop_pair:wn #2 \s__prop ##2 ##3 \q_mark ##4 ##5 \q_stop
7338     { ##4 {#3} {#4} }
7339   \exp_after:wN \__prop_split_aux:w #1 \q_mark \use_i:nn
7340   \__prop_pair:wn #2 \s__prop { } \q_mark \use_ii:nn \q_stop
7341 }
7342 \cs_new:Npn \__prop_split_aux:w { }
```

(End definition for `\__prop_split:NnTF`, `\__prop_split_aux:NnTF`, and `\__prop_split_aux:w`.)

`\prop_remove:Nn`  
`\prop_remove:NV`  
`\prop_remove:cn`  
`\prop_remove:cV`  
`\prop_gremove:Nn`  
`\prop_gremove:NV`  
`\prop_gremove:cn`  
`\prop_gremove:cV`

Deleting from a property starts by splitting the list. If the key is present in the property list, the returned value is ignored. If the key is missing, nothing happens.

```
7343 \cs_new_protected:Npn \prop_remove:Nn #1#2
7344 {
7345   \__prop_split:NnTF #1 {#2}
7346   { \tl_set:Nn #1 { ##1 ##3 } }
7347   { }
7348 }
7349 \cs_new_protected:Npn \prop_gremove:Nn #1#2
7350 {
7351   \__prop_split:NnTF #1 {#2}
7352   { \tl_gset:Nn #1 { ##1 ##3 } }
7353   { }
7354 }
7355 \cs_generate_variant:Nn \prop_remove:Nn { NV }
7356 \cs_generate_variant:Nn \prop_remove:Nn { c , cV }
7357 \cs_generate_variant:Nn \prop_gremove:Nn { NV }
7358 \cs_generate_variant:Nn \prop_gremove:Nn { c , cV }
```

(End definition for `\prop_remove:Nn` and `\prop_gremove:Nn`. These functions are documented on page 124.)

**`\prop_get:NnN`** Getting an item from a list is very easy: after splitting, if the key is in the property list, just set the token list variable to the return value, otherwise to `\q_no_value`.

```
\prop_get:NVN
\prop_get:NoN
\prop_get:cnN
\prop_get:cVN
\prop_get:coN
7359 \cs_new_protected:Npn \prop_get:NnN #1#2#3
7360 {
7361   \__prop_split:NnTF #1 {#2}
7362   { \tl_set:Nn #3 {##2} }
7363   { \tl_set:Nn #3 { \q_no_value } }
7364 }
7365 \cs_generate_variant:Nn \prop_get:NnN { NV , No }
7366 \cs_generate_variant:Nn \prop_get:NnN { c , cV , co }
```

(End definition for `\prop_get:NnN`. This function is documented on page 123.)

**`\prop_pop:NnN`** Popping a value also starts by doing the split. If the key is present, save the value in the token list and update the property list as when deleting. If the key is missing, save `\q_no_value` in the token list.

```
\prop_pop:NoN
\prop_pop:cnN
\prop_pop:coN
7367 \cs_new_protected:Npn \prop_pop:NnN #1#2#3
7368 {
7369   \__prop_split:NnTF #1 {#2}
7370   {
7371     \tl_set:Nn #3 {##2}
7372     \tl_set:Nn #1 { ##1 ##3 }
7373   }
7374   { \tl_set:Nn #3 { \q_no_value } }
7375 }
7376 \cs_new_protected:Npn \prop_gpop:NnN #1#2#3
7377 {
7378   \__prop_split:NnTF #1 {#2}
7379   {
7380     \tl_set:Nn #3 {##2}
7381     \tl_gset:Nn #1 { ##1 ##3 }
7382   }
7383   { \tl_set:Nn #3 { \q_no_value } }
7384 }
7385 \cs_generate_variant:Nn \prop_pop:NnN { No }
7386 \cs_generate_variant:Nn \prop_pop:NnN { c , co }
7387 \cs_generate_variant:Nn \prop_gpop:NnN { No }
7388 \cs_generate_variant:Nn \prop_gpop:NnN { c , co }
```

(End definition for `\prop_pop:NnN` and `\prop_gpop:NnN`. These functions are documented on page 123.)

**`\prop_item:Nn`** Getting the value corresponding to a key in a property list in an expandable fashion is similar to mapping some tokens. Go through the property list one `⟨key⟩–⟨value⟩` pair at a time: the arguments of `\__prop_item_Nn:nwn` are the `⟨key⟩` we are looking for, a `⟨key⟩` of the property list, and its associated value. The `⟨keys⟩` are compared (as strings). If they match, the `⟨value⟩` is returned, within `\exp_not:n`. The loop terminates even if the `⟨key⟩` is missing, and yields an empty value, because we have appended the appropriate `⟨key⟩–⟨empty value⟩` pair to the property list.

```
\prop_item:cn
\__prop_item_Nn:nwn
7389 \cs_new:Npn \prop_item:Nn #1#2
7390 {
7391   \exp_last_unbraced:Noo \__prop_item_Nn:nwn { \tl_to_str:n {#2} } #1
```

```

7392     \__prop_pair:wn \tl_to_str:n {#2} \s__prop { }
7393     \__prg_break_point:
7394   }
7395   \cs_new:Npn \__prop_item:Nn:nwn #1#2 \__prop_pair:wn #3 \s__prop #4
7396   {
7397     \str_if_eq_x:nnTF {#1} {#3}
7398     { \__prg_break:n { \exp_not:n {#4} } }
7399     { \__prop_item:Nn:nwn {#1} }
7400   }
7401   \cs_generate_variant:Nn \prop_item:Nn { c }

```

(End definition for `\prop_item:Nn` and `\__prop_item:Nn:nwn`. These functions are documented on page 124.)

**`\prop_pop:NnTF`** Popping an item from a property list, keeping track of whether the key was present or not, is implemented as a conditional. If the key was missing, neither the property list, nor the token list are altered. Otherwise, `\prg_return_true:` is used after the assignments.  
**`\prop_pop:cnNTF`**  
**`\prop_gpop:NnTF`**  
**`\prop_gpop:cnNTF`**

```

7402   \prg_new_protected_conditional:Npnn \prop_pop:NnN #1#2#3 { T , F , TF }
7403   {
7404     \__prop_split:NnTF #1 {#2}
7405     {
7406       \tl_set:Nn #3 {##2}
7407       \tl_set:Nn #1 { ##1 ##3 }
7408       \prg_return_true:
7409     }
7410     { \prg_return_false: }
7411   }
7412   \prg_new_protected_conditional:Npnn \prop_gpop:NnN #1#2#3 { T , F , TF }
7413   {
7414     \__prop_split:NnTF #1 {#2}
7415     {
7416       \tl_set:Nn #3 {##2}
7417       \tl_gset:Nn #1 { ##1 ##3 }
7418       \prg_return_true:
7419     }
7420     { \prg_return_false: }
7421   }
7422   \cs_generate_variant:Nn \prop_pop:NnNT { c }
7423   \cs_generate_variant:Nn \prop_pop:NnNF { c }
7424   \cs_generate_variant:Nn \prop_pop:NnNTF { c }
7425   \cs_generate_variant:Nn \prop_gpop:NnNT { c }
7426   \cs_generate_variant:Nn \prop_gpop:NnNF { c }
7427   \cs_generate_variant:Nn \prop_gpop:NnNTF { c }

```

(End definition for `\prop_pop:NnNTF` and `\prop_gpop:NnNTF`. These functions are documented on page 125.)

**`\prop_put:Nnn`** Since the branches of `\__prop_split:NnTF` are used as the replacement text of an internal macro, and since the `<key>` and new `<value>` may contain arbitrary tokens, it is not safe to include them in the argument of `\__prop_split:NnTF`. We thus start by storing in `\l__prop_internal_tl` tokens which (after x-expansion) encode the key–value pair. This variable can safely be used in `\__prop_split:NnTF`. If the `<key>` was absent, append the new key–value to the list. Otherwise concatenate the extracts `##1` and `##3` with the new

`\prop_put:Nnn`  
`\prop_put:NnV`  
`\prop_put:Nno`  
`\prop_put:Nnx`  
`\prop_put:NvN`  
`\prop_put:NVV`  
`\prop_put:Nnn`  
`\prop_put:Noo`  
`\prop_put:cn`  
`\prop_put:cnV`  
`\prop_put:cno`  
`\prop_put:cnx`  
`\prop_put:cVn`  
`\prop_put:cVV`  
`\prop_put:con`  
`\prop_put:coo`  
`\prop_gput:Nnn`

key-value pair `\l__prop_internal_tl`. The updated entry is placed at the same spot as the original  $\langle key \rangle$  in the property list, preserving the order of entries.

```

7428 \cs_new_protected:Npn \prop_put:Nnn { \__prop_put:NNnn \tl_set:Nx }
7429 \cs_new_protected:Npn \prop_gput:Nnn { \__prop_put:NNnn \tl_gset:Nx }
7430 \cs_new_protected:Npn \__prop_put:NNnn #1#2#3#4
7431 {
7432   \tl_set:Nn \l__prop_internal_tl
7433   {
7434     \exp_not:N \__prop_pair:wn \tl_to_str:n {#3}
7435     \s__prop { \exp_not:n {#4} }
7436   }
7437   \__prop_split:NnTF #2 {#3}
7438   { #1 #2 { \exp_not:n {##1} \l__prop_internal_tl \exp_not:n {##3} } }
7439   { #1 #2 { \exp_not:o {#2} \l__prop_internal_tl } }
7440 }
7441 \cs_generate_variant:Nn \prop_put:Nnn
7442 { NnV , Nno , Nnx , NV , NVV , No , Noo }
7443 \cs_generate_variant:Nn \prop_put:Nnn
7444 { c , cnV , cno , cnx , cV , cVV , co , coo }
7445 \cs_generate_variant:Nn \prop_gput:Nnn
7446 { NnV , Nno , Nnx , NV , NVV , No , Noo }
7447 \cs_generate_variant:Nn \prop_gput:Nnn
7448 { c , cnV , cno , cnx , cV , cVV , co , coo }

```

(End definition for `\prop_put:Nnn`, `\prop_gput:Nnn`, and `\__prop_put:NNnn`. These functions are documented on page 123.)

<pre> \prop_put_if_new:Nnn \prop_put_if_new:cnn \prop_gput_if_new:Nnn \prop_gput_if_new:cnn \__prop_put_if_new:NNnn </pre>	<p>Adding conditionally also splits. If the key is already present, the three brace groups given by <code>\__prop_split:NnTF</code> are removed. If the key is new, then the value is added, being careful to convert the key to a string using <code>\tl_to_str:n</code>.</p> <pre> 7449 \cs_new_protected:Npn \prop_put_if_new:Nnn 7450 { \__prop_put_if_new:NNnn \tl_set:Nx } 7451 \cs_new_protected:Npn \prop_gput_if_new:Nnn 7452 { \__prop_put_if_new:NNnn \tl_gset:Nx } 7453 \cs_new_protected:Npn \__prop_put_if_new:NNnn #1#2#3#4 7454 { 7455   \tl_set:Nn \l__prop_internal_tl 7456   { 7457     \exp_not:N \__prop_pair:wn \tl_to_str:n {#3} 7458     \s__prop \exp_not:n {#4} 7459   } 7460   \__prop_split:NnTF #2 {#3} 7461   { } 7462   { #1 #2 { \exp_not:o {#2} \l__prop_internal_tl } } 7463 } 7464 \cs_generate_variant:Nn \prop_put_if_new:Nnn { c } 7465 \cs_generate_variant:Nn \prop_gput_if_new:Nnn { c } </pre>
--	--

(End definition for `\prop_put_if_new:Nnn`, `\prop_gput_if_new:Nnn`, and `\__prop_put_if_new:NNnn`. These functions are documented on page 123.)

### 15.3 Property list conditionals

<pre> \prop_if_exist_p:N \prop_if_exist_p:c \prop_if_exist:NTF \prop_if_exist:cTF </pre>	<p>Copies of the <code>cs</code> functions defined in <code>l3basics</code>.</p>
--	--

```

7466 \prg_new_eq_conditional:Nnn \prop_if_exist:N \cs_if_exist:N
7467   { TF , T , F , p }
7468 \prg_new_eq_conditional:Nnn \prop_if_exist:c \cs_if_exist:c
7469   { TF , T , F , p }

```

(End definition for `\prop_if_exist:N`. This function is documented on page 124.)

```

\prop_if_empty_p:N Same test as for token lists.
\prop_if_empty_p:c 7470 \prg_new_conditional:Npnn \prop_if_empty:N #1 { p , T , F , TF }
\prop_if_empty:NTF 7471 {
\prop_if_empty:cTF 7472   \tl_if_eq:NNTF #1 \c_empty_prop
7473   \prg_return_true: \prg_return_false:
7474 }
7475 \cs_generate_variant:Nn \prop_if_empty_p:N { c }
7476 \cs_generate_variant:Nn \prop_if_empty:N { NT }
7477 \cs_generate_variant:Nn \prop_if_empty:N { NF }
7478 \cs_generate_variant:Nn \prop_if_empty:N { NTF }

```

(End definition for `\prop_if_empty:N`. This function is documented on page 124.)

```

\prop_if_in_p:Nn Testing expandably if a key is in a property list requires to go through the key–value
\prop_if_in_p:Nv pairs one by one. This is rather slow, and a faster test would be
\prop_if_in_p:No
\prop_if_in_p:cn \prg_new_protected_conditional:Npnn \prop_if_in:Nn #1 #2
\prop_if_in_p:cV {
\prop_if_in_p:co   \@@_split:NnTF #1 {#2}
\prop_if_in:NnTF   { \prg_return_true: }
\prop_if_in:NvTF   { \prg_return_false: }
\prop_if_in:NoTF   }
\prop_if_in:cnTF
\prop_if_in:cVTF
\prop_if_in:coTF
\__prop_if_in:nwnn
\__prop_if_in:N

```

but `\__prop_split:NnTF` is non-expandable.

Instead, the key is compared to each key in turn using `\str_if_eq_x:nn`, which is expandable. To terminate the mapping, we append to the property list the key that is searched for. This second `\tl_to_str:n` is not expanded at the start, but only when included in the `\str_if_eq_x:nn`. It cannot make the breaking mechanism choke, because the arbitrary token list material is enclosed in braces. The second argument of `\__prop_if_in:nwnn` is most often empty. When the *key* is found in the list, `\__prop_if_in:N` receives `\__prop_pair:wn`, and if it is found as the extra item, the function receives `\q_recursion_tail`, easily recognizable.

Here, `\prop_map_function:NN` is not sufficient for the mapping, since it can only map a single token, and cannot carry the key that is searched for.

```

7479 \prg_new_conditional:Npnn \prop_if_in:Nn #1#2 { p , T , F , TF }
7480 {
7481   \exp_last_unbraced:Noo \__prop_if_in:nwnn { \tl_to_str:n {#2} } #1
7482   \__prop_pair:wn \tl_to_str:n {#2} \s_prop { }
7483   \q_recursion_tail
7484   \__prg_break_point:
7485 }
7486 \cs_new:Npn \__prop_if_in:nwnn #1#2 \__prop_pair:wn #3 \s_prop #4
7487 {
7488   \str_if_eq_x:nnTF {#1} {#3}
7489   { \__prop_if_in:N }
7490   { \__prop_if_in:nwnn {#1} }

```



```

7491 }
7492 \cs_new:Npn \__prop_if_in:N #1
7493 {
7494   \if_meaning:w \q_recursion_tail #1
7495   \prg_return_false:
7496   \else:
7497     \prg_return_true:
7498   \fi:
7499   \__prg_break:
7500 }
7501 \cs_generate_variant:Nn \prop_if_in_p:Nn { NV , No }
7502 \cs_generate_variant:Nn \prop_if_in_p:Nn { c , cV , co }
7503 \cs_generate_variant:Nn \prop_if_in:NnT { NV , No }
7504 \cs_generate_variant:Nn \prop_if_in:NnT { c , cV , co }
7505 \cs_generate_variant:Nn \prop_if_in:NnF { NV , No }
7506 \cs_generate_variant:Nn \prop_if_in:NnF { c , cV , co }
7507 \cs_generate_variant:Nn \prop_if_in:NnTF { NV , No }
7508 \cs_generate_variant:Nn \prop_if_in:NnTF { c , cV , co }

```

(End definition for `\prop_if_in:NnTF`, `\__prop_if_in:nwn`, and `\__prop_if_in:N`. These functions are documented on page 124.)

## 15.4 Recovering values from property lists with branching

`\prop_get:NnTF` Getting the value corresponding to a key, keeping track of whether the key was present or not, is implemented as a conditional (with side effects). If the key was absent, the token list is not altered.

```

\prop_get:NnTF
\prop_get:NvNTF
\prop_get:NnNTF
\prop_get:cnNTF
\prop_get:cVNTF
\prop_get:coNTF
7509 \prg_new_protected_conditional:Npnn \prop_get:NnN #1#2#3 { T , F , TF }
7510 {
7511   \__prop_split:NnTF #1 {#2}
7512   {
7513     \tl_set:Nn #3 {##2}
7514     \prg_return_true:
7515   }
7516   { \prg_return_false: }
7517 }
7518 \cs_generate_variant:Nn \prop_get:NnNT { NV , No }
7519 \cs_generate_variant:Nn \prop_get:NnNF { NV , No }
7520 \cs_generate_variant:Nn \prop_get:NnNTF { NV , No }
7521 \cs_generate_variant:Nn \prop_get:NnNT { c , cV , co }
7522 \cs_generate_variant:Nn \prop_get:NnNF { c , cV , co }
7523 \cs_generate_variant:Nn \prop_get:NnNTF { c , cV , co }

```

(End definition for `\prop_get:NnNTF`. This function is documented on page 125.)

## 15.5 Mapping to property lists

`\prop_map_function:NN` The fastest way to do a recursion here is to use an `\if_meaning:w` test: the keys are strings, and thus cannot match the marker `\q_recursion_tail`. A special case to note is when the key #3 is empty: then `\q_recursion_tail` is compared to `\exp_after:wN`, also different. Note that #2 is empty, except at the first iteration, where it is `\s__prop`.

```

\__prop_map_function:Nwn
7524 \cs_new:Npn \prop_map_function:NN #1#2
7525 {
7526   \exp_last_unbraced:NNo \__prop_map_function:Nwn #2 #1

```

```

7527     \__prop_pair:wn \q_recursion_tail \s__prop { }
7528     \__prg_break_point:Nn \prop_map_break: { }
7529   }
7530 \cs_new:Npn \__prop_map_function:Nwwn #1#2 \__prop_pair:wn #3 \s__prop #4
7531 {
7532   \if_meaning:w \q_recursion_tail #3
7533   \exp_after:wN \prop_map_break:
7534   \fi:
7535   #1 {#3} {#4}
7536   \__prop_map_function:Nwwn #1
7537 }
7538 \cs_generate_variant:Nn \prop_map_function:NN { Nc }
7539 \cs_generate_variant:Nn \prop_map_function:NN { c , cc }

```

(End definition for `\prop_map_function:NN` and `\__prop_map_function:Nwwn`. These functions are documented on page 125.)

**`\prop_map_inline:Nn`** Mapping in line requires a nesting level counter. Store the current definition of `\__prop_pair:wn`, and define it anew. At the end of the loop, revert to the earlier definition. Note that besides pairs of the form `\__prop_pair:wn <key> \s__prop {<value>}`, there are a leading and a trailing tokens, but both are equal to `\scan_stop:`, hence have no effect in such inline mapping. Such `\scan_stop:` could have affected ligatures if they appeared during the mapping.

**`\prop_map_inline:cn`**

```

7540 \cs_new_protected:Npn \prop_map_inline:Nn #1#2
7541 {
7542   \cs_gset_eq:cn
7543   { \__prg_map_ \int_use:N \g__prg_map_int :wn } \__prop_pair:wn
7544   \int_gincr:N \g__prg_map_int
7545   \cs_gset_protected:Npn \__prop_pair:wn ##1 \s__prop ##2 {#2}
7546   #1
7547   \__prg_break_point:Nn \prop_map_break:
7548   {
7549     \int_gdecr:N \g__prg_map_int
7550     \cs_gset_eq:Nc \__prop_pair:wn
7551     { \__prg_map_ \int_use:N \g__prg_map_int :wn }
7552   }
7553 }
7554 \cs_generate_variant:Nn \prop_map_inline:Nn { c }

```

(End definition for `\prop_map_inline:Nn`. This function is documented on page 125.)

**`\prop_map_break:`** The break statements are based on the general `\__prg_map_break:Nn`.

**`\prop_map_break:n`**

```

7555 \cs_new:Npn \prop_map_break:
7556 { \__prg_map_break:Nn \prop_map_break: { } }
7557 \cs_new:Npn \prop_map_break:n
7558 { \__prg_map_break:Nn \prop_map_break: }

```

(End definition for `\prop_map_break:` and `\prop_map_break:n`. These functions are documented on page 126.)

## 15.6 Viewing property lists

**`\prop_show:N`** Apply the general `\__msg_show_variable:NNNnn`. Contrarily to sequences and comma lists, we use `\__msg_show_item:nn` to format both the key and the value for each pair.

**`\prop_show:c`**

```

7559 \cs_new_protected:Npn \prop_show:N #1
7560 {
7561   \__msg_show_variable:NNNnn #1
7562   \prop_if_exist:NTF \prop_if_empty:NTF { prop }
7563   { \prop_map_function:NN #1 \__msg_show_item:nn }
7564 }
7565 \cs_generate_variant:Nn \prop_show:N { c }

```

(End definition for `\prop_show:N`. This function is documented on page 126.)

**`\prop_log:N`** Redirect output of `\prop_show:N` to the log.

```

\prop_log:c 7566 \cs_new_protected:Npn \prop_log:N
7567 { \__msg_log_next: \prop_show:N }
7568 \cs_generate_variant:Nn \prop_log:N { c }

```

(End definition for `\prop_log:N`. This function is documented on page 126.)

```

7569 </initex | package>

```

## 16 l3msg implementation

```

7570 <*initex | package>

```

```

7571 <@@=msg>

```

**`\l_msg_internal_tl`** A general scratch for the module.

```

7572 \tl_new:N \l_msg_internal_tl

```

(End definition for `\l_msg_internal_tl`.)

**`\l_msg_line_context_bool`** Controls whether the line context is shown as part of the decoration of all (non-expandable) messages.

```

7573 \bool_new:N \l_msg_line_context_bool

```

(End definition for `\l_msg_line_context_bool`.)

### 16.1 Creating messages

Messages are created and used separately, so there two parts to the code here. First, a mechanism for creating message text. This is pretty simple, as there is not actually a lot to do.

```

\c_msg_text_prefix_tl  Locations for the text of messages.
\c_msg_more_text_prefix_tl 7574 \tl_const:Nn \c_msg_text_prefix_tl { msg~text~>~ }
7575 \tl_const:Nn \c_msg_more_text_prefix_tl { msg~extra~text~>~ }

```

(End definition for `\c_msg_text_prefix_tl` and `\c_msg_more_text_prefix_tl`.)

**`\msg_if_exist:p:nn`** Test whether the control sequence containing the message text exists or not.

```

\msg_if_exist:nnTF 7576 \prg_new_conditional:Npnn \msg_if_exist:nn #1#2 { p , T , F , TF }
7577 {
7578   \cs_if_exist:cTF { \c_msg_text_prefix_tl #1 / #2 }
7579   { \prg_return_true: } { \prg_return_false: }
7580 }

```

(End definition for `\msg_if_exist:nnTF`. This function is documented on page 129.)

`\__chk_if_free_msg:nn` This auxiliary is similar to `\__chk_if_free_cs:N`, and is used when defining messages with `\msg_new:nnnn`.

```

7581 \__debug_patch:nnNw { }
7582 { \__debug_log:x { Defining~message~ #1 / #2 ~\msg_line_context: } }
7583 \cs_new_protected:Npn \__chk_if_free_msg:nn #1#2
7584 {
7585     \msg_if_exist:nnT {#1} {#2}
7586     {
7587         \__msg_kernel_error:nxxx { kernel } { message-already-defined }
7588         {#1} {#2}
7589     }
7590 }
```

(End definition for `\__chk_if_free_msg:nn`.)

`\msg_new:nnnn` Setting a message simply means saving the appropriate text into two functions. A sanity check first.

```

\msg_new:nnn
\msg_gset:nnnn
\msg_gset:nnn
\msg_set:nnnn
\msg_set:nnn
7591 \cs_new_protected:Npn \msg_new:nnnn #1#2
7592 {
7593     \__chk_if_free_msg:nn {#1} {#2}
7594     \msg_gset:nnnn {#1} {#2}
7595 }
7596 \cs_new_protected:Npn \msg_new:nnn #1#2#3
7597 { \msg_new:nnnn {#1} {#2} {#3} { } }
7598 \cs_new_protected:Npn \msg_set:nnnn #1#2#3#4
7599 {
7600     \cs_set:cpn { \c__msg_text_prefix_tl #1 / #2 }
7601     ##1##2##3##4 {#3}
7602     \cs_set:cpn { \c__msg_more_text_prefix_tl #1 / #2 }
7603     ##1##2##3##4 {#4}
7604 }
7605 \cs_new_protected:Npn \msg_set:nnn #1#2#3
7606 { \msg_set:nnnn {#1} {#2} {#3} { } }
7607 \cs_new_protected:Npn \msg_gset:nnnn #1#2#3#4
7608 {
7609     \cs_gset:cpn { \c__msg_text_prefix_tl #1 / #2 }
7610     ##1##2##3##4 {#3}
7611     \cs_gset:cpn { \c__msg_more_text_prefix_tl #1 / #2 }
7612     ##1##2##3##4 {#4}
7613 }
7614 \cs_new_protected:Npn \msg_gset:nnn #1#2#3
7615 { \msg_gset:nnnn {#1} {#2} {#3} { } }
```

(End definition for `\msg_new:nnnn` and others. These functions are documented on page 128.)

## 16.2 Messages: support functions and text

`\c__msg_coding_error_text_tl` Simple pieces of text for messages.

```

\c__msg_continue_text_tl 7616 \tl_const:Nn \c__msg_coding_error_text_tl
\c__msg_critical_text_tl 7617 {
\c__msg_fatal_text_tl    7618     This~is~a~coding~error.
\c__msg_help_text_tl     7619     \ \ \
\c__msg_no_info_text_tl  7620 }
\c__msg_on_line_text_tl  7621 \tl_const:Nn \c__msg_continue_text_tl
\c__msg_return_text_tl
\c__msg_trouble_text_tl
```

```

7622 { Type~<return>~to~continue }
7623 \tl_const:Nn \c__msg_critical_text_tl
7624 { Reading~the~current~file~'\g_file_curr_name_str'~will~stop. }
7625 \tl_const:Nn \c__msg_fatal_text_tl
7626 { This~is~a~fatal~error:~LaTeX~will~abort. }
7627 \tl_const:Nn \c__msg_help_text_tl
7628 { For~immediate~help~type~H~<return> }
7629 \tl_const:Nn \c__msg_no_info_text_tl
7630 {
7631     LaTeX~does~not~know~anything~more~about~this~error,~sorry.
7632     \c__msg_return_text_tl
7633 }
7634 \tl_const:Nn \c__msg_on_line_text_tl { on~line }
7635 \tl_const:Nn \c__msg_return_text_tl
7636 {
7637     \\ \\
7638     Try~typing~<return>~to~proceed.
7639     \\
7640     If~that~doesn't~work,~type~X~<return>~to~quit.
7641 }
7642 \tl_const:Nn \c__msg_trouble_text_tl
7643 {
7644     \\ \\
7645     More~errors~will~almost~certainly~follow: \\
7646     the~LaTeX~run~should~be~aborted.
7647 }

```

(End definition for `\c__msg_coding_error_text_tl` and others.)

`\msg_line_number:` For writing the line number nicely. `\msg_line_context:` was set up earlier, so this is not new.

```

7648 \cs_new:Npn \msg_line_number: { \int_use:N \tex_inputlineno:D }
7649 \cs_gset:Npn \msg_line_context:
7650 {
7651     \c__msg_on_line_text_tl
7652     \c_space_tl
7653     \msg_line_number:
7654 }

```

(End definition for `\msg_line_number:` and `\msg_line_context:`. These functions are documented on page 129.)

## 16.3 Showing messages: low level mechanism

`\msg_interrupt:nnn` The low-level interruption macro is rather opaque, unfortunately. Depending on the availability of more information there is a choice of how to set up the further help. We feed the extra help text and the message itself to a wrapping auxiliary, in this order because we must first setup TeX's `\errhelp` register before issuing an `\errmessage`.

```

7655 \cs_new_protected:Npn \msg_interrupt:nnn #1#2#3
7656 {
7657     \tl_if_empty:nTF {#3}
7658     {
7659         \__msg_interrupt_wrap:nn { \\ \c__msg_no_info_text_tl }
7660         {#1 \\ \\ #2 \\ \\ \c__msg_continue_text_tl }

```

```

7661     }
7662     {
7663         \_msg_interrupt_wrap:nn { \ #3 }
7664         {#1 \\\ #2 \\\ \c__msg_help_text_tl }
7665     }
7666 }

```

(End definition for `\msg_interrupt:nnn`. This function is documented on page 133.)

```

\_msg_interrupt_wrap:nn
\_msg_interrupt_more_text:n

```

First setup TeX's `\errhelp` register with the extra help #1, then build a nice-looking error message with #2. Everything is done using x-type expansion as the new line markers are different for the two type of text and need to be correctly set up. The auxiliary `\_msg_interrupt_more_text:n` receives its argument as a line-wrapped string, which is thus unaffected by expansion.

```

7667 \cs_new_protected:Npn \_msg_interrupt_wrap:nn #1#2
7668 {
7669     \iow_wrap:nnnN {#1} { | ~ } { } \_msg_interrupt_more_text:n
7670     \iow_wrap:nnnN {#2} { ! ~ } { } \_msg_interrupt_text:n
7671 }
7672 \cs_new_protected:Npn \_msg_interrupt_more_text:n #1
7673 {
7674     \exp_args:Nx \tex_errhelp:D
7675     {
7676         |,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
7677         #1 \iow_newline:
7678         |.....
7679     }
7680 }

```

(End definition for `\_msg_interrupt_wrap:nn` and `\_msg_interrupt_more_text:n`.)

```

\_msg_interrupt_text:n

```

The business end of the process starts by producing some visual separation of the message from the main part of the log. The error message needs to be printed with everything made “invisible”: TeX's own information involves the macro in which `\errmessage` is called, and the end of the argument of the `\errmessage`, including the closing brace. We use an active `!` to call the `\errmessage` primitive, and end its argument with `\use_none:n {<dots>}` which fills the output with dots. Two trailing closing braces are turned into spaces to hide them as well. The group in which we alter the definition of the active `!` is closed before producing the message: this ensures that tokens inserted by typing `I` in the command-line are inserted after the message is entirely cleaned up.

The `\_iow_with:Nnn` auxiliary, defined in `l3file`, expects an *<integer variable>*, an integer *<value>*, and some *<code>*. It runs the *<code>* after ensuring that the *<integer variable>* takes the given *<value>*, then restores the former value of the *<integer variable>* if needed. We use it to ensure that the `\newlinechar` is 10, as needed for `\iow_newline:` to work, and that `\errorcontextlines` is `-1`, to avoid showing irrelevant context. Note that restoring the former value of these integers requires inserting tokens after the `\errmessage`, which go in the way of tokens which could be inserted by the user. This is unavoidable.

```

7681 \group_begin:
7682   \char_set_lccode:nn {'\} {'\ }
7683   \char_set_lccode:nn {'\} {'\ }
7684   \char_set_lccode:nn {'\&} {'\!}
7685   \char_set_catcode_active:N \&

```

```

7686 \tex_lowercase:D
7687 {
7688   \group_end:
7689   \cs_new_protected:Npn \__msg_interrupt_text:n #1
7690   {
7691     \iow_term:x
7692     {
7693       \iow_newline:
7694       !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
7695       \iow_newline:
7696       !
7697     }
7698     \__iow_with:Nnn \tex_newlinechar:D { '\^^J }
7699     {
7700       \__iow_with:Nnn \tex_errorcontextlines:D { -1 }
7701       {
7702         \group_begin:
7703         \cs_set_protected:Npn &
7704         {
7705           \tex_errmessage:D
7706           {
7707             #1
7708             \use_none:n
7709             { ..... }
7710           }
7711         }
7712         \exp_after:wN
7713         \group_end:
7714         &
7715       }
7716     }
7717   }
7718 }

```

(End definition for \\_\_msg\_interrupt\_text:n.)

**\msg\_log:n** Printing to the log or terminal without a stop is rather easier. A bit of simple visual  
**\msg\_term:n** work sets things off nicely.

```

7719 \cs_new_protected:Npn \msg_log:n #1
7720 {
7721   \iow_log:n { ..... }
7722   \iow_wrap:nnnN { . ~ #1 } { . ~ } { } \iow_log:n
7723   \iow_log:n { ..... }
7724 }
7725 \cs_new_protected:Npn \msg_term:n #1
7726 {
7727   \iow_term:n { ***** }
7728   \iow_wrap:nnnN { * ~ #1 } { * ~ } { } \iow_term:n
7729   \iow_term:n { ***** }
7730 }

```

(End definition for \msg\_log:n and \msg\_term:n. These functions are documented on page 134.)

## 16.4 Displaying messages

L<sup>A</sup>T<sub>E</sub>X is handling error messages and so the T<sub>E</sub>X ones are disabled. This is already done by the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> kernel, so to avoid messing up any deliberate change by a user this is only set in format mode.

```
7731 <*initex>
7732 \int_gset:Nn \tex_errorcontextlines:D { -1 }
7733 </initex>
```

`\msg_fatal_text:n` A function for issuing messages: both the text and order could in principle vary.

```
\msg_critical_text:n 7734 \cs_new:Npn \msg_fatal_text:n #1
\msg_error_text:n    7735 {
\msg_warning_text:n 7736   Fatal~#1~error
\msg_info_text:n     7737   \bool_if:NT \l__msg_line_context_bool { ~ \msg_line_context: }
7738 }
7739 \cs_new:Npn \msg_critical_text:n #1
7740 {
7741   Critical~#1~error
7742   \bool_if:NT \l__msg_line_context_bool { ~ \msg_line_context: }
7743 }
7744 \cs_new:Npn \msg_error_text:n #1
7745 {
7746   #1~error
7747   \bool_if:NT \l__msg_line_context_bool { ~ \msg_line_context: }
7748 }
7749 \cs_new:Npn \msg_warning_text:n #1
7750 {
7751   #1~warning
7752   \bool_if:NT \l__msg_line_context_bool { ~ \msg_line_context: }
7753 }
7754 \cs_new:Npn \msg_info_text:n #1
7755 {
7756   #1~info
7757   \bool_if:NT \l__msg_line_context_bool { ~ \msg_line_context: }
7758 }
```

(End definition for `\msg_fatal_text:n` and others. These functions are documented on page 129.)

`\msg_see_documentation_text:n` Contextual footer information. The L<sup>A</sup>T<sub>E</sub>X module only comprises L<sup>A</sup>T<sub>E</sub>X3 code, so we refer to the L<sup>A</sup>T<sub>E</sub>X3 documentation rather than simply “L<sup>A</sup>T<sub>E</sub>X”.

```
7759 \cs_new:Npn \msg_see_documentation_text:n #1
7760 {
7761   \ \ \ See~the~
7762   \str_if_eq:nnTF {#1} { LaTeX } { LaTeX3 } {#1} ~
7763   documentation~for~further~information.
7764 }
```

(End definition for `\msg_see_documentation_text:n`. This function is documented on page 130.)

`\__msg_class_new:nn`

```
7765 \group_begin:
7766 \cs_set_protected:Npn \__msg_class_new:nn #1#2
7767 {
7768   \prop_new:c { l__msg_redirect_ #1 _prop }
```



```

7769 \cs_new_protected:cpn { __msg_ #1 _code:nnnnnn }
7770   ##1##2##3##4##5##6 {#2}
7771 \cs_new_protected:cpn { msg_ #1 :nnnnnn } ##1##2##3##4##5##6
7772 {
7773   \use:x
7774   {
7775     \exp_not:n { \_msg_use:nnnnnn {#1} {##1} {##2} }
7776     { \tl_to_str:n {##3} } { \tl_to_str:n {##4} }
7777     { \tl_to_str:n {##5} } { \tl_to_str:n {##6} }
7778   }
7779 }
7780 \cs_new_protected:cpx { msg_ #1 :nnnnn } ##1##2##3##4##5
7781 { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} {##5} { } }
7782 \cs_new_protected:cpx { msg_ #1 :nnnn } ##1##2##3##4
7783 { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} { } { } }
7784 \cs_new_protected:cpx { msg_ #1 :nnn } ##1##2##3
7785 { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} {##3} { } { } { } }
7786 \cs_new_protected:cpx { msg_ #1 :nn } ##1##2
7787 { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} { } { } { } { } }
7788 \cs_new_protected:cpx { msg_ #1 :nnxxx } ##1##2##3##4##5##6
7789 {
7790   \use:x
7791   {
7792     \exp_not:N \exp_not:n
7793     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} }
7794     {##3} {##4} {##5} {##6}
7795   }
7796 }
7797 \cs_new_protected:cpx { msg_ #1 :nnxxx } ##1##2##3##4##5
7798 { \exp_not:c { msg_ #1 :nnxxx } {##1} {##2} {##3} {##4} {##5} { } }
7799 \cs_new_protected:cpx { msg_ #1 :nnxx } ##1##2##3##4
7800 { \exp_not:c { msg_ #1 :nnxxx } {##1} {##2} {##3} {##4} { } { } }
7801 \cs_new_protected:cpx { msg_ #1 :nnx } ##1##2##3
7802 { \exp_not:c { msg_ #1 :nnxxx } {##1} {##2} {##3} { } { } { } }
7803 }

```

(End definition for `\_msg_class_new:nn`.)

`\msg_fatal:nnnnnn` For fatal errors, after the error message `TeX` bails out.

```

\msg_fatal:nnxxx 7804 \_msg_class_new:nn { fatal }
\msg_fatal:nnnnn 7805 {
\msg_fatal:nnxxx 7806   \msg_interrupt:nnn
\msg_fatal:nnnnn 7807   { \msg_fatal_text:n {#1} : ~ "#2" }
\msg_fatal:nnxx 7808   {
\msg_fatal:nnnn 7809     \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
\msg_fatal:nnx 7810     \msg_see_documentation_text:n {#1}
\msg_fatal:nn 7811   }
7812   { \c__msg_fatal_text_tl }
7813 \tex_end:D
7814 }

```

(End definition for `\msg_fatal:nnnnnn` and others. These functions are documented on page 130.)

`\msg_critical:nnnnnn` Not quite so bad: just end the current file.

```

\msg_critical:nnxxx
\msg_critical:nnnnn
\msg_critical:nnxxx
\msg_critical:nnnn
\msg_critical:nnxx
\msg_critical:nnn
\msg_critical:nnx
\msg_critical:nn

```

```

7815 \_msg\_class\_new:nn { critical }
7816 {
7817   \msg\_interrupt:nnn
7818   { \msg\_critical\_text:n {#1} : ~ "#2" }
7819   {
7820     \use:c { \c\_msg\_text\_prefix\_tl #1 / #2 } {#3} {#4} {#5} {#6}
7821     \msg\_see\_documentation\_text:n {#1}
7822   }
7823   { \c\_msg\_critical\_text\_tl }
7824   \tex\_endinput:D
7825 }

```

(End definition for `\msg\_critical:nnnnnn` and others. These functions are documented on page 130.)

`\msg\_error:nnnnnn` For an error, the interrupt routine is called. We check if there is a “more text” by  
`\msg\_error:nnxxxx` comparing that control sequence with a permanently empty text.  
`\msg\_error:nnnnnn` 7826 \\_msg\\_class\\_new:nn { error }  
`\msg\_error:nnxxx` 7827 {  
`\msg\_error:nnnn` 7828 \\_msg\\_error:cnnnnn  
`\msg\_error:nnxx` 7829 { \c\\_msg\\_more\\_text\\_prefix\\_tl #1 / #2 }  
`\msg\_error:nnn` 7830 {#3} {#4} {#5} {#6}  
`\msg\_error:nnx` 7831 {  
`\msg\_error:nn` 7832 \msg\\_interrupt:nnn  
7833 { \msg\\_error\\_text:n {#1} : ~ "#2" }  
7834 {  
7835 \use:c { \c\\_msg\\_text\\_prefix\\_tl #1 / #2 } {#3} {#4} {#5} {#6}  
7836 \msg\\_see\\_documentation\\_text:n {#1}  
7837 }  
7838 }  
7839 }  
7840 \cs\\_new\\_protected:Npn \\_msg\\_error:cnnnnn #1#2#3#4#5#6  
7841 {  
7842 \cs\\_if\\_eq:cNTF {#1} \\_msg\\_no\\_more\\_text:nnnn  
7843 { #6 { } }  
7844 { #6 { \use:c {#1} {#2} {#3} {#4} {#5} } }  
7845 }  
7846 \cs\\_new:Npn \\_msg\\_no\\_more\\_text:nnnn #1#2#3#4 { }

(End definition for `\msg\_error:nnnnnn` and others. These functions are documented on page 131.)

`\msg\_warning:nnnnnn` Warnings are printed to the terminal.  
`\msg\_warning:nnxxxx` 7847 \\_msg\\_class\\_new:nn { warning }  
`\msg\_warning:nnnnn` 7848 {  
`\msg\_warning:nnxxx` 7849 \msg\\_term:n  
`\msg\_warning:nnnn` 7850 {  
`\msg\_warning:nnxx` 7851 \msg\\_warning\\_text:n {#1} : ~ "#2" \\ \\  
`\msg\_warning:nnn` 7852 \use:c { \c\\_msg\\_text\\_prefix\\_tl #1 / #2 } {#3} {#4} {#5} {#6}  
`\msg\_warning:nnx` 7853 }  
`\msg\_warning:nn` 7854 }  
`\msg\_warning:nn`

(End definition for `\msg\_warning:nnnnnn` and others. These functions are documented on page 131.)

`\msg\_info:nnnnnn` Information only goes into the log.  
`\msg\_info:nnxxxx` 7855 \\_msg\\_class\\_new:nn { info }  
`\msg\_info:nnnnn` 7856 {  
`\msg\_info:nnxxx`  
`\msg\_info:nnnn`  
`\msg\_info:nnxx`  
`\msg\_info:nnn`  
`\msg\_info:nnx`  
`\msg\_info:nn`

```

7857     \msg_log:n
7858     {
7859         \msg_info_text:n {#1} : ~ "#2" \\ \\
7860         \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
7861     }
7862 }

```

(End definition for \msg\_info:nnnnnn and others. These functions are documented on page 131.)

**\msg\_log:nnnnnn** “Log” data is very similar to information, but with no extras added.

```

\msg_log:nnxxxx 7863 \__msg_class_new:nn { log }
\msg_log:nnnnnn 7864 {
\msg_log:nnxxx 7865     \iow_wrap:nnnN
\msg_log:nnnn 7866     { \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6} }
\msg_log:nnxx 7867     { } { } \iow_log:n
\msg_log:nnn 7868 }

```

**\msg\_log:nnx** (End definition for \msg\_log:nnnnnn and others. These functions are documented on page 131.)

**\msg\_none:nnnnnn** The none message type is needed so that input can be gobbled.

```

\msg_none:nnxxxx 7869 \__msg_class_new:nn { none } { }

```

**\msg\_none:nnnnnn** (End definition for \msg\_none:nnnnnn and others. These functions are documented on page 132.)

**\msg\_none:nnxxx** End the group to eliminate \\_\_msg\_class\_new:nn.

```

\msg_none:nnnn 7870 \group_end:
\msg_none:nnxx

```

```

\__msg_class_chk_exist:nT
\msg_none:nnx
\msg_none:nn

```

Checking that a message class exists. We build this from \cs\_if\_free:cTF rather than \cs\_if\_exist:cTF because that avoids reading the second argument earlier than necessary.

```

7871 \cs_new:Npn \__msg_class_chk_exist:nT #1
7872 {
7873     \cs_if_free:cTF { __msg_ #1 _code:nnnnnn }
7874     { \__msg_kernel_error:nnx { kernel } { message-class-unknown } {#1} }
7875 }

```

(End definition for \\_\_msg\_class\_chk\_exist:nT.)

**\l\_\_msg\_class\_tl** Support variables needed for the redirection system.

```

\l__msg_current_class_tl 7876 \tl_new:N \l__msg_class_tl
7877 \tl_new:N \l__msg_current_class_tl

```

(End definition for \l\_\_msg\_class\_tl and \l\_\_msg\_current\_class\_tl.)

**\l\_\_msg\_redirect\_prop** For redirection of individually-named messages

```

7878 \prop_new:N \l__msg_redirect_prop

```

(End definition for \l\_\_msg\_redirect\_prop.)

**\l\_\_msg\_hierarchy\_seq** During redirection, split the message name into a sequence with items {/module/submodule}, {/module}, and {}.

```

7879 \seq_new:N \l__msg_hierarchy_seq

```

(End definition for \l\_\_msg\_hierarchy\_seq.)

\l\_\_msg\_class\_loop\_seq Classes encountered when following redirections to check for loops.

```
7880 \seq_new:N \l__msg_class_loop_seq
```

(End definition for \l\_\_msg\_class\_loop\_seq.)

\\_\_msg\_use:nnnnnnn

Actually using a message is a multi-step process. First, some safety checks on the message and class requested. The code and arguments are then stored to avoid passing them around. The assignment to \\_\_msg\_use\_code: is similar to \tl\_set:Nn. The message is eventually produced with whatever \l\_\_msg\_class\_tl is when \\_\_msg\_use\_code: is called.

\\_\_msg\_use\_redirect\_name:n

\\_\_msg\_use\_hierarchy:nwN

\\_\_msg\_use\_redirect\_module:n

\\_\_msg\_use\_code:

```
7881 \cs_new_protected:Npn \__msg_use:nnnnnnn #1#2#3#4#5#6#7
```

```
7882 {
```

```
7883   \msg_if_exist:nnTF {#2} {#3}
```

```
7884   {
```

```
7885     \__msg_class_chk_exist:nT {#1}
```

```
7886     {
```

```
7887       \tl_set:Nn \l__msg_current_class_tl {#1}
```

```
7888       \cs_set_protected:Npx \__msg_use_code:
```

```
7889       {
```

```
7890         \exp_not:n
```

```
7891         {
```

```
7892           \use:c { __msg_ \l__msg_class_tl _code:nnnnnnn }
```

```
7893           {#2} {#3} {#4} {#5} {#6} {#7}
```

```
7894         }
```

```
7895       }
```

```
7896       \__msg_use_redirect_name:n { #2 / #3 }
```

```
7897     }
```

```
7898   }
```

```
7899   { \__msg_kernel_error:nxx { kernel } { message-unknown } {#2} {#3} }
```

```
7900 }
```

```
7901 \cs_new_protected:Npn \__msg_use_code: { }
```

The first check is for a individual message redirection. If this applies then no further redirection is attempted. Otherwise, split the message name into module/submodule/message (with an arbitrary number of slashes), and store {/module/submodule}, {/module} and {} into \l\_\_msg\_hierarchy\_seq. We then map through this sequence, applying the most specific redirection.

```
7902 \cs_new_protected:Npn \__msg_use_redirect_name:n #1
```

```
7903 {
```

```
7904   \prop_get:NnNTF \l__msg_redirect_prop { / #1 } \l__msg_class_tl
```

```
7905   { \__msg_use_code: }
```

```
7906   {
```

```
7907     \seq_clear:N \l__msg_hierarchy_seq
```

```
7908     \__msg_use_hierarchy:nwN { }
```

```
7909     #1 \q_mark \__msg_use_hierarchy:nwN
```

```
7910     / \q_mark \use_none_delimit_by_q_stop:w
```

```
7911     \q_stop
```

```
7912     \__msg_use_redirect_module:n { }
```

```
7913   }
```

```
7914 }
```

```
7915 \cs_new_protected:Npn \__msg_use_hierarchy:nwN #1#2 / #3 \q_mark #4
```

```
7916 {
```

```
7917   \seq_put_left:Nn \l__msg_hierarchy_seq {#1}
```

```
7918   #4 { #1 / #2 } #3 \q_mark #4
```

```
7919 }
```

At this point, the items of `\l__msg_hierarchy_seq` are the various levels at which we should look for a redirection. Redirections which are less specific than the argument of `\__msg_use_redirect_module:n` are not attempted. This argument is empty for a class redirection, `/module` for a module redirection, *etc.* Loop through the sequence to find the most specific redirection, with module `##1`. The loop is interrupted after testing for a redirection for `##1` equal to the argument `#1` (least specific redirection allowed). When a redirection is found, break the mapping, then if the redirection targets the same class, output the code with that class, and otherwise set the target as the new current class, and search for further redirections. Those redirections should be at least as specific as `##1`.

```
7920 \cs_new_protected:Npn \__msg_use_redirect_module:n #1
7921 {
7922   \seq_map_inline:Nn \l__msg_hierarchy_seq
7923   {
7924     \prop_get:cnTF { l__msg_redirect_ \l__msg_current_class_tl _prop }
7925     {##1} \l__msg_class_tl
7926     {
7927       \seq_map_break:n
7928       {
7929         \tl_if_eq:NNTF \l__msg_current_class_tl \l__msg_class_tl
7930         { \__msg_use_code: }
7931         {
7932           \tl_set_eq:NN \l__msg_current_class_tl \l__msg_class_tl
7933           \__msg_use_redirect_module:n {##1}
7934         }
7935       }
7936     }
7937     {
7938       \str_if_eq:nnT {##1} {#1}
7939       {
7940         \tl_set_eq:NN \l__msg_class_tl \l__msg_current_class_tl
7941         \seq_map_break:n { \__msg_use_code: }
7942       }
7943     }
7944   }
7945 }
```

(End definition for `\__msg_use:nnnnnnn` and others.)

**`\msg_redirect_name:nnn`** Named message always use the given class even if that class is redirected further. An empty target class cancels any existing redirection for that message.

```
7946 \cs_new_protected:Npn \msg_redirect_name:nnn #1#2#3
7947 {
7948   \tl_if_empty:nTF {#3}
7949   { \prop_remove:Nn \l__msg_redirect_prop { / #1 / #2 } }
7950   {
7951     \__msg_class_chk_exist:nT {#3}
7952     { \prop_put:Nnn \l__msg_redirect_prop { / #1 / #2 } {#3} }
7953   }
7954 }
```

(End definition for `\msg_redirect_name:nnn`. This function is documented on page [133](#).)

```

\msg_redirect_class:nn
\msg_redirect_module:nnn
  \__msg_redirect:nnn
\__msg_redirect_loop_chk:nnn
\__msg_redirect_loop_list:n

```

If the target class is empty, eliminate the corresponding redirection. Otherwise, add the redirection. We must then check for a loop: as an initialization, we start by storing the initial class in \l\_\_msg\_current\_class\_tl.

```

7955 \cs_new_protected:Npn \msg_redirect_class:nn
7956   { \__msg_redirect:nnn { } }
7957 \cs_new_protected:Npn \msg_redirect_module:nnn #1
7958   { \__msg_redirect:nnn { / #1 } }
7959 \cs_new_protected:Npn \__msg_redirect:nnn #1#2#3
7960   {
7961     \__msg_class_chk_exist:nT {#2}
7962     {
7963       \tl_if_empty:nTF {#3}
7964       { \prop_remove:cn { l__msg_redirect_ #2 _prop } {#1} }
7965       {
7966         \__msg_class_chk_exist:nT {#3}
7967         {
7968           \prop_put:cnn { l__msg_redirect_ #2 _prop } {#1} {#3}
7969           \tl_set:Nn \l__msg_current_class_tl {#2}
7970           \seq_clear:N \l__msg_class_loop_seq
7971           \__msg_redirect_loop_chk:nnn {#2} {#3} {#1}
7972         }
7973       }
7974     }
7975   }

```

Since multiple redirections can only happen with increasing specificity, a loop requires that all steps are of the same specificity. The new redirection can thus only create a loop with other redirections for the exact same module, #1, and not submodules. After some initialization above, follow redirections with \l\_\_msg\_class\_tl, and keep track in \l\_\_msg\_class\_loop\_seq of the various classes encountered. A redirection from a class to itself, or the absence of redirection both mean that there is no loop. A redirection to the initial class marks a loop. To break it, we must decide which redirection to cancel. The user most likely wants the newly added redirection to hold with no further redirection. We thus remove the redirection starting from #2, target of the new redirection. Note that no message is emitted by any of the underlying functions: otherwise we may get an infinite loop because of a message from the message system itself.

```

7976 \cs_new_protected:Npn \__msg_redirect_loop_chk:nnn #1#2#3
7977   {
7978     \seq_put_right:Nn \l__msg_class_loop_seq {#1}
7979     \prop_get:cnNT { l__msg_redirect_ #1 _prop } {#3} \l__msg_class_tl
7980     {
7981       \str_if_eq_x:nnF { \l__msg_class_tl } {#1}
7982       {
7983         \tl_if_eq:NNTF \l__msg_class_tl \l__msg_current_class_tl
7984         {
7985           \prop_put:cnn { l__msg_redirect_ #2 _prop } {#3} {#2}
7986           \__msg_kernel_warning:nnxxxx
7987           { kernel } { message-redirect-loop }
7988           { \seq_item:Nn \l__msg_class_loop_seq { 1 } }
7989           { \seq_item:Nn \l__msg_class_loop_seq { 2 } }
7990           {#3}
7991           {
7992             \seq_map_function:NN \l__msg_class_loop_seq

```

```

7993         \_msg_redirect_loop_list:n
7994         { \seq_item:Nn \l__msg_class_loop_seq { 1 } }
7995     }
7996 }
7997 { \_msg_redirect_loop_chk:onn \l__msg_class_tl {#2} {#3} }
7998 }
7999 }
8000 }
8001 \cs_generate_variant:Nn \_msg_redirect_loop_chk:nnn { o }
8002 \cs_new:Npn \_msg_redirect_loop_list:n #1 { {#1} ~ => ~ }

```

(End definition for `\msg_redirect_class:nn` and others. These functions are documented on page 132.)

## 16.5 Kernel-specific functions

`\_msg_kernel_new:nnnn` The kernel needs some messages of its own. These are created using pre-built functions. Two functions are provided: one more general and one which only has the short text part.

```

\_msg_kernel_new:nnnn
\_msg_kernel_new:nnn
\_msg_kernel_set:nnnn
\_msg_kernel_set:nnn
8003 \cs_new_protected:Npn \_msg_kernel_new:nnnn #1#2
8004 { \msg_new:nnnn { LaTeX } { #1 / #2 } }
8005 \cs_new_protected:Npn \_msg_kernel_new:nnn #1#2
8006 { \msg_new:nnn { LaTeX } { #1 / #2 } }
8007 \cs_new_protected:Npn \_msg_kernel_set:nnnn #1#2
8008 { \msg_set:nnnn { LaTeX } { #1 / #2 } }
8009 \cs_new_protected:Npn \_msg_kernel_set:nnn #1#2
8010 { \msg_set:nnn { LaTeX } { #1 / #2 } }

```

(End definition for `\_msg_kernel_new:nnnn` and others.)

`\_msg_kernel_class_new:nN` All the functions for kernel messages come in variants ranging from 0 to 4 arguments. Those with less than 4 arguments are defined in terms of the 4-argument variant, in a way very similar to `\_msg_class_new:nn`. This auxiliary is destroyed at the end of the group.

`\_msg_kernel_class_new_aux:nN`

```

8011 \group_begin:
8012 \cs_set_protected:Npn \_msg_kernel_class_new:nN #1
8013 { \_msg_kernel_class_new_aux:nN { kernel_ #1 } }
8014 \cs_set_protected:Npn \_msg_kernel_class_new_aux:nN #1#2
8015 {
8016   \cs_new_protected:cpn { __msg_ #1 :nnnnnn } ##1##2##3##4##5##6
8017   {
8018     \use:x
8019     {
8020       \exp_not:n { #2 { LaTeX } { ##1 / ##2 } }
8021       { \tl_to_str:n {##3} } { \tl_to_str:n {##4} }
8022       { \tl_to_str:n {##5} } { \tl_to_str:n {##6} }
8023     }
8024   }
8025   \cs_new_protected:cpx { __msg_ #1 :nnnnnn } ##1##2##3##4##5
8026   { \exp_not:c { __msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} {##5} { } }
8027   \cs_new_protected:cpx { __msg_ #1 :nnnn } ##1##2##3##4
8028   { \exp_not:c { __msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} { } { } }
8029   \cs_new_protected:cpx { __msg_ #1 :nnn } ##1##2##3
8030   { \exp_not:c { __msg_ #1 :nnnnnn } {##1} {##2} {##3} { } { } { } }
8031   \cs_new_protected:cpx { __msg_ #1 :nn } ##1##2

```

```

8032 { \exp_not:c { __msg_ #1 :nnnnnn } {##1} {##2} { } { } { } }
8033 \cs_new_protected:cpx { __msg_ #1 :nnxxxx } ##1##2##3##4##5##6
8034 {
8035     \use:x
8036     {
8037         \exp_not:N \exp_not:n
8038         { \exp_not:c { __msg_ #1 :nnnnnn } {##1} {##2} }
8039         {##3} {##4} {##5} {##6}
8040     }
8041 }
8042 \cs_new_protected:cpx { __msg_ #1 :nnxxx } ##1##2##3##4##5
8043 { \exp_not:c { __msg_ #1 :nnxxxx } {##1} {##2} {##3} {##4} {##5} { } }
8044 \cs_new_protected:cpx { __msg_ #1 :nnxx } ##1##2##3##4
8045 { \exp_not:c { __msg_ #1 :nnxxxx } {##1} {##2} {##3} {##4} { } { } }
8046 \cs_new_protected:cpx { __msg_ #1 :nnx } ##1##2##3
8047 { \exp_not:c { __msg_ #1 :nnxxxx } {##1} {##2} {##3} { } { } { } }
8048 }

```

[illegible]

```
8049 \__msg_kernel_class_new:nN { fatal } \__msg_fatal_code:nnnnnn
8050 \cs_undefine:N \__msg_kernel_error:nnxx
8051 \cs_undefine:N \__msg_kernel_error:nnx
8052 \cs_undefine:N \__msg_kernel_error:nn
8053 \__msg_kernel_class_new:nN { error } \__msg_error_code:nnnnnn
```

[illegible]

```
8054 \_msg_kernel_class_new:nN { warning } \msg_warning:nnxxxxx
8055 \_msg_kernel_class_new:nN { info } \msg_info:nnxxxxx
```

End the group to eliminate \\_msg\_kernel\_class\_new:nN.

Error messages needed to actually implement the message system itself.



```

8071 \c__msg_return_text_tl
8072 }
8073 \__msg_kernel_new:nnnn { kernel } { message-class-unknown }
8074 { Unknown~message~class~'~{#1}'~. }
8075 {
8076 LaTeX~has~been~asked~to~redirect~messages~to~a~class~'~{#1}'~:\\
8077 this~was~never~defined.
8078 \c__msg_return_text_tl
8079 }
8080 \__msg_kernel_new:nnnn { kernel } { message-redirect-loop }
8081 {
8082 Message~redirection~loop~caused~by~ {#1} ~=>~ {#2}
8083 \tl_if_empty:nF {#3} { ~for~module~' \use_none:n #3 ' } .
8084 }
8085 {
8086 Adding~the~message~redirection~ {#1} ~=>~ {#2}
8087 \tl_if_empty:nF {#3} { ~for~the~module~' \use_none:n #3 ' } ~
8088 created~an~infinite~loop\\\\
8089 \iow_indent:n { #4 \\\ }
8090 }

```

Messages for earlier kernel modules.

```

8091 \__msg_kernel_new:nnnn { kernel } { bad-number-of-arguments }
8092 { Function~'~{#1}'~cannot~be~defined~with~#2~arguments. }
8093 {
8094 \c__msg_coding_error_text_tl
8095 LaTeX~has~been~asked~to~define~a~function~'~{#1}'~with~
8096 #2~arguments~.~
8097 TeX~allows~between~0~and~9~arguments~for~a~single~function.
8098 }
8099 \__msg_kernel_new:nnn { kernel } { char-active }
8100 { Cannot~generate~active~chars. }
8101 \__msg_kernel_new:nnn { kernel } { char-invalid-catcode }
8102 { Invalid~catcode~for~char~generation. }
8103 \__msg_kernel_new:nnn { kernel } { char-null-space }
8104 { Cannot~generate~null~char~as~a~space. }
8105 \__msg_kernel_new:nnn { kernel } { char-out-of-range }
8106 { Charcode~requested~out~of~engine~range. }
8107 \__msg_kernel_new:nnn { kernel } { char-space }
8108 { Cannot~generate~space~chars. }
8109 \__msg_kernel_new:nnnn { kernel } { command-already-defined }
8110 { Control~sequence~#1~already~defined. }
8111 {
8112 \c__msg_coding_error_text_tl
8113 LaTeX~has~been~asked~to~create~a~new~control~sequence~'~{#1}'~
8114 but~this~name~has~already~been~used~elsewhere. \\ \\
8115 The~current~meaning~is:\\
8116 \\ #2
8117 }
8118 \__msg_kernel_new:nnnn { kernel } { command-not-defined }
8119 { Control~sequence~#1~undefined. }
8120 {
8121 \c__msg_coding_error_text_tl
8122 LaTeX~has~been~asked~to~use~a~control~sequence~'~{#1}'~:\\
8123 this~has~not~been~defined~yet.

```

```

8124 }
8125 \_msg_kernel_new:nnn { kernel } { deprecated-command }
8126 {
8127   The-deprecated-command-~'#2'-has-been-or-will-be-removed-on~#1.
8128   \tl_if_empty:nF {#3} { ~Use-instead~'#3'. }
8129 }
8130 \_msg_kernel_new:nnnn { kernel } { empty-search-pattern }
8131 { Empty-search-pattern. }
8132 {
8133   \c_msg_coding_error_text_tl
8134   LaTeX-has-been-asked-to-replace-an-empty-pattern-by~'#1':~that~
8135   would-lead-to-an-infinite-loop!
8136 }
8137 \_msg_kernel_new:nnnn { kernel } { out-of-registers }
8138 { No-room-for-a-new~#1. }
8139 {
8140   TeX-only-supports-\int_use:N \c_max_register_int \ %
8141   of-each-type.~All-the~#1~registers-have-been-used.~
8142   This-run-will-be-aborted-now.
8143 }
8144 \_msg_kernel_new:nnnn { kernel } { non-base-function }
8145 { Function~'#1'~is-not-a-base-function }
8146 {
8147   \c_msg_coding_error_text_tl
8148   Functions-defined-through-\iow_char:N\cs_new:Nn~must-have~
8149   a-signature-consisting-of-only-normal-arguments~'N'~and~'n'.~
8150   To-define-variants-use-\iow_char:N\cs_generate_variant:Nn~
8151   and-to-define-other-functions-use-\iow_char:N\cs_new:Npn.
8152 }
8153 \_msg_kernel_new:nnnn { kernel } { missing-colon }
8154 { Function~'#1'~contains-no~':'~. }
8155 {
8156   \c_msg_coding_error_text_tl
8157   Code-level-functions-must-contain~':'~to-separate-the~
8158   argument-specification-from-the-function-name.~This-is~
8159   needed-when-defining-conditionals-or-variants,~or-when-building-a~
8160   parameter-text-from-the-number-of-arguments-of-the-function.
8161 }
8162 \_msg_kernel_new:nnnn { kernel } { overflow }
8163 { Integers-larger-than~2^{30}-1~cannot-be-stored-in-arrays. }
8164 {
8165   An-attempt-was-made-to-store~#3-at-position~#2-in-the-array~'#1'.~
8166   The-largest-allowed-value~#4-will-be-used-instead.
8167 }
8168 \_msg_kernel_new:nnnn { kernel } { out-of-bounds }
8169 { Access-to-an-entry-beyond-an-array's-bounds. }
8170 {
8171   An-attempt-was-made-to-access-or-store-data-at-position~#2-of-the~
8172   array~'#1',~but-this-array-has-entries-at-positions-from~1~to~#3.
8173 }
8174 \_msg_kernel_new:nnnn { kernel } { protected-predicate }
8175 { Predicate~'#1'~must-be-expandable. }
8176 {
8177   \c_msg_coding_error_text_tl

```

```

8178 LaTeX-has-been-asked-to-define-~'~#1'~as-a-protected-predicate.~
8179 Only-expandable-tests-can-have-a-predicate-version.
8180 }
8181 \__msg_kernel_new:nnnn { kernel } { conditional-form-unknown }
8182 { Conditional-form-~'~#1'~for-function-~'~#2'~unknown. }
8183 {
8184   \c__msg_coding_error_text_tl
8185   LaTeX-has-been-asked-to-define-the-conditional-form-~'~#1'~of~
8186   the-function-~'~#2',~but-only-~'TF',~'T',~'F',~and-~'p'~forms-exist.
8187 }
8188 \__msg_kernel_new:nnnn { kernel } { scanmark-already-defined }
8189 { Scan-mark-~#1-already-defined. }
8190 {
8191   \c__msg_coding_error_text_tl
8192   LaTeX-has-been-asked-to-create-a-new-scan-mark-~'~#1'~
8193   but-this-name-has-already-been-used-for-a-scan-mark.
8194 }
8195 \__msg_kernel_new:nnnn { kernel } { variable-not-defined }
8196 { Variable-~#1-undefined. }
8197 {
8198   \c__msg_coding_error_text_tl
8199   LaTeX-has-been-asked-to-show-a-variable-~#1,~but-this-has-not~
8200   been-defined-yet.
8201 }
8202 \__msg_kernel_new:nnnn { kernel } { variant-too-long }
8203 { Variant-form-~'~#1'~longer-than-base-signature-of-~'~#2'. }
8204 {
8205   \c__msg_coding_error_text_tl
8206   LaTeX-has-been-asked-to-create-a-variant-of-the-function-~'~#2'~
8207   with-a-signature-starting-with-~'~#1',~but-that-is-longer-than~
8208   the-signature-(part-after-the-colon)-of-~'~#2'.
8209 }
8210 \__msg_kernel_new:nnnn { kernel } { invalid-variant }
8211 { Variant-form-~'~#1'~invalid-for-base-form-~'~#2'. }
8212 {
8213   \c__msg_coding_error_text_tl
8214   LaTeX-has-been-asked-to-create-a-variant-of-the-function-~'~#2'~
8215   with-a-signature-starting-with-~'~#1',~but-cannot-change-an-argument~
8216   from-type-~'~#3'~to-type-~'~#4'.
8217 }

```

Some errors are only needed in package mode if debugging is enabled by one of the options `enable-debug`, `check-declarations`, `log-functions`, or on the contrary if debugging is turned off. In format mode the error is somewhat different.

```

8218 \*package)
8219 \bool_if:NTF \l@expl@enable@debug@bool
8220 {
8221   \__msg_kernel_new:nnn { kernel } { debug-unpatchable }
8222   { Only-some-definitions-can-be-patched;~'~#3'~cannot. }
8223   \__msg_kernel_new:nnnn { check } { non-declared-variable }
8224   { The-variable-~#1-has-not-been-declared-~\msg_line_context:. }
8225   {
8226     Checking-is-active,~and-you-have-tried-do-so-something-like: \
8227     \ \tl_set:Nn ~ #1 ~ \{ ~ ... ~ \} \

```

```

8228         without~first~having: \\\
8229         \ \ \tl_new:N ~ #1 \\\
8230         \\\
8231         LaTeX~will~create~the~variable~and~continue.
8232     }
8233 }
8234 {
8235     \__msg_kernel_new:nnnn { kernel } { enable-debug }
8236     { To~use~'#1'~load~expl3~with~the~'enable-debug'~option. }
8237     {
8238         The~function~'#1'~will~be~ignored~because~it~can~only~work~if~
8239         some~internal~functions~in~expl3~have~been~appropriately~
8240         defined.~This~only~happens~if~one~of~the~options~
8241         'enable-debug',~'check-declarations'~or~'log-functions'~was~
8242         given~when~loading~expl3.
8243     }
8244 }
8245 \</package>
8246 \*initex>
8247 \__msg_kernel_new:nnnn { kernel } { enable-debug }
8248 { '#1'~cannot~be~used~in~format~mode. }
8249 {
8250     The~function~'#1'~will~be~ignored~because~it~can~only~work~if~
8251     some~internal~functions~in~expl3~have~been~appropriately~
8252     defined.~This~only~happens~in~package~mode~(and~only~if~one~of~
8253     the~options~'enable-debug',~'check-declarations'~or~'log-functions'~
8254     was~given~when~loading~expl3.
8255 }
8256 \</initex>

```

Some errors only appear in expandable settings, hence don't need a “more-text” argument.

```

8257 \__msg_kernel_new:nnn { kernel } { bad-variable }
8258 { Erroneous~variable~#1~used! }
8259 \__msg_kernel_new:nnn { kernel } { misused-sequence }
8260 { A~sequence~was~misused. }
8261 \__msg_kernel_new:nnn { kernel } { misused-prop }
8262 { A~property~list~was~misused. }
8263 \__msg_kernel_new:nnn { kernel } { negative-replication }
8264 { Negative~argument~for~\prg_replicate:nn. }
8265 \__msg_kernel_new:nnn { kernel } { unknown-comparison }
8266 { Relation~'#1'~unknown:~use~=,~<,~>,~==,~!=,~<=,~>=. }
8267 \__msg_kernel_new:nnn { kernel } { zero-step }
8268 { Zero~step~size~for~step~function~#1. }

```

Messages used by the “show” functions.

```

8269 \__msg_kernel_new:nnn { kernel } { show-clist }
8270 {
8271     The~comma~list~ \tl_if_empty:nF {#1} { #1 ~ }
8272     \tl_if_empty:nTF {#2}
8273     { is~empty }
8274     { contains~the~items~(without~outer~braces): }
8275 }
8276 \__msg_kernel_new:nnn { kernel } { show-prop }
8277 {

```

```

8278     The~property~list~#1~
8279     \tl_if_empty:nTF {#2}
8280       { is~empty }
8281       { contains~the~pairs~(without~outer~braces): }
8282   }
8283   \__msg_kernel_new:nnn { kernel } { show-seq }
8284   {
8285     The~sequence~#1~
8286     \tl_if_empty:nTF {#2}
8287       { is~empty }
8288       { contains~the~items~(without~outer~braces): }
8289   }
8290   \__msg_kernel_new:nnn { kernel } { show-streams }
8291   {
8292     \tl_if_empty:nTF {#2} { No~ } { The~following~ }
8293     \str_case:nn {#1}
8294       {
8295         { ior } { input ~ }
8296         { iow } { output ~ }
8297       }
8298     streams~are~
8299     \tl_if_empty:nTF {#2} { open } { in~use: }
8300   }

```

## 16.6 Expandable errors

`\__msg_expandable_error:n` In expansion only context, we cannot use the normal means of reporting errors. Instead, we feed `\LaTeX3 error:` an undefined control sequence, `\LaTeX3 error:`. It is thus interrupted, and shows the context, which thanks to the odd-looking `\use:n` is

```

<argument> \LaTeX3 error:
           The error message.

```

In other words, `\TeX` is processing the argument of `\use:n`, which is `\LaTeX3 error:` (*error message*). Then `\__msg_expandable_error:w` cleans up. In fact, there is an extra subtlety: if the user inserts tokens for error recovery, they should be kept. Thus we also use an odd space character (with category code 7) and keep tokens until that space character, dropping everything else until `\q_stop`. The `\exp_end:` prevents losing braces around the user-inserted text if any, and stops the expansion of `\exp:w`. The group is used to prevent `\LaTeX3~error:` from being globally equal to `\scan_stop:`.

```

8301 \group_begin:
8302 \cs_set_protected:Npn \__msg_tmp:w #1#2
8303 {
8304   \cs_new:Npn \__msg_expandable_error:n ##1
8305   {
8306     \exp:w
8307     \exp_after:wN \exp_after:wN
8308     \exp_after:wN \__msg_expandable_error:w
8309     \exp_after:wN \exp_after:wN
8310     \exp_after:wN \exp_end:
8311     \use:n { #1 #2 ##1 } #2
8312   }
8313 \cs_new:Npn \__msg_expandable_error:w ##1 #2 ##2 #2 {##1}

```

```

8314 }
8315 \exp_args:Ncx \__msg_tmp:w { LaTeX3-error: }
8316 { \char_generate:nn { '\ } { 7 } }
8317 \group_end:

```

(End definition for \\_\_msg\_expandable\_error:n and \\_\_msg\_expandable\_error:w.)

\\_\_msg\_kernel\_expandable\_error:nnnnnn The command built from the csname \c\_@@\_text\_prefix\_tl LaTeX / #1 / #2 takes four arguments and builds the error text, which is fed to \\_\_msg\_expandable\_error:n.

```

\__msg_kernel_expandable_error:nnnnnn
\__msg_kernel_expandable_error:nnnnn
\__msg_kernel_expandable_error:nnnn
\__msg_kernel_expandable_error:nnn
\__msg_kernel_expandable_error:nn
8318 \cs_new:Npn \__msg_kernel_expandable_error:nnnnnn #1#2#3#4#5#6
8319 {
8320   \exp_args:Nf \__msg_expandable_error:n
8321   {
8322     \exp_args:NNc \exp_after:wN \exp_stop_f:
8323     { \c_@@_text_prefix_tl LaTeX / #1 / #2 }
8324     {#3} {#4} {#5} {#6}
8325   }
8326 }
8327 \cs_new:Npn \__msg_kernel_expandable_error:nnnnn #1#2#3#4#5
8328 {
8329   \__msg_kernel_expandable_error:nnnnnn
8330   {#1} {#2} {#3} {#4} {#5} { }
8331 }
8332 \cs_new:Npn \__msg_kernel_expandable_error:nnnn #1#2#3#4
8333 {
8334   \__msg_kernel_expandable_error:nnnnnn
8335   {#1} {#2} {#3} {#4} { } { }
8336 }
8337 \cs_new:Npn \__msg_kernel_expandable_error:nnn #1#2#3
8338 {
8339   \__msg_kernel_expandable_error:nnnnnn
8340   {#1} {#2} {#3} { } { } { }
8341 }
8342 \cs_new:Npn \__msg_kernel_expandable_error:nn #1#2
8343 {
8344   \__msg_kernel_expandable_error:nnnnnn
8345   {#1} {#2} { } { } { } { }
8346 }

```

(End definition for \\_\_msg\_kernel\_expandable\_error:nnnnnn and others.)

## 16.7 Showing variables

Functions defined in this section are used for diagnostic functions in l3clist, l3file, l3prop, l3seq, xtemplate

```

\g__msg_log_next_bool
\__msg_log_next:
8347 \bool_new:N \g__msg_log_next_bool
8348 \cs_new_protected:Npn \__msg_log_next:
8349 { \bool_gset_true:N \g__msg_log_next_bool }

```

(End definition for \g\_\_msg\_log\_next\_bool and \\_\_msg\_log\_next:.)

`\_msg_show_pre:nnnnn` Print the text of a message to the terminal or log file without formatting: short cuts around `\iow_wrap:nnnN`. The choice of terminal or log file is done by `\_msg_show_pre_aux:n`.

```

8350 \cs_new_protected:Npn \_msg_show_pre:nnnnn #1#2#3#4#5#6
8351 {
8352   \exp_args:Nx \iow_wrap:nnnN
8353   {
8354     \exp_not:c { \c_msg_text_prefix_tl #1 / #2 }
8355     { \tl_to_str:n {#3} }
8356     { \tl_to_str:n {#4} }
8357     { \tl_to_str:n {#5} }
8358     { \tl_to_str:n {#6} }
8359   }
8360   { } { } \_msg_show_pre_aux:n
8361 }
8362 \cs_new_protected:Npn \_msg_show_pre:nnxxx #1#2#3#4#5#6
8363 {
8364   \use:x
8365   { \exp_not:n { \_msg_show_pre:nnnnn {#1} {#2} } {#3} {#4} {#5} {#6} }
8366 }
8367 \cs_generate_variant:Nn \_msg_show_pre:nnnnn { nnnnnV }
8368 \cs_new_protected:Npn \_msg_show_pre_aux:n
8369 { \bool_if:NTF \g_msg_log_next_bool { \iow_log:n } { \iow_term:n } }

```

(End definition for `\_msg_show_pre:nnnnn` and `\_msg_show_pre_aux:n`.)

`\_msg_show_variable:NNNnn` The arguments of `\_msg_show_variable:NNNnn` are

- The *⟨variable⟩* to be shown as #1.
- An *⟨if-exist⟩* conditional #2 with NTF signature.
- An *⟨if-empty⟩* conditional #3 or other function with NTF signature (sometimes `\use_ii:nnn`).
- The *⟨message⟩* #4 to use.
- A construction #5 which produces the formatted string eventually passed to the `\showtokens` primitive. Typically this is a mapping of the form `\seq_map_function:NN ⟨variable⟩ \_msg_show_item:n`.

If *⟨if-exist⟩* *⟨variable⟩* is false, throw an error and remember to reset `\g_msg_log_next_bool`, which is otherwise reset by `\_msg_show_wrap:n`. If *⟨message⟩* is not empty, output the message `LaTeX/kernel/show-⟨message⟩` with as its arguments the *⟨variable⟩*, and either an empty second argument or ? depending on the result of *⟨if-empty⟩* *⟨variable⟩*. Afterwards, show the contents of #5 using `\_msg_show_wrap:n` or `\_msg_log_wrap:n`.

```

8370 \cs_new_protected:Npn \_msg_show_variable:NNNnn #1#2#3#4#5
8371 {
8372   #2 #1
8373   {
8374     \tl_if_empty:nF {#4}
8375     {
8376       \_msg_show_pre:nnxxx { LaTeX / kernel } { show- #4 }

```

```

8377         { \token_to_str:N #1 } { #3 #1 { } { ? } } { } { }
8378     }
8379     \__msg_show_wrap:n {#5}
8380 }
8381 {
8382     \__msg_kernel_error:n { kernel } { variable-not-defined }
8383     { \token_to_str:N #1 }
8384     \bool_gset_false:N \g__msg_log_next_bool
8385 }
8386 }

```

(End definition for `\__msg_show_variable:NNNnn`.)

**`\__msg_show_wrap:Nn`** A short-hand used for `\int_show:n` and many other functions that passes to `\__msg_show_wrap:n` the result of applying `#1` (a function such as `\int_eval:n`) to the expression `#2`. The leading `>~` is needed by `\__msg_show_wrap:n`. The use of x-expansion ensures that `#1` is expanded in the scope in which the show command is called, rather than in the group created by `\iow_wrap:nnnN`. This is only important for expressions involving the `\currentgrouplevel` or `\currentgrouptype`. On the other hand we want the expression to be converted to a string with the usual escape character, hence within the wrapping code.

```

8387 \cs_new_protected:Npn \__msg_show_wrap:Nn #1#2
8388 {
8389     \exp_args:Nx \__msg_show_wrap:n
8390     {
8391         > ~ \exp_not:n { \tl_to_str:n {#2} } =
8392         \exp_not:N \tl_to_str:n { #1 {#2} }
8393     }
8394 }

```

(End definition for `\__msg_show_wrap:Nn`.)

**`\__msg_show_wrap:n`** The argument of `\__msg_show_wrap:n` is line-wrapped using `\iow_wrap:nnnN`. Everything before the first `>` in the wrapped text is removed, as well as an optional space following it (because of f-expansion). In order for line-wrapping to give the correct result, the first `>` must in fact appear at the beginning of a line and be followed by a space (or a line-break), so in practice, the argument of `\__msg_show_wrap:n` begins with `>~` or `\>~`.

The line-wrapped text is then either sent to the log file through `\iow_log:x`, or shown in the terminal using the  $\varepsilon$ -TeX primitive `\showtokens` after removing a leading `>~` and trailing dot since those are added automatically by `\showtokens`. The trailing dot was included in the first place because its presence can affect line-wrapping. Note that the space after `>` is removed through f-expansion rather than by using an argument delimited by `>~` because the space may have been replaced by a line-break when line-wrapping.

A special case is that if the line-wrapped text is a single dot (in other words if the argument of `\__msg_show_wrap:n` x-expands to nothing) then no `>~` should be removed. This makes it unnecessary to check explicitly for emptiness when using for instance `\seq_map_function:NN <seq var> \__msg_show_item:n` as the argument of `\__msg_show_wrap:n`.

Finally, the token list `\l__msg_internal_tl` containing the result of all these manipulations is displayed to the terminal using `\etex_showtokens:D` and odd `\exp_after:wN` which expand the closing brace to improve the output slightly. The calls



to `\__iow_with:Nnn` ensure that the `\newlinechar` is set to 10 so that the `\iow_newline:` inserted by the line-wrapping code are correctly recognized by T<sub>E</sub>X, and that `\errorcontextlines` is -1 to avoid printing irrelevant context.

Note also that `\g__msg_log_next_bool` is only reset if that is necessary. This allows the user of an interactive prompt to insert tokens as a response to  $\varepsilon$ -T<sub>E</sub>X's `\showtokens`.

```

8395 \cs_new_protected:Npn \__msg_show_wrap:n #1
8396 { \iow_wrap:nnnN { #1 . } { } { } \__msg_show_wrap_aux:n }
8397 \cs_new_protected:Npn \__msg_show_wrap_aux:n #1
8398 {
8399   \tl_if_single:nTF {#1}
8400   { \tl_clear:N \l__msg_internal_tl }
8401   { \tl_set:Nf \l__msg_internal_tl { \__msg_show_wrap_aux:w #1 \q_stop } }
8402   \bool_if:NTF \g__msg_log_next_bool
8403   {
8404     \iow_log:x { > ~ \l__msg_internal_tl . }
8405     \bool_gset_false:N \g__msg_log_next_bool
8406   }
8407   {
8408     \__iow_with:Nnn \tex_newlinechar:D { 10 }
8409     {
8410       \__iow_with:Nnn \tex_errorcontextlines:D { -1 }
8411       {
8412         \etex_showtokens:D \exp_after:wN \exp_after:wN \exp_after:wN
8413         { \exp_after:wN \l__msg_internal_tl }
8414       }
8415     }
8416   }
8417 }
8418 \cs_new:Npn \__msg_show_wrap_aux:w #1 > #2 . \q_stop {#2}

```

(End definition for `\__msg_show_wrap:n`, `\__msg_show_wrap_aux:n`, and `\__msg_show_wrap_aux:w`.)

Each item in the variable is formatted using one of the following functions.

```

\__msg_show_item:n
\__msg_show_item:nn
\__msg_show_item_unbraced:nn
8419 \cs_new:Npn \__msg_show_item:n #1
8420 {
8421   \> \ \ \ \{ \tl_to_str:n {#1} \}
8422 }
8423 \cs_new:Npn \__msg_show_item:nn #1#2
8424 {
8425   \> \ \ \ \{ \tl_to_str:n {#1} \}
8426   \ \ => \ \ \ \{ \tl_to_str:n {#2} \}
8427 }
8428 \cs_new:Npn \__msg_show_item_unbraced:nn #1#2
8429 {
8430   \> \ \ \ \tl_to_str:n {#1}
8431   \ \ => \ \ \ \tl_to_str:n {#2}
8432 }

```

(End definition for `\__msg_show_item:n`, `\__msg_show_item:nn`, and `\__msg_show_item_unbraced:nn`.)

```

8433 </initex | package>

```

## 17 I3file implementation

The following test files are used for this code: *m3file001*.

```
8434 \<initex | package>
8435 \<@@=file>
```

### 17.1 File operations

**\g\_file\_curr\_dir\_str** The name of the current file should be available at all times. For the format the file name needs to be picked up at the start of the run. In L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> package mode the current file name is collected from \currname.

**\g\_file\_curr\_ext\_str**

**\g\_file\_curr\_name\_str**

```
8436 \str_new:N \g_file_curr_dir_str
8437 \str_new:N \g_file_curr_ext_str
8438 \str_new:N \g_file_curr_name_str
8439 \<initex>
8440 \tex_everyjob:D \exp_after:wN
8441 {
8442   \tex_the:D \tex_everyjob:D
8443   \str_gset:Nx \g_file_curr_name_str { \tex_jobname:D }
8444 }
8445 \</initex>
8446 \<package>
8447 \cs_if_exist:NT \currname
8448 { \str_gset_eq:NN \g_file_curr_name_str \currname }
8449 \</package>
```

(End definition for \g\_file\_curr\_dir\_str, \g\_file\_curr\_ext\_str, and \g\_file\_curr\_name\_str. These variables are documented on page 138.)

**\g\_\_file\_stack\_seq** The input list of files is stored as a sequence stack. In package mode we can recover the information from the details held by L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> (we must be in the preamble and loaded using \usepackage or \RequirePackage). As L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> doesn't store directory and name separately, we stick to the same convention here.

```
8450 \seq_new:N \g__file_stack_seq
8451 \<package>
8452 \group_begin:
8453   \cs_set_protected:Npn \__file_tmp:w #1#2#3
8454   {
8455     \tl_if_blank:nTF {#1}
8456     {
8457       \cs_set:Npn \__file_tmp:w ##1 " ##2 " ##3 \q_stop { { } {##2} { } }
8458       \seq_gput_right:Nx \g__file_stack_seq
8459       {
8460         \exp_after:wN \__file_tmp:w \tex_jobname:D
8461         " \tex_jobname:D " \q_stop
8462       }
8463     }
8464     {
8465       \seq_gput_right:Nn \g__file_stack_seq { { } {#1} {#2} }
8466       \__file_tmp:w
8467     }
8468   }
8469   \cs_if_exist:NT \@currnamestack
```

```

8470 { \exp_after:wN \__file_tmp:w \@currnamestack }
8471 \group_end:
8472 \</package>

```

(End definition for \g\_\_file\_stack\_seq.)

**\g\_\_file\_record\_seq** The total list of files used is recorded separately from the current file stack, as nothing is ever popped from this list. The current file name should be included in the file list! In format mode, this is done at the very start of the T<sub>E</sub>X run. In package mode we will eventually copy the contents of \@filelist.

```

8473 \seq_new:N \g__file_record_seq
8474 \*initex>
8475 \tex_everyjob:D \exp_after:wN
8476 {
8477   \tex_the:D \tex_everyjob:D
8478   \seq_gput_right:NV \g__file_record_seq \g_file_curr_name_str
8479 }
8480 \</initex>

```

(End definition for \g\_\_file\_record\_seq.)

**\l\_\_file\_tmp\_tl** Used as a short-term scratch variable.

```

8481 \tl_new:N \l__file_tmp_tl

```

(End definition for \l\_\_file\_tmp\_tl.)

**\l\_\_file\_base\_name\_str** For storing the basename and full path whilst passing data internally.

```

8482 \str_new:N \l__file_base_name_str
8483 \str_new:N \l__file_full_name_str

```

(End definition for \l\_\_file\_base\_name\_str and \l\_\_file\_full\_name\_str.)

**\l\_\_file\_dir\_str** Used in parsing a path into parts: in contrast to the above, these are never used outside of the current module.

```

8484 \str_new:N \l__file_dir_str
8485 \str_new:N \l__file_ext_str
8486 \str_new:N \l__file_name_str

```

(End definition for \l\_\_file\_dir\_str, \l\_\_file\_ext\_str, and \l\_\_file\_name\_str.)

**\l\_file\_search\_path\_seq** The current search path.

```

8487 \seq_new:N \l_file_search_path_seq

```

(End definition for \l\_file\_search\_path\_seq. This variable is documented on page 138.)

**\l\_\_file\_tmp\_seq** Scratch space for comma list conversion in package mode.

```

8488 \*package>
8489 \seq_new:N \l__file_tmp_seq
8490 \</package>

```

(End definition for \l\_\_file\_tmp\_seq.)

`\__file_name_sanitize:nN` For converting a token list to a string where active characters are treated as strings from the start. The logic to the quoting normalisation is the same as used by `\lualatexquotejobname`: check for balanced `"`, and assuming they balance strip all of them out before quoting the entire name if it contains spaces.

```

8491 \cs_new_protected:Npn \__file_name_sanitize:nN #1#2
8492 {
8493   \group_begin:
8494   \seq_map_inline:Nn \l_char_active_seq
8495   {
8496     \tl_set:Nx \l__file_tmp_tl { \iow_char:N ##1 }
8497     \char_set_active_eq:NN ##1 \l__file_tmp_tl
8498   }
8499   \tl_set:Nx \l__file_tmp_tl {#1}
8500   \tl_set:Nx \l__file_tmp_tl
8501   { \tl_to_str:N \l__file_tmp_tl }
8502   \exp_args:NNNV \group_end:
8503   \str_set:Nn #2 \l__file_tmp_tl
8504 }
8505 \cs_new_protected:Npn \__file_name_quote:nN #1#2
8506 {
8507   \str_set:Nx #2 {#1}
8508   \int_if_even:nF
8509   { 0 \tl_map_function:NN #2 \__file_name_quote_aux:n }
8510   {
8511     \__msg_kernel_error:nnx
8512     { kernel } { unbalanced-quote-in-filename } {#2}
8513   }
8514   \tl_remove_all:Nn #2 { " }
8515   \tl_if_in:NnT #2 { ~ }
8516   { \str_set:Nx #2 { " \exp_not:V #2 " } }
8517 }
8518 \cs_new:Npn \__file_name_quote_aux:n #1
8519 { \token_if_eq_charcode:NNT #1 " { + 1 } }

```

(End definition for `\__file_name_sanitize:nN`, `\__file_name_quote:nN`, and `\__file_name_sanitize_aux:n`.)

`\file_get_full_name:nN` The way to test if a file exists is to try to open it: if it does not exist then `TeX` reports end-of-file. A search is made looking at each potential path in turn (starting from the current directory). The first location is of course treated as the correct one: this is done by jumping to `\__prg_break_point:`. If nothing is found, `#2` is returned empty. A special case when there is no extension is that once the first location is found we test the existence of the file with `.tex` extension in that directory, and if it exists we include the `.tex` extension in the result.

```

8520 \cs_new_protected:Npn \file_get_full_name:nN #1#2
8521 {
8522   \__file_name_sanitize:nN {#1} \l__file_base_name_str
8523   \__file_get_full_name_search:nN { } \use:n
8524   \seq_map_inline:Nn \l_file_search_path_seq
8525   { \__file_get_full_name_search:nN { ##1 / } \seq_map_break:n }
8526   < *package >
8527   \cs_if_exist:NT \input@path
8528   {

```

```

8529     \tl_map_inline:Nn \input@path
8530     { \__file_get_full_name_search:nN { ##1 } \tl_map_break:n }
8531   }
8532 </package>
8533   \str_clear:N \l__file_full_name_str
8534   \__prg_break_point:
8535   \str_if_empty:NF \l__file_full_name_str
8536   {
8537     \exp_args:NV \file_parse_full_name:nNNN \l__file_full_name_str
8538     \l__file_dir_str \l__file_name_str \l__file_ext_str
8539     \str_if_empty:NT \l__file_ext_str
8540     {
8541       \__ior_open:No \g__file_internal_ior
8542       { \l__file_full_name_str .tex }
8543       \ior_if_eof:NF \g__file_internal_ior
8544       { \str_put_right:Nn \l__file_full_name_str { .tex } }
8545     }
8546   }
8547   \str_set_eq:NN #2 \l__file_full_name_str
8548   \ior_close:N \g__file_internal_ior
8549 }
8550 \cs_generate_variant:Nn \file_get_full_name:nN { V }
8551 \cs_new_protected:Npn \__file_get_full_name_search:nN #1#2
8552 {
8553   \__file_name_quote:nN
8554   { \tl_to_str:n {#1} \l__file_base_name_str }
8555   \l__file_full_name_str
8556   \__ior_open:No \g__file_internal_ior \l__file_full_name_str
8557   \ior_if_eof:NF \g__file_internal_ior { #2 { \__prg_break: } }
8558 }

```

(End definition for `\file_get_full_name:nN` and `\__file_get_full_name_search:nN`. These functions are documented on page 139.)

**`\file_if_exist:nTF`** The test for the existence of a file is a wrapper around the function to add a path to a file. If the file was found, the path contains something, whereas if the file was not located then the return value is empty.

```

8559 \prg_new_protected_conditional:Npnn \file_if_exist:n #1 { T , F , TF }
8560 {
8561   \file_get_full_name:nN {#1} \l__file_full_name_str
8562   \str_if_empty:NTF \l__file_full_name_str
8563   { \prg_return_false: }
8564   { \prg_return_true: }
8565 }

```

(End definition for `\file_if_exist:nTF`. This function is documented on page 138.)

**`\__file_missing:n`** An error message for a missing file, also used in `\ior_open:Nn`.

```

8566 \cs_new_protected:Npn \__file_missing:n #1
8567 {
8568   \__file_name_sanitize:nN {#1} \l__file_base_name_str
8569   \__msg_kernel_error:nxx { kernel } { file-not-found }
8570   { \l__file_base_name_str }
8571 }

```

(End definition for \\_file\_missing:n.)

```

\file_input:n Loading a file is done in a safe way, checking first that the file exists and loading only
\__file_input:n if it does. Push the file name on the \g__file_stack_seq, and add it to the file list,
\__file_input:V either \g__file_record_seq, or \@filelist in package mode.
\__file_input_push:n
\__file_input_pop:
\__file_input_pop:nnn
8572 \cs_new_protected:Npn \file_input:n #1
8573 {
8574   \file_get_full_name:nN {#1} \l__file_full_name_str
8575   \str_if_empty:NTF \l__file_full_name_str
8576     { \_file_missing:n {#1} }
8577     { \_file_input:V \l__file_full_name_str }
8578 }
8579 \cs_new_protected:Npn \__file_input:n #1
8580 {
8581   \*initex
8582   \seq_gput_right:Nn \g__file_record_seq {#1}
8583   \*initex
8584   \*package
8585   \clist_if_exist:NTF \@filelist
8586     { \@addtofilelist {#1} }
8587     { \seq_gput_right:Nn \g__file_record_seq {#1} }
8588   \*package
8589   \__file_input_push:n {#1}
8590   \tex_input:D #1 \c_space_tl
8591   \__file_input_pop:
8592 }
8593 \cs_generate_variant:Nn \__file_input:n { V }

```

Keeping a track of the file data is easy enough: we store the separated parts so we do not need to parse them twice.

```

8594 \cs_new_protected:Npn \__file_input_push:n #1
8595 {
8596   \seq_gpush:Nx \g__file_stack_seq
8597   {
8598     { \g_file_curr_dir_str }
8599     { \g_file_curr_name_str }
8600     { \g_file_curr_ext_str }
8601   }
8602   \file_parse_full_name:nNNN {#1}
8603   \l__file_dir_str \l__file_name_str \l__file_ext_str
8604   \str_gset_eq:NN \g_file_curr_dir_str \l__file_dir_str
8605   \str_gset_eq:NN \g_file_curr_name_str \l__file_name_str
8606   \str_gset_eq:NN \g_file_curr_ext_str \l__file_ext_str
8607 }
8608 \cs_new_protected:Npn \__file_input_pop:
8609 {
8610   \seq_gpop:NN \g__file_stack_seq \l__file_tmp_tl
8611   \exp_after:wN \__file_input_pop:nnn \l__file_tmp_tl
8612 }
8613 \cs_new_protected:Npn \__file_input_pop:nnn #1#2#3
8614 {
8615   \str_gset:Nn \g_file_curr_dir_str {#1}
8616   \str_gset:Nn \g_file_curr_name_str {#2}
8617   \str_gset:Nn \g_file_curr_ext_str {#3}

```

```
8618 }
```

(End definition for `\file_input:n` and others. These functions are documented on page 139.)

```
\file_parse_full_name:nNNN
  \_file_parse_full_name_auxi:w
  \_file_parse_full_name_split:nNNNTF
```

Parsing starts by stripping off any surrounding quotes. Then find the directory #4 by splitting at the last /. (The auxiliary returns `true/false` depending on whether it found the delimiter.) We correct for the case of a file in the root /, as in that case we wish to keep the trailing (and only) slash. Then split the base name #5 at the last dot. If there was indeed a dot, #5 contains the name and #6 the extension without the dot, which we add back for convenience. In the special case of no extension given, the auxiliary stored the name into #6, we just have to move it to #5.

```
8619 \cs_new_protected:Npn \file_parse_full_name:nNNN #1#2#3#4
8620 {
8621   \exp_after:wN \_file_parse_full_name_auxi:w
8622   \tl_to_str:n { #1 " #1 " } \q_stop #2#3#4
8623 }
8624 \cs_new_protected:Npn \_file_parse_full_name_auxi:w #1 " #2 " #3 \q_stop #4#5#6
8625 {
8626   \_file_parse_full_name_split:nNNNTF {#2} / #4 #5
8627   { \str_if_empty:NT #4 { \str_set:Nn #4 { / } } }
8628   { }
8629   \exp_args:No \_file_parse_full_name_split:nNNNTF {#5} . #5 #6
8630   { \str_put_left:Nn #6 { . } }
8631   {
8632     \str_set_eq:NN #5 #6
8633     \str_clear:N #6
8634   }
8635 }
8636 \cs_new_protected:Npn \_file_parse_full_name_split:nNNNTF #1#2#3#4
8637 {
8638   \cs_set_protected:Npn \_file_tmp:w ##1 ##2 #2 ##3 \q_stop
8639   {
8640     \tl_if_empty:nTF {##3}
8641     {
8642       \str_set:Nn #4 {##2}
8643       \tl_if_empty:nTF {##1}
8644       {
8645         \str_clear:N #3
8646         \use_ii:nn
8647       }
8648       {
8649         \str_set:Nx #3 { \str_tail:n {##1} }
8650         \use_i:nn
8651       }
8652     }
8653     { \_file_tmp:w { ##1 #2 ##2 } ##3 \q_stop }
8654   }
8655   \_file_tmp:w { } #1 #2 \q_stop
8656 }
```

(End definition for `\file_parse_full_name:nNNN`, `\_file_parse_full_name_auxi:w`, and `\_file_parse_full_name_split:nNNNTF`. These functions are documented on page 139.)

```
\file_show_list: A function to list all files used to the log, without duplicates. In package mode, if
\file_log_list: \@filelist is still defined, we need to take this list of file names into account (we
\_file_list_aux:n
```

capture it `\AtBeginDocument` into `\g__file_record_seq`), turning it to a string (this does not affect the commas of this comma list). The message system is a bit finnick (it can only display results that start with `>~` and end with a dot) so that constrains the possible markup. The advantage is that we get terminal and log outputs for free.

```

8657 \cs_new_protected:Npn \file_show_list:
8658 {
8659   \seq_clear:N \l__file_tmp_seq
8660 }*package)
8661   \clist_if_exist:NT \@filelist
8662   {
8663     \exp_args:NNx \seq_set_from_clist:Nn \l__file_tmp_seq
8664       { \tl_to_str:N \@filelist }
8665   }
8666 }/package)
8667   \seq_concat:NNN \l__file_tmp_seq \l__file_tmp_seq \g__file_record_seq
8668   \seq_remove_duplicates:N \l__file_tmp_seq
8669   \__msg_show_wrap:n
8670   {
8671     >~File~List~< \\
8672     \seq_map_function:NN \l__file_tmp_seq \__file_list_aux:n
8673     .....
8674   }
8675 }
8676 \cs_new:Npn \__file_list_aux:n #1 { #1 \\ }
8677 \cs_new_protected:Npn \file_log_list:
8678 { \__msg_log_next: \file_show_list: }

```

(End definition for `\file_show_list:`, `\file_log_list:`, and `\__file_list_aux:n`. These functions are documented on page 139.)

When used as a package, there is a need to hold onto the standard file list as well as the new one here. File names recorded in `\@filelist` must be turned to strings before being added to `\g__file_record_seq`.

```

8679 (*package)
8680 \AtBeginDocument
8681 {
8682   \exp_args:NNx \seq_set_from_clist:Nn \l__file_tmp_seq
8683     { \tl_to_str:N \@filelist }
8684   \seq_gconcat:NNN \g__file_record_seq \g__file_record_seq \l__file_tmp_seq
8685 }
8686 }/package)

```

## 17.2 Input operations

```
8687 (@@=ior)
```

### 17.2.1 Variables and constants

`\c_term_ior` Reading from the terminal (with a prompt) is done using a positive but non-existent stream number. Unlike writing, there is no concept of reading from the log.

```
8688 \int_const:Nn \c_term_ior { 16 }
```

(End definition for `\c_term_ior`. This variable is documented on page 146.)



`\g__ior_streams_seq` A list of the currently-available input streams to be used as a stack. In format mode, all streams (from 0 to 15) are available, while the package requests streams to L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> as they are needed (initially none are needed), so the starting point varies!

```

8689 \seq_new:N \g__ior_streams_seq
8690 \*initex
8691 \seq_gset_split:Nnn \g__ior_streams_seq { , }
8692 { 0 , 1 , 2 , 3 , 4 , 5 , 6 , 7 , 8 , 9 , 10 , 11 , 12 , 13 , 14 , 15 }
8693 \</initex>

```

(End definition for `\g__ior_streams_seq`.)

`\l__ior_stream_tl` Used to recover the raw stream number from the stack.

```

8694 \tl_new:N \l__ior_stream_tl

```

(End definition for `\l__ior_stream_tl`.)

`\g__ior_streams_prop` The name of the file attached to each stream is tracked in a property list. To get the correct number of reserved streams in package mode the underlying mechanism needs to be queried. For L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> and plain T<sub>E</sub>X this data is stored in `\count16`: with the `etex` package loaded we need to subtract 1 as the register holds the number of the next stream to use. In ConT<sub>E</sub>Xt, we need to look at `\count38` but there is no subtraction: like the original plain T<sub>E</sub>X/L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> mechanism it holds the value of the *last* stream allocated.

```

8695 \prop_new:N \g__ior_streams_prop
8696 \*package
8697 \int_step_inline:nnnn
8698 { 0 }
8699 { 1 }
8700 {
8701   \cs_if_exist:NTF \normalend
8702   { \tex_count:D 38 \scan_stop: }
8703   {
8704     \tex_count:D 16 \scan_stop:
8705     \cs_if_exist:NT \loccount { - 1 }
8706   }
8707 }
8708 {
8709   \prop_gput:Nnn \g__ior_streams_prop {#1} { Reserved-by~format }
8710 }
8711 \</package>

```

(End definition for `\g__ior_streams_prop`.)

### 17.2.2 Stream management

`\ior_new:N` Reserving a new stream is done by defining the name as equal to using the terminal.

```

\ior_new:c
8712 \cs_new_protected:Npn \ior_new:N #1 { \cs_new_eq:NN #1 \c_term_ior }
8713 \cs_generate_variant:Nn \ior_new:N { c }

```

(End definition for `\ior_new:N`. This function is documented on page 140.)

`\ior_open:Nn` Use the conditional version, with an error if the file is not found.

```

\ior_open:cn
8714 \cs_new_protected:Npn \ior_open:Nn #1#2
8715 { \ior_open:NnF #1 {#2} { \__file_missing:n {#2} } }
8716 \cs_generate_variant:Nn \ior_open:Nn { c }

```

(End definition for `\ior_open:Nn`. This function is documented on page 140.)

`\ior_open:NnTF` An auxiliary searches for the file in the T<sub>E</sub>X, L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> and L<sup>A</sup>T<sub>E</sub>X 3 paths. Then pass the  
`\ior_open:cnTF` file found to the lower-level function which deals with streams. The `full_name` is empty when the file is not found.

```

8717 \prg_new_protected_conditional:Npnn \ior_open:Nn #1#2 { T , F , TF }
8718 {
8719   \file_get_full_name:nN {#2} \l__file_full_name_str
8720   \str_if_empty:NTF \l__file_full_name_str
8721     { \prg_return_false: }
8722     {
8723       \__ior_open:No #1 \l__file_full_name_str
8724       \prg_return_true:
8725     }
8726 }
8727 \cs_generate_variant:Nn \ior_open:NnT { c }
8728 \cs_generate_variant:Nn \ior_open:NnF { c }
8729 \cs_generate_variant:Nn \ior_open:NnTF { c }

```

(End definition for `\ior_open:NnTF`. This function is documented on page 140.)

`\__ior_new:N` In package mode, streams are reserved using `\newread` before they can be managed by `ior`. To prevent `ior` from being affected by redefinitions of `\newread` (such as done by the third-party package `morewrites`), this macro is saved here under a private name. The complicated code ensures that `\__ior_new:N` is not `\outer` despite plain T<sub>E</sub>X's `\newread` being `\outer`.

```

8730 \*package>
8731 \exp_args:NNf \cs_new_protected:Npn \__ior_new:N
8732   { \exp_args:NNc \exp_after:wN \exp_stop_f: { newread } }
8733 \*package>

```

(End definition for `\__ior_new:N`.)

`\__ior_open:Nn` The stream allocation itself uses the fact that there is a list of all of those available, so  
`\__ior_open:No` allocation is simply a question of using the number at the top of the list. In package  
`\__ior_open_stream:Nn` mode, life gets more complex as it's important to keep things in sync. That is done using a two-part approach: any streams that have already been taken up by `ior` but are now free are tracked, so we first try those. If that fails, ask plain T<sub>E</sub>X or L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> for a new stream and use that number (after a bit of conversion).

```

8734 \cs_new_protected:Npn \__ior_open:Nn #1#2
8735 {
8736   \ior_close:N #1
8737   \seq_gpop:NNTF \g__ior_streams_seq \l__ior_stream_tl
8738     { \__ior_open_stream:Nn #1 {#2} }
8739 \*initex>
8740   { \_msg_kernel_fatal:nn { kernel } { input-streams-exhausted } }
8741 \*initex>
8742 \*package>
8743   {
8744     \__ior_new:N #1
8745     \tl_set:Nx \l__ior_stream_tl { \int_eval:n {#1} }
8746     \__ior_open_stream:Nn #1 {#2}
8747   }

```

```

8748 \endpackage
8749 }
8750 \cs_generate_variant:Nn \__ior_open:Nn { No }
8751 \cs_new_protected:Npn \__ior_open_stream:Nn #1#2
8752 {
8753   \tex_global:D \tex_chardef:D #1 = \l__ior_stream_tl \scan_stop:
8754   \prop_gput:NVn \g__ior_streams_prop #1 {#2}
8755   \tex_openin:D #1 #2 \scan_stop:
8756 }

```

(End definition for `\__ior_open:Nn` and `\__ior_open_stream:Nn`.)

**`\ior_close:N`** Closing a stream means getting rid of it at the T<sub>E</sub>X level and removing from the various data structures. Unless the name passed is an invalid stream number (outside the range [0, 15]), it can be closed. On the other hand, it only gets added to the stack if it was not already there, to avoid duplicates building up.

**`\ior_close:c`**

```

8757 \cs_new_protected:Npn \ior_close:N #1
8758 {
8759   \int_compare:nT { -1 < #1 < \c_term_ior }
8760   {
8761     \tex_closein:D #1
8762     \prop_gremove:NV \g__ior_streams_prop #1
8763     \seq_if_in:NVF \g__ior_streams_seq #1
8764     { \seq_gpush:NV \g__ior_streams_seq #1 }
8765     \cs_gset_eq:NN #1 \c_term_ior
8766   }
8767 }
8768 \cs_generate_variant:Nn \ior_close:N { c }

```

(End definition for `\ior_close:N`. This function is documented on page 140.)

**`\ior_show_list:`** Show the property lists, but with some “pretty printing”. See the `l3msg` module. The first argument of the message is `ior` (as opposed to `iow`) and the second is empty if no read stream is open and non-empty (in fact a question mark) otherwise. The code of the message `show-streams` takes care of translating `ior/iow` to English. The list of streams is formatted using `\__msg_show_item_unbraced:nn`.

**`\ior_log_list:`**

**`\__ior_list:Nn`**

```

8769 \cs_new_protected:Npn \ior_show_list:
8770 { \__ior_list:Nn \g__ior_streams_prop { ior } }
8771 \cs_new_protected:Npn \ior_log_list:
8772 { \__msg_log_next: \ior_show_list: }
8773 \cs_new_protected:Npn \__ior_list:Nn #1#2
8774 {
8775   \__msg_show_pre:nnxxxx { LaTeX / kernel } { show-streams }
8776   {#2} { \prop_if_empty:NF #1 { ? } } { } { }
8777   \__msg_show_wrap:n
8778   { \prop_map_function:NN #1 \__msg_show_item_unbraced:nn }
8779 }

```

(End definition for `\ior_show_list:`, `\ior_log_list:`, and `\__ior_list:Nn`. These functions are documented on page 140.)

### 17.2.3 Reading input

**\if\_eof:w** The primitive conditional

```
8780 \cs_new_eq:NN \if_eof:w \tex_ifeof:D
```

(End definition for \if\_eof:w.)

**\ior\_if\_eof\_p:N** To test if some particular input stream is exhausted the following conditional is provided.  
**\ior\_if\_eof:N $\underline{TF}$**  The primitive test can only deal with numbers in the range [0,15] so we catch outliers (they are exhausted).

```
8781 \prg_new_conditional:Npnn \ior_if_eof:N #1 { p , T , F , TF }
8782 {
8783   \cs_if_exist:NTF #1
8784   {
8785     \int_compare:nTF { -1 < #1 < \c_term_ior }
8786     {
8787       \if_eof:w #1
8788       \prg_return_true:
8789       \else:
8790       \prg_return_false:
8791       \fi:
8792     }
8793     { \prg_return_true: }
8794   }
8795   { \prg_return_true: }
8796 }
```

(End definition for \ior\_if\_eof:N $\underline{TF}$ . This function is documented on page 143.)

**\ior\_get:NN** And here we read from files.

```
8797 \cs_new_protected:Npn \ior_get:NN #1#2
8798 { \tex_read:D #1 to #2 }
```

(End definition for \ior\_get:NN. This function is documented on page 141.)

**\ior\_str\_get:NN** Reading as strings is a more complicated wrapper, as we wish to remove the endline character.

```
8799 \cs_new_protected:Npn \ior_str_get:NN #1#2
8800 {
8801   \use:x
8802   {
8803     \int_set:Nn \tex_endlinechar:D { -1 }
8804     \exp_not:n { \etex_readline:D #1 to #2 }
8805     \int_set:Nn \tex_endlinechar:D { \int_use:N \tex_endlinechar:D }
8806   }
8807 }
```

(End definition for \ior\_str\_get:NN. This function is documented on page 141.)

**\ior\_map\_break:** Usual map breaking functions.

```
\ior_map_break:n
8808 \cs_new:Npn \ior_map_break:
8809 { \__prg_map_break:NN \ior_map_break: { } }
8810 \cs_new:Npn \ior_map_break:n
8811 { \__prg_map_break:NN \ior_map_break: }
```

(End definition for `\ior_map_break:` and `\ior_map_break:n`. These functions are documented on page 142.)

```

\ior_map_inline:Nn Mapping to an input stream can be done on either a token or a string basis, hence the
\ior_str_map_inline:Nn set up. Within that, there is a check to avoid reading past the end of a file, hence the
  \__ior_map_inline:NNn two applications of \ior_if_eof:N. This mapping cannot be nested with twice the same
  \__ior_map_inline:NNNn stream, as the stream has only one “current line”.
\__ior_map_inline_loop:NNN
  \l__ior_internal_tl
8812 \cs_new_protected:Npn \ior_map_inline:Nn
8813   { \__ior_map_inline:NNn \ior_get:NN }
8814 \cs_new_protected:Npn \ior_str_map_inline:Nn
8815   { \__ior_map_inline:NNn \ior_str_get:NN }
8816 \cs_new_protected:Npn \__ior_map_inline:NNn
8817   {
8818     \int_gincr:N \g__prg_map_int
8819     \exp_args:Nc \__ior_map_inline:NNNn
8820       { __prg_map_ \int_use:N \g__prg_map_int :n }
8821   }
8822 \cs_new_protected:Npn \__ior_map_inline:NNNn #1#2#3#4
8823   {
8824     \cs_gset_protected:Npn #1 ##1 {#4}
8825     \ior_if_eof:NF #3 { \__ior_map_inline_loop:NNN #1#2#3 }
8826     \__prg_break_point:Nn \ior_map_break:
8827       { \int_gdecr:N \g__prg_map_int }
8828   }
8829 \cs_new_protected:Npn \__ior_map_inline_loop:NNN #1#2#3
8830   {
8831     #2 #3 \l__ior_internal_tl
8832     \ior_if_eof:NF #3
8833     {
8834       \exp_args:No #1 \l__ior_internal_tl
8835       \__ior_map_inline_loop:NNN #1#2#3
8836     }
8837   }
8838 \tl_new:N \l__ior_internal_tl

```

(End definition for `\ior_map_inline:Nn` and others. These functions are documented on page 142.)

`\g__file_internal_ior` Needed by the higher-level code, but cannot be created until here.

```
8839 \ior_new:N \g__file_internal_ior
```

(End definition for `\g__file_internal_ior`.)

## 17.3 Output operations

```
8840 <@@=iow>
```

There is a lot of similarity here to the input operations, at least for many of the basics. Thus quite a bit is copied from the earlier material with minor alterations.

### 17.3.1 Variables and constants

`\c_log_iow` Here we allocate two output streams for writing to the transcript file only (`\c_log_iow`)  
`\c_term_iow` and to both the terminal and transcript file (`\c_term_iow`). Recent LuaTeX provide 128 write streams; we also use `\c_term_iow` as the first non-allowed write stream so its value depends on the engine.

```

8841 \int_const:Nn \c_log_iow { -1 }
8842 \int_const:Nn \c_term_iow
8843 {
8844   \cs_if_exist:NTF \luatex_directlua:D
8845   {
8846     \int_compare:nNnTF \luatex luatexversion:D > { 80 }
8847     { 128 }
8848     { 16 }
8849   }
8850   { 16 }
8851 }

```

(End definition for `\c_log_iow` and `\c_term_iow`. These variables are documented on page 146.)

`\g__iow_streams_seq` A list of the currently-available output streams to be used as a stack.

```

8852 \seq_new:N \g__iow_streams_seq
8853 \*initex
8854 \use:x
8855 {
8856   \exp_not:n { \seq_gset_split:Nnn \g__iow_streams_seq { } }
8857   {
8858     \int_step_function:nnnN { 0 } { 1 } { \c_term_iow }
8859     \prg_do_nothing:
8860   }
8861 }
8862 \</initex>

```

(End definition for `\g__iow_streams_seq`.)

`\l__iow_stream_tl` Used to recover the raw stream number from the stack.

```

8863 \tl_new:N \l__iow_stream_tl

```

(End definition for `\l__iow_stream_tl`.)

`\g__iow_streams_prop` As for reads with the appropriate adjustment of the register numbers to check on.

```

8864 \prop_new:N \g__iow_streams_prop
8865 \*package
8866 \int_step_inline:nnnn
8867 { 0 }
8868 { 1 }
8869 {
8870   \cs_if_exist:NTF \normalend
8871   { \tex_count:D 39 \scan_stop: }
8872   {
8873     \tex_count:D 17 \scan_stop:
8874     \cs_if_exist:NT \loccount { - 1 }
8875   }
8876 }
8877 {
8878   \prop_gput:Nnn \g__iow_streams_prop {#1} { Reserved-by~format }
8879 }
8880 \</package>

```

(End definition for `\g__iow_streams_prop`.)

## 17.4 Stream management

**\iow\_new:N** Reserving a new stream is done by defining the name as equal to writing to the terminal:  
**\iow\_new:c** odd but at least consistent.

```
8881 \cs_new_protected:Npn \iow_new:N #1 { \cs_new_eq:NN #1 \c_term_iow }
8882 \cs_generate_variant:Nn \iow_new:N { c }
```

(End definition for \iow\_new:N. This function is documented on page 140.)

**\\_\_iow\_new:N** As for read streams, copy \newwrite in package mode, making sure that it is not \outer.

```
8883 \*package
8884 \exp_args:NNf \cs_new_protected:Npn \__iow_new:N
8885 { \exp_args:NNc \exp_after:wN \exp_stop_f: { newwrite } }
8886 \*package
```

(End definition for \\_\_iow\_new:N.)

**\iow\_open:Nn** The same idea as for reading, but without the path and without the need to allow for a  
**\iow\_open:cn** conditional version.

```
\__iow_open_stream:Nn 8887 \cs_new_protected:Npn \iow_open:Nn #1#2
\__iow_open_stream:NV 8888 {
8889   \__file_name_sanitize:nN {#2} \l__file_base_name_str
8890   \iow_close:N #1
8891   \seq_gpop:NNTF \g__iow_streams_seq \l__iow_stream_tl
8892   { \__iow_open_stream:NV #1 \l__file_base_name_str }
8893 \*initex
8894 { \__msg_kernel_fatal:nn { kernel } { output-streams-exhausted } }
8895 \*initex
8896 \*package
8897 {
8898   \__iow_new:N #1
8899   \tl_set:Nx \l__iow_stream_tl { \int_eval:n {#1} }
8900   \__iow_open_stream:NV #1 \l__file_base_name_str
8901 }
8902 \*package
8903 }
8904 \cs_generate_variant:Nn \iow_open:Nn { c }
8905 \cs_new_protected:Npn \__iow_open_stream:Nn #1#2
8906 {
8907   \tex_global:D \tex_chardef:D #1 = \l__iow_stream_tl \scan_stop:
8908   \prop_gput:NVn \g__iow_streams_prop #1 {#2}
8909   \tex_immediate:D \tex_openout:D #1 #2 \scan_stop:
8910 }
8911 \cs_generate_variant:Nn \__iow_open_stream:Nn { NV }
```

(End definition for \iow\_open:Nn and \\_\_iow\_open\_stream:Nn. These functions are documented on page 140.)

**\iow\_close:N** Closing a stream is not quite the reverse of opening one. First, the close operation is  
**\iow\_close:c** easier than the open one, and second as the stream is actually a number we can use it directly to show that the slot has been freed up.

```
8912 \cs_new_protected:Npn \iow_close:N #1
8913 {
8914   \int_compare:nT { - \c_log_iow < #1 < \c_term_iow }
8915   {
```

```

8916         \tex_immediate:D \tex_closeout:D #1
8917         \prop_gremove:NV \g__iow_streams_prop #1
8918         \seq_if_in:NVF \g__iow_streams_seq #1
8919         { \seq_gpush:NV \g__iow_streams_seq #1 }
8920         \cs_gset_eq:NN #1 \c_term_iow
8921     }
8922 }
8923 \cs_generate_variant:Nn \iow_close:N { c }

```

(End definition for `\iow_close:N`. This function is documented on page 140.)

`\iow_show_list:` Done as for input, but with a copy of the auxiliary so the name is correct.

```

\iow_log_list:
\__iow_list:Nn
8924 \cs_new_protected:Npn \iow_show_list:
8925 { \__iow_list:Nn \g__iow_streams_prop { iow } }
8926 \cs_new_protected:Npn \iow_log_list:
8927 { \__msg_log_next: \iow_show_list: }
8928 \cs_new_eq:NN \__iow_list:Nn \__ior_list:Nn

```

(End definition for `\iow_show_list:`, `\iow_log_list:`, and `\__iow_list:Nn`. These functions are documented on page 140.)

#### 17.4.1 Deferred writing

`\iow_shipout_x:Nn` First the easy part, this is the primitive, which expects its argument to be braced.

```

\iow_shipout_x:Nx
\iow_shipout_x:cn
\iow_shipout_x:cx
8929 \cs_new_protected:Npn \iow_shipout_x:Nn #1#2
8930 { \tex_write:D #1 {#2} }
8931 \cs_generate_variant:Nn \iow_shipout_x:Nn { c, Nx, cx }

```

(End definition for `\iow_shipout_x:Nn`. This function is documented on page 144.)

`\iow_shipout:Nn` With  $\varepsilon$ -TEX available deferred writing without expansion is easy.

```

\iow_shipout:Nx
\iow_shipout:cn
\iow_shipout:cx
8932 \cs_new_protected:Npn \iow_shipout:Nn #1#2
8933 { \tex_write:D #1 { \exp_not:n {#2} } }
8934 \cs_generate_variant:Nn \iow_shipout:Nn { c, Nx, cx }

```

(End definition for `\iow_shipout:Nn`. This function is documented on page 144.)

#### 17.4.2 Immediate writing

`\__iow_with:Nnn` If the integer #1 is equal to #2, just leave #3 in the input stream. Otherwise, pass the old value to an auxiliary, which sets the integer to the new value, runs the code, and restores the integer.

```

\__iow_with_aux:nNnn
8935 \cs_new_protected:Npn \__iow_with:Nnn #1#2
8936 {
8937     \int_compare:nNnTF {#1} = {#2}
8938     { \use:n }
8939     { \exp_args:No \__iow_with_aux:nNnn { \int_use:N #1 } #1 {#2} }
8940 }
8941 \cs_new_protected:Npn \__iow_with_aux:nNnn #1#2#3#4
8942 {
8943     \int_set:Nn #2 {#3}
8944     #4
8945     \int_set:Nn #2 {#1}
8946 }

```



(End definition for `\_iow\_with:Nnn` and `\_iow\_with\_aux:nNnn`.)

**`\iow\_now:Nn`** This routine writes the second argument onto the output stream without expansion. If this stream isn't open, the output goes to the terminal instead. If the first argument is `\iow\_now:Nx` no output stream at all, we get an internal error. We don't use the expansion done by `\iow\_now:cn` `\write` to get the `Nx` variant, because it differs in subtle ways from `x`-expansion, namely, macro parameter characters would not need to be doubled. We set the `\newlinechar` to 10 using `\_iow\_with:Nnn` to support formats such as plain T<sub>E</sub>X: otherwise, `\iow\_newline:` would not work. We do not do this for `\iow\_shipout:Nn` or `\iow\_shipout\_x:Nn`, as T<sub>E</sub>X looks at the value of the `\newlinechar` at shipout time in those cases.

```
8947 \cs_new_protected:Npn \iow_now:Nn #1#2
8948 {
8949   \_iow\_with:Nnn \tex_newlinechar:D { '\^^J }
8950   { \tex_immediate:D \tex_write:D #1 { \exp_not:n {#2} } }
8951 }
8952 \cs_generate_variant:Nn \iow_now:Nn { c, Nx, cx }
```

(End definition for `\iow\_now:Nn`. This function is documented on page 143.)

**`\iow\_log:n`** Writing to the log and the terminal directly are relatively easy.  
**`\iow\_log:x`**  
**`\iow\_term:n`**  
**`\iow\_term:x`**

```
8953 \cs_set_protected:Npn \iow_log:x { \iow_now:Nx \c_log_iow }
8954 \cs_new_protected:Npn \iow_log:n { \iow_now:Nn \c_log_iow }
8955 \cs_set_protected:Npn \iow_term:x { \iow_now:Nx \c_term_iow }
8956 \cs_new_protected:Npn \iow_term:n { \iow_now:Nn \c_term_iow }
```

(End definition for `\iow\_log:n` and `\iow\_term:n`. These functions are documented on page 143.)

### 17.4.3 Special characters for writing

**`\iow\_newline:`** Global variable holding the character that forces a new line when something is written to an output stream.

```
8957 \cs_new:Npn \iow_newline: { ^^J }
```

(End definition for `\iow\_newline:`. This function is documented on page 144.)

**`\iow\_char:N`** Function to write any escaped char to an output stream.

```
8958 \cs_new_eq:NN \iow_char:N \cs_to_str:N
```

(End definition for `\iow\_char:N`. This function is documented on page 144.)

### 17.4.4 Hard-wrapping lines to a character count

The code here implements a generic hard-wrapping function. This is used by the messaging system, but is designed such that it is available for other uses.

**`\c\_catcode\_other\_space\_tl`** Create a space with category code 12: an “other” space.

```
8959 \tl_const:Nx \c_catcode\_other\_space\_tl { \char_generate:nn { '\ } { 12 } }
```

(End definition for `\c\_catcode\_other\_space\_tl`. This function is documented on page 145.)

**`\l\_iow\_line\_count\_int`** This is the “raw” number of characters in a line which can be written to the terminal. The standard value is the line length typically used by T<sub>E</sub>XLive and MikT<sub>E</sub>X.

```
8960 \int_new:N \l_iow_line_count_int
8961 \int_set:Nn \l_iow_line_count_int { 78 }
```

(End definition for `\l_iow_line_count_int`. This variable is documented on page 145.)

`\l__iow_newline_tl` The token list inserted to produce a new line, with the *<run-on text>*.

```
8962 \tl_new:N \l__iow_newline_tl
```

(End definition for `\l__iow_newline_tl`.)

`\l_iow_line_target_int` This stores the target line count: the full number of characters in a line, minus any part for a leader at the start of each line.

```
8963 \int_new:N \l_iow_line_target_int
```

(End definition for `\l_iow_line_target_int`.)

`\__iow_set_indent:n` The `one_indent` variables hold one indentation marker and its length. The `\__iow_unindent:w` auxiliary removes one indentation. The function `\__iow_set_indent:n` (that could possibly be public) sets the indentation in a consistent way. We set it to four spaces by default.

```
8964 \tl_new:N \l__iow_one_indent_tl
8965 \int_new:N \l__iow_one_indent_int
8966 \cs_new:Npn \__iow_unindent:w { }
8967 \cs_new_protected:Npn \__iow_set_indent:n #1
8968 {
8969   \tl_set:Nx \l__iow_one_indent_tl
8970     { \exp_args:No \__str_to_other_fast:n { \tl_to_str:n {#1} } }
8971   \int_set:Nn \l__iow_one_indent_int { \str_count:N \l__iow_one_indent_tl }
8972   \exp_last_unbraced:NNo
8973     \cs_set:Npn \__iow_unindent:w \l__iow_one_indent_tl { }
8974 }
8975 \exp_args:Nx \__iow_set_indent:n { \prg_replicate:nn { 4 } { ~ } }
```

(End definition for `\__iow_set_indent:n` and others.)

`\l_iow_indent_tl` The current indentation (some copies of `\l__iow_one_indent_tl`) and its number of characters.

```
8976 \tl_new:N \l_iow_indent_tl
8977 \int_new:N \l_iow_indent_int
```

(End definition for `\l_iow_indent_tl` and `\l_iow_indent_int`.)

`\l_iow_line_tl` These hold the current line of text and a partial line to be added to it, respectively.

```
8978 \tl_new:N \l_iow_line_tl
8979 \tl_new:N \l_iow_line_part_tl
```

(End definition for `\l_iow_line_tl` and `\l_iow_line_part_tl`.)

`\l_iow_line_break_bool` Indicates whether the line was broken precisely at a chunk boundary.

```
8980 \bool_new:N \l_iow_line_break_bool
```

(End definition for `\l_iow_line_break_bool`.)

`\l__iow_wrap_tl` Used for the expansion step before detokenizing, and for the output from wrapping text: fully expanded and with lines which are not overly long.

```
8981 \tl_new:N \l__iow_wrap_tl
```

(End definition for `\l__iow_wrap_tl`.)

`\c__iow_wrap_marker_tl` Every special action of the wrapping code is starts with the same recognizable string, `\c__iow_wrap_end_marker_tl` `\c__iow_wrap_marker_tl`. Upon seeing that “word”, the wrapping code reads one space-delimited argument to know what operation to perform. The setting of `\escapechar` here is not very important, but makes `\c__iow_wrap_marker_tl` look marginally nicer.

```

8982 \group_begin:
8983   \int_set:Nn \tex_escapechar:D { -1 }
8984   \tl_const:Nx \c__iow_wrap_marker_tl
8985     { \tl_to_str:n { \^^I \^^O \^^W \^^_ \^^W \^^R \^^A \^^P } }
8986 \group_end:
8987 \tl_map_inline:nn
8988   { { end } { newline } { indent } { unindent } }
8989   {
8990     \tl_const:cx { c__iow_wrap_ #1 _marker_tl }
8991     {
8992       \c__iow_wrap_marker_tl
8993       #1
8994       \c_catcode_other_space_tl
8995     }
8996   }

```

(End definition for `\c__iow_wrap_marker_tl` and others.)

`\iow_indent:n` We set `\iow_indent:n` to produce an error when outside messages. Within wrapped message, it is set to `\__iow_indent:n` when valid and otherwise to `\__iow_indent_error:n`. The first places the instruction for increasing the indentation before its argument, and the instruction for unindenting afterwards. The second produces an error expandably. Note that there are no forced line-break, so the indentation only changes when the next line is started.

```

8997 \cs_new_protected:Npn \iow_indent:n #1
8998   {
8999     \__msg_kernel_error:nnnnn { kernel } { iow-indent }
9000     { \iow_wrap:nnnN } { \iow_indent:n } { #1 }
9001     #1
9002   }
9003 \cs_new:Npx \__iow_indent:n #1
9004   {
9005     \c__iow_wrap_indent_marker_tl
9006     #1
9007     \c__iow_wrap_unindent_marker_tl
9008   }
9009 \cs_new:Npn \__iow_indent_error:n #1
9010   {
9011     \__msg_kernel_expandable_error:nnnnn { kernel } { iow-indent }
9012     { \iow_wrap:nnnN } { \iow_indent:n } { #1 }
9013     #1
9014   }

```

(End definition for `\iow_indent:n`, `\__iow_indent:n`, and `\__iow_indent_error:n`. These functions are documented on page 145.)

`\iow_wrap:nnnN` The main wrapping function works as follows. First give `\`, `\_` and other formatting commands the correct definition for messages and perform the given setup #3. The definition of `\_` uses an “other” space rather than a normal space, because the latter might be absorbed by `TeX` to end a number or other f-type expansions.

```

9015 \cs_new_protected:Npn \iow_wrap:nnnN #1#2#3#4
9016 {
9017   \group_begin:
9018     \int_set:Nn \tex_escapechar:D { -1 }
9019     \cs_set:Npx \{ { \token_to_str:N \{ }
9020     \cs_set:Npx \# { \token_to_str:N \# }
9021     \cs_set:Npx \} { \token_to_str:N \} }
9022     \cs_set:Npx \% { \token_to_str:N \% }
9023     \cs_set:Npx \~ { \token_to_str:N \~ }
9024     \int_set:Nn \tex_escapechar:D { 92 }
9025     \cs_set_eq:NN \ \ \c__iow_wrap_newline_marker_tl
9026     \cs_set_eq:NN \ \ \c_catcode_other_space_tl
9027     \cs_set_eq:NN \iow_indent:n \__iow_indent:n
9028     #3

```

Then fully-expand the input: in package mode, the expansion uses L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>’s `\protected` mechanism. As soon as the expansion is done, reset `\iow_indent:n` to its error definition: it only works in the first argument of `\iow_wrap:nnnN`.

```

9029 <*initex>
9030   \tl_set:Nx \l__iow_wrap_tl {#1}
9031 </initex>
9032 <*package>
9033   \__iow_wrap_set:Nx \l__iow_wrap_tl {#1}
9034 </package>
9035   \cs_set_eq:NN \iow_indent:n \__iow_indent_error:n

```

Afterwards, set the newline marker (two assignments to fully expand, then convert to a string) and initialize the target count for lines (the first line has target count `\l_iow_line_count_int` instead).

```

9036   \tl_set:Nx \l__iow_newline_tl { \iow_newline: #2 }
9037   \tl_set:Nx \l__iow_newline_tl { \tl_to_str:N \l__iow_newline_tl }
9038   \int_set:Nn \l__iow_line_target_int
9039     { \l_iow_line_count_int - \str_count:N \l__iow_newline_tl + 1 }

```

There is then a loop over the input, which stores the wrapped result in `\l__iow_wrap_tl`. After the loop, the resulting text is passed on to the function which has been given as a post-processor. The `\tl_to_str:N` step converts the “other” spaces back to normal spaces. The `f`-expansion removes a leading space from `\l__iow_wrap_tl`.

```

9040   \__iow_wrap_do:
9041   \exp_args:NNf \group_end:
9042   #4 { \tl_to_str:N \l__iow_wrap_tl }
9043 }

```

As using the generic loader means that `\protected@edef` is not available, it’s not placed directly in the wrap function but is set up as an auxiliary. In the generic loader this can then be redefined.

```

9044 <*package>
9045 \cs_new_eq:NN \__iow_wrap_set:Nx \protected@edef
9046 </package>

```

(End definition for `\iow_wrap:nnnN` and `\__iow_wrap_set:Nx`. These functions are documented on page 145.)

`\__iow_wrap_do:` Escape spaces. Set up a few variables, in particular the initial value of `\l__iow_wrap_tl`:  
`\__iow_wrap_start:w` the space stops the `f`-expansion of the main wrapping function and `\use_none:n` removes

a newline marker inserted by later code. The main loop consists of repeatedly calling the `chunk` auxiliary to wrap chunks delimited by (newline or indentation) markers.

```

9047 \cs_new_protected:Npn \__iow_wrap_do:
9048 {
9049   \tl_set:Nx \l__iow_wrap_tl
9050   {
9051     \exp_args:No \__str_to_other_fast:n \l__iow_wrap_tl
9052     \c__iow_wrap_end_marker_tl
9053   }
9054   \exp_after:wN \__iow_wrap_start:w \l__iow_wrap_tl
9055 }
9056 \cs_new_protected:Npn \__iow_wrap_start:w
9057 {
9058   \bool_set_false:N \l__iow_line_break_bool
9059   \tl_clear:N \l__iow_line_tl
9060   \tl_clear:N \l__iow_line_part_tl
9061   \tl_set:Nn \l__iow_wrap_tl { ~ \use_none:n }
9062   \int_zero:N \l__iow_indent_int
9063   \tl_clear:N \l__iow_indent_tl
9064   \__iow_wrap_chunk:nw { \l__iow_line_count_int }
9065 }

```

(End definition for `\__iow_wrap_do:` and `\__iow_wrap_start:w`.)

`\__iow_wrap_chunk:nw`  
`\__iow_wrap_next:nw`

The `chunk` and `next` auxiliaries are defined indirectly to obtain the expansions of `\c_catcode_other_space_tl` and `\c__iow_wrap_marker_tl` in their definition. The `next` auxiliary calls a function corresponding to the type of marker (its `##2`), which can be `newline` or `indent` or `unindent` or `end`. The first argument of the `chunk` auxiliary is a target number of characters and the second is some string to wrap. If the chunk is empty simply call `next`. Otherwise, set up a call to `\__iow_wrap_line:nw`, including the indentation if the current line is empty, and including a trailing space (`#1`) before the `\__iow_wrap_end_chunk:w` auxiliary.

```

9066 \cs_set_protected:Npn \__iow_tmp:w #1#2
9067 {
9068   \cs_new_protected:Npn \__iow_wrap_chunk:nw ##1##2 #2
9069   {
9070     \tl_if_empty:nTF {##2}
9071     {
9072       \tl_clear:N \l__iow_line_part_tl
9073       \__iow_wrap_next:nw {##1}
9074     }
9075     {
9076       \tl_if_empty:NTF \l__iow_line_tl
9077       {
9078         \__iow_wrap_line:nw
9079         { \l__iow_indent_tl }
9080         ##1 - \l__iow_indent_int ;
9081       }
9082       { \__iow_wrap_line:nw { } ##1 ; }
9083       ##2 #1
9084       \__iow_wrap_end_chunk:w 7 6 5 4 3 2 1 0 \q_stop
9085     }
9086   }

```

```

9087 \cs_new_protected:Npn \__iow_wrap_next:nw ##1##2 #1
9088 { \use:c { __iow_wrap_##2:n } {##1} }
9089 }
9090 \exp_args:NVV \__iow_tmp:w \c_catcode_other_space_tl \c__iow_wrap_marker_tl

```

(End definition for \\_\_iow\_wrap\_chunk:nw and \\_\_iow\_wrap\_next:nw.)

```

\__iow_wrap_line:nw
\__iow_wrap_line_loop:w
\__iow_wrap_line_aux:Nw
\__iow_wrap_line_end:NnnnnnnnN
\__iow_wrap_line_end:nw
\__iow_wrap_end_chunk:w

```

This is followed by  $\{\langle string \rangle\} \langle intexpr \rangle$  ;. It stores the  $\langle string \rangle$  and up to  $\langle intexpr \rangle$  characters from the current chunk into  $\backslash l\_iow\_line\_part\_tl$ . Characters are grabbed 8 at a time and left in  $\backslash l\_iow\_line\_part\_tl$  by the `line_loop` auxiliary. When  $k < 8$  remain to be found, the `line_aux` auxiliary calls the `line_end` auxiliary followed by (the single digit)  $k$ , then  $7 - k$  empty brace groups, then the chunk's remaining characters. The `line_end` auxiliary leaves  $k$  characters from the chunk in the line part, then ends the assignment. Ignore the `\use_none:nnnnn` line for now. If the next character is a space the line can be broken there: store what we found into the result and get the next line. Otherwise some work is needed to find a break-point. So far we have ignored what happens if the chunk is shorter than the requested number of characters: this is dealt with by the `end_chunk` auxiliary, which gets treated like a character by the rest of the code. It ends up being called either as one of the arguments #2-#9 of the `line_loop` auxiliary or as one of the arguments #2-#8 of the `line_end` auxiliary. In both cases stop the assignment and work out how many characters are still needed. The weird `\use_none:nnnnn` ensures that the required data is in the right place.

```

9091 \cs_new_protected:Npn \__iow_wrap_line:nw #1
9092 {
9093   \tex_edef:D \l__iow_line_part_tl { \if_false: } \fi:
9094   #1
9095   \exp_after:wN \__iow_wrap_line_loop:w
9096   \__int_value:w \__int_eval:w
9097 }
9098 \cs_new:Npn \__iow_wrap_line_loop:w #1 ; #2#3#4#5#6#7#8#9
9099 {
9100   \if_int_compare:w #1 < 8 \exp_stop_f:
9101     \__iow_wrap_line_aux:Nw #1
9102   \fi:
9103   #2 #3 #4 #5 #6 #7 #8 #9
9104   \exp_after:wN \__iow_wrap_line_loop:w
9105   \__int_value:w \__int_eval:w #1 - 8 ;
9106 }
9107 \cs_new:Npn \__iow_wrap_line_aux:Nw #1#2#3 \exp_after:wN #4 ;
9108 {
9109   #2
9110   \exp_after:wN \__iow_wrap_line_end:NnnnnnnnN
9111   \exp_after:wN #1
9112   \exp:w \exp_end_continue_f:w
9113   \exp_after:wN \exp_after:wN
9114   \if_case:w #1 \exp_stop_f:
9115     \prg_do_nothing:
9116   \or: \use_none:n
9117   \or: \use_none:nn
9118   \or: \use_none:nnn
9119   \or: \use_none:nnnn
9120   \or: \use_none:nnnnn
9121   \or: \use_none:nnnnnn

```

```

9122 \or: \use_none:nnnnnnn
9123 \fi:
9124 { } { } { } { } { } { } { } { } { } #3
9125 }
9126 \cs_new:Npn \__iow_wrap_line_end:NnnnnnnN #1#2#3#4#5#6#7#8#9
9127 {
9128     #2 #3 #4 #5 #6 #7 #8
9129     \use_none:nnnnn \__int_eval:w 8 - ; #9
9130     \token_if_eq_charcode:NNTF \c_space_token #9
9131     { \__iow_wrap_line_end:nw { } }
9132     { \if_false: { \fi: } \__iow_wrap_break:w #9 }
9133 }
9134 \cs_new:Npn \__iow_wrap_line_end:nw #1
9135 {
9136     \if_false: { \fi: }
9137     \__iow_wrap_store_do:n {#1}
9138     \__iow_wrap_next_line:w
9139 }
9140 \cs_new:Npn \__iow_wrap_end_chunk:w
9141 #1 \__int_eval:w #2 - #3 ; #4#5 \q_stop
9142 {
9143     \if_false: { \fi: }
9144     \exp_args:Nf \__iow_wrap_next:nw { \int_eval:n { #2 - #4 } }
9145 }

```

(End definition for \\_\_iow\_wrap\_line:nw and others.)

<pre> \__iow_wrap_break:w \__iow_wrap_break_first:w \__iow_wrap_break_none:w \__iow_wrap_break_loop:w \__iow_wrap_break_end:w </pre>	<p>Functions here are defined indirectly: \__iow_tmp:w is eventually called with an “other” space as its argument. The goal is to remove from \l__iow_line_part_tl the part after the last space. In most cases this is done by repeatedly calling the <code>break_loop</code> auxiliary, which leaves “words” (delimited by spaces) until it hits the trailing space: then its argument <code>##3</code> is ? \__iow_wrap_break_end:w instead of a single token, and that <code>break_end</code> auxiliary leaves in the assignment the line until the last space, then calls \__iow_wrap_line_end:nw to finish up the line and move on to the next. If there is no space in \l__iow_line_part_tl then the <code>break_first</code> auxiliary calls the <code>break_none</code> auxiliary. In that case, if the current line is empty, the complete word (including <code>##4</code>, characters beyond what we had grabbed) is added to the line, making it over-long. Otherwise, the word is used for the following line (and the last space of the line so far is removed because it was inserted due to the presence of a marker).</p>
--	---

```

9146 \cs_set_protected:Npn \__iow_tmp:w #1
9147 {
9148     \cs_new:Npn \__iow_wrap_break:w
9149     {
9150         \tex_edef:D \l__iow_line_part_tl
9151         { \if_false: } \fi:
9152         \exp_after:wN \__iow_wrap_break_first:w
9153         \l__iow_line_part_tl
9154         #1
9155         { ? \__iow_wrap_break_end:w }
9156         \q_mark
9157     }
9158     \cs_new:Npn \__iow_wrap_break_first:w ##1 #1 ##2
9159     {

```

```

9160     \use_none:nn ##2 \__iow_wrap_break_none:w
9161     \__iow_wrap_break_loop:w ##1 #1 ##2
9162   }
9163   \cs_new:Npn \__iow_wrap_break_none:w ##1##2 #1 ##3 \q_mark ##4 #1
9164   {
9165     \tl_if_empty:NTF \l__iow_line_tl
9166     { ##2 ##4 \__iow_wrap_line_end:nw { } }
9167     { \__iow_wrap_line_end:nw { \__iow_wrap_trim:N } ##2 ##4 #1 }
9168   }
9169   \cs_new:Npn \__iow_wrap_break_loop:w ##1 #1 ##2 #1 ##3
9170   {
9171     \use_none:n ##3
9172     ##1 #1
9173     \__iow_wrap_break_loop:w ##2 #1 ##3
9174   }
9175   \cs_new:Npn \__iow_wrap_break_end:w ##1 #1 ##2 ##3 #1 ##4 \q_mark
9176   { ##1 \__iow_wrap_line_end:nw { } ##3 }
9177 }
9178 \exp_args:NV \__iow_tmp:w \c_catcode_other_space_tl

```

(End definition for \\_\_iow\_wrap\_break:w and others.)

\\_\_iow\_wrap\_next\_line:w The special case where the end of a line coincides with the end of a chunk is detected here, to avoid a spurious empty line. Otherwise, call \\_\_iow\_wrap\_line:nw to find characters for the next line (remembering to account for the indentation).

```

9179 \cs_new_protected:Npn \__iow_wrap_next_line:w #1#2 \q_stop
9180 {
9181   \tl_clear:N \l__iow_line_tl
9182   \token_if_eq_meaning:NNTF #1 \__iow_wrap_end_chunk:w
9183   {
9184     \tl_clear:N \l__iow_line_part_tl
9185     \bool_set_true:N \l__iow_line_break_bool
9186     \__iow_wrap_next:nw { \l__iow_line_target_int }
9187   }
9188   {
9189     \__iow_wrap_line:nw
9190     { \l__iow_indent_tl }
9191     \l__iow_line_target_int - \l__iow_indent_int ;
9192     #1 #2 \q_stop
9193   }
9194 }

```

(End definition for \\_\_iow\_wrap\_next\_line:w.)

\\_\_iow\_wrap\_indent: These functions are called after a chunk has been wrapped, when encountering indent/unindent markers. Add the line part (last line part of the previous chunk) to the line so far and reset a boolean denoting the presence of a line-break. Most importantly, add or remove one indent from the current indent (both the integer and the token list). Finally, continue wrapping.

```

9195 \cs_new_protected:Npn \__iow_wrap_indent:n #1
9196 {
9197   \tl_put_right:Nx \l__iow_line_tl { \l__iow_line_part_tl }
9198   \bool_set_false:N \l__iow_line_break_bool
9199   \int_add:Nn \l__iow_indent_int { \l__iow_one_indent_int }

```



```

9200     \tl_put_right:No \l__iow_indent_tl { \l__iow_one_indent_tl }
9201     \__iow_wrap_chunk:nw {#1}
9202   }
9203 \cs_new_protected:Npn \__iow_wrap_unindent:n #1
9204 {
9205     \tl_put_right:Nx \l__iow_line_tl { \l__iow_line_part_tl }
9206     \bool_set_false:N \l__iow_line_break_bool
9207     \int_sub:Nn \l__iow_indent_int { \l__iow_one_indent_int }
9208     \tl_set:Nx \l__iow_indent_tl
9209       { \exp_after:wN \__iow_unindent:w \l__iow_indent_tl }
9210     \__iow_wrap_chunk:nw {#1}
9211 }

```

(End definition for \\_\_iow\_wrap\_indent: and \\_\_iow\_wrap\_unindent:.)

\\_\_iow\_wrap\_newline: These functions are called after a chunk has been line-wrapped, when encountering a **newline**/end marker. Unless we just took a line-break, store the line part and the line so far into the whole \l\_\_iow\_wrap\_tl, trimming a trailing space. In the **newline** case look for a new line (of length \l\_\_iow\_line\_target\_int) in a new chunk.

```

9212 \cs_new_protected:Npn \__iow_wrap_newline:n #1
9213 {
9214     \bool_if:NF \l__iow_line_break_bool
9215       { \__iow_wrap_store_do:n { \__iow_wrap_trim:N } }
9216     \bool_set_false:N \l__iow_line_break_bool
9217     \__iow_wrap_chunk:nw { \l__iow_line_target_int }
9218 }
9219 \cs_new_protected:Npn \__iow_wrap_end:n #1
9220 {
9221     \bool_if:NF \l__iow_line_break_bool
9222       { \__iow_wrap_store_do:n { \__iow_wrap_trim:N } }
9223     \bool_set_false:N \l__iow_line_break_bool
9224 }

```

(End definition for \\_\_iow\_wrap\_newline: and \\_\_iow\_wrap\_end:.)

\\_\_iow\_wrap\_store\_do:n First add the last line part to the line, then append it to \l\_\_iow\_wrap\_tl with the appropriate new line (with “run-on” text), possibly with its last space removed (#1 is empty or \\_\_iow\_wrap\_trim:N).

```

9225 \cs_new_protected:Npn \__iow_wrap_store_do:n #1
9226 {
9227     \tl_set:Nx \l__iow_line_tl
9228       { \l__iow_line_tl \l__iow_line_part_tl }
9229     \tl_set:Nx \l__iow_wrap_tl
9230       {
9231         \l__iow_wrap_tl
9232         \l__iow_newline_tl
9233         #1 \l__iow_line_tl
9234       }
9235     \tl_clear:N \l__iow_line_tl
9236 }

```

(End definition for \\_\_iow\_wrap\_store\_do:n.)

```

\__iow_wrap_trim:N Remove one trailing “other” space from the argument.
\__iow_wrap_trim:w
9237 \cs_set_protected:Npn \__iow_tmp:w #1
9238 {
9239   \cs_new:Npn \__iow_wrap_trim:N ##1
9240     { \tl_if_empty:NF ##1 { \exp_after:wN \__iow_wrap_trim:w ##1 \q_stop } }
9241   \cs_new:Npn \__iow_wrap_trim:w ##1 #1 \q_stop {##1}
9242 }
9243 \exp_args:NV \__iow_tmp:w \c_catcode_other_space_tl

```

(End definition for \\_\_iow\_wrap\_trim:N and \\_\_iow\_wrap\_trim:w.)

## 17.5 Messages

```

9244 \__msg_kernel_new:nnnn { kernel } { file-not-found }
9245 { File~'##1'~not-found. }
9246 {
9247   The~requested~file~could~not~be~found~in~the~current~directory,~
9248   in~the~TeX~search~path~or~in~the~LaTeX~search~path.
9249 }
9250 \__msg_kernel_new:nnnn { kernel } { input-streams-exhausted }
9251 { Input~streams~exhausted }
9252 {
9253   TeX~can~only~open~up~to~16~input~streams~at~one~time.\\
9254   All~16~are~currently~in~use,~and~something~wanted~to~open~
9255   another~one.
9256 }
9257 \__msg_kernel_new:nnnn { kernel } { output-streams-exhausted }
9258 { Output~streams~exhausted }
9259 {
9260   TeX~can~only~open~up~to~16~output~streams~at~one~time.\\
9261   All~16~are~currently~in~use,~and~something~wanted~to~open~
9262   another~one.
9263 }
9264 \__msg_kernel_new:nnnn { kernel } { unbalanced-quote-in-filename }
9265 { Unbalanced~quotes~in~file~name~'##1'. }
9266 {
9267   File~names~must~contain~balanced~numbers~of~quotes~(").
9268 }
9269 \__msg_kernel_new:nnnn { kernel } { iow-indent }
9270 { Only~##1 (arg-1)~allows~##2 }
9271 {
9272   The~command~##2 can~only~be~used~in~messages~
9273   which~will~be~wrapped~using~##1.~
9274   It~was~called~with~argument~'##3'.
9275 }

```

## 17.6 Deprecated functions

```

\g_file_current_name_tl For removal after 2018-12-31.
9276 \tl_new:N \g_file_current_name_tl
9277 \tl_gset:Nn \g_file_current_name_tl { \g_file_curr_name_str }

```

(End definition for \g\_file\_current\_name\_tl.)

```

\file_path_include:n Wrapper functions to manage the search path.
\file_path_remove:n
\__file_path_include:n
9278 \cs_new_protected:Npn \file_path_include:n #1
9279 {
9280     \__msg_kernel_warning:nnxxx { kernel } { deprecated-command }
9281     { 2018-12-31 }
9282     { \token_to_str:N \file_path_include:n }
9283     {
9284         \token_to_str:N \seq_put_right:Nn \c_space_tl
9285         \token_to_str:N \l_file_search_path_seq
9286     }
9287     \__file_name_sanitiz:nN {#1} \l__file_full_name_str
9288     \seq_if_in:NVF \l_file_search_path_seq \l__file_full_name_str
9289     { \seq_put_right:NV \l_file_search_path_seq \l__file_full_name_str }
9290 }
9291 \cs_new_protected:Npn \file_path_remove:n #1
9292 {
9293     \__msg_kernel_warning:nnxxx { kernel } { deprecated-command }
9294     { 2018-12-31 }
9295     { \token_to_str:N \file_path_remove:n }
9296     {
9297         \token_to_str:N \seq_remove_all:Nn \c_space_tl
9298         \token_to_str:N \l_file_search_path_seq
9299     }
9300     \__file_name_sanitiz:nN {#1} \l__file_full_name_str
9301     \seq_remove_all:NV \l_file_search_path_seq \l__file_full_name_str
9302 }

```

(End definition for \file\_path\_include:n, \file\_path\_remove:n, and \\_\_file\_path\_include:n.)

```

\file_add_path:nN For removal after 2018-12-31.
9303 \cs_new_protected:Npn \file_add_path:nN #1#2
9304 {
9305     \__msg_kernel_warning:nnxxx { kernel } { deprecated-command }
9306     { 2018-12-31 }
9307     { \token_to_str:N \file_add_path:nN }
9308     { \token_to_str:N \file_get_full_name:nN }
9309     \file_get_full_name:nN {#1} #2
9310     \str_if_empty:NT #2
9311     { \tl_set:Nn #2 { \q_no_value } }
9312 }

```

(End definition for \file\_add\_path:nN.)

```

\ior_get_str:NN For removal after 2017-12-31.
9313 \cs_new_protected:Npn \ior_get_str:NN
9314 {
9315     \__msg_kernel_warning:nnxxx { kernel } { deprecated-command }
9316     { 2017-12-31 }
9317     { \token_to_str:N \ior_get_str:NN }
9318     { \token_to_str:N \ior_str_get:NN }
9319     \cs_gset_eq:NN \ior_get_str:NN \ior_str_get:NN
9320     \ior_str_get:NN
9321 }

```

(End definition for \ior\_get\_str:NN.)

\file\_list: Renamed to \file\_log\_list:. For removal after 2018-12-31.

```
9322 \cs_new_protected:Npn \file_list:
9323 {
9324   \__msg_kernel_warning:nnxxx { kernel } { deprecated-command }
9325   { 2018-12-31 }
9326   { \token_to_str:N \file_list: }
9327   { \token_to_str:N \file_log_list: }
9328   \cs_gset_eq:NN \file_list: \file_log_list:
9329   \file_log_list:
9330 }
```

*(End definition for \file\_list:.)*

\ior\_list\_streams: These got a more consistent naming.

```
\ior_log_streams: 9331 \cs_new_protected:Npn \ior_list_streams:
\ior_list_streams: 9332 {
\ior_log_streams: 9333   \__msg_kernel_warning:nnxxx { kernel } { deprecated-command }
9334   { 2018-12-31 }
9335   { \token_to_str:N \ior_list_streams: }
9336   { \token_to_str:N \ior_show_list: }
9337   \cs_gset_eq:NN \ior_list_streams: \ior_show_list:
9338   \ior_show_list:
9339 }
9340 \cs_new_protected:Npn \ior_log_streams:
9341 {
9342   \__msg_kernel_warning:nnxxx { kernel } { deprecated-command }
9343   { 2018-12-31 }
9344   { \token_to_str:N \ior_log_streams: }
9345   { \token_to_str:N \ior_log_list: }
9346   \cs_gset_eq:NN \ior_log_streams: \ior_log_list:
9347   \ior_log_list:
9348 }
9349 \cs_new_protected:Npn \ior_list_streams:
9350 {
9351   \__msg_kernel_warning:nnxxx { kernel } { deprecated-command }
9352   { 2018-12-31 }
9353   { \token_to_str:N \ior_list_streams: }
9354   { \token_to_str:N \ior_show_list: }
9355   \cs_gset_eq:NN \ior_list_streams: \ior_show_list:
9356   \ior_show_list:
9357 }
9358 \cs_new_protected:Npn \ior_log_streams:
9359 {
9360   \__msg_kernel_warning:nnxxx { kernel } { deprecated-command }
9361   { 2018-12-31 }
9362   { \token_to_str:N \ior_log_streams: }
9363   { \token_to_str:N \ior_log_list: }
9364   \cs_gset_eq:NN \ior_log_streams: \ior_log_list:
9365   \ior_log_list:
9366 }
```

*(End definition for \ior\_list\_streams: and others.)*

```
9367 </initex | package>
```

## 18 l3skip implementation

9368  $\langle *initex | package \rangle$

9369  $\langle @@=dim \rangle$

### 18.1 Length primitives renamed

$\backslash if\_dim:w$  Primitives renamed.  
 $\backslash\_dim\_eval:w$  9370  $\backslash cs\_new\_eq:Nn \backslash if\_dim:w \quad \backslash tex\_ifdim:D$   
 $\backslash\_dim\_eval\_end:$  9371  $\backslash cs\_new\_eq:Nn \backslash\_dim\_eval:w \quad \backslash etex\_dimexpr:D$   
9372  $\backslash cs\_new\_eq:Nn \backslash\_dim\_eval\_end: \quad \backslash tex\_relax:D$

(End definition for  $\backslash if\_dim:w$ ,  $\backslash\_dim\_eval:w$ , and  $\backslash\_dim\_eval\_end:$ . These functions are documented on page 161.)

### 18.2 Creating and initialising dim variables

$\backslash dim\_new:N$  Allocating  $\langle dim \rangle$  registers ...  
 $\backslash dim\_new:c$  9373  $\langle *package \rangle$   
9374  $\backslash cs\_new\_protected:Npn \backslash dim\_new:N \#1$   
9375 {  
9376  $\backslash\_chk\_if\_free\_cs:N \#1$   
9377  $\backslash cs:w newdimen \backslash cs\_end: \#1$   
9378 }  
9379  $\langle /package \rangle$   
9380  $\backslash cs\_generate\_variant:Nn \backslash dim\_new:N \{ c \}$

(End definition for  $\backslash dim\_new:N$ . This function is documented on page 148.)

$\backslash dim\_const:Nn$  Contrarily to integer constants, we cannot avoid using a register, even for constants.  
 $\backslash dim\_const:cn$  9381  $\backslash cs\_new\_protected:Npn \backslash dim\_const:Nn \#1$   
9382 {  
9383  $\backslash dim\_new:N \#1$   
9384  $\backslash dim\_gset:Nn \#1$   
9385 }  
9386  $\backslash cs\_generate\_variant:Nn \backslash dim\_const:Nn \{ c \}$

(End definition for  $\backslash dim\_const:Nn$ . This function is documented on page 148.)

$\backslash dim\_zero:N$  Reset the register to zero.  
 $\backslash dim\_zero:c$  9387  $\backslash cs\_new\_protected:Npn \backslash dim\_zero:N \#1 \{ \#1 \backslash c\_zero\_dim \}$   
 $\backslash dim\_gzero:N$  9388  $\backslash cs\_new\_protected:Npn \backslash dim\_gzero:N \{ \backslash tex\_global:D \backslash dim\_zero:N \}$   
 $\backslash dim\_gzero:c$  9389  $\backslash cs\_generate\_variant:Nn \backslash dim\_zero:N \{ c \}$   
9390  $\backslash cs\_generate\_variant:Nn \backslash dim\_gzero:N \{ c \}$

(End definition for  $\backslash dim\_zero:N$  and  $\backslash dim\_gzero:N$ . These functions are documented on page 148.)

$\backslash dim\_zero\_new:N$  Create a register if needed, otherwise clear it.  
 $\backslash dim\_zero\_new:c$  9391  $\backslash cs\_new\_protected:Npn \backslash dim\_zero\_new:N \#1$   
 $\backslash dim\_gzero\_new:N$  9392 {  $\backslash dim\_if\_exist:Ntf \#1 \{ \backslash dim\_zero:N \#1 \} \{ \backslash dim\_new:N \#1 \} \}$   
 $\backslash dim\_gzero\_new:c$  9393  $\backslash cs\_new\_protected:Npn \backslash dim\_gzero\_new:N \#1$   
9394 {  $\backslash dim\_if\_exist:Ntf \#1 \{ \backslash dim\_gzero:N \#1 \} \{ \backslash dim\_new:N \#1 \} \}$   
9395  $\backslash cs\_generate\_variant:Nn \backslash dim\_zero\_new:N \{ c \}$   
9396  $\backslash cs\_generate\_variant:Nn \backslash dim\_gzero\_new:N \{ c \}$

(End definition for `\dim_zero_new:N` and `\dim_gzero_new:N`. These functions are documented on page 148.)

`\dim_if_exist_p:N` Copies of the `cs` functions defined in `l3basics`.  
`\dim_if_exist_p:c` 9397 `\prg_new_eq_conditional:Nn \dim_if_exist:N \cs_if_exist:N`  
`\dim_if_exist:NTF` 9398 `{ TF , T , F , p }`  
`\dim_if_exist:cTF` 9399 `\prg_new_eq_conditional:Nn \dim_if_exist:c \cs_if_exist:c`  
9400 `{ TF , T , F , p }`

(End definition for `\dim_if_exist:NTF`. This function is documented on page 148.)

### 18.3 Setting dim variables

`\dim_set:Nn` Setting dimensions is easy enough.  
`\dim_set:cn` 9401 `\cs_new_protected:Npn \dim_set:Nn #1#2`  
`\dim_gset:Nn` 9402 `{ #1 ~ \__dim_eval:w #2 \__dim_eval_end: }`  
`\dim_gset:cn` 9403 `\cs_new_protected:Npn \dim_gset:Nn { \tex_global:D \dim_set:Nn }`  
9404 `\cs_generate_variant:Nn \dim_set:Nn { c }`  
9405 `\cs_generate_variant:Nn \dim_gset:Nn { c }`

(End definition for `\dim_set:Nn` and `\dim_gset:Nn`. These functions are documented on page 149.)

`\dim_set_eq:NN` All straightforward.  
`\dim_set_eq:cN` 9406 `\cs_new_protected:Npn \dim_set_eq:NN #1#2 { #1 = #2 }`  
`\dim_set_eq:Nc` 9407 `\cs_generate_variant:Nn \dim_set_eq:NN { c }`  
`\dim_set_eq:cc` 9408 `\cs_generate_variant:Nn \dim_set_eq:NN { Nc , cc }`  
`\dim_gset_eq:NN` 9409 `\cs_new_protected:Npn \dim_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }`  
`\dim_gset_eq:cN` 9410 `\cs_generate_variant:Nn \dim_gset_eq:NN { c }`  
`\dim_gset_eq:Nc` 9411 `\cs_generate_variant:Nn \dim_gset_eq:NN { Nc , cc }`  
`\dim_gset_eq:cc` (End definition for `\dim_set_eq:NN` and `\dim_gset_eq:NN`. These functions are documented on page 149.)

`\dim_add:Nn` Using `by` here deals with the (incorrect) case `\dimen123`.  
`\dim_add:cn` 9412 `\cs_new_protected:Npn \dim_add:Nn #1#2`  
`\dim_gadd:Nn` 9413 `{ \tex_advance:D #1 by \__dim_eval:w #2 \__dim_eval_end: }`  
`\dim_gadd:cn` 9414 `\cs_new_protected:Npn \dim_gadd:Nn { \tex_global:D \dim_add:Nn }`  
`\dim_sub:Nn` 9415 `\cs_generate_variant:Nn \dim_add:Nn { c }`  
`\dim_sub:cn` 9416 `\cs_generate_variant:Nn \dim_gadd:Nn { c }`  
`\dim_gsub:Nn` 9417 `\cs_new_protected:Npn \dim_sub:Nn #1#2`  
`\dim_gsub:cn` 9418 `{ \tex_advance:D #1 by - \__dim_eval:w #2 \__dim_eval_end: }`  
9419 `\cs_new_protected:Npn \dim_gsub:Nn { \tex_global:D \dim_sub:Nn }`  
9420 `\cs_generate_variant:Nn \dim_sub:Nn { c }`  
9421 `\cs_generate_variant:Nn \dim_gsub:Nn { c }`

(End definition for `\dim_add:Nn` and others. These functions are documented on page 149.)

## 18.4 Utilities for dimension calculations

`\dim_abs:n` Functions for min, max, and absolute value with only one evaluation. The absolute value  
`\__dim_abs:N` is evaluated by removing a leading - if present.

`\dim_max:nn`

`\dim_min:nn`

`\__dim_maxmin:wwN`

```

9422 \cs_new:Npn \dim_abs:n #1
9423 {
9424   \exp_after:wN \__dim_abs:N
9425   \dim_use:N \__dim_eval:w #1 \__dim_eval_end:
9426 }
9427 \cs_new:Npn \__dim_abs:N #1
9428 { \if_meaning:w - #1 \else: \exp_after:wN #1 \fi: }
9429 \cs_new:Npn \dim_max:nn #1#2
9430 {
9431   \dim_use:N \__dim_eval:w \exp_after:wN \__dim_maxmin:wwN
9432   \dim_use:N \__dim_eval:w #1 \exp_after:wN ;
9433   \dim_use:N \__dim_eval:w #2 ;
9434   >
9435   \__dim_eval_end:
9436 }
9437 \cs_new:Npn \dim_min:nn #1#2
9438 {
9439   \dim_use:N \__dim_eval:w \exp_after:wN \__dim_maxmin:wwN
9440   \dim_use:N \__dim_eval:w #1 \exp_after:wN ;
9441   \dim_use:N \__dim_eval:w #2 ;
9442   <
9443   \__dim_eval_end:
9444 }
9445 \cs_new:Npn \__dim_maxmin:wwN #1 ; #2 ; #3
9446 {
9447   \if_dim:w #1 #3 #2 ~
9448   #1
9449   \else:
9450   #2
9451   \fi:
9452 }
```

(End definition for `\dim_abs:n` and others. These functions are documented on page 149.)

`\dim_ratio:nn` With dimension expressions, something like `10 pt * ( 5 pt / 10 pt )` does not work.  
`\__dim_ratio:n` Instead, the ratio part needs to be converted to an integer expression. Using `\__int_value:w` forces everything into `sp`, avoiding any decimal parts.

```

9453 \cs_new:Npn \dim_ratio:nn #1#2
9454 { \__dim_ratio:n {#1} / \__dim_ratio:n {#2} }
9455 \cs_new:Npn \__dim_ratio:n #1
9456 { \__int_value:w \__dim_eval:w (#1) \__dim_eval_end: }
```

(End definition for `\dim_ratio:nn` and `\__dim_ratio:n`. These functions are documented on page 150.)

## 18.5 Dimension expression conditionals

`\dim_compare_p:nNn` Simple comparison.

`\dim_compare:nNnTF`

```

9457 \prg_new_conditional:Npnn \dim_compare:nNn #1#2#3 { p , T , F , TF }
9458 {
9459   \if_dim:w \__dim_eval:w #1 #2 \__dim_eval:w #3 \__dim_eval_end:
```

```

9460     \prg_return_true: \else: \prg_return_false: \fi:
9461 }

```

(End definition for \dim\_compare:nNnTF. This function is documented on page 150.)

**\dim\_compare\_p:n** This code is adapted from the \int\_compare:nTF function. First make sure that there is at least one relation operator, by evaluating a dimension expression with a trailing \\_\\_prg\_compare\_error:. Just like for integers, the looping auxiliary \\_\\_dim\_compare:wNn closes a primitive conditional and opens a new one. It is actually easier to grab a dimension operand than an integer one, because once evaluated, dimensions all end with pt (with category other). Thus we do not need specific auxiliaries for the three “simple” relations <, =, and >.

```

9462 \prg_new_conditional:Npnn \dim_compare:n #1 { p , T , F , TF }
9463 {
9464     \exp_after:wN \_\_dim_compare:w
9465     \dim_use:N \_\_dim_eval:w #1 \_\_prg_compare_error:
9466 }
9467 \cs_new:Npn \_\_dim_compare:w #1 \_\_prg_compare_error:
9468 {
9469     \exp_after:wN \if_false: \exp:w \exp_end_continue_f:w
9470     \_\_dim_compare:wNn #1 ? { = \_\_dim_compare_end:w \else: } \q_stop
9471 }
9472 \exp_args:Nno \use:nn
9473 { \cs_new:Npn \_\_dim_compare:wNn #1 }
9474 { \tl_to_str:n {pt} }
9475 #2#3
9476 {
9477     \if_meaning:w = #3
9478     \use:c { \_\_dim_compare_#2:w }
9479     \fi:
9480     #1 pt \exp_stop_f:
9481     \prg_return_false:
9482     \exp_after:wN \use_none_delimit_by_q_stop:w
9483     \fi:
9484     \reverse_if:N \if_dim:w #1 pt #2
9485     \exp_after:wN \_\_dim_compare:wNn
9486     \dim_use:N \_\_dim_eval:w #3
9487 }
9488 \cs_new:cpn { \_\_dim_compare_! :w }
9489 #1 \reverse_if:N #2 ! #3 = { #1 #2 = #3 }
9490 \cs_new:cpn { \_\_dim_compare_ = :w }
9491 #1 \_\_dim_eval:w = { #1 \_\_dim_eval:w }
9492 \cs_new:cpn { \_\_dim_compare_ < :w }
9493 #1 \reverse_if:N #2 < #3 = { #1 #2 > #3 }
9494 \cs_new:cpn { \_\_dim_compare_ > :w }
9495 #1 \reverse_if:N #2 > #3 = { #1 #2 < #3 }
9496 \cs_new:Npn \_\_dim_compare_end:w #1 \prg_return_false: #2 \q_stop
9497 { #1 \prg_return_false: \else: \prg_return_true: \fi: }

```

(End definition for \dim\_compare:nTF and others. These functions are documented on page 151.)

**\dim\_case:nn** For dimension cases, the first task to fully expand the check condition. The over all idea is then much the same as for \str\_case:nn(TF) as described in l3basics.

**\dim\_case:nnTF**

```

9498 \cs_new:Npn \dim_case:nnTF #1

```

**\\_\\_dim\_case:nnTF**

**\\_\\_dim\_case:nw**

**\\_\\_dim\_case\_end:nw**



```

9499 {
9500   \exp:w
9501   \exp_args:Nf \_dim_case:nnTF { \dim_eval:n {#1} }
9502 }
9503 \cs_new:Npn \dim_case:nnT #1#2#3
9504 {
9505   \exp:w
9506   \exp_args:Nf \_dim_case:nnTF { \dim_eval:n {#1} } {#2} {#3} { }
9507 }
9508 \cs_new:Npn \dim_case:nnF #1#2
9509 {
9510   \exp:w
9511   \exp_args:Nf \_dim_case:nnTF { \dim_eval:n {#1} } {#2} { }
9512 }
9513 \cs_new:Npn \dim_case:nn #1#2
9514 {
9515   \exp:w
9516   \exp_args:Nf \_dim_case:nnTF { \dim_eval:n {#1} } {#2} { } { }
9517 }
9518 \cs_new:Npn \_dim_case:nnTF #1#2#3#4
9519 { \_dim_case:nw {#1} #2 {#1} { } \q_mark {#3} \q_mark {#4} \q_stop }
9520 \cs_new:Npn \_dim_case:nw #1#2#3
9521 {
9522   \dim_compare:nNnTF {#1} = {#2}
9523   { \_dim_case_end:nw {#3} }
9524   { \_dim_case:nw {#1} }
9525 }
9526 \cs_new_eq:NN \_dim_case_end:nw \_prg_case_end:nw

```

(End definition for `\dim_case:nnTF` and others. These functions are documented on page 152.)

## 18.6 Dimension expression loops

`\dim_while_do:nn` `while_do` and `do_while` functions for dimensions. Same as for the `int` type only the names have changed.

```

\dim_until_do:nn
\dim_do_while:nn
\dim_do_until:nn
9527 \cs_new:Npn \dim_while_do:nn #1#2
9528 {
9529   \dim_compare:nT {#1}
9530   {
9531     #2
9532     \dim_while_do:nn {#1} {#2}
9533   }
9534 }
9535 \cs_new:Npn \dim_until_do:nn #1#2
9536 {
9537   \dim_compare:nF {#1}
9538   {
9539     #2
9540     \dim_until_do:nn {#1} {#2}
9541   }
9542 }
9543 \cs_new:Npn \dim_do_while:nn #1#2
9544 {
9545   #2

```

```

9546     \dim_compare:nT {#1}
9547     { \dim_do_while:nn {#1} {#2} }
9548   }
9549   \cs_new:Npn \dim_do_until:nn #1#2
9550   {
9551     #2
9552     \dim_compare:nF {#1}
9553     { \dim_do_until:nn {#1} {#2} }
9554   }

```

(End definition for `\dim_while_do:nn` and others. These functions are documented on page 153.)

`\dim_while_do:nNnn` `\dim_while_do` and `do_while` functions for dimensions. Same as for the `int` type only the names have changed.

```

\dim_until_do:nNnn
\dim_do_while:nNnn
\dim_do_until:nNnn
9555   \cs_new:Npn \dim_while_do:nNnn #1#2#3#4
9556   {
9557     \dim_compare:nNnT {#1} #2 {#3}
9558     {
9559       #4
9560       \dim_while_do:nNnn {#1} #2 {#3} {#4}
9561     }
9562   }
9563   \cs_new:Npn \dim_until_do:nNnn #1#2#3#4
9564   {
9565     \dim_compare:nNnF {#1} #2 {#3}
9566     {
9567       #4
9568       \dim_until_do:nNnn {#1} #2 {#3} {#4}
9569     }
9570   }
9571   \cs_new:Npn \dim_do_while:nNnn #1#2#3#4
9572   {
9573     #4
9574     \dim_compare:nNnT {#1} #2 {#3}
9575     { \dim_do_while:nNnn {#1} #2 {#3} {#4} }
9576   }
9577   \cs_new:Npn \dim_do_until:nNnn #1#2#3#4
9578   {
9579     #4
9580     \dim_compare:nNnF {#1} #2 {#3}
9581     { \dim_do_until:nNnn {#1} #2 {#3} {#4} }
9582   }

```

(End definition for `\dim_while_do:nNnn` and others. These functions are documented on page 153.)

## 18.7 Using dim expressions and variables

`\dim_eval:n` Evaluating a dimension expression expandably.

```

9583   \cs_new:Npn \dim_eval:n #1
9584   { \dim_use:N \__dim_eval:w #1 \__dim_eval_end: }

```

(End definition for `\dim_eval:n`. This function is documented on page 153.)

`\dim_use:N` Accessing a  $\langle dim \rangle$ .

```

\dim_use:c 9585   \cs_new_eq:NN \dim_use:N \tex_the:D

```

We hand-code this for some speed gain:

```
9586 %\cs_generate_variant:Nn \dim_use:N { c }
9587 \cs_new:Npn \dim_use:c #1 { \tex_the:D \cs:w #1 \cs_end: }
```

(End definition for `\dim_use:N`. This function is documented on page 153.)

`\dim_to_decimal:n` A function which comes up often enough to deserve a place in the kernel. Evaluate the dimension expression `#1` then remove the trailing `pt`. The argument is put in parentheses as this prevents the dimension expression from terminating early and leaving extra tokens lying around. This is used a lot by low-level manipulations.

```
\__dim_to_decimal:w
9588 \cs_new:Npn \dim_to_decimal:n #1
9589 {
9590   \exp_after:wN
9591   \__dim_to_decimal:w \dim_use:N \__dim_eval:w (#1) \__dim_eval_end:
9592 }
9593 \use:x
9594 {
9595   \cs_new:Npn \exp_not:N \__dim_to_decimal:w
9596   ##1 . ##2 \tl_to_str:n { pt }
9597 }
9598 {
9599   \int_compare:nNnTF {#2} > { 0 }
9600   { #1 . #2 }
9601   { #1 }
9602 }
```

(End definition for `\dim_to_decimal:n` and `\__dim_to_decimal:w`. These functions are documented on page 154.)

`\dim_to_decimal_in_bp:n` Conversion to big points is done using a scaling inside `\__dim_eval:w` as  $\varepsilon$ -TeX does that using 64-bit precision. Here, 800/803 is the integer fraction for 72/72.27. This is a common case so is hand-coded for accuracy (and speed).

```
9603 \cs_new:Npn \dim_to_decimal_in_bp:n #1
9604 { \dim_to_decimal:n { ( #1 ) * 800 / 803 } }
```

(End definition for `\dim_to_decimal_in_bp:n`. This function is documented on page 154.)

`\dim_to_decimal_in_sp:n` Another hard-coded conversion: this one is necessary to avoid things going off-scale.

```
9605 \cs_new:Npn \dim_to_decimal_in_sp:n #1
9606 { \int_eval:n { \__dim_eval:w #1 \__dim_eval_end: } }
```

(End definition for `\dim_to_decimal_in_sp:n`. This function is documented on page 154.)

`\dim_to_decimal_in_unit:nn` An analogue of `\dim_ratio:nn` that produces a decimal number as its result, rather than a rational fraction for use within dimension expressions.

```
9607 \cs_new:Npn \dim_to_decimal_in_unit:nn #1#2
9608 {
9609   \dim_to_decimal:n
9610   {
9611     1pt *
9612     \dim_ratio:nn {#1} {#2}
9613   }
9614 }
```

(End definition for `\dim_to_decimal_in_unit:nn`. This function is documented on page 154.)

`\dim_to_fp:n` Defined in l3fp-convert, documented here.

*(End definition for \dim\_to\_fp:n. This function is documented on page 155.)*

## 18.8 Viewing dim variables

`\dim_show:N` Diagnostics.

```
\dim_show:c 9615 \cs_new_eq:NN \dim_show:N \__kernel_register_show:N
9616 \cs_generate_variant:Nn \dim_show:N { c }
```

*(End definition for \dim\_show:N. This function is documented on page 155.)*

`\dim_show:n` Diagnostics. We don't use the TeX primitive `\showthe` to show dimension expressions: this gives a more unified output.

```
9617 \cs_new_protected:Npn \dim_show:n
9618 { \__msg_show_wrap:Nn \dim_eval:n }
```

*(End definition for \dim\_show:n. This function is documented on page 155.)*

`\dim_log:N` Diagnostics. Redirect output of `\dim_show:n` to the log.

```
\dim_log:c 9619 \cs_new_eq:NN \dim_log:N \__kernel_register_log:N
\dim_log:n 9620 \cs_new_eq:NN \dim_log:c \__kernel_register_log:c
9621 \cs_new_protected:Npn \dim_log:n
9622 { \__msg_log_next: \dim_show:n }
```

*(End definition for \dim\_log:N and \dim\_log:n. These functions are documented on page 155.)*

## 18.9 Constant dimensions

`\c_zero_dim` Constant dimensions.

```
\c_max_dim 9623 \dim_const:Nn \c_zero_dim { 0 pt }
9624 \dim_const:Nn \c_max_dim { 16383.99999 pt }
```

*(End definition for \c\_zero\_dim and \c\_max\_dim. These variables are documented on page 155.)*

## 18.10 Scratch dimensions

`\l_tmpa_dim` We provide two local and two global scratch registers, maybe we need more or less.

```
\l_tmpb_dim 9625 \dim_new:N \l_tmpa_dim
\g_tmpa_dim 9626 \dim_new:N \l_tmpb_dim
\g_tmpb_dim 9627 \dim_new:N \g_tmpa_dim
9628 \dim_new:N \g_tmpb_dim
```

*(End definition for \l\_tmpa\_dim and others. These variables are documented on page 155.)*

## 18.11 Creating and initialising skip variables

**\skip\_new:N** Allocation of a new internal registers.

```
\skip_new:c      9629 (*package)
                  9630 \cs_new_protected:Npn \skip_new:N #1
                  9631 {
                  9632     \__chk_if_free_cs:N #1
                  9633     \cs:w newskip \cs_end: #1
                  9634 }
                  9635 \</package>
                  9636 \cs_generate_variant:Nn \skip_new:N { c }
```

(End definition for \skip\_new:N. This function is documented on page 156.)

**\skip\_const:Nn** Contrarily to integer constants, we cannot avoid using a register, even for constants.

```
\skip_const:cn  9637 \cs_new_protected:Npn \skip_const:Nn #1
                  9638 {
                  9639     \skip_new:N #1
                  9640     \skip_gset:Nn #1
                  9641 }
                  9642 \cs_generate_variant:Nn \skip_const:Nn { c }
```

(End definition for \skip\_const:Nn. This function is documented on page 156.)

**\skip\_zero:N** Reset the register to zero.

```
\skip_zero:c      9643 \cs_new_protected:Npn \skip_zero:N #1 { #1 \c_zero_skip }
\skip_gzero:N      9644 \cs_new_protected:Npn \skip_gzero:N { \tex_global:D \skip_zero:N }
\skip_gzero:c      9645 \cs_generate_variant:Nn \skip_zero:N { c }
                  9646 \cs_generate_variant:Nn \skip_gzero:N { c }
```

(End definition for \skip\_zero:N and \skip\_gzero:N. These functions are documented on page 156.)

**\skip\_zero\_new:N** Create a register if needed, otherwise clear it.

```
\skip_zero_new:c  9647 \cs_new_protected:Npn \skip_zero_new:N #1
\skip_gzero_new:N  9648 { \skip_if_exist:NTF #1 { \skip_zero:N #1 } { \skip_new:N #1 } }
\skip_gzero_new:c  9649 \cs_new_protected:Npn \skip_gzero_new:N #1
                  9650 { \skip_if_exist:NTF #1 { \skip_gzero:N #1 } { \skip_new:N #1 } }
                  9651 \cs_generate_variant:Nn \skip_zero_new:N { c }
                  9652 \cs_generate_variant:Nn \skip_gzero_new:N { c }
```

(End definition for \skip\_zero\_new:N and \skip\_gzero\_new:N. These functions are documented on page 156.)

**\skip\_if\_exist\_p:N** Copies of the cs functions defined in l3basics.

```
\skip_if_exist_p:c 9653 \prg_new_eq_conditional:NNn \skip_if_exist:N \cs_if_exist:N
\skip_if_exist:NTF 9654 { TF , T , F , p }
\skip_if_exist:cTF 9655 \prg_new_eq_conditional:NNn \skip_if_exist:c \cs_if_exist:c
                  9656 { TF , T , F , p }
```

(End definition for \skip\_if\_exist:NTF. This function is documented on page 156.)

## 18.12 Setting skip variables

`\skip_set:Nn` Much the same as for dimensions.

```

\skip_set:cn      9657 \cs_new_protected:Npn \skip_set:Nn #1#2
\skip_gset:Nn     9658 { #1 ~ \etex_glueexpr:D #2 \scan_stop: }
\skip_gset:cn     9659 \cs_new_protected:Npn \skip_gset:Nn { \tex_global:D \skip_set:Nn }
                  9660 \cs_generate_variant:Nn \skip_set:Nn { c }
                  9661 \cs_generate_variant:Nn \skip_gset:Nn { c }

```

(End definition for `\skip_set:Nn` and `\skip_gset:Nn`. These functions are documented on page 156.)

`\skip_set_eq:NN` All straightforward.

```

\skip_set_eq:cn   9662 \cs_new_protected:Npn \skip_set_eq:NN #1#2 { #1 = #2 }
\skip_set_eq:Nc   9663 \cs_generate_variant:Nn \skip_set_eq:NN { c }
\skip_set_eq:cc   9664 \cs_generate_variant:Nn \skip_set_eq:NN { Nc , cc }
\skip_gset_eq:NN  9665 \cs_new_protected:Npn \skip_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
\skip_gset_eq:cn  9666 \cs_generate_variant:Nn \skip_gset_eq:NN { c }
\skip_gset_eq:Nc  9667 \cs_generate_variant:Nn \skip_gset_eq:NN { Nc , cc }
\skip_gset_eq:cc

```

(End definition for `\skip_set_eq:NN` and `\skip_gset_eq:NN`. These functions are documented on page 156.)

`\skip_add:Nn` Using `by` here deals with the (incorrect) case `\skip123`.

```

\skip_add:cn      9668 \cs_new_protected:Npn \skip_add:Nn #1#2
\skip_gadd:Nn     9669 { \tex_advance:D #1 by \etex_glueexpr:D #2 \scan_stop: }
\skip_gadd:cn     9670 \cs_new_protected:Npn \skip_gadd:Nn { \tex_global:D \skip_add:Nn }
\skip_sub:Nn      9671 \cs_generate_variant:Nn \skip_add:Nn { c }
\skip_sub:cn      9672 \cs_generate_variant:Nn \skip_gadd:Nn { c }
\skip_gsub:Nn     9673 \cs_new_protected:Npn \skip_sub:Nn #1#2
\skip_gsub:cn     9674 { \tex_advance:D #1 by - \etex_glueexpr:D #2 \scan_stop: }
                  9675 \cs_new_protected:Npn \skip_gsub:Nn { \tex_global:D \skip_sub:Nn }
                  9676 \cs_generate_variant:Nn \skip_sub:Nn { c }
                  9677 \cs_generate_variant:Nn \skip_gsub:Nn { c }

```

(End definition for `\skip_add:Nn` and others. These functions are documented on page 156.)

## 18.13 Skip expression conditionals

`\skip_if_eq_p:nn` Comparing skips means doing two expansions to make strings, and then testing them.  
`\skip_if_eq:nnTF` As a result, only equality is tested.

```

9678 \prg_new_conditional:Npnn \skip_if_eq:nn #1#2 { p , T , F , TF }
9679 {
9680   \if_int_compare:w
9681     \__str_if_eq_x:nn { \skip_eval:n { #1 } } { \skip_eval:n { #2 } }
9682     = 0 \exp_stop_f:
9683     \prg_return_true:
9684   \else:
9685     \prg_return_false:
9686   \fi:
9687 }

```

(End definition for `\skip_if_eq:nnTF`. This function is documented on page 157.)

`\skip_if_finite_p:n` With  $\varepsilon$ -TeX, we have an easy access to the order of infinities of the stretch and shrink components of a skip. However, to access both, we either need to evaluate the expression twice, or evaluate it, then call an auxiliary to extract both pieces of information from the result. Since we are going to need an auxiliary anyways, it is quicker to make it search for the string `fil` which characterizes infinite glue.

```

9688 \cs_set_protected:Npn \__cs_tmp:w #1
9689 {
9690   \prg_new_conditional:Npnn \skip_if_finite:n ##1 { p , T , F , TF }
9691   {
9692     \exp_after:wN \__skip_if_finite:wwNw
9693     \skip_use:N \etex_glueexpr:D ##1 ; \prg_return_false:
9694     #1 ; \prg_return_true: \q_stop
9695   }
9696   \cs_new:Npn \__skip_if_finite:wwNw ##1 #1 ##2 ; ##3 ##4 \q_stop {##3}
9697 }
9698 \exp_args:No \__cs_tmp:w { \tl_to_str:n { fil } }

```

(End definition for `\skip_if_finite:nTF` and `\__skip_if_finite:wwNw`. These functions are documented on page 157.)

## 18.14 Using skip expressions and variables

`\skip_eval:n` Evaluating a skip expression expandably.

```

9699 \cs_new:Npn \skip_eval:n #1
9700 { \skip_use:N \etex_glueexpr:D #1 \scan_stop: }

```

(End definition for `\skip_eval:n`. This function is documented on page 157.)

`\skip_use:N` Accessing a  $\langle skip \rangle$ .

```

\skip_use:c
9701 \cs_new_eq:NN \skip_use:N \tex_the:D
9702 %\cs_generate_variant:Nn \skip_use:N { c }
9703 \cs_new:Npn \skip_use:c #1 { \tex_the:D \cs:w #1 \cs_end: }

```

(End definition for `\skip_use:N`. This function is documented on page 157.)

## 18.15 Inserting skips into the output

`\skip_horizontal:N` Inserting skips.

```

\skip_horizontal:c
\skip_horizontal:n
\skip_vertical:N
\skip_vertical:c
\skip_vertical:n
9704 \cs_new_eq:NN \skip_horizontal:N \tex_hskip:D
9705 \cs_new:Npn \skip_horizontal:n #1
9706 { \skip_horizontal:N \etex_glueexpr:D #1 \scan_stop: }
9707 \cs_new_eq:NN \skip_vertical:N \tex_vskip:D
9708 \cs_new:Npn \skip_vertical:n #1
9709 { \skip_vertical:N \etex_glueexpr:D #1 \scan_stop: }
9710 \cs_generate_variant:Nn \skip_horizontal:N { c }
9711 \cs_generate_variant:Nn \skip_vertical:N { c }

```

(End definition for `\skip_horizontal:N` and others. These functions are documented on page 158.)

## 18.16 Viewing skip variables

**\skip\_show:N** Diagnostics.

**\skip\_show:c** 9712 \cs\_new\_eq:NN \skip\_show:N \\_\_kernel\_register\_show:N  
9713 \cs\_generate\_variant:Nn \skip\_show:N { c }

(End definition for \skip\_show:N. This function is documented on page 157.)

**\skip\_show:n** Diagnostics. We don't use the TeX primitive \showthe to show skip expressions: this gives a more unified output.

9714 \cs\_new\_protected:Npn \skip\_show:n  
9715 { \\_\_msg\_show\_wrap:Nn \skip\_eval:n }

(End definition for \skip\_show:n. This function is documented on page 158.)

**\skip\_log:N** Diagnostics. Redirect output of \skip\_show:n to the log.

**\skip\_log:c** 9716 \cs\_new\_eq:NN \skip\_log:N \\_\_kernel\_register\_log:N  
**\skip\_log:n** 9717 \cs\_new\_eq:NN \skip\_log:c \\_\_kernel\_register\_log:c  
9718 \cs\_new\_protected:Npn \skip\_log:n  
9719 { \\_\_msg\_log\_next: \skip\_show:n }

(End definition for \skip\_log:N and \skip\_log:n. These functions are documented on page 158.)

## 18.17 Constant skips

**\c\_zero\_skip** Skips with no rubber component are just dimensions but need to terminate correctly.

**\c\_max\_skip** 9720 \skip\_const:Nn \c\_zero\_skip { \c\_zero\_dim }  
9721 \skip\_const:Nn \c\_max\_skip { \c\_max\_dim }

(End definition for \c\_zero\_skip and \c\_max\_skip. These functions are documented on page 158.)

## 18.18 Scratch skips

**\l\_tmpa\_skip** We provide two local and two global scratch registers, maybe we need more or less.

**\l\_tmppb\_skip** 9722 \skip\_new:N \l\_tmpa\_skip  
**\g\_tmpa\_skip** 9723 \skip\_new:N \l\_tmppb\_skip  
**\g\_tmppb\_skip** 9724 \skip\_new:N \g\_tmpa\_skip  
9725 \skip\_new:N \g\_tmppb\_skip

(End definition for \l\_tmpa\_skip and others. These variables are documented on page 158.)

## 18.19 Creating and initialising muskip variables

**\muskip\_new:N** And then we add muskips.

**\muskip\_new:c** 9726 \\*package  
9727 \cs\_new\_protected:Npn \muskip\_new:N #1  
9728 {  
9729 \\_\_chk\_if\_free\_cs:N #1  
9730 \cs:w newmuskip \cs\_end: #1  
9731 }  
9732 \\*package  
9733 \cs\_generate\_variant:Nn \muskip\_new:N { c }

(End definition for \muskip\_new:N. This function is documented on page 159.)



**\muskip\_const:Nn** Contrarily to integer constants, we cannot avoid using a register, even for constants.

```
\muskip_const:cn
9734 \cs_new_protected:Npn \muskip_const:Nn #1
9735 {
9736   \muskip_new:N #1
9737   \muskip_gset:Nn #1
9738 }
9739 \cs_generate_variant:Nn \muskip_const:Nn { c }
```

(End definition for \muskip\_const:Nn. This function is documented on page 159.)

**\muskip\_zero:N** Reset the register to zero.

```
\muskip_zero:c
9740 \cs_new_protected:Npn \muskip_zero:N #1
\muskip_gzero:N
9741 { #1 \c_zero_muskip }
\muskip_gzero:c
9742 \cs_new_protected:Npn \muskip_gzero:N { \tex_global:D \muskip_zero:N }
9743 \cs_generate_variant:Nn \muskip_zero:N { c }
9744 \cs_generate_variant:Nn \muskip_gzero:N { c }
```

(End definition for \muskip\_zero:N and \muskip\_gzero:N. These functions are documented on page 159.)

**\muskip\_zero\_new:N** Create a register if needed, otherwise clear it.

```
\muskip_zero_new:c
9745 \cs_new_protected:Npn \muskip_zero_new:N #1
\muskip_gzero_new:N
9746 { \muskip_if_exist:NTF #1 { \muskip_zero:N #1 } { \muskip_new:N #1 } }
\muskip_gzero_new:c
9747 \cs_new_protected:Npn \muskip_gzero_new:N #1
9748 { \muskip_if_exist:NTF #1 { \muskip_gzero:N #1 } { \muskip_new:N #1 } }
9749 \cs_generate_variant:Nn \muskip_zero_new:N { c }
9750 \cs_generate_variant:Nn \muskip_gzero_new:N { c }
```

(End definition for \muskip\_zero\_new:N and \muskip\_gzero\_new:N. These functions are documented on page 159.)

**\muskip\_if\_exist\_p:N** Copies of the cs functions defined in l3basics.

```
\muskip_if_exist_p:c
9751 \prg_new_eq_conditional:NNn \muskip_if_exist:N \cs_if_exist:N
\muskip_if_exist:N $\underline{TF}$ 
9752 { TF , T , F , p }
\muskip_if_exist:c $\underline{TF}$ 
9753 \prg_new_eq_conditional:NNn \muskip_if_exist:c \cs_if_exist:c
9754 { TF , T , F , p }
```

(End definition for \muskip\_if\_exist:N $\underline{TF}$ . This function is documented on page 159.)

## 18.20 Setting muskip variables

**\muskip\_set:Nn** This should be pretty familiar.

```
\muskip_set:cn
9755 \cs_new_protected:Npn \muskip_set:Nn #1#2
\muskip_gset:Nn
9756 { #1 ~ \etex_muexpr:D #2 \scan_stop: }
\muskip_gset:cn
9757 \cs_new_protected:Npn \muskip_gset:Nn { \tex_global:D \muskip_set:Nn }
9758 \cs_generate_variant:Nn \muskip_set:Nn { c }
9759 \cs_generate_variant:Nn \muskip_gset:Nn { c }
```

(End definition for \muskip\_set:Nn and \muskip\_gset:Nn. These functions are documented on page 160.)

`\muskip_set_eq:NN` All straightforward.

```

\muskip_set_eq:cn 9760 \cs_new_protected:Npn \muskip_set_eq:NN #1#2 { #1 = #2 }
\muskip_set_eq:Nc 9761 \cs_generate_variant:Nn \muskip_set_eq:NN { c }
\muskip_set_eq:cc 9762 \cs_generate_variant:Nn \muskip_set_eq:NN { Nc , cc }
\muskip_gset_eq:NN 9763 \cs_new_protected:Npn \muskip_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
\muskip_gset_eq:cn 9764 \cs_generate_variant:Nn \muskip_gset_eq:NN { c }
\muskip_gset_eq:Nc 9765 \cs_generate_variant:Nn \muskip_gset_eq:NN { Nc , cc }
\muskip_gset_eq:cc

```

*(End definition for \muskip\_set\_eq:NN and \muskip\_gset\_eq:NN. These functions are documented on page 160.)*

`\muskip_add:Nn` Using by here deals with the (incorrect) case `\muskip123`.

```

\muskip_add:cn 9766 \cs_new_protected:Npn \muskip_add:Nn #1#2
\muskip_gadd:Nn 9767 { \tex_advance:D #1 by \etex_muexpr:D #2 \scan_stop: }
\muskip_gadd:cn 9768 \cs_new_protected:Npn \muskip_gadd:Nn { \tex_global:D \muskip_add:Nn }
\muskip_sub:Nn 9769 \cs_generate_variant:Nn \muskip_add:Nn { c }
\muskip_sub:cn 9770 \cs_generate_variant:Nn \muskip_gadd:Nn { c }
\muskip_gsub:Nn 9771 \cs_new_protected:Npn \muskip_sub:Nn #1#2
\muskip_gsub:cn 9772 { \tex_advance:D #1 by - \etex_muexpr:D #2 \scan_stop: }
9773 \cs_new_protected:Npn \muskip_gsub:Nn { \tex_global:D \muskip_sub:Nn }
9774 \cs_generate_variant:Nn \muskip_sub:Nn { c }
9775 \cs_generate_variant:Nn \muskip_gsub:Nn { c }

```

*(End definition for \muskip\_add:Nn and others. These functions are documented on page 159.)*

## 18.21 Using muskip expressions and variables

`\muskip_eval:n` Evaluating a muskip expression expandably.

```

9776 \cs_new:Npn \muskip_eval:n #1
9777 { \muskip_use:N \etex_muexpr:D #1 \scan_stop: }

```

*(End definition for \muskip\_eval:n. This function is documented on page 160.)*

`\muskip_use:N` Accessing a  $\langle muskip \rangle$ .

```

\muskip_use:c 9778 \cs_new_eq:NN \muskip_use:N \tex_the:D
9779 \cs_generate_variant:Nn \muskip_use:N { c }

```

*(End definition for \muskip\_use:N. This function is documented on page 160.)*

## 18.22 Viewing muskip variables

`\muskip_show:N` Diagnostics.

```

\muskip_show:c 9780 \cs_new_eq:NN \muskip_show:N \__kernel_register_show:N
9781 \cs_generate_variant:Nn \muskip_show:N { c }

```

*(End definition for \muskip\_show:N. This function is documented on page 160.)*

`\muskip_show:n` Diagnostics. We don't use the TeX primitive `\showthe` to show muskip expressions: this gives a more unified output.

```

9782 \cs_new_protected:Npn \muskip_show:n
9783 { \__msg_show_wrap:Nn \muskip_eval:n }

```

*(End definition for \muskip\_show:n. This function is documented on page 160.)*

**\muskip\_log:N** Diagnostics. Redirect output of \muskip\_show:n to the log.  
**\muskip\_log:c** 9784 \cs\_new\_eq:NN \muskip\_log:N \\_\_kernel\_register\_log:N  
**\muskip\_log:n** 9785 \cs\_new\_eq:NN \muskip\_log:c \\_\_kernel\_register\_log:c  
9786 \cs\_new\_protected:Npn \muskip\_log:n  
9787 { \\_\_msg\_log\_next: \muskip\_show:n }

(End definition for \muskip\_log:N and \muskip\_log:n. These functions are documented on page 161.)

## 18.23 Constant muskips

**\c\_zero\_muskip** Constant muskips given by their value.  
**\c\_max\_muskip** 9788 \muskip\_const:Nn \c\_zero\_muskip { 0 mu }  
9789 \muskip\_const:Nn \c\_max\_muskip { 16383.99999 mu }

(End definition for \c\_zero\_muskip and \c\_max\_muskip. These functions are documented on page 161.)

## 18.24 Scratch muskips

**\l\_tmpa\_muskip** We provide two local and two global scratch registers, maybe we need more or less.  
**\l\_tmpb\_muskip** 9790 \muskip\_new:N \l\_tmpa\_muskip  
**\g\_tmpa\_muskip** 9791 \muskip\_new:N \l\_tmpb\_muskip  
**\g\_tmpb\_muskip** 9792 \muskip\_new:N \g\_tmpa\_muskip  
9793 \muskip\_new:N \g\_tmpb\_muskip

(End definition for \l\_tmpa\_muskip and others. These variables are documented on page 161.)

9794 </initex | package>

# 19 l3keys Implementation

9795 <\*initex | package>

## 19.1 Low-level interface

The low-level key parser is based heavily on keyval, but with a number of additional “safety” requirements and with the idea that the parsed list of key–value pairs can be processed in a variety of ways. The net result is that this code needs around twice the amount of time as keyval to parse the same list of keys. To optimise speed as far as reasonably practical, a number of lower-level approaches are taken rather than using the higher-level expl3 interfaces.

9796 <@@=keyval>

**\l\_keyval\_key\_tl** The current key name and value.  
**\l\_keyval\_value\_tl** 9797 \tl\_new:N \l\_keyval\_key\_tl  
9798 \tl\_new:N \l\_keyval\_value\_tl

(End definition for \l\_keyval\_key\_tl and \l\_keyval\_value\_tl.)

**\l\_keyval\_sanitise\_tl** A token list variable for dealing with awkward category codes in the input.  
9799 \tl\_new:N \l\_keyval\_sanitise\_tl

(End definition for \l\_keyval\_sanitise\_tl.)

`\keyval_parse:NNn` The main function starts off by normalising category codes in package mode. That’s relatively “expensive” so is skipped (hopefully) in format mode. We then hand off to the parser. The use of `\q_mark` here prevents loss of braces from the key argument. This particular quark is chosen as it fits in with `\__tl_trim_spaces:nn` and allows a performance enhancement as the token can be carried through. Notice that by passing the two processor commands along the input stack we avoid the need to track these at all.

```

9800 \cs_new_protected:Npn \keyval_parse:NNn #1#2#3
9801 {
9802   \*initex
9803   \__keyval_loop:NNw #1#2 \q_mark #3 , \q_recursion_tail ,
9804   \</initex>
9805   \*package>
9806   \tl_set:Nn \l__keyval_sanitise_tl {#3}
9807   \__keyval_sanitise_equals:
9808   \__keyval_sanitise_comma:
9809   \exp_after:wN \__keyval_loop:NNw \exp_after:wN #1 \exp_after:wN #2
9810   \exp_after:wN \q_mark \l__keyval_sanitise_tl , \q_recursion_tail ,
9811   \</package>
9812 }

```

(End definition for `\keyval_parse:NNn`. This function is documented on page 175.)

`\__keyval_sanitise_equals:` A reasonably fast search and replace set up specifically for the active tokens. The nature of the input is known so everything is hard-coded. With only two tokens to cover, the speed gain from using dedicated functions is worth it.

```

\__keyval_sanitise_equals:
\__keyval_sanitise_comma:
  \__keyval_sanitise_equals_auxi:w
  \__keyval_sanitise_equals_auxii:w
  \__keyval_sanitise_comma_auxi:w
  \__keyval_sanitise_comma_auxii:w
\__keyval_sanitise_aux:w
9813 \*package>
9814 \group_begin:
9815   \char_set_catcode_active:n { \ = }
9816   \char_set_catcode_active:n { \ , }
9817   \cs_new_protected:Npn \__keyval_sanitise_equals:
9818   {
9819     \exp_after:wN \__keyval_sanitise_equals_auxi:w \l__keyval_sanitise_tl
9820     \q_mark = \q_nil =
9821     \exp_after:wN \__keyval_sanitise_aux:w \l__keyval_sanitise_tl
9822   }
9823   \cs_new_protected:Npn \__keyval_sanitise_equals_auxi:w #1 =
9824   {
9825     \tl_set:Nn \l__keyval_sanitise_tl {#1}
9826     \__keyval_sanitise_equals_auxii:w
9827   }
9828   \cs_new_protected:Npn \__keyval_sanitise_equals_auxii:w #1 =
9829   {
9830     \if_meaning:w \q_nil #1 \scan_stop:
9831     \else:
9832       \tl_set:Nx \l__keyval_sanitise_tl
9833       {
9834         \exp_not:o \l__keyval_sanitise_tl
9835         \token_to_str:N =
9836         \exp_not:n {#1}
9837       }
9838       \exp_after:wN \__keyval_sanitise_equals_auxii:w
9839     \fi:

```

```

9840     }
9841     \cs_new_protected:Npn \__keyval_sanitise_comma:
9842     {
9843         \exp_after:wN \__keyval_sanitise_comma_auxi:w \l__keyval_sanitise_tl
9844         \q_mark , \q_nil ,
9845         \exp_after:wN \__keyval_sanitise_aux:w \l__keyval_sanitise_tl
9846     }
9847     \cs_new_protected:Npn \__keyval_sanitise_comma_auxi:w #1 ,
9848     {
9849         \tl_set:Nn \l__keyval_sanitise_tl {#1}
9850         \__keyval_sanitise_comma_auxii:w
9851     }
9852     \cs_new_protected:Npn \__keyval_sanitise_comma_auxii:w #1 ,
9853     {
9854         \if_meaning:w \q_nil #1 \scan_stop:
9855         \else:
9856             \tl_set:Nx \l__keyval_sanitise_tl
9857             {
9858                 \exp_not:o \l__keyval_sanitise_tl
9859                 \token_to_str:N ,
9860                 \exp_not:n {#1}
9861             }
9862             \exp_after:wN \__keyval_sanitise_comma_auxii:w
9863         \fi:
9864     }
9865     \group_end:
9866     \cs_new_protected:Npn \__keyval_sanitise_aux:w #1 \q_mark
9867     { \tl_set:Nn \l__keyval_sanitise_tl {#1} }
9868     \</package>

```

(End definition for \\_\_keyval\_sanitise\_equals: and others.)

\\_\_keyval\_loop:NNw A fast test for the end of the loop, remembering to remove the leading quark first. Assuming that is not the case, look for a key and value then loop around, re-inserting a leading quark in front of the next position.

```

9869     \cs_new_protected:Npn \__keyval_loop:NNw #1#2#3 ,
9870     {
9871         \exp_after:wN \if_meaning:w \exp_after:wN \q_recursion_tail
9872         \use_none:n #3 \prg_do_nothing:
9873     \else:
9874         \__keyval_split:NNw #1#2#3 == \q_stop
9875         \exp_after:wN \__keyval_loop:NNw \exp_after:wN #1 \exp_after:wN #2
9876         \exp_after:wN \q_mark
9877     \fi:
9878     }

```

(End definition for \\_\_keyval\_loop:NNw.)

\\_\_keyval\_split:NNw The value is picked up separately from the key so there can be another quark inserted at the front, keeping braces and allowing both parts to share the same code paths. The  
\\_\_keyval\_split\_value:NNw at the front, keeping braces and allowing both parts to share the same code paths. The  
\\_\_keyval\_split\_tidy:w key is found first then there's a check that there is something there: this is biased to the  
\\_\_keyval\_action: common case of there actually being a key. For the value, we first need to see if there is anything to do: if there is, extract it. The appropriate action is then inserted in front

of the key and value. Doing this using an assignment is marginally faster than an expansion chain.

```

9879 \cs_new_protected:Npn \__keyval_split:NNw #1#2#3 =
9880 {
9881   \__keyval_def:Nn \l__keyval_key_tl {#3}
9882   \if_meaning:w \l__keyval_key_tl \c_empty_tl
9883     \exp_after:wN \__keyval_split_tidy:w
9884   \else:
9885     \exp_after:wN \__keyval_split_value:NNw \exp_after:wN #1 \exp_after:wN #2
9886     \exp_after:wN \q_mark
9887   \fi:
9888 }
9889 \cs_new_protected:Npn \__keyval_split_value:NNw #1#2#3 = #4 \q_stop
9890 {
9891   \if:w \scan_stop: \tl_to_str:n {#4} \scan_stop:
9892     \cs_set:Npx \__keyval_action:
9893       { \exp_not:N #1 { \exp_not:o \l__keyval_key_tl } }
9894   \else:
9895     \if:w \scan_stop: \etex_detokenize:D \exp_after:wN { \use_none:n #4 }
9896     \scan_stop:
9897     \__keyval_def:Nn \l__keyval_value_tl {#3}
9898     \cs_set:Npx \__keyval_action:
9899       {
9900         \exp_not:N #2
9901         { \exp_not:o \l__keyval_key_tl }
9902         { \exp_not:o \l__keyval_value_tl }
9903       }
9904     \else:
9905       \cs_set:Npn \__keyval_action:
9906         { \__msg_kernel_error:nn { kernel } { misplaced-equals-sign } }
9907     \fi:
9908   \fi:
9909   \__keyval_action:
9910 }
9911 \cs_new_protected:Npn \__keyval_split_tidy:w #1 \q_stop
9912 {
9913   \if:w \scan_stop: \etex_detokenize:D \exp_after:wN { \use_none:n #1 }
9914   \scan_stop:
9915   \else:
9916     \exp_after:wN \__keyval_empty_key:
9917   \fi:
9918 }
9919 \cs_new:Npn \__keyval_action: { }
9920 \cs_new_protected:Npn \__keyval_empty_key:
9921   { \__msg_kernel_error:nn { kernel } { misplaced-equals-sign } }

```

(End definition for \\_\_keyval\_split:NNw and others.)

\\_\_keyval\_def:Nn First trim spaces off, then potentially remove a set of braces. By using the internal interface \\_\_tl\_trim\_spaces:nn we can take advantage of the fact it needs a leading \q\_mark in this process. The \exp\_after:wN removes the quark, the delimited argument deals with any braces.

```

9922 \cs_new_protected:Npn \__keyval_def:Nn #1#2
9923   { \tl_set:Nx #1 { \__tl_trim_spaces:nn {#2} \__keyval_def_aux:n } }

```

```

9924 \cs_new:Npn \__keyval_def_aux:n #1
9925 { \exp_after:wN \__keyval_def_aux:w #1 \q_stop }
9926 \cs_new:Npn \__keyval_def_aux:w #1 \q_stop { \exp_not:n {#1} }

(End definition for \__keyval_def:Nn, \__keyval_def_aux:n, and \__keyval_def_aux:w.)
One message for the low level parsing system.

9927 \__msg_kernel_new:nnnn { kernel } { misplaced-equals-sign }
9928 { Misplaced-equals-sign-in-key-value-input~\msg_line_number: }
9929 {
9930 LaTeX-is-attempting-to-parse-some-key-value-input-but-found~
9931 two-equals-signs-not-separated-by-a-comma.
9932 }

```

## 19.2 Constants and variables

```

9933 <@@=keys>

```

Various storage areas for the different data which make up keys.

```

\c__keys_code_root_tl
\c__keys_default_root_tl
\c__keys_groups_root_tl
\c__keys_inherit_root_tl
\c__keys_type_root_tl
\c__keys_validate_root_tl
9934 \tl_const:Nn \c__keys_code_root_tl { key~code~>~ }
9935 \tl_const:Nn \c__keys_default_root_tl { key~default~>~ }
9936 \tl_const:Nn \c__keys_groups_root_tl { key~groups~>~ }
9937 \tl_const:Nn \c__keys_inherit_root_tl { key~inherit~>~ }
9938 \tl_const:Nn \c__keys_type_root_tl { key~type~>~ }
9939 \tl_const:Nn \c__keys_validate_root_tl { key~validate~>~ }

```

(End definition for \c\_\_keys\_code\_root\_tl and others.)

\c\_\_keys\_props\_root\_tl The prefix for storing properties.

```

9940 \tl_const:Nn \c__keys_props_root_tl { key~prop~>~ }

```

(End definition for \c\_\_keys\_props\_root\_tl.)

**\l\_keys\_choice\_int** Publicly accessible data on which choice is being used when several are generated as a set.

**\l\_keys\_choice\_tl**

```

9941 \int_new:N \l_keys_choice_int
9942 \tl_new:N \l_keys_choice_tl

```

(End definition for \l\_keys\_choice\_int and \l\_keys\_choice\_tl. These variables are documented on page 169.)

**\l\_\_keys\_groups\_clist** Used for storing and recovering the list of groups which apply to a key: set as a comma list but at one point we have to use this for a token list recovery.

```

9943 \clist_new:N \l__keys_groups_clist

```

(End definition for \l\_\_keys\_groups\_clist.)

**\l\_keys\_key\_tl** The name of a key itself: needed when setting keys.

```

9944 \tl_new:N \l_keys_key_tl

```

(End definition for \l\_keys\_key\_tl. This variable is documented on page 171.)

**\l\_\_keys\_module\_tl** The module for an entire set of keys.

```

9945 \tl_new:N \l__keys_module_tl

```

(End definition for \l\_\_keys\_module\_tl.)

`\l__keys_no_value_bool` A marker is needed internally to show if only a key or a key plus a value was seen: this is recorded here.

```

9946 \bool_new:N \l__keys_no_value_bool

(End definition for \l__keys_no_value_bool.)

```

`\l__keys_only_known_bool` Used to track if only “known” keys are being set.

```

9947 \bool_new:N \l__keys_only_known_bool

(End definition for \l__keys_only_known_bool.)

```

`\l_keys_path_tl` The “path” of the current key is stored here: this is available to the programmer and so is public.

```

9948 \tl_new:N \l_keys_path_tl

(End definition for \l_keys_path_tl. This variable is documented on page 171.)

```

`\l__keys_property_tl` The “property” begin set for a key at definition time is stored here.

```

9949 \tl_new:N \l__keys_property_tl

(End definition for \l__keys_property_tl.)

```

`\l__keys_selective_bool` Two flags for using key groups: one to indicate that “selective” setting is active, a second to specify which type (“opt-in” or “opt-out”).

```

9950 \bool_new:N \l__keys_selective_bool
9951 \bool_new:N \l__keys_filtered_bool

(End definition for \l__keys_selective_bool and \l__keys_filtered_bool.)

```

`\l__keys_selective_seq` The list of key groups being filtered in or out during selective setting.

```

9952 \seq_new:N \l__keys_selective_seq

(End definition for \l__keys_selective_seq.)

```

`\l__keys_unused_clist` Used when setting only some keys to store those left over.

```

9953 \tl_new:N \l__keys_unused_clist

(End definition for \l__keys_unused_clist.)

```

`\l_keys_value_tl` The value given for a key: may be empty if no value was given.

```

9954 \tl_new:N \l_keys_value_tl

(End definition for \l_keys_value_tl. This variable is documented on page 171.)

```

`\l__keys_tmp_bool` Scratch space.

```

9955 \bool_new:N \l__keys_tmp_bool

(End definition for \l__keys_tmp_bool.)

```



## 19.3 The key defining mechanism

`\keys_define:nn` The public function for definitions is just a wrapper for the lower level mechanism, more or less. The outer function is designed to keep a track of the current module, to allow safe nesting. The module is set removing any leading / (which is not needed here).

```
\__keys_define:nnn
\__keys_define:onn

9956 \cs_new_protected:Npn \keys_define:nn
9957 { \__keys_define:onn \l__keys_module_tl }
9958 \cs_new_protected:Npn \__keys_define:nnn #1#2#3
9959 {
9960   \tl_set:Nx \l__keys_module_tl { \__keys_remove_spaces:n {#2} }
9961   \keyval_parse:NNn \__keys_define:n \__keys_define:nn {#3}
9962   \tl_set:Nn \l__keys_module_tl {#1}
9963 }
9964 \cs_generate_variant:Nn \__keys_define:nnn { o }
```

(End definition for `\keys_define:nn` and `\__keys_define:nnn`. These functions are documented on page 164.)

`\__keys_define:n` The outer functions here record whether a value was given and then converge on a common internal mechanism. There is first a search for a property in the current key name, then a check to make sure it is known before the code hands off to the next step.

```
\__keys_define:nn
\__keys_define:nn
\__keys_define_aux:nn

9965 \cs_new_protected:Npn \__keys_define:n #1
9966 {
9967   \bool_set_true:N \l__keys_no_value_bool
9968   \__keys_define_aux:nn {#1} { }
9969 }
9970 \cs_new_protected:Npn \__keys_define:nn #1#2
9971 {
9972   \bool_set_false:N \l__keys_no_value_bool
9973   \__keys_define_aux:nn {#1} {#2}
9974 }
9975 \cs_new_protected:Npn \__keys_define_aux:nn #1#2
9976 {
9977   \__keys_property_find:n {#1}
9978   \cs_if_exist:cTF { \c__keys_props_root_tl \l__keys_property_tl }
9979   { \__keys_define_code:n {#2} }
9980   {
9981     \tl_if_empty:NF \l__keys_property_tl
9982     {
9983       \__msg_kernel_error:nnxx { kernel } { property-unknown }
9984       { \l__keys_property_tl } { \l_keys_path_tl }
9985     }
9986   }
9987 }
```

(End definition for `\__keys_define:n`, `\__keys_define:nn`, and `\__keys_define_aux:nn`.)

`\__keys_property_find:n` Searching for a property means finding the last . in the input, and storing the text before and after it. Everything is turned into strings, so there is no problem using an x-type expansion.

```
\__keys_property_find:w

9988 \cs_new_protected:Npn \__keys_property_find:n #1
9989 {
9990   \tl_set:Nx \l__keys_property_tl { \__keys_remove_spaces:n {#1} }
9991   \exp_after:wN \__keys_property_find:w \l__keys_property_tl . . \q_stop {#1}
```

```

9992     }
9993 \cs_new_protected:Npn \__keys_property_find:w #1 . #2 . #3 \q_stop #4
9994 {
9995     \tl_if_blank:nTF {#3}
9996     {
9997         \tl_clear:N \l__keys_property_tl
9998         \__msg_kernel_error:nnn { kernel } { key-no-property } {#4}
9999     }
10000     {
10001         \str_if_eq:nnTF {#3} { . }
10002         {
10003             \tl_set:Nx \l_keys_path_tl
10004             {
10005                 \tl_if_empty:NF \l__keys_module_tl
10006                 { \l__keys_module_tl / }
10007                 #1
10008             }
10009             \tl_set:Nn \l__keys_property_tl { . #2 }
10010         }
10011         {
10012             \tl_set:Nx \l_keys_path_tl { \l__keys_module_tl / #1 . #2 }
10013             \__keys_property_search:w #3 \q_stop
10014         }
10015     }
10016 }
10017 \cs_new_protected:Npn \__keys_property_search:w #1 . #2 \q_stop
10018 {
10019     \str_if_eq:nnTF {#2} { . }
10020     {
10021         \tl_set:Nx \l_keys_path_tl { \l_keys_path_tl }
10022         \tl_set:Nn \l__keys_property_tl { . #1 }
10023     }
10024     {
10025         \tl_set:Nx \l_keys_path_tl { \l_keys_path_tl . #1 }
10026         \__keys_property_search:w #2 \q_stop
10027     }
10028 }

```

(End definition for \\_\_keys\_property\_find:n and \\_\_keys\_property\_find:w.)

\\_\_keys\_define\_code:n Two possible cases. If there is a value for the key, then just use the function. If not, then  
 \\_\_keys\_define\_code:w a check to make sure there is no need for a value with the property. If there should be  
 one then complain, otherwise execute it. There is no need to check for a : as if it was  
 missing the earlier tests would have failed.

```

10029 \cs_new_protected:Npn \__keys_define_code:n #1
10030 {
10031     \bool_if:NTF \l__keys_no_value_bool
10032     {
10033         \exp_after:wN \__keys_define_code:w
10034         \l__keys_property_tl \q_stop
10035         { \use:c { \c__keys_props_root_tl \l__keys_property_tl } }
10036         {
10037             \__msg_kernel_error:nxxx { kernel }
10038             { property-requires-value } { \l__keys_property_tl }

```

```

10039         { \l_keys_path_tl }
10040     }
10041 }
10042 { \use:c { \c__keys_props_root_tl \l__keys_property_tl } {#1} }
10043 }
10044 \use:x
10045 {
10046     \cs_new:Npn \exp_not:N \__keys_define_code:w
10047         ##1 \c_colon_str ##2 \exp_not:N \q_stop
10048 }
10049 { \tl_if_empty:nTF {#2} }

```

(End definition for `\__keys_define_code:n` and `\__keys_define_code:w`.)

## 19.4 Turning properties into actions

`\__keys_bool_set:Nn` Boolean keys are really just choices, but all done by hand. The second argument here is the scope: either empty or `g` for global.

```

10050 \cs_new_protected:Npn \__keys_bool_set:Nn #1#2
10051 {
10052     \bool_if_exist:NF #1 { \bool_new:N #1 }
10053     \__keys_choice_make:
10054     \__keys_cmd_set:nx { \l_keys_path_tl / true }
10055     { \exp_not:c { bool_ #2 set_true:N } \exp_not:N #1 }
10056     \__keys_cmd_set:nx { \l_keys_path_tl / false }
10057     { \exp_not:c { bool_ #2 set_false:N } \exp_not:N #1 }
10058     \__keys_cmd_set:nn { \l_keys_path_tl / unknown }
10059     {
10060         \_msg_kernel_error:nxx { kernel } { boolean-values-only }
10061         { \l_keys_key_tl }
10062     }
10063     \__keys_default_set:n { true }
10064 }
10065 \cs_generate_variant:Nn \__keys_bool_set:Nn { c }

```

(End definition for `\__keys_bool_set:Nn`.)

`\__keys_bool_set_inverse:Nn` Inverse boolean setting is much the same.

```

10066 \cs_new_protected:Npn \__keys_bool_set_inverse:Nn #1#2
10067 {
10068     \bool_if_exist:NF #1 { \bool_new:N #1 }
10069     \__keys_choice_make:
10070     \__keys_cmd_set:nx { \l_keys_path_tl / true }
10071     { \exp_not:c { bool_ #2 set_false:N } \exp_not:N #1 }
10072     \__keys_cmd_set:nx { \l_keys_path_tl / false }
10073     { \exp_not:c { bool_ #2 set_true:N } \exp_not:N #1 }
10074     \__keys_cmd_set:nn { \l_keys_path_tl / unknown }
10075     {
10076         \_msg_kernel_error:nxx { kernel } { boolean-values-only }
10077         { \l_keys_key_tl }
10078     }
10079     \__keys_default_set:n { true }
10080 }
10081 \cs_generate_variant:Nn \__keys_bool_set_inverse:Nn { c }

```

(End definition for `\_keys_bool_set_inverse:Nn`.)

`\_keys_choice_make:` To make a choice from a key, two steps: set the code, and set the unknown key. As  
`\_keys_multichoice_make:` multichoice and choices are essentially the same bar one function, the code is given  
`\_keys_choice_make:N` together.  
`\_keys_choice_make_aux:N`

```

10082 \cs_new_protected:Npn \_keys_choice_make:
10083   { \_keys_choice_make:N \_keys_choice_find:n }
10084 \cs_new_protected:Npn \_keys_multichoice_make:
10085   { \_keys_choice_make:N \_keys_multichoice_find:n }
10086 \cs_new_protected:Npn \_keys_choice_make:N #1
10087   {
10088     \cs_if_exist:cTF
10089       { \c__keys_type_root_tl \_keys_parent:o \l_keys_path_tl }
10090       {
10091         \str_if_eq_x:nnTF
10092           { \exp_not:v { \c__keys_type_root_tl \_keys_parent:o \l_keys_path_tl } }
10093           { choice }
10094           {
10095             \_msg_kernel_error:nxxx { kernel } { nested-choice-key }
10096             { \l_keys_path_tl } { \_keys_parent:o \l_keys_path_tl }
10097           }
10098           { \_keys_choice_make_aux:N #1 }
10099       }
10100       { \_keys_choice_make_aux:N #1 }
10101   }
10102 \cs_new_protected:Npn \_keys_choice_make_aux:N #1
10103   {
10104     \cs_set_nopar:cpn { \c__keys_type_root_tl \l_keys_path_tl } { choice }
10105     \_keys_cmd_set:nn { \l_keys_path_tl } { #1 {##1} }
10106     \_keys_cmd_set:nn { \l_keys_path_tl / unknown }
10107     {
10108       \_msg_kernel_error:nxxx { kernel } { key-choice-unknown }
10109       { \l_keys_path_tl } {##1}
10110     }
10111   }

```

(End definition for `\_keys_choice_make:` and others.)

`\_keys_choices_make:nn` Auto-generating choices means setting up the root key as a choice, then defining each  
`\_keys_multichoice_make:nn` choice in turn.

```

\_keys_choices_make:Nnn
10112 \cs_new_protected:Npn \_keys_choices_make:nn
10113   { \_keys_choices_make:Nnn \_keys_choice_make: }
10114 \cs_new_protected:Npn \_keys_multichoice_make:nn
10115   { \_keys_choices_make:Nnn \_keys_multichoice_make: }
10116 \cs_new_protected:Npn \_keys_choices_make:Nnn #1#2#3
10117   {
10118     #1
10119     \int_zero:N \l_keys_choice_int
10120     \clist_map_inline:nn {#2}
10121     {
10122       \int_incr:N \l_keys_choice_int
10123       \_keys_cmd_set:nx { \l_keys_path_tl / \_keys_remove_spaces:n {##1} }
10124       {
10125         \tl_set:Nn \exp_not:N \l_keys_choice_tl {##1}

```

```

10126         \int_set:Nn \exp_not:N \l_keys_choice_int
10127         { \int_use:N \l_keys_choice_int }
10128         \exp_not:n {#3}
10129     }
10130 }
10131 }

```

*(End definition for \\_\_keys\_choices\_make:nn, \\_\_keys\_multichoices\_make:nn, and \\_\_keys\_choices-make:Nnn.)*

**\\_\_keys\_cmd\_set:nn** Setting the code for a key first logs if appropriate that we are defining a new key, then saves the code.

```

\__keys_cmd_set:nx
\__keys_cmd_set:Vn
\__keys_cmd_set:Vo
10132 \__debug_patch:nnNw
10133 {
10134     \cs_if_exist:cF { \c__keys_code_root_tl #1 }
10135     { \__debug_log:x { Defining~key~#1~\msg_line_context: } }
10136 }
10137 { }
10138 \cs_new_protected:Npn \__keys_cmd_set:nn #1#2
10139 { \cs_set_protected:cpn { \c__keys_code_root_tl #1 } ##1 {#2} }
10140 \cs_generate_variant:Nn \__keys_cmd_set:nn { nx , Vn , Vo }

```

*(End definition for \\_\_keys\_cmd\_set:nn.)*

**\\_\_keys\_default\_set:n** Setting a default value is easy. These are stored using `\cs_set:cpx` as this avoids any worries about whether a token list exists.

```

10141 \cs_new_protected:Npn \__keys_default_set:n #1
10142 {
10143     \tl_if_empty:nTF {#1}
10144     {
10145         \cs_set_eq:cN
10146         { \c__keys_default_root_tl \l_keys_path_tl }
10147         \tex_undefined:D
10148     }
10149     {
10150         \cs_set:cpx
10151         { \c__keys_default_root_tl \l_keys_path_tl }
10152         { \exp_not:n {#1} }
10153     }
10154 }

```

*(End definition for \\_\_keys\_default\_set:n.)*

**\\_\_keys\_groups\_set:n** Assigning a key to one or more groups uses comma lists. As the list of groups only exists if there is anything to do, the setting is done using a scratch list. For the usual grouping reasons we use the low-level approach to undefining a list. We also use the low-level approach for the other case to avoid tripping up the `check-declarations` code.

```

10155 \cs_new_protected:Npn \__keys_groups_set:n #1
10156 {
10157     \clist_set:Nn \l__keys_groups_clist {#1}
10158     \clist_if_empty:NTF \l__keys_groups_clist
10159     {
10160         \cs_set_eq:cN { \c__keys_groups_root_tl \l_keys_path_tl }
10161         \tex_undefined:D

```

```

10162     }
10163     {
10164         \cs_set_eq:cN { \c__keys_groups_root_tl \l_keys_path_tl }
10165         \l__keys_groups_clist
10166     }
10167 }

```

*(End definition for \\_\_keys\_groups\_set:n.)*

**\\_\_keys\_inherit:n** Inheritance means ignoring anything already said about the key: zap the lot and set up.

```

10168 \cs_new_protected:Npn \__keys_inherit:n #1
10169 {
10170     \__keys_undefine:
10171     \cs_set_nopar:cpn { \c__keys_inherit_root_tl \l_keys_path_tl } {#1}
10172 }

```

*(End definition for \\_\_keys\_inherit:n.)*

**\\_\_keys\_initialise:n** A set up for initialisation: just run the code if it exists.

```

10173 \cs_new_protected:Npn \__keys_initialise:n #1
10174 {
10175     \cs_if_exist_use:cT { \c__keys_code_root_tl \l_keys_path_tl } { {#1} }
10176 }

```

*(End definition for \\_\_keys\_initialise:n.)*

**\\_\_keys\_meta\_make:n** To create a meta-key, simply set up to pass data through.

```

\__keys_meta_make:nn
10177 \cs_new_protected:Npn \__keys_meta_make:n #1
10178 {
10179     \__keys_cmd_set:Vo \l_keys_path_tl
10180     {
10181         \exp_after:wN \keys_set:nn
10182         \exp_after:wN { \l__keys_module_tl } {#1}
10183     }
10184 }
10185 \cs_new_protected:Npn \__keys_meta_make:nn #1#2
10186 { \__keys_cmd_set:Vn \l_keys_path_tl { \keys_set:nn {#1} {#2} } }

```

*(End definition for \\_\_keys\_meta\_make:n and \\_\_keys\_meta\_make:nn.)*

**\\_\_keys\_undefine:** Undefining a key has to be done without `\cs_undefine:c` as that function acts globally.

```

10187 \cs_new_protected:Npn \__keys_undefine:
10188 {
10189     \clist_map_inline:nn
10190     { code , default , groups , inherit , type , validate }
10191     {
10192         \cs_set_eq:cN
10193         { \tl_use:c { c__keys_ ##1 _root_tl } \l_keys_path_tl }
10194         \tex_undefined:D
10195     }
10196 }

```

*(End definition for \\_\_keys\_undefine:.)*

`\__keys_value_requirement:nn` Validating key input is done using a second function which runs before the main key code. Setting that up means setting it equal to a generic stub which does the check. This approach makes the lookup very fast at the cost of one additional csname per key that needs it. The cleanup here has to know the structure of the following code.

```

10197 \cs_new_protected:Npn \__keys_value_requirement:nn #1#2
10198 {
10199   \str_case:nnF {#2}
10200   {
10201     { true }
10202     {
10203       \cs_set_eq:cc
10204       { \c__keys_validate_root_tl \l_keys_path_tl }
10205       { __keys_validate_ #1 : }
10206     }
10207   { false }
10208   {
10209     \cs_if_eq:ccT
10210     { \c__keys_validate_root_tl \l_keys_path_tl }
10211     { __keys_validate_ #1 : }
10212     {
10213       \cs_set_eq:cN
10214       { \c__keys_validate_root_tl \l_keys_path_tl }
10215       \tex_undefined:D
10216     }
10217   }
10218 }
10219 {
10220   \__msg_kernel_error:nnx { kernel } { property-boolean-values-only }
10221   { .value_ #1 :n }
10222 }
10223 }
10224 \cs_new_protected:Npn \__keys_validate_forbidden:
10225 {
10226   \bool_if:NF \l__keys_no_value_bool
10227   {
10228     \__msg_kernel_error:nnxx { kernel } { value-forbidden }
10229     { \l_keys_path_tl } { \l_keys_value_tl }
10230     \__keys_validate_cleanup:w
10231   }
10232 }
10233 \cs_new_protected:Npn \__keys_validate_required:
10234 {
10235   \bool_if:NT \l__keys_no_value_bool
10236   {
10237     \__msg_kernel_error:nnx { kernel } { value-required }
10238     { \l_keys_path_tl }
10239     \__keys_validate_cleanup:w
10240   }
10241 }
10242 \cs_new_protected:Npn \__keys_validate_cleanup:w #1 \cs_end: #2#3 { }

```

(End definition for `\__keys_value_requirement:nn` and others.)

`\__keys_variable_set:NnnN` Setting a variable takes the type and scope separately so that it is easy to make a new  
`\__keys_variable_set:cnnN`

variable if needed.

```

10243 \cs_new_protected:Npn \__keys_variable_set:NnnN #1#2#3#4
10244 {
10245     \use:c { #2_if_exist:NF } #1 { \use:c { #2_new:N } #1 }
10246     \__keys_cmd_set:nx { \l_keys_path_tl }
10247     {
10248         \exp_not:c { #2 _ #3 set:N #4 }
10249         \exp_not:N #1
10250         \exp_not:n { {##1} }
10251     }
10252 }
10253 \cs_generate_variant:Nn \__keys_variable_set:NnnN { c }

```

(End definition for `\__keys_variable_set:NnnN`.)

## 19.5 Creating key properties

The key property functions are all wrappers for internal functions, meaning that things stay readable and can also be altered later on.

Importantly, while key properties have “normal” argument specs, the underlying code always supplies one braced argument to these. As such, argument expansion is handled by hand rather than using the standard tools. This shows up particularly for the two-argument properties, where things would otherwise go badly wrong.

```

.bool_set:N One function for this.
.bool_set:c 10254 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_set:N } #1
.bool_gset:N 10255 { \__keys_bool_set:Nn #1 { } }
.bool_gset:c 10256 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_set:c } #1
10257 { \__keys_bool_set:cn {#1} { } }
10258 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_gset:N } #1
10259 { \__keys_bool_set:Nn #1 { g } }
10260 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_gset:c } #1
10261 { \__keys_bool_set:cn {#1} { g } }

```

(End definition for `.bool_set:N` and `.bool_gset:N`. These functions are documented on page 165.)

```

.bool_set_inverse:N One function for this.
.bool_set_inverse:c 10262 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_set_inverse:N } #1
.bool_gset_inverse:N 10263 { \__keys_bool_set_inverse:Nn #1 { } }
.bool_gset_inverse:c 10264 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_set_inverse:c } #1
10265 { \__keys_bool_set_inverse:cn {#1} { } }
10266 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_gset_inverse:N } #1
10267 { \__keys_bool_set_inverse:Nn #1 { g } }
10268 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_gset_inverse:c } #1
10269 { \__keys_bool_set_inverse:cn {#1} { g } }

```

(End definition for `.bool_set_inverse:N` and `.bool_gset_inverse:N`. These functions are documented on page 165.)

`.choice:` Making a choice is handled internally, as it is also needed by `.generate_choices:n`.

```

10270 \cs_new_protected:cpn { \c__keys_props_root_tl .choice: }
10271 { \__keys_choice_make: }

```

(End definition for `.choice:`. This function is documented on page 165.)



**.choices:nn** For auto-generation of a series of mutually-exclusive choices. Here, #1 consists of two separate arguments, hence the slightly odd-looking implementation.

```
.choices:Vn
.choices:on
.choices:xn
10272 \cs_new_protected:cpn { \c__keys_props_root_tl .choices:nn } #1
10273 { \__keys_choices_make:nn #1 }
10274 \cs_new_protected:cpn { \c__keys_props_root_tl .choices:Vn } #1
10275 { \exp_args:NV \__keys_choices_make:nn #1 }
10276 \cs_new_protected:cpn { \c__keys_props_root_tl .choices:on } #1
10277 { \exp_args:No \__keys_choices_make:nn #1 }
10278 \cs_new_protected:cpn { \c__keys_props_root_tl .choices:xn } #1
10279 { \exp_args:Nx \__keys_choices_make:nn #1 }
```

(End definition for .choices:nn. This function is documented on page 165.)

**.code:n** Creating code is simply a case of passing through to the underlying set function.

```
10280 \cs_new_protected:cpn { \c__keys_props_root_tl .code:n } #1
10281 { \__keys_cmd_set:nn { \l_keys_path_tl } {#1} }
```

(End definition for .code:n. This function is documented on page 165.)

**.clist\_set:N**

```
.clist_set:c
10282 \cs_new_protected:cpn { \c__keys_props_root_tl .clist_set:N } #1
10283 { \__keys_variable_set:NnnN #1 { clist } { } n }
.clist_gset:N
10284 \cs_new_protected:cpn { \c__keys_props_root_tl .clist_set:c } #1
10285 { \__keys_variable_set:cnnN {#1} { clist } { } n }
10286 \cs_new_protected:cpn { \c__keys_props_root_tl .clist_gset:N } #1
10287 { \__keys_variable_set:NnnN #1 { clist } { g } n }
10288 \cs_new_protected:cpn { \c__keys_props_root_tl .clist_gset:c } #1
10289 { \__keys_variable_set:cnnN {#1} { clist } { g } n }
```

(End definition for .clist\_set:N and .clist\_gset:N. These functions are documented on page 165.)

**.default:n** Expansion is left to the internal functions.

```
.default:V
10290 \cs_new_protected:cpn { \c__keys_props_root_tl .default:n } #1
10291 { \__keys_default_set:n {#1} }
.default:o
10292 \cs_new_protected:cpn { \c__keys_props_root_tl .default:V } #1
10293 { \exp_args:NV \__keys_default_set:n #1 }
10294 \cs_new_protected:cpn { \c__keys_props_root_tl .default:o } #1
10295 { \exp_args:No \__keys_default_set:n {#1} }
10296 \cs_new_protected:cpn { \c__keys_props_root_tl .default:x } #1
10297 { \exp_args:Nx \__keys_default_set:n {#1} }
```

(End definition for .default:n. This function is documented on page 166.)

**.dim\_set:N** Setting a variable is very easy: just pass the data along.

```
.dim_set:c
10298 \cs_new_protected:cpn { \c__keys_props_root_tl .dim_set:N } #1
10299 { \__keys_variable_set:NnnN #1 { dim } { } n }
.clist_gset:N
10300 \cs_new_protected:cpn { \c__keys_props_root_tl .dim_set:c } #1
10301 { \__keys_variable_set:cnnN {#1} { dim } { } n }
10302 \cs_new_protected:cpn { \c__keys_props_root_tl .dim_gset:N } #1
10303 { \__keys_variable_set:NnnN #1 { dim } { g } n }
10304 \cs_new_protected:cpn { \c__keys_props_root_tl .dim_gset:c } #1
10305 { \__keys_variable_set:cnnN {#1} { dim } { g } n }
```

(End definition for .dim\_set:N and .dim\_gset:N. These functions are documented on page 166.)

**.fp\_set:N** Setting a variable is very easy: just pass the data along.

```

10306 \cs_new_protected:cpn { \c__keys_props_root_tl .fp_set:N } #1
10307 { \__keys_variable_set:NnnN #1 { fp } { } n }
.fp_gset:N
10308 \cs_new_protected:cpn { \c__keys_props_root_tl .fp_set:c } #1
10309 { \__keys_variable_set:cnnN {#1} { fp } { } n }
.fp_gset:c
10310 \cs_new_protected:cpn { \c__keys_props_root_tl .fp_gset:N } #1
10311 { \__keys_variable_set:NnnN #1 { fp } { g } n }
10312 \cs_new_protected:cpn { \c__keys_props_root_tl .fp_gset:c } #1
10313 { \__keys_variable_set:cnnN {#1} { fp } { g } n }

```

(End definition for .fp\_set:N and .fp\_gset:N. These functions are documented on page 166.)

**.groups:n** A single property to create groups of keys.

```

10314 \cs_new_protected:cpn { \c__keys_props_root_tl .groups:n } #1
10315 { \__keys_groups_set:n {#1} }

```

(End definition for .groups:n. This function is documented on page 166.)

**.inherit:n** Nothing complex: only one variant at the moment!

```

10316 \cs_new_protected:cpn { \c__keys_props_root_tl .inherit:n } #1
10317 { \__keys_inherit:n {#1} }

```

(End definition for .inherit:n. This function is documented on page 166.)

**.initial:n** The standard hand-off approach.

```

10318 \cs_new_protected:cpn { \c__keys_props_root_tl .initial:n } #1
10319 { \__keys_initialise:n {#1} }
.initial:V
10320 \cs_new_protected:cpn { \c__keys_props_root_tl .initial:V } #1
10321 { \exp_args:NV \__keys_initialise:n #1 }
.initial:o
10322 \cs_new_protected:cpn { \c__keys_props_root_tl .initial:o } #1
10323 { \exp_args:No \__keys_initialise:n {#1} }
.initial:x
10324 \cs_new_protected:cpn { \c__keys_props_root_tl .initial:x } #1
10325 { \exp_args:Nx \__keys_initialise:n {#1} }

```

(End definition for .initial:n. This function is documented on page 167.)

**.int\_set:N** Setting a variable is very easy: just pass the data along.

```

10326 \cs_new_protected:cpn { \c__keys_props_root_tl .int_set:N } #1
10327 { \__keys_variable_set:NnnN #1 { int } { } n }
.int_gset:N
10328 \cs_new_protected:cpn { \c__keys_props_root_tl .int_set:c } #1
10329 { \__keys_variable_set:cnnN {#1} { int } { } n }
.int_gset:c
10330 \cs_new_protected:cpn { \c__keys_props_root_tl .int_gset:N } #1
10331 { \__keys_variable_set:NnnN #1 { int } { g } n }
10332 \cs_new_protected:cpn { \c__keys_props_root_tl .int_gset:c } #1
10333 { \__keys_variable_set:cnnN {#1} { int } { g } n }

```

(End definition for .int\_set:N and .int\_gset:N. These functions are documented on page 167.)

**.meta:n** Making a meta is handled internally.

```

10334 \cs_new_protected:cpn { \c__keys_props_root_tl .meta:n } #1
10335 { \__keys_meta_make:n {#1} }

```

(End definition for .meta:n. This function is documented on page 167.)

**.meta:nn** Meta with path: potentially lots of variants, but for the moment no so many defined.

```
10336 \cs_new_protected:cpn { \c__keys_props_root_tl .meta:nn } #1
10337 { \__keys_meta_make:nn #1 }
```

(End definition for .meta:nn. This function is documented on page 167.)

**.multichoice:** The same idea as .choice: and .choices:nn, but where more than one choice is allowed.

```
.multichoices:nn 10338 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoice: }
.multichoices:Vn 10339 { \__keys_multichoice_make: }
.multichoices:on 10340 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoices:nn } #1
.multichoices:xn 10341 { \__keys_multichoices_make:nn #1 }
10342 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoices:Vn } #1
10343 { \exp_args:NV \__keys_multichoices_make:nn #1 }
10344 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoices:on } #1
10345 { \exp_args:No \__keys_multichoices_make:nn #1 }
10346 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoices:xn } #1
10347 { \exp_args:Nx \__keys_multichoices_make:nn #1 }
```

(End definition for .multichoice: and .multichoices:nn. These functions are documented on page 167.)

**.skip\_set:N** Setting a variable is very easy: just pass the data along.

```
.skip_set:c 10348 \cs_new_protected:cpn { \c__keys_props_root_tl .skip_set:N } #1
.skip_gset:N 10349 { \__keys_variable_set:NnnN #1 { skip } { } n }
10350 \cs_new_protected:cpn { \c__keys_props_root_tl .skip_set:c } #1
10351 { \__keys_variable_set:cnnN {#1} { skip } { } n }
10352 \cs_new_protected:cpn { \c__keys_props_root_tl .skip_gset:N } #1
10353 { \__keys_variable_set:NnnN #1 { skip } { g } n }
10354 \cs_new_protected:cpn { \c__keys_props_root_tl .skip_gset:c } #1
10355 { \__keys_variable_set:cnnN {#1} { skip } { g } n }
```

(End definition for .skip\_set:N and .skip\_gset:N. These functions are documented on page 167.)

**.tl\_set:N** Setting a variable is very easy: just pass the data along.

```
.tl_set:c 10356 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_set:N } #1
.tl_gset:N 10357 { \__keys_variable_set:NnnN #1 { tl } { } n }
.tl_gset:c 10358 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_set:c } #1
.tl_set_x:N 10359 { \__keys_variable_set:cnnN {#1} { tl } { } n }
.tl_set_x:c 10360 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_set_x:N } #1
.tl_gset_x:N 10361 { \__keys_variable_set:NnnN #1 { tl } { } x }
.tl_gset_x:c 10362 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_set_x:c } #1
10363 { \__keys_variable_set:cnnN {#1} { tl } { } x }
10364 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_gset:N } #1
10365 { \__keys_variable_set:NnnN #1 { tl } { g } n }
10366 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_gset:c } #1
10367 { \__keys_variable_set:cnnN {#1} { tl } { g } n }
10368 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_gset_x:N } #1
10369 { \__keys_variable_set:NnnN #1 { tl } { g } x }
10370 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_gset_x:c } #1
10371 { \__keys_variable_set:cnnN {#1} { tl } { g } x }
```

(End definition for .tl\_set:N and others. These functions are documented on page 167.)

**.undefine:** Another simple wrapper.

```
10372 \cs_new_protected:cpn { \c__keys_props_root_tl .undefine: }
10373 { \__keys_undefine: }
```

(End definition for `.undefine:.`. This function is documented on page 168.)

`.value_forbidden:n` These are very similar, so both call the same function.

```
.value_required:n 10374 \cs_new_protected:cpn { \c__keys_props_root_tl .value_forbidden:n } #1
                  10375 { \__keys_value_requirement:nn { forbidden } {#1} }
                  10376 \cs_new_protected:cpn { \c__keys_props_root_tl .value_required:n } #1
                  10377 { \__keys_value_requirement:nn { required } {#1} }
```

(End definition for `.value_forbidden:n` and `.value_required:n`. These functions are documented on page 168.)

## 19.6 Setting keys

`\keys_set:nn` A simple wrapper again.

```
\keys_set:nV 10378 \cs_new_protected:Npn \keys_set:nn
\keys_set:nv 10379 { \__keys_set:onn { \l__keys_module_tl } }
\keys_set:no 10380 \cs_new_protected:Npn \__keys_set:nnn #1#2#3
\__keys_set:nnn 10381 {
\__keys_set:onn 10382 \tl_set:Nx \l__keys_module_tl { \__keys_remove_spaces:n {#2} }
                  10383 \keyval_parse:NNn \__keys_set:n \__keys_set:nn {#3}
                  10384 \tl_set:Nn \l__keys_module_tl {#1}
                  10385 }
                  10386 \cs_generate_variant:Nn \keys_set:nn { nV , nv , no }
                  10387 \cs_generate_variant:Nn \__keys_set:nnn { o }
```

(End definition for `\keys_set:nn` and `\__keys_set:nnn`. These functions are documented on page 171.)

`\keys_set_known:nnN` Setting known keys simply means setting the appropriate flag, then running the standard code. To allow for nested setting, any existing value of `\l__keys_unused_clist` is saved on the stack and reset afterwards. Note that for speed/simplicity reasons we use a `tl` operation to set the `clist` here!

```
\keys_set_known:nVN 10388 \cs_new_protected:Npn \keys_set_known:nnN
\keys_set_known:nvN 10389 { \__keys_set_known:onnN \l__keys_unused_clist }
\keys_set_known:noN 10390 \cs_generate_variant:Nn \keys_set_known:nnN { nV , nv , no }
\__keys_set_known:nnnN 10391 \cs_new_protected:Npn \__keys_set_known:nnnN #1#2#3#4
\__keys_set_known:onnN 10392 {
\keys_set_known:nV 10393 \clist_clear:N \l__keys_unused_clist
\keys_set_known:nv 10394 \keys_set_known:nn {#2} {#3}
\keys_set_known:no 10395 \tl_set:Nx #4 { \exp_not:o { \l__keys_unused_clist } }
\__keys_keys_set_known:nn 10396 \tl_set:Nn \l__keys_unused_clist {#1}
                          10397 }
                          10398 \cs_generate_variant:Nn \__keys_set_known:nnnN { o }
                          10399 \cs_new_protected:Npn \keys_set_known:nn #1#2
                          10400 {
                          10401 \bool_if:NTF \l__keys_only_known_bool
                          10402 { \keys_set:nn }
                          10403 { \__keys_set_known:nn }
                          10404 {#1} {#2}
                          10405 }
                          10406 \cs_generate_variant:Nn \keys_set_known:nn { nV , nv , no }
                          10407 \cs_new_protected:Npn \__keys_set_known:nn #1#2
                          10408 {
                          10409 \bool_set_true:N \l__keys_only_known_bool
                          10410 \keys_set:nn {#1} {#2}
```

```

10411     \bool_set_false:N \l__keys_only_known_bool
10412 }

```

(End definition for \keys\_set\_known:nnN and others. These functions are documented on page 172.)

```

\keys_set_filter:nnnN The idea of setting keys in a selective manner again uses flags wrapped around the basic
\keys_set_filter:nnVN code. The comments on \keys_set_known:nnN also apply here. We have a bit more
\keys_set_filter:nnvN shuffling to do to keep everything nestable.
\keys_set_filter:nnoN
__keys_set_filter:nnnnN
__keys_set_filter:onnnN
\keys_set_filter:nnn 10413 \cs_new_protected:Npn \keys_set_filter:nnnN
\keys_set_filter:nnV 10414 { \__keys_set_filter:onnnN \l__keys_unused_clist }
\keys_set_filter:nnv 10415 \cs_generate_variant:Nn \keys_set_filter:nnnN { nnV , nnv , nno }
\keys_set_filter:nno 10416 \cs_new_protected:Npn \__keys_set_filter:nnnnN #1#2#3#4#5
__keys_set_filter:nnn 10417 {
\keys_set_groups:nnn 10418 \clist_clear:N \l__keys_unused_clist
\keys_set_groups:nnV 10419 \keys_set_filter:nnn {#2} {#3} {#4}
\keys_set_groups:nnv 10420 \tl_set:Nx #5 { \exp_not:o { \l__keys_unused_clist } }
\keys_set_groups:nno 10421 \tl_set:Nn \l__keys_unused_clist {#1}
__keys_set_selective:nnn 10422 }
__keys_set_selective:nnnn 10423 \cs_generate_variant:Nn \__keys_set_filter:nnnnN { o }
__keys_set_selective:onnn 10424 \cs_new_protected:Npn \keys_set_filter:nnn #1#2#3
__keys_set_selective:nn 10425 {
10426 \bool_if:NTF \l__keys_filtered_bool
10427 { \__keys_set_selective:nnn }
10428 { \__keys_set_filter:nnn }
10429 {#1} {#2} {#3}
10430 }
10431 \cs_generate_variant:Nn \keys_set_filter:nnn { nnV , nnv , nno }
10432 \cs_new_protected:Npn \__keys_set_filter:nnn #1#2#3
10433 {
10434 \bool_set_true:N \l__keys_filtered_bool
10435 \__keys_set_selective:nnn {#1} {#2} {#3}
10436 \bool_set_false:N \l__keys_filtered_bool
10437 }
10438 \cs_new_protected:Npn \keys_set_groups:nnn #1#2#3
10439 {
10440 \bool_if:NTF \l__keys_filtered_bool
10441 { \__keys_set_groups:nnn }
10442 { \__keys_set_selective:nnn }
10443 {#1} {#2} {#3}
10444 }
10445 \cs_generate_variant:Nn \keys_set_groups:nnn { nnV , nnv , nno }
10446 \cs_new_protected:Npn \__keys_set_groups:nnn #1#2#3
10447 {
10448 \bool_set_false:N \l__keys_filtered_bool
10449 \__keys_set_selective:nnn {#1} {#2} {#3}
10450 \bool_set_true:N \l__keys_filtered_bool
10451 }
10452 \cs_new_protected:Npn \__keys_set_selective:nnn
10453 { \__keys_set_selective:onnn \l__keys_selective_seq }
10454 \cs_new_protected:Npn \__keys_set_selective:nnnn #1#2#3#4
10455 {
10456 \seq_set_from_clist:Nn \l__keys_selective_seq {#3}
10457 \bool_if:NTF \l__keys_selective_bool
10458 { \keys_set:nn }

```

```

10459         { \__keys_set_selective:nn }
10460         {#2} {#4}
10461         \tl_set:Nn \l__keys_selective_seq {#1}
10462     }
10463 \cs_generate_variant:Nn \__keys_set_selective:nnnn { o }
10464 \cs_new_protected:Npn \__keys_set_selective:nn #1#2
10465 {
10466     \bool_set_true:N \l__keys_selective_bool
10467     \keys_set:nn {#1} {#2}
10468     \bool_set_false:N \l__keys_selective_bool
10469 }

```

(End definition for \keys\_set\_filter:nnnN and others. These functions are documented on page 173.)

<pre> \__keys_set:n \__keys_set:nn \__keys_set_aux:nnn \__keys_set_aux:onn \__keys_find_key_module:w \__keys_set_aux: \__keys_set_selective: </pre>	<p>A shared system once again. First, set the current path and add a default if needed. There are then checks to see if the a value is required or forbidden. If everything passes, move on to execute the code.</p> <pre> 10470 \cs_new_protected:Npn \__keys_set:n #1 10471 { 10472     \bool_set_true:N \l__keys_no_value_bool 10473     \__keys_set_aux:onn \l__keys_module_tl {#1} { } 10474 } 10475 \cs_new_protected:Npn \__keys_set:nn #1#2 10476 { 10477     \bool_set_false:N \l__keys_no_value_bool 10478     \__keys_set_aux:onn \l__keys_module_tl {#1} {#2} 10479 } </pre>
---	--

The key path here can be fully defined, after which there is a search for the key and module names: the user may have passed them with part of what is actually the module (for our purposes) in the key name. As that happens on a per-key basis, we use the stack approach to restore the module name without a group.

```

10480 \cs_new_protected:Npn \__keys_set_aux:nnn #1#2#3
10481 {
10482     \tl_set:Nx \l_keys_path_tl
10483     {
10484         \tl_if_blank:nF {#1}
10485         { #1 / }
10486         \__keys_remove_spaces:n {#2}
10487     }
10488     \tl_clear:N \l__keys_module_tl
10489     \exp_after:wN \__keys_find_key_module:w \l_keys_path_tl / \q_stop
10490     \__keys_value_or_default:n {#3}
10491     \bool_if:NTF \l__keys_selective_bool
10492     { \__keys_set_selective: }
10493     { \__keys_execute: }
10494     \tl_set:Nn \l__keys_module_tl {#1}
10495 }
10496 \cs_generate_variant:Nn \__keys_set_aux:nnn { o }
10497 \cs_new_protected:Npn \__keys_find_key_module:w #1 / #2 \q_stop
10498 {
10499     \tl_if_blank:nTF {#2}
10500     { \tl_set:Nn \l_keys_key_tl {#1} }
10501     {

```

```

10502         \tl_put_right:Nx \l__keys_module_tl
10503         {
10504             \tl_if_empty:NF \l__keys_module_tl { / }
10505             #1
10506         }
10507         \__keys_find_key_module:w #2 \q_stop
10508     }
10509 }

```

If selective setting is active, there are a number of possible sub-cases to consider. The key name may not be known at all or if it is, it may not have any groups assigned. There is then the question of whether the selection is opt-in or opt-out.

```

10510 \cs_new_protected:Npn \__keys_set_selective:
10511 {
10512     \cs_if_exist:cTF { \c__keys_groups_root_tl \l_keys_path_tl }
10513     {
10514         \clist_set_eq:Nc \l__keys_groups_clist
10515         { \c__keys_groups_root_tl \l_keys_path_tl }
10516         \__keys_check_groups:
10517     }
10518     {
10519         \bool_if:NTF \l__keys_filtered_bool
10520         { \__keys_execute: }
10521         { \__keys_store_unused: }
10522     }
10523 }

```

In the case where selective setting requires a comparison of the list of groups which apply to a key with the list of those which have been set active. That requires two mappings, and again a different outcome depending on whether opt-in or opt-out is set.

```

10524 \cs_new_protected:Npn \__keys_check_groups:
10525 {
10526     \bool_set_false:N \l__keys_tmp_bool
10527     \seq_map_inline:Nn \l__keys_selective_seq
10528     {
10529         \clist_map_inline:Nn \l__keys_groups_clist
10530         {
10531             \str_if_eq:nnT {##1} {####1}
10532             {
10533                 \bool_set_true:N \l__keys_tmp_bool
10534                 \clist_map_break:n { \seq_map_break: }
10535             }
10536         }
10537     }
10538     \bool_if:NTF \l__keys_tmp_bool
10539     {
10540         \bool_if:NTF \l__keys_filtered_bool
10541         { \__keys_store_unused: }
10542         { \__keys_execute: }
10543     }
10544     {
10545         \bool_if:NTF \l__keys_filtered_bool
10546         { \__keys_execute: }
10547         { \__keys_store_unused: }
10548     }

```

```
10549 }
```

(End definition for `\_keys_set:n` and others.)

`\_keys_value_or_default:n` If a value is given, return it as #1, otherwise send a default if available.

```
10550 \cs_new_protected:Npn \_keys_value_or_default:n #1
10551 {
10552   \bool_if:NTF \l_keys_no_value_bool
10553   {
10554     \cs_if_exist:cTF { \c__keys_default_root_tl \l_keys_path_tl }
10555     {
10556       \tl_set_eq:Nc
10557         \l_keys_value_tl
10558         { \c__keys_default_root_tl \l_keys_path_tl }
10559     }
10560     { \tl_clear:N \l_keys_value_tl }
10561   }
10562   { \tl_set:Nn \l_keys_value_tl {#1} }
10563 }
```

(End definition for `\_keys_value_or_default:n`.)

`\_keys_execute:` Actually executing a key is done in two parts. First, look for the key itself, then look  
`\_keys_execute_unknown:` for the **unknown** key with the same path. If both of these fail, complain. What exactly  
`\_keys_execute:nn` happens if a key is unknown depends on whether unknown keys are being skipped or if  
`\_keys_store_unused:` an error should be raised.

```
10564 \cs_new_protected:Npn \_keys_execute:
10565 {
10566   \cs_if_exist:cTF { \c__keys_code_root_tl \l_keys_path_tl }
10567   {
10568     \cs_if_exist_use:c { \c__keys_validate_root_tl \l_keys_path_tl }
10569     \cs:w \c__keys_code_root_tl \l_keys_path_tl \exp_after:wN \cs_end:
10570     \exp_after:wN { \l_keys_value_tl }
10571   }
10572   { \_keys_execute_unknown: }
10573 }
10574 \cs_new_protected:Npn \_keys_execute_unknown:
10575 {
10576   \bool_if:NTF \l_keys_only_known_bool
10577   { \_keys_store_unused: }
10578   {
10579     \cs_if_exist:cTF
10580     { \c__keys_inherit_root_tl \_keys_parent:o \l_keys_path_tl }
10581     {
10582       \clist_map_inline:cn
10583       { \c__keys_inherit_root_tl \_keys_parent:o \l_keys_path_tl }
10584       {
10585         \cs_if_exist:cT
10586         { \c__keys_code_root_tl ##1 / \l_keys_key_tl }
10587         {
10588           \cs:w \c__keys_code_root_tl ##1 / \l_keys_key_tl
10589           \exp_after:wN \cs_end: \exp_after:wN
10590           { \l_keys_value_tl }
10591         }
10592       }
10593     }
10594   }
10595 }
```



```

10592     }
10593   }
10594 }
10595 {
10596   \cs_if_exist:cTF { \c__keys_code_root_tl \l__keys_module_tl / unknown }
10597   {
10598     \cs:w \c__keys_code_root_tl \l__keys_module_tl / unknown
10599     \exp_after:wN \cs_end: \exp_after:wN { \l_keys_value_tl }
10600   }
10601   {
10602     \__msg_kernel_error:nxxx { kernel } { key-unknown }
10603     { \l_keys_path_tl } { \l__keys_module_tl }
10604   }
10605 }
10606 }
10607 }
10608 \cs_new:Npn \__keys_execute:nn #1#2
10609 {
10610   \cs_if_exist:cTF { \c__keys_code_root_tl #1 }
10611   {
10612     \cs:w \c__keys_code_root_tl #1 \exp_after:wN \cs_end:
10613     \exp_after:wN { \l_keys_value_tl }
10614   }
10615   {#2}
10616 }
10617 \cs_new_protected:Npn \__keys_store_unused:
10618 {
10619   \clist_put_right:Nx \l__keys_unused_clist
10620   {
10621     \exp_not:o \l_keys_key_tl
10622     \bool_if:NF \l__keys_no_value_bool
10623     { = { \exp_not:o \l_keys_value_tl } }
10624   }
10625 }

```

(End definition for `\__keys_execute:` and others.)

`\__keys_choice_find:n` Executing a choice has two parts. First, try the choice given, then if that fails call the  
`\__keys_multichoice_find:n` unknown key. That always exists, as it is created when a choice is first made. So there  
is no need for any escape code. For multiple choices, the same code ends up used in a  
mapping.

```

10626 \cs_new:Npn \__keys_choice_find:n #1
10627 {
10628   \__keys_execute:nn { \l_keys_path_tl / \__keys_remove_spaces:n {#1} }
10629   { \__keys_execute:nn { \l_keys_path_tl / unknown } { } }
10630 }
10631 \cs_new:Npn \__keys_multichoice_find:n #1
10632 { \clist_map_function:nN {#1} \__keys_choice_find:n }

```

(End definition for `\__keys_choice_find:n` and `\__keys_multichoice_find:n`.)

## 19.7 Utilities

`\__keys_parent:n` Used to strip off the ending part of the key path after the last /.  
`\__keys_parent:o`  
`\__keys_parent:w`

```

10633 \cs_new:Npn \__keys_parent:n #1
10634 { \__keys_parent:w #1 / / \q_stop { } }
10635 \cs_generate_variant:Nn \__keys_parent:n { o }
10636 \cs_new:Npn \__keys_parent:w #1 / #2 / #3 \q_stop #4
10637 {
10638   \tl_if_blank:nTF {#2}
10639   { \use_none:n #4 }
10640   {
10641     \__keys_parent:w #2 / #3 \q_stop { #4 / #1 }
10642   }
10643 }

```

(End definition for \\_\_keys\_parent:n and \\_\_keys\_parent:w.)

**\\_\_keys\_remove\_spaces:n** Removes all spaces from the input which is detokenized as a result. This function has the same effect as `\zap@space` in L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> after applying `\tl_to_str:n`. It is set up to be fast as the use case here is tightly defined. The ? is only there to allow for a space after `\use_none:nn` responsible for ending the loop.

**\\_\_keys\_remove\_spaces:w**

```

10644 \cs_new:Npn \__keys_remove_spaces:n #1
10645 {
10646   \exp_after:wN \__keys_remove_spaces:w \tl_to_str:n {#1}
10647   \use_none:nn ? ~
10648 }
10649 \cs_new:Npn \__keys_remove_spaces:w #1 ~
10650 { #1 \__keys_remove_spaces:w }

```

(End definition for \\_\_keys\_remove\_spaces:n and \\_\_keys\_remove\_spaces:w.)

**\keys\_if\_exist\_p:nn** A utility for others to see if a key exists.

**\keys\_if\_exist:nnTF**

```

10651 \prg_new_conditional:Npnn \keys_if_exist:nn #1#2 { p , T , F , TF }
10652 {
10653   \cs_if_exist:cTF
10654   { \c__keys_code_root_tl \__keys_remove_spaces:n { #1 / #2 } }
10655   { \prg_return_true: }
10656   { \prg_return_false: }
10657 }

```

(End definition for \keys\_if\_exist:nnTF. This function is documented on page 173.)

**\keys\_if\_choice\_exist\_p:nnn** Just an alternative view on \keys\_if\_exist:nnTF.

**\keys\_if\_choice\_exist:nnnTF**

```

10658 \prg_new_conditional:Npnn \keys_if_choice_exist:nnn #1#2#3
10659 { p , T , F , TF }
10660 {
10661   \cs_if_exist:cTF
10662   { \c__keys_code_root_tl \__keys_remove_spaces:n { #1 / #2 / #3 } }
10663   { \prg_return_true: }
10664   { \prg_return_false: }
10665 }

```

(End definition for \keys\_if\_choice\_exist:nnnTF. This function is documented on page 173.)

**\keys\_show:nn** To show a key, test for its existence to issue the correct message (same message, but with a `t` or `f` argument, then build the control sequences which contain the code and other

**\\_\_keys\_show:N**

information about the key, call an intermediate auxiliary which constructs the code to be displayed to the terminal, and finally conclude with `\__msg_show_wrap:n`.

```

10666 \cs_new_protected:Npn \keys_show:nn #1#2
10667 {
10668   \keys_if_exist:nnTF {#1} {#2}
10669   {
10670     \__msg_show_pre:nnxxxx { LaTeX / kernel } { show-key }
10671     { \__keys_remove_spaces:n { #1 / #2 } } { t } { } { }
10672     \exp_args:Nc \__keys_show:N
10673     { \c__keys_code_root_tl \__keys_remove_spaces:n { #1 / #2 } }
10674   }
10675   {
10676     \__msg_show_pre:nnxxxx { LaTeX / kernel } { show-key }
10677     { \__keys_remove_spaces:n { #1 / #2 } } { f } { } { }
10678     \__msg_show_wrap:n { }
10679   }
10680 }
10681 \cs_new_protected:Npn \__keys_show:N #1
10682 {
10683   \use:x
10684   {
10685     \__msg_show_wrap:n
10686     {
10687       \exp_not:N \__msg_show_item_unbraced:nn { code }
10688       { \token_get_replacement_spec:N #1 }
10689     }
10690   }
10691 }

```

(End definition for `\keys_show:nn` and `\__keys_show:N`. These functions are documented on page 173.)

**`\keys_log:nn`** Redirect output of `\keys_show:nn` to the log.

```

10692 \cs_new_protected:Npn \keys_log:nn
10693 { \__msg_log_next: \keys_show:nn }

```

(End definition for `\keys_log:nn`. This function is documented on page 173.)

## 19.8 Messages

For when there is a need to complain.

```

10694 \__msg_kernel_new:nnnn { kernel } { boolean-values-only }
10695 { Key~'#1'~accepts~boolean~values~only. }
10696 { The~key~'#1'~only~accepts~the~values~'true'~and~'false'. }
10697 \__msg_kernel_new:nnnn { kernel } { key-choice-unknown }
10698 { Key~'#1'~accepts~only~a~fixed~set~of~choices. }
10699 {
10700   The~key~'#1'~only~accepts~predefined~values,~
10701   and~'#2'~is~not~one~of~these.
10702 }
10703 \__msg_kernel_new:nnnn { kernel } { key-no-property }
10704 { No~property~given~in~definition~of~key~'#1'. }
10705 {
10706   \c__msg_coding_error_text_tl
10707   Inside~\keys_define:nn~each~key~name~

```

```

10708     needs~a~property:  \ \ \ \
10709     \iow_indent:n { #1 .<property> } \ \ \ \
10710     LaTeX~did~not~find~a~'. ' ~to~indicate~the~start~of~a~property.
10711   }
10712   \__msg_kernel_new:nnnn { kernel } { key-unknown }
10713   { The~key~'#1'~is~unknown~and~is~being~ignored. }
10714   {
10715     The~module~'#2'~does~not~have~a~key~called~'#1'. \ \
10716     Check~that~you~have~spelled~the~key~name~correctly.
10717   }
10718   \__msg_kernel_new:nnnn { kernel } { nested-choice-key }
10719   { Attempt~to~define~'#1'~as~a~nested~choice~key. }
10720   {
10721     The~key~'#1'~cannot~be~defined~as~a~choice~as~the~parent~key~'#2'~is~
10722     itself~a~choice.
10723   }
10724   \__msg_kernel_new:nnnn { kernel } { property-boolean-values-only }
10725   { The~property~'#1'~accepts~boolean~values~only. }
10726   {
10727     \c__msg_coding_error_text_tl
10728     The~property~'#1'~only~accepts~the~values~'true'~and~'false'.
10729   }
10730   \__msg_kernel_new:nnnn { kernel } { property-requires-value }
10731   { The~property~'#1'~requires~a~value. }
10732   {
10733     \c__msg_coding_error_text_tl
10734     LaTeX~was~asked~to~set~property~'#1'~for~key~'#2'. \ \
10735     No~value~was~given~for~the~property,~and~one~is~required.
10736   }
10737   \__msg_kernel_new:nnnn { kernel } { property-unknown }
10738   { The~key~property~'#1'~is~unknown. }
10739   {
10740     \c__msg_coding_error_text_tl
10741     LaTeX~has~been~asked~to~set~the~property~'#1'~for~key~'#2':~
10742     this~property~is~not~defined.
10743   }
10744   \__msg_kernel_new:nnnn { kernel } { value-forbidden }
10745   { The~key~'#1'~does~not~take~a~value. }
10746   {
10747     The~key~'#1'~should~be~given~without~a~value. \ \
10748     The~value~'#2'~was~present:~the~key~will~be~ignored.
10749   }
10750   \__msg_kernel_new:nnnn { kernel } { value-required }
10751   { The~key~'#1'~requires~a~value. }
10752   {
10753     The~key~'#1'~must~have~a~value. \ \
10754     No~value~was~present:~the~key~will~be~ignored.
10755   }
10756   \__msg_kernel_new:nnn { kernel } { show-key }
10757   {
10758     The~key~#1~
10759     \str_if_eq:nnTF {#2} { t }
10760     { has~the~properties: }
10761     { is~undefined. }

```

```

10762 }
10763 </initex | package>

```

## 20 l3fp implementation

Nothing to see here: everything is in the subfiles!

## 21 l3fp-aux implementation

```

10764 <*initex | package>
10765 <@@=fp>

```

### 21.1 Internal representation

Internally, a floating point number  $\langle X \rangle$  is a token list containing

```
\s__fp \__fp_chk:w <case> <sign> <body> ;
```

Let us explain each piece separately.

Internal floating point numbers are used in expressions, and in this context are subject to **f**-expansion. They must leave a recognizable mark after **f**-expansion, to prevent the floating point number from being re-parsed. Thus, `\s__fp` is simply another name for `\relax`.

When used directly without an accessor function, floating points should produce an error: this is the role of `\__fp_chk:w`. We could make floating point variables be protected to prevent them from expanding under **x**-expansion, but it seems more convenient to treat them as a subcase of token list variables.

The (decimal part of the) IEEE-754-2008 standard requires the format to be able to represent special floating point numbers besides the usual positive and negative cases. We distinguish the various possibilities by their  $\langle case \rangle$ , which is a single digit:

- 0 zeros: `+0` and `-0`,
- 1 “normal” numbers (positive and negative),
- 2 infinities: `+inf` and `-inf`,
- 3 quiet and signalling **nan**.

The  $\langle sign \rangle$  is 0 (positive) or 2 (negative), except in the case of **nan**, which have  $\langle sign \rangle = 1$ . This ensures that changing the  $\langle sign \rangle$  digit to  $2 - \langle sign \rangle$  is exactly equivalent to changing the sign of the number.

Special floating point numbers have the form

```
\s__fp \__fp_chk:w <case> <sign> \s__fp... ;
```

where `\s__fp...` is a scan mark carrying information about how the number was formed (useful for debugging).

Normal floating point numbers ( $\langle case \rangle = 1$ ) have the form

```
\s__fp \__fp_chk:w 1 <sign> {<exponent>} {<X1>} {<X2>} {<X3>} {<X4>} ;
```

Table 1: Internal representation of floating point numbers.

Representation	Meaning
0 0 \s\_fp\_... ;	Positive zero.
0 2 \s\_fp\_... ;	Negative zero.
1 0 {\langle exponent\rangle} {\langle X_1\rangle} {\langle X_2\rangle} {\langle X_3\rangle} {\langle X_4\rangle} ;	Positive floating point.
1 2 {\langle exponent\rangle} {\langle X_1\rangle} {\langle X_2\rangle} {\langle X_3\rangle} {\langle X_4\rangle} ;	Negative floating point.
2 0 \s\_fp\_... ;	Positive infinity.
2 2 \s\_fp\_... ;	Negative infinity.
3 1 \s\_fp\_... ;	Quiet nan.
3 1 \s\_fp\_... ;	Signalling nan.

Here, the  $\langle exponent \rangle$  is an integer, between  $-10000$  and  $10000$ . The body consists in four blocks of exactly 4 digits,  $0000 \leq \langle X_i \rangle \leq 9999$ , and the floating point is

$$(-1)^{\langle sign \rangle/2} \langle X_1 \rangle \langle X_2 \rangle \langle X_3 \rangle \langle X_4 \rangle \cdot 10^{\langle exponent \rangle - 16}$$

where we have concatenated the 16 digits. Currently, floating point numbers are normalized such that the  $\langle exponent \rangle$  is minimal, in other words,  $1000 \leq \langle X_1 \rangle \leq 9999$ .

Calculations are done in base 10000, *i.e.* one myriad.

## 21.2 Using arguments and semicolons

\\_fp\\_use\\_none\\_stop\\_f:n This function removes an argument (typically a digit) and replaces it by \exp\\_stop\\_f:, a marker which stops f-type expansion.

```
10766 \cs_new:Npn \_fp\_use\_none\_stop\_f:n #1 { \exp\_stop\_f: }
```

(End definition for \\_fp\\_use\\_none\\_stop\\_f:n.)

\\_fp\\_use\\_s:n Those functions place a semicolon after one or two arguments (typically digits).

```
10767 \cs_new:Npn \_fp\_use\_s:n #1 { #1; }
10768 \cs_new:Npn \_fp\_use\_s:nn #1#2 { #1#2; }
```

(End definition for \\_fp\\_use\\_s:n and \\_fp\\_use\\_s:nn.)

\\_fp\\_use\\_none\\_until\\_s:w Those functions select specific arguments among a set of arguments delimited by a semicolon.

```
\_fp\_use\_i\_until\_s:nw
\_fp\_use\_ii\_until\_s:nnw
10769 \cs_new:Npn \_fp\_use\_none\_until\_s:w #1; { }
10770 \cs_new:Npn \_fp\_use\_i\_until\_s:nw #1#2; { #1 }
10771 \cs_new:Npn \_fp\_use\_ii\_until\_s:nnw #1#2#3; { #2 }
```

(End definition for \\_fp\\_use\\_none\\_until\\_s:w, \\_fp\\_use\\_i\\_until\\_s:nw, and \\_fp\\_use\\_ii\\_until\\_s:nnw.)

\\_fp\\_reverse\\_args:Nww Many internal functions take arguments delimited by semicolons, and it is occasionally useful to swap two such arguments.

```
10772 \cs_new:Npn \_fp\_reverse\_args:Nww #1 #2; #3; { #1 #3; #2; }
```

(End definition for \\_fp\\_reverse\\_args:Nww.)

`\__fp_rrot:www` Rotate three arguments delimited by semicolons. This is the inverse (or the square) of the Forth primitive ROT, hence the name.

```
10773 \cs_new:Npn \__fp_rrot:www #1; #2; #3; { #2; #3; #1; }
```

(End definition for `\__fp_rrot:www`.)

`\__fp_use_i:ww` Many internal functions take arguments delimited by semicolons, and it is occasionally useful to remove one or two such arguments.

`\__fp_use_i:www`

```
10774 \cs_new:Npn \__fp_use_i:ww #1; #2; { #1; }
```

```
10775 \cs_new:Npn \__fp_use_i:www #1; #2; #3; { #1; }
```

(End definition for `\__fp_use_i:ww` and `\__fp_use_i:www`.)

## 21.3 Constants, and structure of floating points

`\s__fp` Floating points numbers all start with `\s__fp \__fp_chk:w`, where `\s__fp` is equal to the TeX primitive `\relax`, and `\__fp_chk:w` is protected. The rest of the floating point number is made of characters (or `\relax`). This ensures that nothing expands under f-expansion, nor under x-expansion. However, when typeset, `\s__fp` does nothing, and `\__fp_chk:w` is expanded. We define `\__fp_chk:w` to produce an error.

```
10776 \__scan_new:N \s__fp
```

```
10777 \cs_new_protected:Npn \__fp_chk:w #1 ;
```

```
10778 {
```

```
10779   \__msg_kernel_error:nnx { kernel } { misused-fp }
```

```
10780   { \fp_to_tl:n { \s__fp \__fp_chk:w #1 ; } }
```

```
10781 }
```

(End definition for `\s__fp` and `\__fp_chk:w`.)

`\s__fp_mark` Aliases of `\tex_relax:D`, used to terminate expressions.

`\s__fp_stop`

```
10782 \__scan_new:N \s__fp_mark
```

```
10783 \__scan_new:N \s__fp_stop
```

(End definition for `\s__fp_mark` and `\s__fp_stop`.)

`\s__fp_invalid` A couple of scan marks used to indicate where special floating point numbers come from.

`\s__fp_underflow`

```
10784 \__scan_new:N \s__fp_invalid
```

`\s__fp_overflow`

```
10785 \__scan_new:N \s__fp_underflow
```

`\s__fp_division`

```
10786 \__scan_new:N \s__fp_overflow
```

`\s__fp_exact`

```
10787 \__scan_new:N \s__fp_division
```

```
10788 \__scan_new:N \s__fp_exact
```

(End definition for `\s__fp_invalid` and others.)

`\c_zero_fp` The special floating points. We define the floating points here as “exact”.

`\c_minus_zero_fp`

```
10789 \tl_const:Nn \c_zero_fp { \s__fp \__fp_chk:w 0 0 \s__fp_exact ; }
```

`\c_inf_fp`

```
10790 \tl_const:Nn \c_minus_zero_fp { \s__fp \__fp_chk:w 0 2 \s__fp_exact ; }
```

`\c_minus_inf_fp`

```
10791 \tl_const:Nn \c_inf_fp { \s__fp \__fp_chk:w 2 0 \s__fp_exact ; }
```

`\c_nan_fp`

```
10792 \tl_const:Nn \c_minus_inf_fp { \s__fp \__fp_chk:w 2 2 \s__fp_exact ; }
```

```
10793 \tl_const:Nn \c_nan_fp { \s__fp \__fp_chk:w 3 1 \s__fp_exact ; }
```

(End definition for `\c_zero_fp` and others. These variables are documented on page 182.)

$\backslash c\_fp\_prec\_int$ $\backslash c\_fp\_half\_prec\_int$ $\backslash c\_fp\_block\_int$	<p>The number of digits of floating points.</p> <pre> 10794 \int_const:Nn \c_fp_prec_int { 16 } 10795 \int_const:Nn \c_fp_half_prec_int { 8 } 10796 \int_const:Nn \c_fp_block_int { 4 } </pre> <p>(End definition for <math>\backslash c\_fp\_prec\_int</math>, <math>\backslash c\_fp\_half\_prec\_int</math>, and <math>\backslash c\_fp\_block\_int</math>.)</p>
$\backslash c\_fp\_myriad\_int$	<p>Blocks have 4 digits so this integer is useful.</p> <pre> 10797 \int_const:Nn \c_fp_myriad_int { 10000 } </pre> <p>(End definition for <math>\backslash c\_fp\_myriad\_int</math>.)</p>
$\backslash c\_fp\_minus\_min\_exponent\_int$ $\backslash c\_fp\_max\_exponent\_int$	<p>Normal floating point numbers have an exponent between <math>- \text{minus\_min\_exponent}</math> and <math>\text{max\_exponent}</math> inclusive. Larger numbers are rounded to <math>\pm\infty</math>. Smaller numbers are rounded to <math>\pm 0</math>. It would be more natural to define a <math>\text{min\_exponent}</math> with the opposite sign but that would waste one T<sub>E</sub>X count.</p> <pre> 10798 \int_const:Nn \c_fp_minus_min_exponent_int { 10000 } 10799 \int_const:Nn \c_fp_max_exponent_int { 10000 } </pre> <p>(End definition for <math>\backslash c\_fp\_minus\_min\_exponent\_int</math> and <math>\backslash c\_fp\_max\_exponent\_int</math>.)</p>
$\backslash c\_fp\_max\_exp\_exponent\_int$	<p>If a number's exponent is larger than that, its exponential overflows/underflows.</p> <pre> 10800 \int_const:Nn \c_fp_max_exp_exponent_int { 5 } </pre> <p>(End definition for <math>\backslash c\_fp\_max\_exp\_exponent\_int</math>.)</p>
$\backslash c\_fp\_overflowing\_fp$	<p>A floating point number that is bigger than all normal floating point numbers. This replaces infinities when converting to formats that do not support infinities.</p> <pre> 10801 \tl_const:Nx \c_fp_overflowing_fp 10802 { 10803   \s_fp \_fp_chk:w 1 0 10804   { \int_eval:n { \c_fp_max_exponent_int + 1 } } 10805   {1000} {0000} {0000} {0000} ; 10806 } </pre> <p>(End definition for <math>\backslash c\_fp\_overflowing\_fp</math>.)</p>
$\backslash\_fp\_zero\_fp:N$ $\backslash\_fp\_inf\_fp:N$	<p>In case of overflow or underflow, we have to output a zero or infinity with a given sign.</p> <pre> 10807 \cs_new:Npn \_fp_zero_fp:N #1 10808 { \s_fp \_fp_chk:w 0 #1 \s_fp_underflow ; } 10809 \cs_new:Npn \_fp_inf_fp:N #1 10810 { \s_fp \_fp_chk:w 2 #1 \s_fp_overflow ; } </pre> <p>(End definition for <math>\backslash\_fp\_zero\_fp:N</math> and <math>\backslash\_fp\_inf\_fp:N</math>.)</p>
$\backslash\_fp\_exponent:w$	<p>For normal numbers, the function expands to the exponent, otherwise to 0. This is used in l3str-format.</p> <pre> 10811 \cs_new:Npn \_fp_exponent:w \s_fp \_fp_chk:w #1 10812 { 10813   \if_meaning:w 1 #1 10814     \exp_after:wN \_fp_use_ii_until_s:nnw 10815   \else: 10816     \exp_after:wN \_fp_use_i_until_s:nw 10817     \exp_after:wN 0 10818   \fi: 10819 } </pre>



(End definition for `\_fp_exponent:w`.)

`\_fp_neg_sign:N` When appearing in an integer expression or after `\_int_value:w`, this expands to the sign opposite to `#1`, namely 0 (positive) is turned to 2 (negative), 1 (nan) to 1, and 2 to 0.

```
10820 \cs_new:Npn \_fp_neg_sign:N #1
10821 { \_int_eval:w 2 - #1 \_int_eval_end: }
```

(End definition for `\_fp_neg_sign:N`.)

## 21.4 Overflow, underflow, and exact zero

`\_fp_sanitize:Nw` `\_fp_sanitize:wN` `\_fp_sanitize_zero:w` Expects the sign and the exponent in some order, then the significand (which we don't touch). Outputs the corresponding floating point number, possibly underflowed to  $\pm 0$  or overflowed to  $\pm\infty$ . The functions `\_fp_underflow:w` and `\_fp_overflow:w` are defined in `l3fp-traps`.

```
10822 \cs_new:Npn \_fp_sanitize:Nw #1 #2;
10823 {
10824   \if_case:w
10825     \if_int_compare:w #2 > \c_fp_max_exponent_int 1 ~ \else:
10826     \if_int_compare:w #2 < - \c_fp_minus_min_exponent_int 2 ~ \else:
10827     \if_meaning:w 1 #1 3 ~ \fi: \fi: \fi: 0 ~
10828   \or: \exp_after:wN \_fp_overflow:w
10829   \or: \exp_after:wN \_fp_underflow:w
10830   \or: \exp_after:wN \_fp_sanitize_zero:w
10831   \fi:
10832   \s_fp \_fp_chk:w 1 #1 {#2}
10833 }
10834 \cs_new:Npn \_fp_sanitize:wN #1; #2 { \_fp_sanitize:Nw #2 #1; }
10835 \cs_new:Npn \_fp_sanitize_zero:w \s_fp \_fp_chk:w #1 #2 #3;
10836 { \c_zero_fp }
```

(End definition for `\_fp_sanitize:Nw`, `\_fp_sanitize:wN`, and `\_fp_sanitize_zero:w`.)

## 21.5 Expanding after a floating point number

`\_fp_exp_after_o:w` `\_fp_exp_after_f:nw` Places *tokens* (empty in the case of `\_fp_exp_after_o:w`) between the *floating point* and the *more tokens*, then hits those tokens with either o-expansion (one `\exp_after:wN`) or f-expansion, and leaves the floating point number unchanged.

We first distinguish normal floating points, which have a significand, from the much simpler special floating points.

```
10837 \cs_new:Npn \_fp_exp_after_o:w \s_fp \_fp_chk:w #1
10838 {
10839   \if_meaning:w 1 #1
10840     \exp_after:wN \_fp_exp_after_normal:nNNw
10841   \else:
10842     \exp_after:wN \_fp_exp_after_special:nNNw
10843   \fi:
10844   { }
10845   #1
10846 }
10847 \cs_new:Npn \_fp_exp_after_f:nw #1 \s_fp \_fp_chk:w #2
10848 {
```

```

10849     \if_meaning:w 1 #2
10850         \exp_after:wN \__fp_exp_after_normal:nNNw
10851     \else:
10852         \exp_after:wN \__fp_exp_after_special:nNNw
10853     \fi:
10854     { \exp:w \exp_end_continue_f:w #1 }
10855     #2
10856 }

```

(End definition for \\_\_fp\_exp\_after\_o:w and \\_\_fp\_exp\_after\_f:nw.)

\\_\_fp\_exp\_after\_special:nNNw Special floating point numbers are easy to jump over since they contain few tokens.

```

10857 \cs_new:Npn \__fp_exp_after_special:nNNw #1#2#3#4;
10858 {
10859     \exp_after:wN \s__fp
10860     \exp_after:wN \__fp_chk:w
10861     \exp_after:wN #2
10862     \exp_after:wN #3
10863     \exp_after:wN #4
10864     \exp_after:wN ;
10865     #1
10866 }

```

(End definition for \\_\_fp\_exp\_after\_special:nNNw.)

\\_\_fp\_exp\_after\_normal:nNNw For normal floating point numbers, life is slightly harder, since we have many tokens to jump over. Here it would be slightly better if the digits were not braced but instead were delimited arguments (for instance delimited by ,). That may be changed some day.

```

10867 \cs_new:Npn \__fp_exp_after_normal:nNNw #1 1 #2 #3 #4#5#6#7;
10868 {
10869     \exp_after:wN \__fp_exp_after_normal:Nwwwww
10870     \exp_after:wN #2
10871     \__int_value:w #3 \exp_after:wN ;
10872     \__int_value:w 1 #4 \exp_after:wN ;
10873     \__int_value:w 1 #5 \exp_after:wN ;
10874     \__int_value:w 1 #6 \exp_after:wN ;
10875     \__int_value:w 1 #7 \exp_after:wN ; #1
10876 }
10877 \cs_new:Npn \__fp_exp_after_normal:Nwwwww
10878     #1 #2; 1 #3 ; 1 #4 ; 1 #5 ; 1 #6 ;
10879     { \s__fp \__fp_chk:w 1 #1 {#2} {#3} {#4} {#5} {#6} ; }

```

(End definition for \\_\_fp\_exp\_after\_normal:nNNw.)

\\_\_fp\_exp\_after\_array\_f:w  
\\_\_fp\_exp\_after\_stop\_f:nw

```

10880 \cs_new:Npn \__fp_exp_after_array_f:w #1
10881 {
10882     \cs:w \__fp_exp_after \__fp_type_from_scan:N #1 _f:nw \cs_end:
10883     { \__fp_exp_after_array_f:w }
10884     #1
10885 }
10886 \cs_new_eq:NN \__fp_exp_after_stop_f:nw \use_none:nn

```

(End definition for \\_\_fp\_exp\_after\_array\_f:w and \\_\_fp\_exp\_after\_stop\_f:nw.)

## 21.6 Packing digits

When a positive integer `#1` is known to be less than  $10^8$ , the following trick splits it into two blocks of 4 digits, padding with zeros on the left.

```
\cs_new:Npn \pack:NNNNNw #1 #2#3#4#5 #6; { {#2#3#4#5} {#6} }
\exp_after:wN \pack:NNNNNw
  \__int_value:w \__int_eval:w 1 0000 0000 + #1 ;
```

The idea is that adding  $10^8$  to the number ensures that it has exactly 9 digits, and can then easily find which digits correspond to what position in the number. Of course, this can be modified for any number of digits less or equal to 9 (we are limited by `TeX`'s integers). This method is very heavily relied upon in `l3fp-basics`.

More specifically, the auxiliary inserts `+ #1#2#3#4#5 ; {#6}`, which allows us to compute several blocks of 4 digits in a nested manner, performing carries on the fly. Say we want to compute  $12345 \times 66778899$ . With simplified names, we would do

```
\exp_after:wN \post_processing:w
\__int_value:w \__int_eval:w - 5 0000
  \exp_after:wN \pack:NNNNNw
    \__int_value:w \__int_eval:w 4 9995 0000
      + 12345 * 6677
    \exp_after:wN \pack:NNNNNw
      \__int_value:w \__int_eval:w 5 0000 0000
        + 12345 * 8899 ;
```

The `\exp_after:wN` triggers `\__int_value:w \__int_eval:w`, which starts a first computation, whose initial value is  $-5\,0000$  (the “leading shift”). In that computation appears an `\exp_after:wN`, which triggers the nested computation `\__int_value:w \__int_eval:w` with starting value  $4\,9995\,0000$  (the “middle shift”). That, in turn, expands `\exp_after:wN` which triggers the third computation. The third computation's value is  $5\,0000\,0000 + 12345 \times 8899$ , which has 9 digits. Adding  $5 \cdot 10^8$  to the product allowed us to know how many digits to expect as long as the numbers to multiply are not too big; it also works to some extent with negative results. The `pack` function puts the last 4 of those 9 digits into a brace group, moves the semi-colon delimiter, and inserts a `+`, which combines the carry with the previous computation. The shifts nicely combine into  $5\,0000\,0000/10^4 + 4\,9995\,0000 = 5\,0000\,0000$ . As long as the operands are in some range, the result of this second computation has 9 digits. The corresponding `pack` function, expanded after the result is computed, braces the last 4 digits, and leaves `+ {5 digits}` for the initial computation. The “leading shift” cancels the combination of the other shifts, and the `\post_processing:w` takes care of packing the last few digits.

Admittedly, this is quite intricate. It is probably the key in making `l3fp` as fast as other pure `TeX` floating point units despite its increased precision. In fact, this is used so much that we provide different sets of packing functions and shifts, depending on ranges of input.

This set of shifts allows for computations involving results in the range  $[-4 \cdot 10^8, 5 \cdot 10^8 - 1]$ . Shifted values all have exactly 9 digits.

```
\__fp_pack:NNNNNw
\c_fp_trailing_shift_int
\c_fp_middle_shift_int
\c_fp_leading_shift_int
10887 \int_const:Nn \c_fp_leading_shift_int { - 5 0000 }
10888 \int_const:Nn \c_fp_middle_shift_int { 5 0000 * 9999 }
10889 \int_const:Nn \c_fp_trailing_shift_int { 5 0000 * 10000 }
10890 \cs_new:Npn \__fp_pack:NNNNNw #1 #2#3#4#5 #6; { + #1#2#3#4#5 ; {#6} }
```

(End definition for `\_fp_pack:NNNNNw` and others.)

`\_fp_pack_big:NNNNNw` This set of shifts allows for computations involving results in the range  $[-5 \cdot 10^8, 6 \cdot 10^8 - 1]$  (actually a bit more). Shifted values all have exactly 10 digits. Note that the upper bound is due to T<sub>E</sub>X's limit of  $2^{31} - 1$  on integers. The shifts are chosen to be roughly the mid-point of  $10^9$  and  $2^{31}$ , the two bounds on 10-digit integers in T<sub>E</sub>X.

```
10891 \int_const:Nn \c_fp_big_leading_shift_int { - 15 2374 }
10892 \int_const:Nn \c_fp_big_middle_shift_int { 15 2374 * 9999 }
10893 \int_const:Nn \c_fp_big_trailing_shift_int { 15 2374 * 10000 }
10894 \cs_new:Npn \_fp_pack_big:NNNNNw #1#2 #3#4#5#6 #7;
10895 { + #1#2#3#4#5#6 ; {#7} }
```

(End definition for `\_fp_pack_big:NNNNNw` and others.)

`\_fp_pack_Bigg:NNNNNw` This set of shifts allows for computations with results in the range  $[-1 \cdot 10^9, 147483647]$ ; the end-point is  $2^{31} - 1 - 2 \cdot 10^9 \simeq 1.47 \cdot 10^8$ . Shifted values all have exactly 10 digits.

```
10896 \int_const:Nn \c_fp_Bigg_leading_shift_int { - 20 0000 }
10897 \int_const:Nn \c_fp_Bigg_middle_shift_int { 20 0000 * 9999 }
10898 \int_const:Nn \c_fp_Bigg_trailing_shift_int { 20 0000 * 10000 }
10899 \cs_new:Npn \_fp_pack_Bigg:NNNNNw #1#2 #3#4#5#6 #7;
10900 { + #1#2#3#4#5#6 ; {#7} }
```

(End definition for `\_fp_pack_Bigg:NNNNNw` and others.)

`\_fp_pack_twice_four:wNNNNNNNN` Grabs two sets of 4 digits and places them before the semi-colon delimiter. Putting several copies of this function before a semicolon packs more digits since each takes the digits packed by the others in its first argument.

```
10901 \cs_new:Npn \_fp_pack_twice_four:wNNNNNNNN #1; #2#3#4#5 #6#7#8#9
10902 { #1 {#2#3#4#5} {#6#7#8#9} ; }
```

(End definition for `\_fp_pack_twice_four:wNNNNNNNN`.)

`\_fp_pack_eight:wNNNNNNNN` Grabs one set of 8 digits and places them before the semi-colon delimiter as a single group. Putting several copies of this function before a semicolon packs more digits since each takes the digits packed by the others in its first argument.

```
10903 \cs_new:Npn \_fp_pack_eight:wNNNNNNNN #1; #2#3#4#5 #6#7#8#9
10904 { #1 {#2#3#4#5#6#7#8#9} ; }
```

(End definition for `\_fp_pack_eight:wNNNNNNNN`.)

`\_fp_basics_pack_low:NNNNNw` Addition and multiplication of significands are done in two steps: first compute a (more or less) exact result, then round and pack digits in the final (braced) form. These functions take care of the packing, with special attention given to the case where rounding has caused a carry. Since rounding can only shift the final digit by 1, a carry always produces an exact power of 10. Thus, `\_fp_basics_pack_high_carry:w` is always followed by four times `{0000}`.

This is used in l3fp-basics and l3fp-extended.

```
10905 \cs_new:Npn \_fp_basics_pack_low:NNNNNw #1 #2#3#4#5 #6;
10906 { + #1 - 1 ; {#2#3#4#5} {#6} ; }
10907 \cs_new:Npn \_fp_basics_pack_high:NNNNNw #1 #2#3#4#5 #6;
10908 {
10909   \if_meaning:w 2 #1
10910     \_fp_basics_pack_high_carry:w
10911   \fi:
```

```
10912 ; {#2#3#4#5} {#6}
```

```
10913 }
```

```
10914 \cs_new:Npn \__fp_basics_pack_high_carry:w \fi: ; #1
```

```
10915 { \fi: + 1 ; {1000} }
```

(End definition for `\__fp_basics_pack_low:NNNNw`, `\__fp_basics_pack_high:NNNNw`, and `\__fp_basics_pack_high_carry:w`.)

This is used in `l3fp-basics` for additions and divisions. Their syntax is confusing, hence the name.

```
10916 \cs_new:Npn \__fp_basics_pack_weird_low:NNNNw #1 #2#3#4 #5;
```

```
10917 {
```

```
10918   \if_meaning:w 2 #1
```

```
10919     + 1
```

```
10920   \fi:
```

```
10921   \__int_eval_end:
```

```
10922   #2#3#4; {#5} ;
```

```
10923 }
```

```
10924 \cs_new:Npn \__fp_basics_pack_weird_high:NNNNNNNw
```

```
10925   1 #1#2#3#4 #5#6#7#8 #9; { ; {#1#2#3#4} {#5#6#7#8} {#9} }
```

(End definition for `\__fp_basics_pack_weird_low:NNNNw` and `\__fp_basics_pack_weird_high:NNNNNNNw`.)

## 21.7 Decimate (dividing by a power of 10)

```
\__fp_decimate:nNnnnn
```

Each  $\langle X_i \rangle$  consists in 4 digits exactly, and  $1000 \leq \langle X_1 \rangle < 9999$ . The first argument determines by how much we shift the digits.  $\langle f_1 \rangle$  is called as follows: where  $0 \leq \langle X'_i \rangle < 10^8 - 1$  are 8 digit integers, forming the truncation of our number. In other words,

$$\left( \sum_{i=1}^4 \langle X_i \rangle \cdot 10^{-4i} \cdot 10^{-\langle shift \rangle} - \langle X'_1 \rangle \cdot 10^{-8} + \langle X'_2 \rangle \cdot 10^{-16} \right) \in [0, 10^{-16}).$$

To round properly later, we need to remember some information about the difference. The  $\langle rounding \rangle$  digit is 0 if and only if the difference is exactly 0, and 5 if and only if the difference is exactly  $0.5 \cdot 10^{-16}$ . Otherwise, it is the (non-0, non-5) digit closest to  $10^{17}$  times the difference. In particular, if the shift is 17 or more, all the digits are dropped,  $\langle rounding \rangle$  is 1 (not 0), and  $\langle X'_1 \rangle$  and  $\langle X'_2 \rangle$  are both zero.

If the shift is 1, the  $\langle rounding \rangle$  digit is simply the only digit that was pushed out of the brace groups (this is important for subtraction). It would be more natural for the  $\langle rounding \rangle$  digit to be placed after the  $\langle X'_i \rangle$ , but the choice we make involves less reshuffling.

Note that this function treats negative  $\langle shift \rangle$  as 0.

```
10926 \cs_new:Npn \__fp_decimate:nNnnnn #1
```

```
10927 {
```

```
10928   \cs:w
```

```
10929     __fp_decimate_
```

```
10930     \if_int_compare:w \__int_eval:w #1 > \c__fp_prec_int
```

```
10931       tiny
```

```
10932     \else:
```

```
10933       \__int_to_roman:w \__int_eval:w #1
```

```
10934     \fi:
```

```
10935     :Nnnnn
```

```
10936   \cs_end:
```

```
10937 }
```

Each of the auxiliaries see the function  $\langle f_1 \rangle$ , followed by 4 blocks of 4 digits.

(End definition for `\_fp\_decimate:nNnnnn`.)

If the  $\langle shift \rangle$  is zero, or too big, life is very easy.

```
\_fp\_decimate_:Nnnnn
\_fp\_decimate\_tiny:Nnnnn
10938 \cs_new:Npn \_fp\_decimate_:Nnnnn #1 #2#3#4#5
10939 { #1 0 {#2#3} {#4#5} ; }
10940 \cs_new:Npn \_fp\_decimate\_tiny:Nnnnn #1 #2#3#4#5
10941 { #1 1 { 0000 0000 } { 0000 0000 } 0 #2#3#4#5 ; }
```

(End definition for `\_fp\_decimate_:Nnnnn` and `\_fp\_decimate\_tiny:Nnnnn`.)

Shifting happens in two steps: compute the  $\langle rounding \rangle$  digit, and repack digits into two blocks of 8. The sixteen functions are very similar, and defined through `\_fp\_tmp:w`. The arguments are as follows: #1 indicates which function is being defined; after one step of expansion, #2 yields the “extra digits” which are then converted by `\_fp\_round\_digit:Nw` to the  $\langle rounding \rangle$  digit (note the + separating blocks of digits to avoid overflowing TeX’s integers). This triggers the f-expansion of `\_fp\_decimate\_pack:nnnnnnnnnw`,<sup>10</sup> responsible for building two blocks of 8 digits, and removing the rest. For this to work, #3 alternates between braced and unbraced blocks of 4 digits, in such a way that the 5 first and 5 next token groups yield the correct blocks of 8 digits.

```
\_fp\_decimate\_auxi:Nnnnn
\_fp\_decimate\_auxii:Nnnnn
\_fp\_decimate\_auxiii:Nnnnn
\_fp\_decimate\_auxiv:Nnnnn
\_fp\_decimate\_auxv:Nnnnn
\_fp\_decimate\_auxvi:Nnnnn
\_fp\_decimate\_auxvii:Nnnnn
\_fp\_decimate\_auxviii:Nnnnn
\_fp\_decimate\_auxix:Nnnnn
\_fp\_decimate\_auxx:Nnnnn
\_fp\_decimate\_auxxi:Nnnnn
\_fp\_decimate\_auxxii:Nnnnn
\_fp\_decimate\_auxxiii:Nnnnn
\_fp\_decimate\_auxxiv:Nnnnn
\_fp\_decimate\_auxxv:Nnnnn
\_fp\_decimate\_auxxvi:Nnnnn
10942 \cs_new:Npn \_fp\_tmp:w #1 #2 #3
10943 {
10944   \cs_new:cpn { \_fp\_decimate_ #1 :Nnnnn } ##1 ##2##3##4##5
10945   {
10946     \exp_after:wN ##1
10947     \_int_value:w
10948     \exp_after:wN \_fp\_round\_digit:Nw #2 ;
10949     \_fp\_decimate\_pack:nnnnnnnnnw #3 ;
10950   }
10951 }
10952 \_fp\_tmp:w {i} {\use\_none:nnn #50}{ 0{#2}#3{#4}#5 }
10953 \_fp\_tmp:w {ii} {\use\_none:nn #5 }{ 00{#2}#3{#4}#5 }
10954 \_fp\_tmp:w {iii} {\use\_none:n #5 }{ 000{#2}#3{#4}#5 }
10955 \_fp\_tmp:w {iv} { #5 }{ {0000}#2{#3}#4 #5 }
10956 \_fp\_tmp:w {v} {\use\_none:nnn #4#5 }{ 0{0000}#2{#3}#4 #5 }
10957 \_fp\_tmp:w {vi} {\use\_none:nn #4#5 }{ 00{0000}#2{#3}#4 #5 }
10958 \_fp\_tmp:w {vii} {\use\_none:n #4#5 }{ 000{0000}#2{#3}#4 #5 }
10959 \_fp\_tmp:w {viii}{ #4#5 }{ {0000}0000{#2}#3 #4 #5 }
10960 \_fp\_tmp:w {ix} {\use\_none:nnn #3#4+#5}{ 0{0000}0000{#2}#3 #4 #5 }
10961 \_fp\_tmp:w {x} {\use\_none:nn #3#4+#5}{ 00{0000}0000{#2}#3 #4 #5 }
10962 \_fp\_tmp:w {xi} {\use\_none:n #3#4+#5}{ 000{0000}0000{#2}#3 #4 #5 }
10963 \_fp\_tmp:w {xii} { #3#4+#5}{ {0000}0000{0000}#2 #3 #4 #5 }
10964 \_fp\_tmp:w {xiii}{\use\_none:nnn#2#3+#4#5}{ 0{0000}0000{0000}#2 #3 #4 #5 }
10965 \_fp\_tmp:w {xiv} {\use\_none:nn #2#3+#4#5}{ 00{0000}0000{0000}#2 #3 #4 #5 }
10966 \_fp\_tmp:w {xv} {\use\_none:n #2#3+#4#5}{ 000{0000}0000{0000}#2 #3 #4 #5 }
10967 \_fp\_tmp:w {xvi} { #2#3+#4#5}{ {0000}0000{0000}0000 #2 #3 #4 #5 }
```

(End definition for `\_fp\_decimate\_auxi:Nnnnn` and others.)

The computation of the  $\langle rounding \rangle$  digit leaves an unfinished `\_int\_value:w`, which expands the following functions. This allows us to repack nicely the digits we keep.

```
\_fp\_decimate\_pack:nnnnnnnnnw
```

<sup>10</sup>No, the argument spec is not a mistake: the function calls an auxiliary to do half of the job.

Those digits come as an alternation of unbraced and braced blocks of 4 digits, such that the first 5 groups of token consist in 4 single digits, and one brace group (in some order), and the next 5 have the same structure. This is followed by some digits and a semicolon.

```

10968 \cs_new:Npn \__fp_decimate_pack:nnnnnnnnnw #1#2#3#4#5
10969 { \__fp_decimate_pack:nnnnnw { #1#2#3#4#5 } }
10970 \cs_new:Npn \__fp_decimate_pack:nnnnnw #1 #2#3#4#5#6
10971 { {#1} {#2#3#4#5#6} }

```

(End definition for `\__fp_decimate_pack:nnnnnnnnnw`.)

## 21.8 Functions for use within primitive conditional branches

The functions described in this section are not pretty and can easily be misused. When correctly used, each of them removes one `\fi:` as part of its parameter text, and puts one back as part of its replacement text.

Many computation functions in `l3fp` must perform tests on the type of floating points that they receive. This is often done in an `\if_case:w` statement or another conditional statement, and only a few cases lead to actual computations: most of the special cases are treated using a few standard functions which we define now. A typical use context for those functions would be In this example, the case 0 returns the floating point  $\langle fp\ var \rangle$ , expanding once after that floating point. Case 1 does  $\langle some\ computation \rangle$  using the  $\langle floating\ point \rangle$  (presumably compute the operation requested by the user in that non-trivial case). Case 2 returns the  $\langle floating\ point \rangle$  without modifying it, removing the  $\langle junk \rangle$  and expanding once after. Case 3 closes the conditional, removes the  $\langle junk \rangle$  and the  $\langle floating\ point \rangle$ , and expands  $\langle something \rangle$  next. In other cases, the “ $\langle junk \rangle$ ” is expanded, performing some other operation on the  $\langle floating\ point \rangle$ . We provide similar functions with two trailing  $\langle floating\ points \rangle$ .

`\__fp_case_use:nw` This function ends a TeX conditional, removes junk until the next floating point, and places its first argument before that floating point, to perform some operation on the floating point.

```

10972 \cs_new:Npn \__fp_case_use:nw #1#2 \fi: #3 \s__fp { \fi: #1 \s__fp }

```

(End definition for `\__fp_case_use:nw`.)

`\__fp_case_return:nw` This function ends a TeX conditional, removes junk and a floating point, and places its first argument in the input stream. A quirk is that we don’t define this function requiring a floating point to follow, simply anything ending in a semicolon. This, in turn, means that the  $\langle junk \rangle$  may not contain semicolons.

```

10973 \cs_new:Npn \__fp_case_return:nw #1#2 \fi: #3 ; { \fi: #1 }

```

(End definition for `\__fp_case_return:nw`.)

`\__fp_case_return_o:Nw` This function ends a TeX conditional, removes junk and a floating point, and returns its first argument (an  $\langle fp\ var \rangle$ ) then expands once after it.

```

10974 \cs_new:Npn \__fp_case_return_o:Nw #1#2 \fi: #3 \s__fp #4 ;
10975 { \fi: \exp_after:wN #1 }

```

(End definition for `\__fp_case_return_o:Nw`.)

`\_fp_case_return_same_o:w` This function ends a TeX conditional, removes junk, and returns the following floating point, expanding once after it.

```
10976 \cs_new:Npn \_fp_case_return_same_o:w #1 \fi: #2 \s__fp
10977 { \fi: \_fp_exp_after_o:w \s__fp }
```

(End definition for `\_fp_case_return_same_o:w`.)

`\_fp_case_return_o:Nww` Same as `\_fp_case_return_o:Nw` but with two trailing floating points.

```
10978 \cs_new:Npn \_fp_case_return_o:Nww #1#2 \fi: #3 \s__fp #4 ; #5 ;
10979 { \fi: \exp_after:wN #1 }
```

(End definition for `\_fp_case_return_o:Nww`.)

`\_fp_case_return_i_o:ww` Similar to `\_fp_case_return_same_o:w`, but this returns the first or second of two trailing floating point numbers, expanding once after the result.

```
\_fp_case_return_ii_o:ww
10980 \cs_new:Npn \_fp_case_return_i_o:ww #1 \fi: #2 \s__fp #3 ; \s__fp #4 ;
10981 { \fi: \_fp_exp_after_o:w \s__fp #3 ; }
10982 \cs_new:Npn \_fp_case_return_ii_o:ww #1 \fi: #2 \s__fp #3 ;
10983 { \fi: \_fp_exp_after_o:w }
```

(End definition for `\_fp_case_return_i_o:ww` and `\_fp_case_return_ii_o:ww`.)

## 21.9 Integer floating points

`\_fp_int_p:w` Tests if the floating point argument is an integer. For normal floating point numbers, `\_fp_int:wTF` this holds if the rounding digit resulting from `\_fp_decimate:nNnnnn` is 0.

```
10984 \prg_new_conditional:Npnn \_fp_int:w \s__fp \_fp_chk:w #1 #2 #3 #4;
10985 { TF , T , F , p }
10986 {
10987   \if_case:w #1 \exp_stop_f:
10988     \prg_return_true:
10989   \or:
10990     \if_charcode:w 0
10991       \_fp_decimate:nNnnnn { \c__fp_prec_int - #3 }
10992       \_fp_use_i_until_s:nw #4
10993       \prg_return_true:
10994     \else:
10995       \prg_return_false:
10996     \fi:
10997   \else: \prg_return_false:
10998   \fi:
10999 }
```

(End definition for `\_fp_int:wTF`.)

## 21.10 Small integer floating points

`\_fp_small_int:wTF` Tests if the floating point argument is an integer or  $\pm\infty$ . If so, it is converted to an integer in the range  $[-10^8, 10^8]$  and fed as a braced argument to the *⟨true code⟩*. Otherwise, the *⟨false code⟩* is performed.

First filter special cases: zeros and infinities are integers, `nan` is not. For normal numbers, `decimate`. If the rounding digit is not 0 run the *⟨false code⟩*. If it is, then the integer is `#2 #3`; use `#3` if `#2` vanishes and otherwise  $10^8$ .



```

11000 \cs_new:Npn \__fp_small_int:wTF \s__fp \__fp_chk:w #1#2
11001 {
11002   \if_case:w #1 \exp_stop_f:
11003     \__fp_case_return:nw { \__fp_small_int_true:wTF 0 ; }
11004   \or: \exp_after:wN \__fp_small_int_normal:NnwTF
11005   \or:
11006     \__fp_case_return:nw
11007     {
11008       \exp_after:wN \__fp_small_int_true:wTF \__int_value:w
11009       \if_meaning:w 2 #2 - \fi: 1 0000 0000 ;
11010     }
11011   \else: \__fp_case_return:nw \use_ii:nn
11012   \fi:
11013   #2
11014 }
11015 \cs_new:Npn \__fp_small_int_true:wTF #1; #2#3 { #2 {#1} }
11016 \cs_new:Npn \__fp_small_int_normal:NnwTF #1#2#3;
11017 {
11018   \__fp_decimate:nNnnnn { \c__fp_prec_int - #2 }
11019   \__fp_small_int_test:NnnwNw
11020   #3 #1
11021 }
11022 \cs_new:Npn \__fp_small_int_test:NnnwNw #1#2#3#4; #5
11023 {
11024   \if_meaning:w 0 #1
11025     \exp_after:wN \__fp_small_int_true:wTF
11026     \__int_value:w \if_meaning:w 2 #5 - \fi:
11027     \if_int_compare:w #2 > 0 \exp_stop_f:
11028     1 0000 0000
11029   \else:
11030     #3
11031   \fi:
11032   \exp_after:wN ;
11033   \else:
11034     \exp_after:wN \use_ii:nn
11035   \fi:
11036 }

```

(End definition for \\_\_fp\_small\_int:wTF and others.)

## 21.11 Length of a floating point array

`\__fp_array_count:n` Count the number of items in an array of floating points. The technique is very similar to `\tl_count:n`, but with the loop built-in. Checking for the end of the loop is done with the `\use_none:n #1` construction.

```

11037 \cs_new:Npn \__fp_array_count:n #1
11038 {
11039   \__int_value:w \__int_eval:w 0
11040   \__fp_array_count_loop:Nw #1 { ? \__prg_break: } ;
11041   \__prg_break_point:
11042   \__int_eval_end:
11043 }
11044 \cs_new:Npn \__fp_array_count_loop:Nw #1#2;
11045 { \use_none:n #1 + 1 \__fp_array_count_loop:Nw }

```

(End definition for `\_fp_array_count:n` and `\_fp_array_count_loop:Nw`.)

## 21.12 x-like expansion expandably

`\_fp_expand:n`  
`\_fp_expand_loop:nwnN`

This expandable function behaves in a way somewhat similar to `\use:x`, but much less robust. The argument is `f`-expanded, then the leading item (often a single character token) is moved to a storage area after `\s\_fp\_mark`, and `f`-expansion is applied again, repeating until the argument is empty. The result built one piece at a time is then inserted in the input stream. Note that spaces are ignored by this procedure, unless surrounded with braces. Multiple tokens which do not need expansion can be inserted within braces.

```

11046 \cs_new:Npn \_fp_expand:n #1
11047 {
11048   \_fp_expand_loop:nwnN { }
11049   #1 \prg_do_nothing:
11050   \s\_fp\_mark { } \_fp_expand_loop:nwnN
11051   \s\_fp\_mark { } \_fp_use_i_until_s:nw ;
11052 }
11053 \cs_new:Npn \_fp_expand_loop:nwnN #1#2 \s\_fp\_mark #3 #4
11054 {
11055   \exp_after:wN #4 \exp:w \exp_end_continue_f:w
11056   #2
11057   \s\_fp\_mark { #3 #1 } #4
11058 }

```

(End definition for `\_fp_expand:n` and `\_fp_expand_loop:nwnN`.)

## 21.13 Messages

Using a floating point directly is an error.

```

11059 \_msg_kernel_new:nnnn { kernel } { misused-fp }
11060 { A~floating~point~with~value~'#1'~was~misused. }
11061 {
11062   To~obtain~the~value~of~a~floating~point~variable,~use~
11063   '\token_to_str:N \fp_to_decimal:N',~
11064   '\token_to_str:N \fp_to_scientific:N',~or~other~
11065   conversion~functions.
11066 }
11067 </initex | package>

```

## 22 l3fp-traps Implementation

```

11068 (*initex | package)
11069 <@@=fp>

```

Exceptions should be accessed by an `n`-type argument, among

- `invalid_operation`
- `division_by_zero`
- `overflow`

- underflow
- inexact (actually never used).

## 22.1 Flags

```

flag_fp_invalid_operation  Flags to denote exceptions.
flag_fp_division_by_zero  11070 \flag_new:n { fp_invalid_operation }
flag_fp_overflow          11071 \flag_new:n { fp_division_by_zero }
flag_fp_underflow         11072 \flag_new:n { fp_overflow }
                          11073 \flag_new:n { fp_underflow }

```

(End definition for flag fp\_invalid\_operation and others. These variables are documented on page 184.)

## 22.2 Traps

Exceptions can be trapped to obtain custom behaviour. When an invalid operation or a division by zero is trapped, the trap receives as arguments the result as an N-type floating point number, the function name (multiple letters for prefix operations, or a single symbol for infix operations), and the operand(s). When an overflow or underflow is trapped, the trap receives the resulting overly large or small floating point number if it is not too big, otherwise it receives  $+\infty$ . Currently, the inexact exception is entirely ignored.

The behaviour when an exception occurs is controlled by the definitions of the functions

- \\_\_fp\_invalid\_operation:nnw,
- \\_\_fp\_invalid\_operation\_o:Nww,
- \\_\_fp\_invalid\_operation\_tl\_o:ff,
- \\_\_fp\_division\_by\_zero\_o:Nnw,
- \\_\_fp\_division\_by\_zero\_o:NNww,
- \\_\_fp\_overflow:w,
- \\_\_fp\_underflow:w.

Rather than changing them directly, we provide a user interface as \fp\_trap:nn {*<exception>*} {*<way of trapping>*}, where the *<way of trapping>* is one of **error**, **flag**, or **none**.

We also provide \\_\_fp\_invalid\_operation\_o:nw, defined in terms of \\_\_fp\_invalid\_operation:nnw.

```

\fp_trap:nn
11074 \cs_new_protected:Npn \fp_trap:nn #1#2
11075 {
11076   \cs_if_exist_use:cF { __fp_trap_#1_set_#2: }
11077   {
11078     \clist_if_in:nnTF
11079     { invalid_operation , division_by_zero , overflow , underflow }
11080     {#1}
11081     {

```

```

11082         \_msg_kernel_error:nxxx { kernel }
11083         { unknown-fpu-trap-type } {#1} {#2}
11084     }
11085     {
11086         \_msg_kernel_error:nxx
11087         { kernel } { unknown-fpu-exception } {#1}
11088     }
11089 }
11090 }

```

(End definition for \fp\_trap:nn. This function is documented on page 184.)

\\_fp\_trap\_invalid\_operation\_set\_error: We provide three types of trapping for invalid operations: either produce an error and raise the relevant flag; or only raise the flag; or don't even raise the flag. In most cases, the function produces as a result its first argument, possibly with post-expansion.

```

\_fp_trap_invalid_operation_set_error:
\_fp_trap_invalid_operation_set_flag:
\_fp_trap_invalid_operation_set_none:
\_fp_trap_invalid_operation_set:N
11091 \cs_new_protected:Npn \_fp_trap_invalid_operation_set_error:
11092 { \_fp_trap_invalid_operation_set:N \prg_do_nothing: }
11093 \cs_new_protected:Npn \_fp_trap_invalid_operation_set_flag:
11094 { \_fp_trap_invalid_operation_set:N \use_none:nnnnn }
11095 \cs_new_protected:Npn \_fp_trap_invalid_operation_set_none:
11096 { \_fp_trap_invalid_operation_set:N \use_none:nnnnnnn }
11097 \cs_new_protected:Npn \_fp_trap_invalid_operation_set:N #1
11098 {
11099     \exp_args:Nno \use:n
11100     { \cs_set:Npn \_fp_invalid_operation:nw ##1##2##3; }
11101     {
11102         #1
11103         \_fp_error:nfn { fp-invalid } {##2} { \fp_to_tl:n { ##3; } } { }
11104         \flag_raise:n { fp_invalid_operation }
11105         ##1
11106     }
11107     \exp_args:Nno \use:n
11108     { \cs_set:Npn \_fp_invalid_operation_o:Nw ##1##2; ##3; }
11109     {
11110         #1
11111         \_fp_error:nfn { fp-invalid-ii }
11112         { \fp_to_tl:n { ##2; } } { \fp_to_tl:n { ##3; } } {##1}
11113         \flag_raise:n { fp_invalid_operation }
11114         \exp_after:wN \c_nan_fp
11115     }
11116     \exp_args:Nno \use:n
11117     { \cs_set:Npn \_fp_invalid_operation_tl_o:ff ##1##2 }
11118     {
11119         #1
11120         \_fp_error:nfn { fp-invalid } {##1} {##2} { }
11121         \flag_raise:n { fp_invalid_operation }
11122         \exp_after:wN \c_nan_fp
11123     }
11124 }

```

(End definition for \\_fp\_trap\_invalid\_operation\_set\_error: and others.)

\\_fp\_trap\_division\_by\_zero\_set\_error: We provide three types of trapping for invalid operations and division by zero: either produce an error and raise the relevant flag; or only raise the flag; or don't even raise the

flag. In all cases, the function must produce a result, namely its first argument,  $\pm\infty$  or NaN.

```

11125 \cs_new_protected:Npn \__fp_trap_division_by_zero_set_error:
11126 { \__fp_trap_division_by_zero_set:N \prg_do_nothing: }
11127 \cs_new_protected:Npn \__fp_trap_division_by_zero_set_flag:
11128 { \__fp_trap_division_by_zero_set:N \use_none:nnnnn }
11129 \cs_new_protected:Npn \__fp_trap_division_by_zero_set_none:
11130 { \__fp_trap_division_by_zero_set:N \use_none:nnnnnnn }
11131 \cs_new_protected:Npn \__fp_trap_division_by_zero_set:N #1
11132 {
11133   \exp_args:Nno \use:n
11134   { \cs_set:Npn \__fp_division_by_zero_o:Nnw ##1##2##3; }
11135   {
11136     #1
11137     \__fp_error:nfn { fp-zero-div } {##2} { \fp_to_tl:n { ##3; } } { }
11138     \flag_raise:n { fp_division_by_zero }
11139     \exp_after:wN ##1
11140   }
11141   \exp_args:Nno \use:n
11142   { \cs_set:Npn \__fp_division_by_zero_o:NNww ##1##2##3; ##4; }
11143   {
11144     #1
11145     \__fp_error:nfn { fp-zero-div-ii }
11146     { \fp_to_tl:n { ##3; } } { \fp_to_tl:n { ##4; } } {##2}
11147     \flag_raise:n { fp_division_by_zero }
11148     \exp_after:wN ##1
11149   }
11150 }

```

(End definition for `\__fp_trap_division_by_zero_set_error:` and others.)

<code>\__fp_trap_overflow_set_error:</code> <code>\__fp_trap_overflow_set_flag:</code> <code>\__fp_trap_overflow_set_none:</code> <code>\__fp_trap_overflow_set:N</code> <code>\__fp_trap_underflow_set_error:</code> <code>\__fp_trap_underflow_set_flag:</code> <code>\__fp_trap_underflow_set_none:</code> <code>\__fp_trap_underflow_set:N</code> <code>\__fp_trap_overflow_set:NnNn</code>	<p>Just as for invalid operations and division by zero, the three different behaviours are obtained by feeding <code>\prg_do_nothing:</code>, <code>\use_none:nnnnn</code> or <code>\use_none:nnnnnnn</code> to an auxiliary, with a further auxiliary common to overflow and underflow functions. In most cases, the argument of the <code>\__fp_overflow:w</code> and <code>\__fp_underflow:w</code> functions will be an (almost) normal number (with an exponent outside the allowed range), and the error message thus displays that number together with the result to which it overflowed or underflowed. For extreme cases such as <code>10 ** 1e9999</code>, the exponent would be too large for T<sub>E</sub>X, and <code>\__fp_overflow:w</code> receives <math>\pm\infty</math> (<code>\__fp_underflow:w</code> would receive <math>\pm 0</math>); then we cannot do better than simply say an overflow or underflow occurred.</p>
---	--

```

11151 \cs_new_protected:Npn \__fp_trap_overflow_set_error:
11152 { \__fp_trap_overflow_set:N \prg_do_nothing: }
11153 \cs_new_protected:Npn \__fp_trap_overflow_set_flag:
11154 { \__fp_trap_overflow_set:N \use_none:nnnnn }
11155 \cs_new_protected:Npn \__fp_trap_overflow_set_none:
11156 { \__fp_trap_overflow_set:N \use_none:nnnnnnn }
11157 \cs_new_protected:Npn \__fp_trap_overflow_set:N #1
11158 { \__fp_trap_overflow_set:NnNn #1 { overflow } \__fp_inf_fp:N { inf } }
11159 \cs_new_protected:Npn \__fp_trap_underflow_set_error:
11160 { \__fp_trap_underflow_set:N \prg_do_nothing: }
11161 \cs_new_protected:Npn \__fp_trap_underflow_set_flag:
11162 { \__fp_trap_underflow_set:N \use_none:nnnnn }
11163 \cs_new_protected:Npn \__fp_trap_underflow_set_none:

```

```

11164 { \__fp_trap_underflow_set:N \use_none:nnnnnnn }
11165 \cs_new_protected:Npn \__fp_trap_underflow_set:N #1
11166 { \__fp_trap_overflow_set:NnNn #1 { underflow } \__fp_zero_fp:N { 0 } }
11167 \cs_new_protected:Npn \__fp_trap_overflow_set:NnNn #1#2#3#4
11168 {
11169   \exp_args:Nno \use:n
11170   { \cs_set:cpn { \__fp_ #2 :w } \s__fp \__fp_chk:w ##1##2##3; }
11171   {
11172     #1
11173     \__fp_error:nffn
11174     { fp-flow \if_meaning:w 1 ##1 -to \fi: }
11175     { \fp_to_tl:n { \s__fp \__fp_chk:w ##1##2##3; } }
11176     { \token_if_eq_meaning:NNF 0 ##2 { - } #4 }
11177     {#2}
11178     \flag_raise:n { fp_#2 }
11179     #3 ##2
11180   }
11181 }

```

(End definition for \\_\_fp\_trap\_overflow\_set\_error: and others.)

\\_\_fp\_invalid\_operation:nnw Initialize the control sequences (to log properly their existence). Then set invalid operations to trigger an error, and division by zero, overflow, and underflow to act silently on their flag.

```

\__fp_invalid_operation_o:Nnw
\__fp_invalid_operation_tl_o:ff
\__fp_division_by_zero_o:Nnw
\__fp_division_by_zero_o:NNww
\__fp_overflow:w
\__fp_underflow:w
11182 \cs_new:Npn \__fp_invalid_operation:nnw #1#2#3; { }
11183 \cs_new:Npn \__fp_invalid_operation_o:Nnw #1#2; #3; { }
11184 \cs_new:Npn \__fp_invalid_operation_tl_o:ff #1 #2 { }
11185 \cs_new:Npn \__fp_division_by_zero_o:Nnw #1#2#3; { }
11186 \cs_new:Npn \__fp_division_by_zero_o:NNww #1#2#3; #4; { }
11187 \cs_new:Npn \__fp_overflow:w { }
11188 \cs_new:Npn \__fp_underflow:w { }
11189 \fp_trap:nn { invalid_operation } { error }
11190 \fp_trap:nn { division_by_zero } { flag }
11191 \fp_trap:nn { overflow } { flag }
11192 \fp_trap:nn { underflow } { flag }

```

(End definition for \\_\_fp\_invalid\_operation:nnw and others.)

\\_\_fp\_invalid\_operation\_o:nw Convenient short-hands for returning \c\_nan\_fp for a unary or binary operation, and expanding after.

```

11193 \cs_new:Npn \__fp_invalid_operation_o:nw
11194 { \__fp_invalid_operation:nnw { \exp_after:wN \c_nan_fp } }
11195 \cs_generate_variant:Nn \__fp_invalid_operation_o:nw { f }

```

(End definition for \\_\_fp\_invalid\_operation\_o:nw.)

## 22.3 Errors

```

\__fp_error:nnnn
\__fp_error:nnfn
\__fp_error:nffn
11196 \cs_new:Npn \__fp_error:nnnn
11197 { \__msg_kernel_expandable_error:nnnnn { kernel } }
11198 \cs_generate_variant:Nn \__fp_error:nnnn { nnf, nff }

```

(End definition for \\_\_fp\_error:nnnn.)

## 22.4 Messages

Some messages.

```

11199 \_msg_kernel_new:nnnn { kernel } { unknown-fpu-exception }
11200 {
11201     The~FPU~exception~'#1'~is~not~known:~
11202     that~trap~will~never~be~triggered.
11203 }
11204 {
11205     The~only~exceptions~to~which~traps~can~be~attached~are \\
11206     \iow_indent:n
11207     {
11208         * ~ invalid_operation \\
11209         * ~ division_by_zero \\
11210         * ~ overflow \\
11211         * ~ underflow
11212     }
11213 }
11214 \_msg_kernel_new:nnnn { kernel } { unknown-fpu-trap-type }
11215 { The~FPU~trap~type~'#2'~is~not~known. }
11216 {
11217     The~trap~type~must~be~one~of \\
11218     \iow_indent:n
11219     {
11220         * ~ error \\
11221         * ~ flag \\
11222         * ~ none
11223     }
11224 }
11225 \_msg_kernel_new:nnn { kernel } { fp-flow }
11226 { An ~ #3 ~ occurred. }
11227 \_msg_kernel_new:nnn { kernel } { fp-flow-to }
11228 { #1 ~ #3 ed ~ to ~ #2 . }
11229 \_msg_kernel_new:nnn { kernel } { fp-zero-div }
11230 { Division~by~zero~in~ #1 (#2) }
11231 \_msg_kernel_new:nnn { kernel } { fp-zero-div-ii }
11232 { Division~by~zero~in~ (#1) #3 (#2) }
11233 \_msg_kernel_new:nnn { kernel } { fp-invalid }
11234 { Invalid~operation~ #1 (#2) }
11235 \_msg_kernel_new:nnn { kernel } { fp-invalid-ii }
11236 { Invalid~operation~ (#1) #3 (#2) }
11237 </initex | package>

```

## 23 I3fp-round implementation

```

11238 <(*initex | package>
11239 <@@=fp>

\_fp_parse_word_trunc:N
\_fp_parse_word_floor:N
\_fp_parse_word_ceil:N
11240 \cs_new:Npn \_fp_parse_word_trunc:N
11241 { \_fp_parse_function:NNN \_fp_round_o:Nw \_fp_round_to_zero:NNN }
11242 \cs_new:Npn \_fp_parse_word_floor:N
11243 { \_fp_parse_function:NNN \_fp_round_o:Nw \_fp_round_to_ninf:NNN }

```

```

11244 \cs_new:Npn \__fp_parse_word_ceil:N
11245 { \__fp_parse_function:NNN \__fp_round_o:Nw \__fp_round_to_pinf:NNN }

```

(End definition for `\__fp_parse_word_trunc:N`, `\__fp_parse_word_floor:N`, and `\__fp_parse_word_ceil:N`.)

```

\__fp_parse_word_round:N
\__fp_parse_round:Nw
\__fp_parse_round_deprecation_error:Nw
round+
round0
round-

```

This looks for +, -, 0 after round. That syntax was deprecated in 2013 but the system to tell users about deprecated syntax was not really available then, so we did not have anything set up. When l3doc complains, remove the syntax by removing everything until the last `\fi:` in `\__fp_parse_word_round:N` (and getting rid of the unused definitions of `\__fp_parse_round:Nw` and `\__fp_parse_round_deprecation_error:Nw` here and in l3deprecation, perhaps also of the fp-deprecated error).

```

11246 \cs_new:Npn \__fp_parse_word_round:N #1#2
11247 {
11248   \if_meaning:w + #2
11249     \__fp_parse_round:Nw \__fp_round_to_pinf:NNN
11250   \else:
11251     \if_meaning:w 0 #2
11252       \__fp_parse_round:Nw \__fp_round_to_zero:NNN
11253     \else:
11254       \if_meaning:w - #2
11255         \__fp_parse_round:Nw \__fp_round_to_ninf:NNN
11256       \fi:
11257     \fi:
11258   \fi:
11259   \__fp_parse_function:NNN
11260   \__fp_round_o:Nw \__fp_round_to_nearest:NNN #1
11261   #2
11262 }
11263 \cs_new:Npn \__fp_parse_round:Nw
11264   #1 #2 \__fp_round_to_nearest:NNN #3#4 { #2 #1 #3 }
11265 \cs_new:Npn \__fp_parse_round_deprecation_error:Nw
11266   #1 #2 \__fp_round_to_nearest:NNN #3#4
11267 {
11268   \__fp_error:nnfn { fp-deprecated } { round#4() }
11269   {
11270     \str_case:nn {#2}
11271       { { + } { ceil } { 0 } { trunc } { - } { floor } }
11272     { { } }
11273   #2 #1 #3
11274 }

```

(End definition for `\__fp_parse_word_round:N` and others.)

## 23.1 Rounding tools

`\c__fp_five_int` This is used as the half-point for which numbers are rounded up/down.

```

11275 \int_const:Nn \c__fp_five_int { 5 }

```

(End definition for `\c__fp_five_int`.)

Floating point operations often yield a result that cannot be exactly represented in a significand with 16 digits. In that case, we need to round the exact result to a representable number. The IEEE standard defines four rounding modes:



- Round to nearest: round to the representable floating point number whose absolute difference with the exact result is the smallest. If the exact result lies exactly at the mid-point between two consecutive representable floating point numbers, round to the floating point number whose last digit is even.
- Round towards negative infinity: round to the greatest floating point number not larger than the exact result.
- Round towards zero: round to a floating point number with the same sign as the exact result, with the largest absolute value not larger than the absolute value of the exact result.
- Round towards positive infinity: round to the least floating point number not smaller than the exact result.

This is not fully implemented in `l3fp` yet, and transcendental functions fall back on the “round to nearest” mode. All rounding for basic algebra is done through the functions defined in this module, which can be redefined to change their rounding behaviour (but there is not interface for that yet).

The rounding tools available in this module are many variations on a base function `\__fp_round:NNN`, which expands to `0\exp_stop_f:` or `1\exp_stop_f:` depending on whether the final result should be rounded up or down.

- `\__fp_round:NNN <sign> <digit1> <digit2>` can expand to `0\exp_stop_f:` or `1\exp_stop_f:.`
- `\__fp_round_s:NNNw <sign> <digit1> <digit2> <more digits>;` can expand to `0\exp_stop_f:;` or `1\exp_stop_f:.`
- `\__fp_round_neg:NNN <sign> <digit1> <digit2>` can expand to `0\exp_stop_f:` or `1\exp_stop_f:.`

See implementation comments for details on the syntax.

`\__fp_round:NNN`

`\__fp_round_to_nearest:NNN`

`\__fp_round_to_nearest_ninf:NNN`

`\__fp_round_to_nearest_zero:NNN`

`\__fp_round_to_nearest_pinf:NNN`

`\__fp_round_to_ninf:NNN`

`\__fp_round_to_zero:NNN`

`\__fp_round_to_pinf:NNN`

If rounding the number  $\langle final\ sign \rangle \langle digit_1 \rangle . \langle digit_2 \rangle$  to an integer rounds it towards zero (truncates it), this function expands to `0\exp_stop_f:`, and otherwise to `1\exp_stop_f:.` Typically used within the scope of an `\__int_eval:w`, to add 1 if needed, and thereby round correctly. The result depends on the rounding mode.

It is very important that  $\langle final\ sign \rangle$  be the final sign of the result. Otherwise, the result would be incorrect in the case of rounding towards  $-\infty$  or towards  $+\infty$ . Also recall that  $\langle final\ sign \rangle$  is 0 for positive, and 2 for negative.

By default, the functions below return `0\exp_stop_f:`, but this is superseded by `\__fp_round_return_one:`, which instead returns `1\exp_stop_f:`, expanding everything and removing `0\exp_stop_f:` in the process. In the case of rounding towards  $\pm\infty$  or towards 0, this is not really useful, but it prepares us for the “round to nearest, ties to even” mode.

The “round to nearest” mode is the default. If the  $\langle digit_2 \rangle$  is larger than 5, then round up. If it is less than 5, round down. If it is exactly 5, then round such that  $\langle digit_1 \rangle$  plus the result is even. In other words, round up if  $\langle digit_1 \rangle$  is odd.

The “round to nearest” mode has three variants, which differ in how ties are rounded: down towards  $-\infty$ , truncated towards 0, or up towards  $+\infty$ .

11276 `\cs_new:Npn \__fp_round_return_one:`

11277 `{ \exp_after:wN 1 \exp_after:wN \exp_stop_f: \exp:w }`

11278 `\cs_new:Npn \__fp_round_to_ninf:NNN #1 #2 #3`

```

11279 {
11280     \if_meaning:w 2 #1
11281     \if_int_compare:w #3 > 0 \exp_stop_f:
11282     \__fp_round_return_one:
11283     \fi:
11284     \fi:
11285     0 \exp_stop_f:
11286 }
11287 \cs_new:Npn \__fp_round_to_zero:NNN #1 #2 #3 { 0 \exp_stop_f: }
11288 \cs_new:Npn \__fp_round_to_pinf:NNN #1 #2 #3
11289 {
11290     \if_meaning:w 0 #1
11291     \if_int_compare:w #3 > 0 \exp_stop_f:
11292     \__fp_round_return_one:
11293     \fi:
11294     \fi:
11295     0 \exp_stop_f:
11296 }
11297 \cs_new:Npn \__fp_round_to_nearest:NNN #1 #2 #3
11298 {
11299     \if_int_compare:w #3 > \c__fp_five_int
11300     \__fp_round_return_one:
11301     \else:
11302     \if_meaning:w 5 #3
11303     \if_int_odd:w #2 \exp_stop_f:
11304     \__fp_round_return_one:
11305     \fi:
11306     \fi:
11307     \fi:
11308     0 \exp_stop_f:
11309 }
11310 \cs_new:Npn \__fp_round_to_nearest_ninf:NNN #1 #2 #3
11311 {
11312     \if_int_compare:w #3 > \c__fp_five_int
11313     \__fp_round_return_one:
11314     \else:
11315     \if_meaning:w 5 #3
11316     \if_meaning:w 2 #1
11317     \__fp_round_return_one:
11318     \fi:
11319     \fi:
11320     \fi:
11321     0 \exp_stop_f:
11322 }
11323 \cs_new:Npn \__fp_round_to_nearest_zero:NNN #1 #2 #3
11324 {
11325     \if_int_compare:w #3 > \c__fp_five_int
11326     \__fp_round_return_one:
11327     \fi:
11328     0 \exp_stop_f:
11329 }
11330 \cs_new:Npn \__fp_round_to_nearest_pinf:NNN #1 #2 #3
11331 {
11332     \if_int_compare:w #3 > \c__fp_five_int

```

```

11333     \__fp_round_return_one:
11334 \else:
11335     \if_meaning:w 5 #3
11336     \if_meaning:w 0 #1
11337         \__fp_round_return_one:
11338     \fi:
11339 \fi:
11340 \fi:
11341 0 \exp_stop_f:
11342 }
11343 \cs_new_eq:NN \__fp_round:NNN \__fp_round_to_nearest:NNN

```

(End definition for \\_\_fp\_round:NNN and others.)

**\\_\_fp\_round\_s:NNNw** Similar to \\_\_fp\_round:NNN, but with an extra semicolon, this function expands to 0\exp\_stop\_f:; if rounding *⟨final sign⟩⟨digit⟩.⟨more digits⟩* to an integer truncates, and to 1\exp\_stop\_f:; otherwise. The *⟨more digits⟩* part must be a digit, followed by something that does not overflow a \int\_use:N \\_\_int\_eval:w construction. The only relevant information about this piece is whether it is zero or not.

```

11344 \cs_new:Npn \__fp_round_s:NNNw #1 #2 #3 #4;
11345 {
11346     \exp_after:wN \__fp_round:NNN
11347     \exp_after:wN #1
11348     \exp_after:wN #2
11349     \__int_value:w \__int_eval:w
11350     \if_int_odd:w 0 \if_meaning:w 0 #3 1 \fi:
11351         \if_meaning:w 5 #3 1 \fi:
11352         \exp_stop_f:
11353     \if_int_compare:w \__int_eval:w #4 > 0 \exp_stop_f:
11354     1 +
11355     \fi:
11356     \fi:
11357     #3
11358 ;
11359 }

```

(End definition for \\_\_fp\_round\_s:NNNw.)

**\\_\_fp\_round\_digit:Nw** This function should always be called within an \\_\_int\_value:w or \\_\_int\_eval:w expansion; it may add an extra \\_\_int\_eval:w, which means that the integer or integer expression should not be ended with a synonym of \relax, but with a semi-colon for instance.

```

11360 \cs_new:Npn \__fp_round_digit:Nw #1 #2;
11361 {
11362     \if_int_odd:w \if_meaning:w 0 #1 1 \else:
11363         \if_meaning:w 5 #1 1 \else:
11364         0 \fi: \fi: \exp_stop_f:
11365     \if_int_compare:w \__int_eval:w #2 > 0 \exp_stop_f:
11366     \__int_eval:w 1 +
11367     \fi:
11368     \fi:
11369     #1
11370 }

```

(End definition for `\_fp\_round\_digit:Nw`.)

```

\_fp\_round\_neg:NNN This expands to 0\exp\_stop\_f: or 1\exp\_stop\_f: after doing the following test. Start-
\_fp\_round\_to\_nearest\_neg:NNN ing from a number of the form  $\langle final\ sign \rangle 0.\langle 15\ digits \rangle \langle digit_1 \rangle$  with exactly 15 (non-all-
\_fp\_round\_to\_nearest\_ninf\_neg:NNN zero) digits before  $\langle digit_1 \rangle$ , subtract from it  $\langle final\ sign \rangle 0.0 \dots 0 \langle digit_2 \rangle$ , where there are
\_fp\_round\_to\_nearest\_zero\_neg:NNN 16 zeros. If in the current rounding mode the result should be rounded down, then this
\_fp\_round\_to\_nearest\_pinf\_neg:NNN function returns 1\exp\_stop\_f:. Otherwise, i.e., if the result is rounded back to the
\_fp\_round\_to\_ninf\_neg:NNN first operand, then this function returns 0\exp\_stop\_f:.
\_fp\_round\_to\_zero\_neg:NNN It turns out that this negative “round to nearest” is identical to the positive one.
\_fp\_round\_to\_pinf\_neg:NNN And this is the default mode.

11371 \cs\_new\_eq:NN \_fp\_round\_to\_ninf\_neg:NNN \_fp\_round\_to\_pinf:NNN
11372 \cs\_new:Npn \_fp\_round\_to\_zero\_neg:NNN #1 #2 #3
11373 {
11374   \if\_int\_compare:w #3 > 0 \exp\_stop\_f:
11375   \_fp\_round\_return\_one:
11376   \fi:
11377   0 \exp\_stop\_f:
11378 }
11379 \cs\_new\_eq:NN \_fp\_round\_to\_pinf\_neg:NNN \_fp\_round\_to\_ninf:NNN
11380 \cs\_new\_eq:NN \_fp\_round\_to\_nearest\_neg:NNN \_fp\_round\_to\_nearest:NNN
11381 \cs\_new\_eq:NN \_fp\_round\_to\_nearest\_ninf\_neg:NNN \_fp\_round\_to\_nearest\_pinf:NNN
11382 \cs\_new:Npn \_fp\_round\_to\_nearest\_zero\_neg:NNN #1 #2 #3
11383 {
11384   \if\_int\_compare:w #3 < \c\_fp\_five\_int \else:
11385   \_fp\_round\_return\_one:
11386   \fi:
11387   0 \exp\_stop\_f:
11388 }
11389 \cs\_new\_eq:NN \_fp\_round\_to\_nearest\_pinf\_neg:NNN \_fp\_round\_to\_nearest\_ninf:NNN
11390 \cs\_new\_eq:NN \_fp\_round\_neg:NNN \_fp\_round\_to\_nearest\_neg:NNN

```

(End definition for `\_fp\_round\_neg:NNN` and others.)

## 23.2 The round function

`\_fp\_round\_o:Nw` The `trunc`, `ceil` and `floor` functions expect one or two arguments (the second is 0 by default), and the `round` function also accepts a third argument (`nan` by default), which changes #1 from `\_fp\_round\_to\_nearest:NNN` to one of its analogues.

```

11391 \cs\_new:Npn \_fp\_round\_o:Nw #1#2 @
11392 {
11393   \if\_case:w
11394     \_int\_eval:w \_fp\_array\_count:n {#2} \_int\_eval\_end:
11395     \_fp\_round\_no\_arg\_o:Nw #1 \exp:w
11396   \or: \_fp\_round:Nwn #1 #2 {0} \exp:w
11397   \or: \_fp\_round:Nww #1 #2 \exp:w
11398   \else: \_fp\_round:Nwww #1 #2 @ \exp:w
11399   \fi:
11400   \exp\_after:wN \exp\_end:
11401 }

```

(End definition for `\_fp\_round\_o:Nw`.)

\\_fp\_round\_no\_arg\_o:Nw

```

11402 \cs_new:Npn \_fp_round_no_arg_o:Nw #1
11403 {
11404   \cs_if_eq:NNTF #1 \_fp_round_to_nearest:NNN
11405   { \_fp_error:nnnn { fp-num-args } { round () } { 1 } { 3 } }
11406   {
11407     \_fp_error:nffn { fp-num-args }
11408     { \_fp_round_name_from_cs:N #1 () } { 1 } { 2 }
11409   }
11410   \exp_after:wN \c_nan_fp
11411 }

```

(End definition for \\_fp\_round\_no\_arg\_o:Nw.)

\\_fp\_round:Nwww

Having three arguments is only allowed for round, not trunc, ceil, floor, so check for that case. If all is well, construct one of \\_fp\_round\_to\_nearest:NNN, \\_fp\_round\_to\_nearest\_zero:NNN, \\_fp\_round\_to\_nearest\_ninf:NNN, \\_fp\_round\_to\_nearest\_pinf:NNN and act accordingly.

```

11412 \cs_new:Npn \_fp_round:Nwww #1#2 ; #3 ; \s_fp \_fp_chk:w #4#5#6 ; #7 @
11413 {
11414   \cs_if_eq:NNTF #1 \_fp_round_to_nearest:NNN
11415   {
11416     \tl_if_empty:nTF {#7}
11417     {
11418       \exp_args:Nc \_fp_round:Nww
11419       {
11420         \_fp_round_to_nearest
11421         \if_meaning:w 0 #4 _zero \else:
11422         \if_case:w #5 \exp_stop_f: _pinf \or: \else: _ninf \fi: \fi:
11423         :NNN
11424       }
11425       #2 ; #3 ;
11426     }
11427     {
11428       \_fp_error:nnnn { fp-num-args } { round () } { 1 } { 3 }
11429       \exp_after:wN \c_nan_fp
11430     }
11431   }
11432   {
11433     \_fp_error:nffn { fp-num-args }
11434     { \_fp_round_name_from_cs:N #1 () } { 1 } { 2 }
11435     \exp_after:wN \c_nan_fp
11436   }
11437 }

```

(End definition for \\_fp\_round:Nwww.)

\\_fp\_round\_name\_from\_cs:N

```

11438 \cs_new:Npn \_fp_round_name_from_cs:N #1
11439 {
11440   \cs_if_eq:NNTF #1 \_fp_round_to_zero:NNN { trunc }
11441   {
11442     \cs_if_eq:NNTF #1 \_fp_round_to_ninf:NNN { floor }
11443     {

```

```

11444         \cs_if_eq:NNTF #1 \__fp_round_to_pinf:NNN { ceil }
11445         { round }
11446     }
11447 }
11448 }

```

(End definition for \\_\_fp\_round\_name\_from\_cs:N.)

\\_\_fp\_round:Nww

\\_\_fp\_round:Nwn

```

11449 \cs_new:Npn \__fp_round:Nww #1#2 ; #3 ;
11450 {
11451     \__fp_small_int:wTF #3; { \__fp_round:Nwn #1#2; }
11452     {
11453         \__fp_invalid_operation_tl_o:ff
11454         { \__fp_round_name_from_cs:N #1 }
11455         { \__fp_array_to_clist:n { #2; #3; } }
11456     }
11457 }
11458 \cs_new:Npn \__fp_round:Nwn #1 \s__fp \__fp_chk:w #2#3#4; #5
11459 {
11460     \if_meaning:w 1 #2
11461     \exp_after:wN \__fp_round_normal:NwNNnw
11462     \exp_after:wN #1
11463     \__int_value:w #5
11464     \else:
11465     \exp_after:wN \__fp_exp_after_o:w
11466     \fi:
11467     \s__fp \__fp_chk:w #2#3#4;
11468 }
11469 \cs_new:Npn \__fp_round_normal:NwNNnw #1#2 \s__fp \__fp_chk:w 1#3#4#5;
11470 {
11471     \__fp_decimate:nNnnnn { \c__fp_prec_int - #4 - #2 }
11472     \__fp_round_normal:NnnwNNnn #5 #1 #3 {#4} {#2}
11473 }
11474 \cs_new:Npn \__fp_round_normal:NnnwNNnn #1#2#3#4; #5#6
11475 {
11476     \exp_after:wN \__fp_round_normal:NNwNnn
11477     \__int_value:w \__int_eval:w
11478     \if_int_compare:w #2 > 0 \exp_stop_f:
11479     1 \__int_value:w #2
11480     \exp_after:wN \__fp_round_pack:Nw
11481     \__int_value:w \__int_eval:w 1#3 +
11482     \else:
11483     \if_int_compare:w #3 > 0 \exp_stop_f:
11484     1 \__int_value:w #3 +
11485     \fi:
11486     \fi:
11487     \exp_after:wN #5
11488     \exp_after:wN #6
11489     \use_none:nnnnnn #3
11490     #1
11491     \__int_eval_end:
11492     0000 0000 0000 0000 ; #6
11493 }

```

```

11494 \cs_new:Npn \__fp_round_pack:Nw #1
11495 { \if_meaning:w 2 #1 + 1 \fi: \__int_eval_end: }
11496 \cs_new:Npn \__fp_round_normal:NNwNnn #1 #2
11497 {
11498   \if_meaning:w 0 #2
11499     \exp_after:wN \__fp_round_special:NwwNnn
11500     \exp_after:wN #1
11501   \fi:
11502   \__fp_pack_twice_four:wNNNNNNNN
11503   \__fp_pack_twice_four:wNNNNNNNN
11504   \__fp_round_normal_end:wwNnn
11505   ; #2
11506 }
11507 \cs_new:Npn \__fp_round_normal_end:wwNnn #1;#2;#3#4#5
11508 {
11509   \exp_after:wN \__fp_exp_after_o:w \exp:w \exp_end_continue_f:w
11510   \__fp_sanitizew:Nw #3 #4 ; #1 ;
11511 }
11512 \cs_new:Npn \__fp_round_special:NwwNnn #1#2;#3;#4#5#6
11513 {
11514   \if_meaning:w 0 #1
11515     \__fp_case_return:nw
11516     { \exp_after:wN \__fp_zero_fp:N \exp_after:wN #4 }
11517   \else:
11518     \exp_after:wN \__fp_round_special_aux:Nw
11519     \exp_after:wN #4
11520     \__int_value:w \__int_eval:w 1
11521     \if_meaning:w 1 #1 -#6 \else: +#5 \fi:
11522   \fi:
11523   ;
11524 }
11525 \cs_new:Npn \__fp_round_special_aux:Nw #1#2;
11526 {
11527   \exp_after:wN \__fp_exp_after_o:w \exp:w \exp_end_continue_f:w
11528   \__fp_sanitizew:Nw #1#2; {1000}{0000}{0000}{0000};
11529 }

```

(End definition for \\_\_fp\_round:Nww and others.)

```

11530 </initex | package>

```

## 24 l3fp-parse implementation

```

11531 <*initex | package>
11532 <@@=fp>

```

### 24.1 Work plan

The task at hand is non-trivial, and some previous failed attempts show that the code leads to unreadable logs, so we had better get it (almost) right the first time. Let us first describe our goal, then discuss the design precisely before writing any code.

`\__fp_parse:n` Evaluates the *<floating point expression>* and leaves the result in the input stream as an internal floating point number. This function forms the basis of almost all public l3fp functions. During evaluation, each token is fully f-expanded.

`\__fp_parse_o:n` does the same but expands once after its result.

**TeXhackers note:** Registers (integers, toks, etc.) are automatically unpacked, without requiring a function such as `\int_use:N`. Invalid tokens remaining after `f`-expansion lead to unrecoverable low-level TeX errors.

(End definition for `\__fp_parse:n`.)

Floating point expressions are composed of numbers, given in various forms, infix operators, such as `+`, `**`, or `,` (which joins two numbers into a list), and prefix operators, such as the unary `-`, functions, or opening parentheses. Here is a list of precedences which control the order of evaluation (some distinctions are irrelevant for the order of evaluation, but serve as signals), from the tightest binding to the loosest binding.

16 Function calls with multiple arguments.

15 Function calls expecting exactly one argument.

13/14 Binary `**` and `^` (right to left).

12 Unary `+`, `-`, `!` (right to left).

10 Binary `*`, `/`, and juxtaposition (implicit `*`).

9 Binary `+` and `-`.

7 Comparisons.

6 Logical `and`, denoted by `&&`.

5 Logical `or`, denoted by `||`.

4 Ternary operator `?:`, piece `?`.

3 Ternary operator `?:`, piece `:`.

2 Commas, and parentheses accepting commas.

1 Parentheses expecting exactly one argument.

0 Start and end of the expression.

```
\c__fp_prec_funcii_int
\c__fp_prec_func_int      11533 \int_const:Nn \c__fp_prec_funcii_int { 16 }
\c__fp_prec_hatii_int     11534 \int_const:Nn \c__fp_prec_func_int   { 15 }
\c__fp_prec_hat_int       11535 \int_const:Nn \c__fp_prec_hatii_int   { 14 }
\c__fp_prec_not_int       11536 \int_const:Nn \c__fp_prec_hat_int     { 13 }
\c__fp_prec_times_int     11537 \int_const:Nn \c__fp_prec_not_int    { 12 }
\c__fp_prec_plus_int      11538 \int_const:Nn \c__fp_prec_times_int   { 10 }
\c__fp_prec_comp_int      11539 \int_const:Nn \c__fp_prec_plus_int    { 9 }
\c__fp_prec_and_int       11540 \int_const:Nn \c__fp_prec_comp_int    { 7 }
\c__fp_prec_or_int        11541 \int_const:Nn \c__fp_prec_and_int     { 6 }
\c__fp_prec_quest_int     11542 \int_const:Nn \c__fp_prec_or_int      { 5 }
\c__fp_prec_colon_int     11543 \int_const:Nn \c__fp_prec_quest_int   { 4 }
\c__fp_prec_comma_int     11544 \int_const:Nn \c__fp_prec_colon_int   { 3 }
\c__fp_prec_paren_int     11545 \int_const:Nn \c__fp_prec_comma_int   { 2 }
\c__fp_prec_end_int       11546 \int_const:Nn \c__fp_prec_paren_int   { 1 }
\c__fp_prec_end_int       11547 \int_const:Nn \c__fp_prec_end_int     { 0 }
```

(End definition for `\c__fp_prec_funcii_int` and others.)



### 24.1.1 Storing results

The main question in parsing expressions expandably is to decide where to put the intermediate results computed for various subexpressions.

One option is to store the values at the start of the expression, and carry them together as the first argument of each macro. However, we want to **f**-expand tokens one by one in the expression (as `\int_eval:n` does), and with this approach, expanding the next unread token forces us to jump with `\exp_after:wN` over every value computed earlier in the expression. With this approach, the run-time grows at least quadratically in the length of the expression, if not as its cube (inserting the `\exp_after:wN` is tricky and slow).

A second option is to place those values at the end of the expression. Then expanding the next unread token is straightforward, but this still hits a performance issue: for long expressions we would be reaching all the way to the end of the expression at every step of the calculation. The run-time is again quadratic.

A variation of the above attempts to place the intermediate results which appear when computing a parenthesized expression near the closing parenthesis. This still lets us expand tokens as we go, and avoids performance problems as long as there are enough parentheses. However, it would be much better to avoid requiring the closing parenthesis to be present as soon as the corresponding opening parenthesis is read: the closing parenthesis may still be hidden in a macro yet to be expanded.

Hence, we need to go for some fine expansion control: the result is stored *before* the start!

Let us illustrate this idea in a simple model: adding positive integers which may be resulting from the expansion of macros, or may be values of registers. Assume that one number, say, 12345, has already been found, and that we want to parse the next number. The current status of the code may look as follows.

```
\exp_after:wN \add:ww \__int_value:w 12345 \exp_after:wN ;  
\exp:w \operand:w <stuff>
```

One step of expansion expands `\exp_after:wN`, which triggers the primitive `\__int_value:w`, which reads the five digits we have already found, 12345. This integer is unfinished, causing the second `\exp_after:wN` to expand, and to trigger the construction `\exp:w`, which expands `\operand:w`, defined to read what follows and make a number out of it, then leave `\exp_end:`, the number, and a semicolon in the input stream. Once `\operand:w` is done expanding, we obtain essentially

```
\exp_after:wN \add:ww \__int_value:w 12345 ;  
\exp:w \exp_end: 333444 ;
```

where in fact `\exp_after:wN` has already been expanded, `\__int_value:w` has already seen 12345, and `\exp:w` is still looking for a number. It finds `\exp_end:`, hence expands to nothing. Now, `\__int_value:w` sees the `;`, which cannot be part of a number. The expansion stops, and we are left with

```
\add:ww 12345 ; 333444 ;
```

which can safely perform the addition by grabbing two arguments delimited by `;`.

If we were to continue parsing the expression, then the following number should also be cleaned up before the next use of a binary operation such as `\add:ww`. Just like `\__int_value:w 12345 \exp_after:wN ;` expanded what follows once, we need `\add:ww` to

do the calculation, and in the process to expand the following once. This is also true in our real application: all the functions of the form `\__fp_..._o:ww` expand what follows once. This comes at the cost of leaving tokens in the input stack, and we need to be careful not to waste this memory. All of our discussion above is nice but simplistic, as operations should not simply be performed in the order they appear.

### 24.1.2 Precedence and infix operators

The various operators we will encounter have different precedences, which influence the order of calculations:  $1 + 2 \times 3 = 1 + (2 \times 3)$  because  $\times$  has a higher precedence than  $+$ . The true analog of our macro `\operand:w` must thus take care of that. When looking for an operand, it needs to perform calculations until reaching an operator which has lower precedence than the one which called `\operand:w`. This means that `\operand:w` must know what the previous binary operator is, or rather, its precedence: we thus rename it `\operand:Nw`. Let us describe as an example how we plan to do the calculation  $41 - 2^3 * 4 + 5$ . Here, we abuse notations: the first argument of `\operand:Nw` should be an integer constant (`\c__fp_prec_plus_int, ...`) equal to the precedence of the given operator, not directly the operator itself.

- Clean up 41 and find  $-$ . We call `\operand:Nw -` to find the second operand.
- Clean up 2 and find  $\wedge$ .
- Compare the precedences of  $-$  and  $\wedge$ . Since the latter is higher, we need to compute the exponentiation. For this, find the second operand with a nested call to `\operand:Nw \wedge`.
- Clean up 3 and find  $*$ .
- Compare the precedences of  $\wedge$  and  $*$ . Since the former is higher, `\operand:Nw \wedge` has found the second operand of the exponentiation, which is computed:  $2^3 = 8$ .
- We now have  $41 + 8 * 4 + 5$ , and `\operand:Nw -` is still looking for a second operand for the subtraction. Is it 8?
- Compare the precedences of  $-$  and  $*$ . Since the latter is higher, we are not done with 8. Call `\operand:Nw *` to find the second operand of the multiplication.
- Clean up 4, and find  $-$ .
- Compare the precedences of  $*$  and  $-$ . Since the former is higher, `\operand:Nw *` has found the second operand of the multiplication, which is computed:  $8 * 4 = 32$ .
- We now have  $41 + 32 + 5$ , and `\operand:Nw -` is still looking for a second operand for the subtraction. Is it 32?
- Compare the precedences of  $-$  and  $+$ . Since they are equal, `\operand:Nw -` has found the second operand for the subtraction, which is computed:  $41 - 32 = 9$ .
- We now have  $9 + 5$ .

The procedure above stops short of performing all computations, but adding a surrounding call to `\operand:Nw` with a very low precedence ensures that all computations are performed before `\operand:Nw` is done. Adding a trailing marker with the same very low precedence prevents the surrounding `\operand:Nw` from going beyond the marker.

The pattern above to find an operand for a given operator, is to find one number and the next operator, then compare precedences to know if the next computation should be done. If it should, then perform it after finding its second operand, and look at the next operator, then compare precedences to know if the next computation should be done. This continues until we find that the next computation should not be done. Then, we stop.

We are now ready to get a bit more technical and describe which of the `l3fp-parse` functions correspond to each step above.

First, `\__fp_parse_operand:Nw` is the `\operand:Nw` function above, with small modifications due to expansion issues discussed later. We denote by  $\langle precedence \rangle$  the argument of `\__fp_parse_operand:Nw`, that is, the precedence of the binary operator whose operand we are trying to find. The basic action is to read numbers from the input stream. This is done by `\__fp_parse_one:Nw`. A first approximation of this function is that it reads one  $\langle number \rangle$ , performing no computation, and finds the following binary  $\langle operator \rangle$ . Then it expands to

```
 $\langle number \rangle$ 
\__fp_parse_infix_ $\langle operator \rangle$ :N  $\langle precedence \rangle$ 
```

expanding the `infix` auxiliary before leaving the above in the input stream.

We now explain the `infix` auxiliaries. We need some flexibility in how we treat the case of equal precedences: most often, the first operation encountered should be performed, such as  $1-2-3$  being computed as  $(1-2)-3$ , but  $2^3^4$  should be evaluated as  $2^{(3^4)}$  instead. For this reason, and to support the equivalence between `**` and `^` more easily, each binary operator is converted to a control sequence `\__fp_parse_infix_ $\langle operator \rangle$ :N` when it is encountered for the first time. Instead of passing both precedences to a test function to do the comparison steps above, we pass the  $\langle precedence \rangle$  (of the earlier operator) to the `infix` auxiliary for the following  $\langle operator \rangle$ , to know whether to perform the computation of the  $\langle operator \rangle$ . If it should not be performed, the `infix` auxiliary expands to

```
@ \use_none:n \__fp_parse_infix_ $\langle operator \rangle$ :N
```

and otherwise it calls `\__fp_parse_operand:Nw` with the precedence of the  $\langle operator \rangle$  to find its second operand  $\langle number_2 \rangle$  and the next  $\langle operator_2 \rangle$ , and expands to

```
@ \__fp_parse_apply_binary:NwNwN
 $\langle operator \rangle$   $\langle number_2 \rangle$ 
@ \__fp_parse_infix_ $\langle operator_2 \rangle$ :N
```

The `infix` function is responsible for comparing precedences, but cannot directly call the computation functions, because the first operand  $\langle number \rangle$  is before the `infix` function in the input stream. This is why we stop the expansion here and give control to another function to close the loop.

A definition of `\__fp_parse_operand:Nw  $\langle precedence \rangle$`  with some of the expansion control removed is

```
\exp_after:wN \__fp_parse_continue:NwN
\exp_after:wN  $\langle precedence \rangle$ 
\exp:w \exp_end_continue_f:w
\__fp_parse_one:Nw  $\langle precedence \rangle$ 
```

This expands `\__fp_parse_one:Nw`  $\langle precedence \rangle$  completely, which finds a number, wraps the next  $\langle operator \rangle$  into an infix function, feeds this function the  $\langle precedence \rangle$ , and expands it, yielding either

```
\__fp_parse_continue:NwN  $\langle precedence \rangle$ 
 $\langle number \rangle$  @
\use_none:n \__fp_parse_infix_ $\langle operator \rangle$ :N
```

or

```
\__fp_parse_continue:NwN  $\langle precedence \rangle$ 
 $\langle number \rangle$  @
\__fp_parse_apply_binary:NwNwN
 $\langle operator \rangle$   $\langle number_2 \rangle$ 
@ \__fp_parse_infix_ $\langle operator_2 \rangle$ :N
```

The definition of `\__fp_parse_continue:NwN` is then very simple:

```
\cs_new:Npn \__fp_parse_continue:NwN #1#2@#3 { #3 #1 #2 @ }
```

In the first case, #3 is `\use_none:n`, yielding

```
\use_none:n  $\langle precedence \rangle$   $\langle number \rangle$  @
\__fp_parse_infix_ $\langle operator \rangle$ :N
```

then  $\langle number \rangle$  @  $\__fp\_parse\_infix\_ \langle operator \rangle$ :N. In the second case, #3 is `\__fp_parse_apply_binary:NwNwN`, whose role is to compute  $\langle number \rangle$   $\langle operator \rangle$   $\langle number_2 \rangle$  and to prepare for the next comparison of precedences: first we get

```
\__fp_parse_apply_binary:NwNwN
 $\langle precedence \rangle$   $\langle number \rangle$  @
 $\langle operator \rangle$   $\langle number_2 \rangle$ 
@ \__fp_parse_infix_ $\langle operator_2 \rangle$ :N
```

then

```
\exp_after:wN \__fp_parse_continue:NwN
\exp_after:wN  $\langle precedence \rangle$ 
\exp:w \exp_end_continue_f:w
\__fp_ $\langle operator \rangle$ _o:ww  $\langle number \rangle$   $\langle number_2 \rangle$ 
\exp:w \exp_end_continue_f:w
\__fp_parse_infix_ $\langle operator_2 \rangle$ :N  $\langle precedence \rangle$ 
```

where `\__fp_ $\langle operator \rangle$ _o:ww` computes  $\langle number \rangle$   $\langle operator \rangle$   $\langle number_2 \rangle$  and expands after the result, thus triggers the comparison of the precedence of the  $\langle operator_2 \rangle$  and the  $\langle precedence \rangle$ , continuing the loop.

We have introduced the most important functions here, and the next few paragraphs we describe various subtleties.

### 24.1.3 Prefix operators, parentheses, and functions

Prefix operators (unary `-`, `+`, `!`) and parentheses are taken care of by the same mechanism, and functions (`sin`, `exp`, etc.) as well. Finding the argument of the unary `-`, for instance, is very similar to grabbing the second operand of a binary infix operator, with a subtle precedence explained below. Once that operand is found, the operator can be applied to it (for the unary `-`, this simply flips the sign). A left parenthesis is just a prefix operator with a very low precedence equal to that of the closing parenthesis (which is treated as an infix operator, since it normally appears just after numbers), so that all computations are performed until the closing parenthesis. The prefix operator associated to the left parenthesis does not alter its argument, but it removes the closing parenthesis (with some checks).

Prefix operators are the reason why we only summarily described the function `\_fp_parse_one:Nw` earlier. This function is responsible for reading in the input stream the first possible *number* and the next infix *operator*. If what follows `\_fp_parse_one:Nw` *precedence* is a prefix operator, then we must find the operand of this prefix operator through a nested call to `\_fp_parse_operand:Nw` with the appropriate precedence, then apply the operator to the operand found to yield the result of `\_fp_parse_one:Nw`. So far, all is simple.

The unary operators `+`, `-`, `!` complicate things a little bit: `-3**2` should be  $-(3^2) = -9$ , and not  $(-3)^2 = 9$ . This would easily be done by giving `-` a lower precedence, equal to that of the infix `+` and `-`. Unfortunately, this fails in cases such as `3**-2*4`, yielding  $3^{-2 \times 4}$  instead of the correct  $3^{-2} \times 4$ . A second attempt would be to call `\_fp_parse_operand:Nw` with the *precedence* of the previous operator, but `0>-2+3` is then parsed as `0>-(2+3)`: the addition is performed because it binds more tightly than the comparison which precedes `-`. The correct approach is for a unary `-` to perform operations whose precedence is greater than both that of the previous operation, and that of the unary `-` itself. The unary `-` is given a precedence higher than multiplication and division. This does not lead to any surprising result, since  $-(x/y) = (-x)/y$  and similarly for multiplication, and it reduces the number of nested calls to `\_fp_parse_operand:Nw`.

Functions are implemented as prefix operators with very high precedence, so that their argument is the first number that can possibly be built.

Note that contrarily to the **infix** functions discussed earlier, the **prefix** functions do perform tests on the previous *precedence* to decide whether to find an argument or not, since we know that we need a number, and must never stop there.

### 24.1.4 Numbers and reading tokens one by one

So far, we have glossed over one important point: what is a “number”? A number is typically given in the form *significand***e***exponent*, where the *significand* is any non-empty string composed of decimal digits and at most one decimal separator (a period), the exponent “**e***exponent*” is optional and is composed of an exponent mark **e** followed by a possibly empty string of signs `+` or `-` and a non-empty string of decimal digits. The *significand* can also be an integer, dimension, skip, or muskip variable, in which case dimensions are converted from points (or mu units) to floating points, and the *exponent* can also be an integer variable. Numbers can also be given as floating point variables, or as named constants such as `nan`, `inf` or `pi`. We may add more types in the future.

When `\_fp_parse_one:Nw` is looking for a “number”, here is what happens.

- If the next token is a control sequence with the meaning of `\scan_stop:`, it can be: `\s__fp`, in which case our job is done, as what follows is an internal floating point number, or `\s__fp_mark`, in which case the expression has come to an early end, as we are still looking for a number here, or something else, in which case we consider the control sequence to be a bad variable resulting from c-expansion.
- If the next token is a control sequence with a different meaning, we assume that it is a register, unpack it with `\tex_the:D`, and use its value (in `pt` for dimensions and `skips`, `mu` for muskips) as the *significand* of a number: we look for an exponent.
- If the next token is a digit, we remove any leading zeros, then read a significand larger than 1 if the next character is a digit, read a significand smaller than 1 if the next character is a period, or we have found a significand equal to 0 otherwise, and look for an exponent.
- If the next token is a letter, we collect more letters until the first non-letter: the resulting word may denote a function such as `asin`, a constant such as `pi` or be unknown. In the first case, we call `\__fp_parse_operand:Nw` to find the argument of the function, then apply the function, before declaring that we are done. Otherwise, we are done, either with the value of the constant, or with the value `nan` for unknown words.
- If the next token is anything else, we check whether it is a known prefix operator, in which case `\__fp_parse_operand:Nw` finds its operand. If it is not known, then either a number is missing (if the token is a known infix operator) or the token is simply invalid in floating point expressions.

Once a number is found, `\__fp_parse_one:Nw` also finds an infix operator. This goes as follows.

- If the next token is a control sequence, it could be the special marker `\s__fp_mark`, and otherwise it is a case of juxtaposing numbers, such as `2\c_zero`, with an implied multiplication.
- If the next token is a letter, it is also a case of juxtaposition, as letters cannot be proper infix operators.
- Otherwise (including in the case of digits), if the token is a known infix operator, the appropriate `\__fp_infix_<operator>:N` function is built, and if it does not exist, we complain. In particular, the juxtaposition `\c_zero 2` is disallowed.

In the above, we need to test whether a character token `#1` is a digit:

```
\if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
  is a digit
\else:
  not a digit
\fi:
```

To exclude 0, replace 9 by 10. The use of `\token_to_str:N` ensures that a digit with any catcode is detected. To test if a character token is a letter, we need to work with its character code, testing if ‘`#1`’ lies in [65, 90] (uppercase letters) or [97, 112] (lowercase letters)

```

\if_int_compare:w \__int_eval:w
  ( '#1 \if_int_compare:w '#1 > 'Z - 32 \fi: ) / 26 = 3 \exp_stop_f:
  is a letter
\else:
  not a letter
\fi:

```

At all steps, we try to accept all category codes: when `#1` is kept to be used later, it is almost always converted to category code other through `\token_to_str:N`. More precisely, catcodes `{3,6,7,8,11,12}` should work without trouble, but not `{1,2,4,10,13}`, and of course `{0,5,9}` cannot become tokens.

Floating point expressions should behave as much as possible like  $\varepsilon$ -TeX-based integer expressions and dimension expressions. In particular, `f`-expansion should be performed as the expression is read, token by token, forcing the expansion of protected macros, and ignoring spaces. One advantage of expanding at every step is that restricted expandable functions can then be used in floating point expressions just as they can be in other kinds of expressions. Problematically, spaces stop `f`-expansion: for instance, the macro `\X` below would not be expanded if we simply performed `f`-expansion.

```

\DeclareDocumentCommand {\test} {m} { \fp_eval:n {#1} }
\ExplSyntaxOff
\test { 1 + \X }

```

Of course, spaces typically do not appear in a code setting, but may very easily come in document-level input, from which some expressions may come. To avoid this problem, at every step, we do essentially what `\use:f` would do: take an argument, put it back in the input stream, then `f`-expand it. This is not a complete solution, since a macro's expansion could contain leading spaces which would stop the `f`-expansion before further macro calls are performed. However, in practice it should be enough: in particular, floating point numbers are correctly expanded to the underlying `\s__fp ...` structure. The `f`-expansion is performed by `\__fp_parse_expand:w`.

## 24.2 Main auxiliary functions

`\__fp_parse_operand:Nw` Reads the "...", performing every computation with a precedence higher than  $\langle precedence \rangle$ , then expands to where the  $\langle operation \rangle$  is the first operation with a lower precedence, possibly `end`, and the "..." start just after the  $\langle operation \rangle$ .

(End definition for `\__fp_parse_operand:Nw`.)

`\__fp_parse_infix_+:N` If `+` has a precedence higher than the  $\langle precedence \rangle$ , cleans up a second  $\langle operand \rangle$  and finds the  $\langle operation_2 \rangle$  which follows, and expands to Otherwise expands to A similar function exists for each infix operator.

(End definition for `\__fp_parse_infix_+:N`.)

`\__fp_parse_one:Nw` Cleans up one or two operands depending on how the precedence of the next operation compares to the  $\langle precedence \rangle$ . If the following  $\langle operation \rangle$  has a precedence higher than  $\langle precedence \rangle$ , expands to and otherwise expands to

(End definition for `\__fp_parse_one:Nw`.)

## 24.3 Helpers

`\__fp_parse_expand:w` This function must always come within a `\exp:w` expansion. The  $\langle tokens \rangle$  should be the part of the expression that we have not yet read. This requires in particular closing all conditionals properly before expanding.

```
11548 \cs_new:Npn \__fp_parse_expand:w #1 { \exp_end_continue_f:w #1 }
```

(End definition for `\__fp_parse_expand:w`.)

`\_fp_parse_return_semicolon:w` This very odd function swaps its position with the following `\fi:` and removes `\__fp_parse_expand:w` normally responsible for expansion. That turns out to be useful.

```
11549 \cs_new:Npn \_fp_parse_return_semicolon:w
11550     #1 \fi: \__fp_parse_expand:w { \fi: ; #1 }
```

(End definition for `\_fp_parse_return_semicolon:w`.)

`\__fp_type_from_scan:N` Grabs the pieces of the stringified  $\langle token \rangle$  which lies after the first `s__fp`. If the  $\langle token \rangle$  does not contain that string, the result is `_?`.

`\__fp_type_from_scan:w`

```
11551 \cs_new:Npx \__fp_type_from_scan:N #1
11552 {
11553     \exp_not:N \exp_after:wN \exp_not:N \__fp_type_from_scan:w
11554     \exp_not:N \token_to_str:N #1 \exp_not:N \q_mark
11555     \tl_to_str:n { s__fp _? } \exp_not:N \q_mark \exp_not:N \q_stop
11556 }
11557 \use:x
11558 {
11559     \cs_new:Npn \exp_not:N \__fp_type_from_scan:w
11560         ##1 \tl_to_str:n { s__fp } ##2 \exp_not:N \q_mark ##3 \exp_not:N \q_stop
11561         {##2}
11562 }
```

(End definition for `\__fp_type_from_scan:N` and `\__fp_type_from_scan:w`.)

`\_fp_parse_digits_vii:N` These functions must be called within an `\__int_value:w` or `\__int_eval:w` construction. The first token which follows must be f-expanded prior to calling those functions.  
`\_fp_parse_digits_vi:N` The functions read tokens one by one, and output digits into the input stream, until  
`\_fp_parse_digits_v:N` meeting a non-digit, or up to a number of digits equal to their index. The full expansion  
`\_fp_parse_digits_iv:N` is

`\_fp_parse_digits_iii:N`

`\_fp_parse_digits_ii:N`

`\_fp_parse_digits_i:N`

`\_fp_parse_digits_:N`

$\langle digits \rangle ; \langle filling\ 0 \rangle ; \langle length \rangle$

where  $\langle filling\ 0 \rangle$  is a string of zeros such that  $\langle digits \rangle \langle filling\ 0 \rangle$  has the length given by the index of the function, and  $\langle length \rangle$  is the number of zeros in the  $\langle filling\ 0 \rangle$  string. Each function puts a digit into the input stream and calls the next function, until we find a non-digit. We are careful to pass the tested tokens through `\token_to_str:N` to normalize their category code.

```
11563 \cs_set_protected:Npn \__fp_tmp:w #1 #2 #3
11564 {
11565     \cs_new:cpn { \_fp_parse_digits_ #1 :N } ##1
11566     {
11567         \if_int_compare:w 9 < 1 \token_to_str:N ##1 \exp_stop_f:
11568         \token_to_str:N ##1 \exp_after:wN #2 \exp:w
11569     } \else:
11570         \_fp_parse_return_semicolon:w #3 ##1
```



```

11571         \fi:
11572         \__fp_parse_expand:w
11573     }
11574 }
11575 \__fp_tmp:w {vii} \__fp_parse_digits_vi:N { 0000000 ; 7 }
11576 \__fp_tmp:w {vi} \__fp_parse_digits_v:N { 000000 ; 6 }
11577 \__fp_tmp:w {v} \__fp_parse_digits_iv:N { 00000 ; 5 }
11578 \__fp_tmp:w {iv} \__fp_parse_digits_iii:N { 0000 ; 4 }
11579 \__fp_tmp:w {iii} \__fp_parse_digits_ii:N { 000 ; 3 }
11580 \__fp_tmp:w {ii} \__fp_parse_digits_i:N { 00 ; 2 }
11581 \__fp_tmp:w {i} \__fp_parse_digits_:N { 0 ; 1 }
11582 \cs_new:Npn \__fp_parse_digits_:N { ; ; 0 }

```

(End definition for \\_\_fp\_parse\_digits\_vii:N and others.)

## 24.4 Parsing one number

`\__fp_parse_one:Nw` This function finds one number, and packs the symbol which follows in an `\__fp_parse_infix...` csname. #1 is the previous *<precedence>*, and #2 the first token of the operand. We distinguish four cases: #2 is equal to `\scan_stop:` in meaning, #2 is a different control sequence, #2 is a digit, and #2 is something else (this last case is split further later). Despite the earlier *f*-expansion, #2 may still be expandable if it was protected by `\exp_not:N`, as may happen with the  $\text{\LaTeX 2}_\epsilon$  command `\protect`. Using a well placed `\reverse_if:N`, this case is sent to `\__fp_parse_one_fp:NN` which deals with it robustly.

```

11583 \cs_new:Npn \__fp_parse_one:Nw #1 #2
11584 {
11585     \if_catcode:w \scan_stop: \exp_not:N #2
11586     \exp_after:wN \if_meaning:w \exp_not:N #2 #2 \else:
11587     \exp_after:wN \reverse_if:N
11588     \fi:
11589     \if_meaning:w \scan_stop: #2
11590     \exp_after:wN \exp_after:wN
11591     \exp_after:wN \__fp_parse_one_fp:NN
11592     \else:
11593     \exp_after:wN \exp_after:wN
11594     \exp_after:wN \__fp_parse_one_register:NN
11595     \fi:
11596     \else:
11597     \if_int_compare:w 9 < 1 \token_to_str:N #2 \exp_stop_f:
11598     \exp_after:wN \exp_after:wN
11599     \exp_after:wN \__fp_parse_one_digit:NN
11600     \else:
11601     \exp_after:wN \exp_after:wN
11602     \exp_after:wN \__fp_parse_one_other:NN
11603     \fi:
11604     \fi:
11605     #1 #2
11606 }

```

(End definition for \\_\_fp\_parse\_one:Nw.)

`\__fp_parse_one_fp:NN` This function receives a *<precedence>* and a control sequence equal to `\scan_stop:` in meaning. There are three cases, dispatched using `\__fp_type_from_scan:N`.  
`\__fp_exp_after_mark_f:nw`  
`\__fp_exp_after_?_f:nw`

- `\s__fp` starts a floating point number, and we call `\__fp_exp_after_f:nw`, which f-expands after the floating point.
- `\s__fp_mark` is a premature end, we call `\__fp_exp_after_mark_f:nw`, which triggers an `fp-early-end` error.
- For a control sequence not containing `\s__fp`, we call `\__fp_exp_after_?_f:nw`, causing a `bad-variable` error.

This scheme is extensible: additional types can be added by starting the variables with a scan mark of the form `\s__fp_⟨type⟩` and defining `\__fp_exp_after_⟨type⟩_f:nw`. In all cases, we make sure that the second argument of `\__fp_parse_infix:NN` is correctly expanded. A special case only enabled in L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> is that if `\protect` is encountered then the error message mentions the control sequence which follows it rather than `\protect` itself. The test for L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> uses `\@unexpandable@protect` rather than `\protect` because `\protect` is often `\scan_stop:` hence “does not exist”.

```

11607 \cs_new:Npn \__fp_parse_one_fp:NN #1#2
11608 {
11609     \cs:w __fp_exp_after \__fp_type_from_scan:N #2 _f:nw \cs_end:
11610     {
11611         \exp_after:wN \__fp_parse_infix:NN
11612         \exp_after:wN #1 \exp:w \__fp_parse_expand:w
11613     }
11614     #2
11615 }
11616 \cs_new:Npn \__fp_exp_after_mark_f:nw #1
11617 {
11618     \__msg_kernel_expandable_error:nn { kernel } { fp-early-end }
11619     \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w #1
11620 }
11621 \cs_new:cpn { __fp_exp_after_?_f:nw } #1#2
11622 {
11623     \__msg_kernel_expandable_error:nnn { kernel } { bad-variable } {#2}
11624     \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w #1
11625 }
11626 \*package
11627 \cs_set_protected:Npn \__fp_tmp:w #1
11628 {
11629     \cs_if_exist:NT #1
11630     {
11631         \cs_gset:cpn { __fp_exp_after_?_f:nw } ##1##2
11632         {
11633             \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w ##1
11634             \str_if_eq:nnTF {##2} { \protect }
11635             {
11636                 \cs_if_eq:NNTF ##2 #1 { \use_i:nn } { \use:n }
11637                 { \__msg_kernel_expandable_error:nnn { kernel } { fp-robust-cmd } }
11638             }
11639             { \__msg_kernel_expandable_error:nnn { kernel } { bad-variable } {##2} }
11640         }
11641     }
11642 }
11643 \exp_args:Nc \__fp_tmp:w { \@unexpandable@protect }
11644 \</package>

```

(End definition for `\_fp_parse_one_fp:NN`, `\_fp_exp_after_mark_f:nw`, and `\_fp_exp_after_?_f:nw`.)

`\_fp_parse_one_register:NN` This is called whenever #2 is a control sequence other than `\scan_stop:` in meaning. We special-case `\wd`, `\ht`, `\dp` (see later) and otherwise assume that it is a register, but carefully unpack it with `\tex_the:D` within braces. First, we find the exponent following #2. Then we unpack #2 with `\tex_the:D`, and the `auxii` auxiliary distinguishes integer registers from dimensions/skips from muskips, according to the presence of a period and/or of `pt`. For integers, simply convert  $\langle value \rangle e \langle exponent \rangle$  to a floating point number with `\_fp_parse:n` (this is somewhat wasteful). For other registers, the decimal rounding provided by TeX does not accurately represent the binary value that it manipulates, so we extract this binary value as a number of scaled points with `\_int_value:w` `\_dim_eval:w`  $\langle decimal value \rangle$  pt, and use an auxiliary of `\dim_to_fp:n`, which performs the multiplication by  $2^{-16}$ , correctly rounded.

```

11645 \cs_new:Npn \_fp_parse_one_register:NN #1#2
11646 {
11647   \exp_after:wN \_fp_parse_infix_after_operand:NwN
11648   \exp_after:wN #1
11649   \exp:w \exp_end_continue_f:w
11650   \if_meaning:w \box_wd:N #2 \_fp_parse_one_register_wd:w \fi:
11651   \if_meaning:w \box_ht:N #2 \_fp_parse_one_register_wd:w \fi:
11652   \if_meaning:w \box_dp:N #2 \_fp_parse_one_register_wd:w \fi:
11653   \exp_after:wN \_fp_parse_one_register_aux:Nw
11654   \exp_after:wN #2
11655   \_int_value:w
11656   \exp_after:wN \_fp_parse_exponent:N
11657   \exp:w \_fp_parse_expand:w
11658 }
11659 \cs_new:Npx \_fp_parse_one_register_aux:Nw #1
11660 {
11661   \exp_not:n
11662   {
11663     \exp_after:wN \use:nn
11664     \exp_after:wN \_fp_parse_one_register_auxii:wwwNw
11665   }
11666   \exp_not:N \exp_after:wN { \exp_not:N \tex_the:D #1 }
11667   ; \exp_not:N \_fp_parse_one_register_dim:ww
11668   \tl_to_str:n { pt } ; \exp_not:N \_fp_parse_one_register_mu:www
11669   . \tl_to_str:n { pt } ; \exp_not:N \_fp_parse_one_register_int:www
11670   \exp_not:N \q_stop
11671 }
11672 \use:x
11673 {
11674   \cs_new:Npn \exp_not:N \_fp_parse_one_register_auxii:wwwNw
11675     ##1 . ##2 \tl_to_str:n { pt } ##3 ; ##4##5 \exp_not:N \q_stop
11676     { ##4 ##1.##2; }
11677   \cs_new:Npn \exp_not:N \_fp_parse_one_register_mu:www
11678     ##1 \tl_to_str:n { mu } ; ##2 ;
11679     { \exp_not:N \_fp_parse_one_register_dim:ww ##1 ; }
11680 }
11681 \cs_new:Npn \_fp_parse_one_register_int:www #1; #2.; #3;
11682 { \_fp_parse:n { #1 e #3 } }
11683 \cs_new:Npn \_fp_parse_one_register_dim:ww #1; #2;

```

```

11684 {
11685   \exp_after:wN \__fp_from_dim_test:ww
11686   \__int_value:w #2 \exp_after:wN ,
11687   \__int_value:w \__dim_eval:w #1 pt ;
11688 }

```

The `\wd`, `\dp`, `\ht` primitives expect an integer argument. We abuse the exponent parser to find the integer argument: simply include the exponent marker `e`. Once that “exponent” is found, use `\tex_the:D` to find the box dimension and then copy what we did for dimensions.

```

11689 \cs_new:Npn \__fp_parse_one_register_wd:w
11690   #1#2 \exp_after:wN #3#4 \__fp_parse_expand:w
11691   {
11692     #1
11693     \exp_after:wN \__fp_parse_one_register_wd:Nw
11694     #4 \__fp_parse_expand:w e
11695   }
11696 \cs_new:Npn \__fp_parse_one_register_wd:Nw #1#2 ;
11697   {
11698     \exp_after:wN \__fp_from_dim_test:ww
11699     \exp_after:wN 0 \exp_after:wN ,
11700     \__int_value:w \__dim_eval:w
11701     \exp_after:wN \use:n \exp_after:wN { \tex_the:D #1 #2 } ;
11702   }

```

(End definition for `\__fp_parse_one_register:NN` and others.)

`\__fp_parse_one_digit:NN` A digit marks the beginning of an explicit floating point number. Once the number is found, we catch the case of overflow and underflow with `\__fp_sanitize:wN`, then `\__fp_parse_infix_after_operand:NwN` expands `\__fp_parse_infix:NN` after the number we find, to wrap the following infix operator as required. Finding the number itself begins by removing leading zeros: further steps are described later.

```

11703 \cs_new:Npn \__fp_parse_one_digit:NN #1
11704   {
11705     \exp_after:wN \__fp_parse_infix_after_operand:NwN
11706     \exp_after:wN #1
11707     \exp:w \exp_end_continue_f:w
11708     \exp_after:wN \__fp_sanitize:wN
11709     \__int_value:w \__int_eval:w 0 \__fp_parse_trim_zeros:N
11710   }

```

(End definition for `\__fp_parse_one_digit:NN`.)

`\__fp_parse_one_other:NN` For this function, `#2` is a character token which is not a digit. If it is an ASCII letter, `\__fp_parse_letters:N` beyond this one and give the result to `\__fp_parse_word:Nw`. Otherwise, the character is assumed to be a prefix operator, and we build `\__fp_parse_prefix_{operator}:Nw`.

```

11711 \cs_new:Npn \__fp_parse_one_other:NN #1 #2
11712   {
11713     \if_int_compare:w
11714       \__int_eval:w
11715       ( '#2 \if_int_compare:w '#2 > 'Z - 32 \fi: ) / 26
11716     = 3 \exp_stop_f:
11717     \exp_after:wN \__fp_parse_word:Nw

```

```

11718     \exp_after:wN #1
11719     \exp_after:wN #2
11720     \exp:w \exp_after:wN \_fp_parse_letters:N
11721     \exp:w
11722   \else:
11723     \exp_after:wN \_fp_parse_prefix:NNN
11724     \exp_after:wN #1
11725     \exp_after:wN #2
11726     \cs:w
11727       \_fp_parse_prefix_ \token_to_str:N #2 :Nw
11728     \exp_after:wN
11729     \cs_end:
11730     \exp:w
11731   \fi:
11732   \_fp_parse_expand:w
11733 }

```

(End definition for \\_fp\_parse\_one\_other:NN.)

\\_fp\_parse\_word:Nw  
\\_fp\_parse\_letters:N

Finding letters is a simple recursion. Once \\_fp\_parse\_letters:N has done its job, we try to build a control sequence from the word #2. If it is a known word, then the corresponding action is taken, and otherwise, we complain about an unknown word, yield \c\_nan\_fp, and look for the following infix operator. Note that the unknown word could be a mistyped function as well as a mistyped constant, so there is no way to tell whether to look for arguments; we do not. The standard requires “inf” and “infinity” and “nan” to be recognized regardless of case, but we probably don’t want to allow every l3fp word to have an arbitrary mixture of lower and upper case, so we test and use a differently-named control sequence.

```

11734 \cs_new:Npn \_fp_parse_word:Nw #1#2;
11735 {
11736   \cs_if_exist_use:cF { \_fp_parse_word_#2:N }
11737   {
11738     \cs_if_exist_use:cF { \_fp_parse_caseless_ \str_fold_case:n {#2} :N }
11739     {
11740       \_msg_kernel_expandable_error:nnn
11741       { kernel } { unknown-fp-word } {#2}
11742       \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w
11743       \_fp_parse_infix:NN
11744     }
11745   }
11746   #1
11747 }
11748 \cs_new:Npn \_fp_parse_letters:N #1
11749 {
11750   \exp_end_continue_f:w
11751   \if_int_compare:w
11752     \if_catcode:w \scan_stop: \exp_not:N #1
11753     0
11754   \else:
11755     \_int_eval:w
11756     ( ‘#1 \if_int_compare:w ‘#1 > ‘Z - 32 \fi: ) / 26
11757   \fi:
11758   = 3 \exp_stop_f:
11759   \exp_after:wN #1

```

```

11760     \exp:w \exp_after:wN \_fp_parse_letters:N
11761     \exp:w
11762   \else:
11763     \_fp_parse_return_semicolon:w #1
11764   \fi:
11765   \_fp_parse_expand:w
11766 }

```

(End definition for \\_fp\_parse\_word:Nw and \\_fp\_parse\_letters:N.)

```

\_fp_parse_prefix:NNN
\_fp_parse_prefix_unknown:NNN

```

For this function, #1 is the previous *<precedence>*, #2 is the operator just seen, and #3 is a control sequence which implements the operator if it is a known operator. If this control sequence is `\scan_stop:`, then the operator is in fact unknown. Either the expression is missing a number there (if the operator is valid as an infix operator), and we put `nan`, wrapping the infix operator in a csname as appropriate, or the character is simply invalid in floating point expressions, and we continue looking for a number, starting again from `\_fp_parse_one:Nw`.

```

11767 \cs_new:Npn \_fp_parse_prefix:NNN #1#2#3
11768 {
11769   \if_meaning:w \scan_stop: #3
11770     \exp_after:wN \_fp_parse_prefix_unknown:NNN
11771     \exp_after:wN #2
11772   \fi:
11773   #3 #1
11774 }
11775 \cs_new:Npn \_fp_parse_prefix_unknown:NNN #1#2#3
11776 {
11777   \cs_if_exist:cTF { \_fp_parse_infix_ \token_to_str:N #1 :N }
11778   {
11779     \_msg_kernel_expandable_error:nnn
11780     { kernel } { fp-missing-number } {#1}
11781     \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w
11782     \_fp_parse_infix:NN #3 #1
11783   }
11784   {
11785     \_msg_kernel_expandable_error:nnn
11786     { kernel } { fp-unknown-symbol } {#1}
11787     \_fp_parse_one:Nw #3
11788   }
11789 }

```

(End definition for \\_fp\_parse\_prefix:NNN and \\_fp\_parse\_prefix\_unknown:NNN.)

#### 24.4.1 Numbers: trimming leading zeros

Numbers are parsed as follows: first we trim leading zeros, then if the next character is a digit, start reading a significand  $\geq 1$  with the set of functions `\_fp_parse_large...`; if it is a period, the significand is  $< 1$ ; and otherwise it is zero. In the second case, trim additional zeros after the period, counting them for an exponent shift  $\langle exp_1 \rangle < 0$ , then read the significand with the set of functions `\_fp_parse_small...`. Once the significand is read, read the exponent if `e` is present.

`\__fp_parse_trim_zeros:N` This function expects an already expanded token. It removes any leading zero, then distinguishes three cases: if the first non-zero token is a digit, then call `\__fp_parse_large:N` (the significand is  $\geq 1$ ); if it is `.`, then continue trimming zeros with `\__fp_parse_strim_zeros:N`; otherwise, our number is exactly zero, and we call `\__fp_parse_zero:` to take care of that case.

```

11790 \cs_new:Npn \__fp_parse_trim_zeros:N #1
11791 {
11792   \if:w 0 \exp_not:N #1
11793     \exp_after:wN \__fp_parse_trim_zeros:N
11794     \exp:w
11795   \else:
11796     \if:w . \exp_not:N #1
11797       \exp_after:wN \__fp_parse_strim_zeros:N
11798       \exp:w
11799     \else:
11800       \__fp_parse_trim_end:w #1
11801     \fi:
11802   \fi:
11803   \__fp_parse_expand:w
11804 }
11805 \cs_new:Npn \__fp_parse_trim_end:w #1 \fi: \fi: \__fp_parse_expand:w
11806 {
11807   \fi:
11808   \fi:
11809   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
11810     \exp_after:wN \__fp_parse_large:N
11811   \else:
11812     \exp_after:wN \__fp_parse_zero:
11813   \fi:
11814   #1
11815 }

```

(End definition for `\__fp_parse_trim_zeros:N` and `\__fp_parse_trim_end:w`.)

`\__fp_parse_strim_zeros:N` If we have removed all digits until a period (or if the body started with a period), then enter the “small\_trim” loop which outputs `-1` for each removed 0. Those `-1` are added to an integer expression waiting for the exponent. If the first non-zero token is a digit, call `\__fp_parse_small:N` (our significand is smaller than 1), and otherwise, the number is an exact zero. The name `strim` stands for “small trim”.

```

11816 \cs_new:Npn \__fp_parse_strim_zeros:N #1
11817 {
11818   \if:w 0 \exp_not:N #1
11819     - 1
11820     \exp_after:wN \__fp_parse_strim_zeros:N \exp:w
11821   \else:
11822     \__fp_parse_strim_end:w #1
11823   \fi:
11824   \__fp_parse_expand:w
11825 }
11826 \cs_new:Npn \__fp_parse_strim_end:w #1 \fi: \__fp_parse_expand:w
11827 {
11828   \fi:
11829   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:

```

```

11830     \exp_after:wN \__fp_parse_small:N
11831   \else:
11832     \exp_after:wN \__fp_parse_zero:
11833   \fi:
11834   #1
11835 }

```

(End definition for \\_\_fp\_parse\_strim\_zeros:N and \\_\_fp\_parse\_strim\_end:w.)

**\\_\_fp\_parse\_zero:** After reading a significand of 0, find any exponent, then put a sign of 1 for \\_\_fp-sanitize:wN, which removes everything and leaves an exact zero.

```

11836 \cs_new:Npn \__fp_parse_zero:
11837 {
11838   \exp_after:wN ; \exp_after:wN 1
11839   \__int_value:w \__fp_parse_exponent:N
11840 }

```

(End definition for \\_\_fp\_parse\_zero:.)

#### 24.4.2 Number: small significand

**\\_\_fp\_parse\_small:N** This function is called after we have passed the decimal separator and removed all leading zeros from the significand. It is followed by a non-zero digit (with any catcode). The goal is to read up to 16 digits. But we can't do that all at once, because \\_\_int\_value:w (which allows us to collect digits and continue expanding) can only go up to 9 digits. Hence we grab digits in two steps of 8 digits. Since #1 is a digit, read seven more digits using \\_\_fp\_parse\_digits\_vii:N. The `small_leading` auxiliary leaves those digits in the \\_\_int\_value:w, and grabs some more, or stops if there are no more digits. Then the `pack_leading` auxiliary puts the various parts in the appropriate order for the processing further up.

```

11841 \cs_new:Npn \__fp_parse_small:N #1
11842 {
11843   \exp_after:wN \__fp_parse_pack_leading:NNNNNww
11844   \__int_value:w \__int_eval:w 1 \token_to_str:N #1
11845   \exp_after:wN \__fp_parse_small_leading:wwNN
11846   \__int_value:w 1
11847   \exp_after:wN \__fp_parse_digits_vii:N
11848   \exp:w \__fp_parse_expand:w
11849 }

```

(End definition for \\_\_fp\_parse\_small:N.)

**\\_fp\_parse\_small\_leading:wwNN** We leave *<digits>* *<zeros>* in the input stream: the functions used to grab digits are such that this constitutes digits 1 through 8 of the significand. Then prepare to pack 8 more digits, with an exponent shift of zero (this shift is used in the case of a large significand). If #4 is a digit, leave it behind for the packing function, and read 6 more digits to reach a total of 15 digits: further digits are involved in the rounding. Otherwise put 8 zeros in to complete the significand, then look for an exponent.

```

11850 \cs_new:Npn \_fp_parse_small_leading:wwNN 1 #1 ; #2; #3 #4
11851 {
11852   #1 #2
11853   \exp_after:wN \_fp_parse_pack_trailing:NNNNNNww
11854   \exp_after:wN 0

```



```

11855     \__int_value:w \__int_eval:w 1
11856     \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
11857         \token_to_str:N #4
11858         \exp_after:wN \__fp_parse_small_trailing:wwNN
11859         \__int_value:w 1
11860         \exp_after:wN \__fp_parse_digits_vi:N
11861         \exp:w
11862     \else:
11863         0000 0000 \__fp_parse_exponent:Nw #4
11864     \fi:
11865     \__fp_parse_expand:w
11866 }

```

(End definition for \\_\_fp\_parse\_small\_leading:wwNN.)

\\_\_fp\_parse\_small\_trailing:wwNN Leave digits 10 to 15 (arguments #1 and #2) in the input stream. If the *<next token>* is a digit, it is the 16th digit, we keep it, then the `small_round` auxiliary considers this digit and all further digits to perform the rounding: the function expands to nothing, to +0 or to +1. Otherwise, there is no 16-th digit, so we put a 0, and look for an exponent.

```

11867 \cs_new:Npn \__fp_parse_small_trailing:wwNN 1 #1 ; #2; #3 #4
11868 {
11869     #1 #2
11870     \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
11871         \token_to_str:N #4
11872         \exp_after:wN \__fp_parse_small_round:NN
11873         \exp_after:wN #4
11874         \exp:w
11875     \else:
11876         0 \__fp_parse_exponent:Nw #4
11877     \fi:
11878     \__fp_parse_expand:w
11879 }

```

(End definition for \\_\_fp\_parse\_small\_trailing:wwNN.)

\\_\_fp\_parse\_pack\_trailing:NNNNNNww Those functions are expanded after all the digits are found, we took care of the rounding, as well as the exponent. The last argument is the exponent. The previous five arguments are 8 digits which we pack in groups of 4, and the argument before that is 1, except in the rare case where rounding lead to a carry, in which case the argument is 2. The `trailing` function has an exponent shift as its first argument, which we add to the exponent found in the `e...` syntax. If the trailing digits cause a carry, the integer expression for the leading digits is incremented (+1 in the code below). If the leading digits propagate this carry all the way up, the function `\__fp_parse_pack_carry:w` increments the exponent, and changes the significand from 0000... to 1000...: this is simple because such a carry can only occur to give rise to a power of 10.

```

11880 \cs_new:Npn \__fp_parse_pack_trailing:NNNNNNww #1 #2 #3#4#5#6 #7; #8 ;
11881 {
11882     \if_meaning:w 2 #2 + 1 \fi:
11883     ; #8 + #1 ; {#3#4#5#6} {#7};
11884 }
11885 \cs_new:Npn \__fp_parse_pack_leading:NNNNNNww #1 #2#3#4#5 #6; #7;
11886 {
11887     + #7

```

```

11888     \if_meaning:w 2 #1 \_fp_parse_pack_carry:w \fi:
11889     ; 0 {#2#3#4#5} {#6}
11890   }
11891   \cs_new:Npn \_fp_parse_pack_carry:w \fi: ; 0 #1
11892   { \fi: + 1 ; 0 {1000} }

```

(End definition for `\_fp_parse_pack_trailing:NNNNNww`, `\_fp_parse_pack_leading:NNNNNww`, and `\_fp_parse_pack_carry:w`.)

### 24.4.3 Number: large significand

Parsing a significand larger than 1 is a little bit more difficult than parsing small significands. We need to count the number of digits before the decimal separator, and add that to the final exponent. We also need to test for the presence of a dot each time we run out of digits, and branch to the appropriate `parse_small` function in those cases.

`\_fp_parse_large:N` This function is followed by the first non-zero digit of a “large” significand ( $\geq 1$ ). It is called within an integer expression for the exponent. Grab up to 7 more digits, for a total of 8 digits.

```

11893 \cs_new:Npn \_fp_parse_large:N #1
11894 {
11895   \exp_after:wN \_fp_parse_large_leading:wwNN
11896   \_int_value:w 1 \token_to_str:N #1
11897   \exp_after:wN \_fp_parse_digits_vii:N
11898   \exp:w \_fp_parse_expand:w
11899 }

```

(End definition for `\_fp_parse_large:N`.)

`\_fp_parse_large_leading:wwNN` We shift the exponent by the number of digits in #1, namely the target number, 8, minus the *number of zeros* (number of digits missing). Then prepare to pack the 8 first digits. If the *next token* is a digit, read up to 6 more digits (digits 10 to 15). If it is a period, try to grab the end of our 8 first digits, branching to the `small` functions since the number of digit does not affect the exponent anymore. Finally, if this is the end of the significand, insert the *zeros* to complete the 8 first digits, insert 8 more, and look for an exponent.

```

11900 \cs_new:Npn \_fp_parse_large_leading:wwNN 1 #1 ; #2; #3 #4
11901 {
11902   + \c__fp_half_prec_int - #3
11903   \exp_after:wN \_fp_parse_pack_leading:NNNNNww
11904   \_int_value:w \_int_eval:w 1 #1
11905   \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
11906     \exp_after:wN \_fp_parse_large_trailing:wwNN
11907     \_int_value:w 1 \token_to_str:N #4
11908     \exp_after:wN \_fp_parse_digits_vi:N
11909     \exp:w
11910   \else:
11911     \if:w . \exp_not:N #4
11912       \exp_after:wN \_fp_parse_small_leading:wwNN
11913       \_int_value:w 1
11914       \cs:w
11915         \_fp_parse_digits_
11916         \_int_to_roman:w #3
11917         :N \exp_after:wN
11918       \cs_end:

```

```

11919         \exp:w
11920     \else:
11921         #2
11922         \exp_after:wN \__fp_parse_pack_trailing:NNNNNNww
11923         \exp_after:wN 0
11924         \__int_value:w 1 0000 0000
11925         \__fp_parse_exponent:Nw #4
11926     \fi:
11927 \fi:
11928 \__fp_parse_expand:w
11929 }

```

(End definition for \\_\_fp\_parse\_large\_leading:wwNN.)

\\_\_fp\_parse\_large\_trailing:wwNN

We have just read 15 digits. If the *<next token>* is a digit, then the exponent shift caused by this block of 8 digits is 8, first argument to the `pack_trailing` function. We keep the *<digits>* and this 16-th digit, and find how this should be rounded using `\__fp_parse_large_round:NN`. Otherwise, the exponent shift is the number of *<digits>*, 7 minus the *<number of zeros>*, and we test for a decimal point. This case happens in 123451234512345.67 with exactly 15 digits before the decimal separator. Then branch to the appropriate `small` auxiliary, grabbing a few more digits to complement the digits we already grabbed. Finally, if this is truly the end of the significand, look for an exponent after using the *<zeros>* and providing a 16-th digit of 0.

```

11930 \cs_new:Npn \__fp_parse_large_trailing:wwNN 1 #1 ; #2; #3 #4
11931 {
11932     \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
11933         \exp_after:wN \__fp_parse_pack_trailing:NNNNNNww
11934         \exp_after:wN \c__fp_half_prec_int
11935         \__int_value:w \__int_eval:w 1 #1 \token_to_str:N #4
11936         \exp_after:wN \__fp_parse_large_round:NN
11937         \exp_after:wN #4
11938         \exp:w
11939     \else:
11940         \exp_after:wN \__fp_parse_pack_trailing:NNNNNNww
11941         \__int_value:w \__int_eval:w 7 - #3 \exp_stop_f:
11942         \__int_value:w \__int_eval:w 1 #1
11943         \if:w . \exp_not:N #4
11944             \exp_after:wN \__fp_parse_small_trailing:wwNN
11945             \__int_value:w 1
11946             \cs:w
11947                 __fp_parse_digits_
11948                 \__int_to_roman:w #3
11949                 :N \exp_after:wN
11950             \cs_end:
11951             \exp:w
11952         \else:
11953             #2 0 \__fp_parse_exponent:Nw #4
11954         \fi:
11955     \fi:
11956     \__fp_parse_expand:w
11957 }

```

(End definition for \\_\_fp\_parse\_large\_trailing:wwNN.)

#### 24.4.4 Number: beyond 16 digits, rounding

`\__fp_parse_round_loop:N` This loop is called when rounding a number (whether the mantissa is small or large).  
`\__fp_parse_round_up:N` It should appear in an integer expression. This function reads digits one by one, until reaching a non-digit, and adds 1 to the integer expression for each digit. If all digits found are 0, the function ends the expression by ;0, otherwise by ;1. This is done by switching the loop to `round_up` at the first non-zero digit, thus we avoid to test whether digits are 0 or not once we see a first non-zero digit.

```

11958 \cs_new:Npn \__fp_parse_round_loop:N #1
11959 {
11960   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
11961     + 1
11962     \if:w 0 \token_to_str:N #1
11963       \exp_after:wN \__fp_parse_round_loop:N
11964       \exp:w
11965     \else:
11966       \exp_after:wN \__fp_parse_round_up:N
11967       \exp:w
11968     \fi:
11969   \else:
11970     \__fp_parse_return_semicolon:w 0 #1
11971   \fi:
11972   \__fp_parse_expand:w
11973 }
11974 \cs_new:Npn \__fp_parse_round_up:N #1
11975 {
11976   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
11977     + 1
11978     \exp_after:wN \__fp_parse_round_up:N
11979     \exp:w
11980   \else:
11981     \__fp_parse_return_semicolon:w 1 #1
11982   \fi:
11983   \__fp_parse_expand:w
11984 }

```

(End definition for `\__fp_parse_round_loop:N` and `\__fp_parse_round_up:N`.)

`\__fp_parse_round_after:wN` After the loop `\__fp_parse_round_loop:N`, this function fetches an exponent with `\__fp_parse_exponent:N`, and combines it with the number of digits counted by `\__fp_parse_round_loop:N`. At the same time, the result 0 or 1 is added to the surrounding integer expression.

```

11985 \cs_new:Npn \__fp_parse_round_after:wN #1; #2
11986 {
11987   + #2 \exp_after:wN ;
11988   \__int_value:w \__int_eval:w #1 + \__fp_parse_exponent:N
11989 }

```

(End definition for `\__fp_parse_round_after:wN`.)

`\__fp_parse_small_round:NN` Here, #1 is the digit that we are currently rounding (we only care whether it is even or odd).  
`\__fp_parse_round_after:wN` If #2 is not a digit, then fetch an exponent and expand to ;*exponent* only. Otherwise, we expand to +0 or +1, then ;*exponent*. To decide which, call `\__fp_round_s:NNNw` to know whether to round up, giving it as arguments a sign 0 (all explicit

numbers are positive), the digit #1 to round, the first following digit #2, and either +0 or +1 depending on whether the following digits are all zero or not. This last argument is obtained by `\__fp_parse_round_loop:N`, whose number of digits we discard by multiplying it by 0. The exponent which follows the number is also fetched by `\__fp_parse_round_after:wN`.

```

11990 \cs_new:Npn \__fp_parse_small_round:NN #1#2
11991 {
11992   \if_int_compare:w 9 < 1 \token_to_str:N #2 \exp_stop_f:
11993   +
11994   \exp_after:wN \__fp_round_s:NNNw
11995   \exp_after:wN 0
11996   \exp_after:wN #1
11997   \exp_after:wN #2
11998   \__int_value:w \__int_eval:w
11999   \exp_after:wN \__fp_parse_round_after:wN
12000   \__int_value:w \__int_eval:w 0 * \__int_eval:w 0
12001   \exp_after:wN \__fp_parse_round_loop:N
12002   \exp:w
12003   \else:
12004     \__fp_parse_exponent:Nw #2
12005   \fi:
12006   \__fp_parse_expand:w
12007 }

```

(End definition for `\__fp_parse_small_round:NN` and `\__fp_parse_round_after:wN`.)

```

\__fp_parse_large_round:NN
  \__fp_parse_large_round_test:NN
  \__fp_parse_large_round_aux:wNN

```

Large numbers are harder to round, as there may be a period in the way. Again, #1 is the digit that we are currently rounding (we only care whether it is even or odd). If there are no more digits (#2 is not a digit), then we must test for a period: if there is one, then switch to the rounding function for small significands, otherwise fetch an exponent. If there are more digits (#2 is a digit), then round, checking with `\__fp_parse_round_loop:N` if all further digits vanish, or some are non-zero. This loop is not enough, as it is stopped by a period. After the loop, the `aux` function tests for a period: if it is present, then we must continue looking for digits, this time discarding the number of digits we find.

```

12008 \cs_new:Npn \__fp_parse_large_round:NN #1#2
12009 {
12010   \if_int_compare:w 9 < 1 \token_to_str:N #2 \exp_stop_f:
12011   +
12012   \exp_after:wN \__fp_round_s:NNNw
12013   \exp_after:wN 0
12014   \exp_after:wN #1
12015   \exp_after:wN #2
12016   \__int_value:w \__int_eval:w
12017   \exp_after:wN \__fp_parse_large_round_aux:wNN
12018   \__int_value:w \__int_eval:w 1
12019   \exp_after:wN \__fp_parse_round_loop:N
12020   \else: %^^A could be dot, or e, or other
12021     \exp_after:wN \__fp_parse_large_round_test:NN
12022     \exp_after:wN #1
12023     \exp_after:wN #2
12024   \fi:
12025 }

```

```

12026 \cs_new:Npn \__fp_parse_large_round_test:NN #1#2
12027 {
12028   \if:w . \exp_not:N #2
12029     \exp_after:wN \__fp_parse_small_round:NN
12030     \exp_after:wN #1
12031     \exp:w
12032   \else:
12033     \__fp_parse_exponent:Nw #2
12034   \fi:
12035   \__fp_parse_expand:w
12036 }
12037 \cs_new:Npn \__fp_parse_large_round_aux:wNN #1 ; #2 #3
12038 {
12039   + #2
12040   \exp_after:wN \__fp_parse_round_after:wN
12041   \__int_value:w \__int_eval:w #1
12042   \if:w . \exp_not:N #3
12043     + 0 * \__int_eval:w 0
12044     \exp_after:wN \__fp_parse_round_loop:N
12045     \exp:w \exp_after:wN \__fp_parse_expand:w
12046   \else:
12047     \exp_after:wN ;
12048     \exp_after:wN 0
12049     \exp_after:wN #3
12050   \fi:
12051 }

```

(End definition for `\__fp_parse_large_round:NN`, `\__fp_parse_large_round_test:NN`, and `\__fp_parse_large_round_aux:wNN`.)

#### 24.4.5 Number: finding the exponent

Expansion is a little bit tricky here, in part because we accept input where multiplication is implicit.

```

\@@_parse:n { 3.2 erf(0.1) }
\@@_parse:n { 3.2 e\l_my_int }
\@@_parse:n { 3.2 \c_pi_fp }

```

The first case indicates that just looking one character ahead for an “e” is not enough, since we would mistake the function `erf` for an exponent of “rf”. An alternative would be to look two tokens ahead and check if what follows is a sign or a digit, considering in that case that we must be finding an exponent. But taking care of the second case requires that we unpack registers after `e`. However, blindly expanding the two tokens ahead completely would break the third example (unpacking is even worse). Indeed, in the course of reading `3.2`, `\c_pi_fp` is expanded to `\s__fp \__fp_chk:w 1 0 {-1} {3141}` ... ; and `\s__fp` stops the expansion. Expanding two tokens ahead would then force the expansion of `\__fp_chk:w` (despite it being protected), and that function tries to produce an error.

What can we do? Really, the reason why this last case breaks is that just as `TEX` does, we should read ahead as little as possible. Here, the only case where there may be an exponent is if the first token ahead is `e`. Then we expand (and possibly unpack) the second token.

`\__fp_parse_exponent:Nw` This auxiliary is convenient to smuggle some material through `\fi:` ending conditional processing. We place those `\fi:` (argument #2) at a very odd place because this allows us to insert `\__int_eval:w ...` there if needed.

```

12052 \cs_new:Npn \__fp_parse_exponent:Nw #1 #2 \__fp_parse_expand:w
12053 {
12054     \exp_after:wN ;
12055     \__int_value:w #2 \__fp_parse_exponent:N #1
12056 }

```

*(End definition for \\_\_fp\_parse\_exponent:Nw.)*

`\__fp_parse_exponent:N` This function should be called within an `\__int_value:w` expansion (or within an integer expression). It leaves digits of the exponent behind it in the input stream, and terminates the expansion with a semicolon. If there is no `e`, leave an exponent of 0. If there is an `e`, expand the next token to run some tests on it. The first rough test is that if the character code of #1 is greater than that of 9 (largest code valid for an exponent, less than any code valid for an identifier), there was in fact no exponent; otherwise, we search for the sign of the exponent.

```

12057 \cs_new:Npn \__fp_parse_exponent:N #1
12058 {
12059     \if:w e \exp_not:N #1
12060         \exp_after:wN \__fp_parse_exponent_aux:N
12061         \exp:w
12062     \else:
12063         0 \__fp_parse_return_semicolon:w #1
12064     \fi:
12065     \__fp_parse_expand:w
12066 }
12067 \cs_new:Npn \__fp_parse_exponent_aux:N #1
12068 {
12069     \if_int_compare:w \if_catcode:w \scan_stop: \exp_not:N #1
12070         0 \else: '#1 \fi: > '9 \exp_stop_f:
12071         0 \exp_after:wN ; \exp_after:wN e
12072     \else:
12073         \exp_after:wN \__fp_parse_exponent_sign:N
12074     \fi:
12075     #1
12076 }

```

*(End definition for \\_\_fp\_parse\_exponent:N and \\_\_fp\_parse\_exponent\_aux:N.)*

`\__fp_parse_exponent_sign:N` Read signs one by one (if there is any).

```

12077 \cs_new:Npn \__fp_parse_exponent_sign:N #1
12078 {
12079     \if:w + \if:w - \exp_not:N #1 + \fi: \token_to_str:N #1
12080         \exp_after:wN \__fp_parse_exponent_sign:N
12081         \exp:w \exp_after:wN \__fp_parse_expand:w
12082     \else:
12083         \exp_after:wN \__fp_parse_exponent_body:N
12084         \exp_after:wN #1
12085     \fi:
12086 }

```

*(End definition for \\_\_fp\_parse\_exponent\_sign:N.)*

`\__fp_parse_exponent_body:N` An exponent can be an explicit integer (most common case), or various other things (most of which are invalid).

```

12087 \cs_new:Npn \__fp_parse_exponent_body:N #1
12088 {
12089   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
12090     \token_to_str:N #1
12091     \exp_after:wN \__fp_parse_exponent_digits:N
12092     \exp:w
12093   \else:
12094     \__fp_parse_exponent_keep:NTF #1
12095     { \__fp_parse_return_semicolon:w #1 }
12096     {
12097       \exp_after:wN ;
12098       \exp:w
12099     }
12100   \fi:
12101   \__fp_parse_expand:w
12102 }

```

*(End definition for \\_\_fp\_parse\_exponent\_body:N.)*

`\__fp_parse_exponent_digits:N` Read digits one by one, and leave them behind in the input stream. When finding a non-digit, stop, and insert a semicolon. Note that we do not check for overflow of the exponent, hence there can be a T<sub>E</sub>X error. It is mostly harmless, except when parsing 0e9876543210, which should be a valid representation of 0, but is not.

```

12103 \cs_new:Npn \__fp_parse_exponent_digits:N #1
12104 {
12105   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
12106     \token_to_str:N #1
12107     \exp_after:wN \__fp_parse_exponent_digits:N
12108     \exp:w
12109   \else:
12110     \__fp_parse_return_semicolon:w #1
12111   \fi:
12112   \__fp_parse_expand:w
12113 }

```

*(End definition for \\_\_fp\_parse\_exponent\_digits:N.)*

`\__fp_parse_exponent_keep:N` This is the last building block for parsing exponents. The argument #1 is already fully expanded, and neither + nor - nor a digit. It can be:

- `\s__fp`, marking the start of an internal floating point, invalid here;
- another control sequence equal to `\relax`, probably a bad variable;
- a register: in this case we make sure that it is an integer register, not a dimension;
- a character other than +, - or digits, again, an error.

```

12114 \prg_new_conditional:Npnn \__fp_parse_exponent_keep:N #1 { TF }
12115 {
12116   \if_catcode:w \scan_stop: \exp_not:N #1
12117   \if_meaning:w \scan_stop: #1
12118   \if_int_compare:w

```



```

12119         \_str_if_eq_x:nn { \s__fp } { \exp_not:N #1 }
12120         = 0 \exp_stop_f:
12121     0
12122     \_msg_kernel_expandable_error:nnn
12123     { kernel } { fp-after-e } { floating-point~ }
12124     \prg_return_true:
12125 \else:
12126     0
12127     \_msg_kernel_expandable_error:nnn
12128     { kernel } { bad-variable } { #1 }
12129     \prg_return_false:
12130 \fi:
12131 \else:
12132     \if_int_compare:w
12133         \_str_if_eq_x:nn { \_int_value:w #1 } { \tex_the:D #1 }
12134         = 0 \exp_stop_f:
12135         \_int_value:w #1
12136     \else:
12137         0
12138         \_msg_kernel_expandable_error:nnn
12139         { kernel } { fp-after-e } { dimension~#1 }
12140     \fi:
12141     \prg_return_false:
12142 \fi:
12143 \else:
12144     0
12145     \_msg_kernel_expandable_error:nnn
12146     { kernel } { fp-missing } { exponent }
12147     \prg_return_true:
12148 \fi:
12149 }

```

(End definition for \\_fp\_parse\_exponent\_keep:NTF.)

## 24.5 Constants, functions and prefix operators

### 24.5.1 Prefix operators

\\_fp\_parse\_prefix+:Nw A unary + does nothing: we should continue looking for a number.

```

12150 \cs_new_eq:cN { \_fp_parse_prefix+:Nw } \_fp_parse_one:Nw

```

(End definition for \\_fp\_parse\_prefix+:Nw.)

\\_fp\_parse\_apply\_unary:NNNwN Here, #1 is a precedence, #2 is some extra data used by some functions, #3 is *e.g.*, \\_fp\_sin\_o:w, and expands once after the calculation, #4 is the operand, and #5 is a \\_fp\_parse\_infix\_...:N function. We feed the data #2, and the argument #4, to the function #3, which expands \exp:w thus the infix function #5.

This is redefined in l3fp-extras.

```

12151 \cs_new:Npn \_fp_parse_apply_unary:NNNwN #1#2#3#4#5
12152 {
12153     #3 #2 #4 @
12154     \exp:w \exp_end_continue_f:w #5 #1
12155 }

```

(End definition for \\_fp\_parse\_apply\_unary:NNNwN.)

`\__fp_parse_prefix_-:Nw` The unary `-` and boolean not are harder: we parse the operand using a precedence equal  
`\__fp_parse_prefix_!:Nw` to the maximum of the previous precedence `##1` and the precedence `\c__fp_prec_not_-`  
`int` of the unary operator, then call the appropriate `\__fp_⟨operation⟩_o:w` function,  
where the `⟨operation⟩` is `set_sign` or `not`.

```

12156 \cs_set_protected:Npn \__fp_tmp:w #1#2#3#4
12157 {
12158   \cs_new:cpn { __fp_parse_prefix_ #1 :Nw } ##1
12159   {
12160     \exp_after:wN \__fp_parse_apply_unary:NNNwN
12161     \exp_after:wN ##1
12162     \exp_after:wN #4
12163     \exp_after:wN #3
12164     \exp:w
12165     \if_int_compare:w #2 < ##1
12166       \__fp_parse_operand:Nw ##1
12167     \else:
12168       \__fp_parse_operand:Nw #2
12169     \fi:
12170     \__fp_parse_expand:w
12171   }
12172 }
12173 \__fp_tmp:w - \c__fp_prec_not_int \__fp_set_sign_o:w 2
12174 \__fp_tmp:w ! \c__fp_prec_not_int \__fp_not_o:w ?

```

(End definition for `\__fp_parse_prefix_-:Nw` and `\__fp_parse_prefix_!:Nw`.)

`\__fp_parse_prefix_:Nw` Numbers which start with a decimal separator (a period) end up here. Of course, we do  
not look for an operand, but for the rest of the number. This function is very similar to  
`\__fp_parse_one_digit:NN` but calls `\__fp_parse_strim_zeros:N` to trim zeros after  
the decimal point, rather than the `trim_zeros` function for zeros before the decimal  
point.

```

12175 \cs_new:cpn { __fp_parse_prefix_:Nw } #1
12176 {
12177   \exp_after:wN \__fp_parse_infix_after_operand:NwN
12178   \exp_after:wN #1
12179   \exp:w \exp_end_continue_f:w
12180   \exp_after:wN \__fp_sanitize:wN
12181   \__int_value:w \__int_eval:w 0 \__fp_parse_strim_zeros:N
12182 }

```

(End definition for `\__fp_parse_prefix_:Nw`.)

`\__fp_parse_prefix(:Nw` The left parenthesis is treated as a unary prefix operator because it appears in exactly  
`\__fp_parse_lparen_after:NwN` the same settings. Commas are allowed if the previous precedence is 16 (function with  
multiple arguments). In this case, find an operand using the precedence 1; otherwise the  
precedence 0. Once the operand is found, the `lparen_after` auxiliary makes sure that  
there was a closing parenthesis (otherwise it complains), and leaves in the input stream  
the array it found as an operand, fetching the following infix operator.

```

12183 \cs_new:cpn { __fp_parse_prefix(:Nw } #1
12184 {
12185   \exp_after:wN \__fp_parse_lparen_after:NwN
12186   \exp_after:wN #1
12187   \exp:w

```

```

12188     \if_int_compare:w #1 = \c__fp_prec_funcii_int
12189     \__fp_parse_operand:Nw \c__fp_prec_comma_int
12190     \else:
12191     \__fp_parse_operand:Nw \c__fp_prec_paren_int
12192     \fi:
12193     \__fp_parse_expand:w
12194 }
12195 \cs_new:Npx \__fp_parse_lparen_after:NwN #1#2 @ #3
12196 {
12197     \exp_not:N \token_if_eq_meaning:NNTF #3
12198     \exp_not:c { __fp_parse_infix_):N }
12199     {
12200         \exp_not:N \__fp_exp_after_array_f:w #2 \s__fp_stop
12201         \exp_not:N \exp_after:wN
12202         \exp_not:N \__fp_parse_infix:NN
12203         \exp_not:N \exp_after:wN #1
12204         \exp_not:N \exp:w
12205         \exp_not:N \__fp_parse_expand:w
12206     }
12207     {
12208         \exp_not:N \__msg_kernel_expandable_error:nnn
12209         { kernel } { fp-missing } { ) }
12210         #2 @
12211         \exp_not:N \use_none:n #3
12212     }
12213 }

```

(End definition for \\_\_fp\_parse\_prefix\_(:Nw and \\_\_fp\_parse\_lparen\_after:NwN.)

\\_\_fp\_parse\_prefix\_):Nw

The right parenthesis can appear as unary prefixes when arguments of a multi-argument function end with a comma, or when there is no argument, as in `max(1,2,)` or in `rand()`. In single-argument functions (precedence 0 rather than 1) forbid this.

```

12214 \cs_new:cpn { __fp_parse_prefix_):Nw } #1
12215 {
12216     \if_int_compare:w #1 = \c__fp_prec_comma_int
12217     \else:
12218     \__msg_kernel_expandable_error:nnn
12219     { kernel } { fp-missing-number } { ) }
12220     \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w
12221     \fi:
12222     \__fp_parse_infix:NN #1 )
12223 }

```

(End definition for \\_\_fp\_parse\_prefix\_):Nw.)

## 24.5.2 Constants

\\_\_fp\_parse\_word\_inf:N  
\\_\_fp\_parse\_word\_nan:N  
\\_\_fp\_parse\_word\_pi:N  
\\_\_fp\_parse\_word\_deg:N  
\\_\_fp\_parse\_word\_true:N  
\\_\_fp\_parse\_word\_false:N

Some words correspond to constant floating points. The floating point constant is left as a result of \\_\_fp\_parse\_one:Nw after expanding \\_\_fp\_parse\_infix:NN.

```

12224 \cs_set_protected:Npn \__fp_tmp:w #1 #2
12225 {
12226     \cs_new:cpn { __fp_parse_word_#1:N }
12227     { \exp_after:wN #2 \exp:w \exp_end_continue_f:w \__fp_parse_infix:NN }
12228 }

```

```

12229 \__fp_tmp:w { inf } \c_inf_fp
12230 \__fp_tmp:w { nan } \c_nan_fp
12231 \__fp_tmp:w { pi } \c_pi_fp
12232 \__fp_tmp:w { deg } \c_one_degree_fp
12233 \__fp_tmp:w { true } \c_one_fp
12234 \__fp_tmp:w { false } \c_zero_fp

```

(End definition for \\_\_fp\_parse\_word\_inf:N and others.)

```

\__fp_parse_caseless_inf:N
\__fp_parse_caseless_infinity:N
\__fp_parse_caseless_nan:N

```

Copies of \\_\_fp\_parse\_word\_...:N commands, to allow arbitrary case as mandated by the standard.

```

12235 \cs_new_eq:NN \__fp_parse_caseless_inf:N \__fp_parse_word_inf:N
12236 \cs_new_eq:NN \__fp_parse_caseless_infinity:N \__fp_parse_word_inf:N
12237 \cs_new_eq:NN \__fp_parse_caseless_nan:N \__fp_parse_word_nan:N

```

(End definition for \\_\_fp\_parse\_caseless\_inf:N, \\_\_fp\_parse\_caseless\_infinity:N, and \\_\_fp\_parse\_caseless\_nan:N.)

```

\__fp_parse_word_pt:N
\__fp_parse_word_in:N
\__fp_parse_word_pc:N
\__fp_parse_word_cm:N
\__fp_parse_word_mm:N
\__fp_parse_word_dd:N
\__fp_parse_word_cc:N
\__fp_parse_word_nd:N
\__fp_parse_word_nc:N
\__fp_parse_word_bp:N
\__fp_parse_word_sp:N

```

Dimension units are also floating point constants but their value is not stored as a floating point constant. We give the values explicitly here.

```

12238 \cs_set_protected:Npn \__fp_tmp:w #1 #2
12239 {
12240   \cs_new:cpn { __fp_parse_word_#1:N }
12241   {
12242     \__fp_exp_after_f:nw { \__fp_parse_infix:NN }
12243     \s__fp \__fp_chk:w 10 #2 ;
12244   }
12245 }
12246 \__fp_tmp:w {pt} { {1} {1000} {0000} {0000} {0000} }
12247 \__fp_tmp:w {in} { {2} {7227} {0000} {0000} {0000} }
12248 \__fp_tmp:w {pc} { {2} {1200} {0000} {0000} {0000} }
12249 \__fp_tmp:w {cm} { {2} {2845} {2755} {9055} {1181} }
12250 \__fp_tmp:w {mm} { {1} {2845} {2755} {9055} {1181} }
12251 \__fp_tmp:w {dd} { {1} {1070} {0085} {6496} {0630} }
12252 \__fp_tmp:w {cc} { {2} {1284} {0102} {7795} {2756} }
12253 \__fp_tmp:w {nd} { {1} {1066} {9783} {4645} {6693} }
12254 \__fp_tmp:w {nc} { {2} {1280} {3740} {1574} {8031} }
12255 \__fp_tmp:w {bp} { {1} {1003} {7500} {0000} {0000} }
12256 \__fp_tmp:w {sp} { {-4} {1525} {8789} {0625} {0000} }

```

(End definition for \\_\_fp\_parse\_word\_pt:N and others.)

```

\__fp_parse_word_em:N
\__fp_parse_word_ex:N

```

The font-dependent units em and ex must be evaluated on the fly. We reuse an auxiliary of \dim\_to\_fp:n.

```

12257 \tl_map_inline:nn { {em} {ex} }
12258 {
12259   \cs_new:cpn { __fp_parse_word_#1:N }
12260   {
12261     \exp_after:wN \__fp_from_dim_test:ww
12262     \exp_after:wN 0 \exp_after:wN ,
12263     \__int_value:w \__dim_eval:w 1 #1 \exp_after:wN ;
12264     \exp:w \exp_end_continue_f:w \__fp_parse_infix:NN
12265   }
12266 }

```

(End definition for \\_\_fp\_parse\_word\_em:N and \\_\_fp\_parse\_word\_ex:N.)

### 24.5.3 Functions

```

\__fp_parse_unary_function:NNN
\__fp_parse_function:NNN
12267 \cs_new:Npn \__fp_parse_unary_function:NNN #1#2#3
12268 {
12269   \exp_after:wN \__fp_parse_apply_unary:NNNwN
12270   \exp_after:wN #3
12271   \exp_after:wN #2
12272   \exp_after:wN #1
12273   \exp:w
12274   \__fp_parse_operand:Nw \c__fp_prec_func_int \__fp_parse_expand:w
12275 }
12276 \cs_new:Npn \__fp_parse_function:NNN #1#2#3
12277 {
12278   \exp_after:wN \__fp_parse_apply_unary:NNNwN
12279   \exp_after:wN #3
12280   \exp_after:wN #2
12281   \exp_after:wN #1
12282   \exp:w
12283   \__fp_parse_operand:Nw \c__fp_prec_funcii_int \__fp_parse_expand:w
12284 }

```

(End definition for `\__fp_parse_unary_function:NNN` and `\__fp_parse_function:NNN`.)

### 24.6 Main functions

`\__fp_parse:n` Start an `\exp:w` expansion so that `\__fp_parse:n` expands in two steps. The `\__fp_parse_operand:Nw` function performs computations until reaching an operation with precedence `\c__fp_prec_end_int` or less, namely, the end of the expression. The marker `\s__fp_mark` indicates that the next token is an already parsed version of an infix operator, and `\__fp_parse_infix_end:N` has infinitely negative precedence. Finally, clean up a (well-defined) set of extra tokens and stop the initial expansion with `\exp_end:`.

```

12285 \cs_new:Npn \__fp_parse:n #1
12286 {
12287   \exp:w
12288   \exp_after:wN \__fp_parse_after:ww
12289   \exp:w
12290   \__fp_parse_operand:Nw \c__fp_prec_end_int
12291   \__fp_parse_expand:w #1
12292   \s__fp_mark \__fp_parse_infix_end:N
12293   \s__fp_stop
12294 }
12295 \cs_new:Npn \__fp_parse_after:ww
12296   #1@ \__fp_parse_infix_end:N \s__fp_stop
12297 { \exp_end: #1 }

```

(End definition for `\__fp_parse:n` and `\__fp_parse_after:ww`.)

```

\__fp_parse_o:n
12298 \cs_new:Npn \__fp_parse_o:n #1
12299 {
12300   \exp_after:wN \exp_after:wN
12301   \exp_after:wN \__fp_exp_after_o:w
12302   \__fp_parse:n {#1}

```

12303 }

(End definition for \\_fp\_parse\_o:n.)

\\_fp\_parse\_operand:Nw This is just a shorthand which sets up both \\_fp\_parse\_continue:NwN and \\_fp\_parse\_one:Nw with the same precedence. Note the trailing \exp:w.  
\\_fp\_parse\_continue:NwN

```
12304 \cs_new:Npn \_fp_parse_operand:Nw #1
12305 {
12306   \exp_end_continue_f:w
12307   \exp_after:wN \_fp_parse_continue:NwN
12308   \exp_after:wN #1
12309   \exp:w \exp_end_continue_f:w
12310   \exp_after:wN \_fp_parse_one:Nw
12311   \exp_after:wN #1
12312   \exp:w
12313 }
12314 \cs_new:Npn \_fp_parse_continue:NwN #1 #2 @ #3 { #3 #1 #2 @ }
```

(End definition for \\_fp\_parse\_operand:Nw and \\_fp\_parse\_continue:NwN.)

\\_fp\_parse\_apply\_binary:NwNwN Receives  $\langle precedence \rangle \langle operand_1 \rangle @ \langle operation \rangle \langle operand_2 \rangle @ \langle infix command \rangle$ . Builds the appropriate call to the  $\langle operation \rangle$  #3.

This is redefined in l3fp-extras.

```
12315 \cs_new:Npn \_fp_parse_apply_binary:NwNwN #1 #2@ #3 #4@ #5
12316 {
12317   \exp_after:wN \_fp_parse_continue:NwN
12318   \exp_after:wN #1
12319   \exp:w \exp_end_continue_f:w \cs:w \_fp_#3_o:ww \cs_end: #2 #4
12320   \exp:w \exp_end_continue_f:w #5 #1
12321 }
```

(End definition for \\_fp\_parse\_apply\_binary:NwNwN.)

## 24.7 Infix operators

\\_fp\_parse\_infix\_after\_operand:NwN

```
12322 \cs_new:Npn \_fp_parse_infix_after_operand:NwN #1 #2;
12323 {
12324   \_fp_exp_after_f:nw { \_fp_parse_infix:NN #1 }
12325   #2;
12326 }
12327 \cs_new:Npn \_fp_parse_infix:NN #1 #2
12328 {
12329   \if_catcode:w \scan_stop: \exp_not:N #2
12330   \if_int_compare:w
12331     \_str_if_eq_x:nn { \s_fp_mark } { \exp_not:N #2 }
12332     = 0 \exp_stop_f:
12333     \exp_after:wN \exp_after:wN
12334     \exp_after:wN \_fp_parse_infix_mark:NNN
12335   \else:
12336     \exp_after:wN \exp_after:wN
12337     \exp_after:wN \_fp_parse_infix_juxtapose:N
12338   \fi:
12339   \else:
```

```

12340         \if_int_compare:w
12341             \__int_eval:w
12342             ( '#2 \if_int_compare:w '#2 > 'Z - 32 \fi: ) / 26
12343             = 3 \exp_stop_f:
12344             \exp_after:wN \exp_after:wN
12345             \exp_after:wN \__fp_parse_infix_juxtapose:N
12346         \else:
12347             \exp_after:wN \__fp_parse_infix_check:NNN
12348             \cs:w
12349             __fp_parse_infix_ \token_to_str:N #2 :N
12350             \exp_after:wN \exp_after:wN \exp_after:wN
12351         \cs_end:
12352         \fi:
12353     \fi:
12354     #1
12355     #2
12356 }
12357 \cs_new:Npx \__fp_parse_infix_check:NNN #1#2#3
12358 {
12359     \exp_not:N \if_meaning:w \scan_stop: #1
12360     \exp_not:N \__msg_kernel_expandable_error:nnn
12361     { kernel } { fp-missing } { * }
12362     \exp_not:N \exp_after:wN
12363     \exp_not:c { __fp_parse_infix_*:N }
12364     \exp_not:N \exp_after:wN #2
12365     \exp_not:N \exp_after:wN #3
12366     \exp_not:N \else:
12367         \exp_not:N \exp_after:wN #1
12368         \exp_not:N \exp_after:wN #2
12369         \exp_not:N \exp:w
12370         \exp_not:N \exp_after:wN
12371         \exp_not:N \__fp_parse_expand:w
12372     \exp_not:N \fi:
12373 }

```

(End definition for \\_\_fp\_parse\_infix\_after\_operand:NwN.)

### 24.7.1 Closing parentheses and commas

\\_\_fp\_parse\_infix\_mark:NNN As an infix operator, \s\_\_fp\_mark means that the next token (#3) has already gone through \\_\_fp\_parse\_infix:NN and should be provided the precedence #1. The scan mark #2 is discarded.

```

12374 \cs_new:Npn \__fp_parse_infix_mark:NNN #1#2#3 { #3 #1 }

```

(End definition for \\_\_fp\_parse\_infix\_mark:NNN.)

\\_\_fp\_parse\_infix\_end:N This one is a little bit odd: force every previous operator to end, regardless of the precedence.

```

12375 \cs_new:Npn \__fp_parse_infix_end:N #1
12376 { @ \use_none:n \__fp_parse_infix_end:N }

```

(End definition for \\_\_fp\_parse\_infix\_end:N.)

\\_fp\_parse\_infix\_):N This is very similar to \\_fp\_parse\_infix\_end:N, complaining about an extra closing parenthesis if the previous operator was the beginning of the expression.

```

12377 \cs_set_protected:Npn \_fp_tmp:w #1
12378 {
12379   \cs_new:Npn #1 ##1
12380   {
12381     \if_int_compare:w ##1 < \c__fp_prec_paren_int
12382     \_msg_kernel_expandable_error:nnn { kernel } { fp-extra } { ) }
12383     \exp_after:wN \_fp_parse_infix:NN
12384     \exp_after:wN ##1
12385     \exp:w \exp_after:wN \_fp_parse_expand:w
12386   \else:
12387     \exp_after:wN @
12388     \exp_after:wN \use_none:n
12389     \exp_after:wN #1
12390   \fi:
12391 }
12392 }
12393 \exp_args:Nc \_fp_tmp:w { \_fp_parse_infix_):N }

```

(End definition for \\_fp\_parse\_infix\_):N.)

\\_fp\_parse\_infix\_,:N \\_fp\_,\_o:ww is a complicated way of replacing any number of floating point arguments by nan.

```

\_fp_parse_infix_comma:w
\_fp_parse_infix_comma_error:w
\_fp_,_o:ww
12394 \cs_set_protected:Npn \_fp_tmp:w #1
12395 {
12396   \cs_new:Npn #1 ##1
12397   {
12398     \if_int_compare:w ##1 > \c__fp_prec_comma_int
12399     \exp_after:wN @
12400     \exp_after:wN \use_none:n
12401     \exp_after:wN #1
12402   \else:
12403     \if_int_compare:w ##1 < \c__fp_prec_comma_int
12404     \_fp_parse_infix_comma_error:w
12405   \fi:
12406     \exp_after:wN \_fp_parse_infix_comma:w
12407     \exp:w \_fp_parse_operand:Nw \c__fp_prec_comma_int
12408     \exp_after:wN \_fp_parse_expand:w
12409   \fi:
12410 }
12411 }
12412 \exp_args:Nc \_fp_tmp:w { \_fp_parse_infix_,:N }
12413 \cs_new:Npn \_fp_parse_infix_comma:w #1 @
12414 { #1 @ \use_none:n }
12415 \cs_new:Npn \_fp_parse_infix_comma_error:w #1 \exp:w
12416 {
12417   \fi:
12418   \_msg_kernel_expandable_error:nn { kernel } { fp-extra-comma }
12419   \exp_after:wN @
12420   \exp_after:wN \_fp_parse_apply_binary:NwNwN
12421   \exp_after:wN ,
12422   \exp:w
12423 }

```



```

12424 \cs_set_protected:Npn \__fp_tmp:w #1
12425 {
12426   \cs_new:Npn #1 ##1
12427   {
12428     \if_meaning:w \s__fp ##1
12429     \exp_after:wN \__fp_use_i_until_s:nw
12430     \exp_after:wN #1
12431     \fi:
12432     \exp_after:wN \c_nan_fp
12433     ##1
12434   }
12435 }
12436 \exp_args:Nc \__fp_tmp:w { __fp_,_o:ww }

```

(End definition for \\_\_fp\_parse\_infix\_,:N and others.)

### 24.7.2 Usual infix operators

As described in the “work plan”, each infix operator has an associated \...\_infix... function, a computing function, and precedence, given as arguments to \\_\_fp\_tmp:w. Using the general mechanism for arithmetic operations. The power operation must be associative in the opposite order from all others. For this, we use two distinct precedences.

```

12437 \cs_set_protected:Npn \__fp_tmp:w #1#2#3#4
12438 {
12439   \cs_new:Npn #1 ##1
12440   {
12441     \if_int_compare:w ##1 < #3
12442     \exp_after:wN @
12443     \exp_after:wN \__fp_parse_apply_binary:NwNwN
12444     \exp_after:wN #2
12445     \exp:w
12446     \__fp_parse_operand:Nw #4
12447     \exp_after:wN \__fp_parse_expand:w
12448     \else:
12449     \exp_after:wN @
12450     \exp_after:wN \use_none:n
12451     \exp_after:wN #1
12452     \fi:
12453   }
12454 }
12455 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_^:N } ^
12456 \c__fp_prec_hatii_int \c__fp_prec_hat_int
12457 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix/:N } /
12458 \c__fp_prec_times_int \c__fp_prec_times_int
12459 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_mul:N } *
12460 \c__fp_prec_times_int \c__fp_prec_times_int
12461 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix -:N } -
12462 \c__fp_prec_plus_int \c__fp_prec_plus_int
12463 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix +:N } +
12464 \c__fp_prec_plus_int \c__fp_prec_plus_int
12465 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_and:N } &
12466 \c__fp_prec_and_int \c__fp_prec_and_int
12467 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_or:N } |
12468 \c__fp_prec_or_int \c__fp_prec_or_int

```

(End definition for `\_fp_parse_infix_+ :N` and others.)

### 24.7.3 Juxtaposition

`\_fp_parse_infix_(:N` When an opening parenthesis appears where we expect an infix operator, we compute the product of the previous operand and the contents of the parentheses using `\_fp_parse_infix_juxtapose:N`.

```
12469 \cs_new:cpn { \_fp_parse_infix_(:N } #1
12470 { \_fp_parse_infix_juxtapose:N #1 ( }
```

(End definition for `\_fp_parse_infix_(:N`.)

`\_fp_parse_infix_juxtapose:N` Juxtaposition follows the same scheme as other binary operations, but calls `\_fp_parse_apply_juxtapose:NwwN` rather than directly calling `\_fp_parse_apply_binary:NwwN`. This lets us catch errors such as `... (1,2,3)pt` where one operand of the juxtaposition is not a single number: both #3 and #5 of the apply auxiliary must be empty.

```
12471 \cs_new:Npn \_fp_parse_infix_juxtapose:N #1
12472 {
12473   \if_int_compare:w #1 < \c__fp_prec_times_int
12474     \exp_after:wN @
12475     \exp_after:wN \_fp_parse_apply_juxtapose:NwwN
12476     \exp:w
12477     \_fp_parse_operand:Nw \c__fp_prec_times_int
12478     \exp_after:wN \_fp_parse_expand:w
12479   \else:
12480     \exp_after:wN @
12481     \exp_after:wN \use_none:n
12482     \exp_after:wN \_fp_parse_infix_juxtapose:N
12483   \fi:
12484 }
12485 \cs_new:Npn \_fp_parse_apply_juxtapose:NwwN #1 #2;#3@ #4;#5@
12486 {
12487   \if_catcode:w ^ \tl_to_str:n { #3 #5 } ^
12488   \else:
12489     \_fp_error:nffn { fp-invalid-ii }
12490     { \_fp_array_to_clist:n { #2; #3 } }
12491     { \_fp_array_to_clist:n { #4; #5 } }
12492     { }
12493   \fi:
12494   \_fp_parse_apply_binary:NwwN #1 #2;@ * #4;@
12495 }
```

(End definition for `\_fp_parse_infix_juxtapose:N` and `\_fp_parse_apply_juxtapose:NwwN`.)

### 24.7.4 Multi-character cases

`\_fp_parse_infix_*:N`

```
12496 \cs_set_protected:Npn \_fp_tmp:w #1
12497 {
12498   \cs_new:cpn { \_fp_parse_infix_*:N } ##1##2
12499   {
12500     \if:w * \exp_not:N ##2
```

```

12501         \exp_after:wN #1
12502         \exp_after:wN ##1
12503     \else:
12504         \exp_after:wN \__fp_parse_infix_mul:N
12505         \exp_after:wN ##1
12506         \exp_after:wN ##2
12507     \fi:
12508 }
12509 }
12510 \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_~:N }

```

(End definition for \\_\_fp\_parse\_infix\_\*:N.)

```

\__fp_parse_infix_|:Nw
\__fp_parse_infix_&:Nw

```

```

12511 \cs_set_protected:Npn \__fp_tmp:w #1#2#3
12512 {
12513     \cs_new:Npn #1 ##1##2
12514     {
12515         \if:w #2 \exp_not:N ##2
12516             \exp_after:wN #1
12517             \exp_after:wN ##1
12518             \exp:w \exp_after:wN \__fp_parse_expand:w
12519         \else:
12520             \exp_after:wN #3
12521             \exp_after:wN ##1
12522             \exp_after:wN ##2
12523         \fi:
12524     }
12525 }
12526 \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_|:N } | \__fp_parse_infix_or:N
12527 \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_&:N } & \__fp_parse_infix_and:N

```

(End definition for \\_\_fp\_parse\_infix\_|:Nw and \\_\_fp\_parse\_infix\_&:Nw.)

### 24.7.5 Ternary operator

```

\__fp_parse_infix_?:N
\__fp_parse_infix_:N

```

```

12528 \cs_set_protected:Npn \__fp_tmp:w #1#2#3#4
12529 {
12530     \cs_new:Npn #1 ##1
12531     {
12532         \if_int_compare:w ##1 < \c__fp_prec_quest_int
12533             #4
12534             \exp_after:wN @
12535             \exp_after:wN #2
12536             \exp:w
12537             \__fp_parse_operand:Nw #3
12538             \exp_after:wN \__fp_parse_expand:w
12539         \else:
12540             \exp_after:wN @
12541             \exp_after:wN \use_none:n
12542             \exp_after:wN #1
12543         \fi:
12544     }

```

```

12545     }
12546 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_?:N }
12547   \__fp_ternary:NwwN \c__fp_prec_quest_int { }
12548 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_:N }
12549   \__fp_ternary_auxii:NwwN \c__fp_prec_colon_int
12550   {
12551     \__msg_kernel_expandable_error:nnnn
12552     { kernel } { fp-missing } { ? } { ~for~?: }
12553   }

```

(End definition for \\_\_fp\_parse\_infix\_?:N and \\_\_fp\_parse\_infix\_:N.)

## 24.7.6 Comparisons

```

\__fp_parse_infix_<:N
\__fp_parse_infix_=:N
\__fp_parse_infix_>:N
\__fp_parse_infix_!:N
\__fp_parse_excl_error:
\__fp_parse_compare:NNNNNNN
\__fp_parse_compare_auxi:NNNNNNN
\__fp_parse_compare_auxii:NNNNN
\__fp_parse_compare_end:NNNNw
\__fp_compare:wNNNNw
12554 \cs_new:cpn { __fp_parse_infix_<:N } #1
12555   { \__fp_parse_compare:NNNNNNN #1 1 0 0 0 0 < }
12556 \cs_new:cpn { __fp_parse_infix_=:N } #1
12557   { \__fp_parse_compare:NNNNNNN #1 1 0 0 0 0 = }
12558 \cs_new:cpn { __fp_parse_infix_>:N } #1
12559   { \__fp_parse_compare:NNNNNNN #1 1 0 0 0 0 > }
12560 \cs_new:cpn { __fp_parse_infix_!:N } #1
12561   {
12562     \exp_after:wN \__fp_parse_compare:NNNNNNN
12563     \exp_after:wN #1
12564     \exp_after:wN 0
12565     \exp_after:wN 1
12566     \exp_after:wN 1
12567     \exp_after:wN 1
12568     \exp_after:wN 1
12569   }
12570 \cs_new:Npn \__fp_parse_excl_error:
12571   {
12572     \__msg_kernel_expandable_error:nnnn
12573     { kernel } { fp-missing } { = } { ~after~!. }
12574   }
12575 \cs_new:Npn \__fp_parse_compare:NNNNNNN #1
12576   {
12577     \if_int_compare:w #1 < \c__fp_prec_comp_int
12578       \exp_after:wN \__fp_parse_compare_auxi:NNNNNNN
12579       \exp_after:wN \__fp_parse_excl_error:
12580     \else:
12581       \exp_after:wN @
12582       \exp_after:wN \use_none:n
12583       \exp_after:wN \__fp_parse_compare:NNNNNNN
12584     \fi:
12585   }
12586 \cs_new:Npn \__fp_parse_compare_auxi:NNNNNNN #1#2#3#4#5#6#7
12587   {
12588     \if_case:w
12589       \__int_eval:w \exp_after:wN ‘ \token_to_str:N #7 - ‘< \__int_eval_end:
12590       \__fp_parse_compare_auxii:NNNNN #2#2#4#5#6
12591     \or: \__fp_parse_compare_auxii:NNNNN #2#3#2#5#6
12592     \or: \__fp_parse_compare_auxii:NNNNN #2#3#4#2#6

```

```

12593     \or: \__fp_parse_compare_auxii:NNNNN #2#3#4#5#2
12594     \else: #1 \__fp_parse_compare_end:NNNNw #3#4#5#6#7
12595     \fi:
12596 }
12597 \cs_new:Npn \__fp_parse_compare_auxii:NNNNN #1#2#3#4#5
12598 {
12599     \exp_after:wN \__fp_parse_compare_auxi:NNNNNNN
12600     \exp_after:wN \prg_do_nothing:
12601     \exp_after:wN #1
12602     \exp_after:wN #2
12603     \exp_after:wN #3
12604     \exp_after:wN #4
12605     \exp_after:wN #5
12606     \exp:w \exp_after:wN \__fp_parse_expand:w
12607 }
12608 \cs_new:Npn \__fp_parse_compare_end:NNNNw #1#2#3#4#5 \fi:
12609 {
12610     \fi:
12611     \exp_after:wN @
12612     \exp_after:wN \__fp_parse_apply_compare:NwNNNNNNwN
12613     \exp_after:wN \c_one_fp
12614     \exp_after:wN #1
12615     \exp_after:wN #2
12616     \exp_after:wN #3
12617     \exp_after:wN #4
12618     \exp:w
12619     \__fp_parse_operand:Nw \c__fp_prec_comp_int \__fp_parse_expand:w #5
12620 }
12621 \cs_new:Npn \__fp_parse_apply_compare:NwNNNNNNwN
12622 #1 #2@ #3 #4#5#6#7 #8@ #9
12623 {
12624     \if_int_odd:w
12625         \if_meaning:w \c_zero_fp #3
12626         0
12627     \else:
12628         \if_case:w \__fp_compare_back:ww #8 #2 \exp_stop_f:
12629             #5 \or: #6 \or: #7 \else: #4
12630         \fi:
12631     \fi:
12632     \exp_stop_f:
12633     \exp_after:wN \__fp_parse_apply_compare_aux:NNwN
12634     \exp_after:wN \c_one_fp
12635 \else:
12636     \exp_after:wN \__fp_parse_apply_compare_aux:NNwN
12637     \exp_after:wN \c_zero_fp
12638 \fi:
12639 #1 #8 #9
12640 }
12641 \cs_new:Npn \__fp_parse_apply_compare_aux:NNwN #1 #2 #3; #4
12642 {
12643     \if_meaning:w \__fp_parse_compare:NNNNNNN #4
12644     \exp_after:wN \__fp_parse_continue_compare:NNwNN
12645     \exp_after:wN #1
12646     \exp_after:wN #2

```

```

12647     \exp:w \exp_end_continue_f:w
12648     \__fp_exp_after_o:w #3;
12649     \exp:w \exp_end_continue_f:w
12650   \else:
12651     \exp_after:wN \__fp_parse_continue:NwN
12652     \exp_after:wN #2
12653     \exp:w \exp_end_continue_f:w
12654     \exp_after:wN #1
12655     \exp:w \exp_end_continue_f:w
12656   \fi:
12657   #4 #2
12658 }
12659 \cs_new:Npn \__fp_parse_continue_compare:NNwNN #1#2 #3@ #4#5
12660 { #4 #2 #3@ #1 }

```

(End definition for `\__fp_parse_infix_<:N` and others.)

## 24.8 Candidate: defining new l3fp functions

`\fp_function:Nw` Parse the argument of the function #1 using `\__fp_parse_operand:Nw` with a precedence of 16, and pass the function and argument to `\__fp_function_apply:nw`.

```

12661 \cs_new:Npn \fp_function:Nw #1
12662 {
12663   \exp_after:wN \__fp_function_apply:nw
12664   \exp_after:wN #1
12665   \exp:w
12666   \__fp_parse_operand:Nw \c__fp_prec_funcii_int \__fp_parse_expand:w
12667 }

```

(End definition for `\fp_function:Nw`.)

`\fp_new_function:Npn` Save the code provided by the user in the control sequence `\__fp_user_#1`. Define `\__fp_new_function:NNnnn` #1 to call `\__fp_function_apply:nw` after parsing one operand using `\__fp_parse_operand:Nw` with precedence 16. The auxiliary `\__fp_function_args:Nwn` receives the user function and the number of arguments (half of the number of tokens in the parameter text #2), followed by the operand (as a token list of floating points). It checks the number of arguments, and applies the user function to the arguments (without the outer brace group).

```

12668 \cs_new_protected:Npn \fp_new_function:Npn #1#2#
12669 {
12670   \__fp_new_function:Ncfnn #1
12671   { \__fp_user_ \cs_to_str:N #1 }
12672   { \int_eval:n { \tl_count:n {#2} / 2 } }
12673   {#2}
12674 }
12675 \cs_new_protected:Npn \__fp_new_function:NNnnn #1#2#3#4#5
12676 {
12677   \cs_new:Npn #1
12678   {
12679     \exp_after:wN \__fp_function_apply:nw \exp_after:wN
12680     {
12681       \exp_after:wN \__fp_function_args:Nwn
12682       \exp_after:wN #2
12683       \__int_value:w #3 \exp_after:wN ; \exp_after:wN

```

```

12684     }
12685     \exp:w
12686     \__fp_parse_operand:Nw \c__fp_prec_funcii_int \__fp_parse_expand:w
12687   }
12688   \cs_new:Npn #2 #4 {#5}
12689 }
12690 \cs_generate_variant:Nn \__fp_new_function:NNnnn { Ncf }
12691 \cs_new:Npn \__fp_function_args:Nwn #1#2; #3
12692 {
12693   \int_compare:nNnTF { \tl_count:n {#3} } = {#2}
12694   { #1 #3 }
12695   {
12696     \_msg_kernel_expandable_error:nnnnn
12697     { kernel } { fp-num-args } { #1() } {#2} {#2}
12698     \c_nan_fp
12699   }
12700 }

```

(End definition for \fp\_new\_function:Npn, \\_\_fp\_new\_function:NNnnn, and \\_\_fp\_function\_args:Nwn.)

```

\__fp_function_apply:nw
\__fp_function_store:wwNwnn
  \__fp_function_store_end:wnnn

```

The auxiliary \\_\_fp\_function\_apply:nw is called after parsing an operand, so it receives some code #1, then the operand ending with @, then a function such as \\_\_fp\_parse\_infix\_+:N (but not always of this form, see comparisons for instance). Package the operand (an array) into a token list with floating point items: this is the role of \\_\_fp\_function\_store:wwNwnn and \\_\_fp\_function\_store\_end:wnnn. Then apply \\_\_fp\_parse:n to the code #1 followed by a brace group with this token list. This results in a floating point result, which is then correctly parsed as the next operand of whatever was looking for one. The trailing \s\_\_fp\_mark is used as a special infix operator to indicate that the next token has already gone through \\_\_fp\_parse\_infix:NN.

```

12701 \cs_new:Npn \__fp_function_apply:nw #1#2 @
12702 {
12703   \__fp_parse:n
12704   {
12705     \__fp_function_store:wwNwnn #2
12706     \s__fp_mark \__fp_function_store:wwNwnn ;
12707     \s__fp_mark \__fp_function_store_end:wnnn
12708     \s__fp_stop { } { } {#1}
12709   }
12710   \s__fp_mark
12711 }
12712 \cs_new:Npn \__fp_function_store:wwNwnn
12713   #1; #2 \s__fp_mark #3#4 \s__fp_stop #5#6
12714   { #3 #2 \s__fp_mark #3#4 \s__fp_stop { #5 #6 } { { #1; } } }
12715 \cs_new:Npn \__fp_function_store_end:wnnn
12716   #1 \s__fp_stop #2#3#4
12717   { #4 {#2} }

```

(End definition for \\_\_fp\_function\_apply:nw, \\_\_fp\_function\_store:wwNwnn, and \\_\_fp\_function\_store\_end:wnnn.)

## 24.9 Messages

```

12718 \_msg_kernel_new:nnn { kernel } { fp-deprecated }
12719 { '#1'~deprecated;~use~'#2' }

```

```

12720 \_msg_kernel_new:nnn { kernel } { unknown-fp-word }
12721 { Unknown~fp~word~#1. }
12722 \_msg_kernel_new:nnn { kernel } { fp-missing }
12723 { Missing~#1~inserted #2. }
12724 \_msg_kernel_new:nnn { kernel } { fp-extra }
12725 { Extra~#1~ignored. }
12726 \_msg_kernel_new:nnn { kernel } { fp-early-end }
12727 { Premature~end~in~fp~expression. }
12728 \_msg_kernel_new:nnn { kernel } { fp-after-e }
12729 { Cannot~use~#1 after~'e'. }
12730 \_msg_kernel_new:nnn { kernel } { fp-missing-number }
12731 { Missing~number~before~'#1'. }
12732 \_msg_kernel_new:nnn { kernel } { fp-unknown-symbol }
12733 { Unknown~symbol~#1~ignored. }
12734 \_msg_kernel_new:nnn { kernel } { fp-extra-comma }
12735 { Unexpected~comma:~extra~arguments~ignored. }
12736 \_msg_kernel_new:nnn { kernel } { fp-num-args }
12737 { #1~expects~between~#2~and~#3~arguments. }
12738 \*package)
12739 \cs_if_exist:cT { @unexpandable@protect }
12740 {
12741   \_msg_kernel_new:nnn { kernel } { fp-robust-cmd }
12742   { Robust~command~#1 invalid~in~fp~expression! }
12743 }
12744 \</package>
12745 \</initex | package>

```

## 25 13fp-logic Implementation

```

12746 \*initex | package)
12747 \<@@=fp>

```

Those functions may receive a variable number of arguments.

```

\__fp_parse_word_max:N
\__fp_parse_word_min:N
12748 \cs_new:Npn \__fp_parse_word_max:N
12749 { \__fp_parse_function:NNN \__fp_minmax_o:Nw 2 }
12750 \cs_new:Npn \__fp_parse_word_min:N
12751 { \__fp_parse_function:NNN \__fp_minmax_o:Nw 0 }

```

(End definition for \\_\_fp\_parse\_word\_max:N and \\_\_fp\_parse\_word\_min:N.)

### 25.1 Syntax of internal functions

- \\_\_fp\_compare\_npos:nwn {<expo<sub>1</sub>>} <body<sub>1</sub>> ; {<expo<sub>2</sub>>} <body<sub>2</sub>> ;
- \\_\_fp\_minmax\_o:Nw <sign> <floating point array>
- \\_\_fp\_not\_o:w ? <floating point array> (with one floating point number only)
- \\_\_fp\_&\_o:ww <floating point> <floating point>
- \\_\_fp\_|\_o:ww <floating point> <floating point>
- \\_\_fp\_ternary:NwN, \\_\_fp\_ternary\_auxi:NwN, \\_\_fp\_ternary\_auxii:NwN have to be understood.



## 25.2 Existence test

`\fp_if_exist_p:N` Copies of the `cs` functions defined in `l3basics`.  
`\fp_if_exist_p:c` 12752 `\prg_new_eq_conditional:Nn \fp_if_exist:N \cs_if_exist:N { TF , T , F , p }`  
`\fp_if_exist:N $\overline{TF}$`  12753 `\prg_new_eq_conditional:Nn \fp_if_exist:c \cs_if_exist:c { TF , T , F , p }`  
`\fp_if_exist:c $\overline{TF}$`  (End definition for `\fp_if_exist:N $\overline{TF}$` . This function is documented on page 179.)

## 25.3 Comparison

`\fp_compare_p:n` Within floating point expressions, comparison operators are treated as operations, so we  
`\fp_compare:n $\overline{TF}$`  evaluate #1, then compare with 0.  
`\__fp_compare_return:w` 12754 `\prg_new_conditional:Npnn \fp_compare:n #1 { p , T , F , TF }`  
12755 `{`  
12756 `\exp_after:wN \__fp_compare_return:w`  
12757 `\exp:w \exp_end_continue_f:w \__fp_parse:n {#1}`  
12758 `}`  
12759 `\cs_new:Npn \__fp_compare_return:w \s_fp \__fp_chk:w #1#2;`  
12760 `{`  
12761 `\if_meaning:w 0 #1`  
12762 `\prg_return_false:`  
12763 `\else:`  
12764 `\prg_return_true:`  
12765 `\fi:`  
12766 `}`  
(End definition for `\fp_compare:n $\overline{TF}$`  and `\__fp_compare_return:w`. These functions are documented on page 180.)

`\fp_compare_p:nNn` Evaluate #1 and #3, using an auxiliary to expand both, and feed the two floating point  
`\fp_compare:nNn $\overline{TF}$`  numbers swapped to `\__fp_compare_back:ww`, defined below. Compare the result with  
`\__fp_compare_aux:wn` ‘#2-‘=, which is -1 for <, 0 for =, 1 for > and 2 for ?.  
12767 `\prg_new_conditional:Npnn \fp_compare:nNn #1#2#3 { p , T , F , TF }`  
12768 `{`  
12769 `\if_int_compare:w`  
12770 `\exp_after:wN \__fp_compare_aux:wn`  
12771 `\exp:w \exp_end_continue_f:w \__fp_parse:n {#1} {#3}`  
12772 `= \__int_eval:w ‘#2 - ‘= \__int_eval_end:`  
12773 `\prg_return_true:`  
12774 `\else:`  
12775 `\prg_return_false:`  
12776 `\fi:`  
12777 `}`  
12778 `\cs_new:Npn \__fp_compare_aux:wn #1; #2`  
12779 `{`  
12780 `\exp_after:wN \__fp_compare_back:ww`  
12781 `\exp:w \exp_end_continue_f:w \__fp_parse:n {#2} #1;`  
12782 `}`  
(End definition for `\fp_compare:nNn $\overline{TF}$`  and `\__fp_compare_aux:wn`. These functions are documented on page 180.)

`\__fp_compare_back:ww`  
`\__fp_compare_nan:w`

`\__fp_compare_back:ww`  $\langle y \rangle$  ;  $\langle x \rangle$  ;  
 Expands (in the same way as `\int_eval:n`) to  $-1$  if  $x < y$ ,  $0$  if  $x = y$ ,  $1$  if  $x > y$ , and  $2$  otherwise (denoted as  $x?y$ ). If either operand is `nan`, stop the comparison with `\__fp_compare_nan:w` returning  $2$ . If  $x$  is negative, swap the outputs  $1$  and  $-1$  (i.e.,  $>$  and  $<$ ); we can henceforth assume that  $x \geq 0$ . If  $y \geq 0$ , and they have the same type, either they are normal and we compare them with `\__fp_compare_npos:nwnw`, or they are equal. If  $y \geq 0$ , but of a different type, the highest type is a larger number. Finally, if  $y \leq 0$ , then  $x > y$ , unless both are zero.

```

12783 \cs_new:Npn \__fp_compare_back:ww
12784   \s__fp \__fp_chk:w #1 #2 #3;
12785   \s__fp \__fp_chk:w #4 #5 #6;
12786   {
12787     \__int_value:w
12788     \if_meaning:w 3 #1 \exp_after:wN \__fp_compare_nan:w \fi:
12789     \if_meaning:w 3 #4 \exp_after:wN \__fp_compare_nan:w \fi:
12790     \if_meaning:w 2 #5 - \fi:
12791     \if_meaning:w #2 #5
12792     \if_meaning:w #1 #4
12793     \if_meaning:w 1 #1
12794     \__fp_compare_npos:nwnw #6; #3;
12795     \else:
12796       0
12797     \fi:
12798     \else:
12799     \if_int_compare:w #4 < #1 - \fi: 1
12800     \fi:
12801     \else:
12802     \if_int_compare:w #1#4 = 0 \exp_stop_f:
12803       0
12804     \else:
12805       1
12806     \fi:
12807     \fi:
12808     \exp_stop_f:
12809   }
12810 \cs_new:Npn \__fp_compare_nan:w #1 \fi: \exp_stop_f: { 2 \exp_stop_f: }
```

(End definition for `\__fp_compare_back:ww` and `\__fp_compare_nan:w`.)

`\__fp_compare_npos:nwnw`  
`\__fp_compare_significand:nnnnnnnn`

`\__fp_compare_npos:nwnw`  $\{\langle expo_1 \rangle\} \langle body_1 \rangle$  ;  $\{\langle expo_2 \rangle\} \langle body_2 \rangle$  ;  
 Within an `\__int_value:w ... \exp_stop_f:` construction, this expands to  $0$  if the two numbers are equal,  $-1$  if the first is smaller, and  $1$  if the first is bigger. First compare the exponents: the larger one denotes the larger number. If they are equal, we must compare significands. If both the first 8 digits and the next 8 digits coincide, the numbers are equal. If only the first 8 digits coincide, the next 8 decide. Otherwise, the first 8 digits are compared.

```

12811 \cs_new:Npn \__fp_compare_npos:nwnw #1#2; #3#4;
12812   {
12813     \if_int_compare:w #1 = #3 \exp_stop_f:
12814     \__fp_compare_significand:nnnnnnnn #2 #4
12815     \else:
12816     \if_int_compare:w #1 < #3 - \fi: 1
12817     \fi:
```

```

12818 }
12819 \cs_new:Npn \__fp_compare_significand:nnnnnnnn #1#2#3#4#5#6#7#8
12820 {
12821   \if_int_compare:w #1#2 = #5#6 \exp_stop_f:
12822   \if_int_compare:w #3#4 = #7#8 \exp_stop_f:
12823     0
12824   \else:
12825     \if_int_compare:w #3#4 < #7#8 - \fi: 1
12826   \fi:
12827 \else:
12828   \if_int_compare:w #1#2 < #5#6 - \fi: 1
12829 \fi:
12830 }

```

(End definition for `\__fp_compare_npos:nwnw` and `\__fp_compare_significand:nnnnnnnn`.)

## 25.4 Floating point expression loops

`\fp_do_until:nn` These are quite easy given the above functions. The `do_until` and `do_while` versions execute the body, then test. The `until_do` and `while_do` do it the other way round.

```

\fp_do_while:nn
\fp_until_do:nn
\fp_while_do:nn
12831 \cs_new:Npn \fp_do_until:nn #1#2
12832 {
12833   #2
12834   \fp_compare:nF {#1}
12835   { \fp_do_until:nn {#1} {#2} }
12836 }
12837 \cs_new:Npn \fp_do_while:nn #1#2
12838 {
12839   #2
12840   \fp_compare:nT {#1}
12841   { \fp_do_while:nn {#1} {#2} }
12842 }
12843 \cs_new:Npn \fp_until_do:nn #1#2
12844 {
12845   \fp_compare:nF {#1}
12846   {
12847     #2
12848     \fp_until_do:nn {#1} {#2}
12849   }
12850 }
12851 \cs_new:Npn \fp_while_do:nn #1#2
12852 {
12853   \fp_compare:nT {#1}
12854   {
12855     #2
12856     \fp_while_do:nn {#1} {#2}
12857   }
12858 }

```

(End definition for `\fp_do_until:nn` and others. These functions are documented on page 181.)

`\fp_do_until:nNnn` As above but not using the `nNn` syntax.

```

\fp_do_while:nNnn
\fp_until_do:nNnn
\fp_while_do:nNnn
12859 \cs_new:Npn \fp_do_until:nNnn #1#2#3#4
12860 {

```

```

12861     #4
12862     \fp_compare:nNnF {#1} #2 {#3}
12863     { \fp_do_until:nNnn {#1} #2 {#3} {#4} }
12864   }
12865 \cs_new:Npn \fp_do_while:nNnn #1#2#3#4
12866 {
12867     #4
12868     \fp_compare:nNnT {#1} #2 {#3}
12869     { \fp_do_while:nNnn {#1} #2 {#3} {#4} }
12870   }
12871 \cs_new:Npn \fp_until_do:nNnn #1#2#3#4
12872 {
12873     \fp_compare:nNnF {#1} #2 {#3}
12874     {
12875         #4
12876         \fp_until_do:nNnn {#1} #2 {#3} {#4}
12877     }
12878   }
12879 \cs_new:Npn \fp_while_do:nNnn #1#2#3#4
12880 {
12881     \fp_compare:nNnT {#1} #2 {#3}
12882     {
12883         #4
12884         \fp_while_do:nNnn {#1} #2 {#3} {#4}
12885     }
12886   }

```

(End definition for `\fp_do_until:nNnn` and others. These functions are documented on page 181.)

**`\fp_step_function:nnnN`** The approach here is somewhat similar to `\int_step_function:nnnN`. There are two subtleties: we use the internal parser `\__fp_parse:n` to avoid converting back and forth from the internal representation; and (due to rounding) even a non-zero step does not guarantee that the loop counter increases.

**`\fp_step_function:nnnc`**  
`\__fp_step:wwwN`  
`\__fp_step:NnnnnN`  
`\__fp_step:NfnnnN`

```

12887 \cs_new:Npn \fp_step_function:nnnN #1#2#3
12888 {
12889     \exp_after:wN \__fp_step:wwwN
12890     \exp:w \exp_end_continue_f:w \__fp_parse_o:n {#1}
12891     \exp:w \exp_end_continue_f:w \__fp_parse_o:n {#2}
12892     \exp:w \exp_end_continue_f:w \__fp_parse:n {#3}
12893   }
12894 \cs_generate_variant:Nn \fp_step_function:nnnN { nnnc }
12895 % \end{macrocode}
12896 % Only \enquote{normal} floating points (not $\pm 0$,
12897 % $\pm\texttt{inf}$, $\texttt{nan}$) can be used as step; if positive,
12898 % call \cs{__fp_step:NnnnnN} with argument |>| otherwise~|<|. This
12899 % function has one more argument than its integer counterpart, namely
12900 % the previous value, to catch the case where the loop has made no
12901 % progress. Conversion to decimal is done just before calling the
12902 % user's function.
12903 % \begin{macrocode}
12904 \cs_new:Npn \__fp_step:wwwN #1 ; \s__fp \__fp_chk:w #2#3#4 ; #5; #6
12905 {
12906     \token_if_eq_meaning:NNTF #2 1
12907     {

```

```

12908     \token_if_eq_meaning:NNTF #3 0
12909     { \__fp_step:NnnnnN > }
12910     { \__fp_step:NnnnnN < }
12911   }
12912   {
12913     \token_if_eq_meaning:NNTF #2 0
12914     { \__msg_kernel_expandable_error:nnn { kernel } { zero-step } {#6} }
12915     {
12916       \__fp_error:nfn { fp-bad-step } { }
12917       { \fp_to_tl:n { \s__fp \__fp_chk:w #2#3#4 ; } } {#6}
12918     }
12919     \use_none:nnnnn
12920   }
12921   { #1 ; } { \c_nan_fp } { \s__fp \__fp_chk:w #2#3#4 ; } { #5 ; } #6
12922 }
12923 \cs_new:Npn \__fp_step:NnnnnN #1#2#3#4#5#6
12924 {
12925   \fp_compare:nNnTF {#2} = {#3}
12926   {
12927     \__fp_error:nfn { fp-tiny-step }
12928     { \fp_to_tl:n {#3} } { \fp_to_tl:n {#4} } {#6}
12929   }
12930   {
12931     \fp_compare:nNnF {#2} #1 {#5}
12932     {
12933       \exp_args:Nf #6 { \__fp_to_decimal_dispatch:w #2 }
12934       \__fp_step:NfnnnN
12935       #1 { \__fp_parse:n { #2 + #4 } } {#2} {#4} {#5} #6
12936     }
12937   }
12938 }
12939 \cs_generate_variant:Nn \__fp_step:NnnnnN { Nf }

```

(End definition for `\fp_step_function:nnnN`, `\__fp_step:wwwN`, and `\__fp_step:NnnnnN`. These functions are documented on page 182.)

`\fp_step_inline:nnnn` As for `\int_step_inline:nnnn`, create a global function and apply it, following up with a break point.

```

\fp_step_variable:nnnNn
\__fp_step:NNnnnnn
12940 \cs_new_protected:Npn \fp_step_inline:nnnn
12941 {
12942   \int_gincr:N \g__prg_map_int
12943   \exp_args:NNc \__fp_step:NNnnnn
12944   \cs_gset_protected:Npn
12945   { __prg_map_ \int_use:N \g__prg_map_int :w }
12946 }
12947 \cs_new_protected:Npn \fp_step_variable:nnnNn #1#2#3#4#5
12948 {
12949   \int_gincr:N \g__prg_map_int
12950   \exp_args:NNc \__fp_step:NNnnnn
12951   \cs_gset_protected:Npx
12952   { __prg_map_ \int_use:N \g__prg_map_int :w }
12953   {#1} {#2} {#3}
12954   {
12955     \tl_set:Nn \exp_not:N #4 {##1}

```

```

12956         \exp_not:n {#5}
12957     }
12958 }
12959 \cs_new_protected:Npn \__fp_step:NNnnnn #1#2#3#4#5#6
12960 {
12961     #1 #2 ##1 {#6}
12962     \fp_step_function:nnnN {#3} {#4} {#5} #2
12963     \__prg_break_point:Nn \scan_stop: { \int_gdecr:N \g__prg_map_int }
12964 }

```

(End definition for `\fp_step_inline:nnnn`, `\fp_step_variable:nnnNn`, and `\__fp_step:NNnnnn`. These functions are documented on page 182.)

```

12965 \__msg_kernel_new:nnn { kernel } { fp-bad-step }
12966 { Invalid~step~size~#2~in~step~function~#3. }
12967 \__msg_kernel_new:nnn { kernel } { fp-tiny-step }
12968 { Tiny~step~size~(#1+#2=#1)~in~step~function~#3. }

```

## 25.5 Extrema

`\__fp_minmax_o:Nw` The argument `#1` is 2 to find the maximum of an array `#2` of floating point numbers, and 0 to find the minimum. We read numbers sequentially, keeping track of the largest (smallest) number found so far. If numbers are equal (for instance  $\pm 0$ ), the first is kept. We append  $-\infty$  ( $\infty$ ), for the case of an empty array. Since no number is smaller (larger) than that, this additional item only affects the maximum (minimum) in the case of `max()` and `min()` with no argument. The weird fp-like trailing marker breaks the loop correctly: see the precise definition of `\__fp_minmax_loop:Nww`.

```

12969 \cs_new:Npn \__fp_minmax_o:Nw #1#2 @
12970 {
12971     \if_meaning:w 0 #1
12972         \exp_after:wN \__fp_minmax_loop:Nww \exp_after:wN +
12973     \else:
12974         \exp_after:wN \__fp_minmax_loop:Nww \exp_after:wN -
12975     \fi:
12976     #2
12977     \s__fp \__fp_chk:w 2 #1 \s__fp_exact ;
12978     \s__fp \__fp_chk:w { 3 \__fp_minmax_break_o:w } ;
12979 }

```

(End definition for `\__fp_minmax_o:Nw`.)

`\__fp_minmax_loop:Nww` The first argument is `-` or `+` to denote the case where the currently largest (smallest) number found (first floating point argument) should be replaced by the new number (second floating point argument). If the new number is `nan`, keep that as the extremum, unless that extremum is already a `nan`. Otherwise, compare the two numbers. If the new number is larger (in the case of `max`) or smaller (in the case of `min`), the test yields `true`, and we keep the second number as a new maximum; otherwise we keep the first number. Then loop.

```

12980 \cs_new:Npn \__fp_minmax_loop:Nww
12981     #1 \s__fp \__fp_chk:w #2#3; \s__fp \__fp_chk:w #4#5;
12982 {
12983     \if_meaning:w 3 #4
12984         \if_meaning:w 3 #2
12985             \__fp_minmax_auxi:ww

```

```

12986     \else:
12987         \__fp_minmax_auxii:ww
12988     \fi:
12989 \else:
12990     \if_int_compare:w
12991         \__fp_compare_back:ww
12992         \s__fp \__fp_chk:w #4#5;
12993         \s__fp \__fp_chk:w #2#3;
12994         = #1 1 \exp_stop_f:
12995         \__fp_minmax_auxii:ww
12996     \else:
12997         \__fp_minmax_auxi:ww
12998     \fi:
12999 \fi:
13000 \__fp_minmax_loop:Nww #1
13001     \s__fp \__fp_chk:w #2#3;
13002     \s__fp \__fp_chk:w #4#5;
13003 }

```

(End definition for \\_\_fp\_minmax\_loop:Nww.)

```

\__fp_minmax_auxi:ww Keep the first/second number, and remove the other.
\__fp_minmax_auxii:ww
13004 \cs_new:Npn \__fp_minmax_auxi:ww #1 \fi: \fi: #2 \s__fp #3 ; \s__fp #4;
13005 { \fi: \fi: #2 \s__fp #3 ; }
13006 \cs_new:Npn \__fp_minmax_auxii:ww #1 \fi: \fi: #2 \s__fp #3 ;
13007 { \fi: \fi: #2 }

```

(End definition for \\_\_fp\_minmax\_auxi:ww and \\_\_fp\_minmax\_auxii:ww.)

\\_\_fp\_minmax\_break\_o:w This function is called from within an \if\_meaning:w test. Skip to the end of the tests, close the current test with \fi:, clean up, and return the appropriate number with one post-expansion.

```

13008 \cs_new:Npn \__fp_minmax_break_o:w #1 \fi: \fi: #2 \s__fp #3; #4;
13009 { \fi: \__fp_exp_after_o:w \s__fp #3; }

```

(End definition for \\_\_fp\_minmax\_break\_o:w.)

## 25.6 Boolean operations

\\_\_fp\_not\_o:w Return true or false, with two expansions, one to exit the conditional, and one to please l3fp-parse. The first argument is provided by l3fp-parse and is ignored.

```

13010 \cs_new:cpn { __fp_not_o:w } #1 \s__fp \__fp_chk:w #2#3; @
13011 {
13012     \if_meaning:w 0 #2
13013     \exp_after:wN \exp_after:wN \exp_after:wN \c_one_fp
13014     \else:
13015     \exp_after:wN \exp_after:wN \exp_after:wN \c_zero_fp
13016     \fi:
13017 }

```

(End definition for \\_\_fp\_not\_o:w.)

`\__fp_&_o:ww` For and, if the first number is zero, return it (with the same sign). Otherwise, return  
`\__fp_|_o:ww` the second one. For or, the logic is reversed: if the first number is non-zero, return  
`\__fp_and_return:wNw` it, otherwise return the second number: we achieve that by hi-jacking `\__fp_&_o:ww`,  
inserting an extra argument, `\else:`, before `\s__fp`. In all cases, expand after the  
floating point number.

```

13018 \group_begin:
13019   \char_set_catcode_letter:N &
13020   \char_set_catcode_letter:N |
13021   \cs_new:Npn \__fp_&_o:ww #1 \s__fp \__fp_chk:w #2#3;
13022   {
13023     \if_meaning:w 0 #2 #1
13024     \__fp_and_return:wNw \s__fp \__fp_chk:w #2#3;
13025     \fi:
13026     \__fp_exp_after_o:w
13027   }
13028   \cs_new:Npn \__fp_|_o:ww { \__fp_&_o:ww \else: }
13029 \group_end:
13030 \cs_new:Npn \__fp_and_return:wNw #1; \fi: #2#3; { \fi: #2 #1; }

```

(End definition for `\__fp_&_o:ww`, `\__fp_|_o:ww`, and `\__fp_and_return:wNw`.)

## 25.7 Ternary operator

`\__fp_ternary:NwN` The first function receives the test and the true branch of the `?:` ternary operator. It  
`\__fp_ternary_auxi:NwN` returns the true branch, unless the test branch is zero. In that case, the function returns  
`\__fp_ternary_auxii:NwN` a very specific nan. The second function receives the output of the first function, and the  
`\__fp_ternary_loop_break:w` false branch. It returns the previous input, unless that is the special nan, in which case  
`\__fp_ternary_loop:Nw` we return the false branch.  
`\__fp_ternary_map_break:`  
`\__fp_ternary_break_point:n`

```

13031 \cs_new:Npn \__fp_ternary:NwN #1 #2@ #3@ #4
13032 {
13033   \if_meaning:w \__fp_parse_infix_:N #4
13034   \__fp_ternary_loop:Nw
13035   #2
13036   \s__fp \__fp_chk:w { \__fp_ternary_loop_break:w } ;
13037   \__fp_ternary_break_point:n { \exp_after:wN \__fp_ternary_auxi:NwN }
13038   \exp_after:wN #1
13039   \exp:w \exp_end_continue_f:w
13040   \__fp_exp_after_array_f:w #3 \s__fp_stop
13041   \exp_after:wN @
13042   \exp:w
13043   \__fp_parse_operand:Nw \c__fp_prec_colon_int
13044   \__fp_parse_expand:w
13045   \else:
13046     \__msg_kernel_expandable_error:nnnn
13047     { kernel } { fp-missing } { : } { ~for~?: }
13048     \exp_after:wN \__fp_parse_continue:NwN
13049     \exp_after:wN #1
13050     \exp:w \exp_end_continue_f:w
13051     \__fp_exp_after_array_f:w #3 \s__fp_stop
13052     \exp_after:wN #4
13053     \exp_after:wN #1
13054   \fi:
13055 }

```



```

13056 \cs_new:Npn \__fp_ternary_loop_break:w
13057   #1 \fi: #2 \__fp_ternary_break_point:n #3
13058   {
13059     0 = 0 \exp_stop_f: \fi:
13060     \exp_after:wN \__fp_ternary_auxii:NwwN
13061   }
13062 \cs_new:Npn \__fp_ternary_loop:Nw \s__fp \__fp_chk:w #1#2;
13063   {
13064     \if_int_compare:w #1 > 0 \exp_stop_f:
13065     \exp_after:wN \__fp_ternary_map_break:
13066     \fi:
13067     \__fp_ternary_loop:Nw
13068   }
13069 \cs_new:Npn \__fp_ternary_map_break: #1 \__fp_ternary_break_point:n #2 {#2}
13070 \cs_new:Npn \__fp_ternary_auxi:NwwN #1#2@#3@#4
13071   {
13072     \exp_after:wN \__fp_parse_continue:NwN
13073     \exp_after:wN #1
13074     \exp:w \exp_end_continue_f:w
13075     \__fp_exp_after_array_f:w #2 \s__fp_stop
13076     #4 #1
13077   }
13078 \cs_new:Npn \__fp_ternary_auxii:NwwN #1#2@#3@#4
13079   {
13080     \exp_after:wN \__fp_parse_continue:NwN
13081     \exp_after:wN #1
13082     \exp:w \exp_end_continue_f:w
13083     \__fp_exp_after_array_f:w #3 \s__fp_stop
13084     #4 #1
13085   }

```

(End definition for \\_\_fp\_ternary:NwwN and others.)

```
13086 </initex | package>
```

## 26 l3fp-basics Implementation

```
13087 <*initex | package>
```

```
13088 <@@=fp>
```

The l3fp-basics module implements addition, subtraction, multiplication, and division of two floating points, and the absolute value and sign-changing operations on one floating point. All operations implemented in this module yield the outcome of rounding the infinitely precise result of the operation to the nearest floating point.

Some algorithms used below end up being quite similar to some described in “What Every Computer Scientist Should Know About Floating Point Arithmetic”, by David Goldberg, which can be found at <http://cr.yp.to/2005-590/goldberg.pdf>.

Unary functions.

```

\__fp_parse_word_abs:N
\__fp_parse_word_sign:N
\__fp_parse_word_sqrt:N
13089 \cs_new:Npn \__fp_parse_word_abs:N
13090   { \__fp_parse_unary_function:NNN \__fp_set_sign_o:w 0 }
13091 \cs_new:Npn \__fp_parse_word_sign:N
13092   { \__fp_parse_unary_function:NNN \__fp_sign_o:w ? }
13093 \cs_new:Npn \__fp_parse_word_sqrt:N
13094   { \__fp_parse_unary_function:NNN \__fp_sqrt_o:w ? }

```

(End definition for `\__fp_parse_word_abs:N`, `\__fp_parse_word_sign:N`, and `\__fp_parse_word_sqrt:N`.)

## 26.1 Addition and subtraction

We define here two functions, `\__fp_-_o:ww` and `\__fp+_o:ww`, which perform the subtraction and addition of their two floating point operands, and expand the tokens following the result once.

A more obscure function, `\__fp_add_big_i_o:wNww`, is used in `l3fp-expo`.

The logic goes as follows:

- `\__fp_-_o:ww` calls `\__fp+_o:ww` to do the work, with the sign of the second operand flipped;
- `\__fp+_o:ww` dispatches depending on the type of floating point, calling specialized auxiliaries;
- in all cases except summing two normal floating point numbers, we return one or the other operands depending on the signs, or detect an invalid operation in the case of  $\infty - \infty$ ;
- for normal floating point numbers, compare the signs;
- to add two floating point numbers of the same sign or of opposite signs, shift the significand of the smaller one to match the bigger one, perform the addition or subtraction of significands, check for a carry, round, and pack using the `\__fp-basics_pack_...` functions.

The trickiest part is to round correctly when adding or subtracting normal floating point numbers.

### 26.1.1 Sign, exponent, and special numbers

`\__fp_-_o:ww` The `\__fp+_o:ww` auxiliary has a hook: it takes one argument between the first `\s__fp` and `\__fp_chk:w`, which is applied to the sign of the second operand. Positioning the hook there means that `\__fp+_o:ww` can still perform the sanity check that it was followed by `\s__fp`.

```

13095 \cs_new:cpx { __fp_-_o:ww } \s__fp
13096 {
13097   \exp_not:c { __fp+_o:ww }
13098   \exp_not:n { \s__fp \__fp_neg_sign:N }
13099 }

```

(End definition for `\__fp_-_o:ww`.)

`\__fp+_o:ww` This function is either called directly with an empty `#1` to compute an addition, or it is called by `\__fp_-_o:ww` with `\__fp_neg_sign:N` as `#1` to compute a subtraction, in which case the second operand's sign should be changed. If the *<types>* `#2` and `#4` are the same, dispatch to case `#2` (0, 1, 2, or 3), where we call specialized functions: thanks to `\__int_value:w`, those receive the tweaked *<sign<sub>2</sub>>* (expansion of `#1#5`) as an argument. If the *<types>* are distinct, the result is simply the floating point number with the highest *<type>*. Since case 3 (used for two `nan`) also picks the first operand, we can also use it

when  $\langle type_1 \rangle$  is greater than  $\langle type_2 \rangle$ . Also note that we don't need to worry about  $\langle sign_2 \rangle$  in that case since the second operand is discarded.

```

13100 \cs_new:cpn { __fp+_o:ww }
13101   \s__fp #1 \__fp_chk:w #2 #3 ; \s__fp \__fp_chk:w #4 #5
13102   {
13103     \if_case:w
13104       \if_meaning:w #2 #4
13105       #2
13106     \else:
13107       \if_int_compare:w #2 > #4 \exp_stop_f:
13108       3
13109     \else:
13110       4
13111     \fi:
13112   \fi:
13113   \exp_stop_f:
13114     \exp_after:wN \__fp_add_zeros_o:Nww \__int_value:w
13115   \or:   \exp_after:wN \__fp_add_normal_o:Nww \__int_value:w
13116   \or:   \exp_after:wN \__fp_add_inf_o:Nww \__int_value:w
13117   \or:   \__fp_case_return_i_o:ww
13118   \else: \exp_after:wN \__fp_add_return_ii_o:Nww \__int_value:w
13119   \fi:
13120   #1 #5
13121   \s__fp \__fp_chk:w #2 #3 ;
13122   \s__fp \__fp_chk:w #4 #5
13123 }

```

(End definition for  $\backslash\_fp\_+_o:ww$ .)

$\backslash\_fp\_add\_return\_ii\_o:Nww$  Ignore the first operand, and return the second, but using the sign #1 rather than #4. As usual, expand after the floating point.

```

13124 \cs_new:Npn \__fp_add_return_ii_o:Nww #1 #2 ; \s__fp \__fp_chk:w #3 #4
13125   { \__fp_exp_after_o:w \s__fp \__fp_chk:w #3 #1 }

```

(End definition for  $\backslash\_fp\_add\_return\_ii\_o:Nww$ .)

$\backslash\_fp\_add\_zeros\_o:Nww$  Adding two zeros yields  $\backslash c\_zero\_fp$ , except if both zeros were  $-0$ .

```

13126 \cs_new:Npn \__fp_add_zeros_o:Nww #1 \s__fp \__fp_chk:w 0 #2
13127   {
13128     \if_int_compare:w #2 #1 = 20 \exp_stop_f:
13129     \exp_after:wN \__fp_add_return_ii_o:Nww
13130   \else:
13131     \__fp_case_return_i_o:ww
13132   \fi:
13133   #1
13134   \s__fp \__fp_chk:w 0 #2
13135 }

```

(End definition for  $\backslash\_fp\_add\_zeros\_o:Nww$ .)

$\backslash\_fp\_add\_inf\_o:Nww$  If both infinities have the same sign, just return that infinity, otherwise, it is an invalid operation. We find out if that invalid operation is an addition or a subtraction by testing whether the tweaked  $\langle sign_2 \rangle$  (#1) and the  $\langle sign_2 \rangle$  (#4) are identical.

```

13136 \cs_new:Npn \__fp_add_inf_o:Nww

```

```

13137     #1 \s__fp \__fp_chk:w 2 #2 #3; \s__fp \__fp_chk:w 2 #4
13138   {
13139     \if_meaning:w #1 #2
13140       \__fp_case_return_i_o:ww
13141     \else:
13142       \__fp_case_use:nw
13143       {
13144         \exp_last_unbraced:Nf \__fp_invalid_operation_o:Nww
13145         { \token_if_eq_meaning:NNTF #1 #4 + - }
13146       }
13147     \fi:
13148     \s__fp \__fp_chk:w 2 #2 #3;
13149     \s__fp \__fp_chk:w 2 #4
13150   }

```

(End definition for \\_\_fp\_add\_inf\_o:Nww.)

```

\__fp_add_normal_o:Nww      \__fp_add_normal_o:Nww <sign2> \s__fp \__fp_chk:w 1 <sign1> <exp1>
                             <body1> ; \s__fp \__fp_chk:w 1 <initial sign2> <exp2> <body2> ;

```

We now have two normal numbers to add, and we have to check signs and exponents more carefully before performing the addition.

```

13151 \cs_new:Npn \__fp_add_normal_o:Nww #1 \s__fp \__fp_chk:w 1 #2
13152 {
13153   \if_meaning:w #1#2
13154     \exp_after:wN \__fp_add_npos_o:NnwNnw
13155   \else:
13156     \exp_after:wN \__fp_sub_npos_o:NnwNnw
13157   \fi:
13158   #2
13159 }

```

(End definition for \\_\_fp\_add\_normal\_o:Nww.)

### 26.1.2 Absolute addition

In this subsection, we perform the addition of two positive normal numbers.

```

\__fp_add_npos_o:NnwNnw      \__fp_add_npos_o:NnwNnw <sign1> <exp1> <body1> ; \s__fp \__fp_chk:w 1
                             <initial sign2> <exp2> <body2> ;

```

Since we are doing an addition, the final sign is  $\langle sign_1 \rangle$ . Start an  $\backslash\_int\_eval:w$ , responsible for computing the exponent: the result, and the  $\langle final\ sign \rangle$  are then given to  $\backslash\_fp\_sanitize:Nw$  which checks for overflow. The exponent is computed as the largest exponent #2 or #5, incremented if there is a carry. To add the significands, we decimate the smaller number by the difference between the exponents. This is done by  $\backslash\_fp\_add\_big\_i:wNww$  or  $\backslash\_fp\_add\_big\_ii:wNww$ . We need to bring the final sign with us in the midst of the calculation to round properly at the end.

```

13160 \cs_new:Npn \__fp_add_npos_o:NnwNnw #1#2#3 ; \s__fp \__fp_chk:w 1 #4 #5
13161 {
13162   \exp_after:wN \__fp_sanitize:Nw
13163   \exp_after:wN #1
13164   \__int_value:w \__int_eval:w
13165   \if_int_compare:w #2 > #5 \exp_stop_f:
13166   #2

```

```

13167     \exp_after:wN \_fp_add_big_i_o:wNww \_int_value:w -
13168     \else:
13169         #5
13170     \exp_after:wN \_fp_add_big_ii_o:wNww \_int_value:w
13171     \fi:
13172     \_int_eval:w #5 - #2 ; #1 #3;
13173 }

```

(End definition for \\_fp\_add\_npos\_o:NnwNnw.)

\\_fp\_add\_big\_i\_o:wNww      \\_fp\_add\_big\_i\_o:wNww  $\langle shift \rangle$  ;  $\langle final\ sign \rangle$   $\langle body_1 \rangle$  ;  $\langle body_2 \rangle$  ;  
\\_fp\_add\_big\_ii\_o:wNww      Used in l3fp-expo. Shift the significand of the small number, then add with \\_fp-add\_significand\_o:NnnwnnnnN.

```

13174 \cs_new:Npn \_fp_add_big_i_o:wNww #1; #2 #3; #4;
13175 {
13176     \_fp_decimate:nNnnnn {#1}
13177     \_fp_add_significand_o:NnnwnnnnN
13178     #4
13179     #3
13180     #2
13181 }
13182 \cs_new:Npn \_fp_add_big_ii_o:wNww #1; #2 #3; #4;
13183 {
13184     \_fp_decimate:nNnnnn {#1}
13185     \_fp_add_significand_o:NnnwnnnnN
13186     #3
13187     #4
13188     #2
13189 }

```

(End definition for \\_fp\_add\_big\_i\_o:wNww and \\_fp\_add\_big\_ii\_o:wNww.)

\\_fp\_add\_significand\_o:NnnwnnnnN      \\_fp\_add\_significand\_o:NnnwnnnnN  $\langle rounding\ digit \rangle$   $\{ \langle Y'_1 \rangle \}$   $\{ \langle Y'_2 \rangle \}$   
\\_fp\_add\_significand\_pack:NNNNNNN       $\langle extra-digits \rangle$  ;  $\{ \langle X_1 \rangle \}$   $\{ \langle X_2 \rangle \}$   $\{ \langle X_3 \rangle \}$   $\{ \langle X_4 \rangle \}$   $\langle final\ sign \rangle$   
\\_fp\_add\_significand\_test\_o:N

To round properly, we must know at which digit the rounding should occur. This requires to know whether the addition produces an overall carry or not. Thus, we do the computation now and check for a carry, then go back and do the rounding. The rounding may cause a carry in very rare cases such as  $0.99 \dots 95 \rightarrow 1.00 \dots 0$ , but this situation always give an exact power of 10, for which it is easy to correct the result at the end.

```

13190 \cs_new:Npn \_fp_add_significand_o:NnnwnnnnN #1 #2#3 #4; #5#6#7#8
13191 {
13192     \exp_after:wN \_fp_add_significand_test_o:N
13193     \_int_value:w \_int_eval:w 1#5#6 + #2
13194     \exp_after:wN \_fp_add_significand_pack:NNNNNNN
13195     \_int_value:w \_int_eval:w 1#7#8 + #3 ; #1
13196 }
13197 \cs_new:Npn \_fp_add_significand_pack:NNNNNNN #1 #2#3#4#5#6#7
13198 {
13199     \if_meaning:w 2 #1
13200     + 1
13201     \fi:
13202     ; #2 #3 #4 #5 #6 #7 ;
13203 }
13204 \cs_new:Npn \_fp_add_significand_test_o:N #1

```

```

13205 {
13206     \if_meaning:w 2 #1
13207     \exp_after:wN \__fp_add_significand_carry_o:wwwNN
13208     \else:
13209     \exp_after:wN \__fp_add_significand_no_carry_o:wwwNN
13210     \fi:
13211 }

```

(End definition for \\_\_fp\_add\_significand\_o:NnnwnnnN, \\_\_fp\_add\_significand\_pack:NNNNNN, and \\_\_fp\_add\_significand\_test\_o:N.)

\\_\_fp\_add\_significand\_no\_carry\_o:wwwNN  $\langle 8d \rangle$  ;  $\langle 6d \rangle$  ;  $\langle 2d \rangle$  ;  $\langle \text{rounding digit} \rangle$   $\langle \text{sign} \rangle$

If there's no carry, grab all the digits again and round. The packing function \\_\_fp\_basics\_pack\_high:NNNNNw takes care of the case where rounding brings a carry.

```

13212 \cs_new:Npn \__fp_add_significand_no_carry_o:wwwNN
13213     #1; #2; #3#4 ; #5#6
13214 {
13215     \exp_after:wN \__fp_basics_pack_high:NNNNNw
13216     \__int_value:w \__int_eval:w 1 #1
13217     \exp_after:wN \__fp_basics_pack_low:NNNNNw
13218     \__int_value:w \__int_eval:w 1 #2 #3#4
13219     + \__fp_round:NNN #6 #4 #5
13220     \exp_after:wN ;
13221 }

```

(End definition for \\_\_fp\_add\_significand\_no\_carry\_o:wwwNN.)

\\_\_fp\_add\_significand\_carry\_o:wwwNN  $\langle 8d \rangle$  ;  $\langle 6d \rangle$  ;  $\langle 2d \rangle$  ;  $\langle \text{rounding digit} \rangle$   $\langle \text{sign} \rangle$

The case where there is a carry is very similar. Rounding can even raise the first digit from 1 to 2, but we don't care.

```

13222 \cs_new:Npn \__fp_add_significand_carry_o:wwwNN
13223     #1; #2; #3#4; #5#6
13224 {
13225     + 1
13226     \exp_after:wN \__fp_basics_pack_weird_high:NNNNNNNNw
13227     \__int_value:w \__int_eval:w 1 1 #1
13228     \exp_after:wN \__fp_basics_pack_weird_low:NNNNNw
13229     \__int_value:w \__int_eval:w 1 #2#3 +
13230     \exp_after:wN \__fp_round:NNN
13231     \exp_after:wN #6
13232     \exp_after:wN #3
13233     \__int_value:w \__fp_round_digit:Nw #4 #5 ;
13234     \exp_after:wN ;
13235 }

```

(End definition for \\_\_fp\_add\_significand\_carry\_o:wwwNN.)

### 26.1.3 Absolute subtraction

\\_\_fp\_sub\_npos\_o:NnwNnw  $\langle \text{sign}_1 \rangle$   $\langle \text{exp}_1 \rangle$   $\langle \text{body}_1 \rangle$  ; \s\_\_fp \\_\_fp\_chk:w 1  
 \\_\_fp\_sub\_eq\_o:Nnwnw  $\langle \text{initial sign}_2 \rangle$   $\langle \text{exp}_2 \rangle$   $\langle \text{body}_2 \rangle$  ;  
 \\_\_fp\_sub\_npos\_ii\_o:Nnwnw

Rounding properly in some modes requires to know what the sign of the result will be. Thus, we start by comparing the exponents and significands. If the numbers coincide, return zero. If the second number is larger, swap the numbers and call `\__fp_sub_npos_i_o:Nnwnw` with the opposite of  $\langle sign_1 \rangle$ .

```

13236 \cs_new:Npn \__fp_sub_npos_o:NnwNnw #1#2#3; \s__fp \__fp_chk:w 1 #4#5#6;
13237 {
13238   \if_case:w \__fp_compare_npos:nwnw {#2} #3; {#5} #6; \exp_stop_f:
13239     \exp_after:wN \__fp_sub_eq_o:Nnwnw
13240   \or:
13241     \exp_after:wN \__fp_sub_npos_i_o:Nnwnw
13242   \else:
13243     \exp_after:wN \__fp_sub_npos_ii_o:Nnwnw
13244   \fi:
13245   #1 {#2} #3; {#5} #6;
13246 }
13247 \cs_new:Npn \__fp_sub_eq_o:Nnwnw #1#2; #3; { \exp_after:wN \c_zero_fp }
13248 \cs_new:Npn \__fp_sub_npos_ii_o:Nnwnw #1 #2; #3;
13249 {
13250   \exp_after:wN \__fp_sub_npos_i_o:Nnwnw
13251   \__int_value:w \__fp_neg_sign:N #1
13252   #3; #2;
13253 }

```

(End definition for `\__fp_sub_npos_o:NnwNnw`, `\__fp_sub_eq_o:Nnwnw`, and `\__fp_sub_npos_ii_o:Nnwnw`.)

`\__fp_sub_npos_i_o:Nnwnw`

After the computation is done, `\__fp_sanitizew` checks for overflow/underflow. It expects the  $\langle final\ sign \rangle$  and the  $\langle exponent \rangle$  (delimited by ;). Start an integer expression for the exponent, which starts with the exponent of the largest number, and may be decreased if the two numbers are very close. If the two numbers have the same exponent, call the **near** auxiliary. Otherwise, decimate  $y$ , then call the **far** auxiliary to evaluate the difference between the two significands. Note that we decimate by 1 less than one could expect.

```

13254 \cs_new:Npn \__fp_sub_npos_i_o:Nnwnw #1 #2#3; #4#5;
13255 {
13256   \exp_after:wN \__fp_sanitizew
13257   \exp_after:wN #1
13258   \__int_value:w \__int_eval:w
13259   #2
13260   \if_int_compare:w #2 = #4 \exp_stop_f:
13261     \exp_after:wN \__fp_sub_back_near_o:nnnnnnnnN
13262   \else:
13263     \exp_after:wN \__fp_decimate:nNnnnn \exp_after:wN
13264     { \__int_value:w \__int_eval:w #2 - #4 - 1 \exp_after:wN }
13265     \exp_after:wN \__fp_sub_back_far_o:NnnwnnnnnN
13266   \fi:
13267   #5
13268   #3
13269   #1
13270 }

```

(End definition for `\__fp_sub_npos_i_o:Nnwnw`.)

`\__fp_sub_back_near_o:nnnnnnnnN`  
`\__fp_sub_back_near_pack:NNNNNNw`  
`\__fp_sub_back_near_after:wNNNNw`

`\__fp_sub_back_near_o:nnnnnnnnN`  $\{\langle Y_1 \rangle\}$   $\{\langle Y_2 \rangle\}$   $\{\langle Y_3 \rangle\}$   $\{\langle Y_4 \rangle\}$   $\{\langle X_1 \rangle\}$   
 $\{\langle X_2 \rangle\}$   $\{\langle X_3 \rangle\}$   $\{\langle X_4 \rangle\}$   $\langle final\ sign \rangle$

In this case, the subtraction is exact, so we discard the *final sign* #9. The very large shifts of  $10^9$  and  $1.1 \cdot 10^9$  are unnecessary here, but allow the auxiliaries to be reused later. Each integer expression produces a 10 digit result. If the resulting 16 digits start with a 0, then we need to shift the group, padding with trailing zeros.

```

13271 \cs_new:Npn \__fp_sub_back_near_o:nnnnnnnnN #1#2#3#4 #5#6#7#8 #9
13272 {
13273   \exp_after:wN \__fp_sub_back_near_after:wNNNNw
13274   \__int_value:w \__int_eval:w 10#5#6 - #1#2 - 11
13275   \exp_after:wN \__fp_sub_back_near_pack:NNNNNNw
13276   \__int_value:w \__int_eval:w 11#7#8 - #3#4 \exp_after:wN ;
13277 }
13278 \cs_new:Npn \__fp_sub_back_near_pack:NNNNNNw #1#2#3#4#5#6#7 ;
13279 { + #1#2 ; {#3#4#5#6} {#7} ; }
13280 \cs_new:Npn \__fp_sub_back_near_after:wNNNNw 10 #1#2#3#4 #5 ;
13281 {
13282   \if_meaning:w 0 #1
13283   \exp_after:wN \__fp_sub_back_shift:wnnnn
13284   \fi:
13285   ; {#1#2#3#4} {#5}
13286 }

```

(End definition for `\__fp_sub_back_near_o:nnnnnnnnN`, `\__fp_sub_back_near_pack:NNNNNNw`, and `\__fp_sub_back_near_after:wNNNNw`.)

```

\__fp_sub_back_shift:wnnnn
\__fp_sub_back_shift_ii:ww
  \_fp_sub_back_shift_iii:NNNNNNNNw
    \_fp_sub_back_shift_iv:nnnnw

```

`\__fp_sub_back_shift:wnnnn` ;  $\{ \langle Z_1 \rangle \} \{ \langle Z_2 \rangle \} \{ \langle Z_3 \rangle \} \{ \langle Z_4 \rangle \}$  ;  
 This function is called with  $\langle Z_1 \rangle \leq 999$ . Act with `\number` to trim leading zeros from  $\langle Z_1 \rangle \langle Z_2 \rangle$  (we don't do all four blocks at once, since non-zero blocks would then overflow TeX's integers). If the first two blocks are zero, the auxiliary receives an empty #1 and trims #2#30 from leading zeros, yielding a total shift between 7 and 16 to the exponent. Otherwise we get the shift from #1 alone, yielding a result between 1 and 6. Once the exponent is taken care of, trim leading zeros from #1#2#3 (when #1 is empty, the space before #2#3 is ignored), get four blocks of 4 digits and finally clean up. Trailing zeros are added so that digits can be grabbed safely.

```

13287 \cs_new:Npn \__fp_sub_back_shift:wnnnn ; #1#2
13288 {
13289   \exp_after:wN \__fp_sub_back_shift_ii:ww
13290   \__int_value:w #1 #2 0 ;
13291 }
13292 \cs_new:Npn \__fp_sub_back_shift_ii:ww #1 0 ; #2#3 ;
13293 {
13294   \if_meaning:w @ #1 @
13295   - 7
13296   - \exp_after:wN \use_i:nnn
13297   \exp_after:wN \__fp_sub_back_shift_iii:NNNNNNNNw
13298   \__int_value:w #2#3 0 ~ 123456789;
13299   \else:
13300   - \__fp_sub_back_shift_iii:NNNNNNNNw #1 123456789;
13301   \fi:
13302   \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
13303   \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
13304   \exp_after:wN \__fp_sub_back_shift_iv:nnnnw
13305   \exp_after:wN ;
13306   \__int_value:w

```



```

13307      #1 ~ #2#3 0 ~ 0000 0000 0000 000 ;
13308    }
13309    \cs_new:Npn \__fp_sub_back_shift_iii:NNNNNNNNw #1#2#3#4#5#6#7#8#9; {#8}
13310    \cs_new:Npn \__fp_sub_back_shift_iv:nnnnw #1 ; #2 ; { ; #1 ; }

```

(End definition for \\_\_fp\_sub\_back\_shift:wnnnn and others.)

```

\__fp_sub_back_far_o:NnnwnnnnN      \__fp_sub_back_far_o:NnnwnnnnN <rounding> {\langle Y'_1 \rangle} {\langle Y'_2 \rangle}
<extra-digits> ; {\langle X_1 \rangle} {\langle X_2 \rangle} {\langle X_3 \rangle} {\langle X_4 \rangle} <final sign>

```

If the difference is greater than  $10^{\langle expo_x \rangle}$ , call the `very_far` auxiliary. If the result is less than  $10^{\langle expo_x \rangle}$ , call the `not_far` auxiliary. If it is too close to know yet, namely if  $1\langle Y'_1 \rangle\langle Y'_2 \rangle = \langle X_1 \rangle\langle X_2 \rangle\langle X_3 \rangle\langle X_4 \rangle 0$ , then call the `quite_far` auxiliary. We use the odd combination of space and semi-colon delimiters to allow the `not_far` auxiliary to grab each piece individually, the `very_far` auxiliary to use `\__fp_pack_eight:wNNNNNNNN`, and the `quite_far` to ignore the significands easily (using the `; delimiter`).

```

13311    \cs_new:Npn \__fp_sub_back_far_o:NnnwnnnnN #1 #2#3 #4; #5#6#7#8
13312    {
13313      \if_case:w
13314        \if_int_compare:w 1 #2 = #5#6 \use_i:nnnn #7 \exp_stop_f:
13315        \if_int_compare:w #3 = \use_none:n #7#8 0 \exp_stop_f:
13316        0
13317      \else:
13318        \if_int_compare:w #3 > \use_none:n #7#8 0 - \fi: 1
13319      \fi:
13320    \else:
13321      \if_int_compare:w 1 #2 > #5#6 \use_i:nnnn #7 - \fi: 1
13322    \fi:
13323    \exp_stop_f:
13324      \exp_after:wN \__fp_sub_back_quite_far_o:wwNN
13325    \or:   \exp_after:wN \__fp_sub_back_very_far_o:wwwNN
13326    \else: \exp_after:wN \__fp_sub_back_not_far_o:wwwNN
13327    \fi:
13328    #2 ~ #3 ; #5 #6 ~ #7 #8 ; #1
13329  }

```

(End definition for \\_\_fp\_sub\_back\_far\_o:NnnwnnnnN.)

```

\__fp_sub_back_quite_far_o:wwNN
\__fp_sub_back_quite_far_ii:NN

```

The easiest case is when  $x - y$  is extremely close to a power of 10, namely the first digit of  $x$  is 1, and all others vanish when subtracting  $y$ . Then the `<rounding> #3` and the `<final sign> #4` control whether we get 1 or 0.9999999999999999. In the usual round-to-nearest mode, we get 1 whenever the `<rounding>` digit is less than or equal to 5 (remember that the `<rounding>` digit is only equal to 5 if there was no further non-zero digit).

```

13330    \cs_new:Npn \__fp_sub_back_quite_far_o:wwNN #1; #2; #3#4
13331    {
13332      \exp_after:wN \__fp_sub_back_quite_far_ii:NN
13333      \exp_after:wN #3
13334      \exp_after:wN #4
13335    }
13336    \cs_new:Npn \__fp_sub_back_quite_far_ii:NN #1#2
13337    {
13338      \if_case:w \__fp_round_neg:NNN #2 0 #1
13339      \exp_after:wN \use_i:nn
13340    \else:
13341      \exp_after:wN \use_ii:nn

```

```

13342 \fi:
13343 { ; {1000} {0000} {0000} {0000} ; }
13344 { - 1 ; {9999} {9999} {9999} {9999} ; }
13345 }

```

(End definition for `\__fp_sub_back_quite_far_o:wwwNN` and `\__fp_sub_back_quite_far_ii:NN`.)

`\__fp_sub_back_not_far_o:wwwNN`

In the present case,  $x$  and  $y$  have different exponents, but  $y$  is large enough that  $x - y$  has a smaller exponent than  $x$ . Decrement the exponent (with `-1`). Then proceed in a way similar to the `near` auxiliaries seen earlier, but multiplying  $x$  by 10 (`#30` and `#40` below), and with the added quirk that the *rounding* digit has to be taken into account. Namely, we may have to decrease the result by one unit if `\__fp_round_neg:NNN` returns 1. This function expects the *final sign* `#6`, the last digit of `1100000000+#40-#2`, and the *rounding* digit. Instead of redoing the computation for the second argument, we note that `\__fp_round_neg:NNN` only cares about its parity, which is identical to that of the last digit of `#2`.

```

13346 \cs_new:Npn \__fp_sub_back_not_far_o:wwwNN #1 ~ #2; #3 ~ #4; #5#6
13347 {
13348   - 1
13349   \exp_after:wN \__fp_sub_back_near_after:wNNNNw
13350   \__int_value:w \__int_eval:w 1#30 - #1 - 11
13351   \exp_after:wN \__fp_sub_back_near_pack:NNNNNNw
13352   \__int_value:w \__int_eval:w 11 0000 0000 + #40 - #2
13353   - \exp_after:wN \__fp_round_neg:NNN
13354   \exp_after:wN #6
13355   \use_none:n nnnnnnn #2 #5
13356   \exp_after:wN ;
13357 }

```

(End definition for `\__fp_sub_back_not_far_o:wwwNN`.)

`\__fp_sub_back_very_far_o:wwwNN`  
`\__fp_sub_back_very_far_ii_o:nnNwwNN`

The case where  $x - y$  and  $x$  have the same exponent is a bit more tricky, mostly because it cannot reuse the same auxiliaries. Shift the  $y$  significand by adding a leading 0. Then the logic is similar to the `not_far` functions above. Rounding is a bit more complicated: we have two *rounding* digits `#3` and `#6` (from the decimation, and from the new shift) to take into account, and getting the parity of the main result requires a computation. The first `\__int_value:w` triggers the second one because the number is unfinished; we can thus not use 0 in place of 2 there.

```

13358 \cs_new:Npn \__fp_sub_back_very_far_o:wwwNN #1#2#3#4#5#6#7
13359 {
13360   \__fp_pack_eight:wNNNNNNNN
13361   \__fp_sub_back_very_far_ii_o:nnNwwNN
13362   { 0 #1#2#3 #4#5#6#7 }
13363   ;
13364 }
13365 \cs_new:Npn \__fp_sub_back_very_far_ii_o:nnNwwNN #1#2 ; #3 ; #4 ~ #5; #6#7
13366 {
13367   \exp_after:wN \__fp_basics_pack_high:NNNNNw
13368   \__int_value:w \__int_eval:w 1#4 - #1 - 1
13369   \exp_after:wN \__fp_basics_pack_low:NNNNNw
13370   \__int_value:w \__int_eval:w 2#5 - #2
13371   - \exp_after:wN \__fp_round_neg:NNN
13372   \exp_after:wN #7

```

```

13373         \__int_value:w
13374         \if_int_odd:w \__int_eval:w #5 - #2 \__int_eval_end:
13375             1 \else: 2 \fi:
13376         \__int_value:w \__fp_round_digit:Nw #3 #6 ;
13377     \exp_after:wN ;
13378 }

```

(End definition for \\_\_fp\_sub\_back\_very\_far\_o:wwwNN and \\_\_fp\_sub\_back\_very\_far\_ii\_o:nnNwwNN.)

## 26.2 Multiplication

### 26.2.1 Signs, and special numbers

\\_\_fp\*\_o:ww We go through an auxiliary, which is common with \\_\_fp/\_o:ww. The first argument is the operation, used for the invalid operation exception. The second is inserted in a formula to dispatch cases slightly differently between multiplication and division. The third is the operation for normal floating points. The fourth is there for extra cases needed in \\_\_fp/\_o:ww.

```

13379 \cs_new:cpn { __fp*_o:ww }
13380 {
13381     \__fp_mul_cases_o:NnNww
13382     *
13383     { - 2 + }
13384     \__fp_mul_npos_o:Nww
13385     { }
13386 }

```

(End definition for \\_\_fp\*\_o:ww.)

\\_\_fp\_mul\_cases\_o:nNnww Split into 10 cases (12 for division). If both numbers are normal, go to case 0 (same sign) or case 1 (opposite signs): in both cases, call \\_\_fp\_mul\_npos\_o:Nww to do the work. If the first operand is `nan`, go to case 2, in which the second operand is discarded; if the second operand is `nan`, go to case 3, in which the first operand is discarded (note the weird interaction with the final test on signs). Then we separate the case where the first number is normal and the second is zero: this goes to cases 4 and 5 for multiplication, 10 and 11 for division. Otherwise, we do a computation which dispatches the products  $0 \times 0 = 0 \times 1 = 1 \times 0 = 0$  to case 4 or 5 depending on the combined sign, the products  $0 \times \infty$  and  $\infty \times 0$  to case 6 or 7 (invalid operation), and the products  $1 \times \infty = \infty \times 1 = \infty \times \infty = \infty$  to cases 8 and 9. Note that the code for these two cases (which return  $\pm\infty$ ) is inserted as argument #4, because it differs in the case of divisions.

```

13387 \cs_new:Npn \__fp_mul_cases_o:NnNww
13388     #1#2#3#4 \s__fp \__fp_chk:w #5#6#7; \s__fp \__fp_chk:w #8#9
13389 {
13390     \if_case:w \__int_eval:w
13391         \if_int_compare:w #5 #8 = 11 ~
13392             1
13393         \else:
13394             \if_meaning:w 3 #8
13395                 3
13396             \else:
13397                 \if_meaning:w 3 #5
13398                     2
13399                 \else:

```

```

13400         \if_int_compare:w #5 #8 = 10 ~
13401             9 #2 - 2
13402         \else:
13403             (#5 #2 #8) / 2 * 2 + 7
13404         \fi:
13405     \fi:
13406 \fi:
13407 \fi:
13408     \if_meaning:w #6 #9 - 1 \fi:
13409 \__int_eval_end:
13410     \__fp_case_use:nw { #3 0 }
13411 \or: \__fp_case_use:nw { #3 2 }
13412 \or: \__fp_case_return_i_o:ww
13413 \or: \__fp_case_return_ii_o:ww
13414 \or: \__fp_case_return_o:Nww \c_zero_fp
13415 \or: \__fp_case_return_o:Nww \c_minus_zero_fp
13416 \or: \__fp_case_use:nw { \__fp_invalid_operation_o:Nww #1 }
13417 \or: \__fp_case_use:nw { \__fp_invalid_operation_o:Nww #1 }
13418 \or: \__fp_case_return_o:Nww \c_inf_fp
13419 \or: \__fp_case_return_o:Nww \c_minus_inf_fp
13420 #4
13421 \fi:
13422 \s__fp \__fp_chk:w #5 #6 #7;
13423 \s__fp \__fp_chk:w #8 #9
13424 }

```

(End definition for \\_\_fp\_mul\_cases\_o:nNnnnw.)

## 26.2.2 Absolute multiplication

In this subsection, we perform the multiplication of two positive normal numbers.

```

\__fp_mul_npos_o:Nww \__fp_mul_npos_o:Nww <final sign> \s__fp \__fp_chk:w 1 <sign1> {<exp1>}
<body1> ; \s__fp \__fp_chk:w 1 <sign2> {<exp2>} <body2> ;

```

After the computation, \\_\_fp\_sanitize:Nw checks for overflow or underflow. As we did for addition, \\_\_int\_eval:w computes the exponent, catching any shift coming from the computation in the significand. The <final sign> is needed to do the rounding properly in the significand computation. We setup the post-expansion here, triggered by \\_\_fp\_mul\_significand\_o:nnnnNnnnn.

This is also used in l3fp-convert.

```

13425 \cs_new:Npn \__fp_mul_npos_o:Nww
13426 #1 \s__fp \__fp_chk:w #2 #3 #4 #5 ; \s__fp \__fp_chk:w #6 #7 #8 #9 ;
13427 {
13428     \exp_after:wN \__fp_sanitize:Nw
13429     \exp_after:wN #1
13430     \__int_value:w \__int_eval:w
13431     #4 + #8
13432     \__fp_mul_significand_o:nnnnNnnnn #5 #1 #9
13433 }

```

(End definition for \\_\_fp\_mul\_npos\_o:Nww.)

```

\__fp_mul_significand_o:nnnnNnnnn \__fp_mul_significand_o:nnnnNnnnn {<X1>} {<X2>} {<X3>} {<X4>} <sign>
\__fp_mul_significand_drop:NNNNNw {<Y1>} {<Y2>} {<Y3>} {<Y4>}
\__fp_mul_significand_keep:NNNNNw

```

Note the three semicolons at the end of the definition. One is for the last `\__fp_mul_significand_drop:NNNNNw`; one is for `\__fp_round_digit:Nw` later on; and one, preceded by `\exp_after:wN`, which is correctly expanded (within an `\__int_eval:w`), is used by `\__fp_basics_pack_low:NNNNNw`.

The product of two 16 digit integers has 31 or 32 digits, but it is impossible to know which one before computing. The place where we round depends on that number of digits, and may depend on all digits until the last in some rare cases. The approach is thus to compute the 5 first blocks of 4 digits (the first one is between 100 and 9999 inclusive), and a compact version of the remaining 3 blocks. Afterwards, the number of digits is known, and we can do the rounding within yet another set of `\__int_eval:w`.

```

13434 \cs_new:Npn \__fp_mul_significand_o:nnnnNnnnn #1#2#3#4 #5 #6#7#8#9
13435 {
13436   \exp_after:wN \__fp_mul_significand_test_f:NNN
13437   \exp_after:wN #5
13438   \__int_value:w \__int_eval:w 99990000 + #1*#6 +
13439   \exp_after:wN \__fp_mul_significand_keep:NNNNNw
13440   \__int_value:w \__int_eval:w 99990000 + #1*#7 + #2*#6 +
13441   \exp_after:wN \__fp_mul_significand_keep:NNNNNw
13442   \__int_value:w \__int_eval:w 99990000 + #1*#8 + #2*#7 + #3*#6 +
13443   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
13444   \__int_value:w \__int_eval:w 99990000 + #1*#9 + #2*#8 + #3*#7 + #4*#6 +
13445   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
13446   \__int_value:w \__int_eval:w 99990000 + #2*#9 + #3*#8 + #4*#7 +
13447   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
13448   \__int_value:w \__int_eval:w 99990000 + #3*#9 + #4*#8 +
13449   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
13450   \__int_value:w \__int_eval:w 100000000 + #4*#9 ;
13451   ; \exp_after:wN ;
13452 }
13453 \cs_new:Npn \__fp_mul_significand_drop:NNNNNw #1#2#3#4#5 #6;
13454 { #1#2#3#4#5 ; + #6 }
13455 \cs_new:Npn \__fp_mul_significand_keep:NNNNNw #1#2#3#4#5 #6;
13456 { #1#2#3#4#5 ; #6 ; }

```

(End definition for `\__fp_mul_significand_o:nnnnNnnnn`, `\__fp_mul_significand_drop:NNNNNw`, and `\__fp_mul_significand_keep:NNNNNw`.)

```

\__fp_mul_significand_test_f:NNN \__fp_mul_significand_test_f:NNN <sign> 1 <digits 1-8> ; <digits 9-12> ;
<digits 13-16> ; + <digits 17-20> + <digits 21-24> + <digits 25-28> + <digits
29-32> ; \exp_after:wN ;

```

If the *<digit 1>* is non-zero, then for rounding we only care about the digits 16 and 17, and whether further digits are zero or not (check for exact ties). On the other hand, if *<digit 1>* is zero, we care about digits 17 and 18, and whether further digits are zero.

```

13457 \cs_new:Npn \__fp_mul_significand_test_f:NNN #1 #2 #3
13458 {
13459   \if_meaning:w 0 #3
13460     \exp_after:wN \__fp_mul_significand_small_f:NNwwwN
13461   \else:
13462     \exp_after:wN \__fp_mul_significand_large_f:NwwNNNN
13463   \fi:
13464   #1 #3
13465 }

```

(End definition for `\_fp_mul_significand_test_f:NNN`.)

`\_fp_mul_significand_large_f:NwwNNNN` In this branch,  $\langle digit\ 1 \rangle$  is non-zero. The result is thus  $\langle digits\ 1-16 \rangle$ , plus some rounding which depends on the digits 16, 17, and whether all subsequent digits are zero or not. Here, `\_fp_round_digit:Nw` takes digits 17 and further (as an integer expression), and replaces it by a  $\langle rounding\ digit \rangle$ , suitable for `\_fp_round:NNN`.

```

13466 \cs_new:Npn \_fp_mul_significand_large_f:NwwNNNN #1 #2; #3; #4#5#6#7; +
13467   {
13468     \exp_after:wN \_fp_basics_pack_high:NNNNNw
13469     \_int_value:w \_int_eval:w 1#2
13470     \exp_after:wN \_fp_basics_pack_low:NNNNNw
13471     \_int_value:w \_int_eval:w 1#3#4#5#6#7
13472     + \exp_after:wN \_fp_round:NNN
13473     \exp_after:wN #1
13474     \exp_after:wN #7
13475     \_int_value:w \_fp_round_digit:Nw
13476   }

```

(End definition for `\_fp_mul_significand_large_f:NwwNNNN`.)

`\_fp_mul_significand_small_f:NNwwN` In this branch,  $\langle digit\ 1 \rangle$  is zero. Our result is thus  $\langle digits\ 2-17 \rangle$ , plus some rounding which depends on the digits 17, 18, and whether all subsequent digits are zero or not. The 8 digits 1#3 are followed, after expansion of the `small_pack` auxiliary, by the next digit, to form a 9 digit number.

```

13477 \cs_new:Npn \_fp_mul_significand_small_f:NNwwN #1 #2#3; #4#5; #6; + #7
13478   {
13479     - 1
13480     \exp_after:wN \_fp_basics_pack_high:NNNNNw
13481     \_int_value:w \_int_eval:w 1#3#4
13482     \exp_after:wN \_fp_basics_pack_low:NNNNNw
13483     \_int_value:w \_int_eval:w 1#5#6#7
13484     + \exp_after:wN \_fp_round:NNN
13485     \exp_after:wN #1
13486     \exp_after:wN #7
13487     \_int_value:w \_fp_round_digit:Nw
13488   }

```

(End definition for `\_fp_mul_significand_small_f:NNwwN`.)

## 26.3 Division

### 26.3.1 Signs, and special numbers

Time is now ripe to tackle the hardest of the four elementary operations: division.

`\_fp/_o:ww` Filtering special floating point is very similar to what we did for multiplications, with a few variations. Invalid operation exceptions display `/` rather than `*`. In the formula for dispatch, we replace `- 2 +` by `-`. The case of normal numbers is treated using `\_fp_div_npos_o:Nww` rather than `\_fp_mul_npos_o:Nww`. There are two additional cases: if the first operand is normal and the second is a zero, then the division by zero exception is raised: cases 10 and 11 of the `\if_case:w` construction in `\_fp_mul_cases_o:NnNww` are provided as the fourth argument here.

```

13489 \cs_new:cpn { \_fp/_o:ww }

```

```

13490 {
13491   \__fp_mul_cases_o:NnNnw
13492   /
13493   { - }
13494   \__fp_div_npos_o:Nww
13495   {
13496     \or:
13497     \__fp_case_use:nw
13498     { \__fp_division_by_zero_o:NNww \c_inf_fp / }
13499     \or:
13500     \__fp_case_use:nw
13501     { \__fp_division_by_zero_o:NNww \c_minus_inf_fp / }
13502   }
13503 }

```

(End definition for \\_\_fp\_/\_o:ww.)

```

\__fp_div_npos_o:Nww   \__fp_div_npos_o:Nww <final sign> \s__fp \__fp_chk:w 1 <sign_A> {\exp A}
                        {\langle A_1 \rangle} {\langle A_2 \rangle} {\langle A_3 \rangle} {\langle A_4 \rangle} ; \s__fp \__fp_chk:w 1 <sign_Z> {\exp Z}
                        {\langle Z_1 \rangle} {\langle Z_2 \rangle} {\langle Z_3 \rangle} {\langle Z_4 \rangle} ;

```

We want to compute  $A/Z$ . As for multiplication, `\__fp_sanitize:Nw` checks for overflow or underflow; we provide it with the  $\langle final\ sign \rangle$ , and an integer expression in which we compute the exponent. We set up the arguments of `\__fp_div_significand_i_o:wnnw`, namely an integer  $\langle y \rangle$  obtained by adding 1 to the first 5 digits of  $Z$  (explanation given soon below), then the four  $\{\langle A_i \rangle\}$ , then the four  $\{\langle Z_i \rangle\}$ , a semi-colon, and the  $\langle final\ sign \rangle$ , used for rounding at the end.

```

13504 \cs_new:Npn \__fp_div_npos_o:Nww
13505   #1 \s__fp \__fp_chk:w 1 #2 #3 #4 ; \s__fp \__fp_chk:w 1 #5 #6 #7#8#9;
13506   {
13507     \exp_after:wN \__fp_sanitize:Nw
13508     \exp_after:wN #1
13509     \__int_value:w \__int_eval:w
13510     #3 - #6
13511     \exp_after:wN \__fp_div_significand_i_o:wnnw
13512     \__int_value:w \__int_eval:w #7 \use_i:nnnn #8 + 1 ;
13513     #4
13514     {\#7}{\#8}\#9 ;
13515     #1
13516   }

```

(End definition for \\_\_fp\_div\_npos\_o:Nww.)

### 26.3.2 Work plan

In this subsection, we explain how to avoid overflowing  $\text{\TeX}$ 's integers when performing the division of two positive normal numbers.

We are given two numbers,  $A = 0.A_1A_2A_3A_4$  and  $Z = 0.Z_1Z_2Z_3Z_4$ , in blocks of 4 digits, and we know that the first digits of  $A_1$  and of  $Z_1$  are non-zero. To compute  $A/Z$ , we proceed as follows.

- Find an integer  $Q_A \simeq 10^4 A/Z$ .
- Replace  $A$  by  $B = 10^4 A - Q_A Z$ .

- Find an integer  $Q_B \simeq 10^4 B/Z$ .
- Replace  $B$  by  $C = 10^4 B - Q_B Z$ .
- Find an integer  $Q_C \simeq 10^4 C/Z$ .
- Replace  $C$  by  $D = 10^4 C - Q_C Z$ .
- Find an integer  $Q_D \simeq 10^4 D/Z$ .
- Consider  $E = 10^4 D - Q_D Z$ , and ensure correct rounding.

The result is then  $Q = 10^{-4}Q_A + 10^{-8}Q_B + 10^{-12}Q_C + 10^{-16}Q_D + \text{rounding}$ . Since the  $Q_i$  are integers,  $B$ ,  $C$ ,  $D$ , and  $E$  are all exact multiples of  $10^{-16}$ , in other words, computing with 16 digits after the decimal separator yields exact results. The problem is the risk of overflow: in general  $B$ ,  $C$ ,  $D$ , and  $E$  may be greater than 1.

Unfortunately, things are not as easy as they seem. In particular, we want all intermediate steps to be positive, since negative results would require extra calculations at the end. This requires that  $Q_A \leq 10^4 A/Z$  etc. A reasonable attempt would be to define  $Q_A$  as

$$\backslash\text{int\_eval:n}\left\{\frac{A_1 A_2}{Z_1 + 1} - 1\right\} \leq 10^4 \frac{A}{Z}$$

Subtracting 1 at the end takes care of the fact that  $\varepsilon\text{-TeX}$ 's  $\backslash\_int\_eval:w$  rounds divisions instead of truncating (really,  $1/2$  would be sufficient, but we work with integers). We add 1 to  $Z_1$  because  $Z_1 \leq 10^4 Z < Z_1 + 1$  and we need  $Q_A$  to be an underestimate. However, we are now underestimating  $Q_A$  too much: it can be wrong by up to 100, for instance when  $Z = 0.1$  and  $A \simeq 1$ . Then  $B$  could take values up to 10 (maybe more), and a few steps down the line, we would run into arithmetic overflow, since  $\text{TeX}$  can only handle integers less than roughly  $2 \cdot 10^9$ .

A better formula is to take

$$Q_A = \backslash\text{int\_eval:n}\left\{\frac{10 \cdot A_1 A_2}{\lfloor 10^{-3} \cdot Z_1 Z_2 \rfloor + 1} - 1\right\}.$$

This is always less than  $10^9 A/(10^5 Z)$ , as we wanted. In words, we take the 5 first digits of  $Z$  into account, and the 8 first digits of  $A$ , using 0 as a 9-th digit rather than the true digit for efficiency reasons. We shall prove that using this formula to define all the  $Q_i$  avoids any overflow. For convenience, let us denote

$$y = \lfloor 10^{-3} \cdot Z_1 Z_2 \rfloor + 1,$$

so that, taking into account the fact that  $\varepsilon\text{-TeX}$  rounds ties away from zero,

$$\begin{aligned} Q_A &= \left\lfloor \frac{A_1 A_2 0}{y} - \frac{1}{2} \right\rfloor \\ &> \frac{A_1 A_2 0}{y} - \frac{3}{2}. \end{aligned}$$

Note that  $10^4 < y \leq 10^5$ , and  $999 \leq Q_A \leq 99989$ . Also note that this formula does not cause an overflow as long as  $A < (2^{31} - 1)/10^9 \simeq 2.147 \dots$ , since the numerator involves an integer slightly smaller than  $10^9 A$ .



Let us bound  $B$ :

$$\begin{aligned}
10^5 B &= A_1 A_2 0 + 10 \cdot 0 \cdot A_3 A_4 - 10 \cdot Z_1 \cdot Z_2 Z_3 Z_4 \cdot Q_A \\
&< A_1 A_2 0 \cdot \left(1 - 10 \cdot \frac{Z_1 \cdot Z_2 Z_3 Z_4}{y}\right) + \frac{3}{2} \cdot 10 \cdot Z_1 \cdot Z_2 Z_3 Z_4 + 10 \\
&\leq \frac{A_1 A_2 0 \cdot (y - 10 \cdot Z_1 \cdot Z_2 Z_3 Z_4)}{y} + \frac{3}{2} y + 10 \\
&\leq \frac{A_1 A_2 0 \cdot 1}{y} + \frac{3}{2} y + 10 \leq \frac{10^9 A}{y} + 1.6 \cdot y.
\end{aligned}$$

At the last step, we hide 10 into the second term for later convenience. The same reasoning yields

$$\begin{aligned}
10^5 B &< 10^9 A/y + 1.6y, \\
10^5 C &< 10^9 B/y + 1.6y, \\
10^5 D &< 10^9 C/y + 1.6y, \\
10^5 E &< 10^9 D/y + 1.6y.
\end{aligned}$$

The goal is now to prove that none of  $B$ ,  $C$ ,  $D$ , and  $E$  can go beyond  $(2^{31} - 1)/10^9 = 2.147 \dots$ .

Combining the various inequalities together with  $A < 1$ , we get

$$\begin{aligned}
10^5 B &< 10^9/y + 1.6y, \\
10^5 C &< 10^{13}/y^2 + 1.6(y + 10^4), \\
10^5 D &< 10^{17}/y^3 + 1.6(y + 10^4 + 10^8/y), \\
10^5 E &< 10^{21}/y^4 + 1.6(y + 10^4 + 10^8/y + 10^{12}/y^2).
\end{aligned}$$

All of those bounds are convex functions of  $y$  (since every power of  $y$  involved is convex, and the coefficients are positive), and thus maximal at one of the end-points of the allowed range  $10^4 < y \leq 10^5$ . Thus,

$$\begin{aligned}
10^5 B &< \max(1.16 \cdot 10^5, 1.7 \cdot 10^5), \\
10^5 C &< \max(1.32 \cdot 10^5, 1.77 \cdot 10^5), \\
10^5 D &< \max(1.48 \cdot 10^5, 1.777 \cdot 10^5), \\
10^5 E &< \max(1.64 \cdot 10^5, 1.7777 \cdot 10^5).
\end{aligned}$$

All of those bounds are less than  $2.147 \cdot 10^5$ , and we are thus within  $\text{T}_{\text{E}}\text{X}$ 's bounds in all cases!

We later need to have a bound on the  $Q_i$ . Their definitions imply that  $Q_A < 10^9 A/y - 1/2 < 10^5 A$  and similarly for the other  $Q_i$ . Thus, all of them are less than 177770.

The last step is to ensure correct rounding. We have

$$A/Z = \sum_{i=1}^4 (10^{-4i} Q_i) + 10^{-16} E/Z$$

exactly. Furthermore, we know that the result is in  $[0.1, 10)$ , hence will be rounded to a multiple of  $10^{-16}$  or of  $10^{-15}$ , so we only need to know the integer part of  $E/Z$ , and a “rounding” digit encoding the rest. Equivalently, we need to find the integer part of  $2E/Z$ , and determine whether it was an exact integer or not (this serves to detect ties). Since

$$\frac{2E}{Z} = 2 \frac{10^5 E}{10^5 Z} \leq 2 \frac{10^5 E}{10^4} < 36,$$

this integer part is between 0 and 35 inclusive. We let  $\varepsilon\text{-TeX}$  round

$$P = \text{\texttt{\textbackslash int\_eval:n}} \left\{ \frac{2 \cdot E_1 E_2}{Z_1 Z_2} \right\},$$

which differs from  $2E/Z$  by at most

$$\frac{1}{2} + 2 \left| \frac{E}{Z} - \frac{E}{10^{-8} Z_1 Z_2} \right| + 2 \left| \frac{10^8 E - E_1 E_2}{Z_1 Z_2} \right| < 1,$$

( $1/2$  comes from  $\varepsilon\text{-TeX}$ ’s rounding) because each absolute value is less than  $10^{-7}$ . Thus  $P$  is either the correct integer part, or is off by 1; furthermore, if  $2E/Z$  is an integer,  $P = 2E/Z$ . We will check the sign of  $2E - PZ$ . If it is negative, then  $E/Z \in ((P-1)/2, P/2)$ . If it is zero, then  $E/Z = P/2$ . If it is positive, then  $E/Z \in (P/2, (P+1)/2)$ . In each case, we know how to round to an integer, depending on the parity of  $P$ , and the rounding mode.

### 26.3.3 Implementing the significand division

`\_fp\_div\_significand\_i\_o:wnnw`

`\_fp\_div\_significand\_i\_o:wnnw`  $\langle y \rangle$  ;  $\{\langle A_1 \rangle\} \{\langle A_2 \rangle\} \{\langle A_3 \rangle\} \{\langle A_4 \rangle\}$   
 $\{\langle Z_1 \rangle\} \{\langle Z_2 \rangle\} \{\langle Z_3 \rangle\} \{\langle Z_4 \rangle\}$  ;  $\langle sign \rangle$

Compute  $10^6 + Q_A$  (a 7 digit number thanks to the shift), unbrace  $\langle A_1 \rangle$  and  $\langle A_2 \rangle$ , and prepare the  $\langle continuation \rangle$  arguments for 4 consecutive calls to `\_fp\_div\_significand\_calc:wnnnnnnnn`. Each of these calls needs  $\langle y \rangle$  (#1), and it turns out that we need post-expansion there, hence the `\_int\_value:w`. Here, #4 is six brace groups, which give the six first n-type arguments of the `calc` function.

```

13517 \cs_new:Npn \_fp\_div\_significand\_i\_o:wnnw #1 ; #2#3 #4 ;
13518 {
13519   \exp_after:wN \_fp\_div\_significand\_test\_o:w
13520   \_int\_value:w \_int\_eval:w
13521   \exp_after:wN \_fp\_div\_significand\_calc:wnnnnnnnn
13522   \_int\_value:w \_int\_eval:w 999999 + #2 #3 0 / #1 ;
13523   #2 #3 ;
13524   #4
13525   { \exp_after:wN \_fp\_div\_significand\_ii:wN \_int\_value:w #1 }
13526   { \exp_after:wN \_fp\_div\_significand\_ii:wN \_int\_value:w #1 }
13527   { \exp_after:wN \_fp\_div\_significand\_ii:wN \_int\_value:w #1 }
13528   { \exp_after:wN \_fp\_div\_significand\_iii:wnnnnnnn \_int\_value:w #1 }
13529 }

```

(End definition for `\_fp\_div\_significand\_i\_o:wnnw`.)

`\_fp\_div\_significand\_calc:wnnnnnnnn`  
`\_fp\_div\_significand\_calc\_i:wnnnnnnnn`  
`\_fp\_div\_significand\_calc\_ii:wnnnnnnnn`

`\_fp\_div\_significand\_calc:wnnnnnnnn`  $\langle 10^6 + Q_A \rangle$  ;  $\langle A_1 \rangle \langle A_2 \rangle$  ;  $\{\langle A_3 \rangle\}$   
 $\{\langle A_4 \rangle\} \{\langle Z_1 \rangle\} \{\langle Z_2 \rangle\} \{\langle Z_3 \rangle\} \{\langle Z_4 \rangle\} \{\langle continuation \rangle\}$   
 expands to

$$\langle 10^6 + Q_A \rangle \langle continuation \rangle ; \langle B_1 \rangle \langle B_2 \rangle ; \{ \langle B_3 \rangle \} \{ \langle B_4 \rangle \} \{ \langle Z_1 \rangle \} \{ \langle Z_2 \rangle \} \{ \langle Z_3 \rangle \} \{ \langle Z_4 \rangle \}$$

where  $B = 10^4 A - Q_A \cdot Z$ . This function is also used to compute  $C$ ,  $D$ ,  $E$  (with the input shifted accordingly), and is used in `l3fp-expo`.

We know that  $0 < Q_A < 1.8 \cdot 10^5$ , so the product of  $Q_A$  with each  $Z_i$  is within  $\text{T}_{\text{E}}\text{X}$ 's bounds. However, it is a little bit too large for our purposes: we would not be able to use the usual trick of adding a large power of 10 to ensure that the number of digits is fixed.

The bound on  $Q_A$ , implies that  $10^6 + Q_A$  starts with the digit 1, followed by 0 or 1. We test, and call different auxiliaries for the two cases. An earlier implementation did the tests within the computation, but since we added a  $\langle continuation \rangle$ , this is not possible because the macro has 9 parameters.

The result we want is then (the overall power of 10 is arbitrary):

$$10^{-4}(\#2 - \#1 \cdot \#5 - 10 \cdot \langle i \rangle \cdot \#5\#6) + 10^{-8}(\#3 - \#1 \cdot \#6 - 10 \cdot \langle i \rangle \cdot \#7) \\ + 10^{-12}(\#4 - \#1 \cdot \#7 - 10 \cdot \langle i \rangle \cdot \#8) + 10^{-16}(-\#1 \cdot \#8),$$

where  $\langle i \rangle$  stands for the  $10^5$  digit of  $Q_A$ , which is 0 or 1, and  $\#1$ ,  $\#2$ , *etc.* are the parameters of either auxiliary. The factors of 10 come from the fact that  $Q_A = 10 \cdot 10^4 \cdot \langle i \rangle + \#1$ . As usual, to combine all the terms, we need to choose some shifts which must ensure that the number of digits of the second, third, and fourth terms are each fixed. Here, the positive contributions are at most  $10^8$  and the negative contributions can go up to  $10^9$ . Indeed, for the auxiliary with  $\langle i \rangle = 1$ ,  $\#1$  is at most 80000, leading to contributions of at worse  $-8 \cdot 10^8 4$ , while the other negative term is very small  $< 10^6$  (except in the first expression, where we don't care about the number of digits); for the auxiliary with  $\langle i \rangle = 0$ ,  $\#1$  can go up to 99999, but there is no other negative term. Hence, a good choice is  $2 \cdot 10^9$ , which produces totals in the range  $[10^9, 2.1 \cdot 10^9]$ . We are flirting with  $\text{T}_{\text{E}}\text{X}$ 's limits once more.

```

13530 \cs_new:Npn \__fp_div_significand_calc:wwnnnnnnn #1#
13531 {
13532   \if_meaning:w 1 #1
13533     \exp_after:wN \__fp_div_significand_calc_i:wwnnnnnnn
13534   \else:
13535     \exp_after:wN \__fp_div_significand_calc_ii:wwnnnnnnn
13536   \fi:
13537 }
13538 \cs_new:Npn \__fp_div_significand_calc_i:wwnnnnnnn #1; #2;#3#4 #5#6#7#8 #9
13539 {
13540   1 1 #1
13541   #9 \exp_after:wN ;
13542   \__int_value:w \__int_eval:w \c__fp_Bigg_leading_shift_int
13543   + #2 - #1 * #5 - #5#60
13544   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
13545   \__int_value:w \__int_eval:w \c__fp_Bigg_middle_shift_int
13546   + #3 - #1 * #6 - #70
13547   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
13548   \__int_value:w \__int_eval:w \c__fp_Bigg_middle_shift_int
13549   + #4 - #1 * #7 - #80
13550   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
13551   \__int_value:w \__int_eval:w \c__fp_Bigg_trailing_shift_int
13552   - #1 * #8 ;

```

```

13553     {#5}{#6}{#7}{#8}
13554   }
13555   \cs_new:Npn \__fp_div_significand_calc_ii:wwnnnnnnn #1; #2;#3#4 #5#6#7#8 #9
13556   {
13557     1 0 #1
13558     #9 \exp_after:wN ;
13559     \__int_value:w \__int_eval:w \c__fp_Bigg_leading_shift_int
13560     + #2 - #1 * #5
13561     \exp_after:wN \__fp_pack_Bigg:NNNNNNw
13562     \__int_value:w \__int_eval:w \c__fp_Bigg_middle_shift_int
13563     + #3 - #1 * #6
13564     \exp_after:wN \__fp_pack_Bigg:NNNNNNw
13565     \__int_value:w \__int_eval:w \c__fp_Bigg_middle_shift_int
13566     + #4 - #1 * #7
13567     \exp_after:wN \__fp_pack_Bigg:NNNNNNw
13568     \__int_value:w \__int_eval:w \c__fp_Bigg_trailing_shift_int
13569     - #1 * #8 ;
13570     {#5}{#6}{#7}{#8}
13571   }

```

(End definition for \\_\_fp\_div\_significand\_calc:wwnnnnnnn, \\_\_fp\_div\_significand\_calc\_i:wwnnnnnnn, and \\_\_fp\_div\_significand\_calc\_ii:wwnnnnnnn.)

```

\__fp_div_significand_ii:wwn    \__fp_div_significand_ii:wwn ⟨y⟩ ; ⟨B1⟩ ; {⟨B2⟩} {⟨B3⟩} {⟨B4⟩} {⟨Z1⟩}
                                {⟨Z2⟩} {⟨Z3⟩} {⟨Z4⟩} ⟨continuations⟩ ⟨sign⟩

```

Compute  $Q_B$  by evaluating  $\langle B_1 \rangle \langle B_2 \rangle 0 / y - 1$ . The result is output to the left, in an  $\backslash\_int\_eval:w$  which we start now. Once that is evaluated (and the other  $Q_i$  also, since later expansions are triggered by this one), a packing auxiliary takes care of placing the digits of  $Q_B$  in an appropriate way for the final addition to obtain  $Q$ . This auxiliary is also used to compute  $Q_C$  and  $Q_D$  with the inputs  $C$  and  $D$  instead of  $B$ .

```

13572 \cs_new:Npn \__fp_div_significand_ii:wwn #1; #2;#3
13573 {
13574   \exp_after:wN \__fp_div_significand_pack:NNN
13575   \__int_value:w \__int_eval:w
13576   \exp_after:wN \__fp_div_significand_calc:wwnnnnnnn
13577   \__int_value:w \__int_eval:w 999999 + #2 #3 0 / #1 ; #2 #3 ;
13578 }

```

(End definition for \\_\_fp\_div\_significand\_ii:wwn.)

```

\__fp_div_significand_iii:wwnnnnn    \__fp_div_significand_iii:wwnnnnn ⟨y⟩ ; ⟨E1⟩ ; {⟨E2⟩} {⟨E3⟩} {⟨E4⟩}
                                       {⟨Z1⟩} {⟨Z2⟩} {⟨Z3⟩} {⟨Z4⟩} ⟨sign⟩

```

We compute  $P \simeq 2E/Z$  by rounding  $2E_1E_2/Z_1Z_2$ . Note the first 0, which multiplies  $Q_D$  by 10: we later add (roughly)  $5 \cdot P$ , which amounts to adding  $P/2 \simeq E/Z$  to  $Q_D$ , the appropriate correction from a hypothetical  $Q_E$ .

```

13579 \cs_new:Npn \__fp_div_significand_iii:wwnnnnn #1; #2;#3#4#5 #6#7
13580 {
13581   0
13582   \exp_after:wN \__fp_div_significand_iv:wwnnnnnnn
13583   \__int_value:w \__int_eval:w ( 2 * #2 #3 ) / #6 #7 ; % <- P
13584   #2 ; {#3} {#4} {#5}
13585   {#6} {#7}
13586 }

```

(End definition for `\_fp_div_significand_iii:wwnnnnn`.)

`\_fp_div_significand_iv:wwnnnnnn`  
`\_fp_div_significand_v:NNw`  
`\_fp_div_significand_vi:Nw`

`\_fp_div_significand_iv:wwnnnnnn`  $\langle P \rangle$  ;  $\langle E_1 \rangle$  ;  $\{\langle E_2 \rangle\}$   $\{\langle E_3 \rangle\}$   $\{\langle E_4 \rangle\}$   
 $\{\langle Z_1 \rangle\}$   $\{\langle Z_2 \rangle\}$   $\{\langle Z_3 \rangle\}$   $\{\langle Z_4 \rangle\}$   $\langle sign \rangle$

This adds to the current expression  $(10^7 + 10 \cdot Q_D)$  a contribution of  $5 \cdot P + \text{sign}(T)$  with  $T = 2E - PZ$ . This amounts to adding  $P/2$  to  $Q_D$ , with an extra  $\langle \text{rounding} \rangle$  digit. This  $\langle \text{rounding} \rangle$  digit is 0 or 5 if  $T$  does not contribute, *i.e.*, if  $0 = T = 2E - PZ$ , in other words if  $10^{16}A/Z$  is an integer or half-integer. Otherwise it is in the appropriate range,  $[1, 4]$  or  $[6, 9]$ . This is precise enough for rounding purposes (in any mode).

It seems an overkill to compute  $T$  exactly as I do here, but I see no faster way right now.

Once more, we need to be careful and show that the calculation `#1 · #6#7` below does not cause an overflow: naively,  $P$  can be up to 35, and `#6#7` up to  $10^8$ , but both cannot happen simultaneously. To show that things are fine, we split in two (non-disjoint) cases.

- For  $P < 10$ , the product obeys  $P \cdot \text{\#6\#7} < 10^8 \cdot P < 10^9$ .
- For large  $P \geq 3$ , the rounding error on  $P$ , which is at most 1, is less than a factor of 2, hence  $P \leq 4E/Z$ . Also,  $\text{\#6\#7} \leq 10^8 \cdot Z$ , hence  $P \cdot \text{\#6\#7} \leq 4E \cdot 10^8 < 10^9$ .

Both inequalities could be made tighter if needed.

Note however that  $P \cdot \text{\#8\#9}$  may overflow, since the two factors are now independent, and the result may reach  $3.5 \cdot 10^9$ . Thus we compute the two lower levels separately. The rest is standard, except that we use `+` as a separator (ending integer expressions explicitly).  $T$  is negative if the first character is `-`, it is positive if the first character is neither 0 nor `-`. It is also positive if the first character is 0 and second argument of `\_fp_div_significand_vi:Nw`, a sum of several terms, is also zero. Otherwise, there was an exact agreement:  $T = 0$ .

```

13587 \cs_new:Npn \_fp_div_significand_iv:wwnnnnnn #1; #2; #3#4#5 #6#7#8#9
13588 {
13589   + 5 * #1
13590   \exp_after:wN \_fp_div_significand_vi:Nw
13591   \__int_value:w \__int_eval:w -20 + 2*#2#3 - #1*#6#7 +
13592   \exp_after:wN \_fp_div_significand_v:NN
13593   \__int_value:w \__int_eval:w 199980 + 2*#4 - #1*#8 +
13594   \exp_after:wN \_fp_div_significand_v:NN
13595   \__int_value:w \__int_eval:w 200000 + 2*#5 - #1*#9 ;
13596 }
13597 \cs_new:Npn \_fp_div_significand_v:NN #1#2 { #1#2 \__int_eval_end: + }
13598 \cs_new:Npn \_fp_div_significand_vi:Nw #1#2;
13599 {
13600   \if_meaning:w 0 #1
13601     \if_int_compare:w \__int_eval:w #2 > 0 + 1 \fi:
13602   \else:
13603     \if_meaning:w - #1 - \else: + \fi: 1
13604   \fi:
13605   ;
13606 }

```

(End definition for `\_fp_div_significand_iv:wwnnnnnn`, `\_fp_div_significand_v:NNw`, and `\_fp_div_significand_vi:Nw`.)

`\_fp_div_significand_pack:NNN` At this stage, we are in the following situation:  $\text{\TeX}$  is in the process of expanding several integer expressions, thus functions at the bottom expand before those above.

```
\_fp_div_significand_test_o:w 10^6 + Q_A \_fp_div_significand_-
pack:NNN 10^6 + Q_B \_fp_div_significand_pack:NNN 10^6 + Q_C \_fp_-
div_significand_pack:NNN 10^7 + 10 \cdot Q_D + 5 \cdot P + \varepsilon ; \langle sign \rangle
```

Here,  $\varepsilon = \text{sign}(T)$  is 0 in case  $2E = PZ$ , 1 in case  $2E > PZ$ , which means that  $P$  was the correct value, but not with an exact quotient, and  $-1$  if  $2E < PZ$ , *i.e.*,  $P$  was an overestimate. The packing function we define now does nothing special: it removes the  $10^6$  and carries two digits (for the  $10^5$ 's and the  $10^4$ 's).

```
13607 \cs_new:Npn \_fp_div_significand_pack:NNN 1 #1 #2 { + #1 #2 ; }
```

(End definition for `\_fp_div_significand_pack:NNN`.)

```
\_fp_div_significand_test_o:w \_fp_div_significand_test_o:w 1 0 \langle 5d \rangle ; \langle 4d \rangle ; \langle 4d \rangle ; \langle 5d \rangle ; \langle sign \rangle
```

The reason we know that the first two digits are 1 and 0 is that the final result is known to be between 0.1 (inclusive) and 10, hence  $\widetilde{Q}_A$  (the tilde denoting the contribution from the other  $Q_i$ ) is at most 99999, and  $10^6 + \widetilde{Q}_A = 10 \dots$ .

It is now time to round. This depends on how many digits the final result will have.

```
13608 \cs_new:Npn \_fp_div_significand_test_o:w 10 #1
13609 {
13610   \if_meaning:w 0 #1
13611     \exp_after:wN \_fp_div_significand_small_o:wwwNNNNwN
13612   \else:
13613     \exp_after:wN \_fp_div_significand_large_o:wwwNNNNwN
13614   \fi:
13615   #1
13616 }
```

(End definition for `\_fp_div_significand_test_o:w`.)

```
\_fp_div_significand_small_o:wwwNNNNwN \_fp_div_significand_small_o:wwwNNNNwN 0 \langle 4d \rangle ; \langle 4d \rangle ; \langle 4d \rangle ; \langle 5d \rangle
; \langle final sign \rangle
```

Standard use of the functions `\_fp_basics_pack_low:NNNNw` and `\_fp_basics_pack_high:NNNNw`. We finally get to use the  $\langle final\ sign \rangle$  which has been sitting there for a while.

```
13617 \cs_new:Npn \_fp_div_significand_small_o:wwwNNNNwN
13618   0 #1; #2; #3; #4#5#6#7#8; #9
13619 {
13620   \exp_after:wN \_fp_basics_pack_high:NNNNw
13621   \_int_value:w \_int_eval:w 1 #1#2
13622   \exp_after:wN \_fp_basics_pack_low:NNNNw
13623   \_int_value:w \_int_eval:w 1 #3#4#5#6#7
13624   + \_fp_round:NNN #9 #7 #8
13625   \exp_after:wN ;
13626 }
```

(End definition for `\_fp_div_significand_small_o:wwwNNNNwN`.)

```

\__fp_div_significand_large_o:wwwNNNNwN \__fp_div_significand_large_o:wwwNNNNwN <5d> ; <4d> ; <4d> ; <5d> ;
<sign>

```

We know that the final result cannot reach 10, hence 1#1#2, together with contributions from the level below, cannot reach  $2 \cdot 10^9$ . For rounding, we build the *<rounding digit>* from the last two of our 18 digits.

```

13627 \cs_new:Npn \__fp_div_significand_large_o:wwwNNNNwN
13628   #1; #2; #3; #4#5#6#7#8; #9
13629   {
13630     + 1
13631     \exp_after:wN \__fp_basics_pack_weird_high:NNNNNNNNw
13632     \__int_value:w \__int_eval:w 1 #1 #2
13633     \exp_after:wN \__fp_basics_pack_weird_low:NNNNw
13634     \__int_value:w \__int_eval:w 1 #3 #4 #5 #6 +
13635     \exp_after:wN \__fp_round:NNN
13636     \exp_after:wN #9
13637     \exp_after:wN #6
13638     \__int_value:w \__fp_round_digit:Nw #7 #8 ;
13639     \exp_after:wN ;
13640   }

```

(End definition for \\_\_fp\_div\_significand\_large\_o:wwwNNNNwN.)

## 26.4 Square root

\\_\_fp\_sqrt\_o:w Zeros are unchanged:  $\sqrt{-0} = -0$  and  $\sqrt{+0} = +0$ . Negative numbers (other than  $-0$ ) have no real square root. Positive infinity, and `nan`, are unchanged. Finally, for normal positive numbers, there is some work to do.

```

13641 \cs_new:Npn \__fp_sqrt_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
13642   {
13643     \if_meaning:w 0 #2 \__fp_case_return_same_o:w \fi:
13644     \if_meaning:w 2 #3
13645       \__fp_case_use:nw { \__fp_invalid_operation_o:nw { sqrt } }
13646     \fi:
13647     \if_meaning:w 1 #2 \else: \__fp_case_return_same_o:w \fi:
13648     \__fp_sqrt_npos_o:w
13649     \s__fp \__fp_chk:w #2 #3 #4;
13650   }

```

(End definition for \\_\_fp\_sqrt\_o:w.)

\\_\_fp\_sqrt\_npos\_o:w Prepare \\_\_fp\_sanitize:Nw to receive the final sign 0 (the result is always positive) and the exponent, equal to half of the exponent #1 of the argument. If the exponent #1 is even, find a first approximation of the square root of the significand  $10^8 a_1 + a_2 = 10^8 \#2\#3 + \#4\#5$  through Newton's method, starting at  $x = 57234133 \simeq 10^{7.75}$ . Otherwise, first shift the significand of of the argument by one digit, getting  $a'_1 \in [10^6, 10^7)$  instead of  $[10^7, 10^8)$ , then use Newton's method starting at  $17782794 \simeq 10^{7.25}$ .

```

13651 \cs_new:Npn \__fp_sqrt_npos_o:w \s__fp \__fp_chk:w 1 0 #1#2#3#4#5;
13652   {
13653     \exp_after:wN \__fp_sanitize:Nw
13654     \exp_after:wN 0
13655     \__int_value:w \__int_eval:w
13656     \if_int_odd:w #1 \exp_stop_f:
13657       \exp_after:wN \__fp_sqrt_npos_auxi_o:wwwNNN

```

```

13658      \fi:
13659      #1 / 2
13660      \__fp_sqrt_Newton_o:wnn 56234133; 0; {#2#3} {#4#5} 0
13661    }
13662 \cs_new:Npn \__fp_sqrt_npos_auxi_o:wnnnN #1 / 2 #2; 0; #3#4#5
13663 {
13664   ( #1 + 1 ) / 2
13665   \__fp_pack_eight:wNNNNNNNN
13666   \__fp_sqrt_npos_auxii_o:wNNNNNNNN
13667   ;
13668   0 #3 #4
13669 }
13670 \cs_new:Npn \__fp_sqrt_npos_auxii_o:wNNNNNNNN #1; #2#3#4#5#6#7#8#9
13671 { \__fp_sqrt_Newton_o:wnn 17782794; 0; {#1} {#2#3#4#5#6#7#8#9} }

```

(End definition for `\__fp_sqrt_npos_o:w`, `\__fp_sqrt_npos_auxi_o:wnnnN`, and `\__fp_sqrt_npos_auxii_o:wNNNNNNNN`.)

`\__fp_sqrt_Newton_o:wnn`

Newton's method maps  $x \mapsto [(x + [10^8 a_1/x])/2]$  in each iteration, where  $[b/c]$  denotes  $\varepsilon$ -TeX's division. This division rounds the real number  $b/c$  to the closest integer, rounding ties away from zero, hence when  $c$  is even,  $b/c - 1/2 + 1/c \leq [b/c] \leq b/c + 1/2$  and when  $c$  is odd,  $b/c - 1/2 + 1/(2c) \leq [b/c] \leq b/c + 1/2 - 1/(2c)$ . For all  $c$ ,  $b/c - 1/2 + 1/(2c) \leq [b/c] \leq b/c + 1/2$ .

Let us prove that the method converges when implemented with  $\varepsilon$ -TeX integer division, for any  $10^6 \leq a_1 < 10^8$  and starting value  $10^6 \leq x < 10^8$ . Using the inequalities above and the arithmetic-geometric inequality  $(x + t)/2 \geq \sqrt{xt}$  for  $t = 10^8 a_1/x$ , we find

$$x' = \left\lfloor \frac{x + [10^8 a_1/x]}{2} \right\rfloor \geq \frac{x + 10^8 a_1/x - 1/2 + 1/(2x)}{2} \geq \sqrt{10^8 a_1} - \frac{1}{4} + \frac{1}{4x}.$$

After any step of iteration, we thus have  $\delta = x - \sqrt{10^8 a_1} \geq -0.25 + 0.25 \cdot 10^{-8}$ . The new difference  $\delta' = x' - \sqrt{10^8 a_1}$  after one step is bounded above as

$$x' - \sqrt{10^8 a_1} \leq \frac{x + 10^8 a_1/x + 1/2}{2} + \frac{1}{2} - \sqrt{10^8 a_1} \leq \frac{\delta}{2} \frac{\delta}{\sqrt{10^8 a_1} + \delta} + \frac{3}{4}.$$

For  $\delta > 3/2$ , this last expression is  $\leq \delta/2 + 3/4 < \delta$ , hence  $\delta$  decreases at each step: since all  $x$  are integers,  $\delta$  must reach a value  $-1/4 < \delta \leq 3/2$ . In this range of values, we get  $\delta' \leq \frac{3}{4} \frac{3}{2\sqrt{10^8 a_1}} + \frac{3}{4} \leq 0.75 + 1.125 \cdot 10^{-7}$ . We deduce that the difference  $\delta = x - \sqrt{10^8 a_1}$  eventually reaches a value in the interval  $[-0.25 + 0.25 \cdot 10^{-8}, 0.75 + 11.25 \cdot 10^{-8}]$ , whose width is  $1 + 11 \cdot 10^{-8}$ . The corresponding interval for  $x$  may contain two integers, hence  $x$  might oscillate between those two values.

However, the fact that  $x \mapsto x - 1$  and  $x - 1 \mapsto x$  puts stronger constraints, which are not compatible: the first implies

$$x + [10^8 a_1/x] \leq 2x - 2$$

hence  $10^8 a_1/x \leq x - 3/2$ , while the second implies

$$x - 1 + [10^8 a_1/(x - 1)] \geq 2x - 1$$

hence  $10^8 a_1/(x - 1) \geq x - 1/2$ . Combining the two inequalities yields  $x^2 - 3x/2 \geq 10^8 a_1 \geq x - 3x/2 + 1/2$ , which cannot hold. Therefore, the iteration always converges to a single



integer  $x$ . To stop the iteration when two consecutive results are equal, the function `\_fp_sqrt_Newton_o:wnn` receives the newly computed result as `#1`, the previous result as `#2`, and  $a_1$  as `#3`. Note that  $\varepsilon$ -TeX combines the computation of a multiplication and a following division, thus avoiding overflow in `#3 * 100000000 / #1`. In any case, the result is within  $[10^7, 10^8]$ .

```

13672 \cs_new:Npn \_fp_sqrt_Newton_o:wnn #1; #2; #3
13673 {
13674   \if_int_compare:w #1 = #2 \exp_stop_f:
13675     \exp_after:wN \_fp_sqrt_auxi_o:NNNNwnnnN
13676     \_int_value:w \_int_eval:w 9999 9999 +
13677     \exp_after:wN \_fp_use_none_until_s:w
13678   \fi:
13679   \exp_after:wN \_fp_sqrt_Newton_o:wnn
13680   \_int_value:w \_int_eval:w (#1 + #3 * 1 0000 0000 / #1) / 2 ;
13681   #1; {#3}
13682 }

```

(End definition for `\_fp_sqrt_Newton_o:wnn`.)

`\_fp_sqrt_auxi_o:NNNNwnnnN`

This function is followed by  $10^8 + x - 1$ , which has 9 digits starting with 1, then ;  $\{ \langle a_1 \rangle \} \{ \langle a_2 \rangle \} \langle a' \rangle$ . Here,  $x \simeq \sqrt{10^8 a_1}$  and we want to estimate the square root of  $a = 10^{-8} a_1 + 10^{-16} a_2 + 10^{-17} a'$ . We set up an initial underestimate

$$y = (x - 1)10^{-8} + 0.2499998875 \cdot 10^{-8} \lesssim \sqrt{a}.$$

From the inequalities shown earlier, we know that  $y \leq \sqrt{10^{-8} a_1} \leq \sqrt{a}$  and that  $\sqrt{10^{-8} a_1} \leq y + 10^{-8} + 11 \cdot 10^{-16}$  hence (using  $0.1 \leq y \leq \sqrt{a} \leq 1$ )

$$a - y^2 \leq 10^{-8} a_1 + 10^{-8} - y^2 \leq (y + 10^{-8} + 11 \cdot 10^{-16})^2 - y^2 + 10^{-8} < 3.2 \cdot 10^{-8},$$

and  $\sqrt{a} - y = (a - y^2)/(\sqrt{a} + y) \leq 16 \cdot 10^{-8}$ . Next, `\_fp_sqrt_auxii_o:NnnnnnnnnN` is called several times to get closer and closer underestimates of  $\sqrt{a}$ . By construction, the underestimates  $y$  are always increasing,  $a - y^2 < 3.2 \cdot 10^{-8}$  for all. Also,  $y < 1$ .

```

13683 \cs_new:Npn \_fp_sqrt_auxi_o:NNNNwnnnN 1 #1#2#3#4#5;
13684 {
13685   \_fp_sqrt_auxii_o:NnnnnnnnnN
13686   \_fp_sqrt_auxiii_o:wnnnnnnnnn
13687   {#1#2#3#4} {#5} {2499} {9988} {7500}
13688 }

```

(End definition for `\_fp_sqrt_auxi_o:NNNNwnnnN`.)

`\_fp_sqrt_auxii_o:NnnnnnnnnN`

This receives a continuation function `#1`, then five blocks of 4 digits for  $y$ , then two 8-digit blocks and a single digit for  $a$ . A common estimate of  $\sqrt{a} - y = (a - y^2)/(\sqrt{a} + y)$  is  $(a - y^2)/(2y)$ , which leads to alternating overestimates and underestimates. We tweak this, to only work with underestimates (no need then to worry about signs in the computation). Each step finds the largest integer  $j \leq 6$  such that  $10^{4j}(a - y^2) < 2 \cdot 10^8$ , then computes the integer (with  $\varepsilon$ -TeX's rounding division)

$$10^{4j} z = \left[ ([10^{4j}(a - y^2)] - 257) \cdot (0.5 \cdot 10^8) / [10^8 y + 1] \right].$$

The choice of  $j$  ensures that  $10^{4j} z < 2 \cdot 10^8 \cdot 0.5 \cdot 10^8 / 10^7 = 10^9$ , thus  $10^9 + 10^{4j} z$  has exactly 10 digits, does not overflow TeX's integer range, and starts with 1. Incidentally, since all  $a - y^2 \leq 3.2 \cdot 10^{-8}$ , we know that  $j \geq 3$ .

Let us show that  $z$  is an underestimate of  $\sqrt{a}-y$ . On the one hand,  $\sqrt{a}-y \leq 16 \cdot 10^{-8}$  because this holds for the initial  $y$  and values of  $y$  can only increase. On the other hand, the choice of  $j$  implies that  $\sqrt{a}-y \leq 5(\sqrt{a}+y)(\sqrt{a}-y) = 5(a-y^2) < 10^{9-4j}$ . For  $j = 3$ , the first bound is better, while for larger  $j$ , the second bound is better. For all  $j \in [3, 6]$ , we find  $\sqrt{a}-y < 16 \cdot 10^{-2j}$ . From this, we deduce that

$$10^{4j}(\sqrt{a}-y) = \frac{10^{4j}(a-y^2-(\sqrt{a}-y)^2)}{2y} \geq \frac{\lfloor 10^{4j}(a-y^2) \rfloor - 257}{2 \cdot 10^{-8} \lfloor 10^8 y + 1 \rfloor} + \frac{1}{2}$$

where we have replaced the bound  $10^{4j}(16 \cdot 10^{-2j}) = 256$  by 257 and extracted the corresponding term  $1/(2 \cdot 10^{-8} \lfloor 10^8 y + 1 \rfloor) \geq 1/2$ . Given that  $\varepsilon$ -TeX's integer division obeys  $\lfloor b/c \rfloor \leq b/c + 1/2$ , we deduce that  $10^{4j}z \leq 10^{4j}(\sqrt{a}-y)$ , hence  $y+z \leq \sqrt{a}$  is an underestimate of  $\sqrt{a}$ , as claimed. One implementation detail: because the computation involves  $-4*4 - 2*3*5 - 2*2*6$  which may be as low as  $-5 \cdot 10^8$ , we need to use the `pack_big` functions, and the big shifts.

```

13689 \cs_new:Npn \__fp_sqrt_auxii_o:NnnnnnnN #1 #2#3#4#5#6 #7#8#9
13690 {
13691   \exp_after:wN #1
13692   \__int_value:w \__int_eval:w \c__fp_big_leading_shift_int
13693   + #7 - #2 * #2
13694   \exp_after:wN \__fp_pack_big:NNNNNNw
13695   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
13696   - 2 * #2 * #3
13697   \exp_after:wN \__fp_pack_big:NNNNNNw
13698   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
13699   + #8 - #3 * #3 - 2 * #2 * #4
13700   \exp_after:wN \__fp_pack_big:NNNNNNw
13701   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
13702   - 2 * #3 * #4 - 2 * #2 * #5
13703   \exp_after:wN \__fp_pack_big:NNNNNNw
13704   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
13705   + #9 000 0000 - #4 * #4 - 2 * #3 * #5 - 2 * #2 * #6
13706   \exp_after:wN \__fp_pack_big:NNNNNNw
13707   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
13708   - 2 * #4 * #5 - 2 * #3 * #6
13709   \exp_after:wN \__fp_pack_big:NNNNNNw
13710   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
13711   - #5 * #5 - 2 * #4 * #6
13712   \exp_after:wN \__fp_pack_big:NNNNNNw
13713   \__int_value:w \__int_eval:w
13714   \c__fp_big_middle_shift_int
13715   - 2 * #5 * #6
13716   \exp_after:wN \__fp_pack_big:NNNNNNw
13717   \__int_value:w \__int_eval:w
13718   \c__fp_big_trailing_shift_int
13719   - #6 * #6 ;
13720   % (
13721   - 257 ) * 5000 0000 / (#2#3 + 1) + 10 0000 0000 ;
13722   {#2}{#3}{#4}{#5}{#6} {#7}{#8}{#9}
13723 }

```

(End definition for `\__fp_sqrt_auxii_o:NnnnnnnN`.)

```

    \_fp_sqrt_auxiii_o:wnnnnnnnn
  \_fp_sqrt_auxiv_o:NNNNNw
  \_fp_sqrt_auxv_o:NNNNNw
  \_fp_sqrt_auxvi_o:NNNNNw
  \_fp_sqrt_auxvii_o:NNNNNw

```

We receive here the difference  $a - y^2 = d = \sum_i d_i \cdot 10^{-4i}$ , as  $\langle d_2 \rangle ; \{\langle d_3 \rangle\} \dots \{\langle d_{10} \rangle\}$ , where each block has 4 digits, except  $\langle d_2 \rangle$ . This function finds the largest  $j \leq 6$  such that  $10^{4j}(a - y^2) < 2 \cdot 10^8$ , then leaves an open parenthesis and the integer  $\lfloor 10^{4j}(a - y^2) \rfloor$  in an integer expression. The closing parenthesis is provided by the caller `\_fp_sqrt_auxii_o:NNnnnnnnN`, which completes the expression

$$10^{4j}z = \left[ (\lfloor 10^{4j}(a - y^2) \rfloor - 257) \cdot (0.5 \cdot 10^8) / \lfloor 10^8 y + 1 \rfloor \right]$$

for an estimate of  $10^{4j}(\sqrt{a} - y)$ . If  $d_2 \geq 2$ ,  $j = 3$  and the `auxiv` auxiliary receives  $10^{12}z$ . If  $d_2 \leq 1$  but  $10^4 d_2 + d_3 \geq 2$ ,  $j = 4$  and the `auxv` auxiliary is called, and receives  $10^{16}z$ , and so on. In all those cases, the `auxviii` auxiliary is set up to add  $z$  to  $y$ , then go back to the `auxii` step with continuation `auxiii` (the function we are currently describing). The maximum value of  $j$  is 6, regardless of whether  $10^{12}d_2 + 10^8 d_3 + 10^4 d_4 + d_5 \geq 1$ . In this last case, we detect when  $10^{24}z < 10^7$ , which essentially means  $\sqrt{a} - y \lesssim 10^{-17}$ : once this threshold is reached, there is enough information to find the correctly rounded  $\sqrt{a}$  with only one more call to `\_fp_sqrt_auxii_o:NNnnnnnnN`. Note that the iteration cannot be stuck before reaching  $j = 6$ , because for  $j < 6$ , one has  $2 \cdot 10^8 \leq 10^{4(j+1)}(a - y^2)$ , hence

$$10^{4j}z \geq \frac{(20000 - 257)(0.5 \cdot 10^8)}{\lfloor 10^8 y + 1 \rfloor} \geq (20000 - 257) \cdot 0.5 > 0.$$

```

13724 \cs_new:Npn \_fp_sqrt_auxiii_o:wnnnnnnnn
13725   #1; #2#3#4#5#6#7#8#9
13726   {
13727     \if_int_compare:w #1 > 1 \exp_stop_f:
13728     \exp_after:wN \_fp_sqrt_auxiv_o:NNNNNw
13729     \__int_value:w \__int_eval:w (#1#2 %)
13730   \else:
13731     \if_int_compare:w #1#2 > 1 \exp_stop_f:
13732     \exp_after:wN \_fp_sqrt_auxv_o:NNNNNw
13733     \__int_value:w \__int_eval:w (#1#2#3 %)
13734   \else:
13735     \if_int_compare:w #1#2#3 > 1 \exp_stop_f:
13736     \exp_after:wN \_fp_sqrt_auxvi_o:NNNNNw
13737     \__int_value:w \__int_eval:w (#1#2#3#4 %)
13738   \else:
13739     \exp_after:wN \_fp_sqrt_auxvii_o:NNNNNw
13740     \__int_value:w \__int_eval:w (#1#2#3#4#5 %)
13741   \fi:
13742   \fi:
13743   \fi:
13744   }
13745 \cs_new:Npn \_fp_sqrt_auxiv_o:NNNNNw 1#1#2#3#4#5#6;
13746   { \_fp_sqrt_auxviii_o:nnnnnnn {#1#2#3#4#5#6} {00000000} }
13747 \cs_new:Npn \_fp_sqrt_auxv_o:NNNNNw 1#1#2#3#4#5#6;
13748   { \_fp_sqrt_auxviii_o:nnnnnnn {000#1#2#3#4#5} {#60000} }
13749 \cs_new:Npn \_fp_sqrt_auxvi_o:NNNNNw 1#1#2#3#4#5#6;
13750   { \_fp_sqrt_auxviii_o:nnnnnnn {0000000#1} {#2#3#4#5#6} }
13751 \cs_new:Npn \_fp_sqrt_auxvii_o:NNNNNw 1#1#2#3#4#5#6;
13752   {
13753     \if_int_compare:w #1#2 = 0 \exp_stop_f:
13754     \exp_after:wN \_fp_sqrt_auxx_o:NNnnnnnn
13755   \fi:

```

```

13756     \_fp_sqrt_auxviii_o:nnnnnnnn {00000000} {000#1#2#3#4#5}
13757 }

```

(End definition for \\_fp\_sqrt\_auxiii\_o:wnnnnnnn and others.)

\\_fp\_sqrt\_auxviii\_o:nnnnnnnn Simply add the two 8-digit blocks of  $z$ , aligned to the last four of the five 4-digit blocks of  $y$ , then call the auxii auxiliary to evaluate  $y'^2 = (y + z)^2$ .

```

13758 \cs_new:Npn \_fp_sqrt_auxviii_o:nnnnnnnn #1#2 #3#4#5#6#7
13759 {
13760     \exp_after:wN \_fp_sqrt_auxix_o:wnwnw
13761     \__int_value:w \__int_eval:w #3
13762     \exp_after:wN \_fp_basics_pack_low:NNNNw
13763     \__int_value:w \__int_eval:w #1 + 1#4#5
13764     \exp_after:wN \_fp_basics_pack_low:NNNNw
13765     \__int_value:w \__int_eval:w #2 + 1#6#7 ;
13766 }
13767 \cs_new:Npn \_fp_sqrt_auxix_o:wnwnw #1; #2#3; #4#5;
13768 {
13769     \_fp_sqrt_auxii_o:NnnnnnnnN
13770     \_fp_sqrt_auxiii_o:wnnnnnnnnn {#1}{#2}{#3}{#4}{#5}
13771 }

```

(End definition for \\_fp\_sqrt\_auxviii\_o:nnnnnnnn and \\_fp\_sqrt\_auxix\_o:wnwnw.)

\\_fp\_sqrt\_auxx\_o:Nnnnnnnnn At this stage,  $j = 6$  and  $10^{24}z < 10^7$ , hence  
\\_fp\_sqrt\_auxxi\_o:wwnnN

$$10^7 + 1/2 > 10^{24}z + 1/2 \geq (10^{24}(a - y^2) - 258) \cdot (0.5 \cdot 10^8) / (10^8y + 1),$$

then  $10^{24}(a - y^2) - 258 < 2(10^7 + 1/2)(y + 10^{-8})$ , and

$$10^{24}(a - y^2) < (10^7 + 1290.5)(1 + 10^{-8}/y)(2y) < (10^7 + 1290.5)(1 + 10^{-7})(y + \sqrt{a}),$$

which finally implies  $0 \leq \sqrt{a} - y < 0.2 \cdot 10^{-16}$ . In particular,  $y$  is an underestimate of  $\sqrt{a}$  and  $y + 0.5 \cdot 10^{-16}$  is a (strict) overestimate. There is at exactly one multiple  $m$  of  $0.5 \cdot 10^{-16}$  in the interval  $[y, y + 0.5 \cdot 10^{-16})$ . If  $m^2 > a$ , then the square root is inexact and is obtained by rounding  $m - \epsilon$  to a multiple of  $10^{-16}$  (the precise shift  $0 < \epsilon < 0.5 \cdot 10^{-16}$  is irrelevant for rounding). If  $m^2 = a$  then the square root is exactly  $m$ , and there is no rounding. If  $m^2 < a$  then we round  $m + \epsilon$ . For now, discard a few irrelevant arguments #1, #2, #3, and find the multiple of  $0.5 \cdot 10^{-16}$  within  $[y, y + 0.5 \cdot 10^{-16})$ ; rather, only the last 4 digits #8 of  $y$  are considered, and we do not perform any carry yet. The auxxi auxiliary sets up auxii with a continuation function auxxii instead of auxiii as before. To prevent auxii from giving a negative results  $a - m^2$ , we compute  $a + 10^{-16} - m^2$  instead, always positive since  $m < \sqrt{a} + 0.5 \cdot 10^{-16}$  and  $a \leq 1 - 10^{-16}$ .

```

13772 \cs_new:Npn \_fp_sqrt_auxx_o:Nnnnnnnnn #1#2#3 #4#5#6#7#8
13773 {
13774     \exp_after:wN \_fp_sqrt_auxxi_o:wwnnN
13775     \__int_value:w \__int_eval:w
13776     (#8 + 2499) / 5000 * 5000 ;
13777     {#4} {#5} {#6} {#7} ;
13778 }
13779 \cs_new:Npn \_fp_sqrt_auxxi_o:wwnnN #1; #2; #3#4#5
13780 {
13781     \_fp_sqrt_auxii_o:NnnnnnnnN

```

```

13782     \__fp_sqrt_auxxii_o:nnnnnnnnnw
13783     #2 {#1}
13784     {#3} { #4 + 1 } #5
13785 }

```

(End definition for \\_\_fp\_sqrt\_auxx\_o:nnnnnnnn and \\_\_fp\_sqrt\_auxxi\_o:wnnnN.)

\\_\_fp\_sqrt\_auxxii\_o:nnnnnnnnnw  
\\_\_fp\_sqrt\_auxxiii\_o:w

The difference  $0 \leq a + 10^{-16} - m^2 \leq 10^{-16} + (\sqrt{a} - m)(\sqrt{a} + m) \leq 2 \cdot 10^{-16}$  was just computed: its first 8 digits vanish, as do the next four, #1, and most of the following four, #2. The guess  $m$  is an overestimate if  $a + 10^{-16} - m^2 < 10^{-16}$ , that is, #1#2 vanishes. Otherwise it is an underestimate, unless  $a + 10^{-16} - m^2 = 10^{-16}$  exactly. For an underestimate, call the auxxiv function with argument 9998. For an exact result call it with 9999, and for an overestimate call it with 10000.

```

13786 \cs_new:Npn \__fp_sqrt_auxxii_o:nnnnnnnnnw 0; #1#2#3#4#5#6#7#8 #9;
13787 {
13788   \if_int_compare:w #1#2 > 0 \exp_stop_f:
13789   \if_int_compare:w #1#2 = 1 \exp_stop_f:
13790   \if_int_compare:w #3#4 = 0 \exp_stop_f:
13791   \if_int_compare:w #5#6 = 0 \exp_stop_f:
13792   \if_int_compare:w #7#8 = 0 \exp_stop_f:
13793     \__fp_sqrt_auxxiii_o:w
13794     \fi:
13795     \fi:
13796     \fi:
13797     \fi:
13798     \exp_after:wN \__fp_sqrt_auxxiv_o:wnnnnnnnN
13799     \__int_value:w 9998
13800   \else:
13801     \exp_after:wN \__fp_sqrt_auxxiv_o:wnnnnnnnN
13802     \__int_value:w 10000
13803   \fi:
13804   ;
13805 }
13806 \cs_new:Npn \__fp_sqrt_auxxiii_o:w \fi: \fi: \fi: \fi: #1 \fi: ;
13807 {
13808   \fi: \fi: \fi: \fi: \fi:
13809   \__fp_sqrt_auxxiv_o:wnnnnnnnN 9999 ;
13810 }

```

(End definition for \\_\_fp\_sqrt\_auxxii\_o:nnnnnnnnnw and \\_\_fp\_sqrt\_auxxiii\_o:w.)

\\_\_fp\_sqrt\_auxxiv\_o:wnnnnnnnN

This receives 9998, 9999 or 10000 as #1 when  $m$  is an underestimate, exact, or an overestimate, respectively. Then comes  $m$  as five blocks of 4 digits, but where the last block #6 may be 0, 5000, or 10000. In the latter case, we need to add a carry, unless  $m$  is an overestimate (#1 is then 10000). Then comes  $a$  as three arguments. Rounding is done by \\_\_fp\_round:NNN, whose first argument is the final sign 0 (square roots are positive). We fake its second argument. It should be the last digit kept, but this is only used when ties are “rounded to even”, and only when the result is exactly half-way between two representable numbers rational square roots of numbers with 16 significant digits have: this situation never arises for the square root, as any exact square root of a 16 digit number has at most 8 significant digits. Finally, the last argument is the next digit, possibly shifted by 1 when there are further nonzero digits. This is achieved by \\_\_fp\_round\_digit:Nw, which receives (after removal of the 10000’s digit) one of 0000, 0001, 4999, 5000, 5001, or 9999, which it converts to 0, 1, 4, 5, 6, and 9, respectively.

```

13811 \cs_new:Npn \__fp_sqrt_auxxiv_o:wnnnnnnnN #1; #2#3#4#5#6 #7#8#9
13812 {
13813   \exp_after:wN \__fp_basics_pack_high:NNNNNw
13814   \__int_value:w \__int_eval:w 1 0000 0000 + #2#3
13815   \exp_after:wN \__fp_basics_pack_low:NNNNNw
13816   \__int_value:w \__int_eval:w 1 0000 0000
13817   + #4#5
13818   \if_int_compare:w #6 > #1 \exp_stop_f: + 1 \fi:
13819   + \exp_after:wN \__fp_round:NNN
13820   \exp_after:wN 0
13821   \exp_after:wN 0
13822   \__int_value:w
13823   \exp_after:wN \use_i:nn
13824   \exp_after:wN \__fp_round_digit:Nw
13825   \__int_value:w \__int_eval:w #6 + 19999 - #1 ;
13826   \exp_after:wN ;
13827 }

```

(End definition for \\_\_fp\_sqrt\_auxxiv\_o:wnnnnnnnN.)

## 26.5 About the sign

\\_\_fp\_sign\_o:w Find the sign of the floating point: nan, +0, -0, +1 or -1.

```

\__fp_sign_aux_o:w 13828 \cs_new:Npn \__fp_sign_o:w ? \s__fp \__fp_chk:w #1#2; @
13829 {
13830   \if_case:w #1 \exp_stop_f:
13831     \__fp_case_return_same_o:w
13832   \or: \exp_after:wN \__fp_sign_aux_o:w
13833   \or: \exp_after:wN \__fp_sign_aux_o:w
13834   \else: \__fp_case_return_same_o:w
13835   \fi:
13836   \s__fp \__fp_chk:w #1 #2;
13837 }
13838 \cs_new:Npn \__fp_sign_aux_o:w \s__fp \__fp_chk:w #1 #2 #3 ;
13839 { \exp_after:wN \__fp_set_sign_o:w \exp_after:wN #2 \c_one_fp @ }

```

(End definition for \\_\_fp\_sign\_o:w and \\_\_fp\_sign\_aux\_o:w.)

\\_\_fp\_set\_sign\_o:w This function is used for the unary minus and for abs. It leaves the sign of nan invariant, turns negative numbers (sign 2) to positive numbers (sign 0) and positive numbers (sign 0) to positive or negative numbers depending on #1. It also expands after itself in the input stream, just like \\_\_fp\_+\_o:ww.

```

13840 \cs_new:Npn \__fp_set_sign_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
13841 {
13842   \exp_after:wN \__fp_exp_after_o:w
13843   \exp_after:wN \s__fp
13844   \exp_after:wN \__fp_chk:w
13845   \exp_after:wN #2
13846   \__int_value:w
13847   \if_case:w #3 \exp_stop_f: #1 \or: 1 \or: 0 \fi: \exp_stop_f:
13848   #4;
13849 }

```

(End definition for \\_\_fp\_set\_sign\_o:w.)

```
13850 </initex | package>
```

## 27 l3fp-extended implementation

13851  $\langle *initex \mid package \rangle$

13852  $\langle @@=fp \rangle$

### 27.1 Description of fixed point numbers

This module provides a few functions to manipulate positive floating point numbers with extended precision (24 digits), but mostly provides functions for fixed-point numbers with this precision (24 digits). Those are used in the computation of Taylor series for the logarithm, exponential, and trigonometric functions. Since we eventually only care about the 16 first digits of the final result, some of the calculations are not performed with the full 24-digit precision. In other words, the last two blocks of each fixed point number may be wrong as long as the error is small enough to be rounded away when converting back to a floating point number. The fixed point numbers are expressed as

$$\{\langle a_1 \rangle\} \{\langle a_2 \rangle\} \{\langle a_3 \rangle\} \{\langle a_4 \rangle\} \{\langle a_5 \rangle\} \{\langle a_6 \rangle\} ;$$

where each  $\langle a_i \rangle$  is exactly 4 digits (ranging from 0000 to 9999), except  $\langle a_1 \rangle$ , which may be any “not-too-large” non-negative integer, with or without leading zeros. Here, “not-too-large” depends on the specific function (see the corresponding comments for details). Checking for overflow is the responsibility of the code calling those functions. The fixed point number  $a$  corresponding to the representation above is  $a = \sum_{i=1}^6 \langle a_i \rangle \cdot 10^{-4i}$ .

Most functions we define here have the form They perform the  $\langle calculation \rangle$  on the two  $\langle operands \rangle$ , then feed the result (6 brace groups followed by a semicolon) to the  $\langle continuation \rangle$ , responsible for the next step of the calculation. Some functions only accept an N-type  $\langle continuation \rangle$ . This allows constructions such as

```
\__fp_fixed_add:wnn  $\langle X_1 \rangle$  ;  $\langle X_2 \rangle$  ;
\__fp_fixed_mul:wnn  $\langle X_3 \rangle$  ;
\__fp_fixed_add:wnn  $\langle X_4 \rangle$  ;
```

to compute  $(X_1 + X_2) \cdot X_3 + X_4$ . This turns out to be very appropriate for computing continued fractions and Taylor series.

At the end of the calculation, the result is turned back to a floating point number using  $\backslash\_fp\_fixed\_to\_float\_o:wn$ . This function has to change the exponent of the floating point number: it must be used after starting an integer expression for the overall exponent of the result.

### 27.2 Helpers for numbers with extended precision

$\backslash c\_fp\_one\_fixed\_tl$  The fixed-point number 1, used in l3fp-expo.

```
13853 \tl_const:Nn \c__fp_one_fixed_tl
13854 { {10000} {0000} {0000} {0000} {0000} {0000} ; }
```

(End definition for  $\backslash c\_fp\_one\_fixed\_tl$ .)

$\backslash\_fp\_fixed\_continue:wn$  This function simply calls the next function.

```
13855 \cs_new:Npn \__fp_fixed_continue:wn #1; #2 { #2 #1; }
```

(End definition for  $\backslash\_fp\_fixed\_continue:wn$ .)

`\__fp_fixed_add_one:wn` This function adds 1 to the fixed point  $\langle a \rangle$ , by changing  $a_1$  to  $10000 + a_1$ , then calls the  $\langle continuation \rangle$ . This requires  $a_1 + 10000 < 2^{31}$ .

```

13856 \cs_new:Npn \__fp_fixed_add_one:wn #1#2; #3
13857 {
13858   \exp_after:wn #3 \exp_after:wn
13859   { \__int_value:w \__int_eval:w \c__fp_myriad_int + #1 } #2 ;
13860 }

```

(End definition for `\__fp_fixed_add_one:wn`.)

`\__fp_fixed_div_myriad:wn` Divide a fixed point number by 10000. This is a little bit more subtle than just removing the last group and adding a leading group of zeros: the first group #1 may have any number of digits, and we must split #1 into the new first group and a second group of exactly 4 digits. The choice of shifts allows #1 to be in the range  $[0, 5 \cdot 10^8 - 1]$ .

```

13861 \cs_new:Npn \__fp_fixed_div_myriad:wn #1#2#3#4#5#6;
13862 {
13863   \exp_after:wn \__fp_fixed_mul_after:wnn
13864   \__int_value:w \__int_eval:w \c__fp_leading_shift_int
13865   \exp_after:wn \__fp_pack:NNNNNw
13866   \__int_value:w \__int_eval:w \c__fp_trailing_shift_int
13867   + #1 ; {#2}{#3}{#4}{#5};
13868 }

```

(End definition for `\__fp_fixed_div_myriad:wn`.)

`\__fp_fixed_mul_after:wnn` The fixed point operations which involve multiplication end by calling this auxiliary. It braces the last block of digits, and places the  $\langle continuation \rangle$  #3 in front.

```

13869 \cs_new:Npn \__fp_fixed_mul_after:wnn #1; #2; #3 { #3 {#1} #2; }

```

(End definition for `\__fp_fixed_mul_after:wnn`.)

## 27.3 Multiplying a fixed point number by a short one

`\__fp_fixed_mul_short:wnn` Computes the product  $c = ab$  of  $a = \sum_i \langle a_i \rangle 10^{-4i}$  and  $b = \sum_i \langle b_i \rangle 10^{-4i}$ , rounds it to the closest multiple of  $10^{-24}$ , and leaves  $\langle continuation \rangle \{ \langle c_1 \rangle \} \dots \{ \langle c_6 \rangle \}$ ; in the input stream, where each of the  $\langle c_i \rangle$  are blocks of 4 digits, except  $\langle c_1 \rangle$ , which is any  $\text{\TeX}$  integer. Note that indices for  $\langle b \rangle$  start at 0: for instance a second operand of  $\{0001\}\{0000\}\{0000\}$  leaves the first operand unchanged (rather than dividing it by  $10^4$ , as `\__fp_fixed_mul:wnn` would).

```

13870 \cs_new:Npn \__fp_fixed_mul_short:wnn #1#2#3#4#5#6; #7#8#9;
13871 {
13872   \exp_after:wn \__fp_fixed_mul_after:wnn
13873   \__int_value:w \__int_eval:w \c__fp_leading_shift_int
13874   + #1*#7
13875   \exp_after:wn \__fp_pack:NNNNNw
13876   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
13877   + #1*#8 + #2*#7
13878   \exp_after:wn \__fp_pack:NNNNNw
13879   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
13880   + #1*#9 + #2*#8 + #3*#7
13881   \exp_after:wn \__fp_pack:NNNNNw
13882   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
13883   + #2*#9 + #3*#8 + #4*#7

```



```

13884      \exp_after:wN \__fp_pack:NNNNNw
13885      \__int_value:w \__int_eval:w \c__fp_middle_shift_int
13886      + #3*#9 + #4*#8 + #5*#7
13887      \exp_after:wN \__fp_pack:NNNNNw
13888      \__int_value:w \__int_eval:w \c__fp_trailing_shift_int
13889      + #4*#9 + #5*#8 + #6*#7
13890      + ( #5*#9 + #6*#8 + #6*#9 / \c__fp_myriad_int )
13891      / \c__fp_myriad_int ; ;
13892  }

```

(End definition for \\_\_fp\_fixed\_mul\_short:wnn.)

## 27.4 Dividing a fixed point number by a small integer

```

\__fp_fixed_div_int:wwN
\__fp_fixed_div_int:wnN
\__fp_fixed_div_int_auxi:wnn
  \__fp_fixed_div_int_auxii:wnn
\__fp_fixed_div_int_pack:Nw
\__fp_fixed_div_int_after:Nw

```

Divides the fixed point number  $\langle a \rangle$  by the (small) integer  $0 < \langle n \rangle < 10^4$  and feeds the result to the  $\langle continuation \rangle$ . There is no bound on  $a_1$ .

The arguments of the *i* auxiliary are 1: one of the  $a_i$ , 2:  $n$ , 3: the *ii* or the *iii* auxiliary. It computes a (somewhat tight) lower bound  $Q_i$  for the ratio  $a_i/n$ .

The *ii* auxiliary receives  $Q_i$ ,  $n$ , and  $a_i$  as arguments. It adds  $Q_i$  to a surrounding integer expression, and starts a new one with the initial value 9999, which ensures that the result of this expression has 5 digits. The auxiliary also computes  $a_i - n \cdot Q_i$ , placing the result in front of the 4 digits of  $a_{i+1}$ . The resulting  $a'_{i+1} = 10^4(a_i - n \cdot Q_i) + a_{i+1}$  serves as the first argument for a new call to the *i* auxiliary.

When the *iii* auxiliary is called, the situation looks like this:

```

\__fp_fixed_div_int_after:Nw \langle continuation \rangle
-1 + Q_1
\__fp_fixed_div_int_pack:Nw 9999 + Q_2
\__fp_fixed_div_int_pack:Nw 9999 + Q_3
\__fp_fixed_div_int_pack:Nw 9999 + Q_4
\__fp_fixed_div_int_pack:Nw 9999 + Q_5
\__fp_fixed_div_int_pack:Nw 9999
\__fp_fixed_div_int_auxii:wnn Q_6 ; {\langle n \rangle} {\langle a_6 \rangle}

```

where expansion is happening from the last line up. The *iii* auxiliary adds  $Q_6 + 2 \simeq a_6/n + 1$  to the last 9999, giving the integer closest to  $10000 + a_6/n$ .

Each *pack* auxiliary receives 5 digits followed by a semicolon. The first digit is added as a carry to the integer expression above, and the 4 other digits are braced. Each call to the *pack* auxiliary thus produces one brace group. The last brace group is produced by the *after* auxiliary, which places the  $\langle continuation \rangle$  as appropriate.

```

13893 \cs_new:Npn \__fp_fixed_div_int:wwN #1#2#3#4#5#6 ; #7 ; #8
13894 {
13895   \exp_after:wN \__fp_fixed_div_int_after:Nw
13896   \exp_after:wN #8
13897   \__int_value:w \__int_eval:w - 1
13898   \__fp_fixed_div_int:wnN
13899   #1; {\#7} \__fp_fixed_div_int_auxi:wnn
13900   #2; {\#7} \__fp_fixed_div_int_auxi:wnn
13901   #3; {\#7} \__fp_fixed_div_int_auxi:wnn
13902   #4; {\#7} \__fp_fixed_div_int_auxi:wnn
13903   #5; {\#7} \__fp_fixed_div_int_auxi:wnn
13904   #6; {\#7} \__fp_fixed_div_int_auxii:wnn ;
13905 }

```

```

13906 \cs_new:Npn \__fp_fixed_div_int:wnN #1; #2 #3
13907 {
13908   \exp_after:wN #3
13909   \__int_value:w \__int_eval:w #1 / #2 - 1 ;
13910   {#2}
13911   {#1}
13912 }
13913 \cs_new:Npn \__fp_fixed_div_int_auxi:wN #1; #2 #3
13914 {
13915   + #1
13916   \exp_after:wN \__fp_fixed_div_int_pack:Nw
13917   \__int_value:w \__int_eval:w 9999
13918   \exp_after:wN \__fp_fixed_div_int:wnN
13919   \__int_value:w \__int_eval:w #3 - #1*#2 \__int_eval_end:
13920 }
13921 \cs_new:Npn \__fp_fixed_div_int_auxii:wN #1; #2 #3 { + #1 + 2 ; }
13922 \cs_new:Npn \__fp_fixed_div_int_pack:Nw #1 #2; { + #1; {#2} }
13923 \cs_new:Npn \__fp_fixed_div_int_after:Nw #1 #2; { #1 {#2} }

```

(End definition for `\__fp_fixed_div_int:wnN` and others.)

## 27.5 Adding and subtracting fixed points

```

\__fp_fixed_add:wN
\__fp_fixed_sub:wN
\__fp_fixed_add:Nnnnnwn
\__fp_fixed_add:nnNnnwn
\__fp_fixed_add_pack:NNNNNwn
\__fp_fixed_add_after:NNNNNwn

```

Computes  $a + b$  (resp.  $a - b$ ) and feeds the result to the  $\langle continuation \rangle$ . This function requires  $0 \leq a_1, b_1 \leq 114748$ , its result must be positive (this happens automatically for addition) and its first group must have at most 5 digits:  $(a \pm b)_1 < 100000$ . The two functions only differ by a sign, hence use a common auxiliary. It would be nice to grab the 12 brace groups in one go; only 9 parameters are allowed. Start by grabbing the sign,  $a_1, \dots, a_4$ , the rest of  $a$ , and  $b_1$  and  $b_2$ . The second auxiliary receives the rest of  $a$ , the sign multiplying  $b$ , the rest of  $b$ , and the  $\langle continuation \rangle$  as arguments. After going down through the various level, we go back up, packing digits and bringing the  $\langle continuation \rangle$  (#8, then #7) from the end of the argument list to its start.

```

13924 \cs_new:Npn \__fp_fixed_add:wN { \__fp_fixed_add:Nnnnnwn + }
13925 \cs_new:Npn \__fp_fixed_sub:wN { \__fp_fixed_add:Nnnnnwn - }
13926 \cs_new:Npn \__fp_fixed_add:Nnnnnwn #1 #2#3#4#5 #6; #7#8
13927 {
13928   \exp_after:wN \__fp_fixed_add_after:NNNNNwn
13929   \__int_value:w \__int_eval:w 9 9999 9998 + #2#3 #1 #7#8
13930   \exp_after:wN \__fp_fixed_add_pack:NNNNNwn
13931   \__int_value:w \__int_eval:w 1 9999 9998 + #4#5
13932   \__fp_fixed_add:nnNnnwn #6 #1
13933 }
13934 \cs_new:Npn \__fp_fixed_add:nnNnnwn #1#2 #3 #4#5 #6#7 ; #8
13935 {
13936   #3 #4#5
13937   \exp_after:wN \__fp_fixed_add_pack:NNNNNwn
13938   \__int_value:w \__int_eval:w 2 0000 0000 #3 #6#7 + #1#2 ; {#8} ;
13939 }
13940 \cs_new:Npn \__fp_fixed_add_pack:NNNNNwn #1 #2#3#4#5 #6; #7
13941 { + #1 ; {#7} {#2#3#4#5} {#6} }
13942 \cs_new:Npn \__fp_fixed_add_after:NNNNNwn 1 #1 #2#3#4#5 #6; #7
13943 { #7 {#1#2#3#4#5} {#6} }

```

(End definition for `\__fp_fixed_add:wN` and others.)

## 27.6 Multiplying fixed points

`\__fp_fixed_mul:wnn` Computes  $a \times b$  and feeds the result to  $\langle continuation \rangle$ . This function requires  $0 \leq a_1, b_1 < 10000$ . Once more, we need to play around the limit of 9 arguments for  $\text{\TeX}$  macros. Note that we don't need to obtain an exact rounding, contrarily to the `*` operator, so things could be harder. We wish to perform carries in

$$\begin{aligned}
 a \times b = & a_1 \cdot b_1 \cdot 10^{-8} \\
 & + (a_1 \cdot b_2 + a_2 \cdot b_1) \cdot 10^{-12} \\
 & + (a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1) \cdot 10^{-16} \\
 & + (a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1) \cdot 10^{-20} \\
 & + \left( a_2 \cdot b_4 + a_3 \cdot b_3 + a_4 \cdot b_2 \right. \\
 & \quad \left. + \frac{a_3 \cdot b_4 + a_4 \cdot b_3 + a_1 \cdot b_6 + a_2 \cdot b_5 + a_5 \cdot b_2 + a_6 \cdot b_1}{10^4} \right. \\
 & \quad \left. + a_1 \cdot b_5 + a_5 \cdot b_1 \right) \cdot 10^{-24} + O(10^{-24}),
 \end{aligned}$$

where the  $O(10^{-24})$  stands for terms which are at most  $5 \cdot 10^{-24}$ ; ignoring those leads to an error of at most 5 ulp. Note how the first 15 terms only depend on  $a_1, \dots, a_4$  and  $b_1, \dots, b_4$ , while the last 6 terms only depend on  $a_1, a_2, a_5, a_6$ , and the corresponding parts of  $b$ . Hence, the first function grabs  $a_1, \dots, a_4$ , the rest of  $a$ , and  $b_1, \dots, b_4$ , and writes the 15 first terms of the expression, including a left parenthesis for the fraction. The `i` auxiliary receives  $a_5, a_6, b_1, b_2, a_1, a_2, b_5, b_6$  and finally the  $\langle continuation \rangle$  as arguments. It writes the end of the expression, including the right parenthesis and the denominator of the fraction. The  $\langle continuation \rangle$  is finally placed in front of the 6 brace groups by `\__fp_fixed_mul_after:wnn`.

```

13944 \cs_new:Npn \__fp_fixed_mul:wnn #1#2#3#4 #5; #6#7#8#9
13945 {
13946   \exp_after:wN \__fp_fixed_mul_after:wnn
13947   \__int_value:w \__int_eval:w \c__fp_leading_shift_int
13948   \exp_after:wN \__fp_pack:NNNNNw
13949   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
13950   + #1*#6
13951   \exp_after:wN \__fp_pack:NNNNNw
13952   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
13953   + #1*#7 + #2*#6
13954   \exp_after:wN \__fp_pack:NNNNNw
13955   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
13956   + #1*#8 + #2*#7 + #3*#6
13957   \exp_after:wN \__fp_pack:NNNNNw
13958   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
13959   + #1*#9 + #2*#8 + #3*#7 + #4*#6
13960   \exp_after:wN \__fp_pack:NNNNNw
13961   \__int_value:w \__int_eval:w \c__fp_trailing_shift_int
13962   + #2*#9 + #3*#8 + #4*#7
13963   + ( #3*#9 + #4*#8
13964     + \__fp_fixed_mul:nnnnnnnw #5 {#6}{#7} {#1}{#2}
13965   )
13966 \cs_new:Npn \__fp_fixed_mul:nnnnnnnw #1#2 #3#4 #5#6 #7#8 ;
13967 {
13968   #1*#4 + #2*#3 + #5*#8 + #6*#7 ) / \c__fp_myriad_int

```

```

13969     + #1*#3 + #5*#7 ; ;
13970 }

```

(End definition for `\_fp\_fixed\_mul:wnn` and `\_fp\_fixed\_mul:nnnnnnnw`.)

## 27.7 Combining product and sum of fixed points

`\_fp\_fixed\_mul\_add:wnn` Compute  $a \times b + c$ ,  $c - a \times b$ , and  $1 - a \times b$  and feed the result to the *(continuation)*.  
`\_fp\_fixed\_mul\_sub\_back:wnn` Those functions require  $0 \leq a_1, b_1, c_1 \leq 10000$ . Since those functions are at the heart of  
`\_fp\_fixed\_mul\_one\_minus\_mul:wnn` the computation of Taylor expansions, we over-optimize them a bit, and in particular we do not factor out the common parts of the three functions.

For definiteness, consider the task of computing  $a \times b + c$ . We perform carries in

$$\begin{aligned}
 a \times b + c = & (a_1 \cdot b_1 + c_1 c_2) \cdot 10^{-8} \\
 & + (a_1 \cdot b_2 + a_2 \cdot b_1) \cdot 10^{-12} \\
 & + (a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1 + c_3 c_4) \cdot 10^{-16} \\
 & + (a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1) \cdot 10^{-20} \\
 & + \left( a_2 \cdot b_4 + a_3 \cdot b_3 + a_4 \cdot b_2 \right. \\
 & \quad \left. + \frac{a_3 \cdot b_4 + a_4 \cdot b_3 + a_1 \cdot b_6 + a_2 \cdot b_5 + a_5 \cdot b_2 + a_6 \cdot b_1}{10^4} \right. \\
 & \quad \left. + a_1 \cdot b_5 + a_5 \cdot b_1 + c_5 c_6 \right) \cdot 10^{-24} + O(10^{-24}),
 \end{aligned}$$

where  $c_1 c_2$ ,  $c_3 c_4$ ,  $c_5 c_6$  denote the 8-digit number obtained by juxtaposing the two blocks of digits of  $c$ , and  $\cdot$  denotes multiplication. The task is obviously tough because we have 18 brace groups in front of us.

Each of the three function starts the first two levels (the first, corresponding to  $10^{-4}$ , is empty), with  $c_1 c_2$  in the first level, calls the `i` auxiliary with arguments described later, and adds a trailing `+ c_5 c_6 ; { (continuation) } ;`. The `+ c_5 c_6` piece, which is omitted for `\_fp\_fixed\_one\_minus\_mul:wnn`, is taken in the integer expression for the  $10^{-24}$  level.

```

13971 \cs_new:Npn \_fp\_fixed\_mul\_add:wnn #1; #2; #3#4#5#6#7#8;
13972 {
13973   \exp\_after:wN \_fp\_fixed\_mul\_after:wnn
13974   \_int\_value:w \_int\_eval:w \c\_fp\_big\_leading\_shift\_int
13975   \exp\_after:wN \_fp\_pack\_big:NNNNNNw
13976   \_int\_value:w \_int\_eval:w \c\_fp\_big\_middle\_shift\_int + #3 #4
13977   \_fp\_fixed\_mul\_add:Nwnnnwnnn +
13978   + #5 #6 ; #2 ; #1 ; #2 ; +
13979   + #7 #8 ; ;
13980 }
13981 \cs_new:Npn \_fp\_fixed\_mul\_sub\_back:wnn #1; #2; #3#4#5#6#7#8;
13982 {
13983   \exp\_after:wN \_fp\_fixed\_mul\_after:wnn
13984   \_int\_value:w \_int\_eval:w \c\_fp\_big\_leading\_shift\_int
13985   \exp\_after:wN \_fp\_pack\_big:NNNNNNw
13986   \_int\_value:w \_int\_eval:w \c\_fp\_big\_middle\_shift\_int + #3 #4
13987   \_fp\_fixed\_mul\_add:Nwnnnwnnn -
13988   + #5 #6 ; #2 ; #1 ; #2 ; -
13989   + #7 #8 ; ;
13990 }
13991 \cs_new:Npn \_fp\_fixed\_one\_minus\_mul:wnn #1; #2;

```

```

13992 {
13993   \exp_after:wN \_fp_fixed_mul_after:wwn
13994   \_int_value:w \_int_eval:w \c\_fp_big_leading_shift_int
13995   \exp_after:wN \_fp_pack_big:NNNNNNw
13996   \_int_value:w \_int_eval:w \c\_fp_big_middle_shift_int + 1 0000 0000
13997   \_fp_fixed_mul_add:Nwnnnwnnn -
13998   ; #2 ; #1 ; #2 ; -
13999   ; ;
14000 }

```

(End definition for \\_fp\_fixed\_mul\_add:wwn, \\_fp\_fixed\_mul\_sub\_back:wwn, and \\_fp\_fixed\_mul\_one\_minus\_mul:wn.)

\\_fp\_fixed\_mul\_add:Nwnnnwnnn

Here,  $\langle op \rangle$  is either + or -. Arguments #3, #4, #5 are  $\langle b_1 \rangle$ ,  $\langle b_2 \rangle$ ,  $\langle b_3 \rangle$ ; arguments #7, #8, #9 are  $\langle a_1 \rangle$ ,  $\langle a_2 \rangle$ ,  $\langle a_3 \rangle$ . We can build three levels:  $a_1 \cdot b_1$  for  $10^{-8}$ ,  $(a_1 \cdot b_2 + a_2 \cdot b_1)$  for  $10^{-12}$ , and  $(a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1 + c_3 c_4)$  for  $10^{-16}$ . The  $a$ - $b$  products use the sign #1. Note that #2 is empty for \\_fp\_fixed\_one\_minus\_mul:wn. We call the *ii* auxiliary for levels  $10^{-20}$  and  $10^{-24}$ , keeping the pieces of  $\langle a \rangle$  we've read, but not  $\langle b \rangle$ , since there is another copy later in the input stream.

```

14001 \cs_new:Npn \_fp_fixed_mul_add:Nwnnnwnnn #1 #2; #3#4#5#6; #7#8#9
14002 {
14003   #1 #7*#3
14004   \exp_after:wN \_fp_pack_big:NNNNNNw
14005   \_int_value:w \_int_eval:w \c\_fp_big_middle_shift_int
14006   #1 #7*#4 #1 #8*#3
14007   \exp_after:wN \_fp_pack_big:NNNNNNw
14008   \_int_value:w \_int_eval:w \c\_fp_big_middle_shift_int
14009   #1 #7*#5 #1 #8*#4 #1 #9*#3 #2
14010   \exp_after:wN \_fp_pack_big:NNNNNNw
14011   \_int_value:w \_int_eval:w \c\_fp_big_middle_shift_int
14012   #1 \_fp_fixed_mul_add:nnnnwnnn {#7}{#8}{#9}
14013 }

```

(End definition for \\_fp\_fixed\_mul\_add:Nwnnnwnnn.)

\\_fp\_fixed\_mul\_add:nnnnwnnn

Level  $10^{-20}$  is  $(a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1)$ , multiplied by the sign, which was inserted by the *i* auxiliary. Then we prepare level  $10^{-24}$ . We don't have access to all parts of  $\langle a \rangle$  and  $\langle b \rangle$  needed to make all products. Instead, we prepare the partial expressions

$$b_1 + a_4 \cdot b_2 + a_3 \cdot b_3 + a_2 \cdot b_4 + a_1$$

$$b_2 + a_4 \cdot b_3 + a_3 \cdot b_4 + a_2.$$

Obviously, those expressions make no mathematical sense: we complete them with  $a_5 \cdot$  and  $\cdot b_5$ , and with  $a_6 \cdot b_1 + a_5 \cdot$  and  $\cdot b_5 + a_1 \cdot b_6$ , and of course with the trailing  $+ c_5 c_6$ . To do all this, we keep  $a_1$ ,  $a_5$ ,  $a_6$ , and the corresponding pieces of  $\langle b \rangle$ .

```

14014 \cs_new:Npn \_fp_fixed_mul_add:nnnnwnnn #1#2#3#4#5; #6#7#8#9
14015 {
14016   ( #1*#9 + #2*#8 + #3*#7 + #4*#6 )
14017   \exp_after:wN \_fp_pack_big:NNNNNNw
14018   \_int_value:w \_int_eval:w \c\_fp_big_trailing_shift_int
14019   \_fp_fixed_mul_add:nnnnwnnn
14020   { #6 + #4*#7 + #3*#8 + #2*#9 + #1 }
14021   { #7 + #4*#8 + #3*#9 + #2 }
14022   {#1} #5;

```

```

14023     {#6}
14024 }

```

(End definition for `\_fp_fixed_mul_add:nnnnwnnnn`.)

`\_fp_fixed_mul_add:nnnnwnnnN` Complete the  $\langle partial_1 \rangle$  and  $\langle partial_2 \rangle$  expressions as explained for the `ii` auxiliary. The second one is divided by 10000: this is the carry from level  $10^{-28}$ . The trailing  $+c_5c_6$  is taken into the expression for level  $10^{-24}$ . Note that the total of level  $10^{-24}$  is in the interval  $[-5 \cdot 10^8, 6 \cdot 10^8]$  (give or take a couple of 10000), hence adding it to the shift gives a 10-digit number, as expected by the packing auxiliaries. See `l3fp-aux` for the definition of the shifts and packing auxiliaries.

```

14025 \cs_new:Npn \_fp_fixed_mul_add:nnnnwnnnN #1#2 #3#4#5; #6#7#8; #9
14026 {
14027     #9 (#4* #1 *#7)
14028     #9 (#5*#6+#4* #2 *#7+#3*#8) / \c__fp_myriad_int
14029 }

```

(End definition for `\_fp_fixed_mul_add:nnnnwnnnN`.)

## 27.8 Extended-precision floating point numbers

In this section we manipulate floating point numbers with roughly 24 significant figures (“extended-precision” numbers, in short, “ep”), which take the form of an integer exponent, followed by a comma, then six groups of digits, ending with a semicolon. The first group of digit may be any non-negative integer, while other groups of digits have 4 digits. In other words, an extended-precision number is an exponent ending in a comma, then a fixed point number. The corresponding value is  $0.\langle digits \rangle \cdot 10^{\langle exponent \rangle}$ . This convention differs from floating points.

`\_fp_ep_to_fixed:wnn` Converts an extended-precision number with an exponent at most 4 and a first block less than  $10^8$  to a fixed point number whose first block has 12 digits, hopefully starting with many zeros.

```

14030 \cs_new:Npn \_fp_ep_to_fixed:wnn #1,#2
14031 {
14032     \exp_after:wN \_fp_ep_to_fixed_auxi:www
14033     \__int_value:w \__int_eval:w 1 0000 0000 + #2 \exp_after:wN ;
14034     \exp:w \exp_end_continue_f:w
14035     \prg_replicate:nn { 4 - \int_max:nn {#1} { -32 } } { 0 } ;
14036 }
14037 \cs_new:Npn \_fp_ep_to_fixed_auxi:www 1#1; #2; #3#4#5#6#7;
14038 {
14039     \_fp_pack_eight:wNNNNNNNN
14040     \_fp_pack_twice_four:wNNNNNNNN
14041     \_fp_pack_twice_four:wNNNNNNNN
14042     \_fp_pack_twice_four:wNNNNNNNN
14043     \_fp_ep_to_fixed_auxii:nnnnnnwn ;
14044     #2 #1#3#4#5#6#7 0000 !
14045 }
14046 \cs_new:Npn \_fp_ep_to_fixed_auxii:nnnnnnwn #1#2#3#4#5#6#7; #8! #9
14047 { #9 {#1#2}{#3}{#4}{#5}{#6}{#7}; }

```

(End definition for `\_fp_ep_to_fixed:wnn`, `\_fp_ep_to_fixed_auxi:www`, and `\_fp_ep_to_fixed_auxii:nnnnnnwn`.)

```

\__fp_ep_to_ep:wwN
\__fp_ep_to_ep_loop:N
\__fp_ep_to_ep_end:www
\__fp_ep_to_ep_zero:ww

```

Normalize an extended-precision number. More precisely, leading zeros are removed from the mantissa of the argument, decreasing its exponent as appropriate. Then the digits are packed into 6 groups of 4 (discarding any remaining digit, not rounding). Finally, the continuation #8 is placed before the resulting exponent-mantissa pair. The input exponent may in fact be given as an integer expression. The `loop` auxiliary grabs a digit: if it is 0, decrement the exponent and continue looping, and otherwise call the `end` auxiliary, which places all digits in the right order (the digit that was not 0, and any remaining digits), followed by some 0, then packs them up neatly in  $3 \times 2 = 6$  blocks of four. At the end of the day, remove with `\__fp_use_i:ww` any digit that did not make it in the final mantissa (typically only zeros, unless the original first block has more than 4 digits).

```

14048 \cs_new:Npn \__fp_ep_to_ep:wwN #1,#2#3#4#5#6#7; #8
14049 {
14050   \exp_after:wN #8
14051   \__int_value:w \__int_eval:w #1 + 4
14052   \exp_after:wN \use_i:nn
14053   \exp_after:wN \__fp_ep_to_ep_loop:N
14054   \__int_value:w \__int_eval:w 1 0000 0000 + #2 \__int_eval_end:
14055   #3#4#5#6#7 ; ; !
14056 }
14057 \cs_new:Npn \__fp_ep_to_ep_loop:N #1
14058 {
14059   \if_meaning:w 0 #1
14060   - 1
14061   \else:
14062     \__fp_ep_to_ep_end:www #1
14063   \fi:
14064   \__fp_ep_to_ep_loop:N
14065 }
14066 \cs_new:Npn \__fp_ep_to_ep_end:www
14067 #1 \fi: \__fp_ep_to_ep_loop:N #2; #3!
14068 {
14069   \fi:
14070   \if_meaning:w ; #1
14071   - 2 * \c__fp_max_exponent_int
14072   \__fp_ep_to_ep_zero:ww
14073   \fi:
14074   \__fp_pack_twice_four:wNNNNNNNN
14075   \__fp_pack_twice_four:wNNNNNNNN
14076   \__fp_pack_twice_four:wNNNNNNNN
14077   \__fp_use_i:ww , ;
14078   #1 #2 0000 0000 0000 0000 0000 0000 ;
14079 }
14080 \cs_new:Npn \__fp_ep_to_ep_zero:ww \fi: #1; #2; #3;
14081 { \fi: , {1000}{0000}{0000}{0000}{0000}{0000} ; }

```

(End definition for `\__fp_ep_to_ep:wwN` and others.)

```

\__fp_ep_compare:www
\__fp_ep_compare_aux:www

```

In `l3fp-trig` we need to compare two extended-precision numbers. This is based on the same function for positive floating point numbers, with an extra test if comparing only 16 decimals is not enough to distinguish the numbers. Note that this function only works if the numbers are normalized so that their first block is in `[1000,9999]`.

```

14082 \cs_new:Npn \__fp_ep_compare:www #1,#2#3#4#5#6#7;

```

```

14083 { \_fp_ep_compare_aux:www {#1}{#2}{#3}{#4}{#5}; #6#7; }
14084 \cs_new:Npn \_fp_ep_compare_aux:www #1;#2;#3,#4#5#6#7#8#9;
14085 {
14086   \if_case:w
14087     \_fp_compare_npos:nwnw #1; {#3}{#4}{#5}{#6}{#7}; \exp_stop_f:
14088     \if_int_compare:w #2 = #8#9 \exp_stop_f:
14089       0
14090     \else:
14091       \if_int_compare:w #2 < #8#9 - \fi: 1
14092     \fi:
14093   \or: 1
14094   \else: -1
14095   \fi:
14096 }

```

(End definition for \\_fp\_ep\_compare:www and \\_fp\_ep\_compare\_aux:www.)

\\_fp\_ep\_mul:wwwN      Multiply two extended-precision numbers: first normalize them to avoid losing too much precision, then multiply the mantissas #2 and #4 as fixed point numbers, and sum the exponents #1 and #3. The result's first block is in [100,9999].

\\_fp\_ep\_mul\_raw:wwwN

```

14097 \cs_new:Npn \_fp_ep_mul:wwwN #1,#2; #3,#4;
14098 {
14099   \_fp_ep_to_ep:wwN #3,#4;
14100   \_fp_fixed_continue:wn
14101   {
14102     \_fp_ep_to_ep:wwN #1,#2;
14103     \_fp_ep_mul_raw:wwwN
14104   }
14105   \_fp_fixed_continue:wn
14106 }
14107 \cs_new:Npn \_fp_ep_mul_raw:wwwN #1,#2; #3,#4; #5
14108 {
14109   \_fp_fixed_mul:wn #2; #4;
14110   { \exp_after:wN #5 \_int_value:w \_int_eval:w #1 + #3 , }
14111 }

```

(End definition for \\_fp\_ep\_mul:wwwN and \\_fp\_ep\_mul\_raw:wwwN.)

## 27.9 Dividing extended-precision numbers

Divisions of extended-precision numbers are difficult to perform with exact rounding: the technique used in `l3fp-basics` for 16-digit floating point numbers does not generalize easily to 24-digit numbers. Thankfully, there is no need for exact rounding.

Let us call  $\langle n \rangle$  the numerator and  $\langle d \rangle$  the denominator. After a simple normalization step, we can assume that  $\langle n \rangle \in [0.1, 1)$  and  $\langle d \rangle \in [0.1, 1)$ , and compute  $\langle n \rangle / (10 \langle d \rangle) \in (0.01, 1)$ . In terms of the 6 blocks of digits  $\langle n_1 \rangle \cdots \langle n_6 \rangle$  and the 6 blocks  $\langle d_1 \rangle \cdots \langle d_6 \rangle$ , the condition translates to  $\langle n_1 \rangle, \langle d_1 \rangle \in [1000, 9999]$ .



We first find an integer estimate  $a \simeq 10^8/\langle d \rangle$  by computing

$$\begin{aligned}\alpha &= \left\lfloor \frac{10^9}{\langle d_1 \rangle + 1} \right\rfloor \\ \beta &= \left\lfloor \frac{10^9}{\langle d_1 \rangle} \right\rfloor \\ a &= 10^3\alpha + (\beta - \alpha) \cdot \left( 10^3 - \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \right) - 1250,\end{aligned}$$

where  $\left\lfloor \frac{\cdot}{\cdot} \right\rfloor$  denotes  $\varepsilon$ -TEX's rounding division, which rounds ties away from zero. The idea is to interpolate between  $10^3\alpha$  and  $10^3\beta$  with a parameter  $\langle d_2 \rangle/10^4$ , so that when  $\langle d_2 \rangle = 0$  one gets  $a = 10^3\beta - 1250 \simeq 10^{12}/\langle d_1 \rangle \simeq 10^8/\langle d \rangle$ , while when  $\langle d_2 \rangle = 9999$  one gets  $a = 10^3\alpha - 1250 \simeq 10^{12}/(\langle d_1 \rangle + 1) \simeq 10^8/\langle d \rangle$ . The shift by 1250 helps to ensure that  $a$  is an underestimate of the correct value. We shall prove that

$$1 - 1.755 \cdot 10^{-5} < \frac{\langle d \rangle a}{10^8} < 1.$$

We can then compute the inverse of  $\langle d \rangle a / 10^8 = 1 - \epsilon$  using the relation  $1/(1 - \epsilon) \simeq (1 + \epsilon)(1 + \epsilon^2) + \epsilon^4$ , which is correct up to a relative error of  $\epsilon^5 < 1.6 \cdot 10^{-24}$ . This allows us to find the desired ratio as

$$\frac{\langle n \rangle}{\langle d \rangle} = \frac{\langle n \rangle a}{10^8} ((1 + \epsilon)(1 + \epsilon^2) + \epsilon^4).$$

Let us prove the upper bound first (multiplied by  $10^{15}$ ). Note that  $10^7\langle d \rangle < 10^3\langle d_1 \rangle + 10^{-1}(\langle d_2 \rangle + 1)$ , and that  $\varepsilon$ -TEX's division  $\left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor$  underestimates  $10^{-1}(\langle d_2 \rangle + 1)$  by 0.5 at most, as can be checked for each possible last digit of  $\langle d_2 \rangle$ . Then,

$$10^7\langle d \rangle a < \left( 10^3\langle d_1 \rangle + \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor + \frac{1}{2} \right) \left( \left( 10^3 - \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \right) \beta + \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \alpha - 1250 \right) \quad (1)$$

$$< \left( 10^3\langle d_1 \rangle + \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor + \frac{1}{2} \right) \quad (2)$$

$$\left( \left( 10^3 - \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \right) \left( \frac{10^9}{\langle d_1 \rangle} + \frac{1}{2} \right) + \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \left( \frac{10^9}{\langle d_1 \rangle + 1} + \frac{1}{2} \right) - 1250 \right) \quad (3)$$

$$< \left( 10^3\langle d_1 \rangle + \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor + \frac{1}{2} \right) \left( \frac{10^{12}}{\langle d_1 \rangle} - \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \frac{10^9}{\langle d_1 \rangle(\langle d_1 \rangle + 1)} - 750 \right) \quad (4)$$

We recognize a quadratic polynomial in  $[\langle d_2 \rangle/10]$  with a negative leading coefficient: this polynomial is bounded above, according to  $([\langle d_2 \rangle/10] + a)(b - c[\langle d_2 \rangle/10]) \leq (b + ca)^2/(4c)$ . Hence,

$$10^7\langle d \rangle a < \frac{10^{15}}{\langle d_1 \rangle(\langle d_1 \rangle + 1)} \left( \langle d_1 \rangle + \frac{1}{2} + \frac{1}{4}10^{-3} - \frac{3}{8} \cdot 10^{-9}\langle d_1 \rangle(\langle d_1 \rangle + 1) \right)^2$$

Since  $\langle d_1 \rangle$  takes integer values within  $[1000, 9999]$ , it is a simple programming exercise to check that the squared expression is always less than  $\langle d_1 \rangle(\langle d_1 \rangle + 1)$ , hence  $10^7\langle d \rangle a < 10^{15}$ . The upper bound is proven. We also find that  $\frac{3}{8}$  can be replaced by slightly smaller numbers, but nothing less than  $0.374563\dots$ , and going back through the derivation of

the upper bound, we find that 1250 is as small a shift as we can obtain without breaking the bound.

Now, the lower bound. The same computation as for the upper bound implies

$$10^7 \langle d \rangle a > \left( 10^3 \langle d_1 \rangle + \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil - \frac{1}{2} \right) \left( \frac{10^{12}}{\langle d_1 \rangle} - \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil \frac{10^9}{\langle d_1 \rangle (\langle d_1 \rangle + 1)} - 1750 \right)$$

This time, we want to find the minimum of this quadratic polynomial. Since the leading coefficient is still negative, the minimum is reached for one of the extreme values  $[y/10] = 0$  or  $[y/10] = 100$ , and we easily check the bound for those values.

We have proven that the algorithm gives us a precise enough answer. Incidentally, the upper bound that we derived tells us that  $a < 10^8 / \langle d \rangle \leq 10^9$ , hence we can compute  $a$  safely as a  $\text{T}_{\text{E}}\text{X}$  integer, and even add  $10^9$  to it to ease grabbing of all the digits. The lower bound implies  $10^8 - 1755 < a$ , which we do not care about.

`\__fp_ep_div:wwwn` Compute the ratio of two extended-precision numbers. The result is an extended-precision number whose first block lies in the range  $[100, 9999]$ , and is placed after the  $\langle continuation \rangle$  once we are done. First normalize the inputs so that both first block lie in  $[1000, 9999]$ , then call `\__fp_ep_div_esti:wwwn`  $\langle denominator \rangle$   $\langle numerator \rangle$ , responsible for estimating the inverse of the denominator.

```

14112 \cs_new:Npn \__fp_ep_div:wwwn #1,#2; #3,#4;
14113 {
14114   \__fp_ep_to_ep:wwN #1,#2;
14115   \__fp_fixed_continue:wn
14116   {
14117     \__fp_ep_to_ep:wwN #3,#4;
14118     \__fp_ep_div_esti:wwwn
14119   }
14120 }
```

(End definition for `\__fp_ep_div:wwwn`.)

`\__fp_ep_div_esti:wwwn` The `esti` function evaluates  $\alpha = 10^9 / (\langle d_1 \rangle + 1)$ , which is used twice in the expression for  $a$ , and combines the exponents `#1` and `#4` (with a shift by 1 because we later compute  $\langle n \rangle / (10 \langle d \rangle)$ ). Then the `estii` function evaluates  $10^9 + a$ , and puts the exponent `#2` after the continuation `#7`: from there on we can forget exponents and focus on the mantissa. The `estiii` function multiplies the denominator `#7` by  $10^{-8}a$  (obtained as  $a$  split into the single digit `#1` and two blocks of 4 digits, `#2#3#4#5` and `#6`). The result  $10^{-8}a \langle d \rangle = (1 - \epsilon)$ , and a partially packed  $10^{-9}a$  (as a block of four digits, and five individual digits, not packed by lack of available macro parameters here) are passed to `\__fp_ep_div_epsilon:wnNNNNn`, which computes  $10^{-9}a / (1 - \epsilon)$ , that is,  $1 / (10 \langle d \rangle)$  and we finally multiply this by the numerator `#8`.

```

14121 \cs_new:Npn \__fp_ep_div_esti:wwwn #1,#2#3; #4,
14122 {
14123   \exp_after:wN \__fp_ep_div_estii:wwnnwwn
14124   \__int_value:w \__int_eval:w 10 0000 0000 / ( #2 + 1 )
14125   \exp_after:wN ;
14126   \__int_value:w \__int_eval:w #4 - #1 + 1 ,
14127   {#2} #3;
14128 }
14129 \cs_new:Npn \__fp_ep_div_estii:wwnnwwn #1; #2,#3#4#5; #6; #7
14130 {
```

```

14131 \exp_after:wN \_fp_ep_div_estiii:NNNNNwwwn
14132 \_int_value:w \_int_eval:w 10 0000 0000 - 1750
14133 + #1 000 + (10 0000 0000 / #3 - #1) * (1000 - #4 / 10) ;
14134 {#3}{#4}#5; #6; { #7 #2, }
14135 }
14136 \cs_new:Npn \_fp_ep_div_estiii:NNNNNwwwn 1#1#2#3#4#5#6; #7;
14137 {
14138 \_fp_fixed_mul_short:wwn #7; {#1}{#2#3#4#5}{#6};
14139 \_fp_ep_div_epsilon:wnNNNNNn {#1#2#3#4}#5#6
14140 \_fp_fixed_mul:wwn
14141 }

```

(End definition for `\_fp_ep_div_esti:wwwwn`, `\_fp_ep_div_estii:wwnnwwn`, and `\_fp_ep_div_estiii:NNNNNwwwn`.)

```

\_fp_ep_div_epsilon:wnNNNNNn
\_fp_ep_div_epsilon_pack:NNNNNw
\_fp_ep_div_epsilonii:wwnnNNNNNn

```

The bounds shown above imply that the `epsi` function's first operand is  $(1 - \epsilon)$  with  $\epsilon \in [0, 1.755 \cdot 10^{-5}]$ . The `epsi` function computes  $\epsilon$  as  $1 - (1 - \epsilon)$ . Since  $\epsilon < 10^{-4}$ , its first block vanishes and there is no need to explicitly use `#1` (which is 9999). Then `epsiii` evaluates  $10^{-9}a/(1 - \epsilon)$  as  $(1 + \epsilon^2)(1 + \epsilon)(10^{-9}a\epsilon) + 10^{-9}a$ . Importantly, we compute  $10^{-9}a\epsilon$  before multiplying it with the rest, rather than multiplying by  $\epsilon$  and then  $10^{-9}a$ , as this second option loses more precision. Also, the combination of `short_mul` and `div_myriad` is both faster and more precise than a simple `mul`.

```

14142 \cs_new:Npn \_fp_ep_div_epsilon:wnNNNNNn 1#1#2#3#4#5#6;
14143 {
14144 \exp_after:wN \_fp_ep_div_epsilonii:wwnnNNNNNn
14145 \_int_value:w \_int_eval:w 1 9998 - #2
14146 \exp_after:wN \_fp_ep_div_epsilon_pack:NNNNNw
14147 \_int_value:w \_int_eval:w 1 9999 9998 - #3#4
14148 \exp_after:wN \_fp_ep_div_epsilon_pack:NNNNNw
14149 \_int_value:w \_int_eval:w 2 0000 0000 - #5#6 ; ;
14150 }
14151 \cs_new:Npn \_fp_ep_div_epsilon_pack:NNNNNw 1#1#2#3#4#5#6;
14152 { + #1 ; {#2#3#4#5} {#6} }
14153 \cs_new:Npn \_fp_ep_div_epsilonii:wwnnNNNNNn 1#1; #2; #3#4#5#6#7#8
14154 {
14155 \_fp_fixed_mul:wwn {0000}{#1}#2; {0000}{#1}#2;
14156 \_fp_fixed_add_one:wN
14157 \_fp_fixed_mul:wwn {10000} {#1} #2 ;
14158 {
14159 \_fp_fixed_mul_short:wwn {0000}{#1}#2; {#3}{#4#5#6#7}{#8000};
14160 \_fp_fixed_div_myriad:wn
14161 \_fp_fixed_mul:wwn
14162 }
14163 \_fp_fixed_add:wwn {#3}{#4#5#6#7}{#8000}{0000}{0000}{0000};
14164 }

```

(End definition for `\_fp_ep_div_epsilon:wnNNNNNn`, `\_fp_ep_div_epsilon_pack:NNNNNw`, and `\_fp_ep_div_epsilonii:wwnnNNNNNn`.)

## 27.10 Inverse square root of extended precision numbers

The idea here is similar to division. Normalize the input, multiplying by powers of 100 until we have  $x \in [0.01, 1)$ . Then find an integer approximation  $r \in [101, 1003]$  of  $10^2/\sqrt{x}$ , as the fixed point of iterations of the Newton method: essentially  $r \mapsto (r + 10^8/(x_1r))/2$ ,

starting from a guess that optimizes the number of steps before convergence. In fact, just as there is a slight shift when computing divisions to ensure that some inequalities hold, we replace  $10^8$  by a slightly larger number which ensures that  $r^2x \geq 10^4$ . This also causes  $r \in [101, 1003]$ . Another correction to the above is that the input is actually normalized to  $[0.1, 1)$ , and we use either  $10^8$  or  $10^9$  in the Newton method, depending on the parity of the exponent. Skipping those technical hurdles, once we have the approximation  $r$ , we set  $y = 10^{-4}r^2x$  (or rather, the correct power of 10 to get  $y \simeq 1$ ) and compute  $y^{-1/2}$  through another application of Newton's method. This time, the starting value is  $z = 1$ , each step maps  $z \mapsto z(1.5 - 0.5yz^2)$ , and we perform a fixed number of steps. Our final result combines  $r$  with  $y^{-1/2}$  as  $x^{-1/2} = 10^{-2}ry^{-1/2}$ .

`\__fp_ep_isqrt:wnn`

`\__fp_ep_isqrt_aux:wnn`

`\__fp_ep_isqrt_auxii:wwnnwn`

First normalize the input, then check the parity of the exponent #1. If it is even, the result's exponent will be  $-\#1/2$ , otherwise it will be  $(\#1 - 1)/2$  (except in the case where the input was an exact power of 100). The `auxii` function receives as #1 the result's exponent just computed, as #2 the starting value for the iteration giving  $r$  (the values 168 and 535 lead to the least number of iterations before convergence, on average), as #3 and #4 one empty argument and one 0, depending on the parity of the original exponent, as #5 and #6 the normalized mantissa ( $\#5 \in [1000, 9999]$ ), and as #7 the continuation. It sets up the iteration giving  $r$ : the `esti` function thus receives the initial two guesses #2 and 0, an approximation #5 of  $10^4x$  (its first block of digits), and the empty/zero arguments #3 and #4, followed by the mantissa and an altered continuation where we have stored the result's exponent.

```

14165 \cs_new:Npn \__fp_ep_isqrt:wnn #1,#2;
14166 {
14167   \__fp_ep_to_ep:wnn #1,#2;
14168   \__fp_ep_isqrt_auxi:wnn
14169 }
14170 \cs_new:Npn \__fp_ep_isqrt_auxi:wnn #1,
14171 {
14172   \exp_after:wN \__fp_ep_isqrt_auxii:wwnnwn
14173   \__int_value:w \__int_eval:w
14174   \int_if_odd:nTF {#1}
14175     { (1 - #1) / 2 , 535 , { 0 } { } }
14176     { 1 - #1 / 2 , 168 , { } { 0 } }
14177 }
14178 \cs_new:Npn \__fp_ep_isqrt_auxii:wwnnwn #1, #2, #3#4 #5#6; #7
14179 {
14180   \__fp_ep_isqrt_esti:wwnnwn #2, 0, #5, {#3} {#4}
14181   {#5} #6 ; { #7 #1 , }
14182 }

```

(End definition for `\__fp_ep_isqrt:wnn`, `\__fp_ep_isqrt_aux:wnn`, and `\__fp_ep_isqrt_auxii:wwnnwn`.)

`\__fp_ep_isqrt_esti:wwnnwn`

`\__fp_ep_isqrt_estii:wwnnwn`

`\__fp_ep_isqrt_estiii:NNNNNwnn`

If the last two approximations gave the same result, we are done: call the `estii` function to clean up. Otherwise, evaluate  $(\langle prev \rangle + 1.005 \cdot 10^8 \text{ or } 9 / (\langle prev \rangle \cdot x)) / 2$ , as the next approximation: omitting the 1.005 factor, this would be Newton's method. We can check by brute force that if #4 is empty (the original exponent was even), the process computes an integer slightly larger than  $100/\sqrt{x}$ , while if #4 is 0 (the original exponent was odd), the result is an integer slightly larger than  $100/\sqrt{x/10}$ . Once we are done, we evaluate  $100r^2/2$  or  $10r^2/2$  (when the exponent is even or odd, respectively) and feed that to `estiii`. This third auxiliary finds  $y_{\text{even}}/2 = 10^{-4}r^2x/2$  or  $y_{\text{odd}}/2 = 10^{-5}r^2x/2$  (again, depending on earlier parity). A simple program shows that  $y \in [1, 1.0201]$ . The

number  $y/2$  is fed to `\__fp_ep_isqrt_epsilon:wN`, which computes  $1/\sqrt{y}$ , and we finally multiply the result by  $r$ .

```

14183 \cs_new:Npn \__fp_ep_isqrt_esti:wwnnwn #1, #2, #3, #4
14184 {
14185   \if_int_compare:w #1 = #2 \exp_stop_f:
14186     \exp_after:wN \__fp_ep_isqrt_estii:wwnnwn
14187   \fi:
14188   \exp_after:wN \__fp_ep_isqrt_esti:wwnnwn
14189   \__int_value:w \__int_eval:w
14190     (#1 + 1 0050 0000 #4 / (#1 * #3)) / 2 ,
14191   #1, #3, {#4}
14192 }
14193 \cs_new:Npn \__fp_ep_isqrt_estii:wwnnwn #1, #2, #3, #4#5
14194 {
14195   \exp_after:wN \__fp_ep_isqrt_estiii:NNNNNwwnn
14196   \__int_value:w \__int_eval:w 1000 0000 + #2 * #2 #5 * 5
14197   \exp_after:wN , \__int_value:w \__int_eval:w 10000 + #2 ;
14198 }
14199 \cs_new:Npn \__fp_ep_isqrt_estiii:NNNNNwwnn 1#1#2#3#4#5#6, 1#7#8; #9;
14200 {
14201   \__fp_fixed_mul_short:wwn #9; {#1} {#2#3#4#5} {#600} ;
14202   \__fp_ep_isqrt_epsilon:wN
14203   \__fp_fixed_mul_short:wwn {#7} {#80} {0000} ;
14204 }

```

(End definition for `\__fp_ep_isqrt_esti:wwnnwn`, `\__fp_ep_isqrt_estii:wwnnwn`, and `\__fp_ep_isqrt_estiii:NNNNNwwnn`.)

`\__fp_ep_isqrt_epsilon:wN`  
`\__fp_ep_isqrt_epsilonii:wwN`

Here, we receive a fixed point number  $y/2$  with  $y \in [1, 1.0201]$ . Starting from  $z = 1$  we iterate  $z \mapsto z(3/2 - z^2 y/2)$ . In fact, we start from the first iteration  $z = 3/2 - y/2$  to avoid useless multiplications. The `epsii` auxiliary receives  $z$  as `#1` and  $y$  as `#2`.

```

14205 \cs_new:Npn \__fp_ep_isqrt_epsilon:wN #1;
14206 {
14207   \__fp_fixed_sub:wwn {15000}{0000}{0000}{0000}{0000}{0000}; #1;
14208   \__fp_ep_isqrt_epsilonii:wwN #1;
14209   \__fp_ep_isqrt_epsilonii:wwN #1;
14210   \__fp_ep_isqrt_epsilonii:wwN #1;
14211 }
14212 \cs_new:Npn \__fp_ep_isqrt_epsilonii:wwN #1; #2;
14213 {
14214   \__fp_fixed_mul:wwn #1; #1;
14215   \__fp_fixed_mul_sub_back:wwnn #2;
14216     {15000}{0000}{0000}{0000}{0000}{0000};
14217   \__fp_fixed_mul:wwn #1;
14218 }

```

(End definition for `\__fp_ep_isqrt_epsilon:wN` and `\__fp_ep_isqrt_epsilonii:wwN`.)

## 27.11 Converting from fixed point to floating point

After computing Taylor series, we wish to convert the result from extended precision (with or without an exponent) to the public floating point format. The functions here should be called within an integer expression for the overall exponent of the floating point.

`\_fp_ep_to_float_o:wwN` An extended-precision number is simply a comma-delimited exponent followed by a fixed  
`\_fp_ep_inv_to_float_o:wwN` point number. Leave the exponent in the current integer expression then convert the  
fixed point number.

```

14219 \cs_new:Npn \_fp_ep_to_float_o:wwN #1,
14220 { + \_int_eval:w #1 \_fp_fixed_to_float_o:wN }
14221 \cs_new:Npn \_fp_ep_inv_to_float_o:wwN #1,#2;
14222 {
14223   \_fp_ep_div:wwwN 1,{1000}{0000}{0000}{0000}{0000}{0000}; #1,#2;
14224   \_fp_ep_to_float_o:wwN
14225 }

```

(End definition for `\_fp_ep_to_float_o:wwN` and `\_fp_ep_inv_to_float_o:wwN`.)

`\_fp_fixed_inv_to_float_o:wN` Another function which reduces to converting an extended precision number to a float.

```

14226 \cs_new:Npn \_fp_fixed_inv_to_float_o:wN
14227 { \_fp_ep_inv_to_float_o:wwN 0, }

```

(End definition for `\_fp_fixed_inv_to_float_o:wN`.)

`\_fp_fixed_to_float_rad_o:wN` Converts the fixed point number #1 from degrees to radians then to a floating point  
number. This could perhaps remain in `l3fp-trig`.

```

14228 \cs_new:Npn \_fp_fixed_to_float_rad_o:wN #1;
14229 {
14230   \_fp_fixed_mul:wwN #1; {5729}{5779}{5130}{8232}{0876}{7981};
14231   { \_fp_ep_to_float_o:wwN 2, }
14232 }

```

(End definition for `\_fp_fixed_to_float_rad_o:wN`.)

`\_fp_fixed_to_float_o:wN` yields

`\_fp_fixed_to_float_o:Nw`  $\langle exponent \rangle ; \{ \langle a'_1 \rangle \} \{ \langle a'_2 \rangle \} \{ \langle a'_3 \rangle \} \{ \langle a'_4 \rangle \} ;$

And the `to_fixed` version gives six brace groups instead of 4, ensuring that  $1000 \leq \langle a'_1 \rangle \leq 9999$ . At this stage, we know that  $\langle a_1 \rangle$  is positive (otherwise, it is sign of an error before), and we assume that it is less than  $10^8$ .<sup>11</sup>

```

14233 \cs_new:Npn \_fp_fixed_to_float_o:Nw #1#2; { \_fp_fixed_to_float_o:wN #2; #1 }
14234 \cs_new:Npn \_fp_fixed_to_float_o:wN #1#2#3#4#5#6; #7
14235 {
14236   + \_int_eval:w \c__fp_block_int % for the 8-digit-at-the-start thing.
14237   \exp_after:wN \exp_after:wN
14238   \exp_after:wN \_fp_fixed_to_loop:N
14239   \exp_after:wN \use_none:n
14240   \_int_value:w \_int_eval:w
14241   1 0000 0000 + #1 \exp_after:wN \_fp_use_none_stop_f:n
14242   \_int_value:w 1#2 \exp_after:wN \_fp_use_none_stop_f:n
14243   \_int_value:w 1#3#4 \exp_after:wN \_fp_use_none_stop_f:n
14244   \_int_value:w 1#5#6
14245   \exp_after:wN ;
14246   \exp_after:wN ;
14247 }
14248 \cs_new:Npn \_fp_fixed_to_loop:N #1
14249 {

```

<sup>11</sup>Bruno: I must double check this assumption.

```

14250 \if_meaning:w 0 #1
14251 - 1
14252 \exp_after:wN \__fp_fixed_to_loop:N
14253 \else:
14254 \exp_after:wN \__fp_fixed_to_loop_end:w
14255 \exp_after:wN #1
14256 \fi:
14257 }
14258 \cs_new:Npn \__fp_fixed_to_loop_end:w #1 #2 ;
14259 {
14260 \if_meaning:w ; #1
14261 \exp_after:wN \__fp_fixed_to_float_zero:w
14262 \else:
14263 \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
14264 \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
14265 \exp_after:wN \__fp_fixed_to_float_pack:ww
14266 \exp_after:wN ;
14267 \fi:
14268 #1 #2 0000 0000 0000 0000 ;
14269 }
14270 \cs_new:Npn \__fp_fixed_to_float_zero:w ; 0000 0000 0000 0000 ;
14271 {
14272 - 2 * \c__fp_max_exponent_int ;
14273 {0000} {0000} {0000} {0000} ;
14274 }
14275 \cs_new:Npn \__fp_fixed_to_float_pack:ww #1 ; #2#3 ; ;
14276 {
14277 \if_int_compare:w #2 > 4 \exp_stop_f:
14278 \exp_after:wN \__fp_fixed_to_float_round_up:wnnnnw
14279 \fi:
14280 ; #1 ;
14281 }
14282 \cs_new:Npn \__fp_fixed_to_float_round_up:wnnnnw ; #1#2#3#4 ;
14283 {
14284 \exp_after:wN \__fp_basics_pack_high:NNNNw
14285 \__int_value:w \__int_eval:w 1 #1#2
14286 \exp_after:wN \__fp_basics_pack_low:NNNNw
14287 \__int_value:w \__int_eval:w 1 #3#4 + 1 ;
14288 }

```

(End definition for \\_\_fp\_fixed\_to\_float\_o:wN and \\_\_fp\_fixed\_to\_float\_o:Nw.)

```

14289 \</initex | package>

```

## 28 l3fp-expo implementation

```

14290 \*initex | package>

```

```

14291 \<@@=fp>

```

```

\__fp_parse_word_exp:N
\__fp_parse_word_ln:N

```

Unary functions.

```

14292 \cs_new:Npn \__fp_parse_word_exp:N
14293 { \__fp_parse_unary_function:NNN \__fp_exp_o:w ? }
14294 \cs_new:Npn \__fp_parse_word_ln:N
14295 { \__fp_parse_unary_function:NNN \__fp_ln_o:w ? }

```

(End definition for `\_fp_parse_word_exp:N` and `\_fp_parse_word_ln:N`.)

## 28.1 Logarithm

### 28.1.1 Work plan

As for many other functions, we filter out special cases in `\_fp_ln_o:w`. Then `\_fp_ln_npos_o:w` receives a positive normal number, which we write in the form  $a \cdot 10^b$  with  $a \in [0.1, 1)$ .

*The rest of this section is actually not in sync with the code. Or is the code not in sync with the section? In the current code,  $c \in [1, 10]$  is such that  $0.7 \leq ac < 1.4$ .*

We are given a positive normal number, of the form  $a \cdot 10^b$  with  $a \in [0.1, 1)$ . To compute its logarithm, we find a small integer  $5 \leq c < 50$  such that  $0.91 \leq ac/5 < 1.1$ , and use the relation

$$\ln(a \cdot 10^b) = b \cdot \ln(10) - \ln(c/5) + \ln(ac/5).$$

The logarithms  $\ln(10)$  and  $\ln(c/5)$  are looked up in a table. The last term is computed using the following Taylor series of  $\ln$  near 1:

$$\ln\left(\frac{ac}{5}\right) = \ln\left(\frac{1+t}{1-t}\right) = 2t \left(1 + t^2 \left(\frac{1}{3} + t^2 \left(\frac{1}{5} + t^2 \left(\frac{1}{7} + t^2 \left(\frac{1}{9} + \dots\right)\right)\right)\right)\right)$$

where  $t = 1 - 10/(ac + 5)$ . We can now see one reason for the choice of  $ac \sim 5$ : then  $ac + 5 = 10(1 - \epsilon)$  with  $-0.05 < \epsilon \leq 0.045$ , hence

$$t = \frac{\epsilon}{1 - \epsilon} = \epsilon(1 + \epsilon)(1 + \epsilon^2)(1 + \epsilon^4) \dots,$$

is not too difficult to compute.

### 28.1.2 Some constants

A few values of the logarithm as extended fixed point numbers. Those are needed in the implementation. It turns out that we don't need the value of  $\ln(5)$ .

<code>\c__fp_ln_i_fixed_tl</code>	14296	<code>\tl_const:Nn \c__fp_ln_i_fixed_tl</code>	{ {0000}{0000}{0000}{0000}{0000}{0000};}
<code>\c__fp_ln_ii_fixed_tl</code>	14297	<code>\tl_const:Nn \c__fp_ln_ii_fixed_tl</code>	{ {6931}{4718}{0559}{9453}{0941}{7232};}
<code>\c__fp_ln_iii_fixed_tl</code>	14298	<code>\tl_const:Nn \c__fp_ln_iii_fixed_tl</code>	{ {10986}{1228}{8668}{1096}{9139}{5245};}
<code>\c__fp_ln_iv_fixed_tl</code>	14299	<code>\tl_const:Nn \c__fp_ln_iv_fixed_tl</code>	{ {13862}{9436}{1119}{8906}{1883}{4464};}
<code>\c__fp_ln_vii_fixed_tl</code>	14300	<code>\tl_const:Nn \c__fp_ln_vii_fixed_tl</code>	{ {17917}{5946}{9228}{0550}{0081}{2477};}
<code>\c__fp_ln_viii_fixed_tl</code>	14301	<code>\tl_const:Nn \c__fp_ln_viii_fixed_tl</code>	{ {19459}{1014}{9055}{3133}{0510}{5353};}
<code>\c__fp_ln_ix_fixed_tl</code>	14302	<code>\tl_const:Nn \c__fp_ln_ix_fixed_tl</code>	{ {20794}{4154}{1679}{8359}{2825}{1696};}
<code>\c__fp_ln_x_fixed_tl</code>	14303	<code>\tl_const:Nn \c__fp_ln_x_fixed_tl</code>	{ {21972}{2457}{7336}{2193}{8279}{0490};}
	14304	<code>\tl_const:Nn \c__fp_ln_x_fixed_tl</code>	{ {23025}{8509}{2994}{0456}{8401}{7991};}

(End definition for `\c__fp_ln_i_fixed_tl` and others.)

### 28.1.3 Sign, exponent, and special numbers

`\_fp_ln_o:w` The logarithm of negative numbers (including  $-\infty$  and  $-0$ ) raises the “invalid” exception. The logarithm of  $+0$  is  $-\infty$ , raising a division by zero exception. The logarithm of  $+\infty$  or a `nan` is itself. Positive normal numbers call `\_fp_ln_npos_o:w`.

```
14305 \cs_new:Npn \_fp_ln_o:w #1 \s__fp \_fp_chk:w #2#3#4; @
14306 {
```



```

14307 \if_meaning:w 2 #3
14308 \__fp_case_use:nw { \__fp_invalid_operation_o:nw { ln } }
14309 \fi:
14310 \if_case:w #2 \exp_stop_f:
14311 \__fp_case_use:nw
14312 { \__fp_division_by_zero_o:Nnw \c_minus_inf_fp { ln } }
14313 \or:
14314 \else:
14315 \__fp_case_return_same_o:w
14316 \fi:
14317 \__fp_ln_npos_o:w \s__fp \__fp_chk:w #2#3#4;
14318 }

```

(End definition for \\_\_fp\_ln\_o:w.)

#### 28.1.4 Absolute ln

\\_\_fp\_ln\_npos\_o:w We catch the case of a significand very close to 0.1 or to 1. In all other cases, the final result is at least  $10^{-4}$ , and then an error of  $0.5 \cdot 10^{-20}$  is acceptable.

```

14319 \cs_new:Npn \__fp_ln_npos_o:w \s__fp \__fp_chk:w 10#1#2#3;
14320 { %^^A todo: ln(1) should be "exact zero", not "underflow"
14321 \exp_after:wN \__fp_sanitize:Nw
14322 \__int_value:w % for the overall sign
14323 \if_int_compare:w #1 < 1 \exp_stop_f:
14324 2
14325 \else:
14326 0
14327 \fi:
14328 \exp_after:wN \exp_stop_f:
14329 \__int_value:w \__int_eval:w % for the exponent
14330 \__fp_ln_significand:NNNNnnnnN #2#3
14331 \__fp_ln_exponent:wn {#1}
14332 }

```

(End definition for \\_\_fp\_ln\_npos\_o:w.)

\\_\_fp\_ln\_significand:NNNNnnnnN  $\langle X_1 \rangle \{ \langle X_2 \rangle \} \{ \langle X_3 \rangle \} \{ \langle X_4 \rangle \} \langle continuation \rangle$   
This function expands to  
 $\langle continuation \rangle \{ \langle Y_1 \rangle \} \{ \langle Y_2 \rangle \} \{ \langle Y_3 \rangle \} \{ \langle Y_4 \rangle \} \{ \langle Y_5 \rangle \} \{ \langle Y_6 \rangle \} ;$

where  $Y = -\ln(X)$  as an extended fixed point.

```

14333 \cs_new:Npn \__fp_ln_significand:NNNNnnnnN #1#2#3#4
14334 {
14335 \exp_after:wN \__fp_ln_x_ii:wnnnn
14336 \__int_value:w
14337 \if_case:w #1 \exp_stop_f:
14338 \or:
14339 \if_int_compare:w #2 < 4 \exp_stop_f:
14340 \__int_eval:w 10 - #2
14341 \else:
14342 6
14343 \fi:
14344 \or: 4
14345 \or: 3

```

```

14346     \or: 2
14347     \or: 2
14348     \or: 2
14349     \else: 1
14350     \fi:
14351 ; { #1 #2 #3 #4 }
14352 }

```

(End definition for `\_fp_ln_significand:NNNNnnnN`.)

`\_fp_ln_x_ii:wnnnn` We have thus found  $c \in [1, 10]$  such that  $0.7 \leq ac < 1.4$  in all cases. Compute  $1 + x = 1 + ac \in [1.7, 2.4]$ .

```

14353 \cs_new:Npn \_fp_ln_x_ii:wnnnn #1; #2#3#4#5
14354 {
14355   \exp_after:wN \_fp_ln_div_after:Nw
14356   \cs:w c\_fp_ln\_int_to_roman:w #1\_fixed_tl \exp_after:wN \cs_end:
14357   \_int_value:w
14358   \exp_after:wN \_fp_ln_x_iv:wnnnnnnnnn
14359   \_int_value:w \_int_eval:w
14360   \exp_after:wN \_fp_ln_x_iii_var:NNNNNw
14361   \_int_value:w \_int_eval:w 9999 9990 + #1*#2#3 +
14362   \exp_after:wN \_fp_ln_x_iii:NNNNNw
14363   \_int_value:w \_int_eval:w 10 0000 0000 + #1*#4#5 ;
14364   {20000} {0000} {0000} {0000}
14365 } %^A todo: reoptimize (a generalization attempt failed).
14366 \cs_new:Npn \_fp_ln_x_iii:NNNNNw #1#2 #3#4#5#6 #7;
14367 { #1#2; {#3#4#5#6} {#7} }
14368 \cs_new:Npn \_fp_ln_x_iii_var:NNNNNw #1 #2#3#4#5 #6;
14369 {
14370   #1#2#3#4#5 + 1 ;
14371   {#1#2#3#4#5} {#6}
14372 }

```

The Taylor series to be used is expressed in terms of  $t = (x - 1)/(x + 1) = 1 - 2/(x + 1)$ . We now compute the quotient with extended precision, reusing some code from `\_fp_/o:ww`. Note that  $1 + x$  is known exactly.

To reuse notations from `l3fp-basics`, we want to compute  $A/Z$  with  $A = 2$  and  $Z = x + 1$ . In `l3fp-basics`, we considered the case where both  $A$  and  $Z$  are arbitrary, in the range  $[0.1, 1)$ , and we had to monitor the growth of the sequence of remainders  $A$ ,  $B$ ,  $C$ , etc. to ensure that no overflow occurred during the computation of the next quotient. The main source of risk was our choice to define the quotient as roughly  $10^9 \cdot A/10^5 \cdot Z$ : then  $A$  was bound to be below  $2.147 \cdots$ , and this limit was never far.

In our case, we can simply work with  $10^8 \cdot A$  and  $10^4 \cdot Z$ , because our reason to work with higher powers has gone: we needed the integer  $y \simeq 10^5 \cdot Z$  to be at least  $10^4$ , and now, the definition  $y \simeq 10^4 \cdot Z$  suffices.

Let us thus define  $y = \lfloor 10^4 \cdot Z \rfloor + 1 \in (1.7 \cdot 10^4, 2.4 \cdot 10^4]$ , and

$$Q_1 = \left\lfloor \frac{\lfloor 10^8 \cdot A \rfloor}{y} - \frac{1}{2} \right\rfloor.$$

(The  $1/2$  comes from how `eTeX` rounds.) As for division, it is easy to see that  $Q_1 \leq 10^4 A/Z$ , i.e.,  $Q_1$  is an underestimate.

Exactly as we did for division, we set  $B = 10^4 A - Q_1 Z$ . Then

$$\begin{aligned} 10^4 B &\leq A_1 A_2 \cdot A_3 A_4 - \left( \frac{A_1 A_2}{y} - \frac{3}{2} \right) 10^4 Z \\ &\leq A_1 A_2 \left( 1 - \frac{10^4 Z}{y} \right) + 1 + \frac{3}{2} y \\ &\leq 10^8 \frac{A}{y} + 1 + \frac{3}{2} y \end{aligned}$$

In the same way, and using  $1.7 \cdot 10^4 \leq y \leq 2.4 \cdot 10^4$ , and convexity, we get

$$\begin{aligned} 10^4 A &= 2 \cdot 10^4 \\ 10^4 B &\leq 10^8 \frac{A}{y} + 1.6y \leq 4.7 \cdot 10^4 \\ 10^4 C &\leq 10^8 \frac{B}{y} + 1.6y \leq 5.8 \cdot 10^4 \\ 10^4 D &\leq 10^8 \frac{C}{y} + 1.6y \leq 6.3 \cdot 10^4 \\ 10^4 E &\leq 10^8 \frac{D}{y} + 1.6y \leq 6.5 \cdot 10^4 \\ 10^4 F &\leq 10^8 \frac{E}{y} + 1.6y \leq 6.6 \cdot 10^4 \end{aligned}$$

Note that we compute more steps than for division: since  $t$  is not the end result, we need to know it with more accuracy (on the other hand, the ending is much simpler, as we don't need an exact rounding for transcendental functions, but just a faithful rounding).

`__fp_ln_x_iv:wnnnnnnnn <1 or 2> <8d> ; {<4d>} {<4d>} <fixed-tl>`

The number is  $x$ . Compute  $y$  by adding 1 to the five first digits.

```

14373 \cs_new:Npn __fp_ln_x_iv:wnnnnnnnn #1; #2#3#4#5 #6#7#8#9
14374 {
14375   \exp_after:wN __fp_div_significand_pack:NNN
14376   \__int_value:w \__int_eval:w
14377   \__fp_ln_div_i:w #1 ;
14378   #6 #7 ; {#8} {#9}
14379   {#2} {#3} {#4} {#5}
14380   { \exp_after:wN __fp_ln_div_ii:wnn \__int_value:w #1 }
14381   { \exp_after:wN __fp_ln_div_ii:wnn \__int_value:w #1 }
14382   { \exp_after:wN __fp_ln_div_ii:wnn \__int_value:w #1 }
14383   { \exp_after:wN __fp_ln_div_ii:wnn \__int_value:w #1 }
14384   { \exp_after:wN __fp_ln_div_vi:wnn \__int_value:w #1 }
14385 }
14386 \cs_new:Npn __fp_ln_div_i:w #1;
14387 {
14388   \exp_after:wN __fp_div_significand_calc:wnnnnnnnn
14389   \__int_value:w \__int_eval:w 999999 + 2 0000 0000 / #1 ; % Q1
14390 }
14391 \cs_new:Npn __fp_ln_div_ii:wnn #1; #2;#3 % y; B1;B2 <- for k=1
14392 {
```

```

14393 \exp_after:wN \__fp_div_significand_pack:NNN
14394 \__int_value:w \__int_eval:w
14395 \exp_after:wN \__fp_div_significand_calc:wnnnnnnnn
14396 \__int_value:w \__int_eval:w 999999 + #2 #3 / #1 ; % Q2
14397 #2 #3 ;
14398 }
14399 \cs_new:Npn \__fp_ln_div_vi:wnn #1; #2;#3#4#5 #6#7#8#9 %y;F1;F2F3F4x1x2x3x4
14400 {
14401 \exp_after:wN \__fp_div_significand_pack:NNN
14402 \__int_value:w \__int_eval:w 1000000 + #2 #3 / #1 ; % Q6
14403 }

```

We now have essentially

$$\begin{aligned} & \backslash\_fp\_ln\_div\_after:Nw \langle fixed\ tl \rangle \backslash\_fp\_div\_significand\_pack:NNN 10^6 + \\ & Q_1 \backslash\_fp\_div\_significand\_pack:NNN 10^6 + Q_2 \backslash\_fp\_div\_significand\_ \\ & pack:NNN 10^6 + Q_3 \backslash\_fp\_div\_significand\_pack:NNN 10^6 + Q_4 \backslash\_fp\_ \\ & div\_significand\_pack:NNN 10^6 + Q_5 \backslash\_fp\_div\_significand\_pack:NNN \\ & 10^6 + Q_6 ; \langle exponent \rangle ; \langle continuation \rangle \end{aligned}$$

where  $\langle fixed\ tl \rangle$  holds the logarithm of a number in  $[1, 10]$ , and  $\langle exponent \rangle$  is the exponent. Also, the expansion is done backwards. Then  $\backslash\_fp\_div\_significand\_pack:NNN$  puts things in the correct order to add the  $Q_i$  together and put semicolons between each piece. Once those have been expanded, we get

$$\begin{aligned} & \backslash\_fp\_ln\_div\_after:Nw \langle fixed-tl \rangle \langle 1d \rangle ; \langle 4d \rangle ; \langle 4d \rangle ; \langle 4d \rangle ; \langle 4d \rangle ; \langle 4d \rangle ; \\ & \langle 4d \rangle ; \langle exponent \rangle ; \end{aligned}$$

Just as with division, we know that the first two digits are 1 and 0 because of bounds on the final result of the division  $2/(x+1)$ , which is between roughly 0.8 and 1.2. We then compute  $1 - 2/(x+1)$ , after testing whether  $2/(x+1)$  is greater than or smaller than 1.

```

14404 \cs_new:Npn \__fp_ln_div_after:Nw #1#2;
14405 {
14406 \if_meaning:w 0 #2
14407 \exp_after:wN \__fp_ln_t_small:Nw
14408 \else:
14409 \exp_after:wN \__fp_ln_t_large:NNw
14410 \exp_after:wN -
14411 \fi:
14412 #1
14413 }
14414 \cs_new:Npn \__fp_ln_t_small:Nw #1 #2; #3; #4; #5; #6; #7;
14415 {
14416 \exp_after:wN \__fp_ln_t_large:NNw
14417 \exp_after:wN + % <sign>
14418 \exp_after:wN #1
14419 \__int_value:w \__int_eval:w 9999 - #2 \exp_after:wN ;
14420 \__int_value:w \__int_eval:w 9999 - #3 \exp_after:wN ;
14421 \__int_value:w \__int_eval:w 9999 - #4 \exp_after:wN ;
14422 \__int_value:w \__int_eval:w 9999 - #5 \exp_after:wN ;
14423 \__int_value:w \__int_eval:w 9999 - #6 \exp_after:wN ;
14424 \__int_value:w \__int_eval:w 1 0000 - #7 ;
14425 }

```

```

    \__fp_ln_t_large:NNw <sign><fixed tl> <t1>; <t2>; <t3>; <t4>; <t5>; <t6>;
    <exponent>; <continuation>

```

Compute the square  $t^2$ , and keep  $t$  at the end with its sign. We know that  $t < 0.1765$ , so every piece has at most 4 digits. However, since we were not careful in `\__fp_ln_t_small:w`, they can have less than 4 digits.

```

14426 \cs_new:Npn \__fp_ln_t_large:NNw #1 #2 #3; #4; #5; #6; #7; #8;
14427 {
14428   \exp_after:wN \__fp_ln_square_t_after:w
14429   \__int_value:w \__int_eval:w 9999 0000 + #3*#3
14430   \exp_after:wN \__fp_ln_square_t_pack:NNNNw
14431   \__int_value:w \__int_eval:w 9999 0000 + 2*#3*#4
14432   \exp_after:wN \__fp_ln_square_t_pack:NNNNw
14433   \__int_value:w \__int_eval:w 9999 0000 + 2*#3*#5 + #4*#4
14434   \exp_after:wN \__fp_ln_square_t_pack:NNNNw
14435   \__int_value:w \__int_eval:w 9999 0000 + 2*#3*#6 + 2*#4*#5
14436   \exp_after:wN \__fp_ln_square_t_pack:NNNNw
14437   \__int_value:w \__int_eval:w 1 0000 0000 + 2*#3*#7 + 2*#4*#6 + #5*#5
14438   + (2*#3*#8 + 2*#4*#7 + 2*#5*#6) / 1 0000
14439   % ; ; ;
14440   \exp_after:wN \__fp_ln_twice_t_after:w
14441   \__int_value:w \__int_eval:w -1 + 2*#3
14442   \exp_after:wN \__fp_ln_twice_t_pack:Nw
14443   \__int_value:w \__int_eval:w 9999 + 2*#4
14444   \exp_after:wN \__fp_ln_twice_t_pack:Nw
14445   \__int_value:w \__int_eval:w 9999 + 2*#5
14446   \exp_after:wN \__fp_ln_twice_t_pack:Nw
14447   \__int_value:w \__int_eval:w 9999 + 2*#6
14448   \exp_after:wN \__fp_ln_twice_t_pack:Nw
14449   \__int_value:w \__int_eval:w 9999 + 2*#7
14450   \exp_after:wN \__fp_ln_twice_t_pack:Nw
14451   \__int_value:w \__int_eval:w 10000 + 2*#8 ; ;
14452   { \__fp_ln_c:NwNw #1 }
14453   #2
14454 }
14455 \cs_new:Npn \__fp_ln_twice_t_pack:Nw #1 #2; { + #1 ; {#2} }
14456 \cs_new:Npn \__fp_ln_twice_t_after:w #1; { ; ; ; {#1} }
14457 \cs_new:Npn \__fp_ln_square_t_pack:NNNNw #1 #2#3#4#5 #6;
14458   { + #1#2#3#4#5 ; {#6} }
14459 \cs_new:Npn \__fp_ln_square_t_after:w 1 0 #1#2#3 #4;
14460   { \__fp_ln_Taylor:wwNw {0#1#2#3} {#4} }

```

(End definition for `\__fp_ln_x_ii:wnnnn`.)

`\__fp_ln_Taylor:wwNw` Denoting  $T = t^2$ , we get

```

    \__fp_ln_Taylor:wwNw {<T1>} {<T2>} {<T3>} {<T4>} {<T5>} {<T6>} ; ;
    {<(2t)1>} {<(2t)2>} {<(2t)3>} {<(2t)4>} {<(2t)5>} {<(2t)6>} ; { \__fp_ln_
    c:NwNw <sign> } <fixed tl> <exponent>; <continuation>

```

And we want to compute

$$\ln\left(\frac{1+t}{1-t}\right) = 2t \left(1 + T \left(\frac{1}{3} + T \left(\frac{1}{5} + T \left(\frac{1}{7} + T \left(\frac{1}{9} + \cdots\right)\right)\right)\right)\right)$$

The process looks as follows

```

\loop 5; A;
\div_int 5; 1.0; \add A; \mul T; {\loop \eval 5-2;}
\add 0.2; A; \mul T; {\loop \eval 5-2;}
\mul B; T; {\loop 3;}
\loop 3; C;

```

This uses the routine for dividing a number by a small integer ( $< 10^4$ ).

```

14461 \cs_new:Npn \__fp_ln_Taylor:wwNw
14462 { \__fp_ln_Taylor_loop:www 21 ; {0000}{0000}{0000}{0000}{0000}{0000} ; }
14463 \cs_new:Npn \__fp_ln_Taylor_loop:www #1; #2; #3;
14464 {
14465   \if_int_compare:w #1 = 1 \exp_stop_f:
14466   \__fp_ln_Taylor_break:w
14467   \fi:
14468   \exp_after:wN \__fp_fixed_div_int:wwN \c__fp_one_fixed_tl #1;
14469   \__fp_fixed_add:wwn #2;
14470   \__fp_fixed_mul:wwn #3;
14471   {
14472     \exp_after:wN \__fp_ln_Taylor_loop:www
14473     \__int_value:w \__int_eval:w #1 - 2 ;
14474   }
14475   #3;
14476 }
14477 \cs_new:Npn \__fp_ln_Taylor_break:w \fi: #1 \__fp_fixed_add:wwn #2#3; #4 ;;
14478 {
14479   \fi:
14480   \exp_after:wN \__fp_fixed_mul:wwn
14481   \exp_after:wN { \__int_value:w \__int_eval:w 10000 + #2 } #3;
14482 }

```

(End definition for  $\backslash\_\text{fp\_ln\_Taylor:wwNw}$ .)

$\backslash\_\text{fp\_ln\_c:NwNw}$   $\langle\text{sign}\rangle \{\langle r_1 \rangle\} \{\langle r_2 \rangle\} \{\langle r_3 \rangle\} \{\langle r_4 \rangle\} \{\langle r_5 \rangle\} \{\langle r_6 \rangle\}$  ;  $\langle\text{fixed tl}\rangle$   
 $\langle\text{exponent}\rangle$  ;  $\langle\text{continuation}\rangle$

We are now reduced to finding  $\ln(c)$  and  $\langle\text{exponent}\rangle \ln(10)$  in a table, and adding it to the mixture. The first step is to get  $\ln(c) - \ln(x) = -\ln(a)$ , then we get  $\text{b}\ln(10)$  and add or subtract.

For now,  $\ln(x)$  is given as  $\cdot 10^0$ . Unless both the exponent is 1 and  $c = 1$ , we shift to working in units of  $\cdot 10^4$ , since the final result is at least  $\ln(10/7) \simeq 0.35$ .

```

14483 \cs_new:Npn \__fp_ln_c:NwNw #1 #2; #3
14484 {
14485   \if_meaning:w + #1
14486   \exp_after:wN \exp_after:wN \exp_after:wN \__fp_fixed_sub:wwn
14487   \else:
14488   \exp_after:wN \exp_after:wN \exp_after:wN \__fp_fixed_add:wwn
14489   \fi:
14490   #3 #2 ;
14491 }

```

(End definition for  $\backslash\_\text{fp\_ln\_c:NwNw}$ .)

$\backslash\_\text{fp\_ln\_exponent:wn}$   $\backslash\_\text{fp\_ln\_exponent:wn} \{\langle s_1 \rangle\} \{\langle s_2 \rangle\} \{\langle s_3 \rangle\} \{\langle s_4 \rangle\} \{\langle s_5 \rangle\} \{\langle s_6 \rangle\}$  ;  
 $\{\langle\text{exponent}\rangle\}$

Compute  $\langle exponent \rangle$  times  $\ln(10)$ . Apart from the cases where  $\langle exponent \rangle$  is 0 or 1, the result is necessarily at least  $\ln(10) \simeq 2.3$  in magnitude. We can thus drop the least significant 4 digits. In the case of a very large (positive or negative) exponent, we can (and we need to) drop 4 additional digits, since the result is of order  $10^4$ . Naively, one would think that in both cases we can drop 4 more digits than we do, but that would be slightly too tight for rounding to happen correctly. Besides, we already have addition and subtraction for 24 digits fixed point numbers.

```

14492 \cs_new:Npn \__fp_ln_exponent:wn #1; #2
14493 {
14494   \if_case:w #2 \exp_stop_f:
14495     0 \__fp_case_return:nw { \__fp_fixed_to_float_o:Nw 2 }
14496   \or:
14497     \exp_after:wN \__fp_ln_exponent_one:ww \__int_value:w
14498   \else:
14499     \if_int_compare:w #2 > 0 \exp_stop_f:
14500       \exp_after:wN \__fp_ln_exponent_small:NNww
14501       \exp_after:wN 0
14502       \exp_after:wN \__fp_fixed_sub:wwn \__int_value:w
14503     \else:
14504       \exp_after:wN \__fp_ln_exponent_small:NNww
14505       \exp_after:wN 2
14506       \exp_after:wN \__fp_fixed_add:wwn \__int_value:w -
14507     \fi:
14508   \fi:
14509   #2; #1;
14510 }

```

Now we painfully write all the cases.<sup>12</sup> No overflow nor underflow can happen, except when computing  $\ln(1)$ .

```

14511 \cs_new:Npn \__fp_ln_exponent_one:ww 1; #1;
14512 {
14513   0
14514   \exp_after:wN \__fp_fixed_sub:wwn \c__fp_ln_x_fixed_tl #1;
14515   \__fp_fixed_to_float_o:wN 0
14516 }

```

For small exponents, we just drop one block of digits, and set the exponent of the log to 4 (minus any shift coming from leading zeros in the conversion from fixed point to floating point). Note that here the exponent has been made positive.

```

14517 \cs_new:Npn \__fp_ln_exponent_small:NNww #1#2#3; #4#5#6#7#8#9;
14518 {
14519   4
14520   \exp_after:wN \__fp_fixed_mul:wwn
14521     \c__fp_ln_x_fixed_tl
14522     {#3}{0000}{0000}{0000}{0000}{0000} ;
14523   #2
14524     {0000}{#4}{#5}{#6}{#7}{#8};
14525   \__fp_fixed_to_float_o:wN #1
14526 }

```

(End definition for  $\backslash\_fp\_ln\_exponent:wn$ .)

---

<sup>12</sup>Bruno: do rounding.

## 28.2 Exponential

### 28.2.1 Sign, exponent, and special numbers

\\_\_fp\_exp\_o:w

```
14527 \cs_new:Npn \__fp_exp_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
14528 {
14529   \if_case:w #2 \exp_stop_f:
14530     \__fp_case_return_o:Nw \c_one_fp
14531   \or:
14532     \exp_after:wN \__fp_exp_normal_o:w
14533   \or:
14534     \if_meaning:w 0 #3
14535       \exp_after:wN \__fp_case_return_o:Nw
14536       \exp_after:wN \c_inf_fp
14537     \else:
14538       \exp_after:wN \__fp_case_return_o:Nw
14539       \exp_after:wN \c_zero_fp
14540     \fi:
14541   \or:
14542     \__fp_case_return_same_o:w
14543   \fi:
14544   \s__fp \__fp_chk:w #2#3#4;
14545 }
```

(End definition for \\_\_fp\_exp\_o:w.)

\\_\_fp\_exp\_normal\_o:w  
\\_\_fp\_exp\_pos\_o:NNwnw  
\\_\_fp\_exp\_overflow:NN

```
14546 \cs_new:Npn \__fp_exp_normal_o:w \s__fp \__fp_chk:w 1#1
14547 {
14548   \if_meaning:w 0 #1
14549     \__fp_exp_pos_o:NNwnw + \__fp_fixed_to_float_o:wN
14550   \else:
14551     \__fp_exp_pos_o:NNwnw - \__fp_fixed_inv_to_float_o:wN
14552   \fi:
14553 }
14554 \cs_new:Npn \__fp_exp_pos_o:NNwnw #1#2#3 \fi: #4#5;
14555 {
14556   \fi:
14557   \if_int_compare:w #4 > \c__fp_max_exp_exponent_int
14558     \token_if_eq_charcode:NNTF + #1
14559     { \__fp_exp_overflow:NN \__fp_overflow:w \c_inf_fp }
14560     { \__fp_exp_overflow:NN \__fp_underflow:w \c_zero_fp }
14561   \exp:w
14562   \else:
14563     \exp_after:wN \__fp_sanitize:Nw
14564     \exp_after:wN 0
14565     \__int_value:w #1 \__int_eval:w
14566     \if_int_compare:w #4 < 0 \exp_stop_f:
14567       \exp_after:wN \use_i:nn
14568     \else:
14569       \exp_after:wN \use_ii:nn
14570     \fi:
14571     {
14572       0
```



```

14573         \__fp_decimate:nNnnnn { - #4 }
14574         \__fp_exp_Taylor:Nnnwn
14575     }
14576     {
14577         \__fp_decimate:nNnnnn { \c__fp_prec_int - #4 }
14578         \__fp_exp_pos_large:NnnNwn
14579     }
14580     #5
14581     {#4}
14582     #1 #2 0
14583     \exp:w
14584     \fi:
14585     \exp_after:wN \exp_end:
14586 }
14587 \cs_new:Npn \__fp_exp_overflow:NN #1#2
14588 {
14589     \exp_after:wN \exp_after:wN
14590     \exp_after:wN #1
14591     \exp_after:wN #2
14592 }

```

(End definition for \\_\_fp\_exp\_normal\_o:w, \\_\_fp\_exp\_pos\_o:Nnnwn, and \\_\_fp\_exp\_overflow:NN.)

```

\__fp_exp_Taylor:Nnnwn
\__fp_exp_Taylor_loop:www
\__fp_exp_Taylor_break:Nww

```

This function is called for numbers in the range  $[10^{-9}, 10^{-1}]$ . We compute 10 terms of the Taylor series. The first argument is irrelevant (rounding digit used by some other functions). The next three arguments, at least 16 digits, delimited by a semicolon, form a fixed point number, so we pack it in blocks of 4 digits.

```

14593 \cs_new:Npn \__fp_exp_Taylor:Nnnwn #1#2#3 #4; #5 #6
14594 {
14595     #6
14596     \__fp_pack_twice_four:wNNNNNNNN
14597     \__fp_pack_twice_four:wNNNNNNNN
14598     \__fp_pack_twice_four:wNNNNNNNN
14599     \__fp_exp_Taylor_ii:ww
14600     ; #2#3#4 0000 0000 ;
14601 }
14602 \cs_new:Npn \__fp_exp_Taylor_ii:ww #1; #2;
14603 { \__fp_exp_Taylor_loop:www 10 ; #1 ; #1 ; \s__stop }
14604 \cs_new:Npn \__fp_exp_Taylor_loop:www #1; #2; #3;
14605 {
14606     \if_int_compare:w #1 = 1 \exp_stop_f:
14607     \exp_after:wN \__fp_exp_Taylor_break:Nww
14608     \fi:
14609     \__fp_fixed_div_int:wwN #3 ; #1 ;
14610     \__fp_fixed_add_one:wN
14611     \__fp_fixed_mul:wwN #2 ;
14612     {
14613         \exp_after:wN \__fp_exp_Taylor_loop:www
14614         \__int_value:w \__int_eval:w #1 - 1 ;
14615         #2 ;
14616     }
14617 }
14618 \cs_new:Npn \__fp_exp_Taylor_break:Nww #1 #2; #3 \s__stop
14619 { \__fp_fixed_add_one:wN #2 ; }

```

(End definition for `\__fp_exp_Taylor:Nnnwn`, `\__fp_exp_Taylor_loop:www`, and `\__fp_exp_Taylor-break:Nww`.)

`\__fp_exp_pos_large:NnnNwn` The first two arguments are irrelevant (a rounding digit, and a brace group with 8 zeros).  
`\__fp_exp_large_after:wn` The third argument is the integer part of our number, then we have the decimal part  
`\__fp_exp_large:w` delimited by a semicolon, and finally the exponent, in the range  $[0, 5]$ . Remove leading  
`\__fp_exp_large_v:wN` zeros from the integer part: putting #4 in there too ensures that an integer part of 0 is  
`\__fp_exp_large_iv:wN` also removed. Then read digits one by one, looking up  $\exp(\langle digit \rangle \cdot 10^{\langle exponent \rangle})$  in a table,  
`\__fp_exp_large_iii:wN` and multiplying that to the current total. The loop is done by having the auxiliary for  
`\__fp_exp_large_ii:wN` one exponent call the auxiliary for the next exponent. The current total is expressed by  
`\__fp_exp_large_i:wN` leaving the exponent behind in the input stream (we are currently within an `\__int-`  
`\__fp_exp_large:wN` `eval:w`), and keeping track of a fixed point number, #1 for the numbered auxiliaries. Our  
usage of `\if_case:w` is somewhat dirty for optimization: `TeX` jumps to the appropriate  
case, but we then close the `\if_case:w` “by hand”, using `\or:` and `\fi:` as delimiters.

```

14620 \cs_new:Npn \__fp_exp_pos_large:NnnNwn #1#2#3 #4#5; #6
14621 {
14622   \exp_after:wN \exp_after:wN
14623   \cs:w \__fp_exp_large_ \__int_to_roman:w #6 :wN \exp_after:wN \cs_end:
14624   \exp_after:wN \c__fp_one_fixed_tl
14625   \__int_value:w #3 #4 \exp_stop_f:
14626   #5 00000 ;
14627 }
14628 \cs_new:Npn \__fp_exp_large:w #1 \or: #2 \fi:
14629 { \fi: \__fp_fixed_mul:wnn #1; }
14630 \cs_new:Npn \__fp_exp_large_v:wN #1; #2
14631 {
14632   \if_case:w #2 ~ \exp_after:wN \__fp_fixed_continue:wn \or:
14633   + 4343 \__fp_exp_large:w {8806}{8182}{2566}{2921}{5872}{6150} \or:
14634   + 8686 \__fp_exp_large:w {7756}{0047}{2598}{6861}{0458}{3204} \or:
14635   + 13029 \__fp_exp_large:w {6830}{5723}{7791}{4884}{1932}{7351} \or:
14636   + 17372 \__fp_exp_large:w {6015}{5609}{3095}{3052}{3494}{7574} \or:
14637   + 21715 \__fp_exp_large:w {5297}{7951}{6443}{0315}{3251}{3576} \or:
14638   + 26058 \__fp_exp_large:w {4665}{6719}{0099}{3379}{5527}{2929} \or:
14639   + 30401 \__fp_exp_large:w {4108}{9724}{3326}{3186}{5271}{5665} \or:
14640   + 34744 \__fp_exp_large:w {3618}{6973}{3140}{0875}{3856}{4102} \or:
14641   + 39087 \__fp_exp_large:w {3186}{9209}{6113}{3900}{6705}{9685} \or:
14642   \fi:
14643   #1;
14644   \__fp_exp_large_iv:wN
14645 }
14646 \cs_new:Npn \__fp_exp_large_iv:wN #1; #2
14647 {
14648   \if_case:w #2 ~ \exp_after:wN \__fp_fixed_continue:wn \or:
14649   + 435 \__fp_exp_large:w {1970}{0711}{1401}{7046}{9938}{8888} \or:
14650   + 869 \__fp_exp_large:w {3881}{1801}{9428}{4368}{5764}{8232} \or:
14651   + 1303 \__fp_exp_large:w {7646}{2009}{8905}{4704}{8893}{1073} \or:
14652   + 1738 \__fp_exp_large:w {1506}{3559}{7005}{0524}{9009}{7592} \or:
14653   + 2172 \__fp_exp_large:w {2967}{6283}{8402}{3667}{0689}{6630} \or:
14654   + 2606 \__fp_exp_large:w {5846}{4389}{5650}{2114}{7278}{5046} \or:
14655   + 3041 \__fp_exp_large:w {1151}{7900}{5080}{6878}{2914}{4154} \or:
14656   + 3475 \__fp_exp_large:w {2269}{1083}{0850}{6857}{8724}{4002} \or:
14657   + 3909 \__fp_exp_large:w {4470}{3047}{3316}{5442}{6408}{6591} \or:
14658   \fi:

```

```

14659     #1;
14660     \__fp_exp_large_iii:wN
14661 }
14662 \cs_new:Npn \__fp_exp_large_iii:wN #1; #2
14663 {
14664     \if_case:w #2 ~          \exp_after:wN \__fp_fixed_continue:wn \or:
14665     + 44 \__fp_exp_large:w {2688}{1171}{4181}{6135}{4484}{1263} \or:
14666     + 87 \__fp_exp_large:w {7225}{9737}{6812}{5749}{2581}{7748} \or:
14667     + 131 \__fp_exp_large:w {1942}{4263}{9524}{1255}{9365}{8421} \or:
14668     + 174 \__fp_exp_large:w {5221}{4696}{8976}{4143}{9505}{8876} \or:
14669     + 218 \__fp_exp_large:w {1403}{5922}{1785}{2837}{4107}{3977} \or:
14670     + 261 \__fp_exp_large:w {3773}{0203}{0092}{9939}{8234}{0143} \or:
14671     + 305 \__fp_exp_large:w {1014}{2320}{5473}{5004}{5094}{5533} \or:
14672     + 348 \__fp_exp_large:w {2726}{3745}{7211}{2566}{5673}{6478} \or:
14673     + 391 \__fp_exp_large:w {7328}{8142}{2230}{7421}{7051}{8866} \or:
14674     \fi:
14675     #1;
14676     \__fp_exp_large_ii:wN
14677 }
14678 \cs_new:Npn \__fp_exp_large_ii:wN #1; #2
14679 {
14680     \if_case:w #2 ~          \exp_after:wN \__fp_fixed_continue:wn \or:
14681     + 5 \__fp_exp_large:w {2202}{6465}{7948}{0671}{6516}{9579} \or:
14682     + 9 \__fp_exp_large:w {4851}{6519}{5409}{7902}{7796}{9107} \or:
14683     + 14 \__fp_exp_large:w {1068}{6474}{5815}{2446}{2146}{9905} \or:
14684     + 18 \__fp_exp_large:w {2353}{8526}{6837}{0199}{8540}{7900} \or:
14685     + 22 \__fp_exp_large:w {5184}{7055}{2858}{7072}{4640}{8745} \or:
14686     + 27 \__fp_exp_large:w {1142}{0073}{8981}{5684}{2836}{6296} \or:
14687     + 31 \__fp_exp_large:w {2515}{4386}{7091}{9167}{0062}{6578} \or:
14688     + 35 \__fp_exp_large:w {5540}{6223}{8439}{3510}{0525}{7117} \or:
14689     + 40 \__fp_exp_large:w {1220}{4032}{9431}{7840}{8020}{0271} \or:
14690     \fi:
14691     #1;
14692     \__fp_exp_large_i:wN
14693 }
14694 \cs_new:Npn \__fp_exp_large_i:wN #1; #2
14695 {
14696     \if_case:w #2 ~          \exp_after:wN \__fp_fixed_continue:wn \or:
14697     + 1 \__fp_exp_large:w {2718}{2818}{2845}{9045}{2353}{6029} \or:
14698     + 1 \__fp_exp_large:w {7389}{0560}{9893}{0650}{2272}{3043} \or:
14699     + 2 \__fp_exp_large:w {2008}{5536}{9231}{8766}{7740}{9285} \or:
14700     + 2 \__fp_exp_large:w {5459}{8150}{0331}{4423}{9078}{1103} \or:
14701     + 3 \__fp_exp_large:w {1484}{1315}{9102}{5766}{0342}{1116} \or:
14702     + 3 \__fp_exp_large:w {4034}{2879}{3492}{7351}{2260}{8387} \or:
14703     + 4 \__fp_exp_large:w {1096}{6331}{5842}{8458}{5992}{6372} \or:
14704     + 4 \__fp_exp_large:w {2980}{9579}{8704}{1728}{2747}{4359} \or:
14705     + 4 \__fp_exp_large:w {8103}{0839}{2757}{5384}{0077}{1000} \or:
14706     \fi:
14707     #1;
14708     \__fp_exp_large_:wN
14709 }
14710 \cs_new:Npn \__fp_exp_large_:wN #1; #2
14711 {
14712     \if_case:w #2 ~          \exp_after:wN \__fp_fixed_continue:wn \or:

```

```

14713 + 1 \__fp_exp_large:w {1105}{1709}{1807}{5647}{6248}{1171} \or:
14714 + 1 \__fp_exp_large:w {1221}{4027}{5816}{0169}{8339}{2107} \or:
14715 + 1 \__fp_exp_large:w {1349}{8588}{0757}{6003}{1039}{8374} \or:
14716 + 1 \__fp_exp_large:w {1491}{8246}{9764}{1270}{3178}{2485} \or:
14717 + 1 \__fp_exp_large:w {1648}{7212}{7070}{0128}{1468}{4865} \or:
14718 + 1 \__fp_exp_large:w {1822}{1188}{0039}{0508}{9748}{7537} \or:
14719 + 1 \__fp_exp_large:w {2013}{7527}{0747}{0476}{5216}{2455} \or:
14720 + 1 \__fp_exp_large:w {2225}{5409}{2849}{2467}{6045}{7954} \or:
14721 + 1 \__fp_exp_large:w {2459}{6031}{1115}{6949}{6638}{0013} \or:
14722 \fi:
14723 #1;
14724 \__fp_exp_large_after:wwn
14725 }
14726 \cs_new:Npn \__fp_exp_large_after:wwn #1; #2; #3
14727 {
14728   \__fp_exp_Taylor:Nnnwn ? { } { } 0 #2; {} #3
14729   \__fp_fixed_mul:wwn #1;
14730 }

```

(End definition for `\__fp_exp_pos_large:NnnNwn` and others.)

## 28.3 Power

Raising a number  $a$  to a power  $b$  leads to many distinct situations.

$a^b$	$-\infty$	$(-\infty, -0)$	$-p/5^k$	$\pm 0$	$+p/5^k$	$(0, \infty)$	$+\infty$	NaN
$+\infty$	$+0$		$+0$	$+1$		$+\infty$	$+\infty$	NaN
$(1, \infty)$	$+0$		$+ a ^b$	$+1$		$+ a ^b$	$+\infty$	NaN
$+1$	$+1$		$+1$	$+1$		$+1$	$+1$	$+1$
$(0, 1)$	$+\infty$		$+ a ^b$	$+1$		$+ a ^b$	$+0$	NaN
$+0$	$+\infty$		$+\infty$	$+1$		$+0$	$+0$	NaN
$-0$	$+\infty$	NaN	$(-1)^{p\infty}$	$+1$	$(-1)^{p0}$	$+0$	$+0$	NaN
$(-1, 0)$	$+\infty$	NaN	$(-1)^p a ^b$	$+1$	$(-1)^p a ^b$	NaN	$+0$	NaN
$-1$	$+1$	NaN	$(-1)^p$	$+1$	$(-1)^p$	NaN	$+1$	NaN
$(-\infty, -1)$	$+0$	NaN	$(-1)^p a ^b$	$+1$	$(-1)^p a ^b$	NaN	$+\infty$	NaN
$-\infty$	$+0$	$+0$	$(-1)^{p0}$	$+1$	$(-1)^{p\infty}$	NaN	$+\infty$	NaN
NaN	NaN	NaN	NaN	$+1$	NaN	NaN	NaN	NaN

We distinguished in this table the cases of finite (positive or negative) exponents of the form  $b = p/q$  with  $q$  odd (hence necessarily a power of 5), as  $(-1)^{p/q} = (-1)^p$  is defined in that case. One peculiarity of this operation is that  $\text{NaN}^0 = 1^{\text{NaN}} = 1$ , because this relation is obeyed for any number, even  $\pm\infty$ .

`\__fp^_o:ww` We cram most of the tests into a single function to save csnames. First treat the case  $b = 0$ :  $a^0 = 1$  for any  $a$ , even `nan`. Then test the sign of  $a$ .

- If it is positive, and  $a$  is a normal number, call `\__fp_pow_normal_o:ww` followed by the two `fp`  $a$  and  $b$ . For  $a = +0$  or  $+\text{inf}$ , call `\__fp_pow_zero_or_inf:ww` instead, to return either  $+0$  or  $+\infty$  as appropriate.
- If  $a$  is a `nan`, then skip to the next semicolon (which happens to be conveniently the end of  $b$ ) and return `nan`.

- Finally, if  $a$  is negative, compute  $a^b$  (`\__fp_pow_normal_o:ww` which ignores the sign of its first operand), and keep an extra copy of  $a$  and  $b$  (the second brace group, containing  $\{ b \ a \}$ , is inserted between  $a$  and  $b$ ). Then do some tests to find the final sign of the result if it exists.

```

14731 \cs_new:cpn { __fp_ \iow_char:N \^_o:ww }
14732   \s__fp \__fp_chk:w #1#2#3; \s__fp \__fp_chk:w #4#5#6;
14733   {
14734     \if_meaning:w 0 #4
14735       \__fp_case_return_o:Nw \c_one_fp
14736     \fi:
14737     \if_case:w #2 \exp_stop_f:
14738       \exp_after:wN \use_i:nn
14739     \or:
14740       \__fp_case_return_o:Nw \c_nan_fp
14741     \else:
14742       \exp_after:wN \__fp_pow_neg:www
14743       \exp:w \exp_end_continue_f:w \exp_after:wN \use:nn
14744     \fi:
14745     {
14746       \if_meaning:w 1 #1
14747         \exp_after:wN \__fp_pow_normal_o:ww
14748       \else:
14749         \exp_after:wN \__fp_pow_zero_or_inf:ww
14750       \fi:
14751       \s__fp \__fp_chk:w #1#2#3;
14752     }
14753     { \s__fp \__fp_chk:w #4#5#6; \s__fp \__fp_chk:w #1#2#3; }
14754     \s__fp \__fp_chk:w #4#5#6;
14755   }

```

(End definition for `\__fp_ \^_o:ww`.)

`\__fp_pow_zero_or_inf:ww` Raising  $-0$  or  $-\infty$  to `nan` yields `nan`. For other powers, the result is  $+0$  if  $0$  is raised to a positive power or  $\infty$  to a negative power, and  $+\infty$  otherwise. Thus, if the type of  $a$  and the sign of  $b$  coincide, the result is  $0$ , since those conveniently take the same possible values,  $0$  and  $2$ . Otherwise, either  $a = \pm\infty$  and  $b > 0$  and the result is  $+\infty$ , or  $a = \pm 0$  with  $b < 0$  and we have a division by zero unless  $b = -\infty$ .

```

14756 \cs_new:Npn \__fp_pow_zero_or_inf:ww
14757   \s__fp \__fp_chk:w #1#2; \s__fp \__fp_chk:w #3#4
14758   {
14759     \if_meaning:w 1 #4
14760       \__fp_case_return_same_o:w
14761     \fi:
14762     \if_meaning:w #1 #4
14763       \__fp_case_return_o:Nw \c_zero_fp
14764     \fi:
14765     \if_meaning:w 2 #1
14766       \__fp_case_return_o:Nw \c_inf_fp
14767     \fi:
14768     \if_meaning:w 2 #3
14769       \__fp_case_return_o:Nw \c_inf_fp
14770     \else:
14771       \__fp_case_use:nw

```

```

14772     {
14773         \__fp_division_by_zero_o:NNww \c_inf_fp ^
14774         \s__fp \__fp_chk:w #1 #2 ;
14775     }
14776     \fi:
14777     \s__fp \__fp_chk:w #3#4
14778 }

```

(End definition for \\_\_fp\_pow\_zero\_or\_inf:ww.)

\\_\_fp\_pow\_normal\_o:ww We have in front of us  $a$ , and  $b \neq 0$ , we know that  $a$  is a normal number, and we wish to compute  $|a|^b$ . If  $|a| = 1$ , we return 1, unless  $a = -1$  and  $b$  is **nan**. Indeed, returning 1 at this point would wrongly raise “invalid” when the sign is considered. If  $|a| \neq 1$ , test the type of  $b$ :

0 Impossible, we already filtered  $b = \pm 0$ .

1 Call \\_\_fp\_pow\_npos\_o:Nww.

2 Return  $+\infty$  or  $+0$  depending on the sign of  $b$  and whether the exponent of  $a$  is positive or not.

3 Return  $b$ .

```

14779 \cs_new:Npn \__fp_pow_normal_o:ww
14780   \s__fp \__fp_chk:w 1 #1#2#3; \s__fp \__fp_chk:w #4#5
14781   {
14782     \if_int_compare:w \__str_if_eq_x:nn { #2 #3 }
14783       { 1 {1000} {0000} {0000} {0000} } = 0 \exp_stop_f:
14784     \if_int_compare:w #4 #1 = 32 \exp_stop_f:
14785     \exp_after:wN \__fp_case_return_ii_o:ww
14786     \fi:
14787     \__fp_case_return_o:Nww \c_one_fp
14788     \fi:
14789     \if_case:w #4 \exp_stop_f:
14790     \or:
14791       \exp_after:wN \__fp_pow_npos_o:Nww
14792       \exp_after:wN #5
14793     \or:
14794       \if_meaning:w 2 #5 \exp_after:wN \reverse_if:N \fi:
14795       \if_int_compare:w #2 > 0 \exp_stop_f:
14796       \exp_after:wN \__fp_case_return_o:Nww
14797       \exp_after:wN \c_inf_fp
14798     \else:
14799       \exp_after:wN \__fp_case_return_o:Nww
14800       \exp_after:wN \c_zero_fp
14801     \fi:
14802     \or:
14803       \__fp_case_return_ii_o:ww
14804     \fi:
14805     \s__fp \__fp_chk:w 1 #1 {#2} #3 ;
14806     \s__fp \__fp_chk:w #4 #5
14807   }

```

(End definition for \\_\_fp\_pow\_normal\_o:ww.)

`\__fp_pow_npos_o:Nww` We now know that  $a \neq \pm 1$  is a normal number, and  $b$  is a normal number too. We want to compute  $|a|^b = (|x| \cdot 10^n)^{y \cdot 10^p} = \exp((\ln|x| + n \ln(10)) \cdot y \cdot 10^p) = \exp(z)$ . To compute the exponential accurately, we need to know the digits of  $z$  up to the 16-th position. Since the exponential of  $10^5$  is infinite, we only need at most 21 digits, hence the fixed point result of `\__fp_ln_o:w` is precise enough for our needs. Start an integer expression for the decimal exponent of  $e^{|z|}$ . If  $z$  is negative, negate that decimal exponent, and prepare to take the inverse when converting from the fixed point to the floating point result.

```

14808 \cs_new:Npn \__fp_pow_npos_o:Nww #1 \s__fp \__fp_chk:w 1#2#3
14809 {
14810   \exp_after:wN \__fp_sanitize:Nw
14811   \exp_after:wN 0
14812   \__int_value:w
14813   \if:w #1 \if_int_compare:w #3 > 0 \exp_stop_f: 0 \else: 2 \fi:
14814   \exp_after:wN \__fp_pow_npos_aux:NNnw
14815   \exp_after:wN +
14816   \exp_after:wN \__fp_fixed_to_float_o:wN
14817   \else:
14818   \exp_after:wN \__fp_pow_npos_aux:NNnw
14819   \exp_after:wN -
14820   \exp_after:wN \__fp_fixed_inv_to_float_o:wN
14821   \fi:
14822   {#3}
14823 }

```

(End definition for `\__fp_pow_npos_o:Nww`.)

`\__fp_pow_npos_aux:NNnw` The first argument is the conversion function from fixed point to float. Then comes an exponent and the 4 brace groups of  $x$ , followed by  $b$ . Compute  $-\ln(x)$ .

```

14824 \cs_new:Npn \__fp_pow_npos_aux:NNnw #1#2#3#4#5; \s__fp \__fp_chk:w 1#6#7#8;
14825 {
14826   #1
14827   \__int_eval:w
14828   \__fp_ln_significand:NNNNnnnN #4#5
14829   \__fp_pow_exponent:wnN {#3}
14830   \__fp_fixed_mul:wwN #8 {0000}{0000} ;
14831   \__fp_pow_B:wwN #7;
14832   #1 #2 0 % fixed_to_float_o:wN
14833 }
14834 \cs_new:Npn \__fp_pow_exponent:wnN #1; #2
14835 {
14836   \if_int_compare:w #2 > 0 \exp_stop_f:
14837   \exp_after:wN \__fp_pow_exponent:Nwnnnnw % n\ln(10) - (-\ln(x))
14838   \exp_after:wN +
14839   \else:
14840   \exp_after:wN \__fp_pow_exponent:Nwnnnnw % -(\ln|\ln(10) + (-\ln(x)))
14841   \exp_after:wN -
14842   \fi:
14843   #2; #1;
14844 }
14845 \cs_new:Npn \__fp_pow_exponent:Nwnnnnw #1#2; #3#4#5#6#7#8;
14846 { %^A todo: use that in ln.
14847   \exp_after:wN \__fp_fixed_mul_after:wwN
14848   \__int_value:w \__int_eval:w \c__fp_leading_shift_int

```

```

14849     \exp_after:wN \__fp_pack:NNNNNw
14850     \__int_value:w \__int_eval:w \c__fp_middle_shift_int
14851     #1#2*23025 - #1 #3
14852     \exp_after:wN \__fp_pack:NNNNNw
14853     \__int_value:w \__int_eval:w \c__fp_middle_shift_int
14854     #1 #2*8509 - #1 #4
14855     \exp_after:wN \__fp_pack:NNNNNw
14856     \__int_value:w \__int_eval:w \c__fp_middle_shift_int
14857     #1 #2*2994 - #1 #5
14858     \exp_after:wN \__fp_pack:NNNNNw
14859     \__int_value:w \__int_eval:w \c__fp_middle_shift_int
14860     #1 #2*0456 - #1 #6
14861     \exp_after:wN \__fp_pack:NNNNNw
14862     \__int_value:w \__int_eval:w \c__fp_trailing_shift_int
14863     #1 #2*8401 - #1 #7
14864     #1 ( #2*7991 - #8 ) / 1 0000 ; ;
14865 }
14866 \cs_new:Npn \__fp_pow_B:wwN #1#2#3#4#5#6; #7;
14867 {
14868     \if_int_compare:w #7 < 0 \exp_stop_f:
14869     \exp_after:wN \__fp_pow_C_neg:w \__int_value:w -
14870     \else:
14871     \if_int_compare:w #7 < 22 \exp_stop_f:
14872     \exp_after:wN \__fp_pow_C_pos:w \__int_value:w
14873     \else:
14874     \exp_after:wN \__fp_pow_C_overflow:w \__int_value:w
14875     \fi:
14876     \fi:
14877     #7 \exp_after:wN ;
14878     \__int_value:w \__int_eval:w 10 0000 + #1 \__int_eval_end:
14879     #2#3#4#5#6 0000 0000 0000 0000 0000 0000 ; %^A todo: how many 0?
14880 }
14881 \cs_new:Npn \__fp_pow_C_overflow:w #1; #2; #3
14882 {
14883     + 2 * \c__fp_max_exponent_int
14884     \exp_after:wN \__fp_fixed_continue:wn \c__fp_one_fixed_tl
14885 }
14886 \cs_new:Npn \__fp_pow_C_neg:w #1 ; 1
14887 {
14888     \exp_after:wN \exp_after:wN \exp_after:wN \__fp_pow_C_pack:w
14889     \prg_replicate:nn {#1} {0}
14890 }
14891 \cs_new:Npn \__fp_pow_C_pos:w #1; 1
14892 { \__fp_pow_C_pos_loop:wN #1; }
14893 \cs_new:Npn \__fp_pow_C_pos_loop:wN #1; #2
14894 {
14895     \if_meaning:w 0 #1
14896     \exp_after:wN \__fp_pow_C_pack:w
14897     \exp_after:wN #2
14898     \else:
14899     \if_meaning:w 0 #2
14900     \exp_after:wN \__fp_pow_C_pos_loop:wN \__int_value:w
14901     \else:
14902     \exp_after:wN \__fp_pow_C_overflow:w \__int_value:w

```



```

14903     \fi:
14904     \__int_eval:w #1 - 1 \exp_after:wN ;
14905     \fi:
14906   }
14907 \cs_new:Npn \__fp_pow_C_pack:w
14908 { \exp_after:wN \__fp_exp_large_v:wN \c__fp_one_fixed_tl }

```

(End definition for `\__fp_pow_npos_aux:NNnw`.)

`\__fp_pow_neg:www`  
`\__fp_pow_neg_aux:wNN`

This function is followed by three floating point numbers:  $a^b$ ,  $a \in [-\infty, -0]$ , and  $b$ . If  $b$  is an even integer (case  $-1$ ),  $a^b = a^b$ . If  $b$  is an odd integer (case  $0$ ),  $a^b = -a^b$ , obtained by a call to `\__fp_pow_neg_aux:wNN`. Otherwise, the sign is undefined. This is invalid, unless  $a^b$  turns out to be  $+0$  or `nan`, in which case we return that as  $a^b$ . In particular, since the underflow detection occurs before `\__fp_pow_neg:www` is called,  $(-0.1)**(12345.67)$  gives  $+0$  rather than complaining that the sign is not defined.

```

14909 \cs_new:Npn \__fp_pow_neg:www \s__fp \__fp_chk:w #1#2; #3; #4;
14910 {
14911   \if_case:w \__fp_pow_neg_case:w #4 ;
14912     \exp_after:wN \__fp_pow_neg_aux:wNN
14913   \or:
14914     \if_int_compare:w \__int_eval:w #1 / 2 = 1 \exp_stop_f:
14915     \__fp_invalid_operation_o:Nww ^ #3; #4;
14916     \exp:w \exp_end_continue_f:w
14917     \exp_after:wN \exp_after:wN
14918     \exp_after:wN \__fp_use_none_until_s:w
14919   \fi:
14920   \fi:
14921   \__fp_exp_after_o:w
14922   \s__fp \__fp_chk:w #1#2;
14923 }
14924 \cs_new:Npn \__fp_pow_neg_aux:wNN #1 \s__fp \__fp_chk:w #2#3
14925 {
14926   \exp_after:wN \__fp_exp_after_o:w
14927   \exp_after:wN \s__fp
14928   \exp_after:wN \__fp_chk:w
14929   \exp_after:wN #2
14930   \__int_value:w \__int_eval:w 2 - #3 \__int_eval_end:
14931 }

```

(End definition for `\__fp_pow_neg:www` and `\__fp_pow_neg_aux:wNN`.)

`\__fp_pow_neg_case:w`  
`\__fp_pow_neg_case_aux:nnnnn`  
`\__fp_pow_neg_case_aux:w`

This function expects a floating point number, and determines its “parity”. It should be used after `\if_case:w` or in an integer expression. It gives  $-1$  if the number is an even integer divided by some power of  $5$ ,  $0$  if the number is an odd integer divided by some power of  $5$ , and  $1$  otherwise. Zeros and  $\pm\infty$  are even (because very large finite floating points are even), while `nan` is a non-integer. The sign of normal numbers is irrelevant to parity. The idea is to repeatedly multiply the number by  $5$  (by halving the mantissa and shifting the exponent) until the mantissa is odd (this can only happen at most  $53$  times since  $2^{54} > 10^{16}$ ): if the resulting exponent is larger than  $16$  the parity is even, if it is exactly  $16$  the parity is odd, and otherwise we should return  $1$ . Of course there is a shortcut: we stop as soon as the exponent exceeds  $16$ .

```

14932 \cs_new:Npn \__fp_pow_neg_case:w \s__fp \__fp_chk:w #1#2#3;
14933 {

```

```

14934 \if_case:w #1 \exp_stop_f:
14935     -1
14936 \or: \__fp_pow_neg_case_aux:nnnnn #3
14937 \or: -1
14938 \else: 1
14939 \fi:
14940 \exp_stop_f:
14941 }
14942 \cs_new:Npn \__fp_pow_neg_case_aux:nnnnn #1#2#3#4#5
14943 { \__fp_pow_neg_case_aux:w #1 ; #2 #3 ; #4 #5 ; }
14944 \cs_new:Npn \__fp_pow_neg_case_aux:w #1 ; #2 ; #3 ;
14945 {
14946     \if_int_compare:w #1 > \c__fp_prec_int
14947         -1
14948     \else:
14949         \if_int_odd:w #3 \exp_stop_f:
14950         \if_int_compare:w #1 = \c__fp_prec_int
14951             0
14952         \else:
14953             1
14954         \fi:
14955     \else:
14956         \exp_after:wN \__fp_pow_neg_case_aux:w
14957         \__int_value:w \__int_eval:w #1 + 1 \exp_after:wN ;
14958         \__int_value:w \__int_eval:w (#2 + 1) / 2 - 1 \exp_after:wN ;
14959         \__int_value:w \__int_eval:w
14960         \if_int_odd:w #2 \exp_stop_f: 5000 0000 + \fi: #3 / 2 ;
14961     \fi:
14962 \fi:
14963 }

```

(End definition for \\_\_fp\_pow\_neg\_case:w, \\_\_fp\_pow\_neg\_case\_aux:nnnnn, and \\_\_fp\_pow\_neg\_case\_aux:w.)

```

14964 </initex | package>

```

## 29 l3fp-trig Implementation

```

14965 <*initex | package>
14966 <@@=fp>

```

Unary functions.

```

\__fp_parse_word_acos:N
\__fp_parse_word_acosd:N
\__fp_parse_word_acsc:N
\__fp_parse_word_acscd:N
\__fp_parse_word_asec:N
\__fp_parse_word_asecd:N
\__fp_parse_word_asin:N
\__fp_parse_word_asind:N
\__fp_parse_word_cos:N
\__fp_parse_word_cosd:N
\__fp_parse_word_cot:N
\__fp_parse_word_cotd:N
\__fp_parse_word_csc:N
\__fp_parse_word_cscd:N
\__fp_parse_word_sec:N
\__fp_parse_word_secd:N
\__fp_parse_word_sin:N
\__fp_parse_word_sind:N
\__fp_parse_word_tan:N
\__fp_parse_word_tand:N

```

```

14967 \tl_map_inline:nn
14968 {
14969     {acos} {acsc} {asec} {asin}
14970     {cos} {cot} {csc} {sec} {sin} {tan}
14971 }
14972 {
14973     \cs_new:cpx { __fp_parse_word_#1:N }
14974     {
14975         \exp_not:N \__fp_parse_unary_function:NNN
14976         \exp_not:c { __fp_#1_o:w }
14977         \exp_not:N \use_i:nn
14978     }

```

```

14979     \cs_new:cpx { __fp_parse_word_#1d:N }
14980     {
14981         \exp_not:N \__fp_parse_unary_function:NNN
14982         \exp_not:c { __fp_#1_o:w }
14983         \exp_not:N \use_ii:nn
14984     }
14985 }

```

(End definition for `\__fp_parse_word_acos:N` and others.)

`\__fp_parse_word_acot:N`  
`\__fp_parse_word_acotd:N`  
`\__fp_parse_word_atan:N`  
`\__fp_parse_word_atand:N`

Those functions may receive a variable number of arguments.

```

14986 \cs_new:Npn \__fp_parse_word_acot:N
14987 { \__fp_parse_function:NNN \__fp_acot_o:Nw \use_i:nn }
14988 \cs_new:Npn \__fp_parse_word_acotd:N
14989 { \__fp_parse_function:NNN \__fp_acot_o:Nw \use_ii:nn }
14990 \cs_new:Npn \__fp_parse_word_atan:N
14991 { \__fp_parse_function:NNN \__fp_atan_o:Nw \use_i:nn }
14992 \cs_new:Npn \__fp_parse_word_atand:N
14993 { \__fp_parse_function:NNN \__fp_atan_o:Nw \use_ii:nn }

```

(End definition for `\__fp_parse_word_acot:N` and others.)

## 29.1 Direct trigonometric functions

The approach for all trigonometric functions (sine, cosine, tangent, cotangent, cosecant, and secant), with arguments given in radians or in degrees, is the same.

- Filter out special cases ( $\pm 0$ ,  $\pm \text{inf}$  and  $\text{NaN}$ ).
- Keep the sign for later, and work with the absolute value  $|x|$  of the argument.
- Small numbers ( $|x| < 1$  in radians,  $|x| < 10$  in degrees) are converted to fixed point numbers (and to radians if  $|x|$  is in degrees).
- For larger numbers, we need argument reduction. Subtract a multiple of  $\pi/2$  (in degrees, 90) to bring the number to the range to  $[0, \pi/2)$  (in degrees,  $[0, 90)$ ).
- Reduce further to  $[0, \pi/4]$  (in degrees,  $[0, 45]$ ) using  $\sin x = \cos(\pi/2 - x)$ , and when working in degrees, convert to radians.
- Use the appropriate power series depending on the octant  $\lfloor \frac{x}{\pi/4} \rfloor \bmod 8$  (in degrees, the same formula with  $\pi/4 \rightarrow 45$ ), the sign, and the function to compute.

### 29.1.1 Filtering special cases

`\__fp_sin_o:w`

This function, and its analogs for `cos`, `csc`, `sec`, `tan`, and `cot` instead of `sin`, are followed either by `\use_i:nn` and a float in radians or by `\use_ii:nn` and a float in degrees. The sine of  $\pm 0$  or  $\text{NaN}$  is the same float. The sine of  $\pm \infty$  raises an invalid operation exception with the appropriate function name. Otherwise, call the `trig` function to perform argument reduction and if necessary convert the reduced argument to radians. Then, `\__fp_sin_series_o:NNwww` is called to compute the Taylor series: this function receives a sign `#3`, an initial octant of 0, and the function `\__fp_ep_to_float_o:wwN` which converts the result of the series to a floating point directly rather than taking its inverse, since  $\sin(x) = \#3 \sin|x|$ .

```

14994 \cs_new:Npn \__fp_sin_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
14995 {
14996   \if_case:w #2 \exp_stop_f:
14997     \__fp_case_return_same_o:w
14998   \or: \__fp_case_use:nw
14999     {
15000       \__fp_trig:NNNNNwn #1 \__fp_sin_series_o:NNwww
15001       \__fp_ep_to_float_o:wwN #3 0
15002     }
15003   \or: \__fp_case_use:nw
15004     { \__fp_invalid_operation_o:fw { #1 { sin } { sind } } }
15005   \else: \__fp_case_return_same_o:w
15006   \fi:
15007   \s__fp \__fp_chk:w #2 #3 #4;
15008 }

```

(End definition for \\_\_fp\_sin\_o:w.)

**\\_\_fp\_cos\_o:w** The cosine of  $\pm 0$  is 1. The cosine of  $\pm\infty$  raises an invalid operation exception. The cosine of NaN is itself. Otherwise, the **trig** function reduces the argument to at most half a right-angle and converts if necessary to radians. We then call the same series as for sine, but using a positive sign 0 regardless of the sign of  $x$ , and with an initial octant of 2, because  $\cos(x) = +\sin(\pi/2 + |x|)$ .

```

15009 \cs_new:Npn \__fp_cos_o:w #1 \s__fp \__fp_chk:w #2#3; @
15010 {
15011   \if_case:w #2 \exp_stop_f:
15012     \__fp_case_return_o:Nw \c_one_fp
15013   \or: \__fp_case_use:nw
15014     {
15015       \__fp_trig:NNNNNwn #1 \__fp_sin_series_o:NNwww
15016       \__fp_ep_to_float_o:wwN 0 2
15017     }
15018   \or: \__fp_case_use:nw
15019     { \__fp_invalid_operation_o:fw { #1 { cos } { cosd } } }
15020   \else: \__fp_case_return_same_o:w
15021   \fi:
15022   \s__fp \__fp_chk:w #2 #3;
15023 }

```

(End definition for \\_\_fp\_cos\_o:w.)

**\\_\_fp\_csc\_o:w** The cosecant of  $\pm 0$  is  $\pm\infty$  with the same sign, with a division by zero exception (see **\\_\_fp\_cot\_zero\_o:Nfw** defined below), which requires the function name. The cosecant of  $\pm\infty$  raises an invalid operation exception. The cosecant of NaN is itself. Otherwise, the **trig** function performs the argument reduction, and converts if necessary to radians before calling the same series as for sine, using the sign #3, a starting octant of 0, and inverting during the conversion from the fixed point sine to the floating point result, because  $\csc(x) = \#3(\sin|x|)^{-1}$ .

```

15024 \cs_new:Npn \__fp_csc_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
15025 {
15026   \if_case:w #2 \exp_stop_f:
15027     \__fp_cot_zero_o:Nfw #3 { #1 { csc } { csd } }
15028   \or: \__fp_case_use:nw
15029     {

```

```

15030         \__fp_trig:NNNNNwn #1 \__fp_sin_series_o:NNwww
15031         \__fp_ep_inv_to_float_o:wwN #3 0
15032     }
15033 \or: \__fp_case_use:nw
15034     { \__fp_invalid_operation_o:fw { #1 { csc } { cscd } } }
15035 \else: \__fp_case_return_same_o:w
15036 \fi:
15037 \s__fp \__fp_chk:w #2 #3 #4;
15038 }

```

(End definition for \\_\_fp\_csc\_o:w.)

\\_\_fp\_sec\_o:w The secant of  $\pm 0$  is 1. The secant of  $\pm\infty$  raises an invalid operation exception. The secant of NaN is itself. Otherwise, the `trig` function reduces the argument and turns it to radians before calling the same series as for sine, using a positive sign 0, a starting octant of 2, and inverting upon conversion, because  $\sec(x) = +1/\sin(\pi/2 + |x|)$ .

```

15039 \cs_new:Npn \__fp_sec_o:w #1 \s__fp \__fp_chk:w #2#3; @
15040 {
15041     \if_case:w #2 \exp_stop_f:
15042         \__fp_case_return_o:Nw \c_one_fp
15043     \or: \__fp_case_use:nw
15044         {
15045             \__fp_trig:NNNNNwn #1 \__fp_sin_series_o:NNwww
15046             \__fp_ep_inv_to_float_o:wwN 0 2
15047         }
15048     \or: \__fp_case_use:nw
15049         { \__fp_invalid_operation_o:fw { #1 { sec } { secd } } }
15050     \else: \__fp_case_return_same_o:w
15051     \fi:
15052     \s__fp \__fp_chk:w #2 #3;
15053 }

```

(End definition for \\_\_fp\_sec\_o:w.)

\\_\_fp\_tan\_o:w The tangent of  $\pm 0$  or NaN is the same floating point number. The tangent of  $\pm\infty$  raises an invalid operation exception. Once more, the `trig` function does the argument reduction step and conversion to radians before calling `\__fp_tan_series_o:NNwww`, with a sign #3 and an initial octant of 1 (this shift is somewhat arbitrary). See `\__fp_cot_o:w` for an explanation of the 0 argument.

```

15054 \cs_new:Npn \__fp_tan_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
15055 {
15056     \if_case:w #2 \exp_stop_f:
15057         \__fp_case_return_same_o:w
15058     \or: \__fp_case_use:nw
15059         {
15060             \__fp_trig:NNNNNwn #1
15061             \__fp_tan_series_o:NNwww 0 #3 1
15062         }
15063     \or: \__fp_case_use:nw
15064         { \__fp_invalid_operation_o:fw { #1 { tan } { tand } } }
15065     \else: \__fp_case_return_same_o:w
15066     \fi:
15067     \s__fp \__fp_chk:w #2 #3 #4;
15068 }

```

(End definition for `\_fp_tan_o:w`.)

`\_fp_cot_o:w` The cotangent of  $\pm 0$  is  $\pm\infty$  with the same sign, with a division by zero exception (see `\_fp_cot_zero_o:Nfw`). The cotangent of  $\pm\infty$  raises an invalid operation exception. The cotangent of NaN is itself. We use  $\cot x = -\tan(\pi/2 + x)$ , and the initial octant for the tangent was chosen to be 1, so the octant here starts at 3. The change in sign is obtained by feeding `\_fp_tan_series_o:NNwww` two signs rather than just the sign of the argument: the first of those indicates whether we compute tangent or cotangent. Those signs are eventually combined.

```

15069 \cs_new:Npn \_fp_cot_o:w #1 \s_fp \_fp_chk:w #2#3#4; @
15070 {
15071   \if_case:w #2 \exp_stop_f:
15072     \_fp_cot_zero_o:Nfw #3 { #1 { cot } { cotd } }
15073   \or: \_fp_case_use:nw
15074     {
15075       \_fp_trig:NNNNwn #1
15076       \_fp_tan_series_o:NNwww 2 #3 3
15077     }
15078   \or: \_fp_case_use:nw
15079     { \_fp_invalid_operation_o:fw { #1 { cot } { cotd } } }
15080   \else: \_fp_case_return_same_o:w
15081   \fi:
15082   \s_fp \_fp_chk:w #2 #3 #4;
15083 }
15084 \cs_new:Npn \_fp_cot_zero_o:Nfw #1#2#3 \fi:
15085 {
15086   \fi:
15087   \token_if_eq_meaning:NNTF 0 #1
15088   { \exp_args:Nnf \_fp_division_by_zero_o:Nnw \c_inf_fp }
15089   { \exp_args:Nnf \_fp_division_by_zero_o:Nnw \c_minus_inf_fp }
15090   {#2}
15091 }

```

(End definition for `\_fp_cot_o:w` and `\_fp_cot_zero_o:Nfw`.)

### 29.1.2 Distinguishing small and large arguments

`\_fp_trig:NNNNwn` The first argument is `\use_i:nn` if the operand is in radians and `\use_ii:nn` if it is in degrees. Arguments #2 to #5 control what trigonometric function we compute, and #6 to #8 are pieces of a normal floating point number. Call the `_series` function #2, with arguments #3, either a conversion function (`\_fp_ep_to_float_o:wN` or `\_fp_ep_inv_to_float_o:wN`) or a sign 0 or 2 when computing tangent or cotangent; #4, a sign 0 or 2; the octant, computed in an integer expression starting with #5 and stopped by a period; and a fixed point number obtained from the floating point number by argument reduction (if necessary) and conversion to radians (if necessary). Any argument reduction adjusts the octant accordingly by leaving a (positive) shift into its integer expression. Let us explain the integer comparison. Two of the four `\exp_after:wN` are expanded, the expansion hits the test, which is true if the float is at least 1 when working in radians, and at least 10 when working in degrees. Then one of the remaining `\exp_after:wN` hits #1, which picks the `trig` or `trigd` function in whichever branch of the conditional was taken. The final `\exp_after:wN` closes the conditional. At the end of the day, a

number is **large** if it is  $\geq 1$  in radians or  $\geq 10$  in degrees, and **small** otherwise. All four **trig/trigd** auxiliaries receive the operand as an extended-precision number.

```

15092 \cs_new:Npn \__fp_trig:NNNNNwn #1#2#3#4#5 \s__fp \__fp_chk:w 1#6#7#8;
15093 {
15094     \exp_after:wN #2
15095     \exp_after:wN #3
15096     \exp_after:wN #4
15097     \__int_value:w \__int_eval:w #5
15098     \exp_after:wN \exp_after:wN \exp_after:wN \exp_after:wN
15099     \if_int_compare:w #7 > #1 0 1 \exp_stop_f:
15100     #1 \__fp_trig_large:ww \__fp_trigd_large:ww
15101     \else:
15102     #1 \__fp_trig_small:ww \__fp_trigd_small:ww
15103     \fi:
15104     #7,#8{0000}{0000};
15105 }
```

(End definition for \\_\_fp\_trig:NNNNNwn.)

### 29.1.3 Small arguments

**\\_\_fp\_trig\_small:ww** This receives a small extended-precision number in radians and converts it to a fixed point number. Some trailing digits may be lost in the conversion, so we keep the original floating point number around: when computing sine or tangent (or their inverses), the last step is to multiply by the floating point number (as an extended-precision number) rather than the fixed point number. The period serves to end the integer expression for the octant.

```

15106 \cs_new:Npn \__fp_trig_small:ww #1,#2;
15107 { \__fp_ep_to_fixed:wwn #1,#2; . #1,#2; }
```

(End definition for \\_\_fp\_trig\_small:ww.)

**\\_\_fp\_trigd\_small:ww** Convert the extended-precision number to radians, then call **\\_\_fp\_trig\_small:ww** to massage it in the form appropriate for the **\_series** auxiliary.

```

15108 \cs_new:Npn \__fp_trigd_small:ww #1,#2;
15109 {
15110     \__fp_ep_mul_raw:wwwN
15111     -1,{1745}{3292}{5199}{4329}{5769}{2369}; #1,#2;
15112     \__fp_trig_small:ww
15113 }
```

(End definition for \\_\_fp\_trigd\_small:ww.)

### 29.1.4 Argument reduction in degrees

**\\_\_fp\_trigd\_large:ww** Note that  $25 \times 360 = 9000$ , so  $10^{k+1} \equiv 10^k \pmod{360}$  for  $k \geq 3$ . When the exponent **#1** is very large, we can thus safely replace it by 22 (or even 19). We turn the floating point number into a fixed point number with two blocks of 8 digits followed by five blocks of 4 digits. The original float is  $100 \times \langle block_1 \rangle \cdots \langle block_3 \rangle . \langle block_4 \rangle \cdots \langle block_7 \rangle$ , or is equal to it modulo 360 if the exponent **#1** is very large. The first auxiliary finds  $\langle block_1 \rangle + \langle block_2 \rangle \pmod{9}$ , a single digit, and prepends it to the 4 digits of  $\langle block_3 \rangle$ . It also unpacks  $\langle block_4 \rangle$  and grabs the 4 digits of  $\langle block_7 \rangle$ . The second auxiliary grabs the  $\langle block_3 \rangle$  plus any contribution from the first two blocks as **#1**, the first digit of  $\langle block_4 \rangle$  (just after the

decimal point in hundreds of degrees) as #2, and the three other digits as #3. It finds the quotient and remainder of #1#2 modulo 9, adds twice the quotient to the integer expression for the octant, and places the remainder (between 0 and 8) before #3 to form a new  $\langle block_4 \rangle$ . The resulting fixed point number is  $x \in [0, 0.9]$ . If  $x \geq 0.45$ , we add 1 to the octant and feed  $0.9 - x$  with an exponent of 2 (to compensate the fact that we are working in units of hundreds of degrees rather than degrees) to `\_fp_trigd_small:ww`. Otherwise, we feed it  $x$  with an exponent of 2. The third auxiliary also discards digits which were not packed into the various  $\langle blocks \rangle$ . Since the original exponent #1 is at least 2, those are all 0 and no precision is lost (#6 and #7 are four 0 each).

```

15114 \cs_new:Npn \_fp_trigd_large:ww #1, #2#3#4#5#6#7;
15115 {
15116   \exp_after:wN \_fp_pack_eight:wNNNNNNNN
15117   \exp_after:wN \_fp_pack_eight:wNNNNNNNN
15118   \exp_after:wN \_fp_pack_twice_four:wNNNNNNNN
15119   \exp_after:wN \_fp_pack_twice_four:wNNNNNNNN
15120   \exp_after:wN \_fp_trigd_large_auxi:nnnnwNNNN
15121   \exp_after:wN ;
15122   \exp:w \exp_end_continue_f:w
15123   \prg_replicate:nn { \int_max:nn { 22 - #1 } { 0 } } { 0 }
15124   #2#3#4#5#6#7 0000 0000 0000 !
15125 }
15126 \cs_new:Npn \_fp_trigd_large_auxi:nnnnwNNNN #1#2#3#4#5; #6#7#8#9
15127 {
15128   \exp_after:wN \_fp_trigd_large_auxii:wNw
15129   \_int_value:w \_int_eval:w #1 + #2
15130   - (#1 + #2 - 4) / 9 * 9 \_int_eval_end:
15131   #3;
15132   #4; #5{#6#7#8#9};
15133 }
15134 \cs_new:Npn \_fp_trigd_large_auxii:wNw #1; #2#3;
15135 {
15136   + (#1#2 - 4) / 9 * 2
15137   \exp_after:wN \_fp_trigd_large_auxiii:www
15138   \_int_value:w \_int_eval:w #1#2
15139   - (#1#2 - 4) / 9 * 9 \_int_eval_end: #3 ;
15140 }
15141 \cs_new:Npn \_fp_trigd_large_auxiii:www #1; #2; #3!
15142 {
15143   \if_int_compare:w #1 < 4500 \exp_stop_f:
15144     \exp_after:wN \_fp_use_i_until_s:nw
15145     \exp_after:wN \_fp_fixed_continue:wn
15146   \else:
15147     + 1
15148   \fi:
15149   \_fp_fixed_sub:wnn {9000}{0000}{0000}{0000}{0000}{0000};
15150   {#1}#2{0000}{0000};
15151   { \_fp_trigd_small:ww 2, }
15152 }

```

(End definition for `\_fp_trigd_large:ww` and others.)



### 29.1.5 Argument reduction in radians

Arguments greater or equal to 1 need to be reduced to a range where we only need a few terms of the Taylor series. We reduce to the range  $[0, 2\pi]$  by subtracting multiples of  $2\pi$ , then to the smaller range  $[0, \pi/2]$  by subtracting multiples of  $\pi/2$  (keeping track of how many times  $\pi/2$  is subtracted), then to  $[0, \pi/4]$  by mapping  $x \rightarrow \pi/2 - x$  if appropriate. When the argument is very large, say,  $10^{100}$ , an equally large multiple of  $2\pi$  must be subtracted, hence we must work with a very good approximation of  $2\pi$  in order to get a sensible remainder modulo  $2\pi$ .

Specifically, we multiply the argument by an approximation of  $1/(2\pi)$  with 10048 digits, then discard the integer part of the result, keeping 52 digits of the fractional part. From the fractional part of  $x/(2\pi)$  we deduce the octant (quotient of the first three digits by 125). We then multiply by 8 or  $-8$  (the latter when the octant is odd), ignore any integer part (related to the octant), and convert the fractional part to an extended precision number, before multiplying by  $\pi/4$  to convert back to a value in radians in  $[0, \pi/4]$ .

It is possible to prove that given the precision of floating points and their range of exponents, the 52 digits may start at most with 24 zeros. The 5 last digits are affected by carries from computations which are not done, hence we are left with at least  $52 - 24 - 5 = 23$  significant digits, enough to round correctly up to  $0.6 \cdot \text{ulp}$  in all cases.

`\_fp_trig_inverse_two_pi:` This macro expands to `,,!` or `,!` followed by 10112 decimals of  $10^{-16}/(2\pi)$ . The number of decimals we really need is the maximum exponent plus the number of digits we later need, 52, plus 12 (4 – 1 groups of 4 digits). We store the decimals as a control sequence name, and convert it to a token list when required: strings take up less memory than their token list representation.

```

15153 \cs_new:Npx \_fp_trig_inverse_two_pi:
15154 {
15155     \exp_not:n { \exp_after:wN \use_none:n \token_to_str:N }
15156     \cs:w , , !
15157     0000000000000000159154943091895335768883763372514362034459645740 ~
15158     4564487476673440588967976342265350901138027662530859560728427267 ~
15159     5795803689291184611457865287796741073169983922923996693740907757 ~
15160     3077746396925307688717392896217397661693362390241723629011832380 ~
15161     1142226997557159404618900869026739561204894109369378440855287230 ~
15162     9994644340024867234773945961089832309678307490616698646280469944 ~
15163     8652187881574786566964241038995874139348609983868099199962442875 ~
15164     5851711788584311175187671605465475369880097394603647593337680593 ~
15165     0249449663530532715677550322032477781639716602294674811959816584 ~
15166     0606016803035998133911987498832786654435279755070016240677564388 ~
15167     8495713108801221993761476813777647378906330680464579784817613124 ~
15168     2731406996077502450029775985708905690279678513152521001631774602 ~
15169     0924811606240561456203146484089248459191435211575407556200871526 ~
15170     6068022171591407574745827225977462853998751553293908139817724093 ~
15171     5825479707332871904069997590765770784934703935898280871734256403 ~
15172     6689511662545705943327631268650026122717971153211259950438667945 ~
15173     0376255608363171169525975812822494162333431451061235368785631136 ~
15174     3669216714206974696012925057833605311960859450983955671870995474 ~
15175     6510431623815517580839442979970999505254387566129445883306846050 ~
15176     7852915151410404892988506388160776196993073410389995786918905980 ~
15177     9373777206187543222718930136625526123878038753888110681406765434 ~
15178     0828278526933426799556070790386060352738996245125995749276297023 ~

```

15179 5940955843011648296411855777124057544494570217897697924094903272 ~  
15180 9477021664960356531815354400384068987471769158876319096650696440 ~  
15181 4776970687683656778104779795450353395758301881838687937766124814 ~  
15182 9530599655802190835987510351271290432315804987196868777594656634 ~  
15183 6221034204440855497850379273869429353661937782928735937843470323 ~  
15184 0237145837923557118636341929460183182291964165008783079331353497 ~  
15185 7909974586492902674506098936890945883050337030538054731232158094 ~  
15186 3197676032283131418980974982243833517435698984750103950068388003 ~  
15187 9786723599608024002739010874954854787923568261139948903268997427 ~  
15188 0834961149208289037767847430355045684560836714793084567233270354 ~  
15189 8539255620208683932409956221175331839402097079357077496549880868 ~  
15190 6066360968661967037474542102831219251846224834991161149566556037 ~  
15191 9696761399312829960776082779901007830360023382729879085402387615 ~  
15192 5744543092601191005433799838904654921248295160707285300522721023 ~  
15193 6017523313173179759311050328155109373913639645305792607180083617 ~  
15194 9548767246459804739772924481092009371257869183328958862839904358 ~  
15195 6866663975673445140950363732719174311388066383072592302759734506 ~  
15196 0548212778037065337783032170987734966568490800326988506741791464 ~  
15197 6835082816168533143361607309951498531198197337584442098416559541 ~  
15198 5225064339431286444038388356150879771645017064706751877456059160 ~  
15199 8716857857939226234756331711132998655941596890719850688744230057 ~  
15200 5191977056900382183925622033874235362568083541565172971088117217 ~  
15201 9593683256488518749974870855311659830610139214454460161488452770 ~  
15202 2511411070248521739745103866736403872860099674893173561812071174 ~  
15203 0478899368886556923078485023057057144063638632023685201074100574 ~  
15204 8592281115721968003978247595300166958522123034641877365043546764 ~  
15205 6456565971901123084767099309708591283646669191776938791433315566 ~  
15206 5066981321641521008957117286238426070678451760111345080069947684 ~  
15207 2235698962488051577598095339708085475059753626564903439445420581 ~  
15208 7886435683042000315095594743439252544850674914290864751442303321 ~  
15209 3324569511634945677539394240360905438335528292434220349484366151 ~  
15210 466322860247766660495314065734357553014090827988091478669343492 ~  
15211 2737602634997829957018161964321233140475762897484082891174097478 ~  
15212 2637899181699939487497715198981872666294601830539583275209236350 ~  
15213 6853889228468247259972528300766856937583659722919824429747406163 ~  
15214 8183113958306744348516928597383237392662402434501997809940402189 ~  
15215 6134834273613676449913827154166063424829363741850612261086132119 ~  
15216 9863346284709941839942742955915628333990480382117501161211667205 ~  
15217 1912579303552929241134403116134112495318385926958490443846807849 ~  
15218 0973982808855297045153053991400988698840883654836652224668624087 ~  
15219 2540140400911787421220452307533473972538149403884190586842311594 ~  
15220 6322744339066125162393106283195323883392131534556381511752035108 ~  
15221 7459558201123754359768155340187407394340363397803881721004531691 ~  
15222 8295194879591767395417787924352761740724605939160273228287946819 ~  
15223 3649128949714953432552723591659298072479985806126900733218844526 ~  
15224 7943350455801952492566306204876616134365339920287545208555344144 ~  
15225 0990512982727454659118132223284051166615650709837557433729548631 ~  
15226 2041121716380915606161165732000083306114606181280326258695951602 ~  
15227 4632166138576614804719932707771316441201594960110632830520759583 ~  
15228 4850305079095584982982186740289838551383239570208076397550429225 ~  
15229 9847647071016426974384504309165864528360324933604354657237557916 ~  
15230 1366324120457809969715663402215880545794313282780055246132088901 ~  
15231 8742121092448910410052154968097113720754005710963406643135745439 ~  
15232 9159769435788920793425617783022237011486424925239248728713132021 ~

15233 7667360756645598272609574156602343787436291321097485897150713073 ~  
15234 9104072643541417970572226547980381512759579124002534468048220261 ~  
15235 7342299001020483062463033796474678190501811830375153802879523433 ~  
15236 4195502135689770912905614317878792086205744999257897569018492103 ~  
15237 2420647138519113881475640209760554895793785141404145305151583964 ~  
15238 2823265406020603311891586570272086250269916393751527887360608114 ~  
15239 5569484210322407772727421651364234366992716340309405307480652685 ~  
15240 0930165892136921414312937134106157153714062039784761842650297807 ~  
15241 8606266969960809184223476335047746719017450451446166382846208240 ~  
15242 8673595102371302904443779408535034454426334130626307459513830310 ~  
15243 2293146934466832851766328241515210179422644395718121717021756492 ~  
15244 196444939653222187658488244511909401340504432139858628621083179 ~  
15245 3939608443898019147873897723310286310131486955212620518278063494 ~  
15246 5711866277825659883100535155231665984394090221806314454521212978 ~  
15247 9734471488741258268223860236027109981191520568823472398358013366 ~  
15248 0683786328867928619732367253606685216856320119489780733958419190 ~  
15249 6659583867852941241871821727987506103946064819585745620060892122 ~  
15250 8416394373846549589932028481236433466119707324309545859073361878 ~  
15251 6290631850165106267576851216357588696307451999220010776676830946 ~  
15252 9814975622682434793671310841210219520899481912444048751171059184 ~  
15253 4139907889455775184621619041530934543802808938628073237578615267 ~  
15254 7971143323241969857805637630180884386640607175368321362629671224 ~  
15255 2609428540110963218262765120117022552929289655594608204938409069 ~  
15256 0760692003954646191640021567336017909631872891998634341086903200 ~  
15257 5796637103128612356988817640364252540837098108148351903121318624 ~  
15258 7228181050845123690190646632235938872454630737272808789830041018 ~  
15259 9485913673742589418124056729191238003306344998219631580386381054 ~  
15260 2457893450084553280313511884341007373060595654437362488771292628 ~  
15261 9807423539074061786905784443105274262641767830058221486462289361 ~  
15262 9296692992033046693328438158053564864073184440599549689353773183 ~  
15263 6726613130108623588021288043289344562140479789454233736058506327 ~  
15264 0439981932635916687341943656783901281912202816229500333012236091 ~  
15265 8587559201959081224153679499095448881099758919890811581163538891 ~  
15266 6339402923722049848375224236209100834097566791710084167957022331 ~  
15267 7897107102928884897013099533995424415335060625843921452433864640 ~  
15268 3432440657317477553405404481006177612569084746461432976543900008 ~  
15269 3826521145210162366431119798731902751191441213616962045693602633 ~  
15270 6102355962140467029012156796418735746835873172331004745963339773 ~  
15271 2477044918885134415363760091537564267438450166221393719306748706 ~  
15272 2881595464819775192207710236743289062690709117919412776212245117 ~  
15273 2354677115640433357720616661564674474627305622913332030953340551 ~  
15274 3841718194605321501426328000879551813296754972846701883657425342 ~  
15275 5016994231069156343106626043412205213831587971115075454063290657 ~  
15276 0248488648697402872037259869281149360627403842332874942332178578 ~  
15277 7750735571857043787379693402336902911446961448649769719434527467 ~  
15278 4429603089437192540526658890710662062575509930379976658367936112 ~  
15279 8137451104971506153783743579555867972129358764463093757203221320 ~  
15280 2460565661129971310275869112846043251843432691552928458573495971 ~  
15281 5042565399302112184947232132380516549802909919676815118022483192 ~  
15282 5127372199792134331067642187484426215985121676396779352982985195 ~  
15283 8545392106957880586853123277545433229161989053189053725391582222 ~  
15284 923259727813342781825606488233760719681014481453198336237910767 ~  
15285 1255017528826351836492103572587410356573894694875444694018175923 ~  
15286 0609370828146501857425324969212764624247832210765473750568198834 ~

```

15287 5641035458027261252285503154325039591848918982630498759115406321 ~
15288 0354263890012837426155187877318375862355175378506956599570028011 ~
15289 5841258870150030170259167463020842412449128392380525772514737141 ~
15290 2310230172563968305553583262840383638157686828464330456805994018 ~
15291 7001071952092970177990583216417579868116586547147748964716547948 ~
15292 8312140431836079844314055731179349677763739898930227765607058530 ~
15293 4083747752640947435070395214524701683884070908706147194437225650 ~
15294 2823145872995869738316897126851939042297110721350756978037262545 ~
15295 8141095038270388987364516284820180468288205829135339013835649144 ~
15296 3004015706509887926715417450706686888783438055583501196745862340 ~
15297 8059532724727843829259395771584036885940989939255241688378793572 ~
15298 7967951654076673927031256418760962190243046993485989199060012977 ~
15299 7469214532970421677817261517850653008552559997940209969455431545 ~
15300 2745856704403686680428648404512881182309793496962721836492935516 ~
15301 2029872469583299481932978335803459023227052612542114437084359584 ~
15302 944338363838317751841160881711251279233374577219339820819005406 ~
15303 3292937775306906607415304997682647124407768817248673421685881509 ~
15304 9133422075930947173855159340808957124410634720893194912880783576 ~
15305 3115829400549708918023366596077070927599010527028150868897828549 ~
15306 4340372642729262103487013992868853550062061514343078665396085995 ~
15307 0058714939141652065302070085265624074703660736605333805263766757 ~
15308 2018839497277047222153633851135483463624619855425993871933367482 ~
15309 0422097449956672702505446423243957506869591330193746919142980999 ~
15310 3424230550172665212092414559625960554427590951996824313084279693 ~
15311 7113207021049823238195747175985519501864630940297594363194450091 ~
15312 9150616049228764323192129703446093584259267276386814363309856853 ~
15313 2786024332141052330760658841495858718197071242995959226781172796 ~
15314 4438853796763139274314227953114500064922126500133268623021550837
15315 \cs_end:
15316 }

```

(End definition for `\_fp_trig_inverse_two_pi:`.)

`\_fp_trig_large:ww` The exponent #1 is between 1 and 10000. We discard the integer part of  $10^{\#1-16}/(2\pi)$ , that is, the first #1 digits of  $10^{-16}/(2\pi)$ , because it yields an integer contribution to  $x/(2\pi)$ . The `auxii` auxiliary discards 64 digits at a time thanks to spaces inserted in the result of `\_fp_trig_inverse_two_pi:`, while `auxiii` discards 8 digits at a time, and `auxiv` discards digits one at a time. Then 64 digits are packed into groups of 4 and the `auxv` auxiliary is called.

```

15317 \cs_new:Npn \_fp_trig_large:ww #1, #2#3#4#5#6;
15318 {
15319   \exp_after:wN \_fp_trig_large_auxi:wwwww
15320   \__int_value:w \__int_eval:w (#1 - 32) / 64 \exp_after:wN ,
15321   \__int_value:w \__int_eval:w (#1 - 4) / 8 \exp_after:wN ,
15322   \__int_value:w #1 \_fp_trig_inverse_two_pi: ;
15323   {#2}{#3}{#4}{#5} ;
15324 }
15325 \cs_new:Npn \_fp_trig_large_auxi:wwwww #1, #2, #3, #4!
15326 {
15327   \prg_replicate:nn {#1} { \_fp_trig_large_auxii:ww }
15328   \prg_replicate:nn { #2 - #1 * 8 }
15329   { \_fp_trig_large_auxiii:wwnnnnnnnn }
15330   \prg_replicate:nn { #3 - #2 * 8 }
15331   { \_fp_trig_large_auxiv:wN }

```

```

15332 \prg_replicate:nn { 8 } { \__fp_pack_twice_four:wNNNNNNNN }
15333 \__fp_trig_large_auxv:www
15334 ;
15335 }
15336 \cs_new:Npn \__fp_trig_large_auxii:ww #1; #2 ~ { #1; }
15337 \cs_new:Npn \__fp_trig_large_auxiii:wNNNNNNNN
15338 #1; #2#3#4#5#6#7#8#9 { #1; }
15339 \cs_new:Npn \__fp_trig_large_auxiv:wN #1; #2 { #1; }

```

(End definition for \\_\_fp\_trig\_large:ww and others.)

```

\__fp_trig_large_auxv:www
\__fp_trig_large_auxvi:wNNNNNNNN
\__fp_trig_large_pack:NNNNNw

```

First come the first 64 digits of the fractional part of  $10^{1-16}/(2\pi)$ , arranged in 16 blocks of 4, and ending with a semicolon. Then some more digits of the same fractional part, ending with a semicolon, then 4 blocks of 4 digits holding the significand of the original argument. Multiply the 16-digit significand with the 64-digit fractional part: the `auxvi` auxiliary receives the significand as `#2#3#4#5` and 16 digits of the fractional part as `#6#7#8#9`, and computes one step of the usual ladder of `pack` functions we use for multiplication (see *e.g.*, `\__fp_fixed_mul:wwn`), then discards one block of the fractional part to set things up for the next step of the ladder. We perform 13 such steps, replacing the last `middle` shift by the appropriate `trailing` shift, then discard the significand and remaining 3 blocks from the fractional part, as there are not enough digits to compute any more step in the ladder. The last semicolon closes the ladder, and we return control to the `auxvii` auxiliary.

```

15340 \cs_new:Npn \__fp_trig_large_auxv:www #1; #2; #3;
15341 {
15342   \exp_after:wN \__fp_use_i_until_s:nw
15343   \exp_after:wN \__fp_trig_large_auxvii:w
15344   \__int_value:w \__int_eval:w \c__fp_leading_shift_int
15345   \prg_replicate:nn { 13 }
15346   { \__fp_trig_large_auxvi:wNNNNNNNN }
15347   + \c__fp_trailing_shift_int - \c__fp_middle_shift_int
15348   \__fp_use_i_until_s:nw
15349   ; #3 #1 ; ;
15350 }
15351 \cs_new:Npn \__fp_trig_large_auxvi:wNNNNNNNN #1; #2#3#4#5#6#7#8#9
15352 {
15353   \exp_after:wN \__fp_trig_large_pack:NNNNNw
15354   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
15355   + #2*#9 + #3*#8 + #4*#7 + #5*#6
15356   #1; {#2}{#3}{#4}{#5} {#7}{#8}{#9}
15357 }
15358 \cs_new:Npn \__fp_trig_large_pack:NNNNNw #1#2#3#4#5#6;
15359 { + #1#2#3#4#5 ; #6 }

```

(End definition for \\_\_fp\_trig\_large\_auxv:www, \\_\_fp\_trig\_large\_auxvi:wNNNNNNNN, and \\_\_fp\_trig\_large\_pack:NNNNNw.)

```

\__fp_trig_large_auxvii:w
\__fp_trig_large_auxviii:w
\__fp_trig_large_auxix:Nw
\__fp_trig_large_auxx:wNNNNN
\__fp_trig_large_auxxi:w

```

The `auxvii` auxiliary is followed by 52 digits and a semicolon. We find the octant as the integer part of 8 times what follows, or equivalently as the integer part of `#1#2#3/125`, and add it to the surrounding integer expression for the octant. We then compute 8 times the 52-digit number, with a minus sign if the octant is odd. Again, the last `middle` shift is converted to a `trailing` shift. Any integer part (including negative values which come up when the octant is odd) is discarded by `\__fp_use_i_until_s:nw`. The resulting

fractional part should then be converted to radians by multiplying by  $2\pi/8$ , but first, build an extended precision number by abusing `\__fp_ep_to_ep_loop:N` with the appropriate trailing markers. Finally, `\__fp_trig_small:ww` sets up the argument for the functions which compute the Taylor series.

```

15360 \cs_new:Npn \__fp_trig_large_auxvii:w #1#2#3
15361 {
15362   \exp_after:wN \__fp_trig_large_auxviii:ww
15363   \__int_value:w \__int_eval:w (#1#2#3 - 62) / 125 ;
15364   #1#2#3
15365 }
15366 \cs_new:Npn \__fp_trig_large_auxviii:ww #1;
15367 {
15368   + #1
15369   \if_int_odd:w #1 \exp_stop_f:
15370     \exp_after:wN \__fp_trig_large_auxix:Nw
15371     \exp_after:wN -
15372   \else:
15373     \exp_after:wN \__fp_trig_large_auxix:Nw
15374     \exp_after:wN +
15375   \fi:
15376 }
15377 \cs_new:Npn \__fp_trig_large_auxix:Nw
15378 {
15379   \exp_after:wN \__fp_use_i_until_s:nw
15380   \exp_after:wN \__fp_trig_large_auxxi:w
15381   \__int_value:w \__int_eval:w \c__fp_leading_shift_int
15382   \prg_replicate:nn { 13 }
15383   { \__fp_trig_large_auxx:wNNNNN }
15384   + \c__fp_trailing_shift_int - \c__fp_middle_shift_int
15385   ;
15386 }
15387 \cs_new:Npn \__fp_trig_large_auxx:wNNNNN #1; #2 #3#4#5#6
15388 {
15389   \exp_after:wN \__fp_trig_large_pack:NNNNNw
15390   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
15391   #2 8 * #3#4#5#6
15392   #1; #2
15393 }
15394 \cs_new:Npn \__fp_trig_large_auxxi:w #1;
15395 {
15396   \exp_after:wN \__fp_ep_mul_raw:wwwN
15397   \__int_value:w \__int_eval:w 0 \__fp_ep_to_ep_loop:N #1 ; ; !
15398   0,{7853}{9816}{3397}{4483}{0961}{5661};
15399   \__fp_trig_small:ww
15400 }

```

(End definition for `\__fp_trig_large_auxvii:w` and others.)

### 29.1.6 Computing the power series

`\__fp_sin_series_o:NNwww` Here we receive a conversion function `\__fp_ep_to_float_o:wwN` or `\__fp_ep_inv_to_float_o:wwN`, a *sign* (0 or 2), a (non-negative) *octant* delimited by a dot, a *fixed point* number delimited by a semicolon, and an extended-precision number. The auxiliary receives:

- the conversion function #1;
- the final sign, which depends on the octant #3 and the sign #2;
- the octant #3, which controls the series we use;
- the square #4 \* #4 of the argument as a fixed point number, computed with `\__fp_fixed_mul:wnn`;
- the number itself as an extended-precision number.

If the octant is in  $\{1, 2, 5, 6, \dots\}$ , we are near an extremum of the function and we use the series

$$\cos(x) = 1 - x^2 \left( \frac{1}{2!} - x^2 \left( \frac{1}{4!} - x^2 \left( \dots \right) \right) \right).$$

Otherwise, the series

$$\sin(x) = x \left( 1 - x^2 \left( \frac{1}{3!} - x^2 \left( \frac{1}{5!} - x^2 \left( \dots \right) \right) \right) \right)$$

is used. Finally, the extended-precision number is converted to a floating point number with the given sign, and `\__fp_sanitizew` checks for overflow and underflow.

```

15401 \cs_new:Npn \__fp_sin_series_o:NNwww #1#2#3. #4;
15402 {
15403   \__fp_fixed_mul:wnn #4; #4;
15404   {
15405     \exp_after:wN \__fp_sin_series_aux_o:NNwww
15406     \exp_after:wN #1
15407     \__int_value:w
15408     \if_int_odd:w \__int_eval:w (#3 + 2) / 4 \__int_eval_end:
15409       #2
15410     \else:
15411       \if_meaning:w #2 0 2 \else: 0 \fi:
15412     \fi:
15413     {#3}
15414   }
15415 }
15416 \cs_new:Npn \__fp_sin_series_aux_o:NNwww #1#2#3 #4; #5,#6;
15417 {
15418   \if_int_odd:w \__int_eval:w #3 / 2 \__int_eval_end:
15419     \exp_after:wN \use_i:nn
15420   \else:
15421     \exp_after:wN \use_ii:nn
15422   \fi:
15423   { % 1/18!
15424     \__fp_fixed_mul_sub_back:wwwn {0000}{0000}{0000}{0001}{5619}{2070};
15425     #4;{0000}{0000}{0000}{0477}{9477}{3324};
15426     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0000}{0011}{4707}{4559}{7730};
15427     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0000}{2087}{6756}{9878}{6810};
15428     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0027}{5573}{1922}{3985}{8907};
15429     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{2480}{1587}{3015}{8730}{1587};
15430     \__fp_fixed_mul_sub_back:wwwn #4;{0013}{8888}{8888}{8888}{8888}{8889};
15431     \__fp_fixed_mul_sub_back:wwwn #4;{0416}{6666}{6666}{6666}{6666}{6667};
15432     \__fp_fixed_mul_sub_back:wwwn #4;{5000}{0000}{0000}{0000}{0000}{0000};

```

```

15433     \__fp_fixed_mul_sub_back:wwwn#4;{10000}{0000}{0000}{0000}{0000}{0000};
15434     { \__fp_fixed_continue:wn 0, }
15435 }
15436 { % 1/17!
15437     \__fp_fixed_mul_sub_back:wwwn {0000}{0000}{0000}{0028}{1145}{7254};
15438     #4;{0000}{0000}{0000}{7647}{1637}{3182};
15439     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0000}{0160}{5904}{3836}{8216};
15440     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0002}{5052}{1083}{8544}{1719};
15441     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0275}{5731}{9223}{9858}{9065};
15442     \__fp_fixed_mul_sub_back:wwwn #4;{0001}{9841}{2698}{4126}{9841}{2698};
15443     \__fp_fixed_mul_sub_back:wwwn #4;{0083}{3333}{3333}{3333}{3333}{3333};
15444     \__fp_fixed_mul_sub_back:wwwn #4;{1666}{6666}{6666}{6666}{6666}{6667};
15445     \__fp_fixed_mul_sub_back:wwwn#4;{10000}{0000}{0000}{0000}{0000}{0000};
15446     { \__fp_ep_mul:wwwn 0, } #5,#6;
15447 }
15448 {
15449     \exp_after:wN \__fp_sanitize:Nw
15450     \exp_after:wN #2
15451     \__int_value:w \__int_eval:w #1
15452 }
15453 #2
15454 }

```

(End definition for \\_\_fp\_sin\_series\_o:NNwww and \\_\_fp\_sin\_series\_aux\_o:NNwww.)

\\_\_fp\_tan\_series\_o:NNwww  
\\_\_fp\_tan\_series\_aux\_o:Nnwww

Contrarily to \\_\_fp\_sin\_series\_o:NNwww which received a conversion auxiliary as #1, here, #1 is 0 for tangent and 2 for cotangent. Consider first the case of the tangent. The octant #3 starts at 1, which means that it is 1 or 2 for  $|x| \in [0, \pi/2]$ , it is 3 or 4 for  $|x| \in [\pi/2, \pi]$ , and so on: the intervals on which  $\tan|x| \geq 0$  coincide with those for which  $\lfloor (\#3 + 1)/2 \rfloor$  is odd. We also have to take into account the original sign of  $x$  to get the sign of the final result; it is straightforward to check that the first \\_\_int\_value:w expansion produces 0 for a positive final result, and 2 otherwise. A similar story holds for  $\cot(x)$ .

The auxiliary receives the sign, the octant, the square of the (reduced) input, and the (reduced) input (an extended-precision number) as arguments. It then computes the numerator and denominator of

$$\tan(x) \simeq \frac{x(1 - x^2(a_1 - x^2(a_2 - x^2(a_3 - x^2(a_4 - x^2a_5))))))}{1 - x^2(b_1 - x^2(b_2 - x^2(b_3 - x^2(b_4 - x^2b_5)))}.$$

The ratio is computed by \\_\_fp\_ep\_div:wwwn, then converted to a floating point number. For octants #3 (really, quadrants) next to a pole of the functions, the fixed point numerator and denominator are exchanged before computing the ratio. Note that this \if\_int\_odd:w test relies on the fact that the octant is at least 1.

```

15455 \cs_new:Npn \__fp_tan_series_o:NNwww #1#2#3. #4;
15456 {
15457     \__fp_fixed_mul:wn #4; #4;
15458     {
15459         \exp_after:wN \__fp_tan_series_aux_o:Nnwww
15460         \__int_value:w
15461         \if_int_odd:w \__int_eval:w #3 / 2 \__int_eval_end:
15462         \exp_after:wN \reverse_if:N
15463         \fi:

```



```

15464     \if_meaning:w #1#2 2 \else: 0 \fi:
15465     {#3}
15466   }
15467 }
15468 \cs_new:Npn \__fp_tan_series_aux_o:Nnwww #1 #2 #3; #4,#5;
15469 {
15470   \__fp_fixed_mul_sub_back:wwwn {0000}{0000}{1527}{3493}{0856}{7059};
15471   #3; {0000}{0159}{6080}{0274}{5257}{6472};
15472   \__fp_fixed_mul_sub_back:wwwn #3; {0002}{4571}{2320}{0157}{2558}{8481};
15473   \__fp_fixed_mul_sub_back:wwwn #3; {0115}{5830}{7533}{5397}{3168}{2147};
15474   \__fp_fixed_mul_sub_back:wwwn #3; {1929}{8245}{6140}{3508}{7719}{2982};
15475   \__fp_fixed_mul_sub_back:wwwn #3; {10000}{0000}{0000}{0000}{0000}{0000};
15476   { \__fp_ep_mul:wwwn 0, } #4,#5;
15477   {
15478     \__fp_fixed_mul_sub_back:wwwn {0000}{0007}{0258}{0681}{9408}{4706};
15479     #3; {0000}{2343}{7175}{1399}{6151}{7670};
15480     \__fp_fixed_mul_sub_back:wwwn #3; {0019}{2638}{4588}{9232}{8861}{3691};
15481     \__fp_fixed_mul_sub_back:wwwn #3; {0536}{6357}{0691}{4344}{6852}{4252};
15482     \__fp_fixed_mul_sub_back:wwwn #3; {5263}{1578}{9473}{6842}{1052}{6315};
15483     \__fp_fixed_mul_sub_back:wwwn #3; {10000}{0000}{0000}{0000}{0000}{0000};
15484     {
15485       \reverse_if:N \if_int_odd:w
15486       \__int_eval:w (#2 - 1) / 2 \__int_eval_end:
15487       \exp_after:wN \__fp_reverse_args:Nww
15488       \fi:
15489       \__fp_ep_div:wwwn 0,
15490     }
15491   }
15492   {
15493     \exp_after:wN \__fp_sanitize:Nw
15494     \exp_after:wN #1
15495     \__int_value:w \__int_eval:w \__fp_ep_to_float_o:wwN
15496   }
15497   #1
15498 }

```

(End definition for `\__fp_tan_series_o:NNwww` and `\__fp_tan_series_aux_o:Nnwww`.)

## 29.2 Inverse trigonometric functions

All inverse trigonometric functions (arcsine, arccosine, arctangent, arccotangent, arcsecant, and arcsecant) are based on a function often denoted `atan2`. This function is accessed directly by feeding two arguments to arctangent, and is defined by  $\text{atan}(y, x) = \text{atan}(y/x)$  for generic  $y$  and  $x$ . Its advantages over the conventional arctangent is that it takes values in  $[-\pi, \pi]$  rather than  $[-\pi/2, \pi/2]$ , and that it is better behaved in boundary cases. Other inverse trigonometric functions are expressed in terms

of atan as

$$\operatorname{acos} x = \operatorname{atan}(\sqrt{1-x^2}, x) \quad (5)$$

$$\operatorname{asin} x = \operatorname{atan}(x, \sqrt{1-x^2}) \quad (6)$$

$$\operatorname{asec} x = \operatorname{atan}(\sqrt{x^2-1}, 1) \quad (7)$$

$$\operatorname{acsc} x = \operatorname{atan}(1, \sqrt{x^2-1}) \quad (8)$$

$$\operatorname{atan} x = \operatorname{atan}(x, 1) \quad (9)$$

$$\operatorname{acot} x = \operatorname{atan}(1, x). \quad (10)$$

Rather than introducing a new function, **atan2**, the arctangent function **atan** is overloaded: it can take one or two arguments. In the comments below, following many texts, we call the first argument  $y$  and the second  $x$ , because  $\operatorname{atan}(y, x) = \operatorname{atan}(y/x)$  is the angular coordinate of the point  $(x, y)$ .

As for direct trigonometric functions, the first step in computing  $\operatorname{atan}(y, x)$  is argument reduction. The sign of  $y$  gives that of the result. We distinguish eight regions where the point  $(x, |y|)$  can lie, of angular size roughly  $\pi/8$ , characterized by their “octant”, between 0 and 7 included. In each region, we compute an arctangent as a Taylor series, then shift this arctangent by the appropriate multiple of  $\pi/4$  and sign to get the result. Here is a list of octants, and how we compute the arctangent (we assume  $y > 0$ ; otherwise replace  $y$  by  $-y$  below):

0  $0 < |y| < 0.41421x$ , then  $\operatorname{atan} \frac{|y|}{x}$  is given by a nicely convergent Taylor series;

1  $0 < 0.41421x < |y| < x$ , then  $\operatorname{atan} \frac{|y|}{x} = \frac{\pi}{4} - \operatorname{atan} \frac{x-|y|}{x+|y|}$ ;

2  $0 < 0.41421|y| < x < |y|$ , then  $\operatorname{atan} \frac{|y|}{x} = \frac{\pi}{4} + \operatorname{atan} \frac{-x+|y|}{x+|y|}$ ;

3  $0 < x < 0.41421|y|$ , then  $\operatorname{atan} \frac{|y|}{x} = \frac{\pi}{2} - \operatorname{atan} \frac{x}{|y|}$ ;

4  $0 < -x < 0.41421|y|$ , then  $\operatorname{atan} \frac{|y|}{x} = \frac{\pi}{2} + \operatorname{atan} \frac{-x}{|y|}$ ;

5  $0 < 0.41421|y| < -x < |y|$ , then  $\operatorname{atan} \frac{|y|}{x} = \frac{3\pi}{4} - \operatorname{atan} \frac{x+|y|}{-x+|y|}$ ;

6  $0 < -0.41421x < |y| < -x$ , then  $\operatorname{atan} \frac{|y|}{x} = \frac{3\pi}{4} + \operatorname{atan} \frac{-x-|y|}{-x+|y|}$ ;

7  $0 < |y| < -0.41421x$ , then  $\operatorname{atan} \frac{|y|}{x} = \pi - \operatorname{atan} \frac{|y|}{-x}$ .

In the following, we denote by  $z$  the ratio among  $|\frac{y}{x}|$ ,  $|\frac{x}{y}|$ ,  $|\frac{x+y}{x-y}|$ ,  $|\frac{x-y}{x+y}|$  which appears in the right-hand side above.

### 29.2.1 Arctangent and arccotangent

`\__fp_atan_o:Nw`

`\__fp_acot_o:Nw`

`\__fp_atan_dispatch_o:NNnNw`

The parsing step manipulates **atan** and **acot** like **min** and **max**, reading in an array of operands, but also leaves `\use_i:nn` or `\use_ii:nn` depending on whether the result should be given in radians or in degrees. Here, we dispatch according to the number of arguments. The one-argument versions of arctangent and arccotangent are special cases of the two-argument ones:  $\operatorname{atan}(y) = \operatorname{atan}(y, 1) = \operatorname{acot}(1, y)$  and  $\operatorname{acot}(x) = \operatorname{atan}(1, x) = \operatorname{atan}(x, 1)$ .

15499 `\cs_new:Npn \__fp_atan_o:Nw`

```

15500 {
15501     \__fp_atan_dispatch_o:NNnNw
15502     \__fp_acotii_o:Nww \__fp_atanii_o:Nww { atan }
15503 }
15504 \cs_new:Npn \__fp_acot_o:Nw
15505 {
15506     \__fp_atan_dispatch_o:NNnNw
15507     \__fp_atanii_o:Nww \__fp_acotii_o:Nww { acot }
15508 }
15509 \cs_new:Npn \__fp_atan_dispatch_o:NNnNw #1#2#3#4#5@
15510 {
15511     \if_case:w
15512         \__int_eval:w \__fp_array_count:n {#5} - 1 \__int_eval_end:
15513         \exp_after:wN #1 \exp_after:wN #4 \c_one_fp #5
15514         \exp:w
15515     \or: #2 #4 #5 \exp:w
15516     \else:
15517         \msg_kernel_expandable_error:nnnnn
15518         { kernel } { fp-num-args } { #3() } { 1 } { 2 }
15519         \exp_after:wN \c_nan_fp \exp:w
15520     \fi:
15521     \exp_after:wN \exp_end:
15522 }

```

(End definition for \\_\_fp\_atan\_o:Nw, \\_\_fp\_acot\_o:Nw, and \\_\_fp\_atan\_dispatch\_o:NNnNw.)

\\_\_fp\_atanii\_o:Nww If either operand is nan, we return it. If both are normal, we call \\_\_fp\_atan\_normal\_o:NNnwNnw. If both are zero or both infinity, we call \\_\_fp\_atan\_inf\_o:NNNw with argument 2, leading to a result among  $\{\pm\pi/4, \pm3\pi/4\}$  (in degrees,  $\{\pm45, \pm135\}$ ). Otherwise, one is much bigger than the other, and we call \\_\_fp\_atan\_inf\_o:NNNw with either an argument of 4, leading to the values  $\pm\pi/2$  (in degrees,  $\pm90$ ), or 0, leading to  $\{\pm0, \pm\pi\}$  (in degrees,  $\{\pm0, \pm180\}$ ). Since  $\text{acot}(x, y) = \text{atan}(y, x)$ , \\_\_fp\_acotii\_o:ww simply reverses its two arguments.

```

15523 \cs_new:Npn \__fp_atanii_o:Nww
15524     #1 \s_fp \__fp_chk:w #2#3#4; \s_fp \__fp_chk:w #5
15525 {
15526     \if_meaning:w 3 #2 \__fp_case_return_i_o:ww \fi:
15527     \if_meaning:w 3 #5 \__fp_case_return_ii_o:ww \fi:
15528     \if_case:w
15529         \if_meaning:w #2 #5
15530             \if_meaning:w 1 #2 10 \else: 0 \fi:
15531         \else:
15532             \if_int_compare:w #2 > #5 \exp_stop_f: 1 \else: 2 \fi:
15533         \fi:
15534         \exp_stop_f:
15535         \__fp_case_return:nw { \__fp_atan_inf_o:NNNw #1 #3 2 }
15536     \or: \__fp_case_return:nw { \__fp_atan_inf_o:NNNw #1 #3 4 }
15537     \or: \__fp_case_return:nw { \__fp_atan_inf_o:NNNw #1 #3 0 }
15538     \fi:
15539     \__fp_atan_normal_o:NNnwNnw #1
15540     \s_fp \__fp_chk:w #2#3#4;
15541     \s_fp \__fp_chk:w #5
15542 }
15543 \cs_new:Npn \__fp_acotii_o:Nww #1#2; #3;

```

```
15544 { \_fp_atanii_o:Nww #1#3; #2; }
```

(End definition for \\_fp\_atanii\_o:Nww and \\_fp\_acotii\_o:Nww.)

\\_fp\_atan\_inf\_o:NNNw

This auxiliary is called whenever one number is  $\pm 0$  or  $\pm \infty$  (and neither is NaN). Then the result only depends on the signs, and its value is a multiple of  $\pi/4$ . We use the same auxiliary as for normal numbers, \\_fp\_atan\_combine\_o:NwwwwwN, with arguments the final sign #2; the octant #3;  $\text{atan } z/z = 1$  as a fixed point number;  $z = 0$  as a fixed point number; and  $z = 0$  as an extended-precision number. Given the values we provide,  $\text{atan } z$  is computed to be 0, and the result is  $[\#3/2] \cdot \pi/4$  if the sign #5 of  $x$  is positive, and  $[(7 - \#3)/2] \cdot \pi/4$  for negative  $x$ , where the divisions are rounded up.

```
15545 \cs_new:Npn \_fp_atan_inf_o:NNNw #1#2#3 \s_fp \_fp_chk:w #4#5#6;
15546 {
15547   \exp_after:wN \_fp_atan_combine_o:NwwwwwN
15548   \exp_after:wN #2
15549   \__int_value:w \__int_eval:w
15550   \if_meaning:w 2 #5 7 - \fi: #3 \exp_after:wN ;
15551   \c_fp_one_fixed_tl
15552   {0000}{0000}{0000}{0000}{0000}{0000};
15553   0,{0000}{0000}{0000}{0000}{0000}{0000}; #1
15554 }
```

(End definition for \\_fp\_atan\_inf\_o:NNNw.)

\\_fp\_atan\_normal\_o:NNwNnw

Here we simply reorder the floating point data into a pair of signed extended-precision numbers, that is, a sign, an exponent ending with a comma, and a six-block mantissa ending with a semi-colon. This extended precision is required by other inverse trigonometric functions, to compute things like  $\text{atan}(x, \sqrt{1 - x^2})$  without intermediate rounding errors.

```
15555 \cs_new_protected:Npn \_fp_atan_normal_o:NNwNnw
15556   #1 \s_fp \_fp_chk:w 1#2#3#4; \s_fp \_fp_chk:w 1#5#6#7;
15557 {
15558   \_fp_atan_test_o:NwwNwwN
15559   #2 #3, #4{0000}{0000};
15560   #5 #6, #7{0000}{0000}; #1
15561 }
```

(End definition for \\_fp\_atan\_normal\_o:NNwNnw.)

\\_fp\_atan\_test\_o:NwwNwwN

This receives: the sign #1 of  $y$ , its exponent #2, its 24 digits #3 in groups of 4, and similarly for  $x$ . We prepare to call \\_fp\_atan\_combine\_o:NwwwwwN which expects the sign #1, the octant, the ratio  $(\text{atan } z)/z = 1 - \dots$ , and the value of  $z$ , both as a fixed point number and as an extended-precision floating point number with a mantissa in  $[0.01, 1)$ . For now, we place #1 as a first argument, and start an integer expression for the octant. The sign of  $x$  does not affect  $z$ , so we simply leave a contribution to the octant:  $\langle \text{octant} \rangle \rightarrow 7 - \langle \text{octant} \rangle$  for negative  $x$ . Then we order  $|y|$  and  $|x|$  in a non-decreasing order: if  $|y| > |x|$ , insert 3- in the expression for the octant, and swap the two numbers. The finer test with 0.41421 is done by \\_fp\_atan\_div:wnwnw after the operands have been ordered.

```
15562 \cs_new:Npn \_fp_atan_test_o:NwwNwwN #1#2,#3; #4#5,#6;
15563 {
15564   \exp_after:wN \_fp_atan_combine_o:NwwwwwN
15565   \exp_after:wN #1
```

```

15566 \__int_value:w \__int_eval:w
15567 \if_meaning:w 2 #4
15568 7 - \__int_eval:w
15569 \fi:
15570 \if_int_compare:w
15571 \__fp_ep_compare:www #2,#3; #5,#6; > 0 \exp_stop_f:
15572 3 -
15573 \exp_after:wN \__fp_reverse_args:Nww
15574 \fi:
15575 \__fp_atan_div:wnwnw #2,#3; #5,#6;
15576 }

```

(End definition for \\_\_fp\_atan\_test\_o:NwwNwwN.)

```

\__fp_atan_div:wnwnw
\__fp_atan_near:wwn
\__fp_atan_near_aux:wn

```

This receives two positive numbers  $a$  and  $b$  (equal to  $|x|$  and  $|y|$  in some order), each as an exponent and 6 blocks of 4 digits, such that  $0 < a < b$ . If  $0.41421b < a$ , the two numbers are “near”, hence the point  $(y, x)$  that we started with is closer to the diagonals  $\{|y| = |x|\}$  than to the axes  $\{xy = 0\}$ . In that case, the octant is 1 (possibly combined with the 7– and 3– inserted earlier) and we wish to compute  $\operatorname{atan} \frac{b-a}{a+b}$ . Otherwise, the octant is 0 (again, combined with earlier terms) and we wish to compute  $\operatorname{atan} \frac{a}{b}$ . In any case, call \\_\_fp\_atan\_auxi:ww followed by  $z$ , as a comma-delimited exponent and a fixed point number.

```

15577 \cs_new:Npn \__fp_atan_div:wnwnw #1,#2#3; #4,#5#6;
15578 {
15579 \if_int_compare:w
15580 \__int_eval:w 41421 * #5 < #2 000
15581 \if_case:w \__int_eval:w #4 - #1 \__int_eval_end: 00 \or: 0 \fi:
15582 \exp_stop_f:
15583 \exp_after:wN \__fp_atan_near:wwn
15584 \fi:
15585 0
15586 \__fp_ep_div:wwwn #1,{#2}#3; #4,{#5}#6;
15587 \__fp_atan_auxi:ww
15588 }
15589 \cs_new:Npn \__fp_atan_near:wwn
15590 0 \__fp_ep_div:wwwn #1,#2; #3,
15591 {
15592 1
15593 \__fp_ep_to_fixed:wn #1 - #3, #2;
15594 \__fp_atan_near_aux:wn
15595 }
15596 \cs_new:Npn \__fp_atan_near_aux:wn #1; #2;
15597 {
15598 \__fp_fixed_add:wn #1; #2;
15599 { \__fp_fixed_sub:wn #2; #1; { \__fp_ep_div:wwwn 0, } 0, }
15600 }

```

(End definition for \\_\_fp\_atan\_div:wnwnw, \\_\_fp\_atan\_near:wwn, and \\_\_fp\_atan\_near\_aux:wn.)

```

\__fp_atan_auxi:ww
\__fp_atan_auxii:w

```

Convert  $z$  from a representation as an exponent and a fixed point number in  $[0.01, 1)$  to a fixed point number only, then set up the call to \\_\_fp\_atan\_Taylor\_loop:www, followed by the fixed point representation of  $z$  and the old representation.

```

15601 \cs_new:Npn \__fp_atan_auxi:ww #1,#2;
15602 { \__fp_ep_to_fixed:wn #1,#2; \__fp_atan_auxii:w #1,#2; }

```

```

15603 \cs_new:Npn \__fp_atan_auxii:w #1;
15604 {
15605   \__fp_fixed_mul:wwn #1; #1;
15606   {
15607     \__fp_atan_Taylor_loop:www 39 ;
15608     {0000}{0000}{0000}{0000}{0000}{0000} ;
15609   }
15610   ! #1;
15611 }

```

(End definition for \\_\_fp\_atan\_auxi:ww and \\_\_fp\_atan\_auxii:w.)

\\_\_fp\_atan\_Taylor\_loop:www We compute the series of  $(\operatorname{atan} z)/z$ . A typical intermediate stage has  $\#1 = 2k - 1$ ,  $\#2 = \frac{1}{2k+1} - z^2(\frac{1}{2k+3} - z^2(\dots - z^2\frac{1}{39}))$ , and  $\#3 = z^2$ . To go to the next step  $k \rightarrow k - 1$ , we compute  $\frac{1}{2k-1}$ , then subtract from it  $z^2$  times  $\#2$ . The loop stops when  $k = 0$ : then  $\#2$  is  $(\operatorname{atan} z)/z$ , and there is a need to clean up all the unnecessary data, end the integer expression computing the octant with a semicolon, and leave the result  $\#2$  afterwards.

```

15612 \cs_new:Npn \__fp_atan_Taylor_loop:www #1; #2; #3;
15613 {
15614   \if_int_compare:w #1 = -1 \exp_stop_f:
15615   \__fp_atan_Taylor_break:w
15616   \fi:
15617   \exp_after:wN \__fp_fixed_div_int:wwN \c__fp_one_fixed_tl #1;
15618   \__fp_rrot:www \__fp_fixed_mul_sub_back:wwwn #2; #3;
15619   {
15620     \exp_after:wN \__fp_atan_Taylor_loop:www
15621     \__int_value:w \__int_eval:w #1 - 2 ;
15622   }
15623   #3;
15624 }
15625 \cs_new:Npn \__fp_atan_Taylor_break:w
15626   \fi: #1 \__fp_fixed_mul_sub_back:wwwn #2; #3 !
15627   { \fi: ; #2 ; }

```

(End definition for \\_\_fp\_atan\_Taylor\_loop:www and \\_\_fp\_atan\_Taylor\_break:w.)

\\_\_fp\_atan\_combine\_o:NwwwwN This receives a  $\langle sign \rangle$ , an  $\langle octant \rangle$ , a fixed point value of  $(\operatorname{atan} z)/z$ , a fixed point number  $z$ , and another representation of  $z$ , as an  $\langle exponent \rangle$  and the fixed point number  $10^{-\langle exponent \rangle} z$ , followed by either `\use_i:nn` (when working in radians) or `\use_ii:nn` (when working in degrees). The function computes the floating point result

$$\langle sign \rangle \left( \left\lceil \frac{\langle octant \rangle}{2} \right\rceil \frac{\pi}{4} + (-1)^{\langle octant \rangle} \frac{\operatorname{atan} z}{z} \cdot z \right), \quad (11)$$

multiplied by  $180/\pi$  if working in degrees, and using in any case the most appropriate representation of  $z$ . The floating point result is passed to `\__fp_sanitizew`, which checks for overflow or underflow. If the octant is 0, leave the exponent  $\#5$  for `\__fp_sanitizew`, and multiply  $\#3 = \frac{\operatorname{atan} z}{z}$  with  $\#6$ , the adjusted  $z$ . Otherwise, multiply  $\#3 = \frac{\operatorname{atan} z}{z}$  with  $\#4 = z$ , then compute the appropriate multiple of  $\frac{\pi}{4}$  and add or subtract the product  $\#3 \cdot \#4$ . In both cases, convert to a floating point with `\__fp_fixed_to_float_o:wN`.

```

15628 \cs_new:Npn \__fp_atan_combine_o:NwwwwN #1 #2; #3; #4; #5; #6; #7
15629 {

```

```

15630 \exp_after:wN \__fp_sanitizew
15631 \exp_after:wN #1
15632 \__int_value:w \__int_eval:w
15633 \if_meaning:w 0 #2
15634 \exp_after:wN \use_i:nn
15635 \else:
15636 \exp_after:wN \use_ii:nn
15637 \fi:
15638 { #5 \__fp_fixed_mul:wwn #3; #6; }
15639 {
15640 \__fp_fixed_mul:wwn #3; #4;
15641 {
15642 \exp_after:wN \__fp_atan_combine_aux:ww
15643 \__int_value:w \__int_eval:w #2 / 2 ; #2;
15644 }
15645 }
15646 { #7 \__fp_fixed_to_float_o:wN \__fp_fixed_to_float_rad_o:wN }
15647 #1
15648 }
15649 \cs_new:Npn \__fp_atan_combine_aux:ww #1; #2;
15650 {
15651 \__fp_fixed_mul_short:wwn
15652 {7853}{9816}{3397}{4483}{0961}{5661};
15653 {#1}{0000}{0000};
15654 {
15655 \if_int_odd:w #2 \exp_stop_f:
15656 \exp_after:wN \__fp_fixed_sub:wwn
15657 \else:
15658 \exp_after:wN \__fp_fixed_add:wwn
15659 \fi:
15660 }
15661 }

```

(End definition for \\_\_fp\_atan\_combine\_o:NwwwN and \\_\_fp\_atan\_combine\_aux:ww.)

### 29.2.2 Arcsine and arccosine

\\_\_fp\_asin\_o:w Again, the first argument provided by l3fp-parse is \use\_i:nn if we are to work in radians and \use\_ii:nn for degrees. Then comes a floating point number. The arcsine of  $\pm 0$  or NaN is the same floating point number. The arcsine of  $\pm\infty$  raises an invalid operation exception. Otherwise, call an auxiliary common with \\_\_fp\_acos\_o:w, feeding it information about what function is being performed (for “invalid operation” exceptions).

```

15662 \cs_new:Npn \__fp_asin_o:w #1 \s__fp \__fp_chk:w #2#3; @
15663 {
15664 \if_case:w #2 \exp_stop_f:
15665 \__fp_case_return_same_o:w
15666 \or:
15667 \__fp_case_use:nw
15668 { \__fp_asin_normal_o:NfwNnnnw #1 { #1 { asin } { asind } } }
15669 \or:
15670 \__fp_case_use:nw
15671 { \__fp_invalid_operation_o:fw { #1 { asin } { asind } } }
15672 \else:
15673 \__fp_case_return_same_o:w

```

```

15674     \fi:
15675     \s__fp \__fp_chk:w #2 #3;
15676 }

```

(End definition for \\_\_fp\_asin\_o:w.)

**\\_\_fp\_acos\_o:w** The arccosine of  $\pm 0$  is  $\pi/2$  (in degrees, 90). The arccosine of  $\pm\infty$  raises an invalid operation exception. The arccosine of NaN is itself. Otherwise, call an auxiliary common with \\_\_fp\_sin\_o:w, informing it that it was called by acos or acosd, and preparing to swap some arguments down the line.

```

15677 \cs_new:Npn \__fp_acos_o:w #1 \s__fp \__fp_chk:w #2#3; @
15678 {
15679     \if_case:w #2 \exp_stop_f:
15680     \__fp_case_use:nw { \__fp_atan_inf_o:NNNw #1 0 4 }
15681     \or:
15682     \__fp_case_use:nw
15683     {
15684         \__fp_asin_normal_o:NfwNnnnnw #1 { #1 { acos } { acosd } }
15685         \__fp_reverse_args:Nww
15686     }
15687     \or:
15688     \__fp_case_use:nw
15689     { \__fp_invalid_operation_o:fw { #1 { acos } { acosd } } }
15690     \else:
15691     \__fp_case_return_same_o:w
15692     \fi:
15693     \s__fp \__fp_chk:w #2 #3;
15694 }

```

(End definition for \\_\_fp\_acos\_o:w.)

**\\_\_fp\_asin\_normal\_o:NfwNnnnnw** If the exponent #5 is at most 0, the operand lies within  $(-1, 1)$  and the operation is permitted: call \\_\_fp\_asin\_auxi\_o:NnNww with the appropriate arguments. If the number is exactly  $\pm 1$  (the test works because we know that  $\#5 \geq 1$ ,  $\#6\#7 \geq 10000000$ ,  $\#8\#9 \geq 0$ , with equality only for  $\pm 1$ ), we also call \\_\_fp\_asin\_auxi\_o:NnNww. Otherwise, \\_\_fp\_use\_i:ww gets rid of the asin auxiliary, and raises instead an invalid operation, because the operand is outside the domain of arcsine or arccosine.

```

15695 \cs_new:Npn \__fp_asin_normal_o:NfwNnnnnw
15696 #1#2#3 \s__fp \__fp_chk:w 1#4#5#6#7#8#9;
15697 {
15698     \if_int_compare:w #5 < 1 \exp_stop_f:
15699     \exp_after:wN \__fp_use_none_until_s:w
15700     \fi:
15701     \if_int_compare:w \__int_eval:w #5 + #6#7 + #8#9 = 1000 0001 ~
15702     \exp_after:wN \__fp_use_none_until_s:w
15703     \fi:
15704     \__fp_use_i:ww
15705     \__fp_invalid_operation_o:fw {#2}
15706     \s__fp \__fp_chk:w 1#4{#5}{#6}{#7}{#8}{#9};
15707     \__fp_asin_auxi_o:NnNww
15708     #1 {#3} #4 #5,{#6}{#7}{#8}{#9}{0000}{0000};
15709 }

```

(End definition for \\_\_fp\_asin\_normal\_o:NfwNnnnnw.)



`__fp_asin_auxi_o:NnNww`  
`__fp_asin_isqrt:wn`

We compute  $x/\sqrt{1-x^2}$ . This function is used by `asin` and `acos`, but also by `acsc` and `asec` after inverting the operand, thus it must manipulate extended-precision numbers. First evaluate  $1-x^2$  as  $(1+x)(1-x)$ : this behaves better near  $x=1$ . We do the addition/subtraction with fixed point numbers (they are not implemented for extended-precision floats), but go back to extended-precision floats to multiply and compute the inverse square root  $1/\sqrt{1-x^2}$ . Finally, multiply by the (positive) extended-precision float  $|x|$ , and feed the (signed) result, and the number  $+1$ , as arguments to the arctangent function. When computing the arccosine, the arguments  $x/\sqrt{1-x^2}$  and  $+1$  are swapped by #2 (`__fp_reverse_args:Nww` in that case) before `__fp_atan_test_o:NwwNwwN` is evaluated. Note that the arctangent function requires normalized arguments, hence the need for `ep_to_ep` and continue after `ep_mul`.

```

15710 \cs_new:Npn __fp_asin_auxi_o:NnNww #1#2#3#4,#5;
15711 {
15712   __fp_ep_to_fixed:wwn #4,#5;
15713   __fp_asin_isqrt:wn
15714   __fp_ep_mul:wwwn #4,#5;
15715   __fp_ep_to_ep:wwN
15716   __fp_fixed_continue:wn
15717   { #2 __fp_atan_test_o:NwwNwwN #3 }
15718   0 1,{1000}{0000}{0000}{0000}{0000}{0000}; #1
15719 }
15720 \cs_new:Npn __fp_asin_isqrt:wn #1;
15721 {
15722   \exp_after:wN __fp_fixed_sub:wwn \c__fp_one_fixed_tl #1;
15723   {
15724     __fp_fixed_add_one:wn #1;
15725     __fp_fixed_continue:wn { __fp_ep_mul:wwwn 0, } 0,
15726   }
15727   __fp_ep_isqrt:wwn
15728 }

```

(End definition for `__fp_asin_auxi_o:NnNww` and `__fp_asin_isqrt:wn`.)

### 29.2.3 Arccosecant and arcsecant

`__fp_acsc_o:w`

Cases are mostly labelled by #2, except when #2 is 2: then we use #3#2, which is 02 = 2 when the number is  $+\infty$  and 22 when the number is  $-\infty$ . The arccosecant of  $\pm 0$  raises an invalid operation exception. The arccosecant of  $\pm\infty$  is  $\pm 0$  with the same sign. The arcosecant of NaN is itself. Otherwise, `__fp_acsc_normal_o:NfwNnw` does some more tests, keeping the function name (`acsc` or `acscd`) as an argument for invalid operation exceptions.

```

15729 \cs_new:Npn __fp_acsc_o:w #1 \s_fp __fp_chk:w #2#3#4; @
15730 {
15731   \if_case:w \if_meaning:w 2 #2 #3 \fi: #2 \exp_stop_f:
15732     __fp_case_use:nw
15733     { __fp_invalid_operation_o:fw { #1 { acsc } { acscd } } }
15734   \or: __fp_case_use:nw
15735     { __fp_acsc_normal_o:NfwNnw #1 { #1 { acsc } { acscd } } }
15736   \or: __fp_case_return_o:Nw \c_zero_fp
15737   \or: __fp_case_return_same_o:w
15738   \else: __fp_case_return_o:Nw \c_minus_zero_fp
15739   \fi:
15740   \s_fp __fp_chk:w #2 #3 #4;

```

```
15741 }
```

(End definition for `\_fp_acsc_o:w`.)

`\_fp_asec_o:w` The arcsecant of  $\pm 0$  raises an invalid operation exception. The arcsecant of  $\pm\infty$  is  $\pi/2$  (in degrees, 90). The arcosecant of NaN is itself. Otherwise, do some more tests, keeping the function name `asec` (or `asecd`) as an argument for invalid operation exceptions, and a `\_fp_reverse_args:Nww` following precisely that appearing in `\_fp_acos_o:w`.

```
15742 \cs_new:Npn \_fp_asec_o:w #1 \s__fp \_fp_chk:w #2#3; @
15743 {
15744   \if_case:w #2 \exp_stop_f:
15745     \_fp_case_use:nw
15746     { \_fp_invalid_operation_o:fw { #1 { asec } { asecd } } }
15747   \or:
15748     \_fp_case_use:nw
15749     {
15750       \_fp_acsc_normal_o:NfwNnw #1 { #1 { asec } { asecd } }
15751       \_fp_reverse_args:Nww
15752     }
15753   \or: \_fp_case_use:nw { \_fp_atan_inf_o:NNNw #1 0 4 }
15754   \else: \_fp_case_return_same_o:w
15755   \fi:
15756   \s__fp \_fp_chk:w #2 #3;
15757 }
```

(End definition for `\_fp_asec_o:w`.)

`\_fp_acsc_normal_o:NfwNnw` If the exponent is non-positive, the operand is less than 1 in absolute value, which is always an invalid operation: complain. Otherwise, compute the inverse of the operand, and feed it to `\_fp_asin_auxi_o:NnNww` (with all the appropriate arguments). This computes what we want thanks to  $\operatorname{acsc}(x) = \operatorname{asin}(1/x)$  and  $\operatorname{asec}(x) = \operatorname{acos}(1/x)$ .

```
15758 \cs_new:Npn \_fp_acsc_normal_o:NfwNnw #1#2#3 \s__fp \_fp_chk:w 1#4#5#6;
15759 {
15760   \int_compare:nNnTF {#5} < 1
15761   {
15762     \_fp_invalid_operation_o:fw {#2}
15763     \s__fp \_fp_chk:w 1#4{#5}#6;
15764   }
15765   {
15766     \_fp_ep_div:wwwn
15767     1,{1000}{0000}{0000}{0000}{0000};
15768     #5,#6{0000}{0000};
15769     { \_fp_asin_auxi_o:NnNww #1 {#3} #4 }
15770   }
15771 }
```

(End definition for `\_fp_acsc_normal_o:NfwNnw`.)

```
15772 </initex | package>
```

## 30 13fp-convert implementation

15773  $\langle *initex \mid package \rangle$

15774  $\langle @@=fp \rangle$

### 30.1 Trimming trailing zeros

`\__fp_trim_zeros:w`  
`\__fp_trim_zeros_loop:w`  
`\__fp_trim_zeros_dot:w`  
`\__fp_trim_zeros_end:w`

If #1 ends with a 0, the loop auxiliary takes that zero as an end-delimiter for its first argument, and the second argument is the same loop auxiliary. Once the last trailing zero is reached, the second argument is the dot auxiliary, which removes a trailing dot if any. We then clean-up with the end auxiliary, keeping only the number.

```
15775 \cs_new:Npn \__fp_trim_zeros:w #1 ;
15776 {
15777   \__fp_trim_zeros_loop:w #1
15778   ; \__fp_trim_zeros_loop:w 0; \__fp_trim_zeros_dot:w .; \s__stop
15779 }
15780 \cs_new:Npn \__fp_trim_zeros_loop:w #1 0; #2 { #2 #1 ; #2 }
15781 \cs_new:Npn \__fp_trim_zeros_dot:w #1 .; { \__fp_trim_zeros_end:w #1 ; }
15782 \cs_new:Npn \__fp_trim_zeros_end:w #1 ; #2 \s__stop { #1 }
```

(End definition for `\__fp_trim_zeros:w` and others.)

### 30.2 Scientific notation

`\fp_to_scientific:N`  
`\fp_to_scientific:c`  
`\fp_to_scientific:n`

The three public functions evaluate their argument, then pass it to `\__fp_to_scientific_dispatch:w`.

```
15783 \cs_new:Npn \fp_to_scientific:N #1
15784 { \exp_after:wN \__fp_to_scientific_dispatch:w #1 }
15785 \cs_generate_variant:Nn \fp_to_scientific:N { c }
15786 \cs_new:Npn \fp_to_scientific:n
15787 {
15788   \exp_after:wN \__fp_to_scientific_dispatch:w
15789   \exp:w \exp_end_continue_f:w \__fp_parse:n
15790 }
```

(End definition for `\fp_to_scientific:N` and `\fp_to_scientific:n`. These functions are documented on page 179.)

`\__fp_to_scientific_dispatch:w`  
`\__fp_to_scientific_normal:wnnnnn`  
`\__fp_to_scientific_normal:wNw`

Expressing an internal floating point number in scientific notation is quite easy: no rounding, and the format is very well defined. First cater for the sign: negative numbers (#2 = 2) start with -; we then only need to care about positive numbers and `nan`. Then filter the special cases:  $\pm 0$  are represented as 0; infinities are converted to a number slightly larger than the largest after an “invalid\_operation” exception; `nan` is represented as 0 after an “invalid\_operation” exception. In the normal case, decrement the exponent and unbrace the 4 brace groups, then in a second step grab the first digit (previously hidden in braces) to order the various parts correctly.

```
15791 \cs_new:Npn \__fp_to_scientific_dispatch:w \s__fp \__fp_chk:w #1#2
15792 {
15793   \if_meaning:w 2 #2 \exp_after:wN - \exp:w \exp_end_continue_f:w \fi:
15794   \if_case:w #1 \exp_stop_f:
15795     \__fp_case_return:nw { 0.0000000000000000e0 }
15796   \or: \exp_after:wN \__fp_to_scientific_normal:wnnnnn
15797   \or:
```

```

15798     \__fp_case_use:nw
15799     {
15800         \__fp_invalid_operation:nnw
15801         { \fp_to_scientific:N \c__fp_overflowing_fp }
15802         { fp_to_scientific }
15803     }
15804 \or:
15805     \__fp_case_use:nw
15806     {
15807         \__fp_invalid_operation:nnw
15808         { \fp_to_scientific:N \c_zero_fp }
15809         { fp_to_scientific }
15810     }
15811 \fi:
15812 \s__fp \__fp_chk:w #1 #2
15813 }
15814 \cs_new:Npn \__fp_to_scientific_normal:wnnnnn
15815 \s__fp \__fp_chk:w 1 #1 #2 #3#4#5#6 ;
15816 {
15817     \exp_after:wN \__fp_to_scientific_normal:wNw
15818     \exp_after:wN e
15819     \__int_value:w \__int_eval:w #2 - 1
15820     ; #3 #4 #5 #6 ;
15821 }
15822 \cs_new:Npn \__fp_to_scientific_normal:wNw #1 ; #2#3;
15823 { #2.#3 #1 }

(End definition for \__fp_to_scientific_dispatch:w, \__fp_to_scientific_normal:wnnnnn, and \__-
fp_to_scientific_normal:wNw.)

```

### 30.3 Decimal representation

**\fp\_to\_decimal:N** All three public variants are based on the same `\__fp_to_decimal_dispatch:w` after evaluating their argument to an internal floating point.

**\fp\_to\_decimal:c**

**\fp\_to\_decimal:n**

```

15824 \cs_new:Npn \fp_to_decimal:N #1
15825 { \exp_after:wN \__fp_to_decimal_dispatch:w #1 }
15826 \cs_generate_variant:Nn \fp_to_decimal:N { c }
15827 \cs_new:Npn \fp_to_decimal:n
15828 {
15829     \exp_after:wN \__fp_to_decimal_dispatch:w
15830     \exp:w \exp_end_continue_f:w \__fp_parse:n
15831 }

```

(End definition for `\fp_to_decimal:N` and `\fp_to_decimal:n`. These functions are documented on page 178.)

`\__fp_to_decimal_dispatch:w`  
`\__fp_to_decimal_normal:wnnnnn`  
`\__fp_to_decimal_large:Nnnw`  
`\__fp_to_decimal_huge:wnnnn`

The structure is similar to `\__fp_to_scientific_dispatch:w`. Insert `-` for negative numbers. Zero gives 0,  $\pm\infty$  and NaN yield an “invalid operation” exception; note that  $\pm\infty$  produces a very large output, which we don’t expand now since it most likely won’t be needed. Normal numbers with an exponent in the range  $[1, 15]$  have that number of digits before the decimal separator: “decimate” them, and remove leading zeros with `\__int_value:w`, then trim trailing zeros and dot. Normal numbers with an exponent 16 or larger have no decimal separator, we only need to add trailing zeros. When the exponent is non-positive, the result should be  $0.\langle zeros \rangle \langle digits \rangle$ , trimmed.

```

15832 \cs_new:Npn \__fp_to_decimal_dispatch:w \s__fp \__fp_chk:w #1#2
15833 {
15834   \if_meaning:w 2 #2 \exp_after:wN - \exp:w \exp_end_continue_f:w \fi:
15835   \if_case:w #1 \exp_stop_f:
15836     \__fp_case_return:nw { 0 }
15837   \or: \exp_after:wN \__fp_to_decimal_normal:wnnnnn
15838   \or:
15839     \__fp_case_use:nw
15840     {
15841       \__fp_invalid_operation:nnw
15842       { \fp_to_decimal:N \c__fp_overflowing_fp }
15843       { fp_to_decimal }
15844     }
15845   \or:
15846     \__fp_case_use:nw
15847     {
15848       \__fp_invalid_operation:nnw
15849       { 0 }
15850       { fp_to_decimal }
15851     }
15852   \fi:
15853   \s__fp \__fp_chk:w #1 #2
15854 }
15855 \cs_new:Npn \__fp_to_decimal_normal:wnnnnn
15856 \s__fp \__fp_chk:w 1 #1 #2 #3#4#5#6 ;
15857 {
15858   \int_compare:nNnTF {#2} > 0
15859   {
15860     \int_compare:nNnTF {#2} < \c__fp_prec_int
15861     {
15862       \__fp_decimate:nNnnnn { \c__fp_prec_int - #2 }
15863       \__fp_to_decimal_large:Nnnw
15864     }
15865     {
15866       \exp_after:wN \exp_after:wN
15867       \exp_after:wN \__fp_to_decimal_huge:wnnnnn
15868       \prg_replicate:nn { #2 - \c__fp_prec_int } { 0 } ;
15869     }
15870     {#3} {#4} {#5} {#6}
15871   }
15872   {
15873     \exp_after:wN \__fp_trim_zeros:w
15874     \exp_after:wN 0
15875     \exp_after:wN .
15876     \exp:w \exp_end_continue_f:w \prg_replicate:nn { - #2 } { 0 }
15877     #3#4#5#6 ;
15878   }
15879 }
15880 \cs_new:Npn \__fp_to_decimal_large:Nnnw #1#2#3#4;
15881 {
15882   \exp_after:wN \__fp_trim_zeros:w \__int_value:w
15883   \if_int_compare:w #2 > 0 \exp_stop_f:
15884   #2
15885   \fi:

```

```

15886         \exp_stop_f:
15887         #3.#4 ;
15888     }
15889 \cs_new:Npn \__fp_to_decimal_huge:wnnnn #1; #2#3#4#5 { #2#3#4#5 #1 }

```

(End definition for \\_\_fp\_to\_decimal\_dispatch:w and others.)

## 30.4 Token list representation

**\fp\_to\_tl:N** These three public functions evaluate their argument, then pass it to \\_\_fp\_to\_tl\_dispatch:w.

**\fp\_to\_tl:c**

**\fp\_to\_tl:n**

```

15890 \cs_new:Npn \fp_to_tl:N #1 { \exp_after:wN \__fp_to_tl_dispatch:w #1 }
15891 \cs_generate_variant:Nn \fp_to_tl:N { c }
15892 \cs_new:Npn \fp_to_tl:n
15893 {
15894     \exp_after:wN \__fp_to_tl_dispatch:w
15895     \exp:w \exp_end_continue_f:w \__fp_parse:n
15896 }

```

(End definition for \fp\_to\_tl:N and \fp\_to\_tl:n. These functions are documented on page 179.)

**\\_\_fp\_to\_tl\_dispatch:w**  
**\\_\_fp\_to\_tl\_normal:nnnnn**  
**\\_\_fp\_to\_tl\_scientific:wnnnnn**  
**\\_\_fp\_to\_tl\_scientific:wNw**

A structure similar to \\_\_fp\_to\_scientific\_dispatch:w and \\_\_fp\_to\_decimal\_dispatch:w, but without the “invalid operation” exception. First filter special cases. We express normal numbers in decimal notation if the exponent is in the range  $[-2, 16]$ , and otherwise use scientific notation.

```

15897 \cs_new:Npn \__fp_to_tl_dispatch:w \s_fp \__fp_chk:w #1#2
15898 {
15899     \if_meaning:w 2 #2 \exp_after:wN - \exp:w \exp_end_continue_f:w \fi:
15900     \if_case:w #1 \exp_stop_f:
15901         \__fp_case_return:nw { 0 }
15902     \or: \exp_after:wN \__fp_to_tl_normal:nnnnn
15903     \or: \__fp_case_return:nw { inf }
15904     \else: \__fp_case_return:nw { nan }
15905     \fi:
15906 }
15907 \cs_new:Npn \__fp_to_tl_normal:nnnnn #1
15908 {
15909     \int_compare:nTF
15910     { -2 <= #1 <= \c__fp_prec_int }
15911     { \__fp_to_decimal_normal:wnnnnn }
15912     { \__fp_to_tl_scientific:wnnnnn }
15913     \s_fp \__fp_chk:w 1 0 {#1}
15914 }
15915 \cs_new:Npn \__fp_to_tl_scientific:wnnnnn
15916 \s_fp \__fp_chk:w 1 #1 #2 #3#4#5#6 ;
15917 {
15918     \exp_after:wN \__fp_to_tl_scientific:wNw
15919     \exp_after:wN e
15920     \__int_value:w \__int_eval:w #2 - 1
15921     ; #3 #4 #5 #6 ;
15922 }
15923 \cs_new:Npn \__fp_to_tl_scientific:wNw #1 ; #2#3;
15924 { \__fp_trim_zeros:w #2.#3 ; #1 }

```

(End definition for \\_\_fp\_to\_tl\_dispatch:w and others.)

## 30.5 Formatting

This is not implemented yet, as it is not yet clear what a correct interface would be, for this kind of structured conversion from a floating point (or other types of variables) to a string. Ideas welcome.

## 30.6 Convert to dimension or integer

`\fp_to_dim:N` These three public functions rely on `\fp_to_decimal:n` internally.

```
\fp_to_dim:c 15925 \cs_new:Npn \fp_to_dim:N #1
\fp_to_dim:n 15926 { \fp_to_decimal:N #1 pt }
15927 \cs_generate_variant:Nn \fp_to_dim:N { c }
15928 \cs_new:Npn \fp_to_dim:n #1
15929 { \fp_to_decimal:n {#1} pt }
```

(End definition for `\fp_to_dim:N` and `\fp_to_dim:n`. These functions are documented on page 178.)

`\fp_to_int:N` These three public functions evaluate their argument, then pass it to `\fp_to_int_dispatch:w`.

```
\fp_to_int:c 15930 \cs_new:Npn \fp_to_int:N #1 { \exp_after:wN \__fp_to_int_dispatch:w #1 }
\fp_to_int:n 15931 \cs_generate_variant:Nn \fp_to_int:N { c }
15932 \cs_new:Npn \fp_to_int:n
15933 {
15934   \exp_after:wN \__fp_to_int_dispatch:w
15935   \exp:w \exp_end_continue_f:w \__fp_parse:n
15936 }
```

(End definition for `\fp_to_int:N` and `\fp_to_int:n`. These functions are documented on page 179.)

`\__fp_to_int_dispatch:w` To convert to an integer, first round to 0 places (to the nearest integer), then express the result as a decimal number: the definition of `\__fp_to_decimal_dispatch:w` is such that there are no trailing dot nor zero.

```
15937 \cs_new:Npn \__fp_to_int_dispatch:w #1;
15938 {
15939   \exp_after:wN \__fp_to_decimal_dispatch:w \exp:w \exp_end_continue_f:w
15940   \__fp_round:Nwn \__fp_round_to_nearest:NNN #1; { 0 }
15941 }
```

(End definition for `\__fp_to_int_dispatch:w`.)

## 30.7 Convert from a dimension

`\dim_to_fp:n` The dimension expression (which can in fact be a glue expression) is evaluated, converted to a number (*i.e.*, expressed in scaled points), then multiplied by  $2^{-16} = 0.0000152587890625$  to give a value expressed in points. The auxiliary `\__fp_mul_npos_o:Nww` expects the desired *final sign* and two floating point operands (of the form `\s__fp ... ;`) as arguments. This set of functions is also used to convert dimension registers to floating points while parsing expressions: in this context there is an additional exponent, which is the first argument of `\__fp_from_dim_test:ww`, and is combined with the exponent  $-4$  of  $2^{-16}$ . There is also a need to expand afterwards: this is performed by `\__fp_mul_npos_o:Nww`, and cancelled by `\prg_do_nothing:` here.

```
15942 \cs_new:Npn \dim_to_fp:n #1
15943 {
```

```

15944 \exp_after:wN \_fp_from_dim_test:ww
15945 \exp_after:wN 0
15946 \exp_after:wN ,
15947 \_int_value:w \etex_glueexpr:D #1 ;
15948 }
15949 \cs_new:Npn \_fp_from_dim_test:ww #1, #2
15950 {
15951 \if_meaning:w 0 #2
15952 \_fp_case_return:nw { \exp_after:wN \c_zero_fp }
15953 \else:
15954 \exp_after:wN \_fp_from_dim:wNw
15955 \_int_value:w \_int_eval:w #1 - 4
15956 \if_meaning:w - #2
15957 \exp_after:wN , \exp_after:wN 2 \_int_value:w
15958 \else:
15959 \exp_after:wN , \exp_after:wN 0 \_int_value:w #2
15960 \fi:
15961 \fi:
15962 }
15963 \cs_new:Npn \_fp_from_dim:wNw #1,#2#3;
15964 {
15965 \_fp_pack_twice_four:wNNNNNNNN \_fp_from_dim:wNNnnnnnn ;
15966 #3 000 0000 00 {10}987654321; #2 {#1}
15967 }
15968 \cs_new:Npn \_fp_from_dim:wNNnnnnnn #1; #2#3#4#5#6#7#8#9
15969 { \_fp_from_dim:wnnnnwNn #1 {#2#300} {0000} ; }
15970 \cs_new:Npn \_fp_from_dim:wnnnnwNn #1; #2#3#4#5#6; #7#8
15971 {
15972 \_fp_mul_npos_o:Nww #7
15973 \s__fp \_fp_chk:w 1 #7 {#5} #1 ;
15974 \s__fp \_fp_chk:w 1 0 {#8} {1525} {8789} {0625} {0000} ;
15975 \prg_do_nothing:
15976 }

```

(End definition for `\dim_to_fp:n` and others. These functions are documented on page 155.)

## 30.8 Use and eval

**\fp\_use:N** Those public functions are simple copies of the decimal conversions.

```

\fp_use:c 15977 \cs_new_eq:NN \fp_use:N \fp_to_decimal:N
\fp_eval:n 15978 \cs_generate_variant:Nn \fp_use:N { c }
15979 \cs_new_eq:NN \fp_eval:n \fp_to_decimal:n

```

(End definition for `\fp_use:N` and `\fp_eval:n`. These functions are documented on page 179.)

**\fp\_abs:n** Trivial but useful. See the implementation of `\fp_add:Nn` for an explanation of why to use `\_fp_parse:n`, namely, for better error reporting.

```

15980 \cs_new:Npn \fp_abs:n #1
15981 { \fp_to_decimal:n { abs \_fp_parse:n {#1} } }

```

(End definition for `\fp_abs:n`. This function is documented on page 192.)

**\fp\_max:nn** Similar to `\fp_abs:n`, for consistency with `\int_max:nn`, etc.

```

\fp_min:nn 15982 \cs_new:Npn \fp_max:nn #1#2

```



```

15983 { \fp_to_decimal:n { max ( \__fp_parse:n {#1} , \__fp_parse:n {#2} ) } }
15984 \cs_new:Npn \fp_min:nn #1#2
15985 { \fp_to_decimal:n { min ( \__fp_parse:n {#1} , \__fp_parse:n {#2} ) } }

```

(End definition for `\fp_max:nn` and `\fp_min:nn`. These functions are documented on page 192.)

### 30.9 Convert an array of floating points to a comma list

`\__fp_array_to_clist:n` Converts an array of floating point numbers to a comma-list. If speed here ends up irrelevant, we can simplify the code for the auxiliary to become

```

\cs_new:Npn \__fp_array_to_clist_loop:Nw #1#2;
{
  \use_none:n #1
  { , ~ } \fp_to_tl:n { #1 #2 ; }
  \__fp_array_to_clist_loop:Nw
}

```

The `\use_ii:nn` function is expanded after `\__fp_expand:n` is done, and it removes `,~` from the start of the representation.

```

15986 \cs_new:Npn \__fp_array_to_clist:n #1
15987 {
15988   \tl_if_empty:nF {#1}
15989   {
15990     \__fp_expand:n
15991     {
15992       { \use_ii:nn }
15993       \__fp_array_to_clist_loop:Nw #1 { ? \__prg_break: } ;
15994       \__prg_break_point:
15995     }
15996   }
15997 }
15998 \cs_new:Npx \__fp_array_to_clist_loop:Nw #1#2;
15999 {
16000   \exp_not:N \use_none:n #1
16001   \exp_not:N \exp_after:wN
16002   {
16003     \exp_not:N \exp_after:wN ,
16004     \exp_not:N \exp_after:wN \c_space_tl
16005     \exp_not:N \exp:w
16006     \exp_not:N \exp_end_continue_f:w
16007     \exp_not:N \__fp_to_tl_dispatch:w #1 #2 ;
16008   }
16009   \exp_not:N \__fp_array_to_clist_loop:Nw
16010 }

```

(End definition for `\__fp_array_to_clist:n` and `\__fp_array_to_clist_loop:Nw`.)

```

16011 </initex | package>

```

## 31 l3fp-random Implementation

```

16012 <*initex | package>

```

16013 <@@=fp>

\\\_fp\_parse\_word\_rand:N  
\\\_fp\_parse\_word\_randint:N

Those functions may receive a variable number of arguments. We won't use the argument ?.

16014 \\cs\_new:Npn \\\_fp\_parse\_word\_rand:N  
16015 { \\\_fp\_parse\_function:NNN \\\_fp\_rand\_o:Nw ? }  
16016 \\cs\_new:Npn \\\_fp\_parse\_word\_randint:N  
16017 { \\\_fp\_parse\_function:NNN \\\_fp\_randint\_o:Nw ? }

(End definition for \\\_fp\_parse\_word\_rand:N and \\\_fp\_parse\_word\_randint:N.)

## 31.1 Engine support

At present, X<sub>Y</sub>TeX, pTeX and upTeX do not provide random numbers, while LuaTeX and pdfTeX provide the primitive `\pdfutex_uniformdeviate:D` (`\pdfuniformdeviate` in pdfTeX and `\uniformdeviate` in LuaTeX). We write the test twice simply in order to write the false branch first.

16018 \\cs\_if\_exist:NF \\pdfutex\_uniformdeviate:D  
16019 {  
16020 \\\_msg\_kernel\_new:nnn { kernel } { fp-no-random }  
16021 { Random-numbers-unavailable }  
16022 \\cs\_new:Npn \\\_fp\_rand\_o:Nw ? #1 @  
16023 {  
16024 \\\_msg\_kernel\_expandable\_error:nn { kernel } { fp-no-random }  
16025 \\exp\_after:wN \\c\_nan\_fp  
16026 }  
16027 \\cs\_new\_eq:NN \\\_fp\_randint\_o:Nw \\\_fp\_rand\_o:Nw  
16028 }  
16029 \\cs\_if\_exist:NT \\pdfutex\_uniformdeviate:D  
16030 {

\\\_fp\_rand\_uniform:  
\\\_fp\_rand\_size\_int  
\\\_fp\_rand\_four\_int  
\\\_fp\_rand\_eight\_int

The `\pdfutex_uniformdeviate:D` primitive gives a pseudo-random integer in a range  $[0, n - 1]$  of the user's choice. This number is meant to be uniformly distributed, but is produced by rescaling a uniform pseudo-random integer in  $[0, 2^{28} - 1]$ . For instance, setting  $n$  to (any multiple of)  $2^{29}$  gives only even values. Thus it is only safe to call `\pdfutex_uniformdeviate:D` with argument  $2^{28}$ . This integer is also used in the implementation of `\int_rand:nn`. We also use variants of this number rounded down to multiples of  $10^4$  and  $10^8$ .

16031 \\cs\_new:Npn \\\_fp\_rand\_uniform:  
16032 { \\pdfutex\_uniformdeviate:D \\\_fp\_rand\_size\_int }  
16033 \\int\_const:Nn \\\_fp\_rand\_size\_int { 268 435 456 }  
16034 \\int\_const:Nn \\\_fp\_rand\_four\_int { 268 430 000 }  
16035 \\int\_const:Nn \\\_fp\_rand\_eight\_int { 200 000 000 }

(End definition for \\\_fp\_rand\_uniform: and others.)

\\\_fp\_rand\_myriads:n  
\\\_fp\_rand\_myriads\_loop:nn  
\\\_fp\_rand\_myriads\_get:w  
\\\_fp\_rand\_myriads\_last:  
\\\_fp\_rand\_myriads\_last:w

Used as `\\_fp_rand_myriads:n {XXX}` with one input character per block of four digit we want. Given a pseudo-random integer from the primitive, we extract 2 blocks of digits if possible, namely if the integer is less than  $2 \times 10^8$ . If that's not possible, we try to extract 1 block, which succeeds in the range  $[2 \times 10^8, 26843 \times 10^4)$ . For the 5456 remaining possible values we just throw away the random integer and get a new one. Depending on whether we got 2, 1, or 0 blocks, remove the same number of characters from the input stream with `\use_i:nnn`, `\use_i:nn` or nothing.

```

16036 \cs_new:Npn \__fp_rand_myriads:n #1
16037 {
16038   \__fp_rand_myriads_loop:nn #1
16039   { ? \use_i_delimit_by_q_stop:nw \__fp_rand_myriads_last: }
16040   { ? \use_none_delimit_by_q_stop:w } \q_stop
16041 }
16042 \cs_new:Npn \__fp_rand_myriads_loop:nn #1#2
16043 {
16044   \use_none:n #2
16045   \exp_after:wN \__fp_rand_myriads_get:w
16046   \__int_value:w \__fp_rand_uniform: ; {#1}{#2}
16047 }
16048 \cs_new:Npn \__fp_rand_myriads_get:w #1 ;
16049 {
16050   \if_int_compare:w #1 < \c__fp_rand_eight_int
16051   \exp_after:wN \use_none:n
16052   \__int_value:w \__int_eval:w
16053   \c__fp_rand_eight_int + #1 \__int_eval_end:
16054   \exp_after:wN \use_i:nnn
16055   \else:
16056   \if_int_compare:w #1 < \c__fp_rand_four_int
16057   \exp_after:wN \use_none:nnnnn
16058   \__int_value:w \__int_eval:w
16059   \c__fp_rand_four_int + #1 \__int_eval_end:
16060   \exp_after:wN \exp_after:wN \exp_after:wN \use_i:nn
16061   \fi:
16062   \fi:
16063   \__fp_rand_myriads_loop:nn
16064 }
16065 \cs_new:Npn \__fp_rand_myriads_last:
16066 {
16067   \exp_after:wN \__fp_rand_myriads_last:w
16068   \__int_value:w \__fp_rand_uniform: ;
16069 }
16070 \cs_new:Npn \__fp_rand_myriads_last:w #1 ;
16071 {
16072   \if_int_compare:w #1 < \c__fp_rand_four_int
16073   \exp_after:wN \use_none:nnnnn
16074   \__int_value:w \__int_eval:w
16075   \c__fp_rand_four_int + #1 \__int_eval_end:
16076   \else:
16077   \exp_after:wN \__fp_rand_myriads_last:
16078   \fi:
16079 }

```

(End definition for \\_\_fp\_rand\_myriads:n and others.)

## 31.2 Random floating point

\\_\_fp\_rand\_o:Nw First we check that random was called without argument. Then get four blocks of four digits.

```

\__fp_rand_o:
\__fp_rand_o:w
16080 \cs_new:Npn \__fp_rand_o:Nw ? #1 @
16081 {
16082   \tl_if_empty:nTF {#1}

```

```

16083     { \_fp_rand_o: }
16084     {
16085         \_msg_kernel_expandable_error:nnnnn
16086         { kernel } { fp-num-args } { rand() } { 0 } { 0 }
16087         \exp_after:wN \c_nan_fp
16088     }
16089 }
16090 \cs_new:Npn \_fp_rand_o:
16091 { \_fp_parse_o:n { . \_fp_rand_myriads:n { xxxx } } }

```

(End definition for \\_fp\_rand\_o:Nw, \\_fp\_rand\_o:, and \\_fp\_rand\_o:w.)

### 31.3 Random integer

```

\_fp_randint_o:Nw
\_fp_randint_badarg:w
  \_fp_randint_e:w
    \_fp_randint_e:wnn
    \_fp_randint_e:wwNnn
    \_fp_randint_e:wwwNnn
\_fp_randint_narrow_e:nnnn
\_fp_randint_wide_e:nnnn
\_fp_randint_wide_e:wnnn

```

Enforce that there is one argument (then add first argument 1) or two arguments. Enforce that they are integers in  $(-10^{16}, 10^{16})$  and ordered. We distinguish narrow ranges (less than  $2^{28}$ ) from wider ones.

For narrow ranges, compute the number  $n$  of possible outputs as an integer using `\fp_to_int:n`, and reduce a pseudo-random 28-bit integer  $r$  modulo  $n$ . On its own, this is not uniform when  $[0, 2^{28} - 1]$  does not divide evenly into intervals of size  $n$ . The auxiliary `\_fp_randint_e:wwwNnn` discards the pseudo-random integer if it lies in an incomplete interval, and repeats.

For wide ranges we use the same code except for the last eight digits which use `\_fp_rand_myriads:n`. It is not safe to combine the first digits with the last eight as a single string of digits, as this may exceed 16 digits and be rounded. Instead, we first add the first few digits (times  $10^8$ ) to the lower bound. The result is compared to the upper bound and the process repeats if needed.

```

16092 \cs_new:Npn \_fp_randint_o:Nw ? #1 @
16093 {
16094   \if_case:w
16095     \_int_eval:w \_fp_array_count:n {#1} - 1 \_int_eval_end:
16096     \exp_after:wN \_fp_randint_e:w \c_one_fp #1
16097   \or: \_fp_randint_e:w #1
16098   \else:
16099     \_msg_kernel_expandable_error:nnnnn
16100     { kernel } { fp-num-args } { randint() } { 1 } { 2 }
16101     \exp_after:wN \c_nan_fp \exp:w
16102   \fi:
16103   \exp_after:wN \exp_end:
16104 }
16105 \cs_new:Npn \_fp_randint_badarg:w \s__fp \_fp_chk:w #1#2#3;
16106 {
16107   \_fp_int:wTF \s__fp \_fp_chk:w #1#2#3;
16108   {
16109     \if_meaning:w 1 #1
16110       \if_int_compare:w
16111         \use_i_delimit_by_q_stop:nw #3 \q_stop > \c__fp_prec_int
16112         1 \exp_stop_f:
16113       \fi:
16114     \fi:
16115   }
16116   { 1 \exp_stop_f: }
16117 }

```

```

16118 \cs_new:Npn \__fp_randint_e:w #1; #2;
16119 {
16120   \if_case:w
16121     \__fp_randint_badarg:w #1;
16122     \__fp_randint_badarg:w #2;
16123     \fp_compare:nNnTF { #1; } > { #2; } { 1 } { 0 } \exp_stop_f:
16124     \exp_after:wN \exp_after:wN \exp_after:wN \__fp_randint_e:wnn
16125     \__fp_parse:n { #2; - #1; } { #1; } { #2; }
16126   \or:
16127     \__fp_invalid_operation_tl_o:ff
16128     { randint } { \__fp_array_to_clist:n { #1; #2; } }
16129   \exp:w
16130   \fi:
16131 }
16132 \cs_new:Npn \__fp_randint_e:wnn #1;
16133 {
16134   \exp_after:wN \__fp_randint_e:wwNnn
16135   \__int_value:w \__fp_rand_uniform: \exp_after:wN ;
16136   \exp:w \exp_end_continue_f:w
16137   \fp_compare:nNnTF { #1 ; } < \c__fp_rand_size_int
16138   { \fp_to_int:n { #1 ; + 1 } ; \__fp_randint_narrow_e:nnnn }
16139   { \fp_to_int:n { floor(#1 ; * 1e-8 + 1) } ; \__fp_randint_wide_e:nnnn }
16140 }
16141 \cs_new:Npn \__fp_randint_e:wwNnn #1 ; #2 ;
16142 {
16143   \exp_after:wN \__fp_randint_e:wwwNnn
16144   \__int_value:w \int_mod:nn {#1} {#2} ; #1 ; #2 ;
16145 }
16146 \cs_new:Npn \__fp_randint_e:wwwNnn #1 ; #2 ; #3 ; #4
16147 {
16148   \int_compare:nNnTF { #2 - #1 + #3 } > \c__fp_rand_size_int
16149   {
16150     \exp_after:wN \__fp_randint_e:wwNnn
16151     \__int_value:w \__fp_rand_uniform: ; #3 ; #4
16152   }
16153   { #4 {#1} {#3} }
16154 }
16155 \cs_new:Npn \__fp_randint_narrow_e:nnnn #1#2#3#4
16156 { \__fp_parse_o:n { #3 + #1 } \exp:w }
16157 \cs_new:Npn \__fp_randint_wide_e:nnnn #1#2#3#4
16158 {
16159   \exp_after:wN \exp_after:wN
16160   \exp_after:wN \__fp_randint_wide_e:wnnn
16161   \__fp_parse:n { #3 + #1e8 + \__fp_rand_myriads:n { xx } }
16162   {#2} {#3} {#4}
16163 }
16164 \cs_new:Npn \__fp_randint_wide_e:wnnn #1 ; #2#3#4
16165 {
16166   \fp_compare:nNnTF { #1 ; } > {#4}
16167   {
16168     \exp_after:wN \__fp_randint_e:wwNnn
16169     \__int_value:w \__fp_rand_uniform: ; #2 ;
16170     \__fp_randint_wide_e:nnnn {#3} {#4}
16171   }

```

```

16172 { \_fp_exp_after_o:w #1 ; \exp:w }
16173 }

```

(End definition for `\_fp_randint_o:Nw` and others.)

End the initial conditional that ensures these commands are only defined in pdfTeX and LuaTeX.

```

16174 }

```

```

16175 </initex | package>

```

## 32 l3fp-assign implementation

```

16176 <*initex | package>

```

```

16177 <@@=fp>

```

### 32.1 Assigning values

**\fp\_new:N** Floating point variables are initialized to be +0.

```

16178 \cs_new_protected:Npn \fp_new:N #1
16179 { \cs_new_eq:NN #1 \c_zero_fp }
16180 \cs_generate_variant:Nn \fp_new:N {c}

```

(End definition for `\fp_new:N`. This function is documented on page 177.)

**\fp\_set:Nn** Simply use `\_fp_parse:n` within various f-expanding assignments.

```

\fp_set:cn 16181 \cs_new_protected:Npn \fp_set:Nn #1#2
\fp_gset:Nn 16182 { \tl_set:Nx #1 { \exp_not:f { \_fp_parse:n {#2} } } }
\fp_gset:cn 16183 \cs_new_protected:Npn \fp_gset:Nn #1#2
\fp_const:Nn 16184 { \tl_gset:Nx #1 { \exp_not:f { \_fp_parse:n {#2} } } }
\fp_const:cn 16185 \cs_new_protected:Npn \fp_const:Nn #1#2
16186 { \tl_const:Nx #1 { \exp_not:f { \_fp_parse:n {#2} } } }
16187 \cs_generate_variant:Nn \fp_set:Nn {c}
16188 \cs_generate_variant:Nn \fp_gset:Nn {c}
16189 \cs_generate_variant:Nn \fp_const:Nn {c}

```

(End definition for `\fp_set:Nn`, `\fp_gset:Nn`, and `\fp_const:Nn`. These functions are documented on page 177.)

**\fp\_set\_eq:NN** Copying a floating point is the same as copying the underlying token list.

```

\fp_set_eq:cn 16190 \cs_new_eq:NN \fp_set_eq:NN \tl_set_eq:NN
\fp_set_eq:Nc 16191 \cs_new_eq:NN \fp_gset_eq:NN \tl_gset_eq:NN
\fp_set_eq:cc 16192 \cs_generate_variant:Nn \fp_set_eq:NN { c , Nc , cc }
\fp_gset_eq:NN 16193 \cs_generate_variant:Nn \fp_gset_eq:NN { c , Nc , cc }

```

(End definition for `\fp_set_eq:NN` and `\fp_gset_eq:NN`. These functions are documented on page 178.)

**\fp\_gset\_eq:NN** Setting a floating point to zero: copy `\c_zero_fp`.

```

\fp_gset_eq:cn 16194 \cs_new_protected:Npn \fp_zero:N #1 { \fp_set_eq:NN #1 \c_zero_fp }
\fp_gzero:N 16195 \cs_new_protected:Npn \fp_gzero:N #1 { \fp_gset_eq:NN #1 \c_zero_fp }
\fp_gzero:c 16196 \cs_generate_variant:Nn \fp_zero:N { c }
16197 \cs_generate_variant:Nn \fp_gzero:N { c }

```

(End definition for `\fp_zero:N` and `\fp_gzero:N`. These functions are documented on page 177.)

**\fp\_zero\_new:N** Set the floating point to zero, or define it if needed.

**\fp\_zero\_new:c** 16198 \cs\_new\_protected:Npn \fp\_zero\_new:N #1  
**\fp\_gzero\_new:N** 16199 { \fp\_if\_exist:NTF #1 { \fp\_zero:N #1 } { \fp\_new:N #1 } }  
**\fp\_gzero\_new:c** 16200 \cs\_new\_protected:Npn \fp\_gzero\_new:N #1  
16201 { \fp\_if\_exist:NTF #1 { \fp\_gzero:N #1 } { \fp\_new:N #1 } }  
16202 \cs\_generate\_variant:Nn \fp\_zero\_new:N { c }  
16203 \cs\_generate\_variant:Nn \fp\_gzero\_new:N { c }

(End definition for \fp\_zero\_new:N and \fp\_gzero\_new:N. These functions are documented on page 177.)

## 32.2 Updating values

These match the equivalent functions in l3int and l3skip.

**\fp\_add:Nn** For the sake of error recovery we should not simply set #1 to  $\#1 \pm (\#2)$ : for instance, if #2 is 0)+2, the parsing error would be raised at the last closing parenthesis rather than at the closing parenthesis in the user argument. Thus we evaluate #2 instead of just putting parentheses. As an optimization we use `__fp_parse:n` rather than `\fp_eval:n`, which would convert the result away from the internal representation and back.

**\fp\_add:cn** 16204 \cs\_new\_protected:Npn \fp\_add:Nn { \_\_fp\_add:NNNn \fp\_set:Nn + }  
**\fp\_gadd:Nn** 16205 \cs\_new\_protected:Npn \fp\_gadd:Nn { \_\_fp\_add:NNNn \fp\_gset:Nn + }  
**\fp\_sub:Nn** 16206 \cs\_new\_protected:Npn \fp\_sub:Nn { \_\_fp\_add:NNNn \fp\_set:Nn - }  
**\fp\_gsub:Nn** 16207 \cs\_new\_protected:Npn \fp\_gsub:Nn { \_\_fp\_add:NNNn \fp\_gset:Nn - }  
**\fp\_gsub:cn** 16208 \cs\_new\_protected:Npn \_\_fp\_add:NNNn #1#2#3#4  
16209 { #1 #3 { #3 #2 \_\_fp\_parse:n {#4} } }  
16210 \cs\_generate\_variant:Nn \fp\_add:Nn { c }  
16211 \cs\_generate\_variant:Nn \fp\_gadd:Nn { c }  
16212 \cs\_generate\_variant:Nn \fp\_sub:Nn { c }  
16213 \cs\_generate\_variant:Nn \fp\_gsub:Nn { c }

(End definition for \fp\_add:Nn and others. These functions are documented on page 178.)

## 32.3 Showing values

**\fp\_show:N** This shows the result of computing its argument. The input of `__msg_show_variable:NNNnn` must start with `>~` (or be empty).

**\fp\_show:c** 16214 \cs\_new\_protected:Npn \fp\_show:N #1  
**\fp\_show:n** 16215 {  
16216 \_\_msg\_show\_variable:NNNnn #1 \fp\_if\_exist:NTF ? { }  
16217 { > ~ \token\_to\_str:N #1 = \fp\_to\_tl:N #1 }  
16218 }  
16219 \cs\_new\_protected:Npn \fp\_show:n  
16220 { \_\_msg\_show\_wrap:Nn \fp\_to\_tl:n }  
16221 \cs\_generate\_variant:Nn \fp\_show:N { c }

(End definition for \fp\_show:N and \fp\_show:n. These functions are documented on page 184.)

**\fp\_log:N** Redirect output of \fp\_show:N and \fp\_show:n to the log.

**\fp\_log:c** 16222 \cs\_new\_protected:Npn \fp\_log:N  
**\fp\_log:n** 16223 { \_\_msg\_log\_next: \fp\_show:N }  
16224 \cs\_new\_protected:Npn \fp\_log:n  
16225 { \_\_msg\_log\_next: \fp\_show:n }  
16226 \cs\_generate\_variant:Nn \fp\_log:N { c }

(End definition for \fp\_log:N and \fp\_log:n. These functions are documented on page 184.)

## 32.4 Some useful constants and scratch variables

`\c_one_fp` Some constants.

`\c_e_fp` 16227 `\fp_const:Nn \c_e_fp` { 2.718 2818 2845 9045 }  
 16228 `\fp_const:Nn \c_one_fp` { 1 }

(End definition for `\c_one_fp` and `\c_e_fp`. These variables are documented on page 183.)

`\c_pi_fp` We simply round  $\pi$  to and  $\pi/180$  to 16 significant digits.

`\c_one_degree_fp` 16229 `\fp_const:Nn \c_pi_fp` { 3.141 5926 5358 9793 }  
 16230 `\fp_const:Nn \c_one_degree_fp` { 0.0 1745 3292 5199 4330 }

(End definition for `\c_pi_fp` and `\c_one_degree_fp`. These variables are documented on page 183.)

`\l_tmpa_fp` Scratch variables are simply initialized there.

`\l_tmpb_fp` 16231 `\fp_new:N \l_tmpa_fp`  
`\g_tmpa_fp` 16232 `\fp_new:N \l_tmpb_fp`  
`\g_tmpb_fp` 16233 `\fp_new:N \g_tmpa_fp`  
 16234 `\fp_new:N \g_tmpb_fp`

(End definition for `\l_tmpa_fp` and others. These variables are documented on page 183.)

16235 `\</initex | package>`

## 33 l3sort implementation

16236 `\*initex | package>`

16237 `\<@@=sort>`

### 33.1 Variables

`\l__sort_length_int` The sequence has `\l__sort_length_int` items and is stored from `\l__sort_min_int`  
`\l__sort_min_int` to `\l__sort_top_int - 1`. While reading the sequence in memory, we check that  
`\l__sort_top_int` `\l__sort_top_int` remains at most `\l__sort_max_int`, precomputed by `\__sort_-`  
`\l__sort_max_int` `compute_range:.` That bound is such that the merge sort only uses `\toks` registers  
`\l__sort_true_max_int` less than `\l__sort_true_max_int`, namely those that have not been allocated for use in  
 other code: the user's comparison code could alter these.

16238 `\int_new:N \l__sort_length_int`  
 16239 `\int_new:N \l__sort_min_int`  
 16240 `\int_new:N \l__sort_top_int`  
 16241 `\int_new:N \l__sort_max_int`  
 16242 `\int_new:N \l__sort_true_max_int`

(End definition for `\l__sort_length_int` and others.)

`\l__sort_block_int` Merge sort is done in several passes. In each pass, blocks of size `\l__sort_block_int` are  
 merged in pairs. The block size starts at 1, and, for a length in the range  $[2^k + 1, 2^{k+1}]$ ,  
 reaches  $2^k$  in the last pass.

16243 `\int_new:N \l__sort_block_int`

(End definition for `\l__sort_block_int`.)



`\l__sort_begin_int` When merging two blocks, `\l__sort_begin_int` marks the lowest index in the two blocks, and `\l__sort_end_int` marks the highest index, plus 1.

16244 `\int_new:N \l__sort_begin_int`

16245 `\int_new:N \l__sort_end_int`

(End definition for `\l__sort_begin_int` and `\l__sort_end_int`.)

`\l__sort_A_int` When merging two blocks (whose end-points are `beg` and `end`),  $A$  starts from the high end of the low block, and decreases until reaching `beg`. The index  $B$  starts from the top of the range and marks the register in which a sorted item should be put. Finally,  $C$  points to the copy of the high block in the interval of registers starting at `\l__sort_length_int`, upwards.  $C$  starts from the upper limit of that range.

16246 `\int_new:N \l__sort_A_int`

16247 `\int_new:N \l__sort_B_int`

16248 `\int_new:N \l__sort_C_int`

(End definition for `\l__sort_A_int`, `\l__sort_B_int`, and `\l__sort_C_int`.)

### 33.2 Finding available `\toks` registers

`\__sort_shrink_range:` After `\__sort_compute_range:` (defined below) determines that `\toks` registers between `\l__sort_min_int` (included) and `\l__sort_true_max_int` (excluded) have not yet been assigned, `\__sort_shrink_range:` computes `\l__sort_max_int` to reflect the need for a buffer when merging blocks in the merge sort. Given  $2^n \leq A \leq 2^n + 2^{n-1}$  registers we can sort  $\lfloor A/2 \rfloor + 2^{n-2}$  items while if we have  $2^n + 2^{n-1} \leq A \leq 2^{n+1}$  registers we can sort  $A - 2^{n-1}$  items. We first find out a power  $2^n$  such that  $2^n \leq A \leq 2^{n+1}$  by repeatedly halving `\l__sort_block_int`, starting at  $2^{15}$  or  $2^{14}$  namely half the total number of registers, then we use the formulas and set `\l__sort_max_int`.

16249 `\cs_new_protected:Npn \__sort_shrink_range:`

16250 `{`

16251 `\int_set:Nn \l__sort_A_int`

16252 `{ \l__sort_true_max_int - \l__sort_min_int + 1 }`

16253 `\int_set:Nn \l__sort_block_int { \c_max_register_int / 2 }`

16254 `\__sort_shrink_range_loop:`

16255 `\int_set:Nn \l__sort_max_int`

16256 `{`

16257 `\int_compare:nNnTF`

16258 `{ \l__sort_block_int * 3 / 2 } > \l__sort_A_int`

16259 `{`

16260 `\l__sort_min_int`

16261 `+ ( \l__sort_A_int - 1 ) / 2`

16262 `+ \l__sort_block_int / 4`

16263 `- 1`

16264 `}`

16265 `{ \l__sort_true_max_int - \l__sort_block_int / 2 }`

16266 `}`

16267 `}`

16268 `\cs_new_protected:Npn \__sort_shrink_range_loop:`

16269 `{`

16270 `\if_int_compare:w \l__sort_A_int < \l__sort_block_int`

16271 `\tex_divide:D \l__sort_block_int 2 \exp_stop_f:`

16272 `\exp_after:wN \__sort_shrink_range_loop:`

16273 `\fi:`

```
16274 }
```

(End definition for `\_sort_shrink_range:` and `\_sort_shrink_range_loop:`)

`\_sort_compute_range:` First find out what `\toks` have not yet been assigned. There are many cases. In L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> with no package, available `\toks` range from `\count15 + 1` to `\c_max_register_int` included (this was not altered despite the 2015 changes). When `\loctoks` is defined, namely in plain (e)T<sub>E</sub>X, or when the package `etex` is loaded in L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>, redefine `\_sort_compute_range:` to use the range `\count265` to `\count275 - 1`. The `elocalloc` package also defines `\loctoks` but uses yet another number for the upper bound, namely `\e@alloc@top` (minus one). We must check for `\loctoks` every time a sorting function is called, as `etex` or `elocalloc` could be loaded.

In ConT<sub>E</sub>Xt MkIV the range is from `\c_syst_last_allocated_toks + 1` to `\c_max_register_int`, and in MkII it is from `\lastallocatedtoks + 1` to `\c_max_register_int`. In all these cases, call `\_sort_shrink_range:`. The L<sup>A</sup>T<sub>E</sub>X 3 format mode is easiest: no `\toks` are ever allocated so available `\toks` range from 0 to `\c_max_register_int` and we precompute the result of `\_sort_shrink_range:`.

```
16275 (*package)
16276 \cs_new_protected:Npn \_sort_compute_range:
16277 {
16278   \int_set:Nn \l__sort_min_int { \tex_count:D 15 + 1 }
16279   \int_set:Nn \l__sort_true_max_int { \c_max_register_int + 1 }
16280   \_sort_shrink_range:
16281   \if_meaning:w \loctoks \tex_undefined:D \else:
16282     \if_meaning:w \loctoks \scan_stop: \else:
16283       \_sort_redefine_compute_range:
16284       \_sort_compute_range:
16285     \fi:
16286   \fi:
16287 }
16288 \cs_new_protected:Npn \_sort_redefine_compute_range:
16289 {
16290   \cs_if_exist:cTF { ver@elocalloc.sty }
16291   {
16292     \cs_gset_protected:Npn \_sort_compute_range:
16293     {
16294       \int_set:Nn \l__sort_min_int { \tex_count:D 265 }
16295       \int_set_eq:NN \l__sort_true_max_int \e@alloc@top
16296       \_sort_shrink_range:
16297     }
16298   }
16299   {
16300     \cs_gset_protected:Npn \_sort_compute_range:
16301     {
16302       \int_set:Nn \l__sort_min_int { \tex_count:D 265 }
16303       \int_set:Nn \l__sort_true_max_int { \tex_count:D 275 }
16304       \_sort_shrink_range:
16305     }
16306   }
16307 }
16308 \cs_if_exist:NT \loctoks { \_sort_redefine_compute_range: }
16309 \tl_map_inline:nn { \lastallocatedtoks \c_syst_last_allocated_toks }
16310 {
```

```

16311 \cs_if_exist:NT #1
16312 {
16313   \cs_gset_protected:Npn \__sort_compute_range:
16314   {
16315     \int_set:Nn \l__sort_min_int { #1 + 1 }
16316     \int_set:Nn \l__sort_true_max_int { \c_max_register_int + 1 }
16317     \__sort_shrink_range:
16318   }
16319 }
16320 }
16321 \</package>
16322 \<*initex>
16323 \int_const:Nn \c__sort_max_length_int
16324 { ( \c_max_register_int + 1 ) * 3 / 4 }
16325 \cs_new_protected:Npn \__sort_compute_range:
16326 {
16327   \int_set:Nn \l__sort_min_int { 0 }
16328   \int_set:Nn \l__sort_true_max_int { \c_max_register_int + 1 }
16329   \int_set:Nn \l__sort_max_int { \c__sort_max_length_int }
16330 }
16331 \</initex>

```

(End definition for `\__sort_compute_range:`, `\__sort_redefine_compute_range:`, and `\c__sort_max_length_int`.)

### 33.3 Protected user commands

`\__sort_main:NNNnNn` Sorting happens in three steps. First store items in `\toks` registers ranging from `\l__sort_min_int` to `\l__sort_top_int - 1`, while checking that the list is not too long. If we reach the maximum length, all further items are entirely ignored after raising an error. Secondly, sort the array of `\toks` registers, using the user-defined sorting function, #6. Finally, unpack the `\toks` registers (now sorted) into a variable of the right type, by x-expanding the code in #4, specific to each type of list.

```

16332 \cs_new_protected:Npn \__sort_main:NNNnNn #1#2#3#4#5#6
16333 {
16334   \group_begin:
16335   \<package> \__sort_disable_toksdef:
16336   \__sort_compute_range:
16337   \int_set_eq:NN \l__sort_top_int \l__sort_min_int
16338   #2 #5
16339   {
16340     \if_int_compare:w \l__sort_top_int = \l__sort_max_int
16341     \__sort_too_long_error:NNw #3 #5
16342     \fi:
16343     \tex_toks:D \l__sort_top_int {##1}
16344     \int_incr:N \l__sort_top_int
16345   }
16346   \int_set:Nn \l__sort_length_int
16347   { \l__sort_top_int - \l__sort_min_int }
16348   \cs_set:Npn \__sort_compare:nn ##1 ##2 { #6 }
16349   \int_set:Nn \l__sort_block_int { 1 }
16350   \__sort_level:
16351   \use:x
16352   {

```

```

16353         \group_end:
16354         #1 \exp_not:N #5 {#4}
16355     }
16356 }

```

(End definition for `\__sort_main:NNNnNn`.)

`\seq_sort:Nn` The first argument to `\__sort_main:NNNnNn` is the final assignment function used, either `\tl_set:Nn` or `\tl_gset:Nn` to control local versus global results. The second argument is what mapping function is used when storing items to `\toks` registers, and the third breaks away from the loop. The fourth is used to build back the correct kind of list from the contents of the `\toks` registers, including the leading `\s__seq`. Fifth and sixth arguments are the variable to sort, and the sorting method as inline code.

```

16357 \cs_new_protected:Npn \seq_sort:Nn
16358 {
16359     \__sort_main:NNNnNn \tl_set:Nn
16360     \seq_map_inline:Nn \seq_map_break:n
16361     { \s__seq \__sort_toks:NN \exp_not:N \__seq_item:n }
16362 }
16363 \cs_generate_variant:Nn \seq_sort:Nn { c }
16364 \cs_new_protected:Npn \seq_gsort:Nn
16365 {
16366     \__sort_main:NNNnNn \tl_gset:Nn
16367     \seq_map_inline:Nn \seq_map_break:n
16368     { \s__seq \__sort_toks:NN \exp_not:N \__seq_item:n }
16369 }
16370 \cs_generate_variant:Nn \seq_gsort:Nn { c }

```

(End definition for `\seq_sort:Nn` and `\seq_gsort:Nn`. These functions are documented on page 61.)

`\tl_sort:Nn` Again, use `\tl_set:Nn` or `\tl_gset:Nn` to control the scope of the assignment. Mapping through the token list is done with `\tl_map_inline:Nn`, and producing the token list is very similar to sequences, removing `\__seq_item:n`.

```

16371 \cs_new_protected:Npn \tl_sort:Nn
16372 {
16373     \__sort_main:NNNnNn \tl_set:Nn
16374     \tl_map_inline:Nn \tl_map_break:n
16375     { \__sort_toks:NN \prg_do_nothing: \prg_do_nothing: }
16376 }
16377 \cs_generate_variant:Nn \tl_sort:Nn { c }
16378 \cs_new_protected:Npn \tl_gsort:Nn
16379 {
16380     \__sort_main:NNNnNn \tl_gset:Nn
16381     \tl_map_inline:Nn \tl_map_break:n
16382     { \__sort_toks:NN \prg_do_nothing: \prg_do_nothing: }
16383 }
16384 \cs_generate_variant:Nn \tl_gsort:Nn { c }

```

(End definition for `\tl_sort:Nn` and `\tl_gsort:Nn`. These functions are documented on page 43.)

`\clist_sort:Nn` The case of empty comma-lists is a little bit special as usual, and filtered out: there is nothing to sort in that case. Otherwise, the input is done with `\clist_map_inline:Nn`, and the output requires some more elaborate processing than for sequences and token lists. The first comma must be removed. An item must be wrapped in an extra set

`\__sort_clist:NNn`

of braces if it contains either the space or the comma characters. This is taken care of by `\clist_wrap_item:n`, but `\__sort_toks:NN` would simply feed `\tex_the:D \tex_toks:D ⟨number⟩` as an argument to that function; hence we need to expand this argument once to unpack the register.

```

16385 \cs_new_protected:Npn \clist_sort:Nn
16386 { \__sort_clist:NNn \tl_set:Nn }
16387 \cs_new_protected:Npn \clist_gsort:Nn
16388 { \__sort_clist:NNn \tl_gset:Nn }
16389 \cs_generate_variant:Nn \clist_sort:Nn { c }
16390 \cs_generate_variant:Nn \clist_gsort:Nn { c }
16391 \cs_new_protected:Npn \__sort_clist:NNn #1#2#3
16392 {
16393   \clist_if_empty:NF #2
16394   {
16395     \__sort_main:NNNnNn #1
16396     \clist_map_inline:Nn \clist_map_break:n
16397     {
16398       \exp_last_unbraced:Nf \use_none:n
16399       { \__sort_toks:NN \exp_args:No \__clist_wrap_item:n }
16400     }
16401     #2 {#3}
16402   }
16403 }

```

(End definition for `\clist_sort:Nn`, `\clist_gsort:Nn`, and `\__sort_clist:NNn`. These functions are documented on page 101.)

`\__sort_toks:NN` Unpack the various `\toks` registers, from `\l__sort_min_int` to `\l__sort_top_int - 1`.  
`\__sort_toks:NNw` The functions #1 and #2 allow us to treat the three data structures in a unified way:

- for sequences, they are `\exp_not:N \__seq_item:n`, expanding to the `\__seq_item:n` separator, as expected;
- for token lists, they expand to nothing;
- for comma lists, they expand to `\exp_args:No \clist_wrap_item:n`, taking care of unpacking the register before letting the undocumented internal `clist` function `\clist_wrap_item:n` do the work of putting a comma and possibly braces.

```

16404 \cs_new:Npn \__sort_toks:NN #1#2
16405 { \__sort_toks:NNw #1 #2 \l__sort_min_int ; }
16406 \cs_new:Npn \__sort_toks:NNw #1#2#3 ;
16407 {
16408   \if_int_compare:w #3 < \l__sort_top_int
16409   #1 #2 { \tex_the:D \tex_toks:D #3 }
16410   \exp_after:wN \__sort_toks:NNw \exp_after:wN #1 \exp_after:wN #2
16411   \__int_value:w \__int_eval:w #3 + 1 \exp_after:wN ;
16412   \fi:
16413 }

```

(End definition for `\__sort_toks:NN` and `\__sort_toks:NNw`.)

### 33.4 Merge sort

**\\_\_sort\_level:** This function is called once blocks of size `\l__sort_block_int` (initially 1) are each sorted. If the whole list fits in one block, then we are done (this also takes care of the case of an empty list or a list with one item). Otherwise, go through pairs of blocks starting from 0, then double the block size, and repeat.

```

16414 \cs_new_protected:Npn \__sort_level:
16415 {
16416   \if_int_compare:w \l__sort_block_int < \l__sort_length_int
16417     \l__sort_end_int \l__sort_min_int
16418     \__sort_merge_blocks:
16419     \tex_advance:D \l__sort_block_int \l__sort_block_int
16420     \exp_after:wN \__sort_level:
16421   \fi:
16422 }
```

(End definition for `\__sort_level:.`)

**\\_\_sort\_merge\_blocks:** This function is called to merge a pair of blocks, starting at the last value of `\l__sort_end_int` (end-point of the previous pair of blocks). If shifting by one block to the right we reach the end of the list, then this pass has ended: the end of the list is sorted already. Otherwise, store the result of that shift in *A*, which indexes the first block starting from the top end. Then locate the end-point (maximum) of the second block: shift *end* upwards by one more block, but keeping it  $\leq$  *top*. Copy this upper block of `\toks` registers in registers above *length*, indexed by *C*: this is covered by `\__sort_copy_block:.` Once this is done we are ready to do the actual merger using `\__sort_merge_blocks_aux:`, after shifting *A*, *B* and *C* so that they point to the largest index in their respective ranges rather than pointing just beyond those ranges. Of course, once that pair of blocks is merged, move on to the next pair.

```

16423 \cs_new_protected:Npn \__sort_merge_blocks:
16424 {
16425   \l__sort_begin_int \l__sort_end_int
16426   \tex_advance:D \l__sort_end_int \l__sort_block_int
16427   \if_int_compare:w \l__sort_end_int < \l__sort_top_int
16428     \l__sort_A_int \l__sort_end_int
16429     \tex_advance:D \l__sort_end_int \l__sort_block_int
16430     \if_int_compare:w \l__sort_end_int > \l__sort_top_int
16431       \l__sort_end_int \l__sort_top_int
16432     \fi:
16433     \l__sort_B_int \l__sort_A_int
16434     \l__sort_C_int \l__sort_top_int
16435     \__sort_copy_block:
16436     \int_decr:N \l__sort_A_int
16437     \int_decr:N \l__sort_B_int
16438     \int_decr:N \l__sort_C_int
16439     \exp_after:wN \__sort_merge_blocks_aux:
16440     \exp_after:wN \__sort_merge_blocks:
16441   \fi:
16442 }
```

(End definition for `\__sort_merge_blocks:.`)

`\__sort_copy_block:` We wish to store a copy of the “upper” block of `\toks` registers, ranging between the initial value of `\l__sort_B_int` (included) and `\l__sort_end_int` (excluded) into a new range starting at the initial value of `\l__sort_C_int`, namely `\l__sort_top_int`.

```

16443 \cs_new_protected:Npn \__sort_copy_block:
16444 {
16445   \tex_toks:D \l__sort_C_int \tex_toks:D \l__sort_B_int
16446   \int_incr:N \l__sort_C_int
16447   \int_incr:N \l__sort_B_int
16448   \if_int_compare:w \l__sort_B_int = \l__sort_end_int
16449     \use_i:nn
16450   \fi:
16451   \__sort_copy_block:
16452 }

```

(End definition for `\__sort_copy_block:`.)

`\__sort_merge_blocks_aux:` At this stage, the first block starts at `\l__sort_begin_int`, and ends at `\l__sort_A_int`, and the second block starts at `\l__sort_top_int` and ends at `\l__sort_C_int`. The result of the merger is stored at positions indexed by `\l__sort_B_int`, which starts at `\l__sort_end_int - 1` and decreases down to `\l__sort_begin_int`, covering the full range of the two blocks. In other words, we are building the merger starting with the largest values. The comparison function is defined to return either `swapped` or `same`. Of course, this means the arguments need to be given in the order they appear originally in the list.

```

16453 \cs_new_protected:Npn \__sort_merge_blocks_aux:
16454 {
16455   \exp_after:wN \__sort_compare:nn \exp_after:wN
16456   { \tex_the:D \tex_toks:D \exp_after:wN \l__sort_A_int \exp_after:wN }
16457   \exp_after:wN { \tex_the:D \tex_toks:D \l__sort_C_int }
16458   \prg_do_nothing:
16459   \__sort_return_mark:N
16460   \__sort_return_mark:N
16461   \__sort_return_none_error:
16462 }

```

(End definition for `\__sort_merge_blocks_aux:`.)

`\sort_return_same:` The marker removes one token. Each comparison should call `\sort_return_same:` or `\sort_return_swapped:` exactly once. If neither is called, `\__sort_return_none_error:` is called.

```

\__sort_return_swapped:
\__sort_return_mark:N
\__sort_return_none_error:
\__sort_return_two_error:w
16463 \cs_new_protected:Npn \sort_return_same: #1 \__sort_return_mark:N
16464 { #1 \__sort_return_mark:N \__sort_return_two_error:w \__sort_return_same: }
16465 \cs_new_protected:Npn \sort_return_swapped: #1 \__sort_return_mark:N
16466 { #1 \__sort_return_mark:N \__sort_return_two_error:w \__sort_return_swapped: }
16467 \cs_new_protected:Npn \__sort_return_mark:N #1 { }
16468 \cs_new_protected:Npn \__sort_return_none_error:
16469 {
16470   \__msg_kernel_error:nxxx { kernel } { return-none }
16471   { \tex_the:D \tex_toks:D \l__sort_A_int }
16472   { \tex_the:D \tex_toks:D \l__sort_C_int }
16473   \__sort_return_same:
16474 }
16475 \cs_new_protected:Npn \__sort_return_two_error:w

```

```

16476      #1 \__sort_return_none_error:
16477      { \__msg_kernel_error:nn { kernel } { return-two } }

```

(End definition for \sort\_return\_same: and others. These functions are documented on page ??.)

**\\_\_sort\_return\_same:** If the comparison function returns **same**, then the second argument fed to **\\_\_sort\_compare:nn** should remain to the right of the other one. Since we build the merger starting from the right, we copy that **\toks** register into the allotted range, then shift the pointers *B* and *C*, and go on to do one more step in the merger, unless the second block has been exhausted: then the remainder of the first block is already in the correct registers and we are done with merging those two blocks.

```

16478 \cs_new_protected:Npn \__sort_return_same:
16479 {
16480   \tex_toks:D \l__sort_B_int \tex_toks:D \l__sort_C_int
16481   \int_decr:N \l__sort_B_int
16482   \int_decr:N \l__sort_C_int
16483   \if_int_compare:w \l__sort_C_int < \l__sort_top_int
16484     \use_i:nn
16485   \fi:
16486   \__sort_merge_blocks_aux:
16487 }

```

(End definition for \\_\_sort\_return\_same:.)

**\\_\_sort\_return\_swapped:** If the comparison function returns **swapped**, then the next item to add to the merger is the first argument, contents of the **\toks** register *A*. Then shift the pointers *A* and *B* to the left, and go for one more step for the merger, unless the left block was exhausted (*A* goes below the threshold). In that case, all remaining **\toks** registers in the second block, indexed by *C*, are copied to the merger by **\\_\_sort\_merge\_blocks\_end:.**

```

16488 \cs_new_protected:Npn \__sort_return_swapped:
16489 {
16490   \tex_toks:D \l__sort_B_int \tex_toks:D \l__sort_A_int
16491   \int_decr:N \l__sort_B_int
16492   \int_decr:N \l__sort_A_int
16493   \if_int_compare:w \l__sort_A_int < \l__sort_begin_int
16494     \__sort_merge_blocks_end: \use_i:nn
16495   \fi:
16496   \__sort_merge_blocks_aux:
16497 }

```

(End definition for \\_\_sort\_return\_swapped:.)

**\\_\_sort\_merge\_blocks\_end:** This function's task is to copy the **\toks** registers in the block indexed by *C* to the merger indexed by *B*. The end can equally be detected by checking when *B* reaches the threshold **begin**, or when *C* reaches **top**.

```

16498 \cs_new_protected:Npn \__sort_merge_blocks_end:
16499 {
16500   \tex_toks:D \l__sort_B_int \tex_toks:D \l__sort_C_int
16501   \int_decr:N \l__sort_B_int
16502   \int_decr:N \l__sort_C_int
16503   \if_int_compare:w \l__sort_B_int < \l__sort_begin_int
16504     \use_i:nn
16505   \fi:
16506   \__sort_merge_blocks_end:
16507 }

```



(End definition for `\_sort_merge_blocks_end:`.)

### 33.5 Expandable sorting

Sorting expandably is very different from sorting and assigning to a variable. Since tokens cannot be stored, they must remain in the input stream, and be read through at every step. It is thus necessarily much slower (at best  $O(n^2 \ln n)$ ) than non-expandable sorting functions ( $O(n \ln n)$ ).

A prototypical version of expandable quicksort is as follows. If the argument has no item, return nothing, otherwise partition, using the first item as a pivot (argument #4 of `\_sort:nnNnn`). The arguments of `\_sort:nnNnn` are 1. items less than #4, 2. items greater or equal to #4, 3. comparison, 4. pivot, 5. next item to test. If #5 is the tail of the list, call `\tl_sort:nN` on #1 and on #2, placing #4 in between; `\use:ff` expands the parts to make `\tl_sort:nN` f-expandable. Otherwise, compare #4 and #5 using #3. If they are ordered, place #5 amongst the “greater” items, otherwise amongst the “lesser” items, and continue partitioning.

```
\cs_new:Npn \tl_sort:nN #1#2
{
  \tl_if_blank:nF {#1}
  {
    \_sort:nnNnn { } { } #2
    #1 \q_recursion_tail \q_recursion_stop
  }
}
\cs_new:Npn \_sort:nnNnn #1#2#3#4#5
{
  \quark_if_recursion_tail_stop_do:nn {#5}
  { \use:ff { \tl_sort:nN {#1} #3 {#4} } { \tl_sort:nN {#2} #3 } }
  #3 {#4} {#5}
  { \_sort:nnNnn {#1} { #2 {#5} } #3 {#4} }
  { \_sort:nnNnn { #1 {#5} } {#2} #3 {#4} }
}
\cs_generate_variant:Nn \use:nn { ff }
```

There are quite a few optimizations available here: the code below is less legible, but more than twice as fast.

In the simple version of the code, `\_sort:nnNnn` is called  $O(n \ln n)$  times on average (the number of comparisons required by the quicksort algorithm). Hence most of our focus is on optimizing that function.

The first speed up is to avoid testing for the end of the list at every call to `\_sort:nnNnn`. For this, the list is prepared by changing each  $\langle item \rangle$  of the original token list into  $\langle command \rangle \{ \langle item \rangle \}$ , just like sequences are stored. We arrange things such that the  $\langle command \rangle$  is the  $\langle conditional \rangle$  provided by the user: the loop over the  $\langle prepared tokens \rangle$  then looks like

```
\cs_new:Npn \_sort_loop:wNn ... #6#7
{
  #6 { \pivot } { #7 } \loop big \loop small
  \extra arguments
}
```

```

    \_sort_loop:wNn ... <prepared tokens>
    <end-loop> {} \q_stop

```

In this example, which matches the structure of `\_sort_quick_split_i:NnnnnNn` and a few other functions below, the `\_sort_loop:wNn` auxiliary normally receives the user's `<conditional>` as #6 and an `<item>` as #7. This is compared to the `<pivot>` (the argument #5, not shown here), and the `<conditional>` leaves the `<loop big>` or `<loop small>` auxiliary, which both have the same form as `\_sort_loop:wNn`, receiving the next pair `<conditional> {<item>}` as #6 and #7. At the end, #6 is the `<end-loop>` function, which terminates the loop.

The second speed up is to minimize the duplicated tokens between the `true` and `false` branches of the conditional. For this, we introduce two versions of `\_sort:nnnnNn`, which receive the new item as #1 and place it either into the list #2 of items less than the pivot #4 or into the list #3 of items greater or equal to the pivot.

```

\cs_new:Npn \_sort_i:nnnnNn #1#2#3#4#5#6
{
    #5 {#4} {#6} \_sort_ii:nnnnNn \_sort_i:nnnnNn
    {#6} { #2 {#1} } {#3} {#4}
}
\cs_new:Npn \_sort_ii:nnnnNn #1#2#3#4#5#6
{
    #5 {#4} {#6} \_sort_ii:nnnnNn \_sort_i:nnnnNn
    {#6} {#2} { #3 {#1} } {#4}
}

```

Note that the two functions have the form of `\_sort_loop:wNn` above, receiving as #5 the conditional or a function to end the loop. In fact, the lists #2 and #3 must be made of pairs `<conditional> {<item>}`, so we have to replace {#6} above by { #5 {#6} }, and {#1} by #1. The actual functions have one more argument, so all argument numbers are shifted compared to this code.

The third speed up is to avoid `\use:ff` using a continuation-passing style: `\_sort_quick_split:NnNn` expects a list followed by `\q_mark {<code>}`, and expands to `<code> <sorted list>`. Sorting the two parts of the list around the pivot is done with

```

\_sort_quick_split:NnNn #2 ... \q_mark
{
    \_sort_quick_split:NnNn #1 ... \q_mark {<code>}
    {<pivot>}
}

```

Items which are larger than the `<pivot>` are sorted, then placed after code that sorts the smaller items, and after the (braced) `<pivot>`.

The fourth speed up is avoid the recursive call to `\tl_sort:nN` with an empty first argument. For this, we introduce functions similar to the `\_sort_i:nnnnNn` of the last example, but aware of whether the list of `<conditional> {<item>}` read so far that are less than the pivot, and the list of those greater or equal, are empty or not: see `\_sort_quick_split:NnNn` and functions defined below. Knowing whether the lists are empty or not is useless if we do not use distinct ending codes as appropriate. The splitting auxiliaries communicate to the `<end-loop>` function (that is initially placed after the “prepared” list) by placing a specific ending function, ignored when looping, but useful at the end. In fact, the `<end-loop>` function does nothing but place the appropriate

ending function in front of all its arguments. The ending functions take care of sorting non-empty sublists, placing the pivot in between, and the continuation before.

The final change in fact slows down the code a little, but is required to avoid memory issues: schematically, when `TEX` encounters

```
\use:n { \use:n { \use:n { ... } ... } ... }
```

the argument of the first `\use:n` is not completely read by the second `\use:n`, hence must remain in memory; then the argument of the second `\use:n` is not completely read when grabbing the argument of the third `\use:n`, hence must remain in memory, and so on. The memory consumption grows quadratically with the number of nested `\use:n`. In practice, this means that we must read everything until a trailing `\q_stop` once in a while, otherwise sorting lists of more than a few thousand items would exhaust a typical `TEX`'s memory.

`\tl_sort:nN`

```
\__sort_quick_prepare:Nnnn
  \__sort_quick_prepare_end:NNNnw
  \__sort_quick_cleanup:w
```

The code within the `\exp_not:f` sorts the list, leaving in most cases a leading `\exp_not:f`, which stops the expansion, letting the result be return within `\exp_not:n`. We filter out the case of a list with no item, which would otherwise cause problems. Then prepare the token list #1 by inserting the conditional #2 before each item. The `prepare` auxiliary receives the conditional as #1, the prepared token list so far as #2, the next prepared item as #3, and the item after that as #4. The loop ends when #4 contains `\__prg_break_point:`, then the `prepare_end` auxiliary finds the prepared token list as #4. The scene is then set up for `\__sort_quick_split:NnNn`, which sorts the prepared list and perform the post action placed after `\q_mark`, namely removing the trailing `\s__stop` and `\q_stop` and leaving `\exp_stop_f:` to stop `f`-expansion.

```
16508 \cs_new:Npn \tl_sort:nN #1#2
16509 {
16510   \exp_not:f
16511   {
16512     \tl_if_blank:nF {#1}
16513     {
16514       \__sort_quick_prepare:Nnnn #2 { } { }
16515       #1
16516       { \__prg_break_point: \__sort_quick_prepare_end:NNNnw }
16517       \q_stop
16518     }
16519   }
16520 }
16521 \cs_new:Npn \__sort_quick_prepare:Nnnn #1#2#3#4
16522 {
16523   \__prg_break: #4 \__prg_break_point:
16524   \__sort_quick_prepare:Nnnn #1 { #2 #3 } { #1 {#4} }
16525 }
16526 \cs_new:Npn \__sort_quick_prepare_end:NNNnw #1#2#3#4#5 \q_stop
16527 {
16528   \__sort_quick_split:NnNn #4 \__sort_quick_end:nnTFNn { }
16529   \q_mark { \__sort_quick_cleanup:w \exp_stop_f: }
16530   \s__stop \q_stop
16531 }
16532 \cs_new:Npn \__sort_quick_cleanup:w #1 \s__stop \q_stop {#1}
```

(End definition for `\tl_sort:nN` and others. These functions are documented on page 43.)

```

\__sort_quick_split:NnNn
\__sort_quick_only_i:NnnnnNn
\__sort_quick_only_ii:NnnnnNn
\__sort_quick_split_i:NnnnnNn
\__sort_quick_split_ii:NnnnnNn

```

The `only_i`, `only_ii`, `split_i` and `split_ii` auxiliaries receive a useless first argument, the new item #2 (that they append to either one of the next two arguments), the list #3 of items less than the pivot, bigger items #4, the pivot #5, a *function* #6, and an item #7. The *function* is the user's *conditional* except at the end of the list where it is `\__sort_quick_end:nnTFNn`. The comparison is applied to the *pivot* and the *item*, and calls the `only_i` or `split_i` auxiliaries if the *item* is smaller, and the `only_ii` or `split_ii` auxiliaries otherwise. In both cases, the next auxiliary goes to work right away, with no intermediate expansion that would slow down operations. Note that the argument #2 left for the next call has the form *conditional* {*item*}, so that the lists #3 and #4 keep the right form to be fed to the next sorting function. The `split` auxiliary differs from these in that it is missing three of the arguments, which would be empty, and its first argument is always the user's *conditional* rather than an ending function.

```

16533 \cs_new:Npn \__sort_quick_split:NnNn #1#2#3#4
16534 {
16535   #3 {#2} {#4} \__sort_quick_only_ii:NnnnnNn \__sort_quick_only_i:NnnnnNn
16536   \__sort_quick_single_end:nnnwnw
16537   { #3 {#4} } { } { } {#2}
16538 }
16539 \cs_new:Npn \__sort_quick_only_i:NnnnnNn #1#2#3#4#5#6#7
16540 {
16541   #6 {#5} {#7} \__sort_quick_split_ii:NnnnnNn \__sort_quick_only_i:NnnnnNn
16542   \__sort_quick_only_i_end:nnnwnw
16543   { #6 {#7} } { #3 #2 } { } {#5}
16544 }
16545 \cs_new:Npn \__sort_quick_only_ii:NnnnnNn #1#2#3#4#5#6#7
16546 {
16547   #6 {#5} {#7} \__sort_quick_only_ii:NnnnnNn \__sort_quick_split_i:NnnnnNn
16548   \__sort_quick_only_ii_end:nnnwnw
16549   { #6 {#7} } { } { #4 #2 } {#5}
16550 }
16551 \cs_new:Npn \__sort_quick_split_i:NnnnnNn #1#2#3#4#5#6#7
16552 {
16553   #6 {#5} {#7} \__sort_quick_split_ii:NnnnnNn \__sort_quick_split_i:NnnnnNn
16554   \__sort_quick_split_end:nnnwnw
16555   { #6 {#7} } { #3 #2 } {#4} {#5}
16556 }
16557 \cs_new:Npn \__sort_quick_split_ii:NnnnnNn #1#2#3#4#5#6#7
16558 {
16559   #6 {#5} {#7} \__sort_quick_split_ii:NnnnnNn \__sort_quick_split_i:NnnnnNn
16560   \__sort_quick_split_end:nnnwnw
16561   { #6 {#7} } {#3} { #4 #2 } {#5}
16562 }

```

(End definition for `\__sort_quick_split:NnNn` and others.)

```

\__sort_quick_end:nnTFNn
\__sort_quick_single_end:nnnwnw
\__sort_quick_only_i_end:nnnwnw
\__sort_quick_only_ii_end:nnnwnw
\__sort_quick_split_end:nnnwnw

```

The `\__sort_quick_end:nnTFNn` appears instead of the user's conditional, and receives as its arguments the pivot #1, a fake item #2, a `true` and a `false` branches #3 and #4, followed by an ending function #5 (one of the four auxiliaries here) and another copy #6 of the fake item. All those are discarded except the function #5. This function receives lists #1 and #2 of items less than or greater than the pivot #3, then a continuation code #5 just after `\q_mark`. To avoid a memory problem described earlier, all of the ending functions read #6 until `\q_stop` and place #6 back into the input stream. When the lists #1 and #2 are empty, the `single` auxiliary simply places the continuation #5

before the pivot {#3}. When #2 is empty, #1 is sorted and placed before the pivot {#3}, taking care to feed the continuation #5 as a continuation for the function sorting #1. When #1 is empty, #2 is sorted, and the continuation argument is used to place the continuation #5 and the pivot {#3} before the sorted result. Finally, when both lists are non-empty, items larger than the pivot are sorted, then items less than the pivot, and the continuations are done in such a way to place the pivot in between.

```

16563 \cs_new:Npn \__sort_quick_end:nnTFNn #1#2#3#4#5#6 {#5}
16564 \cs_new:Npn \__sort_quick_single_end:nnnwnw #1#2#3#4 \q_mark #5#6 \q_stop
16565 { #5 {#3} #6 \q_stop }
16566 \cs_new:Npn \__sort_quick_only_i_end:nnnwnw #1#2#3#4 \q_mark #5#6 \q_stop
16567 {
16568   \__sort_quick_split:NnNn #1
16569   \__sort_quick_end:nnTFNn { } \q_mark {#5}
16570   {#3}
16571   #6 \q_stop
16572 }
16573 \cs_new:Npn \__sort_quick_only_ii_end:nnnwnw #1#2#3#4 \q_mark #5#6 \q_stop
16574 {
16575   \__sort_quick_split:NnNn #2
16576   \__sort_quick_end:nnTFNn { } \q_mark { #5 {#3} }
16577   #6 \q_stop
16578 }
16579 \cs_new:Npn \__sort_quick_split_end:nnnwnw #1#2#3#4 \q_mark #5#6 \q_stop
16580 {
16581   \__sort_quick_split:NnNn #2 \__sort_quick_end:nnTFNn { } \q_mark
16582   {
16583     \__sort_quick_split:NnNn #1
16584     \__sort_quick_end:nnTFNn { } \q_mark {#5}
16585     {#3}
16586   }
16587   #6 \q_stop
16588 }

```

(End definition for \\_\_sort\_quick\_end:nnTFNn and others.)

### 33.6 Messages

\\_\_sort\_error: Bailing out of the sorting code is a bit tricky. It may not be safe to use a delimited argument, so instead we redefine many l3sort commands to be trivial, with \\_\_sort\_level: getting rid of the final assignment. This error recovery won't work in a group.

```

16589 \cs_new_protected:Npn \__sort_error:
16590 {
16591   \cs_set_eq:NN \__sort_merge_blocks_aux: \prg_do_nothing:
16592   \cs_set_eq:NN \__sort_merge_blocks: \prg_do_nothing:
16593   \cs_set_protected:Npn \__sort_level: \use:x ##1 { \group_end: }
16594 }

```

(End definition for \\_\_sort\_error:.)

\\_\_sort\_disable\_toksdef: While sorting, \toksdef is locally disabled to prevent users from using \newtoks or similar commands in their comparison code: the \toks registers that would be assigned are in use by l3sort. In format mode, none of this is needed since there is no \toks allocator.

```

16595 \package
16596 \cs_new_protected:Npn \__sort_disable_toksdef:
16597   { \cs_set_eq:NN \toksdef \__sort_disabled_toksdef:n }
16598 \cs_new_protected:Npn \__sort_disabled_toksdef:n #1
16599   {
16600     \__msg_kernel_error:nnx { kernel } { toksdef }
16601     { \token_to_str:N #1 }
16602     \__sort_error:
16603     \tex_toksdef:D #1
16604   }
16605 \__msg_kernel_new:nnnn { kernel } { toksdef }
16606   { Allocation~of~\iow_char:N\ toks~registers~impossible~while~sorting. }
16607   {
16608     The~comparison~code~used~for~sorting~a~list~has~attempted~to~
16609     define~#1~as~a~new~\iow_char:N\ toks~register~using~\iow_char:N\ newtoks~
16610     or~a~similar~command.~The~list~will~not~be~sorted.
16611   }
16612 \package

```

(End definition for \\_\_sort\_disable\_toksdef: and \\_\_sort\_disabled\_toksdef:n.)

\\_\_sort\_too\_long\_error:NNw When there are too many items in a sequence, this is an error, and we clean up properly the mapping over items in the list: break using the type-specific breaking function #1.

```

16613 \cs_new_protected:Npn \__sort_too_long_error:NNw #1#2 \fi:
16614   {
16615     \fi:
16616     \__msg_kernel_error:nnxxx { kernel } { too-large }
16617     { \token_to_str:N #2 }
16618     { \int_eval:n { \l__sort_true_max_int - \l__sort_min_int } }
16619     { \int_eval:n { \l__sort_top_int - \l__sort_min_int } }
16620     #1 \__sort_error:
16621   }
16622 \__msg_kernel_new:nnnn { kernel } { too-large }
16623   { The~list~#1~is~too~long~to~be~sorted~by~TeX. }
16624   {
16625     TeX~has~#2~toks~registers~still~available:~
16626     this~only~allows~to~sort~with~up~to~#3~
16627     items.~All~extra~items~will~be~deleted.
16628   }

```

(End definition for \\_\_sort\_too\_long\_error:NNw.)

```

16629 \__msg_kernel_new:nnnn { kernel } { return-none }
16630   { The~comparison~code~did~not~return. }
16631   {
16632     When~sorting~a~list,~the~code~to~compare~items~#1~and~#2~
16633     did~not~call~
16634     \iow_char:N\ sort_return_same: ~nor~
16635     \iow_char:N\ sort_return_swapped: .~
16636     Exactly~one~of~these~should~be~called.
16637   }
16638 \__msg_kernel_new:nnnn { kernel } { return-two }
16639   { The~comparison~code~returned~multiple~times. }
16640   {
16641     When~sorting~a~list,~the~code~to~compare~items~called~

```

```

16642 \iow_char:N\sort_return_same: ~or~
16643 \iow_char:N\sort_return_swapped: ~multiple-times.~
16644 Exactly~one~of~these~should~be~called.
16645 }

```

### 33.7 Deprecated functions

`\sort_ordered:` These functions were renamed for consistency.

```

\sort_reversed: 16646 \cs_new_protected:Npn \sort_ordered:
16647 {
16648   \__msg_kernel_warning:nxxxx { kernel } { deprecated-command }
16649   { 2018-12-31 }
16650   { \token_to_str:N \sort_ordered: }
16651   { \token_to_str:N \sort_return_same: }
16652   \cs_gset_eq:NN \sort_ordered: \sort_return_same:
16653   \sort_return_same:
16654 }
16655 \cs_new_protected:Npn \sort_reversed:
16656 {
16657   \__msg_kernel_warning:nxxxx { kernel } { deprecated-command }
16658   { 2018-12-31 }
16659   { \token_to_str:N \sort_reversed: }
16660   { \token_to_str:N \sort_return_swapped: }
16661   \cs_gset_eq:NN \sort_reversed: \sort_return_swapped:
16662   \sort_return_swapped:
16663 }

```

(End definition for `\sort_ordered:` and `\sort_reversed:.`)

```

16664 </initex | package>

```

## 34 l3tl-analysis implementation

### 34.1 Internal functions

`\s__tl` The format used to store token lists internally uses the scan mark `\s__tl` as a delimiter.

(End definition for `\s__tl.`)

---

```

\underline{\tl_analysis_map_inline:nn} \tl_analysis_map_inline:nn {<token list>} {<inline function>}

```

Applies the *<inline function>* to each individual *<token>* in the *<token list>*. The *<inline function>* receives three arguments:

- *<tokens>*, which both o-expand and x-expand to the *<token>*. The detailed form of *<token>* may change in later releases.
- *<catcode>*, a capital hexadecimal digit which denotes the category code of the *<token>* (0: control sequence, 1: begin-group, 2: end-group, 3: math shift, 4: alignment tab, 6: parameter, 7: superscript, 8: subscript, A: space, B: letter, C:other, D:active).
- *<char code>*, a decimal representation of the character code of the token, −1 if it is a control sequence (with *<catcode>* 0).

For optimizations in `l3regex` (when matching control sequences), it may be useful to provide a `\_s\_tl\_analysis\_from\_str\_map\_inline:nn` function, perhaps named `\_s\_str\_analysis\_map\_inline:nn`.

## 34.2 Internal format

The task of the `l3tl-analysis` module is to convert token lists to an internal format which allows us to extract all the relevant information about individual tokens (category code, character code), as well as reconstruct the token list quickly. This internal format is used in `l3regex` where we need to support arbitrary tokens, and it is used in conversion functions in `l3str-convert`, where we wish to support clusters of characters instead of single tokens.

We thus need a way to encode any  $\langle token \rangle$  (even begin-group and end-group character tokens) in a way amenable to manipulating tokens individually. The best we can do is to find  $\langle tokens \rangle$  which both `o`-expand and `x`-expand to the given  $\langle token \rangle$ . Collecting more information about the category code and character code is also useful for regular expressions, since most regexes are catcode-agnostic. The internal format thus takes the form of a succession of items of the form

$\langle tokens \rangle \backslash s\_tl \langle catcode \rangle \langle char\ code \rangle \backslash s\_tl$

The  $\langle tokens \rangle$  `o`- and `x`-expand to the original token in the token list or to the cluster of tokens corresponding to one Unicode character in the given encoding (for `l3str-convert`). The  $\langle catcode \rangle$  is given as a single hexadecimal digit, 0 for control sequences. The  $\langle char\ code \rangle$  is given as a decimal number, -1 for control sequences.

Using delimited arguments lets us build the  $\langle tokens \rangle$  progressively when doing an encoding conversion in `l3str-convert`. On the other hand, the delimiter `\s\_tl` may not appear unbraced in  $\langle tokens \rangle$ . This is not a problem because we are careful to wrap control sequences in braces (as an argument to `\exp\_not:n`) when converting from a general token list to the internal format.

The current rule for converting a  $\langle token \rangle$  to a balanced set of  $\langle tokens \rangle$  which both `o`-expands and `x`-expands to it is the following.

- A control sequence `\cs` becomes `\exp\_not:n { \cs } \s\_tl 0 -1 \s\_tl`.
- A begin-group character `{` becomes `\exp\_after:wN { \if\_false: } \fi: \s\_tl 1 \langle char\ code \rangle \s\_tl`.
- An end-group character `}` becomes `\if\_false: { \fi: } \s\_tl 2 \langle char\ code \rangle \s\_tl`.
- A character with any other category code becomes `\exp\_not:n { \langle character \rangle } \s\_tl \langle hex\ catcode \rangle \langle char\ code \rangle \s\_tl`.

16665 `\*initex | package)`

16666 `\@@=tl\_analysis)`

## 34.3 Variables and helper functions

`\s\_tl` The scan mark `\s\_tl` is used as a delimiter in the internal format. This is more practical than using a quark, because we would then need to control expansion much more carefully:



compare `\__int_value:w ‘#1 \s__tl` with `\__int_value:w ‘#1 \exp_stop_f: \exp_not:N \q_mark` to extract a character code followed by the delimiter in an x-expansion.

```
16667 \__scan_new:N \s__tl
```

*(End definition for \s\_\_tl.)*

`\l__tl_analysis_internal_tl` This token list variable is used to hand the argument of `\tl_show_analysis:n` to `\tl_show_analysis:N`.

```
16668 \tl_new:N \l__tl_analysis_internal_tl
```

*(End definition for \l\_\_tl\_analysis\_internal\_tl.)*

`\l__tl_analysis_token` The tokens in the token list are probed with the TeX primitive `\futurelet`. We use `\l__tl_analysis_token` in that construction. In some cases, we convert the following token to a string before probing it: then the token variable used is `\l__tl_analysis_char_token`.

```
16669 \cs_new_eq:NN \l__tl_analysis_token ?
```

```
16670 \cs_new_eq:NN \l__tl_analysis_char_token ?
```

*(End definition for \l\_\_tl\_analysis\_token and \l\_\_tl\_analysis\_char\_token.)*

`\l__tl_analysis_normal_int` The number of normal (N-type argument) tokens since the last special token.

```
16671 \int_new:N \l__tl_analysis_normal_int
```

*(End definition for \l\_\_tl\_analysis\_normal\_int.)*

`\l__tl_analysis_index_int` During the first pass, this is the index in the array being built. During the second pass, it is equal to the maximum index in the array from the first pass.

```
16672 \int_new:N \l__tl_analysis_index_int
```

*(End definition for \l\_\_tl\_analysis\_index\_int.)*

`\l__tl_analysis_nesting_int` Nesting depth of explicit begin-group and end-group characters during the first pass. This lets us detect the end of the token list without a reserved end-marker.

```
16673 \int_new:N \l__tl_analysis_nesting_int
```

*(End definition for \l\_\_tl\_analysis\_nesting\_int.)*

`\l__tl_analysis_type_int` When encountering special characters, we record their “type” in this integer.

```
16674 \int_new:N \l__tl_analysis_type_int
```

*(End definition for \l\_\_tl\_analysis\_type\_int.)*

`\g__tl_analysis_result_tl` The result of the conversion is stored in this token list, with a succession of items of the form

*⟨tokens⟩ \s\_\_tl ⟨catcode⟩ ⟨char code⟩ \s\_\_tl*

```
16675 \tl_new:N \g__tl_analysis_result_tl
```

*(End definition for \g\_\_tl\_analysis\_result\_tl.)*

`\_tl_analysis_extract_charcode:` Extracting the character code from the meaning of `\l\_tl_analysis_token`. This has no error checking, and should only be assumed to work for begin-group and end-group character tokens. It produces a number in the form ‘*⟨char⟩*’.

```

16676 \cs_new:Npn \_tl_analysis_extract_charcode:
16677 {
16678   \exp_after:wN \_tl_analysis_extract_charcode_aux:w
16679   \token_to_meaning:N \l\_tl_analysis_token
16680 }
16681 \cs_new:Npn \_tl_analysis_extract_charcode_aux:w #1 ~ #2 ~ { ‘ ’ }

```

(End definition for `\_tl_analysis_extract_charcode:` and `\_tl_analysis_extract_charcode_aux:w`.)

`\_tl_analysis_cs_space_count:NN` Counts the number of spaces in the string representation of its second argument, as well as the number of characters following the last space in that representation, and feeds the two numbers as semicolon-delimited arguments to the first argument. When this function is used, the escape character is printable and non-space.

```

16682 \cs_new:Npn \_tl_analysis_cs_space_count:NN #1 #2
16683 {
16684   \exp_after:wN #1
16685   \__int_value:w \__int_eval:w 0
16686   \exp_after:wN \_tl_analysis_cs_space_count:w
16687   \token_to_str:N #2
16688   \fi: \_tl_analysis_cs_space_count_end:w ; ~ !
16689 }
16690 \cs_new:Npn \_tl_analysis_cs_space_count:w #1 ~
16691 {
16692   \if_false: #1 #1 \fi:
16693   + 1
16694   \_tl_analysis_cs_space_count:w
16695 }
16696 \cs_new:Npn \_tl_analysis_cs_space_count_end:w ; #1 \fi: #2 !
16697 { \exp_after:wN ; \__int_value:w \str_count_ignore_spaces:n {#1} ; }

```

(End definition for `\_tl_analysis_cs_space_count:NN`, `\_tl_analysis_cs_space_count:w`, and `\_tl_analysis_cs_space_count_end:w`.)

## 34.4 Plan of attack

Our goal is to produce a token list of the form roughly

$$\begin{aligned}
 &\langle token\ 1 \rangle \backslash s\_tl \langle catcode\ 1 \rangle \langle char\ code\ 1 \rangle \backslash s\_tl \\
 &\langle token\ 2 \rangle \backslash s\_tl \langle catcode\ 2 \rangle \langle char\ code\ 2 \rangle \backslash s\_tl \\
 &\dots \langle token\ N \rangle \backslash s\_tl \langle catcode\ N \rangle \langle char\ code\ N \rangle \backslash s\_tl
 \end{aligned}$$

Most but not all tokens can be grabbed as an undelimited (N-type) argument by  $\text{\TeX}$ . The plan is to have a two pass system. In the first pass, locate special tokens, and store them in various `\toks` registers. In the second pass, which is done within an x-expanding assignment, normal tokens are taken in as N-type arguments, and special tokens are retrieved from the `\toks` registers, and removed from the input stream by some means. The whole process takes linear time, because we avoid building the result one item at a time.

To ease the difficult first pass, we first do some setup with `\_tl_analysis_setup:n`. Active characters set equal to non-active characters cause trouble, so we disable all active

characters by setting them equal to `undefined` locally. We also set there the escape character to be printable (backslash, but this later oscillates between slash and backslash): this makes it possible to distinguish characters from control sequences.

A token has two characteristics: its `\meaning`, and what it looks like for  $\TeX$  when it is in scanning mode (*e.g.*, when capturing parameters for a macro). For our purposes, we distinguish the following meanings:

- begin-group token (category code 1), either space (character code 32), or non-space;
- end-group token (category code 2), either space (character code 32), or non-space;
- space token (category code 10, character code 32);
- anything else (then the token is always an N-type argument).

The token itself can “look like” one of the following

- a non-active character, in which case its meaning is automatically that associated to its character code and category code, we call it “true” character;
- an active character (we eliminate those in the setup step);
- a control sequence.

The only tokens which are not valid N-type arguments are true begin-group characters, true end-group characters, and true spaces. We detect those characters by scanning ahead with `\futurelet`, then distinguishing true characters from control sequences set equal to them using the `\string` representation.

The second pass is a simple exercise in expandable loops.

`\__tl_analysis:n` Everything is done within a group, and all definitions are local. We use `\group_align_safe_begin/end:` to avoid problems in case `\__tl_analysis:n` is used within an alignment and its argument contains alignment tab tokens.

```

16698 \cs_new_protected:Npn \__tl_analysis:n #1
16699 {
16700   \group_begin:
16701     \group_align_safe_begin:
16702       \__tl_analysis_setup:n {#1}
16703       \__tl_analysis_a:n {#1}
16704       \__tl_analysis_b:n {#1}
16705     \group_align_safe_end:
16706   \group_end:
16707 }
```

(End definition for `\__tl_analysis:n`.)

## 34.5 Setup

`\__tl_analysis_setup:n` Active characters can cause problems later on in the processing, so the first step is to disable them, by setting them to `undefined`. Since Unicode contains too many characters to loop over all of them, we instead loop over the input token list as a string: any active character in the token list must appear in its string representation. The string is shortened a little by making the escape character unprintable. The active space must be disabled

separately (the loop skips over it otherwise), and we end the loop by feeding an odd non-N-type argument to the looping macro. For pTeX and upTeX we skip characters beyond [0, 255] because \lccode only allows those values.

```

16708 \cs_new_protected:Npn \__tl_analysis_setup:n #1
16709 {
16710   \int_set:Nn \tex_escapechar:D { -1 }
16711   \exp_after:wN \__tl_analysis_disable_loop:N
16712   \tl_to_str:n {#1} { ~ } { ? \__prg_break: }
16713   \__prg_break_point:
16714   \scan_stop:
16715 }
16716 \group_begin:
16717 \char_set_catcode_active:N ^^@
16718 \cs_new_protected:Npn \__tl_analysis_disable_loop:N #1
16719 {
16720   \tex_lccode:D 0 = '#1 ~
16721   \tex_lowercase:D { \tex_let:D ^^@ } \tex_undefined:D
16722   \__tl_analysis_disable_loop:N
16723 }
16724 \cs_if_exist:NT \ptex_kanjiskip:D
16725 {
16726   \cs_gset_protected:Npn \__tl_analysis_disable_loop:N #1
16727   {
16728     \use_none:n #1 \scan_stop:
16729     \if_int_compare:w 256 > '#1 \exp_stop_f:
16730     \tex_lccode:D 0 = '#1 ~
16731     \tex_lowercase:D { \tex_let:D ^^@ } \tex_undefined:D
16732     \fi:
16733     \__tl_analysis_disable_loop:N
16734   }
16735 }
16736 \group_end:

```

(End definition for \\_\_tl\_analysis\_setup:n and \\_\_tl\_analysis\_disable\_loop:N.)

## 34.6 First pass

The goal of this pass is to detect special (non-N-type) tokens, and count how many N-type tokens lie between special tokens. Also, we wish to store some representation of each special token in a \toks register.

After the setup step, we have 11 types of tokens:

1. a true non-space begin-group character;
2. a true space begin-group character;
3. a true non-space end-group character;
4. a true space end-group character;
5. a true space blank space character;
6. an undefined active character;
7. any other true character;

8. a control sequence equal to a begin-group token (category code 1);
9. a control sequence equal to an end-group token (category code 2);
10. a control sequence equal to a space token (character code 32, category code 10);
11. any other control sequence.

Our first tool is `\futurelet`. This cannot distinguish case 8 from 1 or 2, nor case 9 from 3 or 4, nor case 10 from case 5. Those cases are later distinguished by applying the `\string` primitive to the following token, after possibly changing the escape character to ensure that a control sequence's string representation cannot be mistaken for the true character.

In cases 6, 7, and 11, the following token is a valid N-type argument, so we grab it and distinguish the case of a character from a control sequence: in the latter case, `\str_tail:n {\token}` is non-empty, because the escape character is printable.

`\__tl_analysis_a:n` We read tokens one by one using `\futurelet`. While performing the loop, we keep track of the number of true begin-group characters minus the number of true end-group characters in `\l__tl_analysis_nesting_int`. This reaches  $-1$  when we read the closing brace.

```

16737 \cs_new_protected:Npn \__tl_analysis_a:n #1
16738 {
16739   \int_set:Nn \tex_escapechar:D { 92 }
16740   \int_zero:N \l__tl_analysis_normal_int
16741   \int_zero:N \l__tl_analysis_index_int
16742   \int_zero:N \l__tl_analysis_nesting_int
16743   \if_false: { \fi: \__tl_analysis_a_loop:w #1 }
16744   \int_decr:N \l__tl_analysis_index_int
16745 }

```

(End definition for `\__tl_analysis_a:n`.)

`\__tl_analysis_a_loop:w` Read one character and check its type.

```

16746 \cs_new_protected:Npn \__tl_analysis_a_loop:w
16747 { \tex_futurelet:D \l__tl_analysis_token \__tl_analysis_a_type:w }

```

(End definition for `\__tl_analysis_a_loop:w`.)

`\__tl_analysis_a_type:w` At this point, `\l__tl_analysis_token` holds the meaning of the following token. We store in `\l__tl_analysis_type_int` the meaning of the token ahead:

- 0 space token;
- 1 begin-group token;
- -1 end-group token;
- 2 other.

The values 0, 1,  $-1$  correspond to how much a true such character changes the nesting level (2 is used only here, and is irrelevant later). Then call the auxiliary for each case. Note that nesting conditionals here is safe because we only skip over `\l__tl_analysis_token` if it matches with one of the character tokens (hence is not a primitive conditional).

```

16748 \cs_new_protected:Npn \__tl_analysis_a_type:w

```

```

16749 {
16750   \l__tl_analysis_type_int =
16751   \if_meaning:w \l__tl_analysis_token \c_space_token
16752     0
16753   \else:
16754     \if_catcode:w \exp_not:N \l__tl_analysis_token \c_group_begin_token
16755       1
16756     \else:
16757       \if_catcode:w \exp_not:N \l__tl_analysis_token \c_group_end_token
16758         - 1
16759     \else:
16760       2
16761     \fi:
16762   \fi:
16763   \fi:
16764   \exp_stop_f:
16765   \if_case:w \l__tl_analysis_type_int
16766     \exp_after:wN \__tl_analysis_a_space:w
16767   \or: \exp_after:wN \__tl_analysis_a_bgroup:w
16768   \or: \exp_after:wN \__tl_analysis_a_safe:N
16769   \else: \exp_after:wN \__tl_analysis_a_egroup:w
16770   \fi:
16771 }

```

(End definition for \\_\_tl\_analysis\_a\_type:w.)

\\_\_tl\_analysis\_a\_space:w In this branch, the following token's meaning is a blank space. Apply \string to that token: if it is a control sequence the result starts with the escape character; otherwise it is a true blank space, whose string representation is also a blank space. We test for that in \\_\_tl\_analysis\_a\_space\_test:w, after grabbing as \l\_\_tl\_analysis\_char\_token the first character of the string representation. Also, since \\_\_tl\_analysis\_a\_store: expects the special token to be stored in the relevant \toks register, we do that. The extra \exp\_not:n is unnecessary of course, but it makes the treatment of all tokens more homogeneous. If we discover that the next token was actually a control sequence instead of a true space, then we step the counter of normal tokens. We now have in front of us the whole string representation of the control sequence, including potential spaces; those will appear to be true spaces later in this pass. Hence, all other branches of the code in this first pass need to consider the string representation, so that the second pass does not need to test the meaning of tokens, only strings.

```

16772 \cs_new_protected:Npn \__tl_analysis_a_space:w
16773 {
16774   \tex_afterassignment:D \__tl_analysis_a_space_test:w
16775   \exp_after:wN \cs_set_eq:NN
16776   \exp_after:wN \l__tl_analysis_char_token
16777   \token_to_str:N
16778 }
16779 \cs_new_protected:Npn \__tl_analysis_a_space_test:w
16780 {
16781   \if_meaning:w \l__tl_analysis_char_token \c_space_token
16782     \tex_toks:D \l__tl_analysis_index_int { \exp_not:n { ~ } }
16783     \__tl_analysis_a_store:
16784   \else:
16785     \int_incr:N \l__tl_analysis_normal_int

```

```

16786     \fi:
16787     \__tl_analysis_a_loop:w
16788 }

```

(End definition for `\__tl_analysis_a_space:w` and `\__tl_analysis_a_space_test:w`.)

`\__tl_analysis_a_bgroup:w` The token might be either a true character token with catcode 1 or 2, or it could be a control sequence. The only tricky case is if the character code happens to be equal to the escape character: then we change the escape character from backslash to solidus or back, so that the string representation of the true character and of a control sequence set equal to it start differently. Then probe what the first character of that string representation is: this is the place where we need `\l__tl_analysis_char_token` to be a separate control sequence from `\l__tl_analysis_token`, to compare them.

```

16789 \group_begin:
16790   \char_set_catcode_group_begin:N \^^@
16791   \char_set_catcode_group_end:N \^^E
16792   \cs_new_protected:Npn \__tl_analysis_a_bgroup:w
16793     { \__tl_analysis_a_group:nw { \exp_after:wN \^^@ \if_false: \^^E \fi: } }
16794   \char_set_catcode_group_begin:N \^^B
16795   \char_set_catcode_group_end:N \^^@
16796   \cs_new_protected:Npn \__tl_analysis_a_egroup:w
16797     { \__tl_analysis_a_group:nw { \if_false: \^^B \fi: \^^@ } }
16798 \group_end:
16799 \cs_new_protected:Npn \__tl_analysis_a_group:nw #1
16800 {
16801   \tex_lccode:D 0 = \__tl_analysis_extract_charcode: \scan_stop:
16802   \tex_lowercase:D { \tex_toks:D \l__tl_analysis_index_int {#1} }
16803   \if_int_compare:w \tex_lccode:D 0 = \tex_escapechar:D
16804     \int_set:Nn \tex_escapechar:D { 139 - \tex_escapechar:D }
16805   \fi:
16806   \tex_afterassignment:D \__tl_analysis_a_group_test:w
16807   \exp_after:wN \cs_set_eq:NN
16808   \exp_after:wN \l__tl_analysis_char_token
16809   \token_to_str:N
16810 }
16811 \cs_new_protected:Npn \__tl_analysis_a_group_test:w
16812 {
16813   \if_charcode:w \l__tl_analysis_token \l__tl_analysis_char_token
16814     \__tl_analysis_a_store:
16815   \else:
16816     \int_incr:N \l__tl_analysis_normal_int
16817   \fi:
16818   \__tl_analysis_a_loop:w
16819 }

```

(End definition for `\__tl_analysis_a_bgroup:w` and others.)

`\__tl_analysis_a_store:` This function is called each time we meet a special token; at this point, the `\toks` register `\l__tl_analysis_index_int` holds a token list which expands to the given special token. Also, the value of `\l__tl_analysis_type_int` indicates which case we are in:

- -1 end-group character;
- 0 space character;

- 1 begin-group character.

We need to distinguish further the case of a space character (code 32) from other character codes, because those behave differently in the second pass. Namely, after testing the `\lccode` of 0 (which holds the present character code) we change the cases above to

- -2 space end-group character;
- -1 non-space end-group character;
- 0 space blank space character;
- 1 non-space begin-group character;
- 2 space begin-group character.

This has the property that non-space characters correspond to odd values of `\l__tl_analysis_type_int`. The number of normal tokens, and the type of special token, are packed into a `\skip` register. Finally, we check whether we reached the last closing brace, in which case we stop by disabling the looping function (locally).

```

16820 \cs_new_protected:Npn \__tl_analysis_a_store:
16821 {
16822   \tex_advance:D \l__tl_analysis_nesting_int \l__tl_analysis_type_int
16823   \if_int_compare:w \tex_lccode:D 0 = '\ \exp_stop_f:
16824     \tex_multiply:D \l__tl_analysis_type_int 2 \exp_stop_f:
16825   \fi:
16826   \tex_skip:D \l__tl_analysis_index_int
16827     = \l__tl_analysis_normal_int sp plus \l__tl_analysis_type_int sp \scan_stop:
16828   \int_incr:N \l__tl_analysis_index_int
16829   \int_zero:N \l__tl_analysis_normal_int
16830   \if_int_compare:w \l__tl_analysis_nesting_int = -1 \exp_stop_f:
16831     \cs_set_eq:NN \__tl_analysis_a_loop:w \scan_stop:
16832   \fi:
16833 }
```

(End definition for `\__tl_analysis_a_store:.`)

`\__tl_analysis_a_safe:N`  
`\__tl_analysis_a_cs:ww`

This should be the simplest case: since the upcoming token is safe, we can simply grab it in a second pass. However, other branches of the code must pass their tokens through `\string`, hence we do it here as well, with some optimizations. If the token is a single character (including space), the `\if_charcode:w` test yields true, and we simply count one “normal” token. On the other hand, if the token is a control sequence, we should replace it by its string representation for compatibility with other code branches. Instead of slowly looping through the characters with the main code, we use the knowledge of how the second pass works: if the control sequence name contains no space, count that token as a number of normal tokens equal to its string length. If the control sequence contains spaces, they should be registered as special characters by increasing `\l__tl_analysis_index_int` (no need to carefully count character between each space), and all characters after the last space should be counted in the following sequence of “normal” tokens.

```

16834 \cs_new_protected:Npn \__tl_analysis_a_safe:N #1
16835 {
16836   \if_charcode:w
16837     \scan_stop:
```



```

16838     \exp_after:wN \use_none:n \token_to_str:N #1 \prg_do_nothing:
16839     \scan_stop:
16840     \int_incr:N \l__tl_analysis_normal_int
16841   \else:
16842     \__tl_analysis_cs_space_count:NN \__tl_analysis_a_cs:ww #1
16843   \fi:
16844   \__tl_analysis_a_loop:w
16845 }
16846 \cs_new_protected:Npn \__tl_analysis_a_cs:ww #1; #2;
16847 {
16848   \if_int_compare:w #1 > 0 \exp_stop_f:
16849     \tex_skip:D \l__tl_analysis_index_int
16850     = \__int_eval:w \l__tl_analysis_normal_int + 1 sp \scan_stop:
16851     \tex_advance:D \l__tl_analysis_index_int #1 \exp_stop_f:
16852     \l__tl_analysis_normal_int #2 \exp_stop_f:
16853   \else:
16854     \tex_advance:D \l__tl_analysis_normal_int #2 \exp_stop_f:
16855   \fi:
16856 }

```

(End definition for `\__tl_analysis_a_safe:N` and `\__tl_analysis_a_cs:ww`.)

## 34.7 Second pass

The second pass is an exercise in expandable loops. All the necessary information is stored in `\skip` and `\toks` registers.

```

\__tl_analysis_b:n
\__tl_analysis_b_loop:w

```

Start the loop with the index 0. No need for an end-marker: the loop stops by itself when the last index is read. We repeatedly oscillate between reading long stretches of normal tokens, and reading special tokens.

```

16857 \cs_new_protected:Npn \__tl_analysis_b:n #1
16858 {
16859   \tl_gset:Nx \g__tl_analysis_result_tl
16860   {
16861     \__tl_analysis_b_loop:w 0; #1
16862     \__prg_break_point:
16863   }
16864 }
16865 \cs_new:Npn \__tl_analysis_b_loop:w #1;
16866 {
16867   \exp_after:wN \__tl_analysis_b_normals:ww
16868   \__int_value:w \tex_skip:D #1 ; #1 ;
16869 }

```

(End definition for `\__tl_analysis_b:n` and `\__tl_analysis_b_loop:w`.)

```

\__tl_analysis_b_normals:ww
\__tl_analysis_b_normal:wwN

```

The first argument is the number of normal tokens which remain to be read, and the second argument is the index in the array produced in the first step. A character's string representation is always one character long, while a control sequence is always longer (we have set the escape character to a printable value). In both cases, we leave `\exp_not:n` `{\token}` `\s__tl` in the input stream (after x-expansion). Here, `\exp_not:n` is used rather than `\exp_not:N` because `#3` could be `\s__tl`, hence must be hidden behind braces in the result.

```

16870 \cs_new:Npn \__tl_analysis_b_normals:ww #1;
16871 {
16872   \if_int_compare:w #1 = 0 \exp_stop_f:
16873     \__tl_analysis_b_special:w
16874   \fi:
16875   \__tl_analysis_b_normal:wwN #1;
16876 }
16877 \cs_new:Npn \__tl_analysis_b_normal:wwN #1; #2; #3
16878 {
16879   \exp_not:n { \exp_not:n { #3 } } \s__tl
16880   \if_charcode:w
16881     \scan_stop:
16882     \exp_after:wN \use_none:n \token_to_str:N #3 \prg_do_nothing:
16883     \scan_stop:
16884     \exp_after:wN \__tl_analysis_b_char:Nww
16885   \else:
16886     \exp_after:wN \__tl_analysis_b_cs:Nww
16887   \fi:
16888   #3 #1; #2;
16889 }

```

(End definition for \\_\_tl\_analysis\_b\_normals:ww and \\_\_tl\_analysis\_b\_normal:wwN.)

\\_\_tl\_analysis\_b\_char:Nww If the normal token we grab is a character, leave  $\langle catcode \rangle$   $\langle charcode \rangle$  followed by \s\_\_tl in the input stream, and call \\_\_tl\_analysis\_b\_normals:ww with its first argument decremented.

```

16890 \cs_new:Npx \__tl_analysis_b_char:Nww #1
16891 {
16892   \exp_not:N \if_meaning:w #1 \exp_not:N \tex_undefined:D
16893   \token_to_str:N D \exp_not:N \else:
16894   \exp_not:N \if_catcode:w #1 \c_catcode_other_token
16895   \token_to_str:N C \exp_not:N \else:
16896   \exp_not:N \if_catcode:w #1 \c_catcode_letter_token
16897   \token_to_str:N B \exp_not:N \else:
16898   \exp_not:N \if_catcode:w #1 \c_math_toggle_token      3 \exp_not:N \else:
16899   \exp_not:N \if_catcode:w #1 \c_alignment_token      4 \exp_not:N \else:
16900   \exp_not:N \if_catcode:w #1 \c_math_superscript_token 7 \exp_not:N \else:
16901   \exp_not:N \if_catcode:w #1 \c_math_subscript_token  8 \exp_not:N \else:
16902   \exp_not:N \if_catcode:w #1 \c_space_token
16903   \token_to_str:N A \exp_not:N \else:
16904   6
16905   \exp_not:n { \fi: \fi: \fi: \fi: \fi: \fi: \fi: \fi: }
16906   \exp_not:N \__int_value:w '#1 \s__tl
16907   \exp_not:N \exp_after:wN \exp_not:N \__tl_analysis_b_normals:ww
16908   \exp_not:N \__int_value:w \exp_not:N \__int_eval:w - 1 +
16909 }

```

(End definition for \\_\_tl\_analysis\_b\_char:Nww.)

\\_\_tl\_analysis\_b\_cs:Nww If the token we grab is a control sequence, leave 0 -1 (as category code and character code) in the input stream, followed by \s\_\_tl, and call \\_\_tl\_analysis\_b\_normals:ww with updated arguments.

```

16910 \cs_new:Npn \__tl_analysis_b_cs:Nww #1
16911 {

```

```

16912     0 -1 \s__tl
16913     \__tl_analysis_cs_space_count:NN \__tl_analysis_b_cs_test:ww #1
16914   }
16915   \cs_new:Npn \__tl_analysis_b_cs_test:ww #1 ; #2 ; #3 ; #4 ;
16916   {
16917     \exp_after:wN \__tl_analysis_b_normals:ww
16918     \__int_value:w \__int_eval:w
16919     \if_int_compare:w #1 = 0 \exp_stop_f:
16920       #3
16921     \else:
16922       \tex_skip:D \__int_eval:w #4 + #1 \__int_eval_end:
16923     \fi:
16924     - #2
16925     \exp_after:wN ;
16926     \__int_value:w \__int_eval:w #4 + #1 ;
16927   }

```

(End definition for \\_\_tl\_analysis\_b\_cs:Nww and \\_\_tl\_analysis\_b\_cs\_test:ww.)

\\_\_tl\_analysis\_b\_special:w Here, #1 is the current index in the array built in the first pass. Check now whether we reached the end (we shouldn't keep the trailing end-group character that marked the end of the token list in the first pass). Unpack the \toks register: when x-expanding again, we will get the special token. Then leave the category code in the input stream, followed by the character code, and call \\_\_tl\_analysis\_b\_loop:w with the next index.

```

16928 \group_begin:
16929   \char_set_catcode_other:N A
16930   \cs_new:Npn \__tl_analysis_b_special:w
16931     \fi: \__tl_analysis_b_normal:wwN 0 ; #1 ;
16932   {
16933     \fi:
16934     \if_int_compare:w #1 = \l__tl_analysis_index_int
16935       \exp_after:wN \__prg_break:
16936     \fi:
16937     \tex_the:D \tex_toks:D #1 \s__tl
16938     \if_case:w \etex_gluestretch:D \tex_skip:D #1 \exp_stop_f:
16939       A
16940     \or: 1
16941     \or: 1
16942     \else: 2
16943     \fi:
16944     \if_int_odd:w \etex_gluestretch:D \tex_skip:D #1 \exp_stop_f:
16945       \exp_after:wN \__tl_analysis_b_special_char:wN \__int_value:w
16946     \else:
16947       \exp_after:wN \__tl_analysis_b_special_space:w \__int_value:w
16948     \fi:
16949     \__int_eval:w 1 + #1 \exp_after:wN ;
16950     \token_to_str:N
16951   }
16952 \group_end:
16953 \cs_new:Npn \__tl_analysis_b_special_char:wN #1 ; #2
16954   {
16955     \__int_value:w '#2 \s__tl
16956     \__tl_analysis_b_loop:w #1 ;
16957   }

```

```

16958 \cs_new:Npn \__tl_analysis_b_special_space:w #1 ; ~
16959 {
16960     32 \s__tl
16961     \__tl_analysis_b_loop:w #1 ;
16962 }

```

(End definition for `\__tl_analysis_b_special:w`, `\__tl_analysis_b_special_char:wN`, and `\__tl_analysis_b_special_space:w`.)

## 34.8 Mapping through the analysis

`\__tl_analysis_map_inline:nn` First obtain the analysis of the token list into `\g__tl_analysis_result_tl`. To allow nested mappings, increase the nesting depth `\g__prg_map_int` (shared between all modules), then define the looping macro, which has a name specific to that nesting depth. That looping grabs the `<tokens>`, `<catcode>` and `<char code>`; it checks for the end of the loop with `\use_none:n ##2`, normally empty, but which becomes `\tl_map_break:` at the end; it then performs the user's code #2, and loops by calling itself. When the loop ends, remember to decrease the nesting depth.

```

16963 \cs_new_protected:Npn \__tl_analysis_map_inline:nn #1
16964 {
16965     \__tl_analysis:n {#1}
16966     \int_gincr:N \g__prg_map_int
16967     \exp_args:Nc \__tl_analysis_map_inline_aux:Nn
16968     { __tl_analysis_map_inline_ \int_use:N \g__prg_map_int :wNw }
16969 }
16970 \cs_new_protected:Npn \__tl_analysis_map_inline_aux:Nn #1#2
16971 {
16972     \cs_gset_protected:Npn #1 ##1 \s__tl ##2 ##3 \s__tl
16973     {
16974         \use_none:n ##2
16975         #2
16976         #1
16977     }
16978     \exp_after:wN #1
16979     \g__tl_analysis_result_tl
16980     \s__tl { ? \tl_map_break: } \s__tl
16981     \__prg_break_point:Nn \tl_map_break: { \int_gdecr:N \g__prg_map_int }
16982 }

```

(End definition for `\__tl_analysis_map_inline:nn` and `\__tl_analysis_map_inline_aux:Nn`.)

## 34.9 Showing the results

`\tl_show_analysis:N` Add to `\__tl_analysis:n` a third pass to display tokens to the terminal. If the token list variable is not defined, throw the same error as `\tl_show:N` by simply calling that function.  
`\tl_show_analysis:n`  
`\__tl_analysis_show:`

```

16983 \cs_new_protected:Npn \tl_show_analysis:N #1
16984 {
16985     \tl_if_exist:NTF #1
16986     {
16987         \exp_args:No \__tl_analysis:n {#1}
16988         \__msg_show_pre:nnxxxx { LaTeX / kernel } { show-tl-analysis }
16989         { \token_to_str:N #1 } { \tl_if_empty:NTF #1 { } { ? } } { } { }

```

```

16990     \_tl_analysis_show:
16991   }
16992   { \tl_show:N #1 }
16993 }
16994 \cs_new_protected:Npn \tl_show_analysis:n #1
16995 {
16996   \_tl_analysis:n {#1}
16997   \_msg_show_pre:nnxxxx { LaTeX / kernel } { show-tl-analysis }
16998   { } { \tl_if_empty:nTF {#1} { } { ? } } { } { }
16999   \_tl_analysis_show:
17000 }
17001 \cs_new_protected:Npn \_tl_analysis_show:
17002 {
17003   \group_begin:
17004   \exp_args:NNx
17005   \group_end:
17006   \_msg_show_wrap:n
17007   {
17008     \exp_after:wN \_tl_analysis_show_loop:wNw \g__tl_analysis_result_tl
17009     \s__tl { ? \_prg_break: } \s__tl
17010     \_prg_break_point:
17011   }
17012 }

```

(End definition for `\tl_show_analysis:N`, `\tl_show_analysis:n`, and `\_tl_analysis_show:`. These functions are documented on page 196.)

`\_tl_analysis_show_loop:wNw` Here, `#1` o- and x-expands to the token; `#2` is the category code (one uppercase hexadecimal digit), 0 for control sequences; `#3` is the character code, which we ignore. In the cases of control sequences and active characters, the meaning may overflow one line, and we want to truncate it. Those cases are thus separated out.

```

17013 \cs_new:Npn \_tl_analysis_show_loop:wNw #1 \s__tl #2 #3 \s__tl
17014 {
17015   \use_none:n #2
17016   \exp_not:n { \ > \ \ }
17017   \if_int_compare:w "#2 = 0 \exp_stop_f:
17018     \exp_after:wN \_tl_analysis_show_cs:n
17019   \else:
17020     \if_int_compare:w "#2 = 13 \exp_stop_f:
17021     \exp_after:wN \exp_after:wN
17022     \exp_after:wN \_tl_analysis_show_active:n
17023   \else:
17024     \exp_after:wN \exp_after:wN
17025     \exp_after:wN \_tl_analysis_show_normal:n
17026   \fi:
17027   \fi:
17028   {#1}
17029   \_tl_analysis_show_loop:wNw
17030 }

```

(End definition for `\_tl_analysis_show_loop:wNw`.)

`\_tl_analysis_show_normal:n` Non-active characters are a simple matter of printing the character, and its meaning. Our test suite checks that begin-group and end-group characters do not mess up TeX's alignment status.

```

17031 \cs_new:Npn \__tl_analysis_show_normal:n #1
17032 {
17033   \exp_after:wN \token_to_str:N #1 ~
17034   ( \exp_after:wN \token_to_meaning:N #1 )
17035 }

```

(End definition for \\_\_tl\_analysis\_show\_normal:n.)

\\_\_tl\_analysis\_show\_value:N This expands to the value of #1 if it has any.

```

17036 \cs_new:Npn \__tl_analysis_show_value:N #1
17037 {
17038   \token_if_expandable:NF #1
17039   {
17040     \token_if_chardef:NTF      #1 \__prg_break: { }
17041     \token_if_mathchardef:NTF #1 \__prg_break: { }
17042     \token_if_dim_register:NTF #1 \__prg_break: { }
17043     \token_if_int_register:NTF #1 \__prg_break: { }
17044     \token_if_skip_register:NTF #1 \__prg_break: { }
17045     \token_if_toks_register:NTF #1 \__prg_break: { }
17046     \use_none:nnn
17047     \__prg_break_point:
17048     \use:n { \exp_after:wN = \tex_the:D #1 }
17049   }
17050 }

```

(End definition for \\_\_tl\_analysis\_show\_value:N.)

\\_\_tl\_analysis\_show\_cs:n Control sequences and active characters are printed in the same way, making sure not to go beyond the \l\_iow\_line\_count\_int. In case of an overflow, we replace the last characters by \c\_\_tl\_analysis\_show\_etc\_str.

\\_\_tl\_analysis\_show\_active:n

\\_\_tl\_analysis\_show\_long:nn

\\_\_tl\_analysis\_show\_long\_aux:nnnn

```

17051 \cs_new:Npn \__tl_analysis_show_cs:n #1
17052 { \exp_args:No \__tl_analysis_show_long:nn {#1} { control-sequence= } }
17053 \cs_new:Npn \__tl_analysis_show_active:n #1
17054 { \exp_args:No \__tl_analysis_show_long:nn {#1} { active-character= } }
17055 \cs_new:Npn \__tl_analysis_show_long:nn #1
17056 {
17057   \__tl_analysis_show_long_aux:oofn
17058   { \token_to_str:N #1 }
17059   { \token_to_meaning:N #1 }
17060   { \__tl_analysis_show_value:N #1 }
17061 }
17062 \cs_new:Npn \__tl_analysis_show_long_aux:nnnn #1#2#3#4
17063 {
17064   \int_compare:nNnTF
17065   { \str_count:n { #1 ~ ( #4 #2 #3 ) } }
17066   > { \l_iow_line_count_int - 3 }
17067   {
17068     \str_range:nnn { #1 ~ ( #4 #2 #3 ) } { 1 }
17069     {
17070       \l_iow_line_count_int - 3
17071       - \str_count:N \c__tl_analysis_show_etc_str
17072     }
17073     \c__tl_analysis_show_etc_str
17074   }

```

```

17075      { #1 ~ ( #4 #2 #3 ) }
17076    }
17077 \cs_generate_variant:Nn \__tl_analysis_show_long_aux:nnnn { oof }

```

(End definition for \\_\_tl\_analysis\_show\_cs:n and others.)

## 34.10 Messages

`\c__tl_analysis_show_etc_str` When a control sequence (or active character) and its meaning are too long to fit in one line of the terminal, the end is replaced by this token list.

```

17078 \tl_const:Nx \c__tl_analysis_show_etc_str % (
17079   { \token_to_str:N \ETC.) }

```

(End definition for \c\_\_tl\_analysis\_show\_etc\_str.)

```

17080 \__msg_kernel_new:nnn { kernel } { show-tl-analysis }
17081 {
17082   The~token~list~ \tl_if_empty:nF {#1} { #1 ~ }
17083   \tl_if_empty:nTF {#2}
17084     { is~empty }
17085     { contains~the~tokens: }
17086 }
17087 </initex | package>

```

## 35 l3tl-build implementation

```

17088 <*initex | package>
17089 <@@=tl_buidl>

```

### 35.1 Variables and helper functions

`\l__tl_build_start_index_int` `\l__tl_build_index_int` Integers pointing to the starting index (currently always starts at zero), and the current index. The corresponding `\toks` are accessed directly by number.

```

17090 \int_new:N \l__tl_build_start_index_int
17091 \int_new:N \l__tl_build_index_int

```

(End definition for \l\_\_tl\_build\_start\_index\_int and \l\_\_tl\_build\_index\_int.)

`\l__tl_build_result_tl` The resulting token list is normally built in one go by unpacking all `\toks` in some range. In the rare cases where there are too many `\__tl_build_one:n` commands, leading to the depletion of registers, the contents of the current set of `\toks` is unpacked into `\l__tl_build_result_tl`. This prevents overflow from affecting the end-user (beyond an obvious performance hit).

```

17092 \tl_new:N \l__tl_build_result_tl

```

(End definition for \l\_\_tl\_build\_result\_tl.)

`\__tl_build_unpack:` `\__tl_build_unpack_loop:w` The various pieces of the token list are built in `\toks` from the `start_index` (inclusive) to the (current) `index` (excluded). Those `\toks` are unpacked and stored in order in the `result` token list. Optimizations would be possible here, for instance, unpacking 10 `\toks` at a time with a macro expanding to `\the\toks#10...\the\toks#19`, but this should be kept for much later.

```

17093 \cs_new_protected:Npn \__tl_build_unpack:

```

```

17094 {
17095   \tl_put_right:Nx \l__tl_build_result_tl
17096   {
17097     \exp_after:wN \__tl_build_unpack_loop:w
17098     \int_use:N \l__tl_build_start_index_int ;
17099     \__prg_break_point:
17100   }
17101 }
17102 \cs_new:Npn \__tl_build_unpack_loop:w #1 ;
17103 {
17104   \if_int_compare:w #1 = \l__tl_build_index_int
17105   \exp_after:wN \__prg_break:
17106   \fi:
17107   \tex_the:D \tex_toks:D #1 \exp_stop_f:
17108   \exp_after:wN \__tl_build_unpack_loop:w
17109   \int_use:N \__int_eval:w #1 + 1 ;
17110 }

```

(End definition for `\__tl_build_unpack:` and `\__tl_build_unpack_loop:w`.)

## 35.2 Building the token list

Similar to what is done for coffins: redefine some command, here `\__tl_build_end_`  
`aux:n` to hold the relevant assignment (see `\__tl_build_end:` for details). Then initialize  
the start index and the current index at zero, and empty the `result` token list.

```

\__tl_build:Nw
\__tl_build_x:Nw
\__tl_gbuild:Nw
\__tl_gbuild_x:Nw
\__tl_build_aux:NNw
17111 \cs_new_protected:Npn \__tl_build:Nw
17112 { \__tl_build_aux:NNw \tl_set:Nn }
17113 \cs_new_protected:Npn \__tl_build_x:Nw
17114 { \__tl_build_aux:NNw \tl_set:Nx }
17115 \cs_new_protected:Npn \__tl_gbuild:Nw
17116 { \__tl_build_aux:NNw \tl_gset:Nn }
17117 \cs_new_protected:Npn \__tl_gbuild_x:Nw
17118 { \__tl_build_aux:NNw \tl_gset:Nx }
17119 \cs_new_protected:Npn \__tl_build_aux:NNw #1#2
17120 {
17121   \group_begin:
17122   \cs_set:Npn \__tl_build_end_assignment:n
17123   { \group_end: #1 #2 }
17124   \int_zero:N \l__tl_build_start_index_int
17125   \int_zero:N \l__tl_build_index_int
17126   \tl_clear:N \l__tl_build_result_tl
17127 }

```

(End definition for `\__tl_build:Nw` and others.)

`\__tl_build_end:` When we are done building a token list, unpack all `\toks` into the `result` token list, and  
`\__tl_build_end_assignment:n` expand this list before closing the group. The `\__tl_build_end_assignment:n` function  
is defined by `\__tl_build_aux:NNw` to end the group and hold the relevant assignment.  
Its value outside is irrelevant, but just in case, we set it to a function which would clean  
up the contents of `\l__tl_build_result_tl`.

```

17128 \cs_new_protected:Npn \__tl_build_end:
17129 {
17130   \__tl_build_unpack:
17131   \exp_args:No

```



```

17132     \l__tl_build_end_assignment:n \l__tl_build_result_tl
17133   }
17134   \cs_new_eq:NN \l__tl_build_end_assignment:n \use_none:n

```

(End definition for `\l__tl_build_end:` and `\l__tl_build_end_assignment:n`.)

**`\l__tl_build_one:n`** Store the tokens in a free `\toks`, then move the pointer to the next one. If we overflow, **`\l__tl_build_one:o`** unpack the current `\toks`, and reset the current index, preparing to fill more `\toks`. This **`\l__tl_build_one:x`** could be optimized by avoiding to read #1, using `\afterassignment`.

```

17135   \cs_new_protected:Npn \l__tl_build_one:n #1
17136   {
17137     \tex_toks:D \l__tl_build_index_int {#1}
17138     \int_incr:N \l__tl_build_index_int
17139     \if_int_compare:w \l__tl_build_index_int > \c_max_register_int
17140       \l__tl_build_unpack:
17141       \l__tl_build_index_int \l__tl_build_start_index_int
17142     \fi:
17143   }
17144   \cs_new_protected:Npn \l__tl_build_one:o #1
17145   {
17146     \tex_toks:D \l__tl_build_index_int \exp_after:wN {#1}
17147     \int_incr:N \l__tl_build_index_int
17148     \if_int_compare:w \l__tl_build_index_int > \c_max_register_int
17149       \l__tl_build_unpack:
17150       \l__tl_build_index_int \l__tl_build_start_index_int
17151     \fi:
17152   }
17153   \cs_new_protected:Npn \l__tl_build_one:x #1
17154   { \use:x { \l__tl_build_one:n {#1} } }

```

(End definition for `\l__tl_build_one:n`.)

```

17155   </initex | package>

```

## 36 l3regex implementation

```

17156   <*initex | package>

```

```

17157   <@@=regex>

```

### 36.1 Plan of attack

Most regex engines use backtracking. This allows to provide very powerful features (back-references come to mind first), but it is costly, and raises the problem of catastrophic backtracking. Since  $\text{\TeX}$  is not first and foremost a programming language, complicated code tends to run slowly, and we must use faster, albeit slightly more restrictive, techniques, coming from automata theory.

Given a regular expression of  $n$  characters, we do the following:

- (Compiling.) Analyse the regex, finding invalid input, and convert it to an internal representation.
- (Building.) Convert the compiled regex to a non-deterministic finite automaton (NFA) with  $O(n)$  states which accepts precisely token lists matching that regex.

- (Matching.) Loop through the query token list one token (one “position”) at a time, exploring in parallel every possible path (“active thread”) through the NFA, considering active threads in an order determined by the quantifiers’ greediness.

We use the following vocabulary in the code comments (and in variable names).

- *Group*: index of the capturing group,  $-1$  for non-capturing groups.
- *Position*: each token in the query is labelled by an integer  $\langle position \rangle$ , with  $\text{min\_pos} - 1 \leq \langle position \rangle \leq \text{max\_pos}$ . The lowest and highest positions correspond to imaginary begin and end markers (with inaccessible category code and character code).
- *Query*: the token list to which we apply the regular expression.
- *State*: each state of the NFA is labelled by an integer  $\langle state \rangle$  with  $\text{min\_state} \leq \langle state \rangle < \text{max\_state}$ .
- *Active thread*: state of the NFA that is reached when reading the query token list for the matching. Those threads are ordered according to the greediness of quantifiers.
- *Step*: used when matching, starts at 0, incremented every time a character is read, and is not reset when searching for repeated matches. The integer `\l__regex_step_int` is a unique id for all the steps of the matching algorithm.

We use `l3intarray` to manipulate arrays of integers (stored into some dimension registers in scaled points). We also abuse TeX’s `\toks` registers, by accessing them directly by number rather than tying them to control sequence using the `\newtoks` allocation functions. Specifically, these arrays and `\toks` are used as follows. When compiling, `\toks` registers are used under the hood by functions from the `l3tl-build` module. When building, `\toks\langle state \rangle` holds the tests and actions to perform in the  $\langle state \rangle$  of the NFA. When matching,

- `\g__regex_state_active_intarray` holds the last  $\langle step \rangle$  in which each  $\langle state \rangle$  was active.
- `\g__regex_thread_state_intarray` maps each  $\langle thread \rangle$  (with  $\text{min\_active} \leq \langle thread \rangle < \text{max\_active}$ ) to the  $\langle state \rangle$  in which the  $\langle thread \rangle$  currently is. The  $\langle threads \rangle$  or ordered starting from the best to the least preferred.
- `\toks\langle thread \rangle` holds the submatch information for the  $\langle thread \rangle$ , as the contents of a property list.
- `\g__regex_charcode_intarray` and `\g__regex_catcode_intarray` hold the character codes and category codes of tokens at each  $\langle position \rangle$  in the query.
- `\g__regex_balance_intarray` holds the balance of begin-group and end-group character tokens which appear before that point in the token list.
- `\toks\langle position \rangle` holds  $\langle tokens \rangle$  which o- and x-expand to the  $\langle position \rangle$ -th token in the query.

- `\g__regex_submatch_prev_intarray`, `\g__regex_submatch_begin_intarray` and `\g__regex_submatch_end_intarray` hold, for each submatch (as would be extracted by `\regex_extract_all:nnN`), the place where the submatch started to be looked for and its two end-points. For historical reasons, the minimum index is twice `max_state`, and the used registers go up to `\l__regex_submatch_int`. They are organized in blocks of `\l__regex_capturing_group_int` entries, each block corresponding to one match with all its submatches stored in consecutive entries.

`\count` registers are not abused, which means that we can safely use named integers in this module. Note that `\box` registers are not abused either; maybe we could leverage those for some purpose.

The code is structured as follows. Variables are introduced in the relevant section. First we present some generic helper functions. Then comes the code for compiling a regular expression, and for showing the result of the compilation. The building phase converts a compiled regex to NFA states, and the automaton is run by the code in the following section. The only remaining brick is parsing the replacement text and performing the replacement. We are then ready for all the user functions. Finally, messages, and a little bit of tracing code.

## 36.2 Helpers

`\__regex_standard_escapechar:` Make the `\escapechar` into the standard backslash.

```
17158 \cs_new_protected:Npn \__regex_standard_escapechar:
17159 { \int_set:Nn \tex_escapechar:D { '\ } }
```

*(End definition for `\__regex_standard_escapechar:.`)*

`\__regex_toks_use:w` Unpack a `\toks` given its number.

```
17160 \cs_new:Npn \__regex_toks_use:w { \tex_the:D \tex_toks:D }
```

*(End definition for `\__regex_toks_use:w.`)*

`\__regex_toks_clear:N` Empty a `\toks` or set it to a value, given its number.

```
\__regex_toks_set:Nn 17161 \cs_new_protected:Npn \__regex_toks_clear:N #1
\__regex_toks_set:No 17162 { \tex_toks:D #1 { } }
17163 \cs_new_eq:NN \__regex_toks_set:Nn \tex_toks:D
17164 \cs_new_protected:Npn \__regex_toks_set:No #1
17165 { \__regex_toks_set:Nn #1 \exp_after:wN }
```

*(End definition for `\__regex_toks_clear:N` and `\__regex_toks_set:Nn.`)*

`\__regex_toks_memcpy:NNn` Copy #3 `\toks` registers from #2 onwards to #1 onwards, like C's `memcpy`.

```
17166 \cs_new_protected:Npn \__regex_toks_memcpy:NNn #1#2#3
17167 {
17168   \prg_replicate:nn {#3}
17169   {
17170     \tex_toks:D #1 = \tex_toks:D #2
17171     \int_incr:N #1
17172     \int_incr:N #2
17173   }
17174 }
```

*(End definition for `\__regex_toks_memcpy:NNn.`)*

`\__regex_toks_put_left:Nx` During the building phase we wish to add x-expanded material to `\toks`, either to the left or to the right. The expansion is done “by hand” for optimization (these operations are used quite a lot). The `Nn` version of `\__regex_toks_put_right:Nx` is provided because it is more efficient than x-expanding with `\exp_not:n`.

```

17175 \cs_new_protected:Npn \__regex_toks_put_left:Nx #1#2
17176 {
17177   \cs_set:Npx \__regex_tmp:w { #2 }
17178   \tex_toks:D #1 \exp_after:wN \exp_after:wN \exp_after:wN
17179   { \exp_after:wN \__regex_tmp:w \tex_the:D \tex_toks:D #1 }
17180 }
17181 \cs_new_protected:Npn \__regex_toks_put_right:Nx #1#2
17182 {
17183   \cs_set:Npx \__regex_tmp:w {#2}
17184   \tex_toks:D #1 \exp_after:wN
17185   { \tex_the:D \tex_toks:D \exp_after:wN #1 \__regex_tmp:w }
17186 }
17187 \cs_new_protected:Npn \__regex_toks_put_right:Nn #1#2
17188 { \tex_toks:D #1 \exp_after:wN { \tex_the:D \tex_toks:D #1 #2 } }

```

*(End definition for \\_\_regex\_toks\_put\_left:Nx and \\_\_regex\_toks\_put\_right:Nx.)*

`\__regex_curr_cs_to_str:` Expands to the string representation of the token (known to be a control sequence) at the current position `\l__regex_curr_pos_int`. It should only be used in x-expansion to avoid losing a leading space.

```

17189 \cs_new:Npn \__regex_curr_cs_to_str:
17190 {
17191   \exp_after:wN \exp_after:wN \exp_after:wN \cs_to_str:N
17192   \tex_the:D \tex_toks:D \l__regex_curr_pos_int
17193 }

```

*(End definition for \\_\_regex\_curr\_cs\_to\_str:.)*

### 36.2.1 Constants and variables

`\__regex_tmp:w` Temporary function used for various short-term purposes.

```

17194 \cs_new:Npn \__regex_tmp:w { }

```

*(End definition for \\_\_regex\_tmp:w.)*

`\l__regex_internal_a_tl` Temporary variables used for various purposes.

```

\l__regex_internal_b_tl
\l__regex_internal_a_int
\l__regex_internal_b_int
\l__regex_internal_c_int
\l__regex_internal_bool
\l__regex_internal_seq
\g__regex_internal_tl
17195 \tl_new:N \l__regex_internal_a_tl
17196 \tl_new:N \l__regex_internal_b_tl
17197 \int_new:N \l__regex_internal_a_int
17198 \int_new:N \l__regex_internal_b_int
17199 \int_new:N \l__regex_internal_c_int
17200 \bool_new:N \l__regex_internal_bool
17201 \seq_new:N \l__regex_internal_seq
17202 \tl_new:N \g__regex_internal_tl

```

*(End definition for \l\_\_regex\_internal\_a\_tl and others.)*

`\c__regex_no_match_regex` This regular expression matches nothing, but is still a valid regular expression. We could use a failing assertion, but I went for an empty class. It is used as the initial value for regular expressions declared using `\regex_new:N`.

```

17203 \tl_const:Nn \c__regex_no_match_regex
17204 {
17205     \__regex_branch:n
17206     { \__regex_class:NnnnN \c_true_bool { } { 1 } { 0 } \c_true_bool }
17207 }

```

*(End definition for \c\_\_regex\_no\_match\_regex.)*

`\g__regex_charcode_intarray`  
`\g__regex_catcode_intarray`  
`\g__regex_balance_intarray` The first thing we do when matching is to go once through the query token list and store the information for each token into `\g__regex_charcode_intarray`, `\g__regex_catcode_intarray` and `\toks` registers. We also store the balance of begin-group/end-group characters into `\g__regex_balance_intarray`.

```

17208 \__intarray_new:Nn \g__regex_charcode_intarray { 65536 }
17209 \__intarray_new:Nn \g__regex_catcode_intarray { 65536 }
17210 \__intarray_new:Nn \g__regex_balance_intarray { 65536 }

```

*(End definition for \g\_\_regex\_charcode\_intarray, \g\_\_regex\_catcode\_intarray, and \g\_\_regex\_balance\_intarray.)*

`\l__regex_balance_int` During this phase, `\l__regex_balance_int` counts the balance of begin-group and end-group character tokens which appear before a given point in the token list. This variable is also used to keep track of the balance in the replacement text.

```

17211 \int_new:N \l__regex_balance_int

```

*(End definition for \l\_\_regex\_balance\_int.)*

`\l__regex_cs_name_tl` This variable is used in `\__regex_item_cs:n` to store the csname of the currently-tested token when the regex contains a sub-regex for testing csnames.

```

17212 \tl_new:N \l__regex_cs_name_tl

```

*(End definition for \l\_\_regex\_cs\_name\_tl.)*

### 36.2.2 Testing characters

`\c__regex_ascii_min_int`  
`\c__regex_ascii_max_control_int`  
`\c__regex_ascii_max_int`

```

17213 \int_const:Nn \c__regex_ascii_min_int { 0 }
17214 \int_const:Nn \c__regex_ascii_max_control_int { 31 }
17215 \int_const:Nn \c__regex_ascii_max_int { 127 }

```

*(End definition for \c\_\_regex\_ascii\_min\_int, \c\_\_regex\_ascii\_max\_control\_int, and \c\_\_regex\_ascii\_max\_int.)*

`\c__regex_ascii_lower_int`

```

17216 \int_const:Nn \c__regex_ascii_lower_int { 'a - 'A }

```

*(End definition for \c\_\_regex\_ascii\_lower\_int.)*

`\__regex_break_point:TF`  
`\__regex_break_true:w`

When testing whether a character of the query token list matches a given character class in the regular expression, we often have to test it against several ranges of characters, checking if any one of those matches. This is done with a structure like

```

    <test1> ... <testn>
    \__regex_break_point:TF {<true code>} {<false code>}

```

If any of the tests succeeds, it calls `\__regex_break_true:w`, which cleans up and leaves `<true code>` in the input stream. Otherwise, `\__regex_break_point:TF` leaves the `<false code>` in the input stream.

```

17217 \cs_new_protected:Npn \__regex_break_true:w
17218     #1 \__regex_break_point:TF #2 #3 {#2}
17219 \cs_new_protected:Npn \__regex_break_point:TF #1 #2 { #2 }

```

(End definition for `\__regex_break_point:TF` and `\__regex_break_true:w`.)

`\__regex_item_reverse:n` This function makes showing regular expressions easier, and lets us define `\D` in terms of `\d` for instance. There is a subtlety: the end of the query is marked by `-2`, and thus matches `\D` and other negated properties; this case is caught by another part of the code.

```

17220 \cs_new_protected:Npn \__regex_item_reverse:n #1
17221 {
17222     #1
17223     \__regex_break_point:TF { } \__regex_break_true:w
17224 }

```

(End definition for `\__regex_item_reverse:n`.)

`\__regex_item_caseful_equal:n` Simple comparisons triggering `\__regex_break_true:w` when true.

```

\__regex_item_caseful_range:nn
17225 \cs_new_protected:Npn \__regex_item_caseful_equal:n #1
17226 {
17227     \if_int_compare:w #1 = \l__regex_curr_char_int
17228     \exp_after:wN \__regex_break_true:w
17229     \fi:
17230 }
17231 \cs_new_protected:Npn \__regex_item_caseful_range:nn #1 #2
17232 {
17233     \reverse_if:N \if_int_compare:w #1 > \l__regex_curr_char_int
17234     \reverse_if:N \if_int_compare:w #2 < \l__regex_curr_char_int
17235     \exp_after:wN \exp_after:wN \exp_after:wN \__regex_break_true:w
17236     \fi:
17237     \fi:
17238 }

```

(End definition for `\__regex_item_caseful_equal:n` and `\__regex_item_caseful_range:nn`.)

`\__regex_item_caseless_equal:n` For caseless matching, we perform the test both on the `current_char` and on the `case_changed_char`. Before doing the second set of tests, we make sure that `case_changed_char` has been computed.

```

\__regex_item_caseless_range:nn
17239 \cs_new_protected:Npn \__regex_item_caseless_equal:n #1
17240 {
17241     \if_int_compare:w #1 = \l__regex_curr_char_int
17242     \exp_after:wN \__regex_break_true:w
17243     \fi:
17244     \if_int_compare:w \l__regex_case_changed_char_int = \c_max_int
17245     \__regex_compute_case_changed_char:
17246     \fi:
17247     \if_int_compare:w #1 = \l__regex_case_changed_char_int
17248     \exp_after:wN \__regex_break_true:w

```

```

17249     \fi:
17250   }
17251   \cs_new_protected:Npn \__regex_item_caseless_range:nn #1 #2
17252   {
17253     \reverse_if:N \if_int_compare:w #1 > \l__regex_curr_char_int
17254     \reverse_if:N \if_int_compare:w #2 < \l__regex_curr_char_int
17255     \exp_after:wN \exp_after:wN \exp_after:wN \__regex_break_true:w
17256     \fi:
17257     \fi:
17258     \if_int_compare:w \l__regex_case_changed_char_int = \c_max_int
17259     \__regex_compute_case_changed_char:
17260     \fi:
17261     \reverse_if:N \if_int_compare:w #1 > \l__regex_case_changed_char_int
17262     \reverse_if:N \if_int_compare:w #2 < \l__regex_case_changed_char_int
17263     \exp_after:wN \exp_after:wN \exp_after:wN \__regex_break_true:w
17264     \fi:
17265     \fi:
17266   }

```

(End definition for \\_\_regex\_item\_caseless\_equal:n and \\_\_regex\_item\_caseless\_range:nn.)

\\_\_regex\_compute\_case\_changed\_char: This function is called when \l\_\_regex\_case\_changed\_char\_int has not yet been computed (or rather, when it is set to the marker value \c\_max\_int). If the current character code is in the range [65,90] (upper-case), then add 32, making it lowercase. If it is in the lower-case letter range [97,122], subtract 32.

```

17267   \cs_new_protected:Npn \__regex_compute_case_changed_char:
17268   {
17269     \int_set_eq:NN \l__regex_case_changed_char_int \l__regex_curr_char_int
17270     \if_int_compare:w \l__regex_curr_char_int > 'Z \exp_stop_f:
17271     \if_int_compare:w \l__regex_curr_char_int > 'z \exp_stop_f: \else:
17272     \if_int_compare:w \l__regex_curr_char_int < 'a \exp_stop_f: \else:
17273     \int_sub:Nn \l__regex_case_changed_char_int { \c__regex_ascii_lower_int }
17274     \fi:
17275     \fi:
17276     \else:
17277     \if_int_compare:w \l__regex_curr_char_int < 'A \exp_stop_f: \else:
17278     \int_add:Nn \l__regex_case_changed_char_int { \c__regex_ascii_lower_int }
17279     \fi:
17280     \fi:
17281   }

```

(End definition for \\_\_regex\_compute\_case\_changed\_char:.)

\\_\_regex\_item\_equal:n Those must always be defined to expand to a `caseful` (default) or `caseless` version, and not be protected: they must expand when compiling, to hard-code which tests are caseless or caseful.

```

17282   \cs_new_eq:NN \__regex_item_equal:n ?
17283   \cs_new_eq:NN \__regex_item_range:nn ?

```

(End definition for \\_\_regex\_item\_equal:n and \\_\_regex\_item\_range:nn.)

\\_\_regex\_item\_catcode:nT The argument is a sum of powers of 4 with exponents given by the allowed category codes (between 0 and 13). Dividing by a given power of 4 gives an odd result if and only if that

category code is allowed. If the catcode does not match, then skip the character code tests which follow.

```

17284 \cs_new_protected:Npn \__regex_item_catcode:
17285 {
17286   "
17287   \if_case:w \l__regex_curr_catcode_int
17288     1          \or: 4          \or: 10       \or: 40
17289     \or: 100    \or:          \or: 1000      \or: 4000
17290     \or: 10000  \or:          \or: 100000    \or: 400000
17291     \or: 1000000 \or: 4000000 \else: 1*0
17292   \fi:
17293 }
17294 \cs_new_protected:Npn \__regex_item_catcode:nT #1
17295 {
17296   \if_int_odd:w \__int_eval:w #1 / \__regex_item_catcode: \__int_eval_end:
17297   \exp_after:wN \use:n
17298   \else:
17299   \exp_after:wN \use_none:n
17300   \fi:
17301 }
17302 \cs_new_protected:Npn \__regex_item_catcode_reverse:nT #1#2
17303 { \__regex_item_catcode:nT {#1} { \__regex_item_reverse:n {#2} } }

```

(End definition for \\_\_regex\_item\_catcode:nT, \\_\_regex\_item\_catcode\_reverse:nT, and \\_\_regex\_item\_catcode:.)

\\_\_regex\_item\_exact:nn This matches an exact  $\langle category \rangle$ - $\langle character code \rangle$  pair, or an exact control sequence, more precisely one of several possible control sequences.

```

17304 \cs_new_protected:Npn \__regex_item_exact:nn #1#2
17305 {
17306   \if_int_compare:w #1 = \l__regex_curr_catcode_int
17307   \if_int_compare:w #2 = \l__regex_curr_char_int
17308   \exp_after:wN \exp_after:wN \exp_after:wN \__regex_break_true:w
17309   \fi:
17310   \fi:
17311 }
17312 \cs_new_protected:Npn \__regex_item_exact_cs:n #1
17313 {
17314   \int_compare:nNnTF \l__regex_curr_catcode_int = 0
17315   {
17316     \tl_set:Nx \l__regex_internal_a_tl
17317     { \scan_stop: \__regex_curr_cs_to_str: \scan_stop: }
17318     \tl_if_in:noTF { \scan_stop: #1 \scan_stop: } \l__regex_internal_a_tl
17319     { \__regex_break_true:w } { }
17320   }
17321   { }
17322 }

```

(End definition for \\_\_regex\_item\_exact:nn and \\_\_regex\_item\_exact\_cs:n.)

\\_\_regex\_item\_cs:n Match a control sequence (the argument is a compiled regex). First test the catcode of the current token to be zero. Then perform the matching test, and break if the csname indeed matches. The three \exp\_after:wN expand the contents of the \toks $\langle current position \rangle$  (of the form \exp\_not:n { $\langle control sequence \rangle$ }) to  $\langle control sequence \rangle$ . We store



the cs name before building states for the cs, as those states may overlap with toks registers storing the user's input.

```

17323 \cs_new_protected:Npn \__regex_item_cs:n #1
17324 {
17325   \int_compare:nNnT \l__regex_curr_catcode_int = 0
17326   {
17327     \group_begin:
17328     \tl_set:Nx \l__regex_cs_name_tl { \__regex_curr_cs_to_str: }
17329     \__regex_single_match:
17330     \__regex_disable_submatches:
17331     \__regex_build_for_cs:n {#1}
17332     \bool_set_eq:NN \l__regex_saved_success_bool \g__regex_success_bool
17333     \exp_args:NV \__regex_match:n \l__regex_cs_name_tl
17334     \if_meaning:w \c_true_bool \g__regex_success_bool
17335       \group_insert_after:N \__regex_break_true:w
17336     \fi:
17337     \bool_gset_eq:NN \g__regex_success_bool \l__regex_saved_success_bool
17338     \group_end:
17339   }
17340 }

```

(End definition for \\_\_regex\_item\_cs:n.)

### 36.2.3 Character property tests

\\_\_regex\_prop\_d: Character property tests for \d, \W, etc. These character properties are not affected by the (?i) option. The characters recognized by each one are as follows: \d=[0-9], \w=[0-9A-Z\_a-z], \s=[\ \\_ \^ \^ I \^ J \^ L \^ M], \h=[\ \\_ \^ I], \v=[\ \^ J - \^ M], and the upper case counterparts match anything that the lower case does not match. The order in which the various tests appear is optimized for usual mostly lower case letter text.

```

17341 \cs_new_protected:Npn \__regex_prop_d:
17342 { \__regex_item_caseful_range:nn { '0 } { '9 } }
17343 \cs_new_protected:Npn \__regex_prop_h:
17344 {
17345   \__regex_item_caseful_equal:n { '\ }
17346   \__regex_item_caseful_equal:n { '\^ I }
17347 }
17348 \cs_new_protected:Npn \__regex_prop_s:
17349 {
17350   \__regex_item_caseful_equal:n { '\ }
17351   \__regex_item_caseful_equal:n { '\^ I }
17352   \__regex_item_caseful_equal:n { '\^ J }
17353   \__regex_item_caseful_equal:n { '\^ L }
17354   \__regex_item_caseful_equal:n { '\^ M }
17355 }
17356 \cs_new_protected:Npn \__regex_prop_v:
17357 { \__regex_item_caseful_range:nn { '\^ J } { '\^ M } } % lf, vtab, ff, cr
17358 \cs_new_protected:Npn \__regex_prop_w:
17359 {
17360   \__regex_item_caseful_range:nn { 'a } { 'z }
17361   \__regex_item_caseful_range:nn { 'A } { 'Z }
17362   \__regex_item_caseful_range:nn { '0 } { '9 }
17363   \__regex_item_caseful_equal:n { '_' }

```

```

17364     }
17365     \cs_new_protected:Npn \__regex_prop_N:
17366     {
17367         \__regex_item_reverse:n
17368         { \__regex_item_caseful_equal:n { '\^J } }
17369     }

```

(End definition for \\_\_regex\_prop\_d: and others.)

```

\__regex_posix_alnum: POSIX properties. No surprise.
\__regex_posix_alpha: 17370 \cs_new_protected:Npn \__regex_posix_alnum:
\__regex_posix_ascii: 17371 { \__regex_posix_alpha: \__regex_posix_digit: }
\__regex_posix_blank: 17372 \cs_new_protected:Npn \__regex_posix_alpha:
\__regex_posix_cntrl: 17373 { \__regex_posix_lower: \__regex_posix_upper: }
\__regex_posix_digit: 17374 \cs_new_protected:Npn \__regex_posix_ascii:
\__regex_posix_graph: 17375 {
\__regex_posix_lower: 17376     \__regex_item_caseful_range:nn
\__regex_posix_print: 17377     \c__regex_ascii_min_int
\__regex_posix_punct: 17378     \c__regex_ascii_max_int
17379 }
\__regex_posix_space: 17380 \cs_new_eq:NN \__regex_posix_blank: \__regex_prop_h:
\__regex_posix_upper: 17381 \cs_new_protected:Npn \__regex_posix_cntrl:
\__regex_posix_word: 17382 {
\__regex_posix_xdigit: 17383     \__regex_item_caseful_range:nn
17384     \c__regex_ascii_min_int
17385     \c__regex_ascii_max_control_int
17386     \__regex_item_caseful_equal:n \c__regex_ascii_max_int
17387 }
17388 \cs_new_eq:NN \__regex_posix_digit: \__regex_prop_d:
17389 \cs_new_protected:Npn \__regex_posix_graph:
17390 { \__regex_item_caseful_range:nn { '!' } { '\~ } }
17391 \cs_new_protected:Npn \__regex_posix_lower:
17392 { \__regex_item_caseful_range:nn { 'a' } { 'z' } }
17393 \cs_new_protected:Npn \__regex_posix_print:
17394 { \__regex_item_caseful_range:nn { '\ ' } { '\~ } }
17395 \cs_new_protected:Npn \__regex_posix_punct:
17396 {
17397     \__regex_item_caseful_range:nn { '!' } { '/' }
17398     \__regex_item_caseful_range:nn { ':' } { '@' }
17399     \__regex_item_caseful_range:nn { '[' ] } { '' }
17400     \__regex_item_caseful_range:nn { '\{ } } { '\~ }
17401 }
17402 \cs_new_protected:Npn \__regex_posix_space:
17403 {
17404     \__regex_item_caseful_equal:n { '\ ' }
17405     \__regex_item_caseful_range:nn { '\^I } { '\^M }
17406 }
17407 \cs_new_protected:Npn \__regex_posix_upper:
17408 { \__regex_item_caseful_range:nn { 'A' } { 'Z' } }
17409 \cs_new_eq:NN \__regex_posix_word: \__regex_prop_w:
17410 \cs_new_protected:Npn \__regex_posix_xdigit:
17411 {
17412     \__regex_posix_digit:
17413     \__regex_item_caseful_range:nn { 'A' } { 'F' }

```

```

17414     \_regex_item_caseful_range:nn { 'a } { 'f }
17415 }

```

(End definition for \\_regex\_posix\_alnum: and others.)

### 36.2.4 Simple character escape

Before actually parsing the regular expression or the replacement text, we go through them once, converting `\n` to the character 10, *etc.* In this pass, we also convert any special character (`*`, `?`, `{`, *etc.*) or escaped alphanumeric character into a marker indicating that this was a special sequence, and replace escaped special characters and non-escaped alphanumeric characters by markers indicating that those were “raw” characters. The rest of the code can then avoid caring about escaping issues (those can become quite complex to handle in combination with ranges in character classes).

Usage: `\_regex_escape_use:nnnn` *<inline 1>* *<inline 2>* *<inline 3>* *<{token list}>*  
The *<token list>* is converted to a string, then read from left to right, interpreting backslashes as escaping the next character. Unescaped characters are fed to the function *<inline 1>*, and escaped characters are fed to the function *<inline 2>* within an `x`-expansion context (typically those functions perform some tests on their argument to decide how to output them). The escape sequences `\a`, `\e`, `\f`, `\n`, `\r`, `\t` and `\x` are recognized, and those are replaced by the corresponding character, then fed to *<inline 3>*. The result is then left in the input stream. Spaces are ignored unless escaped.

The conversion is mostly done within an `x`-expanding assignment, except for the `\x` escape sequence, which is not amenable to that in general. For this, we use the general framework of `\_tl_build:Nw`.

`\_regex_escape_use:nnnn` The result is built in `\l\_regex_internal_a_tl`, which is then left in the input stream. Go through #4 once, applying #1, #2, or #3 as relevant to each character (after de-escaping it). Note that we cannot replace `\tl_set:Nx` and `\_tl_build_one:o` by a single call to `\_tl_build_one:x`, because the `x`-expanding assignment may be interrupted by `\x`.

```

17416 \cs_new_protected:Npn \_regex_escape_use:nnnn #1#2#3#4
17417 {
17418   \trace_push:nnn { regex } { 1 } { \_regex_escape_use:nnnn }
17419   \_tl_build:Nw \l\_regex_internal_a_tl
17420   \cs_set:Npn \_regex_escape_unescaped:N ##1 { #1 }
17421   \cs_set:Npn \_regex_escape_escaped:N ##1 { #2 }
17422   \cs_set:Npn \_regex_escape_raw:N ##1 { #3 }
17423   \_regex_standard_escapechar:
17424   \tl_gset:Nx \g\_regex_internal_tl { \_str_to_other_fast:n {#4} }
17425   \tl_set:Nx \l\_regex_internal_b_tl
17426   {
17427     \exp_after:wN \_regex_escape_loop:N \g\_regex_internal_tl
17428     { break } \_prg_break_point:
17429   }
17430   \_tl_build_one:o \l\_regex_internal_b_tl
17431   \_tl_build_end:
17432   \trace_pop:nnn { regex } { 1 } { \_regex_escape_use:nnnn }
17433   \l\_regex_internal_a_tl
17434 }

```

(End definition for \\_regex\_escape\_use:nnnn.)

`__regex_escape_loop:N` `__regex_escape\:w` `__regex_escape_loop:N` reads one character: if it is special (space, backslash, or end-marker), perform the associated action, otherwise it is simply an unescaped character. After a backslash, the same is done, but unknown characters are “escaped”.

```

17435 \cs_new:Npn __regex_escape_loop:N #1
17436 {
17437   \cs_if_exist_use:cF { __regex_escape\_token_to_str:N #1:w }
17438   { __regex_escape_unescaped:N #1 }
17439   __regex_escape_loop:N
17440 }
17441 \cs_new:cpn { __regex_escape\_c_backslash_str :w }
17442   __regex_escape_loop:N #1
17443 {
17444   \cs_if_exist_use:cF { __regex_escape\_token_to_str:N #1:w }
17445   { __regex_escape_escaped:N #1 }
17446   __regex_escape_loop:N
17447 }

```

(End definition for `__regex_escape_loop:N` and `__regex_escape\:w`.)

`__regex_escape_unescaped:N` `__regex_escape_escaped:N` `__regex_escape_raw:N` Those functions are never called before being given a new meaning, so their definitions here don’t matter.

```

17448 \cs_new_eq:NN __regex_escape_unescaped:N ?
17449 \cs_new_eq:NN __regex_escape_escaped:N ?
17450 \cs_new_eq:NN __regex_escape_raw:N ?

```

(End definition for `__regex_escape_unescaped:N`, `__regex_escape_escaped:N`, and `__regex_escape_raw:N`.)

`__regex_escape_break:w` `__regex_escape_/break:w` `__regex_escape_/a:w` `__regex_escape_/e:w` `__regex_escape_/f:w` `__regex_escape_/n:w` `__regex_escape_/r:w` `__regex_escape_/t:w` `__regex_escape_\_w` The loop is ended upon seeing the end-marker “break”, with an error if the string ended in a backslash. Spaces are ignored, and `\a`, `\e`, `\f`, `\n`, `\r`, `\t` take their meaning here.

```

17451 \cs_new_eq:NN __regex_escape_break:w __prg_break:
17452 \cs_new:cpn { __regex_escape_/break:w }
17453 {
17454   \if_false: { \fi: }
17455   __msg_kernel_error:nn { kernel } { trailing-backslash }
17456   \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:
17457 }
17458 \cs_new:cpn { __regex_escape\_~:w } { }
17459 \cs_new:cpx { __regex_escape_/a:w }
17460   { \exp_not:N __regex_escape_raw:N \iow_char:N ^^G }
17461 \cs_new:cpx { __regex_escape_/t:w }
17462   { \exp_not:N __regex_escape_raw:N \iow_char:N ^^I }
17463 \cs_new:cpx { __regex_escape_/n:w }
17464   { \exp_not:N __regex_escape_raw:N \iow_char:N ^^J }
17465 \cs_new:cpx { __regex_escape_/f:w }
17466   { \exp_not:N __regex_escape_raw:N \iow_char:N ^^L }
17467 \cs_new:cpx { __regex_escape_/r:w }
17468   { \exp_not:N __regex_escape_raw:N \iow_char:N ^^M }
17469 \cs_new:cpx { __regex_escape_/e:w }
17470   { \exp_not:N __regex_escape_raw:N \iow_char:N ^^[ }

```

(End definition for `__regex_escape_break:w` and others.)

```

    \_regex_escape_/x:w
    \_regex_escape_x_end:w
    \_regex_escape_x_large:n

```

When \x is encountered, \\_regex\_escape\_x\_test:N is responsible for grabbing some hexadecimal digits, and feeding the result to \\_regex\_escape\_x\_end:w. If the number is too big interrupt the assignment and produce an error, otherwise call \\_regex\_escape\_raw:N on the corresponding character token.

```

17471 \cs_new:cpn { \_regex_escape_/x:w } \_regex_escape_loop:N
17472 {
17473     \exp_after:wN \_regex_escape_x_end:w
17474     \_int_value:w "0 \_regex_escape_x_test:N
17475 }
17476 \cs_new:Npn \_regex_escape_x_end:w #1 ;
17477 {
17478     \int_compare:nNnTF {#1} > \c_max_char_int
17479     {
17480         \if_false: { \fi: }
17481         \_tl_build_one:o \l_regex_internal_b_tl
17482         \_msg_kernel_error:nnx { kernel } { x-overflow } {#1}
17483         \tl_set:Nx \l_regex_internal_b_tl
17484             { \if_false: } \fi:
17485     }
17486     {
17487         \exp_last_unbraced:Nf \_regex_escape_raw:N
17488         { \char_generate:nn {#1} { 12 } }
17489     }
17490 }

```

(End definition for \\_regex\_escape\_/x:w, \\_regex\_escape\_x\_end:w, and \\_regex\_escape\_x\_large:n.)

```

    \_regex_escape_x_test:N
    \_regex_escape_x_testii:N

```

Find out whether the first character is a left brace (allowing any number of hexadecimal digits), or not (allowing up to two hexadecimal digits). We need to check for the end-of-string marker. Eventually, call either \\_regex\_escape\_x\_loop:N or \\_regex\_escape\_x:N.

```

17491 \cs_new:Npn \_regex_escape_x_test:N #1
17492 {
17493     \str_if_eq_x:nnTF {#1} { break } { ; }
17494     {
17495         \if_charcode:w \c_space_token #1
17496         \exp_after:wN \_regex_escape_x_test:N
17497         \else:
17498         \exp_after:wN \_regex_escape_x_testii:N
17499         \exp_after:wN #1
17500         \fi:
17501     }
17502 }
17503 \cs_new:Npn \_regex_escape_x_testii:N #1
17504 {
17505     \if_charcode:w \c_left_brace_str #1
17506     \exp_after:wN \_regex_escape_x_loop:N
17507     \else:
17508     \_regex_hexadecimal_use:NNTF #1
17509     { \exp_after:wN \_regex_escape_x:N }
17510     { ; \exp_after:wN \_regex_escape_loop:N \exp_after:wN #1 }
17511     \fi:
17512 }

```

(End definition for `\_regex_escape_x:test:N` and `\_regex_escape_x:testii:N`.)

`\_regex_escape_x:N` This looks for the second digit in the unbraced case.

```

17513 \cs_new:Npn \_regex_escape_x:N #1
17514 {
17515   \str_if_eq_x:nnTF {#1} { break } { ; }
17516   {
17517     \_regex_hexadecimal_use:NTF #1
17518     { ; \_regex_escape_loop:N }
17519     { ; \_regex_escape_loop:N #1 }
17520   }
17521 }
```

(End definition for `\_regex_escape_x:N`.)

`\_regex_escape_x_loop:N` Grab hexadecimal digits, skip spaces, and at the end, check that there is a right brace,  
`\_regex_escape_x_loop_error:` otherwise raise an error outside the assignment.

```

17522 \cs_new:Npn \_regex_escape_x_loop:N #1
17523 {
17524   \str_if_eq_x:nnTF {#1} { break }
17525   { ; \_regex_escape_x_loop_error:n { } {#1} }
17526   {
17527     \_regex_hexadecimal_use:NTF #1
17528     { \_regex_escape_x_loop:N }
17529     {
17530       \token_if_eq_charcode:NNTF \c_space_token #1
17531       { \_regex_escape_x_loop:N }
17532       {
17533         ;
17534         \exp_after:wN
17535         \token_if_eq_charcode:NNTF \c_right_brace_str #1
17536         { \_regex_escape_loop:N }
17537         { \_regex_escape_x_loop_error:n {#1} }
17538       }
17539     }
17540   }
17541 }
17542 \cs_new:Npn \_regex_escape_x_loop_error:n #1
17543 {
17544   \if_false: { \fi: }
17545   \__tl_build_one:o \l__regex_internal_b_tl
17546   \__msg_kernel_error:nnx { kernel } { x-missing-rbrace } {#1}
17547   \tl_set:Nx \l__regex_internal_b_tl
17548   { \if_false: } \fi: \_regex_escape_loop:N #1
17549 }
```

(End definition for `\_regex_escape_x_loop:N` and `\_regex_escape_x_loop_error:.`)

`\_regex_hexadecimal_use:N` TeX detects uppercase hexadecimal digits for us but not the lowercase letters, which we need to detect and replace by their uppercase counterpart.

```

17550 \prg_new_conditional:Npnn \_regex_hexadecimal_use:N #1 { TF }
17551 {
17552   \if_int_compare:w 1 < "1 \token_to_str:N #1 \exp_stop_f:
17553   #1 \prg_return_true:
```

```

17554     \else:
17555         \if_case:w \__int_eval:w
17556             \exp_after:wN ‘ \token_to_str:N #1 - ‘a
17557             \__int_eval_end:
17558             A
17559         \or: B
17560         \or: C
17561         \or: D
17562         \or: E
17563         \or: F
17564     \else:
17565         \prg_return_false:
17566         \exp_after:wN \use_none:n
17567     \fi:
17568     \prg_return_true:
17569 \fi:
17570 }

```

(End definition for \\_\_regex\_hexadecimal\_use:NTF.)

\\_\_regex\_char\_if\_alphanumeric:NTF

These two tests are used in the first pass when parsing a regular expression. That pass is responsible for finding escaped and non-escaped characters, and recognizing which ones have special meanings and which should be interpreted as “raw” characters. Namely,

- alphanumeric characters are “raw” if they are not escaped, and may have a special meaning when escaped;
- non-alphanumeric printable ascii characters are “raw” if they are escaped, and may have a special meaning when not escaped;
- characters other than printable ascii are always “raw”.

The code is ugly, and highly based on magic numbers and the ascii codes of characters. This is mostly unavoidable for performance reasons. Maybe the tests can be optimized a little bit more. Here, “alphanumeric” means 0–9, A–Z, a–z; “special” character means non-alphanumeric but printable ascii, from space (hex 20) to del (hex 7E).

```

17571 \prg_new_conditional:Npnn \__regex_char_if_special:N #1 { TF }
17572 {
17573     \if_int_compare:w ‘#1 > ‘Z \exp_stop_f:
17574     \if_int_compare:w ‘#1 > ‘z \exp_stop_f:
17575     \if_int_compare:w ‘#1 < \c__regex_ascii_max_int
17576     \prg_return_true: \else: \prg_return_false: \fi:
17577     \else:
17578     \if_int_compare:w ‘#1 < ‘a \exp_stop_f:
17579     \prg_return_true: \else: \prg_return_false: \fi:
17580     \fi:
17581     \else:
17582     \if_int_compare:w ‘#1 > ‘9 \exp_stop_f:
17583     \if_int_compare:w ‘#1 < ‘A \exp_stop_f:
17584     \prg_return_true: \else: \prg_return_false: \fi:
17585     \else:
17586     \if_int_compare:w ‘#1 < ‘0 \exp_stop_f:
17587     \if_int_compare:w ‘#1 < ‘\ \exp_stop_f:
17588     \prg_return_false: \else: \prg_return_true: \fi:
17589     \else: \prg_return_false: \fi:

```

```

17590     \fi:
17591   \fi:
17592 }
17593 \prg_new_conditional:Npnn \_regex_char_if_alphanumeric:N #1 { TF }
17594 {
17595   \if_int_compare:w '#1 > 'Z \exp_stop_f:
17596   \if_int_compare:w '#1 > 'z \exp_stop_f:
17597   \prg_return_false:
17598   \else:
17599     \if_int_compare:w '#1 < 'a \exp_stop_f:
17600     \prg_return_false: \else: \prg_return_true: \fi:
17601   \fi:
17602   \else:
17603     \if_int_compare:w '#1 > '9 \exp_stop_f:
17604     \if_int_compare:w '#1 < 'A \exp_stop_f:
17605     \prg_return_false: \else: \prg_return_true: \fi:
17606   \else:
17607     \if_int_compare:w '#1 < '0 \exp_stop_f:
17608     \prg_return_false: \else: \prg_return_true: \fi:
17609   \fi:
17610   \fi:
17611 }

```

(End definition for `\_regex_char_if_alphanumeric:N` and `\_regex_char_if_special:N`.)

### 36.3 Compiling

A regular expression starts its life as a string of characters. In this section, we convert it to internal instructions, resulting in a “compiled” regular expression. This compiled expression is then turned into states of an automaton in the building phase. Compiled regular expressions consist of the following:

- `\_regex_class:NnnnN`  $\langle \text{boolean} \rangle$   $\{ \langle \text{tests} \rangle \}$   $\{ \langle \text{min} \rangle \}$   $\{ \langle \text{more} \rangle \}$   $\langle \text{lazyness} \rangle$
- `\_regex_group:nnnN`  $\{ \langle \text{branches} \rangle \}$   $\{ \langle \text{min} \rangle \}$   $\{ \langle \text{more} \rangle \}$   $\langle \text{lazyness} \rangle$ , also `\_regex_group_no_capture:nnnN` and `\_regex_group_resetting:nnnN` with the same syntax.
- `\_regex_branch:n`  $\{ \langle \text{contents} \rangle \}$
- `\_regex_command_K:`
- `\_regex_assertion:Nn`  $\langle \text{boolean} \rangle$   $\{ \langle \text{assertion test} \rangle \}$ , where the  $\langle \text{assertion test} \rangle$  is `\_regex_b_test:` or  $\{ \_regex_anchor:N \langle \text{integer} \rangle \}$

Tests can be the following:

- `\_regex_item_caseful_equal:n`  $\{ \langle \text{char code} \rangle \}$
- `\_regex_item_caseless_equal:n`  $\{ \langle \text{char code} \rangle \}$
- `\_regex_item_caseful_range:nn`  $\{ \langle \text{min} \rangle \}$   $\{ \langle \text{max} \rangle \}$
- `\_regex_item_caseless_range:nn`  $\{ \langle \text{min} \rangle \}$   $\{ \langle \text{max} \rangle \}$
- `\_regex_item_catcode:nT`  $\{ \langle \text{catcode bitmap} \rangle \}$   $\{ \langle \text{tests} \rangle \}$



- `\__regex_item_catcode_reverse:nT`  $\{\langle catcode\ bitmap\rangle\}$   $\{\langle tests\rangle\}$
- `\__regex_item_reverse:n`  $\{\langle tests\rangle\}$
- `\__regex_item_exact:nn`  $\{\langle catcode\rangle\}$   $\{\langle char\ code\rangle\}$
- `\__regex_item_exact_cs:n`  $\{\langle csnames\rangle\}$ , more precisely given as  $\langle csname\rangle\ \backslash scan\_stop: \langle csname\rangle\ \backslash scan\_stop: \langle csname\rangle$  and so on in a brace group.
- `\__regex_item_cs:n`  $\{\langle compiled\ regex\rangle\}$

### 36.3.1 Variables used when compiling

`\l__regex_group_level_int` We make sure to open the same number of groups as we close.

```
17612 \int_new:N \l__regex_group_level_int
```

(End definition for `\l__regex_group_level_int`.)

`\l__regex_mode_int` While compiling, ten modes are recognized, labelled  $-63$ ,  $-23$ ,  $-6$ ,  $-2$ ,  $0$ ,  $2$ ,  $3$ ,  $6$ ,  $23$ ,  $63$ .  
`\c__regex_cs_in_class_mode_int` See section 36.3.3. We only define some of these as constants.

```
17613 \int_new:N \l__regex_mode_int
17614 \int_const:Nn \c__regex_cs_in_class_mode_int { -6 }
17615 \int_const:Nn \c__regex_cs_mode_int { -2 }
17616 \int_const:Nn \c__regex_outer_mode_int { 0 }
17617 \int_const:Nn \c__regex_catcode_mode_int { 2 }
17618 \int_const:Nn \c__regex_class_mode_int { 3 }
17619 \int_const:Nn \c__regex_catcode_in_class_mode_int { 6 }
```

(End definition for `\l__regex_mode_int` and others.)

`\l__regex_catcodes_int` We wish to allow constructions such as `\c[~BE](. . \cL[a-z] . .)`, where the outer catcode test applies to the whole group, but is superseded by the inner catcode test. For this to work, we need to keep track of lists of allowed category codes: `\l__regex_catcodes_int` and `\l__regex_default_catcodes_int` are bitmaps, sums of  $4^c$ , for all allowed catcodes  $c$ . The latter is local to each capturing group, and we reset `\l__regex_catcodes_int` to that value after each character or class, changing it only when encountering a `\c` escape. The boolean records whether the list of categories of a catcode test has to be inverted: compare `\c[~BE]` and `\c[BE]`.

```
17620 \int_new:N \l__regex_catcodes_int
17621 \int_new:N \l__regex_default_catcodes_int
17622 \bool_new:N \l__regex_catcodes_bool
```

(End definition for `\l__regex_catcodes_int`, `\l__regex_default_catcodes_int`, and `\l__regex_catcodes_bool`.)

`\c__regex_catcode_C_int` Constants:  $4^c$  for each category, and the sum of all powers of 4.

```
17623 \int_const:Nn \c__regex_catcode_C_int { "1 }
17624 \int_const:Nn \c__regex_catcode_B_int { "4 }
17625 \int_const:Nn \c__regex_catcode_E_int { "10 }
17626 \int_const:Nn \c__regex_catcode_M_int { "40 }
17627 \int_const:Nn \c__regex_catcode_T_int { "100 }
17628 \int_const:Nn \c__regex_catcode_P_int { "1000 }
17629 \int_const:Nn \c__regex_catcode_U_int { "4000 }
17630 \int_const:Nn \c__regex_catcode_D_int { "10000 }
17631 \int_const:Nn \c__regex_catcode_S_int { "100000 }
```

```
\c__regex_catcode_O_int
\c__regex_catcode_A_int
\c__regex_all_catcodes_int
```

```

17632 \int_const:Nn \c__regex_catcode_L_int { "400000 }
17633 \int_const:Nn \c__regex_catcode_O_int { "1000000 }
17634 \int_const:Nn \c__regex_catcode_A_int { "4000000 }
17635 \int_const:Nn \c__regex_all_catcodes_int { "5515155 }

```

(End definition for \c\_\_regex\_catcode\_C\_int and others.)

`\l__regex_internal_regex` The compilation step stores its result in this variable.

```

17636 \cs_new_eq:NN \l__regex_internal_regex \c__regex_no_match_regex

```

(End definition for \l\_\_regex\_internal\_regex.)

`\l__regex_show_prefix_seq` This sequence holds the prefix that makes up the line displayed to the user. The various items must be removed from the right, which is tricky with a token list, hence we use a sequence.

```

17637 \seq_new:N \l__regex_show_prefix_seq

```

(End definition for \l\_\_regex\_show\_prefix\_seq.)

`\l__regex_show_lines_int` A hack. To know whether a given class has a single item in it or not, we count the number of lines when showing the class.

```

17638 \int_new:N \l__regex_show_lines_int

```

(End definition for \l\_\_regex\_show\_lines\_int.)

### 36.3.2 Generic helpers used when compiling

`\__regex_get_digits:NTFw` If followed by some raw digits, collect them one by one in the integer variable #1, and take the true branch. Otherwise, take the false branch.

```

17639 \cs_new_protected:Npn \__regex_get_digits:NTFw #1#2#3#4#5
17640 {
17641   \__regex_if_raw_digit:NNTF #4 #5
17642   { #1 = #5 \__regex_get_digits_loop:nw {#2} }
17643   { #3 #4 #5 }
17644 }
17645 \cs_new:Npn \__regex_get_digits_loop:nw #1#2#3
17646 {
17647   \__regex_if_raw_digit:NNTF #2 #3
17648   { #3 \__regex_get_digits_loop:nw {#1} }
17649   { \scan_stop: #1 #2 #3 }
17650 }

```

(End definition for \\_\_regex\_get\_digits:NTFw and \\_\_regex\_get\_digits\_loop:w.)

`\__regex_if_raw_digit:NNTF` Test used when grabbing digits for the {m,n} quantifier. It only accepts non-escaped digits.

```

17651 \prg_new_conditional:Npnn \__regex_if_raw_digit:NN #1#2 { TF }
17652 {
17653   \if_meaning:w \__regex_compile_raw:N #1
17654   \if_int_compare:w 1 < 1 #2 \exp_stop_f:
17655   \prg_return_true:
17656   \else:
17657   \prg_return_false:
17658   \fi:
17659   \else:

```

```

17660         \prg_return_false:
17661     \fi:
17662 }

```

(End definition for `\_regex_if_raw_digit:NNTF`.)

### 36.3.3 Mode

When compiling the NFA corresponding to a given regex string, we can be in ten distinct modes, which we label by some magic numbers:

- 6 `[\c{...}]` control sequence in a class,
- 2 `\c{...}` control sequence,
- 0 ... outer,
- 2 `\c...` catcode test,
- 6 `[\c...]` catcode test in a class,
- 63 `[\c{[...]}]` class inside mode -6,
- 23 `\c{[...]}` class inside mode -2,
- 3 `[...]` class inside mode 0,
- 23 `\c[...]` class inside mode 2,
- 63 `[\c[...]]` class inside mode 6.

This list is exhaustive, because `\c` escape sequences cannot be nested, and character classes cannot be nested directly. The choice of numbers is such as to optimize the most useful tests, and make transitions from one mode to another as simple as possible.

- Even modes mean that we are not directly in a character class. In this case, a left bracket appends 3 to the mode. In a character class, a right bracket changes the mode as  $m \rightarrow (m - 15)/13$ , truncated.
- Grouping, assertion, and anchors are allowed in non-positive even modes (0, -2, -6), and do not change the mode. Otherwise, they trigger an error.
- A left bracket is special in even modes, appending 3 to the mode; in those modes, quantifiers and the dot are recognized, and the right bracket is normal. In odd modes (within classes), the left bracket is normal, but the right bracket ends the class, changing the mode from  $m$  to  $(m - 15)/13$ , truncated; also, ranges are recognized.
- In non-negative modes, left and right braces are normal. In negative modes, however, left braces trigger a warning; right braces end the control sequence, going from -2 to 0 or -6 to 3, with error recovery for odd modes.
- Properties (such as the `\d` character class) can appear in any mode.

`\_regex_if_in_class:TF` Test whether we are directly in a character class (at the innermost level of nesting). There, many escape sequences are not recognized, and special characters are normal. Also, for every raw character, we must look ahead for a possible raw dash.

```

17663 \cs_new:Npn \_regex_if_in_class:TF
17664 {
17665   \if_int_odd:w \l__regex_mode_int
17666     \exp_after:wN \use_i:nn
17667   \else:
17668     \exp_after:wN \use_ii:nn
17669   \fi:
17670 }

```

(End definition for `\_regex_if_in_class:TF`.)

`\_regex_if_in_cs:TF` Right braces are special only directly inside control sequences (at the inner-most level of nesting, not counting groups).

```

17671 \cs_new:Npn \_regex_if_in_cs:TF
17672 {
17673   \if_int_odd:w \l__regex_mode_int
17674     \exp_after:wN \use_ii:nn
17675   \else:
17676     \if_int_compare:w \l__regex_mode_int < \c__regex_outer_mode_int
17677       \exp_after:wN \exp_after:wN \exp_after:wN \use_i:nn
17678     \else:
17679       \exp_after:wN \exp_after:wN \exp_after:wN \use_ii:nn
17680     \fi:
17681   \fi:
17682 }

```

(End definition for `\_regex_if_in_cs:TF`.)

`\_regex_if_in_class_or_catcode:TF` Assertions are only allowed in modes 0, -2, and -6, *i.e.*, even, non-positive modes.

```

17683 \cs_new:Npn \_regex_if_in_class_or_catcode:TF
17684 {
17685   \if_int_odd:w \l__regex_mode_int
17686     \exp_after:wN \use_i:nn
17687   \else:
17688     \if_int_compare:w \l__regex_mode_int > \c__regex_outer_mode_int
17689       \exp_after:wN \exp_after:wN \exp_after:wN \use_i:nn
17690     \else:
17691       \exp_after:wN \exp_after:wN \exp_after:wN \use_ii:nn
17692     \fi:
17693   \fi:
17694 }

```

(End definition for `\_regex_if_in_class_or_catcode:TF`.)

`\_regex_if_within_catcode:TF` This test takes the true branch if we are in a catcode test, either immediately following it (modes 2 and 6) or in a class on which it applies (modes 23 and 63). This is used to tweak how left brackets behave in modes 2 and 6.

```

17695 \cs_new:Npn \_regex_if_within_catcode:TF
17696 {
17697   \if_int_compare:w \l__regex_mode_int > \c__regex_outer_mode_int
17698     \exp_after:wN \use_i:nn

```

```

17699     \else:
17700         \exp_after:wN \use_ii:nn
17701     \fi:
17702 }

```

(End definition for \\_regex\_if\_within\_catcode:TF.)

\\_regex\_chk\_c\_allowed:T The \c escape sequence is only allowed in modes 0 and 3, *i.e.*, not within any other \c escape sequence.

```

17703 \cs_new_protected:Npn \_regex_chk_c_allowed:T
17704 {
17705     \if_int_compare:w \l__regex_mode_int = \c__regex_outer_mode_int
17706         \exp_after:wN \use:n
17707     \else:
17708         \if_int_compare:w \l__regex_mode_int = \c__regex_class_mode_int
17709             \exp_after:wN \exp_after:wN \exp_after:wN \use:n
17710         \else:
17711             \_msg_kernel_error:nn { kernel } { c-bad-mode }
17712             \exp_after:wN \exp_after:wN \exp_after:wN \use_none:n
17713         \fi:
17714     \fi:
17715 }

```

(End definition for \\_regex\_chk\_c\_allowed:T.)

\\_regex\_mode\_quit\_c: This function changes the mode as it is needed just after a catcode test.

```

17716 \cs_new_protected:Npn \_regex_mode_quit_c:
17717 {
17718     \if_int_compare:w \l__regex_mode_int = \c__regex_catcode_mode_int
17719         \int_set_eq:NN \l__regex_mode_int \c__regex_outer_mode_int
17720     \else:
17721         \if_int_compare:w \l__regex_mode_int = \c__regex_catcode_in_class_mode_int
17722             \int_set_eq:NN \l__regex_mode_int \c__regex_class_mode_int
17723         \fi:
17724     \fi:
17725 }

```

(End definition for \\_regex\_mode\_quit\_c:.)

### 36.3.4 Framework

\\_regex\_compile:w Used when compiling a user regex or a regex for the \c{...} escape sequence within another regex. Start building a token list within a group (with x-expansion at the outset), and set a few variables (group level, catcodes), then start the first branch. At the end, make sure there are no dangling classes nor groups, close the last branch: we are done building \l\_\_regex\_internal\_regex.

```

17726 \cs_new_protected:Npn \_regex_compile:w
17727 {
17728     \__tl_build_x:Nw \l__regex_internal_regex
17729     \int_zero:N \l__regex_group_level_int
17730     \int_set_eq:NN \l__regex_default_catcodes_int \c__regex_all_catcodes_int
17731     \int_set_eq:NN \l__regex_catcodes_int \l__regex_default_catcodes_int
17732     \cs_set:Npn \_regex_item_equal:n { \_regex_item_caseful_equal:n }
17733     \cs_set:Npn \_regex_item_range:nn { \_regex_item_caseful_range:nn }

```

```

17734     \__tl_build_one:n { \__regex_branch:n { \if_false: } \fi: }
17735   }
17736 \cs_new_protected:Npn \__regex_compile_end:
17737 {
17738   \__regex_if_in_class:TF
17739   {
17740     \__msg_kernel_error:nn { kernel } { missing-rbrack }
17741     \use:c { \__regex_compile_] : }
17742     \prg_do_nothing: \prg_do_nothing:
17743   }
17744   { }
17745   \if_int_compare:w \l__regex_group_level_int > 0 \exp_stop_f:
17746     \__msg_kernel_error:nnx { kernel } { missing-rparen }
17747     { \int_use:N \l__regex_group_level_int }
17748     \prg_replicate:nn
17749     { \l__regex_group_level_int }
17750     {
17751       \__tl_build_one:n
17752       {
17753         \if_false: { \fi: }
17754         \if_false: { \fi: } { 1 } { 0 } \c_true_bool
17755       }
17756       \__tl_build_end:
17757       \__tl_build_one:o \l__regex_internal_regex
17758     }
17759     \fi:
17760     \__tl_build_one:n { \if_false: { \fi: } }
17761   \__tl_build_end:
17762 }

```

(End definition for \\_\_regex\_compile:w and \\_\_regex\_compile\_end:.)

\\_\_regex\_compile:n The compilation is done between \\_\_regex\_compile:w and \\_\_regex\_compile\_end:, starting in mode 0. Then \\_\_regex\_escape\_use:nnnn distinguishes special characters, escaped alphanumerics, and raw characters, interpreting \a, \x and other sequences. The 4 trailing \prg\_do\_nothing: are needed because some functions defined later look up to 4 tokens ahead. Before ending, make sure that any \c{...} is properly closed. No need to check that brackets are closed properly since \\_\_regex\_compile\_end: does that. However, catch the case of a trailing \cL construction.

```

17763 \cs_new_protected:Npn \__regex_compile:n #1
17764 {
17765   \__regex_compile:w
17766   \__regex_standard_escapechar:
17767   \int_set_eq:NN \l__regex_mode_int \c__regex_outer_mode_int
17768   \__regex_escape_use:nnnn
17769   {
17770     \__regex_char_if_special:NTF ##1
17771     \__regex_compile_special:N \__regex_compile_raw:N ##1
17772   }
17773   {
17774     \__regex_char_if_alphanumeric:NTF ##1
17775     \__regex_compile_escaped:N \__regex_compile_raw:N ##1
17776   }
17777   { \__regex_compile_raw:N ##1 }

```

```

17778     { #1 }
17779     \prg_do_nothing: \prg_do_nothing:
17780     \prg_do_nothing: \prg_do_nothing:
17781     \int_compare:nNnT \l__regex_mode_int = \c__regex_catcode_mode_int
17782     { \__msg_kernel_error:nn { kernel } { c-trailing } }
17783     \int_compare:nNnT \l__regex_mode_int < \c__regex_outer_mode_int
17784     {
17785         \__msg_kernel_error:nn { kernel } { c-missing-rbrace }
17786         \__regex_compile_end_cs:
17787         \prg_do_nothing: \prg_do_nothing:
17788         \prg_do_nothing: \prg_do_nothing:
17789     }
17790     \__regex_compile_end:
17791 }

```

(End definition for \\_\_regex\_compile:n.)

\\_\_regex\_compile\_escaped:N If the special character or escaped alphanumeric has a particular meaning in regexes, the corresponding function is used. Otherwise, it is interpreted as a raw character. We distinguish special characters from escaped alphanumeric characters because they behave differently when appearing as an end-point of a range.

```

17792 \cs_new_protected:Npn \__regex_compile_special:N #1
17793 {
17794     \cs_if_exist_use:cF { __regex_compile_#1: }
17795     { \__regex_compile_raw:N #1 }
17796 }
17797 \cs_new_protected:Npn \__regex_compile_escaped:N #1
17798 {
17799     \cs_if_exist_use:cF { __regex_compile_/#1: }
17800     { \__regex_compile_raw:N #1 }
17801 }

```

(End definition for \\_\_regex\_compile\_escaped:N and \\_\_regex\_compile\_special:N.)

\\_\_regex\_compile\_one:x This is used after finding one “test”, such as \d, or a raw character. If that followed a catcode test (e.g., \cL), then restore the mode. If we are not in a class, then the test is “standalone”, and we need to add \\_\_regex\_class:NnnnN and search for quantifiers. In any case, insert the test, possibly together with a catcode test if appropriate.

```

17802 \cs_new_protected:Npn \__regex_compile_one:x #1
17803 {
17804     \__regex_mode_quit_c:
17805     \__regex_if_in_class:TF { }
17806     {
17807         \__tl_build_one:n
17808         { \__regex_class:NnnnN \c_true_bool { \if_false: } \fi: }
17809     }
17810     \__tl_build_one:x
17811     {
17812         \if_int_compare:w \l__regex_catcodes_int < \c__regex_all_catcodes_int
17813         \__regex_item_catcode:nT { \int_use:N \l__regex_catcodes_int }
17814         { \exp_not:N \exp_not:n {#1} }
17815         \else:
17816         \exp_not:N \exp_not:n {#1}
17817         \fi:

```

```

17818     }
17819     \int_set_eq:NN \l__regex_catcodes_int \l__regex_default_catcodes_int
17820     \__regex_if_in_class:TF { } { \__regex_compile_quantifier:w }
17821 }

```

(End definition for \\_\_regex\_compile\_one:x.)

\\_\_regex\_compile\_abort\_tokens:n This function places the collected tokens back in the input stream, each as a raw character.  
 \\_\_regex\_compile\_abort\_tokens:x Spaces are not preserved.

```

17822 \cs_new_protected:Npn \__regex_compile_abort_tokens:n #1
17823 {
17824   \use:x
17825   {
17826     \exp_args:No \tl_map_function:nN { \tl_to_str:n {#1} }
17827     \__regex_compile_raw:N
17828   }
17829 }
17830 \cs_generate_variant:Nn \__regex_compile_abort_tokens:n { x }

```

(End definition for \\_\_regex\_compile\_abort\_tokens:n.)

### 36.3.5 Quantifiers

\\_\_regex\_compile\_quantifier:w This looks ahead and finds any quantifier (special character equal to either of ?+\*{ ).

```

17831 \cs_new_protected:Npn \__regex_compile_quantifier:w #1#2
17832 {
17833   \token_if_eq_meaning:NNTF #1 \__regex_compile_special:N
17834   {
17835     \cs_if_exist_use:cF { \__regex_compile_quantifier_#2:w }
17836     { \__regex_compile_quantifier_none: #1 #2 }
17837   }
17838   { \__regex_compile_quantifier_none: #1 #2 }
17839 }

```

(End definition for \\_\_regex\_compile\_quantifier:w.)

\\_\_regex\_compile\_quantifier\_none: Those functions are called whenever there is no quantifier, or a braced construction is invalid (equivalent to no quantifier, and whatever characters were grabbed are left raw).  
 \\_\_regex\_compile\_quantifier\_abort:xNN

```

17840 \cs_new_protected:Npn \__regex_compile_quantifier_none:
17841 { \__tl_build_one:n { \if_false: { \fi: } { 1 } { 0 } \c_false_bool } }
17842 \cs_new_protected:Npn \__regex_compile_quantifier_abort:xNN #1#2#3
17843 {
17844   \__regex_compile_quantifier_none:
17845   \__msg_kernel_warning:nxx { kernel } { invalid-quantifier } {#1} {#3}
17846   \__regex_compile_abort_tokens:x {#1}
17847   #2 #3
17848 }

```

(End definition for \\_\_regex\_compile\_quantifier\_none: and \\_\_regex\_compile\_quantifier\_abort:xNN.)

\\_\_regex\_compile\_quantifier\_lazy:nnNN Once the “main” quantifier ( ?, \*, + or a braced construction ) is found, we check whether it is lazy ( followed by a question mark ). We then add to the compiled regex a closing brace ( ending \\_\_regex\_class:NnnnN and friends ), the start-point of the range, its end-point, and a boolean, true for lazy and false for greedy operators.



```

17849 \cs_new_protected:Npn \__regex_compile_quantifier_lazyiness:nnNN #1#2#3#4
17850 {
17851   \str_if_eq:nnTF { #3 #4 } { \__regex_compile_special:N ? }
17852   { \__tl_build_one:n { \if_false: { \fi: } { #1 } { #2 } \c_true_bool } }
17853   {
17854     \__tl_build_one:n { \if_false: { \fi: } { #1 } { #2 } \c_false_bool }
17855     #3 #4
17856   }
17857 }

```

(End definition for `\__regex_compile_quantifier_lazyiness:nnNN`.)

`\__regex_compile_quantifier?:w` For each “basic” quantifier, `?`, `*`, `+`, feed the correct arguments to `\__regex_compile_quantifier_lazyiness:nnNN`, `-1` means that there is no upper bound on the number of repetitions.

```

17858 \cs_new_protected:cpn { \__regex_compile_quantifier?:w }
17859 { \__regex_compile_quantifier_lazyiness:nnNN { 0 } { 1 } }
17860 \cs_new_protected:cpn { \__regex_compile_quantifier*:w }
17861 { \__regex_compile_quantifier_lazyiness:nnNN { 0 } { -1 } }
17862 \cs_new_protected:cpn { \__regex_compile_quantifier+:w }
17863 { \__regex_compile_quantifier_lazyiness:nnNN { 1 } { -1 } }

```

(End definition for `\__regex_compile_quantifier?:w`, `\__regex_compile_quantifier*:w`, and `\__regex_compile_quantifier+:w`.)

`\__regex_compile_quantifier{ :w` Three possible syntaxes: `{⟨int⟩}`, `{⟨int⟩,}`, or `{⟨int⟩,⟨int⟩}`. Any other syntax causes us to abort and put whatever we collected back in the input stream, as `raw` characters, including the opening brace. Grab a number into `\l__regex_internal_a_int`. If the number is followed by a right brace, the range is `[a, a]`. If followed by a comma, grab one more number, and call the `_ii` or `_iii` auxiliary. Those auxiliaries check for a closing brace, leading to the range `[a, ∞]` or `[a, b]`, encoded as `{a}{-1}` and `{a}{b-a}`.

```

17864 \cs_new_protected:cpn { \__regex_compile_quantifier_ \c_left_brace_str :w }
17865 {
17866   \__regex_get_digits:NTFw \l__regex_internal_a_int
17867   { \__regex_compile_quantifier_braced_auxi:w }
17868   { \__regex_compile_quantifier_abort:xNN { \c_left_brace_str } }
17869 }
17870 \cs_new_protected:Npn \__regex_compile_quantifier_braced_auxi:w #1#2
17871 {
17872   \str_case_x:nnF { #1 #2 }
17873   {
17874     { \__regex_compile_special:N \c_right_brace_str }
17875     {
17876       \exp_args:No \__regex_compile_quantifier_lazyiness:nnNN
17877       { \int_use:N \l__regex_internal_a_int } { 0 }
17878     }
17879     { \__regex_compile_special:N , }
17880     {
17881       \__regex_get_digits:NTFw \l__regex_internal_b_int
17882       { \__regex_compile_quantifier_braced_auxiii:w }
17883       { \__regex_compile_quantifier_braced_auxii:w }
17884     }
17885   }
17886 }

```

```

17887     \_regex_compile_quantifier_abort:xNN
17888     { \c_left_brace_str \int_use:N \l__regex_internal_a_int }
17889     #1 #2
17890   }
17891 }
17892 \cs_new_protected:Npn \_regex_compile_quantifier_braced_auxii:w #1#2
17893 {
17894   \str_if_eq_x:nnTF
17895   { #1 #2 } { \_regex_compile_special:N \c_right_brace_str }
17896   {
17897     \exp_args:No \_regex_compile_quantifier_lazyness:nnNN
17898     { \int_use:N \l__regex_internal_a_int } { -1 }
17899   }
17900   {
17901     \_regex_compile_quantifier_abort:xNN
17902     { \c_left_brace_str \int_use:N \l__regex_internal_a_int , }
17903     #1 #2
17904   }
17905 }
17906 \cs_new_protected:Npn \_regex_compile_quantifier_braced_auxiii:w #1#2
17907 {
17908   \str_if_eq_x:nnTF
17909   { #1 #2 } { \_regex_compile_special:N \c_right_brace_str }
17910   {
17911     \if_int_compare:w \l__regex_internal_a_int > \l__regex_internal_b_int
17912     \_msg_kernel_error:nxxx { kernel } { backwards-quantifier }
17913     { \int_use:N \l__regex_internal_a_int }
17914     { \int_use:N \l__regex_internal_b_int }
17915     \int_zero:N \l__regex_internal_b_int
17916   \else:
17917     \int_sub:Nn \l__regex_internal_b_int \l__regex_internal_a_int
17918   \fi:
17919   \exp_args:Noo \_regex_compile_quantifier_lazyness:nnNN
17920   { \int_use:N \l__regex_internal_a_int }
17921   { \int_use:N \l__regex_internal_b_int }
17922 }
17923 {
17924   \_regex_compile_quantifier_abort:xNN
17925   {
17926     \c_left_brace_str
17927     \int_use:N \l__regex_internal_a_int ,
17928     \int_use:N \l__regex_internal_b_int
17929   }
17930   #1 #2
17931 }
17932 }

```

(End definition for `\_regex_compile_quantifier_{:w}` and others.)

### 36.3.6 Raw characters

`\_regex_compile_raw_error:N` Within character classes, and following catcode tests, some escaped alphanumeric sequences such as `\b` do not have any meaning. They are replaced by a raw character, after spitting out an error.

```

17933 \cs_new_protected:Npn \__regex_compile_raw_error:N #1
17934 {
17935   \__msg_kernel_error:nnx { kernel } { bad-escape } {#1}
17936   \__regex_compile_raw:N #1
17937 }

```

(End definition for \\_\_regex\_compile\_raw\_error:N.)

**\\_\_regex\_compile\_raw:N** If we are in a character class and the next character is an unescaped dash, this denotes a range. Otherwise, the current character #1 matches itself.

```

17938 \cs_new_protected:Npn \__regex_compile_raw:N #1#2#3
17939 {
17940   \__regex_if_in_class:TF
17941   {
17942     \str_if_eq:nnTF {#2#3} { \__regex_compile_special:N - }
17943     { \__regex_compile_range:Nw #1 }
17944     {
17945       \__regex_compile_one:x
17946       { \__regex_item_equal:n { \__int_value:w '#1 ~ } }
17947       #2 #3
17948     }
17949   }
17950   {
17951     \__regex_compile_one:x
17952     { \__regex_item_equal:n { \__int_value:w '#1 ~ } }
17953     #2 #3
17954   }
17955 }

```

(End definition for \\_\_regex\_compile\_raw:N.)

**\\_\_regex\_compile\_range:Nw** We have just read a raw character followed by a dash; this should be followed by an end-point for the range. Valid end-points are: any raw character; any special character, except a right bracket. In particular, escaped characters are forbidden.

**\\_\_regex\_if\_end\_range:NNTF**

```

17956 \prg_new_protected_conditional:Npnn \__regex_if_end_range:NN #1#2 { TF }
17957 {
17958   \if_meaning:w \__regex_compile_raw:N #1
17959   \prg_return_true:
17960   \else:
17961     \if_meaning:w \__regex_compile_special:N #1
17962     \if_charcode:w ] #2
17963     \prg_return_false:
17964     \else:
17965       \prg_return_true:
17966     \fi:
17967     \else:
17968       \prg_return_false:
17969     \fi:
17970   \fi:
17971 }
17972 \cs_new_protected:Npn \__regex_compile_range:Nw #1#2#3
17973 {
17974   \__regex_if_end_range:NNTF #2 #3
17975   {

```

```

17976     \if_int_compare:w '#1 > '#3 \exp_stop_f:
17977     \__msg_kernel_error:nxxx { kernel } { range-backwards } {#1} {#3}
17978   \else:
17979     \__tl_build_one:x
17980     {
17981       \if_int_compare:w '#1 = '#3 \exp_stop_f:
17982       \__regex_item_equal:n
17983     \else:
17984       \__regex_item_range:nn { \__int_value:w '#1 ~ }
17985     \fi:
17986     { \__int_value:w '#3 ~ }
17987   }
17988   \fi:
17989 }
17990 {
17991   \__msg_kernel_warning:nxxx { kernel } { range-missing-end }
17992   {#1} { \c_backslash_str #3 }
17993   \__tl_build_one:x
17994   {
17995     \__regex_item_equal:n { \__int_value:w '#1 ~ }
17996     \__regex_item_equal:n { \__int_value:w '- ~ }
17997   }
17998   #2#3
17999 }
18000 }

```

(End definition for \\_\_regex\_compile\_range:Nw and \\_\_regex\_if\_end\_range:NNTF.)

### 36.3.7 Character properties

\\_\_regex\_compile\_.: In a class, the dot has no special meaning. Outside, insert \\_\_regex\_prop\_., which matches any character or control sequence, and refuses -2 (end-marker).

```

18001 \cs_new_protected:cpx { __regex_compile_.: }
18002 {
18003   \exp_not:N \__regex_if_in_class:TF
18004   { \__regex_compile_raw:N . }
18005   { \__regex_compile_one:x \exp_not:c { __regex_prop_.: } }
18006 }
18007 \cs_new_protected:cpn { __regex_prop_.: }
18008 {
18009   \if_int_compare:w \l__regex_curr_char_int > - 2 \exp_stop_f:
18010   \exp_after:wN \__regex_break_true:w
18011   \fi:
18012 }

```

(End definition for \\_\_regex\_compile\_.: and \\_\_regex\_prop\_..)

\\_\_regex\_compile\_/d: The constants \\_\_regex\_prop\_d:, etc. hold a list of tests which match the corresponding character class, and jump to the \\_\_regex\_break\_point:TF marker. As for a normal character, we check for quantifiers.

```

18013 \cs_set_protected:Npn \__regex_tmp:w #1#2
18014 {
18015   \cs_new_protected:cpx { __regex_compile_/#1: }
18016   { \__regex_compile_one:x \exp_not:c { __regex_prop_#1: } }

```

\\_\_regex\_compile\_/V:  
 \\_\_regex\_compile\_/w:  
 \\_\_regex\_compile\_/W:  
 \\_\_regex\_compile\_/N:

```

18017 \cs_new_protected:cpx { __regex_compile_/#2: }
18018 {
18019     \__regex_compile_one:x
18020     { \__regex_item_reverse:n \exp_not:c { __regex_prop_#1: } }
18021 }
18022 }
18023 \__regex_tmp:w d D
18024 \__regex_tmp:w h H
18025 \__regex_tmp:w s S
18026 \__regex_tmp:w v V
18027 \__regex_tmp:w w W
18028 \cs_new_protected:cpn { __regex_compile_/N: }
18029 { \__regex_compile_one:x \__regex_prop_N: }

```

(End definition for \\_\_regex\_compile\_/d: and others.)

### 36.3.8 Anchoring and simple assertions

\\_\_regex\_compile\_anchor:NF In modes where assertions are allowed, anchor to the start of the query, the start of the match, or the end of the query, depending on the integer #1. In other modes, #2 treats the character as raw, with an error for escaped letters (\$ is valid in a class, but \A is definitely a mistake on the user's part).

```

\__regex_compile_~:
\__regex_compile_/A:
\__regex_compile_/G:
\__regex_compile_$:
\__regex_compile_/Z:
\__regex_compile_/z:
18030 \cs_new_protected:Npn \__regex_compile_anchor:NF #1#2
18031 {
18032     \__regex_if_in_class_or_catcode:TF {#2}
18033     {
18034         \__tl_build_one:n
18035         { \__regex_assertion:Nn \c_true_bool { \__regex_anchor:N #1 } }
18036     }
18037 }
18038 \cs_set_protected:Npn \__regex_tmp:w #1#2
18039 {
18040     \cs_new_protected:cpn { __regex_compile_/#1: }
18041     { \__regex_compile_anchor:NF #2 { \__regex_compile_raw_error:N #1 } }
18042 }
18043 \__regex_tmp:w A \l__regex_min_pos_int
18044 \__regex_tmp:w G \l__regex_start_pos_int
18045 \__regex_tmp:w Z \l__regex_max_pos_int
18046 \__regex_tmp:w z \l__regex_max_pos_int
18047 \cs_set_protected:Npn \__regex_tmp:w #1#2
18048 {
18049     \cs_new_protected:cpn { __regex_compile_#1: }
18050     { \__regex_compile_anchor:NF #2 { \__regex_compile_raw:N #1 } }
18051 }
18052 \exp_args:Nx \__regex_tmp:w { \iow_char:N \^ } \l__regex_min_pos_int
18053 \exp_args:Nx \__regex_tmp:w { \iow_char:N \$ } \l__regex_max_pos_int

```

(End definition for \\_\_regex\_compile\_anchor:NF and others.)

\\_\_regex\_compile\_/b: Contrarily to ^ and \$, which could be implemented without really knowing what precedes in the token list, this requires more information, namely, the knowledge of the last character code.

```

18054 \cs_new_protected:cpn { __regex_compile_/b: }
18055 {

```

```

18056     \__regex_if_in_class_or_catcode:TF
18057     { \__regex_compile_raw_error:N b }
18058     {
18059         \__tl_build_one:n
18060         { \__regex_assertion:Nn \c_true_bool { \__regex_b_test: } }
18061     }
18062 }
18063 \cs_new_protected:cpn { __regex_compile_/B: }
18064 {
18065     \__regex_if_in_class_or_catcode:TF
18066     { \__regex_compile_raw_error:N B }
18067     {
18068         \__tl_build_one:n
18069         { \__regex_assertion:Nn \c_false_bool { \__regex_b_test: } }
18070     }
18071 }

```

(End definition for \\_\_regex\_compile\_/b: and \\_\_regex\_compile\_/B:.)

### 36.3.9 Character classes

`\__regex_compile_:` Outside a class, right brackets have no meaning. In a class, change the mode ( $m \rightarrow (m - 15)/13$ , truncated) to reflect the fact that we are leaving the class. Look for quantifiers, unless we are still in a class after leaving one (the case of `[... \cL[...] ...]`). quantifiers.

```

18072 \cs_new_protected:cpn { __regex_compile_[: }
18073 {
18074     \__regex_if_in_class:TF
18075     {
18076         \if_int_compare:w \l__regex_mode_int > \c__regex_catcode_in_class_mode_int
18077         \__tl_build_one:n { \if_false: { \fi: } }
18078         \fi:
18079         \tex_advance:D \l__regex_mode_int - 15 \exp_stop_f:
18080         \tex_divide:D \l__regex_mode_int 13 \exp_stop_f:
18081         \if_int_odd:w \l__regex_mode_int \else:
18082             \exp_after:wN \__regex_compile_quantifier:w
18083         \fi:
18084     }
18085     { \__regex_compile_raw:N ] }
18086 }

```

(End definition for \\_\_regex\_compile\_[:.)

`\__regex_compile_[:` In a class, left brackets might introduce a POSIX character class, or mean nothing. Immediately following `\c<category>`, we must insert the appropriate catcode test, then parse the class; we pre-expand the catcode as an optimization. Otherwise (modes 0, -2 and -6) just parse the class. The mode is updated later.

```

18087 \cs_new_protected:cpn { __regex_compile_[[: }
18088 {
18089     \__regex_if_in_class:TF
18090     { \__regex_compile_class_posix_test:w }
18091     {
18092         \__regex_if_within_catcode:TF
18093         {
18094             \exp_after:wN \__regex_compile_class_catcode:w

```

```

18095         \int_use:N \l__regex_catcodes_int ;
18096     }
18097     { \__regex_compile_class_normal:w }
18098 }
18099 }

```

(End definition for \\_\_regex\_compile\_[:.])

\\_\_regex\_compile\_class\_normal:w In the “normal” case, we insert \\_\_regex\_class:NnnnN *<boolean>* in the compiled code. The *<boolean>* is true for positive classes, and false for negative classes, characterized by a leading  $\sim$ . The auxiliary \\_\_regex\_compile\_class:TFNN also checks for a leading ] which has a special meaning.

```

18100 \cs_new_protected:Npn \__regex_compile_class_normal:w
18101 {
18102     \__regex_compile_class:TFNN
18103     { \__regex_class:NnnnN \c_true_bool }
18104     { \__regex_class:NnnnN \c_false_bool }
18105 }

```

(End definition for \\_\_regex\_compile\_class\_normal:w.)

\\_\_regex\_compile\_class\_catcode:w This function is called for a left bracket in modes 2 or 6 (catcode test, and catcode test within a class). In mode 2 the whole construction needs to be put in a class (like single character). Then determine if the class is positive or negative, inserting \\_\_regex\_item\_catcode:nT or the reverse variant as appropriate, each with the current catcodes bitmap #1 as an argument, and reset the catcodes.

```

18106 \cs_new_protected:Npn \__regex_compile_class_catcode:w #1;
18107 {
18108     \if_int_compare:w \l__regex_mode_int = \c__regex_catcode_mode_int
18109     \__tl_build_one:n
18110     { \__regex_class:NnnnN \c_true_bool { \if_false: } \fi: }
18111     \fi:
18112     \int_set_eq:NN \l__regex_catcodes_int \l__regex_default_catcodes_int
18113     \__regex_compile_class:TFNN
18114     { \__regex_item_catcode:nT {#1} }
18115     { \__regex_item_catcode_reverse:nT {#1} }
18116 }

```

(End definition for \\_\_regex\_compile\_class\_catcode:w.)

\\_\_regex\_compile\_class:TFNN If the first character is  $\sim$ , then the class is negative (use #2), otherwise it is positive (use #1). If the next character is a right bracket, then it should be changed to a raw one.

```

18117 \cs_new_protected:Npn \__regex_compile_class:TFNN #1#2#3#4
18118 {
18119     \l__regex_mode_int = \__int_value:w \l__regex_mode_int 3 \exp_stop_f:
18120     \str_if_eq:nnTF { #3 #4 } { \__regex_compile_special:N ^ }
18121     {
18122         \__tl_build_one:n { #2 { \if_false: } \fi: }
18123         \__regex_compile_class:NN
18124     }
18125     {
18126         \__tl_build_one:n { #1 { \if_false: } \fi: }
18127         \__regex_compile_class:NN #3 #4
18128     }

```

```

18129 }
18130 \cs_new_protected:Npn \__regex_compile_class:NN #1#2
18131 {
18132   \token_if_eq_charcode:NNTF #2 ]
18133   { \__regex_compile_raw:N #2 }
18134   { #1 #2 }
18135 }

```

(End definition for \\_\_regex\_compile\_class:TFNN and \\_\_regex\_compile\_class:NN.)

\\_\_regex\_compile\_class\_posix\_test:w Here we check for a syntax such as [:alpha:]. We also detect [= and [. which have a meaning in POSIX regular expressions, but are not implemented in l3regex. In case we see [:, grab raw characters until hopefully reaching :]. If that's missing, or the POSIX class is unknown, abort. If all is right, add the test to the current class, with an extra \\_\_regex\_item\_reverse:n for negative classes.

```

18136 \cs_new_protected:Npn \__regex_compile_class_posix_test:w #1#2
18137 {
18138   \token_if_eq_meaning:NNT \__regex_compile_special:N #1
18139   {
18140     \str_case:nn { #2 }
18141     {
18142       : { \__regex_compile_class_posix:NNNNw }
18143       = { \__msg_kernel_warning:nxx { kernel } { posix-unsupported } { = } }
18144       . { \__msg_kernel_warning:nxx { kernel } { posix-unsupported } { . } }
18145     }
18146   }
18147   \__regex_compile_raw:N [ #1 #2
18148 }
18149 \cs_new_protected:Npn \__regex_compile_class_posix:NNNNw #1#2#3#4#5#6
18150 {
18151   \str_if_eq:nnTF { #5 #6 } { \__regex_compile_special:N ^ }
18152   {
18153     \bool_set_false:N \l__regex_internal_bool
18154     \tl_set:Nx \l__regex_internal_a_tl { \if_false: } \fi:
18155     \__regex_compile_class_posix_loop:w
18156   }
18157   {
18158     \bool_set_true:N \l__regex_internal_bool
18159     \tl_set:Nx \l__regex_internal_a_tl { \if_false: } \fi:
18160     \__regex_compile_class_posix_loop:w #5 #6
18161   }
18162 }
18163 \cs_new:Npn \__regex_compile_class_posix_loop:w #1#2
18164 {
18165   \token_if_eq_meaning:NNTF \__regex_compile_raw:N #1
18166   { #2 \__regex_compile_class_posix_loop:w }
18167   { \if_false: { \fi: } \__regex_compile_class_posix_end:w #1 #2 }
18168 }
18169 \cs_new_protected:Npn \__regex_compile_class_posix_end:w #1#2#3#4
18170 {
18171   \str_if_eq:nnTF { #1 #2 #3 #4 }
18172   { \__regex_compile_special:N : \__regex_compile_special:N ] }
18173   {
18174     \cs_if_exist:cTF { __regex_posix_ \l__regex_internal_a_tl : }

```



```

18175         {
18176             \__regex_compile_one:x
18177             {
18178                 \bool_if:NF \l__regex_internal_bool \__regex_item_reverse:n
18179                 \exp_not:c { \__regex_posix_ \l__regex_internal_a_tl : }
18180             }
18181         }
18182         {
18183             \__msg_kernel_warning:nxx { kernel } { posix-unknown }
18184             { \l__regex_internal_a_tl }
18185             \__regex_compile_abort_tokens:x
18186             {
18187                 [: \bool_if:NF \l__regex_internal_bool { ^ }
18188                 \l__regex_internal_a_tl :]
18189             }
18190         }
18191     }
18192     {
18193         \__msg_kernel_error:nxxx { kernel } { posix-missing-close }
18194         { [: \l__regex_internal_a_tl ] { #2 #4 }
18195         \__regex_compile_abort_tokens:x { [: \l__regex_internal_a_tl ]
18196         #1 #2 #3 #4
18197         }
18198     }

```

(End definition for \\_\_regex\_compile\_class\_posix\_test:w and others.)

### 36.3.10 Groups and alternations

\\_\_regex\_compile\_group\_begin:N The contents of a regex group are turned into compiled code in \l\_\_regex\_internal\_regex, which ends up with items of the form \\_\_regex\_branch:n {<concatenation>}. This construction is done using l3tl-build within a TeX group, which automatically makes sure that options (case-sensitivity and default catcode) are reset at the end of the group. The argument #1 is \\_\_regex\_group:nnnN or a variant thereof. A small subtlety to support \cL(abc) as a shorthand for (\cLa\cLb\cLc): exit any pending catcode test, save the category code at the start of the group as the default catcode for that group, and make sure that the catcode is restored to the default outside the group.

```

18199 \cs_new_protected:Npn \__regex_compile_group_begin:N #1
18200 {
18201     \__tl_build_one:n { #1 { \if_false: } \fi: }
18202     \__regex_mode_quit_c:
18203     \__tl_build:Nw \l__regex_internal_regex
18204     \int_set_eq:NN \l__regex_default_catcodes_int \l__regex_catcodes_int
18205     \int_incr:N \l__regex_group_level_int
18206     \__tl_build_one:n { \__regex_branch:n { \if_false: } \fi: }
18207 }
18208 \cs_new_protected:Npn \__regex_compile_group_end:
18209 {
18210     \if_int_compare:w \l__regex_group_level_int > 0 \exp_stop_f:
18211     \__tl_build_one:n { \if_false: { \fi: } }
18212     \__tl_build_end:
18213     \int_set_eq:NN \l__regex_catcodes_int \l__regex_default_catcodes_int
18214     \__tl_build_one:o \l__regex_internal_regex
18215     \exp_after:wN \__regex_compile_quantifier:w

```

```

18216 \else:
18217   \__msg_kernel_warning:nn { kernel } { extra-rparen }
18218   \exp_after:wN \__regex_compile_raw:N \exp_after:wN )
18219 \fi:
18220 }

```

(End definition for \\_\_regex\_compile\_group\_begin:N and \\_\_regex\_compile\_group\_end:.)

\\_\_regex\_compile(: In a class, parentheses are not special. Outside, check for a ?, denoting special groups, and run the code for the corresponding special group.

```

18221 \cs_new_protected:cpn { __regex_compile(: }
18222 {
18223   \__regex_if_in_class:TF { \__regex_compile_raw:N ( }
18224   { \__regex_compile_lparen:w }
18225 }
18226 \cs_new_protected:Npn \__regex_compile_lparen:w #1#2#3#4
18227 {
18228   \str_if_eq:nnTF { #1 #2 } { \__regex_compile_special:N ? }
18229   {
18230     \cs_if_exist_use:cF
18231     { __regex_compile_special_group\_token_to_str:N #4 :w }
18232     {
18233       \__msg_kernel_warning:nnx { kernel } { special-group-unknown }
18234       { (? #4 }
18235       \__regex_compile_group_begin:N \__regex_group:nnnN
18236       \__regex_compile_raw:N ? #3 #4
18237     }
18238   }
18239   {
18240     \__regex_compile_group_begin:N \__regex_group:nnnN
18241     #1 #2 #3 #4
18242   }
18243 }

```

(End definition for \\_\_regex\_compile(:.)

\\_\_regex\_compile\_|: In a class, the pipe is not special. Otherwise, end the current branch and open another one.

```

18244 \cs_new_protected:cpn { __regex_compile_|: }
18245 {
18246   \__regex_if_in_class:TF { \__regex_compile_raw:N | }
18247   {
18248     \__tl_build_one:n
18249     { \if_false: { \fi: } \__regex_branch:n { \if_false: } \fi: }
18250   }
18251 }

```

(End definition for \\_\_regex\_compile\_|:.)

\\_\_regex\_compile\_): Within a class, parentheses are not special. Outside, close a group.

```

18252 \cs_new_protected:cpn { __regex_compile_): }
18253 {
18254   \__regex_if_in_class:TF { \__regex_compile_raw:N ) }
18255   { \__regex_compile_group_end: }
18256 }

```

(End definition for `\_regex_compile_`:.)

`\_regex_compile_special_group_::w` Non-capturing, and resetting groups are easy to take care of during compilation; for those  
`\_regex_compile_special_group_|:w` groups, the harder parts come when building.

```
18257 \cs_new_protected:cpn { \_regex_compile_special_group_::w }
18258 { \_regex_compile_group_begin:N \_regex_group_no_capture:nnnN }
18259 \cs_new_protected:cpn { \_regex_compile_special_group_|:w }
18260 { \_regex_compile_group_begin:N \_regex_group_resetting:nnnN }
```

(End definition for `\_regex_compile_special_group_::w` and `\_regex_compile_special_group_|:w`.)

`\_regex_compile_special_group_i:w` The match can be made case-insensitive by setting the option with `(?i)`; the original  
`\_regex_compile_special_group_-:w` behaviour is restored by `(?-i)`. This is the only supported option.

```
18261 \cs_new_protected:Npn \_regex_compile_special_group_i:w #1#2
18262 {
18263   \str_if_eq:nnTF { #1 #2 } { \_regex_compile_special:N ) }
18264   {
18265     \cs_set:Npn \_regex_item_equal:n { \_regex_item_caseless_equal:n }
18266     \cs_set:Npn \_regex_item_range:nn { \_regex_item_caseless_range:nn }
18267   }
18268   {
18269     \_msg_kernel_warning:nnx { kernel } { unknown-option } { (?i #2 }
18270     \_regex_compile_raw:N (
18271     \_regex_compile_raw:N ?
18272     \_regex_compile_raw:N i
18273     #1 #2
18274   }
18275 }
18276 \cs_new_protected:cpn { \_regex_compile_special_group_-:w } #1#2#3#4
18277 {
18278   \str_if_eq:nnTF { #1 #2 #3 #4 }
18279   { \_regex_compile_raw:N i \_regex_compile_special:N ) }
18280   {
18281     \cs_set:Npn \_regex_item_equal:n { \_regex_item_caseful_equal:n }
18282     \cs_set:Npn \_regex_item_range:nn { \_regex_item_caseful_range:nn }
18283   }
18284   {
18285     \_msg_kernel_warning:nnx { kernel } { unknown-option } { (?-#2#4 }
18286     \_regex_compile_raw:N (
18287     \_regex_compile_raw:N ?
18288     \_regex_compile_raw:N -
18289     #1 #2 #3 #4
18290   }
18291 }
```

(End definition for `\_regex_compile_special_group_i:w` and `\_regex_compile_special_group_-:w`.)

### 36.3.11 Catcodes and csnames

`\_regex_compile_/c:` The `\c` escape sequence can be followed by a capital letter representing a character  
`\_regex_compile_c_test:NN` category, by a left bracket which starts a list of categories, or by a brace group holding  
 a regular expression for a control sequence name. Otherwise, raise an error.

```
18292 \cs_new_protected:cpn { \_regex_compile_/c: }
18293 { \_regex_chk_c_allowed:T { \_regex_compile_c_test:NN } }
```

```

18294 \cs_new_protected:Npn \__regex_compile_c_test:NN #1#2
18295 {
18296   \token_if_eq_meaning:NNTF #1 \__regex_compile_raw:N
18297   {
18298     \int_if_exist:cTF { c__regex_catcode_#2_int }
18299     {
18300       \int_set_eq:Nc \l__regex_catcodes_int { c__regex_catcode_#2_int }
18301       \l__regex_mode_int
18302       = \if_case:w \l__regex_mode_int
18303         \c__regex_catcode_mode_int
18304       \else:
18305         \c__regex_catcode_in_class_mode_int
18306       \fi:
18307       \token_if_eq_charcode:NNT C #2 { \__regex_compile_c_C:NN }
18308     }
18309   }
18310   { \cs_if_exist_use:cF { __regex_compile_c_#2:w } }
18311   {
18312     \__msg_kernel_error:nnx { kernel } { c-missing-category } {#2}
18313     #1 #2
18314   }
18315 }

```

(End definition for \\_\_regex\_compile\_/c: and \\_\_regex\_compile\_c\_test:NN.)

\\_\_regex\_compile\_c\_C:NN If \cC is not followed by . or (...) then complain because that construction cannot match anything, except in cases like \cC[\c{...}], where it has no effect.

```

18316 \cs_new_protected:Npn \__regex_compile_c_C:NN #1#2
18317 {
18318   \token_if_eq_meaning:NNTF #1 \__regex_compile_special:N
18319   {
18320     \token_if_eq_charcode:NNTF #2 .
18321     { \use_none:n }
18322     { \token_if_eq_charcode:NNTF #2 ( } % )
18323   }
18324   { \use_n:n }
18325   { \__msg_kernel_error:nnn { kernel } { c-C-invalid } {#2} }
18326   #1 #2
18327 }

```

(End definition for \\_\_regex\_compile\_c\_C:NN.)

\\_\_regex\_compile\_c[:w When encountering \c[, the task is to collect uppercase letters representing character categories. First check for ^ which negates the list of category codes.

```

\__regex_compile_c_lbrack_loop:NN
\__regex_compile_c_lbrack_add:N
\__regex_compile_c_lbrack_end:
18328 \cs_new_protected:cpn { __regex_compile_c[:w } #1#2
18329 {
18330   \l__regex_mode_int
18331   = \if_case:w \l__regex_mode_int
18332     \c__regex_catcode_mode_int
18333   \else:
18334     \c__regex_catcode_in_class_mode_int
18335   \fi:
18336   \int_zero:N \l__regex_catcodes_int
18337   \str_if_eq:nnTF { #1 #2 } { \__regex_compile_special:N ^ }

```

```

18338     {
18339         \bool_set_false:N \l__regex_catcodes_bool
18340         \__regex_compile_c_lbrack_loop:NN
18341     }
18342     {
18343         \bool_set_true:N \l__regex_catcodes_bool
18344         \__regex_compile_c_lbrack_loop:NN
18345         #1 #2
18346     }
18347 }
18348 \cs_new_protected:Npn \__regex_compile_c_lbrack_loop:NN #1#2
18349 {
18350     \token_if_eq_meaning:NNTF #1 \__regex_compile_raw:N
18351     {
18352         \int_if_exist:cTF { c__regex_catcode_#2_int }
18353         {
18354             \exp_args:Nc \__regex_compile_c_lbrack_add:N
18355                 { c__regex_catcode_#2_int }
18356             \__regex_compile_c_lbrack_loop:NN
18357         }
18358     }
18359     {
18360         \token_if_eq_charcode:NNTF #2 ]
18361         { \__regex_compile_c_lbrack_end: }
18362     }
18363     {
18364         \__msg_kernel_error:nmx { kernel } { c-missing-rbrack } {#2}
18365         \__regex_compile_c_lbrack_end:
18366         #1 #2
18367     }
18368 }
18369 \cs_new_protected:Npn \__regex_compile_c_lbrack_add:N #1
18370 {
18371     \if_int_odd:w \__int_eval:w \l__regex_catcodes_int / #1 \__int_eval_end:
18372     \else:
18373         \int_add:Nn \l__regex_catcodes_int {#1}
18374     \fi:
18375 }
18376 \cs_new_protected:Npn \__regex_compile_c_lbrack_end:
18377 {
18378     \if_meaning:w \c_false_bool \l__regex_catcodes_bool
18379     \int_set:Nn \l__regex_catcodes_int
18380     { \c__regex_all_catcodes_int - \l__regex_catcodes_int }
18381     \fi:
18382 }

```

(End definition for `\__regex_compile_c[:w]` and others.)

`\__regex_compile_c_{`: The case of a left brace is easy, based on what we have done so far: in a group, compile the regular expression, after changing the mode to forbid nesting `\c`. Additionally, disable submatch tracking since groups don't escape the scope of `\c{...}`.

```

18383 \cs_new_protected:cpn { __regex_compile_c_ \c_left_brace_str :w }
18384 {
18385     \__regex_compile:w

```

```

18386     \_regex_disable_submatches:
18387     \l\_regex_mode_int
18388     = \if_case:w \l\_regex_mode_int
18389       \c\_regex_cs_mode_int
18390     \else:
18391       \c\_regex_cs_in_class_mode_int
18392     \fi:
18393   }

```

(End definition for \\_regex\_compile\_c{:.})

\\_regex\_compile\_}: Non-escaped right braces are only special if they appear when compiling the regular expression for a csname, but not within a class: \c{[{}]} matches the control sequences \{ and \}. So, end compiling the inner regex (this closes any dangling class or group). Then insert the corresponding test in the outer regex. As an optimization, if the control sequence test simply consists of several explicit possibilities (branches) then use \\_regex\_item\_exact\_cs:n with an argument consisting of all possibilities separated by \scan\_stop:.

```

18394 \flag_new:n { \_regex_cs }
18395 \cs_new_protected:cpn { \_regex_compile_ \c_right_brace_str : }
18396 {
18397   \_regex_if_in_cs:TF
18398   { \_regex_compile_end_cs: }
18399   { \exp_after:wN \_regex_compile_raw:N \c_right_brace_str }
18400 }
18401 \cs_new_protected:Npn \_regex_compile_end_cs:
18402 {
18403   \_regex_compile_end:
18404   \flag_clear:n { \_regex_cs }
18405   \tl_set:Nx \l\_regex_internal_a_tl
18406   {
18407     \exp_after:wN \_regex_compile_cs_aux:Nn \l\_regex_internal_regex
18408     \q_nil \q_nil \q_recursion_stop
18409   }
18410   \exp_args:Nx \_regex_compile_one:x
18411   {
18412     \flag_if_raised:nTF { \_regex_cs }
18413     { \_regex_item_cs:n { \exp_not:o \l\_regex_internal_regex } }
18414     { \_regex_item_exact_cs:n { \tl_tail:N \l\_regex_internal_a_tl } }
18415   }
18416 }
18417 \cs_new:Npn \_regex_compile_cs_aux:Nn #1#2
18418 {
18419   \cs_if_eq:NNTF #1 \_regex_branch:n
18420   {
18421     \scan_stop:
18422     \_regex_compile_cs_aux:NnnnnN #2
18423     \q_nil \q_nil \q_nil \q_nil \q_nil \q_nil \q_recursion_stop
18424     \_regex_compile_cs_aux:Nn
18425   }
18426   {
18427     \quark_if_nil:NF #1 { \flag_raise:n { \_regex_cs } }
18428     \use_none_delimit_by_q_recursion_stop:w
18429   }

```

```

18430 }
18431 \cs_new:Npn \__regex_compile_cs_aux:NNnnnN #1#2#3#4#5#6
18432 {
18433   \bool_lazy_all:nTF
18434   {
18435     { \cs_if_eq_p:NN #1 \__regex_class:NnnnN }
18436     {#2}
18437     { \tl_if_head_eq_meaning_p:nN {#3} \__regex_item_caseful_equal:n }
18438     { \int_compare_p:nNn { \tl_count:n {#3} } = { 2 } }
18439     { \int_compare_p:nNn {#5} = { 0 } }
18440   }
18441   {
18442     \prg_replicate:nn {#4}
18443     { \char_generate:nn { \use_ii:nn #3 } {12} }
18444     \__regex_compile_cs_aux:NNnnnN
18445   }
18446   {
18447     \quark_if_nil:NF #1
18448     {
18449       \flag_raise:n { \__regex_cs }
18450       \use_i_delimit_by_q_recursion_stop:nw
18451     }
18452     \use_none_delimit_by_q_recursion_stop:w
18453   }
18454 }

```

(End definition for `\__regex_compile_`: and others.)

### 36.3.12 Raw token lists with `\u`

```

\__regex_compile_/u:
\__regex_compile_u_loop:NN

```

The `\u` escape is invalid in classes and directly following a catcode test. Otherwise, it must be followed by a left brace. We then collect the characters for the argument of `\u` within an `x`-expanding assignment. In principle we could just wait to encounter a right brace, but this is unsafe: if the right brace was missing, then we would reach the end-markers of the regex, and continue, leading to obscure fatal errors. Instead, we only allow raw and special characters, and stop when encountering a special right brace, any escaped character, or the end-marker.

```

18455 \cs_new_protected:cpn { \__regex_compile_/u: } #1#2
18456 {
18457   \__regex_if_in_class_or_catcode:TF
18458   { \__regex_compile_raw_error:N u #1 #2 }
18459   {
18460     \str_if_eq_x:nnTF {#1#2} { \__regex_compile_special:N \c_left_brace_str }
18461     {
18462       \tl_set:Nx \l__regex_internal_a_tl { \if_false: } \fi:
18463       \__regex_compile_u_loop:NN
18464     }
18465     {
18466       \__msg_kernel_error:nn { kernel } { u-missing-lbrace }
18467       \__regex_compile_raw:N u #1 #2
18468     }
18469   }
18470 }
18471 \cs_new:Npn \__regex_compile_u_loop:NN #1#2

```

```

18472 {
18473   \token_if_eq_meaning:NNTF #1 \__regex_compile_raw:N
18474   { #2 \__regex_compile_u_loop:NN }
18475   {
18476     \token_if_eq_meaning:NNTF #1 \__regex_compile_special:N
18477     {
18478       \exp_after:wN \token_if_eq_charcode:NNTF \c_right_brace_str #2
18479       { \if_false: { \fi: } \__regex_compile_u_end: }
18480       { #2 \__regex_compile_u_loop:NN }
18481     }
18482     {
18483       \if_false: { \fi: }
18484       \__msg_kernel_error:nxx { kernel } { u-missing-rbrace } {#2}
18485       \__regex_compile_u_end:
18486       #1 #2
18487     }
18488   }
18489 }

```

(End definition for \\_\_regex\_compile\_/u: and \\_\_regex\_compile\_u\_loop:NN.)

\\_\_regex\_compile\_u\_end: Once we have extracted the variable's name, we store the contents of that variable in \l\_\_regex\_internal\_a\_tl. The behaviour of \u then depends on whether we are within a \c{...} escape (in this case, the variable is turned to a string), or not.

```

18490 \cs_new_protected:Npn \__regex_compile_u_end:
18491 {
18492   \tl_set:Nv \l__regex_internal_a_tl { \l__regex_internal_a_tl }
18493   \if_int_compare:w \l__regex_mode_int = \c__regex_outer_mode_int
18494     \__regex_compile_u_not_cs:
18495   \else:
18496     \__regex_compile_u_in_cs:
18497   \fi:
18498 }

```

(End definition for \\_\_regex\_compile\_u\_end:.)

\\_\_regex\_compile\_u\_in\_cs: When \u appears within a control sequence, we convert the variable to a string with escaped spaces. Then for each character insert a class matching exactly that character, once.

```

18499 \cs_new_protected:Npn \__regex_compile_u_in_cs:
18500 {
18501   \tl_gset:Nx \g__regex_internal_tl
18502   { \exp_args:No \__str_to_other_fast:n { \l__regex_internal_a_tl } }
18503   \__tl_build_one:x
18504   {
18505     \tl_map_function:NN \g__regex_internal_tl
18506     \__regex_compile_u_in_cs_aux:n
18507   }
18508 }
18509 \cs_new:Npn \__regex_compile_u_in_cs_aux:n #1
18510 {
18511   \__regex_class:NnnnN \c_true_bool
18512   { \__regex_item_caseful_equal:n { \__int_value:w '#1 } }
18513   { 1 } { 0 } \c_false_bool
18514 }

```



(End definition for `\_regex_compile_u_in_cs:`)

`\_regex_compile_u_not_cs:` In mode 0, the `\u` escape adds one state to the NFA for each token in `\l\_regex\_internal\_a\_tl`. If a given *<token>* is a control sequence, then insert a string comparison test, otherwise, `\_regex_item_exact:nn` which compares catcode and character code.

```

18515 \cs_new_protected:Npn \_regex_compile_u_not_cs:
18516   {
18517     \exp_args:No \_tl_analysis_map_inline:nn { \l\_regex\_internal\_a\_tl }
18518     {
18519       \_tl_build_one:n
18520       {
18521         \_regex_class:NnnN \c_true_bool
18522         {
18523           \if_int_compare:w "##2 = 0 \exp_stop_f:
18524             \_regex_item_exact_cs:n { \exp_after:wN \cs_to_str:N ##1 }
18525           \else:
18526             \_regex_item_exact:nn { \_int_value:w "##2 } { ##3 }
18527           \fi:
18528         }
18529         { 1 } { 0 } \c_false_bool
18530       }
18531     }
18532   }

```

(End definition for `\_regex_compile_u_not_cs:`)

### 36.3.13 Other

`\_regex_compile_/K:` The `\K` control sequence is currently the only “command”, which performs some action, rather than matching something. It is allowed in the same contexts as `\b`. At the compilation stage, we leave it as a single control sequence, defined later.

```

18533 \cs_new_protected:cpn { \_regex_compile_/K: }
18534   {
18535     \int_compare:nNnTF \l\_regex_mode_int = \c\_regex_outer_mode_int
18536       { \_tl_build_one:n { \_regex_command_K: } }
18537       { \_regex_compile_raw_error:N K }
18538   }

```

(End definition for `\_regex_compile_/K:`)

### 36.3.14 Showing regexes

`\_regex_show:Nn` Within a `\_tl_build:Nw ... \_tl_build_end:` group, we redefine all the function that can appear in a compiled regex, then run the regex. The result is then shown.

```

18539 \cs_new_protected:Npn \_regex_show:Nn #1#2
18540   {
18541     \_tl_build:Nw \l\_regex\_internal\_a\_tl
18542     \cs_set_protected:Npn \_regex_branch:n
18543     {
18544       \seq_pop_right:NN \l\_regex_show_prefix_seq \l\_regex\_internal\_a\_tl
18545       \_regex_show_one:n { +-branch }
18546       \seq_put_right:No \l\_regex_show_prefix_seq \l\_regex\_internal\_a\_tl
18547       \use:n
18548     }

```

```

18549 \cs_set_protected:Npn \__regex_group:nnnN
18550 { \__regex_show_group_aux:nnnnN { } }
18551 \cs_set_protected:Npn \__regex_group_no_capture:nnnN
18552 { \__regex_show_group_aux:nnnnN { ~(no~capture) } }
18553 \cs_set_protected:Npn \__regex_group_resetting:nnnN
18554 { \__regex_show_group_aux:nnnnN { ~(resetting) } }
18555 \cs_set_eq:NN \__regex_class:NnnnN \__regex_show_class:NnnnN
18556 \cs_set_protected:Npn \__regex_command_K:
18557 { \__regex_show_one:n { reset~match~start~(\iow_char:N\K) } }
18558 \cs_set_protected:Npn \__regex_assertion:Nn ##1##2
18559 { \__regex_show_one:n { \bool_if:NF ##1 { negative~ } assertion:~##2 } }
18560 \cs_set:Npn \__regex_b_test: { word~boundary }
18561 \cs_set_eq:NN \__regex_anchor:N \__regex_show_anchor_to_str:N
18562 \cs_set_protected:Npn \__regex_item_caseful_equal:n ##1
18563 { \__regex_show_one:n { char~code~\int_eval:n{##1} } }
18564 \cs_set_protected:Npn \__regex_item_caseful_range:nn ##1##2
18565 { \__regex_show_one:n { range~[\int_eval:n{##1}, \int_eval:n{##2}] } }
18566 \cs_set_protected:Npn \__regex_item_caseless_equal:n ##1
18567 { \__regex_show_one:n { char~code~\int_eval:n{##1}~(caseless) } }
18568 \cs_set_protected:Npn \__regex_item_caseless_range:nn ##1##2
18569 {
18570   \__regex_show_one:n
18571   { Range~[\int_eval:n{##1}, \int_eval:n{##2}]~(caseless) }
18572 }
18573 \cs_set_protected:Npn \__regex_item_catcode:Nt
18574 { \__regex_show_item_catcode:Nt \c_true_bool }
18575 \cs_set_protected:Npn \__regex_item_catcode_reverse:Nt
18576 { \__regex_show_item_catcode:Nt \c_false_bool }
18577 \cs_set_protected:Npn \__regex_item_reverse:n
18578 { \__regex_show_scope:nn { Reversed~match } }
18579 \cs_set_protected:Npn \__regex_item_exact:nn ##1##2
18580 { \__regex_show_one:n { char~##2,~catcode~##1 } }
18581 \cs_set_eq:NN \__regex_item_exact_cs:n \__regex_show_item_exact_cs:n
18582 \cs_set_protected:Npn \__regex_item_cs:n
18583 { \__regex_show_scope:nn { control~sequence } }
18584 \cs_set:cpn { __regex_prop_.: } { \__regex_show_one:n { any~token } }
18585 \seq_clear:N \l__regex_show_prefix_seq
18586 \__regex_show_push:n { ~ }
18587 \cs_if_exist_use:N #1
18588 \__tl_build_end:
18589 \__msg_show_variable:NNNnn #1 \cs_if_exist:NTF ? { }
18590 { >~Compiled~regex~#2: \l__regex_internal_a_tl }
18591 }

```

(End definition for \\_\_regex\_show:Nn.)

\\_\_regex\_show\_one:n Every part of the final message go through this function, which adds one line to the output, with the appropriate prefix.

```

18592 \cs_new_protected:Npn \__regex_show_one:n #1
18593 {
18594   \int_incr:N \l__regex_show_lines_int
18595   \__tl_build_one:x
18596   {
18597     \exp_not:N \

```

```

18598     \seq_map_function:NN \l__regex_show_prefix_seq \use:n
18599     #1
18600   }
18601 }

```

(End definition for \\_\_regex\_show\_one:n.)

\\_\_regex\_show\_push:n Enter and exit levels of nesting. The scope function prints its first argument as an “introduction”, then performs its second argument in a deeper level of nesting.

```

\__regex_show_pop:
\__regex_show_scope:nn
18602 \cs_new_protected:Npn \__regex_show_push:n #1
18603 { \seq_put_right:Nx \l__regex_show_prefix_seq { #1 ~ } }
18604 \cs_new_protected:Npn \__regex_show_pop:
18605 { \seq_pop_right:NN \l__regex_show_prefix_seq \l__regex_internal_a_tl }
18606 \cs_new_protected:Npn \__regex_show_scope:nn #1#2
18607 {
18608   \__regex_show_one:n {#1}
18609   \__regex_show_push:n { ~ }
18610   #2
18611   \__regex_show_pop:
18612 }

```

(End definition for \\_\_regex\_show\_push:n, \\_\_regex\_show\_pop:, and \\_\_regex\_show\_scope:nn.)

\\_\_regex\_show\_group\_aux:nnnnN We display all groups in the same way, simply adding a message, (no capture) or (resetting), to special groups. The odd \use\_ii:nn avoids printing a spurious +-branch for the first branch.

```

18613 \cs_new_protected:Npn \__regex_show_group_aux:nnnnN #1#2#3#4#5
18614 {
18615   \__regex_show_one:n { , -group~begin #1 }
18616   \__regex_show_push:n { | }
18617   \use_ii:nn #2
18618   \__regex_show_pop:
18619   \__regex_show_one:n
18620   { ‘-group~end \__regex_msg_repeated:nnN {#3} {#4} #5 }
18621 }

```

(End definition for \\_\_regex\_show\_group\_aux:nnnnN.)

\\_\_regex\_show\_class:NnnnN I’m entirely unhappy about this function: I couldn’t find a way to test if a class is a single test. Instead, collect the representation of the tests in the class. If that had more than one line, write Match or Don’t match on its own line, with the repeating information if any. Then the various tests on lines of their own, and finally a line. Otherwise, we need to evaluate the representation of the tests again (since the prefix is incorrect). That’s clunky, but not too expensive, since it’s only one test.

```

18622 \cs_set:Npn \__regex_show_class:NnnnN #1#2#3#4#5
18623 {
18624   \__tl_build:Nw \l__regex_internal_a_tl
18625   \int_zero:N \l__regex_show_lines_int
18626   \__regex_show_push:n {~}
18627   #2
18628   \exp_last_unbraced:Nf
18629   \int_case:nnF { \l__regex_show_lines_int }
18630   {
18631     {0}

```

```

18632         {
18633             \_tl_build_end:
18634             \_regex_show_one:n { \bool_if:NTF #1 { Fail } { Pass } }
18635         }
18636     {1}
18637     {
18638         \_tl_build_end:
18639         \bool_if:NTF #1
18640         {
18641             #2
18642             \_tl_build_one:n { \_regex_msg_repeated:nnN {#3} {#4} #5 }
18643         }
18644         {
18645             \_regex_show_one:n
18646             { Don't~match~\_regex_msg_repeated:nnN {#3} {#4} #5 }
18647             \_tl_build_one:o \l__regex_internal_a_tl
18648         }
18649     }
18650 }
18651 {
18652     \_tl_build_end:
18653     \_regex_show_one:n
18654     {
18655         \bool_if:NTF #1 { M } { Don't~m } atch
18656         \_regex_msg_repeated:nnN {#3} {#4} #5
18657     }
18658     \_tl_build_one:o \l__regex_internal_a_tl
18659 }
18660 }

```

(End definition for \\_regex\_show\_class:NnnnN.)

\\_regex\_show\_anchor\_to\_str:N The argument is an integer telling us where the anchor is. We convert that to the relevant info.

```

18661 \cs_new:Npn \_regex_show_anchor_to_str:N #1
18662 {
18663     anchor~at~
18664     \str_case:nnF { #1 }
18665     {
18666         { \l__regex_min_pos_int } { start~(\iow_char:N\A) }
18667         { \l__regex_start_pos_int } { start~of~match~(\iow_char:N\G) }
18668         { \l__regex_max_pos_int } { end~(\iow_char:N\Z) }
18669     }
18670     { <error:~'#1'~not~recognized> }
18671 }

```

(End definition for \\_regex\_show\_anchor\_to\_str:N.)

\\_regex\_show\_item\_catcode:NnT Produce a sequence of categories which the catcode bitmap #2 contains, and show it, indenting the tests on which this catcode constraint applies.

```

18672 \cs_new_protected:Npn \_regex_show_item_catcode:NnT #1#2
18673 {
18674     \seq_set_split:Nnn \l__regex_internal_seq { } { CBEMTPUDSLOA }
18675     \seq_set_filter:Nnn \l__regex_internal_seq \l__regex_internal_seq

```

```

18676     { \int_if_odd_p:n { #2 / \int_use:c { c__regex_catcode_##1_int } } }
18677 \__regex_show_scope:nn
18678 {
18679     categories~
18680     \seq_map_function:NN \l__regex_internal_seq \use:n
18681     , ~
18682     \bool_if:NF #1 { negative~ } class
18683 }
18684 }

```

(End definition for `\__regex_show_item_catcode:NnT`.)

`\__regex_show_item_exact_cs:n`

```

18685 \cs_new_protected:Npn \__regex_show_item_exact_cs:n #1
18686 {
18687     \seq_set_split:Nnn \l__regex_internal_seq { \scan_stop: } {#1}
18688     \seq_set_map:NNn \l__regex_internal_seq
18689     \l__regex_internal_seq { \iow_char:N\##1 }
18690     \__regex_show_one:n
18691     { control~sequence~ \seq_use:Nn \l__regex_internal_seq { ~or~ } }
18692 }

```

(End definition for `\__regex_show_item_exact_cs:n`.)

## 36.4 Building

### 36.4.1 Variables used while building

`\l__regex_min_state_int`    The last state that was allocated is `\l__regex_max_state_int - 1`, so that `\l__regex_max_state_int` always points to a free state. The `min_state` variable is 1, but is included to avoid hard-coding this value everywhere.

```

18693 \int_new:N \l__regex_min_state_int
18694 \int_set:Nn \l__regex_min_state_int { 1 }
18695 \int_new:N \l__regex_max_state_int

```

(End definition for `\l__regex_min_state_int` and `\l__regex_max_state_int`.)

`\l__regex_left_state_int`    Alternatives are implemented by branching from a `left` state into the various choices, then merging those into a `right` state. We store information about those states in two sequences. Those states are also used to implement group quantifiers. Most often, the `left` and `right` pointers only differ by 1.

```

18696 \int_new:N \l__regex_left_state_int
18697 \int_new:N \l__regex_right_state_int
18698 \seq_new:N \l__regex_left_state_seq
18699 \seq_new:N \l__regex_right_state_seq

```

(End definition for `\l__regex_left_state_int` and others.)

`\l__regex_capturing_group_int`    `\l__regex_capturing_group_int` is the next ID number to be assigned to a capturing group. This starts at 0 for the group enclosing the full regular expression, and groups are counted in the order of their left parenthesis, except when encountering `resetting` groups.

```

18700 \int_new:N \l__regex_capturing_group_int

```

(End definition for `\l__regex_capturing_group_int`.)

### 36.4.2 Framework

This phase is about going from a compiled regex to an NFA. Each state of the NFA is stored in a `\toks`. The operations which can appear in the `\toks` are

- `\__regex_action_start_wildcard`: inserted at the start of the regular expression to make it unanchored.
- `\__regex_action_success`: marks the exit state of the NFA.
- `\__regex_action_cost:n {⟨shift⟩}` is a transition from the current `⟨state⟩` to `⟨state⟩ + ⟨shift⟩`, which consumes the current character: the target state is saved and will be considered again when matching at the next position.
- `\__regex_action_free:n {⟨shift⟩}`, and `\__regex_action_free_group:n {⟨shift⟩}` are free transitions, which immediately perform the actions for the state `⟨state⟩ + ⟨shift⟩` of the NFA. They differ in how they detect and avoid infinite loops. For now, we just need to know that the `group` variant must be used for transitions back to the start of a group.
- `\__regex_action_submatch:n {⟨key⟩}` where the `⟨key⟩` is a group number followed by `<` or `>` for the beginning or end of group. This causes the current position in the query to be stored as the `⟨key⟩` submatch boundary.

We strive to preserve the following properties while building.

- The current capturing group is `capturing_group - 1`, and if a group opened now it would be labelled `capturing_group`.
- The last allocated state is `max_state - 1`, so `max_state` is a free state.
- The `left_state` points to a state to the left of the current group or of the last class.
- The `right_state` points to a newly created, empty state, with some transitions leading to it.
- The `left/right` sequences hold a list of the corresponding end-points of nested groups.

`\__regex_build:n` The `n`-type function first compiles its argument. Reset some variables. Allocate two states, and put a wildcard in state 0 (transitions to state 1 and 0 state). Then build the regex within a (capturing) group numbered 0 (current value of `capturing_group`). Finally, if the match reaches the last state, it is successful.

```
\__regex_build:N
18701 \cs_new_protected:Npn \__regex_build:n #1
18702 {
18703   \__regex_compile:n {#1}
18704   \__regex_build:N \l__regex_internal_regex
18705 }
18706 \cs_new_protected:Npn \__regex_build:N #1
18707 {
18708   {trace} \trace_push:nnn { regex } { 1 } { __regex_build }
18709   \__regex_standard_escapechar:
18710   \int_zero:N \l__regex_capturing_group_int
18711   \int_set_eq:NN \l__regex_max_state_int \l__regex_min_state_int
```

```

18712 \__regex_build_new_state:
18713 \__regex_build_new_state:
18714 \__regex_toks_put_right:Nn \l__regex_left_state_int
18715 { \__regex_action_start_wildcard: }
18716 \__regex_group:nnnN {#1} { 1 } { 0 } \c_false_bool
18717 \__regex_toks_put_right:Nn \l__regex_right_state_int
18718 { \__regex_action_success: }
18719 <trace> \__regex_trace_states:n { 2 }
18720 <trace> \trace_pop:nnn { regex } { 1 } { __regex_build }
18721 }

```

(End definition for \\_\_regex\_build:n and \\_\_regex\_build:N.)

\\_\_regex\_build\_for\_cs:n When using a regex to match a cs, we don't insert a wildcard, we anchor at the end, and since we ignore submatches, there is no need to surround the expression with a group. However, for branches to work properly at the outer level, we need to put the appropriate left and right states in their sequence.

```

18722 \cs_new_protected:Npn \__regex_build_for_cs:n #1
18723 {
18724 <trace> \trace_push:nnn { regex } { 1 } { __regex_build_for_cs }
18725 \int_set_eq:NN \l__regex_max_state_int \l__regex_min_state_int
18726 \__regex_build_new_state:
18727 \__regex_build_new_state:
18728 \__regex_push_lr_states:
18729 #1
18730 \__regex_pop_lr_states:
18731 \__regex_toks_put_right:Nn \l__regex_right_state_int
18732 {
18733 \if_int_compare:w \l__regex_curr_pos_int = \l__regex_max_pos_int
18734 \exp_after:wN \__regex_action_success:
18735 \fi:
18736 }
18737 <trace> \__regex_trace_states:n { 2 }
18738 <trace> \trace_pop:nnn { regex } { 1 } { __regex_build_for_cs }
18739 }

```

(End definition for \\_\_regex\_build\_for\_cs:n.)

### 36.4.3 Helpers for building an nfa

\\_\_regex\_push\_lr\_states: When building the regular expression, we keep track of pointers to the left-end and  
\\_\_regex\_pop\_lr\_states: right-end of each group without help from T<sub>E</sub>X's grouping.

```

18740 \cs_new_protected:Npn \__regex_push_lr_states:
18741 {
18742 \seq_push:No \l__regex_left_state_seq
18743 { \int_use:N \l__regex_left_state_int }
18744 \seq_push:No \l__regex_right_state_seq
18745 { \int_use:N \l__regex_right_state_int }
18746 }
18747 \cs_new_protected:Npn \__regex_pop_lr_states:
18748 {
18749 \seq_pop:NN \l__regex_left_state_seq \l__regex_internal_a_tl
18750 \int_set:Nn \l__regex_left_state_int \l__regex_internal_a_tl
18751 \seq_pop:NN \l__regex_right_state_seq \l__regex_internal_a_tl

```

```

18752     \int_set:Nn \l__regex_right_state_int \l__regex_internal_a_tl
18753   }

```

(End definition for \\_\_regex\_push\_lr\_states: and \\_\_regex\_pop\_lr\_states:.)

\\_\_regex\_build\_transition\_left:NNN Add a transition from #2 to #3 using the function #1. The left function is used for higher priority transitions, and the right function for lower priority transitions (which should be performed later). The signatures differ to reflect the differing usage later on. Both functions could be optimized.

```

18754 \cs_new_protected:Npn \__regex_build_transition_left:NNN #1#2#3
18755   { \__regex_toks_put_left:Nx #2 { #1 { \int_eval:n { #3 - #2 } } } }
18756 \cs_new_protected:Npn \__regex_build_transition_right:nNn #1#2#3
18757   { \__regex_toks_put_right:Nx #2 { #1 { \int_eval:n { #3 - #2 } } } }

```

(End definition for \\_\_regex\_build\_transition\_left:NNN and \\_\_regex\_build\_transition\_right:nNn.)

\\_\_regex\_build\_new\_state: Add a new empty state to the NFA. Then update the left, right, and max states, so that the right state is the new empty state, and the left state points to the previously “current” state.

```

18758 \cs_new_protected:Npn \__regex_build_new_state:
18759   {
18760     \*trace>
18761     \trace:nmx { regex } { 2 }
18762     {
18763       regex~new~state~
18764       L=\int_use:N \l__regex_left_state_int ~ -> ~
18765       R=\int_use:N \l__regex_right_state_int ~ -> ~
18766       M=\int_use:N \l__regex_max_state_int ~ -> ~
18767       \int_eval:n { \l__regex_max_state_int + 1 }
18768     }
18769   \*trace<
18770   \__regex_toks_clear:N \l__regex_max_state_int
18771   \int_set_eq:NN \l__regex_left_state_int \l__regex_right_state_int
18772   \int_set_eq:NN \l__regex_right_state_int \l__regex_max_state_int
18773   \int_incr:N \l__regex_max_state_int
18774   }

```

(End definition for \\_\_regex\_build\_new\_state:.)

\\_\_regex\_build\_transitions\_lazyness:NNNNN This function creates a new state, and puts two transitions starting from the old current state. The order of the transitions is controlled by #1, true for lazy quantifiers, and false for greedy quantifiers.

```

18775 \cs_new_protected:Npn \__regex_build_transitions_lazyness:NNNNN #1#2#3#4#5
18776   {
18777     \__regex_build_new_state:
18778     \__regex_toks_put_right:Nx \l__regex_left_state_int
18779     {
18780       \if_meaning:w \c_true_bool #1
18781         #2 { \int_eval:n { #3 - \l__regex_left_state_int } }
18782         #4 { \int_eval:n { #5 - \l__regex_left_state_int } }
18783       \else:
18784         #4 { \int_eval:n { #5 - \l__regex_left_state_int } }
18785         #2 { \int_eval:n { #3 - \l__regex_left_state_int } }
18786       \fi:

```



```

18787     }
18788 }

```

(End definition for `\_regex_build_transitions_lazyness:NNNNN`.)

### 36.4.4 Building classes

`\_regex_class:NnnnN` The arguments are:  $\langle\text{boolean}\rangle$   $\{\langle\text{tests}\rangle\}$   $\{\langle\text{min}\rangle\}$   $\{\langle\text{more}\rangle\}$   $\langle\text{lazyness}\rangle$ . First store the tests with a trailing `\_regex_action_cost:n`, in the true branch of `\_regex_break_point:TF` for positive classes, or the false branch for negative classes. The integer  $\langle\text{more}\rangle$  is 0 for fixed repetitions,  $-1$  for unbounded repetitions, and  $\langle\text{max}\rangle - \langle\text{min}\rangle$  for a range of repetitions.

```

18789 \cs_new_protected:Npn \_regex_class:NnnnN #1#2#3#4#5
18790 {
18791   \cs_set:Npx \_regex_tests_action_cost:n ##1
18792   {
18793     \exp_not:n { \exp_not:n {#2} }
18794     \bool_if:NTF #1
18795       { \_regex_break_point:TF { \_regex_action_cost:n {##1} } { } }
18796       { \_regex_break_point:TF { } { \_regex_action_cost:n {##1} } }
18797   }
18798   \if_case:w - #4 \exp_stop_f:
18799     \_regex_class_repeat:n {#3}
18800   \or: \_regex_class_repeat:nN {#3} #5
18801   \else: \_regex_class_repeat:nnN {#3} {#4} #5
18802   \fi:
18803 }
18804 \cs_new:Npn \_regex_tests_action_cost:n { \_regex_action_cost:n }

```

(End definition for `\_regex_class:NnnnN` and `\_regex_tests_action_cost:n`.)

`\_regex_class_repeat:n` This is used for a fixed number of repetitions. Build one state for each repetition, with a transition controlled by the tests that we have collected. That works just fine for  $\#1 = 0$  repetitions: nothing is built.

```

18805 \cs_new_protected:Npn \_regex_class_repeat:n #1
18806 {
18807   \prg_replicate:nn {#1}
18808   {
18809     \_regex_build_new_state:
18810     \_regex_build_transition_right:nNn \_regex_tests_action_cost:n
18811     \l__regex_left_state_int \l__regex_right_state_int
18812   }
18813 }

```

(End definition for `\_regex_class_repeat:n`.)

`\_regex_class_repeat:nN` This implements unbounded repetitions of a single class (e.g. the  $*$  and  $+$  quantifiers). If the minimum number  $\#1$  of repetitions is 0, then build a transition from the current state to itself governed by the tests, and a free transition to a new state (hence skipping the tests). Otherwise, call `\_regex_class_repeat:n` for the code to match  $\#1$  repetitions, and add free transitions from the last state to the previous one, and to a new one. In both cases, the order of transitions is controlled by the lazyness boolean  $\#2$ .

```

18814 \cs_new_protected:Npn \_regex_class_repeat:nN #1#2
18815 {

```

```

18816 \if_int_compare:w #1 = 0 \exp_stop_f:
18817 \__regex_build_transitions_lazyness:NNNN #2
18818 \__regex_action_free:n \l__regex_right_state_int
18819 \__regex_tests_action_cost:n \l__regex_left_state_int
18820 \else:
18821 \__regex_class_repeat:n {#1}
18822 \int_set_eq:NN \l__regex_internal_a_int \l__regex_left_state_int
18823 \__regex_build_transitions_lazyness:NNNN #2
18824 \__regex_action_free:n \l__regex_right_state_int
18825 \__regex_action_free:n \l__regex_internal_a_int
18826 \fi:
18827 }

```

(End definition for \\_\_regex\_class\_repeat:nN.)

\\_\_regex\_class\_repeat:nnN

We want to build the code to match from #1 to #1 + #2 repetitions. Match #1 repetitions (can be 0). Compute the final state of the next construction as `a`. Build #2 > 0 states, each with a transition to the next state governed by the tests, and a transition to the final state `a`. The computation of `a` is safe because states are allocated in order, starting from `max_state`.

```

18828 \cs_new_protected:Npn \__regex_class_repeat:nnN #1#2#3
18829 {
18830 \__regex_class_repeat:n {#1}
18831 \int_set:Nn \l__regex_internal_a_int
18832 { \l__regex_max_state_int + #2 - 1 }
18833 \prg_replicate:nn { #2 }
18834 {
18835 \__regex_build_transitions_lazyness:NNNN #3
18836 \__regex_action_free:n \l__regex_internal_a_int
18837 \__regex_tests_action_cost:n \l__regex_right_state_int
18838 }
18839 }

```

(End definition for \\_\_regex\_class\_repeat:nnN.)

### 36.4.5 Building groups

\\_\_regex\_group\_aux:nnnnN

Arguments: {<label>} {<contents>} {<min>} {<more>} <lazyness>. If <min> is 0, we need to add a state before building the group, so that the thread which skips the group does not also set the start-point of the submatch. After adding one more state, the `left_state` is the left end of the group, from which all branches stem, and the `right_state` is the right end of the group, and all branches end their course in that state. We store those two integers to be queried for each branch, we build the NFA states for the contents #2 of the group, and we forget about the two integers. Once this is done, perform the repetition: either exactly #3 times, or #3 or more times, or between #3 and #3 + #4 times, with lazyness #5. The <label> #1 is used for submatch tracking. Each of the three auxiliaries expects `left_state` and `right_state` to be set properly.

```

18840 \cs_new_protected:Npn \__regex_group_aux:nnnnN #1#2#3#4#5
18841 {
18842 (trace) \trace_push:nnn { regex } { 1 } { __regex_group }
18843 \if_int_compare:w #3 = 0 \exp_stop_f:
18844 \__regex_build_new_state:
18845 (assert)\assert_int:n { \l__regex_max_state_int = \l__regex_right_state_int + 1 }

```

```

18846     \_regex_build_transition_right:nNn \_regex_action_free_group:n
18847     \l__regex_left_state_int \l__regex_right_state_int
18848 \fi:
18849 \_regex_build_new_state:
18850 \_regex_push_lr_states:
18851 #2
18852 \_regex_pop_lr_states:
18853 \if_case:w - #4 \exp_stop_f:
18854     \_regex_group_repeat:nn {#1} {#3}
18855 \or:  \_regex_group_repeat:nnN {#1} {#3} #5
18856 \else: \_regex_group_repeat:nnnN {#1} {#3} {#4} #5
18857 \fi:
18858 <trace> \trace_pop:nnn { regex } { 1 } { __regex_group }
18859 }

```

(End definition for \\_regex\_group\_aux:nnnnN.)

\\_regex\_group:nnnN Hand to \\_regex\_group\_aux:nnnnN the label of that group (expanded), and the group itself, with some extra commands to perform.

```

18860 \cs_new_protected:Npn \_regex_group:nnnN #1
18861 {
18862     \exp_args:No \_regex_group_aux:nnnnN
18863     { \int_use:N \l__regex_capturing_group_int }
18864     {
18865         \int_incr:N \l__regex_capturing_group_int
18866         #1
18867     }
18868 }
18869 \cs_new_protected:Npn \_regex_group_no_capture:nnnN
18870 { \_regex_group_aux:nnnnN { -1 } }

```

(End definition for \\_regex\_group:nnnN and \\_regex\_group\_no\_capture:nnnN.)

\\_regex\_group\_resetting:nnnN Again, hand the label  $-1$  to \\_regex\_group\_aux:nnnnN, but this time we work a little bit harder to keep track of the maximum group label at the end of any branch, and to reset the group number at each branch. This relies on the fact that a compiled regex always is a sequence of items of the form \\_regex\_branch:n {<branch>}.

```

18871 \cs_new_protected:Npn \_regex_group_resetting:nnnN #1
18872 {
18873     \_regex_group_aux:nnnnN { -1 }
18874     {
18875         \exp_args:Noo \_regex_group_resetting_loop:nnNn
18876         { \int_use:N \l__regex_capturing_group_int }
18877         { \int_use:N \l__regex_capturing_group_int }
18878         #1
18879         { ?? \_prg_break:n } { }
18880         \_prg_break_point:
18881     }
18882 }
18883 \cs_new_protected:Npn \_regex_group_resetting_loop:nnNn #1#2#3#4
18884 {
18885     \use_none:nn #3 { \int_set:Nn \l__regex_capturing_group_int {#1} }
18886     \int_set:Nn \l__regex_capturing_group_int {#2}
18887     #3 {#4}

```

```

18888 \exp_args:Nf \__regex_group_resetting_loop:nnNn
18889 { \int_max:nn {#1} { \l__regex_capturing_group_int } }
18890 {#2}
18891 }

```

(End definition for \\_\_regex\_group\_resetting:nnnN and \\_\_regex\_group\_resetting\_loop:nnNn.)

**\\_\_regex\_branch:n** Add a free transition from the left state of the current group to a brand new state, starting point of this branch. Once the branch is built, add a transition from its last state to the right state of the group. The left and right states of the group are extracted from the relevant sequences.

```

18892 \cs_new_protected:Npn \__regex_branch:n #1
18893 {
18894   <trace> \trace_push:nnn { regex } { 1 } { __regex_branch }
18895   \__regex_build_new_state:
18896   \seq_get:NN \l__regex_left_state_seq \l__regex_internal_a_tl
18897   \int_set:Nn \l__regex_left_state_int \l__regex_internal_a_tl
18898   \__regex_build_transition_right:nNn \__regex_action_free:n
18899   \l__regex_left_state_int \l__regex_right_state_int
18900   #1
18901   \seq_get:NN \l__regex_right_state_seq \l__regex_internal_a_tl
18902   \__regex_build_transition_right:nNn \__regex_action_free:n
18903   \l__regex_right_state_int \l__regex_internal_a_tl
18904   <trace> \trace_pop:nnn { regex } { 1 } { __regex_branch }
18905 }

```

(End definition for \\_\_regex\_branch:n.)

**\\_\_regex\_group\_repeat:nn** This function is called to repeat a group a fixed number of times #2; if this is 0 we remove the group altogether (but don't reset the capturing\_group label). Otherwise, the auxiliary \\_\_regex\_group\_repeat\_aux:n copies #2 times the \toks for the group, and leaves internal\_a pointing to the left end of the last repetition. We only record the submatch information at the last repetition. Finally, add a state at the end (the transition to it has been taken care of by the replicating auxiliary).

```

18906 \cs_new_protected:Npn \__regex_group_repeat:nn #1#2
18907 {
18908   \if_int_compare:w #2 = 0 \exp_stop_f:
18909   \int_set:Nn \l__regex_max_state_int
18910   { \l__regex_left_state_int - 1 }
18911   \__regex_build_new_state:
18912   \else:
18913     \__regex_group_repeat_aux:n {#2}
18914     \__regex_group_submatches:nNN {#1}
18915     \l__regex_internal_a_int \l__regex_right_state_int
18916     \__regex_build_new_state:
18917   \fi:
18918 }

```

(End definition for \\_\_regex\_group\_repeat:nn.)

**\\_\_regex\_group\_submatches:nNN** This inserts in states #2 and #3 the code for tracking submatches of the group #1, unless inhibited by a label of -1.

```

18919 \cs_new_protected:Npn \__regex_group_submatches:nNN #1#2#3
18920 {

```

```

18921     \if_int_compare:w #1 > - 1 \exp_stop_f:
18922         \__regex_toks_put_left:Nx #2 { \__regex_action_submatch:n { #1 < } }
18923         \__regex_toks_put_left:Nx #3 { \__regex_action_submatch:n { #1 > } }
18924     \fi:
18925 }

```

(End definition for \\_\_regex\_group\_submatches:nNN.)

\\_\_regex\_group\_repeat\_aux:n Here we repeat \toks ranging from left\_state to max\_state, #1 > 0 times. First add a transition so that the copies “chain” properly. Compute the shift c between the original copy and the last copy we want. Shift the right\_state and max\_state to their final values. We then want to perform c copy operations. At the end, b is equal to the max\_state, and a points to the left of the last copy of the group.

```

18926 \cs_new_protected:Npn \__regex_group_repeat_aux:n #1
18927 {
18928     \__regex_build_transition_right:nNn \__regex_action_free:n
18929     \l__regex_right_state_int \l__regex_max_state_int
18930     \int_set_eq:NN \l__regex_internal_a_int \l__regex_left_state_int
18931     \int_set_eq:NN \l__regex_internal_b_int \l__regex_max_state_int
18932     \if_int_compare:w \__int_eval:w #1 > 1 \exp_stop_f:
18933         \int_set:Nn \l__regex_internal_c_int
18934         {
18935             ( #1 - 1 )
18936             * ( \l__regex_internal_b_int - \l__regex_internal_a_int )
18937         }
18938         \int_add:Nn \l__regex_right_state_int { \l__regex_internal_c_int }
18939         \int_add:Nn \l__regex_max_state_int { \l__regex_internal_c_int }
18940         \__regex_toks_memcpy:NNn
18941             \l__regex_internal_b_int
18942             \l__regex_internal_a_int
18943             \l__regex_internal_c_int
18944     \fi:
18945 }

```

(End definition for \\_\_regex\_group\_repeat\_aux:n.)

\\_\_regex\_group\_repeat:nnN This function is called to repeat a group at least n times; the case n = 0 is very different from n > 0. Assume first that n = 0. Insert submatch tracking information at the start and end of the group, add a free transition from the right end to the “true” left state a (remember: in this case we had added an extra state before the left state). This forms the loop, which we break away from by adding a free transition from a to a new state.

Now consider the case n > 0. Repeat the group n times, chaining various copies with a free transition. Add submatch tracking only to the last copy, then add a free transition from the right end back to the left end of the last copy, either before or after the transition to move on towards the rest of the NFA. This transition can end up before submatch tracking, but that is irrelevant since it only does so when going again through the group, recording new matches. Finally, add a state; we already have a transition pointing to it from \\_\_regex\_group\_repeat\_aux:n.

```

18946 \cs_new_protected:Npn \__regex_group_repeat:nnN #1#2#3
18947 {
18948     \if_int_compare:w #2 = 0 \exp_stop_f:
18949         \__regex_group_submatches:nnN {#1}
18950         \l__regex_left_state_int \l__regex_right_state_int

```

```

18951     \int_set:Nn \l__regex_internal_a_int
18952     { \l__regex_left_state_int - 1 }
18953     \__regex_build_transition_right:nNn \__regex_action_free:n
18954     \l__regex_right_state_int \l__regex_internal_a_int
18955     \__regex_build_new_state:
18956     \if_meaning:w \c_true_bool #3
18957         \__regex_build_transition_left:NNN \__regex_action_free:n
18958         \l__regex_internal_a_int \l__regex_right_state_int
18959     \else:
18960         \__regex_build_transition_right:nNn \__regex_action_free:n
18961         \l__regex_internal_a_int \l__regex_right_state_int
18962     \fi:
18963 \else:
18964     \__regex_group_repeat_aux:n {#2}
18965     \__regex_group_submatches:nNN {#1}
18966     \l__regex_internal_a_int \l__regex_right_state_int
18967     \if_meaning:w \c_true_bool #3
18968         \__regex_build_transition_right:nNn \__regex_action_free_group:n
18969         \l__regex_right_state_int \l__regex_internal_a_int
18970     \else:
18971         \__regex_build_transition_left:NNN \__regex_action_free_group:n
18972         \l__regex_right_state_int \l__regex_internal_a_int
18973     \fi:
18974     \__regex_build_new_state:
18975 \fi:
18976 }

```

(End definition for \\_\_regex\_group\_repeat:nnN.)

\\_\_regex\_group\_repeat:nnnN

We wish to repeat the group between #2 and #2 + #3 times, with a laziness controlled by #4. We insert submatch tracking up front: in principle, we could avoid recording submatches for the first #2 copies of the group, but that forces us to treat specially the case #2 = 0. Repeat that group with submatch tracking #2 + #3 times (the maximum number of repetitions). Then our goal is to add #3 transitions from the end of the #2-th group, and each subsequent groups, to the end. For a lazy quantifier, we add those transitions to the left states, before submatch tracking. For the greedy case, we add the transitions to the right states, after submatch tracking and the transitions which go on with more repetitions. In the greedy case with #2 = 0, the transition which skips over all copies of the group must be added separately, because its starting state does not follow the normal pattern: we had to add it “by hand” earlier.

```

18977 \cs_new_protected:Npn \__regex_group_repeat:nnnN #1#2#3#4
18978 {
18979     \__regex_group_submatches:nNN {#1}
18980     \l__regex_left_state_int \l__regex_right_state_int
18981     \__regex_group_repeat_aux:n { #2 + #3 }
18982     \if_meaning:w \c_true_bool #4
18983         \int_set_eq:NN \l__regex_left_state_int \l__regex_max_state_int
18984         \prg_replicate:nn { #3 }
18985         {
18986             \int_sub:Nn \l__regex_left_state_int
18987             { \l__regex_internal_b_int - \l__regex_internal_a_int }
18988             \__regex_build_transition_left:NNN \__regex_action_free:n
18989             \l__regex_left_state_int \l__regex_max_state_int

```

```

18990     }
18991 \else:
18992   \prg_replicate:nn { #3 - 1 }
18993   {
18994     \int_sub:Nn \l__regex_right_state_int
18995     { \l__regex_internal_b_int - \l__regex_internal_a_int }
18996     \__regex_build_transition_right:nNn \__regex_action_free:n
18997     \l__regex_right_state_int \l__regex_max_state_int
18998   }
18999   \if_int_compare:w #2 = 0 \exp_stop_f:
19000     \int_set:Nn \l__regex_right_state_int
19001     { \l__regex_left_state_int - 1 }
19002   \else:
19003     \int_sub:Nn \l__regex_right_state_int
19004     { \l__regex_internal_b_int - \l__regex_internal_a_int }
19005   \fi:
19006   \__regex_build_transition_right:nNn \__regex_action_free:n
19007   \l__regex_right_state_int \l__regex_max_state_int
19008 \fi:
19009 \__regex_build_new_state:
19010 }

```

(End definition for \\_\_regex\_group\_repeat:nnnN.)

### 36.4.6 Others

\\_\_regex\_assertion:Nn Usage: \\_\_regex\_assertion:Nn *<boolean>* {*<test>*}, where the *<test>* is either of the two other functions. Add a free transition to a new state, conditionally to the assertion test.

\\_\_regex\_b\_test: The \\_\_regex\_b\_test: test is used by the \b and \B escape: check if the last character was a word character or not, and do the same to the current character. The boundary-markers of the string are non-word characters for this purpose. Anchors at the start or end of match use \\_\_regex\_anchor:N, with a position controlled by the integer #1.

```

19011 \cs_new_protected:Npn \__regex_assertion:Nn #1#2
19012 {
19013   \__regex_build_new_state:
19014   \__regex_toks_put_right:Nx \l__regex_left_state_int
19015   {
19016     \exp_not:n {#2}
19017     \__regex_break_point:TF
19018     \bool_if:NF #1 { { } }
19019     {
19020       \__regex_action_free:n
19021       {
19022         \int_eval:n
19023         { \l__regex_right_state_int - \l__regex_left_state_int }
19024       }
19025     }
19026     \bool_if:NT #1 { { } }
19027   }
19028 }
19029 \cs_new_protected:Npn \__regex_anchor:N #1
19030 {
19031   \if_int_compare:w #1 = \l__regex_curr_pos_int
19032     \exp_after:wN \__regex_break_true:w

```

```

19033     \fi:
19034   }
19035   \cs_new_protected:Npn \__regex_b_test:
19036   {
19037     \group_begin:
19038       \int_set_eq:NN \l__regex_curr_char_int \l__regex_last_char_int
19039       \__regex_prop_w:
19040       \__regex_break_point:TF
19041       { \group_end: \__regex_item_reverse:n \__regex_prop_w: }
19042       { \group_end: \__regex_prop_w: }
19043   }

```

(End definition for `\__regex_assertion:Nn`, `\__regex_b_test:`, and `\__regex_anchor:N`.)

`\__regex_command_K:` Change the starting point of the 0-th submatch (full match), and transition to a new state, pretending that this is a fresh thread.

```

19044   \cs_new_protected:Npn \__regex_command_K:
19045   {
19046     \__regex_build_new_state:
19047     \__regex_toks_put_right:Nx \l__regex_left_state_int
19048     {
19049       \__regex_action_submatch:n { 0< }
19050       \bool_set_true:N \l__regex_fresh_thread_bool
19051       \__regex_action_free:n
19052       { \int_eval:n { \l__regex_right_state_int - \l__regex_left_state_int } }
19053       \bool_set_false:N \l__regex_fresh_thread_bool
19054     }
19055   }

```

(End definition for `\__regex_command_K:`.)

## 36.5 Matching

We search for matches by running all the execution threads through the NFA in parallel, reading one token of the query at each step. The NFA contains “free” transitions to other states, and transitions which “consume” the current token. For free transitions, the instruction at the new state of the NFA is performed immediately. When a transition consumes a character, the new state is appended to a list of “active states”, stored in `\g__regex_thread_state_intarray`: this thread is made active again when the next token is read from the query. At every step (for each token in the query), we unpack that list of active states and the corresponding submatch props, and empty those.

If two paths through the NFA “collide” in the sense that they reach the same state after reading a given token, then they only differ in how they previously matched, and any future execution would be identical for both. (Note that this would be wrong in the presence of back-references.) Hence, we only need to keep one of the two threads: the thread with the highest priority. Our NFA is built in such a way that higher priority actions always come before lower priority actions, which makes things work.

The explanation in the previous paragraph may make us think that we simply need to keep track of which states were visited at a given step: after all, the loop generated when matching `(a?)*` against `a` is broken, isn’t it? No. The group first matches `a`, as it should, then repeats; it attempts to match `a` again but fails; it skips `a`, and finds out that this state has already been seen at this position in the query: the match stops. The capturing group is (wrongly) `a`. What went wrong is that a thread collided with itself,



and the later version, which has gone through the group one more times with an empty match, should have a higher priority than not going through the group.

We solve this by distinguishing “normal” free transitions `\__regex_action_free:n` from transitions `\__regex_action_free_group:n` which go back to the start of the group. The former keeps threads unless they have been visited by a “completed” thread, while the latter kind of transition also prevents going back to a state visited by the current thread.

### 36.5.1 Variables used when matching

<code>\l__regex_min_pos_int</code> <code>\l__regex_max_pos_int</code> <code>\l__regex_curr_pos_int</code> <code>\l__regex_start_pos_int</code> <code>\l__regex_success_pos_int</code>	<p>The tokens in the query are indexed from <code>min_pos</code> for the first to <code>max_pos - 1</code> for the last, and their information is stored in several arrays and <code>\toks</code> registers with those numbers. We don’t start from 0 because the <code>\toks</code> registers with low numbers are used to hold the states of the NFA. We match without backtracking, keeping all threads in lockstep from the <code>current_pos</code> in the query. The starting point of the current match attempt is <code>start_pos</code>, and <code>success_pos</code>, updated whenever a thread succeeds, is used as the next starting position.</p>
---	--

```

19056 \int_new:N \l__regex_min_pos_int
19057 \int_new:N \l__regex_max_pos_int
19058 \int_new:N \l__regex_curr_pos_int
19059 \int_new:N \l__regex_start_pos_int
19060 \int_new:N \l__regex_success_pos_int

```

*(End definition for `\l__regex_min_pos_int` and others.)*

<code>\l__regex_curr_char_int</code> <code>\l__regex_curr_catcode_int</code> <code>\l__regex_last_char_int</code> <code>\l__regex_case_changed_char_int</code>	<p>The character and category codes of the token at the current position; the character code of the token at the previous position; and the character code of the result of changing the case of the current token (A-Z↔a-z). This last integer is only computed when necessary, and is otherwise <code>\c_max_int</code>. The <code>current_char</code> variable is also used in various other phases to hold a character code.</p>
---	--

```

19061 \int_new:N \l__regex_curr_char_int
19062 \int_new:N \l__regex_curr_catcode_int
19063 \int_new:N \l__regex_last_char_int
19064 \int_new:N \l__regex_case_changed_char_int

```

*(End definition for `\l__regex_curr_char_int` and others.)*

<code>\l__regex_curr_state_int</code>	<p>For every character in the token list, each of the active states is considered in turn. The variable <code>\l__regex_curr_state_int</code> holds the state of the NFA which is currently considered: transitions are then given as shifts relative to the current state.</p>
---------------------------------------	---

```

19065 \int_new:N \l__regex_curr_state_int

```

*(End definition for `\l__regex_curr_state_int`.)*

<code>\l__regex_curr_submatches_prop</code> <code>\l__regex_success_submatches_prop</code>	<p>The submatches for the thread which is currently active are stored in the <code>current_submatches</code> property list variable. This property list is stored by <code>\__regex_action_cost:n</code> into the <code>\toks</code> register for the target state of the transition, to be retrieved when matching at the next position. When a thread succeeds, this property list is copied to <code>\l__regex_success_submatches_prop</code>: only the last successful thread remains there.</p>
---	--

```

19066 \prop_new:N \l__regex_curr_submatches_prop
19067 \prop_new:N \l__regex_success_submatches_prop

```

*(End definition for `\l__regex_curr_submatches_prop` and `\l__regex_success_submatches_prop`.)*

`\l__regex_step_int` This integer, always even, is increased every time a character in the query is read, and not reset when doing multiple matches. We store in `\g__regex_state_active_intarray` the last step in which each  $\langle state \rangle$  in the NFA was encountered. This lets us break infinite loops by not visiting the same state twice in the same step. In fact, the step we store is equal to `step` when we have started performing the operations of `\toks $\langle state \rangle$` , but not finished yet. However, once we finish, we store `step + 1` in `\g__regex_state_active_intarray`. This is needed to track submatches properly (see building phase). The `step` is also used to attach each set of submatch information to a given iteration (and automatically discard it when it corresponds to a past step).

```
19068 \int_new:N \l__regex_step_int
```

(End definition for `\l__regex_step_int`.)

`\l__regex_min_active_int` All the currently active threads are kept in order of precedence in `\g__regex_thread_state_intarray`, and the corresponding submatches in the `\toks`. For our purposes, those serve as an array, indexed from `min_active` (inclusive) to `max_active` (excluded).  
`\l__regex_max_active_int` At the start of every step, the whole array is unpacked, so that the space can immediately be reused, and `max_active` is reset to `min_active`, effectively clearing the array.

```
19069 \int_new:N \l__regex_min_active_int
```

```
19070 \int_new:N \l__regex_max_active_int
```

(End definition for `\l__regex_min_active_int` and `\l__regex_max_active_int`.)

`\g__regex_state_active_intarray` `\g__regex_state_active_intarray` stores the last  $\langle step \rangle$  in which each  $\langle state \rangle$  was active.  
`\g__regex_thread_state_intarray` `\g__regex_thread_state_intarray` stores threads to be considered in the next step, more precisely the states in which these threads are.

```
19071 \__intarray_new:Nn \g__regex_state_active_intarray { 65536 }
```

```
19072 \__intarray_new:Nn \g__regex_thread_state_intarray { 65536 }
```

(End definition for `\g__regex_state_active_intarray` and `\g__regex_thread_state_intarray`.)

`\l__regex_every_match_tl` Every time a match is found, this token list is used. For single matching, the token list is empty. For multiple matching, the token list is set to repeat the matching, after performing some operation which depends on the user function. See `\__regex_single_match:` and `\__regex_multi_match:n`.

```
19073 \tl_new:N \l__regex_every_match_tl
```

(End definition for `\l__regex_every_match_tl`.)

`\l__regex_fresh_thread_bool` When doing multiple matches, we need to avoid infinite loops where each iteration matches the same empty token list. When an empty token list is matched, the next successful match of the same empty token list is suppressed. We detect empty matches by setting `\l__regex_fresh_thread_bool` to `true` for threads which directly come from the start of the regex or from the `\K` command, and testing that boolean whenever a thread succeeds. The function `\__regex_if_two_empty_matches:F` is redefined at every match attempt, depending on whether the previous match was empty or not: if it was, then the function must cancel a purported success if it is empty and at the same spot as the previous match; otherwise, we definitely don't have two identical empty matches, so the function is `\use:n`.

```
19074 \bool_new:N \l__regex_fresh_thread_bool
```

```
19075 \bool_new:N \l__regex_empty_success_bool
```

```
19076 \cs_new_eq:NN \__regex_if_two_empty_matches:F \use:n
```

(End definition for `\l__regex_fresh_thread_bool`, `\l__regex_empty_success_bool`, and `\__regex_if_two_empty_matches:F`.)

`\g__regex_success_bool` The boolean `\l__regex_match_success_bool` is true if the current match attempt was successful, and `\g__regex_success_bool` is true if there was at least one successful match. This is the only global variable in this whole module, but we would need it to be local when matching a control sequence with `\c{...}`. This is done by saving the global variable into `\l__regex_saved_success_bool`, which is local, hence not affected by the changes due to inner regex functions.

```
19077 \bool_new:N \g__regex_success_bool
19078 \bool_new:N \l__regex_saved_success_bool
19079 \bool_new:N \l__regex_match_success_bool
```

(End definition for `\g__regex_success_bool`, `\l__regex_saved_success_bool`, and `\l__regex_match_success_bool`.)

### 36.5.2 Matching: framework

`\__regex_match:n` First store the query into `\toks` registers and arrays (see `\__regex_query_set:nnn`). Then initialize the variables that should be set once for each user function (even for multiple matches). Namely, the overall matching is not yet successful; none of the states should be marked as visited (`\g__regex_state_active_intarray`), and we start at step 0; we pretend that there was a previous match ending at the start of the query, which was not empty (to avoid smothering an empty match at the start). Once all this is set up, we are ready for the ride. Find the first match.

```
19080 \cs_new_protected:Npn \__regex_match:n #1
19081 {
19082   \trace_push:nnx { regex } { 1 } { __regex_match }
19083   \trace:nnx { regex } { 1 } { analyzing~query~token~list }
19084   \int_zero:N \l__regex_balance_int
19085   \int_set:Nn \l__regex_curr_pos_int { 2 * \l__regex_max_state_int }
19086   \__regex_query_set:nnn { } { -1 } { -2 }
19087   \int_set_eq:NN \l__regex_min_pos_int \l__regex_curr_pos_int
19088   \__tl_analysis_map_inline:nn {#1}
19089     { \__regex_query_set:nnn {##1} {"##2"} {##3} }
19090   \int_set_eq:NN \l__regex_max_pos_int \l__regex_curr_pos_int
19091   \__regex_query_set:nnn { } { -1 } { -2 }
19092   \trace:nnx { regex } { 1 } { initializing }
19093   \bool_gset_false:N \g__regex_success_bool
19094   \int_step_inline:nnnn
19095     \l__regex_min_state_int { 1 } { \l__regex_max_state_int - 1 }
19096     { \__intarray_gset_fast:Nnn \g__regex_state_active_intarray {##1} { 1 } }
19097   \int_set_eq:NN \l__regex_min_active_int \l__regex_max_state_int
19098   \int_zero:N \l__regex_step_int
19099   \int_set_eq:NN \l__regex_success_pos_int \l__regex_min_pos_int
19100   \int_set:Nn \l__regex_min_submatch_int
19101     { 2 * \l__regex_max_state_int }
19102   \int_set_eq:NN \l__regex_submatch_int \l__regex_min_submatch_int
19103   \bool_set_false:N \l__regex_empty_success_bool
19104   \__regex_match_once:
19105   \trace_pop:nnx { regex } { 1 } { __regex_match }
19106 }
```

(End definition for `\__regex_match:n`.)

`\__regex_match_once:` This function finds one match, then does some action defined by the `every_match` token list, which may recursively call `\__regex_match_once:`. First initialize some variables: set the conditional which detects identical empty matches; this match attempt starts at the previous `success_pos`, is not yet successful, and has no submatches yet; clear the array of active threads, and put the starting state 0 in it. We are then almost ready to read our first token in the query, but we actually start one position earlier than the start, and `get` that token, to set `last_char` properly for word boundaries. Then call `\__regex_match_loop:`, which runs through the query until the end or until a successful match breaks early.

```

19107 \cs_new_protected:Npn \__regex_match_once:
19108 {
19109     \if_meaning:w \c_true_bool \l__regex_empty_success_bool
19110     \cs_set:Npn \__regex_if_two_empty_matches:F
19111     { \int_compare:nNf \l__regex_start_pos_int = \l__regex_curr_pos_int }
19112     \else:
19113     \cs_set_eq:NN \__regex_if_two_empty_matches:F \use:n
19114     \fi:
19115     \int_set_eq:NN \l__regex_start_pos_int \l__regex_success_pos_int
19116     \bool_set_false:N \l__regex_match_success_bool
19117     \prop_clear:N \l__regex_curr_submatches_prop
19118     \int_set_eq:NN \l__regex_max_active_int \l__regex_min_active_int
19119     \__regex_store_state:n { \l__regex_min_state_int }
19120     \int_set:Nn \l__regex_curr_pos_int
19121     { \l__regex_start_pos_int - 1 }
19122     \__regex_query_get:
19123     \__regex_match_loop:
19124     \l__regex_every_match_tl
19125 }

```

(End definition for `\__regex_match_once:`.)

`\__regex_single_match:` For a single match, the overall success is determined by whether the only match attempt is a success. When doing multiple matches, the overall matching is successful as soon as any match succeeds. Perform the action #1, then find the next match.

`\__regex_multi_match:n`

```

19126 \cs_new_protected:Npn \__regex_single_match:
19127 {
19128     \tl_set:Nn \l__regex_every_match_tl
19129     { \bool_gset_eq:NN \g__regex_success_bool \l__regex_match_success_bool }
19130 }
19131 \cs_new_protected:Npn \__regex_multi_match:n #1
19132 {
19133     \tl_set:Nn \l__regex_every_match_tl
19134     {
19135         \if_meaning:w \c_true_bool \l__regex_match_success_bool
19136         \bool_gset_true:N \g__regex_success_bool
19137         #1
19138         \exp_after:wN \__regex_match_once:
19139     \fi:
19140     }
19141 }

```

(End definition for `\__regex_single_match:` and `\__regex_multi_match:n`.)

```

19142 \cs_new_protected:Npn \__regex_match_loop:
19143 {
19144   \int_add:Nn \l__regex_step_int { 2 }
19145   \int_incr:N \l__regex_curr_pos_int
19146   \int_set_eq:NN \l__regex_last_char_int \l__regex_curr_char_int
19147   \int_set_eq:NN \l__regex_case_changed_char_int \c_max_int
19148   \__regex_query_get:
19149   \use:x
19150   {
19151     \int_set_eq:NN \l__regex_max_active_int \l__regex_min_active_int
19152     \int_step_function:nnnN
19153       { \l__regex_min_active_int }
19154       { 1 }
19155       { \l__regex_max_active_int - 1 }
19156     \__regex_match_one_active:n
19157   }
19158   \__prg_break_point:
19159   \bool_set_false:N \l__regex_fresh_thread_bool %^^A was arg of break_point:n
19160   \if_int_compare:w \l__regex_max_active_int > \l__regex_min_active_int
19161     \if_int_compare:w \l__regex_curr_pos_int < \l__regex_max_pos_int
19162       \exp_after:wN \exp_after:wN \exp_after:wN \__regex_match_loop:
19163     \fi:
19164   \fi:
19165 }
19166 \cs_new:Npn \__regex_match_one_active:n #1
19167 {
19168   \__regex_use_state_and_submatches:nn
19169   { \__intarray_item_fast:Nn \g__regex_thread_state_intarray {#1} }
19170   { \__regex_toks_use:w #1 }
19171 }

```

(End definition for \\_\_regex\_match\_loop: and \\_\_regex\_match\_one\_active:n.)

\\_\_regex\_query\_set:nnn The arguments are: tokens that o and x expand to one token of the query, the catcode, and the character code. Store those, and the current brace balance (used later to check for overall brace balance) in a \toks register and some arrays, then update the balance.

```

19172 \cs_new_protected:Npn \__regex_query_set:nnn #1#2#3
19173 {
19174   \__intarray_gset_fast:Nnn \g__regex_charcode_intarray
19175     { \l__regex_curr_pos_int } {#3}
19176   \__intarray_gset_fast:Nnn \g__regex_catcode_intarray
19177     { \l__regex_curr_pos_int } {#2}
19178   \__intarray_gset_fast:Nnn \g__regex_balance_intarray
19179     { \l__regex_curr_pos_int } { \l__regex_balance_int }
19180   \__regex_toks_set:Nn \l__regex_curr_pos_int {#1}

```

```

19181     \int_incr:N \l__regex_curr_pos_int
19182     \if_case:w #2 \exp_stop_f:
19183     \or: \int_incr:N \l__regex_balance_int
19184     \or: \int_decr:N \l__regex_balance_int
19185     \fi:
19186 }

```

(End definition for \\_\_regex\_query\_set:nnn.)

**\\_\_regex\_query\_get:** Extract the current character and category codes at the current position from the appropriate arrays.

```

19187 \cs_new_protected:Npn \__regex_query_get:
19188 {
19189     \l__regex_curr_char_int
19190     = \__intarray_item_fast:Nn \g__regex_charcode_intarray
19191       { \l__regex_curr_pos_int } \scan_stop:
19192     \l__regex_curr_catcode_int
19193     = \__intarray_item_fast:Nn \g__regex_catcode_intarray
19194       { \l__regex_curr_pos_int } \scan_stop:
19195 }

```

(End definition for \\_\_regex\_query\_get:.)

### 36.5.3 Using states of the nfa

**\\_\_regex\_use\_state:** Use the current NFA instruction. The state is initially marked as belonging to the current **step**: this allows normal free transition to repeat, but group-repeating transitions won't. Once we are done exploring all the branches it spawned, the state is marked as **step + 1**: any thread hitting it at that point will be terminated.

```

19196 \cs_new_protected:Npn \__regex_use_state:
19197 {
19198     < *trace >
19199     \trace:nnx { regex } { 2 } { state~\int_use:N \l__regex_curr_state_int }
19200     < /trace >
19201     \__intarray_gset_fast:Nnn \g__regex_state_active_intarray
19202       { \l__regex_curr_state_int } { \l__regex_step_int }
19203     \__regex_toks_use:w \l__regex_curr_state_int
19204     \__intarray_gset_fast:Nnn \g__regex_state_active_intarray
19205       { \l__regex_curr_state_int } { \l__regex_step_int + 1 }
19206 }

```

(End definition for \\_\_regex\_use\_state:.)

**\\_\_regex\_use\_state\_and\_submatches:mn** This function is called as one item in the array of active threads after that array has been unpacked for a new step. Update the **current\_state** and **current\_submatches** and use the state if it has not yet been encountered at this step.

```

19207 \cs_new_protected:Npn \__regex_use_state_and_submatches:mn #1 #2
19208 {
19209     \int_set:Nn \l__regex_curr_state_int {#1}
19210     \if_int_compare:w
19211       \__intarray_item_fast:Nn \g__regex_state_active_intarray
19212         { \l__regex_curr_state_int }
19213         < \l__regex_step_int
19214     \tl_set:Nn \l__regex_curr_submatches_prop {#2}

```

```

19215         \exp_after:wN \_regex\_use\_state:
19216     \fi:
19217     \scan\_stop:
19218 }

```

(End definition for \\_regex\\_use\\_state\\_and\\_submatches:nn.)

### 36.5.4 Actions when matching

\\_regex\\_action\\_start\\_wildcard: For an unanchored match, state 0 has a free transition to the next and a costly one to itself, to repeat at the next position. To catch repeated identical empty matches, we need to know if a successful thread corresponds to an empty match. The instruction resetting \l\\_regex\\_fresh\\_thread\\_bool may be skipped by a successful thread, hence we had to add it to \\_regex\\_match\\_loop: too.

```

19219 \cs\_new\_protected:Npn \_regex\_action\_start\_wildcard:
19220 {
19221     \bool\_set\_true:N \l\_regex\_fresh\_thread\_bool
19222     \_regex\_action\_free:n {1}
19223     \bool\_set\_false:N \l\_regex\_fresh\_thread\_bool
19224     \_regex\_action\_cost:n {0}
19225 }

```

(End definition for \\_regex\\_action\\_start\\_wildcard:.)

\\_regex\\_action\\_free:n These functions copy a thread after checking that the NFA state has not already been used at this position. If not, store submatches in the new state, and insert the instructions for that state in the input stream. Then restore the old value of \l\\_regex\\_curr\\_state\\_int and of the current submatches. The two types of free transitions differ by how they test that the state has not been encountered yet: the `group` version is stricter, and will not use a state if it was used earlier in the current thread, hence forcefully breaking the loop, while the “normal” version will revisit a state even within the thread itself.

```

\_regex\_action\_free\_group:n
\_regex\_action\_free\_aux:nn
19226 \cs\_new\_protected:Npn \_regex\_action\_free:n
19227 { \_regex\_action\_free\_aux:nn { > \l\_regex\_step\_int \else: } }
19228 \cs\_new\_protected:Npn \_regex\_action\_free\_group:n
19229 { \_regex\_action\_free\_aux:nn { < \l\_regex\_step\_int } }
19230 \cs\_new\_protected:Npn \_regex\_action\_free\_aux:nn #1#2
19231 {
19232     \use:x
19233     {
19234         \int\_add:Nn \l\_regex\_curr\_state\_int {#2}
19235         \exp\_not:n
19236         {
19237             \if\_int\_compare:w
19238                 \_intarray\_item\_fast:Nn \g\_regex\_state\_active\_intarray
19239                 { \l\_regex\_curr\_state\_int }
19240                 #1
19241             \exp\_after:wN \_regex\_use\_state:
19242             \fi:
19243         }
19244         \int\_set:Nn \l\_regex\_curr\_state\_int
19245         { \int\_use:N \l\_regex\_curr\_state\_int }
19246         \tl\_set:Nn \exp\_not:N \l\_regex\_curr\_submatches\_prop
19247         { \exp\_not:o \l\_regex\_curr\_submatches\_prop }

```

```

19248     }
19249 }

```

(End definition for `\__regex_action_free:n`, `\__regex_action_free_group:n`, and `\__regex_action_free_aux:nn`.)

`\__regex_action_cost:n` A transition which consumes the current character and shifts the state by #1. The resulting state is stored in the appropriate array for use at the next position, and we also store the current submatches.

```

19250 \cs_new_protected:Npn \__regex_action_cost:n #1
19251 {
19252     \exp_args:No \__regex_store_state:n
19253     { \__int_value:w \__int_eval:w \l__regex_curr_state_int + #1 }
19254 }

```

(End definition for `\__regex_action_cost:n`.)

`\__regex_store_state:n` Put the given state in `\g__regex_thread_state_intarray`, and increment the length of the array. Also store the current submatch in the appropriate `\toks`.

```

19255 \cs_new_protected:Npn \__regex_store_state:n #1
19256 {
19257     \__regex_store_submatches:
19258     \__intarray_gset_fast:Nnn \g__regex_thread_state_intarray
19259     { \l__regex_max_active_int } {#1}
19260     \int_incr:N \l__regex_max_active_int
19261 }
19262 \cs_new_protected:Npn \__regex_store_submatches:
19263 {
19264     \__regex_toks_set:No \l__regex_max_active_int
19265     { \l__regex_curr_submatches_prop }
19266 }

```

(End definition for `\__regex_store_state:n` and `\__regex_store_submatches:.`)

`\__regex_disable_submatches:` Some user functions don't require tracking submatches. We get a performance improvement by simply defining the relevant functions to remove their argument and do nothing with it.

```

19267 \cs_new_protected:Npn \__regex_disable_submatches:
19268 {
19269     \cs_set_protected:Npn \__regex_store_submatches: { }
19270     \cs_set_protected:Npn \__regex_action_submatch:n ##1 { }
19271 }

```

(End definition for `\__regex_disable_submatches:.`)

`\__regex_action_submatch:n` Update the current submatches with the information from the current position. Maybe a bottleneck.

```

19272 \cs_new_protected:Npn \__regex_action_submatch:n #1
19273 {
19274     \prop_put:Nno \l__regex_curr_submatches_prop {#1}
19275     { \int_use:N \l__regex_curr_pos_int }
19276 }

```

(End definition for `\__regex_action_submatch:n`.)



`\__regex_action_success:` There is a successful match when an execution path reaches the last state in the NFA, unless this marks a second identical empty match. Then mark that there was a successful match; it is empty if it is “fresh”; and we store the current position and submatches. The current step is then interrupted with `\__prg_break:`, and only paths with higher precedence are pursued further. The values stored here may be overwritten by a later success of a path with higher precedence.

```

19277 \cs_new_protected:Npn \__regex_action_success:
19278 {
19279   \__regex_if_two_empty_matches:F
19280   {
19281     \bool_set_true:N \l__regex_match_success_bool
19282     \bool_set_eq:NN \l__regex_empty_success_bool
19283     \l__regex_fresh_thread_bool
19284     \int_set_eq:NN \l__regex_success_pos_int \l__regex_curr_pos_int
19285     \prop_set_eq:NN \l__regex_success_submatches_prop
19286     \l__regex_curr_submatches_prop
19287     \__prg_break:
19288   }
19289 }

```

(End definition for `\__regex_action_success:`.)

## 36.6 Replacement

### 36.6.1 Variables and helpers used in replacement

`\l__regex_replacement_csnames_int` The behaviour of closing braces inside a replacement text depends on whether a sequences `\c{` or `\u{` has been encountered. The number of “open” such sequences that should be closed by `}` is stored in `\l__regex_replacement_csnames_int`, and decreased by 1 by each `}`.

```

19290 \int_new:N \l__regex_replacement_csnames_int

```

(End definition for `\l__regex_replacement_csnames_int`.)

`\l__regex_replacement_category_tl` This sequence of letters is used to correctly restore categories in nested constructions such as `\cL(abc\cD(_d)`.

`\l__regex_replacement_category_seq`

```

19291 \tl_new:N \l__regex_replacement_category_tl
19292 \seq_new:N \l__regex_replacement_category_seq

```

(End definition for `\l__regex_replacement_category_tl` and `\l__regex_replacement_category_seq`.)

`\l__regex_balance_tl` This token list holds the replacement text for `\__regex_replacement_balance_one_match:n` while it is being built incrementally.

```

19293 \tl_new:N \l__regex_balance_tl

```

(End definition for `\l__regex_balance_tl`.)

`\__regex_replacement_balance_one_match:n` This expects as an argument the first index of a set of entries in `\g__regex_submatch_begin_intarray` (and related arrays) which hold the submatch information for a given match. It can be used within an integer expression to obtain the brace balance incurred by performing the replacement on that match. This combines the braces lost by removing the match, braces added by all the submatches appearing in the replacement, and braces appearing explicitly in the replacement. Even though it is always redefined before use,

we initialize it as for an empty replacement. An important property is that concatenating several calls to that function must result in a valid integer expression (hence a leading + in the actual definition).

```
19294 \cs_new:Npn \__regex_replacement_balance_one_match:n #1
19295 { - \__regex_submatch_balance:n {#1} }
```

(End definition for \\_\_regex\_replacement\_balance\_one\_match:n.)

\\_\_regex\_replacement\_do\_one\_match:n

The input is the same as \\_\_regex\_replacement\_balance\_one\_match:n. This function is redefined to expand to the part of the token list from the end of the previous match to a given match, followed by the replacement text. Hence concatenating the result of this function with all possible arguments (one call for each match), as well as the range from the end of the last match to the end of the string, produces the fully replaced token list. The initialization does not matter, but (as an example) we set it as for an empty replacement.

```
19296 \cs_new:Npn \__regex_replacement_do_one_match:n #1
19297 {
19298   \__regex_query_range:nn
19299   { \__intarray_item_fast:Nn \g__regex_submatch_prev_intarray {#1} }
19300   { \__intarray_item_fast:Nn \g__regex_submatch_begin_intarray {#1} }
19301 }
```

(End definition for \\_\_regex\_replacement\_do\_one\_match:n.)

\\_\_regex\_replacement\_exp\_not:N

This function lets us navigate around the fact that the primitive \exp\_not:n requires a braced argument. As far as I can tell, it is only needed if the user tries to include in the replacement text a control sequence set equal to a macro parameter character, such as \c\_parameter\_token. Indeed, within an x-expanding assignment, \exp\_not:N # behaves as a single #, whereas \exp\_not:n {#} behaves as a doubled ##.

```
19302 \cs_new:Npn \__regex_replacement_exp_not:N #1 { \exp_not:n {#1} }
```

(End definition for \\_\_regex\_replacement\_exp\_not:N.)

### 36.6.2 Query and brace balance

\\_\_regex\_query\_range:nn

\\_\_regex\_query\_range\_loop:ww

When it is time to extract submatches from the token list, the various tokens are stored in \toks registers numbered from \l\_\_regex\_min\_pos\_int inclusive to \l\_\_regex\_max\_pos\_int exclusive. The function \\_\_regex\_query\_range:nn {<min>} {<max>} unpacks registers from the position <min> to the position <max> - 1 included. Once this is expanded, a second x-expansion results in the actual tokens from the query. That second expansion is only done by user functions at the very end of their operation, after checking (and correcting) the brace balance first.

```
19303 \cs_new:Npn \__regex_query_range:nn #1#2
19304 {
19305   \exp_after:wN \__regex_query_range_loop:ww
19306   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
19307   \__int_value:w \__int_eval:w #2 ;
19308   \__prg_break_point:
19309 }
19310 \cs_new:Npn \__regex_query_range_loop:ww #1 ; #2 ;
19311 {
19312   \if_int_compare:w #1 < #2 \exp_stop_f:
19313   \else:
```

```

19314     \exp_after:wN \__prg_break:
19315 \fi:
19316 \__regex_toks_use:w #1 \exp_stop_f:
19317 \exp_after:wN \__regex_query_range_loop:ww
19318     \__int_value:w \__int_eval:w #1 + 1 ; #2 ;
19319 }

```

(End definition for \\_\_regex\_query\_range:nn and \\_\_regex\_query\_range\_loop:ww.)

\\_\_regex\_query\_submatch:n Find the start and end positions for a given submatch (of a given match).

```

19320 \cs_new:Npn \__regex_query_submatch:n #1
19321 {
19322     \__regex_query_range:nn
19323     { \__intarray_item_fast:Nn \g__regex_submatch_begin_intarray {#1} }
19324     { \__intarray_item_fast:Nn \g__regex_submatch_end_intarray {#1} }
19325 }

```

(End definition for \\_\_regex\_query\_submatch:n.)

\\_\_regex\_submatch\_balance:n Every user function must result in a balanced token list (unbalanced token lists cannot be stored by TeX). When we unpacked the query, we kept track of the brace balance, hence the contribution from a given range is the difference between the brace balances at the  $\langle \max pos \rangle$  and  $\langle \min pos \rangle$ . These two positions are found in the corresponding “submatch” arrays.

```

19326 \cs_new_protected:Npn \__regex_submatch_balance:n #1
19327 {
19328     \__int_eval:w
19329     \int_compare:nNnTF
19330     { \__intarray_item_fast:Nn \g__regex_submatch_end_intarray {#1} } = 0
19331     { 0 }
19332     {
19333         \__intarray_item_fast:Nn \g__regex_balance_intarray
19334         { \__intarray_item_fast:Nn \g__regex_submatch_end_intarray {#1} }
19335     }
19336     -
19337     \int_compare:nNnTF
19338     { \__intarray_item_fast:Nn \g__regex_submatch_begin_intarray {#1} } = 0
19339     { 0 }
19340     {
19341         \__intarray_item_fast:Nn \g__regex_balance_intarray
19342         { \__intarray_item_fast:Nn \g__regex_submatch_begin_intarray {#1} }
19343     }
19344     \__int_eval_end:
19345 }

```

(End definition for \\_\_regex\_submatch\_balance:n.)

### 36.6.3 Framework

\\_\_regex\_replacement:n The replacement text is built incrementally by abusing \toks within a group (see |3tl-build). We keep track in \l\_\_regex\_balance\_int of the balance of explicit begin- and end-group tokens and we store in \l\_\_regex\_balance\_tl some code to compute the brace balance from submatches (see its description). Detect unescaped right braces, and escaped characters, with trailing \prg\_do\_nothing: because some of the later function

look-ahead. Once the whole replacement text has been parsed, make sure that there is no open csname. Finally, define the `balance_one_match` and `do_one_match` functions.

```

19346 \cs_new_protected:Npn \__regex_replacement:n #1
19347 {
19348   <trace> \trace_push:nnn { regex } { 1 } { __regex_replacement:n }
19349   \__tl_build:Nw \l__regex_internal_a_tl
19350   \int_zero:N \l__regex_balance_int
19351   \tl_clear:N \l__regex_balance_tl
19352   \__regex_escape_use:nnnn
19353   {
19354     \if_charcode:w \c_right_brace_str ##1
19355       \__regex_replacement_rbrace:N
19356     \else:
19357       \__regex_replacement_normal:n
19358     \fi:
19359     ##1
19360   }
19361   { \__regex_replacement_escaped:N ##1 }
19362   { \__regex_replacement_normal:n ##1 }
19363   {#1}
19364   \prg_do_nothing: \prg_do_nothing:
19365   \if_int_compare:w \l__regex_replacement_csnames_int > 0 \exp_stop_f:
19366     \__msg_kernel_error:nnx { kernel } { replacement-missing-rbrace }
19367     { \int_use:N \l__regex_replacement_csnames_int }
19368     \__tl_build_one:x
19369     { \prg_replicate:nn \l__regex_replacement_csnames_int \cs_end: }
19370   \fi:
19371   \seq_if_empty:NF \l__regex_replacement_category_seq
19372   {
19373     \__msg_kernel_error:nnx { kernel } { replacement-missing-rparen }
19374     { \seq_count:N \l__regex_replacement_category_seq }
19375     \seq_clear:N \l__regex_replacement_category_seq
19376   }
19377   \cs_gset:Npx \__regex_replacement_balance_one_match:n ##1
19378   {
19379     + \int_use:N \l__regex_balance_int
19380     \l__regex_balance_tl
19381     - \__regex_submatch_balance:n {##1}
19382   }
19383   \__tl_build_end:
19384   \exp_args:No \__regex_replacement_aux:n \l__regex_internal_a_tl
19385   <trace> \trace_pop:nnn { regex } { 1 } { __regex_replacement:n }
19386 }
19387 \cs_new_protected:Npn \__regex_replacement_aux:n #1
19388 {
19389   \cs_set:Npn \__regex_replacement_do_one_match:n ##1
19390   {
19391     \__regex_query_range:nn
19392     { \__intarray_item_fast:Nn \g__regex_submatch_prev_intarray {##1} }
19393     { \__intarray_item_fast:Nn \g__regex_submatch_begin_intarray {##1} }
19394     #1
19395   }
19396 }

```

(End definition for `\_regex_replacement:n` and `\_regex_replacement_aux:n`.)

```

\_regex_replacement_normal:n Most characters are simply sent to the output by \_tl_build_one:n, unless a particu-
                             lar category code has been requested: then \_regex_replacement_c_A:w or a similar
                             auxiliary is called. One exception is right parentheses, which restore the category code in
                             place before the group started. Note that the sequence is non-empty there: it contains an
                             empty entry corresponding to the initial value of \l__regex_replacement_category_tl.
19397 \cs_new_protected:Npn \_regex_replacement_normal:n #1
19398   {
19399     \tl_if_empty:NTF \l__regex_replacement_category_tl
19400     { \_tl_build_one:n {#1} }
19401     { % (
19402       \token_if_eq_charcode:NNTF #1 )
19403       {
19404         \seq_pop:NN \l__regex_replacement_category_seq
19405         \l__regex_replacement_category_tl
19406       }
19407       {
19408         \use:c { __regex_replacement_c_ \l__regex_replacement_category_tl :w }
19409         \_regex_replacement_normal:n {#1}
19410       }
19411     }
19412   }

```

(End definition for `\_regex_replacement_normal:n`.)

`\_regex_replacement_escaped:N` As in parsing a regular expression, we use an auxiliary built from `#1` if defined. Otherwise, check for escaped digits (standing from submatches from 0 to 9): anything else is a raw character. We use `\token_to_str:N` to give spaces the right category code.

```

19413 \cs_new_protected:Npn \_regex_replacement_escaped:N #1
19414   {
19415     \cs_if_exist_use:cF { __regex_replacement_#1:w }
19416     {
19417       \if_int_compare:w 1 < 1#1 \exp_stop_f:
19418       \_regex_replacement_put_submatch:n {#1}
19419       \else:
19420       \exp_args:No \_regex_replacement_normal:n
19421       { \token_to_str:N #1 }
19422       \fi:
19423     }
19424   }

```

(End definition for `\_regex_replacement_escaped:N`.)

### 36.6.4 Submatches

`\_regex_replacement_put_submatch:n` Insert a submatch in the replacement text. This is dropped if the submatch number is larger than the number of capturing groups. Unless the submatch appears inside a `\c{...}` or `\u{...}` construction, it must be taken into account in the brace balance. Later on, `##1` will be replaced by a pointer to the 0-th submatch for a given match. We cannot use `\int_eval:n` because it is expandable, and would be expanded too early (short of adding `\exp_not:N`, making the code messy again).

```

19425 \cs_new_protected:Npn \_regex_replacement_put_submatch:n #1

```

```

19426 {
19427     \if_int_compare:w #1 < \l__regex_capturing_group_int
19428     \__tl_build_one:n { \__regex_query_submatch:n { #1 + ##1 } }
19429     \if_int_compare:w \l__regex_replacement_csnames_int = 0 \exp_stop_f:
19430     \tl_put_right:Nn \l__regex_balance_tl
19431     { + \__regex_submatch_balance:n { \__int_eval:w #1+##1 \__int_eval_end: } }
19432     \fi:
19433     \fi:
19434 }

```

(End definition for \\_\_regex\_replacement\_put\_submatch:n.)

\\_\_regex\_replacement\_g:w Grab digits for the \g escape sequence in a primitive assignment to the integer \l\_\_-  
 \\_\_regex\_replacement\_g\_digits:NN regex\_internal\_a\_int. At the end of the run of digits, check that it ends with a right brace.

```

19435 \cs_new_protected:Npn \__regex_replacement_g:w #1#2
19436 {
19437     \str_if_eq_x:nnTF { #1#2 } { \__regex_replacement_normal:n \c_left_brace_str }
19438     { \l__regex_internal_a_int = \__regex_replacement_g_digits:NN }
19439     { \__regex_replacement_error:NNN g #1 #2 }
19440 }
19441 \cs_new:Npn \__regex_replacement_g_digits:NN #1#2
19442 {
19443     \token_if_eq_meaning:NNTF #1 \__regex_replacement_normal:n
19444     {
19445         \if_int_compare:w 1 < 1#2 \exp_stop_f:
19446         #2
19447         \exp_after:wN \use_i:nnn
19448         \exp_after:wN \__regex_replacement_g_digits:NN
19449     \else:
19450         \exp_stop_f:
19451         \exp_after:wN \__regex_replacement_error:NNN
19452         \exp_after:wN g
19453     \fi:
19454 }
19455 {
19456     \exp_stop_f:
19457     \if_meaning:w \__regex_replacement_rbrace:N #1
19458     \exp_args:No \__regex_replacement_put_submatch:n
19459     { \int_use:N \l__regex_internal_a_int }
19460     \exp_after:wN \use_none:nn
19461     \else:
19462         \exp_after:wN \__regex_replacement_error:NNN
19463         \exp_after:wN g
19464     \fi:
19465 }
19466 #1 #2
19467 }

```

(End definition for \\_\_regex\_replacement\_g:w and \\_\_regex\_replacement\_g\_digits:NN.)

### 36.6.5 Csnames in replacement

\\_\_regex\_replacement\_c:w \c may only be followed by an unescaped character. If followed by a left brace, start a control sequence by calling an auxiliary common with \u. Otherwise test whether the

category is known; if it is not, complain.

```

19468 \cs_new_protected:Npn \__regex_replacement_c:w #1#2
19469 {
19470   \token_if_eq_meaning:NNTF #1 \__regex_replacement_normal:n
19471   {
19472     \exp_after:wN \token_if_eq_charcode:NNTF \c_left_brace_str #2
19473     { \__regex_replacement_cu_aux:Nw \__regex_replacement_exp_not:N }
19474     {
19475       \cs_if_exist:cTF { \__regex_replacement_c_#2:w }
19476       { \__regex_replacement_cat:NNN #2 }
19477       { \__regex_replacement_error:NNN c #1#2 }
19478     }
19479   }
19480   { \__regex_replacement_error:NNN c #1#2 }
19481 }

```

(End definition for \\_\_regex\_replacement\_c:w.)

`\__regex_replacement_cu_aux:Nw` Start a control sequence with `\cs:w`, protected from expansion by #1 (either `\__regex_replacement_exp_not:N` or `\exp_not:V`), or turned to a string by `\tl_to_str:V` if inside another csname construction `\c` or `\u`. We use `\tl_to_str:V` rather than `\tl_to_str:N` to deal with integers and other registers.

```

19482 \cs_new_protected:Npn \__regex_replacement_cu_aux:Nw #1
19483 {
19484   \if_case:w \l__regex_replacement_csnames_int
19485   \__tl_build_one:n { \exp_not:n { \exp_after:wN #1 \cs:w } }
19486   \else:
19487   \__tl_build_one:n { \exp_not:n { \exp_after:wN \tl_to_str:V \cs:w } }
19488   \fi:
19489   \int_incr:N \l__regex_replacement_csnames_int
19490 }

```

(End definition for \\_\_regex\_replacement\_cu\_aux:Nw.)

`\__regex_replacement_u:w` Check that `\u` is followed by a left brace. If so, start a control sequence with `\cs:w`, which is then unpacked either with `\exp_not:V` or `\tl_to_str:V` depending on the current context.

```

19491 \cs_new_protected:Npn \__regex_replacement_u:w #1#2
19492 {
19493   \str_if_eq_x:nnTF { #1#2 } { \__regex_replacement_normal:n \c_left_brace_str }
19494   { \__regex_replacement_cu_aux:Nw \exp_not:V }
19495   { \__regex_replacement_error:NNN u #1#2 }
19496 }

```

(End definition for \\_\_regex\_replacement\_u:w.)

`\__regex_replacement_rbrace:N` Within a `\c{...}` or `\u{...}` construction, end the control sequence, and decrease the brace count. Otherwise, this is a raw right brace.

```

19497 \cs_new_protected:Npn \__regex_replacement_rbrace:N #1
19498 {
19499   \if_int_compare:w \l__regex_replacement_csnames_int > 0 \exp_stop_f:
19500   \__tl_build_one:n \cs_end:
19501   \int_decr:N \l__regex_replacement_csnames_int
19502   \else:

```

```

19503     \_regex_replacement_normal:n {#1}
19504     \fi:
19505 }

```

(End definition for \\_regex\_replacement\_rbrace:N.)

### 36.6.6 Characters in replacement

Here, #1 is a letter among BEMTPUDSLOA and #2#3 denote the next character. Complain if we reach the end of the replacement or if the construction appears inside \c{...} or \u{...}, and detect the case of a parenthesis. In that case, store the current category in a sequence and switch to a new one.

```

19506 \cs_new_protected:Npn \_regex_replacement_cat:NNN #1#2#3
19507 {
19508     \token_if_eq_meaning:NNTF \prg_do_nothing: #3
19509     { \_msg_kernel_error:nn { kernel } { replacement-catcode-end } }
19510     {
19511         \int_compare:nNnTF { \l__regex_replacement_csnames_int } > 0
19512         {
19513             \_msg_kernel_error:nnnn
19514             { kernel } { replacement-catcode-in-cs } {#1} {#3}
19515             #2 #3
19516         }
19517         {
19518             \str_if_eq:nnTF { #2 #3 } { \_regex_replacement_normal:n ( } % )
19519             {
19520                 \seq_push:NV \l__regex_replacement_category_seq
19521                 \l__regex_replacement_category_tl
19522                 \tl_set:Nn \l__regex_replacement_category_tl {#1}
19523             }
19524             {
19525                 \token_if_eq_meaning:NNT #2 \_regex_replacement_escaped:N
19526                 {
19527                     \_regex_char_if_alphanumeric:NTF #3
19528                     {
19529                         \_msg_kernel_error:nnnn
19530                         { kernel } { replacement-catcode-escaped }
19531                         {#1} {#3}
19532                     }
19533                     { }
19534                 }
19535                 \use:c { \_regex_replacement_c_#1:w } #2 #3
19536             }
19537         }
19538     }
19539 }

```

(End definition for \\_regex\_replacement\_cat:NNN.)

We now need to change the category code of the null character many times, hence work in a group. The catcode-specific macros below are defined in alphabetical order; if you are trying to understand the code, start from the end of the alphabet as those categories are simpler than active or begin-group.

```

19540 \group_begin:

```



`\_regex_replacement_char:nNN` The only way to produce an arbitrary character–catcode pair is to use the `\lowercase` or `\uppercase` primitives. This is a wrapper for our purposes. The first argument is the null character with various catcodes. The second and third arguments are grabbed from the input stream: `#3` is the character whose character code to reproduce. We could use `\char_generate:nn` but only for some catcodes (active characters and spaces are not supported).

```

19541 \cs_new_protected:Npn \_regex_replacement_char:nNN #1#2#3
19542 {
19543   \tex_lccode:D 0 = '#3 \scan_stop:
19544   \tex_lowercase:D { \_tl_build_one:n {#1} }
19545 }

```

*(End definition for \\_regex\_replacement\_char:nNN.)*

`\_regex_replacement_c_A:w` For an active character, expansion must be avoided, twice because we later do two x-expansions, to unpack `\toks` for the query, and to expand their contents to tokens of the query.

```

19546 \char_set_catcode_active:N \^^@
19547 \cs_new_protected:Npn \_regex_replacement_c_A:w
19548 { \_regex_replacement_char:nNN { \exp_not:n { \exp_not:N \^^@ } } }

```

*(End definition for \\_regex\_replacement\_c\_A:w.)*

`\_regex_replacement_c_B:w` An explicit begin-group token increases the balance, unless within a `\c{...}` or `\u{...}` construction. Add the desired begin-group character, using the standard `\if_false:` trick. We eventually x-expand twice. The first time must yield a balanced token list, and the second one gives the bare begin-group token. The `\exp_after:wN` is not strictly needed, but is more consistent with l3tl-analysis.

```

19549 \char_set_catcode_group_begin:N \^^@
19550 \cs_new_protected:Npn \_regex_replacement_c_B:w
19551 {
19552   \if_int_compare:w \l__regex_replacement_csnames_int = 0 \exp_stop_f:
19553   \int_incr:N \l__regex_balance_int
19554   \fi:
19555   \_regex_replacement_char:nNN
19556   { \exp_not:n { \exp_after:wN \^^@ \if_false: } \fi: } }
19557 }

```

*(End definition for \\_regex\_replacement\_c\_B:w.)*

`\_regex_replacement_c_C:w` This is not quite catcode-related: when the user requests a character with category “control sequence”, the one-character control symbol is returned. As for the active character, we prepare for two x-expansions.

```

19558 \cs_new_protected:Npn \_regex_replacement_c_C:w #1#2
19559 { \_tl_build_one:n { \exp_not:N \exp_not:N \exp_not:c {#2} } }

```

*(End definition for \\_regex\_replacement\_c\_C:w.)*

`\_regex_replacement_c_D:w` Subscripts fit the mould: `\lowercase` the null byte with the correct category.

```

19560 \char_set_catcode_math_subscript:N \^^@
19561 \cs_new_protected:Npn \_regex_replacement_c_D:w
19562 { \_regex_replacement_char:nNN { \^^@ } }

```

*(End definition for \\_regex\_replacement\_c\_D:w.)*

`\_regex_replacement_c_E:w` Similar to the begin-group case, the second x-expansion produces the bare end-group token.

```

19563 \char_set_catcode_group_end:N \^^@
19564 \cs_new_protected:Npn \_regex_replacement_c_E:w
19565 {
19566   \if_int_compare:w \l__regex_replacement_csnames_int = 0 \exp_stop_f:
19567   \int_decr:N \l__regex_balance_int
19568   \fi:
19569   \_regex_replacement_char:nNN
19570   { \exp_not:n { \if_false: { \fi: ^^@ } }
19571   }

```

*(End definition for \\_regex\_replacement\_c\_E:w.)*

`\_regex_replacement_c_L:w` Simply `\lowercase` a letter null byte to produce an arbitrary letter.

```

19572 \char_set_catcode_letter:N \^^@
19573 \cs_new_protected:Npn \_regex_replacement_c_L:w
19574 { \_regex_replacement_char:nNN { ^^@ } }

```

*(End definition for \\_regex\_replacement\_c\_L:w.)*

`\_regex_replacement_c_M:w` No surprise here, we lowercase the null math toggle.

```

19575 \char_set_catcode_math_toggle:N \^^@
19576 \cs_new_protected:Npn \_regex_replacement_c_M:w
19577 { \_regex_replacement_char:nNN { ^^@ } }

```

*(End definition for \\_regex\_replacement\_c\_M:w.)*

`\_regex_replacement_c_O:w` Lowercase an other null byte.

```

19578 \char_set_catcode_other:N \^^@
19579 \cs_new_protected:Npn \_regex_replacement_c_O:w
19580 { \_regex_replacement_char:nNN { ^^@ } }

```

*(End definition for \\_regex\_replacement\_c\_O:w.)*

`\_regex_replacement_c_P:w` For macro parameters, expansion is a tricky issue. We need to prepare for two x-expansions and passing through various macro definitions. Note that we cannot replace one `\exp_not:n` by doubling the macro parameter characters because this would misbehave if a mischievous user asks for `\c{\cP\#}`, since that macro parameter character would be doubled.

```

19581 \char_set_catcode_parameter:N \^^@
19582 \cs_new_protected:Npn \_regex_replacement_c_P:w
19583 {
19584   \_regex_replacement_char:nNN
19585   { \exp_not:n { \exp_not:n { ^^@^^@^^@^^@ } } }
19586 }

```

*(End definition for \\_regex\_replacement\_c\_P:w.)*

`\_regex_replacement_c_S:w` Spaces are normalized on input by TeX to have character code 32. It is in fact impossible to get a token with character code 0 and category code 10. Hence we use 32 instead of 0 as our base character.

```

19587 \cs_new_protected:Npn \_regex_replacement_c_S:w #1#2
19588 {

```

```

19589 \if_int_compare:w '#2 = 0 \exp_stop_f:
19590 \__msg_kernel_error:nn { kernel } { replacement-null-space }
19591 \fi:
19592 \tex_lccode:D '\ = '#2 \scan_stop:
19593 \tex_lowercase:D { \__tl_build_one:n {~} }
19594 }

```

(End definition for `\__regex_replacement_c_S:w`.)

`\__regex_replacement_c_T:w` No surprise for alignment tabs here. Those are surrounded by the appropriate braces whenever necessary, hence they don't cause trouble in alignment settings.

```

19595 \char_set_catcode_alignment:N \^^@
19596 \cs_new_protected:Npn \__regex_replacement_c_T:w
19597 { \__regex_replacement_char:nnn { ^^@ } }

```

(End definition for `\__regex_replacement_c_T:w`.)

`\__regex_replacement_c_U:w` Simple call to `\__regex_replacement_char:nnn` which lowercases the math superscript `^^@`.

```

19598 \char_set_catcode_math_superscript:N \^^@
19599 \cs_new_protected:Npn \__regex_replacement_c_U:w
19600 { \__regex_replacement_char:nnn { ^^@ } }

```

(End definition for `\__regex_replacement_c_U:w`.)

Restore the catcode of the null byte.

```

19601 \group_end:

```

### 36.6.7 An error

`\__regex_replacement_error:nnn` Simple error reporting by calling one of the messages `replacement-c`, `replacement-g`, or `replacement-u`.

```

19602 \cs_new_protected:Npn \__regex_replacement_error:nnn #1#2#3
19603 {
19604   \__msg_kernel_error:nnx { kernel } { replacement-#1 } {#3}
19605   #2 #3
19606 }

```

(End definition for `\__regex_replacement_error:nnn`.)

## 36.7 User functions

`\regex_new:N` Before being assigned a sensible value, a regex variable matches nothing.

```

19607 \cs_new_protected:Npn \regex_new:N #1
19608 { \cs_new_eq:NN #1 \c__regex_no_match_regex }

```

(End definition for `\regex_new:N`. This function is documented on page 205.)

`\regex_set:Nn` Compile, then store the result in the user variable with the appropriate assignment function.  
`\regex_gset:Nn`  
`\regex_const:Nn`

```

19609 \cs_new_protected:Npn \regex_set:Nn #1#2
19610 {
19611   \__regex_compile:n {#2}
19612   \tl_set_eq:NN #1 \l__regex_internal_regex
19613 }

```

```

19614 \cs_new_protected:Npn \regex_gset:Nn #1#2
19615 {
19616   \__regex_compile:n {#2}
19617   \tl_gset_eq:NN #1 \l__regex_internal_regex
19618 }
19619 \cs_new_protected:Npn \regex_const:Nn #1#2
19620 {
19621   \__regex_compile:n {#2}
19622   \tl_const:Nx #1 { \exp_not:o \l__regex_internal_regex }
19623 }

```

(End definition for `\regex_set:Nn`, `\regex_gset:Nn`, and `\regex_const:Nn`. These functions are documented on page 205.)

**`\regex_show:N`** User functions: the `n` variant requires compilation first. Then show the variable with some appropriate text. The auxiliary `\__regex_show:Nx` is defined in a different section.

**`\regex_show:n`**

```

19624 \cs_new_protected:Npn \regex_show:n #1
19625 {
19626   \__regex_compile:n {#1}
19627   \__regex_show:Nn \l__regex_internal_regex
19628   { { \tl_to_str:n {#1} } }
19629 }
19630 \cs_new_protected:Npn \regex_show:N #1
19631 { \__regex_show:Nn #1 { variable~\token_to_str:N #1 } }

```

(End definition for `\regex_show:N` and `\regex_show:n`. These functions are documented on page 205.)

**`\regex_match:nnTF`** Those conditionals are based on a common auxiliary defined later. Its first argument builds the NFA corresponding to the regex, and the second argument is the query token list. Once we have performed the match, convert the resulting boolean to `\prg_return_true:` or false.

**`\regex_match:NnTF`**

```

19632 \prg_new_protected_conditional:Npnn \regex_match:nn #1#2 { T , F , TF }
19633 {
19634   \__regex_if_match:nn { \__regex_build:n {#1} } {#2}
19635   \__regex_return:
19636 }
19637 \prg_new_protected_conditional:Npnn \regex_match:Nn #1#2 { T , F , TF }
19638 {
19639   \__regex_if_match:nn { \__regex_build:N #1 } {#2}
19640   \__regex_return:
19641 }

```

(End definition for `\regex_match:nnTF` and `\regex_match:NnTF`. These functions are documented on page 205.)

**`\regex_count:nnN`** Again, use an auxiliary whose first argument builds the NFA.

**`\regex_count:NnN`**

```

19642 \cs_new_protected:Npn \regex_count:nnN #1
19643 { \__regex_count:nnN { \__regex_build:n {#1} } }
19644 \cs_new_protected:Npn \regex_count:NnN #1
19645 { \__regex_count:nnN { \__regex_build:N #1 } }

```

(End definition for `\regex_count:nnN` and `\regex_count:NnN`. These functions are documented on page 206.)

```

\regex_extract_once:nnN
\regex_extract_once:NnN
\regex_extract_all:nnN
\regex_extract_all:NnN
\regex_replace_once:nnN
\regex_replace_once:NnN
\regex_replace_all:nnN
\regex_replace_all:NnN
\regex_split:nnN
\regex_split:NnN
\regex_extract_once:nnNTF
\regex_extract_once:NnNTF
\regex_extract_all:nnNTF
\regex_extract_all:NnNTF
\regex_replace_once:nnNTF
\regex_replace_once:NnNTF
\regex_replace_all:nnNTF
\regex_replace_all:NnNTF
\regex_split:nnNTF
\regex_split:NnNTF

```

We define here 40 user functions, following a common pattern in terms of :nnN auxiliaries, defined in the coming subsections. The auxiliary is handed \\_\_regex\_build:n or \\_\_-regex\_build:N with the appropriate regex argument, then all other necessary arguments (replacement text, token list, *etc.* The conditionals call \\_\_regex\_return: to return either true or false once matching has been performed.

```

19646 \cs_set_protected:Npn \__regex_tmp:w #1#2#3
19647 {
19648   \cs_new_protected:Npn #2 ##1 { #1 { \__regex_build:n {##1} } }
19649   \cs_new_protected:Npn #3 ##1 { #1 { \__regex_build:N ##1 } }
19650   \prg_new_protected_conditional:Npnn #2 ##1##2##3 { T , F , TF }
19651     { #1 { \__regex_build:n {##1} } {##2} ##3 \__regex_return: }
19652   \prg_new_protected_conditional:Npnn #3 ##1##2##3 { T , F , TF }
19653     { #1 { \__regex_build:N ##1 } {##2} ##3 \__regex_return: }
19654 }
19655 \__regex_tmp:w \__regex_extract_once:nnN
19656 \__regex_tmp:w \__regex_extract_once:NnN
19657 \__regex_tmp:w \__regex_extract_all:nnN
19658 \__regex_tmp:w \__regex_extract_all:NnN
19659 \__regex_tmp:w \__regex_replace_once:nnN
19660 \__regex_tmp:w \__regex_replace_once:NnN
19661 \__regex_tmp:w \__regex_replace_all:nnN
19662 \__regex_tmp:w \__regex_replace_all:NnN
19663 \__regex_tmp:w \__regex_split:nnN \__regex_split:NnN

```

(End definition for \regex\_extract\_once:nnN and others. These functions are documented on page ??.)

### 36.7.1 Variables and helpers for user functions

\l\_\_regex\_match\_count\_int The number of matches found so far is stored in \l\_\_regex\_match\_count\_int. This is only used in the \regex\_count:nnN functions.

```
19664 \int_new:N \l__regex_match_count_int
```

(End definition for \l\_\_regex\_match\_count\_int.)

\_\_regex\_begin Those flags are raised to indicate extra begin-group or end-group tokens when extracting submatches.

```
19665 \flag_new:n { __regex_begin }
19666 \flag_new:n { __regex_end }
```

(End definition for \_\_regex\_begin and \_\_regex\_end.)

\l\_\_regex\_min\_submatch\_int The end-points of each submatch are stored in two arrays whose index *<submatch>* ranges from \l\_\_regex\_min\_submatch\_int (inclusive) to \l\_\_regex\_submatch\_int (exclusive). Each successful match comes with a 0-th submatch (the full match), and one match for each capturing group: submatches corresponding to the last successful match are labelled starting at zeroth\_submatch. The entry \l\_\_regex\_zeroth\_submatch\_int in \g\_\_regex\_submatch\_prev\_intarray holds the position at which that match attempt started: this is used for splitting and replacements.

```
19667 \int_new:N \l__regex_min_submatch_int
19668 \int_new:N \l__regex_submatch_int
19669 \int_new:N \l__regex_zeroth_submatch_int
```

(End definition for \l\_\_regex\_min\_submatch\_int, \l\_\_regex\_submatch\_int, and \l\_\_regex\_zeroth\_submatch\_int.)

`\g_regex_submatch_prev_intarray` Hold the place where the match attempt begun and the end-points of each submatch.

```

\g_regex_submatch_begin_intarray 19670 \__intarray_new:Nn \g_regex_submatch_prev_intarray { 65536 }
\g_regex_submatch_end_intarray    19671 \__intarray_new:Nn \g_regex_submatch_begin_intarray { 65536 }
                                   19672 \__intarray_new:Nn \g_regex_submatch_end_intarray { 65536 }

(End definition for \g_regex_submatch_prev_intarray, \g_regex_submatch_begin_intarray, and
 \g_regex_submatch_end_intarray.)

```

`\__regex_return:` This function triggers either `\prg_return_false:` or `\prg_return_true:` as appropriate to whether a match was found or not. It is used by all user conditionals.

```

19673 \cs_new_protected:Npn \__regex_return:
19674 {
19675     \if_meaning:w \c_true_bool \g_regex_success_bool
19676         \prg_return_true:
19677     \else:
19678         \prg_return_false:
19679     \fi:
19680 }

```

(End definition for `\__regex_return:`.)

### 36.7.2 Matching

`\__regex_if_match:nn` We don't track submatches, and stop after a single match. Build the NFA with #1, and perform the match on the query #2.

```

19681 \cs_new_protected:Npn \__regex_if_match:nn #1#2
19682 {
19683     \group_begin:
19684         \__regex_disable_submatches:
19685         \__regex_single_match:
19686         #1
19687         \__regex_match:n {#2}
19688     \group_end:
19689 }

```

(End definition for `\__regex_if_match:nn`.)

`\__regex_count:nnN` Again, we don't care about submatches. Instead of aborting after the first "longest match" is found, we search for multiple matches, incrementing `\l__regex_match_count_int` every time to record the number of matches. Build the NFA and match. At the end, store the result in the user's variable.

```

19690 \cs_new_protected:Npn \__regex_count:nnN #1#2#3
19691 {
19692     \group_begin:
19693         \__regex_disable_submatches:
19694         \int_zero:N \l__regex_match_count_int
19695         \__regex_multi_match:n { \int_incr:N \l__regex_match_count_int }
19696         #1
19697         \__regex_match:n {#2}
19698         \exp_args:NNNo
19699     \group_end:
19700     \int_set:Nn #3 { \int_use:N \l__regex_match_count_int }
19701 }

```

(End definition for `\__regex_count:nnN`.)

### 36.7.3 Extracting submatches

`__regex_extract_once:nnN` Match once or multiple times. After each match (or after the only match), extract the submatches using `__regex_extract:.` At the end, store the sequence containing all the submatches into the user variable #3 after closing the group.

```

19702 \cs_new_protected:Npn __regex_extract_once:nnN #1#2#3
19703 {
19704   \group_begin:
19705     __regex_single_match:
19706     #1
19707     __regex_match:n {#2}
19708     __regex_extract:
19709     __regex_group_end_extract_seq:N #3
19710   }
19711 \cs_new_protected:Npn __regex_extract_all:nnN #1#2#3
19712 {
19713   \group_begin:
19714     __regex_multi_match:n { __regex_extract: }
19715     #1
19716     __regex_match:n {#2}
19717     __regex_group_end_extract_seq:N #3
19718   }

```

(End definition for `__regex_extract_once:nnN` and `__regex_extract_all:nnN`.)

`__regex_split:nnN` Splitting at submatches is a bit more tricky. For each match, extract all submatches, and replace the zeroth submatch by the part of the query between the start of the match attempt and the start of the zeroth submatch. This is inhibited if the delimiter matched an empty token list at the start of this match attempt. After the last match, store the last part of the token list, which ranges from the start of the match attempt to the end of the query. This step is inhibited if the last match was empty and at the very end: decrement `\l__regex_submatch_int`, which controls which matches will be used.

```

19719 \cs_new_protected:Npn __regex_split:nnN #1#2#3
19720 {
19721   \group_begin:
19722     __regex_multi_match:n
19723     {
19724       \if_int_compare:w \l__regex_start_pos_int < \l__regex_success_pos_int
19725         __regex_extract:
19726         __intarray_gset_fast:Nnn \g__regex_submatch_prev_intarray
19727         { \l__regex_zeroth_submatch_int } { 0 }
19728         __intarray_gset_fast:Nnn \g__regex_submatch_end_intarray
19729         { \l__regex_zeroth_submatch_int }
19730         {
19731           __intarray_item_fast:Nn \g__regex_submatch_begin_intarray
19732           { \l__regex_zeroth_submatch_int }
19733         }
19734         __intarray_gset_fast:Nnn \g__regex_submatch_begin_intarray
19735         { \l__regex_zeroth_submatch_int }
19736         { \l__regex_start_pos_int }
19737       \fi:
19738     }
19739     #1
19740     __regex_match:n {#2}

```

```

19741 (assert)\assert_int:n { \l__regex_curr_pos_int = \l__regex_max_pos_int }
19742   \__intarray_gset_fast:Nnn \g__regex_submatch_prev_intarray
19743     { \l__regex_submatch_int } { 0 }
19744   \__intarray_gset_fast:Nnn \g__regex_submatch_end_intarray
19745     { \l__regex_submatch_int }
19746     { \l__regex_max_pos_int }
19747   \__intarray_gset_fast:Nnn \g__regex_submatch_begin_intarray
19748     { \l__regex_submatch_int }
19749     { \l__regex_start_pos_int }
19750   \int_incr:N \l__regex_submatch_int
19751   \if_meaning:w \c_true_bool \l__regex_empty_success_bool
19752     \if_int_compare:w \l__regex_start_pos_int = \l__regex_max_pos_int
19753       \int_decr:N \l__regex_submatch_int
19754     \fi:
19755   \fi:
19756   \__regex_group_end_extract_seq:N #3
19757 }

```

(End definition for \\_\_regex\_split:nnN.)

\\_\_regex\_group\_end\_extract\_seq:N The end-points of submatches are stored as entries of two arrays from \l\_\_regex\_min\_submatch\_int to \l\_\_regex\_submatch\_int (exclusive). Extract the relevant ranges into \l\_\_regex\_internal\_a\_tl. We detect unbalanced results using the two flags @@\_begin and @@\_end, raised whenever we see too many begin-group or end-group tokens in a submatch. We disable \\_\_seq\_item:n to prevent two x-expansions.

```

19758 \cs_new_protected:Npn \__regex_group_end_extract_seq:N #1
19759 {
19760   \cs_set_eq:NN \__seq_item:n \scan_stop:
19761   \flag_clear:n { __regex_begin }
19762   \flag_clear:n { __regex_end }
19763   \tl_set:Nx \l__regex_internal_a_tl
19764     {
19765       \s__seq
19766       \int_step_function:nnnN
19767         { \l__regex_min_submatch_int }
19768         { 1 }
19769         { \l__regex_submatch_int - 1 }
19770       \__regex_extract_seq_aux:n
19771     }
19772   \int_compare:nNnF
19773     { \flag_height:n { __regex_begin } + \flag_height:n { __regex_end } }
19774     = 0
19775     {
19776       \__msg_kernel_error:nnxxx { kernel } { result-unbalanced }
19777       { splitting~or~extracting~submatches }
19778       { \flag_height:n { __regex_end } }
19779       { \flag_height:n { __regex_begin } }
19780     }
19781   \use:x
19782   {
19783     \group_end:
19784     \tl_set:Nn \exp_not:N #1 { \l__regex_internal_a_tl }
19785   }
19786 }

```



(End definition for `\_regex_group_end_extract_seq:N`.)

`\_regex_extract_seq_aux:n` The `:n` auxiliary builds one item of the sequence of submatches. First compute the brace balance of the submatch, then extract the submatch from the query, adding the appropriate braces and raising a flag if the submatch is not balanced.

`\_regex_extract_seq_aux:ww`

```

19787 \cs_new:Npn \_regex_extract_seq_aux:n #1
19788 {
19789   \_seq_item:n
19790   {
19791     \exp_after:wN \_regex_extract_seq_aux:ww
19792     \_int_value:w \_regex_submatch_balance:n {#1} ; #1;
19793   }
19794 }
19795 \cs_new:Npn \_regex_extract_seq_aux:ww #1; #2;
19796 {
19797   \if_int_compare:w #1 < 0 \exp_stop_f:
19798     \flag_raise:n { \_regex_end }
19799     \prg_replicate:nn {-#1} { \exp_not:n { { \if_false: } \fi: } }
19800   \fi:
19801   \_regex_query_submatch:n {#2}
19802   \if_int_compare:w #1 > 0 \exp_stop_f:
19803     \flag_raise:n { \_regex_begin }
19804     \prg_replicate:nn {#1} { \exp_not:n { \if_false: { \fi: } } }
19805   \fi:
19806 }
```

(End definition for `\_regex_extract_seq_aux:n` and `\_regex_extract_seq_aux:ww`.)

`\_regex_extract:`  
`\_regex_extract_b:wn`  
`\_regex_extract_e:wn`

Our task here is to extract from the property list `\l__regex_success_submatches_prop` the list of end-points of submatches, and store them in appropriate array entries, from `\l__regex_zeroth_submatch_int` upwards. We begin by emptying those entries. Then for each  $\langle key \rangle$ – $\langle value \rangle$  pair in the property list update the appropriate entry. This is somewhat a hack: the  $\langle key \rangle$  is a non-negative integer followed by `<` or `>`, which we use in a comparison to `-1`. At the end, store the information about the position at which the match attempt started, in `\g__regex_submatch_prev_intarray`.

```

19807 \cs_new_protected:Npn \_regex_extract:
19808 {
19809   \if_meaning:w \c_true_bool \g__regex_success_bool
19810     \int_set_eq:NN \l__regex_zeroth_submatch_int \l__regex_submatch_int
19811     \prg_replicate:nn \l__regex_capturing_group_int
19812     {
19813       \__intarray_gset_fast:Nnn \g__regex_submatch_begin_intarray
19814       { \l__regex_submatch_int } { 0 }
19815       \__intarray_gset_fast:Nnn \g__regex_submatch_end_intarray
19816       { \l__regex_submatch_int } { 0 }
19817       \__intarray_gset_fast:Nnn \g__regex_submatch_prev_intarray
19818       { \l__regex_submatch_int } { 0 }
19819       \int_incr:N \l__regex_submatch_int
19820     }
19821   \prop_map_inline:Nn \l__regex_success_submatches_prop
19822   {
19823     \if_int_compare:w ##1 - 1 \exp_stop_f:
19824     \exp_after:wN \_regex_extract_e:wn \_int_value:w
```

```

19825         \else:
19826             \exp_after:wN \__regex_extract_b:wn \__int_value:w
19827         \fi:
19828         \__int_eval:w \l__regex_zeroth_submatch_int + ##1 {##2}
19829     }
19830     \__intarray_gset_fast:Nnn \g__regex_submatch_prev_intarray
19831     { \l__regex_zeroth_submatch_int } { \l__regex_start_pos_int }
19832 \fi:
19833 }
19834 \cs_new_protected:Npn \__regex_extract_b:wn #1 < #2
19835 { \__intarray_gset_fast:Nnn \g__regex_submatch_begin_intarray {#1} {#2} }
19836 \cs_new_protected:Npn \__regex_extract_e:wn #1 > #2
19837 { \__intarray_gset_fast:Nnn \g__regex_submatch_end_intarray {#1} {#2} }

```

(End definition for \\_\_regex\_extract:, \\_\_regex\_extract\_b:wn, and \\_\_regex\_extract\_e:wn.)

### 36.7.4 Replacement

\\_\_regex\_replace\_once:nnN

Build the NFA and the replacement functions, then find a single match. If the match failed, simply exit the group. Otherwise, we do the replacement. Extract submatches. Compute the brace balance corresponding to replacing this match by the replacement (this depends on submatches). Prepare the replaced token list: the replacement function produces the tokens from the start of the query to the start of the match and the replacement text for this match; we need to add the tokens from the end of the match to the end of the query. Finally, store the result in the user's variable after closing the group: this step involves an additional x-expansion, and checks that braces are balanced in the final result.

```

19838 \cs_new_protected:Npn \__regex_replace_once:nnN #1#2#3
19839 {
19840     \group_begin:
19841     \__regex_single_match:
19842     #1
19843     \__regex_replacement:n {#2}
19844     \exp_args:No \__regex_match:n { #3 }
19845     \if_meaning:w \c_false_bool \g__regex_success_bool
19846     \group_end:
19847     \else:
19848         \__regex_extract:
19849         \int_set:Nn \l__regex_balance_int
19850         {
19851             \__regex_replacement_balance_one_match:n
19852             { \l__regex_zeroth_submatch_int }
19853         }
19854         \tl_set:Nx \l__regex_internal_a_tl
19855         {
19856             \__regex_replacement_do_one_match:n { \l__regex_zeroth_submatch_int }
19857             \__regex_query_range:nn
19858             {
19859                 \__intarray_item_fast:Nn \g__regex_submatch_end_intarray
19860                 { \l__regex_zeroth_submatch_int }
19861             }
19862             { \l__regex_max_pos_int }
19863         }
19864         \__regex_group_end_replace:N #3
19865     \fi:

```

```
19866 }
```

(End definition for `\__regex_replace_once:nnN`.)

`\__regex_replace_all:nnN` Match multiple times, and for every match, extract submatches and additionally store the position at which the match attempt started. The entries from `\l__regex_min_submatch_int` to `\l__regex_submatch_int` hold information about submatches of every match in order; each match corresponds to `\l__regex_capturing_group_int` consecutive entries. Compute the brace balance corresponding to doing all the replacements: this is the sum of brace balances for replacing each match. Join together the replacement texts for each match (including the part of the query before the match), and the end of the query.

```
19867 \cs_new_protected:Npn \__regex_replace_all:nnN #1#2#3
19868 {
19869   \group_begin:
19870   \__regex_multi_match:n { \__regex_extract: }
19871   #1
19872   \__regex_replacement:n {#2}
19873   \exp_args:No \__regex_match:n {#3}
19874   \int_set:Nn \l__regex_balance_int
19875   {
19876     0
19877     \int_step_function:nnnN
19878     { \l__regex_min_submatch_int }
19879     \l__regex_capturing_group_int
19880     { \l__regex_submatch_int - 1 }
19881     \__regex_replacement_balance_one_match:n
19882   }
19883   \tl_set:Nx \l__regex_internal_a_tl
19884   {
19885     \int_step_function:nnnN
19886     { \l__regex_min_submatch_int }
19887     \l__regex_capturing_group_int
19888     { \l__regex_submatch_int - 1 }
19889     \__regex_replacement_do_one_match:n
19890     \__regex_query_range:nn
19891     \l__regex_start_pos_int \l__regex_max_pos_int
19892   }
19893   \__regex_group_end_replace:N #3
19894 }
```

(End definition for `\__regex_replace_all:nnN`.)

`\__regex_group_end_replace:N` If the brace balance is not 0, raise an error. Then set the user's variable #1 to the x-expansion of `\l__regex_internal_a_tl`, adding the appropriate braces to produce a balanced result. And end the group.

```
19895 \cs_new_protected:Npn \__regex_group_end_replace:N #1
19896 {
19897   \if_int_compare:w \l__regex_balance_int = 0 \exp_stop_f:
19898   \else:
19899     \__msg_kernel_error:nnxxx { kernel } { result-unbalanced }
19900     { replacing }
19901     { \int_max:nn { - \l__regex_balance_int } { 0 } }
19902     { \int_max:nn { \l__regex_balance_int } { 0 } }
```

```

19903     \fi:
19904     \use:x
19905     {
19906         \group_end:
19907         \tl_set:Nn \exp_not:N #1
19908         {
19909             \if_int_compare:w \l__regex_balance_int < 0 \exp_stop_f:
19910             \prg_replicate:nn { - \l__regex_balance_int }
19911             { { \if_false: } \fi: }
19912             \fi:
19913             \l__regex_internal_a_tl
19914             \if_int_compare:w \l__regex_balance_int > 0 \exp_stop_f:
19915             \prg_replicate:nn { \l__regex_balance_int }
19916             { \if_false: { \fi: } }
19917             \fi:
19918         }
19919     }
19920 }

```

(End definition for `\__regex_group_end_replace:N`.)

### 36.7.5 Storing and showing compiled patterns

## 36.8 Messages

Messages for the preparsing phase.

```

19921 \__msg_kernel_new:nnnn { kernel } { trailing-backslash }
19922 { Trailing-escape-character~'\iow_char:N\\'. }
19923 {
19924     A~regular-expression-or-its-replacement-text-ends-with~
19925     the-escape-character~'\iow_char:N\\'.~It-will-be-ignored.
19926 }
19927 \__msg_kernel_new:nnnn { kernel } { x-missing-rbrace }
19928 { Missing-closing-brace-in~'\iow_char:N\\x'~hexadecimal-sequence. }
19929 {
19930     You-wrote-something-like~
19931     '\iow_char:N\\x{\...#1'~
19932     The-closing-brace-is-missing.
19933 }
19934 \__msg_kernel_new:nnnn { kernel } { x-overflow }
19935 { Character-code~'#1'~too-large-in~'\iow_char:N\\x'~hexadecimal-sequence. }
19936 {
19937     You-wrote-something-like~
19938     '\iow_char:N\\x{\int_to_Hex:n{#1}}'.~
19939     The-character-code~#1~is-larger-than~
19940     the-maximum-value~\int_use:N \c_max_char_int.
19941 }

```

Invalid quantifier.

```

19942 \__msg_kernel_new:nnnn { kernel } { invalid-quantifier }
19943 { Braced-quantifier~'#1'~may-not-be-followed-by~'#2'. }
19944 {
19945     The-character~'#2'~is-invalid-in-the-braced-quantifier~'#1'~
19946     The-only-valid-quantifiers-are~'*',~'?',~'+',~'{<int>}',~
19947     '{<min>,'~and~'{<min>,<max>}',~optionally-followed-by~'?''.

```

19948 }

Messages for missing or extra closing brackets and parentheses, with some fancy singular/plural handling for the case of parentheses.

```
19949 \__msg_kernel_new:nnnn { kernel } { missing-rbrack }
19950 { Missing-right-bracket-inserted-in-regular-expression. }
19951 {
19952   LaTeX~was~given~a~regular~expression~where~a~character~class~
19953   was~started~with~'['~,~but~the~matching~'']~is~missing.
19954 }
19955 \__msg_kernel_new:nnnn { kernel } { missing-rparen }
19956 {
19957   Missing-right~
19958   \int_compare:nTF { #1 = 1 } { parenthesis } { parentheses } ~
19959   inserted-in-regular-expression.
19960 }
19961 {
19962   LaTeX~was~given~a~regular~expression~with~\int_eval:n {#1} ~
19963   more~left~parentheses~than~right~parentheses.
19964 }
19965 \__msg_kernel_new:nnnn { kernel } { extra-rparen }
19966 { Extra-right-parenthesis-ignored-in-regular-expression. }
19967 {
19968   LaTeX~came~across~a~closing-parenthesis~when~no~submatch-group~
19969   was~open.~The~parenthesis~will~be~ignored.
19970 }
```

Some escaped alphanumerics are not allowed everywhere.

```
19971 \__msg_kernel_new:nnnn { kernel } { bad-escape }
19972 {
19973   Invalid-escape~'\iow_char:N\\#1'~
19974   \__regex_if_in_cs:TF { within-a-control-sequence. }
19975   {
19976     \__regex_if_in_class:TF
19977     { in-a-character-class. }
19978     { following-a-category-test. }
19979   }
19980 }
19981 {
19982   The~escape~sequence~'\iow_char:N\\#1'~may~not~appear~
19983   \__regex_if_in_cs:TF
19984   {
19985     within-a-control-sequence-test-introduced-by~
19986     '\iow_char:N\\c\iow_char:N\{' .
19987   }
19988   {
19989     \__regex_if_in_class:TF
19990     { within-a-character-class~ }
19991     { following-a-category-test~such~as~'\iow_char:N\\cL'~ }
19992     because-it~does~not~match~exactly~one~character.
19993   }
19994 }
```

Range errors.

```
19995 \__msg_kernel_new:nnnn { kernel } { range-missing-end }
```

```

19996 { Invalid-end-point-for-range-~'#1-#2'~in-character-class. }
19997 {
19998   The-end-point-~'#2'~of-the-range-~'#1-#2'~may-not-serve-as-an-
19999   end-point-for-a-range:~alphanumeric-characters-should-not-be-
20000   escaped,~and-non-alphanumeric-characters-should-be-escaped.
20001 }
20002 \_msg_kernel_new:nnnn { kernel } { range-backwards }
20003 { Range-~'#1-#2'~out-of-order-in-character-class. }
20004 {
20005   In-ranges-of-characters~'[x-y]'~appearing-in-character-classes,~
20006   the-first-character-code-must-not-be-larger-than-the-second.~
20007   Here,~'#1'~has-character-code~\int_eval:n {'#1},~while~
20008   '#2'~has-character-code~\int_eval:n {'#2}.
20009 }

```

Errors related to \c and \u.

```

20010 \_msg_kernel_new:nnnn { kernel } { c-bad-mode }
20011 { Invalid-nested-~'\iow_char:N\\c'~escape-in-regular-expression. }
20012 {
20013   The-~'\iow_char:N\\c'~escape-cannot-be-used-within-
20014   a-control-sequence-test-~'\iow_char:N\\c{...}'~.~
20015   To-combine-several-category-tests,~use-~'\iow_char:N\\c[...]'.
20016 }
20017 \_msg_kernel_new:nnnn { kernel } { c-C-invalid }
20018 { '~'\iow_char:N\\cC'~should-be-followed-by~'.'~or~'(',~not~'#1'. }
20019 {
20020   The-~'\iow_char:N\\cC'~construction-restricts-the-next-item-to-be-a-
20021   control-sequence-or-the-next-group-to-be-made-of-control-sequences.~
20022   It-only-makes-sense-to-follow-it-by~'.'~or-by-a-group.
20023 }
20024 \_msg_kernel_new:nnnn { kernel } { c-missing-rbrace }
20025 { Missing-right-brace-inserted-for-~'\iow_char:N\\c'~escape. }
20026 {
20027   LaTeX-was-given-a-regular-expression-where-a-
20028   '~'\iow_char:N\\c\iow_char:N\{...'~construction-was-not-ended-
20029   with-a-closing-brace-~'\iow_char:N\}''.
20030 }
20031 \_msg_kernel_new:nnnn { kernel } { c-missing-rbrack }
20032 { Missing-right-bracket-inserted-for-~'\iow_char:N\\c'~escape. }
20033 {
20034   A-construction-~'\iow_char:N\\c[...'~appears-in-a-
20035   regular-expression,~but-the-closing~'']~is-not-present.
20036 }
20037 \_msg_kernel_new:nnnn { kernel } { c-missing-category }
20038 { Invalid-character-~'#1'~following-~'\iow_char:N\\c'~escape. }
20039 {
20040   In-regular-expressions,~the-~'\iow_char:N\\c'~escape-sequence~
20041   may-only-be-followed-by-a-left-brace,~a-left-bracket,~or-a-
20042   capital-letter-representing-a-character-category,~namely~
20043   one-of~'ABCDELMOPSTU'.
20044 }
20045 \_msg_kernel_new:nnnn { kernel } { c-trailing }
20046 { Trailing-category-code-escape-~'\iow_char:N\\c'... }
20047 {
20048   A-regular-expression-ends-with-~'\iow_char:N\\c'~followed-

```

```

20049     by~a~letter.~It~will~be~ignored.
20050   }
20051   \_msg_kernel_new:nnnn { kernel } { u-missing-lbrace }
20052   { Missing~left~brace~following~'\iow_char:N\\u'~escape. }
20053   {
20054     The~'\iow_char:N\\u'~escape~sequence~must~be~followed~by~
20055     a~brace~group~with~the~name~of~the~variable~to~use.
20056   }
20057   \_msg_kernel_new:nnnn { kernel } { u-missing-rbrace }
20058   { Missing~right~brace~inserted~for~'\iow_char:N\\u'~escape. }
20059   {
20060     LaTeX~
20061     \str_if_eq_x:nnTF { } {#2}
20062     { reached~the~end~of~the~string~ }
20063     { encountered~an~escaped~alphanumeric~character '\iow_char:N\\#2'~ }
20064     when~parsing~the~argument~of~an~'\iow_char:N\\u\iow_char:N\{...\}'~escape.
20065   }

```

Errors when encountering the POSIX syntax [:...:].

```

20066   \_msg_kernel_new:nnnn { kernel } { posix-unsupported }
20067   { POSIX~collating~element~'\#1 ~ #1'~not~supported. }
20068   {
20069     The~'\[.foo.]'~and~'\[=bar=]'~syntaxes~have~a~special~meaning~
20070     in~POSIX~regular~expressions.~This~is~not~supported~by~LaTeX.~
20071     Maybe~you~forgot~to~escape~a~left~bracket~in~a~character~class?
20072   }
20073   \_msg_kernel_new:nnnn { kernel } { posix-unknown }
20074   { POSIX~class~'\[:#1:]'~unknown. }
20075   {
20076     '\[:#1:]'~is~not~among~the~known~POSIX~classes~
20077     '\[:alnum:]',~'\[:alpha:]',~'\[:ascii:]',~'\[:blank:]',~
20078     '\[:cntrl:]',~'\[:digit:]',~'\[:graph:]',~'\[:lower:]',~
20079     '\[:print:]',~'\[:punct:]',~'\[:space:]',~'\[:upper:]',~
20080     '\[:word:]',~and~'\[:xdigit:]'.
20081   }
20082   \_msg_kernel_new:nnnn { kernel } { posix-missing-close }
20083   { Missing~closing~':'~for~POSIX~class. }
20084   { The~POSIX~syntax~'#1'~must~be~followed~by~':'',~not~'#2'. }

```

In various cases, the result of a `l3regex` operation can leave us with an unbalanced token list, which we must re-balance by adding begin-group or end-group character tokens.

```

20085   \_msg_kernel_new:nnnn { kernel } { result-unbalanced }
20086   { Missing~brace~inserted~when~#1. }
20087   {
20088     LaTeX~was~asked~to~do~some~regular~expression~operation,~
20089     and~the~resulting~token~list~would~not~have~the~same~number~
20090     of~begin~group~and~end~group~tokens.~Braces~were~inserted:~
20091     #2~left,~#3~right.
20092   }

```

Error message for unknown options.

```

20093   \_msg_kernel_new:nnnn { kernel } { unknown-option }
20094   { Unknown~option~'#1'~for~regular~expressions. }
20095   {

```

```

20096     The~only~available~option~is~'case-insensitive',~toggled-by~
20097     '(?i)'~and~'(?-i)'.
20098 }
20099 \_msg_kernel_new:nnnn { kernel } { special-group-unknown }
20100 { Unknown~special~group~'#1~...'~in~a~regular~expression. }
20101 {
20102     The~only~valid~constructions~starting~with~'?'~are~
20103     '(:~...~)',~'(?|~...~)',~'(?i)',~and~'(?-i)'.
20104 }

```

Errors in the replacement text.

```

20105 \_msg_kernel_new:nnnn { kernel } { replacement-c }
20106 { Misused~'\iow_char:N\\c'~command~in~a~replacement~text. }
20107 {
20108     In~a~replacement~text,~the~'\iow_char:N\\c'~escape~sequence~
20109     can~be~followed~by~one~of~the~letters~'ABCDELMOPTU'~
20110     or~a~brace~group,~not~by~'#1'.
20111 }
20112 \_msg_kernel_new:nnnn { kernel } { replacement-u }
20113 { Misused~'\iow_char:N\\u'~command~in~a~replacement~text. }
20114 {
20115     In~a~replacement~text,~the~'\iow_char:N\\u'~escape~sequence~
20116     must~be~followed~by~a~brace~group~holding~the~name~of~the~
20117     variable~to~use.
20118 }
20119 \_msg_kernel_new:nnnn { kernel } { replacement-g }
20120 {
20121     Missing~brace~for~the~'\iow_char:N\\g'~construction~
20122     in~a~replacement~text.
20123 }
20124 {
20125     In~the~replacement~text~for~a~regular~expression~search,~
20126     submatches~are~represented~either~as~'\iow_char:N \\g{dd..d}',~
20127     or~'\d',~where~'d'~are~single~digits.~Here,~a~brace~is~missing.
20128 }
20129 \_msg_kernel_new:nnnn { kernel } { replacement-catcode-end }
20130 {
20131     Missing~character~for~the~'\iow_char:N\\c<category><character>'~
20132     construction~in~a~replacement~text.
20133 }
20134 {
20135     In~a~replacement~text,~the~'\iow_char:N\\c'~escape~sequence~
20136     can~be~followed~by~one~of~the~letters~'ABCDELMOPTU'~representing~
20137     the~character~category.~Then,~a~character~must~follow.~LaTeX~
20138     reached~the~end~of~the~replacement~when~looking~for~that.
20139 }
20140 \_msg_kernel_new:nnnn { kernel } { replacement-catcode-escaped }
20141 {
20142     Escaped~letter~or~digit~after~category~code~in~replacement~text.
20143 }
20144 {
20145     In~a~replacement~text,~the~'\iow_char:N\\c'~escape~sequence~
20146     can~be~followed~by~one~of~the~letters~'ABCDELMOPTU'~representing~
20147     the~character~category.~Then,~a~character~must~follow,~not~
20148     '\iow_char:N\\#2'.

```



```

20149 }
20150 \_msg_kernel_new:nnnn { kernel } { replacement-catcode-in-cs }
20151 {
20152   Category-code~'\iow_char:N\c#1#3'~ignored~inside~
20153   '\iow_char:N\c\{...\}'~in~a~replacement~text.
20154 }
20155 {
20156   In~a~replacement~text,~the~category~codes~of~the~argument~of~
20157   '\iow_char:N\c\{...\}'~are~ignored~when~building~the~control~
20158   sequence~name.
20159 }
20160 \_msg_kernel_new:nnnn { kernel } { replacement-null-space }
20161 { TeX~cannot~build~a~space~token~with~character~code~0. }
20162 {
20163   You~asked~for~a~character~token~with~category~space,~
20164   and~character~code~0,~for~instance~through~
20165   '\iow_char:N\cS\iow_char:N\c00'.~
20166   This~specific~case~is~impossible~and~will~be~replaced~
20167   by~a~normal~space.
20168 }
20169 \_msg_kernel_new:nnnn { kernel } { replacement-missing-rbrace }
20170 { Missing~right~brace~inserted~in~replacement~text. }
20171 {
20172   There~ \int_compare:nTF { #1 = 1 } { was } { were } ~ #1~
20173   missing~right~\int_compare:nTF { #1 = 1 } { brace } { braces } .
20174 }
20175 \_msg_kernel_new:nnnn { kernel } { replacement-missing-rparen }
20176 { Missing~right~parenthesis~inserted~in~replacement~text. }
20177 {
20178   There~ \int_compare:nTF { #1 = 1 } { was } { were } ~ #1~
20179   missing~right~\int_compare:nTF { #1 = 1 } { parenthesis } { parentheses } .
20180 }

```

`\_regex_msg_repeated:nnN` This is not technically a message, but seems related enough to go there. The arguments are: #1 is the minimum number of repetitions; #2 is the number of allowed extra repetitions (−1 for infinite number), and #3 tells us about laziness.

```

20181 \cs_new:Npn \_regex_msg_repeated:nnN #1#2#3
20182 {
20183   \str_if_eq:x:nnF { #1 #2 } { 1 0 }
20184   {
20185     , ~ repeated ~
20186     \int_case:nnF {#2}
20187     {
20188       { -1 } { #1~or~more~times,~\bool_if:NTF #3 { lazy } { greedy } }
20189       { 0 } { #1~times }
20190     }
20191     {
20192       between~#1~and~\int_eval:n {#1+#2}~times,~
20193       \bool_if:NTF #3 { lazy } { greedy }
20194     }
20195   }
20196 }

```

(End definition for `\_regex_msg_repeated:nnN`.)

## 36.9 Code for tracing

The tracing code is still very experimental, and is meant to be used with the `l3trace` package, currently in `l3trial`.

```
\__regex_trace_states:n This function lists the contents of all states of the NFA, stored in \toks from 0 to \l__-
regex_max_state_int (excluded).
20197 < *trace>
20198 \cs_new_protected:Npn \__regex_trace_states:n #1
20199 {
20200   \int_step_inline:nnnn
20201     \l__regex_min_state_int
20202     { 1 }
20203     { \l__regex_max_state_int - 1 }
20204     {
20205       \trace:nxx { regex } { #1 }
20206       { \iow_char:N \toks ##1 = { \__regex_toks_use:w ##1 } }
20207     }
20208   }
20209 < /trace>

(End definition for \__regex_trace_states:n.)

20210 < /initex | package>
```

## 37 l3box implementation

```
20211 < *initex | package>
20212 < @@=box>
```

The code in this module is very straight forward so I'm not going to comment it very extensively.

### 37.1 Creating and initialising boxes

*The following test files are used for this code: `m3box001.lvt`.*

```
\box_new:N Defining a new <box> register: remember that box 255 is not generally available.
\box_new:c
20213 < *package>
20214 \cs_new_protected:Npn \box_new:N #1
20215 {
20216   \__chk_if_free_cs:N #1
20217   \cs:w newbox \cs_end: #1
20218 }
20219 < /package>
20220 \cs_generate_variant:Nn \box_new:N { c }

Clear a <box> register.
20221 \cs_new_protected:Npn \box_clear:N #1
\box_clear:N { \box_set_eq:NN #1 \c_empty_box }
20222
\box_clear:c 20223 \cs_new_protected:Npn \box_gclear:N #1
\box_gclear:N { \box_gset_eq:NN #1 \c_empty_box }
20224
\box_gclear:N 20225 \cs_generate_variant:Nn \box_clear:N { c }
\box_gclear:c 20226 \cs_generate_variant:Nn \box_gclear:N { c }
```

Clear or new.

```

20227 \cs_new_protected:Npn \box_clear_new:N #1
20228 { \box_if_exist:NTF #1 { \box_clear:N #1 } { \box_new:N #1 } }
\box_clear_new:c
20229 \cs_new_protected:Npn \box_gclear_new:N #1
20230 { \box_if_exist:NTF #1 { \box_gclear:N #1 } { \box_new:N #1 } }
\box_gclear_new:N
20231 \cs_generate_variant:Nn \box_clear_new:N { c }
20232 \cs_generate_variant:Nn \box_gclear_new:N { c }

```

Assigning the contents of a box to be another box.

```

20233 \cs_new_protected:Npn \box_set_eq:NN #1#2
20234 { \tex_setbox:D #1 \tex_copy:D #2 }
\box_set_eq:cN
20235 \cs_new_protected:Npn \box_gset_eq:NN
20236 { \tex_global:D \box_set_eq:NN }
\box_set_eq:Nc
20237 \cs_generate_variant:Nn \box_set_eq:NN { c , Nc , cc }
\box_set_eq:cc
20238 \cs_generate_variant:Nn \box_gset_eq:NN { c , Nc , cc }
\box_gset_eq:cN
\box_gset_eq:Nc
\box_gset_eq:cc
\box_set_eq_clear:NN
20239 \cs_new_protected:Npn \box_set_eq_clear:NN #1#2
20240 { \tex_setbox:D #1 \tex_box:D #2 }
\box_set_eq_clear:cN
20241 \cs_new_protected:Npn \box_gset_eq_clear:NN
20242 { \tex_global:D \box_set_eq_clear:NN }
\box_set_eq_clear:Nc
20243 \cs_generate_variant:Nn \box_set_eq_clear:NN { c , Nc , cc }
\box_set_eq_clear:cc
20244 \cs_generate_variant:Nn \box_gset_eq_clear:NN { c , Nc , cc }
\box_gset_eq_clear:cN
\box_gset_eq_clear:Nc
\box_gset_eq_clear:cc

```

Assigning the contents of a box to be another box. This clears the second box globally (that's how TeX does it).

Copies of the cs functions defined in l3basics.

```

20245 \prg_new_eq_conditional:NNn \box_if_exist:N \cs_if_exist:N
20246 { TF , T , F , p }
\box_if_exist_p:N
20247 \prg_new_eq_conditional:NNn \box_if_exist:c \cs_if_exist:c
\box_if_exist_p:c
20248 { TF , T , F , p }
\box_if_exist:N $\underline{TF}$ 
\box_if_exist:c $\underline{TF}$ 

```

## 37.2 Measuring and setting box dimensions

Accessing the height, depth, and width of a  $\langle box \rangle$  register.

```

20249 \cs_new_eq:NN \box_ht:N \tex_ht:D
\box_ht:N
20250 \cs_new_eq:NN \box_dp:N \tex_dp:D
\box_ht:c
20251 \cs_new_eq:NN \box_wd:N \tex_wd:D
\box_dp:N
20252 \cs_generate_variant:Nn \box_ht:N { c }
\box_dp:c
20253 \cs_generate_variant:Nn \box_dp:N { c }
\box_wd:N
20254 \cs_generate_variant:Nn \box_wd:N { c }
\box_wd:c

```

Measuring is easy: all primitive work. These primitives are not expandable, so the derived functions are not either.

```

20255 \cs_new_protected:Npn \box_set_dp:Nn #1#2
20256 { \box_dp:N #1 \__dim_eval:w #2 \__dim_eval_end: }
\box_set_dp:Nc
20257 \cs_new_protected:Npn \box_set_ht:Nn #1#2
20258 { \box_ht:N #1 \__dim_eval:w #2 \__dim_eval_end: }
\box_set_dp:cN
20259 \cs_new_protected:Npn \box_set_wd:Nn #1#2
20260 { \box_wd:N #1 \__dim_eval:w #2 \__dim_eval_end: }
\box_set_dp:Nc
20261 \cs_generate_variant:Nn \box_set_ht:Nn { c }
20262 \cs_generate_variant:Nn \box_set_dp:Nn { c }
20263 \cs_generate_variant:Nn \box_set_wd:Nn { c }

```

### 37.3 Using boxes

Using a  $\langle box \rangle$ . These are just  $\text{\TeX}$  primitives with meaningful names.

```

20264 \cs_new_eq:NN \box_use_clear:N \tex_box:D
\box_use_clear:N 20265 \cs_new_eq:NN \box_use:N \tex_copy:D
20266 \cs_generate_variant:Nn \box_use_clear:N { c }
\box_use:N 20267 \cs_generate_variant:Nn \box_use:N { c }
\box_use:c

```

Move box material in different directions.

```

20268 \cs_new_protected:Npn \box_move_left:nn #1#2
\box_move_left:nn 20269 { \tex_moveleft:D \__dim_eval:w #1 \__dim_eval_end: #2 }
\box_move_right:nn 20270 \cs_new_protected:Npn \box_move_right:nn #1#2
20271 { \tex_moveright:D \__dim_eval:w #1 \__dim_eval_end: #2 }
\box_move_up:nn 20272 \cs_new_protected:Npn \box_move_up:nn #1#2
20273 { \tex_raise:D \__dim_eval:w #1 \__dim_eval_end: #2 }
\box_move_down:nn 20274 \cs_new_protected:Npn \box_move_down:nn #1#2
20275 { \tex_lower:D \__dim_eval:w #1 \__dim_eval_end: #2 }

```

### 37.4 Box conditionals

The primitives for testing if a  $\langle box \rangle$  is empty/void or which type of box it is.

```

20276 \cs_new_eq:NN \if_hbox:N \tex_ifhbox:D
\if_hbox:N 20277 \cs_new_eq:NN \if_vbox:N \tex_ifvbox:D
\if_vbox:N 20278 \cs_new_eq:NN \if_box_empty:N \tex_ifvoid:D
\if_box_empty:N

20279 \prg_new_conditional:Npnn \box_if_horizontal:N #1 { p , T , F , TF }
\box_if_horizontal_p:N 20280 { \if_hbox:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
\box_if_horizontal_p:c 20281 \prg_new_conditional:Npnn \box_if_vertical:N #1 { p , T , F , TF }
\box_if_horizontal:N $\underline{TF}$  20282 { \if_vbox:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
\box_if_horizontal:c $\underline{TF}$  20283 \cs_generate_variant:Nn \box_if_horizontal_p:N { c }
\box_if_vertical_p:N 20284 \cs_generate_variant:Nn \box_if_horizontal:NT { c }
\box_if_vertical_p:c 20285 \cs_generate_variant:Nn \box_if_horizontal:NF { c }
\box_if_vertical:N $\underline{TF}$  20286 \cs_generate_variant:Nn \box_if_horizontal:NTF { c }
\box_if_vertical:c $\underline{TF}$  20287 \cs_generate_variant:Nn \box_if_vertical_p:N { c }
20288 \cs_generate_variant:Nn \box_if_vertical:NT { c }
20289 \cs_generate_variant:Nn \box_if_vertical:NF { c }
20290 \cs_generate_variant:Nn \box_if_vertical:NTF { c }

```

Testing if a  $\langle box \rangle$  is empty/void.

```

20291 \prg_new_conditional:Npnn \box_if_empty:N #1 { p , T , F , TF }
\box_if_empty_p:N 20292 { \if_box_empty:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
\box_if_empty_p:c 20293 \cs_generate_variant:Nn \box_if_empty_p:N { c }
\box_if_empty:N $\underline{TF}$  20294 \cs_generate_variant:Nn \box_if_empty:NT { c }
\box_if_empty:c $\underline{TF}$  20295 \cs_generate_variant:Nn \box_if_empty:NF { c }
20296 \cs_generate_variant:Nn \box_if_empty:NTF { c }

```

(End definition for  $\backslash\text{box\_new:N}$  and others. These functions are documented on page 211.)

## 37.5 The last box inserted

`\box_set_to_last:N` Set a box to the previous box.

```

\box_set_to_last:c 20297 \cs_new_protected:Npn \box_set_to_last:N #1
\box_gset_to_last:N 20298 { \tex_setbox:D #1 \tex_lastbox:D }
\box_gset_to_last:c 20299 \cs_new_protected:Npn \box_gset_to_last:N
20300 { \tex_global:D \box_set_to_last:N }
20301 \cs_generate_variant:Nn \box_set_to_last:N { c }
20302 \cs_generate_variant:Nn \box_gset_to_last:N { c }
```

(End definition for `\box_set_to_last:N` and `\box_gset_to_last:N`. These functions are documented on page 213.)

## 37.6 Constant boxes

`\c_empty_box` A box we never use.

```

20303 \box_new:N \c_empty_box
```

(End definition for `\c_empty_box`. This variable is documented on page 214.)

## 37.7 Scratch boxes

`\l_tmpa_box` Scratch boxes.

```

\l_tmpb_box 20304 \box_new:N \l_tmpa_box
\g_tmpa_box 20305 \box_new:N \l_tmpb_box
\g_tmpb_box 20306 \box_new:N \g_tmpa_box
20307 \box_new:N \g_tmpb_box
```

(End definition for `\l_tmpa_box` and others. These variables are documented on page 214.)

## 37.8 Viewing box contents

TeX's `\showbox` is not really that helpful in many cases, and it is also inconsistent with other L<sup>A</sup>T<sub>E</sub>X3 show functions as it does not actually shows material in the terminal. So we provide a richer set of functionality.

`\box_show:N` Essentially a wrapper around the internal function, but evaluating the breadth and depth arguments now outside the group.

```

\box_show:c
\box_show:Nnn 20308 \cs_new_protected:Npn \box_show:N #1
\box_show:cnn 20309 { \box_show:Nnn #1 \c_max_int \c_max_int }
20310 \cs_generate_variant:Nn \box_show:N { c }
20311 \cs_new_protected:Npn \box_show:Nnn #1#2#3
20312 { \__box_show:NNff 1 #1 { \int_eval:n {#2} } { \int_eval:n {#3} } }
20313 \cs_generate_variant:Nn \box_show:Nnn { c }
```

(End definition for `\box_show:N` and `\box_show:Nnn`. These functions are documented on page 214.)

`\box_log:N` Getting TeX to write to the log without interruption the run is done by altering the interaction mode. For that, the  $\varepsilon$ -TeX extensions are needed.

```

\box_log:c
\box_log:Nnn 20314 \cs_new_protected:Npn \box_log:N #1
\box_log:cnn 20315 { \box_log:Nnn #1 \c_max_int \c_max_int }
\__box_log:nNnn 20316 \cs_generate_variant:Nn \box_log:N { c }
20317 \cs_new_protected:Npn \box_log:Nnn
20318 { \exp_args:No \__box_log:nNnn { \tex_the:D \etex_interactionmode:D } }
```

```

20319 \cs_new_protected:Npn \__box_log:nNnn #1#2#3#4
20320 {
20321   \int_set:Nn \etex_interactionmode:D { 0 }
20322   \__box_show:NNff 0 #2 { \int_eval:n {#3} } { \int_eval:n {#4} }
20323   \int_set:Nn \etex_interactionmode:D {#1}
20324 }
20325 \cs_generate_variant:Nn \box_log:Nnn { c }

```

(End definition for `\box_log:N`, `\box_log:Nnn`, and `\__box_log:nNnn`. These functions are documented on page 214.)

`\__box_show:NNnn`  
`\__box_show:NNff`

The internal auxiliary to actually do the output uses a group to deal with breadth and depth values. The `\use:n` here gives better output appearance. Setting `\tracingonline` and `\errorcontextlines` is used to control what appears in the terminal.

```

20326 \cs_new_protected:Npn \__box_show:NNnn #1#2#3#4
20327 {
20328   \box_if_exist:NTF #2
20329   {
20330     \group_begin:
20331     \int_set:Nn \tex_showboxbreadth:D {#3}
20332     \int_set:Nn \tex_showboxdepth:D {#4}
20333     \int_set:Nn \tex_tracingonline:D {#1}
20334     \int_set:Nn \tex_errorcontextlines:D { -1 }
20335     \tex_showbox:D \use:n {#2}
20336   \group_end:
20337   }
20338   {
20339     \_msg_kernel_error:nxx { kernel } { variable-not-defined }
20340     { \token_to_str:N #2 }
20341   }
20342 }
20343 \cs_generate_variant:Nn \__box_show:NNnn { NNff }

```

(End definition for `\__box_show:NNnn`.)

## 37.9 Horizontal mode boxes

**`\hbox:n`** (The test suite for this command, and others in this file, is `m3box002.lvt`.)  
 Put a horizontal box directly into the input stream.

```

20344 \cs_new_protected:Npn \hbox:n #1
20345 { \tex_hbox:D \scan_stop: { \group_begin: #1 \group_end: } }

```

(End definition for `\hbox:n`. This function is documented on page 215.)

**`\hbox_set:Nn`**  
**`\hbox_set:cn`**  
**`\hbox_gset:Nn`**  
**`\hbox_gset:cn`**

```

20346 \cs_new_protected:Npn \hbox_set:Nn #1#2
20347 { \tex_setbox:D #1 \tex_hbox:D { \group_begin: #2 \group_end: } }
20348 \cs_new_protected:Npn \hbox_gset:Nn { \tex_global:D \hbox_set:Nn }
20349 \cs_generate_variant:Nn \hbox_set:Nn { c }
20350 \cs_generate_variant:Nn \hbox_gset:Nn { c }

```

(End definition for `\hbox_set:Nn` and `\hbox_gset:Nn`. These functions are documented on page 215.)

`\hbox_set_to_wd:Nnn` Storing material in a horizontal box with a specified width.

```

\hbox_set_to_wd:cnn 20351 \cs_new_protected:Npn \hbox_set_to_wd:Nnn #1#2#3
\hbox_gset_to_wd:Nnn 20352 {
\hbox_gset_to_wd:cnn 20353   \tex_setbox:D #1 \tex_hbox:D to \_dim_eval:w #2 \_dim_eval_end:
20354   { \group_begin: #3 \group_end: }
20355 }
20356 \cs_new_protected:Npn \hbox_gset_to_wd:Nnn
20357 { \tex_global:D \hbox_set_to_wd:Nnn }
20358 \cs_generate_variant:Nn \hbox_set_to_wd:Nnn { c }
20359 \cs_generate_variant:Nn \hbox_gset_to_wd:Nnn { c }

```

(End definition for `\hbox_set_to_wd:Nnn` and `\hbox_gset_to_wd:Nnn`. These functions are documented on page 215.)

`\hbox_set:Nw` Storing material in a horizontal box. This type is useful in environment definitions.

```

\hbox_set:cw 20360 \cs_new_protected:Npn \hbox_set:Nw #1
\hbox_gset:Nw 20361 {
\hbox_gset:cw 20362   \tex_setbox:D #1 \tex_hbox:D
\hbox_set_end: 20363   \c_group_begin_token
\hbox_gset_end: 20364   \group_begin:
20365 }
20366 \cs_new_protected:Npn \hbox_gset:Nw
20367 { \tex_global:D \hbox_set:Nw }
20368 \cs_generate_variant:Nn \hbox_set:Nw { c }
20369 \cs_generate_variant:Nn \hbox_gset:Nw { c }
20370 \cs_new_protected:Npn \hbox_set_end:
20371 {
20372   \group_end:
20373   \c_group_end_token
20374 }
20375 \cs_new_eq:NN \hbox_gset_end: \hbox_set_end:

```

(End definition for `\hbox_set:Nw` and others. These functions are documented on page 215.)

`\hbox_set_to_wd:Nnw` Combining the above ideas.

```

\hbox_set_to_wd:cnw 20376 \cs_new_protected:Npn \hbox_set_to_wd:Nnw #1#2
\hbox_gset_to_wd:Nnw 20377 {
\hbox_gset_to_wd:cnw 20378   \tex_setbox:D #1 \tex_hbox:D to \_dim_eval:w #2 \_dim_eval_end:
20379   \c_group_begin_token
20380   \group_begin:
20381 }
20382 \cs_new_protected:Npn \hbox_gset_to_wd:Nnw
20383 { \tex_global:D \hbox_set_to_wd:Nnw }
20384 \cs_generate_variant:Nn \hbox_set_to_wd:Nnw { c }
20385 \cs_generate_variant:Nn \hbox_gset_to_wd:Nnw { c }

```

(End definition for `\hbox_set_to_wd:Nnw` and `\hbox_gset_to_wd:Nnw`. These functions are documented on page 216.)

`\hbox_to_wd:nn` Put a horizontal box directly into the input stream.

```

\hbox_to_zero:n 20386 \cs_new_protected:Npn \hbox_to_wd:nn #1#2
20387 {
20388   \tex_hbox:D to \_dim_eval:w #1 \_dim_eval_end:
20389   { \group_begin: #2 \group_end: }
20390 }

```

```

20391 \cs_new_protected:Npn \hbox_to_zero:n #1
20392 { \tex_hbox:D to \c_zero_dim { \group_begin: #1 \group_end: } }

```

(End definition for `\hbox_to_wd:nn` and `\hbox_to_zero:n`. These functions are documented on page 215.)

`\hbox_overlap_left:n` Put a zero-sized box with the contents pushed against one side (which makes it stick out on the other) directly into the input stream.

```

20393 \cs_new_protected:Npn \hbox_overlap_left:n #1
20394 { \hbox_to_zero:n { \tex_hss:D #1 } }
20395 \cs_new_protected:Npn \hbox_overlap_right:n #1
20396 { \hbox_to_zero:n { #1 \tex_hss:D } }

```

(End definition for `\hbox_overlap_left:n` and `\hbox_overlap_right:n`. These functions are documented on page 215.)

`\hbox_unpack:N` Unpacking a box and if requested also clear it.

```

\hbox_unpack:c
\hbox_unpack_clear:N
\hbox_unpack_clear:c
20397 \cs_new_eq:NN \hbox_unpack:N \tex_unhcopy:D
20398 \cs_new_eq:NN \hbox_unpack_clear:N \tex_unhbox:D
20399 \cs_generate_variant:Nn \hbox_unpack:N { c }
20400 \cs_generate_variant:Nn \hbox_unpack_clear:N { c }

```

(End definition for `\hbox_unpack:N` and `\hbox_unpack_clear:N`. These functions are documented on page 216.)

## 37.10 Vertical mode boxes

TeX ends these boxes directly with the internal `end_graf` routine. This means that there is no `\par` at the end of vertical boxes unless we insert one.

`\vbox:n` The following test files are used for this code: `m3box003.lvt`.

The following test files are used for this code: `m3box003.lvt`.

`\vbox_top:n` Put a vertical box directly into the input stream.

```

20401 \cs_new_protected:Npn \vbox:n #1
20402 { \tex_vbox:D { \group_begin: #1 \par \group_end: } }
20403 \cs_new_protected:Npn \vbox_top:n #1
20404 { \tex_vtop:D { \group_begin: #1 \par \group_end: } }

```

(End definition for `\vbox:n` and `\vbox_top:n`. These functions are documented on page 216.)

`\vbox_to_ht:nn` Put a vertical box directly into the input stream.

```

\vbox_to_zero:n
\vbox_to_ht:nn
\vbox_to_zero:n
20405 \cs_new_protected:Npn \vbox_to_ht:nn #1#2
20406 {
20407   \tex_vbox:D to \__dim_eval:w #1 \__dim_eval_end:
20408   { \group_begin: #2 \par \group_end: }
20409 }
20410 \cs_new_protected:Npn \vbox_to_zero:n #1
20411 {
20412   \tex_vbox:D to \c_zero_dim
20413   { \group_begin: #1 \par \group_end: }
20414 }

```

(End definition for `\vbox_to_ht:nn` and others. These functions are documented on page 216.)



**\vbox\_set:Nn** Storing material in a vertical box with a natural height.

```

\vbox_set:cn      20415 \cs_new_protected:Npn \vbox_set:Nn #1#2
\vbox_gset:Nn     20416 {
\vbox_gset:cn     20417   \tex_setbox:D #1 \tex_vbox:D
                  20418   { \group_begin: #2 \par \group_end: }
                  20419 }
                  20420 \cs_new_protected:Npn \vbox_gset:Nn { \tex_global:D \vbox_set:Nn }
                  20421 \cs_generate_variant:Nn \vbox_set:Nn { c }
                  20422 \cs_generate_variant:Nn \vbox_gset:Nn { c }

```

(End definition for \vbox\_set:Nn and \vbox\_gset:Nn. These functions are documented on page 217.)

**\vbox\_set\_top:Nn** Storing material in a vertical box with a natural height and reference point at the baseline of the first object in the box.

```

\vbox_set_top:cn  20423 \cs_new_protected:Npn \vbox_set_top:Nn #1#2
\vbox_gset_top:cn  20424 {
                  20425   \tex_setbox:D #1 \tex_vtop:D
                  20426   { \group_begin: #2 \par \group_end: }
                  20427 }
                  20428 \cs_new_protected:Npn \vbox_gset_top:Nn
                  20429 { \tex_global:D \vbox_set_top:Nn }
                  20430 \cs_generate_variant:Nn \vbox_set_top:Nn { c }
                  20431 \cs_generate_variant:Nn \vbox_gset_top:Nn { c }

```

(End definition for \vbox\_set\_top:Nn and \vbox\_gset\_top:Nn. These functions are documented on page 217.)

**\vbox\_set\_to\_ht:Nnn** Storing material in a vertical box with a specified height.

```

\vbox_set_to_ht:cnn 20432 \cs_new_protected:Npn \vbox_set_to_ht:Nnn #1#2#3
\vbox_gset_to_ht:Nnn 20433 {
\vbox_gset_to_ht:cnn 20434   \tex_setbox:D #1 \tex_vbox:D to \_dim_eval:w #2 \_dim_eval_end:
                  20435   { \group_begin: #3 \par \group_end: }
                  20436 }
                  20437 \cs_new_protected:Npn \vbox_gset_to_ht:Nnn
                  20438 { \tex_global:D \vbox_set_to_ht:Nnn }
                  20439 \cs_generate_variant:Nn \vbox_set_to_ht:Nnn { c }
                  20440 \cs_generate_variant:Nn \vbox_gset_to_ht:Nnn { c }

```

(End definition for \vbox\_set\_to\_ht:Nnn and \vbox\_gset\_to\_ht:Nnn. These functions are documented on page 217.)

**\vbox\_set:Nw** Storing material in a vertical box. This type is useful in environment definitions.

```

\vbox_set:cw      20441 \cs_new_protected:Npn \vbox_set:Nw #1
\vbox_gset:Nw     20442 {
\vbox_gset:cw     20443   \tex_setbox:D #1 \tex_vbox:D
\vbox_set_end:    20444   \c_group_begin_token
\vbox_gset_end:   20445   \group_begin:
                  20446 }
                  20447 \cs_new_protected:Npn \vbox_gset:Nw
                  20448 { \tex_global:D \vbox_set:Nw }
                  20449 \cs_generate_variant:Nn \vbox_set:Nw { c }
                  20450 \cs_generate_variant:Nn \vbox_gset:Nw { c }
                  20451 \cs_new_protected:Npn \vbox_set_end:
                  20452 {
                  20453   \par

```

```

20454     \group_end:
20455     \c_group_end_token
20456   }
20457   \cs_new_eq:NN \vbox_gset_end: \vbox_set_end:

```

(End definition for `\vbox_set:Nw` and others. These functions are documented on page 217.)

```

\ vbox_set_to_ht:Nnw A combination of the above ideas.
\ vbox_set_to_ht:cnw 20458 \cs_new_protected:Npn \vbox_set_to_ht:Nnw #1#2
\ vbox_gset_to_ht:Nnw 20459 {
\ vbox_gset_to_ht:cnw 20460   \tex_setbox:D #1 \tex_vbox:D to \_dim_eval:w #2 \_dim_eval_end:
20461   \c_group_begin_token
20462   \group_begin:
20463 }
20464 \cs_new_protected:Npn \vbox_gset_to_ht:Nnw
20465 { \tex_global:D \vbox_set_to_ht:Nnw }
20466 \cs_generate_variant:Nn \vbox_set_to_ht:Nnw { c }
20467 \cs_generate_variant:Nn \vbox_gset_to_ht:Nnw { c }

```

(End definition for `\vbox_set_to_ht:Nnw` and `\vbox_gset_to_ht:Nnw`. These functions are documented on page 217.)

```

\ vbox_unpack:N Unpacking a box and if requested also clear it.
\ vbox_unpack:c 20468 \cs_new_eq:NN \vbox_unpack:N \tex_unvcopy:D
\ vbox_unpack_clear:N 20469 \cs_new_eq:NN \vbox_unpack_clear:N \tex_unvbox:D
\ vbox_unpack_clear:c 20470 \cs_generate_variant:Nn \vbox_unpack:N { c }
20471 \cs_generate_variant:Nn \vbox_unpack_clear:N { c }

```

(End definition for `\vbox_unpack:N` and `\vbox_unpack_clear:N`. These functions are documented on page 217.)

```

\ vbox_set_split_to_ht:NNn Splitting a vertical box in two.
20472 \cs_new_protected:Npn \vbox_set_split_to_ht:NNn #1#2#3
20473 { \tex_setbox:D #1 \tex_vsplit:D #2 to \_dim_eval:w #3 \_dim_eval_end: }

```

(End definition for `\vbox_set_split_to_ht:NNn`. This function is documented on page 217.)

### 37.11 Affine transformations

`\l__box_angle_fp` When rotating boxes, the angle itself may be needed by the engine-dependent code. This is done using the `fp` module so that the value is tidied up properly.

```

20474 \fp_new:N \l__box_angle_fp

```

(End definition for `\l__box_angle_fp`.)

`\l__box_cos_fp` `\l__box_sin_fp` These are used to hold the calculated sine and cosine values while carrying out a rotation.

```

20475 \fp_new:N \l__box_cos_fp
20476 \fp_new:N \l__box_sin_fp

```

(End definition for `\l__box_cos_fp` and `\l__box_sin_fp`.)

`\l__box_top_dim` `\l__box_bottom_dim` `\l__box_left_dim` `\l__box_right_dim` These are the positions of the four edges of a box before manipulation.

```

20477 \dim_new:N \l__box_top_dim
20478 \dim_new:N \l__box_bottom_dim
20479 \dim_new:N \l__box_left_dim
20480 \dim_new:N \l__box_right_dim

```




Figure 1: Co-ordinates of a box prior to rotation.

(End definition for `\l__box_top_dim` and others.)

```
\l__box_top_new_dim These are the positions of the four edges of a box after manipulation.
\l__box_bottom_new_dim 20481 \dim_new:N \l__box_top_new_dim
\l__box_left_new_dim 20482 \dim_new:N \l__box_bottom_new_dim
\l__box_right_new_dim 20483 \dim_new:N \l__box_left_new_dim
20484 \dim_new:N \l__box_right_new_dim
```

(End definition for `\l__box_top_new_dim` and others.)

```
\l__box_internal_box Scratch space, but also needed by some parts of the driver.
```

```
20485 \box_new:N \l__box_internal_box
```

(End definition for `\l__box_internal_box`.)

**\box\_rotate:Nn** Rotation of a box starts with working out the relevant sine and cosine. The actual

`\__box_rotate:N` rotation is in an auxiliary to keep the flow slightly clearer

```
\__box_rotate_x:nnN 20486 \cs_new_protected:Npn \box_rotate:Nn #1#2
\__box_rotate_y:nnN 20487 {
\__box_rotate_quadrant_one: 20488 \hbox_set:Nn #1
\__box_rotate_quadrant_two: 20489 {
\__box_rotate_quadrant_three: 20490 \fp_set:Nn \l__box_angle_fp {#2}
\__box_rotate_quadrant_four: 20491 \fp_set:Nn \l__box_sin_fp { sind ( \l__box_angle_fp ) }
20492 \fp_set:Nn \l__box_cos_fp { cosd ( \l__box_angle_fp ) }
20493 \__box_rotate:N #1
20494 }
20495 }
```

The edges of the box are then recorded: the left edge is always at zero. Rotation of the four edges then takes place: this is most efficiently done on a quadrant by quadrant basis.

```
20496 \cs_new_protected:Npn \__box_rotate:N #1
20497 {
20498 \dim_set:Nn \l__box_top_dim { \box_ht:N #1 }
20499 \dim_set:Nn \l__box_bottom_dim { -\box_dp:N #1 }
20500 \dim_set:Nn \l__box_right_dim { \box_wd:N #1 }
20501 \dim_zero:N \l__box_left_dim
```

The next step is to work out the  $x$  and  $y$  coordinates of vertices of the rotated box in relation to its original coordinates. The box can be visualized with vertices  $B$ ,  $C$ ,  $D$  and  $E$  is illustrated (Figure 1). The vertex  $O$  is the reference point on the baseline, and in this implementation is also the centre of rotation. The formulae are, for a point  $P$  and

angle  $\alpha$ :

$$\begin{aligned} P'_x &= P_x - O_x \\ P'_y &= P_y - O_y \\ P''_x &= (P'_x \cos(\alpha)) - (P'_y \sin(\alpha)) \\ P''_y &= (P'_x \sin(\alpha)) + (P'_y \cos(\alpha)) \\ P'''_x &= P''_x + O_x + L_x \\ P'''_y &= P''_y + O_y \end{aligned}$$

The “extra” horizontal translation  $L_x$  at the end is calculated so that the leftmost point of the resulting box has  $x$ -coordinate 0. This is desirable as T<sub>E</sub>X boxes must have the reference point at the left edge of the box. (As  $O$  is always  $(0,0)$ , this part of the calculation is omitted here.)

```

20502     \fp_compare:nNnTF \l__box_sin_fp > \c_zero_fp
20503     {
20504         \fp_compare:nNnTF \l__box_cos_fp > \c_zero_fp
20505         { \__box_rotate_quadrant_one: }
20506         { \__box_rotate_quadrant_two: }
20507     }
20508     {
20509         \fp_compare:nNnTF \l__box_cos_fp < \c_zero_fp
20510         { \__box_rotate_quadrant_three: }
20511         { \__box_rotate_quadrant_four: }
20512     }

```

The position of the box edges are now known, but the box at this stage be misplaced relative to the current T<sub>E</sub>X reference point. So the content of the box is moved such that the reference point of the rotated box is in the same place as the original.

```

20513     \hbox_set:Nn \l__box_internal_box { \box_use:N #1 }
20514     \hbox_set:Nn \l__box_internal_box
20515     {
20516         \tex_kern:D -\l__box_left_new_dim
20517         \hbox:n
20518         {
20519             \__driver_box_use_rotate:Nn
20520             \l__box_internal_box
20521             \l__box_angle_fp
20522         }
20523     }

```

Tidy up the size of the box so that the material is actually inside the bounding box. The result can then be used to reset the original box.

```

20524     \box_set_ht:Nn \l__box_internal_box { \l__box_top_new_dim }
20525     \box_set_dp:Nn \l__box_internal_box { -\l__box_bottom_new_dim }
20526     \box_set_wd:Nn \l__box_internal_box
20527     { \l__box_right_new_dim - \l__box_left_new_dim }
20528     \box_use:N \l__box_internal_box
20529 }

```

These functions take a general point ( $\#1, \#2$ ) and rotate its location about the origin, using the previously-set sine and cosine values. Each function gives only one component of the location of the updated point. This is because for rotation of a box each step needs only one value, and so performance is gained by avoiding working out both  $x'$  and  $y'$  at the same time. Contrast this with the equivalent function in the `l3coffins` module, where both parts are needed.

```

20530 \cs_new_protected:Npn \__box_rotate_x:nnN #1#2#3
20531 {
20532   \dim_set:Nn #3
20533   {
20534     \fp_to_dim:n
20535     {
20536       \l__box_cos_fp * \dim_to_fp:n {#1}
20537       - \l__box_sin_fp * \dim_to_fp:n {#2}
20538     }
20539   }
20540 }
20541 \cs_new_protected:Npn \__box_rotate_y:nnN #1#2#3
20542 {
20543   \dim_set:Nn #3
20544   {
20545     \fp_to_dim:n
20546     {
20547       \l__box_sin_fp * \dim_to_fp:n {#1}
20548       + \l__box_cos_fp * \dim_to_fp:n {#2}
20549     }
20550   }
20551 }

```

Rotation of the edges is done using a different formula for each quadrant. In every case, the top and bottom edges only need the resulting  $y$ -values, whereas the left and right edges need the  $x$ -values. Each case is a question of picking out which corner ends up at with the maximum top, bottom, left and right value. Doing this by hand means a lot less calculating and avoids lots of comparisons.

```

20552 \cs_new_protected:Npn \__box_rotate_quadrant_one:
20553 {
20554   \__box_rotate_y:nnN \l__box_right_dim \l__box_top_dim
20555   \l__box_top_new_dim
20556   \__box_rotate_y:nnN \l__box_left_dim \l__box_bottom_dim
20557   \l__box_bottom_new_dim
20558   \__box_rotate_x:nnN \l__box_left_dim \l__box_top_dim
20559   \l__box_left_new_dim
20560   \__box_rotate_x:nnN \l__box_right_dim \l__box_bottom_dim
20561   \l__box_right_new_dim
20562 }
20563 \cs_new_protected:Npn \__box_rotate_quadrant_two:
20564 {
20565   \__box_rotate_y:nnN \l__box_right_dim \l__box_bottom_dim
20566   \l__box_top_new_dim
20567   \__box_rotate_y:nnN \l__box_left_dim \l__box_top_dim
20568   \l__box_bottom_new_dim
20569   \__box_rotate_x:nnN \l__box_right_dim \l__box_top_dim
20570   \l__box_left_new_dim
20571   \__box_rotate_x:nnN \l__box_left_dim \l__box_bottom_dim
20572   \l__box_right_new_dim
20573 }
20574 \cs_new_protected:Npn \__box_rotate_quadrant_three:
20575 {
20576   \__box_rotate_y:nnN \l__box_left_dim \l__box_bottom_dim
20577   \l__box_top_new_dim

```

```

20578 \__box_rotate_y:nnN \l__box_right_dim \l__box_top_dim
20579 \l__box_bottom_new_dim
20580 \__box_rotate_x:nnN \l__box_right_dim \l__box_bottom_dim
20581 \l__box_left_new_dim
20582 \__box_rotate_x:nnN \l__box_left_dim \l__box_top_dim
20583 \l__box_right_new_dim
20584 }
20585 \cs_new_protected:Npn \__box_rotate_quadrant_four:
20586 {
20587 \__box_rotate_y:nnN \l__box_left_dim \l__box_top_dim
20588 \l__box_top_new_dim
20589 \__box_rotate_y:nnN \l__box_right_dim \l__box_bottom_dim
20590 \l__box_bottom_new_dim
20591 \__box_rotate_x:nnN \l__box_left_dim \l__box_bottom_dim
20592 \l__box_left_new_dim
20593 \__box_rotate_x:nnN \l__box_right_dim \l__box_top_dim
20594 \l__box_right_new_dim
20595 }

```

(End definition for `\box_rotate:Nn` and others. These functions are documented on page 219.)

`\l__box_scale_x_fp` Scaling is potentially-different in the two axes.

```

\l__box_scale_y_fp 20596 \fp_new:N \l__box_scale_x_fp
20597 \fp_new:N \l__box_scale_y_fp

```

(End definition for `\l__box_scale_x_fp` and `\l__box_scale_y_fp`.)

`\box_resize_to_wd_and_ht_plus_dp:Nnn` Resizing a box starts by working out the various dimensions of the existing box.

```

\box_resize_to_wd_and_ht_plus_dp:cmn 20598 \cs_new_protected:Npn \box_resize_to_wd_and_ht_plus_dp:Nnn #1#2#3
\__box_resize_set_corners:N 20599 {
\__box_resize:N 20600 \hbox_set:Nn #1
\__box_resize:NNN 20601 {
20602 \__box_resize_set_corners:N #1

```

The  $x$ -scaling and resulting box size is easy enough to work out: the dimension is that given as #2, and the scale is simply the new width divided by the old one.

```

20603 \fp_set:Nn \l__box_scale_x_fp
20604 { \dim_to_fp:n {#2} / \dim_to_fp:n { \l__box_right_dim } }

```

The  $y$ -scaling needs both the height and the depth of the current box.

```

20605 \fp_set:Nn \l__box_scale_y_fp
20606 {
20607 \dim_to_fp:n {#3}
20608 / \dim_to_fp:n { \l__box_top_dim - \l__box_bottom_dim }
20609 }

```

Hand off to the auxiliary which does the rest of the work.

```

20610 \__box_resize:N #1
20611 }
20612 }
20613 \cs_generate_variant:Nn \box_resize_to_wd_and_ht_plus_dp:Nnn { c }
20614 \cs_new_protected:Npn \__box_resize_set_corners:N #1
20615 {
20616 \dim_set:Nn \l__box_top_dim { \box_ht:N #1 }
20617 \dim_set:Nn \l__box_bottom_dim { -\box_dp:N #1 }
20618 \dim_set:Nn \l__box_right_dim { \box_wd:N #1 }

```

```

20619 \dim_zero:N \l__box_left_dim
20620 }

```

With at least one real scaling to do, the next phase is to find the new edge co-ordinates. In the  $x$  direction this is relatively easy: just scale the right edge. In the  $y$  direction, both dimensions have to be scaled, and this again needs the absolute scale value. Once that is all done, the common resize/rescale code can be employed.

```

20621 \cs_new_protected:Npn \__box_resize:N #1
20622 {
20623   \__box_resize:NNN \l__box_right_new_dim
20624   \l__box_scale_x_fp \l__box_right_dim
20625   \__box_resize:NNN \l__box_bottom_new_dim
20626   \l__box_scale_y_fp \l__box_bottom_dim
20627   \__box_resize:NNN \l__box_top_new_dim
20628   \l__box_scale_y_fp \l__box_top_dim
20629   \__box_resize_common:N #1
20630 }
20631 \cs_new_protected:Npn \__box_resize:NNN #1#2#3
20632 {
20633   \dim_set:Nn #1
20634     { \fp_to_dim:n { \fp_abs:n { #2 } * \dim_to_fp:n { #3 } } }
20635 }

```

(End definition for `\box_resize_to_wd_and_ht_plus_dp:Nnn` and others. These functions are documented on page 219.)

```

\box_resize_to_ht:Nn Scaling to a (total) height or to a width is a simplified version of the main resizing
\box_resize_to_ht:cn operation, with the scale simply copied between the two parts. The internal auxiliary is
\box_resize_to_ht_plus_dp:Nn called using the scaling value twice, as the sign for both parts is needed (as this allows
\box_resize_to_ht_plus_dp:cn the same internal code to be used as for the general case).
\box_resize_to_wd:Nn
\box_resize_to_wd:cn
\box_resize_to_wd_and_ht:Nnn
\box_resize_to_wd_and_ht:cnn
20636 \cs_new_protected:Npn \box_resize_to_ht:Nn #1#2
20637 {
20638   \hbox_set:Nn #1
20639   {
20640     \__box_resize_set_corners:N #1
20641     \fp_set:Nn \l__box_scale_y_fp
20642       {
20643         \dim_to_fp:n {#2}
20644         / \dim_to_fp:n { \l__box_top_dim }
20645       }
20646     \fp_set_eq:NN \l__box_scale_x_fp \l__box_scale_y_fp
20647     \__box_resize:N #1
20648   }
20649 }
20650 \cs_generate_variant:Nn \box_resize_to_ht:Nn { c }
20651 \cs_new_protected:Npn \box_resize_to_ht_plus_dp:Nn #1#2
20652 {
20653   \hbox_set:Nn #1
20654   {
20655     \__box_resize_set_corners:N #1
20656     \fp_set:Nn \l__box_scale_y_fp
20657     {
20658       \dim_to_fp:n {#2}
20659       / \dim_to_fp:n { \l__box_top_dim - \l__box_bottom_dim }

```

```

20660     }
20661     \fp_set_eq:NN \l__box_scale_x_fp \l__box_scale_y_fp
20662     \__box_resize:N #1
20663   }
20664 }
20665 \cs_generate_variant:Nn \box_resize_to_ht_plus_dp:Nn { c }
20666 \cs_new_protected:Npn \box_resize_to_wd:Nn #1#2
20667 {
20668   \hbox_set:Nn #1
20669   {
20670     \__box_resize_set_corners:N #1
20671     \fp_set:Nn \l__box_scale_x_fp
20672     { \dim_to_fp:n {#2} / \dim_to_fp:n { \l__box_right_dim } }
20673     \fp_set_eq:NN \l__box_scale_y_fp \l__box_scale_x_fp
20674     \__box_resize:N #1
20675   }
20676 }
20677 \cs_generate_variant:Nn \box_resize_to_wd:Nn { c }
20678 \cs_new_protected:Npn \box_resize_to_wd_and_ht:Nnn #1#2#3
20679 {
20680   \hbox_set:Nn #1
20681   {
20682     \__box_resize_set_corners:N #1
20683     \fp_set:Nn \l__box_scale_x_fp
20684     { \dim_to_fp:n {#2} / \dim_to_fp:n { \l__box_right_dim } }
20685     \fp_set:Nn \l__box_scale_y_fp
20686     {
20687       \dim_to_fp:n {#3}
20688       / \dim_to_fp:n { \l__box_top_dim }
20689     }
20690     \__box_resize:N #1
20691   }
20692 }
20693 \cs_generate_variant:Nn \box_resize_to_wd_and_ht:Nnn { c }

```

(End definition for `\box_resize_to_ht:Nn` and others. These functions are documented on page 218.)

**`\box_scale:Nnn`** When scaling a box, setting the scaling itself is easy enough. The new dimensions are also relatively easy to find, allowing only for the need to keep them positive in all cases.

**`\box_scale:cnn`** Once that is done then after a check for the trivial scaling a hand-off can be made to the common code. The code here is split into two as this allows sharing with the auto-resizing functions.

**`\__box_scale_aux:N`**

```

20694 \cs_new_protected:Npn \box_scale:Nnn #1#2#3
20695 {
20696   \hbox_set:Nn #1
20697   {
20698     \fp_set:Nn \l__box_scale_x_fp {#2}
20699     \fp_set:Nn \l__box_scale_y_fp {#3}
20700     \__box_scale_aux:N #1
20701   }
20702 }
20703 \cs_generate_variant:Nn \box_scale:Nnn { c }
20704 \cs_new_protected:Npn \__box_scale_aux:N #1
20705 {

```



```

20706 \dim_set:Nn \l__box_top_dim { \box_ht:N #1 }
20707 \dim_set:Nn \l__box_bottom_dim { -\box_dp:N #1 }
20708 \dim_set:Nn \l__box_right_dim { \box_wd:N #1 }
20709 \dim_zero:N \l__box_left_dim
20710 \dim_set:Nn \l__box_top_new_dim
20711 { \fp_abs:n { \l__box_scale_y_fp } \l__box_top_dim }
20712 \dim_set:Nn \l__box_bottom_new_dim
20713 { \fp_abs:n { \l__box_scale_y_fp } \l__box_bottom_dim }
20714 \dim_set:Nn \l__box_right_new_dim
20715 { \fp_abs:n { \l__box_scale_x_fp } \l__box_right_dim }
20716 \__box_resize_common:N #1
20717 }

```

(End definition for `\box_scale:Nnn` and `\__box_scale_aux:N`. These functions are documented on page 220.)

`\box_autosize_to_wd_and_ht:Nnn` Although autosizing a box uses dimensions, it has more in common in implementation with scaling. As such, most of the real work here is done elsewhere.

```

\box_autosize_to_wd_and_ht:cnn
\box_autosize_to_wd_and_ht_plus_dp:cnn
\box_autosize_to_wd_and_ht_plus_dp:Nnn
\__box_autosize:Nnnn
20718 \cs_new_protected:Npn \box_autosize_to_wd_and_ht:Nnn #1#2#3
20719 { \__box_autosize:Nnnn #1 {#2} {#3} { \box_ht:N #1 } }
20720 \cs_generate_variant:Nn \box_autosize_to_wd_and_ht:Nnn { c }
20721 \cs_new_protected:Npn \box_autosize_to_wd_and_ht_plus_dp:Nnn #1#2#3
20722 { \__box_autosize:Nnnn #1 {#2} {#3} { \box_ht:N #1 + \box_dp:N #1 } }
20723 \cs_generate_variant:Nn \box_autosize_to_wd_and_ht_plus_dp:Nnn { c }
20724 \cs_new_protected:Npn \__box_autosize:Nnnn #1#2#3#4
20725 {
20726   \hbox_set:Nn #1
20727   {
20728     \fp_set:Nn \l__box_scale_x_fp { ( #2 ) / \box_wd:N #1 }
20729     \fp_set:Nn \l__box_scale_y_fp { ( #3 ) / ( #4 ) }
20730     \fp_compare:nNnTF \l__box_scale_x_fp > \l__box_scale_y_fp
20731       { \fp_set_eq:NN \l__box_scale_x_fp \l__box_scale_y_fp }
20732       { \fp_set_eq:NN \l__box_scale_y_fp \l__box_scale_x_fp }
20733     \__box_scale_aux:N #1
20734   }
20735 }

```

(End definition for `\box_autosize_to_wd_and_ht:Nnn`, `\box_autosize_to_wd_and_ht_plus_dp:cnn`, and `\__box_autosize:Nnnn`. These functions are documented on page 218.)

`\__box_resize_common:N` The main resize function places its input into a box which start off with zero width, and includes the handles for engine rescaling.

```

20736 \cs_new_protected:Npn \__box_resize_common:N #1
20737 {
20738   \hbox_set:Nn \l__box_internal_box
20739   {
20740     \__driver_box_use_scale:Nnn
20741     #1
20742     \l__box_scale_x_fp
20743     \l__box_scale_y_fp
20744   }

```

The new height and depth can be applied directly.

```

20745 \fp_compare:nNnTF \l__box_scale_y_fp > \c_zero_fp
20746 {

```

```

20747     \box_set_ht:Nn \l__box_internal_box { \l__box_top_new_dim }
20748     \box_set_dp:Nn \l__box_internal_box { -\l__box_bottom_new_dim }
20749   }
20750   {
20751     \box_set_dp:Nn \l__box_internal_box { \l__box_top_new_dim }
20752     \box_set_ht:Nn \l__box_internal_box { -\l__box_bottom_new_dim }
20753   }

```

Things are not quite as obvious for the width, as the reference point needs to remain unchanged. For positive scaling factors resizing the box is all that is needed. However, for case of a negative scaling the material must be shifted such that the reference point ends up in the right place.

```

20754   \fp_compare:nNnTF \l__box_scale_x_fp < \c_zero_fp
20755   {
20756     \hbox_to_wd:nn { \l__box_right_new_dim }
20757     {
20758       \tex_kern:D \l__box_right_new_dim
20759       \box_use:N \l__box_internal_box
20760       \tex_hss:D
20761     }
20762   }
20763   {
20764     \box_set_wd:Nn \l__box_internal_box { \l__box_right_new_dim }
20765     \hbox:n
20766     {
20767       \tex_kern:D \c_zero_dim
20768       \box_use:N \l__box_internal_box
20769       \tex_hss:D
20770     }
20771   }
20772 }

```

(End definition for `\__box_resize_common:N`.)

## 37.12 Deprecated functions

```

\box_resize:Nnn
\box_resize:cnn
20773 \cs_new_eq:NN \box_resize:Nnn \box_resize_to_wd_and_ht_plus_dp:Nnn
20774 \cs_new_eq:NN \box_resize:cnn \box_resize_to_wd_and_ht_plus_dp:cnn

```

(End definition for `\box_resize:Nnn`.)

```

20775 </initex | package>

```

## 38 l3coffins Implementation

```

20776 <*initex | package>
20777 <@@=coffin>

```

### 38.1 Coffins: data structures and general variables

```

\l__coffin_internal_box Scratch variables.
\l__coffin_internal_dim
\l__coffin_internal_tl
20778 \box_new:N \l__coffin_internal_box
20779 \dim_new:N \l__coffin_internal_dim
20780 \tl_new:N \l__coffin_internal_tl

```

(End definition for `\l__coffin_internal_box`, `\l__coffin_internal_dim`, and `\l__coffin_internal_tl`.)

`\c__coffin_corners_prop` The “corners”; of a coffin define the real content, as opposed to the  $\TeX$  bounding box. They all start off in the same place, of course.

```
20781 \prop_new:N \c__coffin_corners_prop
20782 \prop_put:Nnn \c__coffin_corners_prop { tl } { { Opt } { Opt } }
20783 \prop_put:Nnn \c__coffin_corners_prop { tr } { { Opt } { Opt } }
20784 \prop_put:Nnn \c__coffin_corners_prop { bl } { { Opt } { Opt } }
20785 \prop_put:Nnn \c__coffin_corners_prop { br } { { Opt } { Opt } }
```

(End definition for `\c__coffin_corners_prop`.)

`\c__coffin_poles_prop` Pole positions are given for horizontal, vertical and reference-point based values.

```
20786 \prop_new:N \c__coffin_poles_prop
20787 \tl_set:Nn \l__coffin_internal_tl { { Opt } { Opt } { Opt } { 1000pt } }
20788 \prop_put:Nno \c__coffin_poles_prop { l } { \l__coffin_internal_tl }
20789 \prop_put:Nno \c__coffin_poles_prop { hc } { \l__coffin_internal_tl }
20790 \prop_put:Nno \c__coffin_poles_prop { r } { \l__coffin_internal_tl }
20791 \tl_set:Nn \l__coffin_internal_tl { { Opt } { Opt } { 1000pt } { Opt } }
20792 \prop_put:Nno \c__coffin_poles_prop { b } { \l__coffin_internal_tl }
20793 \prop_put:Nno \c__coffin_poles_prop { vc } { \l__coffin_internal_tl }
20794 \prop_put:Nno \c__coffin_poles_prop { t } { \l__coffin_internal_tl }
20795 \prop_put:Nno \c__coffin_poles_prop { B } { \l__coffin_internal_tl }
20796 \prop_put:Nno \c__coffin_poles_prop { H } { \l__coffin_internal_tl }
20797 \prop_put:Nno \c__coffin_poles_prop { T } { \l__coffin_internal_tl }
```

(End definition for `\c__coffin_poles_prop`.)

`\l__coffin_slope_x_fp` Used for calculations of intersections.

```
20798 \fp_new:N \l__coffin_slope_x_fp
20799 \fp_new:N \l__coffin_slope_y_fp
```

(End definition for `\l__coffin_slope_x_fp` and `\l__coffin_slope_y_fp`.)

`\l__coffin_error_bool` For propagating errors so that parts of the code can work around them.

```
20800 \bool_new:N \l__coffin_error_bool
```

(End definition for `\l__coffin_error_bool`.)

`\l__coffin_offset_x_dim` The offset between two sets of coffin handles when typesetting. These values are corrected from those requested in an alignment for the positions of the handles.

`\l__coffin_offset_y_dim`

```
20801 \dim_new:N \l__coffin_offset_x_dim
20802 \dim_new:N \l__coffin_offset_y_dim
```

(End definition for `\l__coffin_offset_x_dim` and `\l__coffin_offset_y_dim`.)

`\l__coffin_pole_a_tl` Needed for finding the intersection of two poles.

`\l__coffin_pole_b_tl`

```
20803 \tl_new:N \l__coffin_pole_a_tl
20804 \tl_new:N \l__coffin_pole_b_tl
```

(End definition for `\l__coffin_pole_a_tl` and `\l__coffin_pole_b_tl`.)

```

\l__coffin_x_dim For calculating intersections and so forth.
\l__coffin_y_dim
\l__coffin_x_prime_dim
\l__coffin_y_prime_dim

```

(End definition for \l\_\_coffin\_x\_dim and others.)

## 38.2 Basic coffin functions

There are a number of basic functions needed for creating coffins and placing material in them. This all relies on the following data structures.

**\coffin\_if\_exist\_p:N** Several of the higher-level coffin functions would give multiple errors if the coffin does not exist. A cleaner way to handle this is provided here: both the box and the coffin structure are checked.

```

\coffin_if_exist:NTF
\coffin_if_exist:cTF
20809 \prg_new_conditional:Npnn \coffin_if_exist:N #1 { p , T , F , TF }
20810 {
20811   \cs_if_exist:NTF #1
20812   {
20813     \cs_if_exist:cTF { l__coffin_poles_ __int_value:w #1 _prop }
20814     { \prg_return_true: }
20815     { \prg_return_false: }
20816   }
20817   { \prg_return_false: }
20818 }
20819 \cs_generate_variant:Nn \coffin_if_exist_p:N { c }
20820 \cs_generate_variant:Nn \coffin_if_exist:NT { c }
20821 \cs_generate_variant:Nn \coffin_if_exist:NF { c }
20822 \cs_generate_variant:Nn \coffin_if_exist:NTF { c }

```

(End definition for \coffin\_if\_exist:NTF. This function is documented on page 221.)

**\\_\_coffin\_if\_exist:NT** Several of the higher-level coffin functions would give multiple errors if the coffin does not exist. So a wrapper is provided to deal with this correctly, issuing an error on erroneous use.

```

20823 \cs_new_protected:Npn \__coffin_if_exist:NT #1#2
20824 {
20825   \coffin_if_exist:NTF #1
20826   { #2 }
20827   {
20828     \__msg_kernel_error:nxx { kernel } { unknown-coffin }
20829     { \token_to_str:N #1 }
20830   }
20831 }

```

(End definition for \\_\_coffin\_if\_exist:NT.)

**\coffin\_clear:N** Clearing coffins means emptying the box and resetting all of the structures.

```

\coffin_clear:c
20832 \cs_new_protected:Npn \coffin_clear:N #1
20833 {
20834   \__coffin_if_exist:NT #1
20835   {
20836     \box_clear:N #1

```

```

20837         \__coffin_reset_structure:N #1
20838     }
20839 }
20840 \cs_generate_variant:Nn \coffin_clear:N { c }

```

(End definition for `\coffin_clear:N`. This function is documented on page 221.)

**`\coffin_new:N`** Creating a new coffin means making the underlying box and adding the data structures.  
**`\coffin_new:c`** These are created globally, as there is a need to avoid any strange effects if the coffin is created inside a group. This means that the usual rule about `\l...` variables has to be broken.

```

20841 \cs_new_protected:Npn \coffin_new:N #1
20842 {
20843     \box_new:N #1
20844     \__debug_suspend_log:
20845     \prop_clear_new:c { l__coffin_corners_ \__int_value:w #1 _prop }
20846     \prop_clear_new:c { l__coffin_poles_ \__int_value:w #1 _prop }
20847     \prop_gset_eq:cN { l__coffin_corners_ \__int_value:w #1 _prop }
20848         \c__coffin_corners_prop
20849     \prop_gset_eq:cN { l__coffin_poles_ \__int_value:w #1 _prop }
20850         \c__coffin_poles_prop
20851     \__debug_resume_log:
20852 }
20853 \cs_generate_variant:Nn \coffin_new:N { c }

```

(End definition for `\coffin_new:N`. This function is documented on page 221.)

**`\hcoffin_set:Nn`** Horizontal coffins are relatively easy: set the appropriate box, reset the structures then  
**`\hcoffin_set:cn`** update the handle positions.

```

20854 \cs_new_protected:Npn \hcoffin_set:Nn #1#2
20855 {
20856     \__coffin_if_exist:NT #1
20857     {
20858         \hbox_set:Nn #1
20859         {
20860             \color_ensure_current:
20861             #2
20862         }
20863         \__coffin_reset_structure:N #1
20864         \__coffin_update_poles:N #1
20865         \__coffin_update_corners:N #1
20866     }
20867 }
20868 \cs_generate_variant:Nn \hcoffin_set:Nn { c }

```

(End definition for `\hcoffin_set:Nn`. This function is documented on page 221.)

**`\vcoffin_set:Nnn`** Setting vertical coffins is more complex. First, the material is typeset with a given width.  
**`\vcoffin_set:cnn`** The default handles and poles are set as for a horizontal coffin, before finding the top baseline using a temporary box. No `\color_ensure_current:` here as that would add a whatsit to the start of the vertical box and mess up the location of the T pole (see *TEX by Topic* for discussion of the `\vtop` primitive, used to do the measuring).

```

20869 \cs_new_protected:Npn \vcoffin_set:Nnn #1#2#3
20870 {

```

```

20871     \__coffin_if_exist:NT #1
20872     {
20873         \vbox_set:Nn #1
20874         {
20875             \dim_set:Nn \tex_hsize:D {#2}
20876     <*package>
20877             \dim_set_eq:NN \linewidth \tex_hsize:D
20878             \dim_set_eq:NN \columnwidth \tex_hsize:D
20879     </package>
20880             #3
20881         }
20882         \__coffin_reset_structure:N #1
20883         \__coffin_update_poles:N #1
20884         \__coffin_update_corners:N #1
20885         \vbox_set_top:Nn \l__coffin_internal_box { \vbox_unpack:N #1 }
20886         \__coffin_set_pole:Nnx #1 { T }
20887         {
20888             { Opt }
20889             {
20890                 \dim_eval:n
20891                 { \box_ht:N #1 - \box_ht:N \l__coffin_internal_box }
20892             }
20893             { 1000pt }
20894             { Opt }
20895         }
20896         \box_clear:N \l__coffin_internal_box
20897     }
20898 }
20899 \cs_generate_variant:Nn \vcoffin_set:Nnn { c }

```

(End definition for `\vcoffin_set:Nnn`. This function is documented on page 222.)

`\hcoffin_set:Nw` These are the “begin”/“end” versions of the above: watch the grouping!

`\hcoffin_set:cw`

`\hcoffin_set_end:`

```

20900 \cs_new_protected:Npn \hcoffin_set:Nw #1
20901 {
20902     \__coffin_if_exist:NT #1
20903     {
20904         \hbox_set:Nw #1 \color_ensure_current:
20905         \cs_set_protected:Npn \hcoffin_set_end:
20906         {
20907             \hbox_set_end:
20908             \__coffin_reset_structure:N #1
20909             \__coffin_update_poles:N #1
20910             \__coffin_update_corners:N #1
20911         }
20912     }
20913 }
20914 \cs_new_protected:Npn \hcoffin_set_end: { }
20915 \cs_generate_variant:Nn \hcoffin_set:Nw { c }

```

(End definition for `\hcoffin_set:Nw` and `\hcoffin_set_end:`. These functions are documented on page 221.)

`\vcoffin_set:Nnw` The same for vertical coffins.

`\vcoffin_set:cnw`

`\vcoffin_set_end:`

```

20916 \cs_new_protected:Npn \vcoffin_set:Nnw #1#2

```

```

20917 {
20918   \__coffin_if_exist:NT #1
20919   {
20920     \vbox_set:Nw #1
20921     \dim_set:Nn \tex_hsize:D {#2}
20922 (*package)
20923     \dim_set_eq:NN \linewidth \tex_hsize:D
20924     \dim_set_eq:NN \columnwidth \tex_hsize:D
20925 (//package)
20926 \cs_set_protected:Npn \vcoffin_set_end:
20927 {
20928   \vbox_set_end:
20929   \__coffin_reset_structure:N #1
20930   \__coffin_update_poles:N #1
20931   \__coffin_update_corners:N #1
20932   \vbox_set_top:Nn \l__coffin_internal_box { \vbox_unpack:N #1 }
20933   \__coffin_set_pole:Nnx #1 { T }
20934   {
20935     { Opt }
20936     {
20937       \dim_eval:n
20938       { \box_ht:N #1 - \box_ht:N \l__coffin_internal_box }
20939     }
20940     { 1000pt }
20941     { Opt }
20942   }
20943   \box_clear:N \l__coffin_internal_box
20944 }
20945 }
20946 }
20947 \cs_new_protected:Npn \vcoffin_set_end: { }
20948 \cs_generate_variant:Nn \vcoffin_set:Nnw { c }

```

(End definition for `\vcoffin_set:Nnw` and `\vcoffin_set_end:`. These functions are documented on page 222.)

**`\coffin_set_eq:NN`** Setting two coffins equal is just a wrapper around other functions.

```

\coffin_set_eq:Nc 20949 \cs_new_protected:Npn \coffin_set_eq:NN #1#2
\coffin_set_eq:cN 20950 {
\coffin_set_eq:cc 20951   \__coffin_if_exist:NT #1
20952   {
20953     \box_set_eq:NN #1 #2
20954     \__coffin_set_eq_structure:NN #1 #2
20955   }
20956 }
20957 \cs_generate_variant:Nn \coffin_set_eq:NN { c , Nc , cc }

```

(End definition for `\coffin_set_eq:NN`. This function is documented on page 221.)

**`\c_empty_coffin`** Special coffins: these cannot be set up earlier as they need `\coffin_new:N`. The empty coffin is set as a box as the full coffin-setting system needs some material which is not yet available.

```

\l__coffin_aligned_coffin
\l__coffin_aligned_internal_coffin
20958 \coffin_new:N \c_empty_coffin
20959 \hbox_set:Nn \c_empty_coffin { }

```

```

20960 \coffin_new:N \l__coffin_aligned_coffin
20961 \coffin_new:N \l__coffin_aligned_internal_coffin

```

(End definition for `\c_empty_coffin`, `\l__coffin_aligned_coffin`, and `\l__coffin_aligned_internal_coffin`. These variables are documented on page 224.)

`\l_tmpa_coffin` The usual scratch space.

```

\l_tmpb_coffin 20962 \coffin_new:N \l_tmpa_coffin
20963 \coffin_new:N \l_tmpb_coffin

```

(End definition for `\l_tmpa_coffin` and `\l_tmpb_coffin`. These variables are documented on page 224.)

### 38.3 Measuring coffins

`\coffin_dp:N` Coffins are just boxes when it comes to measurement. However, semantically a separate set of functions are required.

```

\coffin_dp:c 20964 \cs_new_eq:NN \coffin_dp:N \box_dp:N
\coffin_ht:N 20965 \cs_new_eq:NN \coffin_dp:c \box_dp:c
\coffin_ht:c 20966 \cs_new_eq:NN \coffin_ht:N \box_ht:N
\coffin_wd:N 20967 \cs_new_eq:NN \coffin_ht:c \box_ht:c
\coffin_wd:c 20968 \cs_new_eq:NN \coffin_wd:N \box_wd:N
20969 \cs_new_eq:NN \coffin_wd:c \box_wd:c

```

(End definition for `\coffin_dp:N`, `\coffin_ht:N`, and `\coffin_wd:N`. These functions are documented on page 223.)

### 38.4 Coffins: handle and pole management

`\__coffin_get_pole:NnN` A simple wrapper around the recovery of a coffin pole, with some error checking and recovery built-in.

```

20970 \cs_new_protected:Npn \__coffin_get_pole:NnN #1#2#3
20971 {
20972   \prop_get:cnNF
20973     { l__coffin_poles_ \__int_value:w #1 _prop } {#2} #3
20974   {
20975     \_msg_kernel_error:nxx { kernel } { unknown-coffin-pole }
20976     {#2} { \token_to_str:N #1 }
20977     \tl_set:Nn #3 { { Opt } { Opt } { Opt } { Opt } }
20978   }
20979 }

```

(End definition for `\__coffin_get_pole:NnN`.)

`\__coffin_reset_structure:N` Resetting the structure is a simple copy job.

```

20980 \cs_new_protected:Npn \__coffin_reset_structure:N #1
20981 {
20982   \prop_set_eq:cN { l__coffin_corners_ \__int_value:w #1 _prop }
20983     \c__coffin_corners_prop
20984   \prop_set_eq:cN { l__coffin_poles_ \__int_value:w #1 _prop }
20985     \c__coffin_poles_prop
20986 }

```

(End definition for `\__coffin_reset_structure:N`.)



`\_coffin_set_eq_structure:NN` Setting coffin structures equal simply means copying the property list.

```

\coffin_gset_eq_structure:NN
20987 \cs_new_protected:Npn \_coffin_set_eq_structure:NN #1#2
20988 {
20989   \prop_set_eq:cc { l__coffin_corners_ \_int_value:w #1 _prop }
20990   { l__coffin_corners_ \_int_value:w #2 _prop }
20991   \prop_set_eq:cc { l__coffin_poles_ \_int_value:w #1 _prop }
20992   { l__coffin_poles_ \_int_value:w #2 _prop }
20993 }
20994 \cs_new_protected:Npn \_coffin_gset_eq_structure:NN #1#2
20995 {
20996   \prop_gset_eq:cc { l__coffin_corners_ \_int_value:w #1 _prop }
20997   { l__coffin_corners_ \_int_value:w #2 _prop }
20998   \prop_gset_eq:cc { l__coffin_poles_ \_int_value:w #1 _prop }
20999   { l__coffin_poles_ \_int_value:w #2 _prop }
21000 }

```

(End definition for `\_coffin_set_eq_structure:NN` and `\_coffin_gset_eq_structure:NN`.)

`\coffin_set_horizontal_pole:Nnn` Setting the pole of a coffin at the user/designer level requires a bit more care. The idea here is to provide a reasonable interface to the system, then to do the setting with full expansion. The three-argument version is used internally to do a direct setting.

```

\coffin_set_horizontal_pole:cnm
\coffin_set_vertical_pole:Nnn
\coffin_set_vertical_pole:cnm
\__coffin_set_pole:Nnn
\__coffin_set_pole:Nnx
21001 \cs_new_protected:Npn \coffin_set_horizontal_pole:Nnn #1#2#3
21002 {
21003   \__coffin_if_exist:NT #1
21004   {
21005     \__coffin_set_pole:Nnx #1 {#2}
21006     {
21007       { Opt } { \dim_eval:n {#3} }
21008       { 1000pt } { Opt }
21009     }
21010   }
21011 }
21012 \cs_new_protected:Npn \coffin_set_vertical_pole:Nnn #1#2#3
21013 {
21014   \__coffin_if_exist:NT #1
21015   {
21016     \__coffin_set_pole:Nnx #1 {#2}
21017     {
21018       { \dim_eval:n {#3} } { Opt }
21019       { Opt } { 1000pt }
21020     }
21021   }
21022 }
21023 \cs_new_protected:Npn \_coffin_set_pole:Nnn #1#2#3
21024 { \prop_put:cnm { l__coffin_poles_ \_int_value:w #1 _prop } {#2} {#3} }
21025 \cs_generate_variant:Nn \coffin_set_horizontal_pole:Nnn { c }
21026 \cs_generate_variant:Nn \coffin_set_vertical_pole:Nnn { c }
21027 \cs_generate_variant:Nn \_coffin_set_pole:Nnn { Nnx }

```

(End definition for `\coffin_set_horizontal_pole:Nnn`, `\coffin_set_vertical_pole:Nnn`, and `\_coffin_set_pole:Nnn`. These functions are documented on page 222.)

`\_coffin_update_corners:N` Updating the corners of a coffin is straight-forward as at this stage there can be no rotation. So the corners of the content are just those of the underlying TeX box.

```

21028 \cs_new_protected:Npn \__coffin_update_corners:N #1
21029 {
21030   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } { tl }
21031   { { Opt } { \dim_eval:n { \box_ht:N #1 } } } }
21032   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } { tr }
21033   { { \dim_eval:n { \box_wd:N #1 } } { \dim_eval:n { \box_ht:N #1 } } } }
21034   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } { bl }
21035   { { Opt } { \dim_eval:n { -\box_dp:N #1 } } } }
21036   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } { br }
21037   { { \dim_eval:n { \box_wd:N #1 } } { \dim_eval:n { -\box_dp:N #1 } } } }
21038 }

```

(End definition for \\_\_coffin\_update\_corners:N.)

\\_\_coffin\_update\_poles:N This function is called when a coffin is set, and updates the poles to reflect the nature of size of the box. Thus this function only alters poles where the default position is dependent on the size of the box. It also does not set poles which are relevant only to vertical coffins.

```

21039 \cs_new_protected:Npn \__coffin_update_poles:N #1
21040 {
21041   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { hc }
21042   {
21043     { \dim_eval:n { 0.5 \box_wd:N #1 } }
21044     { Opt } { Opt } { 1000pt }
21045   }
21046   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { r }
21047   {
21048     { \dim_eval:n { \box_wd:N #1 } }
21049     { Opt } { Opt } { 1000pt }
21050   }
21051   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { vc }
21052   {
21053     { Opt }
21054     { \dim_eval:n { ( \box_ht:N #1 - \box_dp:N #1 ) / 2 } }
21055     { 1000pt }
21056     { Opt }
21057   }
21058   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { t }
21059   {
21060     { Opt }
21061     { \dim_eval:n { \box_ht:N #1 } }
21062     { 1000pt }
21063     { Opt }
21064   }
21065   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { b }
21066   {
21067     { Opt }
21068     { \dim_eval:n { -\box_dp:N #1 } }
21069     { 1000pt }
21070     { Opt }
21071   }
21072 }

```

(End definition for \\_\_coffin\_update\_poles:N.)

### 38.5 Coffins: calculation of pole intersections

\\_coffin\_calculate\_intersection:Nmn  
 \\_coffin\_calculate\_intersection:nnnnnnnn  
 \\_coffin\_calculate\_intersection\_aux:nnnnnN

The lead off in finding intersections is to recover the two poles and then hand off to the auxiliary for the actual calculation. There may of course not be an intersection, for which an error trap is needed.

```

21073 \cs_new_protected:Npn \_coffin_calculate_intersection:Nnn #1#2#3
21074 {
21075   \_coffin_get_pole:NnN #1 {#2} \l__coffin_pole_a_tl
21076   \_coffin_get_pole:NnN #1 {#3} \l__coffin_pole_b_tl
21077   \bool_set_false:N \l__coffin_error_bool
21078   \exp_last_two_unbraced:Noo
21079   \_coffin_calculate_intersection:nnnnnnnn
21080   \l__coffin_pole_a_tl \l__coffin_pole_b_tl
21081   \bool_if:NT \l__coffin_error_bool
21082   {
21083     \_msg_kernel_error:nn { kernel } { no-pole-intersection }
21084     \dim_zero:N \l__coffin_x_dim
21085     \dim_zero:N \l__coffin_y_dim
21086   }
21087 }
```

The two poles passed here each have four values (as dimensions),  $(a, b, c, d)$  and  $(a', b', c', d')$ . These are arguments 1–4 and 5–8, respectively. In both cases  $a$  and  $b$  are the co-ordinates of a point on the pole and  $c$  and  $d$  define the direction of the pole. Finding the intersection depends on the directions of the poles, which are given by  $d/c$  and  $d'/c'$ . However, if one of the poles is either horizontal or vertical then one or more of  $c, d, c'$  and  $d'$  are zero and a special case is needed.

```

21088 \cs_new_protected:Npn \_coffin_calculate_intersection:nnnnnnnn
21089   #1#2#3#4#5#6#7#8
21090 {
21091   \dim_compare:nNnTF {#3} = { \c_zero_dim }
```

The case where the first pole is vertical. So the  $x$ -component of the intersection is at  $a$ . There is then a test on the second pole: if it is also vertical then there is an error.

```

21092   {
21093     \dim_set:Nn \l__coffin_x_dim {#1}
21094     \dim_compare:nNnTF {#7} = { \c_zero_dim
21095       { \bool_set_true:N \l__coffin_error_bool }
21096   }
```

The second pole may still be horizontal, in which case the  $y$ -component of the intersection is  $b'$ . If not,

$$y = \frac{d'}{c'} (x - a') + b'$$

with the  $x$ -component already known to be #1. This calculation is done as a generalised auxiliary.

```

21096   {
21097     \dim_compare:nNnTF {#8} = { \c_zero_dim
21098       { \dim_set:Nn \l__coffin_y_dim {#6} }
21099       {
21100         \_coffin_calculate_intersection_aux:nnnnnN
21101         {#1} {#5} {#6} {#7} {#8} \l__coffin_y_dim
21102       }
21103     }
21104 }
```

If the first pole is not vertical then it may be horizontal. If so, then the procedure is essentially the same as that already done but with the  $x$ - and  $y$ -components interchanged.

```

21105     {
21106         \dim_compare:nNnTF {#4} = \c_zero_dim
21107         {
21108             \dim_set:Nn \l__coffin_y_dim {#2}
21109             \dim_compare:nNnTF {#8} = { \c_zero_dim }
21110             { \bool_set_true:N \l__coffin_error_bool }
21111         }
21112         \dim_compare:nNnTF {#7} = \c_zero_dim
21113         { \dim_set:Nn \l__coffin_x_dim {#5} }

```

The formula for the case where the second pole is neither horizontal nor vertical is

$$x = \frac{c'}{d'}(y - b') + a'$$

which is again handled by the same auxiliary.

```

21114     {
21115         \__coffin_calculate_intersection_aux:nnnnnN
21116         {#2} {#6} {#5} {#8} {#7} \l__coffin_x_dim
21117     }
21118 }
21119 }

```

The first pole is neither horizontal nor vertical. This still leaves the second pole, which may be a special case. For those possibilities, the calculations are the same as above with the first and second poles interchanged.

```

21120     {
21121         \dim_compare:nNnTF {#7} = \c_zero_dim
21122         {
21123             \dim_set:Nn \l__coffin_x_dim {#5}
21124             \__coffin_calculate_intersection_aux:nnnnnN
21125             {#5} {#1} {#2} {#3} {#4} \l__coffin_y_dim
21126         }
21127         {
21128             \dim_compare:nNnTF {#8} = \c_zero_dim
21129             {
21130                 \dim_set:Nn \l__coffin_y_dim {#6}
21131                 \__coffin_calculate_intersection_aux:nnnnnN
21132                 {#6} {#2} {#1} {#4} {#3} \l__coffin_x_dim
21133             }

```

If none of the special cases apply then there is still a need to check that there is a unique intersection between the two pole. This is the case if they have different slopes.

```

21134     {
21135         \fp_set:Nn \l__coffin_slope_x_fp
21136         { \dim_to_fp:n {#4} / \dim_to_fp:n {#3} }
21137         \fp_set:Nn \l__coffin_slope_y_fp
21138         { \dim_to_fp:n {#8} / \dim_to_fp:n {#7} }
21139         \fp_compare:nNnTF
21140         \l__coffin_slope_x_fp = \l__coffin_slope_y_fp
21141         { \bool_set_true:N \l__coffin_error_bool }

```

All of the tests pass, so there is the full complexity of the calculation:

$$x = \frac{a(d/c) - a'(d'/c') - b + b'}{(d/c) - (d'/c')}$$

and noting that the two ratios are already worked out from the test just performed. There is quite a bit of shuffling from dimensions to floating points in order to do the work. The  $y$ -values is then worked out using the standard auxiliary starting from the  $x$ -position.

```

21142         {
21143             \dim_set:Nn \l__coffin_x_dim
21144             {
21145                 \fp_to_dim:n
21146                 {
21147                     (
21148                         \dim_to_fp:n {#1} * \l__coffin_slope_x_fp
21149                         - ( \dim_to_fp:n {#5} * \l__coffin_slope_y_fp )
21150                         - \dim_to_fp:n {#2}
21151                         + \dim_to_fp:n {#6}
21152                     )
21153                     /
21154                     ( \l__coffin_slope_x_fp - \l__coffin_slope_y_fp )
21155                 }
21156             }
21157             \__coffin_calculate_intersection_aux:nnnnnN
21158             { \l__coffin_x_dim }
21159             {#5} {#6} {#8} {#7} \l__coffin_y_dim
21160         }
21161     }
21162 }
21163 }
21164 }
21165 }

```

The formula for finding the intersection point is in most cases the same. The formula here is

$$\#6 = \#4 \cdot \left( \frac{\#1 - \#2}{\#5} \right) \#3$$

Thus #4 and #5 should be the directions of the pole while #2 and #3 are co-ordinates.

```

21166 \cs_new_protected:Npn \__coffin_calculate_intersection_aux:nnnnnN
21167     #1#2#3#4#5#6
21168     {
21169         \dim_set:Nn #6
21170         {
21171             \fp_to_dim:n
21172             {
21173                 \dim_to_fp:n {#4} *
21174                 ( \dim_to_fp:n {#1} - \dim_to_fp:n {#2} ) /
21175                 \dim_to_fp:n {#5}
21176                 + \dim_to_fp:n {#3}
21177             }
21178         }
21179     }

```

(End definition for `\__coffin_calculate_intersection:Nnn`, `\__coffin_calculate_intersection:nnnnnnnn`, and `\__coffin_calculate_intersection_aux:nnnnnN`.)

## 38.6 Aligning and typesetting of coffins

`\coffin_join:NnnNnnnn` This command joins two coffins, using a horizontal and vertical pole from each coffin and making an offset between the two. The result is stored as the as a third coffin, which has all of its handles reset to standard values. First, the more basic alignment function `\coffin_join:Nnnnnnnn` is used to get things started.

```

21180 \cs_new_protected:Npn \coffin_join:NnnNnnnn #1#2#3#4#5#6#7#8
21181   {
21182     \__coffin_align:NnnNnnnnN
21183     #1 {#2} {#3} #4 {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin

```

Correct the placement of the reference point. If the  $x$ -offset is negative then the reference point of the second box is to the left of that of the first, which is corrected using a kern. On the right side the first box might stick out, which would show up if it is wider than the sum of the  $x$ -offset and the width of the second box. So a second kern may be needed.

```

21184   \hbox_set:Nn \l__coffin_aligned_coffin
21185   {
21186     \dim_compare:nNnT { \l__coffin_offset_x_dim } < \c_zero_dim
21187     { \tex_kern:D -\l__coffin_offset_x_dim }
21188     \hbox_unpack:N \l__coffin_aligned_coffin
21189     \dim_set:Nn \l__coffin_internal_dim
21190     { \l__coffin_offset_x_dim - \box_wd:N #1 + \box_wd:N #4 }
21191     \dim_compare:nNnT \l__coffin_internal_dim < \c_zero_dim
21192     { \tex_kern:D -\l__coffin_internal_dim }
21193   }

```

The coffin structure is reset, and the corners are cleared: only those from the two parent coffins are needed.

```

21194   \__coffin_reset_structure:N \l__coffin_aligned_coffin
21195   \prop_clear:c
21196   { \l__coffin_corners_ \__int_value:w \l__coffin_aligned_coffin _ prop }
21197   \__coffin_update_poles:N \l__coffin_aligned_coffin

```

The structures of the parent coffins are now transferred to the new coffin, which requires that the appropriate offsets are applied. That then depends on whether any shift was needed.

```

21198   \dim_compare:nNnTF \l__coffin_offset_x_dim < \c_zero_dim
21199   {
21200     \__coffin_offset_poles:Nnn #1 { -\l__coffin_offset_x_dim } { Opt }
21201     \__coffin_offset_poles:Nnn #4 { Opt } { \l__coffin_offset_y_dim }
21202     \__coffin_offset_corners:Nnn #1 { -\l__coffin_offset_x_dim } { Opt }
21203     \__coffin_offset_corners:Nnn #4 { Opt } { \l__coffin_offset_y_dim }
21204   }
21205   {
21206     \__coffin_offset_poles:Nnn #1 { Opt } { Opt }
21207     \__coffin_offset_poles:Nnn #4
21208     { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
21209     \__coffin_offset_corners:Nnn #1 { Opt } { Opt }
21210     \__coffin_offset_corners:Nnn #4
21211     { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
21212   }

```

```

21213     \__coffin_update_vertical_poles:NNN #1 #4 \l__coffin_aligned_coffin
21214     \coffin_set_eq:NN #1 \l__coffin_aligned_coffin
21215 }
21216 \cs_generate_variant:Nn \coffin_join:NnnNnnnn { c , Nnnc , cncnc }

```

(End definition for \coffin\_join:NnnNnnnn. This function is documented on page 223.)

**\coffin\_attach:NnnNnnnn**

**\coffin\_attach:cncNnnnn**

**\coffin\_attach:Nnncnnnn**

**\coffin\_attach:cncncnnnn**

**\coffin\_attach\_mark:NnnNnnnn**

A more simple version of the above, as it simply uses the size of the first coffin for the new one. This means that the work here is rather simplified compared to the above code. The function used when marking a position is hear also as it is similar but without the structure updates.

```

21217 \cs_new_protected:Npn \coffin_attach:NnnNnnnn #1#2#3#4#5#6#7#8
21218 {
21219     \__coffin_align:NnnNnnnnN
21220     #1 {#2} {#3} #4 {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin
21221     \box_set_ht:Nn \l__coffin_aligned_coffin { \box_ht:N #1 }
21222     \box_set_dp:Nn \l__coffin_aligned_coffin { \box_dp:N #1 }
21223     \box_set_wd:Nn \l__coffin_aligned_coffin { \box_wd:N #1 }
21224     \__coffin_reset_structure:N \l__coffin_aligned_coffin
21225     \prop_set_eq:cc
21226     { \l__coffin_corners_ \__int_value:w \l__coffin_aligned_coffin _prop }
21227     { \l__coffin_corners_ \__int_value:w #1 _prop }
21228     \__coffin_update_poles:N \l__coffin_aligned_coffin
21229     \__coffin_offset_poles:Nnn #1 { Opt } { Opt }
21230     \__coffin_offset_poles:Nnn #4
21231     { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
21232     \__coffin_update_vertical_poles:NNN #1 #4 \l__coffin_aligned_coffin
21233     \coffin_set_eq:NN #1 \l__coffin_aligned_coffin
21234 }
21235 \cs_new_protected:Npn \coffin_attach_mark:NnnNnnnn #1#2#3#4#5#6#7#8
21236 {
21237     \__coffin_align:NnnNnnnnN
21238     #1 {#2} {#3} #4 {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin
21239     \box_set_ht:Nn \l__coffin_aligned_coffin { \box_ht:N #1 }
21240     \box_set_dp:Nn \l__coffin_aligned_coffin { \box_dp:N #1 }
21241     \box_set_wd:Nn \l__coffin_aligned_coffin { \box_wd:N #1 }
21242     \box_set_eq:NN #1 \l__coffin_aligned_coffin
21243 }
21244 \cs_generate_variant:Nn \coffin_attach:NnnNnnnn { c , Nnnc , cncnc }

```

(End definition for \coffin\_attach:NnnNnnnn and \coffin\_attach\_mark:NnnNnnnn. These functions are documented on page 222.)

**\\_\_coffin\_align:NnnNnnnnN**

The internal function aligns the two coffins into a third one, but performs no corrections on the resulting coffin poles. The process begins by finding the points of intersection for the poles for each of the input coffins. Those for the first coffin are worked out after those for the second coffin, as this allows the ‘primed’ storage area to be used for the second coffin. The ‘real’ box offsets are then calculated, before using these to re-box the input coffins. The default poles are then set up, but the final result depends on how the bounding box is being handled.

```

21245 \cs_new_protected:Npn \__coffin_align:NnnNnnnnN #1#2#3#4#5#6#7#8#9
21246 {
21247     \__coffin_calculate_intersection:Nnn #4 {#5} {#6}
21248     \dim_set:Nn \l__coffin_x_prime_dim { \l__coffin_x_dim }

```

```

21249 \dim_set:Nn \l__coffin_y_prime_dim { \l__coffin_y_dim }
21250 \__coffin_calculate_intersection:Nnn #1 {#2} {#3}
21251 \dim_set:Nn \l__coffin_offset_x_dim
21252 { \l__coffin_x_dim - \l__coffin_x_prime_dim + #7 }
21253 \dim_set:Nn \l__coffin_offset_y_dim
21254 { \l__coffin_y_dim - \l__coffin_y_prime_dim + #8 }
21255 \hbox_set:Nn \l__coffin_aligned_internal_coffin
21256 {
21257   \box_use:N #1
21258   \tex_kern:D -\box_wd:N #1
21259   \tex_kern:D \l__coffin_offset_x_dim
21260   \box_move_up:nn { \l__coffin_offset_y_dim } { \box_use:N #4 }
21261 }
21262 \coffin_set_eq:NN #9 \l__coffin_aligned_internal_coffin
21263 }

```

(End definition for `\__coffin_align:NnnNnnnnN`.)

`\__coffin_offset_poles:Nnn` Transferring structures from one coffin to another requires that the positions are updated by the offset between the two coffins. This is done by mapping to the property list of the source coffins, moving as appropriate and saving to the new coffin data structures. The test for a - means that the structures from the parent coffins are uniquely labelled and do not depend on the order of alignment. The pay off for this is that - should not be used in coffin pole or handle names, and that multiple alignments do not result in a whole set of values.

```

21264 \cs_new_protected:Npn \__coffin_offset_poles:Nnn #1#2#3
21265 {
21266   \prop_map_inline:cn { l__coffin_poles_ \__int_value:w #1 _prop }
21267   { \__coffin_offset_pole:Nnnnnnn #1 {##1} ##2 {#2} {#3} }
21268 }
21269 \cs_new_protected:Npn \__coffin_offset_pole:Nnnnnnn #1#2#3#4#5#6#7#8
21270 {
21271   \dim_set:Nn \l__coffin_x_dim { #3 + #7 }
21272   \dim_set:Nn \l__coffin_y_dim { #4 + #8 }
21273   \tl_if_in:nnTF {#2} { - }
21274   { \tl_set:Nn \l__coffin_internal_tl { {#2} } }
21275   { \tl_set:Nn \l__coffin_internal_tl { { #1 - #2 } } }
21276   \exp_last_unbraced:NNo \__coffin_set_pole:Nnx \l__coffin_aligned_coffin
21277   { \l__coffin_internal_tl }
21278   {
21279     { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
21280     {#5} {#6}
21281   }
21282 }

```

(End definition for `\__coffin_offset_poles:Nnn` and `\__coffin_offset_pole:Nnnnnnn`.)

`\__coffin_offset_corners:Nnn` Saving the offset corners of a coffin is very similar, except that there is no need to worry about naming: every corner can be saved here as order is unimportant.

```

21283 \cs_new_protected:Npn \__coffin_offset_corners:Nnn #1#2#3
21284 {
21285   \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
21286   { \__coffin_offset_corner:Nnnnn #1 {##1} ##2 {#2} {#3} }
21287 }

```



```

21288 \cs_new_protected:Npn \__coffin_offset_corner:Nnnnn #1#2#3#4#5#6
21289 {
21290   \prop_put:cnx
21291   { l__coffin_corners_ \__int_value:w \l__coffin_aligned_coffin _prop }
21292   { #1 - #2 }
21293   {
21294     { \dim_eval:n { #3 + #5 } }
21295     { \dim_eval:n { #4 + #6 } }
21296   }
21297 }

```

(End definition for \\_\_coffin\_offset\_corners:Nnn and \\_\_coffin\_offset\_corner:Nnnnn.)

```

\__coffin_update_vertical_poles:NNN
\__coffin_update_T:nnnnnnnnN
\__coffin_update_B:nnnnnnnnN

```

The T and B poles need to be recalculated after alignment. These functions find the larger absolute value for the poles, but this is of course only logical when the poles are horizontal.

```

21298 \cs_new_protected:Npn \__coffin_update_vertical_poles:NNN #1#2#3
21299 {
21300   \__coffin_get_pole:NnN #3 { #1 -T } \l__coffin_pole_a_tl
21301   \__coffin_get_pole:NnN #3 { #2 -T } \l__coffin_pole_b_tl
21302   \exp_last_two_unbraced:Noo \__coffin_update_T:nnnnnnnnN
21303   \l__coffin_pole_a_tl \l__coffin_pole_b_tl #3
21304   \__coffin_get_pole:NnN #3 { #1 -B } \l__coffin_pole_a_tl
21305   \__coffin_get_pole:NnN #3 { #2 -B } \l__coffin_pole_b_tl
21306   \exp_last_two_unbraced:Noo \__coffin_update_B:nnnnnnnnN
21307   \l__coffin_pole_a_tl \l__coffin_pole_b_tl #3
21308 }
21309 \cs_new_protected:Npn \__coffin_update_T:nnnnnnnnN #1#2#3#4#5#6#7#8#9
21310 {
21311   \dim_compare:nNnTF {#2} < {#6}
21312   {
21313     \__coffin_set_pole:Nnx #9 { T }
21314     { { Opt } {#6} { 1000pt } { Opt } }
21315   }
21316   {
21317     \__coffin_set_pole:Nnx #9 { T }
21318     { { Opt } {#2} { 1000pt } { Opt } }
21319   }
21320 }
21321 \cs_new_protected:Npn \__coffin_update_B:nnnnnnnnN #1#2#3#4#5#6#7#8#9
21322 {
21323   \dim_compare:nNnTF {#2} < {#6}
21324   {
21325     \__coffin_set_pole:Nnx #9 { B }
21326     { { Opt } {#2} { 1000pt } { Opt } }
21327   }
21328   {
21329     \__coffin_set_pole:Nnx #9 { B }
21330     { { Opt } {#6} { 1000pt } { Opt } }
21331   }
21332 }

```

(End definition for \\_\_coffin\_update\_vertical\_poles:NNN, \\_\_coffin\_update\_T:nnnnnnnnN, and \\_\_coffin\_update\_B:nnnnnnnnN.)

`\coffin_typeset:Nnnnn` Typesetting a coffin means aligning it with the current position, which is done using a coffin with no content at all. As well as aligning to the empty coffin, there is also a need to leave vertical mode, if necessary.

```

21333 \cs_new_protected:Npn \coffin_typeset:Nnnnn #1#2#3#4#5
21334 {
21335     \mode_leave_vertical:
21336     \__coffin_align:NnnNnnnnN \c_empty_coffin { H } { l }
21337     #1 {#2} {#3} {#4} {#5} \l__coffin_aligned_coffin
21338     \box_use:N \l__coffin_aligned_coffin
21339 }
21340 \cs_generate_variant:Nn \coffin_typeset:Nnnnn { c }

```

(End definition for `\coffin_typeset:Nnnnn`. This function is documented on page 223.)

## 38.7 Coffin diagnostics

`\l__coffin_display_coffin` Used for printing coffins with data structures attached.

```

\l__coffin_display_coord_coffin 21341 \coffin_new:N \l__coffin_display_coffin
\l__coffin_display_pole_coffin 21342 \coffin_new:N \l__coffin_display_coord_coffin
21343 \coffin_new:N \l__coffin_display_pole_coffin

```

(End definition for `\l__coffin_display_coffin`, `\l__coffin_display_coord_coffin`, and `\l__coffin_display_pole_coffin`.)

`\l__coffin_display_handles_prop` This property list is used to print coffin handles at suitable positions. The offsets are expressed as multiples of the basic offset value, which therefore acts as a scale-factor.

```

21344 \prop_new:N \l__coffin_display_handles_prop
21345 \prop_put:Nnn \l__coffin_display_handles_prop { tl }
21346 { { b } { r } { -1 } { 1 } }
21347 \prop_put:Nnn \l__coffin_display_handles_prop { thc }
21348 { { b } { hc } { 0 } { 1 } }
21349 \prop_put:Nnn \l__coffin_display_handles_prop { tr }
21350 { { b } { l } { 1 } { 1 } }
21351 \prop_put:Nnn \l__coffin_display_handles_prop { vcl }
21352 { { vc } { r } { -1 } { 0 } }
21353 \prop_put:Nnn \l__coffin_display_handles_prop { vhc }
21354 { { vc } { hc } { 0 } { 0 } }
21355 \prop_put:Nnn \l__coffin_display_handles_prop { vcr }
21356 { { vc } { l } { 1 } { 0 } }
21357 \prop_put:Nnn \l__coffin_display_handles_prop { bl }
21358 { { t } { r } { -1 } { -1 } }
21359 \prop_put:Nnn \l__coffin_display_handles_prop { bhc }
21360 { { t } { hc } { 0 } { -1 } }
21361 \prop_put:Nnn \l__coffin_display_handles_prop { br }
21362 { { t } { l } { 1 } { -1 } }
21363 \prop_put:Nnn \l__coffin_display_handles_prop { Tl }
21364 { { t } { r } { -1 } { -1 } }
21365 \prop_put:Nnn \l__coffin_display_handles_prop { Thc }
21366 { { t } { hc } { 0 } { -1 } }
21367 \prop_put:Nnn \l__coffin_display_handles_prop { Tr }
21368 { { t } { l } { 1 } { -1 } }
21369 \prop_put:Nnn \l__coffin_display_handles_prop { Hl }
21370 { { vc } { r } { -1 } { 1 } }
21371 \prop_put:Nnn \l__coffin_display_handles_prop { Hhc }

```

```

21372 { { vc } { hc } { 0 } { 1 } }
21373 \prop_put:Nnn \l__coffin_display_handles_prop { Hr }
21374 { { vc } { 1 } { 1 } { 1 } }
21375 \prop_put:Nnn \l__coffin_display_handles_prop { Bl }
21376 { { b } { r } { -1 } { -1 } }
21377 \prop_put:Nnn \l__coffin_display_handles_prop { Bhc }
21378 { { b } { hc } { 0 } { -1 } }
21379 \prop_put:Nnn \l__coffin_display_handles_prop { Br }
21380 { { b } { 1 } { 1 } { -1 } }

```

(End definition for `\l__coffin_display_handles_prop`.)

`\l__coffin_display_offset_dim` The standard offset for the label from the handle position when displaying handles.

```

21381 \dim_new:N \l__coffin_display_offset_dim
21382 \dim_set:Nn \l__coffin_display_offset_dim { 2pt }

```

(End definition for `\l__coffin_display_offset_dim`.)

`\l__coffin_display_x_dim` As the intersections of poles have to be calculated to find which ones to print, there is  
`\l__coffin_display_y_dim` a need to avoid repetition. This is done by saving the intersection into two dedicated values.

```

21383 \dim_new:N \l__coffin_display_x_dim
21384 \dim_new:N \l__coffin_display_y_dim

```

(End definition for `\l__coffin_display_x_dim` and `\l__coffin_display_y_dim`.)

`\l__coffin_display_poles_prop` A property list for printing poles: various things need to be deleted from this to get a “nice” output.

```

21385 \prop_new:N \l__coffin_display_poles_prop

```

(End definition for `\l__coffin_display_poles_prop`.)

`\l__coffin_display_font_tl` Stores the settings used to print coffin data: this keeps things flexible.

```

21386 \tl_new:N \l__coffin_display_font_tl
21387 \*initex
21388 \tl_set:Nn \l__coffin_display_font_tl { } % TODO
21389 \*initex
21390 \*package
21391 \tl_set:Nn \l__coffin_display_font_tl { \sfamily \tiny }
21392 \*package

```

(End definition for `\l__coffin_display_font_tl`.)

`\coffin_mark_handle:Nnnn` Marking a single handle is relatively easy. The standard attachment function is used,  
`\coffin_mark_handle:cnnn` meaning that there are two calculations for the location. However, this is likely to be  
`\__coffin_mark_handle_aux:nnnnNnn` okay given the load expected. Contrast with the more optimised version for showing all handles which comes next.

```

21393 \cs_new_protected:Npn \coffin_mark_handle:Nnnn #1#2#3#4
21394 {
21395   \hcoffin_set:Nn \l__coffin_display_pole_coffin
21396   {
21397     \*initex
21398     \hbox:n { \tex_vrule:D width 1pt height 1pt \scan_stop: } % TODO
21399     \*initex
21400     \*package

```

```

21401         \color {#4}
21402         \rule { 1pt } { 1pt }
21403     \end{package}
21404 }
21405 \coffin_attach_mark:NnnNnnnn #1 {#2} {#3}
21406 \l__coffin_display_pole_coffin { hc } { vc } { Opt } { Opt }
21407 \hcoffin_set:Nn \l__coffin_display_coord_coffin
21408 {
21409 \*initex
21410 % TODO
21411 \end{initex}
21412 \end{package}
21413 \color {#4}
21414 \end{package}
21415 \l__coffin_display_font_tl
21416 ( \tl_to_str:n { #2 , #3 } )
21417 }
21418 \prop_get:NnN \l__coffin_display_handles_prop
21419 { #2 #3 } \l__coffin_internal_tl
21420 \quark_if_no_value:NTF \l__coffin_internal_tl
21421 {
21422     \prop_get:NnN \l__coffin_display_handles_prop
21423     { #3 #2 } \l__coffin_internal_tl
21424     \quark_if_no_value:NTF \l__coffin_internal_tl
21425     {
21426         \coffin_attach_mark:NnnNnnnn #1 {#2} {#3}
21427         \l__coffin_display_coord_coffin { l } { vc }
21428         { 1pt } { Opt }
21429     }
21430     {
21431         \exp_last_unbraced:No \__coffin_mark_handle_aux:nnnnNnn
21432         \l__coffin_internal_tl #1 {#2} {#3}
21433     }
21434 }
21435 {
21436     \exp_last_unbraced:No \__coffin_mark_handle_aux:nnnnNnn
21437     \l__coffin_internal_tl #1 {#2} {#3}
21438 }
21439 }
21440 \cs_new_protected:Npn \__coffin_mark_handle_aux:nnnnNnn #1#2#3#4#5#6#7
21441 {
21442     \coffin_attach_mark:NnnNnnnn #5 {#6} {#7}
21443     \l__coffin_display_coord_coffin {#1} {#2}
21444     { #3 \l__coffin_display_offset_dim }
21445     { #4 \l__coffin_display_offset_dim }
21446 }
21447 \cs_generate_variant:Nn \coffin_mark_handle:Nnnn { c }

```

(End definition for `\coffin_mark_handle:Nnnn` and `\__coffin_mark_handle_aux:nnnnNnn`. These functions are documented on page 224.)

`\coffin_display_handles:Nn`  
`\coffin_display_handles:cn`  
`\__coffin_display_handles_aux:nnnnnn`  
`\__coffin_display_handles_aux:nnnn`  
`\__coffin_display_attach:Nnnnn`

Printing the poles starts by removing any duplicates, for which the H poles is used as the definitive version for the baseline and bottom. Two loops are then used to find the combinations of handles for all of these poles. This is done such that poles are removed

during the loops to avoid duplication.

```

21448 \cs_new_protected:Npn \coffin_display_handles:Nn #1#2
21449 {
21450   \hcoffin_set:Nn \l__coffin_display_pole_coffin
21451   {
21452     \*initex
21453     \hbox:n { \tex_vrule:D width 1pt height 1pt \scan_stop: } % TODO
21454   }
21455   \*package
21456   \color {#2}
21457   \rule { 1pt } { 1pt }
21458 \*package
21459 }
21460 \prop_set_eq:Nc \l__coffin_display_poles_prop
21461 { \l__coffin_poles_ \__int_value:w #1 _prop }
21462 \__coffin_get_pole:NnN #1 { H } \l__coffin_pole_a_tl
21463 \__coffin_get_pole:NnN #1 { T } \l__coffin_pole_b_tl
21464 \tl_if_eq:NNT \l__coffin_pole_a_tl \l__coffin_pole_b_tl
21465 { \prop_remove:Nn \l__coffin_display_poles_prop { T } }
21466 \__coffin_get_pole:NnN #1 { B } \l__coffin_pole_b_tl
21467 \tl_if_eq:NNT \l__coffin_pole_a_tl \l__coffin_pole_b_tl
21468 { \prop_remove:Nn \l__coffin_display_poles_prop { B } }
21469 \coffin_set_eq:NN \l__coffin_display_coffin #1
21470 \prop_map_inline:Nn \l__coffin_display_poles_prop
21471 {
21472   \prop_remove:Nn \l__coffin_display_poles_prop {##1}
21473   \__coffin_display_handles_aux:nnnnnn {##1} ##2 {#2}
21474 }
21475 \box_use:N \l__coffin_display_coffin
21476 }

```

For each pole there is a check for an intersection, which here does not give an error if none is found. The successful values are stored and used to align the pole coffin with the main coffin for output. The positions are recovered from the preset list if available.

```

21477 \cs_new_protected:Npn \__coffin_display_handles_aux:nnnnnn #1#2#3#4#5#6
21478 {
21479   \prop_map_inline:Nn \l__coffin_display_poles_prop
21480   {
21481     \bool_set_false:N \l__coffin_error_bool
21482     \__coffin_calculate_intersection:nnnnnnnn {#2} {#3} {#4} {#5} ##2
21483     \bool_if:NF \l__coffin_error_bool
21484     {
21485       \dim_set:Nn \l__coffin_display_x_dim { \l__coffin_x_dim }
21486       \dim_set:Nn \l__coffin_display_y_dim { \l__coffin_y_dim }
21487       \__coffin_display_attach:Nnnnn
21488       \l__coffin_display_pole_coffin { hc } { vc }
21489       { Opt } { Opt }
21490       \hcoffin_set:Nn \l__coffin_display_coord_coffin
21491       {
21492         \*initex
21493         % TODO
21494       }
21495     }
21496     \*package
21497     \color {#6}

```

```

21497 \end{package}
21498 \l__coffin_display_font_tl
21499 ( \tl_to_str:n { #1 , ##1 } )
21500 }
21501 \prop_get:NnN \l__coffin_display_handles_prop
21502 { #1 ##1 } \l__coffin_internal_tl
21503 \quark_if_no_value:NTF \l__coffin_internal_tl
21504 {
21505   \prop_get:NnN \l__coffin_display_handles_prop
21506   { ##1 #1 } \l__coffin_internal_tl
21507   \quark_if_no_value:NTF \l__coffin_internal_tl
21508   {
21509     \__coffin_display_attach:Nnnnn
21510     \l__coffin_display_coord_coffin { 1 } { vc }
21511     { 1pt } { 0pt }
21512   }
21513   {
21514     \exp_last_unbraced:No
21515     \__coffin_display_handles_aux:nnnn
21516     \l__coffin_internal_tl
21517   }
21518 }
21519 {
21520   \exp_last_unbraced:No \__coffin_display_handles_aux:nnnn
21521   \l__coffin_internal_tl
21522 }
21523 }
21524 }
21525 }
21526 \cs_new_protected:Npn \__coffin_display_handles_aux:nnnn #1#2#3#4
21527 {
21528   \__coffin_display_attach:Nnnnn
21529   \l__coffin_display_coord_coffin {#1} {#2}
21530   { #3 \l__coffin_display_offset_dim }
21531   { #4 \l__coffin_display_offset_dim }
21532 }
21533 \cs_generate_variant:Nn \coffin_display_handles:Nn { c }

```

This is a dedicated version of `\coffin_attach:NnnNnnnn` with a hard-wired first coffin. As the intersection is already known and stored for the display coffin the code simply uses it directly, with no calculation.

```

21534 \cs_new_protected:Npn \__coffin_display_attach:Nnnnn #1#2#3#4#5
21535 {
21536   \__coffin_calculate_intersection:Nnn #1 {#2} {#3}
21537   \dim_set:Nn \l__coffin_x_prime_dim { \l__coffin_x_dim }
21538   \dim_set:Nn \l__coffin_y_prime_dim { \l__coffin_y_dim }
21539   \dim_set:Nn \l__coffin_offset_x_dim
21540   { \l__coffin_display_x_dim - \l__coffin_x_prime_dim + #4 }
21541   \dim_set:Nn \l__coffin_offset_y_dim
21542   { \l__coffin_display_y_dim - \l__coffin_y_prime_dim + #5 }
21543   \hbox_set:Nn \l__coffin_aligned_coffin
21544   {
21545     \box_use:N \l__coffin_display_coffin
21546     \tex_kern:D -\box_wd:N \l__coffin_display_coffin

```

```

21547     \tex_kern:D \l__coffin_offset_x_dim
21548     \box_move_up:nn { \l__coffin_offset_y_dim } { \box_use:N #1 }
21549   }
21550   \box_set_ht:Nn \l__coffin_aligned_coffin
21551     { \box_ht:N \l__coffin_display_coffin }
21552   \box_set_dp:Nn \l__coffin_aligned_coffin
21553     { \box_dp:N \l__coffin_display_coffin }
21554   \box_set_wd:Nn \l__coffin_aligned_coffin
21555     { \box_wd:N \l__coffin_display_coffin }
21556   \box_set_eq:NN \l__coffin_display_coffin \l__coffin_aligned_coffin
21557 }

```

(End definition for `\coffin_display_handles:Nn` and others. These functions are documented on page 223.)

**`\coffin_show_structure:N`** For showing the various internal structures attached to a coffin in a way that keeps things relatively readable. If there is no apparent structure then the code complains.

**`\coffin_show_structure:c`**

```

21558 \cs_new_protected:Npn \coffin_show_structure:N #1
21559 {
21560   \__coffin_if_exist:NT #1
21561   {
21562     \__msg_show_pre:nnxxxx { LaTeX / kernel } { show-coffin }
21563     { \token_to_str:N #1 }
21564     { \dim_eval:n { \coffin_ht:N #1 } }
21565     { \dim_eval:n { \coffin_dp:N #1 } }
21566     { \dim_eval:n { \coffin_wd:N #1 } }
21567     \__msg_show_wrap:n
21568     {
21569       \prop_map_function:cN
21570         { l__coffin_poles_ \__int_value:w #1 _prop }
21571       \__msg_show_item_unbraced:nn
21572     }
21573   }
21574 }
21575 \cs_generate_variant:Nn \coffin_show_structure:N { c }

```

(End definition for `\coffin_show_structure:N`. This function is documented on page 224.)

**`\coffin_log_structure:N`** Redirect output of `\coffin_show_structure:N` to the log.

**`\coffin_log_structure:c`**

```

21576 \cs_new_protected:Npn \coffin_log_structure:N
21577 { \__msg_log_next: \coffin_show_structure:N }
21578 \cs_generate_variant:Nn \coffin_log_structure:N { c }

```

(End definition for `\coffin_log_structure:N`. This function is documented on page 224.)

## 38.8 Messages

```

21579 \__msg_kernel_new:nnnn { kernel } { no-pole-intersection }
21580 { No~intersection~between~coffin~poles. }
21581 {
21582   \c__msg_coding_error_text_tl
21583   LaTeX~was~asked~to~find~the~intersection~between~two~poles,~
21584   but~they~do~not~have~a~unique~meeting~point:~
21585   the~value~(0~pt,~0~pt)~will~be~used.
21586 }

```

```

21587 \__msg_kernel_new:nnnn { kernel } { unknown-coffin }
21588 { Unknown-coffin~'#1'. }
21589 { The-coffin~'#1'~was~never~defined. }
21590 \__msg_kernel_new:nnnn { kernel } { unknown-coffin-pole }
21591 { Pole~'#1'~unknown-for-coffin~'#2'. }
21592 {
21593   \c__msg_coding_error_text_tl
21594   LaTeX~was~asked~to~find~a~typesetting~pole~for~a~coffin,~
21595   but~either~the~coffin~does~not~exist~or~the~pole~name~is~wrong.
21596 }
21597 \__msg_kernel_new:nnn { kernel } { show-coffin }
21598 {
21599   Size-of-coffin~#1 : \
21600   > ~ ht~==~#2 \
21601   > ~ dp~==~#3 \
21602   > ~ wd~==~#4 \
21603   Poles-of-coffin~#1 :
21604 }
21605 </initex | package>

```

## 39 l3color Implementation

```

21606 <*initex | package>

```

**\color\_group\_begin:** Grouping for color is almost the same as using the basic `\group_begin:` and `\group_end:` functions. However, in vertical mode the end-of-group needs a `\par`, which in horizontal mode does nothing.

```

21607 \cs_new_eq:NN \color_group_begin: \group_begin:
21608 \cs_new_protected:Npn \color_group_end:
21609 {
21610   \par
21611   \group_end:
21612 }

```

*(End definition for \color\_group\_begin: and \color\_group\_end:. These functions are documented on page 225.)*

**\color\_ensure\_current:** A driver-independent wrapper for setting the foreground color to the current color “now”.

```

21613 \cs_new_protected:Npn \color_ensure_current:
21614 {
21615   \__driver_color_ensure_current:
21616   \group_insert_after:N \__driver_color_reset:
21617 }

```

*(End definition for \color\_ensure\_current:. This function is documented on page 225.)*

**\l\_\_color\_current\_tl** The current color: the format here is taken from dvips but it is easy enough to convert to pdfmode as required.

```

21618 \tl_new:N \l__color_current_tl
21619 \tl_set:Nn \l__color_current_tl { gray~0 }

```

*(End definition for \l\_\_color\_current\_tl.)*

```

21620 </initex | package>

```



## 40 l3sys implementation

21621  $\langle *initex | package \rangle$

### 40.1 The name of the job

$\backslash c\_sys\_jobname\_str$  Inherited from the L<sup>A</sup>T<sub>E</sub>X3 name for the primitive: this needs to actually contain the text of the job name rather than the name of the primitive, of course.

```
21622  $\langle *initex \rangle$ 
21623  $\backslash tex\_everyjob:D \exp\_after:wN$ 
21624 {
21625    $\backslash tex\_the:D \backslash tex\_everyjob:D$ 
21626    $\backslash str\_const:Nx \backslash c\_sys\_jobname\_str \{ \backslash tex\_jobname:D \}$ 
21627 }
21628  $\langle /initex \rangle$ 
21629  $\langle *package \rangle$ 
21630  $\backslash str\_const:Nx \backslash c\_sys\_jobname\_str \{ \backslash tex\_jobname:D \}$ 
21631  $\langle /package \rangle$ 
```

(End definition for  $\backslash c\_sys\_jobname\_str$ . This variable is documented on page 226.)

### 40.2 Time and date

$\backslash c\_sys\_minute\_int$  Copies of the information provided by T<sub>E</sub>X  
 $\backslash c\_sys\_hour\_int$  21632  $\backslash int\_const:Nn \backslash c\_sys\_minute\_int$   
 $\backslash c\_sys\_day\_int$  21633 {  $\backslash int\_mod:nn \{ \backslash tex\_time:D \} \{ 60 \} \}$   
 $\backslash c\_sys\_month\_int$  21634  $\backslash int\_const:Nn \backslash c\_sys\_hour\_int$   
 $\backslash c\_sys\_year\_int$  21635 {  $\backslash int\_div\_truncate:nn \{ \backslash tex\_time:D \} \{ 60 \} \}$   
21636  $\backslash int\_const:Nn \backslash c\_sys\_day\_int \{ \backslash tex\_day:D \}$   
21637  $\backslash int\_const:Nn \backslash c\_sys\_month\_int \{ \backslash tex\_month:D \}$   
21638  $\backslash int\_const:Nn \backslash c\_sys\_year\_int \{ \backslash tex\_year:D \}$

(End definition for  $\backslash c\_sys\_minute\_int$  and others. These variables are documented on page 226.)

### 40.3 Detecting the engine

$\backslash sys\_if\_engine\_luatex\_p:$  Set up the engine tests on the basis exactly one test should be true. Mainly a case of  
 $\backslash sys\_if\_engine\_luatex:TF$  looking for the appropriate marker primitive. For upT<sub>E</sub>X, there is a complexity in that  
 $\backslash sys\_if\_engine\_pdftex\_p:$  setting  $-kanji\_internal=sjis$  or  $-kanji\_internal=euc$  effective makes it more like  
 $\backslash sys\_if\_engine\_pdftex:TF$  pT<sub>E</sub>X. In those cases we therefore report pT<sub>E</sub>X rather than upT<sub>E</sub>X.

```
\sys_if_engine_ptex_p: 21639  $\backslash clist\_map\_inline:nn \{ lua , pdf , p , up , xe \}$ 
\sys_if_engine_ptex:TF 21640 {
\sys_if_engine_uptex_p: 21641    $\backslash cs\_new\_eq:cN \{ sys\_if\_engine\_ \#1 tex:T \} \backslash use\_none:n$ 
\sys_if_engine_uptex:TF 21642    $\backslash cs\_new\_eq:cN \{ sys\_if\_engine\_ \#1 tex:F \} \backslash use:n$ 
\sys_if_engine_xetex_p: 21643    $\backslash cs\_new\_eq:cN \{ sys\_if\_engine\_ \#1 tex:TF \} \backslash use\_ii:nn$ 
\sys_if_engine_xetex:TF 21644    $\backslash cs\_new\_eq:cN \{ sys\_if\_engine\_ \#1 tex:p: \} \backslash c\_false\_bool$ 
\c_sys_engine_str      21645 }
21646  $\backslash cs\_if\_exist:NT \backslash luatex\_luatexversion:D$ 
21647 {
21648    $\backslash cs\_gset\_eq:NN \backslash sys\_if\_engine\_luatex:T \backslash use:n$ 
21649    $\backslash cs\_gset\_eq:NN \backslash sys\_if\_engine\_luatex:F \backslash use\_none:n$ 
21650    $\backslash cs\_gset\_eq:NN \backslash sys\_if\_engine\_luatex:TF \backslash use\_i:nn$ 
21651    $\backslash cs\_gset\_eq:NN \backslash sys\_if\_engine\_luatex:p: \backslash c\_true\_bool$ 
21652    $\backslash str\_const:Nn \backslash c\_sys\_engine\_str \{ luatex \}$ 
```

```

21653 }
21654 \cs_if_exist:NT \pdfTeX_pdftexversion:D
21655 {
21656   \cs_gset_eq:NN \sys_if_engine_pdftex:T \use:n
21657   \cs_gset_eq:NN \sys_if_engine_pdftex:F \use_none:n
21658   \cs_gset_eq:NN \sys_if_engine_pdftex:TF \use_i:nn
21659   \cs_gset_eq:NN \sys_if_engine_pdftex_p: \c_true_bool
21660   \str_const:Nn \c_sys_engine_str { pdftex }
21661 }
21662 \cs_if_exist:NT \ptex_kanjiskip:D
21663 {
21664   \bool_lazy_and:nnTF
21665   { \cs_if_exist_p:N \uptex_disablecjktoken:D }
21666   { \int_compare_p:nNn { \ptex_jis:D "2121 } = { "3000 } }
21667   {
21668     \cs_gset_eq:NN \sys_if_engine_uptex:T \use:n
21669     \cs_gset_eq:NN \sys_if_engine_uptex:F \use_none:n
21670     \cs_gset_eq:NN \sys_if_engine_uptex:TF \use_i:nn
21671     \cs_gset_eq:NN \sys_if_engine_uptex_p: \c_true_bool
21672     \str_const:Nn \c_sys_engine_str { uptex }
21673   }
21674   {
21675     \cs_gset_eq:NN \sys_if_engine_ptex:T \use:n
21676     \cs_gset_eq:NN \sys_if_engine_ptex:F \use_none:n
21677     \cs_gset_eq:NN \sys_if_engine_ptex:TF \use_i:nn
21678     \cs_gset_eq:NN \sys_if_engine_ptex_p: \c_true_bool
21679     \str_const:Nn \c_sys_engine_str { ptex }
21680   }
21681 }
21682 \cs_if_exist:NT \xetex_XeTeXversion:D
21683 {
21684   \cs_gset_eq:NN \sys_if_engine_xetex:T \use:n
21685   \cs_gset_eq:NN \sys_if_engine_xetex:F \use_none:n
21686   \cs_gset_eq:NN \sys_if_engine_xetex:TF \use_i:nn
21687   \cs_gset_eq:NN \sys_if_engine_xetex_p: \c_true_bool
21688   \str_const:Nn \c_sys_engine_str { xetex }
21689 }

```

(End definition for `\sys_if_engine luatex:TF` and others. These functions are documented on page 226.)

## 40.4 Detecting the output

`\sys_if_output_dvi_p:` This is a simple enough concept: the two views here are complementary.

```

\sys_if_output_dvi:TF 21690 \int_compare:nNnTF
\sys_if_output_pdf_p: 21691 { \cs_if_exist_use:NF \pdfTeX_pdfoutput:D { 0 } } > { 0 }
\sys_if_output_pdf:TF 21692 {
  \c_sys_output_str 21693 \cs_new_eq:NN \sys_if_output_dvi:T \use_none:n
21694 \cs_new_eq:NN \sys_if_output_dvi:F \use:n
21695 \cs_new_eq:NN \sys_if_output_dvi:TF \use_ii:nn
21696 \cs_new_eq:NN \sys_if_output_dvi_p: \c_false_bool
21697 \cs_new_eq:NN \sys_if_output_pdf:T \use:n
21698 \cs_new_eq:NN \sys_if_output_pdf:F \use_none:n
21699 \cs_new_eq:NN \sys_if_output_pdf:TF \use_i:nn

```

```

21700 \cs_new_eq:NN \sys_if_output_pdf_p: \c_true_bool
21701 \str_const:Nn \c_sys_output_str { pdf }
21702 }
21703 {
21704 \cs_new_eq:NN \sys_if_output_dvi:T \use:n
21705 \cs_new_eq:NN \sys_if_output_dvi:F \use_none:n
21706 \cs_new_eq:NN \sys_if_output_dvi:TF \use_i:nn
21707 \cs_new_eq:NN \sys_if_output_dvi_p: \c_true_bool
21708 \cs_new_eq:NN \sys_if_output_pdf:T \use_none:n
21709 \cs_new_eq:NN \sys_if_output_pdf:F \use:n
21710 \cs_new_eq:NN \sys_if_output_pdf:TF \use_ii:nn
21711 \cs_new_eq:NN \sys_if_output_pdf_p: \c_false_bool
21712 \str_const:Nn \c_sys_output_str { dvi }
21713 }

```

(End definition for `\sys_if_output_dvi:TF`, `\sys_if_output_pdf:TF`, and `\c_sys_output_str`. These functions are documented on page 227.)

```

21714 </initex | package>

```

## 41 l3deprecation implementation

```

21715 <*initex | package>
21716 <@@=deprecation>

```

`\__deprecation_error:Nnn` The `\outer` definition here ensures the command cannot appear in an argument. Use this auxiliary on all commands that have been removed since 2015.

```

21717 \cs_new_protected:Npn \__deprecation_error:Nnn #1#2#3
21718 {
21719 \etex_protected:D \tex_outer:D \tex_edef:D #1
21720 {
21721 \exp_not:N \__msg_kernel_expandable_error:nnnnn
21722 { kernel } { deprecated-command }
21723 { \tl_to_str:n {#3} } { \token_to_str:N #1 } { \tl_to_str:n {#2} }
21724 \exp_not:N \__msg_kernel_error:nnxxx
21725 { kernel } { deprecated-command }
21726 { \tl_to_str:n {#3} } { \token_to_str:N #1 } { \tl_to_str:n {#2} }
21727 }
21728 }
21729 \__deprecation_error:Nnn \c_job_name_tl { \c_sys_jobname_str } { 2017-01-01 }
21730 \__deprecation_error:Nnn \dim_case:nnn { \dim_case:nnF } { 2015-07-14 }
21731 \__deprecation_error:Nnn \int_case:nnn { \int_case:nnF } { 2015-07-14 }
21732 \__deprecation_error:Nnn \int_from_binary:n { \int_from_bin:n } { 2016-01-05 }
21733 \__deprecation_error:Nnn \int_from_hexadecimal:n { \int_from_hex:n } { 2016-01-05 }
21734 \__deprecation_error:Nnn \int_from_octal:n { \int_from_oct:n } { 2016-01-05 }
21735 \__deprecation_error:Nnn \int_to_binary:n { \int_to_bin:n } { 2016-01-05 }
21736 \__deprecation_error:Nnn \int_to_hexadecimal:n { \int_to_hex:n } { 2016-01-05 }
21737 \__deprecation_error:Nnn \int_to_octal:n { \int_to_oct:n } { 2016-01-05 }
21738 \__deprecation_error:Nnn \luatex_if_engine_p: { \sys_if_engine luatex_p: } { 2017-01-01 }
21739 \__deprecation_error:Nnn \luatex_if_engine:F { \sys_if_engine luatex:F } { 2017-01-01 }
21740 \__deprecation_error:Nnn \luatex_if_engine:T { \sys_if_engine luatex:T } { 2017-01-01 }
21741 \__deprecation_error:Nnn \luatex_if_engine:TF { \sys_if_engine luatex:TF } { 2017-01-01 }
21742 \__deprecation_error:Nnn \pdfTeX_if_engine_p: { \sys_if_engine pdfTeX_p: } { 2017-01-01 }
21743 \__deprecation_error:Nnn \pdfTeX_if_engine:F { \sys_if_engine pdfTeX:F } { 2017-01-01 }

```

```

21744 \__deprecation_error:Nnn \pdfTeX_if_engine:T { \sys_if_engine_pdfTeX:T } { 2017-01-01 }
21745 \__deprecation_error:Nnn \pdfTeX_if_engine:TF { \sys_if_engine_pdfTeX:TF } { 2017-01-01 }
21746 \__deprecation_error:Nnn \prop_get:cn { \prop_item:cn } { 2016-01-05 }
21747 \__deprecation_error:Nnn \prop_get:Nn { \prop_item:Nn } { 2016-01-05 }
21748 \__deprecation_error:Nnn \quark_if_recursion_tail_break:N { } { 2015-07-14 }
21749 \__deprecation_error:Nnn \quark_if_recursion_tail_break:n { } { 2015-07-14 }
21750 \__deprecation_error:Nnn \scan_align_safe_stop: { protected-commands } { 2017-01-01 }
21751 \__deprecation_error:Nnn \str_case:nnn { \str_case:nnF } { 2015-07-14 }
21752 \__deprecation_error:Nnn \str_case:onnn { \str_case:onF } { 2015-07-14 }
21753 \__deprecation_error:Nnn \str_case:x:nnn { \str_case:x:nnF } { 2015-07-14 }
21754 \__deprecation_error:Nnn \tl_case:cnn { \tl_case:cnF } { 2015-07-14 }
21755 \__deprecation_error:Nnn \tl_case:Nnn { \tl_case:NnF } { 2015-07-14 }
21756 \__deprecation_error:Nnn \xetex_if_engine_p: { \sys_if_engine_xetex_p: } { 2017-01-01 }
21757 \__deprecation_error:Nnn \xetex_if_engine:F { \sys_if_engine_xetex:F } { 2017-01-01 }
21758 \__deprecation_error:Nnn \xetex_if_engine:T { \sys_if_engine_xetex:T } { 2017-01-01 }
21759 \__deprecation_error:Nnn \xetex_if_engine:TF { \sys_if_engine_xetex:TF } { 2017-01-01 }

```

(End definition for \\_\_deprecation\_error:Nnn.)

**\deprecation\_error:** Some commands were more recently deprecated and not yet removed; only make these into errors if the user requests it. This allows testing code even if it relies on other packages: load all other packages, call `\deprecation_error:`, and load the code that one is interested in testing.

One of the deprecated syntaxes is within floating point expressions; to keep related code in the same place we define in `l3fp-parse` a version of `\__fp_parse_round:Nw` producing an error.

```

21760 \cs_new_protected:Npn \deprecation_error:
21761 {
21762   \__deprecation_error:Nnn \tl_to_lowercase:n { } { 2017-12-31 }
21763   \__deprecation_error:Nnn \tl_to_uppercase:n { } { 2017-12-31 }
21764   \__deprecation_error:Nnn \ior_get_str:NN { \ior_str_get:NN } { 2017-12-31 }
21765   \__deprecation_error:Nnn \box_resize:Nnn { \box_resize_to_wd_and_ht_plus_dp:Nnn } { 2017-12-31 }
21766   \__deprecation_error:Nnn \box_resize:cnn { \box_resize_to_wd_and_ht_plus_dp:cnn } { 2017-12-31 }
21767   \__deprecation_error:Nnn \c_minus_one { - 1 } { 2018-12-31 }
21768   \__deprecation_error:Nnn \sort_ordered: { \sort_return_same: } { 2018-12-31 }
21769   \__deprecation_error:Nnn \sort_reversed: { \sort_return_swapped: } { 2018-12-31 }
21770   \__deprecation_error:Nnn \g_file_current_name_tl { \g_file_curr_name_str } { 2018-12-31 }
21771   \__deprecation_error:Nnn \file_add_path:nN { \file_get_full_name:nN } { 2018-12-31 }
21772   \__deprecation_error:Nnn \file_path_include:n
21773     { \seq_put_right:Nn \l_file_search_path_seq } { 2018-12-31 }
21774   \__deprecation_error:Nnn \file_path_remove:n
21775     { \seq_remove_all:Nn \l_file_search_path_seq } { 2018-12-31 }
21776   \__deprecation_error:Nnn \file_list: { \file_log_list: } { 2018-12-31 }
21777   \__deprecation_error:Nnn \ior_list_streams: { \ior_show_list: } { 2018-12-31 }
21778   \__deprecation_error:Nnn \ior_log_streams: { \ior_log_list: } { 2018-12-31 }
21779   \__deprecation_error:Nnn \iow_list_streams: { \iow_show_list: } { 2018-12-31 }
21780   \__deprecation_error:Nnn \iow_log_streams: { \iow_log_list: } { 2018-12-31 }
21781   \cs_set_eq:NN \__fp_parse_round:Nw \__fp_parse_round_deprecation_error:Nw
21782   \cs_set_eq:NN \deprecation_error: \scan_stop:
21783 }

```

(End definition for \deprecation\_error:. This function is documented on page ??.)

```

21784 </initex | package>

```

## 42 l3candidates Implementation

21785  $\langle *initex | package \rangle$

### 42.1 Additions to l3basics

**$\backslash mode\_leave\_vertical$ :** The approach here is different to that used by L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> or plain T<sub>E</sub>X, which unbox a void box to force horizontal mode. That inserts the `\everypar` tokens *before* the re-inserted unboxing tokens. The approach here uses either the `\quitvmode` primitive or the equivalent protected macro. In vertical mode, the `\indent` primitive is inserted: this will switch to horizontal mode and insert `\everypar` tokens and nothing else. Unlike the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> version, the availability of  $\varepsilon$ -T<sub>E</sub>X means using a mode test can be done at for example the start of an `\halign`. The `\quitvmode` primitive essentially wraps the same code up at the engine level.

```
21786 \cs_new_protected:Npx \mode_leave_vertical:
21787 {
21788   \cs_if_exist:NTF \pdfTeX_quitvmode:D
21789   { \pdfTeX_quitvmode:D }
21790   {
21791     \exp_not:n
21792     {
21793       \if_mode_vertical:
21794         \exp_after:wN \tex_indent:D
21795       \fi:
21796     }
21797   }
21798 }
```

(End definition for `\mode_leave_vertical`:. This function is documented on page 230.)

### 42.2 Additions to l3box

21799  $\langle @@=box \rangle$

### 42.3 Viewing part of a box

**$\backslash box\_clip:N$**  A wrapper around the driver-dependent code.

```
\box_clip:c 21800 \cs_new_protected:Npn \box_clip:N #1
21801 { \hbox_set:Nn #1 { \__driver_box_use_clip:N #1 } }
21802 \cs_generate_variant:Nn \box_clip:N { c }
```

(End definition for `\box_clip:N`. This function is documented on page 230.)

**$\backslash box\_trim:Nnnnn$**  Trimming from the left- and right-hand edges of the box is easy: kern the appropriate parts off each side.

```
\box_trim:cnnnn 21803 \cs_new_protected:Npn \box_trim:Nnnnn #1#2#3#4#5
21804 {
21805   \hbox_set:Nn \l__box_internal_box
21806   {
21807     \tex_kern:D -\__dim_eval:w #2 \__dim_eval_end:
21808     \box_use:N #1
21809     \tex_kern:D -\__dim_eval:w #4 \__dim_eval_end:
21810   }
```

For the height and depth, there is a need to watch the baseline is respected. Material always has to stay on the correct side, so trimming has to check that there is enough material to trim. First, the bottom edge. If there is enough depth, simply set the depth, or if not move down so the result is zero depth. `\box_move_down:nn` is used in both cases so the resulting box always contains a `\lower` primitive. The internal box is used here as it allows safe use of `\box_set_dp:Nn`.

```

21811 \dim_compare:nNnTF { \box_dp:N #1 } > {#3}
21812 {
21813   \hbox_set:Nn \l__box_internal_box
21814   {
21815     \box_move_down:nn \c_zero_dim
21816     { \box_use:N \l__box_internal_box }
21817   }
21818   \box_set_dp:Nn \l__box_internal_box { \box_dp:N #1 - (#3) }
21819 }
21820 {
21821   \hbox_set:Nn \l__box_internal_box
21822   {
21823     \box_move_down:nn { #3 - \box_dp:N #1 }
21824     { \box_use:N \l__box_internal_box }
21825   }
21826   \box_set_dp:Nn \l__box_internal_box \c_zero_dim
21827 }

```

Same thing, this time from the top of the box.

```

21828 \dim_compare:nNnTF { \box_ht:N \l__box_internal_box } > {#5}
21829 {
21830   \hbox_set:Nn \l__box_internal_box
21831   {
21832     \box_move_up:nn \c_zero_dim
21833     { \box_use:N \l__box_internal_box }
21834   }
21835   \box_set_ht:Nn \l__box_internal_box
21836   { \box_ht:N \l__box_internal_box - (#5) }
21837 }
21838 {
21839   \hbox_set:Nn \l__box_internal_box
21840   {
21841     \box_move_up:nn { #5 - \box_ht:N \l__box_internal_box }
21842     { \box_use:N \l__box_internal_box }
21843   }
21844   \box_set_ht:Nn \l__box_internal_box \c_zero_dim
21845 }
21846 \box_set_eq:NN #1 \l__box_internal_box
21847 }
21848 \cs_generate_variant:Nn \box_trim:Nnnnn { c }

```

(End definition for `\box_trim:Nnnnn`. This function is documented on page 230.)

**`\box_viewport:Nnnnn`**  
**`\box_viewport:cnnnn`**

The same general logic as for the trim operation, but with absolute dimensions. As a result, there are some things to watch out for in the vertical direction.

```

21849 \cs_new_protected:Npn \box_viewport:Nnnnn #1#2#3#4#5
21850 {
21851   \hbox_set:Nn \l__box_internal_box

```

```

21852     {
21853       \tex_kern:D -\__dim_eval:w #2 \__dim_eval_end:
21854       \box_use:N #1
21855       \tex_kern:D \__dim_eval:w #4 - \box_wd:N #1 \__dim_eval_end:
21856     }
21857 \dim_compare:nNnTF {#3} < \c_zero_dim
21858 {
21859   \hbox_set:Nn \l__box_internal_box
21860   {
21861     \box_move_down:nn \c_zero_dim
21862     { \box_use:N \l__box_internal_box }
21863   }
21864   \box_set_dp:Nn \l__box_internal_box { -\dim_eval:n {#3} }
21865 }
21866 {
21867   \hbox_set:Nn \l__box_internal_box
21868   { \box_move_down:nn {#3} { \box_use:N \l__box_internal_box } }
21869   \box_set_dp:Nn \l__box_internal_box \c_zero_dim
21870 }
21871 \dim_compare:nNnTF {#5} > \c_zero_dim
21872 {
21873   \hbox_set:Nn \l__box_internal_box
21874   {
21875     \box_move_up:nn \c_zero_dim
21876     { \box_use:N \l__box_internal_box }
21877   }
21878   \box_set_ht:Nn \l__box_internal_box
21879   {
21880     #5
21881     \dim_compare:nNnT {#3} > \c_zero_dim
21882     { - (#3) }
21883   }
21884 }
21885 {
21886   \hbox_set:Nn \l__box_internal_box
21887   {
21888     \box_move_up:nn { -\dim_eval:n {#5} }
21889     { \box_use:N \l__box_internal_box }
21890   }
21891   \box_set_ht:Nn \l__box_internal_box \c_zero_dim
21892 }
21893 \box_set_eq:NN #1 \l__box_internal_box
21894 }
21895 \cs_generate_variant:Nn \box_viewport:Nnnnn { c }

```

(End definition for `\box_viewport:Nnnnn`. This function is documented on page 230.)

## 42.4 Additions to `l3clist`

21896 `<@@=clist>`

`\clist_rand_item:n` The N-type function is not implemented through the n-type function for efficiency: for instance comma-list variables do not require space-trimming of their items. Even testing for emptiness of an n-type comma-list is slow, so we count items first and use that both

`\clist_rand_item:N`

`\clist_rand_item:c`

`\__clist_rand_item:nn`

for the emptiness test and the pseudo-random integer. Importantly, `\clist_item:Nn` and `\clist_item:nn` only evaluate their argument once.

```

21897 \cs_new:Npn \clist_rand_item:n #1
21898 { \exp_args:Nf \__clist_rand_item:nn { \clist_count:n {#1} } {#1} }
21899 \cs_new:Npn \__clist_rand_item:nn #1#2
21900 {
21901   \int_compare:nNf {#1} = 0
21902   { \clist_item:nn {#2} { \int_rand:nn { 1 } {#1} } }
21903 }
21904 \cs_new:Npn \clist_rand_item:N #1
21905 {
21906   \clist_if_empty:NF #1
21907   { \clist_item:Nn #1 { \int_rand:nn { 1 } { \clist_count:N #1 } } }
21908 }
21909 \cs_generate_variant:Nn \clist_rand_item:N { c }

```

(End definition for `\clist_rand_item:n`, `\clist_rand_item:N`, and `\__clist_rand_item:nn`. These functions are documented on page 231.)

## 42.5 Additions to l3coffins

21910 `<@@=coffin>`

## 42.6 Rotating coffins

`\l__coffin_sin_fp` Used for rotations to get the sine and cosine values.

`\l__coffin_cos_fp` 21911 `\fp_new:N \l__coffin_sin_fp`  
 21912 `\fp_new:N \l__coffin_cos_fp`

(End definition for `\l__coffin_sin_fp` and `\l__coffin_cos_fp`.)

`\l__coffin_bounding_prop` A property list for the bounding box of a coffin. This is only needed during the rotation, so there is just the one.

21913 `\prop_new:N \l__coffin_bounding_prop`

(End definition for `\l__coffin_bounding_prop`.)

`\l__coffin_bounding_shift_dim` The shift of the bounding box of a coffin from the real content.

21914 `\dim_new:N \l__coffin_bounding_shift_dim`

(End definition for `\l__coffin_bounding_shift_dim`.)

`\l__coffin_left_corner_dim` These are used to hold maxima for the various corner values: these thus define the minimum size of the bounding box after rotation.

`\l__coffin_right_corner_dim` 21915 `\dim_new:N \l__coffin_left_corner_dim`  
`\l__coffin_bottom_corner_dim` 21916 `\dim_new:N \l__coffin_right_corner_dim`  
`\l__coffin_top_corner_dim` 21917 `\dim_new:N \l__coffin_bottom_corner_dim`  
 21918 `\dim_new:N \l__coffin_top_corner_dim`

(End definition for `\l__coffin_left_corner_dim` and others.)



`\coffin_rotate:Nn` Rotating a coffin requires several steps which can be conveniently run together. The sine and cosine of the angle in degrees are computed. This is then used to set `\l__coffin_sin_fp` and `\l__coffin_cos_fp`, which are carried through unchanged for the rest of the procedure.

```

21919 \cs_new_protected:Npn \coffin_rotate:Nn #1#2
21920 {
21921   \fp_set:Nn \l__coffin_sin_fp { sind ( #2 ) }
21922   \fp_set:Nn \l__coffin_cos_fp { cosd ( #2 ) }

```

The corners and poles of the coffin can now be rotated around the origin. This is best achieved using mapping functions.

```

21923   \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
21924   { \__coffin_rotate_corner:Nnnn #1 {##1} ##2 }
21925   \prop_map_inline:cn { l__coffin_poles_ \__int_value:w #1 _prop }
21926   { \__coffin_rotate_pole:Nnnnn #1 {##1} ##2 }

```

The bounding box of the coffin needs to be rotated, and to do this the corners have to be found first. They are then rotated in the same way as the corners of the coffin material itself.

```

21927   \__coffin_set_bounding:N #1
21928   \prop_map_inline:Nn \l__coffin_bounding_prop
21929   { \__coffin_rotate_bounding:nnn {##1} ##2 }

```

At this stage, there needs to be a calculation to find where the corners of the content and the box itself will end up.

```

21930   \__coffin_find_corner_maxima:N #1
21931   \__coffin_find_bounding_shift:
21932   \box_rotate:Nn #1 {#2}

```

The correction of the box position itself takes place here. The idea is that the bounding box for a coffin is tight up to the content, and has the reference point at the bottom-left. The  $x$ -direction is handled by moving the content by the difference in the positions of the bounding box and the content left edge. The  $y$ -direction is dealt with by moving the box down by any depth it has acquired. The internal box is used here to allow for the next step.

```

21933   \hbox_set:Nn \l__coffin_internal_box
21934   {
21935     \tex_kern:D
21936     \__dim_eval:w
21937     \l__coffin_bounding_shift_dim - \l__coffin_left_corner_dim
21938     \__dim_eval_end:
21939     \box_move_down:nn { \l__coffin_bottom_corner_dim }
21940     { \box_use:N #1 }
21941   }

```

If there have been any previous rotations then the size of the bounding box will be bigger than the contents. This can be corrected easily by setting the size of the box to the height and width of the content. As this operation requires setting box dimensions and these transcend grouping, the safe way to do this is to use the internal box and to reset the result into the target box.

```

21942   \box_set_ht:Nn \l__coffin_internal_box
21943   { \l__coffin_top_corner_dim - \l__coffin_bottom_corner_dim }
21944   \box_set_dp:Nn \l__coffin_internal_box { 0 pt }
21945   \box_set_wd:Nn \l__coffin_internal_box

```

```

21946      { \l__coffin_right_corner_dim - \l__coffin_left_corner_dim }
21947      \hbox_set:Nn #1 { \box_use:N \l__coffin_internal_box }

```

The final task is to move the poles and corners such that they are back in alignment with the box reference point.

```

21948      \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
21949      { \__coffin_shift_corner:Nnnn #1 {##1} ##2 }
21950      \prop_map_inline:cn { l__coffin_poles_ \__int_value:w #1 _prop }
21951      { \__coffin_shift_pole:Nnnnnn #1 {##1} ##2 }
21952    }
21953    \cs_generate_variant:Nn \coffin_rotate:Nn { c }

```

(End definition for \coffin\_rotate:Nn. This function is documented on page 231.)

\\_\_coffin\_set\_bounding:N The bounding box corners for a coffin are easy enough to find: this is the same code as for the corners of the material itself, but using a dedicated property list.

```

21954    \cs_new_protected:Npn \__coffin_set_bounding:N #1
21955    {
21956      \prop_put:Nnx \l__coffin_bounding_prop { tl }
21957      { { 0 pt } { \dim_eval:n { \box_ht:N #1 } } }
21958      \prop_put:Nnx \l__coffin_bounding_prop { tr }
21959      { { \dim_eval:n { \box_wd:N #1 } } { \dim_eval:n { \box_ht:N #1 } } }
21960      \dim_set:Nn \l__coffin_internal_dim { -\box_dp:N #1 }
21961      \prop_put:Nnx \l__coffin_bounding_prop { bl }
21962      { { 0 pt } { \dim_use:N \l__coffin_internal_dim } }
21963      \prop_put:Nnx \l__coffin_bounding_prop { br }
21964      { { \dim_eval:n { \box_wd:N #1 } } { \dim_use:N \l__coffin_internal_dim } }
21965    }

```

(End definition for \\_\_coffin\_set\_bounding:N.)

\\_\_coffin\_rotate\_bounding:nnn Rotating the position of the corner of the coffin is just a case of treating this as a vector from the reference point. The same treatment is used for the corners of the material itself and the bounding box.

```

21966    \cs_new_protected:Npn \__coffin_rotate_bounding:nnn #1#2#3
21967    {
21968      \__coffin_rotate_vector:nnNN {#2} {#3} \l__coffin_x_dim \l__coffin_y_dim
21969      \prop_put:Nnx \l__coffin_bounding_prop {#1}
21970      { { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim } }
21971    }
21972    \cs_new_protected:Npn \__coffin_rotate_corner:Nnnn #1#2#3#4
21973    {
21974      \__coffin_rotate_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
21975      \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } {#2}
21976      { { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim } }
21977    }

```

(End definition for \\_\_coffin\_rotate\_bounding:nnn and \\_\_coffin\_rotate\_corner:Nnnn.)

\\_\_coffin\_rotate\_pole:Nnnnnn Rotating a single pole simply means shifting the co-ordinate of the pole and its direction. The rotation here is about the bottom-left corner of the coffin.

```

21978    \cs_new_protected:Npn \__coffin_rotate_pole:Nnnnnn #1#2#3#4#5#6
21979    {
21980      \__coffin_rotate_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
21981      \__coffin_rotate_vector:nnNN {#5} {#6}

```

```

21982     \l__coffin_x_prime_dim \l__coffin_y_prime_dim
21983     \__coffin_set_pole:Nnx #1 {#2}
21984     {
21985         { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
21986         { \dim_use:N \l__coffin_x_prime_dim }
21987         { \dim_use:N \l__coffin_y_prime_dim }
21988     }
21989 }

```

(End definition for \\_\_coffin\_rotate\_pole:Nnnnnn.)

\\_\_coffin\_rotate\_vector:nnNN A rotation function, which needs only an input vector (as dimensions) and an output space. The values \l\_\_coffin\_cos\_fp and \l\_\_coffin\_sin\_fp should previously have been set up correctly. Working this way means that the floating point work is kept to a minimum: for any given rotation the sin and cosine values do no change, after all.

```

21990 \cs_new_protected:Npn \__coffin_rotate_vector:nnNN #1#2#3#4
21991 {
21992     \dim_set:Nn #3
21993     {
21994         \fp_to_dim:n
21995         {
21996             \dim_to_fp:n {#1} * \l__coffin_cos_fp
21997             - \dim_to_fp:n {#2} * \l__coffin_sin_fp
21998         }
21999     }
22000     \dim_set:Nn #4
22001     {
22002         \fp_to_dim:n
22003         {
22004             \dim_to_fp:n {#1} * \l__coffin_sin_fp
22005             + \dim_to_fp:n {#2} * \l__coffin_cos_fp
22006         }
22007     }
22008 }

```

(End definition for \\_\_coffin\_rotate\_vector:nnNN.)

\\_\_coffin\_find\_corner\_maxima:N The idea here is to find the extremities of the content of the coffin. This is done by looking for the smallest values for the bottom and left corners, and the largest values for the top and right corners. The values start at the maximum dimensions so that the case where all are positive or all are negative works out correctly.

\\_\_coffin\_find\_corner\_maxima\_aux:nn

```

22009 \cs_new_protected:Npn \__coffin_find_corner_maxima:N #1
22010 {
22011     \dim_set:Nn \l__coffin_top_corner_dim { -\c_max_dim }
22012     \dim_set:Nn \l__coffin_right_corner_dim { -\c_max_dim }
22013     \dim_set:Nn \l__coffin_bottom_corner_dim { \c_max_dim }
22014     \dim_set:Nn \l__coffin_left_corner_dim { \c_max_dim }
22015     \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
22016     { \__coffin_find_corner_maxima_aux:nn ##2 }
22017 }
22018 \cs_new_protected:Npn \__coffin_find_corner_maxima_aux:nn #1#2
22019 {
22020     \dim_set:Nn \l__coffin_left_corner_dim
22021     { \dim_min:nn { \l__coffin_left_corner_dim } {#1} }

```

```

22022 \dim_set:Nn \l__coffin_right_corner_dim
22023 { \dim_max:nn { \l__coffin_right_corner_dim } {#1} }
22024 \dim_set:Nn \l__coffin_bottom_corner_dim
22025 { \dim_min:nn { \l__coffin_bottom_corner_dim } {#2} }
22026 \dim_set:Nn \l__coffin_top_corner_dim
22027 { \dim_max:nn { \l__coffin_top_corner_dim } {#2} }
22028 }

```

(End definition for `\__coffin_find_corner_maxima:N` and `\__coffin_find_corner_maxima_aux:nn`.)

`\__coffin_find_bounding_shift:`  
`\__coffin_find_bounding_shift_aux:nn`

The approach to finding the shift for the bounding box is similar to that for the corners. However, there is only one value needed here and a fixed input property list, so things are a bit clearer.

```

22029 \cs_new_protected:Npn \__coffin_find_bounding_shift:
22030 {
22031   \dim_set:Nn \l__coffin_bounding_shift_dim { \c_max_dim }
22032   \prop_map_inline:Nn \l__coffin_bounding_prop
22033     { \__coffin_find_bounding_shift_aux:nn ##2 }
22034 }
22035 \cs_new_protected:Npn \__coffin_find_bounding_shift_aux:nn #1#2
22036 {
22037   \dim_set:Nn \l__coffin_bounding_shift_dim
22038     { \dim_min:nn { \l__coffin_bounding_shift_dim } {#1} }
22039 }

```

(End definition for `\__coffin_find_bounding_shift:` and `\__coffin_find_bounding_shift_aux:nn`.)

`\__coffin_shift_corner:Nnnn`  
`\__coffin_shift_pole:Nnnnnn`

Shifting the corners and poles of a coffin means subtracting the appropriate values from the  $x$ - and  $y$ -components. For the poles, this means that the direction vector is unchanged.

```

22040 \cs_new_protected:Npn \__coffin_shift_corner:Nnnn #1#2#3#4
22041 {
22042   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _ prop } {#2}
22043   {
22044     { \dim_eval:n { #3 - \l__coffin_left_corner_dim } }
22045     { \dim_eval:n { #4 - \l__coffin_bottom_corner_dim } }
22046   }
22047 }
22048 \cs_new_protected:Npn \__coffin_shift_pole:Nnnnnn #1#2#3#4#5#6
22049 {
22050   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _ prop } {#2}
22051   {
22052     { \dim_eval:n { #3 - \l__coffin_left_corner_dim } }
22053     { \dim_eval:n { #4 - \l__coffin_bottom_corner_dim } }
22054     {#5} {#6}
22055   }
22056 }

```

(End definition for `\__coffin_shift_corner:Nnnn` and `\__coffin_shift_pole:Nnnnnn`.)

## 42.7 Resizing coffins

`\l__coffin_scale_x_fp`  
`\l__coffin_scale_y_fp`

Storage for the scaling factors in  $x$  and  $y$ , respectively.

```

22057 \fp_new:N \l__coffin_scale_x_fp
22058 \fp_new:N \l__coffin_scale_y_fp

```

(End definition for `\l__coffin_scale_x_fp` and `\l__coffin_scale_y_fp`.)

`\l__coffin_scaled_total_height_dim`  
`\l__coffin_scaled_width_dim`

When scaling, the values given have to be turned into absolute values.

```
22059 \dim_new:N \l__coffin_scaled_total_height_dim
22060 \dim_new:N \l__coffin_scaled_width_dim
```

(End definition for `\l__coffin_scaled_total_height_dim` and `\l__coffin_scaled_width_dim`.)

`\coffin_resize:Nnn`  
`\coffin_resize:cnn`

Resizing a coffin begins by setting up the user-friendly names for the dimensions of the coffin box. The new sizes are then turned into scale factor. This is the same operation as takes place for the underlying box, but that operation is grouped and so the same calculation is done here.

```
22061 \cs_new_protected:Npn \coffin_resize:Nnn #1#2#3
22062 {
22063   \fp_set:Nn \l__coffin_scale_x_fp
22064     { \dim_to_fp:n {#2} / \dim_to_fp:n { \coffin_wd:N #1 } }
22065   \fp_set:Nn \l__coffin_scale_y_fp
22066     {
22067       \dim_to_fp:n {#3}
22068       / \dim_to_fp:n { \coffin_ht:N #1 + \coffin_dp:N #1 }
22069     }
22070   \box_resize_to_wd_and_ht_plus_dp:Nnn #1 {#2} {#3}
22071   \__coffin_resize_common:Nnn #1 {#2} {#3}
22072 }
22073 \cs_generate_variant:Nn \coffin_resize:Nnn { c }
```

(End definition for `\coffin_resize:Nnn`. This function is documented on page 231.)

`\__coffin_resize_common:Nnn`

The poles and corners of the coffin are scaled to the appropriate places before actually resizing the underlying box.

```
22074 \cs_new_protected:Npn \__coffin_resize_common:Nnn #1#2#3
22075 {
22076   \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
22077     { \__coffin_scale_corner:Nnnn #1 {##1} ##2 }
22078   \prop_map_inline:cn { l__coffin_poles_ \__int_value:w #1 _prop }
22079     { \__coffin_scale_pole:Nnnnnn #1 {##1} ##2 }
```

Negative  $x$ -scaling values place the poles in the wrong location: this is corrected here.

```
22080 \fp_compare:nNnT \l__coffin_scale_x_fp < \c_zero_fp
22081 {
22082   \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
22083     { \__coffin_x_shift_corner:Nnnn #1 {##1} ##2 }
22084   \prop_map_inline:cn { l__coffin_poles_ \__int_value:w #1 _prop }
22085     { \__coffin_x_shift_pole:Nnnnnn #1 {##1} ##2 }
22086 }
22087 }
```

(End definition for `\__coffin_resize_common:Nnn`.)

`\coffin_scale:Nnn`  
`\coffin_scale:cnn`

For scaling, the opposite calculation is done to find the new dimensions for the coffin. Only the total height is needed, as this is the shift required for corners and poles. The scaling is done the T<sub>E</sub>X way as this works properly with floating point values without needing to use the `fp` module.

```
22088 \cs_new_protected:Npn \coffin_scale:Nnn #1#2#3
```

```

22089 {
22090   \fp_set:Nn \l__coffin_scale_x_fp {#2}
22091   \fp_set:Nn \l__coffin_scale_y_fp {#3}
22092   \box_scale:Nnn #1 { \l__coffin_scale_x_fp } { \l__coffin_scale_y_fp }
22093   \dim_set:Nn \l__coffin_internal_dim
22094     { \coffin_ht:N #1 + \coffin_dp:N #1 }
22095   \dim_set:Nn \l__coffin_scaled_total_height_dim
22096     { \fp_abs:n { \l__coffin_scale_y_fp } \l__coffin_internal_dim }
22097   \dim_set:Nn \l__coffin_scaled_width_dim
22098     { -\fp_abs:n { \l__coffin_scale_x_fp } \coffin_wd:N #1 }
22099   \__coffin_resize_common:Nnn #1
22100     { \l__coffin_scaled_width_dim } { \l__coffin_scaled_total_height_dim }
22101 }
22102 \cs_generate_variant:Nn \coffin_scale:Nnn { c }

```

(End definition for `\coffin_scale:Nnn`. This function is documented on page 231.)

`\__coffin_scale_vector:nnNN` This function scales a vector from the origin using the pre-set scale factors in  $x$  and  $y$ . This is a much less complex operation than rotation, and as a result the code is a lot clearer.

```

22103 \cs_new_protected:Npn \__coffin_scale_vector:nnNN #1#2#3#4
22104 {
22105   \dim_set:Nn #3
22106     { \fp_to_dim:n { \dim_to_fp:n {#1} * \l__coffin_scale_x_fp } }
22107   \dim_set:Nn #4
22108     { \fp_to_dim:n { \dim_to_fp:n {#2} * \l__coffin_scale_y_fp } }
22109 }

```

(End definition for `\__coffin_scale_vector:nnNN`.)

`\__coffin_scale_corner:Nnnn` `\__coffin_scale_pole:Nnnnnn` Scaling both corners and poles is a simple calculation using the preceding vector scaling.

```

22110 \cs_new_protected:Npn \__coffin_scale_corner:Nnnn #1#2#3#4
22111 {
22112   \__coffin_scale_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
22113   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } {#2}
22114     { { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim } }
22115 }
22116 \cs_new_protected:Npn \__coffin_scale_pole:Nnnnnn #1#2#3#4#5#6
22117 {
22118   \__coffin_scale_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
22119   \__coffin_set_pole:Nnx #1 {#2}
22120   {
22121     { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
22122     {#5} {#6}
22123   }
22124 }

```

(End definition for `\__coffin_scale_corner:Nnnn` and `\__coffin_scale_pole:Nnnnnn`.)

`\__coffin_x_shift_corner:Nnnn` `\__coffin_x_shift_pole:Nnnnnn` These functions correct for the  $x$  displacement that takes place with a negative horizontal scaling.

```

22125 \cs_new_protected:Npn \__coffin_x_shift_corner:Nnnn #1#2#3#4
22126 {
22127   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } {#2}

```

```

22128     {
22129       { \dim_eval:n { #3 + \box_wd:N #1 } } {#4}
22130     }
22131   }
22132 \cs_new_protected:Npn \__coffin_x_shift_pole:Nnnnnn #1#2#3#4#5#6
22133 {
22134   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } {#2}
22135   {
22136     { \dim_eval:n #3 + \box_wd:N #1 } {#4}
22137     {#5} {#6}
22138   }
22139 }

```

(End definition for \\_\_coffin\_x\_shift\_corner:Nnnn and \\_\_coffin\_x\_shift\_pole:Nnnnnn.)

## 42.8 Additions to l3file

22140 <@@=file>

\file\_get\_md5hash:nN These are all wrappers around the pdfTeX primitives doing the same jobs: as we want  
 \file\_get\_size:nN consistent file paths to be found, they are all set up using \file\_get\_full\_name:nN  
 \file\_get\_timestamp:nN and so are non-expandable get functions. Much of the code is repetitive but we need  
 \\_\_file\_get\_details:nnN to branch for LuaTeX (emulation in Lua), for the slightly different syntax needed for  
 \pdfTEX\_md5sum:D and for the fact that primitive coverage varies in other engines.

```

22141 \cs_new_protected:Npn \file_get_md5hash:nN #1#2
22142 { \__file_get_details:nnN {#1} { md5sum } {#2} }
22143 \cs_new_protected:Npn \file_get_size:nN #1#2
22144 { \__file_get_details:nnN {#1} { size } {#2} }
22145 \cs_new_protected:Npn \file_get_timestamp:nN #1#2
22146 { \__file_get_details:nnN {#1} { moddate } {#2} }
22147 \cs_new_protected:Npn \__file_get_details:nnN #1#2#3
22148 {
22149   \file_get_full_name:nN {#1} \l__file_full_name_str
22150   \str_set:Nx #3
22151   {
22152     \use:c { pdfTEX_file #2 :D } \exp_after:wN
22153     { \l__file_full_name_str }
22154   }
22155 }
22156 \cs_if_exist:NTF \luatex_directlua:D
22157 {
22158   \cs_set_protected:Npn \__file_get_details:nnN #1#2#3
22159   {
22160     \file_get_full_name:nN {#1} \l__file_full_name_str
22161     \str_set:Nx #3
22162     {
22163       \lua_now_x:n
22164       {
22165         l3kernel.file#2
22166         ( " \lua_escape_x:n { \l__file_full_name_str } " )
22167       }
22168     }
22169   }
22170 }

```

```

22171 {
22172   \cs_set_protected:Npn \file_get_md5five_hash:nN #1#2
22173   {
22174     \file_get_full_name:nN {#1} \l__file_full_name_str
22175     \tl_set:Nx #2
22176     {
22177       \pdfTeX_md5fivesum:D file \exp_after:wN
22178       { \l__file_full_name_str }
22179     }
22180   }
22181   \cs_if_exist:NT \xetex_XeTeXversion:D
22182   {
22183     \cs_set_protected:Npn \__file_get_details:nnN #1#2#3
22184     {
22185       \tl_clear:N #3
22186       \__msg_kernel_error:nnx
22187       { kernel } { xetex-primitive-not-available }
22188       { \exp_not:c { pdfFile #2 } }
22189     }
22190   }
22191 }
22192 \__msg_kernel_new:nnnn { kernel } { xetex-primitive-not-available }
22193 { Primitive~\token_to_str:N #1 not~available }
22194 {
22195   XeTeX~does~not~currently~provide~functionality~equivalent~to~the~
22196   \token_to_str:N #1 primitive.
22197 }

```

(End definition for `\file_get_md5five_hash:nN` and others. These functions are documented on page 231.)

`\file_if_exist_input:nTF` Input of a file with a test for existence cannot be done the usual way as the tokens to insert are in an odd place.

```

22198 \cs_new_protected:Npn \file_if_exist_input:n #1
22199 {
22200   \file_get_full_name:nN {#1} \l__file_full_name_str
22201   \str_if_empty:NF \l__file_full_name_str
22202   { \__file_input:V \l__file_full_name_str }
22203 }
22204 \cs_new_protected:Npn \file_if_exist_input:nT #1#2
22205 {
22206   \file_get_full_name:nN {#1} \l__file_full_name_str
22207   \str_if_empty:NF \l__file_full_name_str
22208   {
22209     #2
22210     \__file_input:V \l__file_full_name_str
22211   }
22212 }
22213 \cs_new_protected:Npn \file_if_exist_input:nF #1#2
22214 {
22215   \file_get_full_name:nN {#1} \l__file_full_name_str
22216   \str_if_empty:NTF \l__file_full_name_str
22217   {#2}
22218   { \__file_input:V \l__file_full_name_str }

```



```

22219 }
22220 \cs_new_protected:Npn \file_if_exist_input:nTF #1#2#3
22221 {
22222   \file_get_full_name:nN {#1} \l__file_full_name_str
22223   \str_if_empty:NTF \l__file_full_name_str
22224     {#3}
22225     {
22226       #2
22227       \__file_input:V \l__file_full_name_str
22228     }
22229 }

```

(End definition for `\file_if_exist_input:nTF`. This function is documented on page 232.)

**`\file_input_stop:`** A simple rename.

```

22230 \cs_new_protected:Npn \file_input_stop: { \tex_endinput:D }

```

(End definition for `\file_input_stop:`. This function is documented on page 232.)

## 42.9 Additions to `l3int`

```

22231 <@@=int>

```

**`\int_rand:nn`** Evaluate the argument and filter out the case where the lower bound #1 is more than the upper bound #2. Then determine whether the range is narrower than `\c_fp_rand_size_int`; #2-#1 may overflow for very large positive #2 and negative #1. If the range is wide, use slower code from `l3fp`. If the range is narrow, call `\__int_rand_narrow:nn`  $\{ \langle \text{choices} \rangle \}$  {#1} where  $\langle \text{choices} \rangle$  is the number of possible outcomes. Then `\__int_rand_narrow:nnnn` receives a random number reduced modulo  $\langle \text{choices} \rangle$ , the random number itself,  $\langle \text{choices} \rangle$  and #1. To avoid bias, throw away the random number if it lies in the last, incomplete, interval of size  $\langle \text{choices} \rangle$  in  $[0, \c\_fp\_rand\_size\_int - 1]$ , and try again.

```

22232 \cs_if_exist:NTF \pdfTEX_uniformdeviate:D
22233 {
22234   \cs_new:Npn \int_rand:nn #1#2
22235   {
22236     \exp_after:wN \__int_rand:ww
22237     \__int_value:w \__int_eval:w #1 \exp_after:wN ;
22238     \__int_value:w \__int_eval:w #2 ;
22239   }
22240   \cs_new:Npn \__int_rand:ww #1; #2;
22241   {
22242     \int_compare:nNnTF {#1} > {#2}
22243     {
22244       \__msg_kernel_expandable_error:nnnn
22245       { kernel } { backward-range } {#1} {#2}
22246       \__int_rand:ww #2; #1;
22247     }
22248     {
22249       \int_compare:nNnTF {#1} > 0
22250       { \int_compare:nNnTF { #2 - #1 } < \c_fp_rand_size_int }
22251       { \int_compare:nNnTF {#2} < { #1 + \c_fp_rand_size_int } }
22252       {
22253         \exp_args:Nf \__int_rand_narrow:nn

```

```

22254         { \int_eval:n { #2 - #1 + 1 } } {#1}
22255     }
22256     { \fp_to_int:n { randint(#1,#2) } }
22257 }
22258 }
22259 \cs_new:Npn \__int_rand_narrow:nn
22260 {
22261     \exp_args:No \__int_rand_narrow:nnn
22262     { \pdfTeX_uniformdeviate:D \c__fp_rand_size_int }
22263 }
22264 \cs_new:Npn \__int_rand_narrow:nnn #1#2
22265 {
22266     \exp_args:Nf \__int_rand_narrow:nnnn
22267     { \int_mod:nn {#1} {#2} } {#1} {#2}
22268 }
22269 \cs_new:Npn \__int_rand_narrow:nnnn #1#2#3#4
22270 {
22271     \int_compare:nNnTF { #2 - #1 + #3 } > \c__fp_rand_size_int
22272     { \__int_rand_narrow:nn {#3} {#4} }
22273     { \int_eval:n { #4 + #1 } }
22274 }
22275 }
22276 {
22277     \cs_new:Npn \int_rand:nn #1#2
22278     {
22279         \_msg_kernel_expandable_error:nn { kernel } { fp-no-random }
22280         \int_eval:n {#1}
22281     }
22282 }

```

(End definition for `\int_rand:nn` and others. These functions are documented on page 232.)

The following must be added to `l3msg`.

```

22283 \cs_if_exist:NT \pdfTeX_uniformdeviate:D
22284 {
22285     \_msg_kernel_new:nnn { kernel } { backward-range }
22286     { Bounds-ordered-backwards-in-\int_rand:nn {#1}~{#2}. }
22287 }

```

## 42.10 Additions to `l3msg`

```

22288 <@@=msg>

```

Pass to an auxiliary the message to display and the module name

```

\msg_expandable_error:nnnnnn
\msg_expandable_error:nnffff
\msg_expandable_error:nnnnn
\msg_expandable_error:nnfff
\msg_expandable_error:nnnn
\msg_expandable_error:nnff
\msg_expandable_error:nnn
\msg_expandable_error:nnf
\msg_expandable_error:nn
\_msg_expandable_error_module:nn
22289 \cs_new:Npn \msg_expandable_error:nnnnnn #1#2#3#4#5#6
22290 {
22291     \exp_args:Nf \_msg_expandable_error_module:nn
22292     {
22293         \exp_args:Nf \tl_to_str:n
22294         { \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6} }
22295     }
22296     {#1}
22297 }
22298 \cs_new:Npn \msg_expandable_error:nnnnn #1#2#3#4#5
22299 { \msg_expandable_error:nnnnnn {#1} {#2} {#3} {#4} {#5} { } }

```

```

22300 \cs_new:Npn \msg_expandable_error:nnnn #1#2#3#4
22301 { \msg_expandable_error:nnnnnn {#1} {#2} {#3} {#4} { } { } }
22302 \cs_new:Npn \msg_expandable_error:nnn #1#2#3
22303 { \msg_expandable_error:nnnnnn {#1} {#2} {#3} { } { } { } }
22304 \cs_new:Npn \msg_expandable_error:nn #1#2
22305 { \msg_expandable_error:nnnnnn {#1} {#2} { } { } { } { } }
22306 \cs_generate_variant:Nn \msg_expandable_error:nnnnnn { nnffff }
22307 \cs_generate_variant:Nn \msg_expandable_error:nnnnnn { nnfff }
22308 \cs_generate_variant:Nn \msg_expandable_error:nnnn { nnff }
22309 \cs_generate_variant:Nn \msg_expandable_error:nnnn { nnf }
22310 \cs_new:Npn \__msg_expandable_error_module:nn #1#2
22311 {
22312   \exp_after:wN \exp_after:wN
22313   \exp_after:wN \use_none_delimit_by_q_stop:w
22314   \use:n { \::error ! ~ #2 : ~ #1 } \q_stop
22315 }

```

(End definition for `\msg_expandable_error:nnnnnn` and others. These functions are documented on page 233.)

## 42.11 Additions to `l3prop`

```

22316 <@@=prop>

```

`\prop_count:N` Counting the key–value pairs in a property list is done using the same approach as for other count functions: turn each entry into a +1 then use integer evaluation to actually do the mathematics.

`\prop_count:c`  
`\__prop_count:nn`

```

22317 \cs_new:Npn \prop_count:N #1
22318 {
22319   \int_eval:n
22320   {
22321     0
22322     \prop_map_function:NN #1 \__prop_count:nn
22323   }
22324 }
22325 \cs_new:Npn \__prop_count:nn #1#2 { + 1 }
22326 \cs_generate_variant:Nn \prop_count:N { c }

```

(End definition for `\prop_count:N` and `\__prop_count:nn`. These functions are documented on page 233.)

`\prop_map_tokens:Nn` The mapping is very similar to `\prop_map_function:NN`. It grabs one key–value pair at a time, and stops when reaching the marker key `\q_recursion_tail`, which cannot appear in normal keys since those are strings. The odd construction `\use:n {#1}` allows #1 to contain any token without interfering with `\prop_map_break:.` Argument #2 of `\__prop_map_tokens:nwn` is `\s__prop` the first time, and is otherwise empty.

`\prop_map_tokens:cn`  
`\__prop_map_tokens:nwn`

```

22327 \cs_new:Npn \prop_map_tokens:Nn #1#2
22328 {
22329   \exp_last_unbraced:Nno \__prop_map_tokens:nwn {#2} #1
22330   \__prop_pair:wn \q_recursion_tail \s__prop { }
22331   \__prg_break_point:Nn \prop_map_break: { }
22332 }
22333 \cs_new:Npn \__prop_map_tokens:nwn #1#2 \__prop_pair:wn #3 \s__prop #4
22334 {
22335   \if_meaning:w \q_recursion_tail #3

```

```

22336     \exp_after:wN \prop_map_break:
22337     \fi:
22338     \use:n {#1} {#3} {#4}
22339     \__prop_map_tokens:nwn {#1}
22340   }
22341   \cs_generate_variant:Nn \prop_map_tokens:Nn { c }

```

(End definition for `\prop_map_tokens:Nn` and `\__prop_map_tokens:nwn`. These functions are documented on page 233.)

```

\prop_rand_key_value:N
\prop_rand_key_value:c
  \__prop_rand:NN
  \__prop_rand_item:Nw

```

Contrarily to `clist`, `seq` and `tl`, there is no function to get an item of a `prop` given an integer between 1 and the number of items, so we write the appropriate code. There is no bounds checking because `\int_rand:nn` is always within bounds. At the end, leave either the key #3 or the value #4 in the input stream.

```

22342 \cs_new:Npn \prop_rand_key_value:N { \__prop_rand:NN \__prop_rand:nNn }
22343 \cs_new:Npn \__prop_rand:nNn #1#2#3 { \exp_not:n { {#1} {#3} } }
22344 \cs_new:Npn \__prop_rand:NN #1#2
22345   {
22346     \prop_if_empty:NTF #2 { }
22347     {
22348       \exp_after:wN \__prop_rand_item:Nw \exp_after:wN #1
22349       \__int_value:w \int_rand:nn { 1 } { \prop_count:N #2 } #2
22350       \q_stop
22351     }
22352   }
22353 \cs_new:Npn \__prop_rand_item:Nw #1#2 \s__prop \__prop_pair:wn #3 \s__prop #4
22354   {
22355     \int_compare:nNnF {#2} > 1
22356     { \use_i_delimit_by_q_stop:nw { #1 {#3} \exp_not:n {#4} } }
22357     \exp_after:wN \__prop_rand_item:Nw \exp_after:wN #1
22358     \__int_value:w \int_eval:n { #2 - 1 } \s__prop
22359   }
22360 \cs_generate_variant:Nn \prop_rand_key_value:N { c }

```

(End definition for `\prop_rand_key_value:N`, `\__prop_rand:NN`, and `\__prop_rand_item:Nw`. These functions are documented on page 233.)

## 42.12 Additions to `l3seq`

```

22361 <@@=seq>

```

```

\seq_mapthread_function:NNN
\seq_mapthread_function:NcN
\seq_mapthread_function:cNN
\seq_mapthread_function:ccN
  \__seq_mapthread_function:wNN
  \__seq_mapthread_function:wNw
  \__seq_mapthread_function:Nnnwnn

```

The idea is to first expand both sequences, adding the usual `{ ? \__prg_break: } { }` to the end of each one. This is most conveniently done in two steps using an auxiliary function. The mapping then throws away the first tokens of #2 and #5, which for items in both sequences are `\s__seq \__seq_item:n`. The function to be mapped are then be applied to the two entries. When the code hits the end of one of the sequences, the break material stops the entire loop and tidy up. This avoids needing to find the count of the two sequences, or worrying about which is longer.

```

22362 \cs_new:Npn \seq_mapthread_function:NNN #1#2#3
22363   { \exp_after:wN \__seq_mapthread_function:wNN #2 \q_stop #1 #3 }
22364 \cs_new:Npn \__seq_mapthread_function:wNN \s__seq #1 \q_stop #2#3
22365   {
22366     \exp_after:wN \__seq_mapthread_function:wNw #2 \q_stop #3
22367     #1 { ? \__prg_break: } { }

```

```

22368     \__prg_break_point:
22369   }
22370 \cs_new:Npn \__seq_mapthread_function:wNw \s__seq #1 \q_stop #2
22371 {
22372   \__seq_mapthread_function:Nnnwnn #2
22373   #1 { ? \__prg_break: } { }
22374   \q_stop
22375 }
22376 \cs_new:Npn \__seq_mapthread_function:Nnnwnn #1#2#3#4 \q_stop #5#6
22377 {
22378   \use_none:n #2
22379   \use_none:n #5
22380   #1 {#3} {#6}
22381   \__seq_mapthread_function:Nnnwnn #1 #4 \q_stop
22382 }
22383 \cs_generate_variant:Nn \seq_mapthread_function:NNN { Nc }
22384 \cs_generate_variant:Nn \seq_mapthread_function:NNN { c , cc }

```

(End definition for `\seq_mapthread_function:NNN` and others. These functions are documented on page 234.)

`\seq_set_filter:NNn` Similar to `\seq_map_inline:Nn`, without a `\__prg_break_point:` because the user's code is performed within the evaluation of a boolean expression, and skipping out of that would break horribly. The `\__seq_wrap_item:n` function inserts the relevant `\__seq_item:n` without expansion in the input stream, hence in the x-expanding assignment.

`\seq_gset_filter:NNn`

`\__seq_set_filter:NNNn`

```

22385 \cs_new_protected:Npn \seq_set_filter:NNn
22386 { \__seq_set_filter:NNNn \tl_set:Nx }
22387 \cs_new_protected:Npn \seq_gset_filter:NNn
22388 { \__seq_set_filter:NNNn \tl_gset:Nx }
22389 \cs_new_protected:Npn \__seq_set_filter:NNNn #1#2#3#4
22390 {
22391   \__seq_push_item_def:n { \bool_if:nT {#4} { \__seq_wrap_item:n {##1} } }
22392   #1 #2 { #3 }
22393   \__seq_pop_item_def:
22394 }

```

(End definition for `\seq_set_filter:NNn`, `\seq_gset_filter:NNn`, and `\__seq_set_filter:NNNn`. These functions are documented on page 234.)

`\seq_set_map:NNn` Very similar to `\seq_set_filter:NNn`. We could actually merge the two within a single function, but it would have weird semantics.

`\seq_gset_map:NNn`

`\__seq_set_map:NNNn`

```

22395 \cs_new_protected:Npn \seq_set_map:NNn
22396 { \__seq_set_map:NNNn \tl_set:Nx }
22397 \cs_new_protected:Npn \seq_gset_map:NNn
22398 { \__seq_set_map:NNNn \tl_gset:Nx }
22399 \cs_new_protected:Npn \__seq_set_map:NNNn #1#2#3#4
22400 {
22401   \__seq_push_item_def:n { \exp_not:N \__seq_item:n {#4} }
22402   #1 #2 { #3 }
22403   \__seq_pop_item_def:
22404 }

```

(End definition for `\seq_set_map:NNn`, `\seq_gset_map:NNn`, and `\__seq_set_map:NNNn`. These functions are documented on page 234.)

`\seq_rand_item:N` Importantly, `\seq_item:Nn` only evaluates its argument once.

```

\seq_rand_item:c 22405 \cs_new:Npn \seq_rand_item:N #1
                  22406 {
                  22407   \seq_if_empty:NF #1
                  22408   { \seq_item:Nn #1 { \int_rand:nn { 1 } { \seq_count:N #1 } } }
                  22409 }
                  22410 \cs_generate_variant:Nn \seq_rand_item:N { c }

```

(End definition for `\seq_rand_item:N`. This function is documented on page 234.)

## 42.13 Additions to `l3skip`

```
22411 <@@=skip>
```

`\skip_split_finite_else_action:nnNN` This macro is useful when performing error checking in certain circumstances. If the `<skip>` register holds finite glue it sets #3 and #4 to the stretch and shrink component, resp. If it holds infinite glue set #3 and #4 to zero and issue the special action #2 which is probably an error message. Assignments are local.

```

22412 \cs_new:Npn \skip_split_finite_else_action:nnNN #1#2#3#4
22413 {
22414   \skip_if_finite:nTF {#1}
22415   {
22416     #3 = \etex_gluestretch:D #1 \scan_stop:
22417     #4 = \etex_glueshrink:D #1 \scan_stop:
22418   }
22419   {
22420     #3 = \c_zero_skip
22421     #4 = \c_zero_skip
22422     #2
22423   }
22424 }

```

(End definition for `\skip_split_finite_else_action:nnNN`. This function is documented on page 234.)

## 42.14 Additions to `l3sys`

```
22425 <@@=sys>
```

`\sys_if_rand_exist:p:` Currently, randomness exists under pdfTeX and LuaTeX.

```

\sys_if_rand_exist:TF 22426 \cs_if_exist:NTF \pdftex_uniformdeviate:D
                      22427 {
                      22428   \prg_new_conditional:Npnn \sys_if_rand_exist: { p , T , F , TF }
                      22429   { \prg_return_true: }
                      22430 }
                      22431 {
                      22432   \prg_new_conditional:Npnn \sys_if_rand_exist: { p , T , F , TF }
                      22433   { \prg_return_false: }
                      22434 }

```

(End definition for `\sys_if_rand_exist:TF`. This function is documented on page 235.)

`\sys_rand_seed:` Unpack the primitive.

```
22435 \cs_new:Npn \sys_rand_seed: { \tex_the:D \pdftex_randomseed:D }
```

(End definition for `\sys_rand_seed:.` This function is documented on page 235.)

**\sys\_gset\_rand\_seed:n** The primitive always assigns the seed globally.

```
22436 \cs_new_protected:Npn \sys_gset_rand_seed:n #1
22437 { \pdfTeX_setrandomseed:D \__int_eval:w #1 \__int_eval_end: }
```

(End definition for \sys\_gset\_rand\_seed:n. This function is documented on page 235.)

**\c\_sys\_shell\_escape\_int** Expose the engine's shell escape status to the user.

```
22438 \int_const:Nn \c_sys_shell_escape_int
22439 {
22440   \sys_if_engine luatex:TF
22441   {
22442     \luatex_directlua:D
22443     {
22444       tex.sprint((status.shell_escape~or~os.execute()) .. " ")
22445     }
22446   }
22447   {
22448     \pdfTeX_shellescape:D
22449   }
22450 }
```

(End definition for \c\_sys\_shell\_escape\_int. This variable is documented on page 235.)

**\sys\_if\_shell\_p:** Performs a check for whether shell escape is enabled. This returns true if either of restricted or unrestricted shell escape is enabled.

**\sys\_if\_shell:TF**

```
22451 \prg_new_conditional:Nnn \sys_if_shell: { p , T , F , TF }
22452 {
22453   \if_int_compare:w \c_sys_shell_escape_int = 0 ~
22454   \prg_return_false:
22455   \else:
22456   \prg_return_true:
22457   \fi:
22458 }
```

(End definition for \sys\_if\_shell:TF. This function is documented on page 235.)

**\sys\_if\_shell\_unrestricted\_p:** Performs a check for whether *unrestricted* shell escape is enabled.

**\sys\_if\_shell\_unrestricted:TF**

```
22459 \prg_new_conditional:Nnn \sys_if_shell_unrestricted: { p , T , F , TF }
22460 {
22461   \if_int_compare:w \c_sys_shell_escape_int = 1 ~
22462   \prg_return_true:
22463   \else:
22464   \prg_return_false:
22465   \fi:
22466 }
```

(End definition for \sys\_if\_shell\_unrestricted:TF. This function is documented on page 235.)

**\sys\_if\_shell\_unrestricted\_p:** Performs a check for whether *restricted* shell escape is enabled. This returns false if unrestricted shell escape is enabled. Unrestricted shell escape is not considered a superset of restricted shell escape in this case. To find whether any shell escape is enabled use **\sys\_if\_shell:**.

**\sys\_if\_shell\_unrestricted:TF**

```
22467 \prg_new_conditional:Nnn \sys_if_shell_restricted: { p , T , F , TF }
22468 {
```

```

22469     \if_int_compare:w \c_sys_shell_escape_int = 2 ~
22470     \prg_return_true:
22471   \else:
22472     \prg_return_false:
22473   \fi:
22474 }

```

(End definition for `\sys_if_shell_unrestricted:TF`. This function is documented on page 235.)

`\c__sys_shell_stream_int` This is not needed for LuaTeX: shell escape there isn't done using a T<sub>E</sub>X interface

```

22475 \sys_if_engine luatex:F
22476 { \int_const:Nn \c__sys_shell_stream_int { 18 } }

```

(End definition for `\c__sys_shell_stream_int`.)

**`\sys_shell_now:n`** Execute commands through shell escape immediately.

```

22477 \sys_if_engine luatex:TF
22478 {
22479   \cs_new_protected:Npn \sys_shell_now:n #1
22480   {
22481     \luatex_directlua:D
22482     {
22483       os.execute("
22484         \luatex_luaescapestring:D { \etex_detokenize:D {#1} }
22485       ")
22486     }
22487   }
22488 }
22489 {
22490   \cs_new_protected:Npn \sys_shell_now:n #1
22491   {
22492     \iow_now:Nn \c__sys_shell_stream_int { #1 }
22493   }
22494 }
22495 \cs_generate_variant:Nn \sys_shell_now:n { x }

```

(End definition for `\sys_shell_now:n`. This function is documented on page 236.)

**`\sys_shell_shipout:n`** Execute commands through shell escape at shipout.

```

22496 \sys_if_engine luatex:TF
22497 {
22498   \cs_new_protected:Npn \sys_shell_shipout:n #1
22499   {
22500     \luatex_latelua:D
22501     {
22502       os.execute("
22503         \luatex_luaescapestring:D { \etex_detokenize:D {#1} }
22504       ")
22505     }
22506   }
22507 }
22508 {
22509   \cs_new_protected:Npn \sys_shell_shipout:n #1
22510   {
22511     \iow_shipout:Nn \c__sys_shell_stream_int { #1 }

```



```

22512     }
22513   }
22514   \cs_generate_variant:Nn \sys_shell_shipout:n { x }

```

(End definition for `\sys_shell_shipout:n`. This function is documented on page 236.)

## 42.15 Additions to `l3tl`

```

22515 <@@=tl>

```

`\tl_if_single_token_p:n`  
`\tl_if_single_token:nTF`

There are four cases: empty token list, token list starting with a normal token, with a brace group, or with a space token. If the token list starts with a normal token, remove it and check for emptiness. For the next case, an empty token list is not a single token. Finally, we have a non-empty token list starting with a space or a brace group. Applying `f`-expansion yields an empty result if and only if the token list is a single space.

```

22516 \prg_new_conditional:Npnn \tl_if_single_token:n #1 { p , T , F , TF }
22517 {
22518   \tl_if_head_is_N_type:nTF {#1}
22519   { \__tl_if_empty_return:o { \use_none:n #1 } }
22520   {
22521     \tl_if_empty:nTF {#1}
22522     { \prg_return_false: }
22523     { \__tl_if_empty_return:o { \exp:w \exp_end_continue_f:w #1 } }
22524   }
22525 }

```

(End definition for `\tl_if_single_token:nTF`. This function is documented on page 236.)

`\tl_reverse_tokens:n`  
`\__tl_reverse_group:nn`

The same as `\tl_reverse:n` but with recursion within brace groups.

```

22526 \cs_new:Npn \tl_reverse_tokens:n #1
22527 {
22528   \etex_unexpanded:D \exp_after:wN
22529   {
22530     \exp:w
22531     \__tl_act:NNNnn
22532     \__tl_reverse_normal:nN
22533     \__tl_reverse_group:nn
22534     \__tl_reverse_space:n
22535     { }
22536     {#1}
22537   }
22538 }
22539 \cs_new:Npn \__tl_reverse_group:nn #1
22540 {
22541   \__tl_act_group_recurse:NNn
22542   \__tl_act_reverse_output:n
22543   { \tl_reverse_tokens:n }
22544 }

```

`\__tl_act_group_recurse:NNn`

In many applications of `\__tl_act:NNNnn`, we need to recursively apply some transformation within brace groups, then output. In this code, `#1` is the output function, `#2` is the transformation, which should expand in two steps, and `#3` is the group.

```

22545 \cs_new:Npn \__tl_act_group_recurse:NNn #1#2#3
22546 {

```

```

22547 \exp_args:Nf #1
22548 { \exp_after:wN \exp_after:wN \exp_after:wN { #2 {#3} } }
22549 }

```

(End definition for `\tl_reverse_tokens:n`, `\__tl_reverse_group:nn`, and `\__tl_act_group_recurse:Nnn`. These functions are documented on page 236.)

```

\__tl_act_count_normal:nN
\__tl_act_count_group:nn
\__tl_act_count_space:n

```

The token count is computed through an `\int_eval:n` construction. Each `1+` is output to the left, into the integer expression, and the sum is ended by the `\exp_end:` inserted by `\__tl_act_end:wn` (which is technically implemented as `\c_zero`). Somewhat a hack!

```

22550 \cs_new:Npn \tl_count_tokens:n #1
22551 {
22552   \int_eval:n
22553   {
22554     \__tl_act:NNNnn
22555     \__tl_act_count_normal:nN
22556     \__tl_act_count_group:nn
22557     \__tl_act_count_space:n
22558     { }
22559     {#1}
22560   }
22561 }
22562 \cs_new:Npn \__tl_act_count_normal:nN #1 #2 { 1 + }
22563 \cs_new:Npn \__tl_act_count_space:n #1 { 1 + }
22564 \cs_new:Npn \__tl_act_count_group:nn #1 #2
22565 { 2 + \tl_count_tokens:n {#2} + }

```

(End definition for `\tl_count_tokens:n` and others. These functions are documented on page 236.)

```

\tl_set_from_file:Nnn
\tl_set_from_file:cnn
\tl_gset_from_file:Nnn
\tl_gset_from_file:cnn
\__tl_set_from_file:NNnn
\__tl_from_file_do:w

```

The approach here is similar to that for doing a rescan, and so the same internals can be reused. Thus the plan is to insert a pair of tokens of the same charcode but different catcodes after the file has been read. This plus `\exp_not:N` allows the primitive to be used to carry out a set operation.

```

22566 \cs_new_protected:Npn \tl_set_from_file:Nnn
22567 { \__tl_set_from_file:NNnn \tl_set:Nn }
22568 \cs_new_protected:Npn \tl_gset_from_file:Nnn
22569 { \__tl_set_from_file:NNnn \tl_gset:Nn }
22570 \cs_generate_variant:Nn \tl_set_from_file:Nnn { c }
22571 \cs_generate_variant:Nn \tl_gset_from_file:Nnn { c }
22572 \cs_new_protected:Npn \__tl_set_from_file:NNnn #1#2#3#4
22573 {
22574   \file_get_full_name:nN {#4} \l__file_full_name_str
22575   \str_if_empty:NTF \l__file_full_name_str
22576   { \__file_missing:n {#4} }
22577   {
22578     \group_begin:
22579     \exp_args:No \etex_veryeof:D
22580     { \c__tl_rescan_marker_tl \exp_not:N }
22581     #3 \scan_stop:
22582     \exp_after:wN \__tl_from_file_do:w
22583     \exp_after:wN \prg_do_nothing:
22584     \tex_input:D \l__file_full_name_str \scan_stop:
22585     \exp_args:NNNo \group_end:
22586     #1 #2 \l__tl_internal_a_tl

```

```

22587     }
22588   }
22589   \exp_args:Nno \use:nn
22590   { \cs_new_protected:Npn \__tl_from_file_do:w #1 }
22591   { \c__tl_rescan_marker_tl }
22592   { \tl_set:No \l__tl_internal_a_tl {#1} }

```

(End definition for `\tl_set_from_file:Nnn` and others. These functions are documented on page 239.)

`\tl_set_from_file_x:Nnn` When reading a file and allowing expansion of the content, the set up only needs to prevent TeX complaining about the end of the file. That is done simply, with a group then used to trap the definition needed. Once the business is done using some scratch space, the tokens can be transferred to the real target.

```

\__tl_set_from_file_x:NNnn
22593 \cs_new_protected:Npn \tl_set_from_file_x:Nnn
22594   { \__tl_set_from_file_x:NNnn \tl_set:Nn }
22595 \cs_new_protected:Npn \tl_gset_from_file_x:Nnn
22596   { \__tl_set_from_file_x:NNnn \tl_gset:Nn }
22597 \cs_generate_variant:Nn \tl_set_from_file_x:Nnn { c }
22598 \cs_generate_variant:Nn \tl_gset_from_file_x:Nnn { c }
22599 \cs_new_protected:Npn \__tl_set_from_file_x:NNnn #1#2#3#4
22600   {
22601     \file_get_full_name:nN {#4} \l__file_full_name_str
22602     \str_if_empty:NTF \l__file_full_name_str
22603       { \__file_missing:n {#4} }
22604     {
22605       \group_begin:
22606         \etex_veryeof:D { \exp_not:N }
22607         #3 \scan_stop:
22608         \tl_set:Nx \l__tl_internal_a_tl
22609           { \tex_input:D \l__file_full_name_str \c_space_token }
22610         \exp_args:NNNo \group_end:
22611         #1 #2 \l__tl_internal_a_tl
22612       }
22613     }

```

(End definition for `\tl_set_from_file_x:Nnn`, `\tl_gset_from_file_x:Nnn`, and `\__tl_set_from_file_x:NNnn`. These functions are documented on page 240.)

#### 42.15.1 Unicode case changing

The mechanisms needed for case changing are somewhat involved, particularly to allow for all of the special cases. These functions also require the appropriate data extracted from the Unicode documentation (either manually or automatically).

`\tl_if_head_eq_catcode:oNTF` Extra variants.

```

22614 \cs_generate_variant:Nn \tl_if_head_eq_catcode:nNTF { o }

```

(End definition for `\tl_if_head_eq_catcode:oNTF`. This function is documented on page 44.)

`\tl_lower_case:n` The user level functions here are all wrappers around the internal functions for case changing.  
`\tl_upper_case:n`  
`\tl_mixed_case:n`  
`\tl_lower_case:nn`  
`\tl_upper_case:nn`  
`\tl_mixed_case:nn`

```

22615 \cs_new:Npn \tl_lower_case:n { \__tl_change_case:nnn { lower } { } }
22616 \cs_new:Npn \tl_upper_case:n { \__tl_change_case:nnn { upper } { } }
22617 \cs_new:Npn \tl_mixed_case:n { \__tl_change_case:nnn { mixed } { } }

```

```

22618 \cs_new:Npn \tl_lower_case:nn { \__tl_change_case:nnn { lower } }
22619 \cs_new:Npn \tl_upper_case:nn { \__tl_change_case:nnn { upper } }
22620 \cs_new:Npn \tl_mixed_case:nn { \__tl_change_case:nnn { mixed } }

```

(End definition for `\tl_lower_case:n` and others. These functions are documented on page 236.)

The mechanism for the core conversion of case is based on the idea that we can use a loop to grab the entire token list plus a quark: the latter is used as an end marker and to avoid any brace stripping. Depending on the nature of the first item in the grabbed argument, it can either be processed as a single token, treated as a group or treated as a space. These different cases all work by re-reading #1 in the appropriate way, hence the repetition of #1 `\q_recursion_stop`.

```

22621 \cs_new:Npn \__tl_change_case:nnn #1#2#3
22622 {
22623   \etex_unexpanded:D \exp_after:wN
22624   {
22625     \exp:w
22626     \__tl_change_case_aux:nnn {#1} {#2} {#3}
22627   }
22628 }
22629 \cs_new:Npn \__tl_change_case_aux:nnn #1#2#3
22630 {
22631   \group_align_safe_begin:
22632   \__tl_change_case_loop:wnn
22633   #3 \q_recursion_tail \q_recursion_stop {#1} {#2}
22634   \__tl_change_case_result:n { }
22635 }
22636 \cs_new:Npn \__tl_change_case_loop:wnn #1 \q_recursion_stop
22637 {
22638   \tl_if_head_is_N_type:nTF {#1}
22639   { \__tl_change_case_N_type:Nwnn }
22640   {
22641     \tl_if_head_is_group:nTF {#1}
22642     { \__tl_change_case_group:nwnn }
22643     { \__tl_change_case_space:wnn }
22644   }
22645   #1 \q_recursion_stop
22646 }

```

Earlier versions of the code where only x-type expandable rather than f-type: this causes issues with nesting and so the slight performance hit is taken for a better outcome in usability terms. Setting up for f-type expandability has two requirements: a marker token after the main loop (see above) and a mechanism to “load” and finalise the result. That is handled in the code below, which includes the necessary material to end the `\exp:w` expansion.

```

22647 \cs_new:Npn \__tl_change_case_output:nwn #1#2 \__tl_change_case_result:n #3
22648 { #2 \__tl_change_case_result:n { #3 #1 } }
22649 \cs_generate_variant:Nn \__tl_change_case_output:nwn { V , o , v , f }
22650 \cs_new:Npn \__tl_change_case_end:wn #1 \__tl_change_case_result:n #2
22651 {
22652   \group_align_safe_end:
22653   \exp_end:
22654   #2
22655 }

```

Handling for the cases where the current argument is a brace group or a space is relatively easy. For the brace case, the routine works recursively, using the expandability of the mechanism to ensure that the result is finalised before storage. For the space case it is simply a question of removing the space in the input and storing it in the output. In both cases, and indeed for the N-type grabber, after removing the current item from the input `\__tl_change_case_loop:wnn` is inserted in front of the remaining tokens.

```

22656 \cs_new:Npn \__tl_change_case_group:nwnn #1#2 \q_recursion_stop #3#4
22657 {
22658   \use:c { __tl_change_case_group_ #3 : nnnn } {#1} {#2} {#3} {#4}
22659 }
22660 \cs_new:Npn \__tl_change_case_group_lower:nnnn #1#2#3#4
22661 {
22662   \__tl_change_case_output:own
22663   {
22664     \exp_after:wN
22665     {
22666       \exp:w
22667       \__tl_change_case_aux:nnn {#3} {#4} {#1}
22668     }
22669   }
22670   \__tl_change_case_loop:wnn #2 \q_recursion_stop {#3} {#4}
22671 }
22672 \cs_new_eq:NN \__tl_change_case_group_upper:nnnn
22673 \__tl_change_case_group_lower:nnnn

```

For the “mixed” case, a group is taken as forcing a switch to lower casing. That means we need a separate auxiliary. (Tracking whether we have found a first character inside a group and transferring the information out looks pretty horrible.)

```

22674 \cs_new:Npn \__tl_change_case_group_mixed:nnnn #1#2#3#4
22675 {
22676   \__tl_change_case_output:own
22677   {
22678     \exp_after:wN
22679     {
22680       \exp:w
22681       \__tl_change_case_aux:nnn {#3} {#4} {#1}
22682     }
22683   }
22684   \__tl_change_case_loop:wnn #2 \q_recursion_stop { lower } {#4}
22685 }
22686 \exp_last_unbraced:NNo \cs_new:Npn \__tl_change_case_space:wnn \c_space_tl
22687 {
22688   \__tl_change_case_output:nwn { ~ }
22689   \__tl_change_case_loop:wnn
22690 }

```

For N-type arguments there are several stages to the approach. First, a simply check for the end-of-input marker, which if found triggers the final clean up and output step. Assuming that is not the case, the first check is for math-mode escaping: this test can encompass control sequences or other N-type tokens so is handled up front.

```

22691 \cs_new:Npn \__tl_change_case_N_type:Nwnn #1#2 \q_recursion_stop
22692 {
22693   \quark_if_recursion_tail_stop_do:Nn #1
22694   { \__tl_change_case_end:wn }

```

```

22695 \exp_after:wN \_tl_change_case_N_type:NNNnnn
22696 \exp_after:wN #1 \l_tl_case_change_math_tl
22697 \q_recursion_tail ? \q_recursion_stop {#2}
22698 }

```

Looking for math mode escape first requires a loop over the possible token pairs to see if the current input (#1) matches an open-math case (#2). If it does then this test loop is ended and a new input-gathering one is begun. The latter simply transfers material from the input to the output without any expansion, testing each N-type token to see if it matches the close-math case required. If that is the situation then the “math loop” stops and resumes the main loop: as that might be either the standard case-changing one or the mixed-case alternative, it is not hard-coded into the math loop but is rather passed as argument #3 to `\_tl_change_case_math:NNNnnn`. If no close-math token is found then the final clean-up is forced (*i.e.* there is no assumption of “well-behaved” input in terms of math mode).

```

22699 \cs_new:Npn \_tl_change_case_N_type:NNNnnn #1#2#3
22700 {
22701   \quark_if_recursion_tail_stop_do:Nn #2
22702   { \_tl_change_case_N_type:NNnn #1 }
22703   \token_if_eq_meaning:NNTF #1 #2
22704   {
22705     \use_i_delimit_by_q_recursion_stop:nw
22706     {
22707       \_tl_change_case_math:NNNnnn
22708       #1 #3 \_tl_change_case_loop:wnn
22709     }
22710   }
22711   { \_tl_change_case_N_type:NNNnnn #1 }
22712 }
22713 \cs_new:Npn \_tl_change_case_math:NNNnnn #1#2#3#4
22714 {
22715   \_tl_change_case_output:nwn {#1}
22716   \_tl_change_case_math_loop:wNNnn #4 \q_recursion_stop #2 #3
22717 }
22718 \cs_new:Npn \_tl_change_case_math_loop:wNNnn #1 \q_recursion_stop
22719 {
22720   \tl_if_head_is_N_type:nTF {#1}
22721   { \_tl_change_case_math:NwNNnn }
22722   {
22723     \tl_if_head_is_group:nTF {#1}
22724     { \_tl_change_case_math_group:nwNNnn }
22725     { \_tl_change_case_math_space:wNNnn }
22726   }
22727   #1 \q_recursion_stop
22728 }
22729 \cs_new:Npn \_tl_change_case_math:NwNNnn #1#2 \q_recursion_stop #3#4
22730 {
22731   \token_if_eq_meaning:NNTF \q_recursion_tail #1
22732   { \_tl_change_case_end:wN }
22733   {
22734     \_tl_change_case_output:nwn {#1}
22735     \token_if_eq_meaning:NNTF #1 #3
22736     { #4 #2 \q_recursion_stop }
22737     { \_tl_change_case_math_loop:wNNnn #2 \q_recursion_stop #3#4 }

```

```

22738     }
22739   }
22740   \cs_new:Npn \__tl_change_case_math_group:nwNNnn #1#2 \q_recursion_stop
22741   {
22742     \__tl_change_case_output:nwn { {#1} }
22743     \__tl_change_case_math_loop:wNNnn #2 \q_recursion_stop
22744   }
22745   \exp_last_unbraced:NNo
22746   \cs_new:Npn \__tl_change_case_math_space:wNNnn \c_space_tl
22747   {
22748     \__tl_change_case_output:nwn { ~ }
22749     \__tl_change_case_math_loop:wNNnn
22750   }

```

Once potential math-mode cases are filtered out the next stage is to test if the token grabbed is a control sequence: they cannot be used in the lookup table and also may require expansion. At this stage the loop code starting `\__tl_change_case_loop:wnn` is inserted: all subsequent steps in the code which need a look-ahead are coded to rely on this and thus have w-type arguments if they may do a look-ahead.

```

22751   \cs_new:Npn \__tl_change_case_N_type:Nnnn #1#2#3#4
22752   {
22753     \token_if_cs:NTF #1
22754     { \__tl_change_case_cs_letterlike:Nn #1 {#3} }
22755     { \use:c { \__tl_change_case_char_ #3 :Nnn } #1 {#3} {#4} }
22756     \__tl_change_case_loop:wnn #2 \q_recursion_stop {#3} {#4}
22757   }

```

For character tokens there are some special cases to deal with then the majority of changes are covered by using the T<sub>E</sub>X data as a lookup along with expandable character generation. This avoids needing a very large number of macros or (as seen in earlier versions) a somewhat tricky split of the characters into various blocks. Notice that the special case code may do a look-ahead so requires a final w-type argument whereas the core lookup table does not and also guarantees an output so f-type expansion may be used to obtain the case-changed result.

```

22758   \cs_new:Npn \__tl_change_case_char_lower:Nnn #1#2#3
22759   {
22760     \cs_if_exist_use:cF { \__tl_change_case_ #2 _ #3 :Nnw }
22761     { \use_ii:nn }
22762     #1
22763     {
22764       \use:c { \__tl_change_case_ #2 _ sigma:Nnw } #1
22765       { \__tl_change_case_char:nN {#2} #1 }
22766     }
22767   }
22768   \cs_new_eq:NN \__tl_change_case_char_upper:Nnn
22769   \__tl_change_case_char_lower:Nnn

```

For mixed case, the code is somewhat different: there is a need to look up both mixed and upper case chars and we have to cover the situation where there is a character to skip over.

```

22770   \cs_new:Npn \__tl_change_case_char_mixed:Nnn #1#2#3
22771   {
22772     \__tl_change_case_mixed_switch:w
22773     \cs_if_exist_use:cF { \__tl_change_case_mixed_ #3 :Nnw }

```

```

22774     {
22775         \cs_if_exist_use:cF { __tl_change_case_upper_ #3 :Nnw }
22776         { \use_ii:nn }
22777     }
22778     #1
22779     { \__tl_change_case_mixed_skip:N #1 }
22780 }

```

For Unicode engines we can handle all characters directly. However, for the 8-bit engines the aim is to deal with (a subset of) Unicode (UTF-8) input. They deal with that by making the upper half of the range active, so we look for that and if found work out how many UTF-8 octets there are to deal with. Those can then be grabbed to reconstruct the full Unicode character, which is then used in a lookup. (As will become obvious below, there is no intention here of covering all of Unicode.)

```

22781 \cs_if_exist:NTF \utex_char:D
22782 {
22783     \cs_new:Npn \__tl_change_case_char:nN #1#2
22784     { \__tl_change_case_char_auxi:nN {#1} #2 }
22785 }
22786 {
22787     \cs_new:Npn \__tl_change_case_char:nN #1#2
22788     {
22789         \int_compare:nNnTF { '#2 } > { "80 }
22790         {
22791             \int_compare:nNnTF { '#2 } < { "E0 }
22792             { \__tl_change_case_char_UTFviii:nNNN {#1} #2 }
22793             {
22794                 \int_compare:nNnTF { '#2 } < { "F0 }
22795                 { \__tl_change_case_char_UTFviii:nNNNN {#1} #2 }
22796                 { \__tl_change_case_char_UTFviii:nNNNNN {#1} #2 }
22797             }
22798         }
22799         { \__tl_change_case_char_auxi:nN {#1} #2 }
22800     }
22801 }

```

To allow for the special case of mixed case, we insert here a action-dependent auxiliary.

```

22802 \cs_new:Npn \__tl_change_case_char_auxi:nN #1#2
22803 { \use:c { __tl_change_case_char_ #1 :N } #2 }
22804 \cs_new:Npn \__tl_change_case_char_lower:N #1
22805 {
22806     \__tl_change_case_output:fwn
22807     {
22808         \cs_if_exist_use:cF { c_unicode_lower_ \token_to_str:N #1 _tl }
22809         { \__tl_change_case_char_auxii:nN { lower } #1 }
22810     }
22811 }
22812 \cs_new:Npn \__tl_change_case_char_upper:N #1
22813 {
22814     \__tl_change_case_output:fwn
22815     {
22816         \cs_if_exist_use:cF { c_unicode_upper_ \token_to_str:N #1 _tl }
22817         { \__tl_change_case_char_auxii:nN { upper } #1 }
22818     }

```



```

22819 }
22820 \cs_new:Npn \__tl_change_case_char_mixed:N #1
22821 {
22822   \cs_if_exist:cTF { c__unicode_mixed_ \token_to_str:N #1 _tl }
22823   {
22824     \__tl_change_case_output:fwn
22825     { \tl_use:c { c__unicode_mixed_ \token_to_str:N #1 _tl } }
22826   }
22827   { \__tl_change_case_char_upper:N #1 }
22828 }
22829 \cs_if_exist:NTF \utex_char:D
22830 {
22831   \cs_new:Npn \__tl_change_case_char_auxii:nN #1#2
22832   {
22833     \int_compare:nNnTF { \use:c { __tl_lookup_ #1 :N } #2 } = { 0 }
22834     { \exp_stop_f: #2 }
22835     {
22836       \char_generate:nn
22837       { \use:c { __tl_lookup_ #1 :N } #2 }
22838       { \char_value_catcode:n { \use:c { __tl_lookup_ #1 :N } #2 } }
22839     }
22840   }
22841   \cs_new_protected:Npn \__tl_lookup_lower:N #1 { \tex_lccode:D '#1 }
22842   \cs_new_protected:Npn \__tl_lookup_upper:N #1 { \tex_uccode:D '#1 }
22843   \cs_new_eq:NN \__tl_lookup_mixed:N \__tl_lookup_upper:N
22844 }
22845 {
22846   \cs_new:Npn \__tl_change_case_char_auxii:nN #1#2 { \exp_stop_f: #2 }
22847   \cs_new:Npn \__tl_change_case_char_UTFviii:nNNN #1#2#3#4
22848   { \__tl_change_case_char_UTFviii:nnN {#1} {#2#4} #3 }
22849   \cs_new:Npn \__tl_change_case_char_UTFviii:nNNNN #1#2#3#4#5
22850   { \__tl_change_case_char_UTFviii:nnN {#1} {#2#4#5} #3 }
22851   \cs_new:Npn \__tl_change_case_char_UTFviii:nNNNNN #1#2#3#4#5#6
22852   { \__tl_change_case_char_UTFviii:nnN {#1} {#2#4#5#6} #3 }
22853   \cs_new:Npn \__tl_change_case_char_UTFviii:nnN #1#2#3
22854   {
22855     \cs_if_exist:cTF { c__unicode_ #1 _ \tl_to_str:n {#2} _tl }
22856     {
22857       \__tl_change_case_output:vnw
22858       { c__unicode_ #1 _ \tl_to_str:n {#2} _tl }
22859     }
22860     { \__tl_change_case_output:nwn {#2} }
22861   } #3
22862 }
22863 }

```

Before dealing with general control sequences there are the special ones to deal with. Letter-like control sequences are a simple look-up, while for accents the loop is much as done elsewhere. Notice that we have a no-op test to make sure there is no unexpected expansion of letter-like input. The split into two parts here allows us to insert the “switch” code for mixed casing.

```

22864 \cs_new:Npn \__tl_change_case_cs_letterlike:Nn #1#2
22865 {
22866   \str_if_eq:nnTF {#2} { mixed }

```

```

22867     {
22868       \__tl_change_case_cs_letterlike:NnN #1 { upper }
22869       \__tl_change_case_mixed_switch:w
22870     }
22871     { \__tl_change_case_cs_letterlike:NnN #1 {#2} \prg_do_nothing: }
22872   }
22873 \cs_new:Npn \__tl_change_case_cs_letterlike:NnN #1#2#3
22874 {
22875   \cs_if_exist:cTF { c__tl_change_case_ #2 _ \token_to_str:N #1 _tl }
22876   {
22877     \__tl_change_case_output:vwN
22878     { c__tl_change_case_ #2 _ \token_to_str:N #1 _tl }
22879     #3
22880   }
22881   {
22882     \cs_if_exist:cTF
22883     {
22884       c__tl_change_case_
22885       \str_if_eq:nnTF {#2} { lower } { upper } { lower }
22886       _ \token_to_str:N #1 _tl
22887     }
22888     {
22889       \__tl_change_case_output:nwn {#1}
22890       #3
22891     }
22892     {
22893       \exp_after:wN \__tl_change_case_cs_accents:NN
22894       \exp_after:wN #1 \l_tl_case_change_accents_tl
22895       \q_recursion_tail \q_recursion_stop
22896     }
22897   }
22898 }
22899 \cs_new:Npn \__tl_change_case_cs_accents:NN #1#2
22900 {
22901   \quark_if_recursion_tail_stop_do:Nn #2
22902   { \__tl_change_case_cs:N #1 }
22903   \str_if_eq:nnTF {#1} {#2}
22904   {
22905     \use_i_delimit_by_q_recursion_stop:nw
22906     { \__tl_change_case_output:nwn {#1} }
22907   }
22908   { \__tl_change_case_cs_accents:NN #1 }
22909 }

```

To deal with a control sequence there is first a need to test if it is on the list which indicate that case changing should be skipped. That's done using a loop as for the other special cases. If a hit is found then the argument is grabbed: that comes *after* the loop function which is therefore rearranged. In a L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> context, `\protect` needs to be treated specially, to prevent expansion of the next token but output it without braces.

```

22910 \cs_new:Npn \__tl_change_case_cs:N #1
22911 {
22912   <*package>
22913   \str_if_eq:nnTF {#1} { \protect } { \__tl_change_case_protect:wNN }
22914   </package>

```

```

22915 \exp_after:wN \_tl_change_case_cs:NN
22916 \exp_after:wN #1 \l_tl_case_change_exclude_tl
22917 \q_recursion_tail \q_recursion_stop
22918 }
22919 \cs_new:Npn \_tl_change_case_cs:NN #1#2
22920 {
22921 \quark_if_recursion_tail_stop_do:Nn #2
22922 {
22923 \_tl_change_case_cs_expand:Nnw #1
22924 { \_tl_change_case_output:nwn {#1} }
22925 }
22926 \str_if_eq:nnTF {#1} {#2}
22927 {
22928 \use_i_delimit_by_q_recursion_stop:nw
22929 { \_tl_change_case_cs:NNn #1 }
22930 }
22931 { \_tl_change_case_cs:NN #1 }
22932 }
22933 \cs_new:Npn \_tl_change_case_cs:NNn #1#2#3
22934 {
22935 \_tl_change_case_output:nwn { #1 {#3} }
22936 #2
22937 }
22938 \*package
22939 \cs_new:Npn \_tl_change_case_protect:wNN #1 \q_recursion_stop #2 #3
22940 { \_tl_change_case_output:nwn { \protect #3 } #2 }
22941 \*package

```

When a control sequence is not on the exclude list the other test if to see if it is expandable. Once again, if there is a hit then the loop function is grabbed as part of the clean-up and reinserted before the now expanded material. The test for expandability has to check for end-of-recursion as it is needed by the look-ahead code which might hit the end of the input. The test is done in two parts as `\bool_if:nTF` would choke if #1 was (!

```

22942 \cs_new:Npn \_tl_change_case_if_expandable:NTF #1
22943 {
22944 \token_if_expandable:NTF #1
22945 {
22946 \bool_lazy_any:nTF
22947 {
22948 { \token_if_eq_meaning_p:NN \q_recursion_tail #1 }
22949 { \token_if_protected_macro_p:N #1 }
22950 { \token_if_protected_long_macro_p:N #1 }
22951 }
22952 { \use_ii:nn }
22953 { \use_i:nn }
22954 }
22955 { \use_ii:nn }
22956 }
22957 \cs_new:Npn \_tl_change_case_cs_expand:Nnw #1#2
22958 {
22959 \_tl_change_case_if_expandable:NTF #1
22960 { \_tl_change_case_cs_expand:NN #1 }
22961 { #2 }
22962 }

```

```

22963 \cs_new:Npn \__tl_change_case_cs_expand:NN #1#2
22964 { \exp_after:wN #2 #1 }

```

For mixed case, there is an additional list of exceptions to deal with: once that is sorted, we can move on back to the main loop.

```

22965 \cs_new:Npn \__tl_change_case_mixed_skip:N #1
22966 {
22967   \exp_after:wN \__tl_change_case_mixed_skip:NN
22968   \exp_after:wN #1 \l_tl_mixed_case_ignore_tl
22969   \q_recursion_tail \q_recursion_stop
22970 }
22971 \cs_new:Npn \__tl_change_case_mixed_skip:NN #1#2
22972 {
22973   \quark_if_recursion_tail_stop_do:nn {#2}
22974   { \__tl_change_case_char:nN { mixed } #1 }
22975   \int_compare:nNnT { '#1 } = { '#2 }
22976   {
22977     \use_i_delimit_by_q_recursion_stop:nw
22978     {
22979       \__tl_change_case_output:nwn {#1}
22980       \__tl_change_case_mixed_skip_tidy:Nwn
22981     }
22982   }
22983   \__tl_change_case_mixed_skip:NN #1
22984 }
22985 \cs_new:Npn \__tl_change_case_mixed_skip_tidy:Nwn #1#2 \q_recursion_stop #3
22986 {
22987   \__tl_change_case_loop:wnn #2 \q_recursion_stop { mixed }
22988 }

```

Needed to switch from mixed to lower casing when we have found a first character in the former mode.

```

22989 \cs_new:Npn \__tl_change_case_mixed_switch:w
22990 #1 \__tl_change_case_loop:wnn #2 \q_recursion_stop #3
22991 {
22992   #1
22993   \__tl_change_case_loop:wnn #2 \q_recursion_stop { lower }
22994 }

```

(End definition for \\_\_tl\_change\_case:nnn and others.)

If the current char is an upper case sigma, the a check is made on the next item in the input. If it is N-type and not a control sequence then there is a look-ahead phase.

```

\__tl_change_case_lower_sigma:Nnw
\__tl_change_case_lower_sigma:w
\__tl_change_case_lower_sigma:Nw
\__tl_change_case_upper_sigma:Nnw
22995 \cs_new:Npn \__tl_change_case_lower_sigma:Nnw #1#2#3#4 \q_recursion_stop
22996 {
22997   \int_compare:nNnTF { '#1 } = { "03A3 }
22998   {
22999     \__tl_change_case_output:fwn
23000     { \__tl_change_case_lower_sigma:w #4 \q_recursion_stop }
23001   }
23002   {#2}
23003   #3 #4 \q_recursion_stop
23004 }
23005 \cs_new:Npn \__tl_change_case_lower_sigma:w #1 \q_recursion_stop
23006 {

```

```

23007     \tl_if_head_is_N_type:nTF {#1}
23008     { \__tl_change_case_lower_sigma:Nw #1 \q_recursion_stop }
23009     { \c__unicode_final_sigma_tl }
23010   }
23011 \cs_new:Npn \__tl_change_case_lower_sigma:Nw #1#2 \q_recursion_stop
23012 {
23013   \__tl_change_case_if_expandable:NTF #1
23014   {
23015     \exp_after:wN \__tl_change_case_lower_sigma:w #1
23016     #2 \q_recursion_stop
23017   }
23018   {
23019     \token_if_letter:NTF #1
23020     { \c__unicode_std_sigma_tl }
23021     { \c__unicode_final_sigma_tl }
23022   }
23023 }

```

Simply skip to the final step for upper casing.

```

23024 \cs_new_eq:NN \__tl_change_case_upper_sigma:Nnw \use_ii:nn

```

(End definition for \\_\_tl\_change\_case\_lower\_sigma:Nnw and others.)

```

\__tl_change_case_lower_tr:Nnw
\__tl_change_case_lower_tr_auxi:Nw
\__tl_change_case_lower_tr_auxii:Nw
\__tl_change_case_upper_tr:Nnw
\__tl_change_case_lower_az:Nnw
\__tl_change_case_upper_az:Nnw

```

The Turkic languages need special treatment for dotted-i and dotless-i. The lower casing rule can be expressed in terms of searching first for either a dotless-I or a dotted-I. In the latter case the mapping is easy, but in the former there is a second stage search.

```

23025 \cs_if_exist:NTF \utex_char:D
23026 {
23027   \cs_new:Npn \__tl_change_case_lower_tr:Nnw #1#2
23028   {
23029     \int_compare:nNnTF { '#1 } = { "0049 }
23030     { \__tl_change_case_lower_tr_auxi:Nw }
23031     {
23032       \int_compare:nNnTF { '#1 } = { "0130 }
23033       { \__tl_change_case_output:nwn { i } }
23034       { #2 }
23035     }
23036   }

```

After a dotless-I there may be a dot-above character. If there is then a dotted-i should be produced, otherwise output a dotless-i. When the combination is found both the dotless-I and the dot-above char have to be removed from the input, which is done by the \use\_ii:nn (it grabs \\_\_tl\_change\_case\_loop:wn and the dot-above char and discards the latter).

```

23037   \cs_new:Npn \__tl_change_case_lower_tr_auxi:Nw #1#2 \q_recursion_stop
23038   {
23039     \tl_if_head_is_N_type:nTF {#2}
23040     { \__tl_change_case_lower_tr_auxii:Nw #2 \q_recursion_stop }
23041     { \__tl_change_case_output:Vwn \c__unicode_dotless_i_tl }
23042     #1 #2 \q_recursion_stop
23043   }
23044 \cs_new:Npn \__tl_change_case_lower_tr_auxii:Nw #1#2 \q_recursion_stop
23045 {
23046   \__tl_change_case_if_expandable:NTF #1
23047   {

```

```

23048         \exp_after:wN \__tl_change_case_lower_tr_auxi:Nw #1
23049         #2 \q_recursion_stop
23050     }
23051     {
23052         \bool_lazy_or:nnTF
23053         { \token_if_cs_p:N #1 }
23054         { ! \int_compare_p:nNn { '#1 } = { "0307 } }
23055         { \__tl_change_case_output:Vwn \c__unicode_dotless_i_tl }
23056         {
23057             \__tl_change_case_output:nwn { i }
23058             \use_i:nn
23059         }
23060     }
23061 }
23062 }

```

For 8-bit engines, dot-above is not available so there is a simple test for an upper-case I. Then we can look for the UTF-8 representation of an upper case dotted-I without the combining char. If it's not there, preserve the UTF-8 sequence as-is.

```

23063 {
23064     \cs_new:Npn \__tl_change_case_lower_tr:Nnw #1#2
23065     {
23066         \int_compare:nNnTF { '#1 } = { "0049 }
23067         { \__tl_change_case_output:Vwn \c__unicode_dotless_i_tl }
23068         {
23069             \int_compare:nNnTF { '#1 } = { 196 }
23070             { \__tl_change_case_lower_tr_auxi:Nw #1 {#2} }
23071             {#2}
23072         }
23073     }
23074     \cs_new:Npn \__tl_change_case_lower_tr_auxi:Nw #1#2#3#4
23075     {
23076         \int_compare:nNnTF { '#4 } = { 176 }
23077         {
23078             \__tl_change_case_output:nwn { i }
23079             #3
23080         }
23081         {
23082             #2
23083             #3 #4
23084         }
23085     }
23086 }

```

Upper casing is easier: just one exception with no context.

```

23087 \cs_new:Npn \__tl_change_case_upper_tr:Nnw #1#2
23088 {
23089     \int_compare:nNnTF { '#1 } = { "0069 }
23090     { \__tl_change_case_output:Vwn \c__unicode_dotted_I_tl }
23091     {#2}
23092 }

```

Straight copies.

```

23093 \cs_new_eq:NN \__tl_change_case_lower_az:Nnw \__tl_change_case_lower_tr:Nnw
23094 \cs_new_eq:NN \__tl_change_case_upper_az:Nnw \__tl_change_case_upper_tr:Nnw

```

(End definition for `\_tl_change_case_lower_tr:Nnw` and others.)

`\_tl_change_case_lower_lt:Nnw` For Lithuanian, the issue to be dealt with is dots over lower case letters: these should be present if there is another accent. That means that there is some work to do when lower casing I and J. The first step is a simple match attempt: `\c__tl_accents_lt_tl` contains accented upper case letters which should gain a dot-above char in their lower case form. This is done using f-type expansion so only one pass is needed to find if it works or not. If there was no hit, the second stage is to check for I, J and I-ogonek, and if the current char is a match to look for a following accent.

```

23095 \cs_new:Npn \_tl_change_case_lower_lt:Nnw #1
23096 {
23097   \exp_args:Nf \_tl_change_case_lower_lt:nNnw
23098   { \str_case:nVF #1 \c__unicode_accents_lt_tl \exp_stop_f: }
23099   #1
23100 }
23101 \cs_new:Npn \_tl_change_case_lower_lt:nNnw #1#2
23102 {
23103   \tl_if_blank:nTF {#1}
23104   {
23105     \exp_args:Nf \_tl_change_case_lower_lt:nnw
23106     {
23107       \int_case:nnF {‘#2}
23108       {
23109         { "0049 } i
23110         { "004A } j
23111         { "012E } \c__unicode_i_ogonek_tl
23112       }
23113       \exp_stop_f:
23114     }
23115   }
23116   {
23117     \_tl_change_case_output:nwn {#1}
23118     \use_none:n
23119   }
23120 }
23121 \cs_new:Npn \_tl_change_case_lower_lt:nnw #1#2
23122 {
23123   \tl_if_blank:nTF {#1}
23124   {#2}
23125   {
23126     \_tl_change_case_output:nwn {#1}
23127     \_tl_change_case_lower_lt:Nw
23128   }
23129 }

```

Grab the next char and see if it is one of the accents used in Lithuanian: if it is, add the dot-above char into the output.

```

23130 \cs_new:Npn \_tl_change_case_lower_lt:Nw #1#2 \q_recursion_stop
23131 {
23132   \tl_if_head_is_N_type:nT {#2}
23133   { \_tl_change_case_lower_lt:NNw }
23134   #1 #2 \q_recursion_stop
23135 }
23136 \cs_new:Npn \_tl_change_case_lower_lt:NNw #1#2#3 \q_recursion_stop

```

```

23137 {
23138   \_tl_change_case_if_expandable:NTF #2
23139   {
23140     \exp_after:wN \_tl_change_case_lower_lt:Nw \exp_after:wN #1 #2
23141     #3 \q_recursion_stop
23142   }
23143   {
23144     \bool_lazy_and:nnT
23145     { ! \token_if_cs_p:N #2 }
23146     {
23147       \bool_lazy_any_p:n
23148       {
23149         { \int_compare_p:nNn { '#2 } = { "0300 } }
23150         { \int_compare_p:nNn { '#2 } = { "0301 } }
23151         { \int_compare_p:nNn { '#2 } = { "0303 } }
23152       }
23153     }
23154     { \_tl_change_case_output:Vwn \c__unicode_dot_above_tl }
23155     #1 #2#3 \q_recursion_stop
23156   }
23157 }

```

For upper casing, the test required is for a dot-above char after an I, J or I-ogonek. First a test for the appropriate letter, and if found a look-ahead and potentially one token dropped.

```

23158 \cs_new:Npn \_tl_change_case_upper_lt:Nnw #1
23159 {
23160   \exp_args:Nf \_tl_change_case_upper_lt:nnw
23161   {
23162     \int_case:nnF { '#1 }
23163     {
23164       { "0069 } I
23165       { "006A } J
23166       { "012F } \c__unicode_I_ogonek_tl
23167     }
23168     \exp_stop_f:
23169   }
23170 }
23171 \cs_new:Npn \_tl_change_case_upper_lt:nnw #1#2
23172 {
23173   \tl_if_blank:nTF {#1}
23174   {#2}
23175   {
23176     \_tl_change_case_output:nnw {#1}
23177     \_tl_change_case_upper_lt:Nw
23178   }
23179 }
23180 \cs_new:Npn \_tl_change_case_upper_lt:Nw #1#2 \q_recursion_stop
23181 {
23182   \tl_if_head_is_N_type:nT {#2}
23183   { \_tl_change_case_upper_lt:NNw }
23184   #1 #2 \q_recursion_stop
23185 }
23186 \cs_new:Npn \_tl_change_case_upper_lt:NNw #1#2#3 \q_recursion_stop

```



```

23187 {
23188   \_tl_change_case_if_expandable:NTF #2
23189   {
23190     \exp_after:wN \_tl_change_case_upper_lt:Nw \exp_after:wN #1 #2
23191     #3 \q_recursion_stop
23192   }
23193   {
23194     \bool_lazy_and:nnTF
23195     { ! \token_if_cs_p:N #2 }
23196     { \int_compare_p:nNn { '#2 } = { "0307 } }
23197     { #1 }
23198     { #1 #2 }
23199     #3 \q_recursion_stop
23200   }
23201 }

```

(End definition for \\_tl\_change\_case\_lower\_lt:Nnw and others.)

\\_tl\_change\_case\_upper\_de-alt:Nnw A simple alternative version for German.

```

23202 \cs_new:cpn { \_tl_change_case_upper_de-alt:Nnw } #1#2
23203 {
23204   \int_compare:nNnTF { '#1 } = { 223 }
23205   { \_tl_change_case_output:Vwn \c__unicode_upper_Eszett_tl }
23206   {#2}
23207 }

```

(End definition for \\_tl\_change\_case\_upper\_de-alt:Nnw.)

\\_unicode\_codepoint\_to\_UTFviii:n This code converts a codepoint into the correct UTF-8 representation. As there are a variable number of octets, the result starts with the numeral 1–4 to indicate the nature of the returned value. Note that this code covers the full range even though at this stage it is not required here. Also note that longer-term this is likely to need a public interface and/or moving to l3str (see experimental string conversions). In terms of the algorithm itself, see <https://en.wikipedia.org/wiki/UTF-8> for the octet pattern.

```

23208 \cs_new:Npn \_unicode_codepoint_to_UTFviii:n #1
23209 {
23210   \exp_args:Nf \_unicode_codepoint_to_UTFviii_auxi:n
23211   { \int_eval:n {#1} }
23212 }
23213 \cs_new:Npn \_unicode_codepoint_to_UTFviii_auxi:n #1
23214 {
23215   \if_int_compare:w #1 > "80 ~
23216   \if_int_compare:w #1 < "800 ~
23217   2
23218   \_unicode_codepoint_to_UTFviii_auxii:Nnn C {#1} { 64 }
23219   \_unicode_codepoint_to_UTFviii_auxiii:n {#1}
23220   \else:
23221   \if_int_compare:w #1 < "10000 ~
23222   3
23223   \_unicode_codepoint_to_UTFviii_auxii:Nnn E {#1} { 64 * 64 }
23224   \_unicode_codepoint_to_UTFviii_auxiii:n {#1}
23225   \_unicode_codepoint_to_UTFviii_auxiii:n
23226   { \int_div_truncate:nn {#1} { 64 } }
23227   \else:

```

```

23228         4
23229         \__unicode_codepoint_to_UTFviii_auxii:Nnn F
23230         {#1} { 64 * 64 * 64 }
23231         \__unicode_codepoint_to_UTFviii_auxiii:n
23232         { \int_div_truncate:nn {#1} { 64 * 64 } }
23233         \__unicode_codepoint_to_UTFviii_auxiii:n
23234         { \int_div_truncate:nn {#1} { 64 } }
23235         \__unicode_codepoint_to_UTFviii_auxiii:n {#1}
23236
23237         \fi:
23238         \fi:
23239         \else:
23240         1 {#1}
23241         \fi:
23242     }
23243 \cs_new:Npn \__unicode_codepoint_to_UTFviii_auxii:Nnn #1#2#3
23244 { { \int_eval:n { "#10 + \int_div_truncate:nn {#2} {#3} } } }
23245 \cs_new:Npn \__unicode_codepoint_to_UTFviii_auxiii:n #1
23246 { { \int_eval:n { \int_mod:nn {#1} { 64 } + 128 } } }

```

(End definition for \\_\_unicode\_codepoint\_to\_UTFviii:n and others.)

\c\_\_unicode\_std\_sigma\_tl The above needs various special token lists containing pre-formed characters. This set are only available in Unicode engines, with no-op definitions for 8-bit use.

```

\c__unicode_final_sigma_tl
\c__unicode_accents_lt_tl
\c__unicode_dot_above_tl
\c__unicode_upper_Eszett_tl
23247 \cs_if_exist:NTF \utex_char:D
23248 {
23249     \tl_const:Nx \c__unicode_std_sigma_tl { \utex_char:D "03C3 ~ }
23250     \tl_const:Nx \c__unicode_final_sigma_tl { \utex_char:D "03C2 ~ }
23251     \tl_const:Nx \c__unicode_accents_lt_tl
23252     {
23253         \utex_char:D "00CC ~
23254         { \utex_char:D "0069 ~ \utex_char:D "0307 ~ \utex_char:D "0300 ~ }
23255         \utex_char:D "00CD ~
23256         { \utex_char:D "0069 ~ \utex_char:D "0307 ~ \utex_char:D "0301 ~ }
23257         \utex_char:D "0128 ~
23258         { \utex_char:D "0069 ~ \utex_char:D "0307 ~ \utex_char:D "0303 ~ }
23259     }
23260     \tl_const:Nx \c__unicode_dot_above_tl { \utex_char:D "0307 ~ }
23261     \tl_const:Nx \c__unicode_upper_Eszett_tl { \utex_char:D "1E9E ~ }
23262 }
23263 {
23264     \tl_const:Nn \c__unicode_std_sigma_tl { }
23265     \tl_const:Nn \c__unicode_final_sigma_tl { }
23266     \tl_const:Nn \c__unicode_accents_lt_tl { }
23267     \tl_const:Nn \c__unicode_dot_above_tl { }
23268     \tl_const:Nn \c__unicode_upper_Eszett_tl { }
23269 }

```

(End definition for \c\_\_unicode\_std\_sigma\_tl and others.)

\c\_\_unicode\_dotless\_i\_tl For cases where there is an 8-bit option in the T1 font set up, a variant is provided in both cases.

```

\c__unicode_dotted_I_tl
\c__unicode_i_ogonek_tl
\c__unicode_I_ogonek_tl
23270 \group_begin:
23271 \cs_if_exist:NTF \utex_char:D

```

```

23272 {
23273   \cs_set_protected:Npn \__tl_tmp:w #1#2
23274   { \tl_const:Nx #1 { \utex_char:D "#2 ~ } }
23275 }
23276 {
23277   \cs_set_protected:Npn \__tl_tmp:w #1#2
23278   {
23279     \group_begin:
23280     \cs_set_protected:Npn \__tl_tmp:w ##1##2##3
23281     {
23282       \tl_const:Nx #1
23283       {
23284         \exp_after:wN \exp_after:wN \exp_after:wN
23285         \exp_not:N \__char_generate:nn {##2} { 13 }
23286         \exp_after:wN \exp_after:wN \exp_after:wN
23287         \exp_not:N \__char_generate:nn {##3} { 13 }
23288       }
23289     }
23290     \tl_set:Nx \l__tl_internal_a_tl
23291     { \__unicode_codepoint_to_UTFviii:n {"#2} }
23292     \exp_after:wN \__tl_tmp:w \l__tl_internal_a_tl
23293   \group_end:
23294 }
23295 }
23296 \__tl_tmp:w \c__unicode_dotless_i_tl { 0131 }
23297 \__tl_tmp:w \c__unicode_dotted_I_tl { 0130 }
23298 \__tl_tmp:w \c__unicode_i_ogonek_tl { 012F }
23299 \__tl_tmp:w \c__unicode_I_ogonek_tl { 012E }
23300 \group_end:

```

(End definition for \c\_\_unicode\_dotless\_i\_tl and others.)

For 8-bit engines we now need to define the case-change data for the multi-octet mappings. These need a list of what code points are doable in T1 so the list is hard coded (there's no saving in loading the mappings dynamically). All of the straight-forward ones have two octets, so that is taken as read.

```

23301 \group_begin:
23302   \bool_lazy_or:nnT
23303   { \sys_if_engine_pdftex_p: }
23304   { \sys_if_engine_uptex_p: }
23305   {
23306     \cs_set_protected:Npn \__tl_loop:nn #1#2
23307     {
23308       \quark_if_recursion_tail_stop:n {#1}
23309       \tl_set:Nx \l__tl_internal_a_tl
23310       {
23311         \__unicode_codepoint_to_UTFviii:n {"#1}
23312         \__unicode_codepoint_to_UTFviii:n {"#2}
23313       }
23314       \exp_after:wN \__tl_tmp:w \l__tl_internal_a_tl
23315       \__tl_loop:nn
23316     }
23317   \cs_set_protected:Npn \__tl_tmp:w #1#2#3#4#5#6
23318   {
23319     \tl_const:cx

```

```

23320         {
23321             c__unicode_lower_
23322             \char_generate:nn {#2} { 12 }
23323             \char_generate:nn {#3} { 12 }
23324             _tl
23325         }
23326         {
23327             \exp_after:wN \exp_after:wN \exp_after:wN
23328             \exp_not:N \__char_generate:nn {#5} { 13 }
23329             \exp_after:wN \exp_after:wN \exp_after:wN
23330             \exp_not:N \__char_generate:nn {#6} { 13 }
23331         }
23332     \tl_const:cx
23333     {
23334         c__unicode_upper_
23335         \char_generate:nn {#5} { 12 }
23336         \char_generate:nn {#6} { 12 }
23337         _tl
23338     }
23339     {
23340         \exp_after:wN \exp_after:wN \exp_after:wN
23341         \exp_not:N \__char_generate:nn {#2} { 13 }
23342         \exp_after:wN \exp_after:wN \exp_after:wN
23343         \exp_not:N \__char_generate:nn {#3} { 13 }
23344     }
23345 }
23346 \__tl_loop:nn
23347 { 00C0 } { 00E0 }
23348 { 00C2 } { 00E2 }
23349 { 00C3 } { 00E3 }
23350 { 00C4 } { 00E4 }
23351 { 00C5 } { 00E5 }
23352 { 00C6 } { 00E6 }
23353 { 00C7 } { 00E7 }
23354 { 00C8 } { 00E8 }
23355 { 00C9 } { 00E9 }
23356 { 00CA } { 00EA }
23357 { 00CB } { 00EB }
23358 { 00CC } { 00EC }
23359 { 00CD } { 00ED }
23360 { 00CE } { 00EE }
23361 { 00CF } { 00EF }
23362 { 00D0 } { 00F0 }
23363 { 00D1 } { 00F1 }
23364 { 00D2 } { 00F2 }
23365 { 00D3 } { 00F3 }
23366 { 00D4 } { 00F4 }
23367 { 00D5 } { 00F5 }
23368 { 00D6 } { 00F6 }
23369 { 00D8 } { 00F8 }
23370 { 00D9 } { 00F9 }
23371 { 00DA } { 00FA }
23372 { 00DB } { 00FB }
23373 { 00DC } { 00FC }

```

23374	{ 00DD }	{ 00FD }
23375	{ 00DE }	{ 00FE }
23376	{ 0100 }	{ 0101 }
23377	{ 0102 }	{ 0103 }
23378	{ 0104 }	{ 0105 }
23379	{ 0106 }	{ 0107 }
23380	{ 0108 }	{ 0109 }
23381	{ 010A }	{ 010B }
23382	{ 010C }	{ 010D }
23383	{ 010E }	{ 010F }
23384	{ 0110 }	{ 0111 }
23385	{ 0112 }	{ 0113 }
23386	{ 0114 }	{ 0115 }
23387	{ 0116 }	{ 0117 }
23388	{ 0118 }	{ 0119 }
23389	{ 011A }	{ 011B }
23390	{ 011C }	{ 011D }
23391	{ 011E }	{ 011F }
23392	{ 0120 }	{ 0121 }
23393	{ 0122 }	{ 0123 }
23394	{ 0124 }	{ 0125 }
23395	{ 0128 }	{ 0129 }
23396	{ 012A }	{ 012B }
23397	{ 012C }	{ 012D }
23398	{ 012E }	{ 012F }
23399	{ 0132 }	{ 0133 }
23400	{ 0134 }	{ 0135 }
23401	{ 0136 }	{ 0137 }
23402	{ 0139 }	{ 013A }
23403	{ 013B }	{ 013C }
23404	{ 013E }	{ 013F }
23405	{ 0141 }	{ 0142 }
23406	{ 0143 }	{ 0144 }
23407	{ 0145 }	{ 0146 }
23408	{ 0147 }	{ 0148 }
23409	{ 014A }	{ 014B }
23410	{ 014C }	{ 014D }
23411	{ 014E }	{ 014F }
23412	{ 0150 }	{ 0151 }
23413	{ 0152 }	{ 0153 }
23414	{ 0154 }	{ 0155 }
23415	{ 0156 }	{ 0157 }
23416	{ 0158 }	{ 0159 }
23417	{ 015A }	{ 015B }
23418	{ 015C }	{ 015D }
23419	{ 015E }	{ 015F }
23420	{ 0160 }	{ 0161 }
23421	{ 0162 }	{ 0163 }
23422	{ 0164 }	{ 0165 }
23423	{ 0168 }	{ 0169 }
23424	{ 016A }	{ 016B }
23425	{ 016C }	{ 016D }
23426	{ 016E }	{ 016F }
23427	{ 0170 }	{ 0171 }

```

23428     { 0172 } { 0173 }
23429     { 0174 } { 0175 }
23430     { 0176 } { 0177 }
23431     { 0178 } { 00FF }
23432     { 0179 } { 017A }
23433     { 017B } { 017C }
23434     { 017D } { 017E }
23435     { 01CD } { 01CE }
23436     { 01CF } { 01D0 }
23437     { 01D1 } { 01D2 }
23438     { 01D3 } { 01D4 }
23439     { 01E2 } { 01E3 }
23440     { 01E6 } { 01E7 }
23441     { 01E8 } { 01E9 }
23442     { 01EA } { 01EB }
23443     { 01F4 } { 01F5 }
23444     { 0218 } { 0219 }
23445     { 021A } { 021B }
23446     \q_recursion_tail ?
23447     \q_recursion_stop
23448     \cs_set_protected:Npn \__tl_tmp:w #1#2#3
23449     {
23450         \group_begin:
23451         \cs_set_protected:Npn \__tl_tmp:w ##1##2##3
23452         {
23453             \tl_const:cx
23454             {
23455                 c__unicode_ #3 _
23456                 \char_generate:nn {##2} { 12 }
23457                 \char_generate:nn {##3} { 12 }
23458                 _tl
23459             }
23460             {#2}
23461         }
23462         \tl_set:Nx \l__tl_internal_a_tl
23463         { \__unicode_codepoint_to_UTFviii:n { "#1 } }
23464         \exp_after:wN \__tl_tmp:w \l__tl_internal_a_tl
23465         \group_end:
23466     }
23467     \__tl_tmp:w { 00DF } { SS } { upper }
23468     \__tl_tmp:w { 00DF } { Ss } { mixed }
23469     \__tl_tmp:w { 0131 } { I } { upper }
23470 }
23471 \group_end:

```

The (fixed) look-up mappings for letter-like control sequences.

```

23472 \group_begin:
23473 \cs_set_protected:Npn \__tl_change_case_setup:NN #1#2
23474 {
23475     \quark_if_recursion_tail_stop:N #1
23476     \tl_const:cn { c__tl_change_case_lower_ \token_to_str:N #1 _tl } { #2 }
23477     \tl_const:cn { c__tl_change_case_upper_ \token_to_str:N #2 _tl } { #1 }
23478     \__tl_change_case_setup:NN
23479 }
23480 \__tl_change_case_setup:NN

```

```

23481 \AA \aa
23482 \AE \ae
23483 \DH \dh
23484 \DJ \dj
23485 \IJ \ij
23486 \L \l
23487 \NG \ng
23488 \O \o
23489 \OE \oe
23490 \SS \ss
23491 \TH \th
23492 \q_recursion_tail ?
23493 \q_recursion_stop
23494 \tl_const:cn { c__tl_change_case_upper_ \token_to_str:N \i _tl } { I }
23495 \tl_const:cn { c__tl_change_case_upper_ \token_to_str:N \j _tl } { J }
23496 \group_end:

```

`\l_tl_case_change_accents_tl` A list of accents to leave alone.

```

23497 \tl_new:N \l_tl_case_change_accents_tl
23498 \tl_set:Nn \l_tl_case_change_accents_tl
23499 { \" \' \. \^ \' \~ \c \H \k \r \t \u \v }

```

(End definition for `\l_tl_case_change_accents_tl`. This variable is documented on page 238.)

`\_tl_change_case_mixed_nl:Nnw` For Dutch, there is a single look-ahead test for `ij` when title casing. If the appropriate letters are found, produce `IJ` and gobble the `j/J`.

```

\_tl_change_case_mixed_nl:Nw
\_tl_change_case_mixed_nl:NNw
23500 \cs_new:Npn \_tl_change_case_mixed_nl:Nnw #1
23501 {
23502   \bool_lazy_or:nnTF
23503     { \int_compare_p:nNn { '#1 } = { 'i } }
23504     { \int_compare_p:nNn { '#1 } = { 'I } }
23505     {
23506       \_tl_change_case_output:nwn { I }
23507       \_tl_change_case_mixed_nl:Nw
23508     }
23509   }
23510 \cs_new:Npn \_tl_change_case_mixed_nl:Nw #1#2 \q_recursion_stop
23511 {
23512   \tl_if_head_is_N_type:nT {#2}
23513   { \_tl_change_case_mixed_nl:NNw }
23514   #1 #2 \q_recursion_stop
23515 }
23516 \cs_new:Npn \_tl_change_case_mixed_nl:NNw #1#2#3 \q_recursion_stop
23517 {
23518   \_tl_change_case_if_expandable:NTF #2
23519   {
23520     \exp_after:wN \_tl_change_case_mixed_nl:Nw \exp_after:wN #1 #2
23521     #3 \q_recursion_stop
23522   }
23523   {
23524     \bool_lazy_and:nnTF
23525       { ! ( \token_if_cs_p:N #2 ) }
23526       {
23527         \bool_lazy_or_p:nn

```

```

23528         { \int_compare_p:nNn { '#2 } = { 'j } }
23529         { \int_compare_p:nNn { '#2 } = { 'J } }
23530     }
23531     {
23532         \_tl_change_case_output:nwn { J }
23533         #1
23534     }
23535     { #1 #2 }
23536     #3 \q_recursion_stop
23537 }
23538 }

```

(End definition for `\_tl_change_case_mixed_n1:Nnw`, `\_tl_change_case_mixed_n1:Nw`, and `\_tl_change_case_mixed_n1:NNw`.)

`\l_tl_case_change_math_tl` The list of token pairs which are treated as math mode and so not case changed.

```

23539 \tl_new:N \l_tl_case_change_math_tl
23540 \*package
23541 \tl_set:Nn \l_tl_case_change_math_tl
23542 { $ $ \ ( \ ) }
23543 \*package

```

(End definition for `\l_tl_case_change_math_tl`. This variable is documented on page 237.)

`\l_tl_case_change_exclude_tl` The list of commands for which an argument is not case changed.

```

23544 \tl_new:N \l_tl_case_change_exclude_tl
23545 \*package
23546 \tl_set:Nn \l_tl_case_change_exclude_tl
23547 { \cite \ensuremath \label \ref }
23548 \*package

```

(End definition for `\l_tl_case_change_exclude_tl`. This variable is documented on page 238.)

`\l_tl_mixed_case_ignore_tl` Characters to skip over when finding the first letter in a word to be mixed cased.

```

23549 \tl_new:N \l_tl_mixed_case_ignore_tl
23550 \tl_set:Nx \l_tl_mixed_case_ignore_tl
23551 {
23552     ( % )
23553     [ % ]
23554     \cs_to_str:N \{ % \%
23555     '
23556     -
23557 }

```

(End definition for `\l_tl_mixed_case_ignore_tl`. This variable is documented on page 239.)

## 42.15.2 Other additions to `l3tl`

`\tl_rand_item:n` Importantly `\tl_item:nn` only evaluates its argument once.

```

\tl_rand_item:N 23558 \cs_new:Npn \tl_rand_item:n #1
\tl_rand_item:c 23559 {
23560     \tl_if_blank:nF {#1}
23561     { \tl_item:nn {#1} { \int_rand:nn { 1 } { \tl_count:n {#1} } } }
23562 }
23563 \cs_new:Npn \tl_rand_item:N { \exp_args:No \tl_rand_item:n }
23564 \cs_generate_variant:Nn \tl_rand_item:N { c }

```



(End definition for `\tl_rand_item:n` and `\tl_rand_item:N`. These functions are documented on page 240.)

```

\tl_range:Nnn To avoid checking for the end of the token list at every step, start by counting the number
\tl_range:cnn l of items and “normalizing” the bounds, namely clamping them to the interval  $[0, l]$  and
\tl_range:nnn dealing with negative indices. More precisely, \__tl_range:nnw receives the number of
\__tl_range:nnnw items to skip at the beginning of the token list, and the index of the last item to keep.
\__tl_range:nnw If nothing should be kept, leave {}: this stops the f-expansion of \tl_head:f and that
\__tl_range_normalize:nn function produces an empty result. Otherwise, repeatedly call \__tl_range_skip:w
\__tl_range_collect:w to delete #1 items from the input stream (the extra brace group avoids an off-by-one
\__tl_range_skip:w mistake), then repeatedly call \__tl_range_collect:w to store in its second argument
the items to be kept. Eventually, the result is a brace group followed by the rest of the
token list, and \tl_head:f cleans up and gives the result in \exp_not:n.

23565 \cs_new:Npn \tl_range:Nnn { \exp_args:No \tl_range:nnn }
23566 \cs_generate_variant:Nn \tl_range:Nnn { c }
23567 \cs_new:Npn \tl_range:nnn #1#2#3
23568 {
23569   \tl_head:f
23570   {
23571     \exp_args:Nf \__tl_range:nnnw { \tl_count:n {#1} } {#2} {#3}
23572     #1
23573   }
23574 }
23575 \cs_new:Npn \__tl_range:nnnw #1#2#3
23576 {
23577   \exp_args:Nff \__tl_range:nnw
23578   {
23579     \exp_args:Nf \__tl_range_normalize:nn
23580     { \int_eval:n { #2 - 1 } } {#1}
23581   }
23582   {
23583     \exp_args:Nf \__tl_range_normalize:nn
23584     { \int_eval:n {#3} } {#1}
23585   }
23586 }
23587 \cs_new:Npn \__tl_range:nnw #1#2
23588 {
23589   \if_int_compare:w #2 > #1 \exp_stop_f: \else:
23590     \exp_after:wN { \exp_after:wN }
23591   \fi:
23592   \exp_after:wN \__tl_range_collect:w
23593   \__int_value:w \__int_eval:w #2 - #1 \exp_after:wN ;
23594   \exp_after:wN { \exp_after:wN }
23595   \exp:w \__tl_range_skip:w #1 ; { }
23596 }
23597 \cs_new:Npn \__tl_range_skip:w #1 ; #2
23598 {
23599   \if_int_compare:w #1 > 0 \exp_stop_f:
23600     \exp_after:wN \__tl_range_skip:w
23601     \__int_value:w \__int_eval:w #1 - 1 \exp_after:wN ;
23602   \else:
23603     \exp_after:wN \exp_end:
23604   \fi:

```

```

23605 }
23606 \cs_new:Npn \__tl_range_collect:w #1 ; #2#3
23607 {
23608   \if_int_compare:w #1 > 1 \exp_stop_f:
23609     \exp_after:wN \__tl_range_collect:w
23610     \__int_value:w \__int_eval:w #1 - 1 \exp_after:wN ;
23611   \fi:
23612   { #2 {#3} }
23613 }

```

(End definition for `\tl_range:Nnn` and others. These functions are documented on page 240.)

`\__tl_range_normalize:nn` This function converts an  $\langle index \rangle$  argument into an explicit position in the token list (a result of 0 denoting “out of bounds”). Expects two explicit integer arguments: the  $\langle index \rangle$  #1 and the string count #2. If #1 is negative, replace it by #1 + #2 + 1, then limit to the range [0, #2].

```

23614 \cs_new:Npn \__tl_range_normalize:nn #1#2
23615 {
23616   \int_eval:n
23617   {
23618     \if_int_compare:w #1 < 0 \exp_stop_f:
23619       \if_int_compare:w #1 < -#2 \exp_stop_f:
23620       0
23621     \else:
23622       #1 + #2 + 1
23623     \fi:
23624   \else:
23625     \if_int_compare:w #1 < #2 \exp_stop_f:
23626     #1
23627   \else:
23628     #2
23629   \fi:
23630   \fi:
23631 }
23632 }

```

(End definition for `\__tl_range_normalize:nn`.)

## 42.16 Additions to l3tokens

23633  $\langle @@=peek \rangle$

**`\peek_N_type:TF`** All tokens are N-type tokens, except in four cases: begin-group tokens, end-group tokens, space tokens with character code 32, and outer tokens. Since `\l_peek_token` might be outer, we cannot use the convenient `\bool_if:nTF` function, and must resort to the old trick of using `\ifodd` to expand a set of tests. The **false** branch of this test is taken if the token is one of the first three kinds of non-N-type tokens (explicit or implicit), thus we call `\__peek_false:w`. In the **true** branch, we must detect outer tokens, without impacting performance too much for non-outer tokens. The first filter is to search for **outer** in the meaning of `\l_peek_token`. If that is absent, `\use_none_delimit_by_q_stop:w` cleans up, and we call `\__peek_true:w`. Otherwise, the token can be a non-outer macro or a primitive mark whose parameter or replacement text contains **outer**, it can be the primitive `\outer`, or it can be an outer token. Macros and marks would have **ma** in the part before the first occurrence of **outer**; the meaning of `\outer` has nothing after

outer, contrarily to outer macros; and that covers all cases, calling `\__peek_true:w` or `\__peek_false:w` as appropriate. Here, there is no *search token*, so we feed a dummy `\scan_stop:` to the `\__peek_token_generic:NNTF` function.

```

23634 \group_begin:
23635   \cs_set_protected:Npn \__peek_tmp:w #1 \q_stop
23636   {
23637     \cs_new_protected:Npn \__peek_execute_branches_N_type:
23638     {
23639       \if_int_odd:w
23640         \if_catcode:w \exp_not:N \l_peek_token { 0 \exp_stop_f: \fi:
23641         \if_catcode:w \exp_not:N \l_peek_token } 0 \exp_stop_f: \fi:
23642         \if_meaning:w \l_peek_token \c_space_token 0 \exp_stop_f: \fi:
23643         1 \exp_stop_f:
23644         \exp_after:wN \__peek_N_type:w
23645         \token_to_meaning:N \l_peek_token
23646         \q_mark \__peek_N_type_aux:nnw
23647         #1 \q_mark \use_none_delimit_by_q_stop:w
23648         \q_stop
23649         \exp_after:wN \__peek_true:w
23650       \else:
23651         \exp_after:wN \__peek_false:w
23652       \fi:
23653     }
23654     \cs_new_protected:Npn \__peek_N_type:w ##1 #1 ##2 \q_mark ##3
23655     { ##3 {##1} {##2} }
23656   }
23657   \exp_after:wN \__peek_tmp:w \tl_to_str:n { outer } \q_stop
23658 \group_end:
23659 \cs_new_protected:Npn \__peek_N_type_aux:nnw #1 #2 #3 \fi:
23660 {
23661   \fi:
23662   \tl_if_in:noTF {#1} { \tl_to_str:n {ma} }
23663   { \__peek_true:w }
23664   { \tl_if_empty:nTF {#2} { \__peek_true:w } { \__peek_false:w } }
23665 }
23666 \cs_new_protected:Npn \peek_N_type:TF
23667 { \__peek_token_generic:NNTF \__peek_execute_branches_N_type: \scan_stop: }
23668 \cs_new_protected:Npn \peek_N_type:T
23669 { \__peek_token_generic:NNT \__peek_execute_branches_N_type: \scan_stop: }
23670 \cs_new_protected:Npn \peek_N_type:F
23671 { \__peek_token_generic:NNTF \__peek_execute_branches_N_type: \scan_stop: }

(End definition for \peek_N_type:TF and others. These functions are documented on page 241.)

23672 </initex | package>

```

## 43 l3luatex implementation

```

23673 (*initex | package)

```

### 43.1 Breaking out to Lua

```

23674 (*tex)

```

`\lua_now_x:n` Wrappers around the primitives. As with engines other than LuaTeX these have to be macros, we give them the same status in all cases. When LuaTeX is not in use, simply give an error message/

```

\lua_now_x:n
\lua_now:n
\lua_shipout_x:n
\lua_shipout:n
\lua_escape_x:n
\lua_escape:n
23675 \cs_new:Npn \lua_now_x:n #1 { \luatex_directlua:D {#1} }
23676 \cs_new:Npn \lua_now:n #1 { \lua_now_x:n { \exp_not:n {#1} } }
23677 \cs_new_protected:Npn \lua_shipout_x:n #1 { \luatex_latelua:D {#1} }
23678 \cs_new_protected:Npn \lua_shipout:n #1
23679 { \lua_shipout_x:n { \exp_not:n {#1} } }
23680 \cs_new:Npn \lua_escape_x:n #1 { \luatex_luaescapestring:D {#1} }
23681 \cs_new:Npn \lua_escape:n #1 { \lua_escape_x:n { \exp_not:n {#1} } }
23682 \sys_if_engine luatex:F
23683 {
23684   \clist_map_inline:nn
23685   { \lua_now_x:n , \lua_now:n , \lua_escape_x:n , \lua_escape:n }
23686   {
23687     \cs_set:Npn #1 ##1
23688     {
23689       \__msg_kernel_expandable_error:nnn
23690       { kernel } { luatex-required } { #1 }
23691     }
23692   }
23693   \clist_map_inline:nn
23694   { \lua_shipout_x:n , \lua_shipout:n }
23695   {
23696     \cs_set_protected:Npn #1 ##1
23697     {
23698       \__msg_kernel_error:nnn
23699       { kernel } { luatex-required } { #1 }
23700     }
23701   }
23702 }

```

(End definition for `\lua_now_x:n` and others. These functions are documented on page 242.)

## 43.2 Messages

```

23703 \__msg_kernel_new:nnnn { kernel } { luatex-required }
23704 { LuaTeX~engine~not~in~use!~Ignoring~#1. }
23705 {
23706   The~feature~you~are~using~is~only~available~
23707   with~the~LuaTeX~engine.~LaTeX3~ignored~'~#1'~.
23708 }
23709 </tex>

```

## 43.3 Lua functions for internal use

```

23710 <*lua>

```

Most of the emulation of pdfTeX here is based heavily on Heiko Oberdiek's `pdfTeX-cmds` package.

**13kernel** Create a table for the kernel's own use.

```

23711 13kernel = 13kernel or { }

```

(End definition for `l3kernel`.)

Local copies of global tables.

```
23712 local io      = io
23713 local kpse     = kpse
23714 local lfs      = lfs
23715 local math     = math
23716 local md5      = md5
23717 local os       = os
23718 local string   = string
23719 local tex      = tex
23720 local unicode  = unicode
```

Local copies of standard functions.

```
23721 local abs      = math.abs
23722 local byte      = string.byte
23723 local floor     = math.floor
23724 local format    = string.format
23725 local gsub      = string.gsub
23726 local kpse_find = kpse.find_file
23727 local lfs_attr  = lfs.attributes
23728 local md5_sum   = md5.sum
23729 local open      = io.open
23730 local os_date   = os.date
23731 local setcatcode = tex.setcatcode
23732 local str_format = string.format
23733 local sprint    = tex.sprint
23734 local write     = tex.write
23735 local utf8_char = unicode.utf8.char
```

`escapehex` An internal auxiliary to convert a string to the matching hex escape. This works on a byte basis: extension to handled UTF-8 input is covered in `pdftexcmds` but is not currently required here.

```
23736 local function escapehex(str)
23737   write((gsub(str, ".",
23738     function (ch) return format("%02X", byte(ch)) end)))
23739 end
```

(End definition for `escapehex`.)

`l3kernel.charcat` Creating arbitrary chars needs a category code table. As set up here, one may have been assigned earlier (see `l3bootstrap`) or a hard-coded one is used. The latter is intended for format mode and should be adjusted to match an eventual allocator.

```
23740 local charcat_table = l3kernel.charcat_table or 1
23741 local function charcat(charcode, catcode)
23742   setcatcode(charcat_table, charcode, catcode)
23743   sprint(charcat_table, utf8_char(charcode))
23744 end
23745 l3kernel.charcat = charcat
```

(End definition for `l3kernel.charcat`.)

`l3kernel.filemdfivesum` Read an entire file and hash it: the hash function itself is a built-in. As Lua is byte-based there is no work needed here in terms of UTF-8 (see `pdftexcmds` and how it handles strings that have passed through LuaTeX).

```

23746 local function filemdfivesum(name)
23747   local file = kpse_find(name, "tex", true)
23748   if file then
23749     local f = open(file, "r")
23750     if f then
23751       local data = f:read("*a")
23752       escapehex(md5_sum(data))
23753       f:close()
23754     end
23755   end
23756 end
23757 l3kernel.filemdfivesum = filemdfivesum

```

(End definition for l3kernel.filemdfivesum.)

**l3kernel.filemoddate** See procedure makepdftime in utils.c of pdfTeX.

```

23758 local function filemoddate(name)
23759   local file = kpse_find(name, "tex", true)
23760   if file then
23761     local date = lfs_attr(file, "modification")
23762     if date then
23763       local d = os_date("!*t", date)
23764       if d.sec >= 60 then
23765         d.sec = 59
23766       end
23767       local u = os_date("!*t", date)
23768       local off = 60 * (d.hour - u.hour) + d.min - u.min
23769       if d.year ~= u.year then
23770         if d.year > u.year then
23771           off = off + 1440
23772         else
23773           off = off - 1440
23774         end
23775       elseif d.yday ~= u.yday then
23776         if d.yday > u.yday then
23777           off = off + 1440
23778         else
23779           off = off - 1440
23780         end
23781       end
23782       local timezone
23783       if off == 0 then
23784         timezone = "Z"
23785       else
23786         local hours = floor(off / 60)
23787         local mins = abs(off - hours * 60)
23788         timezone = str_format("%+03d", hours)
23789         .. " " .. str_format("%02d", mins) .. " "
23790       end
23791       write("D:"
23792         .. str_format("%04d", d.year)
23793         .. str_format("%02d", d.month)
23794         .. str_format("%02d", d.day)
23795         .. str_format("%02d", d.hour)

```

```

23796         .. str_format("%02d", d.min)
23797         .. str_format("%02d", d.sec)
23798         .. timezone)
23799     end
23800 end
23801 end
23802 l3kernel.filemoddate = filemoddate

```

(End definition for l3kernel.filemoddate.)

**l3kernel.filesize** A simple disk lookup.

```

23803 local function filesize(name)
23804     local file = kpse_find(name, "tex", true)
23805     if file then
23806         local size = lfs_attr(file, "size")
23807         if size then
23808             write(size)
23809         end
23810     end
23811 end
23812 l3kernel.filesize = filesize

```

(End definition for l3kernel.filesize.)

**l3kernel.strcmp** String comparison which gives the same results as pdfTeX's `\pdfstrcmp`, although the ordering should likely not be relied upon!

```

23813 local function strcmp(A, B)
23814     if A == B then
23815         write("0")
23816     elseif A < B then
23817         write("-1")
23818     else
23819         write("1")
23820     end
23821 end
23822 l3kernel.strcmp = strcmp

```

(End definition for l3kernel.strcmp.)

## 43.4 Generic Lua and font support

```

23823 ⟨*initex⟩

```

A small amount of generic code is used by almost all LuaTeX material so needs to be loaded by the format.

```

23824 attribute_count_name = "g__alloc_attribute_int"
23825 bytecode_count_name  = "g__alloc_bytecode_int"
23826 chunkname_count_name  = "g__alloc_chunkname_int"
23827 whatsit_count_name    = "g__alloc_whatsit_int"
23828 require("l3luatex")

```

With the above available the font loader code used by plain TeX and L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> when used with LuaTeX can be loaded here. This is thus being treated more-or-less as part of the engine itself.

```

23829 require("luaotfload-main")

```

```

23830 local _void = luaotfload.main()
23831  $\langle$ /initex $\rangle$ 
23832  $\langle$ /lua $\rangle$ 
23833  $\langle$ /initex | package $\rangle$ 

```

## 44 l3drivers Implementation

```

23834  $\langle$ *initex | package $\rangle$ 
23835  $\langle$ @@=driver $\rangle$ 

```

Whilst there is a reasonable amount of code overlap between drivers, it is much clearer to have the blocks more-or-less separated than run in together and DocStripped out in parts. As such, most of the following is set up on a per-driver basis, though there is some common code (again given in blocks not interspersed with other material).

All the file identifiers are up-front so that they come out in the right place in the files.

```

23836  $\langle$ *package $\rangle$ 
23837 \ProvidesExplFile
23838  $\langle$ *dvipdfmx $\rangle$ 
23839 {l3dvidpfmt.def}{2017/03/18}{ $\langle$  $\rangle$ }
23840 {L3 Experimental driver: dvipdfmx}
23841  $\langle$ /dvipdfmx $\rangle$ 
23842  $\langle$ *dvips $\rangle$ 
23843 {l3dvips.def}{2017/03/18}{ $\langle$  $\rangle$ }
23844 {L3 Experimental driver: dvips}
23845  $\langle$ /dvips $\rangle$ 
23846  $\langle$ *dvisvgm $\rangle$ 
23847 {l3dvisvgm.def}{2017/03/18}{ $\langle$  $\rangle$ }
23848 {L3 Experimental driver: dvisvgm}
23849  $\langle$ /dvisvgm $\rangle$ 
23850  $\langle$ *pdfmode $\rangle$ 
23851 {l3pdfmode.def}{2017/03/18}{ $\langle$  $\rangle$ }
23852 {L3 Experimental driver: PDF mode}
23853  $\langle$ /pdfmode $\rangle$ 
23854  $\langle$ *xdvipdfmx $\rangle$ 
23855 {l3xdvidpfmt.def}{2017/03/18}{ $\langle$  $\rangle$ }
23856 {L3 Experimental driver: xdvipdfmx}
23857  $\langle$ /xdvipdfmx $\rangle$ 
23858  $\langle$ /package $\rangle$ 

```

The order of the driver code here is such that we get somewhat logical outcomes in terms of code sharing whilst keeping things readable. (Trying to mix all of the code by concept is almost unmanageable.) The key parts which are shared are

- Color support is either `dvips`-like or `pdfmode`-like.
- `pdfmode` and `(x)dvipdfmx` share drawing routines.
- `xdvipdfmx` is largely the same as `dvipdfmx` so takes most of the same code.

### 44.1 Color support

Whilst `(x)dvipdfmx` does have its own approach to color specials, it is easier to use `dvips`-like ones for all cases except direct PDF output. As such the color code is collected here in two blocks.



#### 44.1.1 dvips-style

23859  $\langle *dvismgm | dvipdfmx | dvips | xdvipdfmx \rangle$

$\_\_\_driver\_color\_pickup$ : Allow for L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>.

```
23860  $\langle *package \rangle$ 
23861  $\backslash AtBeginDocument$ 
23862 {
23863    $\backslash @ifpackageloaded \{ color \}$ 
23864   {
23865      $\backslash cs\_new\_protected:Npn \_\_\_driver\_color\_pickup$ :
23866     {  $\backslash tl\_set\_eq:NN \backslash l\_color\_current\_tl \backslash current@color \}$ 
23867   }
23868   {  $\backslash cs\_new\_protected:Npn \_\_\_driver\_color\_pickup$ : { } }
23869 }
23870  $\langle /package \rangle$ 
```

(End definition for  $\_\_\_driver\_color\_pickup$ :.)

$\_\_\_driver\_color\_ensure\_current$ : Directly set the color using the specials: no optimisation here.

```
 $\_\_\_driver\_color\_reset$ : 23871  $\backslash cs\_new\_protected:Npn \_\_\_driver\_color\_ensure\_current$ :
23872 {
23873  $\langle *package \rangle$ 
23874    $\_\_\_driver\_color\_pickup$ :
23875  $\langle /package \rangle$ 
23876    $\backslash tex\_special:D \{ color\_push~\backslash l\_color\_current\_tl \}$ 
23877 }
23878  $\backslash cs\_new\_protected:Npn \_\_\_driver\_color\_reset$ :
23879 {  $\backslash tex\_special:D \{ color\_pop \}$  }
```

(End definition for  $\_\_\_driver\_color\_ensure\_current$ : and  $\_\_\_driver\_color\_reset$ :.)

23880  $\langle /dvismgm | dvipdfmx | dvips | xdvipdfmx \rangle$

#### 44.1.2 pdfmode

23881  $\langle *pdfmode \rangle$

$\_\_\_driver\_color\_pickup$ : The current color in driver-dependent format: pick up the package-mode data if available.  
 $\_\_\_driver\_color\_pickup\_aux$ : We end up converting back and forward in this route as we store our color data in dvips format.

```
23882  $\langle *package \rangle$ 
23883  $\backslash AtBeginDocument$ 
23884 {
23885    $\backslash @ifpackageloaded \{ color \}$ 
23886   {
23887      $\backslash cs\_new\_protected:Npn \_\_\_driver\_color\_pickup$ :
23888     {
23889        $\backslash tl\_set:Nx \backslash l\_color\_current\_tl$ 
23890       {
23891          $\backslash exp\_after:wN \_\_\_driver\_color\_pickup\_aux:w$ 
23892          $\backslash current@color ~ 0 ~ 0 ~ 0 ~ 0 \backslash q\_stop$ 
23893       }
23894     }
23895      $\backslash cs\_new:Npn \_\_\_driver\_color\_pickup\_aux:w \#1 ~ \#2 ~ \#3 ~ \#4 ~ \#5 ~ \#6 \backslash q\_stop$ 
23896     {
```

```

23897         \str_if_eq:nnTF {#2} { g }
23898         { gray ~ #1 }
23899         {
23900             \str_if_eq:nnTF {#4} { rg }
23901             { rgb ~ #1 ~ #2 ~ #3 }
23902             {
23903                 \str_if_eq:nnTF {#5} { k }
23904                 { cmyk ~ #1 ~ #2 ~ #3 ~ #4 }
23905                 { gray ~ #1 }
23906             }
23907         }
23908     }
23909 }
23910 { \cs_new_protected:Npn \__driver_color_pickup: { } }
23911 }
23912 \</package>

```

(End definition for \\_\_driver\_color\_pickup: and \\_\_driver\_color\_pickup\_aux:.)

\l\_\_driver\_color\_stack\_int pdfTeX and LuaTeX have multiple stacks available, and to track which one is in use a variable is required.

```

23913 \int_new:N \l__driver_color_stack_int

```

(End definition for \l\_\_driver\_color\_stack\_int.)

\\_\_driver\_color\_ensure\_current: There is a dedicated primitive/primitive interface for setting colors. As with scoping, this approach is not suitable for cached operations. Since we are using the dvips format to store color, there is a bit of work to correctly place it in the output.

```

\__driver_color_convert:w
\__driver_color_convert_gray:w
\__driver_color_convert_cmyk:w
\__driver_color_convert_rgb:w
\__driver_color_reset:
23914 \cs_new_protected:Npx \__driver_color_ensure_current:
23915 {
23916     *package)
23917     \exp_not:N \__driver_color_pickup:
23918 \</package>
23919     \cs_if_exist:NTF \luatex_pdfextension:D
23920     { \luatex_pdfextension:D colorstack }
23921     { \pdftex_pdfcolorstack:D }
23922     \exp_not:N \l__driver_color_stack_int push
23923     {
23924         \exp_not:N \exp_after:wN
23925         \exp_not:N \__driver_color_convert:w
23926         \exp_not:N \l__color_current_tl
23927         \c_space_tl 0 ~ 0 ~ 0
23928         \exp_not:N \q_stop
23929     }
23930 }
23931 \cs_new:Npn \__driver_color_convert:w #1 ~
23932 { \use:c { __driver_color_convert_ #1 :w } }
23933 \cs_new:Npn \__driver_color_convert_gray:w #1 ~ #2 \q_stop
23934 { #1 ~ g ~ #1 ~ G }
23935 \cs_new:Npn \__driver_color_convert_cmyk:w #1 ~ #2 ~ #3 ~ #4 \q_stop
23936 { #1 ~ #2 ~ #3 ~ rg ~ #1 ~ #2 ~ #3 ~ RG }
23937 \cs_new:Npn \__driver_color_convert_rgb:w #1 ~ #2 ~ #3 ~ #4 ~ #5 \q_stop
23938 { #1 ~ #2 ~ #3 ~ #4 ~ k ~ #1 ~ #2 ~ #3 ~ #4 ~ K }
23939 \cs_new_protected:Npx \__driver_color_reset:

```

```

23940 {
23941   \cs_if_exist:NTF \luatex_pdfextension:D
23942     { \luatex_pdfextension:D colorstack }
23943     { \pdfex_pdfcolorstack:D }
23944   \exp_not:N \l__driver_color_stack_int pop \scan_stop:
23945 }

```

(End definition for `\__driver_color_ensure_current:` and others.)

```

23946 \pdfmode

```

## 44.2 dvips driver

```

23947 \*dvips

```

### 44.2.1 Basics

`\__driver_literal:n` In the case of dvips there is no build-in saving of the current position, and so some additional PostScript is required to set up the transformation matrix and also to restore it afterwards. Notice the use of the stack to save the current position “up front” and to move back to it at the end of the process.

```

23948 \cs_new_protected:Npn \__driver_literal:n #1
23949 {
23950   \tex_special:D
23951   {
23952     ps:
23953     currentpoint~
23954     currentpoint~translate~
23955     #1 ~
23956     neg~exch~neg~exch~translate
23957   }
23958 }

```

(End definition for `\__driver_literal:n`.)

`\__driver_scope_begin:` Scope saving/restoring is done directly with no need to worry about the transformation matrix. General scoping is only for the graphics stack so the lower-cost `gsave/grestore` pair are used.

```

23959 \cs_new_protected:Npn \__driver_scope_begin:
23960 { \tex_special:D { ps:gsave } }
23961 \cs_new_protected:Npn \__driver_scope_end:
23962 { \tex_special:D { ps:grestore } }

```

(End definition for `\__driver_scope_begin:` and `\__driver_scope_end:.`)

## 44.3 Driver-specific auxiliaries

`\__driver_absolute_lengths:n` The dvips driver scales all absolute dimensions based on the output resolution selected and any T<sub>E</sub>X magnification. Thus for any operation involving absolute lengths there is a correction to make. This is based on `normalscale` from `special.pro` but using the stack rather than a definition to save the current matrix.

```

23963 \cs_new:Npn \__driver_absolute_lengths:n #1
23964 {
23965   matrix~currentmatrix~
23966   Resolution~72~div~VResolution~72~div~scale~

```

```

23967     DVImag~dup~scale~
23968     #1 ~
23969     setmatrix
23970 }

```

(End definition for `\_driver_absolute_lengths:n`.)

#### 44.3.1 Box operations

`\_driver_box_use_clip:N` Much the same idea as for the PDF mode version but with a slightly different syntax for creating the clip path. To avoid any scaling issues we need the absolute length auxiliary here.

```

23971 \cs_new_protected:Npn \_driver_box_use_clip:N #1
23972 {
23973   \_driver_scope_begin:
23974   \_driver_literal:n
23975   {
23976     \_driver_absolute_lengths:n
23977     {
23978       0 ~
23979       \dim_to_decimal_in_bp:n { \box_dp:N #1 } ~
23980       \dim_to_decimal_in_bp:n { \box_wd:N #1 } ~
23981       \dim_to_decimal_in_bp:n { -\box_ht:N #1 - \box_dp:N #1 } ~
23982       rectclip
23983     }
23984   }
23985   \hbox_overlap_right:n { \box_use:N #1 }
23986   \_driver_scope_end:
23987   \skip_horizontal:n { \box_wd:N #1 }
23988 }

```

(End definition for `\_driver_box_use_clip:N`.)

`\_driver_box_use_rotate:Nn` Rotating using dvips does not require that the box dimensions are altered and has a very convenient built-in operation. Zero rotation must be written as 0 not -0 so there is a quick test.

```

23989 \cs_new_protected:Npn \_driver_box_use_rotate:Nn #1#2
23990 {
23991   \_driver_scope_begin:
23992   \_driver_literal:n
23993   {
23994     \fp_compare:nNnTF {#2} = \c_zero_fp
23995     { 0 }
23996     { \fp_eval:n { round ( -#2 , 5 ) } } ~
23997     rotate
23998   }
23999   \box_use:N #1
24000   \_driver_scope_end:
24001 }
24002 % \end{macro}
24003 %
24004 % \begin{macro}{\_driver_box_use_scale:Nnn}
24005 %   The \texttt{dvips} driver once again has a dedicated operation we can
24006 %   use here.

```

```

24007 % \begin{macrocode}
24008 \cs_new_protected:Npn \__driver_box_use_scale:Nnn #1#2#3
24009 {
24010   \__driver_scope_begin:
24011   \__driver_literal:n
24012   {
24013     \fp_eval:n { round ( #2 , 5 ) } ~
24014     \fp_eval:n { round ( #3 , 5 ) } ~
24015     scale
24016   }
24017   \hbox_overlap_right:n { \box_use:N #1 }
24018   \__driver_scope_end:
24019 }

```

(End definition for \\_\_driver\_box\_use\_rotate:Nn.)

## 44.4 Images

\\_\_driver\_image\_getbb\_eps:n Simply use the generic function.

```

24020 \cs_new_eq:NN \__driver_image_getbb_eps:n \__image_read_bb:n

```

(End definition for \\_\_driver\_image\_getbb\_eps:n.)

\\_\_driver\_image\_include\_eps:n The special syntax is relatively clear here: remember we need PostScript sizes here.

```

24021 \cs_new_protected:Npn \__driver_image_include_eps:n #1
24022 {
24023   \tex_special:D { PSfile = #1 }
24024 }

```

(End definition for \\_\_driver\_image\_include\_eps:n.)

## 44.5 Drawing

\\_\_driver\_draw\_literal:n Literals with no positioning (using ps: each one is positioned but cut off from everything else, so no good for the stepwise approach needed here).

```

24025 \cs_new_protected:Npn \__driver_draw_literal:n #1
24026 { \tex_special:D { ps:: ~ #1 } }
24027 \cs_generate_variant:Nn \__driver_draw_literal:n { x }

```

(End definition for \\_\_driver\_draw\_literal:n.)

\\_\_driver\_draw\_begin: The ps::[begin] special here deals with positioning but allows us to continue on to a matching ps::[end]: contrast with ps:, which positions but where we can't split material between separate calls. The @beginspecial/@endspecial pair are from special.pro and correct the scale and y-axis direction. The reference point at the start of the box is saved (as l3x/l3y) as it is needed when inserting various items.

\\_\_driver\_draw\_end:

```

24028 \cs_new_protected:Npn \__driver_draw_begin:
24029 {
24030   \tex_special:D { ps::[begin] }
24031   \tex_special:D { ps::~~save }
24032   \tex_special:D { ps::~~/l3x~currentpoint~/l3y~exch~def~def }
24033   \tex_special:D { ps::~~@beginspecial }
24034 }
24035 \cs_new_protected:Npn \__driver_draw_end:

```

```

24036 {
24037   \tex_special:D { ps::~@endspecial }
24038   \tex_special:D { ps::~restore }
24039   \tex_special:D { ps:::[end] }
24040 }

```

(End definition for `\_driver\_draw\_begin:` and `\_driver\_draw\_end:.`)

`\_driver\_draw\_scope\_begin:` Scope here may need to contain saved definitions, so the entire memory rather than just the graphic state has to be sent to the stack.

```

24041 \cs_new_protected:Npn \_driver\_draw\_scope\_begin:
24042 { \_driver\_draw\_literal:n { save } }
24043 \cs_new_protected:Npn \_driver\_draw\_scope\_end:
24044 { \_driver\_draw\_literal:n { restore } }

```

(End definition for `\_driver\_draw\_scope\_begin:` and `\_driver\_draw\_scope\_end:.`)

`\_driver\_draw\_moveto:nn` Path creation operations mainly resolve directly to PostScript primitive steps, with only the need to convert to bp. Notice that x-type expansion is included here to ensure that any variable values are forced to literals before any possible caching. There is no native rectangular path command (without also clipping, filling or stroking), so that task is done using a small amount of PostScript.

```

24045 \cs_new_protected:Npn \_driver\_draw\_moveto:nn #1#2
24046 {
24047   \_driver\_draw\_literal:x
24048   { \dim\_to\_decimal\_in\_bp:n {#1} ~ \dim\_to\_decimal\_in\_bp:n {#2} ~ moveto }
24049 }
24050 \cs_new_protected:Npn \_driver\_draw\_lineto:nn #1#2
24051 {
24052   \_driver\_draw\_literal:x
24053   { \dim\_to\_decimal\_in\_bp:n {#1} ~ \dim\_to\_decimal\_in\_bp:n {#2} ~ lineto }
24054 }
24055 \cs_new_protected:Npn \_driver\_draw\_rectangle:nnnn #1#2#3#4
24056 {
24057   \_driver\_draw\_literal:x
24058   {
24059     \dim\_to\_decimal\_in\_bp:n {#4} ~ \dim\_to\_decimal\_in\_bp:n {#3} ~
24060     \dim\_to\_decimal\_in\_bp:n {#1} ~ \dim\_to\_decimal\_in\_bp:n {#2} ~
24061     moveto~dup~0~rlineto~exch~0~exch~rlineto~neg~0~rlineto~closepath
24062   }
24063 }
24064 \cs_new_protected:Npn \_driver\_draw\_curveto:nnnnnn #1#2#3#4#5#6
24065 {
24066   \_driver\_draw\_literal:x
24067   {
24068     \dim\_to\_decimal\_in\_bp:n {#1} ~ \dim\_to\_decimal\_in\_bp:n {#2} ~
24069     \dim\_to\_decimal\_in\_bp:n {#3} ~ \dim\_to\_decimal\_in\_bp:n {#4} ~
24070     \dim\_to\_decimal\_in\_bp:n {#5} ~ \dim\_to\_decimal\_in\_bp:n {#6} ~
24071     curveto
24072   }
24073 }

```

(End definition for `\_driver\_draw\_moveto:nn` and others.)

`\__driver_draw_evenodd_rule:` The even-odd rule here can be implemented as a simply switch.

`\__driver_draw_nonzero_rule:`

```

24074 \cs_new_protected:Npn \__driver_draw_evenodd_rule:
24075   { \bool_gset_true:N \g__driver_draw_eor_bool }
24076 \cs_new_protected:Npn \__driver_draw_nonzero_rule:
24077   { \bool_gset_false:N \g__driver_draw_eor_bool }
24078 \bool_new:N \g__driver_draw_eor_bool

(End definition for \__driver_draw_evenodd_rule:, \__driver_draw_nonzero_rule:, and \g__driver_
draw_eor_bool.)

```

`\__driver_draw_closepath:` Unlike PDF, PostScript doesn't track separate colors for strokes and other elements. It is also desirable to have the `clip` keyword after a stroke or fill. To achieve those outcomes, there is some work to do. For color, if a stroke or fill color is defined it is used for the relevant operation, with a graphic scope inserted as required. That does mean that once such a color is set all further uses inside the same scope have to use scoping: see also `\__driver_draw_fillstroke:` the color set up functions. For clipping, the required ordering is achieved using a T<sub>E</sub>X switch. All of the operations end with a new path instruction as they do not terminate (again in contrast to PDF).

`\__driver_draw_clip:`

`\__driver_draw_discardpath:`

`\g__driver_draw_clip_bool`

```

24079 \cs_new_protected:Npn \__driver_draw_closepath:
24080   { \__driver_draw_literal:n { closepath } }
24081 \cs_new_protected:Npn \__driver_draw_stroke:
24082   {
24083     \__driver_draw_literal:n { currentdict~/l3sc-known~{gsave~l3sc}~if }
24084     \__driver_draw_literal:n { stroke }
24085     \__driver_draw_literal:n { currentdict~/l3sc-known~{grestore}~if }
24086     \bool_if:NT \g__driver_draw_clip_bool
24087     {
24088       \__driver_draw_literal:x
24089       {
24090         \bool_if:NT \g__driver_draw_eor_bool { eo }
24091         clip
24092       }
24093     }
24094     \__driver_draw_literal:n { newpath }
24095     \bool_gset_false:N \g__driver_draw_clip_bool
24096   }
24097 \cs_new_protected:Npn \__driver_draw_closestroke:
24098   {
24099     \__driver_draw_closepath:
24100     \__driver_draw_stroke:
24101   }
24102 \cs_new_protected:Npn \__driver_draw_fill:
24103   {
24104     \__driver_draw_literal:n { currentdict~/l3fc-known~{gsave~l3fc}~if }
24105     \__driver_draw_literal:x
24106     {
24107       \bool_if:NT \g__driver_draw_eor_bool { eo }
24108       fill
24109     }
24110     \__driver_draw_literal:n { currentdict~/l3fc-known~{grestore}~if }
24111     \bool_if:NT \g__driver_draw_clip_bool
24112     {
24113       \__driver_draw_literal:x
24114       {

```

```

24115         \bool_if:NT \g__driver_draw_eor_bool { eo }
24116         clip
24117     }
24118 }
24119 \__driver_draw_literal:n { newpath }
24120 \bool_gset_false:N \g__driver_draw_clip_bool
24121 }
24122 \cs_new_protected:Npn \__driver_draw_fillstroke:
24123 {
24124     \__driver_draw_literal:n { currentdict~/l3fc-known~{gsave~l3fc}~if }
24125     \__driver_draw_literal:x
24126     {
24127         \bool_if:NT \g__driver_draw_eor_bool { eo }
24128         fill
24129     }
24130     \__driver_draw_literal:n { currentdict~/l3fc-known~{grestore}~if }
24131     \__driver_draw_literal:n { currentdict~/l3sc-known~{gsave~l3sc}~if }
24132     \__driver_draw_literal:n { stroke }
24133     \__driver_draw_literal:n { currentdict~/l3sc-known~{grestore}~if }
24134     \bool_if:NT \g__driver_draw_clip_bool
24135     {
24136         \__driver_draw_literal:x
24137         {
24138             \bool_if:NT \g__driver_draw_eor_bool { eo }
24139             clip
24140         }
24141     }
24142     \__driver_draw_literal:n { newpath }
24143     \bool_gset_false:N \g__driver_draw_clip_bool
24144 }
24145 \cs_new_protected:Npn \__driver_draw_clip:
24146 { \bool_gset_true:N \g__driver_draw_clip_bool }
24147 \bool_new:N \g__driver_draw_clip_bool
24148 \cs_new_protected:Npn \__driver_draw_discardpath:
24149 {
24150     \bool_if:NT \g__driver_draw_clip_bool
24151     {
24152         \__driver_draw_literal:x
24153         {
24154             \bool_if:NT \g__driver_draw_eor_bool { eo }
24155             clip
24156         }
24157     }
24158     \__driver_draw_literal:n { newpath }
24159     \bool_gset_false:N \g__driver_draw_clip_bool
24160 }

```

(End definition for \\_\_driver\_draw\_closepath: and others.)

<pre> \__driver_draw_dash:nn \__driver_draw_dash:n \__driver_draw_linewidth:n \__driver_draw_miterlimit:n \__driver_draw_cap_but: \__driver_draw_cap_round: \__driver_draw_cap_rectangle: \__driver_draw_join_miter: \__driver_draw_join_round: \__driver_draw_join_bevel: </pre>	<p>Converting paths to output is again a case of mapping directly to PostScript operations.</p> <pre> 24161 \cs_new_protected:Npn \__driver_draw_dash:nn #1#2 24162 { 24163     \__driver_draw_literal:x 24164     { </pre>
---	---



```

24165     [ ~
24166     \clist_map_function:nN {#1} \__driver_draw_dash:n
24167     ] ~
24168     \dim_to_decimal_in_bp:n {#2} ~ setdash
24169   }
24170 }
24171 \cs_new:Npn \__driver_draw_dash:n #1
24172 { \dim_to_decimal_in_bp:n {#1} ~ }
24173 \cs_new_protected:Npn \__driver_draw_linewidth:n #1
24174 {
24175   \__driver_draw_literal:x
24176   { \dim_to_decimal_in_bp:n {#1} ~ setlinewidth }
24177 }
24178 \cs_new_protected:Npn \__driver_draw_miterlimit:n #1
24179 { \__driver_draw_literal:x { \fp_eval:n {#1} ~ setmiterlimit } }
24180 \cs_new_protected:Npn \__driver_draw_cap_but:
24181 { \__driver_draw_literal:n { 0 ~ setlinecap } }
24182 \cs_new_protected:Npn \__driver_draw_cap_round:
24183 { \__driver_draw_literal:n { 1 ~ setlinecap } }
24184 \cs_new_protected:Npn \__driver_draw_cap_rectangle:
24185 { \__driver_draw_literal:n { 2 ~ setlinecap } }
24186 \cs_new_protected:Npn \__driver_draw_join_miter:
24187 { \__driver_draw_literal:n { 0 ~ setlinejoin } }
24188 \cs_new_protected:Npn \__driver_draw_join_round:
24189 { \__driver_draw_literal:n { 1 ~ setlinejoin } }
24190 \cs_new_protected:Npn \__driver_draw_join_bevel:
24191 { \__driver_draw_literal:n { 2 ~ setlinejoin } }

```

(End definition for \\_\_driver\_draw\_dash:nn and others.)

```

\__driver_draw_color_reset: To allow color to be defined for strokes and fills separately and to respect scoping, the
    \__driver_draw_color_cmyk:nnnn data needs to be stored at the PostScript level. We cannot undefine (local) fill/stroke
    \__driver_draw_color_cmyk_fill:nnnn colors once set up but we can set them blank to improve performance slightly.
    \__driver_draw_color_cmyk_stroke:nnnn
\__driver_draw_color_gray:n
    \__driver_draw_color_gray_fill:n
    \__driver_draw_color_gray_stroke:n
\__driver_draw_color_rgb:nnn
    \__driver_draw_color_rgb_fill:nnn
    \__driver_draw_color_rgb_stroke:nnn
24192 \cs_new_protected:Npn \__driver_draw_color_reset:
24193 {
24194   \__driver_draw_literal:n { currentdic~/l3fc-known~{ /l3fc~ { } ~def }~if }
24195   \__driver_draw_literal:n { currentdic~/l3sc-known~{ /l3sc~ { } ~def }~if }
24196 }
24197 \cs_new_protected:Npn \__driver_draw_color_cmyk:nnnn #1#2#3#4
24198 {
24199   \__driver_draw_literal:x
24200   {
24201     \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
24202     \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
24203     setcmykcolor ~
24204   }
24205   \__driver_draw_color_reset:
24206 }
24207 \cs_new_protected:Npn \__driver_draw_color_cmyk_fill:nnnn #1#2#3#4
24208 {
24209   \__driver_draw_literal:x
24210   {
24211     /l3fc ~
24212     {

```

```

24213         \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
24214         \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
24215         setcmykcolor
24216     } ~
24217     def
24218 }
24219 }
24220 \cs_new_protected:Npn \__driver_draw_color_cmyk_stroke:nnnn #1#2#3#4
24221 {
24222     \__driver_draw_literal:x
24223     {
24224         /l3sc ~
24225         {
24226             \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
24227             \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
24228             setcmykcolor
24229         } ~
24230         def
24231     }
24232 }
24233 \cs_new_protected:Npn \__driver_draw_color_gray:n #1
24234 {
24235     \__driver_draw_literal:x { \fp_eval:n {#1} ~ setgray }
24236     \__driver_draw_color_reset:
24237 }
24238 \cs_new_protected:Npn \__driver_draw_color_gray_fill:n #1
24239 { \__driver_draw_literal:x { /l3fc ~ { \fp_eval:n {#1} ~ setgray } ~ def } }
24240 \cs_new_protected:Npn \__driver_draw_color_gray_stroke:n #1
24241 { \__driver_draw_literal:x { /l3sc ~ { \fp_eval:n {#1} ~ setgray } ~ def } }
24242 \cs_new_protected:Npn \__driver_draw_color_rgb:nnn #1#2#3
24243 {
24244     \__driver_draw_literal:x
24245     {
24246         \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~
24247         setrgbcolor
24248     }
24249     \__driver_draw_color_reset:
24250 }
24251 \cs_new_protected:Npn \__driver_draw_color_rgb_fill:nnn #1#2#3
24252 {
24253     \__driver_draw_literal:x
24254     {
24255         /l3fc ~
24256         {
24257             \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~
24258             setrgbcolor
24259         } ~
24260         def
24261     }
24262 }
24263 \cs_new_protected:Npn \__driver_draw_color_rgb_stroke:nnn #1#2#3
24264 {
24265     \__driver_draw_literal:x
24266     {

```

```

24267         /l3sc ~
24268         {
24269             \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~
24270             setrgbcolor
24271         } ~
24272         def
24273     }
24274 }

```

(End definition for `\_driver_draw_color_reset:` and others.)

`\_driver_draw_transformcm:nnnnnn` The first four arguments here are floats (the affine matrix), the last two are a displacement vector. Once again, force evaluation to allow for caching.

```

24275 \cs_new_protected:Npn \_driver_draw_transformcm:nnnnnn #1#2#3#4#5#6
24276 {
24277     \_driver_draw_literal:x
24278     {
24279         [
24280             \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
24281             \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
24282             \dim_to_decimal_in_bp:n {#5} ~ \dim_to_decimal_in_bp:n {#6} ~
24283         ] ~
24284         concat
24285     }
24286 }

```

(End definition for `\_driver_draw_transformcm:nnnnnn`.)

`\_driver_draw_hbox:Nnnnnnn` Inside a picture `@beginspecial/@endspecial` are active, which is normally a good thing but means that the position and scaling would be off if the box was inserted directly. Instead, we need to reverse the effect of the (normally desirable) shift/scaling within the box. That requires knowing where the reference point for the drawing is: saved as `l3x/l3y` at the start of the picture. Transformation here is relative to the drawing origin so has to be done purely in driver code not using  $\TeX$  offsets.

```

24287 \cs_new_protected:Npn \_driver_draw_hbox:Nnnnnnn #1#2#3#4#5#6#7
24288 {
24289     \_driver_scope_begin:
24290     \tex_special:D { ps::[end] }
24291     \_driver_draw_transformcm:nnnnnn {#2} {#3} {#4} {#5} {#6} {#7}
24292     \tex_special:D { ps::~72~Resolution~div~72~VResolution~div~neg~scale }
24293     \tex_special:D { ps::~magscale~{1~DVImag~div~dup~scale}~if }
24294     \tex_special:D { ps::~l3x~neg~l3y~neg~translate }
24295     \group_begin:
24296         \box_set_wd:Nn #1 { Opt }
24297         \box_set_ht:Nn #1 { Opt }
24298         \box_set_dp:Nn #1 { Opt }
24299         \box_use:N #1
24300     \group_end:
24301     \tex_special:D { ps::[begin] }
24302     \_driver_scope_end:
24303 }

```

(End definition for `\_driver_draw_hbox:Nnnnnnn`.)

```

24304 </dvips>

```

## 44.6 pdfmode driver

24305 `\*pdfmode`

The direct PDF driver covers both pdfTeX and LuaTeX. The latter renames/restructures the driver primitives but this can be handled at one level of abstraction. As such, we avoid using two separate drivers for this material at the cost of some x-type definitions to get everything expanded up-front.

### 44.6.1 Basics

`\__driver_literal:n` This is equivalent to `\special{pdf:}` but the engine can track it. Without the `direct` keyword everything is kept in sync: the transformation matrix is set to the current point automatically. Note that this is still inside the text (BT ...ET block).

```
24306 \cs_new_protected:Npx \__driver_literal:n #1
24307 {
24308   \cs_if_exist:NTF \luatex_pdfextension:D
24309     { \luatex_pdfextension:D literal }
24310     { \pdftex_pdfliteral:D }
24311     {#1}
24312 }
```

(End definition for `\__driver_literal:n`.)

`\__driver_scope_begin:` Higher-level interfaces for saving and restoring the graphic state.

```
\__driver_scope_end:
24313 \cs_new_protected:Npx \__driver_scope_begin:
24314 {
24315   \cs_if_exist:NTF \luatex_pdfextension:D
24316     { \luatex_pdfextension:D save \scan_stop: }
24317     { \pdftex_pdfsave:D }
24318 }
24319 \cs_new_protected:Npx \__driver_scope_end:
24320 {
24321   \cs_if_exist:NTF \luatex_pdfextension:D
24322     { \luatex_pdfextension:D restore \scan_stop: }
24323     { \pdftex_pdfrestore:D }
24324 }
```

(End definition for `\__driver_scope_begin:` and `\__driver_scope_end:.`)

`\__driver_matrix:n` Here the appropriate function is set up to insert an affine matrix into the PDF. With pdfTeX and LuaTeX in direct PDF output mode there is a primitive for this, which only needs the rotation/scaling/skew part.

```
24325 \cs_new_protected:Npx \__driver_matrix:n #1
24326 {
24327   \cs_if_exist:NTF \luatex_pdfextension:D
24328     { \luatex_pdfextension:D setmatrix }
24329     { \pdftex_pdfsetmatrix:D }
24330     {#1}
24331 }
```

(End definition for `\__driver_matrix:n`.)

## 44.6.2 Box operations

`\_driver_box_use_clip:N` The general method is to save the current location, define a clipping path equivalent to the bounding box, then insert the content at the current position and in a zero width box. The “real” width is then made up using a horizontal skip before tidying up. There are other approaches that can be taken (for example using XForm objects), but the logic here shares as much code as possible and uses the same conversions (and so same rounding errors) in all cases.

```

24332 \cs_new_protected:Npn \_driver_box_use_clip:N #1
24333 {
24334   \_driver_scope_begin:
24335   \_driver_literal:n
24336   {
24337     0~
24338     \dim_to_decimal_in_bp:n { -\box_dp:N #1 } ~
24339     \dim_to_decimal_in_bp:n { \box_wd:N #1 } ~
24340     \dim_to_decimal_in_bp:n { \box_ht:N #1 + \box_dp:N #1 } ~
24341     re~W~n
24342   }
24343   \hbox_overlap_right:n { \box_use:N #1 }
24344   \_driver_scope_end:
24345   \skip_horizontal:n { \box_wd:N #1 }
24346 }

```

(End definition for `\_driver_box_use_clip:N`.)

`\_driver_box_use_rotate:Nn` Rotations are set using an affine transformation matrix which therefore requires sine/cosine values not the angle itself. We store the rounded values to avoid rounding twice. There are also a couple of comparisons to ensure that `-0` is not written to the output, as this avoids any issues with problematic display programs. Note that numbers are compared to 0 after rounding.

```

24347 \cs_new_protected:Npn \_driver_box_use_rotate:Nn #1#2
24348 {
24349   \_driver_scope_begin:
24350   \box_set_wd:Nn #1 \c_zero_dim
24351   \fp_set:Nn \l__driver_cos_fp { round ( cosd ( #2 ) , 5 ) }
24352   \fp_compare:nNnT \l__driver_cos_fp = \c_zero_fp
24353     { \fp_zero:N \l__driver_cos_fp }
24354   \fp_set:Nn \l__driver_sin_fp { round ( sind ( #2 ) , 5 ) }
24355   \_driver_matrix:n
24356   {
24357     \fp_use:N \l__driver_cos_fp \c_space_tl
24358     \fp_compare:nNnTF \l__driver_sin_fp = \c_zero_fp
24359       { 0~0 }
24360       {
24361         \fp_use:N \l__driver_sin_fp
24362         \c_space_tl
24363         \fp_eval:n { -\l__driver_sin_fp }
24364       }
24365     \c_space_tl
24366     \fp_use:N \l__driver_cos_fp
24367   }
24368   \box_use:N #1
24369   \_driver_scope_end:

```

```

24370     }
24371     \fp_new:N \l__driver_cos_fp
24372     \fp_new:N \l__driver_sin_fp

```

(End definition for \\_\_driver\_box\_use\_rotate:Nn, \l\_\_driver\_cos\_fp, and \l\_\_driver\_sin\_fp.)

**\\_\_driver\_box\_use\_scale:Nnn** The same idea as for rotation but without the complexity of signs and cosines.

```

24373 \cs_new_protected:Npn \__driver_box_use_scale:Nnn #1#2#3
24374 {
24375     \__driver_scope_begin:
24376     \__driver_matrix:n
24377     {
24378         \fp_eval:n { round ( #2 , 5 ) } ~
24379         0~0~
24380         \fp_eval:n { round ( #3 , 5 ) }
24381     }
24382     \hbox_overlap_right:n { \box_use:N #1 }
24383     \__driver_scope_end:
24384 }

```

(End definition for \\_\_driver\_box\_use\_scale:Nnn.)

## 44.7 Images

**\l\_\_driver\_image\_attr\_tl** In PDF mode, additional attributes of an image (such as page number) are needed both to obtain the bounding box and when inserting the image: this occurs as the image dictionary approach means they are read as part of the bounding box operation. As such, it is easier to track additional attributes using a dedicated `tl` rather than build up the same data twice.

```

24385 \tl_new:N \l__driver_image_attr_tl

```

(End definition for \l\_\_driver\_image\_attr\_tl.)

**\\_\_driver\_image\_getbb\_jpg:n** Getting the bounding box here requires us to box up the image and measure it. To deal with the difference in feature support in bitmap and vector images but keeping the common parts, there is a little work to do in terms of auxiliaries. The key here is to notice that we need two forms of the attributes: a “short” set to allow us to track for caching, and the full form to pass to the primitive.

```

\__driver_image_getbb_pdf:n
\__driver_image_getbb_png:n
\__driver_image_getbb_auxi:n
    \__driver_image_getbb_auxii:n
24386 \cs_new_protected:Npn \__driver_image_getbb_jpg:n #1
24387 {
24388     \int_zero:N \l__image_page_int
24389     \tl_clear:N \l__image_pagebox_tl
24390     \tl_set:Nx \l__driver_image_attr_tl
24391     {
24392         \tl_if_empty:NF \l__image_decode_tl
24393         { :D \l__image_decode_tl }
24394         \bool_if:NT \l__image_interpolate_bool
24395         { :I }
24396     }
24397     \tl_clear:N \l__driver_image_attr_tl
24398     \__driver_image_getbb_auxi:n {#1}
24399 }
24400 \cs_new_eq:NN \__driver_image_getbb_png:n \__driver_image_getbb_jpg:n
24401 \cs_new_protected:Npn \__driver_image_getbb_pdf:n #1

```

```

24402 {
24403   \tl_clear:N \l__image_decode_tl
24404   \bool_set_false:N \l__image_interpolate_bool
24405   \tl_set:Nx \l__driver_image_attr_tl
24406     {
24407       : \l__image_pagebox_tl
24408       \int_compare:nNnT \l__image_page_int > 1
24409         { :P \int_use:N \l__image_page_int }
24410     }
24411   \__driver_image_getbb_auxi:n {#1}
24412 }
24413 \cs_new_protected:Npn \__driver_image_getbb_auxi:n #1
24414 {
24415   \dim_zero:N \l__image_llx_dim
24416   \dim_zero:N \l__image_lly_dim
24417   \dim_if_exist:cTF { c__image_ #1 \l__driver_image_attr_tl _urx_dim }
24418     {
24419       \dim_set_eq:Nc \l__image_urx_dim
24420         { c__image_ #1 \l__driver_image_attr_tl _urx_dim }
24421       \dim_set_eq:Nc \l__image_ury_dim
24422         { c__image_ #1 \l__driver_image_attr_tl _ury_dim }
24423     }
24424     { \__driver_image_getbb_auxii:n {#1} }
24425 }
24426 % \begin{macrocode}
24427 % Measuring the image is done by boxing up: for PDF images we could
24428 % use \pdfTeX pdfximagebbbox:D/, but if doesn't work for other types.
24429 % As the box always starts at $(0,0)$ there is no need to worry about
24430 % the lower-left position.
24431 % \begin{macrocode}
24432 \cs_new_protected:Npn \__driver_image_getbb_auxii:n #1
24433 {
24434   \tex_immediate:D \pdfTeX pdfximage:D
24435   \bool_lazy_or:nnT
24436     { \l__image_interpolate_bool }
24437     { ! \tl_if_empty_p:N \l__image_decode_tl }
24438     {
24439       attr ~
24440       {
24441         \tl_if_empty:NF \l__image_decode_tl
24442           { /Decode~[ \l__image_decode_tl ] }
24443         \bool_if:NT \l__image_interpolate_bool
24444           { /Interpolate~true }
24445       }
24446     }
24447   \int_compare:nNnT \l__image_page_int > 0
24448     { page ~ \int_use:N \l__image_page_int }
24449   \tl_if_empty:NF \l__image_pagebox_tl
24450     { \l__image_pagebox_tl }
24451   {#1}
24452   \hbox_set:Nn \l__image_tmp_box
24453     { \pdfTeX pdfrefximage:D \pdfTeX pdflastximage:D }
24454   \dim_set:Nn \l__image_urx_dim { \box_wd:N \l__image_tmp_box }
24455   \dim_set:Nn \l__image_ury_dim { \box_ht:N \l__image_tmp_box }

```

```

24456 \int_const:cn { c__image_ #1 \l__driver_image_attr_tl _int }
24457 { \tex_the:D \pdfTeX_pdflastximage:D }
24458 \dim_const:cn { c__image_ #1 \l__driver_image_attr_tl _urx_dim }
24459 { \l__image_urx_dim }
24460 \dim_const:cn { c__image_ #1 \l__driver_image_attr_tl _ury_dim }
24461 { \l__image_ury_dim }
24462 }

```

(End definition for `\__driver_image_getbb_jpg:n` and others.)

`\__driver_image_include_jpg:n` Images are already loaded for the measurement part of the code, so inclusion is straightforward, with only any attributes to worry about. The latter carry through from determination of the bounding box.

```

24463 \cs_new_protected:Npn \__driver_image_include_jpg:n #1
24464 {
24465   \pdfTeX_pdfrefximage:D
24466   \int_use:c { c__image_ #1 \l__driver_image_attr_tl _int }
24467 }
24468 \cs_new_eq:NN \__driver_image_include_pdf:n \__driver_image_include_jpg:n
24469 \cs_new_eq:NN \__driver_image_include_png:n \__driver_image_include_jpg:n

```

(End definition for `\__driver_image_include_jpg:n`, `\__driver_image_include_pdf:n`, and `\__driver_image_include_png:n`.)

```

24470 \pdfmode

```

## 44.8 dvipdfmx driver

```

24471 \*dvipdfmx |xdvipdfmx

```

The `dvipdfmx` shares code with the PDF mode one (using the common section to this file) but also with `xdvipdfmx`. The latter is close to identical to `dvipdfmx` and so all of the code here is extracted for both drivers, with some `clean up` for `xdvipdfmx` as required.

### 44.8.1 Basics

`\__driver_literal:n` Equivalent to `pdf:content` but favored as the link to the pdfTeX primitive approach is clearer. Some higher-level operations use `\tex_special:D` directly: see the later comments on where this is useful.

```

24472 \cs_new_protected:Npn \__driver_literal:n #1
24473 { \tex_special:D { pdf:literal~ #1 } }

```

(End definition for `\__driver_literal:n`.)

`\__driver_scope_begin:` Scoping is done using the driver-specific specials.

```

\__driver_scope_end:
24474 \cs_new_protected:Npn \__driver_scope_begin:
24475 { \tex_special:D { x:gsave } }
24476 \cs_new_protected:Npn \__driver_scope_end:
24477 { \tex_special:D { x:grestore } }

```

(End definition for `\__driver_scope_begin:` and `\__driver_scope_end:`.)



## 44.8.2 Box operations

`\_driver_box_use_clip:N` The code here is identical to that for `pdfmode`: unlike rotation and scaling, there is no higher-level support in the driver for clipping.

```

24478 \cs_new_protected:Npn \_driver_box_use_clip:N #1
24479 {
24480   \_driver_scope_begin:
24481   \_driver_literal:n
24482   {
24483     0~
24484     \dim_to_decimal_in_bp:n { -\box_dp:N #1 } ~
24485     \dim_to_decimal_in_bp:n { \box_wd:N #1 } ~
24486     \dim_to_decimal_in_bp:n { \box_ht:N #1 + \box_dp:N #1 } ~
24487     re~W~n
24488   }
24489   \hbox_overlap_right:n { \box_use:N #1 }
24490   \_driver_scope_end:
24491   \skip_horizontal:n { \box_wd:N #1 }
24492 }

```

(End definition for `\_driver_box_use_clip:N`.)

`\_driver_box_use_rotate:Nn` Rotating in (x)dvi<sub>pdf</sub> can be implemented using either PDF or driver-specific code. The former approach however is not “aware” of the content of boxes: this means that any embedded links would not be adjusted by the rotation. As such, the driver-native approach is preferred: the code therefore is similar (though not identical) to the `dvips` version (notice the rotation angle here is positive). As for `dvips`, zero rotation is written as 0 not -0.

```

24493 \cs_new_protected:Npn \_driver_box_use_rotate:Nn #1#2
24494 {
24495   \_driver_scope_begin:
24496   \tex_special:D
24497   {
24498     x:rotate~
24499     \fp_compare:nNnTF {#2} = \c_zero_fp
24500     { 0 }
24501     { \fp_eval:n { round ( #2 , 5 ) } }
24502   }
24503   \box_use:N #1
24504   \_driver_scope_end:
24505 }

```

(End definition for `\_driver_box_use_rotate:Nn`.)

`\_driver_box_use_scale:Nnn` Much the same idea for scaling: use the higher-level driver operation to allow for box content.

```

24506 \cs_new_protected:Npn \_driver_box_use_scale:Nnn #1#2#3
24507 {
24508   \_driver_scope_begin:
24509   \tex_special:D
24510   {
24511     x:scale~
24512     \fp_eval:n { round ( #2 , 5 ) } ~
24513     \fp_eval:n { round ( #3 , 5 ) }

```

```

24514     }
24515     \hbox_overlap_right:n { \box_use:N #1 }
24516     \__driver_scope_end:
24517 }

```

(End definition for \\_\_driver\_box\_use\_scale:Nnn.)

## 44.9 Images

\\_\_driver\_image\_getbb\_eps:n Simply use the generic functions: only for dvipdfmx in the extraction cases.

```

\__driver_image_getbb_jpg:n 24518 \cs_new_eq:NN \__driver_image_getbb_eps:n \__image_read_bb:n
\__driver_image_getbb_pdf:n 24519 (*dvipdfmx)
\__driver_image_getbb_png:n 24520 \cs_new_protected:Npn \__driver_image_getbb_jpg:n #1
24521 {
24522     \int_zero:N \l__image_page_int
24523     \tl_clear:N \l__image_pagebox_tl
24524     \__image_extract_bb:n {#1}
24525 }
24526 \cs_new_eq:NN \__driver_image_getbb_png:n \__driver_image_getbb_jpg:n
24527 \cs_new_protected:Npn \__driver_image_getbb_pdf:n #1
24528 {
24529     \tl_clear:N \l__image_decode_tl
24530     \bool_set_false:N \l__image_interpolate_bool
24531     \__image_extract_bb:n {#1}
24532 }
24533 </dvipdfmx>

```

(End definition for \\_\_driver\_image\_getbb\_eps:n and others.)

\g\_\_driver\_image\_int Used to track the object number associated with each image.

```

24534 \int_new:N \g__driver_image_int

```

(End definition for \g\_\_driver\_image\_int.)

\\_\_driver\_image\_include\_eps:n The special syntax depends on the file type. There is a difference in how PDF images are best handled between dvipdfmx and xdvipdfmx: for the latter it is better to use the primitive route. The relevant code for that is included later in this file.

```

\__driver_image_include_jpg:n
\__driver_image_include_pdf:n
\__driver_image_include_png:n 24535 \cs_new_protected:Npn \__driver_image_include_eps:n #1
\__driver_image_include_auxi:nn 24536 {
\__driver_image_include_auxii:nnn 24537     \tex_special:D { PSfile = #1 }
\__driver_image_include_auxii:xnn 24538 }
\__driver_image_include_auxiii:nnn 24539 \cs_new_protected:Npn \__driver_image_include_jpg:n #1
24540 { \__driver_image_include_auxi:nn {#1} { image } }
24541 \cs_new_eq:NN \__driver_image_include_png:n \__driver_image_include_jpg:n
24542 (*dvipdfmx)
24543 \cs_new_protected:Npn \__driver_image_include_pdf:n #1
24544 { \__driver_image_include_auxi:nn {#1} { epdf } }
24545 </dvipdfmx>

```

Image inclusion is set up to use the fact that each image is stored in the PDF as an XObject. This means that we can include repeated images only once and refer to them. To allow that, track the nature of each image: much the same as for the direct PDF mode case.

```

24546 \cs_new_protected:Npn \__driver_image_include_auxi:nn #1#2

```

```

24547 {
24548   \_driver_image_include_auxii:xnn
24549   {
24550     \tl_if_empty:NF \l__image_pagebox_tl
24551     { : \l__image_pagebox_tl }
24552     \int_compare:nNnT \l__image_page_int > 1
24553     { :P \int_use:N \l__image_page_int }
24554     \tl_if_empty:NF \l__image_decode_tl
24555     { :D \l__image_decode_tl }
24556     \bool_if:NT \l__image_interpolate_bool
24557     { :I }
24558   }
24559   {#1} {#2}
24560 }
24561 \cs_new_protected:Npn \_driver_image_include_auxiii:nnn #1#2#3
24562 {
24563   \int_if_exist:cTF { c__image_ #2#1 _int }
24564   {
24565     \tex_special:D
24566     { pdf:usexobj~@image \int_use:c { c__image_ #2#1 _int } }
24567   }
24568   { \_driver_image_include_auxiii:nn {#2} {#1} {#3} }
24569 }
24570 \cs_generate_variant:Nn \_driver_image_include_auxii:nnn { x }

```

Inclusion using the specials is relatively straight-forward, but there is one wrinkle. To get the pagebox correct for PDF images in all cases, it is necessary to provide both that information and the bbox argument: odd things happen otherwise!

```

24571 \cs_new_protected:Npn \_driver_image_include_auxiii:nnn #1#2#3
24572 {
24573   \int_gincr:N \g__driver_image_int
24574   \int_const:cn { c__image_ #1#2 _int } { \g__driver_image_int }
24575   \tex_special:D
24576   {
24577     pdf:#3~
24578     @image \int_use:c { c__image_ #1#2 _int }
24579     \int_compare:nNnT \l__image_page_int > 1
24580     { page ~ \int_use:N \l__image_page_int \c_space_tl }
24581     \tl_if_empty:NF \l__image_pagebox_tl
24582     {
24583       pagebox ~ \l__image_pagebox_tl \c_space_tl
24584       bbox ~
24585       \dim_to_decimal_in_bp:n \l__image_llx_dim \c_space_tl
24586       \dim_to_decimal_in_bp:n \l__image_lly_dim \c_space_tl
24587       \dim_to_decimal_in_bp:n \l__image_urx_dim \c_space_tl
24588       \dim_to_decimal_in_bp:n \l__image_ury_dim \c_space_tl
24589     }
24590     (#1)
24591     \bool_lazy_or:nnT
24592     { \l__image_interpolate_bool }
24593     { ! \tl_if_empty_p:N \l__image_decode_tl }
24594     {
24595       <<
24596       \tl_if_empty:NF \l__image_decode_tl

```

```

24597         { /Decode~[ \l__image_decode_tl ] }
24598         \bool_if:NT \l__image_interpolate_bool
24599         { /Interpolate~true> }
24600     >>
24601 }
24602 }
24603 }

```

(End definition for \\_driver\_image\_include\_eps:n and others.)

```

24604 </dvipdfmx | xdvipdfmx>

```

## 44.10 xdvipdfmx driver

```

24605 <*xdvipdfmx>

```

## 44.11 Images

\\_driver\_image\_getbb\_jpg:n For xdvipdfmx, there are two primitives that allow us to obtain the bounding box without needing extractbb. The only complexity is passing the various minor variations to a common core process. The X<sub>Y</sub>TEX primitive omits the text box from the page box specification, so there is also some “trimming” to do here.

```

\_driver_image_getbb_auxi:nN
\_driver_image_getbb_auxii:nNn
\_driver_image_getbb_auxii:VnN
\_driver_image_getbb_auxiii:nNnn
\_driver_image_getbb_auxiv:nNnn
\_driver_image_getbb_auxiv:VnNnn
\_driver_image_getbb_auxv:nNnn
\_driver_image_getbb_auxv:nNnn
\_driver_image_getbb_pagebox:w
24606 \cs_new_protected:Npn \_driver_image_getbb_jpg:n #1
24607 {
24608     \int_zero:N \l__image_page_int
24609     \tl_clear:N \l__image_pagebox_tl
24610     \_driver_image_getbb_auxi:nN {#1} \xetex_picfile:D
24611 }
24612 \cs_new_eq:NN \_driver_image_getbb_png:n \_driver_image_getbb_jpg:n
24613 \cs_new_protected:Npn \_driver_image_getbb_pdf:n #1
24614 {
24615     \tl_clear:N \l__image_decode_tl
24616     \bool_set_false:N \l__image_interpolate_bool
24617     \_driver_image_getbb_auxi:nN {#1} \xetex_pdffile:D
24618 }
24619 \cs_new_protected:Npn \_driver_image_getbb_auxi:nN #1#2
24620 {
24621     \int_compare:nNnTF \l__image_page_int > 1
24622     { \_driver_image_getbb_auxii:VnN \l__image_page_int {#1} #2 }
24623     { \_driver_image_getbb_auxiii:nNnn {#1} #2 }
24624 }
24625 \cs_new_protected:Npn \_driver_image_getbb_auxii:nNn #1#2#3
24626 { \_driver_image_getbb_aux:nNnn {#2} #3 { :P #1 } { page #1 } }
24627 \cs_generate_variant:Nn \_driver_image_getbb_auxii:nNn { V }
24628 \cs_new_protected:Npn \_driver_image_getbb_auxiii:nNnn #1#2#3#4
24629 {
24630     \tl_if_empty:NTF \l__image_pagebox_tl
24631     { \_driver_image_getbb_auxiv:VnNnn \l__image_pagebox_tl }
24632     { \_driver_image_getbb_auxv:nNnn }
24633     {#1} #2 {#3} {#4}
24634 }
24635 \cs_new_protected:Npn \_driver_image_getbb_auxiv:nNnn #1#2#3#4#5
24636 {
24637     \use:x
24638     {

```

```

24639     \_driver_image_getbb_auxv:nNnn {#2} #3 { : #1 #4 }
24640     { #5 ~ \_driver_image_getbb_pagebox:w #1 }
24641   }
24642 }
24643 \cs_generate_variant:Nn \_driver_image_getbb_auxiv:nnNnn { V }
24644 \cs_new_protected:Npn \_driver_image_getbb_auxv:nNnn #1#2#3#4
24645 {
24646   \dim_zero:N \l__image_llx_dim
24647   \dim_zero:N \l__image_lly_dim
24648   \dim_if_exist:cTF { c__image_ #1#3 _urx_dim }
24649   {
24650     \dim_set_eq:Nc \l__image_urx_dim { c__image_ #1#3 _urx_dim }
24651     \dim_set_eq:Nc \l__image_ury_dim { c__image_ #1#3 _ury_dim }
24652   }
24653   { \_driver_image_getbb_auxvi:nNnn {#1} #2 {#3} {#4} }
24654 }
24655 \cs_new_protected:Npn \_driver_image_getbb_auxvi:nNnn #1#2#3#4
24656 {
24657   \hbox_set:Nn \l__image_tmp_box { #2 #1 ~ #4 }
24658   \dim_set:Nn \l__image_utx_dim { \box_wd:N \l__image_tmp_box }
24659   \dim_set:Nn \l__image_ury_dim { \box_ht:N \l__image_tmp_box }
24660   \dim_const:cn { c__image_ #1#3 _urx_dim }
24661   { \l__image_urx_dim }
24662   \dim_const:cn { c__image_ #1#3 _ury_dim }
24663   { \l__image_ury_dim }
24664 }
24665 \cs_new:Npn \_driver_image_getbb_pagebox:w #1 box {#1}

```

(End definition for \\_driver\_image\_getbb\_jpg:n and others.)

\\_driver\_image\_include\_pdf:n For PDF images, properly supporting the `pagebox` concept in X<sub>Y</sub>TeX is best done using the `\xetex_pdffile:D` primitive. The syntax here is the same as for the image measurement part, although we know at this stage that there must be some valid setting for `\l__image_pagebox_tl`.

```

24666 \cs_new_protected:Npn \_driver_image_include_pdf:n #1
24667 {
24668   \xetex_pdffile:D "#1" ~
24669   \int_compare:nNnT \l__image_page_int > 0
24670   { page~ \int_use:N \l__image_page_int }
24671   \_driver_image_getbb_auxiv:VnNnn \l__image_pagebox_tl
24672 }

```

(End definition for \\_driver\_image\_include\_pdf:n.)

```

24673 </xdvipdfmx>

```

## 44.12 Drawing commands: pdfmode and (x)dvipdfmx

Both `pdfmode` and `(x)dvipdfmx` directly produce PDF output and understand a shared set of specials for drawing commands.

```

24674 (*dvipdfmx | pdfmode | xdvipdfmx)

```

## 44.13 Drawing

`\_driver_draw_literal:n` Pass data through using a dedicated interface.  
`\_driver_draw_literal:x` 24675 \cs\_new\_eq:NN \\_driver\_draw\_literal:n \\_driver\_literal:n  
24676 \cs\_generate\_variant:Nn \\_driver\_draw\_literal:n { x }  
*(End definition for \\_driver\_draw\_literal:n.)*

`\_driver_draw_begin:` No special requirements here, so simply set up a drawing scope.  
`\_driver_draw_end:` 24677 \cs\_new\_protected:Npn \\_driver\_draw\_begin:  
24678 { \\_driver\_draw\_scope\_begin: }  
24679 \cs\_new\_protected:Npn \\_driver\_draw\_end:  
24680 { \\_driver\_draw\_scope\_end: }  
*(End definition for \\_driver\_draw\_begin: and \\_driver\_draw\_end:.)*

`\_driver_draw_scope_begin:` In contrast to a general scope, a drawing scope is always done using the PDF operators  
`\_driver_draw_scope_end:` so is the same for all relevant drivers.  
24681 \cs\_new\_protected:Npn \\_driver\_draw\_scope\_begin:  
24682 { \\_driver\_draw\_literal:n { q } }  
24683 \cs\_new\_protected:Npn \\_driver\_draw\_scope\_end:  
24684 { \\_driver\_draw\_literal:n { Q } }  
*(End definition for \\_driver\_draw\_scope\_begin: and \\_driver\_draw\_scope\_end:.)*

`\_driver_draw_moveto:nn` Path creation operations all resolve directly to PDF primitive steps, with only the need to  
`\_driver_draw_lineto:nn` convert to bp. Notice that x-type expansion is included here to ensure that any variable  
`\_driver_draw_curveto:nnnnnn` values are forced to literals before any possible caching.  
`\_driver_draw_rectangle:nnnn` 24685 \cs\_new\_protected:Npn \\_driver\_draw\_moveto:nn #1#2  
24686 {  
24687 \\_driver\_draw\_literal:x  
24688 { \dim\_to\_decimal\_in\_bp:n {#1} ~ \dim\_to\_decimal\_in\_bp:n {#2} ~ m }  
24689 }  
24690 \cs\_new\_protected:Npn \\_driver\_draw\_lineto:nn #1#2  
24691 {  
24692 \\_driver\_draw\_literal:x  
24693 { \dim\_to\_decimal\_in\_bp:n {#1} ~ \dim\_to\_decimal\_in\_bp:n {#2} ~ l }  
24694 }  
24695 \cs\_new\_protected:Npn \\_driver\_draw\_curveto:nnnnnn #1#2#3#4#5#6  
24696 {  
24697 \\_driver\_draw\_literal:x  
24698 {  
24699 \dim\_to\_decimal\_in\_bp:n {#1} ~ \dim\_to\_decimal\_in\_bp:n {#2} ~  
24700 \dim\_to\_decimal\_in\_bp:n {#3} ~ \dim\_to\_decimal\_in\_bp:n {#4} ~  
24701 \dim\_to\_decimal\_in\_bp:n {#5} ~ \dim\_to\_decimal\_in\_bp:n {#6} ~  
24702 c  
24703 }  
24704 }  
24705 \cs\_new\_protected:Npn \\_driver\_draw\_rectangle:nnnn #1#2#3#4  
24706 {  
24707 \\_driver\_draw\_literal:x  
24708 {  
24709 \dim\_to\_decimal\_in\_bp:n {#1} ~ \dim\_to\_decimal\_in\_bp:n {#2} ~  
24710 \dim\_to\_decimal\_in\_bp:n {#3} ~ \dim\_to\_decimal\_in\_bp:n {#4} ~

```

24711         re
24712     }
24713 }

```

(End definition for `\_driver\_draw\_moveto:nn` and others.)

The even-odd rule here can be implemented as a simply switch.

```

\__driver\_draw\_evenodd\_rule:
\__driver\_draw\_nonzero\_rule:
\g\_driver\_draw\_eor\_bool
24714 \cs\_new\_protected:Npn \__driver\_draw\_evenodd\_rule:
24715 { \bool\_gset\_true:N \g\_driver\_draw\_eor\_bool }
24716 \cs\_new\_protected:Npn \__driver\_draw\_nonzero\_rule:
24717 { \bool\_gset\_false:N \g\_driver\_draw\_eor\_bool }
24718 \bool\_new:N \g\_driver\_draw\_eor\_bool

```

(End definition for `\_driver\_draw\_evenodd\_rule:`, `\_driver\_draw\_nonzero\_rule:`, and `\g\_driver\_draw\_eor\_bool`.)

Converting paths to output is again a case of mapping directly to PDF operations.

```

\__driver\_draw\_closepath:
\__driver\_draw\_stroke:
\__driver\_draw\_closestroke:
\__driver\_draw\_fill:
\__driver\_draw\_fillstroke:
\__driver\_draw\_clip:
\__driver\_draw\_discardpath:
24719 \cs\_new\_protected:Npn \__driver\_draw\_closepath:
24720 { \__driver\_draw\_literal:n { h } }
24721 \cs\_new\_protected:Npn \__driver\_draw\_stroke:
24722 { \__driver\_draw\_literal:n { S } }
24723 \cs\_new\_protected:Npn \__driver\_draw\_closestroke:
24724 { \__driver\_draw\_literal:n { s } }
24725 \cs\_new\_protected:Npn \__driver\_draw\_fill:
24726 {
24727     \__driver\_draw\_literal:x
24728     { f \bool\_if:NT \g\_driver\_draw\_eor\_bool * }
24729 }
24730 \cs\_new\_protected:Npn \__driver\_draw\_fillstroke:
24731 {
24732     \__driver\_draw\_literal:x
24733     { B \bool\_if:NT \g\_driver\_draw\_eor\_bool * }
24734 }
24735 \cs\_new\_protected:Npn \__driver\_draw\_clip:
24736 {
24737     \__driver\_draw\_literal:x
24738     { W \bool\_if:NT \g\_driver\_draw\_eor\_bool * }
24739 }
24740 \cs\_new\_protected:Npn \__driver\_draw\_discardpath:
24741 { \__driver\_draw\_literal:n { n } }

```

(End definition for `\_driver\_draw\_closepath:` and others.)

Converting paths to output is again a case of mapping directly to PDF operations.

```

\__driver\_draw\_dash:nn
\__driver\_draw\_dash:n
\__driver\_draw\_linewidth:n
\__driver\_draw\_miterlimit:n
\__driver\_draw\_cap\_butt:
\__driver\_draw\_cap\_round:
\__driver\_draw\_cap\_rectangle:
\__driver\_draw\_join\_miter:
\__driver\_draw\_join\_round:
\__driver\_draw\_join\_bevel:
24742 \cs\_new\_protected:Npn \__driver\_draw\_dash:nn #1#2
24743 {
24744     \__driver\_draw\_literal:x
24745     {
24746         [ ~
24747         \clist\_map\_function:nN {#1} \__driver\_draw\_dash:n
24748         ] ~
24749         \dim\_to\_decimal\_in\_bp:n {#2} ~ d
24750     }
24751 }
24752 \cs\_new:Npn \__driver\_draw\_dash:n #1

```

```

24753 { \dim_to_decimal_in_bp:n {#1} ~ }
24754 \cs_new_protected:Npn \__driver_draw_linewidth:n #1
24755 {
24756   \__driver_draw_literal:x
24757   { \dim_to_decimal_in_bp:n {#1} ~ w }
24758 }
24759 \cs_new_protected:Npn \__driver_draw_miterlimit:n #1
24760 { \__driver_draw_literal:x { \fp_eval:n {#1} ~ M } }
24761 \cs_new_protected:Npn \__driver_draw_cap_but:
24762 { \__driver_draw_literal:n { 0 ~ J } }
24763 \cs_new_protected:Npn \__driver_draw_cap_round:
24764 { \__driver_draw_literal:n { 1 ~ J } }
24765 \cs_new_protected:Npn \__driver_draw_cap_rectangle:
24766 { \__driver_draw_literal:n { 2 ~ J } }
24767 \cs_new_protected:Npn \__driver_draw_join_miter:
24768 { \__driver_draw_literal:n { 0 ~ j } }
24769 \cs_new_protected:Npn \__driver_draw_join_round:
24770 { \__driver_draw_literal:n { 1 ~ j } }
24771 \cs_new_protected:Npn \__driver_draw_join_bevel:
24772 { \__driver_draw_literal:n { 2 ~ j } }

```

(End definition for \\_\_driver\_draw\_dash:nn and others.)

Yet more fast conversion, all using the FPU to allow for expressions in numerical input.

```

\__driver_draw_color_cmyk:nnnn
\__driver_draw_color_cmyk fill:nnnn
\__driver_draw_color_cmyk stroke:nnnn
\__driver_draw_color_cmyk_aux:nnnn
\__driver_draw_color_gray:n
\__driver_draw_color_gray fill:n
\__driver_draw_color_gray stroke:n
\__driver_draw_color_gray_aux:n
\__driver_draw_color_rgb:nnnn
\__driver_draw_color_rgb fill:nnn
\__driver_draw_color_rgb stroke:nnn
\__driver_draw_color_rgb_aux:nnnn
24773 \cs_new_protected:Npn \__driver_draw_color_cmyk:nnnn #1#2#3#4
24774 {
24775   \use:x
24776   {
24777     \__driver_draw_color_cmyk_aux:nnnn
24778     { \fp_eval:n {#1} }
24779     { \fp_eval:n {#2} }
24780     { \fp_eval:n {#3} }
24781     { \fp_eval:n {#4} }
24782   }
24783 }
24784 \cs_new_protected:Npn \__driver_draw_color_cmyk_aux:nnnn #1#2#3#4
24785 {
24786   \__driver_draw_literal:n
24787   { #1 ~ #2 ~ #3 ~ #4 ~ k ~ #1 ~ #2 ~ #3 ~ #4 ~ K }
24788 }
24789 \cs_new_protected:Npn \__driver_draw_color_cmyk_fill:nnnn #1#2#3#4
24790 {
24791   \__driver_draw_literal:x
24792   {
24793     \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
24794     \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
24795     k
24796   }
24797 }
24798 \cs_new_protected:Npn \__driver_draw_color_cmyk_stroke:nnnn #1#2#3#4
24799 {
24800   \__driver_draw_literal:x
24801   {
24802     \fp_eval:n {#1} ~ \fp_eval:n {#2} ~

```



```

24803         \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
24804         K
24805     }
24806 }
24807 \cs_new_protected:Npn \__driver_draw_color_gray:n #1
24808 {
24809     \use:x
24810     { \__driver_draw_color_gray_aux:n { \fp_eval:n {#1} } }
24811 }
24812 \cs_new_protected:Npn \__driver_draw_color_gray_aux:n #1
24813 {
24814     \__driver_draw_literal:n { #1 ~ g ~ #1 ~ G }
24815 }
24816 \cs_new_protected:Npn \__driver_draw_color_gray_fill:n #1
24817 { \__driver_draw_literal:x { \fp_eval:n {#1} ~ g } }
24818 \cs_new_protected:Npn \__driver_draw_color_gray_stroke:n #1
24819 { \__driver_draw_literal:x { \fp_eval:n {#1} ~ G } }
24820 \cs_new_protected:Npn \__driver_draw_color_rgb:nnn #1#2#3
24821 {
24822     \use:x
24823     {
24824         \__driver_draw_color_rgb_aux:nnn
24825         { \fp_eval:n {#1} }
24826         { \fp_eval:n {#2} }
24827         { \fp_eval:n {#3} }
24828     }
24829 }
24830 \cs_new_protected:Npn \__driver_draw_color_rgb_aux:nnn #1#2#3
24831 {
24832     \__driver_draw_literal:n
24833     { #1 ~ #2 ~ #3 ~ rg ~ #1 ~ #2 ~ #3 ~ RG }
24834 }
24835 \cs_new_protected:Npn \__driver_draw_color_rgb_fill:nnn #1#2#3
24836 {
24837     \__driver_draw_literal:x
24838     { \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~ rg }
24839 }
24840 \cs_new_protected:Npn \__driver_draw_color_rgb_stroke:nnn #1#2#3
24841 {
24842     \__driver_draw_literal:x
24843     { \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~ RG }
24844 }

```

(End definition for \\_\_driver\_draw\_color\_cmyk:nnnn and others.)

`\__driver_draw_transformcm:nnnnnn` The first four arguments here are floats (the affine matrix), the last two are a displacement vector. Once again, force evaluation to allow for caching.

```

24845 \cs_new_protected:Npn \__driver_draw_transformcm:nnnnnn #1#2#3#4#5#6
24846 {
24847     \__driver_draw_literal:x
24848     {
24849         \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
24850         \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
24851         \dim_to_decimal_in_bp:n {#5} ~ \dim_to_decimal_in_bp:n {#6} ~

```

```

24852         cm
24853     }
24854 }

```

(End definition for `\_driver\_draw\_transformcm:nnnnnn`.)

```

\_driver\_draw\_hbox:Nnnnnnn
\l\_driver\_tmp\_box

```

Inserting a TeX box transformed to the requested position and using the current matrix is done using a mixture of TeX and low-level manipulation. The offset can be handled by TeX, so only any rotation/skew/scaling component needs to be done using the matrix operation. As this operation can never be cached, the scope is set directly not using the draw version.

```

24855 \cs_new_protected:Npn \_driver\_draw\_hbox:Nnnnnnn #1#2#3#4#5#6#7
24856 {
24857     \hbox_set:Nn \l\_driver\_tmp\_box
24858     {
24859         \tex_kern:D \_dim_eval:w #6 \_dim_eval_end:
24860         \_driver\_scope_begin:
24861         \_driver\_draw\_transformcm:nnnnnn {#2} {#3} {#4} {#5}
24862         { Opt } { Opt }
24863         \box_move_up:nn {#7} { \box_use:N #1 }
24864         \_driver\_scope_end:
24865     }
24866     \box_set_wd:Nn \l\_driver\_tmp\_box { Opt }
24867     \box_set_ht:Nn \l\_driver\_tmp\_box { Opt }
24868     \box_set_dp:Nn \l\_driver\_tmp\_box { Opt }
24869     \box_use:N \l\_driver\_tmp\_box
24870 }
24871 \box_new:N \l\_driver\_tmp\_box

```

(End definition for `\_driver\_draw\_hbox:Nnnnnnn` and `\l\_driver\_tmp\_box`.)

```

24872 </dviptfm | pdfmode | xdvipdfmx>

```

## 44.14 dvisvgm driver

```

24873 (*dvisvgm)

```

### 44.14.1 Basics

```

\_driver\_literal:n

```

Unlike the other drivers, the requirements for making SVG files mean that we can't conveniently transform all operations to the current point. That makes life a bit more tricky later as that needs to be accounted for. A new line is added after each call to help to keep the output readable for debugging.

```

24874 \cs_new_protected:Npn \_driver\_literal:n #1
24875 { \tex_special:D { dvisvgm:raw~ #1 { ?nl } } }

```

(End definition for `\_driver\_literal:n`.)

```

\_driver\_scope_begin:
\_driver\_scope_end:

```

A scope in SVG terms is slightly different to the other drivers as operations have to be “tied” to these not simply inside them.

```

24876 \cs_new_protected:Npn \_driver\_scope_begin:
24877 { \_driver\_literal:n { <g> } }
24878 \cs_new_protected:Npn \_driver\_scope_end:
24879 { \_driver\_literal:n { </g> } }

```

(End definition for `\_driver\_scope_begin:` and `\_driver\_scope_end:.`)

## 44.15 Driver-specific auxiliaries

`\__driver_scope_begin:n` In SVG transformations, clips and so on are attached directly to scopes so we need a way or allowing for that. This is rather more useful than `\__driver_scope_begin:` as a result. No assumptions are made about the nature of the scoped operation(s).

```
24880 \cs_new_protected:Npn \__driver_scope_begin:n #1
24881 { \__driver_literal:n { <g~ #1 > } }
```

(End definition for `\__driver_scope_begin:n`.)

### 44.15.1 Box operations

`\__driver_box_use_clip:N` Clipping in SVG is more involved than with other drivers. The first issue is that the clipping path must be defined separately from where it is used, so we need to track how many paths have applied. The naming here uses `l3cp` as the namespace with a number following. Rather than use a rectangular operation, we define the path manually as this allows it to have a depth: easier than the alternative approach of shifting content up and down using scopes to allow for the depth of the  $\text{\TeX}$  box and keep the reference point the same!

`\g__driver_clip_path_int`

```
24882 \cs_new_protected:Npn \__driver_box_use_clip:N #1
24883 {
24884   \int_gincr:N \g__driver_clip_path_int
24885   \__driver_literal:n
24886     { < clipPath-id = " l3cp \int_use:N \g__driver_clip_path_int " > }
24887   \__driver_literal:n
24888     {
24889       <
24890         path ~ d =
24891           "
24892             M ~ 0 ~
24893               \dim_to_decimal:n { -\box_dp:N #1 } ~
24894             L ~ \dim_to_decimal:n { \box_wd:N #1 } ~
24895               \dim_to_decimal:n { -\box_dp:N #1 } ~
24896             L ~ \dim_to_decimal:n { \box_wd:N #1 } ~
24897               \dim_to_decimal:n { \box_ht:N #1 + \box_dp:N #1 } ~
24898             L ~ 0 ~
24899               \dim_to_decimal:n { \box_ht:N #1 + \box_dp:N #1 } ~
24900             Z
24901           "
24902         />
24903       }
24904   \__driver_literal:n
24905     { < /clipPath > }
```

In general the SVG set up does not try to transform coordinates to the current point. For clipping we need to do that, so have a transformation here to get us to the right place, and a matching one just before the  $\text{\TeX}$  box is inserted to get things back on track. The clip path needs to come between those two such that it lines up with the current point, as does the  $\text{\TeX}$  box.

```
24906 \__driver_scope_begin:n
24907 {
24908   transform =
24909     "
```

```

24910         translate ( { ?x } , { ?y } ) ~
24911         scale ( 1 , -1 )
24912     "
24913 }
24914 \__driver_scope_begin:n
24915 {
24916     clip-path = "url ( \c_hash_str l3cp \int_use:N \g__driver_clip_path_int ) "
24917 }
24918 \__driver_scope_begin:n
24919 {
24920     transform =
24921     "
24922         scale ( -1 , 1 ) ~
24923         translate ( { ?x } , { ?y } ) ~
24924         scale ( -1 , -1 )
24925     "
24926 }
24927 \box_use:N #1
24928 \__driver_scope_end:
24929 \__driver_scope_end:
24930 \__driver_scope_end:
24931 % \skip_horizontal:n { \box_wd:N #1 }
24932 }
24933 \int_new:N \g__driver_clip_path_int

```

(End definition for \\_\_driver\_box\_use\_clip:N and \g\_\_driver\_clip\_path\_int.)

**\\_\_driver\_box\_use\_rotate:Nn** Rotation has a dedicated operation which includes a centre-of-rotation optional pair. That can be picked up from the driver syntax, so there is no need to worry about the transformation matrix.

```

24934 \cs_new_protected:Npn \__driver_box_use_rotate:Nn #1#2
24935 {
24936     \__driver_scope_begin:n
24937     {
24938         transform =
24939         "
24940             rotate
24941             ( \fp_eval:n { round ( -#2 , 5 ) } , ~ { ?x } , ~ { ?y } )
24942         "
24943     }
24944     \box_use:N #1
24945     \__driver_scope_end:
24946 }

```

(End definition for \\_\_driver\_box\_use\_rotate:Nn.)

**\\_\_driver\_box\_use\_scale:Nnn** In contrast to rotation, we have to account for the current position in this case. That is done using a couple of translations in addition to the scaling (which is therefore done backward with a flip).

```

24947 \cs_new_protected:Npn \__driver_box_use_scale:Nnn #1#2#3
24948 {
24949     \__driver_scope_begin:n
24950     {
24951         transform =

```

```

24952         "
24953         translate ( { ?x } , { ?y } ) ~
24954         scale
24955         (
24956             \fp_eval:n { round ( -#2 , 5 ) } ,
24957             \fp_eval:n { round ( -#3 , 5 ) }
24958         ) ~
24959         translate ( { ?x } , { ?y } ) ~
24960         scale ( -1 )
24961     "
24962 }
24963 \hbox_overlap_right:n { \box_use:N #1 }
24964 \__driver_scope_end:
24965 }

```

(End definition for \\_\_driver\_box\_use\_scale:Nnn.)

## 44.16 Images

\\_\_driver\_image\_getbb\_png:n  
\\_\_driver\_image\_getbb\_jpg:n

These can be included by extracting the bounding box data.

```

24966 \cs_new_eq:NN \__driver_image_getbb_png:n \__image_extract_bb:n
24967 \cs_new_eq:NN \__driver_image_getbb_jpg:n \__image_extract_bb:n

```

(End definition for \\_\_driver\_image\_getbb\_png:n and \\_\_driver\_image\_getbb\_jpg:n.)

\\_driver\_image\_include\_png:n  
\\_driver\_image\_include\_jpg:n  
\\_driver\_image\_include\_bitmap\_quote:w

The driver here has built-in support for basic image inclusion (see `dvisvgm.def` for a more complex approach, needed if clipping, *etc.*, is covered at the image driver level).

The only issue is that `#1` must be quote-corrected. The `dvisvgm:img` operation quotes the file name, but if it is already quoted (contains spaces) then we have an issue: we simply strip off any quotes as a result.

```

24968 \cs_new_protected:Npn \__driver_image_include_png:n #1
24969 {
24970     \tex_special:D
24971     {
24972         dvisvgm:img~
24973         \dim_to_decimal:n { \l__image_ury_dim } ~
24974         \dim_to_decimal:n { \l__image_ury_dim } ~
24975         \__driver_image_include_bitmap_quote:w #1 " " \q_stop
24976     }
24977 }
24978 \cs_new_eq:NN \__driver_image_include_jpg:n \__driver_image_include_png:n
24979 \cs_new:Npn \__driver_image_include_bitmap_quote:w #1 " #2 " #3 \q_stop { #1#2 }

```

(End definition for \\_\_driver\_image\_include\_png:n, \\_\_driver\_image\_include\_jpg:n, and \\_\_driver\_image\_include\_bitmap\_quote:w.)

## 44.17 Drawing

\\_\_driver\_draw\_literal:n  
\\_driver\_draw\_literal:x

The same as the more general literal call.

```

24980 \cs_new_eq:NN \__driver_draw_literal:n \__driver_literal:n
24981 \cs_generate_variant:Nn \__driver_draw_literal:n { x }

```

(End definition for \\_\_driver\_draw\_literal:n.)

`\__driver_draw_begin:` A drawing needs to be set up such that the co-ordinate system is translated. That is  
`\__driver_draw_end:` done inside a scope, which as described below

```
24982 \cs_new_protected:Npn \__driver_draw_begin:
24983 {
24984   \__driver_draw_scope_begin:
24985   \__driver_draw_scope:n { transform="translate({?x},{?y})~scale(1,-1)" }
24986 }
24987 \cs_new_protected:Npn \__driver_draw_end:
24988 { \__driver_draw_scope_end: }
```

(End definition for `\__driver_draw_begin:` and `\__driver_draw_end:.`)

`\__driver_draw_scope_begin:` Several settings that with other drivers are “stand alone” have to be given as part of  
`\__driver_draw_scope_end:` a scope in SVG. As a result, there is a need to provide a mechanism to automatically  
`\__driver_draw_scope:n` close these extra scopes. That is done using a dedicated function and a pair of tracking  
`\__driver_draw_scope:x` variables. Within each graphics scope we use a global variable to do the work, with a  
`\g__driver_draw_scope_int` group used to save the value between scopes. The result is that no direct action is needed  
`\l__driver_draw_scope_int` when creating a scope.

```
24989 \cs_new_protected:Npn \__driver_draw_scope_begin:
24990 {
24991   \int_set_eq:NN
24992   \l__driver_draw_scope_int
24993   \g__driver_draw_scope_int
24994   \group_begin:
24995   \int_gzero:N \g__driver_draw_scope_int
24996 }
24997 \cs_new_protected:Npn \__driver_draw_scope_end:
24998 {
24999   \prg_replicate:nn
25000   { \g__driver_draw_scope_int }
25001   { \__driver_draw_literal:n { </g> } }
25002   \group_end:
25003   \int_gset_eq:NN
25004   \g__driver_draw_scope_int
25005   \l__driver_draw_scope_int
25006 }
25007 \cs_new_protected:Npn \__driver_draw_scope:n #1
25008 {
25009   \__driver_draw_literal:n { <g~ #1 > }
25010   \int_gincr:N \g__driver_draw_scope_int
25011 }
25012 \cs_generate_variant:Nn \__driver_draw_scope:n { x }
25013 \int_new:N \g__driver_draw_scope_int
25014 \int_new:N \l__driver_draw_scope_int
```

(End definition for `\__driver_draw_scope_begin:` and others.)

`\__driver_draw_moveto:nn` Once again, some work is needed to get path constructs correct. Rather than write the  
`\__driver_draw_lineto:nn` values as they are given, the entire path needs to be collected up before being output  
`\__driver_draw_rectangle:nnnn` in one go. For that we use a dedicated storage routine, which adds spaces as required.  
`\__driver_draw_curveto:nnnnnn` Since paths should be fully expanded there is no need to worry about the internal x-type  
`\__driver_draw_add_to_path:n` expansion.

```
\g__driver_draw_path_tl 25015 \cs_new_protected:Npn \__driver_draw_moveto:nn #1#2
```

```

25016 {
25017   \__driver_draw_add_to_path:n
25018   { M ~ \dim_to_decimal:n {#1} ~ \dim_to_decimal:n {#2} }
25019 }
25020 \cs_new_protected:Npn \__driver_draw_lineto:nn #1#2
25021 {
25022   \__driver_draw_add_to_path:n
25023   { L ~ \dim_to_decimal:n {#1} ~ \dim_to_decimal:n {#2} }
25024 }
25025 \cs_new_protected:Npn \__driver_draw_rectangle:nnnn #1#2#3#4
25026 {
25027   \__driver_draw_add_to_path:n
25028   {
25029     M ~ \dim_to_decimal:n {#1} ~ \dim_to_decimal:n {#2}
25030     h ~ \dim_to_decimal:n {#3} ~
25031     v ~ \dim_to_decimal:n {#4} ~
25032     h ~ \dim_to_decimal:n { -#3 } ~
25033     Z
25034   }
25035 }
25036 \cs_new_protected:Npn \__driver_draw_curveto:nnnnnn #1#2#3#4#5#6
25037 {
25038   \__driver_draw_add_to_path:n
25039   {
25040     C ~
25041     \dim_to_decimal:n {#1} ~ \dim_to_decimal:n {#2} ~
25042     \dim_to_decimal:n {#3} ~ \dim_to_decimal:n {#4} ~
25043     \dim_to_decimal:n {#5} ~ \dim_to_decimal:n {#6}
25044   }
25045 }
25046 \cs_new_protected:Npn \__driver_draw_add_to_path:n #1
25047 {
25048   \tl_gset:Nx \g__driver_draw_path_tl
25049   {
25050     \g__driver_draw_path_tl
25051     \tl_if_empty:NF \g__driver_draw_path_tl { \c_space_tl }
25052     #1
25053   }
25054 }
25055 \tl_new:N \g__driver_draw_path_tl

```

(End definition for \\_\_driver\_draw\_moveto:nn and others.)

The fill rules here have to be handled as scopes.

```

25056 \cs_new_protected:Npn \__driver_draw_evenodd_rule:
25057   { \__driver_draw_scope:n { fill-rule="evenodd" } }
25058 \cs_new_protected:Npn \__driver_draw_nonzero_rule:
25059   { \__driver_draw_scope:n { fill-rule="nonzero" } }

```

(End definition for \\_\_driver\_draw\_evenodd\_rule: and \\_\_driver\_draw\_nonzero\_rule:.)

```

\__driver_draw_path:n
\__driver_draw_closepath:
\__driver_draw_stroke:
\__driver_draw_closestroke:
\__driver_draw_fill:
\__driver_draw_fillstroke:
\__driver_draw_clip:
\__driver_draw_discardpath:
\g__driver_draw_clip_bool
\g__driver_draw_path_int

```

Setting fill and stroke effects and doing clipping all has to be done using scopes. This means setting up the various requirements in a shared auxiliary which deals with the bits and pieces. Clipping paths are reused for path drawing: not essential but avoids

constructing them twice. Discarding a path needs a separate function as it's not quite the same.

```

25060 \cs_new_protected:Npn \__driver_draw_closepath:
25061 { \__driver_draw_add_to_path:n { Z } }
25062 \cs_new_protected:Npn \__driver_draw_path:n #1
25063 {
25064   \bool_if:NTF \g__driver_draw_clip_bool
25065   {
25066     \int_gincr:N \g__driver_clip_path_int
25067     \__driver_draw_literal:x
25068     {
25069       < clipPath-id = " l3cp \int_use:N \g__driver_clip_path_int " >
25070       { ?nl }
25071       <path-d=" \g__driver_draw_path_tl "/> { ?nl }
25072       < /clipPath > { ? nl }
25073       <
25074         use-xlink:href =
25075         "\c_hash_str l3path \int_use:N \g__driver_path_int " ~
25076         #1
25077       />
25078     }
25079     \__driver_draw_scope:x
25080     {
25081       clip-path =
25082       "url( \c_hash_str l3cp \int_use:N \g__driver_clip_path_int)"
25083     }
25084   }
25085   {
25086     \__driver_draw_literal:x
25087     { <path ~ d=" \g__driver_draw_path_tl " ~ #1 /> }
25088   }
25089   \tl_gclear:N \g__driver_draw_path_tl
25090   \bool_gset_false:N \g__driver_draw_clip_bool
25091 }
25092 \int_new:N \g__driver_path_int
25093 \cs_new_protected:Npn \__driver_draw_stroke:
25094 { \__driver_draw_path:n { style="fill:none" } }
25095 \cs_new_protected:Npn \__driver_draw_closestroke:
25096 {
25097   \__driver_draw_closepath:
25098   \__driver_draw_stroke:
25099 }
25100 \cs_new_protected:Npn \__driver_draw_fill:
25101 { \__driver_draw_path:n { style="stroke:none" } }
25102 \cs_new_protected:Npn \__driver_draw_fillstroke:
25103 { \__driver_draw_path:n { } }
25104 \cs_new_protected:Npn \__driver_draw_clip:
25105 { \bool_gset_true:N \g__driver_draw_clip_bool }
25106 \bool_new:N \g__driver_draw_clip_bool
25107 \cs_new_protected:Npn \__driver_draw_discardpath:
25108 {
25109   \bool_if:NT \g__driver_draw_clip_bool
25110   {
25111     \int_gincr:N \g__driver_clip_path_int

```



```

25112     \_driver_draw_literal:x
25113     {
25114         < clipPath-id = " l3cp \int_use:N \g__driver_clip_path_int " >
25115             { ?nl }
25116             <path-d=" \g__driver_draw_path_tl "/> { ?nl }
25117             < /clipPath >
25118         }
25119     \_driver_draw_scope:x
25120     {
25121         clip-path =
25122             "url( \c_hash_str l3cp \int_use:N \g__driver_clip_path_int)"
25123     }
25124 }
25125 \tl_gclear:N \g__driver_draw_path_tl
25126 \bool_gset_false:N \g__driver_draw_clip_bool
25127 }

```

(End definition for \\_driver\_draw\_path:n and others.)

All of these ideas are properties of scopes in SVG. The only slight complexity is converting the dash array properly (doing any required maths).

```

\__driver_draw_dash:nn
\__driver_draw_dash:n
\__driver_draw_dash_aux:nn
\__driver_draw_linewidth:n
\__driver_draw_miterlimit:n
\__driver_draw_cap_but:
\__driver_draw_cap_round:
\__driver_draw_cap_rectangle:
\__driver_draw_join_miter:
\__driver_draw_join_round:
\__driver_draw_join_bevel:
25128 \cs_new_protected:Npn \_driver_draw_dash:nn #1#2
25129 {
25130     \use:x
25131     {
25132         \__driver_draw_dash_aux:nn
25133         { \clist_map_function:nn {#1} \__driver_draw_dash:n }
25134         { \dim_to_decimal:n {#2} }
25135     }
25136 }
25137 \cs_new:Npn \_driver_draw_dash:n #1
25138 { , \dim_to_decimal_in_bp:n {#1} }
25139 \cs_new_protected:Npn \_driver_draw_dash_aux:nn #1#2
25140 {
25141     \__driver_draw_scope:x
25142     {
25143         stroke-dasharray =
25144         "
25145             \tl_if_empty:oTF { \use_none:n #1 }
25146             { none }
25147             { \use_none:n #1 }
25148         " ~
25149         stroke-offset=" #2 "
25150     }
25151 }
25152 \cs_new_protected:Npn \_driver_draw_linewidth:n #1
25153 { \__driver_draw_scope:x { stroke-width=" \dim_to_decimal:n {#1} " } }
25154 \cs_new_protected:Npn \_driver_draw_miterlimit:n #1
25155 { \__driver_draw_scope:x { stroke-miterlimit=" \fp_eval:n {#1} " } }
25156 \cs_new_protected:Npn \_driver_draw_cap_but:
25157 { \__driver_draw_scope:n { stroke-linecap="butt" } }
25158 \cs_new_protected:Npn \_driver_draw_cap_round:
25159 { \__driver_draw_scope:n { stroke-linecap="round" } }
25160 \cs_new_protected:Npn \_driver_draw_cap_rectangle:

```

```

25161 { \_driver_draw_scope:n { stroke-linecap="square" } }
25162 \cs_new_protected:Npn \_driver_draw_join_miter:
25163 { \_driver_draw_scope:n { stroke-linejoin="miter" } }
25164 \cs_new_protected:Npn \_driver_draw_join_round:
25165 { \_driver_draw_scope:n { stroke-linejoin="round" } }
25166 \cs_new_protected:Npn \_driver_draw_join_bevel:
25167 { \_driver_draw_scope:n { stroke-linejoin="bevel" } }

```

(End definition for \\_driver\_draw\_dash:nn and others.)

SVG only works with RGB colors, so there is some conversion to do. The values also need to be given as percentages, which means a little more maths.

```

\_driver_draw_color_cmyk:nnnn
\_driver_draw_color_cmyk_fill:nnnn
\_driver_draw_color_cmyk_stroke:nnnn
\_driver_draw_color_gray:n
\_driver_draw_color_gray_fill:n
\_driver_draw_color_gray_stroke:n
\_driver_draw_color_rgb:nnnn
\_driver_draw_color_rgb_fill:nnnn
\_driver_draw_color_rgb_stroke:nnnn

25168 \cs_new_protected:Npn \_driver_draw_color_cmyk_aux:NNnnnnn #1#2#3#4#5#6
25169 {
25170   \use:x
25171   {
25172     \_driver_draw_color_rgb_auxii:nnn
25173     { \fp_eval:n { -100 * ( (#3) * ( 1 - (#6) ) - 1 ) } }
25174     { \fp_eval:n { -100 * ( (#4) * ( 1 - (#6) ) + #6 - 1 ) } }
25175     { \fp_eval:n { -100 * ( (#5) * ( 1 - (#6) ) + #6 - 1 ) } }
25176   }
25177   #1 #2
25178 }
25179 \cs_new_protected:Npn \_driver_draw_color_cmyk:nnnn
25180 { \_driver_draw_color_cmyk_aux:NNnnnnn \c_true_bool \c_true_bool }
25181 \cs_new_protected:Npn \_driver_draw_color_cmyk_fill:nnnn
25182 { \_driver_draw_color_cmyk_aux:NNnnnnn \c_false_bool \c_true_bool }
25183 \cs_new_protected:Npn \_driver_draw_color_cmyk_stroke:nnnn
25184 { \_driver_draw_color_cmyk_aux:NNnnnnn \c_true_bool \c_false_bool }
25185 \cs_new_protected:Npn \_driver_draw_color_gray_aux:NNn #1#2#3
25186 {
25187   \use:x
25188   {
25189     \_driver_draw_color_gray_aux:nnN
25190     { \fp_eval:n { 100 * (#3) } }
25191   }
25192   #1 #2
25193 }
25194 \cs_new_protected:Npn \_driver_draw_color_gray_aux:nnN #1
25195 { \_driver_draw_color_rgb_auxii:nnnNN {#1} {#1} {#1} }
25196 \cs_generate_variant:Nn \_driver_draw_color_gray_aux:nnN { x }
25197 \cs_new_protected:Npn \_driver_draw_color_gray:n
25198 { \_driver_draw_color_gray_aux:NNn \c_true_bool \c_true_bool }
25199 \cs_new_protected:Npn \_driver_draw_color_gray_fill:n
25200 { \_driver_draw_color_gray_aux:NNn \c_false_bool \c_true_bool }
25201 \cs_new_protected:Npn \_driver_draw_color_gray_stroke:n
25202 { \_driver_draw_color_gray_aux:NNn \c_true_bool \c_false_bool }
25203 \cs_new_protected:Npn \_driver_draw_color_rgb_auxi:NNnnn #1#2#3#4#5
25204 {
25205   \use:x
25206   {
25207     \_driver_draw_color_rgb_auxii:nnnNN
25208     { \fp_eval:n { 100 * (#3) } }
25209     { \fp_eval:n { 100 * (#4) } }

```

```

25210         { \fp_eval:n { 100 * (#5) } }
25211     }
25212     #1 #2
25213 }
25214 \cs_new_protected:Npn \__driver_draw_color_rgb_auxii:nnnNN #1#2#3#4#5
25215 {
25216     \__driver_draw_scope:x
25217     {
25218         \bool_if:NT #4
25219         {
25220             fill =
25221             "
25222             rgb
25223             (
25224                 #1 \c_percent_str ,
25225                 #2 \c_percent_str ,
25226                 #3 \c_percent_str
25227             )
25228             "
25229             \bool_if:NT #5 { ~ }
25230         }
25231         \bool_if:NT #5
25232         {
25233             stroke =
25234             "
25235             rgb
25236             (
25237                 #1 \c_percent_str ,
25238                 #2 \c_percent_str ,
25239                 #3 \c_percent_str
25240             )
25241             "
25242         }
25243     }
25244 }
25245 \cs_new_protected:Npn \__driver_draw_color_rgb:nnn
25246 { \__driver_draw_color_rgb_auxi:NNnnn \c_true_bool \c_true_bool }
25247 \cs_new_protected:Npn \__driver_draw_color_rgb_fill:nnn
25248 { \__driver_draw_color_rgb_auxi:NNnnn \c_false_bool \c_true_bool }
25249 \cs_new_protected:Npn \__driver_draw_color_rgb_stroke:nnn
25250 { \__driver_draw_color_rgb_auxi:NNnnn \c_true_bool \c_false_bool }

```

(End definition for \\_\_driver\_draw\_color\_cmyk:nnnn and others.)

**\\_\_driver\_draw\_transformcm:nnnnnn**

The first four arguments here are floats (the affine matrix), the last two are a displacement vector. Once again, force evaluation to allow for caching.

```

25251 \cs_new_protected:Npn \__driver_draw_transformcm:nnnnnn #1#2#3#4#5#6
25252 {
25253     \__driver_draw_scope:x
25254     {
25255         transform =
25256         "
25257         matrix
25258         (

```

```

25259         \fp_eval:n {#1} , \fp_eval:n {#2} ,
25260         \fp_eval:n {#3} , \fp_eval:n {#4} ,
25261         \dim_to_decimal:n {#5} , \dim_to_decimal:n {#6}
25262     )
25263     "
25264 }
25265 }

```

(End definition for \\_driver\_draw\_transformcm:nnnnnn.)

**\\_driver\_draw\_hbox:Nnnnnnn** No special savings can be made here: simply displace the box inside a scope. As there is nothing to re-box, just make the box passed of zero size.

```

25266 \cs_new_protected:Npn \_driver_draw_hbox:Nnnnnnn #1#2#3#4#5#6#7
25267 {
25268     \_driver_scope_begin:
25269     \_driver_draw_transformcm:nnnnnn {#2} {#3} {#4} {#5} {#6} {#7}
25270     \_driver_literal:n
25271     {
25272         < g~
25273         stroke="none"~
25274         transform="scale(-1,1)~translate({?x},{?y})~scale(-1,-1)"
25275     >
25276     }
25277     \group_begin:
25278     \box_set_wd:Nn #1 { Opt }
25279     \box_set_ht:Nn #1 { Opt }
25280     \box_set_dp:Nn #1 { Opt }
25281     \box_use:N #1
25282     \group_end:
25283     \_driver_literal:n { </g> }
25284     \_driver_scope_end:
25285 }

```

(End definition for \\_driver\_draw\_hbox:Nnnnnnn.)

25286 </dvisvgm>

25287 </initex | package>