

# The `xparse` package

## Document command parser\*

The L<sup>A</sup>T<sub>E</sub>X3 Project<sup>†</sup>

Released 2017/02/10

The `xparse` package provides a high-level interface for producing document-level commands. In that way, it is intended as a replacement for the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> `\newcommand` macro. However, `xparse` works so that the interface to a function (optional arguments, stars and mandatory arguments, for example) is separate from the internal implementation. `xparse` provides a normalised input for the internal form of a function, independent of the document-level argument arrangement.

At present, the functions in `xparse` which are regarded as “stable” are:

- `\DeclareDocumentCommand`
- `\NewDocumentCommand`
- `\RenewDocumentCommand`
- `\ProvideDocumentCommand`
- `\DeclareDocumentEnvironment`
- `\NewDocumentEnvironment`
- `\RenewDocumentEnvironment`
- `\ProvideDocumentEnvironment`
- `\DeclareExpandableDocumentCommand`
- `\IfNoValue(TF)`
- `\IfBoolean(TF)`

with the other functions currently regarded as “experimental”. Please try all of the commands provided here, but be aware that the experimental ones may change or disappear.

---

\*This file describes v6878, last revised 2017/02/10.

<sup>†</sup>E-mail: [latex-team@latex-project.org](mailto:latex-team@latex-project.org)

## 0.1 Specifying arguments

Before introducing the functions used to create document commands, the method for specifying arguments with `xparse` will be illustrated. In order to allow each argument to be defined independently, `xparse` does not simply need to know the number of arguments for a function, but also the nature of each one. This is done by constructing an *argument specification*, which defines the number of arguments, the type of each argument and any additional information needed for `xparse` to read the user input and properly pass it through to internal functions.

The basic form of the argument specifier is a list of letters, where each letter defines a type of argument. As will be described below, some of the types need additional information, such as default values. The argument types can be divided into two, those which define arguments that are mandatory (potentially raising an error if not found) and those which define optional arguments. The mandatory types are:

- m A standard mandatory argument, which can either be a single token alone or multiple tokens surrounded by curly braces. Regardless of the input, the argument will be passed to the internal code surrounded by a brace pair. This is the `xparse` type specifier for a normal `TeX` argument.
- l An argument which reads everything up to the first open group token: in standard `TeX` this is a left brace.
- r Reads a “required” delimited argument, where the delimiters are given as  $\langle token1 \rangle$  and  $\langle token2 \rangle$ : `r $\langle token1 \rangle\langle token2 \rangle$` . If the opening  $\langle token \rangle$  is missing, the default marker `-NoValue-` will be inserted after a suitable error.
- R As for `r`, this is a “required” delimited argument but has a user-definable recovery  $\langle default \rangle$ , given as `R $\langle token1 \rangle\langle token2 \rangle\{ \langle default \rangle \}$` .
- u Reads an argument “until”  $\langle tokens \rangle$  are encountered, where the desired  $\langle tokens \rangle$  are given as an argument to the specifier: `u $\{ \langle tokens \rangle \}$` .
- v Reads an argument “verbatim”, between the following character and its next occurrence, in a way similar to the argument of the `TeXε` command `\verb`. Thus a v-type argument is read between two matching tokens, which cannot be any of `%`, `\`, `#`, `{`, `}` or `␣`. The verbatim argument can also be enclosed between braces, `{` and `}`. A command with a verbatim argument will not work when it appears within an argument of another function.

The types which define optional arguments are:

- o A standard `TeX` optional argument, surrounded with square brackets, which will supply the special `-NoValue-` marker if not given (as described later).
- d An optional argument which is delimited by  $\langle token1 \rangle$  and  $\langle token2 \rangle$ , which are given as arguments: `d $\langle token1 \rangle\langle token2 \rangle$` . As with `o`, if no value is given the special marker `-NoValue-` is returned.
- O As for `o`, but returns  $\langle default \rangle$  if no value is given. Should be given as `O $\{ \langle default \rangle \}$` .
- D As for `d`, but returns  $\langle default \rangle$  if no value is given: `D $\langle token1 \rangle\langle token2 \rangle\{ \langle default \rangle \}$` . Internally, the `o`, `d` and `O` types are short-cuts to an appropriated-constructed `D` type argument.

- s An optional star, which will result in a value `\BooleanTrue` if a star is present and `\BooleanFalse` otherwise (as described later).
- t An optional  $\langle token \rangle$ , which will result in a value `\BooleanTrue` if  $\langle token \rangle$  is present and `\BooleanFalse` otherwise. Given as `t\langle token \rangle`.
- g An optional argument given inside a pair of `TeX` group tokens (in standard `LaTeX`, `{ ... }`), which returns `-NoValue-` if not present.
- G As for `g` but returns  $\langle default \rangle$  if no value is given: `G\langle default \rangle`.
- e An optional set of *embellishments*, each of which requires a *value*. If a key is not present, `-NoValue-` is returned. The returned data is a token list comprising one braced entry per key, ordered as for the key list in the argument specification. Given as `e\langle tokens \rangle`. *This is an experimental type.*
- E As for `e` but returns one or more  $\langle defaults \rangle$  if values are not given: `E\langle tokens \rangle\{\langle defaults \rangle\}`. See Section 0.6 for more details.

Using these specifiers, it is possible to create complex input syntax very easily. For example, given the argument definition ‘`s o o m O{default}`’, the input ‘`*[Foo]{Bar}`’ would be parsed as:

- #1 = `\BooleanTrue`
- #2 = `Foo`
- #3 = `-NoValue-`
- #4 = `Bar`
- #5 = `default`

whereas ‘`[One][Two]{}[Three]`’ would be parsed as:

- #1 = `\BooleanFalse`
- #2 = `One`
- #3 = `Two`
- #4 =
- #5 = `Three`

Delimited argument types (`d`, `o` and `r`) are defined such that they require matched pairs of delimiters when collecting an argument. For example

```
\DeclareDocumentCommand{\foo}{o}{#1}
\foo[[content]] % #1 = "[content]"
\foo[[] % Error: missing closing "]"
```

Also note that `{` and `}` cannot be used as delimiters as they are used by `TeX` as grouping tokens. Arguments to be grabbed inside these tokens must be created as either `m`- or `g`-type arguments.

Within delimited arguments, non-balanced or otherwise awkward tokens may be included by protecting the entire argument with a brace pair

```
\DeclareDocumentCommand{\foo}{o}{#1}
\foo[{[] % Allowed as the "[" is 'hidden'
```

These braces will be stripped if they surround the *entire* content of the optional argument

```
\DeclareDocumentCommand{\foo}{o}{#1}
\foo[{abc}] % => "abc"
\foo[ {abc}] % => " {abc}"
```

Two more tokens have a special meaning when creating an argument specifier. First, `+` is used to make an argument long (to accept paragraph tokens). In contrast to  $\text{\LaTeX 2}_\epsilon$ 's `\newcommand`, this applies on an argument-by-argument basis. So modifying the example to `'s o o +m O{default}'` means that the mandatory argument is now `\long`, whereas the optional arguments are not.

Secondly, the token `>` is used to declare so-called “argument processors”, which can be used to modify the contents of an argument before it is passed to the macro definition. The use of argument processors is a somewhat advanced topic, (or at least a less commonly used feature) and is covered in Section 0.9.

When an optional argument is followed by a mandatory argument with the same delimiter, `xparse` issues a warning because the optional argument could not be omitted by the user, thus becoming in effect mandatory. This applies to `o`, `d`, `O`, `D`, `s`, `t`, `e`, and `E` type arguments followed by `r` or `R`-type required arguments, but also to `g` or `G` type arguments followed by `m` type arguments.

## 0.2 Spacing and optional arguments

$\text{\TeX}$  will find the first argument after a function name irrespective of any intervening spaces. This is true for both mandatory and optional arguments. So `\foo[arg]` and `\foo_{arg}` are equivalent. Spaces are also ignored when collecting arguments up to the last mandatory argument to be collected (as it must exist). So after

```
\DeclareDocumentCommand \foo { m o m } { ... }
```

the user input `\foo{arg1}[arg2]{arg3}` and `\foo{arg1}_{arg2}_{arg3}` will both be parsed in the same way. However, spaces are *not* ignored when parsing optional arguments after the last mandatory argument. Thus with

```
\DeclareDocumentCommand \foo { m o } { ... }
```

`\foo{arg1}[arg2]` will find an optional argument but `\foo{arg1}_{arg2}` will not. This is so that trailing optional arguments are not picked up “by accident” in input.

There is one major exception to the rules listed above: when `xparse` is used to define what  $\text{\TeX}$  defines as “control symbols” in which the function name is made up of a single character, such as “`\`”, spaces are *not* ignored directly after them even for mandatory arguments.

## 0.3 Required delimited arguments

The contrast between a delimited (`D`-type) and “required delimited” (`R`-type) argument is that an error will be raised if the latter is missing. Thus for example

```
\DeclareDocumentCommand {\foo} {r()m} {}
\foo{oops}
```

will lead to an error message being issued. The marker `-NoValue-` (`r`-type) or user-specified default (for `R`-type) will be inserted to allow error recovery.

Users should note that support for required delimited arguments is somewhat experimental. Feedback is therefore very welcome on the `LaTeX-L` mailing list.

## 0.4 Verbatim arguments

Arguments of type `v` are read in verbatim mode, which will result in the grabbed argument consisting of tokens of category codes 12 (“other”) and 13 (“active”), except spaces, which are given category code 10 (“space”). The argument is delimited in a similar manner to the  $\text{\LaTeX} 2_{\epsilon}$  `\verb` function, or by (correctly nested) pairs of braces.

Functions containing verbatim arguments cannot appear in the arguments of other functions. The `v` argument specifier includes code to check this, and will raise an error if the grabbed argument has already been tokenized by  $\text{\TeX}$  in an irreversible way.

By default, an argument of type `v` must be at most one line. Prefixing with `+` allows line breaks within the argument.

Users should note that support for verbatim arguments is somewhat experimental. Feedback is therefore very welcome on the  $\text{\LaTeX-L}$  mailing list.

## 0.5 Default values of arguments

Uppercase argument types (`O`, `D`, ...) allow to specify a default value to be used when the argument is missing; their lower-case counterparts use the special marker `-NoValue-`. The default value can be expressed in terms of the value of any other arguments by using `#1`, `#2`, and so on.

```
\DeclareDocumentCommand {\conjugate} { m O{#1ed} O{#2} } {(#1,#2,#3)}
\conjugate {walk}           % => (walk,walked,walked)
\conjugate {find} [found]   % => (find,found,found)
\conjugate {do} [did] [done] % => (do,did,done)
```

The default values may refer to arguments that appear later in the argument specification. For instance a command could accept two optional arguments, equal by default:

```
\DeclareDocumentCommand {\margins} { O{#3} m O{#1} m } {(#1,#2,#3,#4)}
\margins {a} {b}           % => {(-NoValue-,a,-NoValue-,b)}
\margins [1cm] {a} {b}      % => {(1cm,a,1cm,b)}
\margins {a} [1cm] {b}      % => {(1cm,a,1cm,b)}
\margins [1cm] {a} [2cm] {b} % => {(1cm,a,2cm,b)}
```

Users should note that support for default arguments referring to other arguments is somewhat experimental. Feedback is therefore very welcome on the  $\text{\LaTeX-L}$  mailing list.

## 0.6 Default values for “embellishments”

The `E`-type argument allows one default value per test token. This is achieved by giving a list of defaults for each entry in the list, for example:

```
E{^_}{UP}{DOWN}
```

If the list of default values is *shorter* than the list of test tokens, the special `\NoValue` marker will be returned (as for the `e`-type argument). Thus for example

```
E{^_}{UP}
```

has default `UP` for the `^` test token, but will return the `\NoValue` marker as a default for `_`. This allows mixing of explicit defaults with testing for missing values.

## 0.7 Declaring commands and environments

With the concept of an argument specifier defined, it is now possible to describe the methods available for creating both functions and environments using `xparse`.

The interface-building commands are the preferred method for creating document-level functions in L<sup>A</sup>T<sub>E</sub>X 3. All of the functions generated in this way are naturally robust (using the L<sup>A</sup>T<sub>E</sub>X `\protected` mechanism).

---

`\DeclareDocumentCommand`  
`\NewDocumentCommand`  
`\RenewDocumentCommand`  
`\ProvideDocumentCommand`

---

`\DeclareDocumentCommand`  $\langle\textit{Function}\rangle$   $\{\langle\textit{arg spec}\rangle\}$   $\{\langle\textit{code}\rangle\}$

This family of commands are used to create a document-level  $\langle\textit{function}\rangle$ . The argument specification for the function is given by  $\langle\textit{arg spec}\rangle$ , and expanding to be replaced by the  $\langle\textit{code}\rangle$ .

As an example:

```
\DeclareDocumentCommand \chapter { s o m }
{
  \IfBooleanTF {#1}
  { \typesetstarchapter {#3} }
  { \typesetnormalchapter {#2} {#3} }
}
```

would be a way to define a `\chapter` command which would essentially behave like the current L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> command (except that it would accept an optional argument even when a `*` was parsed). The `\typesetnormalchapter` could test its first argument for being `-NoValue-` to see if an optional argument was present.

The difference between the `\Declare...`, `\New...`, `\Renew...` and `\Provide...` versions is the behaviour if  $\langle\textit{function}\rangle$  is already defined.

- `\DeclareDocumentCommand` will always create the new definition, irrespective of any existing  $\langle\textit{function}\rangle$  with the same name.
- `\NewDocumentCommand` will issue an error if  $\langle\textit{function}\rangle$  has already been defined.
- `\RenewDocumentCommand` will issue an error if  $\langle\textit{function}\rangle$  has not previously been defined.
- `\ProvideDocumentCommand` creates a new definition for  $\langle\textit{function}\rangle$  only if one has not already been given.

**T<sub>E</sub>Xhackers note:** Unlike L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>'s `\newcommand` and relatives, the `\DeclareDocumentCommand` family of functions do not prevent creation of functions with names starting `\end...`

---

`\DeclareDocumentEnvironment`  
`\NewDocumentEnvironment`  
`\RenewDocumentEnvironment`  
`\ProvideDocumentEnvironment`

---

`\DeclareDocumentEnvironment`  $\{\langle\textit{environment}\rangle\}$   $\{\langle\textit{arg spec}\rangle\}$   
 $\{\langle\textit{start code}\rangle\}$   $\{\langle\textit{end code}\rangle\}$

These commands work in the same way as `\DeclareDocumentCommand`, etc., but create environments (`\begin{ $\langle\textit{function}\rangle$ }` ... `\end{ $\langle\textit{function}\rangle$ }`). Both the  $\langle\textit{start code}\rangle$  and  $\langle\textit{end code}\rangle$  may access the arguments as defined by  $\langle\textit{arg spec}\rangle$ .

## 0.8 Testing special values

Optional arguments created using `xparse` make use of dedicated variables to return information about the nature of the argument received.

---

<code>\IfNoValueT</code>	★	<code>\IfNoValueTF {⟨argument⟩} {⟨true code⟩} {⟨false code⟩}</code>
<code>\IfNoValueF</code>	★	<code>\IfNoValueT {⟨argument⟩} {⟨true code⟩}</code>
<code>\IfNoValueTF</code>	★	<code>\IfNoValueF {⟨argument⟩} {⟨false code⟩}</code>

---

The `\IfNoValue(TF)` tests are used to check if `⟨argument⟩` (`#1`, `#2`, *etc.*) is the special `-NoValue-` marker. For example

```
\DeclareDocumentCommand \foo { o m }
{
  \IfNoValueTF {#1}
  { \DoSomethingJustWithMandatoryArgument {#2} }
  { \DoSomethingWithBothArguments {#1} {#2} }
}
```

will use a different internal function if the optional argument is given than if it is not present.

Note that three tests are available, depending on which outcome branches are required: `\IfNoValueTF`, `\IfNoValueT` and `\IfNoValueF`.

As the `\IfNoValue(TF)` tests are expandable, it is possible to test these values later, for example at the point of typesetting or in an expansion context.

It is important to note that `-NoValue-` is constructed such that it will *not* match the simple text input `-NoValue-`, *i.e.* that

```
\IfNoValueTF{-NoValue-}
```

will be logically **false**.

---

<code>\IfValueT</code>	★	<code>\IfValueTF {⟨argument⟩} {⟨true code⟩} {⟨false code⟩}</code>
<code>\IfValueF</code>	★	
<code>\IfValueTF</code>	★	

---

The reverse form of the `\IfNoValue(TF)` tests are also available as `\IfValue(TF)`. The context will determine which logical form makes the most sense for a given code scenario.

---

<code>\BooleanFalse</code>		
<code>\BooleanTrue</code>		

---

The **true** and **false** flags set when searching for an optional token (using `s` or `t⟨token⟩`) have names which are accessible outside of code blocks.

---

<code>\IfBooleanT</code>	★	<code>\IfBooleanTF {⟨argument⟩} {⟨true code⟩} {⟨false code⟩}</code>
<code>\IfBooleanF</code>	★	
<code>\IfBooleanTF</code>	★	

---

Used to test if `⟨argument⟩` (`#1`, `#2`, *etc.*) is `\BooleanTrue` or `\BooleanFalse`. For example

```
\DeclareDocumentCommand \foo { s m }
{
  \IfBooleanTF #1
  { \DoSomethingWithStar {#2} }
  { \DoSomethingWithoutStar {#2} }
}
```

checks for a star as the first argument, then chooses the action to take based on this information.

## 0.9 Argument processors

xparse introduces the idea of an argument processor, which is applied to an argument *after* it has been grabbed by the underlying system but before it is passed to  $\langle code \rangle$ . An argument processor can therefore be used to regularise input at an early stage, allowing the internal functions to be completely independent of input form. Processors are applied to user input and to default values for optional arguments, but *not* to the special `\NoValue` marker.

Each argument processor is specified by the syntax  $\langle processor \rangle$  in the argument specification. Processors are applied from right to left, so that

$\langle \backslash ProcessorB \rangle \langle \backslash ProcessorA \rangle m$

would apply `\ProcessorA` followed by `\ProcessorB` to the tokens grabbed by the `m` argument.

---

### `\ProcessedArgument`

---

xparse defines a very small set of processor functions. In the main, it is anticipated that code writers will want to create their own processors. These need to accept one argument, which is the tokens as grabbed (or as returned by a previous processor function). Processor functions should return the processed argument as the variable `\ProcessedArgument`.

---

### `\ReverseBoolean`

---

`\ReverseBoolean`

This processor reverses the logic of `\BooleanTrue` and `\BooleanFalse`, so that the example from earlier would become

```
\DeclareDocumentCommand \foo { > { \ReverseBoolean } s m }
{
  \IfBooleanTF #1
  { \DoSomethingWithoutStar {#2} }
  { \DoSomethingWithStar {#2} }
}
```

---

### `\SplitArgument`

---

Updated: 2012-02-12

`\SplitArgument { $\langle number \rangle$ } { $\langle token \rangle$ }`

This processor splits the argument given at each occurrence of the  $\langle token \rangle$  up to a maximum of  $\langle number \rangle$  tokens (thus dividing the input into  $\langle number \rangle + 1$  parts). An error is given if too many  $\langle tokens \rangle$  are present in the input. The processed input is placed inside  $\langle number \rangle + 1$  sets of braces for further use. If there are fewer than  $\{ \langle number \rangle \}$  of  $\{ \langle tokens \rangle \}$  in the argument then `\NoValue` markers are added at the end of the processed argument.

```
\DeclareDocumentCommand \foo
{ > { \SplitArgument { 2 } { ; } } m }
{ \InternalFunctionOfThreeArguments #1 }
```

Any category code 13 (active)  $\langle tokens \rangle$  will be replaced before the split takes place. Spaces are trimmed at each end of each item parsed.



---

**\SplitList**

---

**\SplitList** { $\langle token(s) \rangle$ }

This processor splits the argument given at each occurrence of the  $\langle token(s) \rangle$  where the number of items is not fixed. Each item is then wrapped in braces within #1. The result is that the processed argument can be further processed using a mapping function.

```
\DeclareDocumentCommand \foo
{ > { \SplitList { ; } } m }
{ \MappingFunction #1 }
```

If only a single  $\langle token \rangle$  is used for the split, any category code 13 (active)  $\langle token \rangle$  will be replaced before the split takes place.

---

**\ProcessList** ★

---

**\ProcessList** { $\langle list \rangle$ } { $\langle function \rangle$ }

To support **\SplitList**, the function **\ProcessList** is available to apply a  $\langle function \rangle$  to every entry in a  $\langle list \rangle$ . The  $\langle function \rangle$  should absorb one argument: the list entry. For example

```
\DeclareDocumentCommand \foo
{ > { \SplitList { ; } } m }
{ \ProcessList {#1} { \SomeDocumentFunction } }
```

**This function is experimental.**

---

**\TrimSpaces**

---

**\TrimSpaces**

Removes any leading and trailing spaces (tokens with character code 32 and category code 10) for the ends of the argument. Thus for example declaring a function

```
\DeclareDocumentCommand \foo
{ > { \TrimSpaces } m }
{ \showtokens {#1} }
```

and using it in a document as

```
\foo{ hello world }
```

will show `hello world` at the terminal, with the space at each end removed. **\TrimSpaces** will remove multiple spaces from the ends of the input in cases where these have been included such that the standard T<sub>E</sub>X conversion of multiple spaces to a single space does not apply.

**This function is experimental.**

## 0.10 Fully-expandable document commands

There are *very rare* occasion when it may be useful to create functions using a fully-expandable argument grabber. To support this, **xparse** can create expandable functions as well as the usual robust ones. This imposes a number of restrictions on the nature of the arguments accepted by a function, and the code it implements. This facility should only be used when *absolutely necessary*; if you do not understand when this might be, *do not use these functions*!

---

<code>\DeclareExpandableDocumentCommand</code>	<code>\DeclareExpandableDocumentCommand</code>
	<code>\langle function \rangle \{ \langle arg spec \rangle \} \{ \langle code \rangle \}</code>

---

This command is used to create a document-level  $\langle function \rangle$ , which will grab its arguments in a fully-expandable manner. The argument specification for the function is given by  $\langle arg spec \rangle$ , and the function will execute  $\langle code \rangle$ . In general,  $\langle code \rangle$  will also be fully expandable, although it is possible that this will not be the case (for example, a function for use in a table might expand so that `\omit` is the first non-expandable token).

Parsing arguments expandably imposes a number of restrictions on both the type of arguments that can be read and the error checking available:

- The last argument (if any are present) must be one of the mandatory types `m` or `r`.
- All arguments are either short or long: it is not possible to mix short and long argument types.
- The mandatory argument types `l` and `u` are not available.
- The optional argument types `g` and `G` are not available.
- The “verbatim” argument type `v` is not available.
- Argument processors (using `>`) are not available.
- It is not possible to differentiate between, for example `\foo[` and `\foo{[}`: in both cases the `[` will be interpreted as the start of an optional argument. As a result, checking for optional arguments is less robust than in the standard version.

`xparse` will issue an error if an argument specifier is given which does not conform to the first six requirements. The last item is an issue when the function is used, and so is beyond the scope of `xparse` itself.

## 0.11 Access to the argument specification

The argument specifications for document commands and environments are available for examination and use.

---

<code>\GetDocumentCommandArgSpec</code>	<code>\GetDocumentCommandArgSpec \langle function \rangle</code>
<code>\GetDocumentEnvironmentArgSpec</code>	<code>\GetDocumentEnvironmentArgSpec \langle environment \rangle</code>

---

These functions transfer the current argument specification for the requested  $\langle function \rangle$  or  $\langle environment \rangle$  into the token list variable `\ArgumentSpecification`. If the  $\langle function \rangle$  or  $\langle environment \rangle$  has no known argument specification then an error is issued. The assignment to `\ArgumentSpecification` is local to the current  $\text{\TeX}$  group.

---

<code>\ShowDocumentCommandArgSpec</code>	<code>\ShowDocumentCommandArgSpec \langle function \rangle</code>
<code>\ShowDocumentEnvironmentArgSpec</code>	<code>\ShowDocumentEnvironmentArgSpec \langle environment \rangle</code>

---

These functions show the current argument specification for the requested  $\langle function \rangle$  or  $\langle environment \rangle$  at the terminal. If the  $\langle function \rangle$  or  $\langle environment \rangle$  has no known argument specification then an error is issued.

## 1 Load-time options

`log-declarations` The package recognises the load-time option `log-declarations`, which is a key-value

option taking the value `true` and `false`. By default, the option is set to `true`, meaning that each command or environment declared is logged. By loading `xparse` using

```
\usepackage[log-declarations=false]{xparse}
```

this may be suppressed and no information messages are produced.

## Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols		N	
<code>\</code>	4	<code>\New...</code>	6
<b>A</b>		<code>\newcommand</code>	1, 4, 6
<code>\ArgumentSpecification</code>	10, 10	<code>\NewDocumentCommand</code>	1, 6, 6
<b>B</b>		<code>\NewDocumentEnvironment</code>	1, 6
<code>\begin</code>	6	<code>\NoValue</code>	5, 5, 8, 8
<code>\BooleanFalse</code>	3, 3, 7, 7, 8	<b>O</b>	
<code>\BooleanTrue</code>	3, 3, 7, 7, 8	<code>\omit</code>	10
<b>C</b>		options:	
<code>\chapter</code>	6	<code>log-declarations</code>	10
<b>D</b>		<b>P</b>	
<code>\Declare...</code>	6	<code>\ProcessedArgument</code>	8, 8
<code>\DeclareDocumentCommand</code>	1, 6, 6, 6, 6, 6	<code>\ProcessList</code>	9, 9, 9
<code>\DeclareDocumentEnvironment</code>	1, 6, 6	<code>\ProcessorA</code>	8
<code>\DeclareExpandableDocumentCommand</code>	1, 10, 10	<code>\ProcessorB</code>	8
<b>E</b>		<code>\protected</code>	6
<code>\end</code>	6	<code>\Provide...</code>	6
<code>\end...</code>	6	<code>\ProvideDocumentCommand</code>	1, 6, 6
<b>G</b>		<code>\ProvideDocumentEnvironment</code>	1, 6
<code>\GetDocumentCommandArgSpec</code>	10, 10	<b>R</b>	
<code>\GetDocumentEnvironmentArgSpec</code>	10, 10	<code>\Renew...</code>	6
<b>I</b>		<code>\RenewDocumentCommand</code>	1, 6, 6
<code>\IfBoolean(TF)</code>	1	<code>\RenewDocumentEnvironment</code>	1, 6
<code>\IfBooleanTF</code>	7, 7	<code>\ReverseBoolean</code>	8, 8
<code>\IfNoValue(TF)</code>	1, 7, 7, 7	<b>S</b>	
<code>\IfNoValueTF</code>	7, 7, 7, 7, 7, 7, 7	<code>\ShowDocumentCommandArgSpec</code>	10, 10
<code>\IfValue(TF)</code>	7	<code>\ShowDocumentEnvironmentArgSpec</code>	10, 10
<code>\IfValueTF</code>	7, 7	<code>\SplitArgument</code>	8, 8
<b>L</b>		<code>\SplitList</code>	9, 9, 9
<code>log-declarations (option)</code>	10	<b>T</b>	
<code>\long</code>	4	<code>\TrimSpaces</code>	9, 9, 9
		<code>\typesetnormalchapter</code>	6
		<b>V</b>	
		<code>\verb</code>	2, 5