

The `lastpage` package

H.-Martin Münch

`<Martin.Muench at Uni-Bonn.de>`

invented by Jeffrey P. Goldberg

`<jeffrey+news at goldmark.org>`

2011/08/08 v1.2i

Abstract

This L^AT_EX package puts the label `LastPage` (`\AtEndDocument`) into the `.aux` file, allowing the user to refer to the last page of a document. This might be particularly useful in places like headers or footers. –

When more than one page numbering scheme is used, or the `fnsymbol` page numbering scheme is used, or another package has output after this package, or the number of pages instead of the last page's name is needed, or the page numbers exceed a certain range, there might be problems, which can be solved by using the `pageslts` package instead.

Disclaimer for web links: The author is not responsible for any contents referred to in this work unless he has full knowledge of illegal contents. If any damage occurs by the use of information presented there, only the author of the respective pages might be liable, not the one who has referred to these pages.

Save per page about 200 ml water, 2 g CO₂ and 2 g wood:
Therefore please print only if this is really necessary.

Contents

1	Introduction	3
2	Usage	3
3	A lot of WARNINGS	4
3.1	<code>\AtEndDocument</code>	4
3.2	Interaction with very old versions of the <code>endfloat</code> package	4
3.3	Page name instead of page number	4
3.4	Wrong last page number with more than one page numbering scheme	5
3.5	<code>\addtocounter{page}{...}</code> and <code>\setcounter{page}{...}</code>	5
3.6	Page number reset by <code>\pagenumbering{...}</code>	5
3.7	Last pages of different page numbering schemes	5
3.8	Current page	5
3.9	First page	5
3.10	Using the <code>fnsymbol</code> page numbering scheme	6
3.11	Page counter overflow	6
3.12	Other packages manipulating <code>\lastpage@putlabel</code>	6
4	Alternatives	7
5	Example	10
6	The implementation	12
7	Installation	17
7.1	Downloads	17
7.2	Package, unpacking TDS	19
7.3	Refresh file name databases	20
7.4	Some details for the interested	20
7.5	Compiling the example	20
8	Acknowledgements	20
9	History	21
	[1994/06/17 v0.99a]	21
	[1994/06/25 v0.1b]	21
	[1994/07/20 v0.1b (again)]	21
	[2010/02/18 v1.1]	21
	[2010/07/29 v1.2a]	21
	[2010/08/12 v1.2b]	22
	[2010/08/23 v1.2c]	22
	[2010/08/25 v1.2d]	22
	[2010/09/12 v1.2e]	22
	[2010/09/24 v1.2f]	23
	[2011/02/01 v1.2g]	23
	[2011/07/03 v1.2h]	23
	[2011/08/08 v1.2i]	23
10	Index	24

1 Introduction

This L^AT_EX package puts the label `LastPage` (`\AtEndDocument`) into the aux file, allowing the user to refer to the last page of a document via `\pageref{LastPage}`. This might be particularly useful in places like headers or footers.

This package was invented by **Jeffrey P. Goldberg**, and is now maintained by H.-MARTIN MÜNCH. A big “Thank you!” to JEFFREY P. GOLDBERG for granting this.

If you are more ambitious in respect to your aims with this package, you might want to have a look at the `pageslts` package (see section 4: Alternatives).

2 Usage

Just load the package placing

```
\usepackage{lastpage}
```

in the preamble of your L^AT_EX 2_ε source file or

```
\usepackage{lastpage209}
```

in the preamble of your L^AT_EX 2.09 source file.

For example for various draft forms it is desirable to have a page reference to the last page, so that e.g. page footers can contain something like “page *N* of *K*”, where *N* is the current page and *K* is the last page. Once the package is loaded, anywhere in the text references can be made to the label `LastPage`. In particular one can use the `fancyhdr` or `nccfancyhdr` package, or redefinitions of the page headings and footings to get a reference to the last page.

In your document the code

```
\makeatletter
\renewcommand{\@evenfoot}{%
  \normalsize\slshape DRAFT \today\hfil \upshape %
  page {\thepage} of \pageref{LastPage}}
\renewcommand{\@oddfoot}{\@evenfoot}
\makeatother
```

creates footers like

“DRAFT August 8, 2011 page 7 of 9”

in the compiled document (cf. the `lastpage-example` file).

If the `hyperref` package is used, the references are hyperlinked to their aims. If these hyperlinks shall be suppressed, `\pageref*{...}` instead of `\pageref{...}` can be used.

The `lastpage` package does not provide the words “page” or “of”, but e.g. the `handout` class uses “of” in the definition of the footer. (In the `lastpage-example` also `\@evenfoot` is redefined, but it is not the `lastpage` package redefining this.) If you want to change “page” or “of” (e.g. to another language), you therefore have got to look in the used class/package(s)/preamble instead of in the `lastpage` package.

3 A lot of WARNINGS

(Short: try using the `pageslts` package instead, if you have room for some more `\counters`.¹)

3.1 `\AtEndDocument`

The output of a $\text{\LaTeX} 2_{\epsilon}$ run is not independent of the order in which the packages are loaded. It is often the case that the same formats for which one must put tables and figure at the end, are the ones in which endnotes are also required. If one wants to use `\AtEndDocument` here as well (as done for `\pageref{LastPage}`), then it is easy to get to three separate uses of `\AtEndDocument` (assuming one uses this for the endnotes as well). Clearly it is not safe for any package writer or user to assume that no material will follow what they put into `\AtEndDocument`. Therefore a message, which begins with `AED`, is included in every usage of `\AtEndDocument`. –

(The `pageslts` package solves this problem by using `\AfterLastShipout` from HEIKO OBERDIEK’s `atveryend` package for the references `\lastpageref{VeryLastPage}` and `\lastpageref{LastPages}`.)

3.2 Interaction with very old versions of the `endfloat` package

The very old version 2.0 (and earlier) of the `endfloat` package actually redefined the `\enddocument` command, and so interfered drastically with the $\text{\LaTeX} 2_{\epsilon}$ commands which make use of `\AtEndDocument`. Newer versions of `endfloat` exists (at the time of writing this documentation: v2.4i as of 1995/10/11) in modern documentation form, which should be available from the same source where you received this file, see subsection 7.1.

A note is placed in the style file. If you want your `LastPage` to label the last page of these end floats, you need to load `lastpage` after loading `endfloat` (or use `VeryLastPage` from the `pageslts` package instead). If, on the other hand, you want `LastPage` to refer to the (not so) last page, exclusive of the the floats at the end, then load in the reverse order. Independent from the order of `lastpage` and `endfloat`, you will still need the modified² version of `endfloat`.

Other $\text{\LaTeX} 2.09$ (!) packages also seem to like to redefine `\enddocument`. In addition to the old `endfloat`, `harvard` comes to mind. All of these will need to be modified swiftly. **If possible, update to $\text{\LaTeX} 2_{\epsilon}$!**

3.3 Page name instead of page number

When any page numbering scheme other than `arabic` is used at the page, which `\pageref{LastPage}` refers to, the *name* and not the *number* of the page is given. For example, `Alph` page numbering scheme and 10 pages will give `J` instead of 10, `Roman` page numbering scheme and 10 pages will give `X` instead of 10, and so on.

(The `pageslts` package puts `\lastpageref{LastPages}` (with `s` at the end) at your disposal for remediation.)

¹To determine the number of used and available counters and other registers, the `regstats` package might be helpful.

²The “new” version is over 15 years old, so it might be time to update to this version, if you did not do it already.

3.4 Wrong last page number with more than one page numbering scheme

When more than one page numbering scheme is used, `LastPage` does not give the total **number** of pages (even if `arabic` is the page numbering scheme of that page). For example, for a document with VI+36 pages, it gives “36” as reference to the last page. While this is correct, the total number of pages is 42.

(The `pageslts` package puts `\lastpageref{LastPages}` (with `s` at the end) at your disposal for remediation.)

3.5 `\addtocounter{page}{...}` and `\setcounter{page}{...}`

When the page number was manipulated by `\addtocounter{page}{...}` or `\setcounter{page}{...}`, `LastPage` does not give the total **number** of pages (even if `arabic` is the page numbering scheme of that page).

(The `pageslts` package puts `\lastpageref{LastPages}` (with `s` at the end) at your disposal for remediation: `LastPages` ignores page number manipulation.)

3.6 Page number reset by `\pagenumbering{...}`

At a page numbering change the page number is reset to one. Therefore `LastPage` does not give the total **number** of pages (even if `arabic` is the page numbering scheme of that page). Furthermore, now two pages have the same name.

(The `pageslts` package does not only put `\lastpageref{LastPages}` (with `s` at the end) at your disposal for remediation: `LastPages` also ignores page number manipulation. It furthermore offers the option `pagecontinue` to continue the page numbering, when `\pagenumbering{...}` is used.)

3.7 Last pages of different page numbering schemes

`\pageref{LastPage}` refers to the (maybe not so) last page of the last page numbering scheme. References to the respective last page of the other page numbering schemes are not provided.

(The `pageslts` package does this with labels `pagesLTS.<numbering scheme>`, where `<numbering scheme>` is e.g. `arabic`, `roman`, `Roman`, `alph`, or `Alph`. For `fnsymbol` please use `\lastpageref{pagesLTS.fnsymbol}` instead of `\pageref{pagesLTS.fnsymbol}`.)

3.8 Current page

The command `\thepage` gives the **name** of the current page in the current page numbering scheme, which is different from the current total/absolute page number e.g. with a second page numbering scheme, `\addtocounter{page}{...}`, or `\setcounter{page}{...}`, and it will not be an arabic number at all, if the current page numbering scheme is not arabic.

(The `pageslts` package provides the command `\theCurrentPage` and for the current number of pages in the current page numbering scheme `\theCurrentPageLocal`.)

3.9 First page

There is no special label at the first page. (This is the `lastpage` package, after all.)

(The `pageslts` package creates a label `pagesLTS.0` at the first page of the document.)

3.10 Using the `fnsymbol` page numbering scheme

Using the `fnsymbol` page numbering scheme can result in problems! When the page, where `\pageref{lastpage}` points at, is in `fnsymbol` page numbering scheme, this package might skew up – and quite totally for that, especially when used together with old versions of the `hyperref` package (e.g. `hyperref` v6.80x as of 2010/04/17). When testing with version v6.82g as of 2011/04/17, the hyperlink did not aim at the last page, but at least the given name of the last page was right.

(The `pageslts` package with `\lastpageref{lastpage}` and appropriate package options should cope even with this case.)

3.11 Page counter overflow

“The ranges of supported counter values are more or less restricted. Only `\arabic` can be used with any counter value \TeX supports.

Presentation command	Supported domain	Ignored values	Error message ‘Counter too large’
<code>\arabic</code>	<code>-MAX..MAX</code>		
<code>\roman</code> , <code>\Roman</code>	<code>1..MAX</code>	<code>-MAX..0</code>	
<code>\alph</code> , <code>\Alph</code>	<code>1..26</code>	0	<code>-MAX..-1</code> , <code>27..MAX</code>
<code>\fnsymbol</code>	<code>1..9</code>	0	<code>-MAX..-1</code> , <code>10..MAX</code>

`MAX = 2147483647`

” (HEIKO OBERDIEK: The `alphalph` package, 2010/04/18, v2.3, first table, p. 2).

When *any* page is out of that range, there will be a counter overflow.

(`lastpage` probably is not the right package to be asked to correct this anyway, but the `pageslts` package (with appropriate options) can do this.)

3.12 Other packages manipulating `\lastpage@putlabel`

The `hyperref` package redefines the `\lastpage@putlabel` command, and the `revtex4` class redefines the `\lastpage@putlabel` command, and the `hyperref` package redefines the `\lastpage@putlabel` command, if the `revtex4` class is used, and the `pageslts` “kills” the `\lastpage@putlabel` command, because that package uses more advanced labels.

In my humble opinion it would be preferably if one package (the original one, i.e. `lastpage`) would do the job right, all others packages would check for the version of that package, and if an old version is found, an error (or at least a warning) message about the use of an outdated package is given, and *then* as “last aid” the command of the outdated package is redefined.

Therefore here none of the definitions or commands of the other packages is altered, but `\lastpage@putlabel` was replaced by `\lastpage@putlabel`. Because `\lastpage@putlabel` is no longer called, now there should not be any double definitions of the `lastpage` label.

4 Alternatives

There are similar packages, which do (or do not) similar things (or even more). As I neither know what exactly you want to accomplish when using this package (e. g. page number vs. page name, hyperlinks or not), nor what resources you have (e. g. ε -TeX), here is a list of some possible alternatives:

`lastpage209.sty`

- If L^AT_EX 2.09 is still used, and if you are unable to switch to L^AT_EX 2_ε, the L^AT_EX 2.09 compatible `lastpage209.sty` can be used, which is defined as follows:

(It is also generated automatically from `lastpage.dtx` when compiling it.)

```

1      \(*lastpage209)
2      % FOR LaTeX 2.09 ONLY - FOR LaTeX 2e USE lastpage.sty OR pageslts.sty!
3      % This is lastpage209.sty invented by Jeffrey P. Goldberg
4      % (jeffrey+news at goldmark dot org), maintained by
5      % H.-Martin M{"u}ench (Martin dot Muench at Uni-Bonn dot de).
6      \let\origenddocument=\enddocument%
7      \def\enddocument{\clearpage%
8          {\addtocounter{page}{-1}%
9              \immediate\write\@mainaux{\string\newlabel{LastPage}{\the page}}}%
10         \addtocounter{page}{+1}%
11         \origenddocument%
12     }%
13 \(*lastpage209)

```

(after PIET VAN OOSTRUM: Page layout in L^AT_EX, March 2, 2004, section 16; fancyhdr.pdf). Because `\enddocument` is redefined, similar problems as with the old version of the endfloat package (see subsection 3.2) will arise.

If possible, update to L^AT_EX 2_ε (and maybe to the `pageslts` package)!

`pageslts`

- The `pageslts` package first started as a revision of this `lastpage` package, but it became obvious that a replacement was needed to accomplish what the `pageslts` package does. For backward compatibility, a label named `LastPage` is provided. Thus `\usepackage{lastpage}` can be replaced by `\usepackage[pagecontinue=false,alphMult=0,AlphMulti=0,fnSymbolmult=false,romanMult=false,RomanMulti=false]{pageslts}`, if the behaviour of the `lastpage` package should be simulated. The default options are `\usepackage[pagecontinue=true,alphMult=ab,AlphMulti=AB,fnSymbolmult=true,romanMult=true,RomanMulti=true]{pageslts}`. Benefits of `pageslts` package (with appropriate options) are:

- + Labels `LastPage` (`\AtEndDocument`) and `VeryLastPage` (`\AfterLastShipout`), allowing the user to refer to the (very) last page of a document.
- + For example, when more than one page numbering scheme is used, the label `LastPages` gives the total *number* of pages.
- + At the last page of each page numbering scheme a label `pagesLTS.<numbering scheme>` is placed, where `<numbering scheme>` is e. g. `arabic`, `roman`, `Roman`, `alph`, or `Alph`. For `fnSymbol` please use `\lastpageref{pagesLTS.fnSymbol}` instead of `\pageref{pagesLTS.fnSymbol}`.

- + When the same numbering scheme is used twice, the page numbers are either reset to one or continued automatically, depending on the option given when the package is called.
- + The command `\theCurrentPage` prints the current total/absolute page number – in contrast to `\thepage`, which gives only the page *name* in the current page numbering scheme. `\theCurrentPageLocal` gives the current number of pages in the current page numbering scheme. `\thepage` and `\theCurrentPageLocal` are different e.g. when `\addtocounter{page}{...}` or `\setcounter{page}{...}` were used.
- + At the first page of the document a label `pagesLTS.0` is created.
- + The `alphalph` package is supported, i.e. page numbers `alph` or `Alph` > 26 and `fnyambol` > 9 can be used (with according options set). Even zero and negative page numbers can be used with `arabic`, `alph`, `Alph`, `roman`, `Roman`, and `fnsymbol` page numbering (with `alphalph` package and according options).
- + It is checked whether a (very) old `endfloat` package is in use. If it is, a warning or even an error message is given, depending on `endfloat` version.
- + A rerun warning is given, when labels have changed.

Further labels are provided for special cases.

`totpages`

- The `totpages` package provides a `totpages` label similar to `LastPages` `\AtEndDocument` (instead of `\AfterLastShipout`, as done by `pageslts`). The `totpages` package additionally computes the number of paper sheets needed to (double) print the document (with one, two, three, ... pages on one sheet of paper) (which can be achieved also with the `papermas` package, an extension of the `pageslts` package, which further allows to compute the mass of that printed version of the document, useful e.g. when sending it by mail to determine the postage).

`nofm.sty`

- “There is a package `nofm.sty` available, but some versions of it are defective, and most don’t work with `fancyhdr` because they take over the complete page layout.” (PIET VAN OOSTRUM: Page layout in \LaTeX , March 2, 2004, section 16; `fancyhdr.pdf`)
`nofm` as of 1991/02/25 (without version number), available at <ftp://tug.ctan.org/pub/tex-archive/obsolete/macros/latex209/contrib/misc/nofm.sty>,
does not work with e.g. `hyperref`, redefines `\enddocument` as well as `\@oddhead`, `\@evenhead`, `\@oddfoot`, and `\@evenfoot`.
If you know the (CTAN:) location of a **working** (!) version, please send an e-mail to the `lastpage` maintainer, thanks!

`count1to`

- You may want to have a look at the `count1to` package.

`zref`

- The `zref` package of HEIKO OBERDIEK requires $\varepsilon\text{-}\text{\TeX}$. `lastpage` does not require $\varepsilon\text{-}\text{\TeX}$, but if you already have $\varepsilon\text{-}\text{\TeX}$, you may have a look at the extensive `zref` package, whether it suits your needs better (or additionally or whatsoever).

(You programmed or found another alternative, which is available at [CTAN](#)?
OK, send an e-mail to me with the name, location at [CTAN](#):, and a short notice,
and I will probably include it in the list above.)

About how to get those packages, please see subsection [7.1](#).

5 Example

```
14 (*example)
15 \documentclass[british]{article}
16 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
17 \AtEndDocument{\message{^^JLaTeX Info: Executing hook 'AtEndDocument'.}}
18 \usepackage[draft]{showkeys}[2007/08/07]% v3.15
19 %%      Use final instead of draft to hide the keys. %%
20 \usepackage{hyperref}[2011/04/17]% v6.82g
21 \hypersetup{%
22   extension=pdf,%
23   plainpages=false,%
24   pdfpagelabels=true,%
25   hyperindex=false,%
26   pdflang={en},%
27   pdftitle={lastpage package example},%
28   pdfauthor={Hans-Martin Muench},%
29   pdfsubject={Example for the lastpage package},%
30   pdfkeywords={LaTeX, lastpage, Hans-Martin Muench},%
31   pdfview=Fit,%
32   pdfstartview=Fit,%
33   pdfpagelayout=SinglePage%
34 }
35 \usepackage{lastpage}[2011/08/08]% v1.2i
36 \makeatletter
37 \renewcommand{\@evenfoot}{%
38   \normalsize\slshape \today\hfil \upshape page \thepage%
39   \ of \pageref{LastPage}}
40 \renewcommand{\@oddfoot}{\@evenfoot}
41 \makeatother
42 \gdef\unit#1{\mathord{\thinspace\mathrm{#1}}}%
43 \listfiles
44 \begin{document}
45 \pagenumbering{Roman}
46
47 \section*{Example for lastpage}
48 \markboth{Example for lastpage}{Example for lastpage}
49
50 This example demonstrates the use of package\newline
51 \textsf{lastpage}, v1.2i as of 2011/08/08 (HMM; JPG).\newline
52 The package takes no options.\newline
53 For more details please see the documentation!\newline
54
55 \noindent \label{keys} To hide the \pageref{keys}{\quad } use option
56 \texttt{final} instead of \texttt{draft} with the \textsf{showkeys}
57 package (or remove the package call from the preamble of
58 this document).\newline
59
60 \textbf{Hyperlinks or not:} If the \textsf{hyperref} package is loaded,
61 the references are also hyperlinked:\newline
62 \smallskip
63 Last page's name (LastPage): \pageref{LastPage}\newline
64 \noindent If the \textsf{hyperref} package is loaded, but the hyperlinks
65 of the references shall be suppressed, \verb|\pageref*{...}|
66 can be used:\newline
67 \smallskip
68 Last page's name (LastPage): \pageref*{LastPage}\newline
69
```

```

70 \textbf{Trademarks} appear throughout this example without any
71 trademark symbol; they are the property of their respective
72 trademark owner. There is no intention of infringement; the
73 usage is to the benefit of the trademark owner.\newline
74
75 \textbf{Tip}: Use \textit{logical page numbers} for
76 the display of the pdf!\newline
77 (In Adobe Reader X (10.1.0): \underline{E}dit $>$
78 Prefere\underline{n}ces (Ctrl+k) $>$ Page Display $>$
79 Page Content and Information $>$ Use logical page
80 \nolinebreak{\underline{n}umbers.})\newline
81
82 If you are more ambitouse in respect to your aims with this package,
83 you might want to have a look at the \textsf{pageslts} package\newline
84 \makeatletter
85 \ifundefined{Hy@Warning}{% hyperref not loaded
86     \verb|http://www.ctan.org/tex-archive/macros/latex/contrib/pageslts/|.
87 }{% hyperref loaded
88     \href{http://www.ctan.org/tex-archive/macros/latex/contrib/pageslts/}{%
89     CTAN:/macros/latex/contrib/pageslts/}).
90 }%
91 \makeatother
92
93 \bigskip
94
95 Save per page about $200\unit{ml}$~water, $2\unit{g}$~CO$_{2}$
96 and $2\unit{g}$~wood:\newline
97 Therefore please print only if this is really necessary.\newline
98 I do NOT think, that it is necessary to print THIS file, really\newline
99 (at least not after this page)!
100
101 \bigskip
102
103 \noindent The page (\verb|\thepage|): \thepage \newline
104
105 \noindent Last page's name (LastPage): \pageref{LastPage}
106
107 \newpage
108
109 \noindent The page (\verb|\thepage|): \thepage \newline
110
111 \noindent Last page's name (LastPage): \pageref{LastPage}
112
113 \newpage
114
115 \noindent The page (\verb|\thepage|): \thepage \newline
116
117 \noindent Last page's name (LastPage): \pageref{LastPage}
118
119 \newpage
120
121 \section*{The End}
122
123 \noindent The page (\verb|\thepage|): \thepage \newline
124
125 \noindent Last page's name (LastPage): \pageref{LastPage}
126 \end{document}
127 \end{example}

```

6 The implementation

We start off by checking that we are loading into L^AT_EX 2_ε and announcing the name and version of this package.

```
128 (*package)
129 \NeedsTeXFormat{LaTeX2e}[2009/09/24]
130 \ProvidesPackage{lastpage}[2011/08/08 v1.2i
131           Refers to last page's name (HMM; JPG)]%
132
```

A short description of the lastpage package:

```
133 %% Allows for things like
134 %% Page \thepage\ of \pageref{LastPage}
135 %% to get
136 %% 'Page 7 of 9'.
```

A last information for the user(s):

```
137 %% For LaTeX 2.09 use lastpage209.sty.
138 %% For LaTeX 2e maybe consider upgrading to the pageslts package.
139 %% lastpage may work with earlier versions of LaTeX2e,
140 %% but this was not tested. Please consider updating your LaTeX
141 %% contribution to the most recent version (if it is not already
142 %% the most recent version).
143
```

The very old version 2.0 (and earlier) of the endfloat package actually redefined the `\enddocument` command, and so interfered drastically with the L^AT_EX 2_ε commands which make use of `\AtEndDocument`. Newer versions of endfloat exists (at the time of writing this documentation: v2.4i as of 1995/10/11) in modern documentation form, which are available from [CTAN](#): (see subsection 7.1). A note is placed here. (The pageslts package even checks whether a (very) old endfloat package is in use. If it is, a warning or even an error message is given, depending on endfloat version.)

```
144 %% The recent version of the endfloat package is v2.4i as of 1995/10/11.
145 %% The lastpage package is not fully compatible with version 2.0
146 %% (and earlier) of the endfloat package, because those versions
147 %% redefined the \enddocument command.
148
```

There are no options to be introduced.

For comparisons, “one” is defined (`\@one` does not work for this).

```
149 \def\lastpage@one{1}
```

We define `\lastpage@hyper` and `\lastpage@LTS` to be “0”.

```
150 \gdef\lastpage@hyper{0}
151 \gdef\lastpage@LTS{0}
```

We define `\lastpage@firstpage` to be “1”.

```
152 \def\lastpage@firstpage{1}
153
```

```

\AtBeginDocument \AtBeginDocument it is checked whether the hyperref package is loaded.
(\@ifpackageloaded cannot be used later than \AtBeginDocument.)
If this is the case, \lastpage@hyper is defined as 1 (otherwise it stays 0).

154 \AtBeginDocument{%
155   \@ifpackageloaded{hyperref}{\gdef\lastpage@hyper{1}}{}%
156   \@ifpackageloaded{pageslts}{%
157     \PackageWarning{lastpage}{Package pageslts found.\MessageBreak%
158       Therefore the lastpage package is no longer\MessageBreak%
159       necessary.%
160     }%
161     \gdef\lastpage@LTS{1}%
162   }\PackageInfo{lastpage}{%
163     Please have a look at the pageslts package at\MessageBreak%
164     http://www.ctan.org/tex-archive/ \MessageBreak%
165     macros/latex/contrib/pageslts/ \MessageBreak%
166     or\MessageBreak%
167     http://www.ctan.org/tex-archive/ \MessageBreak%
168     install/macros/latex/contrib/pageslts.tds.zip\MessageBreak%
169     !}%
170   }%
171   \@ifpackageloaded{pagesLTS}{%
172     \PackageWarning{lastpage}{%
173       Outdated pagesLTS package found.\MessageBreak%
174       Please replace by a recent version of\MessageBreak%
175       pageslts package, see e.g. at\MessageBreak%
176       http://www.ctan.org/tex-archive/ \MessageBreak%
177       macros/latex/contrib/pageslts/ \MessageBreak%
178       or\MessageBreak%
179       http://www.ctan.org/tex-archive/ \MessageBreak%
180       install/macros/latex/contrib/pageslts.tds.zip\MessageBreak%
181       !\MessageBreak%
182       With pagesLTS as well as pageslts package\MessageBreak%
183       the lastpage package is no longer necessary.\MessageBreak%
184     }%
185     \gdef\lastpage@LTS{1}%
186   }{}%

```

\lastpage@putlabel, used by older versions of this package, is redefined e. g. by revtex and hyperref. While now \lastpage@putlabel is used instead, revtex or hyperref could also define a label LastPage, which then would be multiply defined. (Which is no big issue, if it is associated with the same page.) Therefore we define

```

187 \gdef\lastpage@putlabel{\relax}%

```

Because \lastpage@putlabel might be (re)defined later, depending on the order in which the packages are loaded, we will do this again \AtEndDocument.

```

188 }
189

```

`\lastpage@putl@bel` This command does the writing of the label:

```

190 \newcommand{\lastpage@putl@bel}{%
    \AtBeginDocument it is checked whether the hyperref package is loaded,
    \@ifpackageloaded{hyperref}{\gdef\lastpage@hyper{1}}{ }.
    \@ifpackageloaded cannot be used later than \AtBeginDocument.
    User SEBASTIAN BANK found and reported (Thanks!) a case, when this check is
    not sufficient. Using a class with
    \usepackage{lastpage}
    \AtBeginDocument{\usepackage{hyperref}}
    leads to failed detection of the hyperref package, because \AtBeginDocument first
    the check for hyperref is performed, and then hyperref is loaded. As mentioned
    above, \@ifpackageloaded cannot be used later, so here we do not check for
    the hyperref package again, but for its \Hy@Warning command. In version 1.2c
    of the lastpage package, it was checked for the \hyperref command, but as it
    turned out, tclatex is defining that. If some other package or user is defining
    \Hy@Warning, lastpage will falsely assume, that hyperref has been loaded, but in
    my humble opinion, defining \Hy@Warning does not make sense and is bad style
    (except definition by the hyperref package itself, of course).

191 \ifundefined{Hy@Warning}{% hyperref not loaded
192 }{\gdef\lastpage@hyper{1}% hyperref loaded
193 }%

```

If the `pageslts` package is used, this `lastpage` package is not needed at all. The `LastPage` label would even be defined twice. Thus, if `pageslts` is used, here nothing is done:

```

194 \ifx\lastpage@LTS\lastpage@one%
195 \else%

```

Otherwise the label is set:

We have got to distinguish whether `hyperref` has been loaded or not:

```

196 \ifx\lastpage@hyper\lastpage@one%
197 \lastpage@putlabelhyper%
198 \else%

```

When `hyperref` has not been loaded, we just write the simple label into the `aux` file:

```

199 \begingroup
200 \addtocounter{page}{-1}%
201 \immediate\write\@auxout{\string\newlabel{LastPage}{\thepage}}%
202 \addtocounter{page}{+1}%
203 \endgroup
204 \fi%
205 \fi%
206 }
207

```

`\lastpage@putlabelhyper` When `hyperref` has been loaded, the label is set with the `\lastpage@putlabelhyper` command. If the `hyperref` package is used, but `pageanchors` are disabled, the hyperlinking will not work.

```

208 \newcommand{\lastpage@putlabelhyper}{%
209 \ifHy@pageanchor%
210 \else%
211 \PackageError{lastpage}{hyperref option pageanchor disabled}{%
212 The \string\pageref{LastPage} link doesn't work\MessageBreak%
213 using hyperref with disabled option 'pageanchor'.\MessageBreak%

```

```

214 }%
215 \fi%

```

Since the page has been put out, we are on the page *after* that page. We therefore subtract one from the page counter. (For the compiler, this is equal to `\advance\c@page\m@ne`, but for human readers of the code it is probably easier to understand.)

```

216 \begingroup%
217 \addtocounter{page}{-1}%

```

Simply using `\label` for `LastPage` would not work, because labels wait for the output routines to work, and there may be no more invocations of the output routines. To force the write out, we need to do an `\immediate` write into the `aux` file.

```

218 %% The following code is from the hyperref package      %%
219 %% [2010/04/17 v6.80x; newer versions are available]    %%
220 %% by Heiko Oberdiek (Big Thanks!).                    %%
221 \let\@number\@firstofone
222 \ifHy@pageanchor
223 \ifHy@hypertextnames
224 \ifHy@plainpages
225 \def\Hy@temp{\arabic{page}}%
226 \else
227 \Hy@unicodedefalse
228 %% Code not from hyperref package:                      %%
229 %% The following lines are taken from the pageslts package, %%
230 %% which in turn got them from the hyperref package and  %%
231 %% modified them.                                         %%
232 %% Without the modification, after the first shipout "PD1" %%
233 %% is inserted each time |\pdfstringdef\Hy@temp{\thepage}| %%
234 %% is executed.                                           %%
235 \ifnum \value{page}=1%

```

We do not count the pages ourselves, and so they could have been changed by e.g. `\pagenumbering{...}`, `\addtocounter{page}{...}`, `\setcounter{page}{...}`. Thus the page might have the number one while not being the first page at all. Using the `everyshi` package would help, but this package should not require other packages. The `pageslts` package does a better handling, but requires some other packages.

We will make a mistake here at most once:

```

236 \ifx \lastpage@firstpage\lastpage@one
237 \def\Hy@temp{\thepage}%
238 \gdef\lastpage@firstpage{0}%
239 \else%
240 %% Code from hyperref package again:                    %%
241 \pdfstringdef\Hy@temp{\thepage}%
242 %% End of code from the hyperref package.              %%
243 \fi%
244 %% The pageslts package would even check for fnsymbol page %%
245 %% numbering scheme and adapt the code correspondingly.  %%
246 \else%
247 %% Code from hyperref package again:                    %%
248 \pdfstringdef\Hy@temp{\thepage}%
249 %% Code from pageslts package again:                    %%
250 \fi%
251 %% Code from hyperref package again:                    %%
252 \fi

```

```

253     \else
254     \def\Hy@temp{\the\Hy@pagecounter}%
255     \fi
256 \fi
257 \immediate\write\@auxout{%
258     \string\newlabel
259     {LastPage}{\the\thepage}{\the\Hy@temp}{\the\Hy@temp}{\the\Hy@temp}{\the\Hy@temp}%
260     \ifHy@pageanchor page.\Hy@temp\fi}{\the\Hy@temp}%
261 }%
262 %% End of code from the hyperref package.

```

After the writeout we restore the page number again, since there might be other things still to be done.

```

263     \addtocounter{page}{+1}%
264 \endgroup
265 }
266

```

`\AtEndDocument` `\AtEndDocument` we again (re)define `\lastpage@putlabel` to do nothing.

```

267 \AtEndDocument{%
268     \gdef\lastpage@putlabel{\relax}

```

It is checked whether writing to files is allowed (otherwise, only an error message is issued and nothing is done).

```

269     \if@files%

```

We put in a `\message` to show, in what order things (which were called) are done (see subsection 3.1).

```

270     \message{^^JAED: lastpage setting LastPage^^J}%

```

After this we issue a `\clearpage` to put out all floats, which are still floatig, and place the `LastPage` label.

```

271     \clearpage\lastpage@putlabel%

```

When writing to files is not allowed, only an error message is issued and nothing is done.

```

272 \else%
273     \PackageError{lastpage}{No auxiliary file allowed}%
274     {The lastpage package was not allowed to write to an .aux file.\MessageBreak%
275     This package does not work without access to an .aux file.\MessageBreak%
276     Press Ctrl+Z to exit.\MessageBreak%
277 }%
278 \fi%
279 }
280 \endpackage

```


7 Installation

First, please make sure that there is no old version of **lastpage** at some obsolete place in your system!

7.1 Downloads

Everything is available at CTAN: <http://www.ctan.org/tex-archive/>, but may need additional packages themselves.

`lastpage.dtx` For unpacking the `lastpage.dtx` file and constructing the documentation it is required:

- T_EXFormat L^AT_EX 2_ε: <http://www.CTAN.org/>
- document class `ltxdoc`, 2007/11/11, v2.0u,
[CTAN:macros/latex/base/ltxdoc.dtx](http://www.ctan.org/macros/latex/base/ltxdoc.dtx)
- package `holtxdoc`, 2011/02/04, v0.21,
[CTAN:macros/latex/contrib/oberdiek/holtxdoc.dtx](http://www.ctan.org/macros/latex/contrib/oberdiek/holtxdoc.dtx)
- package `hypdoc`, 2010/03/26, v1.9,
[CTAN:macros/latex/contrib/oberdiek/hypdoc.dtx](http://www.ctan.org/macros/latex/contrib/oberdiek/hypdoc.dtx)

`lastpage.sty` The `lastpage.sty` for L^AT_EX 2_ε (i. e. each document using the `lastpage` package) requires:

- T_EXFormat L^AT_EX 2_ε, <http://www.CTAN.org/>
- package `lastpage`, 2011/08/08, v1.2i,
[CTAN:macros/latex/contrib/lastpage/lastpage.dtx](http://www.ctan.org/macros/latex/contrib/lastpage/lastpage.dtx)

and can use

- package `hyperref`, 2011/04/17, v6.82g,
[CTAN:macros/latex/contrib/hyperref.zip](http://www.ctan.org/macros/latex/contrib/hyperref.zip)

`lastpage209.sty` The `lastpage209.sty` for L^AT_EX 2.09 (i. e. each document using the `lastpage209` package) requires:

- T_EXFormat L^AT_EX, v2.09
- package `lastpage209`, 2011/08/08, v1.2i, included in
[CTAN:macros/latex/contrib/lastpage/lastpage.dtx](http://www.ctan.org/macros/latex/contrib/lastpage/lastpage.dtx)

and does not work with `hyperref`, which needs L^AT_EX 2_ε.

`lastpage-example.tex` The `lastpage-example.tex` requires the same file as all documents using the `lastpage` package, i. e.

- package `lastpage`, 2011/08/08, v1.2i,
[CTAN:macros/latex/contrib/lastpage/lastpage.dtx](http://www.ctan.org/macros/latex/contrib/lastpage/lastpage.dtx)
(Well, it is the example file for this package, and because you are reading the documentation for the `lastpage` package, it can be assumed that you already have some version of it – is it the current one?)

and additionally:

- class `article`, 2007/10/19, v1.4h, from `classes.dtx`:
[CTAN:macros/latex/base/classes.dtx](http://www.ctan.org/macros/latex/base/classes.dtx)

	<ul style="list-style-type: none"> - package <code>showkeys</code>, 2007/08/07, v3.15, CTAN:macros/latex/required/tools/showkeys.dtx - package <code>hyperref</code>, 2011/04/17, v6.82g, CTAN:macros/latex/contrib/hyperref.zip
<code>endfloat</code>	<p>The <code>endfloat</code> package is not required, but because the <code>lastpage</code> package is incompatible with <i>very</i> old versions of the <code>endfloat</code> package (see subsection 3.2), here the recent one is listed:</p> <ul style="list-style-type: none"> - package <code>endfloat</code>, 1995/10/11, v2.4i, CTAN:macros/latex/contrib/endfloat/endfloat.dtx
<code>fancyhdr</code> <code>nccfancyhdr</code>	<p>Neither the <code>fancyhdr</code> nor the <code>nccfancyhdr</code> package is required (older versions of the <code>lastpage</code> package used its predecessor <code>fancyheadings</code>), but because they were mentioned, also they are listed here:</p> <ul style="list-style-type: none"> - package <code>fancyhdr</code>, 2005/03/22, v3.2, CTAN:macros/latex/contrib/fancyhdr.zip - package <code>nccfancyhdr</code>, 2004/12/07, v1.1, CTAN:macros/latex/contrib/ncctools/source/nccfancyhdr.dtx
<code>regstats</code>	<p>For counting the used counters (and other registers), the <code>regstats</code> package was mentioned (it is not required). It can be found at:</p> <ul style="list-style-type: none"> - package <code>regstats</code>, 2011/06/18, v1.0d, CTAN:macros/latex/contrib/regstats/regstats.dtx
<code>count1to</code> <code>nofm</code> <code>totpages</code> <code>lastpage</code> <code>zref</code>	<p>As possible alternatives in section 4, Alternatives, there are listed</p> <ul style="list-style-type: none"> - package <code>pageslts</code>, 2011/08/08, v1.2a, CTAN:macros/latex/contrib/pageslts/pageslts.dtx - package <code>papermas</code>, 2011/08/08, v1.0g; the <code>papermas</code> package can be considered as kind of add-on to the <code>pageslts</code> package. CTAN:macros/latex/contrib/papermas/papermas.dtx - package <code>count1to</code>, 2009/05/24, v2.1, CTAN:macros/latex/contrib/ms/count1to.dtx - package <code>nofm</code>, 1991/02/25, v?., ftp://tug.ctan.org/pub/tex-archive/obsolete/macros/latex209/contrib/misc/nofm.sty, does not work with e.g. <code>hyperref</code> - package <code>totpages</code>, 2005/09/19, v2.00, CTAN:macros/latex/contrib/totpages/totpages.dtx - package <code>zref</code>, 2011/03/18, v2.21, CTAN:macros/latex/contrib/oberdiek/zref.dtx, requires ϵ-TeX.
<code>Oberdiek</code> <code>holtxdoc</code> <code>zref</code>	<p>All packages of HEIKO OBERDIEK's bundle 'oberdiek' (especially <code>holtxdoc</code> and <code>zref</code>) are also available in a TDS compliant ZIP archive: CTAN:install/macros/latex/contrib/oberdiek.tds.zip.</p> <p>It is probably best to download and use this, because the packages in there are quite probably both recent and compatible among themselves.</p>
<code>hyperref</code>	<p><code>hyperref</code> is not included in that bundle and needs to be downloaded separately, http://mirror.ctan.org/install/macros/latex/contrib/hyperref.tds.zip.</p>
<code>Münch</code>	<p>A hyperlinked list of my (other) packages can be found at http://www.Uni-Bonn.de/~uzs5pv/LaTeX.html.</p>

7.2 Package, unpacking TDS

Package. This package is available on [CTAN](#):

[CTAN:macros/latex/contrib/lastpage/lastpage.dtx](#)
The source file.

[CTAN:macros/latex/contrib/lastpage/lastpage.pdf](#)
The documentation.

[CTAN:macros/latex/contrib/lastpage/lastpage-example.pdf](#)
The compiled example file, as it should look like.

[CTAN:macros/latex/contrib/lastpage/README](#)
The README file.

There is also a `lastpage.tds.zip` available:

[CTAN:install/macros/latex/contrib/lastpage.tds.zip](#)
Everything in TDS compliant, compiled format.

which additionally contains

<code>lastpage.ins</code>	The installation file.
<code>lastpage.drv</code>	The driver to generate the documentation.
<code>lastpage.sty</code>	The <code>.sty</code> file.
<code>lastpage209.sty</code>	The <code>.sty</code> file for \LaTeX 2.09 only .
<code>lastpage-example.tex</code>	The example file.

For required other packages, see the preceding subsection.

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain \TeX :

```
tex lastpage.dtx
```

About generating the documentation see paragraph 7.4 below.

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree), **but first you should delete the old `lastpage` files (which are probably located in other directories)**. You can make a backup of the old files before deleting them, of course.

<code>lastpage.sty</code>	→ <code>tex/latex/lastpage.sty</code>
<code>lastpage.pdf</code>	→ <code>doc/latex/lastpage.pdf</code>
<code>lastpage-example.tex</code>	→ <code>doc/latex/lastpage-example.tex</code>
<code>lastpage-example.pdf</code>	→ <code>doc/latex/lastpage-example.pdf</code>
<code>lastpage.dtx</code>	→ <code>source/latex/lastpage.dtx</code>
<code>lastpage209.sty</code>	→ <code>tex/latex/lastpage209.sty</code> for \LaTeX 2.09

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

7.3 Refresh file name databases

If your $\text{T}_{\text{E}}\text{X}$ distribution ($\text{t}_{\text{E}}\text{X}$, $\text{m}_{\text{ik}}\text{T}_{\text{E}}\text{X}$,...) relies on file name databases, you must refresh these. For example, $\text{t}_{\text{E}}\text{X}$ users run `texhash` or `mktextlsr`.

7.4 Some details for the interested

Unpacking with $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$. The `.dtx` chooses its action depending on the format:

plain $\text{T}_{\text{E}}\text{X}$: Run `docstrip` and extract the files.

$\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$: Generate the documentation.

If you insist on using $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ for `docstrip` (really, `docstrip` does not need $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$), then inform the `autodetect` routine about your intention:

```
latex \let\install=y\input{lastpage.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by a configuration file `ltxdoc.cfg`. For instance, put the following line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with $\text{pdfL}^{\text{A}}\text{T}_{\text{E}}\text{X}$:

```
pdflatex lastpage.dtx
makeindex -s gind.ist lastpage.idx
pdflatex lastpage.dtx
makeindex -s gind.ist lastpage.idx
pdflatex lastpage.dtx
```

7.5 Compiling the example

The example file, `lastpage-example.tex`, can be compiled via

```
latex lastpage-example.tex
or (recommended)
pdflatex lastpage-example.tex
```

and will need at least two compiler runs to get all references right.

8 Acknowledgements

I (H.-MARTIN MÜNCH) would like to thank JEFFREY P. GOLDBERG (`jeffrey+news at goldmark dot org`) for inventing the `lastpage` package as well as for granting me to update it. Further I would like to thank HEIKO OBERDIEK for providing a lot (!) of useful packages (from which I also got everything I know about creating a file in `dtx` format, ok, say it: copying), and the `news:comp.text.tex` and `news:de.comp.text.tex` newsgroups for their help in all things $\text{T}_{\text{E}}\text{X}$. Thanks for bug reports go to ULRIKE FISCHER, SEBASTIAN BANK, and JAMES HEDGES. Thanks to SVEN SIEGMUND for pointing out a necessary further explanation in the documentation.

9 History

[1994/06/17 v0.99a]

- First shot by JEFFREY P. GOLDBERG.

[1994/06/25 v0.1b]

- Last version number created by JEFFREY P. GOLDBERG.

[1994/07/20 v0.1b (again)]

- Documentation updated by JEFFREY P. GOLDBERG.
The main source code of the `lastpage` package 1994/07/20, v0.1b, was:

```
\NeedsTeXFormat{LaTeX2e}[1994/06/01]
\ProvidesPackage{lastpage}[1994/07/20 v0.1b
  LaTeX2e package for refs to last page number (JPG)]
\def\lastpage@putlabel{\addtocounter{page}{-1}%
  \immediate\write\@auxout{\string
    \newlabel{LastPage}{\thepage}}%
  \addtocounter{page}{1}}
\AtEndDocument{%
  \message{AED: lastpage setting LastPage}%
  \clearpage\lastpage@putlabel}%
\endinput
```

and then the `hyperref` package and the `revtex4` class even redefine `\lastpage@putlabel` (at least `hyperref` version ~~2010/09/13, v6.81n~~
2011/04/17, v6.82g, and `REVTeX4` version 2010/07/25, v4.1r, still do this).

[2010/02/18 v1.1]

- Proposed `LastPages` label by H.-MARTIN MÜNCH on [news:comp.text.tex](http://groups.google.com/group/comp.text.tex/msg/4407493da9c747f0?dmode=source), see e. g. <http://groups.google.com/group/comp.text.tex/msg/4407493da9c747f0?dmode=source>; now available in the `pageslts` package.

[2010/07/29 v1.2a]

- Complete rewriting of the package; upgrade from `fancyheadings` to `fancyhdr` package, then removed the need for the `fancyhdr` package at all.
- Included `lastpage209.sty` for \LaTeX 2.09.
- Replacement of `\filedate`, `-version`, `-name`, ... because of \LaTeX bug 2705:
Synopsis: Possible problem with `\fileversion` and `\filedate`
<http://www.latex-project.org/cgi-bin/ltxbugs2html?category=LaTeX&responsible=anyone&state=anything&keyword=lastpage&pr=latex%2F2705&search=>
- Example `lastpage-example.tex`.
- Alternatives listing (section 4).

- Listing of T_EX sources (subsection 7.1).
- A lot (!) of details.
- Complete rewriting of the documentation.
- Added a list of my other packages.
- Everything in DTX framework.
- Included a `\Checksum`.
- Complete rewriting of the README file.

[2010/08/12 v1.2b]

- Bug fix: `\@PackageInfoNoLine` is only available, if the `hyperref` package is loaded. (Bug reported by ULRIKE FISCHER, thanks!)
- Detected another bug: `\ifHy@pageanchor` etc. do not work without `hyperref`, and `\else` related to `\ifHy@pageanchor` was wrongly associated with a preceding `\if`, and everything went wrong. Now everything should work without `hyperref` again.
- Renamed `\lastpage@putlabel` to `\lastpage@putl@bel` to get rid of the conflicts with other classes and packages and resulting multiple definitions of `lastpage` label.

[2010/08/23 v1.2c]

- Bug fix: Additionally to checking for the `hyperref` package `\AtBeginDocument`, when placing the `lastpage` label it is also checked for the `\hyperref` command, in case `hyperref` was not loaded at `\begin{document}` yet. (Bug reported by SEBASTIAN BANK, thanks!)
- Changed the `\unit` definition (got rid of an old `\rm`).
- Changed `\lastpage@puthyperlabel` to `\lastpage@putlabelhyper` analogous to `\pagesLTS@putlabelhyper` of the `pageslts` package.
- The recent version of the Adobe Reader ~~is~~was 9.3.3 (instead of 9.3.1).
- Updated version number and date of `pagesLTS` package (especially for the check for outdated versions).
- Removed wrong `%` from the driver file.

[2010/08/25 v1.2d]

- Bug fix: also `tcilatex` defines the `\hyperref` command, therefore for `hyperref` package detection this had to be changed to `\Hy@Warning`.

[2010/09/12 v1.2e]

- JAMES HEDGES (Thanks!) pointed out, that there was no instruction in the documentation about suppressing hyperlinks: added (also to the example).
- The recent version of the Adobe Reader ~~is~~was 9.3.4 (instead of 9.3.3).
- Diverse small changes.

[2010/09/24 v1.2f]

- Updated to version 2010/09/13 v6.81n of the `hyperref` package.
- New version of REVTeX4 2010/07/25, v4.1r, old problem.
- New version of `pagesLTS` package, 2010/09/22, v1.1k.
- Moved the package from `.../latex/muench/lastpage/...` to `.../latex/lastpage/...`
(Please make sure that any old versions of the `lastpage` package are properly uninstalled from your system.)

[2011/02/01 v1.2g]

- Updated to version 2010/04/24 v0.19 of the `holtxdoc` package.
- New version of `pagesLTS` package, 2011/02/01, v1.1m.
- Replaced the list of my packages with a link to a web page list of those, which has the advantage of showing the recent versions of all those packages.
- Updated to version 2010/12/16 v6.81z of the `hyperref` package.
- The recent version of the Adobe Reader ~~is~~was X (10.0.0) (instead of 9.3.4). Its handling of special page numbers was improved.
- Minor details.

[2011/07/03 v1.2h]

- The `holtxdoc` package was fixed (recent: 2011/02/04, v0.21), therefore the warning in `drv` could be removed. – Adapted the style of this documentation to new OBERDIEK `dtx` style.
- New version of `pagesLTS` package, 2011/03/17, v1.1o.
- New version of `ulem` package, 2011/03/18.
- There is a new version of the `hyperref` package: 2011/04/17, v6.82g.
- There is a new version of the `papermas` package: 2011/06/02, v1.0f .
- The recent version of the Adobe Reader is X (10.1.0; instead of 10.0.0).
- Corrected a reference to `lastpage` at CTAN:.
- Corrected a reference to `pagesLTS` at CTAN:.
- Corrected references in the README.

[2011/08/08 v1.2i]

- The `pagesLTS` package has been renamed to `pageslts`: 2011/08/08, v1.2a.
- Some details.

When you find a mistake or have a suggestion for an improvement of this package, please send an e-mail to the maintainer, thanks! (Please see BUG REPORTS in the README.)

10 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
\@auxout	201, 257
\@evenfoot	37, 40
\@firstofone	221
\ifpackageloaded	155, 156, 171
\ifundefined	85, 191
\@mainaux	9
\@number	221
\@oddfont	40
A	
\addtocounter	8, 10, 200, 202, 217, 263
\AtBeginDocument	<u>154</u>
\AtEndDocument	17, <u>267</u>
C	
\clearpage	7, 271
\countto	8, 18
E	
\endfloat	18
F	
\fancyhdr	18
H	
\holtxdoc	18
\Hy@pagecounter	254
\Hy@temp	225, 233, 237, 241, 248, 254, 260
\Hy@unicodedefalse	227
\hyperref	18
\hypersetup	21
I	
\if@files	269
\ifHy@hypertexnames	223
\ifHy@pageanchor	209, 222, 260
\ifHy@plainpages	224
\immediate	9, 201, 257
L	
\label	55
\lastpage	18
\lastpage-example.tex	17
\lastpage.dtx	17
\lastpage.sty	17
\lastpage209.sty	7, 17
\lastpage@firstpage	152, 236, 238
\lastpage@hyper	150, 155, 192, 196
\lastpage@LTS	151, 161, 185, 194
\lastpage@one	149, 194, 196, 236
\lastpage@putl@bel	<u>190</u> , 271
\lastpage@putlabel	187, 268
\lastpage@putlabelhyper	197, <u>208</u>
M	
\M{"{u}nch	18
\markboth	48
\message	17, 270
N	
\nccfancyhdr	18
\newcommand	190, 208
\newlabel	9, 201, 258
\nofm	18
\nofm.sty	8
O	
\Oberdiek	18
\origenddocument	6, 11
P	
\PackageError	211, 273
\PackageInfo	162
\PackageWarning	157, 172
\pagenumbering	45
\pageslts	7
\pdfstringdef	233, 241, 248
R	
\regstats	18
\renewcommand	37, 40
S	
\slshape	38
T	
\thepage	9, 38, 103, 109, 115, 123, 134, 201, 233, 237, 241, 248, 259
\totpages	8, 18
U	
\unit	42, 95, 96
\upshape	38
V	
\value	235
W	
\write	9, 201, 257
Z	
\zref	8, 18, 18