

Lwarp

LATEX HTML5

The **lwarp** package

LATEX to HTML

v0.61 — 2018/10/13

© 2016–2018 Brian Dunn
bd@BDTechConcepts.com

Abstract

The **lwarp** package allows LATEX to directly produce HTML5 output, using external utility programs only for the final conversion of text and images. Math may be represented by SVG files or MATHJAX.

Documents may be produced by pdfLATEX, LuaLATEX, or XeLATEX. A **texlua** script removes the need for system utilities such as **make** and **gawk**, and also supports **xindy** and **latexmk**. Configuration is automatic at the first manual compile.

Print and HTML versions of each document may coexist, each with its own set of auxiliary files. Support files are self-generated on request. Assistance is provided for import into EPUB conversion software and word processors.

A modular package-loading system uses the **lwarp** version of a package for HTML when available. More than 300 LATEX packages are supported with these high-level source-compatibility replacements, and many others work as-is.

A tutorial is provided to quickly introduce the user to the major components of the package.

To update existing projects, see section 2: Updates.

For a list of supported features, see table 1: Supported packages and features.

Note that this is still a “beta” version of **lwarp**, and some things may change in response to user feedback and further project development.

License:

This work may be distributed and/or modified under the conditions of the LaTeX Project Public License, either version 1.3 of this license or (at your option) any later version. The latest version of this license is in <http://www.latex-project.org/lppl.txt> and version 1.3 or later is part of all distributions of LaTeX version 2005/12/01 or later.

1 Supporting TeX development

TeX and related projects:

- are mostly open-sourced and a volunteer effort;
- benefit students, academics, scientists, engineers, and businesses;
- help drive education, public and private research, and commercial activity;
- are used in the fields of mathematics, science, engineering, and humanities;
- span decades of development;
- are enduring—many older packages are still actively used and maintained;
- are largely backwards compatible;
- are portable across all the major computing platforms;
- are usable even on older computers and away from internet access;
- are continuing to maintain relevance with modern improvements;
- require no yearly subscription fees;
- and are supported by an active community of knowledgeable volunteers.

Please consider helping by joining and/or contributing to the TeX Users Group, a United States 501(c)(3) tax-exempt charitable organization. Contributions are accepted by credit card, check, or Pay Pal, via the United Way, or by USA or European bank transfer. Membership in TUG supports the development of TeXLive, the major TeX distribution.

Donations may be directed towards individual projects:

TUG Bursary Fund: Assistance for attending annual TUG meetings.

CTAN: The Comprehensive TeX Archive Network—Central storage for TeX.

TeX Development Fund: Support for specific projects.

EduTeX: Teaching and using TeX in schools and universities.

GUST e-foundry fonts: Enhanced for math and additional language groups.

LaTeX Project: Modernizing the L^AT_EX core.

Libre Font Fund: Fonts, tools (FontForge), and distribution (the Open Font Library).

LuaTeX: Combining the pdfTeX engine and the Lua language.

MetaPost: Postscript graphics.

MacTeX: TeX for Mac.

PDF Accessibility: Modern PDF standards.

Other: Additional projects may be specified.

To make a contribution:

<https://www.tug.org/donate.html>

For users of MiKTeX:

<https://miktex.org/donations.html>

For country-specific TeX users groups:

<http://tug.org/usergroups.html>

Contents

1 Supporting TeX development	2
List of Figures	52
List of Tables	52
2 Updates	53
3 Introduction	71
3.1 Supported packages and features	73
4 Alternatives	78
4.1 Internet class	78
4.2 TeX4ht	78
4.3 Translators	78
4.4 AsciiDoc and Asciidoctor	79
4.4.1 Asciidoctor-LaTeX	79
4.5 Pandoc	79
4.6 Word processors	79
4.7 Commercial systems	79
4.8 Comparisons	79
5 Installation	81
5.1 Installing the lwarpm package	83
5.2 Installing the lwarpmk utility	85
5.2.1 Using a local copy of lwarpmk	86
5.3 Installing additional utilities	87
6 Tutorial	89
6.1 Starting a new project	89
6.2 Compiling the print version with lwarpmk	93
6.3 Compiling the HTML version with lwarpmk	94
6.4 Generating the SVG images	95
6.5 Using MATHJAX for math	97
6.6 Changing the CSS style	98
6.7 Customizing the HTML output	98
6.8 Using latexmk	99
6.9 Using XeLaTeX or LuaLaTeX	100
6.10 Using DVI LaTeX	100
6.11 Using a glossary	101
6.12 Cleaning auxiliary files	102
6.13 Cleaning auxiliary and output files	102
6.14 Cleaning the images from the lateximages directory	102
6.15 Converting PDF or EPS images to SVG	102
6.16 Creating HTML from an incomplete compile	102

6.17	Processing multiple projects in the same directory	103
6.18	Using the make utility	103
7	Converting an existing document	104
8	Additional details	105
8.1	Shell escape	105
8.2	Font and UTF-8 support	105
8.2.1	Indexes, glossaries, and encoding	107
8.3	lwarf package loading and options	108
8.4	Customizing the HTML output	112
8.4.1	Example HTML file naming	117
8.5	Customizing the CSS	118
8.6	Selecting the operating system	120
8.7	Selecting actions for print or HTML output	120
8.8	Commands to be placed into the warpprint environment	121
8.9	Title page	122
8.10	HTML page meta descriptions	123
8.11	HTML page meta title	123
8.12	HTML page meta author	123
9	Special cases and limitations	123
9.1	Things to avoid	124
9.2	Formatting	124
9.2.1	Text formatting	124
9.2.2	Horizontal space	125
9.2.3	Text alignment	125
9.2.4	Accents	125
9.2.5	textcomp package	125
9.2.6	Superscripts and other non-math uses of math mode	125
9.2.7	Empty <code>\item</code> followed by a new line of text or a nested list:	126
9.2.8	Filenames and URLs in lists or footnotes	126
9.2.9	relsize package	126
9.3	Boxes and minipages	126
9.3.1	Marginpars	126
9.3.2	Save Boxes	126
9.3.3	Minipages	127
9.3.4	Side-by-side minipages	127
9.3.5	Framed minipages and other environments	128
9.3.6	fancybox package	129
9.3.7	mdframed package	130
9.4	Cross-references	131
9.4.1	Page references	131
9.4.2	cleveref and variorref packages	131
9.4.3	Hyperlinks, hyperref , and url	132
9.4.4	Footnotes and page notes	132

9.5	Front and back matter	133
9.5.1	Custom classes with multiple authors and affiliations	133
9.5.2	Starred chapters and sections	133
9.5.3	abstract package	134
9.5.4	titling and authblk	134
9.5.5	tocloft package	134
9.5.6	appendix package	135
9.5.7	pagenote package	135
9.5.8	endnotes package	135
9.5.9	BibTeX	135
9.5.10	glossaries package	135
9.5.11	Indexing overview	137
9.5.12	Indexing with basic L ^A T _E X and makeidx	137
9.5.13	Indexing with index	138
9.5.14	Indexing with splitidx	139
9.5.15	Indexing with imakeidx	141
9.5.16	Indexes with memoir	144
9.5.17	Using a custom makeindex style file	147
9.5.18	Using a custom xindy style file	148
9.5.19	Additional indexing limitations	149
9.5.20	Index positions, toc , tocbibind	149
9.6	Math	150
9.6.1	Rendering tradeoffs	150
9.6.2	SVG option	151
9.6.3	MATHJAX option	152
9.6.4	Customizing MATHJAX	152
9.6.5	MATHJAX limitations	152
9.6.6	Catcode changes	153
9.6.7	Complicated inline math objects	153
9.6.8	Complicated display math objects	154
9.6.9	chemformula package	154
9.6.10	mhchem package	154
9.6.11	ntheorem package	154
9.6.12	siunitx package	155
9.6.13	units and nicefrac packages	155
9.6.14	newtxmath package	155
9.7	Graphics	155
9.7.1	tikz package	157
9.7.2	grffile package	157
9.7.3	color package	157
9.7.4	xcolor package	157
9.7.5	epstopdf package	158
9.7.6	pstricks package	158
9.7.7	pdftricks package	158
9.7.8	psfrag package	159
9.7.9	pstool package	159

9.7.10 <code>overpic</code> package	159
9.8 Tabbing	159
9.9 Tabular	160
9.9.1 <code>longtable</code> package	162
9.9.2 <code>supertabular</code> and <code>xtab</code> packages	163
9.9.3 <code>bigdelim</code> package	163
9.10 Floats	164
9.10.1 Float contents alignment	164
9.10.2 <code>float</code> , <code>trivfloat</code> , and/or <code>algorithmicx</code> together	164
9.10.3 <code>caption</code> and <code>subcaption</code> packages	164
9.10.4 <code>subfig</code> package	165
9.10.5 <code>floatrow</code> package	165
9.10.6 <code>keyfloat</code> package	165
9.11 Koma-Script	166
9.12 Memoir	166
9.13 Miscellaneous packages	167
9.13.1 <code>verse</code> and <code>memoir</code>	167
9.13.2 <code>newclude</code> package	167
9.13.3 <code>babel</code> package	168
9.13.4 <code>polyglossia</code> package	168
9.13.5 <code>todonotes</code> and <code>luatodonotes</code> packages	168
9.13.6 <code>fixme</code>	169
9.13.7 <code>xparse</code>	169
10 Compiling using custom shell commands	170
10.1 Command options	170
10.2 Literal character macros	170
10.3 <code>latexmk</code>	172
10.4 <code>perltx</code> package	172
10.5 <code>pythontex</code> package	172
10.6 Other packages	173
10.7 <code>make</code> program	173
11 EPUB conversion	174
12 Word-processor conversion	176
12.1 Activating word-processor conversion	176
12.2 Additional modifications	178
12.3 Recommendations	179
12.4 Limitations	180
13 Modifying l warp	182
13.1 Creating a development system	182
13.2 Modifying a package for <code>l warp</code>	184
13.2.1 Adding a package to the <code>l warp.dtx</code> file	185
13.3 Modifying a class for <code>l warp</code>	185

13.4	Testing l warp	185
13.5	Modifying l warpmk	186
14	Troubleshooting	187
14.1	Using the l warp.sty package	187
14.1.1	Debug tracing output	191
14.2	Compiling the l warp.dtx file	191
1	l warp.sty	192
15	Implementation	192
16	Section depths and HTML headings	193
17	Source Code	194
18	Detecting the TeX Engine — pdflatex, lualatex, xelatex	195
19	MD5 hashing	195
20	pdfLaTeX T1 and UTF8 encoding	196
21	Unicode input characters	196
22	Miscellaneous tools	197
23	Early package requirements	197
24	Operating-System portability	198
24.1	Literal characters	198
24.2	Common portability code	199
24.3	Unix, Linux, and Mac OS	199
24.4	MS-WINDOWS	200
25	Package options	200
25.1	Conditional compilation	206
26	Package load order	207
26.1	Tests of package load order	207
26.2	Error for disallowed packages loaded before l warp	209
26.3	Enforcing package loading after l warp	209
27	Required packages	216
28	Loading packages	220
29	Additional required packages	224

30	File handles	224
31	Include a file	225
32	Copying a file	226
33	Debugging messages	227
34	Defining print and HTML versions of macros and environments	228
35	HTML-conversion output modifications	233
35.1	User-level controls	233
35.2	Heading adjustments	235
36	Remembering original formatting macros	236
37	Accents	239
38	Configuration Files	240
38.1	Decide whether to generate configuration files	240
38.2	project_html.tex	241
38.3	l warpmk configuration files	241
38.3.1	Helper macros	241
38.3.2	l warpmk.conf	247
38.3.3	<project>.l warpmkconf	248
38.4	l warp.css	248
38.5	l warp_sagebrush.css	277
38.6	l warp_formal.css	283
38.7	sample_project.css	287
38.8	l warp.ist	287
38.9	l warp.xdy	288
38.10	l warp_one_limage.cmd	289
38.11	l warp_mathjax.txt	290
38.12	l warpmk.lua — l warpmk option	292
39	Stacks	310
39.1	Assigning depths	311
39.2	Closing actions	311
39.3	Closing depths	312
39.4	Pushing and popping the stack	312
40	Data arrays	314
41	Localizing catcodes	314
42	Localizing dynamic math	315
43	Sanitizing labels and filenames	317

44	HTML entities	317
45	HTML filename generation	318
46	Homepage link	321
47	\LWRPrintStack diagnostic tool	321
48	Closing stack levels	322
49	PDF pages and styles	323
50	HTML tags, spans, divs, elements	324
50.1	Mapping L ^A T _E X Sections to HTML Sections	324
50.2	Babel-French tag modifications	325
50.3	HTML tags	326
50.4	Block tags and comments	328
50.5	Div class and element class	329
50.6	Single-line elements	330
50.7	HTML5 semantic elements	331
50.8	High-level block and inline classes	331
50.9	Closing HTML tags	333
51	Paragraph handling	334
52	Paragraph start/stop handling	338
53	Page headers and footers	340
54	CSS	341
55	Title, HTML meta author, HTML meta description	342
56	Footnotes	343
56.1	Regular page footnotes	344
56.2	Minipage footnotes	344
56.3	Titlepage thanks	344
56.4	Regular page footnote implementation	344
56.5	Minipage footnote implementation	346
56.6	Printing pending footnotes	348
57	Margins	349
58	Splitting HTML files	350
59	Sectioning	358
59.1	User-level starred section commands	358
59.2	Book class commands	359

59.3	Sectioning support macros	360
59.4	\section and friends	367
60	Starting a new file	369
61	Starting HTML output	371
62	Ending HTML output	375
63	Title page	376
63.1	Setting the title, etc.	377
63.2	\if@titlepage	378
63.3	Changes for \affiliation	378
63.4	Printing the thanks	379
63.5	Printing the title, etc. in HTML	380
63.6	Printing the title, etc. in print form	381
63.7	\maketitle for HTML output	381
63.8	\published and \subtitle	385
64	Abstract	386
65	Quote and verse	387
65.1	Attributions	387
65.2	Quotes, quotations	387
65.3	Verse	388
65.3.1	TEX core verse environment	388
65.3.2	verse and memoir	389
66	Verbatim and tabbing	389
67	Theorems	392
68	Lists	393
68.1	List environment	394
68.2	Itemize	398
68.3	Enumerate	398
68.4	Description	399
68.5	Patching the lists	400
69	Tabular	401
69.1	Limitations	401
69.2	Temporary package-related macros	404
69.2.1	arydshln	404
69.3	Token lookahead	404
69.4	Tabular variables	405
69.5	Handling &, @, !, and bar	408
69.5.1	Handling &	410

69.5.2	Filling an unfinished row	411
69.6	Handling \\	413
69.7	Looking ahead in the column specifications	414
69.8	Parsing @, >, <, !, bar columns	415
69.9	Parsing 'l', 'c', or 'r' columns	419
69.10	Parsing 'p', 'm', or 'b' columns	419
69.11	Parsing 'w' columns	420
69.12	Parsing 'D' columns	420
69.13	Parsing the column specifications	420
69.14	colortbl and xparse tabular color support	425
69.15	Starting a new row	427
69.16	Printing vertical bar tags	428
69.17	Printing at or bang tags	428
69.18	Data opening tag	429
69.19	Midrules	431
69.20	Cell colors	438
69.21	Multicolumns	442
69.21.1	Parsing multicolumns	442
69.21.2	Multicolumn factored code	446
69.21.3	Multicolumn	449
69.21.4	Longtable captions	449
69.21.5	Counting HTML tabular columns	452
69.22	Multirow if not loaded	454
69.23	Multicolumnrow	454
69.24	Utility macros inside a table	455
69.25	Special-case tabular markers	456
69.26	Checking for a new table cell	457
69.27	\mrowcell	460
69.28	\mcrowcell	460
69.29	HTML tabular environment	461
70	Cross-references	467
70.1	Setup	467
70.2	Zref setup	469
70.3	Labels	470
70.4	References	472
70.5	Hyper-references	475
71	Floats	479
71.1	Float environment	480
71.2	Float tracking	482
71.3	Caption inside a float environment	483
71.4	Caption and LOF linking and tracking	484
72	Table of Contents, LOF, LOT	487
72.1	Reading and printing the TOC	488

72.2	High-level TOC commands	491
72.3	Side TOC	491
72.4	Low-level TOC line formatting	493
73	Index and glossary	496
74	Bibliography presentation	499
75	Restoring original formatting	500
76	Math	502
76.1	Limitations	502
76.1.1	Rendering tradeoffs	502
76.1.2	SVG option	503
76.1.3	MATHJAX option	503
76.1.4	Customizing MATHJAX	504
76.1.5	MATHJAX limitations	504
76.1.6	Catcode changes	505
76.1.7	Complicated inline math objects	505
76.1.8	Complicated display math objects	505
76.2	HTML alt tag names	506
76.3	Inline and display math	506
76.4	MATHJAX support	518
76.5	Equation environment	520
76.6	\displaymathnormal and \displaymathother	523
76.7	AMS Math environments	524
76.7.1	Support macros	524
76.7.2	Environment patches	526
77	Lateximages	528
77.1	Description	528
77.2	Support counters and macros	530
77.3	Font size	530
77.4	Sanitizing math expressions for HTML	531
77.5	Equation numbers	533
77.6	HTML alt tags	534
77.7	lateximage environment	534
78	center, flushleft, flushright	540
79	Pre-loaded packages	542
80	Siunitx	543
81	Graphics print-mode modifications	544
81.1	General limitations	544
81.2	Print-mode modifications	545

82 Xcolor boxes	546
83 Chemmacros environments	549
84 Cleveref	550
85 Picture	553
86 Boxes and Minipages	554
86.1 Counters and lengths	555
86.2 Footnote handling	555
86.3 Minipage handling	555
86.4 Parbox, mbox, makebox, framebox, fbox, raisebox	559
87 Direct formatting	564
88 Skips, spaces, font sizes	572
89 \phantomsection	580
90 \LaTeX{} and other logos	580
90.1 HTML logos	581
90.2 Print logos	583
91 \AtBeginDocument, \AtEndDocument	583
92 Koma-script	583
93 Memoir	584
94 Trademarks	585
2 lwarf-2up.sty	586
95 2up	586
3 lwarf-a4.sty	586
96 a4	586
4 lwarf-a4wide.sty	586
97 a4wide	586

5 l warp-a5comb.sty	587
98 a5comb	587
6 l warp-abstract.sty	587
99 abstract	587
7 l warp-accsupp.sty	589
100 accsupp	589
8 l warp-acro.sty	590
101 acro	590
9 l warp-acronym.sty	591
102 acronym	591
10 l warp-adjmulticol.sty	593
103 adjmulticol	593
11 l warp-addlines.sty	594
104 addlines	594
12 l warp-ae.sty	594
105 ae	594
13 l warp-aecc.sty	594
106 aecc	594
14 l warp-afterpage.sty	594
107 afterpage	594

15 l warp-algorithm2e.sty	595
108 algorithm2e	595
16 l warp-algorithmicx.sty	599
109 algorithmicx	599
17 l warp-alltt.sty	600
110 alltt	600
18 l warp-amsmath.sty	600
111 amsmath	600
19 l warp-amsthm.sty	607
112 amsthm	607
20 l warp-anonchap.sty	611
113 anonchap	611
21 l warp-any size.sty	612
114 anysize	612
22 l warp-appendix.sty	612
115 appendix	612
23 l warp-arabicfront.sty	613
116 arabicfront	613
24 l warp-array.sty	613
117 array	613

25 larp-arydshln.sty	614
118 arydshln	614
26 larp-asymptote.sty	616
119 asymptote	616
27 larp-atbegshi.sty	616
120 atbegshi	616
28 larp-attachfile.sty	617
121 attachfile	617
29 larp-attachfile2.sty	618
122 attachfile2	618
30 larp-authblk.sty	620
123 authblk	620
31 larp-axessibility.sty	621
124 axessibility	621
32 larp-axodraw2.sty	622
125 axodraw2	622
33 larp-backref.sty	622
126 backref	622
34 larp-balance.sty	622
127 balance	622

35 lwarf-bibunits.sty	623
128 bibunits	623
36 lwarf-bigdelim.sty	623
129 bigdelim	623
37 lwarf-bigstrut.sty	624
130 bigstrut	624
38 lwarf-blowup.sty	625
131 blowup	625
39 lwarf-booklet.sty	625
132 booklet	625
40 lwarf-bookmark.sty	626
133 bookmark	626
41 lwarf-booktabs.sty	626
134 booktabs	626
42 lwarf-bophook.sty	628
135 bophook	628
43 lwarf-boxedminipage.sty	628
136 boxedminipage	628
44 lwarf-boxedminipage2e.sty	628
137 boxedminipage2e	628

45 l warp-breakurl.sty	629
138 breakurl	629
46 l warp-breqn.sty	629
139 breqn	629
47 l warp-bxpaper size.sty	631
140 bxpaper size	631
48 l warp-bytefield.sty	632
141 bytefield	632
49 l warp-cancel.sty	632
142 cancel	632
50 l warp-canonic layout.sty	633
143 canonic layout	633
51 l warp-caption.sty	633
144 caption	633
52 l warp-caption2.sty	636
145 caption2	636
53 l warp-cases.sty	637
146 cases	637
54 l warp-ccaption.sty	637
147 ccaption	637

55 lwarf-changebar.sty	638
148 changebar	638
56 lwarf-changepage.sty	638
149 changepage	638
57 lwarf-chngpage.sty	639
150 chngpage	639
58 lwarf-chappg.sty	639
151 chappg	639
59 lwarf-chapterbib.sty	639
152 chapterbib	639
60 lwarf-chemfig.sty	640
153 chemfig	640
61 lwarf-chemformula.sty	641
154 chemformula	641
62 lwarf-chemgreek.sty	646
155 chemgreek	646
63 lwarf-chemmacros.sty	647
156 chemmacros	647
156.1 Changes to the user's document	647
156.2 Code	648
156.3 Loading modules	648
156.4 New environments	648

156.5 Acid-base	649
156.6 Charges	651
156.7 Nomenclature	651
156.8 Particles	653
156.9 Phases	654
156.10 Mechanisms	655
156.11 Newman	657
156.12 Orbital	658
156.13 Reactions	658
156.14 Redox	659
156.15 Scheme	660
156.16 Spectroscopy	660
156.17 Thermodynamics	665
64 lwarf-chemnum.sty	667
157 chemnum	667
65 lwarf-chkfloat.sty	668
158 chkfloat	668
66 lwarf-cite.sty	668
159 cite	668
67 lwarf-clrdblpq.sty	668
160 clrdblpq	668
68 lwarf-cmdtrack.sty	669
161 cmdtrack	669
69 lwarf-color.sty	669
162 color	669
70 lwarf-colortbl.sty	669

163	colortbl	669
71	l warp-continue.sty	671
164	continue	671
72	l warp-copyrightbox.sty	671
165	copyrightbox	671
73	l warp-crop.sty	672
166	crop	672
74	l warp-cuted.sty	672
167	cuted	672
75	l warp-cutwin.sty	673
168	cutwin	673
76	l warp-dblfloatfix.sty	674
169	dblfloatfix	674
77	l warp-dblfnote.sty	674
170	dblfnote	674
78	l warp-dcolumn.sty	674
171	dcolumn	674
79	l warp-diagbox.sty	675
172	diagbox	675

80 l warp-dprogress.sty	676
173 dprogress	676
81 l warp-draftcopy.sty	677
174 draftcopy	677
82 l warp-draftfigure.sty	677
175 draftfigure	677
83 l warp-draftwatermark.sty	678
176 draftwatermark	678
84 l warp-easy-todo.sty	678
177 easy-todo	678
85 l warp-ebook.sty	679
178 ebook	679
86 l warp-ellipsis.sty	679
179 ellipsis	679
87 l warp-emptypage.sty	680
180 emptypage	680
88 l warp-endfloat.sty	680
181 endfloat	680
89 l warp-endheads.sty	681
182 endheads	681

90 l warp-endnotes.sty	681
183 endnotes	681
91 l warp-enumerate.sty	682
184 enumerate	682
92 l warp-enumitem.sty	682
185 enumitem	682
93 l warp-epigraph.sty	683
186 epigraph	683
94 l warp-epsfig.sty	684
187 epsfig	684
95 l warp-epstopdf.sty	685
188 epstopdf	685
96 l warp-epstopdf-base.sty	685
189 epstopdf-base	685
97 l warp-errata.sty	686
190 errata	686
98 l warp-eso-pic.sty	688
191 eso-pic	688
99 l warp-everypage.sty	689
192 everypage	689

100 l warp-everyshi.sty	689
193 everyshi	689
101 l warp-extramarks.sty	689
194 extramarks	689
102 l warp-fancybox.sty	690
195 fancybox	690
103 l warp-fancyheadings.sty	696
196 fancyheadings	696
104 l warp-fancyhdr.sty	696
197 fancyhdr	696
105 l warp-fancyref.sty	697
198 fancyref	697
106 l warp-fancytabs.sty	698
199 fancytabs	698
107 l warp-fancyvrb.sty	698
200 fancyvrb	698
108 l warp-figcaps.sty	705
201 figcaps	705
109 l warp-figsize.sty	705

202 figsize	705
110 l warp-fix2col.sty	706
203 fix2col	706
111 l warp-fixme.sty	706
204 fixme	706
112 l warp-fixmetodonotes.sty	707
205 fixmetodonotes	707
113 l warp-flafter.sty	708
206 flafter	708
114 l warp-float.sty	708
207 float	708
115 l warp-floatflt.sty	710
208 floatflt	710
116 l warp-floatpag.sty	711
209 floatpag	711
117 l warp-floatrow.sty	711
210 floatrow	711
118 l warp-fltrace.sty	717
211 fltrace	717

119 l warp-flushend.sty	717
212 flushend	717
120 l warp-fnbreak.sty	718
213 fnbreak	718
121 l warp-fncychap.sty	718
214 fncychap	718
122 l warp-fnlineno.sty	719
215 fnlineno	719
123 l warp-fnpos.sty	719
216 fnpos	719
124 l warp-fontenc.sty	719
217 fontenc	719
125 l warp-fontspec.sty	720
218 fontspec	720
126 l warp-footmisc.sty	720
219 footmisc	720
127 l warp-footnote.sty	721
220 footnote	721
128 l warp-footnotehyper.sty	722
221 footnotehyper	722

129 l warp-footnpag.sty	723
222 footnpag	723
130 l warp-forest.sty	723
223 forest	723
131 l warp-framed.sty	724
224 framed	724
132 l warp-ftnright.sty	726
225 ftnright	726
133 l warp-fullminipage.sty	726
226 fullminipage	726
134 l warp-fullpage.sty	727
227 fullpage	727
135 l warp-fullwidth.sty	727
228 fullwidth	727
136 l warp-fwlw.sty	727
229 fwlw	727
137 l warp-geometry.sty	728
230 geometry	728
138 l warp-glossaries.sty	728
231 glossaries	728

139 l warp-glossary.sty	731
232 glossary	731
 140 l warp-graphics.sty	731
233 graphics	731
233.1 Graphics extensions	731
233.2 Length conversions and graphics options	732
233.3 Printing HTML styles	735
233.4 \includegraphics	735
233.5 Boxes	741
 141 l warp-graphicx.sty	744
234 graphicx	744
 142 l warp-grffile.sty	744
235 grffile	744
 143 l warp-grid.sty	745
236 grid	745
 144 l warp-grid-system.sty	745
237 grid-system	745
 145 l warp-gridset.sty	745
238 gridset	745
 146 l warp-hang.sty	746
239 hang	746
 147 l warp-hanging.sty	747

240 hanging	747
148 l warp-hypcap.sty	748
241 hypcap	748
149 l warp-hypdestopt.sty	749
242 hypdestopt	749
150 l warp-hypernat.sty	749
243 hypernat	749
151 l warp-hyperref.sty	749
244 hyperref	749
152 l warp-hyperxmp.sty	755
245 hyperxmp	755
153 l warp-hyphenat.sty	755
246 hyphenat	755
154 l warp-idxlayout.sty	756
247 idxlayout	756
155 l warp-ifoddpage.sty	757
248 ifoddpage	757
156 l warp-imakeidx.sty	757
249 imakeidx	757

157 l warp-indentfirst.sty	762
250 indentfirst	762
158 l warp-index.sty	762
251 index	762
159 l warp-inputenc.sty	764
252 inputenc	764
160 l warp-inputenx.sty	764
253 inputenx	764
161 l warp-intopdf.sty	764
254 intopdf	764
162 l warp-keyfloat.sty	765
255 keyfloat	765
163 l warp-layaureo.sty	767
256 layaureo	767
164 l warp-layout.sty	767
257 layout	767
165 l warp-leading.sty	768
258 leading	768
166 l warp-letterspace.sty	768

259 letterspace	768
167 lwarf-letrine.sty	768
260 letrine	768
168 lwarf-lineno.sty	769
261 lineno	769
169 lwarf-lips.sty	772
262 lips	772
170 lwarf-listings.sty	772
263 listings	772
171 lwarf-longtable.sty	777
264 longtable	777
172 lwarf-lscape.sty	779
265 lscape	779
173 lwarf-ltablex.sty	779
266 ltablex	779
174 lwarf-ltcaption.sty	780
267 ltcaption	780
175 lwarf-ltxgrid.sty	780
268 ltxgrid	780

176 l warp-ltxtable.sty	780
269 ltxtable	780
177 l warp-lua-check-hyphen.sty	781
270 lua-check-hyphen	781
178 l warp-lua-visual-debug.sty	781
271 lua-visual-debug	781
179 l warp-luacolor.sty	781
272 luacolor	781
180 l warp-luatodonotes.sty	782
273 luatodonotes	782
181 l warp-magaz.sty	784
274 magaz	784
182 l warp-makeidx.sty	784
275 makeidx	784
183 l warp-marginfit.sty	785
276 marginfit	785
184 l warp-marginfix.sty	785
277 marginfix	785
185 l warp-marginnote.sty	786
278 marginnote	786

186 l warp-mcaption.sty	786
279 mcaption	786
187 l warp-mdframed.sty	787
280 mdframed	787
280.1 Limitations	787
280.2 Package loading	788
280.3 Patches	788
280.4 Initial setup	789
280.5 Color and length HTML conversion	789
280.6 Environment encapsulation	789
280.7 Mdframed environment	791
280.8 Titles and subtitles	792
280.9 New environments	794
188 l warp-memhfixc.sty	797
281 memhfixc	797
189 l warp-metalogo.sty	797
282 metalogo	797
190 l warp-mhchem.sty	798
283 mhchem	798
191 l warp-microtype.sty	800
284 microtype	800
192 l warp-midfloat.sty	801
285 midfloat	801
193 l warp-midpage.sty	801
286 midpage	801

194 l warp-morefloats.sty	802
287 morefloats	802
195 l warp-moreverb.sty	802
288 moreverb	802
196 l warp-morewrites.sty	803
289 morewrites	803
197 l warp-mparhack.sty	804
290 mparhack	804
198 l warp-multicol.sty	804
291 multicol	804
199 l warp-multirow.sty	805
292 multirow	805
292.1 Multirow	806
292.2 Combined multicolumn and multirow	807
200 l warp-multitoc.sty	808
293 multitoc	808
201 l warp-nameref.sty	809
294 nameref	809
202 l warp-natbib.sty	809
295 natbib	809
203 l warp-nccfancyhdr.sty	810

296 nccfancyhdr	810
204 l warp-needspace.sty	811
297 needspace	811
205 l warp-newclude.sty	811
298 newclude	811
206 l warp-newunicodechar.sty	811
299 newunicodechar	811
207 l warp-nextpage.sty	812
300 nextpage	812
208 l warp-nicefrac.sty	812
301 nicefrac	812
209 l warp-nonfloat.sty	813
302 nonfloat	813
210 l warp-nonumonpart.sty	813
303 nonumonpart	813
211 l warp-nopageno.sty	813
304 nopageno	813
212 l warp-nowidow.sty	813
305 nowidow	813

213 l warp-ntheorem.sty	814
306 ntheorem	814
306.1 Limitations	814
306.2 Options	815
306.3 Remembering the theorem style	815
306.4 HTML cross-referencing	819
306.5 \newtheoremstyle	819
306.6 Standard styles	819
306.7 Additional objects	821
306.8 Renewed standard configuration	821
306.9 amsthm option	823
306.10 Ending a theorem	825
306.11 \NoEndMark	825
306.12 List-of	825
306.13 Symbols	826
306.14 Cross-referencing	827
214 l warp-overpic.sty	827
307 overpic	827
215 l warp-pagegrid.sty	828
308 pagegrid	828
216 l warp-pagenote.sty	828
309 pagenote	828
217 l warp-pagesel.sty	828
310 pagesel	828
218 l warp-paralist.sty	828
311 paralist	828
219 l warp-parnotes.sty	829
312 parnotes	829

220 l warp-parskip.sty	830
313 parskip	830
221 l warp-pbox.sty	830
314 vbox	830
222 l warp-pdflandscape.sty	831
315 pdflandscape	831
223 l warp-pdfpages.sty	831
316 pdfpages	831
224 l warp-pdfprivacy.sty	834
317 pdfprivacy	834
225 l warp-pdfrender.sty	834
318 pdfrender	834
226 l warp-pdfsync.sty	834
319 pdfsync	834
227 l warp-pdftricks.sty	835
320 pdftricks	835
228 l warp-pdfx.sty	836
321 pdfx	836
229 l warp-pfnote.sty	836

l warp	38
322 pfnote	836
230 l warp-phfqit.sty	836
323 phfqit	836
231 l warp-placeins.sty	837
324 placeins	837
232 l warp-prelim2e.sty	837
325 prelim2e	837
233 l warp-prettyref.sty	837
326 prettyref	837
234 l warp-preview.sty	838
327 preview	838
235 l warp-psfrag.sty	838
328 psfrag	838
236 l warp-psfragx.sty	839
329 psfragx	839
237 l warp-pst-eps.sty	839
330 pst-eps	839
238 l warp-pstool.sty	840
331 pstool	840

239 l warp-pstricks.sty	841
332 pstricks	841
240 l warp-quotchap.sty	841
333 quotchap	841
241 l warp-quoting.sty	842
334 quoting	842
242 l warp-ragged2e.sty	843
335 ragged2e	843
243 l warp-realscripts.sty	843
336 realscripts	843
244 l warp-refcheck.sty	844
337 refcheck	844
245 l warp-register.sty	845
338 register	845
246 l warp-relsize.sty	845
339 relsize	845
247 l warp-repeatindex.sty	847
340 repeatindex	847
248 l warp-resizegather.sty	848

l warp	40
341 resizegather	848
249 l warp-romanbar.sty	848
342 romanbar	848
250 l warp-romanbarpagenumber.sty	848
343 romanbarpagenumber	848
251 l warp-rotating.sty	849
344 rotating	849
252 l warp-rotfloat.sty	849
345 rotfloat	849
253 l warp-savetrees.sty	850
346 savetrees	850
254 l warp-scalefnt.sty	850
347 scalefnt	850
255 l warp-schemata.sty	851
348 schemata	851
256 l warp-scrextend.sty	851
349 scrextend	851
257 l warp-scrhack.sty	854
350 scrhack	854

258 l warp-scrlayer.sty	855
351 scrlayer	855
259 l warp-scrlayer-notecolumn.sty	856
352 scrlayer-notecolumn	856
260 l warp-scrlayer-scrpage.sty	857
353 scrlayer-scrpage	857
261 l warp-section.sty	858
354 section	858
262 l warp-sectionbreak.sty	859
355 sectionbreak	859
263 l warp-sectsty.sty	859
356 sectsty	859
264 l warp-setspace.sty	860
357 setspace	860
265 l warp-shadow.sty	861
358 shadow	861
266 l warp-showidx.sty	862
359 showidx	862
267 l warp-showkeys.sty	862
360 showkeys	862

268 l warp-sidecap.sty	862
361 sidecap	862
269 l warp-sidenotes.sty	863
362 sidenotes	863
270 l warp-SIunits.sty	865
363 SIunits	865
271 l warp-siunitx.sty	865
364 siunitx	865
272 l warp-soul.sty	871
365 soul	871
273 l warp-soulpos.sty	873
366 soulpos	873
274 l warp-soulutf8.sty	873
367 soulutf8	873
275 l warp-splitidx.sty	874
368 splitidx	874
276 l warp-srcltx.sty	875
369 srcltx	875
277 l warp-srctex.sty	876
370 srctex	876

278 l warp-stabular.sty	876
371 stabular	876
279 l warp-stffloats.sty	877
372 stffloats	877
280 l warp-subfig.sty	877
373 subfig	877
281 l warp-subfigure.sty	882
374 subfigure	882
282 l warp-supertabular.sty	883
375 supertabular	883
283 l warp-syntonly.sty	884
376 syntonly	884
284 l warp-t1enc.sty	885
377 t1enc	885
285 l warp-tables.sty	885
378 tables	885
286 l warp-tabularx.sty	885
379 tabularx	885
287 l warp-tabulary.sty	886
380 tabulary	886

288 l warp-textarea.sty	886
381 textarea	886
289 l warp-textcomp.sty	887
382 textcomp	887
382.1 Limitations	887
382.2 Package loading	887
382.3 HTML symbols	887
382.3.1 pdf ^L T _E X symbols	888
382.3.2 X ^L T _E X and Lua ^L T _E X symbols	888
382.4 HTML dicrotics	889
290 l warp-textfit.sty	890
383 textfit	890
291 l warp-textpos.sty	891
384 textpos	891
292 l warp-theorem.sty	891
385 theorem	891
385.1 Remembering the theorem style	892
385.2 CSS patches	893
293 l warp-thinsp.sty	895
386 thinsp	895
294 l warp-threadcol.sty	896
387 threadcol	896
295 l warp-threeparttable.sty	896
388 threeparttable	896

296 l warp-thumb.sty	897
389 thumb	897
297 l warp-thumbs.sty	897
390 thumbs	897
298 l warp-tikz.sty	898
391 tikz	898
299 l warp-titleps.sty	899
392 titleps	899
300 l warp-titleref.sty	903
393 titleref	903
301 l warp-titlesec.sty	903
394 titlesec	903
302 l warp-tocletoc.sty	905
395 titletoc	905
303 l warp-titling.sty	907
396 titling	907
304 l warp-toctbasic.sty	912
397 toctbasic	912
305 l warp-toctbibind.sty	912
398 toctbibind	912

306 l warp-tocenter.sty	914
399 tocenter	914
307 l warp-tocloft.sty	915
400 tocloft	915
308 l warp-tocstyle.sty	921
401 tocstyle	921
309 l warp-todo.sty	922
402 todo	922
310 l warp-todonotes.sty	923
403 todonotes	923
311 l warp-transparent.sty	925
404 transparent	925
312 l warp-trimclip.sty	925
405 trimclip	925
313 l warp-trivfloat.sty	926
406 trivfloat	926
406.1 Combining \newfloat, \trivfloat, and algorithmicx	927
314 l warp-turnthepage.sty	927
407 turnthepage	927
315 l warp-typearea.sty	927

408 typearea	927
316 l warp-ulem.sty	928
409 ulem	928
317 l warp-underscore.sty	930
410 underscore	930
318 l warp-units.sty	930
411 units	930
319 l warp-upref.sty	931
412 upref	931
320 l warp-url.sty	931
413 url	931
321 l warp-uspace.sty	932
414 uspace	932
322 l warp-verse.sty	932
415 verse	932
323 l warp-verbars.sty	934
416 verbars	934
324 l warp-vmargin.sty	934
417 vmargin	934

325 l warp-vowel.sty	935
418 vowel	935
326 l warp-vpe.sty	936
419 vpe	936
327 l warp-vwcol.sty	936
420 vwcol	936
328 l warp-wallpaper.sty	938
421 wallpaper	938
329 l warp-wasysym.sty	939
422 wasysym	939
330 l warp-watermark.sty	939
423 watermark	939
331 l warp-widows-and-orphans.sty	939
424 widows-and-orphans	939
332 l warp-wrapfig.sty	940
425 wrapfig	940
333 l warp-xbmks.sty	941
426 xbmks	941
334 l warp-xcolor.sty	941

427 xcolor	941
427.1 Limitations	942
427.2 Xcolor definitions: location and timing	942
427.3 Package loading	944
427.4 Remembering and restoring original definitions	944
427.5 HTML color style	945
427.6 HTML border	946
427.7 High-level macros	946
427.8 Row colors	951
 335 l warp-xellipsis.sty	 952
428 xellipsis	952
 336 l warp-xfrac.sty	 953
429 xfrac	953
 337 l warp-xltabular.sty	 956
430 xltabular	956
 338 l warp-xltxtra.sty	 956
431 xltxtra	956
 339 l warp-xmpincl.sty	 957
432 xmpincl	957
 340 l warp-xpiano.sty	 957
433 xpiano	957
 341 l warp-xtab.sty	 958
434 xtab	958
 342 l warp-xunicode.sty	 960

435 xunicode	960
343 l warp-xurl.sty	960
436 xurl	960
344 l warp-xy.sty	960
437 xy	960
345 l warp-zwpagelayout.sty	961
438 zwpagelayout	961
346 l warp-patch-komascript.sty	963
439 patch-komascript	963
347 l warp-patch-memoir.sty	965
440 patch-memoir	965
440.1 Packages	966
440.2 Preliminary setup	967
440.3 Laying out the page	967
440.4 Text and fonts	970
440.5 Titles	971
440.6 Abstracts	971
440.7 Document divisions	971
440.8 Pagination and headers	974
440.9 Paragraphs and lists	975
440.10 Contents lists	976
440.11 Floats and captions	981
440.12 Page notes	984
440.13 Decorative text	986
440.14 Poetry	986
440.15 Boxes, verbatims and files	986
440.16 Cross referencing	987
440.17 Back matter	988
440.18 Miscellaneous	989
440.19 Ccaption emulation	990
440.20 Final patchwork	992

Change History	993
Index of Objects	1018
General Index	1038
Troubleshooting Index	1042
Index of Indexes	1047

List of Figures

1	tutorial.tex listing	90
---	--------------------------------	----

List of Tables

1	l ^A T _E X–HTML generation — l warp package — Supported features	73
2	Required software programs	82
3	Files created along with the print version	92
4	l warp package options	109
5	HTML settings	113
6	Literal character macros	171
7	Section HTML headings for word-processor conversion	180
8	Section depths and HTML headings	193
9	Tabular baseline	421
10	Tabular HTML column conversions	421
11	Cross-referencing data structures	468
12	Float data structures	479
13	AMSthm package—CSS styling of theorems and proofs	608
14	Ntheorem package—CSS styling of theorems and proofs	814
15	Theorem package—CSS styling of theorems and proofs	892

2 Updates

The following is a summary of updates to **l warp**, highlighting new features and any special changes which must be made due to improvements or modifications in **l warp** itself.

For a detailed list of the most recent changes, see the end of the Change History on page 1017.

v0.61: Custom compilation, EPS-related packages, documentation, indexes.

docs	<ul style="list-style-type: none"> • Split index into multiple indexes. See page 1047. • Improved documentation regarding font selection. See section 8.2. • Added documentation regarding debugging options. See section 33. • Added documentation regarding HTML entities inside program listings. See section 9.2.1. 						
custom compiling	<ul style="list-style-type: none"> • Added options to specify the shell commands to execute for <code>l warpmk print</code> and <code>l warpmk html</code>, allowing the use of l warp with perltx, pythontex, etc. If not specified, these are set automatically depending on the L^AT_EX engine, <code>--shell-escape</code>, and l warp options. See section 10. 						
⚠ changed names	<ul style="list-style-type: none"> • <u>Changed macro names to match <code>\displaymathother</code>, <code>\displaymathnormal</code>:</u> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center; width: 50%;">Old</th><th style="text-align: center; width: 50%;">New</th></tr> </thead> <tbody> <tr> <td style="text-align: center;"><code>\StartDynamicMath</code></td><td style="text-align: center;"><code>\inlinemathother</code></td></tr> <tr> <td style="text-align: center;"><code>\StopDynamicMath</code></td><td style="text-align: center;"><code>\inlinemathnormal</code></td></tr> </tbody> </table> 	Old	New	<code>\StartDynamicMath</code>	<code>\inlinemathother</code>	<code>\StopDynamicMath</code>	<code>\inlinemathnormal</code>
Old	New						
<code>\StartDynamicMath</code>	<code>\inlinemathother</code>						
<code>\StopDynamicMath</code>	<code>\inlinemathnormal</code>						
fixes	<ul style="list-style-type: none"> • Fix: Paragraph tags in a tabular. • Fix: supertabular and xtab captions. • Fix: DVI L^AT_EX <code>\includegraphics</code> EPS images. • Fix: newfloat lists. • Fix: CSS footnotes text align, minipage tabular and footnote margins. 						
packages	<ul style="list-style-type: none"> • Added epsfig, psfrag, psfragx, pstool. • Added copyrightbox, pdfprivacy, thinsp, threadcol, uspace. • Added chkfloat, cmdtrack, dprogress, lua-visual-debug, refcheck, srcltx, srctex, vpe, xbmks. 						
	<p>v0.60: Fixes for longtable, listings.</p>						
fixes	<ul style="list-style-type: none"> • longtable, etc.: Fixes for slowdown and memory management for very long tables. • listings: Fix for HTML entities, and also when used inside a list. • diagbox: Fix for incorrect HTML par tags. 						
packages	<ul style="list-style-type: none"> • Added 2up, booklet. • Added bophook, draftfigure, fullminipage, grid-system, layaureo. 						

- Added **leading**, **widows-and-orphans**.
- Added **fancytabs**, **thumb**, **thumbs**.

v0.59: DVI **latex**, MATHJAX, **asymptote**, **pdftricks** and **pstricks**, **epstopdf**, **brqen**.

⚠ Reset the configuration

- Due to changes in **lwarpmk**, **recompile any existing project a single time** using **pdflatex filename.tex** or similar, after which **lwarpmk** may then be used with the new configuration files.

lwarpmk

- Added an error if **lwarpmk.conf**'s format has changed and the document must be recompiled.
- Added a warning if the **lwarpmk.conf** configuration file appears to be for the wrong operating system, in case files are transferred between systems.
- Added

lwarpmk epstopdf <list-of-EPS-files>

to quickly convert a document's EPS images to PDF or SVG. See section [9.7](#).

dvi latex

- Added support for DVI **latex**. See section [8.3](#).

latexmk

- Fix for --shell-escape with **latexmk**.

math

- Updated MathJax script to v2.7.4.
- Fix: Mathjax chapter number removed from non-numeric tagged equations.
- Added MathJax support for **nicefrac**, **units**.
- Fix for \[and \] with \displaymathnormal.

images

- Fix for \includegraphics filename expansion.

• \includegraphics now works with .pdf and .eps filename extensions.

packages

- Moved **amsmath** out of the **lwarf** core.
- Fix for **chemformula** \NMR.
- Added **asymptote**, **pdftricks**, **pstricks**, **pst-eps**.
- Added **breqn**, **Slunits**.
- Added **bxpapersize**, **canoniclayout**, **draftcopy**, **fnbreak**, **nccfancyhdr**.
- Added **accsupp**, **axessibility**.
- Added **xunicode**.
- Improved and now supports **epstopdf**.
- Tested to work as-is: **eepic**, **sepfootnotes**.

docs

- Added information about setting up a development version of **lwarf**.

v0.58: Extensive improvements in indexing, glossaries. Adds PDF-inclusion packages.

⚠ Reset the configuration

- Due to changes in **lwarpmk**, recompile any existing project a single time using `pdflatex filename.tex` or similar, after which **lwarpmk** may then be used with the new configuration files.

lwarpmk
glossaries

- **lwarpmk**: Added the `-p` option to specify the project name.
- **lwarpmk**: Now uses **makeglossaries** for glossary generation, allowing the processing of multiple glossaries at once.
- Added **lwarf** option `GlossaryCmd` to specify the shell command used by `lwarpmk printglossary` and `lwarpmk htmlglossary`. Defaults to **makeglossaries**.
- Docs: Extra indexing options. See section 9.5.11.
- Added support for **makeindex**. (Previously supported only **xindy**.) Also added indexing packages listed below.
- Added **lwarf** options `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to specify shell commands used by `lwarpmk printindex`, `lwarpmk htmlindex`, and **latexmk**. May be preset with the `makeindex` or `xindy` **lwarf** options. See section 8.3.
- Added **lwarf** options `makeindex` and `xindy` to set `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to sensible values for a typical single index. See section 8.3.
- Added **lwarf** option `makeindexStyle` to tell **lwarpmk** to use a custom style instead of `lwarf.ist`. See section 9.5.17.
- Fix for index entries with `\see`, `\seealso`, `\emph`, `\textbf`, etc.
- Replaced each `\csuse` with `\cnameuse` for improved error detection.
- Additional internal print/HTML macro selection improvements.
- Fix: `\printindex` finishes pending `\index` writes first.
- Fixes for **memoir**: `makeidx`, `ccaption`, multiple indexes, `\specialindex`.
- Fixes for **komascript**: Indexing improvements.
- Added `imakeidx`, `index`, `repeatindex`, `splitidx`.
- Added `attachfile`, `attachfile2`, `intopdf`, `pdffpages`, `pdfx`.
- Added `cases`.
- Tested to work as-is: `notes2bib`, `hvindex`.

v0.57: `algorithm2e`, `float` styles, tabular packages, internal improvements.

MathJax
math macros

- Added support for MathJax equations with `\footnote`, `\footnotemark`.
- Added `\StartDefiningMath` and `\StopDefiningMath` for use when defining macros in the preamble which contain `$`. See section 9.6.6.

- dynamic math**
 - ⚠ new name**
 - lateximage alt tags**
 - misc. fixes**
 - packages**
 - v0.56:** Shell escape, tabular packages.
 - lwarfmk**
 - tabular**
 - misc. fixes**
- Added `\inlinemathother` and `\inlinemathnormal` to delimit math expressions which depend on a variable condition such as a counter. Such expressions will not be hashed for reuse, and will be converted to SVG math images even when MathJax is enabled. See section 9.6.7.
- Renamed `\EndDefiningTabulars` to `\StopDefiningTabulars`.
- Improved localization for `lateximage` HTML alt tags. For SVG math images, the alt tag under some conditions will be set to `\mathimagername`, which defaults to “math image”. For packages, the alt tag is set using the package name followed by `\packagediagramname`, which defaults to “diagram”. Ex:
- ```
(-xy- diagram)
```
- See section 8.4.
- Fix: Improved print/HTML macro selection.
  - Fix: `\href` text catcodes.
  - Fix: `\subref` text.
  - Fixes: Colored `\rule` and `\boxframe`.
  - **float, rotfloat:** Adds support for float styles `ruled` and `boxed`.
  - **float:** Fix: Do not create `\l@<type>` until `\listof` is used.
  - **marginnote:** Fix: Long optional argument.
  - **ellipsis:** Adds `\midwordellipsis`.
  - **breakurl:** Fix for text catcodes.
  - Added `algorithm2e`, `register`, `ltablex`, `xltabular`, `xellipsis`, `trimclip`, `errata`, `vowel`, `xpiano`.
  - Prevents **glossary**.
  - Tested to work as-is with `gauss`, `phonrule`, `piano`, `Slunits`, `tikzcodeblocks`.
- Added
- ```
lwarfmk pdftosvg <list-of-PDF-files>
```
- to quickly convert a document’s PDF images to SVG, for use with HTML. See section 9.7.
- Added support for `--shell-escape`. See section 8.1.
 - Added support for `array` w and W columns.
 - Fix: `\multicolumn` parameter handling.
 - Added support for double `\hlines`, `\midrules`, and vertical rules.
 - Added support for `arydshln` dashed lines with `HTML tabular`, but reverts to plain rules for `lateximage` and `SVG math array`.
 - Fix: `\thinspace`.

- packages**
- Fix: **paralist** compact environments.
 - Added **parnotes**, **quoting**, **lua-check-hyphen**, **toccenter**, **underscore**.
 - Tested to work as-is with **babelbib**, **bibunits**, **bodegraph**, **fast-diagram**, **nicematrix**, **structmech**.

v0.55: Various fixes.

- misc fixes**
- Fix: Extraneous space in file links, which also prevented **Calibre EPUB** conversions.
 - Fix: Float optional argument regression.
 - Fix: \ForceHTMLTOC with \phantomsection.
 - Fix: Overfull boxes in **latexitimages**.
 - Fix: QED symbols in **latexitimage**.
- packages**
- **koma-script**: Fix: Figure with \centering, etc.
 - Added **clrdblpfg**.

v0.54: Float \centering, improved image checks.

⚠ Reset the configuration

- Due to changes in **lwarfmk**, **recompile any existing project a single time** using **pdflatex filename.tex** or similar, after which **lwarfmk** may then be used with the new configuration files.

lwarfmk

- **lwarfmk** **limages** checks for the presence of the HTML version of the document and valid image references before attempting to create the **latexitimages**.

Bn_TE_X

- **lwarfmk**: Improved error message if configuration file does not exist.

polyglossia

macros in section names

document encoding

⚠ New and revised encoding options

- Added documentation for avoiding error with BibTeX and \etalchar. See section [9.5.9](#).
- Added documentation regarding **polyglossia**. See section [9.13.4](#).
- Added documentation regarding the use of macros in section names. See section [9.1](#).

- Renamed and added package options:

Old Package Option	New Package Option
xdyFilename	xindyStyle
IndexLanguage	xindyLanguage
--	xindyCodepage
--	pdftotextEnc

Use these options along with **inputenc** or **inputenx** to process documents in an encoding other than UTF-8. See section [8.2](#).

floats with `\centering`, etc.

- Floats now honor `\centering`, `\raggedright`, `\raggedleft`, and their `ragged2e` equivalents, when placed directly after:

```
\begin{floattype}
\centering
```

misc. fixes

- `tikz`: `\pgfpicture`, `fit`, `align`, `font`.
- `ragged2e`: `\centering` etc.
- `hyperref`: `\hypertarget` was creating duplicate of `\label`.
- `hyperref`: Active chars inside `\hyperref`, `\hyperlink`.
- `hyperref`: `\ref` inside `\hyperlink` caused a nested HTML link.
- `glossaries`: Fix when not using `babel` or `polyglossia`.
- `textcomp`: `\textperthousand`.
- L^AT_EX core verse environment: line spacing.
- Removed `\citetitle`, adjusted `\attribution`.
- `memoir`: Minor update for v3.7g.
- Added `inputenx`, `bibunits`, `chngpage`, `forest`, `magaz`, `gridset`.
- Prevents loading `ae`, `aecc`, `t1enc`, and `wasyssym`.



packages

v0.53: Improved image checks.

l warpmk

- `l warpmk`: Added a warning about corrupted images due to the need to recompile the document one more time.
- `l warpmk`: Added the `l warpmk cleanimages` command.
- Added documentation for `l warpmk cleanimages` and `l warpmk pdftohtml`.

v0.52: Improved footnotes, SVG math.

documentation

- Improved install instructions regarding `l warp_baseline_marker.png`.
- Added documentation regarding footnotes in section headings, and footnotes with `\VerbatimFootnotes` from `fancybox`, `fancyvrb`. See section 9.4.4.
- Added documentation regarding font selection when using X^AT_EX or LuaL^AT_EX with `fontspec` and traditional font packages. See section 8.2.

SVG math

- Fix: Limit the number of background tasks when generating `lateximages`.
- Added user-adjustable SVG math font scaling. See section 77.3.
- Added warnings if `l warp_baseline_marker.png` is not present, or if `graphicx` or `graphics` is not loaded.
- Improved `\ensuremath` hashing expansion.
- Fix: `equation*` with `split`.
- tabbing now works inside a `lateximage`. Use for math in tabbing.

- MathJax
 - Fix: MathJax script was not executing in some conditions.
 - Added `\CustomizeMathJax` to add custom functions. See section 9.6.
 - footnotes
 - Fix: Footnote numbering when using `HTMLDebugComments`.
 - Fix: Footnote paragraph tags.
 - Fix: `FootnoteDepth` defaults to `\subsubsection`.
 - misc. fixes
 - Fix: `\kill` in a `lateximage`.
 - Fix: `\FileDepth`, misc. others, when input encoding is not `utf8`.
 - Fix: `\texorpdfstring` in a section name.
 - packages
 - **hyperref** emulation: Fix for #, %, &, ~, _ characters in URLs.
 - **fancybox**, **fancyvrb**: Initial support for `\VerbatimFootnotes`.
 - **nicefrac**: Added with fix for `\ensuremath`.
 - **graphicx**: Fix for option defaults. Added v1.1a/b options.
 - **endfloat**: Updated for v2.6.
 - **url**: Fixes for active characters.
- v0.51:** Improved SVG math, added numerous chemistry packages.
- documentation
 - Docs: Added [Things to avoid](#).
 - Docs: Added to [Converting an existing document](#).
 - Docs: Multiple authors and affiliations with custom classes. See section 9.5.1.
 - Docs: **tikz** with matrices. See section 9.7.1.
 - SVG math
 - Improved SVG math baseline.
 - Improved SVG math font and color.
 - Faster SVG math rendering.
 - Improved support for display math containing complicated math objects, such as **tikz-cd**. See section 9.6.8.
 - Fix: `\addcontentsline` inside SVG math.
 - Fix: SVG math containing an embedded `lateximage`.
 - MathJax
 - MathJax now handles `\ensuremath` in expressions.
 - misc. fixes
 - Fix: Added `alignat` environment.
 - Fix: **afterpackage** no longer required, which conflicted with **scrfile**.
 - Fix: **titling** \thanks mark.
 - Fix: **fancybox** improvements.
 - Fix: **tikz** \tikz macro. (Previously only the `tikzpicture` environment worked.)
 - Fix: **tikz** with optional argument.
 - packages
 - Added **mhchem**, **chemfig**, **chemformula**, **chemmacros**, **chemnum**, **chemgreek**, **epstopdf-base**, **grid**, **ltxgrid**.

v0.50: Improved svg math.

- | | |
|-----------------------------|--|
| svg math | <ul style="list-style-type: none"> • SVG math and other <code>lateximages</code> now are converted to SVG using parallel background tasks, utilizing all available CPU cores. • Inline SVG math image file names now are MD5 hashes made from their source <code>TeX</code> code. Identical inline math expressions, such as multiple instance of <code>\$x\$</code>, now share a single image file. This reduces the number of images to store, transmit, process, and display. Each image file is only converted to SVG a single time, and reused if it already exists. Display math and other forms of SVG image such as <code>picture</code> and <code>Tikz</code> still use individual image files which are recreated each time <code>lwarpmk limages</code> is run. • Fixes: SVG math and/or <code>\underline</code> in a sectioning file name. • Improved SVG display math and tags. • Improved SVG math and <code>siunitx</code> alt tags. • Improved <code>siunitx</code> units. • Fix: <code>\ensuremath</code> with MathJax now creates a <code>lateximage</code>. • Fix: <code>\centering</code>, etc. in SVG math, <code>lateximage</code>, <code>Tikz</code>. |
| misc. fixes | <ul style="list-style-type: none"> • Fix: Made various macros robust, additionally fixing <code>authblk</code>. • Fix: <code>ntheorem</code> if neither standard nor <code>amsthm</code> selected. • Fix: <code>listings</code>: Improved column alignment. • Fix: Load <code>fontspec</code> if necessary. |
| packages | <ul style="list-style-type: none"> • Added <code>xy</code>, <code>epstopdf</code>, <code>diagbox</code>, <code>pbox</code>, <code>bytefield</code>, <code>axodraw2</code>, <code>phfqt</code>, <code>schemata</code>, <code>dblfloatfix</code>, <code>nonfloat</code>, <code>morefloats</code>. |

v0.49:

- | | |
|----------------------------|---|
| tabular | <ul style="list-style-type: none"> • Added <code>xcolor \rowcolors</code>. • Fix: <code>\noalign</code> inside a <code>tabular</code>. |
| math | <ul style="list-style-type: none"> • Fix: <code>\eqref</code> in a caption. |
| misc fixes | <ul style="list-style-type: none"> • Fix: Incorrect PDF font size changes caused occasional HTML corruption. • Fix: <code>printlen</code> changes are now grouped for HTML output. |
| packages | <ul style="list-style-type: none"> • Added <code>vwcol</code>, <code>verbbars</code>, <code>hyphenat</code>, <code>lineno</code>, <code>fnc lineno</code>, <code>figsize</code>, <code>hypdestopt</code>, <code>pagegrid</code>, <code>pdfrender</code>, <code>luacolor</code>, <code>resizegather</code>. |

v0.48:

- | | |
|-------------------------------|--|
| documentation | <ul style="list-style-type: none"> • Added some documentation regarding converting an existing document. See section 7. |
| cleveref | <ul style="list-style-type: none"> • Updated compatibility for new <code>cleveref</code> v0.21. |
| tabular | <ul style="list-style-type: none"> • Fix: Ignores optional tabular column arguments. |

- minor updates
 - Added `\leftline`, `\centerline`, `\rightline`.
 - Lists have improved font control via `\makelabel`.
 - Print-mode `lateximage` now boxed to the natural width of its multiline contents.
 - `abstract` now allows an optional name, as required by some classes.
- math
 - Fix: Improved spacing, `\mbox`, and font sizes with SVG math, Tikz.
 - `siunitx`: Improved SVG math, fraction compatibility, color output.
- misc. fixes
 - Fix: LOF/LOT links.
 - Fix: Virtual page size grouping caused excessive PDF page breaks.
 - Fix: Parsing similar package names in a single `\usepackage`.
 - Fix: Adapts to classes without `\part`.
 - Fix: `\newline` in `\title` was causing `
` in window title.
 - Fix: `\maketitle` with `\cr`, `\crrcr`, `\noalign`, for **IEEEtran** class.
 - Fix: `xfrac` neutralized `BlockClass` and others.
 - Fix: `todonotes` and `luatodonotes`: Improved `\todototoc`.
- packages
 - Added `colortbl`, `chapterbib`, `acro`, `acronym`, `hypernat`, `hypcap`, `stfloats`, `vmargin`, `fancyheadings`.
 - `fancyref`: Now directly supported.

v0.47:

- math
 - Improved SVG math baseline and sizing.
 - Fixes: `svgmath` in captions, subcaptions, `\nameref`.
 - Fixes: Line wrap at hyphen in HTML output.
- packages
 - Added `endheads`, `multitoc`, `sectionbreak`, `blowup`, `xurl`.

v0.46:

- ⚠ name change
- misc. fixes
 - `\PrintStack` changed to `\LWRPrintStack`.
 - Fix: Empty lines between `tabular` rows.
 - Fix: Stack unnesting.
 - Fix: SVG math and `lateximages` in numerous situations.
 - Fix: Spaces in `\usepackage`.
 - Fix: Now allows MATHJAX inside `verse`.

v0.45:

- | | |
|----------------------------------|---|
| documentation | <ul style="list-style-type: none">• Improved MiKTeX install instructions.• Improved graphics and epstopdf instructions.• Updates to the Introduction. |
| memoir | <ul style="list-style-type: none">• Added memoir, memhfixc. See section 9.12. |
| cross-references | <ul style="list-style-type: none">• Fix: Now allows underscores in labels.• Fix: <code>_</code> and <code>\<blank></code> in section/file names. |
| math | <ul style="list-style-type: none">• Fix: Now allows MATHJAX inside tabbing. |
| bibliography | <ul style="list-style-type: none">• Fix: Bibliography \em names.• Added cite, natbib, backref. (Also works as-is with biblatex.) |
| misc. fixes | <ul style="list-style-type: none">• Fix: Empty lines between tabular rows.• Fix: “Improper \prevdepth” with minipages, lists.• Fix: Incorrect svg math and lateximages with subfig.• Fix: Lateximages from incorrect pages with Mathjax.• Fix: Missing sidetoc if using listings.• Fix: Added an array emulation package. |
| packages | <ul style="list-style-type: none">• Added subfigure, prettyref, hanging, midpage, falter, fltrace, changebar, endfloat, continue, fwlw, turnthepage, footnpag, pagesel, textfit, titleref. |

v0.44:

- | | |
|---------------------------------------|--|
| koma-script | <ul style="list-style-type: none">• Added koma-script classes (except scrlltr2, scrjura).• Added scrextend, scrlayer, scrlayer-notecolumn, scrlayer-scrpage, scrhack, tocstyle, tocbasic. |
| HTML title and author | <ul style="list-style-type: none">• Added \HTMLTitle. Fixed web page title if \HTMLTitle empty and no \title given and not using titling package.• Fixed web page author if \HTMLAuthor is empty and \author is not given. |
| encodings | <ul style="list-style-type: none">• If using pdflatex, automatically loads T1 and UTF8 encodings. (Additional fontenc encodings may be loaded after l warp.) |
| lists | <ul style="list-style-type: none">• Added list and trivlist environments, hang. |
| tabular | <ul style="list-style-type: none">• Fix: \multicolumn alignment if formatting for a word processor.• Added ltxtable. |
| math | <ul style="list-style-type: none">• Fix: MATHJAX combined with lateximages.• algorithmicx: Improved comment symbol and floating. |
| packages | <ul style="list-style-type: none">• Completed todonotes and luatodonotes.• Added todo, easy-todo, fixmetodonotes, fixme.• Added soulutf8, soulpos, cancel. |

- Added **section**, **fancyref**, **ifoddpage**.
- Added **preview**, **atbegshi**, **watermark**.
- Improved **tocloft** \newlistof and \newlistentry.

v0.43:

- footnotes**
 - Docs: Reorganized HTML customization, added an HTML settings table. See section 8.4.
 - Added **FootnoteDepth** to control the placement of pending footnotes before section breaks. By default, pending footnotes are printed before each \subparagraph or higher.
- sectioning**
 - Fix: Expansion in section name.
- tabular**
 - Fix: Ignore spaces in tabular column specification.
 - Fix: Tabular rules at bottom or when finishing incomplete rows.
 - Fix: \multicolumn at/bang/before/after specifications, trim, and vertical rules.
 - Fix: **supertabular** and **xtab** column misalignment.
- math**
 - Fix: equation*.
 - Fix: SVG math in a section name.
 - Fix: \ref and \eqref in SVG math.
- packages**
 - Added **todonotes** and **luatodonotes** (but only disabled).
 - Added **breakurl**.
 - **hyperref**: Fix: Several macros were made robust, \Gauge added.

v0.42:

- Support \TeX !**
 - Added \TeX development support page, **Supporting \TeX development**.
- word-processor conversion**
 - ⚠️ name change
 - The boolean **FormatWordProcessor** has been renamed **FormatWP**.
 - The boolean **HTMLMarkFloats** has been renamed **WPMarkFloats**.
 - New booleans control whether to place additional marks around mini-pages, at the table of contents, at the LOF and LOT, and whether to print math as \TeX source for copy/paste into the **LibreOffice Writer TeXMaths** extension.
 - Improved formatting for numerous objects. See section 12.
- tabbing**
 - Add: **tabbing** environment.
- overpic**
 - Add: **overpic** package. See section 307.
- math**
 - Fix: Text copy/paste of **AMS** math environment numbers and names.
 - Improved \ensuremath.

- symbols**
 - MATHJAX with **siunitx**: Updated script and documentation.
 - **textcomp**: Improved \interrobangdown.
 - **realscripts**: Fix for subscripts in a **lateximage**.
 - load order**
 - **morewrites**: Enforces loading before **l warp**.
- v0.41:**
- tabular**
 - Added tabular vertical rules, subject to some limitations. See the rules section of section 9.9.
 - Improved **booktabs**: Width and trim are honored.
 - Added \mcolrowcell for empty cells inside a \multicolumnrow. **Use \mcolrowcell instead of \mrowcell for two-dimensional cells created by \multicolumnrow**. Continue to use \mrowcell for empty cells in a \multirow. See section 292.2 on page 807.
 - Fix: Unfinished tabular rows are automatically filled.
 - Fix for tabular column specifiers while using **babel-french**. (\NoAutoSpacing is activated then nullified inside the tabular, due to a conflict with the tabular column parsing code.)
 - ⚠ new syntax**
 - Added \mcolrowcell for empty cells inside a \multicolumnrow. **Use \mcolrowcell instead of \mrowcell for two-dimensional cells created by \multicolumnrow**. Continue to use \mrowcell for empty cells in a \multirow. See section 292.2 on page 807.
 - Fix: Unfinished tabular rows are automatically filled.
 - Fix for tabular column specifiers while using **babel-french**. (\NoAutoSpacing is activated then nullified inside the tabular, due to a conflict with the tabular column parsing code.)
- v0.40:**
- graphics, graphicx**
 - **graphics** and **graphicx** have been moved from the **l warp** core, and are only loaded if requested with \usepackage.
 - Improved **graphics** \graphicspath support. Multiple image directories may now be used. **Refer to .pdf files without a file extension** to allow the HTML version to use a .svg, .png, .jpg, or .gif version instead. See section 9.7.
 - **grffile** is now directly supported instead of emulated.
 - Fix for **bigdelim**, and improved documentation. See section 129.
 - Improved **LATEX** and **textcomp** symbols.
 - Fix for **LATEX** logos and \InlineClass, etc. inside a **lateximage**.
 - Fix for **xltextra** with **XATEX**.
 - Fixes for **tocbibind** with \simplechapter, etc.
 - Fixes for \multicolumnrow and \nullfonts with older versions of **multirow** and **xparse**.
 - Added \underline.
 - \includegraphics path**
 - Improved **graphics** \graphicspath support. Multiple image directories may now be used. **Refer to .pdf files without a file extension** to allow the HTML version to use a .svg, .png, .jpg, or .gif version instead. See section 9.7.
 - ⚠ image file extensions**
 - Improved **graphics** \graphicspath support. Multiple image directories may now be used. **Refer to .pdf files without a file extension** to allow the HTML version to use a .svg, .png, .jpg, or .gif version instead. See section 9.7.
 - bigdelim**
 - Fix for **bigdelim**, and improved documentation. See section 129.
 - symbols**
 - Improved **LATEX** and **textcomp** symbols.
 - fixes**
 - Fix for **LATEX** logos and \InlineClass, etc. inside a **lateximage**.
 - Fix for **xltextra** with **XATEX**.
 - Fixes for **tocbibind** with \simplechapter, etc.
 - Fixes for \multicolumnrow and \nullfonts with older versions of **multirow** and **xparse**.
 - Added \underline.
 - margins**
 - Added **adjmulticol**.
 - columns**
 - Added **cuted**, **midfloat**.
 - footnotes**
 - Added **pfnote**, **fnpos**, **dblfnote**.
 - tabular**
 - Added **stabular**, **tbls**.
 - sectioning**
 - Added **sectsty**, **anonchap**, **quotchap**.

v0.39:

title pages

⚠ \published and
\subtitle

⚠ load order

tabular

multi column/row cell

⚠ macros inside tabular

⚠ tabular defined inside
another environment

tabular

margins

page layout

- Improved the titlepage HTML code, \thanks notes, and \maketitle. **titling** is no longer required, but is still supported. The \published and \subtitle fields are no longer provided, but \AddSubtitlePublished replicates them using **titling**. See section 63.8. **authblk** is added, and should be loaded before **titling**. See section 63.
- \multirow now supports the new optional vpos argument.
- Added \multicolumnrow for combined \multicolumn and \multirow. See section 292.2.
- Tabular special cases:
 - Added \TabularMacro to mark custom macros inside tabular data cells, avoiding row corruption. See section 9.9.
 - Added \ResumeTabular for use when a tabular environment is defined inside another environment. See section 9.9.
- Added **supertabular**, **xtab**, **bigstrut**, **bigdelim**.
- Added **fullwidth**.
- Added **addlines**, **anysize**, **a4**, **a4wide**, **a5comb**, **textarea**, **zwpagelayout**, **typearea**, **ebook**.

v0.38:

forced single-pass compile

starred sections

updated tutorial

packages

font size

page numbering

front & back matter

- Added **lwarpmk print1** and **lwarpmk html1** actions to force a compile of the project a single time. Useful when multiple passes are not needed, or changes were not detected.
- Added \ForceHTMLPage and \ForceHTMLTOC to force a starred sectional unit onto its own HTML page and with its own TOC entry. See section 9.5.2.
- Modified the tutorial to use the new \ForceHTMLPage and \ForceHTMLTOC macros.
- Added **appendix**, **tocbibind**, **fncychap**, **fix2col**.
- Added **relsize**, **scalefnt**.
- Added **realscripts**, **metalogo**, **xltxtra**.
- Added **grffile**, **romanbar**.
- Added **arabicfront**, **chappg**, **nonumonpart**, **nopageno**, **romanbarpagenumber**.
- Docs: Improved description of the use of front/back matter. See section 9.5.
- Fix: **color** requests **xcolor**.
- Fix: \part for **article** class.

v0.37:

- \include for HTML**
 - \include now maintains independent .aux files for HTML versions.
- latexmk**
 - **comment**, used by **l warp**, now maintains independent cut files for print and HTML versions, helping **latexmk** to better know whether to recompile.
- accents and symbols**
 - Improved support for L^AT_EX accents, **textcomp**, **siunitx** symbols.
- babel-french**
 - Improved **babel-french** handling for load order and ~ tilde.

v0.36:

- Recorganized the documentation section regarding special cases and limitations. (Section 9)
- Improved source formatting.
- \fbox and related now use \fboxsep and \fboxrule.
- \makebox and \framebox now use width and position.
- \fcolorbox and related now work inside a **latexitimage**.
- **babel-french**: Improvements for French variants, load order, footnotes, ellipses.
- Improved footnote numbering. **latexitimage** footnotes now appear as regular footnotes to match the numbering of the print version. Also fixed a regression with MATHJAX.
- Improved **siunitx** units.
- Fix for filenames while using MATHJAX.
- Fix for \rule when **xcolor** is not loaded.
- Added **transparent**, **upref**.

v0.35: Fix: \textbf and related.

v0.34:

- ⚠ Optional arguments**
- BlockClass's optional argument has been moved in front of the mandatory argument:
 $\text{BlockClass}[style]\{class\}$ (NEW)
instead of:
 $\text{BlockClass}\{class\}[style]$ (OLD)
- This change makes it more consistent with L^AT_EX standards, and avoids problems with space between arguments.
- Likewise, \InlineClass's optional argument now comes before the mandatory arguments:
 $\text{\InlineClass}[style]\{class\}\{text\}$

⚠ Optional arguments

- spans with minipages
 - framing minipages
 - lateximage, svg math, tabular
 - eqnarray
 - verbatim packages
 - framing packages
 - list packages
 - babel-french
- Improved compatibility between spans, minipages, lists, frames, and math. Handles minipages and lists inside an HTML span, such as an `\fbox` containing a minipage, although with minimal HTML fomatting. See section 9.3.3. `\fboxBlock` is added to frame minipages, tables, and lists with full HTML formatting but no longer inline, and behaves as `\fbox` for print output. The `fminipage` environment is added for framed minipages, as an environment with full HTML formatting, and draws a framed minipage in print output. See section 9.3.5. `\fbox` and minipages now often work in SVG math and lateximages. MATHJAX supports `\fbox`, but not `\fboxBlock` nor `fminipage`.
 - Improved compatibility between `lateximage` and `minipage`, `\parbox`, `\makebox`, `\fbox`, `\framebox`, `\raisebox`, `\scalebox`, `\reflectbox`, `tabular`, `booktabs`.
 - Improved font control for `lateximagees` and `svg math`.
 - Added the `eqnarray` environments.
 - `fancyvrb` is no longer required (preloaded), but is still supported.
 - Added `verbatim` and `moreverb`.
 - Added `fancybox`, `boxedminipage2e` and `shadow`.
 - `enumitem` is no longer required, but is still supported.
 - Added `enumerate` and `paralist`.
 - `titleps` is no longer required, but is still supported.
 - Added `crop`.
 - Added `rotfloat`, `marginfit`, and several minor packages; see the change log.
 - Adds fixed-width HTML spaces around punctuation when using `babel-french`. LuaTEX does not yet use the extra punctuation spacing.

v0.33:

- Tabular @ and ! columns now havetheir own HTML columns.
- & catcode changes are localized, perhaps causing errors about the tab alignment character &, so any definitions of macros or environments which themselves contain `tabular` and & must be enclosed within `\StartDefiningTabulars` and `\StopDefiningTabulars` (previously called `\EndDefiningTabulars`). See section 41. This change is not required for the routine use of tables, but only when a table is defined inside another macro or environment, and while also using the & character inside the definition. This may include the use inside conditional expressions.
- Several math environments were incorrectly placed inline. Also, for `amsmath` with SVG math, the `fleqn` option has been removed, resulting in improved spacing for aligned equations.
- Bug fixes; see the changelog.

v0.32: Bug fixes; no source changes needed:

- **lwarpmk** has been adjusted to work with the latest **luatex**.
- Spaces in the `\usepackage` and `\RequirePackage` package lists are now accepted and ignored.
- Fix for the **glossaries** package and `\glo@name`.

v0.31: Bug fix; no source changes needed:

- Improved compatibility with **keyfloat**, including the new `keywrap` environment.

v0.30:

 **l warp-newproject**

- **l warp-newproject** has been removed, and its functions have been combined with **l warp**.

To modify existing documents, remove from the document source:

```
\usepackage{l warp-newproject}
```

The **l warp** package now produces the configuration files during print output, and also accepts the option `lwarpmk` if desired.

 **HTML setup changes.**

- A number of macros related to HTML settings have been converted to options, and other macros and options have been renamed to create a consistent syntax:

Old Macro	New Package Option
<code>\HomeHTMLFileName</code>	<code>HomeHTMLfilename</code>
<code>\HTMLFileName</code>	<code>HTMLfilename</code>
<code>\useLatexmk</code>	<code>latexmk</code>
<code>\warpOSwindows</code>	<code>OSWindows</code>

Old Package Option	New Package Option
<code>lwarpmklang</code> (new)	<code>xindyLanguage</code> <code>xindyStyle</code>

Old Macro	New Macro
<code>\MetaLanguage</code>	<code>\HTMLLanguage</code>
<code>\HTMLAuthor</code>	<code>\HTMLAuthor</code>
<code>\NewHTMLDescription</code>	<code>\HTMLDescription</code>
<code>\SetFirstPageTop</code>	<code>\HTMLFirstPageTop</code>
<code>\SetPageTop</code>	<code>\HTMLPageTop</code>
<code>\SetPageBottom</code>	<code>\HTMLPageBottom</code>
<code>\NewCSS</code>	<code>\CSSFilename</code>

- Per the above changes, in existing documents, modify the package load of **lwarf**, such as:

```
\usepackage[  
    HomeHTMLFilename=index,  
    HTMLFilename={},  
    xindyLanguage=english  
]{lwarf}
```

- The file `lwarf_html.xdy` has been renamed `lwarf.xdy`. To update each document's project:
 1. Make the changes shown above.
 2. Recompile the document in print mode. This updates the project's configuration files, and also generates the new file `lwarf.xdy`.
 3. The old file `lwarf_html.xdy` may be deleted.
- The new **lwarf** package option `xindyStyle` may be used to tell **lwarpmk** to use a custom `.xdy` file instead of `lwarf.xdy`. See section 9.5.18.
- Improvements in index processing:
 - `xindy`'s language is now used for index processing as well as glossary.
 - Print mode without `latexmk` now uses `xindy` instead of `makeindex`.
 - `texindy/xindy` usage depends on `pdflatex` vs `xelatex`, `lualatex`.
 - For `pdflatex` and `texindy`, the `-C utf8` option is used. This is supported in modern distributions, but a customized `lwarpmk.lua` may need to be created for use with older distributions.

v0.29:

- Add: `lwarpmklang` option for **lwarf-newproject** and **lwarf**. Sets the language to use while processing the glossary. (As of v0.30, this has been changed to the `IndexLanguage` option.) (As of v0.54, this has been changed to the `xindyLanguage` option.)
- Fix: `\includegraphics` when no optional arguments.

v0.28:

- `\HTMLAuthor {<name>}` assigns HTML meta author if non-empty. Defaults to `\theauthor`.
- Boolean `HTMLDebugComments` controls whether HTML comments are added for closing `<div>`s, opening and closing sections, etc.
- Boolean `FormatEPUB` changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.
- Boolean `FormatWordProcessor` changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments. Name changed to `FormatWP` as of v0.42.

- Boolean `HTMLMarkFloats` adds text marks around floats only if the boolean `FormatWordProcessor` is true. These make it easier to identify float boundaries, which are to be manually converted to word-processor frames. Name changed to `WPMarkFloats` as of v0.42.
- Updated for the new `MATHJAX` CDN repository.
- Adds `tabulary`.
- Supports the options syntax for `graphics`.
- Improved index references, now pointing exactly to their target.
- Adds `glossaries`. `lwarpmk` is modified to add `printglossary` and `htmlglossary` actions.

3 Introduction

The **l warp** project aims to allow a rich \LaTeX document to be converted to a reasonable HTML5 interpretation, with only minor intervention on the user's part. No attempt has been made to force \LaTeX to provide for every HTML-related possibility, and HTML cannot exactly render every possible \LaTeX concept. Where compromise is necessary, it is desirable to allow the print output to remain typographically rich, and compromise only in the HTML conversion.

Several “modern” features of HTML5, CSS3, and SVG are employed to allow a fairly feature-rich document without relying on the use of JAVASCRIPT. Limited testing on older browsers shows that these new features degrade gracefully.

l warp is a native \TeX package, and operates by either patching or emulating various functions. Source-level compatibility is a major goal, but occasional user intervention is required in certain cases.

As a package running directly in \TeX , **l warp** has some advantages over other methods of HTML conversion. \TeX itself is still used, allowing a wider range of \TeX trickery to be understood. Lua expressions are still available with LuaTeX . Entire categories of \TeX packages work as-is when used with **l warp**: definitions, file handling, utilities, internal data structures and calculations, specialized math-mode typesetting for various fields of science and engineering, and anything generating plain-text output. Blocks of PDF output may be automatically converted to SVG images while using the same font and spacing as the original print document, directly supporting *Tikz* and *picture*. Numerous packages are easily adapted for HTML versions, either by loading and patching the originals, or by creating nullified or emulated replacements, and all without resorting to external programming. As a result, several hundred packages have already been adapted (table 1), and an uncounted number more work as-is.

Packages have been selected according to several criteria: perceived importance, popularity lists, recent CTAN updates, CTAN topics, mention in other packages, support by other HTML conversion methods, and from sample documents taken from public archives. These include some “obsolete” packages as well.¹

Assistance is also provided for modifying the HTML output to suit the creation of EPUB documents, and for modifying the HTML output to ease import into a word processor.

¹An amazing number of decades-old packages are still in use today.

pdflatex, **xelatex**, or **lualatex** may be used, allowing **lwarf** to process the usual image formats. While generating HTML output, SVG files are used in place of PDF. Other formats such as PNG and JPG are used as-is.

SVG images may be used for math, and are also used for `picture`, `Tikz`, and similar environments. The SVG format has better browser and e-book support than MathML (as of this writing), while still allowing for high-quality display and printing of images (again, subject to potentially bug-ridden² browser support).

Furthermore, SVG images allow math to be presented with the same precise formatting as in the print version. Math is accompanied by `<alt>` tags holding the L^AT_EX source for the expression, allowing it to be copy/pasted into other documents.³ Custom L^AT_EX macros may be used as-is in math expressions, since the math is evaluated entirely inside L^AT_EX. An MD5 hash is used to combine multiple instances of the same inline math expression into a single image file, which then needs to be converted to SVG only a single time.

The MATHJAX JavaScript display engine may be selected for math display instead of using SVG images. Subject to browser support and Internet access, MATHJAX allows an HTML page to display math without relying on a large number of external image files.⁴ **lwarf** maintains L^AT_EX control for cross-referencing and equation numbering, and attempts to force MATHJAX to tag equations accordingly.

A **texlua** program called **lwarpmk** is used to process either the print or HTML version of the document. A few external utility programs are used to finish the conversion from a L^AT_EX-generated PDF file which happens to have HTML5 tags, to a number of HTML5 plain-text files and accompanying images.

lwarf automatically generates the extra files necessary for the HTML conversion, such as css and .xdy files, and configuration files for the utility **lwarpmk**. Also included is a parallel version of the user's source document, `<sourcename>-html.tex`, which selects HTML output and then inputs the user's own source. This process allows both the printed and HTML versions to co-exist side-by-side, each with their own auxiliary files.

When requesting packages during HTML conversion, **lwarf** first looks to see if it has its own modified version to use instead of the standard L^AT_EX version. These `lwarf-pagename.sty` files contain code used to emulate or replace functions for HTML output.

²FIREFOX has had an on-again/off-again bug for quite some time regarding printing svgs at high resolution.

³There seems to be some debate as to whether MathML is actually an improvement over L^AT_EX for sharing math. The author has no particular opinion on the matter, except to say that in this case L^AT_EX is much easier to implement!

⁴One SVG image file per math expression, except that duplicate inline math expressions are combined into a single file according to the MD5 hash function of its contents. A common scientific paper can easily include several thousand files, and in one case the MD5 hash cut the number of files in half and the rendering time by 30%.

3.1 Supported packages and features

Table 1 lists some of the various L^AT_EX features and packages which may be used. Many are tested to work as-is, some are patches for the original packages, and some are emulations written for source-level compatibility. Many are nullified as being irrelevant to HTML output.

Table 1: L^AT_EX–HTML generation — l warp package — Supported features

Category	Status and supported features.
Engines:	DVI L ^A T _E X, pdfL ^A T _E X, XeL ^A T _E X, LuaL ^A T _E X
Compiling:	latexmk , perltex , pythontex , make , etc.
Classes:	article , book , report , scrartcl , scrbook , scrreprt , memoir .
Koma-script:	scrextend , scrhack , scrlayer . Others as listed below.
Memoir:	memhfixc
Page layout:	2up , a4 , a4wide , a5comb , addlines , any size , atbegshi , blowup , booklet , bophook , bxpaper size , canoniclayout , clrdblpg , continue , draftcopy , draftfigure , draftwatermark , ebook , everyshi , fancyhdr , fancytabs , fullminipage , fullpage , fwlw , geometry , grid , grid-system , gridset , layaureo , leading , ltxgrid , nccfancyhdr , pagegrid , pdfprivacy , pagesel , preview , scrlayer-scrpage , textarea , threadcol , thumb , thumbs , titleps , toccenter , turnthepage , typearea , vmargin , watermark , zwpagelayout . Tested to work as-is: underlin .
Sectioning:	Adds FileDepth for splitting the HTML output. Files may be numbered sequentially or named according to section name. Common short words and punctuation are removed from the filenames. anonchap , fncychap , quotchap , section , sectionbreak , sectsty , titlesec .
Table of contents, figures, tables:	Supported, with hyperlinks. multitoc , shorttoc , titletoc , tocbasic , tocbibind , tocloft , tocstyle .
Title page:	\maketitle , titlepage , authblk , titling .
Front & back matter:	abstract , appendix .

l warp Supported Functions — continued

Category	Status
Indexing:	makeindex and xindy are supported, with hyperlinks. idxlayout , imakeidx , index , makeidx , repeatindex , splitidx . Tested to work as-is: hvindex , sepfootnotes .
Glossary:	glossaries and xindy are used.
Bibliography:	babelbib , backref , bilatex , bibunits , chapterbib , cite , hypernat , natbib . Tested to work as-is: notes2bib .
Cross-references:	bookmark , breakurl , cleveref , fancyref , hypdestopt , hyperref , prettyref , titleref , url , varioref , xurl .
Languages:	babel , polyglossia .
Margin notes:	marginfit , marginfix , scrlayer-notecolumn .
Footnotes:	Adds FootnoteDepth to print footnotes at section breaks. dblfnote , endheads , endnotes , fnbreak , fnpos , footmisc , footnote , footnpag , marginnote , nccfoots , pagenote , parnotes , pfnote , sidenote .
Math:	Converted to SVG images with HTML <alt> tags containing the L ^A T _E X source for the math expression. MATHJAX supported as an alternative. amsmath : \mathcal{M} S environments are supported. User-defined macros are available during conversion, due to native L ^A T _E X processing.
Theorems:	Native L ^A T _E X theorems, amsthm , ntheorem , theorem .
Additional math:	Math fonts via SVG images, breqn , cases , resizegather , xy . Tested to work as-is: amscd , bm , braket , delarray , guass , nicematrix , pb-diagram , tikz-cd , etc.
Display math with \\displaymathother:	Complicated math objects in display math, such as tikz-cd , etc.
Units and fractions:	nicefrac , Slunits , siunitx , units , xfrac . Tested to work as-is: Slunits .

lwrap Supported Functions — continued

Category	Status
Floats:	Appear where declared. <code>capt-of</code> , <code>caption</code> , <code>cutwin</code> , <code>dblfloatfix</code> , <code>endfloat</code> , <code>fix2col</code> , <code>flafter</code> , <code>float</code> , <code>floatflt</code> , <code>floatrow</code> , <code>filtrace</code> , <code>hypcap</code> , <code>keyfloat</code> , <code>morefloats</code> , <code>newfloat</code> , <code>nonfloat</code> , <code>placeins</code> , <code>rotfloat</code> , <code>stfloats</code> , <code>subcaption</code> , <code>subfig</code> , <code>subfigure</code> , <code>subfloat</code> , <code>trivfloat</code> , <code>wrapfig</code> .
Tabular:	<code>tabular</code> environment, <code>array</code> , <code>arydshln</code> , <code>bigdelim</code> , <code>booktabs</code> , <code>colortbl</code> , <code>diagbox</code> , <code>longtable</code> , <code>ltablex</code> , <code>ltxtable</code> , <code>multirow</code> , <code>supertabular</code> , <code>tabularx</code> , <code>tabulary</code> , <code>threeparttable</code> , <code>xltabular</code> , <code>xtab</code> .
Graphics:	<code>graphics</code> and <code>graphicx</code> . <code>\includegraphics</code> supports <code>width</code> , <code>height</code> , <code>origin</code> , <code>angle</code> , and <code>scale</code> tags, and adds <code>class</code> . References to PDF files are changed to SVG, other image types are accepted as well. <code>\rotatebox</code> and <code>\scalebox</code> are supported as well as HTML can handle. <code>rotating</code> is emulated but all objects are unrotated. <code>picture</code> , <code>tikz</code> , and <code>xy</code> are converted to an SVG image. <code>asymptote</code> , <code>epsfig</code> , <code>epstopdf</code> , <code>figsize</code> , <code>grffile</code> , <code>overpic</code> , <code>psfrag</code> , <code>psfragx</code> , <code>pst-eps</code> , <code>pstool</code> , <code>pstricks</code> . Tested to work as-is: <code>eepic</code> , <code>tikz-3dplot</code> .
<code>xcolor</code> :	Full package color names, any color models, and mixing. <code>\textcolor</code> , <code>\colorbox</code> , <code>\fcolorbox</code> . Enhanced for HTML compatibility.
Lists:	Standard L ^A T _E X environments, <code>enumerate</code> , <code>enumitem</code> , <code>hang</code> , <code>paralist</code> .
Environments:	Standard L ^A T _E X environments.
<code>minipage</code> , <code>\parbox</code> :	Some HTML5-imposed limitations. Nested minipages are supported. <code>pbox</code> .
Quotations:	<code>copyrightbox</code> , <code>csquotes</code> , <code>epigraph</code> , <code>quoting</code> , <code>verse</code> .
Verbatim:	<code>fancyvrb</code> , <code>moreverb</code> , <code>shortvrb</code> , <code>verbatim</code> .
Frames:	<code>boxedminipage2e</code> , <code>fancybox</code> , <code>framed</code> , <code>mdframed</code> , <code>shadow</code> , <code>verbbars</code> .
Multi-columns:	<code>adjmulticol</code> , <code>multicol</code> , <code>vwcol</code> .

l warp Supported Functions — continued

Category	Status
Margins:	<code>fullwidth</code> , <code>hanging</code> , <code>midpage</code> .
Line numbering:	<code>flineno</code> , <code>lineno</code> .
Acronyms:	<code>acro</code> , <code>acronym</code> .
Editorial:	<code>changebar</code> , <code>easy-todo</code> , <code>errata</code> , <code>fixme</code> , <code>fixmetodonotes</code> , <code>todo</code> , <code>todonotes</code> .
Direct formatting:	<code>\emph</code> , <code>\textsuperscript</code> , <code>\textbf</code> , etc are supported. <code>\bfseries</code> , etc. are only supported in some cases. <code>cancel</code> , <code>ellipsis</code> , <code>hyphenat</code> , <code>letrine</code> , <code>lips</code> , <code>lua-check-hyphen</code> , <code>luacolor</code> , <code>magaz</code> , <code>nowidow</code> , <code>pdfrender</code> , <code>realscripts</code> , <code>relsize</code> , <code>scalefont</code> , <code>soul</code> , <code>soulpos</code> , <code>soulutf8</code> , <code>textfit</code> , <code>thinsp</code> , <code>trimclip</code> , <code>ulem</code> , <code>underscore</code> , <code>uspace</code> , <code>widows-and-orphans</code> , <code>xellipsis</code> .
Ordinals:	<code>engord</code> , <code>fmtcount</code> , <code>nth</code> .
Text ligatures:	Ligatures for symbols are supported. Ligatures for f, q, t are intentionally turned off because many simpler browsers do not display them correctly. Modern full-featured browsers re-create these ligatures on-the-fly.
Horizontal space:	HTML output for thin-unbreakable, unbreakable, <code>\enskip</code> , <code>\quad</code> , <code>\qquad</code> , <code>\hspace</code> .
Rules:	<code>\rule</code> with width, height, raise, text color.
HTML reserved characters:	<code>\&</code> , <code>\textless</code> , and <code>\textgreater</code> are converted to HTML entities.
Fonts:	Used as-is. Appear in SVG math expressions or embedded image environments.
Symbols:	Native L ^A T _E X diacriticals, <code>chemgreek</code> , <code>textalpha</code> , <code>textcomp</code> , <code>textgreek</code> , <code>xunicode</code> . Tested to work as-is: <code>gensymb</code> .
Files:	<code>attachfile</code> , <code>attachfile2</code> , <code>hyperxmp</code> , <code>intopdf</code> , <code>pdfpages</code> , <code>pdfx</code> , <code>xmpincl</code> .

l warp Supported Functions — continued

Category	Status
Science and engineering:	algorithm2e, algorithmicx, axodraw2, bytefield, chemfig, chemformula, chemgreek, chemmacros, chemnum, listings, mhchem, phfqt, register. Tested to work as-is: blochsphere, bodegraph, bohr, circuitikz, elements, fast-diagram, hepnicenames, heppennames, linop, pgfgantt, physics, simpler-wick, slashed, structmech, tikzcodeblocks.
Liberal arts and humanities:	forest, schemata, vowel, xpiano. Tested to work as-is: phonrule, piano, tikz-dependency.
Accessibility:	accsupp, axessibility.
Debug:	chkfloat, cmdtrack, dprogress, lua-visual-debug, refcheck, srcltx, srctex, vpe, xbmks.
Working as-is:	Various utility, calculation, file, and text-only packages, such as calc, fileerr, somedefs, trace, xspace. Also, most math-only packages, including specialized typesetting for various fields of science and engineering.

4 Alternatives

Summarized below are several other ways to convert a \LaTeX or other document to HTML. Where an existing \LaTeX document is to be converted to HTML, **lwarf** may be a good choice. For new projects with a large number of documents, it may be worth investigating the alternatives before decided which path to take.

4.1 Internet class

cls internet The closest to **lwarf** in design principle is the **internet** class by Andrew Stacey—an interesting project which directly produces several versions of markdown, and also HTML and EPUB. <https://github.com/loopspace/latex-to-internet>

4.2 TeX4ht

Prog TeX4ht <http://tug.org/tex4ht/>

Prog htlatex This system uses native \LaTeX processing to produce a DVI file containing special commands, and then uses additional post-processing for the HTML conversion by way of numerous configuration files. In some cases **lwarf** provides a better HTML conversion, and it supports a different set of packages. TeX4ht produces several other forms of output beyond HTML, including ODT and a direct path to EPUB, and is still being developed.

4.3 Translators

These systems use external programs to translate a subset of \LaTeX syntax into HTML. Search for each on CTAN (<http://ctan.org>).

Prog Hevea **H^Ev^Fa:** <http://hevea.inria.fr/> (not on CTAN)

Prog TtH **T_TH:** <http://hutchinson.belmont.ma.us/tth/>

Prog GELLMU **GELLMU:** <http://www.albany.edu/~hammond/gellmu/>

Prog LaTeXML **ET_EXML:** <http://dlmf.nist.gov/LaTeXML/>

Prog Plastex **PlasTeX:** <https://github.com/tiarno/plastex>

Prog LaTeX2HTML **ET_EX2HTML:** <http://www.latex2html.org/>
and <http://ctan.org/pkg/latex2html>.

Prog TeX2page **TeX2page:** <http://ds26gte.github.io/tex2page/index.html>

Finally, Glad \TeX may used to directly insert \LaTeX math into HTML:

Prog GladTeX **GladTeX:** <http://humenda.github.io/GladTeX/>

4.4 Asciidoc and Asciidoctor

Asciidoc is one of the most capable markup languages, providing enough features to produce the typical technical-writing document with cross-references, and it writes \LaTeX and HTML .

- Prog Asciidoc **Asciidoctor:** <http://asciidoctor.org/> (More active.)
- Prog AsciiDoctor **Asciidoc:** <http://asciidoc.org/> (The original project.)

4.4.1 Asciidoctor-LaTeX

The Asciidoctor-LaTeX project is developing additional \LaTeX -related features.

Asciidoctor-LaTeX:

- Prog Asciidoctor-LaTeX <http://www.noteshare.io/book/asciidoctor-latex-manual>
- <https://github.com/asciidoctor/asciidoctor-latex>

4.5 Pandoc

- Prog Pandoc A markup system which also reads and writes \LaTeX and HTML .

Pandoc: <http://pandoc.org/>

(Watch for improvements in cross-references to figures and tables.)

4.6 Word processors

- Prog Word It should be noted that the popular word processors have advanced through the years in their abilities to represent math with a \LaTeX -ish input syntax, unicode math fonts, and high-quality output, and also generate HTML with varying success. See recent developments in MICROSOFT® **Word**® and LIBREOFFICE™ **Writer**.
- Prog LibreOffice
- Prog OpenOffice

4.7 Commercial systems

- Prog Adobe Likewise, several professional systems exist whose abilities have been advancing in the areas of typesetting, cross-referencing, and HTML generation. See ADOBE® **FrameMaker**®, ADOBE **InDesign**®, and MADCAP **Flare**™.
- Prog FrameMaker
- Prog InDesign

- Prog Flare
- Prog Madcap

Asciidoc, Pandoc, and various other markup languages typically have a syntax which tries to be natural and human-readable, but the use of advanced features tends to require many combinations of special characters, resulting in a complicated mess of syntax. By contrast, \LaTeX spells things out in readable words but takes longer to type, although integrated editors exist which can provide faster entry and a graphic user interface. For those functions which are covered by the typical markup language it is arguable that \LaTeX is comparably easy to learn, while \LaTeX provides many more

advanced features where needed, along with a large number of pre-existing packages which provide solutions to numerous common tasks.

Text-based document-markup systems share some of the advantages of \LaTeX vs. a typical word processor. Documents formats are stable. The documents themselves are portable, work well with revision control, do not crash or become corrupted, and are easily generated under program control. Formatting commands are visible, cross-referencing is automatic, and editing is responsive. Search/replace with regular expressions provides a powerful tool for the manipulation of both document contents and structure. Markup systems and some commercial systems allow printed output through a \LaTeX back end, yielding high-quality results especially when the \LaTeX template is adjusted, but they lose the ability to use \LaTeX macros and other \LaTeX source-document features.

The effort required to customize the output of each markup system varies. For print output, \LaTeX configuration files are usually used. For HTML output, a css file will be available, but additional configuration may require editing some form of control file with a different syntax, such as XML. In the case of **lwarf**, CSS is used, and much HTML output is adjusted through the usual \LaTeX optional macro parameters, but further customization may require patching \LaTeX code.

The popular word processors and professional document systems each has a large base of after-market support including pre-designed styles and templates, and often include content-management systems for topic reuse.

5 Installation

Table 2 shows the tools which are used for the L^AT_EX to HTML conversion. In most cases, these will be available via the standard package-installation tools.

Detailed installation instructions follow.

Table 2: Required software programs

Provided by your \LaTeX distribution:

From T_EXLive: <http://tug.org/texlive/>.

\LaTeX : `pdflatex`, `xelatex`, or `lualatex`.

The lwarf package: This package.

The lwarpmk utility: Provided along with this package. This should be an operating-system executable in the same way that `pdflatex` or `latexmk` is. It is possible to have the `lwarf` package generate a local copy of `lwarpmk` called `lwarpmk.lua`. See table 3.

luatex: Used by the `lwarpmk` program to simplify and automate document generation.

xindy: The `xindy` program is used by `lwarf` to create indexes. On a MiK_TE_X system this may have to be acquired separately, but it is part of the regular installer as of mid 2015.

latexmk: Optionally used by `lwarpmk` to compile \LaTeX code. On a MiK_TE_X system, **Perl** may need to be installed first.

pdfcrop: Used to pull images out of the \LaTeX PDF.

POPLER PDF utilities:

pdftotext: Used to convert PDF to text.

pdfseparate: Used to pull images out of the \LaTeX PDF.

pdftocairo: Used to convert images to SVG.

These might be provided by your operating-system package manager.

From POPLER: poppler.freedesktop.org.

For MACOS®, see <https://brew.sh/>, install **Homebrew**, then

```
Enter ⇒ brew install poppler
```

For WINDOWS, see:

<https://sourceforge.net/projects/poppler-win32/> and:
<http://blog.alivate.com.au/poppler-windows/>

Perl:

This may be provided by your operating-system package manager, and is required for some of the POPLER PDF utilities.

strawberryperl.com (recommended), perl.org

Automatically downloaded from the internet as required:

MATHJAX: Optionally used to display math. From: mathjax.org

5.1 Installing the l warp package

There are several ways to install **l warp**. These are listed here with the preferred methods listed first:

Pre-installed: Try entering into a command line:

Enter ⇒ kpsewhich l warp.sty

If a path to **l warp.sty** is shown, then **l warp** is already installed and you may skip to the next section.

T E X Live: If using a T E X Live distribution, try installing via **tlmgr**:

Enter ⇒ tlmgr install l warp

MiK T E X: If using MiK T E X:

1. To install **l warp** the first time, use the **MiK T E X Package Manager (Admin)**.
2. To update **l warp**, use **MiK T E X Update (Admin)**.
3. Either way, also update the package **miktex-misc**, which will install and update the **l warpmk** executable.

Operating-system package: The operating-system package manager may already have **l warp**, perhaps as part of a set of T E X-related packages.

CTAN TDS archive: **l warp** may be downloaded from the Comprehensive T E X Archive:

1. See <http://ctan.org/pkg/l warp> for the **l warp** package.
2. Download the TDS archive: **l warp.tds.zip**
3. Find the T E X local directory:

T E X Live:

Enter ⇒ kpsewhich -var-value TEXMFLOCAL

MiK T E X:

In the “Settings” window, “Roots” tab, look for a local TDS root.

This should be something like:

/usr/local/texlive/texmf-local/

4. Unpack the archive in the TDS local directory.
5. Renew the cache:

Enter ⇒ mktexlsr

— or —

Enter ⇒ texhash

Or, for Windows MiK T E X, start the program called **MiK T E X Settings (Admin)** and click on the button called Refresh FNDB.

CTAN .dtx and .ins files: Another form of TeX package is .dtx and .ins source files. These files are used to create the documentation and .sty files.

1. See <http://ctan.org/pkg/lwarp> for the **lwarp** package.
2. Download the zip archive **lwarp.zip** into your own **lwarp** directory.
3. Unpack **lwarp.zip**.
4. Locate the contents **lwarp.dtx** and **lwarp.ins**
5. Create the **.sty** files:
Enter ⇒ `pdflatex lwarp.ins`
6. Create the documentation:

```
pdflatex lwarp.dtx (several times)
makeindex -s gglo.ist -o lwarp.gls lwarp.glo
makeindex -s gind.ist lwarp.idx
pdflatex lwarp.dtx (several times)
```

7. Copy the **.sty** files somewhere such as the TeX Live local tree found in the previous CTAN TDS section, under the subdirectory:
 `<texlocal>/tex/latex/local/lwarp`
8. Copy **lwarp_baseline_marker.png** and **lwarp_baseline_marker.eps** to the same place as the **.sty** files.
9. Copy the documentation **lwarp.pdf** to a source directory in the local tree, such as:
 `<texlocal>/doc/local/lwarp`
10. Renew the cache:
 Enter ⇒ `mktexlsr`
 — or —
 Enter ⇒ `texhash`
Or, for Windows MiKTeX, start the program called **MiKTeX Settings (Admin)** and click on the button called Refresh FNDB.
11. See section [5.2.1](#) to generate your local copy of **lwarpmk**.
12. Once the local version of **lwarpmk.lua** is installed, it may be made available system-wide as per section [5.2](#).

Project-local CTAN .dtx and .ins files: The .dtx and .ins files may be downloaded to a project directory, then compiled right there, alongside the document source files. The resultant *.sty and **lwarpmk.lua** files may be used as-is, so long as they are in the same directory as the document source. The files **lwarp_baseline_marker.png** and **lwarp_baseline_marker.eps** must also be copied as well. This approach is especially useful if you would like to temporarily test **lwarp** before deciding whether to permanently install it.

5.2 Installing the `lwarpmk` utility

(Note: If `lwarpmk` is not already installed, it is easiest to use a local copy instead of installing it system-wide. See section 5.2.1.)

After the `lwarf` package is installed, you may need to setup the `lwarpmk` utility:

1. At a command line, try executing `lwarpmk`. If the `lwarpmk` help message appears, then `lwarpmk` is already set up. If not, it is easiest to generate and use a local copy. See section 5.2.1.
2. For MiK $\mathrm{T}\bar{\mathrm{E}}$ X, try updating the `miktex-misc` package. This may install the `lwarpmk` executable for you.

Otherwise, continue with the following:

3. Locate the file `lwarpmk.lua`, which should be in the `scripts` directory of the TDS tree. On a $\mathrm{T}\bar{\mathrm{E}}$ X Live or MiK $\mathrm{T}\bar{\mathrm{E}}$ X system you may use

Enter \Rightarrow `kpsewhich lwarpmk.lua`

(If the file is not found, you may also generate a local copy and use it instead. See section 5.2.1.)

4. Create `lwarpmk`:

Unix: Create a symbolic link and make it executable:

- (a) Locate the $\mathrm{T}\bar{\mathrm{E}}$ X Live binaries:

Enter \Rightarrow `kpsewhich -var-value TEXMFROOT`

This will be something like:

`/usr/local/texlive/<year>`

The binaries are then located in the `bin/<arch>` directory under the root:

`/usr/local/texlive/<year>/bin/<architecture>/`

In this directory you will find programs such as `pdflatex` and `makeindex`.

- (b) In the binaries directory, create a new symbolic link from the binaries directory to `lwarpmk.lua`:

Enter \Rightarrow `ln -s <path to lwarpmk.lua> lwarpmk`

- (c) Make the link executable:

Enter \Rightarrow `chmod 0755 lwarpmk`

WINDOWS $\mathrm{T}\bar{\mathrm{E}}$ X Live: Create a new `lwarpmk.exe` file:

- (a) Locate the $\mathrm{T}\bar{\mathrm{E}}$ X Live binaries as shown above for Unix.

- (b) In the binaries directory, make a *copy* of `runscript.exe` and call it `lwarpmk.exe`. This will call the copy of `lwarpmk.lua` which is in the `scripts` directory of the distribution.

WINDOWS MiK $\mathrm{T}\bar{\mathrm{E}}$ X: Create a new `lwarpmk.bat` file:

- (a) Locate the binaries. These will be in a directory such as:

C:\Program Files\MiKTeX 2.9\miktex\bin\x64

In this directory you will find programs such as pdflatex.exe and makeindex.exe.

- (b) Create a new file named l warpmk.bat containing:

```
texlua "C:\Program Files\MiKTeX 2.9\scripts\l warp\l warpmk.texlua" %*
```

This will call the copy of l warpmk.lua which is in the scripts directory of the distribution.

5.2.1 Using a local copy of l warpmk

It is also possible to use a local version of l warpmk:

1. When compiling the tutorial in section 6, use the l warpmk option for the l warp package:

```
\usepackage[l warpmk]{l warp}
```

2. When the tutorial is compiled with pdflatex, the file l warpmk.lua will be generated along with the other configuration files.

3. l warpmk.lua may be used for this project:

Unix:

- (a) Make l warpmk.lua executable:

Enter ⇒ chmod 0755 l warpmk.lua

- (b) Compile documents with

Enter ⇒ ./l warpmk.lua html

Enter ⇒ ./l warpmk.lua print

etc.

- (c) It may be useful to rename or link to a version without the .lua suffix.

WINDOWS:

Compile documents with either of the following, depending on which command shell is being used:

Enter ⇒ texlua l warpmk.lua html

Enter ⇒ texlua l warpmk.lua print

etc.

Or:

Enter ⇒ l warpmk html

Enter ⇒ l warpmk print

etc.

5.3 Installing additional utilities

To test for the existence of the additional utilities:

Enter the following in a command line. If each programs' version is displayed, then that utility is already installed. See table 2 on page 82.

```
Enter ⇒ luatex --version
Enter ⇒ xindy --version
Enter ⇒ latexmk --version
Enter ⇒ perl --version
Enter ⇒ pdfcrop --version
Enter ⇒ pdftotext -v
Enter ⇒ pdfseparate --version
Enter ⇒ pdftocairo -v
```

To install xindy, latexmk, and pdfcrop:

The TeX utilities **xindy**, **latexmk**, and **pdfcrop** may be installed in **TexLive** with **tlmgr**, installed by **MikTeX**, provided by your operating system's package manager, or downloaded from the **CTAN** archive:

```
http://ctan.org/pkg/xindy
http://ctan.org/pkg/latexmk
http://ctan.org/pkg/pdfcrop
```

Prog pdftotext **To install the POPPLER utilities to a Unix/Linux system:**

Prog pdfseparate The tools from the POPPLER project should be provided by your operating system's package manager.
Prog pdftocairo

To install the POPPLER utilities to a MACOS machine:

1. Install **Homebrew** from <https://brew.sh/>:

Enter ⇒

```
/usr/bin/ruby -e "$(curl -fsSL https://raw.githubusercontent.com/Homebrew/install/master/install)"
```

2. Install the POPPLER utilities:

Enter ⇒ brew install poppler

To install the POPPLER utilities to a WINDOWS machine:

1. See table 2 on page 82.
2. Download and extract the POPPLER utilities **pdftotext**, **pdfseparate**, and **pdfcrop** to a directory, such as Poppler.
3. In the Start window, type "Path" to search for results related to Path. Or open the control panel and search for "Path".
4. Choose "Edit the system environment variables" in the control panel.

5. Choose the "Environment Variables" button.
6. Choose the "Path" variable, then the "Edit" button.
7. Choose the "New" button to make an additional entry.
8. Enter the bin directory of the POPPLER utilities, such as:
C:\Users\<myname>\Desktop\Poppler\poppler-0.5_x86\poppler-0.5\bin
Be sure to include \bin.
9. Click "Ok" when done.

Prog perl **To install Perl to a WINDOWS machine:**

1. Download and install a version of **Perl**, such as STRAWBERRY PERL, to a directory without a space in its name, such as C:\Strawberry.
2. Edit the Path as seen above for the POPPLER utilities.
3. Enter the bin directory of the **Perl** utility, such as:
C:\Strawberry\perl\bin
Be sure to include \bin.
4. Click "Ok" when done.

Any utilities installed by hand must be added to the PATH.

6 Tutorial

This section shows an example of how to create an **l warp** document.

Need help?

The index to this document contains several hundred custom entries. Also included are automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category. A [Troubleshooting](#) section is also available.

6.1 Starting a new project

1. Create a new project directory called `tutorial`.
- File `tutorial.tex` 2. Inside the `tutorial` directory, create a new file called `tutorial.tex`. This may be done several ways:

Copy from the documentation PDF:

A listing is in fig. 1, which may be copied/pasted from the figure directly into your own editor, depending on the quality of the PDF viewer and editor, or:

Copy from the l warp documentation directory:

Another copy may be found by entering into a command line:

Enter ⇒ `texdoc -l l warp_tutorial.txt`

This should be in the `doc/latex/l warp/` directory along with this PDF documentation. Copy `l warp_tutorial.txt` directly into your `tutorial` directory, renamed as `tutorial.tex`.

 **Bad formatting!**

When using WINDOWS, use an editor other than Notepad, since Notepad does not accept the end-of-line from a Unix text file.

3. Compile the project:

Enter ⇒ `pdflatex tutorial.tex`

(several times)

(`xelatex` or `lualatex` may be used as well. **l warp** also supports DVI `latex` for use with .eps images.)

4. View the resulting `tutorial.pdf` with a PDF viewer.

A number of new files are created when `tutorial.tex` is compiled, as shown in table 3. These files are created by the **l warp** package.

(Two of the new files are configuration files for the helper program **l warpmk**. Whenever a print version of the document is created, the configuration files for **l warpmk** are updated to record the operating system, L^AT_EX engine (`latex`, `pdflatex`, `xelatex`, or `lualatex`), the filenames of the source code and HTML output, and whether the additional helper program `latexmk` will be used to compile the document.)

Figure 1: tutorial.tex listing

Note: There are two pages!

```
% Save this as tutorial.tex for the lwarf package tutorial.

\documentclass{book}

\usepackage{iftex}

% --- LOAD FONT SELECTION AND ENCODING BEFORE LOADING LWARP ---

\ifPDFTeX
\usepackage{lmodern}           % pdflatex or dvi latex
\usepackage[T1]{fontenc}
\usepackage[utf8]{inputenc}
\else
\usepackage{fontspec}          % XeLaTeX or LuaLaTeX
\fi

% --- LWARP IS LOADED NEXT ---
\usepackage[
%   HomeHTMLFilename=index,      % Filename of the homepage.
%   HTMLFilename={node-},        % Filename prefix of other pages.
%   IndexLanguage=english,       % Language for xindy index, glossary.
%   latexmk,                   % Use latexmk to compile.
%   OSWindows,                 % Force Windows. (Usually automatic.)
%   mathjax,                   % Use MathJax to display math.
]{lwarf}
% \boolfalse{FileSectionNames} % If false, numbers the files.

% --- LOAD PDFLATEX MATH FONTS HERE ---

% --- OTHER PACKAGES ARE LOADED AFTER LWARP ---
\usepackage{makeidx} \makeindex
\usepackage{xcolor}           % (Demonstration purposes only.)
\usepackage{hyperref,cleveref} % LOAD THESE LAST!

% --- LATEX AND HTML CUSTOMIZATION ---
\title{The Lwarf Tutorial}
\author{Some Author}
\setcounter{tocdepth}{2}        % Include subsections in the \TOC.
\setcounter{secnumdepth}{2}      % Number down to subsections.
\setcounter{FileDepth}{1}        % Split \HTML\ files at sections
\booltrue{CombineHigherDepths} % Combine parts/chapters/sections
\setcounter{SideTOCDepth}{1}      % Include subsections in the side\TOC
\HTMLTitle{Webpage Title}       % Overrides \title for the web page.
\HTMLAuthor{Some Author}        % Sets the HTML meta author tag.
```

```

\HTMLLanguage{en-US} % Sets the HTML meta language.
\HTMLDescription{A description.}% Sets the HTML meta description.
\HTMLFirstPageTop{Name and \fbox{HOMEPAGE LOGO}}
\HTMLPageTop{\fbox{LOGO}}
\HTMLPageBottom{Contact Information and Copyright}
\CSSFilename{l warp_sagebrush.css}

\begin{document}

\maketitle % Or titlepage/titlingpage environment.

% An article abstract would go here.

\tableofcontents % MUST BE BEFORE THE FIRST SECTION BREAK!
\listoffigures

\chapter{First chapter}

\section{A section}

This is some text which is indexed.\index{Some text.}

\subsection{A subsection}

See \cref{fig:withtext}.

\begin{figure}\begin{center}
\fbox{\textcolor{blue!50!green}{Text in a figure.}}
\caption{A figure with text\label{fig:withtext}}
\end{center}\end{figure}

\section{Some math}

Inline math: $r = r_0 + vt - \frac{1}{2}at^2$  

followed by display math:  

\begin{equation}
a^2 + b^2 = c^2
\end{equation}

\begin{warpprint} % For print output ...
\cleardoublepage % ... a common method to place index entry into TOC.
\phantomsection
\addcontentsline{toc}{chapter}{\indexname}
\end{warpprint}
\ForceHTMLPage % HTML index will be on its own page.
\ForceHTMLTOC % HTML index will have its own toc entry.
\printindex

\end{document}

```

Table 3: Files created along with the print version

tutorial.pdf: The PDF output from L^AT_EX. The print version of the document.

tutorial_html.tex: A small .tex file used to create a parallel HTML version of the document, which co-exists with usual the PDF version, and which will have its own auxiliary files. In this way, both PDF and HTML documents may co-exist side-by-side.

Auxiliary files: The usual L^AT_EX files .aux, .log, .out, .toc, .lof, .idx. When an HTML version of the document is created, _html versions of the auxiliary files will also be generated.

lwarpmk.conf: A configuration file for lwarpmk, which is used to automate the compilation of PDF or HTML versions of the document.

tutorial.lwarpmkconf: Another configuration file used by lwarpmk, which is only useful if you wish to have several projects residing in the same directory.

.css files: lwarf.css, lwarf_formal.css, lwarf_sagebrush.css These files are standard for lwarf, and are not meant to be modified by the user.

sample_project.css: An example of a user-customized css file, which may be used for project-specific changes to the lwarf defaults.

lwarf.ist: Used by lwarf while creating an index using makeindex. This file should not be modified by the user. A custom file may be used instead, if necessary.

lwarf.xdy: Used by lwarf while creating an index using xindy. This file should not be modified by the user. A custom file may be used instead, if necessary.

lwarf_one_limage.txt: For WINDOWS only. Used to process SVG images in the background. Copied to lwarf_one_limage.cmd when images are generated.

lwarf_mathjax.txt: Inserted into the HTML files when MATHJAX is used to display math. This file should not be modified by the user.

comment.cut: A temporary file used by lwarf to conditionally process blocks of text. This file may be ignored.

When the lwarpmk option is given to the lwarf package:

lwarpmk.lua: A local copy of the lwarpmk utility.

On Unix-related operating systems this file must be made executable:

```
chmod u+x lwarpmk.lua
```

This may be useful to have to archive with a project for future use.

6.2 Compiling the print version with **lwarpmk**

The **lwarpmk** utility program is used to compile either the printed or the **HTML** version of the document.

lwarpmk print is used to recompile a printed version of the document.

1. Re-compile the print version:

Enter ⇒ **lwarpmk print**

lwarpmk prints an introduction then checks to see if the document must be recompiled. If it seems that the files are up-to-date, then **lwarpmk** informs you of that fact and then exits.

2. Make a small change in the original document, such as adding a space character.
3. Recompile again.

Enter ⇒ **lwarpmk print**

The document is recompiled when a change is seen in the source. Several compilations may be necessary to resolve cross-references.

4. Force a recompile to occur.

Enter ⇒ **lwarpmk again**

Enter ⇒ **lwarpmk print**

lwarpmk again updates the date code for the file, triggering a recompile the next time the document is made.⁵

5. Process the index.⁶ ⁷

Enter ⇒ **lwarpmk printindex**

6. Recompile again to include the index.

Enter ⇒ **lwarpmk print**

7. To force a single recompile when needed, even if no changes were detected:

Enter ⇒ **lwarpmk print1**

Note that the **HTML** customization commands are ignored while making the print version.

⁵Although, when using the utility **latexmk** (introduced later), the changed date is ignored and an actual change in contents must occur to cause a recompile.

⁶The command **lwarpmk printglossary** is also available to process a glossary produced with the **glossaries** package. See section 9.5.10.

⁷Also see section 9.5.12 for index options.

6.3 Compiling the HTML version with lwarfmk

`lwarfmk html` is used to recompile an HTML version of the document.

1. Compile the HTML version:

Enter ⇒ `lwarfmk html`

- (a) `lwarfmk` uses L^AT_EX to process `tutorial_html.tex` to create `tutorial_html.pdf`.
- (b) `pdftotext` is then used to convert to the file `tutorial_html.html`. This file is a plain-text file containing HTML tags and content for the entire document.
- (c) `lwarfmk` manually splits `tutorial_html.html` into individual HTML files according to the HTML settings. For this tutorial, the result is `tutorial.html` (the home page), along with `First-chapter.html`⁸, `Some-math.html`, and the document's index in `_Index.html`.⁹

2. View the HTML page in a web browser.

Open the file `tutorial.html` in a web browser.

`math`

Note that math is still displayed as its alt tag, which is the plain-text L^AT_EX source, until the images of the math expressions have been generated. Math may be displayed as SVG images or by a MATHJAX script, as seen in sections 6.4 and 6.5.

3. Force a recompile:

Enter ⇒ `lwarfmk again`

Enter ⇒ `lwarfmk html`

Enter ⇒ `lwarfmk print`

4. Process the HTML index and recompile:¹⁰¹¹

Enter ⇒ `lwarfmk htmlindex`

Enter ⇒ `lwarfmk html`

`_Index.html` is updated for the new L^AT_EX index.

5. Reload the web page to see the added index.

6. To force a single recompile when needed, even if no changes were detected:

Enter ⇒ `lwarfmk html1`

⁸`First-chapter.html` also contains the first section, even though the second section is its own HTML page. This behavior is controlled by the boolean `CombineHigherDepths`.

⁹`index.html` is commonly used as a homepage, so the document index is in `_Index.html`.

¹⁰The command `lwarfmk htmlglossary` is also available to process a glossary produced with the `glossaries` package. See section 9.5.10.

¹¹Also see section 9.5.12 for index options.

6.4 Generating the SVG images

math as svg images

By default **lwarf** represents math as svg images with the \LaTeX source included in `alt` attributes. In this way, the math is displayed as it was drawn by \LaTeX , and the \LaTeX source may be copied and pasted into other documents.

picture and Tikz

lwarf uses the same mechanism for `picture` and `Tikz` environments.

1. Create the svg images:

```
Enter ⇒ lwarpmk limages
Enter ⇒ lwarpmk html
```

2. Move to the tutorial's HTML math page and reload the document in the browser.
3. The math images are displayed using the same font and formatting as the printed version.
4. Copy/paste a math expression into a text editor to see the \LaTeX source.

⚠️ adding/removing

When a math expression, `picture`, or `Tikz` environment is added or removed, the svg images must be re-created by entering `lwarpmk limages` to maintain the proper image-file associations. Inline svg math may be hashed and thus not need to be recreated, but display math and objects such as `Tikz` may move to new image numbers when the document is changed.

Before attempting to create the svg image files, **lwarpmk** verifies that the `HTML` version of the document exists and has correct internal image references.¹² If it is necessary to recompile the document's `HTML` version, **lwarpmk** will inform so with an error message.

⚠️ HTML instead of images

If `HTML` appears where an svg image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time. **lwarpmk** attempts to detect this situation and print a warning.

⚠️ page counter

Incorrect svg images will also occur if the document changes the page counter:

```
\setcounter{page}{<value>}
```

The page counter must *not* be adjusted by the user.

Expressing math as svg images has the advantage of representing the math exactly as \LaTeX would, but has the disadvantage of requiring an individual file for each math expression. For inline math, and some other objects, **lwarf** uses an MD5 hash on its \LaTeX source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as `picture` and

¹²This becomes important when dealing with a document containing thousands of images.

Tikz require one image file each. For a document with a large amount of math, see section [6.5](#) to use MATHJAX instead.

6.5 Using MATHJAX for math

math with MATHJAX Math may also be represented using the MATHJAX JAVASCRIPT project.

1. In the tutorial's source code, uncomment the `mathjax` package option for `l warp`:

```
mathjax, % Use MathJax to display math.
```

2. Recompile

```
Enter ⇒ l warpmk html
```

3. Reload the math page.

⚠ MATHJAX requirements

MATHJAX requires web access unless a local copy of MATHJAX is available, and it also requires that JAVASCRIPT is enabled for the web page. The math is rendered by MATHJAX. Right-click on math to see several options for rendering, and for copying the L^AT_EX source.

While using MATHJAX has many advantages, it may not be able to represent complex expressions or spacing adjustments as well as L^AT_EX, and it may not support some math-related packages.

6.6 Changing the CSS style

For a formal css style, add to the preamble:

```
\usepackage{lwarf}
...
\CSSFilename{lwarf_formal.css}
...
\begin{document}
```

For a modern css style, lwarf_sagebrush.css is also provided:

```
\CSSFilename{lwarf_sagebrush.css}
```

See section 8.5 for more information about modifying the CSS styling of the document.

6.7 Customizing the HTML output

A number of settings may be made to control the HTML output, including filename generation, automatic compilation, math output, document splitting, meta data, and page headers and footers.

See section 8.4 for more information.

6.8 Using `latexmk`

`latexmk` is a L^AT_EX utility used to monitor changes in source files and recompile as needed.

1. In the tutorial's source code uncomment the `latexmk` option for the `l warp` package:

```
latexmk, % Use latexmk to compile.
```

2. Recompile the printed version of the document.

```
Enter ⇒ l warpmk print
```

`l warp` updates its own configuration files (`l warpmk.conf` and `tutorial.l warpmkconf`) whenever the printed version of the document is compiled. These configuration files remember that `l warpmk` should use `latexmk` to compile the document.

3. Recompile the document.

```
Enter ⇒ l warpmk print
```

and/or

```
Enter ⇒ l warpmk html
```

Changes are detected by comparing checksums rather than modification times, so `l warpmk` again will not trigger a recompile, but `latexmk` has a much better awareness of changes than the `l warpmk` utility does and it is likely to correctly know when to recompile. A recompile may be forced by making a small change to the source, and a single recompile may be forced with:

`forced single-pass recompile`

```
Enter ⇒ l warpmk print1
```

and/or

```
Enter ⇒ l warpmk html1
```

6.9 Using XeLaTeX or LuaLaTeX

Xe \TeX or Lua \TeX may be used instead of \TeX .

1. Remove the auxiliary files for the project:

Enter \Rightarrow lwarfpmk cleanall

2. Use **xelatex** or **lualatex** to compile the printed version a single time.

Enter \Rightarrow xelatex tutorial.tex

-or-

Enter \Rightarrow lualatex tutorial.tex

When the compile occurs, the configuration files for **lwarfpmk** are modified to remember which \TeX engine was used. Xe \TeX or Lua \TeX will be used for future runs of **lwarfpmk**.

3. To recompile the document:

Enter \Rightarrow lwarfpmk print

-and-

Enter \Rightarrow lwarfpmk html

4. Also remember to update the indexes and recompile again:

Enter \Rightarrow lwarfpmk htmlindex

Enter \Rightarrow lwarfpmk html

Enter \Rightarrow lwarfpmk printindex

Enter \Rightarrow lwarfpmk print

6.10 Using DVI LaTeX

Traditional DVI LaTeX may also be used along with .eps image files. An SVG version of each image must also be provided. **lwarfpmk** may be used to convert image formats.

To convert EPS files to PDF:

Enter \Rightarrow lwarfpmk epstopdf *.eps (or a list of files)

To convert PDF files to SVG:

Enter \Rightarrow lwarfpmk pdftosvg *.pdf (or a list of files)

 **bitmapped fonts** See section 8.2 regarding font selection to avoid the use of bitmapped fonts.

6.11 Using a glossary

lwarf supports the **glossaries** package, although this tutorial does not supply an example.

To process the glossary for the print version:

Enter ⇒ `lwarfpmk printglossary`

 (If `makeglossaries` is not found, see section 9.5.10.)

To process the glossary for the HTML version:

Enter ⇒ `lwarfpmk htmlglossary`

In each case, the document will have to be recompiled afterwards:

Enter ⇒ `lwarfpmk html1`

Enter ⇒ `lwarfpmk html`

Enter ⇒ `lwarfpmk print1`

Enter ⇒ `lwarfpmk print`

See section 9.5.10 to set options for processing glossaries.

6.12 Cleaning auxiliary files

To remove the auxiliary files .aux, .toc, .lof, .lot, .idx, .ind, .log, and .gl*:

Enter ⇒ lwarfmk clean

6.13 Cleaning auxiliary and output files

To remove the auxiliary files, and also remove the .pdf and .html files:

Enter ⇒ lwarfmk cleanall

6.14 Cleaning the images from the lateximages directory

The lateximage directory contains SVG images automatically generated for inline and display math, **tikz**, etc. To remove all the images from the lateximages directory:

Enter ⇒ lwarfmk cleanimages

6.15 Converting PDF or EPS images to SVG

HTML cannot display PDF or EPS images, so any external PDF graphics images must be converted to SVG format. **pdftocairo** and **epstopdf** may be used one image at a time, but **lwarfmk** also provides a way to convert PDF or EPS images in bulk:

Enter ⇒ lwarfmk epstopdf *.eps (or a list of files)

Enter ⇒ lwarfmk pdftosvg *.pdf (or a list of files)

Be sure to always provide SVG files for HTML output.

6.16 Creating HTML from an incomplete compile

During testing it may be useful to finish the HTML conversion even when the document had errors and did not compile successfully. To attempt an HTML conversion of an incomplete document:

Enter ⇒ lwarfmk pdftohtml [-p project]

6.17 Processing multiple projects in the same directory

It is possible to have several projects in the same directory. **lwarfpmk** has an optional parameter which is the document to compile.

To create each project:

```
Enter ⇒ pdflatex project_a
```

```
Enter ⇒ pdflatex project_b
```

Each project is given its own configuration file:

```
project_a.lwarpmkconf, project_b.lwarpmkconf
```

To compile each project with **lwarkmk**:

```
Enter ⇒ lwarpmk print -p project_a
```

```
Enter ⇒ lwarpmk html -p project_b
```

6.18 Using the make utility

lwarpmk has an action which may be useful for integration with the common **make** utility:

```
lwarpmk pdftohtml [-p project]
```

make may be used to compile the code to PDF with HTML tags (`project_html.pdf`), then **lwarpmk** may be used to convert each target to HTML files.

7 Converting an existing document

To convert an existing document for use with **l warp**:

1. Arrange the document in the following order:
 - (a) Declare the `\documentclass`.
 - (b) Load text fonts.
 - (c) Load `inputenc` or `inputenx`, `fontenc`, and/or `fontspec`.
 - (d) Load **l warp**.
 - (e) Load remaining packages.
2. Modify the document:
 - (a) Avoid the `scale` option. Change:

```
\includegraphics[scale=<xx>]
```

to:

```
\includegraphics[width=<yy>\linewidth]
```
 - (b) Possible changes to tabular environments include `*` columns, `multirow`, `longtable`, `supertabular`, `xtab`, `bigdelim`. See section 9.9.
 - (c) Possible option clashes with `memoir`. See section 9.12.
 - (d) If using indexes, see section 9.5.12.
 - (e) If using many indexes, glossaries, .aux files, etc., see section 9.5.12 regarding `morewrites`. If `morewrites` is already used, be sure to add the setup with `allocate=10`.
 - (f) Other changes as per **Special cases and limitations**, section 9.
3. Convert any PDF images to SVG. See section 9.7.
4. Manually compile the print version with `latex`, `pdflatex`, `lualatex`, or `xelatex`.
5. `lwarpmk print` to finish the print version.
6. `lwarpmk html` to create the HTML version.
7. `lwarpmk limages` to create the SVG images of any SVG math, `lateximage`, `Tikz`, etc.

Need help?

The index to this document contains several hundred custom entries. Also included are automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category. A **Troubleshooting** section is also available.

8 Additional details

8.1 Shell escape

Opt `--shell-escape` Some documents require the use of an external program, which is allowed when using the `--shell-escape` command-line option. When the document is first compiled manually, and also whenever the print version is recompiled, **lwarf** detects and remembers whether shell escape is enabled. If so, it will also be enabled when the document is recompiled with **lwarpmk**.

8.2 Font and UTF-8 support

⚠ **type 3 bitmapped fonts** **lwarf** uses **pdftotext** to convert PDF output into UTF-8-encoded text. This process requires that UTF-8 information be embedded in the PDF file, which may prevent the use of older “type 3” bit-mapped fonts, and of older packages such as **ae**. The **lwarf** option `pdftotextEnc` may be useful in some situations. See section 8.3.

vector fonts While using DVI **latex** or PDF **pdflatex**, if no font-related package is specified then the default Computer Modern font is used, which may be a “type 3” bit-mapped font which may not convert well to plain text. A “type 1” vector font is required.

Computer Modern

⚠ **pdflatex**

⚠ **DVI latex**

Pkg **cm-super**

Pkg **lmodern**

To use the updated **cm-super**’s type 1 fonts instead of Computer Modern, install the **cm-super** font package.

To use Latin Modern instead, add

```
usepackage{lmodern}
```

to the preamble.

Pkg **dejavu** Another useful option is the Deja Vu series of fonts, which have an increased coverage of language and glyphs:

```
\usepackage{dejavu}
```

latex, pdflatex, T1, UTF8

While using DVI **latex** or PDF **pdflatex**, **fontenc** is automatically loaded with T1 encoding. **fontenc** may be loaded with an additional encoding after **lwarf**. **inputenc** is automatically loaded with UTF8 encoding if it has not yet been loaded, but may also be specified with another encoding such as latin1. See the next section regarding index encoding.

xelatex and **lualatex**

X^ET_EX and LuaX^ET_EX users must use the **fontspec** package. Do NOT use **fontenc**!

Place **fontspec** or **fontenc**, **xunicode**, and other font and UTF-8 related commands after the `\documentclass` command and before `\usepackage{lwarf}`.

⚠ package conflicts

In some cases, a package conflict may require that a font package be loaded after `l warp`, which should work as well:

1. `documentclass{article/book/report}` comes first, followed by any of:
2. Font and UTF-8 related commands:

- For X_ET_EX or Lua_ET_EX:

Pkg `fontspec`

ligatures

`l warp` sets the following to turn off T_EX ligatures during the generation of HTML tags, and turn off common ligatures in regular text, since older browsers may not display them correctly and newer browsers can automatically re-create them.

```
\defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
```

- For pdflatex:

Pkg `lmodern`

Pkg `fontenc`

Pkg `inputenc`

Pkg `inputenx`

Pkg `newunicodechar`

File `glyptounicode.tex`

- (a) `\usepackage{lmodern}`, or other font-related packages
- (b) `\usepackage[T1]{fontenc}`
- (c) `\usepackage[utf8]{inputenc}`, or `latin1`, etc. Or use `inputenx`.
- (d) `\usepackage{newunicodechar}` along with related definitions.
- (e) To assist with the PDF-HTML conversion:
 - i. `\input glyptounicode.tex`
 - ii. `\input glyptounicode-cmr.tex%` from the `pdfx` package
 - iii. `\pdfgentounicode=1`

- (f) Another option to assist with the PDF-HTML conversion:
 - `\usepackage{cmap}`

- (g) `\usepackage{textcomp}`

3. `\usepackage{l warp}` (section 8.3) goes after any of the above, followed by:
4. `\usepackage{newtxmath}` or other math-related font packages. Many of these load `amsmath`, which must be loaded after `l warp`, so they must also be loaded after `l warp`.
5. `\setmonofont{TeX Gyre Cursor}` or similar may be required if using X_ET_EX or Lua_ET_EX and `fontspec` along with traditional font packages such as `txfonts`, `newtxttext`, etc. This is required to turn off the monospaced font's ligatures with `fontspec` after loading the traditional font packages. Monospaced output ligatures must be turned off to produce the correct HTML characters.
6. ... the rest of the preamble and the main document.

⚠ `fontspec` with traditional font packages

8.2.1 Indexes, glossaries, and encoding

lwarf uses the **xindy** program to processes indexes. **xelatex** and **lualatex** use **xindy** and **pdflatex** uses **texindy**.

The **lwarf** option `xindyLanguage` may be used to set the language option for **xindy**, and the `xindyCodepage` option may be used to set the codepage option for **xindy**. These are used for index generation.

8.3 l warp package loading and options

l warp supports **book**, **report**, and **article** classes, as well as the equivalent Koma-script classes and **memoir**.

Load the **l warp** package immediately after the font and UTF-8 setup commands.

Package options may be set while loading **l warp**, or later with

```
\l warpsetup{{key=value, ...}}
```

Pkg **l warp**

Opt **mathsvg** **mathjax**: For math display, select **mathsvg** (default), or **mathjax**. For more information about the math options, see section 9.6.

Opt **latexmk** **latexmk**: Tells **l warpmk** to use **latexmk** to recompile the document several times if necessary. Otherwise, **l warpmk** attempts to determine for itself whether to recompile. See section 8.4.

Opt **dvips** **dvips**: Tells **l warpmk** to use **dvips** and **ps2pdf** to convert DVI output to PDF.

Default: **false** **dvipdfm**: Tells **l warpmk** to use **dvipdfm** to convert DVI output to PDF.

Default: **false** **dvipdfmx**: Tells **l warpmk** to use **dvipdfmx** to convert DVI output to PDF.

Opt **dvipdfmx** **HomeHTMLFilename**: See section 8.4.

Opt **HomeHTMLFilename** **Default: {}** **HTMLFilename**: See section 8.4.

Opt **HTMLfilename** **Default: {}** **PrintLatexCmd**: Sets the shell commands executed by **l warpmk print**. If not specified, will automatically be set according to the detected L^AT_EX engine and the use of **--shell-escape**.

Opt **PrintLatexCmd** **Default: <automatic>** **HTMLLatexCmd**: Sets the shell commands executed by **l warpmk html**. If not specified, will automatically be set according to the detected L^AT_EX engine and the use of **--shell-escape**.

Opt **makeindex** **makeindex**: Sets **PrintIndexCmd**, **HTMLIndexCmd**, and **LatexmkImageCmd** to use **makeindex** when generating indexes with **l warpmk printindex**, **l warpmk htmlindex**, or **latexmk**. If neither **makeindex** nor **xindy** is used, **makeindex** is assumed.

Opt **xindy** **xindy**: Sets **PrintIndexCmd**, **HTMLIndexCmd**, and **LatexmkImageCmd** to use **xindy** when generating indexes with **l warpmk printindex**, **l warpmk htmlindex**, or **latexmk**.

Opt **makeindexStyle** **makeindexStyle**: If you wish to use a custom **.ist** file for index generation, see section 25.
Default: **l warp.ist**

Opt **xindyStyle** **xindyStyle**: If you wish to use a custom **.xdy** file for index generation, see section 25.
Default: **l warp.xdy**

Table 4: **lwarf** package options

Option	Description
<code>mathsvg</code>	Show math using SVG images.
<code>mathjax</code>	Show math using MATHJAX.
<code>latexmk</code>	Use <code>latexmk</code> for compiling documents.
<code>dvips</code>	Use <code>dvips</code> and <code>ps2pdf</code> to convert DVI documents.
<code>dvipdfm</code>	Use <code>dvipdfm</code> to convert DVI documents.
<code>dvipdfmx</code>	Use <code>dvipdfmx</code> to convert DVI documents.
<code>HomeHTMLFilename</code>	The filename of the home page.
<code>HTMLFilename</code>	A prefix for the filenames of the remaining web pages.
<code>PrintLatexCmd</code>	The shell commands for <code>lwarpmk print</code> .
<code>HTMLLatexCmd</code>	The shell commands for <code>lwarpmk html</code> .
For indexing (section 9.5.12) and glossaries (section 9.5.10):	
<code>makeindex</code>	Use <code>makeindex</code> to generate indices.
<code>xindy</code>	Use <code>xindy</code> to generate indices.
<code>makeindexStyle</code>	Set a custom style for <code>makeindex</code> .
<code>xindyStyle</code>	Set a custom style for <code>xindy</code> .
<code>xindyLanguage</code>	The <code>xindy</code> language option used for index generation.
<code>xindyCodepage</code>	The <code>xindy</code> codepage option used for index generation.
<code>PrintIndexCmd</code>	Shell commands executed by <code>lwarpmk printindex</code> .
<code>HTMLIndexCmd</code>	Shell commands executed by <code>lwarpmk htmlindex</code> .
<code>LatexmkIndexCmd</code>	Shell commands executed by <code>latexmk</code> .
<code>GlossaryCmd</code>	Shell command executed by <code>lwarpmk printglossary</code> and <code>lwarpmk htmlglossary</code> .
Seldom necessary:	
<code>OSWindows</code>	Force compatibility with MS-WINDOWS.
<code>pdftotextEnc</code>	Set the encoding for <code>pdftotext</code> .
<code>lwarpmk</code>	Generate a local copy of <code>lwarpmk.lua</code> .
Used internally by <code>lwarf</code> :	
<code>warpprint</code>	Generate print output, and also generate configuration files.
<code>warpHTML</code>	Generate HTML output.
<code>BaseJobname</code>	The <code>\jobname</code> to use. Set to the <code>\jobname</code> of the printed version even while generating HTML.

Opt `xindyLanguage` `xindyLanguage:` If using an index or glossary, see section 25.
 Default: `english`

Opt `xindyCodepage` `xindyCodepage:` If using an index, see section 25.
 Default: `utf8`

Opt `PrintIndexCmd` `PrintIndexCmd:` Sets the shell commands executed by `lwarpmk printindex`. If not specified, will be set by the selection of `makeindex` or `xindy`. May be used to specify the creation of multiple indexes. See section 9.5.12.
 Default: `<automatic>`

automatic setting

xindy

Examples:

```
makeindex -s lwarf.ist projectname.idx          (makeindex)
xindy -M lwarf.xdy -L english -C utf8 projectname.idx      (xindy)
```

The use of the `makeindex` or `xindy` options sets `PrintIndexCmd` to sensible values for each of those programs while compiling a single index. `lwarf`'s `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options will be used if specified.

If specifying `PrintIndexCmd` manually, be sure to assign an `xindy` language and codepage with the `-L` and `-C` `xindy` options, as the `lwarf` `xindyLanguage` and `xindyCodepage` options are not used for the `PrintIndexCmd` option when it is set manually.

This option is stored in the configuration files `lwarpmk.conf` and `*.lwarpmkconf`, and is then passed by the `lwarpmk printindex` command to the operating system to compile the print indexes. Since the command string is parsed by TeX, written to a file, read from the file by LuaTeX, and finally passed to the operating system, any attempt at quoting will be problematic. For complicated commands, it would be best to create a shell script, and simply refer to the script with the `lwarf PrintIndexCmd` option.

Opt `HTMLIndexCmd` `HTMLIndexCmd:` Sets the shell commands executed by `lwarpmk htmlindex`. If not specified, will be set by the selection of `makeindex` or `xindy`. May be used to specify the creation of multiple indexes. See section 9.5.12.
 Default: `<automatic>`

automatic setting

filenames

Example settings are similar to `PrintIndexCmd`, but append `_html` to the filenames:

```
makeindex -s lwarf.ist projectname_html.idx      (makeindex)
xindy -M lwarf.xdy -L english -C utf8 projectname_html.idx (xindy)
```

The use of the `makeindex` or `xindy` options sets `HTMLIndexCmd` to sensible values for each of those programs while compiling a single index. `lwarf`'s `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options will be used if specified.

If specifying `HTMLIndexCmd` manually, be sure to assign an `xindy` language and codepage with the `-L` and `-C` `xindy` options, as the `lwarf` `xindyLanguage` and `xindyCodepage` options are not used for the `HTMLIndexCmd` option when it is set manually.

As with `PrintIndexCmd`, to generate complicated indexes it may be worthwhile to use a shell script, then refer to that script with `HTMLIndexCmd`.

Opt LatexmkIndexCmd Default: <automatic>	LatexmkIndexCmd: Sets the shell commands executed by latexmk . Unlike PrintIndexCmd and HTMLIndexCmd, LatexmkIndexCmd does not include any filenames, which will be provided instead by latexmk . See section 9.5.12.
	Example settings are similar to PrintIndexCmd, but without a filename: <pre>makeindex -s l warp.ist (makeindex) xindy -M l warp.xdy -L english -C utf8 (xindy)</pre>
automatic setting	The use of the makeindex or xindy options sets LatexmkIndexCmd to either of the two settings shown above. l warp 's makeindexStyle, xindyStyle, xindyLanguage, and xindyCodepage options will be used if specified. Unlike PrintIndexCmd and HTMLIndexCmd, latexmk uses either of the single-line settings of LatexmkIndexCmd shown above to compile each of multiple indexes if necessary.
⚠️ xindy	If specifying LatexmkIndexCmd manually, be sure to assign an xindy language and codepage with the -L and -C xindy options, as the l warp xindyLanguage and xindyCodepage options are not used for the LatexmkIndexCmd option when it is set manually.
Opt GlossaryCmd Default: <code>makeglossaries</code>	GlossaryCmd: Sets the shell command executed by l warp mk printglossary and l warp mk htmlglossary . The print or HTML glossary filename is appended to this command. See section 9.5.10.
Opt OSWindows	OSWindows: l warp attempts to automatically sense WINDOWS, but it may be forced with this option. See section 8.6.
Opt pdftotextEnc Default: <code>UTF-8</code>	pdftotextEnc: Used to specify the encoding used by pdftotext during the PDF-HTML conversion. In most situations, the default is the correct choice.
Opt l warpmk	l warpmk: If you wish to have l warp generate a local copy of l warpmk.lua for archival or local-installation purposes, compile the print version with the l warpmk option set. See section 25.
<hr/>	
The following options are used internally by l warp , and usually are not used in the user's document:	
Opt warpprint Opt warpHTML	warpprint and warpHTML: Usually controlled by l warpmk , and not set in the document. Select the warpprint option to generate print output (default), or the warpHTML option to generate HTML5 output. The default is print output, so the print version may be compiled with the usual pdflatex , etc. When l warp is loaded in print mode, it creates <project>.html.tex , which sets the warpHTML option before calling the user's source code <project>.tex . In this way, <project>.tex can \usepackage{lwarp} without any options to create a printed version, while <project>.html.tex will create an HTML version.
Opt BaseJobname Default: <code>\jobname</code>	BaseJobname: Not intended for the user. Used internally by l warp when creating the *_html.tex file used to compile the HTML version. See section 25.

8.4 Customizing the HTML output

⚠ Placement! Table 5 shows several settings may be used to customize the HTML output. Watch for the correct placement of each!

⚠ Changes! Note that if changes are made, it is best to first:

1. Clear all the HTML, PDF, and auxiliary files:

Enter ⇒ `lwarpmk clearall`

2. Recompile the print version in order to recreate the configuration files for **lwarpmk**:

Enter ⇒ `lwarpmk print`

3. Finally, recompile the HTML version with the new settings:

Enter ⇒ `lwarpmk html`

Options for the lwarf package:

Use the following as options for `\usepackage[<options>]{lwarf}`:

Opt `HomeHTMLFilename`
Default: `\BaseJobname`

HomeHTMLFilename: Filename of the homepage, without the “.html” suffix.
Defaults to the `\BaseJobname`. A common setting is:

`HomeHTMLFilename=index`

filename underscores

causing the homepage to be the file `index.html`. Underscores are allowed in `HomeHTMLFilename` and `HTMLFilename` options, but may need to be escaped elsewhere, such as when appearing in a list:

`\item [\href{file_name.pdf}{text}] \`

See section 8.4.1 for examples of naming and numbering HTML files.

Opt `HTMLFilename`
Default: `<empty>`

HTMLFilename: A filename prefix for the rest of the HTML web pages. Useful for numbered web pages with a common prefix. May be empty. See section 8.4.1 for examples of naming and numbering HTML files.

Opt `latexmk`
Default: `false`

latexmk: Controls whether **lwarf** uses **latexmk** to compile the document. This setting is written to **lwarpmk**'s configuration files.

Opt `mathsvg`
Default: `true`

mathsvg: Selects SVG display for math output. (The default.)

Opt `mathjax`
Default: `false`

mathjax: Selects MATHJAX for math output.

Opt `makeindex`

makeindex: Selects **makeindex** for index generation by **lwarpmk**.

Default: `makeindex`

Opt `xindy`

xindy: Selects **xindy** for index generation by **lwarpmk**.

Default: `makeindex`

Table 5: HTML settings

Option	Description
<code>SideTOCDepth</code>	Sectioning depth of the sidetoc.
<code>FileDepth</code>	Sectioning depth of the file splits.
<code>CombineHigherDepths</code>	Combine higher section levels.
<code>FileSectionNames</code>	Use section names for file names, else use numbers.
<code>FootnoteDepth</code>	Sectioning depth of footnotes.
<code>\abstractname</code>	The name of the abstract.
<code>\mathimagename</code>	The SVG math image <code>lateximage alt</code> tag.
<code>\packagediagramname</code>	The suffix for a package's <code>lateximage alt</code> tags.
<code>\CSSFilename</code>	The css for the following files.
<code>\HTMLLanguage</code>	The <code>html lang</code> tag.
<code>\HTMLTitle</code>	The <code>HTML title</code> meta tag, overriding <code>\title</code> .
<code>\HTMLAuthor</code>	The <code>HTML author</code> meta tag, overriding <code>\author</code> .
<code>\HTMLDescription</code>	The <code>HTML description</code> meta tag.
<code>\HTMLFirstPageTop</code>	Heading for the home page.
<code>\HTMLPageTop</code>	Heading for the other pages.
<code>\HTMLPageBottom</code>	Footing for all pages.
<code>HTMLDebugComments</code>	Boolean to generate HTML comments.

Placed in the preamble before `\begin{document}`:

Ctr `tocdepth` **tocdepth:** Sectioning depth of the table of contents. See section 16 for a list of L^AT_EX stack depths.

Ctr `SideTOCDepth` **SideTOCDepth:** Sectioning depth of the sidetoc. Defaults to 1, causing the sidetoc to show sections but not subsections.
Default: 1

sideroc Each subpage of the website has its own small table of contents on the side (the “sidetoc”). Its depth is set by SideTOCDepth. This sidetoc is only shown if the web page is wide enough. When using a narrow web browser window, “responsive web design” is used to show the sidetoc at the top of the page and a link back to “Home” at the bottom.

It is recommended to set:

`SideTOCDepth = FileDepth`

or

`SideTOCDepth = FileDepth+1`

 **inaccessible pages**

If SideTOCDepth < FileDepth, web pages will be inaccessible via the sidetoc.

Ctr `FileDepth` **FileDepth:** Sectioning depth of file splits. Defaults to -5, causing the entire HTML website to be one single file.
Default: -5

- To place the entire file into one HTML page, use:
`\setcounter{FileDepth}{-5}`
- To split the HTML file at \section depth, use:
`\setcounter{FileDepth}{1}`
- To ensure that the HTML pages/files are accessible:
Place a `\tableofcontents` somewhere before the first section break (therefore in the “home page”), and set
`tocdepth >= FileDepth`



Bool `CombineHigherDepths` **CombineHigherDepths:** Combine a higher section with its first lower subsections, down to the FileDepth. Defaults to true. Set to false to simulate the concept of a chapter opening on its own page, for example.
Default: true

 **Inaccesible pages!**

The file splits are controlled by the counter FileDepth and the boolean CombineHigherDepths. Setting FileDepth to 0 splits the file at chapters, 1 at sections, etc. CombineHigherDepths controls whether to combine pages at levels higher than the chosen FileDepth, such as in this tutorial where the page which opens the chapter also contains the first section. Be careful to set tocdepth and SideTOCDepth to allow access to each page of the website. Set tocdepth and SideTOCDepth to be greater than or equal to FileDepth.

⚠ Lost in an old page!

When making changes to the file structure, it is possible to end up with the web browser pointing to an old file which is no longer in use. When this occurs, changes to the web site will not appear in the browser, even if reloading the page, because that page is no longer in use. It is best to return to the home page, clean the files (`lwarpmk cleanall`), change `FileDepth` and/or `CombineHigherDepths`, then finally recompile and renavigate to the desired page using the new file structure.

Bool `FileSectionNames`
Default: `true`

FileSectionNames: If true, web page filenames are derived from a sanitized version of the section names. If false, web pages are numbered. Either way, the `HTMLFilename` option is used as a prefix. See section [8.4.1](#) for examples of naming and numbering HTML files. The user must ensure that filenames are unique after begin sanitized. For example, math in the section name is removed before creating the filename, so the rest of the filename must be sufficiently unique to avoid name collisions.

Ctr `FootnoteDepth`
Default: `3`

FootnoteDepth: Determines where to place pending footnotes. 3 places footnotes before each break down to the \subsubsection level. 1 places footnotes before each \section break. Any pending footnotes are also placed at the bottom of each page before each file break.

Bool `HTMLDebugComments`
Default: `false`

HTMLDebugComments: Set true to generate HTML comments, such as which section or `<div>` is being opened or closed.

\abstractname
Default: `Abstract`

\abstractname: The name of the abstract. This may also be over-written by the `babel` package. Defaults to “Abstract”.

Placed before `\begin{document}`, or before any sectioning command which causes a file break:

\CSSFilename
Default: `lwarp.css`

\CSSFilename: {`<filename.css>`} Sets the css file to use for the following files. May be changed before each each sectioning command which would cause a file split.

The css styles of the web pages are set by the `\CSSFilename` command. If `\CSSFilename` is not used, a default plain style is used to mimic printed L^AT_EX output. `lwarp_sagebrush.css` is a semi-fancy colored style as shown in this tutorial. Change it to `lwarp_formal.css` for a more formal look, or comment out the `\CSSFilename` command to see the default. `\CSSFilename` may be used before each file break to set the css for individual pages of the website.

\HTMLLanguage
Default: `en-US`

\HTMLLanguage: {`<language>`} The HTML file’s `html lang` meta tag. Defaults to `en-US`.

\HTMLTitle
Default: `\thetitle`

\HTMLTitle: {`<title>`} Overrides `\title` for the HTML header’s meta title. Defaults to `\thetitle`, which is set by `\title`, or empty otherwise. Un-

like the author, `\thetitle` is set by `\title` even if not using the **titling** package.

`\HTMLAuthor`
Default: `\theauthor`

`\HTMLAuthor: {<author>}` The HTML header's meta author. Defaults to `\theauthor`, which is set by `\author` if using the **titling** package, but is empty otherwise. There are several ways to represent the author and affiliations, especially if using the **authblk** package, most of which do not result in a sensible `\theauthor`, so `\HTMLAuthor` is useful to create a list of authors without their affiliations.

`\HTMLDescription`
Default: `<empty>`

`\HTMLDescription: {<description>}` Sets the HTML `description` tag for the following files. May be changed before each each sectioning command which would cause a file split.

`\HTMLFirstPageTop`
Default: `<empty>`

`\HTMLFirstPageTop: {<contents>}` A user-definable custom action applied to the top of the home page. Useful for logos, etc. Defaults empty. Ignored in print output.

`\HTMLPageTop`
Default: `<empty>`

`\HTMLPageTop: {<contents>}` A user-definable custom action applied to the top of pages other than the home page. Useful for logos, etc. Defaults empty. `\LinkHome` may be used to place a link back to the homepage. Ignored in print output.

`\HTMLPageBottom`
Default: `<empty>`

`\HTMLPageBottom: {<contents>}` A user-definable custom action applied to the bottom of each web page. Useful for authors, copyright notices, contact information, etc. Defaults empty. `\LinkHome` may be used to place a link back to the homepage. Ignored in print output.

Placed in the home page before the first sectioning command which causes a file break:

 `\tableofcontents`
TOC on the homepage!

`\tableofcontents:` Used to place a table of contents on the home page. This command must be used before the first file split, so that a way is available to navigate to other files from the homepage.

Links to each chapter/section are provided, as selected by `tocdepth`.

Placed in the document wherever necessary:

`\mathimagename`
Default: `math image`

`\mathimagename:` When creating an SVG math image, its `alt` tag may be set to the math expression, which may be hashed for image reuse. In the case of `\ensuremath` or after `\inlinemathother`, where the contents require a unique image for each instance of the same expression, the `alt` tag is set to `\mathimagename`, and the image is not reused.

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "math image",

and it may be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following SVG math images.

\packagediagramname
Default: diagram

\packagediagramname: For many packages, the output is placed inside a `latexitimage` with an HTML alt tag set to the package name followed by \packagediagramname. For example:

(-xy- diagram)

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "diagram", and may it be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following `latexitimages`.

Env warpprint

warpprint: An environment which is only used while generating print output. Place inside anything which does not apply to HTML and which may cause problems with **lwarf**. If **lwarf** knows about and emulates or supports a package then its related macros, lengths, counters, etc. probably won't have to be placed inside a warpprint environment, but unknown packages may cause problems which may be isolated from **lwarf** using this environment.



Do not place anything else on the same line as \end{warpprint}.

Env warpHTML

warpHTML: An environment which is only used while generating HTML output. This is useful for website logos and other items which have no purpose in printed output.



Do not place anything else on the same line as \end{warpHTML}.

\warpprintonly

\warpprintonly: {<contents>} A macro version of the warpprint environment.

\warpHTMLonly

\warpHTMLonly: {<contents>} A macro version of the warpHTML environment.

8.4.1 Example HTML file naming

Examples of ways to name or number HTML files:

Numbered HTML nodes:

Example: Homepage `index.html`, and `node-1`, `node-2`.¹³

¹³See `\SetHTMLFileName` to number in groups by chapter, for example.

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={node-}
]{lwarf}
\boolfalse{FileSectionNames}
```

Named HTML sections, no prefix:

Example: index.html, and About.html, Products.html

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={}
]{lwarf}
\booltrue{FileSectionNames}
```

Named HTML sections, with prefix:

Example: Homepage mywebsite.html, and additional pages such as mywebsite-About.html, mywebsite-Products, etc.

```
\usepackage[
    HomeHTMLFilename=mywebsite,
    HTMLFilename={mywebsite-}
]{lwarf}
\booltrue{FileSectionNames}
```

8.5 Customizing the CSS

\CSSFilename **Default: lwarf.css** \CSSFilename may be used to choose which .css file is used to display each page of the web site. Use \CSSFilename before \begin{document} to assign the style of the home page. If different parts of the website should have different styles, call \CSSFilename again before each section heading which creates a new file. This may be changed numerous times throughout the file, resulting in different HTML pages having different css files assigned:

```
...
\CSSFilename{myCSS.css}
\chapter{Another Chapter}
...
```

The styles provided by lwarf include:

lwarf.css: A default style if \CSSfilename is not used. This style is comparable to a plain L^AT_EX document. To set this style, you may use \CSSfilename{lwarf.css}, or no \CSSfilename call at all.

lwarf_formal.css: A formal style with a serif fonts and a traditional look.

lwarf_sagebrush.css: A style with muted colors, gradient backgrounds, additional borders, and rounded corners.

To see each style in use, change the \CSSfilename entry in the tutorial, lwarfpmk html again, and then reload the tutorial webpage.

Custom css A customized style may also be created. For each new project a file called sample_project.css is generated. This may be renamed to <project>.css then used by assigning \CSSfilename{<project>.css}.

 **Rename it!** Note that sample_project.css is overwritten whenever lwarf is loaded in print mode. It is therefore important to rename the file to something like <project>.css before using it, so that your own changes are not overwritten.

<project>.css has an entry which loads lwarf.css, and this entry may be changed to load lwarf_formal.css or lwarf_sagebrush.css if desired. Additional changes to the css may be made by making entries later in the <project>.css file.

File lwarf.css It is best to make a local project-specific css file such as project.css, containing only things which are different from lwarf.css. The file project.css should refer to lwarf.css as follows:

```
/* ( --- Start of project.css --- ) */
/* ( --- A sample project-specific CSS file for lwarf --- ) */

/* Uncomment one of the following: */
@import url("lwarf.css") ;
/* @import url("lwarf_formal.css") ; */
/* @import url("lwarf_sagebrush.css") ; */

/* Project-specific CSS setting follow here. */
/* . . . */

/* ( --- End of project.css --- ) */
```

Finally use \CSSfilename{<project>.css} in the document to activate the custom CSS.

8.6 Selecting the operating system

Prog Unix	lwarf tries to detect which operating system is being used. UNIX / MAC OS / LINUX is the default (collectively referred to as “UNIX” in the configuration files), and MS-WINDOWS is supported as well.
Prog Mac OS	
Prog Linux	
Prog MS-Windows	If MS-WINDOWS is not correctly detected, use the lwarf option <code>OSWindows</code> .
Prog Windows	
Opt OSWindows	When detected or specified, the operating-system path separator used by lwarf is modified, and the boolean <code>usingOSWindows</code> is set true. This boolean may be tested by the user for later use.

8.7 Selecting actions for print or HTML output

The following environments and macros are used to select actions which only apply to either traditional L^AT_EX print-formatted PDF generation, or to HTML generation.

For most of built-in L^AT_EX and many additional packages there is user-level source code support or emulation, so no special handling will be required. For those cases which **lwarf** does not handle by itself, the following environments and macros may be used to isolate sections of code for print-only or HTML-only.

These environments are also useful for creating a special version of the titlepage for print and another for HTML.

Env <code>warpHTML</code>	Anything which is to be done only for HTML5 output is surrounded by a <code>warpHTML</code> environment:
---------------------------	--

```
\begin{warpHTML}
  ... something to be done only during HTML generation
\end{warpHTML}
```

 `\end{warpHTML}` Do *not* place anything else on the same line as `\end{warpHTML}`. The exact phrase is used to mark the end of the environment.

Env <code>warpprint</code>	Anything which is to be done only for print output is surrounded by a <code>warpprint</code> environment:
----------------------------	---

```
\begin{warpprint}
  ... something to be done only during traditional PDF generation
\end{warpprint}
```

⚠ `\end{warpprint}` As above, do not place anything else on the line with `\end{warpprint}`.

Env `warpall` Anything which is to be done for any output may be surrounded by a `warpall` environment. Doing so is optional.

```
\begin{warpall}
  ... something to be done during print PDF or HTML output
\end{warpall}
```

As above, do not place anything else on the line with `\end{warpall}`.

Macros are also provided for print-only or HTML-only code:

`\warpprintonly {<actions>}`

Performs the given actions only when print output is being generated.

`\warpHTMLonly {<actions>}`

Performs the given actions only when HTML output is being generated.

8.8 Commands to be placed into the `warpprint` environment

Certain print-related commands should always be placed inside a `warpprint` environment, or may need other special handling. These are unrelated to HTML output, but are hard to isolate automatically. For example:

- Paragraph formatting: `\parindent \parskip`
- Manual page positions such as the `textpos` package, which is emulated but only in a limited way.
- Anything changing the page counter. `lwarp` requires that the page counter not be adjusted during HTML output.

Some packages require additional setup commands. Where these packages are emulated for HTML, setup commands may work for the emulated HTML output as well as for print output. See the details for each package in this document for more information.

Also see section 14: [Troubleshooting](#).

8.9 Title page

In the preamble, place an additional block of code to set the following:

```
\title{Document Title} % One line only
\author{Author One\affiliation{Affiliation One} \and
        Author Two\affiliation{Affiliation Two} }
\date{Optional date}
```

The title is used in the meta tags in the `HTML` files, unless overridden by `\HTMLTitle`, and the rest are used in `\maketitle`. To use a `\subtitle` or `\published` field, see section 63.8.

`\maketitle` Use `\maketitle` just after the `\begin{document}`, as this will establish the title of the homepage. Optionally, use a `titlepage` environment instead.

`Env titlepage` The `titlepage` environment may be used to hold a custom title page. The `titlepage` will be set in a `<div>` class `titlepage`, and `\printtitle`, etc. may be used inside this environment.

`Env titlingpage` Another form of custom title page, where `\maketitle` is allowed, and additional information may be included as well.

`\title {\langle title\rangle}`

⚠ newlines Avoid newlines in the `\title`; these will interfere with the file break and css detection. Use a `\subtitle` command instead (section 63.8). The title will appear in the document `\maketitle` as a heading `<h1>`. The `HTML` meta `title` tag will also have this title, unless `\HTMLTitle` is used to set the meta title to something else instead.

`\author {\langle author\rangle}`

In `\author`, `\protect` may be needed before some formatting commands. In `HTML`, the author will appear in a `<div>` of class `author` in the `\maketitle`. If the `titling` package is used, the author will also appear in a `HTML` meta tag, but `\HTMLAuthor` may be necessary to create a plain list of names if `\author` had affiliations added. `\affiliation` is a new addition to `lwrap`.

`\date {\langle date\rangle}`

`\date` works as expected. In `HTML`, this will appear in a `<div>` class `titledate`.

`\thanks {\langle text\rangle}`

`\thanks` are allowed in the `titlepage` fields, and will be rendered as `HTML` notes at the bottom of the title page.

8.10 HTML page meta descriptions

\HTMLDescription {\(A description of the web page.)} The default is no description.

limitations Each page of HTML output should have its own HTML meta description, which usually shows up in web search results, is limited to around 150 characters in length, and should not include the ASCII double quote character ('').

placement Use \HTMLDescription just before \begin{document} to set the description of the home page, and also just before each sectioning command such as \chapter or \section where a new file will be generated, depending on FileDepth. For example, if FileDepth is 1, use \HTMLDescription just before each \section command, and that description will be placed inside the HTML page for that \section. The same description will be used for all following HTML files as well, until reset by a new \HTMLDescription. It is best to use a unique description for each HTML file.

disabling To disable the generation of HTML description meta tags, use:

```
\HTMLDescription{}
```

8.11 HTML page meta title

\HTMLTitle {\(title)} Sets the contents of the web page <meta name="title"> element. Defaults to \HTMLtitle{\thetitle}. May be set empty to cancel the meta title tag.

8.12 HTML page meta author

\HTMLAuthor {\(author)} Sets the contents of the web page <meta name="author"> element. Defaults to \HTMLAuthor{\theauthor}. May be set empty to cancel the meta author tag.

\author may be used to create a list of authors and their affiliations, in several formats if using **authblk**, and these may not successfully parse properly into a sensible list for \theauthor. \HTMLAuthor may be used to set the meta tag to a simple list of names.

9 Special cases and limitations

Some commonly-used L^AT_EX expressions should be modified as follows to allow for a smooth conversion to both HTML and print-formatted outputs.

Need help?

The index to this document contains several hundred custom entries. Also included are automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category. A [Troubleshooting](#) section is also available.

9.1 Things to avoid

In the document, avoid the following:

page counter: Do not adjust the page counter. If doing so is required for the print version, place the adjustment inside a `\warpprint` environment.

Custom math environment macros: Do not use expressions such as `\beq` as a replacement for `\begin{equation}`.

Custom macros in section, figure, table names: Custom macros which appear in sectioning commands or float captions then appear in the `.toc`, `.lof`, and `.lot` lists, and should be made robust using `\newrobustcmd` or `\robustify` from `etoolbox`, `xparse`, etc.

When setting `FileSectionNames` to `true` to name the `HTML` files from the section names, the file names are created from sanitized versions of the chapter or section names, but the section names must be plain text or something which expands into plain text. Robust macros will not work at the sectioning level which is used for file names, but a robust macro or other complicated name may be used for the mandatory argument of `\chapter`, `\section`, etc., if a plain-text version is also included in the optional argument:

```
\chapter[Plain Name]{\ARobustMacro{Fancy Name}}
```

9.2 Formatting

9.2.1 Text formatting

 `\bfseries`, etc. `\textbf`, etc. are supported, but `\bfseries`, etc. work only in some situations.

 **HTML special chars** `&`, `<`, and `>` have special meanings in `HTML`. If `\&`, `\textless`, and `\textgreater` are used, proper `HTML` entities will be used, but there may be `HTML` parsing problems if these special characters occur unescaped in program listings or other verbatim text.

program listings For program listings, the `listings` package is supported, and its `literate` option is used to convert `&`, `<`, and `>` to proper `HTML` entities.

verbatim The various `verbatim`-related environments do not convert `&`, `<`, and `>`, so care must be taken to avoid accidentally including valid `HTML` code inside these environments. Adding a space on either side may be sufficient.

9.2.2 Horizontal space

\hspace \hspace is converted to an inline HTML span of the given width, except that 0 width is ignored, a width of .16667em is converted to an HTML thin breakable space (U+2009), and a \fill is converted to a \qquad.

\, ~ and \,, are converted to HTML entities.

\kern \kern and \hskip are entered into the HTML PDF output as-is, then interpreted by \hskip **pdftotext**, and thus usually appear as a single space.

9.2.3 Text alignment

Use the environments center, flushright, flushleft instead of the macros \centering, \raggedright, \raggedleft.

⚠ figure & table \centering, etc. are honored in a figure or table if they are the first command inside the float:

```
\begin{table*}
\centering
\caption{A Table}
...
```

9.2.4 Accents

Native L^AT_EX accents such as \" will work, but many more kinds of accents are available when using Unicode-aware X^AL_ET_EX and LuaL^AT_EX.

9.2.5 textcomp package

Pkg textcomp Some **textcomp** symbols do not have Unicode equivalents, and thus are not supported.

⚠ missing symbols Many **textcomp** symbols are not supported by many fonts. In the CSS try referencing fonts which are more complete, but expect to see gaps in coverage.

9.2.6 Superscripts and other non-math uses of math mode

Use x instead of \${}^x\$

9.2.7 Empty \item followed by a new line of text or a nested list:

lists Use a trailing backslash: \item[label] \

9.2.8 Filenames and URLs in lists or footnotes

filename underscore Escape underscores in the filenames:

```
\item[\href{file\_name.pdf}{text}]
```

9.2.9 relsize package

Pkg **relsize** For HTML, only the inline macros are supported: \textlarger, \textsmaller, and \textscale. Each becomes an inline span of a modified font-size.

\relsize, \larger, \smaller, and \relscale are ignored.

While creating SVG math for HTML, the original definitions are temporarily restored, and so should work as expected.

 **not small** The HTML browser's setting for minimum font size may limit how small the output will be displayed.

9.3 Boxes and minipages

9.3.1 Marginpars

\marginpar [⟨left⟩] {⟨right⟩} \marginpar may contain paragraphs, but in order to remain inline with the surrounding text **l warp** nullifies block-related macros inside the \marginpar. Paragraph breaks are converted to
 tags.

\marginparBlock [⟨left⟩] {⟨right⟩} To include block-related macros, use \marginparBlock, which takes the same arguments but creates a <div> instead of a . A line break will occur in the text where the \marginBlock occurs.

9.3.2 Save Boxes

TeX boxes are placed inline and do not allow line breaks, so boxes with long contents may overflow the line during HTML conversion. This is mostly a problem when the boxes contain objects which themselves hold large HTML tags, such as rotation

commands with long contents. When this object overflows the line, some HTML code will be lost and the page will be corrupted.

9.3.3 Minipages

- ⚠ **inline** A line of text with an inline minipage or parbox will have the minipage or parbox placed onto its own line, because a paragraph is a block element and cannot be made `inline-block`.
- placement** Minipages and parboxes will be placed side-by-side in HTML unless you place a `\newline` between them.
- side-by-side** Side-by-side minipages may be separated by `\quad`, `\quad`, `\enskip`, `\hspace`, `\hfill`, or a `\rule`. When inside a `center` environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side minipages and these spacing commands, but not at the start or end of the paragraph.
- in a span** There is limited support for minipages inside an HTML ``. An HTML `<div>` cannot appear inside a ``. While in a ``, minipages, and parboxes, and any enclosed lists have limited HTML tags, resulting in an “inline” format, without markup except for HTML breaks. Use `\newline` or `\par` for an HTML break.
- size** When using `\ linewidth`, `\ textwidth`, and `\ textheight`, widths and heights are scaled proportionally to a 6×9 inch text area.
- no-width minipages** A minipage of width exactly `\ linewidth` is automatically given no HTML width.
- full-width minipages** A new macro `\minipagewhilewidth` requests that the next minipage be generated without an HTML `width` attribute, allowing it to be the full width of the display rather than the fixed width given.
- ⚠ **text alignment** Nested minipages adopt their parent’s text alignment in HTML, whereas in regular L^AT_EX PDF output they do not. Use a `flushleft` or similar environment in the child minipage to force a text alignment.

9.3.4 Side-by-side minipages

Place side-by-side minipages inside a `center` environment, with horizontal space between them, such as `\quad`, `\quad`, `\hspace`, or `\hfill`. The result is similar in print and HTML. Do not use space commands at the start or end of the line.

9.3.5 Framed minipages and other environments

\fbox can only be used around inline `` items during HTML output, but HTML cannot place a block element such as a `<div>` for a minipage or a list inside of a ``. Several options are provided for framing an object, depending on which kind of object and which packages are loaded:

`\fbox` For a framed object, options include:
`\fboxBlock`

`Env fminipage` **To remove the frame in HTML output:** Place the `\fbox` command and its closing brace inside `\warpprint` environments. This will nullify the frame for HTML output.

For inline text: **To frame the contents inline with some formatting losses in HTML:** This is the default action of `\fbox` when enclosing a minipage. During HTML output, `\fbox` nullifies the HTML tags for `minipage`, `\parbox`, and lists. The contents are included as inline text inside the `\fbox`'s `` of class `framebox`. For lists, line breaks are converted to HTML breaks. The result is a plain-text inline version of the contents, framed inline with the surrounding text, but lacking any extra HTML markup.

For inline `minipage` and lists: **To frame the contents on their own line with improved formatting in HTML:** A new command `\fboxBlock` is included, intended to be a direct replacement for `\fbox` for cases where the `\fbox` surrounds a minipage, table, or list. For print output, this behaves as `\fbox`. For HTML output, the contents are placed inside an HTML `<div>` with the class `framed`, resulting in the contents being placed on their own line with a frame surrounding them. The contents preserve their HTML formatting, so lists and minipages look nicer, and valid HTML is created for a `tabular`. While an `\fbox` containing a `tabular` is valid L^AT_EX code, the result in HTML is problematic since a table is a `<div>` not a ``, so use `\fboxBlock` around a `tabular`, or else place the `tabular` inside a `minipage`, or use `fminipage`, described next. Also see below regarding the “Misplaced alignment tab character &.” error.

For display `tabular`, `minipages`, and lists: **To create a framed minipage in both print and HTML:** A new environment `fminipage` is included. For print output, this is identical to `minipage`, except that it is also framed. For HTML output, this forms a `<div>` of class `framed`, the contents preserve their HTML formatting, and valid HTML is created for a `tabular`. Also see below regarding the “Misplaced alignment tab character &.” error.

colored boxes and frames: **To create colored frames and boxes:** See section 427 for `xcolor`'s `\colorbox` and `\fcolorbox`, and `l warp`'s additional `\colorboxBlock` and `\fcolorboxBlock`.

To frame tables or verbatim environments: Place the contents inside a `fminipage`, or perhaps a `\fboxBlock` for a `tabular`. Also, if using `\fboxblock` with `tabular`, you will have to use `\StartDefiningTabulars` before the start of the

⚠ Misplaced alignment tab character &

macro which uses \fboxBlock and the tabular, and \StopDefiningTabulars afterwards. Also see the **l warp** documentation for the **fancybox** package.

To frame equations: See section 195 for the **fancybox** package.

For fancy framed minipages: See packages **boxedminipage**, **shadow**, **fancybox**, **framed**, **mdframed**.

Custom environments: Use a custom environment to create a sidebar, containing a BlockClass environment with custom css formatting, and \warpprintonly{\hrule} command:

```
\begin{BlockClass}{frameminipage}% ignored in print output
    % use CSS to format div class ``frameminipage''
    \warpprintonly{\hrule} % only appears in print output
    Contents
    \warpprintonly{\hrule} % only appears in print output
\end{BlockClass}
```

9.3.6 fancybox package

Pkg fancybox framed equation example

fancybox's documentation has an example FramedEqn environment which combines math, \Sbox, a minipage, and an \fbox. This combination requires that the entire environment be enclosed inside a **lateximage**, which is done by adding \bgroup at the very start of FramedEqn's beginning code, and \egroup at the very end of the ending code. Unfortunately, the **HTML alt** attribute is not used here.

```
\newenvironment{FramedEqn}
{
\bgroup
\latextimage% NEW
\setlength{\fboxsep}{15pt}
...}{...
\[\fbox{\TheSbox}\]
\egroup
```

framing alternatives \fbox works with **fancybox**. Also see **l warp**'s \fboxBlock macro and fminipage environment for alternatives to \fbox for framing environments.

framed table example

The **fancybox** documentation's example framed table using an \fbox containing a tabular does not work with **l warp**, but the **FramedTable** environment does work if \fbox is replaced by \fboxBlock. This method loses **HTML** formatting. A better method is to enclose the table's contents inside a fminipage environment. The caption may be placed either inside or outside the fminipage:

```
\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
...
\end{tabular}
\end{fminipage}
\end{table}
```

- ⚠ **framed verbatim** **l warp** does not support the `verbatim` environment inside a span, box, or `fancybox`'s `\Sbox`, but a `verbatim` may be placed inside a `fminipage`. The `fancybox` documentation's example `FramedVerb` may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
\VerbatimEnvironment
\fminipage{#1}
\begin{Verbatim}
\end{Verbatim}
\endfminipage
}
```

framed \VerbBox `fancybox`'s `\VerbBox` may be used inside `\fbox`.

indented alignment `LVerbatim`, `\LVerbatimInput`, and `\LUseVerbatim` indent with horizontal space which may not line up exactly with what `pdftotext` detects. Some lines may be off slightly in their left edge.

9.3.7 mdframed package

Pkg **mdframed support** Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for `mdframed` environments and frame titles.

- ⚠ **loading** When used, **l warp** loads `mdframed` in HTML with `framemethod=none`.

font For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where `\textbf` must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the `mdframed`

source). Since **lwarf** does not support `\bfseries` and friends, only one font selection may be made at a time.

theoremtitlefont `theoremtitlefont` is not supported, since the following text is not in braces in the `mdframed` source.

footnotes Footnotes are currently placed at the bottom of the HTML page.

ignored options `userdefinedwidth` and `align` are currently ignored.

9.4 Cross-references

⚠️ labels Labels with special characters may be a problem. It is best to stick with alphanumeric, hyphen, underscore, and perhaps the colon (if not French).

⚠️ \nameref `\nameref` refers to the most recently-used section where the `\label` was defined. If no section has been defined before the `\label`, the link will be empty. Index entries also use `\nameref` and have the same limitation.

9.4.1 Page references

⚠️ ⓁTeX page numbers The printed page does not translate to the HTML page, so `\pageref` references are converted to parentheses containing `\pagerefPageFor`, which defaults to “see”, followed by a hyperlink to the appropriate object.

Ex:

```
\ref{sec:name} on page \pageref{sec:name}
in HTML becomes:
“Sec. 1.23 on page (see sec. 1.23)”.
```

`\pagerefPageFor` may be redefined to “page for”, empty, etc. See page 474.

9.4.2 cleveref and varioref packages

Pkg cleveref `cleveref` and `varioref` are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to “for”.

⚠️ cleveref page numbers

Ex:

```
\cpageref{tab:first,tab:second}
in HTML becomes:
“pages for table 4.1 and for table 4.2”
```

See `\cpagerefFor` at page 552 to redefine the message which is printed for page number references.

9.4.3 Hyperlinks, hyperref, and url

Pkg `hyperref` **lwarf** emulates `hyperref`, including the creation of active hyperlinks, but does not require that `hyperref` be loaded by the document.

 **comments between arguments** Do not place a comment with a % character between arguments for `\hyperref`, etc., as it is neutralized for inclusion in HTML URLs.

lwarf can also load `url`, but `url` should not be used at the same time as `hyperref`, since they both define the `\url` command. **lwarf** does not (yet) attempt to convert `url` links into hyperlinks during HTML output, nor does `url` create hyperlinks during print output.

 **backref** When generating HTML, **lwarf**'s emulation of `hyperref` does not automatically load `backref`, so `backref` must be loaded explicitly.

9.4.4 Footnotes and page notes

lwarf uses native L^AT_EX footnote code, although with its own `\box` to avoid the L^AT_EX output routine. The usual functions mostly work as-is.

The `footmisc` stable option is emulated by **lwarf**.

 **sectioning commands** When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the `footmisc` package with the `stable` option, provide a short TOC entry, and `\protect` the `\footnote`:

```
\usepackage[stable]{footmisc}
...
\subsection[Subsection Name]
{Subsection Name\protect\footnote{A footnote.}}
```

 **memoir** If using `memoir` class, with which **lwarf** preloads `footmisc`, the `stable` option must be declared before **lwarf** is loaded:

```
\PassOptionsToPackage{stable}{footmisc}
\usepackage{lwarf}
...
```

Do not use a starred sectioning command. As an alternative, it may be possible to adjust `\secnumdepth` instead.

 **\VerbatimFootnotes** If using `fancybox` or `fancyvrb` with `\VerbatimFootnotes`, and using footnotes in a

⚠️ sectioning or displaymath sectioning command or display math, use `\footnotemark` and `\footnotetext`:

```
\subsection[Subsection Name]
{Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbatim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when `\VerbatimFootnotes` are selected. The browser usually compensates.

⚠️ pfnote numbers While emulating `pfnote`, **l warp** is not able to reset HTML footnote numbers per page number to match the printed version, as `HTML` has no concept of page numbers. **l warp** therefore uses continuous footnote numbering even for `pfnote`.

9.5 Front and back matter

9.5.1 Custom classes with multiple authors and affiliations

Some classes allow multiple authors and affiliations. Often it is possible to emulate these using a standard class along with `authblk`:

```
%\documentclass{customclass} % for print document
\documentclass{article} % for HTML document

\usepackage{l warp}
\begin{warpHTML}
\usepackage{authblk}
\let\affiliation\affil % maybe required
\end{warpHTML}
```

9.5.2 Starred chapters and sections

The following describes `\ForceHTMLPage` and `\ForceHTMLTOC`, which may be used for `endnotes`, `glossaries`, `tocbibind`, and the index. See the following sections where applicable. Continue here if interested in the reason for adding these commands to **l warp**.

Some packages use `\chapter*` or `\section*` to introduce reference material such as notes or lists, often to be placed in the back matter of a book. These starred sections are placed inline instead of on their own HTML pages, and they are not given TOC entries.

l warp provides a method to cause a starred section to be on its own HTML page, subject to `FileDepth`, and also a method to cause the starred section to have its own TOC entry during HTML output.

`\ForceHTMLPage` To place a starred section on its own HTML page, use `\ForceHTMLPage` just before the `\chapter*` or `\section*`. **l warp** will create a new page for the starred sectional unit.

A starred sectional unit does not have a TOC entry unless one is placed manually. The typical method using `\phantomsection` and `\addcontentsline` works for inline text but fails when the new starred section is given its own webpage after the TOC entry is created, or when creating an EPUB where the TOC entry will point to the page before the starred section. If the starred section has its own HTML page but no correct TOC entry pointing to that page, the page will be inaccessible unless some other link is created.

`\ForceHTMLTOC` To automatically force the HTML version of the document to have a TOC entry for a starred section, use `\ForceHTMLTOC` just before the `\chapter*` or `\section*`, and place `\phantomsection` and `\addcontentsline` inside a `\warpprint` environment.

For print output, `\ForceHTMLTOC` and `\ForceHTMLPage` have no effect.

9.5.3 abstract package

Pkg `abstract` If using the `number` option with file splits, be sure to place the table of contents before the abstract. The `number` option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

⚠️ missing TOC

9.5.4 titling and authblk

Pkg `titling` **l warp** supports the native L^AT_EX titling commands, and also supports the packages `authblk` and `titling`. If both are used, `authblk` should be loaded before `titling`.

Pkg `authblk`

package support If using the `titling` package, additional titlepage fields for `\published` and `\subtitle` may be added by using `\AddSubtitlePublished` in the preamble. See section 63.8.

⚠️ load order

`\published` and `\subtitle`

9.5.5 tocloft package

Opt `tocloft` titles If using `tocloft` with `tocbibind`, `anonchap`, `fncychap`, or other packages which change chapter title formatting, load `tocloft` with its `titles` option, which tells `tocloft` to use standard L^AT_EX commands to create the titles, allowing other packages to work with it.

Pkg `tocloft`

Pkg `tocloft`

⚠️ tocloft & other packages

9.5.6 appendix package

Pkg `appendix` During HTML conversion, the option `toc` without the option `page` results in a `toc` link to whichever section was before the `appendices` environment. It is recommended to use both `toc` and also `page` at the same time.

9.5.7 pagenote package

Pkg `pagenote` **pagenote** works as-is, but the `page` option is disabled.

9.5.8 endnotes package

Pkg `endnotes` To place the endnotes in the TOC, use:

table of contents

```
\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*\notesname{Endnotes} % optional
```

HTML page To additionally have the endnotes on their own HTML page, if `FileDepth` allows:

```
\ForceHTMLPage
\theendnotes
```

9.5.9 BibTeX

`\etalchar` Displays a superscript “+” to indicate “and others”.

⚠️ Modify `*.bib` When enough authors are cited for a source, `BIBTEX` may use the `\etalchar` command to display a math superscript with a + character to indicate “and others”. Without modification, this will result in an “Improper `\prevdepth`” error. At present, **l warp** requires that `\etalchar` be replaced by a text superscript. To do so, add to the start of the `.bib` file the following:

```
@PREAMBLE{"\let\etalchar\relax \newcommand{\etalchar}[1]{\textsuperscript{#1}}"}
```

9.5.10 glossaries package

Pkg `glossaries` **l warp mk** has the commands `l warp mk printglossary` and `l warp mk htmlglossary`, which process the glossaries created by the `glossaries` package using that package’s `makeglossaries` command.

processing glossaries

Opt `GlossaryCmd`

Default: `makeglossaries`

Opt `l warp mk printglossary`

Opt `l warp mk htmlglossary`

The shell command to execute is set by the `lwarf` option `GlossaryCmd`, which defaults to `makeglossaries`. The print or HTML glossary filename is appended to this command.

 `makeglossaries` not found

In some situations it may be required to modify the default command, such as to add the `perl` command in front:

```
\usepackage[
    GlossaryCmd={perl makeglossaries},
] {lwarf}
```

`xindy language` To set the language to use for processing glossaries with `xindy`:

```
\usepackage[
    GlossaryCmd={makeglossaries -L english},
] {lwarf}
```

Other options for `makeglossaries` may be set as well.

`placement and toc options` The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

Numbered section, on its own HTML page:

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
...
\printglossaries
```

Unnumbered section, inline with the current HTML page:

```
\usepackage[xindy,toc]{glossaries}
...
\printglossaries
```

Unnumbered section, on its own HTML page:

```
\usepackage[xindy,toc]{glossaries}
...
\ForceHTMLPage
\printglossaries
```

 `glossary style` The default `style=item` option for `glossaries` conflicts with `lwarf`, so the style is forced to `index` instead.

 `number list` The page number list in the printed form would become `\nameref`s in HTML, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

`print/HTML versions` The print and HTML versions of the glossary differ in their internal page numbers. Separate commands for generating print and HTML glossaries are used, even though the page number is currently ignored.

9.5.11 Indexing overview

There are many ways to process indexes for a \LaTeX document, including native \LaTeX capabilities, a number of packages and classes, the possible availability of shell escape and `latexmk`, and the need to process print and HTML versions. `lwarf` attempts to provide easy recompilation of indexes along with the rest of the document, but the various indexing options must be set correctly. Numerous examples are given below. Some differ in minor details, so the important parts are highlighted in red, and options are in green.

Once set up properly, the entire document may be recompiled with `lwarpmk print` and `lwarpmk html`. In some cases, it will also be necessary to compile the indexes with `lwarpmk printindex` and `lwarpmk htmlindex`. A recompile may then be forced with `lwarpmk print1` and `lwarpmk html1`.

manual processing The user may continue to process indexes manually or by shell script without the use of `lwarpmk`, but adjustments will be required to process HTML indexes as well. In general, `*.idx` and `*.ind` files will be accompanied by `*_html.idx` and `*_html.ind` files.

custom index style If using a custom indexing style file, see sections 9.5.17 and 9.5.18.

source code See section 73 for `lwarf`'s core index and glossary code, section 251 for `index`, section 368 for `splitidx`, section 249 for `imakeidx`, section 398 for `tocbibind`, and section 440.17 for `memoir`'s indexing patches.

9.5.12 Indexing with basic \TeX and `makeidx`

lwarpmk processing The following allow the user to process indexes automatically, or using `lwarpmk`'s commands:

Enter ⇒ `lwarpmk printindex`

Enter ⇒ `lwarpmk htmlindex`

For a single index using `makeindex`:

```
\usepackage[makeindex,latexmk]{lwarf}
```

The usual `.idx` and `.ind` files will be used, along with the new `lwarf.ist` style file. When creating the HTML index, “`_html`” is automatically appended to each of the names.

`lwarpmk` will use `latexmk` if specified, in which case `latexmk` will create the index automatically. Otherwise, use

Enter ⇒ `lwarpmk printindex`

Enter ⇒ lwarfpmk htmlindex
to compile the indexes.

For a single index using xindy:

```
\usepackage[  
    xindy,  
    xindyLanguage=english,  
    xindyCodepage=utf8,  
    latexmk  
]{lwarf}
```

The usual .idx and .ind files will be used, along with the new lwarf.xdy style file.

lwarfpmk will use **latexmk** if specified, in which case **latexmk** will create the index automatically. Otherwise, use

```
Enter ⇒ lwarfpmk printindex  
Enter ⇒ lwarfpmk htmlindex  
to compile the indexes.
```

9.5.13 Indexing with index

lwarf is told how to use **makeindex** using the PrintIndexCmd and HTMLIndexCmd options. The file lwarf.ist is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

For multiple indexes using makeindex and index:

(Assuming that the second index has file extensions .sist and .sind)

```
\usepackage[
    makeindex, latexmk,
    PrintIndexCmd={
        makeindex -s lwarf.ist <projectname>.idx ;
        makeindex -s lwarf.ist
            -o <projectname>.sind <projectname>.sidx
    },
    HTMLIndexCmd={
        makeindex -s lwarf.ist <projectname>_html.idx ;
        makeindex -s lwarf.ist
            -o <projectname>_html.sind <projectname>_html.sidx
    }
]{lwarf}
\usepackage{index}
...
\makeindex
\newindex{secondname}{sidx}{sind}{Second Index}
```

 **WINDOWS**

For WINDOWS, replace the two ";" characters with "&".

When creating the HTML index, "_html" is automatically appended to the index filenames.

Use

```
Enter ⇒ lwarpmk printindex
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

If the `latexmk` option is selected for `lwarf`, `latexmk` will compile the document but will *not* compile the indexes. `lwarpmk printindex` and `lwarpmk htmlindex` will still be required.

9.5.14 Indexing with splitidx

`lwarf` is told how to use `splitindex` using the `PrintIndexCmd` and `HTMLIndexCmd` options. The file `lwarf.ist` is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

If the `latexmk` option is selected for `lwarf`, `latexmk` will compile the document but will *not* compile the indexes. `lwarpmk printindex` and `lwarpmk htmlindex` will still be required.

 **\thepage** When using `\AtWriteToIndex` or `\AtNextWriteToIndex`, the user must not refer to `\thepage` during HTML output, as the concept of a page number is meaningless. Instead, do

```
\addtocounter{LWR@autoindex}{1}
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}
```

where the \index-like action occurs, and then refer to \arabic{LWR@autoindex} instead of \thepage where the reference should occur.

See section 440.17 in the **l warp-patch-memoir** package for the \@@wrspindexhyp macro as an example.

For multiple indexes using makeindex and splitidx:

```
\usepackage[
    makeindex, latexmk,
    PrintIndexCmd={
        splitindex <projectname> -- -s l warp.ist
    },
    HTMLIndexCmd={
        splitindex <projectname>_html -- -s l warp.ist
    }
]{l warp}
\usepackage{splitidx}
...
\makeindex
\newindex[Second Index]{secondname}
```

When creating the HTML index, “_html” is automatically appended to each of the names.

Use

```
Enter ⇒ l warpmk printindex
Enter ⇒ l warpmk htmlindex
```

to compile the indexes.

For multiple indexes using **xindy** and **splitidx**:

```
\usepackage[
    xindy, latexmk,
    PrintIndexCmd={
        splitindex -m xindy <projectname> -- -M lwarf.xdy
        -L english -C utf8                                <optional>
    },
    HTMLIndexCmd={
        splitindex -m xindy <projectname>_html -- -M lwarf.xdy
        -L english -C utf8                                <optional>
    }
]{lwarf}
\usepackage{splitidx}
...
\makeindex
\newindex[Second Index]{secondname}
```

When creating the HTML index, “`_html`” is automatically appended to each of the names.

Use

```
Enter ⇒ lwarpmk printindex
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

9.5.15 Indexing with **imakeidx**

Due to the number of methods which may be used to process multiple indexes, the options for style file and **xindy** language and codepage must be specified in one of several different ways. These are described in detail later in this section, but are summarized here.

If shell escape is used, **imakeidx** will automatically compile the indexes by itself. Options specifying a custom style file and **xindy** language and codepage must be specified for each `\makeindex` command using its `options=` option, which must include **lwarf**'s special `lwarf.ist` or `lwarf.xdy` file, or a file based on them. If using a custom indexing style file, see sections 9.5.17 and 9.5.18. The `splitindex` option is also available if shell escape is used, in which case the **splitidx** package and **splitindex** program will also be used.

If shell escape is not possible, **latexmk** may be used to automatically compile the indexes. The style, language, and codepage options are specified with **lwarf**'s `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options. These are passed to **latexmk** by **lwarpmk**'s `lwarpmk printindex` and `lwarpmk htmlindex` commands.

Where shell escape and **latexmk** are not possible, **lwarpmk** may be used to manually compile the indexes. **lwarf**'s PrintIndexCmd and HTMLIndexCmd options are used.

For a single or multiple indexes using **makeindex** and **imakeidx**:

The index style **lwarf.ist** is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```
\usepackage[makeindex,latexmk]{lwarf}
\usepackage[makeindex]{imakeidx}
...
\makeindex[options={-s lwarf.ist}]
\makeindex[name=secondname,options={-s lwarf.ist}]
```

imakeidx will automatically compile the indexes. Shell escape is not required while using **makeindex**. **latexmk** may be specified, and if so it will be used for **lwarpmk print** and **lwarpmk html**, but **imakeidx** will actually create the indexes.

For a single or multiple indexes using **makeindex** and **splitindex** with **imakeidx**:

The index style **lwarf.ist** is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```
\usepackage[makeindex,latexmk]{lwarf}
\usepackage[makeindex,splitindex]{imakeidx}
...
\makeindex[options={-s lwarf.ist}]
\makeindex[name=secondname,options={-s lwarf.ist}]
```

enable shell escape

Shell escape is required while using **splitindex**. For the first compile, use

Enter ⇒ `pdflatex --shell-escape projectname.tex`

Enter ⇒ `pdflatex --enable-write18 projectname.tex` (MikTeX)

or similar with **xelatex** or **lualatex**. **lwarf** will remember that shell escape was used.

imakeidx will automatically execute **splitindex**, and will also use **makeindex** to compile the indexes.

latexmk may be specified, and if so it will be used for **lwarpmk print** and **lwarpmk html**, but **imakeidx** will actually create the indexes.

For multiple indexes using `xindy` and `imakeidx`, using shell escape:

Options may be given to `imakeidx`'s `\makeindex` command. The style file `lwarf.xdy` is automatically used for HTML output, and is not necessary for print output since the output will be similar. If language or codepage must be set, they should be specified as options for `\makeindex`, since `imakeidx` will process the indexes.

```
\usepackage[xindy,latexmk]{lwarf}
\usepackage[xindy,splitindex]{imakeidx}
...
\makeindex[
    options={ -M lwarf.xdy -L english -c utf8 }
]
\makeindex[
    name=secondname,
    options={ -M lwarf.xdy -L english -c utf8 }
]
```

⚠ enable shell escape

For the first compile, use

```
Enter ⇒ pdflatex --shell-escape projectname.tex
Enter ⇒ pdflatex --enable-write18 projectname.tex (MiKTeX)
```

or similar with `xelatex` or `lualatex`. `lwarf` will remember that shell escape was used.

`imakeidx` will automatically execute `splitindex` if selected, and will also use `xindy` to compile the indexes.

If selected, `latexmk` will automatically recompile the entire document as necessary.

For indexes using `xindy` and `imakeidx`, without shell escape, but with `latexmk`:

`lwarf`'s options are used, and are passed to `latexmk`.

```
\usepackage[
    xindy,
    xindyLanguage=english,                                     <optional>
    xindyCodepage=utf8,                                      <optional>
    latexmk,
]{lwarf}
\usepackage[xindy]{imakeidx}
...
\makeindex
\makeindex[name=secondname]
```

`latexmk` will create the indexes automatically when `lwarfmk print` and `lwarfmk html` are executed.

For indexes using xindy and imakeidx, without shell escape, and *without* latexmk:

lwarfmk must be told how to create the indexes:

```
\usepackage[
    xindy,
    PrintIndexCmd={
        xindy -M lwarf.xdy -L english -C utf8
            <projectname>.idx ;
        xindy -M lwarf.xdy -L english -C utf8
            secondname.idx
    },
    HTMLIndexCmd={
        xindy -M lwarf.xdy -L english -C utf8
            <projectname>.html.idx ;
        xindy -M lwarf.xdy -L english -C utf8
            secondname.html.idx
    }
]{lwarf}
\usepackage[xindy]{imakeidx}
...
\makeindex
\makeindex[name=secondname]
```

⚠ WINDOWS

For WINDOWS, replace the two “;” characters with “&”.

<projectname> is the \jobname: if compiling “name.tex”, use the filenames name.idx and name_html.idx.

Use

```
Enter ⇒ lwarfmk printindex
Enter ⇒ lwarfmk htmlindex
```

to compile the indexes.

9.5.16 Indexes with memoir

For a single index with memoir and makeindex:

```
\documentclass{memoir}
\usepackage[makeindex,latexmk]{lwarf}
...
\makeindex
```

The usual .idx and .ind files will be used, along with the lwarf.ist style file.

lwarfmk will use **latexmk** if specified, in which case **latexmk** will create the index automatically. Otherwise, use

```
Enter ⇒ lwarfmk printindex
```

Enter ⇒ `lwarpmk htmlindex`
 to compile the indexes.

For multiple indexes with memoir and makeindex, using latexmk:

`lwarf`'s options are used, and are passed to `latexmk`.

```
\documentclass{memoir}
\usepackage[makeindex, latexmk]{lwarf}
...
\makeindex
\makeindex[secondname]
```

`lwarpmk` will use `latexmk` to create the indexes automatically when the user executes `lwarpmk print` and `lwarpmk html`.

For multiple indexes with memoir and makeindex, without latexmk:

`lwarpmk` must be told how to create the indexes:

```
\documentclass{memoir}
\usepackage[
  makeindex,
  PrintIndexCmd={
    makeindex -s lwarf.ist <projectname>.idx ;
    makeindex -s lwarf.ist secondname.idx
  },
  HTMLIndexCmd={
    makeindex -s lwarf.ist <projectname>_html.idx ;
    makeindex -s lwarf.ist secondname_html.idx
  }
]{lwarf}
...
\makeindex
\makeindex[secondname]
```

 **WINDOWS**

For WINDOWS, replace the two “;” characters with “&”.

`<projectname>` is the `\jobname`: if compiling “`name.tex`”, use the filenames `name.idx` and `name_html.idx`.

Use

```
Enter ⇒ lwarpmk printindex
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

For a single index with memoir and xindy:

```
\documentclass{memoir}
\usepackage[
    xindy,
    xindyLanguage=english,                                <optional>
    xindyCodepage=utf8,                                 <optional>
    latexmk
]{lwarf}
...
\xindyindex
\makeindex
```

The usual .idx and .ind files will be used, along with the lwarf.xdy style file.

lwarfmk will use **latexmk** if specified, in which case **latexmk** will create the index automatically. Otherwise, use

```
Enter ⇒ lwarfmk printindex
Enter ⇒ lwarfmk htmlindex
```

to compile the indexes.

For multiple indexes with memoir and xindy, using latexmk:

lwarf's options are used, and are passed to **latexmk**.

```
\documentclass{memoir}
\usepackage[
    xindy,
    xindyLanguage=english,                                <optional>
    xindyCodepage=utf8,                                 <optional>
    latexmk
]{lwarf}
...
\xindyindex
\makeindex
\makeindex[secondname]
```

lwarfmk will use **latexmk** to create the indexes automatically.

For multiple indexes with memoir and xindy, without latexmk:

lwarpmk must be told how to create the indexes:

```
\documentclass{memoir}
\usepackage[
    xindy,
    PrintIndexCmd={
        xindy -M lwarf.xdy -L english -C utf8
        <projectname>.idx ;
        xindy -M lwarf.xdy -L english -C utf8
        secondname.idx
    },
    HTMLIndexCmd={
        xindy -M lwarf.xdy -L english -C utf8
        <projectname>.html.idx ;
        xindy -M lwarf.xdy -L english -C utf8
        secondname.html.idx
    }
]{lwarf}
...
\xindyindex
\makeindex
\makeindex[secondname]
```

⚠ WINDOWS

For WINDOWS, replace the four “;” characters with “&”.

<projectname> is the \jobname: if compiling “name.tex”, use the filenames name.idx and name.html.idx.

Use

```
Enter ⇒ lwarpmk printindex
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

9.5.17 Using a custom makeindex style file

Prog makeindex File lwarf.ist When using **makeindex**, **lwarpmk** uses the file lwarf.ist to process the index. This file is over-written by **lwarf** whenever a print version of the document is processed.

To use a custom **makeindex** style file:

1. Copy lwarf.ist to a new filename such as projectname.ist
2. Make changes to projectname.ist. Keep the lines which refer to \hyperindexref. These lines creates the hyperlinks for the HTML index. During print output \hyperindexref becomes a null function.

Opt `makeindexStyle` 3. In the document source use the `makeindexStyle` option for **lwarp**:

```
\usepackage[
    ... other options ...
    \textred{makeindexStyle=projectname.ist},
]{lwarp}
```

Likewise, refer to the custom style file if using `\PrintIndexCmd`, `\HTMLIndexCmd`, or `\LatexmkIndexCmd`.

4. Recompile the print version, which causes **lwarp** to rewrite the `lwarpmk.conf` configuration file. This tells **lwarpmk** to use the custom `projectname.ist` file instead of `lwarp.ist`.

9.5.18 Using a custom `xindy` style file

Prog `xindy` When using `xindy`, **lwarpmk** uses the file `lwarp.xdy` to process the index. This file is over-written by **lwarp** whenever a print version of the document is processed.
File `lwarp.xdy`

To use a custom `xindy` style file:

1. Copy `lwarp.xdy` to a new filename such as `projectname.xdy`
2. Make changes to `projectname.xdy`.

Keep the lines which refer to `\hyperindexref`:

```
(define-attributes ((\"hyperindexref\")))
(markup-locref :open "\hyperindexref{" :close "}")
...
(markup-locref :open "\textit{\hyperindexref{" :close "}}" :attr "textit")
```

These lines create the hyperlinks for the HTML index. During print output `\hyperindexref` becomes a null function.

To create custom styles, refer to the lines for `\textbf` and `\textit`.

Opt `xindyStyle` 3. In the document source use the `xindyStyle` option for **lwarp**:

```
\usepackage[
    ... other options ...
    \textred{xindyStyle=projectname.xdy},
]{lwarp}
```

Likewise, refer to the custom style file if using `\PrintIndexCmd`, `\HTMLIndexCmd`, or `\LatexmkIndexCmd`.

4. Recompile the print version, which causes **lwarp** to rewrite the `lwarpmk.conf` configuration file. This tells **lwarpmk** to use the custom `projectname.xdy` file instead of `lwarp.xdy`.

9.5.19 Additional indexing limitations

⚠ xindy with hyperref `xindy` and `hyperref` may not work well together for print output with “see”, “see also”, reference ranges, or stylized index references. It may be necessary to turn off hyper-referencing for indexes:

```
\usepackage[hyperindex=false]{hyperref}
```

⚠ empty index If an HTML index is empty, it may be necessary to add the following before `l warp` is loaded:

```
\usepackage{morewrites}
\morewritessetup{allocate=10}
...
\usepackage{l warp}
```

makeindex custom display styles When using `makeindex`, custom display styles are possible:

```
\begin{warpprint}
\newcommand{\notesstyle}[1]{#1nn}
\end{warpprint}

\begin{warpHTML}
\makeatletter
\newcommand{\notesstyle}[1]{\LWR@doindexentry{#1} notes }
\makeatother
\end{warpHTML}
...
A sentence.\index[key|notesstyle]
```

xindy custom display styles For custom styles with `xindy`, see `l warp.xdy` for `\textbf` and `\textit` as examples.

9.5.20 Index positions, toc, tocbibind

placement and toc options An index may be placed inline with other HTML text, or on its own HTML page:

Pkg `makeidx` **Inline, with a manual TOC entry:**

A commonly-used method to introduce an index in a L^AT_EX document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname} or chapter
\printindex
```

Pkg `makeidx` **On its own HTML page, with a manual TOC entry:**

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}%
or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex
```

Pkg `tocbibind` **Inline, with an automatic TOC entry:**

The **tocbibind** package may be used to automatically place an entry in the TOC.

```
\usepackage[nottoc]{tocbibind}
...
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex
```

Pkg `tocbibind` **On its own HTML page, with an automatic TOC entry:**

```
\usepackage[nottoc]{tocbibind}
...
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex
```

Opt `tocbibind numindex` Use the **tocbibind numindex** option to generate a numbered index. Without this option, the index heading has no number.

Other packages, such as **imakeidx**, may also have options for including the index in the Table of Contents.

Pkg `tocloft` If using **tocloft** with **tocbibind**, **anonchap**, **fncychap**, or other packages which change chapter title formatting, load **tocloft** with its **titles** option, which tells **tocloft** to use standard L^AT_EX commands to create the titles, allowing other packages to work with it.

9.6 Math

9.6.1 Rendering tradeoffs

Math rendering Math may be rendered as SVG graphics or using the MATHJAX JavaScript display engine.

SVG files	Rendering math as images creates a new SVG file for each expression, except that an MD5 hash is used to combine identical duplicates of the same inline math expression into a single file, which must be converted to SVG only once. Display math is still handled as individual files, since it may contain labels or references which are likely to change.
SVG inline	The SVG images are currently stored separately, but they could be encoded in-line directly into the HTML document. This may reduce the number of files and potentially speed loading the images, but slows the display of the rest of the document before the images are loaded.
PNG files	Others L ^A T _E X-to-HTML converters have used PNG files, sometimes pre-scaled for print resolution but displayed on-screen at a scaled down size. This allows high-quality print output at the expense of larger files, but SVG files are the preferred approach for scalable graphics.
MathML	Conversion to MathML might be a better approach, among other things allowing a more compact representation of math than SVG drawings. Problems with MathML include limited browser support and some issues with the fine control of the appearance of the result. Also see section 11 regarding EPUB output with MATHJAX.

9.6.2 SVG option

SVG math option For SVG math, math is rendered as usual by L^AT_EX into the initial PDF file using the current font¹⁴, then is captured from the PDF and converted to SVG graphics via a number of utility programs. The SVG format is a scalable-vector web format, so math may be typeset by L^AT_EX with its fine control and precision, then displayed or printed at any size, depending on (sometimes broken) browser support. An HTML alt attribute carries the L^AT_EX code which generated the math, allowing copy/paste of the L^AT_EX math expression into other documents.

SVG image font size For the `lateximage` environment, the size of the math and text used in the SVG image may be adjusted by setting `\LateximageFontSizeName` to a font size name—*without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{\normalsize}
```

For inline SVG math, font size is instead controlled by `\LateximageFontSizeScale`, which defaults to:

```
\newcommand*{\LateximageFontSizeScale}{.75}
```

SVG math copy/paste For SVG math, text copy/paste from the HTML `<alt>` tags lists the equation number or tag for single equations, along with the L^AT_EX code for the math expression. For *AMS* environments with multiple numbers in the same environment, only the first and

¹⁴See section 429 regarding fonts and fractions.

last is copy/pasted, as a range. No tags are listed inside a starred \mathcal{AMS} environment, although the `\tag` macro will still appear inside the \TeX math expression.

-  **SVG math in \TeX boxes** SVG math does not work inside \TeX boxes, since a `\newpage` is required before and after each image.

9.6.3 MATHJAX option

MATHJAX math option The popular MATHJAX alternative (mathjax.org) may be used to display math.

Prog MathJax

When MATHJAX is enabled, math is rendered twice:

1. As regular \TeX PDF output placed inside an HTML comment, allowing equation numbering and cross referencing to be almost entirely under the control of \TeX , and
2. As detokenized printed \TeX commands placed directly into the HTML output for interpretation by the MATHJAX display scripts. An additional script is used to pre-set the equation number format and value according to the current \TeX values, and the MATHJAX cross-referencing system is ignored in favor of the \TeX internal system, seamlessly integrating with the rest of the \TeX code.

9.6.4 Customizing MATHJAX

MATHJAX does not have preexisting support every possible math function. Additional MATHJAX function definitions may be defined. These will be declared at the start of each HTML page, and thus will have a global effect.

Examples:

```
\CustomizeMathJax{
    \newcommand{\expval}[1]{\langle #1 \rangle}
    \newcommand{\abs}[1]{| #1 |}
}

\CustomizeMathJax{\newcommand{\arsinh}{\text{arsinh}}}
\CustomizeMathJax{\newcommand{\arcosh}{\text{arcosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
```

9.6.5 MATHJAX limitations

MATHJAX limitations Limitations when using MATHJAX include:

Prog MathJax

subequations

- MATHJAX itself does not support subequations. This may be improved by pars-

ing the \TeX math expression to manually insert tags, but this has not yet been done.

[footnotes in math](#)

[lateximage](#)

- Footnotes inside equations are not yet supported while using MATHJAX.

- Math appearing inside a `lateximage`, and therefore also inside a `Tikz` or `picture` environment, is rendered as SVG math even if MATHJAX is used in the rest of the document.

[siunitx](#)

 [siunitx inside an equation](#)

- Usage of `siunitx` inside a math equation is supported via a third-party MATHJAX extension. While inside a math expression, do not use `\SI` or `\si` inside `\text`, where it will be rendered as normal text.

<https://github.com/burnpanck/MathJax-siunitx>

Also see section [9.6.12](#).

[tabbing](#)

- A tabbing environment is emulated using an HTML `<pre>`. While MATHJAX is enabled inside `tabbing`, the browser may not correctly render the horizontal alignment of the math and text following after on the same line.

 [other macros and packages](#)

- Other math-related macros and packages are not supported by MATHJAX, including `\ensuremath` and `bigdelim`, along with occasionally-used macros such as `\relax`. `lwarf` emulates footnotes, `units`, and `nicefrac` for MathJax.

9.6.6 Catcode changes

[preamble macros with math](#)

The math shift character `$` is not set for HTML output until after the preamble. Macros defined in the preamble which contain `$` must be enclosed between `\StartDefiningMath` and `\StopDefiningMath` to temporarily change to the HTML meaning of `$`:

```
\StartDefiningMath
\newcommand{...}
\StopDefiningMath
```

As an alternative, use `\(` and `\)` instead of `$`, in which case `\StartDefiningMath` and `\StopDefiningMath` are not necessary.

If a package defines macros using `$`, it may be necessary to use `\StartDefiningMath` and `\StopDefiningMath` before and after loading the package.

9.6.7 Complicated inline math objects

`\inlinemathnormal`
`\inlinemathother`

An inline math expression is usually converted to a reusable hashed SVG math image, or a MathJax expression. The hash or expression depends on the contents of the math expression. In most cases this math expression is static, such as `$x+1$`, so the

**changing contents
complicated alt tag**

image can be reused for multiples instances of the same expression. In some cases, the math expression includes a counter or other object which may change between uses. Another problem is complicated contents which do not expand well in an alt tag. The macro `\inlinemathother` may be used before a dynamic math expression, and `\inlinemathnormal` after. Doing so tells `l warp` to use an unhashed SVG math image, even if MathJax is in use. See section 42.

9.6.8 Complicated display math objects

`\displaymathnormal` By default, or when selecting `\displaymathnormal`, MATHJAX math display environments print their contents as text into HTML, and SVG display math environments render their contents as SVG images and use their contents as the alt tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Tikz pictures, compilation will fail.

`\displaymathother`
**MathJax unsupported
complicated alt tag** When selecting `\displaymathother`, it is assumed that the contents are more complicated than “pure” math. An example is an elaborate Tikz picture, which will not render in MATHJAX and will not make sense as an HTML alt tag. In this mode, MATHJAX is turned off, math display environments become SVG images, even if MATHJAX is selected, and the HTML alt tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Tikz pictures are more likely to compile successfully.

9.6.9 chemformula package

**⚠ chemformula with
MATHJAX**

`chemformula` works best without MATHJAX. If MATHJAX is used, `\displaymathother` must be used before array, and then `\displaymathnormal` may be used after. (The `chemformula` package adapts to array, but does not know about MATHJAX, and MATHJAX does not know about `chemformula`.)

While using MATHJAX, `\displaymathother` may also be used for other forms of display and inline math which contain `chemformula` expressions.

9.6.10 mhchem package

See section 283.

9.6.11 ntheorem package

Pkg ntheorem This conversion is not total. Font control is via css, and the custom L^AT_EX font settings are ignored.

⚠ Font control

⚠ **Equation numbering**

ntheorem has a bug with equation numbering in *AMS* environments when the option `thref` is used. **l warp** does not share this bug, so equations with `\split`, etc, are numbered correctly with **l warp**'s HTML output, but not with the print output. It is recommended to use `cleveref` instead of **ntheorem**'s `thref` option.

9.6.12 siunitx package

Pkg **siunitx** Due to **pdftotext** limitations, fraction output is replaced by symbol output for `per-mode` and `quotient-mode`.

⚠ **math mode required**

Some units will require that the expression be placed inside math mode.

NOTE: As of this writing, the **siunitx** extension for MATHJAX is not currently hosted at any public CDN, thus **siunitx** is not usable with MATHJAX unless a local copy of this extension is created first.

⚠ **tabular**

Tabular `S` columns are rendered as simple `c` columns, and tabular `s` columns are not supported. These may be replaced by `c` columns with each cell contained in `\num` or `\si`.

9.6.13 units and nicefrac packages

Pkg **units** **units** and **nicefrac** work with **l warp**, but MATHJAX does not have an extension for **units** or **nicefrac**. These packages do work with **l warp**'s option `svgmath`.

9.6.14 newtxmath package

Pkg **newtxmath** The proper load order is:

⚠ **loading sequence**

```
...
\usepackage{l warp}
...
\usepackage{amsthm}
\usepackage{newtxmath}
...
```

9.7 Graphics

Pkg **graphics** For `\includegraphics` with `.pdf` or `.eps` files, the user must provide a `.pdf` or

Pkg **graphicx** `.eps` image file for use in print mode, and also a `.svg`, `.png`, or `.jpg` version of the same image for use in HTML.

\includegraphics file formats

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, **l warp** will automatically choose the .pdf or .eps format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a .pdf or .eps image is referred to with its file extension, the extension will be changed to .svg for HTML:

```
\includegraphics{filename.pdf} % uses .svg in HTML  
\includegraphics{filename.eps} % uses .svg in HTML
```

Prog pdftocairo To convert a PDF image to SVG, use the utility **pdftocairo**:

[PDF to SVG](#)

Enter ⇒ pdftocairo -svg filename.pdf

Prog l warpmk pdftosvg For a large number of images, use **l warpmk**:

Enter ⇒ l warpmk pdftosvg *.pdf (or a list of filenames)

Prog l warpmk epstopdf For EPS images converted to PDF using the package **epstopdf**, use

[epstopdf package](#)

Enter ⇒ l warpmk pdftosvg *.PDF

to convert to SVG images.

[DVI latex](#) When using DVI **latex**, it is necessary to convert EPS to PDF and then to SVG:

Enter ⇒ l warpmk epstopdf *.eps (or a list of filenames)

Enter ⇒ l warpmk pdftosvg *.pdf (or a list of filenames)

[PNG and JPG](#) For PNG or JPG while using **pdflatex**, **lualatex**, or **xelatex**, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

[GIF](#) GIF files may be used for HTML, but another format must also be provided for print output.

[file extension priorities](#) If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

⚠ [graphics vs. graphicx](#)

If using the older **graphics** syntax, use both optional arguments for `\includegraphics`. A single optional parameter is interpreted as the newer **graphicx** syntax. Note that viewports are not supported by **l warp** — the entire image will be shown.

⚠ [viewport](#)

⚠ [viewport units](#)

For `\includegraphics`, avoid px and % units for width and height, or enclose them inside `warpHTML` environments. For font-proportional image sizes, use ex or em. For fixed-sized images, use cm, mm, in, pt, or pc. Use the keys `width=.5\linewidth`, or similar for `\textwidth` or `\textheight` to give fixed-sized images proportional to a

6 by 9 inch text area. Do not use the `scale` option, since it is not well supported by HTML browsers.

options `\includegraphics` accepts `width` and `height`, `origin`, `rotate` and `scale`, plus a new `class` key.

HTML class With HTML output, `\includegraphics` accepts an optional `class=xyz` keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

\rotatebox `\rotatebox` accepts the optional `origin` key.

⚠ browser support `\rotatebox`, `\scalebox`, and `\reflectbox` depend on modern browser support. The css3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike L^AT_EX, so expect some ugly results for scaling and rotating.

9.7.1 tikz package

Pkg `tikz` If using display math with `tikzpicture` or `\tikz`, along with matrices with the `&` character, the document must be modified as follows:

⚠ displaymath and matrices

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of `&` in the `tikz` expression must be replaced with `\&`.

9.7.2 grffile package

Pkg `grffile` `grffile` is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

9.7.3 color package

Pkg `color` `color` is superceded by `xcolor`, and `l warp` requires several of the features of `xcolor`. When `color` is requested, `xcolor` is loaded as well.

9.7.4 xcolor package

Pkg `xcolor` `\colorboxBlock` and `\fcolorboxBlock` are provided for increased HTML compatibility.
\colorboxBlock and \fcolorboxBlock

bility, and they are identical to `\colorbox` and `\fcolorbox` in print mode. In HTML mode they place their contents into a `<div>` instead of a ``. These `<div>`s are set to `display: inline-block` so adjacent `\colorboxBlocks` appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for `\colorboxBlock` and `\fcolorboxBlock` are created by `l warp`'s core if `xcolor` is loaded.

`background: none` `\fcolorbox` and `\fcolorboxBlock` allow a background color of `none`, in which case only the frame is drawn, which can be useful for HTML.

`color support` Color definitions, models, and mixing are fully supported without any changes required.

`colored tables` `\rowcolors` is supported, except that the optional argument is ignored so far.

`colored text and boxes` `\textcolor`, `\colorbox`, and `\fcolorbox` are supported.

`\color` and `\pagecolor` `\color` and `\pagecolor` are ignored. Use `css` or `\textcolor` where possible.

9.7.5 epstopdf package

Pkg `epstopdf` Images with an `.eps` extension will be converted to `.pdf`. The HTML output uses the `.svg` version, so use

Enter ⇒ `l warpmk pdftosvg <listofPDFfiles>`

to generate `.svg` versions.

9.7.6 pstricks package

Pkg `pstricks` All `pstricks` content should be contained inside a `pspicture` environment.

⚠ use `pspicture`

9.7.7 pdftricks package

Pkg `pdftricks` The `pdftricks` image files `<jobname>-fig*.pdf` must be converted to `.svg`, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

Enter ⇒ `l warpmk pdftosvg <jobname>-fig*.pdf`

9.7.8 psfrag package

Pkg **psfrag** The `psfrags` environment is modified to use `lateximage` to encapsulate the image. Always use a `psfrags` environment to contain any local `\psfrag` macros and the associated `\includegraphics` or `\epsfig` calls. Outside of a `psfrags` environment, `psfrags` adjustments will not be seen by `lwarf`.

⚠️ use psfrags Tip: Use a mono-spaced font for the tags in the EPS file.

9.7.9 pstool package

Pkg **pstool** `\graphicspath` is ignored, and the file directory must be stated.

⚠️ path and filename The filename must not have a file extension.

Use

Enter ⇒ `lwarfmk html`

followed by

Enter ⇒ `lwarfmk limages`

9.7.10 overpic package

Pkg **overpic** The macros `\overpicfontsize` and `\overpicfontskip` are used during HTML generation. These are sent to `\fontsize` to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the `overpic` and `Overpic` environments.

⚠️ scaling

9.8 Tabbing

The `tabbing` environment works, except that `svg` math and `lateximages` do not yet work inside the environment.

⚠️ math in tabbing If math is used inside `tabbing`, place `tabbing` inside a `lateximage` environment, which will render the entire environment as a single `SVG` image.

9.9 Tabular

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, * column specifiers, **siunitx** S columns, or the packages **multirow**, **longtable**, **supertabular**, or **xtab**.

Defining environments:

 Misplaced alignment
tab character &

- When defining environments or macros which include tabular and instances of the & character, it may be necessary to make & active before the environment or macro is defined, then restore & to its default catcode after, using the following commands. These are ignored in print mode.

```
\StartDefiningTabulars
```

```
<define macros or environments using tabular and &  
here>
```

```
\StopDefiningTabulars
```

This includes before and after defining any macro which used \ttabbox from **floatrow**.

- When creating a new environment which contains a tabular environment, lwarf's emulation of the tabular does not automatically resume when the containing environment ends, resulting in corrupted HTML rows. To fix this, use \ResumeTabular as follows. This is ignored in print mode.

```
\StartDefiningTabulars % because & is used in a
```

```
definition
```

```
\newenvironment{outerenvironment}
```

```
{
```

```
\tabular{cc}
```

```
left & right \\
```

```
}
```

```
{
```

```
\TabularMacro\ResumeTabular
```

```
left & right \\
```

```
\endtabular
```

```
}
```

```
\StopDefiningTabulars
```

Cell contents:

 \multirow

- For **multirow**, insert \mrowcell into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output.

```
... & \multirow{2}{.5in}{text} & ...
```

```
... & \mrowcell & ...
```

vposn

Note that recent versions of **multirow** include a new optional vposn argument.

- The **multirow** documentation regarding colored cells recommends using a negative number of rows. This will not work with **l warp**, so \warpprintonly and \warpHTMLonly must be used to make versions for print and HTML.
- See section 292.2 for \multicolumnrow.

 \multicolumn & \multirow

l warp does not support directly combining \multicolumn and \multirow. Use \multicolumnrow instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}{c}{3}{0}{1in}{Opt}{Text}
```

The two arguments for \multicolumn come first, followed by the five arguments for \multirow, many of which are optional, followed by the contents.

As per \multirow, skipped cells to the right of the \multicolumnrow statement are not included in the source code on the same line. On the following lines, \mcolrowcell must be used for each cell of each column and each row to be skipped:

```
... & \multicolumnrow{2}{c}{c}{3}{0}{1in}{Opt}{Text} & ...
... & \mcolrowcell & \mcolrowcell & ...
... & \mcolrowcell & \mcolrowcell & ...
```

vposn

Note that recent versions of **multirow** include a new optional vposn argument.

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use \TabularMacro just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \\
```

Column specifiers:

 * column specification

- * in a column specification is not used (so far). Repeat the column type the correct number of times.

@ and !

- Only one each of @ and ! is used at each column, and they are used in that order.

\multirow

- In \multirow cells, the print version may have extra instances of <, >, @, and ! cells on the second and later rows in the \multirow which do not appear in the HTML version.

- \newcolumntype is ignored; unknown column types are set to l.

Rules:

vertical rules

- Doubled \hlines, \midrules, and vertical rules are supported.
- Vertical rules next to either side of an @ or ! column are displayed on both sides of the column.

width and trim

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with @ or ! columns, and full-width rules ignore trim.

full-width rules

- \toprule, \midrule, \bottomrule, and \hline ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

combined rules

- If you wish to use \cmidrule followed by \bottomrule, it may be necessary to use:

```
\cmidrule{2-3} \\[-2ex]
\bottomrule
```

The optional -2ex is ignored in HTML, but improves the visual formatting in the print output.

- For \toprule and \bottomrule, when combined with a warpprint or warpHTML environment, if a “Misplaced \noalign” error occurs, change

This & That \endhead

to

\warpprintonly{This & That \endhead}

and likewise with the other \end headings. Keep the \endfirsthead row unchanged, as it is still relevant to HTML output.

colortbl:**⚠ row/cell color**

Only use \rowcolor and \cellcolor at the start of a row, in that order.

colortbl ignores the overhang arguments.

Other:

- \tabularx ignores the width, but X columns do produce paragraph columns or multicolumns.

longtable headings

- For **longtable**, place headings and footings which do not apply to HTML inside \warpprintonly{}.

⚠ S columns

- For S columns (from the **siunitx** package), while producing print output, anything non-numeric must be placed inside {} braces, including commands such as \multirow. While producing HTML output, though, anything placed inside braces is not seen by l warp’s tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

```
\warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
\warpHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
```

9.9.1 longtable package

Pkg **longtable** Longtable \endhead, \endfoot, and \endlastfoot rows are not used for HTML, and

⚠ Misplaced `\noalign` these rows should be disabled. Use

```
\warpprintonly{row contents}
```

instead of

```
\begin{warpprint} ... \end{warpprint}
```

Doing so helps avoid “Misplaced `\noalign`.” when using `\begin{warpprint}`.

Keep the `\endfirsthead` row, which is still relevant to HTML output.

⚠ `\kill` `\kill` is ignored, place a `\kill` line inside

```
\begin{warpprint} ... \end{warpprint}
```

or place it inside `\warpingprintonly`.

⚠ `lateximage` `longtable` is not supported inside a `lateximage`.

9.9.2 supertabular and xtab packages

Pkg `supertabular` For `\tablefirsthead`, etc., enclose them as follows:

Pkg <code>xtab</code>	<code>\StartDefiningTabulars</code>
	<code>\tablefirsthead</code>
	<code>...</code>
	<code>\StopDefiningTabulars</code>

See section 9.9.

⚠ `lateximage` `supertabular` and `xtab` are not supported inside a `lateximage`.

9.9.3 bigdelim package

Pkg `bigdelim` `\ldelim` and `\rdelim` use `\multirow`, so `\mrowcell` must be used in the proper number of empty cells in the same column below `\ldelim` or `\rdelim`, but not in cells which are above or below the delimiter:



```
\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\{}{2}{.25in}[left ] & c & d \\
\mrowcell{e & f} \\
<empty> & g & h \\
\end{tabular}
```

<>	a	b
left {	c	d
	e	f
<>	g	h

9.10 Floats

9.10.1 Float contents alignment

⚠ figure & table alignment \centering, etc. are honored in a figure or table if they are the first command inside the float:

```
\begin{table*}
\centering
\caption{A Table}
...
```

9.10.2 float, trivfloat, and/or algorithmicx together

Pkg float If using \newfloat, **trivfloat**, and/or **algorithmicx** together, see section 406.1.

Pkg trivfloat

Pkg algorithmicx

⚠ package conflicts

Pkg caption To pass options to caption, select the options before loading **lwrap**:

Pkg subcaption

⚠ options

```
\documentclass{article}
...
\PassOptionsToPackage{options_list}{caption}
...
\usepackage{lwrap}
...
\usepackage{caption}
```

⚠ numbering To ensure proper float numbering, set caption positions such as:

```
\captionsetup[table]{position=top}
\captionsetup[figure]{position=bottom}
```

Similarly for **subtable**, **subfigure**, and **longtable**.

9.10.4 subfig package

Pkg subfig

-  **lof/lotdepth** At present, the package options for `lofdepth` and `lotdepth` are not working. These counters must be set separately after the package has been loaded.

In the document source, use `\hfill` and `\hspace*` subfig>inline between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

9.10.5 floatrow package

Pkg floatrow

 **Misplaced alignment tab character &** Use `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros using `\ttabbox` with a tabular inside. See section 9.9.

 **subfig package** When combined with the **subfig** package, while inside a `subfloatrow` `\ffigbox` and `\ttabbox` must have the caption in the first of the two of the mandatory arguments.

-  **\FBwidth, \FBheight** The emulation of **floatrow** does not support `\FBwidth` or `\FBheight`. These values are pre-set to `.3\linewidth` and `2in`. Possible solutions include:

- Use fixed lengths. **l warp** will scale the `HTML` lengths appropriately.
- Use `warpprint` and `warpHTML` environments to select appropriate values for each case.
- Inside a `warpHTML` environment, manually change `\FBwidth` or `\FBheight` before the `\ffigbox` or `\ttabbox`. Use `\FBwidth` or `\FBheight` normally afterwards; it will be used as expected in print output, and will use your custom-selected value in `HTML` output. This custom value will be used repeatedly, until it is manually changed to a new value.

9.10.6 keyfloat package

Pkg keyfloat

If placing a `\keyfig[H]` inside a `keywrap`, use an absolute width for `\keyfig`, instead of `lw`-proportional widths. (The `[H]` option forces the use of a `minipage`, which

internally adjusts for a virtual 6-inch wide minipage, which then corrupts the `lw` option.)

9.11 Koma-Script

`Cls komascript` Many features are ignored during the HTML conversion. The goal is source-level compatibility.

`\titlehead`, `\subject`, `\captionformat`, `\figureformat`, and `\tableformat` are not yet emulated.

 **Not fully tested!** [Please send bug reports!](#)

Some features have not yet been tested. Please contact the author with any bug reports.

9.12 Memoir

`Cls memoir` While emulating `memoir`, `l warp` pre-loads a number of packages (section 440.1). This

 **options clash** can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading `l warp`:

```
\documentclass{memoir}
...
\PassOptionsToPackage{options_list}{package_name}
...
\usepackage{l warp}
...
\usepackage{package_name}
```

`\verbfootnote` is not supported.

`\newfootnoteseries`, etc. are not supported.

`l warp` loads `pagenote` to perform `memoir`'s pagenote functions, but there are minor differences in `\pagenotesubhead` and related macros.

Poem numbering is not supported.

The `verbatim` environment does not yet support the `memoir` enhancements. It is currently recommended to load and use `fancyvrb` instead.

The `memoir` glossary system is not yet supported by `l warpmk`. The `glossaries` package may be used instead, but does require the glossary entries be changed from the `memoir` syntax to the `glossaries` syntax.

9.13 Miscellaneous packages

9.13.1 verse and memoir

- Pkg **verse** When using **verse** or **memoir**, always place a \\ after each line.
- Cls **memoir**
\attrib The documentation for the **verse** and **memoir** packages suggest defining an \attrib command, which may already exist in current documents, but it will only work for print output. **lwarf** provides \attribution, which works for both print and HTML output. To combine the two so that \attrib is used for print and \attribution is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

- Len **\vleftskip** These lengths are used by **verse** and **memoir** to control the left margin, and they may already be set by the user for print output. New lengths **\HTMLvleftskip** and **\HTMLleftmargini** are provided to control the margins in HTML output. These new lengths may be set by the user before any **verse** environment, and persist until they are manually changed again. One reason to change **\HTMLleftmargini** is if there is a wide **\flagverse** in use, such as the word “Chorus”, in which case the value of **\HTMLleftmargini** should be set to a wide enough length to contain “Chorus”. The default is wide enough for a stanza number.

-  **spacing** Horizontal spacing relies on **pdftotext**’s ability to discern the layout (-layout option) of the text in the HTML-tagged PDF output. For some settings of **\HTMLleftmargini** or **\HTMLleftskip** the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

9.13.2 newclude package

- Pkg **newclude** **newclude** modifies **\label** in a non-adaptive way, so **newclude** must be loaded before **lwarf** is loaded:

```
\documentclass{article}
...<font setup>
\usepackage{newclude}
\usepackage[warpHTML]{lwarf}
...
```

9.13.3 babel package

Pkg babel

- ⚠ \CaptionSeparator When French is used, the caption separator is changed to a dash. The following may be used to restore it to a colon:

```
\renewcommand*\CaptionSeparator{:-}
```

- punctuation spaces Also when French is used, lwarf creates fixed-width space around punctuation by patching \FBcolonspace, \FBthinspace, \FBguillspace, \FBmedkern, \FBthickkern, \FBtextellipsis, and the tilde. If the user's document also changes these parameters, the user's changes should be placed inside a warpprint environment so that the user's changes do not affect the HTML output.

9.13.4 polyglossia package

Pkg polyglossia lwarf uses cleveref, which has some limitations when using polyglossia, possibly resulting in the error

```
! Undefined control sequence. ... \@begindocumenthook
```

To test compatibility, add

```
\usepackage{cleveref}
```

near the end of the preamble (as the last package to be loaded), and try to compile the print version. It may be necessary to set

```
\setdefaultlanguage{english}
```

or some other language supported by cleveref, then select other languages using \setotherlanguages.

Once the print version works with cleveref and polyglossia, the HTML version should work as well using lwarf.

9.13.5 todonotes and luatodonotes packages

- Pkg todonotes The documentation for todonotes and luatodonotes have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

9.13.6 **fixme**

Pkg **fixme** External layouts (\fxloadlayouts) are not supported.

⚠️ external layouts

User control is provided for setting the **HTML** styling of the “faces”. The defaults are as follows, and may be changed in the preamble after **fixme** is loaded:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}
```

9.13.7 **xparse**

Pkg **xparse** To remove from the log any warnings about redeclaring objects, place the following before **l warp** is loaded:

```
\usepackage[log-declarations=false]{xparse}
```

10 Compiling using custom shell commands

lwarf and **lwarpmk** try to make it easy to process print and HTML compilation tasks in most situations. Depending on the operating system, command-line options, TeX engine, and **lwarf** options, the commands **lwarpmk print** and **lwarpmk html** are automatically set up to correctly recompile the project. These actions may be overridden using **lwarf** options, thus allowing the use of packages such as **perltex** and **pythontex**.

10.1 Command options

Opt **PrintLatexCmd** The **lwarf** options **PrintLatexCmd** and **HTMLLatexCmd** are used to set customized commands to be executed by **lwarpmk print** and **lwarpmk html**.

PrintLatexCmd should be set to shell commands which take `project.tex` and generate `project.pdf`.

HTMLLatexCmd should be set to take `project_html.tex` and generate `project_html.pdf`.

lwarpmk will then take `project_html.pdf` and automatically convert it and generate `project.html`.

10.2 Literal character macros

The **lwarf** package options are parsed by TeX, and so some characters require the use of a special macro to represent them. See table 6. `\LWRopquote` and `\LWRopseq` may be used to increase operating-system portability. `\jobname` must have `_html` appended for processing HTML. `\space` may be necessary between other macros.

 **macro not found** To use these macros, either **kvoptions-patch** must be loaded before **lwarf**:

```
\usepackage{kvoptions-patch}
\usepackage[
    PrintLatexCmd={ ... } ,
    HTMLLatexCmd={ ... }
]{lwarf}
```

Table 6: Literal character macros

Character	Macro	Comment
%	\LWRpercent	
\$	\LWRdollar	
&	\LWRamp	
%	\LWRhash	
\	\LWRbackslash	
' or "	\LWRopquote	Depends on the operating system.
& or &&	\LWRopseq	Depends on the operating system.
(space)	\space	Forces an extra space.
(jobname)	\jobname	Without file extension.

or \lwarfsetup must be used to set PrintLatexCmd and HTMLLatexCmd:

```
\usepackage[...]{lwarf}
\lwarfsetup{
  PrintLatexCmd=
  {
    latex tm \LWRopseq
    dvips -o tm-pics.ps tm.dvi \LWRopseq
    ps2pdf tm-pics.ps \LWRopseq
    pdflatex tm.tex
  } ,
  HTMLLatexCmd=
  {
    latex tm_html \LWRopseq
    dvips -o tm_html-pics.ps tm_html.dvi \LWRopseq
    ps2pdf tm_html-pics.ps \LWRopseq
    pdflatex tm_html.tex
  }
}
```

10.3 latexmk

Prog **latexmk** If **latexmk** is used for a project, it may be easiest to continue using it.

latexmk *project.tex* would create *project.pdf* as normal.

latexmk *project_html.tex* would create *project_html.pdf*, then

l warp mk pdftohtml *project_html.pdf* would take *project_html.pdf* and convert it to *project.html*.

Pkg **sagetex** **latexmk** may simplify the use of packages such as **sagetex**.

10.4 perltex package

Pkg **perltx** The **l warp** package option settings to use **perltx** would be similar to:

```
\usepackage[
    ...
    PrintLatexCmd={perltx -latex=pdflatex project.tex} ,
    HTMLLatexCmd={perltx -latex=pdflatex project_html.tex} ,
    ...
]{l warp}
```

 “impure” math Place **perltx** math expressions between `\displaymathother` and `\displaymathnormal`, or `\inlinemathother` and `\inlinemathnormal`. See section 9.6.8.

10.5 pythontex package

Pkg **pythontex** An example using **pythontex**:

```
\usepackage[
    ...
    PrintLatexCmd={
        pdflatex project.tex \LWRopseq
        pythontex project \LWRopseq
        pdflatex project.tex
    } ,
    HTMLLatexCmd={
        pdflatex project_html.tex \LWRopseq
        pythontex project_html \LWRopseq
        pdflatex project_html.tex
    } ,
    ...
]{l warp}
```

Another possibility is to use **latexmk**, placing the **latexmk ...** commands in the PrintLatexCmd and HTMLLatexCmd options. While using these options, the **l warp** option **latexmk** would not be used.

- ⚠ “impure” math
 - ⚠ HTML look-alike
- No attempt has yet been made to make **pythontex** robust with HTML output. Some math objects must be surrounded by `\displaymathother ... \displaymathnormal`, or `\inlinemathother ... \inlinemathnormal`. Displays of code may have to be enclosed inside a `lateXimage` environment to prevent <, > and similar from being interpreted by the browser as HTML entities.

10.6 Other packages

- | | | |
|-----|-----------------|--|
| Pkg | sympytex | Other packages such as sympytex and rterface would be set up similar to pythontex , |
| Pkg | rterface | and the same warnings would apply. |

10.7 make program

- | | | |
|------|-------------|--|
| Prog | make | To use l warp with the make program, have the <code>makefile</code> take <code>project.tex</code> and generate the print version <code>project.pdf</code> , as normal. <code>\usepackage{l warp}</code> must be used, and it generates <code>l warpmk.conf</code> when the print version is created. |
|------|-------------|--|

To generate HTML, first have `project_html.tex` be compiled to generate `project_html.pdf`. This must be in PDF format. Finally, have `project_html.pdf` be converted to HTML using `l warpmk pdftohtml project_html.pdf`, and convert SVG math with `l warpmk l images`.

11 EPUB conversion

lwarf does not produce EPUB documents, but it may be told to modify its HTML output to greatly assist in the conversion. An external program may then be used to finish the conversion to EPUB.

<meta> author To assign the author's name for regular **lwarf** HTML files, and also for the EPUB, use `\HTMLAuthor {<name>}`. This assigns the name to the `<meta>` author element. It may be set empty, and it defaults to `\theauthor`.

A special boolean is provided to simplify the process of converting **lwarf** HTML output to EPUB:

FormatEPUB

Bool **FormatEPUB**
Default: **false**

`FormatEPUB` changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.

To help convert **lwarf** HTML output to EPUB, add

`\booltrue{FormatEPUB}`

to the project's source preamble after `\usepackage{lwarf}`. The EPUB version of the document cannot co-exist with the regular HTML version, so

Enter ⇒ `lwarfmk cleanall`

Enter ⇒ `lwarfmk html`

Enter ⇒ `lwarfmk limages`

to recompile with the `FormatEPUB` boolean turned on. Several changes are then made to the HTML output:

- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.

Calibre The resulting files will be ready to be loaded into an EPUB conversion program, such as the open-source program **Calibre** (<https://calibre-ebook.com/>).

 **search order** The EPUB conversion program must know what order the files are included. For **lwarf** projects, set the EPUB conversion software to do a breadth-first search of the files. For **Calibre**, this option is found in

Preferences → Plugins → File type plugins → HTML to Zip

 **encoding** Check the box Add linked files in breadth first order. Set the document encoding as utf-8, which is what **lwarf** generates for HTML, even if the original printed document uses some other encoding.

 **section breaks** The EPUB-conversion program must also know where the section breaks are located. For a list of **lwarf**'s section headings, see table 8. For example, an article class document would break at \section, which is mapped to HTML heading level <h4>, whereas a book class document would break at \chapter, which is HTML heading level <h3>. For **Calibre**, this option is found in

Preferences → Conversion (Common Options) → Structure Detection → Detect chapters at (XPath expression)

Select the “magic wand” to the right of this entry box, and set the first entry

Match HTML tags with tag name:

to “h4”. (Or “h3” for document classes with \chapters.) The Detect chapters at field should then show

//h:h4 — or — //h:h3

This option is also available on the main tool bar at the Convert books button.

Once these settings have been made, the **lwarf**-generated HTML files may be loaded by **Calibre**, and then converted to an EPUB.

MATHJAX support

MATHJAX may be used in EPUB documents. Some e-readers include MATHJAX, but any given reader may or may not have a recent version, and may or may not include extensions such as support for **siunitx**.

lwarf adds some modifications to MathML to support equations numbered by chapter. These modifications may not be compatible with the e-reader's version of MATHJAX, so **lwarf** requests that a known version be loaded instead. In some cases chapter numbering of equations still doesn't work.

Until math support in EPUB documents is improved, it is recommended to use SVG images instead of MATHJAX, especially for equations numbered by chapter, or where **siunitx** support is important.

12 Word-processor conversion

lwarf may be told to modify its HTML output to make it easier to import the HTML document into a word processor. At the time of this writing, it seems that LIBREOFFICE works best at preserving table layout, but it still has some limitations, such as an inability to automatically assign figure and table frames and captions according to user-selected HTML classes. **lwarf** provides some assistance in locating these frame boundaries, as shown below.

12.1 Activating word-processor conversion

A special boolean is provided to simplify the process of converting **lwarf** HTML output to EPUB:

FormatWP

Bool FormatWP
Default: **false**

Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments. Additionally, honors the booleans WPMarkFloats, WPMarkMinipages, WPMarkTOC, and WPMarkLOFT.

To help modify **lwarf** HTML output for easier import to a word processor, add

`\booltrue{FormatWP}`

to the project's source preamble after **lwarf** is loaded. The following changes are then made to the HTML output:

- If using a class without chapters, `\section` and lower are shifted up in level for the HTML heading tags. The css has not been changed, so the section heading formats will not match the normal HTML output, but when imported to LibreOffice Writer the higher section headings will import as **Heading 1** for the title, **Heading 2** for `\section`, etc.
- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.
- Forces single-file output.
- Turns off HTML debugging comments. These are comments appearing inside the HTML code, marking the opening/closing of sections and `<div>`s, but they are no longer useful when the document has been imported into a word processor.

- An additional `<div>` with an `id` encapsulates each float and minipage, which on import into **LibreOffice Writer** causes a thin frame to appear around the text block for each.
- Float captions are given an explicit italic formatting.
- Tabular rule borders are made explicit for **LibreOffice Writer**. LIBREOFFICE displays a light border around each cell while editing, even those which have no border when printed, and **lwarf** also uses a light border for thin rules, so it will be best to judge the results using the print preview instead of while editing in LIBREOFFICE.
- `\includegraphics` and `svg` math width and height are made explicit for LIBREOFFICE.
- `\hspace` is approximated by a number of `\quads`, and rules are approximated by a number of underscores.
- Explicit HTML styles are given to:
 - `\textsc`, etc.
 - `\underline`, **soul** and **ulem** markup.
 - `center`, `flushleft`, `flushright`.
 - `\marginpar`, **keyfloat**, **sidenotes**, **floatflt**, and **wrapfig**.
 - **fancybox** `\shadowbox`, etc.
 - The $\mathrm{\mathbb{E}\Gamma\mathrm{E}}$ and $\mathrm{T\Gamma\mathrm{E}}$ logos.

- Honors several booleans:

WPMarkFloats: Marks the begin and end of floats.

WPMarkMinipages: Marks the begin and end of minipages.

WPMarkTOC: Marks the location of the Table of Contents.

WPMarkLOFT: Marks the locations of the List of Figures/Tables.

WPMarkMath: Prints $\mathrm{\mathbb{E}\Gamma\mathrm{E}}$ math instead of using images.

WPTitleHeading: Adjusts title and section headings.

Several of these may be used to add markers to the HTML text which help determine where to adjust the word processor document after import.

12.2 Additional modifications

WPMarkFloats

Adds

```
==== begin table ====
...
==== end ===
```

or

```
==== begin figure ====
...
==== end ===
```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions.

WPMarkMinipages

Adds

```
==== begin minipage ===
...
==== end minipage ===
```

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

WPMarkTOC

While formatting for word processors, adds

```
==== table of contents ===
```

Bool WPMarkTOC

Default: true

where the Table of Contents would have been. This helps identify where to insert the actual TOC.

If set false, the actual toc is printed instead.

WPMarkLOFT

While formatting for word processors, adds

```
==== list of figures ==== and/or
==== list of tables ====
```

Bool WPMarkLOFT

Default: false

where each of these lists would have been. This helps identify where to insert the actual lists.

If set false, the actual lists are printed instead.

WPMarkMath

While formatting for word processors, prints math as L^AT_EX code instead of creating SVG images or MATHJAX. This is useful for cut/paste into the LibreOffice Writer TeXMaths extension.

Bool WPMarkMath

Default: false

Prog TeXMaths

siunitx

\usepackage{siunitx}

in the TeXMaths preamble. Equation numbering is problematic for AMS math environments.

WPTitleHeading

While formatting for word processors, true sets the document title to <h1>, which is expected for HTML documents, but also causes the lower-level section headings to start at **Heading 2** when imported into LIBREOFFICE. Set to false to cause the title to be plain text, and the section headings to begin at **Heading 1**.

See table 7 on page 180.

12.3 Recommendations

TOC, LOF, LOT For use with LibreOffice Writer, it is recommended to:

1. Set \booltrue{FormatWP}.
2. Set \booltrue{WPMarkTOC} and \boolfalse{WPMarkLOFT}.
3. Use **lwarf** to generate the HTML document.
4. Copy/paste from the HTML document into an empty LibreOffice Writer document.
5. Manually insert a LIBREOFFICE TOC in the LIBREOFFICE document.

Table 7: Section HTML headings for word-processor conversion

Section	HTML headings*			
	With \chapter		Without \chapter	
	WPTitleHeading	WPTitleHeading	—	—
Title	<h1>	plain	<h1>	plain
\part	<h2>	<h1>	<h2>	<h1>
\chapter	<h3>	<h2>	—	—
\section	<h4>	<h3>	<h3>	<h2>
\subsection	<h5>	<h4>	<h4>	<h3>
\subsubsection	<h6>	<h5>	<h5>	<h4>
\paragraph	span	<h6>	<h6>	<h5>

* For default depths when not FormatWP, see table 8 on page 193.

6. Manually add frames around each float, adding a caption which is cut/pasted from each float's simulated caption.
7. Manually create cross references.

This process yields a document with an actual LIBREOFFICE Table of Contents, but a simulated List of Figures and List of Tables.

siunitx For **siunitx**, remember to adjust the preamble as mentioned above.

LO view border options LIBREOFFICE has options in the **View** menu to turn on/off the display of thin borders around table cells and text objects.

12.4 Limitations

Floats and captions are not explicitly converted to LIBREOFFICE floats with their own captions. Floats are surrounded by a thin frame in the LIBREOFFICE editor, and may be marked with WPMarkFloats, but are not given a proper LIBREOFFICE object frame. Captions are given an explicit italic formatting, but not a proper LIBREOFFICE paragraph style.

Cross references are not actual LIBREOFFICE linked cross references.

The List of Figures and List of Tables are not linked. The pasted pseudo LOF and LOT match the numbering of the L^AT_EX and HTML versions.

Equation numbering is not automatic, but the equation numbers in SVG math will match the L^AT_EX and HTML output. SVG math is recommended when using the *AMS* environments, which may have multiple numbered equations per object.

As of when last checked, LIBREOFFICE ignores the following:

- Minipage alignment.
- Tabular cell vertical alignment.
- Image rotation and scaling.
- Rounded border corners, which are also used by:
 - \textcircled
 - **booktabs** trim
- \hspace and rules, also used by **algorithmic**.
- Coloring of text decorations, used by **soul** and **ulem**.
- Overline text decoration, used by **romanbar**.

Libreoffice also has limitations with frames and backgrounds:

- Multiple lines in an object are framed individually instead of as a whole.
- Nested frames are not handled correctly.
- Images inside boxes are not framed correctly.
- Spans with background colors and frames are not displayed correctly.

13 Modifying lwarf

locating something To quickly find the source for a package in `lwarf.dtx`, search for `*packagename`, such as `*siunitx`.

Likewise, to quickly find the source for a file in `lwarf.dtx`, search for `*filename`, such as `*lwarf.css`.

Purely text-based packages probably will work as-is when generating `HTML`.

Look to existing code for ideas on how to expand into new code.

image of TeX output An environment may be converted to a `lateximage` then displayed with an image of the resulting `\TeX` output. See section 85 for an example of the `picture` environment.

CSS classes To create a custom `HTML` block or inline `css` class, see section 50.8.

print/HTML macros To create print and `HTML` versions of the same macro or environment, see section 34.

⚠ TeX boxes Any `\TeX` boxes must be undone, as `SVG` math or `lateximages` require `\newpage`, which will not work in a `\TeX` box.

index recreation To recreate the index for the `lwarf` documentation:

```
makeindex -s gglo.ist -o lwarf.gls lwarf.glo
splitindex lwarf.idx -- -s gind.ist
```

13.1 Creating a development system

The following creates a local development system for `lwarf` on a TeXLive system in a Unix-like environment. Doing so allows anything requesting `lwarf` to use the development version instead of whichever version is installed in TeXLive.

Create a development directory:

Place into this directory `lwarf.dtx` and `lwarf.ins`.

To create `lwarf.sty`, execute

Enter ⇒ `pdflatex lwarf.ins`

which creates `lwarf.sty` and several hundred additional `lwarf-*.sty` files for the various packages which are supported.

To create the documentation `lwarf.pdf`, execute

Enter ⇒ `pdflatex lwarf.dtx`

To make the development files visible to other projects:

Create the directory

```
/usr/local/texlive/texmf-local/tex/latex/local/lwarf
```

Inside this directory, create the file update, containing:

```
ln -s /path_to_dev_directory/lwarf*.sty .
ln -s /path_to_dev_directory/lwarf_baseline_marker.png .
ln -s /path_to_dev_directory/lwarf_baseline_marker.eps .
mktexlsr
```

Run ./update now, and whenever a new lwarf-* package is added.

To make the development version of lwarpmk visible to other projects:

```
cd /opt
ln -s /usr/local/texlive/texmf-local/bin/x86_64-linux texbin_local
cd texbin_local
ln -s ../../scripts/lwarf/lwarpmk.lua lwarpmk
cd /usr/local/texlive/texmf-local/scripts/
mkdir lwarf
cd lwarf
ln -s /path_to_dev_directory/lwarpmk.lua lwarpmk
```

Verify that the correct version is found with

Enter ⇒ which lwarpmk

To make the local versions visible to the shell:

Paths must be set by the shell startup, such as in .bashrc and .cshrc:

In .bashrc:

```
PATH=/opt/texbin_local:/opt/texbin:$PATH
```

In .cshrc:

```
setenv PATH ${HOME}/bin:/opt/texbin_local:/opt/texbin:${PATH}
```

13.2 Modifying a package for l warp

If a class loads additional packages, it will be required to modify the class for **l warp**, since **l warp** must be loaded before most other packages.

To work with **l warp**, a class must first set up anything which replicates the functions of the basic \TeX classes, load any required fonts, then load **l warp**, then finally load and adjust any other required packages.

When creating **HTML**, **l warp** redefines the `\usepackage` and `\RequirePackage` macros such that it first looks to see if a `l warp-<packagename>.sty` version exists. If so, the **l warp** version is used instead. This modular system allows users to create their own versions of packages for **l warp** to use for **HTML**, simply by creating a new package with a `l warp-` prefix. If placed in the local directory along with the source code, it will be seen by that project alone. If placed alongside the other `l warp-` packages where \TeX can see it, then the user's new package will be seen by any documents using **l warp**. (Remember `mktexlsr` or `texhash`.)

An `l warp-<packagename>.sty` package is only used during **HTML** generation. Its purpose is to pretend to be the original package, while modify anything necessary to create a successful **HTML** conversion. For many packages it is sufficient to simply provide nullified macros, lengths, counters, etc. for anything which the original package does, while passing the raw text on to be typeset. See the pre-existing `l warp-` packages for examples.

Anything the user might expect of the original package must be replaced or emulated by the new `l warp-` package, including package options, user-adjustable counters, lengths, and booleans, and conditional behaviors. In many of these packages, most of the new definitions have a “local” prefix according to the package name, and @ characters inside the name, which hides these names from the user. In most cases these macros will not need to be emulated for **HTML** output. Only the “user-facing” macros need to be nullified or emulated.

Each lwarf- package should first call either

```
\LWR@ProvidesPackageDrop
```

or

```
\LWR@ProvidesPackagePass
```

If “Drop”ped, the original print-version package is ignored, and only the lwarf-version is used. Use this where the original print version is useless for HTML. If “Pass”ed, the original package is loaded first, with the user-supplied options, then the lwarf- version continues loading as well. See section 306 (ntheorem) for an example of selectively disabling user options for a package. Use this when HTML output only requires some modifications of the original package. For a case where the original package is usable without changes, there is no need to create a lwarf-version.

13.2.1 Adding a package to the lwarf.dtx file

When adding a package to lwarf.dtx for permanent including in **lwarf**, provide the lwarf-<packagename> code in lwarf.dtx, add its entry into lwarf.ins, and also remember to add

```
\LWR@loadafter{<packagename>}
```

to lwarf.dtx in section 26.1. This causes **lwarf** to stop with an error if **packagename** is loaded before **lwarf**. Finally, add an entry in table 1, Supported packages and features, and also the Updates section.

13.3 Modifying a class for lwarf

If a class loads additional packages, it will be required to modify the class for **lwarf**, since **lwarf** must be loaded before most other packages.

To work with **lwarf**, a class must first set up anything which replicates the functions of the basic L^AT_EX classes, load any required fonts, then load **lwarf**, then finally load and adjust any other required packages.

13.4 Testing lwarf

When changes have been made, test the print output before testing the HTML. The print output compiles faster, and any errors in the printed version will be easier to figure out than the HTML version.

Remember that the configuration files are only rewritten when compiling the printed version of the document.

When changing the source to **lwarpmk** or a css file in l warp .dtx:

1. Change the source in l warp .dtx.
2. pdflatex l warp .ins
3. pdflatex l warp .dtx
4. If modifying **lwarpmk** the new version should now be active.
5. If modifying css files:
 - (a) For the document, l warpmk print to update the css files in the project.
 - (b) Reload the HTML document to see the effect of the new css files.

Sometimes it is worth checking the <project>_html.pdf file, which is the PDF containing HTML tags. Also, <project>_html.html has the text conversion of these tags, before the file is split into individual HTML files.

It is also worth checking the browser's tools for verifying the correctness of HTML and css code.

13.5 Modifying lwarpmk

Prog l warpmk In most installations, l warpmk.lua is an executable file located somewhere the operating system knows about, and it is called by typing "l warpmk" into a terminal.
File l warpmk.lua

A project-local copy of l warpmk.lua may be generated, modified, and then used to compile documents:

1. Add the l warpmk option to the **l warp** package.
2. Recompile the printed version of the document. The l warpmk option causes **l warp** to create a local copy of l warpmk.lua
3. The l warpmk option may now be removed from the **l warp** package.
4. Copy and rename l warpmk.lua to a new file such as mymake.lua.
5. Modify mymake.lua as desired.
6. If necessary, make mymake.lua executable.
7. Use mymake.lua instead of l warpmk.lua.

14 Troubleshooting

14.1 Using the l warp.sty package

Also see:

Section 8.8: Commands to be placed into the warpprint environment

Section 9: Special cases and limitations

Text is not converting correctly / corrupted HTML tags:

- Font-related UTF-8 information must be embedded in the PDF file. See section 8.2 regarding bitmapped vs. vector fonts.
- See section 9.2.1 regarding HTML entities and the characters &, <, and >.

Undefined HTML settings:

- See the warning regarding the placement of the HTML settings at section 8.4.

Tabular problems: See section 9.9.

Obscure error messages:

Print first: Be sure that a print version of the document compiles and that your document's L^AT_EX code is correct, before attempting to generate an HTML version.

`\end{warpHTML}, \end{warpprint}, \end{warpall}`: Each of these must be without any other characters on the same line.

Options clash: If using `memoir`, see section 9.12.

“No room for a new \write.”: Before `\usepackage{l warp}`, add:

```
\usepackage{morewrites}  
\morewritessetup{allocate=10}
```

“Missing \$ inserted.”: If using a filename or URL in a footnote or `\item`, escape underscores with `_`.

“Label(s) may have changed. Rerun to get cross-references right.”:

This warning may repeat endlessly if a math expression is used in a caption. Simple math expressions such as `$X=1$` may be replaced with

```
\textit{X}\,=\,,1
```

“Leaders not followed by proper glue”: This can be caused by a missing `1@<floattype>` or `1@<sectiontype>` definition. See `l warp`'s definitions for examples.

“Improper `\prevdepth`”: `\ateximages` and `svg` math require `\newpage`, which cannot work inside `\TeX` boxes or `\ensuremath`. Anything using `\newsavebox`, `\newbox`, `\lrbox`, `\savebox`, `\hbox`, `\vbox`, `\usebox`, `\sbox`, etc., must be modified to work without box commands.

If you find something using `\ensuremath`, have it temporarily set:

```
\LetLtxMacro{\ensuredmath}{\LWR@origensuredmath}
```

inside a group first.

Also, custom macros which appear inside a section, figure, or table name should be made robust since they appear inside the `.toc`, `.lof`, or `.lot` files. Use `\newrobustcmd` or `\robustify` from `etoolbox`, `xparse`, etc.

If using BibTeX, see section 9.5.9.

“! Undefined control sequence. ... \begindocumenthook”: See section 9.13.4 if using `polyglossia`.

“`\begin{equation}` ended by `\end{document}`”: Do not use custom macros such as `\beq` and `\eeq` to replace

```
\begin{equation}
...
\end{equation}
```

“Misplaced `\omit`”: If using `\LWR@formatted` to define new macros for print and HTML modes, see section 34 regarding `\LWR@expandableformatted`.

Complicated objects inside math: Some objects, such as Tikz, may not compile in lwarf’s normal math emulation. Insert

```
\displaymathother -or- \inlinemathother  
before the math, and then
```

```
\displaymathnormal -or- \inlinemathnormal  
when displaying “normal” math. See section 9.6.8.
```

Slow compilation of math objects: Complicated math objects can also cause problems with alt tags, resulting in very slow compilation, large alt tags, and possible crashes. Use `\inlinemathother ... \inlinemathnormal` or `\displaymathother ... \displaymathnormal` around the math expression.

△ MATHJAX **Incorrect MATHJAX:** Some objects do not convert to MATHJAX. Use `\displaymathother` before these objects, then `\displaymathnormal` to return to “normal” display math. See section 9.6.8.

Missing sections: See section 8.4 regarding the `FileDepth` and `SideTOCDepth` counters, and the use of `\tableofcontents` in the home page.

Misnumbered footnotes from section headings: See section 9.4.4.

Missing HTML files:

- See the warning regarding changes to the HTML settings at section 8.4.
- Ensure that the filenames are unique after math and short words are removed. See FileSectionNames at section 8.4.

Missing / incorrect cross-references:

- Use lwarfpmk again followed by lwarfpmk html or lwarfpmk print to compile the document one more time.

- Labels with special characters may be a problem. It is best to stick with alpha-numeric, hyphen, underscore, and perhaps the colon (if not French).

\nameref refers to the most recently-used section where the \label was defined. If no section has been defined before the \label, the link will be empty. Index entries also use \nameref and have the same limitation.

- **cleveref** and **varioref** are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for \cpageref and \cpagerefrange. This phrase includes \cpagerefFor, which defaults to "for".

Ex:

```
\cpageref{tab:first,tab:second}
in HTML becomes:
“pages for table 4.1 and for table 4.2”
```

See \cpagerefFor at page 552 to redefine the message which is printed for page number references.

BibTeX errors with \etalchar: See section 9.5.9.

Malformed URLs: Do not use the % character between arguments of \hyperref, etc., as this character is among those which is neutralized for inclusion in HTML URLs.

Em-dashes or En-dashes in listing captions and titles:

Use X_ET_EX or LuaX_ET_EX.

FLOATS OUT OF SEQUENCE:

Mixed “Here” and floating: Floats [H]ere and regular floats may become out of order. \clearpage if necessary.

Caption setup: With \captionsetup set the positions for the captions above or below to match their use in the source code.

IMAGES ARE APPEARING IN STRANGE PLACES:

- Enter lwarfpmk limages to refresh the lateximage images.

SVG images:**⚠️ adding/removing**

When a math expression, `picture`, or `Tikz` environment is added or removed, the `svg` images must be re-created by entering `lwarpmk images` to maintain the proper image-file associations. Inline `svg` math may be hashed and thus not need to be recreated, but display math and objects such as `Tikz` may move to new image numbers when the document is changed.

Before attempting to create the `svg` image files, `lwarpmk` verifies that the `HTML` version of the document exists and has correct internal image references.¹⁵ If it is necessary to recompile the document's `HTML` version, `lwarpmk` will inform so with an error message.

If `HTML` appears where an `svg` image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time. `lwarpmk` attempts to detect this situation and print a warning.

Incorrect `svg` images will also occur if the document changes the page counter:

⚠️ page counter

```
\setcounter{page}{<value>}
```

The page counter must *not* be adjusted by the user.

⚠️ Lots of files!

Expressing math as `svg` images has the advantage of representing the math exactly as `LATEX` would, but has the disadvantage of requiring an individual file for each math expression. For inline math, and some other objects, `lwarf` uses an MD5 hash on its `LATEX` source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as `picture` and `Tikz` require one image file each. For a document with a large amount of math, see section 6.5 to use `MATHJAX` instead.

Plain-looking document:

- The document's `css` stylesheet may not be available, or may be linked incorrectly. Verify any `\CSSFilename` statements point to a valid `css` file.

Broken fragments of HTML:

- Check the `PDF` file used to create `HTML` to see if the tags overflowed the margin. (This is why such large page size and margins are used.)

Changes do not seem to be taking effect:

- Be sure to `lwarpmk clean`, recompile, then start by reloading the home page. You may have been looking at an older version of the document. If you changed a section name, you may have been looking at the file for the old name.
- See the warning regarding changes to the `HTML` settings at section 8.4.
- Verify that the proper `css` is actually being used.

¹⁵This becomes important when dealing with a document containing thousands of images.

- The browser may compensate for some subtle changes, such as automatically generating ligatures, reflowing text, etc.

Un-matched conditional compiles:

- Verify the proper begin/end of warpprint, warpHTML, and warpall environments.

14.1.1 Debug tracing output

\tracinglwarp When \tracinglwarp is used, **lwarp** will add extra tracing messages to the .log file. The last several messages may help track down errors.

Place \tracinglwarp just after \usepackage{lwarp} to activate tracing.

14.2 Compiling the lwarp.dtx file

lwarp_tutorial.tex: Copy or link lwarp_tutorial.txt from the TDS doc directory to the source directory, or wherever you wish to compile the documentation. This file is included verbatim in the documentation, but is in the doc directory so that it may be found by **texdoc** and copied by the user.

Illogical error messages caused by an out-of-sync lwarp.sty file:

1. Delete the lwarp.sty file.
2. Enter **pdflatex lwarp.ins** to generate a new lwarp.sty file.
3. Enter **pdflatex lwarp.dtx** to recompile the lwarp.pdf documentation.

Un-nested environments:

Be sure to properly nest:

- `\begin{macrocode}` and `\end{macrocode}`
- `\begin{macro}` and `\end{macro}`
- `\begin{environment}` and `\end{environment}`

File 1 **l warp .sty**

15 Implementation

This package is perhaps best described as a large collection of smaller individual technical challenges, in many cases solved through a number of *erude haeks* clever tricks. Reference sources are given for many of the solutions, and a quick internet search will provide additional possibilities.

Judgement calls were made, and are often commented. Improvements are possible. The author is open to ideas and suggestions.

Packages were patched for re-use where they provided significant functionality. Examples include **xcolor** with its color models and conversion to **HTML** color output, and **siunitx** which provides many number and unit-formatting options, almost all of which are available in pure-text form, and thus easily used by **pdftotext**.

Packages were emulated where their primary purpose was visual formatting which is not relevant to **HTML** output. For example, packages related to sectioning are already patched by numerous other packages, creating a difficult number of combinations to try to support, and yet in **HTML** output all of the formatting is thrown away, so these packages are merely emulated.

Packages with graphical output are allowed as-is, but must be nested inside a **lateXimage** environment to preserve the graphics.

Testing has primarily been done with the Iceweasel/Firefox browser.

Table 8: Section depths and HTML headings

Section	\LaTeX depth	HTML headings *
title of the entire website		<h1>
none	-5	new for this package
book	-2	not yet used
part	-1	<h2>
chapter	0	<h3>
section	1	<h4>
subsection	2	<h5>
subsubsection	3	<h6>
paragraph	4	
subparagraph	5	
listitem	7	new for this package, used for list items

* If `FormatWP` is true, section headings may be adjusted, depending on `WPTitleHeading`. See table 7 on page 180.

16 Section depths and HTML headings

Stacks are created to track depth inside the \LaTeX document structure. This depth is translated to HTML headings as shown in table 8. “Depth” here is not depth in the traditional computer-science stack-usage sense, but rather a representation of the nesting depth inside the \LaTeX document structure.

When starting a new section, the program first must close out any existing sections and lists of a deeper level to keep the HTML tags nested correctly.

Support for the `memoir` package will require the addition of a book level, which may push the HTML headings down a step, and also cause `subsubsection` to become a `<div>` due to a limit of six HTML headings.

It is possible to use HTML5 `<section>` and `<h1>` for all levels, but this may not be well-recognized by older browsers.

Fixed levels for parts and chapters allow the css to remain fixed as well.

17 Source Code

This is where the documented source code for **lwarf** begins, continuing through the following sections all the way to the change log and index at the end of this document.

The following sections document the actual implementation of the **lwarf** package.

line numbers The small numbers at the left end of a line refer to line numbers in the `lwarf.sty` file.

subjects Blue-colored tags in the left margin aid in quickly identifying the subject of each paragraph.

objects Black-colored tags in the left margin are used to identify programming objects such as files, packages, environments, booleans, and counters. Items without a tag are

index entries command macros. Each of these also appears in the index as individual entries, and are also listed together under “files”, “packages”, “environments”, “booleans”, and “counters”.

 **warnings** Special warnings are marked with a warning icon.

for HTML output: Green-colored tags in the left margin show which sections of source code apply to

for PRINT output: the generation of HTML, print, or both forms of output.

for HTML & PRINT:

18 Detecting the TeX Engine — pdflatex, lualatex, xe-latex

See: <http://tex.stackexchange.com/a/47579>.

Detects XeTeX and LuaTeX:

```

1 \RequirePackage{ifutex}
2 \newif\ifxetexorluatex
3 \ifXeTeX
4   \xetexorluatextrue
5 \else
6   \ifLuaTeX
7     \xetexorluatextrue
8   \else
9     \xetexorluatexfalse
10  \fi
11 \fi
12
13 \ifLuaTeX
14 \RequirePackage{luatex85}% until the geometry package is updated
15 \fi
16
17 \RequirePackage{ifpdf}
```

19 MD5 hashing

The MD5 hash is used for `lateximage` filenames for SVG math.

```

18 \newcommand{\LWR@mdfive}[1]{%
19 \PackageError{l warp}%
20 {No MD5 macro was found.}%
21 {\Lwarp must find the macros pdfmdfivesum or mdfivesum.}%
22 }
23
24 \ifPDFTeX% pdflatex or dvi latex
25 \let\LWR@mdfive\pdfmdfivesum
26 \fi
27
28 \ifLuaTeX
29 \RequirePackage{pdftexcmds}
30 \let\LWR@mdfive\pdf@mdfivesum
31 \fi
32
33 \ifXeTeX
```

```

34 \@ifundefined{pdffivesum}{}{%
35   {\let\LWR@mdfive\pdfmdfivesum}%
36 \@ifundefined{mdfivesum}{}{%
37   {\let\LWR@mdfive\mdfivesum}%
38 \fi}

```

20 pdfLaTeX T1 and UTF8 encoding

When using `pdfLTE`, **l warp** requires T1 encoding, and recommends UTF8 encoding.

If some other input encoding is already defined, **l warp** will try to use it instead, and hope for the best.

`XLTE` and `LuaLTE` are both UTF8 by nature.

```

39 \ifPDFTeX% pdflatex or dvi latex
40 \RequirePackage[T1]{fontenc}
41
42 \@ifpackageloaded{inputenc}{}{%
43   \@ifpackageloaded{inputenx}{}{%
44     \RequirePackage[utf8]{inputenc}%
45   }%
46 }%
47 \fi

```

21 Unicode input characters

for HTML & PRINT: If using `pdflatex`, convert a minimal set of Unicode characters. Additional characters may be defined by the user, as needed.

A commonly-used multiply symbol is declared to be `\textttimes`.

The first arguments of `\newunicodechar` below are text ligatures in the source code, even though they are not printed in the following listing.

```

48 \RequirePackage{newunicodechar}
49
50 \newunicodechar{x}{\textttimes}
51
52 \ifPDFTeX% pdflatex or dvi latex
53 \newunicodechar{ff}{ff}% the first arguments are ligatures
54 \newunicodechar{fi}{fi}
55 \newunicodechar{fl}{fl}

```

```

56 \newunicodechar{ffi}{ffi}
57 \newunicodechar{ffl}{ffl}
58 \newunicodechar{--}{---}
59 \newunicodechar{-}{--}

```

In PDFT_EX, preserve upright quotes in verbatim text:

```

60 \RequirePackage{upquote}
61 \else
62 \fi

```

22 Miscellaneous tools

\LWR@providelength {<\lengthname>} Provides the length if it isn't defined yet.

Used to provide source compatibility for lengths which will be ignored, but might or might not be already provided by other packages.

```

63 \newcommand*\LWR@providelength[1]{%
64     \ifdefined\length{#1}{}{\newlength{#1}}%
65 }

```

Prints a length in the given units, without printing the unit itself.

```

\LWR@convertto {<dest unit>} {<length>}
66 \newcommand*{\LWR@convertto}[2]{\strip@pt\dimexpr #2*65536/\number\dimexpr 1#1}

```

\LWR@patcherror {<packagename>} {<macroname>}

Prints an error if could not patch a macro.

```

67 \newcommand*{\LWR@patcherror}[2]{%
68 \PackageError{l warp}%
69 {Unable to patch package #1, macro #2}%
70 {Please contact the author of the l warp package.}%
71 }

```

23 Early package requirements

Pkg etoolbox Provides \ifbool and other functions.

Pkg `xpatch` Patches macros with optional arguments.

```
72 \RequirePackage{etoolbox}[2011/01/03]%
73 \RequirePackage{xpatch}
```

Pkg `ifplatform` Provides `\ifwindows` to try to automatically detect WINDOWS OS.

```
74 \RequirePackage{ifplatform}%
sense op-system platform
```

Pkg `letltxmacro` Used to redefine `\textbf` and friends.

```
75 \RequirePackage{letltxmacro}
```

24 Operating-System portability

Prog Unix **lwarf** tries to detect which operating system is being used. UNIX / MAC OS / LINUX is the default (collectively referred to as “UNIX” in the configuration files), and MS-WINDOWS is supported as well.

Prog Mac OS If MS-WINDOWS is not correctly detected, use the **lwarf** option `OSWindows`.

Prog Windows When detected or specified, the operating-system path separator used by **lwarf** is modified, and the boolean `usingOSWindows` is set true. This boolean may be tested by the user for later use.

24.1 Literal characters

Literal characters to be used in `PrintLatexCmd` and `HTMLLatexCmd`. These are defined without @ to easily allow their inclusion in the user’s document.

The literal % character:

```
76 \let\LWRpercent\@percentchar
```

The literal \$ character:

```
77 \catcode`\$=12
78 \def\LWRdollar{\$}
79 \catcode`\$=3
```

The literal & character:

```
80 \catcode`\\=12
81 \def\LWRamp{&}
82 \catcode`\\=4
```

The literal \ character. The ampersand is temporarily set to the escape character during the definition of the backslash macro.

```
83 \catcode`\\=0
84 &\catcode`\\=12
85 &\def&\LWRbackslash{\}
86 &\catcode`\\=0
87 \catcode`\\=4
```

The literal # character:

```
88 \catcode`\\#=12
89 \def\LWRhash{#}
90 \catcode`\\#=6
```

\LWRopquote The operating system's quote mark, UNIX default. For WINDOWS, see \LWR@setOSWindows, below.

```
91 \def\LWRopquote{'}  
92 \def\LWRopseq{\space\LWRamp\LWRamp\space\space}
```

\LWRopseq The operating system's sequential execution command, UNIX default. For WINDOWS, see \LWR@setOSWindows, below.

24.2 Common portability code

Bool usingOSWindows Set if the OSWindows option is used, or if WINDOWS is automatically detected.

```
93 \newbool{usingOSWindows}
94 \boolfalse{usingOSWindows}
```

24.3 Unix, Linux, and Mac OS

\OSPathSymbol Symbol used to separate directories in a path.

```
95 \newcommand*\OSPathSymbol{/}
```

24.4 MS-WINDOWS

For MS-WINDOWS:

\LWR@setOSWindows Set defaults for the MS-WINDOWS operating system. **l warp** attempts to auto-detect the operating system, and the OSWindows option may also be used to force MS-WINDOWS compatibility.

```
96 \newcommand*{\LWR@setOSWindows}{  
97 {  
98 \booltrue{usingOSWindows}  
99 \renewcommand*{\OSPathSymbol}{\@backslashchar}  
100 \def\LWRopquote{"}  
101 \def\LWRopseq{\space\WRamp\space\space}  
102 }
```

Test for windows during compile. The user may also specify OSWindows package option in case this test fails.

```
103 \ifwindows  
104 \LWR@setOSWindows  
105 \fi
```

25 Package options

Pkg kvoptions Allows key/value package options.

```
106 \RequirePackage{kvoptions}  
107 \SetupKeyvalOptions{family=LWR,prefix=LWR@}
```

\l warpsetup A user interface to set the keys:

```
108 \newcommand{\l warpsetup}[1]{\setkeys{LWR}{#1}}
```

Bool warpingprint

Bool warpingHTML

Bool mathjax

Bool LWR@origmathjax

Set to true/false depending on the package option selections for print/HTML/EPUB output and mathsvg/mathjax.

LWR@origmathjax remembers the original setting to be restored by \displaymathnormal.

```
109 \newbool{warpingprint}
```

```

110 \newbool{warpingHTML}
111 \newbool{mathjax}
112 \newbool{LWR@origmathjax}

```

defaults The default is print output, and SVG math if the user chose HTML output.

```

113 \booltrue{warpingprint}%
114 \boolfalse{warpingHTML}%
115 \boolfalse{mathjax}%

```

Opt warpprint If the warpprint option is given, boolean warpingprint is true and boolean warpingHTML is false, and may be used for \ifbool tests.

```

116 \DeclareVoidOption{warpprint}{%
117 \PackageInfo{l warp}{Using option 'warpprint'}%
118 \booltrue{warpingprint}%
119 \boolfalse{warpingHTML}%
120 }

```

Env warpHTML Anything in the warpHTML environment will be generated for HTML output only.

Opt warpHTML If the warpHTML option is given, boolean warpingHTML is true and boolean warpingprint is false, and may be used for \ifbool tests.

```

121 \DeclareVoidOption{warpHTML}{%
122 \PackageInfo{l warp}{Using option 'warpHTML'}%
123 \booltrue{warpingHTML}%
124 \boolfalse{warpingprint}%
125 }

```

Opt mathsvg Option mathsvg selects SVG math display: If the mathsvg option is given, boolean mathjax is false, and may be used for \ifbool tests.

```

126 \DeclareVoidOption{mathsvg}{%
127 \PackageInfo{l warp}{Using option 'mathsvg'}%
128 \boolfalse{mathjax}%
129 \boolfalse{LWR@origmathjax}%
130 }

```

Opt mathjax Option mathjax selects MATHJAX math display: If the mathjax option is given, boolean mathjax is true, may be used for \ifbool tests.

```

131 \DeclareVoidOption{mathjax}{%
132 \PackageInfo{l warp}{Using option 'mathjax'}%
133 \booltrue{mathjax}%
134 \booltrue{LWR@origmathjax}%
135 }

```

Opt `BaseJobname` Option `BaseJobname` sets the `\BaseJobname` for this document.

This is the `\jobname` of the printed version, even if currently compiling the `HTML` version. I.e. this is the `\jobname` without `_html` appended. This is used to set `\HomeHTMLFilename` if the user did not provide one.

```
136 \DeclareStringOption[\jobname]{BaseJobname}
```

Opt `makeindexStyle` Selects a custom `.ist` file. The default is `lwarf.ist`. A customized file should be based on `lwarf.ist`, and must retain the lines related to `\hyperindexref`.

```
137 \DeclareStringOption[lwarf.ist]{makeindexStyle}
```

Opt `xindyStyle` Selects a custom `.xdy` file. The default is `lwarf.xdy`. A customized file should be based on `lwarf.xdy`, and must retain the line

```
(markup-locref :open "\hyperindexref{" :close "})
```

```
138 \DeclareStringOption[lwarf.xdy]{xindyStyle}
```

Opt `xindyLanguage` Sets the `xindy` language to be assigned in `lwarpmk`'s configuration files. This is then used by `lwarpmk` while processing the index and glossary.

```
139 \DeclareStringOption[english]{xindyLanguage}
```

Opt `xindyCodepage` Sets the `xindy` codepage to be assigned in `lwarpmk`'s configuration files. This is then used by `lwarpmk` while processing the index.

```
140 \DeclareStringOption[utf8]{xindyCodepage}
```

Opt `pdftotextEnc`
Default: `UTF-8` The option `pdftotextEnc` sets the encoding used by `pdftotext`. This is passed to `pdftotext` using its `-enc` option, and is used when converting `LEX` PDF output with HTML tags into a plain-text file with HTML tags.

```
141 \DeclareStringOption[UTF-8]{pdftotextEnc}
```

Opt `lwarpmk` Tells `lwarf` to generate a local copy of `lwarpmk` called `lwarpmk.lua`. Useful for archiving for future use. This file may be made executable and acts just like `lwarpmk`.

If `lwarpmk` option, creates a local copy of `lwarpmk.lua`:

```
142 \newbool{LWR@creatinglwarpmk}
143 \boolfalse{LWR@creatinglwarpmk}
144
```

```
145 \DeclareVoidOption{lwarpmk} {
146 \PackageInfo{lwarf}{Using option 'lwarpmk'}
147 \booltrue{LWR@creatinglwarpmk}
148 }
```

- Opt OSWindows Tells **lwarf** to use MS-WINDOWS compatibility. Auto-detection of the operating system is attempted, and this option is only necessary if the auto-detection fails. See the automatically-generated `lwarpmk.conf` file to find out whether the operating system was detected correctly.

```
149 \DeclareVoidOption{OSWindows} {
150 \PackageInfo{lwarf}{Using option 'OSWindows'}
151 \LWR@setOSWindows
152 }
```

- Opt HomeHTMLFilename The filename of the homepage. The default is the jobname. This option is stored into `\LWR@HomeHTMLFilename`, and later transferred into `\HomeHTMLFilename` for internal use.
 Default: `\lwarf`

```
153 \DeclareStringOption[] {HomeHTMLFilename}
```

- Opt HTMLFilename The filename prefix of web pages after the homepage. The default is empty, no prefix. This option is stored into `\LWR@HTMLFilename`, and later transferred into `\HTMLFilename` for internal use.
 Default: `<empty>`

```
154 \DeclareStringOption[] {HTMLFilename}
```

- Opt PrintLatexCmd The shell commands to use to compile the print document.
 Default: `<automatic>`

```
155 \DeclareStringOption[] {PrintLatexCmd}
```

- Opt HTMMLatexCmd The shell commands to use to compile the HTML document.
 Default: `<automatic>`

```
156 \DeclareStringOption[] {HTMMLatexCmd}
```

- Opt PrintIndexCmd The shell commands to use to compile the print indexes.
 Default: `<empty>`

```
157 \DeclareStringOption[] {PrintIndexCmd}
```

- Opt HTMLIndexCmd The shell commands to use to compile the HTML indexes.
 Default: `<empty>`

```
158 \DeclareStringOption[] {HTMLIndexCmd}
```

- Opt LatexmkIndexCmd The shell commands to be used by **latexmk** to compile the print indexes. Unlike
 Default: `<empty>`

`PrintIndexCmd` and `HTMLIndexCmd`, `LatexmkIndexCmd` does not include the file-name, which will be provided by `latexmk`.

```
159 \DeclareStringOption[] {LatexmkIndexCmd}
```

`Opt makeindex` Tells `lwarf` to use `makeindex` for index generation. When `lwarpmk.conf` and `*.lwarpmkconf` are generated, `PrintIndexCmd` and `HTMLIndexCmd` will be set for `makeindex` with a single index file.

```
160 \DeclareBoolOption[false] {makeindex}
```

`Opt xindy` Tells `lwarf` to use `xindy` for index generation. When `lwarpmk.conf` and `*.lwarpmkconf` are generated, `PrintIndexCmd` and `HTMLIndexCmd` will be set for `xindy` with a single index file.

```
161 \DeclareBoolOption[false] {xindy}
```

`Opt GlossaryCmd` The shell command to use to compile the glossary. The print or HTML version of the glossary filename will be appended to this command.
`Default: makerglossaries`

```
162 \DeclareStringOption[makerglossaries] {GlossaryCmd}
```

`Opt latexmk` Option `latexmk` tells `lwarpmk` to use `latexmk` when compiling documents.

```
163 \DeclareBoolOption[false] {latexmk}
```

`Opt dvips` Option `dvips` tells `lwarpmk` to use `dvips` when compiling DVI `latex` documents.

```
164 \DeclareBoolOption[false] {dvips}
```

`Opt dvipdfm` Option `dvipdfm` tells `lwarpmk` to use `dvipdfm` when compiling DVI `latex` documents.

```
165 \DeclareBoolOption[false] {dvipdfm}
```

`Opt dvipdfmx` Option `dvipdfmx` tells `lwarpmk` to use `dvipdfmx` when compiling DVI `latex` documents.

```
166 \DeclareBoolOption[false] {dvipdfmx}
```

Execute options Execute the package options, with the defaults which have been set just above:

```
167 \ProcessKeyvalOptions*\relax
```

Assign the `\BaseJobname` if the user hasn't provided one:

```
168 \providecommand*\{\BaseJobname}\{\LWR@\BaseJobname\}
```

Defaults unless already over-ridden by the user:

```

169 \ifcsempty{\LWR@HomeHTMLFilename}{
170   \newcommand*{\HomeHTMLFilename}{\BaseJobname}
171 }{
172   \csedef{\HomeHTMLFilename}{\LWR@HomeHTMLFilename}
173 }
174
175 \csedef{\HTMLFilename}{\LWR@HTMLFilename}
```

\LWR@PrintIndexCmd and \LWR@HTMLIndexCmd are tested to see if they are empty. If so, they are set to a reasonable defaults for a single index using **makeindex**, then possibly set to defaults for **xindy** if the **lwarf xindy** option was selected.

```

176 \ifdefempty{\LWR@PrintIndexCmd}{
177   \renewcommand{\LWR@PrintIndexCmd}{%
178     makeindex -s \LWR@makeindexStyle \space \jobname.idx%
179   }
180   \ifbool{\LWR@xindy}{%
181     \renewcommand{\LWR@PrintIndexCmd}{%
182       xindy
183       -M \LWR@xindyStyle \space
184       -L \LWR@xindyLanguage \space
185       -C \LWR@xindyCodepage \space
186       \jobname.idx%
187     }
188   }{}
189 }{}
190
191 \ifdefempty{\LWR@HTMLIndexCmd}{%
192   \renewcommand{\LWR@HTMLIndexCmd}{%
193     makeindex -s \LWR@makeindexStyle \space \jobname_html.idx%
194   }
195   \ifbool{\LWR@xindy}{%
196     \renewcommand{\LWR@HTMLIndexCmd}{%
197       xindy
198       -M \LWR@xindyStyle \space
199       -L \LWR@xindyLanguage \space
200       -C \LWR@xindyCodepage \space
201       \jobname_html.idx%
202     }
203   }{}
204 }{}
205
206 \ifdefempty{\LWR@LatexmkIndexCmd}{%
207   \renewcommand{\LWR@LatexmkIndexCmd}{%
208     makeindex -s \LWR@makeindexStyle%
209   }
210   \ifbool{\LWR@xindy}{%
```

```

211     \renewcommand{\LWR@LatexmkIndexCmd}{%
212         xindy
213         -M \LWR@xindyStyle \space
214         -L \LWR@xindyLanguage \space
215         -C \LWR@xindyCodepage%
216     }
217 }{ }
218 }{ }

```

25.1 Conditional compilation

\warpprintonly {*contents*}

Only process the contents if producing printed output.

```
219 \newcommand{\warpprintonly}[1]{\ifbool{warpingprint}{#1}{}}
```

\warpHTMLonly {*contents*}

Only process the contents if producing HTML output.

```
220 \newcommand{\warpHTMLonly}[1]{\ifbool{warpingHTML}{#1}{}}
```

Pkg comment Provides conditional code blocks.

Attempts to use **versions** or **verbatim** fail in some cases, and do not provide much of a speed benefit even when they do work.

```
221 \RequirePackage{comment}
```

Use `comment_print.cut` for print mode, and `comment_html.cut` for HTML mode. This helps **latexmk** to more reliably know whether to recompile.

```

222 \ifbool{warpingHTML}{%
223 \def\DefaultCutFileName{\def\CommentCutFile{comment_html.cut}}%
224 }{}%
225 %
226 \ifbool{warpingprint}{%
227 \def\DefaultCutFileName{\def\CommentCutFile{comment_print.cut}}%
228 }{}%
229 \excludecomment{testing}

```

Env warpall Anything in the `warpall` environment will be generated for print or HTML outputs.

```
230 \includecomment{warpall}
```

Env **warpprint** Anything in the warpprint environment will be generated for print output only.

Env **warpHTML** For HTML output:

```
231 \ifbool{warpingHTML}{%
232 \includecomment{warpHTML}%
233 }%
234 {\excludecomment{warpHTML}}%
```



```
235 \ifbool{warpingprint}%
236 {\includecomment{warpprint}}%
237 {\excludecomment{warpprint}}
```

Optionally generate a local copy of **lwarpmk**. Default to no.

```
238 \ifbool{LWR@creatinglwarpmk}{%
239 {\includecomment{LWR@createlwarpmk}}%
240 {\excludecomment{LWR@createlwarpmk}}}
```

26 Package load order

Several packages should only be loaded before **l warp**, and most others should only be loaded after.

Packages which should only be loaded before **l warp** have their own

```
l warp-<packagename>.sty
```

which use `\LWR@loadbefore` to trigger an error if they are loaded after **l warp**. Examples include **fontspec**, **inputenc**, **inputenx**, **fontenc**, and **newunicodechar**.

Most packages should be loaded after **l warp**. This is enforced by a large number of `\LWR@loadafter` statements, below.

Some packages are emulated by **memoir**, and so these are tested by `\LWR@notmemoirloadafter`, which does not cause an error if **memoir** is used.

26.1 Tests of package load order

```
\LWR@loadafter {<packagename>} Error if this package was loaded before l warp.
```

```

241 \newcommand*{\LWR@loadafter}[1]{%
242 \@ifpackageloaded{#1}%
243 {%
244 \PackageError{lwarf}%
245 {Package #1, or one which uses #1, must be loaded after lwarf}%
246 {Move \detokenize{\usepackage}{#1} after \detokenize{\usepackage}{lwarf}.}%
247 Package #1 may also be loaded by something else, which must also be moved%
248 after lwarf.}%
249 }%
250 {}%
251 }

```

\LWR@notmemoirloadafter {\<packagename>} Error if not **memoir** class and this package was loaded before **lwarf**.

memoir emulates many packages, and pretends that they have already been loaded.

```

252 \@ifclassloaded{memoir}%
253 {\newcommand*{\LWR@notmemoirloadafter}[1]{}}
254 {\LetLtxMacro{\LWR@notmemoirloadafter}{\LWR@loadafter}}

```

\LWR@loadbefore {\<packagename>} Error if this package is after **lwarf**.

```

255 \newcommand*{\LWR@loadbefore}[1]{%
256 \@ifpackageloaded{#1}%
257 {}%
258 {%
259 \PackageError{lwarf}%
260 {Package #1 must be loaded before lwarf}%
261 {Move \detokenize{\usepackage}{#1} before \detokenize{\usepackage}{lwarf}.}%
262 }%
263 }

```

\LWR@loadnever {\<badpackagename>} {\<replacementpkgnname>}

The first packages is not supported, so tell the user to use the second instead.

```

264 \newcommand*{\LWR@loadnever}[2]{%
265 \PackageError{lwarf}%
266 {Package #1 is not supported by lwarf's HTML conversion.}%
267 {Package(s) #2 may be useful instead}%
268 {Package #1 might conflict with lwarf in some way,}%
269 {or is superceded by another package.}%
270 {For a possible alternative, see package(s) #2.}%
271 }

```

\LWR@earlyloadnever {\<badpackagename>} {\<replacementpkgnname>}

The first packages is not supported, so tell the user to use the second instead. This version checks immediately for packages which may have been loaded before **lwarf**.

```

272 \newcommand*{\LWR@earlyloadnever}[2]{%
273 \@ifpackageloaded{#1}{%
274 \PackageError{lwarf}%
275 {Package #1 is not supported by lwarf's HTML conversion.}%
276 {Package(s) #2 may be useful instead}%
277 {Package #1 might conflict with lwarf in some way,}%
278 {or is superceded by another package.}%
279 {For a possible alternative, see package(s) #2.}%
280 }{}%
281 }
```

26.2 Error for disallowed packages loaded before lwarf

```

282 \LWR@earlyloadnever{ae}{cm-super, lmodern}%
283 \LWR@earlyloadnever{aecmpl}{cm-super, lmodern}%
284 \LWR@earlyloadnever{aecc}{cm-super, lmodern}%
285 \LWR@earlyloadnever{boxedminipage}{boxedminipage2e}%
286 \LWR@earlyloadnever{caption2}{caption}%
287 % \LWR@earlyloadnever{ccaption}{caption}% might be preloaded by memoir
288 \LWR@earlyloadnever{fancyheadings}{fancyhdr}%
289 \LWR@earlyloadnever{glossary}{glossaries}%
290 \LWR@earlyloadnever{t1enc}{fontenc, inputenc, inputenx}%
291 \LWR@earlyloadnever{wasysym}{textcomp, amssymb, amsfonts, mnsymbol, fdsymbol}
```

26.3 Enforcing package loading after lwarf

Packages which should only be loaded after **lwarf** are tested here to trip an error if they have already been loaded.

The following packages must be loaded after **lwarf**:

```

292 \LWR@loadafter{2up}%
293 \LWR@loadafter{a4}%
294 \LWR@loadafter{a4wide}%
295 \LWR@loadafter{a5comb}%
296 \LWR@notmemoirloadafter{abstract}%
297 \LWR@loadafter{accsupp}%
298 \LWR@loadafter{acro}%
299 \LWR@loadafter{acronym}%
300 \LWR@loadafter{adjmulticol}%
301 \LWR@loadafter{addlines}%
302 \LWR@loadafter{ae}%
303 \LWR@loadafter{aecc}
```

```
304 \LWR@loadafter{afterpage}
305 \LWR@loadafter{algorithm2e}
306 \LWR@loadafter{algorithmicx}
307 \LWR@loadafter{alltt}
308 \LWR@loadafter{amsmath}
309 \LWR@loadafter{amsthm}
310 \LWR@loadafter{anonchap}
311 \LWR@loadafter{any-size}
312 \LWR@notmemoirloadafter{appendix}
313 \LWR@loadafter{arabicfront}
314 \LWR@notmemoirloadafter{array}
315 \LWR@loadafter{arydshln}
316 \LWR@loadafter{asymptote}
317 % \LWR@loadafter{atbegshi} used by morewrites
318 \LWR@loadafter{attachfile}
319 \LWR@loadafter{attachfile2}
320 \LWR@loadafter{authblk}
321 \LWR@loadafter{axessibility}
322 \LWR@loadafter{axodraw2}
323 \LWR@loadafter{backref}
324 \LWR@loadafter{balance}
325 \LWR@loadafter{bigdelim}
326 \LWR@loadafter{bigstrut}
327 \LWR@loadafter{blowup}
328 \LWR@loadafter{booklet}
329 \LWR@loadafter{bookmark}
330 \LWR@notmemoirloadafter{booktabs}
331 \LWR@loadafter{bophook}
332 \LWR@loadafter{boxedminipage}
333 \LWR@loadafter{boxedminipage2e}
334 \LWR@loadafter{breakurl}
335 \LWR@loadafter{breqn}
336 \LWR@loadafter{bxpaper-size}
337 \LWR@loadafter{bytfield}
338 \LWR@loadafter{cancel}
339 \LWR@loadafter{canoniclayout}
340 \LWR@loadafter{caption}
341 \LWR@loadafter{caption2}
342 \LWR@loadafter{cases}
343 % \LWR@loadafter{ccaption} may be preloaded by memoir
344 \LWR@loadafter{changebar}
345 \LWR@notmemoirloadafter{changepage}
346 \LWR@notmemoirloadafter{chngpage}
347 \LWR@loadafter{chappg}
348 \LWR@loadafter{chapterbib}
349 \LWR@loadafter{chemfig}
350 \LWR@loadafter{chemformula}
351 \LWR@loadafter{chemgreek}
352 \LWR@loadafter{chemmacros}
353 \LWR@loadafter{chemnum}
```

```
354 \LWR@loadafter{chkfloat}
355 \LWR@loadafter{cite}
356 \LWR@loadafter{cmdtrack}
357 \LWR@loadafter{color}
358 \LWR@loadafter{colortbl}
359 \LWR@loadafter{continue}
360 \LWR@loadafter{copyrightbox}
361 \LWR@notmemoirloadafter{crop}
362 \LWR@loadafter{cuted}
363 \LWR@loadafter{cutwin}
364 \LWR@loadafter{dblfloatfix}
365 \LWR@loadafter{dblfnote}
366 \LWR@notmemoirloadafter{dcolumn}
367 \LWR@loadafter{diagbox}
368 \LWR@loadafter{dprogress}
369 \LWR@loadafter{draftcopy}
370 \LWR@loadafter{draftfigure}
371 \LWR@loadafter{draftwatermark}
372 \LWR@loadafter{easy-todo}
373 \LWR@loadafter{ebook}
374 \LWR@loadafter{ellipsis}
375 \LWR@loadafter{emptypage}
376 \LWR@loadafter{endfloat}
377 \LWR@loadafter{endheads}
378 \LWR@loadafter{endnotes}
379 \LWR@notmemoirloadafter{enumerate}
380 \LWR@loadafter{enumitem}
381 \LWR@notmemoirloadafter{epigraph}
382 \LWR@loadafter{epsfig}
383 \LWR@loadafter{epstopdf}
384 \LWR@loadafter{epstopdf-base}
385 \LWR@loadafter{errata}
386 \LWR@loadafter{eso-pic}
387 \LWR@loadafter{everypage}
388 \LWR@loadafter{everyshi}
389 \LWR@loadafter{extramarks}
390 \LWR@loadafter{fancybox}
391 \LWR@loadafter{fancyhdr}
392 \LWR@loadafter{fancyheadings}
393 \LWR@loadafter{fancyref}
394 \LWR@loadafter{fancytabs}
395 \LWR@loadafter{fancyvrb}
396 \LWR@loadafter{figcaps}
397 \LWR@loadafter{figsize}
398 \LWR@loadafter{fix2col}
399 \LWR@loadafter{fixme}
400 \LWR@loadafter{fixmetodonotes}
401 \LWR@loadafter{flafter}
402 \LWR@loadafter{float}
403 \LWR@loadafter{floatflt}
```

```
404 \LWR@loadafter{floatpag}
405 \LWR@loadafter{floatrow}
406 \LWR@loadafter{fltrace}
407 \LWR@loadafter{flushend}
408 \LWR@loadafter{fnbreak}
409 \LWR@loadafter{fncychap}
410 \LWR@loadafter{fnlineno}
411 \LWR@loadafter{fnpos}
412 % fontenc must be loaded before l warp
413 % fontspec must be loaded before l warp
414 \LWR@loadafter{footmisc}
415 \LWR@loadafter{footnote}
416 \LWR@loadafter{footnotehyper}
417 \LWR@loadafter{footnpag}
418 \LWR@loadafter{forest}
419 \LWR@loadafter{framed}
420 \LWR@loadafter{ftnright}
421 \LWR@loadafter{fullminipage}
422 \LWR@loadafter{fullpage}
423 \LWR@loadafter{fullwidth}
424 \LWR@loadafter{fwlw}
425 \LWR@loadafter{geometry}
426 \LWR@loadafter{glossaries}
427 % \LWR@loadafter{graphics} % pre-loaded by xunicode
428 % \LWR@loadafter{graphicx} % pre-loaded by xunicode
429 \LWR@loadafter{glossary}
430 \LWR@loadafter{grffile}
431 \LWR@loadafter{grid}
432 \LWR@loadafter{grid-system}
433 \LWR@loadafter{gridset}
434 \LWR@loadafter{hang}
435 \LWR@loadafter{hanging}
436 \LWR@loadafter{hypcap}
437 \LWR@loadafter{hypdestopt}
438 \LWR@loadafter{hypernat}
439 \LWR@loadafter{hyperref}
440 \LWR@loadafter{hyperxmp}
441 \LWR@loadafter{hyphenat}
442 \LWR@loadafter{idxlayout}
443 \LWR@loadafter{ifoddpage}
444 \LWR@loadafter{imakeidx}
445 \LWR@loadafter{indentfirst}
446 \LWR@notmemoirloadafter{index}
447 % inputenc must be loaded before l warp
448 % inputenx must be loaded before l warp
449 \LWR@loadafter{intopdf}
450 \LWR@loadafter{keyfloat}
451 \LWR@loadafter{layaureo}
452 \LWR@loadafter{layout}
453 \LWR@loadafter{leading}
```

```
454 \LWR@loadafterspace{letterspace}
455 \LWR@loadafterspace{lettrine}
456 \LWR@loadafterspace{lineno}
457 \LWR@loadafterspace{lips}
458 \LWR@loadafterspace{listings}
459 \LWR@loadafterspace{longtable}
460 \LWR@loadafterspace{lscape}
461 \LWR@loadafterspace{ltablex}
462 \LWR@loadafterspace{ltcaption}
463 \LWR@loadafterspace{ltxgrid}
464 \LWR@loadafterspace{ltxtable}
465 \LWR@loadafterspace{lua-check-hyphen}
466 \LWR@loadafterspace{lua-visual-debug}
467 \LWR@loadafterspace{luacolor}
468 \LWR@loadafterspace{luatodonotes}
469 \LWR@loadafterspace{magaz}
470 \LWR@notmemoirloadafterspace{makeidx}
471 \LWR@loadafterspace{marginfit}
472 \LWR@loadafterspace{marginfix}
473 \LWR@loadafterspace{marginnote}
474 \LWR@loadafterspace{mcaption}
475 \LWR@loadafterspace{mdframed}
476 \LWR@loadafterspace{memhfixc}
477 \LWR@loadafterspace{metalogo}
478 \LWR@loadafterspace{mhchem}
479 \LWR@loadafterspace{microtype}
480 \LWR@loadafterspace{midfloat}
481 \LWR@loadafterspace{midpage}
482 \LWR@loadafterspace{morefloats}
483 \LWR@notmemoirloadafterspace{moreverb}
484 % morewrites must be loaded before l warp
485 \LWR@notmemoirloadafterspace{mparhack}
486 %\LWR@loadafterspace{multicol} loaded by ltxdoc
487 \LWR@loadafterspace{multirow}
488 \LWR@loadafterspace{multitoc}
489 \LWR@loadafterspace{nameref}
490 \LWR@loadafterspace{natbib}
491 \LWR@notmemoirloadafterspace{nccfancyhdr}
492 \LWR@notmemoirloadafterspace{needspace}
493 % newclude must be loaded before l warp
494 \LWR@loadafterspace{newtxmath}
495 % newunicodechar must be loaded before l warp
496 \LWR@notmemoirloadafterspace{nextpage}
497 \LWR@loadafterspace{nicefrac}
498 \LWR@loadafterspace{nonfloat}
499 \LWR@loadafterspace{nonumonpart}
500 \LWR@loadafterspace{nopageno}
501 \LWR@loadafterspace{nowidow}
502 \LWR@loadafterspace{ntheorem}
503 \LWR@loadafterspace{overpic}
```

```
504 \LWR@loadafter{pagegrid}
505 \LWR@notmemoirloadafter{pagenote}
506 \LWR@loadafter{pagesel}
507 \LWR@loadafter{paralist}
508 \LWR@loadafter{parnotes}
509 \LWR@notmemoirloadafter{parskip}
510 \LWR@loadafter{pbox}
511 \LWR@loadafter{pdfrender}
512 \LWR@loadafter{pdflandscape}
513 \LWR@loadafter{pdfpages}
514 \LWR@loadafter{pdfprivacy}
515 \LWR@loadafter{pdfsync}
516 \LWR@loadafter{pdftricks}
517 \LWR@loadafter{pdfx}
518 \LWR@loadafter{pfnote}
519 \LWR@loadafter{phfqt}
520 \LWR@loadafter{placeins}
521 \LWR@loadafter{prelim2e}
522 \LWR@loadafter{prettyref}
523 \LWR@loadafter{preview}
524 \LWR@loadafter{psfrag}
525 \LWR@loadafter{psfragx}
526 \LWR@loadafter{pst-eps}
527 \LWR@loadafter{pstool}
528 \LWR@loadafter{pstricks}
529 \LWR@loadafter{quotchap}
530 \LWR@loadafter{quoting}
531 \LWR@loadafter{ragged2e}
532 \LWR@loadafter{realscripts}
533 \LWR@loadafter{refcheck}
534 \LWR@loadafter{register}
535 \LWR@loadafter{relsize}
536 \LWR@loadafter{repeatindex}
537 \LWR@loadafter{resizegather}
538 \LWR@loadafter{romanbar}
539 \LWR@loadafter{romanbarpagename}
540 \LWR@loadafter{rotating}
541 \LWR@loadafter{rotfloat}
542 \LWR@loadafter{savetrees}
543 % \LWR@loadafter{scalefnt} loaded by babel-french
544 \LWR@loadafter{schemata}
545 \LWR@loadafter{scrextrnd}
546 \LWR@loadafter{scrhack}
547 \LWR@loadafter{scrlayer}
548 \LWR@loadafter{scrlayer-notecolumn}
549 \LWR@loadafter{scrlayer-scrpage}
550 \LWR@loadafter{section}
551 \LWR@loadafter{sectionbreak}
552 \LWR@loadafter{sectsty}
553 \LWR@notmemoirloadafter{setspace}
```

```
554 \LWR@loadaft{shadow}
555 \LWR@notmemoirloadaft{showidx}
556 \LWR@loadaft{showkeys}
557 \LWR@loadaft{sidecap}
558 \LWR@loadaft{ sidenotes}
559 \LWR@loadaft{SIunits}
560 \LWR@loadaft{siunitx}
561 \LWR@loadaft{soul}
562 \LWR@loadaft{soulpos}
563 \LWR@loadaft{soulutf8}
564 \LWR@loadaft{splitidx}
565 \LWR@loadaft{srcctx}
566 \LWR@loadaft{srctex}
567 \LWR@loadaft{stabular}
568 \LWR@loadaft{stfloats}
569 \LWR@loadaft{subfig}
570 \LWR@loadaft{subfigure}
571 \LWR@loadaft{supertabular}
572 \LWR@loadaft{t1inc}
573 \LWR@loadaft{tbls}
574 \LWR@notmemoirloadaft{tabularx}
575 \LWR@loadaft{tabulary}
576 \LWR@loadaft{textarea}
577 % \LWR@loadaft{textcomp} % maybe before l warp with font packages
578 \LWR@loadaft{textfit}
579 \LWR@loadaft{textpos}
580 \LWR@loadaft{theorem}
581 \LWR@loadaft{thinsp}
582 \LWR@loadaft{threadcol}
583 \LWR@loadaft{threeparttable}
584 \LWR@loadaft{thumb}
585 \LWR@loadaft{thumbs}
586 \LWR@loadaft{tikz}
587 \LWR@loadaft{titleps}
588 \LWR@loadaft{titlesec}
589 \LWR@loadaft{titletoc}
590 \LWR@notmemoirloadaft{titling}
591 % \LWR@loadaft{tocbasic} % preloaded by koma-script classes
592 \LWR@notmemoirloadaft{tocbibind}
593 \LWR@loadaft{toccenter}
594 \LWR@notmemoirloadaft{tocloft}
595 \LWR@loadaft{tocstyle}
596 \LWR@loadaft{todo}
597 \LWR@loadaft{todonotes}
598 \LWR@loadaft{transparent}
599 \LWR@loadaft{trimclip}
600 \LWR@loadaft{trivfloat}
601 \LWR@loadaft{turnthepage}
```

```

602 % \LWR@loadaft{typearea}%
603 \LWR@loadaft{ulem}
604 \LWR@loadaft{underscore}
605 \LWR@loadaft{units}
606 \LWR@loadaft{upref}
607 \LWR@loadaft{url}
608 \LWR@loadaft{uspace}
609 \LWR@loadaft{varioref}%
610 \LWR@notmemoirloadaft{verse}
611 \LWR@loadaft{verbars}
612 \LWR@loadaft{vmargin}
613 \LWR@loadaft{vowel}
614 \LWR@loadaft{vpe}
615 \LWR@loadaft{vwcol}
616 \LWR@loadaft{wallpaper}
617 \LWR@loadaft{wasysym}
618 \LWR@loadaft{watermark}
619 \LWR@loadaft{widows-and-orphans}
620 \LWR@loadaft{wrapfig}
621 \LWR@loadaft{xbmks}
622 \LWR@loadaft{xcolor}
623 \LWR@loadaft{xellipsis}
624 \LWR@loadaft{xfrac}
625 \LWR@loadaft{xltabular}
626 \LWR@loadaft{xltextra}
627 \LWR@loadaft{xmpincl}
628 \LWR@loadaft{xpiano}
629 \LWR@loadaft{xtab}
630 % xunicode must be loaded before lwarf
631 \LWR@loadaft{xurl}
632 \LWR@loadaft{xy}
633 \LWR@loadaft{zwpagelayout}

```

27 Required packages

These packages are automatically loaded by **lwarf** when generating HTML output. Some of them are also automatically loaded when generating print output, but some are not.

for HTML output: 634 \begin{warpHTML}

Load **fontspec** if necessary:

```

635 \ifxetexorluatex
636 \@ifpackageloaded{fontspec}{}{
637 \usepackage[no-math]{fontspec}

```

```
638 }
```

The monospaced font is used for HTML tags, so turn off its TeX ligatures and common ligatures:

```
639 \defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
640 \defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
641 \defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
642 \else
```

pdflatex only: Only pre-loaded if **pdflatex** is being used.

Pkg **microtype**

ligatures Older browsers don't display ligatures. Turn off letter ligatures, keeping L^ET_X dash and quote ligatures, which may fail on older browsers but at least won't corrupt written words.

```
643 \RequirePackage{microtype}
644
645 \microtypesetup{
646   protrusion=false,
647   expansion=false,
648   tracking=false,
649   kerning=false,
650   spacing=false}
651
652 \DisableLigatures[f,q,t,T,Q]{encoding = *,family = *}

653 \fi

654 \end{warpHTML}
```

Pkg **geometry** Tactics to avoid unwanted page breaks and margin overflow:

- Uses a very long and wide page to minimize page breaks and margin overflow.
- Uses a scriptsize font.
- Uses extra space at the margin to avoid HTML tag overflow off the page.
- Forces a new PDF page before some environments.
- Forces line break between major pieces of long tags.

for HTML output: 655 \begin{warpHTML}
656 \RequirePackage[paperheight=190in,paperwidth=20in,%
657 left=2in,right=6in,%

```
658 top=1in,bottom=1in,%
659 ]{geometry}
660 \twosidefalse
661 \mparswitchfalse
662 \end{warpHTML}
```

for HTML & PRINT: 663 \begin{warpall}

Pkg xparse

TeX3 command argument parsing

```
664 \RequirePackage{xparse}
```

```
665 \end{warpall}
```

for HTML output: 666 \begin{warpHTML}

Pkg expl3

TeX3 programming

```
667 \RequirePackage{expl3}
```

Pkg gettitlestring

Used to emulate \nameref.

```
668 \RequirePackage{gettitlestring}
```

Pkg everyhook

everyhook is used to patch paragraph handling.

```
669 \RequirePackage{everyhook}
670 \end{warpHTML}
```

for HTML & PRINT: 671 \begin{warpall}

Pkg filecontents

Used to write helper files, done in print mode.

Patched to work with **morewrites**, per <https://tex.stackexchange.com/questions/312830/does-morewrites-not-support-filecontents-and-can-i-write-body-of-environment-us/312910>

```
672 \RequirePackage{filecontents}
673
674 \@ifpackagelater{filecontents}{2011/10/09}%
675 {}
676 {
677 \newwrite\fcwrite
678 \let\LWR@origfilec@ntents\filec@ntents
679 \def\filec@ntents{\def\chardef##1\write{\let\reserved@c\fcwrite}\LWR@origfilec@ntents}
680 }
```

```
681 \end{warpall}
```

for HTML output: 682 \begin{warpHTML}

Pkg xifthen

```
683 \RequirePackage{xifthen}
```

Pkg verbatim

```
684 \RequirePackage{verbatim}
```

Pkg calc

```
685 \RequirePackage{calc}
```

Pkg refcount

Provides \setcounterref, \setcounterpageref, etc.

```
686 \RequirePackage{refcount}
```

Pkg newfloat

```
687 \RequirePackage{newfloat}
```

```
688 \end{warpHTML}
```

for HTML & PRINT: 689 \begin{warpall}

Pkg xstring

```
690 \RequirePackage{xstring}
```

Pkg environ Used to encapsulate math environments for re-use in HTML <alt> text.

```
691 \RequirePackage{environ}
```

```
692 \end{warpall}
```

for HTML output: 693 \begin{warpHTML}

Pkg zref Used for cross-references.

```
694 \RequirePackage{zref}
```

Pkg printlen Used to convert lengths for image width/height options.

```
695 \RequirePackage{printlen}
```

\LWR@printlength {\langle length\rangle}

Prints a length using a locally-controlled unit and space. Rounding is used unless the length is small.

```
696 \newrobustcmd*\LWR@printlength[1]{%
697 \begingroup%
698 \uselengthunit{PT}%
699 \renewcommand*\unitspace{}%
700 \ifdimless{#1}{10pt}{%
701   \printlength{#1}%
702 }{%
703   \rndprintlength{#1}%
704 }%
705 \endgroup%
706 }
```

```
707 \end{warpHTML}
```

for PRINT output: 708 \begin{warpprint}

Pkg varwidth Used for print-mode lateximage:

```
709 \RequirePackage{varwidth}
```

```
710 \end{warpprint}
```

28 Loading packages

for HTML output: 711 \begin{warpHTML}

Remember the original \RequirePackage:

```
712 \LetLtxMacro{\LWR@origRequirePackage}{\RequirePackage}
```

\LWR@requirepackagenames Stores the list of required package names.

```
713 \newcommand*{\LWR@requirepackagenames}{}{}
```

\LWR@parsedrequirepackagenames Stores the parsed list of required package names after spaces are removed and l warp- is prepended.

```
714 \newcommand*{\LWR@parsedrequirepackagenames}{}{}
```

\LWR@findword [*1: separator*] {*2: list*} {*3: index*} [*4: destination*]

Note that argument 4 is passed directly to \StrBetween.

```
715 \newcommand*{\LWR@findword}[3][,]{%
716     \StrBetween[#3,\numexpr#3+1]{#1#2#1}{#1}{#1}%
717 }
```

\LWR@lookforpackagename {*index*}

If this is an l warp-supported package name, re-direct it to the l warp version by renaming it l warp- followed by the original name.

Looks index deep into the list of package names, \LWR@requirepackagenames, and builds \LWR@parsedrequirepackagenames which is the modified list of names.

```
718 \newcommand*{\LWR@lookforpackagename}[1]{%
```

Find the *index*'th package name from the list:

```
719 \LWR@findword{\LWR@requirepackagenames}{#1}[\LWR@strresult]%
```

Remove blanks. The original name with blanks is in LWR@strresult and the final name with no blanks goes into LWR@strresulttwo.

```
720 \StrSubstitute[100]{\LWR@strresult}{ }{}[\LWR@strresulttwo]%
```

See if the package name was found:

```
721 \IfStrEq{\LWR@strresulttwo}{}{%
722 }% no filename
723 }% yes filename
```

If found, and if an **l warp**-equivalent name exists, use **l warp-*** instead.

```

725   \IfFileExists{l warp-\LWR@strresulttwo.sty}%
726   {%
727     \ifdefvoid{\LWR@parsedrequirepackagenames}{%
728       \edef\LWR@parsedrequirepackagenames{l warp-\LWR@strresulttwo}%
729     }{%
730       \edef\LWR@parsedrequirepackagenames{%
731         \LWR@parsedrequirepackagenames,l warp-\LWR@strresulttwo}%
732     }{%
733   }{%
734 }{%
735 }{%
736   \ifdefvoid{\LWR@parsedrequirepackagenames}{%
737     \edef\LWR@parsedrequirepackagenames{\LWR@strresulttwo}%
738   }{%
739     \edef\LWR@parsedrequirepackagenames{%
740       \LWR@parsedrequirepackagenames,\LWR@strresulttwo}%
741   }{%
742 }{%
743 }% no l warp-* file
744 }% yes filename
745 }

```

\RequirePackage [⟨1: options⟩] {⟨2: package names⟩} [⟨3: version⟩]

For each of many package names in a comma-separated list, if an **l warp** version of a package exists, select it instead of the **L_ET_X** version.

```
746 \RenewDocumentCommand{\RequirePackage}{o m o}{%
```

Redirect up to twenty names:¹⁶

```

747 \renewcommand*{\LWR@requirepackagenames}{#2}%
748 \renewcommand*{\LWR@parsedrequirepackagenames}{}%
749 \LWR@lookforpackagename{1}%
750 \LWR@lookforpackagename{2}%
751 \LWR@lookforpackagename{3}%
752 \LWR@lookforpackagename{4}%
753 \LWR@lookforpackagename{5}%
754 \LWR@lookforpackagename{6}%
755 \LWR@lookforpackagename{7}%
756 \LWR@lookforpackagename{8}%
757 \LWR@lookforpackagename{9}%
758 \LWR@lookforpackagename{10}%

```

¹⁶This was originally nine names, but then I came across a package which used twelve...

```

759 \LWR@lookforpackagename{11}%
760 \LWR@lookforpackagename{12}%
761 \LWR@lookforpackagename{13}%
762 \LWR@lookforpackagename{14}%
763 \LWR@lookforpackagename{15}%
764 \LWR@lookforpackagename{16}%
765 \LWR@lookforpackagename{17}%
766 \LWR@lookforpackagename{18}%
767 \LWR@lookforpackagename{19}%
768 \LWR@lookforpackagename{20}%

```

\RequirePackage depending on the options and version:

```

769 \IfValueTF{#1}%
770 {%
771   \IfValueTF{#3}%
772   {%
773     {\LWR@origRequirePackage[#1]{\LWR@parsedrequirepackagenames}{#3}}%
774   }%
775 }%
776 \IfValueTF{#3}%
777 {%
778   {\LWR@origRequirePackage{\LWR@parsedrequirepackagenames}{#3}}%
779 }%
780 }%
781 \LetLtxMacro\usepackage\RequirePackage

```

\LWR@ProvidesPackagePass {*pkgnname*} [*version*]

Uses the original package, including options.

```

782 \NewDocumentCommand{\LWR@ProvidesPackagePass}{m o}{%
783   \PackageInfo{lwarf}{Using package '#1' and adding lwarf modifications, including options,}%
784 \IfValueTF{#2}%
785 {%
786   \ProvidesPackage{lwerp-#1}{#2}%
787   \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{#1}}%
788   \ProcessOptions\relax
789 }%
790 \IfValueTF{#2}%
791 {%
792   \LWR@origRequirePackage{#1}{#2}%
793   \LWR@origRequirePackage{#1}%
794 }

```

\LWR@ProvidesPackageDrop {*pkgnname*} [*version*]

Ignores the original package and uses lwarf's version instead. Drops/discards all options.

```

793 \NewDocumentCommand{\LWR@ProvidesPackageDrop}{m o}{
794   \PackageInfo{lwarf}{Replacing package '#1' with the lwarf version, discarding options,}%
795   \IfValueTF{#2}
796   {\ProvidesPackage{lwarf-#1}[#2]}
797   {\ProvidesPackage{lwarf-#1}}

```

Ignore all options.

```
798 \DeclareOption*{}
```

Nullifies then processes the options. Seems to be required when options contain curly braces, which were causing “Missing `\begin{document}`”.

```

799 % \ProcessOptions\relax% original LaTeX code
800 \let\ds@\emptyset% from the original \ProcessOptions
801 \edef\@curroptions{}% lwarf modification to \ProcessOptions
802 \processoptions\relax% from the original \ProcessOptions
803 }

804 \end{warpHTML}

```

29 Additional required packages

for HTML output: 805 `\begin{warpHTML}`

Pkg caption

```

806 \RequirePackage{caption}%

807 \end{warpHTML}

```

30 File handles

Defines file handles for writes.

for HTML & PRINT: 808 `\begin{warpall}`

`\LWR@quickfile` For quick temporary use only. This is reused in several places.

```
809 \newwrite\LWR@quickfile%
```

```

810 \end{warpall}

for HTML output: 811 \begin{warpHTML}

\LWR@lateximagesfile For lateximages.txt.

812 \newwrite\LWR@lateximagesfile

813 \end{warpHTML}

```

31 Include a file

During HTML output, `\include{<filename>}` causes the following to occur:

1. `lwarp` creates `<filename>_html_inc.tex` whose contents are:
`\input <filename>.tex`
2. `<filename>_html_inc.tex` is then `\included` instead of `<filename>.tex`.
3. `<filename>_html_inc.aux` is automatically generated and used by L^AT_EX.

```

for HTML output: 814 \begin{warpHTML}

\include {<filename>}

\@include {<filename>} Modified to load _html_inc files.

815 \def\@include#1 {%
816   \immediate\openout\LWR@quickfile #1_html_inc.tex% lwarp
817   \immediate\write\LWR@quickfile{\string\input{#1.tex}}% lwarp
818   \immediate\closeout\LWR@quickfile% lwarp
819   \LWR@origclearpage% \changed
820   \if@files
821     \immediate\write\@mainaux{\string\@input{#1_html_inc.aux}}% changed
822   \fi
823   \tempswattrue
824   \if@partsw
825     \tempswafalse
826     \edef\reserved@b{#1}%
827     \@for\reserved@a:=\@partlist\do
828       {\ifx\reserved@a\reserved@b\@tempswattrue\fi}%
829 \fi

```

```

830 \if@tempswa
831   \let\@auxout\@partaux
832   \if@filesw
833     \immediate\openout\@partaux #1_html_inc.aux % changed
834     \immediate\write\@partaux{\relax}%
835   \fi
836   \@input{\#1_html_inc.tex}% changed
837   \LWR@origclearpage% changed
838   \@writeckpt{\#1}%
839   \if@filesw
840     \immediate\closeout\@partaux
841   \fi
842 \else
843   \deadcycles\z@
844   \nameuse{cp@\#1}%
845 \fi
846 \let\@auxout\@mainaux%
847 }

848 \end{warpHTML}

```

32 Copying a file

for HTML output: 849 \begin{warpHTML}

\LWR@copyfile {*source filename*} {*destination filename*}

Used to copy the .toc file to .sidetoc to re-print the toc in the sidetoc navigation pane.

```

850 \newwrite\LWR@copyoutfile % open the file to write to
851 \newread\LWR@copyinfile % open the file to read from
852
853 \newcommand*\LWR@copyfile[2]{%
854 \LWR@traceinfo{\LWR@copyfile: copying #1 to #2}
855
856 \immediate\openout\LWR@copyoutfile=#2
857 \openin\LWR@copyinfile=#1
858 \begingroup\endlinechar=-1
859 \makeatletter
860
861 \LWR@traceinfo{\LWR@copyfile: about to loop}
862
863 \loop\unless\ifeof\LWR@copyinfile
864   \LWR@traceinfo{\LWR@copyfile: one line}
865   \read\LWR@copyinfile to\LWR@fileline % Read one line and store it into \LWR@fileline

```

```

866 \% \LWR@fileline\par % print the content into the pdf
867 \% print the content:
868 \immediate\write\LWR@copyoutfile{\unexpanded\expandafter{\LWR@fileline}}%
869 \repeat
870 \immediate\closeout\LWR@copyoutfile
871 \LWR@traceinfo{LWR@copyfile: done}
872 \endgroup
873 }

874 \end{warpHTML}

```

33 Debugging messages

HTML comments To have the HTML output include additional HTML comments, such as which `<div>` is closing, use

```
\booltrue{HTMLDebugComments}
```

debugging information To have debug information written to the log, use

```
\tracingl warp
```

for HTML & PRINT: 875 \begin{warpall}

Bool LWR@tracingl warp True if tracing is turned on.

```
876 \newbool{LWR@tracingl warp}
```

`\tracingl warp` Turns on the debug tracing messages.

```
877 \newcommand{\tracingl warp}{\booltrue{LWR@tracingl warp}}
```

`\LWR@traceinfo {<text>}` If tracing is turned on, writes the text to the .log file.

```

878 \newcommand{\LWR@traceinfo}[1]{%
879 \ifbool{LWR@tracingl warp}{%
880 {%
881     \typeout{*** lwarp: #1}%
882 }{%
883 {}{%
884 }

```

Bool HTMLDebugComments Add comments in HTML about closing `<div>`s, sections, etc.

Default: `false`

```
885 \newbool{HTMLDebugComments}
886 \boolfalse{HTMLDebugComments}
```

If `\tracingl warp`, show where preamble hooks occur:

```
887 \AfterEndPreamble{
888 \LWR@traceinfo{AfterEndPreamble}
889 }
890
891 \AtBeginDocument{
892 \LWR@traceinfo{AtBeginDocument}
893 }

894 \end{warpall}
```

34 Defining print and HTML versions of macros and environments

The following refers to defining objects inside `l warp`, and is not for the user's document.

Many macros and environments must be provided as both print and HTML versions.

While generating the print version of a document, the original macros as defined by L^AT_EX and its packages are used as-is.

While generating the HTML version of a document, the original macro or environment is redefined to call a new HTML version or a copy of the original print version. The new HTML versions of macros and environments are used most of the time. Copies of the print versions are used inside a `lateximage` environment, which draws and remembers an image of the printed output, and also several other places. The copies of the print versions may also be used by the HTML versions, such as when the HTML version merely encloses the print version inside HTML tags.

The general structure for providing print and HTML versions of a macro or environment is as follows:

For a preexisting macro, not defined with `xparse`: An HTML version is provided with a special name, inside a `warpHTML` environment, then `\LWR@formatted` is used to redefine and patch various macros:

```
\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...}%
may also use xparse
```

```
\LWR@formatted{name}
\end{warpHTML}
```

`\LWR@formatted{name}` copies the original print version, then redefines `\name` to use either the print or HTML version depending on which mode `l warp` is using. `xparse` may be used to define the new HTML version, even if the original did not use `xparse`.

For a preexisting environment, not defined with `xparse`: The process is similar. Note the use of `\LWR@formattedenv` instead of `\LWR@formatted`.

```
\begin{warpHTML}
\newenvironment{\LWR@HTML@name}{...}{...} % may also use xparse

\LWR@formattedenv{name}
\end{warpHTML}
```

If the original used `xparse`: A copy must be made using a new name:

```
\begin{warpHTML}
\NewDocumentCommand{\LWR@print@name}{...}{...} % copy the original

\NewDocumentCommand{\LWR@HTML@name}{...}{...} % or use \newcommand

\LWR@formatted{name}
\end{warpHTML}
```

Similar for an environment, using `\LWR@formattedenv`. (`\LWR@formatted` and `\LWR@formattedenv` use `\LetLtxMacro` to copy the original print definition, which may not work with macros and environments created by `xparse`, so the print version must be manually recreated in the `l warp` source.)

For a new macro or environment, not using `xparse` for the print version:

```
\begin{warpall}
\newcommand{\name}{...} % NOT xparse!
\end{warpall}

\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...} % may use xparse for HTML

\LWR@formatted{name}
\end{warpHTML}
```

Similar for an environment. The plain `\name` or environment `name` is used for the printed version, and is placed inside `warpall`. `xparse` may be used for the `\LWR@HTML@<name>` version.

For a new macro or environment, using `xparse`: It is possible to use `xparse` for an entirely new macro or environment by defining the `\LWR@print@<name>` version with `xparse`, along with `\name` defined without `xparse` to refer directly to the `\LWR@print` version:

```
\begin{warpall}
\NewDocumentCommand{\LWR@print@name}{...} {...}%
\NewDocumentEnvironment{\LWR@print@name}{...} {...} { ... }

% Simply a call to \LWR@print@name:
\newcommand{\name}{\LWR@print@name}%
\newenvironment{name}{\LWR@print@name}{\end\LWR@print@name}
\end{warpall}

\begin{warpHTML}
\NewDocumentCommand{\LWR@HTML@name}{...} {...}%
\NewDocumentEnvironment{\LWR@HTML@name}{...} {...} { ... }

\LWR@formatted{name}%
\LWR@formattedenv{name}
\end{warpHTML}
```

In general, `\LWR@formatted` or `\LWR@formattedenv` are placed inside a `warpHTML` environment, and while producing an HTML document they do the following:

- Macros are modified:
 1. The pre-existing print version `\name` is saved as `\LWR@print@<name>`, unless `\LWR@print@<name>` is already defined.
 2. The original `\name` is redefined to call either the print or HTML version depending on which format is in use at the moment, as set by `\LWR@formatting`, which is defined as either “print” or “HTML”.
- When `lwarf` is producing a print document, the original definitions are used, as well as any new definitions defined in `warpall` above.
- When `lwarf` is generating HTML output, `\LWR@formatting` is set to “HTML”, and `\name` is directed to `\LWR@HTML@<name>`.
- When `lwarf` is generating HTML output but enters a `lateximage` environment, or for some other reason needs to draw images using the original print definitions, `\LWR@formatting` is changed to “print” and `\name` is then redirected to `\LWR@print@<name>`, which was the original `\name`.

Since arguments are not handled by the new \name, any star and other arguments are processed by the print or HTML version.

Expandable versions are also provided as well. These usually are necessary for anything which could appear inside a tabular, without which a “Misplaced \omit” error may occur.

```
\LWR@expandableformatted
\LWR@expandableformattedenv
```

(Older versions of l warp used \LetLtxMacro for everything, but this could fail when using macros defined by xparse. This older system is still in use for many definitions.)

for HTML output: 895 \begin{warpHTML}

\LWR@formatting Remembers if selected print/HTML formatting.

Used while \LWR@restoreorigformatting, such as in an lateximage. May be set to either “print” or “HTML”.

```
896 \newcommand*{\LWR@formatting}{HTML}
```

\LWR@formatted {\(macroname)} No backslash in the macro name.

If not yet defined, defines \LWR@print@<name> as the original print-mode \<name>. Also redefines \<name> to use \LWR@<format>@<name>, where <format> is set by \LWR@formatting, and is print or HTML.

```
897 \newcommand*{\LWR@formatted}[1]{%
898     \ifcsundef{\LWR@print@#1}{%
899         \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
900             \csname#1\endcsname%
901     }{%
902     \ifcsundef{#1}{%
903         \expandafter\newrobustcmd\csname #1\endcsname{%
904             \nameuse{\LWR@LWR@formatting @#1}%
905         }%
906     }{%
907         \expandafter\renewrobustcmd\csname #1\endcsname{%
908             \nameuse{\LWR@LWR@formatting @#1}%
909         }%
910     }%
911 }
```

\LWR@expandableformatted {\(macroname)} No backslash in the macro name.

An expandable version of \LWR@formatted.

```

912 \newcommand*{\LWR@expandableformatted}[1]{%
913     \ifcsundef{\LWR@print@#1}{%
914         \expandafter\LetLtxMacro\csname \LWR@print@#1\expandafter\endcsname%
915         \csname#1\endcsname%
916     }{%
917     \ifcsundef{#1}{%
918         \expandafter\newcommand\csname #1\endcsname{%
919             \nameuse{\LWR@\LWR@formatting @#1}%
920         }%
921     }{%
922         \expandafter\renewcommand\csname #1\endcsname{%
923             \nameuse{\LWR@\LWR@formatting @#1}%
924         }%
925     }%
926 }

```

\LWR@formattedenv {*environmentname*}

If not yet defined, defines the environment `\LWR@print@<name>` as the original print-mode `<name>`. Also redefines the environment `<name>` to use environment `\LWR@<format>@<name>`, where `<format>` is set by `\LWR@formatting`, and is print or HTML.

```

927 \newcommand*{\LWR@formattedenv}[1]{%
928     \ifcsundef{\LWR@print@#1}{%
929         \expandafter\LetLtxMacro\csname \LWR@print@#1\expandafter\endcsname%
930         \csname#1\endcsname%
931         \csletcs{endLWR@print@#1}{end#1}%
932     }{%
933     \DeclareDocumentEnvironment{#1}{}{%
934         {\nameuse{\LWR@\LWR@formatting @#1}}%
935         {\nameuse{endLWR@\LWR@formatting @#1}}%
936     }

```

\LWR@expandableformattedenv {*environmentname*}

An expandable version of `\LWR@formattedenv`.

```

937 \newcommand*{\LWR@expandableformattedenv}[1]{%
938     \ifcsundef{\LWR@print@#1}{%
939         \expandafter\LetLtxMacro\csname \LWR@print@#1\expandafter\endcsname%
940         \csname#1\endcsname%
941         \csletcs{endLWR@print@#1}{end#1}%
942     }{%
943     \DeclareExpandableDocumentEnvironment{#1}{}{%
944         {\nameuse{\LWR@\LWR@formatting @#1}}%
945         {\nameuse{endLWR@\LWR@formatting @#1}}%
946     }

```

```
947 \end{warpHTML}
```

35 HTML-conversion output modifications

These booleans modify the HTML output in various ways to improve conversion to EPUB or word processor imports.

for HTML & PRINT: 948 \begin{warpall}

35.1 User-level controls

Bool FormatEPUB Changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.
Default: false

```
949 \newbool{FormatEPUB}  
950 \boolfalse{FormatEPUB}
```

Bool FormatWP Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments.
Default: false

```
951 \newbool{FormatWP}  
952 \boolfalse{FormatWP}
```

Bool WPMarkFloats Adds
Default: false
===== begin table =====
...
===== end =====
or
===== begin figure =====
...
===== end =====

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions.¹⁷

```
953 \newbool{WPMarkFloats}  
954 \boolfalse{WPMarkFloats}
```

Bool WPMarkMinipages Adds

```
Default: false      === begin minipage ===
                  ...
      === end minipage ===
```

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

```
955 \newbool{WPMarkMinipages}
956 \boolfalse{WPMarkMinipages}
```

Bool WPMarkTOC While formatting for word processors, adds
 Default: true === table of contents ===

where the Table of Contents would have been. This helps identify where to insert the actual TOC.

If set false, the actual TOC is printed instead.

```
957 \newbool{WPMarkTOC}
958 \booltrue{WPMarkTOC}
```

Bool WPMarkLOFT While formatting for word processors, adds
 Default: false === list of figures === and/or
 === list of tables ===

where each of these lists would have been. This helps identify where to insert the actual lists.

If set false, the actual lists are printed instead.

```
959 \newbool{WPMarkLOFT}
960 \boolfalse{WPMarkLOFT}
```

Bool WPMarkMath While formatting for word processors, prints math as \LaTeX code instead of creating SVG images or MATHJAX. This is useful for cut/paste into the **LibreOffice Writer TeXMaths** extension.

```
961 \newbool{WPMarkMath}
962 \boolfalse{WPMarkMath}
```

Bool WPTitleHeading While formatting for word processors, true sets the document title to <h1>, which is expected for HTML documents, but also causes the lower-level section headings to

¹⁷Perhaps some day word processors will have HTML import options for identifying <figure> and <figcaption> tags for figures and tables.

start at **Heading 2** when imported into LIBREOFFICE. Set to `false` to cause the title to be plain text, and the section headings to begin at **Heading 1**.

See table 7 on page 180.

```
963 \newbool{WPTitleHeading}
964 \boolfalse{WPTitleHeading}

965 \end{warpall}
```

35.2 Heading adjustments

If formatting the HTML for a word processor, adjust heading levels.

If `WPTitleHeading` is true, adjust so that part is **Heading 1**.

If `WPTitleHeading` is false, use `<h1>` for the title, and set part to **Heading 2**.

for HTML output:

```
966 \begin{warpHTML}

967 \AtBeginDocument{
968 \ifbool{FormatWP}{
969 \@ifundefined{chapter}{

970 \ifbool{WPTitleHeading}{% part and section starting at h2
971 \renewcommand*\{\LWR@tagtitle\}{h1}
972 \renewcommand*\{\LWR@tagtitleend\}{/h1}
973 \renewcommand*\{\LWR@tagpart\}{h2}
974 \renewcommand*\{\LWR@tagpartend\}{/h2}
975 \renewcommand*\{\LWR@tagsection\}{h3}
976 \renewcommand*\{\LWR@tagsectionend\}{/h3}
977 \renewcommand*\{\LWR@tagsubsection\}{h4}
978 \renewcommand*\{\LWR@tagsubsectionend\}{/h4}
979 \renewcommand*\{\LWR@tagsubsubsection\}{h5}
980 \renewcommand*\{\LWR@tagsubsubsectionend\}{/h5}
981 \renewcommand*\{\LWR@tagparagraph\}{h6}
982 \renewcommand*\{\LWR@tagparagraphend\}{/h6}
983 \renewcommand*\{\LWR@tag subparagraph\}{span class="subparagraph"}
984 \renewcommand*\{\LWR@tag subparagraphend\}{/span}
985 }% WPTitleHeading
986 {% not WPTitleHeading, part and section starting at h1
987 \renewcommand*\{\LWR@tagtitle\}{div class="title"}
988 \renewcommand*\{\LWR@tagtitleend\}{/div}
989 \renewcommand*\{\LWR@tagpart\}{h1}
990 \renewcommand*\{\LWR@tagpartend\}{/h1}
991 \renewcommand*\{\LWR@tagsection\}{h2}
992 \renewcommand*\{\LWR@tagsectionend\}{/h2}
993 \renewcommand*\{\LWR@tagsubsection\}{h3}}
```

```

994 \renewcommand*{\LWR@tagsubsectionend}{/h3}
995 \renewcommand*{\LWR@tagsubsubsection}{h4}
996 \renewcommand*{\LWR@tagsubsubsubsection}{/h4}
997 \renewcommand*{\LWR@tagparagraph}{h5}
998 \renewcommand*{\LWR@tagparagraphend}{/h5}
999 \renewcommand*{\LWR@tagsubparagraph}{h6}
1000 \renewcommand*{\LWR@tagsubparagraphend}{/h6}
1001 }% not WPTitleHeading
1002 }% chapter undefined
1003 {% chapter defined
1004 \ifbool{WPTitleHeading}{}%
1005 {% not WPTitleHeading, part and chapter starting at h1
1006 \renewcommand*{\LWR@tagtitle}{div class="title"}
1007 \renewcommand*{\LWR@tagtitleend}{/div}
1008 \renewcommand*{\LWR@tagpart}{h1}
1009 \renewcommand*{\LWR@tagpartend}{/h1}
1010 \renewcommand*{\LWR@tagchapter}{h2}
1011 \renewcommand*{\LWR@tagchapterend}{/h2}
1012 \renewcommand*{\LWR@tagsection}{h3}
1013 \renewcommand*{\LWR@tagsectionend}{/h3}
1014 \renewcommand*{\LWR@tagsubsection}{h4}
1015 \renewcommand*{\LWR@tagsubsectionend}{/h4}
1016 \renewcommand*{\LWR@tagsubsubsection}{h5}
1017 \renewcommand*{\LWR@tagsubsubsubsection}{/h5}
1018 \renewcommand*{\LWR@tagparagraph}{h6}
1019 \renewcommand*{\LWR@tagparagraphend}{/h6}
1020 \renewcommand*{\LWR@tagsubparagraph}{span class="subparagraph"}
1021 \renewcommand*{\LWR@tagsubparagraphend}{/span}
1022 }% not WPTitleHeading
1023 }% chapter defined
1024 }{}% FormatWP
1025 }% AtBeginDocument

1026 \end{warpHTML}

```

36 Remembering original formatting macros

for HTML output: 1027 \begin{warpHTML}

Remember original definitions of formatting commands. Will be changed to HTML commands for most uses. Will be temporarily restored to original meaning inside any `lateximage` environment. Also nullify unused commands.

Some packages redefine `\#`, which is used to generate HTML, so the original must be remembered here.

```
1028 \chardef\LWR@origpound='\#
1029 \let\LWR@origcomma\",
1030 \let\LWR@origthinspace\thinspace
1031 \let\LWR@orignegthinspace\negthinspace
1032 \let\LWR@origtilde-
1033 \let\LWR@origenskip\enskip
1034 \let\LWR@origquad\quad
1035 \let\LWR@origqquad\qquad
1036 \let\LWR@orighfil\hfil
1037 \let\LWR@orighss\hss
1038 \let\LWR@origllap\llap
1039 \let\LWR@origrlap\rlap
1040 \let\LWR@orighfilneg\hfilneg
1041
1042 \let\LWR@origmedskip\medskip
1043 \let\LWR@origbigskip\bigskip
1044
1045 \let\LWR@origtextellipsis{textellipsis}
1046
1047 \LetLtxMacro{\LWR@origtextrm}{textrm}
1048 \LetLtxMacro{\LWR@origtextsf}{textsf}
1049 \LetLtxMacro{\LWR@origtexttt}{texttt}
1050 \LetLtxMacro{\LWR@origtextnormal}{textnormal}
1051 \LetLtxMacro{\LWR@origtextbf}{textbf}
1052 \LetLtxMacro{\LWR@origtextmd}{textmd}
1053 \LetLtxMacro{\LWR@origtextit}{textit}
1054 \LetLtxMacro{\LWR@origtextsl}{textsl}
1055 \LetLtxMacro{\LWR@origtextsc}{textsc}
1056 \LetLtxMacro{\LWR@origtextup}{textup}
1057 \LetLtxMacro{\LWR@origemph}{emph}
1058
1059 \LetLtxMacro{\LWR@origrmfamily}{rmfamily}
1060 \LetLtxMacro{\LWR@origsffamily}{sffamily}
1061 \LetLtxMacro{\LWR@origttfamily}{ttfamily}
1062 \LetLtxMacro{\LWR@origbfseries}{bfseries}
1063 \LetLtxMacro{\LWR@origmdseries}{mdseries}
1064 \LetLtxMacro{\LWR@origupshape}{upshape}
1065 \LetLtxMacro{\LWR@origslshape}{slshape}
1066 \LetLtxMacro{\LWR@origscshape}{scshape}
1067 \LetLtxMacro{\LWR@origitshape}{itshape}
1068 \LetLtxMacro{\LWR@origem}{em}
1069 \LetLtxMacro{\LWR@orignormalfont}{normalfont}
1070
1071 \let\LWR@origonecolumn\onecolumn
1072
1073 \let\LWR@origsp\sp
1074 \let\LWR@origsb\sb
1075 \LetLtxMacro{\LWR@origtextsups}{textsups}
```

```
1076 \LetLtxMacro{\LWR@orig@textsuperscript}{\textsuperscript}
1077
1078 \AtBeginDocument{
1079 \LetLtxMacro{\LWR@origtextsubscript}{\textsubscript}
1080 \LetLtxMacro{\LWR@orig@textsubscript}{\textsubscript}
1081 }
1082
1083 \LetLtxMacro{\LWR@origunderline}{\underline}

1084 \let{\LWR@orignewpage}{\newpage}
1085
1086 \let{\LWR@origpagestyle}{\pagestyle}
1087 \let{\LWR@origthispagestyle}{\thispagestyle}
1088 \LetLtxMacro{\LWR@origpagenumbering}{\pagenumbering}
1089
1090 \let{\LWR@orignewline}{\newline}
1091
1092
1093 \AtBeginDocument{%
1094 \let{\LWR@orig@trivlist}{\trivlist}
1095 \let{\LWR@origtrivlist}{\trivlist}
1096 \let{\LWR@origendtrivlist}{\endtrivlist}
1097 \LetLtxMacro{\LWR@origitem}{\item}
1098 \LetLtxMacro{\LWR@origitemize}{\itemize}
1099 \LetLtxMacro{\LWR@endorigitemize}{\enditemize}
1100 \LetLtxMacro{\LWR@origenumerate}{\enumerate}
1101 \LetLtxMacro{\LWR@endorigenumerate}{\endenumerate}
1102 \LetLtxMacro{\LWR@origdescription}{\description}
1103 \LetLtxMacro{\LWR@endorigdescription}{\enddescription}
1104 \let{\LWR@orig@mklab}{\@mklab}
1105 \let{\LWR@origmakelabel}{\makelabel}
1106 \let{\LWR@orig@donoparitem}{\@donoparitem}
1107 \LetLtxMacro{\LWR@orig@item}{\@item}
1108 \let{\LWR@orig@nbitem}{\@nbitem}
1109 }
1110
1111 \let{\LWR@origpar}{\par}
1112
1113 \LetLtxMacro{\LWR@origfootnote}{\footnote}
1114 \let{\LWR@orig@mpfootnotetext}{\@mpfootnotetext}
1115
1116 \let{\LWR@origclearpage}{\clearpage}
1117
1118
1119 \AtBeginDocument{%
1120 \LetLtxMacro{\LWR@orighline}{\hline}
1121 \LetLtxMacro{\LWR@origcline}{\cline}
1122 }
```

```
1123 \end{warpHTML}
```

37 Accents

Native \LaTeX accents such as \^e will work, but many more kinds of accents are available when using Unicode-aware \Xe\LaTeX and \Lua\LaTeX .

for HTML output: 1124 \begin{warpHTML}

Without \AtBeginDocument , \t was being re-defined somewhere.

```
1125 \AtBeginDocument{
```

The following are restored for print when inside a \teximage .

For Unicode engines, only \t needs to be redefined:

```
1126 \LetLtxMacro{\LWR@origt}{\t}
```

For \pdf\LaTeX , additional work is required:

```
1127 \ifPDFTeX% pdflatex or dvi latex
1128 \LetLtxMacro{\LWR@origequalaccent}{%
1129 \LetLtxMacro{\LWR@origdotaccent}{.
1130 \LetLtxMacro{\LWR@origu}{\u}
1131 \LetLtxMacro{\LWR@origv}{\v}
1132 \LetLtxMacro{\LWR@origc}{\c}
1133 \LetLtxMacro{\LWR@origd}{\d}
1134 \LetLtxMacro{\LWR@origb}{\b}
```

The \HTML redefinitions follow.

For \pdf\LaTeX , Unicode diacritical marks are used:

```
1135 \renewcommand*{\=}[1]{\#1\HTMLunicode{0305}}
1136 \renewcommand*{\.}[1]{\#1\HTMLunicode{0307}}
1137 \renewcommand*{\u}[1]{\#1\HTMLunicode{0306}}
1138 \renewcommand*{\v}[1]{\#1\HTMLunicode{030C}}
1139 \renewcommand*{\c}[1]{\#1\HTMLunicode{0327}}
1140 \renewcommand*{\d}[1]{\#1\HTMLunicode{0323}}
1141 \renewcommand*{\b}[1]{\#1\HTMLunicode{0331}}
1142 \fi
```

For all engines, a Unicode diacritical tie is used:

```
1143 \def\LWR@t{\#1\#2{\#1\HTMLunicode{0361}\#2}
1144 \renewcommand*{\t}[1]{\LWR@t#1}
```

\LWR@restoreorigaccents Called from \restoreoriginalformatting when a `lateximage` is begun.

```
1145 \ifPDFTeX% pdflatex or dvi latex
1146 \newcommand*{\LWR@restoreorigaccents}{%
1147 \LetLtxMacro{\LWR@origequalaccent}{%
1148 \LetLtxMacro{\LWR@origdotaccent}{%
1149 \LetLtxMacro{\LWR@origu}{%
1150 \LetLtxMacro{\LWR@origv}{%
1151 \LetLtxMacro{\LWR@origt}{%
1152 \LetLtxMacro{\LWR@origc}{%
1153 \LetLtxMacro{\LWR@origd}{%
1154 \LetLtxMacro{\LWR@origb}{%
1155 }%
1156 \else% XeLaTeX, LuaLaTeX:
1157 \newcommand*{\LWR@restoreorigaccents}{%
1158 \LetLtxMacro{\LWR@origt}{%
1159 }%
1160 \fi%
1161 }% AtBeginDocument
```

```
1162 \end{warpHTML}
```

38 Configuration Files

38.1 Decide whether to generate configuration files

Configuration files are only written if processing the print version of the document, and not processing a `pstool` image. `pstool` uses an additional compile for each image using the original document's preamble, which includes `lwarp`, so the `lwarp` configuration files are turned off if `-pstool` is part of the `\jobname`.

Default to no configuration files:

```
1163 \excludecomment{LWRwriteconf}
```

Generate configuration files if print mode and not `-pstool`:

```
for PRINT output: 1164 \begin{warpprint}
1165 \fullexpandarg%
1166 \IfSubStr*{\jobname}{-pstool}%
1167 {
```

```

1168     \typeout{lwarf: jobname with -pstool is found,}%
1169     \typeout{lwarf: \space\space not generating configuration files.}%
1170 }
1171 {
1172     \typeout{lwarf: generating configuration files}
1173     \includecomment{LWRwriteconf}
1174 }
1175 \end{warpprint}

```

38.2 project_html.tex

File project_html.tex Used to allow an HTML version of the document to exist alongside the print version.

Config file:

```

1176 \begin{LWRwriteconf}
1177 \immediate\openout\LWR@quickfile=\jobname_html.tex
1178 \immediate\write\LWR@quickfile{%
1179 \detokenize{\PassOptionsToPackage}{%
1180 {warpHTML,BaseJobname=\jobname}{lwarf}}%
1181 }%
1182 \immediate\write\LWR@quickfile{%
1183 \detokenize{\input}\string{\jobname.tex}\string }%
1184 }%
1185 \immediate\closeout\LWR@quickfile
1186 \end{LWRwriteconf}

```

38.3 lwarpmk configuration files

Config file:

\LWR@lwarfconfversion The version number of the configuration file, allowing **lwarpmk** to detect an obsolete configuration file format. Incremented by one each time the configuration file format changes. (This is NOT the same as the **lwarf** version number.)

```
1188 \newcommand*\LWR@lwarfconfversion{1}% also in lwarpmk.lua
```

38.3.1 Helper macros

\LWR@shellescapecmd The LaTeX compile option for shell escape, if used.

```

1189 \ifshellescape
1190     \def\LWR@shellescapecmd{--shell-escape }
1191 \else
1192     \def\LWR@shellescapecmd{}

```

```
1193 \fi
```

```
\LWR@compilecmd {<engine>} {<suffix>}
```

Used to form the basic compilation command for a document, adding the optional shell escape.

Engine is **pdflatex**, etc. Suffix is empty or _html

```
1194 \newcommand*{\LWR@compilecmd}[2]{%
1195     #1 \LWR@shellescapecmd \jobname#2%
1196 }
```

```
\LWR@addcompilecmd {<cmd>} {<suffix>}
```

Adds to the compilation command.

Cmd is **dvipdfmx**, etc. Suffix is empty or _html

```
1197 \newcommand*{\LWR@addcompilecmd}[2]{%
1198     \LWRopseq
1199     #1 \jobname#2%
1200 }
```

```
\LWR@unknownengine Error message if not sure which LATEX engine is being used.
```

```
1201 \newcommand*{\LWR@unknownengine}{%
1202     \PackageError{l warp}%
1203     {Unknown LATEX engine.}%
1204     {L warp only knows about pdflatex, dvi latex, xelatex, and lualatex.}%
1205 }
```

```
\LWR@latexmkvar {<varname>} {<value>}
```

Adds a **latexmk** variable assignment.

```
1206 \newcommand*{\LWR@latexmkvar}[2]{%
1207     -e
1208     \LWRopquote%
1209     \LWRdollar #1=q/#2/%
1210     \LWRopquote
1211 }
```

```
\LWR@latexmkcmd {<latexmk options>}
```

Sets a call to **latexmk** with the given options, possibly adding --shell-escape, and also adding the indexing program.

```
1212 \newcommand*{\LWR@latexmkkcmd}[1]{%
1213   latexmk  \space \LWR@shellescapecmd \space #1 \space
1214   -recorder \space
1215   \LWR@latexmkkvar{makeindex}{\LWR@LatexmkIndexCmd}
1216 }
```

\LWR@latexmkdvipdfm {*dvipdfm or dvipdfmx*}

Adds the options settings for **dvipdfm** or **dvipdfmx**.

```
1217 \newcommand*{\LWR@latexmkdvipdfm}[1]{%
1218   -pdfdvi \space
1219   \LWR@latexmkkvar{dvipdf}{%
1220     #1
1221     \Opercentchar 0
1222     -o \Opercentchar D
1223     \Opercentchar S%
1224   }
1225 }
```

\LWR@PrintLatexCmd If not set by the user, the following sets the command to use to compile the source to PDF form.
\LWR@HTMLLatexCmd

If using **latexmk**, a complicated string is created, eventually resulting in something such as:

For **xelatex** with --shell-escape:

```
[[latexmk -xelatex --shell-escape -recorder
-e '$makeindex = q/makeindex -s lwarf.ist/' <jobname>.html]]
```

For **dvipdfmx**:

```
[[latexmk -pdfdvi -e '$dvipdf=q/dvipdfmx %0 -o %D %S/'
-recorder
-e '$makeindex=q/makeindex -s lwarf.ist/' <jobname>.html]]
```

For the following, temporary values are computed, but the permanent values are only set if the originals were not assigned by the user.

```
1226 \ifbool{\LWR@latexmkk}{
```

For **latexmk** with **pdflatex** or **lualatex**:

```
1227      \ifpdf
```

For **latexmk** with **pdflatex**:

```
1228      \ifPDFTeX
1229          \def\LWR@latexcmd{\LWR@latexmkcmd{-pdf -dvi- -ps-}}
1230      \else
```

For **latexmk** with **lualatex**:

```
1231      \ifLuaTeX
1232          \def\LWR@latexcmd{\LWR@latexmkcmd{-lualatex}}
1233      \else
1234          \LWR@unknownengine
1235      \fi
1236      \fi
1237      \else% \ifpdf
```

For **latexmk** with **xelatex** or **DVI latex**:

```
1238      \ifXeTeX
```

For **latexmk** with **xelatex**:

```
1239          \def\LWR@latexcmd{\LWR@latexmkcmd{-xelatex}}
1240      \else% \ifXeTeX
```

For **latexmk** with **DVI latex**:

```
1241      \ifbool{LWR@dvipdfm}{
1242          \def\LWR@latexcmd{%
1243              \LWR@latexmkcmd{%
1244                  \LWR@latexmkdvipdfm{dvipdfm}%
1245              }
1246          }
1247      }{
1248          \ifbool{LWR@dvipdfmx}{
1249              \def\LWR@latexcmd{%
1250                  \LWR@latexmkcmd{%
1251                      \LWR@latexmkdvipdfm{dvipdfmx}%
1252                  }
1253              }
1254          }{
1255              \def\LWR@latexcmd{\LWR@latexmkcmd{-pdfps}}
1256          }
1257      }
```

```
1258      \fi
1259      \fi% \ifpdf
```

The final assignment if **latexmk**:

```
1260      \def\LWR@tempprintlatexcmd{\LWR@latexcmd \space \jobname}
1261      \def\LWR@tempHTMLlatexcmd{\LWR@latexcmd \space \jobname_html}
1262 }% latexmk
```

Without **latexmk**, the compiling command is simply the compiler name and the optional shell escape:

```
1263 {%
1264     \ifpdf
```

For **pdflatex** or **lualatex**:

```
1265     \ifPDFTeX
```

For **pdflatex**:

```
1266         \def\LWR@tempprintlatexcmd{\LWR@compilecmd{pdflatex}{}}
1267         \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{pdflatex}{_html}}
1268     \else
1269         \ifLuaTeX
```

For **lualatex**:

```
1270         \def\LWR@tempprintlatexcmd{\LWR@compilecmd{lualatex}{}}
1271         \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{lualatex}{_html}}
1272     \else
1273         \LWR@unknownengine
1274     \fi
1275     \fi
1276 \else% \ifpdf
```

For DVI **latex** or **xelatex**:

```
1277     \ifXeTeX
```

For **xelatex**:

```
1278         \def\LWR@tempprintlatexcmd{\LWR@compilecmd{xelatex}{}}
1279         \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{xelatex}{_html}}
1280     \else
```

For DVI **latex**. Default to **dvips**, unless told to use **dvipdfm** or **dvipdfmx**:

```
1281           \ifbool{LWR@dvipdfm}{
```

For DVI **latex** with **dvipdfm**:

```
1282           \def\LWR@tempprintlatexcmd{%
1283             \LWR@compilecmd{latex}{}%
1284             \LWR@addcompilecmd{dvipdfm}{}%
1285           }%
1286           \def\LWR@tempHTMLlatexcmd{%
1287             \LWR@compilecmd{latex}{_html}%
1288             \LWR@addcompilecmd{dvipdfm}{_html}%
1289           }%
1290           \ifbool{LWR@dvipdfmx}{%
1291             \ifbool{LWR@dvipdfmx}{%
```

For DVI **latex** with **dvipdfmx**:

```
1292           \def\LWR@tempprintlatexcmd{%
1293             \LWR@compilecmd{latex}{}%
1294             \LWR@addcompilecmd{dvipdfmx}{}%
1295           }%
1296           \def\LWR@tempHTMLlatexcmd{%
1297             \LWR@compilecmd{latex}{_html}%
1298             \LWR@addcompilecmd{dvipdfmx}{_html}%
1299           }%
1300           \ifbool{dvips}{%
```

For DVI **latex** with **dvips** and **ps2pdf**:

```
1301           \def\LWR@tempprintlatexcmd{%
1302             \LWR@compilecmd{latex}{}%
1303             \LWR@addcompilecmd{dvips}{}%
1304             \LWR@addcompilecmd{ps2pdf}{} .ps%
1305           }%
1306           \def\LWR@tempHTMLlatexcmd{%
1307             \LWR@compilecmd{latex}{_html}%
1308             \LWR@addcompilecmd{dvips}{_html}%
1309             \LWR@addcompilecmd{ps2pdf}{_html} .ps%
1310           }%
1311         }%
1312       }%
1313     \fi% \ifXeTeX
1314   \fi% \ifpdf
1315 }% latexmk
```

Only make the setting permanent if the original was empty:

```
1316   \ifdefempty{\LWR@PrintLatexCmd}{%
1317     \def\LWR@PrintLatexCmd{\LWR@tempprintlatexcmd}
```

```

1318     }{}
1319     \ifdefempty{\LWR@HTMLLatexCmd}{%
1320       \def\LWR@HTMLLatexCmd{\LWR@tempHTMLlatexcmd}
1321     }{}}

\LWR@writeconf {<filename>}

```

Common code for each of `lwarpmk.conf` and `<project>.lwarpmkconf`. Each entry is a variable name, the equal sign, and a quoted string inside `[[and]]`, which are `lua`'s long quote characters, allowing the use of single and double quotes inside.

```

1322 \newcommand{\LWR@writeconf}[1]{%
1323 \ifcsdef{LWR@quickfile}{}{\newwrite{\LWR@quickfile}}
1324 \immediate\openout\LWR@quickfile=\#1
1325 \immediate\write\LWR@quickfile{confversion = [[\LWR@lwarpmkconfversion]]}
1326 \ifbool{usingOSWindows}{%
1327   \immediate\write\LWR@quickfile{opsystem = [[Windows]]}
1328 }{%
1329   \immediate\write\LWR@quickfile{opsystem = [[Unix]]}
1330 }
1331 \immediate\write\LWR@quickfile{sourcename = [[\jobname]]}
1332 \immediate\write\LWR@quickfile{homehtmlfilename = [[\HomeHTMLFilename]]}
1333 \immediate\write\LWR@quickfile{htmlfilename = [[\HTMLFilename]]}
1334 \immediate\write\LWR@quickfile{latexmk = [[\ifbool{LWR@latexmk}{true}{false}]]}
1335 \immediate\write\LWR@quickfile{printlatexcmd = [[\LWR@PrintLatexCmd]]}
1336 \immediate\write\LWR@quickfile{HTMLlatexcmd = [[\LWR@HTMLLatexCmd]]}
1337 \immediate\write\LWR@quickfile{printindexcmd = [[\LWR@PrintIndexCmd]]}
1338 \immediate\write\LWR@quickfile{HTMLindexcmd = [[\LWR@HTMLIndexCmd]]}
1339 \immediate\write\LWR@quickfile{latexmkindexcmd = [[\LWR@LatexmkIndexCmd]]}
1340 \immediate\write\LWR@quickfile{glossarycmd = [[\LWR@GlossaryCmd]]}
1341 \immediate\write\LWR@quickfile{pdftotextenc = [[\LWR@pdftotextEnc]]}
1342 \immediate\closeout\LWR@quickfile
1343 }
1344

1345 \end{LWR@writeconf}

```

38.3.2 lwarpmk.conf

File `lwarpmk.conf` `lwarpmk.conf` is automatically (re-)created by the `l warp` package when executing `pdflatex <project.tex>`, or similar for `xelatex` or `lualatex`, in print-document generation mode, which is the default unless the `warpHTML` option is given. `lwarpmk.conf` is then used by the utility `lwarpmk`.

Config file: 1346 `\begin{LWR@writeconf}`
1347

```
1348 \AtBeginDocument{\LWR@writeconf{lwarpmk.conf}}
1349
1350 \end{LWRwriteconf}
```

38.3.3 <project>.lwarpmkconf

File project.lwarpmkconf A project-specific configuration file for **lwarpmk**.

The `makeindex` and `xindy` options have already been handled for `lwarf.conf`.

Config file:

```
1351 \begin{LWRwriteconf}
1352
1353 \AtBeginDocument{\LWR@writeconf{\jobname.lwarpmkconf}}
1354
1355 \end{LWRwriteconf}
```

38.4 lwarf.css

File lwarf.css This is the base css layer used by **lwarf**.

This must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
1356 \begin{LWRwriteconf}
1357 \begin{filecontents*}{lwarf.css}
1358 /*
1359   CSS stylesheet for the LaTeX lwarf package
1360   Copyright 2016-2018 Brian Dunn -- BD Tech Concepts LLC
1361 */
1362
1363
1364 /* a fix for older browsers: */
1365 header, section, footer, aside, nav, main,
1366   article, figure { display: block; }
1367
1368
1369 A:link {color:#000080 ; text-decoration: none ; }
1370 A:visited {color:#800000 ; }
1371 A:hover {color:#000080 ; text-decoration: underline ;}
1372 A:active {color:#800000 ; }
1373
1374 a.tocpart {display: inline-block ; margin-left: 0em ;
1375   font-weight: bold ;}
1376 a.tocchapter {display: inline-block ; margin-left: 0em ;
1377   font-weight: bold ;}
1378 a.tocsection {display: inline-block ; margin-left: 1em ;}
```

```
1379     text-indent: -.5em ; font-weight: bold ; }
1380 a.tocsubsection {display: inline-block ; margin-left: 2em ;
1381     text-indent: -.5em ; }
1382 a.tocsubsubsection {display: inline-block ; margin-left: 3em ;
1383     text-indent: -.5em ; }
1384 a.tocparagraph {display: inline-block ; margin-left: 4em ;
1385     text-indent: -.5em ; }
1386 a.toc subparagraph {display: inline-block ; margin-left: 5em ;
1387     text-indent: -.5em ; }
1388 a.tocfigure {margin-left: 0em}
1389 a.tocsubfigure {margin-left: 2em}
1390 a.toctable {margin-left: 0em}
1391 a.tocsubtable {margin-left: 2em}
1392 a.toctheorem {margin-left: 0em}
1393 a.toclstlisting {margin-left: 0em}
1394
1395 body {
1396     font-family: "DejaVu Serif", "Bitstream Vera Serif",
1397                 "Lucida Bright", Georgia, serif;
1398     background: #FAF7F4 ;
1399     color: black ;
1400     margin: 0em ;
1401     padding: 0em ;
1402     font-size: 100% ;
1403     line-height: 1.2 ;
1404 }
1405
1406 p {margin: 1.5ex 0em 1.5ex 0em ;}
1407 table p {margin: .5ex 0em .5ex 0em ;}
1408
1409 /* Holds a section number to add space between it and the name */
1410 span.sectionnumber { margin-right: 0em }
1411
1412 /* Inserted in front of index lines */
1413 span.indexitem {margin-left: 0em}
1414 span.indexsubitem {margin-left: 2em}
1415 span.indexsubsubitem {margin-left: 4em}
1416
1417 div.hidden, span.hidden { display: none ; }
1418
1419 kbd, span.texttt {
1420     font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
1421                 "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
1422                 "Courier New", monospace;
1423     font-size: 100% ;
1424 }
1425
1426 pre { padding: 3pt ; }
1427
1428 span.strong, span.textbf, div.strong, div.textbf { font-weight: bold; }
```

```
1429
1430 span.textit, div.textit { font-style: italic; }
1431
1432 span.textmd, div.textmd { font-weight: normal; }
1433
1434 span.textsc, div.textsc { font-variant: small-caps; }
1435
1436 span.textsl, div.textsl { font-style: oblique; }
1437
1438 span.textup, div.textup { font-variant: normal; }
1439
1440 span.textrm, div.textrm {
1441     font-family: "DejaVu Serif", "Bitstream Vera Serif",
1442     "Lucida Bright", Georgia, serif;
1443 }
1444
1445 span.textsf, div.textsf {
1446     font-family: "DejaVu Sans", "Bitstream Vera Sans",
1447     Geneva, Verdana, sans-serif ;
1448 }
1449
1450 span.textcircled { border: 1px solid black ; border-radius: 1ex ; }
1451
1452 span.underline {
1453     text-decoration: underline ;
1454     text-decoration-skip: auto ;
1455 }
1456
1457 span.overline {
1458     text-decoration: overline ;
1459     text-decoration-skip: auto ;
1460 }
1461
1462 /* for diagbox */
1463 div.diagboxtitleN { border-bottom: 1px solid gray }
1464 div.diagboxtitleS { border-top: 1px solid gray }
1465
1466 div.diagboxE {
1467     padding-left: 2em ;
1468     text-align: right ;
1469 }
1470
1471 div.diagboxW {
1472     padding-right: 2em ;
1473     text-align: left ;
1474 }
1475
1476
1477
1478 /* For realscripts */
```

```
1479.supsubscript {  
1480    display: inline-block;  
1481    text-align:left ;  
1482}  
1483  
1484.supsubscript sup,  
1485.supsubscript sub {  
1486    position: relative;  
1487    display: block;  
1488    font-size: .5em;  
1489    line-height: 1;  
1490}  
1491  
1492.supsubscript sup {  
1493    top: .5em;  
1494}  
1495  
1496.supsubscript sub {  
1497    top: .5em;  
1498}  
1499  
1500 div.attribution p {  
1501    text-align: right ;  
1502    font-size: 80%;  
1503}  
1504  
1505 span.poemtitle {  
1506    font-size: 120% ; font-weight: bold;  
1507}  
1508  
1509 pre.tabbing {  
1510    font-family: "Linux Libertine Mono O", "Lucida Console",  
1511        "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",  
1512        "Liberation Mono", "FreeMono", "Andale Mono",  
1513        "Nimbus Mono L", "Courier New", monospace;  
1514}  
1515  
1516blockquote {  
1517    margin-left: 0px ;  
1518    margin-right: 0px ;  
1519}  
1520  
1521/* quotchap is for the quotchap package */  
1522div.quotchap {  
1523    font-style: oblique ;  
1524    overflow-x: auto ;  
1525    margin-left: 2em ;  
1526    margin-right: 2em ;  
1527}  
1528
```

```
1529blockquote p, div.quotchap p {
1530    line-height: 1.5;
1531    text-align: left ;
1532    font-size: .85em ;
1533    margin-left: 3em ;
1534    margin-right: 3em ;
1535 }
1536
1537 /* qauthor is for the quotchap package */
1538 div.qauthor {
1539    display: block ;
1540    text-align: right ;
1541    margin-left: auto ;
1542    margin-right: 2em ;
1543    font-size: 80% ;
1544    font-variant: small-caps;
1545 }
1546
1547 div.qauthor p {
1548    text-align: right ;
1549 }
1550
1551 blockquotation {
1552    margin-left: 0px ;
1553    margin-right: 0px ;
1554 }
1555
1556 blockquotation p {
1557    line-height: 1.5;
1558    text-align: left ;
1559    font-size: .85em ;
1560    margin-left: 3em ;
1561    margin-right: 3em ;
1562 }
1563
1564 div.epigraph, div.dictum {
1565    line-height: 1.2;
1566    text-align: left ;
1567    padding: 3ex 1em 0ex 1em ;
1568 /*     margin: 3ex auto 3ex auto ; */ /* Epigraph centered */
1569    margin: 3ex 1em 3ex auto ; /* Epigraph to the right */
1570 /*     margin: 3ex 1em 3ex 1em ; */ /* Epigraph to the left */
1571    font-size: .85em ;
1572    max-width: 27em ;
1573 }
1574
1575 div.epigraphsource, div.dictumauthor {
1576    text-align:right ;
1577    margin-left:auto ;
1578 /*     max-width: 50% ; */
```

```
1579     border-top: 1px solid #AOAOAO ;
1580     padding-bottom: 3ex ;
1581     line-height: 1.2;
1582 }
1583
1584 div.epigraph p, div.dictum p { padding: .5ex ; margin: 0ex ;}
1585 div.epigraphsource p, div.dictumauthor p { padding: .5ex 0ex 0ex 0ex ; margin: 0ex ;}
1586 div.dictumauthor { font-style:italic }
1587
1588
1589 /* copyrightbox package */
1590 div.copyrightbox { margin: .5ex .5em }
1591 div.copyrightbox p {margin: 0px .5em ; padding: 0px}
1592 div.copyrightboxnote {text-align: left ; font-size: 60%}
1593
1594
1595 /* lettrine package */
1596 span.lettrine { font-size: 4ex ; float: left ; }
1597 span.lettrinetext { font-variant: small-caps ; }
1598
1599 /* ulem and soul packages: */
1600 span.uline {
1601     text-decoration: underline ;
1602     text-decoration-skip: auto ;
1603 }
1604
1605 span.uuline {
1606     text-decoration: underline ;
1607     text-decoration-skip: auto ;
1608     text-decoration-style: double ;
1609 }
1610
1611 span.uwave {
1612     text-decoration: underline ;
1613     text-decoration-skip: auto ;
1614     text-decoration-style: wavy ;
1615 }
1616
1617 span.sout {
1618     text-decoration: line-through ;
1619 }
1620
1621 span.xout {
1622     text-decoration: line-through ;
1623 }
1624
1625 span.dashuline {
1626     text-decoration: underline ;
1627     text-decoration-skip: auto ;
1628     text-decoration-style: dashed ;
```

```
1629 }
1630
1631 span.dotunderline {
1632     text-decoration: underline ;
1633     text-decoration-skip: auto ;
1634     text-decoration-style: dotted ;
1635 }
1636
1637 span.letterspacing { letter-spacing: .2ex ; }
1638
1639 span.capsspacing {
1640     font-variant: small-caps ;
1641     letter-spacing: .1ex ;
1642 }
1643
1644 span.highlight { background: #F8E800 ; }
1645
1646
1647
1648
1649 html body {
1650     margin: 0 ;
1651     line-height: 1.2;
1652 }
1653
1654
1655 body div {
1656     margin: 0ex;
1657 }
1658
1659
1660 h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
1661 {
1662     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
1663         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
1664         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
1665         "Times New Roman", serif;
1666     font-style: normal ;
1667     font-weight: bold ;
1668     text-align: left ;
1669 }
1670
1671 h1 { /* title of the entire website, used on each page */
1672     text-align: center ;
1673     font-size: 2.5em ;
1674     padding: .4ex 0em 0ex 0em ;
1675 }
1676 h2 { font-size: 2.25em }
1677 h3 { font-size: 2em }
1678 h4 { font-size: 1.75em }
```

```
1679 h5 { font-size: 1.5em }
1680 h6 { font-size: 1.25em }
1681 span.paragraph {font-size: 1em ; font-variant: normal ;
1682     margin-right: 1em ; }
1683 span.subparagraph {font-size: 1em ; font-variant: normal ;
1684     margin-right: 1em ; }
1685
1686 div.minisec {
1687     font-family: "DejaVu Sans", "Bitstream Vera Sans",
1688         Geneva, Verdana, sans-serif ;
1689     font-style: normal ;
1690     font-weight: bold ;
1691     text-align: left ;
1692 }
1693
1694 /* Title of the file */
1695 h1 {
1696     margin: 0ex 0em 0ex 0em ;
1697     line-height: 1.3;
1698     text-align: center ;
1699 }
1700
1701 /* Part */
1702 h2 {
1703     margin: 1ex 0em 1ex 0em ;
1704     line-height: 1.3;
1705     text-align: center ;
1706 }
1707
1708 /* Chapter */
1709 h3 {
1710     margin: 3ex 0em 1ex 0em ;
1711     line-height: 1.3;
1712 }
1713
1714 /* Section */
1715 h4 {
1716     margin: 3ex 0em 1ex 0em ;
1717     line-height: 1.3;
1718 }
1719
1720 /* Sub-Section */
1721 h5 {
1722     margin: 3ex 0em 1ex 0em ;
1723     line-height: 1.3;
1724 }
1725
1726 /* Sub-Sub-Section */
1727 h6 {
1728     margin: 3ex 0em 1ex 0em ;
```

```
1729   line-height: 1.3;
1730 }
1731
1732
1733 div.titlepage {
1734   text-align: center ;
1735 }
1736
1737 .footnotes {
1738   text-align: left ;
1739   font-size: .85em ;
1740   margin: 3ex 2em 0ex 2em ;
1741   border-top: 1px solid silver ;
1742 }
1743
1744 .marginpar, .marginparblock {
1745   max-width:50%;
1746   float:right;
1747   text-align:left;
1748   margin: 1ex 0.5em 1ex 1em ;
1749   padding: 1ex 0.5em 1ex 0.5em ;
1750   font-size: 85% ;
1751   border-top: 1px solid silver ;
1752   border-bottom: 1px solid silver ;
1753   overflow-x: auto;
1754 }
1755
1756 .marginpar br { margin-bottom: 2ex ; }
1757
1758 div.marginblock, div.marginparblock {
1759   max-width:50%;
1760   float:right;
1761   text-align:left;
1762   margin: 1ex 0.5em 1ex 1em ;
1763   padding: 1ex 0.5em 1ex 0.5em ;
1764   overflow-x: auto;
1765 }
1766
1767 div.marginblock div.minipage,
1768 div.marginparblock div.minipage {
1769   display: block ;
1770   margin: Opt auto Opt auto ;
1771 }
1772
1773 div.marginblock div.minipage p ,
1774 div.marginparblock div.minipage p
1775   { font-size: 85%}
1776
1777 div.marginblock br ,
1778 div.marginparblock br
```

```
1779     { margin-bottom: 2ex ; }
1780
1781
1782 section.textbody div.footnotes{
1783     margin: 3ex 2em 0ex 2em ;
1784     border-bottom: 2px solid silver ;
1785 }
1786
1787 .footnoteheader {
1788     border-top: 2px solid silver ;
1789     margin-top: 3ex ;
1790     padding-top: 1ex ;
1791     font-weight: bold ;
1792 }
1793
1794 .mpfootnotes {
1795     text-align: left ;
1796     font-size: .85em ;
1797     margin-left: 1em ;
1798     border-top: 1px solid silver ;
1799 }
1800
1801 /* Remove footnote top border in the title page. */
1802 div.titlepage div.mpfootnotes {
1803     border-top: none ;
1804 }
1805
1806
1807
1808 ol {
1809     margin: 1ex 1em 1ex 0em;
1810     line-height: 1.2;
1811 }
1812
1813 ul, body dir, body menu {
1814     margin: 3ex 1em 3ex 0em;
1815     line-height: 1.2;
1816 }
1817
1818 li { margin: 0ex 0em 1ex 0em; }
1819
1820 html {
1821     margin: 0;
1822     padding: 0;
1823 }
1824
1825 .programlisting {
1826     font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
1827                 "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
1828                 "Courier New", monospace;
```

```
1829   margin: 1ex 0ex 1ex 0ex ;
1830   padding: .5ex 0pt .5ex 0pt ;
1831   overflow-x: auto;
1832 }
1833
1834 section.textbody>pre.programlisting {
1835 border-top: 1px solid silver ;
1836 border-bottom: 1px solid silver ;
1837 }
1838
1839
1840 div.displaymath {
1841   text-align: center ;
1842 }
1843
1844 div.displaymathnumbered {
1845   text-align: right ;
1846   margin-left: 5% ;
1847   margin-right: 5% ;
1848   min-width: 2.5in ;
1849 }
1850
1851 @media all and (min-width: 400px) {
1852   div.displaymathnumbered {
1853     margin-left: 10% ;
1854     margin-right: 10% ;
1855   }
1856 }
1857
1858 @media all and (min-width: 800px) {
1859   div.displaymathnumbered {
1860     margin-right: 20% ;
1861   }
1862 }
1863
1864 @media all and (min-width: 1200px) {
1865   div.displaymathnumbered {
1866     margin-right: 30% ;
1867   }
1868 }
1869
1870
1871 .inlineprogramlisting {
1872   font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
1873   "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
1874   "Courier New", monospace;
1875   overflow-x: auto;
1876 }
1877
1878 span.listinglabel {
```

```
1879     display: inline-block ;
1880     font-size: 70% ;
1881     width: 4em ;
1882     text-align: right ;
1883     margin-right: 2em ;
1884 }
1885
1886 div.abstract {
1887   margin: 2em 5% 2em 5% ;
1888   padding: 1ex 1em 1ex 1em ;
1889 /* font-weight: bold ; */
1890   font-size: 90% ;
1891   text-align: left ;
1892 }
1893
1894 div.abstract dl {line-height:1.5;}
1895 div.abstract dt {color:#304070;}
1896
1897 div.abstracttitle{
1898   font-family: "URW Classico", Optima, "Linux Biolinum 0",
1899             "Linux Libertine 0", "Liberation Serif", "Nimbus Roman No 9 L",
1900             "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
1901   font-weight:bold;
1902   font-size:1.25em;
1903   text-align: center ;
1904 }
1905
1906 span.abstractrunintitle{
1907   font-family: "URW Classico", Optima, "Linux Biolinum 0",
1908             "Linux Libertine 0", "Liberation Serif", "Nimbus Roman No 9 L",
1909             "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
1910   font-weight:bold;
1911 }
1912
1913
1914 .verbatim {
1915   overflow-x: auto ;
1916 }
1917
1918 .alltt {
1919   overflow-x: auto ;
1920 }
1921
1922
1923 .bverbatim {
1924   margin: 1ex Opt 1ex Opt ;
1925   padding: .5ex Opt .5ex Opt ;
1926   overflow-x: auto ;
1927 }
1928
```

```
1929 .lverbatim {
1930     margin: 1ex 0pt 1ex 0pt ;
1931     padding: .5ex 0pt .5ex 0pt ;
1932     overflow-x: auto ;
1933 }
1934
1935 .fancyvrb {
1936     font-size:.85em ;
1937     margin: 3ex 0pt 3ex 0pt
1938 }
1939
1940 .fancyvrblabel {
1941     font-weight:bold;
1942     text-align: center ;
1943 }
1944
1945
1946 .verse {
1947     font-family: "Linux Libertine Mono O", "Lucida Console",
1948         "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
1949         "Liberation Mono", "FreeMono", "Andale Mono",
1950         "Nimbus Mono L", "Courier New", monospace;
1951     margin-left: 1em ;
1952 }
1953
1954
1955 div.singlespace { line-height: 1.2 ; }
1956 div.onehalfspace { line-height: 1.5 ; }
1957 div.doublespace { line-height: 2 ; }
1958
1959
1960 /* Word processor format output: */
1961 div.wpfigure { border: 1px solid red ; margin: .5ex ; padding: .5ex ; }
1962 div.wptable { border: 1px solid blue ; margin: .5ex ; padding: .5ex ; }
1963 div.wpminipage { border: 1px solid green ; margin: .5ex ; padding: .5ex ;}
1964
1965
1966
1967
1968 /* Minipage environments, vertically aligned to top, center, bottom: */
1969 .minipage, .fminipage, .fcolorminipage {
1970     /* display: inline-block ; */
1971         /* Mini pages which follow each other will be tiled. */
1972     margin: .25em .25em .25em .25em;
1973     padding: .25em .25em .25em .25em;
1974     display: inline-flex;
1975     flex-direction: column ;
1976     overflow: auto;
1977 }
1978
```

```
1979 /* Paragraphs in the flexbox did not collapse their margins. */
1980 /* Have not yet researched this. */
1981 .minipage p {margin: .75ex 0em .75ex 0em ;}
1982
1983 .fboxBlock .minipage, .colorbox .minipage, .colorboxBlock .minipage,
1984 .fcolorbox .minipage, .fcolorboxBlock .minipage
1985     {border: none ; background: none;}
1986
1987 .fbox, .fboxBlock { border: 1px solid black ; }
1988
1989 .fbox, .fboxBlock, .fcolorbox, .fcolorboxBlock, .colorbox, .colorboxBlock,
1990 .fminipage, .fcolorminipage
1991     {display: inline-block}
1992
1993 .shadowbox, .shabox {
1994     border: 1px solid black;
1995     box-shadow: 3px 3px 3px #808080 ;
1996     border-radius: 0px ;
1997     padding: .4ex .3em .4ex .3em ;
1998     margin: 0pt .3ex 0pt .3ex ;
1999     display: inline-block ;
2000 }
2001
2002 .doublebox {
2003     border: 3px double black;
2004     border-radius: 0px ;
2005     padding: .4ex .3em .4ex .3em ;
2006     margin: 0pt .3ex 0pt .3ex ;
2007     display: inline-block ;
2008 }
2009
2010 .ovalbox, .Ovalbox {
2011     border: 1px solid black;
2012     border-radius: 1ex ;
2013     padding: .4ex .3em .4ex .3em ;
2014     margin: 0pt .3ex 0pt .3ex ;
2015     display: inline-block ;
2016 }
2017
2018 .Ovalbox { border-width: 2px ; }
2019
2020 .framebox {
2021     border: 1px solid black;
2022     border-radius: 0px ;
2023     padding: .3ex .2em 0ex .2em ;
2024     margin: 0pt .1ex 0pt .1ex ;
2025     display: inline-block ;
2026 }
2027
2028
```

```
2029 .mdframed {
2030 /*     padding: 0ex ; */
2031 /*     border: 1px solid blafck; */
2032 /*     border-radius: 0px ; */
2033     padding: 0ex ;
2034     margin: 3ex 5% 3ex 5% ;
2035 /*     display: inline-block ; */
2036 }
2037
2038 .mdframed p { padding: 0ex .5em 0ex .5em ; }
2039
2040 .mdframed dl { padding: 0ex .5em 0ex .5em ; }
2041
2042 .mdframedtitle {
2043     padding: .5em ;
2044     display: block ;
2045     font-size: 130% ;
2046     margin-bottom: 1ex ;
2047 }
2048
2049 .mdframedsubtitle {
2050     padding: 0ex .5em 0ex .5em ;
2051     display: block ;
2052     font-size: 115% ;
2053 }
2054
2055 .mdframedsubsubtitle {
2056     padding: 0ex .5em 0ex .5em ;
2057     display: block ;
2058 }
2059
2060 .mdtheorem {
2061     padding: 0ex .5em 0ex .5em ;
2062     margin: 3ex 5% 3ex 5% ;
2063 /*     display: inline-block ; */
2064 }
2065
2066
2067 /* framed package */
2068 .framed, pre.boxedverbatim, fcolorbox {
2069     margin: 3ex 0em 3ex 0em ;
2070     border: 1px solid black;
2071     border-radius: 0px ;
2072     padding: .3ex 1em 0ex 1em ;
2073     display: block ;
2074 }
2075
2076 .shaded {
2077     margin: 3ex 0em 3ex 0em ;
2078     padding: .3ex 1em .3ex 1em ;
```

```
2079     display: block ;
2080 }
2081
2082 .snugframed {
2083     margin: 3ex 0em 3ex 0em ;
2084     border: 1px solid black;
2085     border-radius: 0px ;
2086     display: block ;
2087 }
2088
2089 .framedleftbar {
2090     margin: 3ex 0em 3ex 0em ;
2091     border-left: 3pt solid black;
2092     border-radius: 0px ;
2093     padding: .3ex .2em .3ex 1em ;
2094     display: block ;
2095 }
2096
2097 .framedtitle {
2098     margin: 0em ;
2099     padding: 0em ;
2100     font-size: 130%
2101 }
2102
2103 .framedtitle p { padding: .3em }
2104
2105
2106
2107 dl {
2108     margin: 1ex 2em 1ex 0em;
2109     line-height: 1.3;
2110 }
2111
2112 dl dt {
2113     margin-top: 1ex;
2114     margin-left: 1em ;
2115     font-weight: bold;
2116 }
2117
2118 dl dd p { margin-top: 0em; }
2119
2120
2121 nav {
2122     font-family: "URW Classico", Optima, "Linux Biolinum 0",
2123             "DejaVu Sans", "Bitstream Vera Sans",
2124             Geneva, Verdana, sans-serif ;
2125     margin-bottom: 4ex ;
2126 }
2127
2128 nav p {
```

```
2129     line-height: 1.2 ;
2130     margin-top:.5ex ;
2131     margin-bottom:.5ex;
2132     font-size: .9em ;
2133 }
2134
2135
2136
2137 img, img.hyperimage, img.borderimage {
2138     max-width: 600px;
2139     border: 1px solid silver;
2140     box-shadow: 3px 3px 3px #808080 ;
2141     padding: .5% ;
2142     margin: .5% ;
2143     background: none ;
2144 }
2145
2146 img.inlineimage{
2147     padding: 0px ;
2148     box-shadow: none ;
2149     border: none ;
2150     background: none ;
2151     margin: 0px ;
2152     display: inline-block ;
2153     border-radius: 0px ;
2154 }
2155
2156 img.logoimage{
2157     max-width: 300px ;
2158     box-shadow: 3px 3px 3px #808080 ;
2159     border: 1px solid black ;
2160     background:none ;
2161     padding:0 ;
2162     margin:.5ex ;
2163     border-radius: 10px ;
2164 }
2165
2166
2167 .section {
2168 /*
2169     To have each section float relative to each other:
2170 */
2171 /*
2172     display: block ;
2173     float: left ;
2174     position: relative ;
2175     background: white ;
2176     border: 1px solid silver ;
2177     padding: .5em ;
2178 */
```

```
2179     margin: 0ex .5em 0ex .5em ;
2180     padding: 0 ;
2181 }
2182
2183
2184 figure {
2185     margin: 5ex auto 5ex auto ;
2186     padding: 1ex 1em 1ex 1em ;
2187     overflow-x: auto ;
2188 }
2189
2190
2191 /* To automatically center images in figures: */
2192 /*
2193 figure img.inlineimage {
2194     margin: 0ex auto 0ex auto ;
2195     display: block ;
2196 }
2197 */
2198
2199 /* To automatically center minipages in figures: */
2200 /*
2201 figure div.minipage, figure div.minipage div.minipage {
2202     margin: 1ex auto 1ex auto ;
2203     display: block ;
2204 }
2205 */
2206
2207 figure div.minipage p { font-size: 85% ; }
2208
2209 figure.subfigure, figure.subtable {
2210     display: inline-block ; margin: 3ex 1em 3ex 1em ;
2211 }
2212
2213 figcaption .minipage { margin:0 ; padding: 0 }
2214
2215 div.minipage figure { border: none ; box-shadow: none ; }
2216 div.minipage figure.table { margin: 0ex }
2217 div.minipage div.footnotes { margin: 1ex 2em 0ex 2em }
2218
2219 div.floatrow { text-align: center; }
2220
2221 div.floatrow figure { display: inline-block ; margin: 1ex 2% ; }
2222
2223 div.floatfoot { font-size: .85em ;
2224     border-top: 1px solid silver ; line-height: 1.2 ; }
2225
2226 figcaption , .lstlistingtitle {
2227     font-size: .85em ;
2228     text-align: center ;
```

```
2229     font-weight: bold ;
2230     margin-top: 1ex ;
2231     margin-bottom: 1ex ;
2232 }
2233
2234 figure.subfigure figcaption, figure.subtable figcaption {
2235     border-bottom: none ; background: none ;
2236 }
2237
2238 div.nonfloatcaption {
2239     margin: 1ex auto 1ex auto ;
2240     font-size: .85em ;
2241     text-align: center ;
2242     font-weight: bold ;
2243 }
2244
2245 /* For a \RawCaption inside a minipage inside a figure's floatrow: */
2246 figure div.floatrow div.minipage figcaption {
2247     border: none ;
2248     background: none ;
2249 }
2250
2251
2252 /* For packages such as float, rotfloat, and algorithm2e: */
2253
2254 figure.boxed, figure.boxruled {
2255     border: 1px solid black ;
2256 }
2257
2258 figure.ruled {
2259     border-top: 1px solid black ;
2260     border-bottom: 1px solid black ;
2261     border-left: 0px ;
2262     border-right: 0px ;
2263     border-radius: 0px ;
2264     background: none ;
2265     box-shadow: none ;
2266 }
2267
2268 figure.ruled figcaption, figure.boxruled figcaption {
2269     border-top: 1px solid silver ;
2270     border-bottom: 1px solid silver ;
2271 }
2272
2273
2274 table {
2275     margin: 1ex auto 1ex auto ;
2276     border-collapse: separate ;
2277     border-spacing: 0px ;
2278     line-height: 1.3 ;
```

```
2279      }
2280
2281 tr.hline td {border-top: 1px solid #808080 ; margin-top: 0ex ;
2282     margin-bottom: 0ex ; } /* for \hline */
2283
2284 tr.tbrule td {border-top: 1px solid black ; margin-top: 0ex ;
2285     margin-bottom: 0ex ; } /* for \toprule, \bottomrule */
2286
2287 td {padding: .5ex .5em .5ex .5em ;}
2288
2289 table td.tdl { text-align: left ; vertical-align: middle ; }
2290 table td.tdc { text-align: center ; vertical-align: middle ; }
2291 table td.tdat { text-align: center ; vertical-align: middle ; padding: 0px ; margin: 0px ; }
2292 table td.tdbang { text-align: center ; vertical-align: middle ; }
2293 table td.tdr { text-align: right ; vertical-align: middle ; }
2294 table td.tdp { text-align: left ; vertical-align: bottom ; }
2295 table td.tdm { text-align: left ; vertical-align: middle ; }
2296 table td.tdb { text-align: left ; vertical-align: top ; }
2297 table td.tdP { text-align: center ; vertical-align: bottom ; }
2298 table td.tdM { text-align: center ; vertical-align: middle ; }
2299 table td.tdB { text-align: center ; vertical-align: top ; }
2300
2301 table td.tvertbarl { border-left: 1px solid black }
2302 table td.tvertbarldouble { border-left: 4px double black }
2303 table td.tvertbarr { border-right: 1px solid black }
2304 table td.tvertbarrdouble { border-right: 4px double black }
2305
2306 table td.tvertbarldash { border-left: 1px dashed black }
2307 table td.tvertbarldoubledash { border-left: 2px dashed black }
2308 table td.tvertbarrdash { border-right: 1px dashed black }
2309 table td.tvertbarrdoubledash { border-right: 2px dashed black }
2310
2311
2312 /* for cmidrules: */
2313 table td.tdrule {
2314     border-top: 1px solid #AOAOAO ;
2315 }
2316
2317 table td.tdrulel {
2318     border-top-left-radius:.5em ;
2319     border-top: 1px solid #AOAOAO ;
2320 }
2321
2322 table td.tdruler {
2323     border-top-right-radius:.5em ;
2324     border-top: 1px solid #AOAOAO ;
2325 }
2326
2327 table td.tdrulelr {
2328     border-top-left-radius:.5em ;
```

```
2329     border-top-right-radius:.5em ;
2330     border-top: 1px solid #AOAOAO ;
2331 }
2332
2333 /* Margins of paragraphs inside table cells: */
2334 td.tdp p , td.tdprule p , td.tdP p , td.tdPrule p { padding-top: 1ex ;
2335     padding-bottom: 1ex ; margin: 0ex ; }
2336 td.tdm p , td.tdmrule p , td.tdM p , td.tdMrule p { padding-top: 1ex ;
2337     padding-bottom: 1ex ; margin: 0ex ; }
2338 td.tdb p , td.tdbeule p , td.tdB p , td.tdBrule p { padding-top: 1ex ;
2339     padding-bottom: 1ex ; margin: 0ex ; }
2340
2341 td.tdp , td.tdprule , td.tdP , td.tdPrule
2342     { padding: 0ex .5em 0ex .5em ; }
2343 td.tdm , td.tdmrule , td.tdM , td.tdMrule
2344     { padding: 0ex .5em 0ex .5em ; }
2345 td.tdb , td.tdbeule , td.tdB , td.tdBrule
2346     { padding: 0ex .5em 0ex .5em ; }
2347
2348
2349 /* table notes: */
2350 .tnotes {
2351     margin: 0ex 5% 1ex 5% ;
2352     padding: 0.5ex 1em 0.5ex 1em;
2353     font-size:.85em;
2354     text-align: left ;
2355 }
2356 }
2357
2358 .tnotes dl dt p {margin-bottom:0px;}
2359
2360 .tnoteitemheader {margin-right: 1em;}
2361
2362
2363 /* for colortbl and cell color */
2364 div.cellcolor {
2365     width: 100% ;
2366     padding: .5ex .5em .5ex .5em ;
2367     margin: -.5ex -.5em -.5ex -.5em ;
2368 }
2369
2370
2371 /* for bigdelim */
2372 .ldelim, .rdelim { font-size: 200% }
2373
2374
2375 /* center, flushleft, flushright environments */
2376 div.center{text-align:center;}
2377 div.center table {margin-left:auto;margin-right:auto;}
2378 div.flushleft{text-align:left;}
```

```
2379 div.flushleft table {margin-left:0em ; margin-right:auto;}
2380 div.flushright{text-align:right;}
2381 div.flushright table {margin-left:auto ; margin-right: 0em ;}
2382
2383
2384 /* Fancybox */
2385 div.Btrivlist table tr td {
2386     padding: .2ex 0em ;
2387 }
2388
2389
2390 /* program listing callouts: */
2391 span.callout {
2392     font-family: "DejaVu Sans", "Bitstream Vera Sans",
2393                 Geneva, Verdana, sans-serif ;
2394     border-radius: .5em;
2395     background-color:black;
2396     color:white;
2397     padding:0px .25em 0px .25em;
2398     margin: 0 ;
2399     font-weight: bold;
2400     font-size:.72em ;
2401 }
2402
2403 div.programlisting pre.verbatim span.callout{
2404     font-size: .85em ;
2405 }
2406
2407 span.verbatim {
2408     font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
2409                 "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
2410                 "Courier New", monospace;
2411 }
2412
2413
2414
2415 div.published
2416 {
2417     text-align: center ;
2418     font-variant: normal ;
2419     font-style: italic ;
2420     font-size: 1em ;
2421     margin: 3ex 0em 3ex 0em ;
2422 }
2423
2424 div.subtitle
2425 {
2426     text-align: center ;
2427     font-variant: normal ;
2428     font-style: italic ;
```

```
2429     font-size: 1.25em ;
2430     margin: 3ex 0em 3ex 0em ;
2431 }
2432
2433 div.subtitle p { margin: 1ex ; }
2434
2435 div.author
2436 {
2437     font-variant: normal ;
2438     font-style: normal ;
2439     font-size: 1em ;
2440     margin: 3ex 0em 3ex 0em ;
2441 }
2442
2443 div.oneauthor {
2444     display: inline-block ;
2445     margin: 3ex 1em 0ex 1em ;
2446 }
2447
2448 /*
2449 div.author table {
2450     margin: 3ex auto 0ex auto ;
2451     background: none ;
2452 }
2453
2454 div.author table tbody tr td { padding: .25ex ; }
2455 */
2456
2457 span.affiliation {font-size: .85em ; font-variant: small-caps; }
2458
2459 div.titledate {
2460     text-align: center ;
2461     font-size: .85em ;
2462     font-style: italic;
2463     margin: 6ex 0em 6ex 0em ;
2464 }
2465
2466
2467 nav.topnavigation{
2468     text-align: left ;
2469     padding: 0.5ex 1em 0.5ex 1em ;
2470 /*     margin: 2ex 0em 3ex 0em ; */
2471     margin: 0 ;
2472     border-bottom: 1px solid silver ;
2473     border-top: 1px solid silver ;
2474     clear:right ;
2475 }
2476
2477 nav.botnavigation{
2478     text-align: left ;
```

```
2479     padding: 0.5ex 1em 0.5ex 1em ;
2480 /*      margin: 3ex 0em 2ex 0em ; */
2481     margin: 0 ;
2482     border-top: 1px solid silver ;
2483     border-bottom: 1px solid silver ;
2484     clear:right ;
2485 }
2486
2487
2488 header{
2489     line-height: 1.2 ;
2490     font-size: 1em ;
2491 /*      border-bottom: 2px solid silver ; */
2492     margin: 0px ;
2493     padding: 0ex 1em 0ex 1em ;
2494     text-align:center ;
2495 }
2496
2497 header p {margin:0ex;padding:4ex 0em 2ex 0em ;text-align:center;}
2498
2499
2500 footer{
2501     font-size: .85em ;
2502     line-height: 1.2 ;
2503     margin-top: 1ex ;
2504     border-top: 2px solid silver ;
2505     padding: 2ex 1em 2ex 1em ;
2506     clear:right ;
2507     text-align:left ;
2508 }
2509
2510
2511 a.linkhome { font-weight:bold ; font-size: 1em ;}
2512
2513
2514 div.lateximagesource { padding: 0px ; margin: 0px ; display: none; }
2515
2516 img.lateximage{
2517     padding: 0pt ;
2518     margin: 0pt ;
2519     box-shadow: none ;
2520     border: none ;
2521     background: none ;
2522     max-width: 100% ;
2523     border-radius: 0ex ;
2524     border: none ;
2525 }
2526
2527
2528
```

```
2529 nav.sidetoc {  
2530     font-family: "DejaVu Serif", "Bitstream Vera Serif",  
2531         "Lucida Bright", Georgia, serif;  
2532     float:right ;  
2533     width: 20%;  
2534     border-left: 1px solid silver;  
2535     border-top: 1px solid silver;  
2536     border-bottom: 1px solid silver;  
2537 /*      border-top: 2px solid #808080 ; */  
2538     background: #FAF7F4 ;  
2539     padding: 2ex 0em 2ex 1em ;  
2540     margin: 0ex 0em 2ex 1em ;  
2541     font-size:.9em ;  
2542     border-radius: 20px 0px 0px 20px ;  
2543 }  
2544  
2545 div.sidetoccontents {  
2546 /*      border-top: 1px solid silver ; */  
2547     overflow-y: auto ;  
2548     width: 100% ;  
2549     text-align: left ;  
2550 }  
2551  
2552  
2553 nav.sidetoc p {line-height:1.2 ; margin: 1ex .5em 1ex .5em ;  
2554     text-indent: 0 ; }  
2555  
2556 nav.sidetoc p a {color:black ; font-size: .7em ;}  
2557  
2558 div.sidetoctitle {font-size: 1.2em; font-weight:bold; text-align:center;  
2559     border-bottom: 1px solid silver ; }  
2560  
2561 nav.sidetoc a:hover {text-decoration: underline ; }  
2562  
2563  
2564  
2565 section.textbody { margin: 0ex 1em 0ex 1em ;}  
2566  
2567  
2568 div.multicolsheading { -webkit-column-span: all;  
2569     -moz-column-span: all; column-span: all; }  
2570 div.multicols { -webkit-columns: 3 380px ;  
2571     -moz-columns: 3 380px ; columns: 3 380px ; }  
2572 div.multicols p {margin-top: 0ex}  
2573  
2574  
2575 /* Used for algorithm2e: */  
2576 div.alg2evline{  
2577     margin-left: 1em ;  
2578     padding-left: 1em ;
```

```
2579     border-left: 1px solid black ;
2580     border-radius: 0px 0px 0px 1ex ;
2581 }
2582
2583 div.alg2evsline{
2584     margin-left: 1em ;
2585     padding-left: 1em ;
2586     border-left: 1px solid black ;
2587 }
2588
2589 div.alg2enoline{
2590     margin-left: 1em ;
2591     padding-left: 1em ;
2592 }
2593
2594 span.alg2elinenumber{
2595     margin-right: .5em ;
2596     font-size: 50% ;
2597     color: red ;
2598 }
2599
2600
2601 /* Used for algorithmicx: */
2602 span.floatright { float: right ; }
2603
2604
2605
2606
2607 /* Native LaTeX theorems: */
2608
2609 .theoremcontents { font-style: italic; margin-top: 3ex ; margin-bottom: 3ex ; }
2610 .theoremlabel { font-style: normal; font-weight: bold ; margin-right: .5em ; }
2611
2612
2613 /* theorem, amsthm, and ntheorem packages */
2614
2615 span.theoremheader,
2616 span.theoremheaderplain,
2617 span.theoremheaderdefinition,
2618 span.theoremheaderbreak,
2619 span.theoremheadermarginbreak,
2620 span.theoremheaderchangebreak,
2621 span.theoremheaderchange,
2622 span.theoremheadermargin
2623 {
2624     font-style: normal ; font-weight: bold ; margin-right: 1em ;
2625 }
2626
2627 span.amsthmnameplain,
2628 span.amsthmnamedefinition,
```

```
2629 span.amsthmnumberplain,
2630 span.amsthmnumberdefinition
2631 {
2632     font-style:normal ; font-weight: bold ;
2633 }
2634
2635
2636 span.amsthmnameremark,
2637 span.amsthmnumberremark
2638 {font-style:italic ; font-weight: normal ; }
2639
2640
2641 span.amsthmnoteplain,
2642 span.amsthmnotedefinition
2643 {font-style:normal ;}
2644
2645
2646 span.theoremheaderremark,
2647 span.theoremheaderproof,
2648 span.amsthmproofname
2649 {font-style:italic ; font-weight: normal ; margin-right: 1em ; }
2650
2651 span.theoremheadersc
2652 {
2653     font-style:normal ;
2654     font-variant: small-caps ;
2655     font-weight: normal ;
2656     margin-right: 1em ;
2657 }
2658
2659 .theoremendmark {float:right}
2660
2661 div.amsthmbodyplain, div.theorembodyplain, div.theorembodynonumberplain,
2662 div.theorembodybreak, div.theorembodynonumberbreak,
2663 div.theorembodymarginbreak,
2664 div.theorembodychangebreak,
2665 div.theorembodychange,
2666 div.theorembodymargin
2667 {
2668     font-style:italic;
2669     margin-top: 3ex ; margin-bottom: 3ex ;
2670 }
2671
2672 div.theorembodydefinition, div.theorembodyremark, div.theorembodyproof,
2673 div.theorembodyplainupright, nonumberplainuprightsc,
2674 div.amsthmbodydefinition, div.amsthmbodyremark,
2675 div.amsthmproof
2676 {
2677     font-style: normal ;
2678     margin-top: 3ex ; margin-bottom: 3ex ;
```

```
2679 }
2680
2681 span.amsthmnoteremark {}
2682
2683
2684 /*
2685 For CSS LaTeX and related logos:
2686 Based on:
2687 http://edward.oconnor.cx/2007/08/tex-poshlet
2688 http://nitens.org/taraborelli/texlogo
2689 */
2690
2691
2692 .latexlogofont {
2693     font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
2694             "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2695     font-variant: normal ;
2696 }
2697
2698 .latexlogo {
2699     font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
2700             "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2701     letter-spacing: .03em ;
2702     font-size: 1.1em;
2703 }
2704
2705 .latexlogo sup {
2706     text-transform: uppercase;
2707     letter-spacing: .03em ;
2708     font-size: 0.85em;
2709     vertical-align: 0.15em;
2710     margin-left: -0.36em;
2711     margin-right: -0.15em;
2712 }
2713
2714 .latexlogo sub {
2715     text-transform: uppercase;
2716     vertical-align: -0.5ex;
2717     margin-left: -0.1667em;
2718     margin-right: -0.125em;
2719     font-size: 1em;
2720 }
2721
2722 .xetexlogo {
2723     font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
2724             "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2725     letter-spacing: .03em ;
2726     font-size: 1.1em;
2727 }
2728
```

```
2729 /* A smaller gap between Xe and Tex v.s. LaTeX: */
2730 .xetexlogo sub {
2731   text-transform: uppercase;
2732   vertical-align: -0.5ex;
2733   margin-left: -0.0667em;
2734   margin-right: -0.2em;
2735   font-size: 1em;
2736   letter-spacing: .03em ;
2737 }
2738
2739 /* A large gap between Xe and LaTeX v.s. TeX: */
2740 .xelatexlogo sub {
2741   text-transform: uppercase;
2742   vertical-align: -0.5ex;
2743   margin-left: -0.0667em;
2744   margin-right: -.05em;
2745   font-size: 1em;
2746   letter-spacing: .03em ;
2747 }
2748
2749 .amslogo {
2750   font-family: "TeXGyreChorus", "URW Chancery L",
2751   "Apple Chancery", "ITC Zapf Chancery", "Monotype Corsiva",
2752   "Linux Libertine O", "Nimbus Roman No 9 L", "FreeSerif",
2753   "Hoefler Text", Times, "Times New Roman", serif;
2754   font-style: italic;
2755 }
2756
2757 .lyxlogo {
2758   font-family: "URW Classico", Optima, "Linux Biolinum O",
2759   "DejaVu Sans", "Bitstream Vera Sans", Geneva,
2760   Verdana, sans-serif ;
2761 }
2762
2763
2764 /* Only display top and bottom navigation if a small screen: */
2765 /* Hide the sidetoc if a small screen: */
2766 nav.topnavigation { display:none; }
2767 nav.botnavigation { display:none; }
2768
2769 @media screen and (max-width: 45em) {
2770 /*     nav.sidetoc {display:none;} */
2771     nav.sidetoc {
2772       float: none ;
2773       width: 100% ;
2774       margin: 5ex 0px 5ex 0px ;
2775       padding: 0 ;
2776       border-radius: 0 ;
2777       border-bottom: 1px solid black ;
2778       border-top: 1px solid black ;
```

```

2779         box-shadow: none ;
2780     }
2781 /*    nav.topnavigation { display:block } */
2782     nav.botnavigation { display:block }
2783     .marginpar {
2784         max-width: 100%;
2785         float: none;
2786         display:block ;
2787         margin: 1ex 1em 1ex 1em ;
2788     }
2789 }
2790
2791 @media print {
2792     body {
2793         font-family: "Linux Libertine O",
2794             "DejaVu Serif", "Bitstream Vera Serif",
2795             "Liberation Serif", "Nimbus Roman No 9 L",
2796             "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2797     }
2798     nav.sidetoc { display:none; }
2799     nav.topnavigation { display: none; }
2800     nav.botnavigation { display: none; }
2801 }
2802
2803 @media handheld {
2804     nav.sidetoc { display:none; }
2805     nav.topnavigation { display:block }
2806     nav.botnavigation { display:block }
2807 }
2808
2809 @media projection {
2810     nav.sidetoc { display:none; }
2811     nav.topnavigation { display:block }
2812     nav.botnavigation { display:block }
2813 }
2814 \end{filecontents*}
2815 % \end{Verbatim} for syntax highlighting
2816 \end{LWRwriteconf}
```

38.5 lwarp_sagebrush.css

File `lwarp_sagebrush.css` An optional css which may be used for a semi-modern appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

Config file: 2817 \begin{LWRwriteconf}
2818 \begin{filecontents*}{lwarp_sagebrush.css}

```
2819 @import url("lwarp.css") ;
2820
2821
2822 A:link {color:#105030 ; text-decoration: none ; }
2823 A:visited {color:#705030 ; text-shadow:1px 1px 2px #a0a0a0;}
2824 A:hover {color:#006000 ; text-decoration: underline ; text-shadow:0px 0px 2px #a0a0a0;}
2825 A:active {color:#00C000 ; text-shadow:1px 1px 2px #a0a0a0;}
2826
2827
2828
2829 h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
2830 {
2831     font-family: "URW Classico", Optima, "Linux Biolinum 0",
2832             "Linux Libertine O", "Liberation Serif",
2833             "Nimbus Roman No 9 L", "FreeSerif",
2834             "Hoefler Text", Times, "Times New Roman", serif;
2835     font-variant: small-caps ;
2836     font-weight: normal ;
2837     color: #304070 ;
2838     text-shadow: 2px 2px 3px #808080;
2839 }
2840
2841 h1 { /* title of the entire website, used on each page */
2842     font-variant: small-caps ;
2843     color: #304070 ;
2844     text-shadow: 2px 2px 3px #808080;
2845     background-color: #F7F7F0 ;
2846     background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C4);
2847 }
2848
2849 h1 {
2850     border-bottom: 1px solid #304070;
2851     border-top: 2px solid #304070;
2852 }
2853
2854 h2 {
2855     border-bottom: 1px solid #304070;
2856     border-top: 2px solid #304070;
2857     background-color: #F7F7F0 ;
2858     background-image: linear-gradient(to bottom, #F7F7F0, #DADOC0);
2859 }
2860
2861
2862
2863 div.abstract {
2864     background: #f5f5eb ;
2865     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
2866
2867     border: 1px solid silver;
2868     border-radius: 1em ;
```

```
2869 }
2870
2871 div.abstract dl {line-height:1.5;}
2872 div.abstract dt {color:#304070;}
2873
2874 div.abstracttitle{
2875     font-family: "URW Classico", Optima, "Linux Biolinum 0",
2876         "Linux Libertine 0", "Liberation Serif", "Nimbus Roman No 9 L",
2877             "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2878     font-weight:bold;
2879     font-variant: small-caps ;
2880     font-size:1.5em;
2881     border-bottom: 1px solid silver ;
2882     color: #304070 ;
2883     text-align: center ;
2884     text-shadow: 1px 1px 2px #808080;
2885 }
2886
2887 span.abstractrunintitle{
2888     font-family: "URW Classico", Optima, "Linux Biolinum 0",
2889         "Linux Libertine 0", "Liberation Serif", "Nimbus Roman No 9 L",
2890             "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2891     font-weight:bold;
2892 }
2893
2894
2895 div.epigraph, div.dictum {
2896     background: #f5f5eb ;
2897     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
2898
2899     border: 1px solid silver ;
2900     border-radius: 1ex ;
2901     box-shadow: 3px 3px 3px #808080 ;
2902 }
2903
2904
2905 .example {
2906     background-color: #f5f5eb ;
2907     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
2908
2909 }
2910
2911 div.examplettitle{
2912     font-family: "URW Classico", Optima, "Linux Biolinum 0",
2913         "Linux Libertine 0", "Liberation Serif", "Nimbus Roman No 9 L",
2914             "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2915     font-weight:bold;
2916     font-variant: small-caps ;
2917     border-bottom: 1px solid silver ;
2918     color: #304070 ;
```

```
2919     text-align: center ;
2920     text-shadow: 1px 1px 2px #808080;
2921 }
2922
2923
2924 .sidebar {
2925     background-color: #f5f5eb ;
2926     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
2927
2928 }
2929
2930 div.sidebartitle{
2931     font-family: "URW Classico", Optima, "Linux Biolinum 0",
2932         "Linux Libertine 0", "Liberation Serif", "Nimbus Roman No 9 L",
2933         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2934     font-weight:bold;
2935     font-variant: small-caps ;
2936     border-bottom: 1px solid silver ;
2937     color: #304070 ;
2938     text-align: center ;
2939     text-shadow: 1px 1px 2px #808080;
2940 }
2941
2942
2943 .fancyvrblabel {
2944     font-family: "URW Classico", Optima, "Linux Biolinum 0",
2945         "Linux Libertine 0", "Liberation Serif", "Nimbus Roman No 9 L",
2946         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2947     font-weight:bold;
2948     font-variant: small-caps ;
2949     font-size: 1.5em ;
2950     color: #304070 ;
2951     text-align: center ;
2952     text-shadow: 1px 1px 2px #808080;
2953 }
2954
2955 div.minipage {
2956     background-color: #eeeeee7 ;
2957     border: 1px solid silver ;
2958     border-radius: 1ex ;
2959 }
2960
2961 table div.minipage { background: none ; border: none ; }
2962
2963 div.framebox div.minipage {border:none ; background:none}
2964
2965 section.textbody > div.minipage {
2966     box-shadow: 3px 3px 3px #808080 ;
2967 }
2968
```

```
2969 div.fboxBlock div.minipage { box-shadow: none ; }
2970
2971 .framed .minipage , .framedleftbar .minipage {
2972     border: none ;
2973     background: none ;
2974     padding: 0ex ;
2975     margin: 0ex ;
2976 }
2977
2978 figure.figure .minipage, figcaption .minipage { border: none; }
2979
2980 div.marginblock div.minipage ,
2981 div.marginparblock div.minipage
2982     { border: none; }
2983
2984 figure , div.marginblock {
2985     background-color: #eeeeee7 ;
2986     border: 1px solid silver ;
2987     border-radius: 1ex ;
2988     box-shadow: 3px 3px 3px #808080 ;
2989 }
2990
2991 figure figure {
2992     border: 1px solid silver ;
2993     margin: 0em ;
2994     box-shadow: none ;
2995 }
2996
2997 /*
2998 figcaption {
2999     border-top: 1px solid silver ;
3000     border-bottom: 1px solid silver ;
3001     background-color: #e8e8e8 ;
3002 }
3003 */
3004
3005
3006 div.table {
3007     box-shadow: 3px 3px 3px #808080 ;
3008 }
3009
3010 /*
3011 .tnotes {
3012     background: #e8e8e8;
3013     border: 1px solid silver;
3014 }
3015 */
3016
3017
3018 nav.topnavigation{
```

```
3019     background-color: #b0b8b0 ;
3020     background-image: linear-gradient(to bottom, #e0e0e0, #b0b8b0) ;
3021 }
3022
3023 nav.botnavigation{
3024     background-color: #b0b8b0 ;
3025     background-image: linear-gradient(to top, #e0e0e0, #b0b8b0) ;
3026 }
3027
3028
3029
3030 header{
3031     background-color: #F7F7F0 ;
3032     background-image: linear-gradient(to top, #F7F7F0, #b0b8b0);
3033 }
3034
3035 footer{
3036     background-color: #F7F7F0 ;
3037     background-image: linear-gradient(to bottom, #F7F7F0, #b0b8b0);
3038 }
3039
3040
3041
3042 nav.sidetoc {
3043     background-color: #F7F7F0 ;
3044     background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C0);
3045     box-shadow: 3px 3px 3px #808080 ;
3046     border-radius: 0px 0px 0px 20px ;
3047 }
3048
3049 div.sidetotitle {color: #304070 ; }
3050
3051 nav.sidetoc a:hover {
3052     color:#006000 ;
3053     text-decoration: none ;
3054     text-shadow: 0px 0px 2px #a0a0a0;
3055 }
3056
3057
3058 @media screen and (max-width: 45em) {
3059     nav.sidetoc { border-radius: 0 ; }
3060 }
3061
3062
3063 \end{filecontents*}
3064 % \end{Verbatim}%
3065 % for syntax highlighting
3066 \end{LWRwriteconf}
```

38.6 lwarp_formal.css

File `lwarp_formal.css` An optional css which may be used for a more formal appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

```
Config file: 3066 \begin{LWRwriteconf}
3067 \begin{filecontents*}{lwarp_formal.css}
3068 @import url("lwarp.css") ;
3069
3070
3071
3072 A:link {color:#802020 ; text-decoration:none; }
3073 A:visited {color:#802020 ; text-shadow:none ;}
3074 A:hover {color:#400000 ; text-shadow:none ;}
3075 A:active {color:#C00000 ; text-shadow:none ;}
3076
3077
3078 body {
3079     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3080             "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3081             "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3082             "Times New Roman", serif;
3083     background: #fffcf5;
3084 }
3085
3086 span.textrm {
3087     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3088             "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3089             "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3090             "Times New Roman", serif;
3091 }
3092
3093 span.textsf {
3094     font-family: "DejaVu Sans", "Bitstream Vera Sans",
3095             Geneva, Verdana, sans-serif ;
3096 }
3097
3098
3099
3100 h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
3101 {
3102     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3103             "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3104             "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3105             "Times New Roman", serif;
3106     color: #800000 ;
3107     text-shadow: none ;
```

```
3108 }
3109
3110 h1, h2 {
3111     background-color: #ffffcf5 ;
3112     background-image: none ;
3113     border-bottom: 1px solid #808080;
3114     border-top: 2px solid #808080;
3115 }
3116
3117 div.abstracttitle {
3118     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3119         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3120         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3121         "Times New Roman", serif;
3122     color: black ;
3123     text-shadow: none ;
3124 }
3125
3126 span.abstractrunintitle {
3127     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3128         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3129         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3130         "Times New Roman", serif;
3131     color: black ;
3132     text-shadow: none ;
3133 }
3134
3135 div.abstract { font-size: 100% }
3136
3137 .sidebar {
3138     background: #ffffcf5;
3139     background-image: none ;
3140     margin: 2em 5% 2em 5%;
3141     padding: 0.5em 1em;
3142     border: none ;
3143     border-top : 1px solid silver;
3144     border-bottom : 1px solid silver;
3145     font-size: 90% ;
3146 }
3147
3148 div.sidebartitle{
3149     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3150         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3151         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3152         "Times New Roman", serif;
3153     color: #800000 ;
3154     text-shadow: none ;
3155     border: none ;
3156 }
3157
```

```
3158 .example {
3159     background: #ffffcf5;
3160     background-image: none ;
3161     margin: 2em 5% 2em 5%;
3162     padding: 0.5em 1em;
3163     border: none ;
3164     border-top : 1px solid silver;
3165     border-bottom : 1px solid silver;
3166 }
3167
3168 div.exampletitle{
3169     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3170         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3171         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3172         "Times New Roman", serif;
3173     color: #800000 ;
3174     text-shadow: none ;
3175     border: none ;
3176 }
3177
3178 div.fancyvrblabel{
3179     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3180         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3181         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3182         "Times New Roman", serif;
3183     color: #800000 ;
3184     text-shadow: none ;
3185     border: none ;
3186 }
3187
3188
3189
3190 .verse {
3191     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3192         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3193         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3194         "Times New Roman", serif;
3195 }
3196
3197
3198 figure {
3199     margin: 5ex 5% 5ex 5% ;
3200     padding: 1ex 1em 1ex 1em ;
3201     background-color: #ffffcf5 ;
3202     overflow-x: auto ;
3203     border: none ;
3204 /*     border-top: 1px solid silver; */
3205 /*     border-bottom: 1px solid silver; */
3206 }
3207
```

```
3208
3209 figcaption , .lstlisting {
3210     border: none ;
3211 /*      border-top: 1px solid silver ; */
3212 /*      border-bottom: 1px solid silver ; */
3213     background-color: #ffffcf5 ;
3214 }
3215
3216 .tnotes {
3217     background: #ffffcf5 ;
3218 }
3219
3220 .theorem {
3221     background: none ;
3222 }
3223
3224 .minipage {
3225     background-color: #ffffcf5 ;
3226     border: none ;
3227 }
3228
3229 div.floatrow figure { border: none ; }
3230
3231 figure figure { border: none ; }
3232
3233
3234 nav.toc, nav.lof, nav.lot, nav.loi {
3235     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3236         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3237         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3238         "Times New Roman", serif;
3239 }
3240
3241 nav.sidetoc {
3242     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3243         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3244         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3245         "Times New Roman", serif;
3246     background-image: linear-gradient(to bottom, #ffffcf5, #COCOCO);
3247     border-radius: 0px 0px 0px 20px ;
3248 }
3249
3250 div.sidetoctitle{
3251     color: #800000 ;
3252 }
3253
3254 header{
3255     background-color: #e0e0e0 ;
3256     background-image: linear-gradient(to top, #ffffcf5, #b0b0b0);
3257     text-align:center ;
```

```

3258 }
3259
3260 footer{
3261     background-color: #e0e0e0 ;
3262     background-image: linear-gradient(to bottom, #ffffcf5, #b0b0b0);
3263     padding: 2ex 1em 2ex 1em ;
3264     clear:right ;
3265     text-align:left ;
3266 }
3267
3268 nav.botnavigation {
3269     background: #dedcd5 ;
3270     border-top: 1px solid black ;
3271 }
3272 \end{filecontents*}
3273 % \end{Verbatim}%
3274 \end{LWRwriteconf}
```

38.7 sample_project.css

File `sample_project.css` The project-specific css file. Use with `\CSSFilename`.

If used, this must be present both when compiling the project and also when distributing the HTML files.

Config file:

```

3275 \begin{LWRwriteconf}
3276 \begin{filecontents*}{sample_project.css}
3277 /* ( --- Start of project.css --- ) */
3278 /* ( --- A sample project-specific CSS file for lwarp --- ) */
3279
3280 /* Uncomment one of the following: */
3281 @import url("lwarp.css") ;
3282 /* @import url("lwarp_formal.css") ; */
3283 /* @import url("lwarp_sagebrush.css") ; */
3284
3285 /* Project-specific CSS setting follow here. */
3286 /* . . . */
3287
3288 /* ( --- End of project.css --- ) */
3289 \end{filecontents*}
3290 % \end{Verbatim}%
3291 \end{LWRwriteconf}
```

38.8 lwarp.ist

File `lwarp.ist` Used to modify the index for `lwarp`.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

The page compositor line is for **memoir**'s \specialindex.

```
Config file: 3292 \begin{LWRwriteconf}
3293 \begin{filecontents*}{lwarf.ist}
3294 preamble
3295 "\\begin{theindex}
3296   \\providecommand*\\lettergroupDefault[1]{}
3297   \\providecommand*\\lettergroup[1]{%
3298     \\par\\textbf{\#1}\\par
3299     \\nopagebreak
3300   }
3301 "
3302 headings_flag 1
3303 heading_prefix "
3304   \\lettergroup{
3305 heading_suffix "}"
3306 delim_0 ", \\hyperindexref{"
3307 delim_1 ", \\hyperindexref{"
3308 delim_2 ", \\hyperindexref{"
3309 delim_n "}, \\hyperindexref{"
3310 delim_r "} -- \\hyperindexref{"
3311 delim_t "}"
3312 page_compositor "."
3313 \end{filecontents*}
3314 % \end{Verbatim} for syntax highlighting
3315 \end{LWRwriteconf}
```

38.9 lwarf.xdy

File **lwarf.xdy** Used to modify the index for **lwarf**.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

See:

[https://tex.stackexchange.com/questions/80300/
how-can-i-convince-hyperref-and-xindy-to-play-together-nicely](https://tex.stackexchange.com/questions/80300/how-can-i-convince-hyperref-and-xindy-to-play-together-nicely)

```
Config file: 3316 \begin{LWRwriteconf}
3317 \begin{filecontents*}{lwarf.xdy}
3318 (require "tex/inputenc/latin.xdy")
3319 (merge-rule "\PS *" "Postscript")
3320 (require "texindy.xdy")
3321 (require "page-ranges.xdy")
3322 (require "book-order.xdy")
```

```

3323 (define-location-class "arabic-page-numbers"
3324   ("arabic-numbers") :min-range-length 1)
3325 (require "makeindex.xdy")
3326 (define-attributes ((hyperindexref)))
3327 (markup-locref :open "\hyperindexref{" :close "}")
3328 (markup-locref :open "\hyperindexref{" :close "}" :attr "hyperpage")
3329 (markup-locref :open "\textbf{\hyperindexref{" :close "}}" :attr "textbf")
3330 (markup-locref :open "\textit{\hyperindexref{" :close "}}" :attr "textit")
3331 (define-location-class-order ("roman-page-numbers"
3332           "arabic-page-numbers"
3333           "alpha-page-numbers"
3334           "Roman-page-numbers"
3335           "Alpha-page-numbers"
3336           "see"
3337           "seealso"))
3338 \end{filecontents*}
3339 % \end{Verbatim}%
3340 \end{LWRwriteconf}

```

38.10 lwarf_one_limage.cmd

File `lwarf_one_limage.cmd` Used by **lwarf** to help make `lateximages` when using WINDOWS.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

The arguments are each of the three fields from `lateximages.txt`, and also the base name of the source file.

MiKTeX does not allow file `lwarf_one_limage.cmd` to be created directly by **lwarpmk**, so `lwarf_one_limage.txt` is created instead, then copied to `lwarf_one_limage.cmd` by **lwarpmk**. This occurs each time **lwarpmk** used to create `lateximages`.

Config file:

```

3341 \begin{LWRwriteconf}
3342 \begin{filecontents*}{lwarf_one_limage.txt}
3343 @echo off
3344 pdfseparate -f %1 -l %1 %4_html.pdf lateximages\lateximagetemp-\%d.pdf
3345 pdfcrop --hires lateximages\lateximagetemp-\%1.pdf lateximages\%3.pdf
3346 pdftocairo -svg -noshrink lateximages\%3.pdf lateximages\%3.svg
3347 del lateximages\%3.pdf
3348 del lateximages\lateximagetemp-\%1.pdf
3349 exit
3350 \end{filecontents*}
3351 \end{LWRwriteconf}

```

38.11 lwarf_mathjax.txt

File lwarf_mathjax.txt Used by **lwarf** when using MATHJAX.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

```

Config file: 3352 \begin{LWRwriteconf}
3353 \begin{filecontents*}{lwarf_mathjax.txt}
3354 <!-- https://groups.google.com/forum/#!topic/
3355           mathjax-users/jUtewUcE2bY -->
3356 <script type="text/x-mathjax-config">
3357 MathJax.Hub.Register.StartupHook("TeX AMSmath Ready",function () {
3358     var seteqsectionDefault = {name: "", num: 0};
3359     var seteqsections = {}, seteqsection = seteqsectionDefault;
3360     var TEX = MathJax.InputJax.TeX, PARSE = TEX.Parse;
3361     var AMS = MathJax.Extension["TeX/AMSmath"];
3362     TEX.Definitions.Add({
3363         macros: {
3364             seteqsection: "mySection",
3365             seteqnumber: "mySetEqNumber"
3366         }
3367     });
3368
3369     PARSE.Augment({
3370         mySection: function (name) {
3371             seteqsection.num = AMS.number;
3372             var n = this.GetArgument(name);
3373             if (n === "") {
3374                 seteqsection = seteqsectionDefault;
3375             } else {
3376                 if (!seteqsections["_"+n])
3377                     seteqsections["_"+n] = {name:n, num:0};
3378                 seteqsection = seteqsections["_"+n];
3379             }
3380             AMS.number = seteqsection.num;
3381         },
3382         mySetEqNumber: function (name) {
3383             var n = this.GetArgument(name);
3384             if (!n || !n.match(/^\d+$/))
3385                 n = "";
3386             else
3387                 n = parseInt(n)-1;
3388             <!-- $ syntax highlighting -->
3389             if (n === "" || n < 1)
3390                 TEX.Error
3391                     ("Argument to "+name+" should be a positive integer");
3392             AMS.number = n;
3393     })

```

```

3394     });
3395     MathJax.Hub.Config({
3396       TeX: {
3397         equationNumbers: {
3398           formatTag: function (n) {
3399             <!-- if not numeric, don't include the chapter --&gt;
3400             if (!n.match(/^\ *[0-9]+\ *$/ ))
3401               <!-- $ syntax highlighting --&gt;
3402               return "("+(n).replace(/\.\./,"")+"")" ;
3403             else
3404               return "("+(seteqsection.name+"."+n).replace(/\.\./,"")+"")" ;
3405           },
3406           formatID: function (n) {
3407             n = (seteqsection.name+'.'+n).replace
3408               (/[:]'&lt;&gt;&amp;]/g,"").replace(/\.\./,"");
3409             return 'mjax-eqn-' + n;
3410           }
3411         }
3412       }
3413     });
3414 });
3415 &lt;/script&gt;
3416
3417 &lt;!-- http://docs.mathjax.org/en/latest/options/ThirdParty.html --&gt;
3418 &lt;script type="text/x-mathjax-config"&gt;
3419   MathJax.Ajax.config.path["Contrib"] =
3420     "https://cdn.mathjax.org/mathjax/contrib";
3421 &lt;/script&gt;
3422
3423 &lt;!-- https://github.com/burnpanck/MathJax-siunitx --&gt;
3424
3425 &lt;script type="text/x-mathjax-config"&gt;
3426   MathJax.Hub.Config({
3427     extensions: ["tex2jax.js","[siunitx]/siunitx.js"],
3428     jax: ["input/TeX","output/HTML-CSS"],
3429     tex2jax: {
3430       inlineMath: [[["$","$"],["\\(","\\)"]]] ,
3431       processClass: "tabbing|verse"
3432     },
3433     TeX: {extensions: ["AMSmath.js","AMSSymbols.js", "sinuitx.js"]}
3434   });
3435   MathJax.Ajax.config.path['siunitx'] = 'http://rawgit.com/burnpanck/MathJax-siunitx/master/';
3436 &lt;/script&gt;
3437
3438 &lt;script type="text/x-mathjax-config"&gt;
3439   MathJax.Hub.Config({
3440     TeX: {
3441       equationNumbers: {
3442         autoNumber: "AMS"
3443     }
</pre>

```

```

3444      }
3445 });
3446 </script>
3447
3448 <!-- Alternative CDN provider: -->
3449 <script type="text/javascript" async
3450 src="https://cdnjs.cloudflare.com/ajax/libs/mathjax/2.7.4/MathJax.js?config=TeX-AMS_HTML-full">
3451 </script>
3452
3453 <!-- No longer supported after April 30, 2017: -->
3454 <!--
3455 <script
3456   src="https://cdn.mathjax.org/mathjax/latest/MathJax.js?config=TeX-AMS_HTML-full">
3457 </script>
3458 -->
3459
3460 \end{filecontents*}
3461 % \end{Verbatim}%
3462 \end{LWRwriteconf}

```

38.12 lwarpmk.lua — lwarpmk option

Opt **lwarpmk** Creates a local copy of **lwarpmk**.

Prog **lwarpmk** Command-line utility to process **l warp** files and images.

parallel processing `lateximages` and `SVG` math images are generated using multiple processes in parallel. For `UNIX` and `LINUX`, every 32 images the `wait` command is issued to wait for the previous batch of images to finish processing before starting a new batch. For `WINDOWS`, every 32 images one task is dispatched with

```
START /B /WAIT /BELOWNORMAL
```

which causes the operating system to wait until this lesser-priority tasks finishes, hopefully also waiting for the normal priority tasks which were already in progress to also complete. Afterwards, the next batch of images is started.

The following is only generated if the `lwarpmk` option was given to `l warp`.

```

3463 \begin{LWR@createlwarpmk}

3464 \begin{filecontents*}{lwarpmk.lua}
3465 #!/usr/bin/env texlua
3466
3467 -- Copyright 2016-2018 Brian Dunn
3468
3469

```

```
3470 printversion = "v0.61"
3471 requiredconfversion = "1" -- also at *lwarpmk.conf
3472
3473 function printhelp ()
3474 print ("lwarpmk: Use lwarpmk -h or lwarpmk --help for help.") ;
3475 end
3476
3477
3478 function printusage ()
3479 --
3480 -- Print the usage of the lwarpmk command:
3481 --
3482 print ( [[
3483
3484 lwarpmk print [-p project]: Compile the print version if necessary.
3485 lwarpmk print1 [-p project]: Forced single compile of the print version.
3486 lwarpmk printindex [-p project]: Process print indexes.
3487 lwarpmk printglossary [-p project]: Process the glossary for the print version.
3488 lwarpmk html [-p project]: Compile the HTML version if necessary.
3489 lwarpmk html1 [-p project]: Forced single compile of the HTML version.
3490 lwarpmk htmlindex [-p project]: Process HTML indexes.
3491 lwarpmk htmlglossary [-p project]: Process the glossary for the html version.
3492 lwarpmk again [-p project]: Touch the source code to trigger recompiles.
3493 lwarpmk limages [-p project]: Process the "lateximages" created by lwarf.sty.
3494 lwarpmk pdftohtml [-p project]:
3495     For use with latexmk or a Makefile:
3496     Converts project_html.pdf to project_html.html and individual HTML files.
3497     Finishes the HTML conversion even if there was a compile error.
3498 lwarpmk pdftosvg <list of file names>: Converts each PDF file to SVG.
3499 lwarpmk epstopdf <list of file names>: Converts each EPS file to PDF.
3500 lwarpmk clean [-p project]: Remove .aux, .toc, .lof/t, .idx, .ind, .log, *_html_inc.*., .gl*
3501 lwarpmk cleanall [-p project]: Remove auxiliary files and also project.pdf, *.html
3502 lwarpmk cleanlimages: Removes all images from the "lateximages" directory.
3503 lwarpmk -h: Print this help message.
3504 lwarpmk --help: Print this help message.
3505
3506 ]] )
3507 -- printconf ()
3508 end
3509
3510
3511 function splitfile (destfile,sourcefile)
3512 --
3513 -- Split one large sourcefile into a number of files,
3514 -- starting with destfile.
3515 -- The file is split at each occurrence of <!--|Start file|newfilename|*
3516 --
3517 print ("lwarpmk: Splitting " .. sourcefile .. " into " .. destfile) ;
3518 local sfile = io.open(sourcefile)
3519 io.output(destfile)
```

```
3520 for line in sfile.readlines() do
3521 i,j,copen,cstart,newfilename = string.find (line,"(.*)|(.*)|(.*)|") ;
3522 if ( (i~= nil) and (copen == "<!--") and (cstart == "Start file")) then
3523     -- split the file
3524     io.output(newfilename) ;
3525 else
3526     -- not a splitpoint
3527     io.write (line .. "\n") ;
3528 end -- do
3529 end io.close(sfile)
3531 end -- function
3532
3533
3534 function cvalueerror ( line, linenum , cvalue )
3535 --
3536 -- Incorrect value, so print an error and exit.
3537 --
3538     print ("lwarpmk: ===")
3539     print ("lwarpmk: " .. linenum .. " : " .. line ) ;
3540     print (
3541         "lwarpmk: incorrect variable value \""
3542         .. cvalue ..
3543         "\" in lwarpmk.conf.\n"
3544     ) ;
3544     print ("lwarpmk: ===")
3545 --     printconf () ;
3546     os.exit(1) ;
3547 end
3548
3549
3550 function ignoreconf ()
3551 -- Global argument index
3552 argindex = 2
3553 end
3554
3555 function loadconf ()
3556 --
3557 -- Load settings from the project's "lwarpmk.conf" file:
3558 --
3559 -- Default configuration filename:
3560 local conffile = "lwarpmk.conf"
3561 local confroot = "lwarpmk"
3562 -- Global argument index
3563 argindex = 2
3564 -- Optional configuration filename:
3565 if ( arg[argindex] == "-p" ) then
3566     argindex = argindex + 1
3567     confroot = arg[argindex]
3568     conffile = confroot.."lwarpmkconf"
3569     argindex = argindex + 1
```

```
3570 end
3571 -- Additional defaults:
3572 confversion = "0"
3573 opsystem = "Unix"
3574 latexmk = "false"
3575 printlatexcmd = ""
3576 HTMLlatexcmd = ""
3577 printindexcmd = ""
3578 HTMLindexcmd = ""
3579 latexmkindexcmd = ""
3580 -- to be removed:
3581 -- indexprog = "makeindex"
3582 -- makeindexstyle = "lwarf.ist"
3583 -- xindylanguage = "english"
3584 -- xindycodepage = "utf8"
3585 -- xindystyle = "lwarf.xdy"
3586 -- pdftotextenc = "UTF-8"
3587 glossarycmd = "makeglossaries"
3588 -- Verify the file exists:
3589 if (lfs.attributes(conffile,"mode")==nil) then
3590     -- file not exists
3591     print ("lwarpmk: ===")
3592     print ("lwarpmk: File \" .. conffile .. \" does not exist.")
3593     print ("lwarpmk: Move to the project's source directory,")
3594     print ("lwarpmk: recompile using pdflatex, xelatex, or lualatex,")
3595     print ("lwarpmk: then try using lwarpmk again.")
3596     if ( arg[argindex] ~= nil ) then
3597         print (
3598             "lwarpmk: (\" .. confroot ..
3599             \" does not appear to be a project name.)"
3600         )
3601     end
3602     print ("lwarpmk: ===")
3603     printhelp () ;
3604     os.exit(1) -- exit the entire lwarpmk script
3605 else -- file exists
3606 -- Read the file:
3607 print ("lwarpmk: Reading \" .. conffile .. \"")
3608 local cfile = io.open(conffile)
3609 -- Scan each line, parsing each line as: name = [[string]]
3610 local linenum = 0
3611 for line in cfile:lines() do -- scan lines
3612     linenum = linenum + 1
3613     i,j,cvarname,cvalue = string.find (line, "(%w_*)%s*=%s*%[%(([^%])*)%]%" ) ;
3614 -- Error if incorrect enclosing characters:
3615     if ( i == nil ) then
3616         print ("lwarpmk: ===")
3617         print ("lwarpmk: " .. linenum .. " : " .. line ) ;
3618         print ("lwarpmk: Incorrect entry in " .. conffile .. ".\n" ) ;
3619         print ("lwarpmk: ===")
```

```
3620 --     printconf () ;
3621     os.exit(1) ;
3622 end -- nil
3623 if ( cvarname == "confversion" ) then
3624     confversion = cvalue
3625 elseif ( cvarname == "opsystem" ) then
3626     -- Verify choice of opsystem:
3627     if ( (cvalue == "Unix") or (cvalue == "Windows") ) then
3628         opsystem = cvalue
3629     else
3630         cvalueerror ( line, linenum , cvalue )
3631     end
3632 elseif ( cvarname == "sourcename" ) then sourcename = cvalue
3633 elseif ( cvarname == "homehtmlfilename" ) then homehtmlfilename = cvalue
3634 elseif ( cvarname == "htmlfilename" ) then htmlfilename = cvalue
3635 elseif ( cvarname == "latexmk" ) then latexmk = cvalue
3636 elseif ( cvarname == "printlatexcmd" ) then printlatexcmd = cvalue
3637 elseif ( cvarname == "HTMLLatexcmd" ) then HTMLLatexcmd = cvalue
3638 elseif ( cvarname == "printindexcmd" ) then printindexcmd = cvalue
3639 elseif ( cvarname == "HTMLIndexcmd" ) then HTMLIndexcmd = cvalue
3640 elseif ( cvarname == "latexmkindexcmd" ) then latexmkindexcmd = cvalue
3641 elseif ( cvarname == "glossarycmd" ) then glossarycmd = cvalue
3642 elseif ( cvarname == "pdftotextenc" ) then pdftotextenc = cvalue
3643 else
3644     print ("lwarpmk: ===")
3645     print ("lwarpmk: " .. linenum .. " : " .. line ) ;
3646     print (
3647         "lwarpmk: Incorrect variable name \"\" .. cvarname .. \"\" in " ..
3648         conffile .. ".\n"
3649     ) ;
3650     print ("lwarpmk: ===")
3651 --     printconf () ;
3652 os.exit(1) ;
3653 end -- cvarname
3654 end -- do scan lines
3655 io.close(cfile)
3656 end -- file exists
3657 -- Error if sourcename is "lwarp".
3658 -- This could happen if a local copy of lwarp has recently been recompiled.
3659 if sourcename=="lwarp" then
3660     print ("lwarpmk: ===")
3661     print ("lwarpmk: lwarp.sty has recently been recompiled in this directory,")
3662     print ("lwarpmk: and \"lwarpmk.conf\" is no longer set for your own project.")
3663     print ("lwarpmk: Recompile your own project using pdf/lua/xelatex <projectname>.")
3664     print ("lwarpmk: After a recompile, \"lwarpmk.conf\" will be set for your project,")
3665     print ("lwarpmk: and you may again use lwarpmk.")
3666     print ("lwarpmk: ===")
3667     os.exit(1)
3668 end -- sourcename of "lwarp"
3669 -- Select some operating-system commands:
```

```
3670 if opsystem=="Unix" then -- For Unix / Linux / Mac OS:
3671     rmname = "rm"
3672     mvname = "mv"
3673     cpname = "cp"
3674     touchnamepre = "touch"
3675     touchnamepost = ""
3676     newtouchname = "touch"
3677     dirslash = "/"
3678     opquote= "\`"
3679     cmdgroupopenname = " ( "
3680     cmdgroupclosename = " ) "
3681     seqname = " && "
3682     bgname = " &"
3683 elseif opsystem=="Windows" then -- For Windows
3684     rmname = "DEL"
3685     mvname = "MOVE"
3686     cpname = "COPY"
3687     touchnamepre = "COPY /b"
3688     touchnamepost = "+,,"
3689     newtouchname = "echo empty >"
3690     dirslash = "\\\""
3691     opquote= "\\""
3692     cmdgroupopenname = ""
3693     cmdgroupclosename = ""
3694     seqname = " & "
3695     bgname = ""
3696 else
3697     print ("lwarpmk: ===")
3698     print ("lwarpmk: Select Unix or Windows for opsystem." )
3699     print ("lwarpmk: ===")
3700     os.exit(1)
3701 end --- for Windows
3702 -- Warning if the operating system does not appear to be correct,
3703 -- in case files were transferred to another system.
3704 if ( (package.config:sub(1,1)) ~= dirslash ) then
3705     print ("lwarpmk: ===")
3706     print ("lwarpmk: It appears that lwarpmk.conf is for a different operating system." )
3707     print ("lwarpmk: To adjust lwarpmk.conf for the current operating system," )
3708     print ("lwarpmk: recompile the original document using xe/lua/pdflatex." )
3709     print ("lwarpmk: ")
3710     print ("lwarpmk: lwarpmk shall attempt to continue...")
3711     print ("lwarpmk: ===")
3712 end
3713 -- Error if the configuration file's version is not current:
3714 if ( confversion ~= requiredconfversion ) then
3715     print ("lwarpmk: ===")
3716     print ("lwarpmk: The configuration files lwarpmk.conf and "..sourcename.."lwarpmkconf" )
3717     print ("lwarpmk: must be updated. To update the configuration files," )
3718     print ("lwarpmk: recompile "..sourcename.."tex using xe/lua/pdflatex," )
3719     print ("lwarpmk: then use lwarpmk again.")
```

```
3720     print ("lwarpmk: ===")
3721     os.exit(1)
3722 end
3723 end -- loadconf
3724
3725
3726 function executecheckerror ( executecommands , errormessage )
3727 --
3728 -- Execute an operating system call,
3729 -- and maybe exit with an error message.
3730 --
3731 local err
3732 err = os.execute ( executecommands )
3733 if ( err ~= 0 ) then
3734     print ("lwarpmk: ===")
3735     print ("lwarpmk: " .. errormessage )
3736     print ("lwarpmk: ===")
3737     os.exit(1)
3738 end
3739 end -- executecheckerror
3740
3741
3742 function refreshdate ()
3743 os.execute(touchnamepre .. " " .. sourcename .. ".tex" .. touchnamepost)
3744 end
3745
3746
3747
3748 function reruntoget (filesource)
3749 --
3750 -- Scan the LaTeX log file for the phrase "Rerun to get",
3751 -- indicating that the file should be compiled again.
3752 -- Return true if found.
3753 --
3754 local fsource = io.open(filesource)
3755 for line in fsource:lines() do
3756 if ( string.find(line,"Rerun to get") ~= nil ) then
3757     io.close(fsource)
3758     return true
3759 end -- if
3760 end -- do
3761 io.close(fsource)
3762 return false
3763 end
3764
3765
3766
3767 function onetime (latexcmd, fsuffix)
3768 --
3769 -- Compile one time, return true if should compile again.
```

```
3770 -- fsuffix is "" for print, "_html" for HTML output.
3771 --
3772 print("lwarpmk: Compiling with: " .. latexcmd)
3773 executecheckerror (
3774     latexcmd ,
3775     "Compile error."
3776 )
3777 return (reruntoget(sourcename .. fsuffix .. ".log") ) ;
3778 end
3779
3780
3781 function manytimes (latexcmd, fsuffix)
3782 --
3783 -- Compile up to five times.
3784 -- fsuffix is "" for print, "_html" for HTML output
3785 --
3786 if onetime(latexcmd, fsuffix) == true then
3787 if onetime(latexcmd, fsuffix) == true then
3788 if onetime(latexcmd, fsuffix) == true then
3789 if onetime(latexcmd, fsuffix) == true then
3790 if onetime(latexcmd, fsuffix) == true then
3791 end end end end end
3792 end
3793
3794
3795 function verifyfileexists (filename)
3796 --
3797 -- Exit if the given file does not exist.
3798 --
3799 if (lfs.attributes ( filename , "modification" ) == nil ) then
3800     print ("lwarpmk: ===")
3801     print ("lwarpmk: " .. filename .. " not found." ) ;
3802     print ("lwarpmk: ===")
3803     os.exit (1) ;
3804 end
3805 end
3806
3807
3808
3809 function pdftohtml ()
3810 --
3811 -- Convert <project>_html.pdf into HTML files:
3812 --
3813 -- Convert to text:
3814 print ("lwarpmk: Converting " .. sourcename
3815     .."_html.pdf to " .. sourcename .. "_html.html")
3816 os.execute("pdftotext -enc " .. pdftotextenc .. " -nopgbrk -layout "
3817     .. sourcename .. "_html.pdf " .. sourcename .. "_html.html")
3818 -- Split the result into individual HTML files:
3819 splitfile (homehtmlfilename .. ".html" , sourcename .. "_html.html")
```

```
3820 end
3821
3822
3823 function removeaux ()
3824 --
3825 -- Remove auxiliary files:
3826 -- All .aux files are removed since there may be many bbl*.aux files.
3827 --
3828 os.execute ( rmname .. " *.aux " ..
3829     sourcename .. ".toc" .. sourcename .. "_html.toc" ..
3830     sourcename .. ".lof" .. sourcename .. "_html.lof" ..
3831     sourcename .. ".lot" .. sourcename .. "_html.lot" ..
3832     " *.idx" ..
3833     " *.ind" ..
3834     sourcename .. ".ps" .. sourcename .. "_html.ps" ..
3835     sourcename .. ".log" .. sourcename .. "_html.log" ..
3836     sourcename .. ".gl*" .. sourcename .. "_html.gl*" ..
3837     " *_html_inc.*"
3838   )
3839 end
3840
3841 function checkhtmldpdfexists ()
3842 --
3843 -- Error if the HTML document does not exist.
3844 -- The lateximages are drawn from the HTML PDF version of the document,
3845 -- so "lwarpmk html" must be done before "lwarpmk limages".
3846 --
3847 local htmlpdffile = io.open(sourcename .. "_html.pdf", "r")
3848 if ( htmlpdffile == nil ) then
3849   print ("")
3850   print ("lwarpmk: ===")
3851   print ("lwarpmk: The HTML version of the document does not exist.")
3852   print ("lwarpmk: Enter \"lwarpmk html\" to compile the HTML version.")
3853   print ("lwarpmk: ===")
3854   os.exit(1)
3855 end
3856 io.close (htmlpdffile)
3857 end -- checkhtmldpdfexists
3858
3859
3860 function warnlimages ()
3861 --
3862 -- Warning of a missing lateximages.txt file:
3863 --
3864   print ("lwarpmk: ===")
3865   print ("lwarpmk: \"lateximages.txt\" does not exist.")
3866   print ("lwarpmk: Your project does not use SVG math or other lateximages,")
3867   print ("lwarpmk: or the file has been deleted somehow.")
3868   print ("lwarpmk: Use \"lwarpmk html\" to recompile your project")
3869   print ("lwarpmk: and recreate \"lateximages.txt\".")
```

```
3870     print ("lwarpmk: If your project does not use SVG math or other lateximages,")
3871     print ("lwarpmk: then \"lateximages.txt\" will never exist, and")
3872     print ("lwarpmk: \"lwarpmk limages\" will not be necessary.")
3873     print ("lwarpmk: ===")
3874 end -- warnlimages
3875
3876
3877 function checklimages ()
3878 --
3879 -- Check lateximages.txt to see if need to recompile first.
3880 -- If any entry has a page number of zero, then there were incorrect images.
3881 --
3882 print ("lwarpmk: Checking for a valid lateximages.txt file.")
3883 local limagesfile = io.open("lateximages.txt", "r")
3884 if ( limagesfile == nil ) then
3885     warnlimages ()
3886     os.exit(1)
3887 end
3888 -- Track warning to recompile if find a page 0
3889 local pagezerowarning = false
3890 -- Scan lateximages.txt
3891 for line in limagesfile:lines() do
3892     -- lwimgpage is the page number in the PDF which has the image
3893     -- lwimghash is true if this filename is a hash
3894     -- lwimgname is the lateximage filename root to assign for the image
3895     i,j,lwimgpage,lwimghash,lwimgname = string.find (line,"|(.*)|(.*)|(.*)|")
3896     -- For each entry:
3897     if ( (i~=nil) ) then
3898         -- If the page number is 0, image references are incorrect
3899         -- and must recompile the source document:
3900         if ( lwimgpage == "0" ) then
3901             pagezerowarning = true
3902         end
3903     end -- if i~=nil
3904 end -- do
3905 if ( pagezerowarning ) then
3906     print ("")
3907     print ("lwarpmk: ===")
3908     print ("lwarpmk: The document must be recompiled before creating the lateximages.")
3909     print ("lwarpmk: Enter \"lwarpmk html\" again, then try \"lwarpmk limages\" again.")
3910     print ("lwarpmk: ===")
3911     os.exit(1) ;
3912 end -- pagezerowarning
3913 end -- checklimages
3914
3915
3916 function createuniximage ( lwimgfullname )
3917 --
3918 -- Create one lateximage for Unix / Linux / Mac OS.
3919 --
```

```
3920 executecheckerror (
3921     cmdgroupopenname ..
3922     "pdfseparate -f " .. lwimgpage .. " -l " .. lwimgpage .. " " ..
3923     sourcename .. "_html.pdf" ..
3924     "lateximages" .. dirslash .. "lateximagetemp-%d" .. ".pdf" ..
3925     seqname ..
3926     -- Crop the image:
3927     "pdfcrop --hires lateximages" .. dirslash .. "lateximagetemp-" ..
3928     lwimgpage .. ".pdf" ..
3929     "lateximages" .. dirslash .. lwimgname .. ".pdf" ..
3930     seqname ..
3931     -- Convert the image to svg:
3932     "pdftocairo -svg -noshrink lateximages" .. dirslash .. lwimgname .. ".pdf" ..
3933     "lateximages" .. dirslash .. lwimgname .. ".svg" ..
3934     seqname ..
3935     -- Remove the temporary files:
3936     rmname .. " lateximages" .. dirslash .. lwimgname .. ".pdf" .. seqname ..
3937     rmname .. " lateximages" .. dirslash .. "lateximagetemp-" .. lwimgpage .. ".pdf" ..
3938     cmdgroupclosename .. " >/dev/null " .. bgname
3939 ,
3940     "File error trying to convert " .. lwimgfullname
3941 )
3942 -- Every 32 images, wait for completion at below normal priority,
3943 -- allowing other image tasks to catch up.
3944 numimageprocesses = numimageprocesses + 1
3945 if ( numimageprocesses > 32 ) then
3946     numimageprocesses = 0
3947     print ( "lwarpmk: waiting" )
3948     executecheckerror ( "wait" , "File error trying to wait." )
3949 end
3950 end -- createuniximage
3951
3952
3953 function createwindowsimage ( lwimgfullname )
3954 --
3955 -- Create one lateximage for Windows.
3956 --
3957 -- Every 32 images, wait for completion at below normal priority,
3958 -- allowing other image tasks to catch up.
3959 numimageprocesses = numimageprocesses + 1
3960 if ( numimageprocesses > 32 ) then
3961     numimageprocesses = 0
3962     thiswaitcommand = "/WAIT /BELOWNORMAL"
3963     print ( "lwarpmk: waiting" )
3964 else
3965     thiswaitcommand = ""
3966 end
3967 -- Execute the image generation command
3968 executecheckerror (
3969     "start /B " .. thiswaitcommand .. " \\\" l warp_one_limage " ..
```

```
3970     lwimgpage .. " " ..
3971     lwimghash .. " " ..
3972     lwimgname .. " " ..
3973     sourcename .. " <nul >nul"
3974     ,
3975     "File error trying to create image."
3976 )
3977 end -- createwindowsimage
3978
3979
3980 function createonelateximage ( line )
3981 --
3982 -- Given the next line of lateximages.txt, convert a single image.
3983 --
3984 -- lwimgpage is the page number in the PDF which has the image
3985 -- lwimghash is true if this filename is a hash
3986 -- lwimgname is the lateximage filename root to assign for the image
3987 i,j,lwimgpage,lwimghash,lwimgname = string.find (line,"|(.*)|(.*)|(.*)|")
3988 -- For each entry:
3989 if ( (i~=nil) ) then
3990     -- Skip if the page number is 0:
3991     if ( lwimgpage == "0" ) then
3992         pagezerowarning = true
3993     else
3994         -- Skip if this image is hashed and already exists:
3995         local lwimgfullname = "lateximages" .. dirslash .. lwimgname .. ".svg"
3996         if (
3997             (lwimghash ~= "true") or
3998             (lfs.attributes(lwimgfullname,"mode")==nil) -- file not exists
3999         )
4000         then -- not hashed or not exists:
4001             -- Print the name of the file being generated:
4002             print ( "lwarfpmk: " .. lwimgname )
4003             -- Touch/create the dest so that only once instance tries to build it:
4004             executecheckerror (
4005                 newtouchname .. " " .. lwimgfullname ,
4006                 "File error trying to touch " .. lwimgfullname
4007             )
4008             -- Separate out the image into its own single-page pdf:
4009             if opsystem=="Unix" then
4010                 createuniximage (lwimgfullname)
4011             elseif opsystem=="Windows" then
4012                 createwindowsimage (lwimgfullname)
4013             end
4014             end -- not hashed or not exists
4015         end -- not page 0
4016 end -- not nil
4017 end -- createonelateximage
4018
4019
```

```
4020 function create lateximages ()
4021 --
4022 -- Create lateximages based on lateximages.txt:
4023 --
4024 -- See if the document must be recompiled first:
4025 checklimages ()
4026 -- See if the print version exists:
4027 checkhtmlpdfexists ()
4028 -- Attempt to create the lateximages:
4029 print ("lwarpmk: Creating lateximages.")
4030 local limagesfile = io.open("lateximages.txt", "r")
4031 if ( limagesfile == nil ) then
4032     warnlateximages ()
4033     os.exit(1)
4034 end
4035 -- Create the lateximages directory, ignore error if already exists
4036 err = os.execute("mkdir lateximages")
4037 -- For Windows, create lwarp_one_limage.cmd from lwarp_one_limage.txt:
4038 if opsystem=="Windows" then
4039     executecheckerror (
4040         cpname .. " lwarp_one_limage.txt lwarp_one_limage.cmd" ,
4041         "File error trying to copy lwarp_one_limage.txt to lwarp_one_limage.cmd"
4042     )
4043 end -- create lwarp_one_limage.cmd
4044 -- Track the number of parallel processes
4045 numimageprocesses = 0
4046 -- Track warning to recompile if find a page 0
4047 pagezerowarning = false
4048 -- Scan lateximages.txt
4049 for line in limagesfile:lines() do
4050     createonelateximage ( line )
4051 end -- do
4052 io.close(limagesfile)
4053 print ( "lwarpmk limages: ===" )
4054 print ( "lwarpmk limages: Wait a moment for the images to complete" )
4055 print ( "lwarpmk limages: before reloading the page." )
4056 print ( "lwarpmk limages: ===" )
4057 print ( "lwarpmk limages: Done.." )
4058 if ( pagezerowarning == true ) then
4059     print ( "lwarpmk limages: WARNING: Images will be incorrect." )
4060     print ( "lwarpmk limages: Enter \"lwarpmk cleanimages\", then" )
4061     print ( "lwarpmk limages: recompile the document one more time, then" )
4062     print ( "lwarpmk limages: repeat \"lwarpmk images\" again." )
4063 end -- pagezerowarning
4064 end -- function
4065
4066
4067 function convertepstopdf ()
4068 --
4069 -- Converts EPS files to PDF files.
```

```
4070 -- The filenames are arg[argindex] and up.
4071 -- arg[1] is the command "pdftosvg".
4072 --
4073 ignoreconf ()
4074 for i = argindex , #arg do
4075     if (lfs.attributes(arg[i],"mode")==nil) then
4076         print ("lwarpmk: File \" .. arg[i] .. \" does not exist.")
4077     else
4078         print ("lwarpmk: Converting \" .. arg[i] .. \"")
4079         os.execute ( "epstopdf " .. arg[i] )
4080     end -- if
4081 end -- do
4082 end --function
4083
4084
4085 function convertpdftosvg ()
4086 --
4087 -- Converts PDF files to SVG files.
4088 -- The filenames are arg[argindex] and up.
4089 -- arg[1] is the command "pdftosvg".
4090 --
4091 ignoreconf ()
4092 for i = argindex , #arg do
4093     if (lfs.attributes(arg[i],"mode")==nil) then
4094         print ("lwarpmk: File \" .. arg[i] .. \" does not exist.")
4095     else
4096         print ("lwarpmk: Converting \" .. arg[i] .. \"")
4097         os.execute ( "pdftocairo -svg " .. arg[i] )
4098     end -- if
4099 end -- do
4100 end --function
4101
4102
4103 -- Force an update and conclude processing:
4104 function updateanddone ()
4105 print ("lwarpmk: Forcing an update of " .. sourcename .. ".tex.")
4106 refreshdate ()
4107 print ("lwarpmk: " .. sourcename .. ".tex is ready to be recompiled.")
4108 print ("lwarpmk: Done.")
4109 end -- function
4110
4111
4112 -- Start of the main code: --
4113
4114
4115 -- lwarpmk --version :
4116
4117 if (arg[1] == "--version") then
4118 print ( "lwarpmk: " .. printversion )
4119
```

```
4120 else -- not --version
4121
4122
4123 -- print intro:
4124
4125 print ("lwarpmk: " .. printversion .. " Automated make for the LaTeX lwarf package.")
4126
4127
4128 -- lwarpmk print:
4129
4130 if arg[1] == "print" then
4131 loadconf ()
4132 if ( latexmk == "true" ) then
4133     print ("lwarpmk: Compiling with: " .. printlatexcmd)
4134     executecheckerror (
4135         printlatexcmd ,
4136         "Compile error."
4137     )
4138     print ("lwarpmk: Done.")
4139 else -- not latexmk
4140     verifyfileexists (sourcename .. ".tex") ;
4141     -- See if up to date:
4142     if (
4143         ( lfs.attributes ( sourcename .. ".pdf" , "modification" ) == nil ) or
4144         (
4145             lfs.attributes ( sourcename .. ".tex" , "modification" ) >
4146             lfs.attributes ( sourcename .. ".pdf" , "modification" )
4147         )
4148     ) then
4149         -- Recompile if not yet up to date:
4150         manytimes(printlatexcmd, "")
4151         print ("lwarpmk: Done.") ;
4152     else
4153         print ("lwarpmk: " .. sourcename .. ".pdf is up to date.") ;
4154     end
4155 end -- not latexmk
4156
4157
4158 -- lwarpmk print1:
4159
4160 elseif arg[1] == "print1" then
4161     loadconf ()
4162     verifyfileexists (sourcename .. ".tex") ;
4163     onetime(printlatexcmd, "")
4164     print ("lwarpmk: Done.") ;
4165
4166
4167 -- lwarpmk printindex:
4168 -- Compile the index then touch the source
4169 -- to trigger a recompile of the document:
```

```
4170
4171 elseif arg[1] == "printindex" then
4172 loadconf ()
4173 os.execute ( printindexcmd )
4174 print ("lwarpmk: -----")
4175 updateanddone ()
4176
4177
4178 -- lwarpmk printglossary:
4179 -- Compile the glossary then touch the source
4180 -- to trigger a recompile of the document:
4181
4182 elseif arg[1] == "printglossary" then
4183 loadconf ()
4184 print ("lwarpmk: Processing the glossary.")
4185
4186 os.execute(glossarycmd .. " " .. sourcename)
4187 updateanddone ()
4188
4189
4190 -- lwarpmk html:
4191
4192 elseif arg[1] == "html" then
4193 loadconf ()
4194 if ( latexmk == "true" ) then
4195     print ("lwarpmk: Compiling with: " .. HTMLlatexcmd)
4196     executecheckerror (
4197         HTMLlatexcmd ,
4198         "Compile error."
4199     )
4200     pdftohtml ()
4201     print ("lwarpmk: Done.")
4202 else -- not latexmk
4203     verifyfileexists ( sourcename .. ".tex" ) ;
4204     -- See if exists and is up to date:
4205     if (
4206         ( lfs.attributes ( homehtmlfilename .. ".html" , "modification" ) == nil ) or
4207         (
4208             lfs.attributes ( sourcename .. ".tex" , "modification" ) >
4209             lfs.attributes ( homehtmlfilename .. ".html" , "modification" )
4210         )
4211     ) then
4212         -- Recompile if not yet up to date:
4213         manytimes(HTMLlatexcmd, "_html")
4214         pdftohtml ()
4215         print ("lwarpmk: Done.")
4216     else
4217         print ("lwarpmk: " .. homehtmlfilename .. ".html is up to date.")
4218     end
4219 end -- not latexmk
```

```
4220
4221
4222 -- lwarfpmk html1:
4223
4224 elseif arg[1] == "html1" then
4225     loadconf ()
4226     verifyfileexists ( sourcename .. ".tex" ) ;
4227     onetime(HTMLLatexcmd, "_html")
4228     pdftohtml ()
4229     print ("lwarfpmk: Done.")
4230
4231
4232 -- lwarfpmk pdftohtml:
4233 elseif arg[1] == "pdftohtml" then
4234     loadconf ()
4235     pdftohtml ()
4236
4237
4238 -- lwarfpmk htmlindex:
4239 -- Compile the index then touch the source
4240 -- to trigger a recompile of the document:
4241
4242 elseif arg[1] == "htmlindex" then
4243     loadconf ()
4244     os.execute ( HTMLIndexcmd )
4245     print ("lwarfpmk: -----")
4246     updateanddone ()
4247
4248
4249 -- lwarfpmk htmlglossary:
4250 -- Compile the glossary then touch the source
4251 -- to trigger a recompile of the document.
4252 -- The <sourcename>.xdy file is created by the glossaries package.
4253
4254 elseif arg[1] == "htmlglossary" then
4255     loadconf ()
4256     print ("lwarfpmk: Processing the glossary.")
4257     os.execute(glossarycmd .. " " .. sourcename .. "_html")
4258     updateanddone ()
4259
4260
4261 -- lwarfpmk limages:
4262 -- Scan the lateximages.txt file to create lateximages.
4263
4264 elseif arg[1] == "limages" then
4265     loadconf ()
4266     print ("lwarfpmk: Processing images.")
4267     createlateximages ()
4268     print ("lwarfpmk: Done.")
4269
```

```
4270
4271 -- lwarpmk again:
4272 -- Touch the source to trigger a recompile.
4273
4274 elseif arg[1] == "again" then
4275 loadconf ()
4276 updateanddone ()
4277
4278
4279 -- lwarpmk clean:
4280 -- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.*, .gl*
4281
4282 elseif arg[1] == "clean" then
4283 loadconf ()
4284 removeaux ()
4285 print ("lwarpmk: Done.")
4286
4287
4288 -- lwarpmk cleanall
4289 -- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.*, .gl*
4290 --     and also project.pdf, project.dvi, *.html
4291
4292 elseif arg[1] == "cleanall" then
4293 loadconf ()
4294 removeaux ()
4295 os.execute ( rmname .. " " ..
4296     sourcename .. ".pdf" .. sourcename .. "_html.pdf" ..
4297     sourcename .. ".dvi" .. sourcename .. "_html.dvi" ..
4298     "*.*html"
4299     )
4300 print ("lwarpmk: Done.")
4301
4302
4303 -- lwarpmk cleanimages
4304 -- Remove images from the lateximages directory.
4305
4306 elseif arg[1] == "cleanimages" then
4307 loadconf ()
4308 os.execute ( rmname .. " lateximages/*" )
4309 print ("lwarpmk: Done.")
4310
4311 -- lwarpmk epstopdf <list of file names>
4312 -- Convert EPS files to PDF using epstopdf
4313 elseif arg[1] == "epstopdf" then
4314 convertepstopdf ()
4315 print ("lwarpmk: Done.")
4316
4317
4318 -- lwarpmk pdftosvg <list of file names>
4319 -- Convert PDF files to SVG using pdftocairo
```

```

4320 elseif arg[1] == "pdftosvg" then
4321 convertpdftosvg ()
4322 print ("lwarpmk: Done.")
4323
4324
4325 -- lwarpmk with no argument :
4326
4327 elseif (arg[1] == nil) then
4328 printhelp ()
4329
4330
4331 -- lwarpmk -h or lwarpmk --help :
4332
4333 elseif (arg[1] == "-h" ) or (arg[1] == "--help") then
4334 printusage ()
4335
4336
4337 -- Unknown command:
4338
4339 else
4340 printhelp ()
4341 print ("\nlwarpmk: ***** Unknown command \"..arg[1]..\". *****\n")
4342 end
4343
4344 end -- not --version
4345 \end{filecontents*}
4346 % \end{Verbatim}%
4347 \end{LWR@createlwarpmk}

```

39 Stacks

for HTML output: 4348 \begin{warpHTML}

Stacks are used to remember how to close sections and list items. Before a new section is started, previously nested sections and items must be closed out (un-nested) in proper order. Note that starting a new section may close several levels of previously nested items at the same time. For example, starting a new \section would close any currently open subsection, subsubsection, and paragraph. General environments are not nested on the stack since they have their own close mechanism. List environments are nested, and items inside those environments are nested one level deeper still. List environments may be nested inside other list environments, and list items are nested inside list environments as well. Thus, the stack may have items which are not necessarily in order, since a description may contain an enumerate, for example. Depths to be recorded in \LWR@closedepthone, etc.



39.1 Assigning depths

initial depths for empty stack entries:

```
4349 \newcommand*\{LWR@depthnone\}{-5}
```

all sectioning depths are deeper than LWR@depthfinished:

```
4350 \newcommand*\{LWR@depthfinished\}{-4}
4351 \newcommand*\{LWR@depthpart\}{-1}
4352 \newcommand*\{LWR@depthchapter\}{0}
4353 \newcommand*\{LWR@depthsection\}{1}
4354 \newcommand*\{LWR@depthsubsection\}{2}
4355 \newcommand*\{LWR@depthsubsubsection\}{3}
4356 \newcommand*\{LWR@depthparagraph\}{4}
4357 \newcommand*\{LWR@depth subparagraph\}{5}
```

used by \itemize, \enumerate, \description:

```
4358 \newcommand*\{LWR@depthlist\}{6}
```

used by \item:

```
4359 \newcommand*\{LWR@depthlistitem\}{7}
```

39.2 Closing actions

A stack to record the action to take to close each nesting level: Add more levels of stack if necessary for a very deeply nested document, adding to \pushclose and \popclose as well.

```
4360 \newcommand*\{LWR@closeone\}{}% top of the stack
4361 \newcommand*\{LWR@closetwo\}{}%
4362 \newcommand*\{LWR@closethree\}{}%
4363 \newcommand*\{LWR@closefour\}{}%
4364 \newcommand*\{LWR@closefive\}{}%
4365 \newcommand*\{LWR@closesix\}{}%
4366 \newcommand*\{LWR@closeseven\}{}%
4367 \newcommand*\{LWR@closeeight\}{}%
4368 \newcommand*\{LWR@closenine\}{}%
4369 \newcommand*\{LWR@closeten\}{}%
4370 \newcommand*\{LWR@closeeleven\}{}%
4371 \newcommand*\{LWR@closetwelve\}{}%
```

39.3 Closing depths

A stack to record the depth of each level:

-  Note that nested L^AT_EX structures may push depths which are non-sequential.

Ex:

```
\begin{itemize}
  \item{A}
    \begin{description}
      \item{B}
    \end{description}
\end{itemize}
```

```
4372 \newcommand*{\LWR@closedepthonen}{\LWR@depthnone}%
4373 \newcommand*{\LWR@closedepthtwo}{\LWR@depthnone}%
4374 \newcommand*{\LWR@closedepththree}{\LWR@depthnone}%
4375 \newcommand*{\LWR@closedepthfour}{\LWR@depthnone}%
4376 \newcommand*{\LWR@closedepthfive}{\LWR@depthnone}%
4377 \newcommand*{\LWR@closedepthsix}{\LWR@depthnone}%
4378 \newcommand*{\LWR@closedepthseven}{\LWR@depthnone}%
4379 \newcommand*{\LWR@closedeptheight}{\LWR@depthnone}%
4380 \newcommand*{\LWR@closedepthnine}{\LWR@depthnone}%
4381 \newcommand*{\LWR@closedepthten}{\LWR@depthnone}%
4382 \newcommand*{\LWR@closedeptheleven}{\LWR@depthnone}%
4383 \newcommand*{\LWR@closedepthtwelve}{\LWR@depthnone}
```

39.4 Pushing and popping the stack

```
\pushclose {<action>} {<depth>}
```

Pushes one return action and its L^AT_EX depth onto the stacks.

```
4384 \NewDocumentCommand{\pushclose}{m m}
4385 {
4386 \global\let\LWR@closetwelve\LWR@closeeleven
4387 \global\let\LWR@closeeleven\LWR@closeten
4388 \global\let\LWR@closeten\LWR@closenine
4389 \global\let\LWR@closenine\LWR@closeeight
4390 \global\let\LWR@closeeight\LWR@closeseven
4391 \global\let\LWR@closeseven\LWR@closesix
4392 \global\let\LWR@closesix\LWR@closefive
```

```

4393 \global\let\LWR@closefive\LWR@closefour
4394 \global\let\LWR@closefour\LWR@closethree
4395 \global\let\LWR@closethree\LWR@closetwo
4396 \global\let\LWR@closetwo\LWR@closeone
4397 \global\let\LWR@closeone#1
4398 \global\let\LWR@closedephtwelve\LWR@closedeptheleven
4399 \global\let\LWR@closedeptheleven\LWR@closedepthten
4400 \global\let\LWR@closedepthten\LWR@closedepthnine
4401 \global\let\LWR@closedepthnine\LWR@closedeptheight
4402 \global\let\LWR@closedeptheight\LWR@closedepthseven
4403 \global\let\LWR@closedepthseven\LWR@closedepthsix
4404 \global\let\LWR@closedepthsix\LWR@closedepthfive
4405 \global\let\LWR@closedepthfive\LWR@closedepthfour
4406 \global\let\LWR@closedepthfour\LWR@closedepththree
4407 \global\let\LWR@closedepththree\LWR@closedepthtwo
4408 \global\let\LWR@closedepthtwo\LWR@closedepthonne
4409 \global\let\LWR@closedepthonne#2
4410 }

```

\popclose Pops one action and its depth off the stacks.

```

4411 \newcommand*{\popclose}
4412 {
4413 \global\let\LWR@closeone\LWR@closetwo
4414 \global\let\LWR@closetwo\LWR@closethree
4415 \global\let\LWR@closethree\LWR@closefour
4416 \global\let\LWR@closefour\LWR@closefive
4417 \global\let\LWR@closefive\LWR@closesix
4418 \global\let\LWR@closesix\LWR@closeseven
4419 \global\let\LWR@closeseven\LWR@closeeight
4420 \global\let\LWR@closeeight\LWR@closenine
4421 \global\let\LWR@closenine\LWR@closeten
4422 \global\let\LWR@closeten\LWR@closeeleven
4423 \global\let\LWR@closeeleven\LWR@closetwelve
4424 \global\let\LWR@closedepthonne\LWR@closedepthtwo
4425 \global\let\LWR@closedepthtwo\LWR@closedepththree
4426 \global\let\LWR@closedepththree\LWR@closedepthfour
4427 \global\let\LWR@closedepthfour\LWR@closedepthfive
4428 \global\let\LWR@closedepthfive\LWR@closedepthsix
4429 \global\let\LWR@closedepthsix\LWR@closedepthseven
4430 \global\let\LWR@closedepthseven\LWR@closedeptheight
4431 \global\let\LWR@closedeptheight\LWR@closedepthnine
4432 \global\let\LWR@closedepthnine\LWR@closedepthten
4433 \global\let\LWR@closedepthten\LWR@closedeptheleven
4434 \global\let\LWR@closedeptheleven\LWR@closedepthtwelve
4435 }

```

```
4436 \end{warpHTML}
```

40 Data arrays

These macros are similar to the `arrayjobx` package, except that `\LWR@setexparray`'s argument is expanded only once when assigned.

`name` has no backslash, `index` can be a number or a text name, and an empty `value` must be `\relax` instead of empty.

To assign an empty value:

```
\LWR@setexparray{name}{index}{}{}
```

for HTML output: 4437 `\begin{warpHTML}`

```
\LWR@setexparray {<name>} {<index>} {<contents>}

4438 \NewDocumentCommand{\LWR@setexparray}{m m m}{%
4439   \xdef\LWR@thisexparrayname{#1#2}%
4440   \ifstrempty{#3}%
4441     {\csgdef{\LWR@thisexparrayname}{}{}}%
4442     {\csxdef{\LWR@thisexparrayname}{#3}{}}%
4443 }
```



```
\LWR@getexparray {<name>} {<index>}

4444 \newcommand*{\LWR@getexparray}[2]{%
4445   \nameuse{#1#2}%
4446 }
```



```
4447 \end{warpHTML}
```

41 Localizing catcodes

for HTML & PRINT: 4448 `\begin{warpall}`

 **Misplaced alignment tab character &** Place `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros or environments which include the tabular & character in their definitions.

The catcode of & must be changed before the definitions begin, and must be restored afterwards. Doing so avoids the error

Misplaced alignment tab character &.

\StartDefiningTabulars Place before defining something with & in it.

```
4449 \newcommand{\StartDefiningTabulars}{%
4450 \LWR@traceinfo{StartDefiningTabulars}%
4451 \warpHTMLonly{\catcode`\&=\active}%
4452 }
```

\StopDefiningTabulars Place after defining something with & in it.

```
4453 \newcommand{\StopDefiningTabulars}{%
4454 \LWR@traceinfo{StopDefiningTabulars}%
4455 \warpHTMLonly{\catcode`\&=4}%
4456 }
```

Bool LWR@mathmacro True if currently defining math macros. Used to disable SVG math hashing and MathJax math contents while defining a macro using inline math. Begin a macro, it is not guaranteed that the contents are static, and so the image must be unique. The contents also almost certainly will not be parsed correctly by MathJax.

```
4457 \newbool{LWR@mathmacro}
4458 \boolfalse{LWR@mathmacro}
```

\StartDefiningMath Place before defining something with \$ in it.

```
4459 \newcommand{\StartDefiningMath}{%
4460 \LWR@traceinfo{StartDefiningMath}%
4461 \warpHTMLonly{\catcode`\$=\active}%
4462 }
```

\StopDefiningMath Place after defining something with \$ in it.

```
4463 \newcommand{\StopDefiningMath}{%
4464 \LWR@traceinfo{StopDefiningMath}%
4465 \warpHTMLonly{\catcode`\$=3}% math shift
4466 }

4467 \end{warpall}
```

42 Localizing dynamic math

Inline SVG math usually uses a hash of its contents to generate `lateximages` which are reusable for multiple instances with the same contents. If the contents

may change for each use, such as depending on the current value of a counter, then `\inlinemathother` must be used before the inline math expression, and `\inlinemathnormal` must be used after.

For MathJax, the inline math expression is usually printed for MathJax to interpret. When marked as dynamic math, the following inline math expression will be displayed as an unhashed inline SVG image instead.

For existing code and packages, it may be possible to patch macros after they have been defined, using the `xpatch` package, which is pre-loaded by `l warp`:

```
\xpatchcmd{\macro}
  {$math expression$}
  {\inlinemathother$math expression$\inlinemathnormal}
  {}
  {\typeout{Error patching macro.}}
```

for HTML & PRINT: 4468 `\begin{warpall}`

Bool `LWR@dynamicmath` True to mark inline math which is dynamic in nature, thus should not be hashed for reuse.
Default: `false`

```
4469 \newbool{LWR@dynamicmath}
4470 \boolfalse{LWR@dynamicmath}
```

`\inlinemathother` Place before using `$... $` or `\(... \)` if the contents of the math are not static, depending on counters or dynamic macros.

```
4471 \newcommand{\inlinemathother}{%
4472 \LWR@traceinfo{\inlinemathother}%
4473 \booltrue{LWR@dynamicmath}%
4474 }
```

`\inlinemathnormal` Place after using `$... $` or `\(... \)` with dynamic contents.

```
4475 \newcommand{\inlinemathnormal}{%
4476 \LWR@traceinfo{\inlinemathnormal}%
4477 \boolfalse{LWR@dynamicmath}%
4478 }
```

```
4479 \end{warpall}
```

43 Sanitizing labels and filenames

Special handling for underscores in labels and filenames.

for HTML output: 4480 \begin{warpHTML}

\LWR@sanitized The sanitized version of what was given to \LWR@sanitize. Characters are set to their detokenized versions. Required for underscores in labels and filenames.

4481 \newcommand*\{\LWR@sanitized\}{}

\LWR@sanitize {\text{}}

Sanitizes the text and returns the result in \LWR@sanitized.

```
4482 \newcommand*\{\LWR@sanitize\}[1]{%
4483 \LWR@traceinfo{\LWR@sanitize: !#1!}%
4484 \edef\LWR@sanitized{\#1}%
4485 \LWR@traceinfo{\LWR@sanitize expanded: !\LWR@sanitized!}%
4486 \edef\LWR@sanitized{\detokenize\expandafter{\LWR@sanitized}}%
4487 \LWR@traceinfo{\LWR@sanitize result: !\LWR@sanitized!}%
4488 }
```

4489 \end{warpHTML}

44 HTML entities

for HTML output: 4490 \begin{warpHTML}

HTML entities and HTML Unicode entities:

4491 \let\LWR@origampersand\&

\HTMLentity {\text{}}

```
4492 \newcommand*\{\HTMLentity\}[1]{%
4493 % \LWR@traceinfo{\HTMLentity \detokenize{\#1}}%
4494 \begingroup%
4495 \LWR@FBcancel%
4496 \LWR@origampersand\#1;%
4497 \endgroup%
4498 % \LWR@traceinfo{\HTMLentity done}%
4499 }
```

```
\HTMLunicode  {\langle hex\_unicode\rangle}

4500 \newcommand*{\HTMLunicode}[1]{\HTMLentity{\LWR@origpound{}x#1} }

\&

4501 \renewrobustcmd*{\&}{\HTMLentity{amp} }

\textless
\textgreater
4502 \let\LWR@origtextless\textless
4503 \renewcommand*{\textless}{\HTMLentity{lt} }
4504
4505 \let\LWR@origtextgreater\textgreater
4506 \renewcommand*{\textgreater}{\HTMLentity{gt} }

4507 \end{warpHTML}
```

45 HTML filename generation

The filename of the homepage is set to `\HomeHTMLFilename.html`. The filenames of additional sections start with `\HTMLFilename`, to which is appended a section number or a simplified section name, depending on `FileSectionNames`.

for HTML & PRINT: 4508 \begin{warpall}

- `\BaseJobname` The `\jobname` of the printed version, even if currently compiling the HTML version. I.e. this is the `\jobname` without `_html` appended. This is used to set `\HomeHTMLFilename` if the user did not provide one.
- 4509 \providecommand*{\BaseJobname}{\jobname}
- `\HTMLFilename` The prefix for all generated HTML files other than the home page, defaulting to empty. See section [8.4.1](#).
- 4510 \providecommand*{\HTMLFilename}{}{}
- `\HomeHTMLFilename` The filename of the home page, defaulting to the `\BaseJobname`. See section [8.4.1](#).
- 4511 \providecommand*{\HomeHTMLFilename}{\BaseJobname}

\SetHTMLFileName {*number*}

Sets the file number for the next file to be generated. 0 is the home page. Use just before the next sectioning command, and set it to one less than the desired number of the next section. May be used to generate numbered groups of nodes such as 100+ for one chapter, 200+ for another chapter, etc.

```
4512 \newcommand*{\SetHTMLFileName}[1]{%
4513 \setcounter{LWR@htmlfilename}{#1}%
4514 }
```

Bool FileSectionNames Selects how to create HTML file names.

Defaults to use section names in the filenames.

```
4515 \newbool{FileSectionNames}
4516 \booltrue{FileSectionNames}

4517 \end{warpall}
```

for HTML output: 4518 \begin{warpHTML}

Ctr LWR@htmlfilename Records the number of each HTML file as it is being created. Number 0 is the home page.

```
4519 \newcounter{LWR@htmlfilename}
4520 \setcounter{LWR@htmlfilename}{0}
```

\LWR@htmlsectionfilename {*htmlfilename or name*}

Prints the filename for a given section: \HTMLFilename{}filename/name.html

```
4521 \newcommand*{\LWR@htmlsectionfilename}[1]{%
4522 \LWR@traceinfo{LWR@htmlsectionfilename A !\detokenize{#1}!}%
```

Section 0 or empty is given the home filename. The filename must be detokenized for underscores.

```
4523 % \LWR@traceinfo{about to assign temp}%
4524 \edef\LWR@tempone{\#1}%
4525 \LWR@traceinfo{about to compare with ??}%
4526 \ifthenelse{\equal{\LWR@tempone}{??}}{%
4527 {\LWR@traceinfo{found ??}}{%
4528 {\LWR@traceinfo{not found ??}}{%
4529 \LWR@traceinfo{about to compare with zero or empty}%
4530 \ifthenelse{%
4531 \equal{\LWR@tempone}{0}}{%
```

```

4532      \OR \equal{\LWR@tempone}{}%
4533      \OR \equal{\LWR@tempone}{??}%
4534 }%
4535 {%
4536     \LWR@traceinfo{LWR@htmlsectionfilename B \HomeHTMLFilename.html}%
4537     \HomeHTMLFilename.html%
4538 }%

```

For a \LaTeX section named “Index” or “index” without a prefix, create a filename with a leading underscore to avoid colliding with the HTML filename `index.html`:

```

4539 {%
4540     \LWR@traceinfo{LWR@htmlsectionfilename C \LWR@tempone}%
4541     \ifthenelse{%
4542         \equal{\HTMLFilename}{} \AND
4543         \equal{\LWR@tempone}{Index} \OR
4544         \equal{\LWR@tempone}{index}}%
4545     }%
4546     {%
4547         \LWR@traceinfo{Prefixing the index name with an underscore.}%
4548         \#1.html%
4549     }%

```

Otherwise, create a filename with the chosen prefix:

```

4550     {\HTMLFilename#1.html}%
4551 }%
4552 \LWR@traceinfo{LWR@htmlsectionfilename Z}%
4553 }

```

`\LWR@htmlrefsectionfilename {<label>}`

Prints the filename for the given label

```

4554 \newcommand*{\LWR@htmlrefsectionfilename}[1]{%
4555 \LWR@traceinfo{LWR@htmlrefsectionfilename: !\detokenize{\#1}!}%

```

`\LWR@nullfonts` to allow math in a section name.

```

4556 \begingroup%
4557 \LWR@nullfonts%
4558 \LWR@htmlsectionfilename{\LWR@htmlfileref{\#1}}%
4559 \endgroup%
4560 \LWR@traceinfo{LWR@htmlrefsectionfilename: done}%
4561 }

```

```

4562 \end{warpHTML}

```

46 Homepage link

for HTML output: 4563 \begin{warpHTML}

\LinkHome May be used wherever you wish to place a link back to the homepage. The filename must be detokenized for underscores.

```
4564 \newcommand*\{\LinkHome\}{%
4565 \LWR@subhyperrefclass{\HomeHTMLFilename.html}{Home}{linkhome}%
4566 }
```

\LWR@topnavigation Creates a link to the homepage at the top of the page for use when the window is too narrow for the sidetoc.

```
4567 \newcommand*\{\LWR@topnavigation\}{%
4568 \LWR@htmlelementclassline{nav}{topnavigation}{\LinkHome}%
4569 }
```

\LWR@botnavigation Creates a link to the homepage at the bottom of the page for use when the window is too narrow for the sidetoc.

```
4570 \newcommand*\{\LWR@botnavigation\}{%
4571 \LWR@htmlelementclassline{nav}{botnavigation}{\LinkHome}%
4572 }
```

4573 \end{warpHTML}

47 \LWRPrintStack diagnostic tool



Diagnostics tool: Prints the L^AT_EX nesting depth values for the stack levels. \LWR@startpars is used before printing the stack, so that \LWRPrintStack may be called from anywhere in the normal text flow.

for HTML output: 4574 \begin{warpHTML}

\LWRPrintStack Prints the closedepth stack.

```
4575 \newcommand*\{\LWR@subprintstack\}{%
4576 \LWR@closedepthon\ \LWR@closedepthtwo\ \LWR@closedepththree\%
4577 \LWR@closedepthfour\ \LWR@closedepthfive\ \LWR@closedepthsix\%
4578 \LWR@closedepthseven\ \LWR@closedeptheight\ \LWR@closedepthnine\%
4579 \LWR@closedepthon\ \LWR@closedeptheleven\ \LWR@closedepthtwelve\}
```

```

4580 }
4581
4582 \newcommand*{\LWRPrintStack}{%
4583 \LWR@startpars
4584 \LWR@subprintstack
4585 }

4586 \end{warpHTML}

for PRINT output: 4587 \begin{warpprint}

4588 \newcommand*{\LWRPrintStack}{}}

4589 \end{warpprint}

```

48 Closing stack levels

for HTML output: 4590 \begin{warpHTML}

Close one nested level:

```

4591 \newcommand*{\LWR@closeoneprevious}{%
4592
4593 \LWR@closeone
4594
4595 \popclose
4596 }

```

\LWR@closeprevious {<depth>} Close everything up to the given depth:

```

4597 \newcommand*{\LWR@closeprevious}[1]{%
4598 \LWR@traceinfo{\LWR@closeprevious to depth #1, depths are \LWR@subprintstack}%

```

Close any pending paragraph:

```
4599 \LWR@stoppars%
```

Close anything nested deeper than the desired depth. First close anything deeper, then at most one of the same level.

```

4600 \whileboolexpr{test{\ifnumcomp{\LWR@closedepthone}{>}{\#1}}}{%
4601 {%
4602     \LWR@traceinfo{\LWR@closeprevious: closing out depth \LWR@closedepthone}%
4603     \LWR@closeoneprevious%

```

```

4604 }%
4605 \ifboolexpr{test{\ifnumcomp{\LWR@closedepthone}{=}{\#1}}}{%
4606 {%
4607     \LWR@traceinfo{\LWR@closeprevious: closing out depth \LWR@closedepthone}%
4608     \LWR@closeoneprevious%
4609 }{}}%
4610 \LWR@traceinfo{\LWR@closeprevious: done, depths are \LWR@subprintstack}%
4611 }

4612 \end{warpHTML}

```

49 PDF pages and styles

for HTML output: 4613 \begin{warpHTML}

\LWR@forcenewpage New PDF page a before major environment.

This is used just before major environments, such as `verse`. Reduces the chance of an environment overflowing the HTML PDF output page.

```

4614 \newcommand{\LWR@forcenewpage}{%
4615 \LWR@traceinfo{\LWR@forcenewpage}%
4616 \ifinner\else%
4617 \LWR@stoppars\LWR@orignewpage\LWR@startpars%
4618 \fi%
4619 }

```

\pagestyle, etc. are nullified for HTML output.

\pagestyle {\<style>}

```
4620 \renewcommand*{\pagestyle}[1]{}
```

\thispagestyle {\<style>}

```
4621 \renewcommand*{\thispagestyle}[1]{}
```

\markboth {\<left>} {\<right>}

```
4622 \renewcommand*{\markboth}[2]{}
```

\markright {\<right>}

```
4623 \renewcommand*{\markright}[1]{}
```

```
\raggedbottom
4624 \renewcommand*{\raggedbottom}{}}

\flushbottom
4625 \renewcommand*{\flushbottom}{}}

\sloppy
4626 \renewcommand*{\sloppy}{}}

\fussy
4627 \renewcommand*{\fussy}{}}

\pagenumbering * {\langle commands \rangle}
4628 \RenewDocumentCommand{\pagenumbering}{s m}{}}

4629 \end{warpHTML}
```

50 HTML tags, spans, divs, elements

for HTML output: 4630 \begin{warpHTML}

50.1 Mapping L^AT_EX Sections to HTML Sections

```
4631 \newcommand*{\LWR@tagtitle}{h1}
4632 \newcommand*{\LWR@tagtitleend}{/h1}
4633 \newcommand*{\LWR@tagpart}{h2}
4634 \newcommand*{\LWR@tagpartend}{/h2}
4635 \newcommand*{\LWR@tagchapter}{h3}
4636 \newcommand*{\LWR@tagchapterend}{/h3}
4637 \newcommand*{\LWR@tagsection}{h4}
4638 \newcommand*{\LWR@tagsectionend}{/h4}
4639 \newcommand*{\LWR@tagsubsection}{h5}
4640 \newcommand*{\LWR@tagsubsectionend}{/h5}
4641 \newcommand*{\LWR@tagsubsubsection}{h6}
4642 \newcommand*{\LWR@tagsubsubsectionend}{/h6}
4643 \newcommand*{\LWR@tagparagraph}{span class="paragraph"}
```

```

4644 \newcommand*{\LWR@tagparagraphend}{/span}
4645 \newcommand*{\LWR@tagsubparagraph}{span class="subparagraph"}
4646 \newcommand*{\LWR@tagsubparagraphend}{/span}
4647
4648 \newcommand*{\LWR@tagregularparagraph}{p}

```

50.2 Babel-French tag modifications

Adjust **babel-french** for HTML spaces. So far, this only works for **pdflatex** and **xelatex**.

(Emulates or patches code by DANIEL FLIPO.)

```

4649 \providecommand*{\LWR@FBcancel}{}%
4650
4651 \AtBeginDocument{%
4652 \@ifundefined{frenchbsetup}%
4653 {}%
4654 {}%
4655 \frenchbsetup{FrenchFootnotes=false}%
4656 %
4657 \LetLtxMacro{\LWR@FBcancel}{\NoAutoSpacing}%
4658 \renewrobustcmd*{\FBcolonspace}{%
4659 \begingroup%
4660 \LWR@FBcancel%
4661 \LWR@origampersand{\nbsp;}%
4662 \endgroup%
4663 }%
4664 \renewrobustcmd*{\FBthinspace}{%
4665 \begingroup%
4666 \LWR@FBcancel%
4667 \LWR@origampersand{\LWR@origpound{\x202f};\,,\,}%
4668 \endgroup%
4669 }%
4670 \renewrobustcmd*{\FBguillspace}{%
4671 \begingroup%
4672 \LWR@FBcancel%
4673 \LWR@origampersand{\nbsp;~,~for~\og~xyz~\fg{}}%
4674 \endgroup%
4675 }%
4676 \DeclareDocumentCommand{\FBmedkern}{}{%
4677 \begingroup%
4678 \LWR@FBcancel%
4679 \LWR@origampersand{\LWR@origpound{\x202f};\,,\,}%
4680 \endgroup%
4681 }%
4682 \DeclareDocumentCommand{\FBthickkern}{}{%
4683 \begingroup%

```

```

4684     \LWR@FBcancel%
4685     \LWR@origampersand{}nbsp;% ~
4686     \endgroup%
4687   }%
4688   \renewrobustcmd*{~}{\HTMLentity{nbsp}}% was overwritten by babel-french
4689   \ifFBunicode%
4690   \else%
4691     \DeclareTextSymbol{\FBtextellipsis}{LY1}{133}%
4692     \DeclareTextCommandDefault{\FBtextellipsis}{\textellipsis\xspace}%
4693   \fi%
4694 }%
4695 }

```

50.3 HTML tags

\LWR@htmltagc {*tag*} Break ligatures and use upright apostrophes in HTML tags.

\protect is in case the tag appears in TOC, LOF, LOT.

```

4696 \newcommand*{\LWR@htmltagc}[1]{%
4697 \LWR@traceinfo{\LWR@htmltagc !\detokenize{\#1}!}%
4698 \begingroup%
4699 \LWR@FBcancel%
4700 \ifmmode\else\protect\LWR@origttfamily\fi%
4701 \protect\LWR@origtextless%
4702 \#1%
4703 \protect\LWR@origtextgreater%
4704 \endgroup%
4705 % \LWR@traceinfo{\LWR@htmltagc: done}%
4706 }

```

Env \LWR@nestspan Disable minipage, \parbox, and HTML <div>s inside a .

- ⚠ \begin{LWR@nestspan} must follow the opening tag to allow a paragraph to start if the span is at the beginning of a new paragraph.
- ⚠ \end{LWR@nestspan} must follow the or a <p> may appear inside the span.

```

4707 \newcommand*{\LWR@nestspanitem}{%
4708 \if@newlist\else{\LWR@htmltagc{br /}}\fi%
4709 \LWR@origitem%
4710 }
4711
4712 \newenvironment*{\LWR@nestspan}
4713 {%
4714 \LWR@traceinfo{\LWR@nestspan starting}%

```

```

4715 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
4716 {%
4717   \LWR@traceinfo{LWR@nestspan: inside a lateximage}%
4718 }%
4719 {%
4720   \LWR@traceinfo{LWR@nestspan: NOT inside a lateximage}%
4721   \addtocounter{LWR@spandepth}{1}%
4722   \RenewDocumentEnvironment{minipage}{O{t} o O{t} m}{\{}{\}}
4723   \RenewDocumentEnvironment{BlockClass}{o m}{\{}{\}}
4724   \renewcommand{\BlockClassSingle}[2]{##2}%
4725   \renewcommand{\LWR@forcenewpage}{}%
4726   \renewcommand{\LWR@liststart}{}%
4727   \let\item\LWR@nestspanitem%
4728 }%
4729   \renewcommand{\LWR@listend}{\LWR@htmllagc{br /}\LWR@htmllagc{br /}}%
4730 }%
4731 \LWR@traceinfo{LWR@nestspan starting: done}%
4732 }%
4733 {%
4734 \LWR@traceinfo{LWR@nestspan ending}%
4735 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
4736 {%
4737   \addtocounter{LWR@spandepth}{-1}%
4738 \LWR@traceinfo{LWR@nestspan ending: done}%
4739 }%
4740
4741 \AfterEndEnvironment{LWR@nestspan}{\global\let\par\LWR@closeparagraph}

```

\LWR@htmlspan {*tag*} {*text*}

⚠ \LWR@spandepth is used to ensure that paragraph tags are not generated inside a span. The exact sequence of when to add and subtract the counter is important to correctly handle the paragraph tags before and after the span.

```

4742 \NewDocumentCommand{\LWR@htmlspan}{m +m}{%
4743 \LWR@ensuredoingapar%
4744 \LWR@htmllagc{#1}%
4745 \begin{LWR@nestspan}%
4746 #2%
4747 \LWR@htmllagc{/#1}%
4748 \end{LWR@nestspan}%
4749 }

```

\LWR@htmlspanclass [*style*] {*class*} {*text*}

```

4750 \NewDocumentCommand{\LWR@htmlspanclass}{o m +m}{%
4751 \LWR@traceinfo{LWR@htmlspanclass |#1|#2|}%
4752 \LWR@ensuredoingapar%

```

```

4753 \LWR@subhtmlelementclass{span} [#1] {#2}%
4754 \begin{LWR@nestspan}%
4755 #3%
4756 \LWR@htmtagc{/span}%
4757 \LWR@traceinfo{LWR@htmlspanclass done}%
4758 \end{LWR@nestspan}%
4759 }

\LWR@htmntag {<tag>}

Print an HTML tag: <tag>

4760 \newcommand*{\LWR@htmntag}[1]{%
4761 % \LWR@traceinfo{LWR@htmntagb !\detokenize{#1}!}%
4762 \LWR@htmtagc{#1}%
4763 % \LWR@traceinfo{LWR@htmtagb: done}%
4764 }

```

50.4 Block tags and comments

In the following, \origttfamily breaks ligatures, which may not be used for HTML codes:

```

\LWR@htmlopencomment
\LWR@htmlclosecomment
4765 \newcommand*{\LWR@htmlopencomment}{%
4766 {%
4767 % \LWR@traceinfo{LWR@htmlopencomment}%
4768 \begingroup%
4769 \LWR@FBcancel%
4770 \ifmmode\else\protect\LWR@origttfamily\fi%
4771 \LWR@print@mbox{\LWR@origtextless{}!{-}{-}}%
4772 \endgroup%
4773 }%
4774 }
4775
4776 \newcommand*{\LWR@htmlclosecomment}{%
4777 {%
4778 % \LWR@traceinfo{LWR@htmlclosecomment}%
4779 \begingroup%
4780 \LWR@FBcancel%
4781 \ifmmode\else\protect\LWR@origttfamily\fi%
4782 \LWR@print@mbox{{-}{-}\LWR@origtextgreater}%
4783 \endgroup%
4784 }%
4785 }

```

```
\LWR@htmlcomment  {<comment>}

4786 \newcommand{\LWR@htmlcomment}[1]{%
4787 \LWR@htmlopencomment{}%
4788 {%
4789 \LWR@origttfamily% break ligatures
4790 #1%
4791 }%
4792 \LWR@htmclosecomment{}}

\LWR@htmlblockcomment  {<comment>}

4793 \newcommand{\LWR@htmlblockcomment}[1]
4794 {\LWR@stoppars\LWR@htmlcomment{#1}\LWR@startpars}

\LWR@htmlblocktag  {<tag>} print a stand-alone HTML tag

4795 \newcommand*{\LWR@htmlblocktag}[1]{%
4796 \LWR@stoppars%
4797 \LWR@htmntag{#1}%
4798 \LWR@startpars%
4799 }
```

50.5 Div class and element class

```
\LWR@subhtmlelementclass  {<element>} [<style>] {<class>}
```

Factored and reused in several places.

The trailing spaces allow more places for a line break.

```
4800 \NewDocumentCommand{\LWR@subhtmlelementclass}{m O{} m}{%
4801 \LWR@traceinfo{\LWR@subhtmlelementclass !#1!#2!#3!}%
4802 \ifblank{#2}{%
4803 {\LWR@htmntag{#1 class="#3"}% empty option
4804 {\LWR@htmntag{#1 class="#3" style="#2"}% non-empty option
4805 \LWR@traceinfo{\LWR@subhtmlelementclass done}%
4806 }}
```

```
\LWR@htmlelementclass  {<element>} {<class>} [<style>]
```

```
4807 \NewDocumentCommand{\LWR@htmlelementclass}{m o m}{%
4808 \LWR@stoppars%
4809 \LWR@subhtmlelementclass{#1}[#2]{#3}%
4810 }
```

```

4810 \LWR@startpars%
4811 }

\LWR@htmlelementclassend {<element>} {<class>}

4812 \newcommand*{\LWR@htmlelementclassend}[2]{%
4813 \LWR@stoppars%
4814 \LWR@htmltag{/#1}%
4815 \ifbool{HTMLDebugComments}{%
4816     \LWR@htmlcomment{End of #1 ``#2''}%
4817 }{}%
4818 \LWR@startpars%
4819 }

\LWR@htmldivclass [<style>] {<class>}

4820 \NewDocumentCommand{\LWR@htmldivclass}{o m}{%
4821 \LWR@htmlelementclass{div} [#1] {#2}%
4822 }

\LWR@htmldivclassend {<class>}

4823 \newcommand*{\LWR@htmldivclassend}[1]{%
4824 \LWR@htmlelementclassend{div}{#1}%
4825 }

```

50.6 Single-line elements

A single-line element, without a paragraph tag for the line of text:

```

\LWR@htmlelementclassline {<element>} [<style>] {<class>} {<text>}

4826 \NewDocumentCommand{\LWR@htmlelementclassline}{m o m +m}{%
4827 \LWR@stoppars
4828 \LWR@subhtmlelementclass{#1} [#2] {#3}%
4829 #4%
4830 \LWR@htmltag{/#1}
4831 \LWR@startpars
4832 }

```

50.7 HTML5 semantic elements

```
\LWR@htmlelement  {\langle element\rangle}

4833 \newcommand*{\LWR@htmlelement}[1]{%
4834 \LWR@htmlblocktag{#1}%
4835 }

\LWR@htmlelementend {\langle element\rangle}

4836 \newcommand*{\LWR@htmlelementend}[1]{%
4837 \LWR@stoppars%
4838 \LWR@htmlltag{/#1}%
4839 \LWR@startpars%
4840 }%
4841
4842 \end{warpHTML}
```

50.8 High-level block and inline classes

These are high-level commands which allow the creation of arbitrary block or inline sections which may be formatted with css.

Nullified versions are provided for print mode.

For other direct-formatting commands, see section 87.

Env BlockClass [⟨style⟩] {⟨class⟩} High-level interface for <div> classes.

Ex: \begin{BlockClass}{class} text \end{BlockClass}

for PRINT output: 4843 \begin{warpprint}
4844 \NewDocumentEnvironment{BlockClass}{o m}{}{%
4845 \end{warpprint}

for HTML output: 4846 \begin{warpHTML}
4847 \NewDocumentEnvironment{LWR@print@BlockClass}{o m}{}{%
4848 \NewDocumentEnvironment{LWR@HTML@BlockClass}{o m}{}{%
4849 {%
4850 \LWR@origpar%
4851 \LWR@htmldivclass[#1]{#2}%
4852 }%
4853 {\LWR@htmldivclassend{#2}}%
4854 }

```
4855 \LWR@formattedenv{BlockClass}
4856 \end{warpHTML}
```

\BlockClassSingle {<class>} {<text>} A single-line <div>, without a paragraph tag for the line of text.

for HTML & PRINT: 4857 \begin{warpall}
4858 \newcommand{\BlockClassSingle}[2]{#2}
4859 \end{warpall}

for HTML output: 4860 \begin{warpHTML}
4861 \newcommand{\LWR@HTML@BlockClassSingle}[2]{%
4862 \LWR@origpar%
4863 \LWR@htmlelementclassline{div}{#1}{#2}%
4864 }
4865
4866 \LWR@formatted{BlockClassSingle}
4867 \end{warpHTML}

\InlineClass [<style>] {<class>} {<text>} High-level interface for inline span classes.

for PRINT output: 4868 \begin{warpprint}
4869 \NewDocumentCommand{\InlineClass}{o m +m}{#3}%
4870 \end{warpprint}

for HTML output: 4871 \begin{warpHTML}
4872 \NewDocumentCommand{\LWR@print@InlineClass}{o m +m}{#3}%
4873
4874 \NewDocumentCommand{\LWR@HTML@InlineClass}{o m +m}{%
4875 \LWR@htmlspanclass[#1]{#2}{#3}%
4876 }
4877
4878 \LWR@formatted{InlineClass}
4879 \end{warpHTML}

Env LWR@BlockClassWP {{WPstyle}} {{HTMLstyle}} {<class>} Low-level interface for <div> classes with an automatic float ID. These are often used when \ifbool{FormatWP}.

for PRINT output: 4880 \begin{warpprint}
4881 \NewDocumentEnvironment{LWR@BlockClassWP}{m m m}{\begin{float}{#1}{#2}{#3}}{%
4882 \end{warpprint}}

for HTML output: 4883 \begin{warpHTML}
4884 \NewDocumentEnvironment{\LWR@print@LWR@BlockClassWP}{m m m}{\begin{float}{#1}{#2}{#3}}{%
4885 \NewDocumentEnvironment{\LWR@HTML@LWR@BlockClassWP}{m m m}{%
4886 \begin{float}{#1}{#2}{#3}}{%
4887 \LWR@stoppars%
4888 \ifbool{FormatWP}{%

```

4889 {%
4890     \addtocounter{LWR@thisautoidWP}{1}%
4891     \LWR@htmltag{%
4892         div class="#3" %
4893         id="\LWR@print@mbox{autoidWP-\arabic{LWR@thisautoidWP}}"%
4894         \ifblank{#1}{}{ style="#1"}%
4895     }%
4896 }% FormatWP
4897 {%
4898     \LWR@htmltag{%
4899         div class="#3"%
4900         \ifblank{#2}{}{ style="#2"}%
4901     }%
4902 }% not FormatWP
4903 \LWR@startpars%
4904 }
4905 {\LWR@htmldivclassend{#3}}
4906
4907 \LWR@formattedenv{LWR@BlockClassWP}
4908 \end{warpHTML}

```

50.9 Closing HTML tags

for HTML output: 4909 \begin{warpHTML}

Sections H1, H2, etc. do not need a closing HTML tag, but we add a comment for readability:

```

4910 \newcommand*{\LWR@printclosepart}%
4911     {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing part}}{}}
4912 \newcommand*{\LWR@printclosechapter}%
4913     {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing chapter}}{}}
4914 \newcommand*{\LWR@printclosesection}%
4915     {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing section}}{}}
4916 \newcommand*{\LWR@printclosesubsection}%
4917     {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsection}}{}}
4918 \newcommand*{\LWR@printclosesubsubsection}%
4919     {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsubsection}}{}}
4920 \newcommand*{\LWR@printcloseparagraph}%
4921     {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing paragraph}}{}}
4922 \newcommand*{\LWR@printclosesubparagraph}%
4923     {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subparagraph}}{}}

```

Lists require closing HTML tags:

```

4924 \newcommand*{\LWR@printcloselistitem}%
4925     {\LWR@htmltag{/li}}

```

```

4926 \newcommand*{\LWR@printclosedescitem}
4927   {\LWR@htmltag{/dd}}
4928 \newcommand*{\LWR@printcloseitemize}
4929   {\LWR@htmltag{/ul}}
4930 \newcommand*{\LWR@printcloseenumeration}
4931   {\LWR@htmltag{/ol}}
4932 \newcommand*{\LWR@printclosedescription}
4933   {\LWR@htmltag{/dl}}
4934 \end{warpHTML}

```

51 Paragraph handling

These commands generate the HTML paragraph tags when allowed and required.

Paragraph tags are or are not allowed depending on many conditions. Section 52 has high-level commands which allow paragraph-tag generation to start/stop. Even when allowed (`\LWR@doingstartpars`), tags are not generated until a L^AT_EX paragraph is being used (`\LWR@doingapar`). `\LWR@lateximagedepth` is used to prevent nesting tags inside a `\textrm`. `\LWR@spandepth` is used to prevent nesting paragraph tags inside a paragraph, which became important inside `\fbox` commands and other spans.

for HTML output: 4935 `\begin{warpHTML}`

Ctr `\LWR@spandepth` Do not create paragraph tags inside of an HTML span.

```

4936 \newcounter{\LWR@spandepth}
4937 \setcounter{\LWR@spandepth}{0}

```

Bool `\LWR@doingstartpars` Tells whether paragraphs may be generated.

```

4938 \newbool{\LWR@doingstartpars}
4939 \boolfalse{\LWR@doingstartpars}

```

Bool `\LWR@doingapar` Tells whether have actually generated and are currently processing paragraph text.

```

4940 \newbool{\LWR@doingapar}
4941 \global\boolfalse{\LWR@doingapar}

```

`\LWR@ensuredoingapar` If are about to print something visible, and if allowed to start a new paragraph, ensure that are `\LWR@doingapar`, so that paragraph tags are placed:

```

4942 \newcommand*{\LWR@ensuredoingapar}{%

```

```

4943 \ifbool{LWR@doingstartpars}%
4944 {\global\booltrue{LWR@doingapar}}%
4945 {}%
4946 }

```

\PN@parnotes@auto Redefined by **parnotes** to print paragraph notes at the end of each paragraph.

```
4947 \def\PN@parnotes@auto{}%
```

\LWR@openparagraph

```

4948 \newcommand*{\LWR@openparagraph}%
4949 {}%

```

See if paragraph handling is enabled:

```

4950 \ifbool{LWR@doingstartpars}%
4951 {%
    handling pars
}

```

See if have already started a `lateximage` or a ``. If so, do not generate nested paragraph tags.

```

4952 \ifboolexpr{
4953     test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
4954     test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
4955 }%
    nested par tags?

```

If so: Do nothing if already started a `lateximage` page. Cannot nest a `lateximage`. Also do nothing if already inside a ``. Do not nest paragraph tags inside a ``.

```
4956 {}%
    no nested par tags
```

Else: No `lateximage` or `` has been started yet, so it's OK to generate paragraph tags.

```
4957 {}%
    yes nest par tags
```

If **parnotes** is used, paragraph notes are inserted before starting the next paragraph:

```
4958 \PN@parnotes@auto%
```

The opening paragraph tag:

```
4959 \LWR@htmlltagc{\LWR@tagregularparagraph}%
```

Now have started a paragraph.

```
4960 \global\booltrue{LWR@doingapar}%
```

At the endof each paragraph, generate closing tag and do regular /par stuff. (Attempting to use the **everyhook** cr hook for \LWR@closeparagraph does not work well.)

```
4961 \let\par\LWR@closeparagraph%
4962 }% end of yes nest par tags
4963 }% end of handling pars
4964 {}% not handling pars
4965 }
```

\LWR@closeparagraph

```
4966 \newcommand*\LWR@closeparagraph{%
4967 {}%
4968 % \LWR@traceinfo{LWR@closeparagraph}%
}
```

See if paragraph handling is enabled:

```
4969 \ifbool{LWR@doingapar}{}%
```

If currently in paragraph mode:

```
4970 {}% handling pars
```

See if already started a `lateximage` or a ``:

```
4971 \ifboolexpr{%
4972   test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
4973   test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
4974 }%
```

Do nothing if already started a `lateximage` or a ``, but add a parbreak if in a span but not a `lateximage`.

```
4975 {}% no nested par tags
4976 \ifboolexpr{%
4977   test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}} and
4978   test {\ifnumcomp{\value{LWR@lateximagedepth}}{=}{0}}
4979 }%
4980 {} \ifbool{LWR@intabularmetadata}{}{\unskip\LWR@htmlltagc{br /}}%
4981 {}%
4982 }% no nested par tags
```

If have not already started a `\teximage` or a ``:

```
4983      {%
```

Print a closing tag and some extra vertical space.

```
4984          \unskip%
4985          \LWR@htmltagc{/\LWR@tagregularparagraph}%
4986          \LWR@orignewline%
```

No longer doing a paragraph:

```
4987          \global\boolfalse{LWR@doingapar}%
```

Disable the special `\minipage` & `\hspace` interaction until a new minipage is found:

```
4988          \global\boolfalse{LWR@minipagethispar}%
```

If **parnotes** is used, paragraph notes are inserted after ending the previous paragraph:

```
4989          \PN@parnotes@auto%
4990      }% end of yes nest par tags
4991 }% end of handling pars
```

Add a parbreak if in a span, but not in a table outside a row:

```
4992 {%
4993     not handling pars
4994     \ifnumcomp{\value{LWR@spandepth}}{>}{0}%
4995     {\ifbool{LWR@intabularmetadata}{}{\unskip\LWR@htmltagc{br /}}}%
4996 }% not handling pars
```

In most cases, finish with a `\par`, but in the case of paragraphs between lines in a tabular fetch the next token instead:

```
4997 \ifboolexpr{%
4998     not bool {LWR@doingapar} and
4999     test {\ifnumcomp{\value{LWR@tabulardepth}}{>}{0}} and
5000     test {
5001         \ifnumcomp{\value{LWR@tabulardepth}}{=}{\value{LWR@tabularpardepth}}
5002     } and
5003     bool {LWR@intabularmetadata} and
5004     not bool {LWR@tableparcell} and
5005     test {\ifnumcomp{\value{LWR@lateximagedepth}}{=}{0}}
5006 }%
5007 {%
5008     \LWR@getmynexttoken%
```

```

5009 }{%
5010     \LWR@origpar%
5011 }%
5012 }

5013 \end{warpHTML}

```

52 Paragraph start/stop handling

These commands allow/disallow the generation of HTML paragraph tags.

Section 51 has the commands which actually generate the tags.

The everyhook package is used to generate the opening paragraph tags. The closing tags are generated by \par.

for HTML output: 5014 \begin{warpHTML}

\LWR@startpars Begin handling HTML paragraphs. This allows an HTML paragraph to start, but one has not yet begun.

```

5015 \newcommand*\LWR@startpars{%
5016 {%
5017 \% \LWR@traceinfo{\LWR@startpars}%

```

Ignore if inside a span:

```

5018 \ifnumcomp{\value{\LWR@spandepth}}{>}{0}{%
5019 {}%
5020 {}%

```

See if currently handling HTML paragraphs:

```
5021 \ifbool{\LWR@doingstartpars}{%
```

If already in paragraph mode, do nothing.

```
5022 {}%
```

If not currently in paragraph mode:

```
5023 {}%
```

At the start of each paragraph, generate an opening tag:

```
5024      \PushPreHook{par}{\LWR@openparagraph}%
```

At the end of each paragraph, generate closing tag and do regular /par actions:

```
5025      \let\par\LWR@closeparagraph
5026
5027  }% an intentionally blank line
```

Are now handling paragraphs, but have not yet actually started one:

```
5028      \global\setbool{\LWR@doingstartpars}{true}%
```

No <par> tag yet to undo:

```
5029      \global\boolearn{\LWR@doingapar}%
5030  }% nestspan
5031 % \LWR@traceinfo{\LWR@startpars: done}%
5032 }
```

\LWR@stopars Stop handling HTML paragraphs. Any currently open HTML paragraph is closed, and no more will be opened.

```
5033 \newcommand*{\LWR@stopars}%
5034 {%
```

Ignore if inside a span:

```
5035 \ifnumcomp{\value{\LWR@spandepth}}{>}{0}%
5036 { }%
5037 { }
```

See if currently handling HTML paragraphs:

```
5038 \ifbool{\LWR@doingapar}{}
```

if currently in an HTML paragraph:

```
5039 { }
```

Print a closing tag:

```
5040      \unskip%
5041      \LWR@htmlltagc{/}\LWR@tagregularparagraph}%
5042      \LWR@orignewline%
```

No longer have an open HTML paragraph:

```
5043     \global\boolfalse{LWR@doingapar}%
```

Disable the special `minipage` & `\hspace` interaction until a new minipage is found:

```
5044     \global\boolfalse{LWR@minipagethispar}
5045
5046 }% an intentionally blank line
```

If was not in an HTML paragraph:

```
5047 {}%
```

See if currently allowing HTML paragraphs:

```
5048 \ifbool{LWR@doingstartpars}{}
```

If so: clear the par hook to no longer catch paragraphs:

```
5049 {\ClearPreHook{par}}%
```

Else: Do nothing:

```
5050 {}%
```

No longer in paragraph mode:

```
5051 \global\setbool{LWR@doingstartpars}{false}%
```

No `<p>` tag to undo:

```
5052 \global\boolfalse{LWR@doingapar}%
5053 }% nestspan
5054 }
```

```
5055 \end{warpHTML}
```

53 Page headers and footers

for HTML & PRINT: 5056 `\begin{warpall}`

In the following, catcode is manually changed back and forth without groups, since new macros are being defined which must not be contained within the groups.

```
5057 \newcommand{\LWR@firstpagetop}{} % for the home page alone
```

```

5058 \newcommand{\LWR@pagetop}{} % for all other pages
5059 \newcommand{\LWR@pagebottom}{}}

\HTMLFirstPageTop  {\langle text and logos\rangle}

5060 \newcommand{\HTMLFirstPageTop}[1]{%
5061     \renewcommand{\LWR@firstpagetop}{#1}%
5062 }

\HTMLPageTop  {\langle text and logos\rangle}

5063 \newcommand{\HTMLPageTop}[1]{%
5064     \renewcommand{\LWR@pagetop}{#1}%
5065 }

\HTMLPageBottom  {\langle text and logos\rangle}

5066 \newcommand{\HTMLPageBottom}[1]{%
5067     \renewcommand{\LWR@pagebottom}{#1}%
5068 }

5069 \end{warpall}

```

54 CSS

for HTML output: 5070 \begin{warpHTML}

\LWR@currentcss The css filename to use. This may be changed mid-document using \CSSFilename, allowing different css files to be used for different sections of the document.

5071 \newcommand*{\LWR@currentcss}{lwarp.css}

\CSSFilename {\new-css-filename.css} Assigns the css file to be used by the following HTML pages.

```

5072 \newcommand*{\CSSFilename}[1]{%
5073     \renewcommand*{\LWR@currentcss}{#1}%
5074     \onelevel@sanitize\LWR@currentcss%
5075 }
5076
5077 \end{warpHTML}

```

```
for PRINT output: 5078 \begin{warpprint}
5079 \newcommand*{\CSSfilename}[1]{}
5080 \end{warpprint}
```

55 Title, HTML meta author, HTML meta description

```
for HTML output: 5081 \begin{warpHTML}
```

\title {\<title>} Modified to remember \thetitle, which is used to set the HTML page titles.

```
5082 \let\LWR@origtitle\title
5083
5084 \renewcommand*{\title}[1]{%
5085   \LWR@origtitle{\#1}%
5086   \begingroup%
5087     \renewcommand{\thanks}[1]{%
5088       \protected@xdef\thetitle{\#1}%
5089     \endgroup%
5090 }
```

```
5091 \end{warpHTML}
```

```
for HTML & PRINT: 5092 \begin{warpall}
```

\HTMLTitle {\<Titlename>} The Title to place into an HTML meta tag. The default is to use the document \title's setting.

```
5093 \providecommand{\thetitle}{}
5094
5095 \newcommand{\theHTMLTitle}{\thetitle}
5096
5097 \newcommand{\HTMLTitle}[1]{\renewcommand{\theHTMLTitle}{#1}}
```

\HTMLAuthor {\<authorname>} The author to place into an HTML meta tag. If none given, the default is \theauthor, which is empty unless the **titling** package is used.

```
5098 \providecommand{\theauthor}{}
5099
5100 \newcommand{\theHTMLAuthor}{\theauthor}
5101
5102 \newcommand{\HTMLAuthor}[1]{\renewcommand{\theHTMLAuthor}{#1}}
```

This is placed inside an HTML meta tag at the start of each file. This may be changed mid-document using \HTMLDescription, allowing different HTML descriptions to be used for different sections of the document.

-  **HTML author** Do not use double quotes, and do not exceed 150 characters.

\HTMLDescription {*New HTML meta description.*} Assigns the HTML file's description meta tag.

```
5103 \newcommand{\LWR@currentHTMLDescription}{}  
5104  
5105 \newcommand{\HTMLDescription}[1]{%  
5106 \renewcommand{\LWR@currentHTMLDescription}{#1}  
5107 }  
5108  
5109 \end{warpall}
```

56 Footnotes

lwarf uses native L^AT_EX footnote code, although with its own \box to avoid the L^AT_EX output routine. The usual functions mostly work as-is.

The **footmisc** stable option is emulated by **lwarf**.

-  **sectioning commands** When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the **footmisc** package with the **stable** option, provide a short TOC entry, and \protect the \footnote:

```
\usepackage[stable]{footmisc}  
...  
\subsection[Subsection Name]  
{Subsection Name\protect\footnote{A footnote.}}
```

-  **memoir** If using **memoir** class, with which **lwarf** preloads **footmisc**, the **stable** option must be declared before **lwarf** is loaded:

```
\PassOptionsToPackage{stable}{footmisc}  
\usepackage{lwarf}  
...
```

Do not use a starred sectioning command. As an alternative, it may be possible to adjust \secnumdepth instead.

Several kinds of footnotes are used: in a regular page, in a minipage, or as thanks in the titlepage. Each of these is handled differently.

56.1 Regular page footnotes

In HTML documents, footnotes are placed at the bottom of the web page or the section, depending on `FootnoteDepth`, using the L^AT_EX box `\LWR@footnotes`. Using this instead of the original `\footins` box avoids having footnotes be printed by the output routine, since footnotes should be printed per HTML page instead of per PDF page.

See section 56.4 for the implementation.

56.2 Minipage footnotes

See section 56.5 for how minipage footnotes are gathered. See section 86.3 for how minipage footnotes are placed into the document.

56.3 Titlepage thanks

See section 63.7 for titlepage footnotes.

56.4 Regular page footnote implementation

for HTML & PRINT: 5110 `\begin{warpall}`

Ctr `FootnoteDepth` Determines how deeply to place footnotes in the HTML files, similar to `tocdepth`.
Default: 3 The default of 3 places footnotes before each `\subsubsection` or higher. See table 8 for a table of L^AT_EX section headings.

5111 `\newcounter{FootnoteDepth}`
5112 `\setcounter{FootnoteDepth}{3}`

5113 `\end{warpall}`

for HTML output: 5114 `\begin{warpHTML}`

Patch L^AT_EX footnotes to use a new `\box` instead of an insert for `l warp` footnotes. This avoids having the original `\footins` appear at the bottom of a `lateximage`, which is on its own new page.

5115 `\newbox{\LWR@footnotes}`

Much of the following has unneeded print-mode formatting removed.

```
\@makefntext {⟨text⟩}

5116 \long\def\@makefntext#1{\textsuperscript{\@thefnmark}~#1}

\@makefnmark

5117 \def\@makefnmark{%
5118     \textsuperscript{\@thefnmark}%
5119 }
```

Footnotes may be in regular text, in which case paragraphs are tagged, or in a table data cell or `lateximage`, in which case paragraph tags must be added manually.

In a `lateximage` during HTML output, the `lateximage` is placed inside a print-mode `minipage`, but the footnotes are broken out by:

```
\def\@mpfn{footnote}
\def\thempfn{\thefootnote}
\let\@footnotetext\LWR@footnotetext
```

```
\LWR@footnotetext {⟨text⟩}

5120 \long\def\LWR@footnotetext#1{%
5121 \LWR@traceinfo{[LWR@footnotetext]}%
5122 \global\setbox\LWR@footnotes=\vbox{%
```

Add to any current footnotes:

```
5123 \unvbox\LWR@footnotes%
```

Remember the footnote number for `\ref`:

```
5124 \protected@edef\@currentlabel{%
5125     \csname p@footnote\endcsname\@thefnmark%
5126 }% @currentlabel
```

Open a group:

```
5127 \color@begingroup%
```

Use HTML superscripts in the footnote even inside a `lateximage`:

```
5128 \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a `lateximage`:

```

5129      \ifthenelse{%
5130          \boolean{LWR@doingstartpars} \AND%
5131          \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
5132      }%
5133      {}%
5134      {\LWR@htmlltagc{\LWR@tagregularparagraph}}%

```

Append the footnote to the list:

```
5135      \@makefntext{#1}%
```

Closing paragraph tag:

```

5136      \ifthenelse{%
5137          \boolean{LWR@doingstartpars} \AND%
5138          \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
5139      }%
5140      {\par}%
5141      {}%
5142      \LWR@htmlltagc{/}\LWR@tagregularparagraph\%
5143      \LWR@orignewline\%
5144      }%

```

Close the group:

```

5145      \color@endgroup%
5146 }% vbox

```

Paragraph handling:

```

5147 \LWR@ensuredoingapar%
5148 }%

```

\@footnotetext {⟨text⟩}

```
5149 \LetLtxMacro\@footnotetext\LWR@footnotetext
```

56.5 Minipage footnote implementation

Patch L^AT_EX minipage footnotes to use a new \box instead of an insert for **l warp** minipage footnotes. This avoids having the original \ompfootins appear at the bottom of a lateximage, which is on its own new page.

```
5150 \newbox\LWR@mpfootnotes
```

```
\@mpfootnotetext {<text>}

5151 \long\def\@mpfootnotetext#1{%
5152 \LWR@traceinfo{@mpfootnotetext}%
5153 \global\setbox\LWR@mpfootnotes\vbox{%
5154   \unvbox\LWR@mpfootnotes%
5155   \reset@font\footnotesize%
5156   \hsize\columnwidth%
5157   \parboxrestore%
5158   \protected@edef\@currentlabel{%
5159     \csname p@mpfootnote\endcsname\@thefnmark}%
5160   \color@begingroup%
```

Use paragraph tags if in a tabular data cell or a `lateximage`:

```
5161 \ifthenelse{%
5162   \boolean{\LWR@doingstartpars} \AND%
5163   \cnttest{\value{\LWR@lateximagedepth}}{=}{0}%
5164 }%
5165 {}%
5166 {\LWR@htmllagc{\LWR@tagregularparagraph}}%

5167 \makefntext{%
5168   \ignorespaces#1%
5169 }%
```

Don't add the closing paragraph tag if are inside a `lateximage`:

```
5170 \ifthenelse{\cnttest{\value{\LWR@lateximagedepth}}{>}{0} }{%
5171 {}%
5172 {}%
5173 \LWR@htmllagc{/LWR@tagregularparagraph}%
5174 \LWR@newline%
5175 }%
5176 \color@endgroup%
5177 }% vbox
```

Paragraph handling:

```
5178 \LWR@ensuredoingapar%
5179 \LWR@traceinfo{@mpfootnotetext: done}%
5180 }
```

`\thempfootnote` Redefined to remove the `\itshape`, which caused an obscure compiling error in some situations.

```
5181 \AtBeginDocument{%
5182 \def\thempfootnote{\@alph\c@mpfootnote}
```

5183 }

56.6 Printing pending footnotes

\LWR@printpendingfootnotes Enclose the footnotes in a class, print, then clear.

```
5184 \newcommand*{\LWR@printpendingfootnotes}{%
5185 \ifvoid\LWR@footnotes\else
5186   \LWR@forcenewpage
5187   \begin{BlockClass}{footnotes}
5188     \LWR@origmedskip
5189     \unvbox\LWR@footnotes
5190     \setbox\LWR@footnotes=\vbox{}
5191   \end{BlockClass}
5192 \fi
5193 }
```

\LWR@maybeprintpendingfootnotes {<depth>} Used to print footnotes before sections only if formatting for an EPUB or word processor:

```
5194 \newcommand*{\LWR@maybeprintpendingfootnotes}[1]{%
5195 \ifboolexpr{
5196   not test{\ifnumcomp{#1}{>}{\value{FootnoteDepth}}}} or
5197   bool{FormatEPUB} or
5198   bool{FormatWP}
5199 }%
5200 {\LWR@printpendingfootnotes}%
5201 {}%
5202 }
```

\LWR@printpendingmpfootnotes Enclose the minipage footnotes in a class, print, then clear.

```
5203 \newcommand*{\LWR@printpendingmpfootnotes}{%
5204 \ifvoid\LWR@mpfootnotes\else
5205   \LWR@forcenewpage
5206   \begin{BlockClass}{footnotes}
5207     \LWR@print@vspace*\{\baselineskip}
5208     \unvbox\LWR@mpfootnotes
5209     \setbox\LWR@mpfootnotes=\vbox{}
5210   \end{BlockClass}
5211 \fi
5212 }

5213 \end{warpHTML}
```

57 Marginpars

\marginpar [⟨left⟩] {⟨right⟩} \marginpar may contains paragraphs, but in order to remain inline with the surrounding text **l warp** nullifies block-related macros inside the \marginpar. Paragraph breaks are converted to
 tags.

\marginparBlock [⟨left⟩] {⟨right⟩} To include block-related macros, use \marginparBlock, which takes the same arguments but creates a <div> instead of a . A line break will occur in the text where the \marginBlock occurs.

for HTML output: 5214 \begin{warpHTML}

```
\marginpar [⟨left⟩] {⟨right⟩}

5215 \renewcommand{\marginpar}[2] [] {%
5216 \ifbool{FormatWP}{%
5217 {%
5218 \begin{LWR@BlockClassWP}{width:2in; float:right; margin:10pt}{}{\marginblock}%
5219 #2
5220 \end{LWR@BlockClassWP}%
5221 }%
5222 {%
5223 \LWR@htmlspanclass{\marginpar}{#2}%
5224 }%
5225 }
```

\marginparBlock [⟨left⟩] {⟨right⟩}

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

HTML version.

```
5226 \newcommand{\marginparBlock}[2] [] {%
5227 \ifbool{FormatWP}{%
5228 {%
5229 \begin{LWR@BlockClassWP}{width:2in; float:right; margin:10pt}{}{\marginblock}%
5230 #2
5231 \end{LWR@BlockClassWP}%
5232 }%
5233 {%
5234 \begin{BlockClass}{width:2in; float:right; margin:10pt}{\marginparblock}%
5235 #2
5236 \end{BlockClass}%
5237 }%
5238 }
```

```
\reversemarginpar
5239 \renewcommand*{\reversemarginpar}{}

\normalmarginpar
5240 \renewcommand*{\normalmarginpar}{}

5241 \end{warpHTML}

for PRINT output: 5242 \begin{warpprint}
```

\marginparBlock [⟨left⟩] {⟨right⟩}

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

Print version.

```
5243 \LetLtxMacro\marginparBlock\marginpar
5244 \end{warpprint}
```

58 Splitting HTML files

- Files are split according to `FileDepth` and `CombineHigherDepths`.
- Filenames are sanitized by `\LWR@filenamenoblocks`.
- `\LWR@newhtmlfile` finishes an HTML page, adds a comment to tell where and how to split the file, then starts a new HTML page.

for HTML & PRINT: 5245 \begin{warpall}

`Ctr FileDepth {⟨section depth⟩}` determines how deeply to break into new HTML files, similar to `tocdepth`. The default of -5 produces one large HTML file.

```
5246 \newcounter{FileDepth}
5247 \setcounter{FileDepth}{-5}
```

`Bool CombineHigherDepths` Combiile higher-level sections together into one file?

```
5248 \newbool{CombineHigherDepths}
5249 \booltrue{CombineHigherDepths}
```

5250 \end{warpall}

for HTML output: 5251 \begin{warpHTML}

\LWR@thisfilename The currently-active filename or number.

5252 \newcommand*{\LWR@thisfilename}{}{}

\LWR@thisnewfilename The filename being sanitized.

5253 \newcommand*{\LWR@thisnewfilename}{}{}

\LWR@filenamenoblocks {\langle filename \rangle}

Convert blanks into dashes, removes short words, store result in \LWR@thisfilename.

- ⚠ filename collision
 - ⚠ section names
- Be sure that this does not result in filename collisions! Use the optional TOC caption entry parameter for formatting. Remember to \protect \TeX commands which appear in section names and TOC captions.

5254 \newcommand*{\LWR@filenamenoblocks}[1]{%
5255 \begingroup

Locally temporarily disable direct-formatting commands, not used in filenames:

5256 \LWR@nullfonts%
5257 \renewcommand*{\LWR@htmlltagc}[1]{}%

Replaces common symbols and short words with hyphens:

5258 \edef{\LWR@thisnewfilename}{#1}%
5259 \LWR@traceinfo{\LWR@filenamenoblocks \edef: !\LWR@thisnewfilename!}%
5260 \fullexpandarg%

Convert spaces into hyphens:

5261 \StrSubstitute{\LWR@thisnewfilename}{ }{-}[\LWR@thisnewfilename]

Convert punctuation into hyphens:

5262 \StrSubstitute{\LWR@thisnewfilename}{,}{-}[\LWR@thisnewfilename]
5263 \StrSubstitute{\LWR@thisnewfilename}{'}{-}[\LWR@thisnewfilename]
5264 \StrSubstitute{\LWR@thisnewfilename}{%}
5265 {\LWR@origampersand}{-}[\LWR@thisnewfilename]
5266 \StrSubstitute{\LWR@thisnewfilename}{+}{-}[\LWR@thisnewfilename]

```

5267 \StrSubstitute{\LWR@thisnewfilename}{,}{-}[\LWR@thisnewfilename]
5268 \StrSubstitute{\LWR@thisnewfilename}{/}{-}[\LWR@thisnewfilename]
5269 \StrSubstitute{\LWR@thisnewfilename}{:}{-}[\LWR@thisnewfilename]
5270 \StrSubstitute{\LWR@thisnewfilename}{;}{-}[\LWR@thisnewfilename]
5271 \StrSubstitute{\LWR@thisnewfilename}{=}{-}[\LWR@thisnewfilename]
5272 \StrSubstitute{\LWR@thisnewfilename}{?}{-}[\LWR@thisnewfilename]
5273 \StrSubstitute{\LWR@thisnewfilename}{@}{-}[\LWR@thisnewfilename]
5274 \StrSubstitute{\LWR@thisnewfilename}{"}{-}[\LWR@thisnewfilename]
5275 \StrSubstitute{\LWR@thisnewfilename}%
5276     {\textless}{-}[\LWR@thisnewfilename]
5277 \StrSubstitute{\LWR@thisnewfilename}%
5278     {\textgreater}{-}[\LWR@thisnewfilename]
5279 \StrSubstitute{\LWR@thisnewfilename}{\LWR@origpound}{-}[\LWR@thisnewfilename]

5280 \StrSubstitute{\LWR@thisnewfilename}{\_}{-}[\LWR@thisnewfilename]

5281 \StrSubstitute{\LWR@thisnewfilename}{\ }{-}[\LWR@thisnewfilename]
5282 \StrSubstitute{\LWR@thisnewfilename}{\%}{-}[\LWR@thisnewfilename]
5283 \StrSubstitute{\LWR@thisnewfilename}{\{}{-}[\LWR@thisnewfilename]
5284 \StrSubstitute{\LWR@thisnewfilename}{\}}{-}[\LWR@thisnewfilename]
5285 \StrSubstitute{\LWR@thisnewfilename}{\|}{-}[\LWR@thisnewfilename]
5286 \StrSubstitute{\LWR@thisnewfilename}%
5287     {\textbackslash}{-}[\LWR@thisnewfilename]
5288 \StrSubstitute{\LWR@thisnewfilename}{^}{-}[\LWR@thisnewfilename]
5289 \StrSubstitute{\LWR@thisnewfilename}{~}{-}[\LWR@thisnewfilename]
5290 \StrSubstitute{\LWR@thisnewfilename}{\~\{}}{-}[\LWR@thisnewfilename]
5291 %      "\~{}" for babel
5292 \StrSubstitute{\LWR@thisnewfilename}{[]}{-}[\LWR@thisnewfilename]
5293 \StrSubstitute{\LWR@thisnewfilename}{\}]{-}[\LWR@thisnewfilename]
5294 \StrSubstitute{\LWR@thisnewfilename}{'}{-}[\LWR@thisnewfilename]

```

Convert short words:

```

5295 \StrSubstitute{\LWR@thisnewfilename}{-s-}{-}[\LWR@thisnewfilename]
5296 \StrSubstitute{\LWR@thisnewfilename}{-S-}{-}[\LWR@thisnewfilename]
5297 \StrSubstitute{\LWR@thisnewfilename}{-a-}{-}[\LWR@thisnewfilename]
5298 \StrSubstitute{\LWR@thisnewfilename}{-A-}{-}[\LWR@thisnewfilename]
5299 \StrSubstitute{\LWR@thisnewfilename}{-an-}{-}[\LWR@thisnewfilename]
5300 \StrSubstitute{\LWR@thisnewfilename}{-AN-}{-}[\LWR@thisnewfilename]
5301 \StrSubstitute{\LWR@thisnewfilename}{-to-}{-}[\LWR@thisnewfilename]
5302 \StrSubstitute{\LWR@thisnewfilename}{-TO-}{-}[\LWR@thisnewfilename]
5303 \StrSubstitute{\LWR@thisnewfilename}{-by-}{-}[\LWR@thisnewfilename]
5304 \StrSubstitute{\LWR@thisnewfilename}{-BY-}{-}[\LWR@thisnewfilename]
5305 \StrSubstitute{\LWR@thisnewfilename}{-of-}{-}[\LWR@thisnewfilename]
5306 \StrSubstitute{\LWR@thisnewfilename}{-OF-}{-}[\LWR@thisnewfilename]
5307 \StrSubstitute{\LWR@thisnewfilename}{-and-}{-}[\LWR@thisnewfilename]
5308 \StrSubstitute{\LWR@thisnewfilename}{-AND-}{-}[\LWR@thisnewfilename]
5309 \StrSubstitute{\LWR@thisnewfilename}{-for-}{-}[\LWR@thisnewfilename]

```

```

5310 \StrSubstitute{\LWR@thisnewfilename}{-FOR-}{-}[\LWR@thisnewfilename]
5311 \StrSubstitute{\LWR@thisnewfilename}{-the-}{-}[\LWR@thisnewfilename]
5312 \StrSubstitute{\LWR@thisnewfilename}{-THE-}{-}[\LWR@thisnewfilename]

```

Convert multiple hyphens:

```

5313 \StrSubstitute{\LWR@thisnewfilename}{----}{-}[\LWR@thisnewfilename]
5314 \StrSubstitute{\LWR@thisnewfilename}{---}{-}[\LWR@thisnewfilename]
5315 \StrSubstitute{\LWR@thisnewfilename}{--}{-}[\LWR@thisnewfilename]
5316 \StrSubstitute{\LWR@thisnewfilename}{--}{-}[\LWR@thisnewfilename]

```

If pdf^AT_EX and not utf8 encoding, don't try to convert emdash, endash:

```

5317 \ifPDFTeX% pdflatex or dvi latex
5318 \ifdefstring{\inputencodingname}{utf8}{%
5319 \StrSubstitute{\LWR@thisnewfilename}{--}{-}[\LWR@thisnewfilename]
5320 %      emdash
5321 \StrSubstitute{\LWR@thisnewfilename}{-}{-}[\LWR@thisnewfilename]
5322 %      endash
5323 }{%
5324 \else% not PDFTeX
5325 \StrSubstitute{\LWR@thisnewfilename}{--}{-}[\LWR@thisnewfilename]
5326 \StrSubstitute{\LWR@thisnewfilename}{-}{-}[\LWR@thisnewfilename]
5327 \fi%

```

Return the result:

```

5328 \global\let\LWR@thisfilename\LWR@thisnewfilename% return a global result
5329 \endgroup%
5330 \LWR@traceinfo{\LWR@filenamenoblanks: result is \LWR@thisfilename}%
5331 }

```

Ctr Remembers which autopage label was most recently generated. Used to avoid duplicates.

```

5332 \newcounter{\LWR@previousautopagelabel}
5333 \setcounter{\LWR@previousautopagelabel}{-1}

\LWR@newautopagelabel {\langle pagenumber counter\rangle}

5334 \newcommand*{\LWR@newautopagelabel}[1]{%
5335 \ifnumequal{\value{\LWR@previousautopagelabel}}{\value{page}}{%
5336 {}% no action if this autopage label has already been defined
5337 {}%
5338 \label{autopage-\arabic{#1}}%
5339 \setcounter{\LWR@previousautopagelabel}{\value{page}}%
5340 }%
5341 }

```

\LWR@customizedMathJax Additional MATHJAX definitions to be added to the start of each HTML page.

```
5342 \newcommand*\{\LWR@customizedMathJax\}{}%
```

\CustomizeMathJax MATHJAX does not have preexisting support every possible math function. Additional MATHJAX function definitions may be defined. These will be declared at the start of each HTML page, and thus will have a global effect.

Examples:

```
\CustomizeMathJax{
    \newcommand{\expval}[1]{\langle#1\rangle}
    \newcommand{\abs}[1]{\lvert#1\rvert}
}
\CustomizeMathJax{\newcommand{\arsinh}{\text{arsinh}}}
\CustomizeMathJax{\newcommand{\arcosh}{\text{arcosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}

5343 \newcommand*\{\CustomizeMathJax\}[1]{%
5344     \appto{\LWR@customizedMathJax}{%
5345         \(#1\)\par
5346     }%
5347 }
```

\LWR@customizeMathJax

```
5348 \newcommand{\LWR@customizeMathJax}{%
5349 \ifbool{mathjax}{%
5350 \LWR@stoppars
5351 \LWR@htmlcomment{Nullify \textbackslash ensuremath, footnotes for MathJax:}
5352
5353 \(\newcommand\ensuremath[1]{##1}\)
5354
5355 \(\newcommand\footnote[2][]{\text{( Footnote ##1 )}}\)
5356
5357 \(\newcommand\footnotemark[1][]{\text{( Footnote ##1 )}}\)
5358
5359 \LWR@htmlcomment{Additional customizations for MathJax:}
5360
5361 \LWR@customizedMathJax
5362
5363 \LWR@startpars
5364 }{}%
5365 }

5366 \end{warpHTML}

for PRINT output: 5367 \begin{warpprint}
```

\CustomizeMathJax The print-mode version:

```
5368 \newcommand*{\CustomizeMathJax}[1]{}
```

```
5369 \end{warpprint}
```

for HTML output: 5370 \begin{warpHTML}

```
\LWR@newhtmlfile {\<section name>}
```

Finishes the current HTML page with footnotes, footer, navigation, then starts a new HTML page with an HTML comment telling where to split the page and what the new filename and css are, then adds navigation, side TOC, header, and starts the text body.

```
5371 \newcommand*{\LWR@newhtmlfile}[1]{  
5372 \LWR@traceinfo{\LWR@newhtmlfile}}
```

At the bottom of the ending file:

```
5373 \LWR@htmlelementclassend{section}{textbody}  
5374  
5375 \LWR@printpendingfootnotes  
5376
```

No footer between files if EPUB:

```
5377 \ifbool{FormatEPUB}{  
5378 {}  
5379 {  
5380     \LWR@htmlelement{footer}  
5381  
5382     \LWR@pagebottom  
5383  
5384     \LWR@htmlelementend{footer}  
5385 }}
```

No bottom navigation if are finishing the home page or formatting for EPUB or a word-processor.

```
5386 \ifthenelse{\boolean{FormatEPUB} \OR \boolean{FormatWP}}{  
5387 {}  
5388 {\ifnumcomp{\value{\LWR@htmlfilename}}{>}{0}{\LWR@botnavigation}{}}}
```

End of this HTML file:

```

5389 \LWR@stoppars
5390 \LWR@htmlltag{/body}\LWR@orignewline
5391 \LWR@htmlltag{/html}\LWR@orignewline
5392 \LWR@traceinfo{\LWR@newhtmlfile: about to LWR@orignewpage}
5393 \LWR@orignewpage
5394
5395 \addtocounter{\LWR@htmllfilename}{1}%

```

If using a filename, create a version without blanks. The filename without blanks will be placed into \LWR@thisfilename. If not using a filename, the file number will be used instead.

```

5396 \ifbool{FileSectionNames}%
5397 {\LWR@filenamenoblanks{#1}%
5398 {\renewcommand*{\LWR@thisfilename}{\arabic{\LWR@htmllfilename}}}

```

Include an HTML comment to instruct lwarfpmk where to split the files apart. Uses pipe-separated fields for split_html.gawk. Uses monospaced font with ligatures disabled for everything except the title.

```
5399 \LWR@traceinfo{\LWR@newhtmlfile: about to print start file}%

```

\LWR@nullfonts to allow math in a section name.

```

5400 \begingroup%
5401 \LWR@nullfonts%
5402 \LWR@htmllblockcomment{%
5403 |Start file|%
5404 \LWR@htmllsectionfilename{\LWR@thisfilename}|%
5405 }
5406 \endgroup%

```

At the top of the starting file:

```

5407 \LWR@stoppars
5408

```

If pdf~~LT~~E_X and not utf8 encoding, use a hyphen instead of an emdash:

```

5409 \ifPDFTeX% pdflatex or dvi latex
5410 \ifdefstring{\inputencodingname}{utf8}{%
5411 \LWR@filestart{ -- #1}% there is an EMdash in front of the #1
5412 }%
5413 \LWR@filestart{ - #1}% hyphen
5414 }%
5415 \else%
5416 \LWR@filestart{ -- #1}% there is an EMdash in front of the #1
5417 \fi%

```

5418

Track the page numbers:

```
5419 \setcounter{LWR@latestautopage}{\value{page}}%
5420 \LWR@newautopagelabel{LWR@latestautopage}%
```

No navigation between files if formatting for an EPUB or word processor:

```
5421 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
5422 {}
5423 {\LWR@topnavigation}
5424
```

No header if between files if formatting for an EPUB or word processor:

```
5425 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
5426 {}
5427 {
5428     \LWR@htmlelement{header}
5429
5430     \LWR@pagetop
5431
5432     \LWR@htmlelementend{header}
5433 }
5434
```

Print title only if there is one. Skip if formatting for an EPUB or word processor:

```
5435 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
5436 {}
5437 {\ifcvoid{\thetitle}{}{\LWR@printthetitle}}
5438
```

No sidetoc if formatting for an EPUB or word processor:

```
5439 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
5440 {}
5441 {\LWR@sidetoc}
5442
```

Start of the <textbody>:

```
5443 \LWR@htmlelementclass{section}{textbody}
5444
```

Keep paragraph tags disabled for now:

```
5445 \LWR@stopars
5446
```

If using MathJax, disable `\ensuremath` by printing a nullified definition at the start of each file, and add further customizations:

```
5447 \LWR@customizeMathJax
5448 \LWR@traceinfo{\LWR@newhtmlfile: done}
5449 }
5450 \end{warpHTML}
```

59 Sectioning

Sectioning and cross-references have been emulated from scratch, rather than try to patch several layers of existing \TeX code and packages. Formatting is handled by `css`, so the emulated code has much less work to do than the print versions.

Unicode

\triangleleft accents in filenames

Section names and the resulting filenames with accented characters are partially supported, depending on the ability of `pdflatex` to generate characters and `pdftotext` to read them. If extra symbols appear in the text, it may be that `pdflatex` is actually producing a symbol over or under a character, resulting in `pdftotext` picking up the accent symbol separately.

\XeTeX and \LuaTeX directly support accented section and file names.

for HTML output: 5451 `\begin{warpHTML}`

59.1 User-level starred section commands

`\ForceHTMLPage` For HTML output, forces the next section to be on its own HTML page, if `FileDepth` allows, even if starred. For use with `\printindex` and others which generate a starred section which should be on its own HTML page. Also see `\ForceHTMLTOC`.

For print output, no effect.

```
5452 \newbool{\LWR@forcinghtmlpage}
5453 \boolfalse{\LWR@forcinghtmlpage}
5454
5455 \newcommand*{\ForceHTMLPage}{%
5456 \global\booltrue{\LWR@forcinghtmlpage}%
5457 }
```

\ForceHTMLTOC For HTML output, forces the next section to have a TOC entry, even if starred. For use with \printindex and others which generate a starred section which should be in the TOC so that it may be accessed via HTML. Not necessary if used with **tocbibind**. Also see \ForceHTMLPage.

For print output, no effect.

```
5458 \newbool{LWR@forcinghtmltoc}
5459 \boolfalse{LWR@forcinghtmltoc}
5460
5461 \newcommand*\{\ForceHTMLTOC}{%
5462 \global\booltrue{LWR@forcinghtmltoc}%
5463 }

5464 \end{warpHTML}
```

for PRINT output: 5465 \begin{warpprint}
5466 \newcommand*\{\ForceHTMLPage}{}
5467 \newcommand*\{\ForceHTMLTOC}{}
5468 \end{warpprint}

for HTML output: 5469 \begin{warpHTML}

59.2 Book class commands

\mainmatter Declare the main matter section of the document. Does not reset the page number, which must be consecutive arabic numbers for the HTML conversion.

```
5470 \newbool{LWR@mainmatter}
5471 \DeclareDocumentCommand{\mainmatter}{}{%
5472 \booltrue{LWR@mainmatter}%
5473 }
```

\frontmatter Declare the front matter section of the document, using arabic numbering for the internal numbering. Does not reset the page number.

```
5474 \DeclareDocumentCommand{\frontmatter}{}{%
5475 \boolfalse{LWR@mainmatter}%
5476 }
```

\backmatter Declare the back matter section of the document. Does not reset the page number.

```
5477 \DeclareDocumentCommand{\backmatter}{}{%
5478 \boolfalse{LWR@mainmatter}%
5479 }
```

59.3 Sectioning support macros

\LWR@sectionnumber {*<section type>*}

Typeset a section number and its trailing space with CSS formatting:

```
5480 \newcommand*{\LWR@sectionnumber}[1]{%
5481 \InlineClass{sectionnumber}{#1}%
5482 }
```

autosec A tag used by the TOC and index.

\LWR@createautosec {*<section type>*}

Create an autosection tag.

```
5483 \newcommand*{\LWR@createautosec}[1]{%
5484 \LWR@htmntag{#1 id="\LWR@print@mbox{autosec-\arabic{page}}"}%
5485 }
```

\LWR@pushoneclose {*<depth>*} {*printclose>*} Stacks the new sectioning level's closing tag, to be used when this section is closed some time later.

 \LWR@stoppars must be executed first.

```
5486 \NewDocumentCommand{\LWR@pushoneclose}{m m}{%
5487 \LWR@traceinfo{\LWR@pushoneclose #1}%
5488     \pushclose{#2}{#1}%
5489 }
```

\LWR@startnewdepth {*<depth>*} {*printclose>*}

Closes currently stacked tags of a lesser level, then opens the new nesting level by saving this new sectioning level's closing tag for later use.

 \LWR@stoppars must be executed first.

```
5490 \NewDocumentCommand{\LWR@startnewdepth}{m m}{%
```

Close any stacked sections up to this new one.

```
5491 \LWR@closeprevious{#1}%
```

Push a new section depth:

```
5492 \LWR@pushoneclose{\#1}{\#2}%
5493 }
```

Ctr `LWR@prevFileDepth` Remembers the previous `LWR@FileDepth`.

Initialized to a deep level so that any section will trigger a new HTML page after the home page.

```
5494 \newcounter{LWR@prevFileDepth}
5495 \setcounter{LWR@prevFileDepth}{\LWR@depthsubparagraph}
```

`\@seccntformat {<sectiontype>}`

```
5496 \def\@seccntformat#1{\csname the#1\endcsname\protect\quad}
```

`\simplechapterdelim` Used by **tocbibind** and **anonchap**.

```
5497 \newcommand*\simplechapterdelim{}
```

`\@chapcntformat {<sectiontype>}`

\let to `\@seccntformat` by default, but may be redefined by `\simplechapter` and `\restorechapter` from **tocbibind** or **anonchap**.

```
5498 \let\@chapcntformat\@seccntformat
```

Ctr `LWR@currentautosec` Records the page number when the section was created. If a math expression is included in the section name, and SVG math is used, the corresponding `lateximage` will cause the page number to change by the time the following autosec label is created.

```
5499 \newcounter{LWR@currentautosec}
```

`\LWR@section * [<TOC name>] {<name>} {<sectiontype>}`

The common actions for the high-level sectioning commands.

```
5500 \DeclareDocumentCommand{\LWR@section}{m m m m}{%
5501 \LWR@traceinfo{LWR@section |#2| |#3|}%
5502 \LWR@traceinfo{LWR@section: not an empty section}%
5503 \LWR@stoppars%
```

Cancel special `minipage` horizontal space interaction:

```
5504 \global\boolefalse{LWR@minipagethispar}%
```

Start a new HTML file unless starred, and if is a shallow sectioning depth.

Exception: Also start a new HTML file for \part*, for **appendix**.

Generate a new L^AT_EX page so that toc and index page number points to the section:

```

5505 \LWR@traceinfo{LWR@section: testing whether to start a new HTML file}%
5506 \IfBooleanT{#1}{\LWR@traceinfo{LWR@section: starred}}%
5507 \ifbool{LWR@forcinghtmlpage}{\LWR@traceinfo{LWR@section: forcinghtmlpage}{}%}
5508 \ifthenelse{%
5509   \(%
5510   \\\(\NOT\equal{#1}{\BooleanTrue})\OR%
5511   \\\cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}\OR%
5512   \\\boolean{LWR@forcinghtmlpage})%
5513 \)%
5514 \AND%
5515 \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{FileDepth}}%
5516 \AND%
5517 \(%
5518   \NOT\boolean{CombineHigherDepths}\OR%
5519   \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{LWR@prevFileDepth}}%
5520 \)%
5521 \AND%

5522 \(% phantomsection
5523   \NOT\isempty{#3}%
5524   \OR%
5525   \\\(\NOT\equal{#1}{\BooleanTrue})\%
5526 \)%
5527 }%

```

If so: start a new HTML file:

```

5528 {%
5529   new file
      \LWR@traceinfo{LWR@section: new HTML file}%

```

See if there was an optional TOC name entry:

```

5530 \IfNoValueTF{#2}%

```

If no optional entry

```

5531 {\LWR@newhtmlfile{#3}}%

```

If yes an optional entry

```

5532 {\LWR@newhtmlfile{#2}}%
5533 }% new file

```

Else: No new HTML file:

```
5534 {%
```

Generate a new L^AT_EX page so that toc and index page number points to the section:

```
5535     \LWR@traceinfo{\LWR@section: not a new HTML file, about to \LWR@orignewpage}%
5536     \LWR@orignewpage%
5537
5538 }% not new file
```

Remember this section's name for \nameref:

```
5539 \IfValueT{#3}{%
5540 \LWR@traceinfo{\LWR@section: about to \LWR@setlatestname}%
5541 \IfValueTF{#2}{\LWR@setlatestname{#2}}{\LWR@setlatestname{#3}}%
5542 }%
```

Print an opening comment with the level and the name; ex: “section” “Introduction” Footnotes may be used in section names, which would also appear in the HTML section opening comments, so the short TOC entry is used if possible, and a limited opening comment is made if the sectional unit is starred.

```
5543
5544 \ifbool{HTMLDebugComments}{%
5545     \begingroup%
5546     \LWR@nullfonts%
5547     \IfBooleanTF{#1}{ starred
5548     {\LWR@htmlcomment{Opening #4*}}}
5549     {%
5550         \IfNoValueTF{#2}{ short TOC
5551             {\LWR@htmlcomment{Opening #4 ‘#3’}}%
5552             {\LWR@htmlcomment{Opening #4 ‘#2’}}}
5553     }
5554     \endgroup%
5555 }{}%
5556
```

For inline sections paragraph and subparagraph, start a new paragraph now:

```
5557 \ifthenelse{%
5558     \cnttest{\@nameuse{\LWR@depth#4}}{>}{\LWR@depthparagraph}%
5559 }%
5560 {\LWR@startpars}%
5561 {}%
```

Create the opening tag with an autosec:

```

5562 \LWR@traceinfo{LWR@section: about to LWR@createautosec}%
5563 \LWR@createautosec{\@nameuse{LWR@tag#4}}%

5564 \setcounter{LWR@currentautosec}{\value{page}}

```

Check if starred:

```

5565 \IfBooleanTF{#1}%
5566 {%
5567 \LWR@traceinfo{LWR@section: starred}%

```

Starred, but also forcing a TOC entry, so add unnumbered TOC name or regular name:

```

5568 \ifbool{LWR@forcinghtmltoc}%
5569 {\addcontentsline{toc}{#4}{\IfValueTF{#2}{#2}{#3}}}%
5570 {}%
5571 }% starred

```

Not starred, so step counter and add to TOC:

```
5572 {}% not starred
```

Only add a numbered TOC entry if section number is not too deep:

```

5573 \ifthenelse{%
5574     \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{secnumdepth}}%
5575 }%
5576 {}% if secnumdepth

```

If in the main matter, step the counter and add the TOC entry. For article class, **lwarf** assumes that all is mainmatter.

```

5577 \LWR@traceinfo{LWR@section: about to test main matter}%
5578 \ifbool{LWR@mainmatter}%
5579 {}%
5580 \LWR@traceinfo{LWR@section: yes mainmatter}%
5581 \refstepcounter{#4}%

```

Add main matter numbered TOC entry with the TOC name or the regular name:

```

5582 \LWR@traceinfo{LWR@section: about to addcontentsline}%
5583 \addcontentsline{toc}{#4}%
5584 {}%
5585 \protect\numberline{\@nameuse{the#4}}%
5586 {\ignorespaces\IfValueTF{#2}{#2}{#3}\protect\relax}%
5587 }%

```

```

5588          \LWR@traceinfo{LWR@section: finished addcontentsline}%
5589      }% end of if main matter

```

If not main matter, add unnumbered TOC name or regular name:

```

5590      {%
5591          \LWR@traceinfo{LWR@section: no main matter}%
5592          \addcontentsline{toc}{#4}{\IfValueTF{#2}{#2}{#3}}%
5593      }% end of not main matter
5594  }% end of secnumdepth

```

Deeper than secnumdepth, so add an unnumbered TOC entry:

```

5595      {%
5596          \addcontentsline{toc}{#4}{\IfValueTF{#2}{#2}{#3}}%
5597      }%

```

For part, print the section type:

```

5598      \ifbool{LWR@mainmatter}%
5599      {%
5600          \ifthenelse{%
5601              \(\cnttest{\@nameuse{LWR@depth#4}}\{<=}\}%
5602              {\value{secnumdepth}}\() \AND%
5603              \(\cnttest{\@nameuse{LWR@depth#4}}\{<=\{\LWR@depthpart}\}\)%
5604          }%
5605          {\@nameuse{#4name}\~{}}
5606      }%

```

Print the section number:

```

5607          \LWR@traceinfo{LWR@section: about to print section number}%
5608          \ifthenelse{%
5609              \cnttest{\@nameuse{LWR@depth#4}}\{<=}\{\value{secnumdepth}}\}%
5610          }%
5611          {%
5612              \ifstreq{\#4}{chapter}%
5613                  {\protect\LWR@sectionnumber{\@chapcntformat{#4}}\}%
5614                  {\protect\LWR@sectionnumber{\@secntformat{#4}}\}%
5615          }%
5616          {}%
5617          \LWR@traceinfo{LWR@section: finished print section number}%
5618      }{}%
5619 }% end of not starred

```

Print the section name:

```

5620 \LWR@traceinfo{LWR@section: about to print the section name}%
5621 #3%

```

Close the heading tag, such as /H2:

```
5622 \LWR@traceinfo{LWR@section: about to close the heading tag}%
5623 \LWR@htmlltag{\@nameuse{LWR@tag#4end}}%
```

Generate a L^AT_EX label:

```
5624 \LWR@traceinfo{LWR@section: about to create the LaTeX label}%
5625 \LWR@newautopagelabel{LWR@currentautosec}%
```

Start paragraph handing unless is an inline paragraph or subparagraph:

```
5626 \ifthenelse{%
5627     \cnttest{\@nameuse{LWR@depth#4}}{<}{\LWR@depthparagraph}%
5628 }%
5629 {\LWR@startpars}%
5630 {}%
```

If not starred, remember the previous depth to possibly trigger a new HTML page.

HOWEVER, allow a `\part*` to start a new HTML page. This is used by **appendix**.

A starred section does not trigger a new HTML page at the beginning of this macro, so it should not affect it here at the end either. This became an issue when a `\listoftables` was tested in the middle of the document. The `\chapter*` for the list was not allowing a new HTML page for the section following it while `CombineHigherDepths` was true.

```
5631 \ifthenelse{%
5632     \NOT\equal{#1}{\BooleanTrue}\OR%
5633     \cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}%
5634 }%
5635 {%
5636     \setcounter{LWR@prevFileDepth}{\@nameuse{LWR@depth#4}}%
5637 }%
5638 {}%
```

Reset to defaults if not a phantomsection:

```
5639 \ifstrempty{#3}%
5640 {}%
5641 {%
5642 \global\boolefalse{LWR@forcinghtmlpage}%
5643 \global\boolefalse{LWR@forcinghtmltoc}%
5644 }%
5645 %
5646 \LWR@traceinfo{LWR@section: done}%
5647 }
```

59.4 \section and friends

```
\part * [<TOC name>] {<name>}

5648 \newcommand{\part@preamble}{}% for koma-script
5649
5650 \DeclareDocumentCommand{\part}{s o m}%
5651 \LWR@maybeprintpendingfootnotes{\LWR@depthpart}%
5652 \LWR@stoppars%
5653
5654 \LWR@startnewdepth{\LWR@depthpart}{\LWR@printclosepart}%
5655
5656 \LWR@section{#1}{#2}{#3}{part}%
5657
5658 \part@preamble% for koma-script
5659 \renewcommand{\part@preamble}{}%
5660 }

\chapter * [<TOC name>] [<heading name>] {<name>}

5661 \let\@printcites\relax% for quotchap package
5662
5663 \newcommand{\chapter@preamble}{}% for koma-script
5664
5665 \@ifundefined{chapter}
5666 {}
5667 %
5668 \DeclareDocumentCommand{\chapter}{s o o m}%
5669 \IfValueTF{#2}{%
5670 \LWR@traceinfo{chapter #2}%
5671 }{%
5672 \LWR@traceinfo{chapter #4}%
5673 }
5674 \LWR@maybeprintpendingfootnotes{\LWR@depthchapter}%
5675 \LWR@stoppars%
5676
5677 \LWR@startnewdepth{\LWR@depthchapter}{\LWR@printclosechapter}%
5678
5679 \LWR@section{#1}{#2}{#4}{chapter}%
5680
5681 \@printcites% for quotchap package
5682
5683 \chapter@preamble% for koma-script
5684 \renewcommand{\chapter@preamble}{}%
5685 }
5686 }
```

```
\section * [<TOC name>] [<heading name>] {<name>}

5687 \DeclareDocumentCommand{\section}{s o o m}{%
5688 \IfValueTF{#2}{%
5689 \LWR@traceinfo{section #2}%
5690 }{%
5691 \LWR@traceinfo{section #4}%
5692 }%
5693 \LWR@maybeprintpendingfootnotes{\LWR@depthsection}%
5694 \LWR@stoppars%
5695 %
5696 \LWR@startnewdepth{\LWR@depthsection}{\LWR@printclosesection}%
5697 %
5698 \LWR@section{#1}{#2}{#4}{section}%
5699 }

\subsection * [<TOC name>] {<name>}

5700 \DeclareDocumentCommand{\subsection}{s o m}{%
5701 \LWR@maybeprintpendingfootnotes{\LWR@depthsubsection}%
5702 \LWR@stoppars%
5703 %
5704 \LWR@startnewdepth{\LWR@depthsubsection}{\LWR@printclosesubsection}%
5705 %
5706 \LWR@section{#1}{#2}{#3}{subsection}%
5707 }

\subsubsection * [<TOC name>] {<name>}

5708 \DeclareDocumentCommand{\subsubsection}{s o m}{%
5709 \LWR@maybeprintpendingfootnotes{\LWR@depthsubsubsection}%
5710 \LWR@stoppars%
5711 %
5712 \LWR@startnewdepth{\LWR@depthsubsubsection}{\LWR@printclosesubsubsection}%
5713 {\LWR@printclosesubsubsection}%
5714 %
5715 \LWR@section{#1}{#2}{#3}{subsubsection}%
5716 }

\paragraph * [<TOC name>] {<name>}

5717 \DeclareDocumentCommand{\paragraph}{s o m}{%
5718 \LWR@maybeprintpendingfootnotes{\LWR@depthparagraph}%
5719 \LWR@stoppars%
5720 %
5721 \LWR@startnewdepth{\LWR@depthparagraph}{\LWR@printcloseparagraph}%
5722 }
```

```

5723 \LWR@section{#1}{#2}{#3}{paragraph}%
5724 }

\subparagraph * [<TOC name>] {<name>}

5725 \DeclareDocumentCommand{\subparagraph}{s o m}{%
5726 \LWR@maybeprintpendingfootnotes{\LWR@depthsubparagraph}%
5727 \LWR@stoppars%
5728
5729 \LWR@startnewdepth{\LWR@depthsubparagraph}{\LWR@printclosesubparagraph}%
5730
5731 \LWR@section{#1}{#2}{#3}{subparagraph}%
5732 }

5733 \end{warpHTML}

```

60 Starting a new file

for HTML & PRINT: 5734 \begin{warpall}

\HTMLLanguage Default language for the HTML lang tag.

```

5735 \newcommand*{\LWR@currentHTMLLanguage}{en-US}
5736
5737 \newcommand*{\HTMLLanguage}[1]{%
5738 \renewcommand*{\LWR@currentHTMLLanguage}{#1}%
5739 }

5740 \end{warpall}

```

for HTML output: 5741 \begin{warpHTML}

\LWR@filestart {<title_suffix>}

Creates the opening HTML tags.

```

5742 \newcommand*{\LWR@filestart}[1]{%
5743 \LWR@traceinfo{\LWR@filestart !#1!}}

```

Locally temporarily disable direct-formatting commands:

```

5744 \begingroup
5745 \LWR@nullfonts

```

Create the page's HTML header:

```
5746 \LWR@htmlltag{!DOCTYPE html}\LWR@orignewline
```

The language is user-adjustable:

```
5747 \LWR@htmlltag{html lang="\LWR@currentHTMLLanguage"}\LWR@orignewline
```

Start of the meta data:

```
5748 \LWR@htmlltag{head}\LWR@orignewline
```

Charset is fixed at UTF-8:

```
5749 \LWR@htmlltag{meta charset="UTF-8" /}\LWR@orignewline
```

Author:

```
5750 \ifthenelse{\equal{\theHTMLAuthor}{}}{%
5751 {}%
5752 {\LWR@htmlltag{meta name="author" content="\theHTMLAuthor" /}\LWR@orignewline}%
}
```

lwarf is the generator:

```
5753 \LWR@htmlltag{meta name="generator" content="LaTeX lwarf package" /}%
5754 \LWR@orignewline
```

If there is a description, add it now:

```
5755 \ifdefempty{\LWR@currentHTMLDescription}{%
5756 \LWR@htmlltag{%
5757 meta name="description" content="\LWR@currentHTMLDescription" /}%
5758 \LWR@orignewline
5759 }%
```

Mobile-friendly viewport:

```
5760 \LWR@htmlltag{meta name="viewport" %
5761 content="width=device-width, initial-scale=1.0" /}%
5762 \LWR@orignewline
```

IE patch:

```
5763 \LWR@htmlltag{!{-}{-}[if lt IE 9]}\LWR@orignewline
5764 \LWR@htmlltag{%
5765 script src="http://html5shiv.googlecode.com/svn/trunk/html5.js"%
5766 \LWR@htmlltag{/script}\LWR@orignewline
5767 \LWR@htmlltag{![endif]{-}{-}}\LWR@orignewline
```

The page's title:

```
5768 \ifthenelse{\equal{\theHTMLTitle}{}}%
5769 {}%
5770 {\LWR@htmltag{title}\theHTMLTitle#1\LWR@htmltag{/title}\LWR@orignewline}%
```

The page's stylesheet:

```
5771 \LWR@htmltag{%
5772 link rel="stylesheet" type="text/css" href="\LWR@currentcss" /}%
5773 \LWR@orignewline
```

Optional MATHJAX support. The `HTML` tags must be turned off during the verbatim input, and the paragraph handling which was turned on at the end of verbatim input must be immediately turned off again.

```
5774 \ifbool{mathjax}%
5775 {}%
5776   \begingroup%
5777   \LWR@restoreoriglists%
5778   \boolfalse{LWR@verbtags}%
5779   \verbatiminput{lwarp_mathjax.txt}%
5780   \booltrue{LWR@verbtags}%
5781   \endgroup%
5782   \LWR@stopars
5783 }% end of mathjax
5784 {}%
```

End of the header:

```
5785 \LWR@htmltag{/head}\LWR@orignewline
```

Start of the body:

```
5786 \LWR@htmltag{body}\LWR@orignewline
5787 \endgroup
5788 \LWR@traceinfo{LWR@filestart: done}
5789 }

5790 \end{warpHTML}
```

61 Starting HTML output

for HTML output: 5791 `\begin{warpHTML}`

\LWR@LwarpStart Executed at the beginning of the entire document.

```
5792 \catcode`\$=\active
5793 \newcommand*\{LWR@LwarpStart}
5794 {%
5795 \LWR@traceinfo{LWR@LwarpStart}
```

If formatting for a word processor, force filedepth to single-file only, force HTML debug comments off.

```
5796 \ifbool{FormatWP}{%
5797   \setcounter{FileDepth}{-5}%
5798   \boolfalse{HTMLDebugComments}%
5799 }{}
```

Expand and detokenize \HomeHTMLFilename and \HTMLFilename:

```
5800 \edef\LWR@strresult{\HomeHTMLFilename}
5801 \edef\HomeHTMLFilename{\detokenize\expandafter{\LWR@strresult}}
5802 \edef\LWR@strresult{\HTMLFilename}
5803 \edef\HTMLFilename{\detokenize\expandafter{\LWR@strresult}}
```

Force onecolumn and empty page style:

```
5804 \LWR@origonecolumn%
5805 \LWR@origpagestyle{empty}%
```

No black box for overfull lines:

```
5806 \overfullrule=0pt
```

Reduce chance of line overflow in verbatim environments:

```
5807 \LWR@print@scriptsize%
```

In PDF output, don't allow line breaks to interfere with HTML tags:

```
5808 \LWR@print@raggedright%
5809 \LetLtxMacro{\\"}{\LWR@endofline}%
```

Spread the lines for **pdftotext** to read them well:

```
5810 \linespread{1.3}%
```

For **pdftotext** to reliably identify paragraph splits:

```
5811 \setlength{\parindent}{0pt}
5812 \setlength{\parskip}{2ex}
```

For the `lateximages` record file:

```
5813 \immediate\openout\LWR@lateximagesfile=lateximages.txt
```

Removes space around the caption in the HTML:

```
5814 \setlength{\belowcaptionskip}{0ex}
5815 \setlength{\abovecaptionskip}{0ex}
```

Redefine the plain page style to be empty when used by index pages:

```
5816 \renewcommand{\ps@plain}{}{}
```

Plug in some new actions. This is done just before the document start so that they won't be over-written by some other package.

Tabular:

```
5817 \LetLtxMacro\LWR@origtabular\tabular
5818 \LetLtxMacro\LWR@origendtabular\endtabular
5819 \LetLtxMacro\tabular\LWR@tabular
5820 \LetLtxMacro\endtabular\endLWR@tabular
```

Float captions:

```
5821 \let\LWR@origcaption\caption
```

Label in HTML Labels: `\ltx@label` is used in `amsmath` environments and is also patched by `cleveref`.

```
5822 \let\LWR@origltx@label\ltx@label
5823 \let\ltx@label\LWR@htmlmathlabel
```

Logos:

```
5824 \let\TeX\LWR@TeX
5825 \let\LaTeX\LWR@LaTeX
5826 \let\LuaTeX\LWR@LuaTeX
5827 \let\LuaLaTeX\LWR@LuaLaTeX
5828 \let\XeTeX\LWR@XeTeX
5829 \let\XeLaTeX\LWR@XeLaTeX
5830 \let\ConTeXt\LWR@ConTeXt
```

Not yet started any paragraph handling:

```
5831 \global\boolearn{LWR@doingapar}
5832 \global\boolearn{LWR@doingstartpars}
```

Document and page settings:

```
5833 \mainmatter  
5834 \LWR@origpagenumbering{arabic}
```

Start a new HTML file and a header:

```
5835 \LWR@traceinfo{\LWR@l warpStart: Starting new file.}  
5836 \LWR@filestart{}  
5837 \LWR@traceinfo{\LWR@l warpStart: Generating first header.}  
5838 \LWR@htmltag{header}\LWR@orignewline  
5839 \LWR@startpars  
5840 \LWR@firstpagetop  
5841 \LWR@stoppars  
5842 \LWR@htmltag{/header}\LWR@orignewline  
5843 \LWR@traceinfo{\LWR@l warpStart: Generating textbody.}  
5844 \LWR@htmltag{section class="textbody"}
```

Patch the `itemize`, `enumerate`, and `description` environments and `\item`. This works with the native L^AT_EX environments, as well as those provided by `enumitem`, `enumerate`, and `paralist`.

```
5845 \LWR@patchlists
```

Ensure that math mode is active to call **l warp**'s patches:

```
5846 \catcode`$=\active
```

Required for `\nameref` to work with SVG math:

```
5847 \immediate\write\@mainaux{\catcode`\$=\active} %  
5848 \LetLtxMacro{\LWR@syntaxhighlightone$}{% balance for editor syntax highlighting}
```

Allow HTML paragraphs to begin:

```
5849 \LWR@startpars
```

If using MathJax, disable `\ensuremath` by printing a nullified definition at the start of each file, and add further customizations:

```
5850 \LWR@customizeMathJax  
  
5851 \LWR@traceinfo{\LWR@l warpStart: done}  
5852 }  
5853 \catcode`$=3% math shift until l warp starts  
  
5854 \end{warpHTML}
```

62 Ending HTML output

for HTML output: 5855 \begin{warpHTML}

\LWR@requesttoc {<boolean>} {<suffix>} Requests that a toc, lof, or lot be generated.

```
5856 \newcommand*\LWR@requesttoc[2]{%
5857 \ifbool{#1}{%
5858 {%
5859   \expandafter\newwrite\@nameuse{tf@#2}%
5860   \immediate\openout \@nameuse{tf@#2} \jobname.#2\relax
5861 }{}%
5862 }
```

\LWR@LwarpEnd Final stop of all HTML output:

```
5863 \newcommand*\LWR@LwarpEnd{%
5864 {%
5865 \LWR@stopars
5866 \LWR@closeprevious{\LWR@depthfinished}}
```

At the bottom of the ending file:

Close the textbody:

5867 \LWR@htmlelementclassend{section}{textbody}

Print any pending footnotes:

5868 \LWR@printpendingfootnotes

Create the footer:

```
5869 \LWR@htmlelement{footer}
5870
5871 \LWR@pagebottom
5872
5873 \LWR@htmlelementend{footer}
```

No bottom navigation if are finishing the home page, or if formatting for an EPUB or word processor.

Presumably has a table-of-contents.

```
5874 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}{%
5875 {}}
```

```

5876 {
5877     \ifnumcomp{\value{LWR@htmlfilename}}{>}{0}{\LWR@botnavigation}{}
5878 }

5879 \LWR@stopars% final stop of all paragraphs

```

Finish the HTML file:

```

5880 \LWR@htmllag{/body}\LWR@orignewline
5881 \LWR@htmllag{/html}\LWR@orignewline

```

Seems to be required sometimes:

```
5882 \LWR@orignewpage
```

For `lateximage` commands:

```

5883 \immediate\closeout\LWR@lateximagesfile
5884 }

5885 \end{warpHTML}

```

63 Title page

package support **⚠ load order** **lwarf** supports the native \LaTeX titling commands, and also supports the packages **authblk** and **titling**. If both are used, **authblk** should be loaded before **titling**.

\published and \subtitle If using the **titling** package, additional titlepage fields for `\published` and `\subtitle` may be added by using `\AddSubTitlePublished` in the preamble. See section [63.8](#).

affiliation **lwarf** provides for the `\author` macro an additional `\affiliation` macro to provide an affiliation and other additional information for each author in the title page. The affiliation information is removed when using **titlingpage**'s `\theauthor` in the main text.

reusing titlepage information The **titling** package maintains the definitions of `\thetitle`, `\theauthor`, etc., after the title has been typeset. These commands are to be used to refer to the document's title and author, etc., in the main text. These definitions have the `\thanks` and `\affiliation` removed, and for `\author` the `\and` is replaced to generate a simple inline list of authors separated by commas. Note: `\theauthor` does not work well with **authblk** unless the traditional \LaTeX syntax is used.

⚠ \theauthor, authblk

custom titlepages `\printtitle`, `\printauthor`, etc., are provided for use inside a custom **titlepage** or **titlingpage** environment, and these retain the `\thanks` and `\affiliation`.

- \printthanks \printthanks has been added to force the printing of thanks inside a `titlingpage` environment when `\maketitle` is not used.
-  `\thanks` Inside a `\titlepage` or `\titlingpage` environment, use `\thanks` instead of `\footnote` for acknowledgements, etc.

63.1 Setting the title, etc.

The following provide setting commands for both `HTML` and print outputs.

- \author {\langle author\rangle} While using `\maketitle` and print mode, the author is treated as a single-column tabular and the `\and` feature finishes the current tabular then starts a new one for the next author. Each author thus is placed into its own tabular, and an affiliation may be placed on its own line such as

```
\author{Name \\ Affiliation \and Second Name \\ Second Affiliation}
```

For `HTML`, the entire author block is placed inside a `<div>` of class `author`, and each individual author is inside a `<div>` of class `oneauthor`.

- \@title \@title, \@author, etc. store the values as originally assigned, including any \thanks, \and, or \affiliation. These are low-level macros intended to be used by other macros only inside a `titlepage` or `titlingpage`, and are used by `\maketitle`. The author is printed inside a single-column tabular, which becomes multiple single-column tabulars if multiples authors are included. For `HTML`, these tabulars become side-by-side `<div>`s of class `oneauthor`, all of which are combined into one `<div>` of class `author`.

- \printtitle \printtitle, etc. are user-level macros intended to be used in custom `titlepage` or `titlingpage` environments in cases where `\maketitle` is not desired. These commands preserve the `\thanks`, etc., and should not be used in the main text.

- \thetitle \thetitle, \theauthor, and \thedate are available if `titling` has been loaded, and are sanitized user-level versions from which have been removed the `\thanks` and `\affiliation`, and `\and` is changed for inline text usage. The author is printed inline without `\affiliation` or `\thanks`, with `\and` placing commas between multiple authors. Thus, these commands are to be used in the main text whenever the user wishes to refer to the document's title and such. One practical use for this is to place the authors at the bottom of each `HTML` page, such as:

```
\HTMLPageBottom {\langle text\rangle}
```

```
\HTMLPageBottom{
\begin{center}\textcopyright~2016 \theauthor\end{center}
}
```

⚠ **\theauthor, authblk** `\theauthor` does not work well if **authblk** is used. If `\theauthor` is important, it is recommended to use the standard L^AT_EX syntax for `\author`, optionally with **l warp**'s `\affiliation` macro as well.

⚠ **affiliations** After `\maketitle` has completed, `\theauthor` retains the definition of the author, but `\and` is changed to become a comma and a space, intending to print the authors names separated by spaces. This fails when affiliations are included on their own table rows.

\affiliation A solution, provide here, is to define a macro `\affiliation` which, during `\maketitle`, starts a new row and adds the affiliation, but after `\maketitle` is finished `\affiliation` is re-defined to discard its argument, thus printing only the author names when `\author` is later used inline.

63.2 \if@titlepage

for HTML & PRINT: 5886 `\begin{warpall}`

`\if@titlepage` Some classes do not provide `\if@titlepage`. In this case, provide it and force it `false`.

```
5887 \ifcsvoid{@titlepagefalse}{
5888     \newif\if@titlepage
5889     \if@titlepagefalse
5890 }{}
```

5891 `\end{warpall}`

63.3 Changes for \affiliation

\affiliation `\{<text>\}`

Adds the affiliation to the author for use in `\maketitle`.

Inside `titlepage`, this macro prints its argument. Outside, it is null.

for HTML & PRINT: 5892 `\begin{warpall}`
 5893 `\providerobustcmd{\affiliation}[1]{}`
 5894 `\end{warpall}`

for PRINT output: 5895 `\begin{warpprint}`

5896 `\AtBeginEnvironment{titlepage}{`

```

5897 \renewrobustcmd{\affiliation}[1]{\\ \textsc{\small#1}}
5898 }
5899
5900 \AtBeginDocument{
5901 \@ifpackageloaded{titling}{
5902 \AtBeginEnvironment{titlingpage}{
5903 \renewrobustcmd{\affiliation}[1]{\\ \textsc{\small#1}}
5904 }
5905 }{}% titling loaded
5906 }% AtBeginDocument

5907 \end{warpprint}

```

for HTML output: 5908 \begin{warpHTML}

Env `titlepage` Sets up a `<div>` of class `titlepage`. Provided even for `memoir` class, since it is used by `\maketitle`.

```

5909 \DeclareDocumentEnvironment{titlepage}{}
5910 {
5911 \renewrobustcmd{\affiliation}[1]{\\ \InlineClass{affiliation}{##1}}
5912 \LWR@printpendingfootnotes
5913 \LWR@forcenewpage
5914 \BlockClass{titlepage}
5915 }
5916 {
5917 \endBlockClass
5918 \LWR@printpendingfootnotes
5919 }

5920 \end{warpHTML}

```

63.4 Printing the thanks

for HTML & PRINT: 5921 \begin{warpall}

`\printthanks` Forces the `\thanks` to be printed.

This is necessary in a `titlingpage` environment when `\maketitle` was not used.

```

5922 \newcommand*{\printthanks}{\@thanks}

5923 \end{warpall}

```

63.5 Printing the title, etc. in HTML

The following are for printing the title, etc. in a `titlepage` or a `titlingpage` in HTML:

for HTML output: 5924 `\begin{warpHTML}`

`\printtitle`

```
5925 \newcommand*{\printtitle}{%
5926 {
5927 \LWR@stoppars
5928 \LWR@htmltag{\LWR@tagtitle}%
5929 \@title%
5930 \LWR@htmltag{\LWR@tagtitleend}
5931 \LWR@startpars
5932 }
```

`\LWR@printthetitle` A private version which prints the title without footnotes, used to title each HTML page.

```
5933 \newcommand*{\LWR@printthetitle}{%
5934 {
5935 \LWR@stoppars
5936 \LWR@htmltag{\LWR@tagtitle}%
5937 \thetitle%
5938 \LWR@htmltag{\LWR@tagtitleend}
5939 \LWR@startpars
5940 }
```

`\printauthor` HTML version.

```
5941 \newcommand*{\printauthor}{%
```

The entire author block is contained in a `<div>` named `author`:

```
5942 \begin{BlockClass}{author}
```

`\and` finishes one author and starts the next:

```
5943 \renewcommand{\and}{%
5944 \end{BlockClass}
5945 \begin{BlockClass}{oneauthor}
5946 }
```

Individual authors are contained in a `<div>` named `oneauthor`:

```

5947 \begin{BlockClass}{oneauthor}
5948 \@author
5949 \end{BlockClass}
5950 \end{BlockClass}
5951 }

\printdate

5952 \newcommand*\printdate{\%
5953 \begin{BlockClass}{titledate}
5954 \@date
5955 \end{BlockClass}
5956 }

5957 \end{warpHTML}

```

63.6 Printing the title, etc. in print form

The following are for printing the title, etc. in a `titlepage` or a `titlingpage` in print form:

for PRINT output:

```

5958 \begin{warpprint}

\printtitle

5959 \newcommand*\printtitle{{\Huge \@title}}


\printauthor Print mode.

5960 \newcommand*\printauthor
5961   {\large\begin{tabular}[t]{c}\@author\end{tabular}}
```

\printdate

```

5962 \newcommand*\printdate{{\small\textrit{\@date}}}

5963 \end{warpprint}

```

63.7 \maketitle for HTML output

An HTML `<div>` of class `titlepage` is used.

\thanks are a form of footnotes used in the title page. See section 56 for other kinds of footnotes.

See \thanksmarkseries{series}, below, to set the style of the footnote marks.

for HTML output: 5964 \begin{warpHTML}

```

5965 \@ifclassloaded{memoir}
5966 {
5967 \newcommand{\LWR@setfootnoteseries}{%
5968     \renewcommand\thefootnote{\@arabic\c@footnote}%
5969 }
5970 }{%
5971 \if@titlepage
5972 \newcommand{\LWR@setfootnoteseries}{%
5973     \renewcommand\thefootnote{\@arabic\c@footnote}%
5974 }
5975 \else
5976 \newcommand{\LWR@setfootnoteseries}{%
5977     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
5978 }
5979 \fi
5980 }{%
5981 \else
5982 \LWR@maketitlesetup
5983 \def\@makefnmark{\textsuperscript{\thefootnote}}%
5984 \long\def\@makefntext##1{%
5985 \textsuperscript{\@thefnmark}~%
5986 \makethanksmark \Rightarrow \thanksfootmark \Rightarrow \tamark \Rightarrow
5987 \@thefnmark \Rightarrow \itshape a (or similar)
5988 }%
5989 }
```

\LWR@maketitlesetup Patches \thanks macros.

5981 \newcommand*{\LWR@maketitlesetup}{%

Redefine the footnote mark:

```

5982 \LWR@setfootnoteseries%
5983 \def\@makefnmark{\textsuperscript{\thefootnote}}%
```

```

\thefootnote \Rightarrow \nameuse{arabic}{footnote}, or
\thefootnote \Rightarrow \nameuse{fnsymbol}{footnote}
```

Redefine the footnote text:

5984 \long\def\@makefntext##1{%

Make the footnote mark and some extra horizontal space for the tags:

5985 \@thefnmark~%

```

\makethanksmark \Rightarrow \thanksfootmark \Rightarrow \tamark \Rightarrow
\@thefnmark \Rightarrow \itshape a (or similar)
```

Print the text:

```
5986 ##1%
5987 }%
5988 }
```

```
\@fnsymbol {\langle counter\rangle}
```

Re-defined to use an `HTML` entity for the double vertical bar symbol. The original definition used `\|` which was not being seen by `pdftotext`.

```
5989 \def\@fnsymbol#1{\ifcase#1\or *\or \HTMLentity{dagger}\or \HTMLentity{Dagger}\or
5990   \HTMLentity{sect}\or \HTMLentity{para}\or \text{\HTMLunicode{2016}}\or
5991   **\or \HTMLentity{dagger}\HTMLentity{dagger} \or
5992   \HTMLentity{Dagger}\HTMLentity{Dagger} \else\@ctrerr\fi}
```

`\maketitle` `HTML` mode. Creates an `HTML` titlepage div and typesets the title, etc.

Code from the `titling` package is adapted, simplified, and modified for `HTML` output.

```
5993 \renewcommand*\maketitle{%
```

An `HTML` titlepage `<div>` is used for all classes.

```
5994 \begin{titlepage}
```

Set up special patches:

```
5995 \LWR@maketitlesetup
```

Typeset the title, etc:

```
5996 \@maketitle
```

Immediately generate any `\thanks` footnotes:

```
5997 \@thanks
```

Close the `HTML` titlepage div and cleanup:

```
5998 \end{titlepage}
5999 \setcounter{footnote}{0}%
6000 \global\let\thanks\relax
6001 \global\let\maketitle\relax
6002 \global\let\@maketitle\relax
6003 \global\let\@thanks\empty
```

```

6004 \global\let\@author\@empty
6005 \global\let\@date\@empty
6006 \global\let\@title\@empty
6007 \global\let\title\relax
6008 \global\let\author\relax
6009 \global\let\date\relax
6010 \global\let\and\relax
6011 }

```

\@maketitle HTML mode. Typesets the title, etc.:

```

6012 \DeclareDocumentCommand{\@maketitle}{}{%
6013     \LWR@stoppars\LWR@htmltag{\LWR@tagtitle}%
6014     \@title%
6015     \LWR@htmltag{\LWR@tagtitleend}\LWR@startpars%
6016     \begin{BlockClass}{author}%

```

For **IEEEtran** class:

```

6017     \renewcommand*{\cr}{}%
6018     \renewcommand*{\crcr}{}%
6019     \renewcommand*{\noalign}{}%

6020     \renewcommand{\and}{%
6021         \end{BlockClass}%
6022         \begin{BlockClass}{oneauthor}%
6023     }%
6024         \begin{BlockClass}{oneauthor}%
6025             \@author%
6026             \end{BlockClass}%
6027         \end{BlockClass}%
6028         \begin{BlockClass}{titledate}%
6029             \@date%
6030         \end{BlockClass}%
6031 }

```

\LWR@titlingmaketitle \maketitle for use inside an HTML titlingpage environment.

```
6032 \newcommand*{\LWR@titlingmaketitle}{%
```

Keep pending footnotes out of the title block:

```
6033 \@thanks
```

Set up special patches:

```
6034 \LWR@maketitlesetup
```

Typeset the title, etc:

6035 \@maketitle

Immediately generate any \thanks footnotes:

6036 \@thanks
6037 }

6038 \end{warpHTML}

63.8 \published and \subtitle

\subtitle and \published To add \subtitle and \published to the titlepage, load the **titling** package and use \AddSubtitlePublished in the preamble.

The default lwarf.css has definitions for the published and subtitle classes.

If **titling** is loaded, \AddSubtitlePublished creates a number of additional macros, and also assigns some of the **titling** hooks. If **titling** is not loaded, \AddSubtitlePublished creates null macros.

⚠ titling hooks Do not use \AddSubtitlePublished if the user has patched the **titling** hooks for some other reason. Portions are marked \warpprintonly to reduce extra tags in HTML. Similarly, BlockClass has no effect in print mode. Thus, the following may be marked warpall.

for HTML & PRINT: 6039 \begin{warpall}

\AddSubtitlePublished Adds \published and \subtitle, and related.

```
6040 \newcommand*\AddSubtitlePublished{%
6041 \@ifpackageloaded{titling}{% yes titling package
6042   \newcommand{\@published}{}%
6043   \newcommand{\published}[1]{\gdef\@published{\#1}}%
6044   \renewcommand{\maketitlehooka}{\printpublished}%
6045   \newcommand{\printpublished}{%
6046     \warpprintonly{\begin{center}\unskip}%
6047     \begin{BlockClass}{published}%
6048     \warpprintonly{\large\itshape}%
6049     \@published%
6050     \end{BlockClass}%
6051     \warpprintonly{\end{center}}%
6052   }%
6053   \newcommand{\@subtitle}{}%
6054   \newcommand{\subtitle}[1]{\gdef\@subtitle{\#1}}%
```

```

6055     \renewcommand*\maketitlehookb{\printsubtitle}%
6056     \newcommand*\printsubtitle{%
6057         \warpprintonly{\begin{center}\unskip}%
6058         \begin{BlockClass}{subtitle}%
6059         \warpprintonly{\Large\itshape}%
6060         @subtitle%
6061         \end{BlockClass}%
6062         \warpprintonly{\end{center}}%
6063     }%
6064 }% yes titling package
6065 {%- no titling package
6066     \newcommand{\published}[1]{}
6067     \newcommand*\printpublished{}%
6068     \newcommand{\subtitle}{}%
6069     \newcommand*\printsubtitle{}%
6070 }% no titling package
6071 }% \AddSubtitlePublished

6072 \end{warpall}

```

64 Abstract

The following code replaces the L^AT_EX default, and will itself be replaced later if the **abstract** package is loaded.

for HTML output: 6073 \begin{warpHTML}

\abstractname User-redefinable title for the abstract.

Also over-written by the **babel** package.

6074 \providecommand*\abstractname{Abstract}

Some classes allow an optional name, so it is allowed here.

Env abstract

```

6075 \DeclareDocumentEnvironment{abstract}{O{\abstractname}}
6076 {
6077 \LWR@forcenewpage
6078 \BlockClass{abstract}
6079 \BlockClassSingle{abstracttitle}{#1}
6080 }
6081 {

```

```

6082 \endBlockClass
6083 }

6084 \end{warpHTML}

```

65 Quote and verse

65.1 Attributions

\attribution For use with quote, quotation, verse:

Ex: "A quotation." \attribution{\textsc{Author Name}\\\textsl{Book Title}}

for HTML output: 6085 \begin{warpHTML}
6086 \newcommand{\attribution}[1]{%
6087 \begin{BlockClass}{attribution}
6088 #1
6089 \end{BlockClass}
6090 }
6091 \end{warpHTML}

for PRINT output: 6092 \begin{warpprint}
6093 \newcommand{\attribution}[1]{
6094 \begin{flushright}
6095 \unskip
6096 #1
6097 \end{flushright}%
6098 }
6099 \end{warpprint}

65.2 Quotes, quotations

for HTML output: 6100 \begin{warpHTML}

Env quote

```

6101 \renewenvironment*{quote}
6102 {
6103 \LWR@forcenewpage
6104 \LWR@htmlblocktag{blockquote}
6105 }
6106 {\LWR@htmlblocktag{/blockquote}}

```

```

6107
6108 \renewenvironment*{quotation}
6109 {
6110 \LWR@forcenewpage
6111 \LWR@htmlblocktag{blockquotation}
6112 }
6113 {\LWR@htmlblocktag{/blockquotation}}
6114 \end{warpHTML}

```

65.3 Verse

When using `verse` or `memoir`, always place a `\\"` after each line.

- `\attrib` The documentation for the `verse` and `memoir` packages suggest defining an `\attrib` command, which may already exist in current documents, but it will only work for print output. `lwarp` provides `\attribution`, which works for both print and `HTML` output. To combine the two so that `\attrib` is used for print and `\attribution` is used for `HTML`:

```

\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}

```

- Len `\vleftskip` These lengths are used by `verse` and `memoir` to control the left margin, and they may already be set by the user for print output. New lengths `\HTMLvleftskip` and `\HTMLleftmargini` are provided to control the margins in `HTML` output. These new lengths may be set by the user before any `verse` environment, and persist until they are manually changed again. One reason to change `\HTMLleftmargini` is if there is a wide `\flagverse` in use, such as the word “Chorus”, in which case the value of `\HTMLleftmargini` should be set to a wide enough length to contain “Chorus”. The default is wide enough for a stanza number.

⚠ **spacing**

Horizontal spacing relies on `pdftotext`’s ability to discern the layout (`-layout` option) of the text in the `HTML`-tagged PDF output. For some settings of `\HTMLleftmargini` or `\HTMLleftskip` the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

65.3.1 `ETEX core` `verse` environment

for HTML output: 6115 `\begin{warpHTML}`

Env **verse**

```

6116 \renewenvironment{verse}
6117     {\let\\newline% l warp
6118      \list{}{\itemsep     \z@%
6119                  \itemindent   -1.5em%
6120                  \listparindent\itemindent
6121                  \rightmargin \leftmargin
6122                  \advance\leftmargin 1.5em}%
6123      \item\relax}
6124  {\endlist}

6125 \end{warpHTML}
```

for HTML & PRINT: 6126 \begin{warpall}

65.3.2 verse and memoir

The following lengths are used by **verse** and **memoir**. They may be set in either print or HTML output, but are only used in HTML. This allows the user to set **\vleftskip** and **\leftmargini** for print output, and optionally select different values for HTML.

Len **\HTMLvleftskip** Sets **\vleftskip** inside a **verse** environment in HTML.

```

6127 \newlength{\HTMLvleftskip}
6128 \setlength{\HTMLvleftskip}{1em}
```

Len **\HTMLleftmargini** Sets **\leftmargini** inside a **verse** environment in HTML.

```

6129 \newlength{\HTMLleftmargini}
6130 \setlength{\HTMLleftmargini}{4.5em}
```

```
6131 \end{warpall}
```

66 Verbatim and tabbing

for HTML & PRINT: 6132 \begin{warpall}

Len **\VerbatimHTMLWidth** Width to use in HTML **Verbatim** environment.

This width is used when placing line numbers to the right. Ignored during print output.

```
6133 \newlength{\VerbatimHTMLWidth}
6134 \setlength{\VerbatimHTMLWidth}{4in}
6135 \end{warpall}
```

for HTML output: 6136 \begin{warpHTML}

Bool LWR@verbtags Used to temporarily turn off verbatim tags while doing \verb+input+ in the HTML head.

```
6137 \newbool{LWR@verbtags}
6138 \booltrue{LWR@verbtags}
```

\LWR@atbeginverbatim [⟨1: style⟩] {⟨2: negative \baselineskip \vspace⟩} {⟨3: class⟩}

Encloses a verbatim environment with the given css class.

```
6139 \newcommand*{\LWR@atbeginverbatim}[3]{}
6140 {%
```

Avoid excessive space between lines:

```
6141 \setlength{\parskip}{0ex}%
```

Stop generating HTML paragraph tags:

```
6142 \LWR@stopars%
```

Create a new pre of the given class. The tags may temporarily be turned off for internal use, such as loading the MATHJAX script.

```
6143 \ifbool{LWR@verbtags}{%
6144   \LWR@htmltag{pre class="#3"
6145     \ifthenelse{\equal{\#1}{}}{}{style="#1"}}
6146 }%
6147 \LWR@orignewline% pre
6148 \leavevmode\unskip\LWR@print@vspace*{-\#2\baselineskip}%
6149 }{}}
```

Use a mono-spaced font to preserve horizontal positioning. If horizontal alignment is important for the user, use a mono-spaced font in the css for the `verse` class.

```
6150 \begingroup%
```

```
6151 % \LWR@print@normalsize%
6152 \LWR@origttfamily%
6153 \LWR@print@small%
```

Since inside a <pre>, restore the original list processing:

```
6154 \LWR@restoreoriglists%
```

Turn off **babel-french** extra space before punctuation:

```
6155 \LWR@FBcancel%
```

Do not produce HTML tags for \hspace inside a verse par. Restore plain L^AT_EX \hspace functionality:

```
6156 \LWR@select@print@hspace%
6157 }
```

```
\LWR@afterendverbatim {<negative \baselineskip \vspace>}
```

Finishes enclosing a verbatim environment.

```
6158 \newcommand*{\LWR@afterendverbatim}[1]{%
6159 \endgroup%
6160 \par%
```

At the end of the environment, close the pre:

```
6161 \ifbool{\LWR@verbtags}{%
6162   \LWR@print@vspace*{-\#1\baselineskip}%
6163   \noindent\LWR@htmltag{/pre}\LWR@orignewline% pre
6164 }{}}
```

Resume regular paragraph handling:

```
6165 \LWR@startpars%
6166 }
```

```
\verbatiminput {<filename>}
```

Patch \verbatiminput to add HTML tags:

```
6167 \let\LWRV@origverbatim@input\verbatim@input
6168
6169 \renewcommand{\verbatim@input}[2]{%
6170 \ifbool{\LWR@verbtags}{\LWR@forcenewpage}{}}%
6171 \LWR@atbeginverbatim{2.5}{Verbatim}%
6172 \LWRV@origverbatim@input{\#1}{\#2}%
6173 \LWR@afterendverbatim{1.5}%
6174 }
```

Env **verbatim**

```

6175 \AfterEndPreamble{
6176 \LWR@traceinfo{Patching verbatim.}
6177 \AtBeginEnvironment{verbatim}{%
6178 \LWR@forcenewpage%
6179 \LWR@atbeginverbatim{2.5}{verbatim}%
6180 }%
6181 \AfterEndEnvironment{verbatim}{%
6182     \LWR@afterendverbatim{1}%
6183 }%
6184 }

```

Env **tabbing** The tabbing environment works, except that `svg` math and `lateximages` do not yet work inside the environment.

⚠ **math in tabbing** If math is used inside `tabbing`, place `tabbing` inside a `lateximage` environment, which will render the entire environment as a single `svg` image.

```

6185 \newcommand*{\LWR@HTML@tabbing}{%
6186 \LWR@forcenewpage%
6187 \LWR@atbeginverbatim{3}{tabbing}%
6188 \LWR@print@tabbing%
6189 }%
6190
6191 \newcommand*{\LWR@HTML@endtabbing}{%
6192     \LWR@print@endtabbing%
6193     \LWR@afterendverbatim{1}%
6194 }%
6195
6196 \LWR@formatted{tabbing}
6197 \LWR@formatted{endtabbing}

6198 \end{warpHTML}

```

67 Theorems

`\newtheorem` {[*text*] [*counter*] -or- [*oldname*] {[*text*]}

A few minor changes are made to supply HTML tags.

- The entire theorem is placed into a `<div>` of class `theoremcontents`.
- The label for each theorem is placed inside a `` of class `theoremlabel`.

- The contents are placed inside a <div> of class theoremcontents.

```

for HTML output: 6199 \begin{warpHTML}

\@begintheorem {⟨name⟩} {⟨number⟩}

6200 \renewcommand{\@begintheorem}[2]{%
6201 \LWR@forcenewpage
6202 \BlockClass{theoremcontents}
6203 \trivlist
6204 \item[\InlineClass{theoremlabel}{#1\ #2\ }]\itshape
6205 }

\@opargbegintheorem {⟨name⟩} {⟨number⟩} {⟨oparg⟩}

6206 \renewcommand{\@opargbegintheorem}[3]{%
6207 \LWR@forcenewpage
6208 \BlockClass{theoremcontents}
6209 \trivlist
6210 \item[\InlineClass{theoremlabel}{#1\ #2\ (#3)\ }]\itshape
6211 }

\@endtheorem

6212 \renewcommand*{\@endtheorem}{%
6213 \endtrivlist
6214 \endBlockClass% theoremcontents
6215 }

6216 \end{warpHTML}

```

68 Lists

The environments `itemize`, `enumerate`, and `description` are patched when `l warp` is started. These patches support the standard `LATEX` environments, as well as those of `enumerate`, `enumitem`, and `paralist`, and at least the French version of `babel`. Additional patches are done on a package-specific basis.

The `LATEX` source for `itemize` and `enumerate` are found in `source2e`, but the source for `description` is found in `article.cls`, etc.

empty item To have an empty item, use `\mbox{}` or a trailing backslash. This forces a new line in print output, matching the new line which will appear in HTML output. Ex:

```

begin{itemize}
item \mbox{}
\begin{itemize}
...
\end{itemize}
item \
\begin{itemize}
...
\end{itemize}

```

\makelabel While inside a list environment, **l warp** nullifies a number of TeX horizontal skip and fill commands, allowing the user to define **\makelabel** for print mode while HTML mode ignores those commands.

⚠ **label font** When defining **\makelabel** in a list environment, use **\textbf** etc. instead of **\bfseries**.

68.1 List environment

for HTML output: 6217 \begin{warpHTML}

\LWR@printcloselist May be locally redefined by **enumerate** or **description**.

6218 \newcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}

\LWR@printopenlist May be locally redefined by **enumerate** or **description**.

6219 \newcommand*{\LWR@printopenlist}{ul style="\LWR@print@mbox{list-style-type:none}"}

\@mklab Removes PDF spacing.

6220 \AtBeginDocument{
6221 \def\@mklab#1{%
6222 % \hfil %
6223 #1}
6224 \let\makelabel\@mklab
6225 }

\@donoparitem Modified for HTML output by replacing TeX boxes with plain text. Also removes PDF spacing.

6226 \def\@donoparitem{%

```
6227  \c@noparitemfalse
6228 %   \global\setbox\c@labels\hbox{\hskip -\leftmargin
6229 %                               \unhbox\c@labels
6230 %                               \hskip \leftmargin}%
6231 %   \if@minipage\else
6232 %     \c@tempskipa\lastskip
6233 %     \vskip -\lastskip
6234 %     \advance\c@tempskipa\c@outerparskip
6235 %     \advance\c@tempskipa -\parskip
6236 %     \vskip\c@tempskipa
6237 %   \fi
6238 }
```

\c@item Modified for HTML output by replacing TeX boxes with plain text. Also removes PDF spacing.

```
6239 \def\LWR@HTML@citem[#1]{%
6240 \LWR@traceinfo{citem}
6241 \if@c@noparitem
6242   \c@donoparitem
6243 \else
6244 %   \if@c@inlabel
6245 %     \c@indent
6246     \c@par
6247 %   \fi
6248   \c@ifhmode
6249 %   \c@unskip\c@unskip
6250   \c@par
6251 \fi
6252 \c@if@newlist
6253 \c@if@nobreak
6254   \c@nbitem
6255 \else
6256 %   \c@addpenalty\c@beginparpenalty
6257 %   \c@addvspace\c@topsep
6258 %   \c@addvspace{-\c@parskip}%
6259 \fi
6260 \else
6261 %   \c@addpenalty\c@itempenalty
6262 %   \c@addvspace\c@itemsep
6263 \fi
6264 \c@global\c@inlabeltrue
6265 \fi
6266 %   \c@everypar{%
6267   \c@minipagefalse
6268   \c@global\c@newlistfalse
6269 %   \c@if@c@inlabel
6270 %   \c@global\c@inlabelfalse
```

```
6271 %      {\setbox\z@\lastbox
6272 %      \ifvoid\z@
6273 %          \kern-\itemindent
6274 %      \fi}%
6275 %      \box@labels
6276 %      \penalty\z@
6277 %      \fi
6278 %      \if@nobreak
6279 %          \nobreakfalse
6280 %          \clubpenalty \zM
6281 %      \else
6282 %          \clubpenalty \Zclubpenalty
6283 %          \everypar{}%
6284 %      \fi}%
6285 \if@noitemarg
6286     \noitemargfalse
6287     \if@nmbrlist
6288         \refstepcounter\listctr
6289     \fi
6290     \fi
6291     \makelabel{\#1} % extra space
6292 %     \sbox\@tempboxa{\makelabel{\#1}%
6293 %     \global\setbox\@labels\hbox{%
6294 %         \unhbox\@labels
6295 %         \hskip \itemindent
6296 %         \hskip -\labelwidth
6297 %         \hskip -\labelsep
6298 %         \ifdim \wd\@tempboxa >\labelwidth
6299 %             \box\@tempboxa
6300 %         \else
6301 %             \hbox to\labelwidth {\unhbox\@tempboxa}%
6302 %         \fi
6303 %         \hskip \labelsep}%
6304     \ignorespaces%
6305 }
\@nbitem
6306 \def\@nbitem{%
6307 %     \tempskipa\@outerparskip
6308 %     \advance\tempskipa -\parskip
```

```
6309 \%     \addvspace\@tempskipa
6310 }
```

\LWR@listitem [⟨label⟩]

Handles `\item` inside a list, `itemize`, or `enumerate`.

See `\LWR@openparagraph` where extra `\hskip` is used to leave room for the label while inside a list during paragraph construction.

```
6311 \newcommand*\{\LWR@listitem\}%
6312 \LWR@stoppars%
6313 \LWR@startnewdepth{\LWR@depthlistitem}{\LWR@printcloselistitem}%
6314 \LWR@htmlltag{li}%
6315 \LWR@startpars%
6316 \LWR@origitem%
6317 }
```

\LWR@nulllistfills Nullifies various TeX fill commands, in case they are used inside `\makelabel`. Problems are caused when these are nullified all the time.

```
6318 \newcommand*\{\LWR@nulllistfills\}%
6319 \renewcommand*\{\hss\}{}%
6320 \renewcommand*\{\llap\}[1]{##1}%
6321 \renewcommand*\{\rlap\}[1]{##1}%
6322 \renewcommand*\{\hfil\}{}%
6323 \renewcommand*\{\hfilneg\}{}%
6324 \renewcommand*\{\hfill\}{}%
6325 }
```

Env list {⟨label⟩} {⟨commands⟩}

```
6326 \newcommand*\{\LWR@liststart\}%
6327 \LWR@traceinfo{\LWR@liststart}%
6328 \LWR@stoppars%
6329 \LWR@pushoneclose{\LWR@depthlist}{\LWR@printcloselist}%
6330 \LWR@htmlltag{\LWR@printopenlist}\LWR@orignewline%
6331 \LWR@startpars%
6332 \setlength{\topsep}{0pt}%
6333 \setlength{\partopsep}{0pt}%
6334 \setlength{\itemsep}{0pt}%
6335 \setlength{\parsep}{0pt}%
6336 \setlength{\leftmargin}{0pt}%
6337 \setlength{\rightmargin}{0pt}%
6338 \setlength{\listparindent}{0pt}%
6339 \setlength{\itemindent}{0pt}%
6340 \setlength{\labelsep}{1em}%
```

```

6341 \LWR@nulllistfills%
6342 }

6343 \newcommand*{\LWR@listend}{%
6344 \LWR@traceinfo{\LWR@listend}%
6345 \LWR@stoppars%
6346 \LWR@closeprevious{\LWR@depthlist}%
6347 \LWR@startpars%
6348 }

```

68.2 Itemize

\LWR@itemizeitem [*label*]

Handles \item inside an itemize or enumerate.

See \LWR@openparagraph where extra \hspace is used to leave room for the label while inside a list during paragraph construction.

```

6349 \newcommand*{\LWR@itemizeitem}{%
6350 \LWR@stoppars%
6351 \LWR@startnewdepth{\LWR@depthlistitem}{\LWR@printcloselistitem}%
6352 \LWR@htmllisttag{li}%
6353 \LWR@startpars%
6354 \LWR@origitem%
6355 }

```

Env itemize [*options*]

```

6356 \newcommand*{\LWR@itemizestart}{%
6357 \renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}%
6358 \renewcommand*{\LWR@printopenlist}{ul style="\LWR@print@mbox{list-style-type:none}"}
6359 \let\item\LWR@itemizeitem%
6360 \LWR@nulllistfills%
6361 }

```

68.3 Enumerate

An HTML unordered list is used with customized L^AT_EX-generated labels.

Env enumerate [*options*]

```

6362 \newcommand*{\LWR@enumeratestart}{%
6363 \renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
6364 \renewcommand*{\LWR@printopenlist}{ul style="\LWR@print@mbox{list-style-type:none}"}
6365 \let\item\LWR@itemizeitem%
6366 \LWR@nulllistfills%
6367 }

```

68.4 Description

\LWR@descitem [*label*] Handles an \item inside a description.

```

6368 \newcommand*{\LWR@descitem}[1] []%
6369 {%
6370 \LWR@stoppars%
6371 \LWR@setlatestname{#1}%
6372 \LWR@startnewdepth{\LWR@depthlistitem}{\LWR@printclosedescitem}%

```

Temporarily disable \hspace, which article.cls, etc. use per \item for descriptions only. This causes lwarf to mistakenly place an empty span between HTML list tags.

```
6373 \LWR@select@html@nohspace%
```

Process the original \item code:

```
6374 \LWR@origitem[]%
```

Restore \hspace for use in the item text:

```
6375 \LWR@select@html@hspace%
```

```

6376 \LWR@htmlltag{dt}#1\LWR@htmlltag{/dt}%
6377 \LWR@orignewline%
6378 \LWR@htmlltag{dd}%
6379 \LWR@startpars%
6380 }

```

Env description [*options*]

```

6381 \newcommand*{\LWR@descriptionstart}{%
6382 \renewcommand*{\LWR@printcloselist}{\LWR@printclosedescription}
6383 \renewcommand*{\LWR@printopenlist}{dl}
6384 \let\item\LWR@descitem%
6385 \LWR@nulllistfills%
6386 }

```

68.5 Patching the lists

\LWR@patchlists Patches list environments.

\LWR@patchlists remembers \item as defined by whatever packages have been loaded, then patches the itemize, enumerate, and description environments and \item. This works with the native L^AT_EX environments, as well as those provided by enumitem, enumerate, and paralist.

```

6387 \newcommand*{\LWR@patchlists}{%
6388   \LetLtxMacro{\item}{\LWR@listitem}%
6389   \LetLtxMacro{\@item}{\LWR@HTML@item}%
6390   \renewcommand*{\@trivlist}{%
6391     \LWR@traceinfo{@trivlist start}%
6392     \LWR@liststart%
6393     \LWR@orig@trivlist%
6394     \LWR@traceinfo{@trivlist done}%
6395   }%
6396   \renewcommand*{\trivlist}{%
6397     \LWR@traceinfo{trivlist}%
6398     \LWR@origtrivlist%
6399   }%
6400   \renewcommand*{\endtrivlist}{%
6401     \LWR@traceinfo{endtrivlist start}%
6402     \LWR@origendtrivlist\LWR@listend%
6403     \LWR@traceinfo{endtrivlist done}%
6404   }%
6405   \renewcommand*{\itemize}{%
6406     \LWR@itemizestart\LWR@origitemize}%
6407   }%
6408   \renewcommand*{\enumerate}{%
6409     \LWR@enumeratestart\LWR@origenumerate}%
6410   }%
6411   \renewcommand*{\description}{%
6412     \LWR@descriptionstart\LWR@origdescription}%
6413 }%
6414 }
```

\LWR@restoreoriglists Restores the original trivlist environment.

```

6415 \newcommand*{\LWR@restoreoriglists}{%
6416 \LWR@traceinfo{\LWR@restoreoriglists}%
6417 \LetLtxMacro{\item}{\LWR@origitem}%
6418 \LetLtxMacro{\@item}{\LWR@orig@item}%
6419 \let{@trivlist}{\LWR@orig@trivlist}%
6420 \let{trivlist}{\LWR@origtrivlist}%
6421 \let{endtrivlist}{\LWR@origendtrivlist}%
6422 \LetLtxMacro{\itemize}{\LWR@origitemize}
```

```

6423 \LetLtxMacro\enditemize\LWR@endorigitemize%
6424 \LetLtxMacro\enumerate\LWR@origenumerate%
6425 \LetLtxMacro\endenumerate\LWR@endorigenumerate%
6426 \LetLtxMacro\description\LWR@origdescription%
6427 \LetLtxMacro\enddescription\LWR@endorigdescription%
6428 \let\@mklab\LWR@orig@mklab%
6429 \let\makelabel\LWR@origmakelabel%
6430 \let\@donoparitem\LWR@orig@donoparitem%
6431 \let\@nbitem\LWR@orig@nbitem%
6432 }

6433 \end{warpHTML}

```

69 Tabular

This is arguably the most complicated part of the entire package. Numerous tricks are employed to handle the syntax of the \LaTeX core and the various tabular-related packages.

69.1 Limitations

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, * column specifiers, **siunitx** S columns, or the packages **multirow**, **longtable**, **supertabular**, or **xtab**.

Defining environments:

⚠ Misplaced alignment tab character &

- When defining environments or macros which include tabular and instances of the & character, it may be necessary to make & active before the environment or macro is defined, then restore & to its default catcode after, using the following commands. These are ignored in print mode.

```

\StartDefiningTabulars
<define macros or environments using tabular and &
here>
\StopDefiningTabulars

```

⚠ floatrow

This includes before and after defining any macro which used `\ttabbox` from **floatrow**.

⚠ tabular inside another environment

- When creating a new environment which contains a tabular environment, lwarf's emulation of the tabular does not automatically resume

when the containing environment ends, resulting in corrupted HTML rows. To fix this, use \ResumeTabular as follows. This is ignored in print mode.

```
\StartDefiningTabulars % because & is used in a
definition
\newenvironment{outerenvironment}
{
\begin{tabular}{cc}
left & right \\
\end{tabular}
}
{
\TabularMacro\ResumeTabular
left & right \\
\end{tabular}
}
\StopDefiningTabulars
```

Cell contents:

\multirow

- For **multirow**, insert \mrowcell into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output.

```
... & \multirow{2}{.5in}{text} & ...
... & \mrowcell & ...
```

vposn

Note that recent versions of **multirow** include a new optional vposn argument.

- The **multirow** documentation regarding colored cells recommends using a negative number of rows. This will not work with **l warp**, so \warpprintonly and \warpHTMLonly must be used to make versions for print and HTML.
- See section 292.2 for \multicolumnrow.

l warp does not support directly combining \multicolumn and \multirow. Use \multicolumnrow instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}{0}{1in}[Opt]{Text}
```

The two arguments for \multicolumn come first, followed by the five arguments for \multirow, many of which are optional, followed by the contents.

skipped cells

As per \multirow, skipped cells to the right of the \multicolumnrow statement are not included in the source code on the same line. On the following lines, \mcolrowcell must be used for each cell of each column and each row to be skipped:

```
... & \multicolumnrow{2}{c}[c]{3}{0}{1in}[Opt]{Text} & ...
... & \mcolrowcell & \mcolrowcell & ...
... & \mcolrowcell & \mcolrowcell & ...
```

empty cells

vposn

Note that recent versions of **multirow** include a new optional vposn argument.

⚠ macro in a table

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use \TabularMacro just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \\
```

Column specifiers:**⚠ * column specification**

- * in a column specification is not used (so far). Repeat the column type the correct number of times.

@ and !

- Only one each of @ and ! is used at each column, and they are used in that order.

\multirow

- In \multirow cells, the print version may have extra instances of <, >, @, and ! cells on the second and later rows in the \multirow which do not appear in the HTML version.

⚠ \newcolumntype

- \newcolumntype is ignored; unknown column types are set to l.

Rules:**vertical rules**

- Doubled \hlines, \midrules, and vertical rules are supported.
- Vertical rules next to either side of an @ or ! column are displayed on both sides of the column.

width and trim

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with @ or ! columns, and full-width rules ignore trim.

full-width rules

- \toprule, \midrule, \bottomrule, and \hline ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

combined rules

- If you wish to use \cmidrule followed by \bottomrule, it may be necessary to use:

```
\cmidrule{2-3} \\[-2ex]
\bottomrule
```

The optional -2ex is ignored in HTML, but improves the visual formatting in the print output.

- For \toprule and \bottomrule, when combined with a warpprint or warpHTML environment, if a “Misplaced \noalign” error occurs, change

```
This & That \endhead
```

to

```
\warpprintonly{This & That \endhead}
```

and likewise with the other \end headings. Keep the \endfirsthead row unchanged, as it is still relevant to HTML output.

⚠ \warpprintonly**⚠ Misplaced \noalign**

colortbl:

-  **row/cell color** Only use `\rowcolor` and `\cellcolor` at the start of a row, in that order.
colortbl ignores the overhang arguments.

Other:

- **tabularx** ignores the width, but X columns do produce paragraph columns or multicolumns.

longtable headings

- For **longtable**, place headings and footings which do not apply to HTML inside `\warpprintonly{}`.

 **S columns**

- For S columns (from the **siunitx** package), while producing print output, anything non-numeric must be placed inside {} braces, including commands such as `\multirow`. While producing HTML output, though, anything placed inside braces is not seen by **l warp**'s tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

```
\warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
\warpHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
```

for HTML output: 6434 `\begin{warpHTML}`

69.2 Temporary package-related macros

These macros are temporary placeholders for macros defined by various packages. If the relevant package is not loaded, these placeholders are used instead.

69.2.1 arydshln

Emulated by the original L^AT_EX non-dashed versions.

```
6435 \LetLtxMacro{\hdashline}{\hline}
6436 \LetLtxMacro{\cdashline}{\cline}
6437 \LetLtxMacro{\firstdashline}{\hline}
6438 \LetLtxMacro{\lastdashline}{\hline}
```

69.3 Token lookahead

Used by `\LWR@futureonospacelet` to look at the next token.

```
\LWR@mynexttoken
```

```
6439 \newcommand{\LWR@mynexttoken}{\relax}
```

\futurelet copies the next token then executes a function to analyze

\LWR@futurenonospacelet does the same, but ignores intervening white space

Based on the **booktabs** style:

```
\LWR@futurenonospacelet
```

```
6440 \def{\LWR@futurenonospacelet}{\def{\LWR@cs{#1}}{%
6441 \afterassignment{\LWR@fnslone}\let\nexttoken= }%
6442 \def{\LWR@fnslone}{\expandafter{\futurelet{\LWR@cs{\LWR@fnsltwo}}{%
6443 \def{\LWR@fnsltwo}{%
6444 \expandafter{\ifx{\LWR@cs{\@sptoken}\let\next=\LWR@fnslthree}{%
6445 \else\let\next=\nexttoken\fi\next}%
6446 \def{\LWR@fnslthree}{\afterassignment{\LWR@fnslone}\let\next= }}}
```

\LWR@getmynexttoken Looks ahead and copies the next token into \LWR@mynexttoken.

```
6447 \newcommand*{\LWR@getmynexttoken}{%
6448 \LWR@traceinfo{\LWR@getmynexttoken}%
6449 % nothing must follow this next line
6450 \LWR@futurenonospacelet{\LWR@mynexttoken\LWR@tabledatacolumntag}%
6451 }
```

69.4 Tabular variables

Bool LWR@startedrow True if should print a row tag before this column.

```
6452 \newbool{\LWR@startedrow}
6453 \boolfalse{\LWR@startedrow}
```

Bool LWR@tabularcelladded True if have added a data cell for this position.

```
6454 \newbool{\LWR@tabularcelladded}
6455 \boolfalse{\LWR@tabularcelladded}
```

Ctr LWR@hlines Number of \hlines or \midrules above the next row.

```
6456 \newcounter{\LWR@hlines}
```

Ctr LWR@hdashedlines Number of **arydshln** dashed lines above the next row.

```
6457 \newcounter{LWR@hdashedlines}
```

Bool LWR@doingtbrule True if the next row will have a top/bottom rule above it.

```
6458 \newbool{LWR@doingtbrule}  
6459 \boolfalse{LWR@doingtbrule}
```

Bool LWR@doingcmidrule True if the next row will have a cmidrule above it.

This is used by \LWR@tabularfinishrow to force a final empty row to create the border for the \cmidrule.

```
6460 \newbool{LWR@doingcmidrule}  
6461 \boolfalse{LWR@doingcmidrule}
```

Bool LWR@tableparcell True if are handling a paragraph inside a table cell, so must close the paragraph tag before moving on.

```
6462 \newbool{LWR@tableparcell}
```

Bool LWR@skippingmrowcell True if are doing an empty \multirow cell, and thus there is no data tag to close.

```
6463 \newbool{LWR@skippingmrowcell}
```

Bool LWR@skippingmcolrowcell True if are doing an empty \multicolumn cell, and thus there is no data tag to close, and do not print @ and ! columns.

```
6464 \newbool{LWR@skippingmcolrowcell}
```

Bool LWR@skipatbang True if just finished a \multicolumn so should not create the trailing @ or ! columns table data cells.

```
6465 \newbool{LWR@skipatbang}
```

Bool LWR@emptyatbang True if finishing a row and should print empty @ or ! column table data cells.

```
6466 \newbool{LWR@emptyatbang}
```

Bool LWR@intabularmetadata True if are in a tabular but not in a data cell. Used to prevent extra HTML breaks if not inside table data.

```
6467 \newbool{LWR@intabularmetadata}  
6468 \boolfalse{LWR@intabularmetadata}
```

Ctr LWR@tabularDepth Tracks whether & is being used inside a tabular.

```
6469 \newcounter{LWR@tabulardepth}
6470 \setcounter{LWR@tabulardepth}{0}
```

Ctr LWR@tabularpardepth Tracks whether should look ahead at the next token when encountering a \par while processing tabular contents.

When LWR@tabularpardepth is deeper than LWR@tabulardepth then **l warp** has started looking at the contents of the tabular, and thus any \pars encountered must be followed by another token lookahead.

```
6471 \newcounter{LWR@tabularpardepth}
6472 \setcounter{LWR@tabularpardepth}{0}
```

```
6473 \newcommand*{\LWR@colsresult}{}%temp storage for column format results
6474 \newcommand*{\LWR@pposition}{}%
6475 \newcommand*{\LWR@pleft}{}%
6476 \newcommand*{\LWR@pright}{}%
```

LWR@tablecolspec Holds the parsed column specification, of total width LWR@tabletotalLaTeXcols, not counting @ and ! columns.

Will contain a string such as llrrccpc, exactly one letter per \LaTeX table column, without @, !, >, <, or the vertical bar.

\LWR@strresult Holds the result of Str functions.

```
6477 \providecommand*{\LWR@strresult}{}%
6478 \providecommand*{\LWR@strresulttwo}{}%
```

\LWR@origcolspec Holds the original column specs given to tabular.

```
6479 \newcommand*{\LWR@origcolspec}{}%
```

Ctr LWR@tablecolspecwidth Holds the number of tokens in the table columns specification.

This includes one for each @, !, <, > column, and also one for each of the parameters of p, @, !, <, > columns, and three for each D column.

(This is not the total # of \LaTeX columns in the table.)

```
6480 \newcounter{LWR@tablecolspecwidth}
```

Ctr LWR@tablecolspecindex While parsing the \LaTeX table column specification, starts at 1 and is incremented per token of the specification.

```
6481 \newcounter{LWR@tablecolspecindex}
```

Ctr `LWR@tableLaTeXcolindex` While producing the table, resets to 1 at the start of the table and also at each end of line, and is incremented by 1 by each ampersand.

```
6482 \newcounter{LWR@tableLaTeXcolindex}
```

Ctr `LWR@tabletotalLaTeXcols` While parsing a table column specification, begins at 0 and increments by 1 per \TeX table column. Eventually holds the final number of \TeX table columns in each row, not counting @ and ! columns. (In HTML, @ and ! cells become their own columns, but are not included in `LWR@tabletotalLaTeXcols`.)

```
6483 \newcounter{LWR@tabletotalLaTeXcols}
```

Ctr `LWR@tabletotalLaTeXcolsnext` Holds the next \TeX table column index while parsing, equal to one more than `LWR@tabletotalLaTeXcols`.

```
6484 \newcounter{LWR@tabletotalLaTeXcolsnext}
```

`LWR@colatspec` A data array of specifications for @ columns. The leftmost's index is `leftedge`, the others are counter values. See section 40.

`LWR@colbangspec` A data array of specifications for ! columns. The leftmost's index is `leftedge`, the others are counter values. See section 40.

`LWR@colbeforespec` A data array of specifications for > columns.

`LWR@colafterspec` A data array of specifications for < columns.

`LWR@colbarspec` A data array of specifications for vertical rules.

69.5 Handling &, @, !, and bar

For technical discussion regarding problems redefining \&, See:

<http://tex.stackexchange.com/questions/11638/where-do-i-find-futurelets-nasty-behaviour-documented/11860#11860>

```
\LWR@instertatbangcols
```

```
6485 \newcommand*{\LWR@instertatbangcols}{%
6486 \ifbool{LWR@skipatbang}{%
6487 {}{%
6488 {}{%
6489   \LWR@printatbang{at}{\arabic{LWR@tableLaTeXcolindex}}{%
6490   \LWR@printatbang{bang}{\arabic{LWR@tableLaTeXcolindex}}{%
6491 }{%
6492 }}
```

\LWR@closetabledatcell If LWR@skippingmrowcell or LWR@skippingmcolrowcell then there is no data tag to close. Otherwise, close any paragraphs, then close the data tag.

```
6493 \newcommand*{\LWR@closetabledatcell}{%
6494 \LWR@stoppars%
6495 \global\booltrue{\LWR@intabularmetadata}%
6496 \ifbool{\LWR@existingtabular}{ }{%
6497 { not exiting tabular
6498   \ifboolexpr{bool{\LWR@skippingmrowcell} or bool{\LWR@skippingmcolrowcell}}{ }{%
6499 }}
```

If not skipping a \multicolumnrow cell, insert the @ and ! columns after this non-existent column.

```
6500   \ifbool{\LWR@skippingmcolrowcell}{ }{%
6501     {}{%
6502       {\LWR@insertatbangcols}{%
6503     }{%
6504   }{ not skippingmrowcell }}
```

Insert any < then any @ and ! column contents, unless muted for the \bottomrule or a \multicolumn:

```
6505   \unskip%
6506   \ifboolexpr{%
6507     bool{\LWR@tabularmutemods} or
6508     bool{\LWR@skipatbang} or
6509     bool{\LWR@emptyatbang}
6510   }{%
6511   }{%
6512   {\LWR@getexparray{\LWR@col afterspec}{\arabic{\LWR@tableLaTeXcolindex}}}{}}
```

Close paragraphs:

```
6513   \ifbool{\LWR@tableparcell}{\LWR@stoppars}{ }{%
6514   \global\boolfalse{\LWR@tableparcell}}
```

Close the table data cell.

Close any color <div>s.

```
6515   \whileboolexpr{test {\ifnumcomp{\value{\LWR@cellcolordepth}}{>}{0}}}{%
6516     \LWR@htmltag{/div}\LWR@orignewline%
6517     \addtocounter{\LWR@cellcolordepth}{-1}%
6518 }
```

Skip the @ and ! cells if are closing a multicolumn cell.

```

6519      \leavevmode\unskip\LWR@htmntag{/td}\LWR@orignewline%
6520      \global\booltrue{\LWR@tabularcelladded}%
6521      \LWR@insertatbangcols%
6522      }% not skipping mrowcell
6523 }% not exiting tabular
6524 \global\boolese{\LWR@skippingmrowcell}%
6525 \global\boolese{\LWR@skippingmcolrowcell}%
6526 \global\boolese{\LWR@skipatbang}%

```

Color control. Column is set by >{} for each cell, so it must be cleared here.

```

6527 \gdef{\LWR@cellHTMLcolor{}}
6528 \gdef{\LWR@columnHTMLcolor{}}
6529 \setcounter{\LWR@cellcolordepth}{0}
6530 }

```

When not used inside a `tabular`, & performs its original function as recorded here (with catcode 4).

```

6531 \let{\LWR@origampmacro&}
6532 \end{warpHTML}

```

69.5.1 Handling &

for HTML output: 6533 `\begin{warpHTML}`

- & Will behave depending on whether it is being used inside `tabular`.
- & is redefined to test whether it is inside a `tabular` environment, in which case it performs special processing for HTML conversion. If not, it behaves normally.

```

6534 \newcommand*{\LWR@tabularampersand}{%
6535 \LWR@traceinfo{\LWR@tabularampersand}%
6536 \ifnumcomp{\value{\LWR@tabulardepth}}{>}{0}%
6537 }%

```

If not skipping a multirow cell, close the current data cell.

```

6538      \unskip%
6539      \LWR@closetabledatacell%

```

Move to the next column.

```

6540      \addtocounter{\LWR@tableLaTeXcolindex}{1}%

```

Have not yet added data in this column:

```
6541 \global\boolfalse{LWR@tabularcelladded}%
```

Look at the next token to decide multi or single column data tag.

```
6542 \LWR@getmynexttoken%
6543 }%
```

If not inside a tabular, performs the original action:

```
6544 {\LWR@origampmacro}%
6545 }
```

& is left with its original catcode for now.

tikz package seems to require & be left alone until after **tikz** has been loaded. Also, **cleveref** uses the ampersand in one of its options.

& is made active inside a tabular.

& is left alone when in math alignments.

69.5.2 Filling an unfinished row

\LWR@tabularfinishrow Adds empty table cells if necessary to finish the row.

At the end of the table, if any bottom rules are requested then an empty row must be generated to form the borders which show the rules.

```
6546 \newcommand*\LWR@tabularfinishrow{%
```

If not exiting the tabular, or doing a rule, or have already started a row, finish this row:

```
6547 \ifboolexpr{%
6548   not \bool{LWR@exittingtabular} or%
6549   \bool{LWR@doingtbrule} or%
6550   \bool{LWR@doingcmidrule} or%
6551   \test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
6552   \test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}} or%
6553   \bool{LWR@startedrow}%
6554 }{%
```

To temporarily turn off LWR@exittingtabular so that table data tags will still be generated:

If generating a final row for the \bottomrule borders, turn off the @, !, <, and > column output:

```
6555 \ifbool{LWR@existingtabular}{%
6556     \global\booltrue{LWR@tabularmutemods}%
6557 }{%
6558     \global\boolfalse{LWR@tabularmutemods}%
6559 }
```

Locally reenable the table data tags until finished with the final row:

```
6560 \global\boolfalse{LWR@existingtabular}%
```

Generate table data tags and ampersands until the right edge:

```
6561 \whileboolexpr{%
6562     test {
6563         \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}
6564     } or %
6565     (%
6566         bool{LWR@intabularmetadata} and%
6567         not bool{LWR@tabularcelladded} and%
6568         test {
6569             \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{\value{LWR@tabletotalLaTeXcols}}
6570         }%
6571     )%
6572 }%
6573 {%
6574     \LWR@tabledatasinglecolumntag%
```

The following is essentially \LWR@tabularampersand with LWR@emptyatbang added to empty the following cells:

```
6575     \LWR@closetabledatacell%
6576     \addtocounter{LWR@tableLaTeXcolindex}{1}%
6577     \global\boolfalse{LWR@tabularcelladded}%
6578     \global\booltrue{LWR@emptyatbang}%

```

Starts the next cell:

```
6579     \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}{%
6580         {\LWR@getmynexttoken}%
6581         {}%
6582 }%
```

Reenable the original LWR@existingtabular to close the entire table:

```
6583 \ifbool{LWR@tabularmutemods}{%
```

```

6584     \global\booltrue{LWR@exittingtabular}%
6585 }{%
6586     \global\boolfalse{LWR@exittingtabular}%
6587 }%
6588 \global\boolfalse{LWR@tabularmutemods}%

6589 \global\boolfalse{LWR@emptyatbang}%
6590 }{}% ifboolexpr
6591 }

```

69.6 Handling \\

Inside tabular, \\ is redefined to \LWR@tabularendofline

Throws away options \\[dim] or *

\LWR@tabularendofline

```
6592 \NewDocumentCommand{\LWR@tabularendofline}{s o}{%
```

Finish the row:

```

6593 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}{%
6594     {\LWR@tabularfinishrow}%
6595     {\LWR@closetabledatacell}%
6596 \LWR@htmlltag{/tr}\LWR@orignewline%

```

xcolor row color support:

```
6597 \rowc@lors%
```

No longer inside a data cell:

```
6598 \global\booltrue{LWR@intabularmetadata}%
```

Not yet started a table row:

```
6599 \global\boolfalse{LWR@startedrow}%
```

Additional setup:

```

6600 \setcounter{LWR@hlines}{0}%
6601 \setcounter{LWR@hdashedlines}{0}%
6602 \global\boolfalse{LWR@doingtbrule}%
6603 \global\boolfalse{LWR@doingcmidrule}%

```

```
6604 \LWR@clearmidrules%
6605 \gdef\LWR@rowHTMLcolor{}%
```

Start at first column:

```
6606 \setcounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
6607 \global\boolfalse{LWR@tabularcelladded}%
```

Allow T_EX to flush the pending paragraph. Not doing so causes a slowdown for very large tables.

```
6608 \LWR@stopars
6609 \LWR@origpar
```

Look at the next token to decide between single column data tag or a special case:

```
6610 \LWR@getmynexttoken%
6611 }
```

69.7 Looking ahead in the column specifications

```
\LWR@columnspeclookahead {⟨offset⟩}
```

Looks offset tokens ahead in the column specification, setting \LWR@strresulttwo.

The w column alignment will be seen as a single unit such as {c}.

```
6612 \newcommand*{\LWR@columnspeclookahead}[1]{%
6613 \setcounter{LWR@tempcountone}{\value{LWR@tablecolspeccolindex}}%
6614 \addtocounter{LWR@tempcountone}{#1}%
6615 \fullexpandarg%
6616 \StrChar{\LWR@origcolspeccolindex}{\arabic{LWR@tempcountone}}[\LWR@strresulttwo]%
```

Get the contents of the first group in \LWR@strresulttwo:

```
6617 \exploregroups%
6618 \StrChar{\LWR@strresulttwo}{1}[\LWR@strresulttwo]%
6619 \noexploregroups%
6620 }
```

69.8 Parsing @, >, <, !, bar columns

Holds the parsed argument for @, >, <, or ! columns:

```
6621 \newcommand*\{LWR@colparameter}\{}%
```

\LWR@parseatcolumn Handles @{text} columns.

```
6622 \newcommand*\{LWR@parseatcolumn}\{}%
```

Move to the next token after the '@':

```
6623 \LWR@traceinfo\{at column\}%
6624 \addtocounter\{LWR@tablecolsindex\}{1}%
```

Read the next token into \LWR@colparameter, expanding once:

```
6625 \LWR@traceinfo\{about to read the next token\}%
6626 \expandarg%
6627 \StrChar\{LWR@origcolspecl\}%
6628   \arabic\{LWR@tablecolsindex\}\[\LWR@colparameter]
6629 \fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
6630 \LWR@traceinfo\{have now read the next token\}%
6631 \ifnumcomp\{\value\{LWR@tabletotalLaTeXcols\}\}{=}\{0\}%
6632 \{}% left edge of the table:
6633   \LWR@traceinfo\{at the left edge\}%
6634   \LWR@setexpparray\{LWR@colatspec\}\{leftedge\}\[\LWR@colparameter]%
6635   \LWR@traceinfo\{at the left edge: %
6636   \LWR@getexpparray\{LWR@colatspec\}\{leftedge\}\}%
6637 \}%
6638 \{}% not at the left edge:
6639   \LWR@traceinfo\{not at the left edge\}%
6640   \LWR@setexpparray\{LWR@colatspec\}%
6641     \arabic\{LWR@tabletotalLaTeXcols\}\[\LWR@colparameter]%
6642   \LWR@traceinfo\{at \arabic\{LWR@tabletotalLaTeXcols\}: %
6643   \LWR@getexpparray\{LWR@colatspec\}\{arabic\{LWR@tabletotalLaTeXcols\}\}\}%
6644 \}%
6645 \let\LWR@colparameter\relax%
6646 \global\booltrue\{LWR@validtablecol\}%
6647 }
```

\LWR@parsebangcolumn Handles !{text} columns.

```
6648 \newcommand*\{LWR@parsebangcolumn}\{}%
```

Move to the next token after the '!':

```
6649 \LWR@traceinfo{bang column}%
6650 \addtocounter{LWR@tablecolsindex}{1}%
```

Read the next token into \LWR@colparameter, expanding once:

```
6651 \LWR@traceinfo{about to read the next token:}%
6652 \expandarg%
6653 \StrChar{\LWR@origcolspec}%
6654 {\arabic{LWR@tablecolsindex}}[\LWR@colparameter]
6655 \fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
6656 \LWR@traceinfo{have now read the next token}%
6657 \ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
6658 {%
  left edge of the table:
  \LWR@traceinfo{at the left edge}%
  \LWR@setexpparray{LWR@colbangspec}{leftedge}{\LWR@colparameter}%
}%
6662 {%
  not at the left edge:
  \LWR@traceinfo{not at the left edge}%
  \LWR@setexpparray{LWR@colbangspec}%
  {\arabic{LWR@tabletotalLaTeXcols}}{\LWR@colparameter}%
  \LWR@traceinfo{bang \arabic{LWR@tabletotalLaTeXcols}: \LWR@colparameter!}%
}%
6668 \let\LWR@colparameter\relax%
6669 \global\booltrue{LWR@validtablecol}%
670 }
```

\LWR@parsebeforecolumn Handles >{text} columns.

```
6671 \newcommand*{\LWR@parsebeforecolumn}{%
```

Move to the next token after the '>':

```
6672 \addtocounter{LWR@tablecolsindex}{1}%
```

Read the next token, expanding once into \LWR@colparameter:

```
6673 \expandarg%
6674 \StrChar{\LWR@origcolspec}%
6675 {\arabic{LWR@tablecolsindex}}[\LWR@colparameter]%
6676 \fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```

6677 \LWR@setexpparray{\LWR@colbeforespec}%
6678   {\arabic{\LWR@tabletotalLaTeXcolsnext}}{\LWR@colparameter}%
6679 \let\LWR@colparameter\relax%
6680 \global\booltrue{\LWR@validtablecol}%
6681 }

```

\LWR@parseaftercolumn Handles <{text} columns.

```
6682 \newcommand*{\LWR@parseaftercolumn}{%
```

Move to the next token after the '<':

```
6683 \addtocounter{\LWR@tablecolsindex}{1}%
```

Read the next token, expanding once into \LWR@colparameter:

```

6684 \expandarg%
6685 \StrChar{\LWR@origcolspec}%
6686   {\arabic{\LWR@tablecolsindex}}[\LWR@colparameter]%
6687 \fullexpandarg%

```

Store the result into a data array, expanding once out of \LWR@colparameter:

```

6688 \LWR@setexpparray{\LWR@colaferspec}%
6689   {\arabic{\LWR@tabletotalLaTeXcols}}{\LWR@colparameter}%
6690 \let\LWR@colparameter\relax%
6691 \global\booltrue{\LWR@validtablecol}%
6692 }

```

\LWR@parsebarcolumn Handles vertical rules.

```

6693 \newcommand*{\LWR@parsebarcolumn}{%
6694 \LWR@traceinfo{\LWR@parsebarcolumn}%

```

Remember the bar at this position:

```

6695 \ifnumcomp{\value{\LWR@tabletotalLaTeXcols}}{=}{0}%
6696 {%
6697   \edef\LWR@tempone{\LWR@getexpparray{\LWR@colbarspec}{leftedge}}%
6698   \ifdefstring{\LWR@tempone}{tvertbarl}%
6699   {\LWR@setexpparray{\LWR@colbarspec}{leftedge}{tvertbarldouble}}%
6700   {\LWR@setexpparray{\LWR@colbarspec}{leftedge}{tvertbarl}}%
6701 }%
6702 {%
6703   \edef\LWR@tempone{%
6704     \LWR@getexpparray{\LWR@colbarspec}{\arabic{\LWR@tabletotalLaTeXcols}}%

```

```

6705      }%
6706      \ifdefstring{\LWR@tempone}{tvertbarr}%
6707      {%
6708          \LWR@setexpparray{\LWR@colbarspec}%
6709          {\arabic{\LWR@tabletotalLaTeXcols}}{tvertbarrdouble}%
6710      }%
6711      {%
6712          \LWR@setexpparray{\LWR@colbarspec}%
6713          {\arabic{\LWR@tabletotalLaTeXcols}}{tvertbarr}%
6714      }%
6715  }%
6716 \global\booltrue{\LWR@validtablecol}%
6717 }

```

\LWR@parsecoloncolumn Handles vertical rules.

```

6718 \newcommand*{\LWR@parsecoloncolumn}{%
6719 \LWR@traceinfo{\LWR@parsecoloncolumn}%

```

Remember the bar at this position:

```

6720 \ifnumcomp{\value{\LWR@tabletotalLaTeXcols}}{=}{0}%
6721 {%
6722     left edge of the table:
6723     \edef\LWR@tempone{\LWR@getexpparray{\LWR@colbarspec}{leftedge}}%
6724     \ifdefstring{\LWR@tempone}{tvertbarldash}%
6725     {\LWR@setexpparray{\LWR@colbarspec}{leftedge}{tvertbarldoubledash}}%
6726     {\LWR@setexpparray{\LWR@colbarspec}{leftedge}{tvertbarldash}}%
6727 }%
6728 {%
6729     not at the left edge:
6730     \edef\LWR@tempone{%
6731         \LWR@getexpparray{\LWR@colbarspec}{\arabic{\LWR@tabletotalLaTeXcols}}%
6732     }%
6733     \ifdefstring{\LWR@tempone}{tvertbarrdash}%
6734     {\LWR@setexpparray{\LWR@colbarspec}{%
6735         {\arabic{\LWR@tabletotalLaTeXcols}}{tvertbarrdoubledash}}%
6736     }%
6737 \global\booltrue{\LWR@validtablecol}%
6738 }

```

\LWR@parsesemicoloncolumn Handles vertical rules.

```

6739 \newcommand*{\LWR@parsesemicoloncolumn}{%

```

Treat ; as a : column:

```

6740 \LWR@parsecoloncolumn%

```

Skip the following width token:

```
6741 \addtocounter{LWR@tablecolsindex}{1}%
6742 }
```

69.9 Parsing ‘l’, ‘c’, or ‘r’ columns

```
\LWR@parsenormalcolumn {\langle thiscolumn\rangle}
```

Add to the accumulated column specs, advance counters, and pre-clear another column of at, before, and after specs.

```
6743 \newcommand*\{\LWR@parsenormalcolumn}[1]{%
6744 \addtocounter{LWR@tabletotalLaTeXcols}{1}%
6745 \addtocounter{LWR@tabletotalLaTeXcolsnext}{1}%

6746 \LWR@setexpparray{\LWR@tablecolspec}{\arabic{LWR@tabletotalLaTeXcols}}{\#1}%

6747 \LWR@traceinfo{normal column \arabic{LWR@tabletotalLaTeXcols}: #1}%
6748 \LWR@setexpparray{\LWR@colatspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
6749 \LWR@setexpparray{\LWR@colbangspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
6750 \LWR@setexpparray{\LWR@colbeforespec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
6751 \LWR@setexpparray{\LWR@col afterspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
6752 \LWR@setexpparray{\LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
6753 \global\booltrue{LWR@validtablecol}%
6754 }
```

69.10 Parsing ‘p’, ‘m’, or ‘b’ columns

```
\LWR@parsepcolumn {\langle thiscolumn\rangle} The width will be ignored.
```

```
6755 \newcommand*\{\LWR@parsepcolumn}[1]{%
```

Converts to the given column type:

```
6756 \LWR@parsenormalcolumn{\#1}%
```

Skips the following width token:

```
6757 \addtocounter{LWR@tablecolsindex}{1}%
6758 }
```

69.11 Parsing ‘w’ columns

\LWR@parsewcolumn The width will be ignored.

```
6759 \newcommand*\{\LWR@parsewcolumn\}{%
6760 \LWR@columnspeclookahead{1}%
6761 \expandafter\LWR@parseenormalcolumn\expandafter{\LWR@strresulttwo}%
```

Skips the following width and alignment tokens:

```
6762 \addtocounter{LWR@tablecolspectindex}{2}%
6763 }
```

69.12 Parsing ‘D’ columns

From the **dcolumn** package.

\LWR@parseDcolumn {<thiscolumn>} The three parameters will be ignored.

```
6764 \newcommand*\{\LWR@parseDcolumn\}[1]{%
```

Converts to the given column type.

```
6765 \LWR@parseenormalcolumn{#1}%
```

Skips the following three parameters.

```
6766 \addtocounter{LWR@tablecolspectindex}{3}%
6767 }
```

69.13 Parsing the column specifications

- ⚠ **tabular baselines** HTML css cannot exactly match the \TeX concept of a baseline for a table row. Table 9 shows the \TeX results for various vertical-alignment choices, with the baseline of the first column drawn across all the columns for comparison. See the p column specification in table 10 for details.

Table 10 describes how each kind of column is converted to HTML.

Bool LWR@validtablecol True if found a valid table column type.

Table 9: Tabular baseline

l	p	m	b	r
			bot	
		mid	bot	
l	par	mid	bot	r
	par	mid		
	par			

Table 10: Tabular HTML column conversions

l, r, c: Converted to table cells without paragraph tags.

Uses css `vertical-align:middle` so that top or bottom-aligned cells may go above or below this cell.

p: Converted to table cells with paragraph tags. Ref: Table 9, \LaTeX places the top line of a parbox aligned with the rest of the text line, so css `vertical-align:bottom` is used to have the HTML result appear with the paragraph extending below the L, R, C cells at the middle, if possible. This may be confusing as a P cell may not top-align with an L,R,C cell in the HTML conversion, especially in the presence of a B cell, and two P cells side-by-side will be aligned at the bottom instead of the top. Some adjustment of the css may be desired, changing `td.tdp`, `td.tdP`, `td.tdprule`, and `td.tdPrule` to `vertical-align: middle`. Another possibility is to change L,R,C, and P to `vertical-align: top` and not worry about the alignment of B and M cells or trying to approximate \LaTeX baselines.

m: With paragraph tags, css `vertical-align:middle`.

b: With paragraph tags, css `vertical-align:top` so that the bottom of the text is closest to the middle of the text line.

P, M, B: Horizontally-centered versions.

S: Converted to 'r'. Ignores optional argument. From the **siunitx** package.

D: Converted to 'c'. From the **dcolumn** package.

@, !, >, <: One each, in that order.

|: Vertical rule.

Unknown: Converted to 'l'.

\newcolumn: Currently treated as unknown.

```
6768 \newbool{LWR@validtablecol}
```

Bool LWR@opttablecol True if found a table column optional argument.

```
6769 \newbool{LWR@opttablecol}
```

\LWR@parsetablecols {{*cols*}}

Scans the column specification left to right.

Builds \LWR@tablecols with the final specification, one \TeX column per entry. The final number of \TeX columns in each row is stored in LWR@tabletotalLaTeXcols, which is the number of & and \\ in each line, but which does not include @, !, <, > specifications in the count.

```
6770 \newcommand*\{\LWR@parsetablecols}{1}{%
6771 \LWR@traceinfo{\LWR@parsetablecols}}%
```

Remember the original supplied column spec:

```
6772 \renewcommand*\{\LWR@origcols}{#1}{%
```

Remove spaces:

```
6773 \expandarg%
6774 \StrSubstitute{\LWR@origcols}{ }{}[\LWR@origcols]{}
```

The parsed column spec data array, LWR@tablecols, will be overwritten with new values.

Total number of columns found so far. Also pre-initialize the first several columns of specs:

```
6775 \setcounter{LWR@tabletotalLaTeXcols}{0}{%
6776 \setcounter{LWR@tabletotalLaTeXcolsnext}{1}{%
6777 \LWR@setexpparray{\LWR@colat{spec}}{leftedge}{}{%
6778 \LWR@setexpparray{\LWR@colat{spec}}{1}{}{%
6779 \LWR@setexpparray{\LWR@colat{spec}}{2}{}{%
6780 \LWR@setexpparray{\LWR@colat{spec}}{3}{}{%
6781 \LWR@setexpparray{\LWR@colbang{spec}}{leftedge}{}{%
6782 \LWR@setexpparray{\LWR@colbang{spec}}{1}{}{%
6783 \LWR@setexpparray{\LWR@colbang{spec}}{2}{}{%
6784 \LWR@setexpparray{\LWR@colbang{spec}}{3}{}{%
6785 \LWR@setexpparray{\LWR@colbefore{spec}}{1}{}{%
6786 \LWR@setexpparray{\LWR@colbefore{spec}}{2}{}{%
6787 \LWR@setexpparray{\LWR@colbefore{spec}}{3}{}{%
6788 \LWR@setexpparray{\LWR@colafter{spec}}{1}{}{%
```

```

6789 \LWR@setexpparray{\LWR@colaferspec}{2}{}
6790 \LWR@setexpparray{\LWR@colaferspec}{3}{}
6791 \LWR@setexpparray{\LWR@colbarspec}{leftedge}{}
6792 \LWR@setexpparray{\LWR@colbarspec}{1}{}
6793 \LWR@setexpparray{\LWR@colbarspec}{2}{}
6794 \LWR@setexpparray{\LWR@colbarspec}{3}{}

```

Starting at the first column specification:

```
6795 \setcounter{\LWR@tablecolspecindex}{1}
```

Place the colspecs string length into `\LWR@strresult`, and remember the number of characters in the column specification:

```

6796 \expandarg%
6797 \StrLen{\LWR@origcolspec}[\LWR@strresult]%
6798 \fullexpandarg%
6799 \LWR@traceinfo{original column spec length: \LWR@strresult}%
6800 \setcounter{\LWR@tablecolspecwidth}{\LWR@strresult}%

```

Haven't seen any optional arguments so far

```
6801 \global\boolfalse{\LWR@opttablecol}
```

Scan through the column specifications:

```

6802 \whileboolexpr{%
6803     not test{%
6804         \ifnumcomp{\value{\LWR@tablecolspecindex}}{>}{%
6805             {\value{\LWR@tablecolspecwidth}}%
6806         }%
6807     }%
6808 }%

```

Place the next single-character column type into `\LWR@strresult`:

```

6809 \expandarg%
6810 \StrChar{\LWR@origcolspec}{\arabic{\LWR@tablecolspecindex}}[\LWR@strresult]%
6811 \LWR@traceinfo{position \arabic{\LWR@tablecolspecindex}: \LWR@strresult}%
6812 \fullexpandarg%

```

Not yet found a valid column type:

```
6813 \global\boolfalse{\LWR@validtablecol}
```

Skip over any optional arguments, such as **siunitx** S column:

```
6814 \IfStrEq{\LWR@strresult}{[]}{\global\booltrue{\LWR@opttablecol}}{}
```

Throw away anything found inside the optional argument:

```
6815 \ifbool{\LWR@opttablecol}{%
6816 {}% inside an optional argument
6817 {}% not an optional tabular argument}
```

Not inside an optional argument, so consider the column type:

```
6818 \IfStrEq{\LWR@strresult}{l}{\LWR@parsenormalcolumn{l}}{%
6819 \IfStrEq{\LWR@strresult}{c}{\LWR@parsenormalcolumn{c}}{%
6820 \IfStrEq{\LWR@strresult}{r}{\LWR@parsenormalcolumn{r}}{%
6821 \IfStrEq{\LWR@strresult}{L}{\LWR@parsenormalcolumn{l}}{%
6822 \IfStrEq{\LWR@strresult}{C}{\LWR@parsenormalcolumn{c}}{%
6823 \IfStrEq{\LWR@strresult}{R}{\LWR@parsenormalcolumn{r}}{%
6824 \IfStrEq{\LWR@strresult}{J}{\LWR@parsenormalcolumn{l}}{%

6825 \IfStrEq{\LWR@strresult}{S}{\LWR@parsenormalcolumn{c}}{%
6826 \IfStrEq{\LWR@strresult}{s}{\LWR@parsenormalcolumn{c}}{%

6827 \IfStrEq{\LWR@strresult}{\detokenize{c}}{\LWR@parseatcolumn}{%
6828 \IfStrEq{\LWR@strresult}{!}{\LWR@parsebangcolumn}{%
6829 \IfStrEq{\LWR@strresult}{>}{\LWR@parsebeforecolumn}{%
6830 \IfStrEq{\LWR@strresult}{<}{\LWR@parseaftercolumn}{%
6831 \IfStrEq{\LWR@strresult}{|}{\LWR@parsebarcolumn}{%
6832 \IfStrEq{\LWR@strresult}{:}{\LWR@parsecoloncolumn}{%
6833 \IfStrEq{\LWR@strresult}{;}{\LWR@parsesemicoloncolumn}{%

6834 \IfStrEq{\LWR@strresult}{p}{\LWR@parsepcolumn{p}}{%
6835 \IfStrEq{\LWR@strresult}{m}{\LWR@parsepcolumn{m}}{%
6836 \IfStrEq{\LWR@strresult}{b}{\LWR@parsepcolumn{b}}{%

6837 \IfStrEq{\LWR@strresult}{w}{\LWR@parsewcolumn}{%
6838 \IfStrEq{\LWR@strresult}{W}{\LWR@parsewcolumn}{}}
```

From the **dcolumn** package:

```
6839 \IfStrEq{\LWR@strresult}{D}{\LWR@parseDcolumn{c}}{%
```

From the **tabularx** package. X column has no parameter, but will be given paragraph tags.

```
6840 \IfStrEq{\LWR@strresult}{X}{\LWR@parsenormalcolumn{X}}{%
```

Many people define centered versions “P”, “M”, and “B”:

```
\newcolumntype{P}[1]{>{\centering\arraybackslash}p{#1}}
```

```
6841 \IfStrEq{\LWR@strresult}{P}{\LWR@parsepcolumn{P}}{}%
6842 \IfStrEq{\LWR@strresult}{M}{\LWR@parsepcolumn{M}}{}%
6843 \IfStrEq{\LWR@strresult}{B}{\LWR@parsepcolumn{B}}{}%
```

If this column was an invalid column type, convert it to an l column:

```
6844 \ifbool{\LWR@validtablecol}{}{%
6845     \LWR@traceinfo{invalid column type: \LWR@strresult}%
6846     \LWR@parseenormalcolumn{l}%
6847 }%
6848 }% not an optional column argument
```

If read the closing bracket, no longer inside the optional argument:

```
6849 \IfStrEq{\LWR@strresult}{}{\global\boolfalse{\LWR@opttablecol}}%
```

Move to the next character:

```
6850 \addtocounter{\LWR@tablecolsindex}{1}%
6851 }% whiledo
6852 }%
```

69.14 colortbl and xparse tabular color support

These macros provide a minimal emulation of some **colortbl** macros which might appear between table cells. If **colortbl** is loaded, these macros will be replaced with functional versions.

For each of the HTML colors below, the text for the HTML color is set if requested, but the macro is empty if none has been set.

`\rownum` Reserve a counter register.

```
6853 \@ifundefined{\rownum}{\newcount\rownum}{}
```

`\@rowcolors` Emulated in case **xcolor** is not used.

```
6854 \newcommand*{\@rowcolors}{}%
```

`\@rowc@lors` Emulated in case **xcolor** is not used.

```
6855 \newcommand*{\@rowc@lors}{}%
```

\LWR@xcolorrowHTMLcolor Emulated **xcolor** row color.

6856 \newcommand*{\LWR@xcolorrowHTMLcolor}{}{}

\LWR@columnHTMLcolor HTMLstyle code for the column color.

6857 \def\LWR@columnHTMLcolor{}{}

\LWR@rowHTMLcolor HTMLstyle code for the row color.

6858 \def\LWR@rowHTMLcolor{}{}

\LWR@cellHTMLcolor HTMLstyle code for the cell color.

6859 \def\LWR@cellHTMLcolor{}{}

\LWR@ruleHTMLcolor HTMLstyle code for the cell color.

6860 \newcommand*{\LWR@ruleHTMLcolor}{}{}

\rowcolor [⟨model⟩] {⟨color⟩} [⟨left overhang⟩] [⟨right overhang⟩] Print version. The HTML version is in **l warp-colortbl**. Used before starting a tabular data cell, thus \LWR@getmynexttoken.

6861 \newcommand*{\rowcolor}{\LWR@getmynexttoken} %

\arrayrulecolor [⟨model⟩] {⟨color⟩}

\arrayrulecolornexttoken [⟨model⟩] {⟨color⟩}

Print versions for use outside and inside a tabular:

6862 \newcommand{\arrayrulecolor}[2][named]{}{}

6863 \newcommand{\arrayrulecolornexttoken}[2][named]{\LWR@getmynexttoken}

\doublerulesepcolor [⟨model⟩] {⟨color⟩}

\doublerulesepcolornexttoken [⟨model⟩] {⟨color⟩}

Print versions for use inside and outside a tabular:

6864 \newcommand{\doublerulesepcolor}[2][named]{}{}

6865 \newcommand{\doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}

69.15 Starting a new row

\LWR@maybenewtablerow If have not yet started a new table row, begin one now. Creates a new row tag, adding a class for hline or tbrule if necessary.

```
6866 \newcommand*\LWR@maybenewtablerow{%
6867 {%
6868 \ifbool{\LWR@startedrow}{%
6869 {}% started the row
6870 {}% not started the row
```

Remember that now have started the row:

```
6871 \global\booltrue{\LWR@startedrow}%
```

Create the row tag, with a class if necessary.

```
6872 \global\booltrue{\LWR@intabularmetadata}%
6873 \ifboolexpr{%
6874   test{\ifnumcomp{\value{\LWR@hlines}}{>}{0}} or%
6875   test{\ifnumcomp{\value{\LWR@hdashedlines}}{>}{0}}%
6876 }%
6877 {%
6878   \LWR@htmlltag{tr class="hline"}%
6879   \LWR@orignewline%
6880 }%
6881 {%
6882   \ifbool{\LWR@doingtbrule}{%
6883     {%
6884       \ifdefvoid{\LWR@ruleHTMLcolor}{%
6885         \LWR@htmlltag{tr class="tbrule"}%
6886       }{%
6887         \LWR@htmlltag{%
6888           tr class="tbrule" % space
6889           style="border-top: 1px solid % space
6890             \LWR@origpound\LWR@ruleHTMLcolor "%
6891         }%
6892       }%
6893       \LWR@orignewline%
6894     }%
6895     {\LWR@htmlltag{tr}\LWR@orignewline}%
6896   }%
6897 }%
6898 }% end of not doing hline
6899 }% end of not started the row
6900 }
```

69.16 Printing vertical bar tags

```
\LWR@printbartag {<index>}
```

Adds to a tabular data cell an HTML class name for a left/right vertical bar.

```
6899 \newcommand*{\LWR@printbartag}[1]{%
6900 \LWR@traceinfo{\LWR@printbartag !#1!}%
6901 \ifboolexpr{bool{\LWR@tabularmutemods} or bool{\LWR@emptyatbang}}{%
6902 {}% muting or empty
6903 {}% not muting
6904 \edef\LWR@tempone{\LWR@getexpparray{\LWR@colbarspec}{#1}}%
6905 \ifdefempty{\LWR@tempone}{}{\LWR@tempone}%
6906 }% not muting
6907 \LWR@traceinfo{\LWR@printbartag done}%
6908 }
```

69.17 Printing at or bang tags

```
\LWR@printatbang {<at -or- bang>} {<index>}
```

```
6909 \newcommand*{\LWR@printatbang}[2]{%
```

Fetch the column at or bang spec:

```
6910 \xdef\LWR@atbangspec{\LWR@getexpparray{\LWR@col#1spec}{#2}}%
6911 \LWR@traceinfo{atbang: #2 !\LWR@atbangspec!}%
```

Only generate if is not empty;

```
6912 \ifdefempty{\LWR@atbangspec}{%
6913 {}% not empty
6914 {}% not empty
6915 \LWR@htmltag{%
6916     td class="td#1%"%
6917     \LWR@subaddcmidruletrim{}{}%
6918     \LWR@printbartag{#2}%
6919     "%"%
6920     \LWR@tdstartstyles%
6921     \LWR@addcmidrulewidth%
6922     \LWR@addcdashline%
6923     \LWR@addtabularrulecolors%
6924     \LWR@tdendstyles%
6925 }}
```

Create an empty cell if muting for the \bottomrule:

```

6926     \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}{%
6927         {}%
6928         {\LWR@atbangspec}%
6929 }%
6930     \LWR@htmltag{/td}\LWR@orignewline%
6931     \global\booltrue{LWR@tabularcelladded}%
6932 }% not empty
6933 }%

```

\LWR@addleftmostbartag

```

6934 \newcommand*{\LWR@addleftmostbartag}{%
6935 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{1}{%
6936     \LWR@printbartag{leftedge}%
6937 }{}%
6938 }

```

\LWR@tabularleftedge

```

6939 \newcommand*{\LWR@tabularleftedge}{%
6940 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{1}{%
6941 {}%
6942     \LWR@printatbang{at}{leftedge}%
6943     \LWR@printatbang{bang}{leftedge}%
6944 }% left edge
6945 {}% not left edge
6946 }

```

69.18 Data opening tag

\LWR@thiscolspec Temporary storage.

```
6947 \newcommand*{\LWR@thiscolspec}{}%
```

\LWR@tabledatasinglecolumntag Print a table data opening tag with style for alignment and color.

```

6948 \newcommand*{\LWR@tabledatasinglecolumntag}{%
6949 {}%
6950 \LWR@traceinfo{LWR@tabledatasinglecolumntag}%
6951 \LWR@maybenewtablerow%

```

Don't start a new paragraph tag if have already started one:

```
6952 \ifbool{LWR@intabularmetadata}{%
6953 {%
```

If have found the end of tabular command, do not create the next data cell:

```
6954     \ifbool{LWR@existingtabular}{}{%
6955     {%
6956         \ifbool{LWR@exittingtabular}{}{%
6957             \xdef\LWR@strresult{%
6958                 \LWR@getexpparray{LWR@tablecolspe}{{\arabic{LWR@tableLaTeXcolindex}}}}%
6959             }%
6960 \LWR@traceinfo{LWR@tabledata single column tag: about to print td tag}%
6961         \LWR@htmltag{td class="td"}%
```

Print the @ and ! contents before first column:

```
6956     \LWR@tabularleftedge%
```

Fetch the current column's alignment character into \LWR@strresult:

```
6957     \xdef\LWR@strresult{%
6958         \LWR@getexpparray{LWR@tablecolspe}{{\arabic{LWR@tableLaTeXcolindex}}}}%
6959     }%
```

print the start of a new table data cell:

```
6960 \LWR@traceinfo{LWR@tabledata single column tag: about to print td tag}%
6961     \LWR@htmltag{td class="td"}%
```

append this column's spec:

```
6962     \LWR@strresult%
```

If this column has a cmidrule, add "rule" to the end of the HTML class tag. Also add vertical bar tags.

```
6963     \LWR@addcmidruletrim%
6964     \LWR@addleftmostbartag%
6965     \LWR@printbartag{{\arabic{LWR@tableLaTeXcolindex}}}}%
6966     "%
```

Add styles for rules, alignment:

```
6967     \LWR@tdstartstyles%
6968     \LWR@addcmidrulewidth%
6969     \LWR@addcdashline%

6970     \xdef\LWR@thiscolspe{%
6971         \LWR@getexpparray{LWR@tablecolspe}{{\arabic{LWR@tableLaTeXcolindex}}}}%
6972     }%
6973     \LWR@addformatwpalignment{\LWR@thiscolspe}%
```

Add styles for cell and rule colors:

```

6974      \LWR@addtabulararrowcolor%
6975      \LWR@addtabularrulecolors%
6976      \LWR@tdendstyles%
6977      }% HTML td
6978      \LWR@traceinfo{LWR@tabledatasinglecolumntag: done printing td tag}%

```

If this is a p, m, b, or X column, allow paragraphs:

```

6979      \ifboolexpr{%
6980          test{ \ifdefstring{\LWR@strresult}{p} } or
6981          test{ \ifdefstring{\LWR@strresult}{m} } or
6982          test{ \ifdefstring{\LWR@strresult}{b} } or
6983          test{ \ifdefstring{\LWR@strresult}{P} } or
6984          test{ \ifdefstring{\LWR@strresult}{M} } or
6985          test{ \ifdefstring{\LWR@strresult}{B} } or
6986          test{ \ifdefstring{\LWR@strresult}{X} }%
6987      }%
6988      {%
6989          \LWR@traceinfo{LWR@tabledatasinglecolumntag: about to LWR@startpars}%
6990          \global\booltrue{LWR@tableparcell}%
6991          \LWR@startpars%
6992          \LWR@traceinfo{LWR@tabledatasinglecolumntag: done with LWR@startpars}%
6993      }%
6994      {}% no pars

```

Print the > contents unless muted for the \bottomrule:

```

6995      \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}{%
6996      }%
6997      {%
6998          \LWR@getexparray{LWR@colbeforespec}{\arabic{LWR@tableLaTeXcolindex}}%
6999      }%
7000      \global\boolfalse{LWR@intabularmetadata}%
7001      }% not exiting tabular
7002  }{}% in tabular metadata
7003 \LWR@traceinfo{LWR@tabledatasinglecolumntag: done}%
7004 }%

```

69.19 Midrules

LWR@midrules LWR@midrules is a data array (section 40) of columns each containing a non-zero width if a midrule should be created for this column.

LWR@trimlrules LWR@trimlrules is a data array (section 40) of columns containing 1 if a midrule should be left trimmed for each column.

LWR@trimrrules LWR@trimrrules is a data array (section 40) of columns containing r if a midrule should be right trimmed for each column.

LWR@cdashlines LWR@cdashlines is a data array (section 40) of columns each containing a Y if an **arydshln** package "cdashed line" should be created for this column.

Ctr LWR@midrulecounter Indexes across the LWR@midrules and LWR@trim<l/r>rules data arrays.

```
7005 \newcounter{LWR@midrulecounter}
```

Len \LWR@heavyrulewidth The default width of the rule.

```
7006 \newlength{\LWR@heavyrulewidth}
7007 \setlength{\LWR@heavyrulewidth}{.08em}
```

Len \LWR@lightrulewidth The default width of the rule.

```
7008 \newlength{\LWR@lightrulewidth}
7009 \setlength{\LWR@lightrulewidth}{.05em}
```

Len \LWR@cmidrulewidth The default width of the rule.

```
7010 \newlength{\LWR@cmidrulewidth}
7011 \setlength{\LWR@cmidrulewidth}{.03em}
```

Len \LWR@thiscmidrulewidth The width of the next rule, defaulting to \LWR@cmidrulewidth.

If not \LWR@cmidrulewidth, a style will be used to generate the custom width.

Assigned from the LWR@midrules array.

```
7012 \newlength{\LWR@thiscmidrulewidth}
7013 \setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}
```

\LWR@clearmidrules Start new midrules. Called at beginning of tabular and also at \\.

Clears all LWR@midrules and LWR@trimrules markers for this line.

```
7014 \newcommand*{\LWR@clearmidrules}{%
7015 {%
7016 \setcounter{LWR@midrulecounter}{1}%
7017 \whileboolexpr{%
7018     not \value{LWR@midrulecounter}>{%
7019         \ifnumcomp{\value{LWR@midrulecounter}}{>}{%
7020             {\value{LWR@tabletotalLaTeXcols}}}}%
```

```

7021      }%
7022 }%
7023 {%
7024     \LWR@setexpparray{\LWR@midrules}{\arabic{\LWR@midrulecounter}}{0pt}%
7025     \setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
7026     \LWR@setexpparray{\LWR@trimlrules}{\arabic{\LWR@midrulecounter}}{}%
7027     \LWR@setexpparray{\LWR@trimrrules}{\arabic{\LWR@midrulecounter}}{}%
7028     \LWR@setexpparray{\LWR@cdashlines}{\arabic{\LWR@midrulecounter}}{N}%
7029     \addtocounter{\LWR@midrulecounter}{1}%
7030 }%
7031 }

```

`\LWR@subcmidrule {<width>} {<trim>} {<leftcolumn>} {<rightcolumn>}`

Marks LWR@midrules data array elements to be non-zero widths from left to right columns. Also marks trimming for the L and/or R columns.

LWR@doingcmidrule is set to force an empty row at the end of the tabular to create the rule.

```

7032 \newcommand*{\LWR@subcmidrule}[4]{%
7033 \setcounter{\LWR@midrulecounter}{#3}%
7034 \whileboolexpr{%
7035   not test {%
7036     \ifnumcomp{\value{\LWR@midrulecounter}}{>}{#4}%
7037   }%
7038 }%
7039 {%
7040   \LWR@setexpparray{\LWR@midrules}{\arabic{\LWR@midrulecounter}}{#1}%
7041   \addtocounter{\LWR@midrulecounter}{1}%
7042 }% whileo
7043 \IfSubStr{#2}{1}{\LWR@setexpparray{\LWR@trimlrules}{#3}{1}}{}%
7044 \IfSubStr{#2}{r}{\LWR@setexpparray{\LWR@trimrrules}{#4}{r}}{}%
7045 \global\booltrue{\LWR@doingcmidrule}%
7046 }

```

`\LWR@docmidrule [<width>] (<trim>) {<leftcolumn-rightcolumn>}`

Marks LWR@midrules array elements to be a non-zero width from left to right columns. Also marks trimming for the L and/or R columns.

```

7047 \NewDocumentCommand{\LWR@docmidrule}{%
7048   O{\LWR@cmidrulewidth} D(){} >{\SplitArgument{1}{-}m}%
7049   {\LWR@subcmidrule{#1}{#2}{#3}}

```

`\LWR@subcdashline {<leftcolumn>} {<rightcolumn>}`

Marks LWR@cdashlines data array elements to be Y from left to right columns.

`LWR@doingcmidrule` is set to force an empty row at the end of the tabular to create the rule.

```

7050 \newcommand*{\LWR@subcdashline}[2]{%
7051 \setcounter{LWR@midrulecounter}{#1}%
7052 \whileboolexpr{%
7053   not test {%
7054     \ifnumcomp{\value{LWR@midrulecounter}}{>}{#2}%
7055   }%
7056 }%
7057 {%
7058   \LWR@setexparray{LWR@cdashlines}{\arabic{LWR@midrulecounter}}{Y}%
7059   \addtocounter{LWR@midrulecounter}{1}%
7060 }%
7061 \global\booltrue{LWR@doingcmidrule}%
7062 }

```

`\LWR@docdashline {<leftcolumn-rightcolumn>}`

Marks `LWR@cdashlines` data array elements to be Y from left to right columns.

```

7063 \NewDocumentCommand{\LWR@docdashline}{%
7064   >{\SplitArgument{1}{-}m}%
7065   {%
7066     \LWR@subcdashline#1%
7067   }
}

```

Used to compute margins, tabular trims, column offsets:

```

7068 \newlength{\LWR@templengthone}%
7069 \newlength{\LWR@templengthtwo}%
7070 \newlength{\LWR@templengththree}%
7071 \newcounter{LWR@tempcountone}

```

Used to add a style to a table data cell:

```
7072 \newbool{LWR@tdhavecellstyle}
```

`\LWR@tdstartstyles` Begins possibly adding a table data cell style.

```
7073 \newcommand*{\LWR@tdstartstyles}{\global\boolfalse{LWR@tdhavecellstyle}}
```

`\LWR@tdaddstyle` Starts adding a table data cell style.

```

7074 \newcommand*{\LWR@tdaddstyle}{%
7075 \ifbool{LWR@tdhavecellstyle}{%

```

```

7076 {; }%
7077 { style=""}%
7078 \booltrue{LWR@tdhavecellstyle}%
7079 }

```

\LWR@tdendstyles Finishes possibly adding a table data cell style. Prints the closing quote.

```

7080 \newcommand*{\LWR@tdendstyles}{%
7081 \ifbool{LWR@tdhavecellstyle}{%
7082   "%
7083   \global\boolfalse{LWR@tdhavecellstyle}%
7084 }{}%
7085 }

```

\LWR@subaddcmidruletrim {\langle lefttrim\rangle} {\langle righttrim\rangle} Adds a \cmidrule with optional trim.

```

7086 \newcommand*{\LWR@subaddcmidruletrim}[2]{%
7087 \setlength{\LWR@templengthone}{%
7088   \LWR@getexpparray{LWR@midrules}{\arabic{LWR@tableLaTeXcolindex}}%
7089 }%
7090 \ifdimcomp{\LWR@templengthone}{>}{0pt}%
7091 {%

```

Print the class with left and right trim letters appended:

```
7092 \LWR@origtilde tdrule#1#2%
```

Remember the width of the rule:

```

7093 \setlength{\LWR@thiscmidrulewidth}{\LWR@templengthone}%
7094 }%
7095 {%
7096 \setlength{\LWR@thiscmidrulewidth}{0pt}%
7097 }%
7098 }

```

\LWR@addcmidruletrim Adds left or right trim to a \cmidrule.

```

7099 \newcommand*{\LWR@addcmidruletrim}{%
7100 \LWR@subaddcmidruletrim%
7101 {\LWR@getexpparray{LWR@trimlrules}{\arabic{LWR@tableLaTeXcolindex}}}%
7102 {\LWR@getexpparray{LWR@trimrrules}{\arabic{LWR@tableLaTeXcolindex}}}%
7103 }

```

\LWR@addrulewidth {\langle thiswidth\rangle} {\langle defaultwidth\rangle}

If not default width, add a custom style with width and color depending on `thiswidth`.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
7104 \newcommand{\LWR@addrulewidth}[2]{%
```

Only add a custom width if `thiswidth` is different than the `defaultwidth`, or if a color is being used:

```
7105 \ifboolexpr{%
7106     test{\ifdimcomp{#1}{=}{Opt}} or
7107     (
7108         ( test{\ifdimcomp{#1}{=}{#2}} and not bool{FormatWP} )
7109         and ( test {\ifdefvoid{\LWR@ruleHTMLcolor}} )
7110     )
7111 }%
7112 {}% default width and color
7113 {}% custom width and/or color
```

Ensure that the width is wide enough to display in the browser:

```
7114     \LWR@forceminwidth{#1}%
```

Begin adding another style:

```
7115     \LWR@tdaddstyle%
```

The style itself:

```
7116     border-top:\LWR@printlength{\LWR@atleastonept} solid %
```

If default gray, the darkness of the color depends on the thickness of the rule:

```
7117     \ifdefvoid{\LWR@ruleHTMLcolor}{%
7118         \ifdimcomp{#1}{<}{\LWR@lightrulewidth}{%
7119             {\LWR@origpound{}AOAOAO}%
7120             {%
7121                 \ifdimcomp{#1}{<}{\LWR@heavyrulewidth}{%
7122                     {\LWR@origpound{}808080}%
7123                     {black}%
7124                 }%
7125             }%
7126             \LWR@origpound{\LWR@ruleHTMLcolor}%
7127         }%
7128 }% custom width and/or color
7129 }
```

\LWR@addcmidrulewidth Adds a style for the rule width.

Must be placed between \LWR@tdstartstyles and \LWR@tdendstyles.

```
7130 \newcommand{\LWR@addcmidrulewidth}{%
7131 \LWR@addrulewidth{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
7132 }
```

\LWR@addcdashline Must be placed between \LWR@tdstartstyles and \LWR@tdendstyles.

```
7133 \newcommand{\LWR@addcdashline}{%
7134 \edef\LWR@tempone{%
7135   \LWR@getexpparray{\LWR@cdashlines}{\arabic{LWR@tableLaTeXcolindex}}%
7136 }%
7137 \ifdefstring{\LWR@tempone}{Y}{%
7138   \LWR@tdaddstyle%
7139   border-top: 1pt dashed %
7140   \ifdefvoid{\LWR@ruleHTMLcolor}{%
7141     {black}%
7142     {\LWR@origpound\LWR@ruleHTMLcolor}%
7143 }{}%
7144 }
```

\LWR@WPcell {\text-align} {\vertical-align}

```
7145 \newcommand*{\LWR@WPcell}[2]{%
7146 \LWR@tdaddstyle%
7147 \LWR@print@mbox{text-align:#1}; \LWR@print@mbox{vertical-align:#2}%
7148 }
```

\LWR@addformatwpalignment If FormatWP, adds a style for the alignment.

Must be placed between \LWR@tdstartstyles and \LWR@tdendstyles.

```
7149 \newcommand*{\LWR@addformatwpalignment}[1]{%
7150 \ifbool{FormatWP}{%
7151 \IfSubStr{#1}{l}{\LWR@WPcell{left}{middle}}{}%
7152 \IfSubStr{#1}{c}{\LWR@WPcell{center}{middle}}{}%
7153 \IfSubStr{#1}{r}{\LWR@WPcell{right}{middle}}{}%
7154 \IfSubStr{#1}{p}{\LWR@WPcell{left}{bottom}}{}%
7155 \IfSubStr{#1}{m}{\LWR@WPcell{left}{middle}}{}%
7156 \IfSubStr{#1}{b}{\LWR@WPcell{left}{top}}{}%
7157 \IfSubStr{#1}{P}{\LWR@WPcell{center}{bottom}}{}%
7158 \IfSubStr{#1}{M}{\LWR@WPcell{center}{middle}}{}%
7159 \IfSubStr{#1}{B}{\LWR@WPcell{center}{top}}{}%
7160 }{}%
7161 }
```

69.20 Cell colors

\LWR@addtabularrowcolor Adds a cell's row color style, if needed.

No color is added for the final row of empty cells which finishes each tabular.

```

7162 \newcommand*\LWR@addtabularrowcolor{%
7163   \ifbool{\LWR@tabularmutemods}{}{%
7164     \ifdefvoid{\LWR@rowHTMLcolor}{%
7165       \ifdefvoid{\LWR@xcolorrowHTMLcolor}{%
7166         \xcolor{row color}%
7167         \LWR@tdaddstyle{%
7168           background:\LWR@origpound\LWR@xcolorrowHTMLcolor}%
7169         }%
7170       }%
7171     \expandafter\% explicit row color%
7172     \LWR@tdaddstyle{%
7173       background:\LWR@origpound\LWR@rowHTMLcolor}%
7174     }%
7175   }%
7176 }

```

\LWR@addtabularhrulecolor Adds a cell's horizontal rule color style, if needed.

```
7177 \newcommand*\LWR@addtabularhrulecolor{%
```

If either form of horizontal rule is requested:

```

7178 \ifboolexpr{%
7179   test{\ifnumcomp{\value{\LWR@hlines}}{>}{0}} or%
7180   test{\ifnumcomp{\value{\LWR@hdashedlines}}{>}{0}} or%
7181   bool{\LWR@doingtbrule}%
7182 }{%

```

If there is a no custom color:

```

7183   \ifdefvoid{\LWR@ruleHTMLcolor}{%
7184     \%
7185     \ifnumcomp{\value{\LWR@hlines}}{>}{1}{%
7186       \%
7187         \LWR@tdaddstyle{%
7188           border-top: 4px double{%
7189             \%
7190             \ifnumcomp{\value{\LWR@hdashedlines}}{>}{1}{%
7191               \%
7192                 \LWR@tdaddstyle{%
7193                   border-top: 2px dashed{%
7194                     \%

```

```

7195      \ifnumcomp{\value{LWR@hdashedlines}}{=}{1}%
7196      {%
7197          \LWR@tdaddstyle%
7198          border-top: 1px dashed%
7199      }{}}

```

If no color and not doubled or dashed, then add nothing, since a simpler rule is the default.

```
7200      }%
```

If there is a custom color:

```

7201      {%
7202      \ifnumcomp{\value{LWR@hlines}}{>}{1}%
7203      {%
7204          \LWR@tdaddstyle%
7205          border-top: 4px double \LWR@origpound\LWR@ruleHTMLcolor%
7206      }% else
7207      \ifnumcomp{\value{LWR@hdashedlines}}{>}{1}%
7208      {%
7209          \LWR@tdaddstyle%
7210          border-top: 2px dashed \LWR@origpound\LWR@ruleHTMLcolor%
7211      }% else
7212      \ifnumcomp{\value{LWR@hdashedlines}}{=}{1}%
7213      {%
7214          \LWR@tdaddstyle%
7215          border-top: 1px dashed \LWR@origpound\LWR@ruleHTMLcolor%
7216      }% else
7217          \LWR@tdaddstyle%
7218          border-top: 1px solid \LWR@origpound\LWR@ruleHTMLcolor%
7219      }{}}
7220      }%
7221 }{}}
7222 }

```

`\LWR@addtabularrulecolors` Adds a cell's rule color styles, if needed.

No color is added for the final row of empty cells which finishes each tabular.

```
7223 \newcommand*{\LWR@addtabularrulecolors}{%
```

Custom horizontal rule color:

```
7224 \LWR@addtabularhrulecolor%
```

No vertical rules if finishing the tabular with a row of empty cells:

```
7225 \ifbooleq{\LWR@tabularmutemods}{1}{%
```

If at the leftmost cell, possibly add a leftmost vertical rule:

```
7226 \ifnumequal{\value{\LWR@tableLaTeXcolindex}}{1}{%
```

Fetch the left edge's vertical bar specification:

```
7227 \edef\tempone{\LWR@getexpparray{\LWR@colbarspec}{leftedge}}%
```

Add a custom style if a vertical bar was requested:

```
7228 \ifdefstring{\tempone}{tvertbarl}{%
7229   \LWR@tdaddstyle%
730   border-left: 1px solid % space
731   \LWR@origpound\LWR@verruleHTMLcolor%
732 }{%
733 \ifdefstring{\tempone}{tvertbarldouble}{%
734   \LWR@tdaddstyle%
735   border-left: 4px double % space
736   \LWR@origpound\LWR@verruleHTMLcolor%
737 }{%
738 \ifdefstring{\tempone}{tvertbarldash}{%
739   \LWR@tdaddstyle%
740   border-left: 1px dashed % space
741   \LWR@origpound\LWR@verruleHTMLcolor%
742 }{%
743 \ifdefstring{\tempone}{tvertbarldoubledash}{%
744   \LWR@tdaddstyle%
745   border-left: 2px dashed % space
746   \LWR@origpound\LWR@verruleHTMLcolor%
747 }{%
748 }}
```

Possibly add a right vertical rule for this cell:

```
7249 \edef\tempone{%
750   \LWR@getexpparray{\LWR@colbarspec}{\arabic{\LWR@tableLaTeXcolindex}}%
751 }%
752 \ifdefstring{\tempone}{tvertbarr}{%
```

Add a custom style if a vertical bar was requested:

```
753   \LWR@tdaddstyle%
754   border-right: 1px solid \LWR@origpound\LWR@verruleHTMLcolor%
755 }{%
756 \ifdefstring{\tempone}{tvertbarrdouble}{%
757   \LWR@tdaddstyle%
```

```

7258         border-right: 4px double \LWR@origpound\LWR@vertruleHTMLcolor%
7259     }{}}%
7260     \ifdefstring{\LWR@tempone}{tvertbarrdash}{%
7261         \LWR@tdaddstyle%
7262         border-right: 1px dashed \LWR@origpound\LWR@vertruleHTMLcolor%
7263     }{}}%
7264     \ifdefstring{\LWR@tempone}{tvertbarrdoubledash}{%
7265         \LWR@tdaddstyle%
7266         border-right: 2px dashed \LWR@origpound\LWR@vertruleHTMLcolor%
7267     }{}}%
7268 }{}}%
7269 }

```

Ctr `\LWR@cellcolordepth` Counts how many cell color <div>s were added to the current tabular data cell.

```
7270 \newcounter{\LWR@cellcolordepth}
```

`\LWR@subaddtabularcellcolor {<HTML color>}`

```

7271 \newcommand*{\LWR@subaddtabularcellcolor}[1]{%
7272 \LWR@htmntag{div class="cellcolor" style="%"
7273     background:\LWR@origpound{}{}#1 %
7274 " }{}}%
7275 \addtocounter{\LWR@cellcolordepth}{1}%
7276 }

```

`\LWR@addtabularcellcolor` Adds a cell color style, if needed.

```

7277 \newcommand*{\LWR@addtabularcellcolor}{%
7278 \ifdefvoid{\LWR@cellHTMLcolor}{%
7279 }{%
7280     \ifdefvoid{\LWR@rowHTMLcolor}{%
7281     }{%
7282         \ifdefvoid{\LWR@xcolorrowHTMLcolor}{%
7283             }{%
7284                 \ifdefvoid{\LWR@columnHTMLcolor}{%
7285                     }{%
7286                         {\LWR@subaddtabularcellcolor{\LWR@columnHTMLcolor}}{%
7287                     }{%
7288                         {\LWR@subaddtabularcellcolor{\LWR@xcolorrowHTMLcolor}}{%
7289                     }{%
7290                         {\LWR@subaddtabularcellcolor{\LWR@rowHTMLcolor}}{%
7291                     }{%
7292                         {\LWR@subaddtabularcellcolor{\LWR@cellHTMLcolor}}{%
7293 }

```

69.21 Multicolumns

69.21.1 Parsing multicolumns

```
7294 \newcounter{LWR@tablemulticolswidth}
```

Indexes into the multicolumn specification:

```
7295 \newcounter{LWR@tablemulticolspos}
```

Remembers multicolumn vertical rules if found in the column spec.

```
7296 \newcounter{LWR@mcolvertbarsl}
7297 \newcounter{LWR@mcolvertbarsr}
7298 \newcounter{LWR@mcolvertbarsldash}
7299 \newcounter{LWR@mcolvertbarsrdash}
7300 \newbool{LWR@mcolvertbaronleft} %
```

\LWR@printmccoltype {<colspec>} Print any valid column type found. Does not print @, !, >, or < columns or their associated tokens.

This is printed as part of the table data tag's class.

```
7301 \newcommand*{\LWR@printmccoltype}[1]{%
7302 \LWR@traceinfo{lwr@printmccoltype -#1-} %
```

Get one token of the column spec:

```
7303 \StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
```

Add to the HTML tag depending on which column type is found:

```
7304 \IfStrEq{\LWR@strresult}{l}{\{}%
7305 \IfStrEq{\LWR@strresult}{c}{\{}%
7306 \IfStrEq{\LWR@strresult}{r}{\{}%
7307 \IfStrEq{\LWR@strresult}{p}{\{}%
7308 \IfStrEq{\LWR@strresult}{m}{\{}%
7309 \IfStrEq{\LWR@strresult}{b}{\{}%
7310 \IfStrEq{\LWR@strresult}{P}{\{}%
7311 \IfStrEq{\LWR@strresult}{M}{\{}%
7312 \IfStrEq{\LWR@strresult}{B}{\{}%
```

```
7313 \IfStrEq{\LWR@strresult}{w}{\{}%
7314 \IfStrEq{\LWR@strresult}{W}{\{}%
```

```
7315 \IfStrEq{\LWR@strresult}{S}{\{}%
7316 \IfStrEq{\LWR@strresult}{s}{\{}%
```

```

7317 \IfStrEq{\LWR@strresult}{X}{p}{\}%
7318 \IfStrEq{\LWR@strresult}{|}{\}%
7319 {%
7320     \ifbool{\LWR@mcolvertbaronleft}{%
7321         {\addtocounter{\LWR@mcolvertbarsl}{1}}% left edge
7322         {\addtocounter{\LWR@mcolvertbarsr}{1}}% not left edge
7323 }%
7324 {%
7325     \IfStrEq{\LWR@strresult}{:}{\}%
7326     {%
7327         \ifbool{\LWR@mcolvertbaronleft}{%
7328             {\addtocounter{\LWR@mcolvertbarsldash}{1}}% left edge
7329             {\addtocounter{\LWR@mcolvertbarsrdash}{1}}% not left edge
7330     }%
7331     {%
7332         \IfStrEq{\LWR@strresult}{;}{\}%
7333         {%
7334             \ifbool{\LWR@mcolvertbaronleft}{%
7335                 {\addtocounter{\LWR@mcolvertbarsldash}{1}}% left edge
7336                 {\addtocounter{\LWR@mcolvertbarsrdash}{1}}% not left edge
7337             }%
7338             {\boolexpr{\LWR@mcolvertbaronleft}}%
7339         }%
7340     }%
7341 \LWR@traceinfo{lwr@printmccoltype done}%
7342 }

```

\LWR@multicolpartext {*num parameters*} Print the data with paragraph tags, advance to bypass the given number of parameters.

```

7343 \newcommand*{\LWR@multicolpartext}[1]{%
7344 \LWR@startpars%
7345 \LWR@multicoltext%
7346 \addtocounter{\LWR@tablemulticolspos}{#1}%
7347 \LWR@stoppars%
7348 }

```

\LWR@multicolother {*colspec*} For @, !, >, <, print the next token without paragraph tags:

```

7349 \newcommand*{\LWR@multicolother}[1]{%
7350 \addtocounter{\LWR@tablemulticolspos}{1}%
7351 \StrChar{#1}{\arabic{\LWR@tablemulticolspos}}[\LWR@strresult]%
7352 \LWR@strresult%

```

A valid column data type was found:

```
7353 \global\booltrue{LWR@validtablecol}%
7354 }
```

\LWR@multicolskip Nothing to print for this column type.

```
7355 \newcommand*{\LWR@multicolskip}{%
```

A valid column data type was found:

```
7356 \global\booltrue{LWR@validtablecol}%
7357 }
```

\LWR@printmccoldata {*colspect*} Print the data for any valid column type found.

```
7358 \newcommand*{\LWR@printmccoldata}[1]{%
7359 \LWR@traceinfo{lwr@printmccoldata -#1}%
```

Not yet found a valid column type:

```
7360 \global\boolfalse{LWR@validtablecol}%
```

Get one token of the column spec:

```
7361 \StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
```

Print the text depending on which column type is found. Also handles @, >, < as it comes to them.

```
7362 \IfStrEq{\LWR@strresult}{l}{\LWR@multicoltext}{}%
7363 \IfStrEq{\LWR@strresult}{c}{\LWR@multicoltext}{}%
7364 \IfStrEq{\LWR@strresult}{r}{\LWR@multicoltext}{}%
7365 \IfStrEq{\LWR@strresult}{D}{}%
7366 \addtocounter{LWR@tablemulticolspos}{3}%
7367 \LWR@multicoltext%
7368 }{}%
```

```
7369 \IfStrEq{\LWR@strresult}{p}{\LWR@multicolpartext{0}}{}%
7370 \IfStrEq{\LWR@strresult}{m}{\LWR@multicolpartext{0}}{}%
7371 \IfStrEq{\LWR@strresult}{b}{\LWR@multicolpartext{0}}{}%
7372 \IfStrEq{\LWR@strresult}{P}{\LWR@multicolpartext{0}}{}%
7373 \IfStrEq{\LWR@strresult}{M}{\LWR@multicolpartext{0}}{}%
7374 \IfStrEq{\LWR@strresult}{B}{\LWR@multicolpartext{0}}{}%
```

```
7375 \IfStrEq{\LWR@strresult}{w}{\LWR@multicolpartext{3}}{}%
7376 \IfStrEq{\LWR@strresult}{W}{\LWR@multicolpartext{3}}{}%
```

```

7377 \IfStrEq{\LWR@strresult}{S}{\LWR@multicoltext}{}
7378 \IfStrEq{\LWR@strresult}{s}{\LWR@multicoltext}{}

7379 \IfStrEq{\LWR@strresult}{X}{\LWR@multicolpartext{0}}{%
7380 \IfStrEq{\LWR@strresult}{|}{\LWR@multicolskip}{%
7381 \IfStrEq{\LWR@strresult}{:}{\LWR@multicolskip}{%
7382 \IfStrEq{\LWR@strresult}{;}{%
7383     \LWR@multicolskip{%
7384     \addtocounter{LWR@tablemulticolspos}{1}%
7385 }{%
7386 \IfStrEq{\LWR@strresult}{\detokenize{@}}{\LWR@multicolother{#1}}{%
7387 \IfStrEq{\LWR@strresult}{\detokenize{!}}{\LWR@multicolother{#1}}{%
7388 \IfStrEq{\LWR@strresult}{\detokenize{>}}{\LWR@multicolother{#1}}{%
7389 \IfStrEq{\LWR@strresult}{\detokenize{<}}{\LWR@multicolother{#1}}{%

```

If an invalid column type:

```
7390 \ifbool{LWR@validtablecol}{\LWR@multicoltext}{}
```

Tracing:

```

7391 \LWR@traceinfo{lwr@printmccoldata done}{%
7392 }
```

\parsemulticolumnalignment {⟨1: colspec⟩} {⟨2: printresults⟩}

Scan the multicolumn specification and execute the printfunction for each entry.

Note that the spec for a p{spec} column, or @, >, <, is a token list which will NOT match l, c, r, or p.

```

7393 \newcommand*{\LWR@parsemulticolumnalignment}[2]{%
7394 \setcounter{LWR@tablemulticolspos}{1}%
7395 \StrLen{#1}[\LWR@strresult]%
7396 \setcounter{LWR@tablemulticolswidth}{\LWR@strresult}%
```

Scan across the tokens in the column spec:

```

7397 \whileboolexpr{%
7398     not test {%
7399         \ifnumcomp{\value{LWR@tablemulticolspos}}{>}{%
7400             \value{LWR@tablemulticolswidth}}{%
7401         }{%
7402     }{%
7403 }}
```

Execute the assigned print function for each token in the column spec:

7404 #2{#1}%

Move to the next token in the column spec:

```
7405 \addtocounter{LWR@tablemulticolspos}{1}%
7406 }%
7407 }
```

69.21.2 Multicolumn factored code

\LWR@addmulticolverrulecolor

7408 \newcommand*{\LWR@addmulticolverrulecolor}{%

No vertical rules if finishing the tabular with a row of empty cells:

7409 \ifbool{LWR@tabularmutemods}{}{%

Left side:

```
7410 \ifnumcomp{\value{LWR@mcolvertbarsl}}{=}{1}{%
7411   \LWR@tdaddstyle%
7412   border-left: 1px solid \LWR@origpound\LWR@verruleHTMLcolor%
7413 }{%
7414 \ifnumcomp{\value{LWR@mcolvertbarsl}}{>}{1}{%
7415   \LWR@tdaddstyle%
7416   border-left: 4px double \LWR@origpound\LWR@verruleHTMLcolor%
7417 }{%
7418 \ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{%
7419   \LWR@tdaddstyle%
7420   border-left: 1px dashed \LWR@origpound\LWR@verruleHTMLcolor%
7421 }{%
7422 \ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}{%
7423   \LWR@tdaddstyle%
7424   border-left: 2px dashed \LWR@origpound\LWR@verruleHTMLcolor%
7425 }}
```

Right side:

```
7426 \ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{%
7427   \LWR@tdaddstyle%
7428   border-right: 1px solid \LWR@origpound\LWR@verruleHTMLcolor%
7429 }{%
7430 \ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{%
7431   \LWR@tdaddstyle%
7432   border-right: 4px double \LWR@origpound\LWR@verruleHTMLcolor%
7433 }}
```

```

7434     \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{%
7435         \LWR@tdaddstyle%
7436         border-right: 1px dashed \LWR@origpound\LWR@vertruleHTMLcolor%
7437     }{%
7438     \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}{%
7439         \LWR@tdaddstyle%
7440         border-right: 2px dashed \LWR@origpound\LWR@vertruleHTMLcolor%
7441     }{%
7442 }%
7443 }
7444 \newcommand{\LWR@multicoltext}{}%
```

To find multicolumn right trim:

```
7445 \newcounter{LWR@lastmulticolumn}
```

```
\LWR@domulticolumn [{<1: vpos>} [{<2: #rows>} {[<3: numLaTeXcols>} {[<4: numHTMLcols>} {[<5: colspec>} {[<6: text>}]

7446 \NewDocumentCommand{\LWR@domulticolumn}{o o m m m +m}{%
7447 \LWR@traceinfo{LWR@domulticolumn -#1- -#2- -#4- -#5-}}%
```

Remember the text to be inserted, and remember that a valid column type was found:

```

7448 \renewcommand{\LWR@multicoltext}{%
7449 #6%
7450 \global\booltrue{LWR@validtablecol}%
7451 }%
```

Compute the rightmost column to be included. This is used to create the right trim.

```

7452 \setcounter{LWR@lastmulticolumn}{\value{LWR@tableLaTeXcolindex}}%
7453 \addtocounter{LWR@lastmulticolumn}{#3}%
7454 \addtocounter{LWR@lastmulticolumn}{-1}%
```

Row processing:

```
7455 \LWR@maybenewtablerow%
```

Begin the opening table data tag:

```

7456 \LWR@htmntag{td colspan="#4" %
7457 \IfValueT{#2}{ % rows?
7458 rowspan="#2" %
```

```

7459 \IfValueT{#1}{%
7460   \ifstrequal{#1}{b}{\style=\\"LWR@print@mbox{vertical-align:bottom}" }{}%
7461   \ifstrequal{#1}{t}{\style=\\"LWR@print@mbox{vertical-align:top}" }{}%
7462 }% vpos?
7463 }% rows?

7464 class="td"

```

Print the column type and vertical bars:

```

7465 \setcounter{LWR@mcolvertbarsl}{0}%
7466 \setcounter{LWR@mcolvertbarsr}{0}%
7467 \setcounter{LWR@mcolvertbarsldash}{0}%
7468 \setcounter{LWR@mcolvertbarsrdash}{0}%
7469 \booltrue{LWR@mcolvertbaronleft}%
7470 \LWR@parsemulticolumnalignment{#5}{\LWR@printmccoltype}%

```

If this column has a cmidrule, add “rule” to the end of the HTML class tag.

If this position had a “Y” then add “rule” for a horizontal rule:

```

7471 \LWR@subaddcmidruletrim%
7472 {\LWR@getexpparray{\LWR@trimrlrules}{\arabic{LWR@tableLaTeXcolindex}}}{%
7473 {\LWR@getexpparray{\LWR@trimrrrules}{\arabic{LWR@lastmulticolumn}}}{%

```

Also add vertical bar class.

```

7474 \ifnumcomp{\value{LWR@mcolvertbarsl}}{=}{1}{ tvertbarl}{%
7475 \ifnumcomp{\value{LWR@mcolvertbarsl}}{>}{1}{ tvertbarldouble}{%
7476 \ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{ tvertbarr}{%
7477 \ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{ tvertbarrdouble}{%
7478 \ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{ tvertbarldash}{%
7479 \ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}{ tvertbarldoubledash}{%
7480 \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{ tvertbarrdash}{%
7481 \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}{ tvertbarrdoubledash}{%

```

Close the class tag's opening quote: " NOT A TYPO

```
7482 %
```

```
7483 \LWR@tdstartstyles%
```

```
7484 \LWR@addtabulararrowcolor%
```

```

7485 \LWR@addcmidrulewidth%
7486 \LWR@addcdashline%
7487 \LWR@addtabularhrulecolor%

```

```

7488 \LWR@addmulticolvertrulecolor%
7489 \LWR@addformatwpalignment{#5}%
7490 \LWR@tdendstyles%
7491 }% end of the opening table data tag
7492 \global\boolfalse{LWR@intabularmetadata}%
7493 \LWR@parsemulticolumnalignment{#5}{\LWR@printmccoldata}%
7494 }

```

69.21.3 Multicolumn

```

\lwr@htmlemulticolumn {⟨numcols⟩} {⟨alignment⟩} {⟨text⟩}

7495 \NewDocumentCommand{\lwr@htmlemulticolumn}{m m +m}%
7496 {%

```

Figure out how many extra HTML columns to add for @ and ! columns:

```
7497 \LWR@tabularhtmlcolumns{\arabic{LWR@tableLaTeXcolindex}}{#1}
```

Create the multicolumn tag:

```
7498 \LWR@domulticolumn{#1}{\arabic{LWR@tabhtmlcoltotal}}{#2}{#3}{}
```

Move to the next L^AT_EX column:

```

7499 \addtocounter{LWR@tableLaTeXcolindex}{#1}%
7500 \addtocounter{LWR@tableLaTeXcolindex}{-1}%

```

Skip any trailing @ or ! columns for this cell:

```

7501 \global\booltrue{LWR@skipatbang}%
7502 }

```

69.21.4 Longtable captions

longtable captions use `\multicolumn`.

Bool `LWR@starredlongtable` Per the **caption** pacakge, step the counter if `longtable*`.

```

7503 \newbool{LWR@starredlongtable}%
7504 \boolfalse{LWR@starredlongtable}

```

Per the **caption** package. User-redefinable float type.

```
7505 \providecommand*{\LTcaptype}{table}
```

```
\LWR@longtabledatacaptiontag * [<toc entry>] {<caption>}

7506 \NewDocumentCommand{\LWR@longtabledatacaptiontag}{s o +m}
7507 {%
```

Remember the latest name for \nameref:

```
7508 \IfValueTF{#2}{% optional given?
7509     \ifblank{#2}{% optional empty?
7510         {\LWR@setlatestname{#3}}% empty
7511         {\LWR@setlatestname{#2}}% given and non-empty
7512     }% optional given
7513 {\LWR@setlatestname{#3}}% no optional
```

Create a multicolumn across all the columns:

Figure out how many extra HTML columns to add for @ and ! columns found between the first and the last column:

```
7514 \LWR@tabularhtmlcolumns{1}{\arabic{\LWR@tabletotalLaTeXcols}}
```

Create the multicolumn tag:

```
7515 \LWR@domulticolumn{\arabic{\LWR@tabletotalLaTeXcols}}%
7516     {\arabic{\LWR@tabhtmlcoltotal}}%
7517     {P}%
7518 {%
7519 \LWR@domulticolumn
7519 \IfBooleanTF{#1}{ star?}
```

Star version, show a caption but do not make a LOT entry:

```
7520 {%
7521     yes star
7521     \LWR@figcaption%
7522     #3%
7523     \endLWR@figcaption%
7524 }%
7525 {%
    No star:
```

Not the star version:

Don't step the counter if \caption[] {A caption.}

```
7526     \ifbool{\LWR@starredlongtable}{%
7527     {%
7528         \ifblank{#2}{% TOC entry
7529             {}%
7530             {}%
7531             \refstepcounter{\LTcaptype}}%
```

```

7532      \protected@edef{\currentlabel}{%
7533          \@nameuse{p@\LTcaptype}\@nameuse{the\LTcaptype}%
7534      }%
7535      }%
7536  }{}%

```

Create an HTML caption. Afterwards, maybe make a LOT entry.

```

7537  \LWR@figcaption%
7538  \@nameuse{fnum@\LTcaptype}\CaptionSeparator#3%
7539  \endLWR@figcaption%

```

See if an optional caption was given:

```
7540  \ifblank{#2}{ TOC entry empty}
```

if the optional caption was given, but empty, do not form a TOC entry

```
7541  {}%
```

If the optional caption was given, but might only be []:

```

7542  {%
7543      TOC entry not empty
    \IfNoValueTF{#2}{ No TOC entry?}

```

The optional caption is []:

```

7544  {%
7545      No TOC entry
        \addcontentsline%
7546      {\@nameuse{ext@\LTcaptype}}%
7547      {\LTcaptype}%
7548      {%
7549          \protect\numberline%
7550          {\@nameuse{p@\LTcaptype}\@nameuse{the\LTcaptype}}%
7551          {\ignorespaces #3\protect\relax}%
7552      }%
7553  }% end of No TOC entry

```

The optional caption has text enclosed:

```

7554  {%
7555      yes TOC entry
        \addcontentsline%
7556      {\@nameuse{ext@\LTcaptype}}%
7557      {\LTcaptype}%
7558      {%
7559          \protect\numberline%
7560          {\@nameuse{p@\LTcaptype}\@nameuse{the\LTcaptype}}%
7561          {\ignorespaces #2\protect\relax}%

```

```

7562           }%
7563       }% end of yes TOC entry
7564   }% end of TOC entry not empty
7565 }% end of no star

```

Skip any trailing @ or ! columns for this cell:

```

7566 \global\booltrue{LWR@skipatbang}%
7567 }% end of \LWR@domulticolumn
7568
7569 \addtocounter{LWR@tableLaTeXcolindex}{\arabic{LWR@tabletotalLaTeXcols}}
7570 \addtocounter{LWR@tableLaTeXcolindex}{-1}
7571
7572 }

```

69.21.5 Counting HTML tabular columns

The L^AT_EX specification for a table includes a number of columns separated by the & character. These columns differ in content from line to line. Additional virtual columns may be specified by the special @ and ! columns. These columns are identical from line to line, but may be skipped during a multicolumn cell.

For HTML output, @ and ! columns are placed into their own tabular columns. Thus, a L^AT_EX \multicolumn command may span several additional @ and ! columns in HTML output. These additional columns must be added to the total number of columns spanned by an HTML multi-column data cell.

```

7573 \newcounter{LWR@tabhtmlcolindex}
7574 \newcounter{LWR@tabhtmlcolend}
7575 \newcounter{LWR@tabhtmlcoltotal}

```

```
\LWR@subtabularhtmlcolumns {<index>}
```

Factored from \LWr@tabularhtmlcolumns, which follows.

```
7576 \newcommand*{\LWR@subtabularhtmlcolumns}[1]{%
```

Temporarily define a macro equal to the @ specification for this column:

```
7577     \edef\LWR@atbangspec{\LWR@getexparray{LWR@colatspec}{#1}}%
```

If the @ specification is not empty, add to the count:

```

7578     \ifdefempty{\LWR@atbangspec}%
7579         {}%
7580         {\addtocounter{LWR@tabhtmlcoltotal}{1}}%

```

Likewise for the ! columns:

```

7581 \edef\LWR@atbangspec{\LWR@getexparray{\LWR@colbangspec}{#1}}%
7582 \ifempty{\LWR@atbangspec}%
7583 {}%
7584 {\addtocounter{\LWR@tabhtmlcoltotal}{1}}%
7585 }
```

\LWR@tabularhtmlcolumns {{*starting L^EX column*} }{{*number L^EX columns*} }

Compute the total number of HTML columns being spanned, considering the starting L^EX table column and the number of L^EX tabular columns being spanned. Any @ and ! columns within this span are included in the total count. The resulting number of HTML columns is returned in the counter LWR@tabhtmlcoltotal.

```
7586 \newcommand*{\LWR@tabularhtmlcolumns}[2]{%
```

Count the starting index, compute ending index, and begin with the count being the L^EX span, to which additional @ and ! columns may be added:

```

7587 \setcounter{\LWR@tabhtmlcolindex}{#1}%
7588 \setcounter{\LWR@tabhtmlcoltotal}{#2}%
7589 \setcounter{\LWR@tabhtmlcolend}{#1}%
7590 \addtocounter{\LWR@tabhtmlcolend}{#2}%
```

If at the left edge, add the at/bang columns for the left edge:

```

7591 \ifnumcomp{\value{\LWR@tabhtmlcolindex}}{=}{1}{%
7592   \LWR@subtabularhtmlcolumns{leftedge}%
7593 }{}}
```

Walk across the L^EX columns looking for @ and ! columns:

```

7594 \whileboolexpr{%
7595   test {%
7596     \ifnumcomp{\value{\LWR@tabhtmlcolindex}}{<}{\value{\LWR@tabhtmlcolend}}{%
7597       }%
7598     }%
7599   }%
7600   \LWR@subtabularhtmlcolumns{\arabic{\LWR@tabhtmlcolindex}}%
7601   \addtocounter{\LWR@tabhtmlcolindex}{1}%
7602 }% whiledo
7603 }

7604 \end{warpHTML}
```

69.22 Multirow if not loaded

A default definition in case **multirow** is not loaded. This is used during table parsing.

```
7605 \begin{warpHTML}
7606 \newcommand{\multirow}[2][c]{}
7607 \end{warpHTML}
```

69.23 Multicolumnrow

A print-mode version is defined here, and is also used during **HTML** output while inside a **lateximage**.

See section 292 for the **HTML** versions.

for HTML & PRINT: 7608 \begin{warpall}

```
\multicolumnrow {\{1:cols\}} {\{2:halign\}} [\{3:vpos\}] {\{4:numrows\}} [\{5:bigstruts\}] {\{6:width\}} [\{7:fixup\}]
{\{8:text\}}
```

For discussion of the use of **\DeclareExpandableDocumentCommand**, see:
<https://tex.stackexchange.com/questions/168434/problem-with-abbreviation-of-multirow-and-multicolumn-latex>

\AtBeginDocument to adjust after the user may have loaded **multirow**, which requires several tests to determine which version is loaded and thus which options are available.

```
7609 \AtBeginDocument{
```

\@ifundefined{xmultirow} determines if **multirow** was never loaded.

Null action if not loaded:

```
7610 \@ifundefined{xmultirow}
7611 {
7612 \DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}{%
7613   {+m +m +0{c} +m +0{O} +m +0{Opt} +m}%
7614   {}%
7615 }% no version of multirow was loaded
7616 {}% \@xmultirow defined, so some version of multirow was loaded
```

\@ifpackageloaded{multirow} determines if v2.0 or later of **multirow** was used, which included the **\ProvidesPackage** macro.

The print version:

```

7617 \@ifpackageloaded{multirow}{% v2.0 or newer
7618 \@ifpackagelater{multirow}{2016/09/01}{2016/09/27 for v2.0
7619 {%
7620 \DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}{%
7621   +m +m +O{c} +m +O{0} +m +O{Opt} +m}%
7622   {\multicolumn{#1}{#2}{\@xmultirow{#3}{#4}{#5}{#6}{#7}{#8}}}}%
7623 }%
7624 {% loaded but older, probably not executed:
7625 \DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}{%
7626   +m +m +O{c} +m +O{0} +m +O{Opt} +m}%
7627   {\multicolumn{#1}{#2}{\@xmultirow{#4}{#5}{#6}{#7}{#8}}}}%
7628 }%
7629 }% package loaded{multirow}

```

If not \@ifpackageloaded{multirow} but \@xmultirow is defined, then this must be v1.6 or earlier, which did not \ProvidesPackage{multirow}, and did not have the vposn option.

```

7630 {% v1.6 or older did not \ProvidePackage
7631 \DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}{%
7632   +m +m +O{c} +m +O{0} +m +O{Opt} +m}%
7633   {\multicolumn{#1}{#2}{\@xmultirow{#4}{#5}{#6}{#7}{#8}}}}%
7634 }%
7635
7636 }% \@ifundefined{@xmultirow}
7637
7638 \providecommand*{\multicolumnrow}{\LWR@print@multicolumnrow}
7639
7640 }% AtBeginDocument

7641 \end{warpall}

```

69.24 Utility macros inside a table

for HTML output: 7642 \begin{warpHTML}

Used to prevent opening a tabular data cell if the following token is one which does not create tabular data:

```
7643 \newcommand*{\LWR@donothing}{}%
```

In case **array** is not loaded:

```
7644 \let\firsthline\relax
```

```
7645 \let\lasthline\relax
7646 \newcommand*{\firsthline}{}%
7647 \newcommand*{\lasthline}{}%
```

In case **bigdelim** is not loaded:

```
7648 \newcommand*{\ldelim}{}%
7649 \newcommand*{\rdelim}{}%
7650 \end{warpHTML}
```

69.25 Special-case tabular markers

for HTML & PRINT: 7651 \begin{warpall}

\TabularMacro Place this just before inserting a custom macro in a table data cell. Doing so tells **l warp** not to automatically start a new HTML table data cell yet. See section 9.9.

```
7652 \newcommand*{\TabularMacro}{}%
7653 \end{warpall}
```

\ResumeTabular Used to resume tabular entries after resuming an environment.

⚠ tabular inside another environment When creating a new environment which contains a **tabular** environment, **l warp**'s emulation of the **tabular** does not automatically resume when the containing environment ends, resulting in corrupted HTML rows. To fix this, use \ResumeTabular as follows. This is ignored in print mode.

```
\StartDefiningTabulars % because & is used in a definition
\newenvironment{outerenvironment}
{
  \tabular{cc}
  left & right \\
}
{
  \TabularMacro\ResumeTabular
  left & right \\
  \endtabular
}
\StopDefiningTabulars
```

for HTML output: 7654 \begin{warpHTML}

```

7655 \newcommand*{\ResumeTabular}{%
7656 \global\boolfalse{LWR@exittingtabular}%
7657 \global\boolfalse{LWR@tabularmutemods}%
7658 \LWR@getmynexttoken%
7659 }

7660 \end{warpHTML}

for PRINT output: 7661 \begin{warpprint}

7662 \newcommand*{\ResumeTabular}{}

7663 \end{warpprint}

```

69.26 Checking for a new table cell

for HTML output: 7664 \begin{warpHTML}

Bool LWR@exittingtabular When \end is found, turns off the next opening data tag.

```
7665 \newbool{LWR@exittingtabular}
```

Bool LWR@tabularmutemods Mutes HTML output for @, !, < and >.

This is used while printing the final row to generate \bottomrules.

```
7666 \newbool{LWR@tabularmutemods}
```

\LWR@tabledatacolumntag Open a new HTML table cell unless the next token is for a macro which does not create data, such as \hline, \toprule, etc:

```

7667 \newcommand*{\LWR@tabledatacolumntag}{%
7668 {%
7669 \LWR@traceinfo{\LWR@tabledatacolumntag}%

```

\show\LWR@mynexttoken to see what tokens to look for

If not any of the below, start a new table cell:

```
7670 \global\let\LWR@mynextaction\LWR@tabledatasinglecolumntag%
```

If exiting the tabular:

```
7671 \ifdefeql{\LWR@mynexttoken}{\end}%
7672     {\global\booltrue{\LWR@exittingtabular}}{}%
```

longtable can have a caption in a cell

```
7673 \ifdefeql{\LWR@mynexttoken}{\caption}%
7674     {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

Look for other things which would not start a table cell:

```
7675 \ifdefeql{\LWR@mynexttoken}{\multicolumn}%
7676     {\global\let\LWR@mynextaction\LWR@donothing}{}%
7677 \ifdefeql{\LWR@mynexttoken}{\multirow}%
7678     {\global\let\LWR@mynextaction\LWR@donothing}{}%
7679 \ifdefeql{\LWR@mynexttoken}{\multicolumnrow}%
7680     {\global\let\LWR@mynextaction\LWR@donothing}{}%
7681 \ifdefeql{\LWR@mynexttoken}{\noalign}%
7682     {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

If an \mrowcell, this is a cell to be skipped over:

```
7683 \ifdefeql{\LWR@mynexttoken}{\mrowcell}%
7684     {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

If an \mcolrowcell, this is a cell to be skipped over:

```
7685 \ifdefeql{\LWR@mynexttoken}{\mcolrowcell}%
7686     {\global\let\LWR@mynextaction\LWR@donothing}{}%

7687 \ifdefeql{\LWR@mynexttoken}{\TabularMacro}%
7688     {\global\let\LWR@mynextaction\LWR@donothing}{}%

7689 \ifdefeql{\LWR@mynexttoken}{\hline}%
7690     {\global\let\LWR@mynextaction\LWR@donothing}{}%

7691 \ifdefeql{\LWR@mynexttoken}{\firsthline}%
7692     {\global\let\LWR@mynextaction\LWR@donothing}{}%

7693 \ifdefeql{\LWR@mynexttoken}{\lasthline}%
7694     {\global\let\LWR@mynextaction\LWR@donothing}{}%

7695 \ifdefeql{\LWR@mynexttoken}{\toprule}%
7696     {\global\let\LWR@mynextaction\LWR@donothing}{}%

7697 \ifdefeql{\LWR@mynexttoken}{\midrule}%
7698     {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

```
7699 \ifdefeql{\LWR@mynexttoken}{\cmidrule}%
7700     {\global\let\LWR@mynextaction\LWR@donothing}{}%
7701 \ifdefeql{\LWR@mynexttoken}{\morecmidrules}%
7702     {\global\let\LWR@mynextaction\LWR@donothing}{}%
7703 \ifdefeql{\LWR@mynexttoken}{\specialrule}%
7704     {\global\let\LWR@mynextaction\LWR@donothing}{}%
7705 \ifdefeql{\LWR@mynexttoken}{\cline}%
7706     {\global\let\LWR@mynextaction\LWR@donothing}{}%
7707 \ifdefeql{\LWR@mynexttoken}{\bottomrule}%
7708     {\global\let\LWR@mynextaction\LWR@donothing}{}%
7709 \ifdefeql{\LWR@mynexttoken}{\rowcolor}%
7710     {\global\let\LWR@mynextaction\LWR@donothing}{}%
7711 \ifdefeql{\LWR@mynexttoken}{\arrayrulecolor}%
7712     {\global\let\LWR@mynextaction\LWR@donothing}{}%
7713 \ifdefeql{\LWR@mynexttoken}{\doublerulesepcolor}%
7714     {\global\let\LWR@mynextaction\LWR@donothing}{}%
7715 \ifdefeql{\LWR@mynexttoken}{\warpprintonly}%
7716     {\global\let\LWR@mynextaction\LWR@donothing}{}%
7717 \ifdefeql{\LWR@mynexttoken}{\warpHTMLonly}%
7718     {\global\let\LWR@mynextaction\LWR@donothing}{}%
7719 \ifdefeql{\LWR@mynexttoken}{\ldelim}%
7720     {\global\let\LWR@mynextaction\LWR@donothing}{}%
7721 \ifdefeql{\LWR@mynexttoken}{\rdelim}%
7722     {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

For arydshln:

```
7723 \ifdefeql{\LWR@mynexttoken}{\hdashline}%
7724     {\global\let\LWR@mynextaction\LWR@donothing}{}%
7725 \ifdefeql{\LWR@mynexttoken}{\cdashline}%
7726     {\global\let\LWR@mynextaction\LWR@donothing}{}%
7727 \ifdefeql{\LWR@mynexttoken}{\firstdashline}%
7728     {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

```
7729 \ifdefeqequal{\LWR@mynexttoken}{\lasthdashline}%
7730     {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

Ignore an empty line between rows:

```
7731 \ifdefeqequal{\LWR@mynexttoken}{\par}%
7732     {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

No action for an \end token.

Add similar to the above for any other non-data tokens which might appear in the table.

Start the new table cell if was not any of the above:

```
7733 \LWR@traceinfo{LWR@tabledatacolumntag: about to do mynext}%
7734 \LWR@mynextaction%
7735 \LWR@traceinfo{LWR@tabledatacolumntag: done}%
7736 }

7737 \end{warpHTML}
```

69.27 \mrowcell

for HTML & PRINT: 7738 \begin{warpall}

- ⚠ \mrowcell The user must insert \mrowcell into any \multirow cells which must be skipped.
⚠ **multirow cells** This command has no action during print output.

```
7739 \newcommand*{\mrowcell}{}%
7740 \end{warpall}
```

69.28 \mcolrowcell

for HTML & PRINT: 7741 \begin{warpall}

- ⚠ \mcolrowcell The user must insert \mcolrowcell into any \multicolumnrow cells which must be skipped. This command has no action during print output.

```
7742 \newcommand*{\mcolrowcell}{}%
7743 \end{warpall}
```

69.29 HTML tabular environment

for HTML output: 7744 \begin{warpHTML}

These are default definitions in case **booktabs** is not loaded, and are not expected to be used, but must exist as placeholders. They are pre-deleted in case **memoir** has already loaded **booktabs**.

```
7745 \LetLtxMacro\toprule\relax
7746 \LetLtxMacro\midrule\relax
7747 \LetLtxMacro\cmidrule\cline
7748 \LetLtxMacro\bottomrule\relax
7749 \LetLtxMacro\addlinespace\relax
7750 \LetLtxMacro\morecmidrules\relax
7751 \LetLtxMacro\specialrule\relax
7752
7753 \newcommand*\toprule[1][]{\hline}
7754 \newcommand*\midrule[1][]{\hline}
7755 \LetLtxMacro\cmidrule\cline
7756 \newcommand*\bottomrule[1][]{\hline}
7757 \newcommand*\addlinespace[1][]{}
7758 \newcommand*\morecmidrules(){}
7759 \newcommand*\specialrule[3]{\hline}
```

\noalign {<text>} Redefined for use inside tabular.

```
7760 \LetLtxMacro\LWR@orignoalign\noalign
7761
7762 \newcommand{\LWR@tabularnoalign}[1]{%
7763 \begingroup%
7764 \global\advance\rownum\m@ne%
7765 \renewcommand*{\LWR@xcolorrowHTMLcolor}{}%
7766 \multicolumn{\value{\LWR@tabletotalLaTeXcols}}{1}{#1} \\
7767 \endgroup%
7768 % \rowc@lors%
7769 \LWR@getmynexttoken%
7770 }
```

\LWR@HTMLhline The definition of \hline depends on whether **tbls** has been loaded. If so, optional space below the line may be specified, but will be ignored.

```
7771 \AtBeginDocument{
7772 @ifpackageloaded{l warp-tbls}
7773 {
7774 \newcommand*{\LWR@HTMLhline}[1][]{%
7775 \ifbool{FormatWP}{%
7776 {\LWR@docmidrule{1-\arabic{\LWR@tabletotalLaTeXcols}}}}%
```

```

7777     {\addtocounter{LWR@hlines}{1}}%
7778     \LWR@getmynexttoken}%
7779 }
7780 {
7781 \newcommand*{\LWR@HTMLhline}{%
7782     \ifbool{FormatWP}{%
7783         {\LWR@docmidrule{1-\arabic{LWR@tabletotalTeXcols}}}{%
7784             {\addtocounter{LWR@hlines}{1}}{%
7785                 \LWR@getmynexttoken}}{%
7786             }{%
7787 }{%
7788 }% AtBeginDocument
7789 \LWR@HTMLcline {\langle columns\rangle}
7790 \NewDocumentCommand{\LWR@HTMLcline}{m}{%
7791 {\LWR@docmidrule{#1}\LWR@getmynexttoken}}%

```

\LWR@nullifyNoAutoSpacing For **babel-french**, turn off auto spacing at the start of the tabular, then nullify the autospacing commands inside the tabular, since they were not compatible with the tabular column parsing code, which uses **xstring**.

```

7790 \AtBeginDocument{
7791 @ifundefined{frenchbsetup}{%
7792 {%
7793     \newcommand*{\LWR@nullifyNoAutoSpacing}{}{%
7794 }{%
7795 {%
7796     \newcommand*{\LWR@nullifyNoAutoSpacing}{%
7797         \NoAutoSpacing}{%
7798         \renewcommand*{\NoAutoSpacing}{}{%
7799             \renewcommand*{\LWR@FBcancel}{}{%
7800             }{%
7801 }{%
7802 }% AtBeginDocument

```

Env LWR@tabular [*vertposition*] {[*colspecs*}]

The new tabular environment will be \let in \LWR@LwarpStart, since **siunitx** might redefine tabular in the user's document.

```

7803 \StartDefiningTabulars
7804
7805 \newenvironment*{LWR@tabular}[2] []
7806 {%
7807 \LWR@traceinfo{LWR@tabular started}{%
7808 \addtocounter{LWR@tabulardepth}{1}}{%

```

Not yet started a table row:

```
7809 \global\boolfalse{LWR@startedrow}%
```

Not yet doing any rules:

```
7810 \setcounter{LWR@hlines}{0}%
7811 \setcounter{LWR@hdashedlines}{0}%
7812 \global\boolfalse{LWR@doingtbrule}%
7813 \global\boolfalse{LWR@doingcmidrule}%
```

For **babel-french**, turn off auto spacing one time, then nullify the autospacing commands since were not compatible with the tabular parsing code.

```
7814 \LWR@nullifyNoAutoSpacing%
```

Have not yet found the end of tabular command. Unmute the @ and ! columns.

```
7815 \global\boolfalse{LWR@exittingtabular}%
7816 \global\boolfalse{LWR@tabularmutemods}%
```

Create the table tag:

```
7817 \global\booltrue{LWR@intabularmetadata}%
7818 \LWR@traceinfo{LWR@tabular: About to LWR@forecenewpage.}%
7819 \LWR@forcenewpage
7820 \LWR@htmlblocktag{table}%
```

Parse the table columns:

```
7821 \LWR@parsetablecols{#2}%
```

Table col spec is: \LWR@tablecolspec which is a string of llccrr, etc.

Do not place the table inside a paragraph:

```
7822 \LWR@stopars%
```

Track column #:

```
7823 \setcounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
7824 \global\boolfalse{LWR@tabularcelladded}%
```

Start looking for midrules:

```
7825 \LWR@clearmidrules%
```

\\\ becomes a macro to end the table row:

```
7826 \LetLtxMacro{\\\}{\LWR@tabularendofline}%
```

The following adjust for **colortbl**.

```
7827 \LetLtxMacro{\arrayrulecolor}{\arrayrulecolor\nexttoken}%
7828 \LetLtxMacro{\doublerulesepcolor}{\doublerulesepcolor\nexttoken}%
7829 \gdef{\LWR@columnHTMLcolor}{}%
7830 \gdef{\LWR@rowHTMLcolor}{}%
7831 \gdef{\LWR@cellHTMLcolor}{}%
7832 \rowcolors{}
```

The vertical rules are set to the color active at the start of the tabular. \arrayrulecolor will then affect horizontal rules inside the tabular, but not the vertical rules.

```
7833 \edef{\LWR@vertruleHTMLcolor}{\LWR@ruleHTMLcolor}%
```

Tracking the depth of cell color <div>s:

```
7834 \setcounter{\LWR@cellcolordepth}{0}%
```

The following may appear before a data cell is created, so after doing their actions, we look ahead with \LWR@getmynexttoken to see if the next token might create a new data cell:

The optional parameter for \hline supports the **tbls** package.

```
7835 \LWR@traceinfo{\LWR@tabular: redefining macros}%
7836 \LetLtxMacro{\noalign}{\LWR@tabularnoalign}%
7837 \LetLtxMacro{\hline}{\LWR@HTMLhline}%
7838 \LetLtxMacro{\cline}{\LWR@HTMLcline}%

7839 \DeclareDocumentCommand{\hdashline}{o}{%
7840     \ifboolexpr{FormatWP}{%
7841         {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}}{%
7842         {\addtocounter{\LWR@hdashedlines}{1}}}}%
7843     \LWR@getmynexttoken%
7844 }%
```



```
7845 \DeclareDocumentCommand{\cdashline}{m}{%
7846     \LWR@docdashline{##1}\LWR@getmynexttoken%
7847 }%
```



```
7848 \DeclareDocumentCommand{\firsthdashline}{o}{%
```

```

7849     \ifbool{FormatWP}{%
7850         {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}{%
7851             {\addtocounter{LWR@hdashedlines}{1}}{%
7852                 \LWR@getmynexttoken{%
7853             }{%
7854 \DeclareDocumentCommand{\lastdashline}{o}{%
7855     \ifbool{FormatWP}{%
7856         {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}{%
7857             {\addtocounter{LWR@hdashedlines}{1}}{%
7858                 \LWR@getmynexttoken{%
7859             }{%

```

The following create data cells and will have no more data in this cell, so we do not want to look ahead for a possible data cell, so do not want to use \LWR@getmynexttoken.

```

7860 \renewcommand{\multicolumn}{\LWR@htmlmulticolumn}{%
7861 \renewcommand*{\mrowcell}{%
7862     \LWR@maybenewtablerow{%
7863     \LWR@tabularleftedge{%
7864         \global\booltrue{\LWR@skippingmrowcell}{%
7865     }{%
7866 \renewcommand*{\mcolrowcell}{%
7867     \LWR@maybenewtablerow{%
7868     \global\booltrue{\LWR@skippingmcolrowcell}{%
7869 }{%
7870 \LetLtxMacro{\caption{\LWR@longtabledatacaptiontag{%

```

Reset for new processing:

```

7871 \global\boolfalse{\LWR@tableparcell}{%
7872 \global\boolfalse{\LWR@skippingmrowcell}{%
7873 \global\boolfalse{\LWR@skippingmcolrowcell}{%
7874 \global\boolfalse{\LWR@skipatbang}{%
7875 \global\boolfalse{\LWR@emptyatbang}{%

```

Set & for its special meaning inside the tabular:

```

7876 \StartDefiningTabulars{%
7877 \protected\gdef&{\LWR@tabularampersand}{%

```

Nest one level deeper of tabular paragraph handling:

```

7878 \addtocounter{LWR@tabularpardepth}{1}{%

```

Look ahead for a possible table data cell:

```

7879 \LWR@traceinfo{\LWR@tabular: about to \LWR@getmynexttoken}{%

```

```
7880 \LWR@getmynexttoken%
7881 }%
```

Ending the environment:

```
7882 {%
7883 \LWR@traceinfo{LWR@tabular ending}%
```

Unnest one level of tabular paragraph handling:

```
7884 \addtocounter{LWR@tabularpardepth}{-1}%
7885 \ifboolexpr{%
7886     test {%
7887         \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}%
7888     } or %
7889     (%
7890         bool{LWR@intabularmetadata} and%
7891         not bool{LWR@tabularcelladded} and%
7892         test {%
7893             \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{\value{LWR@tabletotalLaTeXcols}}%
7894         }%
7895     )%
7896 }%
7897 {%
7898     \LWR@tabularfinishrow%
7899 }%
7900 {%
7901     \LWR@closetabledatacell%
7902 }%
7903 \LWR@htmlblocktag{/tr}%

```

xcolor row color support:

```
7904 @rowc@lors%
7905 \LWR@htmlblocktag{/table}%
7906 \global\boolexpr{LWR@intabularmetadata}{}%
```

Unnest one level of tabular:

```
7907 \addtocounter{LWR@tabulardepth}{-1}%

```

Restore & to its usual meaning:

```
7908 \protected\gdef&{\LWR@origampmacro}%
7909 \StopDefiningTabulars%
7910 \LWR@traceinfo{LWR@tabular finished ending}%
7911 }
```

```

7912
7913 \StopDefiningTabulars

7914 \end{warpHTML}

```

70 Cross-references

Sectioning commands have been emulated from scratch, so the cross-referencing commands are custom-written for them. Emulating both avoids several layers of patches.

The **zref** package is used to remember section name, file, and lateximage depth and number for each label.

Table 11 shows the data structures related to cross-referencing.

for HTML output: 7915 \begin{warpHTML}

70.1 Setup

\@currentlabelname To remember the most recently defined section name, description, or caption, for \nameref.

```
7916 \providecommand*\@currentlabelname{}{}
```

\LWR@stripperiod {\text} [.]

Removes a trailing period.

```
7917 \def\LWR@stripperiod#1.\ltx@empty#2@nil{#1}%
```

\LWR@setlatestname {\object name}

Removes \label, strips any final period, and remembers the result.

```
7918 \newcommand*\LWR@setlatestname[1]{%
```

Remove \label and other commands from the name, the strip any final period. See **zref-titleref** and **getttitlestring**.

```

7919 \GetTitleStringExpand{#1}%
7920 \edef\@currentlabelname{\detokenize\expandafter{\GetTitleStringResult}}%
```

Table 11: Cross-referencing data structures

Original L^AT_EX:	(print and HTML)
\refstepcounter: Steps the counter and sets \currentlabel.	
\currentlabel: \p@<ctr>\the<ctr> Updated by \refstepcounter.	
\label: Writes to the .aux file: \newlabel{<label>}{{\currentlabel}{\thepage}}	
\newlabel: When the .aux file is read, sets \r@<label>.	
\r@<label>: Set to: {{\currentlabel}{\thepage}}	
\ref: Returns the first part of \r@<label>.	
\pageref: Returns the second part of \r@<label>.	
Added by l warp:	(HTML only)
\label: Adds HTML tags (section 70.3), plus \splabel data (section 70.2):	
zLWR@name: The section name for this label.	
zLWR@htmlfilenumber: The filenumber or name for this label.	
zLWR@lateximagedepth: The lateximagedepth for this label.	
zLWR@lateximagenumber: The lateximagenumber for this label.	
\nameref: Emulated from hyperref for l warp. See section 70.4.	
\ref and \nameref: Adds HTML tags. See section 70.4.	
Added by amsmath:	(print and HTML)
\label: Execution is delayed until the math environment is completed.	
\ltx@label: L ^A T _E X \label, (HTML: patched by l warp,) later patched by cleveref.	
Added by cleveref:	(print and HTML)
\refstepcounter: Added: sets \cref@currentlabel.	
\cref@currentlabel: (<type>=<ctr> unless an alias is used): [<type>] [<arabic{<ctr>}>] [<parent ctrs>]{\p@<ctr>\the<ctr>} Also see section 56.4 for use with footnotes.	
\label: Writes to the .aux file: \newlabel{<label>@\cref}{{\cref@currentlabel}{\thepage}}	
\newlabel: (Unchanged.) When the .aux file is read, sets \r@<label>@\cref.	
\r@<label>@\cref: Set to: {{\cref@currentlabel}{\thepage}}	
Utility functions: See \cref@getlabel, \cref@gettype, \cref@getcounter, \cref@getprefix.	
Cross-referencing names: \crefname and \Crefname assign human-readable names for references to this counter type.	
Additionally patched by l warp:	(HTML only)
\cref, etc.: Modified for l warp. See section 84.	
\label inside math: See section 76.7.1.	
Footnotes: See \noteentry in section 56.4.	

```

7921 \edef\@currentlabelname{%
7922 \expandafter\LWR@stripperiod\@currentlabelname%
7923 \ltx@empty.\ltx@empty\@nil%
7924 }%
7925 }

```

70.2 Zref setup

See:

[http://tex.stackexchange.com/questions/57194/
extract-section-number-from-equation-reference](http://tex.stackexchange.com/questions/57194/extract-section-number-from-equation-reference)

Create a new property list called special:

```
7926 \zref@newlist{special}
```

Define a new property which has the name of the most recently declared section:

```
7927 \zref@newprop{zLWR@name}{\@currentlabelname}
```

Define a new property which has either a filename or a file number:

```

7928 \zref@newprop{zLWR@htmlfilename}{%
7929 \ifbool{FileSectionNames}{\LWR@thisfilename}{\arabic{LWR@htmlfilename}}%
7930 }%

```

Additional properties for lateximages:

```

7931 \zref@newprop{zLWR@lateximagedepth}{\arabic{LWR@lateximagedepth}}
7932 \zref@newprop{zLWR@lateximagenumber}{\arabic{LWR@lateximagenumber}}

```

`zLWR@htmlfilename` property holds the file number or name

Add a `LWR@htmlfilename` property, and `lateximage` properties to `special`:

```

7933 \zref@addprop{special}{zLWR@name}
7934 \zref@addprop{special}{zLWR@htmlfilename}
7935 \zref@addprop{special}{zLWR@lateximagedepth}
7936 \zref@addprop{special}{zLWR@lateximagenumber}

```

Returns the selected field:

```

7937 \newcommand*{\LWR@sref}[2]{%
7938 \zref@extractdefault{\#1}{\#2}{??}%
7939 }

```

\LWR@nameref {*label*} Returns the section name for this label:

```
7940 \newcommand*{\LWR@nameref}[1]{%
7941 \LWR@sref{#1}{zLWR@name}%
7942 }
```

\LWR@htmlfileref {*label*} Returns the file number or name for this label:

```
7943 \newcommand*{\LWR@htmlfileref}[1]{%
```

DO NOT USE \LWR@traceinfo HERE! Will be expanded.

```
7944 \LWR@sref{#1}{zLWR@htmlfilename}%
7945 }
```

\LWR@lateximagedepthref {*label*} Returns the lateximagedepth for this label:

```
7946 \newcommand*{\LWR@lateximagedepthref}[1]{%
7947 \LWR@sref{#1}{zLWR@lateximagedepth}%
7948 }
```

\LWR@lateximagenumberref {*label*} Returns the lateximagenumber for this label:

```
7949 \newcommand*{\LWR@lateximagenumberref}[1]{%
7950 \LWR@sref{#1}{zLWR@lateximagenumber}%
7951 }
```

\LWR@splabel {*label*} Sanitize the name and then creates the label:

```
7952 \newcommand*{\LWR@splabel}[1]{%
7953 \LWR@traceinfo{\LWR@splabel !#1!}%
7954 \LWR@setlatestname{@currentlabelname}%
7955 \zref@labelbylist{#1}{special}%
7956 }
```

70.3 Labels

\LWR@sublabel {*label*} Creates an HTML id tag.

\detokenize is used to allow underscores in the labels.

```
7957 \newcommand*{\LWR@sublabel}[1]{%
7958 \LWR@traceinfo{\LWR@sublabel !#1!}%
```

Create an HTML id tag unless are inside a `lateximage`, since it would appear in the image:

```
7959 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
7960 {}%
7961 {%
  not lateximage
```

If not doing a `lateximage`, create an HTML ID tag: (To be factored...)

```
7962   \LWR@sanitize{#1}%
7963   \ifbool{LWR@doingstartpars}%
7964     {%
      pars allowed
      \ifbool{LWR@doingapar}%
        {%
          par started
          \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}\LWR@htmltag{/a}%
        }%
        par started
      {%
        par not started
        \LWR@stoppars%
        \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}\LWR@htmltag{/a}%
        \LWR@startpars%
      }%
      par not started
    }%
    pars allowed
  {%
    pars not allowed
    \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}\LWR@htmltag{/a}%
  }%
  pars not allowed
}%
not lateximage
7979 }
```

`\LWR@new@label` (*bookmark*) {*label*} [*type*]

label during HTML output when not in SVG math mode, removing extra spaces around the label, as done by regular `\label`.

The is also used during a `lateximage`, including SVG math, since the special label handling is required, but `\LWR@sublabel` does not generate HTML tags inside a `lateximage`.

`clevereref` later encases this to add its own cross-referencing.

The optional *bookmark* is per the `memoir` class, and is ignored.

The optional *type* is per the `ntheorem` package, and is ignored.

```
7980 \NewDocumentCommand{\LWR@new@label}{d() m o}{%
7981 \LWR@traceinfo{LWR@new@label: starting}%
7982 \LWR@traceinfo{LWR@new@label: !#2!}%
7983 % \obspshack%
```

Create a traditional L^AT_EX label, as modified by **cleveref**:

```
7984 \LWR@orig@label{#2}%
```

Create a special label which holds the section number, LWR@htmlfilename, LWR@lateximagedepth, and LWR@lateximagenumber:

```
7985 \LWR@traceinfo{LWR@new@label: filesectionnames is \ifbool{FileSectionNames}{true}{false}}%
7986 \LWR@traceinfo{LWR@new@label: LWR@thisfilename is !\LWR@thisfilename!}%
7987 \LWR@traceinfo{LWR@new@label: LWR@htmlfilename is \arabic{LWR@htmlfilename}}%
7988 \LWR@splabel{#2}%
7989 \LWR@sublabel{#2}%
7990 % \@esphack%
7991 \LWR@traceinfo{LWR@new@label: done}%
7992 }
```

70.4 References

\LWR@startref {<label>} (Common code for \ref and \nameref.)

Open an HTML tag reference to a filename, # character, and a label.

```
7993 \newcommand*{\LWR@startref}[1]%
7994 {%
7995 \edef\LWR@lidref{\LWR@lateximagedepthref{#1}}%
7996 \LWR@sanitize{#1}%
7997 \LWR@traceinfo{LWR@startref A: !#1!}%
```

Create the filename part of the link:

```
7998 \LWR@htmntag{a href="%"
7999 \LWR@traceinfo{LWR@startref B}%
8000 \LWR@print@mbox{\LWR@htmlrefsectionfilename{#1}}%
8001 \LWR@traceinfo{LWR@startref C}%
8002 \LWR@origpound%
```

Create the destination id:

See if LWR@lateximagedepth is unknown:

```
8003 \LWR@traceinfo{LWR@startref D: !#1!}%
8004 \ifthenelse{\equal{\LWR@lidref}{??}}{%
```

“??” if LWR@lateximagedepth is unknown, so create a link with an unknown destination:

```

8005 {%
8006     \LWR@traceinfo{\LWR@startref D0: ??}%
8007     ??%
8008 }%

```

If `\LWR@lateximagedepth` is known. Use a `lateximage` if the depth is greater than zero, or a regular link otherwise:

```

8009 {%
8010     \LWR@traceinfo{\LWR@startref D1: \LWR@lidref}%
8011     \ifthenelse{\cnttest{\LWR@lidref}{>}{0}}{%
8012         {%
8013             \LWR@traceinfo{\LWR@startref D2: \LWR@lidref}%
8014             lateximage\lWR@lateximagenumberref{#1}%
8015         }%
8016     {%
8017         \LWR@traceinfo{\LWR@startref D3}%
}

```

`\detokenize` is used to allow underscores in the labels:

```

8018     \LWR@print@mbox{\LWR@sanitized}%
8019     }%
8020 }%
8021 \LWR@traceinfo{\LWR@startref E}%

```

Closing quote:

```

8022 "}%
8023 \LWR@traceinfo{\LWR@startref F}%
8024 }

```

`\LWR@subnewref {<label>} {<label or sub@label>}`

Factored for the `subfig` package. Uses the original label for the hyper-reference, but prints its own text, such as “1(b)”.

```

8025 \NewDocumentCommand{\LWR@subnewref}{m m}{%
8026 \LWR@traceinfo{\LWR@subnewref #1 #2}%
8027 \LWR@startref{#1}%
8028 \LWR@print@ref{#2}%
8029 \LWR@htmltag{/a}%
8030 }

```

`\ref * {<label>}` `\ref` is redefined to `\LWR@HTML@ref`, except inside the text part of a `\hyperref`, where it is redefined to `\LWR@ref@ignorestar`.

\LWR@HTML@ref * {*label*} Create an internal document reference link, or without a link if starred per **hyperref**.

```

8031 \NewDocumentCommand{\LWR@HTML@ref}{s m}{%
8032 \LWR@traceinfo{LWR@HTML@ref !#2!}%
8033 \IfBooleanTF{#1}%
8034 {\LWR@print@ref{#2}}%
8035 {\LWR@subnewref{#2}{#2}}%
8036 }%
8037
8038 \LWR@formatted{ref}
```

\LWR@ref@ignorestar * {*label*} For use inside \hyperref. Ignores the star, then uses the original \ref.

```

8039 \NewDocumentCommand{\LWR@ref@ignorestar}{s m}{%
8040     \LWR@print@ref{#2}%
8041 }
```

\pagerefPageFor Text for page references.

```
8042 \newcommand*{\pagerefPageFor}{see }
```

\pageref * {*label*} Create an internal document reference, or just the unlinked number if starred, per **hyperref**.

```

8043 \NewDocumentCommand{\LWR@new@pageref}{s m}{%
8044 \IfBooleanTF{#1}%
8045 {(\pagerefPageFor\LWR@print@ref{#2})}%
8046 {(\cpageref{#2})}%
8047 }
```

\nameref {*label*}

```

8048 \newrobustcmd*{\nameref}[1]{%
8049 \LWR@traceinfo{nameref}%
8050 \LWR@startref{#1}%
8051 \LWR@traceinfo{nameref B}%
8052 \LWR@nameref{#1}%
8053 \LWR@traceinfo{nameref C}%
8054 \LWR@htmlltag{/a}%
8055 \LWR@traceinfo{nameref: done}%
8056 }
```

\Nameref {*label*} In print, adds the page number. In HTML, does not.

```
8057 \LetLtxMacro{\nameref}{\nameref}
```

70.5 Hyper-references

- ⚠ Note that the code currently only sanitizes the underscore character. Additional characters should be rendered inert as well. See the `hyperref.sty` definition of `\gdef\hyper@normalise` for an example.

Pkg `hyperref`

- ⚠ Do not tell other packages that `hyperref` is emulated. Some packages patch various commands if `hyperref` is present, which will probably break something, and the emulation already handles whatever may be emulated anyhow.

```
8058 % DO NOT TELL OTHER PACKAGES TO ASSUME HYPERREF, lest they attempt to patch it:
8059 % \EmulatesPackage{hyperref}[2015/08/01]%
% Disabled. Do not do this.
```

Emulates `hyperref`:

`\@currentHref` Added to support `backref`.

```
8060 \AtBeginDocument{
8061 \def\@currentHref{%
8062 autopage-\theLWR@currentautosec%
8063 }
8064 }
```

`\LWR@subhyperref` `{⟨URL⟩}`

Starts a link for `\LWR@hrefb`. A group must have been opened first, with nullified catcodes. The text name is printed afterwards, after the group is closed and catcodes restored.

```
8065 \NewDocumentCommand{\LWR@subhyperref}{m}{%
8066 \LWR@traceinfo{\LWR@subhyperref !#1!}%
8067 \LWR@sanitize{#1}%
8068 \LWR@htmntag{%
8069     a href="\LWR@sanitized" %
8070     target="_blank"\LWR@orignewline%
8071 }%
8072 }
```

`\LWR@subhyperreftext` `{⟨text⟩}`

Finishes the hyperref for `\LWR@hrefb`. Catcodes must have been restored already. To be used after `\LWR@subhyperref`, and after its group has been closed.

```
8073 \newcommand{\LWR@subhyperreftext}[1]{%
```

```

8074 #1%
8075 \LWR@htmltag{/a}%
8076 \LWR@ensuredoingapar%
8077 }

\LWR@subhyperrefclass {⟨URL⟩} {⟨text⟩} {⟨htmlclass⟩}

8078 \NewDocumentCommand{\LWR@subhyperrefclass}{m +m m}{%
8079 \LWR@htmltag{%
8080     a href="#"%
8081         \begingroup\@sanitize#1\endgroup%
8082     " %
8083     class="#3"\LWR@orignewline%
8084 }%
8085 #2%
8086 \LWR@htmltag{/a}%
8087 \LWR@ensuredoingapar%
8088 }

```

`\href [⟨options⟩] {⟨URL⟩}`

Create a link with accompanying text:

```

8089 \DeclareDocumentCommand{\LWR@hrefb}{O{} m}{%
8090 \LWR@ensuredoingapar%
8091 \LWR@subhyperref{#2}%
8092 \endgroup% restore catcodes
8093 \LWR@subhyperreftext%
8094 }%
8095
8096 \newrobustcmd*\href{%
8097 \begingroup%
8098 \catcode`\#=12%
8099 \catcode`\%=12%
8100 \catcode`\&=12%
8101 \catcode`\~=12%
8102 \catcode`\_=12%
8103 \LWR@hrefb%
8104 }

```

`\nolinkurl {⟨URL⟩}`

Print the name of the link without creating the link:

```

8105 \newcommand*\LWR@nolinkurlb[1]{%
8106 \LWR@ensuredoingapar%
8107 \def\LWR@templink{#1}%

```

```

8108 \@onellevel@sanitize\LWR@templink%
8109 \LWR@templink%
8110 \endgroup%
8111 }
8112
8113 \newrobustcmd*\{nolinkurl}{%
8114 \begingroup%
8115 \catcode`\#=12%
8116 \catcode`\%=12%
8117 \catcode`\&=12%
8118 \catcode`\~=12%
8119 \catcode`\_=12%
8120 \LWR@nolinkurlb%
8121 }

```

\url {⟨URL⟩}

Create a link whose text name is the address of the link.

The **url** package may redefine \url, so it is \let to \LWR@urlahere and also redefined by **l warp-url**.

```

8122 \DeclareDocumentCommand{\LWR@urlb}{m}{%
8123 \LWR@ensuredoingapar%
8124 \def\LWR@templink[#1]{%
8125 \@onellevel@sanitize\LWR@templink%
8126 \href{\LWR@templink}{\LWR@templink}%
8127 \endgroup%
8128 }
8129
8130 \newrobustcmd*\{url}{%
8131 \begingroup%
8132 \catcode`\#=12%
8133 \catcode`\%=12%
8134 \catcode`\&=12%
8135 \catcode`\~=12%
8136 \catcode`\_=12%
8137 \LWR@urlb%
8138 }

```

\LWR@subinlineimage [⟨alttag⟩] {⟨class⟩} {⟨filename⟩} {⟨extension⟩} {⟨style⟩}

```

8139 \newcommand*\{LWR@subinlineimage}[5][]{%
8140 \ifblank[#1]{%
8141 {\LWR@htmltag{img src="#3.\#4" alt="#3" style="#5" class="#2"};}%
8142 {\LWR@htmltag{img src="#3.\#4" alt="#1" style="#5" class="#2"};}%
8143 }

```

8144 \end{warpHTML}

Table 12: Float data structures

For each <type> of float (figure, table, etc.) there exists the following:

counter <type>: A counter called <type>, such as `figure`, `table`.

`\<type>name`: Name. `\figurename` prints “Figure”, etc.

`\ext@<type>`: File extension. `\ext@figure` prints “lof”, etc.

`\fps@<type>`: Placement.

`\the<type>`: Number. `\thetable` prints the number of the table, etc.

`\p@<type>`: Parent’s number. Prints the number of the [within] figure, etc.

`\fnum@<type>`: Prints the figure number for the caption.

`\<type>name \the<type>`, “Figure 123”.

`\<type>`: Starts the float environment. `\figure` or `\begin{figure}`

`\end<type>`: Ends the float environment. `\endfigure` or `\end{figure}`

`\tf@<ext>`: The `\TeX` file identifier for the output file.

`\LWR@have<type>`: A boolean remembering whether a `\listof` was requested for a float of this type.

File with extension lo<f,t,a-z>: An output file containing the commands to build the `\listof<type>` “table-of-contents” structure.

Cross-referencing names: For `cleveref`’s `\cref` and related, `\crefname` and `\Crefname` assign human-readable names for references to this float type.

71 Floats

Floats are supported, although partially through emulation.

Table 12 shows the data structure associated with each <type> of float.

`\@makecaption` is redefined to print the float number and caption text, separated by `\CaptionSeparator`, which works with the `babel` package to adjust the caption separator according to the language. French, for example, uses an en-dash instead of a colon: “Figure 123 – Caption text”.

71.1 Float environment

for HTML output: 8145 \begin{warpHTML}

\LWR@floatbegin {*type*} [*placement*] Begins a \newfloat environment.

```
8146 \NewDocumentCommand{\LWR@floatbegin}{m o}{%
8147 \ifbool{FormatWP}{\newline}{}%
8148 \LWR@stoppars
```

There is a new float, so increment the unique float counter:

```
8149 \addtocounter{LWR@thisautoid}{1}%
8150 \booltrue{LWR@freezethisautoid}%

8151 \begingroup%
```

Settings while inside the environment:

```
8152 \LWR@print@raggedright%
```

Open an HTML figure tag. The figure is assigned a class equal to its type, and another class according to the **float** package style, if used. Note that \csuse returns an empty string if \LWR@floatstyle@<type> is not defined.

```
8153 \LWR@htmlltag{%
8154     figure id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}" % space
8155     class="#1 \nameuse{LWR@floatstyle@#1}"%
8156 }%
8157 \ifbool{FormatWP}{%
8158     \LWR@orignewline%
8159     \LWR@BlockClassWP{}{}{wp#1}%
8160 }{}%
```

Update the caption type:

```
8161 \renewcommand*{\@capttype}{#1}%
8162 \caption@settype{#1}%
```

Mark the float for a word processor conversion:

```
8163 \LWR@startpars%
8164 \ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%
8165
8166 === begin #1 ===
8167
8168 }{}%
```

Look for \centering, etc:

```
8169 \LWR@futureonospacelet\LWR@mynexttoken\LWR@floatalignment%
8170 }
```

For **koma-script**. The following does not work for tables.

```
8171 \AtBeginDocument{
8172 @ifpackageloaded{tocbasic}{
8173 \appto\figure@atbegin{%
8174 \LWR@futureonospacelet\LWR@mynexttoken\LWR@floatalignment%
8175 }
8176 }{}}
8177 }
```

\@float Support packages which create floats directly.
 \@dblfloat
 8178 \let@\@float\LWR@floatbegin
 8179 \let@\dblfloat\LWR@floatbegin

\LWR@floatend Ends a \newfloat environment.

```
8180 \newcommand*\LWR@floatend{%
```

If saw a \centering, finish the center environment:

```
8181 \LWR@endfloatalignment%
```

Mark the float end for a word processor conversion:

```
8182 \ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%
8183
8184 === end ===
8185
8186 }{}%
8187 \LWR@stoppars%
```

Close an HTML figure tag:

```
8188 \ifbool{FormatWP}{\endLWR@BlockClassWP}{%
8189 \LWR@htmlelementend{figure}%
8190 \endgroup%
8191 \boolfalse{\LWR@freezethisautoid}%
8192 \LWR@startpars%
8193 \ifbool{FormatWP}{\newline}{%
8194 }}
```

```
\end@float Support packages which create floats directly.
\end@dblfloat
8195 \let\end@float\LWR@floatend
8196 \let\end@dblfloat\LWR@floatend
```

71.2 Float tracking

Ctr LWR@thisautoid A sequential counter for all floats and theorems. This is used to identify the float or theorem then reference it from the List of Figures and List of Tables.

```
8197 \newcounter{LWR@thisautoid}
```

Ctr LWR@thisautoidWP A sequential counter for all word processor conversion <div>s. This is used to convince LIBREOFFICE to form a frame around this element.

```
8198 \newcounter{LWR@thisautoidWP}
```

Bool LWR@freezethisautoid Prevents multiple increments of \LWR@thisautoid inside a float.

```
8199 \newbool{LWR@freezethisautoid}
8200 \boolfalse{LWR@freezethisautoid}
```

\LWR@newautoidanchor Adds a new <autoid> anchor.

```
8201 \newcommand*{\LWR@newautoidanchor}{%
8202 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
8203 {}%
8204 {%
8205 \ifbool{LWR@freezethisautoid}{}{%
8206 \addtocounter{LWR@thisautoid}{1}%
8207 \LWR@htmlltag{a id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}"}%
8208 \LWR@htmlltag{/a}%
8209 }%
8210 }%
8211 }
```

\@capttype Remembers which float type is in use.

```
8212 \newcommand*{\@capttype}{}%
```

\LWR@floatalignmentname Set to center, flushleft, or flushright if saw \centering, \raggedright, or \raggedleft.

```
8213 \newcommand*{\LWR@floatalignmentname}{}%
```

\LWR@floatalignment If sees a \centering, \raggedleft, or \raggedright, creates a center, flushright, or flushleft environment.

```

8214 \newcommand*\LWR@floatalignment{%
8215 \ifdef\streq{\LWR@mynexttoken}{\centering}{%
8216   \center%
8217   \renewcommand*\LWR@floatalignmentname{center}%
8218 }{}}%
8219 \ifdef\streq{\LWR@mynexttoken}{\raggedright}{%
8220   \flushleft%
8221   \renewcommand*\LWR@floatalignmentname{flushleft}%
8222 }{}}%
8223 \ifdef\streq{\LWR@mynexttoken}{\raggedleft}{%
8224   \flushright%
8225   \renewcommand*\LWR@floatalignmentname{flushright}%
8226 }{}}%
8227 }
```

\LWR@endfloatalignment Closes an environment from \LWR@floatalignment.

```

8228 \newcommand*\LWR@endfloatalignment{%
8229 \ifdef\void{\LWR@floatalignmentname}{}{\@nameuse{end\LWR@floatalignmentname}}%
8230 \renewcommand*\LWR@floatalignmentname{}%
8231 }
```

71.3 Caption inside a float environment

\CaptionSeparator How to separate the float number and the caption text.

```
8232 \AtBeginDocument{\providecommand*\CaptionSeparator{:\~}}
```

\@makecaption {\langle name and num\rangle} {\langle text\rangle}

Prints the float type and number, the caption separator, and the caption text.

```

8233 \AtBeginDocument{\renewcommand{\@makecaption}[2]{%
8234   \LWR@traceinfo{@makecaption}%
8235   #1\CaptionSeparator#2%
8236   \LWR@traceinfo{@makecaption: done}%
8237 }%
8238 }
```

71.4 Caption and LOF linking and tracking

When a new HTML file is marked in the L^AT_EX PDF file, the L^AT_EX page number at that point is stored in `LWR@latestautopage`, (and the associated filename is remembered by the special L^AT_EX labels). This page number is used to generate an autopage HTML `<id>` in the HTML output at the start of the new HTML file. Meanwhile, there is a float counter used to generate an HTML autoid `<id>` at the start of the float itself in the HTML file. The autopage and autoid values to use for each float are written to the `.lof`, etc. files just before each float's entry. These values are used by `\l@figure`, etc. to create the HTML links in the List of Figures, etc.

- Ctr `LWR@nextautoid` Tracks autoid for floats. Tracks autopage for floats.
- Ctr `LWR@nextautopage` These are updated per float as the `.lof`, `.lot` file is read.

```
8239 \newcounter{LWR@nextautoid}
8240 \newcounter{LWR@nextautopage}
```

`\LWRsetnextfloat {<autopage>} {<autoid>}`

This is written to the `.lof`, `.lot` file just before each float's usual entry. The autopage and autoid are remembered for `\l@figure` to use when creating the HTML links.

```
8241 \newcommand*{\LWRsetnextfloat}[2]{%
8242 \setcounter{LWR@nextautopage}{#1}%
8243 \setcounter{LWR@nextautoid}{#2}%
8244 }
```

- Ctr `LWR@latestautopage` Updated each time a new HTML file is begun. `\LWRsetnextfloat` is written with this and the autoid by the modified `\addcontentsline` just before each float's entry.

```
8245 \newcounter{LWR@latestautopage}
8246 \setcounter{LWR@latestautopage}{1}
```

- Env `LWR@figcaption` Encapsulates a caption inside `<figcaption>`, and if FormatWP then also a `<div>` with an italic style.

```
8247 \newenvironment*{LWR@figcaption}
8248 {%
8249 \LWR@traceinfo{LWR@figcaption env start}%
8250 \LWR@htmlblocktag{figcaption}%
8251 \ifbool{FormatWP}{%
8252 \begin{BlockClass}[font-style:italic]{italic}%
8253 \LWR@print@vspace*{\baselineskip}%
8254 }{}%
8255 \LWR@traceinfo{LWR@figcaption env start: done}%
```

```
8256 }  
8257 {  
8258 \LWR@traceinfo{LWR@figcaption env end} %  
8259 \ifbool{FormatWP}{\end{BlockClass}}{} %  
8260 \LWR@htmlblocktag{/figcaption} %  
8261 \LWR@traceinfo{LWR@figcaption env end: done} %  
8262 }
```

```
\LWR@HTML@caption@begin {<type>}
```

Low-level patches to create HTML tags for captions.

```
8263 \newcommand*{\LWR@HTML@caption@begin}[1]  
8264 {  
8265 \LWR@traceinfo{LWR@HTML@caption@begin} %
```

Keep par and minipage changes local:

```
8266 \begingroup%
```

The **caption** code was not allowing the closing par tag:

```
8267 \setpar{\LWR@closeparagraph\@@par} %
```

No need for a minipage or \parbox inside the caption:

```
8268 \RenewDocumentEnvironment{minipage}{O{t} o O{t} m}{}{} %  
8269 \RenewDocumentCommand{\parbox}{O{t} o O{t} m +m}{{##5}} %
```

Enclose the original caption code inside an HTML tag:

```
8270 \LWR@figcaption %  
8271 \LWR@traceinfo{LWR@HTML@caption@begin: about to LWR@origcaption@begin} %  
8272 \LWR@print@caption@begin{#1} %  
8273 \LWR@traceinfo{LWR@HTML@caption@begin: done} %  
8274 }
```

```
\LWR@HTML@caption@end Low-level patches to create HTML tags for captions.
```

```
8275 \newcommand*{\LWR@HTML@caption@end} %  
8276 {} %  
8277 \LWR@traceinfo{LWR@HTML@caption@end} %  
8278 \LWR@print@caption@end %
```

Closing tag:

```
8279 \endLWR@figcaption%
```

```

8280 \endgroup%
8281 % \leavevmode% avoid bad space factor (0) error
8282 \LWR@traceinfo{LWR@HTML@caption@end: done}%
8283 }

```

\caption@begin Low-level patches to create HTML tags for captions. These are assigned \AtBeginDocument so that other packages which modify captions will have already been loaded before saving the print-mode version.

```

8284 \AtBeginDocument{
8285 \LWR@formatted{caption@begin}
8286 \LWR@formatted{caption@end}
8287 }

```

\captionlistentry Tracks the float number for this caption used outside a float. Patched to create an HTML anchor.

```

8288 \let\LWR@origcaptionlistentry\captionlistentry
8289
8290 \renewcommand*{\captionlistentry}{%
8291 \LWR@ensuredoingapar%
8292 \LWR@origcaptionlistentry%
8293 }
8294
8295 \def\LWR@LTcaptionlistentry{%
8296 \LWR@ensuredoingapar%
8297 \LWR@htmltag{a id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}"}\LWR@htmltag{/a}%
8298 \bgroup
8299 \@ifstar{\egroup\LWR@LT@captionlistentry}{%
8300 \egroup\LWR@LT@captionlistentry}%
8301 \def\LWR@LT@captionlistentry#1{%
8302 \caption@listentry@\firstoftwo[\LTcaptype]{#1}}%

```

\addcontentsline Patched to write the autopage and autoid before each float's entry. No changes if writing .toc For a theorem, automatically defines \ext@<type> as needed, to mimic and reuse the float mechanism.

f

```

8303 \let\LWR@origaddcontentsline\addcontentsline
8304
8305 \renewcommand*{\addcontentsline}[3]{%
8306 \ifstreq{\#1}{toc}{}{\not TOC
8307 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}{%
8308 {}%
8309 {\LWR@newautoidanchor}}%

```

```

8310     \ifcsvoid{ext@#2}{\csdef{ext@#2}{#1}}{}%
8311     \addtocontents{\nameuse{ext@#2}}{%
8312         \protect\LWRsetnextfloat{%
8313             \arabic{LWR@latestautopage}}%
8314             \arabic{LWR@thisautoid}}%
8315     }%
8316 }% not TOC
8317 \LWR@origaddcontentsline{#1}{#2}{#3}%
8318 }
```

Pkg `capt-of` Either package provides `\captionof`, which is later patched at the beginning of the document.

`\captionof` Patched to handle paragraph tags.

```

8319 \AtBeginDocument{%
8320 \let\LWR@origcaptionof\captionof
8321
8322 \renewcommand*{\captionof}{%
8323 \LWR@stoppars
8324 \LWR@origcaptionof%
8325 }
8326 }

8327 \end{warpHTML}
```

72 Table of Contents, LOF, LOT

This section controls the generation of the TOC, LOF, and LOT.

The `.toc`, `.lof`, and `.lot` files are named by the source code `\jobname`.

In HTML, the printed tables are placed inside a `<div>` of class `toc`, `lof`, or `lot`.

A “`sitetoc`” is provided which prints a subset of the TOC on the side of each page other than the homepage.

The regular L^AT_EX infrastructure is used for TOC, along with some patches to generate HTML output.

for HTML output: 8328 `\begin{warpHTML}`

72.1 Reading and printing the TOC

```
\LWR@myshorttoc {{<toc/lof/lot/sidetoc>}}
```

Reads in and prints the TOC/LOF/LOT at the current position. While doing so, makes the @ character into a normal letter to allow formatting commands in the section names.

Unlike in regular L^AT_EX, the file is not reset after being read, since the sidetoc may be referred to again in each HTML page.

```
8329 \newcommand*\{\\LWR@myshorttoc}[1]{%
8330 \LWR@traceinfo{LWR@myshorttoc: #1}%
8331 \LWR@ensuredoingapar%
```

Only if the file exists:

```
8332 \IfFileExists{\jobname.\#1}{%
8333 \LWR@traceinfo{LWR@myshorttoc: loading}%

```

 Many of the commands in the file will have @ characters in them, so @ must be made a regular letter.

```
8334 \begingroup%
8335 \makeatletter%
```

Read in the toc file:

```
8336 \@input{\jobname.\#1}%
8337 \endgroup%
8338 }%
8339 {}%
8340 \LWR@traceinfo{LWR@myshorttoc: done}%
8341 }
```

```
\LWR@subtableofcontents {{<toc/lof/lot>}} {{<sectionstarname>}}
```

Places a TOC/LOF/LOT at the current position.

```
8342 \NewDocumentCommand{\LWR@subtableofcontents}{m m}{%
```

Closes previous levels:

```
8343 \@ifundefined{chapter}%
8344 {\LWR@closeprevious{\LWR@depthsection}}%
8345 {\LWR@closeprevious{\LWR@depthchapter}}%
```

Prints any pending footnotes so that they appear above the potentially large TOC:

```
8346 \LWR@printpendingfootnotes
```

Place the list into its own chapter (if defined) or section:

```
8347 \@ifundefined{chapter}{\section*{\#2}}{\chapter*{\#2}}
```

Create a new HTML nav containing the TOC/LOF/LOT:

```
8348 \LWR@htmlelementclass{nav}{\#1}
```

Create the actual list:

```
8349 \LWR@myshorttoc{\#1}
```

Close the nav:

```
8350 \LWR@htmlelementclassend{nav}{\#1}
8351 }
```

\@starttoc {\langle ext \rangle}

Patch \@starttoc to encapsulate the toc inside HTML tags:

```
8352 \let\LWR@orig@starttoc\@starttoc
8353
8354 \renewcommand{\@starttoc}[1]{
8355 \LWR@htmlelementclass{nav}{\#1}
8356 \LWR@orig@starttoc{\#1}
8357 \LWR@htmlelementclassend{nav}{\#1}
8358 }
```

Bool LWR@copiedsidetoc Used to only copy the toc file to the sidetoc a single time.

(**listings** and perhaps other packages would re-use \tableofcontents for their own purposes, causing the sidetoc to be copied more than once, and thus end up empty.)

```
8359 \newbool{LWR@copiedsidetoc}
8360 \boolfalse{LWR@copiedsidetoc}
```

\tableofcontents Patch \tableofcontents, etc. to print footnotes first. **newfloat** uses \listoffigures for all future float types.

```
8361 \AtBeginDocument{
```

```

8362 \let\LWR@origtableofcontents\tableofcontents
8363
8364 \renewcommand*\{tableofcontents}{%

```

Do not print the table of contents if formatting for a word processor, which will presumably auto-generate its own updated table of contents:

```

8365 \ifboolexpr{bool{FormatWP} and bool{WPMarkTOC}}{
8366
8367 === table of contents ===
8368
8369 }
8370 {

```

Copy the .toc file to .sidetoc for printing the sidetoc. The original .toc file is renewed when \tableofcontents is finished.

```

8371 \ifboolexpr{LWR@copiedsidetoc}{}{%
8372     \LWR@copyfile{\jobname.toc}{\jobname.sidetoc}%
8373     \booltrue{LWR@copiedsidetoc}%
8374 }%
8375 \LWR@printpendingfootnotes
8376 \LWR@origtableofcontents
8377 }
8378 }% \tableofcontents
8379 }% AtBeginDocument

```

\listoffigures

```

8380 \let\LWR@origlistoffigures\listoffigures
8381
8382 \renewcommand*\{listoffigures}{%
8383 \ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{
8384
8385 === list of figures ===
8386
8387 }
8388 {
8389     \LWR@printpendingfootnotes
8390     \LWR@origlistoffigures
8391 }
8392 }

```

\listoftables

```

8393 \let\LWR@origlistoftables\listoftables
8394
8395 \renewcommand*\{listoftables}{%

```

```

8396 \ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{
8397
8398 === list of tables ===
8399
8400 }
8401 {
8402     \LWR@printpendingfootnotes
8403     \LWR@origlistoftables
8404 }
8405 }
```

72.2 High-level TOC commands

`\listof {⟨type⟩} {⟨title⟩}`

Emulate the `\listof` command from the **float** package (section 207). Used to create lists of custom float types. Also used to redefine the standard L^AT_EX `\listoffigures` and `\listoftables` commands.

```

8406 \NewDocumentCommand{\listof}{m +m}{%
8407 \Ifundefined{l@#1}{%
8408     \csdef{l@#1}##1##2{\hypertocfloat{1}{#1}{\nameuse{ext@#1}}{##1}{##2}}%
8409 }{}%
8410 \LWR@subtableofcontents{\nameuse{ext@#1}}{#2}
8411 \expandafter\newwrite\csname tf@\csname ext@#1\endcsname\endcsname
8412 \immediate\openout \csname tf@\csname ext@#1\endcsname\endcsname
8413     \jobname.\nameuse{ext@#1}\relax
8414 }
```

72.3 Side TOC

The “side TOC” is a table-of-contents positioned to the side.

It may be renamed by redefining `\sidetocname`, and may contain paragraphs.

`css` may be used to format the sideTOC:

CSS related to sideTOC:

`nav.sidetoc`: The entire sidetoc.
`div.sidetoctitle`: The title.
`div.sidetoccontents`: The table of contents.

```
8415 \end{warpHTML}
```

for HTML & PRINT: 8416 \begin{warpall}

Ctr SideTOCDepth Controls how deep the side-TOC gets. Use a standard L^AT_EX section level similar to tocdepth.

```
8417 \newcounter{SideTOCDepth}
8418 \setcounter{SideTOCDepth}{1}
```

\sidetocname Holds the default name for the sidetoc.

```
8419 \newcommand{\sidetocname}{Contents}
8420 \end{warpall}
```

for HTML output: 8421 \begin{warpHTML}

\LWR@sidetoc Creates the actual side-TOC.

```
8422 \newcommand*{\LWR@sidetoc}{
8423 \LWR@forcenewpage
8424 \LWR@stoppars
8425
```

The entire sidetoc is placed into a nav of class sidetoc.

```
8426 \LWR@htmlelementclass{nav}{sidetoc}
8427
8428 \setcounter{tocdepth}{\value{SideTOCDepth}}
8429
```

The title is placed into a <div> of class sidetoctitle, and may contain paragraphs.

```
8430 \begin{BlockClass}{sidetoctitle}
8431 \sidetocname
8432 \end{BlockClass}
```

The table of contents is placed into a <div> of class sidetoccontents.

```
8433 \begin{BlockClass}{sidetoccontents}
8434 \LinkHome
8435
8436 \LWR@myshorttoc{sidetoc}
8437 \end{BlockClass}
8438 \LWR@htmlelementclassend{nav}{sidetoc}
8439 }
```

72.4 Low-level TOC line formatting

\numberline {⟨number⟩}

(Called from each line in the .aux, .lof files.)

Record this section number for further use:

```
8440 \newcommand*{\LWR@numberline}[1]{%
8441 \LWR@sectionnumber{#1}\quad%
8442 }
8443
8444 \LetLtxMacro\numberline\LWR@numberline
```

\hypertoc {⟨1: depth⟩} {⟨2: type⟩} {⟨3: name⟩} {⟨4: page⟩}

Called by \l@section, etc. to create a hyperlink to a section.

The autopage label is always created just after the section opens.

#1 is depth

#2 is section, subsection, etc.

#3 the text of the caption

#4 page number

```
8445 \NewDocumentCommand{\hypertoc}{m m +m m}{%
8446 \LWR@traceinfo{hypertoc !#1!#2!#3!#4!}}%
```

Respond to tocdepth:

```
8447 \ifthenelse{\cnttest{#1}{<=}{\value{tocdepth}}}{%
8448 \LWR@startpars%
```

Create an HTML link to filename#autosec-(page), with text of the caption, of the given HTML class.

```
8449 \LWR@subhyperrefclass{%
8450 \LWR@htmlrefsectionfilename{autopage-#4}\LWR@origpound\LWR@print@mbox{autosec-#4}%
8451 }{#3}{toc#2}%
8452 \LWR@stoppars%
8453 }%
8454 {}%
8455 \LWR@traceinfo{hypertoc done}%
8456 }
```

Ctr `lofdepth` TOC depth for figures.

```
8457 \@ifclassloaded{memoir}{}{  
8458 \newcounter{lofdepth}  
8459 \setcounter{lofdepth}{1}  
8460 }
```

Ctr `lotdepth` TOC depth for tables.

```
8461 \@ifclassloaded{memoir}{}{  
8462 \newcounter{lotdepth}  
8463 \setcounter{lotdepth}{1}  
8464 }
```

`\hypertocfloat {<1: depth>} {<2: type>} {<3: ext of parent>} {<4: caption>} {<5: page>}`

#1 is depth

#2 is figure, table, etc.

#3 is lof, lot, of the parent.

#4 the text of the caption

#5 page number

```
8465 \newcommand{\hypertocfloat}[5]{%  
8466 \LWR@startpars
```

If some float-creation package has not yet defined the float type's `lofdepth` counter, etc, define it here:

```
8467 \@ifundefined{c@#3depth}{%  
8468 \newcounter{#3depth} %  
8469 \setcounter{#3depth}{1} %  
8470 }{}%
```

Respond to `lofdepth`, etc.:

```
8471 \LWR@traceinfo{hypertocfloat depth is #1 #3depth is \arabic{#3depth}}%  
8472 \ifthenelse{\cnttest{#1}{<=}{\arabic{#3depth}}}{%  
8473 \LWR@startpars%
```

Create an `HTML` link to `filename#autoid-(float number)`, with text of the caption, of the given `HTML` class.

```
8474     \LWR@subhyperrefclass{%
8475     \LWR@htmlrefsectionfilename{autopage-\arabic{LWR@nextautopage}}%
8476     \LWR@origpound\LWR@print@mbox{autoid-\arabic{LWR@nextautoid}}}}%
8477     {#4}{toc#2}%
8478     \LWR@stoppars%
8479 }{}%
8480 }
```

Automatically called by \contentsline:

```
\l@part {\langle name\rangle} {\langle page\rangle}
```

Uses \DeclareDocumentCommand in case the class does not happen to have a \part.

```
8481 \DeclareDocumentCommand{\l@part}{m m}{\hypertoc{-1}{part}{#1}{#2}}
```

```
\l@chapter {\langle name\rangle} {\langle page\rangle}
```

Uses \DeclareDocumentCommand in case the class does not happen to have a \chapter.

```
8482 \DeclareDocumentCommand{\l@chapter}{m m}{%
8483   \hypertoc{0}{chapter}{#1}{#2}}
```

```
\l@section {\langle name\rangle} {\langle page\rangle}
```

```
8484 \renewcommand{\l@section}[2]{\hypertoc{1}{section}{#1}{#2}}
```

```
\l@subsection {\langle name\rangle} {\langle page\rangle}
```

```
8485 \renewcommand{\l@subsection}[2]{\hypertoc{2}{subsection}{#1}{#2}}
```

```
\l@subsubsection {\langle name\rangle} {\langle page\rangle}
```

```
8486 \renewcommand{\l@subsubsection}[2]{\hypertoc{3}{subsubsection}{#1}{#2}}
```

```
\l@paragraph {\langle name\rangle} {\langle page\rangle}
```

```
8487 \renewcommand{\l@paragraph}[2]{\hypertoc{4}{paragraph}{#1}{#2}}
```

```
\l@ subparagraph {\langle name\rangle} {\langle page\rangle}
```

```
8488 \renewcommand{\l@ subparagraph}[2]{\hypertoc{5}{subparagraph}{#1}{#2}}
```

```
\l@figure {\langle name\rangle}{\langle page\rangle}
8489 \renewcommand{\l@figure}[2]{\hypertocfloat{1}{figure}{lof}{#1}{#2}}
\l@table {\langle name\rangle}{\langle page\rangle}
8490 \renewcommand{\l@table}[2]{\hypertocfloat{1}{table}{lot}{#1}{#2}}
8491 \end{warpHTML}
```

73 Index and glossary

See:

[http://tex.stackexchange.com/questions/187038/
how-to-mention-section-number-in-index-created-by-imakeidx](http://tex.stackexchange.com/questions/187038/how-to-mention-section-number-in-index-created-by-imakeidx)

Index links are tracked by the counter LWR@autoindex. This counter is used to create a label for each index entry, and a reference to this label for each entry in the index listing. This method allows each index entry to link directly to its exact position in the document.

for HTML output: 8492 \begin{warpHTML}

```
8493 \newcounter{LWR@autoindex}
8494 \setcounter{LWR@autoindex}{0}
8495
8496 \newcounter{LWR@autoglossary}
8497 \setcounter{LWR@autoglossary}{0}
```

Env theindex

```
8498 \@ifundefined{chapter}
8499 {\newcommand*{\LWR@indexsection}[1]{\section*{#1}}}
8500 {\newcommand*{\LWR@indexsection}[1]{\chapter*{#1}}}
8501
8502 \AtBeginDocument{
8503 \renewenvironment*{\theindex}{%
8504     \LWR@indexsection{\indexname}%
8505     \let\item\LWR@indexitem%
8506     \let\subitem\LWR@indexsubitem%
8507     \let\subsubitem\LWR@indexsubsubitem%
8508 }{}%
8509 }% AtBeginDocument
```

\LWR@indexitem [*index key*] The optional argument is added to support **repeatindex**.

```

8510 \newcommand{\LWR@indexitem}[1][\emptyset]{
8511
8512 \InlineClass{indexitem}{}#1%
8513 }
```

\LWR@indexsubitem

```

8514 \newcommand{\LWR@indexsubitem} {
8515
8516 \InlineClass{indexsubitem}{}%
8517 }
```

\LWR@indexsubsubitem

```

8518 \newcommand{\LWR@indexsubsubitem} {
8519
8520 \InlineClass{indexsubsubitem}{}%
8521 }
```

\@wrindex {*term*} Redefined to write the LWR@autoindex counter instead of page.

```

8522 \def\LWR@wrindex#1{%
8523 \addtocounter{LWR@autoindex}{1}%
8524 \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
8525 \protected@write\@indexfile{()}%
8526 {\string\indexentry{#1}{\arabic{LWR@autoindex}}}%
8527 \endgroup
8528 \esphack}
8529
8530 \AtBeginDocument{
8531 \let\@wrindex\LWR@wrindex
8532 }
```

\@wrglossary {*term*} Redefined to write the LWR@latestautopage counter instead of page.

```

8533 \def\@wrglossary#1{%
8534 \addtocounter{LWR@autoglossary}{1}%
8535 \LWR@new@label{LWRglossary-\theLWR@autoglossary}}%
8536 \protected@write\@glossaryfile{()}%
8537 {\string\glossaryentry{#1}{\theLWR@autoglossary}}%
8538 \endgroup
8539 \esphack}
```

\LWR@indexnameref {*LWR@autoindex*}

Creates a hyperlink based on the given entry's autoindex.

```
8540 \newcommand*{\LWR@indexnameref}[1]{\nameref{LWRindex-\#1}}
```

\LWR@doindexentry {*LWR@autoindex, or macros.*}

Creates a hyperlink, or handles \see, \textbf{etc}.

```
8541 \newrobustcmd{\LWR@doindexentry}[1]{%
8542 \IfInteger{#1}{%
8543   {\LWR@indexnameref{#1}}{%
8544     {#1}}{%
8545 }}
```

\LWR@hyperindexrefnullified Handles macros commonly seen inside an \index entry.

To handle additional macros:

```
\appto{\LWR@hyperindexrefnullified}{...}
```

```
8546 \newcommand{\LWR@hyperindexrefnullified}{%
8547 \renewrobustcmd{\emph}[1]{\LWR@HTMLemph{\LWR@doindexentry{\#1}}}{%
8548 \renewrobustcmd{\textbf}[1]{\LWR@HTMLtextbf{\LWR@doindexentry{\#1}}}{%
8549 \renewrobustcmd{\textrm}[1]{\LWR@HTMLtextrm{\LWR@doindexentry{\#1}}}{%
8550 \renewrobustcmd{\textsf}[1]{\LWR@HTMLtextsf{\LWR@doindexentry{\#1}}}{%
8551 \renewrobustcmd{\texttt}[1]{\LWR@HTMLtexttt{\LWR@doindexentry{\#1}}}{%
8552 \renewrobustcmd{\textup}[1]{\LWR@HTMLtextup{\LWR@doindexentry{\#1}}}{%
8553 \renewrobustcmd{\textsc}[1]{\LWR@HTMLtextsc{\LWR@doindexentry{\#1}}}{%
8554 \renewrobustcmd{\textit}[1]{\LWR@HTMLtextit{\LWR@doindexentry{\#1}}}{%
8555 \renewrobustcmd{\textsl}[1]{\LWR@HTMLtextsl{\LWR@doindexentry{\#1}}}{%
8556 }
```

\hyperindexref {*LWR@autoindex*}

\hyperindexref{\LWR@autoindex} is inserted into *.ind by the **makeindex** style file lwarf.ist or the **xindy** style file lwarf.xdy.

```
8557 \newcommand{\hyperindexref}[1]{%
8558 \IfInteger{#1}{%
8559   {\LWR@indexnameref{#1}}{%
8560     {%
8561       \begingroup{%
8562         \LWR@hyperindexrefnullified{%
8563           #1{%
8564             \endgroup{%
8565           }{%
8566 }}
```

```
8567 \end{warpHTML}
```

for PRINT output: A null command for print mode, in case **hyperref** was not used:

```
8568 \begin{warpprint}
8569 \newcommand{\hyperindexref}[1]{#1}
8570 \end{warpprint}
```

for HTML & PRINT: For the **glossaries** package, try to prevent an error where `\glo@name` was not found:

```
8571 \begin{warpall}
8572 \providecommand{\glo@name}{}
8573 \end{warpall}
```

74 Bibliography presentation

for HTML output: 8574 `\begin{warpHTML}`

```
\bibliography {\langle filenames\rangle}
```

Modified to use the base jobname instead of the `_html` jobname.

```
8575 \def\bibliography#1{%
8576   \if@filesw
8577     \immediate\write\@auxout{\string\bibdata{\#1}}%
8578   \fi
8579 %     \ @input{\jobname.bbl}%
8580   \begingroup%
8581     \ @input{\BaseJobname.bbl}%
8582   \endgroup%
8583 }
```

```
\@biblabel {\langle text-refnumber\rangle}
```

```
8584 \renewcommand{\@biblabel}[1]{[#1]\quad}
```

Env thebibliography To emphasize document titles in the bibliography, the following redefines `\em` inside `thebibliography` to gather everything until the next closing brace, then display these tokens with `\textit`.

Adapted from `embracedef.sty`, which is by TAKAYUKI YATO:

<https://gist.github.com/zr-tex8r/b72555e3e7ad2f0a37f1>

```

8585 \AtBeginDocument{
8586 \AtBeginEnvironment{thebibliography}{
8587 \providecommand*\LWR@newem}[1]{\textit{\#1}}
8588
8589 \renewrobustcmd{\em}{%
8590   \begingroup
8591     \gdef\LWR@em@after{\LWR@em@finish\LWR@newem}%
8592     \afterassignment\LWR@em@after
8593     \toks@\bgroup
8594 }
8595
8596 \def\LWR@em@finish#1{%
8597   \xdef\LWR@em@after{\noexpand#1{\the\toks@}}%
8598 }
8599 \endgroup
8600 \LWR@em@after\egroup
8601 }% \AtBeginEnvironment{thebibliography}
8602 }% \AtBeginDocument

8603 \end{warpHTML}

```

75 Restoring original formatting

\LWR@restoreorigformatting Used to temporarily restore the print-mode meaning of a number of formatting, graphics, and symbols-related macros while generating SVG math or a `lateximage`.

Must be used inside a group.

Sets `\LWR@formatting` to print until the end of the group.

A number of packages will `\appto` additional actions to this macro.

Various packages add to this macro using `\appto`.

for HTML output: 8604 \begin{warpHTML}

```

8605 \newcommand*\LWR@restoreorigformatting{}%
8606 \LWR@traceinfo{\LWR@restoreorigformatting}%

```

Numerous macros change their print/HTML meaning depending on `\LWR@formatting`:

```

8607 \renewcommand*\LWR@formatting[1]{\print}%
8608 \linespread{1}%
8609 \let\par\LWR@origpar%

```

```
8610 \LWR@select@print@hskip%
```

```
8611 \LetLtxMacro\hfil\LWR@orighfil%
8612 \let\hss\LWR@orighss%
8613 \let\llap\LWR@origllap%
8614 \let\rlap\LWR@origrlap%
8615 \let\hfilneg\LWR@orighfilneg%
```

```
8616 \let\,\LWR@origcomma% disable HTML short unbreakable space
8617 \let\thinspace\LWR@origthinspace% disable HTML short unbreakable space
8618 \let\negthinspace\LWR@orignegthinspace% disable HTML negative short unbreakable space
8619 \let\textellipsis\LWR@origtextellipsis%
8620 \let\textless\LWR@origtextless%
8621 \let\textgreater\LWR@origtextgreater%
8622 \LetLtxMacro\textrm\LWR@origtextrm%
8623 \LetLtxMacro\textsf\LWR@origtextsf%
8624 \LetLtxMacro\texttt\LWR@origtexttt%
8625 \LetLtxMacro\textbf\LWR@origtextbf%
8626 \LetLtxMacro\textmd\LWR@origtextmd%
8627 \LetLtxMacro\textit\LWR@origtextit%
8628 \LetLtxMacro\textsl\LWR@origtextsl%
8629 \LetLtxMacro\textsc\LWR@origtextsc%
8630 \LetLtxMacro\textup\LWR@origtextup%
8631 \LetLtxMacro\textnormal\LWR@origtextnormal%
8632 \LetLtxMacro\emph\LWR@origemph%
8633 \LetLtxMacro\rmfamily\LWR@origrmfamily%
8634 \LetLtxMacro\sffamily\LWR@origsffamily%
8635 \LetLtxMacro\ttfamily\LWR@origttfamily%
8636 \LetLtxMacro\bfseries\LWR@origbfseries%
8637 \LetLtxMacro\mdseries\LWR@origmdseries%
8638 \LetLtxMacro\upshape\LWR@origupshape%
8639 \LetLtxMacro\slshape\LWR@origslshape%
8640 \LetLtxMacro\scshape\LWR@origscshape%
8641 \LetLtxMacro\itshape\LWR@origitshape%
8642 \LetLtxMacro\em\LWR@origem%
8643 \LetLtxMacro\normalfont\LWR@orignormalfont%
8644 \let\sp\LWR@origsp%
8645 \let\sb\LWR@origsb%
8646 \LetLtxMacro\textsuperscript\LWR@origtextsuptscript%
8647 \LetLtxMacro\@textsuperscript\LWR@orig@textsuperscript%
8648 \LetLtxMacro\textsubscript\LWR@origtextsubscript%
8649 \LetLtxMacro\@textsubscript\LWR@orig@textsubscript%
8650 \LetLtxMacro\underline\LWR@origunderline%
8651 \let~\LWR@origtilde%
8652 \let\enskip\LWR@origenskip%
8653 \let\quad\LWR@origquad%
8654 \let\qquad\LWR@origqquad%
8655 \LetLtxMacro\tabular\LWR@origtabular%
8656 \LetLtxMacro\endtabular\LWR@origendtabular%
```

```

8657 \LetLtxMacro\noalign{\LWR@orignoalign}%
8658 \LetLtxMacro\hline{\LWR@orighline}%
8659 \let\newline{\LWR@orignewline}%
8660 \LetLtxMacro\includegraphics{\LWR@origincludegraphics}%
8661 \let\TeX{\LWR@origTeX}%
8662 \let\LaTeX{\LWR@origLaTeX}%
8663 \let\LaTeXe{\LWR@origLaTeXe}%
8664 \renewcommand*{\Xe}[X\textsubscript{E}]{}%


8665 \LetLtxMacro{@ensuredmath}{\LWR@origensuredmath}%
8666 %
8667 \LWR@restoreorigaccents%
8668 \LWR@restoreoriglists%
8669 %
8670 \LWR@FBcancel%
8671 }

8672 \end{warpHTML}

```

76 Math

76.1 Limitations

76.1.1 Rendering tradeoffs

Math rendering Math may be rendered as SVG graphics or using the MATHJAX JavaScript display engine.

SVG files Rendering math as images creates a new SVG file for each expression, except that an MD5 hash is used to combine identical duplicates of the same inline math expression into a single file, which must be converted to SVG only once. Display math is still handled as individual files, since it may contain labels or references which are likely to change.

SVG inline The SVG images are currently stored separately, but they could be encoded in-line directly into the HTML document. This may reduce the number of files and potentially speed loading the images, but slows the display of the rest of the document before the images are loaded.

PNG files Others L^AT_EX-to-HTML converters have used PNG files, sometimes pre-scaled for print resolution but displayed on-screen at a scaled down size. This allows high-quality print output at the expense of larger files, but SVG files are the preferred approach for scalable graphics.

MathML Conversion to MathML might be a better approach, among other things allowing a more compact representation of math than SVG drawings. Problems with MathML include limited browser support and some issues with the fine control of the appearance of the result. Also see section 11 regarding EPUB output with MATHJAX.

76.1.2 SVG option

SVG math option For SVG math, math is rendered as usual by L^AT_EX into the initial PDF file using the current font¹⁸, then is captured from the PDF and converted to SVG graphics via a number of utility programs. The SVG format is a scalable-vector web format, so math may be typeset by L^AT_EX with its fine control and precision, then displayed or printed at any size, depending on (sometimes broken) browser support. An HTML alt attribute carries the L^AT_EX code which generated the math, allowing copy/paste of the L^AT_EX math expression into other documents.

SVG image font size For the `lateximage` environment, the size of the math and text used in the SVG image may be adjusted by setting `\LateximageFontSizeName` to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{\normalsize}
```

For inline SVG math, font size is instead controlled by `\LateximageFontSizeScale`, which defaults to:

```
\newcommand*{\LateximageFontSizeScale}{.75}
```

SVG math copy/paste For SVG math, text copy/paste from the HTML `<alt>` tags lists the equation number or tag for single equations, along with the L^AT_EX code for the math expression. For *AMS* environments with multiple numbers in the same environment, only the first and last is copy/pasted, as a range. No tags are listed inside a starred *AMS* environment, although the `\tag` macro will still appear inside the L^AT_EX math expression.

⚠ SVG math in T_EX boxes SVG math does not work inside T_EX boxes, since a `\newpage` is required before and after each image.

76.1.3 MATHJAX option

MATHJAX math option The popular MATHJAX alternative (mathjax.org) may be used to display math.

Prog MathJax

When MATHJAX is enabled, math is rendered twice:

¹⁸See section 429 regarding fonts and fractions.

1. As regular \TeX PDF output placed inside an HTML comment, allowing equation numbering and cross referencing to be almost entirely under the control of \TeX , and
2. As detokenized printed \TeX commands placed directly into the HTML output for interpretation by the MATHJAX display scripts. An additional script is used to pre-set the equation number format and value according to the current \TeX values, and the MATHJAX cross-referencing system is ignored in favor of the \TeX internal system, seamlessly integrating with the rest of the \TeX code.

76.1.4 Customizing MATHJAX

MATHJAX does not have preexisting support every possible math function. Additional MATHJAX function definitions may be defined. These will be declared at the start of each HTML page, and thus will have a global effect.

Examples:

```
\CustomizeMathJax{
    \newcommand{\expval}[1]{\langle#1\rangle}
    \newcommand{\abs}[1]{\lvert#1\rvert}
}

\CustomizeMathJax{\newcommand{\arsinh}{\text{arsinh}}}
\CustomizeMathJax{\newcommand{\arcosh}{\text{arcosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
```

76.1.5 MATHJAX limitations

[MATHJAX limitations](#)

Limitations when using MATHJAX include:

Prog MathJax

[subequations](#)

- MATHJAX itself does not support subequations. This may be improved by parsing the \TeX math expression to manually insert tags, but this has not yet been done.

[footnotes in math](#)

- Footnotes inside equations are not yet supported while using MATHJAX.

[lateximage](#)

- Math appearing inside a lateximage, and therefore also inside a Tikz or picture environment, is rendered as SVG math even if MATHJAX is used in the rest of the document.

[siunitx](#)

- Usage of **siunitx** inside a math equation is supported via a third-party MATHJAX extension. While inside a math expression, do not use `\SI` or `\si` inside `\text`, where it will be rendered as normal text.

<https://github.com/burnpanck/MathJax-siunitx>

Also see section [9.6.12](#).

 [siunitx inside an equation](#)

- tabbing**
- A tabbing environment is emulated using an HTML `<pre>`. While MATHJAX is enabled inside tabbing, the browser may not correctly render the horizontal alignment of the math and text following after on the same line.
- ⚠ other macros and packages**
- Other math-related macros and packages are not supported by MATHJAX, including `\ensuremath` and `bigdelim`, along with occasionally-used macros such as `\relax`. **l warp** emulates footnotes, `units`, and `nicefrac` for MathJAX.

76.1.6 Catcode changes

preamble macros with math

The math shift character `$` is not set for HTML output until after the preamble. Macros defined in the preamble which contain `$` must be enclosed between `\StartDefiningMath` and `\StopDefiningMath` to temporarily change to the HTML meaning of `$`:

```
\StartDefiningMath
\newcommand{...}
\StopDefiningMath
```

As an alternative, use `\(` and `\)` instead of `$`, in which case `\StartDefiningMath` and `\StopDefiningMath` are not necessary.

If a package defines macros using `$`, it may be necessary to use `\StartDefiningMath` and `\StopDefiningMath` before and after loading the package.

76.1.7 Complicated inline math objects

`\inlinemathnormal`
`\inlinemathother`

An inline math expression is usually converted to a reusable hashed SVG math image, or a MathJAX expression. The hash or expression depends on the contents of the math expression. In most cases this math expression is static, such as `$x+1$`, so the image can be reused for multiple instances of the same expression. In some cases, the math expression includes a counter or other object which may change between uses. Another problem is complicated contents which do not expand well in an `alt` tag. The macro `\inlinemathother` may be used before a dynamic math expression, and `\inlinemathnormal` after. Doing so tells **l warp** to use an unhashed SVG math image, even if MathJAX is in use. See section 42.

changing contents
complicated alt tag

76.1.8 Complicated display math objects

`\displaymathnormal`

By default, or when selecting `\displaymathnormal`, MATHJAX math display environments print their contents as text into HTML, and SVG display math environments render their contents as SVG images and use their contents as the `alt` tag of HTML

output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Tikz pictures, compilation will fail.

\displaymathother MathJax unsupported complicated alt tag	When selecting <code>\displaymathother</code> , it is assumed that the contents are more complicated than “pure” math. An example is an elaborate Tikz picture, which will not render in MATHJAX and will not make sense as an HTML alt tag. In this mode, MATHJAX is turned off, math display environments become SVG images, even if MATHJAX is selected, and the HTML alt tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Tikz pictures are more likely to compile successfully.
--	--

76.2 HTML alt tag names

Redefinable names for the HTML alt tags, for translation according to the reader’s native language.

for HTML & PRINT: 8673 `\begin{warpall}`

`\mathimagename` The HTML alt tag for an SVG math image.
 Default: "math image"

8674 `\newcommand*{\mathimagename}{math image}`

`\packagediagramname` Appended to the `lateximage` HTML alt tag for the images generated by many packages.
 Default: "diagram"

8675 `\newcommand*{\packagediagramname}{diagram}`

8676 `\end{warpall}`

76.3 Inline and display math

for HTML output: 8677 `\begin{warpHTML}`

`ctr LWR@externalfilecnt` Counter for the external files which are generated and then referenced from the HTML:

8678 `\newcounter{LWR@externalfilecnt}`

`Bool LWR@indisplaymathimage` True if processing display math for SVG output. Inside a `lateximage`, display math is only set to print-mode output if `LWR@indisplaymathimage` is false. Used to avoid nullifying display math before it has been completed.

```
8679 \newbool{LWR@indisplaymathimage}
```

- \\$ Plain dollar signs appearing in the HTML output may be interpreted by MATHJAX to be math shifts. For a plain text dollar \\$, use an HTML entity to avoid it being interpreted by MATHJAX, unless are inside a `lateximage`, in which case it will not be seen by MATHJAX.

```
8680 \let\LWR@origtextdollar\$
8681
8682 \renewcommand*{\$}{%
8683 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}{%
8684 {\LWR@origtextdollar}%
8685 {\HTMLentity{dollar}}%
8686 }}
```

- File `l warp_baseline_marker.png` A marker to be used to help `pdfcrop` identify the inline math baseline and width. If either `graphicx` or `graphics` is loaded, this marker is placed at the lower left and lower right corners of the inline math. `pdfcrop` is then able to identify the width of the image, and also the height of an image such as a horizontal dash which does not otherwise touch the baseline.
- File `l warp_baseline_marker.eps`

A marker with alpha or opacity of 0% is not registered by `pdfcrop`, so the marker is a small square block of 1% alpha, which seems to work while still being effectively invisible in the final SVG image.

If `graphicx` is loaded, this marker is sized as a tiny 1 sp square. If `graphics` is loaded, this marker is used at its default size of around .25 pt. If neither `graphics` package is loaded, the marker is replaced by a 10 sp horizontal space, and there is no assistance for determining baseline or width of the inline math image. The best results are obtained when using `graphicx`.

- `\LWR@addbaselinemarker` Places a small marker in an SVG inline image. If `graphics` or `graphicx` are loaded, the marker is a mostly transparent image. If neither is loaded, no marker is used.

```
8687 \AtBeginDocument{
8688
8689 \ifpdf
8690   \newcommand*{\LWR@baselinename}{l warp_baseline_marker.png}
8691 \else
8692   \ifXeTeX
8693     \newcommand*{\LWR@baselinename}{l warp_baseline_marker.png}
8694   \else
8695     \newcommand*{\LWR@baselinename}{l warp_baseline_marker.eps}
8696   \fi
8697 \fi
8698
8699 \IfFileExists{\LWR@baselinename}{%
8700 {}}
```

```

8701     \@ifpackageloaded{graphicx}{
8702         \newcommand*\lWR@addbaselinemarker{%
8703             \lWR@originincludegraphics{\lWR@baselinename}%
8704         }
8705     }{
8706         \@ifpackageloaded{graphics}{
8707             \newcommand*\lWR@addbaselinemarker{%
8708                 \lWR@originincludegraphics{\lWR@baselinename}%
8709             }
8710         }{
8711             \PackageWarning{l warp}{Load graphicx or graphics
8712             for improved SVG math baselines,}
8713             \newcommand*\lWR@addbaselinemarker(){}
8714         }
8715     }
8716 }% l warp_baseline_marker.png or .eps is not present
8717     \PackageWarning{l warp}{File \lWR@baselinename\space is not installed alongside
8718         the l warp-*.sty files, so SVG math baselines may not be accurate,}
8719     \newcommand*\lWR@addbaselinemarker(){}
8720 }
8721
8722 }% AtBeginDocument

```

\lWR@singledollar * {\langle 2: alt text\rangle} {\langle 3: add'l hashing\rangle} {\langle 4: math expression\rangle}

For inline math. Uses MathJax, or for SVG math the image is measured and adjusted to the baseline of the HTML output, and placed inside a `lateximage`.

image filename hashing If starred, a hashed filename is used. If so, the hash is based on the alt tag and also the additional hashing argument.

This may be used to provide an expression with a simple alt tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated TeX expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is duplicated in the additional hashing argument.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing argument in order to make the hash unique according to the set of options, even if the simple alt tag is still the same.

```

8723 \newlength{\lWR@singledollarwidth}
8724 \newlength{\lWR@singledollarheight}
8725 \newlength{\lWR@singledollardepth}
8726
8727 \newsavebox{\lWR@singledollarbox}
8728

```

```

8729 \NewDocumentCommand{\LWR@subsingle dollar}{s m m m}{%
8730 \LWR@traceinfo{LWR@subsingle dollar}%
8731 \ifnumcomp{\value{LWR@lateximage depth}}{>}{0}%
8732 {%
8733 \LWR@traceinfo{LWR@subsingle dollar: already in a lateximage}%
8734     #4% contents
8735 }%
8736 {%
8737 \begingroup%

```

MathJax cannot parse the often complicated TeX expressions which appear in the various uses of `\ensuredmath`. `\ensuremath` forces the alt tag to “(math image)”, as translated according to `\mathimagename`. If this is the case, force the use of a `lateximage` even if MathJax. Likewise for `siunitx` if `parse-numbers=false`.

If MathJax, or if formatting math for a word processor, and not `\ensuredmath`, and not a dynamic math expression, print the math expression:

```

8738 \ifboolexpr{%
8739     (
8740         bool{mathjax} or
8741         ( bool{FormatWP} and bool{WPMarkMath} )
8742     ) and
8743     ( not test { \ifstrelational{#2}{(\mathimagename)} } ) and % from \ensuredmath
8744     ( not bool{LWR@dynamicmath} )
8745 }%

```

For MATHJAX, print the math between `\(` and `\)`:

```

8746 {%
8747     \LWR@traceinfo{LWR@subsingle dollar: Mathjax}%
8748     {\textbackslash(\textbackslashLWR@HTMLsanitize{#4}\textbackslash)}%
8749 }% mathjax

```

For SVG, print the math inside a `lateximage`, with an `<alt>` tag of the TeX code, and a css style to control the baseline adjustment.

```

8750 {%
8751 \LWR@traceinfo{LWR@subsingle dollar: NOT mathjax, or is ensuremath, or is dynamic}%

```

Measure the depth, width, and height of the math image:

```

8752 \begingroup%

```

Temporarily disable formatting while measuring the image parameters:

```

8753 \LWR@restoreorigformatting%

```

```
8754 \RenewDocumentEnvironment{lateximage}{s o o}{}{}% inside group
8755 \LWR@print@normalsize%
```

Temporarily set font for the HTML PDF output:

```
8756 \LWR@traceinfo{Using font family \LWR@f@family}%
8757 \cnameuse{\LWR@orig\LWR@f@family family}%
8758 \LWR@traceinfo{Using font series \LWR@f@series}%
8759 \cnameuse{\LWR@orig\LWR@f@series series}%
8760 \LWR@traceinfo{Using font shape \LWR@f@shape}%
8761 \cnameuse{\LWR@orig\LWR@f@shape shape}%
```

`lateximagedepth` must be nested to avoid generating paragraph tags. *AMS* math modifies the `\text` macro such that `\addtocounter` does not always occur as expected. Lower-level code is used instead.

```
8762 \global\advance\c@LWR@lateximagedepth 1\relax%
```

Typeset and save the contents, depending on how they were generated:

SVG math: `\LWR@origensuredmath` is part of argument #4.

SVG math \ensuremath: `\LWR@origensuredmath` is part of argument #4.

SVG dynamic math: `\LWR@origensuredmath` is part of argument #4.

Mathjax: Argument #4 is the contents of the math expression without `\LWR@origensuredmath`.
This case is handled above.

Mathjax \ensuremath: `\LWR@origensuredmath` is part of argument #4.

Mathjax dynamic math: Argument #4 is the contents of the math expression without `\LWR@origensuredmath`, so `\LWR@origensuredmath` is added below.

\ifmmode: Included “just in case”.

```
8763 \ifmmode%
8764   \global\sbox{\LWR@singledollarbox}{#4}%
8765 \else%
8766   \ifbool{\LWR@dynamicmath}{}{%
8767     \ifbool{\mathjax}{}{%
8768       \global\sbox{\LWR@singledollarbox}{\LWR@origensuredmath{#4}}%
8769     }{%
8770       \global\sbox{\LWR@singledollarbox}{#4}%
8771     }%
8772   }{%
8773     \global\sbox{\LWR@singledollarbox}{#4}%
8774   }%
8775 }\fi%
```

Add a small and almost transparent marker at the depth of the image.

A math minus sign has the same depth as a plus, even though it does not draw anything below the baseline. This means that **pdfcrop** would crop the image without depth. The marker below the baseline is seen by **pdfcrop** and preserves the depth.

```
8776 \global\sbox{\LWR@singledollarbox}{%
8777   \usebox{\LWR@singledollarbox}%
8778   \raisebox{-\dp\LWR@singledollarbox}{%
8779     \LWR@addbaselinemarker}%
8780   }%
8781 }
```

More low-level code to undo the counter change.

```
8782 \global\advance\c@LWR@lateximagedepth -1\relax% Due to AmS \text macro.
```

Measure the depth:

```
8783 \setlength{\LWR@singledollardepth}{%
8784   \LateximageFontScale\dp\LWR@singledollarbox}%
8785 }
```

Make the length a global change:

```
8786 \global\LWR@singledollardepth=\LWR@singledollardepth%
```

Likewise for width:

```
8787 \setlength{\LWR@singledollarwidth}{%
8788   \LateximageFontScale\wd\LWR@singledollarbox}%
8789 }%
8790 \global\LWR@singledollarwidth=\LWR@singledollarwidth%
```

Likewise for total height:

```
8791 \setlength{\LWR@singledollarheight}{%
8792   \LateximageFontScale\ht\LWR@singledollarbox}%
8793 }%
8794 \addtolength{\LWR@singledollarheight}{%
8795   \LateximageFontScale\dp\LWR@singledollarbox}%
8796 }%
8797 \global\LWR@singledollarheight=\LWR@singledollarheight%
8798 }
```

Set a style for the the height or width. The **em** unit is used so that the math scales according to the user's selected font size.

Start with the greater of the width or the height, biased towards the width:

```

8799      \ifdimgreater{\LWR@singledollarwidth}{.7\LWR@singledollarheight}{%
8800          \def\LWR@singledollarstyle{%
8801              width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
8802          }%
8803      }{%
8804          \def\LWR@singledollarstyle{%
8805              height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
8806          }%
8807      }%

```

If a very narrow width, use the height.

```

8808      \ifdimless{\LWR@singledollarwidth}{.2em}{%
8809      }{%
8810          \def\LWR@singledollarstyle{%
8811              height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
8812          }%
8813      }%
8814      }%

```

If very wide and short, use the width:

```

8815      \ifdimless{\LWR@singledollarheight}{.2em}{%
8816      }{%
8817          \def\LWR@singledollarstyle{%
8818              width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
8819          }%
8820      }%
8821      }%

```

If there is significant text depth, add the depth to the style.

```

8822      \ifdimgreater{\LWR@singledollardepth}{0.05ex}{%
8823          \def\LWR@singledollardepthstyle{%
8824              \ ; % extra space
8825              \LWR@print@mbox{%
8826                  vertical-align:-\LWR@convertto{em}{\the\LWR@singledollardepth} em%
8827              } % extra space
8828          }%
8829      }{%
8830          \def\LWR@singledollardepthstyle{}%
8831      }%

```

Create the `lateximage` using the alternate tag and the computed size and depth. The star causes `lateximage` to use an MD5 hash as the filename. When hashing, also include the current font and color in the hash.

```

8832      \ifbool{LWR@dynamicmath}{%
8833          \LWR@traceinfo{subsingle$}: dynamic}%
8834          \begin{lateximage}% no hashing
8835              [(\mathimagername)]% alt tag
8836              []% no add'l hashing
8837              [\LWR@singledollarstyle \LWR@singledollardepthstyle]%
8838      }% CSS
8839      \LWR@traceinfo{subsingle$}: static}%
8840      \IfValueTF{#1}{%
8841          \LWR@findcurrenttextcolor% sets \LWR@tempcolor
8842          \begin{lateximage}*% use hashing
8843              [#2]%
8844              [% addl' hashing
8845                  #3%
8846                  FM\LWR@f@family%
8847                  SR\LWR@f@series%
8848                  SH\LWR@f@shape%
8849                  CL\LWR@tempcolor%
8850              ]%
8851              [\LWR@singledollarstyle \LWR@singledollardepthstyle]%
8852      }% CSS
8853      \begin{lateximage}% no hashing
8854          [#2]%
8855          []% no add'l hashing
8856          [\LWR@singledollarstyle \LWR@singledollardepthstyle]%
8857      }%
8858  }%

```

Place small and almost transparent markers on the baseline at the left and right edges of the image. These markers are seen by **pdffcrop**, and force vertically-centered objects such as a dash to be raised off the baseline in the cropped image, and also force the total width and left/right margins to be correct. (Except that in some fonts a character may exceed the bounding box, and thus may appear wider than expected when converted to an image.)

```
8859      \LWR@addbaselinemarker%
```

Typeset the contents:

```
8860      \usebox{\LWR@singledollarbox}%
```

The closing baseline marker:

```

8861      \LWR@addbaselinemarker%
8862      \end{lateximage}%
8863 %
8864 }% not mathjax

```

```

8865 \endgroup%
8866 }% not in a lateximage
8867 \LWR@traceinfo{LWR@subsingledollar: done}%
8868 }

8869 \LetLtxMacro{\LWR@origdollar$}
8870 \LetLtxMacro{\LWR@secondorigdollar$}{% balance for editor syntax highlighting

8871 \LetLtxMacro{\LWR@origopenparen\(
8872 \LetLtxMacro{\LWR@origcloseparen\)
8873 \LetLtxMacro{\LWR@origopenbracket\[}
8874 \LetLtxMacro{\LWR@origclosebracket\]}

```

\$ Redefine the dollar sign to place math inside a `lateximage`, or use MATHJAX:
\$\$

```

8875 \begingroup
8876 \catcode`$=\active%
8877 \protected\gdef${\@ifnextchar$\LWR@doubledollar$\LWR@singledollar}%

```

Used by **chemformula** to escape single-dollar math:

```
8878 \protected\gdef\LWR@newsingledollar{\@ifnextchar$\LWR@doubledollar$\LWR@singledollar}%
```

\LWR@doubledollar Redefine the double dollar sign to place math inside a `lateximage`, or use MATHJAX:

```
8879 \protected\gdef\LWR@doubledollar${\#1\$}{%
```

If MATHJAX or formatting for a word processor, print the \TeX expression:

```
8880 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }{%
```

For MATHJAX, print the math between `\[` and `\]`:

```

8881 {
8882
8883     \textbackslash[%
8884     \LWR@HTMLsanitize{\#1}%
8885     \textbackslash]
8886
8887 }% mathjax

```

For SVG, print the math inside a `lateximage`, with an `<alt>` tag of the \TeX code:

```

8888 {%
8889     not mathjax
8890     \begin{BlockClass}{displaymath}%
8891     \LWR@newautoidanchor%
8892     \booltrue{LWR@indisplaymathimage}%

```

```

8892     \begin{lateximage}%
8893     [%
8894         \textbackslash{} % extra space
8895         \LWR@HTMLsanitize{\#1} % extra space
8896         \textbackslash{} ]%%
8897     ]%
8898     \LWR@origdollar\textbackslash{} \LWR@origdollar\#1\textbackslash{} \LWR@origdollar\textbackslash{} \LWR@origdollar%
8899     \end{lateximage}%
8900     \end{BlockClass}%
8901 }% not mathjax
8902 }%


\LWR@singledollar {<alt text>} {<math expression>}

8903 \protected\gdef\textbackslash{} \LWR@singledollar{\%
8904 \ifbool{mathjax}{%
8905     \LWR@subsingledollar*%
8906     {%
8907         \textbackslash{} alt tag
8908         \textbackslash{} \textbackslash{} %
8909         \LWR@HTMLsanitize{\#1} % extra space
8910         \textbackslash{} %
8911         \singledollar% add'l hashing
8912         {\#1}% contents
8913 }% not mathjax
8914     \LWR@subsingledollar*%
8915     {%
8916         \textbackslash{} alt tag
8917         \textbackslash{} \textbackslash{} %
8918         \LWR@HTMLsanitize{\#1} % extra space
8919         \textbackslash{} %
8920         \singledollar% add'l hashing
8921         {\textbackslash{} \LWR@origensuredmath{\#1}}% contents
8922 }% not mathjax
8923 }
8924 \AtBeginDocument{
8925 \protected\gdef\textbackslash{} (#1){\$#1\$}
8926 \protected\gdef\textbackslash{} [#1]{\$\$#1\$\$}
8927 }
8928
8929 \endgroup

8930 \AtBeginDocument{
8931 \LetLtxMacro\textbackslash{} \LWR@openbracketnormal\[
8932 \LetLtxMacro\textbackslash{} \LWR@closebracketnormal\]

```

```
8933 }
```

```
\@ensuredmath {⟨expression⟩}
```

If MathJax, a `lateximage` is used, since `\ensuremath` is often used for complex TeX expressions which MathJax may not render. If SVG math, a hashed file is used with a simple alt tag, but additional hashing provided by the contents.

```
8934 \LetLtxMacro{\LWR@origensuredmath}{\@ensuredmath}
8935
8936 \renewcommand{\@ensuredmath}[1]{%
8937 \ifbool{mathjax}{%
8938   \LWR@subsingle dollar*(\mathimagename){%
8939     \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
8940   }{\relax}%
8941   \LWR@origensuredmath{#1}%
8942 }{%
8943 }% SVG math
```

If already inside a `lateximage` in math mode, continue as-is.

```
8944 \ifmmode%
8945   \LWR@origensuredmath{#1}%
8946 \else%
```

Create an inline math `lateximage` with a simple alt tag and additional hashing according to the contents.

```
8947 \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}{%
8948   {\LWR@origensuredmath{#1}}%
8949 }{%
8950   \LWR@subsingle dollar*(\mathimagename){%
8951     \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
8952   }{%
8953     \LWR@origensuredmath{#1}%
8954   }{%
8955 }%
8956 \fi%
8957 }%
8958 }
```

Remove the old `math` and `displaymath` environments:

```
8959 \let\math\relax
8960 \let\endmath\relax
8961 \let\displaymath\relax
8962 \let\enddisplaymath\relax
```

Env **math** Set math mode then typeset the body of what was between the begin/end. See the **environ** package for \BODY.

```
8963 \NewEnviron{math}{\expandafter{(\BODY\})}
```

Env **LWR@displaymathnormal** Set math mode then typeset the body of what was between the begin/end. See the **environ** package for \BODY.

```
8964 \NewEnviron{LWR@displaymathnormal}{\expandafter{[\BODY]\@ignoretrue}}
```

Set the default displaymath to the normal version:

```
8965 \LetLtxMacro{[}\LWR@openbracketnormal%
8966 \LetLtxMacro{]}{\LWR@closebracketnormal%
8967 \LetLtxMacro{\displaymath}{\LWR@displaymathnormal}%
8968 \LetLtxMacro{\enddisplaymath}{\endLWR@displaymathnormal}%
```

Env **LWR@displaymathother** A version of displaymath which can handle complicated objects, but does not supply MATHJAX or HTML alt tags.

```
8969 \newenvironment{LWR@displaymathother}
8970 {%
8971   \begin{BlockClass}{displaymath}%
8972   \LWR@newautoidanchor%
8973   \booltrue{LWR@indisplaymathimage}%
8974   \begin{lateximage}%
8975   [(display math)]%
8976   \LWR@origdollar\LWR@origdollar%
8977 }%
8978 {%
8979   \LWR@origdollar\LWR@origdollar%
8980   \end{lateximage}%
8981   \end{BlockClass}%
8982 }
```

Env **LWR@equationother** A version of displaymath which can handle complicated objects, but does not supply MATHJAX or HTML alt tags.

```
8983 \newenvironment{LWR@equationother}
8984 {%
8985   \begin{BlockClass}{displaymathnumbered}%
8986   \LWR@newautoidanchor%
8987   \booltrue{LWR@indisplaymathimage}%
8988   \begin{lateximage}%
8989   [(display math)]%
8990   \LWR@origequation%
```

```

8991 }
8992 {%
8993     \LWR@origendequation%
8994     \end{lateximage}%
8995     \end{BlockClass}%
8996 }

```

76.4 MATHJAX support

Ctr `\LWR@nextequation` Used to add one to compute the next equation number.

```
8997 \newcounter{\LWR@nextequation}
```

`\LWR@syncmathjax` Sets the MATHJAX equation format and number for the following equations.

These MATHJAX commands are printed inside “`\(`” and “`\)`” characters. They are printed to HTML output, not interpreted by L^AT_EX.

```
8998 \newcommand*\LWR@syncmathjax{%
```

If using chapters, place the chapter number in front of the equation. Otherwise, use the simple equation number.

```

8999 \ifcsdef{thechapter}{
9000 \InlineClass{hidden}{%
9001 \textbackslash{%
9002 \textbackslash{}seteqsection \{\thechapter\}%
9003 \textbackslash{%
9004 }%
9005 }%
9006 {}% not using chapters

```

MATHJAX doesn't allow setting the equation number to 1:

```
9007 \ifthenelse{\cnttest{\value{equation}}>0}{%
9008 {
```

Tell MATHJAX that the next set of equations begins with the current L^AT_EX equation number, plus one.

```
9009     \setcounter{\LWR@nextequation}{\value{equation}}%
9010     \addtocounter{\LWR@nextequation}{1}
```

Place the MATHJAX command inside “`\(`” and “`\)`” characters, to be printed to HTML, not interpreted by L^AT_EX.

```
9011     \InlineClass{hidden}{  
9012         \textbackslash(   
9013         \textbackslash{}seteqnumber \{\arabic{LWR@nextequation}\}   
9014         \textbackslash)  
9015     }  
9016 }{}% not eq > 0  
9017 }
```

\LWR@hidelatexequation {*<environment>*} {*<contents>*}

Creates the \TeX version of the equation inside an HTML comment.

```
9018 \NewDocumentCommand{\LWR@hidelatexequation}{m +m}{%
```

Stop HTML paragraph handling and open an HTML comment:

```
9019 \LWR@stoppars  
9020 \LWR@htmlopencomment  
9021
```

Start the \TeX math environment inside the HTML comment:

```
9022 \begingroup  
9023 \nameuse{\LWR@orig#1}
```

While in the math environment, restore various commands to their \TeX meanings.

```
9024 \LWR@restoreorigformatting
```

See \LWR@htmlmathlabel in section [76.7.1](#).

Print the contents of the equation:

```
9025 #2
```

End the \TeX math environment inside the HTML comment:

```
9026 \nameuse{\LWR@origend#1}  
9027 \endgroup  
9028
```

Close the HTML comment and resume HTML paragraph handling:

```
9029 \LWR@htmclosecomment  
9030 \LWR@startpars  
9031 }
```

```
\LWR@addmathjax {⟨environment⟩} {⟨contents⟩}
```

Given the name of a math environment and its contents, create a MATHJAX instance. The contents are printed to HTML output, not interpreted by L^AT_EX.

```
9032 \NewDocumentCommand{\LWR@addmathjax}{m +m}{%
```

Enclose the MATHJAX environment inside printed “\⟨” and “\⟩” characters.

```
9033 \LWR@origtilde\LWR@orignewline
9034 \textbackslash{}begin\{#1\}
```

Print the contents, sanitizing for HTML special characters.

```
9035 \LWR@HTMLsanitizeexpand{\detokenize\expandafter{#2}}
```

Close the MATHJAX environment:

```
9036 \textbackslash{}end\{#1\}
9037 \LWR@orignewline
9038 }
```

76.5 Equation environment

Remember existing equation environment:

```
9039 \AtBeginDocument{
9040 \let\LWR@origequation\equation
9041 \let\LWR@origendequation\endequation
9042 \csletcs{\LWR@origequation*}{equation*}
9043 \csletcs{\LWR@origendequation*}{endequation*}
9044 }
```

```
\LWR@doequation {⟨env contents⟩} {⟨env name⟩}
```

For SVG math output, the contents are typeset using the original equation inside a `lateximage`, along with an `<alt>` tag containing a detokenized copy of the L^AT_EX source for the math.

For MATHJAX output, the contents are typeset in an original equation environment placed inside a HTML comment, with special processing for `\labels`. The contents are also printed to the HTML output for processing by the MATHJAX script.

```
9045 \newcommand*{\LWR@doequation}[2]{%
9046
```

If `mathjax` or `FormatWP`, print the \LaTeX expression:

```
9047 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
```

MATHJAX output:

```
9048 {
```

Print commands to synchronize MATHJAX's equation number and format to the current \LaTeX chapter/section and equation number:

```
9049 \LWR@syncmathjax
```

Print the \LaTeX math inside an HTML comment:

```
9050 \LWR@hidelatexequation{#2}{#1}
9051 }
```

SVG output: Create the `lateximage` along with an HTML `<alt>` tag having an equation number, the \LaTeX equation environment commands, and the contents of the environment's `\BODY`.

```
9052 {%
  not mathjax
```

Begin the `lateximage` with an `<alt>` tag containing the math source:

```
9053 \ifstreq{#2}{equation*}{%
  \begin{BlockClass}{displaymath}%
  }{%
  \begin{BlockClass}{displaymathnumbered}%
  }{%
  \LWR@newautoIDanchor%
  \booltrue{\LWR@indisplaymathimage}%
  \begin{lateximage}[%]
    \ifstreq{#2}{equation*}{%
      \ifdefequal{\LWR@equationtag}{\theequation}{%
        no tag was given
      }{%
        (\LWR@equationtag) % tag was given
      }{%
        (\LWR@equationtag) % automatic numbering
      }{%
        \textbackslash{begin}\{#2\} % extra space
        \LWR@HTMLsanitizeexpand{\detokenize\expandafter{#1}} % extra space
        \textbackslash{end}\{#2\}%
      }%
    }%
  ]% alt tag
```

Create the actual \LaTeX -formatted equation inside the `lateximage` using the contents of the environment.

```

9074     \@nameuse{LWR@orig#2}%
9075     #1% contents collected by \collect@body
9076     \@nameuse{LWR@origend#2}%
9077     \end{lateximage}%
9078     \end{BlockClass}%
9079 }% not mathjax
9080 }
```

After the environment, if MATHJAX, print the math to the HTML output for MATHJAX processing:

```

9081 \newcommand*\LWR@doendequation}[1]{%
9082   \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }{%
9083     {%
9084       \LWR@addmathjax{#1}{\BODY}%
9085     }%
9086   }%
9087 }
```

Remove existing equation environment:

```

9088 \AtBeginDocument{
9089 \let\equation\relax
9090 \let\endequation\relax
9091 \csletcs{equation*}\relax
9092 \csletcs{endequation*}\relax
9093 }
```

Env `equation` The new equation environment is created with `\NewEnviron` (from the `environ` package), which stores the contents of its environment in a macro called `\BODY`.

```

9094 \AtBeginDocument{
9095 \NewEnviron{equation}%
9096 {\LWR@doequation{\BODY}{equation}}%
9097 [\LWR@doendequation{equation}]
9098
9099 \LetLtxMacro{\LWR@equationnormal}{equation}
9100 \LetLtxMacro{\endLWR@equationnormal}{endequation}
9101 }
```

Env `equation*`

```

9102 \AtBeginDocument{
9103 \NewEnviron{equation*}%

```

```

9104 {\LWR@doequation{\BODY}{\equation*}}%
9105 [\LWR@doendequation{\equation*}]
9106
9107 \csletcs{\LWR@equationnormalstar}{\equation*}
9108 \csletcs{\LWR@endequationnormalstar}{\endequation*}
9109 }

```

Remember the “less” version of `equation`, which uses MATHJAX and `alt` tags, but does not support complicated contents such as some `Tikz` expressions.

```

9110 \AtBeginDocument{
9111 \LetLtxMacro{\LWR@equationless}{\equation}
9112 \LetLtxMacro{\endLWR@equationless}{\endequation}
9113 \csletcs{\LWR@equationlessstar}{\equation*}
9114 \csletcs{\LWR@endequationlessstar}{\endequation*}
9115 }

```

76.6 `\displaymathnormal` and `\displaymathother`

`\displaymathnormal` By default, or when selecting `\displaymathnormal`, MATHJAX math display environments print their contents as text into HTML, and SVG display math environments render their contents as SVG images and use their contents as the `alt` tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated `Tikz` pictures, compilation will fail.

`\displaymathother`
**MathJax unsupported
complicated alt tag** When selecting `\displaymathother`, it is assumed that the contents are more complicated than “pure” math. An example is an elaborate `Tikz` picture, which will not render in MATHJAX and will not make sense as an HTML `alt` tag. In this mode, MATHJAX is turned off, math display environments become SVG images, even if MATHJAX is selected, and the HTML `alt` tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as `Tikz` pictures are more likely to compile successfully.

`\displaymathnormal`
simple math objects Use when display math environments have simple math which is to sent to MATHJAX or included in HTML `alt` tags.

```

9116 \newcommand*{\displaymathnormal}{%
9117 \ifbool{\LWR@origmathjax}{\booltrue{mathjax}}{\boolfalse{mathjax}}%
9118 \LetLtxMacro{\[\LWR@openbracketnormal}%
9119 \LetLtxMacro{\]\LWR@closebracketnormal}%
9120 \LetLtxMacro{\displaymath}{\LWR@displaymathnormal}%
9121 \LetLtxMacro{\enddisplaymath}{\endLWR@displaymathnormal}%
9122 \LetLtxMacro{\equation}{\LWR@equationnormal}%
9123 \LetLtxMacro{\endequation}{\endLWR@equationnormal}%
9124 \csletcs{\equation*}{\LWR@equationnormalstar}%

```

```
9125 \csletcs{endequation*}{LWR@endequationnormalstar}%
9126 }
```

\displaymathother complicated math objects Use when display math environments have complicated objects which will not work with MathJax or should not be included in HTML alt tags. Complicated contents are more likely to compile correctly.

```
9127 \newcommand*{\displaymathother}{%
9128 \boolfalse{mathjax}%
9129 \LetLtxMacro{\displaymath}{\LWR@displaymathother}%
9130 \LetLtxMacro{\enddisplaymath}{\endLWR@displaymathother}%
9131 \LetLtxMacro{[\LWR@displaymathother}%
9132 \LetLtxMacro{]\endLWR@displaymathother}%
9133 \LetLtxMacro{\equation}{\LWR@equationother}%
9134 \LetLtxMacro{\endequation}{\endLWR@equationother}%
9135 \csletcs{equation*}{displaymath}%
9136 \csletcs{endequation*}{enddisplaymath}%
9137 }

9138 \end{warpHTML}
```

for PRINT output: 9139 \begin{warpprint}

Print-mode versions:

```
9140 \newcommand*{\displaymathnormal}{}
9141 \newcommand*{\displaymathother}{}

9142 \end{warpprint}
```

for HTML output: 9143 \begin{warpHTML}

76.7 AMS Math environments

76.7.1 Support macros

Bool LWR@amsmultiline True if processing a multiline environment.

To compensate for multiline-specific code, LWR@amsmultiline is used to add extra horizontal space in \LWR@htmlmathlabel if it is used in an **amsmath** environment which is not a multiline environment and not an equation.

```
9144 \newbool{LWR@amsmultiline}
9145 \boolfalse{LWR@amsmultiline}
```

```
\LWR@htmlmathlabel {<label>}
```

l warp points `\ltx@label` here. This is used by `\label` when inside a \TeX AMS math environment's math display environment.

`\LWR@origltx@label` points to the \TeX original, modified by **l warp**, then by **amsmath**, then by **cleveref**.

```
9146 \newcommand*{\LWR@htmlmathlabel}{1}{%
9147 \LWR@traceinfo{LWR@htmlmathlabelb #1}%
}
```

If **mathjax** or **FormatWP**, print the \TeX expression:

```
9148 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }{%
9149 {%
```

The combined \TeX & HTML label is printed in a `\text` field:

```
9150 \text{%
```

Shift the label over to the right side of the environment to avoid over-printing the math:

```
9151 \ifboolexpr{LWR@amsmultiline}{}{\hspace*{\totwidth}{}}%
```

Temporarily end the HTML comment, insert the \TeX & HTML label, then resume the HTML comment. `\@firstofone` is required to remove extra braces introduced by the **amsmath** package.)

```
9152 \LWR@htmlclosecomment%
9153 \LWR@origltx@label{#1}%
9154 \LWR@htmlopencomment%
9155 }% text
9156 }% mathjax
9157 {%
9158 \LWR@origltx@label{#1}%
9159 }%
9160 }
```

`\LWR@beginhideamsmath` Starts hiding \TeX math inside an HTML comment.

```
9161 \newcommand*{\LWR@beginhideamsmath}{%
9162 \LWR@stopars
9163 \LWR@origtilde\LWR@orignewline
9164 \LWR@htmlopencomment
9165
9166 \begingroup
9167 \LWR@restoreorigformatting
```

```
9168 }
```

\LWR@endhideamsmath Ends hiding L^AT_EX math inside an HTML comment.

```
9169 \newcommand*\LWR@endhideamsmath{%
9170 \endgroup%
9171 %
9172 \LWR@htmlclosecomment%
9173 \LWR@orignewline%
9174 \LWR@startpars%
9175 }
```

76.7.2 Environment patches

The **amsmath** environments already collect their contents in \@envbody for further processing. eqnarray is not an ***AMS*** package, and thus requires special handling.

For SVG math: Each environment is encapsulated inside a **lateximage** environment, along with a special optional argument of \LWR@amsmathbody or \LWR@amsmathbodynumbered telling **lateximage** to use as the HTML <alt> tag the environment's contents which were automatically captured by the ***AMS*** environment.

For MATHJAX: Each environment is syched with L^AT_EX's equation numbers, typeset with L^AT_EX inside an HTML comment, then printed to HTML output for MATHJAX to process.

Env **eqnarray** This environment is not an ***AMS*** environment and thus its body is not automatically captured, so the **environ** package is used to capture the environment into \BODY.

```
9176 \let\LWR@origeqnarray\eqnarray%
9177 \let\LWR@origendeqnarray\endeqnarray%
```

To remember whether the starred environment was used, and thus whether to number the equations:

```
9178 \newbool{\LWR@numbereqnarray}%
9179 \booltrue{\LWR@numbereqnarray}
```

Common code used by eqnarray and Beqnarray (from **fancybox**):

```
9180 \newcommand{\LWR@eqnarrayfactor}{%
```

If **mathjax** or **FormatWP**, print the L^AT_EX expression:

```
9181 \ifboolexpr{\bool{mathjax} \or (\ bool{FormatWP} \and \bool{WPMarkMath} ) }%
9182 {%
```

If MATHJAX, the environment contents (the \BODY) are executed in a HTML comment to trigger the correct equation number increment (if not starred), then are included verbatim in the output for MATHJAX to interpret:

```
9183     \LWR@syncmathjax
9184     \boolfalse{LWR@amsmultiline}
9185     \ifbool{LWR@numbereqnarray}
9186     {
```

If numbering the equations, execute a copy inside an HTML comment block:

```
9187     \LWR@beginhideamsmath
9188     \LWR@origeqnarray
9189     \BODY
9190     \LWR@origendeqnarray
9191     \LWR@endhideamsmath
```

Then print the (sanitized) contents to the output for MATHJAX to interpret:

```
9192     \LWR@addmathjax{eqnarray}{\BODY}
9193     }%
9194     {%
9194     \ifnot{LWR@numbereqnarray}
```

If not numbering equations, just create the contents for MATHJAX:

```
9195     \LWR@addmathjax{eqnarray*}{\BODY}
9196     }%
9197     \ifnumbereqnarray
9198     }%
9198     \mathjax
9199     \ifbool{LWR@numbereqnarray}
9200     {
```

For numbered SVG equations, first create a `lateximage` with an `alt` attribute containing sanitized copy of the source code:

```
9201     \begin{BlockClass}{displaymathnumbered}%
9202     \LWR@newauto{danchor}%
9203     \booltrue{LWR@indisplaymathimage}%
9204     \begin{lateximage}[(\LWR@startingequationtag--\LWR@equationtag)
9205     \LWR@addmathjax{eqnarray}{\BODY}]
```

Then create the image contents using an actual `eqnarray`:

```
9206     \LWR@origeqnarray
9207     \BODY
9208     \LWR@origendeqnarray
9209     \end{lateximage}
9210     \end{BlockClass}
```

```

9211      }%
9212      {%
9213      \begin{BlockClass}{displaymath}
9214      \LWR@newauto{danchor}%
9215      \booltrue{\LWR@indisplaymathimage}%
9216      \begin{lateximage}[\LWR@addmathjax{eqnarray*}]{\BODY}%
9217      \LWR@origeqnarray
9218      \BODY
9219      \nonumber
9220      \LWR@origendeqnarray
9221      \end{lateximage}%
9222      \end{BlockClass}%
9223      }%
9224      }%
9225      \LWR@numbereqnarray
9226      }%

```

If not numbered, do the same, but an extra `\nonumber` seems to be required:

```

9213      \begin{BlockClass}{displaymath}
9214      \LWR@newauto{danchor}%
9215      \booltrue{\LWR@indisplaymathimage}%
9216      \begin{lateximage}[\LWR@addmathjax{eqnarray*}]{\BODY}%
9217      \LWR@origeqnarray
9218      \BODY
9219      \nonumber
9220      \LWR@origendeqnarray
9221      \end{lateximage}%
9222      \end{BlockClass}%
9223      }%
9224      }%
9225      \LWR@numbereqnarray
9226      }%

```

Default to number equations in the future:

```

9225 \booltrue{\LWR@numbereqnarray}
9226 }%

```

`eqnarray` itself is made with a blank line before and after to force it to be on its own line:

```

9227 \RenewEnviron{eqnarray}{%
9228 \LWR@eqnarrayfactor
9229 }%
9230 \LWR@eqnarrayfactor
9231 }%
9232 }%

```

The starred version is patched to turn off the numbering:

```

9233 \csgpreto{eqnarray*}{\boolfalse{\LWR@numbereqnarray}}%
9234 \end{warpHTML}

```

77 Lateximages

77.1 Description

Env `lateximage` A `lateximage` is a piece of the document which is typeset in `LATEX` then included in

the HTML output as an image. This is used for math if SVG math is chosen, and also for the `picture`, `tikzpicture`, and other environments.

Before typesetting the `lateximage` a large number of formatting, graphics, and symbols-related macros are temporarily restored to their print-mode meaning by `\LWR@restoreorigformatting`. (See section 75.)

A `lateximage` is typeset on its own PDF page inside an HTML comment which starts on the preceding page and ends on following page, and instructions are written to `lateximage.txt` for `lwarpmk` to extract the `lateximage` from the page of the PDF file then generate an accompanying `.svg` file image file. Meanwhile, instructions to show this image are placed into the HTML file after the comment.

An HTML `` is created to hold both the HTML comment, which will have the `pdftotext` conversion, and also the link to the final `.svg` image.

A \TeX label is used to remember which PDF page has the image. A label is used because footnotes, endnotes, and pagenotes may cause the image to appear at a later time. The label is declared along with the image, and so it correctly remembers where the image finally ended up.

HTML alt tag The HTML alt tag is set to the \TeX source for SVG math, some chemistry expressions, and perhaps some other expressions which make sense for text copy/paste. In some other cases, the alt tag is set according to the package name.

When creating an SVG math image, its alt tag may be set to the math expression, which may be hashed for image reuse. In the case of `\ensuremath` or after `\inlinemathother`, where the contents require a unique image for each instance of the same expression, the alt tag is set to `\mathimagedename`, and the image is not reused.

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “math image”, and it may be changed according to the document’s language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following SVG math images.

For many packages, the output is placed inside a `lateximage` with an HTML alt tag set to the package name followed by `\packagediagramname`. For example:

(-xy- diagram)

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “diagram”, and it may be changed according to the document’s language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following `lateximages`.

SVG image font size For the `lateximage` environment, the size of the math and text used in the SVG

image may be adjusted by setting `\LateximageFontSizeName` to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{\normalsize}
```

For inline SVG math, font size is instead controlled by `\LateximageFontSizeScale`, which defaults to:

```
\newcommand*{\LateximageFontSizeScale}{.75}
```

77.2 Support counters and macros

for HTML output: 9235 `\begin{warpHTML}`

Ctr `LWR@lateximagenumber` Sequence the images.

```
9236 \newcounter{LWR@lateximagenumber}
9237 \setcounter{LWR@lateximagenumber}{0}
```

Ctr `LWR@lateximagedepth` Do not create `\latexitimage` inside of `\latexitimage`.

```
9238 \newcounter{LWR@lateximagedepth}
9239 \setcounter{LWR@lateximagedepth}{0}
```

A few utility macros to write special characters:

```
9240 \edef\LWR@hashmark{\string#} % for use in \write
9241 \edef\LWR@percent{\@percentchar} % for use in \write
```

Ctr `LWR@LIPage` Used to reference the PDF page number of a `lateexitimage` to be written into `lateexitimages.txt`.

```
9242 \newcounter{LWR@LIPage}
```

```
9243 \end{warpHTML}
```

77.3 Font size

for HTML & PRINT: 9244 `\begin{warpall}`

`\LateximageFontSizeName` Declares how large to write text in `\latexitimage`. The .svg file text size should blend well with the surrounding HTML text size.

 **no backslash** *Do not include the leading backslash in the name.*

```
9245 \newcommand*{\LateximageFontSizeName}{normalsize}
```

`\LateximageFontSize` Declares how large to scale inline SVG math images. The .svg file text size should blend well with the surrounding HTML text size. The default is .75, but it may be redefined as needed depending on the HTML font.

```
9246 \newcommand*{\LateximageFontSize}{.75}
```

```
9247 \end{warpall}
```

77.4 Sanitizing math expressions for HTML

for HTML output: 9248 \begin{warpHTML}

```
\LWR@HTMLsanitize {\langle text\rangle}
```

Math expressions are converted to `lateximages`, and some math environments may contain &, <, or >, which should not be allowed inside an HTML `<alt>` tag, so must convert them to HTML entities.

Two versions follow, depending on expansion needs. There may be a better way...

```
9249 \newrobustcmd{\LWR@HTMLsanitize}[1]{%
```

Cancel French `babel` character handling, and fully expand the strings:

```
9250 \begingroup%
9251 \LWR@FBcancel%
9252 \fullexpandarg%
```

The &, <, and > may be interpreted by the browser:

```
9253 \protect\StrSubstitute{\detokenize{\#1}}%
9254 {\detokenize{&}}{\detokenize{&}}[\LWR@strresult]%
```

```
9255 \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
9256 {\detokenize{<}}{\detokenize{<}}[\LWR@strresult]%
```

```
9257 \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
9258 {\detokenize{>}}{\detokenize{>}}[\LWR@strresult]%
```

The double quote occasionally causes problems.

```
9259 \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
9260 {\detokenize{"}}{\detokenize{"}}[\LWR@strresult]%
```

MathJax allows expressions to be defined with `\newcommand`. These expressions would appear with `##` for each argument, and each must be changed to a single `#`. This must be done after all the above changes. Attempting another conversion after this causes an error upon further expansion.

```

9261 \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
9262 {\detokenize{##}}{\LWR@origpound}[\LWR@strresult]%

9263 \LWR@strresult%
9264 \endgroup%
9265 }

\LWR@HTMLsanitizeexpand {<text>}

```

This version expands the argument before sanitizing it.

```
9266 \newrobustcmd{\LWR@HTMLsanitizeexpand}[1]{%
```

Cancel French **babel** character handling, and fully expand the strings:

```

9267 \begingroup%
9268 \LWR@FBcancel%
9269 \fullexpandarg%

```

The difference between this and `\LWR@HTMLsanitize` (without “expand”) is the following `\expandafter`:

```

9270 \protect\StrSubstitute{\detokenize\expandafter{\#1}}%
9271 {\detokenize{&}}{\detokenize{&}}[\LWR@strresult]%

9272 \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
9273 {\detokenize{<}}{\detokenize{<}}[\LWR@strresult]%

9274 \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
9275 {\detokenize{>}}{\detokenize{>}}[\LWR@strresult]%

9276 \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
9277 {\detokenize{"}}{\detokenize{"}}[\LWR@strresult]%

```

`\LWR@HTMLsanitizeexpand` is not used for defining new MathJax macros, so the `##` conversion is not needed here.

```

9278 \LWR@strresult%
9279 \endgroup%
9280 }

```

77.5 Equation numbers

Ctr LWR@startingequation For use with `lateximage` and multi-line numbered equations. Remembers the next equation number so that it may be printed in the alt tag.

```

9281 \newcounter{LWR@startingequation}
9282
9283 \@ifundefined{chapter}
9284 {
9285 \renewcommand{\theLWR@startingequation}{%
9286 \arabic{LWR@startingequation}}%
9287 }
9288 }
9289 {%
9290 \chapter{%
9291 \renewcommand{\theLWR@startingequation}{%
9292 \ifnumcomp{\value{chapter}}{>}{0}{\arabic{chapter}.}{}%
9293 \arabic{LWR@startingequation}}%
9294 }

```

Bool LWR@isstartingequation True for the first equation tag, false for later tags in the same environment.

```
9295 \newbool{LWR@isstartingequation}
```

\LWR@startingequationtag Prints the starting equation number or tag.

```
9296 \let\LWR@startingequationtag\theLWR@startingequation
```

\LWR@equationtag Prints the ending equation number or tag.

This is reset by `lateximage`, may be temporarily overwritten by `\tag` calling `\LWR@remembertag`.

```
9297 \newcommand*{\LWR@equationtag}{}%
```

Only if SVG math, patch `\tag` after packages have loaded, in case someone else modified `\tag`.

```

9298 \AtBeginDocument{
9299
9300 \ifbool{mathjax}{}{%

```

\LWR@remembertag $\{\langle tag \rangle\}$

For use inside the math environments while using SVG math. Sets `\theLWR@startingequation` and `\theequation` to the given tag.

```

9301 \NewDocumentCommand{\LWR@remembertag}{m}{%
9302     \ifbool{LWR@isstartingequation}{%
9303         \global\boolfalse{LWR@isstartingequation}%
9304         \xdef\LWR@startingequationtag{#1}%
9305     }{}%
9306 }{%
9307 \xdef\LWR@equationtag{#1}%
9308 }%
9309 }% not mathjax
9310 }% AtBeginDocument

```

77.6 HTML alt tags

`\LWR@amsmathbody {<envname>}` For use inside the optional argument to a `\teximage` to add the contents of a AMS math environment to the `<alt>` tag.

```

9311 \newcommand*{\LWR@amsmathbody}[1]{%
9312     \textbackslash\begin{#1} % extra space
9313 \textbackslash\HTMLsanitizeexpand{\detokenize\expandafter{\the\@envbody}}%
9315 \textbackslash\end{#1}%
9316 }

```

`\LWR@amsmathbodynumbered {<envname>}` For use inside the optional argument to a `\teximage` to add the contents of a AMS math environment to the alt tag, prefixed by the equation numbers.

```

9317 \newcommand*{\LWR@amsmathbodynumbered}[1]{%
9318     \ifnumcomp{\value{LWR@startingequation}}{=}{\value{equation}}{%
9319         (\LWR@equationtag)}{%
9320         (\LWR@startingequationtag--\LWR@equationtag)} % extra space
9321         \LWR@amsmathbody{#1} % extra space
9322     }%
9323 }

```

77.7 `\teximage` environment

Env `\teximage` * [<2: <alt> tag>] [<3: add'l hashing>] [<4: CSS style>]

Typesets the contents and then renders the result as an SVG file. Star causes the image to be hashed for reuse.

The optional `<alt>` tag is included in the HTML code for use with copy/paste.

image filename hashing If starred, a hashed filename is used. If so, the hash is based on the `alt` tag and also the additional hashing argument.

This may be used to provide an expression with a simple `alt` tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated TeX expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is duplicated in the additional hashing argument.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing argument in order to make the hash unique according to the set of options, even if the simple `alt` tag is still the same.

```
9324 \catcode`\$=\active%
9325
9326 \NewDocumentEnvironment{lateximage}{s O{(image)} O{} O{}}
9327 {%
9328 \LWR@traceinfo{lateximage: starting on \jobname.pdf page \arabic{page}}%
9329 \LWR@traceinfo{lateximage: entering depth is \arabic{LWR@lateximagedepth}}%
```

Nested `lateximages` remain one large `lateximage`:

```
9330 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%

```

If nesting inside an already-existing `lateximage`, simply record one more level. *AMS* packages redefine `\addtocounter` to do nothing if inside a `\text`, so lower-level TeX macros are used for tracking nested `lateximages`.

```
9331 {%
9332 %      \addtocounter{LWR@lateximagedepth}{1}%
9333     \global\advance\c@LWR@lateximagedepth 1\relax% Due to AmS \text macro.
9334 }%
```

Otherwise, this is the outer-most `lateximage`:

```
9335 {%
  start of outer-most lateximage
}
```

Remember the next equation number to be allocated, in case it must be printed in a multi-equation environment:

```
9336 \LWR@traceinfo{lateximage: starting outer-most lateximage}%
```

```

9337      \setcounter{LWR@startingequation}{\value{equation}}%
9338      \addtocounter{LWR@startingequation}{1}%
9339      \booltrue{LWR@isstartingequation}%
9340      \let\LWR@startingequationtag\theLWR@startingequation%

```

The default equation tag, unless overwritten by \tag:

```
9341      \let\LWR@equationtag\theequation%
```

Starting a new lateximage:

```

9342      \addtocounter{LWR@lateximagenumber}{1}%
9343      \LWR@traceinfo{lateximage: LWR@lateximagenumber is \arabic{LWR@lateximagenumber}}%

```

While inside a lateximage, locally do not use mathjax:

```
9344      \boolfalse{mathjax}%
```

Be sure that are doing a paragraph:

```
9345      \LWR@ensuredoingapar%
```

Next file:

```

9346      \addtocounter{LWR@externalfilecnt}{1}%
9347      \LWR@traceinfo{lateximage: LWR@externalfilecnt is \arabic{LWR@externalfilecnt}}%

```

Figure out what the next page number will be. \setcounterpageref assigns LWR@LIpage to the page number for the reference LWR@lateximageXXX:

```

9348      \setcounterpageref{LWR@LIpage}{LWR@lateximage\arabic{LWR@lateximagenumber}}%
9349      \LWR@traceinfo{lateximage: LWR@LIpage is \arabic{LWR@LIpage}}%

```

Create an HTML span which will hold the comment which contains the pdftotext translation of the image's page, and also will hold the link to the .svg file:

```

9350      \LWR@htmlltag{span id="lateximage\arabic{LWR@lateximagenumber}" % extra space
9351      class="lateximagesource"}%

```

Write instructions to the lateximages.txt file:

```

9352      \LWR@traceinfo{lateximage: about to write to lateximages.txt}%
9353      \IfBooleanTF{#1}%
9354      {%
9355          \LWR@traceinfo{lateximage: hash true, adding %
9356          !\detokenize\expandafter{#2}!\detokenize\expandafter{#3}!}%

```

Compute and save the hashed file name for later use:

```

9357      \edef\LWR@hashedname{%
9358          \LWR@mdfive{\detokenize\expandafter{\#2}-!-\#3}%
9359  }%
9360          \LWR@mdfive{\detokenize\expandafter{\#2}-!-\detokenize\expandafter{\#3}}%
9361      \LWR@traceinfo{lateximage: hash is \LWR@hashedname}%

```

Write the page, hashing, and hashed name:

```

9362      \immediate\write\LWR@lateximagesfile{%
9363          |\arabic{LWR@LIpage}|true|\LWR@hashedname|%
9364      }%
9365  }% hash
9366  {%- no hash

```

No hash, so write the page, no hashing, and the image number:

```

9367      \LWR@traceinfo{lateximage: hash false}%
9368      \immediate\write\LWR@lateximagesfile{%
9369          |\arabic{LWR@LIpage}|false|lateximage-\arabic{LWR@externalfilecnt}|%
9370      }%
9371  }% no hash

```

Place an open comment tag. This will hide any traces of the `lateximage` PDF page which were picked up by `pdftotext`.

```

9372      \LWR@traceinfo{lateximage: about to create open comment}%
9373      \LWR@htmlopencomment%

```

One level deeper. At this outer-most `lateximage`, it is known that this is not being used inside an $\mathcal{M}\mathcal{S}$ `\text`, since the outer-most level will never be in math mode.

```
9374      \addtocounter{LWR@lateximagedepth}{1}%

```

Start the new PDF page:

```

9375      \LWR@traceinfo{lateximage: about to create a new page}%
9376      \LWR@orignewpage%

```

Typeset the image in a “standard” width page and font size:

```

9377      \LWR@traceinfo{lateximage: about to create minipage}%
9378      \LWR@print@minipage{6in}%
9379      \nameuse{\LWR@print@\LateximageFontSizeName}%

```

Temporarily restore formatting to its PDF definitions: Do not produce HTML tags for `\hspace`, etc. inside a `lateximage`.

```
9380      \LWR@traceinfo{lateximage: about to temporarily restore formatting}%
9381      \LWR@restoreorigformatting%
```

Use full-page footnotes instead of minipage footnotes. These become HTML footnotes.

```
9382      \def\@mpfn{footnote}%
9383      \def\thempfn{\thefootnote}%
9384      \LetLtxMacro\@footnotetext\LWR@footnotetext%
```

Create the `LWR lateximage<number>` label:

```
9385      \LWR@traceinfo{lateximage: about to create label}%
9386      \LWR@orig@label{LWR lateximage\arabic{LWR@lateximagenumber}}%
9387      \LWR@traceinfo{lateximage: finished creating the label}%
```

Enable print-mode math functions:

```
9388      \LetLtxMacro$\LWR@origdollar%
9389      \catcode`\$=3% math shift
9390      \LetLtxMacro\(\LWR@origopenparen%
9391      \LetLtxMacro\)\LWR@origcloseparen%
```

Only enable print-mode display math if are not already inside display math:

```
9392      \ifbool{LWR@indisplaymathimage}{}{%
9393          \not in display math
9394          \LetLtxMacro\[ \LWR@origopenbracket%
9395          \LetLtxMacro\] \LWR@origclosebracket%
9396          \let\equation\LWR@origequation%
9397          \let\endequation\LWR@origendequation%
9398          \csletcs{equation*}{\LWR@origequation*}%
9399          \csletcs{endequation*}{\LWR@origendequation*}%
9400      }%
9401      \not in display math
```

For **chemformula**:

```
9400      \LetLtxMacro\LWR@newsingledollar$%
9401      \LetLtxMacro\LWR@newsingledollar$% syntax highlighting
9402 }% end of outer-most lateximage
9403 \LWR@traceinfo{lateximage: finished start of environment}%
9404 }% end of \begin{lateximage}
```

`\end{lateximage}` When the environment closes:

```
9405 {%
  start of \end{lateximage}
9406 \LWR@traceinfo{lateximage: starting end of lateximage}%
```

Nested more than one deep?

```
9407 \LWR@traceinfo{lateximage: internal depth was \arabic{LWR@lateximagedepth}}%
9408 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{1}%
9409 }%
```

If nesting inside an already existing lateximage, simply record one less level. Uses a lower-level \TeX macro due to $\mathcal{AM}\mathcal{S}$ \text{change of \addtocounter{}}.

```
9409 {%
9410   \LWR@traceinfo{lateximage: unnesting}%
9411   \global\advance\c@LWR@lateximagedepth -1\relax%
9412 }%
```

If this is the outer-most lateximage:

```
9413 {%
  end of outer-most lateximage
```

Finish the lateximage minipage and start a new PDF page:

```
9414 \LWR@traceinfo{lateximage: ending outer-most lateximage}%
9415   \endLWR@print@minipage%
9416   \LWR@orignewpage%
9417   \LWR@print@scriptsize%
```

Close the HTML comment which encapsulated any traces of the lateximage picked up by **pdftotext**:

```
9418   \LWR@print@vspace*{.5\baselineskip}%
9419   \LWR@htmlclosecomment%
9420   \LWR@traceinfo{lateximage: The page after the image is \arabic{page}}%
```

Create a link to the lateximage, allowing its natural height:

```
9421   \IfBooleanTF{#1}{%
9422     starred
9423     {%
9424       \LWR@subinlineimage[#2]{lateximage}%
9425       lateximages\OSPathSymbol%
9426       \LWR@print@mbox{\LWR@hashedname}%
9427       }{%
9428         \LWR@subinlineimage[#2]{lateximage}%
9429       }{%
9430         \LWR@subinlineimage[#2]{lateximage}%
9431       }{%
9432         lateximages\OSPathSymbol%
```

```

9433           \LWR@print@mbox{lateximage-\theLWR@externalfilecnt}%
9434           }{svg}{#4}%
9435       }% no hash

```

Be sure that are doing a paragraph:

```
9436     \LWR@ensuredoingapar%
```

Close the HTML span which has the **pdftotext** comment and also the link to the .svg image:

```

9437     \LWR@htmltag{/span}%
9438     \ifbool{HTMLDebugComments}{%
9439         \LWR@htmlcomment{End of lateximage}%
9440     }%

```

Undo one lateximage level. This is not inside an *AMS* \text, so regular \addtocounter may be used here.

```

9441     \addtocounter{LWR@lateximagedepth}{-1}%
9442 }% end of outer-most lateximage
9443 \LWR@traceinfo{lateximage: exiting depth is \arabic{LWR@lateximagedepth}}%
9444 \LWR@traceinfo{lateximage: done}%
9445 }%
9446 \catcode`\$=3% math shift
9447 \end{warpHTML}

```

for PRINT output: 9448 \begin{warpprint}

Env lateximage [<alt> tag] [<CSS style>]

varwidth is used to create a box of the natural width of its contents.

```

9449 \NewDocumentEnvironment{lateximage}{s o o}
9450     {\begin{varwidth}[b]{\linewidth}}
9451     {\end{varwidth}}
9452 \end{warpprint}

```

78 center, flushleft, flushright

for HTML output: 9453 \begin{warpHTML}

Env **center** Replace center functionality with css tags:

```
9454 \renewenvironment*{center}
9455 {
9456 \LWR@forcenewpage
9457 \ifbool{FormatWP}
9458 {\BlockClass[\LWR@print@mbox{text-align:center}]{center}}
9459 {\BlockClass{center}}
9460 }
9461 {\endBlockClass}
```

Env **flushright**

```
9462 \renewenvironment*{flushright}
9463 {
9464 \LWR@forcenewpage
9465 \ifbool{FormatWP}
9466 {\BlockClass[\LWR@print@mbox{text-align:right}]{flushright}}
9467 {\BlockClass{flushright}}
9468 }
9469 {\endBlockClass}
```

Env **flushleft**

```
9470 \renewenvironment*{flushleft}
9471 {
9472 \LWR@forcenewpage
9473 \ifbool{FormatWP}
9474 {\BlockClass[\LWR@print@mbox{text-align:left}]{flushleft}}
9475 {\BlockClass{flushleft}}
9476 }
9477 {\endBlockClass}
```

\centering, \raggedleft, and \raggedright usually have no effect on the HTML output, but they may be used to compare with the next token to identify their use at the start of a float. See \LWR@floatalignment.

\centering

```
9478 \newcommand*{\LWR@HTML@centering}{%
9479 \ifbool{HTMLDebugComments}{%
9480     \LWR@htmlcomment{centering}%
9481 }{}%
9482 }
9483 \LWR@formatted{centering}
```

```
\raggedleft

9484 \newcommand*{\LWR@HTML@raggedleft}{%
9485 \ifbool{HTMLDebugComments}{%
9486     \LWR@htmlcomment{raggedleft}%
9487 }{}%
9488 }
9489 \LWR@formatted{raggedleft}

\raggedright

9490 \newcommand*{\LWR@HTML@raggedright}{%
9491 \ifbool{HTMLDebugComments}{%
9492     \LWR@htmlcomment{raggedright}%
9493 }{}%
9494 }
9495 \LWR@formatted{raggedright}

\leftline {\langle text\rangle}

9496 \renewcommand{\leftline}[1]{\begin{flushleft}\#1\end{flushleft}>

\centerline {\langle text\rangle}

9497 \renewcommand{\centerline}[1]{\begin{center}\#1\end{center}>

\rightline {\langle text\rangle}

9498 \renewcommand{\rightline}[1]{\begin{flushright}\#1\end{flushright}>

9499 \end{warpHTML}
```

79 Pre-loaded packages

for HTML output: 9500 \begin{warpHTML}

If **textcomp** was loaded before **l warp**, perhaps as part of the font-related packages, explicitly load the l warp patches now:

```
9501 \@ifpackageloaded{textcomp}{\LWR@origRequirePackage{l warp-textcomp}}{}
```

If **xunicode** was loaded before **lwarp**, perhaps as part of the font-related packages, explicitly load the lwarp patches now:

```
9502 \@ifpackageloaded{xunicode}{\LWR@origRequirePackage{lwarp-xunicode}}{}
```

If **graphics** or **graphicx** were loaded before **lwarp**, perhaps by **xunicode**, explicitly load the lwarp patches now:

```
9503 \@ifpackageloaded{graphics}{\LWR@origRequirePackage{lwarp-graphics}}{}
```

```
9504 \@ifpackageloaded{graphicx}{\LWR@origRequirePackage{lwarp-graphicx}}{}
```

```
9505 \end{warpHTML}
```

80 Siunitx

Pkg **siunitx** The **lwarp** core passes a few options to **siunitx**.

fractions Due to **pdftotext** limitations, fraction output is replaced by symbol output for per-mode and quotient-mode.

⚠ **math mode required** Some units will require that the expression be placed inside math mode.

NOTE: As of this writing, the **siunitx** extension for **MATHJAX** is not currently hosted at any public CDN, thus **siunitx** is not usable with **MATHJAX** unless a local copy of this extension is created first.

⚠ **tabular** Tabular S columns are rendered as simple c columns, and tabular s columns are not supported. These may be replaced by c columns with each cell contained in \num or \si.

for HTML output: 9506 \begin{warpHTML}

Options for siunitx:

```
9507 \newrobustcmd{\LWR@siunitx@textcelsius}{\HTMLentity{deg}C}
9508 \newrobustcmd{\LWR@siunitx@textdegree}{\HTMLentity{deg}}
9509 \newrobustcmd{\LWR@siunitx@textprime}{\HTMLunicode{2032}}
9510 \newrobustcmd{\LWR@siunitx@textdblprime}{\HTMLunicode{2033}}
9511 \newrobustcmd{\LWR@siunitx@textplanckbar}{\text{\textit{\HTMLunicode{0127}}}}
9512
9513 \appto{\LWR@restoreorigformatting}{%
9514 \renewrobustcmd{\LWR@siunitx@textcelsius}{\text{\ensuremath{^\circ}C}}%
9515 \renewrobustcmd{\LWR@siunitx@textdegree}{\text{\ensuremath{^\circ}}}%
9516 \renewrobustcmd{\LWR@siunitx@textprime}{\text{\ensuremath{'}}}%
9517 \renewrobustcmd{\LWR@siunitx@textdblprime}{\text{\ensuremath{^{\prime\prime}}}}%
```

```

9518 \renewrobustcmd{\LWR@siunitx@textplanckbar}{\text{\ensuremath{\hbar}}}}%
9519 }
9520
9521 \PassOptionsToPackage{
9522   detect-mode=true,
9523   per-mode=symbol,% fraction is not seen by pdftotext
9524   text-celsius = {\LWR@siunitx@textcelsius},
9525   text-degree = {\LWR@siunitx@textdegree},
9526   text-arcminute = {\LWR@siunitx@textprime} ,
9527   text-arcsecond = {\LWR@siunitx@textdblprime} ,
9528 }{siunitx}

9529 \end{warpHTML}

```

81 Graphics print-mode modifications

81.1 General limitations

\includegraphics file formats For `\includegraphics` with .pdf or .eps files, the user must provide a .pdf or .eps image file for use in print mode, and also a .svg, .png, or .jpg version of the same image for use in HTML.

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, **lwarf** will automatically choose the .pdf or .eps format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a .pdf or .eps image is referred to with its file extension, the extension will be changed to .svg for HTML:

```
\includegraphics{filename.pdf} % uses .svg in HTML
\includegraphics{filename.eps} % uses .svg in HTML
```

Prog `pdftocairo` To convert a PDF image to SVG, use the utility **pdftocairo**:

PDF to SVG

```
Enter ⇒ pdftocairo -svg filename.pdf
```

Prog `lwarpmk pdftosvg` For a large number of images, use **lwarpmk**:

```
Enter ⇒ lwarpmk pdftosvg *.pdf      (or a list of filenames)
```

Prog `lwarpmk epstopdf` For EPS images converted to PDF using the package **epstopdf**, use

epstopdf package

```
Enter ⇒ lwarpmk pdftosvg *.PDF
```

to convert to SVG images.

DVI latex When using DVI **latex**, it is necessary to convert EPS to PDF and then to SVG:

```
Enter ⇒ l warpmk epstopdf *.eps      (or a list of filenames)
Enter ⇒ l warpmk pdftosvg *.pdf       (or a list of filenames)
```

PNG and JPG For PNG or JPG while using **pdflatex**, **lualatex**, or **xelatex**, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

GIF GIF files may be used for HTML, but another format must also be provided for print output.

file extension priorities If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

⚠ graphics vs. graphicx If using the older **graphics** syntax, use both optional arguments for `\includegraphics`. A single optional parameter is interpreted as the newer **graphicx** syntax. Note that viewports are not supported by **l warp** — the entire image will be shown.

⚠ viewport

⚠ viewport units For `\includegraphics`, avoid px and % units for width and height, or enclose them inside `warpHTML` environments. For font-proportional image sizes, use ex or em. For fixed-sized images, use cm, mm, in, pt, or pc. Use the keys `width=.5\linewidth`, or similar for `\textwidth` or `\textheight` to give fixed-sized images proportional to a 6 by 9 inch text area. Do not use the `scale` option, since it is not well supported by HTML browsers.

options `\includegraphics` accepts `width` and `height`, `origin`, `rotate` and `scale`, plus a new `class` key.

HTML class With HTML output, `\includegraphics` accepts an optional `class=xyz` keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

\rotatebox `\rotatebox` accepts the optional `origin` key.

⚠ browser support `\rotatebox`, `\scalebox`, and `\reflectbox` depend on modern browser support. The css3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike L^AT_EX, so expect some ugly results for scaling and rotating.

81.2 Print-mode modifications

for PRINT output: For print output, accept and then discard the new `class` key:

```
9530 \begin{warpprint}
9531 \define@key{Gin}{class}{}{}
```

Print-mode additions for the **overpic** package. See section 307 for the HTML version.

```
9532 \AtBeginDocument{
9533 \@ifpackageloaded{overpic}{
9534 \newcommand*\overpicfontsize{12}
9535 \newcommand*\overpicfontskip{14}
9536 }{}}
9537 }
9538 \end{warpprint}
```

82 Xcolor boxes

Pkg **xcolor** A few new definitions are provided for enhanced HTML colored boxes, and **\fcolorbox** is slightly modified. Print-mode versions are also provided.

Print-mode versions of new **xcolor** definitions. These are defined inside **warpall** because they are also used for HTML while inside a **lateximage**. They are defined **\AtBeginDocument** so that the **xcolor** originals may first be loaded and saved for reuse.

The framed versions are modified to allow a background color of none, in which case only the frame is drawn, allowing the background page color to show.

for HTML & PRINT: 9539 \begin{warpall}

After **xparse** may have been loaded ...

```
9540 \AtBeginDocument{
...
... and only if xcolor was loaded:
9541 \@ifpackageloaded{xcolor}{
9542 \LWR@traceinfo{patching xcolor}}
```

The print version:

\colorboxBlock **\colorboxBlock** is the same as **\colorbox**:

```
9543 \LetLtxMacro{\colorboxBlock}{\colorbox}
```

The original definition is reused by the new versions:

```
9544 \LetLtxMacro{\LWR@orig}{\print@fcolorbox\fcolorbox}
\fcolorbox [⟨framemode⟩] {⟨framecolor⟩} [⟨boxmodel⟩] {⟨boxcolor⟩} {⟨text⟩}
```

In print mode, `\fcolorbox` is modified to accept a background color of `none`.

(`\fcolorbox` is particular about its optional arguments, thus the elaborate combinations of `\ifthenelse`.)

```
9545 \newsavebox{\LWR@colorminipagebox}
9546
9547 \NewDocumentCommand{\LWR@print@fcolorbox}{o m o m +m}{%
9548 \LWR@traceinfo{\LWR@print@fcolorbox #2 #4}}%
```

Pre-load the contents into an LR box so that they can be used inside a `\fcolorbox`:

```
9549 \begin{lrbox}{\LWR@colorminipagebox}%
9550 #5%
9551 \end{lrbox}%
```

Sort out the various optional arguments and the background color of `none`. In each case, the LRbox is placed inside a `\fcolorbox`.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```
9552 \ifthenelse{\equal{#4}{none}}{%
9553 }% #4 none
9554   \LWR@traceinfo{background is none}%
9555   {% scope the \colorlet
9556     \colorlet{\LWR@currentcolor}{.}%
9557     \color{#2}%
9558     \fbox{%
9559       \color{\LWR@currentcolor}%
9560       \usebox{\LWR@colorminipagebox}%
9561     }% fbox
9562   }% colorlet
9563 }% #4 none
9564 {% #4 not none
9565 \LWR@traceinfo{background not none}%
9566 \IfValueTF{#1}{%
9567 }%
9568   \IfValueTF{#3}{%
9569     {\LWR@orig@print@fcolorbox[#1]{#2}{#3}{#4}{\usebox{\LWR@colorminipagebox}}}%
9570     {\LWR@orig@print@fcolorbox[#1]{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
9571 }%
9572 }% no value #1
9573   \IfValueTF{#3}{%
9574     {\LWR@orig@print@fcolorbox[#2]{#3}{#4}{\usebox{\LWR@colorminipagebox}}}%
```

```

9575   {\LWR@orig@print@fcolorbox{#2}{#4}{\usebox{\LWR@colorminipagebox}}}}%
9576 }% no value #1
9577 }% #4 not none
9578 \LWR@traceinfo{\LWR@print@fcolorbox done}%
9579 }
9580
9581 \renewcommand*{\fcolorbox}{\LWR@print@fcolorbox}

```

\fcolorboxBlock [⟨framemode⟩] {⟨framecolor⟩} [⟨boxmodel⟩] {⟨boxcolor⟩} {⟨text⟩}

In print mode, \fcolorboxBlock is the same as \fcolorbox.

```

9582 \newcommand*{\LWR@print@fcolorboxBlock}{\LWR@print@fcolorbox}
9583 \newcommand*{\fcolorboxBlock}{\LWR@print@fcolorboxBlock}

```

Env fcolorminipage [⟨1:framemode⟩] {⟨2:framecolor⟩} [⟨3:boxmodel⟩] {⟨4:boxcolor⟩} [⟨5:align⟩] [⟨6:height⟩] [⟨7:inner-align⟩] {⟨8:width⟩}

In print mode, becomes a \fcolorbox containing a minipage:

```

9584 \NewDocumentEnvironment{\LWR@print@fcolorminipage}{o m o m O{c} O{} o m}
9585 {%
9586 \LWR@traceinfo{*** fcolorminipage: #2 #4 #8}%

```

Pre-load the contents into an LR box so that they can be used inside a \fcolorbox:

```
9587 \begin{lrbox}{\LWR@colorminipagebox}%
```

If inner alignment is not given, use the outer alignment instead:

```

9588 \IfValueTF{#7}{%
9589 {\begin{minipage}[#5][#6][#7]{#8}}{%
9590 {\begin{minipage}[#5][#6][#5]{#8}}{%
9591 }{%
9592 {%
9593 \end{minipage}}{%
9594 \end{lrbox}}{%
9595 \LWR@traceinfo{*** starting end fcolorminipage #1 #2 #3 #4 #8}}%

```

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a \fcolorbox.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```

9596 \ifthenelse{\equal{#4}{none}}{%
9597 {#4 none

```

```

9598      {%
9599          scope the \colorlet
9600          \colorlet{LWR@currentcolor}{.}%
9601          \color{#2}%
9602          \fbox{%
9603              \color{LWR@currentcolor}%
9604              \usebox{\LWR@colorminipagebox}%
9605          }%
9606      }%
9607  #4 none
9608  #4 not none
9609      \IfValueTF{#1}%
9610      {%
9611          \IfValueTF{#3}%
9612              {\LWR@orig@print@fcolorbox[#1]{#2}{#3}{#4}{\usebox{\LWR@colorminipagebox}}}%
9613              {\LWR@orig@print@fcolorbox[#1]{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
9614      }%
9615      {%
9616          \IfValueTF{#3}%
9617              {\LWR@orig@print@fcolorbox[#2]{#3}{#4}{\usebox{\LWR@colorminipagebox}}}%
9618              {\LWR@orig@print@fcolorbox[#2]{#4}{\usebox{\LWR@colorminipagebox}}}%
9619      }%
9620  #4 not none
9621 \LWR@traceinfo{*** finished end fcolorminipage}%
9622 }
9623 \newenvironment*{fcolorminipage}
9624     {\LWR@print@fcolorminipage}
9625     {\endLWR@print@fcolorminipage}
9626 \LWR@traceinfo{xcolor patches done}
9627 }%
9628 }%
9629 \end{warpall}

```

83 Chemmacros environments

`\makepolymerdelims` and redox reactions must be enclosed in a `lateximage` during HTML output. These environments are provided here in print mode, and in the `chemmacros` code in HTML mode, as a high-level semantic syntax which automatically embeds the contents in a `lateximage` with an appropriate alt tag.

```

for PRINT output: 9630 \begin{warpprint}

9631 \AtBeginDocument{
9632 \@ifpackageloaded{chemmacros}{}

```

Env `polymerdelims`

```
9633 \DeclareDocumentEnvironment{polymerdelims}{}  
9634     {}{}
```

Env `redoxreaction` $\{\langle space\ above\rangle\} \{\langle space\ below\rangle\}$

For print output, extra space is included above and below the image, and a `lateximage` is not necessary. This extra space must be enforced, even inside a float, so zero-width rules are used.

For the HTML version, see section [156.4](#).

```
9635 \DeclareDocumentEnvironment{redoxreaction}{m m}  
9636     {\rule{0pt}{#1}}{\rule[-#2]{0pt}{#2}}  
  
9637 }{}% chemmacros  
9638 }% AtBeginDocument  
  
9639 \end{warpprint}
```

84 Cleveref

Pkg `cleveref` `cleveref` package is used as-is with minor patches.

⚠ **cleveref page numbers** `cleveref` and `variorref` are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to “for”.

Ex:

```
\cpageref{tab:first,tab:second}  
in HTML becomes:  
“pages for table 4.1 and for table 4.2”
```

See `\cpagerefFor` at page [552](#) to redefine the message which is printed for page number references.

loading order `cleveref` and the following associated macro patches are automatically preloaded at the end of the preamble via `\AtEndPreamble` and `\AfterEndPreamble`. This is done because the HTML conversion requires `cleveref`. The user’s document may not require `cleveref`, thus the user may never explicitly load it, so during HTML output `lwarf` loads it last. If the user’s document preamble uses `cleveref` options, or functions such as `\crefname`, then `cleveref` may be loaded in the user’s preamble near the end, and `lwarf`’s additional loading of `cleveref` will have no effect.

Table 11 on page 468 shows the data structure of the label/reference system as revised by **l warp** and **cleveref**.

A few patches allow **cleveref** to work as-is:

for HTML output: 9640 \begin{warpHTML}

\AtEndPreamble forces **cleveref** to be loaded last:

```
9641 \AtEndPreamble{  
9642 \RequirePackage{cleveref}  
9643 }
```

The following patches are applied after **cleveref** has loaded, and after \AtBeginDocument. Print-mode versions are not required since they all come down to \ref eventually, and \ref has a print-mode version.

```
9644 \AfterEndPreamble{  
9645 \LWR@traceinfo{Patching cleveref.}}
```

\@setceref {<kindofref>} {<label>}

\@templabel becomes the section number.

```
9646 \def\LWR@orig@@@setceref#1#2{\cref@getlabel{#2}{\@templabel}#1{\@templabel}{}{}%  
9647  
9648 \ifdefeq{\@setceref}{\LWR@orig@@@setceref}{% before v0.21  
9649     \renewcommand*{\@setceref}[2]{#1{\ref{#2}}{}{}}  
9650 }{  
9651     \ifdefeq{\@setceref}{\LWR@orig@@@setceref}{% as of v0.21  
9652         \renewcommand*{\@setceref}[2]{#1{\ref{#2}}{}{}}  
9653 }{  
9654     \PackageWarning{l warp-cleveref}{  
9655         Unknown version of cleveref.  
9656         \protect\cref\space will fail.  
9657     }%  
9658 }  
9659 }
```

\@setcrefrange {<text>} {<label>} {<label>}

```
9660 \def\LWR@orig@@@setcrefrange#1#2#3{  
9661     \cref@getlabel{#2}{\@labela}%  
9662     \cref@getlabel{#3}{\@labelb}%  
9663     #1{\@labela}{\@labelb}{}{}{}%  
9664
```

```

9665 \ifdefined{\@setcrefrange}{\LWR@orig@@@setcrefrange}{
9666     \renewcommand{\@setcrefrange}[3]{%
9667         #1{\ref{#2}}{\ref{#3}}{}{}{}%
9668     }
9669 }{
9670     \ifdefined{\@@setcrefrange}{\LWR@orig@@@setcrefrange}{
9671         \renewcommand{\@@setcrefrange}[3]{%
9672             #1{\ref{#2}}{\ref{#3}}{}{}{}%
9673         }
9674     }{
9675         \PackageWarning{l warp-cleveref}{
9676             Unknown version of cleveref.
9677             \protect\crefrange\space will fail.
9678         }
9679     }
9680 }
9681

```

\cpagerefFor Redefinable word between “page(s)” and the page numbers.

```
9682 \newcommand*{\cpagerefFor}{for}
```

\@@@setcpageref {\<typeofref\>} {\<label\>}, where typeofref is “page” or “pages”

```

9683 \def\LWR@orig@@@setcpageref#1#2{%
9684     \cref@getpageref{#2}{\@temppage}#1{\@temppage}{}{}%
9685
9686 \def\LWR@orig@@@setcpageref#1#2{%
9687     \cpageref@getlabel{#2}{\@temppage}#1{\@temppage}{}{}%
9688
9689 \ifdefined{\@setcpageref}{\LWR@orig@@@setcpageref}{
9690     \renewcommand*{\@setcpageref}[2]{%
9691         #1{\cpagerefFor\ \cref{#2}}{}{}%
9692     }
9693 }{
9694     \ifdefined{\@@setcpageref}{\LWR@orig@@@setcpageref}{
9695         \renewcommand*{\@@setcpageref}[2]{%
9696             #1{\cpagerefFor\ \cref{#2}}{}{}%
9697         }
9698     }
9699     {
9700         \PackageWarning{l warp-cleveref}{
9701             Unknown version of cleveref.
9702             \protect\cpageref\space will fail.
9703         }
9704     }
9705 }

```

```

9706 \def\LWR@orig@@setpagerefrange#1#2#3{%
9707   \cref@getpageref{#2}{\@pagea}%
9708   \cref@getpageref{#3}{\@pageb}%
9709   #1{\@pagea}{\@pageb}{\{}{\}{}{\}}%
9710
9711 \def\LWR@orig@@setpagerefrange#1#2#3{%
9712   \cpageref@getlabel{#2}{\@pagea}%
9713   \cpageref@getlabel{#3}{\@pageb}%
9714   #1{\@pagea}{\@pageb}{\{}{\}{}{\}}%
9715
9716 \ifdefequal{\@@setpagerefrange}{\LWR@orig@@setpagerefrange}{%
9717   \renewcommand*{\@@setpagerefrange}[3]{%
9718     #1{\cpagerefFor\ \cref{#2}}{\cref{#3}}{\{}{\}{}{\}}%
9719   }%
9720 }{%
9721   \ifdefequal{\@@setpagerefrange}{\LWR@orig@@setpagerefrange}{%
9722     \renewcommand*{\@@setpagerefrange}[3]{%
9723       #1{\cpagerefFor\ \cref{#2}}{\cref{#3}}{\{}{\}{}{\}}%
9724     }%
9725   }%
9726   {%
9727     \PackageWarning{lwarp-cleveref}{%
9728       Unknown version of cleveref.%
9729       \protect\cpagerefrange\space will fail.%
9730     }%
9731   }%
9732 }%
9733 }% AfterEndPreamble

```

Remember and patch some label-related definitions. These will be further encased and patched by other packages later.

\label and \pageref do NOT change their behavior according to print or HTML output, and thus do not use the \LWR@formatted system.

```

9735 \LetLtxMacro{\LWR@orig@label}{\label}
9736 \RenewDocumentCommand{\label}{\{}{\LWR@new@label\}}
9737
9738 \LetLtxMacro{\LWR@orig@pageref}{\pageref}
9739 \RenewDocumentCommand{\pageref}{\{}{\LWR@new@pageref\}}
9740 \end{warpHTML}

```

85 Picture

Env **picture** The picture environment is enclosed inside a \latextimage.

for HTML output: 9741 \begin{warpHTML}

```
Env  picture
9742 \BeforeBeginEnvironment{picture}{\begin{lateximage}[(picture)]}
9743
9744 \AfterEndEnvironment{picture}{\end{lateximage}}
9745 \end{warpHTML}
```

86 Boxes and Minipages

A css flexbox is used for minipages and parboxes, allowing external and internal vertical positioning.

- ⚠ inline** A line of text with an inline minipage or parbox will have the minipage or parbox placed onto its own line, because a paragraph is a block element and cannot be made `inline-block`.
- placement** Minipages and parboxes will be placed side-by-side in HTML unless you place a `\newline` between them.
- side-by-side** Side-by-side minipages may be separated by `\quad`, `\qquad`, `\enskip`, `\hspace`, `\hfill`, or a `\rule`. When inside a center environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side minipages and these spacing commands, but not at the start or end of the paragraph.
- in a span** There is limited support for minipages inside an HTML ``. An HTML `<div>` cannot appear inside a ``. While in a ``, minipages, and parboxes, and any enclosed lists have limited HTML tags, resulting in an “inline” format, without markup except for HTML breaks. Use `\newline` or `\par` for an HTML break.
- size** When using `\ linewidth`, `\ textwidth`, and `\ textheight`, widths and heights are scaled proportionally to a 6x9 inch text area.
- no-width minipages** A minipage of width exactly `\ linewidth` is automatically given no HTML width.
- full-width minipages** A new macro `\minipagefullwidth` requests that the next minipage be generated without an HTML `width` attribute, allowing it to be the full width of the display rather than the fixed width given.
- ⚠ text alignment** Nested minipages adopt their parent’s text alignment in HTML, whereas in regular L^AT_EX PDF output they do not. Use a `flushleft` or similar environment in the child minipage to force a text alignment.

for HTML output: 9746 \begin{warpHTML}

86.1 Counters and lengths

Ctr LWR@minipagedepth Used to only reset the line width at the outermost minipage.

```
9747 \newcounter{LWR@minipagedepth}  
9748 \setcounter{LWR@minipagedepth}{0}
```

Len \LWR@minipagewidth Used to convert the width into printable units.

```
9749 \newlength{\LWR@minipagewidth}
```

Len \LWR@minipageheight Used to convert the height into printable units.

```
9750 \newlength{\LWR@minipageheight}
```

86.2 Footnote handling

Also see section 56 for other forms of footnotes. Minipage footnotes are gathered in section 56.5, and then placed into the document in section 86.3.

86.3 Minipage handling

Bool LWR@minipagefullwidth Should the next minipage have no HTML width?

```
9751 \newbool{LWR@minipagefullwidth}  
9752 \boolfalse{LWR@minipagefullwidth}
```

\minipagefullwidth Requests that the next minipage have no width tag in HTML:

for HTML output: 9753 \newcommand*{\minipagefullwidth}{\booltrue{LWR@minipagefullwidth}}
9754 \end{warpHTML}

for PRINT output: 9755 \begin{warpprint}
9756 \newcommand*{\minipagefullwidth}{}
9757 \end{warpprint}

for HTML output: 9758 \begin{warpHTML}

Bool LWR@minipagethispar Has a minipage been seen this paragraph? If true, prevents paragraph tags around horizontal space between minipages.

```
9759 \newbool{LWR@minipagethispar}
9760 \boolfalse{LWR@minipagethispar}
```

Env minipage [*vert position*] [*height*] [*inner vert position*] {*width*}

The vertical positions may be 'c', 't', or 'b'. The inner position may also be 's'.

When using `\linewidth`, `\textwidth`, or `\textheight`, these are scaled proportionally to a 6×9 inch text area.

```
9761 \NewDocumentEnvironment{LWR@HTML@minipage}{O{t} o O{t} m}
9762 {%
9763 \LWR@traceinfo{minipage}%
}
```

Temporarily open a group, in which width and height is computed based on a virtual page size instead of the extra-large PDF page used during HTML tag generation.

The following used to be an actual L^AT_EX minipage.

```
9764 \begingroup
```

Compute width, adjusted for frames:

```
9765 \setlength{\LWR@minipagewidth}{#4}%
9766 \ifthenelse{\cnttest{\value{LWR@minipagedepth}}=0}{%
```

Only create a new page if not yet nested:

```
9767 \LWR@orignewpage%
```

Adjust virtual page size:

```
9768 \addtolength{\LWR@minipagewidth}{3em}%
9769 \setlength{\linewidth}{6in}%
9770 \setlength{\textwidth}{6in}%
9771 \setlength{\textheight}{9in}%
9772 }%
9773 \LWR@traceinfo{computed width is \LWR@printlength{\LWR@minipagewidth}}%
```

Compute height:

```
9774 \setlength{\LWR@minipageheight}{\textheight}%
9775 \IfValueT{#2}{\setlength{\LWR@minipageheight}{#2}}%
```

Track nesting depth:

```
9776 \addtocounter{LWR@minipagedepth}{1}%
```

TeX wants to start a paragraph for the virtual minipage, then start a paragraph again for the contents of the minipage, so cancel the paragraph tag handling until the minipage has begun.

```
9777 \ifbool{FormatWP}{\newline}{}
9778 \LWR@stopars%
```

If FormatWP, add a text frame:

```
9779 \ifbool{FormatWP}{%
9780
9781 \addtocounter{LWR@thisautoidWP}{1}%
9782 \LWR@htmlltag{%
9783     div id="\LWR@print@mbox{autoidWP-\arabic{LWR@thisautoidWP}}" %
9784     class="wpminipage"%
9785 }%
9786
9787 }{}}
```

Create the <div> tag with optional alignment style:

```
9788 \LWR@traceinfo{minipage: creating div class}%
9789 \LWR@htmlltag{div class="minipage" style="%"
9790 \ifthenelse{\equal{#1}{t}}{\LWR@print@mbox{vertical-align:bottom} ; }{%
9791 \ifthenelse{\equal{#1}{c}}{\LWR@print@mbox{vertical-align:middle} ; }{%
9792 \ifthenelse{\equal{#1}{b}}{\LWR@print@mbox{vertical-align:top} ; }{%
9793 \ifthenelse{\equal{#3}{t}}{\LWR@print@mbox{justify-content:flex-start} ; }{%
9794 \ifthenelse{\equal{#3}{c}}{\LWR@print@mbox{justify-content:center} ; }{%
9795 \ifthenelse{\equal{#3}{b}}{\LWR@print@mbox{justify-content:flex-end} ; }{%
9796 \ifthenelse{\equal{#3}{s}}{\LWR@print@mbox{justify-content:space-between} ; }{}}}}}}}
```

Print the width and optional height styles:

```
9797 \LWR@traceinfo{minipage: about to print the width of \LWR@printlength{\LWR@minipagewidth}}%
9798 \ifbool{LWR@minipagefullwidth}{%
9799 {\boolefalse{LWR@minipagefullwidth}}%
9800 {%
9801 \ifthenelse{\lengthtest{#4}=\linewidth}{%
9802 {}%
9803 {width:\LWR@printlength{\LWR@minipagewidth} ; }%
9804 }%
9805 \LWR@traceinfo{minipage: about to print the height}%
9806 \IfValueT{#2}{height:\LWR@printlength{\LWR@minipageheight} ; }%
9807 "}}%
```

Finish with an empty line to start the contents on a new line.

```
9808  
9809 % The preceding empty line is required.
```

Set the user-accessible line and text width and height values inside the virtual minipage. These do not affect the actual size of the PDF output, but are used by any reference to \linewidth, etc. inside the virtual minipage being created here.

```
9810 \setlength{\linewidth}{#4}% the original width  
9811 \setlength{\textwidth}{6in}%  
9812 \setlength{\textheight}{9in}%
```

\raggedright cancels hyphenation, which will be done by HTML instead.

```
9813 \LWR@print@raggedright%
```

Set minipage footnotes:

```
9814 \def\@mpfn{mpfootnote}%">  
9815 \def\thempfn{\thempfootnote}\c@mpfootnote\z@%  
9816 \let\@footnotetext\mpfootnotetext%
```

Resume paragraph tag handling for the contents of the minipage:

```
9817 \LWR@startpars%  
9818 \ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{  
9819  
9820 === begin minipage ===  
9821  
9822 }{}%  
9823 \LWR@traceinfo{minipage: finished starting the minipage}%  
9824 }% finished \minipage  
9825 { \endminipage
```

Print pending minipage footnotes:

```
9826 \LWR@printpendingmpfootnotes%
```

End the environment with closing tag:

```
9827 \ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{  
9828  
9829 === end minipage ===  
9830  
9831 }{}%  
9832 \LWR@stopars%
```

The following used to be an actual L^AT_EX minipage.

```

9833 \endgroup%
9834
9835 \ifbool{FormatWP}{%
9836
9837 \LWR@htmlelementend{div}%
9838
9839 }{}%
9840 \LWR@htmldivclassend{minipage}%
9841
9842 \addtocounter{LWR@minipagedepth}{-1}%
9843 \LWR@startpars%
9844 \ifbool{FormatWP}{\newline}{}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```

9845 \global\booltrue{LWR@minipagethispar}%
9846 \LWR@traceinfo{LWR@minipage: done}%
9847 }
9848
9849 \LWR@formattedenv{minipage}
```

86.4 Parbox, mbox, makebox, framebox, fbox, raisebox

for HTML output:

```
\parbox {<pos>} [<height>] [<inner-pos>] {<width>} {<text>}
```

A parbox uses the minipage code:

```

9850 \NewDocumentCommand{\LWR@HTML@parbox}{O{t} o O{t} m +m}
9851 {
9852 \LWR@traceinfo{parbox of width #4}%
9853 \begin{minipage}[#1][#2][#3]{#4}%
9854 #5
9855 \end{minipage}%
9856 }
9857
9858 \LWR@formatted{parbox}
```

\mbox {<text>} Nullified for HTML.

```

9859 \newcommand*{\LWR@HTML@mbox}[1]{#1}
9860
9861 \LWR@formatted{mbox}
```

```
\makebox  (<())posn) [<width>) [<pos>) {<text>}

9862 \NewDocumentCommand{\LWR@HTML@makebox}{d() o o m}{%
```

Check for the optional width:

```
9863 \IfValueTF{#2}%
9864 {%
```

Check for the horizontal text alignment. For stretched, the best HTML can do is justified alignment.

```
9865      {%
9866      \def\LWR@align{center}%
9867      \ifstreq{\#3}{l}{\def\LWR@align{left}}{}%
9868      \ifstreq{\#3}{r}{\def\LWR@align{right}}{}%
9869      \ifstreq{\#3}{s}{\def\LWR@align{justify}}{}%
```

To print the width argument:

```
9870      \setlength{\LWR@tempwidth}{#2}%
```

inline-block allows width and text-align to be used in a .

```
9871      \InlineClass[%
9872          \LWR@print@mbox{display:inline-block} ; %
9873          \LWR@print@mbox{text-align}:\LWR@align\ ; %
9874          width:\LWR@printlength{\LWR@tempwidth}%
9875      ]%
9876      {makebox}%

9877      {#4}%
9878  }% scope
9879 }%
```

Without a width argument, the text is simply used inline:

```
9880 {#4}%
no width
9881 }
9882
9883 \LWR@formatted{makebox}
```

```
\framebox  [<width>) [<pos>) {<text>}
```

```
9884 \LetLtxMacro{\LWR@origframebox}\framebox
9885
```

```

9886 \NewDocumentCommand{\LWR@HTML@framebox}{o o m}{%
9887 \fbox{\makebox[#1][#2]{#3}}%
9888 }%
9889
9890 \LWR@formatted{framebox}

```

\LWR@forceminwidth {*length*}

Sets \LWR@atleastonept to be at least 1pt.

```

9891 \newlength{\LWR@atleastonept}
9892
9893 \newcommand*{\LWR@forceminwidth}[1]{%
9894 \setlength{\LWR@atleastonept}{#1}%
9895 \ifthenelse{%
9896     \lengthtest{\LWR@atleastonept>0pt}\AND%
9897     \lengthtest{\LWR@atleastonept<1pt}%
9898 }%
9899 {\setlength{\LWR@atleastonept}{1pt}}%
9900 {}%
9901 }

```

\LWR@blackborderpadding Prints the HTML attributes for a black border and padding.

\LWR@forceminwidth must be used first in order to set the border width.

```

9902 \newcommand*{\LWR@blackborderpadding}{%
9903 border:\LWR@printlength{\LWR@atleastonept} solid black ; %
9904 padding:\LWR@printlength{\fboxsep}%
9905 }

```

\fbox {*text*}

Creates a framed inline span enclosing the text.

Create a new HTML version, but don't use it until after **xcolor** may have loaded:

```

9906 \newcommand{\LWR@HTML@fbox}[1]{%
9907 \LWR@traceinfo{HTML fbox}%
9908 \LWR@forceminwidth{\fboxrule}%
9909 \InlineClass[%
9910 \LWR@blackborderpadding%
9911 ]{\fbox}{#1}%
9912 }

```

xcolor \lets things to \fbox when it is loaded, and this must remain even for HTML output while in a *lateximage*, so \fbox is not modified until \AtBeginDocument:

```
9913 \AtBeginDocument{\LWR@formatted{fbox}}
```

\fboxBlock {*text*} Creates a framed HTML <div> of the text.

First, a print-mode version. This is newly defined for print mode, so it is defined inside `warpall`.

for HTML & PRINT: 9914 \end{warpHTML}
9915 \begin{warpall}
9916 \let\fboxBlock\fbox
9917 \end{warpall}
9918 \begin{warpHTML}

for HTML output: Next, an HTML version:

```
9919 \newcommand{\LWR@HTML\fboxBlock}[1]{%  
9920 \LWR@forceminwidth{\fboxrule}-%  
9921 \begin{BlockClass}-%  
9922 \LWR@blackborderpadding-%  
9923 ]\fboxBlock  
9924 #1  
9925 \end{BlockClass}  
9926 }  
9927  
9928 \LWR@formatted{fboxBlock}  
9929  
9930 \end{warpHTML}
```

Env fminipage [*align*] [*height*] [*align*] {*width*}

Creates a framed HTML <div> around its contents.

for HTML & PRINT: Print version:

```
9931 \begin{warpall}  
9932  
9933 \newsavebox{\LWR@fminipagebox}  
9934  
9935 \NewDocumentEnvironment{\LWR@print\fminipage}{O{t} O{t} m}  
9936 {%
```

An outer minipage will be used for vertical alignment. An inner minipage will be framed with `\fbox`.

If the optional inner alignment is not given, use the outer instead:

```
9937 \IfValueTF{#3}{%  
9938 {\def\LWR@thisalign{#3}}%  
9939 {\def\LWR@thisalign{#1}}%
```

Form the outer minipage depending on whether a height was given. Make the outer minipage larger to compensate for the frame.

```
9940 \IfValueTF{#2}%
9941 {\minipage[#1][#2+2\fboxsep+2\fboxrule]{\LWR@thisalign}{#4+2\fboxsep+2\fboxrule}}%
9942 {\minipage[#1]{#4+2\fboxsep+2\fboxrule}}%
```

Capture the contents of the environment:

```
9943 \begin{lrbox}{\LWR@fminipagebox}%
```

Nest the contents inside an inner minipage of the desired size:

```
9944 \IfValueTF{#2}%
9945 {\minipage[#1][#2]{\LWR@thisalign}{#4}}%
9946 {\minipage[#1]{#4}}%
9947 }%
9948 {%
```

Close the inner minipage and the LR box with the contents:

```
9949 \endminipage%
9950 \end{lrbox}%
```

Create a frame around the contents of the environment:

```
9951 \fbox{\usebox{\LWR@fminipagebox}}%
```

The entire thing is placed inside the outer minipage:

```
9952 \endminipage%
9953 }%
9954
9955 \newenvironment{fminipage}{\LWR@print@fminipage}{\endLWR@print@fminipage}
9956
9957 \end{warpall}
```

for HTML output: 9958 \begin{fminipageHTML}

```
9959
9960 \NewDocumentEnvironment{\LWR@HTML@fminipage}{O{t} o O{t} m}
9961 {%
9962 \LWR@traceinfo{fminipage #1 #2 #3 #4}%
9963 \LWR@forceminwidth{\fboxrule}%
9964 \setlength{\LWR@tempwidth}{#4}%
9965 \IfValueT{#2}{\setlength{\LWR@tempheight}{#2}}%
9966 \begin{BlockClass}[%
```

```
9967 \LWR@blackborderpadding ; %
9968 \IfValueT{#2}{height:\LWR@printlength{\LWR@tempheight} ; }%
```

```

9969 width:\LWR@printlength{\LWR@tempwidth}%
9970 ]{fminipage}%
9971 }%
9972 {%
9973 \end{BlockClass}%
9974 \LWR@traceinfo{fminipage done}%
9975 }%
9976
9977 \LWR@formattedenv{fminipage}

9978 \end{warpHTML}

\raisebox  {\raiselen} [height] [depth] {text}

9979 \begin{warpHTML}
9980
9981 \NewDocumentCommand{\LWR@HTML@raisebox}{m o o m}{%
9982 #4%
9983 }
9984
9985 \LWR@formatted{raisebox}

9986 \end{warpHTML}

```

87 Direct formatting

- ⚠ **\bfseries, etc.** \textbf{, etc. are supported, but \bfseries, etc. work only in some situations.}
 - ⚠ **HTML special chars** &, <, and > have special meanings in HTML. If \&, \textless, and \textgreater are used, proper HTML entities will be used, but there may be HTML parsing problems if these special characters occur unescaped in program listings or other verbatim text.
 - program listings** For program listings, the **listings** package is supported, and its `literate` option is used to convert &, <, and > to proper HTML entities.
 - verbatim** The various `verbatim`-related environments do not convert &, <, and >, so care must be taken to avoid accidentally including valid HTML code inside these environments. Adding a space on either side may be sufficient.
- For high-level block and inline custom CSS classes, see section 50.8.
- for HTML output:** 9987 \begin{warpHTML}

```
\LWR@HTMLtextstyle {\FormatWP style} {\class} {\text}
```

If FormatWP, adds an explicit style to the text span class. This is used by LIBREOFFICE to mark its imported text using the given style.

```
9988 \DeclareRobustCommand{\LWR@HTMLtextstyle}[3]{%
9989 \ifbool{FormatWP}{%
9990 {\LWR@htmlspanclass[#1]{#2}{#3}}{%
9991 {\LWR@htmlspanclass[#2]{#3}}{%
9992 }}

\emph {⟨text⟩}

9993 \DeclareRobustCommand{\LWR@HTMLemph}[1]{\LWR@htmlspan{em}{#1}}
9994 \DeclareRobustCommand{\LWR@nullemph}[1]{#1}
9995 \LetLtxMacro{\emph}{\LWR@HTMLemph}

{textmd} {⟨text⟩}

9996 \DeclareRobustCommand{\LWR@HTMLtextmd}[1]{%
9997 {\LWR@HTMLtextstyle{font-weight: normal}{textmd}{#1}}{%
9998 }%
9999 \DeclareRobustCommand{\LWR@nulltextmd}[1]{#1}
10000
10001 \LetLtxMacro{\textmd}{\LWR@HTMLtextmd}

{textbf} {⟨text⟩}

10002 \DeclareRobustCommand{\LWR@HTMLtextbf}[1]{\LWR@htmlspan{b}{#1}}
10003 \DeclareRobustCommand{\LWR@nulltextbf}[1]{#1}
10004 \LetLtxMacro{\textbf}{\LWR@HTMLtextbf}

{textrm} {⟨text⟩}

10005 \DeclareRobustCommand{\LWR@HTMLtextrm}[1]{%
10006 {\LWR@HTMLtextstyle{font-family: serif}{textrm}{#1}}{%
10007 }%
10008
10009 \DeclareRobustCommand{\LWR@nulltextrm}[1]{#1}
10010
10011 \LetLtxMacro{\textrm}{\LWR@HTMLtextrm}

{textsf} {⟨text⟩}

10012 \DeclareRobustCommand{\LWR@HTMLtextsf}[1]{%
10013 {\LWR@HTMLtextstyle{font-family: sans}{textsf}{#1}}{%
10014 }%
10015 \DeclareRobustCommand{\LWR@nulltextsf}[1]{#1}
10016 \LetLtxMacro{\textsf}{\LWR@HTMLtextsf}
```

```
\texttt {⟨text⟩}

10017 \DeclareRobustCommand{\LWR@HTMLtexttt}[1]{\LWR@htmlspan{kbd}{#1}}
10018 \DeclareRobustCommand{\LWR@nulltexttt}[1]{#1}
10019 \LetLtxMacro\texttt{\LWR@HTMLtexttt}

\textup {⟨text⟩}

10020 \DeclareRobustCommand{\LWR@HTMLtextup}[1]{%
10021 \LWR@HTMLtextstyle{font-variant:normal}{textup}{#1}%
10022 }
10023
10024 \DeclareRobustCommand{\LWR@nulltextup}[1]{#1}
10025
10026 \LetLtxMacro\textup{\LWR@HTMLtextup}

\textit {⟨text⟩}

10027 \DeclareRobustCommand{\LWR@HTMLtextit}[1]{\LWR@htmlspan{i}{#1}}
10028 \DeclareRobustCommand{\LWR@nulltextit}[1]{#1}
10029 \LetLtxMacro\textit{\LWR@HTMLtextit}

\textsc {⟨text⟩}

10030 \DeclareRobustCommand{\LWR@HTMLtextsc}[1]{%
10031 \LWR@HTMLtextstyle{font-variant:small-caps}{textsc}{#1}%
10032 }
10033
10034 \DeclareRobustCommand{\LWR@nulltextsc}[1]{#1}
10035
10036 \LetLtxMacro\textsc{\LWR@HTMLtextsc}

\textsl {⟨text⟩}

10037 \DeclareRobustCommand{\LWR@HTMLtextsl}[1]{%
10038 \LWR@HTMLtextstyle{font-style:oblique}{textsl}{#1}%
10039 }
10040
10041 \DeclareRobustCommand{\LWR@nulltextsl}[1]{#1}
10042
10043 \LetLtxMacro\textsl{\LWR@HTMLtextsl}

\textnormal {⟨text⟩}

10044 \DeclareRobustCommand{\LWR@HTMLtextnormal}[1]{\textmd{\textrm{\textup{#1}}}}
10045 \DeclareRobustCommand{\LWR@nulltextnormal}[1]{#1}
10046 \LetLtxMacro\textnormal{\LWR@HTMLtextnormal}
```

```

10047 \DeclareRobustCommand{\LWR@nullrmfamily}{}
10048 \DeclareRobustCommand{\LWR@nullsffamily}{}
10049 \DeclareRobustCommand{\LWR@nullttfamily}{}
10050 \DeclareRobustCommand{\LWR@nullbfseries}{}
10051 \DeclareRobustCommand{\LWR@nullmdseries}{}
10052 \DeclareRobustCommand{\LWR@nullupshape}{}
10053 \DeclareRobustCommand{\LWR@nullslshape}{}
10054 \DeclareRobustCommand{\LWR@nullscshape}{}
10055 \DeclareRobustCommand{\LWR@nullitshape}{}
10056 \DeclareRobustCommand{\LWR@nullem}{[1]{}}
10057 \DeclareRobustCommand{\LWR@nullnormalfont}{}

```

\LWR@nullfonts Removes formatting during filename operations.



Use only inside a group.

The following are *not* made robust, since they must be expanded to their nullified versions.

```

10058 \newcommand*{\LWR@nullfonts}{%
10059 \LetLtxMacro\emph{\LWR@nullemph}%
10060 \LetLtxMacro{textmd}{\LWR@nulltextmd}%
10061 \LetLtxMacro{textbf}{\LWR@nulltextbf}%
10062 \LetLtxMacro{textrm}{\LWR@nulltextrm}%
10063 \LetLtxMacro{textsf}{\LWR@nulltextsf}%
10064 \LetLtxMacro{texttt}{\LWR@nulltexttt}%
10065 \LetLtxMacro{textup}{\LWR@nulltextup}%
10066 \LetLtxMacro{textit}{\LWR@nulltextit}%
10067 \LetLtxMacro{textsc}{\LWR@nulltextsc}%
10068 \LetLtxMacro{textsl}{\LWR@nulltextsl}%
10069 \LetLtxMacro{textnormal}{\LWR@nulltextnormal}%
10070 \LetLtxMacro{rmfamily}{\LWR@nullrmfamily}%
10071 \LetLtxMacro{sffamily}{\LWR@nullsffamily}%
10072 \LetLtxMacro{ttfamily}{\LWR@nullttfamily}%
10073 \LetLtxMacro{bfseries}{\LWR@nullbfseries}%
10074 \LetLtxMacro{mdseries}{\LWR@nullmdseries}%
10075 \LetLtxMacro{upshape}{\LWR@nullupshape}%
10076 \LetLtxMacro{slshape}{\LWR@nullslshape}%
10077 \LetLtxMacro{scshape}{\LWR@nullscshape}%
10078 \LetLtxMacro{itshape}{\LWR@nullitshape}%
10079 \LetLtxMacro{em}{\LWR@nullem}%
10080 \LetLtxMacro{normalfont}{\LWR@nullnormalfont}%

10081 \renewcommand*{\,}{-}%
10082 \renewcommand*{-}{-}%
10083 \renewcommand*{\newline}{ }%
10084 \renewcommand*{\textellipsis}{-}%

```

```
10085 \renewcommand*{\HTMLunicode}[1]{-}%
10086 \renewcommand*{\HTMLentity}[1]{-}%
```

Ampersand becomes “and”, which is a short word and is then removed from the filename.

```
10087 \renewcommand*{\&}{and}%
10088 \renewcommand{\textsuperscript}[1]{##1}%
10089 \renewcommand{\textsubscript}[1]{##1}%
10090 \renewcommand{\underline}[1]{##1}%
10091 \RenewDocumentCommand{\LWR@htmlspanclass}{o m +m}{##3}%
10092 \DeclareExpandableDocumentCommand{\InlineClass}{+o +m +m}{##3}%
10093 \DeclareRobustCommand{\LWR@HTMLtextstyle}[3]{##3}%
```

Nullify math macros.

```
10094 \def\(##1\){}%
10095 \def\[##1\]{}%
10096 \RenewDocumentCommand{\LWR@subsingle dollar}{s m m m}{}
```

Use the simpler form with `\texorpdfstring`:

```
10097 \let\texorpdfstring\relax%
10098 \newcommand{\texorpdfstring}[2]{##2}%
10099 }
```

Remembers the current font family, series, and shape.

```
10100 \newcommand*{\LWR@f@family}{rm}%
10101 \newcommand*{\LWR@f@series}{md}%
10102 \newcommand*{\LWR@f@shape}{up}
```

```
\LWR@textcurrentfont {<text>}
```

Prints the text with the current font choices.

```
10103 \newcommand*{\LWR@textcurrentfont}[1]{%
10104 \InlineClass{%
10105     text\LWR@f@family\LWR@origtilde{}%
10106     text\LWR@f@series\LWR@origtilde{}%
10107     text\LWR@f@shape%
10108 }%
10109 {##1}%
10110 }
```

Env LWR@blocktextcurrentfont Prints the contents with the current font choices.

```
10111 \newenvironment*{LWR@blocktextcurrentfont}{%
10112 \BlockClass{%
10113     text\LWR@f@family\LWR@origtilde{}%
10114     text\LWR@f@series\LWR@origtilde{}%
10115     text\LWR@f@shape%
10116 }%
10117 }{\endBlockClass}

\mdseries
10118 \renewrobustcmd*{\mdseries}{\renewcommand*{\LWR@f@series}{md}}

\bfseries
10119 \renewrobustcmd*{\bfseries}{\renewcommand*{\LWR@f@series}{bf}}

\rmfamily
10120 \renewrobustcmd*{\rmfamily}{\renewcommand*{\LWR@f@family}{rm}}

\sffamily
10121 \renewrobustcmd*{\sffamily}{\renewcommand*{\LWR@f@family}{sf}}

\ttfamily
10122 \renewrobustcmd*{\ttfamily}{\renewcommand*{\LWR@f@family}{tt}}

\upshape
10123 \renewrobustcmd*{\upshape}{\renewcommand*{\LWR@f@shape}{up}}

\itshape
10124 \renewrobustcmd*{\itshape}{\renewcommand*{\LWR@f@shape}{it}}

\scshape
10125 \renewrobustcmd*{\scshape}{\renewcommand*{\LWR@f@shape}{sc}}
```

```
\normalfont
```

```
10126 \renewrobustcmd*{\normalfont}{\rmfamily\mdseries\upshape}
```

```
\sp {<text>}
```

For **siunitx**. Must work in math mode.

```
10127 \renewcommand{\sp}[1]{\text{\sup{#1}}{}}
```

```
\sb {<text>}
```

For **siunitx**. Must work in math mode.

```
10128 \renewcommand{\sb}[1]{\text{\sub{#1}}{}}
```

```
\textsuperscript {<text>}
```

```
10129 \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}
```

```
\textsuperscript {<text>}
```

```
10130 \renewcommand{\textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}
```

```
\textsubscript {<text>}
```

```
10131 \AtBeginDocument{  
10132 \renewrobustcmd{\textsubscript}[1]{\LWR@htmlspan{sub}{#1}}  
10133 }
```

```
\textsubscript {<text>}
```

```
10134 \AtBeginDocument{  
10135 \renewcommand{\textsubscript}[1]{\LWR@htmlspan{sub}{#1}}  
10136 }
```

```
\up {<text>} Prints superscript.
```

This is \let at the beginning of the document in case some other package has changed the definition.

```
10137 \AtBeginDocument{\let\up\textsuperscript}
```

\fup {*text*} Prints superscript.

Supports **fmtcount** package.

This is \let at the beginning of the document in case some other package has changed the definition.

```
10138 \AtBeginDocument{\let\fup\textsuperscript}
```

\underline {*text*}

```
10139 \renewcommand{\underline}[1]{%
10140 \LWR@HTMLtextstyle{%
10141   {text-decoration:underline; text-decoration-skip: auto}%
10142   {\underline}{#1}%
10143 }
```

\LWR@overline {*text*}

```
10144 \newcommand{\LWR@overline}[1]{%
10145 \LWR@HTMLtextstyle{%
10146   {text-decoration:overline; text-decoration-skip: auto}%
10147   {\overline}{#1}%
10148 }
```

\LWR@currenttextcolor The color to use for text and \rule, defaulting to black:

```
10149 \newcommand*{\LWR@currenttextcolor}{black}
```

\LWR@tempcolor The color converted to HTML colorspace.

```
\LWR@tempcolortwo
10150 \newcommand*{\LWR@tempcolor}{}%
10151 \newcommand*{\LWR@tempcolortwo}{}%
```

\LWR@findcurrenttextcolor Sets \LWR@tempcolor to the current color.

```
10152 \newcommand*{\LWR@findcurrenttextcolor}{}%
10153 \renewcommand{\LWR@tempcolor}{black}%
10154 }
```

\LWR@textcurrentcolor {*text*} Like \textcolor but uses the current \color instead.

```
10155 \NewDocumentCommand{\LWR@textcurrentcolor}{m}{%
10156   \renewcommand*{\LWR@currenttextcolor}{black}%
10157   #1%
10158 }
```

```
10159 \end{warpHTML}
```

88 Skips, spaces, font sizes

for HTML output:

```
10160 \begin{warpHTML}  
\, and \thinspace may be redefined by other packages, so are redefined \AtBeginDocument here.
```

Direct-formatting space commands become HTML entities:

```
10161 \AtBeginDocument{  
10162 \renewrobustcmd*{\,}{\HTMLUnicode{202f}} % HTML thin non-breakable space  
10163 \renewrobustcmd*{\thinspace}{\HTMLUnicode{202f}} % HTML thin non-breakable space  
10164 \renewrobustcmd*{\negthinspace}{\HTMLUnicode{202f}} % HTML thin non-breakable space  
10165 \renewrobustcmd*{\~}{\HTMLEntity{nbsp}}  
10166 \renewrobustcmd*{\textellipsis}{\HTMLUnicode{2026}}  
10167 }
```

Direct-formatting font sizes are ignored:

```
10168 \newrobustcmd*{\LWR@HTML@normalsize}{}  
10169 \LWR@formatted{normalsize}  
10170  
10171 \newrobustcmd*{\LWR@HTML@small}{}  
10172 \LWR@formatted{small}  
10173  
10174 \newrobustcmd*{\LWR@HTML@footnotesize}{}  
10175 \LWR@formatted{footnotesize}  
10176  
10177 \newrobustcmd*{\LWR@HTML@scriptsize}{}  
10178 \LWR@formatted{scriptsize}  
10179  
10180 \newrobustcmd*{\LWR@HTML@tiny}{}  
10181 \LWR@formatted{tiny}  
10182  
10183 \newrobustcmd*{\LWR@HTML@large}{}  
10184 \LWR@formatted{large}  
10185  
10186 \newrobustcmd*{\LWR@HTML@Large}{}  
10187 \LWR@formatted{Large}  
10188  
10189 \newrobustcmd*{\LWR@HTML@LARGE}{}  
10190 \LWR@formatted{LARGE}  
10191  
10192 \newrobustcmd*{\LWR@HTML@huge}{}  
10193
```

```
10193 \LWR@formatted{huge}
10194
10195 \newrobustcmd*\{\LWR@HTML@Huge\}{}
10196 \LWR@formatted{Huge}

10197 \DeclareDocumentCommand{\onecolumn}{}
10198 \DeclareDocumentCommand{\twocolumn}{O{}}
10200
10201 #1
10202
10203 }

\hfill

10204 \newcommand*\{\LWR@HTML@hfill\}{\qquad}
10205 \LWR@formatted{hfill}

\hrulefill

10206 \newcommand*\{\LWR@HTML@hrulefill\}{\rule{1in}{1pt}}
10207 \LWR@formatted{hrulefill}

\dotfill

10208 \newcommand*\{\LWR@HTML@dotfill\}{\dots}
10209 \LWR@formatted{dotfill}

\newpage

10210 \renewcommand*\{\newpage\}%
10211
10212 }

\newline Uses the HTML <br /> element.

10213 \newrobustcmd*\{\LWR@newlinebr\}{\unskip\LWR@htmltag{br /}\LWR@orignewline\%}
10214 \LetLtxMacro{\newline}{\LWR@newlinebr}

\\ Redefined to \LWR@endofline or \LWR@tabularendofline.

\LWR@endofline * [<len>]
\\ is assigned to \LWR@endofline at \LWR@LwarpStart.
```

Inside tabular, \\ is temporarily changed to \LWR@tabularendofline.

```
10215 \LetLtxMacro{\LWR@origendofline}\\
10216 \NewDocumentCommand{\LWR@endofline}{s o}%
10217 {%
10218 \newline%
10219 }
```

- \LWR@minipagestartpars Minipages are often placed side-by-side inside figures, with a bit of horizontal space to separate them. Since HTML does not allow a <div> to be inside a p, paragraphs must be turned off during the generation of the minipage, then turned on after the minipage is complete. When this occurs between side-by-side minipages, l warp correctly suppresses the paragraph tags between the minipages, unless some other text is between the minipages. Such text forms its own paragraph, resulting in text after a minipage to be on its own line. Since people often place small horizontal space between minipages, it is desirable to maintain this space if possible. l warp tries to do this by remembering that a minipage has been seen, in which case paragraph tags are suppressed around \hspace, \enskip, \quad, and \quad until the end of the paragraph, when the closing p tag is created.

When a minipage is seen, the boolean LWR@minipagethispar is set, telling the following horizontal whitespace commands to try to suppress their surrounding paragraph tags. LWR@minipagethispar is cleared at the next end of paragraph, when the HTML paragraph closing tag is generated.

Placed just before \hspace, \quad, or \quad's HTML output.

```
10220 \newcommand*{\LWR@minipagestartpars}{%
10221 \ifbool{\LWR@minipagethispar}{\LWR@startpars}{()}%
10222 }
```

- \LWR@minipagestoppars Placed just after \hspace, \quad, or \quad's HTML output.

```
10223 \newcommand*{\LWR@minipagestoppars}{%
10224 \ifbool{\LWR@minipagethispar}{\LWR@stoppars}{()}%
10225 }
```

\quad Handles special minipage & horizontal space interactions.

```
10226 \renewcommand*{\quad}{%
10227 \LWR@minipagestoppars%
10228 \HTMLunicode{2001}%
10229 \LWR@minipagestartpars%
10230 }
```

\qquad Handles special minipage & horizontal space interactions.

```
10231 \renewcommand*{\qquad}{\quad\quad}
```

\enskip Handles special minipage & horizontal space interactions.

```
10232 \renewcommand*{\enskip}{%
10233 \LWR@minipagestopars%
10234 \HTMLunicode{2000}%
10235 \LWR@minipagestartpars%
10236 }
```

Len \LWR@tempwidth Used to compute span width, height, raise for \hspace and \rule:

```
Len \LWR@tempheight
Len \LWR@tempraise 10237 \newlength{\LWR@tempwidth}
10238 \newlength{\LWR@tempheight}
10239 \newlength{\LWR@tempraise}
```

\LWR@select@html@hspace * {\langle length \rangle} * {\langle length \rangle}
\hspace

Handles special minipage & horizontal space interactions.

Prints a span of a given width. Ignores the optional star.

\hspace{\fill} is converted to \hspace{2em}, equal to \qquad.

```
10240 \newcommand{\LWR@select@html@hspace}{%
10241 \RenewDocumentCommand{\hspace}{s m}{%
10242 \setlength{\LWR@tempwidth}{##2}}%
```

If \fill, change to \qquad:

```
10243 \ifnum\gluestretchorder\LWR@tempwidth>0%
10244 \setlength{\LWR@tempwidth}{2em}%
10245 \fi%
```

Only if the width is not zero:

```
10246 \ifdimcomp{\LWR@tempwidth}{=}{0pt}{}
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
10247 \LWR@minipagestopars%
```

Support the HTML thin wrappable space:

```

10248     \ifdimcomp{\LWR@tempwidth}{=}{.16667em}%
10249     {%
10250         \HTMLunicode{2009}% thin breakable space
10251     }%

```

Print the span with the converted width. Not rounded.

```

10252     {%
10253         \LWR@htmlltagc{%
10254             span style="width:\LWR@printlength{\LWR@tempwidth}; % extra space
10255             display:inline-block"%
10256         }%

```

If formatting for a word processor, approximate with a number of \quads, in case a span of a given width is not supported:

```

10257     \ifbool{FormatWP}{%
10258         \setlength{\LWR@templengthone}{\LWR@tempwidth}%
10259         \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
10260             \quad\%
10261             \addtolength{\LWR@templengthone}{-1em}%
10262         }%
10263     }{%

```

Close the span:

```

10264         \LWR@htmlltagc{/span}%
10265     }%

```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```

10266     \LWR@minipagestartpars%
10267 }% width not 0
10268 }%
10269 }

```

```

\LWR@select@html@nohspase * {<length>}
\hspase Used to disable \hspase while creating description \items.

```

```

10270 \newcommand{\LWR@select@html@nohspase}{%
10271     \RenewDocumentCommand{\hspase}{s m}{%
10272 }

```

```
\LWR@select@print@hspase
```

```
10273 \newcommand*{\LWR@select@print@hspace}{%
10274     \renewrobustcmd\hspace{\@ifstar\@hspacer\@hspace}%
10275 }

\hspace * {<length>}
```

Handles special minipage & horizontal space interactions.

```
10276 \LWR@select@html@hspace
```

\LWR@vspace * {<length>} Nullified vspace.

```
10277 \NewDocumentCommand{\LWR@HTML@vspace}{s m}{}
10278
10279 \LWR@formatted{vspace}
```

\linebreak [<num>] Inserts an HTML br tag.

```
10280 \renewcommand*{\linebreak}[1][]{\newline}
```

\nolinebreak [<num>]

```
10281 \renewcommand*{\nolinebreak}[1][]{}
```

\pagebreak [<num>] Starts a new paragraph.

```
10282 \renewcommand*{\pagebreak}[1][]{}
10283
10284 }
```

\nopagebreak [<num>]

```
10285 \renewcommand*{\nopagebreak}[1][]{}
```

\enlargethispage * {<len>}

```
10286 \RenewDocumentCommand{\enlargethispage}{s m}{}

\clearpage
\cleardoublepage
10287 \renewcommand*{\clearpage}{}%
10288 \renewcommand*{\cleardoublepage}{}%
```

```
\rule [⟨raise⟩] {⟨width⟩} {⟨height⟩}
```

Handles special minipage & horizontal space interactions.

Creates a span of a given width and height. Ignores the optional star.

\fill is zero-width, so \hspace{\fill} is ignored.

```
10289 \newcommand*{\LWR@HTML@rule}[3] []{%
```

The width is copied into a temporary \TeX length, from which comparisons and conversions may be made:

```
10290 \setlength{\LWR@tempwidth}{#2}%
```

If it's zero-width then skip the entire rule:

```
10291 \ifthenelse{\lengthtest{\LWR@tempwidth=0pt}}%
10292 {}% zero- width
10293 {}% non-zero width
```

If it's non-zero width, set a minimal thickness so that it more reliably shows in the browser:

```
10294 \ifthenelse{%
10295   \lengthtest{\LWR@tempwidth>0pt}\AND%
10296   \lengthtest{\LWR@tempwidth<1pt}%
10297 }%
10298 {\setlength{\LWR@tempwidth}{1pt}}%
```

Likewise with height:

```
10299 \setlength{\LWR@tempheight}{#3}%
10300 \ifthenelse{%
10301   \lengthtest{\LWR@tempheight>0pt}\AND%
10302   \lengthtest{\LWR@tempheight<1pt}%
10303 }%
10304 {\setlength{\LWR@tempheight}{1pt}}%
```

If had a minipage this paragraph, try to inline the rule without generating paragraph tags:

```
10305 \LWR@minipagestopars%
```

Print the span with the converted width and height. The width and height are NOT rounded, since a height of less than 1pt is quite common in \TeX code.

```
10306 \LWR@findcurrenttextcolor%
```

```
10307      \LWR@htmlltagc{%
10308      span
10309      style=""%
```

The background color is used to draw the filled rule. The color may be changed by `\textcolor`.

```
10310      \ifbool{FormatWP}{}{\background:\LWR@currenttextcolor ; }%
```

The width and height are printed, converted to PT:

```
10311      width:\LWR@printlength{\LWR@tempwidth} ; %
10312      height:\LWR@printlength{\LWR@tempheight} ; %
```

The raise height is converted to a css transform. The *2 raise multiplier is to approximately match HTML output's X height. Conversion to a \TeX length allows a typical \TeX expression to be used as an argument for the raise, whereas printing the raise argument directly to HTML output without conversion to a \TeX length limits the allowable syntax. To do: A superior method would compute a ratio of \TeX ex height, then print that to HTML with an ex unit.

```
10313      \ifblank{#1}%
10314      {}%
10315      {%
10316          \setlength{\LWR@tempraise}{\Opt{-#1}}%
10317          \setlength{\LWR@tempraise}{\LWR@tempraise*2}%
10318          \LWR@orignewline%
10319          -ms-transform: translate(\Opt,\LWR@printlength{\LWR@tempraise}); %
10320          \LWR@orignewline%
10321          -webkit-transform: translate(\Opt,\LWR@printlength{\LWR@tempraise}); %
10322          \LWR@orignewline%
10323          transform: translate(\Opt,\LWR@printlength{\LWR@tempraise}); %
10324          \LWR@orignewline%
10325      }%
```

Display inline-block to place the span inline with the text:

```
10326      display:inline-block;"%
10327      }%
```

If formatting for a word processor, approximate with a number of underscores, in case a span of a given width is not supported:

```
10328      \ifbool{FormatWP}{}%
10329          \setlength{\LWR@templengthone}{\LWR@tempwidth}%
10330          \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
10331              \_{}%
10332              \addtolength{\LWR@templengthone}{-1em}%
}
```

```
10333 }%
10334 }{ }%
```

Close the span:

```
10335 \LWR@htmltagc{/span}%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
10336 \LWR@minipagestartpars%
10337 }% non-zero width
10338 }
10339
10340 \LWR@formatted{rule}

10341 \end{warpHTML}
```

89 \phantomsection

for HTML output: 10342 \begin{warpHTML}

\phantomsection Emulate the **hyperref** \phantomsection command, often used to insert the bibliography into the table of contents. Ignores \ForceHTMLTOC.

```
10343 \DeclareDocumentCommand{\phantomsection}{}
10344 \begingroup%
10345 \boolfalse{LWR@forcinghtmltoc}%
10346 \section*{}%
10347 \endgroup%
10348 }

10349 \end{warpHTML}
```

90 \LaTeX and other logos

Logos for HTML and print modes:

Some of these logos may be redefined in a later package, so after loading other packages, and at the beginning of the document, their definitions are finally \let in \LWR@LwarpStart.

For css conversions, see:

<http://edward.oconnor.cx/2007/08/tex-poshlet>

<http://nitens.org/taraborelli/texlogo>

90.1 HTML logos

for HTML output: 10350 \begin{warpHTML}

\TeX \TeX

latexlogo is a css class used to properly typeset the E and A in \TeX and friends.

latexlogofont is a css class used to select the font for the rest of the logo in \TeX, LuaTeX, ConTeXt, etc.

```
10351 \let\LWR@origTeX\TeX
10352
10353 \newcommand*\{\LWR@TeX}
10354 {%
10355   \InlineClass{latexlogofont}%
10356   {%
10357     \LWR@HTMLtextstyle%
10358     {text-transform:uppercase}%
10359     {latexlogo}%
10360     {T\textsubscript{e}X}%
10361   }%
10362 }
```

\LaTeX \TeX, \TeX2 ε

\LaTeXe

```
10363 \let\LWR@origLaTeX\LaTeX
10364
10365 \newcommand*\{\LWR@LaTeX}
10366 {%
10367   \InlineClass{latexlogofont}%
10368   {%
10369     \LWR@HTMLtextstyle%
10370     {text-transform:uppercase}%
10371     {latexlogo}%
10372     {L\textsuperscript{a}T\textsubscript{e}X}%
10373   }%
10374 }
10375
10376 \let\LWR@origLaTeXe\LaTeXe
10377
10378 \renewcommand*\{\LaTeXe}
```

```
10379 {\LaTeX\InlineClass{latexlogofont}%
10380 {\textsubscript{\textit{\HTMLunicode{3B5}}}}}}
```

\LuaTeX \LuaTeX, \LuaTeX
 \LuaLaTeX
 10381 \newcommand*{\LWR@LuaTeX}{\InlineClass{latexlogofont}{\Lua}\TeX}
 10382 \newcommand*{\LWR@LuaLaTeX}{\InlineClass{latexlogofont}{\Lua}\LaTeX}

\XeTeX \XeTeX, \XeTeX
 \XeLaTeX
 xetexlogo is a css class which aligns the backwards E in \XeTeX and spaces \TeX appropriately.

xelatexlogo is a css class which aligns the backwards E in \XeTeX and spaces \TeX appropriately.

```
10383 \newcommand*{\Xe}%
10384 {X\textsubscript{\HTMLunicode{18e}}}%
10385 \newcommand*{\LWR@XeTeX}{\InlineClass{xetexlogo}{\Xe}\TeX}%
10386 \newcommand*{\LWR@XeLaTeX}{\InlineClass{xelatexlogo}{\Xe}\LaTeX}
```

\ConTeXt \ConTeXt

```
10387 \newcommand*{\LWR@ConTeXt}%
10388 {\InlineClass{latexlogofont}{\Con}\TeX{}%}
10389 \InlineClass{latexlogofont}{\tt}
```

\BibTeX \BIBTeX, *MakeIndex*
 \MakeIndex
 10390 \providecommand*{\BibTeX}%
 10391 {\InlineClass{latexlogofont}{\B\textsc{ib}}\TeX}%
 10392
 10393 \newcommand*{\MakeIndex}%
 10394 {\InlineClass{latexlogofont}{\textit{\MakeIndex}}}

\AmS \AMS

amslogo is a css class used for the \AMS logo.

```
10395 \AtBeginDocument{\DeclareDocumentCommand{\AmS}{}%
10396 {\InlineClass{amslogo}{\textit{\A\textsubscript{\M}S}}}}
```

\MiKTeX \MiKTeX

```
10397 \newcommand*{\MiKTeX}{\InlineClass{latexlogofont}{\MiK}\TeX}
```

\LyX \LyX

lyxlogo is a css class used for the LyX logo.

```
10398 \newcommand*{\LyX}{\InlineClass{lyxlogo}{LyX}}
```

```
10399 \end{warpHTML}
```

90.2 Print logos

for PRINT output:

```
10400 \begin{warpprint}
10401 \newcommand*{\XeTeXrevE}
10402   {\hspace{-.1667em}\raisebox{-.5ex}{\reflectbox{E}}\hspace{-.125em}}
10403 \providecommand*{\XeTeX}{\mbox{X\XeTeXrevE\TeX}}
10404 \providecommand*{\XeLaTeX}{\mbox{X\XeTeXrevE\LaTeX}}
10405 \providecommand*{\AmS}{%
10406 \leavevemode\hbox{$\mathcal A\kern-.2em\lower.376ex\%$}
10407 \hbox{$\mathcal M$\kern-.2em$\mathcal S$}}
10408 \newcommand*{\LyX}{\textsf{LyX}}
10409 \providecommand*{\LuaTeX}{\mbox{Lua\TeX}}
10410 \providecommand*{\LuaLaTeX}{\mbox{Lua\LaTeX}}
10411 \providecommand*{\BibTeX}{\mbox{B\textsc{it}\TeX}}
10412 \providecommand*{\MakeIndex}{\mbox{\textit{MakeIndex}}}
10413 \providecommand*{\ConTeXt}{\mbox{Con\TeXt{t}}}
10414 \providecommand*{\MiKTeX}{\mbox{MiK\TeX}}
10415 \end{warpprint}
```

91 \AtBeginDocument, \AtEndDocument

for HTML output:

```
10416 \begin{warpHTML}
```

\LWR@LwarpStart Automatically sets up the HTML-related actions for the start and end of the document.
 \LWR@LwarpEnd

```
10417 \AfterEndPreamble{\LWR@LwarpStart}
10418 \AtEndDocument{\LWR@LwarpEnd}
```

```
10419 \end{warpHTML}
```

92 Koma-script

Load patches to **koma-script**.

for HTML output: 10420 \begin{warpHTML}

```
10421 \@ifclassloaded{scrbook}{\RequirePackage{l warp-patch-komascript}}{}  
10422 \@ifclassloaded{scrartcl}{\RequirePackage{l warp-patch-komascript}}{}  
10423 \@ifclassloaded{scrreprt}{\RequirePackage{l warp-patch-komascript}}{}  
  
10424 \end{warpHTML}
```

93 Memoir

Load patches to **memoir**.

for HTML output: 10425 \begin{warpHTML}

```
10426 \@ifclassloaded{memoir}{\RequirePackage{l warp-patch-memoir}}{}  
  
10427 \end{warpHTML}
```

94 Trademarks

- **T_EX** is a trademark of American Mathematical Society.
- **ADOBE®** and **ADOBE Framemaker®** are either registered trademarks or trademarks of ADOBE SYSTEMS INCORPORATED in the United States and/or other countries.
- **LINUX®** is the registered trademark of Linus Torvalds in the U.S. and other countries.
- **MAC OS®** is a trademark of **APPLE INC.**
- **MADCAP FLARE™** is the property of **MADCAP SOFTWARE, INC.**
- **MATHJAX** is copyright 2009 and later. The **MATHJAX CONSORTIUM** is a joint venture of the **AMERICAN MATHEMATICAL SOCIETY (AMS)** and the **SOCIETY FOR INDUSTRIAL AND APPLIED MATHEMATICS (SIAM)** to advance mathematical and scientific content on the web.
- **MICROSOFT®**, **ENCARTA**, **MSN**, and **WINDOWS®** are either registered trademarks or trademarks of **MICROSOFT CORPORATION** in the United States and/or other countries.
- **UNIX®** is a registered trademark of **THE OPEN GROUP**.

File 2 **l warp-2up.sty**

§ 95 Package **2up**

Pkg **2up** **2up** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{2up}[2010/05/15]

```
2 \def\source#1#2#3{}
3 \def\target#1#2#3{}
4 \def\targetlayout#1{}
5 \newdimen\pageseplength
6 \newdimen\pagesepwidth
7 \newdimen\pagesepoffset
8 \def\twoupemptypage{}
9 \def\twoupclearpage{}
10 \def\twoupeject{}
11 \def\twouparticle{}
12 \def\twoupplain{}
13 \def\twouplegaltarget{}
14 \def\twouplandscape{}
15 \def\TwoupWrites{}
```

File 3 **l warp-a4.sty**

§ 96 Package **a4**

Pkg **a4** **a4** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{a4}

```
2 \newcommand*\WideMargins{}
```

File 4 **l warp-a4wide.sty**

§ 97 Package **a4wide**

Pkg **a4wide** **a4wide** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{a4wide}

File 5 **l warp-a5comb.sty**

§ 98 Package **a5comb**

Pkg a5comb **a5comb** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{a5comb}

File 6 **l warp-abstract.sty**

§ 99 Package **abstract**

(Emulates or patches code by PETER WILSON.)

Pkg abstract **abstract** is supported and patched by **l warp**.

⚠ missing TOC If using the number option with file splits, be sure to place the table of contents before the abstract. The number option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

for HTML output: **memoir** provides an abstract environment even though it is not an **article** or **report** class. Meanwhile, **l warp** loads **book** to emulate **memoir**, but **book** does not have an abstract environment, so when the **abstract** package is loaded for emulation there is no pre-existing **abstract** to redefine, which would cause an error. Thus, a null **abstract** is provide here:

1 \ProvideDocumentEnvironment{abstract}{}{}{}

Accept all options for **l warp-abstract**:

2 \LWR@ProvidesPackagePass{abstract}

3 \AtBeginDocument{
4 \BeforeBeginEnvironment{abstract}{
5 \LWR@forcenewpage
6 \BlockClass{abstract}
7 }
8 \AfterEndEnvironment{abstract}{\endBlockClass}
9 }
10
11 \renewcommand{\@bsrunintitle}{%

```
12 \hspace*\abstitleskip%
13 {\abstractnamefont%
14 \InlineClass{\abstractrunintitle}{\abstractname}%
15 \@bslabeldelim}%
16 }
17
18 \@ifclassloaded{memoir}
19 {
20   \renewenvironment{abstract}{%
21 %     \titlepage
22     \null\vfil
23     \begin{parpenalty}\lowpenalty
24     \if@bsrunin
25     \else
26       \if@bsstyle
27         \abstitlestyle{\BlockClassSingle{\abstracttitle}{\abstractname}}
28       \else
29         \ifnumber@bs
30           \num@bs
31         \else
32           \begin{\absnamepos}%
33           \abstractnamefont \BlockClassSingle{\abstracttitle}{\abstractname}%
34           \end{parpenalty}\OM
35           \end{\absnamepos}%
36 %           \vspace{\abstitleskip}%
37           \fi
38           \fi
39           \vspace{\abstitleskip}%
40       \fi
41       \put@bsintoc%
42       \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
43       {\par\end{@bstr@ctlist}\vfil\null%\endtitlepage
44     }
45 }% not memoir
46 \if@titlepage
47   \renewenvironment{abstract}{%
48 %     \titlepage
49     \null\vfil
50     \begin{parpenalty}\lowpenalty
51     \if@bsrunin
52     \else
53       \if@bsstyle
54         \abstitlestyle{\BlockClassSingle{\abstracttitle}{\abstractname}}
55       \else
56         \ifnumber@bs
57           \num@bs
58         \else
59           \begin{\absnamepos}%
60           \abstractnamefont \BlockClassSingle{\abstracttitle}{\abstractname}%
61           \end{parpenalty}\OM
```

```

62          \end\absnamepos%
63 %%          \vspace{\abstitleskip}%
64      \fi
65      \fi
66      \vspace{\abstitleskip}%
67  \fi
68  \put@bsintoc%
69  \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
70  {\par\end{@bstr@ctlist}\vfil\null%\endtitlepage
71 }
72 \else
73  \renewenvironment{abstract}{%
74    \if@bsrunin
75    \else
76      \if@bsstyle
77        \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}%
78      \else
79        \ifnumber@bs
80          \num@bs
81        \else
82 \begin{\absnamepos}%
83 \abstractnamefont\BlockClassSingle{abstracttitle}{\abstractname}%
84 \end\absnamepos%
85 %%          \vspace{\abstitleskip}%
86      \fi
87      \fi
88      \vspace{\abstitleskip}%
89    \fi
90    \put@bsintoc%
91    \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
92    {\par\end{@bstr@ctlist}}
93 \fi
94 }% not memoir

```

File 7 **lwarf-accsupp.sty**

§ 100 Package **accsupp**

Pkg **accsupp** **accsupp** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{accsupp}

```

2 \newcommand*\BeginAccSupp[1]{}
3 \newcommand*\EndAccSupp[1]{}

```

File 8 **l warp-acro.sty**

§ 101 Package **acro**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg acro **acro** is patched for use by **l warp**.

for HTML output: 1 \LWR@ProvidesPackagePass{acro}

\DeclareAcronym is used in the preamble, where **l warp** has not yet made the dollar active, so temporarily enable **l warp** math catcode just for this definition:

```

2 \ExplSyntaxOn
3 \NewDocumentCommand \LWR@DeclareAcronym {mm}
4 {
5     \acro_declare_acronym:nn {#1} {#2}
6     \catcode`\$=3% l warp
7 }
8 \ExplSyntaxOff
9
10 \RenewDocumentCommand{\DeclareAcronym}{}{
11     \catcode`\$=\active% l warp
12     \LWR@DeclareAcronym
13 }
```

Modified to activate the current font:

```

14 \ExplSyntaxOn
15 \cs_gset_protected:Npn \acro_write_short:nn #1#2
16 {
17     \mode_if_horizontal:F { \leavevmode }
18     \group_begin:
19         \bool_if:NTF \l__acro_custom_format_bool
20             { \l__acro_custom_format_t1 }
21             { \l__acro_short_format_t1 }
22             {\LWR@textcurrentfont{#2}}% l warp
23     \group_end:
24 }
25
26 \cs_gset_protected:Npn \acro_write_alt:nn #1#2
27 {
28     \mode_if_horizontal:F { \leavevmode }
29     \group_begin:
30         \bool_if:NTF \l__acro_custom_format_bool
```

```

31      { \l__acro_custom_format_t1 }
32      { \l__acro_alt_format_t1 }
33      {\LWR@textcurrentfont{#2}}% l warp
34      \group_end:
35  }
36
37 \cs_gset_protected:Npn \acro_write_long:nn #1#2
38  {
39      \mode_if_horizontal:F { \leavevmode }
40      \group_begin:
41          \bool_if:NTF \l__acro_custom_long_format_bool
42              { \l__acro_custom_long_format_t1 }
43              { \use:n }
44          {
45              \use:x
46              {
47                  \exp_not:n {#1}
48                  {
49                      \bool_if:NTF \l__acro_first_upper_bool
50                          { \exp_not:N \__acro_first_upper_case:n { \exp_not:n {
51                              \LWR@textcurrentfont{#2}}% l warp
52                          } } }
53                          { \exp_not:n { \LWR@textcurrentfont{#2}} }% l warp
54                  }
55                  }
56              }
57          \group_end:
58  }
59 \ExplSyntaxOff

```

File 9 **l warp-acronym.sty**

§ 102 Package **acronym**

(Emulates or patches code by TOBIAS OETIKER.)

Pkg **acronym** **acronym** is patched for use by **l warp**.

⚠ **multiply-defined labels** **\acresetall** does not work with **cleveref**, causing multiply-defined labels. **l warp** patches **acronym** for HTML, but not for print mode.

for HTML output: 1 \LWR@ProvidesPackagePass{acronym}

Uses **\textit** instead of **\itshape**:

```

2 \renewcommand{\acfia}[1]{%
3   {\textit{\AC@acl{#1}}} (\ifAC@starred\acs*{#1}\else\acs{#1}\fi)}

```

Removes the mbox to allow math inside:

```

4 \renewcommand*\AC@acs[1]{%
5 %      \mbox{%
6 \expandafter\AC@get\csname fn@\#1\endcsname\@firstoftwo{\#1}%
7 % }

```

Modified for **cleveref** and **zref**:

```

8 \renewcommand*\AC@und@newl@bel[3]{%
9     \@ifundefined{#1@#3}{%
10    {%
11        \global\expandafter\let\csname#2@#3\endcsname\@nnil
12        \global\expandafter\let\csname#2@#3@cref\endcsname\@nnil% l warp
13    }%
14    {%
15        \global\expandafter\let\csname#1@#3\endcsname\relax
16        \global\expandafter\let\csname#1@#3@cref\endcsname\relax% l warp
17        \global\expandafter\let\csname Z@R@#3\endcsname\relax% l warp
18    }%
19 }%

```

Modified for **cleveref** and **zref**:

```

20 \renewcommand*\AC@testdef[3]{%
21 \ifstreq{\#1}{Z@R}{}{%
22     \ifundefined{s@\#2}{%
23         \expandafter\ifx\csname s@\#2\endcsname\empty
24             \expandafter\@firstofone
25         \else
26             \expandafter\xdef\csname s@\#2\endcsname{%
27                 \expandafter\expandafter
28                 \expandafter\gobble
29                 \csname s@\#2\endcsname
30             }%
31         \expandafter\@gobble
32     }%
33     \fi
34 }%
35 {%
36     \@testdef{\#1}{\#2}{\#3}%
37 }%
38 }% l warp
39 }%

```

File 10 **l warp-adjmulticol.sty**

§ 103 Package **adjmulticol**

(Emulates or patches code by BORIS VEYTSMAN.)

Pkg **adjmulticol** **adjmulticol** is emulated.

Emulation similar to **multcols** is used, with adjusted margins. If the number of columns is specified as 1, it is set so, but if two or greater are used, **l warp** allows a variable number of columns up to three.

```
for HTML output: 1 \LWR@ProvidesPackageDrop{adjmulticol}

2 \RequirePackage{multicol}

adjmulticols * {\{numcols\}} {\{left marg\}} {\{right margin\}}

3 \NewDocumentEnvironment{adjmulticols}{s m m m}
4 {%
```

Compute the margins, and limit to positive only:

```
5 \setlength{\LWR@templengthone}{#3}%
6 \ifdimcomp{\LWR@templengthone}{<}{0pt}{\setlength{\LWR@templengthone}{0pt}}{}%
7 \setlength{\LWR@templengthtwo}{#4}%
8 \ifdimcomp{\LWR@templengthtwo}{<}{0pt}{\setlength{\LWR@templengthtwo}{0pt}}{}%
```

If one column is specified, use a <div> of class **singlecolumn**, else use **multcols**:

```
9 \newcommand*{\LWR@mcolstype}{multcols}%
10 \ifnumcomp{#2}{=}{1}{\renewcommand*{\LWR@mcolstype}{singlecolumn}}{}%
```

Help avoid page overflow:

```
11 \LWR@forcenewpage%
```

Create the <div> with the given margin and class:

```
12 \BlockClass[%
13 \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
14 \LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}%
15 ]{\LWR@mcolstype}%
16 }
```

```
17 {\endBlockClass}
```

File 11 **l warp-addlines.sty**

§ 104 Package **addlines**

(Emulates or patches code by WILL ROBERTSON.)

Pkg **addlines** **addlines** is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{addlines}
2 \newcommand*\addlines[1][1]{}
3 \let\addline\addlines
4 \newcommand*\removelines[1][1]{}
5 \let\removeline\removelines
```

File 12 **l warp-ae.sty**

§ 105 Package **ae**

Pkg **ae** **ae** does not work with **pdftotext**, and is superceded by **latinmodern**.

for HTML output:

```
1 \LWR@loadnever{ae}{latinmodern}
```

File 13 **l warp-aecc.sty**

§ 106 Package **aecc**

Pkg **aecc** **aecc** does not work with **pdftotext**, and is superceded by **latinmodern**.

for HTML output:

```
1 \LWR@loadnever{aecc}{latinmodern}
```

File 14 **l warp-afterpage.sty**

§ 107 Package **afterpage**

(Emulates or patches code by DAVID CARLISLE.)

Pkg afterpage Emulated.

for HTML output: Discard all options for **l warp-afterpage**:

```
1 \LWR@ProvidesPackageDrop{afterpage}
2 \newcommand{\afterpage}[1]{#1}
```

File 15 **l warp-algorithm2e.sty**

§ 108 Package **algorithm2e**

(Emulates or patches code by CHRISTOPHE FIORIO.)

Pkg algorithm2e **algorithm2e** is patched for use by **l warp**.

For print output, captions are placed according to package options, but for HTML output captions are placed where used. Therefore, to have captions appear at the top of the algorithms for both print and HTML, place each captions at the top of each algorithm.

for HTML output: 1 \LWR@ProvidesPackagePass{algorithm2e}

For the list-of entries:

```
2 \renewcommand{\l@algocf}[2]{\hypertocfloat{1}{algocf}{loa}{#1}{#2}}
```

Select the **l warp** float style according to the **algorithm2e** style:

```
3 \newcommand*{\LWR@floatstyle@algocf}{ruled}
4
5 \ifdefstring{\algocf@style}{boxed}{%
6 \renewcommand*{\LWR@floatstyle@algocf}{boxed}
7 }{%
8
9 \ifdefstring{\algocf@style}{boxruled}{%
10 \renewcommand*{\LWR@floatstyle@algocf}{boxruled}
11 }{%
12
13 \ifdefstring{\algocf@style}{plain}{%
14 \renewcommand*{\LWR@floatstyle@algocf}{plain}
15 }{}}
```

Paragraph handling to allow line numbers under certain conditions:

```
16 \newbool{\LWR@algocf@dopars}
```

```

17 \booltrue{LWR@algocf@dopars}
18
19 \renewcommand{\algocf@everypar}{%
20 \ifbool{LWR@algocf@dopars}{%
21   \ifbool{LWR@doingstartpars}{%
22     \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}{%
23       {}%
24       {}%
25       \algocf@everyparnl\algocf@everyparhanging%
26     }%
27   }{}%
28 }{}%
29 }

```

lwarf caption handling:

```

30 \renewcommand{\algocf@makecaption}[2]{%
31 \LWR@HTML@caption@begin{\algocf}%
32 \algocf@captiontext{\#1}{\#2}%
33 \LWR@HTML@caption@end%
34 }

```

Print any caption where it is declared:

```

35 \renewcommand{\algocf@makecaption@plain}[2]{%
36   \LWR@HTML@caption@begin{\algocf}%
37   \algocf@captiontext{\#1}{\#2}%
38   \LWR@HTML@caption@end%
39 }
40
41 \renewcommand{\algocf@makecaption@boxed}[2]{%
42   \LWR@HTML@caption@begin{\algocf}%
43   \algocf@captiontext{\#1}{\#2}%
44   \LWR@HTML@caption@end%
45 }
46
47 \renewcommand{\algocf@makecaption@ruled}[2]{%
48   \LWR@HTML@caption@begin{\algocf}%
49   \algocf@captiontext{\#1}{\#2}%
50   \LWR@HTML@caption@end%
51 }

```

Turn off line numbering while making the caption:

```

52 \long\def\algocf@latexcaption#1[#2]#3{%
53   \boolfalse{LWR@algocf@dopars}%
54   \par%
55   \addcontentsline{\csname ext@#1\endcsname}{#1}%
56   {\protect\numberline{\csname the#1\endcsname}\ignorespaces #2}%

```

```

57 \begingroup%
58 \@parboxrestore%
59 \if@minipage%
60   \csetminipage%
61 \fi%
62 \normalsize%
63 \makecaption{\csname fnum@\#1\endcsname}{\ignorespaces #3}\par%
64 \endgroup%
65 \booltrue{LWR@algocf@dopars}%
66 } lwarf

```

Line numbers are printed in a `` of class `alg2elinenumbers`:

```

67 \renewcommand{\algocf@printnl}[1]{%
68   \InlineClass{alg2elinenumbers}{NlSty{\#1}}{%
69 }

```

While initializing an algorithm environment, locally declare the style of a regular figure to be the same as the algorithm style, in case the `figure` option was used.

```

70 \preto{\algocf@init}{%
71   \edef\LWR@floatstyle@figure{\LWR@floatstyle@algocf}%
72 }

```

For `lwarf`, the algorithm is not assembled inside a box, since `lateximages` would not work, so the captions are printed where declared.

```

73 \renewcommand{\@algocf@start}{%
74   \let{@mathsemicolon=};\def\;{\ifmmode\@mathsemicolon\else\@endalgoln\fi}%
75 %   \raggedright%
76   \AlFnt{}%
77   \booltrue{LWR@algocf@dopars}%
78 } lwarf
79
80 \renewcommand{\@algocf@finish}{%
81   \boolfalse{LWR@algocf@dopars}%
82   \lineskip\normalineskip\setlength{\skiptotal}{\@defaultskiptotal}%
83   \let\;=\@mathsemicolon%
84   \let\]=\@emathdisplay%
85 }

```

Use an HTML break:

```

86 \renewcommand{\BlankLine}{%
87 \LWR@stoppars%
88 \LWR@htmlltagc{br /}%
89 \LWR@startpars%
90 }

```

Simplified for HTML. The paragraph handling must be preserved.

```

91 \renewcommand{\SetKwInOut}[2]{%
92   \algocf@newcommand{\#1}[1]{%
93     \ifthenelse{\boolean{\algocf@hanginginout}}{%
94       {\relax}%
95       {\algocf@seteveryparhanging{\relax}}%
96     \ifthenelse{\boolean{\algocf@inoutnumbered}}{%
97       {\relax}%
98       {\algocf@seteveryparnl{\relax}}%
99     }%
100       \KwSty{\#2\algocf@typo:}%
101       ~##1\par%
102     }%
103     \algocf@linesnumbered% reset the numbering of the lines
104     \ifthenelse{\boolean{\algocf@hanginginout}}{%
105       {\relax}%
106       {\algocf@reseteveryparhanging}%
107     }%
108   }%
109 }
110 \renewcommand{\ResetInOut}[1]{}

```

Each of the following creates a <div> of a given class, and turns off line numbering while creating the <div> tags:

```

111 \renewcommand{\algocf@Vline}[1]{%
112 \boolfalse{LWR@algocf@dopars}%
113 \begin{BlockClass}{alg2evline}%
114 \booltrue{LWR@algocf@dopars}%
115 #1
116 \boolfalse{LWR@algocf@dopars}%
117 \end{BlockClass}%
118 \booltrue{LWR@algocf@dopars}%
119 }

120 \renewcommand{\algocf@Vsline}[1]{%
121 \boolfalse{LWR@algocf@dopars}%
122 \begin{BlockClass}{alg2evsline}%
123 \booltrue{LWR@algocf@dopars}%
124 #1
125 \boolfalse{LWR@algocf@dopars}%
126 \end{BlockClass}%
127 \booltrue{LWR@algocf@dopars}%
128 }

129 \renewcommand{\algocf@Noline}[1]{%
130 \boolfalse{LWR@algocf@dopars}%
131 \begin{BlockClass}{alg2enoline}%

```

```

132 \booltrue{LWR@algocf@dopars}%
133 #1
134 \boolfalse{LWR@algocf@dopars}%
135 \end{BlockClass}
136 \booltrue{LWR@algocf@dopars}%
137 }

```

The [H] environment is converted to a regular float, which in HTML is placed where declared. Reusing the regular float allows the [H] version to reuse the ruled and boxed options.

```

138 \LetLtxMacro\algocf@Here\algocf
139 \LetLtxMacro\endalgocf@Here\endalgocf

```

File 16 l warp-algorithmicx.sty

§ 109 Package **algorithmicx**

(Emulates or patches code by SzÁSZ JÁNOS.)

Pkg algorithmicx **algorithmicx** is supported with minor adjustments.

for HTML output: 1 \LWR@ProvidesPackagePass{algorithmicx}

Inside the `algorithmic` environment, level indenting is converted to a `` of the required length, and comments are placed inside a `` which is floated right.

⚠ **package conflicts** If using `\newfloat`, `trivfloat`, and/or `algorithmicx` together, see section 406.1.

for HTML output: 2 \begin{warpHTML}

```

3 \AtBeginEnvironment{algorithmic}{%
4 %
5 \let\origALG@doentity\ALG@doentity%
6 %
7 \renewcommand*\ALG@doentity{%
8 \origALG@doentity%
9 \LWR@htmltagc{%
10 span style="width:\LWR@printlength{\ALG@thistlm}; display:inline-block;"%
11 }%
12 \ifbool{FormatWP}{%
13 \setlength{\LWR@templengthone}{\the\ALG@thistlm}%
14 \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
15 \quad}%
16 \addtolength{\LWR@templengthone}{-1em}%
17 }%

```

```

18 }{}}%
19 \LWR@htmlltagc{/span}%
20 }%
21
22 \let\LWR@origComment\Comment%
23
24 \renewcommand{\Comment}[1]{%
25     \InlineClass{floatright}{\LWR@origComment{#1}}%
26 }%
27 }
28
29 \renewcommand\algorithmiccomment[1]{%
30 \hfill\HTMLunicode{25B7} #1% white right triangle
31 }%
32 \end{warpHTML}

```

File 17 **l warp-alltt.sty**

§ 110 Package **alltt**

(Emulates or patches code by JOHANNES BRAAMS.)

Pkg **alltt** **alltt** is patched for use by **l warp**.

for HTML output:

```

1 \LWR@ProvidesPackagePass{alltt}

2 \AfterEndPreamble{
3 \LWR@traceinfo{Patching alltt.}
4 \AtBeginEnvironment{alltt}{%
5 \LWR@forcenewpage
6 \LWR@atbeginverbatim{3}{alltt}%
7 }
8 \AfterEndEnvironment{alltt}{%
9     \LWR@afterendverbatim{2}%
10 }
11 }

```

File 18 **l warp-amsmath.sty**

§ 111 Package **amsmath**

(Emulates or patches code by AMERICAN MATHEMATICAL SOCIETY, L^ET_X3 PROJECT.)

Pkg amsmath **amsmath** is patched for use by **l warp**.

for HTML output: 1 \LWR@ProvidesPackagePass{amsmath}

Patches to allow \eqref inside a caption:

```
2 \def\maketag@@@{\text{\#1}}
3 \def\tagform@{\maketag@@@{(\ignorespaces#1\unskip)}}
```

Patches for *AMS* math \tag macro to remember the first tag:

```
4 \ifbool{mathjax}{}{%
5   \LetLtxMacro{\LWR@origmake@df@tag@@}{\make@df@tag@@}
6   \LetLtxMacro{\LWR@origmake@df@tag@@@}{\make@df@tag@@@}
7
8   \renewcommand*{\make@df@tag@@}[1]{%
9     \LWR@remembertag{\#1}%
10    \LWR@origmake@df@tag@@{\#1}%
11  }
12}
13
14 \renewcommand*{\make@df@tag@@@}[1]{%
15   \LWR@remembertag{\#1}%
16   \LWR@origmake@df@tag@@@{\#1}%
17 }
18
19 }% not mathjax
```

The following *AMS* environments are more easily patched in-place:

Env multiline

```
20 \BeforeBeginEnvironment{multiline}%
21
22 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }{%
23 {
24   \LWR@syncmathjax
25   \booltrue{\LWR@amsmultiline}
26   \LWR@beginhideamsmath
27 }
28 {
29   \begin{BlockClass}{displaymathnumbered}
30   \LWR@newautoidanchor%
31   \booltrue{\LWR@indisplaymathimage}%
32   \begin{lateximage}[\LWR@amsmathbodynumbered{multiline}]
33 }
34 }
35
```

```
36 \AfterEndEnvironment{multline}{

37
38 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
39 {
40     \LWR@endhideamsmath
41     \boolfalse{LWR@amsmultiline}
42     \LWR@addmathjax{multline}{\the\@envbody}
43 }
44 {\end{lateximage}\end{BlockClass}}
45
46 }

Env  multiline*

47 \BeforeBeginEnvironment{multline*}{

48
49 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
50 {
51     \LWR@syncmathjax
52     \booltrue{LWR@amsmultiline}
53     \LWR@beginhideamsmath
54 }
55 {
56     \begin{BlockClass}{displaymath}
57     \LWR@newautoidanchor
58     \booltrue{LWR@indisplaymathimage}%
59     \begin{lateximage}[\LWR@amsmathbody{multline*}]
60 }
61 }
62
63 \AfterEndEnvironment{multline*}{

64
65 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
66 {
67     \LWR@endhideamsmath
68     \boolfalse{LWR@amsmultiline}
69     \LWR@addmathjax{multline*}{\the\@envbody}
70 }
71 {\end{lateximage}\end{BlockClass}}
72
73 }
74

Env  gather

75 \BeforeBeginEnvironment{gather}{

76
77 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
```

```
78 {
79     \LWR@syncmathjax
80     \boolexpr{\LWR@amsmultiline}
81     \LWR@beginhideamsmath
82 }
83 {
84     \begin{BlockClass}{displaymathnumbered}
85     \LWR@newautoidanchor%
86     \boolexpr{\LWR@indisplaymathimage}%
87     \begin{lateximage}[\LWR@amsmathbodynumbered{gather}]
88 }
89 }
90
91 \AfterEndEnvironment{gather}{

92 \ifboolexpr{\bool{mathjax} or (\ bool{FormatWP} and \bool{WPMarkMath} ) }{
93 {
94     \LWR@endhideamsmath
95     \LWR@addmathjax{gather}{\the\@envbody}
96 }
97 }
98 \end{lateximage}\end{BlockClass}
99 }
100 }
```

Env `gather*`

```
101 \BeforeBeginEnvironment{gather*}{

102 \ifboolexpr{\bool{mathjax} or (\ bool{FormatWP} and \bool{WPMarkMath} ) }{
103 {
104     \LWR@syncmathjax
105     \boolexpr{\LWR@amsmultiline}
106     \LWR@beginhideamsmath
107 }
108 }
109 {
110     \begin{BlockClass}{displaymath}
111     \LWR@newautoidanchor%
112     \boolexpr{\LWR@indisplaymathimage}%
113     \begin{lateximage}[\LWR@amsmathbody{gather*}]
114 }
115 }
116
117 \AfterEndEnvironment{gather*}{

118 \ifboolexpr{\bool{mathjax} or (\ bool{FormatWP} and \bool{WPMarkMath} ) }{
119 {
120     \LWR@endhideamsmath
121     \LWR@addmathjax{gather*}{\the\@envbody}
122 }
123 }
```

```
124 {\end{lateximage}\end{BlockClass}}
125
126 }

Env  align

127 \BeforeBeginEnvironment{align}{

128 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
129 {
130   \LWR@syncmathjax
131   \boolefalse{\LWR@amsmultiline}
132   \LWR@beginhideamsmath
133
134 }
135 {
136   \begin{BlockClass}{displaymathnumbered}
137   \LWR@newautoidanchor%
138   \booletrue{\LWR@indisplaymathimage}%
139   \begin{lateximage}[\LWR@amsmathbodynumbered{align}]
140 }
141
142
143 \AfterEndEnvironment{align}{

144 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
145 {
146   \LWR@endhideamsmath
147   \LWR@addmathjax{align}{\the\@envbody}
148
149 }
150 {\end{lateximage}\end{BlockClass}}
151
152 }

Env  align*

153 \BeforeBeginEnvironment{align*}{

154 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
155 {
156   \LWR@syncmathjax
157   \boolefalse{\LWR@amsmultiline}
158   \LWR@beginhideamsmath
159
160 }
161 {
162   \begin{BlockClass}{displaymath}
163   \LWR@newautoidanchor%
164   \booletrue{\LWR@indisplaymathimage}%
165   \begin{lateximage}[\LWR@amsmathbody{align*}]
```

```
166 }  
167 }  
168  
169 \AfterEndEnvironment{align*}{  
170     1ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%  
171     \LWR@endhideamsmath  
172 {  
173     \LWR@addmathjax{align*}{\the\@envbody}  
174 }  
175 }  
176 {\end{lateximage}\end{BlockClass}}  
177  
178 }
```

Env flalign

```
179 \BeforeBeginEnvironment{flalign}{  
180  
181 1ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%  
182 {  
183     \LWR@syncmathjax  
184     \boolefalse{LWR@amsmultiline}  
185     \LWR@beginhideamsmath  
186 }  
187 {  
188     \begin{BlockClass}{displaymathnumbered}  
189     \LWR@newautoidanchor%  
190     \booletrue{LWR@indisplaymathimage}%  
191     \begin{lateximage}[\LWR@amsmathbodynumbered{flalign}]  
192 }  
193 }  
194  
195 \AfterEndEnvironment{flalign}{  
196  
197 1ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%  
198 {  
199     \LWR@endhideamsmath  
200     \LWR@addmathjax{flalign}{\the\@envbody}  
201 }  
202 {\end{lateximage}\end{BlockClass}}  
203  
204 }
```

Env flalign*

```
205 \BeforeBeginEnvironment{flalign*}{  
206  
207 1ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
```

```
208 {
209     \LWR@syncmathjax
210     \boolefalse{LWR@amsmultiline}
211     \LWR@beginhideamsmath
212 }
213 {
214     \begin{BlockClass}{displaymath}
215     \LWR@newautoidanchor%
216     \booletrue{LWR@indisplaymathimage}%
217     \begin{lateximage}[\LWR@amsmathbody{flalign*}]
218 }
219 }
220
221 \AfterEndEnvironment{flalign*}{

222 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }{
223
224 {
225     \LWR@endhideamsmath
226     \LWR@addmathjax{flalign*}{\the\@envbody}
227 }
228 {\end{lateximage}\end{BlockClass}}
229 }
230 }

Env alignat

231 \BeforeBeginEnvironment{alignat}{

232 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }{
233
234 {
235     \LWR@syncmathjax
236     \boolefalse{LWR@amsmultiline}
237     \LWR@beginhideamsmath
238 }
239 {
240     \begin{BlockClass}{displaymathnumbered}
241     \LWR@newautoidanchor%
242     \booletrue{LWR@indisplaymathimage}%
243     \begin{lateximage}[\LWR@amsmathbodynumbered{alignat}]
244 }
245 }
246
247 \AfterEndEnvironment{alignat}{

248 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }{
249
250 {
251     \LWR@endhideamsmath
252     \LWR@addmathjax{alignat}{\the\@envbody}
253 }
```

```

254 {\end{lateximage}\end{BlockClass}}
255
256 }

Env alignat*
257 \BeforeBeginEnvironment{alignat*}{

258 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }{
259 \LWR@syncmathjax
260 \boolfalse{LWR@amsmultiline}
261 \LWR@beginhideamsmath
262 }
263 \begin{BlockClass}{displaymath}
264 \LWR@newautoanchor%
265 \booltrue{LWR@indisplaymathimage}%
266 \begin{lateximage}[\LWR@amsbody{alignat*}]
267 \end{lateximage}
268 \end{BlockClass}
269 \begin{displaymath}
270 \LWR@newautoanchor%
271 \booltrue{LWR@indisplaymathimage}%
272 \begin{aligned}
273 \end{aligned}
274 \end{displaymath}
275 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }{
276 \LWR@endhideamsmath
277 \LWR@addmathjax{alignat*}{\the\envbody}
278 }
279 \end{aligned}
280 {\end{lateximage}\end{BlockClass}}
281
282 }

```

File 19 lwarf-amsthm.sty

§ 112 Package **amsthm**

(Emulates or patches code by PUBLICATIONS TECHNICAL GROUP—AMERICAN MATHEMATICAL SOCIETY.)

The original source code is located in `amsclass.dtx`, and printed in `amsclass.pdf`.

Pkg amsthm **amsthm** is patched for use by **lwarf**.

for HTML output: 1 \LWR@ProvidesPackagePass{amsthm}

Table 13: AMSthm package—CSS styling of theorems and proofs

Theorem: <div> of class `amsthmbody<theoremstyle>`

Theorem Name: of class `amsthmname<theoremstyle>`

Theorem Number: of class `amsthmnumber<theoremstyle>`

Theorem Note: of class `amsthmnote<theoremstyle>`

Proof: <div> of class `amsthmproof`

Proof Name: of class `amsthmproofname`

where <theoremstyle> is plain, definition, etc.

Storage for the style being used for new theorems:

```
2 \newcommand{\LWR@newtheoremstyle}{plain}
```

Patched to remember the style being used for new theorems:

```
3 \renewcommand{\theoremstyle}[1]{%
4   \@ifundefined{th@#1}{%
5     \PackageWarning{amsthm}{Unknown theoremstyle '#1'}%
6     \thm@style{plain}%
7     \renewcommand{\LWR@newtheoremstyle}{plain}\l warp
8   }{%
9     \thm@style{#1}%
10    \renewcommand{\LWR@newtheoremstyle}{#1}\l warp
11  }%
12 }
```

Patched to remember the style for this theorem type:

```
13 \def\@xnthm#1#2{%
14   \csedef{\LWR@thmstyle#2}{\LWR@newtheoremstyle}\l warp
15   \let\@tempa\relax
16   \@xp\@if definable\csname #2\endcsname{%
17     \global\@xp\let\csname end#2\endcsname\@endtheorem
18     \ifx *#1% unnumbered, need to get one more mandatory arg
19       \edef\@tempa##1{%
20         \gdef\@xp\@nx\csname#2\endcsname{%
21           \@nx\@thm{\@xp\@nx\csname th@\the\thm@style\endcsname}%
22             {}{##1}}%
23       \else % numbered theorem, need to check for optional arg
24         \def\@tempa{\@oparg{\@ynthm{#2}}[]}\%
25       \fi
26   }
```

```

26     \AtBeginEnvironment{#2}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#2}}}% l warp
27   }%
28   \atempa
29 }

```

Patched to enclose with css:

```

30 \newcommand{\LWR@haveamsthmname}{%
31 \renewcommand{\thmname}[1]{\InlineClass{amsthmname}\LWR@thisthmstyle}{}}
32 }
33
34 \newcommand{\LWR@haveamsthmnumber}{%
35 \renewcommand{\thmnumber}[1]{\InlineClass{amsthmnumber}\LWR@thisthmstyle}{}}
36 }
37
38 \newcommand{\LWR@haveamsthmnote}{%
39 \renewcommand{\thmnote}[1]{\InlineClass{amsthmnote}\LWR@thisthmstyle}{}}
40 }
41
42 \LWR@haveamsthmname
43 \LWR@haveamsthmnumber
44 \LWR@haveamsthmnote

```

Patches for css:

```

45 \def\@begintheorem#1#2[#3]{%
46   \item[%
47 %   \deferral@thm@head{%
48 %     \the\thm@headfont \thm@indent
49 %     \@ifempty{#1}{\let\thmname\@gobble}{\LWR@haveamsthmname}}% l warp
50 %     \@ifempty{#2}{\let\thmnumber\@gobble}{\LWR@haveamsthmnumber}}% l warp
51 %     \@ifempty{#3}{\let\thmnote\@gobble}{\LWR@haveamsthmnote}}% l warp
52 %     \thm@swap\swappedhead\thmhead{#1}{#2}{#3}}%
53 %     \the\thm@headpunct%
54 %     \thmheadnl % possibly a newline.
55 %     \hskip\thm@headsep
56 %   }%
57   ]
58 \ignorespaces}

```

Patched for css:

```

59 \def\@thm#1#2#3{%
60   \ifhmode\unskip\unskip\par\fi
61   \normalfont
62   \LWR@forcenewpage% l warp
63   \BlockClass{amsthmbody}\LWR@thisthmstyle}% l warp
64   \trivlist
65   \let\thmheadnl\relax

```

```

66 \let\thm@swap\@gobble
67 \thm@notefont{\fontseries\mddefault\upshape}%
68 \thm@headpunct{.}% add period after heading
69 \thm@headsep 5\p@ plus\p@ minus\p@\relax
70 \thm@space@setup
71 #1% style overrides
72 \@topsep \thm@preskip % used by thm head
73 \@topsepadd \thm@postskip % used by \endparenv
74 \def\@tempa{\#2}\ifx\@empty\@tempa
75   \def\@tempa{\oparg{\begin{theorem}{}}[]}\%
76 \else
77   \refstepcounter{\#2}\%
78   \def\@tempa{\oparg{\begin{theorem}{\csname the\#2\endcsname}}[]}\%
79 \fi
80 \@tempa
81 }

```

cleveref patches `\@thm` to do `\cref@thmoptarg` if an optional argument is given.
l warp then patches `\cref@thmoptarg` `\AtBeginDocument`.

```

82 \AtBeginDocument{
83 \def\cref@thmoptarg[#1]#2#3#4{%
84   \ifhmode\unskip\unskip\par\fi%
85   \normalfont%
86   \LWR@forcenewpage% l warp
87   \BlockClass{amsthmbody}\LWR@thisthmstyle% l warp
88   \trivlist%
89   \let\thmheadnl\relax%
90   \let\thm@swap\@gobble%
91   \thm@notefont{\fontseries\mddefault\upshape}%
92   \thm@headpunct{.}% add period after heading
93   \thm@headsep 5\p@ plus\p@ minus\p@\relax%
94   \thm@space@setup%
95 #2% style overrides
96   \@topsep \thm@preskip % used by thm head
97   \@topsepadd \thm@postskip % used by \endparenv
98   \def\@tempa{\#3}\ifx\@empty\@tempa
99     \def\@tempa{\oparg{\begin{theorem}{}}[]}\%
100 \else%
101   \refstepcounter{\#1}\#3% <<< cleveref modification
102   \def\@tempa{\oparg{\begin{theorem}{\csname the\#3\endcsname}}[]}\%
103 \fi%
104 \@tempa
105 }%
106 }% AtBeginDocument
107
108 \def\endtheorem{\endtrivlist\endBlockClass\endpefalse }

```

Proof QED symbol:

```

109 \AtBeginDocument{
110 \@ifundefined{LWR@orig@openbox}{
111 \LetLtxMacro{\LWR@orig@openbox}{\openbox}
112 \LetLtxMacro{\LWR@orig@blacksquare}{\blacksquare}
113 \LetLtxMacro{\LWR@orig@Box}{\Box}
114
115 \def\openbox{\text{\HTMLUnicode{25A1}}}% UTF-8 white box
116 \def\blacksquare{\text{\HTMLUnicode{220E}}}% UTF-8 end-of-proof
117 \def\Box{\text{\HTMLUnicode{25A1}}}% UTF-8 white box
118
119 \appto{\LWR@restoreorigformatting}{%
120 \LetLtxMacro{\openbox}{\LWR@orig@openbox}%
121 \LetLtxMacro{\blacksquare}{\LWR@orig@blacksquare}%
122 \LetLtxMacro{\Box}{\LWR@orig@Box}%
123 }% appto
124 }{}% @ifundefined
125 }% AtBeginDocument

```

Patched for css:

```

126 \renewenvironment{proof}[1][\proofname]{\par
127 \LWR@forcenewpage% l warp
128     \BlockClass{amsthmproof}% l warp
129     \pushQED{\qed}%
130     \normalfont \topsep6\p@\oplus6\p@\relax
131     \trivlist
132     \item[
133         \InlineClass{amsthmproofname}{\#1\@addpunct{.}}]\ignorespaces% changes
134     }{%
135     \InlineClass{theoremendmark}{\popQED}\endtrivlist%
136     \endBlockClass% l warp
137     \endpefalse
138 }

```

File 20 **l warp-anonchap.sty**

§ 113 Package **anonchap**

(Emulates or patches code by PETER WILSON.)

Pkg **anonchap** **anonchap** is emulated.

Pkg **tocloft** If using **tocloft** with **tocbibind**, **anonchap**, **fncychap**, or other packages which change chapter title formatting, load **tocloft** with its **titles** option, which tells **tocloft** to

⚠ tocloft & other packages

use standard L^AT_EX commands to create the titles, allowing other packages to work with it.

The code is shared by **tocbibind**.

```
for HTML output: 1 \LWR@ProvidesPackageDrop{anonchap}

2 \newcommand{\simplechapter}[1][]{\@empty}{%
3   \def\@chapcntformat##1{%
4     #1\csname the##1\endcsname\simplechapterdelim\protect\quad%
5   }%
6 }
7
8 \newcommand{\restorechapter}{%
9 \let\@chapcntformat\@secntformat%
10 }
```

File 21 l warp-any size .sty

§ 114 Package **any size**

(Emulates or patches code by MICHAEL SALZENBERG, THOMAS ESSER.)

Pkg **any size** **any size** is emulated.

```
for HTML output: 1 \LWR@ProvidesPackageDrop{any size}

2 \def\papersize#1#2{}
3 \def\marginsize#1#2#3#4{}
```

File 22 l warp-appendix .sty

§ 115 Package **appendix**

(Emulates or patches code by PETER WILSON.)

Pkg **appendix** **appendix** is patched for use by **l warp**.

- ⚠ **incorrect TOC link** During HTML conversion, the option `toc` without the option `page` results in a TOC link to whichever section was before the `appendices` environment. It is recommended to use both `toc` and also `page` at the same time.

```
for HTML output: 1 \LWR@ProvidesPackagePass{appendix}
```

```

2 \renewcommand*{\@chap@pppage}{%
3 \part*{\appendixpagename}
4 \if@dotoc@pp
5 \addapheadtotoc
6 \fi
7 }
8
9 \renewcommand*{\@sec@pppage}{%
10 \part*{\appendixpagename}
11 \if@dotoc@pp
12 \addapheadtotoc
13 \fi
14 }
```

File 23 **l warp-arabicfront.sty**

§ 116 Package **arabicfront**

Pkg **arabicfront** **arabicfront** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{arabicfront}

File 24 **l warp-array.sty**

§ 117 Package **array**

Pkg **array** **array** is used as-is for print output, and emulated for HTML.

for HTML output: Remove the dummy macros:

```

1 \let\firsthline\relax
2 \let\lasthline\relax
3
4 \LWR@ProvidesPackagePass{array}

5 \newcommand*{\LWR@HTML@firsthline}{\LWR@HTMLhline}%
6 \LWR@expandableformatted{firsthline}
7
8 \newcommand*{\LWR@HTML@lasthline}{\LWR@HTMLhline}%
9 \LWR@expandableformatted{lasthline}
```

File 25 **l warp-arydshln.sty**

§ 118 Package **arydshln**

(Emulates or patches code by HIROSHI NAKASHIMA.)

Pkg **arydshln** **arydshln** heavily patches tabular code, so the actual package is not used. **arydshln** is emulated for `HTML` `tabular`, and reverts to solid rules for `SVG` `math array` and `tabular` in a `lateximage`.

CSS is not able to display a double-dashed border, so a single-dashed rule is displayed as a single-dashed border, and a double-dashed rule is displayed as a thicker single-dashed border.

for HTML output: `array` is required to allow `\newcolumn` below.

```
1 \RequirePackage{array}
2 \LWR@ProvidesPackageDrop{arydshln}
```

Ignored, but included for source compatibility:

```
3 \newdimen\dashlinedash \dashlinedash4pt %
4 \newdimen\dashlinegap \dashlinegap4pt %
5 \let\hdashlinewidth\dashlinedash
6 \let\hdashlinegap\dashlinegap
7
8 \def\ADLnullwide{}
9 \def\ADLsomewide{}
10 \def\ADLnullwidehline{}
11 \def\ADLsomewidehline{}
12
13 \def\ADLactivate{}
14 \def\ADLinactivate{}
15 \newcommand*\{\ADLdrawingmode}[1]{}
16 \newcommand*\{\ADLnoshorthanded}{}
17 \newcommand*\{\dashgapcolor}[2][]{}
18 \newcommand*\{\nodashgapcolor}{}
```

In a `lateximage`, revert to solid vertical rules:

```
19 \appto\LWR@restoreorigformatting{
20 \newcolumntype{:}{|}%
21 \newcolumntype{;}{[1]{|}}%
22 \LetLtxMacro\hline\hline%
```

23 }

Some of these macros are already defined as temporary placeholders in the **l warp** core, so they must be redefined here.

The emulated defaults also work for an emulated print mode inside a `lateximage`:

```

24 \def\hdashline{%
25 %      \adl@hdashline\adl@ihdashline
26      \adl@hdashline\adl@inactivehdl
27 }
28 \def\adl@hdashline#1{\noalign{\ifnum0='}\fi
29 %          \ifadl@zwhrule \vskip-\arrayrulewidth
30 %          \else
31 %              \adl@hline\adl@connect\arrayrulewidth
32              \hrule \height \arrayrulewidth% l warp
33 %          \fi
34          \ifnextchar[%]
35              {#1}%
36              {#1[%}
37 %                  \dashlinedash/\dashlinegap
38                  1pt/1pt
39          ]}}
40 % \def\adl@ihdashline[#1/#2]{\ifnum0='{\fi}%
41 %     \multispan{\adl@columns}\unskip \adl@hline\z@[#1/#2]%
42 %     \noalign{\ifnum0='}\fi
43 %     \futurelet\@tempa\adl@xhline}
44 \def\adl@inactivehdl[#1/#2]{%
45 %     \ifadl@zwhrule \vskip-\arrayrulewidth \fi
46     \hrule\height\arrayrulewidth
47     \futurelet\@tempa\adl@xhline}
48 \def\adl@xhline{\ifx\@tempa\hline \adl@ixhline\fi
49     \ifx\@tempa\hdashline \adl@ixhline\fi
50     \ifnum0='{\fi}}
51 \def\adl@ixhline{\vskip\doublerulesep \adl@hline\relax\doublerulesep}
52 \def\adl@hline#1#2{%
53 % \tempcnta#2
54 %     \global\advance\adl@totalheight\tempcnta
55 %     \xdef\adl@rowsL{\adl@rowsL
56 %         (#1/\number\tempcnta);}%
57 %     \xdef\adl@rowsR{\adl@rowsR
58 %         (#1/\number\tempcnta);}
59 }
60
61 \def\cdashline#1{\noalign{\ifnum0='}\fi
62          \ifnextchar[%]
63 %              {\adl@cdline[#1]}%
64 %              {\adl@cdline[#1] [\dashlinedash/\dashlinegap]}%
65          {\adl@inactivecdl[#1]}%

```

```

66          {\adl@inactivecdl[#1][\dashlinedash/\dashlinegap]}
67 }
68
69 \def\adl@inactivecdl[#1-#2] [#3]{\ifnum0='{\fi}\cline{#1-#2}}

```

File 26 **l warp-asymptote.sty**§ 119 Package **asymptote***(Emulates or patches code by ANDY HAMMERLINDL, JOHN BOWMAN, TOM PRINCE.)*Pkg **asymptote** **asymptote** is patched for use by **l warp**.

for HTML output:

```

1 \LWR@ProvidesPackagePass{asymptote}

2 \BeforeBeginEnvironment{asy}{\begin{lateximage}}
3 \AfterEndEnvironment{asy}{\end{lateximage}}
4
5 \xpatchcmd{\asyinclude}
6   {\begingroup}
7   {\begin{lateximage}}
8   {}
9   {\LWR@patcherror{asymptote}{asyinclude-begingroup}}
10
11 \xpatchcmd{\asyinclude}
12   {\endgroup}
13   {\end{lateximage}}
14   {}
15   {\LWR@patcherror{asymptote}{asyinclude-endgroup}}

```

File 27 **l warp-atbegshi.sty**§ 120 Package **atbegshi***(Emulates or patches code by HEIKO OBERDIEK.)*Pkg **atbegshi** Emulated.

for HTML output: Discard all options for **l warp-atbegshi**:

```

1 \LWR@ProvidesPackageDrop{atbegshi}[2011/10/05]

2 \newcommand*{\AtBeginShipout}[1]{}
3 \newbox\AtBeginShipoutBox

```

```

4 \newcommand*{\AtBeginShipoutNext}[1]{}
5 \newcommand*{\AtBeginShipoutFirst}[1]{}
6 \newcommand*{\AtBeginShipoutDiscard}){}
7 \newcommand*{\AtBeginShipoutInit}){}
8 \newcommand*{\AtBeginShipoutAddToBox}[1]{}
9 \newcommand*{\AtBeginShipoutAddToBoxForeground}[1]{}
10 \newcommand*{\AtBeginShipoutUpperLeft}[1]{}
11 \newcommand*{\AtBeginShipoutUpperLeftForeground}[1]{}
12 \newcommand*{\AtBeginShipoutOriginalShipout}[1]{}
13 \def\AtBeginShipoutBoxWidth{Opt}
14 \def\AtBeginShipoutBoxHeight{Opt}
15 \def\AtBeginShipoutBoxDepth{Opt}
16

```

File 28 **lwarf-attachfile.sty**

§ 121 Package **attachfile**

(Emulates or patches code by SCOTT PAKIN.)

Pkg **attachfile** **attachfile** is patched for use by **lwarf**.



Metadata is ignored for now.

for HTML output: 1 \LWR@ProvidesPackagePass{attachfile}

Encloses each icon:

```

2 \newenvironment*{\LWR@attachfile@icon}
3 {
4     \begin{lateximage}*%
5         [-attachfile-]%
6         [%
7             \detokenize\expandafter{\atfi@icon@icon}-%
8             \detokenize\expandafter{\atfi@color@rgb}%
9         ]%
10 }
11 {
12     \end{lateximage}
13 }

```

Each icon is enclosed inside a **LWR@attachfile@icon** environment:

```

14 \xpretocmd{\atfi@acroGraph}{\LWR@attachfile@icon}{}{}
15 \xapptocmd{\atfi@acroGraph}{\endLWR@attachfile@icon}{}{}
16
17 \xpretocmd{\atfi@acroPaperclip}{\LWR@attachfile@icon}{}{}

```

```

18 \xapptocmd{\atfi@acroPaperclip}{\endLWR@attachfile@icon}{}{}
19
20 \xpretocmd{\atfi@acroPushPin}{\LWR@attachfile@icon}{}{}
21 \xapptocmd{\atfi@acroPushPin}{\endLWR@attachfile@icon}{}{}
22
23 \xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
24 \xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}

```

Disable PDF file embedding:

```
25 \DeclareRobustCommand{\atfi@embedfile}[1]{}
```

The displayed output for an \attachfile reference:

```

26 \newcommand*{\LWR@attachfile@appearance}(){}
27
28 \DeclareRobustCommand{\atfi@set@appearance}[1]{%
29     \def\LWR@attachfile@appearance{#1}%
30 }

```

A file annotation becomes a reference:

```

31 \DeclareRobustCommand{\atfi@insert@file@annot}[1]{%
32     \href{#1}{\LWR@attachfile@appearance}%
33 }

```

File 29 **l warp-attachfile2.sty**

§ 122 Package **attachfile2**

(Emulates or patches code by HEIKO OBERDIEK.)

Pkg **attachfile2** **attachfile2** is patched for use by **l warp**.



Metadata is ignored for now.

for HTML output: 1 \LWR@ProvidesPackagePass{attachfile2}

Adds memory of the selected color:

```

2 \def\LWR@attachfiletwo@color{}%
3
4 \define@key{AtFi}{color}{%
5     \def\LWR@attachfiletwo@color{#1}%
6     \HyColor@AttachfileColor{#1}%
7         \atfi@color@tex\atfi@color@inline\atfi@color@annot

```

```
8           {attachfile2}{color}%
9 }
```

Encloses each icon:

```
10 \newenvironment*{LWR@attachfile@icon}
11 {
12     \begin{lateximage} *%
13         [-attachfile-]%
14         [%
15             \detokenize\expandafter{\atfi@icon@icon}-%
16             \detokenize\expandafter{\LWR@attachfiletwo@color}%
17         ]%
18 }
19 {
20     \end{lateximage}
21 }
```

Each icon is enclosed inside a LWR@attachfile@icon environment:

```
22 \xpretocmd{\atfi@acroGraph}{\LWR@attachfile@icon}{}{}
23 \xapptocmd{\atfi@acroGraph}{\endLWR@attachfile@icon}{}{}
24
25 \xpretocmd{\atfi@acroPaperclip}{\LWR@attachfile@icon}{}{}
26 \xapptocmd{\atfi@acroPaperclip}{\endLWR@attachfile@icon}{}{}
27
28 \xpretocmd{\atfi@acroPushPin}{\LWR@attachfile@icon}{}{}
29 \xapptocmd{\atfi@acroPushPin}{\endLWR@attachfile@icon}{}{}
30
31 \xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
32 \xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}
```

Disable PDF file embedding:

```
33 \DeclareRobustCommand{\atfi@embedfile}[1]{}
```

The displayed output for an \attachfile reference:

```
34 \newcommand*{\LWR@attachfile@appearance}(){}
35
36 \def\atfi@set@appearance@icon{%
37     \atfi@set@appearance{\csname atfi@acro\atfi@icon@icon\endcsname}%
38 }
39
40 \DeclareRobustCommand{\atfi@set@appearance}[1]{%
41     \def\LWR@attachfile@appearance{\#1}%
42 }
```

A file annotation becomes a reference:

```
43 \DeclareRobustCommand{\atfi@insert@file@annot}[1]{%
44     \href{#1}{\LWR@attachfile@appearance}%
45 }
```

Modified for text color:

```
46 \DeclareRobustCommand{\notextattachfile}[2][]{%
47     \begingroup
48     \atfi@setup{#1}%
49     \ifatfi@print
50         \leavevmode
51         \begingroup
52             \HyColor@UseColor\atfi@color@tex
53             \LWR@textcurrentcolor{#2}%
54             l warp
54 \% \strut
55         \endgroup
56 \% \else
57 \%     \sbox\ltx@zero{#2\strut}%
58 \%     \makebox[\wd0]{}%
59     \fi
60     \endgroup
61 }
```

Modified to draw the icon:

```
62 \DeclareRobustCommand{\noattachfile}[1][]{%
63     \begingroup
64     \atfi@setup{#1}%
65     \atfi@set@appearance@icon
66     \ifatfi@print
67         \LWR@attachfile@appearance%
68         l warp
69 \% \expandafter
69 \% \atfi@refxform\csname atfi@appobj@\atfi@icon@icon\endcsname
70 \% \else
71 \%     \makebox[\atfi@appearancewidth]{}%
72     \fi
73     \endgroup
74 }
```

File 30 **l warp-authblk.sty**

§ 123 Package **authblk**

(Emulates or patches code by PATRICK W. DALY.)

Pkg authblk **authblk** is patched for HTML.

package support l warp supports the native L^AT_EX titling commands, and also supports the packages **authblk** and **titling**. If both are used, **authblk** should be loaded before **titling**.

\published and **\subtitle** If using the **titling** package, additional titlepage fields for **\published** and **\subtitle** may be added by using **\AddSubTitlePublished** in the preamble. See section 63.8.

(Emulates or patches code by PATRICK W. DALY.)

for HTML output: Require that **authblk** be loaded before **titling**:

```
1 \@ifpackageloaded{titling}{
2 \PackageError{l warp-authblk}
3 {Package authblk must be loaded before titling}
4 {Titling appends authblk's author macro, so authblk must be loaded first.}
5 }
6 {}
```

Load **authblk**:

```
7 \LWR@ProvidesPackagePass{authblk}
```

Patch to add a class for the affiliation:

```
8 \LetLtxMacro\LWRAB@affil\affil
9
10 \renewcommand{\affil}[2][]{%
11 \LWRAB@affil[#1]{\protect\InlineClass{affiliation}{#2}}%
12 }
```

Create an HTML break for an **\authorcr**:

```
13 \renewcommand*{\authorcr}{\protect\LWR@newlinebr}
```

File 31 l warp-axessibility.sty

§ 124 Package **axessibility**

Pkg axessibility **axessibility** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{axessibility}
2 \newcommand{\wrap}[1]{}
```

File 32 **l warp-axodraw2.sty**

§ 125 Package **axodraw2**

(Emulates or patches code by JOHN C. COLLINS, J.A.M. VERMASEREN.)

Pkg **axodraw2** **axodraw2** is patched for use by **l warp**.

for HTML output: 1 \LWR@ProvidesPackagePass{axodraw2}

2 \BeforeBeginEnvironment{axopicture}{\begin{lateximage}[(-axopicture-~\packagediagramname)]} \\ 3 \\ 4 \AfterEndEnvironment{axopicture}{\end{lateximage}}

File 33 **l warp-backref.sty**

§ 126 Package **backref**

(Emulates or patches code by DAVID CARLISLE AND SEBASTIAN RAHTZ.)

Pkg **backref** **backref** is patched for use by **l warp**.

⚠ loading Note that **backref** must be explicitly loaded, and is not automatically loaded by **hyperref** when generating HTML output.

for HTML output: 1 \LWR@ProvidesPackagePass{backref}

Force the **hyperref** option:

2 \def\backref{}{\let\backrefxxx\hyper@section@backref}

File 34 **l warp-balance.sty**

§ 127 Package **balance**

(Emulates or patches code by PATRICK W. DALY.)

Pkg **balance** Emulated.

for HTML output:

Discard all options for **l warp-balance**:

```
1 \LWR@ProvidesPackageDrop{balance}  
  
2 \newcommand*{\balance}{}  
3 \newcommand*{\nobalance}{}
```

File 35 **l warp-bibunits.sty**

§ 128 Package **bibunits**

(Emulates or patches code by THORSTEN HANSEN.)

Pkg **bibunits** **bibunits** is patched for use by **l warp**.

for **HTML output**:
1 \LWR@ProvidesPackagePass{bibunits}

2 \def\bu@bibdata{\BaseJobname}

File 36 **l warp-bigdelim.sty**

§ 129 Package **bigdelim**

(Emulates or patches code by PIET VAN OOSTRUM, ØYSTEIN BACHE, JERRY LEICHTER.)

Pkg **bigdelim** **bigdelim** is used as-is for print or *lateximage*, and patched for **HTML**.

The delimiters are displayed in **HTML** by printing the delimiter, the text, and a thick border across the side of the `\multirow` which indicates the actual height of the delimiter. The delimiter character is given a `` class of `ldelim` or `rdelim`, and the default css sets this to `font-size:200%`

⚠ use `\mrowcell` `\l delim` and `\r delim` use `\multirow`, so `\mrowcell` must be used in the proper number of empty cells in the same column below `\l delim` or `\r delim`, but not in cells which are above or below the delimiter:

```
\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\{}{2}{.25in}[left ] & c & d \\
\mrowcell{e & f} \\
<empty> & g & h \\
\end{tabular}
```

<>	a	b
left {	c	d
	e	f
<>	g	h

for HTML output: First, remove the temporary definitions of `\ldelim` and `\rdelim`, which were previously defined for tabular scanning in case `bigdelim` was not loaded:

```
1 \let\ldelim\relax
2 \let\rdelim\relax
```

Next, load the package's new definitions:

```
3 \LWR@ProvidesPackagePass{bigdelim}

\ldelim {\{1:delimiter\}} {\{2:#rows\}} {\{3:width\}} [\{4:text\}]
\rdelim
 4 \NewDocumentCommand{\LWR@HTML@ldelim}{m m m O{}}
 5 \renewcommand{\LWR@multirowborder}{right}%
 6 \multirow{#2}{#3}{#4} \InlineClass{\ldelim}{#1}%
 7 }
 8
 9 \LWR@formatted{\ldelim}
10
11 \NewDocumentCommand{\LWR@HTML@rdelim}{m m m O{}}
12 \renewcommand{\LWR@multirowborder}{left}%
13 \multirow{#2}{#3}{\InlineClass{\rdelim}{#1} #4}%
14 }
15
16 \LWR@formatted{\rdelim}
```

File 37 **l warp-bigstrut.sty**

§ 130 Package **bigstrut**

(Emulates or patches code by PIET VAN OOSTRUM, ØYSTEIN BACHE, JERRY LEICHTER.)

Pkg **bigstrut** **bigstrut** is used as-is for print or `lateximage`, and patched for HTML.

for HTML output:

```
1 \LWR@ProvidesPackagePass{bigstrut}
2 \LetLtxMacro{\LWR@origbigstrut}{\bigstrut}
3
4 \renewcommand{\bigstrut}[1][x]{}
5
6 \appto{\LWR@restoreorigformatting}{%
7 \LetLtxMacro{\bigstrut}{\LWR@origbigstrut}%
8 }
```

File 38 **l warp-blowup.sty**

§ 131 Package **blowup**

Pkg **blowup** **blowup** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{blowup}
2 \newcommand*\blowUp[1]{}
```

File 39 **l warp-booklet.sty**

§ 132 Package **booklet**

(Emulates or patches code by PETER WILSON.)

Pkg **booklet** **booklet** is nullified.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{booklet}[2009/09/02]
2 \newdimen\pageseplength
3 \newdimen\pagesepwidth
4 \newdimen\pagesepoffset
5 \newif\ifsidebyside \sidebysidetrue
6 \newif\ifuselandscape \uselandscapefalse
7 \newif\ifprintoption \printoptionfalse
8 \newcommand*\{\pagespersignature}[1]{}
9 \def\magstepminus#1{}
10 \newcommand*\{\target}[3]{}
11 \newcommand*\{\source}[3]{}
12 \newcommand*\{\setpdftargetpages}{}
13 \newcommand*\{\setdvipstargetpages}{}
14 \newcommand*\{\targettopbottom}{}
```

```
15 \newcommand*{\twoupemptypage}{}  
16 \newcommand*{\twoupclearpage}{}  
17 \newcommand*{\checkforlandscape}{}  


---


```

File 40 **l warp-bookmark.sty**

§ 133 Package **bookmark**

(Emulates or patches code by HEIKO OBERDIEK.)

Pkg **bookmark** **bookmark** is emulated.

for HTML output: Discard all options for **l warp-bookmark**:

```
1 \LWR@ProvidesPackageDrop{bookmark}  
  
2 \newcommand*{\bookmarksetup}[1]{}  
3 \newcommand*{\bookmarksetupnext}[1]{}  
4 \newcommand*{\bookmark}[2][]{  
5 \newcommand*{\bookmarkdefinestyle}[2]{}  
6 \newcommand*{\bookmarkget}[1]{}  
7 \newcommand{\BookmarkAtEnd}[1]{}
```

File 41 **l warp-booktabs.sty**

§ 134 Package **booktabs**

(Emulates or patches code by SIMON FEAR.)

Pkg **booktabs** **booktabs** is emulated during HTML output, and used as-is during print output and inside an HTML `lateximage`.

for HTML output: First, forget the placeholder macros:

```
1 \LetLtxMacro{\toprule}{\relax}  
2 \LetLtxMacro{\midrule}{\relax}  
3 \LetLtxMacro{\cmidrule}{\cline}  
4 \LetLtxMacro{\bottomrule}{\relax}  
5 \LetLtxMacro{\addlinespace}{\relax}  
6 \LetLtxMacro{\morecmidrules}{\relax}  
7 \LetLtxMacro{\specialrule}{\relax}  
8  
9 \LWR@ProvidesPackagePass{booktabs}
```

```
10 \DeclareDocumentCommand{\LWR@HTML@toprule}{o d()}{%
11     {%
12         \IfValueTF{#1}{%
13             {\LWR@docmidrule[#1] (){1-\arabic{LWR@tabletotalLaTeXcols}}}{%
14             {%
15                 \ifbool{FormatWP}{%
16                     {\LWR@docmidrule[#1] (){1-\arabic{LWR@tabletotalLaTeXcols}}}{%
17                     {\global\booltrue{\LWR@doingtbrule}}}{%
18                 }{%
19                     \LWR@getmynexttoken}%
20                 }{%
21 \LWR@expandableformatted{toprule}%
22             }{%
23 \DeclareDocumentCommand{\LWR@HTML@midrule}{o d()}{%
24     {%
25         \IfValueTF{#1}{%
26             {\LWR@docmidrule[#1] (){1-\arabic{LWR@tabletotalLaTeXcols}}}{%
27             {%
28                 \ifbool{FormatWP}{%
29                     {\LWR@docmidrule[#1] (){1-\arabic{LWR@tabletotalLaTeXcols}}}{%
30                     {\addtocounter{LWR@hlines}{1}}}{%
31                 }{%
32                     \LWR@getmynexttoken}%
33                 }{%
34 \LWR@expandableformatted{midrule}%
35             }{%
36 \DeclareDocumentCommand{\LWR@HTML@cmidrule}{O{\LWR@cmidrulewidth} d() m}{%
37     {\LWR@docmidrule[#1] (#2){#3}}{%
38     \LWR@getmynexttoken}{%
39 }{%
40     }{%
41 \LWR@expandableformatted{cmidrule}%
42     }{%
43 \DeclareDocumentCommand{\LWR@HTML@bottomrule}{o d()}{%
44     {%
45         \IfValueTF{#1}{%
46             {\LWR@docmidrule[#1] (){1-\arabic{LWR@tabletotalLaTeXcols}}}{%
47             {%
48                 \ifbool{FormatWP}{%
49                     {\LWR@docmidrule[#1] (){1-\arabic{LWR@tabletotalLaTeXcols}}}{%
50                     {\global\booltrue{\LWR@doingtbrule}}}{%
51                 }{%
52                     \LWR@getmynexttoken}{%
53                 }{%
54 \LWR@expandableformatted{bottomrule}%
55             }{%
56 \DeclareDocumentCommand{\LWR@HTML@addlinespace}{o}{%
57     }{%
58 \LWR@expandableformatted{addlinespace}%
59 }}
```

```
60 \DeclareDocumentCommand{\LWR@HTML@morecmidrules}{}{}%
61
62 \LWR@expandableformatted{morecmidrules}
63
64 \DeclareDocumentCommand{\LWR@HTML@specialrule}{m m m d()}{%
65     {\LWR@docmidrule[#1] (){1-\arabic{LWR@tabletotalLaTeXcols}}\LWR@getmynexttoken}%
66
67 \LWR@expandableformatted{specialrule}
```

File 42 **l warp-bophook.sty**

§ 135 Package **bophook**

Pkg **bophook** **bophook** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{bophook}

2 \newcommand*{\AtBeginPage}[1]{}
3 \newcommand*{\PageLayout}[1]{}
```

File 43 **l warp-boxedminipage.sty**

§ 136 Package **boxedminipage**

Pkg **boxedminipage** **boxedminipage** is superceded by **boxedminipage2e**.

for HTML output:

```
1 \LWR@loadnever{boxedminipage}{boxedminipage2e}
```

File 44 **l warp-boxedminipage2e.sty**

§ 137 Package **boxedminipage2e**

(Emulates or patches code by SCOTT PAKIN.)

Pkg **boxedminipage2e** **boxedminipage2e** is emulated.

for HTML output: Discard all options for **l warp-boxedminipage2e**:

```
1 \LWR@ProvidesPackageDrop{boxedminipage2e}

2 \newenvironment{boxedminipage}{%
```

```

3 \begin{BlockClass}{framebox}%
4 \minipage%
5 }
6 {
7 \endminipage%
8 \end{BlockClass}
9 }
```

File 45 **l warp-breakurl.sty**

§ 138 Package **breakurl**

(Emulates or patches code by VILAR CAMARA NETO.)

Pkg **breakurl** **breakurl** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{breakurl}

```

2 \LetLtxMacro\burl\url
3
4 \NewDocumentCommand{\LWR@burlaltb}{O{} +m m}{%
5 \LWR@ensuredoingapar%
6 \LWR@subhyperref{#2}%
7 \LWR@subhyperreftext{#3}%
8 \endgroup% restore catcodes
9 }
10
11 \newrobustcmd*\burlalt{%
12 \begingroup%
13 \catcode`\#=12%
14 \catcode`\%=12%
15 \catcode`\&=12%
16 \catcode`\~=12%
17 \catcode`\_=12%
18 \LWR@burlaltb%
19 }
20
21 \LetLtxMacro\urlalt\burlalt
```

File 46 **l warp-breqn.sty**

§ 139 Package **breqn**

(Emulates or patches code by MICHAEL J. DOWNES, MORTEN HØGHOLM.)

Pkg breqn breqn is patched for use by l warp.

⚠ darray darray is not supported.

⚠ MATHJAX MathJax does not support breqn.

for HTML output:

```
1 \LWR@ProvidesPackagePass{breqn}

2 \setkeys{breqn}{spread={5pt}}
3
4 \def\eqnumside{R}
5 % \def\eqnumplace{T}
6
7 \BeforeBeginEnvironment{dmath}{
8     \begin{BlockClass}{displaymathnumbered}
9         \LWR@newautoidanchor%
10        \booltrue{\LWR@indisplaymathimage}%
11        \begin{lateximage}[-breqn dmath- \mathimagename]
12    }
13
14 \AfterEndEnvironment{dmath}{
15     \end{lateximage}\end{BlockClass}
16 }
17
18 \BeforeBeginEnvironment{dmath*}{
19     \begin{BlockClass}{displaymath}
20         \LWR@newautoidanchor%
21        \booltrue{\LWR@indisplaymathimage}%
22        \begin{lateximage}[-breqn dmath*- \mathimagename]
23    }
24
25 \AfterEndEnvironment{dmath*}{
26     \end{lateximage}\end{BlockClass}
27 }
28
29 \BeforeBeginEnvironment{dseries}{
30     \begin{BlockClass}{displaymathnumbered}
31         \LWR@newautoidanchor%
32        \booltrue{\LWR@indisplaymathimage}%
33        \begin{lateximage}[-breqn dseries- \mathimagename]
34    }
35
36 \AfterEndEnvironment{dseries}{
37     \end{lateximage}\end{BlockClass}
38 }
39
40 \BeforeBeginEnvironment{dseries*}{
41     \begin{BlockClass}{displaymath}
42         \LWR@newautoidanchor%
43        \booltrue{\LWR@indisplaymathimage}%
```

```
44     \begin{lateximage}[-breqn dseries*- \mathimagename]
45 }
46
47 \AfterEndEnvironment{dseries*}{
48     \end{lateximage}\end{BlockClass}
49 }
50
51 \BeforeBeginEnvironment{dgroup}){
52     \begin{BlockClass}{displaymath}
53     \LWR@newauto{dgroup}{\mathimagename}%
54     \booltrue{\LWR@indisplaymathimage}%
55     \begin{lateximage}[-breqn dgroup- \mathimagename]
56 }
57
58 \AfterEndEnvironment{dgroup}){
59     \end{lateximage}\end{BlockClass}
60 }
61
62 \BeforeBeginEnvironment{dgroup*}){
63     \begin{BlockClass}{displaymath}
64     \LWR@newauto{dgroup*}{\mathimagename}%
65     \booltrue{\LWR@indisplaymathimage}%
66     \begin{lateximage}[-breqn dgroup*- \mathimagename]
67 }
68
69 \AfterEndEnvironment{dgroup*}){
70     \end{lateximage}\end{BlockClass}
71 }
```

File 47 **l warp-bxpapersize.sty**

§ 140 Package **bxpapersize**

Pkg **bxpapersize** **bxpapersize** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{bxpapersize}

2 \providecommand*\papersizesetup{\bxpapersizesetup}
3 \newcommand*\bxpapersizesetup[1]{}
```

File 48 **l warp-bytefield.sty**

§ 141 Package **bytefield**

(Emulates or patches code by SCOTT PAKIN.)

Pkg bytefield **bytefield** is patched for use by **l warp**.

for HTML output:

```
1 \LWR@ProvidesPackagePass{bytefield}
2 \BeforeBeginEnvironment{bytefield}{\begin{ lateximage }[(-bytefield-\~\packagediagramname)]}
3
4 \AfterEndEnvironment{bytefield}{\end{ lateximage }}
```

File 49 **l warp-cancel.sty**

§ 142 Package **cancel**

Pkg cancel **cancel** is used as-is for SVG math, and emulated for HTML text output.

for HTML output:

```
1 \LWR@origRequirePackage{l warp-xcolor}%
2 \LWR@ProvidesPackagePass{cancel}
```

\cancelto is math-only, so is used as-is.

```
3 \LetLtxMacro{\LWR@origcancel}{\cancel}
4 \LetLtxMacro{\LWR@origbcancel}{\bcancel}
5 \LetLtxMacro{\LWR@origxcancel}{\xcancel}
6
7 \appto{\LWR@restoreorigformatting}{%
8 \LetLtxMacro{\cancel}{\LWR@origcancel}%
9 \LetLtxMacro{\bcancel}{\LWR@origbcancel}%
10 \LetLtxMacro{\xcancel}{\LWR@origxcancel}%
11 }
```

\LWR@cancelcolor {{<text>}} {{<color>}} {{<class>}} {{<colorstyle>}} {{<FormatWPstyle>}}

Add colors if not empty:

```
12 \newcommand{\LWR@cancelcolor}[5]{%
13 \ifcsempty{#2}{%
14 {\LWR@HTMLTextstyle{#5}{#3}{#1}}}}
```

```

15 {\LWR@htmlspanclass [#5:#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}}%
16 }

\cancel {<text>}
17 \DeclareRobustCommand{\cancel}[1]{%
18 \begingroup%
19 \CancelColor%
20 \LWR@findcurrenttextcolor%
21 \color{black}%
22 \LWR@cancelcolor{#1}{\LWR@tempcolor}{sout}{text-decoration-color}%
23     {text-decoration:line-through}%
24 \endgroup%
25 }
26
27 \LetLtxMacro\bcancel\cancel
28 \LetLtxMacro\xcancel\cancel

```

File 50 **l warp-canoniclayout.sty**

§ 143 Package **canoniclayout**

Pkg **canoniclayout** **canoniclayout** is ignored.

for HTML output: s1 \LWR@ProvidesPackageDrop{canoniclayout}

 2 \newcommand*{\currentfontletters}{}%
 3 \newcommand*{\charactersperpage}{}%

File 51 **l warp-caption.sty**

§ 144 Package **caption**

(Emulates or patches code by AXEL SOMMERFELDT.)

Pkg **caption** **caption** is patched for use by **l warp**.

for HTML output: 1 \LWR@ProvidesPackagePass{caption}

 2 \renewcommand\caption@ibox[3]{%
 3 \@testopt{\caption@ibox[#1]{#2}{#3}}{%
 4 % \wd\@tempboxa%
 5 \linewidth\ l warp
 6 }%}

```
7 \% \LWR@traceinfo{caption@ibox: done}%
8 }

9 \long\def\caption@iibox#1#2#3[#4]{%
10   \atestopt{\caption@iibox{#1}{#2}{#3}{#4}}\captionbox@hj@default
11 }

12 \long\def\caption@iibox#1#2#3[#4][#5]{%
13 \% \setbox\@tempboxa\hbox{#6}%
14 \begingroup
15 #1\% set \caption@position
16 \caption@iftop{%
17   \LWR@traceinfo{caption@iibox top}%
18 \endgroup
19 \parbox[t]{#4}{%
20   #1\relax
21   \caption@setposition t%
22 \% \vbox{\caption#2{#3}}%
23 {\caption#2{#3}}\l warp
24 \% \captionbox@hrule
25 \% \csname caption@hj@#5\endcsname
26 \% \unhbox\@tempboxa
27 #6\l warp
28 }%
29 }{%
30 \LWR@traceinfo{caption@iibox bottom}%
31 \endgroup
32 \parbox[b]{#4}{%
33 #1\relax
34 \caption@setposition b%
35 \% \csname caption@hj@#5\endcsname
36 \% \unhbox\@tempboxa
37 #6\l warp
38 \% \captionbox@hrule
39 \% \vtop{\caption#2{#3}}%
40 {\caption#2{#3}}\l warp
41 }%
42 }%
43 \LWR@traceinfo{caption@iibox: done}%
44 }
45

46 \def\caption@caption{%
47 \caption@iftype
48 {%
49 \caption@checkgrouplevel\@empty\caption
50 \caption@star
51 {\caption@refstepcounter\@capttype}%
52 {\caption@dblarg{\@caption\@capttype}}}%
53 {\caption@Error{\noexpand\caption outside float}}%
```

```
54      \caption@gobble}%
55 }
56
57 \long\def\caption@@caption#1[#2]#3{%
58   \ifcaption@star \else
59     \caption@prepareanchor{#1}{#2}%
60     \memcaptioninfo{#1}{\csname the#1\endcsname}{#2}{#3}%
61     \nameuse{nag@hascaptiontrue}%
62   \fi
63
64   \par
65   \caption@beginex{#1}{#2}{#3}%
66   \caption@setfloatcapt{%
67     \caption@boxrestore
68     \if@minipage
69       \setminipage
70     \fi
71     \caption@normalsize
72     \ifcaption@star
73       \let\caption@makeanchor\@firstofone
74     \fi
75     \makecaption{\csname fnum@\#1\endcsname}%
76     {\ignorespaces\caption@makeanchor{#3}}\par
77     \caption@if@minipage\@minipagetrue\@minipagefalse}%
78   \caption@end%
79 }
80
81 \caption@@make {<caption label>} {<caption text>}
82
83 \renewcommand\caption@@make[2]{%
84   \LWR@startpars% l warp
85   \sbox{\tempboxa{#1}}%
86   \ifdim\wd\tempboxa=\z@
87     \let\caption@lsep\relax
88   \fi
89   \caption@ifempty{#2}{%
90     \let\caption@lsep\empty
91     \let\caption@tfmt\@firstofone
92   }%
93   \setpar{\LWR@closeparagraph\@@par}% l warp
94   \caption@applyfont
95   \caption@fmt
96   {\ifcaption@star\else
97     \begingroup
98       \captionlabelfont
99       #1%
100     \endgroup
101   \fi}%
102 }
```

```

98      {\ifcaption@star\else
99          \begingroup
100         \caption@iflf\captionlabelfont
101         \relax\caption@lsep
102         \endgroup
103     \fi}%
104 {{\captionontextfont
105   \caption@ifstrut
106   {\vrule\@height\ht\strutbox\@width\z@}%
107   {}%
108   \nobreak\hskip\z@skip % enable hyphenation
109   \caption@tfmt{\#2}
110 \LWR@ensuredoingapar% lwarf
111   \caption@ifstrut
112   {\ifhmode\@finalstrut\strutbox\fi}%
113   {}%
114   \par}}%
115 \LWR@stoppars% lwarf
116 }

\caption@@make@  {<}> {<}>
117 \renewcommand{\caption@@make@}[2]{%
118   \caption@stepthecounter
119   \caption@beginhook
120   \caption@@make{\#1}{\#2}%
121   \caption@endhook
122 }

123 % \DeclareCaptionBox{none}{\#2}
124 \DeclareCaptionBox{parbox}{%
125 \#2%
126 }
127 \DeclareCaptionBox{colorbox}{%
128 \#2%
129 }

```

File 52 **lwarf-caption2.sty**

§ 145 Package **caption2**

Pkg **caption2** **caption2** is not used. The user is recommended to use **caption** instead.

for HTML output: 1 \LWR@loadnever{caption2}{caption}

File 53 **l warp-cases.sty**

§ 146 Package **cases**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg cases **cases** is patched for use by **l warp**.

 **MATHJAX** MathJax does not support **cases**.

for HTML output: 1 \LWR@ProvidesPackagePass{cases}

```
2 \BeforeBeginEnvironment{numcases} {
3     \begin{BlockClass}{displaymathnumbered}
4     \LWR@newautoidanchor%
5     \booltrue{\LWR@indisplaymathimage}%
6     \begin{lateximage}[-cases- \mathimagename]
7 }
8
9 \AfterEndEnvironment{numcases} {
10    \end{lateximage}\end{BlockClass}
11 }
12
13 \BeforeBeginEnvironment{subnumcases} {
14    \begin{BlockClass}{displaymathnumbered}
15    \LWR@newautoidanchor%
16    \booltrue{\LWR@indisplaymathimage}%
17    \begin{lateximage}[-cases- \mathimagename]
18 }
19
20 \AfterEndEnvironment{subnumcases} {
21    \end{lateximage}\end{BlockClass}
22 }
```

File 54 **l warp-ccaption.sty**

§ 147 Package **ccaption**

Pkg ccaption **ccaption** is not used. The user is recommended to use **caption** instead.

for HTML output: 1 \LWR@loadnever{ccaption}{caption}

File 55 **l warp-changebar.sty**

§ 148 Package **changebar**

Pkg **changebar** **changebar** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{changebar}

2 \newcommand*{\cbstart}={}
3 \newcommand*{\cbend}={}
4 \newenvironment*{\changebar}{}{}
5 \newcommand*{\cbdelete}={}
6 \newcommand*{\nochnagebars}={}
7 \newcommand*{\cbcolor}[1]{}
8 \newlength{\changebarwidth}
9 \newlength{\deletebarwidth}
10 \newlength{\changebarsep}
11 \newcounter{changebargrey}
```

File 56 **l warp-changepage.sty**

§ 149 Package **changepage**

(Emulates or patches code by PETER WILSON.)

Pkg **changepage** **changepage** is emulated.

for HTML output: Discard all options for **l warp-changepage**:

```
1 \LWR@ProvidesPackageDrop{changepage}

2 \newif\ifoddpage
3 \DeclareRobustCommand{\checkoddpage}{\oddpagetrue}
4 \DeclareRobustCommand{\changetext}[5]{}
5 \DeclareRobustCommand{\changepage}[9]{}
6
7 \@ifundefined{adjustwidth}{}
8 \newenvironment{adjustwidth}[2]{}{}
9 \newenvironment{adjustwidth*}[2]{}{}
10 }{
11 \renewenvironment{adjustwidth}[2]{}{}
12 \renewenvironment{adjustwidth*}[2]{}{}
13 }
```

```
14 \DeclareDocumentCommand{\strictpagecheck}{}{  
15 \DeclareDocumentCommand{\easypagecheck}{}{}
```

File 57 **l warp-chngpage.sty**

§ 150 Package **chngpage**

(Emulates or patches code by PETER WILSON.)

Pkg chngpage **chngpage** is emulated.

for HTML output: Discard all options for **l warp-chngpage**:

```
1 \LWR@ProvidesPackageDrop{chngpage}  
2 \LWR@origRequirePackage{changegetPage}
```

File 58 **l warp-chappg.sty**

§ 151 Package **chappg**

(Emulates or patches code by ROBIN FAIRBAIRNS.)

Pkg chappg **chappg** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{chappg}

```
2 \renewcommand{\pagenumbering}[2][]{  
3 \providecommand{\chappgsep}{--}}
```

File 59 **l warp-chapterbib.sty**

§ 152 Package **chapterbib**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg chapterbib **chapterbib** is patched for use by **l warp**.

for HTML output: 1 \LWR@ProvidesPackagePass{chapterbib}

```
2 \xdef\@savedjobname{\BaseJobname}  
3 \let\@currentipfile\@savedjobname
```

File 60 **l warp-chemfig.sty**

§ 153 Package **chemfig**

(Emulates or patches code by CHRISTIAN TELLECHEA.)

Pkg **chemfig** **chemfig** is patched for use by **l warp**.

The images are not hashed because they depend on external settings which may be changed at any time, and are unlikely to be reused inline anyhow.

for HTML output:

```
1 \LWR@ProvidesPackagePass{chemfig}

2 \LetLtxMacro{\LWR@chemfig}{\origchemfig\chemfig}
3
4 \DeclareDocumentCommand{\chemfig}{s O{} O{} m}{%
5   \begin{ lateximage } [(-chemfig--\packagediagramname)]{%
6     \IfBooleanTF{#1}{%
7       \LWR@chemfig*[#2][#3]{#4}%
8     }{%
9       \LWR@chemfig@origchemfig[#2][#3]{#4}%
10    }%
11  }%
12 }%
13
14 \LetLtxMacro{\LWR@chemfig}{\origCF@lewis@b\CF@lewis@b}
15
16 \def\CF@lewis@b#1#2{%
17 \begin{ lateximage } [(-chemfig--\packagediagramname)]{%
18 \LWR@chemfig@origCF@lewis@b{#1}{#2}%
19 }%
20 }%
21
22 \preto{\schemestart}{\begin{ lateximage } [(-chemfig--\packagediagramname)]{%
23 \appto{\CF@schemestop}{\end{ lateximage }}%
24
25 \LetLtxMacro{\LWR@chemfig}{\origchemleft\chemleft}
26
27 \def\chemleft#1#2\chemright#3{%
28 \begin{ lateximage } [(-chemfig--\packagediagramname)]{%
29 \LWR@chemfig@origchemleft#1#2\chemright#3}%
30 }%
31 }%
32
33 \LetLtxMacro{\LWR@chemfig}{\origchemup\chemup}
```

```

34
35 \def\chemup#1#2\chemdown#3{%
36 \begin{lateximage} [(-chemfig-~\packagediagramname)]%
37 \LWR@chemfig@origchemup#1#2\chemdown#3%
38 \end{lateximage}%
39 }

```

File 61 **l warp-chemformula.sty**

§ 154 Package **chemformula**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg **chemformula** **chemformula** is patched for use by **l warp**.

The SVG images are hashed according to contents and local options. Global options are assumed to be constant document-wide.

⚠ MATHJAX **chemformula** with **MATHJAX** **chemformula** works best without MATHJAX. If MATHJAX is used, `\displaymathother` must be used before array, and then `\displaymathnormal` may be used after. (The **chemformula** package adapts to array, but does not know about MATHJAX, and MATHJAX does not know about **chemformula**.)

While using MATHJAX, `\displaymathother` may also be used for other forms of display and inline math which contain **chemformula** expressions.

for HTML output: 1 `\LWR@ProvidesPackagePass{chemformula}` [2017/03/23]

2 `\ExplSyntaxOn`

`\ch` Enclose in an inline SVG image or MathJax. The alt tag is the contents of the `\ch` expression. The filename is hashed, and also has additional hashing information based on the local options.

3 `\RenewDocumentCommand \ch { O{}m }`
4 `{%`

To work inside align with `\displaymathother`, a simple version must be used to work with **chemformula**'s adaptation to align.

```

5   \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
6   {
7     \chemformula_ch:nn {#1} {#2}%
8   } original

```

If used as the outer level, must temporarily ensure MATHJAX is disabled:

```

9      {
10     \begingroup%
11     \boolfalse{mathjax}%

```

An inline image is used, adjusted for the baseline:

```

12    \LWR@subsingle$*{\% l warp
13      \textbackslash{}ch\{\LWR@HTMLsanitize{\#2}\}\% alt text
14    }{%
15      \protect\LWR@HTMLsanitize{\detokenize\expandafter{\#1}}\% add'1 hashing
16    }%
17    {%
18      \chemformula_ch:nn {\#1} {\#2}\% original
19    }%
20    \endgroup%
21  }
22 }

```

\chcpd Similar to \ch.

```

23 \cs_gset_protected:Npn \chemformula_chcpd:nn #1#2
24 {
25   \begingroup%
26   \boolfalse{mathjax}%
27   \LWR@subsingle$*{\% l warp
28     \textbackslash{}chcpd\{\LWR@HTMLsanitize{\#2}\}\%
29   }{%
30     \protect\LWR@HTMLsanitize{\detokenize\expandafter{\#1}}\%
31   }{%
32     \group_begin:
33       \tl_if_blank:nF {\#2}
34     {
35       \keys_set:nn {chemformula} {\#1}
36       \__chemformula_save_catcodes:
37       \__chemformula_sanitize:Nn
38         \l__chemformula_chemformula_tmpa_tl
39         {\#2}
40       \__chemformula_input_compound_no_check:NV
41         \l__chemformula_compound_tl
42         \l__chemformula_chemformula_tmpa_tl
43       \__chemformula_prepare_output:N \l__chemformula_compound_tl
44       \chemformula_write:V \l__chemformula_compound_tl
45     }
46   \group_end:
47 }
48 \endgroup
49 }

```

\charrow If standalone, appears in a regular `lateximage`.

```

50 \RenewDocumentCommand \charrow { mO{}O{} } 
51 {
52   \begin{latentimage}[(chemformula- charrow)]
53   \group_begin:
54     \__chemformula_draw_arrow:nnn {#1} {#2} {#3}
55   \group_end:
56   \end{latentimage}
57 }

```

\chname If standalone, appears in a regular `latentimage`, hashed according to contents.

```

58 \RenewDocumentCommand \chname { R(){}R(){} }
59 {
60   \begin{latentimage}*[%]
61     \textbackslash\chname(\LWR@HTMLsanitize{#1})(\LWR@HTMLsanitize{#2})
62   ]%
63   \chemformula_chwritebelow:nn {#1} {#2}
64   \end{latentimage}
65 }

```

\chlewis Placed inline, hashed according to contents and options.

```

66 \RenewDocumentCommand \chlewis { O{}mm }
67 {
68   \begingroup%
69   \boolfalse{mathjax}%
70   \LWR@subsingle dollar*\textbackslash\chlewis\{#2\}\{#3\}%
71   {
72     \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
73   }%
74   \chemformula_lewis:nnn {#1} {#2} {#3}
75 }
76 \endgroup%
77 }

```

lwarf redefines the \$ character, so special handling is required to escape math expressions inside \ch.

This boolean tracks a new kind of escaped math:

```
78 \bool_new:N      \l__chemformula_first_last_LWRdollar_bool
```

\chemformula_input_escape_math

Adds additional escaping for the new dollar definition:

```

79 \cs_gset_protected:Npn \__chemformula_input_escape_math:n #1
80   {

```

```

81      \__chemformula_first_last_math:n {#1}
82      \bool_if:NT \l_chemformula_first_last_dollar_bool
83      {
84          \bool_set_true:N \l_chemformula_first_last_math_bool
85          \__chemformula_read_escape_dollar:w #1 \q_nil
86      }
87      \bool_if:NT \l_chemformula_first_last_mathbraces_bool
88      {
89          \bool_set_true:N \l_chemformula_first_last_math_bool
90          \__chemformula_read_escape_mathbraces:w #1 \q_nil
91      }

```

Added by **lwarp**:

```

92      \bool_if:NT \l_chemformula_first_last_LWRdollar_bool%      lwarp
93      {
94          \bool_set_true:N \l_chemformula_first_last_math_bool%  lwarp
95          \__chemformula_read_escape_LWRdollar:w #1 \q_nil%    lwarp
96      }
97  }

```

\chemformula_read_escape_LWRdollar

The following parses the contents inside the new dollars.

lwarp keeps the dollar as its original math shift until the document starts. While **chemmacros** is being patched, the dollar must temporarily be set to its new meaning during the following definition.

```

98 \begingroup
99 \catcode`\$=\active
100
101 \cs_new_protected:Npn \__chemformula_read_escape_LWRdollar:w $$\q_nil
102 {
103     \__chemformula_read_escape_math:n {#1}
104 }
105
106 \endgroup

```

\chemformula_bool_set_if_first_last

The following looks at the first and last tokens for delimiters to escape math inside \ch. The original definition is modified to look for the control sequences which are used by the new meaning of \$.

```

107 \cs_new_protected:Npn \__chemformula_bool_cs_set_if_first_last:NnNN #1#2#3#4
108 {
109     \int_zero:N \l_chemformula_tmpa_int
110     \int_zero:N \l_chemformula_tmpb_int

```

```

111      \int_set:Nn \l__chemformula_tmpa_int { \tl_count:n {#2} }
112      \tl_map_inline:nn {#2}
113      {
114          \int_incr:N \l__chemformula_tmpb_int
115          \int_compare:nT { \l__chemformula_tmpb_int = 1 }
116      }

```

At the start, the `cs_` version compares control sequences:

```

117          \ifdefstreq{##1}{#3}%
118          {
119              \bool_set_true:N #1
120          }%
121          {}
122      }

```

At the end, compare more control sequences:

```

123          \int_compare:nT { \l__chemformula_tmpb_int = \l__chemformula_tmpa_int }
124          {
125              \ifdefstreq{##1}{#4}
126              {}
127              {
128                  \bool_set_false:N #1
129              }
130          }
131      }
132  }

```

\chemformula_first_last_math

Modified to check for the new meaning of \$ at first/last:

```

133 \cs_gset_protected:Npn \__chemformula_first_last_math:n #1
134  {
135      \bool_set_false:N \l__chemformula_first_last_math_bool
136      \bool_set_false:N \l__chemformula_first_last_dollar_bool
137      \bool_set_false:N \l__chemformula_first_last_LWRdollar_bool% l warp
138      \bool_set_false:N \l__chemformula_first_last_mathbraces_bool
139      \__chemformula_bool_set_if_first_last:Nnnn
140          \l__chemformula_first_last_dollar_bool
141          {#1}
142          { $ } { $ }
143      \bool_if:NF \l__chemformula_first_last_dollar_bool
144      {
145          \__chemformula_bool_set_if_first_last:Nnnn
146          \l__chemformula_first_last_mathbraces_bool
147          {#1}
148          { \( } { \) }

```

Added by **l warp**:

```

149      \bool_if:NF \l__chemformula_first_last_mathbraces_bool%    l warp
150      {
151          \__chemformula_bool_cs_set_if_first_last:NnNN
152          \l__chemformula_first_last_LWRdollar_bool
153          {#1}
154          { \LWR@newsingledollar } { \LWR@newsingledollar }
155      }%
156      l warp
157  }
158 \ExplSyntaxOff

```

File 62 **l warp-chemgreek.sty**

§ 155 Package **chemgreek**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg **chemgreek** **chemgreek** is patched for use by **l warp**.

Greek symbols

To use text-mode symbols, use packages **textalpha** or **textgreek**. Using the other packages supported by **chemgreek** will result in math-mode greek characters, which will result in SVG images being used. These images will be hashed.

⚠ package selection

If using X_ET_EX or Lua_ET_EX, select the **fontspec** mapping:

```
\selectchemgreekmapping{fontspec}
```

for HTML output: 1 \LWR@ProvidesPackagePass{chemgreek} [2016/02/10]

```

2 \ExplSyntaxOn
3
4 \cs_gset_protected:Npn \chemgreek_text:n #1
5   { { \text {#1} } }
6
7 \appto\LWR@restoreorigformatting{%
8 \cs_set_protected:Npn \chemgreek_text:n #1%
9   { \ensuremath { \text {#1} } } }%
10 }
11
12 \ExplSyntaxOff

```

File 63 **l warp-chemmacros.sty**

§ 156 Package **chemmacros**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg **chemmacros** **chemmacros** is patched for use by **l warp**.

for HTML output: `1 \LWR@ProvidesPackagePass{chemmacros}`

SVG file hashing assumes that the relevant options are constant for the entire document.

§ 156.1 **Changes to the user's document**

⚠ `\makepolymerdelims` When using `\makepolymerdelims`, enclose the entire expression inside a `polymerdelims` environment, such as (from the **chemmacros** manual):

```
\begin{polymerdelims}
\chemfig{-[@{op,.75}]CH_2-CH(-[6]Cl)-[@{cl,0.25}]}
\makepolymerdelims{5pt}[27pt]{op}{cl}
\end{polymerdelims}
```

⚠ `redox reactions` Redox reactions must be enclosed inside a `redoxreaction` environment. For print output, extra space must be included above and/or below the result, so they are declared as arguments to the environment, instead of being manually entered as per the **chemmacros** manual. For HTML output, the extra space is ignored and a `latexitimage` is used instead.

```
\begin{redoxreaction}{7mm}{7mm}
\OX{a,Na} $\rightarrow$ \OX{b,Na}\pch\redox(a,b){oxidation}
\end{redoxreaction}
```

§ 156.2 Code

§ 156.3 Loading modules

Patching **chemmacros** modules must be done `\AtBeginDocument`, since modules are invoked by the user in the preamble, and each patch is only done if the module is loaded.

```
2 \ExplSyntaxOn
3
4 \newcommand{\@ifchemmacrosmoduleloaded}[1]{%
5 \ifl@aded{\c__chemmacros_module_extension_tl}{\c__chemmacros_module_prefix_tl.\#1}%
6 }
7
8 \ExplSyntaxOff
```

§ 156.4 New environments

`\makepolymerdelims` and redox reactions must be enclosed in a `lateximage` during HTML output. These environments are provided here in HTML mode, and in the **lwarp** core in print mode, as a high-level semantic syntax which automatically embeds the contents in a `lateximage` with an appropriate `alt` tag.

Env `polymerdelims`

```
9 \DeclareDocumentEnvironment{polymerdelims}{}{%
10 {\begin{lateximage}[(-chemmacros-polymer)]}}
11 {\end{lateximage}}}
```

Env `redoxreaction` `{<space above>} {<space below>}`

For HTML output, the above and below space is ignored, and a `lateximage` is used instead. For the print output version, see section 83.

```
12 \DeclareDocumentEnvironment{redoxreaction}{m m}{%
13 {\begin{lateximage}[(-chemmacros-redoxreaction)]}}
14 {\end{lateximage}}}
```

```
15 \ExplSyntaxOn
```

§ 156.5 Acid-base

```
16 \AtBeginDocument{  
17 \@ifchemmacrosmoduleloaded{acid-base}{  
18 \PackageInfo{lwarf}{Patching~chemmacros~module~acid-base}  
19  
20 \cs_gset_protected:Npn \chemmacros_p:n #1  
21 {  
22     \begingroup  
23     \boolearn{mathjax}  
24     \LWR@subsingle dollar*{  
25         \textbackslash{}p\{\LWR@HTMLsanitize{\#1}\}}  
26     }{  
27         chemmacrosp\protect\LWR@HTMLsanitize{\detokenize\expandafter{\#1}}%  
28     }{  
29     \group_begin:  
30         \mbox  
31         {  
32             \chemmacros_p_style:n {p}  
33             \ensuremath {\#1}  
34         }  
35     \group_end:  
36     }  
37     \endgroup  
38 }  
39  
40 \RenewDocumentCommand \pH {} {  
41     \begingroup  
42     \boolearn{mathjax}  
43     \LWR@subsingle dollar*{\textbackslash{}pH}{chemmacro}{  
44         \chemmacros_p:n { \chemmacros_chemformula:n {H} }  
45     }  
46     \endgroup  
47 }  
48  
49 \RenewDocumentCommand \pOH {} {  
50     \begingroup  
51     \boolearn{mathjax}  
52     \LWR@subsingle dollar*{\textbackslash{}pOH}{chemmacro}{  
53         \chemmacros_p:n { \chemmacros_chemformula:n {OH} }  
54     }  
55     \endgroup  
56 }  
57  
58 \RenewDocumentCommand \pKa {O{}}{  
59 {  
60     \begingroup  
61     \boolearn{mathjax}  
62     \LWR@subsingle dollar*{\textbackslash{}pKa{[]\#1{}}}{chemmacro #1}{  
63         \chemmacros_p:n {
```

```
64      {
65          \Ka \ifblank {\#1} {}
66          { {} \c_math_subscript_token { \chemmacros_bold:n {\#1} } }
67      }
68  }
69  \endgroup
70 }
71
72 \RenewDocumentCommand \pKb {O{}}
73 {
74     \begingroup
75     \boolfalse{mathjax}
76     \LWR@subsingledollar*\{\textbackslash{}pKb{[]}\#1{[]}\}{chemmacros #1}{
77         \chemmacros_p:n
78     {
79         \Kb \ifblank {\#1} {}
80         { {} \c_math_subscript_token { \chemmacros_bold:n {\#1} } }
81     }
82 }
83 \endgroup
84 }
85
86 \LetLtxMacro \LWR@chemmacros@origKa \Ka
87 \renewcommand*{\Ka}{%
88     \begingroup
89     \boolfalse{mathjax}
90     \LWR@subsingledollar*\{\textbackslash{}Ka\}{chemmacros}{%
91         \LWR@chemmacros@origKa%
92     }%
93     \endgroup
94 }
95
96 \LetLtxMacro \LWR@chemmacros@origKb \Kb
97 \renewcommand*{\Kb}{%
98     \begingroup
99     \boolfalse{mathjax}
100    \LWR@subsingledollar*\{\textbackslash{}Kb\}{chemmacros}{%
101        \LWR@chemmacros@origKb%
102    }%
103    \endgroup
104 }
105
106 \LetLtxMacro \LWR@chemmacros@origKw \Kw
107 \renewcommand*{\Kw}{%
108     \begingroup
109     \boolfalse{mathjax}
110     \LWR@subsingledollar*\{\textbackslash{}Kw\}{chemmacros}{%
111         \LWR@chemmacros@origKw
112     }%
113     \endgroup
```

```

114 }
115
116 }{}}% \@ifchemmacrosmoduleloaded
117 }% AtBeginDocument

```

§ 156.6 Charges

```

118 \AtBeginDocument{
119 \ifchemmacrosmoduleloaded{charges}{%
120 \PackageInfo{l warp}{Patching~chemmacros~module~charges}%
121
122 \cs_gset_protected:Npn \fplus {
123   \begingroup
124   \boolfalse{mathjax}
125   \LWR@subsingle dollar*\textbackslash{}fplus\chemmacros{%
126     \LWR@origensuredmath{\chemformula_fplus:}%
127   }\endgroup
128 }
129 \cs_gset_protected:Npn \fminus {
130   \begingroup
131   \boolfalse{mathjax}
132   \LWR@subsingle dollar*\textbackslash{}fminus\chemmacros{%
133     \LWR@origensuredmath{\chemformula_fminus:}%
134   }\endgroup
135 }
136
137 }{}}% \@ifchemmacrosmoduleloaded
138 }% AtBeginDocument

```

§ 156.7 Nomenclature

```

139 \AtBeginDocument{
140 \ifchemmacrosmoduleloaded{nomenclature}{%
141 \PackageInfo{l warp}{Patching~chemmacros~module~nomenclature}%
142
143 \cs_gset_protected:Npn \chemmacros_charge:n #1
144 {
145   \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}
146   {\chemmacros_chemformula:n { \{}^{\#1} \}}
147 {
148   \ifmmode
149   {\chemmacros_chemformula:n { \{}^{\#1} \}}
150   \else
151   { \textsuperscript{\ensuremath{\#1}} }
152   \fi
153 }
154 }
155
156

```

```
157 \LetLtxMacro{\LWR@chemmacros@origchemprime}{\chemprime}
158 \protected\def\chemprime {\HTMLunicode{2032}}
160
161 \appto{\LWR@restoreorigformatting}{%
162 \LetLtxMacro{\chemprime}{\LWR@chemmacros@origchemprime}%
163 }

164 \ChemCompatibilityFrom{5.8}
165 \cs_gset_protected:Npn \__chemmacros_cip:n #1
166 {
167     \tl_set:Nn \l__chemmacros_tmpa_tl {#1}
168     \int_step_inline:nnnn {0} {1} {9}
169     {
170         \tl_replace_all:Nnn \l__chemmacros_tmpa_tl
171             {##1}
172             { \l__chemmacros_cip_number_tl ##1 }
173     }
174     {
175         \l__chemmacros_cip_inner_tl
176         \LWR@textcurrentcolor{\LWR@textcurrentfont{\% l warp
177             \l__chemmacros_tmpa_tl
178         }}% l warp
179     }
180 }
181 \EndChemCompatibility

182 \RenewDocumentCommand{\Sconf}{O{S}}{%
183 \begin{ lateximage }[\textbackslash{}textbackslash{}Sconf{}[]\#1{}[]]
184     \chemmacros_sconf:n {#1}
185 \end{ lateximage }
186 }
187
188 \RenewDocumentCommand{\Rconf}{O{R}}{%
189 \begin{ lateximage }[\textbackslash{}textbackslash{}Rconf{}[]\#1{}[]]
190     \chemmacros_rconf:n {#1}
191 \end{ lateximage }
192 }

193 \cs_gset_protected:Npn \chemmacros_hapto:n #1
194 {
195     \begingroup
196     \boolfalse{mathjax}
197     \LWR@subsingle dollar*{\textbackslash{}hapto\{#1\}}{\chemmacros}{%
198         \chemmacros_coordination_symbol:nnnn
199         { \l__chemmacros_coord_use_hyphen_bool }
200         {
201             \chemmacros_if_compatibility:nnTF {>} {5.7}
202             { \c_true_bool }
203             { \c_false_bool }
```

```

204      }
205      { \chemeta }
206      {#1}
207    }
208  \endgroup
209 }
210
211 \cs_gset_protected:Npn \chemmacros_dento:n #1
212 {
213   \begingroup
214   \boolfalse{mathjax}
215   \LWR@subsingle dollar*\textbackslash{}dento\{#1\}\{chemmacros\}{
216     \chemmacros_coordination_symbol:nnnn
217     { \l_chemmacros_coord_use_hyphen_bool }
218     {
219       \chemmacros_if_compatibility:nnTF {>} {5.7}
220       { \c_true_bool }
221       { \c_false_bool }
222     }
223     { \chemkappa }
224     {#1}
225   }
226   \endgroup
227 }
228
229 \cs_gset_protected:Npn \chemmacros_bridge:n #1
230 {
231   \begingroup
232   \boolfalse{mathjax}
233   \LWR@subsingle dollar*\textbackslash{}bridge\{#1\}\{chemmacros\}{
234     \chemmacros_coordination_symbol:nnnn
235     { \l_chemmacros_coord_use_hyphen_bool }
236     { \l_chemmacros_bridge_super_bool }
237     { \chemmu }
238     {#1}
239   }
240   \endgroup
241 }
242 }{}% \@ifchemmacrosmoduleloaded
243 }% AtBeginDocument

```

§ 156.8 Particles

```

244 \AtBeginDocument{
245 \ifchemmacrosmoduleloaded{particles}{
246 \PackageInfo{l warp}{Patching~chemmacros~module~particles}
247
248 \cs_gset_protected:Npn \chemmacros_declare_nucleophile:Nn #1#2
249 {

```

```

250 \cs_set_protected:cpn {_chemmacros_ \chemmacros_remove_backslash:N #1:}
251 {
252     \bool_if:NTF \l__chemmacros_nucleophile_elpair_bool
253     {
254         \chemmacros_elpair:n { #2 }
255         \chemmacros_if_compatibility:nnT {>} {5.3}
256         { \skip_horizontal:N \l__chemmacros_nucleophile_dim }
257         \chemmacros_chemformula:n { {}^{\cdot} }
258     }
259     { \chemmacros_chemformula:n { #2^{\cdot} } }
260 }
261 \DeclareDocumentCommand #1 {o}
262 {%
263     \begin{[teximage]}%
264     \group_begin:%
265     \IfNoValueF {##1}%
266     { \chemmacros_set_keys:nn {particles} {##1} }%
267     \use:c {_chemmacros_ \chemmacros_remove_backslash:N #1:}%
268     \group_end:%
269     \end{[teximage]}%
270 }
271 }
272
273 \RenewChemNucleophile \Nuc {Nu}
274 \RenewChemNucleophile \ba {ba}
275
276 }{}% \@ifchemmacrosmoduleloaded
277 }% AtBeginDocument

```

§ 156.9 Phases

```

278 \AtBeginDocument{
279 \@ifchemmacrosmoduleloaded{phases}{%
280 \PackageInfo{l warp}{Patching~chemmacros~module~phases}}
281
282 \cs_undefine:N \chemmacros_phase:n
283 \cs_new_protected:Npn \chemmacros_phase:n #1
284 {
285     \chemmacros_leave_vmode:
286     \bool_if:NTF \l__chemmacros_phases_sub_bool
287     {
288         \ifnumequal{\value{LWR@teximagedepth}}{0}
289         {
290             \textsubscript{ (#1) }
291         }
292         {
293             \chemformula_subscript:n { (#1) }
294         }
295     }

```

```
296      {
297          \skip_horizontal:N \l_chemmacros_phases_space_dim
298          \chemmacros_text:n { (#1) }
299      }
300  }
301
302 }{}% \@ifchemmacrosmoduleloaded
303 }% AtBeginDocument
```

§ 156.10 Mechanisms

```
304 \AtBeginDocument{
305 \ifchemmacrosmoduleloaded{mechanisms}{
306 \PackageInfo{l warp}{Patching~chemmacros~module~mechanisms}
307
308 \chemmacros_define_keys:nn {textmechanisms}
309  {
310     type      .choice: ,
311     type /   .code:n   =
312     {
313         \_chemmacros_set_mechanisms:nnn { S }
314         {
315             \textsubscript{N}
316         }
317         { }
318     } ,
319     type / 1 .code:n   =
320     {
321         \_chemmacros_set_mechanisms:nnn { S }
322         {
323             \textsubscript{N}
324             1
325         }
326         { }
327     } ,
328     type / 2 .code:n   =
329     {
330         \_chemmacros_set_mechanisms:nnn { S }
331         {
332             \textsubscript{N}
333             2
334         }
335         { }
336     } ,
337     type / se .code:n   =
338     {
339         \_chemmacros_set_mechanisms:nnn { S }
340         {
341             \textsubscript{E}
```

```
342         }
343         {
344     } ,
345     type / 1e .code:n    =
346     {
347         \_chemmacros_set_mechanisms:nnn { S }
348         {
349             \textsubscript{E}
350             1
351         }
352         {
353     } ,
354     type / 2e .code:n    =
355     {
356         \_chemmacros_set_mechanisms:nnn { S }
357         {
358             \textsubscript{E}
359             2
360         }
361         {
362     } ,
363     type / ar .code:n    =
364     {
365         \_chemmacros_set_mechanisms:nnn { S }
366         {
367             \textsubscript{E}
368         }
369         { Ar - }
370     } ,
371     type / e .code:n    =
372     { \_chemmacros_set_mechanisms:nnn { E } { } { } } ,
373     type / e1 .code:n   =
374     { \_chemmacros_set_mechanisms:nnn { E } { 1 } { } } ,
375     type / e2 .code:n   =
376     { \_chemmacros_set_mechanisms:nnn { E } { 2 } { } } ,
377     type / cb .code:n   =
378     {
379         \_chemmacros_set_mechanisms:nnn { E }
380         {
381             1
382             \textsubscript{cb}
383         }
384         {
385     } ,
386     type      .default:n =
387 }
388
389 \cs_gset_protected:Npn \chemmacros_mechanisms:n #1
390 {
391     \tl_if_blank:nTF {#1}
```

```

392     { \chemmacros_set_keys:nn {textmechanisms} { type } }
393     { \chemmacros_set_keys:nn {textmechanisms} { type = #1 } }
394     \mbox
395     {
396         \tl_use:N \l__chemmacros_mechanisms_ar_tl
397         \tl_use:N \l__chemmacros_mechanisms_type_tl
398         \tl_use:N \l__chemmacros_mechanisms_mol_tl
399     }
400 }
401
402 \appto\LWR@restoreorigformatting{%
403 \cs_set_protected:Npn \chemmacros_mechanisms:n #1%
404 {%
405     \tl_if_blank:nTF {#1}%
406     { \chemmacros_set_keys:nn {mechanisms} { type } }%
407     { \chemmacros_set_keys:nn {mechanisms} { type = #1 } }%
408     \mbox%
409     {%
410         \tl_use:N \l__chemmacros_mechanisms_ar_t1%
411         \tl_use:N \l__chemmacros_mechanisms_type_t1%
412         \tl_use:N \l__chemmacros_mechanisms_mol_t1%
413     }%
414 }%
415 }%
416
417 }{}% \@ifchemmacrosmoduleloaded
418 }% AtBeginDocument

```

§ 156.11 Newman

```

419 \AtBeginDocument{
420 \ifchemmacrosmoduleloaded{newman}{%
421 \PackageInfo{lwarf}{Patching~chemmacros~module~newman}
422
423 \RenewDocumentCommand \newman {od()m}{%
424 {
425     \IfValueTF{#2}{%
426         {\begin{ lateximage }[\textbackslash newman{#2}\{#3\}] }%
427         {\begin{ lateximage }[\textbackslash newman\{#3\}] }%
428         \group_begin:%
429             \IfNoValueF{#1}{ \chemmacros_set_keys:nn {newman} {#1} }%
430             \IfNoValueTF{#2}{%
431                 { \chemmacros_newman:nn { } {#3} }%
432                 { \chemmacros_newman:nn {#2} {#3} }%
433             \group_end:%
434             \end{ lateximage }%
435     }%
436 }{}% \ifchemmacrosmoduleloaded
437 }{}% \ifchemmacrosmoduleloaded

```

```
438 }% AtBeginDocument
```

§ 156.12 Orbital

```
439 \AtBeginDocument{
440 \@ifchemmacrosmoduleloaded{orbital} {
441 \PackageInfo{l warp}{Patching~chemmacros~module~orbital}
442
443 \RenewDocumentCommand \orbital {om}
444 {
445   \IfValueTF{#1}
446   {
447     \begin{ lateximage }[%
448       \textbackslash orbital{[]}\LWR@HTMLsanitize{#1}{[]}\{#2\}%
449     ] [] [margin-left: 1em ; margin-right: 1em]
450   }
451   {
452     \begin{ lateximage }[%
453       \textbackslash orbital\{#2\}%
454     ] [] [margin-left: 1em ; margin-right: 1em]
455   }
456   \group_begin:
457     \chemmacros_set_keys:nn {orbital/type} {#2}
458     \IfNoValueTF {#1}
459     {
460       \chemmacros_orbital:n { }
461     }
462     \group_end:
463     \end{ lateximage }
464 }
465 }{}% \@ifchemmacrosmoduleloaded
466 }% AtBeginDocument
```

§ 156.13 Reactions

```
\chemmacros_declare_reaction_env {\chem} {\math} {\args number} {\argument list (#2){#3}...)}
467 \AtBeginDocument{
468 \@ifchemmacrosmoduleloaded{reactions} {
469 \PackageInfo{l warp}{Patching~chemmacros~module~reactions}
470
471 \cs_gset_protected:Npn \chemmacros_declare_reaction_env:nnnn #1#2#3#4
472 {
473   \exp_args:Nnx \DeclareDocumentEnvironment {#1} { O{} \prg_replicate:nn {#3+0} {m} }
474   {
475     \boolfalse{mathjax}%
476     \chemmacros_add_reaction_description:n {##1}
477     \__chemmacros_begin_reaction:
478     \chemmacros_reaction_read:nnw {#2} {#4}
```

```
479      }
480      {
481          \_\_chemmacros\_end\_reaction:
482      }
483  }
484 \cs_generate_variant:Nn \chemmacros_declare_reaction_env:nnnn {nnnV}
485
486 \RenewChemReaction {reaction}  {equation}
487 \RenewChemReaction {reaction*} {equation*}
488 \RenewChemReaction {reactions} {align}
489 \RenewChemReaction {reactions*} {align*}
490
491 }{}% \@ifchemmacrosmoduleloaded
492 }% AtBeginDocument
```

§ 156.14 Redox

```
493 \AtBeginDocument{
494 \@ifchemmacrosmoduleloaded{redox}{
495 \PackageInfo{l warp}{Patching~chemmacros~module~redox}
496
497 \NewDocumentCommand \LWR@chemmacros@ox { s m >{\SplitArgument{1}{,}}m }
498  {
499      \IfBooleanTF {#1}
500          { \chemmacros_ox:nnnn {#1} {#2} #3 }
501          { \chemmacros_ox:nnnn { } {#2} #3 }
502  }
503
504 \RenewDocumentCommand \ox { s O{} m }
505  {
506      \begingroup
507      \boolfalse{mathjax}
508      \IfBooleanTF {#1}
509      {
510          \LWR@subsingle dollar*{%
511              \textbackslash{}ox*\{\LWR@HTMLsanitize{#3}\}%
512          }%
513          star \protect\LWR@HTMLsanitize{\detokenize\expandafter{#2}}%
514      }%
515          \LWR@chemmacros@ox* {#2} {#3}%
516      }%
517  }
518  {
519      \LWR@subsingle dollar*{%
520          \textbackslash{}ox*\{\LWR@HTMLsanitize{#3}\}%
521      }%
522          \protect\LWR@HTMLsanitize{\detokenize\expandafter{#2}}%
523      }%
524          \LWR@chemmacros@ox {#2} {#3}%
525      }%
```

```

526      }
527      \endgroup
528  }
529
530 }{ }% \@ifchemmacrosmoduleloaded
531 }% AtBeginDocument

```

§ 156.15 Scheme

Fix for **chemmacros** as of v5.8b, when using **newfloat** and **babel**:

```

532 \AtBeginDocument{
533 \@ifchemmacrosmoduleloaded{scheme}{
534 \PackageInfo{lwarf}{Patching-chemmacrosmodule-scheme}
535
536 \ifdefstring{\schemename}{los}{
537 \SetupFloatingEnvironment{scheme}{
538 name = \chemmacrostranslate:n {scheme-name}
539 }
540 }{}}
541
542 }{ }% \@ifchemmacrosmoduleloaded
543 }% AtBeginDocument

```

§ 156.16 Spectroscopy

```

544 \AtBeginDocument{
545 \@ifchemmacrosmoduleloaded{spectroscopy}{
546 \PackageInfo{lwarf}{Patching-chemmacrosmodule-spectroscopy}
547
548 \ChemCompatibilityTo{5.8}
549 \cs_gset_protected:Npn \__chemmacrosnmr_base:nn #1#2
550 {
551   \tl_if_blank:VF \g__chemmacrosnmr_element_coupled_tl
552   {
553     \tl_put_left:Nn \g__chemmacrosnmr_element_coupled_tl { \{ }
554     \tl_put_right:Nn \g__chemmacrosnmr_element_coupled_tl { \} }
555   }
556   \tl_put_left:Nn \g__chemmacrosnmr_element_coupled_tl {#2}
557 %   \chemmacroscchemformula:n { ^{#1} }
558   \textsuperscript{#1}
559   \bool_if:NTF \l__chemmacrosnmr_parse_bool
560     { \chemformula_ch:nV {} \g__chemmacrosnmr_element_coupled_tl }
561     { \chemmacroscchemformula:V \g__chemmacrosnmr_element_coupled_tl }
562   \tl_use:N \l__chemmacrosnmr_element_method_connector_tl
563   \tl_use:N \l__chemmacrosnmr_method_tl
564 }
565 \EndChemCompatibility
566 \ChemCompatibilityFrom{5.8}

```

```
567 \cs_gset_protected:Npn \__chemm macros_nmr_base:nn #1#2
568  {
569    \group_begin:
570      \tl_use:N \l__chemm macros_nmr_base_format_tl
571      \tl_if_blank:VF \g__chemm macros_nmr_element_coupled_tl
572      {
573        \tl_put_left:Nn \g__chemm macros_nmr_element_coupled_tl { \{ }
574        \tl_put_right:Nn \g__chemm macros_nmr_element_coupled_tl { \} }
575      }
576      \tl_put_left:Nn \g__chemm macros_nmr_element_coupled_tl {#2}
577 %       \chemm macros_chemformula:n { ^{#1} }
578      \textsuperscript{#1}
579      \tl_if_blank:VF \g__chemm macros_nmr_element_coupled_tl
580      {
581        \bool_if:NTF \l__chemm macros_nmr_parse_bool
582          { \chemm formula_ch:nV {} \g__chemm macros_nmr_element_coupled_tl }
583          { \chemm macros_chemformula:V \g__chemm macros_nmr_element_coupled_tl }
584      }
585      \tl_use:N \l__chemm macros_nmr_element_method_connector_tl
586      \tl_use:N \l__chemm macros_nmr_method_tl
587    \group_end:
588  }
589 \EndChemCompatibility
590
591
592 \cs_gset_protected:Npn \chemm macros_nmr_position:n #1
593  {
594    \chemm macros_chemformula:x
595    {
596      \exp_not:V \g__chemm macros_nmr_element_tl
597      \bool_if:NF \l__chemm macros_nmr_position_side_bool
598      {
599        \tl_if_eq:NnTF \l__chemm macros_nmr_position_tl {^}% lwarp
600        { \textsuperscript{\exp_not:n { {#1} }} }% lwarp
601        { \textsubscript{\exp_not:n { {#1} }} }% lwarp
602 %        \exp_not:V \l__chemm macros_nmr_position_tl
603 %        \exp_not:n { {#1} }
604      }
605    }
606    \bool_if:NT \l__chemm macros_nmr_position_side_bool
607    {
608      \tl_use:N \l__chemm macros_nmr_position_tl
609      \chemm macros_nmr_position:n {#1}
610    }
611  }
612
613 \cs_gset_protected:Npn \__chemm macros_nmr_coupling:w (#1;#2)
614  {
615    \tl_set:Nn \l__chemm macros_nmr_coupling_bonds_tl
616    {
```

```
617      \l_chemmacros_nmr_coupling_bonds_pre_tl
618      #1
619      \l_chemmacros_nmr_coupling_bonds_post_tl
620    }
621  \bool_if:NTF \l_chemmacros_nmr_coupling_nuclei_sub_bool
622  {
623    \tl_set:Nn \l_chemmacros_nmr_coupling_nuclei_tl
624    {
625      \c_math_subscript_token
626      \textsubscript{l warp}
627      {
628        \l_chemmacros_nmr_coupling_nuclei_pre_tl
629        \chemmacros_chemformula:n {#2}
630        \l_chemmacros_nmr_coupling_nuclei_post_tl
631      }
632    }
633  }
634  {
635    \tl_set:Nn \l_chemmacros_nmr_coupling_nuclei_tl
636    {
637      \l_chemmacros_nmr_coupling_nuclei_pre_tl
638      \chemmacros_chemformula:n {#2}
639      \l_chemmacros_nmr_coupling_nuclei_post_tl
640    }
641  }
642  \__chemmacros_nmr_coupling_aux_i:w
643 }
644
645 \AfterEndPreamble{%
646 % \NMR{<num>,<elem>}(<num>,<unit>)[<solvent>] ALL arguments are optional
647 % \NMR* same but without ": \$\delta" at end
648 \cs_gset_protected:Npn \chemmacros_nmr:nnnn #1#2#3#4
649  {
650    \bool_if:NT \l_chemmacros_nmr_list_bool { \item \scan_stop: }
651    \group_begin:
652      \chemmacros_leave_vmode:
653      \bool_set_false:N \l_chemmacros_nmr_frequency_bool
654      \bool_set_false:N \l_chemmacros_nmr_solvent_bool
655      \tl_if_empty:nF f#3}
656      { \bool_set_true:N \l_chemmacros_nmr_frequency_bool }
657      \tl_if_empty:nF {#4}
658      { \bool_set_true:N \l_chemmacros_nmr_solvent_bool }
659      \bool_if:nT
660      {
661        \l_chemmacros_nmr_frequency_bool
662        ||
663        \l_chemmacros_nmr_solvent_bool
664      }
665      { \bool_set_true:N \l_chemmacros_nmr_delimiters_bool }
666      \bool_if:nT
```

```
667      {
668          \l__chemmacros_nmr_frequency_bool
669          &&
670          \l__chemmacros_nmr_solvent_bool
671      }
672      { \bool_set_true:N \l__chemmacros_nmr_comma_bool }
673      \tl_if_empty:nTF {#2}
674      {
675          \l__chemmacros_nmr_nucleus:VV
676          \l__chemmacros_nmr_isotope_default_tl
677          \l__chemmacros_nmr_element_default_tl
678      }
679      { \l__chemmacros_nmr_nucleus:w #2 \q_stop }
680      \mode_if_math:TF
681      {
682          \text
683          {
684              \group_begin:
685              \tl_use:N \l__chemmacros_nmr_format_tl
686 \LWR@textcurrentcolor{\LWR@textcurrentfont\% lwarp
687              \l__chemmacros_nmr_base:VV
688              \g__chemmacros_nmr_isotope_tl
689              \g__chemmacros_nmr_element_tl
690              \bool_if:NT \l__chemmacros_nmr_delimiters_bool
691              { ~ ( }
692              \bool_if:NT \l__chemmacros_nmr_frequency_bool
693              { \l__chemmacros_nmr_frequency:n {#3} }
694              \bool_if:NT \l__chemmacros_nmr_comma_bool
695              { , ~ }
696              \bool_if:NT \l__chemmacros_nmr_solvent_bool
697              { \chemmacros_chemformula:n {#4} }
698              \bool_if:NT \l__chemmacros_nmr_delimiters_bool
699              { ) }
700              \tl_if_blank:nT {#1} {::}
701 }%\ lwarp
702          \group_end:
703      }
704      \tl_if_blank:nT {#1}
705      {
706          \delta
707          \text { \l__chemmacros_nmr_delta_tl }
708          \bool_if:NT \l__chemmacros_nmr_use_equal_bool {=}
709      }
710      }
711      {
712          \group_begin:
713          \tl_use:N \l__chemmacros_nmr_format_tl
714 \LWR@textcurrentcolor{\LWR@textcurrentfont\% lwarp
715          \l__chemmacros_nmr_base:VV
716          \g__chemmacros_nmr_isotope_tl
```

```
717          \g_chemmacros_nmr_element_tl
718          \bool_if:NT \l_chemmacros_nmr_delimiters_bool
719          {~{}}
720          \bool_if:NT \l_chemmacros_nmr_frequency_bool
721          { \chemmacros_nmr_frequency:n {#3} }
722          \bool_if:NT \l_chemmacros_nmr_comma_bool
723          {,~{}}
724          \bool_if:NT \l_chemmacros_nmr_solvent_bool
725          {
726              \bool_if:NTF \l_chemmacros_nmr_parse_bool

727      { \chemformula_ch:nn { } {#4} }% original
728      {\ch{#4}}% lwarf
729      {#4}
730      }
731      \bool_if:NT \l_chemmacros_nmr_delimiters_bool
732      {}}
733 }% lwarf
734 \tl_if_blank:nT {#1} {:}
735 \group_end:
736 \tl_if_blank:nT {#1}
737 {
738     \tl_use:N \c_space_tl
739     \c_math_toggle_token
740     \delta
741     \c_math_toggle_token
742     \l_chemmacros_nmr_delta_tl
743     \bool_if:NT \l_chemmacros_nmr_use_equal_bool {~=}
744 }
745 }
746 \group_end:
747 }
748 }% AfterEndPreamble
749
750
751 \RenewDocumentCommand \chemmacros_data:w { smo }
752 {
753     \bool_if:NT \l_chemmacros_nmr_list_bool { \item }
754     {
755         \tl_use:N \l_chemmacros_nmr_format_tl #2
756         \tl_use:N \l_chemmacros_nmr_format_tl
757         \LWR@textcurrentcolor{\LWR@textcurrentfont{%
758             \#2
759             \IfNoValueF {#3} { ~ ( #3 ) }
760             \IfBooleanT {#1} { \bool_if:NT \l_chemmacros_nmr_use_equal_bool { : } }
761         }}% lwarf
762     }
763     \IfBooleanF {#1} { \bool_if:NT \l_chemmacros_nmr_use_equal_bool { ~ = } }
764 }
```

```

765
766 }{}% \@ifchemmacrosmoduleloaded
767 }% AtBeginDocument

```

§ 156.17 Thermodynamics

```

768 \AtBeginDocument{
769 \@ifchemmacrosmoduleloaded{thermodynamics}{
770 \PackageInfo{l warp}{Patching~chemmacros~module~thermodynamics}
771
772 \cs_gset_protected:Npn \chemmacros_state:nn #1#2
773 {
774     \group_begin:
775         \boolfalse{mathjax}
776         \chemmacros_set_keys:nn {thermodynamics} {#1}
777         \LWR@subsingle dollar*{%
778             \textbackslash state{\LWR@HTMLsanitize{#2}}%
779         }%
780         chemmacros_state% add'1 hashing
781         #1% options
782         LSP \tl_use:N \l_chemmacros_state_sp_left_tl% super/subscripts
783         LSB \tl_use:N \l_chemmacros_state_sb_left_tl
784         RSP \tl_use:N \l_chemmacros_state_sp_right_tl
785         RSB \tl_use:N \l_chemmacros_state_sb_right_tl
786     }
787     {
788         \LWR@origensuredmath{
789             \chemmacros_text:V \l_chemmacros_state_pre_tl
790             \c_math_superscript_token
791                 { \chemmacros_text:V \l_chemmacros_state_sp_left_tl }

```

Only add the subscripts if they are being used. This avoids causing an incorrect depth, as the empty subscript will be measured by \TeX but cropped out by **pdfcrop**.

```

792         \tl_if_empty:NTF \l_chemmacros_state_sb_left_tl
793         {}
794         {
795             \c_math_subscript_token
796             { \chemmacros_text:V \l_chemmacros_state_sb_left_tl }
797         }
798         #2
799         \c_math_superscript_token
800             { \chemmacros_text:V \l_chemmacros_state_sp_right_tl }
801         \tl_if_empty:NTF \l_chemmacros_state_sb_right_tl
802         {}
803         {
804             \c_math_subscript_token
805             { \chemmacros_text:V \l_chemmacros_state_sb_right_tl }
806         }

```

```

807          \chemmacros_text:V \l__chemmacros_state_post_tl
808      }
809  }
810 \group_end:
811 }
812 \cs_generate_variant:Nn \chemmacros_state:nn { nV }
813
814 \cs_gset_protected:Npn \chemmacros_declare_state:Nn #1#2
815 {
816     \chemmacros_define_keys:xn
817     {thermodynamics/\chemmacros_remove_backslash:N #1}
818     {
819         pre           .meta:nn = {chemmacros/thermodynamics} { pre = ##1 } ,
820         post          .meta:nn = {chemmacros/thermodynamics} { post = ##1 } ,
821         superscript-left .meta:nn = {chemmacros/thermodynamics} { superscript-left = ##1 } ,
822         superscript-right .meta:nn = {chemmacros/thermodynamics} { superscript-right = ##1 } ,
823         superscript    .meta:n  = {superscript-right = ##1} ,
824         subscript-left .meta:nn = {chemmacros/thermodynamics} { subscript-left = ##1 } ,
825         subscript-right .meta:nn = {chemmacros/thermodynamics} { subscript-right = ##1 } ,
826         subscript     .meta:n  = { subscript-left = ##1 } ,
827         subscript-pos   .choices:nn =
828             { left , right }
829             { \tl_set_eq:NN \l__chemmacros_state_sb_pos_tl \l_keys_choice_tl } ,
830             symbol        .tl_set:N = \l__chemmacros_state_symbol_tl ,
831             unit          .tl_set:N = \l__chemmacros_state_unit_tl
832     }
833 \DeclareDocumentCommand #1 { sO{}D(){}m }
834 {
835     \group_begin:
836     \chemmacros_set_keys:xn
837     {thermodynamics/\chemmacros_remove_backslash:N #1}
838     {#2}
839     \tl_if_blank:nF {##3}
840     {
841         \chemmacros_set_keys:nx {thermodynamics}
842         { subscript-\l__chemmacros_state_sb_pos_tl = \exp_not:n {##3} }
843     }
844     \chemmacros_state:nV {##2} \l__chemmacros_state_symbol_tl
845     \chemmacros_set_keys_groups:nnn {thermodynamics} {variables} {##2}
846     \IfBooleanF {##1} { = ~ \SI {##4} { \l__chemmacros_state_unit_tl } }
847     \group_end:
848 }
849 }
```

The pre-existing macros are redefined with the new definition:

```

850 \RenewChemState \enthalpy { symbol = H , unit = \kilo\joule\per\mole }
851 \RenewChemState \entropy { symbol = S , unit = \joule\per\kelvin\per\mole , pre = }
852 \RenewChemState \gibbs { symbol = G , unit = \kilo\joule\per\mole }
853
```

```

854 }{}% \ifchemmacrosmoduleloaded
855 }% AtBeginDocument
856 \ExplSyntaxOff

```

File 64 **l warp-chemnum.sty**

§ 157 Package **chemnum**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg **chemnum** **chemnum** is patched for use by **l warp**.

for HTML output:

```

1 \LWR@ProvidesPackagePass{chemnum}

2 \ExplSyntaxOn
3
4 \cs_gset_protected:Npn \chemnum_compound_write:n #1
5  {
6      \chemnum_get_compound_property:nn {#1} {pre-main-label-code}
7      \group_begin:
8          \bool_if:NTF \l__chemnum_compound_local_bool
9              { \l__chemnum_local_label_format_t1 }
10             { \chemnum_get_compound_property:nn {#1} {label-format} }
11
12          \LWR@textcurrentfont{
13              \chemnum_get_compound_property:nn {#1} {counter-representation}
14          }
15
16      \group_end:
17      \chemnum_get_compound_property:nn {#1} {post-main-label-code}
18  }

19
20 \cs_gset_protected:Npn \chemnum_subcompound_write:nn #1#2
21  {
22      \group_begin:
23          \bool_if:NTF \l__chemnum_compound_local_bool
24              { \l__chemnum_local_label_format_t1 }
25              { \chemnum_get_compound_property:nn {#1} {label-format} }
26
27          \LWR@textcurrentfont{
28              \chemnum_get_subcompound_property:nnn {#1} {#2}
29              {counter-representation}
30          }
31
32      \group_end:
33  }

```

```
34  
35 \ExplSyntaxOff
```

File 65 **l warp-chkfloat.sty**

§ 158 Package **chkfloat**

Pkg **chkfloat** **chkfloat** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{chkfloat}[2012/08/19]

File 66 **l warp-cite.sty**

§ 159 Package **cite**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg **cite** **cite** is patched for use by **l warp**.

for HTML output: 1 \LWR@ProvidesPackagePass{cite}

For the [super] option, the \kern must be removed:

```
2 \def\LWRCT@biblabel#1{\@citess{#1}\kern-\labelsep,}  
3  
4 \ifdefstreq{\@biblabel}{\LWRCT@biblabel}  
5 {  
6     \def\@biblabel#1{\@citess{#1}}  
7 }{}
```

For the [super] option, \textsuperscript is used instead of math superscript:

```
8 \def\@citess#1{\textsuperscript{#1}}  
9  
10 \DeclareDocumentCommand\citepunct{}{\relax}
```

File 67 **l warp-clrdblpq.sty**

§ 160 Package **clrdblpq**

Pkg **clrdblpq** **clrdblpq** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{clrdblpg}

File 68 l warp-cmdtrack.sty

§ 161 Package **cmdtrack**

Pkg cmdtrack cmdtrack is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{cmdtrack}[2012/12/18]

2 \newcommand{\untrack}[1] {}

File 69 l warp-color.sty

§ 162 Package **color**

Pkg color Allowed but ignored. xcolor is then required as well.

color is superceded by xcolor, and l warp requires several of the features of xcolor. When color is requested, xcolor is loaded as well.

for HTML output: 1 \LWR@ProvidesPackagePass{color}
2 \RequirePackage{xcolor}

File 70 l warp-colortbl.sty

§ 163 Package **colortbl**

Pkg colortbl colortbl is emulated.

⚠ row/color Only use \rowcolor and \cellcolor at the start of a row, in that order.

colortbl ignores the overhang arguments.

for HTML output: A few placeholder definitions are forgotten first:

1 \let\rowcolor\relax
2
3 \LWR@ProvidesPackagePass{colortbl}

The following \LWR@HTML versions are used inside an HTML tabular.

\columncolor [*model*] {[*color*] [*left overhang*] [*right overhang*]}

\LWR@getmynexttoken is not used here because \columncolor is not used inside the data area of the tabular.

```

4 \NewDocumentCommand{\LWR@HTML@columncolor}{0{named} m o o}{%
5 \convertcolorspec{#1}{#2}{HTML}\LWR@columnHTMLcolor%
6 \LWR@addtabularcellcolor%
7 }
8
9 \LWR@formatted{columncolor}
```

\LWR@getmynexttoken is used for \rowcolor because it is used inside the data area of the tabular.

\rowcolor [*model*] {[*color*] [*left overhang*] [*right overhang*]}

```

10 \NewDocumentCommand{\LWR@HTML@rowcolor}{0{named} m o o}{%
11 \convertcolorspec{#1}{#2}{HTML}\LWR@rowHTMLcolor%
12 \LWR@getmynexttoken%
13 }
14
15 \LWR@expandableformatted{rowcolor}
```

\cellcolor [*model*] {[*color*] [*left overhang*] [*right overhang*]}

```

16 \NewDocumentCommand{\LWR@HTML@cellcolor}{0{named} m o o}{%
17 \convertcolorspec{#1}{#2}{HTML}\LWR@cellHTMLcolor%
18 \LWR@addtabularcellcolor%
19 }
20
21 \LWR@formatted{cellcolor}
```

\arrayrulecolor [*model*] {[*color*]}

The HTML version for use outside a tabular. Inside a tabular, \LWR@HTML@arrayrulecolornexttoken is used instead.

```

22 \newcommand{\LWR@HTML@arrayrulecolor}[2][named]{%
23 \convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
24 }
25
26 \LWR@expandableformatted{arrayrulecolor}
```

[*model*] {[*color*]}

\LWR@arrayrulecolornexttoken The HTML version for use inside a tabular.

```
27 \newcommand{\LWR@HTML@arrayrulecolornexttoken}[2][named]{%
```

```

28 \convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
29 \LWR@getmynexttoken%
30 }
31
32 \LWR@expandableformatted{arrayrulecolornexttoken}

```

\doublerulesepcolor [*(model)*] {*(color)*}

The version for use outside a tabular.

```

33 \newcommand{\LWR@HTML@doublerulesepcolor}[2][named]{}
34
35 \LWR@expandableformatted{doublerulesepcolor}

```

[*(model)*] {*(color)*}

\LWR@doublerulesepcolornexttoken
The version for use inside a tabular.

```

36 \newcommand{\LWR@HTML@doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}
37
38 \LWR@expandableformatted{doublerulesepcolornexttoken}

```

File 71 l warp-continue.sty

§ 164 Package **continue**

Pkg **continue** **continue** is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{continue}

2 \newcommand*\{\flagcont}{}%
3 \newcommand*\{\flagend}{}%
4 \newcommand*\{\flagword}{}%
5 \newcommand*\{\preflagword}{}%
6 \newcommand*\{\postflagword}{}%
7 \newlength\contsep
8 \newlength\contdrop

```

File 72 l warp-copyrightbox.sty

§ 165 Package **copyrightbox**

(Emulates or patches code by THOMAS FISCHER, IVES VAN DER FLAAS.)

Pkg **copyrightbox** **copyrightbox** is emulated for use by **l warp**.

The entire copyright box is placed inside a <div> of class `copyrightbox`.

The contents are placed inside a <div> of class `copyrightboxcontents`.

The copyright notice is placed inside a <div> of class `copyrightboxnote`.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{copyrightbox}

2 \newcommand{\copyrightbox}[3][r]{%
3 \begin{BlockClass}[
4   display: inline-flex;
5   flex-direction: column ;
6 ]\copyrightbox}
7 \begin{BlockClass}{copyrightboxcontents}
8 #2
9 \end{BlockClass}
10 \begin{BlockClass}{copyrightboxnote}
11 #3
12 \end{BlockClass}
13 \end{BlockClass}
14 }
15
16 \newcommand{\CRB@setcopyrightfont}(){}
17 \newcommand{\CRB@setcopyrightparagraphstyle}{}{}
```

File 73 lwarf-crop.sty

§ 166 Package **crop**

(Emulates or patches code by MELCHIOR FRANZ.)

Pkg **crop** Emulated.

for HTML output: Discard all options for **lwarf-crop**:

```

1 \LWR@ProvidesPackageDrop{crop}

2 \newcommand*\{\\crop}[1][]{}
3 \newcommand*\{\\cropdef}[6][]{}
```

File 74 lwarf-cuted.sty

§ 167 Package **cuted**

(Emulates or patches code by SIGITAS TOLUŠIS.)

Pkg cuted cuted is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{cuted}

2 \newenvironment{strip}{}{}
3 \newskip\stripsep
4 \def\oldcolsbreak#1{}
```

File 75 l warp-cutwin.sty

§ 168 Package **cutwin**

(Emulates or patches code by PETER WILSON AND ALAN HOENIG.)

Pkg cutwin Emulated.

for HTML output: Discard all options for l warp-cutwin:

```
1 \LWR@ProvidesPackageDrop{cutwin}

2 \newcommand*\{\opencutleft\}{}
3 \newcommand*\{\opencutright\}{}
4 \newcommand*\{\opencutcenter\}{}
5 \newcommand*\{\cutfuzz\}{}
6
7 \newenvironment{cutout}[4]
8 {\marginpar{\windowpagestuff}}
9 {}
10
11 \newcommand*\{\windowpagestuff\}{}
12
13 \newcommand*\{\pageinwindow\}{%
14 % \begin{minipage}{.3\linewidth}
15 \windowpagestuff
16 % \end{minipage}
17 }
18
19 \newenvironment{shapedcutout}[3]
20 {\marginpar{\picinwindow}}
21 {}
22
23 \newcommand*\{\putstuffinpic\}{}
24
25 \newcommand*\{\picinwindow\}{%
26 \begin{picture}(0,0)
27 \putstuffinpic
28 \end{picture}}
```

File 76 **l warp-dblfloatfix.sty**

§ 169 Package **dblfloatfix**

Pkg **dblfloatfix** **dblfloatfix** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{dblfloatfix}

File 77 **l warp-dblfnote.sty**

§ 170 Package **dblfnote**

(Emulates or patches code by HIROSHI NAKASHIMA.)

Pkg **dblfnote** **dblfnote** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{dblfnote}

```
2 \newcounter{DFNsloppiness}
3 \newdimen\DFNcolumnsep
4 \newdimen\DFNcolumnwidth
5 \def\DFNallowcbreak{}
6 \def\DFNinhibitcbreak{}
7 \def\DFNtrysingle{}
8 \def\DFNalwaysdouble{}
9 \def\DFNruleboth{}
10 \def\DFNruleleft{}
```

File 78 **l warp-dcolumn.sty**

§ 171 Package **dcolumn**

Pkg **dcolumn** **dcolumn** is emulated by the **l warp** core.

1 \LWR@ProvidesPackageDrop{dcolumn}

File 79 **l warp-diagbox.sty**

§ 172 Package **diagbox**

(Emulates or patches code by LEO LIU.)

Pkg **diagbox** **diagbox** is patched for use by **l warp**.

for HTML output: 1 \LWR@ProvidesPackagePass{diagbox}

To restore print-mode inside a *lateximage*:

```
2 \LetLtxMacro{\LWR@origdiagbox@double}{\diagbox@double}
3 \LetLtxMacro{\LWR@origdiagbox@triple}{\diagbox@triple}
4
5 \appto{\LWR@restoreorigformatting}{%
6 \LetLtxMacro{\diagbox@double}{\LWR@origdiagbox@double}%
7 \LetLtxMacro{\diagbox@triple}{\LWR@origdiagbox@triple}%
8 }
```

```
\LWR@diagbox@AB {\langle E/W \rangle} {\langle A \rangle} {\langle E/W \rangle} {\langle B \rangle}
9 \newcommand{\LWR@diagbox@AB}[4]{%
10 \begingroup%
11 \LetLtxMacro{\\\newline}{%
12 \BlockClassSingle{\diagbox#1}{#2}%
13 \BlockClassSingle{\diagbox#3}{#4}%
14 \endgroup%
15 \LWR@stoppars%
16 }
```

```
\LWR@diagboxNW {\langle A \rangle} {\langle B \rangle}
17 \newcommand{\LWR@diagboxNW}[2]{%
18 \LWR@diagbox@AB{E}{#2}{W}{#1}%
19 }
```

Likewise for NE, SW, SE:

```
20 \newcommand{\LWR@diagboxNE}[2]{%
21 \LWR@diagbox@AB{W}{#1}{E}{#2}%
22 }
23
24 \let\LWR@diagboxSW\LWR@diagboxNE
25 \let\LWR@diagboxSE\LWR@diagboxNW
```

```
\diagbox@double  {\langle keys\rangle} {\langle A\rangle} {\langle B\rangle}
26 \def\diagbox@double#1#2#3{%
27 \setkeys{diagbox}{dir=NW,#1}%
28 \nameuse{LWR@diagbox\diagbox@dir}{#2}{#3}%
29 }
```

```
\LWR@diagboxTNW {\langle title\rangle} {\langle A\rangle} {\langle B\rangle}
30 \newcommand{\LWR@diagboxTNW}[3]{%
31 \BlockClassSingle{diagboxtitleN}{#1}%
32 \LWR@diagboxNW{#2}{#3}%
33 }
```

Likewise for NE, SW, SE:

```
34 \newcommand{\LWR@diagboxTNE}[3]{%
35 \BlockClassSingle{diagboxtitleN}{#1}%
36 \LWR@diagboxNE{#2}{#3}%
37 }
38
39 \newcommand{\LWR@diagboxTSW}[3]{%
40 \LWR@diagboxSW{#2}{#3}%
41 \BlockClassSingle{diagboxtitleS}{#1}%
42 \LWR@stopars%
43 }
44
45 \newcommand{\LWR@diagboxTSE}[3]{%
46 \LWR@diagboxSE{#2}{#3}%
47 \BlockClassSingle{diagboxtitleS}{#1}%
48 \LWR@stopars%
49 }
```

```
\diagbox@triple {\langle keys\rangle} {\langle A\rangle} {\langle T\rangle} {\langle B\rangle}
50 \def\diagbox@triple#1#2#3#4{%
51 \setkeys{diagbox}{dir=NW,#1}%
52 \nameuse{LWR@diagboxT\diagbox@dir}{#3}{#2}{#4}%
53 }
```

File 80 l warp-dprogress.sty

§ 173 Package **dprogress**

Pkg dprogress dprogress is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{dprogress} [2008/02/21]

File 81 l warp-draftcopy.sty

§ 174 Package **draftcopy**

Pkg draftcopy **draftcopy** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{draftcopy}

2 \newcommand{\draftcopyVersion}[1]{}
3 \newcommand{\draftcopySetGrey}[1]{}
4 \newcommand{\draftcopySetScale}[1]{}
5 \newcommand{\draftcopySetScaleFactor}[1]{}
6 \newcommand{\draftcopyFirstPage}[1]{}
7 \newcommand{\draftcopyLastPage}[1]{}
8 \newcommand{\draftcopyName}[2]{}
9 \newcommand{\draftcopyPageTransform}[1]{}
10 \newcommand{\draftcopyBottomTransform}[1]{}
11 \newcommand{\draftcopyPageX}[1]{}
12 \newcommand{\draftcopyPageY}[1]{}
13 \newcommand{\draftcopyBottomX}[1]{}
14 \newcommand{\draftcopyBottomY}[1]{}
```

File 82 l warp-draftfigure.sty

§ 175 Package **draftfigure**

Pkg draftfigure **draftfigure** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{draftfigure} [2017/07/19]
2 \RequirePackage{xkeyval}

3 \define@key{draftfigure}{code}{}%
4 \define@key{draftfigure}{noframe}[true]{}%
5 \define@key{draftfigure}{filename}[true]{}%
6 \define@key{draftfigure}{content}{}%
7 \define@key{draftfigure}{style}[normal]{}%
8 \define@key{draftfigure}{position}[left]{}%
9 \define@key{draftfigure}{size}[normal]{}%
10 \newcommand\setdf[1]{\setkeys{draftfigure}{#1}}
```

File 83 **l warp-draftwatermark.sty**

§ 176 Package **draftwatermark**

(Emulates or patches code by SERGIO CALLEGARI.)

Pkg **draftwatermark** **draftwatermark** is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{draftwatermark}

2 \newcommand{\SetWatermarkAngle}[1]{}
3 \newcommand{\SetWatermarkColor}[1]{}
4 \newcommand{\SetWatermarkLightness}[1]{}
5 \newcommand{\SetWatermarkFontSize}[1]{}
6 \newcommand{\SetWatermarkScale}[1]{}
7 \newcommand{\SetWatermarkHorCenter}[1]{}
8 \newcommand{\SetWatermarkVertCenter}[1]{}
9 \newcommand{\SetWatermarkText}[1]{}
```

File 84 **l warp-easy-todo.sty**

§ 177 Package **easy-todo**

(Emulates or patches code by JUAN RADA-VILELA.)

Pkg **easy-todo** **easy-todo** is patched for use by **l warp**.

for HTML output:

```
1 \LWR@ProvidesPackagePass{easy-todo}
```

\listoftodos Modified to correct buggy use of **\flushright**.

```
2 \let\LWR@origlistoftodos\listoftodos
3
4 \renewcommand{\listoftodos}{%
5 \begingroup
6 \renewcommand{\flushright}{}
7 \LWR@origlistoftodos
8 \endgroup
9 }
```

\todoii Modified to use **\textcolor** instead of **\color**.

```

10 \renewcommand{\todoii}[2]{%
11 \ifthenelse{\equal{@todoobeyfinal}{true}}{%
12   \ifoptionfinal{\todoenable{false}}{\todoenable{true}}{%
13 }{}}%
14 \ifthenelse{\equal{@todoenable}{true}}{%
15 \refstepcounter{todos}%
16 \noindent{%
17   \todocolor{%
18     \LWR@textcurrentcolor{%
19       \normalfont\scriptsize{\bfseries{\thetodos.\#1}}%
20     }%
21 }%
22 \addcontentsline{lod}{todos}{\protect{\thetodos.\#2}}%
23 }{}}%
24 }

```

File 85 **lwarf-ebook.sty**§ 178 Package **ebook***(Emulates or patches code by JØRGEN STEENSGAARD.)*Pkg **ebook** **ebook** is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{ebook}

2 \setcounter{secnumdepth}{0}
3 \setcounter{tocdepth}{2}
4
5 \providecommand{\pagefill}[1][0.001mm]{\noindent}
6
7 \providecommand{\ebook}{%
8 \setcounter{secnumdepth}{0}
9 \setcounter{tocdepth}{2}
10 }

```

File 86 **lwarf-ellipsis.sty**§ 179 Package **ellipsis***(Emulates or patches code by PETER J. HESLIN.)*Pkg **ellipsis** **ellipsis** is emulated.

```

1 \LWR@ProvidesPackageDrop{ellipsis}
2
3 \newcommand{\ellipsisgap}{0.1em}
4
5 \newcommand*{\midwordellipsis}{\textellipsis}

```

File 87 **lwarf-emptypage.sty**

§ 180 Package **emptypage**

Pkg **emptypage** **emptypage** is ignored.

for HTML output: Discard all options for **lwarf-emptypage**:

```

1 \LWR@ProvidesPackageDrop{emptypage}

```

File 88 **lwarf-endfloat.sty**

§ 181 Package **endfloat**

Pkg **endfloat** **endfloat** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{endfloat}

```

2 \newcommand\figureplace{}
3 \newcommand\tableplace{}
4 \newcommand\floatplace[1]{}
5 \newcounter{posttable}
6 \newcounter{postfigure}
7 \newcommand*{\theposttbl}{}
8 \newcommand*{\thepostfig}{}
9 \newcommand{\AtBeginFigures}[1]{}
10 \newcommand{\AtBeginTables}[1]{}
11 \newcommand{\AtBeginDelayedFloats}[1]{}
12 \newcommand*{\processdelayedfloats}{}
13 \newcommand*{\efloatseparator}{}
14 \def\efloattype{}
15 \providecommand\efloatheading[1]{}
16 \providecommand\efloatpreamble{}
17 \providecommand\efloatpostamble{}

```

File 89 **l warp-endheads.sty**

§ 182 Package **endheads**

Pkg **endheads** **endheads** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{endheads}

2 \newcommand{\changesinglepageabbrev}{[1]{}}
3 \newcommand{\changemultiplepageabbrev}{[1]{}}
4 \newcommand{\changetitlesname}{[1]{}}
5 \newcommand{\changetitlesheader}{[1]{}}
6 \newcommand{\changetitlescontentsname}{[1]{}}
7 \newcommand{\changechaptertitlesline}{[1]{}}
8 \newcommand{\checknoteheaders}{{}}
9 \newif\ifnotesincontentson \notesincontentsonfalse
10 \newcommand{\notesincontents}{\notesincontentsontrue}
11 \newif\ifendnoteheaderson \endnoteheadersonfalse
12 \newcommand{\setupendnoteheaders}{%
13   \endnoteheadersontrue%
14 }
15 \newif\iftitleinnotes \titleinnotestruue
16 \newcommand{\styleforchapternotebegin}{{}}
17 \newcommand{\styleforchapternoteend}{{}}
18 \newcommand{\setstyleforchapternotebegin}{[1]{%
19   \renewcommand{\styleforchapternotebegin}{\#1}%
20 }
21 \newcommand{\setstyleforchapternoteend}{[1]{%
22   \renewcommand{\styleforchapternoteend}{\#1}%
23 }
24 \newcommand{\resetendnotes}{{}}
25 \newif\ifnotesbychapteron \notesbychapteronfalse
26 \newcommand{\notesbychapter}{\notesbychapterontrue}
```

File 90 **l warp-endnotes.sty**

§ 183 Package **endnotes**

(Emulates or patches code by JOHN LAVAGNINO.)

Pkg **endnotes** Used as-is.

table of contents To place the endnotes in the TOC, use:

```
\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*\notesname{Endnotes} % optional
```

HTML page To additionally have the endnotes on their own HTML page, if `FileDepth` allows:

```
\ForceHTMLPage
\theendnotes
```

for HTML output:

```
1 \LWR@ProvidesPackagePass{endnotes}

2 \def\enoteformat{%
3   \rightskip\z@ \leftskip\z@ \parindent=1.8em
4   \leavevmode
5   \llap{
6     \makeenmark
7   }
8 }
9
10 \def\@makeenmark{\hbox{\LWR@htmlspan{sup}{\normalfont\theenmark}}}
11 \def\makeenmark{\@makeenmark}
```

File 91 lwarf-enumerate.sty

§ 184 Package **enumerate**

Pkg **enumerate** **enumerate** is supported with no changes.

This package is only required because it was used in the past to drop and then emulate the package. It cannot be removed because an older version which dropped the package may still remain, for example in a local vs. distribution directory, but it is now supported directly by **lwarf** and thus must no longer be dropped.

for HTML output:

```
1 \LWR@ProvidesPackagePass{enumerate}
```

File 92 lwarf-enumitem.sty

§ 185 Package **enumitem**

(Emulates or patches code by JAVIER BEZOS.)

Pkg **enumitem** **enumitem** is supported with minor adjustments.

for HTML output:

```
1 \LWR@ProvidesPackagePass{enumitem}
```

for HTML output: 2 \begin{warpHTML}

```
\newlist {\name} {\type} {\maxdepth}
\renewlist {\name} {\type} {\maxdepth}
```

For **enumitem** lists, new lists must have the start and end actions assigned to the new environment. Renewed lists already have their actions assigned, and thus need no changes.

```
3 \let\LWR@orignewlist\newlist
4
5 \renewcommand*\newlist[3]{%
6 \LWR@orignewlist{\#1}{\#2}{\#3}%
7 \AtBeginEnvironment{\#1}{\@nameuse{\LWR@#2start}}%
8 \AtEndEnvironment{\#1}{\@nameuse{\LWR@#2end}}%
9 }

10 \end{warpHTML}
```

File 93 lwarf-epigraph.sty

§ 186 Package **epigraph**

(Emulates or patches code by PETER WILSON.)

Pkg epigraph **epigraph** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{epigraph}

```
2 \DeclareDocumentCommand{\qitem}{m m}
3 {
4 \begin{BlockClass}{qitem}
5 #1
6 \ifbool{FormatWP}
7 {\begin{BlockClass}[border-top:1px solid gray]{epigraphsource}}
8 {\begin{BlockClass}{epigraphsource}}
9 #2
10 \end{BlockClass}
11 \end{BlockClass}
12 }
```

```
13 \DeclareDocumentCommand{\epigraph}{m m}
14 {
15 \begin{LWR@BlockClassWP}{\LWR@print@mbox{text-align:right}}{}{epigraph}
16 \qitem{\#1}{\#2}
```

```

17 \end{LWR@BlockClassWP}
18 }
19
20 \DeclareDocumentEnvironment{epigraphs}{}{%
21   {\LWR@BlockClassWP{\LWR@print@mbox{text-align:right}}{}{}{epigraph}}%
22 {\endLWR@BlockClassWP}

```

Use css to format epigraphs.

The following are null commands for source compatibility:

```

23 \newenvironment*{flushepinormal}{}{%
24 \@ifclassloaded{memoir}{%
25 \setlength{\epigraphwidth}{.5\linewidth}%
26 \renewcommand{\textflush}{flushepinormal}%
27 \renewcommand{\epigraphhead}[2][0]{\#2}%
28 \renewcommand{\dropchapter}[1]{%
29 \renewcommand*{\undodrop}{}%
30 }% not memoir
31 \newlength{\epigraphwidth}%
32 \setlength{\epigraphwidth}{.5\linewidth}%
33 \newcommand{\textflush}{flushepinormal}%
34 \newcommand{\epigraphflush}{flushright}%
35 \newcommand{\sourceflush}{flushright}%
36 \newcommand*{\epigraphsize}{\small}%
37 \newlength{\epigraphrule}%
38 \newlength{\beforeepigraphskip}%
39 \newlength{\afterepigraphskip}%
40 \newcommand{\epigraphhead}[2][0]{\#2}%
41 \newcommand{\dropchapter}[1]{%
42 \renewcommand*{\undodrop}{}%
43 }% not memoir
44
45 \let\cleartoevenpage\relax% also in nextpage
46 \newcommand{\cleartoevenpage}[1][]{}
```

File 94 **lwarf-epsfig.sty**

§ 187 Package **epsfig**

Pkg **epsfig** **epsfig** is emulated for use by **lwarf**.

 Only the L^AT_EX2e syntax is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{epsfig}[2017/06/25]

A few additional keys to capture the filename:

```

2 \RequirePackage{graphics}
3
4 \define@key{igraph}{file}{%
5   \xdef\LWR@epsfig@filename{\#1}%
6 }
7
8 \define@key{igraph}{figure}{%
9   \xdef\LWR@epsfig@filename{\#1}%
10 }
11
12 \define@key{igraph}{prolog}{}
13
14 \define@key{igraph}{silent}[]{}

```

The captured filename is used as the argument to `\includegraphics`:

```

15 \newcommand{\epsfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}
16
17 \newcommand{\psfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}

```

File 95 **lwarf-epstopdf.sty**

§ 188 Package **epstopdf**

Pkg **epstopdf** Previous versions of **lwarf** had a nullified verison, but now **epstopdf-base** is supported. **lwarf-epstopdf** becomes a placeholder to overwrite previous versions.

See package **epstopdf-base** for details.

for HTML output: 1 \LWR@ProvidesPackagePass{epstopdf}[2016/05/15]

File 96 **lwarf-epstopdf-base.sty**

§ 189 Package **epstopdf-base**

Pkg **epstopdf-base**

Images with an .eps extension will be converted to .pdf. The HTML output uses the **convert to .svg** .svg version, so use

Enter ⇒ lwarfpmk pdftosvg <listofPDFfiles>

to generate .svg versions.

for HTML output: 1 \LWR@ProvidesPackagePass{epstopdf-base}[2016/05/15]

Redefine to remember the image filename, replacing .pdf with .svg. Use the **epstopdf** print version inside a **lateximage**.

```
2 \newcommand*{\LWR@HTML@ETE@OrgGin@setfile}[3]{%
3   \edef\LWR@tempone{\#3}%
4   \StrSubstitute{\LWR@tempone}{.pdf}{.svg}[\LWR@tempone]%
5   \StrSubstitute{\LWR@tempone}{.PDF}{.SVG}[\LWR@tempone]%
6   \xdef\LWR@parsedfilename{\LWR@tempone}%
7 }%
8
9 \LWR@formatted{ETE@OrgGin@setfile}
```

\includegraphics in HTML mode redefines \Gin@setfile to be \LWR@HTML@Gin@setfile, which is now redirected to **epstopdf**'s version:

```
10 \renewcommand*{\LWR@HTML@Gin@setfile}[3]{%
11   \ETE@Gin@setfile{\#1}{\#2}{\#3}%
12 }
```

Allow .eps images to be found if a suffix is not provided:

```
13 \AtBeginDocument{
14 \DeclareGraphicsExtensions{%
15   .eps,.EPS,.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
16 }
17 \DeclareGraphicsRule{.svg}{svg}{.svg}{}
18 \DeclareGraphicsRule{.SVG}{svg}{.SVG}{}
19 }
```

Likewise when inside a **lateximage**:

```
20 \appto\LWR@restoreorigformatting{%
21 \DeclareGraphicsExtensions{%
22   .eps,.EPS,.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
23 }%
24 }
```

File 97 **lwarf-errata.sty**

§ 190 Package **errata**

(Emulates or patches code by MICHAEL KOHLHASE.)

Pkg errata **errata** is patched for use by **l warp**.

This is for v0.3 of **errata**. A newer version of **errata** with more features is under development, at which time the **l warp** version will have to be updated.

for HTML output: Macros are being defined with the math dollar, so enable the HTML version during package loading:

```
1 \StartDefiningMath
```

Now load the package:

```
2 \LWR@ProvidesPackagePass{errata}[2006/11/12]
```

Patches for dynamic inline math:

```
3 \xpatchcmd{\erratumAdd}
4   {$_a^{\arabic{erratum}}$}
5 %   {\inlinemathother$_a^{\arabic{erratum}}$\inlinemathnormal}
6   {\textsubscript{a}\textsuperscript{\arabic{erratum}}}
7   {}
8   {\LWR@patcherror{erratum}{erratumAdd}}
9
10 \xpatchcmd{\erratumDelete}
11   {$_d^{\arabic{erratum}}$}
12 %   {\inlinemathother$_d^{\arabic{erratum}}$\inlinemathnormal}
13   {\textsubscript{d}\textsuperscript{\arabic{erratum}}}
14   {}
15   {\LWR@patcherror{erratum}{erratumDelete}}
16
17 \xpatchcmd{\erratumReplace}
18   {$_r^{\arabic{erratum}}$}
19 %   {\inlinemathother$_r^{\arabic{erratum}}$\inlinemathnormal}
20   {\textsubscript{r}\textsuperscript{\arabic{erratum}}}
21   {}
22   {\LWR@patcherror{erratum}{erratumReplace}}
23
24 \xpatchcmd{\erratum}
25   {$_a$}
26 %   {\inlinemathother$_a$\inlinemathnormal}
27   {\textsubscript{a}}
28   {}
29   {\LWR@patcherror{erratum}{erratumDelete}}
30
31 \xpatchcmd{\erratum}
32   {$_d^{\@thefnmark}$}
33 %   {\inlinemathother$_d^{\@thefnmark} $\inlinemathnormal}
34   {\textsubscript{d}\textsuperscript{\@thefnmark}}
35   {}
36   {\LWR@patcherror{erratum}{eDelete}}
```

```

37
38 \xpatchcmd{\erratum}
39   {$_r^{\{@thefnmark}$$}
40 %   {\inlinemathother$_r^{\{@thefnmark}$$\inlinemathnormal}
41   {\textsubscript{r}\textsuperscript{\{@thefnmark}}}
42   {}
43   {\LWR@patcherror{erratum}{eReplace}}

```

Finish the current page's errata before closing and reloading the list:

```
44 \preto\PrintErrata{\LWR@orignewpage}
```

No longer defining math macros with the HTML \$:

```
45 \StopDefiningMath
```

File 98 lwarf-eso-pic.sty

§ 191 Package **eso-pic**

(Emulates or patches code by ROLF NIEPRASCHK.)

Pkg **eso-pic** **eso-pic** is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{eso-pic}

2 \newcommand*\LenToUnit(){}
3 \newcommand{\AtPageUpperLeft}[1]{}
4 \newcommand{\AtPageLowerLeft}[1]{}
5 \newcommand{\AtPageCenter}[1]{}
6 \newcommand{\AtStockLowerLeft}[1]{}
7 \newcommand{\AtStockUpperLeft}[1]{}
8 \newcommand{\AtStockCenter}[1]{}
9 \newcommand{\AtTextUpperLeft}[1]{}
10 \newcommand{\AtTextLowerLeft}[1]{}
11 \newcommand{\AtTextCenter}[1]{}
12 \NewDocumentCommand{\AddToShipoutPictureBG}{s +m}{}

13 \newcommand{\AddToShipoutPicture}{\AddToShipoutPictureBG}
14 \NewDocumentCommand{\AddToShipoutPictureFG}{s +m}{}
15 \newcommand*\ClearShipoutPictureBG(){}
16 \newcommand*\ClearShipoutPicture(){}
17 \newcommand*\ClearShipoutPictureFG(){}
18 \newcommand{\gridSetup}[6][]{}

```

File 99 **l warp-everypage.sty**

§ 192 Package **everypage**

(Emulates or patches code by SERGIO CALLEGARI.)

Pkg **everypage** **everypage** is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{everypage}
2 \newcommand*{\AddEverypageHook}[1]{}
3 \newcommand*{\AddThispageHook}[1]{}
```

File 100 **l warp-everyshi.sty**

§ 193 Package **everyshi**

(Emulates or patches code by MARTIN SCHRÖDER.)

Pkg **everyshi** Emulated.

for HTML output: Discard all options for **l warp-everyshi**:

```
1 \LWR@ProvidesPackageDrop{everyshi}
2 \newcommand*{\EveryShipout}[1]{}
3 \newcommand*{\AtNextShipout}[1]{}
```

File 101 **l warp-extramarks.sty**

§ 194 Package **extramarks**

(Emulates or patches code by PIET VAN OOSTRUM.)

Pkg **extramarks** **extramarks** is emulated.

for HTML output: Discard all options for **l warp-extramarks**:

```
1 \LWR@ProvidesPackageDrop{extramarks}
```

```

2 \newcommand*{\extramarks}[2]{}
3 \newcommand*{\firstleftxmark}{}
4 \newcommand*{\lastleftxmark}{}
5 \newcommand*{\firstrightxmark}{}
6 \newcommand*{\lastrightxmark}{}
7 \newcommand*{\firstxmark}{}
8 \newcommand*{\lastxmark}{}
9 \newcommand*{\topxmark}{}
10 \newcommand*{\topleftxmark}{}
11 \newcommand*{\firstleftmark}{}
12 \newcommand*{\lastrightmark}{}

```

File 102 **l warp-fancybox.sty**§ 195 Package **fancybox**

(Emulates or patches code by TIMOTHY VAN ZANDT.)

Pkg **fancybox** **fancybox** is supported with some patches.

framed equation example **fancybox**'s documentation has an example `FramedEqn` environment which combines `math`, `\Sbox`, a `minipage`, and an `\fbox`. This combination requires that the entire environment be enclosed inside a `\latexitimage`, which is done by adding `\latexitimage` at the very start of `FramedEqn`'s beginning code, and `\endlatexitimage` at the very end of the ending code. Unfortunately, the `HTML alt` attribute is not used here.

```

\newenvironment{FramedEqn}
{
\latexitimage% NEW
\setlength{\fboxsep}{15pt}
...}{...
\[\fbox{\TheSbox}\]}
\endlatexitimage% NEW
}

```

framing alternatives `\fbox` works with **fancybox**. Also see **l warp**'s `\fboxBlock` macro and `fminipage` environment for alternatives to `\fbox` for framing environments.

framed table example The **fancybox** documentation's example framed table using an `\fbox` containing a `tabular` does not work with **l warp**, but the `FramedTable` environment does work if `\fbox` is replaced by `\fboxBlock`. This method loses `HTML` formatting. A better method is to enclose the table's contents inside a `fminipage` environment. The caption may be placed either inside or outside the `fminipage`:

```
\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
...
\end{tabular}
\end{fminipage}
\end{table}
```

⚠ **framed verbatim** **lwarp** does not support the `verbatim` environment inside a span, box, or `fancybox`'s `\Sbox`, but a `verbatim` may be placed inside a `fminipage`. The `fancybox` documentation's example `FramedVerb` may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
\VerbatimEnvironment
\fminipage{#1}
\begin{Verbatim}
\end{Verbatim}
\endfminipage
}
```

framed \VerbBox `fancybox`'s `\VerbBox` may be used inside `\fbox`.

indented alignment `LVerbatim`, `\LVerbatimInput`, and `\LUseVerbatim` indent with horizontal space which may not line up exactly with what `pdftotext` detects. Some lines may be off slightly in their left edge.

⚠ **\VerbatimFootnotes**
⚠ **sectioning or displaymath** If using `fancybox` or `fancyvrb` with `\VerbatimFootnotes`, and using footnotes in a sectioning command or display math, use `\footnotemark` and `\footnotetext`:

```
\subsection[Subsection Name]
{Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbatim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when `\VerbatimFootnotes` are selected. The browser usually compensates.

1 `\LWR@ProvidesPackagePass{fancybox}`

After the preamble is loaded, after any patches to `Verbatim`:

2 `\AfterEndPreamble{`
3 `\LWR@traceinfo{Patching fancybox.}`

\VerbatimFootnotes Patched to use the new version.

```
4 \def\VerbatimFootnotes{%
5 \let\@footnotetext\V@footnotetext%
6 \let\LWR@footnotetext\V@footnotetext% l warp
7 }
```

\V@@footnotetext Patches in a subset of **l warp**'s \LWR@footnotetext to the **fancyvrb** version of \V@@footnotetext.

```
8 \def\V@@footnotetext{%
9 \LWR@traceinfo{V@footnotetext}%
10 \global\setbox\LWR@footnotes=\vbox\bgroup%
```

Add to any current footnotes:

```
11 \unvbox\LWR@footnotes%
```

Remember the footnote number for \ref:

```
12 \protected@edef@\currentlabel{%
13   \csname p@footnote\endcsname\@thefnmark%
14 }% @currentlabel
```

Use HTML superscripts in the footnote even inside a **lateximage**:

```
15 \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a **lateximage**:

```
16 \ifthenelse{%
17   \boolean{\LWR@doingstartpars} \AND%
18   \cnttest{\value{\LWR@lateximagedepth}}{=}{0}%
19 }%
20 {}%
21 {\LWR@htmlltagc{\LWR@tagregularparagraph}}%
```

Append the footnote to the list:

```
22 \makefntext{}%
23 \bgroup%
24 \aftergroup{\V@@@footnotetext}%
25 \ignorespaces%
26 }%
27 }% AfterEndPreamble
28 \renewcommand*{\@shadowbox}[1]{%
29 \ifbool{FormatWP}{%
30 {\InlineClass[border:1px solid black]{shadowbox}{#1}}%
31 {\InlineClass{shadowbox}{#1}}%
32 }%
33 }
```

```

34 \renewcommand*{\@doublebox}[1]{%
35 \ifbool{FormatWP}{%
36 {\InlineClass[border:1px double black]{doublebox}{#1}}{%
37 {\InlineClass{doublebox}{#1}}{%
38 }{%
39 \renewcommand*{\@ovalbox}[2]{%
40 \ifbool{FormatWP}{%
41 {\InlineClass[border:1px solid black; border-radius:1ex]{ovalbox}{#2}}{%
42 {\%{%
43 \ifthenelse{\isequivalentto{#1}{\thinlines}}{%
44 {\InlineClass{ovalbox}{#2}}{%
45 {\InlineClass{Ovalbox}{#2}}{%
46 }{%
47 }{%
48 }

```

Convert minipages, parboxes, and lists into linear text using the LWR@nestspan environment:

```

49 \let\LWR@origSbox\Sbox
50
51 \def\Sbox{\LWR@origSbox\LWR@nestspan}
52
53
54 \let\LWR@origendSbox\endSbox
55
56 \def\endSbox{\endLWR@nestspan\LWR@origendSbox}

```

Beqnarray is adapted for MATHJAX or enclosed inside a `lateXimage`:

```

57 \RenewEnviron{Beqnarray}{%
58 {\LWR@eqnarrayfactor}{%
59 \csgpreto{Beqnarray*}{\boolfalse{LWR@numbereqnarray}}{%
60 }

```

`\GenericCaption` is enclosed in an HTML block:

```

61 \renewcommand{\GenericCaption}[1]{%
62 \LWR@figcaption{%
63 #1}{%
64 \endLWR@figcaption}{%
65 }

```

`Btrivlist` is enclosed in an HTML block. This is a tabular, and does not use `\item`.

```

\trivlist {\langle l/c/r\rangle} [\langle t/c/b\rangle]
66 \RenewDocumentEnvironment{Btrivlist}{m o}

```

```

67 {%
68   \begin{BlockClass}{Btrivlist}%
69   \tabular{#1}%
70 }
71 {%
72   \endtabular%
73   \end{BlockClass}%
74 }

```

Btrivlist is also neutralized when used inside a span:

```

75 \AtBeginEnvironment{LWR@nestspan}{%
76 \RenewDocumentEnvironment{Btrivlist}{m o}{\begin{Btrivlist}}{\end{Btrivlist}}
77 }

```

lwarf's handling of \item is patched to accept **fancybox**'s optional arguments:

```

78 \let\LWRFB@origitemizeitem\LWR@itemizeitem
79 \let\LWRFB@origdescitem\LWR@descitem
80
81 \RenewDocumentCommand{\LWR@itemizeitem}{d()o}{%
82   \IfValueTF{#2}{%
83     \LWRFB@origitemizeitem[#2]%
84   }{%
85     \LWRFB@origitemizeitem%
86   }%
87 }
88
89 \RenewDocumentCommand{\LWR@descitem}{d()o}{%
90   \IfValueTF{#2}{%
91     \LWRFB@origdescitem[#2]~%
92   }{%
93     \LWRFB@origdescitem%
94   }%
95 }

96 \RenewDocumentCommand{\LWR@nestspanitem}{d()}{%
97 \if@newlist\else{\LWR@htmltagc{br /}}\fi%
98 \LWR@origitem%
99 }

```

The various boxed lists become regular lists:

```

100 \renewenvironment{Bitemize}[1][] {\begin{itemize}}{\end{itemize}}
101 \renewenvironment{Benumerate}[1][] {\begin{enumerate}}{\end{enumerate}}
102 \renewenvironment{Bdescription}[1][] {\begin{description}}{\end{description}}

```

\boxput simply prints one then the other argument, side-by-side instead of above and behind:

```
103 \RenewDocumentCommand{\boxput}{s d() m m}{%
104 \IfBooleanTF{#1}{#3\quad#4}{#4\quad#3}%
105 }
```

Neutralized commands:

```
106 \RenewDocumentCommand{\fancyput}{s d() m}{}
107 \RenewDocumentCommand{\thisfancyput}{s d() m}{}
108
109 \RenewDocumentCommand{\fancypage}{m m}{}
110 \RenewDocumentCommand{\thisfancypage}{m m}{}
111
112 \def\LandScape#1{}
113 \def\endLandScape{}
114 \def\@Landscape#1#2#3{}
115 \def\endLandscape{}
```

Low-level patches for `UseVerbatim` and friends:

```
116 \let\LWRFB@UseVerbatim\UseVerbatim
117 \renewcommand*{\UseVerbatim}[1]{%
118 \LWR@atbeginverbatim{3}{Verbatim}}%
119 \LWRFB@UseVerbatim{#1}%
120 \LWR@afterendverbatim{.5}%
121 }
122
123 \let\LWRFB@LUseVerbatim\LUseVerbatim
124
125 \renewcommand*{\LUseVerbatim}[1]{%
126 \LWR@atbeginverbatim{3}{LVerbatim}}%
127 \noindent%
128 \LWRFB@LUseVerbatim{#1}%
129 \LWR@afterendverbatim{.5}%
130 }
131
132 \def\@BUseVerbatim[#1]#2{%
133 \LWR@atbeginverbatim{3}{BVerbatim}}%
134 \LWRFB@UseVerbatim{#2}%
135 \LWR@afterendverbatim{.5}%
136 }
```

File 103 **l warp-fancyheadings.sty**

§ 196 Package **fancyheadings**

Pkg **fancyheadings** **fancyheadings** is superceded by **fancyhdr**.

for HTML output: 1 \LWR@loadnever{fancyheadings}{fancyhdr}

File 104 **l warp-fancyhdr.sty**

§ 197 Package **fancyhdr**

(Emulates or patches code by PIET VAN OOSTRUM.)

Pkg **fancyhdr** **fancyhdr** is nullified.

for HTML output: Discard all options for **l warp-fancyhdr**:

```
1 \LWR@ProvidesPackageDrop{fancyhdr}

2 \newcommand*{\fancyhead}[2] []
3 \newcommand*{\fancyfoot}[2] []
4 \newcommand*{\fancyhf}[2] []
5 \newcommand*{\fancypagestyle}[2] []
6 \newcommand*{\lhead}[2] []
7 \newcommand*{\chead}[2] []
8 \newcommand*{\rhead}[2] []
9 \newcommand*{\lfoot}[2] []
10 \newcommand*{\cfoot}[2] []
11 \newcommand*{\rfoot}[2] []
12 \newcommand*{\headrulewidth} {}
13 \newcommand*{\footrulewidth} {}
14 \newcommand*{\fancyheadoffset}[2] []
15 \newcommand*{\fancyfootoffset}[2] []
16 \newcommand*{\fancyhfoffset}[2] []
17 \newcommand*{\iffloatpage}[2]{#2}
18 \newcommand*{\ifftopfloat}[2]{#2}
19 \newcommand*{\iffbotfloat}[2]{#2}
```

File 105 **l warp-fancyref.sty**

§ 198 Package **fancyref**

Pkg **fancyref** **fancyref** is emulated.

for HTML output: 1 \LWR@ProvidesPackagePass{fancyref}

To remove the `margin` option, if `\fancyrefhook` is anything other than the `paren` option, then force it to the default instead. (Comparing to the `margin` option was not possible since **l warp** has revised the meaning of `\mbox` so the comparison failed.)

```

2 \newcommand*{\LWRfref@parenfancyrefhook}[1]{(#1)}
3
4 \ifdef\streq{\fancyrefhook}{\LWRfref@parenfancyrefhook}
5 {}{
6   \renewcommand*{\fancyrefhook}[1]{#1}%
7 }
```

Modified to ignore the page number and **varioref**.

```

8 \renewcommand*{\@f@ref}[4]{%
9   \@ifundefined{#1r@#2@#3}{%
10     \PackageError{fancyref}{%
11       \backslash\@nameuse{#1ref}\space format ``#2''%
12       undefined\MessageBreak
13       for label type ``#3''%
14     }{%
15       The format ``#2'' was not defined for the label type
16       ``#3''\MessageBreak
17       and the \backslash\@nameuse{#1ref}\space command. Perhaps
18       you have only misspelled its name.\MessageBreak
19       Otherwise you will have to define it with
20       \protect\new#1refformat\MessageBreak
21       prior to using it.%
22     }%
23   }{%
24     \fancyrefhook{%
25       \@nameuse{#1r@#2@#3}%
26       {\@ref{#3\fancyrefargdelim#4}}%
27     }%
28     {\@pageref{#3\fancyrefargdelim#4}}% original
29     {\@fancyref@page@ref{#3\fancyrefargdelim#4}}% original
30   }%
31 }
```

```
32 }%
33 }%
```

File 106 **l warp-fancytabs.sty**

§ 199 Package **fancytabs**

Pkg **fancytabs** **fancytabs** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{fancytabs}

2 \newcommand{\fancytab}[3][RIGHT]{}
3 \newcommand{\fancytabsStyle}[1]{}
4 \newcommand{\fancytabsHeight}[1]{}
5 \newcommand{\fancytabsWidth}[1]{}
6 \newcommand{\fancytabsCount}[1]{}
7 \newcommand{\fancytabsLeftColor}[1]{}
8 \newcommand{\fancytabsRightColor}[1]{}
9 \newcommand{\fancytabsTop}[1]{}
10 \newcommand{\fancytabsTextVPos}[1]{}
11 \newcommand{\fancytabsTextHPos}[1]{}
12 \newcommand{\fancytabsGap}[1]{}
13 \newcommand{\fancytabsFloor}[1]{}
14 \newcommand{\fancytabsRotate}[1]{}
```

File 107 **l warp-fancyvrb.sty**

§ 200 Package **fancyvrb**

(Emulates or patches code by TIMOTHY VAN ZANDT.)

Pkg **fancyvrb** **fancyvrb** is supported with some patches.

⚠ **\VerbatimFootnotes**
 ⚠ **sectioning or**
displaymath If using **fancybox** or **fancyvrb** with **\VerbatimFootnotes**, and using footnotes in a sectioning command or display math, use **\footnotemark** and **\footnotetext**:

```
\subsection[Subsection Name]
  {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when `\VerbatimFootnotes` are selected. The browser usually compensates.

```
1 \RequirePackage{xcolor}%
2 for \convertcolorspec
3 \LWR@ProvidesPackagePass{fancyvrb}
```

Initial default patch for `fancyvrb`:

```
4 \fvset{frame=none}%
```

After the preamble is loaded, after any patches to `Verbatim`:

```
5 \AfterEndPreamble{
6 \LWR@traceinfo{Patching fancyvrb.}}
```

`\VerbatimFootnotes` Patched to use the new version.

```
7 \def\VerbatimFootnotes{%
8 \let\@footnotetext\V@footnotetext%
9 \let\footnote\V@footnote%
10 \let\LWR@footnotetext\V@footnotetext% l warp
11 }
```

`\V@@footnotetext` Patches in a subset of `l warp`'s `\LWR@footnotetext` to the `fancyvrb` version of `\V@footnotetext`.

```
12 \def\V@@footnotetext{%
13 \LWR@traceinfo{V@footnotetext}%
14 \global\setbox\LWR@footnotes=\vbox\bgroup%
```

Add to any current footnotes:

```
15 \unvbox\LWR@footnotes%
```

Remember the footnote number for `\ref`:

```
16 \protected@edef@\currentlabel{%
17 \csname p@footnote\endcsname\@thefnmark%
18 }% @currentlabel
```

Use HTML superscripts in the footnote even inside a `lateximage`:

```
19 \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a `lateximage`:

```
20 \ifthenelse{%
21 \boolean{\LWR@doingstartpars} \AND%
22 \cnttest{\value{\LWR@lateximagedepth}}{=}{0}%
23 }%
```

```
24      {}%
25      {\LWR@htmltagc{\LWR@tagregularparagraph}}%
```

Append the footnote to the list:

```
26      \@makefntext{}%
27      \bgroup%
28      \aftergroup{\V@@@footnotetext}%
29      \ignorespaces%
30 }%
31 \preto\FVB@Verbatim{\LWR@forcenewpage}
32 \preto\FVB@LVerbatim{\LWR@forcenewpage}
33 % \preto\FVB@BVerbatim{\LWR@forcenewpage}% Fails, so done below.
```

Simplified to remove PDF formatting:

```
34 \def\FV@BeginListFrame@Single{%
35   \FV@SingleFrameLine{\z@}%
36 }
37
38 \def\FV@EndListFrame@Single{%
39   \FV@SingleFrameLine{\@ne}%
40 }
41
42 \def\FV@BeginListFrame@Lines{%
43   \FV@SingleFrameLine{\z@}%
44 }
45
46 \def\FV@EndListFrame@Lines{%
47   \FV@SingleFrameLine{\@ne}%
48 }
49
50 \renewcommand*\FV@SingleFrameSep{}
```

Adds HTML formatting:

```
51 \def\FV@BUseVerbatim#1{%
52   \LWR@atbeginverbatim[\LWR@FVstyle]{0}{verbatim}%
53   \FV@BVerbatimBegin#1\FV@BVerbatimEnd%
54   \LWR@afterendverbatim{0}%
55 }
```

`\LWR@FVstyle` Holds the style of the verbatim.

```
56 \newcommand*\LWR@FVstyle{}
```

The following patches to `Verbatim` are executed at the start and end of the environment, depending on the choice of `frame`. Original code is from the `fancyvrb` package.

```

57 \newcommand*{\LWR@fvstartnone}{%
58 \LWR@traceinfo{fvstartnone}%
59 % \hbox to\z@{%
60 \LWR@atbeginverbatim[\LWR@FVstyle]{0}{verbatim}%
61 }%
62 }
63
64 \newcommand*{\LWR@f vendnone}{%
65 \LWR@traceinfo{f vendnone}%
66 % \hbox to\z@{%
67 \LWR@afterendverbatim{0}%
68 }%
69 }
70
71 \newcommand*{\LWR@fvstartsingl e}{%
72 \LWR@traceinfo{fvstartsingl e}%
73 \LWR@fvstartnone%
74 \FV@BeginListFrame@Single%
75 }
76
77 \newcommand*{\LWR@fvendsingl e}{%
78 \LWR@traceinfo{fvendsingl e}%
79 \FV@EndListFrame@Single%
80 \LWR@f vendnone%
81 }
82
83 \newcommand*{\LWR@fvstartline}{%
84 \LWR@traceinfo{fvstartline}%
85 \LWR@fvstartnone%
86 % \setlength{\LWR@templengthone}{\baselineskip}%
87 \FV@BeginListFrame@Lines%
88 % \setlength{\baselineskip}{\LWR@templengthone}%
89 % \setlength{\baselineskip}{5pt}%
90 }
91
92 \newcommand*{\LWR@f vendline}{%
93 \LWR@traceinfo{f vendline}%
94 \FV@EndListFrame@Lines%
95 \LWR@f vendnone%
96 }
```

The following patches select the start/left/right/end behaviors depending on `frame`. Original code is from the `fancyvrb` package.

```
97 \newcommand*{\LWR@FVfindbordercolor}{%
```

```
98 \FancyVerbRuleColor%
99 \LWR@findcurrenttextcolor%
100 \color{black}%
101 }
102
103 % border width of \FV@FrameRule
104 \newcommand*{\LWR@FVborderstyle}[1]{%
105 padding#1: \strip@pt\dimexpr \FV@FrameSep\relax\relax pt ; %
106 \LWR@FVfindbordercolor %
107 border#1: \strip@pt\dimexpr \FV@FrameRule\relax\relax pt %
108 solid \LWR@origpound\LWR@tempcolor ; %
109 }
110
111 \def\FV@Frame@none{%
112 \renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle}%
113 \let\FV@BeginListFrame\LWR@fvstartnone%
114 \let\FV@LeftListFrame\relax%
115 \let\FV@RightListFrame\relax%
116 \let\FV@EndListFrame\LWR@fvendnone}
117
118 \FV@Frame@none% default values
119
120 \def\FV@Frame@singles{%
121 \renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle\LWR@FVborderstyle{} }%
122 \let\FV@BeginListFrame\LWR@fvstartsingle%
123 \let\FV@LeftListFrame\FV@LeftListFrame@Single%
124 \let\FV@RightListFrame\FV@RightListFrame@Single%
125 \let\FV@EndListFrame\LWR@fvendsingle}
126
127 \def\FV@Frame@lines{%
128 \renewcommand*{\LWR@FVstyle}{%
129     \LWR@currenttextcolorstyle\LWR@FVborderstyle{-top}\LWR@FVborderstyle{-bottom}%
130 }%
131 \let\FV@BeginListFrame\LWR@fvstartline%
132 \let\FV@LeftListFrame\relax%
133 \let\FV@RightListFrame\relax%
134 \let\FV@EndListFrame\LWR@fvendline}
135
136 \def\FV@Frame@topline{%
137 \renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle\LWR@FVborderstyle{-top}}%
138 \let\FV@BeginListFrame\LWR@fvstartline%
139 \let\FV@LeftListFrame\relax%
140 \let\FV@RightListFrame\relax%
141 \let\FV@EndListFrame\LWR@fvendnone}
142
143 \def\FV@Frame@bottomline{%
144 \renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle\LWR@FVborderstyle{-bottom}}%
145 \let\FV@BeginListFrame\LWR@fvstartnone%
146 \let\FV@LeftListFrame\relax%
147 \let\FV@RightListFrame\relax%
```

```

148 \let\FV@EndListFrame\LWR@fvendline}
149
150 \def\FV@Frame@leftline{%
151 \renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle\LWR@FVborderstyle{-left}}}%
152 % To define the \FV@FrameFillLine macro (from \FV@BeginListFrame)
153 \ifx\FancyVerbFillColor\relax%
154 \let\FV@FrameFillLine\relax%
155 \else%
156 \tempdima\FV@FrameRule\relax%
157 \multiply\tempdima-\tw@%
158 \edef\FV@FrameFillLine{%
159 {\noexpand\FancyVerbFillColor{\vrule\@width\number\tempdima sp}%
160 \kern-\number\tempdima sp}}%
161 \fi%
162 \let\FV@BeginListFrame\LWR@fvstartnone%
163 \let\FV@LeftListFrame\FV@LeftListFrame@Single%
164 \let\FV@RightListFrame\relax%
165 \let\FV@EndListFrame\LWR@fvendnone}

```

Adds the optional label to the top and bottom edges. Original code is from the **fancyvrb** package.

```

166 \def\FV@SingleFrameLine#1{%
167 %    \hbox to\z@{%
168 %        \kern\leftmargin
169 %        \ifnum#1=\z@\relax
170 %            \let\FV@Label\FV@LabelBegin
171 %        \else
172 %            \let\FV@Label\FV@LabelEnd
173 %        \fi
174 %        \ifx\FV@Label\relax
175 %            \FancyVerbRuleColor{\vrule \@width\linewidth \@height\FV@FrameRule}%
176 %        \else
177 %            \ifnum#1=\z@
178 %                \setbox\z@\hbox{\strut\enspace\FV@LabelBegin\enspace\strut}%
179 %                \ifx\FV@LabelPositionTopLine\relax
180 %                \else
181 %                    \LWR@FVfindbordercolor
182 %                    \LWR@htmltagc{%
183 %                        div class="fancyvrblabel" % extra space
184 %                        style="color: \LWR@origpound\LWR@tempcolor"%
185 %                    }
186 %                    \LWR@origtextrm{\FV@LabelBegin}%
187 %                    \LWR@htmltagc{/div}
188 %                \fi
189 %            \else
190 %                \setbox\z@\hbox{\strut\enspace\FV@LabelEnd\enspace\strut}%
191 %                \ifx\FV@LabelPositionBottomLine\relax
192 %                \else

```

```

193     \LWR@FVfindbordercolor
194
195     \LWR@htmltagc{%
196         div class="fancyvrblabel" % extra space
197             style="color: \LWR@origpound\LWR@tempcolor"%
198     }
199     \LWR@origtextrm{\FV@LabelEnd}
200     \LWR@htmltagc{/div}
201     \fi
202     \fi
203     \fi
204 %
205 %
206 }
```

Processes each line, adding optional line numbers. Original code is from the **fancyvrb** package.

```

207 \def\FV@ListProcessLine#1{%
208     \hbox to \hsize{%
209 %         \kern\leftmargin
210         \hbox to \VerbatimHTMLWidth {%
211             \ifcsvvoid{FV@LeftListNumber}{}{\kern 2.5em}%
212             \FV@LeftListNumber%
213 %
214             \FV@LeftListFrame
215             \FancyVerbFormatLine{#1}%
216 %
217             \FV@RightListFrame
218             \FV@RightListNumber%
219         }%
220         \hss% required to avoid underfull hboxes
221 }
```

Env **BVerbatim**

```

222 \AtBeginEnvironment{BVerbatim}
223 {%
224 \LWR@forcenewpage% instead of \preto
225 \LWR@atbeginverbatim{0}{bverbatim}%
226 }
227
228 \AfterEndEnvironment{BVerbatim}
229 {%
230 \LWR@afterendverbatim{0}%
231 }
```

End of the modifications to make at the end of the preamble:

```
232 } % \AfterEndPreamble
```

File 108 **lwarf-figcaps.sty**

§ 201 Package **figcaps**

(Emulates or patches code by PATRICK W. DALY.)

Pkg **figcaps** Emulated.

for HTML output: Discard all options for **lwarf-figcaps**:

```
1 \LWR@ProvidesPackageDrop{figcaps}

2 \newcommand*{\figcapson}={}
3 \newcommand*{\figcapsoff}={}
4 \newcommand*{\printfigures}={}
5 \newcommand*{\figmarkon}={}
6 \newcommand*{\figmarkoff}={}
7 \def\figurecapname{Figure Captions}
8 \def\tablepagename{Tables}
9 \def\figurepagename{Figures}
```

File 109 **lwarf-figsize.sty**

§ 202 Package **figsize**

(Emulates or patches code by ANTHONY A. TANBAKUCHI.)

Pkg **figsize** **figsize** is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{figsize}
```

Emulates a virtual 6×9 inch textsize.

```
2 \newlength{\figwidth}
3 \newlength{\figheight}
4
5 \newcommand{\SetFigLayout}[3][0]{%
6 \setlength{\figheight}{8in}%
7 \setlength{\figheight}{\figheight / #2}%
8 %
```

```

9 \setlength{\figwidth}{5.5in}%
10 \setlength{\figwidth}{\figwidth / #3}%
11 }

```

File 110 **l warp-fix2col.sty**

§ 203 Package **fix2col**

Pkg **fix2col** **fix2col** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{fix2col}

File 111 **l warp-fixme.sty**

§ 204 Package **fixme**

(Emulates or patches code by DIDIER VERRA.)

Pkg **fixme** **fixme** is patched for use by **l warp**.

⚠ **external layouts** External layouts (\fxloadlayouts) are not supported.

User control is provided for setting the HTML styling of the “faces”. The defaults are as follows, and may be changed in the preamble after **fixme** is loaded:

```

\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}

```

for HTML output: 1 \LWR@ProvidesPackagePass{fixme}

Restore **l warp**'s version of \wrindex, ignoring the **fixme** package's target option:

2 \let\@wrindex\LWR@wrindex

Float-related macros required by **l warp**:

```

3 \newcommand{\ext@fixme}{lox}
4
5 \renewcommand{\l@fixme}[2]{\hypertocfloat{1}{fixme}{lox}{#1}{#2}}

```

Other modifications:

```

6 \def\FXFaceInlineHTMLStyle{font-weight:bold}
7
8 \renewcommand*\FXLayoutInline[3]{ %
9   \InlineClass[\FXFaceInlineHTMLStyle]{fixmeinline}%
10   {\@fxtextstd{#1}{#2}{#3}}%
11 }
12
13 \def\FXFaceEnvHTMLStyle{font-weight:bold}
14
15 \renewcommand*\FXEnvLayoutPlainBegin[2]{%
16   \BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}%
17   \ignorespaces#2 \fxnotename{#1}: \ignorespaces}%
18
19 \renewcommand*\FXEnvLayoutPlainEnd[2]{\endBlockClass}%
20
21 \renewcommand*\FXEnvLayoutSignatureBegin[2]{%
22   \BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}%
23   \fxnotename{#1}: \ignorespaces}%
24
25 \renewcommand*\FXEnvLayoutSignatureEnd[2]{\@fxsignature{#2}\endBlockClass}%
26
27 \def\FXFaceSignatureHTMLStyle{font-style:italic}
28
29 \DeclareRobustCommand*\@fxsignature[1]{%
30   \ifthenelse{\equal{#1}{}}{%
31     {}%
32     { -- \InlineClass[\FXFaceSignatureHTMLStyle]{fixmesignature}{#1}}%
33   }%
34
35
36 \def\FXFaceTargetHTMLStyle{font-style:italic}
37
38 \renewcommand\FXTargetLayoutPlain[2]{%
39   \InlineClass[\FXFaceTargetHTMLStyle]{fixmetarget}{#2}}%
40 }

```

File 112 **lwarf-fixmetodonotes.sty**

§ 205 Package **fixmetodonotes**

(Emulates or patches code by GIOELE BARABUCCI.)

Pkg **fixmetodonotes** **fixmetodonotes** is patched for use by **lwarf**.

for HTML output:

```

1 \LWR@ProvidesPackagePass{fixmetodonotes}

2 \renewcommand{\NOTES@addtolist}[2]{%

```

```

3      \refstepcounter{NOTES@note}%
4 %    \phantomsection% REMOVED
5      \addcontentsline{notes}{NOTES@note}{%
6          \protect\numberline{\theNOTES@note}{\#1}: {\#2}}%
7      }%
8 }
9
10 \renewcommand{\NOTES@marker}[2]{\fbox{%
11     \textcolor{#2}{% WAS \color
12         \textbf{\#1}}%
13 }}
```

14

15 \renewcommand{\NOTES@colorline}[2]{%
16 \bgroup%
17 \ULon{\LWR@backgroundcolor{\#1}{\#2}}%
18 }

File 113 **lwarf-flafter.sty**

§ 206 Package **flafter**

Pkg **flafter** **flafter** is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{flafter}
2 \providecommand\f@trace[1]{}
```

File 114 **lwarf-float.sty**

§ 207 Package **float**

(Emulates or patches code by ANSELM LINGNAU.)

Pkg **float** **float** is emulated.

Float styles boxed and ruled are emulated by css and a float class according to style.

The HTML <figure> class is set to the float type, so css may also be used to format the float and its caption, according to float type. Furthermore, an additional class is set to the float style: plain, plaintop, boxed, or ruled, so css may be used to format by float style as well. Default formatting by css is provided for ruled and boxed styles.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{float}[2001/11/08]
```

\listof See section 72.2 for the \listof command.

\LWR@floatstyle The default float style:

```
2 \newcommand*\{\LWR@floatstyle\}{plain}
```

\newfloat {\langle 1: type\rangle} {\langle 2: placement\rangle} {\langle 3: ext\rangle} [{\langle 4: within\rangle}]

Emulates the \newfloat command from the **float** package.
“placement” is ignored.

```
3 \NewDocumentCommand{\newfloat}{m m m o}{%
4 \IfValueTF{#4}{%
5 {\DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}}{%
6 {\DeclareFloatingEnvironment[fileext=#3]{#1}}{}}
```

Remember the float style:

```
7 \csedef{\LWR@floatstyle@#1}{\LWR@floatstyle}%
```

newfloat package automatically creates the \listof command for new floats, but **float** does not, so remove \listof here in case it is manually created later.

```
8 \cslet{\listof#1s}{\relax}%
9 \cslet{\listof#1es}{\relax}%
```

Likesize, **newfloat** also creates \l@<type>, but **float** does not, so remove it here:

```
10 \cslet{\l@#1}{\relax}%
11 }
```

\floatname {\langle type\rangle} {\langle name\rangle}

Sets the text name of the float, such as “Figure”.

```
12 \NewDocumentCommand{\floatname}{m +m}{%
13   \SetupFloatingEnvironment{#1}{name=#2}}%
14 }
```

\floatplacement {\langle type\rangle} {\langle placement\rangle}

Float placement is ignored.

```
15 \newcommand*{\floatplacement}[2]{%
16   \SetupFloatingEnvironment{#1}{placement=#2}}%
17 }
```

\floatstyle {\langle style\rangle}

Remember the style for future floats:

```
18 \newcommand{\floatstyle}[1]{%
19     \def\LWR@floatstyle{#1}%
20 }
```

```
\restylefloat * {\langle type \rangle}
```

Remember the style for this float:

```
21 \NewDocumentCommand{\restylefloat}{s m}{%
22     \csedef{LWR@floatstyle@#2}{\LWR@floatstyle}%
23 }
```

File 115 **l warp-floatfl t.sty**

§ 208 Package **floatfl t**

(Emulates or patches code by MATS DAHLGREN.)

Pkg **floatfl t** Emulated.

for HTML output: Discard all options for **l warp-floatfl t**:

```
1 \LWR@ProvidesPackageDrop{floatfl t}
```

Env **[⟨⟩]** **offset** {⟨type⟩} {⟨width⟩} Borrowed from the **l warp** version of **keyfloat**:

```
2 \NewDocumentEnvironment{KFLTfloatfl t@marginfloat}{O{-1.2ex} m m}%
3 {%
4 \setlength{\LWR@templengthone}{#3}%
5 \LWR@BlockClassWP{%
6     float:right; %
7     width:\LWR@printlength{\LWR@templengthone}; % extra space
8     margin:10pt%
9 }{%
10     width:\LWR@printlength{\LWR@templengthone}%
11 }%
12 {marginblock}%
13 \captionsetup{type=#2}%
14 }%
15 {%
16 \endLWR@BlockClassWP%
17 }
```

Env **floatingfigure** [**⟨placement⟩**] {⟨width⟩}

```
18 \DeclareDocumentEnvironment{floatingfigure}{o m}
```

```
19  {\begin{KFLTfloatfltno@marginfloat}{figure}{#2}}
20  {\end{KFLTfloatfltno@marginfloat}}
```

Env **floatingtable** [*placement*]
 21 \DeclareDocumentEnvironment{floatingtable}{o}
 22 {\begin{KFLTfloatfltno@marginfloat}{table}{1.5in}}
 23 {\end{KFLTfloatfltno@marginfloat}}

File 116 **l warp-floatpag.sty**

§ 209 Package **floatpag**

(Emulates or patches code by VYTAS STATULEVIČIUS AND SIGITAS TOLUŠIS.)

Pkg **floatpag** Emulated.

for HTML output: Discard all options for **l warp-floatpag**:

```
1 \LWR@ProvidesPackageDrop{floatpag}

2 \newcommand*{\floatpagestyle}[1]{}
3 \newcommand*{\rotfloatpagestyle}[1]{}
4 \newcommand*{\thisfloatpagestyle}[1]{}
```

File 117 **l warp-floatrow.sty**

§ 210 Package **floatrow**

(Emulates or patches code by OLGA LAPKO.)

Pkg **floatrow** **floatrow** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{floatrow}

⚠ **Misplaced alignment tab character &** Use `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros using `\ttabbox` with a tabular inside. See section 9.9.

⚠ **subfig package** When combined with the **subfig** package, while inside a `subfloatrow` `\ffigbox` and `\ttabbox` must have the caption in the first of the two of the mandatory arguments.

⚠ **\FBwidth, \FBheight** The emulation of **floatrow** does not support `\FBwidth` or `\FBheight`. These values are pre-set to `.3\linewidth` and `2in`. Possible solutions include:

- Use fixed lengths. **l warp** will scale the HTML lengths appropriately.
- Use **warpprint** and **warpHTML** environments to select appropriate values for each case.
- Inside a **warpHTML** environment, manually change **\FBwidth** or **\FBheight** before the **\ffigbox** or **\ttabbox**. Use **\FBwidth** or **\FBheight** normally afterwards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

After everything has loaded, remember whether **subcaption** was loaded. If not, it is assumed that **subfig** is used instead:

```

2 \newbool{LWR@subcaptionloaded}
3
4 \AtBeginDocument{
5 \@ifpackageloaded{subcaption}
6 {\booltrue{LWR@subcaptionloaded}}
7 {\boolfalse{LWR@subcaptionloaded}}
8 }

\fbox [⟨1 preamble⟩] {⟨2 captype⟩} [⟨3 width⟩] [⟨4 height⟩] [⟨5 vert pos⟩] {⟨6 caption⟩}
{⟨7 object⟩}

```

Only parameters for **captype**, **width**, **caption**, and **object** are used.

LWR@insubfloatrow is true if inside a **subfloatrow** environment.

There are two actions, depending on the use of **subcaption** or **subfig**.

```

9 \NewDocumentCommand{\fbox}{o m o o +m +m}{%
10 \ifbool{LWR@subcaptionloaded}{%
11 {%

```

For **subcaption**:

```

12 \ifbool{LWR@insubfloatrow}{%
13 {%

```

subfigure and **subtable** environments take **width** as an argument.

```

14 \IfValueTF{#3}{%
15 {\@nameuse{sub#2}{#3}}%
16 {\@nameuse{sub#2}{\linewidth}}%
17 }%
18 {%

```

figure and **table** environments do not take a **width** argument.

```

19 \@nameuse{#2}%
20 }%
21 #6

```

```
22
23      #7
```

End the environments:

```
24      \ifbool{LWR@insubfloatrow}%
25      {\@nameuse{endsub#2}}%
26      {\@nameuse{end#2}}%
27 }% subcaption
28 { % assume subfig
```

For **subfig**:

```
29 \ifbool{LWR@insubfloatrow}%
30 { % subfig in a subfloatrow
```

\subfloat is a macro, not an environment.

Package **subfig**'s \subfloat command takes an optional argument which is the caption, but \floatbox argument #6 contains commands to create the caption and label, not the caption itself. Thus, \caption is temporarily disabled to return its own argument without braces.

```
31      \begingroup
32      \let\caption\@firstofone
33      \subfloat[#6]{#7}
34      \endgroup
35 }% subfig in a subfloatrow
36 { % subfig package, but not a subfig
```

figure and **table** are environments:

```
37 \@nameuse{#2}
38 #6
39
40 #7
41 \@nameuse{end#2}
42 }% subfig package, but not a subfig
43 }% assume subfig
44 }
```

Not used:

```
45 \newcommand*\{\nocapbeside\}{}%
46 \newcommand*\{\capbeside\}{}%
47 \newcommand*\{\caption\}{}%
48 \newlength{\FBwidth}%
49 \setlength{\FBwidth}{.3\linewidth}%
50 \newlength{\FBheight}%
51 \setlength{\FBheight}{2in}%
52 \newcommand*\{\useFCwidth\}{}%
53 \newcommand{\floatsetup}[2][]{}
54 \newcommand{\thisfloatsetup}[1]{}%
55 \newcommand{\clearfloatsetup}[1]{}%
```

```

56 \newcommand*{\killfloatstyle}{}

\newfloatcommand {⟨1 command⟩} {⟨2 captype⟩} [⟨3 preamble⟩] [⟨4 default width⟩]
Preamble and default width are ignored.

57 \NewDocumentCommand{\newfloatcommand}{m m o o}{%
58 \cnamedef{#1}{%
59 \floatbox{#2}{%
60 }%
61 }}

\renewfloatcommand {⟨1 command⟩} {⟨2 captype⟩} [⟨3 preamble⟩] [⟨4 default width⟩]
Preamble and default width are ignored.

62 \NewDocumentCommand{\renewfloatcommand}{m m o o}{%
63 \cnamedef{#1}{%
64 \floatbox{#2}{%
65 }%
66 }}

\ffigbox [⟨width⟩] [⟨height⟩] [⟨vposn⟩] {⟨caption commands⟩} {⟨contents⟩}
67 \newfloatcommand{ffigbox}{figure}{\nocapbeside}[]

\ttabbox [⟨width⟩] [⟨height⟩] [⟨vposn⟩] {⟨caption commands⟩} {⟨contents⟩}
68 \newfloatcommand{ttabbox}{table}{\captop}{\FBwidth}

\fcapside [⟨width⟩] [⟨height⟩] [⟨vposn⟩] {⟨caption commands⟩} {⟨contents⟩}
69 \newfloatcommand{fcapside}{figure}{\capbeside}[]

Env   floatrow [⟨numfloats⟩]
The row of floats is placed into a <div> of class floatrow.

70 \newenvironment*{floatrow}[1][2]
71 {
72 \LWR@forcenewpage
73 \BlockClass{floatrow}

While inside the floatrow, divide the \linewidth by the number of floats.

74 \booltrue{\LWR@infloatrow}
75 \setlength{\linewidth}{6in/#1}
76 }
77 {
78 \boolfalse{\LWR@infloatrow}
79 \endBlockClass

```

```
80 }
```

Keys for \DeclareNewFloatType:

```
81 \newcommand*{\LWR@frowkeyplacement}{}%
82 \newcommand*{\LWR@frowkeyname}{}%
83 \newcommand*{\LWR@frowkeyfileext}{}%
84 \newcommand*{\LWR@frowkeywithin}{}%
85 \newcommand*{\LWR@frowkeycapstyle}{}%
86
87 \define@key{frowkeys}{placement}{}%
88 \define@key{frowkeys}{name}{\renewcommand{\LWR@frowkeyname}{#1}}%
89 \define@key{frowkeys}{fileext}{\renewcommand{\LWR@frowkeyfileext}{#1}}%
90 \define@key{frowkeys}{within}{\renewcommand{\LWR@frowkeywithin}{#1}}%
91 \define@key{frowkeys}{relatedcapstyle}{}%
```

\DeclareNewFloatType {⟨type⟩} {⟨options⟩}

Use \listoff{type}{Title} to print a list of the floats.

```
92 \newcommand*{\DeclareNewFloatType}[2]{%
```

Reset key values:

```
93 \renewcommand*{\LWR@frowkeyplacement}{}%
94 \renewcommand*{\LWR@frowkeyname}{}%
95 \renewcommand*{\LWR@frowkeyfileext}{}%
96 \renewcommand*{\LWR@frowkeywithin}{}%
97 \renewcommand*{\LWR@frowkeycapstyle}{}%
```

Read new key values:

```
98 \LWR@traceinfo{about to setkeys frowkeys}%
99 \setkeys{frowkeys}{#2}%
100 \LWR@traceinfo{finished setkeys frowkeys}%
```

Create a new float with optional [within]:

```
101 \ifthenelse{\equal{\LWR@frowkeywithin}{} }{%
102 }{%
103   \LWR@traceinfo{about to newfloat #1 \LWR@frowkeyplacement\ %
104     \LWR@frowkeyfileext}%
105   \newfloat{#1}{\LWR@frowkeyplacement}{\LWR@frowkeyfileext}%
106 }{%
107 }{%
108   \LWR@traceinfo{about to newfloat #1\ \LWR@frowkeyplacement\ %
109     \LWR@frowkeyfileext\ \LWR@frowkeywithin}%
110   \newfloat{#1}{\LWR@frowkeyplacement}{\LWR@frowkeywithin}%
111   {\LWR@frowkeyfileext}{\LWR@frowkeywithin}%
112   \LWR@traceinfo{finished newfloat #1}%
113 }%
```

Rename the float if a name was given:

```

114 \ifthenelse{\equal{\LWR@frowkeyname}{}}{%
115 {}{%
116 {\floatname{#1}{\LWR@frowkeyname}}{%
117 }{%

```

Not used:

```

118 \newcommand{\buildFBBOX}[2]{}
119 \newcommand*{\CenterFloatBoxes}{{}}
120 \newcommand*{\TopFloatBoxes}{{}}
121 \newcommand*{\BottomFloatBoxes}{{}}
122 \newcommand*{\PlainFloatBoxes}{{}}
123
124 \newcommand{\capsubrowsettings}{{}}
125
126 \NewDocumentCommand{\RawFloats}{o o}{}{%

```

\RawCaption {*text*}

To be used inside a minipage or parbox.

```
127 \newcommand{\RawCaption}[1]{#1}
```

\floatfoot {*text*}

Places additional text inside a float, inside a css <div> of class floatfoot.

```

128 \NewDocumentCommand{\floatfoot}{s +m}{%
129 \begin{BlockClass}{floatfoot}
130 #2
131 \end{BlockClass}
132 }
```

Used to compute \linewidth.

```

133 \newbool{LWR@insubfloatrow}
134 \boolfalse{LWR@insubfloatrow}
```

Env subfloatrow [*num_floats*]

```

135 \newenvironment*{subfloatrow}[1][2]
136 {
```

The row of floats is placed into a <div> of class floatrow:

```

137 \LWR@forcenewpage
138 \BlockClass{floatrow}
```

While inside the floatrow, LWR@insubfloatrow is set true, which tells \floatbox to use \subfigure or \subtable.

```
139 \begingroup
140 \booltrue{LWR@insubfloatrow}
141 }
142 {
143 \endgroup
144 \endBlockClass
145 \boolfalse{LWR@insubfloatrow}
146 }
```

File 118 **lwarf-fltrace.sty**

§ 211 Package **fltrace**

Pkg fltrace **fltrace** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{fltrace}

2 \def\tracefloats{}
3 \def\tracefloatsoff{}
4 \def\tracefloatvals{}
```

File 119 **lwarf-flushend.sty**

§ 212 Package **flushend**

(Emulates or patches code by SIGITAS TOLUŠIS.)

Pkg flushend Emulated.

for HTML output: Discard all options for **lwarf-flushend**:

```
1 \LWR@ProvidesPackageDrop{flushend}

2 \newcommand*\{\flushend}={}
3 \newcommand*\{\raggedend}={}
4 \newcommand*\{\flushcolsend}={}
5 \newcommand*\{\raggedcolsend}={}
6 \newcommand*\{\atColsBreak}[1]{}
7 \newcommand*\{\atColsEnd}[1]{}
8 \newcommand*\{\showcolsendlrule}{}
```

File 120 **l warp-fnbreak.sty**

§ 213 Package **fnbreak**

Pkg **fnbreak** **fnbreak** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{fnbreak}

2 \newcommand*{\fnbreakverbose}={}
3 \newcommand*{\fnbreaknonverbose}={}
4 \newcommand*{\fnbreaklabel}={}
5 \newcommand*{\fnbreaknolabel}={}
```

File 121 **l warp-fncychap.sty**

§ 214 Package **fncychap**

(Emulates or patches code by ULF A. LINDGREN.)

Pkg **fncychap** **fncychap** is emulated.

for HTML output: Discard all options for **l warp-fncychap**:

```
1 \LWR@ProvidesPackageDrop{fncychap}

2 \def\mghrulefill#1{}
3 \def\ChNameLowerCase{}
4 \def\ChNameUpperCase{}
5 \def\ChNameAsIs{}
6 \def\ChTitleLowerCase{}
7 \def\ChTitleUpperCase{}
8 \def\ChTitleAsIs{}
9 \newcommand{\ChRuleWidth}[1]{}
10 \newcommand{\ChNameVar}[1]{}
11 \newcommand{\ChNumVar}[1]{}
12 \newcommand{\ChTitleVar}[1]{}
13 \newcommand{\TheAlphaChapter}{}
14 \newcommand{\DOCH}{}
15 \newcommand{\DOTI}[1]{}
16 \newcommand{\DOTIS}[1]{}
17 \newlength{\mylen}
18 \newlength{\myhi}
```

```
19 \newlength{\px}
20 \newlength{\py}
21 \newlength{\pyy}
22 \newlength{\pxx}
23 \newlength{\RW}
24 \newcommand{\FmN}[1]{#1}
25 \newcommand{\FmTi}[1]{#1}
```

File 122 **l warp-fnlineno.sty**

§ 215 Package **fnlineno**

Pkg **fnlineno** **fnlineno** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{fnlineno}

File 123 **l warp-fnpos.sty**

§ 216 Package **fnpos**

(Emulates or patches code by HIROSHI NAKASHIMA.)

Pkg **fnpos** **fnpos** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{fnpos}

```
2 \newcommand*{\makeFNbottom}={}
3 \newcommand*{\makeFNmid}={}
4 \newcommand*{\makeFNbelow}={}
5 \newcommand*{\makeFNabove}={}
```

File 124 **l warp-fontenc.sty**

§ 217 Package **fontenc**

Pkg **fontenc** If using pdf^LE_X, **l warp** used to require **fontenc** be loaded before **l warp**, but now **l warp** itself loads \fontenc with T1 encoding, which **l warp** requires. **fontenc** is now allowed to be loaded with another encoding after **l warp**.

l warp-fontenc is no longer necessary, but is still provided to overwrite older versions.

for HTML output: 1 \LWR@ProvidesPackagePass{fontenc}

File 125 **l warp-fontspec.sty**

§ 218 Package **fontspec**

Pkg **fontspec** Error if **fontspec** is loaded after **l warp**.

Discard all options for **l warp-fontspec**:

for HTML output: 1 \LWR@ProvidesPackageDrop{fontspec}[2017/11/09]

2 \LWR@loadbefore{fontspec}

File 126 **l warp-footmisc.sty**

§ 219 Package **footmisc**

(Emulates or patches code by ROBIN FAIRBAIRNS.)

Pkg **footmisc** **footmisc** is emulated.

l warp incidentally happens to emulate the **stable** option.

1 \LWR@ProvidesPackageDrop{footmisc}

Some nullified commands:

2 \newcommand{\footnotelayout}{}
3 \newcommand{\setfnssymbol}[1]{}
4 \NewDocumentCommand{\DefineFNsymbols}{s m o m}{}
5
6 \newdimen\footnotemargin
7 \footnotemargin1.8em\relax
8
9 \newcommand*\hangfootparskip{0.5\baselineskip}
10 \newcommand*\hangfootparindent{0em}%
11
12 \let\pagefootnoterule\footnoterule
13 \let\mpfootnoterule\footnoterule
14 \def\splitfootnoterule{\kern-3\p@ \hrule \kern2.6\p@}
15
16 \providecommand*\multiplefootnotemarker{3sp}
17 \providecommand*\multfootsep{,}

Using **cleveref**:

```
18 \providecommand*\footref[1]{\labelcref{#1}}
```

The following work as-is:

```
19 \newcommand\mpfootnotemark{%
20   \@ifnextchar[%%
21     \xmpfootnotemark%
22   {%
23     \stepcounter\mpfn%
24     \protected@edef\thefnmark{\thempfn}%
25     \footnotemark%
26   }%
27 }
28 \def\xmpfootnotemark[#1]{%
29   \begingroup%
30   \csname c@\mpfn\endcsname #1\relax%
31   \unrestored@protected@edef\thefnmark{\thempfn}%
32   \endgroup%
33   \footnotemark%
34 }
```

File 127 **l warp-footnote.sty**

§ 220 Package **footnote**

(Emulates or patches code by MARK WOODING.)

Pkg **footnote** **footnote** is used with minor patches.

for HTML output: 1 \LWR@ProvidesPackagePass{footnote}

Removed print-version formatting:

```
2 \def\fn@startnote{%
3   \parboxrestore%
4   \protected@edef\currentlabel{\csname p@\mpfn\endcsname\thefnmark}%
5   \color@begingroup% *** conflicts with l warp
6 }
7
8 % \let\fn@endnote\color@endgroup% *** conflicts with l warp
9 \def\fn@endnote{%
10 \LWR@htmlltagc{/LWR@tagregularparagraph}%
11 \LWR@orignewline%
12 }
```

Removed print-version formatting:

```
13 \def\fn@startfntext{%
14   \setbox\z@\vbox\bgroup%
15   \fn@startnote%
16   \fn@prefntext%
17   \ignorespaces%
18 }
```

Removed print-version formatting, added closing paragraph tag:

```
19 \def\fn@endfntext{%
20   \LWR@htmlltagc{\LWR@tagregularparagraph}%
21   \LWR@orignewline%
22   \fn@postfntext%
23   \egroup%
24   \begingroup%
25   \let\@makefntext\@empty%
26   \let\@finalstrut\@gobble%
27   \LetLtxMacro\rule\@gobbletwo% *8* also the optional argument?
28   \footnotetext{\unvbox\z@}%
29   \endgroup%
30 }
```

These have been redefined, so re-\let them again:

```
31 \let\endfootnote\fn@endfntext
32 \let\endfootnotetext\endfootnote
```

File 128 **l warp-footnotehyper.sty**

§ 221 Package **footnotehyper**

Pkg **footnotehyper** **footnotehyper** is a **hyperref**-safe version of **footnote**. For **l warp**, **footnotehyper** is emulated.

for HTML output: Discard all options for **l warp-footnotehyper**:

```
1 \RequirePackage{footnote}
2 \LWR@ProvidesPackageDrop{footnotehyper}
```

File 129 **l warp-footnpag.sty**

§ 222 Package **footnpag**

Pkg **footnpag** **footnpag** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{footnpag}

File 130 **l warp-forest.sty**

§ 223 Package **forest**

(Emulates or patches code by SAŠO ŽIVANOVIĆ.)

Pkg **forest** **forest** is patched for use by **l warp**.

⚠ **\Forest*** The starred version of the macro **\Forest*** is not supported. **l warp** encases each **lateximage** in an environment, so the global results of the starred **\Forest*** are lost.

for HTML output: 1 \LWR@ProvidesPackagePass{forest}

```
2 \BeforeBeginEnvironment{forest}{\begin{lateximage}[forest]}
```

3

```
4 \AfterEndEnvironment{forest}{\end{lateximage}}
```

5

```
6 \RenewDocumentCommand{\Forest}{s D(){} m}{%
```

7 \forest@config{#2}%

8 \IfBooleanTF{#1}{%

9 \PackageError{l warp-forest} %

10 {Starred \Forest is not supported} %

11 {L warp uses an environment for images, but \Forest* cannot work in an environment.} %

12 \let\forest@next\forest@env%

13 }{\let\forest@next\forest@group@env} %

14 \begin{lateximage}[forest] % l warp

15 \forest@next{#3} %

16 \end{lateximage} % l warp

17 }

File 131 **l warp-framed.sty**

§ 224 Package **framed**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg **framed** **framed** is supported and patched by **l warp**.

for HTML output: Accept all options for **l warp-framed**:

```
1 \LWR@ProvidesPackagePass{framed}
2 \RequirePackage{xcolor}%
3
4 \renewenvironment{framed}{%
5 \LWR@forcenewpage
6 \BlockClass{framed}%
7 }
8 {\endBlockClass}
9
10 \renewenvironment{o framed}{%
11 \LWR@forcenewpage
12 \BlockClass{framed}%
13 }
14 {\endBlockClass}
15
16
17 \renewenvironment{shaded}{%
18 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
19 \LWR@forcenewpage
20 \BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
21 }
22 {\endBlockClass}
23
24 \renewenvironment{shaded*}{%
25 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
26 \LWR@forcenewpage
27 \BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
28 }
29 {\endBlockClass}
30
31
32 \renewenvironment{leftbar}{%
33 \LWR@forcenewpage
34     \BlockClass{framedleftbar}
35     \def\FrameCommand{}%
```

```
36 \MakeFramed {}
37 }%
38 {\endMakeFramed\endBlockClass}
39
40
41 \renewenvironment{snugshade}{%
42 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
43 \LWR@forcenewpage
44 \BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
45 }
46 {\endBlockClass}
47
48 \renewenvironment{snugshade*}{%
49 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
50 \LWR@forcenewpage
51 \BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
52 }
53 {\endBlockClass}
54
55 \let\oframed\framed
56 \let\endoframed\endframed
57
58
59 \RenewEnviron{titled-frame}[1]{%
60 \CustomFBox{#1}{\BODY}{\BODY}{\BODY}{\BODY}{\BODY}{\BODY}}
61 }

\CustomFBox {\langle toptitle\rangle} {\langle bottitle\rangle} {\langle thicknessstop\rangle} {\langle bottom\rangle} {\langle left\rangle} {\langle right\rangle} {\langle text contents\rangle}

62 \renewcommand{\CustomFBox}[7]{%
63 \convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
64 \LWR@forcenewpage
65 \begin{BlockClass}[border: 3px solid \LWR@origpound\LWR@tempcolor]{framed}%
66 \ifthenelse{\isempty{#1}}{}{%
67   \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
68     \textcolor{TFTTitleColor}{\textbf{#1}}%
69   \end{BlockClass}%
70 }% not empty
71
72 #7
73
74 \ifthenelse{\isempty{#2}}{}{%
75   \convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
76   \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
77     \textcolor{TFTTitleColor}{\textbf{#2}}%
78   \end{BlockClass}%
79 }% not empty
80 \end{BlockClass}
```

```

81 }

\TitleBarFrame [⟨marker⟩] {⟨title⟩} {⟨contents⟩}

82 \renewcommand\TitleBarFrame[3] []{
83 \CustomFBox
84   {#2}{#3}%
85   \fboxrule\fboxrule\fboxrule\fboxrule
86   {#3}%
87 }

88 \renewcommand{\TF@Title}[1]{#1}

MakeFramed {⟨settings⟩}

89 \let\MakeFramed\relax
90 \let\endMakeFramed\relax
91
92 \NewEnviron{MakeFramed}[1]{%
93 \FrameCommand{\begin{minipage}{\linewidth}\BODY\end{minipage}}%
94 }

\fb@put@frame {⟨frame cmd no split⟩} {⟨frame cmd split⟩}

95 \renewcommand*\fb@put@frame[2]{%
96 \relax%
97 \@tempboxa%
98 }

```

File 132 **lwarf-ftnright.sty**

§ 225 Package **ftnright**

Pkg **ftnright** **ftnright** is ignored.

for HTML output: Discard all options for **lwarf-ftnright**:

```
1 \LWR@ProvidesPackageDrop{ftnright}
```

File 133 **lwarf-fullminipage.sty**

§ 226 Package **fullminipage**

Pkg **fullminipage** **fullminipage** is nullified.

for HTML output: 1 \LWR@ProvidesPackageDrop{fullminipage}[2014/07/06]

2 \newenvironment{fullminipage}[1] [] {}{}

File 134 **l warp-fullpage.sty**

§ 227 Package **fullpage**

Pkg **fullpage** **fullpage** is ignored.

for HTML output: Discard all options for **l warp-fullpage**:

1 \LWR@ProvidesPackageDrop{fullpage}[1994/06/01]

File 135 **l warp-fullwidth.sty**

§ 228 Package **fullwidth**

(Emulates or patches code by MARCO DANIEL.)

Pkg **fullwidth** **fullwidth** is emulated.

A minipage is used, of no HTML width.

for HTML output: 1 \LWR@ProvidesPackageDrop{fullwidth}

2 \newenvironment*{fullwidth}[1] [] {}%
3 \minipagefullwidth%
4 \minipage{\ linewidth}%
5 }%
6 {}%
7 \endminipage%
8 }

File 136 **l warp-fwlw.sty**

§ 229 Package **f wl w**

Pkg **f wl w** **f wl w** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{f wl w}

```

2 \newbox\FirstWordBox      \global\setbox\FirstWordBox\hbox{ }
3 \newbox\NextWordBox       \global\setbox\NextWordBox\hbox{ }
4 \newbox\LastWordBox        \global\setbox\LastWordBox\hbox{ }
5 \def\ps@fwlhead{ }
6 \def\ps@NextWordFoot{ }

```

File 137 **l warp-geometry.sty**§ 230 Package **geometry***(Emulates or patches code by HIDEO UMEKI.)*

Pkg **geometry** **geometry** is preloaded by **l warp**, but must be nullified as seen by the user's source code.

for HTML output: Discard all options for **l warp-geometry**:

```

1 \LWR@ProvidesPackageDrop{geometry}

2 \renewcommand*\{`geometry}[1]{}
3 \renewcommand*\{`newgeometry}[1]{}
4 \renewcommand*\{`restoregeometry}{}
5 \renewcommand*\{`savegeometry}[1]{}
6 \renewcommand*\{`loadgeometry}[1]{}

```

File 138 **l warp-glossaries.sty**§ 231 Package **glossaries***(Emulates or patches code by NICOLA L.C. TALBOT.)*

Pkg **glossaries** **processing glossaries** **l warpmk** has the commands **l warpmk printglossary** and **l warpmk htmlglossary**, which process the glossaries created by the **glossaries** package using that package's **makerglossaries** command.

Opt **GlossaryCmd** Default: **makerglossaries** The shell command to execute is set by the **l warp** option **GlossaryCmd**, which defaults to **makerglossaries**. The print or HTML glossary filename is appended to this command.

⚠ makeglossaries not found In some situations it may be required to modify the default command, such as to add the **perl** command in front:

```
\usepackage[
    GlossaryCmd={perl makerglossaries},
] {l warp}
```

xindy language To set the language to use for processing glossaries with `xindy`:

```
\usepackage[
    GlossaryCmd={makeglossaries -L english},
] {lwarf}
```

Other options for `makeglossaries` may be set as well.

placement and toc options The glossaries may be placed in a numbered or unnumbered section, given a toc entry, and placed inline or on their own HTML page:

Numbered section, on its own HTML page:

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
...
\printglossaries
```

Unnumbered section, inline with the current HTML page:

```
\usepackage[xindy,toc]{glossaries}
...
\printglossaries
```

Unnumbered section, on its own HTML page:

```
\usepackage[xindy,toc]{glossaries}
...
\ForceHTMLPage
\printglossaries
```

⚠ **glossary style** The default `style=item` option for `glossaries` conflicts with `lwarf`, so the style is forced to `index` instead.

⚠ **number list** The page number list in the printed form would become `\nameref`s in HTML, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

print/HTML versions The print and HTML versions of the glossary differ in their internal page numbers. Separate commands for generating print and HTML glossaries are used, even though the page number is currently ignored.

for HTML output:

```
1 \PassOptionsToPackage{xindy}{glossaries}
2 \LWR@ProvidesPackagePass{glossaries}
3 \setupglossaries{nonumberlist}
4 \setglossarystyle{index}
```

Patched to fix toc pointing to the previous page:

```
5 \renewcommand*{\@p@glossarysection}[2]{%
6   \glsclearpage
```

```

7   \phantomsection
8   \ifdefempty\@@glossarysecstar
9   {%
10    \csname\@@glossarysec\endcsname{#2}%
11  }%
12  {%

```

In the original, the TOC entry was made before the section, thus linking to the phantomsection in the printed version, but for HTML, this caused the link to point to the page before the glossaries, which could be a different HTML file. Here, the TOC entry is made after the section is created:

```

13      \csname\@@glossarysec\endcsname*{#2}%
14      \@gls@toc{#1}{\@@glossarysec}% Moved after the previous line.
15  }%
16  \@@glossaryseclabel
17 }

```

lwarf's sectioning commands cannot handle robust macros when splitting HTML into named filenames. **glossaries** uses `\translate` in sectioning names, and `\translate` is robust and cannot be expanded. The following pre-expands the translations at this moment, making use of `\translatelet`.

```

18 \newcommand*{\LWR@comp@glossaryname}{\translate{Glossary}}
19
20 \ifdefstrequal{\glossaryname}{\LWR@comp@glossaryname}{
21   \translatelet{\LWR@translatetemp}{Glossary}
22   \edef\glossaryname{\LWR@translatetemp}
23 }{%
24
25 \newcommand*{\LWR@comp@acronymname}{\translate{Acronym}}
26
27 \ifdefstrequal{\acronymname}{\LWR@comp@acronymname}{
28   \translatelet{\LWR@translatetemp}{Acronym}
29   \edef\acronymname{\LWR@translatetemp}
30 }{%
31
32 \newcommand*{\LWR@comp@glssymbolsgroupname}{\translate{Symbols (glossaries)}}
33
34 \ifdefstrequal{\glssymbolsgroupname}{\LWR@comp@glssymbolsgroupname}{
35   \translatelet{\LWR@translatetemp}{Symbols (glossaries)}
36   \edef\glssymbolsgroupname{\LWR@translatetemp}
37 }{%
38
39 \newcommand*{\LWR@comp@glsnumbersgroupname}{\translate{Numbers (glossaries)}}
40
41 \ifdefstrequal{\glsnumbersgroupname}{\LWR@comp@glsnumbersgroupname}{
42   \translatelet{\LWR@translatetemp}{Numbers (glossaries)}
43   \edef\glsnumbersgroupname{\LWR@translatetemp}

```

```
44 }{}
```

File 139 **l warp-glossary.sty**

§ 232 Package **glossary**

Pkg **glossary** **glossary** is superceded by **glossaries**.

for HTML output: 1 \LWR@loadnever{glossary}{glossaries}

File 140 **l warp-graphics.sty**

§ 233 Package **graphics**

(Emulates or patches code by D. P. CARLISLE.)

Pkg **graphics** **graphics** is emulated.

for HTML output: 1 \LWR@ProvidesPackagePass{graphics}

§ 233.1 **Graphics extensions**

\DeclareGraphicsExtensions {⟨list⟩}

\AtBeginDocument allow SVG files instead of PDF:

```
2 \AtBeginDocument{
3 \DeclareGraphicsExtensions{.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}
4 \DeclareGraphicsRule{.svg}{svg}{.svg}{}
5 \DeclareGraphicsRule{.SVG}{svg}{.SVG}{}
6 }
```

Inside a *lateximage*, allow PDF instead of SVG:

```
7 \ifpdf
8 \appto{\LWR@restoreorigformatting}{%
9 \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
10 }
11 \else% \ifpdf
12 \ifXeTeX
13 \appto{\LWR@restoreorigformatting}{%
14 \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
15 }
16 \else
```

```

17 \appto\LWR@restoreorigformatting{%
18 \DeclareGraphicsExtensions{.eps,.EPS,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
19 }%
20         \fi
21 \fi

```

§ 233.2 Length conversions and graphics options

 **whitespace** A scaled image in L^AT_EX by default takes only as much space on the page as it requires, but HTML browsers use as much space as the original unscaled image would have taken, with the scaled image over- or under-flowing the area.

Used to store the user's selected dimensions and HTML class.

The class defaults to "inlineimage" unless changed by a `class=xyz` option.

```

22 \newlength{\LWR@igwidth}
23 \newlength{\LWR@igheight}
24 \newcommand*{\LWR@igwidthstyle}{}%
25 \newcommand*{\LWR@igheightstyle}{}%
26 \newcommand*{\LWR@igorigin}{}%
27 \newcommand*{\LWR@igangle}{}%
28 \newcommand*{\LWR@igxscale}{1}%
29 \newcommand*{\LWR@igyscale}{1}%
30 \newcommand*{\LWR@igclass}{inlineimage}

```

Set the actions of each of the key/value combinations for `\includegraphics`. Many are ignored.

If an optional width was given, set an HTML style:

```

31 \define@key{igraph}{width}{%
32 \setlength{\LWR@igwidth}{#1}%
33 \ifthenelse{\lengthtest{\LWR@igwidth > 0pt}}{%
34 }%

```

Default to use the converted fixed length given:

```
35     \renewcommand*{\LWR@igwidthstyle}{width:\LWR@printlength{\LWR@igwidth}}%
```

If ex or em dimensions were given, use those instead:

```

36     \IfEndWith{#1}{ex}{%
37     {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes ex
38     {}% not ex
39     \IfEndWith{#1}{em}{%
40     {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes em
41     {}% not em

```

```

42  \IfEndWith{#1}{\%}{%
43  {\renewcommand*\LWR@igwidthstyle{width:#1}}% yes percent
44  {}% not percent
45  \IfEndWith{#1}{px}{%
46  {\renewcommand*\LWR@igwidthstyle{width:#1}}% yes px
47  {}% not px
48 }{}% end of length > Opt
49 }

```

If an optional height was given, set an HTML style:

```

50 \define@key{igraph}{height}{%
51 \setlength{\LWR@igheight}{#1}%
52 \ifthenelse{\lengthtest{\LWR@igheight > 0pt}}{%
53 {}

```

Default to use the converted fixed length given:

```

54 \renewcommand*\LWR@igheightstyle{%
55   height:\LWR@printlength{\LWR@igheight} % extra space
56 }

```

If ex or em dimensions were given, use those instead:

```

57 \IfEndWith{#1}{ex}{%
58 {\renewcommand*\LWR@igheightstyle{height:#1}}% yes ex
59 {}% not ex
60 \IfEndWith{#1}{em}{%
61 {\renewcommand*\LWR@igheightstyle{height:#1}}% yes em
62 {}% not em
63 \IfEndWith{#1}{\%}{%
64 {\renewcommand*\LWR@igheightstyle{height:#1}}% yes percent
65 {}% not percent
66 \IfEndWith{#1}{px}{%
67 {\renewcommand*\LWR@igheightstyle{height:#1}}% yes px
68 {}% not px
69 }{}% end of length > Opt
70 }

```

Handle origin key:

```

71 \define@key{igraph}{origin}[c]{%
72   \renewcommand*\LWR@igorigin{#1}%
73 }

```

Handle angle key:

```

74 \define@key{igraph}{angle}{\renewcommand*\LWR@igangle{#1}}

```

Handle class key:

```
75 \define@key{igraph}{class}{\renewcommand*\LWR@igclass{\#1}}
76
```

It appears that **graphicx** does not have separate keys for `xscale` and `yscale`. `scale` adjusts both at the same time.

```
77 \define@key{igraph}{scale}{%
78   \renewcommand*\LWR@igxscale{\#1}%
79   \renewcommand*\LWR@igyscale{\#1}%
80 }
```

Numerous ignored keys:

```
81 \define@key{igraph}{bb}={}
82 \define@key{igraph}{bbllx}={}
83 \define@key{igraph}{bbly}={}
84 \define@key{igraph}{bburx}={}
85 \define@key{igraph}{bbury}={}
86 \define@key{igraph}{natwidth}={}
87 \define@key{igraph}{natheight}={}
88 \define@key{igraph}{hiresbb}[true] {}
89 \define@key{igraph}{viewport}={}
90 \define@key{igraph}{trim}={}
91 \define@key{igraph}{totalheight}={}
92 \define@key{igraph}{keepaspectratio}[true] {}
93 \define@key{igraph}{clip}[true] {}
94 \define@key{igraph}{draft}[true] {}
95 \define@key{igraph}{type}={}
96 \define@key{igraph}{ext}={}
97 \define@key{igraph}{read}={}
98 \define@key{igraph}{command}={}
```

New in v1.1a:

```
99 \define@key{igraph}{quite}={}
100 \define@key{igraph}{page}={}
101 \define@key{igraph}{pagebox}={}
102 \define@key{igraph}{interpolate}[true] {}
```

New in v1.1b:

```
103 \define@key{igraph}{decodearray}={}
```

§ 233.3 Printing HTML styles

\LWR@rotstyle {⟨prefix⟩} {⟨degrees⟩}

Prints the rotate style with the given prefix.

prefix is -ms- or -webkit- or nothing, and is used to generate three versions of the transform:rotate style.

```
104 \newcommand*{\LWR@rotstyle}[2]{%
105   #1transform:rotate(-#2deg);%
106 }
```

\LWR@scaletype {⟨prefix⟩} {⟨xscale⟩} {⟨yscale⟩}

Prints the scale style with the given prefix.

prefix is -ms- or -webkit- or nothing, and is used to generate three versions of the transform:scale style.

```
107 \newcommand*{\LWR@scaletype}[3]{%
108   #1transform:scale(#2,#3);%
109 }
```

§ 233.4 \includegraphics

Bool LWR@infloatrow Used to compute \linewidth.

```
110 \newbool{\LWR@infloatrow}%
111 \boolefalse{\LWR@infloatrow}
```

\LWR@opacity For HTML, used only for \includegraphics.

\LWR@opacity may be set by the **transparent** package.

```
112 \def\LWR@opacity{1}
```

\LWR@imagesizebox Used to determine the actual image size if needed.

```
113 \newsavebox{\LWR@imagesizebox}
```

\LWR@HTML@Gin@setfile {⟨w⟩} {⟨h⟩} {⟨filename⟩} Sets the parsed filename for HTMLoutput.

```
114 \newcommand*{\LWR@HTML@Gin@setfile}[3]{%
115   \xdef\LWR@parsedfilename{\#3}%
116 }
```

Key `Gin` class CSS class for the image.

Define the new class key for the print-mode version of `\includegraphics`, which is enabled inside a `latextimage`.

```
117 \AtBeginDocument{  
118 \define@key{Gin}{class}{}  
119 }
```

`\LWR@replaceEPSSVG` Usually, references to `EPS` files become `SVG` files, but if the `epstopdf` package is being used, it automatically converts `EPS` to `PDF`, and the following must NOT be done.

```
120 \AtBeginDocument{  
121 \@ifpackageloaded{epstopdf}  
122 {  
123     \newcommand*{\LWR@replaceEPSSVG}{}  
124 }{  
125     \newcommand*{\LWR@replaceEPSSVG}{%  
126         \StrSubstitute{\LWR@tempone}{.eps}{.svg}[\LWR@tempone]  
127         \StrSubstitute{\LWR@tempone}{.EPS}{.SVG}[\LWR@tempone]  
128     }%  
129 }%  
130 }
```

`\LWR@includegraphicsb` * [`<2: options>`] [`<3: options>`] {[`<4: filename>`}]

`graphics` syntax is `\includegraphics * [<llx, lly>] [<urx, ury>] {[<file>]}`

`graphicx` syntax is `\includegraphics [<key values>] {[<file>]}`

If #3 is empty, only one optional argument was given, thus `graphicx` syntax.

If using `\epsfig` or `\psfig` from the `epsfig` package, #4 will be `\LWR@epsfig@filename`, which will have been set by the `file` or `figure` keys. Therefore, #4 must not be used until after the keys have been processed.

```
131 \NewDocumentCommand{\LWR@includegraphicsb}{s o o m}{  
132 }%
```

Start the image tag on a new line, allow PDF output word wrap:

```
133 \LWR@origtilde \LWR@orignewline%
```

Temporarily compute `\ linewidth`, `\ textwidth`, `\ textheight` arguments with a 6x9 inch size until the next `\endgroup`.

```
134 \begingroup%
```

```

135 \ifthenelse{\cnttest{\value{LWR@minipagedepth}}{=}{0}}%
136 {%
137   \ifbool{LWR@infloatrow}%
138   {}%
139   {%
140     \setlength{\linewidth}{6in}%
141     \setlength{\textwidth}{6in}%
142     \setlength{\textheight}{9in}%
143   }%
144 }{}%

```

For correct em sizing during the width and height conversions:

```
145 \large%
```

Reset some defaults, possibly will be changed below if options were given:

```

146 \setlength{\LWR@igwidth}{Opt}%
147 \setlength{\LWR@igheight}{Opt}%
148 \renewcommand*{\LWR@igwidthstyle}{}%
149 \renewcommand*{\LWR@igheightstyle}{}%
150 \renewcommand*{\LWR@igorigin}{}%
151 \renewcommand*{\LWR@igangle}{}%
152 \renewcommand*{\LWR@igxscale}{1}%
153 \renewcommand*{\LWR@igyscale}{1}%
154 \renewcommand*{\LWR@igclass}{inlineimage}%

```

If #3 is empty, only one optional argument was given, thus **graphicx** syntax:

```

155 \IfValueF{#3}{%
156   \IfValueTF{#2}{%
157     {\setkeys{igraph}{#2}}%
158     {\setkeys{igraph}{}}
159 }%

```

Fully expand and detokenize the filename, changing the file extension to .svg if necessary.

```

160 \begingroup%
161 \LetLtxMacro\Gin@setfile{\LWR@HTML@Gin@setfile}%
162 \edef\LWR@tempone{#4}%
163 \StrSubstitute{\LWR@tempone}{.pdf}{.svg}[\LWR@tempone]%
164 \StrSubstitute{\LWR@tempone}{.PDF}{.SVG}[\LWR@tempone]%
165 \LWR@replaceEPSSVG%
166 \xdef\LWR@parsedfilename{\LWR@tempone}%
167 \Ginclusion@graphics{\detokenize\expandafter{\LWR@tempone}}%
168 \endgroup%
169 \filename@parse{\LWR@parsedfilename}%
170 \LWR@traceinfo{\LWR@parsedfilename is \LWR@parsedfilename}%

```

```
171 % \LWR@sanitize{\LWR@parsedfilename}%
```

If formatting for a word processor, find and set the actual image size, without rotation, using PDF instead of SVG to find the original bounding box:

```
172 \ifbool{FormatWP}{%
173   \begingroup%
174   \ifpdf
175     \appto{\LWR@restoreorigformatting}{%
176       \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
177     }
178   \else% \ifpdf
179     \ifXeTeX
180       \appto{\LWR@restoreorigformatting}{%
181         \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
182       }
183     \else
184       \appto{\LWR@restoreorigformatting}{%
185         \DeclareGraphicsExtensions{.eps,.EPS,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
186       }
187     \fi
188   \fi
189   \define@key{Gin}[angle]{}
190   \IfBooleanTF{#1}{%
191     %% starred
192     \IfValueTF{#3}{%
193       {%
194         \global\sbox{\LWR@imagesizebox}{\LWR@originincludegraphics*[#2][#3][#4]}%
195       }%
196       {%
197         \IfValueTF{#2}{%
198           {%
199             \global\sbox{\LWR@imagesizebox}{\LWR@originincludegraphics*[#2][#4]}%
200           }{%
201             \global\sbox{\LWR@imagesizebox}{\LWR@originincludegraphics*[#4]}%
202           }%
203         }%
204       }%
205     }%
206     %% not starred
207     \IfValueTF{#3}{%
208       \global\sbox{\LWR@imagesizebox}{\LWR@originincludegraphics[#2][#3][#4]}%
209     }%
210     {%
211       \IfValueTF{#2}{%
212         {%
213           \global\sbox{\LWR@imagesizebox}{\LWR@originincludegraphics[#2][#4]}%
214         }{%
215           \global\sbox{\LWR@imagesizebox}{\LWR@originincludegraphics[#4]}%
216         }%
217       }%
218     }%
219   }%
220 }
```

```

216      }%
217      }%
218      }% not starred
219      \endgroup%
220      \settowidth{\LWR@igwidth}{\usebox{\LWR@imagesizebox}}%
221      \global\renewcommand*{\LWR@igwidthstyle}{width:\LWR@printlength{\LWR@igwidth}}%
222      \settoheight{\LWR@igheight}{\usebox{\LWR@imagesizebox}}%
223      \global\renewcommand*{\LWR@igheightstyle}{height:\LWR@printlength{\LWR@igheight}}%
224 }{ }%

```

Create the HTML reference with the graphicspath, filename, extension, alt tag, style, and class.

The \LWR@origtilde adds space between tags in case this is being done inside a \savebox where \newline has no effect.

```

225 \LWR@traceinfo{\LWR@includegraphicsb: about to create href}%
226 \href{\LWR@parsedfilename}%
227 { % start of href
228 \LWR@traceinfo{\LWR@includegraphicsb: about to \LWR@htmntag}%
229 \LWR@htmntag{ % start of image tags
230 img src=" %
231 \begin{group}\@sanitize\LWR@parsedfilename\endgroup%
232 " \LWR@orignewline%

```

Only include a style tag if a width, height, angle, or scale was given:

```

233 \ifthenelse{
234     \NOT\equal{\LWR@igwidthstyle}{} \OR
235     \NOT\equal{\LWR@igheightstyle}{} \OR
236     \NOT\equal{\LWR@igorigin}{} \OR
237     \NOT\equal{\LWR@igangle}{} \OR
238     \NOT\equal{\LWR@igxscale}{1} \OR
239     \NOT\equal{\LWR@igyscale}{1}
240 }%
241 {\LWR@origtilde{} style=" %
242 \ifthenelse{\NOT\equal{\LWR@igwidthstyle}{} }{ %
243 {\LWR@igwidthstyle;}{} }{ %
244 \ifthenelse{\NOT\equal{\LWR@igheightstyle}{} }{ %
245 {\LWR@igheightstyle;}{} }{ %
246 \ifthenelse{\NOT\equal{\LWR@igorigin}{} }{ %
247 {\LWR@origtilde{} transform-origin: \LWR@originnames{\LWR@igorigin}; \LWR@orignewline}{} }{ %
248 \ifthenelse{\NOT\equal{\LWR@igangle}{} }{ %
249 { %
250 \LWR@rotstyle{-ms-}{\LWR@igangle} % extra space
251 \LWR@rotstyle{-webkit-}{\LWR@igangle} % extra space
252 \LWR@rotstyle{}{\LWR@igangle} %
253 }{} }{ %
254 \ifthenelse{\NOT\equal{\LWR@igxscale}{1}\OR%
```

```

255 \NOT\equal{\LWR@igyscale}{1}%
256 {\LWR@scalestyle{-ms-}{\LWR@igxscale}{\LWR@igyscale} % extra space
257 \LWR@scalestyle{-webkit-}{\LWR@igxscale}{\LWR@igyscale} % extra space
258 \LWR@scalestyle{}{\LWR@igxscale}{\LWR@igyscale}{} % extra space
259 %
260 \ifthenelse{\NOT\equal{\LWR@opacity}{1}}%
261 {opacity:\LWR@opacity; }%
262 {}%
263 %
264 " \LWR@orignewline}{}%

```

Set the class:

```

265 \LWR@origtilde{} class="\LWR@igclass" \LWR@orignewline%
266 }% end of image tags
267 }% end of href

```

Return to original page size and font size:

```

268 \endgroup
269 \LWR@traceinfo{LWR@includegraphicsb done}%
270 }

```

\includegraphics [⟨key=val⟩] {⟨filename⟩}

Handles width and height, converted to fixed width and heights.

The user should always use no file suffix in the document source.

```

271 \AtBeginDocument{
272
273 \LWR@traceinfo{Patching includegraphics.}
274
275 \LetLtxMacro{\LWR@origincludegraphics}{\includegraphics}
276
277 \renewcommand*{\includegraphics}{%
278 }

```

This graphic should trigger an HTML paragraph even if alone, so ensure that are doing paragraph handling:

```

279 \LWR@traceinfo{includegraphics}%
280 \LWR@ensuredoingapar%
281 \LWR@includegraphicsb%
282 }% includegraphics
283 }% AtBeginDocument

```

§ 233.5 Boxes

\LWR@rotboxorigin Holds the origin key letters.

```
284 \newcommand*{\LWR@rotboxorigin}{}%
```

\LWR@originname {⟨letter⟩}

Given one \TeX origin key value, translate into an HTML origin word:

```
285 \newcommand*{\LWR@originname}[1]{%
286 \ifthenelse{\equal{#1}{t}}{top}{%
287 \ifthenelse{\equal{#1}{b}}{bottom}{%
288 \ifthenelse{\equal{#1}{c}}{center}{%
289 \ifthenelse{\equal{#1}{l}}{left}{%
290 \ifthenelse{\equal{#1}{r}}{right}{%
291 }}
```

\LWR@originnames {⟨letters⟩}

Given one- or two-letter \TeX origin key values, translate into HTML origin words:

```
292 \newcommand*{\LWR@originnames}[1]{%
293 \StrChar{#1}{1}[\LWR@strresult]%
294 \LWR@originname{\LWR@strresult}%
295 \StrChar{#1}{2}[\LWR@strresult]%
296 \LWR@originname{\LWR@strresult}%
297 }
```

Handle the origin key for \rotatebox:

```
298 \define@key{krotbox}{origin}{%
299 \renewcommand*{\LWR@rotboxorigin}{#1}%
300 }
```

These keys are ignored:

```
301 \define@key{krotbox}{x}{}
302 \define@key{krotbox}{y}{}
303 \define@key{krotbox}{units}{}
```

\rotatebox [⟨keyval list⟩] {⟨angle⟩} {⟨text⟩}

```
304 \AtBeginDocument{
```

The HTML version:

```
305 \NewDocumentCommand{\LWR@HTML@rotatebox}{O{} m +m}{%
```

Reset the origin to “none-given”:

```
306 \renewcommand*{\LWR@rotboxorigin}{}%
```

Process the optional keys, which may set \LWR@rotateboxorigin:

```
307 \setkeys{krotbox}{#1}%
```

Select inline-block so that HTML will transform this span:

```
308 \LWR@htmllagc{span style="display: inline-block; %
```

If an origin was given, translate and print the origin information:

```
309 \ifthenelse{\NOT\equal{\LWR@rotboxorigin}{}}%  
310 {transform-origin: \LWR@originnames{\LWR@rotboxorigin};\LWR@origtilde}{}%
```

Print the rotation information:

```
311 \LWR@rotstyle{-ms-}{#2} % extra space  
312 \LWR@rotstyle{-webkit-}{#2} % extra space  
313 \LWR@rotstyle{}{#2} % extra space  
314 "}\LWR@orignewline%
```

Print the text to be rotated:

```
315 \begin{LWR@nestspan} %  
316 #3%
```

Close the span:

```
317 \LWR@htmllagc{/span} %  
318 \end{LWR@nestspan} %  
319 }
```

The high-level interface:

```
320 \LWR@formatted[rotatebox]  
321  
322 }% AtBeginDocument
```

```
\scalebox {<h-scale>} [<v-scale>] {<text>}
```

```
323 \AtBeginDocument{
```

The HTML version:

```
324 \NewDocumentCommand{\LWR@HTML@scalebox}{m o m}{%
```

Select inline-block so that HTML will transform this span:

```
325 \LWR@htmltagc{span style="display: inline-block; %
```

Print the scaling information:

```
326 \LWR@scalestyle{-ms-}{#1}{\IfNoValueTF{#2}{#1}{#2}} % extra space  
327 \LWR@scalestyle{-webkit-}{#1}{\IfNoValueTF{#2}{#1}{#2}} % extra space  
328 \LWR@scalestyle{}{#1}{\IfNoValueTF{#2}{#1}{#2}} % extra space  
329 "}%
```

Print the text to be scaled:

```
330 \begin{LWR@nestspan} %  
331 #3%
```

Close the span:

```
332 \LWR@htmltagc{/span} %  
333 \end{LWR@nestspan} %  
334 }
```

The high-level interface:

```
335 \LWR@formatted{scalebox}  
336  
337 }% AtBeginDocument  
  
\reflectbox {<text>}  
  
338 \AtBeginDocument{  
339  
340 \newcommand{\LWR@HTML@reflectbox}[1]{%  
341 \scalebox{-1}[1]{#1}%  
342 }% \reflectbox  
343  
344 \LWR@formatted{reflectbox}  
345  
346 }% AtBeginDocument
```

```
\resizebox {<h-length>} {<v-length>} {<text>}
```

Simply prints its text argument.

```
347 \AtBeginDocument{  
348  
349 \NewDocumentCommand{\LWR@HTML@resizebox}{s m m m}{%  
350 #4%  
351 }  
352  
353 \LWR@formatted[resizebox]  
354  
355 }% AtBeginDocument
```

File 141 **l warp-graphicx.sty**

§ 234 Package **graphicx**

Pkg **graphicx** **graphicx** is emulated.

graphicx loads **graphics**, which also loads **l warp-graphics**, which remembers the original graphics definitions for use inside a `lateximage`, and then patches them `\AtBeginDocument` for HTML output.

l warp-graphics handles the syntax of either **graphics** or **graphicx**.

for HTML output: 1 \LWR@ProvidesPackagePass{graphicx}[2017/06/01]

File 142 **l warp-grffile.sty**

§ 235 Package **grffile**

Pkg grffile **grffile** is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

l warp-grffile now exists as a placeholder since **grffile** used to be emulated by **l warp**, and thus older versions of **l warp-grffile** may exist and should be overwritten by this newer version.

for HTML output: 1 \LWR@ProvidesPackagePass{grffile}

File 143 **l warp-grid.sty**

§ 236 Package **grid**

Pkg **grid** **grid** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{grid}

2 \newenvironment*{gridenv}{}{}

File 144 **l warp-grid-system.sty**

§ 237 Package **grid-system**

(Emulates or patches code by MARCUS BITZL.)

Pkg **grid-system** **grid-system** is patched for use by **l warp**.

for HTML output: 1 \LWR@ProvidesPackagePass{grid-system}[2014/02/16]

(\ifdef is in case the older syntax is removed.)

2 \AtBeginEnvironment{Row}{\setlength{\ linewidth}{6in}}
3
4 \ifdef{\endrow}{
5 \AtBeginEnvironment{row}{\setlength{\ linewidth}{6in}}
6 }{}
7
8 \renewcommand{\gridsystem@finishcell}{\hspace{\gridsystem@cellsep}}

File 145 **l warp-gridset.sty**

§ 238 Package **gridset**

Pkg **gridset** **gridset** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{gridset}

```

2 \newcommand*{\gridbase}{}
3 \newcommand*{\gridinterval}{}
4 \newcommand*{\savepos}[1]{}
5 \newcounter{gridcnt}
6 \newcommand*{\vskipnextgrid}{}
7 \newcommand*{\thegridinfo}[1]{}
8 \newcommand*{\theinfo}[1]{}
9 \newcommand*{\theypos}[1]{}

```

File 146 **l warp-hang.sty**

§ 239 Package **hang**

(Emulates or patches code by ANDREAS NOLDA.)

Pkg **hang** **hang** is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{hang}

2 \newlength{\hangingindent}
3 \setlength{\hangingindent}{1em}
4 \newlength{\hangingleftmargin}
5 \setlength{\hangingleftmargin}{0em}
6
7 \newcommand*{\LWR@findhangingleftmargin}{%
8   \setlength{\LWR@templengthone}{\hangingleftmargin}%
9   \addtolength{\LWR@templengthone}{\hangingindent}%
10 }

11
12 \newenvironment{hangingpar}
13 {
14   \LWR@findhangingleftmargin%
15   \BlockClass[% 
16     \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
17     \LWR@print@mbox{text-indent:-\LWR@printlength{\hangingindent}}%
18   ]%
19   {hangingpar}%
20 }
21 {\endBlockClass}
22
23 \newenvironment{hanginglist}
24 {%
25   \renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}%
26   \renewcommand*{\LWR@printopenlist}{%
27     \LWR@findhangingleftmargin%
28     ul style=%
29       \LWR@print@mbox{list-style-type:none;} % extra space

```

```

30          \LWR@print@mbox{%
31              margin-left:\LWR@printlength{\LWR@templengthone}%
32          } ; % extra space
33          \LWR@print@mbox{%
34              text-indent:-\LWR@printlength{\hangingindent}%
35          }%
36          "%
37      }%
38      \let\item\LWR@itemizeitem%
39      \list{}{%
40 }
41 {\endlist}
42
43 \newenvironment{compacthang}
44 {\hanginglist}
45 {\endhanginglist}
46
47 \newlength{\labeledleftmargin}
48 \setlength{\labeledleftmargin}{0em}
49
50 \newenvironment{labeledpar}[2]
51 {%
52     \BlockClass[%
53         \LWR@findhangingleftmargin%
54         \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
55         \LWR@print@mbox{text-indent:-\LWR@printlength{\hangingindent}}%
56     ]{labeledpar}#2%
57 }
58 {\endBlockClass}
59
60 \newenvironment{labeledlist}[1]
61 {\hanginglist}
62 {\endhanginglist}
63
64 \newenvironment{compactlabel}[1]
65 {\hanginglist}
66 {\endhanginglist}

```

File 147 l warp-hanging.sty

§ 240 Package **hanging**

Pkg **hanging** **hanging** is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{hanging}

2 \@ifclassloaded{memoir}{}
```

```

3 \let\hangpara\relax
4 \let\hangparas\relax
5 \let\endhangparas\relax
6 \let\hangpunct\relax
7 \let\endhangpunct\relax
8 }{}
```

\hangpara {*indent*} {*afternum*}
Use `hangparas` instead.

```

9 \newcommand*{\hangpara}[2]{}
```

Env `hangparas` {*indent*} {*afternum*}
10 \newenvironment*{hangparas}[2]
11 {%
12 \BlockClass[%
13 \LWR@print@mbox{margin-left:\LWR@printlength{#1}} ; %
14 \LWR@print@mbox{text-indent:-\LWR@printlength{#1}}%
15]%
16 {hangingpar}%
17 }
18 {\endBlockClass}

Env `hangpunct`
19 \newenvironment*{hangpunct}
20 {\BlockClass{hangpunct}}
21 {\endBlockClass}

22 \newcommand{\nhpt}{.}
23 \newcommand{\nhlq}{`}
24 \newcommand{\nhrq}{'}

File 148 `l warp-hypcap.sty`§ 241 Package **hypcap**Pkg `hypcap` **hypcap** is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{hypcap}

2 \newcommand*{\capstart}{}
3 \newcommand*{\hypcapspace}{}
4 \newcommand*{\hypcapedef}[1]{}
```

```
5 \newcommand*{\capstartfalse}{}  
6 \newcommand*{\capstartrue}{}  


---


```

File 149 **l warp-hypdestopt.sty**

§ 242 Package **hypdestopt**

Pkg hypdestopt **hypdestopt** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{hypdestopt}

File 150 **l warp-hypernat.sty**

§ 243 Package **hypernat**

Pkg hypernat **hypernat** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{hypernat}

File 151 **l warp-hyperref.sty**

§ 244 Package **hyperref**

(Emulates or patches code by SEBASTIAN RAHTZ, HEIKO OBERDIEK.)

Pkg hyperref **hyperref** is emulated.

for HTML output:
1 % \LWR@ProvidesPackageDrop{hyperref}
2 \typeout{Using the l warp html version of package 'hyperref', discarding options.}
3 \typeout{ Are not using ProvidesPackage, so that other packages}
4 \typeout{ do not attempt to patch l warp's version of 'hyperref'.}
5 % \ProvidesPackage{l warp-#1-#2}
6 \DeclareOption*{}
7 \ProcessOptions\relax

8 \newcommand*{\hypersetup}[1]{}
9 \newcommand*{\hyperbaseurl}[1]{}

\hyperimage {<URL>} {{alt text}}

Insert an image with alt text:

```

10 \NewDocumentCommand{\LWR@hyperimageb}{m +m}{%
11 \LWR@ensuredoingapar%
12 \def\LWR@templink{#1}%
13 @onelvel@sanitize\LWR@templink%
14 \LWR@htmltag{img src="\LWR@templink" alt="#2" class="hyperimage"}%
15 \LWR@ensuredoingapar%
16 \endgroup%
17 }%
18
19 \newrobustcmd*\hyperimage{%
20 \begingroup%
21 \catcode`\#=12%
22 \catcode`\%=12%
23 \catcode`\&=12%
24 \catcode`\~=12%
25 \catcode`\_=12%
26 \LWR@hyperimageb%
27 }%
28

```

\hyperdef {⟨1: category⟩} {⟨2: name⟩} {⟨3: text⟩}

Creates an HTML anchor to category.name with the given text.

```

29 \NewDocumentCommand{\LWR@hyperdefb}{m m +m}{%
30 \LWR@ensuredoingapar%
31 \LWR@sublabel{#1.#2}%
32 #3%
33 \endgroup%
34 }%
35
36 \newcommand*\hyperdef{%
37 \begingroup%
38 \catcode`\#=12%
39 \catcode`\%=12%
40 \catcode`\&=12%
41 \catcode`\~=12%
42 \catcode`\_=12%
43 \LWR@hyperdefb%
44 }%
45

```

\LWR@hyperrefb {⟨1: URL⟩} {⟨2: category⟩} {⟨3: name⟩} {⟨4: text⟩}

Creates an HTML link to URL#category.name with the given text.

```

46 \newcommand{\LWR@hyperreffinish}[1]{%
47 \begingroup%
48 \RenewDocumentCommand{\ref}{\ignorespaces}{\LWR@ref@ignorestar}%

```

```
49 #1%
50 \endgroup%
51 \LWR@htmltag{/a}%
52 }
53
54 \newcommand*\LWR@hyperrefbb[3]{%
55 \LWR@htmltag{%
56     a href="%"
57         \detokenize\expandafter{\#1}\LWR@hashmark%
58         \detokenize\expandafter{\#2}. \detokenize\expandafter{\#3}%
59     "%"
60 }%
61 \endgroup%
62 \LWR@hyperreffinish%
63 }
64
65 \newrobustcmd*\LWR@hyperrefb{%
66 \begingroup%
67 \catcode`\#=12%
68 \catcode`\%=12%
69 \catcode`\&=12%
70 \catcode`\~=12%
71 \catcode`\_=12%
72 \LWR@hyperrefbb%
73 }
```

\LWR@hyperrefc [⟨label⟩] {⟨text⟩}

Creates text as an HTML link to the L^AT_EX label.

```
74
75 \NewDocumentCommand{\LWR@hyperrefcb}{O{label}}{%
76 \LWR@startref{#1}%
77 \endgroup%
78 \LWR@hyperreffinish%
79 }
80
81 \newcommand*\LWR@hyperrefc{%
82 \begingroup%
83 \catcode`\#=12%
84 \catcode`\%=12%
85 \catcode`\&=12%
86 \catcode`\~=12%
87 \catcode`\_=12%
88 \LWR@hyperrefcb%
89 }
```

\hyperref {⟨1: URL⟩} {⟨2: category⟩} {⟨3: name⟩} {⟨4: text⟩} — or —

```
[⟨1: label⟩] {⟨2: text⟩}

90 \DeclareRobustCommand*{\hyperref}{%
91 \LWR@ensuredoingapar%
92 \ifnextchar[\LWR@hyperrefc\LWR@hyperrefb%
93 }
```

\hypertarget {⟨name⟩} {⟨text⟩}

Creates an anchor to name with the given text.

```
94 \NewDocumentCommand{\hypertargetb}{m +m}{%
95 \label{LWR-ht-#1}%
96 #2%
97 \endgroup%
98 }
99
100 \newcommand*{\hypertarget}{%
101 \begingroup%
102 \catcode`\#=12%
103 \catcode`\%=12%
104 \catcode`\&=12%
105 \catcode`\~=12%
106 \catcode`\_=12%
107 \LWR@hypertargetb%
108 }
```

\hyperlink {⟨name⟩} {⟨text⟩}

Creates a link to the anchor created by hypertarget, with the given link text.

Declared because also defined by **memoir**.

```
109 \DeclareDocumentCommand{\hyperlinkb}{m}{%
110 \LWR@hyperrefcb[LWR-ht-#1]%
111 }
112
113 \DeclareDocumentCommand{\hyperlink}{()}{%
114 \LWR@ensuredoingapar%
115 \begingroup%
116 \catcode`\#=12%
117 \catcode`\%=12%
118 \catcode`\&=12%
119 \catcode`\~=12%
120 \catcode`\_=12%
121 \LWR@hyperlinkb%
122 }
```

\autoref * {⟨label⟩}

For HTML, \cleveref is used instead.

```
123 \NewDocumentCommand{\autoref}{s m}{%
124 \IfBooleanTF{#1}{\ref{#2}}{\cref{#2}}%
125 }
```

\autopageref {⟨label⟩}

For HTML, \cleveref is used instead.

```
126 \NewDocumentCommand{\autopageref}{s m}{%
127 \IfBooleanTF{#1}{\cpageref{#2}}{\cref{#2}}%
128 }
```

\pdfstringdef {⟨macroname⟩} {⟨*T_EXstring*⟩}

```
129 \newcommand{\pdfstringdef}[2]{}
```

\pdfbookmark [⟨level⟩] {⟨text⟩} {⟨name⟩}

```
130 \newcommand{\pdfbookmark}[3][]{}
```

\currentpdfbookmark {⟨text⟩} {⟨name⟩}

```
131 \newcommand{\currentpdfbookmark}[2]{}
```

\subpdfbookmark {⟨text⟩} {⟨name⟩}

```
132 \newcommand{\subpdfbookmark}[2]{}
```

\belowpdfbookmark {⟨text⟩} {⟨name⟩}

```
133 \newcommand{\belowpdfbookmark}[2]{}
```

\texorpdfstring {⟨*T_EXstring*⟩} {⟨PDFstring⟩}

```
134 \newcommand{\texorpdfstring}[2]{\#1}
```

\hypercalcbp {⟨dimen⟩} From **hyperref**.

```
135 \def\hypercalcbp#1{%
136 \strip@pt\dimexpr 0.99626401\dimexpr(#1)\relax\relax
137 }%
```

\Acrobatmenu {⟨menuoption⟩} {⟨text⟩}

```
138 \newcommand{\Acrobatmenu}[2]{}
```

```
\TextField  [{parameters}]{label}  
139 \DeclareRobustCommand{\TextField}[2][]{}  
  
\CheckBox  [{parameters}]{label}  
140 \DeclareRobustCommand{\CheckBox}[2][]{}  
  
\ChoiceMenu [{parameters}]{label}{{choices}}  
141 \DeclareRobustCommand{\ChoiceMenu}[3][]{}  
  
\PushButton [{parameters}]{label}  
142 \DeclareRobustCommand{\PushButton}[2][]{}  
  
\Submit    [{parameters}]{label}  
143 \DeclareRobustCommand{\Submit}[2][]{}  
  
\Reset    [{parameters}]{label}  
144 \DeclareRobustCommand{\Reset}[2][]{}  
  
\Gauge    [{parameters}]{label}  
145 \DeclareRobustCommand{\Gauge}[2][]{}  
  
\LayoutTextField {label} {field}  
146 \newcommand*{\LayoutTextField}[2]{}  
  
\LayoutChoiceField {label} {field}  
147 \newcommand*{\LayoutChoiceField}[2]{}  
  
\LayoutCheckField {label} {field}  
148 \newcommand*{\LayoutCheckField}[2]{}  
  
\MakeRadioField {width} {height}  
149 \newcommand*{\MakeRadioField}[2]{}  

```

```
\MakeCheckField  {\langle width\rangle} {\langle height\rangle}
150 \newcommand*{\MakeCheckField}[2]{}

\MakeTextField   {\langle width\rangle} {\langle height\rangle}
151 \newcommand*{\MakeTextField}[2]{}

\MakeChoiceField {\langle width\rangle} {\langle height\rangle}
152 \newcommand*{\MakeChoiceField}[2]{}

\MakeFieldButton {\langle text\rangle}
153 \newcommand{\MakeFieldButton}[1]{}
```

File 152 **l warp-hyperxmp.sty**

§ 245 Package **hyperxmp**

Pkg **hyperxmp** Emulated.
for HTML output: Discard all options for **l warp-hyperxmp**:

```
1 \LWR@ProvidesPackageDrop{hyperxmp}
```

File 153 **l warp-hyphenat.sty**

§ 246 Package **hyphenat**

Pkg **hyphenat** **hyphenat** is emulated during **HTML output**, while the print-mode version is used inside a **lateximage**.

for HTML output:

```
1 \LWR@ProvidesPackagePass{hyphenat}

2 \LetLtxMacro{\LWRHYNAT@origtextnhtt}{\textnhtt}
3 \LetLtxMacro{\LWRHYNAT@orignhttfamily}{\nhttfamily}
4 \LetLtxMacro{\LWRHYNAT@orignohyphens}{\nohyphens}
5 \LetLtxMacro{\LWRHYNAT@origbshyp}{\bshyp}
6 \LetLtxMacro{\LWRHYNAT@origfshyp}{\fshyp}
7 \LetLtxMacro{\LWRHYNAT@origdothyp}{\dothyp}
8 \LetLtxMacro{\LWRHYNAT@origcolonhyp}{\colonhyp}
```

```

9 \LetLtxMacro{\LWRHYNAT@orighyp}{\hyp
10
11 \LetLtxMacro{\textnhtt}{\texttt}
12 \LetLtxMacro{\nhttfamily}{\ttfamily}
13
14 \renewcommand{\nohyphens}[1]{#1}
15 \renewrobustcmd{\bshyp}{%
16   \ifmmode\backslash\else\textbackslash\fi%
17 }
18 \renewrobustcmd{\fshyp}{/}
19 \renewrobustcmd{\dothyp}{.}
20 \renewrobustcmd{\colonhyp}{:}
21 \renewrobustcmd{\hyp}{-}
22
23 \appto{\LWR@restoreorigformatting}{%
24 \LetLtxMacro{\textnhtt}{\LWRHYNAT@origtextnhtt}
25 \LetLtxMacro{\nhttfamily}{\LWRHYNAT@orignhttfamily}%
26 \LetLtxMacro{\nohyphens}{\LWRHYNAT@orignohyphens}%
27 \LetLtxMacro{\bshyp}{\LWRHYNAT@origbshyp}%
28 \LetLtxMacro{\fshyp}{\LWRHYNAT@origfshyp}%
29 \LetLtxMacro{\dothyp}{\LWRHYNAT@origdothyp}%
30 \LetLtxMacro{\colonhyp}{\LWRHYNAT@origcolonhyp}%
31 \LetLtxMacro{\hyp}{\LWRHYNAT@orighyp}%
32 }
```

File 154 **l warp-idxlayout.sty**

§ 247 Package **idxlayout**

(Emulates or patches code by THOMAS TITZ.)

Pkg **idxlayout** Emulated.

for HTML output: Discard all options for **l warp-idxlayout**:

```

1 \LWR@ProvidesPackageDrop{idxlayout}

2 \newcommand{\LWR@indexprenote}{}
3
4 \preto{\printindex}{}
5
6 \LWR@orignewpage
7 \LWR@startpars
8
9 \LWR@indexprenote
10
11 }
```

```

12
13 \newcommand{\setindexprenote}[1]{\renewcommand{\LWR@indexprenote}{#1}}
14 \newcommand*{\noindexprenote}{\renewcommand{\LWR@indexprenote}{}}
15
16 \newcommand{\idxlayout}[1]{}
17 \newcommand*{\indexfont}{}
18 \newcommand*{\indexjustific}{}
19 \newcommand*{\indexsubsdelim}{}
20 \newcommand*{\indexstheadcase}{}

```

File 155 **l warp-ifoddpage.sty**

§ 248 Package **ifoddpage**

(Emulates or patches code by MARTIN SCHARRER.)

Pkg **ifoddpage** **ifoddpage** is emulated.

for HTML output: Discard all options for **l warp-ifoddpage**:

```

1 \LWR@ProvidesPackageDrop{ifoddpage}

2 \newif\ifoddpage
3
4 \newif\ifoddpageoroneside
5
6 \DeclareRobustCommand{\checkoddpage}{\oddpage@true\oddpageoroneside@true}
7
8 \def\oddpage@page{1}
9
10 \def\@ifoddpage{%
11     \expandafter\@firstoftwo
12 }
13
14 \def\@ifoddpageoroneside{%
15     \expandafter\@firstoftwo
16 }

```

File 156 **l warp-imakeidx.sty**

§ 249 Package **imakeidx**

(Emulates or patches code by ENRICO GREGORIO.)

Pkg **imakeidx** **imakeidx** is patched for use by **l warp**.

letter headings When using **makeindex**, to match the print and HTML output's display of index letter headings, specify the `lwarf.ist` style:

```
\makeindex[options={-s lwarf.ist}]
```

(For HTML the `lwarf.ist` style is used automatically, which displays letter headings. When using **xindy** the default style also displays letter headings.)

index setup See section 9.5.15 for how to setup **lwarfmk** to process the indexes with **imakeidx**, both with and without shell escape.

for HTML output: 1 \LWR@ProvidesPackagePass{imakeidx}

Use the new HTML suffix:

```
2 \catcode`\_=12%
3 \define@key{imki}{name}{\def\imki@name{\#1_html}}
4 \catcode`\_=8%
```

`\printindex` The HTML version of `\printindex`:

```
5 \catcode`\_=12%
6
7 \renewcommand*\printindex[1][\imki@jobname]{%
8 \LWR@orignewpage%
9 \LWR@startpars%
10 \ifstreq{\#1}{\imki@jobname}{%
11   \@ifundefined{\#1@idxfile}{%
12     \imki@error{\#1}%
13   }{%
14     \imki@putindex{\#1}%
15   }%
16 }{%
17   \@ifundefined{\#1_html@idxfile}{\imki@error{\#1_html}}{\imki@putindex{\#1_html}}%
18 }%
19 }
20
21 \catcode`\_=8%
```

`\@index` The HTML version of `\index`:

```
22 \catcode`\_=12%
23
24 \def\@index[#1]{%
25   \ifstreq{\#1}{\imki@jobname}{%
26     \@ifundefined{\#1@idxfile}{%
27       \imki@error{\#1}%
28     }{%
29       \PackageWarning{imakeidx}{Undefined index file '#1}}%
30   }{%
31     \imki@putindex{\#1}%
32   }%
33 }
```

```

30          \begingroup
31          \@sanitize
32          \imki@nowrindex%
33      }%
34      {%
35          \edef\@idxfile{\#1}%
36          \begingroup
37          \@sanitize
38          \@wrindex\@idxfile%
39      }%
40  }%
41  {%
42      \ifundefined{#1_html@\idxfile}%
43      {%
44          \PackageWarning{imakeidx}{Undefined index file ‘#1_html’}%
45          \begingroup
46          \@sanitize
47          \imki@nowrindex%
48      }%
49      {%
50          \edef\@idxfile{#1_html}%
51          \begingroup
52          \@sanitize
53          \@wrindex\@idxfile%
54      }%
55  }%
56}%
57
58\catcode`\_=8%

\item
\subitem
\subsubitem HTML versions of \item, etc.:
59\appto\theindex{%
60    \let\item\LWR@indexitem%
61    \let\subitem\LWR@indexsubitem%
62    \let\subsubitem\LWR@indexsubsubitem%
63}

\imki@wrindexentrysplit {\langle file\rangle} {\langle entry\rangle} {\langle page\rangle}
\imki@wrindexentryunique {\langle file\rangle} {\langle entry\rangle} {\langle page\rangle}

While writing index entries, adds an HTML label, and writes the label's index instead
of the page number:
64\renewcommand\imki@wrindexentrysplit[3]{%
65\addtocounter{LWR@autoindex}{1}%
66\def\@newlabel{\LWR@index-\arabic{LWR@autoindex}}%

```

```

67 \expandafter\protected@write\csname#1@idxfile\endcsname{}%
68   {\string\indexentry{#2}{\arabic{LWR@autoindex}}}%
69 }
70
71 \renewcommand\imki@wrindexentryunique[3]{%
72 \addtocounter{LWR@autoindex}{1}%
73 \LWR@new@label{\LWR@index-\arabic{LWR@autoindex}}%
74 \protected@write\@indexfile{}%
75   {\string\indexentry{#1}{#2}{\arabic{LWR@autoindex}}}%
76 }
77
78 \def\imki@wrindexsplit#1#2{%
79 \imki@wrindexentrysplit{#1}{#2}{\thepage}%
80 \endgroup\imki@showidxentry{#1}{#2}%
81 \esphack%
82 }
83
84 \def\imki@wrindexunique#1#2{%
85 \imki@wrindexentryunique{#1}{#2}{\thepage}%
86 \endgroup\imki@showidxentry{#1}{#2}%
87 \esphack%
88 }
89

```

\LWR@imki@setxdydefopts

Sets the **xindy** HTML options, ignoring the user's settings.

```

90 \newcommand*{\LWR@imki@setxdydefopts}{%
91   \edef\imki@options{ \space %
92     -M \space \LWR@xindyStyle\space %
93     -L \space \LWR@xindyLanguage\space %
94     -C \space \LWR@xindyCodepage\space %
95   }%
96 }

```

\LWR@imki@setdefopts {*user options*}

Sets the HTML options, added to the user's settings, depending on whether **makeindex** or **xindy** are used.

For **makeindex**, the user's choice is ignored, and only the **lwarf** version is used. (Only one style at a time is possible.)

For **xindy**, multiple modules may be specified, and the **lwarf** version is appended.

```

97 \newcommand*{\LWR@imki@setdefopts}[1]{%
98 \ifblank{#1}{%
99   \edef\imki@options{\space -s \space \LWR@makeindexStyle \space}%
100  \ifdefstring{\imki@progdefault}{xindy}{\LWR@imki@setxdydefopts}{}%
101  \ifdefstring{\imki@progdefault}{texindy}{\LWR@imki@setxdydefopts}{}%
}

```

```

102      \ifdefstring{\imki@progdefault}{true}{\xdef{\LWR@imki@setxdydefopts}{}}%
103  }{%
104      \edef{\imki@options}{\space #1 \space}%
105  }%
106 }

```

\imki@makeindex Use the new HTML options:

```

107 \xpatchcmd{\imki@makeindex}
108     {\let\imki@options\space}
109     {\LWR@imki@setdefopts{}}
110     {}
111     {\LWR@patcherror{imakeidx}{makeindex}}

```

Use the new HTML options.

```
112 \define@key{\imki}{options}{\LWR@imki@setdefopts{#1}}
```

\imki@resetdefaults Use the new HTML options:

```

113 \xpatchcmd{\imki@resetdefaults}
114     {\def\imki@options{}}
115     {\LWR@imki@setdefopts{}}
116     {}
117     {\LWR@patcherror{imakeidx}{resetdefaults}}

```

the index was already defined \AtBeginDocument by the **l warp** core, so it must be redefined here similarly, but patched for **imakeidx**:

Env theindex

```

118 \AtBeginDocument{
119 \renewenvironment*{theindex}{%
120     \imki@maybeaddtotoc
121     \imki@indexlevel{\indexname}
122     \let\item\LWR@indexitem%
123     \let\subitem\LWR@indexsubitem%
124     \let\subsubitem\LWR@indexsubsubitem%
125 }{%
126 }% AtBeginDocument

```

Update to the new defaults:

```
127 \imki@resetdefaults
```

Update to the new patches:

\AtBeginDocument is because \wrindex is previously defined as \AtBeginDocument in the **l warp** core.

```

128 \ifimki@splitindex
129   \let\imki@startidx\imki@startidxunique
130   \AtBeginDocument{\let\@wrindex\imki@wrindexunique}
131   \let\imki@putindex\imki@putindexunique
132   \let\imki@wrindexentry\imki@wrindexentryunique
133   \let\imki@startidxsplit\@undefined
134   \let\imki@wrindexsplit\@undefined
135   \let\imki@putindexsplit\@undefined
136 \else
137   \let\imki@startidx\imki@startidxsplit
138   \AtBeginDocument{\let\@wrindex\imki@wrindexsplit}
139   \let\imki@putindex\imki@putindexsplit
140   \let\imki@wrindexentry\imki@wrindexentrysplit
141   \let\imki@startidxunique\@undefined
142   \let\imki@wrindexunique\@undefined
143   \let\imki@putindexunique\@undefined
144 \fi

```

File 157 **l warp-indentfirst.sty**§ 250 Package **indentfirst**Pkg **indentfirst** **indentfirst** is ignored.Discard all options for **l warp-indentfirst**:**for HTML output:** 1 \LWR@ProvidesPackageDrop{indentfirst}File 158 **l warp-index.sty**§ 251 Package **index**

(Emulates or patches code by DAVID M. JONES.)

Pkg **index** **index** is patched for use by **l warp**.**for HTML output:** 1 \LWR@ProvidesPackagePass{index}Use `\theLWR@autoindex` instead of `\thepage`. `\@tempsw@true` is used to force an immediate write to the index file instead of waiting until the end of the page.

```

2 \xpatchcmd{\newindex}
3   {\x@newindex[\thepage]}
4   {%

```

```

5      \@tempsw@true%
6      \x@newindex[theLWR@autoindex]%
7  }
8  {}
9  {\LWR@patcherror{index}{newindex}}
10
11 \xpatchcmd{\renewindex}
12   {\x@renewindex[thepage]}
13   {%
14     \@tempsw@true%
15     \x@renewindex[theLWR@autoindex]%
16   }
17   {}
18  {\LWR@patcherror{index}{renewindex}}

```

Patched to set a new autoindex:

```

19 \xpatchcmd{@wrindex}
20   {\begingroup}
21   {%
22     \addtocounter{LWR@autoindex}{1}%
23     \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}% lwarf
24     \begingroup%
25   }
26   {}
27  {\LWR@patcherror{index}{@wrindex}}

```

\AtBeginDocument **lwarf** core \lets \@wrindex to \LWR@wrindex. Since the **index** package has been loaded, \let to its version instead:

```

28 \let\LWR@index@\wrindex@\wrindex
29
30 \AtBeginDocument{
31 \let@\wrindex\LWR@index@\wrindex
32 }

```

Modified to add \index@prologue:

```

33 \AtBeginDocument{
34 \renewenvironment*{theindex}{%
35   \LWR@indexsection{\indexname}%
36   \ifx\index@prologue\empty\else
37     \index@prologue
38     \bigskip
39   \fi
40   \let\item\LWR@indexitem%
41   \let\subitem\LWR@indexsubitem%
42   \let\subsubitem\LWR@indexsubsubitem%
43 }{}}

```

```
44 }% AtBeginDocument
```

Disabled:

```
45 \def\@showidx#1{}
46 \let\@texttop\relax
47 \renewcommand*{\raggedbottom}={}
48 \renewcommand*{\flushbottom}={}
49 \renewcommand*{\markboth}[2]{}
50 \renewcommand*{\markright}[1]{}
```

File 159 **l warp-inputenc.sty**

§ 252 Package **inputenc**

Pkg **inputenc** Error if **inputenc** is loaded after **l warp**.

for HTML output: 1 \LWR@ProvidesPackageDrop{inputenc}
2 \LWR@loadbefore{inputenc}

File 160 **l warp-inputenx.sty**

§ 253 Package **inputenx**

Pkg **inputenx** Error if **inputenx** is loaded after **l warp**.

for HTML output: 1 \LWR@ProvidesPackageDrop{inputenx}
2 \LWR@loadbefore{inputenx}

File 161 **l warp-intopdf.sty**

§ 254 Package **intopdf**

Pkg **intopdf** **intopdf** is emulated.

The MIME type and description are ignored for now.

for HTML output: 1 \LWR@ProvidesPackageDrop{intopdf}

```

2 \NewDocumentCommand{\attachandlink}{m o m m}{%
3   \href{#1}{#4}%
4 }

```

File 162 **lwrap-keyfloat.sty**

§ 255 Package **keyfloat**

(Emulates or patches code by BRIAN DUNN.)

Pkg **keyfloat** **keyfloat** is supported with minor adjustments.

⚠ **keywrap** If placing a `\keyfig[H]` inside a `keywrap`, use an absolute width for `\keyfig`, instead of `lw`-proportional widths. (The `[H]` option forces the use of a `minipage`, which internally adjusts for a virtual 6-inch wide `minipage`, which then corrupts the `lw` option.)

for HTML output: 1 \LWR@ProvidesPackagePass{keyfloat}

After **keyfloat** has loaded:

```

2 \AtBeginDocument{

3 \RenewDocumentCommand{\KFLT@onefigureimage}{}
4 {%
5 \LWR@traceinfo{\KFLT@onefigureimage}%
6 \% \begin{lrbox}{\KFLT@envbox}%
7 \ifthenelse{\NOT\equal{\KFLT@lw}{} }{%
8 \includegraphics{%
9 [scale=\KFLT@s, width=\KFLT@imagedwidth]{\KFLT@i}} }{%
10 \% not linewidth
11 \ifthenelse{\dimtest{\KFLT@w}>}{0pt}{%
12 \% width is given
13 \ifthenelse{\dimtest{\KFLT@h}>}{0pt}{%
14 \% w and h
15 \includegraphics{%
16 [scale=\KFLT@s,%
17 width=\KFLT@imagedwidth, height=\KFLT@h]{\KFLT@i}} }{%
18 \% w and h
19 \% only w
20 \includegraphics{%
21 [scale=\KFLT@s, width=\KFLT@imagedwidth]{\KFLT@i}} }{%
22 \% only w
23 \% width is given
24 \% width is not given
25 \ifthenelse{\dimtest{\KFLT@h}>}{0pt}{%

```

```
26 {\includegraphics%
27 [scale=\KFLT@s, height=\KFLT@h]{\KFLT@i}}%
28 {\includegraphics%
29 [scale=\KFLT@s]{\KFLT@i}}%
30 }% width is not given
31 }% not linewidth
32 \%end{lrbox}%
33 \%unskip%
34 \%KFLT@findenvboxwidth%
35 \%begin{turn}{\KFLT@r}%
36 \%KFLT@frame{\usebox{\KFLT@envbox}}%
37 \%unskip%
38 \%end{turn}%
39 \LWR@traceinfo{KFLT@onefigureimage: done}%
40 }

41 \RenewDocumentEnvironment{KFLT@boxinner}{}%
42 {%
43 \LWR@traceinfo{KFLT@boxinner}%
44 \LWR@stoppars%
45 }%
46 {%
47 \LWR@startpars%
48 \LWR@traceinfo{KFLT@boxinner: done}%
49 }

50 \DeclareDocumentEnvironment{KFLT@marginfloat}{O{-1.2ex} m}%
51 {%
52 \LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}{marginblock}%
53 \captionsetup{type=#2}%
54 }%
55 {%
56 \endLWR@BlockClassWP%
57 }

58 \DeclareDocumentEnvironment{marginfigure}{o}%
59 {\begin{KFLT@marginfloat}{figure}%
60 {\end{KFLT@marginfloat}%
61
62 \DeclareDocumentEnvironment{margintable}{o}%
63 {\begin{KFLT@marginfloat}{table}%
64 {\end{KFLT@marginfloat}%

65 \DeclareDocumentEnvironment{keywrap}{m +m}%
66 {%
67 \LWR@ensuredoingapar%
68 \setlength{\LWR@templengthone}{#1}%
69 \begin{LWR@BlockClassWP}{%
```

```
70      float:right; width:\LWR@printlength{\LWR@templengthone}; % extra space
71      margin:10pt%
72 }%
73 {%
74     width:\LWR@printlength{\LWR@templengthone}%
75 }%
76 {marginblock}%
77 \setlength{\ linewidth}{.95\LWR@templengthone}%
78 #2%
79 \end{LWR@BlockClassWP}%
80 }
81 {%
82 }%
83 }% AtBeginDocument
```

File 163 l warp-layaureo.sty

§ 256 Package **layaureo**

Pkg layaureo **layaureo** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{layaureo}[2004/09/16]

File 164 l warp-layout.sty

§ 257 Package **layout**

(Emulates or patches code by KENT MCPHERSON, JOHANNES BRAAMS, HIDEO UMEKI.)

Pkg layout **layout** is emulated.

for HTML output: Discard all options for **l warp-layout**:

```
1 \LWR@ProvidesPackageDrop{layout}
2 \NewDocumentCommand{\layout}{s}{}{}
```

File 165 **l warp-leading.sty**

§ 258 Package **leading**

Pkg **leading** **leading** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{leading}[2008/12/11]

2 \newcommand\leading[1]{}

File 166 **l warp-letterspace.sty**

§ 259 Package **letterspace**

(Emulates or patches code by R SCHLICHT.)

Pkg **letterspace** **letterspace** is a subset of microtype, which is pre-loaded by **l warp**. All user options and macros are ignored and disabled.

for HTML output: Discard all options for **l warp-letterspace**:

1 \LWR@ProvidesPackageDrop{letterspace}
2 \newcommand*\lsstyle{}
3 \newcommand\textls[2][]{
4 \def\textls#1#2{
5 \newcommand*\lslig[1]{#1}

File 167 **l warp-lettrine.sty**

§ 260 Package **lettrine**

(Emulates or patches code by DANIEL FLIPO.)

Pkg **lettrine** Emulated.

for HTML output: Discard all options for **l warp-lettrine**:

1 \LWR@ProvidesPackageDrop{lettrine}

The initial letter is in a of class `lettrine`, and the following text is in a of class `lettrinetext`. `\lettrine[<keys>]{<letter>}{<additional text>}`

```

2 \DeclareDocumentCommand{\lettrine}{o m m}{%
3   \InlineClass{lettrine}{#2}\InlineClass{lettrinetext}{#3} % extra space
4 }
5
6 \newcounter{DefaultLines}
7 \setcounter{DefaultLines}{2}
8 \newcounter{DefaultDepth}
9 \newcommand*{\DefaultOptionsFile}{\relax}
10 \newcommand*{\DefaultLoversize}{0}
11 \newcommand*{\DefaultLraise}{0}
12 \newcommand*{\DefaultLhang}{0}
13 \newdimen\DefaultFindent
14 \setlength{\DefaultFindent}{\z@}
15 \newdimen\DefaultNindent
16 \setlength{\DefaultNindent}{0.5em}
17 \newdimen\DefaultSlope
18 \setlength{\DefaultSlope}{\z@}
19 \newdimen\DiscardVskip
20 \setlength{\DiscardVskip}{0.2\p@}
21 \newif\ifLettrineImage
22 \newif\ifLettrineOnGrid
23 \newif\ifLettrineRealHeight
24
25 \newcommand*{\LettrineTextFont}{\scshape}
26 \newcommand*{\LettrineFontHook}{}
27 \newcommand*{\LettrineFont}[1]{\InlineClass{lettrine}{#1}}
28 \newcommand*{\LettrineFontEPS}[1]{\includegraphics[height=1.5ex]{#1}}

```

File 168 `l warp-lineno.sty`

§ 261 Package **lineno**

(Emulates or patches code by STEPHAN I. BÖTTCHER.)

Pkg `lineno` `lineno` is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{lineno}

2 \newcommand*\resetlinenumber[1][\@ne]{}
3
4 \def\linenumbers{%
5   \@ifnextchar[\{\resetlinenumber\}]{%
6     \@ifstar{\resetlinenumber}{}}{%
7   }
}
```

```
8
9 \newcommand*{\nolinenumbers}{}
10
11 \Cname{linenumbers}{\par\linenumbers}
12 \Cname{runninglinenumbers}{\par\runninglinenumbers}
13
14 \def\endlinenumbers{\par}
15 \let\endrunninglinenumbers\endlinenumbers
16 \let\endpagewiselinenumbers\endlinenumbers
17 \expandafter\let\csname endlinenumbers*\endcsname\endlinenumbers
18 \expandafter\let\csname endrunninglinenumbers*\endcsname\endlinenumbers
19 \let\endnolinenumbers\endlinenumbers
20
21 \def\pagewiselinenumbers{\linenumbers\setpagewiselinenumbers}
22
23 \def\runninglinenumbers{\setrunninglinenumbers\linenumbers}
24
25 \def\setpagewiselinenumbers{}
26
27 \def\setrunninglinenumbers{}
28
29 \def\linenomath{}%
30 \Cname{linenomath}{\%}
31 \def\endlinenomath{}%
32 \expandafter\let\csname endlinenomath*\endcsname\endlinenomath
33
34 \let\linelabel\label
35
36 \def\switchlinenumbers{\@ifstar{}{}}
37 \def\setmakelinenumbers#1{\@ifstar{}{}}
38
39 \def\leftlinenumbers{\@ifstar{}{}}
40 \def\rightlinenumbers{\@ifstar{}{}}
41
42 \newcounter{linenumber}
43 \newcount\c@pagewiselinenumber
44 \let\c@runninglinenumber\c@linenumber
45
46 \def\runningpagewiselinenumbers{}
47 \def\realpagewiselinenumbers{}
48
49
50 \NewDocumentCommand\modulolinenumbers{s o}{}
51
52 \chardef\c@linenumbermodulo=5
53 \modulolinenumbers[1]
54
55 \newcommand*\firstlinenumber[1]{}
56
57 \newcommand\internallinenumbers{}
```

```
58 \let\endinternallinenumbers\endlinenumbers
59 \Cnamedef{internallinenumbers*}{\internallinenumbers*}
60 \expandafter\let\csname endinternallinenumbers*\endcsname\endlinenumbers
61
62 \newcommand*{\linenoplaceholder}[1]{% redefine per language
63     (line number reference for \detokenize\expandafter{#1})
64 }
65
66 \newcommand*{\lineref}[2][]{\linenoplaceholder{#2}}
67 \newcommand*{\linerefP}[2][]{\linenoplaceholder{#2}}
68 \newcommand*{\linerefR}[2][]{\linenoplaceholder{#2}}
69
70 \newcommand\quotelinenumbers
71     {\@ifstar\linenumbers{\@ifnextchar[\linenumbers{\linenumbers*}}}
72
73 \newdimen\linenumbersep
74 \newdimen\linenumberwidth
75 \newdimen\quotelinumbersep
76
77 \quotelinumbersep=\linenumbersep
78 \let\quotelinumberfont\linenumberfont
79
80 \def\linenumberfont{\normalfont\tiny\sffamily}
81
82
83 \linenumberwidth=10pt
84 \linenumbersep=10pt
85
86 \def\thelinenumber{}
87
88 \def\LineNumber{}
89 \def\makeLineNumber{}
90 \def\makeLineNumberLeft{}
91 \def\makeLineNumberRight{}
92 \def\makeLineNumberOdd{}
93 \def\makeLineNumberEven{}
94 \def\makeLineNumberRunning{}
95
96
97 \newenvironment{numquote}    {\quote}{\endquote}
98 \newenvironment{numquotation} {\quotation}{\endquotation}
99 \newenvironment{numquote*}   {\quote}{\endquote}
100 \newenvironment{numquotation*}{\quotation}{\endquotation}
101
102 \newdimen\bframerule
103 \bframerule=\fboxrule
104
105 \newdimen\bframesep
106 \bframesep=\fboxsep
107
```

```

108 \newenvironment{bframe}{%
109   \LWR@forceminwidth{\bframerule}%
110   \BlockClass[%
111     border:\LWR@printlength{\LWR@atleastonept} solid black ; %
112     padding:\LWR@printlength{\bframesep}%
113   ]{bframe}%
114 }%
116 {\endBlockClass}

```

File 169 **l warp-lips.sty**

§ 262 Package **lips**

(Emulates or patches code by MATT SWIFT.)

Pkg **lips** **lips** is emulated.

```

1 \% \LWR@ProvidesPackageDrop{lips}%
2 \PackageInfo{l warp}{Using the l warp version of package ‘lips’.}%
3 \ProvidesPackage{l warp-lips}%
4
5 \NewDocumentCommand{\Lips}{}{\textellipsis}%
6
7 \NewDocumentCommand{\BracketedLips}{}{[\textellipsis]}%
8
9 \let\lips\Lips
10 \let\olips\lips
11
12 \DeclareOption*{}%
13 \DeclareOption{mla}{%
14 \let\lips\BracketedLips
15 }%
16 \ProcessOptions\relax
17
18 \newcommand \LPNobreakList {}

```

File 170 **l warp-listings.sty**

§ 263 Package **listings**

(Emulates or patches code by CARSTEN HEINZ, BROOKS MOSES, JOBST HOFFMANN.)

Pkg **listings** **listings** is supported with some limitations. Text formatting is not yet supported.

```
for HTML output: 1 \begin{warpHTML}

2 \LWR@ProvidesPackagePass{listings}
```

Force flexible columns. Fixed columns inserts spaces in the PDF output.

```
3 \lst@column@flexible
```

Patches to embed listings inside pre tags:

```
4 \let\LWR@origlst@Init\lst@Init
5 \let\LWR@origlst@DeInit\lst@DeInit
6
7 \let\LWR@origlst@EveryPar\lst@EveryPar
8
9 \renewcommand{\lstlisting}[2]{\hypertocfloat{1}{\lstlisting}{lol}{#1}{#2}}
```

```
\lstset {<options>}
```

Use the **listings** literate option to replace HTML entities:

```
10 \def\lstset@#1{\endgroup%
11 %   \ifx\empty\@empty%
12 %     \empty%
13 %   \else%
14 %     \setkeys{lst}{%
15 %       #1%
16 %       ,literate=%
17 %       {<}{\HTMLentity{lt}}{4}%
18 %       {>}{\HTMLentity{gt}}{4}%
19 %       {\&}{\HTMLentity{amp}}{5}%
20 %     }%
21 %   \fi%
22 }
```

```
\lst@Init {<backslash-processing>} Done at the start of a listing.
```

```
23 \renewcommand{\lst@Init}[1]{%
```

Perform the **listings** initialization:

```
24 \LWR@traceinfo{lst@Init}%
25 \renewcommand*{\@capttype}{lstlisting}%
26 \let\lst@aboveskip\z@\let\lst@beforeskip\z@%
27 \gdef\lst@boxpos{t}%
28 \let\lst@frame\empty
29   \let\lst@frametshape\empty
30   \let\lst@framershape\empty
31   \let\lst@framebshape\empty
```

```

32 \let\lst@frameIshape\empty
33 \lstframe@\lst@frameround ffff\relax%
34 \lst@m multicols\empty%
35 \LWR@origlst@Init{\#1}\relax%

```

Avoids extra horizontal space:

```

36 \def\lst@frameIrlr{}%
37 \LWR@traceinfo{finished origlst@Init}%
38 \lst@ifdisplaystyle%

```

Creating a display.

Disable line numbers, produce the <pre>, then reenable line numbers.

```

39 \LWR@traceinfo{About to create verbatim.}%
40 \let\lstthk@EveryPar\relax%
41 \LWR@forcenewpage
42 \LWR@atbeginverbatim{2}{programlisting}%
43
44 \let\lstthk@EveryPar\LWR@origlstthkEveryPar%
45 \else%

```

Inline, so open a :

```

46 \ifbool{\LWR@verbtags}{\LWR@htmltag{span class="inlineprogramlisting"}{}}{%
47 \fi%
48 }%
49

```

\lst@DeInit Done at the end of a listing.

```

50 \renewcommand*{\lst@DeInit}{%
51 \lst@ifdisplaystyle%

```

Creating a display.

Disable line numbers, produce the </pre>, then reenable line numbers:

```

52 \let\lstthk@EveryPar\relax%
53 \LWR@afterendverbatim{0}%
54 \let\lstthk@EveryPar\LWR@origlstthkEveryPar%
55 \else%

```

Inline, so create the closing :

```

56 \ifbool{\LWR@verbtags}{\noindent\LWR@htmltag{/span}{}}{%
57 \fi%

```

Final **listings** deinit:

```

58 \LWR@origlst@DeInit%
59 }%

```

```
\lst@MakeCaption {⟨t/b⟩}
```

This is called BOTH at the top and at the bottom of each listing.

Patched for **lwrap**.

```
60 \def\lst@MakeCaption#1{%
61 \LWR@traceinfo{MAKING CAPTION at #1}%
62 \lst@ifdisplaystyle
63 \LWR@traceinfo{making a listings display caption}%
64 \ifx #1t%
65 \ifx\lst@@caption\empty\expandafter\lst@HRefStepCounter \else
66 \expandafter\refstepcounter
67 \fi {lstlisting}%
68 \LWR@traceinfo{About to assign label: !\lst@label!}%
69 %
70 \label{\lst@label}\fi
71 \LWR@traceinfo{Finished assigning the label.}%
72 \let\lst@arg\lst@intname \lst@ReplaceIn\lst@arg\lst@filenamerpl
73 \global\let\lst@name\lst@arg \global\let\lstname\lst@name
74 \lst@ifnoel\else
75 \ifx\lst@@caption\empty
76 \ifx\lst@caption\empty
77 \ifx\lst@intname\empty \else \def\lst@temp{ }%
78 \ifx\lst@intname\lst@temp \else
```

This code places a contents entry for a non-float. This would have to be modified for **lwrap**:

```
79 \LWR@traceinfo{addcontents lst@name: -\lst@name-}%
80 %
81 \addcontentsline{loll}{lstlisting}{\lst@name}
82 \fi\fi
83 \else
```

This would have to be modified for **lwrap**:

```
84 \LWR@traceinfo{addcontents lst@@caption: -\lst@@caption-}%
85 \addcontentsline{loll}{lstlisting}%
86 {\protect\numberline{\thelstlisting}%
87 {\protect\ignorespaces \lst@@caption \protect\relax}}%
88 \fi
89 \fi
90 \fi
91 \ifx\lst@caption\empty\else
92 \LWR@traceinfo{lst@caption not empty-}%
93 \lst@IfSubstring #1\lst@captionpos
94 {\begingroup
95 \LWR@traceinfo{at the selected position}%
```

These space and box commands are not needed for HTML output:

```
96 \% \let\@vskip\vskip
97 \% \def\vskip{\afterassignment\lst@vskip \tempskipa}%
```

```

98 %           \def\lst@vskip{\nobreak\@@vskip\@tempskipa\nobreak}%
99 %           \par\@parboxrestore\normalsize\normalfont % \noindent (AS)
100 %           \ifx #1\allowbreak \fi
101           \ifx\lst@title\empty

```

New **lwrap** code to create a caption:

```

102           \lst@makecaption\fnam@lstlisting{\ignorespaces \lst@caption}
103           \else

```

New **lwrap** code to create a title:

```

104 %           \lst@maketitle\lst@title % (AS)
105 \LWR@traceinfo{Making title: \lst@title}%
106 \begin{BlockClass}{\lstlistingtitle}\% lwrap
107 \lst@maketitle\lst@title\% lwrap
108 \end{BlockClass}\% lwrap
109           \fi
110 \LWR@traceinfo{About to assign label: !\lst@label!}%
111           \ifx\lst@label\empty\else
112 \leavevmode% gets rid of bad space factor error
113 \GetTitleStringExpand{\lst@caption}%
114 \edef\LWR@lntemp{\GetTitleStringResult}%
115 \edef@\currentlabelname{\detokenize\expandafter{\LWR@lntemp}}%
116 \label{\lst@label}\fi
117 \LWR@traceinfo{Finished assigning the label.}%

```

Not needed for **lwrap**:

```

118 %           \ifx #1b\allowbreak \fi
119           \endgroup}{}%
120           \fi
121 \LWR@traceinfo{end of making a listings display caption}%
122           \else
123 \LWR@traceinfo{INLINE}%
124           \fi
125 \LWR@traceinfo{DONE WITH CAPTION at #1}%
126 }

```

line numbers Patched to keep left line numbers outside of the left margin, and place right line numbers in a field \VerbatimHTMLWidth wide.

```

127 \lst@Key{numbers}{none}{%
128     \let\lst@PlaceNumber\empty
129     \lstKV@SwitchCases{#1}%
130     {none&\%\\
131     left&\def\lst@PlaceNumber{%

```

For now, **lwrap** places left line numbers inline. Ideally the entire line would be moved to the right, but conflicts with list indenting occurs.

```

132 %           \LWR@origllap{
133             \LWR@orignormalfont%
134             \lst@numberstyle{\the\lstnumber}\kern\lst@numbersep%
135 %
136 }\\%
137     right&\def\lst@PlaceNumber{\LWR@origrlap{\LWR@orignormalfont
138         \kern 6in \kern\lst@numbersep
139         \lst@numberstyle{\the\lstnumber}}}%%
140 }{\PackageError{Listings}{Numbers #1 unknown}\@ehc}%

141 \end{warpHTML}

```

File 171 **l warp-longtable.sty**

§ 264 Package **longtable**

(Emulates or patches code by DAVID CARLISLE.)

Pkg **longtable** **longtable** is emulated.

for HTML output: `\LWR@ProvidesPackageDrop{longtable}`

Longtable `\endhead`, `\endfoot`, and `\endlastfoot` rows are not used for HTML, and these rows should be disabled. Use

`\warpprintonly{row contents}`

instead of

`\begin{warpprint} ... \end{warpprint}`

Doing so helps avoid “Misplaced `\noalign`.” when using `\begin{warpprint}`.

Keep the `\endfirsthead` row, which is still relevant to HTML output.

⚠ `\kill` `\kill` is ignored, place a `\kill` line inside

`\begin{warpprint} ... \end{warpprint}`

or place it inside `\warpingprintonly`.

⚠ `lateximage` **longtable** is not supported inside a `lateximage`.

See:

<http://tex.stackexchange.com/questions/43006/why-is-input-not-expandable>

Env `longtable` * [*horizontalignment*] {*colspec*} Emulates the `longtable` environment.

Per the `caption` package, the starred version steps the counter per caption. The unstarred version steps the counter once at the beginning, but not at each caption.

Options [c], [l], and [r] are thrown away.

```

2 \newenvironment{longtable}[2][]{%
3 \LWR@floatbegin{table}%
4 \setcaptiontype{\LTcaptype}%
5 \caption@setoptions{longtable}%
6 \caption@setoptions{@longtable}%
7 \caption@LT@setup%
8 \booltrue{\LWR@starredlongtable}%
9 \let\captionlistentry\LWR@LTcaptionlistentry%
10 \LWR@tabular{#2}%
11 }%
12 {\endLWR@tabular\endLWR@floatend}%
13
14 \newenvironment{longtable}[2][]{%
15 \LWR@floatbegin{table}%
16 \setcaptiontype{\LTcaptype}%
17 \caption@setoptions{longtable}%
18 \caption@setoptions{@longtable}%
19 \caption@LT@setup%
20 \refstepcounter{\LTcaptype}%
21 \let\captionlistentry\LWR@LTcaptionlistentry%
22 \LWR@tabular{#2}%
23 }%
24 {\endLWR@tabular\endLWR@floatend}%
25

```

Provided for compatibility, but ignored:

```

26 \newcounter{LTchunksize}
27 \def\endhead{\LWR@tabularendofline}% throws away options // [dim] and //*
28 \def\endfirsthead{\LWR@tabularendofline}
29 \def\endfoot{\LWR@tabularendofline}
30 \def\endlastfoot{\LWR@tabularendofline}
31 \newcommand\tabularnewline{\LWR@tabularendofline}
32 \newcommand{\setlongtables}{}% Obsolete command, does nothing.
33 \newlength{\LTleft}
34 \newlength{\LTright}
35 \newlength{\LTpre}
36 \newlength{\LTpost}
37 \newlength{\LTcapwidth}

38 \LetLtxMacro{\LWR@origkill}{\kill}
39 \renewcommand*{\kill}{\LWR@tabularendofline}

```

```
40 \appto\LWR@restoreorigformatting{%
41 \LetLtxMacro\kill\LWR@origkill%
42 }
```

File 172 **l warp-lscape.sty**

§ 265 Package **lscape**

(Emulates or patches code by D. P. CARLISLE.)

Pkg **lscape** **lscape** is emulated.

for HTML output: Discard all options for **l warp-lscape**.

```
1 \LWR@ProvidesPackageDrop{lscape}

2 \newenvironment*{landscape}{}{}
```

File 173 **l warp-ltablex.sty**

§ 266 Package **ltablex**

(Emulates or patches code by ANIL K. GOEL.)

Pkg **ltablex** **ltablex** is emulated by **l warp**.

for HTML output: Relies on **tabularx**.

```
1 \RequirePackage{tabularx}
2
3 \LWR@ProvidesPackageDrop{ltablex}
4
5 \DeclareDocumentEnvironment{tabularx}{m o m}
6 {\longtable{#3}}
7 {\endlongtable}
8
9 \DeclareDocumentEnvironment{tabularx*}{m o m}
10 {\longtable{#3}}
11 {\endlongtable}
12
13 \newcommand*{\keepXColumns} {}
14 \newcommand*{\convertXColumns} {}
```

File 174 l warp-l t caption .sty

§ 267 Package **l t caption**

(Emulates or patches code by AXEL SOMMERFELDT.)

Pkg l t caption **l t caption** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{l t caption}

\LTcap type is already defined by l warp.

longtable* is already defined by l warp-longtable.

```
2 \newlength{\LTcapskip}
3 \newlength{\LTcapleft}
4 \newlength{\LTcapright}
5 \newcommand*{\LTcapmarginsfalse}{}{}
```

File 175 l warp-l tx grid .sty

§ 268 Package **l tx grid**

Pkg l tx grid **l tx grid** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{l tx grid}

```
2 \newcommand*{\onecolumngrid}{}{}
3 \newcommand*{\twocolumngrid}{}{}
4 \newcommand*{\removestuff}{}{}
5 \newcommand*{\addstuff}[2]{}{}
6 \newcommand*{\replacestuff}[2]{}{}
```

File 176 l warp-l txt able .sty

§ 269 Package **l txt able**

Pkg l txt able **l txt able** is emulated.

- ⚠ **table numbering** The print version does not seem to honor `longtable*` from the `caption` package, while `l warp` does.

for HTML output: 1 `\LWR@ProvidesPackageDrop{ltxtable}`

```
\LTXtable {<width>} {<file>}  
2 \newcommand*{\LTXtable}[2]{%  
3 \input{#2}%  
4 }
```

File 177 `l warp-lua-check-hyphen.sty`

§ 270 Package **lua-check-hyphen**

Pkg `lua-check-hyphen` **lua-check-hyphen** is ignored.

for HTML output: 1 `\LWR@ProvidesPackageDrop{lua-check-hyphen}`
2 `\newcommand*{\LuaCheckHyphen}[1]{}`

File 178 `l warp-lua-visual-debug.sty`

§ 271 Package **lua-visual-debug**

Pkg `lua-visual-debug` **lua-visual-debug** is ignored.

for HTML output: 1 `\LWR@ProvidesPackageDrop{lua-visual-debug}[2016/05/30]`

File 179 `l warp-luacolor.sty`

§ 272 Package **luacolor**

Pkg `luacolor` **luacolor** is ignored.

for HTML output: 1 `\LWR@ProvidesPackageDrop{luacolor}`
2 `\newcommand{\luacolorProcessBox}[1]{}`

File 180 **l warp-luatodonotes.sty**

§ 273 Package **luatodonotes**

(Emulates or patches code by FABIAN LIPP.)

Pkg luatodonotes **luatodonotes** is emulated.

The documentation for **todonotes** and **luatodonotes** have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

for HTML output: 1 \LWR@ProvidesPackagePass{luatodonotes}

Nullify options:

```
2 \@todonotes@additionalMarginEnabledfalse

3 \if@todonotes@disabled
4 \else
5
6 \newcommand{\ext@todo}{\textcolor{red}{\textsf{todo}}}
7
8 \renewcommand{\l@todo}[2]{\hypertocfloat{1}{\textcolor{red}{\textsf{todo}}}{\l@do}{\#1}{\#2}{

9 \let\LWRTODONOTES@orig@todototoc\todototoc
10
11 \renewcommand*{\todototoc}{%
12 \phantomsection%
13 \LWRTODONOTES@orig@todototoc%
14 }
15
16
17 \renewcommand{\@todonotes@drawMarginNoteWithLine}{%
18 \fcolorbox{%
19   \textcolor{red}{\textsf{@todonotes@currentbordercolor}}%
20   \textcolor{red}{\textsf{@todonotes@currentbackgroundcolor}}%
21   \textcolor{red}{\textsf{@todonotes@numberoftodonotes}}%
22 }{\marginpar{\@todonotes@drawMarginNote}}%
23 }
24
25 \renewcommand{\@todonotes@drawInlineNote}{%
26 \fcolorboxBlock{%
27   \textcolor{red}{\textsf{@todonotes@currentbordercolor}}%
```

```
28      {\@todonotes@currentbackgroundcolor}%
29      {%
30          \if@todonotes@authorgiven%
31              {\@todonotes@author:\,}%
32          \fi%
33          \@todonotes@text%
34      }%
35 }
36
37 \newcommand{\@todonotes@drawMarginNote}{%
38     \if@todonotes@authorgiven%
39         \@todonotes@author\par%
40     \fi%
41     \arabic{@todonotes@numberoftodonotes}: %
42     \fcolorbox{%
43         {\@todonotes@currentbordercolor}%
44         {\@todonotes@currentbackgroundcolor}%
45     }{%
46         \@todonotes@sizecommand%
47         \@todonotes@text %
48     }%
49 }%
50
51 \renewcommand{\missingfigure}[2][]{%
52 \setkeys{todonotes}{#1}%
53 \addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
54 \fcolorboxBlock{%
55     {\@todonotes@currentbordercolor}%
56     {\@todonotes@currentfigcolor}%
57     {%
58         \setlength{\fboxrule}{4pt}%
59         \fcolorbox{red}{white}{Missing figure} \quad #2%
60     }%
61 }%
62
63 \LetLtxMacro{\LWRTODONOTES@orig@todocommon}{\@todocommon}
64
65 \RenewDocumentCommand{\@todocommon}{m m}{%
66 \begingroup%
67 \renewcommand*{\phantomsection}{}%
68 \LWRTODONOTES@orig@todocommon{#1}{#2}%
69 \endgroup%
70 }%
71
72 \renewcommand{\@todoarea}[3][]{%
73     \@todonotes@areaselectedtrue%
74     \@todocommon{#1}{#2}%
75     \@todonotes@textmark@highlight{#3}%
76     \zref@label{\@todonotes@\arabic{@todonotes@numberoftodonotes}@end}%
77 }%
```

```
78
79
80 \DeclareDocumentCommand{\todonotes@textmark@highlight}{m}{%
81   \InlineClass[background:\LWR@origpound{}B3FFB3]{highlight}{#1}%
82 }
83
84 \fi% \if@todonotes@disabled
```

File 181 **l warp-magaz.sty**

§ 274 Package **magaz**

Pkg **magaz** **magaz** is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{magaz}

2 \newcommand\FirstLine[1]{%
3   \begingroup%
4   \FirstLineFont{%
5     \LWR@textcurrentcolor{%
6       \LWR@textcurrentfont{%
7         #1%
8       }%
9     }%
10   }%
11   \endgroup%
12 }
13
14 \providecommand\FirstLineFont{\scshape}
```

File 182 **l warp-makeidx.sty**

§ 275 Package **makeidx**

(Emulates or patches code by L^AT_EX PROJECT TEAM.)

Pkg **makeidx** **makeidx** is patched for use by **l warp**.

for HTML output:

```
1 \LWR@ProvidesPackagePass{makeidx}
```

\@wrindex is redefined \AtBeginDocument by the **l warp** core.

```
\printindex

2 \preto\printindex{%
3   \LWR@orignewpage%
4   \LWR@startpars%
5 }
```

File 183 **l warp-marginfit.sty**

§ 276 Package **marginfit**

Pkg **marginfit** **marginfit** is ignored.

for HTML output: Discard all options for **l warp-marginfit**:

```
1 \LWR@ProvidesPackageDrop{marginfit}
```

File 184 **l warp-marginfix.sty**

§ 277 Package **marginfix**

(Emulates or patches code by STEPHEN HICKS.)

Pkg **marginfix** Emulated.

for HTML output: Discard all options for **l warp-marginfix**:

```
1 \LWR@ProvidesPackageDrop{marginfix}

2 \newcommand*{\marginskip}[1]{}
3 \newcommand*{\clearmargin}{}
4 \newcommand*{\softclearmargin}{}
5 \newcommand*{\extendmargin}[1]{}
6 \newcommand*{\mparshift}[1]{}
7 \newdimen\marginheightadjustment
8 \newdimen\marginposadjustment
9 \newcommand*{\blockmargin}[1][]{}
10 \newcommand*{\unblockmargin}[1][]{}
11 \newcommand*{\marginphantom}[2][]{}
```

File 185 **l warp-marginnote.sty**

§ 278 Package **marginnote**

(Emulates or patches code by MARKUS KOHM.)

Pkg **marginnote** Emulated.

for HTML output: Discard all options for **l warp-marginnote**:

```
1 \LWR@ProvidesPackageDrop{marginnote}

2 \NewDocumentCommand{\marginnote}{+o +m o}{\marginpar{#2}{}}

3 \newcommand*{\marginnoteleftadjust}={}
4 \newcommand*{\marginnoterightadjust}={}
5 \newcommand*{\marginnotetextwidth}={}
6 \let\marginnotetextwidth\textwidth
7 \newcommand*{\marginnotevadjust}={}
8 \newcommand*{\marginfont}={}
9 \newcommand*{\raggedleftmarginnote}={}
10 \newcommand*{\raggedrightmarginnote}={}
```

File 186 **l warp-mcaption.sty**

§ 279 Package **mcaption**

(Emulates or patches code by STEPHAN HENNIG.)

Pkg **mcaption** **mcaption** is nullified.

for HTML output: Discard all options for **l warp-mcaption**:

```
1 \LWR@ProvidesPackageDrop{mcaption}

2 \newenvironment{margincap}{}{}
3 \newcommand*{\margincapalign}{{}}
4 \newlength{\margincapskip}
```

File 187 **l warp-mdframed.sty**

§ 280 Package **mdframed**

(Emulates or patches code by MARCO DANIEL, ELKE SCHUBERT.)

Pkg **mdframed** **mdframed** is loaded with options forced to `framemethod=none`.

§ 280.1 **Limitations**

support Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for **mdframed** environments and frame titles.

⚠ **loading** When used, **l warp** loads **mdframed** in HTML with `framemethod=none`.

font For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where `\textbf` must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the **mdframed** source). Since **l warp** does not support `\bfseries` and friends, only one font selection may be made at a time.

theoremtitlefont **theoremtitlefont** is not supported, since the following text is not in braces in the **mdframed** source.

footnotes Footnotes are currently placed at the bottom of the HTML page.

ignored options `userdefinedwidth` and `align` are currently ignored.

CSS classes Environments created or encapsulated by **mdframed** are enclosed in a `<div>` of class `md<environmentname>`, or **mdframed** otherwise.

Frame titles are placed into a `` of class `mdframedtitle`. Subtitles are in a `` of class `mdframedsubtitle`, and likewise for subsubtitles.

Pre-existing hooks are used to patch extra functions before and after the frames.

§ 280.2 Package loading

for HTML output:

```

1 \RequirePackage{xcolor}%
2 for \convertcolorspec
3 \LWR@ProvidesPackageDrop{mdframed}
```

amsthm must be loaded before **mdframed**

```
4 \LWR@origRequirePackage{amsthm}
```

Do not require *Tikz* or *pstricks*:

```
5 \LWR@origRequirePackage[framemethod=none]{mdframed}
```

§ 280.3 Patches

Patch to remove PDF formatting and add HTML tags:

```

6 \AtBeginDocument{
7 \def\mdf@trivlist#1{%
8   \edef\mdf@temp{%
9     \topsep=\the\topsep\relax%
10    \partopsep=\the\partopsep\relax%
11    \parsep=\the\parsep\relax%
12  }%
13  \setlength{\topsep}{#1}%
14  \topskip\z@%
15  \partopsep\z@%
16  \parsep\z@%
17  \@nblistfalse%
18  \@trivlist%
19  \labelwidth\z@%
20  \leftmargin\z@%
21  \itemindent\z@%
22  \let\@itemlabel\@empty%
23  \def\makelabel##1{##1}%
24  \item\relax\mdf@temp\relax%
25 }
26
27 \renewcommand*{\endmdf@trivlist}{%
28 \LWR@traceinfo{\endmdf@trivlist}%
29 \endtrivlist%
30 \LWR@listend%
31 }
32 }% AtBeginDocument
```

§ 280.4 Initial setup

To handle CSS and paragraphs, patch code at start and end of environment and contents. `\LWR@print@raggedright` helps avoid hyphenation.

```
33 \mdfsetup{
34 startcode={\LWR@mdframedstart\LWR@print@raggedright},
35 endcode={\LWR@mdframedend},
36 startinnercode={\LWR@startpars\LWR@print@raggedright},
37 endinnercode={\LWR@stoppars},
38 }
```

§ 280.5 Color and length HTML conversion

`\LWR@mdfprintcolor` {*mdfcolorkey*}

Given the **mdframed** key, print the color.

```
39 \newcommand*{\LWR@mdfprintcolor}[1]{%
40 \convertcolorspec{named}{\nameuse{mdf@#1}}{HTML}\LWR@tempcolor%
41 \LWR@origpound\LWR@tempcolor
42 }
```

`\LWR@mdfprintlength` {*mdflengthkey*}

Given the **mdframed** key, print the length.

```
43 \newcommand*{\LWR@mdfprintlength}[1]{%
44 \LWR@printlength{\nameuse{mdf@#1}length}}
45 }
```

§ 280.6 Environment encapsulation

`\LWR@mdframedstart` Actions before an mdframe starts.

Encapsulate a frame inside a `<div>` of the desired class.

```
46 \newcommand*{\LWR@mdframedstart}%
47 \LWR@traceinfo{\LWR@mdframedstart start}%
```

Turn off paragraph handling during the generation of the encapsulating tags:

```
48 \LWR@stoppars%
```

Open a `<div>` and with custom class and custom style:

```
49 \LWR@htmtagc{div class="\LWR@mdthisenv" \LWR@orignewline
50 style="" \LWR@orignewline}
```

Convert and print the background color:

```
51 background: \LWR@mdfprintcolor{backgroundcolor} ; \LWR@orignewline
```

Convert and print the border color and width:

```
52 border: \LWR@mdfprintlength{linewidth} solid
53 \LWR@mdfprintcolor{linecolor} ; \LWR@orignewline
```

Convert and print the border radius:

```
54 border-radius: \LWR@mdfprintlength{roundcorner} ; \LWR@orignewline
```

Convert and print the shadow:

```
55 \ifbool{mdf@shadow}{%
56   box-shadow:
57   \LWR@mdfprintlength{shadowsize}
58   \LWR@mdfprintlength{shadowsize}
59   \LWR@mdfprintlength{shadowsize}
60   \LWR@mdfprintcolor{shadowcolor} ;
61 }
62 {box-shadow: none ;}
63 \LWR@orignewline

64 "}
65 \% \LWR@htmldivclass{\LWR@mdthisenv}
```

`mdframed` environment may not work with the HTML versions of the following, so restore them to their originals while inside `mdframed`:

```
66 \LWR@select@print@hspace%
67 \renewcommand*{\rule}{\LWR@print@rule}
68 \LetLtxMacro\makebox\WWR@print@makebox%

69 \LWR@startpars%
70 \LWR@traceinfo{\LWR@mdframedstart done}%
71 }
```

\LWR@mdframedend Actions after an mdframe ends.

After closing the `<div>`, globally restore to the default environment type:

```
72 \newcommand*{\LWR@mdframedend}{%
73 \LWR@traceinfo{\LWR@mdframedend start}%

```

Close the custom `<div>`:

```
74 \LWR@htmldivclassend{\LWR@mdthisenv}
```

Reset future custom class to the default:

```
75 \gdef\LWR@mdthisenv{mdframed}
```

Resume paragraph handling:

```
76 \LWR@startpars%
77 \LWR@traceinfo{\LWR@mdframedend done}%
78 }
```

§ 280.7 Mdframed environment

```
79 \renewenvironment{mdframed}[1] [] {%
80   \color@begingroup%
81   \mdfsetup{userdefinedwidth=\ linewidth,\#1}%
82   \mdf@startcode%
83   \mdf@preenvsetting%
84   \ifdefempty{\mdf@firstframetitle}{}{%
85     {\let\mdf@frametitlesave\mdf@frametitle%
86      \let\mdf@frametitle\mdf@firstframetitle%
87    }%
88   \ifvmode\nointerlineskip\fi%
89   \ifdefempty{\mdf@frametitle}{}{%
90     {\mdfframedtitleenv{\mdf@frametitle}%
91       \mdf@frametitle@use%
92     }%
93   \mdf@trivlist{\mdf@skipabove@length}%%
94   \mdf@settings%
95 %   \mdf@lrbox{\mdf@splitbox@one}%
96 %   \mdf@startinnercode%
97 }%
98 {%
99 %   \mdf@ignorelastdescenders%
100  \par%
101 %   \unskip\ifvmode\nointerlineskip\hrule \@height\z@ \@width\hsize\fi%%
102  \ifmdf@footnoteinside%
103    \def\mdf@reservedaf{%
104      \mdf@footnoteoutput%
105      \mdf@endinnercode%
106      \endmdf@lrbox%
107      \ifdefempty{\mdf@frametitle}{}{%
108        {\mdfframedtitleenv{\mdf@frametitle}\mdf@frametitle@use}%
109        \detected@mdf@put@frame
110      }%
111    \else%
112      \def\mdf@reservedaf{%
113        \mdf@endinnercode%
114        \endmdf@lrbox%
115        \ifdefempty{\mdf@frametitle}{}{%
116          {\mdfframedtitleenv{\mdf@frametitle}\mdf@frametitle@use}%
117          \detected@mdf@put@frame%
118          \mdf@footnoteoutput%
119        }%
120      \fi%
121      \mdf@reservedaf%
122    \aftergroup\endmdf@trivlist%
123    \color@endgroup%
124    \mdf@endcode%
125 }
```

```
\mdf@footnoteoutput
126 \renewrobustcmd*\mdf@footnoteoutput{%
127   \LWR@printpendingmpfootnotes%
128 }
```

§ 280.8 Titles and subtitles

\mdfframedtitleenv {*<title>*}

Encapsulation of the original which places the title inside a of class `mdfframedtitle`:

```
129 \LetLtxMacro{\LWR@origmdfframedtitleenv}{\mdfframedtitleenv}
130
131 \newlength{\LWR@titleroundcorner}
132
133 \renewrobustcmd{\mdfframedtitleenv[1]}{%
134 \LWR@traceinfo{\LWR@mdfframedtitleenv start}%
135 \% \LWR@origmdfframedtitleenv{%
```

Open a with a custom class and custom style:

```
136 \LWR@htmllagc{span class="mdfframedtitle" \LWR@orignewline
137 style=" \LWR@orignewline
```

Convert and print the title background color:

```
138 background:
139 \LWR@mdfprintcolor{frametitlebackgroundcolor}
140 ; \LWR@orignewline
```

Convert and print the title rule:

```
141 \ifbool{\mdf@frametitlerule}{%
142   border-bottom:
143   \LWR@mdfprintlength{frametitlerulewidth}
144   solid
145   \LWR@mdfprintcolor{frametitlerulecolor}
146   ; \LWR@orignewline
147 }{}%
```

Finish the custom style and the opening span tag:

```
148 " \LWR@orignewline
149 }% span
```

Restrict paragraph tags inside a span:

```
150 \begin{LWR@nestspan}%
```

Print the title inside the span:

```
151 #1%
```

Closee the span and unnest the paragraph tag restriction:

```

152 \LWR@htmtagc{/span}%
153 \end{LWR@nestspan}%
154 }%
155 \LWR@traceinfo{LWR@mdframedtitleenv end}%
156 }

\LWR@mdfsubtitlecommon {<sub -or- subsub>} [<options>] {<title>}
Common code for \LWR@mdfsubtitle and \LWR@mdfsubsubtitle.
Encapsulate the subtitle inside a <span> of class mdframedsubtitle:
157 \NewDocumentCommand{\LWR@mdfsubtitlecommon}{m o m}
158 {%
    the following empty line is required
159
160 \LWR@traceinfo{LWR@mdframedsubtitlecommon start}%

Special handling for mdframed: Subtitles have \pars around them, so temporarily
disable them here.
161 \let\par\LWR@origpar%
Open a <span> with a custom class and custom style:
162 \LWR@htmtagc{span class="mdframed#1title"
163 style="" \LWR@orignewline
Convert and print the background color:
164 background:
165 \LWR@mdfprintcolor{#1titlebackgroundcolor}
166 ; \LWR@orignewline
Convert and print the above line:
167 \ifbool{mdf@#1titleaboveline}{%
168     border-top:
169     \LWR@mdfprintlength{#1titleabovelinewidth}
170     solid
171     \LWR@mdfprintcolor{#1titleabovelinecolor}
172     ; \LWR@orignewline
173 }{}}

Convert and print the below line:
174 \ifbool{mdf@#1titlebelowline}{%
175     border-bottom:
176     \LWR@mdfprintlength{#1titlebelowlinewidth}
177     solid
178     \LWR@mdfprintcolor{#1titlebelowlinecolor}
179     ; \LWR@orignewline
180 }{}}

Finish the custom style and the opening span tag:
181 "}% span

```

Restrict paragraph tags inside a span:

```
182 \begin{LWR@nestspan}%
```

Perform the original subtitle action:

```
183 \IfNoValueTF{#2}
184 { \nameuse{LWR@origmdf#1title}{#3}%
185 { \nameuse{LWR@origmdf#1title}{#2}{#3}}%
```

Close the span and unnest the paragraph tag restriction:

```
186 \LWR@htmlltagc{/span}%
187 \end{LWR@nestspan}%
188
189 \LWR@traceinfo{LWR@mdframedsubtitlecommon end}%
190 }
```

\LWR@mdfsubtitle [⟨options⟩] {⟨title⟩}

```
191 \newcommand*{\LWR@mdfsubtitle}{%
192 \LWR@mdfsubtitlecommon{sub}%
193 }
194 \let\mdfsubtitle\LWR@mdfsubtitle
```

\LWR@mdfsubsubtitle [⟨options⟩] {⟨title⟩}

```
195 \newcommand*{\LWR@mdfsubsubtitle}{%
196 \LWR@mdfsubtitlecommon{subsub}%
197 }
198 \let\mdfsubsubtitle\LWR@mdfsubsubtitle
```

§ 280.9 New environments

\LWR@mdthisenv Stores the environment of the frame about to be created:

```
199 \newcommand*{\LWR@mdthisenv}{mdframed}
```

\newmdenv [⟨options⟩] {⟨env-name⟩}

Modified from the original to remember the environment.

```
200 \renewrobustcmd*\newmdenv[2] []{%
201 \newenvironment{#2}%
202 {%
203 \mdfsetup{#1}%
204 \renewcommand*{\LWR@mdthisenv}{md#2}%
205 \begin{mdframed}%
206 }%
207 {\end{mdframed}}%
208 }
```

\surroundwithmdframed [*options*] [*environment*]

Modified from the original to remember the environment.

```
209 \renewrobustcmd*\{\surroundwithmdframed\}[2] [] {%
210 \BeforeBeginEnvironment{#2}{%
211 \renewcommand*\{\LWR@mdthisenv\}{md#2}%
212 \begin{mdframed}[#1]}%
213 \AfterEndEnvironment{#2}{\end{mdframed}}%
214 }
```

\mdtheorem [*mdframed-options*] [*envname*] [*numberedlike*] [*caption*] [*within*]

Modified from the original to remember the environment.

```
215 \DeclareDocumentCommand{\mdtheorem}{ O{} m o m o }{%
216 {\ifcsdef{#2}{%
217 {\mdf@PackageWarning{Environment #2 already exists\MessageBreak}}%
218 {%
219 \IfNoValueTF{#3}{%
220 {\%#3 not given -- number relationship
221 \IfNoValueTF{#5}{%
222 {\%#3+#5 not given
223 \c@definecounter{#2}%
224 \expandafter\xdef\cscname the#2\endcsname{\c@thmcounter{#2}}%
225 \newenvironment{#2}[1][]{%
226 \refstepcounter{#2}%
227 \ifstrempty{##1}{%
228 {\let\temptitle\relax}%
229 {%
230 \def\temptitle{\mdf@theoremseparator%
231 \mdf@theoremspace%
232 \mdf@theoremtitlefont%
233 ##1}%
234 \mdf@thm@caption{#2}{\#4}{\cscname the#2\endcsname{##1}}%
235 }%
236 \begin{mdframed}[#1,frametitle={\strut\#4\ \cscname the#2\endcsname{##1}}]%
237 {\@temptitle}]]}%
238 {\end{mdframed}}%
239 \newenvironment{#2*}[1][]{%
240 \ifstrempty{##1}{\let\temptitle\relax{\def\temptitle{: \ ##1}}%
241 \begin{mdframed}[#1,frametitle={\strut\#4\@temptitle}]}}%
242 {\end{mdframed}}}}%
243 {%
244 {\%#5 given -- reset counter
245 \c@definecounter{#2}\c@newctr{#2}[#5]%
246 \expandafter\xdef\cscname the#2\endcsname{\c@thmcounter{#2}}%
247 \expandafter\xdef\cscname the#2\endcsname{%
248 \expandafter\noexpand\cscname the#5\endcsname \c@thmcountersep\%
249 \c@thmcounter{#2}}%
250 \newenvironment{#2}[1][]{%
```

```
251      \refstepcounter{#2}%
252      \ifstrempty{##1}%
253          {\let\@temptitle\relax}%
254          {%
255              \def\@temptitle{\mdf@theoremseparator%
256                          \mdf@theoremspace%
257                          \mdf@theoremtitlefont%
258                          ##1}%
259              \mdf@thm@caption{#2}{\#4}{\csname the#2\endcsname}{##1}}%
260          }
261      \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
262                                  \@temptitle}]]}%
263      {\end{mdframed}}%
264      \newenvironment{#2*}[1][]{%
265          \ifstrempty{##1}%
266              {\let\@temptitle\relax}%
267              {%
268                  \def\@temptitle{\mdf@theoremseparator%
269                          \mdf@theoremspace%
270                          \mdf@theoremtitlefont%
271                          ##1}%
272                  \mdf@thm@caption{#2}{\#4}{\csname the#2\endcsname}{##1}}%
273              }%
274          \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]]}%
275          {\end{mdframed}}%
276      }%
277  }%
278  \relax -- number relationship
279  \global\@namedef{the#2}{\@nameuse{the#3}}%
280  \newenvironment{#2}[1][]{%
281      \refstepcounter{#3}%
282      \ifstrempty{##1}%
283          {\let\@temptitle\relax}%
284          {%
285              \def\@temptitle{\mdf@theoremseparator%
286                          \mdf@theoremspace%
287                          \mdf@theoremtitlefont%
288                          ##1}%
289              \mdf@thm@caption{#2}{\#4}{\csname the#2\endcsname}{##1}}%
290          }%
291      \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
292                                  \@temptitle}]]}%
293      {\end{mdframed}}%
294      \newenvironment{#2*}[1][]{%
295          \ifstrempty{##1}{\let\@temptitle\relax\def\@temptitle{: \ ##1}}%
296          \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]]}%
297          {\end{mdframed}}%
298      }%
299  \BeforeBeginEnvironment{#2}{\renewcommand*{\LWR@mdthisenv}{md#2}}% l warp
300  \BeforeBeginEnvironment{#2*}{\renewcommand*{\LWR@mdthisenv}{md#2}}% l warp
```

```

301     }%
302 }

\newmdtheoremenv  [<mdframed-options>] [<envname>] [<numberedlike>] [<caption>] [<within>]
Modified from the original to remember the environment.

303 \DeclareDocumentCommand\newmdtheoremenv{O{} m o m o }{%
304   \ifboolexpr{ test {\IfNoValueTF {#3}} and test {\IfNoValueTF {#5}} }{%
305     \newtheorem{#2}{#4}}{%
306     \IfValueT{#3}{\newtheorem{#2}[#3]{#4}}{%
307       \IfValueT{#5}{\newtheorem{#2}{#4}[#5]}{%
308         }%
309       }%
310   \BeforeBeginEnvironment{#2}{%
311     \renewcommand*{\LWR@mdthisenv}{md#2}%
312     \begin{mdframed}[]{#1}}%
313   \AfterEndEnvironment{#2}{%
314     \end{mdframed}}%
315 }

```

File 188 **l warp-memhfixc.sty**

§ 281 Package **memhfixc**

Pkg **memhfixc** **memhfixc** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{memhfixc}

File 189 **l warp-metalogo.sty**

§ 282 Package **metalogo**

(Emulates or patches code by ANDREW GILBERT MOSCHOU.)

Pkg **metalogo** **metalogo** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{metalogo}

```

2 \newcommand\setlogokern[2]{}
3 \newcommand\setlogodrop[2][XeTeX]{}
4 \newcommand\setLaTeXa[1]{}
5 \newcommand\setLaTeXee[1]{}
6 \newcommand\seteverylogo[1]{}
7 \newcommand\everylogo[1]{}

```

File 190 **lwarf-mhchem.sty**

§ 283 Package **mhchem**

(Emulates or patches code by MARTIN HENSEL.)

Pkg **mhchem** **mhchem** is patched for use by **lwarf**.

mhchem expressions are converted to svg math. Inline expressions use hashed filenames to allow reuse, and assume that any **mhchem** options are global.

⚠ **MATHJAX and mhchem** The MATHJAX **mhchem** extension is not yet used. If MATHJAX is used for math in the rest of the document, **lwarf** converts standalone **mhchem** expressions into SVG math images, but expressions inside math must be placed between `\displaymathother` and `\displaymathnormal`:

```
\displaymathother
\[\ce{ ... }]\quad \dots \quad \$\ce{ ... }\$
```

⚠ **nested math** When producing HTML output, **lwarf** does not support the use of nested dollar signs in **mhchem** expressions.

For some examples from the **mhchem** manual, change as follows:

<code>\ce{NaOH(aq,\$\infty)}</code>	% old
<code>\ce{NaOH(aq,\infty)}</code>	% new
<code>\ce{Fe(CN)_{\frac{6}{2}}}</code>	% old
<code>\ce{Fe(CN)_{\frac{6}{2}}}</code>	% new
<code>\ce{NO_{x}}</code>	% old
<code>\ce{NO_x}</code>	% new
<code>\ce{NO_{x}}</code>	% old
<code>\ce{NO_x}</code>	% new
<code>\ce{cis-[PtCl2(NH3)2]}</code>	% old
<code>\ce{\mathit{cis}-[PtCl2(NH3)2]}</code>	% new

for HTML output: 1 \LWR@ProvidesPackagePass{mhchem}

The original definition of \ce:

```
2 \LetLtxMacro{\LWR@mhchem@origce}{\ce}
```

The new definition, called from the new \ce after math shift is set. The starred lateximage uses a hashed filename for the SVG image. The alt tag is set to the **mhchem** expression.

```
3 \newcommand{\LWR@mhchem@HTML@ce}[1]{%
4 \begin{lateximage}*[\\textbackslash{}ce\\{\LWR@HTMLsanitize{#1}\\}]%
5 \LWR@mhchem@origce{#1}%
6 \end{lateximage}%
7 \endgroup%
8 \addtocounter{\LWR@mhchem@cedepth}{-1}%
9 }
```

Only set math shift if outer depth:

```
10 \newcounter{\LWR@mhchem@cedepth}
11 \setcounter{\LWR@mhchem@cedepth}{0}
```

The new \ce. Sets math shift then continues.

```
12 \renewcommand{\ce}{%
13 \begingroup%
14 \ifnumequal{\value{\LWR@mhchem@cedepth}}{0}{%
15   \catcode`\$=3% math shift
16 }{%
17 \addtocounter{\LWR@mhchem@cedepth}{1}%
18 \LWR@mhchem@HTML@ce%
19 }}
```

The original definition of \cesplit:

```
20 \LetLtxMacro{\LWR@mhchem@origcesplit}{\cesplit}
```

The new definition, called from the new \cesplit after math shift is set. The starred lateximage uses a hashed filename for the SVG image. The alt tag is set to the **mhchem** expression.

```
21 \newcommand*{\LWR@mhchem@HTML@cesplit}[2]
22 {%
23 \begin{lateximage}*[\\textbackslash{}cesplit\\{\LWR@HTMLsanitize{#2}\\}]%
24 \LWR@mhchem@origcesplit{#1}{#2}%
25 \end{lateximage}%
26 \endgroup%
27 }
```

Only set math shift if outer depth:

```
28 \newcounter{LWR@mhchem@cesplitdepth}
29 \setcounter{LWR@mhchem@cesplitdepth}{0}
```

The new `\cesplit`. Sets math shift then continues.

```
30 \renewcommand{\cesplit}{%
31 \begingroup%
32 \ifnumequal{\value{LWR@mhchem@cesplitdepth}}{0}{%
33   \catcode`\$=3% math shift
34 }{}%
35 \addtocounter{LWR@mhchem@cesplitdepth}{1}%
36 \LWR@mhchem@HTML@cesplit%
37 }
```

Resore originals inside a `lateximage`:

```
38 \appto\LWR@restoreorigformatting{%
39 \LetLtxMacro{\ce}{\LWR@mhchem@origce}%
40 \LetLtxMacro{\cesplit}{\LWR@mhchem@origcesplit}%
41 }
```

File 191 `l warp-microtype.sty`

§ 284 Package **microtype**

(Emulates or patches code by R SCHLICHT.)

Pkg `microtype` **microtype** is pre-loaded by **l warp**. All user options and macros are ignored and disabled.

for HTML output: Discard all options for **l warp-microtype**:

```
1 \LWR@ProvidesPackageDrop{microtype}

2 \DeclareDocumentCommand{\DeclareMicrotypeSet}{o m m} {}
3 \DeclareDocumentCommand{\UseMicrotypeSet}{o m} {}
4 \DeclareDocumentCommand{\DeclareMicrotypeSetDefault}{o m} {}
5 \DeclareDocumentCommand{\SetProtrusion}{o m m} {}
6 \DeclareDocumentCommand{\SetExpansion}{o m m} {}
7 \DeclareDocumentCommand{\SetTracking}{o m m} {}
8 \DeclareDocumentCommand{\SetExtraKerning}{o m m} {}
9 \DeclareDocumentCommand{\SetExtraSpacing}{o m m} {}
10 \DeclareDocumentCommand{\DisableLigatures}{o m} {}
11 \DeclareDocumentCommand{\DeclareCharacterInheritance}{o m m} {}
12 \DeclareDocumentCommand{\DeclareMicrotypeVariants}{m} {}
```

```

13 \DeclareDocumentCommand{\DeclareMicrotypeAlias}{m m} {}
14 \DeclareDocumentCommand{\LoadMicrotypeFile}{m} {}
15 \DeclareDocumentCommand{\DeclareMicrotypeBabelHook}{m m} {}
16 \DeclareDocumentCommand{\microtypsetup}{m} {}
17 \DeclareDocumentCommand{\microtypecontext}{m} {}
18 \DeclareDocumentCommand{\textmicrotypecontext}{m m}{#2}
19 \Ifpackageloaded{letterspace}{\let\MT@textls\relax}{%
20 \DeclareDocumentCommand{\lsstyle}{}{}}
21 \DeclareDocumentCommand{\textls}{o +m} {}
22 \DeclareDocumentCommand{\lslig}{m}{#1}
23 }
24 \def\DeclareMicrotypeSet#1{\gobbletwo}
25 \def\DeclareMicrotypeVariants#1{\gobble}
26 \onlypreamble\DeclareMicrotypeSet
27 \onlypreamble\UseMicrotypeSet
28 \onlypreamble\DeclareMicrotypeSetDefault
29 \onlypreamble\DisableLigatures
30 \onlypreamble\DeclareMicrotypeVariants
31 \onlypreamble\DeclareMicrotypeBabelHook

```

File 192 **l warp-midfloat.sty**§ 285 Package **midfloat***(Emulates or patches code by SIGITAS TOLUŠIS.)*Pkg **midfloat** **midfloat** is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{midfloat}

2 \newenvironment{strip}[1] [] {} {}
3 \newskip\stripsep

```

File 193 **l warp-midpage.sty**§ 286 Package **midpage**Pkg **midpage** **midpage** is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{midpage}

2 \newenvironment{midpage}
3 {\begin{BlockClass}[\LWR@print@mbox{margin-top:6ex} ; \LWR@print@mbox{margin-bottom:6ex}]{midpa}
4 {\end{BlockClass}}

```

File 194 **l warp-morefloats.sty**

§ 287 Package **morefloats**

Pkg **morefloats** **morefloats** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{morefloats}

File 195 **l warp-moreverb.sty**

§ 288 Package **moreverb**

(Emulates or patches code by ROBIN FAIRBAIRNS.)

Pkg **moreverb** **moreverb** is supported with some patches.

for HTML output:

```
1 \begin{warpHTML}
2 \LWR@ProvidesPackagePass{moreverb}
3 \BeforeBeginEnvironment{verbatimtab}{%
4 \LWR@forcenewpage
5 \LWR@atbeginverbatim{3}{Verbatim}%
6 }
7 \AfterEndEnvironment{verbatimtab}{%
8 \LWR@afterendverbatim{1}%
9 }
10
11
12 \LetLtxMacro{\LWRMV@orig}{\verbatimtabinput}\@verbatimtabinput
13
14 \renewcommand{\@verbatimtabinput}[2][]{%
15 \LWR@forcenewpage
16 \LWR@atbeginverbatim{3}{Verbatim}%
17 \LWRMV@orig{\verbatimtabinput[\#1]{\#2}}%
18 \LWR@afterendverbatim{1}%
19 }
20
21 \BeforeBeginEnvironment{listing}{%
22 \LWR@forcenewpage
23 \LWR@atbeginverbatim{3}{programlisting}%
24 }
```

```
25
26 \AfterEndEnvironment{listing}{%
27 \LWR@afterendverbatim{1}%
28 }
29
30 \BeforeBeginEnvironment{listingcont}{%
31 \LWR@forcenewpage
32 \LWR@atbeginverbatim{3}{programlisting}%
33 }
34
35 \AfterEndEnvironment{listingcont}{%
36 \LWR@afterendverbatim{1}%
37 }

38 \LetLtxMacro{\LWRMV@@listinginput}{\listinginput}
39
40 \renewcommand{\@listinginput}[3][]{%
41 \LWR@forcenewpage
42 \LWR@atbeginverbatim{3}{programlisting}%
43 \LWRMV@@listinginput[#1]{#2}{#3}%
44 \LWR@afterendverbatim{1}%
45 }
46
47
48 \renewenvironment*{boxedverbatim}{%
49 {
50 \LWR@forcenewpage
51 \LWR@atbeginverbatim{3}{boxedverbatim}%
52 \verbatim{%
53 }
54 {
55 \endverbatim{%
56 \LWR@afterendverbatim{1}%
57 }

58 \end{warpHTML}
```

File 196 **l warp-morewrites.sty**

§ 289 Package **morewrites**

Pkg **morewrites** Error if **morewrites** is loaded after **l warp**.

Discard all options for **l warp-morewrites**:

for HTML output: 1 \LWR@ProvidesPackageDrop{morewrites}

```
2 \LWR@loadbefore{morewrites}
```

File 197 **l warp-mparhack.sty**

§ 290 Package **mparhack**

Pkg **mparhack** Ignored.

for HTML output: Discard all options for **l warp-mparhack**:

```
1 \LWR@ProvidesPackageDrop{mparhack}
```

File 198 **l warp-multicol.sty**

§ 291 Package **multicol**

(Emulates or patches code by FRANK MITTELBACH.)

Pkg **multicol** **multicol** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{multicol}[2015/09/13]

Multicols are converted into a 1-3 column display, browser-supported.

The optional multicols heading is placed inside a <div> of class `multicolsheading`.

The content is placed inside a <div> of class `multicols`.

```
2 \begin{warpHTML}
```

Env **multicols** * {<numcols>} [<heading>]
3 \NewDocumentEnvironment{multicols}{s m o}

HTML <div> class to contain everything:

```
4 {  
5 \LWR@forcenewpage  
6 \BlockClass{multicols}
```

Optional HTML <div> class for the heading:

```
7 \IfValueT{#3}{\begin{BlockClass}{multicolsheading}#3\end{BlockClass}}
```

When done with the environment, close the <div>:

```
8 {\endBlockClass}
```

Emulated null functions which are not used in HTML:

```

9 \newcommand*\{\columnbreak\}{}%
10 \newcommand*\{\RLmulticolcolumns\}{}%
11 \newcommand*\{\LRmulticolcolumns\}{}%
12
13 \newlength{\premulticols}%
14 \newlength{\postmulticols}%
15 \newlength{\multicolssep}%
16 \newlength{\multicolbaselineskip}%
17 \newlength{\multicoltolerance}%
18 \newlength{\multicolpretolerance}%
19 \newcommand*\{\columnseprulecolor}{\normalcolor}%
20 \newcounter{columnbadness}%
21 \newcounter{finalcolumnbadness}%
22 \newcounter{collectmore}%
23 \newcounter{unbalance}%
24 \newlength{\multicolovershoot}%
25 \newlength{\multicolundershoot}%

26 \end{warpHTML}

```

File 199 **l warp-multirow.sty**

§ 292 Package **multirow**

(Emulates or patches code by PIET VAN OOSTRUM, ØYSTEIN BACHE, JERRY LEICHTER.)

Pkg **multirow** **multirow** is emulated during HTML output, and used as-is while inside a `\textrimage`.

In a `\textrimage`, the original print-mode versions are temporarily restored by `\LWR@restoreorigformatting`.

See section 69.23 for the print-mode versions.

for HTML output: Remove the placeholder macro which was used if **multirow** was not loaded:

```

1 \LetLtxMacro\multirow\relax
2 \LWR@ProvidesPackagePass{multirow}

```

`\LWR@multirowborder` Set to `left` or `right` to create a thick border for the cell, for use by **bigdelim**:

```
3 \newcommand{\LWR@multirowborder}{}%
```

§ 292.1 Multirow

```
\multirow  [<vpos>] {[<numrows>]} [<bigstruts>] {[<width>]} [<fixup>] {[<text>]}

4 \NewDocumentCommand{\LWR@HTML@multirow}{O{c} m o m o +m}%
5 {%
6 \LWR@traceinfo{*** LWR@HTML@multirow #1 #2 #4}%
7 \LWR@maybenewtablerow%
8 \LWR@tabularleftedge%
```

Print the start of a new table data cell:

```
9 \LWR@htmltag{td rowspan="#2" %
```

The vertical alignment, if given:

```
10 \IfValueT{#1}{%
11 \ifstrequal{#1}{b}{style="\LWR@print@mbox{vertical-align:bottom}" }{}%
12 \ifstrequal{#1}{t}{style="\LWR@print@mbox{vertical-align:top}" }{}%
13 }%
```

The left/right border, if given:

```
14 \ifdefvoid{\LWR@multirowborder}{}{%
15 style="\LWR@print@mbox{border-\LWR@multirowborder:} 2px dotted black ; %
16 \LWR@print@mbox{padding-\LWR@multirowborder:} 2px" %
17 }%
```

A class adds the column spec and the rule:

```
18 class="td%"
```

Append this column's spec:

```
19 \LWR@getexparray{\LWR@tablecolspecl}{\arabic{\LWR@tableLaTeXcolindex}}%
```

If this column has a cmidrule, add “rule” to the end of the HTML class tag. Also add the vertical bar class.

```
20 \LWR@addcmidruletrim%
21 \LWR@addleftmostbartag%
22 \LWR@printbartag{\arabic{\LWR@tableLaTeXcolindex}}%
23 "%

24 \LWR@tdstartstyles%
25 \LWR@addcmidrulewidth%
26 \LWR@addcdashline%
```

```
27 \LWR@addtabularrulecolors%
28 \LWR@tdendstyles%
29 }%
```

The column's < spec:

```
30 \LWR@getexpparray{\LWR@colbeforespec}{\arabic{\LWR@tableTeXcolindex}}%
```

While printing the text, redefine \\ to generate a new line

```
31 \begingroup\LetLtxMacro{\\\}{\LWR@endofline}#6\endgroup%
32 \LWR@stoppars%
33 \global\boolearnfalse{\LWR@intabularmetadata}%
34 \renewcommand{\LWR@multirowborder}{}%
35 \LWR@traceinfo{*** \LWR@HTML@multirow done}%
36 }%
37
38 \LWR@formattted{multirow}
```

§ 292.2 Combined multicolumn and multirow

⚠ `\multicolumn &` `\multirow` **l warp** does not support directly combining `\multicolumn` and `\multirow`. Use `\multicolumnrow` instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}
```

The two arguments for `\multicolumn` come first, followed by the five arguments for `\multirow`, many of which are optional, followed by the contents.

- ⚠ **skipped cells** As per `\multirow`, skipped cells to the right of the `\multicolumnrow` statement are not included in the source code on the same line. On the following lines, `\mcolrowcell` must be used for each cell of each column and each row to be skipped:
- ⚠ **empty cells**

```
... & \multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text} & ...
... & \mcolrowcell & \mcolrowcell & ...
... & \mcolrowcell & \mcolrowcell & ...
```

vposn Note that recent versions of `multirow` include a new optional `vposn` argument.

```
\multicolumnrow {\{1:cols\}} {\{2:halign\}} [\{3:vpos\}] {\{4:numrows\}} [\{5:bigstruts\}] {\{6:width\}} [\{7:fixup\}]
{\{8:text\}}
```

`\@ifpackageloaded{multirow}` determines if v2.0 or later of `multirow` was used, which included the `\ProvidesPackage` macro.

The `HTML` version follows.

\AtBeginDocument because the print version had to see if **multirow** was loaded before determining how to define \LWR@print@multicolumnrow.

```
39 \AtBeginDocument{%
40
41 \NewExpandableDocumentCommand{\LWR@HTML@multicolumnrow}{m m O{} m O{} m O{} +m}{%
```

Figure out how many extra HTML columns to add for @ and ! columns:

```
42 \LWR@tabularhtmlcolumns{\arabic{LWR@tableLaTeXcolindex}}{#1}
```

Create the multicolumn/multirow tag:

```
43 \begingroup%
44 \LetLtxMacro{\LWR@endofline}{%
45 \LWR@domulticolumn[#3][#4]{#1}{\arabic{LWR@tabhtmlcoltotal}}{#2}{#8}}%
46 \endgroup%
```

Move to the next L^AT_EX column:

```
47 \addtocounter{LWR@tableLaTeXcolindex}{#1}%
48 \addtocounter{LWR@tableLaTeXcolindex}{-1}%
```

Skip any trailing @ or ! columns for this cell:

```
49 \global\booltrue{\LWR@skipatbang}%
50 }%
51
52 \LWR@expandableformatted{multicolumnrow}%
53
54 }% \AtBeginDocument
```

File 200 lwarf-multitoc.sty

§ 293 Package **multitoc**

Pkg **multitoc** **multitoc** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{multitoc}

```
2 \newcommand{\multicolumntoc}{2}
3 \newcommand{\multicolumnlot}{2}
4 \newcommand{\multicolumnlof}{2}
5 \newcommand*{\immediateaddtocontents}[2]{}%
```

File 201 **l warp-nameref.sty**

§ 294 Package **nameref**

Pkg **nameref** **nameref** is emulated by **l warp**.

for HTML output: Discard all options for **l warp-nameref**:

```
1 \typeout{Using the l warp html version of package 'nameref', discarding options.}
2 \typeout{    Are not using ProvidesPackage, so that other packages}
3 \typeout{    do not attempt to patch l warp's version of 'nameref'.}
4 \DeclareOption*{}
5 \ProcessOptions\relax
```

File 202 **l warp-natbib.sty**

§ 295 Package **natbib**

(Emulates or patches code by PATRICK W. DALY.)

Pkg **natbib** **natbib** is patched for use by **l warp**.

for HTML output: 1 \LWR@ProvidesPackagePass{natbib}

Replace math < and > with \textless and \textgreater:

A macro to compare:

```
2 \newcommand{\LWRNB@NAT@open}{\textless}
```

To patch \NAT@open and \NAT@close

```
3 \newcommand{\LWRNB@patchnatbibopenclose}{
4 \ifdef\streq{\NAT@open}{\LWRNB@NAT@open}
5 {
6     \renewcommand{\NAT@open}{\textless}
7     \renewcommand{\NAT@close}{\textgreater}
8 }
9 }
```

Do it now in case angle was selected as an option:

```
10 \LWRNB@patchnatbibopenclose
```

Also patch `\setcitestyle` to patch after settings are made:

```

11 \let\LWRNB@origsetcitestyle\setcitestyle
12
13 \renewcommand{\setcitestyle}[1]{%
14 \LWRNB@origsetcitestyle{#1}%
15 \LWRNB@patchnatbibopenclose%
16 }
```

File 203 **l warp-nccfancyhdr.sty**

§ 296 Package **nccfancyhdr**

(Emulates or patches code by ALEXANDER I. ROZHENKO.)

Pkg **nccfancyhdr** **nccfancyhdr** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{nccfancyhdr}

```

2 \newcommand*\headrulewidth{0pt}
3 \newcommand*\footrulewidth{0pt}
4 \newcommand{\headstrutheight}{0pt}
5 \newcommand{\footstrutheight}{0pt}
6 \newcommand*\headrule[1]{\hrule height #1}
7 \newcommand*\footrule[1]{\hrule height #1}
8
9 \newdimen\headwidth
10 \newcommand*\extendedheaders{0pt}
11 \newcommand*\normalheaders{0pt}
12
13 \newcommand*\fancyhead[2][]{\def\@fancyhead##1##2{\def\@fancyhead{##1##2}}}
14 \newcommand*\fancyfoot[2][]{\def\@fancyfoot##1##2{\def\@fancyfoot{##1##2}}}
15 \newcommand*\fancyhf[2][]{\def\@fancyhf##1##2{\def\@fancyhf{##1##2}}}
16 \newcommand*\fancypagestyle[2][]{\def\@fancypagestyle##1##2{\def\@fancypagestyle{##1##2}}}
17 \newcommand*\lhead[2][]{\def\@lhead##1##2{\def\@lhead{##1##2}}}
18 \newcommand*\chead[2][]{\def\@chead##1##2{\def\@chead{##1##2}}}
19 \newcommand*\rhead[2][]{\def\@rhead##1##2{\def\@rhead{##1##2}}}
20 \newcommand*\lfoot[2][]{\def\@lfoot##1##2{\def\@lfoot{##1##2}}}
21 \newcommand*\cfoot[2][]{\def\@cfoot##1##2{\def\@cfoot{##1##2}}}
22 \newcommand*\rfoot[2][]{\def\@rfoot##1##2{\def\@rfoot{##1##2}}}
23
24 \newcommand{\nouppercase}[1]{\def\@nouppercase{#1}}
25
26 \NewDocumentCommand{\fancycenter}{o o m m m}{\def\@fancycenter{#1#2#3#4#5}}
27
28 \NewDocumentCommand{\newpagestyle}{m o m}{\def\@newpagestyle{#1#2#3}}
```

```
30 \newcommand*{\iffloatpage}[2]{#2}
31 \newcommand*{\ifftopfloat}[2]{#2}
32 \newcommand*{\iffbotfloat}[2]{#2}
```

File 204 **l warp-needspace.sty**

§ 297 Package **needspace**

(Emulates or patches code by PETER WILSON.)

Pkg **needspace** **needspace** is not used during HTML conversion.

for HTML output: Discard all options for **l warp-needspace**:

```
1 \LWR@ProvidesPackageDrop{needspace}
2
3 \DeclareDocumentCommand{\needspace}{m}{}
4 \DeclareDocumentCommand{\Needspace}{s m}{}
```

File 205 **l warp-newinclude.sty**

§ 298 Package **newinclude**

Pkg **newinclude** Error if **newinclude** is loaded after **l warp**.

Discard all options for **l warp-newinclude**:

for HTML output: 1 \LWR@ProvidesPackageDrop{newinclude}
 2 \LWR@loadbefore{newinclude}

File 206 **l warp-newunicodechar.sty**

§ 299 Package **newunicodechar**

Pkg **newunicodechar** Error if **newunicodechar** is loaded after **l warp**.

Discard all options for **l warp-newunicodechar**:

for HTML output: 1 \LWR@ProvidesPackageDrop{newunicodechar}
 2 \LWR@loadbefore{newunicodechar}

File 207 **l warp-nextpage.sty**

§ 300 Package **nextpage**

(Emulates or patches code by PETER WILSON.)

Pkg **nextpage** **nextpage** is nullified.

for HTML output: Discard all options for **l warp-nextpage**.

```
1 \LWR@ProvidesPackageDrop{nextpage}
2 \DeclareDocumentCommand{\cleartoevenpage}{o}{}
3 \DeclareDocumentCommand{\movetoevenpage}{o}{}
4 \DeclareDocumentCommand{\cleartooddpage}{o}{}
5 \DeclareDocumentCommand{\movetooddpage}{o}{}
```

File 208 **l warp-nicefrac.sty**

§ 301 Package **nicefrac**

(Emulates or patches code by AXEL REICHERT.)

Pkg **nicefrac** **nicefrac** is patched for use by **l warp**.

for HTML output: 1 \LWR@ProvidesPackagePass{nicefrac}[1998/08/04]

nicefrac uses \TeX boxes, so @ensuredmath must be restored temporarily:

```
2 \LetLtxMacro{\LWR@origUnitsNiceFrac}{\@UnitsNiceFrac}
3
4 \DeclareRobustCommand*{\@UnitsNiceFrac}[3][]{%
5 \begingroup%
6 \LetLtxMacro{\@ensuredmath}{\LWR@origensuredmath}%
7 \LWR@origUnitsNiceFrac[#1]{#2}{#3}%
8 \endgroup%
9 }
```

For Mathjax:

```
10 \CustomizeMathJax{\newcommand{\nicefrac}[3][]{#2/#3}}
```

File 209 **l warp-nonfloat.sty**

§ 302 Package **nonfloat**

(Emulates or patches code by KAI RASCHER.)

Pkg **nonfloat** **nonfloat** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{nonfloat}

2 \LetLtxMacro\topcaption\caption
3 \newcommand{\figcaption}{\def\@capttype{figure}\caption}
4 \newcommand{\tabcaption}{\def\@capttype{table}\topcaption}
5 \newenvironment{narrow}[2]{}{}

File 210 **l warp-nonumonpart.sty**

§ 303 Package **nonumonpart**

Pkg **nonumonpart** **nonumonpart** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{nonumonpart}

File 211 **l warp-nopageno.sty**

§ 304 Package **nopageno**

Pkg **nopageno** **nopageno** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{nopageno}

File 212 **l warp-nowidow.sty**

§ 305 Package **nowidow**

(Emulates or patches code by RAPHAËL PINSON.)

Pkg nowidow **nowidow** is not used during HTML conversion.

Discard all options for **l warp-nowidow**:

for HTML output: 1 \LWR@ProvidesPackageDrop{nowidow}

```
\nowidow  [<lines>]
\setnowidow [<lines>
              2 \newcommand*{\nowidow}[1] []
              3 \newcommand*{\setnowidow}[1] []

\noclub  [<lines>]
\setnoclub [<lines>
              4 \newcommand*{\noclub}[1] []
              5 \newcommand*{\setnoclub}[1] []]
```

File 213 **l warp-ntheorem.sty**

§ 306 Package **ntheorem**

(Emulates or patches code by WOLFGANG MAY, ANDREAS SCHEDLER.)

Pkg ntheorem **ntheorem** is patched for use by **l warp**.

Table 14: Ntheorem package — CSS styling of theorems and proofs

Theorem: <div> of class theorembody<theoremstyle>

Theorem Header: of class theoremheader<style>

where <theoremstyle> is plain, break, etc.

§ 306.1 Limitations

⚠ **Font control** This conversion is not total. Font control is via css, and the custom L^AT_EX font settings are ignored.

⚠ **Equation numbering** **ntheorem** has a bug with equation numbering in *AMS* environments when the option `thref` is used. **l warp** does not share this bug, so equations with `\split`, etc, are numbered correctly with **l warp**'s HTML output, but not with the print output. It is recommended to use `cleveref` instead of **ntheorem**'s `thref` option.

§ 306.2 Options

Options `amsthm` or `standard` choose which set of theorems and proofs to initialize.

 **Disabled options** The options `thmmarks` and `amsmath` are disabled, since they heavily modify the underlying math code. Theorem marks are emulated. The AMS-math modifications are not done.

Option `thref` is disabled because `cleveref` functions are used instead. `\thref` is emulated.

Option `hyperref` is disabled because `l warp` emulated `hyperref`.

Some disabled options:

```

1 \DeclareOption{thref}={}
2
3
4 \newbool{LWR@ntheoremmarks}
5 \boolfalse{LWR@ntheoremmarks}
6
7 \DeclareOption{thmmarks}{
8 \booltrue{LWR@ntheoremmarks}
9 \newif\ifsetendmark\setendmarktrue
10 }
11
12
13 \newbool{LWR@ntheoremamsthm}
14 \boolfalse{LWR@ntheoremamsthm}
15
16 \DeclareOption{amsthm}{\booltrue{LWR@ntheoremamsthm}}
17
18
19 \DeclareOption{amsmath}{}
20 \DeclareOption{hyperref}{}
21
22 \LWR@ProvidesPackagePass{ntheorem}
```

§ 306.3 Remembering the theorem style

Storage for the style being used for new theorems.

```

23 \newcommand{\LWR@newtheoremstyle}[plain]
24 \AtBeginDocument{
25 @ifpackageloaded{cleveref}{
26 \gdef\@thm#1#2#3{%
27   \if@thmmarks
28     \stepcounter{end}\InTheoType{ctr}%
29   \fi
30 }
```

```

30   \renewcommand{\InTheoType}{#1}%
31   \if@thmmarks
32     \stepcounter{curr#1ctr}%
33     \setcounter{end#1ctr}{0}%
34   \fi
35   \refstepcounter[#1]{#2}%
36   \theorem@prework
37   \LWR@forcenewpage% l warp
38   \BlockClass{theorembody#1}%
39   \trivlist %
40   \ifuse@newframeskips % cf. latex.ltx for topsepadd: \@trivlist
41     \ifthm@inframe
42       \thm@topsep\theoreminframepreskipamount
43       \thm@topsepadd\theoreminframepostskipamount
44     \else
45       \thm@topsep\theorempreskipamount
46       \thm@topsepadd\theorempostskipamount
47     \fi
48   \else% oldframeskips
49     \thm@topsep\theorempreskipamount
50     \thm@topsepadd \theorempostskipamount
51     \ifvmode\advance\thm@topsepadd\partopsep\fi
52   \fi
53   \@topsep\thm@topsep
54   \@topsepadd\thm@topsepadd
55   \advance\linewidth -\theorem@indent
56   \advance\linewidth -\theorem@rightindent
57   \advance\@totalleftmargin \theorem@indent
58   \parshape \one \@totalleftmargin \linewidth
59   \@ifnextchar[{\@ythm{#1}{#2}{#3}}{\@xthm{#1}{#2}{#3}}
60 }
61 }% not @ifpackageloading{cleveref}
62 \gdef\@thm#1#2#3{%
63   \if@thmmarks
64     \stepcounter{end\InTheoType ctr}%
65   \fi
66   \renewcommand{\InTheoType}{#1}%
67   \if@thmmarks
68     \stepcounter{curr#1ctr}%
69     \setcounter{end#1ctr}{0}%
70   \fi
71   \refstepcounter{#2}%
72   \theorem@prework
73   \LWR@forcenewpage% l warp
74   \BlockClass{theorembody#1}%
75   \trivlist %
76   \ifuse@newframeskips % cf. latex.ltx for topsepadd: \@trivlist
77     \ifthm@inframe
78       \thm@topsep\theoreminframepreskipamount
79       \thm@topsepadd\theoreminframepostskipamount

```

```

80      \else
81          \thm@topsep\theorempreskipamount
82          \thm@topsepadd\theorempostskipamount
83      \fi
84  \else% oldframeskips
85      \thm@topsep\theorempreskipamount
86      \thm@topsepadd \theorempostskipamount
87      \ifvmode\advance\thm@topsepadd\partopsep\fi
88  \fi
89  \c@topsep\thm@topsep
90  \c@topsepadd\thm@topsepadd
91  \advance\linewidth -\theorem@indent
92  \advance\linewidth -\theorem@rightindent
93  \advance\c@totalleftmargin \theorem@indent
94  \parshape \c@ne \c@totalleftmargin \linewidth
95  \c@ifnextchar[{\c@ythm{\#1}{\#2}{\#3}}{\c@xthm{\#1}{\#2}{\#3}}
96 }
97 }
98 }% AtBeginDocument

```

Patched to remember the style being used for new theorems:

```

99 \gdef\theoremstyle#1{%
100     \c@ifundefined{th@#1}{\@warning
101         {Unknown theoremstyle '#1'. Using 'plain')}%
102         \theorem@style{plain}
103         \renewcommand{\LWR@newtheoremstyle}{plain}%
104     }%
105     {
106         \theorem@style{#1}
107         \renewcommand{\LWR@newtheoremstyle}{#1}%
108     }%
109 }

```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```

110
111 \gdef\c@xthm#1#2[#3]{%
112     \ifthm@tempif
113         \csedef{\LWR@thmstyle#1}{\LWR@newtheoremstyle}%
114         \expandafter\c@ifundefined{c@#1}%
115             {\c@definecounter{#1}}%
116             \c@newctr{#1}[#3]%
117             \expandafter\xdef\c@sectionname{the#1}\endcsname{%
118                 \expandafter\noexpand\c@sectionname{the#3}\endcsname \c@thmcOUNTERsep
119                 {\noexpand\c@sectionname{\the\theoremnumbering}\endcsname{#1}}}%
120             \expandafter\gdef\c@sectionname{mkheader@#1}\endcsname
121                 {\c@sectionname{setparms@#1}\endcsname}

```

```
122      \@thm{\#1}{\#1}{\#2}
123      }%
124      \global\@namedef{end#1}{\@endtheorem}
125      \AtBeginEnvironment{\#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}\% l warp
126      \fi
127 }
128
129 \gdef\@ynthm#1#2{%
130   \ifthm@tempif
131     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}\% l warp
132     \expandafter\@ifundefined{c@#1}%
133       {\@definecounter{#1}}%
134     \expandafter\xdef\csname the#1\endcsname
135       {\noexpand\csname the\theoremnumbering\endcsname{#1}}%
136     \expandafter\gdef\csname mkheader@#1\endcsname
137       {\csname setparms@#1\endcsname
138        \@thm{\#1}{\#1}{\#2}
139        }%
140     \global\@namedef{end#1}{\@endtheorem}
141     \AtBeginEnvironment{\#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}\% l warp
142   \fi
143 }
144
145 \gdef\@othm#1[#2]#3{%
146   \@ifundefined{c@#2}{\@nocounterr{#2}}%
147   \ifthm@tempif
148     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}\% l warp
149     \global\@namedef{the#1}{\@nameuse{the#2}}%
150     \expandafter\protected@xdef\csname num@addtheoremline#1\endcsname{%
151       \noexpand\@num@addtheoremline{#1}{#3}}%
152     \expandafter\protected@xdef\csname nonum@addtheoremline#1\endcsname{%
153       \noexpand\@nonum@addtheoremline{#1}{#3}}%
154     \theoremkeyword{#3}%
155     \expandafter\protected@xdef\csname #1Keyword\endcsname
156       {\the\theoremkeyword}%
157     \expandafter\gdef\csname mkheader@#1\endcsname
158       {\csname setparms@#1\endcsname
159        \@thm{\#1}{\#2}{\#3}
160        }%
161     \global\@namedef{end#1}{\@endtheorem}
162     \AtBeginEnvironment{\#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}\% l warp
163   \fi}
164 }
```

§ 306.4 HTML cross-referencing

Mimics a float by incrementing the float counter and generating an HTML anchor. These are used for list-of-theorem cross-references.

```

165 \newcommand{\LWR@inctheorem}{%
166   \addtocounter{LWR@thisautoid}{1}%
167   \LWR@stoppars%
168   \LWR@htmlltag{a id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}"}\LWR@htmlltag{/a}%
169   \LWR@startpars%
170 }

```

§ 306.5 \newtheoremstyle

The following are patched for css.

These were in individual files thp.sty for plain, thmb.sty for margin break, etc. They are gathered together here.

Each theorem is encased in a BlockClass environment of class theorembody<style>.

Each header is encased in an \InlineClass of class theoremheader<style>.

```

171 \gdef\newtheoremstyle#1#2#3{%
172   \expandafter\@ifundefined{th@#1}%
173   {\expandafter\gdef\csname th@#1\endcsname{%
174     \def\@begintheorem####1#####2{%
175       \LWR@inctheorem% l warp
176       #2}%
177       \def\@opargbegintheorem####1#####2#####3{%
178         \LWR@inctheorem% l warp
179         #3}%
180     }%
181   }%
182 {\PackageError{\basename}{Theorem style #1 already defined}\@eha}%
183 }

```

§ 306.6 Standard styles

```

184 \renewtheoremstyle{plain}%
185   {\item[
186     \InlineClass{theoremheaderplain}{##1\ ##2\theorem@separator}]%
187   {\item[
188     \InlineClass{theoremheaderplain}{##1\ ##2\ (##3)\theorem@separator}]}
189
190 \renewtheoremstyle{break}%
191   {\item[
192     \InlineClass{theoremheaderbreak}{##1\ ##2\theorem@separator}\newline
193   ]}%

```

```
194  {\item[
195    \InlineClass{theoremheaderbreak}%
196    {##1\ ##2\ (##3)\theorem@separator}\newline
197  ]}
198
199 \renewtheoremstyle{change}%
200  {\item[
201    \InlineClass{theoremheaderchange}{##2\ ##1\theorem@separator}]}%
202  {\item[
203    \InlineClass{theoremheaderchange}{##2\ ##1\ (##3)\theorem@separator}]}%
204
205 \renewtheoremstyle{changebreak}%
206  {\item[
207    \InlineClass{theoremheaderchangebreak}%
208    {##2\ ##1\theorem@separator}\newline
209  ]}%
210  {\item[
211    \InlineClass{theoremheaderchangebreak}%
212    {##2\ ##1\ (##3)\theorem@separator}\newline
213  ]}%
214
215 \renewtheoremstyle{margin}%
216  {\item[
217    \InlineClass{theoremheadermargin}{##2 \qquad ##1\theorem@separator}%
218  ]}%
219  {\item[
220    \InlineClass{theoremheadermargin}{##2 \qquad ##1\ (##3)\theorem@separator}%
221  ]}%
222
223 \renewtheoremstyle{marginbreak}%
224  {\item[
225    \InlineClass{theoremheadermarginbreak}%
226    {##2 \qquad ##1\theorem@separator}\newline
227  ]}%
228  {\item[
229    \InlineClass{theoremheadermarginbreak}%
230    {##2 \qquad ##1\ (##3)\theorem@separator}\newline
231  ]}%
232
233 \renewtheoremstyle{nonumberplain}%
234  {\item[
235    \InlineClass{theoremheaderplain}{##1\theorem@separator}]}%
236  {\item[
237    \InlineClass{theoremheaderplain}{##1\ (##3)\theorem@separator}]}%
238
239 \renewtheoremstyle{nonumberbreak}%
240  {\item[
241    \InlineClass{theoremheaderbreak}{##1\theorem@separator}\newline
242  ]}%
243  {\item[
```

```

244     \InlineClass{theoremheaderbreak}{##1\ (###3)\theorem@separator}\newline
245     ]}
246
247 \renewtheoremstyle{empty}%
248   {\item[]}%
249   {\item[
250     \InlineClass{theoremheaderplain}{##3}]}
251
252 \renewtheoremstyle{emptybreak}%
253   {\item[]}%
254   {\item[
255     \InlineClass{theoremheaderplain}{##3}] \ \newline}

```

§ 306.7 Additional objects

The following manually adjust the css for the standard configuration objects which are not a purely plain style:

```
256 \ifbool{LWR@ntheoremamsthm}{}{%
```

Upright text via CSS:

```

257   \newtheoremstyle{plainupright}%
258   {\item[
259     \InlineClass{theoremheaderplain}{##1\ ##2\theorem@separator}]}%
260   {\item[
261     \InlineClass{theoremheaderplain}{##1\ ##2\ (###3)\theorem@separator}}]

```

Upright text and small caps header via CSS:

```

262   \newtheoremstyle{nonumberplainuprightsc}%
263   {\item[
264     \InlineClass{theoremheadersc}{##1\theorem@separator}]}%
265   {\item[
266     \InlineClass{theoremheadersc}{##1\ (###3)\theorem@separator}}]
267 }% not amsthm

```

§ 306.8 Renewed standard configuration

The following standard configuration is renewed using the new css:

```
268 \ifbool{LWR@ntheoremamsthm}{}{%
```

```

269 \ifx\thm@usestd@\undefined
270 \else
271   \theoremnumbering{arabic}
272   \theoremstyle{plain}
273   \RequirePackage{latexsym}

```

```
274 \theoremsymbol{\Box}
275 \theorembodyfont{\itshape}
276 \theoremheaderfont{\normalfont\bfseries}
277 \theoremseparator{}
278 \renewtheorem{Theorem}{Theorem}
279 \renewtheorem{theorem}{Theorem}
280 \renewtheorem{Satz}{Satz}
281 \renewtheorem{satz}{Satz}
282 \renewtheorem{Proposition}{Proposition}
283 \renewtheorem{proposition}{Proposition}
284 \renewtheorem{Lemma}{Lemma}
285 \renewtheorem{lemma}{Lemma}
286 \renewtheorem{Korollar}{Korollar}
287 \renewtheorem{korollar}{Korollar}
288 \renewtheorem{Corollary}{Corollary}
289 \renewtheorem{corollary}{Corollary}
290
291 \theoremstyle{plainupright}
292 \theorembodyfont{\upshape}
293 \theoremsymbol{\HTMLUnicode{25A1}}% UTF-8 white box
294 \renewtheorem{Example}{Example}
295 \renewtheorem{example}{Example}
296 \renewtheorem{Beispiel}{Beispiel}
297 \renewtheorem{beispiel}{Beispiel}
298 \renewtheorem{Bemerkung}{Bemerkung}
299 \renewtheorem{bemerkung}{Bemerkung}
300 \renewtheorem{Anmerkung}{Anmerkung}
301 \renewtheorem{anmerkung}{Anmerkung}
302 \renewtheorem{Remark}{Remark}
303 \renewtheorem{remark}{Remark}
304 \renewtheorem{Definition}{Definition}
305 \renewtheorem{definition}{Definition}
306
307 \theoremstyle{nonumberplainuprightsc}
308 \theoremsymbol{\HTMLUnicode{220E}}% UTF-8 end-of-proof
309 \renewtheorem{Proof}{Proof}
310 \renewtheorem{proof}{Proof}
311 \renewtheorem{Beweis}{Beweis}
312 \renewtheorem{beweis}{Beweis}
313 \qedsymbol{\HTMLUnicode{220E}}% UTF-8 end-of-proof
314
315 \theoremsymbol{}
316 \fi
317 }% not amsthm
```

§ 306.9 amsthm option

Only if the `amsthm` option was given:

```

318 \ifbool{LWR@ntheoremamsthm}{
319   \gdef\th@plain{%
320     \def\theorem@headerfont{\normalfont\bfseries}\itshape%
321     \def\@begintheorem##1##2{%
322       \LWR@inctheorem% l warp
323       \item[%
324         \InlineClass{theoremheaderplain}{##1\ ##2.}]
325       ]}%
326     \def\@opargbegintheorem##1##2##3{%
327       \LWR@inctheorem% l warp
328       \item[%
329         \InlineClass{theoremheaderplain}{##1\ ##2\ (###3).}]
330       ]}%
331     ]}%
332   \gdef\th@nonumberplain{%
333     \def\theorem@headerfont{\normalfont\bfseries}\itshape%
334     \def\@begintheorem##1##2{%
335       \LWR@inctheorem% l warp
336       \item[%
337         \InlineClass{theoremheaderplain}{##1.}]
338       ]}%
339     \def\@opargbegintheorem##1##2##3{%
340       \LWR@inctheorem% l warp
341       \item[%
342         \InlineClass{theoremheaderplain}{##1\ (###3).}]
343       ]}%
344     ]}%
345   \gdef\th@definition{%
346     \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
347     \def\@begintheorem##1##2{%
348       \LWR@inctheorem% l warp
349       \item[%
350         \InlineClass{theoremheaderdefinition}{##1\ ##2.}]
351       ]}%
352     \def\@opargbegintheorem##1##2##3{%
353       \LWR@inctheorem% l warp
354       \item[%
355         \InlineClass{theoremheaderdefinition}{##1\ ##2\ (###3).}]
356       ]}%
357     ]}%
358   \gdef\th@nonumberdefinition{%
359     \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
360     \def\@begintheorem##1##2{%
361       \LWR@inctheorem% l warp
362       \item[%
363

```

```
364 \InlineClass{theoremheaderdefinition}{##1.}
365     ]}
366 \def\@opargbegintheorem##1##2##3{%
367     \LWR@intheorem% l warp
368     \item[
369     \InlineClass{theoremheaderdefinition}{##1\ (###3).}
370     ]}
371
372 \gdef\th@remark{%
373     \def\theorem@headerfont{\itshape}\normalfont%
374     \def\@begintheorem##1##2{%
375         \LWR@intheorem% l warp
376         \item[
377         \InlineClass{theoremheaderremark}{##1\ ##2.}
378         ]}
379     \def\@opargbegintheorem##1##2##3{%
380         \LWR@intheorem% l warp
381         \item[
382         \InlineClass{theoremheaderremark}{##1\ ##2\ (###3).}
383         ]}
384
385 \gdef\th@nonumberremark{%
386     \def\theorem@headerfont{\itshape}\normalfont%
387     \def\@begintheorem##1##2{%
388         \LWR@intheorem% l warp
389         \item[
390         \InlineClass{theoremheaderremark}{##1.}
391         ]}
392     \def\@opargbegintheorem##1##2##3{%
393         \LWR@intheorem% l warp
394         \item[
395         \InlineClass{theoremheaderremark}{##1\ (###3).}
396         ]}
397
398 \gdef\th@proof{%
399     \def\theorem@headerfont{\normalfont\bfseries}\itshape%
400     \def\@begintheorem##1##2{%
401         \LWR@intheorem% l warp
402         \item[
403         \InlineClass{theoremheaderproof}{##1.}
404         ]}
405     \def\@opargbegintheorem##1##2##3{%
406         \LWR@intheorem% l warp
407         \item[
408         \InlineClass{theoremheaderproof}{##1\ (###3).}
409         ]}
410
411
412
413 \newcounter{proof}%
```

```

414 \if@thmmarks
415     \newcounter{currproofctr}%
416     \newcounter{endproofctr}%
417 \fi
418
419 \gdef\proofSymbol{\openbox}
420
421 \newcommand{\proofname}{Proof}
422
423 \newenvironment{proof}[1][\proofname]{
424     \th@proof
425     \def\theorem@headerfont{\itshape}%
426     \normalfont
427     \theoremsymbol{\HTMLUnicode{220E}}% UTF-8 end-of-proof
428     \@thm{proof}{proof}{#1}
429 }%
430 {\endtheorem}
431
432 }{}% amsthm option

```

§ 306.10 Ending a theorem

Patched for css:

```

433 \let\LWR@origendtheorem\endtheorem
434 \renewcommand{\endtheorem}{%
435 \ifbool{\LWR@ntheoremmarks}{%
436     \ifsetendmark{%
437         \InlineClass{theoremendmark}{\csname\InTheoType Symbol\endcsname}%
438         \setendmarkfalse%
439     }%
440 }{}%
441 \LWR@origendtheorem% also does \endtrivlist
442 \ifbool{\LWR@ntheoremmarks}{\global\setendmarktrue}{%
443 \endBlockClass%
444 }

```

§ 306.11 \NoEndMark

```
445 \gdef\NoEndMark{\global\setendmarkfalse}
```

§ 306.12 List-of

Redefined to reuse the float mechanism to add list-of-theorem links:

```
\thm@thmline {\langle 1: printed type \rangle} {\langle 2: # \rangle} {\langle 3: optional \rangle} {\langle 4: page \rangle}
```

```

446 \renewcommand{\thm@@thmline@noname}[4]{%
447 \hypertocfloat{1}{theorem}{thm}{#2 #3}{}

```

```

448 }
449
450 \renewcommand{\thm@@thmline@name}[4]{%
451 \hypertocfloat{1}{theorem}{thm}{#1 #2 #3}{}}%
452 }

```

This was redefined by **ntheorem** when loaded, so it is now redefined for **l warp**:

```
453 \def\thm@@thmline{\thm@@thmline@name}
```

Patch for css:

```

454 \def\listtheorems#1{
455 \LWR@htmlelementclass{nav}{lothm}%
456 \begingroup
457 \c@tocdepth=-2%
458 \def\thm@list{#1}\thm@processlist
459 \endgroup
460 \LWR@htmlelementclassend{nav}{lothm}%
461 }

```

§ 306.13 Symbols

Proof QED symbol:

```

462 \newcommand{\qed}{\qquad\the\quedsymbol}
463
464 \AtBeginDocument{
465 \@ifundefined{LWR@orig@openbox}{
466 \LetLtxMacro{\LWR@orig@openbox}{\openbox}
467 \LetLtxMacro{\LWR@orig@blacksquare}{\blacksquare}
468 \LetLtxMacro{\LWR@orig@Box}{\Box}
469
470 \def\openbox{\text{\HTMLunicode{25A1}}}% UTF-8 white box
471 \def\blacksquare{\text{\HTMLunicode{220E}}}% UTF-8 end-of-proof
472 \def\Box{\text{\HTMLunicode{25A1}}}% UTF-8 white box
473
474 \appto{\LWR@restoreorigformatting}{%
475 \LetLtxMacro{\openbox}{\LWR@orig@openbox}%
476 \LetLtxMacro{\blacksquare}{\LWR@orig@blacksquare}%
477 \LetLtxMacro{\Box}{\LWR@orig@Box}%
478 }% appto
479 }{}% @ifundefined
480 }% AtBeginDocument

```

§ 306.14 Cross-referencing

```
\thref {\langle label \rangle}

481 \newcommand*{\thref}[1]{\cref{#1}}
```

File 214 **l warp-overpic.sty**

§ 307 Package **overpic**

(Emulates or patches code by ROLF NIEPRASCHK.)

Pkg **overpic** **overpic** is patched for use by **l warp**.

⚠ **scaling** The macros `\overpicfontsize` and `\overpicfontskip` are used during HTML generation. These are sent to `\fontsize` to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the `overpic` and `Overpic` environments.

See section 81.2 for the print-mode version of `\overpicfontsize` and `\overpicfontskip`.

for HTML output:

```
1 \LWR@ProvidesPackagePass{overpic}

2 \newcommand*{\overpicfontsize}{12}
3 \newcommand*{\overpicfontskip}{14}
4
5 \BeforeBeginEnvironment{overpic}{%
6   \begin{lateximage}%
7   \fontsize{\overpicfontsize}{\overpicfontskip}%
8   \selectfont%
9 }
10
11 \AfterEndEnvironment{overpic}{\end{lateximage}}
12
13 \BeforeBeginEnvironment{Overpic}{%
14   \begin{lateximage}%
15   \fontsize{\overpicfontsize}{\overpicfontskip}%
16   \selectfont%
17 }
18
19 \AfterEndEnvironment{Overpic}{\end{lateximage}}
```

File 215 **l warp-pagegrid.sty**

§ 308 Package **pagegrid**

Pkg pagegrid **pagegrid** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{pagegrid}
2 \newcommand*{\pagegridsetup}[1]{}

File 216 **l warp-pagenote.sty**

§ 309 Package **pagenote**

Pkg pagenote **pagenote** works as-is, but the **page** option is disabled.

for HTML output: 1 \DeclareOption{page}{}
2 \LWR@ProvidesPackagePass{pagenote}

File 217 **l warp-pagesel.sty**

§ 310 Package **pagesel**

Pkg pagesel **pagesel** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{pagesel}

File 218 **l warp-paralist.sty**

§ 311 Package **paralist**

(Emulates or patches code by BERND SCHANDL.)

Pkg paralist **paralist** is supported with minor changes.

for HTML output: 1 \LWR@ProvidesPackagePass{paralist}

The compact environments are identical to the regular ones:

```

2 \LetLtxMacro{\compactitem}{\itemize}
3 \LetLtxMacro{\compactenum}{\enumerate}
4 \LetLtxMacro{\compactdesc}{\description}
5 \LetLtxMacro{\endcompactitem}{\enditemize}
6 \LetLtxMacro{\endcompactenum}{\endenumerate}
7 \LetLtxMacro{\endcompactdesc}{\enddescription}
```

For the inline environments, revert `\item` to its original print-mode version:

```

8 \AtBeginEnvironment{inparaitem}{\LetLtxMacro{\item}{\LWR@origitem}}
9 \AtBeginEnvironment{inparaenum}{\LetLtxMacro{\item}{\LWR@origitem}}
10 \AtBeginEnvironment{inparadesc}{\LetLtxMacro{\item}{\LWR@origitem}}
```

Manual formatting of the description labels:

```
11 \def\paradescriptionlabel#1{{\normalfont\textbf{#1}}}
```

File 219 **lwarp-parnotes.sty**

§ 312 Package **parnotes**

(Emulates or patches code by CHELSEA HUGHES.)

Pkg **parnotes** **parnotes** is supported with some patches.

for HTML output: 1 \LWR@ProvidesPackagePass{parnotes}

```

2 \long\def\PN@parnote@real#1#2{%
3   \parnotemark{#1}%
4   % Unless this is the first parnote in \PN@text, add a separator first
5   \unless\ifx\PN@text\empty\g@addto@macro\PN@text{\parnoteintercmd}\fi
6   % Redefine \@currentlabel to the parnote label, so \label works
7   \g@addto@macro\PN@text{%
8     \phantomsection%
9     \def\@currentlabel{#1}%
10    \def\cref@currentlabel{}%           lwarp
11    [parnotemark] [\arabic{parnotemark}] []\theparnotemark%
12  }%
13 }%
14 \g@addto@macro\PN@text{%
15   \LWR@textcurrentfont{}%           lwarp
16   \parnotemark{#1}\nolinebreak\thinspace#2%
17 }%
18 }%
```

```

19 }
20
21 \def\PN@parnotes@real{%
22     % We call \par later, so this avoids recursion with \PN@parnotes@auto
23     \PN@inparnotestrue
24     \unless\ifvmode\par\fi
25     % Avoid page breaks between a paragraph and its parnotes
26     \nopagebreak\addvspace{\parnotevskip}%
27     \LWR@forcenewpage%           l warp
28     \begin{BlockClass}{footnotes}%
29     {\parnotefmt{\PN@text}\par}%
30     \end{BlockClass}%
31     \global\def\PN@text{}%
32     \addvspace{\parnotevskip}%
33     %
34     % These can be enabled or disabled by package options
35     %
36     \PN@disable@indent
37     \PN@reset@optional
38     \PN@inparnotesfalse
39 }
40
41 \AtBeginDocument{
42 \crefname{parnotemark}{paragraph note}{paragraph notes}
43 \Crefname{parnotemark}{Paragraph note}{Paragraph notes}
44 }

```

File 220 **l warp-parskip.sty**

§ 313 Package **parskip**

Pkg **parskip** **parskip** is ignored.

for HTML output: Discard all options for **l warp-parskip**.

```
1 \LWR@ProvidesPackageDrop{parskip}
```

File 221 **l warp-pbox.sty**

§ 314 Package **pbox**

(Emulates or patches code by SIMON LAW.)

Pkg **pbox** **pbox** is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{pbox}

2 \NewDocumentCommand{\pbox}{O{t} o O{t} m +m}{%
3 \booltrue{LWR@minipagefullwidth}%
4 \parbox[#1][#2][#3]{#4}{#5}%
5 }%
6
7 \newcommand{\settominwidth}[3][\columnwidth]{%
8 \setwidht{#2}{#3}%
9 }%
10
11 \newcommand{\widthofpbox}[1]{%
12 \widthof{#1}%
13 }

```

File 222 **l warp-pdfescape.sty**

§ 315 Package **pdfescape**

Pkg **pdfescape** **pdfescape** is ignored.

for HTML output: Discard all options for **l warp-pdfescape**:

```
1 \LWR@ProvidesPackageDrop{pdfescape}
```

File 223 **l warp-pdfpages.sty**

§ 316 Package **pdfpages**

(Emulates or patches code by ANDREAS MATTHIAS.)

Pkg **pdfpages** **pdfpages** is patched for use by **l warp**.

Option **link** and **linkname** work:

```
\hyperlink{<filename>.pdf.<pagenumber>}{{some text}}
\hyperlink{<linkname>.<pagenumber>}{{some text}}
```

Options which make no sense in HTML are disabled.

for HTML output:

```
1 \LWR@ProvidesPackagePass{pdfpages}
```

Disable option which have no meaning for HTML output:

```

2 \define@key{pdfpages}{fitpaper}[false]{}
3 \define@key{pdfpages}{landscape}[false]{}
4 \define@key{pdfpages}{openright}[false]{}
5 \define@key{pdfpages}{signature}(){}
6 \define@key{pdfpages}{signature*}(){}
7 \define@key{pdfpages}{booklet}[false]{}
8 \define@key{pdfpages}{rotateoversize}[false]{}
9 \define@key{pdfpages}{doublepages}[false]{}
10 \define@key{pdfpages}{doublepagestwist}[false]{}
11 \define@key{pdfpages}{doublepagestwistodd}[false]{}
12 \define@key{pdfpages}{doublepagestwist*}[false]{}
13 \define@key{pdfpages}{doublepagestwistodd*}[false]{}
14 \define@key{pdfpages}{duplicatepages}[2]{}
15 \define@key{pdfpages}{thread}[false]{}
16 \define@key{pdfpages}{threadname}){}
17 \define@key{pdfpages}{linkfit}){}
18 \define@key{pdfpages}{linktodoc}[false]{}
19 \define@key{pdfpages}{linktodocfit}{}
20 \define@key{pdfpages}{linkfilename}){}
21 \define@key{pdfpages}{survey}[false]{}
22 \define@key{pdfpages}{survey-nolink}[false]{}
23 \define@key{pdfpages}{newwindow}[false]{}

```

Use print mode while measuring the page numbers:

```
24 \xpretocmd{\AM@getpagecount}{\LWR@restoreorigformatting}{}{}
```

Emulate a bit of **eso-pic**:

```

25 \newif\ifESO@texcoord
26
27 \newcommand{\ESO@HookIIBG}{}{}
28
29 \renewcommand{\AM@AddToShipoutPicture}{\g@addto@macro{\ESO@HookIIBG}}
30
31 \renewcommand{\ClearShipoutPicture}{}{}
```

\LWR@esopic@newpage At each \newpage.

```
32 \newcommand*{\LWR@esopic@newpage}{%
```

Is there something to draw?

```

33 \ifdefvoid{\ESO@HookIIBG}%
34 {}%
35 {}%
```

If the link option was specified, add a hyper taraget:

```
36      \ifAM@link%
37          \hypertarget{\AM@linkname.\AM@page}{}%
38      \fi%
```

Draw inside a picture environment of the size of a virtual page:

```
39      \begingroup%
40      \setlength{\unitlength}{1in}%
41      \begin{picture}(8,10.5)%
42      \ESO@HookIIBG%
43      \end{picture}%
44      \endgroup%
45      \global\let\ESO@HookIIBG\empty%
46 }
47 }
```

\AM@output Patched to use \LWR@esopic@newpage.

```
48 \xpatchcmd{\AM@output}
49   {\newpage}
50   {\LWR@esopic@newpage}
51   {}
52   {\LWR@patcherror{pdfpages}{AM@output-1}}
53
54 \xpatchcmd{\AM@output}
55   {\newpage}
56   {\LWR@esopic@newpage}
57   {}
58   {\LWR@patcherror{pdfpages}{AM@output-2}}
59
60 \xpatchcmd{\AM@output}
61   {\newpage}
62   {\LWR@esopic@newpage}
63   {}
64   {\LWR@patcherror{pdfpages}{AM@output-3}}
```

\includepdf Patched to set a reasonable paper size.

```
65 \xpretocmd{\includepdf}{%
66   \begingroup%
67   \setlength{\paperwidth}{8in}%
68   \setlength{\paperheight}{10.5in}%
69 }{}{%
70
71 \xapptocmd{\includepdf}{%
72   \endgroup%
73 }{}{}}
```

\includepdfmerge Patched to set a reasonable paper size.

```

74 \xpreto{cmd}{\includepdfmerge}{%
75   \begingroup%
76   \setlength{\paperwidth}{8in}%
77   \setlength{\paperheight}{10.5in}%
78 }{}{%
79   \xappto{cmd}{\includepdfmerge}{%
80     \endgroup%
81   }{}{%
82 }

```

\AM@hyper@begin@i Hyper links are created by \LWR@esopic@newpage, so don't create them here:
83 \renewcommand{\AM@hyper@begin@i}{}

File 224 **l warp-pdfprivacy.sty**

§ 317 Package **pdfprivacy**

Pkg pdfprivacy **pdfprivacy** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{pdfprivacy}

File 225 **l warp-pdfrender.sty**

§ 318 Package **pdfrender**

Pkg pdfrender **pdfrender** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{pdfrender}

```

2 \newcommand*{\pdfrender}[1]{}
3 \newcommand{\textpdfrender}[2]{#2}

```

File 226 **l warp-pdfsync.sty**

§ 319 Package **pdfsync**

(Emulates or patches code by J. LAURENS.)

Pkg pdfsync Emulated.

for HTML output: Discard all options for **l warp-pdfsync**:

```

1 \LWR@ProvidesPackageDrop{pdfsync}

2 \newcommand*{\pdfsync}{}
3 \newcommand*{\pdfsyncstart}{}
4 \newcommand*{\pdfsyncstop}{}

```

File 227 **l warp-pdftricks.sty**

§ 320 Package **pdftricks**

(Emulates or patches code by C. V. RADHAKRISHNAN, C. V. RAJAGOPAL, ANTOINE CHAMBERT-LOIR.)

Pkg **pdftricks** **pdftricks** is patched for use by **l warp**.

⚠ **convert image files** The **pdftricks** image files <jobname>-fig*.pdf must be converted to .svg, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

Enter ⇒ `l warpmk pdftosvg <jobname>-fig*.pdf`

for HTML output: `1 \LWR@ProvidesPackagePass{pdftricks}`

Reuse the print-mode images:

```
2 \def\PDFTfigname{\BaseJobname-fig\thePSfig}
```

If the .pdf images have not yet been converted to .svg then an error about a missing file will occur. Warn the user to convert the images.

```

3 \PackageWarning{l warp-pdftricks}{
4 When the pdftricks images change,
5 remember to convert PDF images to SVG using 'l warpmk pdftosvg *-fig.pdf',
6 }
7
8 \AfterEndDocument{\typeout{***}}
9 \AfterEndDocument{\typeout{*** Note: If pdftricks images are not found, new, or updated,}}
10 \AfterEndDocument{\typeout{*** \space use 'l warpmk pdftosvg \BaseJobname-fig*.pdf'}}
11 \AfterEndDocument{\typeout{***}}

```

File 228 **l warp-pd fx.sty**

§ 321 Package **pd fx**

Pkg pd fx **pd fx** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{pd fx}

File 229 **l warp-pf note.sty**

§ 322 Package **pf note**

Pkg pf note **pf note** is emulated.

⚠ **pf note numbers** While emulating **pf note**, **l warp** is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. **l warp** therefore uses continuous footnote numbering even for **pf note**.

for HTML output: 1 \LWR@ProvidesPackageDrop{pf note}

File 230 **l warp-ph fqit.sty**

§ 323 Package **ph fqit**

(Emulates or patches code by PHILIPPE FAIST.)

Pkg ph fqit **ph fqit** is patched for use by **l warp**.

for HTML output: 1 \LWR@ProvidesPackagePass{ph fqit}

```
2 \LetLtxMacro{\LWR@origbitstring}{\bitstring}
3
4 \renewcommand{\bitstring}[1]{%
5   \InlineClass[%
6     text-decoration: overline underline ;
7   ]{\bitstring}{#1}%
8   \phfqit@bitstring{#1}%
9 }
10
```

```
11 \appto\LWR@restoreorigformatting{%
12 \LetLtxMacro\bitstring\LWR@origbitstring%
13 }
```

File 231 **l warp-placeins.sty**

§ 324 Package **placeins**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg **placeins** **placeins** is not used during HTML conversion.

Discard all options for **l warp-placeins**:

for HTML output:

```
1 \LWR@ProvidesPackageDrop{placeins}

2 \newcommand*\{FloatBarrier}{}

---


```

File 232 **l warp-prelim2e.sty**

§ 325 Package **prelim2e**

(Emulates or patches code by MARTIN SCHRÖDER.)

Pkg **prelim2e** Emulated.

for HTML output: Discard all options for **l warp-prelim2e**:

```
1 \LWR@ProvidesPackageDrop{prelim2e}

2 \newcommand{\PrelimText}{}%
3 \newcommand{\PrelimTextStyle}{}%
4 \newcommand{\PrelimWords}{}%

---


```

File 233 **l warp-prettyref.sty**

§ 326 Package **prettyref**

(Emulates or patches code by KEVIN S. RULAND.)

Pkg **prettyref** **prettyref** is patched for use by **l warp**.

for HTML output:

```
1 \LWR@ProvidesPackagePass{prettyref}
```

```
2 \newrefformat{fig}{Figure \ref{#1}}
3 \newrefformat{tab}{Table \ref{#1}}
```

File 234 **l warp-preview.sty**

§ 327 Package **preview**

Pkg **preview** **preview** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{preview}[2017/04/24]

```
2 \newenvironment{preview}{}{}
3 \newenvironment{nopreview}{}{}
4 \NewDocumentCommand{\PreviewMacro}{s o o +m}{}
5 \NewDocumentCommand{\PreviewEnvironment}{s o o +m}{}
6 \newcommand{\PreviewSnarfEnvironment}[2][]{}
7 \NewDocumentCommand{\PreviewOpen}{s o}{}
8 \NewDocumentCommand{\PreviewClose}{s o}{}
9 \let\ifPreview\iffalse% \fi for syntax highlighting
```

File 235 **l warp-psfrag.sty**

§ 328 Package **psfrag**

(Emulates or patches code by MICHAEL C. GRANT, DAVID CARLISLE.)

Pkg **psfrag** **psfrag** is patched for use by **l warp**.

⚠ **use psfrags** The **psfrags** environment is modified to use **lateximage** to encapsulate the image. Always use a **psfrags** environment to contain any local **\psfrag** macros and the associated **\includegraphics** or **\epsfig** calls. Outside of a **psfrags** environment, **psfrags** adjustments will not be seen by **l warp**.

⚠ Tip: Use a mono-spaced font for the tags in the EPS file.

for HTML output: 1 \LWR@ProvidesPackagePass{psfrag}[1998/04/11]

A **lateximage** captures the modified image from the document.

```
2 \BeforeBeginEnvironment{psfrags}{%
3   \begin{lateximage}[(-psfrags--\packagediagramname)]%
4 }
5
6 \AfterEndEnvironment{psfrags}{\end{lateximage}}
```

File 236 **l warp-psfragx.sty**

§ 329 Package **psfragx**

(Emulates or patches code by PASCAL KOCKAERT.)

Pkg **psfragx** **psfragx** is patched for use by **l warp**.

for HTML output: 1 \LWR@ProvidesPackagePass{psfragx}[2012/05/02]

A `lateximage` captures the modified image from the document.

```
2 \def\pfx@includegraphicx#1#2{%
3   \begin{latentimage}[(-psfragx--\packagediagramname)]%
4     \mbox{\pfx@overpix{#1}{#2}\endpfx@overpix}%
5   \end{latentimage}%
6 }
7
8 \def\@@@overpix[#1]<#2>[#3]#4{%
9   \begin{latentimage}[(-psfragx--\packagediagramname)]%
10   \pfx@overpix{#1,ovpfgd={#2},ovpbgd={#3}}{#4}%
11 }
12
13 \def\endoverpix{%
14   \endpfx@overpix}%
15 \end{latentimage}%
16 }
```

File 237 **l warp-pst-eps.sty**

§ 330 Package **pst-eps**

(Emulates or patches code by HERBERT VOSS.)

Pkg **pst-eps** **pst-eps** is patched for use by **l warp**.

for HTML output: 1 \LWR@ProvidesPackagePass{pst-eps}

```
2 \renewenvironment{TeXtoEPS}{}{}
3 \renewcommand{\PSTtoEPS}[3][]{}
```

File 238 **l warp-pstool.sty**

§ 331 Package **pstool**

(Emulates or patches code by ZEBB PRIME, WILL ROBERTSON.)

Pkg **pstool** **pstool** is patched for use by **l warp**.

\graphicspath is ignored, and the file directory must be stated.

⚠ **path and filename** The filename must not have a file extension.

Use

Enter ⇒ l warpmk html

followed by

Enter ⇒ l warpmk l images

.

for HTML output: 1 \LWR@ProvidesPackagePass{pstool}

Each image is placed inside a `lateximage` to capture the results of **psfrag**.

```
2 \renewcommand\pstool@alwaysprocess[3][]{%
3   \begin{lateximage}[(-pstool-\packagediagramname)]%
4   \includegraphics{\#2.pdf}%
5   \end{lateximage}%
6 }
7 \LetLtxMacro\pstool@neverprocess\pstool@alwaysprocess
8 \LetLtxMacro\pstool@maybeprocess\pstool@alwaysprocess
9
10 \renewcommand\pstool@@psfragfig[4]{%
11   \begin{lateximage}[(-pstool-\packagediagramname)]%
12   \includegraphics{\#2.pdf}%
13   \end{lateximage}%
14 }
```

File 239 **l warp-pstricks.sty**

§ 332 Package **pstricks**

(Emulates or patches code by TIMOTHY VAN ZANDT.)

Pkg pstricks **pstricks** is patched for use by **l warp**.

⚠ **use pspicture** All **pstricks** content should be contained inside a **pspicture** environment.

for HTML output: 1 \LWR@ProvidesPackagePass{pstricks}

2 \BeforeBeginEnvironment{pspicture}{\begin{lateximage}[(pspicture)]}

3 \AfterEndEnvironment{pspicture}{\end{lateximage}}

File 240 **l warp-quotchap.sty**

§ 333 Package **quotchap**

(Emulates or patches code by KARSTEN TINNEFELD, JAN KLEVER.)

Pkg quotchap **quotchap** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{quotchap}

2 \newcommand{\@quotchap}{}
3 \newlength{\LWR@quotchapwidth}
4
5 \let\@printcites\relax
6
7 \newcommand*{\@iprintcites}{%

Place the quotes inside a **<div>** of class **quotchap**, of the maximum selected width:

8 \begin{BlockClass}[max-width: \LWR@printlength{\LWR@quotchapwidth}]{quotchap}
9 %\begin{minipage}{\LWR@quotchapwidth}
10 \@quotchap
11 %\end{minipage}
12 \end{BlockClass}

Deactivate the quote printing:

```

13 \global\let\@printcites\relax
14 }
15
16 \NewEnviron{savequote}[1][\linewidth]{%

```

Remember the width, adjusted for HTML, and make the length assignment global, per:

<https://tex.stackexchange.com/questions/300823/why-is-setlength-ineffective-inside-a-tabular-environment>

```

17 \setlength{\LWR@quotchapwidth}{#1*2}%
18 \global\LWR@quotchapwidth=\LWR@quotchapwidth%

```

Remember the body, and activate the quote printing:

```

19 \global\let\@quotchap\BODY
20 \global\let\@printcites\@iprintcites%
21 }

```

The quotation author is placed inside a <div> of class qauthor:

```
22 \newcommand{\qauthor}[1]{\begin{BlockClass}{qauthor}{#1}\end{BlockClass}}
```

\qsetcnfont is ignored:

```
23 \newcommand{\qsetcnfont}[1]{}
```

File 241 l warp-quoting.sty

§ 334 Package **quoting**

(Emulates or patches code by THOMAS TITZ.)

Pkg quoting **quoting** is patched for use by **l warp**.

```

for HTML output: 1 \LWR@ProvidesPackagePass{quoting}

2 \xpatchcmd{\quoting}{\quo@begintext}
3   {\begin{LWR@blocktextcurrentfont}\quo@begintext}
4   {}
5   {\LWR@patcherror{quoting}{quoting}}
6
7 \xpatchcmd{\endquoting}{\quo@endtext}
8   {\quo@endtext\end{LWR@blocktextcurrentfont}}
9   {}
10 {\LWR@patcherror{imakeidx}{endquoting}}

```

File 242 **l warp-ragged2e.sty**

§ 335 Package **ragged2e**

(Emulates or patches code by MARTIN SCHRÖDER.)

Pkg **ragged2e** **ragged2e** is not used during HTML conversion.

Discard all options for **l warp-ragged2e**:

for HTML output:

```
1 \LWR@ProvidesPackageDrop{ragged2e}

2 \LetLtxMacro\Centering\centering
3 \LetLtxMacro\RaggedLeft\raggedleft
4 \LetLtxMacro\RaggedRight\raggedright
5 \newcommand*\justify{}{}
6 \newlength{\CenteringLeftskip}
7 \newlength{\RaggedLeftLeftskip}
8 \newlength{\RaggedRightLeftskip}
9 \newlength{\CenteringRightskip}
10 \newlength{\RaggedLeftRightskip}
11 \newlength{\RaggedRightRightskip}
12 \newlength{\CenteringParfillskip}
13 \newlength{\RaggedLeftParfillskip}
14 \newlength{\RaggedRightParfillskip}
15 \newlength{\JustifyingParfillskip}
16 \newlength{\CenteringParindent}
17 \newlength{\RaggedLeftParindent}
18 \newlength{\RaggedRightParindent}
19 \newlength{\JustifyingParindent}
20 \newenvironment*[Center]{\center}{\endcenter}
21 \newenvironment*[FlushLeft]{\flushleft}{\endflushleft}
22 \newenvironment*[FlushRight]{\flushright}{\endflushright}
23 \newenvironment*[justify]{\justify}{\endjustify}
```

File 243 **l warp-realscripts.sty**

§ 336 Package **realscripts**

(Emulates or patches code by WILL ROBERTSON.)

Pkg **realscripts** **realscripts** is emulated. See **l warp.css** for the of class supsubscript.

```

for HTML output: 1 \LWR@ProvidesPackageDrop{realscripts}

2 \let\realsuperscript{textsuperscript}
3 \let\realsubscript{textsubscript}
4
5 \let\fakesuperscript{textsuperscript}
6 \let\fakesubscript{textsubscript}
7
8 \newlength{\subsupersep}
9
10 \newcommand*{\LWR@realscriptsalign}={}
11
12 \newcommand*{\LWR@setrealscriptsalign}[1]{%
13 \renewcommand*{\LWR@realscriptsalign}{}%
14 \ifthenelse{\equal{#1}{c}}{%
15   \renewcommand{\LWR@realscriptsalign}{\LWR@print@mbox{text-align:center} ; }%
16 }{%
17 \ifthenelse{\equal{#1}{r}}{%
18   \renewcommand{\LWR@realscriptsalign}{\LWR@print@mbox{text-align:right} ; }%
19 }{%
20 }
21
22 \DeclareDocumentCommand \textsubsuperscript {s O{1} mm} {%
23 \LWR@setrealscriptsalign{#2}%
24 \InlineClass[\LWR@realscriptsalign]{supsubscript}{%
25 \textsuperscript{#4}\textsubscript{#3}}%
26 }%
27 }
28
29 \DeclareDocumentCommand \textsupersubscript {s O{1} mm} {%
30 \LWR@setrealscriptsalign{#2}%
31 \InlineClass[\LWR@realscriptsalign]{supsubscript}{%
32 \textsubscript{#4}\textsuperscript{#3}}%
33 }%
34 }

```

File 244 lwarf-refcheck.sty

§ 337 Package **refcheck**

Pkg refcheck **refcheck** is ignored.

```

for HTML output: 1 \LWR@ProvidesPackageDrop{refcheck}[2013/02/14]

2 \def\showrefnames{}
3 \def\norefnames{}

```

```

4 \def\showcitenames{}
5 \def\nocitenames{}
6 \def\setonmsgs{}
7 \def\setoffmsgs{}
8 \def\checkunlbld{}
9 \def\ignoreunlbld{}
10 \newcommand*{\refcheckxrdoc}[2][]{}

```

File 245 **l warp-register.sty**

§ 338 Package **register**

(Emulates or patches code by MATTHEW LOVELL.)

Pkg **register** **register** is patched for use by **l warp**.

for HTML output:

```

1 \LWR@ProvidesPackagePass{register}

2 \xpatchcmd{\register}
3   {\centering}
4   {\begin{center}\begin{ lateximage }[(-register-\~\packagediagramname)]\end{ lateximage }\end{center}}
5   {}
6   {\LWR@patcherror{register}{register}}
7
8 \xpatchcmd{\endregister}
9   {\leftskip}
10  {%
11    \end{ lateximage }\end{center}%
12    \leftskip%
13  }%
14  {}
15  {\LWR@patcherror{register}{endregister}}
16
17 \setlength{\regWidth}{5in}

```

File 246 **l warp-relsize.sty**

§ 339 Package **relsize**

(Emulates or patches code by DONALD ARSENEAU, BERNIE COSELL, MATT SWIFT.)

Pkg **relsize** **relsize** is patched for use by **l warp**.

For HTML, only the inline macros are supported: `\textlarger`, `\textsmaller`, and `\textscale`. Each becomes an inline span of a modified font-size.

\relsize, \larger, \smaller, and \relscale are ignored.

While creating SVG math for HTML, the original definitions are temporarily restored, and so should work as expected.

-  **not small** The HTML browser's setting for minimum font size may limit how small the output will be displayed.

for HTML output:

```
1 \LWR@ProvidesPackagePass{relsize}

2 \let\LWR@origrelsize\relsize
3 \LetLtxMacro{\LWR@origlarger}{\larger}
4 \LetLtxMacro{\LWR@origsmaller}{\smaller}
5 \let\LWR@relscale\relscale
6 \LetLtxMacro{\LWR@origtextlarger}{\textlarger}
7 \LetLtxMacro{\LWR@origtextsmaller}{\textsmaller}
8 \let\textscale\textscale
9
10 \appto{\LWR@restoreorigformatting}{%
11   \let\relsize{\LWR@origrelsize}%
12   \LetLtxMacro{\larger}{\LWR@origlarger}%
13   \LetLtxMacro{\smaller}{\LWR@origsmaller}%
14   \let\relscale{\LWR@relscale}%
15   \LetLtxMacro{\textlarger}{\LWR@origtextlarger}%
16   \LetLtxMacro{\textsmaller}{\LWR@origtextsmaller}%
17   \let\textscale{\LWR@textscale}%
18 }
19
20 \newcounter{LWR@relsizetemp}
21
22 \renewcommand*{\relsize}[1]{}
23 \renewcommand*{\larger}[1][]{}
24 \renewcommand*{\smaller}[1][]{}
25 \renewcommand*{\relscale}[1]{}
26
27 \renewcommand*{\textlarger}[2][1]{%
28   \setcounter{LWR@relsizetemp}{100+ (#1*20)}%
29   \InlineClass{font-size:\arabic{LWR@relsizetemp}\%}{textlarger}{#2}%
30 }
31
32 \renewcommand*{\textsmaller}[2][1]{%
33   \setcounter{LWR@relsizetemp}{100- (#1*20)}%
34   \InlineClass{font-size:\arabic{LWR@relsizetemp}\%}{textsmaller}{#2}%
35 }
36
37 \renewcommand*{\textscale}[2]{%
38   \setcounter{LWR@relsizetemp}{100*\real{#1}}%
39   \InlineClass{font-size:\arabic{LWR@relsizetemp}\%}{textscale}{#2}%
40 }
```

File 247 **l warp-repeatindex.sty**

§ 340 Package **repeatindex**

Pkg **repeatindex** **repeatindex** is emulated for **l warp**.

l warp must be used with a special style file:

```
\usepackage[makeindex,makeindexStyle={l warp_repeatindex}]{l warp}
```

where **l warp_repeatindex.ist** may be copied from the following modified version of **l warp.ist**:

```
preamble
"\begin{theindex}
 \providecommand*\lettergroupDefault[1]{}%
 \providecommand*\lettergroup[1]{%
   \par\textbf{\#1}\par
   \nopagebreak
 }
"
headings_flag 1
heading_prefix "
 \lettergroup{
heading_suffix }"
delim_0 ", \hyperindexref{"
delim_1 ", \hyperindexref{"
delim_2 ", \hyperindexref{"
delim_n "}, \hyperindexref{"
delim_r "} -- \hyperindexref{"
delim_t "}"

item_0 "\n \item ["
```

(The modifications are the **delim_0** and **item_0** entries.)

for HTML output: 1 \LWR@ProvidesPackageDrop{repeatindex}[2001/10/13]

In the **l warp** core, **\LWR@indexitem** is modified to accept the optional **\item** argument.

```
2 \RequirePackage{makeidx}
```

```
3 \def\entryprefix{\itshape}
4 \def\entrypostfix{\dots}
```

File 248 **l warp-resizegather.sty**

§ 341 Package **resizegather**

Pkg **resizegather** **resizegather** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{resizegather}
2 \newcommand*\{resizegathersetup}{1}{}{}
```

File 249 **l warp-romanbar.sty**

§ 342 Package **romanbar**

(Emulates or patches code by H.-MARTIN MÜNCH.)

Pkg **romanbar** **romanbar** is patched for use by **l warp**.

An inline class with an overline and underline is used.

for HTML output:

```
1 \LWR@ProvidesPackagePass{romanbar}
2 \DeclareRobustCommand{\Roman@bar}{1}{{% #1 is in Roman, i.e. MMXII
3 \InlineClass[%}
4   text-decoration: overline underline ;
5 ]{\romanbar}{#1}}%
6 }
```

File 250 **l warp-romanbarpagenumber.sty**

§ 343 Package **romanbarpagenumber**

Pkg **romanbarpagenumber** **romanbarpagenumber** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{romanbarpagenumber}
```

File 251 **l warp-rotating.sty**

§ 344 Package **rotating**

(Emulates or patches code by ROBIN FAIRBAIRNS, SEBASTIAN RAHTZ, LEONOR BARROCA.)

Pkg **rotating** **rotating** is emulated.

All rotations are ignored in HTML output.

for HTML output: 1 \LWR@ProvidesPackageDrop{rotating}

```
2 \LetLtxMacro{\sidewaystable}{\table}
3 \let\endsidewaystable\endtable
4
5 \LetLtxMacro{\sidewaysfigure}{\figure}
6 \let\endsidewaysfigure\endfigure
7
8 \newenvironment*{sideways}{}{}
9 \newenvironment*{turn}[1]{}{}
10 \newenvironment*{rotate}[1]{}{}
11 \NewDocumentCommand{\turnbox}{m +m}{#2}
12 \let\rotcaption\caption
13 \let\@makerotcaption\@makecaption
```

File 252 **l warp-rotfloat.sty**

§ 345 Package **rotfloat**

(Emulates or patches code by AXEL SOMMERFELDT.)

Pkg **rotfloat** **rotfloat** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{rotfloat}[2004/01/04]
2
3 \RequirePackage{float}

\newfloat {\langle 1: type\rangle} {\langle 2: placement\rangle} {\langle 3: ext\rangle} [{\langle 4: within\rangle}]

Emulates the `\newfloat` command from the **float** package. Sideways floats are `\let` to the same as regular floats.

“placement” is ignored.

```

4 \RenewDocumentCommand{\newfloat}{m m m o}{%
5 \IfValueTF{#4}{%
6 {%
7     \DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}%
8 }%
9 {%
10    \DeclareFloatingEnvironment[fileext=#3]{#1}%
11 }%
12 \csletcs{sideways}{#1}%
13 \csletcs{endsideways}{#1}{end#1}%

```

Remember the float style:

```

14 \csedef{LWR@floatstyle@#1}{\LWR@floatstyle}%
15 \csedef{LWR@floatstyle@sideways#1}{\LWR@floatstyle}%

```

newfloat package automatically creates the `\listof` command for new floats, but **float** does not, so remove `\listof` here in case it is manually created later:

```

16 \cslet{listof#1s}\relax%
17 \cslet{listof#1es}\relax%
18 \cslet{listofsideways#1s}\relax%
19 \cslet{listofsideways#1es}\relax%
20 }

```

File 253 l warp-savetrees.sty

§ 346 Package **savetrees**

Pkg **savetrees** Emulated.

for HTML output: Discard all options for **l warp-savetrees**:

```
1 \LWR@ProvidesPackageDrop{savetrees}
```

File 254 l warp-scalefnt.sty

§ 347 Package **scalefnt**

(Emulates or patches code by D. CARLISLE.)

Pkg **scalefnt** **scalefnt** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{scalefnt}
2 \DeclareRobustCommand\scalefont[1]{}
```

File 255 **l warp-schemata.sty**

§ 348 Package **schemata**

(Emulates or patches code by CHARLES P. SCHAUM.)

Pkg **schemata** **schemata** is patched for use by **l warp**.

for HTML output:

```
1 \LWR@ProvidesPackagePass{schemata}
2 \LetLtxMacro\LWR@schemata@origschema\schema
3 \LetLtxMacro\LWR@schemata@origSchema\Schema
4
5 \renewcommand{\schema}[3][open]{%
6 \begin{lateximage}%
7 \LWR@print@normalsize
8 \LWR@schemata@origschema[#1]{#2}{#3}%
9 \end{lateximage}%
10 }
11
12 \renewcommand{\Schema}[5][open]{%
13 \begin{lateximage}%
14 \LWR@print@normalsize
15 \LWR@schemata@origSchema[#1]{#2}{#3}{#4}{#5}%
16 \end{lateximage}%
17 }
```

File 256 **l warp-scrextend.sty**

§ 349 Package **scrextend**

Pkg **scrextend** **scrextend** is emulated.

This package may be loaded standalone, but is also loaded automatically if **koma-script** classes are in use. **\DeclareDocumentCommand** is used to overwrite the **koma-script** definitions.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{scrextend}
```

```
2 \DeclareDocumentCommand{\setkomafont}{m m}{}  
3 \DeclareDocumentCommand{\addkomafont}{m m}{}  
4 \DeclareDocumentCommand{\usekomafont}{m}{}  
5  
6 \DeclareDocumentCommand{\usefontofkomafont}{m}{}  
7 \DeclareDocumentCommand{\useencodingofkomafont}{m}{}  
8 \DeclareDocumentCommand{\usesizeofkomafont}{m}{}  
9 \DeclareDocumentCommand{\usefamilyofkomafont}{m}{}  
10 \DeclareDocumentCommand{\useseriesofkomafont}{m}{}  
11 \DeclareDocumentCommand{\useshapeofkomafont}{m}{}  
12  
13 \AtBeginDocument{  
14 \let\LWR@maketitle\maketitle  
15 \DeclareDocumentCommand{\maketitle}{o}{\LWR@maketitle}  
16 }  
17  
18 \DeclareDocumentCommand{\extratitle}{m}{}  
19 \DeclareDocumentCommand{\titlehead}{m}{}  
20 \DeclareDocumentCommand{\subject}{m}{}  
21 \DeclareDocumentCommand{\publishers}{m}{\published{#1}}  
22 \DeclareDocumentCommand{\uppertitleback}{m}{}  
23 \DeclareDocumentCommand{\lowertitleback}{m}{}  
24 \DeclareDocumentCommand{\dedication}{m}{}  
25  
26 \DeclareDocumentCommand{\ifthispageodd}{m m}{#1}  
27  
28 \DeclareDocumentCommand{\titlepagestyle}{}{}  
29  
30 \DeclareDocumentCommand{\cleardoublepageusingstyle}{m}{}  
31 \DeclareDocumentCommand{\cleardoubleemptypage}{}{}  
32 \DeclareDocumentCommand{\cleardoubleplainpage}{}{}  
33 \DeclareDocumentCommand{\cleardoublestandardpage}{}{}  
34 \DeclareDocumentCommand{\cleardoubleoddpage}{}{}  
35 \DeclareDocumentCommand{\cleardoubleoddpageusingstyle}{m}{}  
36 \DeclareDocumentCommand{\cleardoubleoddemptypage}{}{}  
37 \DeclareDocumentCommand{\cleardoubleoddplainpage}{}{}  
38 \DeclareDocumentCommand{\cleardoubleoddstandardpage}{}{}  
39 \DeclareDocumentCommand{\cleardoubleevenpage}{}{}  
40 \DeclareDocumentCommand{\cleardoubleevenpageusingstyle}{m}{}  
41 \DeclareDocumentCommand{\cleardoubleevenemptypage}{}{}  
42 \DeclareDocumentCommand{\cleardoubleevenplainpage}{}{}  
43 \DeclareDocumentCommand{\cleardoubleevenstandardpage}{}{}  
44  
45 \DeclareDocumentCommand{\multiplefootnoteseparator}{}{  
46   \begingroup\let\thefootnotemark\multfootsep\makefnmark\endgroup  
47 }  
48  
49 \DeclareDocumentCommand{\multfootsep}{}{,}  
50  
51 \DeclareDocumentCommand{\footref}{m}{%
```

```
52 \begingroup
53   \unrestored@protected@xdef\@thefnmark{\ref{\#1}}%
54 \endgroup
55 \footnotemark
56 }
57
58 \DeclareDocumentCommand{\deffootnote}{o m m m}{}
59 \DeclareDocumentCommand{\deffootnotemark}{m}{}
60 \DeclareDocumentCommand{\setfootnoterule}{o m}{}
61 \DeclareDocumentCommand{\raggedfootnote}{}{ {}}
62
63 \DeclareDocumentCommand{\dictum}{o m}{%
64 \begin{LWR@BlockClassWP}{\LWR@print@mbox{text-align:right}}{}{dictum}
65   #2
66   \IfValueT{\#1}{%
67     {
68       \ifbool{FormatWP}{%
69         {\begin{BlockClass}[\LWR@print@mbox{border-top:} 1px solid gray]{dictumauthor}}%
70         {\begin{BlockClass}{dictumauthor}}%
71         \dictumauthorformat{\#1}%
72         \end{BlockClass}%
73       }%
74     \end{LWR@BlockClassWP}%
75   }%
76
77 \DeclareDocumentCommand{\dictumwidth}{}{ {}}
78 \DeclareDocumentCommand{\dictumauthorformat}{m}{(\#1)}%
79 \DeclareDocumentCommand{\dictumrule}{}{ {}}
80 \DeclareDocumentCommand{\raggeddictum}{}{ {}}
81 \DeclareDocumentCommand{\raggeddictumtext}{}{ {}}
82 \DeclareDocumentCommand{\raggeddictumauthor}{}{ {}}
83
84 \DeclareDocumentEnvironment{labeling}{o m}
85 {%
86 \def\sc@septext{\#1}%
87 \list{}{ }%
88 \let\makelabel\labelinglabel%
89 }
90 {
91 \endlist
92 }
93
94 \DeclareDocumentCommand{\labelinglabel}{m}{%
95 \#1 \qquad \sc@septext%
96 }
97
98 \let\addmargin\relax
99 \let\endaddmargin\relax
100 \cslet{addmargin*}{\relax}
101 \cslet{endaddmargin*}{\relax}
```

```

102
103 \NewDocumentEnvironment{addmargin}{s O{} m}
104 {
105 \setlength{\LWR@templengthtwo}{#3}
106 \ifblank{#2}
107 {
108   \begin{BlockClass}[
109     \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthtwo}} ;
110     \LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}
111   ]{addmargin}
112 }
113 {
114   \setlength{\LWR@templengthone}{#2}
115   \begin{BlockClass}[
116     \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ;
117     \LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}
118   ]{addmargin}
119 }
120 }
121 {\end{BlockClass}}

```

Ref to create a starred environment:

<https://tex.stackexchange.com/questions/45401/use-the-s-star-argument-with-newdocumentenvironment>

```

122
123 \ExplSyntaxOn
124 \cs_new:cpx {addmargin*} {\addmargin*}
125 \cs_new_eq:cN {endaddmargin*} \endaddmargin
126 \ExplSyntaxOff
127
128 \DeclareDocumentCommand{\marginline}{m}{\marginpar{#1}}

```

File 257 **lwarf-scrhack.sty**

§ 350 Package **scrhack**

Pkg **scrhack** **scrhack** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{scrhack}

File 258 **l warp-scrlayer.sty**

§ 351 Package **scrlayer**

(Emulates or patches code by MARKUS KOHM.)

Pkg scrlayer **scrlayer** is emulated.

⚠ Not fully tested! [Please send bug reports!](#)

for HTML output:

```
1 \LWR@ProvidesPackageDrop{scrlayer}

2 \newcommand*{\DeclareSectionNumberDepth}[2]{}
3 \newcommand*{\DeclareLayer}[2][]{}
4 \newcommand*{\DeclareNewLayer}[2][]{}
5 \newcommand*{\ProvideLayer}[2][]{}
6 \newcommand*{\RedeclareLayer}[2][]{}
7 \newcommand*{\ModifyLayer}[2][]{}
8 \newcommand*{\layerhalign}{}
9 \newcommand*{\layervalign}{}
10 \newcommand*{\layerxoffset}{}
11 \newcommand*{\layeryoffset}{}
12 \newcommand*{\layerwidth}{}
13 \newcommand*{\layerheight}{}
14 \providecommand*{\LenToUnit}[1]{\strip@pt\dimexpr#1*\p@\/\unitlength}
15 \newcommand*{\putUL}[1]{}
16 \newcommand*{\putUR}[1]{}
17 \newcommand*{\putLL}[1]{}
18 \newcommand*{\putLR}[1]{}
19 \newcommand*{\putC}[1]{}
20 \newcommand*{\GetLayerContents}[1]{}
21 \newcommand{\IfLayerExists}[3]{#3}
22 \newcommand*{\DestroyLayer}[1]{}
23 \newcommand*{\layercontentsmeasure}{}
24 \newcommand*{\currentpagestyle}{}
25 \newcommand*{\BeforeSelectAnyPageStyle}[1]{}
26 \newcommand*{\AfterSelectAnyPageStyle}[1]{}
27 \newcommand*{\DeclarePageStyleAlias}[2]{}
28 \newcommand*{\DeclareNewPageStyleAlias}[2]{}
29 \newcommand*{\ProvidePageStyleAlias}[2]{}
30 \newcommand*{\RedeclarePageStyleAlias}[2]{}
31 \newcommand*{\DestroyPageStyleAlias}[1]{}
32 \newcommand*{\GetRealPageStyle}[1]{}
33 \newcommand*{\DeclarePageStyleByLayers}[3][]{}
34 \newcommand*{\DeclareNewPageStyleByLayers}[3][]{}
```

```

35 \newcommand*{\ProvidePageStyleByLayers}{3} []
36 \newcommand*{\RedeclarePageStyleByLayers}{3} []
37 \NewDocumentCommand{\ForEachLayerOfPageStyle}{s m m}{}
38 \newcommand*{\AddLayersToPageStyle}{2} {}
39 \newcommand*{\AddLayersAtBeginOfPageStyle}{2} {}
40 \newcommand*{\AddLayersAtEndOfPageStyle}{2} {}
41 \newcommand*{\RemoveLayersFromPageStyle}{2} {}
42 \newcommand*{\AddLayersToPageStyleBeforeLayer}{3} {}
43 \newcommand*{\AddLayersToPageStyleAfterLayer}{3} {}
44 \newcommand*{\UnifyLayersAtPageStyle}{1} {}
45 \newcommand*{\ModifyLayerPageStyleOptions}{2} {}
46 \newcommand*{\AddToLayerPageStyleOptions}{2} {}
47 \newcommand{\IfLayerPageStyleExists}{3} {#3}
48 \newcommand{\IfRealLayerPageStyleExists}{3} {#3}
49 \newcommand{\IfLayerAtPageStyle}{4} {#4}
50 \newcommand{\IfSomeLayerAtPageStyle}{4} {#4}
51 \newcommand{\IfLayersAtPageStyle}{4} {#4}
52 \newcommand*{\DestroyRealLayerPageStyle}{1} {}
53 @ifundefined{fooheight}{\newlength\fooheight}{}
54 \DeclareDocumentCommand{\automark}{s o m}{}
55 \DeclareDocumentCommand{\manualmark}{o}{}
56 \DeclareDocumentCommand{\MakeMarkcase}{m}{#1}
57 \DeclareDocumentCommand{\GenericMarkFormat}{o}{}
58 \newcommand*{\@mkleft}{1} {}
59 \newcommand*{\@mkright}{1} {}
60 \newcommand*{\@mkdouble}{1} {}
61 \newcommand*{\@mkboth}{2} {}
62 \newcommand*{\scrlayerInitInterface}{1} []
63 \newcommand{\scrlayerAddToInterface}{3} []
64 \newcommand{\scrlayerAddCsToInterface}{3} []
65 \newcommand{\scrlayerOnAutoRemoveInterface}{2} []

```

File 259 **l warp-scrlayer-notecolumn.sty**

§ 352 Package **scrlayer-notecolumn**

(Emulates or patches code by MARKUS KOHM.)

Pkg **scrlayer-notecolumn** **scrlayer-notecolumn** is emulated.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```

1 \LWR@ProvidesPackageDrop{scrlayer-notecolumn}

2 \newcommand*{\DeclareNoteColumn}{2} []
3 \newcommand*{\DeclareNewNoteColumn}{2} []
4 \newcommand*{\ProvideNoteColumn}{2} []

```

```

5 \newcommand*{\RedeclareNoteColumn}[2] {} {}
6 \NewDocumentCommand{\makenote}{s o m}{\marginpar{#3}}
7 \newcommand*{\syncwithnotecolumn}[1] {} {}
8 \newcommand*{\syncwithnotecolumns}[1] {} {}
9 \newcommand*{\clearnotecolumn}[1] {} {}
10 \newcommand*{\clearnotecolumns}[1] {} {}

```

File 260 **l warp-scrlayer-scrpage.sty**

§ 353 Package **scrlayer-scrpage**

(Emulates or patches code by MARKUS KOHM.)

Pkg scrlayer-scrpage **scrlayer-scrpage** is emulated.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```

1 \LWR@ProvidesPackageDrop{scrlayer-scrpage}

2 \@ifundefined{fooheight}{\newlength\fooheight}{}%
3 \NewDocumentCommand{\lehead}{s o m}{}%
4 \NewDocumentCommand{\cehead}{s o m}{}%
5 \NewDocumentCommand{\rehead}{s o m}{}%
6 \NewDocumentCommand{\lohead}{s o m}{}%
7 \NewDocumentCommand{\cohead}{s o m}{}%
8 \NewDocumentCommand{\rohead}{s o m}{}%
9 \NewDocumentCommand{\lefoot}{s o m}{}%
10 \NewDocumentCommand{\cefoot}{s o m}{}%
11 \NewDocumentCommand{\refoot}{s o m}{}%
12 \NewDocumentCommand{\lofoot}{s o m}{}%
13 \NewDocumentCommand{\cofoot}{s o m}{}%
14 \NewDocumentCommand{\rofoot}{s o m}{}%
15 \NewDocumentCommand{\ohead}{s o m}{}%
16 \NewDocumentCommand{\chead}{s o m}{}%
17 \NewDocumentCommand{\ihead}{s o m}{}%
18 \NewDocumentCommand{\ofoot}{s o m}{}%
19 \NewDocumentCommand{\cfoot}{s o m}{}%
20 \NewDocumentCommand{\ifoot}{s o m}{}%
21 \DeclareDocumentCommand{\automark}{s o m}{}%
22 \DeclareDocumentCommand{\manualmark}{}{}%
23 \DeclareDocumentCommand{\MakeMarkcase}{m}{\#1}%
24 \DeclareDocumentCommand{\GenericMarkFormat}{}{}%
25 \newcommand*{\defpairofpagestyles}[3] {} {}
26 \newcommand*{\newpairofpagestyles}[3] {} {}
27 \newcommand*{\renewpairofpagestyles}[3] {} {}
28 \newcommand*{\providepairofpagestyles}[3] {} {}
29 \newcommand*{\clearmainofpairofpagestyles}{}%

```

```

30 \newcommand*{\clearplainofpairofpagestyles}{}
31 \newcommand*{\clearpairofpagestyles}{}
32 \NewDocumentCommand{\deftriplepagestyle}{m o o m m m m m m}{}}
33 \NewDocumentCommand{\newtriplepagestyle}{m o o m m m m m m}{}}
34 \NewDocumentCommand{\renewtriplepagestyle}{m o o m m m m m m}{}}
35 \NewDocumentCommand{\providetriplepagestyle}{m o o m m m m m m}{}}
36 \newcommand*{\defpagestyle}[3] {}
37 \newcommand*{\newpagestyle}[3] {}
38 \newcommand*{\providepagestyle}[3] {}
39 \newcommand*{\renewpagestyle}[3] {}

```

File 261 **l warp-section.sty**

§ 354 Package **section**

Pkg **section** **section** is ignored.

(Emulates or patches code by OLIVER PRETZEL.)

for HTML output: 1 \LWR@ProvidesPackageDrop{section}

```

2 \ifx\chapter\undefined
3   \def\chsize{\Large}\def\hdsize{\huge}\else
4   \def\chsize{\huge}\def\hdsize{\Huge}
5 \fi
6 \let\ttsize\LARGE
7 \let\ausize\large
8 \let\dasize\large
9 \let\secsize\Large
10 \let\subsize\large
11 \let\hdpos\raggedright
12 \newcounter{hddepth}
13 \let\fpind\relax
14 \def\ttfnt{}
15 \def\hdfnt{}
16 \def\fefnt{}
17 \def\thfnt{}
18 \def\pgfnt{}
19 \def\hmkfnt{}
20 \let\mkcse\uppercase
21 \def\hddot{}
22 \def\cpdot{:}
23 \def\nmdot{}
24 \ifx\secindent\undefined
25   \newdimen\secindent
26   \newskip\secpreskp
27   \newskip\secpstskp

```

```
28 \newdimen\subindent
29 \newskip\subpreskp
30 \newskip\subpstskp
31 \newskip\parpstskp
32 \newcount\c@hddepth
33 \fi
```

File 262 **l warp-sectionbreak.sty**

§ 355 Package **sectionbreak**

(Emulates or patches code by MICHAL HOFTICH.)

Pkg **sectionbreak** **sectionbreak** is patched for use by **l warp**.

for HTML output:

```
1 \LWR@ProvidesPackagePass{sectionbreak}

2 \renewcommand\asterism{\HTMLUnicode{2042}}
3
4 \renewcommand\pre@sectionbreak{}
5 \renewcommand\post@sectionbreak{}
6
7 \renewcommand\print@sectionbreak[1]{%
8 \begin{center}
9 #1
10 \end{center}
11 }
12
```

File 263 **l warp-sectsty.sty**

§ 356 Package **sectsty**

(Emulates or patches code by ROWLAND McDONNELL.)

Pkg **sectsty** **sectsty** is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{sectsty}

2 \newcommand*\partfont           [1] {}
3 \newcommand*\partnumberfont     [1] {}
4 \newcommand*\parttitlefont      [1] {}
5 \newcommand*\chapterfont        [1] {}
6 \newcommand*\chapernumberfont   [1] {}
```

```

7 \newcommand*{\chaptertitlefont} [1] {}
8 \newcommand*{\sectionfont} [1] {}
9 \newcommand*{\subsectionfont} [1] {}
10 \newcommand*{\subsubsectionfont} [1] {}
11 \newcommand*{\paragraphfont} [1] {}
12 \newcommand*{\ subparagraphfont} [1] {}
13 \newcommand*{\minisectionfont} [1] {}
14 \newcommand*{\allsectionsfont}[1] {}
15 \newcommand{\nohang}{}

```

\sectionrule is only to be used in *font commands, thus it is ignored.

```

16 \newcommand*{\sectionrule}[5]{}
17
18 \def\ulemheading#1#2{}

```

File 264 **l warp-setspace.sty**

§ 357 Package **setspace**

(Emulates or patches code by ROBIN FAIRBAIRNS.)

Pkg **setspace** **setspace** is not used during HTML conversion.

Discard all options for **l warp-setspace**:

for HTML output:

```

1 \LWR@ProvidesPackageDrop{setspace}
2
3 \newcommand*{\setstretch}[1]{}
4 \newcommand*{\SetSinglespace}[1]{}
5 \newcommand*{\singespacing}{}
6 \newcommand*{\onehalfspacing}{}
7 \newcommand*{\doublespacing}{}
8
9 \newenvironment*{singlespace}{}
10 {
11 \LWR@forcenewpage
12 \BlockClass{singlespace}
13 }
14 {\endBlockClass}
15
16 \newenvironment*{singlespace*}{}
17 {
18 \LWR@forcenewpage
19 \BlockClass{singlespace}
20 }
21 {\endBlockClass}

```

```
22
23 \newenvironment*{spacing}[1]{
24
25 }{
26
27 }
28
29 \newenvironment*{onehalfspace}
30 {
31 \LWR@forcenewpage
32 \BlockClass{onehalfspace}
33 }
34 {\endBlockClass}
35
36 \newenvironment*{doublespace}
37 {
38 \LWR@forcenewpage
39 \BlockClass{doublespace}
40 }
41 {\endBlockClass}
```

File 265 **l warp-shadow.sty**

§ 358 Package **shadow**

(Emulates or patches code by MAURO ORLANDINI.)

Pkg **shadow** **shadow** is emulated.

for HTML output: Discard all options for **l warp-shadow**:

```
1 \LWR@ProvidesPackageDrop{shadow}

2 \newdimen\sboxsep
3 \newdimen\sboxrule
4 \newdimen\sdim
5
6 \newcommand{\shabox}[1]{%
7 \InlineClass{shabox}{#1}%
8 }
```

File 266 **l warp-showidx.sty**

§ 359 Package **showidx**

Pkg **showidx** **showidx** is ignored.

for HTML output: Discard all options for **l warp-showidx**:

1 \LWR@ProvidesPackageDrop{showidx}

\@wrindex is redefined \AtBeginDocument by the **l warp** core.

File 267 **l warp-showkeys.sty**

§ 360 Package **showkeys**

(Emulates or patches code by DAVID CARLISLE, MORTEN HØGHOLM.)

Pkg **showkeys** **showkeys** is ignored.

for HTML output: Discard all options for **l warp-showkeys**:

1 \LWR@ProvidesPackageDrop{showkeys}

2 \NewDocumentCommand{\showkeys}{s}{}

File 268 **l warp-sidecap.sty**

§ 361 Package **sidecap**

(Emulates or patches code by ROLF NIEPRASCHK, HUBERT GÄSSLEIN.)

Pkg **sidecap** **sidecap** is emulated.

for HTML output: Discard all options for **l warp-sidecap**.

1 \LWR@ProvidesPackageDrop{sidecap}

See:

<http://tex.stackexchange.com/questions/45401/>

[use-the-s-star-argument-with-newdocumentenvironment](#)
 regarding the creation of starred environments with **xparse**.

```

2 \NewDocumentEnvironment{SCtable}{soo}
3 {\IfValueTF{#3}{\table[#3]}{\table}}
4 {\endtable}
5
6 \ExplSyntaxOn
7 \cs_new:cpx {SCtable*} {\SCtable*}
8 \cs_new_eq:cN {\endSCtable*} \endSCtable
9 \ExplSyntaxOff
10
11
12 \NewDocumentEnvironment{SCfigure}{soo}
13 {\IfValueTF{#3}{\figure[#3]}{\figure}}
14 {\endfigure}
15
16 \ExplSyntaxOn
17 \cs_new:cpx {SCfigure*} {\SCfigure*}
18 \cs_new_eq:cN {\endSCfigure*} \endSCfigure
19 \ExplSyntaxOff
20
21
22 \newenvironment*{wide}{}{}

```

File 269 **l warp-sidenotes.sty**

§ 362 Package **sidenotes**

(Emulates or patches code by ANDY THOMAS, OLIVER SCHEBAUM.)

Pkg **sidenotes** Patched for **l warp**.

for HTML output: Load the original package:

```
1 \LWR@ProvidesPackagePass{sidenotes}
```

The following patch **sidenotes** for use with **l warp**:

```

\sidenote * [<entry>] [<offset>] {<text>}
2 \RenewDocumentCommand \sidenote {s o o +m}
3 {
4   \LWR@stoppars
5   \begingroup
6   \captionsetup{style=sidenote}
7   \IfBooleanTF{#1}

```

```

8   { % starred
9     \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}
10    \caption*{#4}
11    \end{BlockClass}
12  }
13 { % unstarred
14 \IfNoValueOrEmptyTF{#2}
15   {\def\@sidenotes@sidecaption@tof{#4}}
16   {\def\@sidenotes@sidecaption@tof{#2}}
17   \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}
18   \caption[\@sidenotes@sidecaption@tof]{#4}
19   \end{BlockClass}
20 }
21 \endgroup
22 \LWR@startpars
23 }
```

Borrowed from the **l warp** version of **keyfloat**:

```

24 \NewDocumentEnvironment{KFLTsidenotes@marginfloat}{O{-1.2ex} m}
25 {%
26 \LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}{marginblock}%
27 \captionsetup{type=#2}%
28 }
29 {%
30 \endLWR@BlockClassWP%
31 }
32
33 \RenewDocumentEnvironment{marginfigure}{o}
34  {\begin{KFLTsidenotes@marginfloat}{figure}}
35  {\end{KFLTsidenotes@marginfloat}}
36
37 \RenewDocumentEnvironment{margintable}{o}
38  {\begin{KFLTsidenotes@marginfloat}{table}}
39  {\end{KFLTsidenotes@marginfloat}}
```

The following were changed by **sidenotes**, and now are reset back to their **l warp**-supported originals:

Restoring the definition from the **TEX2E** `article.cls` source:

```

40 \renewenvironment{figure*}
41           {\@dblflo@{figure}}
42           {\end@dblflo@}
43
44 \renewenvironment{table*}
45           {\@dblflo@{table}}
46           {\end@dblflo@}
```

File 270 **l warp-SIunits.sty**

§ 363 Package **SIunits**

(Emulates or patches code by MARCEL HELDOORN.)

Pkg **SIunits** **SIunits** is patched for use by **l warp**.

It is recommended to use `\unit` where possible, which combines the entire expression into a single `lateximage`, and adds the `alt` tag containing the \LaTeX code, allowing for copy/paste. When `units` are used outside of the `\unit` macro, each `unit` macro will have its own `lateximage`, and each will have the `alt` tag set to “`<\mathimagedata>`”, which defaults to “`(math image)`”.

for HTML output: 1 `\LWR@ProvidesPackagePass{SIunits}`

Patched for copy/paste with the `HTML alt` tag:

```

2 \DeclareRobustCommand{\unit}[2]{%
3 \@inunitcommandtrue%    original
4 \LWR@subsingle$% l warp
5 {% alt tag
6   \textbackslash{}unit\{\LWR@HTMLsanitize{\#1}\}%
7   \{ \LWR@HTMLsanitize{\#2}\}% extra space
8 }%
9 {SIunits}% add'l hashing
10 {%
11   \LWR@origensuredmath% l warp modification
12   \SI@fstyle{\#1\@qsk\period@active{\#2}}% original
13 }%
14 }% contents
15 \@inunitcommandfalse% original
16 }
```

File 271 **l warp-siunitx.sty**

§ 364 Package **siunitx**

(Emulates or patches code by JOSEPH WRIGHT.)

Pkg **siunitx** **siunitx** is patched for use by **l warp**.

fractions Due to `pdftotext` limitations, fraction output is replaced by symbol output for

per-mode and quotient-mode.

- ⚠ **math mode required** Some units will require that the expression be placed inside math mode.

NOTE: As of this writing, the **siunitx** extension for MATHJAX is not currently hosted at any public CDN, thus **siunitx** is not usable with MATHJAX unless a local copy of this extension is created first.

- ⚠ **tabular** Tabular S columns are rendered as simple c columns, and tabular s columns are not supported. These may be replaced by c columns with each cell contained in \num or \si.

```
for HTML output: 1 \RequirePackage{xcolor}%
2 % for \convertcolorspec
3 \LWR@ProvidesPackagePass{siunitx}

4 \AtBeginDocument{%
5   % in case textcomp was not loaded
6   \DeclareSIUnit\bohr{\textit{a}\textsubscript{0}}
7   \DeclareSIUnit\clight{\textit{c}\textsubscript{0}}
8   \DeclareSIUnit\elementarycharge{\textit{e}}
9   \DeclareSIUnit\electronmass{\textit{m}\textsubscript{e}}
10  \DeclareSIUnit\hartree{\textit{E}\textsubscript{h}}
11  \DeclareSIUnit\planckbar{\LWR@siunitx@textplanckbar}
12 }%
13 AtBeginDocument
```

\@ensuredmath is not supported inside an \hbox, so it must temporarily be restored to its original. Similar for \mbox. SVG math is created explicitly when necessary, using \LWR@subsingle\$.

```
12
13 \ExplSyntaxOn
14 %
```

Modified to set set HTML \textcolor if not black:

```
15 \cs_undefine:N \__siunitx_print_aux:
16 \cs_new_protected:Npn \__siunitx_print_aux:
17 {
18   \text
19   {
20     \__siunitx_ensure_ltr:n
21     {
22       \color@begingroup
23       \__siunitx_print_color:
24       \__siunitx_font_shape:
25       \__siunitx_font_weight:
26       \use:c
27       {
```

```
28          @@_ \l_siunitx_print_type_tl -
29          text \l_siunitx_font_family_tl :
30      }
31      \bool_if:NTF \l_siunitx_font_math_mode_bool
32      { \l_siunitx_print_math: }
33      {
34          \LWR@findcurrenttextcolor% lwarp
35          \ifdefstring{\LWR@tempcolor}{000000}% lwarp
36          {\l_siunitx_print_text:}% lwarp
37          {% lwarp
38              \LWR@textcurrentcolor{%
39                  \l_siunitx_print_text:
40              }%
41          }%
42      }
43      \color@endgroup
44  }
45 }
46 }
47
48 \cs_undefine:N \l_siunitx_set_math_fam:n
49 \cs_new_protected:Npn \l_siunitx_set_math_fam:n #1 {
50     \int_new:c { c_siunitx_math #1 _int }
51     \group_begin:% lwarp
52         \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
53         \LetLtxMacro\mbox\LWR@print@mbox% lwarp
54         \hbox_set:Nn \l_siunitx_tmp_box
55         {
56             \ensuremath
57             {
58                 \use:c { math #1 }
59             }
60             {
61                 \int_gset:cn { c_siunitx_math #1 _int } { \fam }
62             }
63         }
64     }
65     \group_end:% lwarp
66 }
67
68 \cs_undefine:N \l_siunitx_combined_output:n
69 \cs_new_protected:Npn \l_siunitx_combined_output:n #1 {
70     \group_begin:% lwarp
71     \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
72     \LetLtxMacro\mbox\LWR@print@mbox% lwarp
73     \bool_if:NTF \l_siunitx_number_parse_bool
74     {
75         \tl_clear:N \l_siunitx_number_out_tl
76         \bool_set_false:N \l_siunitx_number_compound_bool
77         \l_siunitx_number_output_parse:n {#1}
```

```

78      }
79      {
80      \_\_siunitx\_unit\_output\_pre\_print:

```

For parse-numbers=false:

```

81 \%      \_\_siunitx\_print:nn { number } { \ensuremath {\#1} } }
82      \LWR@subsingle dollar{\% l warp
83          \textbackslash ( \LWR@HTMLsanitize{\#1} \textbackslash ) \% l warp
84      \{ siunitx\} \% 
85          \_\_siunitx\_print:nn { number } {%
86              \LWR@origensuredmath{\#1}%
87          }%
88      } \% l warp

89      \_\_siunitx\_unit\_output\_print:
90  }
91  \group_end:\% l warp
92 }
93 %

```

For quotients, the fraction code is replaced by the symbol code:

```

94 \cs_undefine:N \_\_siunitx_number_output_quotient_fraction:
95 \cs_new_protected:Npn \_\_siunitx_number_output_quotient_fraction: {
96     \bool_set_true:N \l__siunitx_number_compound_bool
97     \_\_siunitx_number_output_quotient_aux_i:
98     \tl_set_eq:NN \l__siunitx_number_out_tl
99         \l__siunitx_number_numerator_tl
100    \tl_put_right:NV \l__siunitx_number_out_tl \l__siunitx_output_quotient_tl
101    \tl_put_right:NV \l__siunitx_number_out_tl
102        \l__siunitx_number_denominator_tl
103    \_\_siunitx_number_output_single_aux:
104 }

```

For units, the fraction code is replaced by the symbol code:

```

105 \cs_undefine:N \_\_siunitx_unit_format_fraction_fraction:
106 \cs_new_protected:Npn \_\_siunitx_unit_format_fraction_fraction: {
107     \_\_siunitx_unit_format_fraction_symbol_aux:
108     \int_compare:nNnT { \l__siunitx_unit_denominator_int } > { 1 }
109     {
110         \bool_if:NT \l__siunitx_unit_denominator_bracket_bool
111         {
112             \tl_put_left:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_open_tl
113             \tl_put_right:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_close_tl
114         }
115     }
116     \tl_set_eq:NN \l__siunitx_unit_tl \l__siunitx_unit_numerator_tl

```

```
117 \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_per_symbol_tl
118 \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_unit_denominator_tl
119 }

120 \cs_undefine:N \__siunitx_angle_print_astronomy_aux:
121 \cs_new_protected:Npn \__siunitx_angle_print_astronomy_aux: {
122   \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-integer }
123   \l__siunitx_tmpa_tl
124   { \__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
125   \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
126   {\% lateximage
127     \hbox_set:Nn \l__siunitx_angle_marker_box
128     {
129       \__siunitx_print:nn { number } { { \l__siunitx_output_decimal_tl } }
130     }
131     \hbox_set:Nn \l__siunitx_angle_unit_box
132     {
133       \__siunitx_print:nV { unit } \l__siunitx_unit_tl
134       \skip_horizontal:n { -\scriptspace }
135     }
136   \__siunitx_angle_print_astronomy_aux:n { marker }
137   \__siunitx_angle_print_astronomy_aux:n { unit }
138   \hbox_set:Nn \l__siunitx_angle_marker_box
139   {
140     \box_use:N \l__siunitx_angle_marker_box
141     \box_use:N \l__siunitx_angle_unit_box
142   }
143 \dim_compare:nNnTF
144   { \l__siunitx_angle_marker_dim } > { \l__siunitx_angle_unit_dim }
145   { \__siunitx_angle_print_astronomy_marker: }
146   { \__siunitx_angle_print_astronomy_unit: }
147 }%
148 {\% not a lateximage
149   \__siunitx_print:nV { unit } \l__siunitx_unit_tl
150   \__siunitx_print:nn { number } { { \l__siunitx_output_decimal_tl } }
151 }%
152 {\% not a lateximage
153   \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-decimal }
154   \l__siunitx_tmpa_tl
155   { \__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
156 }

156 \RenewDocumentCommand \num { o m } {
157   \leavevmode
158   \group_begin: \% lwarp
159   \LetLtxMacro \ensuredmath \LWR@origensuredmath \% lwarp
160   \LetLtxMacro \mbox \LWR@print@mbox \% lwarp
161   \bool_set_false:N \l__siunitx_font_set_bool
162   \IfNoValueF {#1}
163   { \keys_set:nn { siunitx } {#1} }
```

```
164     \__siunitx_number_output:n {#2}
165   \group_end:% l warp
166 }
167
168 \RenewDocumentCommand \numrange { o m m } {
169   \leavevmode
170   \group_begin:% l warp
171     \LetLtxMacro\@ensuredmath\LWR@origensuredmath% l warp
172     \LetLtxMacro\mbox\LWR@print@mbox% l warp
173     \bool_set_false:N \l__siunitx_font_set_bool
174     \IfNoValueF {#1}
175       { \keys_set:nn { siunitx } {#1} }
176     \__siunitx_range_numbers:nn {#2} {#3}
177   \group_end:% l warp
178 }
179
180 \RenewDocumentCommand \ang { o > { \SplitArgument { 2 } { ; } } m } {
181   \group_begin:% l warp
182     \LetLtxMacro\@ensuredmath\LWR@origensuredmath% l warp
183     \LetLtxMacro\mbox\LWR@print@mbox% l warp
184     \IfNoValueF {#1}
185       { \keys_set:nn { siunitx } {#1} }
186     \__siunitx_angle_output:nnn #2
187   \group_end:% l warp
188 }
189
190 \RenewDocumentCommand \si { o m } {
191   \leavevmode
192   \group_begin:% l warp
193     \LetLtxMacro\@ensuredmath\LWR@origensuredmath% l warp
194     \LetLtxMacro\mbox\LWR@print@mbox% l warp
195     \bool_set_false:N \l__siunitx_font_set_bool
196     \IfNoValueTF {#1}
197       { \__siunitx_unit_output:nn {#2} { } }
198       {
199         \keys_set:nn { siunitx } {#1}
200         \__siunitx_unit_output:nn {#2} {#1}
201       }
202   \group_end:% l warp
203 }
204
205
206 \RenewDocumentCommand{\SIrange}{o m m m}
207 {%
208   \leavevmode
209   \group_begin:% l warp
210     \LetLtxMacro\@ensuredmath\LWR@origensuredmath% l warp
211     \LetLtxMacro\mbox\LWR@print@mbox% l warp
212     \bool_set_false:N \l__siunitx_font_set_bool
213     \IfNoValueTF {#1}
```

```

214      { \_siunitx_range_unit:nnnn {#4} { } {#2} {#3} }
215      {
216          \keys_set:nn { siunitx } {#1}
217          \_siunitx_range_unit:nnnn {#4} {#1} {#2} {#3}
218      }
219      \group_end: \% l warp
220 }
221
222 \ExplSyntaxOff

```

File 272 **l warp-soul.sty**

§ 365 Package **soul**

(Emulates or patches code by MELCHIOR FRANZ.)

Pkg **soul** Emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{soul}[2003/11/17]
2 \RequirePackage{xcolor}%
  for \convertcolorspec

```

Storage for the colors to use:

```

3 \newcommand*\{\LWR@soululcolor\}{}%
4
5 \newcommand*\{\LWR@soulstcolor\}{}%
6
7 \% \definecolor{\LWR@soulhlcolordefault}{HTML}{F8E800}
8 \% \newcommand*\{\LWR@soulhlcolor\}{\LWR@soulhlcolordefault}
9 \newcommand*\{\LWR@soulhlcolor\}{}%

```

\so \{<text>\}

Basic markup with css:

```

10 \newcommand{\so}[1]{%
11 \LWR@HTMLtextstyle{letter-spacing:.2ex}{letterspacing}{#1}%
12 }

```

\caps \{<text>\}

```

13 \newcommand{\caps}[1]{%
14 \LWR@HTMLtextstyle{%
15     {font-variant:small-caps;letter-spacing:.1ex}%
16     {capsspacing}{#1}%
17 }

```

```
\LWR@soulcolor {<text>} {<color>} {<class>} {<colorstyle>} {<FormatWPstyle>}

Add colors if not empty:

18 \newcommand{\LWR@soulcolor}[5]{%
19 \ifcsempty{#2}{%
20 {\LWR@HTMLtextstyle{#5}{#3}{#1}}{%
21 {%
22   \convertcolorspec{named}{\nameuse{#2}}{HTML}\LWR@tempcolor{%
23     \LWR@htmlspanclass[#5;\#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}}{%
24 }{%
25 }{%
26 \newcommand{\ul}[1]{%
27 \LWR@soulcolor{#1}{\LWR@soululcolor}{\uline}{text-decoration-color}{%
28   {text-decoration:underline; text-decoration-skip: auto;}}{%
29 }{%
30 \newcommand{\st}[1]{%
31 \LWR@soulcolor{#1}{\LWR@soulstcolor}{\sout}{text-decoration-color}{%
32   {text-decoration:line-through}}{%
33 }{%
34 }{%
35 \newcommand{\hl}[1]{%
36 \LWR@soulcolor{#1}{\LWR@souhlcolor}{highlight}{background-color}{%
37   {background:\LWR@origpound{}F8E800}}{%
38 }{%
39 }}
```

Nullified:

```
40 \newcommand*\soulaccent}[1]{}
41 \newcommand*\soulregister}[2]{}
42 \newcommand\sloppyword}[1]{#1}
43 \newcommand*\sodef}[5]{\DeclareRobustCommand*#1[1]{\so{##1}}}
44 \newcommand*\resetso}{}
45 \newcommand*\capsdef}[5]{}
46 \newcommand*\capsreset}{}
47 \newcommand*\capssave}[1]{}
48 \newcommand*\capsselect}[1]{}
49 \newcommand*\setul}[2]{}
50 \newcommand*\resetul}{}
51 \newcommand*\setuldepth}[1]{}
52 \newcommand*\setuloverlap}[1]{}
```

Set colors:

```
53 \newcommand*\setulcolor}[1]{\renewcommand{\LWR@soululcolor}{#1}}
54 \newcommand*\setstcolor}[1]{\renewcommand{\LWR@soulstcolor}{#1}}
55 \newcommand*\sethlcolor}[1]{\renewcommand{\LWR@souhlcolor}{#1}}
```

Long versions of the user-level macros:

```
56 \let\textso\so
57 \let\textul\ul
58 \let\texthl\hl
59 \let\textcaps\caps
```

File 273 **l warp-soulpos.sty**

§ 366 Package **soulpos**

(Emulates or patches code by JAVIER BEZOS.)

Pkg soulpos **soulpos** is emulated.

for HTML output:

```
1 \RequirePackage{soul}
2 \RequirePackage{soulutf8}
3 \LWR@ProvidesPackageDrop{soulpos}

4 \NewDocumentCommand{\ulposdef}{m o m}{}%
5
6 \newdimen\ulwidth
7
8 \newcommand\ifulstarttype[1]{%
9 \expandafter\@secondoftwo%
10 }
11
12 \newcommand\ifulenctype[1]{%
13 \expandafter\@secondoftwo%
14 }
15
16 \newcommand{\ulstarttype}{0}
17 \newcommand{\ulenctype}{0}
18 \newcommand{\ulpostolerance}{0}%

```

File 274 **l warp-soulutf8.sty**

§ 367 Package **soulutf8**

Pkg soulutf8 **soulutf8** is emulated.

l warp's HTML output naturally supports UTF-8 encoding.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{soulutf8}
```

File 275 **l warp-splitidx.sty**

§ 368 Package **splitidx**

(Emulates or patches code by MARKUS KOHM.)

Pkg **splitidx** **splitidx** is patched for use by **l warp**.

If the `latexmk` option is selected for **l warp**, `latexmk` will compile the document but will *not* compile the indexes. `l warpmk printindex` and `l warpmk htmlindex` will still be required.

⚠ **\thepage** When using `\AtWriteToIndex` or `\AtNextWriteToIndex`, the user must not refer to `\thepage` during HTML output, as the concept of a page number is meaningless. Instead, do

```
\addtocounter{LWR@autoindex}{1}
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}
```

where the `\index`-like action occurs, and then refer to `\arabic{LWR@autoindex}` instead of `\thepage` where the reference should occur.

See section 440.17 in the **l warp-patch-memoir** package for the `\@@wrsindexhyp` macro as an example.

for HTML output: 1 `\LWR@ProvidesPackagePass{splitidx}`

```
2 \catcode`\_=12%
3 \xpatchcmd{\newindex}
4   {\jobname-#2.idx}
5   {\jobname-#2_html.idx}
6   {}
7   {\LWR@patcherror{splitidx}{\newindex}}
8 \catcode`\_=8%
```

Patched to use **l warp**'s automatic indexing counter instead of `\thepage`:

```
9 \renewcommand*{\@wrsindex}[2][]{%
10   \ifx\relax#1\relax
11   \if@splitidx
12     \@wrsindex[idx]{#2}%
13   \else
14     \def\@tempa{#2}%
15     \if@verbindex\@onelvel@sanitize\@tempa\fi
```

```

16      \@wrindex{\@tempa}%
17      \fi
18  \else
19      \def\@tempa{#2}%
20      \csname index@#1@hook\endcsname
21 %     \expandafter\ifx\csname @@wrsindex\endcsname\relax
22 %       \addtocounter{LWR@autoindex}{1}%           l warp
23 %       \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%   l warp
24 %         \@@wrsindex{#1}{\@tempa}{\thepage}%
25 %         \@@wrsindex{#1}{\@tempa}{\arabic{LWR@autoindex}}%
26 %     \else
27 %       \def\@tempb{\@@wrsindex{#1}}%
28 %       \expandafter\@tempb\@tempa||\\%
29 %
30      \endgroup
31      \esphack
32  \fi
33 }

```

l warp defines sectioning commands with **xparse**, so the below patches are done as temporary redefinitions instead of being **\let**.

```

34 \xpatchcmd{\printsubindex}
35   {\let\section\subsection}
36   {\renewcommand*\section{\subsection}}
37   {}
38   {\LWR@patcherror{splitidx}{printsubindex-section}}
39
40 \xpatchcmd{\printsubindex}
41   {\let\chapter\section}
42   {\renewcommand*\chapter{\section}}
43   {}
44   {\LWR@patcherror{splitidx}{printsubindex-chapter}}
45
46 \xpatchcmd{\printsubindex}
47   {\let\@makechapterhead\section}
48   {\def\@makechapterhead{\section}}
49   {}
50   {\LWR@patcherror{splitidx}{printsubindex-chapter}}

```

File 276 **l warp-srcltx.sty**

§ 369 Package **srcltx**

Pkg **srcltx** **srcltx** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{srcltx}[2006/11/12]

```
2 \newif\ifSRCOK \SRCOKfalse
3 \newcommand*\srcIncludeHook[1]{}
4 \newcommand*\srcInputHook[1]{}
5 \newcommand*\MainFile{}
6 \def\MainFile{\jobname.tex}
7 \newcommand*\CurrentInput{}
8 \gdef\CurrentInput{\MainFile}
9 \newcommand\Input{}
10 \let\Input\input
```

File 277 **l warp-srctex.sty**

§ 370 Package **srctex**

Pkg **srctex** **srctex** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{srctex}[2006/11/12]
2 \LWR@origRequirePackage{l warp-srcctx}

File 278 **l warp-stabular.sty**

§ 371 Package **stabular**

(Emulates or patches code by SIGITAS TOLUŠIS.)

Pkg **stabular** **stabular** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{stabular}

```
Env stabular [<vpos>] {[<colspec>]}
2 \newenvironment{stabular}[2][c]
3 {
4 \begin{tabular}[#1]{#2}
5 \renewcommand{\noalign}{[1]{}}
6 }
7 {\end{tabular}}
Env stabular {[<width>]} [<vpos>] {[<colspec>]}
8 \NewDocumentEnvironment{stabular*}{m o m}
9 {
10 \begin{tabular}[#2]{#3}
```

```
11 \renewcommand{\noalign}{[1]{}
12 }
13 {\end{tabular}}
```

File 279 **l warp-stffloats.sty**

§ 372 Package **stffloats**

Pkg stffloats **stffloats** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{stffloats}

2 \newcommand*{\fnbelowfloat}{}
3 \newcommand*{\fnunderfloat}{}
4 \newcommand*{\setbaselinefloat}{}
5 \newcommand*{\setbaselinefixed}{}
```

File 280 **l warp-subfig.sty**

§ 373 Package **subfig**

(Emulates or patches code by STEVEN DOUGLAS COCHRAN.)

Pkg subfig **subfig** is supported and patched by **l warp**.

⚠ **lof/lotdepth** At present, the package options for `lofdepth` and `lotdepth` are not working. These counters must be set separately after the package has been loaded.

In the document source, use `\hfill` and `\hspace*` subfig>inline between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

for HTML output: Accept all options for **l warp-subfig**:

```
1 \LWR@ProvidesPackagePass{subfig}
```

`\sf@@@subfloat {<1 type>} [<2 lof entry>] [<3 caption>] [<4 contents>]`

The outer minipage allows side-by-side subfloats with `\hfill` between.

```
2 \long\def\sf@@@subfloat#1[#2][#3]{%
3 \begin{minipage}{\linewidth} l warp
```

```

4 \IfValueTF{#2}{%
5   \LWR@setlatestname{#2}%
6 }{%
7   \IfValueTF{#3}{%
8     \LWR@setlatestname{#3}%
9   }{}%
10 }%
11 \LWR@stopars% lwarf
12 \@ifundefined{FBsc@max}{}{%
13   {\FB@readaux{\let\FBsubohight\relax}}%
14 \tempcpta=\@ne
15 \if@minipage
16   \tempcpta=\z@
17 \else\ifdim \lastskip=\z@ \else
18   \tempcpta=\tw@
19 \fi\fi
20 \ifmaincaptiontop
21   \sf@top=\sf@nearskip
22   \sf@bottom=\sf@farskip
23 \else
24   \sf@top=\sf@farskip
25   \sf@bottom=\sf@nearskip
26 \fi
27 \leavevmode

28 % \setbox\tempboxa \hbox{#4}%
29 % \tempdima=\wd\tempboxa
30 % \ifundefined{FBsc@max}{}{%
31 %   {\global\advance\Xhsiz-\wd\tempboxa
32 %    \dimen@\ht\tempboxa
33 %    \advance\dimen@\dp\tempboxa
34 %    \ifdim\dimen@>\FBso@max
35 %      \global\FBso@max\dimen@
36 %    \fi}%

```

Do not use boxes, which interfere with `\textrimage`:

```

37 % \vtop%
38 \bgroup
39 % \vbox%
40 \bgroup
41 \ifcase\tempcpta
42   \minipagetrue
43 \or
44 % \vskip\sf@top
45 \or
46   \ifdim \lastskip=\z@ \else
47 %   \tempskipb\sf@top\relax\addvskip
48   \fi
49 \fi

```

```
50      \sf@ifpositiontop{%
51          \ifx \empty#3\relax \else
52              \sf@subcaption{#1}{#2}{#3}%
53 %
54 %              \vskip\sf@skip
55 %              \vskip\sf@captionadj
56 %
57          \fi\egroup
58 %          \hrule width0pt height0pt depth0pt
59 %          \LWR@startpars% l warp
60 %
61          \box\@tempboxa
62          #4
63          \LWR@stoppars% l warp
64 %
65 %          \box\@tempboxa
66          #4
67          }%
68          \LWR@startpars% l warp
69 %
70          \ifx\FBsubohight\relax
71              \box\@tempboxa
72          #4
73          \else
74              \vbox to \FBsubohight{\FBafil\box\@tempboxa\FBbfil}%
75          #4
76          \fi}%
77          \LWR@stoppars% l warp
78          \egroup
79          \ifx \empty#3\relax \else
80              \vskip\sf@skip
81 %              \hrule width0pt height0pt depth0pt
82 %              \sf@subcaption{#1}{#2}{#3}%
83 %
84          \fi
85          }%
86          \vskip\sf@bottom
87          \egroup
88          \ifundefined{FBsc@max}{}
89          {\addtocounter{FRobj}{-1}%
90          \ifnum\c@FRobj=0\else
91              \subfloatrowsep
92          \fi}%
93          \ifmaincaptiontop\else
94              \global\advance\@nameuse{c@\@capttype}\m@ne
95          \fi
96      \end{minipage}%
97      \LWR@startpars% l warp
98      \endgroup\ignorespaces%
99 }%
```

\sf@subcaption {<1 type>} {<2 lof entry>} {<3 caption>}

```
97 \long\def\sf@subcaption#1#2#3{%
98 \LWR@stopars% l warp
99   \ifx \relax#2\relax \else
100    \bgroup
101      \let\label=\@gobble
102      \let\protect=\string
103      \def\@subcaplabel{%
104        \caption@listfmt{\@nameuse{p#1}}{\@nameuse{the#1}}%
105        \sf@updatecaptionlist{#1}{#2}{\the\value{\@capttype}}{\the\value{#1}}%
106      \egroup
107    \fi
108    \bgroup
109      \ifx \relax#3\relax
110        \let\captionlabelsep=\relax
111      \fi
112    \setbox0\vbox{%
113      \hb@xt@\the\tempdima{%
114      %
115      %          \hss
116      %          \parbox[t]{\the\tempdima}{%
117      %          \caption@make
118      %            {\@nameuse{sub\@capttype name}}%
119      %            {\@nameuse{thesub\@capttype}}%
120      %            {#3}
121      %          }%
122      %          \hss
123      %
124      %
125      \@ifundefined{FBsc@max}%
126      %          {\box0}%
127      %
128      \parbox[t]{\the\tempdima}{%
129 \LWR@traceinfo{sfsubcap B1}% l warp
130           \LWR@figcaption% l warp
131           \caption@make
132           {\@nameuse{sub\@capttype name}}%
133           {\@nameuse{thesub\@capttype}}%
134           {#3}
135           \endLWR@figcaption% l warp
136 \LWR@traceinfo{sfsubcap B2}% l warp
137   }%
138   }%
139   {\dimen@\ht0%
140     \advance\dimen@\dp0%
141     \ifdim\dimen@>\FBsc@max
142       \global\FBsc@max\dimen@
143     \fi
144     \FB@readaux{\let\FBsubcheight\relax}%
145     \ifx\FBsubcheight\relax
```

```

146          \def\next{%
147 %  \parbox[t]{\the\@tempdima}%
148          }%
149          \else
150          \def\next{%
151 %  \parbox[t][\FBsubcheight][t]{\the\@tempdima}%
152          }%
153          \fi
154 %
155 %          \vbox{%
156 %              \hb@xt@\the\@tempdima{%
157 %
158 %                  \hss
159 %                  \next{%
160 %                      \LWR@traceinfo{sfsubcap C1}{ l warp
161 %                          \caption@make
162 %                          {\@nameuse{sub\@capttype name}}%
163 %                          {\@nameuse{thesub\@capttype}}%
164 %                          {\#3}
165 %                      \LWR@traceinfo{sfsubcap C1}{ l warp
166 %                          }%
167 %                          \hss
168 %
169 %                      }
170 %                  }%
171 %                  \egroup
172 %\LWR@startpars% l warp
173 }

```

\subfloat@label Patches for \sf@sub@label:

```

174 \def\subfloat@label{%
175 \LWR@ensuredoingapar% l warp
176 \@ifnextchar(% ) match left parenthesis
177 { \sf@sub@label}
178 { \sf@sub@label( \Sub\@capttype\space
179 \ifundefined{thechapter}{}{\@nameuse{thechapter}\space}%
180 \nameuse{p@sub\@capttype}%
181 \nameuse{thesub\@capttype}.) }%

```

Patches for \subref.

\sf@subref {<label>}

The unstarred version uses a \ref link whose printed text comes from the sub@<label>:

```

182 \renewcommand{\sf@subref}[1]{%
183 \LWR@subnewref{\#1}{sub@#1}%
184 }

```

```
\sf@@subref {<label>}
```

The starred version uses the printed `sub@<label>` which is stored as if it were a page number:

```
185 \renewcommand{\sf@@subref}[1]{\LWR@orig@pageref{sub@#1}}
```

Defining new subfloats. The `l@sub<type>` for each is redefined.

```
\@newsubfloat [{<keys/values>}]{<float name>}
```

```
186 \LetLtxMacro{\LWR@orig@newsubfloat}{\newsubfloat}
```

```
187
```

```
188 \def\@newsubfloat[#1]#2{%
```

```
189 \LWR@orig@newsubfloat[#1]{#2}%
```

```
190 \renewcommand{\l@sub#2}[2]{\hypertocfloat{2}{sub#2}{\ext@sub#2}{##1}{##2}}%
```

```
191 }
```

Pre-defined for figures and tables:

```
\l@subfigure {<text>} {<pagenum>}
```

```
192 \renewcommand{\l@subfigure}[2]{\hypertocfloat{2}{subfigure}{lof}{#1}{#2}}
```

```
\l@subtable {<text>} {<pagenum>}
```

```
193 \renewcommand{\l@subtable}[2]{\hypertocfloat{2}{subtable}{lot}{#1}{#2}}
```

File 281 `l warp-subfigure.sty`

§ 374 Package **subfigure**

Pkg `subfigure` **subfigure** is emulated by **subfig**.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{subfigure}
2 \RequirePackage{subfig}
```

```
3 \LetLtxMacro{\subfigure}{\subfloat}
```

```
4 \LetLtxMacro{\subtable}{\subfloat}
```

```
5 \LetLtxMacro{\Subref}{\subref}
```

```
6 \@ifundefined{figuretopcaptrue}{\newif\iffiguretopcap{}}
```

```
7 \newif\ifsubfiguretopcap
```

```
8 \newif\ifsubcaphang
```

```
9 \newif\ifsubcapcenter
```

```
10 \newif\ifsubcapcenterlast
```

```
11 \newif\ifsubcapnooneline
```

```

12 \newif\ifsbcraggedright
13 \newskip\subfigtopskip
14 \newskip\subfigcapskip
15 \newdimen\subfigcaptopadj
16 \newskip\subfigbottomskip
17 \newdimen\subfigcapmargin
18 \newskip\subfiglabelskip
19 \newcommand*\subcapsize{}{}}
20 \newcommand*\subcaplabelfont{}{}}
21 \newcommand*\subcapfont{}{}}
```

File 282 **l warp-supertabular.sty**

§ 375 Package **supertabular**

(Emulates or patches code by JOHANNES BRAAMS, THEO JURRIENS.)

Pkg **supertabular** **supertabular** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{supertabular}

⚠ Misplaced alignment tab character & For \tablefirsthead, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
...
\StopDefiningTabulars
```

See section 9.9.

⚠ lateximage **supertabular** and **xtab** are not supported inside a **lateximage**.

```

2 \newcommand{\LWRST@firsthead}{}%
3
4 \newcommand{\tablefirsthead}[1]{%
5   \long\gdef\LWRST@firsthead{\#1}%
6 }
7
8 \newcommand{\tablehead}[1]{}%
9 \newcommand{\tabletail}[1]{}%
10
11 \newcommand{\LWRST@lasttail}{}%
12
13 \newcommand{\tablelasttail}[1]{%
14   \long\gdef\LWRST@lasttail{\#1}%
15 }
```

```
16 \newcommand{\tablecaption}[2] []{%
17     \long\gdef\LWRST@caption{%
18         \ifblank{#1}{%
19             {\caption{#2}}%
20             {\caption[#1]{#2}}%
21         }%
22     }%
23 }
24 \let\topcaption\tablecaption
25 \let\bottomcaption\tablecaption

26 \newcommand*{\LWRST@caption}{}%
27
28 \newcommand*{\shrinkheight}[1]{}%
29
30 \NewDocumentEnvironment{supertabular}{s o m}%
31 {%
32 \LWR@traceinfo{supertabular}%
33 \begin{table}%
34 \LWRST@caption{%
35 \begin{tabular}{#3}%
36 \TabularMacro\ifdefvoid{\LWRST@firsthead}{%
37 {\LWR@getmynexttoken}%
38 {\expandafter\LWR@getmynexttoken\LWRST@firsthead}%
39 }%
40 {%
41 \ifdefvoid{\LWRST@lasttail}{%
42 {}%
43 {%
44 \TabularMacro\ResumeTabular{%
45 \LWRST@lasttail}%
46 }%
47 \end{tabular}%
48 \end{table}%
49 \LWR@traceinfo{supertabular done}%
50 }%
51
52 \NewDocumentEnvironment{mpsupertabular}{s o m}%
53 {\minipage{\linewidth}\supertabular{#3}}%
54 {\endsupertabular\endminipage}
```

File 283 **l warp-syntonly.sty**

§ 376 Package **syntonly**

(Emulates or patches code by FRANK MITTELBACH, RAINER SCHÖPF.)

Pkg **syntonly** Emulated.

for HTML output: Discard all options for **l warp-syntonly**:

```
1 \LWR@ProvidesPackageDrop{syntonly}

2 \newif\ifsyntax@
3 \syntax@false
4
5 \newcommand*{\syntaxonly}{}{}
6
7 \@onlypreamble\syntaxonly
```

File 284 **l warp-t1enc.sty**

§ 377 Package **t1enc**

Pkg **t1enc** **t1enc** does not work with **l warp**.

for HTML output: 1 \LWR@loadnever{t1enc}{fontenc, inputenc, inputenx}

File 285 **l warp-tables.sty**

§ 378 Package **tables**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg **tables** **tables** is emulated. \LWR@hline is used to handle the optional argument when **tables** is loaded.

for HTML output: 1 \LWR@ProvidesPackageDrop{tables}

2 \newdimen\tablinesep
3 \newdimen\arraylinesep
4 \newdimen\extrarulesep

File 286 **l warp-tabularx.sty**

§ 379 Package **tabularx**

(Emulates or patches code by DAVID CARLISLE.)

Pkg tabularx **tabularx** is emulated by **l warp**.

for HTML output: Discard all options for **l warp-tabularx**:

```
1 \LWR@ProvidesPackageDrop{tabularx}

2 \DeclareDocumentEnvironment{tabularx}{m o m}
3 {\begin{array}{#3}}
4 {\end{array}}
5
6 \DeclareDocumentEnvironment{tabularx*}{m o m}
7 {\begin{array}{#3}}
8 {\end{array}}
```

File 287 **l warp-tabulary.sty**

§ 380 Package **tabulary**

(Emulates or patches code by DAVID CARLISLE.)

Pkg tabulary **tabulary** is emulated by **l warp**.

for HTML output: Discard all options for **l warp-tabulary**.

Column types L, C, R, and J are emulated by **l warp** core code.

```
1 \LWR@ProvidesPackageDrop{tabulary}

2 \NewDocumentEnvironment{tabulary}{m o m}
3 {\begin{array}{#3}}
4 {\end{array}}
5
6 \NewDocumentEnvironment{tabulary*}{m o m}
7 {\begin{array}{#3}}
8 {\end{array}}
9
10 \newdimen\tymin
11 \newdimen\tymax
12 \def\tyformat{}

---


```

File 288 **l warp-textarea.sty**

§ 381 Package **textarea**

(Emulates or patches code by ALEXANDER I. ROZHENKO.)

Pkg **textarea** **textarea** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{textarea}

2 \newcommand\StartFromTextArea{}
3 \newcommand\StartFromHeaderArea{}
4 \newcommand*\RestoreTextArea{}
5 \newcommand*\ExpandTextArea[1] [*]{}
6 \let\NCC@restoretarea\empty
```

File 289 **l warp-textcomp.sty**

§ 382 Package **textcomp**

(Emulates or patches code by FRANK MITTELBACH, ROBIN FAIRBAIRNS, WERNER LEMBERG.)

Pkg **textcomp** **textcomp** is patched for use by **l warp**.

§ 382.1 Limitations

Some **textcomp** symbols do not have Unicode equivalents, and thus are not supported.

⚠ **missing symbols** Many **textcomp** symbols are not supported by many fonts. In the CSS try referencing fonts which are more complete, but expect to see gaps in coverage.

§ 382.2 Package loading

for HTML output:

```
1 \LWR@ProvidesPackagePass{textcomp}
```

§ 382.3 HTML symbols

For HTML, use HTML entities or direct Unicode, depending on the engine.

\AtBeginDocument improves support for Lua^LT_EX and X^LT_EX.

§ 382.3.1 pdfL^EX symbols

```

2 \AtBeginDocument{
3 \ifPDFTeX% pdflatex or dvi latex
4 \newcommand*{\LWR@HTML@textdegree}{\HTMLentity{deg}}
5 \newcommand*{\LWR@HTML@textcelsius}{\HTMLunicode{2103}}
6 \newcommand*{\LWR@HTML@textohm}{\HTMLunicode{2126}}
7 \newcommand*{\LWR@HTML@textmu}{\HTMLunicode{00B5}}
8 \newcommand*{\LWR@HTML@textlquill}{\HTMLunicode{2045}}
9 \newcommand*{\LWR@HTML@textrquill}{\HTMLunicode{2046}}
10 \newcommand*{\LWR@HTML@textcircledP}{\HTMLunicode{2117}}
11 \newcommand*{\LWR@HTML@texttwelveudash}{\HTMLunicode{2014}}% emdash
12 \newcommand*{\LWR@HTML@textthreequartersemdash}{\HTMLunicode{2014}}% emdash
13 \newcommand*{\LWR@HTML@textmho}{\HTMLunicode{2127}}
14 \newcommand*{\LWR@HTML@textnaira}{\HTMLunicode{20A6}}
15 \newcommand*{\LWR@HTML@textpeso}{\HTMLunicode{20B1}}
16 \newcommand*{\LWR@HTML@textrecipe}{\HTMLunicode{211E}}
17 \newcommand*{\LWR@HTML@textinterrobangdown}{\HTMLunicode{2E18}}
18 \newcommand*{\LWR@HTML@textperthousand}{\HTMLunicode{2030}}
19 \newcommand*{\LWR@HTML@textpertenthousand}{\HTMLunicode{2031}}
20 \newcommand*{\LWR@HTML@textbaht}{\HTMLunicode{0E3F}}
21 \newcommand*{\LWR@HTML@textdiscount}{\%}
22 \newcommand*{\LWR@HTML@textservicemark}{\HTMLunicode{2120}}
23 \else

```

§ 382.3.2 X_L^EX and Lua_L^EX symbols

NOTE: Some of the following do not print well in the listing. Consult the .dtx or .sty file for the actual characters.

```

24 \newcommand*{\LWR@HTML@textdegree}{°}
25 \newcommand*{\LWR@HTML@textcelsius}{°C}
26 \newcommand*{\LWR@HTML@textohm}{Ω}
27 \newcommand*{\LWR@HTML@textmu}{μ}
28 \newcommand*{\LWR@HTML@textlquill}{{}}
29 \newcommand*{\LWR@HTML@textrquill}{{}}
30 \newcommand*{\LWR@HTML@textcircledP}{®}
31 \newcommand*{\LWR@HTML@texttwelveudash}{--}% emdash
32 \newcommand*{\LWR@HTML@textthreequartersemdash}{--}% emdash
33 \newcommand*{\LWR@HTML@textmho}{Ü}
34 \newcommand*{\LWR@HTML@textnaira}{₦}
35 \newcommand*{\LWR@HTML@textpeso}{₱}
36 \newcommand*{\LWR@HTML@textrecipe}{฿}
37 \newcommand*{\LWR@HTML@textinterrobangdown}{ߵ}
38 \newcommand*{\LWR@HTML@textperthousand}{٪.}
39 \newcommand*{\LWR@HTML@textpertenthousand}{٪..}
40 \newcommand*{\LWR@HTML@textbaht}{฿}
41 \newcommand*{\LWR@HTML@textdiscount}{%}

```

```

42 \newcommand*{\LWR@HTML@textservicemark}{}
43 \fi
44
45 \LWR@formatted{textdegree}
46 \LWR@formatted{textcelsius}
47 \LWR@formatted{textohm}
48 \LWR@formatted{textmu}
49 \LWR@formatted{textlquill}
50 \LWR@formatted{textrquill}
51 \LWR@formatted{textcircledP}
52 \LWR@formatted{texttwelveudash}
53 \LWR@formatted{textthreequartersemdash}
54 \LWR@formatted{textmho}
55 \LWR@formatted{textnaira}
56 \LWR@formatted{textpeso}
57 \LWR@formatted{textrecipe}
58 \LWR@formatted{textinterrobangdown}
59 \LWR@formatted{textperthousand}
60 \LWR@formatted{textpertenthousand}
61 \LWR@formatted{textbaht}
62 \LWR@formatted{textdiscount}
63 \LWR@formatted{textservicemark}

```

§ 382.4 HTML dicritics

For HTML, Unicode diacritical marks are used:

```

64 \newcommand*{\LWR@HTML@capitalcedilla}[1]{\#1\HTMLunicode{0327}}
65 \newcommand*{\LWR@HTML@capitalogonek}[1]{\#1\HTMLunicode{0328}}
66 \newcommand*{\LWR@HTML@capitalgrave}[1]{\#1\HTMLunicode{0300}}
67 \newcommand*{\LWR@HTML@capitalacute}[1]{\#1\HTMLunicode{0301}}
68 \newcommand*{\LWR@HTML@capitalcircumflex}[1]{\#1\HTMLunicode{0302}}
69 \newcommand*{\LWR@HTML@capitaltilde}[1]{\#1\HTMLunicode{0303}}
70 \newcommand*{\LWR@HTML@capitaldieresis}[1]{\#1\HTMLunicode{0308}}
71 \newcommand*{\LWR@HTML@capitalhungarumlaut}[1]{\#1\HTMLunicode{30B}}
72 \newcommand*{\LWR@HTML@capitalring}[1]{\#1\HTMLunicode{30A}}
73 \newcommand*{\LWR@HTML@capitalcaron}[1]{\#1\HTMLunicode{30C}}
74 \newcommand*{\LWR@HTML@capitalbreve}[1]{\#1\HTMLunicode{306}}
75 \newcommand*{\LWR@HTML@capitalmacron}[1]{\#1\HTMLunicode{304}}
76 \newcommand*{\LWR@HTML@capitaldotaccent}[1]{\#1\HTMLunicode{307}}

```

\textcircled becomes a span with a rounded border:

```

77 \newcommand*{\LWR@HTML@textcircled}[1]{%
78 \InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{#1}%
79 }
80
81 \LWR@formatted{capitalcedilla}
82 \LWR@formatted{capitalogonek}

```

```

83 \LWR@formatted{capitalgrave}
84 \LWR@formatted{capitalacute}
85 \LWR@formatted{capitalcircumflex}
86 \LWR@formatted{capitaltilde}
87 \LWR@formatted{capitaldieresis}
88 \LWR@formatted{capitalhungarumlaut}
89 \LWR@formatted{capitalring}
90 \LWR@formatted{capitalcaron}
91 \LWR@formatted{capitalbreve}
92 \LWR@formatted{capitalmacron}
93 \LWR@formatted{capitaldotaccent}
94 \LWR@formatted{textcircled}
95
96 }% AtBeginDocument

```

File 290 **l warp-textfit.sty**

§ 383 Package **textfit**

Pkg **textfit** **textfit** is emulated.

Text is placed into a `` of class `textfit`. Sizes are approximated, and also limited by browser min/max font-size settings.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{textfit}

2 \newsavebox{\LWR@textfitbox}
3
4 \newcommand*{\LWR@textfitscale}[2]{%
5 \setlength{\LWR@templengthone}{#1}%
6 \setlength{\LWR@templengthone}{%
7     1em*\ratio{\LWR@templengthone}{\LWR@templengthtwo}%
8 }%
9 \InlineClass[font-size:\LWR@printlength{\LWR@templengthone}]{textfit}{#2}%
10 }

11 \newcommand*{\scaletowidth}[2]{%
12 \sbox{\LWR@textfitbox}{#2}%
13 \settowidth{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
14 \LWR@textfitscale{#1}{#2}%
15 \LWR@textfitscale{#1}{#2}%
16 }
17
18 \newcommand*{\scaletoheight}[2]{%
19 \sbox{\LWR@textfitbox}{#2}%
20 \settoheight{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
21 \LWR@textfitscale{#1}{#2}%
22 }

```

File 291 **l warp-textpos.sty**

§ 384 Package **textpos**

(Emulates or patches code by NORMAN GRAY.)

Pkg **textpos** **textpos** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{textpos}

```
2 \NewDocumentEnvironment{textblock}{m r(){}{}}
3 \NewDocumentEnvironment{textblock*}{m o r(){}{}}
4 \newcommand*\{\\TPGrid}[3][]{}
5 \NewDocumentCommand{\TPMargin}{s o}{}
6 \newcommand*\{\\textblockcolour}[1]{}
7 \newcommand*\{\\textblockrulecolour}[1]{}
8 \newcommand*\{\\textblockcolor}[1]{}
9 \newcommand*\{\\textblockrulecolor}[1]{}
10 \newcommand*\{\\tekstblokkulur}[1]{}
11 \newcommand*\{\\tekstblokrulekulur}[1]{}
12 \newlength{\TPHorizModule}
13 \newlength{\TPVertModule}
14 \newlength{\TPboxrulesize}
15 \newcommand{\textblocklabel}[1]{}
16 \newcommand*\{\\showtextsize}{}
17 \newcommand{\textblockorigin}[2]{}
```

File 292 **l warp-theorem.sty**

§ 385 Package **theorem**

(Emulates or patches code by FRANK MITTELBACH.)

Pkg **theorem** **theorem** is patched for use by **l warp**.

for HTML output: 1 \LWR@ProvidesPackagePass{theorem}

Table 15: Theorem package—CSS styling of theorems and proofs

Theorem: <div> of class theorembody<theoremstyle>

Theorem Header: of class theoremheader

where <theoremstyle> is plain, break, etc.

§ 385.1 Remembering the theorem style

Storage for the style being used for new theorems:

```
2 \newcommand{\LWR@newtheoremstyle}{plain}
```

Patched to remember the style being used for new theorems:

```
3 \gdef\theoremstyle#1{%
4   \@ifundefined{th@#1}{\@warning
5     {Unknown theoremstyle '#1'. Using 'plain'}%
6     \theorem@style{plain}%
7     \renewcommand{\LWR@newtheoremstyle}{plain}\l warp
8   }%
9   \%
10  \theorem@style{#1}%
11  \renewcommand{\LWR@newtheoremstyle}{#1}\l warp
12 }%
13 \begingroup
14   \csname th@\the\theorem@style \endcsname
15 \endgroup
```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```
16 \gdef\xnthy#1#2[#3]{%
17   \expandafter\@if definable\csname #1\endcsname
18   \%
19   \csedef{\LWR@thmstyle#1}{\LWR@newtheoremstyle}\l warp
20   \@definecounter{#1}\@newctr{#1}[#3]%
21   \expandafter\xdef\csname the#1\endcsname
22   {\expandafter\noexpand\csname the#3\endcsname
23    \@thmcOUNTERsep\@thmcOUNTER{#1}}%
24   \def\@tempa{\global\@namedef{#1}}%
25   \expandafter\@tempa\expandafter\%
26   \csname th@\the\theorem@style
27   \expandafter\endcsname\the\theorem@bodyfont
28   \@thm{#1}{#2}}%
29 \global\expandafter\let\csname end#1\endcsname\@endtheorem
```

```

30      \AtBeginEnvironment{\#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}\% l warp
31    }
32
33 \gdef\@ynthm#1#2{%
34   \expandafter\@if definable\csname #1\endcsname
35   {
36     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}\% l warp
37     \@definecounter{#1}%
38     \expandafter\xdef\csname the#1\endcsname{\@thmcounter{#1}}%
39     \def\@tempa{\global\@namedef{#1}}\expandafter \atempa
40     \expandafter\{\csname th@\the \theorem@style \expandafter
41     \endcsname \the\theorem@bodyfont \@thm{#1}{#2}}%
42     \global \expandafter \let \csname end#1\endcsname \endtheorem
43     \AtBeginEnvironment{\#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}\% l warp
44   }%
45
46 \gdef\@othm#1[#2]#3{%
47   \expandafter\ifx\csname c@#2\endcsname\relax
48   \@nocounterr{#2}%
49   \else
50   \expandafter\@if definable\csname #1\endcsname
51   {
52     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}\% l warp
53     \expandafter \xdef \csname the#1\endcsname
54     {\expandafter \noexpand \csname the#2\endcsname}%
55     \def\@tempa{\global\@namedef{#1}}\expandafter \atempa
56     \expandafter\{\csname th@\the \theorem@style \expandafter
57     \endcsname \the\theorem@bodyfont \@thm{#2}{#3}}%
58     \global \expandafter \let \csname end#1\endcsname \endtheorem
59     \AtBeginEnvironment{\#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}\% l warp
60   }%
61 \fi}

```

§ 385.2 CSS patches

The following are patched for css.

These were in individual files thp.sty for plain, thmb.sty for margin break, etc. They are gathered together here.

Each theorem is encased in a `BlockClass` environment of class `theorembody<style>`.

Each header is encased in an `\InlineClass` of class `theoremheader`.

```

62 \gdef\th@plain{%
63   \def\@begintheorem##1##2{%
64     \item[
65       \InlineClass{theoremheader}{##1\ ##2}
66     ]

```

```
67      }%
68 \def\@opargbegintheorem##1##2##3{%
69   \item[
70     \InlineClass{theoremheader}{##1\ ##2\ (##3)}%
71   ]%
72 }
73 }%
74
75 \gdef\th@break{%
76   \def\@begintheorem##1##2{%
77     \item[
78       \InlineClass{theoremheader}{##1\ ##2}\newline%
79     ]%
80   }%
81 \def\@opargbegintheorem##1##2##3{%
82   \item[
83     \InlineClass{theoremheader}{##1\ ##2\ (##3)}\newline%
84   ]%
85 }
86 }
87
88 \gdef\th@marginbreak{%
89   \def\@begintheorem##1##2{%
90     \item[
91       \InlineClass{theoremheader}{##2 \qquad ##1}\newline%
92     ]%
93   }%
94 \def\@opargbegintheorem##1##2##3{%
95   \item[
96     \InlineClass{theoremheader}{##2 \qquad ##1\ %
97     (##3)}\newline%
98   ]%
99 }
100 }
101
102 \gdef\th@changebreak{%
103   \def\@begintheorem##1##2{%
104     \item[
105       \InlineClass{theoremheader}{##2\ ##1}\newline%
106     ]%
107   }%
108 \def\@opargbegintheorem##1##2##3{%
109   \item[
110     \InlineClass{theoremheader}{ ##2\ ##1\ %
111     (##3)}\newline%
112   ]%
113 }
114 }
115
116 \gdef\th@change{%
```

```

117 \def\@begintheorem##1##2{
118   \item[
119     \InlineClass{theoremheader}{##2\ ##1}
120   ]
121 }
122 \def\@opargbegintheorem##1##2##3{%
123   \item[
124     \InlineClass{theoremheader}{##2\ ##1\ (###3)}
125   ]
126 }
127 }
128
129 \gdef\th@margin{%
130   \def\@begintheorem##1##2{
131     \item[
132       \InlineClass{theoremheader}{##2 \qquad ##1}
133     ]
134   }
135 \def\@opargbegintheorem##1##2##3{%
136   \item[
137     \InlineClass{theoremheader}{##2 \qquad ##1\ (###3)}
138   ]
139 }
140 }

```

Patched for css:

```

141 \gdef\@thm#1#2{\refstepcounter{#1}%
142 \LWR@forcenewpage% lwarf
143   \BlockClass{theorembody}\LWR@thisthmstyle}% lwarf
144   \trivlist
145   \topsep \theorempreskipamount % used by first \item
146   \topsepadd \theorempostskipamount % used by \endparenv
147   \ifnextchar [%]
148   {\@ythm{#1}{#2}}%
149   {\@begintheorem{#2}{\csname the#1\endcsname}\ignorespaces}}
150
151 \gdef\@endtheorem{%
152 \endtrivlist
153 \endBlockClass
154 }

```

File 293 **lwarf-thinsp.sty**

§ 386 Package **thinsp**

Pkg **thinsp** **thinsp** is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{thinspace}

2 \AtBeginDocument{
3 \let\thinspace\relax% defined by some packages
4 \newcommand*{\thinspace}{\thinspace}
5 }
6
7 \newcommand*{\stretchthinspace}{\thinspace}
8 \newcommand*{\stretchthinthinspace}{\thinspace}
9 \newcommand*{\stretchnegthinspace}{\negthinspace}
```

File 294 **l warp-threadcol.sty**

§ 387 Package **threadcol**

Pkg **threadcol** **threadcol** is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{threadcol}

2 \newcommand{\setthreadname}[1]{}
```

File 295 **l warp-threeparttable.sty**

§ 388 Package **threeparttable**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg **threeparttable** **threeparttable** is emulated.

Table note are contained inside a css <div> of class tnotes. If **enumitem** is used, the note item labels are also individually highlighted with an additional css of class tnoteitemheader, otherwise they are plain text.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{threeparttable}

\LWR@printtablenote {\textit{text}}
Prints the table note item header inside a css class of tnoteitemheader.

2 \newcommand{\LWR@printtablenote}[1]{\InlineClass{tnoteitemheader}{#1}}
```

Env **threeparttable** [*alignment*] To emulate threeparttable:

```

3 \newenvironment*{threeparttable}[1][b]{}{}
```

```

Env  tablenotes  [<options>]
      4 \newenvironment*{tablenotes}[1] []
      5 {%
      6 \LWR@forcenewpage
      7 \BlockClass{tnotes}%
      8 \ltx@ifpackageloaded{enumitem}{%
      9 \setlist[description]{format=\LWR@printtablenote}%
     10 }{}}%
     11 \description%
     12 }
     13 {%
     14 \enddescription%
     15 \endBlockClass%
     16 }

\tnote  {<text>}
     17 \newcommand{\tnote}[1]{\LWR@htmlspan{sup}{#1}}

```

File 296 **l warp-thumb.sty**

§ 389 Package **thumb**

Pkg **thumb** **thumb** is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{thumb}

2 \newcommand*{\Overviewpage}{}
3 \newlength{\thumbheight}
4 \newlength{\thumbwidth}

```

File 297 **l warp-thumbs.sty**

§ 390 Package **thumbs**

Pkg **thumbs** **thumbs** is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{thumbs}

2 \newcommand{\addthumb}[4]{}
3 \newcommand{\addtitlethumb}[5]{}

```

```

4 \newcommand{\stophumb}{}
5 \newcommand{\continuethumb}{}
6 \newcommand{\thumbsoverview}[1]{}
7 \newcommand{\thumbsoverviewback}[1]{}
8 \newcommand{\thumbsoverviewverso}[1]{}
9 \newcommand{\thumbsoverviewdouble}[1]{}
10 \newcommand{\thumbnewcolumn}{}
11 \newcommand{\addthumbsoverviewtocontents}[2]{}
12 \newcommand{\thumbsnophantom}{}

```

File 298 **l warp-tikz.sty**

§ 391 Package **tikz**

(Emulates or patches code by TILL TANTAU.)

Pkg **tikz** **tikz** is supported.

⚠️ displaymath and matrices If using display math with `\tikzpicture` or `\tikz`, along with matrices with the & character, the document must be modified as follows:

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of & in the `tikz` expression must be replaced with \&.

Accept all options for **l warp-tikz**:

```
1 \LWR@ProvidesPackagePass{tikz}[2015/08/07]
```

catcodes **l warp** changes the catcode of \$ for its own use. The Tikz babel library temporarily changes catcodes back to normal for Tikz's use. `tikz` v3.0.0 introduced the `babel` library which handles catcode changes. For older versions, **l warp** must change \$'s catcode itself.

Also see:

<https://tex.stackexchange.com/questions/16199/test-if-a-package-or-package-option-is-loaded>

```

2 \newbool{LWR@tikzbabel}
3
4 @ifpackagelater{tikz}{2013/12/20}%
5 {\usetikzlibrary{babel}\booltrue{LWR@tikzbabel}}
6 {\boolfalse{LWR@tikzbabel}}
```

- Env **pgfpicture** The `\pgfpicture` environment is enclosed inside a `\lateximage`. Enclose the low-level `\pgfpicture` in a `\lateximage`. This is also used by the higher-level `\tikz` and `tikzpicture`.

```

7 \preto\pgfpicture{%
8   \begin{lateximage}%
9   \ifbool{LWR@tikzbabel}{% Test for Tikz version v3.0.0
10   {}%
11   {\catcode`\$=3}% dollar sign is math shift
12 }%
13
14 \appto\endpgfpicture{\end{lateximage}}

```

Tikz is placed inside an SVG image, so use the original meanings of the following:

```

15 \LetLtxMacro\pgfutil@minipage\LWR@print@minipage
16 \let\pgfutil@endminipage\endLWR@print@minipage
17
18 \let\pgfutil@raggedleft\LWR@print@raggedleft
19 \let\pgfutil@raggedright\LWR@print@raggedright
20
21 \def\pgfutil@font@tiny{\LWR@printtiny}
22 \def\pgfutil@font@scriptsize{\LWR@printsizescriptsize}
23 \def\pgfutil@font@footnotesize{\LWR@printfootnotesize}
24 \def\pgfutil@font@small{\LWR@print@small}
25 \def\pgfutil@font@normalsize{\LWR@print@normalsize}
26 \def\pgfutil@font@large{\LWR@printlarge}
27 \def\pgfutil@font@Large{\LWR@printLarge}
28 \def\pgfutil@font@huge{\LWR@printhuge}
29 \def\pgfutil@font@Huge{\LWR@printHuge}
30
31 \def\pgfutil@font@itshape{\LWR@origitshape}
32 \def\pgfutil@font@bfseries{\LWR@origbfseries}
33
34 \def\pgfutil@font@normalfont{\LWR@orignormalfont}

```

File 299 **l warp-titleps.sty**

§ 392 Package **titleps**

(Emulates or patches code by JAVIER BEZOS.)

- Pkg **titleps** **titleps** is loaded and used by **l warp** during HTML output. All user options and macros are ignored and disabled.

Discard all options for **l warp-titleps**:

for HTML output:

1 \LWR@ProvidesPackageDrop{titleps}

\pagestyle and \thispagestyle are already disabled in the **lwrap** code.

\newpagestyle {*name*} [{*style*}]{*commands*}

2 \NewDocumentCommand{\newpagestyle}{m o m}{}{}

\renewpagestyle {*name*} [{*style*}]{*commands*}

3 \NewDocumentCommand{\renewpagestyle}{m o m}{}{}

\sethead [{*el*}][{*ec*}][{*er*}]{*ol*}{*oc*}{*or*}

4 \NewDocumentCommand{\sethead}{o o m m}{}{}

\setfoot [{*el*}][{*ec*}][{*er*}]{*ol*}{*oc*}{*or*}

5 \NewDocumentCommand{\setfoot}{o o m m}{}{}

\settlemarks * {*names*}

6 \NewDocumentCommand{\settlemarks}{s m}{}{}

\headrule

7 \newcommand*{\headrule}{}{}

\footrule

8 \newcommand*{\footrule}{}{}

\setheadrule {*length*}

9 \newcommand*{\setheadrule}[1]{}{}

\setfootrule {*length*}

10 \newcommand*{\setfootrule}[1]{}{}

\makeheadrule

11 \newcommand*{\makeheadrule}{}{}

\makefootrule

12 \newcommand*{\makefootrule}{}{}

```
\setmarkboth {⟨code⟩}
13 \newcommand{\setmarkboth}[1]{}

\widenhead
14 \NewDocumentCommand{\widenhead}{s o o m m}{}

\bottitlemarks
15 \newcommand*{\bottitlemarks}{{}

\tottitlemarks
16 \newcommand*{\tottitlemarks}{{}

\firstitmarks
17 \newcommand*{\firstitmarks}{{}

\nexttitlemarks
18 \newcommand*{\nexttottitlemarks}{{}

\outertitlemarks
19 \newcommand*{\outertitlemarks}{{}

\innertitlemarks
20 \newcommand*{\innertitlemarks}{{}

\newtitlemark * {⟨name⟩}
21 \NewDocumentCommand{\newtitlemark}{s m}{}

\pretitlemark * {⟨section⟩} {⟨text⟩}
22 \NewDocumentCommand{\pretitlemark}{s m m}{}

\ifsamemark {⟨group⟩} {⟨command⟩} {⟨true⟩} {⟨false⟩}
23 \newcommand{\ifsamemark}[4]{{}

\setfloathead * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨extra⟩} [⟨which⟩]
```

```
24 \NewDocumentCommand{\setfloathead}{s o o o m m m m m}{}

\setfloatfoot * [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨extra⟩} [⟨which⟩]
25 \NewDocumentCommand{\setfloatfoot}{s o o o m m m m m}{}

\nextfloathead * [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨extra⟩} [⟨which⟩]
26 \NewDocumentCommand{\nextfloathead}{s o o o m m m m m}{}

\nextfloatfoot * [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨extra⟩} [⟨which⟩]
27 \NewDocumentCommand{\nextfloatfoot}{s o o o m m m m m}{}

\newmarkset {⟨markset⟩}
28 \newcommand{\newmarkset}[1]{}

\newextramark * {⟨markset⟩} {⟨macro-name⟩}
29 \NewDocumentCommand{\newextramarkset}{s m m}{}

\botextramarks {⟨markset⟩}
30 \newcommand{\botextramarks}[1]{}

\topextramarks {⟨markset⟩}
31 \newcommand{\topextramarks}[1]{}

\firstextramarks {⟨markset⟩}
32 \newcommand{\firstextramarks}[1]{}

\nextextramarks {⟨markset⟩}
33 \newcommand{\nexttopextramarks}[1]{}

\outerextramarks {⟨markset⟩}
34 \newcommand{\outerextramarks}[1]{}

\innerextramarks {⟨markset⟩}
35 \newcommand{\innerextramarks}[1]{}
```

File 300 **l warp-titleref.sty**

§ 393 Package **titleref**

Pkg **titleref** **titleref** is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{titleref}
2
3 \LetLtxMacro\titleref\nameref
4
5 \providecounter{LWR@currenttitle}
6
7 \newcommand*{\currenttitle}{%
8     \addtocounter{LWR@currenttitle}{1}%
9     \label{currenttitle\arabic{LWR@currenttitle}}%
10    \nameref{currenttitle\arabic{LWR@currenttitle}}%
11 }
12
13 \newcommand*{\theTitleReference}[2]{}
```

File 301 **l warp-titlesec.sty**

§ 394 Package **titlesec**

(Emulates or patches code by JAVIER BEZOS.)

Pkg **titlesec** **titlesec** is emulated. All user options and macros are ignored and disabled.

Discard all options for **l warp-titlesec**:

for HTML output:

```
1 \LWR@ProvidesPackageDrop{titlesec}

\titelabel {\langle label-format\rangle}
2 \newcommand*{\titlabel}[1]{}

\titleformat* {\langle command\rangle} {\langle format\rangle}

\titleformat {\langle command\rangle} [{\langle shape\rangle}] {\langle format\rangle} {\langle label\rangle} {\langle sep\rangle} {\langle begfore\rangle} [{\langle after\rangle}]
3 \newcommand\titleformat{%
4     \@ifstar{\ttl@format@s}{%
```

```
5           {\ttl@format@i}}
6 \newcommand{\ttl@format@s}[1]{}
7 \NewDocumentCommand{\ttl@format@i}{m o m m m m o}{}  
  
\chaptertitlename
8 \@ifundefined{@chapapp}{\let\@chapapp\chaptername}{}
9 \newcommand\chaptertitlename{\@chapapp}  
  
\titlespacing * {[<command>] {<left>} {<before>} {<after>} [<right>]}
10 \NewDocumentCommand{\titlespacing}{s m m m m o}{}  
  
\filright
11 \newcommand*\filright{}  
  
\filcenter
12 \newcommand*\filcenter{}  
  
\filleft
13 \newcommand*\filleft{}  
  
\fillast
14 \newcommand*\fillast{}  
  
\filinner
15 \newcommand*\filinner{}  
  
\filouter
16 \newcommand*\filouter{}  
  
\wordsep
17 \newcommand\wordsep{\fontdimen\tw@\font \oplus
18   \fontdimen\thr@@\font \ominus \fontdimen4\font}  
  
\titleline * {[<align>] {<material>}}
19 \NewDocumentCommand{\titleline}{s o m}{}  

```

```

\titlerule  [{<height>}]

20 \providecommand*\titlerule{\@ifstar{\ttl@row}{\ttl@rule}}
21 \newcommand*\ttl@rule[1][]{}
22 \newcommand*\ttl@row[2][]{}

\iftitlemeasuring  {{<true>}} {{<false>}}
23 \newcommand{\iftitlemeasuring}[2]{#2}

\assignpagestyle  {{<command>}} {{<pagestyle>}}
24 \newcommand{\assignpagestyle}[2]{#2}

\titleclass  {{<name>}} [{<startlevel>}]{<class>} [{<cmd>}]
25 \NewDocumentCommand{\titleclass}{m o m o}

```

File 302 l warp-toc.sty

§ 395 Package **titletoc**

(Emulates or patches code by JAVIER BEZOS.)

Pkg titletoc **titletoc** is emulated. All user options and macros are ignored and disabled.

Discard all options for **l warp-titletoc**:

```

for HTML output: 1 \LWR@ProvidesPackageDrop{titletoc}

\dottedcontents  {{<section>}} [{<left>}]{<above>}{{<label>}} {{<leader>}}
2 \NewDocumentCommand{\dottedcontents}{m o m m m}{{}{}{}{}}

\titlecontents  * {{<section>}} [{<left>}]{<above>}{{<numbered>}} {{<numberless>}} {{<filler>}} [{<below>} or begin] [{<separator>}] [{<end>}]
3 \newcommand{\titlecontents}{\@ifstar{\ttl@tcstar}{\ttl@tcnostar}}
4 \NewDocumentCommand{\ttl@tcstar}{m o m m m m o o o}{{}{}{}{}{}{}{}{}}
5 \NewDocumentCommand{\ttl@tcnostar}{m o m m m m o}{{}{}{}{}{}{}{}{}}

\contentsmargin  [{<correction>}] {{<right>}}
6 \newcommand{\contentsmargin}[2][]{}

\thecontentslabel

```

```
7 \newcommand*{\thecontentslabel}{\thecontentslabel}\thecontentspage
8 \newcommand*{\thecontentspage}{\thecontentspage}\contentslabel [⟨format⟩] {⟨space⟩}
9 \newcommand{\contentslabel}[2][]{\thecontentslabel}\contentspage [⟨format⟩]
10 \newcommand{\contentspage}[1][]{\thecontentspage}\contentspush {⟨text⟩}
11 \newcommand{\contentspush}[1]{}
\contentsuse {⟨name⟩} {⟨text⟩}
12 \newcommand{\contentsuse}[2]{}
\startcontents [⟨name⟩]
13 \newcommand*{\startcontents}[1][]{}
\stopcontents [⟨name⟩]
14 \newcommand*{\stopcontents}[1][]{}
\resumecontents [⟨name⟩]
15 \newcommand*{\resumecontents}[1][]{}
\printcontents [⟨name⟩] {⟨prefix⟩} {⟨start⟩} {⟨code⟩}
16 \newcommand{\printcontents}[4][]{}
\startlist [⟨name⟩] {⟨list⟩}
17 \newcommand{\startlist}[2][]{}
\stoplist [⟨name⟩] {⟨list⟩}
18 \newcommand{\stoplist}[2][]{}
```

```
\resumelist  [⟨name⟩] {⟨list⟩}
19 \newcommand{\resumelist}[2][]{}

\printlist   [⟨name⟩] {⟨list⟩} {⟨prefix⟩} {⟨code⟩}
20 \newcommand{\printlist}[4][]{}
```

File 303 **lwarf-titling.sty**

§ 396 Package **titling**

(Emulates or patches code by PETER WILSON.)

Pkg **titling**

package support **lwarf** supports the native L^AT_EX titling commands, and also supports the packages **authblk** and **titling**. If both are used, **authblk** should be loaded before **titling**.

⚠ load order If using the **titling** package, additional titlepage fields for **\published** and **\subtitle** may be added by using **\AddSubtitlePublished** in the preamble. See section 63.8.

The various **titling** footnote restyling commands have no effect.

Pass all options to **lwarf-titling**:

for HTML output: 1 \LWR@ProvidesPackagePass{titling}

\@bsmtitleempty Patch **\@bsmtitleempty**:

```
2 \let\LWR@orig@\@bsmtitleempty\@bsmtitleempty
3 \renewcommand*{\@bsmtitleempty}{%
4 \LWR@orig@\@bsmtitleempty%
5 }
```

\keepthetitle Patch **\keepthetitle**:

```
6 \let\LWR@orig\keepthetitle\keepthetitle
7 \renewcommand*{\keepthetitle}{%
8 \LWR@orig@\keepthetitle%
9 }
```

\killtitle Patch **\killtitle**:

```
10 \let\LWR@orig\killtitle\killtitle
11 \renewcommand*{\killtitle}{%
12 \LWR@orig@\killtitle%
```

13 }

Env `titlingpage`

```
14 \renewenvironment*{titlingpage}{%
15 {%
```

Start an HTML titlepage div:

```
16 \LWR@printpendingfootnotes
17 \begin{titlepage}
```

Prepare for a custom version of `\maketitle` inside the `titlingpage`:

```
18 \LWR@maketitlesetup
19 \let\maketitle\LWR@titlingmaketitle
20 }
21 {
```

At the end of the environment, end the HTML titlepage div:

```
22 \end{titlepage}
23 }
```

Patch the pre/post title/author/date to add HTML tags, then initialize:

```
24
25 \pretitle{}
26 \posttitle{}
27
28 \preauthor{}
29 \postauthor{}
30
31 \predate{}
32 \postdate{}
```

`\LWR@maketitlesetup` Patches `\thanks` macros.

```
33 \renewcommand*{\LWR@maketitlesetup}{%
```

Redefine the footnote mark:

```
34 \def\@makefnmark{\textsuperscript{\@thefnmark}}
```

```
\thefootnote \Rightarrow \nameuse{arabic}{footnote}, or
\thefootnote \Rightarrow \nameuse{fnsymbol}{footnote}
```

Redefine the footnote text:

```
35 \long\def\@makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```
36 \makethanksmark~%
```

```
\makethanksmark \thanksfootmark \tamarck \thefnmark \itshape a (or similar)
```

Print the text:

```
37 ##1%
38 }% \@makefntext
39 }
```

```
\thanksfootmark
```

```
40 \renewcommand{\thanksfootmark}{%
41 % \hb@xt@\thanksmarkwidth{\hfil\normalfont%
42 % \thanksscript{%
43 % \thanksfootpre \tamarck \thanksfootpost%
44 % }%
45 % }%
46 }
```

`\maketitle` HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the **titling** package is adapted, simplified, and modified for HTML output.

```
47 \renewcommand*{\maketitle}{%
```

An HTML titlepage <div> is used for all classes.

```
48 \begin{titlepage}
```

Select which kind of footnote marks to use:

```
49 \@bsmarkseries
```

Set up special patches:

```
50 \LWR@maketitlesetup
```

Typeset the title, etc:

```
51 \@maketitle
```

Immediately generate any \thanks footnotes:

```
52 \@thanks
```

Close the HTML titlepage div:

```
53 \end{titlepage}
```

Reset the footnote counter:

```
54 \@bscontmark
55 }
```

`\@maketitle` Typesets the title, etc. Patched for HTML.

```
56 \DeclareDocumentCommand{\@maketitle}{}
57   {
58     \maketitlehooka
59     {
60       \LWR@stoppars\LWR@htmltag{\LWR@tagtitle}
61       \@bspretitle \@title \@bspstitle
62       \LWR@htmltag{\LWR@tagtitleend}\LWR@startpars
63     }
64     \maketitlehookb
65     {
66       \begin{BlockClass}{author}
67       \renewcommand{\and}{%
68         \end{BlockClass}
69         \begin{BlockClass}{oneauthor}
70       }
71       \begin{BlockClass}{oneauthor}
72       \@bspreauthor \@author \@bspstauthor
73       \end{BlockClass}
74     }
75     \maketitlehookc
76     {
77       \begin{BlockClass}{titledate}
78       \@bspredate \@date \@bspstdate
79       \end{BlockClass}
80     }
81     \maketitlehookd
82 }
```

```
\LWR@titlingmaketitle \maketitle for use inside an HTML titlingpage environment.
```

```
83 \renewcommand*\{\LWR@titlingmaketitle}{%
```

Keep pending footnotes out of the title block:

```
84 \c@thanks
```

Select which kind of footnote marks to use:

```
85 \c@bsmarkseries
```

Set up special patches:

```
86 \LWR@maketitlesetup
```

Typeset the title, etc:

```
87 \c@maketitle
```

Immediately generate any \thanks footnotes:

```
88 \c@thanks
```

Reset the footnote counter:

```
89 \c@bscontmark  
90 }
```

```
\thanksmarkseries {\langle series\rangle}
```

Sets the type of footnote marks used by \thanks, where type is ‘arabic’, ‘roman’, ‘fnsymbol’, etc.

```
91 \renewcommand{\thanksmarkseries}[1]{%  
92 \def\c@bsmarkseries{\renewcommand{\thefootnote}{\c@nameuse{\#1}{footnote}}}}%  
93 }
```

Set default titlepage thanks footnote marks. See section 63.7.

```
94 \c@ifclassloaded{memoir}{  
95   \thanksmarkseries{arabic}  
96 }{  
97 \c@if@titlepage  
98   \thanksmarkseries{arabic}  
99 \celse
```

```
100 \thanksmarkseries{fnsymbol}
101 \fi
102 }% not memoir
```

File 304 **l warp-tocbasic.sty**

§ 397 Package **tocbasic**

(Emulates or patches code by MARKUS KOHM.)

Pkg **tocbasic** **tocbasic** is patched for use by **l warp**.

This package may be loaded standalone, but is also loaded automatically if **koma-script** classes are in use. **\DeclareDocumentCommand** is used to overwrite the **koma-script** definitions.

for HTML output: 1 \LWR@ProvidesPackagePass{tocbasic}

```
2 \DeclareDocumentCommand{\usetocbasicnumberline}{o}={}
3 \DeclareDocumentCommand{\DeclareTOCStyleEntry}{o m m}={}
4 \DeclareDocumentCommand{\DeclareTOCEntryStyle}{m o m}={}
5 \DeclareDocumentCommand{\DefineTOCEntryOption}{m o m}={}
6 \DeclareDocumentCommand{\DefineTOCEntryBooleanOption}{m o m m m}={}
7 \DeclareDocumentCommand{\DefineTOCEntryCommandOption}{m o m m m}={}
8 \DeclareDocumentCommand{\DefineTOCEntryIfOption}{m o m m m}={}
9 \DeclareDocumentCommand{\DefineTOCEntryLengthOption}{m o m m m m}={}
10 \DeclareDocumentCommand{\DefineTOCEntryNumberOption}{m o m m m m}={}
11 \DeclareDocumentCommand{\CloneTOCEntryStyle}{m m}={}
12 \DeclareDocumentCommand{\TOCEntryStyleInitCode}{m m}={}
13 \DeclareDocumentCommand{\TOCEntryStyleStartInitCode}{m m}={}
```

File 305 **l warp-tocbibind.sty**

§ 398 Package **tocbibind**

(Emulates or patches code by PETER WILSON.)

Pkg **tocbibind** **tocbibind** is patched for use by **l warp**.

placement and toc options An index may be placed inline with other HTML text, or on its own HTML page:

Pkg **makeidx** **Inline, with a manual TOC entry:**

A commonly-used method to introduce an index in a L^AT_EX document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname} or chapter
\printindex
```

Pkg **makeidx** **On its own HTML page, with a manual TOC entry:**

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname} or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex
```

Pkg **tocbibind** **Inline, with an automatic TOC entry:**

The **tocbibind** package may be used to automatically place an entry in the TOC.

```
\usepackage[nottoc]{tocbibind}
...
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex
```

Pkg **tocbibind** **On its own HTML page, with an automatic TOC entry:**

```
\usepackage[nottoc]{tocbibind}
...
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex
```

Opt tocbibind numindex Use the **tocbibind numindex** option to generate a numbered index. Without this option, the index heading has no number.

Other packages, such as **imakeidx**, may also have options for including the index in the Table of Contents.

for HTML output:

```

1 \let\simplechapterdelim\relax
2
3 \LWR@ProvidesPackagePass{tocbibind}

4 \renewenvironment{theindex}%
5 {%
6     \if@bibchapter
7         \if@donumindex
8             \chapter{\indexname}
```

```

9      \else
10     \if@dotocind
11       \chapter*{\indexname}
12       \addcontentsline{toc}{chapter}{\indexname}
13     \else
14       \chapter*{\indexname}
15     \fi
16   \fi
17 \else
18   \if@donumindex
19     \section{\indexname}
20   \else
21     \if@dotocind
22       \section*{\indexname}
23       \addcontentsline{toc}{\@tocextra}{\indexname}
24     \else
25       \section*{\indexname}
26     \fi
27   \fi
28 \fi
29 \let\item\LWR@indexitem%
30 \let\subitem\LWR@indexsubitem%
31 \let\subsubitem\LWR@indexsubsubitem%
32 }{}}

```

The following code is shared by **anonchap**.

```

33 \DeclareDocumentCommand{\simplechapter}{O{\@empty}}{%
34   \def\@chapcntformat##1{%
35     #1\csname the##1\endcsname\simplechapterdelim\protect\quad%
36   }%
37 }
38
39 \DeclareDocumentCommand{\restorechapter}{}{%
40 \let\@chapcntformat\@secntformat%
41 }

```

File 306 **lwarf-tocenter.sty**

§ 399 Package **tocenter**

Pkg **tocenter** **tocenter** is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{tocenter}

2 \NewDocumentCommand{\ToCenter}{s o m m}{}

```

```
3 \NewDocumentCommand{\FromMargins}{s o m m m m}{}{}
```

File 307 **l warp-tocloft.sty**

§ 400 Package **tocloft**

(Emulates or patches code by PETER WILSON.)

Pkg **tocloft** **tocloft** is emulated. Most user options and macros are ignored and disabled. `\newlistof` and `\cftchapterprecis` are supported.

Pkg **tocloft** If using **tocloft** with **tocbibind**, **anonchap**, **fncychap**, or other packages which change chapter title formatting, load **tocloft** with its `titles` option, which tells **tocloft** to use standard L^AT_EX commands to create the titles, allowing other packages to work with it.

Discard all options for **l warp-tocloft**:

for HTML output:

```
1 \LWR@ProvidesPackageDrop{tocloft}

\tocloftpagestyle {\langle style\rangle}
2 \newcommand{\tocloftpagestyle}[1]{}

\cftmarktoc
3 \newcommand*{\cftmarktoc}{}{}
```

\cfttoctitlefont
4 \newcommand*{\cfttoctitlefont}{}{}

\cftaftertoctitle
5 \newcommand*{\cftaftertoctitle}{}{}

6 \newlength{\cftbeforetoctitleskip}
7 \newlength{\cftaftertoctitleskip}

\cftmarklof
8 \newcommand*{\cftmarklof}{}{}

\cftloftitlefont



tocloft & other packages

```
9 \newcommand*{\cftloftitlefont}{}  
  
\cftafterloftitle  
10 \newcommand*{\cftafterloftitle}{}  
  
11 \newlength{\cftbeforeloftitleskip}  
12 \newlength{\cftafterloftitleskip}  
  
\cftmarklot  
13 \newcommand*{\cftmarklot}{}  
  
\cftlottitlefont  
14 \newcommand*{\cftlottitlefont}{}  
  
\cftafterlottitle  
15 \newcommand*{\cftafterlottitle}{}  
  
16 \newlength{\cftbeforelottitleskip}  
17 \newlength{\cftafterlottitleskip}  
  
\cftdot  
18 \providecommand*{\cftdot}{.}  
  
\cftdotsep  
19 \providecommand*{\cftdotsep}{1}  
  
\cftnodots  
20 \providecommand*{\cftnodots}{5000}  
  
\cftdotfill {<sep>}  
21 \providecommand{\cftdotfill}[1]{}  
  
\cftsetpnumwidth {<length>}  
22 \DeclareDocumentCommand{\cftsetpnumwidth}{m}{}  
  
\cftsetrmarg {<length>}
```

```

23 \DeclareDocumentCommand{\cftsetrmarg}{m}{}{}

\cftpnumalign {⟨alignment⟩}
24 \DeclareDocumentCommand{\cftpnumalign}{m}{}{}

25 \LWR@providelength{\cftparskip}

```

The part-related items are also provided by **memoir**:

```

26 \LWR@providelength{\cftbeforeparts skip}
27 \LWR@providelength{\cftpartindent}
28 \LWR@providelength{\cftpartnumwidth}
29 \providecommand*\cftpartfont{}{}
30 \providecommand*\cftpartpresnum{}{}
31 \providecommand*\cftpartaftersnum{}{}
32 \providecommand*\cftpartaftersnumb{}{}
33 \providecommand*\cftpartleader{}{}
34 \providecommand*\cftpartdotsep{1}
35 \providecommand*\cftpartpagefont{}{}
36 \providecommand*\cftpartafterpnum{}{}

```

memoir uses the full name “chapter” instead of “chap”:

```

37 \LWR@providelength{\cftbeforechapskip}
38 \LWR@providelength{\cftchapindent}
39 \LWR@providelength{\cftchapnumwidth}
40 \newcommand*\cftchapfont{}{}
41 \newcommand*\cftchappresnum{}{}
42 \newcommand*\cftchapaaftersnum{}{}
43 \newcommand*\cftchapaaftersnumb{}{}
44 \newcommand*\cftchapleader{}{}
45 \newcommand*\cftchapdotsep{1}
46 \newcommand*\cftchappagefont{}{}
47 \newcommand*\cftchapafterpnum{}{}

```

The following do not appear in **memoir**:

```

48 \LWR@providelength{\cftbeforesecskip}
49 \LWR@providelength{\cftsecindent}
50 \LWR@providelength{\cftsecnumwidth}
51 \newcommand*\cftsecfont{}{}
52 \newcommand*\cftsecpresnum{}{}
53 \newcommand*\cftsecaftersnum{}{}
54 \newcommand*\cftsecaftersnumb{}{}
55 \newcommand*\cftsecleader{}{}
56 \newcommand*\cftsecdotsep{1}
57 \newcommand*\cftsecpagefont{}{}
58 \newcommand*\cftsecafterpnum{}{}

```

```
59 \LWR@providelength{\cftbeforesubsecskip}
60 \LWR@providelength{\cftsubsecindent}
61 \LWR@providelength{\cftsubsecnumwidth}
62 \newcommand*{\cftsubsecfont}={}
63 \newcommand*{\cftsubsecpresnum}={}
64 \newcommand*{\cftsubsecaftersnum}={}
65 \newcommand*{\cftsubsecaftersnumb}={}
66 \newcommand*{\cftsubsecleader}={}
67 \newcommand*{\cftsubsecdotsep}{1}
68 \newcommand*{\cftsubsecpagefont}={}
69 \newcommand*{\cftsubsecafterpnum}={}

70 \LWR@providelength{\cftbeforesubsubsecskip}
71 \LWR@providelength{\cftsubsubsecindent}
72 \LWR@providelength{\cftsubsubsecnumwidth}
73 \newcommand*{\cftsubsubsecfont}={}
74 \newcommand*{\cftsubsubsecpresnum}={}
75 \newcommand*{\cftsubsubsecaftersnum}={}
76 \newcommand*{\cftsubsubsecaftersnumb}={}
77 \newcommand*{\cftsubsubsecleader}={}
78 \newcommand*{\cftsubsubsecdotsep}{1}
79 \newcommand*{\cftsubsubsecpagefont}={}
80 \newcommand*{\cftsubsubsecafterpnum}={}

81 \LWR@providelength{\cftbeforeparaskip}
82 \LWR@providelength{\cftpaindent}
83 \LWR@providelength{\cftpnumwidth}
84 \newcommand*{\cftpafont}={}
85 \newcommand*{\cftpapresnum}={}
86 \newcommand*{\cftpaaftersnum}={}
87 \newcommand*{\cftpaaftersnumb}={}
88 \newcommand*{\cftpalaader}={}
89 \newcommand*{\cftpadotsep}{1}
90 \newcommand*{\cftpapagefont}={}
91 \newcommand*{\cftpaafterpnum}={}

92 \LWR@providelength{\cftbeforesubparaskip}
93 \LWR@providelength{\cftsubparaindent}
94 \LWR@providelength{\cftsubparanumwidth}
95 \newcommand*{\cftsubparafont}={}
96 \newcommand*{\cftsubparapresnum}={}
97 \newcommand*{\cftsubparaafersnum}={}
98 \newcommand*{\cftsubparaafersnumb}={}
99 \newcommand*{\cftsubparalaader}={}
100 \newcommand*{\cftsubparadotsep}{1}
101 \newcommand*{\cftsubparapagefont}={}
102 \newcommand*{\cftsubparaafterpnum}={}

103 \LWR@providelength{\cftbeforefigskip}
```

```
104 \LWR@providelength{\cftfigindent}
105 \LWR@providelength{\cftfignumwidth}
106 \newcommand*{\cftfigfont}={}
107 \newcommand*{\cftfigpresnum}={}
108 \newcommand*{\cftfigaftersnum}={}
109 \newcommand*{\cftfigaftersnumb}={}
110 \newcommand*{\cftfigleader}={}
111 \newcommand*{\cftfigdotsep}{1}
112 \newcommand*{\cftfigpagefont}={}
113 \newcommand*{\cftfigafterpnum}={}

114 \LWR@providelength{\cftbeforesubfigskip}
115 \LWR@providelength{\cftsubfigindent}
116 \LWR@providelength{\cftsubfignumwidth}
117 \newcommand*{\cftsubfigfont}={}
118 \newcommand*{\cftsubfigpresnum}={}
119 \newcommand*{\cftsubfigaftersnum}={}
120 \newcommand*{\cftsubfigaftersnumb}={}
121 \newcommand*{\cftsubfigleader}={}
122 \newcommand*{\cftsubfigdotsep}{1}
123 \newcommand*{\cftsubfigpagefont}={}
124 \newcommand*{\cftsubfigafterpnum}={}

125 \LWR@providelength{\cftbeforetabskip}
126 \LWR@providelength{\cfttabindent}
127 \LWR@providelength{\cfttabnumwidth}
128 \newcommand*{\cfttabfont}={}
129 \newcommand*{\cfttabpresnum}={}
130 \newcommand*{\cfttabaftersnum}={}
131 \newcommand*{\cfttabaftersnumb}={}
132 \newcommand*{\cfttableader}={}
133 \newcommand*{\cfttabdotsep}{1}
134 \newcommand*{\cfttabpagefont}={}
135 \newcommand*{\cfttabafterpnum}={}

136 \LWR@providelength{\cftbeforesubtabskip}
137 \LWR@providelength{\cftsubtabindent}
138 \LWR@providelength{\cftsubtabnumwidth}
139 \newcommand*{\cftsubtabfont}={}
140 \newcommand*{\cftsubtabpresnum}={}
141 \newcommand*{\cftsubtabaftersnum}={}
142 \newcommand*{\cftsubtabaftersnumb}={}
143 \newcommand*{\cftsubtableader}={}
144 \newcommand*{\cftsubtabdotsep}{1}
145 \newcommand*{\cftsubtabpagefont}={}
146 \newcommand*{\cftsubtabafterpnum}={}

147 \DeclareDocumentCommand{\cftsetindents}{m m m}{}

---


```

```

148 \newcommand{\pagenumbersoff}[1]{}
149 \newcommand{\pagenumberson}[1]{}

\newlistentry  [within] {counter} {ext} {level-1}
150 \DeclareDocumentCommand{\newlistentry}{o m m m}
151 {%
152 \LWR@traceinfo{newlistentry #2 #3 #4}%
153 \IfValueTF{#1}%
154 {%
155   \c@ifundefined{c@#2}{%
156     \newcounter{#2}[#1]%
157     \expandafter\edef\csname the#2\endcsname{%
158       \expandafter\noexpand\csname the#1\endcsname.\noexpand\arabic{#2}%
159     }%
160   }{}%
161 }%
162 {%
163   \c@ifundefined{c@#2}{%
164     \newcounter{#2}%
165   }{}%
166 }%
167 \c@namedef{l@#2}##1##2{%
168   \hypertocfloat{1}{#2}{#3}{##1}{##2}%
169   \def\cftwhatismyname{#2} from memoir
170 }%
171 \expandafter\newlength\csname cftbefore#2skip\endcsname%
172 \expandafter\newlength\csname cft#2indent\endcsname%
173 \expandafter\newlength\csname cft#2numwidth\endcsname%
174 \c@namedef{cft#2font}{}%
175 \c@namedef{cft#2presnum}{}%
176 \c@namedef{cft#2aftersnum}{}%
177 \c@namedef{cft#2aftersnumb}{}%
178 \c@namedef{cft#2leader}{}%
179 \c@namedef{cft#2dotsep}{1}%
180 \c@namedef{cft#2pagefont}{}%
181 \c@namedef{cft#2afterpnum}{}%
182 \c@namedef{toclevel@#2}{#4}%
183 \c@namedef{cft#2fillnum}##1{}%
184 \LWR@traceinfo{newlistentry done}%
185 }

\newlistof  [within] {type} {ext} {listofname}
Emulated through the \newfloat mechanism.

186 \DeclareDocumentCommand{\newlistof}{o m m m}
187 {%
188 \IfValueTF{#1}{%

```

```

189 {\newlistentry[#1]{#2}{#3}{0}}
190 {\newlistentry[#2]{#3}{0}}
191 \cftnaming{ext@#2}{#3}
192 \cftifundefined{c@#3depth}{\newcounter{#3depth}}{}
193 \cftsetcounter{#3depth}{1}
194 \cftnaming{cftmark#3}{}
195 \cftnaming{listof#2}{\listof{#2}{#4}}
196 \cftnaming{cftmake#3title}{}
197 \cftexpandafter{\cftnewlength\cftname cftbefore#3titleskip\endcsname}
198 \cftexpandafter{\cftnewlength\cftname cftafter#3titleskip\endcsname}
199 \cftnaming{cft#3titlefont}{}
200 \cftnaming{cftafter#3title}{}
201 \cftnaming{cft#3prehook}{}
202 \cftnaming{cft#3posthook}{}
203 }

\cftchapterprecis {<text>}
204 \newcommand{\cftchapterprecis}[1]{%
205   \cftchapterprecishere{#1}
206   \cftchapterprecistoc{#1}
207 \newcommand{\cftchapterprecishere}[1]{%
208   \begin{quote}\textit{#1}\end{quote}}
209 \newcommand{\cftchapterprecistoc}[1]{%
210   \addtocontents{toc}{%
211     \begin{protect}\begin{quote}#1\end{protect}\end{quote}}
212   }
213 }
214 }

```

File 308 **lwarf-tocstyle.sty**

§ 401 Package **tocstyle**

Pkg **tocstyle** **tocstyle** is ignored.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```

1 \LWR@ProvidesPackageDrop{tocstyle}

2 \newcommand*{\usetocstyle}[2][]{}
3 \newcommand*{\deactivatetocstyle}[1][]{}
4 \newcommand*{\reactivatetocstyle}[1][]{}
5 \NewDocumentCommand{\settocfeature}{o o m m}{}
6 \NewDocumentCommand{\settocstylefeature}{o m m}{}
7 \NewDocumentCommand{\newtocstyle}{o o m m}{}
8 \newcommand*{\aliastoc}[2]{}  


```

```
9 \newcommand*{\showtoc}[2][]{}
10 \newcommand{\iftochasdepth}[4]{}
```

File 309 **l warp-todo.sty**

§ 402 Package **todo**

(Emulates or patches code by FEDERICO GARCIA.)

Pkg todo **todo** is patched for use by **l warp**.

for HTML output:

```
1 \LWR@ProvidesPackagePass{todo}

2 \renewcommand\todoitem[2]{%
3   \refstepcounter{todo}%
4   \item[%
5     \HTMLunicode{2610} \quad
6     \ref{todopage}:\thetodo%
7   ] : {\todoformat\ifx#1\todomark\else\textbf{#1}\fi}#2%
8   \label{todolbl}:\thetodo}%
9 }%
10
11 \renewcommand\doneitem[2]{%
12   \stepcounter{todo}%
13   \item[%
14     \HTMLunicode{2611} \quad
15     \ref{todopage}:\thetodo%
16   ] \nameuse{@done}{\the\c@todo}:
17   {\todoformat\ifx#1\todomark\else\textbf{#1}\fi}#2%
18 }
19
20 \xpatchcmd{\@displaytodo}
21   {\todoformat #1}{\todoformat \textbf{#1}}{}
22   {\PackageWarning{l warp-todo}{Unable to patch @displaytodo.}}
23
24 \xpatchcmd{\@displayfulltodo}
25   {\todoformat #1}{\todoformat \textbf{#1}}{}
26   {\PackageWarning{l warp-todo}{Unable to patch @displayfulltodo.}}
27
28 \patchcmd{\todoenv}{\itshape see text.}{\textit{see text.}}{}
29   {\PackageWarning{l warp-todo}{Unable to patch todoenv.}}
30
31 \patchcmd{\astodos}{\todoformat #1}{\todoformat \textbf{#1}}{}
32   {\PackageWarning{l warp-todo}{Unable to patch astodos.}}
33
34 \AtBeginDocument{
35 \crefname{todo}{todo}{todos}
```

```
36 \Crefname{todo}{Todo}{Todos}
37 }
```

File 310 **l warp-todonotes.sty**

§ 403 Package **todonotes**

(Emulates or patches code by HENRIK SKOV MIDTIBY.)

Pkg **todonotes** **todonotes** is emulated.

The documentation for **todonotes** and **luatodonotes** have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

for HTML output:

```
1 \LWR@ProvidesPackagePass{todonotes}

2 \if@todonotes@disabled
3 \else
4
5 \newcommand{\ext@todo}{\tdo}
6
7 \renewcommand{\l@todo}[2]{\hypertocfloat{1}{\tdo}{\#1}{\#2}{

8 \let\LWRTODONOTES@orig@todototoc\todototoc
9
10 \renewcommand*{\todototoc}{%
11 \phantomsection%
12 \LWRTODONOTES@orig@todototoc%
13 }
14
15 \renewcommand{\@todonotes@drawMarginNoteWithLine}{%
16 \fcolorbox
17   {\@todonotes@currentbordercolor}
18   {\@todonotes@currentbackgroundcolor}
19   {\arabic{@todonotes@numberoftodonotes}}
20 \marginpar{\@todonotes@drawMarginNote}
21 }
22
23 \renewcommand{\@todonotes@drawInlineNote}{%
24 \fcolorboxBlock%
25   {\@todonotes@currentbordercolor}%
26   {\@todonotes@currentbackgroundcolor}%
27   {%
28     \if@todonotes@authorgiven%
29       {\@todonotes@author:\,}%

```

```
30      \fi%
31      \@todonotes@text%
32  }%
33 }%
34
35 \renewcommand{\@todonotes@drawMarginNote}{%
36     \if@todonotes@authorgiven%
37         \@todonotes@author\par%
38     \fi%
39     \arabic{@todonotes@numberoftodonotes}: %
40     \fcolorbox{%
41         {\@todonotes@currentbordercolor}%
42         {\@todonotes@currentbackgroundcolor}%
43     }{%
44         \@todonotes@sizecommand%
45         \@todonotes@text %
46     }%
47 }%
48
49 \renewcommand{\@todonotes@drawLineToRightMargin}{}
50
51 \renewcommand{\@todonotes@drawLineToLeftMargin}{}
52
53 \renewcommand{\missingfigure}[2][]{%
54 \setkeys{todonotes}{#1}%
55 \addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
56 \fcolorboxBlock{%
57     {\@todonotes@currentbordercolor}%
58     {\@todonotes@currentfigcolor}%
59 }{%
60     \setlength{\fboxrule}{4pt}%
61     \fcolorbox{red}{white}{Missing figure} \quad #2%
62 }
63 }
64
65 \LetLtxMacro{\LWRTODONOTES@orig}{\@todo}
66
67 \RenewDocumentCommand{\@todo}{o m}{%
68 \begingroup%
69 \renewcommand*{\phantomsection}{()}%
70 \IfValueTF{#1}{%
71     \LWRTODONOTES@orig[#1]{#2}%
72 }{%
73     \LWRTODONOTES@orig{#2}%
74 }
75 \endgroup%
76 }
77
78 \fi% \if@todonotes@disabled
```

File 311 **l warp-transparent.sty**

§ 404 Package **transparent**

(Emulates or patches code by HEIKO OBERDIEK.)

Pkg **transparent** Emulated. `\texttransparent` works for inline objects. `\transparent` only works for `\includegraphics`.

 **Not X_{FIG}TEX!** Note that **transparent** does not work with X_{FIG}TEX.

for HTML output: Discard all options for **l warp-transparent**:

```
1 \LWR@ProvidesPackageDrop{transparent}

2 \newcommand*{\transparent}[1]{\edef\LWR@opacity{#1}}
3
4 \newcommand*{\texttransparent}[2]{%
5 \begingroup%
6 \transparent{#1}%
7 \InlineClass[opacity: #1]{transparent}{#2}%
8 \endgroup%
9 }
```

File 312 **l warp-trimclip.sty**

§ 405 Package **trimclip**

Pkg **trimclip** **trimclip** is nullified.

for HTML output: 1 \LWR@ProvidesPackageDrop{trimclip}

The third argument, the text, is not touched. This allows `\bgroup` / `\egroup`, and `verbatim` content.

```
2 \csdef{trimbox}{\@ifstar@gobble@gobble}
3 \csletcs{trimbox*}{trimbox}
4 \def\endtrimbox{}
5 \csletcs{endtrimbox*}{endtrimbox}
6
7 \csletcs{clipbox}{trimbox}
8 \csletcs{clipbox*}{trimbox}
```

```

9 \csletcs{endclipbox}{endtrimbox}
10 \csletcs{endclipbox*}{endtrimbox}
11
12 \csletcs{marginbox}{trimbox}
13 \csletcs{marginbox*}{trimbox}
14 \csletcs{endmarginbox}{endtrimbox}
15 \csletcs{endmarginbox*}{endtrimbox}
```

File 313 **l warp-trivfloat.sty**

§ 406 Package **trivfloat**

(Emulates or patches code by JOSEPH WRIGHT.)

Pkg **trivfloat** **trivfloat** is forced to use the built-in **l warp** emulation for floats.

Discard all options for **l warp-trivfloat**. This tells **trivfloat** not to use **floatrow** or **memoir**.

To create a new float type and change its name:

```
\trivfloat{example}
\renewcommand{\examplename}{Example Name}
\crefname{example}{example}{examples}
\Crefname{example}{Example}{Examples}
```

```

1 \LWR@ProvidesPackageDrop{trivfloat}
2 \LWR@origRequirePackage{trivfloat}
```

\tfl@chapter@fix Nullified at the beginning of the document. Is used by **trivfloat** to correct float chapter numbers, but is not needed for **l warp**.

for HTML output:

```

3 \begin{warpHTML}
4 \AtBeginDocument{\DeclareDocumentCommand{\tfl@chapter@fix}{m m}{}}
5 \end{warpHTML}
```

§ 406.1 Combining \newfloat, \trivfloat, and algorithmicx

for HTML & PRINT: 6 \begin{warpall}

For both print and HTML output:

- ⚠ When using **float**, **trivfloat**, or **algorithmicx** at the same time, be aware of conflicting file usage. **algorithmicx** uses .loa. **trivfloat** by default starts with .loa and goes up for additional floats, skipping .lof and .lot.
- ⚠ When using \newfloat, be sure to manually assign higher letters to the \newfloat files to avoid .loa used by **algorithmicx**, and any files used by **trivfloat**. Also avoid using .lof and .lot.
- ⚠ When using \trivfloat, you may force it to avoid conflicting with **algorithmicx** by starting **trivfloat**'s file extensions with .lob:

```
\makeatletter
\setcounter{tfl@float@cnt}{1} % start trivfloats with .lob
\makeatletter
```

7 \end{warpall}

File 314 l warp-turnthepage.sty

§ 407 Package **turnthepage**

Pkg **turnthepage** **turnthepage** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{turnthepage}

2 \newcommand{\turnthepage}{}  


```

File 315 l warp-typearea.sty

§ 408 Package **typearea**

(Emulates or patches code by MARKUS KOHM.)

Pkg **typearea** **typearea** is emulated.

This package may be loaded standalone, but is also loaded automatically if **koma-script** classes are in use. `\DeclareDocumentCommand` is used to overwrite the **koma-script** definitions.

for HTML output:

```

1 \LWR@ProvidesPackage{typearea}

2 \DeclareDocumentCommand{\typearea}{o m}{}
3 \DeclareDocumentCommand{\recalctypearea}{}{}
4 \Ifundefined{fooheight}{\newlength\fooheight}{}
5 \DeclareDocumentCommand{\areaset}{o m m}{}
6 \DeclareDocumentCommand{\activateareas}{}{}
7 \DeclareDocumentCommand{\storeareas}{m}{}
8 \DeclareDocumentCommand{\BeforeRestoreareas}{s m}{}
9 \DeclareDocumentCommand{\AfterRestoreareas}{s m}{}
10 \DeclareDocumentCommand{\AfterCalculatingTypearea}{s m}{}
11 \DeclareDocumentCommand{\AfterSettingArea}{s m}{}

```

File 316 l warp-ulem.sty

§ 409 Package **ulem**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg **ulem** Emulated.

for HTML output: Emulate the original package:

```
1 \ProvidesPackage{l warp-ulem}
```

Original **l warp** definitions:

```

2 \LetLtxMacro{\LWR@ulemorig}{\emph\emph}
3 \LetLtxMacro{\LWR@ulemorig}{\textbf\textbf}

```

Basic markup commands, using css:

```

4 \NewDocumentCommand{\uline}{+m}{%
5 \LWR@HTMLtextstyle%
6   {text-decoration:underline; text-decoration-skip: auto}%
7   {uline}{#1}%
8 }
9
10 \NewDocumentCommand{\uuline}{+m}{%
11 \LWR@HTMLtextstyle%
12   {%
13     text-decoration:underline; text-decoration-skip: auto;%

```

```
14         text-decoration-style:double%
15     }%
16     {uuline}{#1}%
17 }
18
19 \NewDocumentCommand{\uwave}{+m}{%
20 \LWR@HTMLtextstyle{%
21   {%
22     text-decoration:underline; text-decoration-skip: auto;%
23     text-decoration-style:wavy%}
24   }%
25   {uwave}{#1}%
26 }
27
28 \NewDocumentCommand{\sout}{+m}{%
29 \LWR@HTMLtextstyle{%
30   {text-decoration:line-through}%
31   {sout}{#1}%
32 }
33
34 \NewDocumentCommand{\xout}{+m}{%
35 \LWR@HTMLtextstyle{%
36   {text-decoration:line-through}%
37   {xout}{#1}%
38 }
39
40 \NewDocumentCommand{\dashuline}{+m}{%
41 \LWR@HTMLtextstyle{%
42   {%
43     text-decoration:underline;%
44     text-decoration-skip: auto;%
45     text-decoration-style:dashed%}
46   }%
47   {dashuline}{#1}%
48 }
49
50 \NewDocumentCommand{\dotuline}{+m}{%
51 \LWR@HTMLtextstyle{%
52   {%
53     text-decoration:underline;%
54     text-decoration-skip: auto;%
55     text-decoration-style: dotted%}
56   }%
57   {dotuline}{#1}%
58 }
```

Nullified parameters:

```
59 \NewDocumentCommand{\ULthickness}{[]}{}
```

```
60 \newlength{\ULdepth}
```

Nullified/emulated macros:

```
61 \NewDocumentCommand{\markoverwith}{m}{}
62 \NewDocumentCommand{\ULon}{+m}{\uline{\#1}\egroup}
```

\useunder only works with \textbf, etc, but not \bfseries, etc.

```
63 \NewDocumentCommand{\useunder}{m m m}{%
64 \relax%
65 \ifx\relax#3\relax\else % argumentative command
66   \def#3{\#1}\MakeRobust{#3}\fi
67 }
```

Triggered by package options, also available for the users:

```
68 \newcommand*{\normalem}{\LetLtxMacro{\emph}{\LWR@ulemorigemph}}
69 \newcommand*{\ULforem}{\LetLtxMacro{\emph}{\uline}}
70 \ULforem% default
```

Package options:

```
71 \DeclareOption{normalem}{\normalem}
72 \DeclareOption{ULforem}{\ULforem}
73 \DeclareOption{normalbf}{}
74 \DeclareOption{UWforbf}{\useunder{\uwave}{\bf}{\textbf}}
75
76 \DeclareOption*{}
77 \ProcessOptions\relax% original LaTeX code
```

File 317 l warp-underscore.sty

§ 410 Package **underscore**

Pkg underscore **underscore** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{underscore}

File 318 l warp-units.sty

§ 411 Package **units**

(Emulates or patches code by AXEL REICHERT.)

Pkg units **units** is patched for use by **l warp**.

for HTML output: 1 \LWR@ProvidesPackagePass{units}[1998/08/04]

For Mathjax:

```
2 \CustomizeMathJax{\newcommand{\unit}{[2] [] {#1 #2}}  
3 \CustomizeMathJax{\newcommand{\unitfrac}{[3] [] {#1 #2/#3}}}
```

File 319 **l warp-upref.sty**

§ 412 Package **upref**

Pkg upref Ignored.

for HTML output: Discard all options for **l warp-upref**:

```
1 \LWR@ProvidesPackageDrop{upref}
```

File 320 **l warp-url.sty**

§ 413 Package **url**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg url **url** is patched for use by **l warp**.

for HTML output: 1 \LWR@ProvidesPackagePass{url}

url uses math mode to print its string inside a group, so the original meaning of math is restored first.

```
2 \LetLtxMacro{\LWR@url@origUrl@FormatString}{\Url@FormatString}  
3  
4 \renewcommand*{\Url@FormatString}{%  
5   \InlineClass{verbatim}{%  
6     \LWR@restoreorigformatting%  
7     \LWR@url@origUrl@FormatString%  
8   }%  
9 }
```

File 321 **l warp-uspace.sty**

§ 414 Package **uspace**

Pkg **uspace** **uspace** is ignored.

for HTML output: `1 \LWR@ProvidesPackageDrop{uspace}`

File 322 **l warp-verse.sty**

§ 415 Package **verse**

(Emulates or patches code by PETER WILSON.)

Pkg **verse** **verse** is supported and patched by **l warp**.

for HTML output: Pass all options for **l warp-verse**:

`1 \LWR@ProvidesPackagePass{verse}`

When using **verse** or **memoir**, always place a `\\"` after each line.

\attrib The documentation for the **verse** and **memoir** packages suggest defining an `\attrib` command, which may already exist in current documents, but it will only work for print output. **l warp** provides `\attribution`, which works for both print and HTML output. To combine the two so that `\attrib` is used for print and `\attribution` is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len `\vleftskip` These lengths are used by **verse** and **memoir** to control the left margin, and they
Len `\vleftmargini` may already be set by the user for print output. New lengths `\HTMLvleftskip` and
Len `\HTMLvleftskip` `\HTMLleftmargini` are provided to control the margins in HTML output. These new
Len `\HTMLleftmargini` lengths may be set by the user before any **verse** environment, and persist until they
are manually changed again. One reason to change `\HTMLleftmargini` is if there
is a wide `\flagverse` in use, such as the word “Chorus”, in which case the value of

\HTMLleftmargini should be set to a wide enough length to contain “Chorus”. The default is wide enough for a stanza number.

-  **spacing** Horizontal spacing relies on **pdftotext**'s ability to discern the layout (-layout option) of the text in the HTML-tagged PDF output. For some settings of \HTMLleftmargini or \HTMLleftskip the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

Env **verse** The **verse** environment will be placed inside a HTML <pre>.

```
2 \AfterEndPreamble{  
3 \LWR@traceinfo{Patching verse.}}
```

At the beginning of the **verse** environment:

```
4 \AtBeginEnvironment{verse}  
5 {%
```

Use the original **list** environment inside a <pre> to attempt to preserve formatting.

```
6 \LWR@restoreoriglists%
```

Pkg **verse** The **verse** or **memoir** packages can place stanza numbers to the left with their **\flagverse** command. Do not allow them to go into the left margin, which would cause **pdfcrop** to crop the entire page further to the left:
 Cls **memoir**
\flagverse
 Len **\vleftskip**

```
7 \ifdef{\vleftskip}{%  
8 \setlength{\vleftskip}{\HTMLvleftskip}  
9 \setlength{\leftmargini}{\HTMLleftmargini}  
10 }{}  
11 \LWR@forcenewpage  
12 \LWR@atbeginverbatim{3}{verse}%
13 }
```

After the end of the **verse** environment, which places the <pre> tag at the regular left margin:

```
14 \AtEndEnvironment{verse}{%  
15 \leavevmode%  
16 \LWR@afterendverbatim{1}%
17 }
```

Patch to place **poemtitle** inside an HTML of class **poemtitle**:

```
18 \ifdef{\poemtitle}{%
19 \DeclareDocumentCommand{\@vstypepoemtitle}{m}{%
```

```
20   \vspace{\beforepoemtitleskip}%
21   {\InLineClass{poemtitle}{\poemtitlefont #1}\par}%
22   \vspace{\afterpoemtitleskip}%
23 }
24 }{}%
25
26 \LWR@traceinfo{Finished patching verse.}%
27 }% AfterEndPreamble
```

File 323 **l warp-vertbars.sty**

§ 416 Package **vertbars**

(Emulates or patches code by PETER WILSON.)

Pkg **vertbars** **vertbars** is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{vertbars}

2 \newlength{\barwidth}
3 \setlength{\barwidth}{0.4pt}
4 \newlength{\barspace}
5 \setlength{\barspace}{1em}
6
7 \newenvironment{vertbar}{
8   \LWR@forcenewpage
9   \LWR@forceminwidth{\barwidth}
10  \begin{BlockClass}[%]
11    border-left: \LWR@printlength{\LWR@atleastonept} solid black ; %
12    padding-left: \LWR@printlength{\barspace}%
13  ]{vertbar}
14 }{
15  \end{BlockClass}
16 }
```

File 324 **l warp-vmargin.sty**

§ 417 Package **vmargin**

Pkg **vmargin** **vmargin** is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{vmargin}
```

```

2 \newcommand*{\LWRVM@customsize}[2]{}
3 \newcommand*{\setpapersize}[2][]{\ifstreq{\#2}{custom}{\LWRVM@customsize}{}}
4 \newcommand*{\setmargins}[8]{}
5 \newcommand*{\setmarginsrb}[8]{}
6 \newcommand*{\setmargnohf}[4]{}
7 \newcommand*{\setmargnohfrb}[4]{}
8 \newcommand*{\setmarg}[4]{}
9 \newcommand*{\setmargrb}[4]{}
10 \newlength{\PaperWidth}
11 \setlength{\PaperWidth}{8.5in}
12 \newlength{\PaperHeight}
13 \setlength{\PaperHeight}{11in}
14 \newif\ifLandscape

```

File 325 **l warp-vowel.sty**

§ 418 Package **vowel**

(Emulates or patches code by FUKUI REI.)

Pkg **vowel** **vowel** is patched for use by **l warp**.

This package has been tested with **pdflatex** and the Type 1 TIPA fonts using the following package load sequence:

```

\usepackage[T3,T1]{fontenc}
\usepackage[utf8]{inputenc}
\usepackage[noenc]{tipa}
\usepackage{vowel}

```

for HTML output: 1 \LWR@ProvidesPackagePass{vowel}

```

2 \renewenvironment{vowel}[1][]{%
3   {%
4     \begin{lateximage}[(-vowel--\packagediagramname)]%
5     \vowel[\#1]%
6   }%
7   {%
8     \@@vowel%
9     \end{lateximage}%
10 }

```

File 326 **l warp-vpe.sty**

§ 419 Package **vpe**

Pkg vpe **vpe** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{vpe}[2012/04/18]

File 327 **l warp-vwcol.sty**

§ 420 Package **vwcol**

(Emulates or patches code by WILL ROBERTSON.)

Pkg vwcol **vwcol** is patched for use with **l warp**.

The width option is ignored. All vwcol environments adjust to 1–3 equal-width columns, depending on the width of the browser window.

The remaining options are supported, except for lines and maxrecursion.

for HTML output: 1 \LWR@ProvidesPackagePass{vwcol}

Factored from \vwcol. Each is given a style tag to append to the final style.

```
\LWR@vwcol@addrule {<style tag>}\n 2 \newcommand*{\LWR@vwcol@addrule}[1]{%\n 3   \appto{\LWR@vwcolstyle}{%\n 4     #1: %\n 5     \LWR@printlength{\vwcol@rule} solid \LWR@origpound\LWR@vwcol@rulecolor ; %\n 6   }%\n 7 }\n\n\LWR@vwcol@addrule {<style tag>}\n 8 \newcommand*{\LWR@vwcol@addgap}[1]{%\n 9   \appto{\LWR@vwcolstyle}{%\n10     #1: %\n11     \LWR@printlength{\vwcol@sep} ; %\n12   }%\n13 }
```

Env `vwcol` {*key/values*}

Redefine the environment to add a HTML style. The style is built depending on the required options.

14 \renewenvironment*{vwcol}[1] [] {%

New paragraph, and process the options:

15 \par\noindent%

16 \vwcolsetup{\#1} %

Begin with no style:

17 \newcommand*{\LWR@vwcolstyle}{}{}

`presep` and `postsep` are created with `HTML margins`:

18 \if@vwcol@presep

19 \appto{\LWR@vwcolstyle}{margin-left: 1em ; padding-left: .5em ; }

20 \fi

21 \if@vwcol@postsep

22 \appto{\LWR@vwcolstyle}{margin-right: 1em ; padding-right: .5em ; }

23 \fi

`sep` becomes `column-gap`:

24 \ifdimgreater{\vwcol@sep}{1sp}{

25 \LWR@vwcol@addgap{column-gap}

26 \LWR@vwcol@addgap{-moz-column-gap}

27 \LWR@vwcol@addgap{-webkit-column-gap}

28 }{}}

`rule` become `column-rule`, while `prerule` and `postrule` become `HTML borders`:

29 \convertcolorspec[named]{\vwcol@rulecol}{HTML}\LWR@vwcol@rulecolor%

30 \ifdimgreater{\vwcol@rule}{0pt}{

31 \ifdimless{\vwcol@rule}{1pt}{

32 \setlength{\vwcol@rule}{1pt}

33 }{}

34 \LWR@vwcol@addrule{column-rule}

35 \LWR@vwcol@addrule{-moz-column-rule}

36 \LWR@vwcol@addrule{-webkit-column-rule}

37 \if@vwcol@prerule \LWR@vwcol@addrule{border-left}\fi

38 \if@vwcol@postrule \LWR@vwcol@addrule{border-right}\fi

39 }{}}

Each of the `justify` options becomes a `text-align`. Indentation is added where appropriate.

40 \ifdefequal{\vwcol@justify}{\RaggedRight}{

41 \appto{\LWR@vwcolstyle}{text-align: left ; }

42 \ifdimgreater{\vwcol@parindent}{0pt}{

43 \appto{\LWR@vwcolstyle}{%

```

44         text-indent: \LWR@printlength{\vvcoll@parindent} ; %
45     }
46   }{}
47 }{}

48 \ifdefequal{\vvcoll@justify}{\RaggedLeft}{%
49   \appto{\LWR@vvcollstyle}{text-align: right ; }
50 }{}

51 \ifdefequal{\vvcoll@justify}{\Centering}{%
52   \appto{\LWR@vvcollstyle}{text-align: center ; }
53 }{}

54 \ifdefequal{\vvcoll@justify}{\justifying}{%
55   \appto{\LWR@vvcollstyle}{text-align: justify ; }
56   \ifdimgreater{\vvcoll@parindent}{0pt}{%
57     \appto{\LWR@vvcollstyle}{%
58       text-indent: \LWR@printlength{\vvcoll@parindent} ; %
59     }
60   }{}
61 }{}}

```

Create the <div> with the assembled style:

```

62 \BlockClass[\LWR@vvcollstyle]{multicols}
63 }

```

When the environment ends:

```

64 {
65 \endBlockClass
66 }

```

File 328 lwarf-wallpaper.sty

§ 421 Package **wallpaper**

(Emulates or patches code by MICHAEL H.F. WILKINSON.)

Pkg wallpaper **wallpaper** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{wallpaper}

```

2 \newcommand*\CenterWallPaper}[2]{}
3 \newcommand*\ThisCenterWallPaper}[2]{}
4 \newcommand*\TileWallPaper}[3]{}
5 \newcommand*\ThisTileWallPaper}[3]{}
6 \newcommand*\TileSquareWallPaper}[2]{}
7 \newcommand*\ThisTileSquareWallPaper}[2]{}
8 \newcommand*\ULCornerWallPaper}[2]{}

```

```
9 \newcommand*{\ThisULCornerWallPaper}[2]{}
10 \newcommand*{\LLCornerWallPaper}[2]{}
11 \newcommand*{\ThisLLCornerWallPaper}[2]{}
12 \newcommand*{\URCornerWallPaper}[2]{}
13 \newcommand*{\ThisURCornerWallPaper}[2]{}
14 \newcommand*{\LRCornerWallPaper}[2]{}
15 \newcommand*{\ThisLRCornerWallPaper}[2]{}
16 \newcommand*{\ClearWallPaper}{}{}
17 \newlength{\wpXoffset}
18 \newlength{\wpYoffset}
```

File 329 **l warp-wasy sym .sty**

§ 422 Package **wasy sym**

Pkg **wasy sym** **wasy sym** does not work with **pdftotext**.

for HTML output: 1 \LWR@loadnever{wasy sym}{textcomp, amssymb, amsfonts, mnsymbol, fdsymbol}

File 330 **l warp-watermark .sty**

§ 423 Package **watermark**

(Emulates or patches code by ALEXANDER I. ROZHENKO.)

Pkg **watermark** **watermark** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{watermark}

2 \newcommand{\watermark}[1]{}
3 \newcommand{\leftwatermark}[1]{}
4 \newcommand{\rightwatermark}[1]{}
5 \newcommand{\thiswatermark}[1]{}
6 \newcommand{\thispageheading}[1]{}

File 331 **l warp-widows-and-orphans .sty**

§ 424 Package **widows-and-orphans**

Pkg **widows-and-orphans** **widows-and-orphans** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{widows-and-orphans} [2018/09/01]

```
2 \NewDocumentCommand\WaOsetup{m}{}  
3 \NewDocumentCommand\WaOparameters{}{}  
4 \NewDocumentCommand\WaOignorenext{}{}
```

File 332 l warp-wrapfig.sty

§ 425 Package **wrapfig**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg wrapfig **wrapfig** is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{wrapfig}  
  
2 \newcommand*\LWR@wrapposition{}  
3  
4 \newcommand*\LWR@subwrapfigure[2]{%  
5 \renewcommand*\LWR@wrapposition{}%  
6 \ifthenelse{  
7     \equal{\#1}{r}\OR\equal{\#1}{R}\OR%  
8     \equal{\#1}{o}\OR\equal{\#1}{O}}%  
9 }%  
10 {\renewcommand*\LWR@wrapposition{float:right}}%  
11 {\renewcommand*\LWR@wrapposition{float:left}}%  
12 \setlength{\LWR@templengthone}{#2}%  
13 \LWR@BlockClassWP{  
14     width:\LWR@printlength{\LWR@templengthone}; \LWR@wrapposition; %  
15     margin:10pt%  
16 }%  
17 {  
18     width:\LWR@printlength{\LWR@templengthone}; \LWR@wrapposition%  
19 }%  
20 {marginblock}%  
21 }  
22  
23  
24 \NewDocumentEnvironment{wrapfigure}{o m o m}  
25 {  
26 \LWR@subwrapfigure{#2}{#4}%  
27 \captionsetup{type=figure}%  
28 }  
29 {  
30 \endLWR@BlockClassWP%  
31 }  
32  
33  
34 \NewDocumentEnvironment{wraptable}{o m o m}
```

```
35 {%
36 \LWR@subwrapfigure{#2}{#4}%
37 \captionsetup{type=table}%
38 }%
39 {%
40 \endLWR@BlockClassWP%
41 }%
42
43
44 \NewDocumentEnvironment{wrapfloat}{m o m o m}%
45 {%
46 \LWR@subwrapfigure{#3}{#5}%
47 \captionsetup{type=#1}%
48 }%
49 {%
50 \endLWR@BlockClassWP%
51 }%
52
53 \newlength{\wrapoverhang}
```

File 333 **l warp-xbmks.sty**

§ 426 Package **xbmks**

Pkg **xbmks** **xbmks** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{xbmks}[2018/07/04]

```
2 \newcommand{\xbmksetup}[1]{}
3 \NewDocumentCommand{\pdfbookmarkx}{o m o m}{}%
4 \NewDocumentCommand{\currentpdfbookmarkx}{m o m}{}%
5 \NewDocumentCommand{\subpdfbookmarkx}{m o m}{}%
6 \NewDocumentCommand{\belowpdfbookmarkx}{m o m}{}%
```

File 334 **l warp-xcolor.sty**

§ 427 Package **xcolor**

(Emulates or patches code by DR. UWE KERN.)

Pkg **xcolor** **xcolor** is supported by l warp.

§ 427.1 Limitations

\colorboxBlock and \fcolorboxBlock	\colorboxBlock and \fcolorboxBlock are provided for increased HTML compatibility, and they are identical to \colorbox and \fcolorbox in print mode. In HTML mode they place their contents into a <div> instead of a . These <div>s are set to display: inline-block so adjacent \colorboxBlocks appear side-by-side in HTML, although text is placed before or after each.
	Print-mode definitions for \colorboxBlock and \fcolorboxBlock are created by l warp's core if xcolor is loaded.
background: none	\fcolorbox and \fcolorboxBlock allow a background color of none, in which case only the frame is drawn, which can be useful for HTML.
color support	Color definitions, models, and mixing are fully supported without any changes required.
colored tables	\rowcolors is supported, except that the optional argument is ignored so far.
colored text and boxes	\textcolor, \colorbox, and \fcolorbox are supported.
\color and \pagecolor	\color and \pagecolor are ignored. Use css or \textcolor where possible.

§ 427.2 Xcolor definitions: location and timing

The l warp core and its l warp-xcolor package are tightly integrated to allow comparable results for print, HTML, and print inside an HTML `lateximage`. This requires a number of definitions and redefinitions depending on whether each of `xcolor` and `lateximage` is being used, and whether print or HTML is being generated. Some of these actions are one-time when `xcolor` is loaded, and others are temporary as `lateximage` is used.

When `xcolor` is loaded in print mode: No special actions are taken at the time that `xcolor` is loaded in print mode, but see \AtBeginDocument below.

When l warp-xcolor is loaded in HTML mode: `xcolor`'s original definitions are saved for later restoration. \LWR@restoreorigformatting is appended to restore these definitions for use inside a `lateximage`. New HTML-mode definitions are created for \textcolor, \pagecolor, \nopagecolor, \colorbox, \colorboxBlock, \fcolorbox, \fcolorboxBlock, and fcolorminipage.

\AtBeginDocument in print or HTML mode: See Section 82. If `xcolor` has been loaded, the print-mode \fcolorbox is modified to accept a background color of none, and additional definitions are created for l warp's new macros print-mode macros \colorboxBlock, \fcolorboxBlock, and fcolorminipage. The HTML versions of these macros will already have been created by l warp-xcolor if it has been loaded.

For use inside an HTML `lateximage`, `\LWR@restoreorigformatting` is appended to temporarily set these functions to their print-mode versions.

In a `lateximage` in HTML mode: `\LWR@restoreorigformatting` temporarily restores the print-mode definitions of `xcolor`'s functions. See `\LWR@restoreorigformatting` on page 500.

`\color:`

Print: Used as-is.

HTML: Ignored by `pdftotext`, and will not appear.

HTML `lateximage`: Colors will appear in a `lateximage`.

`\textcolor:`

Print: Used as-is.

HTML: Redefined by `l warp-xcolor`, page 946.

HTML `lateximage`: Remembers and reuses the print version.

`\pagecolor:`

Print: Used as-is.

HTML: Ignored.

HTML `lateximage`: Colors will be picked up in a `lateximage`.

`\nopagecolor:`

Print: Used as-is.

HTML: Ignored.

HTML `lateximage`: Colors will be picked up in a `lateximage`.

`\colorbox:`

Print: Used as-is.

HTML: Redefined by `l warp-xcolor`, page 947.

HTML `lateximage`: Remembers and reuses the print version.

`\colorboxBlock:`

Print: Becomes `\colorbox`.

HTML: Newly defined by `l warp-xcolor` to use a `<div>`, page 947.

HTML `lateximage`: Remembers and reuses the print version `\colorbox`.

`\fcolorbox:`

Print: Modified to allow a background of `none`.

`\LWR@print@fcolorbox` at section 82

HTML: Redefined by **l warp-xcolor**, page 948.

HTML lateximage: Remembers and reuses the print version.

\fcolorboxBlock:

Print: Becomes \fcolorbox. Section 82

HTML: Newly defined by **l warp-xcolor** to use a <div>, page 948.

HTML lateximage: Remembers and reuses the print version \fcolorbox.

fcolorminipage:

Print: Newly defined in the **l warp** core.

LWR@print@fcolorminipage at section 82

HTML: Newly defined by **l warp-xcolor**, page 949.

HTML lateximage: Uses the print version.

\boxframe:

Print: Used as-is.

HTML: Redefined by **l warp-xcolor**, page 950.

HTML lateximage: Remembers and reuses the print version.

§ 427.3 Package loading

```
for HTML output: 1 \LWR@ProvidesPackagePass{xcolor}
                  2 \begin{warpHTML}
```

§ 427.4 Remembering and restoring original definitions

Remember the following print-mode actions to be restored when inside a `lateximage` environment:

```
3 \LetLtxMacro{\LWR@print@pagecolor}{\pagecolor}
4 \LetLtxMacro{\LWR@print@nopagecolor}{\nopagecolor}
```

`\LWR@restoreorigformatting` Inside a `lateximage` the following gets restored to their print-mode actions:

```
5 \appto{\LWR@restoreorigformatting}{%
6 \LetLtxMacro{\pagecolor}{\LWR@print@pagecolor}%
7 \LetLtxMacro{\nopagecolor}{\LWR@print@nopagecolor}%
8 }
```

§ 427.5 HTML color style

Sets \LWR@tempcolor to the current color.

```
1 \LWR@findcurrenttextcolor
2   9 \renewcommand*\{\LWR@findcurrenttextcolor\}{%
3     10 \protect\colorlet{\LWR@current@color}{.}%
4     11 \protect\convertcolorspec{named}{\LWR@current@color}{HTML}\LWR@tempcolor%
5   12 }
```

Prints a color style for the current color.

```
6 \LWR@currenttextcolorstyle
7   13 \newcommand*\{\LWR@currenttextcolorstyle\}{%
8     14 \LWR@findcurrenttextcolor%
9     15 \ifdefstring{\LWR@tempcolor}{000000}%
10    16 {}%
11    17 {color: \LWR@origpound\LWR@tempcolor ; }%
12    18 }
```

\LWR@textcurrentcolor {\langle text\rangle} Like \textcolor but uses the current \color instead.

```
13 \DeclareDocumentCommand{\LWR@textcurrentcolor}{m}{%
14   \begingroup%
15   \LWR@FBcancel%
16   \LWR@findcurrenttextcolor%
17   \InlineClass [color:\LWR@origpound\LWR@tempcolor]{textcolor}{%
18     \renewcommand*\{\LWR@currenttextcolor\}{\LWR@origpound\LWR@tempcolor}%
19     #1%
20   }%
21   \endgroup%
22 }
```

\LWR@colorstyle {\langle 2: model\rangle} {\langle 3: color\rangle}

For a color style, prints the color converted to HTML colors.

```
23 \NewDocumentCommand{\LWR@colorstyle}{m m}{%
24   \begingroup%
25   \LWR@FBcancel%
```

Use the **xcolor** package to convert to an HTML color space:

```
26 \convertcolorspec{\#1}{\#2}{HTML}\LWR@tempcolor%
```

Print the converted color:

```
27 \LWR@origpound\LWR@tempcolor%
28 \endgroup%
29 }
```

\LWR@backgroundcolor [{\langle model\rangle}] {\langle color\rangle} {\langle text\rangle}

Similar to `\textcolor`, but prints black text against a color background.

Converted into an HTML hex color span.

```
36 \NewDocumentCommand{\LWR@backgroundcolor}{O{named} m m}{%
37 \begingroup%
38 \LWR@FBcancel%
39 \InlineClass[background:\LWR@colorstyle{#1}{#2}]{backgroundcolor}{%
40 #3%
41 }%
42 \endgroup%
43 }
```

§ 427.6 HTML border

`\LWR@borderpadding` [$\langle colorstyle \rangle$] [$\langle color \rangle$] Prints the HTML attributes for a black border and padding.
`\LWR@forceminwidth` must be used first in order to set the border width.

```
44 \newcommand*{\LWR@borderpadding}[2]{%
45 border:\LWR@printlength{\LWR@atleastonept} solid \LWR@colorstyle{#1}{#2} ; %
46 padding:\LWR@printlength{\fboxsep}%
47 }
```

§ 427.7 High-level macros

`\textcolor` [$\langle model \rangle$] [$\langle color \rangle$] [$\langle text \rangle$]

Converted into an HTML hex color span.

```
48 \NewDocumentCommand{\LWR@HTML@textcolor}{o m m}{%
49 \begingroup%
```

Set the PDF color, to be picked up by SVG math if possible.

The print-mode `\color` command cannot accept the named option with color mixing,
but it works with no option at all.

```
50 \IfValueTF{#1}{%
51   \color[#1]{#2}%
52 }{%
53   \color{#2}%
54 }%
55 \LWR@FBcancel%
56 \IfValueTF{#1}{%
57 \InlineClass[color:\LWR@colorstyle{#1}{#2}]{textcolor}{%
58 \renewcommand*{\LWR@currenttextcolor}{\LWR@origpound\LWR@tempcolor}%
59 #3%}
```

```
60 }%
61 }{%
62 \InlineClass [color:\LWR@colorstyle{named}{#2}]{textcolor}{%
63 \renewcommand*\{\LWR@currenttextcolor\}{\LWR@origpound\LWR@tempcolor}%
64 #3%
65 }%
66 }%
67 \endgroup%
68 }
69
70 \LWR@formatted{textcolor}
```

\pagecolor [*model*] {*color*}

Ignored. Use css instead.

```
71 \renewcommand*\{\pagecolor}[2][named]{}
```

\nopagecolor Ignored.

```
72 \renewcommand*\{\nopagecolor}{}
```

\colorbox [*model*] {*color*} {*text*}

Converted into an HTML hex background color .

```
73 \NewDocumentCommand{\LWR@HTML@colorbox}{O{named} m +m}{%
74 \begingroup%
75 \LWR@FBcancel%
76 \InlineClass[%
77 background:\LWR@colorstyle{#1}{#2} ; %
78 padding:\LWR@printlength{\fboxsep}%
79 ]{\colorbox}{#3}%
80 \endgroup%
81 }
82
83 \AtBeginDocument{
84 \LWR@formatted{colorbox}
85 }
```

\colorboxBlock [*model*] {*color*} {*text*}

Converted into an HTML hex background color <div>.

```
86 \NewDocumentCommand{\LWR@HTML@colorboxBlock}{O{named} m +m}{%
```

```

87 \begingroup%
88 \LWR@FBcancel%
89 \begin{BlockClass}[%  

90 background:\LWR@colorstyle{\#1}{\#2} ; %
91 padding:\LWR@printlength{\fboxsep}%
92 ]{colorboxBlock}
93 #3
94 \end{BlockClass}%
95 \endgroup%
96 }
97
98 \AtBeginDocument{
99 \LWR@formatted{colorboxBlock}
100 }

```

\fcolorbox [⟨framemode⟩] {⟨framecolor⟩} [⟨boxmode⟩] {⟨boxcolor⟩} {⟨text⟩}

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```

101 \NewDocumentCommand{\LWR@HTML\fcolorbox}{O{named} m O{named} m +m}{%
102 \LWR@traceinfo{HTML fcolorbox #2 #4}%
103 \begingroup%
104 \LWR@FBcancel%
105 \LWR@forceminwidth{\fboxrule}%
106 \ifthenelse{\equal{#4}{none}}{%
107 {%
108   \InlineClass[%
109     \LWR@borderpadding{\#1}{\#2}%
110   ]{fcolorbox}{\#5}%
111 }%
112 {%
113   \InlineClass[%
114     \LWR@borderpadding{\#1}{\#2} ; %
115     background:\LWR@colorstyle{\#3}{\#4}%
116   ]{fcolorbox}{\#5}%
117 }%
118 \endgroup%
119 }
120
121 \AtBeginDocument{
122 \LWR@formatted{fcolorbox}
123 }

```

\fcolorboxBlock [⟨framemode⟩] {⟨framecolor⟩} [⟨boxmode⟩] {⟨boxcolor⟩} {⟨text⟩}

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```

124 \NewDocumentCommand{\LWR@HTML\fcolorboxBlock}{O{named} m O{named} m +m}{%
125 \LWR@traceinfo{HTML fcolorboxBlock #2 #4}%
126 \begingroup%
127 \LWR@FBcancel%
128 \LWR@forceminwidth{\fboxrule}%
129 \ifthenelse{\equal{#4}{none}}{%
130 {%
131   \begin{BlockClass}[%%
132     \LWR@borderpadding{#1}{#2}%
133   ]\fcolorboxBlock%
134   #5%
135   \end{BlockClass}%
136 }%
137 {%
138   \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
139   \begin{BlockClass}[%%
140     background:\LWR@origpound\LWR@tempcolortwo\ ; %
141     \LWR@borderpadding{#1}{#2}%
142   ]\fcolorboxBlock%
143   #5%
144   \end{BlockClass}%
145 }%
146 \endgroup%
147 \LWR@traceinfo{HTML fcolorboxBlock done}%
148 }%
149
150 \AtBeginDocument{%
151 \LWR@formatted\fcolorboxBlock}%
152 }
```

Creates a framed HTML <div> around its contents.

A print-output version is defined in the **l warp** core: section 82

```

\LWR@subfcollorminipage {<framemode>} {<framecolor>} {<background tag>} {<height>}%
153 \NewDocumentCommand{\LWR@subfcollorminipage}{m m m m}{%
154 \begin{BlockClass}[%%
155 #3%
156 \LWR@borderpadding{#1}{#2} ; %
157 \IfValueT{#4}{height:\LWR@printlength{\LWR@tempheight} ; }%
158 width:\LWR@printlength{\LWR@tempwidth}%
159 ]\fcollorminipage}%
160 }
```

```

Env  fcolorminipage  [<1:framemode>] [<2:framecolor>] [<3:boxmodel>] [<4:boxcolor>] [<5:align>] [<6:height>]
     [<7:inner-align>] [<8:width>]

161 \NewDocumentEnvironment{LWR@HTML@fcolorminipage}{O{named} m 0{named} m 0{c} o o m}
162 {%
163 \LWR@FBcancel%
164 \setlength{\LWR@tempwidth}{#8}%
165 \IfValueT{#6}{\setlength{\LWR@tempheight}{#6}}%
166 \LWR@forceminwidth{\fboxrule}%
167 \convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
168 \ifthenelse{\equal{#4}{none}}{%
169 {\LWR@subfcolorminipage{#1}{#2}{}}{#6}}{%
170 {%
171   \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
172   \LWR@subfcolorminipage{#1}{#2}{background:\LWR@origpound\LWR@tempcolortwo\ ; }{#6}%
173 }%
174 }%
175 {\end{BlockClass}}%
176
177 \AtBeginDocument{%
178 \LWR@formattedenv{fcolorminipage}%
179 }

```

\boxframe {<width>} {<height>} {<depth>}

The depth is added to the height, but the box is not descended below by the depth.
\textcolor is honored.

```

180 \newcommand*{\LWR@HTML@boxframe}[3]{%
181 {%
182 \setlength{\LWR@tempwidth}{#1}%
183 \setlength{\LWR@tempheight}{#2}%
184 \addtolength{\LWR@tempheight}{#3}%
185 \LWR@forceminwidth{\fboxrule}%
186 \LWR@findcurrenttextcolor%
187 \InlineClass[%
188 display:inline-block ; %
189 border:\LWR@printlength{\LWR@atleastonept} solid \LWR@currenttextcolor{} ; %
190 width:\LWR@printlength{\LWR@tempwidth} ; %
191 height:\LWR@printlength{\LWR@tempheight}%
192 ]{boxframe}{}%
193 }%
194 }%
195
196 \LWR@formattedenv{boxframe}

```

§ 427.8 Row colors

```
\rowc@l@rs  [⟨cmds⟩] {⟨startrow⟩} {⟨odd color⟩} {⟨even color⟩}
197 \newcommand*{\LWR@xcolor{tempcolor}{}}{}%
198
199 \def\rowc@l@rs[#1]{#2#3#4}%
200 {
201 \global\rownum=1
202   \global\@rowcolorstrue
203   \ifxempty{#3}{%
204     {\def\@oddrowcolor{\norowcolor}%
205      \convertcolorspec[named]{#3}{HTML}\LWR@xcolor{tempcolor}{}}%
206     \edef\@oddrowcolor{%
207       \csdef{\LWR@xcolor{rowHTMLcolor}}{\LWR@xcolor{tempcolor}}% }%
208     }%
209   }%
210   \ifxempty{#4}{%
211     {\def\@evenrowcolor{\norowcolor}%
212      \convertcolorspec[named]{#4}{HTML}\LWR@xcolor{tempcolor}{}}%
213     \edef\@evenrowcolor{%
214       \csdef{\LWR@xcolor{rowHTMLcolor}}{\LWR@xcolor{tempcolor}}% }%
215     }%
216   }%
217   \if@rowcmd
218     \def\@rowcolors
219     {%
220       #1%
221       \if@rowcolors
222         \noalign{%
223           \relax\ifnum\rownum<#2\norowcolor\else
224             \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi\fi%
225           }%
226           \fi%
227         }%
228       }%
229     }%
230   \else
231     \def\@rowcolors
232     {%
233       \if@rowcolors
234         \ifnum\rownum<#2%
235           \noalign{%
236             \norowcolor
237           }%
238           \else
239             #1%
240           \noalign{%
241             \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi%
242           }%
243         }%
244       }%
245     }%
246   }%
```

```

243           \fi
244           \fi%
245       }%
246   \fi
247   \ignorespaces%
248 }
```

\@norowcolor Turns off color for this row.

```

249 \def\@norowcolor{%
250 \renewcommand{\LWR@xcolorrowHTMLcolor}{()}%
251 }
```

\@rowc@lors Executed at the end of each row.

```

252 \def\@rowc@lors{%
253 %   \noalign{%
254 %     \global\advance\rownum\@ne%
255 %   }%
256   \@rowcolors%
257 }
```

```
258 \end{warpHTML}
```

File 335 lwarf-xellipsis.sty

§ 428 Package **xellipsis**

(Emulates or patches code by DONALD P. GOODMAN III.)

Pkg xellipsis xellipsis is patched for use by lwarf.

When non-zero, each of the spaces is converted to an HTML thin unbreakable space.

for HTML output:

```

1 \LWR@ProvidesPackagePass{xellipsis}

2 \newcommand*{\LWR@xellipsispace}[1]{%
3 \ifdim#1=0pt\else%
4   \ifdim#1<\fontdimen2\font%
5     ,%
6   \else%
7     %
8   \fi%
9 \fi%
10}
11
```

```

12 \def\xelip{%
13 \mbox{%
14   \LWR@xellipsespace{\xelipprebef}%
15   \xelipprechar%
16   \LWR@xellipsespace{\xelippreaft}%
17   \LWR@xellipsespace{\xelipbef}%
18   \xelipchar%
19   \xel@loopi = 1%
20   \loop\ifnum\xelipnum>\xel@loopi%
21     \advance\xel@loopi by1%
22     \LWR@xellipsespace{\xelipgap}%
23     \xelipchar%
24   \repeat%
25   \LWR@xellipsespace{\xelipaft}%
26   \LWR@xellipsespace{\xelippostbef}%
27   \xelippostchar%
28   \LWR@xellipsespace{\xelippostaft}%
29 }%
30 }%

```

File 336 **lwarf-xfrac.sty**§ 429 Package **xfrac**(Emulates or patches code by THE L^AT_EX3 PROJECT.)Pkg **xfrac** Supported by adding **xfrac** instances.**for HTML output:** 1 \LWR@ProvidesPackagePass{xfrac}

⚠ font size In the user's document preamble, **lwarf** should be loaded after font-related setup. During HTML conversion, this font is used by **lwarf** to generate its initial PDF output containing HTML tags, later to be converted by **pdftotext** to a plain text file. While the text may be in any font which **pdftotext** can read, the math is directly converted into SVG images using this same user-selected font. **xfrac** below is set for the Latin Modern (lmr) font. If another font is used, it may be desirable to redefine **\xfracHTMLfontsize** with a different em size.

\sfrac [*<instance>*] [*<num>*] [*<sep>*] [*<denom>*]

A text-mode instance for the default font is provided below. The numerator and denominator formats are adjusted to encase everything in HTML tags. **\scalebox** is made null inside the numerator and denominator, since the HTML tags should not be scaled, and we do not want to introduce additional HTML tags for scaling.

In math mode, which will appear inside a **lateximage**, no adjustments are necessary.

for HTML & PRINT: 2 \begin{warpall}

\xfracHTMLfontsize User-redefinable macro which controls the font size of the fraction.
 3 \newcommand*\{\xfracHTMLfontsize\}{.6em}
 4 \end{warpall}

for HTML output: 5 \begin{warpHTML}

font size A span for a small font, used in the numerator and denominator:

```
6 \newcommand*\{\LWR@htmlsmallfontstart\}%
7 \LWR@htmltagc{span style="font-size:\xfracHTMLfontsize"}%
8 \LWR@nestspan%
9 %
10 }
11
12 \newcommand*\{\LWR@htmlsmallfontend\}%
13 \LWR@htmltagc{/span}%
14 \endLWR@nestspan%
15 }
```

instances Instances of **xfrac** for various font choices:

Produce HTML tags for a small superscript numerator and a small (non-subscript) denominator.

Scaling is turned off so that **pdftotext** correctly reads the result.

```
16 \DeclareInstance{xfrac}{default}{text}{
17 numerator-format = {%
18 \begingroup%
19 \RenewDocumentCommand{\scalebox}{m o m}{##3}%
20 \LWR@htmlsmallfontstart{textsuperscript{#1}\,,\LWR@htmlsmallfontend}%
21 \endgroup%
22 },
23 denominator-format = {%
24 \begingroup%
25 \RenewDocumentCommand{\scalebox}{m o m}{##3}%
26 \LWR@htmlsmallfontstart{}\,,#1\LWR@htmlsmallfontend}%
27 \endgroup%
28 },
```

For **pdftotext**, do not scale the text:

```
29 scaling = false
```

```
30 }
31
32 \DeclareInstance{xfrac}{1mr}{text}{
33 numerator-format = {%
34 \begingroup%
35 \RenewDocumentCommand{\scalebox}{m o m}{##3}%
36 \LWR@htmlsmallfontstart{textsuperscript{#1}\,,\LWR@htmlsmallfontend}%
37 \endgroup%
38 },
39 denominator-format = {%
40 \begingroup%
41 \RenewDocumentCommand{\scalebox}{m o m}{##3}%
42 \LWR@htmlsmallfontstart{}{},#1\LWR@htmlsmallfontend}%
43 \endgroup%
44 },
```

For **pdftotext**, do not scale the text:

```
45 scaling = false
46 }
47
48 \DeclareInstance{xfrac}{1mss}{text}{
49 numerator-format = {%
50 \begingroup%
51 \RenewDocumentCommand{\scalebox}{m o m}{##3}%
52 \LWR@htmlsmallfontstart{textsuperscript{#1}\,,\LWR@htmlsmallfontend}%
53 \endgroup%
54 },
55 denominator-format = {%
56 \begingroup%
57 \RenewDocumentCommand{\scalebox}{m o m}{##3}%
58 \LWR@htmlsmallfontstart{}{},#1\LWR@htmlsmallfontend}%
59 \endgroup%
60 },
```

For **pdftotext**, do not scale the text:

```
61 scaling = false
62 }
63
64 \DeclareInstance{xfrac}{1mtt}{text}{
65 numerator-format = {%
66 \begingroup%
67 \RenewDocumentCommand{\scalebox}{m o m}{##3}%
68 \LWR@htmlsmallfontstart{textsuperscript{#1}\,,\LWR@htmlsmallfontend}%
69 \endgroup%
70 },
71 denominator-format = {%
72 \begingroup%
```

```
73 \RenewDocumentCommand{\scalebox}{m o m}{##3}%
74 \LWR@htmlsmallfontstart{} ,#1\LWR@htmlsmallfontend%
75 \endgroup%
76 },
```

For **pdftotext**, do not scale the text:

```
77 scaling = false
78 }
```

```
79 \end{warpHTML}
```

File 337 **l warp-xltabular.sty**

§ 430 Package **xltabular**

(Emulates or patches code by ROLF NIEPRASCHK, HERBERT VOSS.)

Pkg **xltabular** **xltabular** is emulated by **l warp**.

for HTML output: Relies on **tabularx**.

⚠ **table numbering** At present, an **xltabular** without a caption or with only a **\caption*** may be mis-numbered in HTML, so it may be necessary to place at the end of the table:

```
\warpHTMLonly{\addtocounter{table}{-1}}
```

```
1 \RequirePackage{tabularx}
2
3 \LWR@ProvidesPackageDrop{xltabular}
4
5 \DeclareDocumentEnvironment{xltabular}{o m m}
6 {\longtable{#3}}
7 {\endlongtable}
```

File 338 **l warp-xltxtra.sty**

§ 431 Package **xltxtra**

(Emulates or patches code by WILL ROBERTSON, JONATHAN KEW.)

Pkg **xltxtra** **xltxtra** is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{xltextra}

2 \RequirePackage{realscripts}
3 \RequirePackage{metalogo}
4 \newcommand*\TeX@logo@spacing[6]{}
5
6 \newcommand*{\vfrac}[2]{%
7   \textsuperscript{\#1}/\textsubscript{\#2}%
8 }
9
10 \newcommand\namedglyph[1]{%
11   \tempcnta=\XeTeXglyphindex "#1"\relax
12   \ifnum\tempcnta>0
13     \XeTeXglyph\tempcnta
14   \else
15     \xxt@namedglyph@fallback{\#1}%
16   \fi}
17
18 \newcommand\xxt@namedglyph@fallback[1]{[\#1]}
19
20 \DeclareDocumentCommand{\showhyphens}{m}{}

```

File 339 **lwarf-xmpincl.sty**

§ 432 Package **xmpincl**

(Emulates or patches code by MAARTEN SNEEP.)

Pkg **xmpincl** Emulated.

for HTML output: Discard all options for **lwarf-xmpincl**:

```

1 \LWR@ProvidesPackageDrop{xmpincl}

2 \newcommand*{\includexmp}[1]{}

```

File 340 **lwarf-xpiano.sty**

§ 433 Package **xpiano**

(Emulates or patches code by ENRICO GREGORIO.)

Pkg **xpiano** **xpiano** is patched for use by **lwarf**.

for HTML output:

```

1 \LWR@ProvidesPackagePass{xpiano}

```

```

2 \ExplSyntaxOn
3 \NewDocumentCommand{\LWR@print@keyboard}{ O{}m }
4 {
5 \xpiano_keyboard:nn { #1 } { #2 }
6 }
7
8 \NewDocumentCommand{\LWR@HTML@keyboard}{ O{}m }
9 {
10 \begin{lateximage}*
11   [(-xpiano-\packagediagramname{}: \detokenize\expandafter{#2})]
12   [\detokenize\expandafter{#1}]
13 \xpiano_keyboard:nn { #1 } { #2 }
14 \end{lateximage}
15 }
16 \ExplSyntaxOff
17
18 \LWR@formatted[keyboard]

```

File 341 **lwarf-xtab.sty**

§ 434 Package **xtab**

(Emulates or patches code by PETER WILSON.)

Pkg **xtab** **xtab** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{xtab}

⚠ Misplaced alignment tab character & For `\tablefirsthead`, etc., enclose them as follows:

```

\StartDefiningTabulars
\tablefirsthead
...
\StopDefiningTabulars

```

See section 9.9.

⚠ **latexitimage** **supertabular** and **xtab** are not supported inside a `latexitimage`.

```

2 \newcommand{\LWRXT@firsthead}{}
3
4 \newcommand{\tablefirsthead}[1]{%
5   \long\gdef\LWRXT@firsthead{#1}%
6 }
7
8 \newcommand{\tablehead}[1]{}
9

```

```
10 \newcommand{\tablelasthead}[1]{}
11
12 \newcommand{\notablelasthead}{}%
13
14 \newcommand{\tabletail}[1]{}
15
16 \newcommand{\LWRXT@lasttail}{}%
17
18 \newcommand{\tablelasttail}[1]{%
19     \long\gdef\LWRXT@lasttail{\#1}%
20 }

21 \newcommand{\tablecaption}[2][]{%
22     \long\gdef\LWRXT@caption{%
23         \ifblank{\#1}{%
24             {\caption{\#2}}%
25             {\caption[\#1]{\#2}}%
26         }%
27     }%
28
29 \let\topcaption\tablecaption
30 \let\bottomcaption\tablecaption

31 \newcommand*\LWRXT@caption{}%
32
33 \newcommand*\shrinkheight[1]{}%
34
35 \newcommand*\xentrystretch[1]{}%
36
37 \NewDocumentEnvironment{xtabular}{s o m}%
38 {%
39 \LWR@traceinfo{xtabular}%
40 \table%
41 \LWRXT@caption%
42 \begin{tabular}{#3}%
43 \TabularMacro\ifdefvoid{\LWRXT@firsthead}{%
44 {\LWR@getmynexttoken}%
45 {\expandafter\LWR@getmynexttoken\LWRXT@firsthead}%
46 }%
47 {%
48 \ifdefvoid{\LWRXT@lasttail}{%
49 {}%
50 {%
51 \TabularMacro\ResumeTabular%
52 \LWRXT@lasttail%
53 }%
54 \end{tabular}%
55 \endtable%
56 \LWR@traceinfo{xtabular done}%
}
```

```
57 }  
58  
59 \NewDocumentEnvironment{mpxtabular}{s o m}  
60 {\minipage{\linewidth}\xtabular{#3}}  
61 {\endxtabular\endminipage}
```

File 342 **l warp-xunicode.sty**

§ 435 Package **xunicode**

Pkg xunicode Error if **xunicode** is loaded after **l warp**.

Patch **l warp-xunicode**, but also verify that is was loaded before **l warp**:

for HTML output: 1 \@ifpackageloaded{l warp}{\LWR@loadbefore{xunicode}}{}
2
3 \LWR@ProvidesPackagePass{xunicode}[2011/09/09]

\textcircled becomes a span with a rounded border:

```
4 \newcommand*{\LWR@HTML@textcircled}[1]{%  
5 \InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{#1}%  
6 }  
7  
8 \LWR@formatted{textcircled}
```

File 343 **l warp-xurl.sty**

§ 436 Package **xurl**

Pkg xurl **xurl** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{xurl}

File 344 **l warp-xy.sty**

§ 437 Package **xy**

(Emulates or patches code by KRISTOFFER H. ROSE, ROSS MOORE.)

Pkg xy **xy** is patched for use by **l warp**.

⚠ **\xypolygon** `\xypolygon` must be used inside the `xy` environment, or inside `\xy ... \endxy`.

for HTML output:

```

1 \LWR@ProvidesPackagePass{xy}

2 \AtBeginDocument{
3
4 \preto{\xy}{\begin{ lateximage }[(-xy-\~\packagediagramname)]}
5 \appto{\endxy}{\end{ lateximage }}
6
7 \@ifundefined{xymatrix}{}{
8 \LetLtxMacro{\LWR@origxymatrix}{\xymatrix}
9
10 \renewcommand{\xymatrix}[1]{%
11 \begin{ lateximage }[(-xy- xymatrix \packagediagramname)]
12 \LWR@origxymatrix{#1}
13 \end{ lateximage }
14 }
15 }
16
17 \@ifundefined{xygraph}{}{
18 \LetLtxMacro{\LWR@origxygraph}{\xygraph}
19
20 \renewcommand{\xygraph}[1]{%
21 \begin{ lateximage }[(-xy- xygraph \packagediagramname)]
22 \LWR@origxygraph{#1}
23 \end{ lateximage }
24 }
25 }
26
27 }
```

File 345 **l warp-zwpagelayout.sty**

§ 438 Package **zwpagelayout**

(Emulates or patches code by ŽDENĚK WAGNER.)

Pkg **zwpagelayout** **zwpagelayout** is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{zwpagelayout}

2 \def\noBboxes{}
3 \onlypreamble\noBboxes
4
5 \expandafter\ifx\csname definecolor\endcsname\relax \else
6   \definecolor{cmykblack}{cmyk}{0,0,0,1}
7   \definecolor{grblack}{gray}{0}
```

```
8 \%    \ifzwpl@redefineblack
9 \%        \definecolor{black}{cmyk}{0,0,0,1}\color{black}
10 \%    \fi
11 \definecolor{cmykred}{cmyk}{0,1,1,0}
12 \definecolor{cmykgreen}{cmyk}{1,0,1,0}
13 \definecolor{cmykblue}{cmyk}{1,1,0,0}
14 \definecolor{rgbred}{rgb}{1,0,0}
15 \definecolor{rgbgreen}{rgb}{0,1,0}
16 \definecolor{rgbblue}{rgb}{0,0,1}
17 \%    \ifzwpl@redefinetocmyk
18 \%        \definecolor{red}{cmyk}{0,1,1,0}
19 \%        \definecolor{green}{cmyk}{1,0,1,0}
20 \%        \definecolor{blue}{cmyk}{1,1,0,0}
21 \%    \fi
22 \fi
23
24 \let\OverprintXeTeXExtGState\relax
25
26 \DeclareRobustCommand\SetOverprint{\ignorespaces}
27 \DeclareRobustCommand\SetKnockout{\ignorespaces}
28 \DeclareRobustCommand\textoverprint[1]{{\SetOverprint#1}}
29 \DeclareRobustCommand\textknockout[1]{{\SetKnockout#1}}
30
31 \def\SetPDFminorversion#1{}
32 \onlypreamble\SetPDFminorversion
33
34 \newcommand*\Vcorr{}
35
36 \DeclareRobustCommand\vb[1] []
37 \NewDocumentCommand{\NewOddPage}{* o} {}
38 \NewDocumentCommand{\NewEvenPage}{* o} {}
39 \def\SetOddPageMessage#1{\gdef\ZW@oddwarning}
40 \def\SetEvenPageMessage#1{\gdef\Z@evenwarning}
41 \def\ZW@oddwarning{Empty page inserted}\let\Z@evenwarning\ZW@oddwarning
42
43 \def\clap#1{#1}
44
45 \def\CropFlap{2in}
46 \def\CropSpine{1in}
47 \def\CropXSpine{1in}
48 \def\CropXtrim{.25in}
49 \def\CropYtrim{.25in}
50 \def\UserWidth{5in}
51 \def\UserLeftMargin{1in}
52 \def\UserRightMargin{1in}
53 \def\UserTopMargin{1in}
54 \def\UserBotMargin{1in}
55 \def\thePageNumber{\LWR@origpound\,,\arabic{page}}
56 \ifXeTeX
57 \def\ifcaseZWdriver{\ifcase2}
```

```
58 \else
59 \def\ifcaseZWdriver{\ifcase1}
60 \fi
61 \DeclareRobustCommand\ZWifdriver[2]{}
```

File 346 **l warp-patch-komascript.sty**

§ 439 Package **patch-komascript**

Pkg l warp-patch-komascript Patches for **komascript** classes.

l warp loads this package when **scrbook**, **scrartcl**, or **scrreprt** classes are detected.

Many features are ignored during the **HTML** conversion. The goal is source-level compatibility.

\titlehead, \subject, \captionformat, \figureformat, and \tableformat are not yet emulated.

 Not fully tested! [Please send bug reports!](#)

Some features have not yet been tested. Please contact the author with any bug reports.

for HTML output: 1 \ProvidesPackage{l warp-patch-komascript}

typearea is emulated.

2 \RequirePackage{l warp-typearea}

tocbasic is emulated.

3 \RequirePackage{l warp-tocbasic}

scrextend patches most of the new macros.

4 \RequirePackage{l warp-scrextend}

Indexing macros, simplified for **l warp**:

```
5 \AtBeginDocument{
6
7 \renewcommand*{\idx@heading}{%
8   \idx@@heading{\indexname}%
9 }
10
```

```

11 \renewenvironment{theindex}{%
12   \idx@heading%
13   \index@preamble\par\nobreak
14   \let\item\LWR@indexitem%
15   \let\subitem\LWR@indexsubitem%
16   \let\subsubitem\LWR@indexsubsubitem%
17 }
18 {}
19
20 \renewcommand*\indexspace{}
21
22 }% AtBeginDocument

```

The `\minisec` is placed inside a `<div>` of class `minisec`.

```

23 \renewcommand*{\minisec}[1]{%
24 \begin{BlockClass}{minisec}
25 #1
26 \end{BlockClass}
27 }

```

The part and chapter preambles are placed as plain text just after each heading.

```

28 \@ifundefined{setpartpreamble}{}{%
29 \RenewDocumentCommand{\setpartpreamble}{o o +m}{%
30 \renewcommand{\part@preamble}{#3}%
31 }
32 }
33
34 \@ifundefined{setchapterpreamble}{}{%
35 \RenewDocumentCommand{\setchapterpreamble}{o o +m}{%
36 \renewcommand{\chapter@preamble}{#3}%
37 }
38 }

```

Simple captions are used in all cases.

```

39 \LetLtxMacro{\captionbelow}{\caption
40 \LetLtxMacro{\captionabove}{\caption
41
42 \LetLtxMacro{\captionofbelow}{\captionof
43 \LetLtxMacro{\captionofabove}{\captionof
44
45 \RenewDocumentEnvironment{captionbeside}{o m o o o s}
46 {}
47 }%
48 \IfValueTF{#1}{%
49 {\caption[#1]{#2}}%
50 {\caption{#2}}%

```

```

51 }
52
53 \RenewDocumentEnvironment{captionofbeside}{m o m o o o s}
54 {}
55 {%
56 \IfValueTF{#2}{%
57 {\captionof{#1}{#2}{#3}}{%
58 {\captionof{#1}{#3}}{%
59 }{%
60
61 \RenewDocumentCommand{\setcapindent}{s m}{}{%
62 \renewcommand*{\setcaphanging}{}{%
63 \renewcommand*{\setcapwidth}[2]{}{}{%
64 \renewcommand*{\setcapdynwidth}[2]{}{}{%
65 \RenewDocumentCommand{\setcapmargin}{s o m}{}{%

```

File 347 **lwarf-patch-memoir.sty**

§ 440 Package **patch-memoir**

(Emulates or patches code by PETER WILSON.)

Pkg **lwarf-patch-memoir** Patches for **memoir** class.

⚠ Not fully tested! [Please send bug reports!](#)

lwarf loads this package when the **memoir** class is detected.

While emulating **memoir**, **lwarf** pre-loads a number of packages (section 440.1). This can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading **lwarf**:

```

\documentclass{memoir}
...
\PassOptionsToPackage{options_list}{package_name}
...
\usepackage{lwarf}
...
\usepackage{package_name}

\verbfootnote is not supported.

\newfootnoteseries, etc. are not supported.

```

lwarf loads **pagenote** to perform **memoir**'s pagenote functions, but there are minor differences in **\pagenotesubhead** and related macros.

Poem numbering is not supported.

The `verbatim` environment does not yet support the `memoir` enhancements. It is currently recommended to load and use `fancyvrb` instead.

The `memoir` glossary system is not yet supported by `lwarpmk`. The `glossaries` package may be used instead, but does require the glossary entries be changed from the `memoir` syntax to the `glossaries` syntax.

for HTML output: 1 \ProvidesPackage{l warp-patch-memoir}

§ 440.1 Packages

These are pre-loaded to provide emulation for many of `memoir`'s functions. `memoir` pretends that `abstract`, etc. are already loaded, via its “emulated” package mechanism, but `l warp` is directly loading the “`l warp-`” version of each, which happens to avoid `memoir`'s emulation system.

```

2 \RequirePackage{l warp-abstract}%
3 \RequirePackage{l warp-array}%
4 \RequirePackage{l warp-booktabs}%
5 % \RequirePackage{l warp-ccaption}%
6 \RequirePackage{l warp-changepage}%
7 \RequirePackage{l warp-crop}%
8 \RequirePackage{l warp-dcolumn}%
9 \RequirePackage{l warp-enumerate}%
10 \RequirePackage{l warp-epigraph}%
11 \RequirePackage{l warp-fancyvrb}%
12 \RequirePackage{l warp-footmisc}%
13 \RequirePackage{l warp-framed}%
14 \RequirePackage{l warp-hanging}%
15 \RequirePackage{l warp-makeidx}%
16 \DisemulatePackage{moreverb}%
17 \RequirePackage{l warp-moreverb}%
18 \RequirePackage{l warp-mparhack}%
19 \RequirePackage{l warp-needspace}%
20 \RequirePackage{l warp-nextpage}%
21 \RequirePackage{l warp-pagenote}%
22 \RequirePackage{l warp-parskip}%
23 \RequirePackage{l warp-setspace}%
24 \RequirePackage{l warp-showidx}%
25 \RequirePackage{l warp-subfigure}%
26 \makeindex

```

`subfigure` is emulated via `subfig`, which pre-defines `subfigure` and `subtable`, but `memoir` does not, so they must be tested for here:

```

27 \LetLtxMacro{\LWR@memorignewsubfloat}{\newsubfloat}
28 \RenewDocumentCommand{\newsubfloat}{O{} m}{%

```

```

29     \@ifundefined{c@sub#2}{%
30         \LWR@memorignewsubfloat[#1]{#2}%
31     }{}%
32 }
33
34 \RequirePackage{lwarf-tabularx}%
35 \RequirePackage{lwarf-titling}%
36 % \RequirePackage{lwarf-tocbibind}%
37 \RequirePackage{lwarf-tocloft}%
38 \RequirePackage{lwarf-verse}%

```

§ 440.2 Preliminary setup

Bypass the **memoir** package mechanism:

```
39 \LetLtxMacro{\LWR@orig}{\label{mem@old}\label{}}
```

memoir already set the page size to a default, so it must be forced large for **lwarf**'s use, to avoid tag overflows off the page.

```

40 \setstocksiz{190in}{20in}
41 \setlrmarginsandblock{2in}{2in}{*}
42 \setulmarginsandblock{1in}{1in}{*}

```

§ 440.3 Laying out the page

```

43 \renewcommand*{\stockavi}{}
44 \renewcommand*{\stockav}{}
45 \renewcommand*{\stockaiv}{}
46 \renewcommand*{\stockaiii}{}
47 \renewcommand*{\stockbvi}{}
48 \renewcommand*{\stockbv}{}
49 \renewcommand*{\stockbiv}{}
50 \renewcommand*{\stockbiiii}{}
51 % \renewcommand*{\stockmetriccrownvo}{}% in docs but not in the package
52 \renewcommand*{\stockmlargecrownvo}{}%
53 \renewcommand*{\stockmdemyvo}{}%
54 \renewcommand*{\stockmsmallroyalvo}{}%
55 \renewcommand*{\pageavi}{}
56 \renewcommand*{\pageav}{}
57 \renewcommand*{\pageaiv}{}
58 \renewcommand*{\pageaiii}{}
59 \renewcommand*{\pagebvi}{}
60 \renewcommand*{\pagebv}{}
61 \renewcommand*{\pagebiv}{}
62 \renewcommand*{\pagebiiii}{}
63 % \renewcommand*{\pagemetriccrownvo}{}% in docs but not in the package
64 \renewcommand*{\pagelargecrownvo}{}%
65 \renewcommand*{\pagemdemyvo}{}%

```

```
66 \renewcommand*{\pageasmallroyalvo}{}
67
68 \renewcommand*{\stockdbill}{}
69 \renewcommand*{\stockstatement}{}
70 \renewcommand*{\stockexecutive}{}
71 \renewcommand*{\stockletter}{}
72 \renewcommand*{\stockold}{}
73 \renewcommand*{\stocklegal}{}
74 \renewcommand*{\stockledger}{}
75 \renewcommand*{\stockbroadsheet}{}
76 \renewcommand*{\pagedbill}{}
77 \renewcommand*{\pagestatement}{}
78 \renewcommand*{\pageexecutive}{}
79 \renewcommand*{\pageletter}{}
80 \renewcommand*{\pageold}{}
81 \renewcommand*{\pagelegal}{}
82 \renewcommand*{\pageledger}{}
83 \renewcommand*{\pagebroadsheet}{}
84
85 \renewcommand*{\stockpottvo}{}
86 \renewcommand*{\stockfoolscapvo}{}
87 \renewcommand*{\stockcrownvo}{}
88 \renewcommand*{\stockpostvo}{}
89 \renewcommand*{\stocklargecrownvo}{}
90 \renewcommand*{\stocklargepostvo}{}
91 \renewcommand*{\stocksmalldemyvo}{}
92 \renewcommand*{\stockdemyvo}{}
93 \renewcommand*{\stockmediumvo}{}
94 \renewcommand*{\stocksmallroyalvo}{}
95 \renewcommand*{\stockroyalvo}{}
96 \renewcommand*{\stocksperroyalvo}{}
97 \renewcommand*{\stockimperialvo}{}
98 \renewcommand*{\pagepottvo}{}
99 \renewcommand*{\pagefoolscapvo}{}
100 \renewcommand*{\pagecrownvo}{}
101 \renewcommand*{\pagepostvo}{}
102 \renewcommand*{\pagelargecrownvo}{}
103 \renewcommand*{\pagelargepostvo}{}
104 \renewcommand*{\pagesmalldemyvo}{}
105 \renewcommand*{\pagedemyvo}{}
106 \renewcommand*{\pagemediumvo}{}
107 \renewcommand*{\pagesmallroyalvo}{}
108 \renewcommand*{\pageroyalvo}{}
109 \renewcommand*{\pagesuperroyalvo}{}
110 \renewcommand*{\pageimperialvo}{}
111
112 \renewcommand*{\memfontfamily}{}
113 \renewcommand*{\memfontenc}{}
114 \renewcommand*{\memfontpack}{}
115
```

```
116 \renewcommand*{\anyptfilebase}{}
117 \renewcommand*{\anyptsiz}{10}
118
119 \renewcommand*{\setstocksize}[2]{}
120 \renewcommand*{\settrimmedsize}[3]{}
121 \renewcommand*{\settrims}[2]{}
122
123 % \newlength{\lxvchars}
124 % \setlength{\lxvchars}{305pt}
125 % \newlength{\xlvchars}
126 % \setlength{\xlvchars}{190pt}
127 \renewcommand*{\setxlvchars}[1]{}
128 \renewcommand*{\setlxvchars}[1]{}
129
130 \renewcommand*{\settypeblocksize}[3]{}
131 \renewcommand*{\setlrmargins}[3]{}
132 \renewcommand*{\setlrmarginsandblock}[3]{}
133 \renewcommand*{\setbinding}[1]{}
134 \renewcommand*{\setulmargins}[3]{}
135 \renewcommand*{\setulmarginsandblock}[3]{}
136 \renewcommand*{\setcolsepandrue}[2]{}
137
138 \renewcommand*{\setheadfoot}[2]{}
139 \renewcommand*{\setheaderspaces}[3]{}
140 \renewcommand*{\setmarginnotes}[3]{}
141 \renewcommand*{\setfootins}[2]{}
142 \renewcommand*{\checkandfixthelayout}[1][]{}
143 \renewcommand*{\checkthelayout}[1]{}
144 \renewcommand*{\fixthelayout}{}{}
145 %
146 % \newlength{\stockheight}
147 % \newlength{\trimtop}
148 % \newlength{\trimedge}
149 % \newlength{\stockwidth}
150 % \newlength{\spinemargin}
151 % \newlength{\foremargin}
152 % \newlength{\uppermargin}
153 % \newlength{\headmargin}
154 %
155 \renewcommand*{\typeoutlayout}{}{}
156 \renewcommand*{\typeoutstandardlayout}{}{}
157 \renewcommand*{\settypeoutlayoutunit}[1]{}{}
158 \renewcommand*{\fixpdflayout}{}{}
159 \renewcommand*{\fixdvipslayout}{}{}
160
161 \renewcommand*{\medievalpage}[1][]{}
162 \renewcommand*{\isopage}[1][]{}
163 \renewcommand*{\semiisopage}[1][]{}
164
165 \renewcommand{\setpagebl}[3]{}{}
```

```
166 \renewcommand{\setpageml}[3]{}
167 \renewcommand{\setpagetl}[3]{}
168 \renewcommand{\setpagetm}[3]{}
169 \renewcommand{\setpagetr}[3]{}
170 \renewcommand{\setpagemr}[3]{}
171 \renewcommand{\setpagebr}[3]{}
172 \renewcommand{\setpagebm}[3]{}
173 \renewcommand{\setpagecc}[3]{}
```

§ 440.4 Text and fonts

```
174 \let\miniscule\tiny
175 \let\HUGE\Huge
176
177 \renewcommand*{\abnormalparskip}[1]{}
178 \renewcommand*{\nonzeroparskip}{}{}
179 \renewcommand*{\traditionalparskip}{}{}
180
181 \let\onelinekip\baselineskip
182
183 \let\OnehalfSpacing\onehalfspacing
184 \let\DoubleSpacing\doublespacing
185 \renewcommand*{\setPagenoteSpacing}[1]{}
186 \renewcommand*{\setFloatSpacing}[1]{}
187 \let\SingleSpacing\singlespacing
188 \let\setSingleSpace\SetSinglespace
189 \let\SingleSpace\singlespace
190 \let\endSingleSpace\endsinglespace
191 \let\Spacing\spacing
192 \let\endSpacing\endspacing
193 \let\OnehalfSpace\onehalfspace
194 \let\endOnehalfSpace\endonehalfspace
195 \csletcs{OnehalfSpace*}{onehalfspace}
196 \csletcs{endOnehalfSpace*}{endonehalfspace}
197 \let\DoubleSpace\doublespace
198 \let\endDoubleSpace\enddoublespace
199 \csletcs{DoubleSpace*}{doublespace}
200 \csletcs{endDoubleSpace*}{enddoublespace}
201 \renewcommand*{\setDisplayskipStretch}[1]{}
202 \renewcommand*{\memdisplaystretch}{}{}
203 \renewcommand*{\noDisplayskipStretch}{}{}
204 \renewcommand*{\memdisplayskips}{}{}
205
206 \renewcommand*{\midsloppy}{}{}
207 \renewenvironment*{midsloppypar}{}{}{}
208
209 \renewcommand*{\sloppybottom}{}{}
```

§ 440.5 Titles

```

210 \csletcs{titlingpage*}{titlingpage}
211 \csletcs{endtitlingpage*}{endtitlingpage}
212 \let\titlingpageend\relax
213 \newcommand{\titlingpageend}[2]{}
214 \let\andnext\and
215 \renewcommand*{\thanksmarkstyle}[1]{}
216 \renewcommand{\thanksfootmark}{%
217 \thanksscript{\tamark}%
218 }
219
220 % \newlength{\thanksmarksep}
```

§ 440.6 Abstracts

```

221 \renewcommand*{\abstractcol}{}
222 \renewcommand*{\abstractintoc}{}
223 \renewcommand*{\abstractnum}{}
224 \renewcommand*{\abstractrunin}{}
```

§ 440.7 Document divisions

```

225
226 \def\@apppage{%
227   \part*{\appendixpagename}
228 }
229 \renewcommand\mempreaddappagetotohook{}
230 \renewcommand\mempostaddappagetotohook{}
231
232 \def\@sappage{%
233   \part*{\appendixpagename}
234 }
235
236 \csletcs{frontmatter*}{frontmatter}
237 \csletcs{mainmatter*}{mainmatter}
238 \renewcommand*{\raggedbottomsection}{}
239 \renewcommand*{\normalbottomsection}{}
240 \renewcommand*{\bottomsections skip}{}
241 \renewcommand*{\bottomsectionpenalty}{}
242 \csletcs{appendixpage*}{appendixpage}
243 \renewcommand*{\namedsubappendices}{}
244 \renewcommand*{\unnamedsubappendices}{}
245 \renewcommand*{\setsecnumdepth}[1]{% todo tocsec2
246 \renewcommand*{\maxsecnumdepth}[1]{% todo tocsec2
247 \renewcommand*{\beforebookskip}{}
248 \renewcommand*{\afterbookskip}{}
249 \renewcommand*{\beforepartskip}{}
250 \renewcommand*{\afterpartskip}{}
```

```
251 \renewcommand*{\midbookskip}{}  
252 \renewcommand*{\midpartskip}{}  
253 \renewcommand*{\printbookname}{}  
254 \renewcommand*{\booknamefont}{}  
255 \renewcommand*{\booknamenum}{}  
256 \renewcommand*{\printbooknum}{}  
257 \renewcommand*{\booknumfont}{}  
258 \renewcommand*{\printpartname}{}  
259 \renewcommand*{\partnamefont}{}  
260 \renewcommand*{\partnamenum}{}  
261 \renewcommand*{\printpartnum}{}  
262 \renewcommand*{\partnumfont}{}  
263 \renewcommand*{\printbooktitle}[1]{}  
264 \renewcommand*{\booktitlefont}{}  
265 \renewcommand*{\printparttitle}[1]{}  
266 \renewcommand*{\parttitlefont}{}  
267 \renewcommand*{\bookpageend}{}  
268 \renewcommand*{\bookblankpage}{}  
269 \renewcommand*{\nobookblankpage}{}  
270 \renewcommand*{\partpageend}{}  
271 \renewcommand*{\partblankpage}{}  
272 \renewcommand*{\nopartblankpage}{}  
273 \RenewDocumentCommand{\newleadpage}{s o m m}{}% todo  
274 \RenewDocumentCommand{\renewleadpage}{s o m m}{}% todo  
275 \renewcommand*{\leadpagetoclevel}{chapter}  
276  
277 \renewcommand*{\openright}{}  
278 \renewcommand*{\openleft}{}  
279 \renewcommand*{\openany}{}  
280 \renewcommand*{\clearforchapter}{}  
281 \renewcommand*{\memendofchapterhook}{}  
282 \renewcommand*{\chapterheadstart}{}  
283 % \newlength{\beforechapskip}  
284 \renewcommand*{\afterchapernum}{}  
285 % \newlength{\midchapskip}  
286 \renewcommand*{\afterchaptertitle}{}  
287 % \newlength{\afterchapskip}  
288 \renewcommand*{\printchapername}{}  
289 \renewcommand*{\chapnamefont}{}  
290 \renewcommand*{\chapnamenum}{}  
291 \renewcommand*{\printchapernum}{}  
292 \renewcommand*{\chapnumfont}{}  
293 \renewcommand*{\printchaptertitle}[1]{}  
294 \renewcommand*{\chaptilefont}{}  
295 \renewcommand*{\printchapternonum}{}  
296 \renewcommand*{\indentafterchapter}{}  
297 \renewcommand*{\noindentafterchapter}{}  
298 \renewcommand*{\insertchapterspace}{}  
299  
300 \renewcommand*{\chapterstyle}[1]{}
```

```
301 \renewcommand{\makechapterstyle}[2]{}
302 \renewcommand*{\chapindent}={}
303 \let\chapterprecis\cftchapterprecis
304 \let\chapterprecishere\cftchapterprecishere
305 \let\chapterprecistoc\cftchapterprecistoc
306 \renewcommand*{\precisfont}={}
307 \renewcommand*{\prechapterprecis}={}
308 \renewcommand*{\postchapterprecis}={}
309 \renewcommand{\precistotext}[1]{}
310 \renewcommand*{\precistocfont}={}
311 \renewcommand*{\precistocformat}={}
312 % \newlength{\prechapterprecisshift}
313
314 \renewcommand*{\setbeforesecskip}[1]{}
315 \renewcommand*{\setaftersecskip}[1]{}
316 \renewcommand*{\setsecindent}[1]{}
317 \renewcommand*{\setseheadstyle}[1]{}
318 \renewcommand*{\setbeforesubsecskip}[1]{}
319 \renewcommand*{\setaftersubsecskip}[1]{}
320 \renewcommand*{\setsubsecindent}[1]{}
321 \renewcommand*{\setsubseheadstyle}[1]{}
322 \renewcommand*{\setbeforesubsubsecskip}[1]{}
323 \renewcommand*{\setaftersubsubsecskip}[1]{}
324 \renewcommand*{\setsubsubsecindent}[1]{}
325 \renewcommand*{\setsubsubseheadstyle}[1]{}
326 \renewcommand*{\setbeforeparaskip}[1]{}
327 \renewcommand*{\setafterparaskip}[1]{}
328 \renewcommand*{\setparaindent}[1]{}
329 \renewcommand*{\setparaheadstyle}[1]{}
330 \renewcommand*{\setbeforesubparaskip}[1]{}
331 \renewcommand*{\setaftersubparaskip}[1]{}
332 \renewcommand*{\setsubparaindent}[1]{}
333 \renewcommand*{\setsubparaheadstyle}[1]{}
334 \renewcommand{\@hangfrom}[1]{#1}
335 \renewcommand{\sethangfrom}[1]{}
336 \renewcommand{\setsecnumformat}[1]{}
337
338 \renewcommand*{\hangsecnum}={}
339 \renewcommand*{\defaultsecnum}={}
340
341 \renewcommand*{\sechook}={}
342 \renewcommand{\setsechook}[1]{}
343 \renewcommand*{\subsechook}={}
344 \renewcommand{\setsubsechook}[1]{}
345 \renewcommand*{\subsubsechook}={}
346 \renewcommand{\setsubsubsechook}[1]{}
347 \renewcommand*{\parahook}={}
348 \renewcommand{\setparahook}[1]{}
349 \renewcommand*{\subparahook}={}
350 \renewcommand{\setsubparahook}[1]{}
```

```
351
352 \RenewDocumentCommand{\plainbreak}{s m}{\begin{center}~\end{center}}
353
354 \RenewDocumentCommand{\fancybreak}{s +m}{%
355 \begin{center}#2\end{center}%
356 }
357
358 \RenewDocumentCommand{\plainfancybreak}{s m m +m}{%
359 \begin{center}#4\end{center}%
360 }
361
362 \RenewDocumentCommand{\pfbreak}{s}{%
363 \begin{center}
364 \pfbreakdisplay
365 \end{center}
366 }
367
368 % \newlength{\pfbreakskip}
369 \renewcommand{\pfbreakdisplay}{*\quad*\quad*}
370
371 \renewcommand{\makeheadstyles}[2]{}
372 \renewcommand*{\headstyles}[1]{}
```

§ 440.8 Pagination and headers

```
373 \renewcommand*{\savepagenumber}{}
374 \renewcommand*{\restorepagenumber}{}
375 \renewcommand*{\uppercaseheads}{}
376 \renewcommand*{\nouppercaseheads}{}
377
378 \renewcommand*{\bookpagemark}[1]{}
379 \renewcommand*{\partmark}[1]{}
380 \renewcommand*{\bibmark}{}
381 \renewcommand*{\indexmark}{}
382 \renewcommand*{\glossarymark}{}
383
384 \LWR@origpagestyle{empty}
385 \renewcommand*{\ps@empty}{}
386 \renewcommand*{\makepagestyle}[1]{}
387 \renewcommand*{\emptypshook}{}
388 % \renewcommand*{\empty@oddhead}{}
389 % \renewcommand*{\empty@oddfoot}{}
390 % \renewcommand*{\empty@evenhead}{}
391 % \renewcommand*{\empty@evenfoot}{}
392 \renewcommand*{@oddhead}{}
393 \renewcommand*{@oddfoot}{}
394 \renewcommand*{@evenhead}{}
395 \renewcommand*{@evenfoot}{}
396 \renewcommand*{\aliaspagestyle}[2]{}
```

```

397 \renewcommand*\{\copypagestyle}{2} {}
398
399 \renewcommand*\{\makeevenhead}{4} {}
400 \renewcommand*\{\makeoddhead}{4} {}
401 \renewcommand*\{\makeevenfoot}{4} {}
402 \renewcommand*\{\makeoddfoot}{4} {}
403 \renewcommand*\{\makerunningwidth}{3} {}
404 % \newlength{\headwidth}
405 \renewcommand*\{\makeheadrule}{3} {}
406 \renewcommand*\{\makefootrule}{3} {}
407 \renewcommand*\{\makeheadfootruleprefix}{3} {}
408 % \newlength{\normalrulethickness}
409 % \setlength{\normalrulethickness}{.4pt}
410 % \newlength{\footruleheight}
411 % \newlength{\footruleskip}
412 \renewcommand*\{\makeheadposition}{5} {}
413 \renewcommand{\makepsmarks}{2} {}
414 \renewcommand*\{\makeheadfootstrut}{3} {}
415
416 \renewcommand{\createplainmark}{3} {}
417 \renewcommand{\memUHead}{1} {}
418 \renewcommand{\createmark}{5} {}
419 \renewcommand*\{\clearplainmark}{1} {}
420 \renewcommand*\{\clearmark}{1} {}
421 \renewcommand{\addtopsmarks}{3} {}
422 \renewcommand{\ifonlyfloats}{2} {#2}
423 \renewcommand*\{\mergepagefloatstyle}{3} {}
424
425 \renewcommand*\{\framepichead}{}
426 \renewcommand*\{\framepictextfoot}{}
427 \renewcommand*\{\framepichook}{}
428 \renewcommand*\{\showheadfootlocoff}{}
429 \renewcommand*\{\showtextblocklocoff}{}

```

§ 440.9 Paragraphs and lists

```

430 \renewcommand{\hangfrom}{1} {#1}
431 \let\centerfloat\centering
432 \renewcommand*\{\raggedyright}{1} [] {}
433 % \newlength{\ragrparindent}
434 \renewcommand{\sourceatright}{2} [] {\attribution{#2}}
435 \let\memorigdbs\LWR@endofline
436 \let\memorigpar\par
437 \let\atcentercr\LWR@endofline
438
439 \renewcommand*\{\linenottooshort}{1} [] {}
440 \renewcommand*\{\russianpar}{}
441 \renewcommand*\{\lastlinerulefill}{}
442 \renewcommand*\{\lastlineparrule}{}

```

```

443 \renewcommand*{\justlastraggedleft}{}
444 \renewcommand*{\raggedrightthenleft}{}
445 \renewcommand*{\leftcenterright}{}
446
447 \renewcommand{\leftspringright}[4]{%
448 \begin{minipage}{\#1\linewidth}\#3\end{minipage}\quad\%
449 \begin{minipage}{\#2\linewidth}\begin{flushright}\#4\end{flushright}\end{minipage}%
450 }
451
452 \renewenvironment*{blockdescription}
453 {\LWR@descriptionstart\LWR@origdescription}
454 {\enddescription}
455 \renewcommand*{\blockdescriptionlabel}[1]{\textbf{\#1}}
456 \renewenvironment*{labelled}[1]{\begin{description}}{\end{description}}
457 \renewenvironment*{flexlabelled}[6]{\begin{description}}{\end{description}}
458 \renewcommand*{\tightlists}{}
459 \renewcommand*{\defaultlists}{}
460 \RenewDocumentCommand{\firmlists}{s}{}
461 \renewcommand*{\firmlist}{}
462 \renewcommand*{\tightlist}{}
463 \renewcommand*{\zerotrivseps}{}
464 \renewcommand*{\savetrvseps}{}
465 \renewcommand*{\restoretrvseps}{}

```

§ 440.10 Contents lists

```

466 \csletcs{tableofcontents*}{tableofcontents}
467 \csletcs{listoffigures*}{listoffigures}
468 \csletcs{listoftables*}{listoftables}
469 \renewenvironment{KeepFromToc}{}{}
470 \renewcommand*{\onecoltocetc}{}
471 \renewcommand*{\twocoltocetc}{}
472 \renewcommand*{\ensureonecol}{}
473 \renewcommand*{\restorefromonecol}{}
474 \renewcommand*{\doccoltocetc}{}
475 \renewcommand*{\maxtocdepth}[1]{\% tocsec2}
476 \renewcommand*{\settocdepth}[1]{\% tocsec2}
477
478 \renewcommand{\tocheadstart}{}
479 \renewcommand{\printtoctitle}[1]{}
480 \renewcommand{\tocmark}{}
481 \renewcommand{\aftertoctitle}{}
482 \renewcommand{\lofheadstart}{}
483 \renewcommand{\printloftitle}[1]{}
484 \renewcommand{\lofmark}{}
485 \renewcommand{\afterloftitle}{}
486 \renewcommand{\lotheadstart}{}
487 \renewcommand{\printlottitle}[1]{}
488 \renewcommand{\lotmark}{}

```

```
489 \renewcommand{\afterlottitle}{}  
490  
491 \renewcommand*{\setpnumwidth}[1]{}  
492 \renewcommand*{\setrmarg}[1]{}  
493 \renewcommand*{\cftbookbreak}{}  
494 \renewcommand*{\cftpbreak}{}  
495 \renewcommand*{\cftchapterbreak}{}  
  
496 % \newlength{\cftbeforebookskip}  
497 % \newlength{\cftbookindent}  
498 % \newlength{\cftbooknumwidth}  
499 \renewcommand*{\cftbookfont}{}  
500 \renewcommand*{\cftbookname}{}  
501 \renewcommand*{\cftbookpresnum}{}  
502 \renewcommand*{\cftbookaftersnum}{}  
503 \renewcommand*{\cftbookaftersnumb}{}  
504 \renewcommand*{\cftbookleader}{}  
505 \renewcommand*{\cftbookdotsep}{1}  
506 \renewcommand*{\cftbookpagefont}{}  
507 \renewcommand*{\cftbookafterpnum}{}  
508 \renewcommand*{\cftbookformatpnum}[1]{}  
509 \renewcommand*{\cftbookformatpnumhook}[1]{}
```

Part is already defined by **tocloft**.

```
510 % \newlength{\cftbeforechapterskip}  
511 % \newlength{\cftchapterindent}  
512 % \newlength{\cftchapternumwidth}  
513 \renewcommand*{\cftchapterfont}{}  
514 \renewcommand*{\cftchaptername}{}  
515 \renewcommand*{\cftchapterpresnum}{}  
516 \renewcommand*{\cftchapteraftersnum}{}  
517 \renewcommand*{\cftchapteraftersnumb}{}  
518 \renewcommand*{\cftchapterleader}{}  
519 \renewcommand*{\cftchapterdotsep}{1}  
520 \renewcommand*{\cftchapterpagefont}{}  
521 \renewcommand*{\cftchapterafterpnum}{}  
522 \renewcommand*{\cftchapterformatpnum}[1]{}  
523 \renewcommand*{\cftchapterformatpnumhook}[1]{}  
  
524 % \newlength{\cftbeforesections skip}  
525 % \newlength{\cftsectionindent}  
526 % \newlength{\cftsectionnumwidth}  
527 \renewcommand*{\cftsectionfont}{}  
528 \renewcommand*{\cftsectionname}{}  
529 \renewcommand*{\cftsectionpresnum}{}  
530 \renewcommand*{\cftsectionaftersnum}{}  
531 \renewcommand*{\cftsectionaftersnumb}{}  
532 \renewcommand*{\cftsectionleader}{}  
533 \renewcommand*{\cftsectiondotsep}{1}
```

```
534 \renewcommand*{\cftsectionpagefont}{}
535 \renewcommand*{\cftsectionafterpnum}{}
536 \renewcommand*{\cftsectionformatpnum}[1]{}
537 \renewcommand*{\cftsectionformatpnumhook}[1]{}

538 % \newlength{\cftbeforesubsections skip}
539 % \newlength{\cftsubsectionindent}
540 % \newlength{\cftsubsectionnumwidth}
541 \renewcommand*{\cftsubsectionfont}{}
542 \renewcommand*{\cftsubsectionname}{}
543 \renewcommand*{\cftsubsectionpresnum}{}
544 \renewcommand*{\cftsubsectionaftersnum}{}
545 \renewcommand*{\cftsubsectionaftersnumb}{}
546 \renewcommand*{\cftsubsectionleader}{}
547 \renewcommand*{\cftsubsectiondotsep}{1}
548 \renewcommand*{\cftsubsectionpagefont}{}
549 \renewcommand*{\cftsubsectionafterpnum}{}
550 \renewcommand*{\cftsubsectionformatpnum}[1]{}
551 \renewcommand*{\cftsubsectionformatpnumhook}[1]{}

552 % \newlength{\cftbeforesubsubsections skip}
553 % \newlength{\cftsubsubsectionindent}
554 % \newlength{\cftsubsubsectionnumwidth}
555 \renewcommand*{\cftsubsubsectionfont}{}
556 \renewcommand*{\cftsubsubsectionname}{}
557 \renewcommand*{\cftsubsubsectionpresnum}{}
558 \renewcommand*{\cftsubsubsectionaftersnum}{}
559 \renewcommand*{\cftsubsubsectionaftersnumb}{}
560 \renewcommand*{\cftsubsubsectionleader}{}
561 \renewcommand*{\cftsubsubsectiondotsep}{1}
562 \renewcommand*{\cftsubsubsectionpagefont}{}
563 \renewcommand*{\cftsubsubsectionafterpnum}{}
564 \renewcommand*{\cftsubsubsectionformatpnum}[1]{}
565 \renewcommand*{\cftsubsubsectionformatpnumhook}[1]{}

566 % \newlength{\cftbeforeparagraphskip}
567 % \newlength{\cftparagraphindent}
568 % \newlength{\cftparagraphnumwidth}
569 \renewcommand*{\cftparagraphfont}{}
570 \renewcommand*{\cftparagraphname}{}
571 \renewcommand*{\cftparagraphpresnum}{}
572 \renewcommand*{\cftparagraphaftersnum}{}
573 \renewcommand*{\cftparagraphaftersnumb}{}
574 \renewcommand*{\cftparagraphleader}{}
575 \renewcommand*{\cftparagraphdotsep}{1}
576 \renewcommand*{\cftparagraphpagefont}{}
577 \renewcommand*{\cftparagraphafterpnum}{}
578 \renewcommand*{\cftparagraphformatpnum}[1]{}
579 \renewcommand*{\cftparagraphformatpnumhook}[1]{}
```

```
580 % \newlength{\cftbeforesubparagraphskip}
581 % \newlength{\cftsubparagraphindent}
582 % \newlength{\cftsubparagraphnumwidth}
583 \renewcommand*{\cftsubparagraphfont}={}
584 \renewcommand*{\cftsubparagraphname}={}
585 \renewcommand*{\cftsubparagraphpresnum}={}
586 \renewcommand*{\cftsubparagraphaftersnum}={}
587 \renewcommand*{\cftsubparagraphaftersnumb}={}
588 \renewcommand*{\cftsubparagraphleader}={}
589 \renewcommand*{\cftsubparagraphdotsep}{1}
590 \renewcommand*{\cftsubparagraphpagefont}={}
591 \renewcommand*{\cftsubparagraphafterpnum}={}
592 \renewcommand*{\cftsubparagraphformatpnum}[1]{}
593 \renewcommand*{\cftsubparagraphformatpnumhook}[1] {}

594 % \newlength{\cftbeforefigureskip}
595 % \newlength{\cftfigureindent}
596 % \newlength{\cftfigurenumwidth}
597 \renewcommand*{\cftfigurefont}={}
598 \renewcommand*{\cftfigurename}={}
599 \renewcommand*{\cftfigurepresnum}={}
600 \renewcommand*{\cftfigureaftersnum}={}
601 \renewcommand*{\cftfigureaftersnumb}={}
602 \renewcommand*{\cftfigureleader}={}
603 \renewcommand*{\cftfiguredotsep}{1}
604 \renewcommand*{\cftfigurepagefont}={}
605 \renewcommand*{\cftfigureafterpnum}={}
606 \renewcommand*{\cftfigureformatpnum}[1]{}
607 \renewcommand*{\cftfigureformatpnumhook}[1] {}

608 % \newlength{\cftbeforesubfigureskip}
609 % \newlength{\cftsubfigureindent}
610 % \newlength{\cftsubfigurenumwidth}
611 \newcommand*{\cftsubfigurefont}={}
612 \newcommand*{\cftsubfigurename}={}
613 \newcommand*{\cftsubfigurepresnum}={}
614 \newcommand*{\cftsubfigureaftersnum}={}
615 \newcommand*{\cftsubfigureaftersnumb}={}
616 \newcommand*{\cftsubfigureleader}={}
617 \newcommand*{\cftsubfiguredotsep}{1}
618 \newcommand*{\cftsubfigurepagefont}={}
619 \newcommand*{\cftsubfigureafterpnum}={}
620 \newcommand*{\cftsubfigureformatpnum}[1]{}
621 \newcommand*{\cftsubfigureformatpnumhook}[1] {}

622 % \newlength{\cftbeforetablesip}
623 % \newlength{\cfttableindent}
624 % \newlength{\cfttablenumwidth}
625 \renewcommand*{\cfttablefont}={}
626 \renewcommand*{\cfttablename}={}
```

```
627 \renewcommand*{\cfttablepresnum}{}
628 \renewcommand*{\cfttableaftersnum}{}
629 \renewcommand*{\cfttableaftersnumb}{}
630 \renewcommand*{\cfttableleader}{}
631 \renewcommand*{\cfttabledotsep}{1}
632 \renewcommand*{\cfttablepagefont}{}
633 \renewcommand*{\cfttableafterpnum}{}
634 \renewcommand*{\cfttableformatpnum}[1]{}
635 \renewcommand*{\cfttableformatpnumhook}[1]{}

636 % \newlength{\cftbeforesubtableskip}
637 % \newlength{\cftsubtableindent}
638 % \newlength{\cftsubtablenumwidth}
639 \newcommand*{\cftsubtablefont}{}
640 \newcommand*{\cftsubtablename}{}
641 \newcommand*{\cftsubtablepresnum}{}
642 \newcommand*{\cftsubtableaftersnum}{}
643 \newcommand*{\cftsubtableaftersnumb}{}
644 \newcommand*{\cftsubtableleader}{}
645 \newcommand*{\cftsubtabledotsep}{1}
646 \newcommand*{\cftsubtablepagefont}{}
647 \newcommand*{\cftsubtableafterpnum}{}
648 \newcommand*{\cftsubtableformatpnum}[1]{}
649 \newcommand*{\cftsubtableformatpnumhook}[1]{}

650 \renewcommand*{\booknumberline}[1]{}
651 \renewcommand*{\partnumberline}[1]{}
652 \renewcommand*{\chapternumberline}[1]{}
653 \renewcommand*{\numberlinehook}[1]{}
654 % \renewcommand*{\cftwhatismyname}{}%
655 \renewcommand*{\booknumberlinehook}[1]{}
656 \renewcommand*{\partnumberlinehook}[1]{}
657 \renewcommand*{\chapternumberlinehook}[1]{}
658 \renewcommand{\numberlinebox}[2]{}
659 \renewcommand{\booknumberlinebox}[2]{}
660 \renewcommand{\partnumberlinebox}[2]{}
661 \renewcommand{\chapternumberlinebox}[2]{}
662 %
663 % \newlength{\cftparskip}
664 \renewcommand*{\cftpagenumbersoff}[1]{}
665 \renewcommand*{\cftpagenumberson}[1]{}
666 \renewcommand*{\cftlocalchange}[3]{}
667 \renewcommand*{\cftaddtitleline}[4]{}
668 \renewcommand*{\cftaddnumtitleline}[4]{}
669 \renewcommand{\cftinsertcode}[2]{}
670 \renewcommand{\cftinserthook}[2]{}
671 \renewcommand{\settocpreprocessor}[2]{}
672 \DeclareRobustCommand{\cftpagenumbersoff}[1]{}
673 \DeclareRobustCommand{\cftpagenumberson}[1]{}
```

§ 440.11 Floats and captions

```
\newfloat  [<1: within>] {<2: type>} {<3: ext>} {<4: capname>}
674 \RenewDocumentCommand{\newfloat}{o m m m}{%
675 \IfValueTF{#1}{%
676 {\DeclareFloatingEnvironment[fileext=#3,within=#1,name={#4}]{#2}}{%
677 {\DeclareFloatingEnvironment[fileext=#3,name={#4}]{#2}}}{%
678 \cslet{listof#2s}\relax%
679 \cslet{listof#2es}\relax%
680 }

\newlistof  [<within>] {<type>} {<ext>} {<listofname>}
Emulated through the \newfloat mechanism. Note that memoir uses a different
syntax than tocloft for the name.
681 \RenewDocumentCommand{\newlistof}{o m m m}{%
682 {%
683 \IfValueTF{#1}{%
684 {\newlistentry[#1]{#2}{#3}{0}}{%
685 {\newlistentry[#2]{#3}{0}}{%
686 \cft@namedef{ext@#2}{#3}{%
687 \cft@ifundefined{c@#3depth}{\newcounter{#3depth}}{}{%
688 \cft@setcounter{#3depth}{1}}{%
689 \cft@namedef{#3mark}{}}{%
690 \cft@namedef{#2}{\listof{#2}{#4}}{%
691 \cft@namedef{@cftmake#3title}{}}{%
692 \cft@ifundefined{cftbefore#3titleskip}{%
693     \expandafter\newlength\cftbefore#3titleskip\endcsname{%
694     \expandafter\newlength\cftafter#3titleskip\endcsname{%
695 }}}{%
696 \cft@namedef{cft#3titlefont}{}}{%
697 \cft@namedef{cftafter#3title}{}}{%
698 \cft@namedef{cft#3prehook}{}}{%
699 \cft@namedef{cft#3posthook}{}}{%
700 }

701 \renewcommand{\setfloatadjustment}[2]{}
```

Borrowed from the **l warp** version of **keyfloat**:

```
702 \NewDocumentEnvironment{KFLTmemoir@marginfloat}{O{-1.2ex} m}{%
703 {%
704 \LWR@BlockClassWP{float:right; width:2in; margin:10pt}{\marginblock}{%
705 \captionsetup{type=#2}}{%
706 }}
```

```
707 {%
708 \endLWR@BlockClassWP%
709 }
710
711 \DeclareDocumentEnvironment{marginfigure}{o}
712   {\begin{KFLTmemoir@marginfloat}{figure}}
713   {\end{KFLTmemoir@marginfloat}}
714
715 \DeclareDocumentEnvironment{margintable}{o}
716   {\begin{KFLTmemoir@marginfloat}{table}}
717   {\end{KFLTmemoir@marginfloat}}
718 \renewcommand{\setmarginfloatcaptionadjustment}[2]{}
719 \renewcommand{\setmpjustification}[2]{}
720 \renewcommand*{\mpjustification}{}%
721 \renewcommand*{\setfloatlocations}[2]{}
722 \DeclareDocumentCommand{\suppressfloats}{o}{}%
723 \renewcommand*{\FloatBlock}{}%
724 \renewcommand*{\FloatBlockAllowAbove}{}%
725 \renewcommand*{\FloatBlockAllowBelow}{}%
726 \renewcommand*{\setFloatBlockFor}{}%
727
728 \renewcommand{\captiontitlefinal}[1]{}%
729
730 \renewcommand{\fleitable}{\tablename}%
731 \renewcommand{\flegfigure}{\figurename}%
732 \renewcommand{\flegtoctable}{}%
733 \renewcommand{\flegtocfigure}{}%
734
735
736 \renewcommand{\subcaption}[2][]{%
737 \ifblank{#1}{\subfloat[#2]}{\subfloat[#1][#2]}%}
738 }
739
740 \renewcommand{\contsubcaption}{\ContinuedFloat\subcaption}%
741
742 \LetLtxMacro{\subcaptionref}{\subref}%
743
744 \renewcommand*{\tightsubcaptions}{}%
745 \renewcommand*{\loosesubcaptions}{}%
746
747 \renewcommand*{\subcaptionsize}[1]{}%
748 \renewcommand*{\subcaptionlabelfont}[1]{}%
749 \renewcommand*{\subcaptionfont}[1]{}%
750 \renewcommand*{\subcaptionstyle}[1]{}%
751
752 \renewcommand*{\hangsubcaption}{}%
753 \renewcommand*{\shortsubcaption}{}%
754 \renewcommand*{\normalsubcaption}{}%
```

```
755
756 \RenewDocumentEnvironment{sidecaption}{o m o}
757 {}
758 {
759 \IfValueTF{#1}{\caption[#1]{#2}}{\caption{#2}}%
760 \IfValueT{#3}{\label{#3}}%
761 }
762 %
763 % \newlength{\sidecapwidth}
764 % \newlength{\sidecapsep}
765 \renewcommand*\setsidecaps[2] {}
766 \renewcommand*\sidecapmargin[1] {}
767 % \newif\ifscapmargleft
768 \scapmargleftfalse
769 \renewcommand*\setsidecappos[1] {}
770
771 \RenewDocumentEnvironment{sidecontcaption}{m o}
772 {}
773 %
774 \ContinuedFloat%
775 \caption{#1}%
```

Without `\@capttype`, the section is referred to instead.

```
776 \IfValueT{#2}{\label[\@capttype]{#2}}%
777 }
```

`\sidenamedlegend` does not appear to use the TOC argument.

```
778 \renewenvironment{sidenamedlegend}[2] [] {
779 \begin{center}
780 \@nameuse{@capttype name}\CaptionSeparator#2
781 \end{center}
782 }
783 {}
784
785 \renewenvironment{sidelegend}[1]
786 {\begin{center}
787 #1
788
789 \end{center}}
790 {\end{center}}
791
792 \renewcommand*\sidecapstyle{}
793 \renewcommand*\overridescapmargin[1]{}
794 % \newlength{\sidecappraise}
795 \renewcommand*\sidecapfloatwidth{\linewidth}
796
797 \LetLtxMacro\ctabular\tabular
```

```
798 \LetLtxMacro\endctabular\endtabular
799
800 \renewcommand{\autorows}[5][]{%
801 #5
802 }
803
804 \renewcommand{\autocols}[5][]{%
805 #5
806 }
```

§ 440.12 Page notes

```
807 \renewcommand*{\feetabovefloat}{}%
808 \renewcommand*{\feetbelowfloat}{}%
809 \renewcommand*{\feetatbottom}{}%
810
811 \renewcommand*{\verbfootnote}[2][]{%
812 \PackageError{l warp,memoir}%
813 {Verbatim footnotes are not yet supported by l warp.}%
814 {This may be improved some day.}%
815 }
816
817 \renewcommand*{\plainfootnotes}{}%
818 \renewcommand*{\twocolumnfootnotes}{}%
819 \renewcommand*{\threecolumnfootnotes}{}%
820 \renewcommand*{\paragraphfootnotes}{}%
821 \renewcommand*{\footfudgefiddle}{}%
822
823 \renewcommand*{\newfootnoteseries}[1]{%
824 \PackageError{l warp,memoir}%
825 {Memoir footnote series are not yet supported by l warp.}%
826 {This may be improved some day.}%
827 }
828
829 \renewcommand*{\plainfootstyle}[1]{}%
830 \renewcommand*{\twocolumnfootstyle}[1]{}%
831 \renewcommand*{\threecolumnfootstyle}[1]{}%
832 \renewcommand*{\paragraphfootstyle}[1]{}%
833
834 \renewcommand*{\footfootmark}{}%
835 \renewcommand*{\footmarkstyle}[1]{}%
836
837 % \newlength{\footmarkwidth}
838 % \newlength{\footmarksep}
839 % \newlength{\footparindent}
840
841 \renewcommand*{\foottextfont}{}%
842
843 \renewcommand*{\marginparmargin}[1]{}%
```

```
844 \renewcommand*{\sideparmargin}[1]{}
845
846 \LetLtxMacro{\sidepar}{\marginpar}
847 \renewcommand*{\sideparfont}={}
848 \renewcommand*{\sideparform}={}
849 \LWR@providelength{\sideparvshift}
850
851 \renewcommand*{\parnopar}={}
852
853 \renewcommand{\sidebar}[1]{\begin{quote}#1\end{quote}}
854 \renewcommand*{\sidebarmargin}[1]{}
855 \renewcommand*{\sidebarfont}={}
856 \renewcommand*{\sidebarform}={}
857 % \newlength{\sidebarhsep}
858 % \newlength{\sidebarvsep}
859 % \newlength{\sidebarwidth}
860 % \newlength{\sidebartopsep}
861 \renewcommand{\setsidebarheight}[1]{}
862 \renewcommand*{\setsidebars}[6]{}
863 \renewcommand*{\footnotesatfoot}={}
864 \renewcommand*{\footnotesinmargin}={}
865
866 \LetLtxMacro{\sidefootnote}{\footnote}
867 \LetLtxMacro{\sidefootnotemark}{\footnotemark}
868 \LetLtxMacro{\sidefootnotetext}{\footnotetext}
869
870 \renewcommand*{\sidefootmargin}[1]{}
871 % \newlength{\sidefoothsep}
872 % \newlength{\sidefootvsep}
873 % \newlength{\sidefootwidth}
874 % \newlength{\sidefootadjust}
875 % \newlength{\sidefootheight}
876 \renewcommand*{\setsidefootheight}[1]{}
877 % \renewcommand*{\sidefootfont}{}% in docs but not in the package
878 \renewcommand*{\setsidefeet}[6]{}
879 \renewcommand*{\sidefootmarkstyle}[1]{}
880 \renewcommand*{\sidefoottextfont}={}
881 \renewcommand*{\sidefootform}={}
882
883 \renewcommand*{\continuousnotenums}{\pncntopttrue}% from pagenote
884 \renewcommand*{\notepageref}={}
885 \renewcommand*{\prenotetext}={}
886 \renewcommand*{\postnotetext}={}
887 \renewcommand*{\idtextinnotes}[1]{}
888 \renewcommand*{\printpageinnotes}[1]{}
889 \renewcommand*{\printpageinnoteshyperref}[1]{}
890 \renewcommand*{\foottopagenote}={}
891 \renewcommand*{\pagetofootnote}={}
```

§ 440.13 Decorative text

```

892 \renewcommand*\{\epigraphposition\}[1]{}
893 \renewcommand*\{\epigraphtextposition\}[1]{}
894 \renewcommand*\{\epigraphsourceposition\}[1]{}
895 \renewcommand*\{\epigraphfontsize\}[1]{}
896 \renewcommand*\{\epigraphforheader\}[2][]{}
897 \renewcommand*\{\epigraphpicture\}{}

```

§ 440.14 Poetry

```

898 \renewcommand*\{\vinphantom\}{}
899 \renewcommand*\{\vleftofline\}[1]{#1}
900 % \let\linenumberfrequency\poemlines
901 % \renewcommand*\{\linenumberfont\}[1]{}
902
903 \DeclareDocumentCommand{\PoemTitle}{s o o m}{%
904 \IfValueTF{#2}{%
905 {\poemtitle[#2]{#4}}{%
906 {\poemtitle{#4}}{%
907 }{%
908
909 \renewcommand*\{\NumberPoemTitle\}{}
910 \renewcommand*\{\PlainPoemTitle\}{}
911 \renewcommand*\{\poemtitlepstyle\}{}
912 \renewcommand*\{\poemtitlestarstyle\}[1]{}
913 \renewcommand*\{\poemtitlestarpstyle\}{}
914 \renewcommand*\{\PoemTitleheadstart\}{}
915 \renewcommand*\{\printPoemTitlenonum\}{}
916 \renewcommand*\{\printPoemTitlenum\}{}
917 \renewcommand*\{\afterPoemTitlenum\}{}
918 \renewcommand*\{\printPoemTitletitle\}[1]{}
919 \renewcommand*\{\afterPoemTitle\}{}
920 \newlength{\midpoemtitleskip}
921 \renewcommand*\{\PoemTitlenumfont\}{}
922 \renewcommand*\{\PoemTitlefont\}{}

```

§ 440.15 Boxes, verbatims and files

```

923 \renewenvironment{qframe}{\framed}{\endframed}
924 \renewenvironment{qshade}{\shaded}{\endshaded}

```

Use the **comment** package:

```

925 \renewcommand*\{\commentsoff\}[1]{\includecomment{#1}}
926 \renewcommand*\{\commentson\}[1]{\excludecomment{#1}}
927 \LetLtxMacro\renewcomment\commentson
928
929 \renewcommand*\{\setverbatimfont\}[1]{}

```

```

930 \renewcommand*{\tabson}[1]{}
931 \renewcommand*{\tabsoff}{}{}
932 \renewcommand*{\wrappingon}{}{}
933 \renewcommand*{\wrappingoff}{}{}
934 \renewcommand*{\verbatimindent}{}{}
935 \renewcommand*{\verbatimbreakchar}[1]{}{}

936 \DefineVerbatimEnvironment{fboxverbatim}{Verbatim}{frame=single}

```

`boxedverbatim` is already defined by `moreverb`. `boxedverbatim*` does not appear to work at all, even in a minimal print `memoir` document.

```

937 \renewcommand*{\b vbox}{}{}
938 \renewcommand*{\b topandtail}{}{}
939 \renewcommand*{\b sides}{}{}
940 \renewcommand*{\nob vbox}{}{}
941 % \newlength\b vboxsep
942 \renewcommand*{\btoprulehook}{}{}
943 \renewcommand*{\btopmidhook}{}{}
944 \renewcommand*{\bendrulehook}{}{}
945 \renewcommand*{\bleftsidehook}{}{}
946 \renewcommand*{\brightsidehook}{}{}
947 \renewcommand*{\bperpage}{}{true}
948 \renewcommand*{\bperpage}{}{false}
949 \renewcommand{\btopofpage}[1]{}{}
950 \renewcommand{\bendofpage}[1]{}{}
951 \renewcommand*{\linenumberfrequency}[1]{}{}
952 \renewcommand*{\resetb linenum}{}{}
953 \renewcommand*{\setb linenums}[2]{}{}
954 \renewcommand*{\linenumberfont}[1]{}{}
955 \renewcommand*{\bnumbersinside}{}{}
956 \renewcommand*{\bnumbersoutside}{}{}

```

§ 440.16 Cross referencing

```

957 \renewcommand*{\fref}[1]{\cref{#1}}
958 \renewcommand*{\tref}[1]{\cref{#1}}
959 \renewcommand*{\pref}[1]{\cpageref{#1}}
960 \renewcommand*{\Aref}[1]{\cref{#1}}
961 \renewcommand*{\Bref}[1]{\cref{#1}}
962 \renewcommand*{\Pref}[1]{\cref{#1}}
963 \renewcommand*{\Sref}[1]{\cref{#1}}
964 \renewcommand*{\figurerefname}{Figure}
965 \renewcommand*{\tablerefname}{Table}
966 \renewcommand*{\pagerefname}{page}
967 \renewcommand*{\bookrefname}{Book~}
968 \renewcommand*{\partrefname}{Part~}
969 \renewcommand*{\chapterrefname}{Chapter~}
970 \renewcommand*{\sectionrefname}{\S}

```

```

971 \renewcommand*{\appendixrefname}{Appendix~}
972 \LetLtxMacro\titleoref\nameref
973 \renewcommand*{\headnameref}={}
974 \renewcommand*{\tocnameref}={}
975
976 \providecounter{LWR@currenttitle}
977
978 \renewcommand*{\currenttitle}{%
979     \addtocounter{LWR@currenttitle}{1}%
980     \label{currenttitle}\arabic{LWR@currenttitle}}%
981     \nameref{currenttitle}\arabic{LWR@currenttitle}}%
982 }
983
984 \renewcommand*{\theTitleReference}[2]{}
985 \renewcommand*{\namerefon}{}
986 \renewcommand*{\namerefoff}{}

```

§ 440.17 Back matter

Redefined to write the LWR@autoindex counter instead of page. Note that **memoir** has two versions, depending on the use of **hyperref**.

```

987 \AtBeginDocument{
988
989 \def\@wrindexhyp#1|||\{%
990     \addtocounter{LWR@autoindex}{1}%
991     \LWR@new@label{LWRindex}\arabic{LWR@autoindex}}%
992 %     \ifshowindexmark\@showidx{#1}\fi
993     \protected@write\@auxout{}{%
994     \string\@wrindexm@m{\@idxfile}{#1}\{\arabic{LWR@autoindex}}}}%
995     \endgroup
996     \@esphack}%

```

\specialindex behaves like a regular \index, pointing to where \specialindex is used. If \specialindex is used inside a figure or table after the \caption, then the hyperlink will be given the name of that particular figure or table.

```

997 \def\@wrspindexhyp#1|||\{%
998     \addtocounter{LWR@autoindex}{1}%
999     \LWR@new@label{LWRindex}\arabic{LWR@autoindex}}%
1000 %     \ifshowindexmark\@showidx{#1}\fi
1001     \protected@write\@auxout{}{%
1002     \string\@wrindexm@m{\@idxfile}{#1}\{@nameuse{the\@sptheadidx}}\%
1003 %         \string\@wrindexm@m{\@idxfile}{#1}\{\arabic{LWR@autoindex}}\%
1004     \string\@wrindexm@m{\@idxfile}{#1}\{\arabic{LWR@autoindex}}\%
1005     }%
1006     \endgroup
1007     \@esphack}%
1008

```

```
1009 }% \AtBeginDocument
```

Patched to use _html filename and \BaseJobname:

```
1010 \catcode`\_=12%
1011 \renewcommand*\makeindex[1][\BaseJobname]{%
1012   \if@filesw
1013     \def\gindex{\@bsphack%
1014       \ifnextchar [{\@index}{\@index[\BaseJobname]}}%
1015     \def\specialindex{\@bsphack\@spindex}%
1016     \makememindexhook
1017     \expandafter\newwrite\csname #1@idxfile\endcsname
1018     \expandafter\immediate\openout \csname #1@idxfile\endcsname #1_html.idx\relax
1019     \typeout{Writing index file #1_html.idx }%
1020   \fi}
1021 \catcode`\_=8%
```

Patched to use _html filename and \BaseJobname. This will later be patched by the l warp core.

```
1022 \catcode`\_=12%
1023 \renewcommand{\printindex}[1][\BaseJobname]{\@input@{#1_html.ind}}
1024 \catcode`\_=8%
1025 \DeclareDocumentCommand{\newblock}{}{%
1026 %
1027 \renewcommand*\showindexmarks{}%
1028 \renewcommand*\hideindexmarks{}%
1029 %
1030 \renewcommand*\xindyindex{}%
```

§ 440.18 Miscellaneous

```
1031 \renewcommand*\changemarks{}
1032 \renewcommand*\nochangemarks{}
1033 \renewcommand*\added[1]{}
1034 \renewcommand*\deleted[1]{}
1035 \renewcommand*\changed[1]{}
1036 %
1037 \renewcommand*\showtrimsoff(){}
1038 \renewcommand*\showtrimson(){}
1039 \renewcommand*\trimXmarks(){}
1040 \renewcommand*\trimLmarks(){}
1041 \renewcommand*\trimFrame(){}
1042 \renewcommand*\trimNone(){}
1043 \renewcommand*\trimmarkscolor{}
1044 \renewcommand*\trimmarks(){}
1045 \renewcommand*\tmarktl(){}
1046 \renewcommand*\tmarktr{}
```

```

1047 \renewcommand*{\tmarkbr}{}
1048 \renewcommand*{\tmarkbl}{}
1049 \renewcommand*{\tmarktm}{}
1050 \renewcommand*{\tmarkmr}{}
1051 \renewcommand*{\tmarkbm}{}
1052 \renewcommand*{\tmarkml}{}
1053 \renewcommand*{\trimmark}{}
1054 \renewcommand*{\quarkmarks}{}
1055 \renewcommand*{\registrationColour}[1]{}
1056
1057 \renewcommand*{\leavespergathering}[1]{}
1058
1059 \renewcommand*{\noprelistbreak}{}
1060
1061 \renewcommand*{\cleartorecto}{}
1062 \renewcommand*{\cleartoverso}{}
1063
1064 \renewenvironment{vplace}[1][]{\{}{\}}

```

§ 440.19 Ccaption emulation

```

1065 \renewcommand*{\captiondelim}[1]{\renewcommand*{\CaptionSeparator}{\#1}}
1066 \renewcommand*{\captionnamefont}[1]{}
1067 \renewcommand*{\captiontitlefont}[1]{}
1068 \renewcommand*{\flushleftright}{}
1069 \renewcommand*{\centerlastline}{}
1070 \renewcommand*{\captionstyle}[2][]{}
1071 \DeclareDocumentCommand{\captionwidth}{m}{}
1072 \renewcommand*{\changecaptionwidth}{}
1073 \renewcommand*{\normalcaptionwidth}{}
1074 \renewcommand*{\hangcaption}{}
1075 \renewcommand*{\indentcaption}[1]{}
1076 \renewcommand*{\normalcaption}{}
1077 \renewcommand{\precaption}[1]{}
1078 \renewcommand{\postcaption}[1]{}
1079 \renewcommand{\midbicaption}[1]{}
1080 \renewcommand{\contcaption}[1]{%
1081 % \ContinuedFloat%
1082 % \caption{\#1}%
1083 \begin{LWR@figcaption}%
1084 % later becomes \caption*
1085 % \nameuse{@capttype name} \thechapter.\the\value{@capttype}\CaptionSeparator \#1
1086 \end{LWR@figcaption}
1087 \newlength{\abovelegendskip}
1088 \setlength{\abovelegendskip}{0.5\baselineskip}
1089 \newlength{\belowlegendskip}
1090 \setlength{\belowlegendskip}{\abovelegendskip}

```

The extra \\ here forces a
 in HTML when \legend is used in a \marginpar.

```
1091 \renewcommand{\legend}[1]{\begin{center}#1\\ \end{center}}
```

```
1092
```

```
1093 \renewcommand{\namedlegend}[2][]{
```

```
1094 \begin{center}
```

```
1095 @nameuse{fleg@\capttype}\CaptionSeparator#2\\
```

```
1096 \end{center}
```

```
1097 @nameuse{flegtoc@\capttype}{#1}
```

```
1098 }
```

```
1099
```

```
1100 \renewcommand{\newfixedcaption}[3][\caption]{%
```

```
1101   \renewcommand{#2}{\def@\capttype{#3}#1}}
```

```
1102 \renewcommand{\renewfixedcaption}[3][\caption]{%
```

```
1103   \renewcommand{#2}{\def@\capttype{#3}#1}}
```

```
1104 \renewcommand{\providedeffixedcaption}[3][\caption]{%
```

```
1105   \providecommand{#2}{\def@\capttype{#3}#1}}
```

```
1106
```

```
1107 \renewcommand{\bitwonumcaption}[6][]{%
```

```
1108 \ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
```

```
1109 \addtocounter{@capttype}{-1}%
```

```
1110 \begingroup%
```

```
1111 \csdef{@capttype name}{#4}%
```

```
1112 \ifblank{#5}{\caption{#6}}{\caption[#5]{#6}}%
```

```
1113 \endgroup%
```

```
1114 \ifblank{#1}{}{\label{#1}}%
```

```
1115 }
```

```
1116
```

```
1117 \LetLtxMacro\bionenumcaption\bitwonumcaption% todo
```

```
1118
```

```
1119 \renewcommand{\bicaption}[5][]{%
```

```
1120 \ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
```

```
1121 \begin{LWR@figcaption}% later becomes \caption*
```

```
1122 #4 \thechapter.\the\value{@capttype}\CaptionSeparator #5
```

```
1123 \end{LWR@figcaption}
```

```
1124 \ifblank{#1}{}{\label{#1}}%
```

```
1125 }
```

```
1126
```

```
1127 \renewcommand{\bicontcaption}[3]{%
```

```
1128 \contcaption{#1}%
```

```
1129 \begingroup%
```

```
1130 \csdef{@capttype name}{#2}%
```

```
1131 \contcaption{#3}%
```

```
1132 \endgroup%
```

```
1133 }
```

```
1134 % only in ccaption, not in memoir:
```

```
1135 % \LetLtxMacro\longbitwonumcaption\bitwonumcaption%
```

```
1136 % \LetLtxMacro\longbionenumcaption\bitwonumcaption%
```

```
1137 % \LetLtxMacro\longbicaption\bicaption%
```

```
1138
1139 \RenewDocumentCommand{\subtop}{O{} O{} m}{%
1140 \subfloat[#1][#2][#3]%
1141 }
1142
1143 \RenewDocumentCommand{\subbottom}{O{} O{} m}{%
1144 \subfloat[#1][#2][#3]%
1145 }
1146
1147 \renewcommand{\contsubtop}{%
1148 \ContinuedFloat\addtocounter{@captive}{1}%
1149 \subtop}
1150
1151 \renewcommand{\contsubbottom}{%
1152 \ContinuedFloat\addtocounter{@captive}{1}%
1153 \subbottom}
1154
1155 \renewcommand{\subconcluded}{}
1156
1157 \let\subfigure\subbottom
1158 \let\subtable\subtop
1159
1160 \let\contsubtable\contsubtop
1161 \let\contsubfigure\contsubbottom

1162 \newcommand{\newfloatentry}[4][\empty]{TODO: newfloatentry}
1163 \newcommand{\newfloatlist}[5][\empty]{TODO: newfloatlist}
1164 \newcommand{\newfloatenv}[4][\empty]{TODO: newfloatenv}
1165 \DeclareRobustCommand{\newfloatpagesoff}[1]{}
1166 \DeclareRobustCommand{\newfloatpageson}[1]{}
1167 \newcommand{\setnewfloatindents}[3]{}
```

§ 440.20 Final patchwork

```
1168 \newlistof{tableofcontents}{toc}{\contentsname}
1169 \newlistof{listoffigures}{lof}{\listfigurename}
1170 \newlistof{listoftables}{lot}{\listtablename}
```

Change History

For the most recent changes, see page 1017.

v0.10	General: 2016/03/08 Initial version . . 1	Docs: Trademarks section. 585
v0.11	General: 2016/03/11 1	Docs: Troubleshooting cross-references. 187
	Added section: Operating-System portability. 198	Test Suite: Assigned cleveref name for Test Float. 1
	Added section: Selecting the operating system. 120	Test Suite: Floatrow 1
	Test Suite: MS-WINDOWS in README.txt 1	
	Test Suite: limages and index in README.txt 1	
v0.12	\LWR@newhtmlfile: Bugfix: TOC with numbered files. 356	General: 2016/04/06 1
	General: 2016/03/14 1	Added. 716
	Global: Uses \p@{type} in float captions. 1	Ampersand (&): Fixed handling when passed as an argument. . 410
	Test Suite: Sub-figures 1	Docs: Added warning icons for items needing special attention. 194
v0.13	\CaptionSeparator: Fix for newer babel package. 483	Docs: Clarify print/HTML output. 120
	\LWR@LwarpStart: \up and \fup . . 373	Docs: Moved the supported features table to the introduction. 73
	General: 2016/03/24 1	Files: lwarp_formal.css added. 1
	Fix dollar-redefined bug for newer package. 898	Fix: steps counter 716
	Removed package: subfig 1	Fixed & handling. 714
	Test Suite: Ordinals, Subcaption . . 1	Test Suite: test_suite_formal.css file added. 1
v0.14	\LWR@htmlsectionfilename: Fix: Links to home page. 319	General: 2016/04/11 1
	General: 2016/03/31 1	\titlingpage: Improved print-output spacing. 381
	\floatrow: Added. 711	xfrac: Adjusted for the use of any font: 954
	Docs: Commands for a successful HTML conversion. 123	Added XeLaTeX, LuaLaTeX support. 195
	Docs: Commands into a warpprint environment. 121	Docs: Font and UTF-8 support. . 105
	Docs: Newclude limitations. . . . 167	Docs: Moved location of \usepackage{lwarp}. 108
	Docs: Table: Cross-referencing data structures. 467	Docs: Text not converting. 187
	Docs: Table: Float data structures. 479	Lwarp no longer selects fonts. 105, 216
		Removed package: suffix 1
		Test Suite: Improved titlingpage. 381
		Test Suite: Lwarp no longer selects fonts. 1
		Test Suite: Supports XeLaTeX, LuaLaTeX. 1

v0.17	\LWR@htmlsectionfilename: Fix: Links when entire doc is one HTML page. 319	v0.19	\HTMLfilename: Docs: Escape filename underscores. 318
	General: 2016/04/14 1		\HomeHTMLfilename: Docs: Escape filename underscores. 318
	mdframed: Added. 787		\LWR@l warpStart: Enabled \\ equal to \newline. 372
	Test Suite: Fix: Print-version front-matter page numbers. 1		\LWR@doequation: MATHJAX support. 520
	Test Suite: Mdframed 1		\LWR@doubledollar: MATHJAX support. 514
v0.18	\LWR@includegraphicsb: Add: svgz file extension. 736		\LWR@filestart: l warp_mathjax.txt loaded. 369
	em, ex, %, px dimensions preserved. 736		\LWR@minipagestartpars: Surpresses paragraph tags between minipages. 574
	Fix: \linewidth, \textwidth, \textheight inside a minipage. 736		\LWR@subsingle dollar: MATHJAX support. 508
	Improved HTML output linebreaks. 736		\LateximageFontSizeName: Add: User-adjustable math/lateximage font size. 531
	\LWR@myshorttoc: Reorganize \HomeHTMLfilename logic. 488		\hspace: Fix: \hspace length computations. 575
	\LWR@newhtmlfile: sideroc after title, improving responsive design. 355		\minipagewidth: Added: No width tag for the next minipage in HTML. 555
	\LWR@requesttoc: Reorganize \HomeHTMLfilename logic. 375		\warpHTMLonly: Added. 206
	\LWR@subhyperref: Improved HTML output linebreaks. 475		\warpprintonly: Replaces \rowprintedonly. 206
	\LWR@subhyperrefclass: Improved HTML output linebreaks. 476		\xfracHTMLfontsize: Added. 954
	\LWR@subinlineimage: Surpress extra space. 477		General: 2016/06/08 1
	\hspace: \hspace supported. 575		MATHJAX support added. 518, 524, 526
	General: 2016/05/19 1		multirow: Added optional args. 806
	File: l warp.css: Improved TOC outline display. 1		Adapts to tikz version. 898
	Files: l warp.css and l warp_formal.css: Improved responsive design. 1		Avoids MATHJAX. 507
	Microtype disabled during HTML generation 217		cleveref: Loaded \AtEndPreamble. 551
	PDF Unicode input characters. 196		CSS for table note item. 897
	Test Suite: Verse package 1		Docs: Math options. 108
	lateximage: pdfcrop: --hires added. 535		Docs: Table: Cross-referencing data structures, updated. 467
	Reorganize \HomeHTMLfilename logic. 535		File: l warp.css: tnoteitemheader added. 1
	Surpress extra space. 535		File: l warp_mathjax.txt added. 1
	verse: Supports verse, memoir packages. 933		Introduction: MATHJAX support mentioned. 71
	minipage: Fix: \linewidth, \textwidth, \textheight inside a minipage. 556		Options: mathsvg and mathjax 201
			Supports colored \rule. 945
			titlesp: null \pagestyle and \thispagestyle for HTML. 899

v0.20	
\BlockClassSingle: Renamed from "LWR@htmldivclassline".	332
\HTMLDescription: Added	
\NewHTMLdescription.	
(Renamed in v0.30.)	343
\HTMLFilename: No longer escape underscores.	318
\HomeHTMLFilename: No longer escape underscores.	318
\InlineClass: Renamed from "inlineclass".	332
\LWR@LwarpStart: Fix: math cross references.	373
\LWR@closeparagraph: \unskip extra spaces.	336
No break tags in the start/end of a tabular.	336
\LWR@endofline: Fix: \\	573
\LWR@filestart: Adds meta description.	369
\LWR@htmldivclass: Added optional style.	330
\LWR@htmlelementclass: Added optional style.	329
\LWR@htmlsectionfilename: HTMLFilename: removed additional trailing ' - ', and may be empty.	319
Sections called "Index" or "index" have an underscore prepended to their filenames if no prefix.	319
\LWR@includegraphicsb: Fix:	
\linewidth in a floatrow.	736
Fix: Expands filename.	736
\LWR@longtabledatacaptiontag: Fix: Pars in captions.	450
\LWR@section: Combined higher-level sections together into files.	361
\LWR@setOSWindows: Auto-detects operating system.	200
\LWR@subhtmlelementclass: Factored code.	329
\SetHTMLFileName: Add: Control file numbers.	319
\cpagerefFor: User-redefinable word for page references.	552
\dotfill: Inserts an ellipsis.	573
\hfill: Inserts a \quad.	573
\hrulefill: Inserts a short rule.	573
\hspace: Add: Supports HTML thin breakable space.	575
\hyperindexref: Print mode provided in case hyperref not used.	498
\pageref: Added.	474
\tracingl warp: Added.	227
General: 2017/02/09	1
\afterpage: Added.	595
\alltt: Added.	600
\bookmark: Added.	626
\caption and \subcaption supported.	1
\cleveref and referencing patches:	
Applied \AfterEndPreamble.	551
\draftwatermark: Added.	678
\eso-pic: Added.	688
\everypage: Added.	689
\extramarks: Added.	689
\fancyhdr: Added.	696
\float: Improved float caption type handling.	708
\hyperref: Additional user macros.	749
\keyfloat: Added.	765
\letterspace: User-interface emulated.	768
\listings: Added.	772
\ltcaption: Added.	780
\l warp-newproject: Added.	240
\microtype: User-interface emulated.	800
\needspace: Added.	811
\nowidow: Added.	814
\placeins: Added.	837
\ragged2e: Added.	843
\setspace: Improved support.	860
\textpos: Added.	891
\titlesp: Added.	899
\titlsec: Added.	903
\titletoc: Added.	905
\titling: Improved compatibility.	907
\tocloft: Added.	915
\wallpaper: Added.	938
\wrapfig: Added.	940
Added @, <, > columns.	404
Added single-expansion data arrays.	314
Code factored into independent \l warp_html files.	585

Docs: Examples for generating	
HTML file names.	117
Docs: Improved index.	1
Enhanced titling support.	380
File: <i>l warp.css</i> : Minor fixes for	
validation.	1
File: <i>l warpmk</i> used to compile	
print, HTML, indexes, and	
latexitimages.	1
Fix: \ linewidth in a floatrow.	714
Moved sidebar and example code	
to test suite.	1
Page geometry set to 6in wide with	
large margins.	217
Parallel versions of aux files for	
print/HTML.	1
Removed reliance on make, grep,	
gawk.	1
Tabular: \unskip extra spaces.	404
Test Suite: HTML meta	
descriptions.	1
<i>verbatim</i> : Added.	392
<i>BlockClass</i> : Added optional style.	331
Renamed from "blockclass".	331
<i>LWR@nestspan</i> : Fix: Minipages inside	
a span.	326
v0.21	
\i LWR@L warpStart: Changed	
latexitimages to a .txt file.	372
\i LWR@filestart: Skip title if not	
given.	369
\i LWR@newhtmlfile: Skip title if not	
given.	355
\i marginpar: Fixed source listing.	349
\i marginparBlock: Fixed source	
listing.	349
General: 2017/02/23	1
fontenc : Added.	719
fontspec : Added.	720
inputenc : Added.	764
newclude : Added.	811
newunicodechar : Added.	811
<i>l warpmk</i> : Fix: <i>l warpmk</i> again for	
WINDOWS.	292
<i>l warpmk</i> : Fix: <i>l warpmk l images</i>	
for WINDOWS.	292
<i>l warpmk</i> : Fix: <i>l warpmk</i> uses	
latexitimages text file instead of	
shell script.	292
v0.22	
Add: Errors for misplaced	
packages.	207
Docs: Added internet class.	78
Docs: Added TeX2page, GladTeX.	78
Docs: Installing on WINDOWS.	85
File: <i>l warp_tutorial.txt</i> added.	89
v0.23	
\i LWR@parseDcolumn: Added tabular	
D column.	420
\i LWR@parsebangcolumn: Added	
tabular ! column.	415
\i LWR@parsetablecols: Unknown	
table column types become 1.	
Added tabular D, !, X columns.	422
\i LWR@printmccoldata: Added	
tabular D, !, and X columns.	444
General: 2017/03/02	1
abstract : Added.	587
changepage : Added.	638
dcolumn : Added.	674
ftnright : Added.	726
geometry : Nullified commands.	728
indentfirst : Added.	762
layout : Added.	767
l escape : Added.	779
mcaption : Added.	786
nameref : Added.	809
nextpage : Added.	812
parskip : Added.	830
showkeys : Added.	862
sidecap : Added.	862
tabularx : Added.	886
varioref : Supported.	131
verse : Added.	932
v0.24	
\i LWR@parsetablecols: Fix for vert	
bar column type.	422
\i LWR@printmccoldata: Fix for vert	
bar column type.	444
General: 2017/03/02	1
v0.24	
\i LWR@htmlfileref: Fix: Index links	
while \ tracingl warp.	470
\i hspace: Add: \hspace \ fill	
converts to 2em.	575
\i hypertocfloat: List of floats	
responds to lofdepth,	
lotdepth.	494
General: 2017/03/15	1
floatrow : Support for subfig	711

subfig: Added.	877
tikz: For tikz v3.0.0 or later, auto-loads tikz babel library if necessary.	898
Docs: Filename underscore.	112, 126
Fix for inline images.	898
No longer preloads subcaption ; conflicted with subfig	219
picture: Fix for inline images. . .	554
v0.25	
\LWR@loadnever: Added the ability to prevent conflicting packages.	208
\addcontentsline: Handles theorems.	486
General: 2016/03/22	1
amsthm: Added.	607
ccaption: Prevented.	637
ellipsis: Added.	679
emptypage: Added.	680
framed: Added.	724
lips: Added.	772
mdframed: Help avoid hyphenation.	789
ntheorem: Added.	814
showidx: Added.	862
theorem: Added.	891
Basic L ^A T _E X theorems: improved css.	392
Docs: Adds credits for patched code.	1
Docs: Testing lwarp	185
Fix: Allows XE ^L T _E X and Lua ^L T _E X to preload graphics and graphicx. .	209
v0.26	
General: 2017/03/31	1
lwarp.css: Improved responsive marginpar and marginblock. .	248
cutwin: Added.	673
endnotes: Added.	682
floatflt: Added.	710
footmisc: Added.	720
footnotehyper: Added.	722
footnote: Added.	721
marginfix: Added.	785
marginnote: Added.	786
mparhack: Added.	804
pagenote: Supported as-is. . . .	828
sidenotes: Added.	863
Docs: Improved MiK ^T E _X install instructions.	83, 85
Dollar span avoided in a lateximage.	507
Footnotes now are L^AT_EX boxes instead of pagenotes.	343
lateximage: Labels track page numbers of lateximages.	535
Print mode now uses a minipage of \linewidth.	535
picture: Fix for \makebox in picture.	554
v0.27	
\LWR@footnotetext: Fix for table footnote par tags.	345
General: 2017/04/04	1
lettrine: Added.	768
microtype: Fix with Xe ^L T _E X, Lua ^L T _E X.	800
soul: Added.	871
ulem: Added.	928
Docs: Installing utilities for MACOS.	87
Docs: Limitations of saveboxes. .	126
Page geometry modified to reduce line overflow.	217
v0.28	
\@rindex: Improved indexing. . . .	497
\HTMLAuthor: Added \HTMLauthor. (Renamed in v0.30.)	342
\LWR@LwarpEnd: If FormatEPUB or FormatWP, no bottom nav. . .	375
\LWR@LwarpStart: FormatWordProcessor forces single-file output.	372
\LWR@filestart: Adds HTML meta author.	369
\LWR@forcenewpage: Forces new PDF page before major environments.	323
\LWR@htmlcomment: Breaks ligatures in HTML comments.	329
\LWR@includegraphicsb: Adapts to graphics syntax.	736
\LWR@newhtmlfile: If FormatEPUB or FormatWP: skips headers, footers, nav.	355
\LWR@parsetablecols: Added L, C, R, J column types.	422
\LWR@startref: Removed space. .	472
\chapter: If EPUB, prints footnotes before each section.	367

\hyperindexref: Improved indexing.	498	\HTMLPageTop: Renamed from \SetPageTop.	341
\textup: Fixed span class.	566	General: 2017/04/29	1
General: 2017/04/14	1	l warp-newproject removed, and combined with l warp .	240
glossaries: Added.	729	l warpmk : Add: <code>xdyfile</code> configuration option.	292
graphics: Added.	731	l warpmk : Fix: <code>xindy</code> and <code>texindy</code> adjusted for <code>pdflatex</code> , <code>xelatex</code> and <code>lualatex</code> .	292
tabularx: Fix for optional pos.	886	l warpmk : Fix: <code>xindy</code> now used for print index generation with <code>latemmk</code> .	292
tabulary: Added.	886	l warpmk : language now used for both index and glossary generation.	292
l warpmk : Add: <code>printglossary</code> and <code>htmlglossary</code> commands.	292	File: <code>l warp_html.xdy</code> renamed to <code>l warp.xdy</code> .	288
Added boolean FormatEPUB.	233	Fix: <code>*.css</code> files only written in print mode.	248
Added boolean FormatWP.	233	Fix: <code>l warp.xdy</code> only written in print mode.	288
Added boolean		Fix: <code>l warp_mathjax.txt</code> : Only written in print mode.	290
HTMLDebugComments.	227	Option <code>l warpmklang</code> changed to <code>IndexLanguage</code> .	202
Added boolean HTMLMarkFloats, changed to WPMarkFloats as of v0.42.	233	Option <code>OSWindows</code> replaces macro <code>\warpOSwindows</code> .	203
Docs: Modfyng l warpmk and index processing.	186	Option <code>xdyFilename</code> added.	202
File: <code>l warp_mathjax.txt</code> : Updated CDN repository.	290	Option <code>latemmk</code> replaces macro <code>\UseLatexmk</code> .	204
Forced oneside to maintain large right margin.	217	Options <code>HomeHTMLFilename</code> and <code>HTMLFilename</code> replace macros <code>\HomeHTMLFilename</code> and <code>\HTMLFilename</code> .	203
v0.29		v0.31	
\LWR@includegraphicsb: Fix: Error when no optional arguments.	736	General: 2017/05/15	1
General: 2017/04/15	1	keyfloat : Improved compatibility.	765
*.l warpmkconf: Add: language option for config files.	248	v0.32	
l warpmk.conf: Add: language option for config files.	247	\RequirePackage: Fix: Ignores blanks in package list.	222
l warpmk : Add: language option for config files.	292	General: 2016/06/09	1
Add: <code>l warpmklang</code> option for l warp .	202	glossaries : Prevent error with <code>\glo@name</code> not defined.	499
Docs: Using a glossary	101	l warpmk : Fix: <code>io.lines()</code> changed to <code>file:lines()</code> due to <code>luatex</code> changes.	292
v0.30		v0.33	
\CSSFilename: Renamed from \NewCSS.	341	\HTMLAuthor: Fix: Provides empty default author if none given.	342
\HTMLAuthor: Renamed from \HTMLauthor.	342		
\HTMLDescription: Renamed from \NewHTMLdescription.	343		
\HTMLFirstPageTop: Renamed from \SetFirstPageTop.	341		
\HTMLLanguage: Renamed from \MetaLanguage.	369		
\HTMLPageBottom: Renamed from \SetPageBottom.	341		

\LWR@loadbefore: Fix: No	
\PackageError if already	
loaded.	208
\LWR@parseatcolumn: Fix: Column	
alignment with leftmost @.	415
\LWR@tabledatasinglecolumntag:	
Fix: Macros in tabular could	
cause extra data cell.	429
\LWR@vspace: Add: \vspace	
nullified.	577
\StartDefiningTabulars: Add:	
Avoids error: Misplaced	
alignment tab character &.	315
General: 2017/07/10	1
<code>amsmath</code> : Removed <code>fleqn</code>	
option.	601
<code>fancyhdr</code> : Fix: Optional args for	
\lhead, etc.	696
Add: Tabular at and bang columns	
now have their own HTML	
columns.	404
cleveref: Fix: Loaded	
\AtEndPreamble.	551
Fix: Incorrectly-inline math	
environments.	526
New handling of & to localize	
catcode changes.	404
v0.34	
\@fnsymbol: Text symbols instead of	
math.	383
\InlineClass: Moved optional	
argument in front of mandatory.	332
\LWR@htmldivclass: Moved	
optional argument in front of	
mandatory.	330
\LWR@htmlelementclass: Moved	
optional argument in front of	
mandatory.	329
\LWR@htmlelementclassline:	
Moved optional argument in	
front of mandatory.	330
\LWR@htmlspanclass: Moved	
optional argument in front of	
mandatory.	327
\LWR@nullfonts: Improved font	
control.	567
\LWR@restoreorigformatting:	
<code>booktabs</code> : Works inside	
<code>lateximage</code>	500
Improved font control.	500
\LWR@subhtmelementclass:	
Moved optional argument in	
front of mandatory.	329
\LWR@tabledatacolumntag:	
<code>booktabs</code> : Works inside	
<code>lateximage</code>	457
\fboxBlock: Added.	562
\makebox: Fix: Handles paren arg.	560
General: 2017/08/08	1
<code>babel-french</code> : Adds fixed-width	
HTML spaces to punctuation.	325
<code>balance</code> : Added.	622
<code>booktabs</code> : Works inside	
<code>lateximage</code>	461, 626
<code>boxedminipage2e</code> : Added.	628
<code>boxedminipage</code> : Prevented.	628
<code>crop</code> : Added.	672
<code>enumerate</code> : Added.	682
<code>enumitem</code> : Added, no longer	
required.	682
<code>everyshi</code> : Added.	689
<code>fancybox</code> : Added.	691
<code>fancyvrb</code> : Added, no longer	
required.	699
<code>figcaps</code> : Added.	705
<code>filecontents</code> : Required. Patched for	
<code>morewrites</code>	218
<code>floatpag</code> : Added.	711
<code>flushend</code> : Added.	717
<code>fullpage</code> : Added.	727
<code>hyperxmp</code> : Added.	755
<code>idxlayout</code> : Added.	756
<code>marginfit</code> : Added.	785
<code>mdframed</code> : Improved <code>mdtheorem</code>	
patch.	795
<code>moreverb</code> : Added.	802
<code>paralist</code> : Added.	828
<code>pdflscape</code> : Added.	831
<code>pdfsync</code> : Added.	834
<code>prelim2e</code> : Added.	837
<code>rotfloat</code> : Added.	849
<code>savetrees</code> : Added.	850
<code>shadow</code> : Added.	861
<code>syntonly</code> : Added.	885
<code>titleps</code> : No longer required.	899
<code>titleref</code> : Prevented.	903
<code>xmpincl</code> : Added.	957
Added.	949
Docs: Horizontal space	
limitations.	1

Docs: Misplaced alignment character.	187	\framebox: Fix: Handles width and horiz position.	560
File: <code>l warp_mathjax.txt</code> : Version change.	290	\makebox: Fix: Handles width and horiz position.	560
File: <code>README.txt</code> : updated.	1	General: 2017/08/17	1
Fix: Added the <code>eqnarray</code> environments.	526	babel-french : Adjustements for French variants, load order, footnotes, ellipses.	325
Improved font control.	564	footnote : Extra HTML source space after paragraphs.	721
Lists refactored to remove <code>enumitem</code> requirement.	394	siunitx : Fix for babel-french .	543
Verbatim refactored to remove <code>fancyvrb</code> requirement.	389	siunitx : Improved symbol support.	866
<code>lateximage</code> : Fix: <code>lateximage</code> with <code>minipage</code> , <code>\parbox</code> , <code>\makebox</code> , <code>\fbox</code> , <code>\framebox</code> , <code>\raisebox</code> , <code>\scalebox</code> , <code>\reflectbox</code> .	535	transparent : Added.	925
<code>BlockClass</code> : Moved optional argument in front of mandatory.	331	upref : Added.	931
<code>fminipage</code> : Added.	562	xcolor : Added <code>\fcolorboxBlock</code> , <code>\colorboxBlock</code> .	941
<code>LWR@nestspan</code> : Fix: Minipages, <code>BlocksClass</code> , and lists inside a span.	326	xcolor : Fix: Background none in print mode.	941
<code>LWR@tabular</code> : booktabs : Works inside <code>lateximage</code> .	462	xcolor : Refactored <code>\LWR@colorstyle</code> .	945
v0.35		xcolor : Uses <code>\fboxrule</code> and <code>\fboxsep</code> .	941
General: 2017/08/08	1	xcolor : <code>\fcolorbox</code> etc. now work inside <code>lateximage</code> .	941
Fix: <code>\textbf</code> and related.	564	Docs: Reorganized: Special cases and limitations.	123
v0.36		Source: Improved formatting.	1
<code>\LWR@HTMLsanitize</code> : Fix for babel-french .	531	<code>lateximage</code> : Footnotes appear in regular text instead of the <code>lateximage minipage</code> .	535
<code>\LWR@HTMLsanitizeexpand</code> : Fix for babel-french .	532	<code>LWR@tabular</code> : Fix for babel-french .	462
<code>\LWR@closeparagraph</code> : Extra HTML source space after paragraphs.	336	v0.37	
<code>\LWR@currenttextcolor</code> : Fix for <code>\rule</code> when xcolor not loaded.	571	include : Maintains independent aux files for HTML.	225
<code>\LWR@footnotetext</code> : Extra HTML source space after paragraphs. Force HTML superscripts.	345	General: 2017/08/19	1
<code>\LWR@nullfonts</code> : Fix: Filenames while using MATHJAX.	567	<code>\TeX</code> accents: Added.	239
<code>\LWR@restoreorigformatting</code> : siunitx : Improved super/subscripts in a <code>lateximage</code> .	500	babel-french : Adjustment for load order.	325
<code>\LWR@section</code> : Improved spacing.	361	color : Prevented.	669
<code>\LWR@stopars</code> : Extra HTML source space after paragraphs.	339	comment : Maintains independent cutfiles for print, HTML.	206
<code>\fbox</code> : Fix: Uses <code>\fboxrule</code> and <code>\fboxsep</code> .	561	siunitx : Improved symbol support.	866
		textcomp : Improved support.	887
		l warpmk : Removes additional HTML aux files.	292
		File handles reorganized.	224

v0.38	\@seccntformat: Added for appendix	361	\LWR@domulticolumn: Add: Optional vpos and # rows.	447
	\ForceHTMLPage: Added.	358	\LWR@restoreorigformatting: Appended with \appto instead of calling various macros.	500
	\ForceHTMLTOC: Added.	359	\LWR@tabledatacolumntag: Don't start a data cell if see \TabularMacro.	457
	\LWR@section: \part* starts a new HTML page, for appendix	361	\ResumeTabular: Added.	456
	Modified spacing, uses \newline.	361	\TabularMacro: Added.	456
	\newline: Added trailing \quad.	493	\multicolumnrow: Added.	454, 807
	\part: Fix with article class.	367	\printauthor: Removed minipages.	380
	General: 2017/08/27	1	Supports authblk with <div>s of class oneauthor instead of tabular.	380
	appendix : Added.	612	\thanksmarkseries: Removed minipage footnotes.	911
	arabicfront : Added.	613	General: 2017/09/05	1
	caption2 : Prevented.	636	a4wide : Added.	586
	chappg : Added.	639	a4 : Added.	586
	color : Forces xcolor as well.	669	a5comb : Added.	587
	fix2col : Added.	706	addlines : Added.	594
	fncychap : Added.	718	any size : Added.	612
	grffile : Added.	744	authblk : Added.	621
	metalogo : Added.	797	bigdelim : Added.	624
	nonumonpart : Added.	813	bigstrut : Added.	624
	nopageno : Added.	813	ebook : Added.	679
	pagenote : Option page disabled.	828	fullwidth : Added.	727
	realscripts : Added.	843	midpage : Added.	801
	relsize : Added.	846	multirow : Add: New optional vpos argument.	806
	romanbarpagenumber : Added.	848	multirow : Add: Supports left/right border for bigdelim	806
	romanbar : Added.	848	multirow : Fix: Long text argument.	806
	scalefont : Added.	851	supertabular : Added.	883
	siiunitx : Removed from l warp core.	866	textarea : Added.	887
	textcomp : Removed from l warp core.	887	titling : Improved compatibility.	907
	tocbibind : Added.	913	titling : Removed extraneous center environments.	908
	ltextra : Added.	956	typearea : Added.	928
	l warpmk : Added print1 and html1 actions.	292	xtabular : Added.	958
	Added \markboth, \sloppy, etc.	323	zwpagelayout : Added.	961
	Docs: Enhanced <i>Supported</i> Features table.	73	Docs: Reorganized tabular discussion.	160
	Docs: Index, tocbibind	137	Titlepage \published and \subtitle removed. \AddSubtitlePublished restores.	385
	Docs: Starred sections.	133	titlepage : Clear pending footnotes.	379
v0.39	\@maketitle: titling version.	910		
	Native L ^A T _E X version.	384		
	Removed minipages.	384, 910		
	Supports authblk with <div>s of class oneauthor instead of tabular.	384, 910		
	\AddSubtitlePublished: Added.	385		

Removed minipages.	379	
titlingpage: Clear pending footnotes.	908	
v0.40		
<code>@chapcntformat:</code> Added for tocbibind, anonchap.	361	
<code>\LWR@HTMLhline:</code> Added.	461	
<code>\LWR@includegraphicsb:</code> Add: Full <code>\graphicspath</code> support.	736	
<code>\LWR@nullfonts:</code> Fix: Long arguments for expandable command.	567	v0.41
<code>\LWR@restoreorigformatting:</code> Improved \LaTeX logos inside a <code>lateximage</code>	500	
Improved symbols inside a <code>lateximage</code>	500	
Nullified <code>\InlineClass</code> , etc. inside a <code>lateximage</code>	500	
<code>\LWR@tabledatacolumntag:</code> Fix for bigdelim: <code>\ldelem, \rdelem</code> . . .	457	
<code>\chapter:</code> Added support for quotchap.	367	
<code>\multicolumnrow:</code> Fix: Adapts to older <code>multirow</code> and <code>xparse</code> . . .	454	
<code>\simplechapterdelim:</code> Added for tocbibind, anonchap.	361	
<code>\underline:</code> Added.	571	
General: 2017/09/25	1	
adjmulticol: Added.	593	
anonchap: Added.	612	
bigdelim: Improved documentation.	624	
cuted: Added.	673	
dblfnote: Added.	674	
fnpos: Added.	719	
graphics: Moved out of the <code>lwrap</code> core.	731	
graphics: Restores <code>\includegraphics</code> and <code>\DeclareGraphicsExtensions</code> in a <code>lateximage</code>	731	
graphicx: Moved out of the <code>lwrap</code> core.	744	
grffile: Directly supported.	744	
midfloat: Added.	801	
multirow: Improved <code>bigdelim</code> borders.	806	
pfnote: Added.	836	
quotchap: Added.	841	
sectsty: Added.	859	
stabular: Added.	876	
tbls: Added.	885	
textcomp: Additional symbols, improved XeLaTeX and LuaLaTeX support.	887	
tocbibind: Improved for <code>\simplechapter</code>	913	
xtextra: Fix for <code>\showhyphens</code> with XeLaTeX.	956	
No longer preloads <code>xfrac</code>	220	
\LWR@addcmidruletrim: Add: <code>\cmidrule</code> trims.	435	
\LWR@clearcmidrules: Add: <code>\cmidrule</code> trims.	432	
\LWR@closetabledatacell: Add: Mute <code>></code> for <code>\bottomrule</code>	409	
Fix: At/bang column with <code>\multirow</code>	409	
Fix: Cancel <code><</code> for <code>\multicolumn</code>	409	
\LWR@domulticolumn: Add: <code>\cmidrule</code> trims.	447	
Added vertical rules.	448	
\LWR@nullifyNoAutoSpacing: Fix: <code>\NoAutoSpacing</code> in a tabular with <code>babel-french</code>	462	
\LWR@parsebarcolumn: Added vertical rules.	417	
\LWR@printatbang: Add: <code>\cmidrule</code> trims.	428	
Add: Mute at and bang columns for <code>\bottomrule</code>	428	
\LWR@printbartag: Added vertical rules.	428	
\LWR@subaddcmidruletrim: Added.	435	
\LWR@subcmidrule: Add: <code>\cmidrule</code> trims.	433	
\LWR@tabledatasinglecolumntag: Add: <code>\cmidrule</code> trims.	429	
Add: Mute <code><</code> for <code>\bottomrule</code>	429	
\LWR@tabularfinishrow: Unfinished tabular rows automatically filled.	411	
\mcolrowcell: Added for <code>\multicolumnrow</code> cells.	460	
General: 2017/10/07	1	
multirow: Add: <code>\cmidrule</code> trims.	806	
Added vertical rules.	806	
Fix: <code>< spec</code>	807	

Improved rules.	626
LWR@tabular: Fix: \NoAutoSpacing in a tabular with babel-french	463
v0.42	
\@ensuredmath: Improved	
\ensuremath.	516
\@textsubscript: Added.	570
\@textsuperscript: Added.	570
\LWR@HTMLhline: If FormatWP force explicit border.	461
\LWR@HTMLtextstyle: Added.	565
\LWR@addformatwpalignment: If FormatWP add explicit style for cell alignment.	437
\LWR@addrulewidth: If FormatWP force explicit border.	436
\LWR@amsmathbody: Fix: Numbering and naming AMS math environments.	534
\LWR@amsmathbodynumbered: Fix: Numbering and naming AMS math environments.	534
\LWR@doequation: If FormatWP print LaTeX expression.	521
\LWR@domulticolumn: If FormatWP add cell alignment.	448
\LWR@doubledollar: If FormatWP print LaTeX expression.	514
Improved \ensuremath.	514
Improved line spacing with mathjax.	514
\LWR@floatbegin: If FormatWP add a text frame.	480
\LWR@floatend: If FormatWP add a text frame.	481
\LWR@htmlmathlabel: If FormatWP print LaTeX expression.	525
\LWR@includegraphicsb: Fix: Filename expansion.	736
If FormatWP, use explicit size.	738
\LWR@remembertag: Fix: Numbering and naming AMS math environments.	534
\LWR@restoreorigformatting: Improved \ensuremath.	502
\LWR@subaddcmidruletrim: Opt if no rule given.	435
\LWR@subsingledollar: If FormatWP print LaTeX expression.	508
\LWR@tabledatasinglecolumntag: If FormatWP add cell alignment.	430
\LaTeX: If FormatWP use explicit style.	581
\TeX: If FormatWP use explicit style.	581
\hspace: If FormatWP add \quads.	576
\listoffigures: Added boolean WPMarkLOFT.	490
\listoftables: Added boolean WPMarkLOFT.	490
\marginpar: If FormatWP emulate a wrapfig.	349
\marginparBlock: If FormatWP emulate a wrapfig.	349
\rule: If FormatWP add \quads.	579
\tableofcontents: Added boolean WPMarkTOC.	490
\underline: If FormatWP, use explicit styles for \underline, etc.	571
General: 2017/10/30	1
\textbf and related: If FormatWP, use explicit styles for \textsc, etc.	564
algorithmicx: If FormatWP add \quads.	599
epigraph: If FormatWP add HTML styles.	683
fancybox: If FormatWP add HTML styles.	691
floatfl: Added width.	710
includegraphics: Fix: Class key.	736
keyfloat: If FormatWP add explicit HTML style.	766
moreverb: Simplified formatting of listings.	802
morewrites: Added.	803
multirow: If FormatWP add cell alignment.	806
overpic: Added.	827
realscripts: Fix for subscripts in a lateimage.	843
sidenotes: If FormatWP add explicit HTML style.	864
siunitx: Improved \ensuremath.	866
soul: If FormatWP, add explicit styles.	871
textcomp: Improved \interrobangdown.	887

wrapfig: If FormatWP add explicit	
HTML style.	940
Added boolean WPMarkLOFT.	234
Added boolean WPMarkMath.	234
Added boolean	
WPMarkMinipages.	233
Added boolean WPMarkTOC.	234
Added boolean WPTitleHeading.	234
Docs: Added support page.	2
Docs: Improper \prevdepth.	187
Docs: Reorganized math	
limitations	150
File: l warp_mathjax.txt:	
Updated siunitx script.	290
Fix: Numbering and naming AMS	
math environments.	533
If FormatWP force explicit border.	626
If FormatWP, shift section	
headings.	235
tabbing: Added.	392
lateximage: Fix: Numbering and	
naming AMS math	
environments.	535
center: If FormatWP use explicit	
text-align.	541
minipage: Added boolean	
WPMarkMinipages.	558
If FormatWP add a text frame.	557
eqnarray: Fix: Numbering and	
naming AMS math	
environments.	527
If FormatWP print LaTeX	
expression.	526
LWR@BlockClassWP: Added to factor	
code.	332
LWR@figcaption: If FormatWP forces	
italic captions.	484
v0.43	
\LWR@domulticolumn: Fix for	
vertical rules.	448
Fix: Multicolumn trim.	447, 448
\LWR@maybeprintpendingfootnotes:	
Added FootnoteDepth.	348
\LWR@nullfonts: Fix: Nullify dollar	
inside filenames.	567
\LWR@parsetablecols: Ignore	
spaces in col spec.	422
\LWR@printmccoltype: Added	
vertical rules.	443
v0.44	
\@currentlabelname: Adjustment	
for koma-script.	467
\HTMLTitle: Added.	342
\LWR@addformatwpalignment: Fix	
for multicolumn alignment if	
FormatWP.	437
\LWR@backgroundcolor: Added.	946
\LWR@filestart: Add \HTMLTitle.	371
Fix \HTMLAuthor.	370
\LWR@listitem: Added list and	
trivlist.	397
\LWR@patchlists: Added list and	
trivlist.	400
\LWR@strresult: Fix:	
\providecommand.	407
\LWR@textcurrentcolor: xcolor:	
Added	
\LWR@textcurrentcolor.	945
\addcontentsline: Automatic	
\LWR@newfloatanchor.	486
\chapter: Add preamble for	
koma-script.	367
\marginparBlock: Added.	349
\nopagecolor: xcolor: Fix for	
\nopagecolor.	947

\part: Add preamble for	
koma-script	367
\title: Added \thetitle.	342
General: 2017/11/22	1
algorithmicx : Improved comment	
symbol.	599
atbegshi : Added.	616
cancel : Added.	632
changepage : Additional options.	639
easy-todo : Added.	678
fancyref : Added.	697
fixmetodonotes : Added.	707
fixme : Added.	706
fontenc : Allowed after l warp	719
hang : Added.	746
ifoddpage : Added.	757
ltxtable : Added.	781
luatodonotes : Improved.	782
l warp-patch-komascript : Added.	963
overpic : Fix: Groups for	
lateximages	827
pdfsync : Fixes.	834
preview : Added.	838
scrextend : Added.	851
scrhack : Added.	854
scrlayer-notecolumn : Added.	856
scrlayer-scrpage : Added.	857
scrlayer : Added.	855
section : Added.	858
soulpos : Added.	873
soulutf8 : Added.	873
supertabular : Fix for caption.	884
tikz : Fix: Groups for lateximages	898
tocbasic : Added.	912
tocloft : Added \newlistentry.	920
tocloft : Improved \newlistof.	920
tocstyle : Added.	921
todonotes : Improved.	923
todo : Added.	922
typearea : Added expert	
commands.	928
watermark : Added.	939
xcolor : Added	
\LWR@currenttextcolorstyle.	945
xcolor : Added	
\LWR@findcurrenttextcolor.	945
xtab : Fix for caption.	959
Adjustment for koma-script	215
AMS environments: Fix: Groups	
for latexitimages	601
If pdfLaTeX, require T1 and UTF8	
encoding.	196
picture: overpic : Fix: Groups for	
latexitimages	554
list: Added list and trivlist	397
LWR@nestspan: Added list and	
trivlist	326
v0.45	
\@currentHref: Added.	475
\@donoparitem: Modified for HTML.	394
\@item: Modified for HTML.	395
\@mklab: Modified for HTML.	394
\CSSFilename: Improved filenames	
with underscores.	341
\lWR@LwarpStart: Fix: Latexitimages	
on incorrect pages with Mathjax.	374
\lWR@filenamenoblocks: Fix:	
Section names with \	352
Fix: Section names with	
underscores.	352
\lWR@includegraphicsb: Improved	
URLs with underscores.	736
\lWR@newautoidanchor: Fix: No	
anchor if frozen autoid.	482
\lWR@notmemoirloadafter: Added.	208
\lWR@printpendingmpfootnotes:	
Added.	348
\lWR@startref: Fix: Labels with	
underscores.	473
\lWR@subhyperref: Improved URLs	
with underscores.	475
\lWR@subhyperrefclass: Improved	
URLs with underscores.	476
\lWR@sublabel: Fix: Labels with	
underscores.	470
\lWR@tabledatacolumntag: Fix:	
Empty line between rows.	460
\chapter: Add optional heading title	
for memoir	367
\newpage: Added.	573
\nolinkurl: Fix: Underscore in URL.	476
\normalmarginpar: Added.	350
\reversemarginpar: Added.	350
\section: Add optional heading title	
for memoir	368
\tableofcontents: Fix: Empty	
sidetoc.	489
Fix: Patch \AtBeginDocument.	489
\url: Improved URLs with	
underscores.	477

General: 2018/01/14	1	minipage: Fix: Improper \prevdepth. 556, 558, 559
array: Added.	613	
babel-french: Robust commands.	325	
backref: Added.	622	
breakurl: Fix: Underscore in URL.	629	
changebar: Added.	638	
cite: Added.	668	
continue: Added.	671	
endfloat: Added.	680	
epigraph: Support for memoir .	684	
fancyvrb: Improvements. .	699, 700	
flafter: Added.	708	
fltrace: Added.	717	
footnpag: Added.	723	
fwlw: Added.	727	
hanging: Added.	747	
hyperref: Fix: Underscore in URL.	750	
l warp-patch-memoir: Added.	966	
memhfixc: Added.	797	
memoir: Added.	584	
natbib: Added.	809	
pagesel: Added.	828	
prettyref: Added.	837	
subfigure: Added.	882	
subfig: Fix for subcaption end tag.	880	
subfig: Fix: Math in subcaptions.	878	
textfit: Added.	890	
titleref: Added.	903	
turnthepage: Added.	927	
Allows memoir 's preloaded packages.	209	
Docs: xparse warnings.	169	
Docs: Fix for double hyphens. .	87	
Docs: Improved install instructions.	87	
Docs: Improved MiK $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ install instructions.	83	
Docs: Moved table so doesn't interfere with install docs. . .	82	
File: l warp_mathjax.txt: Allow MATHJAX inside tabbing.	290	
File: l warp_mathjax.txt: Allow MATHJAX inside verse.	290	
Fix: Empty sidetoc.	489	
Improved: Robust \, \ , and \textellipsis commands. .	572	
Separate LWR@thisautoidWP for word processor <div>s.	482	
thebibliography: Patched to emphasize titles.	499	
		v0.46
		\minipage: Fix: Improper \prevdepth. 556, 558, 559
		\LWR@closeparagraph: Fix: Tabular empty lines. 337
		\LWR@closeprevious: Fix: Stack unnesting. 322
		\LWR@forcenewpage: Fix: Improper \prevdepth. 323
		\LWR@lookforpackagename: Fix: Spaces in \usepackage. 222
		\LWR@providelength: Added. 197
		\LWRPrintStack: Name changed from \PrintStack. 321
		\makebox: Fix: Lateximage in a \makebox. 560
		\popclose: Fix: Stack unnesting. 313
		\pushclose: Fix: Stack unnesting. 312
		General: 2018/01/23
		1
		\LWR@tabularpardepth added. 407
		amsthm: Adapted to trivlist changes. 609
		mdframed: Fixes for SVG math or latexitimage in title. 791
		mdframed: Fixes for footnotes. 792
		ntheorem: Adapted to trivlist changes. 814
		theorem: Adapt to trivlist changes. 893, 895
		list: Fix: Stack unnesting. 398
		\LWR@tabular: Fix: Tabular empty lines. 465, 466
		v0.47
		\LWR@HTML@caption@begin: Fix: Argument passed to \LWR@origcaption@begin. 485
		\LWR@LwarpStart: Fix for SVG math in \nameref. 374
		\LWR@WPcell: Fix: Line wrap at HTML hyphen. 437
		\LWR@createautosec: Fix: Line wrap at HTML hyphen. 360
		\LWR@domulticolumn: Fix: Line wrap at HTML hyphen. 448
		\LWR@floatbegin: Fix: Line wrap at HTML hyphen. 480
		\LWR@htmlclosecomment: Add \mbox to prevent line breaks. 328
		\LWR@newautoidanchor: Fix: Line wrap at HTML hyphen. 482

\LWR@printopenlist:	Fix: Line wrap at HTML hyphen.	394
\LWR@startref:	Fix: Line wrap at HTML hyphen.	472
\LWR@sublabel:	Fix: Line wrap at HTML hyphen.	471
\LWR@subsingledollar:	Added SVG math image baseline adjust and em sizing.	508
	Fix: Line wrap at HTML hyphen.	512
\captionlistentry:	Fix: Line wrap at HTML hyphen.	486
\hypertoc:	Fix: Line wrap at HTML hyphen.	493
\hypertocfloat:	Fix: Line wrap at HTML hyphen.	494
\makebox:	Fix: Line wrap at HTML hyphen.	560
General:	2018/01/30	1
adjmulticol:	Fix: Line wrap at HTML hyphen.	593
blowup:	Added.	625
caption:	Added.	633
caption:	Also loads lwarf-caption .	224
changepage:	Fix for pagecheck macros.	639
endheads:	Added.	681
epigraph:	Fix: Line wrap at HTML hyphen.	683
hanging:	Fix: Line wrap at HTML hyphen.	748
hang:	Fix: Line wrap at HTML hyphen.	746
keyfloat:	Fix for SVG math in captions.	765
midpage:	Fix: Line wrap at HTML hyphen.	801
multirow:	Fix: Line wrap at HTML hyphen.	806
multitoc:	Added.	808
ntheorem:	Fix: Line wrap at HTML hyphen.	819
realscripts:	Fix: Line wrap at HTML hyphen.	843
scrextend:	Fix: Line wrap at HTML hyphen.	851
sectionbreak:	Added.	859
sidenotes:	Fix for SVG math in captions.	863
subfig:	Fix for SVG math in captions.	878
subfig:	Fix: Support \nameref.	878
xurl:	Added.	960
lwarpmk:	pdfcrop: Removed hires option for improved crop accuracy.	292
latextimage:	Added CSS style option.	535
	Fix: Line wrap at HTML hyphen.	539
center:	Fix: Line wrap at HTML hyphen.	541
minipage:	Fix: Line wrap at HTML hyphen.	557
flushleft:	Fix: Line wrap at HTML hyphen.	541
flushright:	Fix: Line wrap at HTML hyphen.	541
enumerate:	Fix: Line wrap at HTML hyphen.	398
itemize:	Fix: Line wrap at HTML hyphen.	398
LWR@BlockClassWP:	Fix: Line wrap at HTML hyphen.	332
v0.48		
\@@setcpageref:	Fix for new v0.21 of cleveref .	552
\@@setceref:	Fix for new v0.21 of cleveref .	551
\@@setcrefrange:	Fix for new v0.21 of cleveref .	551
\@biblabel:	Improved bibliography label.	499
\@item:	Honors \makelabel.	395
\@maketitle:	Fix: Errors with IEEEtran class.	384
\LWR@LwarpStart:	Adjusted space around captions.	373
\LWR@ProvidesPackageDrop:	Fix: Options with braces.	224
\LWR@addtabularhrulecolor:	colortbl: Added.	438
\LWR@addtabularrulecolors:	colortbl: Added.	439
\LWR@closetabledatacell:	colortbl: Added.	409, 410
\LWR@includegraphicsb:	Fix: Virtual page size limited to a group.	736, 740
\LWR@lookforpackagename:	Fix: Parsing similar package names.	221

\LWR@newautopagelabel: Fix: TOC,	
LOF, LOT links.	353
\LWR@newhtmlfile: Fix: TOC, LOF,	
LOT links.	357
\LWR@nullfonts: Fix: \newline in	
title.	567
\LWR@parsedrequirepackagenames:	
Fix: Parsing similar package	
names.	221
\LWR@parsetablecols: Fix: Ignore	
optional tabular column	
arguments.	423
\LWR@restoreorigformatting: Fix:	
Spacing in SVG math,	
\lateximage, Tikz.	501
\LWR@section: Fix: TOC, LOF, LOT	
links.	366
\LWR@tabledatasinglecolumntag:	
\colortbl: Added.	431
\LWR@textcurrentfont: Added.	
Improves font control.	568
\bibliography: Fix: \BaseJobname	
for bibliography.	499
\centerline: Added.	542
\l@part: Adapts to classes without	
\part.	495
\leftline: Added.	542
\mbox: Nullified for HTML.	559
\rightline: Added.	542
\thempfootnote: Removed	
\itshape.	347
General: 2018/02/14	1
\acronym: Added.	591
\acro: Added.	590
\chapterbib: Added.	639
\colortbl: Added.	425, 438, 669
\fancyheadings: Prevented.	696
\fancyref: Now directly supported.	697
\hypcap: Added.	748
\hypernat: Added.	749
\hyperref: \texorpdfstring now	
uses the TeX string.	753
\luatodonotes: Improved	
\todototoc.	782
\siunitx: Changes fraction to	
symbol.	868
\siunitx: Improved SVG math.	866, 868
\siunitx: Improved color output.	866
\stfloats: Added.	877
\todonotes: Improved	
\todototoc.	923
\vmargin: Added.	934
\xfrac: Fix: Added groups around	
super/subscripts to localize	
\LWR@nestspan changes.	954
Docs: Converting an existing	
document.	104
Improved font control.	568, 569
\lateximage: Print mode boxed to	
natural width.	540
\abstract: Allow optional name.	386
\LWR@tabular: \colortbl: Added.	464
v0.49	
\LWR@addtabularcellcolor:	
\xcolor: Added tabular row colors.	441
\LWR@domulticolumn: \xcolor: Added	
tabular row colors.	448
\LWR@printlength: Fix: Group	
\printlen changes.	220
\affiliation: Fix: Adapts to classes	
which already provide.	378
\href: Fix: Adapt to classes.	476
\noalign: Fix: \noalign inside	
\tabular.	461
\url: Fix: Adapt to classes.	477
General: 2018/02/19	1
\amsmath: Fix: Patches for	
\eqref.	601
\eso-pic: Fix for	
\AddToShipoutPicture.	688
\figsize: Added.	705
\fnc lineno: Added.	719
\hypdestopt: Added.	749
\hyphenat: Added.	755
\lineno: Added.	769
\luacolor: Added.	781
\pagegrid: Added.	828
\pdfrender: Added.	834
\resizegather: Added.	848
\verbbars: Added.	934
\vwcol: Added.	936
\xcolor: Added tabular row	
colors.	425, 951
Fix: Adapt to classes.	573
v0.50	
\@ensuredmath: Fix: Use	
\latexitimage even if MathJax.	516
Improved SVG math alt tags.	516

\LWR@atbeginverbatim:	Improved column alignment.	390	
\LWR@doequation:	Improved svg math display.	521	
\LWR@doubledollar:	Improved svg math alt tags.	514	
	Improved svg math display.	514	
\LWR@footnotetext:	Robustify macros.	345	
\LWR@htmlrefsectionfilename:	Fix: SVG math in a section name.	320	
\LWR@newhtmlfile:	Fix: SVG math in a section name.	356	
\LWR@nullfonts:	Fix: \underline in sectioning file name.	568	
	Robustify macros.	567	
\LWR@overline:	Added.	571	
\LWR@singledollar:	Fix: Use lateximage even if MathJax.	508	
	Improved svg math alt tags.	508	
	MD5 hash avoids duplicate svg math.	512	
\LWR@vspace:	Robustify macros.	577	
\newline:	Robustify macros.	573	
\textsubscript:	Robustify macros.	570	
\textsuperscript:	Robustify macros.	570	
General:	2018/03/03	1	
	lwarpcss:	Improved svg display math centering.	248
	lwarponeimage.txt:	Added.	289
amsmath:	Fix: Upright tags for svgmath.	601	
axodraw2:	Added.	622	
bytefield:	Added.	632	
dblfloatfix:	Added.	674	
diagbox:	Added.	675	
epstopdf:	Added.	685	
listings:	Force flexible columns.	773	
morefloats:	Added.	802	
nonfloat:	Added.	813	
ntheorem:	Fix: Not standard nor amsthm selected.	821	
pbox:	Added.	830	
phfqt:	Added.	836	
schemata:	Added.	851	
siunitx:	Fix: Loads xcolor .	866	
	siunitx: Improved svg math alt tags.	868	
	siunitx: Improved units.	543, 866, 869	
xy:	Added.	961	
lwarpmk:	Error if lateximages.txt does not exist.	292	
	lwarpmk: Error if lwarpmk.conf points to lwarp .	292	
lwarpmk:	Improved error messages.	292	
lwarpmk:	MD5 hash avoids duplicate svg math.	292	
lwarpmk:	Multiprocess support making lateximages.	292	
AMS environments:	Improved svg math display.	601	
Fix:	Load fontspec if necessary.	216	
	Robustify macros.	569	
lateximage:	Fix: SVG math in a section name.	538	
	MD5 hash avoids duplicate svg math.	536, 539	
eqnarray:	Improved svg math display.	527, 528	
v0.51			
	\@ensuredmath:	Hashes	
		\ensuremath.	516
	\@item:	Restored list label space.	396
	\LWR@HTMLsanitize:	Fix: Escapes double quotes.	531
	\LWR@HTMLsanitizeexpand:	Fix: Escapes double quotes.	532
	\LWR@LwarpStart:	MathJax: Nullifies \ensuremath.	374
	\LWR@addbaselinemarker:	Improved svg math baseline.	507
	\LWR@atbeginverbatim:	Adds vertical offset.	390
	\LWR@customizeMathJax:	MathJax: Nullifies \ensuremath.	354
	\LWR@doequation:	Fix: \addcontentsline inside svg math. Provides an autoid anchor.	521
	\LWR@doubledollar:	Fix: \addcontentsline inside svg math. Provides an autoid anchor.	514
	\LWR@findcurrenttextcolor:	Added	
		\LWR@findcurrenttextcolor when no xcolor .	571
	\LWR@newautoidanchor:	Fix: No autoid is inside a lateximage .	482

\LWR@newhtmlfile: MathJax:	
Nullifies \ensuremath.	358
\LWR@subsingledollar: Fix:	
\ensuredmath inside SVG image.	509
Fix: \teximage inside $\mathcal{M}\mathcal{S}$	
\text.	510
Fix: Honors text font around SVG	
math.	510
Fix: SVG math with enclosed	
\teximage.	509
Improved SVG math baseline.	511
SVG math baseline improved with	
invisible rule at corner.	513
Typeset SVG math only once	
during measurement.	510
\LWR@textcurrentcolor: \xcolor:	
\LWR@textcurrentcolor if	
\xcolor not loaded.	571
\addcontentsline: Add missing	
support for float mechanism if	
necessary.	487
No anchor ID if inside SVG image.	486
\displaymathnormal: Processing for	
complicated display math.	523
\displaymathother: Processing for	
complicated display math.	524
\textcolor: Fix: SVG math color.	946
General: 2018/03/24	1
l warp_one_limage.txt:	
pdftocairo -noshrink added.	289
afterpackage: No longer required.	218
chemfig: Added.	640
chemformula: Added.	641
chemgreek: Added.	646
chemmacros: Added.	647
chemnum: Added.	667
epstopdf-base: Added.	686
fancybox: Fix: Optional tag for	
\item in a span.	694
grid: Added.	745
listings: Forces cleared options.	773
ltxgrid: Added.	780
mhchem: Added.	798
tikz: Fix for \tikz macro.	898
tikz: Fix for tikz with optional	
argument.	898
titling: Fix for \thanks mark.	909
lwarpmk: pdfcrop: Restored	
hires option.	292
lwarpmk: pdftocairo -noshrink	
added.	292
AMS environments: Fix:	
\addcontentsline inside SVG	
math. Provides an autoid anchor.	601
Docs: tikz limitations.	157
Docs: Multiple authors and	
affiliations.	133
Docs: Things to avoid.	124
Docs: Updated Converting an	
existing document.	104
Fix: Remember original \# in case	
is redefined.	236
HTML entity used for text dollar.	507
\teximage: Added additional	
hashing option.	535
Fix: \teximage inside $\mathcal{M}\mathcal{S}$	
\text.	535
Processing for complicated display	
math.	538
alignat: Fix: Added.	606
eqnarray: Fix: \addcontentsline	
inside SVG math. Provides an	
autoid anchor.	527, 528
\LWR@displaymathother: Processing	
for complicated display math.	517
\LWR@equationother: Processing for	
complicated display math.	517
v0.52	
\@ensuredmath: Improved hashing	
expansion.	516
\@mpfootnotetext: Fix: Paragraph	
handling.	347
\CustomizeMathJax: Added.	354
\@LWR@addbaselinemarker:	
Warnings if	
l warp_baseline_marker.png is	
not present or if graphicx/s not	
loaded.	507
\@LWR@customizedMathJax: Added.	354
\@LWR@doequation: Fix: equation*	
now based on equation instead	
of displaymath.	521
Fix: equation* with split.	520
\@LWR@filenamenoblocks: Fix:	
\FileDepth with non-utf8	
encoding.	353
\@LWR@footnotetext: Fix: Paragraph	
handling.	346

\LWR@newhtmlfile: Fix:	v0.53
\FileDepth with non-utf8	
encoding.	356
\LWR@nullfonts: Fix:	
\textorpdfstring in section	
names.	568
\LWR@section: Fix: Footnote	
numbering: Limited HTML	
comment if starred.	363
Fix: Footnote numbering: Use	
short TOC entry for HTMLDebug	
comments.	363
\LWR@subsingledollar: Added	
user-adjustable svg math font	
scaling.	511
\LateximageFontSize: Added	
user-adjustable svg math font	
scaling.	531
\href: Fix: #, %, &, ~, _ in URL.	476
\nolinkurl: Fix: #, %, &, ~, _ in URL.	476
\url: Fix: #, %, &, ~, _ in URL.	477
General: 2018/04/01	1
breakurl: Fix: #, %, &, ~, _ in URL.	629
endfloat: Updated for v2.6.	680
fancyvrb: Initial support for	
\VerbatimFootnotes.	691, 699
hyperref: Fix: #, %, &, ~, _ in	
URL.	750, 752
nicefrac: Added.	812
url: Added.	931
\warpmk: Fix: Memory overflow	
when spawning tasks.	292
\warpmk: Fix: Skip image	
generation if from page 0.	292
Changed FootnoteDepth default	
to \subsubsection.	344
Docs: Improved install	
instructions.	84
Fix: MathJax script line wraps.	
Reduced right margin.	217
If pdfLaTeX, allow other input	
encoding.	196
pkggraphics: Added defaults.	733, 734
pkggraphicx: Updated for v1.1a. .	734
pkggraphicx: Updated for v1.1b. .	734
Restore \kill in a \latexitimage. .	778
tabbing: Fix to allow inside	
\latexitimage.	392
\latexitimage: Fix for hash expansion.	537
	v0.54
General: 2018/04/01	1
\warpmk: Added	
\warpmk cleanimages.	292
\warpmk: Added warning for	
corrupted images.	292
Docs: \warpmk cleanimages. .	102
Docs: \warpmk pdftohtml. . .	102
	v0.54
\LWR@afterendverbatim: Added	
vspace argument.	391
\LWR@atbeginverbatim: Improved	
column alignment.	390
\LWR@earlyloadnever: Added. . .	209
\LWR@endfloatalignment: Honor	
\centering, etc. in floats. . .	483
\LWR@floatalignment: Honor	
\centering, etc. in floats. . .	483
\LWR@floatbegin: Honor	
\centering, etc. in floats. . .	481
\LWR@floatend: Honor \centering,	
etc. in floats.	481
\LateximageFontSizeName:	
Defaults to normalsize.	531
\centering: Added debug	
comment.	541
\raggedleft: Added debug	
comment.	541
\raggedright: Added debug	
comment.	542
General: 2018/04/22	1
*.lwarpmkconf: Option	
IndexLanguage changed to	
xindyLanguage.	248
*.lwarpmkconf: Option	
pdftotextEnc added.	248
*.lwarpmkconf: Option	
xdyFilename changed to	
xindyStyle.	248
*.lwarpmkconf: Option	
xindyCodepage added.	248
lwarpcss: Fix:	
Text-decoration-skip: auto. . .	248
lwarpmk.conf: Option	
IndexLanguage changed to	
xindyLanguage.	247
lwarpmk.conf: Option	
pdftotextEnc added.	247

lwarpmk.conf: Option	
<code>xidyFilename</code> changed to	
<code>xindyStyle</code>	247
lwarpmk.conf: Option	
<code>xindyCodepage</code> added.	247
aecc: Prevented.	594
ae: Prevented.	594
bibunits: Added.	623
chngpage: Added.	639
forest: Added.	723
glossaries: Fix when not using	
<code>babel</code> or <code>Polyglossia</code>	730
gridset: Added.	745
hyperref: Fix: <code>\hyperref</code> and	
<code>\hyperlink</code> with special chars in	
text.	752
hyperref: Fix: <code>\ref</code> in <code>\hyperref</code>	
and <code>\hyperlink</code> caused nested	
link.	752
inputenx: Added.	764
lwarpatch-memoir: Update for	
v3.7g.	971
magaz: Added.	784
ragged2e: Fix: <code>\centering</code> , etc. .	843
t1enc: Prevented.	885
textcomp: Fix for	
<code>\textperthousand</code>	887
tikz: Fixes for <code>\pgfpicture</code> ,	
<code>minipages</code> , <code>fit</code> , <code>align</code> , <code>font</code>	898
wasysym: Prevented.	939
lwarpmk: Added <code>pdftotextenc</code> . .	292
lwarpmk: Added <code>xindycodepage</code> . .	292
lwarpmk: Changed language to	
<code>xindylanguage</code>	292
lwarpmk: Changed <code>xidyfile</code> to	
<code>xindystyle</code>	292
lwarpmk: Improved error if	
configuration file does not exist. .	292
lwarpmk: Increased prominence	
for error for an unknown	
command.	292
lwarpmk: Verifies HTML version	
exists before <code>lwarpmk limages</code> . .	292
lwarpmk: Verifies image	
references before	
<code>lwarpmk limages</code>	292
<code>Add:</code> <code>pdftotextEnc</code>	202
<code>Add:</code> <code>xindyCodepage</code>	202
Added early check for disallowed	
packages.	209
Docs: BibTeX.	135
Docs: Macros in sectioning	
names.	124
Never load <code>aecompl</code>	209
Option <code>IndexLanguage</code> changed	
to <code>xindylanguage</code>	202
Option <code>xidyFilename</code> changed to	
<code>xindyStyle</code>	202
verse: Fix: Line spacing.	389
v0.55	
<code>\LWR@LwarpStart:</code> Fix: Overfull	
boxes in <code>latexitimages</code>	372
<code>\LWR@floatbegin:</code> Fix: Float	
optional args.	481
<code>\LWR@nullfonts:</code> Removed	
extraneous space which	
appeared in file links.	568
<code>\phantomsection:</code> Fix:	
<code>\ForceHTMLTOC</code> with	
<code>\phantomsection</code>	580
General: 2018/04/26	1
clrdblpg: Added.	668
Fix: <code>\centering</code> , etc. for	
<code>koma-script</code>	481
Fix: QED symbols in	
<code>latexitimage</code>	611, 826
v0.56	
<code>\LWR@addcdashline:</code> arydshln:	
Added.	437
<code>\LWR@addmulticolvertrulecolor:</code>	
Adds support for dashed vertical	
rules.	446
Adds support for double vertical	
rules.	446
<code>\LWR@addtabularhrulecolor:</code> Adds	
support for arydshln dashed	
rules.	438
Adds support for double <code>\hlines</code>	
and <code>\midrules</code>	438
<code>\LWR@addtabularrulecolors:</code> Adds	
support for dashed vertical rules. .	439
Adds support for double vertical	
rules.	439
<code>\LWR@closeparagraph:</code> Added	
support for <code>parnotes</code>	337
<code>\LWR@domulticolumn:</code> Adds support	
for dashed vertical rules.	448
Adds support for double vertical	
rules.	448

\LWR@floatbegin: Adds a <class>	
per float package style.	480
\LWR@multicolpartext: Fix:	
multicolumn parameters.	443
\LWR@openparagraph: Added	
support for parnotes	335
\LWR@parsebarcolumn: Adds	
support for double vertical rules. .	417
\LWR@parsecoloncolumn: arydshln :	
Added.	418
\LWR@pasesemicoloncolumn:	
arydshln : Added.	418
\LWR@parsetablecols: Added array	
W column.	424
\LWR@printmccoldata: Added array	
W column.	444
Fix: \multicolumn parameters. .	444
\LWR@printmccoltype: Added array	
W column.	442
Adds support for dashed vertical	
rules.	443
Adds support for double vertical	
rules.	443
\LWR@tabledatacolumnntag: Fix:	
\morecmidrules	459
\LWR@textcurrentfont: Added	
span.textbf, etc.	568
General: 2018/05/12	1
*.lwarpmkconf: Records	
--shell-escape.	248
l warp.css: Added div.textbf,	
etc.	248
l warp.css: Added span.textbf,	
etc.	248
l warpmk.conf: Records	
--shell-escape.	247
arydshln : Added.	404, 614
lua-check-hyphen : Added.	781
paralist : Fixes for compactenum,	
compactitem, compactdesc. . .	828
parnotes : Added.	829
quoting : Added.	842
toccenter : Added.	914
underscore : Added.	930
lwarpmk : Added	
lwarpmk pdftosvg.	292
lwarpmk : Supports	
--shell-escape.	292
Added \thinspace.	572
Docs: <i>lwarpmk pdftosvg</i>	102
\LWR@blocktextcurrentfont: Added	
div.textbf, etc.	569
v0.57	
BlockClassSingle : Improved	
print/HTML output selection. .	332
InlineClass : Improved	
print/HTML output selection. .	332
\LWR@customizeMathJax : MathJax:	
Supports \footnote,	
\footnotemark.	354
\LWR@ref@ignorestar : subcaption :	
Fix: \subref.	474
\LWR@subhyperref : Fix: Text	
catcodes.	475
\LWR@subhyperreftext : Fix: Text	
catcodes.	475
\LWR@subsingledollar : Fix:	
Dynamic inline math	
expressions.	509, 510, 512
\LWR@vspace : Improved print/HTML	
output selection.	577
\StartDefiningMath : Added.	315
\boxframe : xcolor : Fix: Colored	
\boxframe.	950
\colorbox : xcolor : New system for	
switching print and HTML	
outputs.	947
\colorboxBlock : xcolor : New	
system for switching print and	
HTML outputs.	947
\fboxBlock : Improved print/HTML	
output selection.	562
\fcolorbox : xcolor : New system for	
switching print and HTML	
outputs.	948
\framebox : Improved print/HTML	
output selection.	560
\href : Fix: Text catcodes.	476
\inlinemathother : Added.	316
\listof : Fix: Provide \l@name if not	
defined.	491
\makebox : Improved print/HTML	
output selection.	560
\mathimagename : Added.	506
\mbox : Improved print/HTML output	
selection.	559
\multicolumnrow : multirow :	
Improved print/HTML output	
selection.	807

Improved print/HTML output	
selection.	454
\newfloat: rotfloat : Added float	
styles.	850
rotfloat : Fix for listof sideways	
floats.	850
\packagediagramname: Added.	506
\parbox: Improved print/HTML	
output selection.	559
\raisebox: Improved print/HTML	
output selection.	564
\reflectbox: Improved print/HTML	
output selection.	743
\resizebox: Improved print/HTML	
output selection.	743
\rotatebox: Improved print/HTML	
output selection.	741
\rule: Fix: Colored rules.	578
\scalebox: Improved print/HTML	
output selection.	742
\textcolor: xcolor : New system for	
switching print and HTML	
outputs.	946
General: 2018/06/06	1
lwarpm.css: Added ruled, boxed,	
boxruled floats.	248
lwarpm.css: Increased float	
vertical margins.	248
algorithm2e : Added.	595
bigdelim : Improved print/HTML	
output selection.	624
breakurl : Fix: Text catcodes.	629
colortbl : New system for switching	
print and HTML outputs.	670
ellipsis : Added	
\midwordellipsis.	679
errata : Added.	687
float : Added float styles.	709
float : Fix: Do not pre-define	
\l@name.	709
glossary : Prevented.	731
ltabx : Added.	779
marginnote : Fix: Long optional	
argument.	786
multirow : Improved print/HTML	
output selection.	806
register : Added.	845
subcaption : Fix: \subref.	750
trimclip : Added.	925
vowel : Added.	935
xellipsis : Added.	952
xfrac : Improved print/HTML	
\scalebox control.	954
xltabular : Added.	956
xpiano : Added.	957
lwarpmk : Improved code	
factoring.	292
lwarpmk : Improved error	
handling.	292
Docs: Recompiling lwarpmk or	
css files.	186
Docs: Recreating the index for	
lwarp source.	182
New system for switching print	
and HTML outputs.	231
minipage : Improved print/HTML	
output selection.	556
BlockClass : Improved print/HTML	
output selection.	331
fminipage : Improved print/HTML	
output selection.	562
LWR@BlockClassWP : Improved	
print/HTML output selection.	332
v0.58	
\LWR@HTML@caption@begin:	
Improved print/HTML output	
selection.	485
\LWR@HTML@caption@end: Improved	
print/HTML output selection.	485
\LWR@HTML@ref: Improved	
print/HTML output selection.	474
\LWR@doindexentry: Adds support	
for \see, \seealso, \emph,	
\textbf{etc}.	498
\LWR@hyperindexrefnullified:	
Adds support for \see,	
\seealso, \emph, \textbf{etc}.	498
\LWR@indexitem: Accepts optional	
arg for repeatingindex	497
\dotfill: Improved print/HTML	
output selection.	573
\hfill: Improved print/HTML	
output selection.	573
\hrulefill: Improved print/HTML	
output selection.	573
\hyperindexref: Adds support for	
\see, \seealso, \emph, \textbf{etc}.	498
\printindex: Fix: Extra \newpage to	
flush pending \index writes.	784

General: 2018/07/07	1
*.lwarpmkconf: Added option makeindexstyle.	248
*.lwarpmkconf: Added options makeindex and xindy.	248
*.lwarpmkconf: Generated \AtBeginDocument.	248
lwarf.xdy: Requires makeindex.xdy.	288
lwarf.xdy: Supports bold, italic.	288
lwarf_html.ist: Added.	288
lwarpmk.conf: Added option makeindexstyle.	247
lwarpmk.conf: Added options makeindex and xindy.	247
lwarpmk.conf: Generated \AtBeginDocument.	247
array: Improved print/HTML output selection.	613
attachfile2: Added.	618
attachfile: Added.	617
cases: Added.	637
imakeidx: Added.	758
index: Added.	762
intopdf: Added.	764
lwarf-patch-komascript: Modified indexing.	963
lwarf-patch-memoir: Fix for \specialindex.	988
lwarf-patch-memoir: Fix for multiple indexes.	989
makeidx: Added. Moved from lwarf core.	784
memoir: Fix for \firsthline, \lasthline.	455
memoir: Fix for booktabs.	461
pdfpages: Added.	831
pdfx: Added.	836
repeatingindex: Added.	847
splitidx: Added.	874
textcomp: Improved print/HTML output selection.	887
lwarpmk: Added makeindex and xindy options.	292
lwarpmk: Added -p option for project name.	292
lwarpmk: Added optional list of names for <i>lwarpmk printindex</i> and /cmdslwarpmk htmlindex.	292
lwarpmk: Glossary generation now uses makeglossaries .	292
lwarpmk: <i>lwarpmk clean</i> removes all *.ind and *.idx files.	292
Added makeindex option.	204
Added xindy option.	204
Added option makeindexStyle .	202
Docs: Index, makeindex , imakeidx .	137
Docs: Misplaced \omit.	187
Fix: memoir and ccaption .	209
Improved print/HTML output selection.	572
Replaced each \csuse with \@nameuse to force error if undefined.	1
tabbing: Improved print/HTML output selection.	392
v0.59	
\LWR@addbaselinemarker: Uses .eps if DVI latex .	507
\LWR@includegraphicsb: Fix: Expand filename.	737
Now works with .pdf and .eps filename extensions.	736
\LWR@latexmkcmd: Fix: --shell-escape with latexmk .	243
\LWR@writeconf: Compilation commands now preassigned by lwarf instead of being computed by lwarpmk .	247
\[: Fix with \displaymathnormal.	515
General: 2018/09/07	1
Slunits: Added.	865
accsupp: Added.	589
amsmath: Moved from the lwarf core.	601
asymptote: Added.	616
axessibility: Added.	621
breqn: Added.	630
bxpapersize: Added.	631
canoniclayout: Added.	633
chemformula: Fix for \NMR.	664
draftcopy: Added.	677
epstopdf-base: Improved.	686
epstopdf: Improved.	685
fnbreak: Added.	718
nccfancyhdr: Added.	810
pdftricks: Added.	835

pst-eps: Added.	839	draftfigure: Added.	677
pstricks: Added.	841	fancytabs: Added.	698
units: Added support for		fullminipage: Added.	726
MathJax.	931	grid-system: Added.	745
xunicode: Added.	960	layaureo: Added.	767
lwarpmk: Added		leading: Added.	768
<i>lwarpmk epstopdf.</i>	292	listings: Fix for HTML entities.	773
lwarpmk: Consolidated compiling		listings: Fix if inside a list.	774, 776
options into <code>printlatexcmd</code> and		thumbs: Added.	897
<code>HTMLlatexcmd.</code>	292	thumb: Added.	897
lwarpmk: Double instead of		widows-and-orphans: Added.	939
single-dashed <code>--shell-escape</code>			
option.	292		
lwarpmk: Error if <code>lwarpmk.conf</code>		v0.61	
format changed.	292	\DeclareGraphicsExtensions: Fix:	
lwarpmk: Warning if operating		EPS for DVI \LaTeX	731
system changed.	292	\LWR@HTMLLatexCmd: Added	
Added option <code>dvipdfmx</code>	204	<code>HTMLLatexCmd</code> option.	246
Added option <code>dvipdfm</code>	204	Added <code>PrintLatexCmd</code> option.	246
Added option <code>dvips</code>	204	\LWR@addcompilecmd: Removed	
Docs: <i>lwarpmk epstopdf.</i>	102	spaces.	242
File: <code>l warp_mathjax.txt:</code> Fix:		\LWR@closetabledatacell: Fix: Par	
Removed chapter number from		tags in <code>tabular</code>	409
tagged non-numeric MathJax		\LWR@hyperindexrefnullified:	
equations.	290	Made robust,	498
File: <code>l warp_mathjax.txt:</code>		\LWR@includegraphicsb: Fix: EPS	
Updated to MathJax v2.7.4.	290	for DVI \LaTeX	738
picture: Added an alt tag.	554	Set keys before using filename, for	
v0.60		<i>epsfig.</i>	737
\LWR@clearmidrules: <code>tabular</code> : Fix		\LWRopseq: Added spaces.	199
for midrules.	432	\RequirePackage: Support up to 20	
\LWR@parsenormalcolumn:		packages.	222
<code>tabular</code> : Improved memory		\inlinemathnormal: Changed name	
management: Not using <code>xstring</code>	419	from <code>\StopDynamicMath</code> to	
\LWR@tableddatasinglecolumntag:		<i>inlinemathnormal.</i>	316
<code>tabular</code> : Improved memory		\inlinemathother: Changed name	
management: Not using <code>xstring</code>	430	from <code>\StartDynamicMath</code> to	
\LWR@tabularendofline: Fix:		<i>inlinemathother.</i>	316
Slowdown for long tables.	414	\listof: Fix: <code>newfloat</code> lists.	491
General: 2018/09/19	1	\l warpsetup: Added.	200
<code>tabular</code> : Improved memory		General: 2018/10/13	1
management: Global		l warp.css: Footnotes text align	
boolean.	405, 406	left.	248
<code>tabular</code> : Improved memory		l warp.css: Minipage table and	
management: Not using		footnotes: tighter margin.	248
<i>xstring</i>	407, 806	chkfloat: Added.	668
2up: Added.	586	cmdtrack: Added.	669
booklet: Added.	625	copyrightbox: Added.	672
bophook: Added.	628	dprogress: Added.	676
diagbox: Fix for par tags.	676	epsfig: Added.	684
		lua-visual-debug: Added.	781
		pdfprivacy: Added.	834

psfragx : Added.	839	Added HTMLLatexCmd option.	203
psfrag : Added.	838	Added PrintLatexCmd option.	203
pstool : Added.	840	Docs: \tracingl warp	227
refcheck : Added.	844	Docs: Compiling using custom	
srcltx : Added.	875	shell commands.	170
srctex : Added.	876	Docs: Fonts.	105
supertabular : Fix for caption w/o		Docs: HTML entities.	124
opt arg.	883	Docs:	
thinsp : Added.	895	HTMLDebugComments	112, 227
threadcol : Added.	896	Docs: Multiple indexes.	191
uspace : Added.	932	Don't write configuration files if	
vpe : Added.	936	processing pstool image.	240
xbmks : Added.	941	Spaces redefined	
xtab : Fix for caption w/o opt arg.	959	\AtBeginDocument.	572

Index of Objects

This is an index of macros, environments, booleans, counters, lengths, packages, classes, options, keys, files, and various other programming objects. Each is listed by itself, and also by category. In some cases, they are further subdivided by [class].

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition.

Symbols	
\\$	<i>507</i>
\&	<i>318</i> , <u>6534</u>
\(.....	<u>8924</u>
\,	<i>125</i>
--shell-escape (option)	<i>105</i>
\@@setcpageref	<u>9683</u>
\@@setcref	<u>9646</u>
\@@setcrefrange	<u>9660</u>
\@author	<i>377</i>
\@begintheorem	<u>6200</u>
\@biblabel	<u>8584</u>
\@capttype	<u>8212</u>
\@chapcntformat	<u>5498</u>
\@currentHref	<u>8060</u>
\@currentlabelname	<u>7916</u>
\@date	<i>377</i>
\@dلبfloat	<u>8178</u>
\@donoparitem	<u>6226</u>
\@endtheorem	<u>6212</u>
\@ensuredmath	<u>8934</u>
\@float	<u>8178</u>
\@fnssymbol	<u>5989</u>
\@footnotetext	<u>5149</u>
\@include	<u>815</u>
\@item	<u>6239</u>
\@makecaption	<u>8233</u>
\@makefnmark	<u>5117</u>
\@makefntext	<u>5116</u>
\@maketitle	<u>56</u> , <u>6012</u>
\@mklab	<u>6220</u>
\@mpfootnotetext	<u>5151</u>
\@nbitem	<u>6306</u>
\@opargbegintheorem	<u>6206</u>
\@rowc@lors	<u>6855</u>
\@rowcolors	<u>6854</u>
\@seccntformat	<u>5496</u>
\@starttoc	<u>8352</u>
\@textsubscript	<u>10134</u>
\@textsuperscript	<u>10130</u>
\@title	<i>377</i>
\@wrglossary	<u>8533</u>
\@wrindex	<u>8522</u>
\[.....	<u>8924</u>
\\\	<i>573</i>
\\$	<i>514</i>
\\$\\$	<i>514</i>
2up (package)	<u>586</u>
A	
a4 (package)	<u>586</u>
a4wide (package)	<u>586</u>
a5comb (package)	<u>587</u>
abstract (environment)	<u>6075</u>
abstract (package)	<i>134</i> , <u>587</u>
\abstractname	<u>115</u> , <u>6074</u>
accsupp (package)	<u>589</u>
acro (package)	<u>590</u>
acronym (package)	<u>591</u>
\addcontentsline	<u>8303</u>
addlines (package)	<u>594</u>
\AddSubtitlePublished	<u>6040</u>
adjmulticol (package)	<u>593</u>
Adobe (program)	<u>79</u>
ae (package)	<u>594</u>
aecc (package)	<u>594</u>
\affiliation	<u>5892</u>
afterpage (package)	<u>595</u>
algorithm2e (package)	<u>595</u>
algorithmicx (package)	<u>599</u>
algorithmx (package)	<u>164</u>
align (environment)	<u>127</u>

align* (environment)	<u>153</u>	booleans:	
alignat (environment)	<u>231</u>	CombineHigherDepths	<u>114, 350</u>
alignat* (environment)	<u>257</u>	FileSectionNames	<u>115, 319</u>
alltt (package)	<u>600</u>	FormatEPUB	<u>174, 233</u>
\AmS	<u>10395</u>	FormatWP	<u>176, 233</u>
amsmath (package)	<u>601</u>	HTMLDebugComments	<u>115, 227</u>
amsthm (package)	<u>607</u>	LWR@amsmultline	<u>524</u>
\and	<u>377</u>	LWR@copiedsidetoc	<u>489</u>
anonchap (package)	<u>611</u>	LWR@doingapar	<u>334</u>
anysize (package)	<u>612</u>	LWR@doingcmidrule	<u>406</u>
appendix (package)	<u>135, 612</u>	LWR@doingstartpars	<u>334</u>
arabicfront (package)	<u>613</u>	LWR@doingtbrule	<u>406</u>
array (package)	<u>613</u>	LWR@dynamicmath	<u>316</u>
\arrayrulecolor	<u>6862</u>	LWR@emptyatbang	<u>406</u>
\arrayrulecolornexttoken	<u>6862</u>	LWR@exittingtabular	<u>457</u>
arydshln (package)	<u>614</u>	LWR@freezethisautoid	<u>482</u>
AsciiDoc (program)	<u>79</u>	LWR@indisplaymathimage	<u>506</u>
AsciiDoctor (program)	<u>79</u>	LWR@infloatarrow	<u>735</u>
Asciidoctor-LaTeX (program)	<u>79</u>	LWR@intabularmetadata	<u>406</u>
asymptote (package)	<u>616</u>	LWR@isstartingequation	<u>533</u>
atbegshi (package)	<u>616</u>	LWR@mathmacro	<u>315</u>
attachfile (package)	<u>617</u>	LWR@minipagefullwidth	<u>555</u>
attachfile2 (package)	<u>618</u>	LWR@minipagethispar	<u>556</u>
\attrib	<u>167, 388, 932</u>	LWR@opttablecol	<u>422</u>
\attribution	<u>6085</u>	LWR@origmathjax	<u>200</u>
authblk (package)	<u>134, 621</u>	LWR@skipatbang	<u>406</u>
\author	<u>122, 377</u>	LWR@skippingmcolrowcell	<u>406</u>
autosec	<u>360</u>	LWR@skippingmrowcell	<u>406</u>
axessibility (package)	<u>621</u>	LWR@starredlongtable	<u>449</u>
axodraw2 (package)	<u>622</u>	LWR@startedrow	<u>405</u>
B		LWR@tableparcell	<u>406</u>
babel (package)	<u>168</u>	LWR@tabularcelladded	<u>405</u>
\backmatter	<u>5477</u>	LWR@tabularmutemods	<u>457</u>
backref (package)	<u>622</u>	LWR@tracinglwarp	<u>227</u>
balance (package)	<u>622</u>	LWR@validtablecol	<u>420</u>
\BaseJobname	<u>4509</u>	LWR@verbtags	<u>390</u>
BaseJobname (option)	<u>111, 202</u>	mathjax	<u>200</u>
\bfseries	<u>10119</u>	usingOSWindows	<u>199</u>
\bibliography	<u>8575</u>	warpingHTML	<u>200</u>
\BibTeX	<u>10390</u>	warpingprint	<u>200</u>
bibunits (package)	<u>623</u>	WPMarkFloats	<u>178, 233</u>
bigdelim (package)	<u>163, 623</u>	WPMarkLOFT	<u>179, 234</u>
bigstrut (package)	<u>624</u>	WPMarkMath	<u>179, 234</u>
BlockClass (environment)	<u>4843</u>	WPMarkMinipages	<u>178, 233</u>
\BlockClassSingle	<u>4857</u>	WPMarkTOC	<u>178, 234</u>
blowup (package)	<u>625</u>	WPTitleHeading	<u>179, 234</u>
booklet (package)	<u>625</u>	bophook (package)	<u>628</u>
bookmark (package)	<u>626</u>	boxedminipage (package)	<u>628</u>
booktabs (package)	<u>626</u>	boxedminipage2e (package)	<u>628</u>
		\boxframe	<u>180</u>

breakurl (package)	629	\colorboxBlock	86, 9543	
breqn (package)	630	colortbl (package)	669	
BVerbatim (environment)	222	CombineHigherDepths (boolean)	114, 350	
bxpapersize (package)	631	comment (package)	206	
bytefield (package)	632	\ConTeXt	10387	
C				
calc (package)	219	continue (package)	671	
cancel (package)	632	copyrightbox (package)	671	
canoniclayout (package)	633	counters:		
capt-of (package)	487	FileDepth	114, 350	
caption (package)	164, 224, 487, 633	FootnoteDepth	115, 344	
caption2 (package)	636	lofdepth	494	
\caption@begin	8284	lotdepth	494	
\caption@end	8284	LWR@cellcolordepth	441	
\captionlistentry	8288	LWR@currentautosec	361	
\captionof	8319	LWR@externalfilecnt	506	
\CaptionSeparator	8232	LWR@hdashedlines	406	
cases (package)	637	LWR@hlines	405	
ccaption (package)	637	LWR@htmlfilenumber	319	
center (environment)	9454	LWR@latestautopage	484	
\centering	9478	LWR@lateXimagedepth	530	
\centerline	9497	LWR@lateXimagenumber	530	
changebar (package)	638	LWR@LIpage	530	
changepage (package)	638	LWR@midrulecounter	432	
chappg (package)	639	LWR@minipagedepth	555	
\chapter	5661	LWR@nextautoid	484	
chapterbib (package)	639	LWR@nextautopage	484	
chemfig (package)	640	LWR@nextequation	518	
chemformula (package)	641	LWR@prevFileDepth	361	
chemgreek (package)	646	LWR@previousautopagelabel	353	
chemmacros (package)	647	LWR@spandepth	334	
chemnum (package)	667	LWR@startingequation	533	
chkfloat (package)	668	LWR@tablecolsindex	407	
chngepage (package)	639	LWR@tablecolswidth	407	
cite (package)	668	LWR@tableLaTeXcolindex	408	
class (key) [Gin]	736	LWR@tablettotalLaTeXcols	408	
classss:		LWR@tablettotalLaTeXcolsnext	408	
internet	78	LWR@tabularDepth	406	
komascript	166	LWR@tabularpardepth	407	
memoir	166, 167, 933	LWR@thisautoid	482	
\cleardoublepage	10287	LWR@thisautoidWP	482	
\clearpage	10287	SideTOCDepth	114, 492	
cleveref (package)	131, 550	tocdepth	114	
clrdblpg (package)	668	\cpagerefFor	9682	
cm-super (package)	105	crop (package)	672	
cmap (package)	106	\CSSFilename	115, 118, 5072	
cmdtrack (package)	669	\CustomizeMathJax	5343, 5368	
color (package)	157, 669	cuted (package)	673	
\colorbox	73	cutwin (package)	673	

D	
\date	122
dblfloatfix (package)	674
dblfnote (package)	674
dcolumn (package)	674
\DeclareGraphicsExtensions	2
dejavu (package)	105
description (environment)	6381
diagbox (package)	675
\displaymathnormal	154, 505, 523, 9116
\displaymathother	154, 506, 523, 9127
\dotfill	10208
\doublerulesepcolor	6864
\doublerulesepcolornexttoken	6864
dprogress (package)	676
draftcopy (package)	677
draftfigure (package)	677
draftwatermark (package)	678
dvipdfm (option)	108, 204
dvipdfmx (option)	108, 204
dvips (option)	108, 204
 E	
easy-todo (package)	678
ebook (package)	679
ellipsis (package)	679
\emph	9993
emptypage (package)	680
\end@dblfloat	8195
\end@float	8195
endfloat (package)	680
endheads (package)	681
endnotes (package)	135, 681
\enlargethispage	10286
\enskip	574, 10232
enumerate (environment)	6362
enumerate (package)	682
enumitem (package)	682
environ (package)	219
environments:	
abstract	6075
align	127
align*	153
alignat	231
alignat*	257
BlockClass	4843
BVerbatim	222
center	9454
description	6381
enumerate	6362
eqnarray	9176
equation	9094
equation*	9102
fcolorminipage	161, 9584
flalign	179
flalign*	205
flushleft	9470
flushright	9462
fminipage	128, 9931
gather	75
gather*	101
itemize	6356
lateximage	528, 9324, 9449
list	6326
longtable	2
LWR@BlockClassWP	4880
LWR@blocktextcurrentfont	10111
LWR@displaymathnormal	8964
LWR@displaymathother	8969
LWR@equationother	8983
LWR@figcaption	8247
LWR@nestspan	4707
LWR@tabular	7803
math	8963
minipage	9761
multiline	20
multiline*	47
picture	553, 9742
quote	6101
tabbing	6185
thebibliography	8585
theindex	8498
titlepage	122, 5909
titlingpage	14, 122
verbatim	6175
verse	2, 6116
warpall	121, 230
warpHTML	117, 120, 121, 231
warpprint	117, 120, 231
epigraph (package)	683
epsfig (package)	684
epstopdf (package)	158, 685
epstopdf (program)	156, 544
epstopdf-base (package)	685
eqnarray (environment)	9176
equation (environment)	9094
equation* (environment)	9102
errata (package)	687
eso-pic (package)	688
\etalchar	135

etoolbox (package)	197	Flare (program)	79
everyhook (package)	218	float (package)	164, 708
everypage (package)	689	floatflt (package)	710
everyshi (package)	689	floatpag (package)	711
expl3 (package)	218	floatrow (package)	165, 711
extramarks (package)	689	fltrace (package)	717
		\flushbottom	4625
		flushend (package)	717
		flushleft (environment)	9470
		flushright (environment)	9462
		fminipage (environment)	128, 9931
		fnbreak (package)	718
		fncychap (package)	718
		fnlineno (package)	719
		fnpos (package)	719
		fontenc (package)	106, 719
		fontspec (package)	106, 720
		footmisc (package)	720
		footnote (package)	721
		FootnoteDepth (counter)	115, 344
		footnotehyper (package)	722
		footnpag (package)	723
FileDepth (counter)	114, 350	\ForceHTMLPage	134, 5452
files:		\ForceHTMLTOC	134, 5458
glyptounicode.tex	106	forest (package)	723
lwarf.css	119, 248	FormatEPUB (boolean)	174, 233
lwarf.ist	147, 287	FormatWP (boolean)	176, 233
lwarf.xdy	148, 288	\framebox	9884
lwarf_baseline_marker.eps . . .	507	framed (package)	724
lwarf_baseline_marker.png . . .	507	FrameMaker (program)	79
lwarf_formal.css	283	\frontmatter	5474
lwarf_mathjax.txt	290	ftnright (package)	726
lwarf_one_limage.cmd	289	fullminipage (package)	726
lwarf_sagebrush.css	277	fullpage (package)	727
lwarf_tutorial.txt	89	fullwidth (package)	727
lwarpmk.conf	247	\fup	10138
lwarpmk.lua	186	\fussy	4627
project.css	119	\fwlw (package)	727
project.lwarpmkconf	248		
project_html.tex	241		
sample_project.css	119, 287	G	
tutorial.tex	89	gather (environment)	75
FileSectionNames (boolean) . . .	115, 319	gather* (environment)	101
fix2col (package)	706	GELLMU (program)	78
fixme (package)	169, 706	geometry (package)	217, 728
fixmetodonotes (package)	707	getttitlestring (package)	218
flafter (package)	708	[Gin]:	
\flagverse	933	class (key)	736
flalign (environment)	179	GladTeX (program)	78
flalign* (environment)	205	glossaries (package)	135, 728
		glossary (package)	731

GlossaryCmd (option) . . .	<i>111, 135, 204, 728</i>	I	
glyptounicode.tex (file)	<i>106</i>	idxlayout (package)	<i>756</i>
graphics (package)	<i>155, 731</i>	\if@titlepage	<i>5887</i>
graphicx (package)	<i>155, 744</i>	ifoddpage (package)	<i>757</i>
grffile (package)	<i>157, 744</i>	ifplatform (package)	<i>198</i>
grid (package)	<i>745</i>	imakeidx (package)	<i>757</i>
grid-system (package)	<i>745</i>	\include	<i>815</i>
gridset (package)	<i>745</i>	\includegraphics	<i>271</i>
H			
hang (package)	<i>746</i>	indentfirst (package)	<i>762</i>
hanging (package)	<i>747</i>	InDesign (program)	<i>79</i>
Hevea (program)	<i>78</i>	index (package)	<i>762</i>
\hfill	<i>10204</i>	\InlineClass	<i>4868</i>
\HomeHTMLFilename	<i>4511</i>	\inlinemathnormal	<i>153, 505, 4475</i>
HomeHTMLFilename (option) . .	<i>108, 112, 203</i>	\inlinemathother	<i>153, 505, 4471</i>
\href	<i>8089</i>	inputenc (package)	<i>106, 764</i>
\hrulefill	<i>10206</i>	inputenx (package)	<i>106, 764</i>
\hskip	<i>125</i>	internet (class)	<i>78</i>
\hspace	<i>125, 574, 10240, 10270, 10276</i>	intopdf (package)	<i>764</i>
htlatex (program)	<i>78</i>	itemize (environment)	<i>6356</i>
\HTMLAuthor	<i>116, 123, 5098</i>	\itshape	<i>10124</i>
HTMLDebugComments (boolean) . .	<i>115, 227</i>	K	
\HTMLDescription	<i>116, 123, 5103</i>	\kern	<i>125</i>
\HTMLEntity	<i>4492</i>	keyfloat (package)	<i>165, 765</i>
\HTMLFilename	<i>4510</i>	keys:	
HTMLFilename (option)	<i>108, 112, 203</i>	[Gin]:	
\HTMLFirstPageTop	<i>116, 5060</i>	class	<i>736</i>
htmlglossary (option) [lwarpmk] .	<i>135, 728</i>	komascript (class)	<i>166</i>
HTMLIndexCmd (option)	<i>110, 203</i>	kvoptions (package)	<i>200</i>
\HTMLLanguage	<i>115, 5735</i>	L	
HTMLLatexCmd (option)	<i>108, 170, 203</i>	\l@chapter	<i>8482</i>
\HTMLleftmargini (length)	<i>167, 388, 389, 932</i>	\l@figure	<i>8489</i>
\HTMLPageBottom	<i>116, 377, 5066</i>	\l@paragraph	<i>8487</i>
\HTMLPageTop	<i>116, 5063</i>	\l@part	<i>8481</i>
\HTMLTitle	<i>115, 123, 5093</i>	\l@section	<i>8484</i>
\HMLUnicode	<i>4500</i>	\l@subparagraph	<i>8488</i>
\HTMLVleftskip (length)	<i>167, 388, 389, 932</i>	\l@subsection	<i>8485</i>
hypcap (package)	<i>748</i>	\l@subsubsection	<i>8486</i>
hypdestopt (package)	<i>749</i>	\l@table	<i>8490</i>
\hyperindexref	<i>8557</i>	\LaTeX	<i>10363</i>
hypernat (package)	<i>749</i>	\LaTeX2HTML (program)	<i>78</i>
hyperref (package)	<i>132, 475, 749</i>	\LaTeXe	<i>10363</i>
\hypertoc	<i>8445</i>	lateximage (environment)	<i>528, 9324, 9449</i>
\hypertocfloat	<i>8465</i>	\LateximageFontSizeScale	<i>9246</i>
hyperxmp (package)	<i>755</i>	\LateximageFontSizeName	<i>9245</i>
hyphenat (package)	<i>755</i>	latexmk (option)	<i>108, 112, 204</i>

layaureo (package)	767	lwarf (package)	108
layout (package)	767	lwarf-patch-komascript (package) .	963
leading (package)	768	lwarf-patch-memoir (package) . . .	965
\leftline	9496	lwarf.css (file)	119, 248
lengths:		lwarf.ist (file)	147, 287
\HTMLleftmargini	167, 388, 389, 932	lwarf.xdy (file)	148, 288
\HTMLvleftskip	167, 388, 389, 932	lwarf_baseline_marker.eps (file) . .	507
\LWR@cmidrulewidth	432	lwarf_baseline_marker.png (file) . .	507
\LWR@heavyrulewidth	432	lwarf_formal.css (file)	283
\LWR@lightrulewidth	432	lwarf_mathjax.txt (file)	290
\LWR@minipageheight	555	lwarf_one_limage.cmd (file)	289
\LWR@minipagewidth	555	lwarf_sagebrush.css (file)	277
\LWR@tempheight	575	lwarf_tutorial.txt (file)	89
\LWR@tempraise	575	[lwarpmk]:	
\LWR@tempwidth	575	htmlglossary (option)	135, 728
\LWR@thiscmidrulewidth	432	printglossary (option)	135, 728
\VerbatimHTMLWidth	389	lwarpmk (option)	111, 202, 292
\vleftmargini	167, 388, 932	lwarpmk (program)	186, 292
\vleftskip	167, 388, 932, 933	lwarpmk epstopdf (program) . .	156, 544
letltmacro (package)	198	lwarpmk pdf2svg (program) . .	156, 544
letterspace (package)	768	lwarpmk.conf (file)	247
letrine (package)	768	lwarpmk.lua (file)	186
LibreOffice (program)	79	\lwarfsetup	108
\linebreak	10280	\LWR@addbaselinemarker	8687
lineno (package)	769	\LWR@addcdashline	7133
\LinkHome	4564	\LWR@addcmidruletrim	7099
Linux (program)	120, 198	\LWR@addcmidrulewidth	7130
lips (package)	772	\LWR@addcompilecmd	1197
list (environment)	6326	\LWR@addformatwpalignment	7149
listings (package)	772	\LWR@addleftmostbartag	6934
\listof	8406	\LWR@addmathjax	9032
\listoffigures	8380	\LWR@addmulticolvertrulecolor . .	7408
\listoftables	8393	\LWR@addrulewidth	7104
lmodern (package)	105, 106	\LWR@addtabularcellcolor	7277
lofdepth (counter)	494	\LWR@addtabularhrulecolor	7177
longtable (environment)	2	\LWR@addtabulararrowcolor	7162
longtable (package)	162, 777	\LWR@addtabularrulecolors	7223
lotdepth (counter)	494	\LWR@afterendverbatim	6158
lscape (package)	779	\LWR@amsmathbody	9311
ltablex (package)	779	\LWR@amsmathbodynumbered	9317
ltcaption (package)	780	\LWR@amsmultiline (boolean)	524
ltxgrid (package)	780	\LWR@atbeginverbatim	6139
ltxtable (package)	780	\LWR@backgroundcolor	36
lua-check-hyphen (package)	781	\LWR@beginhideamsmath	9161
lua-visual-debug (package)	781	\LWR@blackborderpadding	9902
luacolor (package)	781	\LWR@BlockClassWP (environment) . .	4880
\LuaLaTeX	10381	\LWR@blocktextcurrentfont (environ-	
LuaLaTeX (program) [requirement]	82	ment)	10111
\LuaTeX	10381	\LWR@botnavigation	4570
luatodonotes (package)	168, 782	\LWR@cdashlines	432

LWR@cellcolordepth (counter)	<i>441</i>	LWR@externalfilecnt (counter)	<i>506</i>
\LWR@cellHTMLcolor	<i>6859</i>	\LWR@figcaption (environment)	<i>8247</i>
\LWR@clearmidrules	<i>7014</i>	\LWR@filenamenoblanks	<i>5254</i>
\LWR@closeparagraph	<i>4966</i>	\LWR@filestart	<i>5742</i>
\LWR@closeprevious	<i>4597</i>	\LWR@findcurrenttextcolor	<i>10152</i>
\LWR@closetabledatacell	<i>6493</i>	\LWR@findword	<i>715</i>
\LWR@cmidrulewidth (length)	<i>432</i>	\LWR@floatalignment	<i>8214</i>
LWR@colafterspec	<i>408</i>	\LWR@floatalignmentname	<i>8213</i>
LWR@colatsspec	<i>408</i>	\LWR@floatbegin	<i>8146</i>
LWR@colbangspec	<i>408</i>	\LWR@floatend	<i>8180</i>
LWR@colbarspec	<i>408</i>	\LWR@floatstyle	<i>2</i>
LWR@colbeforespec	<i>408</i>	\LWR@footnotetext	<i>5120</i>
\LWR@columnHTMLcolor	<i>6857</i>	\LWR@forceminwidth	<i>9891</i>
\LWR@columnspeclookahead	<i>6612</i>	\LWR@forcenewpage	<i>4614</i>
\LWR@compilecmd	<i>1194</i>	\LWR@formatted	<i>897</i>
\LWR@convertto	<i>66</i>	\LWR@formattedenv	<i>927</i>
LWR@copiedsidetoc (boolean)	<i>489</i>	\LWR@formatting	<i>896</i>
\LWR@copyfile	<i>850</i>	LWR@freezethisautoid (boolean)	<i>482</i>
\LWR@createautosec	<i>5483</i>	\LWR@futurenonamespacelet	<i>6440</i>
LWR@currentautosec (counter)	<i>361</i>	\LWR@FVstyle	<i>56</i>
\LWR@currentcss	<i>5071</i>	\LWR@getexpparray	<i>4444</i>
\LWR@currenttextcolor	<i>10149</i>	\LWR@getmynexttoken	<i>6447</i>
\LWR@customizedMathJax	<i>5342</i>	\LWR@hdashedlines (counter)	<i>406</i>
\LWR@customizeMathJax	<i>5348</i>	\LWR@heavyrulewidth (length)	<i>432</i>
\LWR@descitem	<i>6368</i>	\LWR@hidelateequation	<i>9018</i>
LWR@displaymathnormal (environment)		\LWR@hlines (counter)	<i>405</i>
.	<i>8964</i>	\LWR@HTML@caption@begin	<i>8263</i>
LWR@displaymathother (environment)	<i>8969</i>	\LWR@HTML@caption@end	<i>8275</i>
\LWR@docdashline	<i>7063</i>	\LWR@HTML@Gin@setfile	<i>114</i>
\LWR@docmidrule	<i>7047</i>	\LWR@HTML@ref	<i>8031</i>
\LWR@doequation	<i>9045</i>	\LWR@htmlblockcomment	<i>4793</i>
\LWR@doindexentry	<i>8541</i>	\LWR@htmlblocktag	<i>4795</i>
LWR@doingapar (boolean)	<i>334</i>	\LWR@HTMLcline	<i>7788</i>
LWR@doingcmidrule (boolean)	<i>406</i>	\LWR@htmclosecomment	<i>4765</i>
LWR@doingstartpars (boolean)	<i>334</i>	\LWR@htmlcomment	<i>4786</i>
LWR@doingtbrule (boolean)	<i>406</i>	\LWR@htmldivclass	<i>4820</i>
\LWR@domulticolumn	<i>7446</i>	\LWR@htmldivclassend	<i>4823</i>
\LWR@doubledollar	<i>8879</i>	\LWR@htmlelement	<i>4833</i>
LWR@dynamicmath (boolean)	<i>316</i>	\LWR@htmlelementclass	<i>4807</i>
\LWR@earlyloadnever	<i>272</i>	\LWR@htmlelementclassend	<i>4812</i>
LWR@emptyatbang (boolean)	<i>406</i>	\LWR@htmlelementclassline	<i>4826</i>
\LWR@endfloatalignment	<i>8228</i>	\LWR@htmlelementend	<i>4836</i>
\LWR@endhideamsmath	<i>9169</i>	LWR@htmlfilename (counter)	<i>319</i>
\LWR@endofline	<i>10215</i>	\LWR@htmlfileref	<i>7943</i>
\LWR@ensuredoingapar	<i>4942</i>	\LWR@HTMLhline	<i>7771</i>
LWR@equationother (environment)	<i>8983</i>	\LWR@HTMLLatexCmd	<i>1226</i>
\LWR@equationtag	<i>9297</i>	\LWR@htmlmathlabel	<i>9146</i>
LWR@exittingtabular (boolean)	<i>457</i>	\LWR@htmlmulticolumn	<i>7495</i>
\LWR@expandableformatted	<i>912</i>	\LWR@htmlopencomment	<i>4765</i>
\LWR@expandableformattedenv	<i>937</i>	\LWR@htmirefsectionfilename	<i>4554</i>

\LWR@HTMLsanitize	9249	\LWR@minipagestartpars	10220
\LWR@HTMLsanitizeexpand	9266	\LWR@minipagestoppars	10223
\LWR@htmlsectionfilename	4521	\LWR@minipagethispar (boolean)	556
\LWR@htmllspan	4742	\LWR@minipagewidth (length)	555
\LWR@htmllspanclass	4750	\LWR@multicolother	7349
\LWR@htmlltag	4760	\LWR@multicolpartext	7343
\LWR@htmlltagc	4696	\LWR@multicolskip	7355
\LWR@HTMLtextstyle	9988	\LWR@multirowborder	3
\LWR@hyperindexrefnullified	8546	\LWR@mynexttoken	6439
\LWR@imagesizebox	113	\LWR@myshorttoc	8329
\LWR@includegraphicsb	131	\LWR@nameref	7940
\LWR@indexitem	8510	\LWR@nestspan (environment)	4707
\LWR@indexnameref	8540	\LWR@new@label	7980
\LWR@indexsubitem	8514	\LWR@newautoidanchor	8201
\LWR@indexsubsubitem	8518	\LWR@newautopagelabel	5334
\LWR@indisplaymathimage (boolean) ..	506	\LWR@newhtmlfile	5371
\LWR@infloatrow (boolean)	735	\LWR@nextautoid (counter)	484
\LWR@instertatbangcols	6485	\LWR@nextautopage (counter)	484
\LWR@intabularmetadata (boolean) ..	406	\LWR@nextequation (counter)	518
\LWR@isstartingequation (boolean) ..	533	\LWR@notmemoirloadafter	252
\LWR@itemizeitem	6349	\LWR@nullfonts	10058
\LWR@latestautopage (counter)	484	\LWR@nullifyNoAutoSpacing	7790
\LWR@lateximagedepth (counter)	530	\LWR@nulllistfills	6318
\LWR@lateximagedepthref	7946	\LWR@opacity	112
\LWR@lateximagenumber (counter)	530	\LWR@openparagraph	4948
\LWR@lateximagenumberref	7949	\LWR@opttablecol (boolean)	422
\LWR@lateximagesfile	812	\LWR@origcolspec	6479
\LWR@latexmkcmd	1212	\LWR@originname	285
\LWR@latexmkdvipdfm	1217	\LWR@originnames	292
\LWR@latexmkvar	1206	\LWR@origmathjax (boolean)	200
\LWR@lightrulewidth (length)	432	\LWR@overline	10144
\LWR@LIpage (counter)	530	\LWR@parseaftercolumn	6682
\LWR@listitem	6311	\LWR@parseatcolumn	6622
\LWR@loadafter	241	\LWR@parsebangcolumn	6648
\LWR@loadbefore	255	\LWR@parsebarcolumn	6693
\LWR@loadnever	264	\LWR@parsebeforecolumn	6671
\LWR@longtabledatacaptiontag	7506	\LWR@parsecoloncolumn	6718
\LWR@lookforpackagename	718	\LWR@parseDcolumn	6764
\LWR@l warpconfversion	1188	\LWR@parsedrequirepackagenames ..	714
\LWR@L warpEnd	5863, 10417	\LWR@parsenormalcolumn	6743
\LWR@L warpStart	5792, 10417	\LWR@parsepcolumn	6755
\LWR@maketitlesetup	33, 5981	\LWR@parsesemicoloncolumn	6739
\LWR@mathmacro (boolean)	315	\LWR@parsetablecols	6770
\LWR@maybenewtablerow	6866	\LWR@parsewcolumn	6759
\LWR@maybeprintpendingfootnotes	5194	\LWR@patcherror	67
\LWR@midrulecounter (counter)	432	\LWR@patchlists	6387
\LWR@midrules	431	\LWR@prevFileDepth (counter)	361
\LWR@minipagedepth (counter)	555	\LWR@previousautopagelabel (counter) ..	353
\LWR@minipagefullwidth (boolean) ..	555	\LWR@printatbang	6909
\LWR@minipageheight (length)	555	\LWR@printbartag	6899

\LWR@printcloselist	6218	\LWR@startpars	5015
\LWR@PrintLatexCmd	1226	\LWR@startref	7993
\LWR@printlength	696	\LWR@stopars	5033
\LWR@printmcldata	7358	\LWR@stripperiod	7917
\LWR@printmcctype	7301	\LWR@strresult	6477
\LWR@printopenlist	6219	\LWR@subaddcmidruletrim	7086
\LWR@printpendingfootnotes	5184	\LWR@subaddtabularcellcolor	7271
\LWR@printpendingmpfootnotes	5203	\LWR@subcdashline	7050
\LWR@printthetitle	5933	\LWR@subcmidrule	7032
\LWR@providelength	63	\LWR@subhtmelementclass	4800
\LWR@ProvidesPackageDrop	793	\LWR@subhyperref	8065
\LWR@ProvidesPackagePass	782	\LWR@subhyperrefclass	8078
\LWR@pushoneclose	5486	\LWR@subhyperreftext	8073
\LWR@quickfile	809	\LWR@subinlineimage	8139
\LWR@ref@ignorestar	8039	\LWR@sublabel	7957
\LWR@remembertag	9301	\LWR@subnewref	8025
\LWR@replaceEPSSVG	120	\LWR@subsingledollar	8723
\LWR@requesttoc	5856	\LWR@subtableofcontents	8342
\LWR@requirepackagenames	713	\LWR@subtabularhtmlcolumns	7576
\LWR@restoreorigaccents	1145	\LWR@syncmathjax	8998
\LWR@restoreorigformatting	8604	LWR@tablecolspect	407
\LWR@restoreoriglists	6415	LWR@tablecolspectindex (counter)	407
\LWR@rotboxorigin	284	LWR@tablecolspectwidth (counter)	407
\LWR@rotstyle	104	\LWR@tabledatacolumnntag	7667
\LWR@rowHTMLcolor	6858	\LWR@tabledatasinglecolumnntag	6948
\LWR@ruleHTMLcolor	6860	LWR@tableLaTeXcolindex (counter)	408
\LWR@sanitize	4482	LWR@tableparcell (boolean)	406
\LWR@sanitized	4481	LWR@tabletotalLaTeXcols (counter)	408
\LWR@scalestyle	107	LWR@tabletotalLaTeXcolsnext (counter)	408
\LWR@section	5500	LWR@tabular (environment)	7803
\LWR@sectionnumber	5480	LWR@tabularcelladded (boolean)	405
\LWR@select@html@hspace	10240	LWR@tabularDepth (counter)	406
\LWR@select@html@nohspace	10270	\LWR@tabularendofline	6592
\LWR@select@print@hspase	10273	\LWR@tabularfinishrow	6546
\LWR@setexparray	4438	\LWR@tabularhtmlcolumns	7586
\LWR@setlatestname	7918	\LWR@tabularleftedge	6939
\LWR@setOSWindows	96	LWR@tabularmutemods (boolean)	457
\LWR@shellescapecmd	1189	LWR@tabularpardepth (counter)	407
\LWR@sidetoc	8422	\LWR@tdaddstyle	7074
\LWR@singledollar	8903	\LWR@tdendstyles	7080
LWR@skipatbang (boolean)	406	\LWR@tdstartstyles	7073
LWR@skippingmcolrowcell (boolean)	406	\LWR@tempcolor	10150
LWR@skippingmrowcell (boolean)	406	\LWR@tempcolorortwo	10150
LWR@spandepth (counter)	334	\LWR@temphight (length)	575
\LWR@splabel	7952	\LWR@tempraise (length)	575
LWR@starredlongtable (boolean)	449	\LWR@tempwidth (length)	575
LWR@startedrow (boolean)	405	\LWR@textcurrentcolor	19, 10155
LWR@startingequation (counter)	533	\LWR@textcurrentfont	10103
\LWR@startingequationtag	9296	\LWR@thisautoid (counter)	482

\LWR@thisautoidWP (counter)	482	mathjax (option)	108, 112, 201
\LWR@thiscmidrulewidth (length)	432	mathsvg (option)	108, 112, 201
\LWR@thiscolspec	6947	\mbox	9859
\LWR@thisfilename	5252	mcaption (package)	786
\LWR@thisnewfilename	5253	\mcolrowcell	7742
\LWR@titlingmaketitle	83, 6032	mdframed (package)	130, 787
\LWR@topnavigation	4567	\mdseries	10118
\LWR@traceinfo	878	memhfixc (package)	797
\LWR@tracingl warp (boolean)	227	memoir (class)	166, 167, 933
\LWR@trimlrules	432	metalogo (package)	797
\LWR@trimrrules	432	mhchem (package)	798
\LWR@unknownenGINE	1201	microtype (package)	217, 800
\LWR@validtablecol (boolean)	420	midfloat (package)	801
\LWR@verbtags (boolean)	390	midpage (package)	801
\LWR@vspace	10277	\MiKTeX	10397
\LWR@WPcell	7145	minipage (environment)	9761
\LWR@writeconf	1322	\minipagewidth	9753
\LWR@xcolorrowHTMLcolor	6856	morefloats (package)	802
\LWRopquote	91	moreverb (package)	802
\LWRopseq	92	morewrites (package)	803
\LWRPrintStack	4575	mparhack (package)	804
\LWRsetnextfloat	8241	\mrowcell	7739
\LyX	10398	MS-Windows (program)	120, 198
M			
Mac OS (program)	120, 198	multicol (package)	804
Madcap (program)	79	\multicolumnrow	39, 7609
magaz (package)	784	\multirow	806
\mainmatter	5470	multirow (package)	805
make (program)	173	multitoc (package)	808
\makebox	9862	multiline (environment)	20
makeidx (package)	149, 150, 784, 912, 913	multiline* (environment)	47
\MakeIndex	10390	N	
makeindex (option)	108, 112, 204	\Nameref	8057
makeindex (program)	147	\nameref	8048
makeindexStyle (option)	108, 148, 202	nameref (package)	809
\makelabel	394	natbib (package)	809
\maketitle	47, 122, 5993	nccfancyhdr (package)	810
marginfit (package)	785	needspace (package)	811
marginfix (package)	785	newclude (package)	167, 811
marginnote (package)	786	\newfloat	4
\marginpar	126, 349, 5215	newfloat (package)	219
\marginparBlock	126, 349, 5226, 5243	\newline	10213
\markboth	4622	\newpage	10210
\markright	4623	\newtheorem	392
math (environment)	8963	newtxmath (package)	155
\mathimagename	116, 8674	newunicodechar (package)	106, 811
MathJax (program)	152, 503, 504	nextpage (package)	812
MathJax (program) [requirement]	82	nicefrac (package)	155, 812
mathjax (boolean)	200	\noalign	7760
		\nolinebreak	10281

\nolinkurl	8105	\OSPathSymbol	95
nonfloat (package)	813	OSWindows (option)	111, 120, 198, 203
nonumonpart (package)	813	overpic (package)	159, 827
\nopagebreak	10285		
\nopagecolor	72		
nopageno (package)	813	\packagediagramname	117, 8675
\normalfont	10126	packages:	
\normalmarginpar	5240	2up	586
nowidow (package)	814	a4	586
ntheorem (package)	154, 814	a4wide	586
\numberline	8440	a5comb	587
numindex (option) [tocbibind]	150, 913	abstract	134, 587
		accsupp	589
		acro	590
		acronym	591
		addlines	594
		adjmulticol	593
		ae	594
		aecc	594
		afterpage	595
		algorithm2e	595
		algorithmicx	599
		algorithmx	164
		alltt	600
		amsmath	601
		amsthm	607
		anonchap	611
		any size	612
		appendix	135, 612
		arabicfront	613
		array	613
		arydshln	614
		asymptote	616
		atbegshi	616
		attachfile	617
		attachfile2	618
		authblk	134, 621
		axessibility	621
		axodraw2	622
		babel	168
		backref	622
		balance	622
		bibunits	623
		bigdelim	163, 623
		bigstrut	624
		blowup	625
		booklet	625
		bookmark	626
		booktabs	626
		bophook	628

boxedminipage	628	ellipsis	679
boxedminipage2e	628	emptypage	680
breakurl	629	endfloat	680
breqn	630	endheads	681
bxpaperize	631	endnotes	135, 681
bytefield	632	enumerate	682
calc	219	enumitem	682
cancel	632	environ	219
canoniclayout	633	epigraph	683
capt-of	487	epsfig	684
caption	164, 224, 487, 633	epstopdf	158, 685
caption2	636	epstopdf-base	685
cases	637	errata	687
ccaption	637	eso-pic	688
changebar	638	etoolbox	197
changepage	638	everyhook	218
chappg	639	everypage	689
chapterbib	639	everyshi	689
chemfig	640	expl3	218
chemformula	641	extramarks	689
chemgreek	646	fancybox	129, 690
chemmacros	647	fancyhdr	696
chemnum	667	fancyheadings	696
chkfloat	668	fancyref	697
chngpage	639	fancytabs	698
cite	668	fancyvrb	698
cleveref	131, 550	figcaps	705
clrdblp	668	figsize	705
cm-super	105	filecontents	218
cmap	106	fix2col	706
cmdtrack	669	fixme	169, 706
color	157, 669	fixmetodonotes	707
colortbl	669	flafter	708
comment	206	float	164, 708
continue	671	floatflt	710
copyrightbox	671	floatpag	711
crop	672	floatrow	165, 711
cuted	673	fltrace	717
cutwin	673	flushend	717
dblfloatfix	674	fnbreak	718
dblfnote	674	fncychap	718
dcolumn	674	fnlineno	719
dejavu	105	fnpos	719
diagbox	675	fontenc	106, 719
dprogress	676	fontspec	106, 720
draftcopy	677	footmisc	720
draftfigure	677	footnote	721
draftwatermark	678	footnotehyper	722
easy-todo	678	footnpag	723
ebook	679	forest	723

framed	724	ltxtable	780
ftnright	726	lua-check-hyphen	781
fullminipage	726	lua-visual-debug	781
fullpage	727	luacolor	781
fullwidth	727	luatodonotes	168, 782
fwlw	727	lwarp	108
geometry	217, 728	lwarp-patch-komascript	963
getttitlestring	218	lwarp-patch-memoir	965
glossaries	135, 728	magaz	784
glossary	731	makeidx	149, 150, 784, 912, 913
graphics	155, 731	marginifit	785
graphicx	155, 744	marginfix	785
grffile	157, 744	marginnote	786
grid	745	mcaption	786
grid-system	745	mdframed	130, 787
gridset	745	memhfixc	797
hang	746	metalogo	797
hanging	747	mhchem	798
hypcap	748	microtype	217, 800
hypdestopt	749	midfloat	801
hypernat	749	midpage	801
hyperref	132, 475, 749	morefloats	802
hyperxmp	755	moreverb	802
hyphenat	755	morewrites	803
idxlayout	756	mparhack	804
ifoddpage	757	multicol	804
ifplatform	198	multirow	805
imakeidx	757	multitoc	808
indentfirst	762	nameref	809
index	762	natbib	809
inputenc	106, 764	nccfancyhdr	810
inputenx	106, 764	needspace	811
intopdf	764	newclude	167, 811
keyfloat	165, 765	newfloat	219
kvoptions	200	newtxmath	155
layaureo	767	newunicodechar	106, 811
layout	767	nextpage	812
leading	768	nicefrac	155, 812
letltxmacro	198	nonfloat	813
letterspace	768	nonumonpart	813
lettrine	768	nopageno	813
lineno	769	nowidow	814
lips	772	ntheorem	154, 814
listings	772	overpic	159, 827
lmodern	105, 106	pagegrid	828
longtable	162, 777	pagenote	135, 828
lscape	779	pagesel	828
ltablex	779	paralist	828
ltcaption	780	parnotes	829
ltxgrid	780	parskip	830

pbox	830	setspace	860
pdflscape	831	shadow	861
pdfpages	831	showidx	862
pdfprivacy	834	showkeys	862
pdfrender	834	sidecap	862
pdfsync	834	sidenotes	863
pdftricks	158, 835	SIunits	865
pdfx	836	siunitx	155, 543, 865
perltex	172	soul	871
pfnote	836	soulpos	873
phfqit	836	soulutf8	873
placeins	837	splitidx	874
polyglossia	168	srcctx	875
prelim2e	837	srctex	876
prettyref	837	stabular	876
preview	838	stffloats	877
printlen	220	subcaption	164
psfrag	159, 838	subfig	165, 877
psfragx	839	subfigure	882
pst-eps	839	supertabular	163, 883
pstool	159, 840	sympytex	173
pstricks	158, 841	syntonly	885
pythontex	172	t1enc	885
quotchap	841	tabls	885
quoting	842	tabularx	886
ragged2e	843	tabulary	886
realscripts	843	textarea	887
refcheck	844	textcomp	106, 125, 887
refcount	219	textfit	890
register	845	textpos	891
relsize	126, 845	theorem	891
repeatindex	847	thinsp	895
resizegather	848	threadcol	896
romanbar	848	threeparttable	896
romanbarpage number	848	thumb	897
rotating	849	thumbs	897
rotfloat	849	tikz	157, 898
rterface	173	titleps	899
sagetex	172	titleref	903
savetrees	850	titlesec	903
scalefnt	851	titletoc	905
schemata	851	titling	134, 907
scrextend	851	tocbasic	912
scrhack	854	tocbibind	150, 912, 913
scrlayer	855	toccenter	914
scrlayer-notecolumn	856	tocloft	134, 150, 611, 915
scrlayer-scrpage	857	tocstyle	921
section	858	todo	922
sectionbreak	859	todonotes	168, 923
sectsty	859	transparent	925

trimclip	925	\pagestyle	4620
trivfloat	164, 926	Pandoc (program)	79
turnthepage	927	\paragraph	5717
typearea	927	paralist (package)	828
ulem	928	\parbox	9850
underscore	930	parnotes (package)	829
units	155, 931	\parsemulticolumnalignment	7393
upref	931	parskip (package)	830
url	132, 931	\part	5648
uspace	932	pbox (package)	830
varioref	131	pdfcrop (program) [requirement]	82
varwidth	220	pdfLaTeX (program) [requirement]	82
verbatim	219	pdflscape (package)	831
verse	167, 932, 933	pdfpages (package)	831
vertbars	934	pdfprivacy (package)	834
vmargin	934	pdfrender (package)	834
vowel	935	pdfseparate (program) [requirement]	82, 87
vpe	936	pdfsync (package)	834
vwcol	936	pdftocairo (program)	156, 544
wallpaper	938	pdftocairo (program) [requirement]	82, 87
wasysym	939	pdftotext (program) [requirement]	82, 87
watermark	939	pdftotextEnc (option)	111, 202
widows-and-orphans	939	pdftricks (package)	158, 835
wrapfig	940	pdfx (package)	836
xbmks	941	perl (program) [requirement]	88
xcolor	157, 546, 941	perltex (package)	172
xellipsis	952	pfnote (package)	836
xfrac	953	\phantomsection	10343
xifthen	219	phfqt (package)	836
xltabular	956	picture (environment)	553, 9742
xltxtra	956	placeins (package)	837
xmpincl	957	Plastex (program)	78
xparse	169, 218	\PN@parnotes@auto	4947
xpatch	198	polyglossia (package)	168
xpiano	957	\popclose	4411
xstring	219	prelim2e (package)	837
xtab	163, 958	prettyref (package)	837
xunicode	960	preview (package)	838
xurl	960	\printauthor	377, 5941, 5960
xy	960	\printdate	377, 5952, 5962
zref	220	printglossary (option) [lwarpmk]	135, 728
zwpagelayout	961	\printindex	2
\pagebreak	10282	PrintIndexCmd (option)	110, 203
\pagecolor	71	PrintLatexCmd (option)	108, 170, 203
pagegrid (package)	828	printlen (package)	220
pagenote (package)	135, 828	\printthanks	377, 379
\pagenumbering	4628	\printtitle	377, 5925, 5959
\pageref	8043		
\pagerefPageFor	8042		
pagesel (package)	828		

programs:	
[requirement]:	
LuaTeX	82
MathJax	82
pdfcrop	82
pdfLaTeX	82
pdfseparate	82, 87
pdftocairo	82, 87
pdftotext	82, 87
perl	88
XeLaTeX	82
Adobe	79
AsciiDoc	79
AsciiDoctor	79
Asciidoctor-LaTeX	79
epstopdf	156, 544
Flare	79
FrameMaker	79
GELLMU	78
GladTeX	78
Hevea	78
htlatex	78
InDesign	79
LaTeX2HTML	78
latexmk	172
LaTeXML	78
LibreOffice	79
Linux	120, 198
lwarpmk	186, 292
lwarpmk epstopdf	156, 544
lwarpmk pdftosvg	156, 544
Mac OS	120, 198
Madcap	79
make	173
makeindex	147
MathJax	152, 503, 504
MS-Windows	120, 198
OpenOffice	79
Pandoc	79
pdftocairo	156, 544
Plastex	78
TeX2page	78
TeX4ht	78
TeXMaths	179
TtH	78
Unix	120, 198
Windows	120, 198
Word	79
xindy	148
project.css (file)	119
project.lwarpmkconf (file)	248
project_html.tex (file)	241
psfrag (package)	159, 838
psfragx (package)	839
pst-eps (package)	839
pstool (package)	159, 840
pstricks (package)	158, 841
\pushclose	4384
pythontex (package)	172
Q	
\qqquad	574, 10231
\quad	574, 10226
quotchap (package)	841
quote (environment)	6101
quoting (package)	842
R	
ragged2e (package)	843
\raggedbottom	4624
\raggedleft	9484
\raggedright	9490
\raisebox	9979
realscripts (package)	843
\ref	8031
refcheck (package)	844
refcount (package)	219
\reflectbox	338
register (package)	845
relsize (package)	126, 845
repeatindex (package)	847
[requirement]:	
LuaTeX (program)	82
MathJax (program)	82
pdfcrop (program)	82
pdfLaTeX (program)	82
pdfseparate (program)	82, 87
pdftocairo (program)	82, 87
pdftotext (program)	82, 87
perl (program)	88
XeLaTeX (program)	82
\RequirePackage	746
\resizebox	347
\resizegather (package)	848
\ResumeTabular	7654
\reversemarginpar	5239
\rightline	9498
\rmfamily	10120
romanbar (package)	848
romanbarpagenumber (package)	848

\rotatebox	304	\StartDefiningTabulars	4449
rotating (package)	849	stfloats (package)	877
rotfloat (package)	849	\StopDefiningMath	4463
\rowcolor	6861	\StopDefiningTabulars	4453
\rownum	6853	subcaption (package)	164
rterface (package)	173	subfig (package)	165, 877
\rule	10289	subfigure (package)	882
S			
sagetex (package)	172	\subparagraph	5725
sample_project.css (file)	119, 287	\subsection	5700
savetrees (package)	850	\subsubsection	5708
\sb	10128	supertabular (package)	163, 883
\scalebox	323	sympytex (package)	173
scalefnt (package)	851	syntonly (package)	885
schemata (package)	851	T	
scrextend (package)	851	t1enc (package)	885
scrhack (package)	854	tabbing (environment)	6185
scrlayer (package)	855	\tableofcontents	116, 8361
scrlayer-notecolumn (package)	856	tabls (package)	885
scrlayer-scrpage (package)	857	\TabularMacro	7652
\scshape	10125	tabularx (package)	886
\section	5687	tabulary (package)	886
section (package)	858	\TeX	10351
sectionbreak (package)	859	\TeX2page (program)	78
sectsty (package)	859	\TeX4ht (program)	78
\SetHTMLFileName	4512	\TeXMaths (program)	179
setspace (package)	860	textarea (package)	887
\sffamily	10121	\textbf	10002
\sfrac	953	\textcolor	48
shadow (package)	861	textcomp (package)	106, 125, 887
showidx (package)	862	textfit (package)	890
showkeys (package)	862	\textgreater	4502
sidecap (package)	862	\textit	10027
sidenotes (package)	863	\textless	4502
SideTOCDepth (counter)	114, 492	\textmd	9996
\sidetocname	8419	\textnormal	10044
\simplechapterdelim	5497	\textpos (package)	891
SIunits (package)	865	\textrm	10005
siunitx (package)	155, 543, 865	\textsc	10030
\sloppy	4626	\textsf	10012
soul (package)	871	\textsl	10037
soulpos (package)	873	\textsubscript	10131
soulutf8 (package)	873	\textsuperscript	10129
\sp	10127	\texttt	10017
splitidx (package)	874	\textup	10020
srcltx (package)	875	\tfl@chapter@fix	926
srctex (package)	876	\thanks	122
stabular (package)	876	\thanksmarkseries	91
\StartDefiningMath	4459	\theauthor	377
		thebibliography (environment)	8585

\thedata	377	upref (package)	931
theindex (environment)	8498	\upshape	10123
\thempfootnote	5181	\url	8122
theorem (package)	891	url (package)	132, 931
\thetitle	377	usingOSWindows (boolean)	199
thinsp (package)	895	uspace (package)	932
\thispagestyle	4621		
threadcol (package)	896		
threeparttable (package)	896	V	
thumb (package)	897	varioref (package)	131
thumbs (package)	897	varwidth (package)	220
tikz (package)	157, 898	verbatim (environment)	6175
\title	122, 5082	verbatim (package)	219
titlepage (environment)	122, 5909	\VerbatimHTMLWidth (length)	389
titleps (package)	899	\verbatimininput	6167
titleref (package)	903	verse (environment)	2, 6116
titles (option) [tocloft]	134	verse (package)	167, 932, 933
titlesec (package)	903	vertbars (package)	934
titletoc (package)	905	\vleftmargini (length)	167, 388, 932
titling (package)	134, 907	\vleftskip (length)	167, 388, 932, 933
titlingpage (environment)	14, 122	vmargin (package)	934
tocbasic (package)	912	vowel (package)	935
[tocbibind]:		vpe (package)	936
numindex (option)	150, 913	vwcol (package)	936
tocbibind (package)	150, 912, 913		
tocdepth (counter)	114	W	
toccenter (package)	914	wallpaper (package)	938
[tocloft]:		warpall (environment)	121, 230
titles (option)	134	warpHTML (environment)	117, 120, 121, 231
tocloft (package)	134, 150, 611, 915	warpHTML (option)	111, 201
tocstyle (package)	921	\warpHTMLonly	117, 121, 220
todo (package)	922	warpingHTML (boolean)	200
todonotes (package)	168, 923	warpingprint (boolean)	200
\tracingl warp	191, 877	warpprint (environment)	117, 120, 231
transparent (package)	925	warpprint (option)	111, 201
trimclip (package)	925	\warpprintonly	117, 121, 219
trivfloat (package)	164, 926	wasysym (package)	939
\ttfamily	10122	watermark (package)	939
TtH (program)	78	widows-and-orphans (package)	939
turnthepage (package)	927	Windows (program)	120, 198
tutorial.tex (file)	89	Word (program)	79
typearea (package)	927	WPMarkFloats (boolean)	178, 233
		WPMarkLOFT (boolean)	179, 234
		WPMarkMath (boolean)	179, 234
		WPMarkMinipages (boolean)	178, 233
ulem (package)	928	WPMarkTOC (boolean)	178, 234
\underline	10139	WPTitleHeading (boolean)	179, 234
underscore (package)	930	wrapfig (package)	940
units (package)	155, 931		
Unix (program)	120, 198	X	
\up	10137	xbmks (package)	941

xcolor (package)	<i>157, 546, 941</i>	xltxtra (package)	<i>956</i>
\XeLaTeX	<u>10383</u>	xmpincl (package)	<i>957</i>
XeLaTeX (program) [requirement]	<i>82</i>	xparse (package)	<i>169, 218</i>
xellipsis (package)	<i>952</i>	xpatch (package)	<i>198</i>
\XeTeX	<u>10383</u>	xpiano (package)	<i>957</i>
xfrac (package)	<i>953</i>	xstring (package)	<i>219</i>
\xfracHTMLfontsize	<i>3</i>	xtab (package)	<i>163, 958</i>
xifthen (package)	<i>219</i>	xunicode (package)	<i>960</i>
xindy (option)	<i>108, 112, 204</i>	xurl (package)	<i>960</i>
xindy (program)	<i>148</i>	xy (package)	<i>960</i>
xindyCodepage (option)	<i>110, 202</i>		Z
xindyLanguage (option)	<i>110, 202</i>	zref (package)	<i>220</i>
xindyStyle (option)	<i>108, 148, 202</i>	zwpagelayout (package)	<i>961</i>
xtabular (package)	<i>956</i>		

General Index

This is an index of instructions and concepts. Look here when wondering how to do something, and check the Troubleshooting Index when something goes wrong.

Entries in **bold** are package, class, or program names.

Symbols	
\,	125
~,	125
A	
accents	
in section & file names	358
adapting	
class	185
document	104
package	184
affiliation	
multiple authors	133
algorithms	
with newfloat , trivfloat	927
array	
mhchem	798
author	
HTML meta tag	123, 342
multiple	133
B	
baseline	
tabular	421
bitmapped fonts	105
bugs	187
C	
Calibre	174
chemistry	
Greek symbols	646
class	
modifying for lwrap	185
code listings	124
compiling	
custom	170
Computer Modern	105
converting	
class	185
document	104
package	184
CSS	
file selection	118
lwrap.css	119
per HTML page	118
project-specific changes	119
D	
danger icon	194
debugging	187
HTML debug comments	227
tracing log	227
Deja Vu	105
description	
HTML meta tag	123, 343
display math	
complicated objects	154
document	
convert existing	104
DVI TeX	100, 105
dynamic math	153, 154
dynamic math expressions	315
E	
EPS image	
converting	102
using	155, 544
EPUB	
conversion software	174
HTML conversion settings	174, 233
error messages	187
export	
to word processor	176
F	
FAQ	187

file	
accent in name	358
hashed name	508, 535
underscore in name	112, 126
unique names	115
font	
Computer Modern	105
Deja Vu	105
ligatures	106
packages	106
selection	105
size — xfrac	954
size — lateimage	151, 503, 530
size — math , SVG	151, 503, 530
type 1 vector	105
type 3 bitmapped	105
footnotes	343
framed objects	128
Frequently Asked Questions	187
G	
generator	
HTML meta tag	370
GIF images	156, 545
glossary	
language	135
options	135
processing	101
graphics	
formats	155, 544
Greek	
chemistry symbols	646
H	
hash	
SVG image filename	508, 535
heading, word processor	179
horizontal space	125
between minipages	574
HTML	
conversion settings	112
debug comments	227
EPUB	174, 233
word processor	176, 233
conversion suggestions	123
entities, conversion	124
filename generation	117
headings	193
meta tag	
author	123, 342
description	123, 343
generator	370
title	123, 342
viewport	370
selecting print/HTML definitions ..	228
tabular column conversion	421
verbatim, in	124
hyperref	
and xindy	137
I	
icon	
warning	194
image	
GIF	156, 545
graphicx package	544
hashed filename	508, 535
PDF or EPS	
converting	102, 156, 545
using	155, 544
PNG and JPG	156, 545
processing	292
\includegraphics	
using	155, 544
index	
custom makeindex style file	147
custom xindy style file	148
custom display styles	149
letter headings	758
placement and toc options ..	149, 912
processing	93, 94, 137
see, <i>seealso</i> , ranges	137
source code	137
table of contents	149, 912
UTF-8	107
xindy and hyperref	137
inline math	
complicated objects	153
item	
empty	393
J	
JAVASCRIPT	
MATHJAX	150, 502
JPG images	156, 545
L	
label	
in HTML	373
math environment	525

language	
glossary	135
language HTML metadata	369
latextimage	
font size	151, 503, 530
processing	292
Latin Modern font	105
LIBREOFFICE	
conversion recommendations	179
import into	176
section headings	179
ligatures	106, 217
line numbers	194
list	
empty item	393
filename	126
listings, program code	124
Lua ^{LT} X	
detection	195
file & section names	358
lwarf	
loading	108
options	108
lwarf.ist	
customizing	147
lwarf.xdy	
customizing	148
lwarfpmk	
customizing	186
M	
make utility	173
makeindex	
customizing	147
margin	
numbers	194
tags	194
markup languages	79
math	
mathjax option	201
mathsvg option	201
mhchem	798
display with complicated objects	154
dynamic	153, 154, 315
font size — SVG	151, 503, 530
inline with complicated objects	153
MATHJAX custom functions	152, 504
MATHJAX summary	152, 503
SVG summary	151, 503
word processor conversion	179
N	
newfloat	
with trivfloat, algorithmic	927
numbers	
left margin	194
P	
package	
modifying for lwarf	184
required	216
\par	
hooks	338
PDF image	
converting	102
using	155, 544
PERL	88
PNG images	156, 545
POPLER	82, 87
print	
selecting print/HTML definitions	228
problems	187
program listings	124
programs	
utility	81

\published	385	troubleshooting	187
		HTML debug comments	227
		tracing log	227
		type 1 vector fonts	105
		type 3 bitmapped fonts	105
		U	
		underscore	
		filename	112, 126
		Unicode	
		enhanced coverage	105
		file & section names	358
		input characters	196
		selection	105
		UTF-8	
		enhanced coverage	105
		file & section names	358
		index	107
		selection	105
		utility	
		programs	81
		V	
		vector fonts	105
		verbatim	
		code and HTML tags	124
		viewport	
		HTML meta tag	370
		W	
		warning icon	194
		word processor	
		conversion recommendations	179
		HTML conversion settings	176, 233
		section headings	179
		X	
		Xe ^L T _E X	
		detection	195
		file & section names	358
		xindy	
		and hyperref	137
		customizing	148
		xparse	
		warnings	169

Troubleshooting Index

This index is a sorted reference of problems and solutions. In order to make it easier to locate a solution, the same issue may be addressed by more than one entry.

Entries with higher page numbers are often duplicates of entries with lower page numbers, as the same warning may occur within the user manual and again within the source code for a given package.

Entries in **bold** are package, class, or program names.

A	MATHJAX	630
abstract		
missing toc	134, 587	
acronym		
multiply-defined labels	591	
\AddSubtitlePublished	385	
affiliation	378	
alt tags	154, 188	
AMSmath		
ntheorem		
numbering	155, 814	
appendix		
incorrect toc link	135, 612	
array		
chemformula	154	
authblk		
\theauthor	376, 378	
titling	134, 376, 621, 907	
author		
affiliation	378	
formatting	122	
B		
babel		
French	168	
backref	622	
backref		
.	132	
bibtex		
\etalchar	135	
Improper \prevdepth	135	
bigdelim	163, 623	
boxes	126	
breqn		
darray	630	
C	Calibre	
	EPUB conversion	174
	caption	
	numbering	164
	options	164
	cases	
	MATHJAX	637
	chemformula	
	MATHJAX	154, 641
	chemgreek	
	fontspec mapping	646
	text-mode symbols	646
	chemmacros	
	\makepolymerdelims	647
	redox reactions	647
	colortbl	
	162, 404, 669
	cross reference	
	incorrect link	189
	missing	189
	CSS	190
E		
	\ensuremath	188
	epstopdf	158, 685
	EPUB	
	encoding	175
	page order	174
	search order	174
	section breaks	175
	\etalchar	135

	F	
fancybox		
\VerbatimFootnotes . . .	133, 691, 698	
fancyvrb		
\VerbatimFootnotes . . .	133, 691, 698	
figure		
macro in name	188	
file		
inaccessible	114	
filename		
accents	358	
collision	351	
Missing \$ inserted	187	
fixme	169, 706	
float		
alignment	125, 164	
out of sequence	189	
floatrow		
\FBwidth and \FBheight . . .	165, 711	
with subfig	165, 711	
floatrow		
\ttabbox	160, 401	
font		
ligatures	106	
missing symbols	125, 887	
monospace	106	
package conflicts	106	
selection	105	
UTF-8	105	
fontspec	105	
footnote		
displaymath	133, 691, 698	
in math	132	
in sectioning command	132	
memoir	132, 343	
misnumbered	132	
paragraph tags	133, 691, 698	
sectioning, footmisc	132, 343	
sectioning, verbatim	133, 691, 698	
title	377	
verbatim	132	
\VerbatimFootnotes	132, 691, 698	
forest	723	
formatting		
\bfseries etc.	124, 564	
frames	128	
	G	
glossaries		
makeglossaries not found . . .	136, 728	
	H	
graphics		
\rotatebox, \scalebox, \reflectbox	157, 545	
image format priorities	156, 545	
images out of order	95, 190	
optional arguments	156, 545	
scaled	732	
viewport	156, 545	
Greek packages	646	
grffile	157, 744	
	I	
horizontal spacing	165, 877	
HTML		
&, <, >	124, 564	
alt tags	154	
author	343	
corrupted	122, 126, 187, 190	
entities	124, 564	
image appear as HTML code . .	95, 190	
inaccessible pages	114, 116	
starred section	134	
missing pages		
filename not unique	115	
recompile	190	
SideTOCDepth and FileDepth .	114	
SideTOCDepth and tocdepth .	114	
page did not update	115, 190	
settings		
changed	112	
undefined	187	
\HTMLAuthor	343	
HTMLIndexCmd		
filenames	110	
hyperref		
backref	132	
comments between arguments .	132	
incorrect link	189	
	J	
image		
appears as HTML code	95, 190	
format priorities	156, 545	
incorrect	95, 189, 190	
viewport	156, 545	
Improper \prevdepth		
bibtex	135	
boxes	188	

\includegraphics	
optional arguments	156, 545
index	
empty	149
empty link	131, 189
missing entries	137
reference ranges	149
see and <i>seealso</i>	149
styling references	149
xindy and <i>hyperref</i>	149
K	
keyfloat	165, 765
L	
label	
\nameref empty	131, 189
characters	131, 189
Label(s) may have changed	187
\LateximageFontName	530
Leaders not followed by proper glue	187
LibreOffice	
import	176
ligatures	106
LINUX	120, 198
list	
empty item	126, 393
listings	189
lists	
label formatting	394
ltxtable	
numbering	781
lua \TeX	105
\LWRbackslash	170
\LWRdollar	170
\LWRhash	170
\LWRopquote	170
\LWRopseq	170
\LWRpercent	170
M	
MAC OS	120, 198
makeglossaries	
not found	136, 728
\makelabel	394
\marginpar	126, 349
math	
Tikz	154
alt tags	188
appears as HTML code	95, 190
chemformula	154
custom macros	188
dynamic	315
equation numbering	
ntheorem	155, 814
footnote	132
in \TeX boxes	152, 503
incorrect	95, 190, 315
non-math contents	188
slow or failed compile	188
subequations	152, 504
tabbing	159, 392
MATHJAX	
breqn	630
cases	637
chemformula	154, 641
errors	154, 188, 315
mhchem	798
siunitx	153, 155, 504, 543, 866
subequations	152, 504
unsupported packages	153, 188, 505
memoir	
options clash	166, 965
mhchem	
MATHJAX	798
nested dollar signs	798
minipage	
alignment	127, 554
horizontal space between	574
in a span	127, 554
inline	127, 554
Misplaced \noalign	163, 777
tabular	
rules	162, 403
Misplaced \omit	
tabular	231
Misplaced alignment tab character &	
floatrow	165, 711
frames	128
supertabular	163, 883, 958
tabular	
macros	160, 314, 401
Missing \$ inserted	
filename or URL	187
morewrites	187
morewrites	149
MS-WINDOWS	120, 198
multiply-defined labels	
acronym	591
\multirow and \multicolumn	161, 402, 807

multirow	160, 402	sectioning
		accents 358
		macro in name 188
		missing 114
		names 351
		starred section 134
		word processor import 179
		siunitx
		MATHJAX 155, 543, 866
		with TeXMaths 179
		sipnidx 155, 543, 866
		MATHJAX 153, 504
		S column 162, 404
		tabular S and s columns 155, 543, 866
		splitidx
		\thepage and \AtWriteToIndex ..
	 139, 874
		subfig
		options 165, 877
		with floatrow 165, 711
		SVG image
		appears as HTML code 95, 190
		incorrect 95, 189, 190
		math incorrect 315
		out of order 95, 190
		sympytex 173
		T
		tabbing
		math 159, 392
		table
		macro in name 188
		numbering 781
		Table of Contents
		missing 116
		tabular
		* column specification 161, 403
		baselines 420
		corrupt rows 160, 401, 456
		\endhead, \endfoot, \endlastfoot
	 163, 777
		inside an environment .. 160, 401, 456
		\kill 163, 777
		macro inside 161, 403
		Misplaced \noalign 162, 403
		Misplaced alignment tab character &
		macros 160, 401
		rules 314
		\multicolumn with \multirow ... 807
		\multirow 460
		R
		reference
		% character between arguments .. 189
		empty link 131, 189
		incorrect link 189
		label characters 131, 189
		missing or incorrect 189
		page number 131, 189, 550
		rterface 173
		S
		sample_projects.css
		overwritten 119

multirow	160, 402	UNIX	120, 198
\newcolumntype	161, 403	URL	
numbering	956	Missing \$ inserted	187
row corruption	161, 403		
rules	162, 403		
S column	162, 404	V	
TeXMaths	179	verbatim	
text		footnote	132
&, <, >	124, 564	framed	130, 691
\bfseries etc.	124, 564	VerbatimFootnotes	133, 691, 698
corrupted	105	verse	
textcomp		spacing	167, 388, 933
missing symbols	125, 887	viewport	156, 545
\theauthor and authblk	376, 378		
tikz		W	
in math	154	warpall	187
matrices, &	157, 898	warpHTML	120, 187
title		warpprint	121, 187
affiliation	378	WINDOWS	120, 198
newlines	122	word processor	
\thanks	377	import	176
titling		sectioning headings	179
authblk	134, 376, 621, 907	X	
hooks	385	xe \mathbb{L} E _X	105
tocloft		xfrac	953
chapter titles	134, 150, 611, 915	xindy	
todonotes	168, 782, 923	hyperref	149
tracing l warp	191	options	
transparent	925	HTMLIndexCmd	110
		LateXmkIndexCmd	111
		PrintIndexCmd	110
U		xltabular	
Undefined control sequence		numbering	956
polyglossia	168	xparse	169
Unicode	105	xy	961
units	155		

Index of Indexes

C		I	
Change History	993	Index of Objects	1018
G		T	
General Index	1038	Troubleshooting Index	1042