Lwarp

LaTeX HTML5

The lwarp package

LaTeX to HTML

v0.68 — 2019/03/05

© 2016–2019 Brian Dunn
bd@BDTechConcepts.com

Abstract

The lwarp package converts LaTeX to HTML by using LaTeX to process the user's document and directly generate HTML tags. External utility programs are only used for the final conversion of text and images. Math may be represented by SVG images or MathJax. Hundreds of LaTeX packages are supported.

Documents may be produced by DVI or PDF LaTeX, LuaLaTeX, XeLaTeX; by several CJK engines, classes, and packages; or by customized systems such as perltex and pythontex. A *texlua* script automates compilation, index, glossary, and batch image processing, and also supports *latexmk*. Configuration is semi-automatic at the first manual compile. Support files are self-generated. Print and HTML versions of each document may coexist.

Assistance is provided for HTML import into EPUB conversion software and word processors.

Requirements include the commonly-available Poppler utilities (included with MiKTeX) and Perl. Detailed installation instructions are included for each of the major operating systems and TeX distributions.

A quick-start tutorial is provided, as well as extensive documentation for special cases, a general index, and a troubleshooting index. Automatic testing of package load order and image generation offers useful advice for resolving errors.

SVG math and many other generated images include LaTeX expressions in the `alt` tags. MathJax may be used with advanced equation numbering under the direct control of lwarp.

Complicated tables are supported, which copy/paste well into LibreOffice Writer.

Supported classes and packages include memoir and koma-script, cleveref, caption, mdframed, siunitx, and many popular packages for tabulars, floats, graphics, theorems, the title page, bibliography, indexing, footnotes, and editorial work.

TeX is a self-modifying tokenized macro-expansion language. Since lwarp is written directly in LaTeX, it is able to interpret the document's meaning at a deeper level than external conversions which merely approximate TeX. HTML5 and CSS3 are leveraged to provide advanced features such as booktabs trim, multicolumns, side-by-side minipages, and JavaScript-free navigation.

For a list of supported features, see table 2: Supported packages and features.

To update existing projects, see section 2: Updates.

Lwarp is still in development. Changes are likely.

License:

This work may be distributed and/or modified under the conditions of the LaTeX Project Public License, either version 1.3 of this license or (at your option) any later version. The latest version of this license is in http://www.latex-project.org/lppl.txt and version 1.3 or later is part of all distributions of LaTeX version 2005/12/01 or later.

1 Support TEX development

TEX and related projects:

- are mostly open-sourced and a volunteer effort;
- benefit students, academics, scientists, engineers, and businesses;
- help drive education, public and private research, and commercial activity;
- are used in the fields of mathematics, science, engineering, and humanities;
- are international in reach;
- span decades of development;
- are enduring — many older packages are still actively used and maintained;
- are largely backwards compatible;
- are portable across all the major computing platforms;
- are usable even on older computers and away from internet access;
- are continuing to maintain relevance with modern improvements;
- require no yearly subscription fees;
- and are supported by an active community of knowledgeable volunteers.

Please consider helping by joining and/or contributing to the TEX Users Group, a United States 501(c)(3) tax-exempt charitable organization. Contributions are accepted by credit card, check, or Pay Pal, via the United Way, or by USA or European bank transfer. Membership in TUG supports the development of TEXLive, the major TEX distribution.

Donations may be directed towards individual projects:

TUG Bursary Fund: Assistance for attending annual TUG meetings.
CTAN: The Comprehensive TEX Archive Network — Central storage for TEX.
TeX Development Fund: Support for specific projects.
EduTeX: Teaching and using TEX in schools and universities.
GUST e-foundry fonts: Enhanced for math and additional language groups.
LaTeX Project: Modernizing the LATEX core.
Libre Font Fund: Fonts, tools (FontForge), and distribution (the Open Font Library).
LuaTeX: Combining the pdfTEX engine and the Lua language.
MetaPost: Postscript graphics.
MacTeX: TEX for Mac.
PDF Accessibility: Modern PDF standards.
Other: Additional projects may be specified.

To make a contribution: https://www.tug.org/donate.html

For country-specific TEX users groups: http://tug.org/usergroups.html

For users of MiKTEX: https://miktex.org/donations.html

Contents

1 Support TEX development 2

List of Figures 53

List of Tables 53

2 Updates 54

3 Introduction 73
3.1 Typesetting conventions . . . 75
3.2 Supported packages and features . . . 76

4 Alternatives 82
4.1 internet class . . . 82
4.2 TEX4HT . . . 82
4.3 Translators . . . 82
4.4 AsciiDoc and Asciidoctor . . . 83
4.4.1 Asciidoctor-LATEX . . . 83
4.5 Pandoc . . . 83
4.6 Word processors . . . 83
4.7 Commercial systems . . . 83
4.8 Comparisons . . . 83

5 Installation 85
5.1 Installing the lwarp package . . . 87
5.2 Installing the *lwarpmk* utility . . . 88
5.2.1 Using a local copy of *lwarpmk* . . . 90
5.3 Installing additional utilities . . . 90

6 Tutorial 92
6.1 Starting a new project . . . 92
6.2 Compiling the print version with *lwarpmk* . . . 96
6.3 Compiling the HTML version with *lwarpmk* . . . 97
6.4 Generating the SVG images . . . 98
6.5 Using MathJax for math . . . 99
6.6 Changing the CSS style . . . 100
6.7 Customizing the HTML output . . . 100
6.8 Using *latexmk* . . . 101
6.9 Using XELATEX or LuaLATEX . . . 102
6.10 Using DVI LATEX . . . 102
6.11 Using a glossary . . . 103
6.11.1 gloss package . . . 103
6.11.2 glossaries package . . . 103
6.12 Cleaning auxiliary files . . . 104
6.13 Cleaning auxiliary and output files . . . 104
6.14 Cleaning the images from the `<project>-images` directory . . . 104
6.15 Converting PDF or EPS images to SVG . . . 104
6.16 Creating HTML from an incomplete compile . . . 104
6.17 Processing multiple projects in the same directory . . . 104
6.18 Using the *make* utility . . . 105

7 Converting an existing document 106

8 Additional details 107
8.1 Shell escape . . . 107
8.2 Font and UTF-8 support . . . 107
8.2.1 Indexes, glossaries, and encoding . . . 108
8.3 lwarp package loading and options . . . 109
8.4 Customizing the HTML output . . . 113
8.4.1 Example HTML file naming . . . 118
8.5 Customizing the CSS . . . 119
8.6 Selecting the operating system . . . 120
8.7 Selecting actions for print or HTML output . . . 120
8.8 Commands to be placed into the warpprint environment . . . 121
8.9 Title page . . . 122
8.10 HTML page meta descriptions . . . 123
8.11 HTML homepage meta title . . . 123
8.12 HTML page meta author . . . 123

9 Special cases and limitations 123
9.1 Things to avoid . . . 124
9.1.1 Invalid HTML . . . 124
9.2 Formatting . . . 124
9.2.1 Text formatting . . . 124
9.2.2 Horizontal space . . . 125
9.2.3 Text alignment . . . 125
9.2.4 Accents . . . 125
9.2.5 textcomp package . . . 125
9.2.6 Superscripts and other non-math uses of math mode . . . 125
9.2.7 Empty \item followed by a new line of text or a nested list: . . . 126
9.2.8 Filenames and URLs in lists or footnotes . . . 126
9.2.9 relsize package . . . 126
9.3 Boxes and minipages . . . 126
9.3.1 Marginpars . . . 126
9.3.2 Save Boxes . . . 126
9.3.3 Minipages . . . 127
9.3.4 Side-by-side minipages . . . 127
9.3.5 Framed minipages and other environments . . . 128
9.3.6 fancybox package . . . 129
9.3.7 mdframed package . . . 130
9.4 Section names . . . 131
9.5 Cross-references . . . 131
9.5.1 Page references . . . 132
9.5.2 cleveref and varioref packages . . . 132
9.5.3 Hyperlinks, hyperref, and url . . . 132
9.5.4 Footnotes and page notes . . . 132
9.6 Front and back matter . . . 134
9.6.1 Custom classes with multiple authors and affiliations . . . 134
9.6.2 Starred chapters and sections . . . 134
9.6.3 abstract package . . . 135
9.6.4 titling and authblk . . . 135
9.6.5 tocloft package . . . 135

9.6.6 appendix package . . . 135
9.6.7 pagenote package . . . 135
9.6.8 endnotes package . . . 135
9.6.9 BibTeX . . . 136
9.6.10 gloss package . . . 136
9.6.11 glossaries package . . . 136
9.6.12 nomencl package . . . 137
9.6.13 Indexing overview . . . 137
9.6.14 Indexing with basic LaTeX and makeidx . . . 138
9.6.15 Indexing with index . . . 139
9.6.16 Indexing with splitidx . . . 139
9.6.17 Indexing with imakeidx . . . 141
9.6.18 Indexes with memoir . . . 144
9.6.19 Using a custom *makeindex* style file . . . 147
9.6.20 Using a custom *xindy* style file . . . 148
9.6.21 Additional indexing limitations . . . 148
9.6.22 Index positions, toc, tocbibind . . . 149
9.7 Math . . . 150
9.7.1 Math in section names . . . 150
9.7.2 Rendering tradeoffs . . . 150
9.7.3 svg option . . . 151
9.7.4 MathJax option . . . 151
9.7.5 Customizing MathJax . . . 152
9.7.6 MathJax limitations . . . 152
9.7.7 Catcode changes . . . 153
9.7.8 Complicated inline math objects . . . 153
9.7.9 Complicated display math objects . . . 153
9.7.10 ntheorem package . . . 153
9.7.11 siunitx package . . . 154
9.7.12 units and nicefrac packages . . . 154
9.7.13 newtxmath package . . . 154
9.8 Graphics . . . 154
9.8.1 tikz package . . . 156
9.8.2 grffile package . . . 156
9.8.3 color package . . . 156
9.8.4 xcolor package . . . 156
9.8.5 epstopdf package . . . 157
9.8.6 pstricks package . . . 157
9.8.7 pdftricks package . . . 157
9.8.8 psfrag package . . . 157
9.8.9 pstool package . . . 158
9.8.10 asymptote package . . . 158
9.8.11 overpic package . . . 158
9.9 Tabbing . . . 158
9.10 Tabular . . . 159
9.10.1 longtable package . . . 161
9.10.2 threeparttablex package . . . 162
9.10.3 supertabular and xtab packages . . . 162
9.10.4 bigdelim package . . . 163
9.11 Floats . . . 163
9.11.1 Float contents alignment . . . 163

9.11.2 float, trivfloat, and/or algorithmicx together . . . 163
9.11.3 caption and subcaption packages . . . 163
9.11.4 subfig package . . . 164
9.11.5 floatrow package . . . 164
9.11.6 keyfloat package . . . 164
9.12 KOMA-SCRIPT classes . . . 165
9.13 MEMOIR class . . . 165
9.14 International languages . . . 165
9.15 Miscellaneous packages . . . 166
9.15.1 verse and memoir . . . 166
9.15.2 newclude package . . . 166
9.15.3 babel package . . . 167
9.15.4 polyglossia package . . . 167
9.15.5 todonotes and luatodonotes packages . . . 167
9.15.6 fixme . . . 167
9.15.7 chemfig package . . . 168
9.15.8 chemformula package . . . 168
9.15.9 mhchem package . . . 168
9.15.10 xparse package . . . 168
9.15.11 kotex package . . . 168

10 Compiling using custom shell commands 169
10.1 Command options . . . 169
10.2 Literal character macros . . . 169
10.3 *latexmk* . . . 170
10.4 perltex package . . . 171
10.5 pythontex package . . . 171
10.6 Other packages . . . 171
10.7 *make* program . . . 172
10.8 UTF-8 locale . . . 172

11 EPUB conversion 173

12 Word-processor conversion 175
12.1 Activating word-processor conversion . . . 175
12.2 Additional modifications . . . 176
12.3 Recommendations . . . 178
12.4 Limitations . . . 179

13 Modifying lwarp 180
13.1 Creating a development system . . . 180
13.2 Modifying a package for lwarp . . . 181
13.2.1 Adding a package to the lwarp.dtx file . . . 182
13.3 Modifying a class for lwarp . . . 182
13.4 Testing lwarp . . . 183
13.5 Modifying *lwarpmk* . . . 183

14 Troubleshooting 185
14.1 Using the lwarp.sty package . . . 185
14.1.1 Debug tracing output . . . 188
14.2 Compiling the `lwarp.dtx` file . . . 188

15 Trademarks 190

1 lwarp.sty 191

16 Implementation 191

17 Section depths and HTML headings 192

18 Source code 193

19 Detecting the TEX engine — *pdflatex*, *lualatex*, *xelatex* 194

20 Early package requirements 194

21 Package load order 194
21.1 Tests of package load order 195
21.2 Error for disallowed packages and classes loaded before lwarp 197
21.3 Enforcing package loading after lwarp 198

22 MD5 hashing 206

23 pdfLATEX T1 and UTF-8 encoding 206

24 Unicode input characters 207

25 Upright quotes 208

26 Miscellaneous tools 208

27 Operating-System portability 209
27.1 Literal characters 209
27.2 Common portability code 211
27.3 UNIX, LINUX, and MAC OS 211
27.4 MS-WINDOWS 211

28 Package options 211
28.1 Additional options support 216
28.2 Conditional compilation 217

29 Required packages 218

30 Loading packages 222

31 Additional required packages 227

32 File handles 227

33 Include a file 228

34 Copying a file 229

35 Debugging messages 230

36 Defining print and HTML versions of macros and environments 231

37 HTML-conversion output modifications 235
37.1 User-level controls . . . 235
37.2 Heading adjustments . . . 237

38 Remembering original formatting macros 238

39 Accents 240

40 Configuration files 241
40.1 Decide whether to generate configuration files . . . 241
40.2 <project>_html.tex . . . 242
40.3 *lwarpmk* configuration files . . . 242
40.3.1 Helper macros . . . 243
40.3.2 lwarpmk.conf . . . 248
40.3.3 <project>.lwarpmkconf . . . 249
40.4 lwarp.css . . . 249
40.5 lwarp_sagebrush.css . . . 277
40.6 lwarp_formal.css . . . 282
40.7 sample_project.css . . . 286
40.8 lwarp.ist . . . 286
40.9 lwarp.xdy . . . 287
40.10 lwarp_one_limage.cmd . . . 287
40.11 lwarp_mathjax.txt . . . 288
40.12 lwarpmk.lua — lwarpmk option . . . 290

41 Stacks 307
41.1 Assigning depths . . . 307
41.2 Closing actions . . . 308
41.3 Closing depths . . . 308
41.4 Pushing and popping the stack . . . 309

42 Data arrays 310

43 Localizing catcodes 311

44 Localizing dynamic math 312

45 HTML entities 313

46 HTML filename generation 314

47 Homepage link 316

48 \LWRPrintStack diagnostic tool 317

49 Closing stack levels 318

50 PDF pages and styles 319

51 HTML tags, spans, divs, elements 320
51.1 Mapping LaTeX sections to HTML sections . . . 320

51.2 Babel-French tag modifications . . . 320
51.3 HTML output formatting . . . 321
51.4 HTML tags . . . 322
51.5 Block tags and comments . . . 323
51.6 Div class and element class . . . 324
51.7 Single-line elements . . . 326
51.8 HTML5 semantic elements . . . 326
51.9 High-level block and inline classes . . . 326
51.10 Closing HTML tags . . . 328

52 Paragraph handling 329

53 Paragraph start/stop handling 333

54 Indentfirst 335

55 Page headers and footers 335

56 CSS 336

57 Title, HTML meta author, HTML meta description 337

58 Footnotes 338
58.1 Regular page footnotes . . . 339
58.2 Minipage footnotes . . . 339
58.3 Titlepage thanks . . . 339
58.4 Regular page footnote implementation . . . 339
58.5 Minipage footnote implementation . . . 342
58.6 Printing pending footnotes . . . 343

59 Marginpars 344

60 Splitting HTML files 345
60.1 Customizing MathJax . . . 350

61 Sectioning 355
61.1 User-level starred section commands . . . 355
61.2 Book class commands . . . 356
61.3 Sectioning support macros . . . 356
61.4 Pre- and post- sectioning names . . . 363
61.5 `\section` and friends . . . 364

62 Starting a new file 366

63 Starting HTML output 370

64 Ending HTML output 372

65 Title page 374
65.1 Setting the title, etc. . . . 374
65.2 `\if@titlepage` . . . 376
65.3 Changes for `\affiliation` . . . 376
65.4 Printing the thanks . . . 377

65.5 Printing the title, etc. in HTML . . . 377
65.6 Printing the title, etc. in print form . . . 378
65.7 \maketitle for HTML output . . . 379
65.8 \published and \subtitle . . . 382

66 Abstract 383

67 Quote and verse 383
67.1 Attributions . . . 383
67.2 Quotes, quotations . . . 384
67.3 Verse . . . 384
67.3.1 LaTeX core verse environment . . . 385
67.3.2 verse and memoir . . . 385

68 Verbatim and tabbing 386

69 Theorems 388

70 Lists 389
70.1 List environment . . . 390
70.2 Itemize . . . 393
70.3 Enumerate . . . 394
70.4 Description . . . 394
70.5 Patching the lists . . . 395

71 Tabular 396
71.1 Limitations . . . 396
71.2 Temporary package-related macros . . . 399
71.2.1 arydshln . . . 399
71.3 Token lookahead . . . 399
71.4 Tabular variables . . . 400
71.5 Handling &, @, !, and bar . . . 403
71.5.1 Handling & . . . 404
71.5.2 Filling an unfinished row . . . 405
71.6 Handling \\ . . . 407
71.7 Looking ahead in the column specifications . . . 408
71.8 Parsing @, >, <, !, bar columns . . . 408
71.9 Parsing 'l', 'c', or 'r' columns . . . 412
71.10 Parsing 'p', 'm', or 'b' columns . . . 412
71.11 Parsing 'w' columns . . . 413
71.12 Parsing 'D' columns . . . 413
71.13 Parsing the column specifications . . . 413
71.14 colortbl and xparse tabular color support . . . 418
71.15 Starting a new row . . . 419
71.16 Printing vertical bar tags . . . 420
71.17 Printing at or bang tags . . . 420
71.18 Data opening tag . . . 421
71.19 Midrules . . . 423
71.20 Cell colors . . . 429
71.21 Multicolumns . . . 433
71.21.1 Parsing multicolumns . . . 433
71.21.2 Multicolumn factored code . . . 436

71.21.3 Multicolumn . . . 439
71.21.4 Longtable captions . . . 440
71.21.5 Counting HTML tabular columns . . . 442
71.22 Multirow if not loaded . . . 443
71.23 Multicolumnrow . . . 444
71.24 Utility macros inside a table . . . 445
71.25 Special-case tabular markers . . . 445
71.26 Checking for a new table cell . . . 446
71.27 \mrowcell . . . 449
71.28 \mcolrowcell . . . 449
71.29 HTML tabular environment . . . 450

72 Cross-references 456
72.1 Setup . . . 456
72.2 New lwarp labels. . . . 458
72.3 Labels . . . 459
72.4 References . . . 460
72.5 Hyper-references . . . 463

73 Floats 467
73.1 Float environment . . . 467
73.2 Float tracking . . . 469
73.3 Caption inside a float environment . . . 471
73.4 Caption and LOF linking and tracking . . . 471

74 Table of Contents, LOF, LOT 474
74.1 Reading and printing the TOC . . . 475
74.2 High-level TOC commands . . . 477
74.3 Side TOC . . . 478
74.4 Low-level TOC line formatting . . . 479

75 Index and glossary 482

76 Bibliography presentation 485

77 Restoring original formatting 486

78 Math 488
78.1 Limitations . . . 488
78.1.1 Math in section names . . . 488
78.1.2 Rendering tradeoffs . . . 488
78.1.3 SVG option . . . 489
78.1.4 MathJax option . . . 489
78.1.5 Customizing MathJax . . . 490
78.1.6 MathJax limitations . . . 490
78.1.7 Catcode changes . . . 491
78.1.8 Complicated inline math objects . . . 491
78.1.9 Complicated display math objects . . . 491
78.2 HTML alt tag names . . . 492
78.3 Inline and display math . . . 492
78.4 MathJax support . . . 503
78.5 Equation environment . . . 505

78.6 \displaymathnormal and \displaymathother . . . 508
78.7 AMS Math environments . . . 509
78.7.1 Support macros . . . 509
78.7.2 Environment patches . . . 510

79 Lateximages 513
79.1 Description . . . 513
79.2 Support counters and macros . . . 514
79.3 Font size . . . 515
79.4 Sanitizing math expressions for HTML . . . 515
79.5 Equation numbers . . . 517
79.6 HTML alt tags . . . 518
79.7 lateximage environment . . . 518

80 center, flushleft, flushright 524

81 Preloaded packages 525

82 siunitx 527

83 Graphics print-mode modifications 528
83.1 General limitations . . . 528
83.2 Print-mode modifications . . . 529

84 xcolor boxes 530

85 chemmacros environments 533

86 cleveref 533

87 picture environment 536

88 Minipages and Boxes 537
88.1 Counters and lengths . . . 538
88.2 Footnote handling . . . 538
88.3 Minipage handling . . . 538
88.4 \parbox, \mbox, \makebox, \framebox, \fbox, \raisebox . . . 542

89 Direct formatting 547

90 Skips, spaces, font sizes 558

91 \phantomsection 565

92 \LaTeX and other logos 565
92.1 HTML logos . . . 566
92.2 Print logos . . . 568

93 \AtBeginDocument, \AtEndDocument 569

94 Loading KOMA-SCRIPT class patches 569

95 Loading MEMOIR class patches 569

96 ut* class patches 570

97 CTEX patches 571

98 kotexutf patches 572

2 lwarp-2in1.sty 573

99 2in1 573

3 lwarp-2up.sty 573

100 2up 573

4 lwarp-a4.sty 573

101 a4 573

5 lwarp-a4wide.sty 574

102 a4wide 574

6 lwarp-a5comb.sty 574

103 a5comb 574

7 lwarp-abstract.sty 574

104 abstract 574

8 lwarp-academicons.sty 576

105 academicons 576

9 lwarp-accsupp.sty 577

106 accsupp 577

10 lwarp-acro.sty 577

107 acro 577

11 lwarp-acronym.sty 579

108 acronym 579

12 lwarp-adjmulticol.sty 580

109 adjmulticol 580

13 lwarp-addlines.sty 581

110 addlines 581

14 lwarp-afterpage.sty 581

111 afterpage 581

15 lwarp-algorithm2e.sty 581

112 algorithm2e 581

16 lwarp-algorithmicx.sty 585

113 algorithmicx 585

17 lwarp-alltt.sty 586

114 alltt 586

18 lwarp-amsmath.sty 586

115 amsmath 586

19 lwarp-amsthm.sty 593

116 amsthm 593

20 lwarp-anonchap.sty 596

117 anonchap 596

21 lwarp-anysize.sty 597

118 anysize 597

22 lwarp-appendix.sty 597

119 appendix 597

23 lwarp-ar.sty 598

120 ar 598

24 lwarp-arabicfront.sty 599

121 arabicfront 599

25 lwarp-array.sty 599

122 array 599

26 lwarp-arydshln.sty 600

123 arydshln 600

27 lwarp-asymptote.sty 602

124 asymptote 602

28 lwarp-atbegshi.sty 603

125 atbegshi 603

29 lwarp-attachfile.sty 603

126 attachfile 603

30 lwarp-attachfile2.sty 604

127 attachfile2 604

31 lwarp-authblk.sty 606

128 authblk 606

32 lwarp-axessibility.sty 607

129 axessibility 607

33 lwarp-axodraw2.sty 607

130 axodraw2 607

34 lwarp-backref.sty 608

131 backref 608

35 lwarp-balance.sty 608

132 balance 608

36 lwarp-bbding.sty 608

133 bbding 608

37 lwarp-biblatex.sty 613

134 biblatex 613

38 lwarp-bibunits.sty 614

135 bibunits 614

39 lwarp-bigdelim.sty 614

136 bigdelim 614

40 lwarp-bigfoot.sty 615

137 bigfoot 615

41 lwarp-bigstrut.sty 616

138 bigstrut 616

42 lwarp-bitpattern.sty 616

139 bitpattern 616

43 lwarp-blowup.sty 616

140 blowup 616

44 lwarp-booklet.sty 617

141 booklet 617

45 lwarp-bookmark.sty 617

142 bookmark 617

46 lwarp-booktabs.sty 618

143 booktabs 618

47 lwarp-bophook.sty 619

144 bophook 619

48 lwarp-bounddvi.sty 619

145 bounddvi 619

49 lwarp-boxedminipage2e.sty 620

146 boxedminipage2e 620

50 lwarp-breakurl.sty 620

147 breakurl 620

51 lwarp-breqn.sty 621

148 breqn 621

52 lwarp-bsheaders.sty 622

149 bsheaders 622

53 lwarp-bxpapersize.sty 622

150 bxpapersize 622

54 lwarp-bytefield.sty 623

151 bytefield 623

55 lwarp-cancel.sty 623

152 cancel 623

56 lwarp-canoniclayout.sty 624

153 canoniclayout 624

57 lwarp-caption.sty 624

154 caption 624

58 lwarp-cases.sty 627

155 cases 627

59 lwarp-changebar.sty 628

156 changebar 628

60 lwarp-changepage.sty 628

157 changepage 628

61 lwarp-changes.sty 629

158 changes 629

62 lwarp-chappg.sty 630

159 chappg 630

63 lwarp-chapterbib.sty 630

160 chapterbib 630

64 lwarp-chemfig.sty 630

161 chemfig 630

65 lwarp-chemformula.sty 632

162 chemformula 632

66 lwarp-chemgreek.sty 636

163 chemgreek 636

67 lwarp-chemmacros.sty 637

164 chemmacros 637
164.1 Changes to the user's document . . . 637
164.2 Code . . . 638
164.3 Loading modules . . . 638
164.4 New environments . . . 638
164.5 Acid-base . . . 638
164.6 Charges . . . 640
164.7 Nomenclature . . . 641
164.8 Particles . . . 643
164.9 Phases . . . 643
164.10 Mechanisms . . . 644
164.11 Newman . . . 646
164.12 Orbital . . . 646
164.13 Reactions . . . 647
164.14 Redox . . . 648
164.15 Scheme . . . 648
164.16 Spectroscopy . . . 649
164.17 Thermodynamics . . . 653

68 lwarp-chemnum.sty 655

165 chemnum 655

69 lwarp-chkfloat.sty 656

166 chkfloat 656

70 lwarp-chngpage.sty 656

167 chngpage 656

71 lwarp-cite.sty 656

168 cite 656

72 lwarp-CJK.sty 657

169 CJK 657

73 lwarp-CJKutf8.sty 657

170 CJKutf8 657

74 lwarp-clrdblpg.sty 657

171 clrdblpg 657

75 lwarp-cmdtrack.sty 657

172 cmdtrack 657

76 lwarp-color.sty 658

173 color 658

77 lwarp-colortbl.sty 658

174 colortbl 658

78 lwarp-continue.sty 660

175 continue 660

79 lwarp-copyrightbox.sty 660

176 copyrightbox 660

80 lwarp-crop.sty 661

177 crop 661

81 lwarp-cuted.sty 661

178 cuted 661

82 lwarp-cutwin.sty 661

179 cutwin 661

83 lwarp-dblfloatfix.sty 662

180 dblfloatfix 662

84 lwarp-dblfnote.sty 662

181 dblfnote 662

85 lwarp-dcolumn.sty 663

182 dcolumn 663

86 lwarp-diagbox.sty 663

183 diagbox 663

87 lwarp-dingbat.sty 664

184 dingbat 664

88 lwarp-dprogress.sty 665

185 dprogress 665

89 lwarp-draftcopy.sty 666

186 draftcopy 666

90 lwarp-draftfigure.sty 666

187 draftfigure 666

91 lwarp-draftwatermark.sty 666

188 draftwatermark 666

92 lwarp-easy-todo.sty 667

189 easy-todo 667

93 lwarp-ebook.sty 668

190 ebook 668

94 lwarp-ed.sty 668

191 ed 668

95 lwarp-ellipsis.sty 669

192 ellipsis 669

96 lwarp-embrac.sty 669

193 embrac 669

97 lwarp-emptypage.sty 670

194 emptypage 670

98 lwarp-endfloat.sty 670

195 endfloat 670

99 lwarp-endheads.sty 671

196 endheads 671

100 lwarp-endnotes.sty 671

197 endnotes 671

101 lwarp-enumerate.sty 672

198 enumerate 672

102 lwarp-enumitem.sty 672

199 enumitem 672

103 lwarp-epigraph.sty 673

200 epigraph 673

104 lwarp-epsfig.sty 674

201 epsfig 674

105 lwarp-epstopdf.sty 675

202 epstopdf 675

106 lwarp-epstopdf-base.sty 675

203 epstopdf-base 675

107 lwarp-errata.sty 676

204 errata 676

108 lwarp-eso-pic.sty 677

205 eso-pic 677

109 lwarp-eurosym.sty 678

206 eurosym 678

110 lwarp-everypage.sty 678

207 everypage 678

111 lwarp-everyshi.sty 679

208 everyshi 679

112 lwarp-extramarks.sty 679

209 extramarks 679

113 lwarp-fancybox.sty 679

210 fancybox 679

114 lwarp-fancyhdr.sty 684

211 fancyhdr 684

115 lwarp-fancyref.sty 685

212 fancyref 685

116 lwarp-fancytabs.sty 686

213 fancytabs 686

117 lwarp-fancyvrb.sty 687

214 fancyvrb 687

118 lwarp-figcaps.sty 692

215 figcaps 692

119 lwarp-figsize.sty 693

216 figsize 693

120 lwarp-fitbox.sty 693

217 fitbox 693

121 lwarp-fix2col.sty 694

218 fix2col 694

122 lwarp-fixme.sty 694

219 fixme 694

123 lwarp-fixmetodonotes.sty 695

220 fixmetodonotes 695

124 lwarp-flafter.sty 696

221 flafter 696

125 lwarp-flippdf.sty 696

222 flippdf 696

126 lwarp-float.sty 696

223 float 696

127 lwarp-floatflt.sty 698

224 floatflt 698

128 lwarp-floatpag.sty 699

225 floatpag 699

129 lwarp-floatrow.sty 699

226 floatrow 699

130 lwarp-fltrace.sty 704

227 fltrace 704

131 lwarp-flushend.sty 704

228 flushend 704

132 lwarp-fnbreak.sty 705

229 fnbreak 705

133 lwarp-fncychap.sty 705

230 fncychap 705

134 lwarp-fnlineno.sty 706

231 fnlineno 706

135 lwarp-fnpara.sty 706

232 fnpara 706

136 lwarp-fnpos.sty 706

233 fnpos 706

137 lwarp-fontawesome.sty 706

234 fontawesome 706

138 lwarp-fontawesome5.sty 708

235 fontawesome5 708

139 lwarp-fontenc.sty 709

236 fontenc 709

140 lwarp-footmisc.sty 709

237 footmisc 709

141 lwarp-footnote.sty 710

238 footnote 710

142 lwarp-footnotebackref.sty 711

239 footnotebackref 711

143 lwarp-footnotehyper.sty 711

240 footnotehyper 711

144 lwarp-footnoterange.sty 711

241 footnoterange 711

145 lwarp-footnpag.sty 712

242 footnpag 712

146 lwarp-foreign.sty 712

243 foreign 712

147 lwarp-forest.sty 712

244 forest 712

148 lwarp-framed.sty 713

245 framed 713

149 lwarp-ftnright.sty 715

246 ftnright 715

150 lwarp-fullminipage.sty 715

247 fullminipage 715

151 lwarp-fullpage.sty 716

248 fullpage 716

152 lwarp-fullwidth.sty 716

249 fullwidth 716

153 lwarp-fwlw.sty 716

250 fwlw 716

154 lwarp-gentombow.sty 717

251 gentombow 717

155 lwarp-geometry.sty 717

252 geometry 717

156 lwarp-gloss.sty 717

253 gloss 717

157 lwarp-glossaries.sty 718

254 glossaries 718

158 lwarp-gmeometric.sty 720

255 gmeometric 720

159 lwarp-graphics.sty 720

256 graphics 720

256.1 Graphics extensions 721
256.2 Length conversions and graphics options 721
256.3 Printing HTML styles 724
256.4 \includegraphics 724
256.5 Boxes 730

160 lwarp-graphicx.sty 733

257 graphicx 733

161 lwarp-grffile.sty 733

258 grffile 733

162 lwarp-grid.sty 733

259 grid 733

163 lwarp-grid-system.sty 733

260 grid-system 733

164 lwarp-gridset.sty 734

261 gridset 734

165 lwarp-hang.sty 734

262 hang 734

166 lwarp-hanging.sty 736

263 hanging 736

167 lwarp-hypcap.sty 737

264 hypcap 737

168 lwarp-hypdestopt.sty 737

265 hypdestopt 737

169 lwarp-hypernat.sty 737

266 hypernat 737

170 lwarp-hyperref.sty 737

267 hyperref 737

171 lwarp-hyperxmp.sty 743

268 hyperxmp 743

172 lwarp-hyphenat.sty 743

269 hyphenat 743

173 lwarp-idxlayout.sty 744

270 idxlayout 744

174 lwarp-ifoddpage.sty 744

271 ifoddpage 744

175 lwarp-imakeidx.sty 745

272 imakeidx 745

176 lwarp-index.sty 749

273 index 749

177 lwarp-intopdf.sty 750

274 intopdf 750

178 lwarp-karnaugh-map.sty 751

275 karnaugh-map 751

179 lwarp-keyfloat.sty 754

276 keyfloat 754

180 lwarp-layaureo.sty 756

277 layaureo 756

181 lwarp-layout.sty 756

278 layout 756

182 lwarp-layouts.sty 756

279 layouts 756

183 lwarp-leading.sty 759

280 leading 759

184 lwarp-letterspace.sty 759

281 letterspace 759

185 lwarp-lettrine.sty 760

282 lettrine 760

186 lwarp-lineno.sty 760

283 lineno 760

187 lwarp-lips.sty 763

284 lips 763

188 lwarp-listings.sty 763

285 listings 763

189 lwarp-lltjext.sty 767

286 lltjext 767

190 lwarp-longtable.sty 768

287 longtable 768

191 lwarp-lscape.sty 771

288 lscape 771

192 lwarp-ltablex.sty 771

289 ltablex 771

193 lwarp-ltcaption.sty 772

290 ltcaption 772

194 lwarp-ltxgrid.sty 772

291 ltxgrid 772

195 lwarp-ltxtable.sty 773

292 ltxtable 773

196 lwarp-lua-check-hyphen.sty 773

293 lua-check-hyphen 773

197 lwarp-lua-visual-debug.sty 773

294 lua-visual-debug 773

198 lwarp-luacolor.sty 773

295 luacolor 773

199 lwarp-luatodonotes.sty 774

296 luatodonotes 774

200 lwarp-magaz.sty 776

297 magaz 776

201 lwarp-makeidx.sty 776

298 makeidx 776

202 lwarp-manyfoot.sty 777

299 manyfoot 777

203 lwarp-marginal.sty 779

300 marginal 779

204 lwarp-marginfit.sty 779

301 marginfit 779

205 lwarp-marginfix.sty 779

302 marginfix 779

206 lwarp-marginnote.sty 780

303 marginnote 780

207 lwarp-marvosym.sty 780

304 marvosym 780

208 lwarp-mcaption.sty 781

305 mcaption 781

209 lwarp-mdframed.sty 781

306 mdframed 781
306.1 Limitations . . . 781
306.2 Package loading . . . 782
306.3 Patches . . . 782
306.4 Initial setup . . . 783
306.5 Color and length HTML conversion . . . 783
306.6 Environment encapsulation . . . 783
306.7 Mdframed environment . . . 785
306.8 Titles and subtitles . . . 786
306.9 New environments . . . 788

210 lwarp-memhfixc.sty 790

307 memhfixc 790

211 lwarp-metalogo.sty 790

308 metalogo 790

212 lwarp-mhchem.sty 791

309 mhchem 791

213 lwarp-microtype.sty 793

310 microtype 793

214 lwarp-midfloat.sty 794

311 midfloat 794

215 lwarp-midpage.sty 794

312 midpage 794

216 lwarp-morefloats.sty 794

313 morefloats 794

217 lwarp-moreverb.sty 794

314 moreverb 794

218 lwarp-mparhack.sty 796

315 mparhack 796

219 lwarp-multicap.sty 796

316 multicap 796

220 lwarp-multicol.sty 796

317 multicol 796

221 lwarp-multicolrule.sty 798

318 multicolrule 798

222 lwarp-multirow.sty 798

319 multirow 798
319.1 Multirow 798
319.2 Combined multicolumn and multirow 800

223 lwarp-multitoc.sty 801

320 multitoc 801

224 lwarp-musicography.sty 801

321 musicography 801

225 lwarp-nameauth.sty 803

322 nameauth 803

226 lwarp-nameref.sty 804

323 nameref 804

227 lwarp-natbib.sty 804

324 natbib 804

228 lwarp-nccfancyhdr.sty 805

325 nccfancyhdr 805

229 lwarp-needspace.sty 806

326 needspace 806

230 lwarp-nextpage.sty 806

327 nextpage 806

231 lwarp-nicefrac.sty 807

328 nicefrac 807

232 lwarp-niceframe.sty 807

329 niceframe 807

233 lwarp-nomencl.sty 808

330 nomencl 808

234 lwarp-nonfloat.sty 808

331 nonfloat 808

235 lwarp-nonumonpart.sty 809

332 nonumonpart 809

236 lwarp-nopageno.sty 809

333 nopageno 809

237 lwarp-notes.sty 809

334 notes 809

238 lwarp-notespages.sty 810

335 notespages 810

239 lwarp-nowidow.sty 810

336 nowidow 810

240 lwarp-ntheorem.sty 811

337 ntheorem 811

337.1 Limitations . . . 811
337.2 Options . . . 811
337.3 Remembering the theorem style . . . 812
337.4 HTML cross-referencing . . . 815
337.5 \newtheoremstyle . . . 815
337.6 Standard styles . . . 815
337.7 Additional objects . . . 817
337.8 Renewed standard configuration . . . 817
337.9 amsthm option . . . 818
337.10 Ending a theorem . . . 820
337.11 \NoEndMark . . . 821
337.12 List-of . . . 821
337.13 Symbols . . . 821
337.14 Cross-referencing . . . 822

241 lwarp-octave.sty 822

338 octave 822

242 lwarp-overpic.sty 823

339 overpic 823

243 lwarp-pagegrid.sty 824

340 pagegrid 824

244 lwarp-pagenote.sty 824

341 pagenote 824

245 lwarp-pagesel.sty 824

342 pagesel 824

246 lwarp-paralist.sty 824

343 paralist 824

247 lwarp-parnotes.sty 825

344 parnotes 825

248 lwarp-parskip.sty 826

345 parskip 826

249 lwarp-pbox.sty 826

346 pbox 826

250 lwarp-pdfcomment.sty 827

347 pdfcomment 827

251 lwarp-pdflscape.sty 827

348 pdflscape 827

252 lwarp-pdfmarginpar.sty 827

349 pdfmarginpar 827

253 lwarp-pdfpages.sty 828

350 pdfpages 828

254 lwarp-pdfprivacy.sty 830

351 pdfprivacy 830

255 lwarp-pdfrender.sty 830

352 pdfrender 830

256 lwarp-pdfsync.sty 831

353 pdfsync 831

257 lwarp-pdftricks.sty 831

354 pdftricks 831

258 lwarp-pdfx.sty 832

355 pdfx 832

259 lwarp-perpage.sty 832

356 perpage 832

260 lwarp-pfnote.sty 833

357 pfnote 833

261 lwarp-phfqit.sty 833

358 phfqit 833

262 lwarp-pifont.sty 834

359 pifont 834

263 lwarp-placeins.sty 834

360 placeins 834

264 lwarp-plarydshln.sty 835

361 plarydshln 835

265 lwarp-plext.sty 835

362 plext 835

266 lwarp-plextarydshln.sty 836

363 plextarydshln 836

267 lwarp-plextcolortbl.sty 836

364 plextcolortbl 836

268 lwarp-prelim2e.sty 836

365 prelim2e 836

269 lwarp-prettyref.sty 837

366 prettyref 837

270 lwarp-preview.sty 837

367 preview 837

271 lwarp-psfrag.sty 837

368 psfrag 837

272 lwarp-psfragx.sty 838

369 psfragx 838

273 lwarp-pst-eps.sty 838

370 pst-eps 838

274 lwarp-pstool.sty 839

371 pstool 839

275 lwarp-pstricks.sty 840

372 pstricks 840

276 lwarp-pxatbegshi.sty 840

373 pxatbegshi 840

277 lwarp-pxeveryshi.sty 840

374 pxeveryshi 840

278 lwarp-pxftnright.sty 840

375 pxftnright 840

279 lwarp-pxjahyper.sty 841

376 pxjahyper 841

280 lwarp-quotchap.sty 841

377 quotchap 841

281 lwarp-quoting.sty 842

378 quoting 842

282 lwarp-ragged2e.sty 842

379 ragged2e 842

283 lwarp-realscripts.sty 843

380 realscripts 843

284 lwarp-refcheck.sty 844

381 refcheck 844

285 lwarp-register.sty 844

382 register 844

286 lwarp-relsize.sty 845

383 relsize 845

287 lwarp-repeatindex.sty 846

384 repeatindex 846

288 lwarp-resizegather.sty 847

385 resizegather 847

289 lwarp-rmpage.sty 847

386 rmpage 847

290 lwarp-romanbar.sty 848

387 romanbar 848

291 lwarp-romanbarpagenumber.sty 848

388 romanbarpagenumber 848

292 lwarp-rotating.sty 848

389 rotating 848

293 lwarp-rotfloat.sty 849

390 rotfloat 849

294 lwarp-rviewport.sty 850

391 rviewport 850

295 lwarp-savetrees.sty 850

392 savetrees 850

296 lwarp-scalefnt.sty 850

393 scalefnt 850

297 lwarp-schemata.sty 850

394 schemata 850

298 lwarp-scrextend.sty 851

395 scrextend 851

299 lwarp-scrhack.sty 854

396 scrhack 854

300 lwarp-scrlayer.sty 854

397 scrlayer 854

301 lwarp-scrlayer-notecolumn.sty 855

398 scrlayer-notecolumn 855

302 lwarp-scrlayer-scrpage.sty 856

399 scrlayer-scrpage 856

303 lwarp-scrpage2.sty 857

400 scrpage2 857

304 lwarp-section.sty 858

401 section 858

305 lwarp-sectionbreak.sty 859

402 sectionbreak 859

306 lwarp-sectsty.sty 859

403 sectsty 859

307 lwarp-semantic-markup.sty 860

404 semantic-markup 860

308 lwarp-setspace.sty 861

405 setspace 861

309 lwarp-shadow.sty 862

406 shadow 862

310 lwarp-showidx.sty 862

407 showidx 862

311 lwarp-showkeys.sty 862

408 showkeys 862

312 lwarp-showtags.sty 863

409 showtags 863

313 lwarp-sidecap.sty 863

410 sidecap 863

314 lwarp-sidenotes.sty 864

411 sidenotes 864

315 lwarp-SIunits.sty 865

412 SIunits 865

316 lwarp-siunitx.sty 866

413 siunitx 866

317 lwarp-soul.sty 871

414 soul 871

318 lwarp-soulpos.sty 872

415 soulpos 872

319 lwarp-soulutf8.sty 873

416 soulutf8 873

320 lwarp-splitidx.sty 873

417 splitidx 873

321 lwarp-srcltx.sty 875

418 srcltx 875

322 lwarp-srctex.sty 875

419 srctex 875

323 lwarp-stabular.sty 875

420 stabular 875

324 lwarp-stfloats.sty 876

421 stfloats 876

325 lwarp-struktex.sty 876

422 struktex 876

326 lwarp-subcaption.sty 877

423 subcaption 877

327 lwarp-subfig.sty 878

424 subfig 878

328 lwarp-subfigure.sty 882

425 subfigure 882

329 lwarp-supertabular.sty 883

426 supertabular 883

330 lwarp-syntonly.sty 884

427 syntonly 884

331 lwarp-tablefootnote.sty 885

428 tablefootnote 885

332 lwarp-tabls.sty 885

429 tabls 885

333 lwarp-tabularx.sty 885

430 tabularx 885

334 lwarp-tabulary.sty 886

431 tabulary 886

335 lwarp-tascmac.sty 886

432 tascmac 886

336 lwarp-textarea.sty 888

433 textarea 888

337 lwarp-textcomp.sty 888

434 textcomp 888
434.1 Limitations . . . 888
434.2 Package loading . . . 889
434.3 HTML symbols . . . 889
434.3.1 pdfLaTeX symbols . . . 889
434.3.2 XeLaTeX and LuaLaTeX symbols . . . 889
434.4 HTML diacritics . . . 890

338 lwarp-textfit.sty 892

435 textfit 892

339 lwarp-textpos.sty 892

436 textpos **892**

340 lwarp-theorem.sty 893

437 theorem **893**
437.1 Remembering the theorem style 893
437.2 css patches 895

341 lwarp-thinsp.sty 897

438 thinsp **897**

342 lwarp-threadcol.sty 897

439 threadcol **897**

343 lwarp-threeparttable.sty 897

440 threeparttable **897**

344 lwarp-threeparttablex.sty 898

441 threeparttablex **898**

345 lwarp-thumb.sty 899

442 thumb **899**

346 lwarp-thumbs.sty 899

443 thumbs **899**

347 lwarp-tikz.sty 900

444 tikz **900**

348 lwarp-titleps.sty 901

445 titleps **901**

349 lwarp-titleref.sty 904

446 titleref **904**

350 lwarp-titlesec.sty 904

447 titlesec 904

351 lwarp-titletoc.sty 906

448 titletoc 906

352 lwarp-titling.sty 908

449 titling 908

353 lwarp-tocbasic.sty 912

450 tocbasic 912

354 lwarp-tocbibind.sty 913

451 tocbibind 913

355 lwarp-tocenter.sty 914

452 tocenter 914

356 lwarp-tocloft.sty 915

453 tocloft 915

357 lwarp-tocstyle.sty 921

454 tocstyle 921

358 lwarp-todo.sty 921

455 todo 921

359 lwarp-todonotes.sty 922

456 todonotes 922

360 lwarp-tram.sty 924

457 tram 924

361 lwarp-transparent.sty 924

458 transparent 924

362 lwarp-trimclip.sty 925

459 trimclip 925

363 lwarp-trivfloat.sty 925

460 trivfloat 925
460.1 Combining \newfloat, \trivfloat, and algorithmicx 926

364 lwarp-truncate.sty 926

461 truncate 926

365 lwarp-turnthepage.sty 927

462 turnthepage 927

366 lwarp-twoup.sty 927

463 twoup 927

367 lwarp-typearea.sty 927

464 typearea 927

368 lwarp-typicons.sty 928

465 typicons 928

369 lwarp-ulem.sty 928

466 ulem 928

370 lwarp-umoline.sty 930

467 umoline 930

371 lwarp-underscore.sty 931

468 underscore 931

372 lwarp-units.sty 931

469 units 931

373 lwarp-unitsdef.sty 932

470 unitsdef 932

374 lwarp-upref.sty 932

471 upref 932

375 lwarp-url.sty 933

472 url 933

376 lwarp-uspace.sty 933

473 uspace 933

377 lwarp-verse.sty 933

474 verse 933

378 lwarp-versonotes.sty 935

475 versonotes 935

379 lwarp-vertbars.sty 935

476 vertbars 935

380 lwarp-vmargin.sty 936

477 vmargin 936

381 lwarp-vowel.sty 936

478 vowel 936

382 lwarp-vpe.sty 937

479 vpe **937**

383 lwarp-vwcol.sty 937

480 vwcol **937**

384 lwarp-wallpaper.sty 939

481 wallpaper **939**

385 lwarp-watermark.sty 940

482 watermark **940**

386 lwarp-widows-and-orphans.sty 940

483 widows-and-orphans **940**

387 lwarp-wrapfig.sty 940

484 wrapfig **940**

388 lwarp-xbmks.sty 941

485 xbmks **941**

389 lwarp-xcolor.sty 942

486 xcolor **942**
486.1 Limitations . . . 942
486.2 xcolor definitions: location and timing . . . 942
486.3 Package loading . . . 944
486.4 Remembering and restoring original definitions . . . 944
486.5 HTML color style . . . 945
486.6 HTML border . . . 946
486.7 High-level macros . . . 946
486.8 Row colors . . . 951

390 lwarp-xechangebar.sty 952

487 xechangebar **952**

391 lwarp-xellipsis.sty 952

488 xellipsis 952

392 lwarp-xetexko-vertical.sty 953

489 xetexko-vertical 953

393 lwarp-xfakebold.sty 953

490 xfakebold 953

394 lwarp-xfrac.sty 954

491 xfrac 954

395 lwarp-xltabular.sty 956

492 xltabular 956

396 lwarp-xltxtra.sty 957

493 xltxtra 957

397 lwarp-xmpincl.sty 957

494 xmpincl 957

398 lwarp-xpiano.sty 958

495 xpiano 958

399 lwarp-xpinyin.sty 958

496 xpinyin 958

400 lwarp-xtab.sty 959

497 xtab 959

401 lwarp-xunicode.sty 960

498 xunicode 960

402 lwarp-xurl.sty 961

499 xurl 961

403 lwarp-xy.sty 962

500 xy 962

404 lwarp-zhlineskip.sty 962

501 zhlineskip 962

405 lwarp-zwpagelayout.sty 963

502 zwpagelayout 963

406 lwarp-patch-komascript.sty 964

503 patch-komascript 964

407 lwarp-patch-memoir.sty 966

504 patch-memoir 966

504.1 Packages . . . 967
504.2 Preliminary setup . . . 968
504.3 Laying out the page . . . 968
504.4 Text and fonts . . . 970
504.5 Titles . . . 971
504.6 Abstracts . . . 971
504.7 Docment divisions . . . 971
504.8 Pagination and headers . . . 974
504.9 Paragraphs and lists . . . 975
504.10 Contents lists . . . 976
504.11 Floats and captions . . . 980
504.12 Page notes . . . 983
504.13 Decorative text . . . 984
504.14 Poetry . . . 985
504.15 Boxes, verbatims and files . . . 985
504.16 Cross referencing . . . 986
504.17 Back matter . . . 987
504.18 Miscellaneous . . . 988
504.19 ccaption emulation . . . 988
504.20 Final patchwork . . . 990

Change History 991

505 Chg Hist 991

Index of Objects 1017

General Index 1037

Troubleshooting Index 1041

Index of Indexes 1046

List of Figures

1 tutorial.tex listing 93

List of Tables

1 Typesetting conventions 75
2 LaTeX lwarp package — Supported features 76
3 Required software programs 86
4 Configuration files created by print version 95
5 lwarp package options 110
6 HTML settings 114
7 Literal character macros 170
8 Section HTML headings for word-processor conversion 178
9 Section depths and HTML headings 192
10 Tabular baseline 414
11 Tabular HTML column conversions 414
12 Cross-referencing data structures 457
13 Float data structures 467
14 amsthm package — CSS styling of theorems and proofs 593
15 Ntheorem package — CSS styling of theorems and proofs 811
16 Theorem package — CSS styling of theorems and proofs 893

2 Updates

The following is a summary of updates to lwarp, highlighting new features and any special changes which must be made due to improvements or modifications in lwarp itself.

For a detailed list of the most recent changes, see the end of the Change History on page 1016.

v0.68: Error handling, tabulars, footnotes.

lwarpmk
- *lwarpmk*: Improved error handling for image generation if compile was incomplete.
- `tabular`: Fix for `\warpprintonly`.

packages
- longtable: Improved flexibility for `\endhead`, etc. Improved error reporting if `\endhead`, etc. incorrect for lwarp.
- threeparttable: Fix for caption type.
- hyperref: Fix for options with braces.
- morefloats: Fix to be loaded early for print output.
- listings: Updated for v1.7.
- Added bigfoot, fnpara, footnotebackref, manyfoot, tablefootnote, threeparttablex.
- Added layouts, niceframe, perpage, showtags.
- Prevented alg, algorithmic, pdfcprot, fncylab.

v0.67: Filename generation, symbol fonts.

docs
- Documentation fix for `<project>-images`, `<project>-images.txt`.
- Added discussion regarding section names. See section 9.4.

filenames
- Added `\FilenameNullify` and `\FilenameSimplify` for filename generation. See section 9.4.
- Core, textcomp, xunicode: Nullified additional symbols during filename generation.

packages
- color: Fix for version number warnings.
- Added academicons, bbding, dingbat, eurosym, fontawesome, fontawesome5, marvosym, pifont, typicons.
- Added changes, easyReview, fitbox, foreign, gloss, karnaugh-map, multicap, nomencl, notes, struktex, umoline, xfakebold.
- Tested to work as-is with askmaps, curves, euro, karnaughmap, tikz-karnaugh.

v0.66: xr, multiple projects, image names/directory, HTML formatting

⚠ Reset the configuration
- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

lateximage
- Adds options `ImagesDirectory` and `ImagesName` to assign directory and name prefixes for `lateximage` images. The new defaults include the jobname, allowing the image directories for multiple projects to coexist.

⚠ existing projects
- To reuse existing `lateximage` directories, add lwarp options

```
\usepackage[
  ImagesDirectory={lateximages},
  ImagesName={lateximage-}
]{lwarp}
```

  If not reused, the existing `lateximages` directory and `lateximages.txt` file may be removed.

filenames
- Added `\FilenameLimit` to control the maximum length of the filenames generated by lwarp.

⚠ Possible filename changes
- Improved filename generation when special characters or macros are used in section names.

Windows
- Fix for **`lwarpmk cleanlimages`** with Windows.

floats
- Fixes for floats in the home page.

lists, table notes
- Improved css for definition lists, table notes.

tabular
- `tabular`: Fixes for `\par` in column specifier, minipage inside `tabular`.

indexing
- Indexing: Fix for a long line of multiple entries.

minipage
- `\minipagefullwidth`: Fix for global changes.
- Added `\UseMinipageWidths` and `\IgnoreMinipageWidths`. See section 9.3.3.

colors
- Improved `\fbox`, `\fboxBlock`, `\fminipage` to use current text color.

HTML
- Improved HTML output formatting.

docs
- Added discussion regarding invalid HTML. See section 9.1.1.
- Added discussion regarding math in section names, `\imagegraphics` `scale` option. See section 7.
- Added discussion regarding international languages in section names. See section 9.14.

packages
- caption: Fix for options clash.
- xr, xr-hyper: Now compatible.
- subcaption: Improved horizontal spacing.
- multicol: Fix for minipage inside `multicols`.
- multicolrule: Updated for v1.2.
- tocbasic: Minor update.
- acronym: Fix for acronym in float caption.
- kotexutf: Patch with *pdflatex* and new lwarp labels.
- extramarks, fancyhdr: Updated for v3.10.
- memoir: Added docs regarding version numbers. See section 9.13.
- zref: No longer required.
- Added ar, ed, indentfirst, nameauth, truncate.
- Verified to work as-is with changelog.
- Prevented colortab, epsf, hyper, picinpar, picins, sistyle, ucs.

v0.65: CSS layout, `alt` tags, Japanese.

page layout
- Moved the sideTOC to the left side, allowing improved CSS for margin notes.
- Improved page layout CSS.

image `alt` tags
- graphicx `\includegraphics`: Added the `alt` key to assign an `alt` tag to an image. Default is "`(image)`", assigned to pass validation.

duplicate HTML files
- Detects and causes an error if duplicate HTML file names are generated, caused by identical or similar sectioning names.

fixes
- Fix for `tabular*`.
- Fix for tabular border colors.
- Fixes `\quad`, `\enskip`, and figure captions to pass validation.

Japanese
- Added ltj* classes, bounddvi, gentombow, lltjext, plarydshln, plext, plextarydshln, plextcolortbl, pxatbegshi, pxeveryshi, pxftnright, pxjahyper, tascmac.
- Verified to work with plarray, plautopatch, plextarray, plextdelarray, pxgentombow, plsiunitx, pxpdfpages, pxpgfrcs, pxpgfmark.

packages
- Added support for fontspec `\textsi` and `\sishape`.
- Added multicol's `\docolaction`.
- Added embrac, footnoterange, multicolrule, versonotes.

v0.64: Koma-Script, Japanese, Chinese.

Japanese
- Added utarticle and related classes.
- Improved ujarticle and related classes.

Chinese
- Fix for biblatex with CTEX and other classes.

Koma-Script
- Fixes for scrlayer, scrlayer-scrpage.

packages
- addlines: Updated to v0.3.
- Added bsheaders, gmeometric, marginal, rmpage, scrpage2.

v0.63: mdframed, Chinese, Japanese, Korean

localization
- Added `\linkhomename`: A user-definable name for the **Home** link.
- Documented `\sidetocname`: A user-definable name for the sideTOC.

fixes
- Fix: `\LinkHome` for print output.

optimizations
- Moved package load checks to the lwarp core to reduce the number of `lwarp-*` files.

packages
- mdframed: Fix with amsthm, improved titles and font control. Improved rule widths.

Chinese
- Fixes for xeCJK.
- Added xpinyin, zhlineskip.
- Verified to work with cjkpunct, upzhkinsoku, zhspacing.

Japanese
- Verified to work with zxjatype, luatexja, luatexja-fontspec.
- Added bxjsarticle and related classes.
- Added ltjsarticle and related classes.
- Added pLaTeX, upLaTeX, ujarticle and related classes.

- Prevented utarticle and related classes.
- Prevented bxcjkatype.

Korean
- Verified to work with kotex, xetexko, luatexko.

v0.62: MiKTEX docs, HTML title, CTEX, xeCJK, bitpattern.

docs
- Docs: Setting a UTF-8 locale. See section 10.8.

MiKTEX
- MiKTEX: Docs for *MiKTeX Console* and miktex-poppler-bin.

HTML <title>
- HTML subpage titles: Added \HTMLTitleBeforeSection and \HTMLTitleAfterSection to select whether the HTML <title> displays the website name before or after the section name. See section 8.4.

fixes
- Fix for package options handling.
- Fixes for horizontal white space between fminipage, fcolorminipage, colorboxBlock, fcolorboxBlock.
- Logos: Fix for XƎTEX logo, improved CSS, made robust, improved search-engine optimization.
- \\[$1]: Additional HTML <br> if $1 > 0 pt.
- Fixes for \includgraphics filename, and with FormatWP.
- Fix: CSS for \textup.
- Fix: Added \slshape.

Chinese
- Added ctex package and related classes, xeCJK.
- Prevented CJK, CJKutf8 unless xeCJK, ctex are used.

packages
- chemfig: Docs for new macro \polymerdelim.
- asymptote: Docs for compilation.
- chngpage: Fix to load lwarp-changepage.
- algorithm2e: Fix with non-book classes.
- register: Updated to v1.8.
- nicefrac: Improved font control and CSS, honors nice and ugly.
- units: Improved font control and CSS, honors tight and loose.
- xfrac: Improved CSS.
- textcomp and xunicode: Fix conflicts with \textcircled.
- ulem: Improved compatibility with CJKulem, lateximage.
- MathJax and siunitx: Removed inoperable extension.
- Added bitpattern, pdfcomment, pdfmarginpar, tram, unitsdef, xechangebar.
- Added musicography, octave, semantic-markup.
- Added 2in1, flippdf, notespages, rviewport, twoup.

v0.61: Custom compilation, EPS-related packages, documentation, indexes.

docs
- Split index into multiple indexes. See page 1046.
- Improved documentation regarding font selection. See section 8.2.
- Added documentation regarding debugging options. See section 35.

- Added documentation regarding HTML entities inside program listings. See section 9.2.1.

custom compiling

- Added options to specify the shell commands to execute for **`lwarpmk print`** and **`lwarpmk html`**, allowing the use of lwarp with perltex, pythontex, etc. If not specified, these are set automatically depending on the LaTeX engine, `--shell-escape`, and lwarp options. See section 10.

⚠ changed names

- Changed macro names to match `\displaymathother`, `\displaymathnormal`:

Old	New
`\StartDynamicMath`	`\inlinemathother`
`\StopDynamicMath`	`\inlinemathnormal`

fixes

- Fix: Paragraph tags in a `tabular`.
- Fix: supertabular and xtab captions.
- Fix: DVI LaTeX `\includegraphics` EPS images.
- Fix: newfloat lists.
- Fix: CSS footnotes text align, minipage tabular and footnote margins.

packages

- Added epsfig, psfrag, psfragx, pstool.
- Added copyrightbox, pdfprivacy, thinsp, threadcol, uspace.
- Added chkfloat, cmdtrack, dprogress, lua-visual-debug, refcheck, srcltx, srctex, vpe, xbmks.

v0.60: Fixes for longtable, listings.

fixes

- longtable, etc.: Fixes for slowdown and memory management for very long tables.
- listings: Fix for HTML entities, and also when used inside a list.
- diagbox: Fix for incorrect HTML par tags.

packages

- Added 2up, booklet.
- Added bophook, draftfigure, fullminipage, grid-system, layaureo.
- Added leading, widows-and-orphans.
- Added fancytabs, thumb, thumbs.

v0.59: DVI *latex*, MathJax, asymptote, pdftricks and pstricks, epstopdf, brqen.

⚠ Reset the configuration

- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

lwarpmk

- Added an error if `lwarpmk.conf`'s format has changed and the document must be recompiled.
- Added a warning if the `lwarpmk.conf` configuration file appears to be for the wrong operating system, in case files are transferred between systems.
- Added

  ```
  lwarpmk epstopdf <list-of-EPS-files>
  ```

  to quickly convert a document's EPS images to PDF or SVG. See section 9.8.

DVI *latex*

- Added support for DVI *latex*. See section 8.3.

latexmk
- Fix for `--shell-escape` with *latexmk*.

math
- Updated MathJax script to v2.7.4.
- Fix: Mathjax chapter number removed from non-numeric tagged equations.
- Added MathJax support for nicefrac, units.
- Fix for `\[` and `\]` with `\displaymathnormal`.

images
- Fix for `\includegraphics` filename expansion.
- `\includegraphics` now works with `.pdf` and `.eps` filename extensions.

packages
- Moved amsmath out of the lwarp core.
- Fix for chemformula `\NMR`.
- Added asymptote, pdftricks, pstricks, pst-eps.
- Added breqn, SIunits.
- Added bxpapersize, canoniclayout, draftcopy, fnbreak, nccfancyhdr.
- Added accsupp, axessibility.
- Added xunicode.
- Improved and now supports epstopdf.
- Tested to work as-is: eepic, sepfootnotes.

docs
- Added information about setting up a development version of lwarp.

v0.58: Extensive improvements in indexing, glossaries. Adds PDF-inclusion packages.

⚠ Reset the configuration
- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

lwarpmk
- *lwarpmk*: Added the `-p` option to specify the project name.

glossaries
- *lwarpmk*: Now uses *makeglossaries* for glossary generation, allowing the processing of multiple glossaries at once.
- Added lwarp option `GlossaryCmd` to specify the shell command used by **`lwarpmk printglossary`** and **`lwarpmk htmlglossary`**. Defaults to **`makeglossaries`**.

index and glossary
- Docs: Extra indexing options. See section 9.6.13.
- Added support for *makeindex*. (Previously supported only *xindy*.) Also added indexing packages listed below.
- Added lwarp options `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to specify shell commands used by **`lwarpmk printindex`**, **`lwarpmk htmlindex`**, and *latexmk*. May be preset with the `makeindex` or `xindy` lwarp options. See section 8.3.
- Added lwarp options `makeindex` and `xindy` to set `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to sensible values for a typical single index. See section 8.3.
- Added lwarp option `makeindexStyle` to tell *lwarpmk* to use a custom style instead of `lwarp.ist`. See section 9.6.19.
- Fix for index entries with `\see`, `\seealso`, `\emph`, `\textbf`, etc.

misc. fixes
- Replaced each `\csuse` with `\@nameuse` for improved error detection.
- Additional internal print/HTML macro selection improvements.

- Fix: `\printindex` finishes pending `\index` writes first.

packages
- Fixes for memoir: makeidx, ccaption, multiple indexes, `\specialindex`.
- Fixes for komascript: Indexing improvements.
- Added imakeidx, index, repeatindex, splitidx.
- Added attachfile, attachfile2, intopdf, pdfpages, pdfx.
- Added cases.
- Tested to work as-is: notes2bib, hvindex.

v0.57: algorithm2e, float styles, tabular packages, internal improvements.

MathJax
- Added support for MathJax equations with `\footnote`, `\footnotemark`.

math macros
- Added `\StartDefiningMath` and `\StopDefiningMath` for use when defining macros in the preamble which contain $. See section 9.7.7.

dynamic math
- Added `\inlinemathother` and `\inlinemathnormal` to delimit math expressions which depend on a variable condition such as a counter. Such expressions will not be hashed for reuse, and will be converted to SVG math images even when MathJax is enabled. See section 9.7.8.

⚠ new name
- Renamed `\EndDefiningTabulars` to `\StopDefiningTabulars`.

`lateximage alt` tags
- Improved localization for `lateximage` HTML `alt` tags. For SVG math images, the `alt` tag under some conditions will be set to `\mathimagename`, which defaults to "math image". For packages, the `alt` tag is set using the package name followed by `\packagediagramname`, which defaults to "diagram". Ex:

  ```
  (-xy- diagram)
  ```

  See section 8.4.
- Fix: Improved print/HTML macro selection.

misc. fixes
- Fix: `\href` text catcodes.
- Fix: `\subref` text.
- Fixes: Colored `\rule` and `\boxframe`.

packages
- float, rotfloat: Adds support for float styles `ruled` and `boxed`.
- float: Fix: Do not create `\l@<type>` until `\listof` is used.
- marginnote: Fix: Long optional argument.
- ellipsis: Adds `\midwordellipsis`.
- breakurl: Fix for text catcodes.
- Added algorithm2e, register, ltablex, xltabular, xellipsis, trimclip, errata, vowel, xpiano.
- Prevents glossary.
- Tested to work as-is with gauss, phonrule, piano, SIunits, tikzcodeblocks.

v0.56: Shell escape, tabular packages.

lwarpmk
- Added

  ```
  lwarpmk pdftosvg <list-of-PDF-files>
  ```

  to quickly convert a document's PDF images to SVG, for use with HTML. See section 9.8.

- Added support for `--shell-escape`. See section 8.1.

tabular
- Added support for array `w` and `W` columns.
- Fix: `\multicolumn` parameter handling.
- Added support for double `\hlines`, `\midrules`, and vertical rules.
- Added support for arydshln dashed lines with HTML `tabular`, but reverts to plain rules for `lateximage` and SVG math `array`.

misc. fixes
- Fix: `\thinspace`.
- Fix: paralist compact environments.

packages
- Added parnotes, quoting, lua-check-hyphen, tocenter, underscore.
- Tested to work as-is with babelbib, bibunits, bodegraph, fast-diagram, nicematrix, structmech.

v0.55: Various fixes.

misc fixes
- Fix: Extraneous space in file links, which also prevented *Calibre* EPUB conversions.
- Fix: Float optional argument regression.
- Fix: `\ForceHTMLTOC` with `\phantomsection`.
- Fix: Overfull boxes in `lateximages`.
- Fix: QED symbols in `lateximage`.

packages
- koma-script: Fix: Figure with `\centering`, etc.
- Added clrdblpg.

v0.54: Float `\centering`, improved image checks.

⚠ Reset the configuration
- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

lwarpmk
- `lwarpmk limages` checks for the presence of the HTML version of the document and valid image references before attempting to create the `lateximages`.
- *lwarpmk*: Improved error message if configuration file does not exist.

BibTeX
- Added documentation for avoiding error with BibTeX and `\etalchar`. See section 9.6.9.

polyglossia
- Added documentation regarding polyglossia. See section 9.15.4.

macros in section names
- Added documentation regarding the use of macros in section names. See section 9.1.

document encoding
⚠ New and revised encoding options
- Renamed and added package options:

Old Package Option	New Package Option
`xdyFilename`	`xindyStyle`
`IndexLanguage`	`xindyLanguage`
---	`xindyCodepage`
---	`pdftotextEnc`

Use these options along with inputenc or inputenx to process documents in an encoding other than UTF-8. See section 8.2.

floats with \centering, etc.

- Floats now honor \centering, \raggedright, \raggedleft, and their ragged2e equivalents, when placed directly after:

```
\begin{floattype}
\centering
```

misc. fixes

- tikz: \pgfpicture, fit, align, font.
- ragged2e: \centering etc.
- hyperref: \hypertarget was creating duplicate of \label.
- hyperref: Active chars inside \hyperref, \hyperlink.
- hyperref: \ref inside \hyperlink caused a nested HTML link.
- glossaries: Fix when not using babel or polyglossia.
- textcomp: \textperthousand.
- LaTeX core verse environment: line spacing.

⚠

- Removed \citetitle, adjusted \attribution.

packages

- memoir: Minor update for v3.7g.
- Added inputenx, bibunits, chngpage, forest, magaz, gridset.
- Prevents loading ae, aecc, t1enc, and wasysym.

v0.53: Improved image checks.

lwarpmk

- *lwarpmk*: Added a warning about corrupted images due to the need to recompile the document one more time.
- *lwarpmk*: Added the **lwarpmk cleanlimages** command.
- Added documentation for **lwarpmk cleanlimages** and **lwarpmk pdftohtml**.

v0.52: Improved footnotes, SVG math.

documentation

- Improved install instructions regarding lwarp_baseline_marker.png.
- Added documentation regarding footnotes in section headings, and footnotes with \VerbatimFootnotes from fancybox, fancyvrb. See section 9.5.4.
- Added documentation regarding font selection when using XeLaTeX or LuaLaTeX with fontspec and traditional font packages. See section 8.2.

SVG math

- Fix: Limit the number of background tasks when generating lateximages.
- Added user-adjustable SVG math font scaling. See section 79.3.
- Added warnings if lwarp_baseline_marker.png is not present, or if graphicx or graphics is not loaded.
- Improved \ensuremath hashing expansion.
- Fix: equation* with split.
- tabbing now works inside a lateximage. Use for math in tabbing.

MathJax

- Fix: MathJax script was not executing in some conditions.
- Added \CustomizeMathJax to add custom functions. See section 9.7.

footnotes

- Fix: Footnote numbering when using HTMLDebugComments.

- Fix: Footnote paragraph tags.
- Fix: `FootnoteDepth` defaults to `\subsubsection`.

misc. fixes
- Fix: `\kill` in a `lateximage`.
- Fix: `\FileDepth`, misc. others, when input encoding is not `utf8`.
- Fix: `\texorpdfstring` in a section name.

packages
- hyperref emulation: Fix for #, %, &, ~, _ characters in URLs.
- fancybox, fancyvrb: Initial support for `\VerbatimFootnotes`.
- nicefrac: Added with fix for `\ensuremath`.
- graphicx: Fix for option defaults. Added v1.1a/b options.
- endfloat: Updated for v2.6.
- url: Fixes for active characters.

v0.51: Improved SVG math, added numerous chemistry packages.

documentation
- Docs: Added Things to avoid.
- Docs: Added to Converting an existing document.
- Docs: Multiple authors and affiliations with custom classes. See section 9.6.1.
- Docs: tikz with matrices. See section 9.8.1.

SVG math
- Improved SVG math baseline.
- Improved SVG math font and color.
- Faster SVG math rendering.
- Improved support for display math containing complicated math objects, such as tikz-cd. See section 9.7.9.
- Fix: `\addcontentsline` inside SVG math.
- Fix: SVG math containing an embedded `lateximage`.

MathJax
- MathJax now handles `\ensuremath` in expressions.

misc. fixes
- Fix: Added `alignat` environment.
- Fix: afterpackage no longer required, which conflicted with scrlfile.
- Fix: titling `\thanks` mark.
- Fix: fancybox improvements.
- Fix: tikz `\tikz` macro. (Previously only the `tikzpicture` environment worked.)
- Fix: tikz with optional argument.

packages
- Added mhchem, chemfig, chemformula, chemmacros, chemnum, chemgreek, epstopdf-base, grid, ltxgrid.

v0.50: Improved SVG math.

SVG math
- SVG math and other `lateximages` now are converted to SVG using parallel background tasks, utilizing all available CPU cores.

- Inline SVG math image file names now are MD5 hashes made from their source LaTeX code. Identical inline math expressions, such as multiple instance of x, now share a single image file. This reduces the number of images to store, transmit, process, and display. Each image file is only converted to SVG a single time, and reused if it already exists. Display math and other forms of SVG image such as `picture` and Ti*k*z still use individual image files which are recreated each time **`lwarpmk limages`** is run.
- Fixes: SVG math and/or `\underline` in a sectioning file name.
- Improved SVG display math and tags.
- Improved SVG math and siunitx `alt` tags.
- Improved siunitx units.
- Fix: `\ensuremath` with MathJax now creates a `lateximage`.
- Fix: `\centering`, etc. in SVG math, `lateximage`, Ti*k*z.

misc. fixes
- Fix: Made various macros robust, additionally fixing authblk.
- Fix: ntheorem if neither `standard` nor `amsthm` selected.
- Fix: listings: Improved column alignment.
- Fix: Load fontspec if necessary.

packages
- Added xy, epstopdf, diagbox, pbox, bytefield, axodraw2, phfqit, schemata, dblfloatfix, nonfloat, morefloats.

v0.49:

tabular
- Added xcolor `\rowcolors`.
- Fix: `\noalign` inside a `tabular`.

math
- Fix: `\eqref` in a caption.

misc fixes
- Fix: Incorrect PDF font size changes caused occasional HTML corruption.
- Fix: printlen changes are now grouped for HTML output.

packages
- Added vwcol, vertbars, hyphenat, lineno, fnlineno, figsize, hypdestopt, pagegrid, pdfrender, luacolor, resizegather.

v0.48:

documentation
- Added some documentation regarding converting an existing document. See section 7.

cleveref
- Updated compatibility for new cleveref v0.21.

tabular
- Fix: Ignores optional tabular column arguments.

minor updates
- Added `\leftline`, `\centerline`, `\rightline`.
- Lists have improved font control via `\makelabel`.
- Print-mode `lateximage` now boxed to the natural width of its multiline contents.
- `abstract` now allows an optional name, as required by some classes.

math
- Fix: Improved spacing, `\mbox`, and font sizes with SVG math, Ti*k*z.
- siunitx: Improved SVG math, fraction compatibility, color output.

misc. fixes
- Fix: LOF/LOT links.

- Fix: Virtual page size grouping caused excessive PDF page breaks.
- Fix: Parsing similar package names in a single `\usepackage`.
- Fix: Adapts to classes without `\part`.
- Fix: `\newline` in `\title` was causing `<br>` in window title.
- Fix: `\maketitle` with `\cr`, `\crcr`, `\noalign`, for IEEEtran class.
- Fix: xfrac neutralized `BlockClass` and others.
- Fix: todonotes and luatodonotes: Improved `\todototoc`.

packages
- Added colortbl, chapterbib, acro, acronym, hypernat, hypcap, stfloats, vmargin, fancyheadings.
- fancyref: Now directly supported.

v0.47:

math
- Improved SVG math baseline and sizing.
- Fixes: SVGmath in captions, subcaptions, `\nameref`.
- Fixes: Line wrap at hyphen in HTML output.

packages
- Added endheads, multitoc, sectionbreak, blowup, xurl.

v0.46:

⚠ name change
- `\PrintStack` changed to `\LWRPrintStack`.

misc. fixes
- Fix: Empty lines between `tabular` rows.
- Fix: Stack unnesting.
- Fix: SVG math and `lateximages` in numerous situations.
- Fix: Spaces in `\usepackage`.
- Fix: Now allows MathJax inside `verse`.

v0.45:

documentation
- Improved *MiKTeX* install instructions.
- Improved graphics and epstopdf instructions.
- Updates to the Introduction.

memoir
- Added memoir, memhfixc. See section 9.13.

cross-references
- Fix: Now allows underscores in labels.
- Fix: `\_` and `\<blank>` in section/file names.

math
- Fix: Now allows MathJax inside `tabbing`.

bibliography
- Fix: Bibliography `\em` names.
- Added cite, natbib, backref. (Also works as-is with biblatex.)

misc. fixes
- Fix: Empty lines between `tabular` rows.
- Fix: "Improper `\prevdepth`" with minipages, lists.
- Fix: Incorrect SVG math and `lateximages` with subfig.
- Fix: Lateximages from incorrect pages with Mathjax.
- Fix: Missing sidetoc if using listings.
- Fix: Added an array emulation package.

packages
- Added subfigure, prettyref, hanging, midpage, flafter, fltrace, changebar, endfloat, continue, fwlw, turnthepage, footnpag, pagesel, textfit, titleref.

v0.44:

koma-script
- Added koma-script classes (except scrlttr2, scrjura).
- Added scrextend, scrlayer, scrlayer-notecolumn, scrlayer-scrpage, scrhack, tocstyle, tocbasic.

HTML title and author
- Added `\HTMLTitle`. Fixed web page title if `\HTMLTitle` empty and no `\title` given and not using titling package.
- Fixed web page author if `\HTMLauthor` is empty and `\author` is not given.

encodings
- If using *pdflatex*, automatically loads T1 and UTF-8 encodings. (Additional fontenc encodings may be loaded after lwarp.)

lists
- Added `list` and `trivlist` environments, hang.

tabular
- Fix: `\multicolumn` alignment if formatting for a word processor.
- Added ltxtable.

math
- Fix: MathJax combined with `lateximages`.
- algorithmicx: Improved comment symbol and floating.

packages
- Completed todonotes and luatodonotes.
- Added todo, easy-todo, fixmetodonotes, fixme.
- Added soulutf8, soulpos, cancel.
- Added section, fancyref, ifoddpage.
- Added preview, atbegshi, watermark.
- Improved tocloft `\newlistof` and `\newlistentry`.

v0.43:

- Docs: Reorganized HTML customization, added an HTML settings table. See section 8.4.

footnotes
- Added `FootnoteDepth` to control the placement of pending footnotes before section breaks. By default, pending footnotes are printed before each `\subparagraph` or higher.

sectioning
- Fix: Expansion in section name.

tabular
- Fix: Ignore spaces in tabular column specification.
- Fix: Tabular rules at bottom or when finishing incomplete rows.
- Fix: `\multicolumn` at/bang/before/after specifications, trim, and vertical rules.
- Fix: supertabular and xtab column misalignment.

math
- Fix: `equation*`.
- Fix: SVG math in a section name.
- Fix: `\ref` and `\eqref` in SVG math.

packages
- Added todonotes and luatodonotes (but only `disabled`).
- Added breakurl.
- hyperref: Fix: Several macros were made robust, `\Gauge` added.

v0.42:

Support TEX!
- Added TEX development support page, Support TEX development.

word-processor conversion
- Improved assitance for word-processor conversions when boolean `FormatWP` is set `true`. See section 12.

⚠ name change
- The boolean `FormatWordProcessor` has been renamed `FormatWP`.

⚠ name change
- The boolean `HTMLMarkFloats` has been renamed `WPMarkFloats`.
- New booleans control whether to place additional marks around minipages, at the table of contents, at the LOF and LOT, and whether to print math as LATEX source for copy/paste into the *LibreOffice Writer TeXMaths* extension.
- Improved formatting for numerous objects. See section 12.

`tabbing`
- Add: `tabbing` environment.

overpic
- Add: overpic package. See section 339.

math
- Fix: Text copy/paste of $\mathcal{AMS}$ math environment numbers and names.
- Improved `\ensuremath`.
- MATHJAX with siunitx: Updated script and documentation.

symbols
- textcomp: Improved `\interrobangdown`.
- realscripts: Fix for subscripts in a `lateximage`.

load order
- morewrites: Enforces loading before lwarp.

v0.41:

`tabular`
- Added tabular vertical rules, subject to some limitations. See the rules section of section 9.10.
- Improved booktabs: Width and trim are honored.

⚠ new syntax
- Added `\mcolrowcell` for empty cells inside a `\multicolumnrow`. Use `\mcolrowcell` instead of `\mrowcell` for two-dimensional cells created by `\multicolumnrow`. Continue to use `\mrowcell` for empty cells in a `\multirow`. See section 319.2 on page 800.
- Fix: Unfinished tabular rows are automatically filled.
- Fix for tabular column specifiers while using babel-french. (`\NoAutoSpacing` is activated then nullified inside the tabular, due to a conflict with the tabular column parsing code.)

v0.40:

graphics, graphicx
- graphics and graphicx have been moved from the lwarp core, and are only loaded if requested with `\usepackage`.

`\includegraphics` path
- Improved graphics `\graphicspath` support. Multiple image directories may now be used.

⚠ image file extensions
- Refer to `.pdf` files without a file extension to allow the HTML version to use a `.svg`, `.png`, `.jpg`, or `.gif` version instead. See section 9.8.
- grffile is now directly supported instead of emulated.

bigdelim
- Fix for bigdelim, and improved documentation. See section 136.

symbols
- Improved LATEX and textcomp symbols.

fixes
- Fix for LaTeX logos and `\InlineClass`, etc. inside a `lateximage`.
- Fix for xltxtra with XeLaTeX.
- Fixes for tocbibind with `\simplechapter`, etc.
- Fixes for `\multicolumnrow` and `\nullfonts` with older versions of multirow and xparse.
- Added `\underline`.

margins
- Added adjmulticol.

columns
- Added cuted, midfloat.

footnotes
- Added pfnote, fnpos, dblfnote.

tabular
- Added stabular, tabls.

sectioning
- Added sectsty, anonchap, quotchap.

v0.39:

title pages
- Improved the titlepage HTML code, `\thanks` notes, and `\maketitle`. titling is no longer required, but is still supported. The `\published` and `\subtitle` fields are no longer provided, but `\AddSubtitlePublished` replicates them using titling. See section 65.8. authblk is added, and should be loaded before titling. See section 65.

⚠ `\published` and `\subtitle` load order

tabular
- `\multirow` now supports the new optional `vpos` argument.

multi column/row cell
- Added `\multicolumnrow` for combined `\multicolumn` and `\multirow`. See section 319.2.
- Tabular special cases:
  - Added `\TabularMacro` to mark custom macros inside tabular data cells, avoiding row corruption. See section 9.10.
  - Added `\ResumeTabular` for use when a `tabular` environment is defined inside another environment. See section 9.10.

⚠ macros inside tabular

⚠ tabular defined inside another environment

tabular
- Added supertabular, xtab, bigstrut, bigdelim.

margins
- Added fullwidth.

page layout
- Added addlines, anysize, a4, a4wide, a5comb, textarea, zwpagelayout, typearea, ebook.

v0.38:

forced single-pass compile
- Added **`lwarpmk print1`** and **`lwarpmk html1`** actions to force a compile of the project a single time. Useful when multiple passes are not needed, or changes were not detected.

starred sections
- Added `\ForceHTMLPage` and `\ForceHTMLTOC` to force a starred sectional unit onto its own HTML page and with its own TOC entry. See section 9.6.2.

updated tutorial
- Modified the tutorial to use the new `\ForceHTMLPage` and `\ForceHTMLTOC` macros.

packages
- Added appendix, tocbibind, fncychap, fix2col.

font size
- Added relsize, scalefnt.
- Added realscripts, metalogo, xltxtra.
- Added grffile, romanbar.

page numbering
- Added arabicfront, chappg, nonumonpart, nopageno, romanbarpagenumber.

front & back matter
- Docs: Improved description of the use of front/back matter. See section 9.6.
- Fix: color requests xcolor.
- Fix: `\part` for article class.

v0.37:

`\include` for HTML
- `\include` now maintains independent `.aux` files for HTML versions.

latexmk
- comment, used by lwarp, now maintains independent cut files for print and HTML versions, helping *latexmk* to better know whether to recompile.

accents and symbols
- Improved support for LaTeX accents, textcomp, siunitx symbols.

babel-french
- Improved babel-french handling for load order and ~ tilde.

v0.36:

- Recorganized the documentation section regarding special cases and limitations. (Section 9)
- Improved source formatting.

boxes and frames
- `\fbox` and related now use `\fboxsep` and `\fboxrule`.
- `\makebox` and `\framebox` now use width and position.
- `\fcolorbox` and related now work inside a `lateximage`.

babel-french
- babel-french: Improvements for French variants, load order, footnotes, ellipses.

footnotes
- Improved footnote numbering. `lateximage` footnotes now appear as regular footnotes to match the numbering of the print version. Also fixed a regression with MathJax.

siunitx
- Improved siunitx units.
- Fix for filenames while using MathJax.
- Fix for `\rule` when xcolor is not loaded.
- Added transparent, upref.

v0.35: Fix: `\textbf` and related.

v0.34:

⚠ Optional arguments
- `BlockClass`'s optional argument has been moved in front of the mandatory argument:

  `BlockClass[style]{class}` (NEW)

  instead of:

  `BlockClass{class}[style]` (OLD)

  This change makes it more consistent with LaTeX standards, and avoids problems with space between arguments.

⚠ Optional arguments
- Likewise, `\InlineClass`'s optional argument now comes before the mandatory arguments:

  `\InlineClass[style]{class}{text}`

spans with minipages
- Improved compatibility between spans, minipages, lists, frames, and math. Handles minipages and lists inside an HTML span, such as an `\fbox` containing a minipage, although with minimal HTML fomatting. See section 9.3.3.

framing minipages
- `\fboxBlock` is added to frame minipages, tables, and lists with full HTML formatting but no longer inline, and behaves as `\fbox` for print output. The `fminipage` environment is added for framed minipages, as an environment with full HTML formatting, and draws a framed minipage in print output. See section 9.3.5. `\fbox` and minipages now often work in SVG math and `lateximages`. MATHJAX supports `\fbox`, but not `\fboxBlock` nor `fminipage`.

`lateximage`, SVG math, `tabular`
- Improved compatibility between `lateximage` and `minipage`, `\parbox`, `\makebox`, `\fbox`, `\framebox`, `\raisebox`, `\scalebox`, `\reflectbox`, `tabular`, booktabs.
- Improved font control for `lateximagees` and SVG math.

`eqnarray`
- Added the `eqnarray` environments.

verbatim packages
- fancyvrb is no longer required (preloaded), but is still supported.
- Added verbatim and moreverb.

framing packages
- Added fancybox, boxedminipage2e and shadow.

list packages
- enumitem is no longer required, but is still supported.
- Added enumerate and paralist.
- titleps is no longer required, but is still supported.
- Added crop.
- Added rotfloat, marginfit, and several minor packages; see the change log.

babel-french
- Adds fixed-width HTML spaces around punctuation when using babel-french. LuaTEX does not yet use the extra punctuation spacing.

v0.33:

- Tabular `@` and `!` columns now havetheir own HTML columns.
- `&` catcode changes are localized, perhaps causing errors about the tab alignment character `&`, so any definitions of macros or environments which themselves contain `tabular` and `&` must be enclosed within `\StartDefiningTabulars` and `\StopDefiningTabulars` (previously called `\EndDefiningTabulars`. See section 43. This change is not required for the routine use of tables, but only when a table is defined inside another macro or environment, and while also using the `&` character inside the definition. This may include the use inside conditional expressions.
- Several math environments were incorrectly placed inline. Also, for amsmath with SVG math, the `fleqn` option has been removed, resulting in improved spacing for aligned equations.
- Bug fixes; see the changelog.

v0.32: Bug fixes; no source changes needed:

- *lwarpmk* has been adjusted to work with the latest *luatex*.
- Spaces in the `\usepackage` and `\RequirePackage` package lists are now accepted and ignored.
- Fix for the glossaries package and `\glo@name`.

v0.31: Bug fix; no source changes needed:

- Improved compatibility with keyfloat, including the new `keywrap` environment.

v0.30:

⚠ lwarp-newproject

- lwarp-newproject has been removed, and its functions have been combined with lwarp.

  To modify existing documents, remove from the document source:

  ```
  \usepackage{lwarp-newproject}
  ```

  The lwarp package now produces the configuration files during print output, and also accepts the option `lwarpmk` if desired.

⚠ HTML setup changes.

- A number of macros related to HTML settings have been converted to options, and other macros and options have been renamed to create a consistent syntax:

Old Macro	New Package Option
`\HomeHTMLFileName`	`HomeHTMLFilename`
`\HTMLFileName`	`HTMLFilename`
`\useLatexmk`	`latexmk`
`\warpOSwindows`	`OSWindows`

Old Package Option	New Package Option
`lwarpmklang`	`xindyLanguage`
(new)	`xindyStyle`

Old Macro	New Macro
`\MetaLanguage`	`\HTMLLanguage`
`\HTMLauthor`	`\HTMLAuthor`
`\NewHTMLdescription`	`\HTMLDescription`
`\SetFirstPageTop`	`\HTMLFirstPageTop`
`\SetPageTop`	`\HTMLPageTop`
`\SetPageBottom`	`\HTMLPageBottom`
`\NewCSS`	`\CSSFilename`

- Per the above changes, in existing documents, modify the package load of lwarp, such as:

  ```
  \usepackage[
      HomeHTMLFilename=index,
      HTMLFilename={},
      xindyLanguage=english
  ]{lwarp}
  ```

- The file `lwarp_html.xdy` has been renamed `lwarp.xdy`. To update each document's project:

  1. Make the changes shown above.
  2. Recompile the document in print mode. This updates the project's configuration files, and also generates the new file `lwarp.xdy`.

3. The old file `lwarp_html.xdy` may be deleted.

- The new lwarp package option `xindyStyle` may be used to tell *lwarpmk* to use a custom `.xdy` file instead of `lwarp.xdy`. See section 9.6.20.
- Improvements in index processing:
  - *xindy*'s language is now used for index processing as well as glossary.
  - Print mode without *latexmk* now uses *xindy* instead of *makeindex*.
  - *texindy*/*xindy* usage depends on *pdflatex* vs *xelatex*, *lualatex*.
  - For *pdflatex* and *texindy*, the `-C utf8` option is used. This is supported in modern distributions, but a customized `lwarpmk.lua` may need to be created for use with older distributions.

v0.29:

- Add: `lwarpmklang` option for lwarp-newproject and lwarp. Sets the language to use while processing the glossary. (As of v0.30, this has been changed to the `IndexLanguage` option.) (As of v0.54, this has been changed to the `xindyLanguage` option.)
- Fix: `\includegraphics` when no optional arguments.

v0.28:

- `\HTMLAuthor {`⟨*name*⟩`}` assigns HTML meta author if non-empty. Defaults to `\theauthor`.
- Booean `HTMLDebugComments` controls whether HTML comments are added for closing `<div>`s, opening and closing sections, etc.
- Boolean `FormatEPUB` changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.
- Boolean `FormatWordProcessor` changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments. Name changed to `FormatWP` as of v0.42.
- Boolean `HTMLMarkFloats` adds text marks around floats only if the boolean `FormatWordProcessor` is `true`. These make it easier to identify float boundaries, which are to be manually converted to word-processor frames. Name changed to `WPMarkFloats` as of v0.42.
- Updated for the new MathJax CDN repository.
- Adds tabulary.
- Supports the options syntax for graphics.
- Improved index references, now pointing exactly to their target.
- Adds glossaries. *lwarpmk* is modified to add `printglosssary` and `htmlglossary` actions.

3 Introduction

The lwarp project aims to allow a rich LaTeX document to be converted to a reasonable HTML5 interpretation, with only minor intervention on the user's part. No attempt has been made to force LaTeX to provide for every HTML-related possibility, and HTML cannot exactly render every possible LaTeX concept. Where compromise is necessary, it is desirable to allow the print output to remain typographically rich, and compromise only in the HTML conversion.

Several "modern" features of HTML5, CSS3, and SVG are employed to allow a fairly feature-rich document without relying on the use of JavaScript. Limited testing on older browsers shows that these new features degrade gracefully.

---

lwarp is a native LaTeX package, and operates by either patching or emulating various functions. Source-level compatibility is a major goal, but occasional user intervention is required in certain cases.

As a package running directly in LaTeX, lwarp has some advantages over other methods of HTML conversion. TeX itself is still used, allowing a wider range of TeX trickery to be understood. Lua expressions are still available with LuaTeX. Entire categories of LaTeX packages work as-is when used with lwarp: definitions, file handling, utilities, internal data structures and calculations, specialized math-mode typesetting for various fields of science and engineering, and anything generating plain-text output. Blocks of PDF output may be automatically converted to SVG images while using the same font and spacing as the original print document, directly supporting Ti*k*z and `picture`. Numerous packages are easily adapted for HTML versions, either by loading and patching the originals, or by creating nullified or emulated replacements, and all without resorting to external programming. As a result, several hundred packages have already been adapted (table 2), and an uncounted number more work as-is.

Packages have been selected according to several criteria: perceived importance, popularity lists, recent CTAN updates, CTAN topics, mention in other packages, support by other HTML conversion methods, and from sample documents taken from public archives. These include some "obsolete" packages as well.[1]

Assistance is also provided for modifying the HTML output to suit the creation of EPUB documents, and for modifying the HTML output to ease import into a word processor.

---

pdflatex, *xelatex*, or *lualatex* may be used, allowing lwarp to process the usual image formats. While generating HTML output, SVG files are used in place of PDF. Other formats such as PNG and JPG are used as-is.

[1] An amazing number of decades-old packages are still in use today.

SVG images may be used for math, and are also used for `picture`, Ti*k*z, and similar environments. The SVG format has better browser and e-book support than MathML (as of this writing), while still allowing for high-quality display and printing of images (again, subject to potentially bug-ridden[2] browser support).

Furthermore, SVG images allow math to be presented with the same precise formatting as in the print version. Math is accompanied by `<alt>` tags holding the LaTeX source for the expression, allowing it to be copy/pasted into other documents.[3] Custom LaTeX macros may be used as-is in math expressions, since the math is evaluated entirely inside LaTeX. An MD5 hash is used to combine multiple instances of the same inline math expression into a single image file, which then needs to be converted to SVG only a single time.

The MathJax JavaScript display engine may be selected for math display instead of using SVG images. Subject to browser support and Internet access, MathJax allows an HTML page to display math without relying on a large number of external image files.[4] lwarp maintains LaTeX control for cross-referencing and equation numbering, and attempts to force MathJax to tag equations accordingly.

A *texlua* program called *lwarpmk* is used to process either the print or HTML version of the document. A few external utility programs are used to finish the conversion from a LaTeX-generated PDF file which happens to have HTML5 tags, to a number of HTML5 plain-text files and accompanying images.

lwarp automatically generates the extra files necessary for the HTML conversion, such as CSS and `.xdy` files, and configuration files for the utility *lwarpmk*. Also included is a parallel version of the user's source document, `<sourcename>-html.tex`, which selects HTML output and then inputs the user's own source. This process allows both the printed and HTML versions to co-exist side-by-side, each with their own auxiliary files.

When requesting packages during HTML conversion, lwarp first looks to see if it has its own modified version to use instead of the standard LaTeX version. These `lwarp-packagename.sty` files contain code used to emulate or replace functions for HTML output.

[2] Firefox has had an on-again/off-again bug for quite some time regareding printing SVGs at high resolution.

[3] There seems to be some debate as to whether MathML is actually an improvement over LaTeX for sharing math. The author has no particular opinion on the matter, except to say that in this case LaTeX is much easier to implement!

[4] One SVG image file per math expression, except that duplicate inline math expressions are combined into a single file according to the MD5 hash function of its contents. A common scientific paper can easily include several thousand files, and in one case the MD5 hash cut the number of files in half and the rendering time by 30%.

3.1 Typesetting conventions

Font weight, family, and style are used to indicate various objects:

Table 1: Typesetting conventions

package	LaTeX package.
program	Program's executable name.
`option`	Program or package option.
`filename`	File name in the operating system.
Brand Name	Proper name for a program, operating system, etc.
`commands`	Commands to be entered by the user.
`code`	Program code.
`\macroname`	LaTeX macro.
`environment`	LaTeX environment.
`counter`	LaTeX counter.
`boolean`	LaTeX boolean.
`<element>`	HTML element.
`attribute`	HTML attribute.
User Interface	A user-interface item.
ACRO	Acronym.

3.2 Supported packages and features

Table 2 lists some of the various LaTeX features and packages which may be used. Many are tested to work as-is, some are patches for the original packages, and some are emulations written for source-level compatibility. Many are nullified as being irrelevent to HTML output.

Table 2: LaTeX lwarp package — Supported features

Category	Status and supported features.
Engines:	DVI LaTeX, pdfLaTeX, XeLaTeX, LuaLaTeX, upLaTeX
Compiling:	latexmk, perltex, pythontex, *make*, etc.
Classes:	article, book, report, scrartcl, scrbook, scrreprt, memoir, CJK-related as listed below.
Koma-script:	scrextend, scrhack, scrlayer. Others as listed below.
Memoir:	memhfixc
Languages:	babel, polyglossia. cjkpunct, xeCJK.
Chinese:	CTeX, ctex, upzhkinsoku, xpinyin, zhlineskip, zhspacing.
Japanese:	upLaTeX, LuaTeX-ja, gentombow, lltjext, plarray, plarydshln, plautopatch, plext, plextarray, plextarydshln, plextcolortbl, plextdelarray, pxatbegshi, pxeveryshi, pxftnright, pxgentombow, pxjahyper, pxpdfpages, pxpgfrcs, pxpgfmark, tascmac, zxjatype. bxjsarticle and related, ltjsarticle and related, luatexja, luatexja-fontspec, ujarticle and related, utarticle and related.
Korean:	kotex, luatexko, xetexko.

lwarp Supported Functions — continued

Category	Status
Page layout:	2in1, 2up, a4, a4wide, a5comb, addlines, anysize, atbegshi, blowup, booklet, bophook, bounddvi, bxpapersize, canoniclayout, changepage, chngpage, clrdblpg, continue, draftcopy, draftfigure, draftwatermark, ebook, everyshi, fancyhdr, fancytabs, flippdf, fullminipage, fullpage, fwlw, geometry, gmeometric, grid, grid-system, gridset, layaureo, layout, layouts, leading, ltxgrid, nccfancyhdr, notespages, nowidow, pagegrid, pdfprivacy, pagesel, preview, rmpage, scrlayer-scrpage, scrpage2, textarea, threadcol, thumb, thumbs, titleps, tocenter, turnthepage, twoup, typearea, vmargin, watermark, widows-and-orphans, zwpagelayout. Tested to work as-is: underlin.
Sectioning:	Adds `FileDepth` for splitting the HTML output. Files may be numbered sequentially or named according to section name. Common short words and punctuation are removed from the filenames. anonchap, bsheaders, fncychap, indentfirst, quotchap, section, sectionbreak, sectsty, titlesec. Tested to work as-is: secdot.
Table of contents, figures, tables:	Supported, with hyperlinks. multitoc, shorttoc, titletoc, tocbasic, tocbibind, tocloft, tocstyle.
Title page:	`\maketitle`, `titlepage`, authblk, titling.
Front & back matter:	abstract, appendix.
Indexing:	*makeindex* and *xindy* are supported, with hyperlinks. idxlayout, imakeidx, index, makeidx, repeatindex, splitidx. Tested to work as-is: hvindex.
Glossary:	gloss, glossaries and *xindy*, nomencl.
Bibliography:	babelbib, backref, biblatex, bibunits, chapterbib, cite, hypernat, natbib, showtags. Tested to work as-is: notes2bib.
Cross-references:	bookmark, breakurl, cleveref, fancyref, hypdestopt, hyperref, perpage, prettyref, titleref, url, varioref, xr, xr-hyper, xurl.
Margin notes:	marginal, marginfit, marginfix, scrlayer-notecolumn, versonotes.

lwarp Supported Functions — continued

Category	Status
Footnotes:	Adds `FootnoteDepth` to print footnotes at section breaks. bigfoot, dblfnote, endheads, endnotes, fnbreak, fnpara, fnpos, footmisc, footnote, footnotebackref, footnoterange, footnpag, manyfoot, marginnote, pagenote, parnotes, pfnote, sidenote, tablefootnote. Tested to work as-is: fixfoot, nccfoots, sepfootnotes.
Math:	Converted to SVG images with HTML `<alt>` tags containing the LaTeX source for the math expression. MathJax supported as an alternative. amsmath: $\mathcal{AMS}$ environments are supported. User-defined macros are available during converson, due to native LaTeX processing.
Theorems:	Native LaTeX theorems, amsthm, ntheorem, theorem.
Additional math:	Math fonts via SVG images, breqn, cases, resizegather, xfakebold, xy. Tested to work as-is: amscd, bm, braket, delarray, guass, nicematrix, pb-diagram, tikz-cd, etc.
Display math with `\displaymathother`:	Complicated math objects in display math, such as tikz-cd, etc.
Units and fractions:	nicefrac, Slunits, siunitx, units, unitsdef, xfrac. Tested to work as-is: Slunits.
Floats:	Appear where declared. capt-of, caption, cutwin, dblfloatfix, endfloat, fix2col, flafter, float, floatflt, floatrow, fltrace, hypcap, keyfloat, morefloats, multicap, newfloat, nonfloat, placeins, rotfloat, stfloats, subcaption, subfig, subfigure, subfloat, trivfloat, wrapfig.
Tabular:	`tabular` environment, array, arydshln, bigdelim, booktabs, colortbl, diagbox, longtable, ltablex, ltxtable, multirow, supertabular, tabularx, tabulary, threeparttable, threeparttablex, xltabular, xtab.

lwarp Supported Functions — continued

Category	Status
Graphics:	graphics and graphicx. `\includegraphics` supports `width`, `height`, `origin`, `angle`, and `scale` tags, and adds `class`. References to PDF files are changed to SVG, other image types are accepted as well. `\rotatebox` and `\scalebox` are supported as well as HTML can handle. rotating is emulated but all objects are unrotated. picture, tikz, and xy are converted to an SVG image. asymptote, epsfig, epstopdf, figsize, fitbox, grffile, overpic, psfrag, psfragx, pst-eps, pstool, pstricks, rviewport. Tested to work as-is: curves, eepic, tikz-3dplot.
xcolor:	Full package color names, any color models, and mixing. `\textcolor`, `\colorbox`, `\fcolorbox`. Enhanced for HTML compatibility.
Lists:	Standard LaTeX environments, enumerate, enumitem, hang, paralist.
Environments:	Standard LaTeX environments.
`minipage`, `\parbox`:	Some HTML5-imposed limitations. Nested minipages are supported. pbox.
Quotations:	copyrightbox, csquotes, epigraph, quoting, verse.
Verbatim:	fancyvrb, moreverb, shortvrb, verbatim.
Frames:	boxedminipage2e, fancybox, framed, mdframed, niceframe, shadow, vertbars.
Multi-columns:	adjmulticol, multicol, multicolrule, vwcol.
Margins:	fullwidth, hanging, midpage.
Line numbering:	fnlineno, lineno.
Direct formatting:	`\emph`, `\textsuperscript`, `\textbf`, etc are supported. `\bfseries`, etc. are only supported in some cases. cancel, ellipsis, embrac, enparen, hyphenat, lettrine, lips, lua-check-hyphen, luacolor, magaz, pdfrender, realscripts, relsize, scalefnt, soul, soulpos, soulutf8, textfit, thinsp, trimclip, truncate, ulem, umoline, underscore, uspace, xellipsis.
Acronyms:	acro, acronym.
Ordinals:	engord, fmtcount, nth.

lwarp Supported Functions — continued

Category	Status
Text ligatures:	Ligatures for symbols are supported. Ligatures for f, q, t are intentionally turned off because many simpler browsers do not display them correctly. Modern full-featured browsers re-create these ligatures on-the-fly.
Horizontal space:	HTML output for thin-unbreakable, unbreakable, `\enskip`, `\quad`, `\qquad`, `\hspace`.
Rules:	`\rule` with width, height, raise, text color.
HTML reserved characters:	`\&`, `\textless`, and `\textgreater` are converted to HTML entities.
Fonts:	Used as-is. Appear in SVG math expressions or embedded image environments.
Symbols:	Native LaTeX diacriticals, academicons, bbding, chemgreek, dingbat, eurosym, fontawesome, fontawesome5, marvosym, pifont, textalpha, textcomp, textgreek, typicons, xunicode. Tested to work as-is: euro, gensymb.
Files:	attachfile, attachfile2, hyperxmp, intopdf, pdfpages, pdfx, xmpincl.
Science and engineering:	algorithm2e, algorithmicx, ar, axodraw2, bitpattern, bytefield, chemfig, chemformula, chemgreek, chemmacros, chemnum, karnaugh-map, listings, mhchem, phfqit, register, struktex. Tested to work as-is: askmaps, blochsphere, bodegraph, bohr, circuitikz, elements, engtlc, fast-diagram, hepnicenames, heppennames, karnaughmap, linop, pgfgantt, physics, simpler-wick, slashed, structmech, tikz-karnaugh, tikzcodeblocks.
Arts and humanities:	foreign, forest, musicography, nameauth, octave, schemata, semantic-markup, vowel, xpiano. Tested to work as-is: phonrule, piano, tikz-dependency.
Admonitions:	notes.
Editorial:	changebar, changes, easy-todo, ed, errata, fixme, fixmetodonotes, pdfcomment, pdfmarginpar, todo, todonotes, tram, xechangebar. Tested to work as-is: changelog, easyReview.

lwarp Supported Functions — continued

Category	Status
Accessibility:	accsupp, axessibility.
Debug:	chkfloat, cmdtrack, dprogress, lua-visual-debug, refcheck, srcltx, srctex, vpe, xbmks.
Working as-is:	Various utility, calculation, file, and text-only packages, such as calc, fileerr, somedefs, trace, xspace. Also, most math-only packages, including specialized typesetting for various fields of science and engineering.

4 Alternatives

Summarized below are several other ways to convert a LaTeX or other document to HTML. Where an existing LaTeX document is to be converted to HTML, lwarp may be a good choice. For new projects with a large number of documents, it may be worth investigating the alternatives before decided which path to take.

4.1 internet class

Cls internet The closest to lwarp in design principle is the `internet` class by Andrew Stacey — an interesting project which directly produces several versions of markdown, and also HTML and EPUB. https://github.com/loopspace/latex-to-internet

4.2 TeX4ht

Prog TeX4ht http://tug.org/tex4ht/

Prog htlatex

This system uses native LaTeX processing to produce a DVI file containing special commands, and then uses additional post-processing for the HTML conversion by way of numerous configuration files. In some cases lwarp provides a better HTML conversion, and it supports a different set of packages. TeX4ht produces several other forms of output beyond HTML, including ODT and a direct path to EPUB, and is still being developed.

4.3 Translators

These systems use external programs to translate a subset of LaTeX syntax into HTML. Search for each on CTAN (http:\ctan.org).

Prog Hevea **HeVeA:** http://hevea.inria.fr/ (not on CTAN)

Prog TtH **TtH:** http://hutchinson.belmont.ma.us/tth/

Prog GELLMU **GELLMU:** http://www.albany.edu/~hammond/gellmu/

Prog LaTeXML **LaTeXML:** http://dlmf.nist.gov/LaTeXML/

Prog Plastex **PlasTeX:** https://github.com/tiarno/plastex

Prog LaTeX2HTML **LaTeX2HTML:** http://www.latex2html.org/
and http://ctan.org/pkg/latex2html.

Prog TeX2page **TeX2page:** http://ds26gte.github.io/tex2page/index.html

Finally, GladTeX may used to directly insert LaTeX math into HTML:

Prog GladTeX **GladTeX:** http://humenda.github.io/GladTeX/

4.4 AsciiDoc and Asciidoctor

AsciiDoc is one of the most capable markup languages, providing enough features to produce the typical technical-writing document with cross-references, and it writes LaTeX and HTML.

Prog AsciiDoc **Asciidoctor:** http://asciidoctor.org/ (More active.)

Prog AsciiDoctor **AsciiDoc:** http://asciidoc.org/ (The original project.)

4.4.1 Asciidoctor-LaTeX

The Asciidoctor-LaTeX project is developing additional LaTeX-related features.

Asciidoctor-LateX:
http://www.noteshare.io/book/asciidoctor-latex-manual
Prog Asciidoctor-LaTeX https://github.com/asciidoctor/asciidoctor-latex

4.5 Pandoc

Prog Pandoc A markup system which also reads and writes LaTeX and HTML.

Pandoc: http://pandoc.org/

(Watch for improvements in cross-references to figures and tables.)

4.6 Word processors

Prog Word
Prog LibreOffice
Prog OpenOffice

It should be noted that the popular word processors have advanced through the years in their abilities to represent math with a LaTeX-ish input syntax, unicode math fonts, and high-quality output, and also generate HTML with varying success. See recent developments in Microsoft® *Word*® and LibreOffice™ *Writer*.

4.7 Commercial systems

Prog Adobe
Prog FrameMaker
Prog InDesign
Prog Flare
Prog Madcap

Likewise, several professional systems exist whose abilities have been advancing in the areas of typesetting, cross-referencing, and HTML generation. See Adobe® *FrameMaker*®, Adobe *InDesign*®, and Madcap *Flare*™.

4.8 Comparisons

AsciiDoc, Pandoc, and various other markup languages typically have a syntax which tries to be natural and human-readable, but the use of advanced features tends to

require many combinations of special characters, resulting in a complicated mess of syntax. By contrast, LaTeX spells things out in readable words but takes longer to type, although integrated editors exist which can provide faster entry and a graphic user interface. For those functions which are covered by the typical markup language it is arguable that LaTeX is comparably easy to learn, while LaTeX provides many more advanced features where needed, along with a large number of pre-existing packages which provide solutions to numerous common tasks.

Text-based document-markup systems share some of the advantages of LaTeX vs. a typical word processor. Documents formats are stable. The documents themselves are portable, work well with revision control, do not crash or become corrupted, and are easily generated under program control. Formatting commands are visible, cross-referencing is automatic, and editing is responsive. Search/replace with regular expressions provides a powerful tool for the manipulation of both document contents and structure. Markup systems and some commercial systems allow printed output through a LaTeX back end, yielding high-quality results especially when the LaTeX template is adjusted, but they lose the ability to use LaTeX macros and other LaTeX source-document features.

The effort required to customize the output of each markup system varies. For print output, LaTeX configuration files are usually used. For HTML output, a CSS file will be available, but additional configuration may require editing some form of control file with a different syntax, such as XML. In the case of lwarp, CSS is used, and much HTML output is adjusted through the usual LaTeX optional macro parameters, but further customization may require patching LaTeX code.

The popular word processors and professional document systems each has a large base of after-market support including pre-designed styles and templates, and often include content-management systems for topic reuse.

5 Installation

Table 3 shows the tools which are used for the LaTeX to HTML conversion. In most cases, these will be available via the standard package-installation tools.

Detailed installation instructions follow.

Table 3: Required software programs

Provided by your LaTeX distribution:

From TeXLive: http://tug.org/texlive/.

LaTeX: *pdflatex*, *xelatex*, or *lualatex*.

The lwarp package: This package.

The *lwarpmk* utility: Provided along with this package. This should be an operating-system executable in the same way that *pdflatex* or *latexmk* is. It is possible to have the lwarp package generate a local copy of *lwarpmk* called `lwarpmk.lua`. See table 4.

***luatex*:** Used by the *lwarpmk* program to simplify and automate document generation.

***xindy*:** The *xindy* program is used by lwarp to create indexes. On a MiKTeX system this may have to be acquired separately, but it is part of the regular installer as of mid 2015.

***latexmk*:** Optionally used by *lwarpmk* to compile LaTeX code. On a MiKTeX system, *Perl* may need to be installed first.

***pdfcrop*:** Used to pull images out of the LaTeX PDF.

Poppler PDF utilities:

***pdftotext*:** Used to convert PDF to text.

***pdfseparate*:** Used to pull images out of the LaTeX PDF.

***pdftocairo*:** Used to convert images to SVG.

These might be provided by your operating-system package manager, and MiKTeX provides miktex-poppler-bin-* packages.

From Poppler: poppler.freedesktop.org.

For MacOS®, see https://brew.sh/, install *Homebrew*, then

Enter ⇒ **`brew install poppler`**

For Windows, see MikTeX miktex-poppler-bin-*, or:
https://sourceforge.net/projects/poppler-win32/ and:
http://blog.alivate.com.au/poppler-windows/

***Perl*:**

This may be provided by your operating-system package manager, and may be required for some of the Poppler PDF utilities.

strawberryperl.com (recommended), perl.org

Automatically downloaded from the internet as required:

MathJax: Optionally used to display math. From: mathjax.org

5.1 Installing the lwarp package

There are several ways to install lwarp. These are listed here with the preferred methods listed first:

Pre-installed: Try entering into a command line:

Enter ⇒ **`kpsewhich lwarp.sty`**

If a path to `lwarp.sty` is shown, then lwarp is already installed and you may skip to the next section.

TEX Live: If using a TEX Live distribution, try installing via *tlmgr*:

Enter ⇒ **`tlmgr install lwarp`**

MiKTEX:

1. For newer versions of MiKTEX, install or update lwarp using the *MiKTeX Console* program.
2. For older versions of MiKTEX, to install lwarp the first time, use the *MiKTeX Package Manager (Admin)*. To update lwarp, use *MiKTeX Update (Admin)*.
3. Either way, also update the package miktex-misc, which will install and update the *lwarpmk* executable.

Operating-system package: The operating-system package manager may already have lwarp, perhaps as part of a set of TEX-related packages.

CTAN TDS archive: lwarp may be downloaded from the Comprehensive TEX Archive:

1. See http://ctan.org/pkg/lwarp for the lwarp package.
2. Download the TDS archive: `lwarp.tds.zip`
3. Find the TEX `local` directory:

   TEX Live:

   Enter ⇒ **`kpsewhich -var-value TEXMFLOCAL`**

   MiKTEX:

   In the **Settings** window, **Roots** tab, look for a local TDS root.

   This should be something like:

   ```
   /usr/local/texlive/texmf-local/
   ```

4. Unpack the archive in the TDS local directory.
5. Renew the cache:

   Enter ⇒ **`mktexlsr`**

   — or —

   Enter ⇒ **`texhash`**

   Or, for WINDOWS MiKTEX, start the program called *MiKTeX Settings (Admin)* and click on the button called **Refresh FNDB**.

CTAN `.dtx` and `.ins` files: Another form of TEX package is `.dtx` and `.ins` source files. These files are used to create the documentation and `.sty` files.

1. See http://ctan.org/pkg/lwarp for the lwarp package.
2. Download the zip archive `lwarp.zip` into your own `lwarp` directory.
3. Unpack `lwarp.zip`.
4. Locate the contents `lwarp.dtx` and `lwarp.ins`
5. Create the `.sty` files:
   Enter ⇒ **`pdflatex lwarp.ins`**
6. Create the documentation:

```
pdflatex lwarp.dtx  (several times)
makeindex -s gglo.ist -o lwarp.gls lwarp.glo
makeindex -s gind.ist lwarp.idx
pdflatex lwarp.dtx  (several times)
```

7. Copy the `.sty` files somewhere such as the TEX Live local tree found in the previous CTAN TDS section, under the subdirectory:
   `<texlocal>/tex/latex/local/lwarp`
8. Copy `lwarp_baseline_marker.png` and `lwarp_baseline_marker.eps` to the same place as the `.sty` files.
9. Copy the documentation `lwarp.pdf` to a `source` directory in the local tree, such as:
   `<texlocal>/doc/local/lwarp`
10. Renew the cache:
    Enter ⇒ **`mktexlsr`**
    — or —
    Enter ⇒ **`texhash`**
    Or, for WINDOWS MiKTEX, start the program called *MiKTeX Settings (Admin)* and click on the button called **Refresh FNDB**.
11. See section 5.2.1 to generate your local copy of *lwarpmk*.
12. Once the local version of `lwarpmk.lua` is installed, it may be made available system-wide as per section 5.2.

Project-local CTAN `.dtx` and `.ins` files: The `.dtx` and `.ins` files may be downloaded to a project directory, then compiled right there, alongside the document source files. The resultant `*.sty` and `lwarpmk.lua` files may be used as-is, so long as they are in the same directory as the document source. The files `lwarp_baseline_marker.png` and `lwarp_baseline_marker.eps` must also be copied as well. This approach is especially useful if you would like to temporarily test lwarp before deciding whether to permanently install it.

Just testing!

5.2 Installing the *lwarpmk* utility

(Note: If *lwarpmk* is not already installed, it is easiest to use a local copy instead of installing it system-wide. See section 5.2.1.)

After the lwarp package is installed, you may need to setup the *lwarpmk* utility:

1. At a command line, try executing **lwarpmk**. If the *lwarpmk* help message appears, then *lwarpmk* is already set up. If not, it is easiest to generate and use a local copy. See section 5.2.1.

2. For MiKTEX, try updating the miktex-misc package. This may install the *lwarpmk* executable for you.

   Otherwise, continue with the following:

3. Locate the file `lwarpmk.lua`, which should be in the `scripts` directory of the TDS tree. On a TEX Live or MiKTEX system you may use

   Enter ⇒ **kpsewhich lwarpmk.lua**

   (If the file is not found, you may also generate a local copy and use it instead. See section 5.2.1.)

4. Create *lwarpmk*:

   Unix: Create a symbolic link and make it executable:

   (a) Locate the TEX Live binaries:

   Enter ⇒ **kpsewhich -var-value TEXMFROOT**

   This will be something like:

   `/usr/local/texlive/<year>`

   The binaries are then located in the `bin/<arch>` directory under the root:

   `/usr/local/texlive/<year>/bin/<architecture>/`

   In this directory you will find programs such as *pdflatex* and *makeindex*.

   (b) In the binaries directory, create a new symbolic link from the binaries directory to `lwarpmk.lua`:

   Enter ⇒ **ln -s <pathtolwarpmk.lua> lwarpmk**

   (c) Make the link executable:

   Enter ⇒ **chmod 0755 lwarpmk**

   WINDOWS TEX Live: Create a new `lwarpmk.exe` file:

   (a) Locate the TEX Live binaries as shown above for UNIX.

   (b) In the binaries directory, make a *copy* of `runscript.exe` and call it `lwarpmk.exe` This will call the copy of `lwarpmk.lua` which is in the `scripts` directory of the distribution.

   WINDOWS MiKTEX: Create a new `lwarpmk.bat` file:

   (a) Locate the MiKTEX binaries. These will be in a directory such as:

   `C:\Program Files\MiKTeX 2.9\miktex\bin\x64`

   In this directory you will find programs such as `pdflatex.exe` and `makeindex.exe`.

   (b) Create a new file named `lwarpmk.bat` containing:

   ```
   texlua "C:\Program Files\MiKTeX 2.9\scripts\lwarp\lwarp.texlua" %*
   ```

   This will call the copy of `lwarpmk.lua` which is in the `scripts` directory of the distribution.

5.2.1 Using a local copy of *lwarpmk*

It is also possible to use a local version of *lwarpmk*:

1. When compiling the tutorial in section 6, use the `lwarpmk` option for the lwarp package:

   ```
   \usepackage[lwarpmk]{lwarp}
   ```

2. When the tutorial is compiled with *pdflatex*, the file `lwarpmk.lua` will be generated along with the other configuration files.

3. `lwarpmk.lua` may be used for this project:

   Unix:

   (a) Make `lwarpmk.lua` executable:
   Enter ⇒ **`chmod 0755 lwarpmk.lua`**

   (b) Compile documents with
   Enter ⇒ **`./lwarpmk.lua html`**
   Enter ⇒ **`./lwarpmk.lua print`**
   etc.

   (c) It may be useful to rename or link to a version without the `.lua` suffix.

   WINDOWS:

   Compile documents with either of the following, depending on which command shell is being used:
   Enter ⇒ **`texlua lwarpmk.lua html`**
   Enter ⇒ **`texlua lwarpmk.lua print`**
   etc.

   Or:
   Enter ⇒ **`lwarpmk html`**
   Enter ⇒ **`lwarpmk print`**
   etc.

5.3 Installing additional utilities

To test for the existence of the additional utilities:

Enter the following in a command line. If each programs' version is displayed, then that utility is already installed. See table 3 on page 86.

Enter ⇒ **`luatex --version`**
Enter ⇒ **`xindy --version`**
Enter ⇒ **`latexmk --version`**
Enter ⇒ **`perl --version`**
Enter ⇒ **`pdfcrop --version`**
Enter ⇒ **`pdftotext -v`**
Enter ⇒ **`pdfseparate --version`**
Enter ⇒ **`pdftocairo -v`**

To install *xindy*, *latexmk*, and *pdfcrop*:

The TEX utilities *xindy*, *latexmk*, and *pdfcrop* may be installed in *TexLive* with *tlmgr*, installed by *MiKTeX*, provided by your operating system's package manager, or downloaded from the *CTAN* archive:

http://ctan.org/pkg/xindy
http://ctan.org/pkg/latexmk
http://ctan.org/pkg/pdfcrop

Prog [requirement] pdftotext
Prog [requirement] pdfseparate
Prog [requirement] pdftocairo

To install the POPPLER utilities to a UNIX/LINUX system:

The tools from the POPPLER project should be provided by your operating system's package manager.

To install the POPPLER utilities to a MACOS machine:

1. Install *Homebrew* from https://brew.sh/:

```
/usr/bin/ruby -e "$(curl -fsSL https://raw.githubusercontent.com/Homebrew/install/master/install)"
```

Enter

2. Install the POPPLER utilities:

Enter ⇒ `brew install poppler`

To install the POPPLER utilities to a WINDOWS machine:

If using MikTEX, install a miktex-poppler-bin-* package. Otherwise:

1. See table 3 on page 86.
2. Download and extract the POPPLER utilities *pdftotext*, *pdfseparate*, and *pdfseparate* to a directory, such as `Poppler`.
3. In the **Start** window, type "Path" to search for results related to Path. Or, open the control panel and search for "Path".
4. Choose **Edit the system environment variables** in the control panel.
5. Choose the **Environment Variables** button.
6. Choose the **Path** variable, then the **Edit** button.
7. Choose the **New** button to make an additional entry.
8. Enter the `bin` directory of the POPPLER utilities, such as:

   `C:\Users\<myname>\Desktop\Poppler\poppler-0.5_x86\poppler-0.5\bin`

   Be sure to include `\bin`.
9. Click **Ok** when done.

Prog [requirement] perl

To install PERL to a WINDOWS machine:

1. Download and install a version of PERL, such as STRAWBERRY PERL, to a directory without a space in its name, such as `C:\Strawberry`.
2. Edit the **Path** as seen above for the POPPLER utilities.
3. Enter the `bin` directory of the *perl* utility, such as:

   `C:\Strawberry\perl\bin`

   Be sure to include `\bin`.
4. Click **Ok** when done.

Any utilities installed by hand must be added to the PATH.

6 Tutorial

This section shows an example of how to create an lwarp document.

Need help?

See the General Index for "how-to", and the Troubleshooting Index if something doesn't work. The Index of Objects contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category. A Troubleshooting section is also available.

6.1 Starting a new project

1. Create a new project directory called `tutorial`.

File `tutorial.tex`

2. Inside the `tutorial` directory, create a new file called `tutorial.tex`. This may be done several ways:

   Copy from the documentation PDF:

   A listing is in fig. 1, which may be copied/pasted from the figure directly into your own editor, depending on the quality of the PDF viewer and editor, or:

   Copy from the lwarp documentation directory:

File `lwarp_tutorial.txt`

   Another copy may be found by entering into a command line:

   Enter ⇒ **`texdoc -l lwarp_tutorial.txt`**

⚠ Note: `.txt` suffix!

   This should be in the `doc/latex/lwarp/` directory along with this PDF documentation. Copy `lwarp_tutorial.txt` directly into your `tutorial` directory, renamed as `tutorial.tex`.

⚠ Bad formatting!

   When using WINDOWS, use an editor other than NOTEPAD, since NOTEPAD does not accept the end-of-line from a UNIX text file.

3. Compile the project:

   Enter ⇒ **`pdflatex tutorial.tex`**

   (several times)

   (*xelatex* or *lualatex* may be used as well. lwarp also supports DVI *latex* for use with `.eps` images.)

4. View the resulting `tutorial.pdf` with a PDF viewer.

A number of new files are created when `tutorial.tex` is compiled, as shown in table 4. These files are created by the `lwarp` package.

(Two of the new files are configuration files for the helper program *lwarpmk*. Whenever a print version of the document is created, the configuration files for *lwarpmk* are updated to record the operating system, LaTeX engine (*latex*, *pdflatex*, *xelatex*, or *lualatex*), the filenames of the source code and HTML output, and whether the additional helper program *latexmk* will be used to compile the document.)

Figure 1: tutorial.tex listing

Note: There are two pages!

```
% Save this as tutorial.tex for the lwarp package tutorial.

\documentclass{book}

\usepackage{iftex}

% --- LOAD FONT SELECTION AND ENCODING BEFORE LOADING LWARP ---

\ifPDFTeX
\usepackage{lmodern}            % pdflatex or dvi latex
\usepackage[T1]{fontenc}
\usepackage[utf8]{inputenc}
\else
\usepackage{fontspec}           % XeLaTeX or LuaLaTeX
\fi

% --- LWARP IS LOADED NEXT ---
\usepackage[
%   HomeHTMLFilename=index,     % Filename of the homepage.
%   HTMLFilename={node-},       % Filename prefix of other pages.
%   IndexLanguage=english,      % Language for xindy index, glossary.
%   latexmk,                    % Use latexmk to compile.
%   OSWindows,                  % Force Windows. (Usually automatic.)
%   mathjax,                    % Use MathJax to display math.
]{lwarp}
% \boolfalse{FileSectionNames}  % If false, numbers the files.

% --- LOAD PDFLATEX MATH FONTS HERE ---

% --- OTHER PACKAGES ARE LOADED AFTER LWARP ---
\usepackage{makeidx} \makeindex
\usepackage{xcolor}             % (Demonstration purposes only.)
\usepackage{hyperref,cleveref}  % LOAD THESE LAST!

% --- LATEX AND HTML CUSTOMIZATION ---
\title{The Lwarp Tutorial}
\author{Some Author}
\setcounter{tocdepth}{2}        % Include subsections in the \TOC.
\setcounter{secnumdepth}{2}     % Number down to subsections.
\setcounter{FileDepth}{1}       % Split \HTML\ files at sections
\booltrue{CombineHigherDepths}  % Combine parts/chapters/sections
\setcounter{SideTOCDepth}{1}    % Include subsections in the side\TOC
\HTMLTitle{Webpage Title}       % Overrides \title for the web page.
\HTMLAuthor{Some Author}        % Sets the HTML meta author tag.
\HTMLLanguage{en-US}            % Sets the HTML meta language.
\HTMLDescription{A description.}% Sets the HTML meta description.
\HTMLFirstPageTop{Name and \fbox{HOMEPAGE LOGO}}
\HTMLPageTop{\fbox{LOGO}}
\HTMLPageBottom{Contact Information and Copyright}
\CSSFilename{lwarp_sagebrush.css}
```

```
\begin{document}

\maketitle                      % Or titlepage/titlingpage environment.

% An article abstract would go here.

\tableofcontents                % MUST BE BEFORE THE FIRST SECTION BREAK!
\listoffigures

\chapter{First chapter}

\section{A section}

This is some text which is indexed.\index{Some text.}

\subsection{A subsection}

See \cref{fig:withtext}.

\begin{figure}\begin{center}
\fbox{\textcolor{blue!50!green}{Text in a figure.}}
\caption{A figure with text\label{fig:withtext}}
\end{center}\end{figure}

\section{Some math}

Inline math: $r = r_0 + vt - \frac{1}{2}at^2$
followed by display math:
\begin{equation}
a^2 + b^2 = c^2
\end{equation}


\begin{warpprint}   % For print output ...
\cleardoublepage    % ... a common method to place index entry into TOC.
\phantomsection
\addcontentsline{toc}{chapter}{\indexname}
\end{warpprint}
\ForceHTMLPage      % HTML index will be on its own page.
\ForceHTMLTOC       % HTML index will have its own toc entry.
\printindex

\end{document}
```

Table 4: Configuration files created by print version

tutorial.pdf: The PDF output from LaTeX. The print version of the document.

tutorial_html.tex: A small `.tex` file used to create a parallel HTML version of the document, which co-exists with usual the PDF version, and which will have its own auxiliary files. In this way, both PDF and HTML documents may co-exist side-by-side.

Auxiliary files: The usual LaTeX files `.aux`, `.log`, `.out`, `.toc`, `.lof`, `.idx`. When an HTML version of the document is created, `_html` versions of the auxiliary files will also be generated.

lwarpmk.conf: A configuration file for *lwarpmk*, which is used to automate the compilation of PDF or HTML versions of the document.

tutorial.lwarpmkconf: Another configuration file used by *lwarpmk*, which is only useful if you wish to have several projects residing in the same directory.

.css files: `lwarp.css`, `lwarp_formal.css`, `lwarp_sagebrush.css` These files are standard for lwarp, and are not meant to be modified by the user.

sample_project.css: An example of a user-customized css file, which may be used for project-specific changes to the lwarp defaults.

lwarp.ist: Used by lwarp while creating an index using *makeindex*. This file should not be modified by the user. A custom file may be used instead, if necessary.

lwarp.xdy: Used by lwarp while creating an index using *xindy*. This file should not be modified by the user. A custom file may be used instead, if necessary.

lwarp_one_limage.txt: For Windows only. Used to process SVG images in the background. Copied to `lwarp_one_limage.cmd` when images are generated.

lwarp_mathjax.txt: Inserted into the HTML files when MathJax is used to display math. This file should not be modified by the user.

comment.cut: A temporary file used by lwarp to conditionally process blocks of text. This file may be ignored.

When the `lwarpmk` option is given to the lwarp package:

lwarpmk.lua: A local copy of the *lwarpmk* utility.

On Unix-related operating systems this file must be made executable:

```
chmod u+x lwarpmk.lua
```

This may be useful to have to archive with a project for future use.

6.2 Compiling the print version with *lwarpmk*

The *lwarpmk* utility program is used to compile either the printed or the HTML version of the document.

`lwarpmk print` is used to recompile a printed version of the document.

1. Re-compile the print version:

   Enter ⇒ **`lwarpmk print`**

   lwarpmk prints an introduction then checks to see if the document must be recompiled. If it seems that the files are up-to-date, then *lwarpmk* informs you of that fact and then exits.

2. Make a small change in the original document, such as adding a space character.

3. Recompile again.

   Enter ⇒ **`lwarpmk print`**

   The document is recompiled when a change is seen in the source. Several compilations may be necessary to resolve cross-references.

4. Force a recompile to occur.

   Enter ⇒ **`lwarpmk again`**

   Enter ⇒ **`lwarpmk print`**

   `lwarpmk again` updates the date code for the file, triggering a recompile the next time the document is made.[5]

5. Process the index.[6] [7]

   Enter ⇒ **`lwarpmk printindex`**

6. Recompile again to include the index.

   Enter ⇒ **`lwarpmk print`**

7. To force a single recompile when needed, even if no changes were detected:

   Enter ⇒ **`lwarpmk print1`**

Note that the HTML customization commands are ignored while making the print version.

[5] Although, when using the utility *latexmk* (introduced later), the changed date is ignored and an actual change in contents must occur to cause a recompile.

[6] The command **`lwarpmk printglossary`** is also available to process a glossary produced with the glossaries package. See section 9.6.11.

[7] Also see section 9.6.14 for index options.

6.3 Compiling the HTML version with *lwarpmk*

`lwarpmk html` is used to recompile an HTML version of the document.

1. Compile the HTML version:

   Enter ⇒ **`lwarpmk html`**

   (a) *lwarpmk* uses LaTeX to process `tutorial_html.tex` to create `tutorial_html.pdf`.

   (b) *pdftotext* is then used to convert to the file `tutorial_html.html`. This file is a plain-text file containing HTML tags and content for the entire document.

   (c) *lwarpmk* manually splits `tutorial_html.html` into individual HTML files according to the HTML settings. For this tutorial, the result is `tutorial.html` (the home page), along with `First-chapter.html`[8], `Some-math.html`, and the document's index in `_Index.html`.[9]

2. View the HTML page in a web browser.

   Open the file `tutorial.html` in a web browser.

math Note that math is still displayed as its `alt` tag, which is the plain-text LaTeX source, until the images of the math expressions have been generated. Math may be displayed as SVG images or by a MathJax script, as seen in sections 6.4 and 6.5.

3. Force a recompile:

   Enter ⇒ **`lwarpmk again`**

   Enter ⇒ **`lwarpmk html`**

   Enter ⇒ **`lwarpmk print`**

4. Process the HTML index and recompile:[10][11]

   Enter ⇒ **`lwarpmk htmlindex`**

   Enter ⇒ **`lwarpmk html`**

   `_Index.html` is updated for the new LaTeX index.

5. Reload the web page to see the added index.

6. To force a single recompile when needed, even if no changes were detected:

   Enter ⇒ **`lwarpmk html1`**

[8] `First-chapter.html` also contains the first section, even though the second section is its own HTML page. This behavior is controlled by the boolean `CombineHigherDepths`.

[9] `index.html` is commonly used as a homepage, so the document index is in `_Index.html`.

[10] The command **`lwarpmk htmlglossary`** is also available to process a glossary produced with the glossaries package. See section 9.6.11.

[11] Also see section 9.6.14 for index options.

6.4 Generating the SVG images

math as SVG images

By default lwarp represents math as SVG images, with the LaTeX source included in `alt` attributes. In this way, the math is displayed as it was drawn by LaTeX, and the LaTeX source may be copied and pasted into other documents.

`picture` and Ti*k*z

lwarp uses the same mechanism for `picture` and Ti*k*z environments.

1. Create the SVG images:

   Enter ⇒ **`lwarpmk limages`**

   Enter ⇒ **`lwarpmk html`**

2. Move to the tutorial's HTML math page and reload the document in the browser.
3. The math images are displayed using the same font and formatting as the printed version.
4. Copy/paste a math expression into a text editor to see the LaTeX source.

⚠ adding/removing

When a math expression, `picture`, or Ti*k*z environment is added or removed, the SVG images must be re-created by entering **`lwarpmk limages`** to maintain the proper image-file associations. Inline SVG math may be hashed and thus not need to be recreated, but display math and objects such as Ti*k*z may move to new image numbers when the document is changed.

recompile first

Before attempting to create the SVG image files, *lwarpmk* verifies that the HTML version of the document exists and has correct internal image references.[12] If it is necessary to recompile the document's HTML version one more time, *lwarpmk* usually will inform the user with an error message, but there are some conditions which cannot be detected, so the user should watch for the LaTeX recompile warnings.

⚠ HTML instead of images

If HTML appears where an SVG image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time.

⚠ page counter

Incorrect SVG images will also occur if the document changes the page counter:

```
\setcounter{page}{<value>}
```

The page counter must *not* be adjusted by the user.

⚠ Lots of files!

Expressing math as SVG images has the advantage of representing the math exactly as LaTeX would, but has the disadvantage of requiring an individual file for each math expression. For inline math, and some other objects, lwarp uses an MD5 hash on its LaTeX source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as `picture` and Ti*k*z require one image file each. For a document with a large amount of math, see section 6.5 to use MathJax instead.

[12] This becomes important when dealing with a document containing thousands of images.

6.5 Using MathJax for math

math with MathJax

Math may also be represented using the MathJax Javascript project.

1. In the tutorial's source code, uncomment the `mathjax` package option for lwarp:

   ```
   mathjax, % Use MathJax to display math.
   ```

2. Recompile

   Enter ⇒ **`lwarpmk html`**

3. Reload the math page.

⚠ MathJax requirements

MathJax requires web access unless a local copy of MathJax is available, and it also requires that Javascript is enabled for the web page. The math is rendered by MathJax. Right-click on math to see several options for rendering, and for copying the LaTeX source.

While using MathJax has many advantages, it may not be able to represent complex expressions or spacing adjustments as well as LaTeX, and it may not support some math-related packages.

6.6 Changing the css style

For a formal css style, add to the preamble:

```
\usepackage{lwarp}
. . .
\CSSFilename{lwarp_formal.css}
. . .
\begin{document}
```

For a modern css style, `lwarp_sagebrush.css` is also provided:

```
\CSSFilename{lwarp_sagebrush.css}
```

See section 8.5 for more information about modifying the css styling of the document.

6.7 Customizing the HTML output

A number of settings may be made to control the HTML output, including filename generation, automatic compilation, math output, document splitting, meta data, and page headers and footers.

See section 8.4 for more information.

6.8 Using *latexmk*

latexmk is a LaTeX utility used to monitor changes in source files and recompile as needed.

1. In the tutorial's source code uncomment the `latexmk` option for the lwarp package:

   ```
   latexmk, % Use latexmk to compile.
   ```

2. Recompile the printed version of the document.

   Enter ⇒ **`lwarpmk print`**

   lwarp updates its own configuration files (`lwarpmk.conf` and `tutorial.lwarpmkconf`) whenever the printed version of the document is compiled. These configuration files remember that *lwarpmk* should use *latexmk* to compile the document.

3. Recompile the document.

   Enter ⇒ **`lwarpmk print`**

   and/or

   Enter ⇒ **`lwarpmk html`**

Changes are detected by comparing checksums rather than modification times, so `lwarpmk again` will not trigger a recompile, but *latexmk* has a much better awareness of changes than the *lwarpmk* utility does and it is likely to correctly know when to recompile. A recompile may be forced by making a small change to the source, and a single recompile may be forced with:

forced single-pass recompile

Enter ⇒ **`lwarpmk print1`**

and/or

Enter ⇒ **`lwarpmk html1`**

6.9 Using XeLaTeX or LuaLaTeX

XeLaTeX or LuaLaTeX may be used instead of LaTeX.

1. Remove the auxiliary files for the project:

   Enter ⇒ **`lwarpmk cleanall`**

2. Use *xelatex* or *lualatex* to compile the printed version a single time.

   Enter ⇒ **`xelatex tutorial.tex`**

   -or-

   Enter ⇒ **`lualatex tutorial.tex`**

   When the compile occurs, the configuration files for *lwarpmk* are modified to remember which TeX engine was used. XeLaTeX or LuaLaTeX will be used for future runs of *lwarpmk*.

3. To recompile the document:

   Enter ⇒ **`lwarpmk print`**

   -and-

   Enter ⇒ **`lwarpmk html`**

4. Also remember to update the indexes and recompile again:

   Enter ⇒ **`lwarpmk htmlindex`**

   Enter ⇒ **`lwarpmk html`**

   Enter ⇒ **`lwarpmk printindex`**

   Enter ⇒ **`lwarpmk print`**

6.10 Using DVI LaTeX

Traditional DVI LaTeX may also be used along with `.eps` image files. An SVG version of each image must also be provided. *lwarpmk* may be used to convert image formats.

To convert EPS files to PDF:

Enter ⇒ **`lwarpmk epstopdf *.eps`** **(or a list of files)**

To convert PDF files to SVG:

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of files)**

⚠ bitmapped fonts See section 8.2 regarding font selection to avoid the use of bitmapped fonts.

6.11 Using a glossary

lwarp supports the gloss and glossaries packages, although this tutorial does not supply an example.

6.11.1 gloss package

See section 9.6.10.

6.11.2 glossaries package

To process the glossary for the print version:

Enter ⇒ **`lwarpmk printglossary`**

⚠ (If **`makeglossaries`** is not found, see section 9.6.11.)

To process the glossary for the HTML version:

Enter ⇒ **`lwarpmk htmlglossary`**

In each case, the document will have to be recompiled afterwards:

Enter ⇒ **`lwarpmk html1`**

Enter ⇒ **`lwarpmk html`**

Enter ⇒ **`lwarpmk print1`**

Enter ⇒ **`lwarpmk print`**

See section 9.6.11 to set options for processing glossaries.

6.12 Cleaning auxiliary files

To remove the auxiliary files `.aux`, `.toc`, `.lof`, `.lot`, `.idx`, `.ind`, `.log`, and `.gl*`:

Enter ⇒ **`lwarpmk clean`**

6.13 Cleaning auxiliary and output files

To remove the auxiliary files, and also remove the `.pdf` and `.html` files:

Enter ⇒ **`lwarpmk cleanall`**

6.14 Cleaning the images from the `<project>-images` directory

The `<project>-images` directory contains SVG images automatically generated for inline and display math, tikz, etc. To remove all the images from the `lateximages` directory:

Enter ⇒ **`lwarpmk cleanlimages`**

6.15 Converting PDF or EPS images to SVG

HTML cannot display PDF or EPS images, so any external PDF graphics images must be converted to SVG format. *pdftocairo* and *epstopdf* may be used one image at a time, but *lwarpmk* also provides a way to convert PDF or EPS images in bulk:

Enter ⇒ **`lwarpmk epstopdf *.eps`** **(or a list of files)**

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of files)**

Be sure to always provide SVG files for HTML output.

6.16 Creating HTML from an incomplete compile

During testing it may be useful to finish the HTML conversion even when the document had errors and did not compile successfully. To attempt an HTML conversion of an incomplete document:

Enter ⇒ **`lwarpmk pdftohtml [-p project]`**

6.17 Processing multiple projects in the same directory

It is possible to have several projects in the same directory. *lwarpmk* has an optional parameter which is the document to compile.

To create each project:

Enter ⇒ **pdflatex project_a**

Enter ⇒ **pdflatex project_b**

Each project is given its own configuration file:

`project_a.lwarpmkconf, project_b.lwarpmkconf`

To compile each project with `lwarkmk`:

Enter ⇒ **lwarpmk print -p project_a**

Enter ⇒ **lwarpmk html -p project_b**

6.18 Using the *make* utility

lwarpmk has an action which may be useful for integration with the common *make* utility:

```
lwarpmk pdftohtml [-p project]
```

make may be used to compile the code to PDF with HTML tags (`project_html.pdf`), then *lwarpmk* may be used to convert each target to HTML files.

7 Converting an existing document

To convert an existing document for use with lwarp:

1. Arrange the document in the following order:
   (a) Declare the `\documentclass`.
   (b) Load text fonts.
   (c) Load inputenc or inputenx, fontenc, and/or fontspec.
   (d) Load lwarp.
   (e) Load remaining packages.
2. Modify the document:

⚠ math in section names

   (a) If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring`:

```
\section{A math \texorpdfstring{$1+2=3$}{text description} name}
```

⚠ scale

   (b) Avoid using the `\includegraphics` `scale` option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

   to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

   (c) Possible changes to `tabular` environments include `*` columns, multirow, longtable, supertabular, xtab, bigdelim. See section 9.10.
   (d) Possible option clashes with memoir. See section 9.13.
   (e) If using indexes, see section 9.6.14.
   (f) If using many indexes, glossaries, `.aux` files, etc., see section 9.6.14 regarding morewrites. If morewrites is already used, be sure to add the setup with `allocate=10`.
   (g) Other changes as per Special cases and limitations, section 9.
3. Convert any PDF images to SVG. See section 9.8.
4. Manually compile the print version with *latex*, *pdflatex*, *lualatex*, or *xelatex*.
5. `lwarpmk print` to finish the print version.
6. `lwarpmk html` to create the HTML version.
7. `lwarpmk limages` to create the SVG images of any SVG math, `lateximage`, Ti*k*z, etc.

Need help?

See the General Index for "how-to", and the Troubleshooting Index if something doesn't work. The Index of Objects contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category. A Troubleshooting section is also available.

8 Additional details

8.1 Shell escape

Opt --shell-escape

Some documents require the use of an external program, which is allowed when using the `--shell-escape` command-line option. When the document is first compiled manually, and also whenever the print version is recompiled, lwarp detects and remembers whether shell escape is enabled. If so, it will also be enabled when the document is recompiled with *lwarpmk*.

8.2 Font and UTF-8 support

⚠ type 3 bitmapped fonts

lwarp uses *pdftotext* to convert PDF output into UTF-8-encoded text. This process requires that UTF-8 information be embedded in the PDF file, which may prevent the use of older "type 3" bit-mapped fonts, and of older packages such as ae. The lwarp option `pdftotextEnc` may be useful in some situations. See section 8.3.

vector fonts

Computer Modern

⚠ *pdflatex*

⚠ DVI *latex*

Pkg cm-super

While using DVI *latex* or PDF *pdflatex*, if no font-related package is specified then the default Computer Modern font is used, which may be a "type 3" bit-mapped font which may not convert well to plain text. A "type 1" vector font is required.

To use the updated cm-super's type 1 fonts instead of Computer Modern, install the cm-super font package.

Pkg lmodern

To use Latin Modern instead, add

```
usepackage{lmodern}
```

to the preamble.

Pkg dejavu

Another useful option is the Deja Vu series of fonts, which have an increased coverage of language and glyphs:

```
\usepackage{dejavu}
```

latex, *pdflatex*, T1, UTF8

While using DVI *latex* or PDF *pdflatex*, lwarp automatically loads fontenc with T1 encoding. fontenc may be loaded with an additional encoding after lwarp. inputenc is automatically loaded with UTF8 encoding if if has not yet been loaded, but may also be specified with another encoding such as `latin1`. See the next section regarding index encoding.

⚠ *xelatex* and *lualatex*

XeLaTeX and LuaLaTeX users must use the fontspec package. Do NOT use fontenc!

Place fontspec or fontenc, xunicode, and other font and UTF-8 related commands after the `\documentclass` command and before `\usepackage{lwarp}`.

⚠ package conflicts

In some cases, a package conflict may require that a font package be loaded after lwarp, which should work as well:

1. `documentclass{article/book/report}` comes first, followed by any of:

2. Font and UTF-8 related commands:

   - For XeLaTeX or LuaLaTeX:
     - fontspec and font choices

       Pkg fontspec

       lwarp sets the following to turn off TeX ligatures during the generation of HTML tags, and turn off common ligatures in regular text, since older browsers may not display them correctly and newer browsers can automatically re-create them.

       ligatures

       ```
       \defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
       \defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
       \defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
       ```

   - For *pdflatex*:
     (a) `\usepackage{lmodern}`, or other font-related packages

     Pkg lmodern

     (b) `\usepackage[T1]{fontenc}`

     Pkg fontenc

     (c) `\usepackage[utf8]{inputenc}`, or `latin1`, etc. Or use inputenx.

     Pkg inputenc

     (d) `\usepackage{newunicodechar}` along with related definitions.

     Pkg inputenx

     Pkg newunicodechar

     (e) To assist with the PDF-HTML conversion:
     i. `\input glyphtounicode.tex`
     ii. `\input glyphtounicode-cmr.tex% from the pdfx package`
     iii. `\pdfgentounicode=1`

     File glyphtounicode.tex

     (f) Another option to assist with the PDF-HTML conversion:
     – `\usepackage{cmap}`

     Pkg cmap

     (g) `\usepackage{textcomp}`

     Pkg textcomp

3. `\usepackage{lwarp}` (section 8.3) goes after any of the above, followed by:

4. `\usepackage{newtxmath}` or other math-related font packages. Many of these load amsmath, which must be loaded after lwarp, so they must also be loaded after lwarp.

5. `\setmonofont{TeX Gyre Cursor}` or similar may be required if using XeLaTeX or LuaLaTeX and fontspec along with traditional font packages such as txfonts, newtxtext, etc. This is required to turn off the monospaced font's ligatures with fontspec after loading the traditional font packages. Monospaced output ligatures must be turned off to produce the correct HTML characters.

   ⚠ fontspec with traditional font packages

6. ... the rest of the preamble and the main document.

⚠ UTF-8 locale In some cases, an external program may require a UTF-8 "locale". See section 10.8.

8.2.1 Indexes, glossaries, and encoding

lwarp uses the *xindy* program to processes indexes. *xelatex* and *lualatex* use *xindy* and *pdflatex* uses *texindy*.

The lwarp option `xindyLanguage` may be used to set the language option for xindy, and the `xindyCodepage` option may be used to set the codepage option for xindy. These are used for index generation.

8.3 lwarp package loading and options

lwarp supports book, report, and article classes, as well as the equivalent Koma-script classes and memoir.

Load the lwarp package immediately after the font and UTF-8 setup commands.

Package options may be set while loading lwarp, or later with

```
\lwarpsetup{⟨key=value, . . . ⟩}
```

Pkg lwarp

lwarp package options are as follows:

Opt mathsvg
Opt mathjax

mathsvg, mathjax: For math display, select `mathsvg` (default) or `mathjax`. For more information about the math options, see section 9.7.

Opt latexmk
Default: false

latexmk: Tells *lwarpmk* to use *latexmk* to recompile the document several times if necessary. Otherwise, *lwarpmk* attempts to determing for itself whether to recompile. See section 8.4.

Opt dvips
Default: false

dvips: Tells *lwarpmk* to use *dvips* and *ps2pdf* to convert DVI output to PDF.

Opt dvipdfm
Default: false

dvipdfm: Tells *lwarpmk* to use *dvipdfm* to convert DVI output to PDF.

Opt dvipdfmx
Default: false

dvipdfmx: Tells *lwarpmk* to use *dvipdfmx* to convert DVI output to PDF.

Opt HomeHTMLFilename
Default: {}

HomeHTMLFilename: See section 8.4.

Opt HTMLFilename
Default: {}

HTMLFilename: See section 8.4.

Opt PrintLatexCmd
Default: <automatic>

PrintLatexCmd: Sets the shell commands executed by **`lwarpmk print`**. If not specified, will automatically be set according to the detected LaTeX engine and the use of `--shell-escape`.

Opt HTMLLatexCmd
Default: <automatic>

HTMLLatexCmd: Sets the shell commands executed by **`lwarpmk html`**. If not specified, will automatically be set according to the detected LaTeX engine and the use of `--shell-escape`.

Opt makeindex
Default: makeindex

makeindex: Sets `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkImageCmd` to use *makeindex* when generating indexes with **`lwarpmk printindex`**, **`lwarpmk htmlindex`**, or *latexmk*. If neither `makeindex` nor `xindy` is used, `makeindex` is assumed.

Opt xindy
Default: makeindex

xindy: Sets `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkImageCmd` to use *xindy* when generating indexes with **`lwarpmk printindex`**, **`lwarpmk htmlindex`**, or *latexmk*.

Opt makeindexStyle
Default: lwarp.ist

makeindexStyle: If you wish to use a custom `.ist` file for index generation, see section 28.

Opt xindyStyle
Default: lwarp.xdy

xindyStyle: If you wish to use a custom `.xdy` file for index generation, see section 28.

Opt xindyLanguage
Default: english

xindyLanguage: If using an index or glossary, see section 28.

Opt xindyCodepage
Default: utf8

xindyCodepage: If using an index, see section 28.

Opt PrintIndexCmd
Default: <automatic>

PrintIndexCmd: Sets the shell commands executed by **`lwarpmk printindex`**. If not specified, will be set by the selection of `makeindex` or `xindy`. May be used to specify the creation of multiple indexes. See section 9.6.14.

Table 5: lwarp package options

Option	Description
mathsvg	Show math using SVG images.
mathjax	Show math using MATHJAX.
latexmk	Use *latexmk* for compiling documents.
dvips	Use *dvips* and *ps2pdf* to convert DVI documents.
dvipdfm	Use *dvipdfm* to convert DVI documents.
dvipdfmx	Use *dvipdfmx* to convert DVI documents.
HomeHTMLFilename	The filename of the home page.
HTMLFilename	A prefix for the filenames of the remaining web pages.
PrintLatexCmd	The shell commands for **lwarpmk print**.
HTMLLatexCmd	The shell commands for **lwarpmk html**.
For indexing (section 9.6.14) and glossaries (section 9.6.11):	
makeindex	Use *makeindex* to generate indices.
xindy	Use *xindy* to generate indices.
makeindexStyle	Set a custom style for *makeindex*.
xindyStyle	Set a custom style for *xindy*.
xindyLanguage	The *xindy* language option used for index generation.
xindyCodepage	The *xindy* codepage option used for index generation.
PrintIndexCmd	Shell commands executed by **lwarpmk printindex**.
HTMLIndexCmd	Shell commands executed by **lwarpmk htmlindex**.
LatexmkIndexCmd	Shell commands executed by *latexmk*.
GlossaryCmd	Shell command executed by **lwarpmk printglossary** and **lwarpmk htmlglossary**.
Seldom necessary:	
OSWindows	Force compatibility with MS-WINDOWS.
pdftotextEnc	Set the encoding for *pdftotext*.
lwarpmk	Generate a local copy of lwarpmk.lua.
Used internally by lwarp:	
warpprint	Generate print output, and also generate configuration files.
warpHTML	Generate HTML output.
BaseJobname	The \jobname to use. Set to the \jobname of the printed version even while generating HTML.

Examples:

```
makeindex -s lwarp.ist projectname.idx                (makeindex)
xindy -M lwarp.xdy -L english -C utf8 projectname.idx      (xindy)
```

automatic setting

The use of the `makeindex` or `xindy` options sets `PrintIndexCmd` to sensible values for each of those programs while compiling a single index. lwarp's `makeindexStyle`, `xindyStyle`, `xindyLanuage`, and `xindyCodepage` options will be used if specified.

⚠ xindy

If specifying `PrintIndexCmd` manually, be sure to assign an *xindy* language and codepage with the `-L` and `-C` *xindy* options, as the lwarp `xindyLanguage` and `xindyCodepage` options are not used for the `PrintIndexCmd` option when it is set manually.

This option is stored in the configuration files `lwarpmk.conf` and `*.lwarpmkconf`, and is then passed by the **`lwarpmk printindex`** command to the operating system to compile the print indexes. Since the command string is parsed by TEX, written to a file, read from the file by LuaTEX, and finally passed to the operating system, any attempt at quoting will be problematic. For complicated commands, it would be best to create a shell script, and simply refer to the script with the lwarp `PrintIndexCmd` option.

Opt `HTMLIndexCmd`
Default: `<automatic>`

`HTMLIndexCmd:` Sets the shell commands executed by **`lwarpmk htmlindex`**. If not specified, will be set by the selection of `makeindex` or `xindy`. May be used to specify the creation of multiple indexes. See section 9.6.14.

⚠ filenames

Example settings are similar to `PrintIndexCmd`, but append `_html` to the filenames:

```
makeindex -s lwarp.ist projectname_html.idx           (makeindex)
xindy -M lwarp.xdy -L english -C utf8 projectname_html.idx  (xindy)
```

automatic setting

The use of the `makeindex` or `xindy` options sets `HTMLIndexCmd` to sensible values for each of those programs while compiling a single index. lwarp's `makeindexStyle`, `xindyStyle`, `xindyLanuage`, and `xindyCodepage` options will be used if specified.

⚠ xindy

If specifying `HTMLIndexCmd` manually, be sure to assign an *xindy* language and codepage with the `-L` and `-C` *xindy* options, as the lwarp `xindyLanguage` and `xindyCodepage` options are not used for the `HTMLIndexCmd` option when it is set manually.

As with `PrintIndexCmd`, to generate complicated indexes it may be worthwhile to use a shell script, then refer to that script with `HTMLIndexCmd`.

Opt `LatexmkIndexCmd`
Default: `<automatic>`

`LatexmkIndexCmd:` Sets the shell commands executed by *latexmk*. Unlike `PrintIndexCmd` and `HTMLIndexCmd`, `LatexmkIndexCmd` does not include any filenames, which will be provided instead by *latexmk*. See section 9.6.14.

Example settings are similar to `PrintIndexCmd`, but without a filename:

```
makeindex -s lwarp.ist                                (makeindex)
xindy -M lwarp.xdy -L english -C utf8                      (xindy)
```

automatic setting

The use of the `makeindex` or `xindy` options sets `LatexmkIndexCmd` to either of the two settings show above. lwarp's `makeindexStyle`, `xindyStyle`, `xindyLanuage`, and `xindyCodepage` options will be used if specified. Unlike `PrintIndexCmd` and `HTMLIndexCmd`, *latexmk* uses either of the single-line settings of `LatexmkIndexCmd` shown above to compile each of multiple indexes if necessary.

⚠ xindy

If specifying `LatexmkIndexCmd` manually, be sure to assign an *xindy* language

and codepage with the `-L` and `-C` *xindy* options, as the lwarp `xindyLanguage` and `xindyCodepage` options are not used for the `LatexmkIndexCmd` option when it is set manually.

Opt `GlossaryCmd`
Default: **`makeglossaries`**

`GlossaryCmd`: Sets the shell command executed by **`lwarpmk printglossary`** and **`lwarpmk htmlglossary`**. The print or HTML glossary filename is appended to this command. See section 9.6.11.

Opt `OSWindows`

`OSWindows`: lwarp attempts to automatically sense WINDOWS, but it may be forced with this option. See section 8.6.

Opt `pdftotextEnc`
Default: `UTF-8`

`pdftotextEnc`: Used to specify the encoding used by *pdftotext* during the PDF-HTML conversion. In most situations, the default is the correct choice.

Opt `lwarpmk`

`lwarpmk`: If you wish to have lwarp generate a local copy of `lwarpmk.lua` for archival or local-installation purposes, compile the print version with the `lwarpmk` option set. See section 28.

The following options are used internally by lwarp, and usually are not used in the user's document:

Opt `warpprint`
Opt `warpHTML`

`warpprint` and `warpHTML`: Usually controlled by *lwarpmk*, and not set in the document. Select the `warpprint` option to generate print output (default), or the `warpHTML` option to generate HTML5 output. The default is print output, so the print version may be compiled with the usual *pdflatex*, etc. When lwarp is loaded in print mode, it creates `<project>_html.tex`, which sets the `warpHTML` option before calling the user's source code `<project>.tex`. In this way, `<project>.tex` can `\usepackage{lwarp}` without any options to create a printed version, while `<project>_html.tex` will create an HTML version.

Opt `BaseJobname`
Default: `\jobname`

`BaseJobname`: Not intended for the user. Used internally by lwarp when creating the `*_html.tex` file used to compile the HTML version. See section 28.

8.4 Customizing the HTML output

Table 6 shows several settings may be used to customize the HTML output. Watch for the correct placement of each!

⚠ Placement!

⚠ Changes! Note that if changes are made, it is best to first:

1. Clear all the HTML, PDF, and auxiliary files:
   Enter ⇒ **`lwarpmk clearall`**
2. Recompile the print version in order to recreate the configuration files for *lwarpmk*:
   Enter ⇒ **`lwarpmk print`**
3. Finally, recompile the HTML version with the new settings:
   Enter ⇒ **`lwarpmk html`**

Options for the lwarp package:

Use the following as options for `\usepackage[<options>]{lwarp}`:

Opt HomeHTMLFilename
Default: `\BaseJobname`

HomeHTMLFilename: Filename of the homepage, without the "`.html`" suffix. Defaults to the `\BaseJobname`. A common setting is:

```
HomeHTMLFilename=index
```

causing the homepage to be the file `index.html`. Underscores are allowed in `HomeHTMLFilename` and `HTMLFilename` options, but may need to be escaped elsewhere, such as when appearing in a list:

filename underscores

```
\item [\href{file\_name.pdf}{text}] \
```

See section 8.4.1 for examples of naming and numbering HTML files.

Opt HTMLFilename
Default: `<empty>`

HTMLFilename: A filename prefix for the rest of the HTML web pages. Useful for numbered web pages with a common prefix. May be empty. See section 8.4.1 for examples of naming and numbering HTML files.

Opt latexmk
Default: `false`

latexmk: Controls whether lwarp uses *latexmk* to compile the document. This setting is written to *lwarpmk*'s configuration files.

Opt mathsvg
Default: `true`

mathsvg: Selects SVG display for math output. (The default.)

Opt mathjax
Default: `false`

mathjax: Selects MathJax for math output.

Opt makeindex
Default: `makeindex`

makeindex: Selects *makeindex* for index generation by *lwarpmk*.

Opt xindy
Default: `makeindex`

xindy: Selects *xindy* for index generation by *lwarpmk*.

Placed in the preamble before `\begin{document}`:

`\linkhomename`
Default: `Home`

`\linkhomename`: Name of the link to the home page. Paragraphs are allowed.

Table 6: HTML settings

Macro/Cntr/Bool	Description
\linkhomename	Name of the link to the homepage.
SideTOCDepth	Sectioning depth of the sideTOC.
\sidetocname	Name of the sideTOC.
FileDepth	Sectioning depth of the file splits.
CombineHigherDepths	Combine higher section levels.
FileSectionNames	Use section names for file names, else use numbers.
\FilenameLimit	Maximum length of the generated filenames.
FootnoteDepth	Sectioning depth of footnotes.
\abstractname	The name of the abstract.
\mathimagename	The SVG math image lateximage alt tag.
\packagediagramname	The suffix for a package's lateximage alt tags.
\CSSFilename	The CSS for the following files.
\HTMLLanguage	The HTML lang tag.
\HTMLTitle	The homepage's <title>, overriding \title.
\HTMLTitleBeforeSection	Set subpage <title>s to \HTMLTitle - sectionname
\HTMLTitleAfterSection	Set subpage <title>s to sectioname - \HTMLTitle
\HTMLAuthor	The HTML author meta tag, overriding \author.
\HTMLDescription	The HTML description meta tag.
\HTMLFirstPageTop	Heading for the home page.
\HTMLPageTop	Heading for the other pages.
\HTMLPageBottom	Footing for all pages.
HTMLDebugComments	Boolean to generate HTML comments.

Ctr tocdepth

tocdepth: Sectioning depth of the table of contents. See section 17 for a list of LaTeX stack depths.

Ctr SideTOCDepth
Default: 1

SideTOCDepth: Sectioning depth of the sideTOC. Defaults to 1, causing the sideTOC to show sections but not subsections.

sideTOC

Each subpage of the website has its own small table of contents on the side (the "sideTOC"). Its depth is set by SideTOCDepth. This sideTOC is only shown if the web page is wide enough. When using a narrow web browser window, "responsive web design" is used to show the sideTOC at the top of the page and a link back to **Home** at the bottom.

It is recommended to set:

```
SideTOCDepth = FileDepth
```

or

```
SideTOCDepth = FileDepth+1
```

⚠ inaccessible pages

If SideTOCDepth < FileDepth, web pages will be inaccessible via the sideTOC.

\sidetocname
Default: Contents

\sidetocname: Name of the sideTOC. Paragraphs are allowed.

Ctr FileDepth
Default: -5

FileDepth: Sectioning depth of file splits. Defaults to -5, causing the entire HTML website to be one single file.

- To place the entire file into one HTML page, use:
  `\setcounter{FileDepth}{-5}`
- To split the HTML file at \section depth, use:
  `\setcounter{FileDepth}{1}`

⚠

- To ensure that the HTML pages/files are accessible:
  Place a \tableofcontents somewhere before the first section break (therefore in the "home page"), and set
  `tocdepth >= FileDepth`

Bool CombineHigherDepths
Default: true

CombineHigherDepths: Combine a higher section with its first lower subsections, down to the FileDepth. Defaults to true. Set to false to simulate the concept of a chapter opening on its own page, for example.

The file splits are controlled by the counter FileDepth and the boolean CombineHigherDepths. Setting FileDepth to 0 splits the file at chapters, 1 at sections, etc. CombineHigherDepths controls whether to combine pages at levels higher than the chosen FileDepth, such as in this tutorial where the page which opens the chapter also contains the first section. Be careful to set tocdepth and SideTOCDepth to allow access to each page of the website. Set tocdepth and SideTOCDepth to be greater than or equal to FileDepth.

⚠ Inaccesible pages!

⚠ Lost in an old page!

When making changes to the file structure, it is possible to end up with the web browser pointing to an old file which is no longer in use. When this occurs, changes to the web site will not appear in the browser, even if reloading the page, because that page is no longer in use. It is best to return to the home page, clean the files (`lwarpmk cleanall`), change FileDepth and/or CombineHigherDepths, then finally recompile and renavigate to the desired page using the new file structure.

Bool FileSectionNames
Default: true

FileSectionNames: If true, web page filenames are derived from a sanitized version of the section names. If false, web pages are numbered. Either way, the HTMLFilename option is used as a prefix. See section 8.4.1 for examples of naming and numbering HTML files. The user must ensure that filenames are unique after begin sanitized. For example, math in the section name is removed before creating the filename, so the rest of the filename must be sufficiently unique to avoid name collisions.

⚠ Unique filename!

\FilenameLimit
Default: 80

\FilenameLimit: The maximum length of the filenames generated by lwarp. ".html" is added to this length. Redefine with \newcommand.

Ctr FootnoteDepth
Default: 3

FootnoteDepth: Determines where to place pending footnotes. 3 places footnotes before each break down to the \subsubsection level. 1 places footnotes before each \section break. Any pending footnotes are also placed at the bottom of each page before each file break.

Bool HTMLDebugComments
Default: false

HTMLDebugComments: Set true to generate HTML comments, such as which section or is being opened or closed.

\abstractname
Default: Abstract

\abstractname: The name of the abstract. This may also be over-written by the babel package. Defaults to "Abstract".

Placed before \begin{document}, or before any sectioning command which causes a file break:

\CSSFilename
Default: lwarp.css

\CSSFilename: {⟨*filename.css*⟩} Sets the css file to use for the following files. May be changed before each each sectioning command which would cause a file split.

The css styles of the web pages are set by the \CSSFilename command. If \CSSFilename is not used, a default plain style is used to mimic printed LaTeX output. lwarp_sagebrush.css is a semi-fancy colored style as shown in this tutorial. Change it to lwarp_formal.css for a more formal look, or comment out the \CSSFilename command to see the default. \CSSFilename may be used before each file break to set the css for individual pagess of the website.

\HTMLLanguage
Default: en-US

\HTMLLanguage: {⟨*langauge*⟩} The HTML file's HTML lang meta tag. Defaults to en-US.

\HTMLTitle
Default: \thetitle

\HTMLTitle: {⟨*title*⟩} Overrides \title for the HTML header's meta title. Defaults to \thetitle, which is set by \title, or empty otherwise. Unlike the author, \thetitle is set by \title even if not using the titling package.

\HTMLTitleBeforeSection
Default: \HTMLTitleBeforeSection

\HTMLTitleBeforeSection: Sets subpage <title> tags to show the website title followed by the section name.

\HTMLTitleAfterSection

\HTMLTitleAfterSection: Sets subpage <title> tags to show the section name followed by the website title.

custom <title>

To customize subpage <title>s, redefine \theHTMLTitleSection, which defaults to:

```
\def\theHTMLTitleSection{%
  \theHTMLTitle\theHTMLTitleSeparator\theHTMLSection%
}
```

\HTMLAuthor
Default: \theauthor

\HTMLAuthor: {⟨*author*⟩} The HTML header's meta author. Defaults to \theauthor, which is set by \author if using the titling package, but is empty otherwise. There are several ways to represent the author and affiliations, especially if using the authblk package, most of which do not result in a sensible \theauthor, so \HTMLAuthor is useful to create a list of authors without their affiliations.

\HTMLDescription
Default: <empty>

\HTMLDescription: {⟨*description*⟩} Sets the HTML description tag for the following files. May be changed before each each sectioning command which would cause a file split.

\HTMLFirstPageTop
Default: <empty>

\HTMLFirstPageTop: {⟨*contents*⟩} A user-definable custom action applied to the top of the home page. Useful for logos, etc. Defaults empty. Ignored in print output.

\HTMLPageTop
Default: <empty>

\HTMLPageTop: {⟨*contents*⟩} A user-definable custom action applied to the top of pages other than the home page. Useful for logos, etc. Defaults empty. \LinkHome may be used to place a link back to the homepage. Ignored in print output.

\HTMLPageBottom
Default: <empty>

\HTMLPageBottom: {⟨*contents*⟩} A user-definable custom action applied to the bottom of each web page. Useful for authors, copyright notices, contact information, etc. Defaults empty. \LinkHome may be used to place a link back to the homepage. Ignored in print output.

Placed in the home page before the first sectioning command which causes a file break:

\tableofcontents
⚠ TOC on the homepage!

\tableofcontents: Used to place a table of contents on the home page. This command must be used before the first file split, so that a way is available to navigate to other files from the homepage.

Links to each chapter/section are provided, as selected by tocdepth.

Placed in the document wherever necessary:

\mathimagename
Default: math image

\mathimagename: When creating an SVG math image, its alt tag may be set to the math expression, which may be hashed for image reuse. In the case of \ensuremath or after \inlinemathother, where the contents require a unique image for each instance of the same expression, the alt tag is set to \mathimagename, and the image is not reused.

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "math image", and it may be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following SVG math images.

\packagediagramname
Default: diagram

\packagediagramname: For many packages, the output is placed inside a lateximage with an HTML alt tag set to the package name followed by \packagediagramname. For example:

```
(-xy- diagram)
```

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "diagram", and may it be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following `lateximages`.

Env warpprint

warpprint: An environment which is only used while generating print output. Place inside anything which does not apply to HTML and which may cause problems with lwarp. If lwarp knows about and emulates or supports a package then its related macros, lengths, counters, etc. probably won't have to be placed inside a `warpprint` environment, but unknown packages may cause problems which may be isolated from lwarp using this environment.

⚠ *Do not place anything else on the same line as* `\end{warpprint}`.

Env warpHTML

warpHTML: An environment which is only used while generating HTML output. This is useful for website logos and other items which have no purpose in printed output.

⚠ *Do not place anything else on the same line as* `\end{warpHTML}`.

\warpprintonly

\warpprintonly: {⟨*contents*⟩} A macro version of the `warpprint` environment.

\warpHTMLonly

\warpHTMLonly: {⟨*contents*⟩} A macro version of the `warpHTML` environment.

8.4.1 Example HTML file naming

Examples of ways to name or number HTML files:

Numbered HTML nodes:

Example: Homepage `index.html`, and `node-1`, `node-2`. [13]

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={node-}
]{lwarp}
\boolfalse{FileSectionNames}
```

Named HTML sections, no prefix:

Example: `index.html`, and `About.html`, `Products.html`

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={}
]{lwarp}
\booltrue{FileSectionNames}
```

[13] See `\SetHTMLFileNumber` to number in groups by chapter, for example.

Named HTML sections, with prefix:

Example: Homepage `mywebsite.html`, and additional pages such as `mywebsite-About.html`, `mywebsite-Products`, etc.

```
\usepackage[
    HomeHTMLFilename=mywebsite,
    HTMLFilename={mywebsite-}
]{lwarp}
\booltrue{FileSectionNames}
```

8.5 Customizing the css

`\CSSFilename`
Default: `lwarp.css`

`\CSSFilename` may be used to choose which `.css` file is used to display each page of the web site. Use `\CSSFilename` before `\begin{document}` to assign the style of the home page. If different parts of the website should have different styles, call `\CSSFilename` again before each section heading which creates a new file. This may be changed numerous times throughout the file, resulting in different HTML pages having different css files assigned:

```
...
\CSSFilename{myCSS.css}
\chapter{Another Chapter}
...
```

The styles provided by lwarp include:

`lwarp.css`: A default style if `\CSSFilename` is not used. This style is comparable to a plain LaTeX document. To set this style, you may use `\CSSFilename{lwarp.css}`, or no `\CSSFilename` call at all.

`lwarp_formal.css`: A formal style with a serif fonts and a traditional look.

`lwarp_sagebrush.css`: A style with muted colors, gradient backgrounds, additional borders, and rounded corners.

To see each style in use, change the `\CSSFilename` entry in the tutorial, `lwarpmk html` again, and then reload the tutorial webpage.

Custom css

A customized style may also be created. For each new project a file called `sample_project.css` is generated. This may be renamed to `<project>.css` then used by assigning `\CSSFilename{<project>.css}`.

⚠ Rename it!

Note that `sample_project.css` is overwritten whenever lwarp is loaded in print mode. It is therefore important to rename the file to something like `<project>.css` before using it, so that your own changes are not overwritten.

`<project>.css` has an entry which loads `lwarp.css`, and this entry may be changed to load `lwarp_formal.css` or `lwarp_sagebrush.css` if desired. Additional changes to the css may be made by making entries later in the `<project>.css` file.

File lwarp.css
File project.css
File sample_project.css

It is best to make a local project-specific CSS file such as `project.css`, containing only things which are different from `lwarp.css`. The file `project.css` should refer to `lwarp.css` as follows:

```
/* ( --- Start of project.css --- ) */
/* ( --- A sample project-specific CSS file for lwarp --- ) */

/* Uncomment one of the following: */
@import url("lwarp.css") ;
/* @import url("lwarp_formal.css") ; */
/* @import url("lwarp_sagebrush.css") ; */

/* Project-specific CSS setting follow here. */
/* . . . */

/* ( --- End of project.css --- ) */
```

Finally use `\CSSFilename{<project>.css}` in the document to activate the custom CSS.

8.6 Selecting the operating system

Prog Unix
Prog Mac OS
Prog Linux
Prog MS-Windows
Prog Windows
Opt OSWindows

lwarp tries to detect which operating system is being used. UNIX / MAC OS / LINUX is the default (collectively referred to as "UNIX" in the configuration files), and MS-WINDOWS is supported as well.

If MS-WINDOWS is not correctly detected, use the lwarp option `OSWindows`.

When detected or specified, the operating-system path separator used by lwarp is modified, and the boolean `usingOSWindows` is set `true`. This boolean may be tested by the user for later use.

8.7 Selecting actions for print or HTML output

The following environments and macros are used to select actions which only apply to either traditional LaTeX print-formatted PDF generation, or to HTML generation.

For most of built-in LaTeX and many additional packages there is user-level source code support or emulation, so no special handling will be required. For those cases which lwarp does not handle by itself, the following environments and macros may be used to isolate sections of code for print-only or HTML-only.

These environments are also useful for creating a special version of the titlepage for print and another for HTML.

Env warpHTML

Anything which is to be done only for HTML5 output is surrounded by a `warpHTML` environment:

```
\begin{warpHTML}
 ... something to be done only during \HTML\ generation
\end{warpHTML}
```

⚠ `\end{warpHTML}` Do *not* place anything else on the same line as `\end{warpHTML}`. The exact phrase is used to mark the end of the environment.

Env `warpprint` Anything which is to be done only for print output is surrounded by a `warpprint` environment:

```
\begin{warpprint}
 ... something to be done only during traditional \PDF\ generation
\end{warpprint}
```

⚠ `\end{warpprint}` As above, do not place anything else on the line with `\end{warpprint}`.

Env `warpall` Anything which is to be done for any output may be surrounded by a `warpall` environment. Doing so is optional.

```
\begin{warpall}
 ... something to be done during print \PDF\ or \HTML\ output
\end{warpall}
```

As above, do not place anything else on the line with `\end{warpall}`.

Macros are also provided for print-only or HTML-only code:

`\warpprintonly` {⟨*actions*⟩}

Performs the given actions only when print output is being generated.

`\warpHTMLonly` {⟨*actions*⟩}

Performs the given actions only when HTML output is being generated.

8.8 Commands to be placed into the `warpprint` environment

Certain print-related commands should always be placed inside a `warpprint` environment, or may need other special handling. These are unrelated to HTML output, but are hard to isolate automatically. For example:

- Paragraph formatting: `\parindent` `\parskip`
- Manual page positions such as the textpos package, which is emulated but only in a limited way.

- Anything changing the page counter. lwarp requires that the page counter not be adjusted during HTML output.

Some packages require additional setup commands. Where these packages are emulated for HTML, setup commands may work for the emulated HTML output as well as for print output. See the details for each package in this document for more information.

Also see section 14: Troubleshooting.

8.9 Title page

In the preamble, place an additional block of code to set the following:

```
\title{Document Title} % One line only
\author{Author One\affiliation{Affiliation One} \and
    Author Two\affiliation{Affiliation Two} }
\date{Optional date}
```

The title is used in the meta tags in the HTML files, unless overridden by `\HTMLTitle`, and the rest are used in `\maketitle`. To use a `\subtitle` or `\published` field, see section 65.8.

`\maketitle` Use `\maketitle` just after the `\begin{document}`, as this will establish the title of the homepage. Optionally, use a `titlepage` environment instead.

Env `titlepage` The `titlepage` environment may be used to hold a custom title page. The titlepage will be set in a `<div>` class `titlepage`, and `\printtitle`, etc. may be used inside this environment.

Env `titlingpage` Another form of custom title page, where `\maketitle` is allowed, and additional information may be included as well.

`\title` {⟨*title*⟩}

⚠ newlines Avoid newlines in the `\title`; these will interfere with the file break and css detection. Use a `\subtitle` command instead (section 65.8). The title will appear in the document `\maketitle` as a heading `<h1>`. The HTML meta `title` tag will also have this title, unless `\HTMLTitle` is used to set the meta title to something else instead.

`\author` {⟨*author*⟩}

In `\author`, `\protect` may be needed before some formatting commands. In HTML, the author will appear in a `<div>` of class `author` in the `\maketitle`. If the titling package is used, the author will also appear in a HTML meta tag, but `\HTMLAuthor` may be necessary to create a plain list of names if `\author` had affiliations added. `\affiliation` is a new addition to lwarp.

`\date` {⟨*date*⟩}

`\date` works as expected. In HTML, this will appear in a `<div>` class `titledate`.

`\thanks` {⟨*text*⟩}

\thanks are allowed in the titlepage fields, and will be rendered as HTML notes at the bottom of the title page.

8.10 HTML page meta descriptions

\HTMLDescription {⟨*A description of the web page.*⟩} The default is no description.

limitations Each page of HTML output should have its own HTML meta description, which usually shows up in web search results, is limited to around 150 characters in length, and should not include the ASCII double quote character (").

placement Use \HTMLDescription just before \begin{document} to set the description of the home page, and also just before each sectioning command such as \chapter or \section where a new file will be generated, depending on FileDepth. For example, if FileDepth is 1, use \HTMLDescription just before each \section command, and that description will be placed inside the HTML page for that \section. The same descrition will be used for all following HTML files as well, until reset by a new \HTMLDescription. It is best to use a unique description for each HTML file.

disabling To disable the generation of HTML description meta tags, use:

```
\HTMLDescription{}
```

8.11 HTML homepage meta title

\HTMLTitle {⟨*title*⟩} Sets the contents of the web page <meta name="title"> element. Defaults to \HTMLtitle{\thetitle}. May be set empty to cancel the meta title tag.

See section 8.4 for \HTMLTitleBeforeSection and \HTMLTitleAfterSection, used to set the title for HTML subpages.

8.12 HTML page meta author

\HTMLAuthor {⟨*author*⟩} Sets the contents of the web page <meta name="author"> element. Defaults to \HTMLAuthor{\theauthor}. May be set empty to cancel the meta author tag.

\author may be used to create a list of authors and their affiliations, in several formats if using authblk, and these may not successfully parse properly into a sensible list for \theauthor. \HTMLAuthor may be used to set the meta tag to a simple list of names.

9 Special cases and limitations

Some commonly-used LaTeX expressions should be modified as follows to allow for a smooth conversion to both HTML and print-formatted outputs.

Need help?

See the General Index for "how-to", and the Troubleshooting Index if something doesn't work. The Index of Objects contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category. A Troubleshooting section is also available.

9.1 Things to avoid

In the document, avoid the following:

page counter: Do not adjust the page counter. If doing so is required for the print version, place the adjustment inside a `warpprint` environment.

Custom math environment macros: Do not use expressions such as `\beq` as a replacement for `\begin{equation}`.

Custom macros in section, figure, table names: Custom macros which appear in sectioning commands or float captions then appear in the `.toc`, `.lof`, and `.lot` lists, and should be made robust using `\newrobustcmd` or `\robustify` from etoolbox, xparse, etc.

When setting `FileSectionNames` to `true` to name the HTML files from the section names, the file names are created from sanitized versions of the chapter or section names, but the section names must be plain text or something which expands into plain text. Robust macros will not work at the sectioning level which is used for file names, but a robust macro or other complicated name may be used for the manditory argument of `\chapter`, `\section`, etc., if a plain-text version is also included in the optional argument:

```
\chapter[Plain Name]{\ARobustMacro{Fancy Name}}
```

9.1.1 Invalid HTML

Additionally, some objects are valid LaTeX, but invalid HTML. An example is a tabular inside `\textbf`, since HTML does not allow a table inside a span. lwarp will create the table, and the browser may support it, but the result is technically invalid.

9.2 Formatting

9.2.1 Text formatting

⚠ `\bfseries`, etc.

`\textbf`, etc. are supported, but `\bfseries`, etc. work only in some situations.

⚠ HTML special chars

&, <, and > have special meanings in HTML. If `\&`, `\textless`, and `\textgreater` are used, proper HTML entities will be used, but there may be HTML parsing problems if these special characters occur unescaped in program listings or other verbatim text.

program listings

For program listings, the listings package is supported, and its `literate` option is used to convert &, <, and > to proper HTML entities.

verbatim

The various verbatim-related environments do not convert &, <, and >, so care must be taken to avoid accidentally including valid HTML code inside these environments. Adding a space on either side may be sufficient.

9.2.2 Horizontal space

\hspace

\hspace is converted to an inline HTML span of the given width, except that 0 width is ignored, a width of .16667em is converted to an HTML thin breakable space (U+2009), and a \fill is converted to a \qquad.

\,

~ and \, are converted to HTML entities.

\kern
\hskip

\kern and \hskip are entered into the HTML PDF output as-is, then interpreted by *pdftotext*, and thus usually appear as a single space.

9.2.3 Text alignment

Use the environments center, flushright, flushleft instead of the macros \centering, \raggedright, \raggedleft.

⚠ figure & table alignment

\centering, etc. are honored in a figure or table if they are the first command inside the float:

```
\begin{table*}
\centering
\caption{A Table}
. . .
```

9.2.4 Accents

Native LaTeX accents such as \" will work, but many more kinds of accents are available when using Unicode-aware XeLaTeX and LuaLaTeX.

9.2.5 textcomp package

Pkg textcomp

Some textcomp symbols do not have Unicode equivalents, and thus are not supported.

⚠ missing symbols

Many textcomp symbols are not supported by many fonts. In the CSS try referencing fonts which are more complete, but expect to see gaps in coverage.

9.2.6 Superscripts and other non-math uses of math mode

Use ^{x} instead of ^{x}

9.2.7 Empty `\item` followed by a new line of text or a nested list:

lists Use a trailing backslash: `\item[label] \`

9.2.8 Filenames and URLs in lists or footnotes

filename underscore Escape underscores in the filenames:

```
\item[\href{file\_name.pdf}{text}]
```

9.2.9 relsize package

Pkg relsize For HTML, only the inline macros are supported: `\textlarger`, `\textsmaller`, and `\textscale`. Each becomes an inline span of a modified `font-size`.

`\relsize`, `\larger`, `\smaller`, and `\relscale` are ignored.

While creating SVG math for HTML, the original definitions are temporarilty restored, and so should work as expected.

⚠ not small The HTML browser's setting for minumum font size may limit how small the output will be displayed.

9.3 Boxes and minipages

9.3.1 Marginpars

`\marginpar` `[`⟨*left*⟩`]` `{`⟨*right*⟩`}` `\marginpar` may contains paragraphs, but in order to remain inline with the surrounding text lwarp nullifies block-related macros inside the `\marginpar`. Paragraph breaks are converted to `<br />` tags.

`\marginparBlock` `[`⟨*left*⟩`]` `{`⟨*right*⟩`}` To include block-related macros, use `\marginparBlock`, which takes the same arguments but creates a `<div>` instead of a `<span>`. A line break will occur in the text where the `\marginBlock` occurs.

9.3.2 Save Boxes

TEX boxes are placed inline and do not allow line breaks, so boxes with long contents may overflow the line during HTML conversion. This is mostly a problem when the boxes contain objects which themselves hold large HTML tags, such as rotation commands with long contents. When this object overflows the line, some HTML code will be lost and the page will be corrupted.

9.3.3 Minipages

⚠ inline — A line of text with an inline `minipage` or `\parbox` will have the `minipage` or `\parbox` placed onto its own line, because a paragraph is a block element and cannot be made `inline-block`.

placement — `minipages` and `\parboxes` will be placed side-by-side in HTML unless you place a `\newline` between them.

side-by-side — Side-by-side `minipages` may be separated by `\quad`, `\qquad`, `\enskip`, `\hspace`, `\hfill`, or a `\rule`. When inside a `center` environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side `minipages` and these spacing commands, but not at the start or end of the paragraph.

⚠ minipage in a span — There is limited support for `minipages` inside an HTML `<span>`. An HTML `<div>` cannot appear inside a `<span>`. While in a `<span>`, `minipages`, and `\parboxes`, and any enclosed lists have limited HTML tags, resulting in an "inline" format, without markup except for HTML breaks. Use `\newline` or `\par` for an HTML break.

⚠ minipage size — When using `\linewidth`, `\textwidth`, and `\textheight`, widths and heights in HTML are scaled proportionally to a 6×9 inch text area, and inside a `multicols` `\linewidth` is divided by the specified number of columns.

if width is `\linewidth` — If a `minipage` or `\parbox` is assigned a width of exactly `\linewidth`, in HTML it is automatically given no HTML width, thus allowed to fill the line as needed, similar to how it appears in print output.

full-width if HTML — A new macro `\minipagefullwidth` requests that, during HTML output, the next single `minipage` or `\parbox` be generated without an HTML `width` attribute, allowing it to be the full width of the display rather than the declared print-output width. This may be useful where the printed version's width makes no sense in HTML.

⚠ `tabular`, `multicols`

`\UseMinipageWidths`
`\IgnoreMinipageWidths` — Inside a `tabular` or `multicols` environment, where the width depends on the browser window, `\minipagefullwidth` is effectively used by default for every `minipage` or `\parbox` inside the environment. `\UseMinipageWidths` may be used to tell lwarp to honor the specified widths of all following `minipages` and `\parboxes` until the end of the local scope, and `\IgnoreMinipageWidths` may be used to tell lwarp to ignore the specified widths.

⚠ text alignment — Nested `minipages` adopt their parent's text alignment in HTML, whereas in regular LaTeX PDF output they do not. Use a `flushleft` or similar environment in the child `minipage` to force a text alignment.

9.3.4 Side-by-side minipages

Place side-by-side minipages inside a `center` environment, with horizontal space between them, such as `\quad`, `\qquad`, `\hspace`, or `\hfill`. The result is similar in print and HTML. Do not use space commands at the start or end of the line.

9.3.5 Framed minipages and other environments

\fbox can only be used around inline items during HTML output, but HTML cannot place a block element such as a for a minipage or a list inside of a . Several options are provided for framing an object, depending on which kind of object and which packages are loaded:

\fbox
\fboxBlock
Env fminipage

For a framed object, options include:

To remove the frame in HTML output: Place the \fbox command and its closing brace inside warpprint environments. This will nullify the frame for HTML output.

For inline text:

To frame the contents inline with some formatting losses in HTML: This is the default action of \fbox when enclosing a minipage. During HTML output, \fbox nullifies the HTML tags for minipage, \parbox, and lists. The contents are included as inline text inside the \fbox's of class framebox. For lists, line breaks are converted to HTML breaks. The result is a plain-text inline version of the contents, framed inline with the surrounding text, but lacking any extra HTML markup.

For inline minipage and lists:

To frame the contents on their own line with improved formatting in HTML: A new command \fboxBlock is included, intended to be a direct replacement for \fbox for cases where the \fbox surrounds a minipage, table, or list. For print output, this behaves as \fbox. For HTML output, the contents are placed inside an HTML with the class framed, resulting in the contents being placed on their own line with a frame surrounding them. The contents preserve their HTML formatting, so lists and minipages look nicer, and valid HTML is created for a tabular. While an \fbox containing a tabular is valid LaTeX code, the result in HTML is problematic since a table is a not a , so use \fboxBlock around a tabular, or else place the tabular inside a minipage, or use fminipage, described next. Also see below regarding the "Misplaced alignment tab character &." error.

For display tabular, minipages, and lists:

To create a framed minipage in both print and HTML: A new environment fminipage is included. For print output, this is identical to minipage, except that it is also framed. For HTML output, this forms a of class framed, the contents preserve their HTML formatting, and valid HTML is created for a tabular. Also see section 84 for a new environment fcolorminipage. Also see below regarding the "Misplaced alignment tab character &." error.

colored boxes and frames:

To create colored frames and boxes: See section 486 for xcolor's \colorbox and \fcolorbox, and lwarp's additional \colorboxBlock and \fcolorboxBlock.

⚠ Misplaced alignment tab character &

To frame tables or verbatim environments: Place the contents inside a fminipage, or perhaps a \fboxBlock for a tabular. Also, if using \fboxblock with tabular, you will have to use \StartDefiningTabulars before the start of the macro which uses \fboxBlock and the tabular, and \StopDefiningTabulars afterwards. Also see the lwarp documentation for the fancybox package.

To frame equations: See section 210 for the fancybox package.

For fancy framed minipages: See packages boxedminipage, shadow, fancybox, framed, mdframed.

Custom environments: Use a custom environment to create a sidebar, containing a `BlockClass` environment with custom CSS formatting, and `\warpprintonly{\hrule}` command:

```
\begin{BlockClass}{frameminipage}% ignored in print output
  % use \CSS\ to format div class ``framedminipage''
\warpprintonly{\hrule} % only appears in print output
Contents
\warpprintonly{\hrule} % only appears in print output
\end{BlockClass}
```

9.3.6 fancybox package

Pkg fancybox

framed equation example

fancybox's documentation has an example `FramedEqn` environment which combines math, `\Sbox`, a `minipage`, and an `\fbox`. This combination requires that the entire environment be enclosed inside a `lateximage`, which is done by adding `\lateximage` at the very start of `FramedEqn`'s beginning code, and `\endlateximage` at the very end of the ending code. Unfortunately, the HTML `alt` attribute is not used here.

```
\newenvironmentFramedEqn
{
\lateximage% NEW
\setlength{\fboxsep}{15pt}
. . . }{. . .
\[\fbox{\TheSbox}\]
\endlateximage% NEW
}
```

framing alternatives

`\fbox` works with fancybox. Also see lwarp's `\fboxBlock` macro and `fminipage` environment for alternatives to `\fbox` for framing environments.

framed table example

The fancybox documentation's example framed table using an `\fbox` containing a `tabular` does not work with lwarp, but the `FramedTable` environment does work if `\fbox` is replaced by `\fboxBlock`. This method loses HTML formatting. A better method is to enclose the table's contents inside a `fminipage` environment. The caption may be placed either inside or outside the `fminipage`:

```
\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
. . .
\end{tabular}
\end{fminipage}
\end{table}
```

⚠ framed verbatim

lwarp does not support the `verbatim` environment inside a span, box, or fancybox's `\Sbox`, but a `verbatim` may be placed inside a `fminipage`. The fancybox documentation's example `FramedVerb` may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
\VerbatimEnvironment
\fminipage{#1}
\beginVerbatim
}{
\endVerbatim
\endfminipage
}
```

framed \VerbBox

fancybox's \VerbBox may be used inside \fbox.

indented alignment

LVerbatim, \LVerbatimInput, and \LUseVerbatim indent with horizontal space which may not line up exactly with what *pdftotext* detects. Some lines may be off slightly in their left edge.

9.3.7 mdframed package

Pkg mdframed support

Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for mdframed environments and frame titles.

⚠ loading

When used, lwarp loads mdframed in HTML with `framemethod=none`.

font

For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where \textbf must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the mdframed source). Since lwarp does not support \bfseries and friends, only one font selection may be made at a time.

theoremtitlefont

theoremtitlefont is not supported, since the following text is not in braces in the mdframed source.

ignored options

userdefinedwidth and align are currently ignored.

css classes

Environments created or encapsulated by mdframed are enclosed in a of class mdframed, and also class md<environmentname> for new environments.

Frame titles are placed in a of class |mdframedtitle|. Subtitles are in a of class |mdframedsubtitle|, and likewise for subsubtitles.

9.4 Section names

If using named HTML files, by selecting `\booltrue{FileSectionNames}`:

`\FilenameSimplify` To remove common short words from the automatically-generated filenames, replacing each with a single hyphen "-", use `\FilenameSimplify`:

```
\FilenameSimplify*{-in-}
\FilenameSimplify*{A-}
```

The first example removes the word "in" in the middle of a filename, and the second example removes "A" at the start of the filename. The star forces the arguments to be detokenized, which is required for a plain-text comparison. (The unstarred form is used for a token-sensitive comparison, which is seldom required by the user.) After simplfication, repeated hyphen characters will be further simplified to a single hyphen "-". Finally, single hyphens at the start or end of the filename are removed.

`\FilenameNullify` ⚠ macros in section names

Macro names may appear in the automatically-generated file names. To remove these, create *non-robust* nullified versions of the macros, ensuring that each line ends with a percent character `%` as shown below. These are placed inside `\FilenameNullify`, which adds them to the list of macros which are nullfiied during filename generation. Low-level macros such as `\begingroup` will cause problems when nullfied. Many macros such as `\textbf` are already nullfied. lwarp also already nullifies built-in symbol and textcomp macros, including if defined by xunicode, but not all xunicode macros. See the definition of `\LWR@nullfonts` for a complete list.

```
\FilenameNullify{%
  \renewcommand*{\macroname}[1]{#1}%
  \renewcommand*{\anothermacro}{}%
}
```

⚠ duplicate filename

Avoid duplicate file names. Section names at levels which result in HTML file splits must be unique. lwarp will generate an error if a duplicate HTML filename is generated. Use the optional TOC caption entry parameter for formatting. Remember to `\protect` LaTeX commands which appear in section names and TOC captions.

⚠ math in section names

If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring`:

```
\section{A math \texorpdfstring{$1+2=3$}{text description} name}
```

9.5 Cross-references

labels ⚠ label characters

Labels with special characters may be a problem. It is best to stick with alpha-numeric, hyphen, underscore, and perhaps the colon (if not French).

`\nameref` ⚠ empty link

`\nameref` refers to the most recently-used section where the `\label` was defined. If no section has been defined before the `\label`, the link will be empty. Index entries also use `\nameref` and have the same limitation.

9.5.1 Page references

⚠ LaTeX page numbers

The printed page does not translate to the HTML page, so \pageref references are converted to parentheses containing \pagerefPageFor, which defaults to "see ", followed by a hyperlink to the appropriate object.

Ex:

```
\ref{sec:name} on page \pageref{sec:name}
```

in HTML becomes:

"Sec. 1.23 on page (**see** sec. 1.23)".

\pagerefPageFor may be redefined to "page for ", empty, etc. See page 462.

9.5.2 cleveref and varioref packages

Pkg cleveref
Pkg varioref

cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for \cpageref and \cpagerefrange. This phrase includes \cpagerefFor, which defaults to "for".

⚠ cleveref page numbers

Ex:

```
\cpageref{tab:first,tab:second}
```

in html becomes:

"pages **for** table 4.1 and **for** table 4.2"

See \cpagerefFor at page 535 to redefine the message which is printed for page number references.

9.5.3 Hyperlinks, hyperref, and url

Pkg hyperref
Pkg url

lwarp emulates hyperref, including the creation of active hyperlinks, but does not require that hyperref be loaded by the document.

⚠ comments between arguments

Do not place a comment with a % character between arguments for \hyperref, etc., as it is neutralized for inclusion in HTML URLs.

lwarp can also load url, but url should not be used at the same time as hyperref, since they both define the \url command. lwarp does not (yet) attempt to convert url links into hyperlinks during HTML output, nor does the print version of url create hyperlinks.

⚠ backref

When generating HTML, lwarp's emulation of hyperref does not automatically load backref, so backref must be loaded explicitly.

9.5.4 Footnotes and page notes

lwarp uses native LaTeX footnote code, although with its own \box to avoid the LaTeX output routine. The usual functions mostly work as-is.

footnote numbering

To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For bigfoot, manyfoot, or perpage:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by `FootnoteDepth`, which is not necessarily by HTML page. This is recommended for `\alph`, `\Alph`, or `\fnsymbol` footnotes, due to the limited number of symbols which are available.

footmisc

The footmisc `stable` option is emulated by lwarp.

⚠ sectioning commands

When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the footmisc package with the `stable` option, provide a short TOC entry, and `\protect` the `\footnote`:

```
\usepackage[stable]{footmisc}
. . .
\subsection[Subsection Name]
    {Subsection Name\protect\footnote{A footnote.}}
```

memoir with footmisc

⚠ memoir

If using memoir class, with which lwarp preloads footmisc, the `stable` option must be declared before lwarp is loaded:

```
\PassOptionsToPackage{stable}{footmisc}
\usepackage{lwarp}
. . .
```

Do not use a starred sectioning command. As an alternative, it may be possible to adjust `\secnumdepth` instead.

fancybox, fancyvrb

⚠ `\VerbatimFootnotes`

⚠ sectioning or displaymath

If using fancybox or fancyvrb with `\VerbatimFootnotes`, and using footnotes in a sectioning command or display math, use `\footnotemark` and `\footnotetext`:

```
\subsection[Subsection Name]
    {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when `\VerbatimFootnotes` are selected. The browser usually compensates.

pfnote

⚠ pfnote numbers

While emulating pfnote, lwarp is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. lwarp therefore uses continuous footnote numbering even for pfnote.

bigfoot, manyfoot

If using the bigfoot package, and possibly also manyfoot, problems may occur with counter allocation because lwarp uses many counters, and there is a difference in how counters numbered 256 and up are handled in pdfLaTeX. With bigfoot this has been known to show up as an error related to one footnote insert being forbidden

inside another. Another problem showed up as a input stack error, and which of these problems occurred depended on how many counters were allocated.

As a possible solution, try creating several new counters before defining bigfoot or manyfoot footnotes, hoping to shift the problematic counter above the 256 threshold. It may instead be necessary to use XeLaTeX or LuaLaTeX instead of pdfLaTeX.

9.6 Front and back matter

9.6.1 Custom classes with multiple authors and affiliations

Some classes allow multiple authors and affiliations. Often it is possible to emulate these using a standard class along with authblk:

```
%\documentclass{customclass} % for print document
\documentclass{article} % for html document

\usepackage{lwarp}
\begin{warpHTML}
\usepackage{authblk}
\let\affiliation\affil % maybe required
\end{warpHTML}
```

9.6.2 Starred chapters and sections

The following describes \ForceHTMLPage and \ForceHTMLTOC, which may be used for endnotes, glossaries, tocbibind, bibliographies, and the index. See the following sections where applicable. Continue here if interested in the reason for adding these commands to lwarp.

Some packages use \chapter* or \section* to introduce reference material such as notes or lists, often to be placed in the back matter of a book. These starred sections are placed inline instead of on their own HTML pages, and they are not given TOC entries.

lwarp provides a method to cause a starred section to be on its own HTML page, subject to FileDepth, and also a method to cause the starred section to have its own TOC entry during HTML output.

\ForceHTMLPage To place a starred section on its own HTML page, use \ForceHTMLPage just before the \chapter* or \section*. lwarp will create a new page for the starred sectional unit.

A starred sectional unit does not have a TOC entry unless one is placed manually. The typical method using \phantomsection and \addcontentsline works for inline text but fails when the new starred section is given its own webpage after the TOC entry is created, or when creating an EPUB where the TOC entry will point to the page before the starred section. If the starred section has its own HTML page but no correct TOC entry pointing to that page, the page will be inaccessible unless some other link is created.

⚠ inaccessible HTML page

\ForceHTMLTOC

To automatically force the HTML version of the document to have a TOC entry for a starred section, use \ForceHTMLTOC just before the \chapter* or \section*, and place \phantomsection and \addcontentsline inside a warpprint environment.

For print output, \ForceHTMLTOC and \ForceHTMLPage have no effect.

9.6.3 abstract package

Pkg abstract

⚠ missing TOC

If using the number option with file splits, be sure to place the table of contents before the abstract. The number option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

9.6.4 titling and authblk

Pkg titling

Pkg authblk

package support

⚠ load order

\published and \subtitle

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 65.8.

9.6.5 tocloft package

Opt [tocloft] titles

Pkg tocloft

Pkg tocloft

⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its titles option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

9.6.6 appendix package

Pkg appendix

⚠ incorrect TOC link

During HTML conversion, the option toc without the option page results in a TOC link to whichever section was before the appendices environment. It is recommended to use both toc and also page at the same time.

9.6.7 pagenote package

Pkg pagenote

pagenote works as-is, but the page option is disabled.

9.6.8 endnotes package

Pkg endnotes

table of contents

To place the endnotes in the TOC, use:

```
\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*{\notesname}{Endnotes} % optional
```

HTML page

To additionally have the endnotes on their own HTML page, if `FileDepth` allows:

```
\ForceHTMLPage
\theendnotes
```

9.6.9 BibTeX

`\etalchar`

Displays a superscript "+" to indicate "and others".

⚠ Modify *.bib

When enough authors are cited for a source, BibTeX may use the `\etalchar` command to display a math superscript with a + character to indicate "and others". Without modification, this will result in an "Improper `\prevdepth`" error. At present, lwarp requires that `\etalchar` be replaced by a text superscript. To do so, add to the start of the `.bib` file the following:

```
@PREAMBLE{"\let\etalchar\relax \newcommand{\etalchar}[1]{\textsuperscript{#1}}"}
```

9.6.10 gloss package

Pkg gloss

To process the HTML glossary:

⚠ compiling

```
bibtex <projectname>_html.gls
```

9.6.11 glossaries package

Pkg glossaries

processing glossaries

Opt GlossaryCmd

Default: `makeglossaries`

Opt [lwarpmk] printglossary

Opt [lwarpmk] htmlglossary

lwarpmk has the commands `lwarpmk printglossary` and `lwarpmk htmlglossary`, which process the glossaries created by the glossaries package using that package's *makeglossaries* program.

The shell command to execute is set by the lwarp option `GlossaryCmd`, which defaults to **`makeglossaries`**. The print or HTML glossary filename is appended to this command.

⚠ *makeglossaries* not found

In some situations it may be required to modify the default command, such as to add the **`perl`** command in front:

```
\usepackage[
   GlossaryCmd={perl makeglossaries},
] {lwarp}
```

xindy language

To set the language to use for processing glossaries with *xindy*:

```
\usepackage[
   GlossaryCmd={makeglossaries -L english},
] {lwarp}
```

Other options for *makeglossaries* may be set as well.

placement and TOC options

The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

Numbered section, on its own HTML page:

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
. . .
\printglossaries
```

Unnumbered section, inline with the current HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\printglossaries
```

Unnumbered section, on its own HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\ForceHTMLPage
\printglossaries
```

⚠ glossary style — The default `style=item` option for glossaries conflicts with lwarp, so the style is forced to `index` instead.

⚠ number list — The page number list in the printed form would become `\namerefs` in HTML, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

print/HTML versions — The print and HTML versions of the glossary differ in their internal page numbers. Separate commands for generating print and HTML glossaries are used, even though the page number is currently ignored.

9.6.12 nomencl package

Pkg nomencl — To process the HTML nomenclature:

```
makeindex <project>_html.nlo -s nomencl.ist -o <project>_html.nls
```

9.6.13 Indexing overview

There are many ways to process indexes for a LaTeX document, including native LaTeX capabilities, a number of packages and classes, the possible availability of shell escape and *latexmk*, and the need to process print and HTML versions. lwarp attempts to provide easy recompilation of indexes along with the rest of the document, but the various indexing options must be set correctly. Numerous examples are given below. Some differ in minor details, so the important parts are highlighted in red, and options are in green.

Once set up properly, the entire document may be recompiled with **`lwarpmk print`** and **`lwarpmk html`**. In some cases, it will also be necessary to compile the indexes with **`lwarpmk printindex`** and **`lwarpmk htmlindex`**. A recompile may then be forced with **`lwarpmk print1`** and **`lwarpmk html1`**.

manual processing — The user may continue to process indexes manually or by shell script without the use of *lwarpmk*, but adjustments will be required to process HTML indexes as well. In

general, `*.idx` and `*.ind` files will be accompanied by `*_html.idx` and `*_html.ind` files.

custom index style

If using a custom indexing style file, see sections 9.6.19 and 9.6.20.

source code

See section 75 for lwarp's core index and glossary code, section 273 for index, section 417 for splitidx, section 272 for imakeidx, section 451 for tocbibind, and section 504.17 for memoir's indexing patches.

9.6.14 Indexing with basic LaTeX and makeidx

lwarpmk processing

The following allow the user to process indexes automatically, or using *lwarpmk*'s commands:

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

For a single index using *makeindex*:

```
\usepackage[makeindex,latexmk] {lwarp}
```

The usual `.idx` and `.ind` files will be used, along with the new `lwarp.ist` style file. When creating the HTML index, "`_html`" is automatically appended to each of the names.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For a single index using *xindy*:

```
\usepackage[
    xindy,
    xindyLanguage=english,                  <optional>
    xindyCodepage=utf8,                     <optional>
    latexmk                                 <optional>
]{lwarp}
```

The usual `.idx` and `.ind` files will be used, along with the new `lwarp.xdy` style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

9.6.15 Indexing with index

lwarp is told how to use *makeindex* using the `PrintIndexCmd` and `HTMLIndexCmd` options. The file `lwarp.ist` is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

For multiple indexes using *makeindex* and index:

(Assuming that the second index has file extensions `.sist` and `.sind`)

```
\usepackage[
  makeindex, latexmk,
  PrintIndexCmd={
    makeindex -s lwarp.ist <projectname>.idx ;
    makeindex -s lwarp.ist
      -o <projectname>.sind <projectname>.sidx
  },
  HTMLIndexCmd={
    makeindex -s lwarp.ist <projectname>_html.idx ;
    makeindex -s lwarp.ist
      -o <projectname>_html.sind <projectname>_html.sidx
  }
]{lwarp}
\usepackage{index}
. . .
\makeindex
\newindex{secondname}{sidx}{sind}{Second Index}
```

⚠ WINDOWS *For WINDOWS, replace the two ";" characters with "&".*

When creating the HTML index, "`_html`" is automatically appended to the index filenames.

Use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

If the `latexmk` option is selected for lwarp, *latexmk* will compile the document but will *not* compile the indexes. **`lwarpmk printindex`** and **`lwarpmk htmlindex`** will still be required.

9.6.16 Indexing with splitidx

lwarp is told how to use *splitindex* using the `PrintIndexCmd` and `HTMLIndexCmd` options. The file `lwarp.ist` is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

If the `latexmk` option is selected for lwarp, *latexmk* will compile the document but will *not* compile the indexes. **`lwarpmk printindex`** and **`lwarpmk htmlindex`** will still be required.

⚠ `\thepage` When using `\AtWriteToIndex` or `\AtNextWriteToIndex`, the user must not refer to

\thepage during HTML output, as the concept of a page number is meaningless. Instead, do

```
\addtocounter{LWR@autoindex}{1}
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}
```

where the \index-like action occurs, and then refer to \arabic{LWR@autoindex} instead of \thepage where the reference should occur.

See section 504.17 in the lwarp-patch-memoir package for the \@@wrspindexhyp macro as an example.

For multiple indexes using *makeindex* and splitidx:

```
\usepackage[
  makeindex, latexmk,
  PrintIndexCmd={
    splitindex <projectname> -- -s lwarp.ist
  },
  HTMLIndexCmd={
    splitindex <projectname>_html -- -s lwarp.ist
  }
]{lwarp}
\usepackage{splitidx}
. . .
\makeindex
\newindex[Second Index]{secondname}
```

When creating the HTML index, "_html" is automatically appended to each of the names.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

For multiple indexes using *xindy* and splitidx:

```
\usepackage[
  xindy, latexmk,
  PrintIndexCmd={
    splitindex -m xindy <projectname> -- -M lwarp.xdy
      -L english -C utf8                          <optional>
  },
  HTMLIndexCmd={
    splitindex -m xindy <projectname>_html -- -M lwarp.xdy
      -L english -C utf8                          <optional>
  }
]{lwarp}
\usepackage{splitidx}
. . .
\makeindex
\newindex[Second Index]{secondname}
```

When creating the HTML index, "`_html`" is automatically appended to each of the names.

Use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

9.6.17 Indexing with imakeidx

Due to the number of methods which may be used to process multiple indexes, the options for style file and *xindy* language and codepage must be specified in one of several different ways. These are described in detail later in this section, but are summarized here.

If shell escape is used, imakeidx will automatically compile the indexes by itself. Options specifying a custom style file and *xindy* language and codepage must be specified for each `\makeindex` command using its `options=` option, which must include lwarp's special `lwarp.ist` or `lwarp.xdy` file, or a file based on them. If using a custom indexing style file, see sections 9.6.19 and 9.6.20. The `splitindex` option is also available of shell escape is used, in which case the splitidx package and *splitindex* program will also be used.

If shell escape is not possible, *latexmk* may be used to automatically compile the indexes. The style, language, and codepage options are specified with lwarp's `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options. These are passed to *latexmk* by *lwarpmk*'s **`lwarpmk printindex`** and **`lwarpmk htmlindex`** commands.

Where shell escape and *latexmk* are not possible, *lwarpmk* may be used to manually compile the indexes. lwarp's `PrintIndexCmd` and `HTMLIndexCmd` options are used.

For a single or multiple indexes using *makeindex* and imakeidx:

The index style `lwarp.ist` is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```
\usepackage[makeindex,latexmk] {lwarp}
\usepackage[makeindex]{imakeidx}
. . .
\makeindex[options={-s lwarp.ist}]
\makeindex[name=secondname,options={-s lwarp.ist}]
```

imakeidx will automatically compile the indexes. Shell escape is not required while using *makeindex*. `latexmk` may be specified, and if so it will be used for **`lwarpmk print`** and **`lwarpmk html`**, but *imakeidx* will actually create the indexes.

For a single or multiple indexes using *makeindex* and *splitindex* with imakeidx:

The index style `lwarp.ist` is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```
\usepackage[makeindex,latexmk] {lwarp}
\usepackage[makeindex,splitindex]{imakeidx}
. . .
\makeindex[options={-s lwarp.ist}]
\makeindex[name=secondname,options={-s lwarp.ist}]
```

⚠ enable shell escape

Shell escape is required while using *splitindex*. For the first compile, use

Enter ⇒ **`pdflatex --shell-escape projectname.tex`**

Enter ⇒ **`pdflatex --enable-write18 projectname.tex`** **(MiKTeX)**

or similar with *xelatex* or *lualatex*. lwarp will remember that shell escape was used.

imakeidx will automatically execute *splitindex*, and will also use *makeindex* to compile the indexes.

`latexmk` may be specified, and if so it will be used for **`lwarpmk print`** and **`lwarpmk html`**, but *imakeidx* will actually create the indexes.

For multiple indexes using *xindy* and imakeidx, using shell escape:

Options may be given to imakeidx's `\makeindex` command. The style file `lwarp.xdy` is automatically used for HTML output, and is not necessary for print output since the output will be similar. If language or codepage must be set, they should be specified as options for `\makeindex`, since imakeidx will process the indexes.

```
\usepackage[xindy,latexmk] {lwarp}
\usepackage[xindy,splitindex]{imakeidx}
. . .
\makeindex[
  options={ -M lwarp.xdy -L english -c utf8 }
]
\makeindex[
  name=secondname,
  options={ -M lwarp.xdy -L english -c utf8 }
]
```

⚠ enable shell escape

For the first compile, use

Enter ⇒ **pdflatex --shell-escape projectname.tex**

Enter ⇒ **pdflatex --enable-write18 projectname.tex** **(MiKTeX)**

or similar with *xelatex* or *lualatex*. lwarp will remember that shell escape was used.

imakeidx will automatically execute *splitindex* if selected, and will also use *xindy* to compile the indexes.

If selected, *latexmk* will automatically recompile the entire document as necessary.

For indexes using *xindy* and *imakeidx*, without shell escape, but *with* *latexmk*:

lwarp's options are used, and are passed to *latexmk*.

```
\usepackage[
  xindy,
  xindyLanguage=english,                    <optional>
  xindyCodepage=utf8,                       <optional>
  latexmk,
]{lwarp}
\usepackage[xindy]{imakeidx}
. . .
\makeindex
\makeindex[name=secondname]
```

latexmk will create the indexes automatically when **lwarpmk print** and **lwarpmk html** are executed.

For indexes using *xindy* and *imakeidx*, without shell escape, and *without* *latexmk*:

lwarpmk must be told how to create the indexes:

```
\usepackage[
  xindy,
  PrintIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname.idx
  },
  HTMLIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>_html.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname_html.idx
  }
]{lwarp}
\usepackage[xindy]{imakeidx}
. . .
\makeindex
\makeindex[name=secondname]
```

⚠ WINDOWS *For WINDOWS, replace the two ";" characters with "&".*

`<projectname>` is the `\jobname`: if compiling "`name.tex`", use the filenames `name.idx` and `name_html.idx`.

Use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

9.6.18 Indexes with memoir

For a single index with memoir and makeindex:

```
\documentclass{memoir}
\usepackage[makeindex,latexmk]{lwarp}
. . .
\makeindex
```

The usual `.idx` and `.ind` files will be used, along with the `lwarp.ist` style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For multiple indexes with memoir and makeindex, using *latexmk*:

lwarp's options are used, and are passed to *latexmk*.

```
\documentclass{memoir}
\usepackage[makeindex,latexmk]{lwarp}
...
\makeindex
\makeindex[secondname]
```

lwarpmk will use *latexmk* to create the indexes automatically when the user executes **`lwarpmk print`** and **`lwarpmk html`**.

For multiple indexes with memoir and makeindex, *without* latexmk:

lwarpmk must be told how to create the indexes:

```
\documentclass{memoir}
\usepackage[
  makeindex,
  PrintIndexCmd={
    makeindex -s lwarp.ist <projectname>.idx ;
    makeindex -s lwarp.ist secondname.idx
  },
  HTMLIndexCmd={
    makeindex -s lwarp.ist <projectname>_html.idx ;
    makeindex -s lwarp.ist secondname_html.idx
  }
]{lwarp}
...
\makeindex
\makeindex[secondname]
```

⚠ WINDOWS *For WINDOWS, replace the two ";" characters with "&".*

`<projectname>` is the `\jobname`: if compiling "`name.tex`", use the filenames `name.idx` and `name_html.idx`.

Use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For a single index with memoir and xindy:

```
\documentclass{memoir}
\usepackage[
    xindy,
    xindyLanguage=english,                    <optional>
    xindyCodepage=utf8,                       <optional>
    latexmk                                   <optional>
]{lwarp}
. . .
\xindyindex
\makeindex
```

The usual `.idx` and `.ind` files will be used, along with the `lwarp.xdy` style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For multiple indexes with memoir and xindy, using latexmk:

lwarp's options are used, and are passed to *latexmk*.

```
\documentclass{memoir}
\usepackage[
    xindy,
    xindyLanguage=english,                    <optional>
    xindyCodepage=utf8,                       <optional>
    latexmk
]{lwarp}
. . .
\xindyindex
\makeindex
\makeindex[secondname]
```

lwarpmk will use *latexmk* to create the indexes automatically.

For multiple indexes with memoir and xindy, *without* latexmk:

lwarpmk must be told how to create the indexes:

```
\documentclass{memoir}
\usepackage[
  xindy,
  PrintIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname.idx
  },
  HTMLIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>_html.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname_html.idx
  }
]{lwarp}
...
\xindyindex
\makeindex
\makeindex[secondname]
```

⚠ WINDOWS *For WINDOWS, replace the four ";" characters with "&".*

`<projectname>` is the `\jobname`: if compiling "`name.tex`", use the filenames `name.idx` and `name_html.idx`.

Use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

9.6.19 Using a custom *makeindex* style file

Prog makeindex
File lwarp.ist

When using *makeindex*, *lwarpmk* uses the file `lwarp.ist` to process the index. This file is over-written by lwarp whenever a print version of the document is processed.

To use a custom *makeindex* style file:

1. Copy `lwarp.ist` to a new filename such as `projectname.ist`
2. Make changes to `projectname.ist`. Keep the lines which refer to `\hyperindexref`. These lines creates the hyperlinks for the HTML index. During print output `\hyperindexref` becomes a null function.

Opt makeindexStyle

3. In the document source use the `makeindexStyle` option for lwarp:

```
\usepackage[
    ... other options ...
```

```
    \textred{makeindexStyle=projectname.ist},
]{lwarp}
```

Likewise, refer to the custom style file if using `\PrintIndexCmd`, `\HTMLIndexCmd`, or `\LatexmkIndexCmd`.

4. Recompile the print version, which causes lwarp to rewrite the `lwarpmk.conf` configuration file. This tells *lwarpmk* to use the custom `projectname.ist` file instead of `lwarp.ist`.

9.6.20 Using a custom *xindy* style file

Prog xindy
File lwarp.xdy

When using *xindy*, *lwarpmk* uses the file `lwarp.xdy` to process the index. This file is over-written by lwarp whenever a print version of the document is processed.

To use a custom *xindy* style file:

1. Copy `lwarp.xdy` to a new filename such as `projectname.xdy`
2. Make changes to `projectname.xdy`.

   Keep the lines which refer to `\hyperindexref`:

   ```
   (define-attributes (("hyperindexref")))
   (markup-locref :open "\hyperindexref{" :close "}")
   ...
   (markup-locref :open "\textit{\hyperindexref{" :close "}}" :attr "textit")
   ```

   These lines create the hyperlinks for the HTML index. During print output `\hyperindexref` becomes a null function.

   To create custom styles, refer to the lines for `\textbf` and `\textit`.

Opt xindyStyle

3. In the document source use the `xindyStyle` option for lwarp:

   ```
   \usepackage[
       ... other options ...
       \textred{xindyStyle=projectname.xdy},
   ]{lwarp}
   ```

   Likewise, refer to the custom style file if using `\PrintIndexCmd`, `\HTMLIndexCmd`, or `\LatexmkIndexCmd`.

4. Recompile the print version, which causes lwarp to rewrite the `lwarpmk.conf` configuration file. This tells *lwarpmk* to use the custom `projectname.xdy` file instead of `lwarp.xdy`.

9.6.21 Additional indexing limitations

⚠ xindy with hyperref

xindy and hyperref may not work well together for print output with “see”, “see also”, reference ranges, or stylized index references. It may be necessary to turn off hyper-referencing for indexes:

```
\usepackage[hyperindex=false]{hyperref}
```

⚠ empty index

If an HTML index is empty, it may be necessary to add the following before lwarp is loaded:

```
\usepackage{morewrites}
\morewritessetup{allocate=10}
. . .
\usepackage{lwarp}
```

makeindex custom display styles

When using *makeindex*, custom display styles are possible:

```
\begin{warpprint}
\newcommand{\notesstyle}[1]{#1nn}
\end{warpprint}

\begin{warpHTML}
\makeatletter
\newcommand{\notesstyle}[1]{\LWR@doindexentry{#1} notes }
\makeatother
\end{warpHTML}
. . .
A sentence.\index{key|notesstyle}
```

xindy custom display styles

For custom styles with *xindy*, see `lwarp.xdy` for `\textbf` and `\textit` as examples.

9.6.22 Index positions, TOC, tocbibind

placement and TOC options

An index may be placed inline with other HTML text, or on its own HTML page:

Pkg makeidx **Inline, with a manual TOC entry:**

A commonly-used method to introduce an index in a LaTeX document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\printindex
```

Pkg makeidx **On its own HTML page, with a manual TOC entry:**

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex
```

Pkg tocbibind **Inline, with an automatic TOC entry:**

The tocbibind package may be used to automatically place an entry in the TOC.

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex
```

Pkg tocbibind **On its own HTML page, with an automatic TOC entry:**

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex
```

Opt [tocbibind] numindex
numbered index section

Use the tocbibind `numindex` option to generate a numbered index. Without this option, the index heading has no number.

Other packages, such as imakeidx, may also have options for including the index in the Table of Contents.

Pkg tocloft
⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

9.7 Math

9.7.1 Math in section names

⚠ math in section names

If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring`:

```
\section{A math \texorpdfstring{$1+2=3$}{text description} name}
```

9.7.2 Rendering tradeoffs

Math rendering

Math may be rendered as SVG graphics or using the MathJax JavaScript display engine.

SVG files

Rendering math as images creates a new SVG file for each expression, except that an MD5 hash is used to combine identical duplicates of the same inline math expression into a single file, which must be converted to SVG only once. Display math is still handled as individual files, since it may contain labels or references which are likely to change.

SVG inline

The SVG images are currently stored separately, but they could be encoded in-line directly into the HTML document. This may reduce the number of files and potentially speed loading the images, but slows the display of the rest of the document before the images are loaded.

PNG files

Others LaTeX-to-HTML converters have used PNG files, sometimes pre-scaled for print resolution but displayed on-screen at a scaled down size. This allows high-quality print output at the expense of larger files, but SVG files are the preferred approach for scalable graphics.

MathML

Conversion to MathML might be a better approach, among other things allowing a more compact representation of math than SVG drawings. Problems with MathML include limited browser support and some issues with the fine control of the appearance of the result. Also see section 11 regarding EPUB output with MathJax.

9.7.3 SVG option

SVG math option

For SVG math, math is rendered as usual by LaTeX into the initial PDF file using the current font[14], then is captured from the PDF and converted to SVG graphics via a number of utility programs. The SVG format is a scalable-vector web format, so math may be typeset by LaTeX with its fine control and precision, then displayed or printed at any size, depending on (sometimes broken) browser support. An HTML `alt` attribute carries the LaTeX code which generated the math, allowing copy/paste of the LaTeX math expression into other documents.

SVG image font size

For the `lateximage` environment, the size of the math and text used in the SVG image may be adjusted by setting `\LateximageFontSizeName` to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline SVG math, font size is instead controlled by `\LateximageFontScale`, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

SVG math copy/paste

For SVG math, text copy/paste from the HTML `<alt>` tags lists the equation number or tag for single equations, along with the LaTeX code for the math expression. For $\mathcal{AMS}$ environments with multiple numbers in the same environment, only the first and last is copy/pasted, as a range. No tags are listed inside a starred $\mathcal{AMS}$ environment, although the `\tag` macro will still appear inside the LaTeX math expression.

⚠ SVG math in TeX boxes

SVG math does not work inside TeX boxes, since a `\newpage` is required before and after each image.

9.7.4 MathJax option

MathJax math option

Prog MathJax

The popular MathJax alternative (`mathjax.org`) may be used to display math.

When MathJax is enabled, math is rendered twice:

1. As regular LaTeX PDF output placed inside an HTML comment, allowing equation numbering and cross referencing to be almost entirely under the control of LaTeX, and

[14] See section 491 regarding fonts and fractions.

2. As detokenized printed LaTeX commands placed directly into the HTML output for interpretation by the MathJax display scripts. An additional script is used to pre-set the equation number format and value according to the current LaTeX values, and the MathJax cross-referencing system is ignored in favor of the LaTeX internal system, seamlessly integrating with the rest of the LaTeX code.

9.7.5 Customizing MathJax

MathJax does not have preexisting support every possible math function. Additional MathJax function definitions may be defined. These will be declared at the start of each HTML page, and thus will have a global effect.

Examples:

```
\CustomizeMathJax{
    \newcommand{\expval}[1]{\langle#1\rangle}
    \newcommand{\abs}[1]{\lvert#1\rvert}
}
\CustomizeMathJax{\newcommand{\arsinh}{\text{arsinh}}}
\CustomizeMathJax{\newcommand{\arcosh}{\text{arcosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
```

9.7.6 MathJax limitations

MathJax limitations
Prog MathJax

Limitations when using MathJax include:

subequations

- MathJax itself does not support subequations. This may be improved by parsing the LaTeX math expression to manually insert tags, but this has not yet been done.

footnotes in math

- Footnotes inside equations are not yet supported while using MathJax.

lateximage

- Math appearing inside a lateximage, and therefore also inside a Ti*k*z or `picture` environment, is rendered as SVG math even if MathJax is used in the rest of the document.

siunitx

⚠ siunitx inside an equation

- Usage of siunitx inside a math equation is supported via a third-party MathJax extension. While inside a math expression, do not use `\SI` or `\si` inside `\text`, where it will be rendered as normal text.

  https://github.com/burnpanck/MathJax-siunitx

  Also see section 9.7.11.

tabbing

- A `tabbing` environment is emulated using an HTML <pre>.While MathJax is enabled inside `tabbing`, the browser may not correctly render the horizontal alignment of the math and text following after on the same line.

⚠ other macros and packages

- Other math-related macros and packages are not supported by MathJax, including `\ensuremath` and bigdelim, along with occasionally-used macros such as `\relax`. lwarp emulates footnotes, units, and nicefrac for MathJax.

9.7.7 Catcode changes

preamble macros with math

The math shift character $ is not set for HTML output until after the preamble. Macros defined in the preamble which contain $ must be enclosed between \StartDefiningMath and \StopDefiningMath to temporarily change to the HTML meaning of $:

```
\StartDefiningMath
\newcommand{. . . }
\StopDefiningMath
```

As an alternative, use \(and \) instead of $, in which case \StartDefiningMath and \StopDefiningMath are not necessary.

If a package defines macros using $, it may be nessary to use \StartDefiningMath and \StopDefiningMath before and after loading the package.

9.7.8 Complicated inline math objects

\inlinemathnormal
\inlinemathother

changing contents

complicated alt tag

An inline math expression is usually converted to a reusable hashed SVG math image, or a MathJax expression. The hash or expression depends on the contents of the math expression. In most cases this math expression is static, such as $x+1$, so the image can be reused for multiples instances of the same expression. In some cases, the math expression includes a counter or other object which may change between uses. Another problem is complicated contents which do not expand well in an alt tag. The macro \inlinemathother may be used before a dynamic math expression, and \inlinemathnormal after. Doing so tells lwarp to use an unhashed SVG math image, even if MathJax is in use. See section 44.

9.7.9 Complicated display math objects

\displaymathnormal

By default, or when selecting \displaymathnormal, MATHJAX math display environments print their contents as text into HTML, and SVG display math environments render their contents as SVG images and use their contents as the alt tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Ti*k*z pictures, compilation will fail.

\displaymathother
MathJax unsupported
complicated alt tag

When selecting \displaymathother, it is assumed that the contents are more complicated than "pure" math. An example is an elaborate Ti*k*z picture, which will not render in MATHJAX and will not make sense as an HTML alt tag. In this mode, MATHJAX is turned off, math display environments become SVG images, even if MATHJAX is selected, and the HTML alt tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Ti*k*z pictures are more likely to compile successfully.

9.7.10 ntheorem package

Pkg ntheorem

⚠ Font control

This conversion is not total. Font control is via CSS, and the custom LaTeX font settings are ignored.

⚠ Equation numbering

ntheorem has a bug with equation numbering in $\mathcal{AMS}$ environmentswhen the option `thref` is used. lwarp does not share this bug, so equations with `\split`, etc, are numbered correctly with lwarp's HTML output, but not with the print output. It is recommended to use cleveref instead of ntheorem's `thref` option.

9.7.11 siunitx package

Pkg siunitx

fractions

Due to *pdftotext* limitations, fraction output is replaced by symbol output for `per-mode` and `quotient-mode`.

⚠ math mode required

Some units will require that the expression be placed inside math mode.

NOTE: As of this writing, the siunitx extension for MathJax is not currently hosted at any public CDN, thus siunitx is not usable with MathJax unless a local copy of this extension is created first.

⚠ tabular

Tabular `S` columns are rendered as simple `c` columns, and tabular `s` columns are not supported. These may be replaced by `c` columns with each cell contained in `\num` or `\si`.

9.7.12 units and nicefrac packages

Pkg units

Pkg nicefrac

units and nicefrac work with lwarp, but MathJax does not have an extension for units or nicefrac. These packages do work with lwarp's option `svgmath`.

9.7.13 newtxmath package

Pkg newtxmath

⚠ loading sequence

The proper load order is:

```
...
\usepackage{lwarp}
...
\usepackage{amsthm}
\usepackage{newtxmath}
...
```

9.8 Graphics

Pkg graphics

Pkg graphicx

⚠ scale

Avoid using the `\includegraphics` `scale` option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

`\includegraphics` file formats

For `\includegraphics` with `.pdf` or `.eps` files, the user must provide a `.pdf` or `.eps`

image file for use in print mode, and also a .svg, .png, or .jpg version of the same image for use in HTML.

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, lwarp will automatically choose the .pdf or .eps format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a .pdf or .eps image is referred to with its file extension, the extension will be changed to .svg for HTML:

```
\includegraphics{filename.pdf} % uses .svg in html
\includegraphics{filename.eps} % uses .svg in html
```

Prog pdftocairo
PDF to SVG

To convert a PDF image to SVG, use the utility *pdftocairo*:

Enter ⇒ **pdftocairo -svg filename.pdf**

Prog lwarpmk pdftosvg

For a large number of images, use *lwarpmk*:

Enter ⇒ **lwarpmk pdftosvg *.pdf** **(or a list of filenames)**

Prog lwarpmk epstopdf
Prog epstopdf
epstopdf package

For EPS images converted to PDF using the package epstopdf, use

Enter ⇒ **lwarpmk pdftosvg *.PDF**

to convert to SVG images.

DVI latex

When using DVI *latex*, it is necessary to convert EPS to PDF and then to SVG:

Enter ⇒ **lwarpmk epstopdf *.eps** **(or a list of filenames)**

Enter ⇒ **lwarpmk pdftosvg *.pdf** **(or a list of filenames)**

PNG and JPG

For PNG or JPGwhile using *pdflatex*, *lualatex*, or *xelatex*, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

GIF

GIF files may be used for HTML, but another format must also be provided for print output.

file extension priorities

If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

⚠ graphics vs. graphicx

If using the older graphics syntax, use both optional arguments for \includegraphics. A single optional parameter is interpreted as the newer graphicx syntax. Note that viewports are not supported by lwarp — the entire image will be shown.

⚠ viewport

⚠ viewport units

For \includegraphics, avoid px and % units for width and height, or enclose them inside warpHTML environments. For font-proportional image sizes, use ex or em. For fixed-sized images, use cm, mm, in, pt, or pc. Use the keys width=.5\linewidth, or similar for \textwidth or \textheight to give fixed-sized images proportional to a 6 by 9 inch text area. Do not use the scale option, since it is not well supported by HTML browsers.

options — `\includegraphics` accepts `width` and `height`, `origin`, `rotate` and `scale`, plus new `class` and `alt` keys.

HTML class — With HTML output, `\includegraphics` accepts an optional `class=xyz` keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

HTML `alt` tags — Likewise, the `\includegraphics` `alt` key adds an HTML `alt` tag to an image, and is ignored for print output. If not assigned, each image is given an `alt` tag of "`(image)`".

`\rotatebox` — `\rotatebox` accepts the optional `origin` key.

⚠ browser support — `\rotatebox`, `\scalebox`, and `\reflectbox` depend on modern browser support. The css3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike LaTeX, so expect some ugly results for scaling and rotating.

9.8.1 tikz package

Pkg tikz

⚠ displaymath and matrices — If using display math with `tikzpicture` or `\tikz`, along with matrices with the `&` character, the document must be modified as follows:

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of `&` in the tikz expression must be replaced with `\&`.

9.8.2 grffile package

Pkg grffile

⚠ matching PDF and SVG — grffile is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

9.8.3 color package

Pkg color — color is superceded by xcolor, and lwarp requires several of the features of xcolor. When color is requested, xcolor is loaded as well.

9.8.4 xcolor package

Pkg xcolor

`\colorboxBlock` and `\fcolorboxBlock` — `\colorboxBlock` and `\fcolorboxBlock` are provided for increased HTML compatibility, and they are identical to `\colorbox` and `\fcolorbox` in print mode. In HTML mode they place their contents into a `<div>` instead of a `<span>`. These `<div>`s are set to `display: inline-block` so adjacent `\colorboxBlocks` appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for `\colorboxBlock` and `\fcolorboxBlock` are created by lwarp's core if xcolor is loaded.

background: none

`\fcolorbox` and `\fcolorboxBlock` allow a background color of `none`, in which case only the frame is drawn, which can be useful for HTML.

color support

Color definitions, models, and mixing are fully supported without any changes required.

colored tables

`\rowcolors` is supported, except that the optional argument is ignored so far.

colored text and boxes

`\textcolor`, `\colorbox`, and `\fcolorbox` are supported.

`\color` and `\pagecolor`

`\color` and `\pagecolor` are ignored. Use CSS or `\textcolor` where possible.

9.8.5 epstopdf package

Pkg epstopdf

⚠ convert to `.svg`

Images with an `.eps` extension will be converted to `.pdf`. The HTML output uses the `.svg` version, so use

Enter ⇒ **`lwarpmk pdftosvg <listofPDFfiles>`**

to generate `.svg` versions.

9.8.6 pstricks package

Pkg pstricks

⚠ use `pspicture`

All pstricks content should be contained inside a `pspicture` environment.

9.8.7 pdftricks package

Pkg pdftricks

⚠ convert image files

The pdftricks image files `<jobname>-fig*.pdf` must be converted to `.svg`, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

Enter ⇒ **`lwarpmk pdftosvg <jobname>-fig*.pdf`**

9.8.8 psfrag package

Pkg psfrag

⚠ use `psfrags`

The `psfrags` environment is modified to use `lateximage` to encapsulate the image. Always use a `psfrags` environment to contain any local `\psfrag` macros and the associated `\includegraphics` or `\epsfig` calls. Outside of a `psfrags` environment, psfrags adjustments will not be seen by lwarp.

⚠ Tip: Use a mono-spaced font for the tags in the EPS file.

9.8.9 pstool package

Pkg pstool

\graphicspath is ignored, and the file directory must be stated.

⚠ path and filename

The filename must not have a file extension.

Use

Enter ⇒ **lwarpmk html**

followed by

Enter ⇒ **lwarpmk limages**

.

9.8.10 asymptote package

Pkg asymptote

To compile:

```
pdflatex project.tex
asy project-*.asy
pdflatex project.tex

lwarpmk print
asy project-*.asy
lwarpmk print1
lwarpmk print1

lwarpmk html
asy project_html-*.asy
lwarpmk html1
lwarpmk html1
lwarpmk limages
```

9.8.11 overpic package

Pkg overpic

⚠ scaling

The macros \overpicfontsize and \overpicfontskip are used during HTML generation. These are sent to \fontsize to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the overpic and Overpic environments.

9.9 Tabbing

The tabbing environment works, except that SVG math and lateximages do not yet work inside the environment.

⚠ math in tabbing

If math is used inside tabbing, place tabbing inside a lateximage environment, which

will render the entire environment as a single SVG image.

9.10 Tabular

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, * column specifiers, siunitx S columns, or the packages multirow, longtable, supertabular, or xtab.

Defining macros and environments:

⚠ Misplaced alignment tab character &

- When defining environments or macros which include `tabular` and instances of the & character, it may be necessary to make & active before the environment or macro is defined, then restore & to its default catcode after, using the following commands. These are are ignored in print mode.

```
\StartDefiningTabulars
<define macros or environments using tabular and & here>
\StopDefiningTabulars
```

⚠ floatrow

This includes before and after defining any macro which used `\ttabbox` from floatrow.

⚠ `tabular` inside another environment

- When creating a new environment which contains a `tabular` environment, lwarp's emulation of the tabular does not automatically resume when the containing enviroment ends, resulting in corrupted HTML rows. To fix this, use `\ResumeTabular` as follows. This is ignored in print mode.

```
\StartDefiningTabulars  % because  &  is  used  in  a
definition
\newenvironment{outerenvironment}
{
\tabular{cc}
left & right \\
}
{
\TabularMacro\ResumeTabular
left & right \\
\endtabular
}
\StopDefiningTabulars
```

Cell contents:

⚠ `\multirow`

- For multirow, insert `\mrowcell` into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output.

```
. . . &  \multirow{2}{.5in}{text}  & . . .
. . . &  \mrowcell                 & . . .
```

`vposn`

Note that recent versions of multirow include a new optional `vposn` argument.

- The multirow documentation regarding colored cells recommends using a negative number of rows. This will not work with lwarp, so `\warpprintonly` and `\warpHTMLonly` must be used to make versions for print and HTML.

- See section 319.2 for \multicolumrow.

⚠ \multicolumn & \multirow

lwarp does not support directly combining \multicolumn and \multirow. Use \multicolumnrow instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}
```

The two arguments for \multicolumn come first, followed by the five arguments for \multirow, many of which are optional, followed by the contents.

⚠ skipped cells

As per \multirow, skipped cells to the right of the \multicolumnrow statement are not included in the source code on the same line. On the following

⚠ empty cells

lines, \mcolrowcell must be used for each cell of each column and each row to be skipped:

```
... &  \multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}  & ...
... &  \mcolrowcell          &          \mcolrowcell   & ...
... &  \mcolrowcell          &          \mcolrowcell   & ...
```

vposn

Note that recent versions of multirow include a new optional vposn argument.

⚠ macro in a table

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use \TabularMacro just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \\
```

Column specifiers:

⚠ * column specification

- * in a column specification is not used (so far). Repeat the column type the correct number of times.

@ and !

- Only one each of @ and ! is used at each column, and they are used in that order.

\multirow

- In \multirow cells, the print version may have extra instances of <, >, @, and ! cells on the second and later rows in the \multirow which do not appear in the HTML version.

⚠ \newcolumntype

- \newcolumntype is ignored; unknown column types are set to l.

Rules:

- Doubled \hlines, \midrules, and vertical rules are supported.

vertical rules

- Vertical rules next to either side of an @ or ! column are displayed on both sides of the column.

width and trim

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with @ or ! columns, and full-width rules ignore trim.

full-width rules

- \toprule, \midrule, \bottomrule, and \hline ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

combined rules

- If you wish to use \cmidrule followed by \bottomrule, it may be necessary to use:

```
\cmidrule{2-3} \\[-2ex]
\bottomrule
```

The optional -2ex is ignored in HTML, but improves the visual formatting in the print output.

⚠ \warpprintonly
⚠ Misplaced \noalign

- For \toprule and \bottomrule, when combined with a warpprint or warpHTML environment, if a "Misplaced \noalign" error occurs, change

  ```
  This & That \endhead
  ```

  to

  ```
  \warpprintonly{This & That \endhead}
  ```

  and likewise with the other \end headings. Keep the \endfirsthead row unchanged, as it is still relevent to HTML output.

colortbl:

⚠ row/cell color

Only use \rowcolor and \cellcolor at the start of a row, in that order.

colortbl ignores the overhang arguments.

Other:

- tabularx ignores the width, but X columns do produce paragraph columns or multicolumns.

longtable headings

- For longtable, place headings and footings which do not apply to HTML inside \warpprintonly{}.

⚠ S columns

- For S columns (from the siunitx package), while producing print output, anything non-numeric must be placed inside { } braces, including commands such as \multirow. While producing HTML output, though, anything placed inside braces is not seen by lwarp's tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

  ```
  \warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
  \warpHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
  ```

9.10.1 longtable package

Pkg longtable

Use one of either \endhead or \endfirsthead for both print and HTML, and use a \warpprintonly macro to disable the other head phrase, and also the \endfoot and \endfirstfoot phrases. (See section 9.10.2 if using threeparttablex.)

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{         % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  [ <lastfoot macros> ] \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{
  [ <lastfoot macros> ]   % HTML last footer, without \endfoot
                                                % or \endlastfoot.
}
\end{longtable}
```

⚠ Misplaced \noalign

Use the \warpprintonly macro instead of the warpprint environment. Doing so helps avoid "Misplaced \noalign." when using \begin{warpprint}.

⚠ \kill \kill is ignored, place a \kill line inside

```
\begin{warpprint} . . .  \end{warpprint}
```

or place it inside \warpprintonly.

⚠ lateximage longtable is not supported inside a lateximage.

9.10.2 threeparttablex package

Pkg threeparttablex threeparttablex is used with longtable and booktabs as follows:

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{          % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  \bottomrule \insertTableNotes \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{   % HTML last footer
  \bottomrule
  \UseMinipageWidths     % optional
  \insertTableNotes
  \endlastfoot
}
\end{longtable}
```

table width The table notes are created using a \multicolumn. By default the width is not specified to the browser, so long table notes can cause the table to be spread out horizontally. For HTML output, lwarp guesses the width of the table depending on the number of columns, then restricts its guess to a min/max range. To use this guess for the width of the table notes, use \UseMinipageWidths before \insertTableNotes. The width is then specified, and in many cases the result is an improvement in overall table layout.

9.10.3 supertabular and xtab packages

Pkg supertabular For \tablefirsthead, etc., enclose them as follows:

Pkg xtab

⚠ Misplaced alignment tab character &

```
\StartDefiningTabulars
\tablefirsthead
. . .
\StopDefiningTabulars
```

See section 9.10.

⚠ lateximage supertabular and xtab are not supported inside a lateximage.

9.10.4 bigdelim package

Pkg bigdelim

⚠ use \mrowcell

\ldelim and \rdelim use \multirow, so \mrowcell must be used in the proper number of empty cells in the same column below \ldelim or \rdelim, but not in cells which are above or below the delimiter:

```
\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\{}{2}{.25in}[left ] & c & d \\
\mrowcell & e & f \\
<empty> & g & h \\
\end{tabular}
```

<> a b

left { c d
e f

<> g h

9.11 Floats

9.11.1 Float contents alignment

⚠ figure & table alignment

\centering, etc. are honored in a figure or table if they are the first command inside the float:

```
\begin{table*}
\centering
\caption{A Table}
. . .
```

9.11.2 float, trivfloat, and/or algorithmicx together

Pkg float

Pkg trivfloat

Pkg algorithmicx

If using \newfloat, trivfloat, and/or algorithmicx together, see section 460.1.

9.11.3 caption and subcaption packages

⚠ package conflicts

Pkg caption

Pkg subcaption

⚠ options

To pass options to caption, select the options before loading lwarp:

```
\documentclass{article}
. . .
\PassOptionsToPackage{options_list}{caption}
. . .
\usepackage{lwarp}
. . .
\usepackage{caption}
```

⚠ numbering

To ensure proper float numbering, set caption positions such as:

```
\captionsetup[figure]{position=bottom}
\captionsetup[subfigure]{position=bottom}
\captionsetup[table]{position=top}
\captionsetup[subtable]{position=top}
```

Similarly for longtable. These positions depend on where the user places the `\caption` command inside each float.

9.11.4 subfig package

Pkg subfig

⚠ lof/lotdepth

At present, the package options for `lofdepth` and `lotdepth` are not working. These counters must be set separately after the package has been loaded.

In the document source, use `\hfill` and `\hspace*` subfig>inline between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

9.11.5 floatrow package

Pkg floatrow

Use `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros using `\ttabbox` with a tabular inside. See section 9.10.

⚠ Misplaced alignment tab character &

⚠ subfig package

When combined with the subfig package, while inside a `subfloatrow` `\ffigbox` and `\ttabbox` must have the caption in the first of the two of the mandatory arguments.

⚠ \FBwidth, \FBheight

The emulation of floatrow does not support `\FBwidth` or `\FBheight`. These values are pre-set to `.3\linewidth` and `2in`. Possible solutions include:

- Use fixed lengths. lwarp will scale the HTML lengths appropriately.
- Use `warpprint` and `warpHTML` environments to select appropriate values for each case.
- Inside a `warpHTML` environment, manually change `\FBwidth` or `\FBheight` before the `\ffigbox` or `\ttabbox`. Use `\FBwidth` or `\FBheight` normally afterwards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

9.11.6 keyfloat package

Pkg keyfloat

⚠ keywrap

If placing a `\keyfig[H]` inside a `keywrap`, use an absolute width for `\keyfig`, instead of `lw`-proportional widths. (The `[H]` option forces the use of a minipage, which internally adjusts for a virtual 6-inch wide minipage, which then corrupts the `lw` option.)

9.12 KOMA-SCRIPT classes

Cls komascript

Many features are ignored during the HTML conversion. The goal is source-level compatibility.

\titlehead, \subject, \captionformat, \figureformat, and \tableformat are not yet emulated.

⚠ Not fully tested! Please send bug reports!

Some features have not yet been tested. Please contact the author with any bug reports.

9.13 MEMOIR class

Cls memoir

While emulating memoir, lwarp pre-loads a number of packages (section 504.1). This can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading lwarp:

⚠ options clash

```
\documentclass{memoir}
. . .
\PassOptionsToPackage{options_list}{package_name}
. . .
\usepackage{lwarp}
. . .
\usepackage{package_name}
```

⚠ version numbers

memoir emulates a number of packages, and declares a version date for each which often does not match the date of the corresponding freestanding package. This can cause warnings about incorrect version numbers. Since lwarp is intended to support the freestanding packages, which are often newer than the date declared by memoir, it is hoped that memoir will update and change its emulated version numbers to match.

\verbfootnote is not supported.

\newfootnoteseries, etc. are not supported.

lwarp loads pagenote to perform memoir's pagenote functions, but there are minor differences in \pagenotesubhead and related macros.

Poem numbering is not supported.

The verbatim environment does not yet support the memoir enhancements. It is currently recommended to load and use fancyvrb instead.

The memoir glossary system is not yet supported by *lwarpmk*. The glossaries package may be used instead, but does require the glossary entries be changed from the memoir syntax to the glossaries syntax.

9.14 International languages

⚠ section and file names

If using *pdflatex* with the setting \booltrue{FileSectionNames}, non-ASCII text in

section names can result in corrupted HTML file names. *pdflatex* may be used if setting `\boolfalse{FileSectionNames}`, in which case HTML file numbers will be generated.

For correct HTML file names, use *xelatex*, *lualatex*, or dedicated document classes / engines.

(As of this writing, this warning is only relevent to the kotex package.)

9.15 Miscellaneous packages

9.15.1 verse and memoir

Pkg verse

Cls memoir

\attrib

When using verse or memoir, always place a `\\` after each line.

The documentation for the verse and memoir packages suggest defining an `\attrib` command, which may already exist in current documents, but it will only work for print output. lwarp provides `\attribution`, which works for both print and HTML output. To combine the two so that `\attrib` is used for print and `\attribution` is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len \vleftskip

Len \vleftmargini

Len \HTMLvleftskip

Len \HTMLleftmargini

These lengths are used by verse and memoir to control the left margin, and they may already be set by the user for print output. New lengths `\HTMLvleftskip` and `\HTMLleftmargini` are provided to control the margins in HTML output. These new lengths may be set by the user before any `verse` environment, and persist until they are manually changed again. One reason to change `\HTMLleftmargini` is if there is a wide `\flagverse` in use, such as the word "Chorus", in which case the value of `\HTMLleftmargini` should be set to a wide enough length to contain "Chorus". The default is wide enough for a stanza number.

⚠ spacing

Horizontal spacing relies on *pdftotext*'s ability to discern the layout (`-layout` option) of the text in the HTML-tagged PDF output. For some settings of `\HTMLleftmargini` or `\HTMLleftskip` the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

9.15.2 newclude package

Pkg newclude

⚠ loading

newclude modifies `\label` in a non-adaptive way, so newclude must be loaded before lwarp is loaded:

```
\documentclass{article}
. . . <font setup>
\usepackage{newclude}
\usepackage[warpHTML]{lwarp}
. . .
```

9.15.3 babel package

Pkg babel

⚠ \CaptionSeparator

When French is used, the caption separator is changed to a dash. The following may be used to restore it to a colon:

```
\renewcommand*{\CaptionSeparator}{:~}
```

punctuation spaces

⚠ customized spacing

Also when French is used, lwarp creates fixed-width space around punctuation by patching \FBcolonspace, \FBthinspace, \FBguillspace, \FBmedkern, \FBthickkern, \FBtextellipsis, and the tilde. If the user's document also changes these parameters, the user's changes should be placed inside a warpprint environment so that the user's changes do not affect the HTML output.

9.15.4 polyglossia package

Pkg polyglossia

lwarp uses cleveref, which has some limitations when using polyglossia, possibly resulting in the error

```
! Undefined control sequence. . . . \@begindocumenthook
```

To test compatibility, add

```
\usepackage{cleveref}
```

near the end of the preamble (as the last package to be loaded), and try to compile the print version. It may be necessary to set

```
\setdefaultlanguage{english}
```

or some other language supported by cleveref, then select other languages using \setotherlanguages.

Once the print version works with cleveref and polyglossia, the HTML version should work as well using lwarp.

9.15.5 todonotes and luatodonotes packages

Pkg todonotes

Pkg luatodonotes

The documentation for todonotes and luatodonotes have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

9.15.6 fixme

Pkg fixme

⚠ external layouts

External layouts (\fxloadlayouts) are not supported.

User control is provided for setting the HTML styling of the "faces". The defaults are as follows, and may be changed in the preamble after fixme is loaded:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}
```

9.15.7 chemfig package

If using `\polymerdelim` to add delimiters to a `\chemfig`, wrap both inside a single `lateximage`:

```
\begin{lateximage}[(-chemfig-~\packagediagramname)]
\chemfig{. . . }
\polymerdelim[. . . ]{. . . }
\end{lateximage}
```

9.15.8 chemformula package

⚠ chemformula with MathJax

chemformula works best without MathJax. If MathJax is used, `\displaymathother` must be used before `array`, and then `\displaymathnormal` may be used after. (The chemformula package adapts to `array`, but does not know about MathJax, and MathJax does not know about chemformula.)

While using MathJax, `\displaymathother` may also be used for other forms of display and inline math which contain chemformula expressions.

9.15.9 mhchem package

See section 309.

9.15.10 xparse package

Pkg xparse

To remove from the log any warnings about redeclaring objects, place the following before lwarp is loaded:

```
\usepackage[log-declarations=false]{xparse}
```

9.15.11 kotex package

Pkg kotex

See section 9.14 regarding *pdflatex* and Korean section names.

⚠ Korean section names

10 Compiling using custom shell commands

lwarp and *lwarpmk* try to make it easy to process print and HTML compilation tasks in most situations. Depending on the operating system, command-line options, TEX engine, and lwarp options, the commands **`lwarpmk print`** and **`lwarpmk html`** are automatically set up to correctly recompile the project. These actions may be overridden using lwarp options, thus allowing the use of packages such as perltex and pythontex.

10.1 Command options

Opt PrintLatexCmd
Opt HTMLLatexCmd

The lwarp options `PrintLatexCmd` and `HTMLLatexCmd` are used to set customized commands to be executed by **`lwarpmk print`** and **`lwarpmk html`**.

`PrintLatexCmd` should be set to shell commands which take `project.tex` and generate `project.pdf`.

`HTMLLatexCmd` should be set to take `project_html.tex` and generate `project_html.pdf`. *lwarpmk* will then take `project_html.pdf` and automatically convert it and generate `project.html`.

10.2 Literal character macros

The lwarp package options are parsed by TEX, and so some characters require the use of a special macro to represent them. See table 7. `\LWRopquote` and `\LWRopseq` may be used to increase operating-system portability. `\jobname` must have `_html` appended for processing HTML. `\space` may be necessary between other macros.

⚠ macro not found

To use these macros, either kvoptions-patch must be loaded before lwarp:

```
\usepackage{kvoptions-patch}
\usepackage[
    PrintLatexCmd={ ... } ,
    HTMLLatexCmd={ ... }
]{lwarp}
```

Table 7: Literal character macros

Character	Macro	Comment
%	\LWRpercent	
$	\LWRdollar	
&	\LWRamp	
%	\LWRhash	
\	\LWRbackslash	
' or "	\LWRopquote	Depends on the operating system.
& or &&	\LWRopseq	Depends on the operating system.
(space)	\space	Forces an extra space.
(jobname)	\jobname	Without file extension.

or \lwarpsetup must be used to set PrintLatexCmd and HTMLLatexCmd:

```
\usepackage[...]{lwarp}
\lwarpsetup{
  PrintLatexCmd=
      {
          latex tm \LWRopseq
          dvips -o tm-pics.ps tm.dvi \LWRopseq
          ps2pdf tm-pics.ps \LWRopseq
          pdflatex tm.tex
      } ,
  HTMLLatexCmd=
      {
          latex tm_html \LWRopseq
          dvips -o tm_html-pics.ps tm_html.dvi \LWRopseq
          ps2pdf tm_html-pics.ps \LWRopseq
          pdflatex tm_html.tex
      }
}
```

10.3 *latexmk*

Prog latexmk If *latexmk* is used for a project, it may be easiest to continue using it.

latexmk project.tex would create project.pdf as normal.

latexmk project_html.tex would create project_html.pdf, then

lwarpmk pdftohtml project_html.pdf would take project_html.pdf and convert it to project.html.

Pkg sagetex *latexmk* may simplify the use of packages such as sagetex.

10.4 perltex package

Pkg perltex The lwarp package option settings to use perltex would be similar to:

```
\usepackage[
  . . .
  PrintLatexCmd={perltex -latex=pdflatex project.tex} ,
  HTMLLatexCmd={perltex -latex=pdflatex project_html.tex} ,
  . . .
]{lwarp}
```

⚠ "impure" math Place perltex math expressions between `\displaymathother` and `\displaymathnormal`, or `\inlinemathother` and `\inlinemathnormal`. See section 9.7.9.

10.5 pythontex package

Pkg pythontex An example using pythontex:

```
\usepackage[
  . . .
  PrintLatexCmd={
    pdflatex project.tex \LWRopseq
    pythontex project \LWRopseq
    pdflatex project.tex
  } ,
  HTMLLatexCmd={
    pdflatex project_html.tex \LWRopseq
    pythontex project_html \LWRopseq
    pdflatex project_html.tex
  } ,
  . . .
]{lwarp}
```

Another possibility is to use *latexmk*, placing the **`latexmk . . .`** commands in the `PrintLatexCmd` and `HTMLLatexCmd` options. While using these options, the lwarp option `latexmk` would not be used.

⚠ "impure" math
⚠ HTML look-alike

No attempt has yet been made to make pythontex robust with HTML output. Some math objects must be surrounded by `\displaymathother` ... `\displaymathnormal`, or `\inlinemathother` ... `\inlinemathnormal`. Displays of code may have to be enclosed inside a `lateximage` environment to prevent <, > and similar from being interpreted by the browser as HTML entities.

10.6 Other packages

Pkg sympytex Other packages such as sympytex and rterface would be set up similar to pythontex,

Pkg rterface

and the same warnings would apply.

10.7 *make* program

Prog make

To use lwarp with the *make* program, have the `makefile` take `project.tex` and generate the print version `project.pdf`, as normal. `\usepackage{lwarp}` must be used, and it generates `lwarpmk.conf` when the print version is created.

To generate HTML, first have `project_html.tex` be compiled to generate `project_html.pdf`. This must be in PDF format. Finally, have `project_html.pdf` be converted to HTML using **`lwarpmk pdftohtml project_html.pdf`**, and convert SVG math with **`lwarpmk limages`**.

10.8 UTF-8 locale

⚠ UTF-8 locale

lwarpmk uses the *texlua* program, which sets the "locale" to "C", including for external operating-system calls such as when executing **`lwarpmk html`**. In some cases, an external program called from the user's document may require the use of a UTF-8 "locale". For UNIX-related operating systems, it may be required to use lwarp's custom compilation options to add a locale change:

```
\usepackage{lwarp}[
  PrintLatexCmd={
    env LC_CTYPE=en_US.UTF-8
      xelatex --shell-escape project.tex
  }
  HTMLLatexCmd={
    env LC_CTYPE=en_US.UTF-8
      xelatex --shell-escape project_html.tex
  }
]
```

Pkg ditaa

The only example seen so far where this is required is the ditaa package, where the locale change allows the use of UTF-8 with XeLaTeX and ditaa. To use LuaLaTeX instead, the locale change would have to be made inside the ditaa package where its calls the *ditaa* program.

11 EPUB conversion

lwarp does not produce EPUB documents, but it may be told to modify its HTML output to greatly assist in the conversion. An external program may then be used to finish the conversion to EPUB.

<meta> author

To assign the author's name for regular lwarp HTML files, and also for the EPUB, use `\HTMLAuthor {⟨name⟩}`. This assigns the name to the `<meta>` author element. It may be set empty, and it defaults to `\theauthor`.

A special boolean is provided to simplify the process of converting lwarp HTML output to EPUB:

`FormatEPUB`

Bool `FormatEPUB`
Default: `false`

`FormatEPUB` changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.

To help convert lwarp HTML output to EPUB, add

```
\booltrue{FormatEPUB}
```

to the project's source preamble after `\usepackage{lwarp}`. The EPUB version of the document cannot co-exist with the regular HTML version, so

Enter ⇒ **`lwarpmk cleanall`**

Enter ⇒ **`lwarpmk html`**

Enter ⇒ **`lwarpmk limages`**

to recompile with the `FormatEPUB` boolean turned on. Several changes are then made to the HTML output:

- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.

Calibre

The resulting files will be ready to be loaded into an EPUB conversion program, such as the open-source program *Calibre* (`https://calibre-ebook.com/`).

⚠ search order

The EPUB conversion program must know what order the files are included. For lwarp projects, set the EPUB conversion software to do a breadth-first search of the files. For *Calibre*, this option is found in

Preferences → Plugins → File type plugins → HTML to Zip

⚠ encoding

Check the box Add linked files in breadth first order. Set the document encoding as `utf-8`, which is what lwarp generates for HTML, even if the original printed document uses some other encoding.

⚠ section breaks

The EPUB-conversion program must also know where the section breaks are located. For a list of lwarp's section headings, see table 9. For example, an `article` class document would break at `\section`, which is mapped to HTML heading level `<h4>`, whereas a `book` class document would break at `\chapter`, which is HTML heading level `<h3>`. For *Calibre*, this option is found in

> **Preferences → Conversion (Common Options) → Structure Detection → Detect chapters at (XPath expression)**

Select the "magic wand" to the right of this entry box, and set the first entry

> **Match HTML tags with tag name:**

to "h4". (Or "h3" for document classes with `\chapters`.) The Detect chapters at field should then show

> **//h:h4** — or — **//h:h3**

This option is also available on the main tool bar at the Convert books button.

Once these settings have been made, the lwarp-generated HTML files may be loaded by *Calibre*, and then converted to an EPUB.

MathJax support

MathJax may be used in EPUB documents. Some e-readers include MathJax, but any given reader may or may not have a recent version, and may or may not include extensions such as support for siunitx.

lwarp adds some modifications to MathML to support equations numbered by chapter. These modifications may not be compatible with the e-reader's version of MathJax, so lwarp requests that a known version be loaded instead. In some cases chapter numbering of equations still doesn't work.

Until math support in EPUB documents is improved, it is recommended to use SVG images instead of MathJax, especially for equations numbered by chapter, or where siunitx support is important.

12 Word-processor conversion

lwarp may be told to modify its HTML output to make it easier to import the HTML document into a word processor. At the time of this writing, it seems that LibreOffice works best at preserving table layout, but it still has some limitations, such as an inability to automatically assign figure and table frames and captions according to user-selected HTML classes. lwarp provides some assistance in locating these frame boundaries, as shown below.

12.1 Activating word-processor conversion

A special boolean is provided to simplify the process of converting lwarp HTML output to EPUB:

`FormatWP`

Bool `FormatWP`
Default: `false`

Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments. Additionally, honors the booleans `WPMarkFloats`, `WPMarkMinipages`, `WPMarkTOC`, and `WPMarkLOFT`.

To help modify lwarp HTML output for easier import to a word processor, add

```
\booltrue{FormatWP}
```

to the project's source preamble after lwarp is loaded. The following changes are then made to the HTML output:

formatting adjustments

- If using a class without chapters, `\section` and lower are shifted up in level for the HTML heading tags. The CSS has not been changed, so the section heading formats will not match the normal HTML output, but when imported to *LibreOffice Writer* the higher section headings will import as **Heading 1** for the title, **Heading 2** for `\section`, etc.
- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.
- Forces single-file output.
- Turns off HTML debugging comments. These are comments appearing inside the HTML code, marking the opening/closing of sections and `<div>`s, but they are no longer useful when the document has been imported into a word processor.
- An additional `<div>` with an `id` encapsulates each float and minipage, which on import into *LibreOffice Writer* causes a thin frame to appear around the text block for each.
- Float captions are given an explicit italic formatting.

- Tabular rule borders are made explicit for *LibreOffice Writer*. LibreOffice displays a light border around each cell while editing, even those which have no border when printed, and lwarp also uses a light border for thin rules, so it will be best to judge the results using the print preview instead of while editing in LibreOffice.
- `\includegraphics` and svg math width and height are made explicit for LibreOffice.
- `\hspace` is approximated by a number of `\quad`s, and rules are approximated by a number of underscores.
- Explicit html styles are given to:
  - `\textsc`, etc.
  - `\underline`, soul and ulem markup.
  - `center`, `flushleft`, `flushright`.
  - `\marginpar`, keyfloat, sidenotes, floatflt, and wrapfig.
  - fancybox `\shadowbox`, etc.
  - The LaTeX and TeX logos.
- Honors several booleans:

  `WPMarkFloats`: Marks the begin and end of floats.

  `WPMarkMinipages`: Marks the begin and end of minipages.

  `WPMarkTOC`: Marks the location of the Table of Contents.

  `WPMarkLOFT`: Marks the locations of the List of Figures/Tables.

  `WPMarkMath`: Prints LaTeX math instead of using images.

  `WPTitleHeading`: Adjusts title and section headings.

  Several of these may be used to add markers to the html text which help determine where to adjust the word processor document after import.

12.2 Additional modifications

`WPMarkFloats`

Bool `WPMarkFloats`
Default: `false`

Adds

```
=== begin table ===
. . .
=== end ===
```

or

```
=== begin figure ===
. . .
=== end ===
```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions.

WPMarkMinipages

Bool WPMarkMinipages
Default: false

Adds

```
=== begin minipage ===
. . .
=== end minipage ===
```

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

WPMarkTOC

Bool WPMarkTOC
Default: true

While formatting for word processors, adds

```
=== table of contents ===
```

where the Table of Contents would have been. This helps identify where to insert the actual TOC.

If set `false`*, the actual* TOC *is printed instead.*

WPMarkLOFT

Bool WPMarkLOFT
Default: false

While formatting for word processors, adds

```
=== list of figures ===    and/or
=== list of tables ===
```

where each of these lists would have been. This helps identify where to insert the actual lists.

If set `false`*, the actual lists are printed instead.*

WPMarkMath

siunitx
Bool WPMarkMath
Default: false
Prog TeXMaths

While formatting for word processors, prints math as LaTeX code instead of creating SVG images or MathJax. This is useful for cut/paste into the *LibreOffice Writer TeXMaths* extension.

When using the siunitx package, enter

```
\usepackage{siunitx}
```

in the *TeXMaths* preamble. Equation numbering is problematic for $\mathcal{AMS}$ math environments.

Table 8: Section HTML headings for word-processor conversion

	HTML headings*			
	With \chapter		Without \chapter	
	WPTitleHeading		WPTitleHeading	
Section	true	false	true	false
Title	<h1>	plain	<h1>	plain
\part	<h2>	<h1>	<h2>	<h1>
\chapter	<h3>	<h2>	—	—
\section	<h4>	<h3>	<h3>	<h2>
\subsection	<h5>	<h4>	<h4>	<h3>
\paragraph	<h6>	<h5>	<h5>	<h4>
\subparagraph	span	<h6>	<h6>	<h5>

* For default depths when not FormatWP, see table 9 on page 192.

WPTitleHeading

Bool WPTitleHeading
Default: false
section headings

While formatting for word processors, true sets the document title to <h1>, which is expected for HTML documents, but also causes the lower-level section headings to start at **Heading 2** when imported into LibreOffice. Set to false to cause the title to be plain text, and the section headings to begin at **Heading 1**.

See table 8 on page 178.

12.3 Recommendations

TOC, LOF, LOT

For use with *LibreOffice Writer*, it is recommended to:

1. Set \booltrue{FormatWP}
2. Set \booltrue{WPMarkTOC} and \boolfalse{WPMarkLOFT}
3. Use lwarp to generate the HTML document.
4. Copy/paste from the HTML document into an empty *LibreOffice Writer* document.
5. Manually insert a LibreOffice TOC in the LibreOffice document.
6. Manually add frames around each float, adding a caption which is cut/pasted from each float's simulated caption.
7. Manually create cross references.

This process yields a document with an actual LibreOffice Table of Contents, but a simulated List of Figures and List of Tables.

siunitx

For siunitx, remember to adjust the preamble as mentioned above.

LO view border options

LibreOffice has options in the **View** menu to turn on/off the display of thin borders around table cells and text objects.

12.4 Limitations

Floats and captions are not explicitly converted to LibreOffice floats with their own captions. Floats are surrounded by a thin frame in the LibreOffice editor, and may be marked with `WPMarkFloats`, but are not given a proper LibreOffice object frame. Captions are given an explicit italic formatting, but not a proper LibreOffice paragraph style.

Cross references are not actual LibreOffice linked cross references.

The List of Figures and List of Tables are not linked. The pasted pseudo LOF and LOT match the numbering of the LaTeX and HTML versions.

Equation numbering is not automatic, but the equation numbers in SVG math will match the LaTeX and HTML output. SVG math is recommended when using the $\mathcal{AMS}$ environments, which may have multiple numbered equations per object.

As of when last checked, LibreOffice ignores the following:

- Minipage alignment.
- Tabular cell vertical alignment.
- Image rotation and scaling.
- Rounded border corners, which are also used by:
  - `\textcircled`
  - booktabs trim
- `\hspace` and rules, also used by algorithmic.
- Coloring of text decorations, used by soul and ulem.
- Overline text decoration, used by romanbar.

LibreOffice also has limitations with frames and backgrounds:

- Multiple lines in an object are framed individually instead of as a whole.
- Nested frames are not handled correctly.
- Images inside boxes are not framed correctly.
- Spans with background colors and frames are not displayed correctly.

13 Modifying lwarp

locating something

To quickly find the source for a package in `lwarp.dtx`, search for `*packagename`, such as `*siunitx`.

Likewise, to quickly find the source for a file in `lwarp.dtx`, search for `*filename`, such as `*lwarp.css`.

Purely text-based packages probably will work as-is when generating HTML.

Look to existing code for ideas on how to expand into new code.

image of TEX output

An environment may be converted to a `lateximage` then displayed with an image of the resulting LATEX output. See section 87 for an example of the `picture` environment.

css classes

To create a custom HTML block or inline CSS class, see section 51.9.

print/HTML macros

To create print and HTML versions of the same macro or environment, see section 36.

⚠ TEX boxes

Any TEX boxes must be undone, as SVG math or `lateximages` require `\newpage`, which will not work in a TEX box.

index recreation

To recreate the index for the lwarp documentation:

```
makeindex -s gglo.ist -o lwarp.gls lwarp.glo
splitindex lwarp.idx -- -s gind.ist
```

13.1 Creating a development system

The following creates a local development system for lwarp on a TeXLive system in a UNIX-like environment. Doing so allows anything requesting lwarp to use the development version instead of whichever version is installed in TeXLive.

Create a development directory:

Place into this directory `lwarp.dtx` and `lwarp.ins`.

To create `lwarp.sty`, execute

Enter ⇒ **`pdflatex lwarp.ins`**

which creates `lwarp.sty` and several hundred additional `lwarp-*.sty` files for the various packages which are supported.

To create the documentation `lwarp.pdf`, execute

Enter ⇒ **`pdflatex lwarp.dtx`**

To make the development files visible to other projects:

Create the directory

`/usr/local/texlive/texmf-local/tex/latex/local/lwarp`

Inside this directory, create the file update, containing:

```
ln -s /path_to_dev_directory/lwarp*.sty .
ln -s /path_to_dev_directory/lwarp_baseline_marker.png .
ln -s /path_to_dev_directory/lwarp_baseline_marker.eps .
mktexlsr
```

Run ./update now, and whenever a new lwarp-* package is added.

To make the development version of *lwarpmk* visible to other projects:

```
cd /opt
ln -s /usr/local/texlive/texmf-local/bin/x86_64-linux texbin_local
cd texbin_local
ln -s ../../scripts/lwarp/lwarpmk.lua lwarpmk
cd /usr/local/texlive/texmf-local/scripts/
mkdir lwarp
cd lwarp
ln -s /path_to_dev_directory/lwarpmk.lua lwarpmk
```

Verify that the correct version is found with

Enter ⇒ **`which lwarpmk`**

To make the local versions visible to the shell:

Paths must be set by the shell startup, such as in .bashrc and .cshrc:

In .bashrc:

```
PATH=/opt/texbin_local:/opt/texbin:$PATH
```

In .cshrc:

```
setenv PATH ${HOME}/bin:/opt/texbin_local:/opt/texbin:${PATH}
```

13.2 Modifying a package for lwarp

If a class loads additional packages, it will be required to modify the class for lwarp, since lwarp must be loaded before most other packages.

To work with lwarp, a class must first set up anything which replicates the functions of the basic LaTeX classes, load any required fonts, then load lwarp, then finally load and adjust any other required packages.

When creating HTML, lwarp redefines the \usepackage and \RequirePackage macros such that it first looks to see if a lwarp-<packagename>.sty version exists. If so, the lwarp version is used instead. This modular system allows users to create their own versions of packages for lwarp to use for HTML, simply by creating a new package with

a lwarp- prefix. If placed in the local directory along with the source code, it will be seen by that project alone. If placed alongside the other lwarp- packages where TEX can see it, then the user's new package will be seen by any documents using lwarp. (Remember mktexlsr or texhash.)

An lwarp-<packagename>.sty package is only used during HTML generation. Its purpose is to pretend to be the original package, while modify anything necessary to create a successful HTML conversion. For many packages it is sufficient to simply provide nullified macros, lengths, counters, etc. for anything which the original package does, while passing the raw text on to be typeset. See the pre-existing lwarp- packages for examples.

Anything the user might expect of the original package must be replaced or emulated by the new lwarp- package, including package options, user-adjustable counters, lengths, and booleans, and conditional behaviors. In many of these packages, most of the new definitions have a "local" prefix according to the package name, and @ characters inside the name, which hides these names from the user. In most cases these macros will not need to be emulated for HTML output. Only the "user-facing" macros need to be nullified or emulated.

Each lwarp-* package should first call either of:

```
\LWR@ProvidesPackageDrop
  -or-
\LWR@ProvidesPackagePass
```

If "Drop"ped, the original print-version package is ignored, and only the lwarp- version is used. Use this where the original print version is useless for HTML. If "Pass"ed, the original package is loaded first, with the user-supplied options, then the lwarp- version continues loading as well. See section 337 (ntheorem) for an example of selectively disabling user options for a package. Use this when HTML output only requires some modifications of the original package. For a case where the original package is usable without changes, there is no need to create a lwarp- version.

13.2.1 Adding a package to the lwarp.dtx file

When adding a package to lwarp.dtx for permanent inclusing in lwarp, provide the lwarp-<packagename> code in lwarp.dtx, add its entry into lwarp.ins, and also remember to add

```
\LWR@loadafter{<packagename>}
```

to lwarp.dtx in section 21.1. This causes lwarp to stop with an error if packagename is loaded before lwarp. Finally, add an entry in table 2, Supported packages and features, and also the Updates section.

13.3 Modifying a class for lwarp

If a class loads additional packages, it will be required to modify the class for lwarp, since lwarp must be loaded before most other packages.

To work with lwarp, a class must first set up anything which replicates the functions of the basic LaTeX classes, load any required fonts, then load lwarp, then finally load and adjust any other required packages.

13.4 Testing lwarp

When changes have been made, test the print output before testing the HTML. The print output compiles faster, and any errors in the printed version will be easier to figure out than the HTML version.

Remember that the configuration files are only rewritten when compiling the printed version of the document.

When changing the source to *lwarpmk* or a CSS file in `lwarp.dtx`:

1. Change the source in `lwarp.dtx`.
2. `pdflatex lwarp.ins`
3. `pdflatex lwarp.dtx`
4. If modifying *lwarpmk* the new version should now be active.
5. If modifying CSS files:
   (a) For the document, `lwarpmk print` to update the CSS files in the project.
   (b) Reload the HTML document to see the effect of the new CSS files.

Sometimes it is worth checking the `<project>_html.pdf` file, which is the PDF containing HTML tags. Also, `<project>_html.html` has the text conversion of these tags, before the file is split into individual HTML files.

It is also worth checking the browser's tools for verifying the correctness of HTML and CSS code.

13.5 Modifying *lwarpmk*

Prog `lwarpmk`
File `lwarpmk.lua`

In most installations, `lwarpmk.lua` is an executable file located somewhere the operating system knows about, and it is called by typing **`lwarpmk`** into a terminal.

A project-local copy of `lwarpmk.lua` may be generated, modified, and then used to compile documents:

1. Add the `lwarpmk` option to the lwarp package.
2. Recompile the printed version of the document. The `lwarpmk` option causes lwarp to create a local copy of `lwarpmk.lua`
3. The `lwarpmk` option may now be removed from the lwarp package.
4. Copy and rename `lwarpmk.lua` to a new file such as `mymake.lua`.

5. Modify `mymake.lua` as desired.
6. If necessary, make `mymake.lua` executable.
7. Use `mymake.lua` instead of `lwarpmk.lua`.

14 Troubleshooting

14.1 Using the lwarp.sty package

Also see:
Section 8.8: Commands to be placed into the `warpprint` environment
Section 9: Special cases and limitations

Text is not converting correctly / corrupted HTML tags:

- Font-related UTF-8 information must be embedded in the PDF file. See section 8.2 regarding bitmapped vs. vector fonts.
- See section 9.2.1 regarding HTML entities and the characters &, <, and >.

Undefined HTML settings:

- See the warning regarding the placement of the HTML settings at section 8.4.

Tabular problems: See section 9.10.

Obscure error messages:

Print first: Be sure that a print version of the document compiles and that your document's LaTeX code is correct, before attempting to generate an HTML version.

`\end{warpHTML}, \end{warpprint}, \end{warpall}`: Each of these must be without any other characters on the same line.

Options clash: If using memoir, see section 9.13.

"No room for a new `\write`.": Before `\usepackage{lwarp}`, add:

```
\usepackage{morewrites}
\morewritessetup{allocate=10}
```

"Missing $ inserted.": If using a filename or URL in a footnote or `\item`, escape underscores with `\_`.

"Label(s) may have changed. Rerun to get cross-references right.":

This warning may repeat endlessly if a math expression is used in a caption. Simple math expressions such as $X=1$ may be replaced with

```
\textit{X}\,=\,1
```

"Leaders not followed by proper glue": This can be caused by a missing `l@<floattype>` or `l@<sectiontype>` definition. See lwarp's definitions for examples.

"Improper `\prevdepth`": `lateximages` and SVG math require `\newpage`, which cannot work inside TeX boxes or `\ensuremath`. Anything using `\newsavebox`, `\newbox`, `lrbox`, `\savebox`, `\hbox`, `\vbox`, `\usebox`, `\sbox`, etc., must be modified to work without box commands.

If you find something using `\ensuremath`, have it temporarily set:

```
\LetLtxMacro\@ensuredmath\LWR@origensuredmath
```

inside a group first.

⚠ macros in section,table,figure names

Also, custom macros which appear inside a section, figure, or table name should be made robust since they appear inside the `.toc`, `.lof`, or `.lot` files. Use `\newrobustcmd` or `\robustify` from etoolbox, xparse, etc.

⚠ BibTeX

If using BibTeX, see section 9.6.9.

⚠ polyglossia

"`! Undefined control sequence. ... \@begindocumenthook''`": See section 9.15.4 if using polyglossia.

⚠ custom macros for environments

"`\begin{equation} ended by \end{document}`": Do not use custom macros such as `\beq` and `\eeq` to replace

```
\begin{equation}
...
\end{equation}
```

⚠ `\LWR@formatted`

"`Misplaced \omit`": If using `\LWR@formatted` to define new macros for print and HTML modes, see section 36 regarding `\LWR@expandableformatted`.

⚠ "impure" math objects

Complicated objects inside math: Some objects, such as Ti*k*z, may not compile in lwarp's normal math emulation. Insert

```
\displaymathother -or- \inlinemathother
```

before the math, and then

```
\displaymathnormal -or- \inlinemathnormal
```

when displaying "normal" math. See section 9.7.9.

Slow compliation of math objects: Complicated math objects can also cause problems with `alt` tags, resulting in very slow compilation, large `alt` tags, and possible crashes. Use `\inlinemathother` ... `\inlinemathnormal` or `\displaymathother` ... `\displaymathnormal` around the math expression.

⚠ MathJax

Incorrect MathJax: Some objects do not convert to MathJax. Use `\displaymathother` before these objects, then `\displaymathnormal` to return to "normal" display math. See section 9.7.9.

⚠ MathJax

Missing sections: See section 8.4 regarding the `FileDepth` and `SideTOCDepth` counters, and the use of `\tableofcontents` in the home page.

Misnumbered footnotes from section headings: See section 9.5.4.

Missing HTML files:

- See the warning regarding changes to the HTML settings at section 8.4.
- Ensure that the filenames are unique after math and short words are removed. See `FileSectionNames` at section 8.4.

Missing / incorrect cross-references:

- Use `lwarpmk again` followed by `lwarpmk html` or `lwarpmk print` to compile the document one more time.

labels

⚠ label characters

`\nameref`

⚠ empty link

- Labels with special characters may be a problem. It is best to stick with alpha-numeric, hyphen, underscore, and perhaps the colon (if not French). `\nameref` refers to the most recently-used section where the `\label` was defined. If no section has been defined before the `\label`, the link will be empty. Index entries also use `\nameref` and have the same limitation.

⚠ cleveref page numbers

- cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to "for".

  Ex:

  ```
      \cpageref{tab:first,tab:second}
   in html becomes:
      "pages for table 4.1 and for table 4.2"
  ```

  See `\cpagerefFor` at page 535 to redefine the message which is printed for page number references.

BibTeX errors with `\etalchar`: See section 9.6.9.

Malformed URLs: Do not use the `%` character between arguments of `\hyperref`, etc., as this character is among those which is neutralized for inclusion in HTML URLs.

Em-dashes or En-dashes in listing captions and titles:

Use XeLaTeX or LuaLaTeX.

Floats out of sequence:

Mixed "Here" and floating: Floats [H]ere and regular floats may become out of order. `\clearpage` if necessary.

Caption setup: With `\captionsetup` set the positions for the captions `above` or `below` to match their use in the source code.

Images are appearing in strange places:

- Enter **`lwarpmk limages`** to refresh the `lateximage` images.

SVG images:

⚠ adding/removing

When a math expression, `picture`, or Ti*k*z environment is added or removed, the SVG images must be re-created by entering **`lwarpmk limages`** to maintain the proper image-file associations. Inline SVG math may be hashed and thus not need to be recreated, but display math and objects such as Ti*k*z may move to new image numbers when the document is changed.

recompile first

Before attempting to create the SVG image files, *lwarpmk* verifies that the HTML version of the document exists and has correct internal image references.[15] If it is necessary to recompile the document's HTML version one more time, *lwarpmk* usually will inform the user with an error message, but there are some conditions which cannot be detected, so the user should watch for the LaTeX recompile warnings.

⚠ HTML instead of images

If HTML appears where an SVG image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time.

⚠ page counter

Incorrect SVG images will also occur if the document changes the `page` counter:

```
\setcounter{page}{<value>}
```

The `page` counter must *not* be adjusted by the user.

Expressing math as SVG images has the advantage of representing the math exactly as LaTeX would, but has the disadvantage of requiring an individual file

⚠ Lots of files!

for each math expression. For inline math, and some other objects, lwarp uses an MD5 hash on its LaTeX source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as `picture` and Ti*k*z require one image file each. For a document with a large amount of math, see section 6.5 to use MathJax instead.

Plain-looking document:

- The document's CSS stylesheet may not be available, or may be linked incorrectly. Verify any `\CSSFilename` statements point to a valid CSS file.

Broken fragments of HTML:

- Check the PDF file used to create HTML to see if the tags overflowed the margin. (This is why such large page size and margins are used.)

Changes do not seem to be taking effect:

- Be sure to `lwarpmk clean`, recompile, then start by reloading the home page. You may have been looking at an older version of the document. If you changed a section name, you may have been looking at the file for the old name.
- See the warning regarding changes to the HTML settings at section 8.4.
- Verify that the proper CSS is actually being used.
- The browser may compensate for some subtle changes, such as automatically generating ligatures, reflowing text, etc.

Un-matched conditional compiles:

- Verify the proper `begin`/`end` of `warpprint`, `warpHTML`, and `warpall` environments.

14.1.1 Debug tracing output

`\tracinglwarp` When `\tracinglwarp` is used, lwarp will add extra tracing messages to the `.log` file. The last several messages may help track down errors.

Place `\tracinglwarp` just after `\usepackage{lwarp}` to activate tracing.

14.2 Compiling the `lwarp.dtx` file

`lwarp_tutorial.tex`: Copy or link `lwarp_tutorial.txt` from the TDS doc directory to the `source` directory, or wherever you wish to compile the documentation. This file is included verbatim in the documentation, but is in the `doc` directory so that it may be found by *texdoc* and copied by the user.

Illogical error messages caused by an out-of-sync `lwarp.sty` file:

1. Delete the `lwarp.sty` file.

[15] This becomes important when dealing with a document containing thousands of images.

2. Enter **pdflatex lwarp.ins** to generate a new lwarp.sty file.
3. Enter **pdflatex lwarp.dtx** to recompile the lwarp.pdf documentation.

Un-nested environments:

Be sure to properly nest:

- \begin{macrocode} and \end{macrocode}
- \begin{macro} and \end{macro}
- \begin{environment} and \end{environment}

15 Trademarks

- TEX is a trademark of American Mathematical Society.
- ADOBE® and ADOBE *Framemaker*® are either registered trademarks or trademarks of ADOBE SYSTEMS INCORPORATED in the United States and/or other countries.
- LINUX® is the registered trademark of Linus Torvalds in the U.S. and other countries.
- MAC OS® is a trademark of APPLE INC.
- MADCAP FLARE™ is the property of MADCAP SOFTWARE, INC.
- MATHJAX is copyright 2009 and later. The MATHJAX CONSORTIUM is a joint venture of the AMERICAN MATHEMATICAL SOCIETY (AMS) and the SOCIETY FOR INDUSTRIAL AND APPLIED MATHEMATICS (SIAM) to advance mathematical and scientific content on the web.
- MICROSOFT®, ENCARTA, MSN, and WINDOWS® are either registered trademarks or trademarks of MICROSOFT CORPORATION in the United States and/or other countries.
- UNIX® is a registered trademark of THE OPEN GROUP.

File 1 **lwarp.sty**

16 Implementation

This package is perhaps best described as a large collection of smaller individual technical challenges, in many cases solved through a number of ~~crude hacks~~ clever tricks. Reference sources are given for many of the solutions, and a quick internet search will provide additional possibilities.

Judgement calls were made, and are often commented. Improvements are possible. The author is open to ideas and suggestions.

Packages were patched for re-use where they provided significant functionality. Examples include xcolor with its color models and conversion to HTML color output, and siunitx which provides many number and unit-formatting options, almost all of which are available in pure-text form, and thus easily used by *pdftotext*.

Packages were emulated where their primary purpose was visual formatting which is not relevent to HTML output. For example, packages related to sectioning are already patched by numerous other packages, creating a difficult number of combinations to try to support, and yet in HTML output all of the formatting is thrown away, so these packages are merely emulated.

Packages with graphical output are allowed as-is, but must be nested inside a `lateximage` environment to preserve the graphics.

Testing has primarily been done with the Iceweasel/Firefox browser.

Table 9: Section depths and HTML headings

Section	LaTeX depth	HTML headings *
title of the entire website		<h1>
none	-5	new for this package
book	-2	**not yet used**
part	-1	<h2>
chapter	0	<h3>
section	1	<h4>
subsection	2	<h5>
subsubsection	3	<h6>
paragraph	4	
subparagraph	5	
listitem	7	new for this package, used for list items

* If FormatWP is true, section headings may be adjusted, depending on WPTitleHeading. See table 8 on page 178.

17 Section depths and HTML headings

Stacks are created to track depth inside the LaTeX document structure. This depth is translated to HTML headings as shown in table 9. "Depth" here is not depth in the traditional computer-science stack-usage sense, but rather a representation of the nesting depth inside the LaTeX document structure.

When starting a new section, the program first must close out any existing sections and lists of a deeper level to keep the HTML tags nested correctly.

Support for the memoir package will require the addition of a book level, which may push the HTML headings down a step, and also cause subsubsection to become a due to a limit of six HTML headings.

It is possible to use HTML5 <section> and <h1> for all levels, but this may not be well-recognized by older browsers.

Fixed levels for parts and chapters allow the CSS to remain fixed as well.

18 Source code

This is where the documented source code for lwarp begins, continuing through the following sections all the way to the change log and index at the end of this document.

The following sections document the actual implementation of the lwarp package.

line numbers — The small numbers at the left end of a line refer to line numbers in the `lwarp.sty` file.

subjects — Blue-colored tags in the left margin aid in quickly identifying the subject of each paragraph.

objects — Black-colored tags in the left marign are used to identify programming objects such as files, packages, environments, booleans, and counters. Items without a tag are command macros. Each of these also appears in the index as individual entries, and are also listed together under "files", "packages", "environments", "booleans", and "counters".

index entries

⚠ warnings — Special warnings are marked with a warning icon.

for HTML output: **for PRINT output:** **for HTML & PRINT:** — Green-colored tags in the left margin show which sections of source code apply to the generation of HTML, print, or both forms of output.

— lwarp source code begins on the following page —

19 Detecting the TEX engine — *pdflatex*, *lualatex*, *xelatex*

See: http://tex.stackexchange.com/a/47579.

Detects XƎTEX and LuaLATEX:

```
\RequirePackage{iftex}
\newif\ifxetexorluatex
\ifXeTeX
    \xetexorluatextrue
\else
    \ifLuaTeX
        \xetexorluatextrue
    \else
        \xetexorluatexfalse
    \fi
\fi

\ifLuaTeX
\RequirePackage{luatex85}% until the geometry package is updated
\fi

\RequirePackage{ifpdf}

\RequirePackage{ifptex}
```

20 Early package requirements

Pkg etoolbox Provides `\ifbool` and other functions.

Pkg xpatch Patches macros with optional arguments.

```
\RequirePackage{etoolbox}[2011/01/03]% v2.6 for \BeforeBeginEnvironment, etc.
\RequirePackage{xpatch}
```

Pkg ifplatform Provides `\ifwindows` to try to automatically detect WINDOWS OS.

```
\RequirePackage{ifplatform}% sense op-system platform
```

Pkg letltxmacro

```
\RequirePackage{letltxmacro}
```

21 Package load order

Several packages must never be used with lwarp, others should only be loaded before lwarp, and others should only be loaded after. The lwarp core checks most of these

cases. In some lwarp-* packages, \LWR@loadbefore is used to trigger an error if they are loaded after lwarp, while additional code provides necessary patches for when they are loaded before.

Packages which must be loaded after lwarp are enfoced by a large number of \LWR@loadafter statements, below. Some packages are emulated by memoir, and so these are tested by \LWR@notmemoirloadafter, which does not cause an error if memoir is used.

\LWR@checkloadfilename is used to check each filename to see if it must never be loaded, or must always be loaded before lwarp.

21.1 Tests of package load order

\LWR@loadafter {⟨*packagename*⟩} Error if this package was loaded before lwarp.

```
\newcommand*{\LWR@loadafter}[1]{%
\@ifpackageloaded{#1}
{
    \PackageError{lwarp}
        {Package #1, or one which uses #1, must be loaded after lwarp}
       {Move \detokenize{\usepackage}{#1} after \detokenize{\usepackage}{lwarp}.
       Package #1 may also be loaded by something else, which must also be moved
        after lwarp.}
}
{}
}
```

\LWR@notmemoirloadafter {⟨*packagename*⟩} Error if not memoir class and this package was loaded before lwarp.

memoir emulates many packages, and pretends that they have already been loaded.

```
\@ifclassloaded{memoir}
{\newcommand*{\LWR@notmemoirloadafter}[1]{}}
{\LetLtxMacro\LWR@notmemoirloadafter\LWR@loadafter}
```

\LWR@notltjloadafter {⟨*packagename*⟩} Error if not a ltjs* class and this package was loaded before lwarp.

```
\LetLtxMacro\LWR@notltjloadafter\LWR@loadafter

\@ifclassloaded{ltjarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjsarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjsbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjsreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjspf}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjskiyou}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjtarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjtbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
```

```
\@ifclassloaded{ltjtreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
```

`\LWR@loadbefore` {⟨*packagename*⟩} Error if this package is loaded after lwarp.

```
\newcommand*{\LWR@loadbefore}[1]{%
\@ifpackageloaded{#1}
{}
{
\PackageError{lwarp}
{Package #1 must be loaded before lwarp}
{Move \detokenize{\usepackage}{#1} before \detokenize{\usepackage}{lwarp}.}
}
}
```

`\LWR@checkloadbefore` {⟨*thispackagename*⟩} {⟨*packagename*⟩}

If package names match, error if it is loaded after lwarp.

```
\newcommand*{\LWR@checkloadbefore}[2]{%
    \edef\LWR@tempone{#1}%
    \ifdefstring{\LWR@tempone}{#2}{%
        \LWR@loadbefore{#1}%
    }{}%
}
```

`\LWR@loadnever` {⟨*badpackagename*⟩} {⟨*replacementpkgnames*⟩}

The first packages is not supported, so tell the user to use the second instead.

```
\newcommand*{\LWR@loadnever}[2]{%
\PackageError{lwarp}
{Package #1 is not supported by lwarp's HTML conversion.
Package(s) #2 may be useful instead}
{Package #1 might conflict with lwarp in some way,
or is superceded by another package.
For a possible alternative, see package(s) #2.}
}
```

`\LWR@checkloadnever` {⟨*thispackagename*⟩} {⟨*badpackagename*⟩} {⟨*replacementpkgnames*⟩}

If this package name is the bad packagename, suggest the replacements instead.

```
\newcommand*{\LWR@checkloadnever}[3]{%
    \edef\LWR@tempone{#1}%
    \ifdefstring{\LWR@tempone}{#2}{%
        \LWR@loadnever{#2}{#3}%
    }{}%
}
```

`\LWR@earlyloadnever` {⟨*badpackagename*⟩} {⟨*replacementpkgname*⟩}

The first package is not supported, so tell the user to use the second instead. This version checks immediately for packages which may have been loaded before lwarp.

```
\newcommand*{\LWR@earlyloadnever}[2]{%
\@ifpackageloaded{#1}{%
\PackageError{lwarp}
{Package #1 is not supported by lwarp's HTML conversion.
Package(s) #2 may be useful instead}
{Package #1 might conflict with lwarp in some way,
or is superceded by another package.
For a possible alternative, see package(s) #2.}
}{}%
}
```

`\LWR@earlyclassloadnever` {⟨*badclassname*⟩} {⟨*replacementclassname*⟩}

The first class is not supported, so tell the user to use the second instead. This version checks immediately for classes which may have been loaded before lwarp.

```
\newcommand*{\LWR@earlyclassloadnever}[2]{%
\@ifclassloaded{#1}{%
\PackageError{lwarp}
{Class #1 is not supported by lwarp's HTML conversion.
Class(es) #2 may be useful instead}
{Class #1 might conflict with lwarp in some way,
or is superceded by another class.
For a possible alternative, see class(es) #2.}
}{}%
}
```

21.2 Error for disallowed packages and classes loaded before lwarp

```
\LWR@earlyclassloadnever{jarticle}{ujarticle}
\LWR@earlyclassloadnever{jbook}{ujbook}
\LWR@earlyclassloadnever{jreport}{ujreport}
\LWR@earlyclassloadnever{tarticle}{utarticle}
\LWR@earlyclassloadnever{tbook}{utbook}
\LWR@earlyclassloadnever{treport}{utreport}
\LWR@earlyloadnever{ae}{cm-super, lmodern}
\LWR@earlyloadnever{aecompl}{cm-super, lmodern}
\LWR@earlyloadnever{aecc}{cm-super, lmodern}
\LWR@earlyloadnever{alg}{algorithm2e, algorithmicx}
\LWR@earlyloadnever{algorithmic}{algorithm2e, algorithmicx}
\LWR@earlyloadnever{boxedminipage}{boxedminipage2e}
\LWR@earlyloadnever{caption2}{caption}
% \LWR@earlyloadnever{ccaption}{caption}% might be preloaded by memoir
```

The older CJK and CJKutf8 only work with xeCJK:

```
\@ifpackageloaded{xeCJK}{}{
    \LWR@earlyloadnever{CJK}{ctex, xeCJK}
```

```
    \LWR@earlyloadnever{CJKutf8}{ctex, xeCJK}
}
```

bxcjkatype is based on CJK:

```
\LWR@earlyloadnever{bxcjkjatype}{upLaTeX, bxjsarticle, ujarticle, utarticle}
```

hangul is not in TeXLive, and is not tested:

```
\LWR@earlyloadnever{hangul}{kotex, xetexko, luatexko}
```

Others:

```
\LWR@earlyloadnever{colortab}{colortbl}
\LWR@earlyloadnever{epsf}{graphicx}
\LWR@earlyloadnever{fancyheadings}{fancyhdr}
\LWR@earlyloadnever{fncylab}{cleveref}
\LWR@earlyloadnever{glossary}{glossaries}
\LWR@earlyloadnever{hyper}{hyperref}
\LWR@earlyloadnever{pdfcprot}{microtype}
\LWR@earlyloadnever{picinpar}{floatflt, wrapfig}
\LWR@earlyloadnever{picins}{floatflt, wrapfig}
\LWR@earlyloadnever{sistyle}{siunitx}
\LWR@earlyloadnever{t1enc}{fontenc, inputenc, inputenx}
\LWR@earlyloadnever{ucs}{inputenc, inputencx}
\LWR@earlyloadnever{wasysym}{textcomp, amssymb, amsfonts, mnsymbol, fdsymbol}
```

21.3 Enforcing package loading after lwarp

Packages which should only be loaded after lwarp are tested here to trip an error of they have already been loaded.

The following packages must be loaded after lwarp:

```
\LWR@loadafter{2in1}
\LWR@loadafter{2up}
\LWR@loadafter{a4}
\LWR@loadafter{a4wide}
\LWR@loadafter{a5comb}
\LWR@notmemoirloadafter{abstract}
\LWR@loadafter{academicons}
\LWR@loadafter{accsupp}
\LWR@loadafter{acro}
\LWR@loadafter{acronym}
\LWR@loadafter{adjmulticol}
\LWR@loadafter{addlines}
\LWR@loadafter{ae}
\LWR@loadafter{aecc}
\LWR@loadafter{afterpage}
\LWR@loadafter{algorithm2e}
\LWR@loadafter{algorithmicx}
\LWR@loadafter{alltt}
\LWR@loadafter{amsmath}
\LWR@loadafter{amsthm}
\LWR@loadafter{anonchap}
```

```
\LWR@loadafter{anysize}
\LWR@notmemoirloadafter{appendix}
\LWR@loadafter{ar}
\LWR@loadafter{arabicfront}
\LWR@notmemoirloadafter{array}
\LWR@loadafter{arydshln}
\LWR@loadafter{asymptote}
% \LWR@loadafter{atbegshi}% used by morewrites
\LWR@loadafter{attachfile}
\LWR@loadafter{attachfile2}
\LWR@loadafter{authblk}
\LWR@loadafter{axessibility}
\LWR@loadafter{axodraw2}
\LWR@loadafter{backref}
\LWR@loadafter{balance}
\LWR@loadafter{bbding}
\LWR@loadafter{bigdelim}
\LWR@loadafter{bigfoot}
\LWR@loadafter{bigstrut}
\LWR@loadafter{bitpattern}
\LWR@loadafter{blowup}
\LWR@loadafter{booklet}
\LWR@loadafter{bookmark}
\LWR@notmemoirloadafter{booktabs}
\LWR@loadafter{bophook}
\LWR@loadafter{bounddvi}
\LWR@loadafter{boxedminipage}
\LWR@loadafter{boxedminipage2e}
\LWR@loadafter{breakurl}
\LWR@loadafter{breqn}
\LWR@loadafter{bsheaders}
\LWR@loadafter{bxpapersize}
\LWR@loadafter{bytefield}
\LWR@loadafter{cancel}
\LWR@loadafter{canoniclayout}
\LWR@loadafter{caption}
\LWR@loadafter{caption2}
\LWR@loadafter{cases}
% \LWR@loadafter{ccaption}% may be preloaded by memoir
\LWR@loadafter{changebar}
\LWR@notmemoirloadafter{changepage}
\LWR@loadafter{changes}
\LWR@loadafter{chappg}
\LWR@loadafter{chapterbib}
\LWR@loadafter{chemfig}
\LWR@loadafter{chemformula}
\LWR@loadafter{chemgreek}
\LWR@loadafter{chemmacros}
\LWR@loadafter{chemnum}
\LWR@loadafter{chkfloat}
\LWR@notmemoirloadafter{chngpage}
\LWR@loadafter{cite}
\LWR@loadafter{cmdtrack}
\LWR@loadafter{color}
\LWR@loadafter{colortbl}
```

```
\LWR@loadafter{continue}
\LWR@loadafter{copyrightbox}
\LWR@notmemoirloadafter{crop}
% ctex must be loaded before lwarp
\LWR@loadafter{cuted}
\LWR@loadafter{cutwin}
\LWR@loadafter{dblfloatfix}
\LWR@loadafter{dblfnote}
\LWR@notmemoirloadafter{dcolumn}
\LWR@loadafter{diagbox}
\LWR@loadafter{dingbat}
\LWR@loadafter{dprogress}
\LWR@loadafter{draftcopy}
\LWR@loadafter{draftfigure}
\LWR@loadafter{draftwatermark}
\LWR@loadafter{easy-todo}
\LWR@loadafter{ebook}
\LWR@loadafter{ed}
\LWR@loadafter{ellipsis}
\LWR@loadafter{embrac}
\LWR@loadafter{emptypage}
\LWR@loadafter{endfloat}
\LWR@loadafter{endheads}
\LWR@loadafter{endnotes}
\LWR@notmemoirloadafter{enumerate}
\LWR@loadafter{enumitem}
\LWR@notmemoirloadafter{epigraph}
\LWR@loadafter{epsfig}
\LWR@loadafter{epstopdf}
\LWR@loadafter{epstopdf-base}
\LWR@loadafter{errata}
\LWR@loadafter{eso-pic}
\LWR@loadafter{eurosym}
\LWR@loadafter{everypage}
\LWR@loadafter{everyshi}
\LWR@loadafter{extramarks}
\LWR@loadafter{fancybox}
\LWR@loadafter{fancyhdr}
\LWR@loadafter{fancyheadings}
\LWR@loadafter{fancyref}
\LWR@loadafter{fancytabs}
\LWR@loadafter{fancyvrb}
\LWR@loadafter{figcaps}
\LWR@loadafter{figsize}
\LWR@loadafter{fitbox}
\LWR@loadafter{fix2col}
\LWR@loadafter{fixme}
\LWR@loadafter{fixmetodonotes}
\LWR@loadafter{flafter}
\LWR@loadafter{flippdf}
\LWR@loadafter{float}
\LWR@loadafter{floatflt}
\LWR@loadafter{floatpag}
\LWR@loadafter{floatrow}
\LWR@loadafter{fltrace}
```

```
\LWR@loadafter{flushend}
\LWR@loadafter{fnbreak}
\LWR@loadafter{fncychap}
\LWR@loadafter{fnlineno}
\LWR@loadafter{fnpara}
\LWR@loadafter{fnpos}
\LWR@loadafter{fontawesome}
\LWR@loadafter{fontawesome5}
% fontenc must be loaded before lwarp
% fontspec must be loaded before lwarp
\LWR@loadafter{footmisc}
\LWR@loadafter{footnote}
\LWR@loadafter{footnotebackref}
\LWR@loadafter{footnotehyper}
\LWR@loadafter{footnoterange}
\LWR@loadafter{footnpag}
\LWR@loadafter{foreign}
\LWR@loadafter{forest}
\LWR@loadafter{framed}
\LWR@loadafter{ftnright}
\LWR@loadafter{fullminipage}
\LWR@loadafter{fullpage}
\LWR@loadafter{fullwidth}
\LWR@loadafter{fwlw}
\LWR@loadafter{gentombow}
% geometry is always loaded by lwarp, and lwarp-geometry is AtBeginDocument
\LWR@loadafter{gmeometric}
\LWR@loadafter{glossaries}
% \LWR@loadafter{graphics}% pre-loaded by xunicode
% \LWR@loadafter{graphicx}% pre-loaded by xunicode
\LWR@loadafter{gloss}
\LWR@loadafter{glossary}
\LWR@loadafter{grffile}
\LWR@loadafter{grid}
\LWR@loadafter{grid-system}
\LWR@loadafter{gridset}
\LWR@loadafter{hang}
\LWR@loadafter{hanging}
\LWR@loadafter{hypcap}
\LWR@loadafter{hypdestopt}
\LWR@loadafter{hypernat}
\LWR@loadafter{hyperref}
\LWR@loadafter{hyperxmp}
\LWR@loadafter{hyphenat}
\LWR@loadafter{idxlayout}
\LWR@loadafter{ifoddpage}
\LWR@loadafter{imakeidx}
\LWR@notmemoirloadafter{index}
% inputenc must be loaded before lwarp
% inputenx must be loaded before lwarp
\LWR@loadafter{intopdf}
\LWR@loadafter{karnaugh-map}
\LWR@loadafter{keyfloat}
\LWR@loadafter{layaureo}
\LWR@loadafter{layout}
```

```
\LWR@loadafter{layouts}
\LWR@loadafter{leading}
\LWR@loadafter{letterspace}
\LWR@loadafter{lettrine}
\LWR@loadafter{lineno}
\LWR@loadafter{lips}
\LWR@loadafter{listings}
\LWR@loadafter{longtable}
\LWR@loadafter{lscape}
\LWR@loadafter{ltablex}
\LWR@loadafter{ltcaption}
\LWR@loadafter{ltxgrid}
\LWR@loadafter{ltxtable}
\LWR@loadafter{lua-check-hyphen}
\LWR@loadafter{lua-visual-debug}
\LWR@loadafter{luacolor}
\LWR@loadafter{luatodonotes}
\LWR@loadafter{magaz}
\LWR@notmemoirloadafter{makeidx}
\LWR@loadafter{manyfoot}
\LWR@loadafter{marginfit}
\LWR@loadafter{marginfix}
\LWR@loadafter{marginnote}
\LWR@loadafter{marvosym}
\LWR@loadafter{mcaption}
\LWR@loadafter{mdframed}
\LWR@loadafter{memhfixc}
\LWR@loadafter{metalogo}
\LWR@loadafter{mhchem}
\LWR@loadafter{microtype}
\LWR@loadafter{midfloat}
\LWR@loadafter{midpage}
% morefloats must be allowed early for print mode
\LWR@notmemoirloadafter{moreverb}
% morewrites must be loaded before lwarp
\LWR@notmemoirloadafter{mparhack}
\LWR@loadafter{multicap}
%\LWR@loadafter{multicol}% loaded by ltxdoc
\LWR@loadafter{multicolrule}
\LWR@loadafter{multirow}
\LWR@loadafter{multitoc}
\LWR@loadafter{musicography}
\LWR@loadafter{nameauth}
\LWR@loadafter{nameref}
\LWR@loadafter{natbib}
\LWR@notmemoirloadafter{nccfancyhdr}
\LWR@notmemoirloadafter{needspace}
% newclude must be loaded before lwarp
\LWR@loadafter{newtxmath}
% newunicodechar must be loaded before lwarp
\LWR@notmemoirloadafter{nextpage}
\LWR@loadafter{nicefrac}
\LWR@loadafter{niceframe}
\LWR@loadafter{nomencl}
\LWR@loadafter{nonfloat}
```

```
\LWR@loadafter{nonumonpart}
\LWR@loadafter{nopageno}
\LWR@loadafter{notes}
\LWR@loadafter{notespages}
\LWR@loadafter{nowidow}
\LWR@loadafter{ntheorem}
\LWR@loadafter{octave}
\LWR@loadafter{overpic}
\LWR@loadafter{pagegrid}
\LWR@notmemoirloadafter{pagenote}
\LWR@loadafter{pagesel}
\LWR@loadafter{paralist}
\LWR@loadafter{parnotes}
\LWR@notmemoirloadafter{parskip}
\LWR@loadafter{pbox}
\LWR@loadafter{pdfcomment}
\LWR@loadafter{pdflscape}
\LWR@loadafter{pdfmarginpar}
\LWR@loadafter{pdfpages}
\LWR@loadafter{pdfprivacy}
\LWR@loadafter{pdfrender}
\LWR@loadafter{pdfsync}
\LWR@loadafter{pdftricks}
\LWR@loadafter{pdfx}
\LWR@loadafter{perpage}
\LWR@loadafter{pfnote}
\LWR@loadafter{phfqit}
\LWR@loadafter{pifont}
\LWR@loadafter{placeins}
\LWR@loadafter{plarray}
\LWR@loadafter{plarydshln}
\LWR@loadafter{plextarray}
\LWR@loadafter{plextarydshln}
\LWR@loadafter{plcolortbl}
\LWR@loadafter{plextdelarray}
\LWR@loadafter{prelim2e}
\LWR@loadafter{prettyref}
\LWR@loadafter{preview}
\LWR@loadafter{psfrag}
\LWR@loadafter{psfragx}
\LWR@loadafter{pst-eps}
\LWR@loadafter{pstool}
\LWR@loadafter{pstricks}
% \LWR@loadafter{pxatbegshi}% may be used by morewrites
\LWR@loadafter{pxeveryshi}
\LWR@loadafter{pxftnright}
\LWR@loadafter{pxjahyper}
\LWR@loadafter{quotchap}
\LWR@loadafter{quoting}
\LWR@loadafter{ragged2e}
\LWR@loadafter{realscripts}
\LWR@loadafter{refcheck}
\LWR@loadafter{register}
\LWR@loadafter{relsize}
\LWR@loadafter{repeatindex}
```

```
\LWR@loadafter{resizegather}
\LWR@loadafter{rmpage}
\LWR@loadafter{romanbar}
\LWR@loadafter{romanbarpagenumber}
\LWR@loadafter{rotating}
\LWR@loadafter{rotfloat}
\LWR@loadafter{rviewport}
\LWR@loadafter{savetrees}
% scalefnt is loaded by babel-french
\LWR@loadafter{schemata}
\LWR@loadafter{scrextend}
\LWR@loadafter{scrhack}
\LWR@loadafter{scrlayer}
\LWR@loadafter{scrlayer-notecolumn}
\LWR@loadafter{scrlayer-scrpage}
\LWR@loadafter{scrpage2}
\LWR@loadafter{section}
\LWR@loadafter{sectionbreak}
\LWR@loadafter{sectsty}
\LWR@loadafter{semantic-markup}
\LWR@notmemoirloadafter{setspace}
\LWR@loadafter{shadow}
\LWR@notmemoirloadafter{showidx}
\LWR@loadafter{showkeys}
\LWR@loadafter{showtags}
\LWR@loadafter{sidecap}
\LWR@loadafter{sidenotes}
\LWR@loadafter{SIunits}
\LWR@loadafter{siunitx}
\LWR@loadafter{soul}
\LWR@loadafter{soulpos}
\LWR@loadafter{soulutf8}
\LWR@loadafter{splitidx}
\LWR@loadafter{srcltx}
\LWR@loadafter{srctex}
\LWR@loadafter{stabular}
\LWR@notltjloadafter{stfloats}
\LWR@loadafter{struktex}
\LWR@loadafter{subcaption}
\LWR@loadafter{subfig}
\LWR@loadafter{subfigure}
\LWR@loadafter{supertabular}
\LWR@loadafter{t1inc}
\LWR@loadafter{tabls}
\LWR@loadafter{tablefootnote}
\LWR@notmemoirloadafter{tabularx}
\LWR@loadafter{tabulary}
\LWR@loadafter{tascmac}
\LWR@loadafter{textarea}
% \LWR@loadafter{textcomp}% maybe before lwarp with font packages
\LWR@loadafter{textfit}
\LWR@loadafter{textpos}
\LWR@loadafter{theorem}
\LWR@loadafter{thinsp}
\LWR@loadafter{threadcol}
```

```
\LWR@loadafter{threeparttable}
\LWR@loadafter{threeparttablex}
\LWR@loadafter{thumb}
\LWR@loadafter{thumbs}
\LWR@loadafter{tikz}
\LWR@loadafter{titleps}
\LWR@loadafter{titlesec}
\LWR@loadafter{titletoc}
\LWR@notmemoirloadafter{titling}
% \LWR@loadafter{tocbasic}% preloaded by koma-script classes
\LWR@notmemoirloadafter{tocbibind}
\LWR@loadafter{tocenter}
\LWR@notmemoirloadafter{tocloft}
\LWR@loadafter{tocstyle}
\LWR@loadafter{todo}
\LWR@loadafter{todonotes}
\LWR@loadafter{tram}
\LWR@loadafter{transparent}
\LWR@loadafter{trimclip}
\LWR@loadafter{trivfloat}
\LWR@loadafter{truncate}
\LWR@loadafter{turnthepage}
\LWR@loadafter{twoup}

% \LWR@loadafter{typearea}% preloaded by koma-script classes
\LWR@loadafter{typicons}
% \LWR@loadafter{ulem}% preloaded by ctexart and related classes
\LWR@loadafter{umoline}
\LWR@loadafter{underscore}
\LWR@loadafter{units}
\LWR@loadafter{unitsdef}
\LWR@loadafter{upref}
\LWR@loadafter{url}
\LWR@loadafter{uspace}
\LWR@loadafter{varioref}% no lwarp package provided
\LWR@notmemoirloadafter{verse}
\LWR@loadafter{versonotes}
\LWR@loadafter{vertbars}
\LWR@loadafter{vmargin}
\LWR@loadafter{vowel}
\LWR@loadafter{vpe}
\LWR@loadafter{vwcol}
\LWR@loadafter{wallpaper}
\LWR@loadafter{watermark}
\LWR@loadafter{widows-and-orphans}
\LWR@loadafter{wrapfig}
\LWR@loadafter{xbmks}
\LWR@loadafter{xcolor}
\LWR@loadafter{xechangebar}
\LWR@loadafter{xellipsis}
% xetexko-vertical must be loaded before lwarp
\LWR@loadafter{xfakebold}
\LWR@loadafter{xfrac}
\LWR@loadafter{xltabular}
\LWR@loadafter{xltxtra}
```

```
\LWR@loadafter{xmpincl}
\LWR@loadafter{xpiano}
\LWR@loadafter{xpinyin}
\LWR@loadafter{xtab}
% xunicode must be loaded before lwarp
\LWR@loadafter{xurl}
\LWR@loadafter{xy}
\LWR@loadafter{zwpagelayout}
```

22 MD5 hashing

The MD5 hash is used for `lateximage` filenames for SVG math.

```
\newcommand{\LWR@mdfive}[1]{%
\PackageError{lwarp}
{No MD5 macro was found}
{Lwarp must find the macros pdfmdfivesum or mdfivesum.}
}
```

The default for pdfLaTeX, DVILaTeX, upLaTeX, etc:

```
\let\LWR@mdfive\pdfmdfivesum
```

For LuaLaTeX:

```
\ifLuaTeX
\RequirePackage{pdftexcmds}
\let\LWR@mdfive\pdf@mdfivesum
\fi
```

For XeLaTeX:

```
\ifXeTeX
\@ifundefined{pdffivesum}{}
    {\let\LWR@mdfive\pdfmdfivesum}
\@ifundefined{mdfivesum}{}
    {\let\LWR@mdfive\mdfivesum}
\fi
```

23 pdfLaTeX T1 and UTF-8 encoding

When using pdfLaTeX, lwarp requires T1 encoding, and recommends UTF-8 encoding.

If some other input encoding is already defined, lwarp will try to use it instead, and hope for the best.

XeLaTeX and LuaLaTeX are both UTF-8 by nature.

\LWR@pdfencoding Sets T1, and also utf8 if not already set.

```
\newcommand*{\LWR@pdfencoding}{%
    \RequirePackage[T1]{fontenc}

    \@ifpackageloaded{inputenc}{}{
        \@ifpackageloaded{inputenx}{}{
            \RequirePackage[utf8]{inputenc}
        }
    }
}

\ifPDFTeX% pdflatex or dvi latex
    \LWR@pdfencoding
\fi

\ifpTeX
    \LWR@pdfencoding
\fi
```

24 Unicode input characters

for HTML & PRINT: If using *pdflatex*, convert a minimal set of Unicode characters. Additional characters may be defined by the user, as needed.

A commonly-used multiply symbol is declared to be \texttimes.

The first arguments of \newunicodechar below are text ligatures in the source code, even though they are not printed in the following listing.

```
\ifpTeX
\else
\RequirePackage{newunicodechar}

\newunicodechar{×}{\texttimes}

\ifPDFTeX% pdflatex or dvi latex
\newunicodechar{ff}{ff}% the first arguments are ligatures
\newunicodechar{fi}{fi}
\newunicodechar{fl}{fl}
\newunicodechar{ffi}{ffi}
\newunicodechar{ffl}{ffl}
\newunicodechar{---}{---}
\newunicodechar{--}{--}
\fi

\fi
```

25 Upright quotes

In PDFTEX, preserve upright quotes in verbatim text. upquote also loads textcomp.

```
\ifPDFTeX
\RequirePackage{upquote}
\fi

\ifpTeX
    \RequirePackage{upquote}
\fi
```

26 Miscellaneous tools

\LWR@providelength {⟨\lengthname⟩} Provides the length if it isn't defined yet.

Used to provide source compatibility for lengths which will be ignored, but might or might not be already provided by other packages.

```
\newcommand*\LWR@providelength[1]{%
    \ifdeflength{#1}{}{\newlength{#1}}%
}
```

Prints a length in the given units, without printing the unit itself.

\LWR@convertto {⟨*dest unit*⟩} {⟨*length*⟩}

```
\newcommand*{\LWR@convertto}[2]{\strip@pt\dimexpr #2*65536/\number\dimexpr 1#1}
```

\LWR@patcherror {⟨*packagename*⟩} {⟨*macroname*⟩}

Prints an error if could not patch a macro.

```
\newcommand*{\LWR@patcherror}[2]{%
\PackageError{lwarp}
{Unable to patch package #1, macro #2}
{Please contact the author of the lwarp package.}
}
```

\LWR@isolate {⟨*text*⟩} Isolates Chinese characters from the surrounding text. This is required to avoid extra spaces on either side of the Chinese characters, especially when written to a file.

```
\newcommand{\LWR@isolate}[1]{#1}%

\@ifpackageloaded{ctexpatch}{
    \renewcommand{\LWR@isolate}[1]{\null#1\null}%
```

```
}{}

\@ifpackageloaded{xeCJK}{
    \renewcommand{\LWR@isolate}[1]{\null#1\null}%
}{}
```

\LWR@firstoffour {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩}

\LWR@secondoffour {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩}

\LWR@thirdoffour {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩}

\LWR@fourthoffour {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩}

Expands to the nth of the four arguments. Used for extra cross referencing.

```
\long\def\LWR@firstoffour#1#2#3#4{#1}
\long\def\LWR@secondoffour#1#2#3#4{#2}
\long\def\LWR@thirdoffour#1#2#3#4{#3}
\long\def\LWR@fourthoffour#1#2#3#4{#4}
```

27 Operating-System portability

Prog Unix
Prog Mac OS
Prog Linux

lwarp tries to detect which operating system is being used. UNIX / MAC OS / LINUX is the default (collectively referred to as "UNIX" in the configuration files), and MS-WINDOWS is supported as well.

Prog MS-Windows
Prog Windows

If MS-WINDOWS is not correctly detected, use the lwarp option `OSWindows`.

Opt OSWindows

When detected or specified, the operating-system path separator used by lwarp is modified, and the boolean `usingOSWindows` is set `true`. This boolean may be tested by the user for later use.

27.1 Literal characters

Literal characters to be used in `PrintLatexCmd` and `HTMLLatexCmd`. These are defined without `@` to easily allow their inclusion in the user's document.

The literal `%` character:

```
\let\LWRpercent\@percentchar
```

The literal `$` character:

```
\catcode`\$=12
\def\LWRdollar{$}
\catcode`\$=3
```

The literal & character:

```
\catcode`\&=12
\def\LWRamp{&}
\catcode`\&=4
```

The literal \ character. The ampersand is temporarily set to the escape character during the definition of the backslash macro.

```
\catcode`\&=0
&catcode`&\=12
&def&LWRbackslash{\}
&catcode`&\=0
\catcode`\&=4
```

The literal { character. The ampersand is temporarily set to the begin group character during the definition of the leftbrace macro.

```
\catcode`\&=1
\catcode`\{=12
\def\LWRleftbrace&{}
\catcode`\{=1
\catcode`\&=4
```

The literal } character. The ampersand is temporarily set to the end group character during the definition of the leftbrace macro.

```
\catcode`\&=2
\catcode`\}=12
\def\LWRrightbrace{}&
\catcode`\}=2
\catcode`\&=4
```

The literal # character:

```
\catcode`\#=12
\def\LWRhash{#}
\catcode`\#=6
```

`\LWRopquote` The operating system's quote mark, UNIX default. For WINDOWS, see `\LWR@setOSWindows`, below.

```
\def\LWRopquote{'}
```

`\LWRopseq` The operating system's sequential execution command, UNIX default. For WINDOWS, see `\LWR@setOSWindows`, below.

```
\def\LWRopseq{\space\LWRamp\LWRamp\space\space}
```

27.2 Common portability code

Bool usingOSWindows Set if the OSWindows option is used, or if WINDOWS is automatically detected.

```
\newbool{usingOSWindows}
\boolfalse{usingOSWindows}
```

27.3 UNIX, LINUX, and MAC OS

\OSPathSymbol Symbol used to separate directories in a path.

```
\newcommand*{\OSPathSymbol}{/}
```

27.4 MS-WINDOWS

For MS-WINDOWS:

\LWR@setOSWindows Set defaults for the MS-WINDOWS operating system. lwarp attempts to auto-detect the operatings system, and the OSWindows option may also be used to force MS-WINDOWS compatibility.

```
\newcommand*{\LWR@setOSWindows}
{
\booltrue{usingOSWindows}
\renewcommand*{\OSPathSymbol}{\@backslashchar}
\def\LWRopquote{"}
\def\LWRopseq{\space\LWRamp\space\space}
}
```

Test for windows during compile. The user may also specify OSWindows package option in case this test fails.

```
\ifwindows
\LWR@setOSWindows
\fi
```

28 Package options

Pkg kvoptions Allows key/value package options.

```
\RequirePackage{kvoptions}
\SetupKeyvalOptions{family=LWR,prefix=LWR@}
```

\lwarpsetup A user interface to set the keys:

```
\newcommand{\lwarpsetup}[1]{\setkeys{LWR}{#1}}
```

Bool warpingprint
Bool warpingHTML
Bool mathjax
Bool LWR@origmathjax

Set to true/false depending on the package option selections for print/HTML/EPUB output and mathsvg/mathjax.

LWR@origmathjax remembers the original setting to be restored by \displaymathnormal.

```
\newbool{warpingprint}
\newbool{warpingHTML}
\newbool{mathjax}
\newbool{LWR@origmathjax}
```

defaults The default is print output, and SVG math if the user chose HTML output.

```
\booltrue{warpingprint}%
\boolfalse{warpingHTML}%
\boolfalse{mathjax}%
```

Opt warpprint If the warpprint option is given, boolean warpingprint is true and boolean warpingHTML is false, and may be used for \ifbool tests.

```
\DeclareVoidOption{warpprint}{%
\PackageInfo{lwarp}{Using option 'warpprint'}
\booltrue{warpingprint}%
\boolfalse{warpingHTML}%
}
```

Opt warpHTML Anything in the warpHTML environment will be generated for HTML output only.

Opt warpHTML If the warpHTML option is given, boolean warpingHTML is true and boolean warpingprint is false, and may be used for \ifbool tests.

```
\DeclareVoidOption{warpHTML}{%
\PackageInfo{lwarp}{Using option 'warpHTML'}%
\booltrue{warpingHTML}%
\boolfalse{warpingprint}%
}
```

Opt mathsvg Option mathsvg selects SVG math display: If the mathsvg option is given, boolean mathjax is false, and may be used for \ifbool tests.

```
\DeclareVoidOption{mathsvg}{%
\PackageInfo{lwarp}{Using option 'mathsvg'}
\boolfalse{mathjax}%
\boolfalse{LWR@origmathjax}%

}
```

Opt mathjax

Option mathjax selects MathJax math display: If the mathjax option is given, boolean mathjax is true, may be used for \ifbool tests.

```
\DeclareVoidOption{mathjax}{%
\PackageInfo{lwarp}{Using option 'mathjax'}
\booltrue{mathjax}%
\booltrue{LWR@origmathjax}%
}
```

Opt BaseJobname
Default: \jobname

Option BaseJobname sets the \BaseJobname for this document.

This is the \jobname of the printed version, even if currently compiling the HTML version. I.e. this is the \jobname without _html appended. This is used to set \HomeHTMLFilename if the user did not provide one.

```
\DeclareStringOption[\jobname]{BaseJobname}
```

Opt ImagesDirectory
Default: \jobname-images

Option ImagesDirectory sets the name of the directory to use for the lateximage images.

```
\DeclareStringOption[\BaseJobname-images]{ImagesDirectory}
```

Opt ImagesName
Default: image-

Option ImagesName sets the prefix to use for the lateximage images.

```
\DeclareStringOption[image-]{ImagesName}
```

Opt makeindexStyle
Default: lwarp.ist

Selects a custom .ist file. A customized file should be based on lwarp.ist, and must retain the lines related to \hyperindexref.

```
\DeclareStringOption[lwarp.ist]{makeindexStyle}
```

Opt xindyStyle
Default: lwarp.xdy

Selects a custom .xdy file. A customized file should be based on lwarp.xdy, and must retain the line

```
(markup-locref :open "\hyperindexref{" :close "}")
```

```
\DeclareStringOption[lwarp.xdy]{xindyStyle}
```

Opt xindyLanguage
Default: english

Sets the xindy language to be assigned in *lwarpmk*'s configuration files. This is then used by *lwarpmk* while processing the index and glossary.

```
\DeclareStringOption[english]{xindyLanguage}
```

Opt xindyCodepage
Default: utf8

Sets the xindy codepage to be assigned in *lwarpmk*'s configuration files. This is then used by *lwarpmk* while processing the index.

```
\DeclareStringOption[utf8]{xindyCodepage}
```

Opt pdftotextEnc
Default: UTF-8

The option pdftotextEnc sets the encoding used by *pdftotext*. This is passed to *pdftotext* using its -enc option, and is used when converting LaTeX PDF output with HTML tags into a plain-text file with HTML tags.

```
\DeclareStringOption[UTF-8]{pdftotextEnc}
```

Opt lwarpmk

Tells lwarp to generate a local copy of *lwarpmk* called lwarpmk.lua. Useful for archiving for future use. This file may be made executable and acts just like *lwarpmk*.

If lwarpmk option, creates a local copy of lwarpmk.lua:

```
\newbool{LWR@creatinglwarpmk}
\boolfalse{LWR@creatinglwarpmk}

\DeclareVoidOption{lwarpmk}{
\PackageInfo{lwarp}{Using option 'lwarpmk'}
\booltrue{LWR@creatinglwarpmk}
}
```

Opt OSWindows

Tells lwarp to use MS-Windows compatibility. Auto-detection of the operating system is attempted, and this option is only necessary if the auto-detection fails. See the automatically-generated lwarpmk.conf file to find out whether the operating system was detected correctly.

```
\DeclareVoidOption{OSWindows}{
\PackageInfo{lwarp}{Using option 'OSWindows'}
\LWR@setOSWindows
}
```

Opt HomeHTMLFilename
Default: \BaseJobname

The filename of the homepage. The default is the jobname. This option is stored into \LWR@HomeHTMLFilename, and later transferred into \HomeHTMLFilename for internal use.

```
\DeclareStringOption[]{HomeHTMLFilename}
```

Opt HTMLFilename
Default: <empty>

The filename prefix of web pages after the homepage. The default is empty, no prefix. This option is stored into \LWR@HTMLFilename, and later transferred into \HTMLFilename for internal use.

```
\DeclareStringOption[]{HTMLFilename}
```

Opt PrintLatexCmd
Default: <automatic>

The shell commands to use to compile the print document.

```
\DeclareStringOption[]{PrintLatexCmd}
```

Opt HTMLLatexCmd
Default: <automatic>

The shell commands to use to compile the HTML document.

```
\DeclareStringOption[]{HTMLLatexCmd}
```

Opt PrintIndexCmd
Default: <empty>

The shell commands to use to compile the print indexes.

```
\DeclareStringOption[]{PrintIndexCmd}
```

Opt HTMLIndexCmd
Default: <empty>

The shell commands to use to compile the HTML indexes.

```
\DeclareStringOption[]{HTMLIndexCmd}
```

Opt LatexmkIndexCmd
Default: <empty>

The shell commands to by used by *latexmk* to compile the print indexes. Unlike PrintIndexCmd and HTMLIndexCmd, LatexmkIndexCmd does not include the filename, which will be provided by *latexmk*.

```
\DeclareStringOption[]{LatexmkIndexCmd}
```

Opt makeindex

Tells lwarp to use makeindex for index generation. When lwarpmk.conf and *.lwarpmkconf are generated, PrintIndexCmd and HTMLIndexCmd will be set for *makeindex* with a single index file.

```
\DeclareBoolOption[false]{makeindex}
```

Opt xindy

Tells lwarp to use xindy for index generation. When lwarpmk.conf and *.lwarpmkconf are generated, PrintIndexCmd and HTMLIndexCmd will be set for *xindy* with a single index file.

```
\DeclareBoolOption[false]{xindy}
```

Opt GlossaryCmd
Default: makeglossaries

The shell command to use to compile the glossary. The print or HTML version of the glossary filename will be appended to this command.

```
\DeclareStringOption[makeglossaries]{GlossaryCmd}
```

Opt latexmk

Option latexmk tells *lwarpmk* to use *latexmk* when compiling documents.

```
\DeclareBoolOption[false]{latexmk}
```

Opt dvips

Option dvips tells *lwarpmk* to use *dvips* when compiling DVI *latex* documents.

```
\DeclareBoolOption[false]{dvips}
```

Opt dvipdfm

Option dvipdfm tells *lwarpmk* to use *dvipdfm* when compiling DVI *latex* documents.

```
\DeclareBoolOption[false]{dvipdfm}
```

Opt dvipdfmx

Option dvipdfmx tells *lwarpmk* to use *dvipdfmx* when compiling DVI *latex* documents.

```
\DeclareBoolOption[false]{dvipdfmx}
```

Execute options

Execute the package options, with the defaults which have been set just above:

```
\ProcessKeyvalOptions*\relax
```

28.1 Additional options support

Assign the \BaseJobname if the user hasn't provided one:

```
\providecommand*{\BaseJobname}{\LWR@BaseJobname}
```

Defaults unless already over-ridden by the user:

```
\ifcsempty{LWR@HomeHTMLFilename}{
    \newcommand*{\HomeHTMLFilename}{\BaseJobname}
}{
    \csedef{HomeHTMLFilename}{\LWR@HomeHTMLFilename}
}

\csedef{HTMLFilename}{\LWR@HTMLFilename}
```

Special handling for underscores in labels and filenames.

\LWR@sanitized The sanitized version of what was given to \LWR@sanitize. Characters are set to their detokenized versions. Required for underscores in labels and filenames.

```
\newcommand*{\LWR@sanitized}{}
```

\LWR@sanitize {⟨*text*⟩}

Sanitizes the text and returns the result in \LWR@sanitized.

```
\newcommand*{\LWR@sanitize}[1]{%
\edef\LWR@sanitized{#1}%
\edef\LWR@sanitized{\detokenize\expandafter{\LWR@sanitized}}%
}
```

Sanitize some string options to neutralize underscores.

```
\LWR@sanitize{\LWR@BaseJobname}
\edef\LWR@BaseJobname{\LWR@sanitized}

\LWR@sanitize{\LWR@ImagesDirectory}
\edef\LWR@ImagesDirectory{\LWR@sanitized}

\LWR@sanitize{\LWR@ImagesName}
\edef\LWR@ImagesName{\LWR@sanitized}
```

\LWR@PrintIndexCmd and \LWR@HTMLIndexCmd are tested to see if they are empty. If so, they are set to a reasonable defaults for a single index using *makeindex*, then possibly set to defaults for *xindy* if the lwarp xindy option was selected.

```
\ifdefempty{\LWR@PrintIndexCmd}{
    \renewcommand{\LWR@PrintIndexCmd}{%
        makeindex  -s \LWR@makeindexStyle \space  \jobname.idx%
    }
    \ifbool{LWR@xindy}{
```

```
        \renewcommand{\LWR@PrintIndexCmd}{%
            xindy
            -M \LWR@xindyStyle \space
            -L \LWR@xindyLanguage \space
            -C \LWR@xindyCodepage \space
            \jobname.idx%
        }
    }{}
}{}

\ifdefempty{\LWR@HTMLIndexCmd}{
    \renewcommand{\LWR@HTMLIndexCmd}{%
        makeindex  -s \LWR@makeindexStyle \space  \jobname_html.idx%
    }
    \ifbool{LWR@xindy}{
        \renewcommand{\LWR@HTMLIndexCmd}{%
            xindy
            -M \LWR@xindyStyle \space
            -L \LWR@xindyLanguage \space
            -C \LWR@xindyCodepage \space
            \jobname_html.idx%
        }
    }{}
}{}

\ifdefempty{\LWR@LatexmkIndexCmd}{
    \renewcommand{\LWR@LatexmkIndexCmd}{%
        makeindex  -s \LWR@makeindexStyle%
    }
    \ifbool{LWR@xindy}{
        \renewcommand{\LWR@LatexmkIndexCmd}{%
            xindy
            -M \LWR@xindyStyle \space
            -L \LWR@xindyLanguage \space
            -C \LWR@xindyCodepage%
        }
    }{}
}{}
```

28.2 Conditional compilation

\warpprintonly {⟨*contents*⟩}

Only process the contents if producing printed output.

```
\newcommand{\warpprintonly}[1]{\ifbool{warpingprint}{#1}{}}
```

\warpHTMLonly {⟨*contents*⟩}

Only process the contents if producing HTML output.

```
\newcommand{\warpHTMLonly}[1]{\ifbool{warpingHTML}{#1}{}}
```

Pkg comment Provides conditional code blocks.

Attempts to use versions or verbatim fail in some cases, and do not provide much of a speed benefit even when they do work.

```
\RequirePackage{comment}
```

Use `comment_print.cut` for print mode, and `comment_html.cut` for HTML mode. This helps *latexmk* to more reliably know whether to recompile.

```
\ifbool{warpingHTML}{
\def\DefaultCutFileName{\def\CommentCutFile{comment_html.cut}}
}{}

\ifbool{warpingprint}{
\def\DefaultCutFileName{\def\CommentCutFile{comment_print.cut}}
}{}
```

Env warpall Anything in the `warpall` environment will be generated for print or HTML outputs.

```
\includecomment{warpall}
```

Env warpprint Anything in the `warpprint` environment will be generated for print output only.

Env warpHTML

For HTML output:

```
\ifbool{warpingHTML}
{\includecomment{warpHTML}}
{\excludecomment{warpHTML}}%

\ifbool{warpingprint}
{\includecomment{warpprint}}
{\excludecomment{warpprint}}
```

Optionally generate a local copy of *lwarpmk*. Default to no.

```
\ifbool{LWR@creatinglwarpmk}
{\includecomment{LWR@createlwarpmk}}
{\excludecomment{LWR@createlwarpmk}}
```

29 Required packages

These packages are automatically loaded by lwarp when generating HTML output. Some of them are also automatically loaded when generating print output, but some are not.

for HTML output:

```
\begin{warpHTML}
```

Load fontspec if necessary:

```
\ifxetexorluatex
\@ifpackageloaded{fontspec}{}{
    \usepackage[no-math]{fontspec}
}
```

The monospaced font is used for HTML tags, so turn off its TeX ligatures and common ligatures:

```
\defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
\else
```

pdflatex only: Only pre-loaded if *pdflatex* is being used.

Pkg microtype

ligatures Older browsers don't display ligatures. Turn off letter ligatures, keeping LaTeX dash and quote ligatures, which may fail on older browers but at least won't corrupt written words.

```
\RequirePackage {microtype}

\microtypesetup{
    protrusion=false,
    expansion=false,
    tracking=false,
    kerning=false,
    spacing=false}

\DisableLigatures[f,q,t,T,Q]{encoding = *,family = *}

\fi

\end{warpHTML}
```

Pkg geometry Tactics to avoid unwanted page breaks and margin overflow:

- Uses a very long and wide page to minimize page breaks and margin overflow.
- Uses a scriptsize font.
- Uses extra space at the margin to avoid HTML tag overflow off the page.
- Forces a new PDF page before some environments.
- Forces line break between major pieces of long tags.

for HTML output:

```
\begin{warpHTML}

\RequirePackage{geometry}
```

Avoid class and option conflict by changing settings after package load:

```
\geometry{
    paperheight=190in,%
    paperwidth=20in,%
    left=2in,right=6in,%
    top=1in,bottom=1in,%
}
```

ltjtarticle and other classes may require these to be reset by lwarp:

```
\setlength{\textheight}{0.8\paperheight}
\setlength{\textwidth}{0.7\paperwidth}

\@twosidefalse
\@mparswitchfalse

\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Pkg xparse

LaTeX3 command argument parsing

```
\RequirePackage{xparse}
```

Pkg calc

```
\RequirePackage{calc}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Pkg expl3

LaTeX3 programming

```
\RequirePackage{expl3}
```

Pkg gettitlestring

Used to emulate \nameref.

```
\RequirePackage{gettitlestring}
```

Pkg everyhook

everyhook is used to patch paragraph handling.

```
\@ifundefined{bxjs@everypar}{}{\let\everypar\bxjs@everypar}

```

```
\RequirePackage{everyhook}
\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Pkg filecontents

Used to write helper files, done in print mode.

Patched to work with morewrites, per https://tex.stackexchange.com/questions/312830/does-morewrites-not-support-filecontents-and-can-i-write-body-of-environment-us/312910

```
\RequirePackage{filecontents}

\@ifpackagelater{filecontents}{2011/10/09}%
{}
{
\newwrite\fcwrite
\let\LWR@origfilec@ntents\filec@ntents
\def\filec@ntents{\def\chardef##1\write{\let\reserved@c\fcwrite}\LWR@origfilec@ntents}
}

\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Pkg xifthen

```
\RequirePackage{xifthen}
```

Pkg verbatim

```
\RequirePackage{verbatim}
```

Pkg refcount

Provides \setcounterref, \setcounterpageref, etc.

```
\RequirePackage{refcount}
```

Pkg newfloat

```
\RequirePackage{newfloat}

\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Pkg xstring

⚠ index

There was a short-term bug in xstring regarding \IfInteger which affected lwarp's index generation. The updated version is requested here.

```
\RequirePackage{xstring}[2019/02/01]
```

Pkg environ Used to encapsulate math environments for re-use in HTML <alt> text.

```
\RequirePackage{environ}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Pkg printlen Used to convert lengths for image width/height options.

```
\RequirePackage{printlen}
```

\LWR@printlength {⟨*length*⟩}

Prints a length using a locally-controlled unit and space. Rounding is used unless the length is small.

```
\newrobustcmd*{\LWR@printlength}[1]{%
\begingroup%
\uselengthunit{PT}%
\renewcommand*{\unitspace}{}%
\ifdimless{#1}{10pt}{%
    \printlength{#1}%
}{%
    \rndprintlength{#1}%
}%
\endgroup%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

Pkg varwidth Used for print-mode lateximage.

```
\RequirePackage{varwidth}
```

```
\end{warpprint}
```

30 Loading packages

for HTML & PRINT:

```
\begin{warpall}
```

Remember the original \RequirePackage:

```
\LetLtxMacro\LWR@origRequirePackage\RequirePackage
```

\LWR@requirepackagenames Stores the list of required package names.

```
\newcommand*{\LWR@requirepackagenames}{}
```

\LWR@parsedrequirepackagenames Stores the parsed list of required package names after spaces are removed and `lwarp-` is prepended.

```
\newcommand*{\LWR@parsedrequirepackagenames}{}
```

\LWR@nullifycomment Remove the preexisting `comment` environment. Certain packages define it for their own use.

```
\newcommand*{\LWR@nullifycomment}{%
    \PackageInfo{lwarp}%
       {Nullifying the comment environment before loading \LWR@strresulttwo,}%
    \let\comment\relax%
    \let\endcomment\relax%
}
```

\LWR@findword `[`⟨*1: separator*⟩`]` {⟨*2: list*⟩} {⟨*3: index*⟩} `[`⟨*4: destination*⟩`]`

Note that argument 4 is passed directly to `\StrBetween`.

```
\newcommand*\LWR@findword[3][,]{%
    \StrBetween[#3,\numexpr#3+1]{#1#2#1}{#1}{#1}%
}
```

\LWR@checkloadfilename {⟨*filename*⟩} Checks if this filename should be loaded after lwarp, or never at all.

The following should never be loaded:

```
\newcommand*{\LWR@checkloadfilename}[1]{%
\LWR@checkloadnever{#1}{ae}{latinmodern}
\LWR@checkloadnever{#1}{aecc}{latinmodern}
\LWR@checkloadnever{#1}{alg}{algorithm2e, algorithmicx}
\LWR@checkloadnever{#1}{algorithmic}{algorithm2e, algorithmicx}
\LWR@checkloadnever{#1}{bitfield}{bytefield}
\LWR@checkloadnever{#1}{boxedminipage}{boxedminipage2e}
\LWR@checkloadnever{#1}{caption2}{caption}
\LWR@checkloadnever{#1}{ccaption}{caption}
\LWR@checkloadnever{#1}{colortab}{colortbl}
\LWR@checkloadnever{#1}{doublespace}{setspace}
\LWR@checkloadnever{#1}{epsf}{graphicx}
\LWR@checkloadnever{#1}{fancyheadings}{fancyhdr}
\LWR@checkloadnever{#1}{fncylab}{cleveref}
\LWR@checkloadnever{#1}{glossary}{glossaries}
\LWR@checkloadnever{#1}{hyper}{hyperref}
\LWR@checkloadnever{#1}{newthm}{ntheorem}
\LWR@checkloadnever{#1}{pdfcprot}{microtype}
\LWR@checkloadnever{#1}{picinpar}{floatflt, wrapfig}
\LWR@checkloadnever{#1}{picins}{floatflt, wrapfig}
\LWR@checkloadnever{#1}{rplain}{fancyhdr}
\LWR@checkloadnever{#1}{si}{siunitx}
\LWR@checkloadnever{#1}{sistyle}{siunitx}
\LWR@checkloadnever{#1}{t1enc}{fontenc, inputenc, inputenx}
\LWR@checkloadnever{#1}{ucs}{inputenc, inputencx}
\LWR@checkloadnever{#1}{wasysym}{textcomp, amssymb, amsfonts, mnsymbol, fdsymbol}
```

The following should only be loaded before lwarp:

```
\LWR@checkloadbefore{#1}{ctex}
\LWR@checkloadbefore{#1}{fontspec}
\LWR@checkloadbefore{#1}{inputenc}
\LWR@checkloadbefore{#1}{inputenx}
\LWR@checkloadbefore{#1}{kotex}
\LWR@checkloadbefore{#1}{luatexja}
\LWR@checkloadbefore{#1}{luatexja-fontspec}
\LWR@checkloadbefore{#1}{luatexko}
\LWR@checkloadbefore{#1}{morewrites}
\LWR@checkloadbefore{#1}{newclude}
\LWR@checkloadbefore{#1}{newunicodechar}
\LWR@checkloadbefore{#1}{plext}
\LWR@checkloadbefore{#1}{xeCJK}
\LWR@checkloadbefore{#1}{xetexko}
\LWR@checkloadbefore{#1}{zxjatype}
}
```

`\LWR@lookforpackagename` {⟨*index*⟩}

If HTML, and if this is an lwarp-supported package name, re-direct it to the lwarp version by renaming it `lwarp-` followed by the original name.

Looks `index` deep into the list of package names, `\LWR@requirepackagenames`, and builds `\LWR@parsedrequirepackagenames` which is the modified list of names.

```
\newcommand*{\LWR@lookforpackagename}[1]{%
```

Find the `index`'th package name from the list:

```
\LWR@findword{\LWR@requirepackagenames}{#1}[\LWR@strresult]%
```

Remove blanks. The original name with blanks is in `LWR@strresult` and the final name with no blanks goes into `LWR@strresulttwo`.

```
\StrSubstitute[100]{\LWR@strresult}{ }{}[\LWR@strresulttwo]%
```

See if the package name was found:

```
\IfStrEq{\LWR@strresulttwo}{}%
{}% no filename
{% yes filename was found
```

Possible adjustments before loading the package. Maybe nullify the `comment` environment if the new package will be redefining it for a new purpose.

```
    \ifdefstring{\LWR@strresulttwo}{easyReview}{\LWR@nullifycomment}{}%
```

If HTML, check if the package should be loaded before lwarp, or never at all:

```
    \ifbool{warpingHTML}{\LWR@checkloadfilename{\LWR@strresulttwo}}{}%
```

If HTML, and if found, and if an lwarp-equivalent name exists, use `lwarp-*` instead.

```
    \ifboolexpr{
        bool{warpingHTML} and
        test{\IfFileExists{lwarp-\LWR@strresulttwo.sty}}
    }%
    {% lwarp-* file found
        \ifdefvoid{\LWR@parsedrequirepackagenames}{%
            \edef\LWR@parsedrequirepackagenames{lwarp-\LWR@strresulttwo}%
        }{%
            \edef\LWR@parsedrequirepackagenames{%
                \LWR@parsedrequirepackagenames,lwarp-\LWR@strresulttwo%
            }%
        }%
    }%
    {%
```

Otherwise, use the current package name.

```
        \ifdefvoid{\LWR@parsedrequirepackagenames}{%
            \edef\LWR@parsedrequirepackagenames{\LWR@strresulttwo}%
        }{%
            \edef\LWR@parsedrequirepackagenames{%
                \LWR@parsedrequirepackagenames,\LWR@strresulttwo%
            }%
        }%
    }% no lwarp-* file
}% yes filename
}
```

\RequirePackage `[`⟨*1: options*⟩`]` `{`⟨*2: package names*⟩`}` `[`⟨*3: version*⟩`]`

For each of many package names in a comma-separated list, if an lwarp version of a package exists, select it instead of the LaTeX version.

```
\RenewDocumentCommand{\RequirePackage}{o m o}{%
```

Redirect up to twenty names:[16]

```
\renewcommand*{\LWR@requirepackagenames}{#2}%
\renewcommand*{\LWR@parsedrequirepackagenames}{}%
\LWR@lookforpackagename{1}%
\LWR@lookforpackagename{2}%
\LWR@lookforpackagename{3}%
\LWR@lookforpackagename{4}%
\LWR@lookforpackagename{5}%
\LWR@lookforpackagename{6}%
\LWR@lookforpackagename{7}%
\LWR@lookforpackagename{8}%
\LWR@lookforpackagename{9}%
\LWR@lookforpackagename{10}%
\LWR@lookforpackagename{11}%
```

[16] This was originally nine names, but then I came across a package which used twelve...

```
\LWR@lookforpackagename{12}%
\LWR@lookforpackagename{13}%
\LWR@lookforpackagename{14}%
\LWR@lookforpackagename{15}%
\LWR@lookforpackagename{16}%
\LWR@lookforpackagename{17}%
\LWR@lookforpackagename{18}%
\LWR@lookforpackagename{19}%
\LWR@lookforpackagename{20}%
```

\RequirePackage depending on the options and version:

```
\IfValueTF{#1}%
{% options given
    \IfValueTF{#3}% version given?
    {\LWR@origRequirePackage[#1]{\LWR@parsedrequirepackagenames}[#3]}%
    {\LWR@origRequirePackage[#1]{\LWR@parsedrequirepackagenames}}%
}%
{% no options given
    \IfValueTF{#3}% version given?
    {\LWR@origRequirePackage{\LWR@parsedrequirepackagenames}[#3]}%
    {\LWR@origRequirePackage{\LWR@parsedrequirepackagenames}}%
}%
}
\LetLtxMacro\usepackage\RequirePackage
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@ProvidesPackagePass {⟨*pkgname*⟩} [⟨*version*⟩]

Uses the original package, including options.

```
\NewDocumentCommand{\LWR@ProvidesPackagePass}{m o}{
\PackageInfo{lwarp}{Using package ‘#1’ and adding lwarp modifications, including options,}%
\IfValueTF{#2}
{\ProvidesPackage{lwarp-#1}[#2]}
{\ProvidesPackage{lwarp-#1}}
\DeclareOption*{\PassOptionsToPackage{\CurrentOption}{#1}}
\ProcessOptions\relax
\IfValueTF{#2}
{\LWR@origRequirePackage{#1}[#2]}
{\LWR@origRequirePackage{#1}}
```

In some cases, the following seems to be required to avoid an “unknown option” error, such as when loading xcolor with options.

```
\DeclareOption*{}%
\ProcessOptions\relax
}
```

\LWR@ProvidesPackageDrop {⟨*pkgname*⟩} [⟨*version*⟩]

Ignores the original package and uses lwarp's version instead. Drops/discards all options.

```
\NewDocumentCommand{\LWR@ProvidesPackageDrop}{m o}{
\PackageInfo{lwarp}{Replacing package `#1' with the lwarp version, discarding options,}%
\IfValueTF{#2}
{\ProvidesPackage{lwarp-#1}[#2]}
{\ProvidesPackage{lwarp-#1}}
```

Ignore all options.

```
\DeclareOption*{}
```

Nullifies then processes the options. Seems to be required when options contain curly braces, which were causing "`Missing \begin{document}`".

```
% \ProcessOptions\relax% original LaTeX code
\let\ds@\@empty%         from the original \ProcessOptions
\edef\@curroptions{}%    lwarp modification to \ProcessOptions
\@process@ptions\relax%  from the original \ProcessOptions
}
```

```
\end{warpHTML}
```

31 Additional required packages

for HTML output:

```
\begin{warpHTML}
```

`Pkg caption`

```
\LWR@origRequirePackage{caption}
\AtBeginDocument{\RequirePackage{lwarp-caption}}%
```

```
\end{warpHTML}
```

32 File handles

Defines file handles for writes.

for HTML & PRINT:

```
\begin{warpall}
```

`\LWR@quickfile` For quick temporary use only. This is reused in several places.

```
\newwrite\LWR@quickfile%
```

```
\end{warpall}
```

for HTML output:
```
\begin{warpHTML}
```

`\LWR@lateximagesfile` For `<project>-images.txt`:

```
\newwrite\LWR@lateximagesfile
```

```
\end{warpHTML}
```

33 Include a file

During HTML output, `\include{<filename>}` causes the following to occur:

1. lwarp creates `<filename>_html_inc.tex` whose contents are:
   `\input <filename>.tex`
2. `<filename>_html_inc.tex` is then `\included` instead of `<filename>.tex`.
3. `<filename>_html_inc.aux` is automatically generated and used by LaTeX.

for HTML output:
```
\begin{warpHTML}
```

`\include` {⟨*filename*⟩}

`\@include` {⟨*filename*⟩} Modified to load `_html_inc` files.

```
\def\@include#1 {%
\immediate\openout\LWR@quickfile #1_html_inc.tex% lwarp
\immediate\write\LWR@quickfile{\string\input{#1.tex}}% lwarp
\immediate\closeout\LWR@quickfile% lwarp
\LWR@origclearpage% \changed
\if@filesw
    \immediate\write\@mainaux{\string\@input{#1_html_inc.aux}}% changed
\fi
\@tempswatrue
\if@partsw
    \@tempswafalse
    \edef\reserved@b{#1}%
    \@for\reserved@a:=\@partlist\do
    {\ifx\reserved@a\reserved@b\@tempswatrue\fi}%
\fi
\if@tempswa
    \let\@auxout\@partaux
    \if@filesw
        \immediate\openout\@partaux #1_html_inc.aux % changed
        \immediate\write\@partaux{\relax}%
    \fi
    \@input@{#1_html_inc.tex}% changed
    \LWR@origclearpage% changed
```

```
    \@writeckpt{#1}%
    \if@filesw
        \immediate\closeout\@partaux
    \fi
\else
    \deadcycles\z@
    \@nameuse{cp@#1}%
\fi
\let\@auxout\@mainaux%
}

\end{warpHTML}
```

34 Copying a file

for HTML output:

```
\begin{warpHTML}
```

`\LWR@copyfile` {⟨*source filename*⟩} {⟨*destination filename*⟩}

Used to copy the `.toc` file to `.sidetoc` to re-print the TOC in the sideTOC navigation pane.

```
\newwrite\LWR@copyoutfile  % open the file to write to
\newread\LWR@copyinfile      % open the file to read from

\newcommand*{\LWR@copyfile}[2]{%
\LWR@traceinfo{LWR@copyfile: copying #1 to #2}

\immediate\openout\LWR@copyoutfile=#2
\openin\LWR@copyinfile=#1
\begingroup\endlinechar=-1
\makeatletter

\LWR@traceinfo{LWR@copyfile: about to loop}

\loop\unless\ifeof\LWR@copyinfile
  \LWR@traceinfo{LWR@copyfile: one line}
  \read\LWR@copyinfile to\LWR@fileline  % Read one line and store it into \LWR@fileline
%   \LWR@fileline\par                   % print the content into the pdf
% print the content:
  \immediate\write\LWR@copyoutfile{\unexpanded\expandafter{\LWR@fileline}}%
\repeat
\immediate\closeout\LWR@copyoutfile
\LWR@traceinfo{LWR@copyfile: done}
\endgroup
}

\end{warpHTML}
```

35 Debugging messages

HTML comments

To have the HTML output include additional HTML comments, such as which is closing, use

```
\booltrue{HTMLDebugComments}
```

debugging information

To have debug information written to the log, use

```
\tracinglwarp
```

for HTML & PRINT:

```
\begin{warpall}
```

Bool LWR@tracinglwarp

True if tracing is turned on.

```
\newbool{LWR@tracinglwarp}
```

\tracinglwarp

Turns on the debug tracing messages.

```
\newcommand{\tracinglwarp}{\booltrue{LWR@tracinglwarp}}
```

\LWR@traceinfo {⟨*text*⟩}

If tracing is turned on, writes the text to the .log file.

```
\newcommand{\LWR@traceinfo}[1]{%
\ifbool{LWR@tracinglwarp}%
{%
    \typeout{*** lwarp: #1}%
}%
{}%
}
```

Bool HTMLDebugComments

Default: false

Add comments in HTML about closing s, sections, etc.

```
\newbool{HTMLDebugComments}
\boolfalse{HTMLDebugComments}
```

If \tracinglwarp, show where preamble hooks occur:

```
\AfterEndPreamble{
\LWR@traceinfo{AfterEndPreamble}
}

\AtBeginDocument{
\LWR@traceinfo{AtBeginDocument}
}

\end{warpall}
```

36 Defining print and HTML versions of macros and environments

The following refers to defining objects inside lwarp, and is not for the user's document.

Many macros and environments must be provided as both print and HTML versions.

While generating the print version of a document, the original macros as defined by LaTeX and its packages are used as-is.

While generating the HTML version of a document, the original macro or environment is redefined to call a new HTML version or a copy of the original print version. The new HTML versions of macros and environments are used most of the time. Copies of the print versions are used inside a `latexmage` environment, which draws and remembers an image of the printed output, and also several other places. The copies of the print versions may also be used by the HTML versions, such as when the HTML version merely encloses the print version inside HTML tags.

The general structure for providing print and HTML versions of a macro or environment is as follows:

For a preexisting macro, not defined with xparse: An HTML version is provided with a special name, inside a `warpHTML` environment, then `\LWR@formatted` is used to redefine and patch various macros:

```
\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...}% may also use xparse

\LWR@formatted{name}
\end{warpHTML}
```

`\LWR@formatted{name}` copies the original print version, then redefines `\name` to use either the print or HTML version depending on which mode lwarp is using. xparse may be used to define the new HTML version, even if the original did not use xparse.

For a preexisiting environment, not defined with xparse: The process is similar. Note the use of `\LWR@formattedenv` instead of `\LWR@formatted`.

```
\begin{warpHTML}
\newenvironment{LWR@HTML@name}{...}% may also use xparse

\LWR@formattedenv{name}
\end{warpHTML}
```

If the original used xparse: A copy must be made using a new name:

```
\begin{warpHTML}
\NewDocumentCommand{\LWR@print@name}{..}{..}% copy the original
```

```
\NewDocumentCommand{\LWR@HTML@name}{..}{..}% or use \newcommand

\LWR@formatted{name}
\end{warpHTML}
```

Similar for an environment, using `\LWR@formattedenv`. (`\LWR@formatted` and `\LWR@formattedenv` use `\LetLtxMacro` to copy the original print definiton, which may not work with macros and environments created by xparse, so the print version must be manually recreated in the lwarp source.)

For a new macro or environment, not using xparse for the print version:

```
\begin{warpall}
\newcommand{\name}{...}% NOT xparse!
\end{warpall}

\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...}% may use xparse for HTML

\LWR@formatted{name}
\end{warpHTML}
```

Similar for an environment. The plain `\name` or environment `name` is used for the printed version, and is placed inside `warpall`. xparse may be used for the `\LWR@HTML@<name>` version.

For a new macro or environment, using xparse: It is possible to use xparse for an entirely new macro or environment by defining the `\LWR@print@<name>` version with xparse, along with `\name` defined without xparse to refer directly to the `\LWR@print` version:

```
\begin{warpall}
\NewDocumentCommand{\LWR@print@name}{...} {...}%      -or-
\NewDocumentEnvironment{\LWR@print@name}{...} {...} {...}

% Simply a call to \LWR@print@name:
\newcommand{\name}{\LWR@print@name}%        -or-
\newenvironment{name}{\LWR@print@name}{\endLWR@print@name}
\end{warpall}

\begin{warpHTML}
\NewDocumentCommand{\LWR@HTML@name}{...} {...}%      -or-
\NewDocumentEnvironment{\LWR@HTML@name}{...} {...} {...}

\LWR@formatted{name}%    -or-
\LWR@formattedenv{name}
\end{warpHTML}
```

In general, `\LWR@formatted` or `\LWR@formattedenv` are placed inside a `warpHTML` environment, and while producing an HTML document they do the following:

- Macros are modified:
  1. The pre-existing print version \name is saved as \LWR@print@<name>, unless \LWR@print@<name> is already defined.
  2. The original \name is redefined to call either the print or HTML version depending on which format is in use at the moment, as set by \LWR@formatting, which is defined as either "print" or "HTML".
- When lwarp is producing a print document, the original definitions are used, as well as any new definitions defined in warpall above.
- When lwarp is generating HTML output, \LWR@formatting is set to "HTML", and \name is directed to \LWR@HTML@<name>.
- When lwarp is generating HTML output but enters a lateximage environment, or for some other reason needs to draw images using the original print defintions, \LWR@formatting is changed to "print" and \name is then redirected to \LWR@print@<name>, which was the original \name.

Since arguments are not handled by the new \name, any star and other arguments are processed by the print or HTML version.

Expandable versions are also provided as well. These usually are necessary for anything which could appear inside a tabular, without which a "Misplaced \omit" error may occur.

⚠ Misplaced \omit error

```
\LWR@expandableformatted
\LWR@expandableformattedenv
```

(Older versions of lwarp used \LetLtxMacro for everything, but this could fail when using macros defined by xparse. This older system is still in use for many definitions.)

for HTML output:

```
\begin{warpHTML}
```

\LWR@formatting Remembers if selected print/HTML formatting.

Used while \LWR@restoreorigformatting, such as in an lateximage. May be set to either "print" or "HTML".

```
\newcommand*{\LWR@formatting}{HTML}
```

\LWR@formatted {⟨*macroname*⟩} No backslash in the macro name.

If not yet defined, defines \LWR@print@<name> as the original print-mode \<name>. Also redefines \<name> to use \LWR@<format>@<name>, where <format> is set by \LWR@formatting, and is print or HTML.

```
\newcommand*{\LWR@formatted}[1]{%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
    }{}%
    \ifcsundef{#1}{%
```

```
        \expandafter\newrobustcmd\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }{%
        \expandafter\renewrobustcmd\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }%
}
```

`\LWR@expandableformatted` {⟨*macroname*⟩} No backslash in the macro name.

An expandable version of `\LWR@formatted`.

```
\newcommand*{\LWR@expandableformatted}[1]{%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
    }{}%
    \ifcsundef{#1}{%
        \expandafter\newcommand\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }{%
        \expandafter\renewcommand\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }%
}
```

`\LWR@formattedenv` {⟨*environmentname*⟩}

If not yet defined, defines the environment `LWR@print@<name>` as the original print-mode `<name>`. Also redefines the environment `<name>` to use environment `LWR@<format>@<name>`, where `<format>` is set by `\LWR@formatting`, and is `print` or `HTML`.

```
\newcommand*{\LWR@formattedenv}[1]{%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
        \csletcs{endLWR@print@#1}{end#1}%
    }{}%
    \DeclareDocumentEnvironment{#1}{}%
    {\@nameuse{LWR@\LWR@formatting @#1}}%
    {\@nameuse{endLWR@\LWR@formatting @#1}}%
}
```

`\LWR@expandableformattedenv` {⟨*environmentname*⟩}

An expandable version of `LWR@formattedenv`.

```
\newcommand*{\LWR@expandableformattedenv}[1]{%
    \ifcsundef{LWR@print@#1}{%
```

```
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
        \csletcs{endLWR@print@#1}{end#1}%
    }{}%
    \DeclareExpandableDocumentEnvironment{#1}{}%
    {\@nameuse{LWR@\LWR@formatting @#1}}%
    {\@nameuse{endLWR@\LWR@formatting @#1}}%
}

\end{warpHTML}
```

37 HTML-conversion output modifications

These booleans modify the HTML output in various ways to improve conversion to EPUB or word processor imports.

for HTML & PRINT:

```
\begin{warpall}
```

37.1 User-level controls

Bool FormatEPUB
Default: false

Changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.

```
\newbool{FormatEPUB}
\boolfalse{FormatEPUB}
```

Bool FormatWP
Default: false

Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments.

```
\newbool{FormatWP}
\boolfalse{FormatWP}
```

Bool WPMarkFloats
Default: false

Adds

```
=== begin table ===
. . .
=== end ===
```

or

```
=== begin figure ===
. . .
=== end ===
```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions. [17]

[17] Perhaps some day word processors will have HTML import options for identifying `<figure>` and caption tags for figures and tables.

```
\newbool{WPMarkFloats}
\boolfalse{WPMarkFloats}
```

Bool WPMarkMinipages
Default: false

Adds

```
=== begin minipage ===
. . .
=== end minipage ===
```

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

```
\newbool{WPMarkMinipages}
\boolfalse{WPMarkMinipages}
```

Bool WPMarkTOC
Default: true

While formatting for word processors, adds

```
=== table of contents ===
```

where the Table of Contents would have been. This helps identify where to insert the actual TOC.

If set `false`*, the actual* TOC *is printed instead.*

```
\newbool{WPMarkTOC}
\booltrue{WPMarkTOC}
```

Bool WPMarkLOFT
Default: false

While formatting for word processors, adds

```
=== list of figures ===
=== list of tables ===
```

and / or

where each of these lists would have been. This helps identify where to insert the actual lists.

If set `false`*, the actual lists are printed instead.*

```
\newbool{WPMarkLOFT}
\boolfalse{WPMarkLOFT}
```

Bool WPMarkMath
Default: false

While formatting for word processors, prints math as LaTeX code instead of creating SVG images or MathJax. This is useful for cut/paste into the *LibreOffice Writer TeXMaths* extension.

```
\newbool{WPMarkMath}
\boolfalse{WPMarkMath}
```

Bool WPTitleHeading
Default: false

While formatting for word processors, `true` sets the document title to `<h1>`, which is expected for HTML documents, but also causes the lower-level section headings to start at **Heading 2** when imported into LibreOffice. Set to `false` to cause the title to be plain text, and the section headings to begin at **Heading 1**.

See table 8 on page 178.

```
\newbool{WPTitleHeading}
\boolfalse{WPTitleHeading}

\end{warpall}
```

37.2 Heading adjustments

If formatting the HTML for a word processor, adjust heading levels.

If `WPTitleHeading` is true, adjust so that `part` is **Heading 1**.

If `WPTitleHeading` is false, use `<h1>` for the title, and set `part` to **Heading 2**.

for HTML output:

```
\begin{warpHTML}

\AtBeginDocument{
\ifbool{FormatWP}{
\@ifundefined{chapter}{
\ifbool{WPTitleHeading}{% part and section starting at h2
\renewcommand*{\LWR@tagtitle}{h1}
\renewcommand*{\LWR@tagtitleend}{/h1}
\renewcommand*{\LWR@tagpart}{h2}
\renewcommand*{\LWR@tagpartend}{/h2}
\renewcommand*{\LWR@tagsection}{h3}
\renewcommand*{\LWR@tagsectionend}{/h3}
\renewcommand*{\LWR@tagsubsection}{h4}
\renewcommand*{\LWR@tagsubsectionend}{/h4}
\renewcommand*{\LWR@tagsubsubsection}{h5}
\renewcommand*{\LWR@tagsubsubsectionend}{/h5}
\renewcommand*{\LWR@tagparagraph}{h6}
\renewcommand*{\LWR@tagparagraphend}{/h6}
\renewcommand*{\LWR@tagsubparagraph}{span class="subparagraph"}
\renewcommand*{\LWR@tagsubparagraphend}{/span}
}% WPTitleHeading
{% not WPTitleHeading, part and section starting at h1
\renewcommand*{\LWR@tagtitle}{div class="title"}
\renewcommand*{\LWR@tagtitleend}{/div}
\renewcommand*{\LWR@tagpart}{h1}
\renewcommand*{\LWR@tagpartend}{/h1}
\renewcommand*{\LWR@tagsection}{h2}
\renewcommand*{\LWR@tagsectionend}{/h2}
\renewcommand*{\LWR@tagsubsection}{h3}
\renewcommand*{\LWR@tagsubsectionend}{/h3}
\renewcommand*{\LWR@tagsubsubsection}{h4}
\renewcommand*{\LWR@tagsubsubsectionend}{/h4}
\renewcommand*{\LWR@tagparagraph}{h5}
\renewcommand*{\LWR@tagparagraphend}{/h5}
\renewcommand*{\LWR@tagsubparagraph}{h6}
\renewcommand*{\LWR@tagsubparagraphend}{/h6}
}% not WPTitleHeading
}% chapter undefined
{% chapter defined
\ifbool{WPTitleHeading}{}
```

```
{% not WPTitleHeading, part and chapter starting at h1
\renewcommand*{\LWR@tagtitle}{div class="title"}
\renewcommand*{\LWR@tagtitleend}{/div}
\renewcommand*{\LWR@tagpart}{h1}
\renewcommand*{\LWR@tagpartend}{/h1}
\renewcommand*{\LWR@tagchapter}{h2}
\renewcommand*{\LWR@tagchapterend}{/h2}
\renewcommand*{\LWR@tagsection}{h3}
\renewcommand*{\LWR@tagsectionend}{/h3}
\renewcommand*{\LWR@tagsubsection}{h4}
\renewcommand*{\LWR@tagsubsectionend}{/h4}
\renewcommand*{\LWR@tagsubsubsection}{h5}
\renewcommand*{\LWR@tagsubsubsectionend}{/h5}
\renewcommand*{\LWR@tagparagraph}{h6}
\renewcommand*{\LWR@tagparagraphend}{/h6}
\renewcommand*{\LWR@tagsubparagraph}{span class="subparagraph"}
\renewcommand*{\LWR@tagsubparagraphend}{/span}
}% not WPTitleHeading
}% chapter defined
}{}% FormatWP
}% AtBeginDocument

\end{warpHTML}
```

38 Remembering original formatting macros

for HTML output:

```
\begin{warpHTML}
```

Remember original definitions of formatting commands. Will be changed to HTML commands for most uses. Will be temporarily restored to original meaning inside any lateximage environment. Also nullify unused commands.

Some packages redefine \#, which is used to generate HTML, so the original must be remembered here.

```
\chardef\LWR@origpound=`\#

\let\LWR@origcomma\,
\let\LWR@origthinspace\thinspace
\let\LWR@orignegthinspace\negthinspace
\let\LWR@origtilde~
\let\LWR@origenskip\enskip
\let\LWR@origquad\quad
\let\LWR@origqquad\qquad
\let\LWR@orighfil\hfil
\let\LWR@orighss\hss
\let\LWR@origllap\llap
\let\LWR@origrlap\rlap
\let\LWR@orighfilneg\hfilneg
\let\LWR@orighspace\hspace

\let\LWR@origrule\rule
```

```
\let\LWR@origmedskip\medskip
\let\LWR@origbigskip\bigskip

\let\LWR@origtextellipsis\textellipsis
\let\LWR@orig@textquotedbl\textquotedbl

\LetLtxMacro\LWR@origrmfamily\rmfamily
\LetLtxMacro\LWR@origsffamily\sffamily
\LetLtxMacro\LWR@origttfamily\ttfamily
\LetLtxMacro\LWR@origbfseries\bfseries
\LetLtxMacro\LWR@origmdseries\mdseries
\LetLtxMacro\LWR@origupshape\upshape
\LetLtxMacro\LWR@origslshape\slshape
\LetLtxMacro\LWR@origscshape\scshape


\@ifundefined{sishape}{
    \LetLtxMacro\LWR@origsishape\scshape
}{
    \LetLtxMacro\LWR@origsishape\sishape
}

\LetLtxMacro\LWR@origitshape\itshape
\LetLtxMacro\LWR@origem\em
\LetLtxMacro\LWR@orignormalfont\normalfont

\let\LWR@origonecolumn\onecolumn

\let\LWR@origsp\sp
\let\LWR@origsb\sb
\LetLtxMacro\LWR@origtextsuperscript\textsuperscript
\LetLtxMacro\LWR@orig@textsuperscript\@textsuperscript

\AtBeginDocument{
\LetLtxMacro\LWR@origtextsubscript\textsubscript
\LetLtxMacro\LWR@orig@textsubscript\@textsubscript
}

\LetLtxMacro\LWR@origunderline\underline


\let\LWR@orignewpage\newpage

\let\LWR@origpagestyle\pagestyle
\let\LWR@origthispagestyle\thispagestyle
\LetLtxMacro\LWR@origpagenumbering\pagenumbering

\let\LWR@orignewline\newline


\AtBeginDocument{% in case packages change definition
\let\LWR@orig@trivlist\@trivlist
\let\LWR@origtrivlist\trivlist
\let\LWR@origendtrivlist\endtrivlist
\LetLtxMacro\LWR@origitem\item
\LetLtxMacro\LWR@origitemize\itemize
```

```
\LetLtxMacro\LWR@endorigitemize\enditemize
\LetLtxMacro\LWR@origenumerate\enumerate
\LetLtxMacro\LWR@endorigenumerate\endenumerate
\LetLtxMacro\LWR@origdescription\description
\LetLtxMacro\LWR@endorigdescription\enddescription
\let\LWR@orig@mklab\@mklab
\let\LWR@origmakelabel\makelabel
\let\LWR@orig@donoparitem\@donoparitem
\LetLtxMacro\LWR@orig@item\@item
\let\LWR@orig@nbitem\@nbitem
}

\let\LWR@origpar\par

\LetLtxMacro\LWR@origfootnote\footnote
\let\LWR@orig@mpfootnotetext\@mpfootnotetext

\let\LWR@origclearpage\clearpage


\AtBeginDocument{% in case packages change definition
\LetLtxMacro\LWR@orighline\hline%
\LetLtxMacro\LWR@origcline\cline%
}

\end{warpHTML}
```

39 Accents

Native LaTeX accents such as \" will work, but many more kinds of accents are available when using Unicode-aware XeLaTeX and LuaLaTeX.

for HTML output:

```
\begin{warpHTML}
```

Without \AtBeginDocument, \t was being re-defined somewhere.

```
\AtBeginDocument{
```

The following are restored for print when inside a lateximage.

For Unicode engines, only \t needs to be redefined:

```
\LetLtxMacro\LWR@origt\t
```

For pdfLaTeX, additional work is required:

```
\ifPDFTeX% pdflatex or dvi latex
\LetLtxMacro\LWR@origequalaccent\=
\LetLtxMacro\LWR@origdotaccent\.
\LetLtxMacro\LWR@origu\u
\LetLtxMacro\LWR@origv\v
```

```
\LetLtxMacro\LWR@origc\c
\LetLtxMacro\LWR@origd\d
\LetLtxMacro\LWR@origb\b
```

The HTML redefinitions follow.

For pdfLaTeX, Unicode diacritical marks are used:

```
\renewcommand*{\=}[1]{#1\HTMLunicode{0305}}
\renewcommand*{\.}[1]{#1\HTMLunicode{0307}}
\renewcommand*{\u}[1]{#1\HTMLunicode{0306}}
\renewcommand*{\v}[1]{#1\HTMLunicode{030C}}
\renewcommand*{\c}[1]{#1\HTMLunicode{0327}}
\renewcommand*{\d}[1]{#1\HTMLunicode{0323}}
\renewcommand*{\b}[1]{#1\HTMLunicode{0331}}
\fi
```

For all engines, a Unicode diacritical tie is used:

```
\def\LWR@t#1#2{#1\HTMLunicode{0361}#2}
\renewcommand*{\t}[1]{\LWR@t#1}
```

`\LWR@restoreorigaccents` Called from `\restoreoriginalformatting` when a `lateximage` is begun.

```
\ifPDFTeX% pdflatex or dvi latex
\newcommand*{\LWR@restoreorigaccents}{%
\LetLtxMacro\=\LWR@origequalaccent%
\LetLtxMacro\.\LWR@origdotaccent%
\LetLtxMacro\u\LWR@origu%
\LetLtxMacro\v\LWR@origu%
\LetLtxMacro\t\LWR@origt%
\LetLtxMacro\c\LWR@origc%
\LetLtxMacro\d\LWR@origd%
\LetLtxMacro\b\LWR@origb%
}%
\else% XeLaTeX, LuaLaTeX:
\newcommand*{\LWR@restoreorigaccents}{%
\LetLtxMacro\t\LWR@origt%
}%
\fi%
}% AtBeginDocument
```

```
\end{warpHTML}
```

40 Configuration files

40.1 Decide whether to generate configuration files

Configuration files are only written if processing the print version of the document, and not processing a pstool image. pstool uses an additional compile for each image using

the original document's preamble, which includes lwarp, so the lwarp configuration files are turned off if -pstool is part of the \jobname.

Default to no configuration files:

```
\excludecomment{LWRwriteconf}
```

Generate configuration files if print mode and not -pstool:

for PRINT output:

```
\begin{warpprint}
\fullexpandarg%
\IfSubStr*{\jobname}{-pstool}
    {
        \typeout{lwarp: jobname with -pstool is found,}%
        \typeout{lwarp: \space\space not generating configuration files.}%
    }
    {
        \typeout{lwarp: generating configuration files}
        \includecomment{LWRwriteconf}
    }
\end{warpprint}
```

40.2 <project>_html.tex

File *_html.tex

Used to allow an HTML version of the document to exist alongside the print version.

Config file:

```
\begin{LWRwriteconf}
\immediate\openout\LWR@quickfile=\jobname_html.tex
\immediate\write\LWR@quickfile{%
\detokenize{\PassOptionsToPackage}%
{warpHTML,BaseJobname=\jobname}{lwarp}%
}
\immediate\write\LWR@quickfile{%
\detokenize{\input}\string{\jobname.tex\string }%
}
\immediate\closeout\LWR@quickfile
\end{LWRwriteconf}
```

40.3 *lwarpmk* configuration files

Config file:

```
\begin{LWRwriteconf}
```

\LWR@lwarpconfversion

The version number of the configuration file, allowing *lwarpmk* to detect an obsolete configuration file format. Incremented by one each time the configuration file format changes. (This is NOT the same as the lwarp version number.)

```
\newcommand*{\LWR@lwarpconfversion}{2}% also in lwarpmk.lua
```

40.3.1 Helper macros

`\LWR@shellescapecmd` The LaTeX compile option for shell escape, if used.

```
\ifshellescape
    \def\LWR@shellescapecmd{--shell-escape }
\else
    \def\LWR@shellescapecmd{}
\fi
```

`\LWR@compilecmd` {⟨*engine*⟩} {⟨*suffix*⟩}

Used to form the basic compilation command for a document, adding the optional shell escape.

Engine is *pdflatex*, etc. Suffix is empty or `_html`

```
\newcommand*{\LWR@compilecmd}[2]{%
    #1 \LWR@shellescapecmd \jobname#2%
}
```

`\LWR@addcompilecmd` {⟨*cmd*⟩} {⟨*suffix*⟩}

Adds to the compilation command.

Cmd is *dvipdfmx*, etc. Suffix is empty or `_html`

```
\newcommand*{\LWR@addcompilecmd}[2]{%
    \LWRopseq
    #1 \jobname#2%
}
```

`\LWR@unknownengine` Error message if not sure which LaTeX engine is being used.

```
\newcommand*{\LWR@unknownengine}{%
    \PackageError{lwarp}
    {Unknown LaTeX engine.}
   {Lwarp only knows about pdflatex, dvi latex, xelatex, lualatex, and upLateX.}
}
```

`\LWR@latexmkvar` {⟨*varname*⟩} {⟨*value*⟩}

Adds a *latexmk* variable assignment.

```
\newcommand*{\LWR@latexmkvar}[2]{%
    -e
    \LWRopquote%
    \LWRdollar #1=q/#2/%
    \LWRopquote
}
```

`\LWR@latexmkcmd` {⟨*latexmk options*⟩}

Sets a call to *latexmk* with the given options, possibly adding `--shell-escape`, and also adding the indexing program.

```
\newcommand*{\LWR@latexmkcmd}[1]{%
    latexmk  \space \LWR@shellescapecmd \space  #1 \space
    -recorder \space
    \LWR@latexmkvar{makeindex}{\LWR@LatexmkIndexCmd}
}
```

`\LWR@latexmkdvipdfm` {⟨*dvipdfm or dvipdfmx*⟩}

Adds the options settings for *dvipdfm* or *dvipdfmx*.

```
\newcommand*{\LWR@latexmkdvipdfm}[1]{%
    -pdfdvi \space
    \LWR@latexmkvar{dvipdf}{%
        #1
        \@percentchar O
        -o \@percentchar D
        \@percentchar S%
    }
}
```

`\LWR@compileuplatex` Sets compile options for upLaTeX with ujarticle or related classes.

```
\newcommand*{\LWR@compileuplatex}{
    \def\LWR@tempprintlatexcmd{%
        \LWR@compilecmd{uplatex}{}
        \LWR@addcompilecmd{dvipdfmx}{}
    }
    \def\LWR@tempHTMLlatexcmd{%
        \LWR@compilecmd{uplatex}{_html}
        \LWR@addcompilecmd{dvipdfmx}{_html}
    }
}
```

`\LWR@PrintLatexCmd` `\LWR@HTMLLatexCmd` If not set by the user, the following sets the command to use to compile the source to PDF form.

If using *latexmk*, a complicated string is created, eventually resulting in something such as:

For *xelatex* with `--shell-escape`:

```
[[latexmk   -xelatex   --shell-escape  -recorder
    -e '$makeindex = q/makeindex -s lwarp.ist/'  <jobname>_html]]
```

For *dvipdfmx*:

```
[[latexmk   -pdfdvi  -e '$dvipdf=q/dvipdfmx %O -o %D %S/'
    -recorder
    -e '$makeindex=q/makeindex -s lwarp.ist/'   <jobname>_html]]
```

For the following, temporary values are computed, but the permanent values are only set if the originals were not assigned by the user.

```
\ifbool{LWR@latexmk}{
```

For *latexmk* with *pdflatex* or *lualatex*:

```
    \ifpdf
```

For *latexmk* with *pdflatex*:

```
        \ifPDFTeX
            \def\LWR@latexcmd{\LWR@latexmkcmd{-pdf -dvi- -ps-}}
        \else
```

For *latexmk* with *lualatex*:

```
            \ifLuaTeX
                \def\LWR@latexcmd{\LWR@latexmkcmd{-lualatex}}
            \else
                \LWR@unknownengine
            \fi
        \fi
    \else% \ifpdf
```

For *latexmk* with *xelatex* or DVI *latex*:

```
        \ifXeTeX
```

For *latexmk* with *xelatex*:

```
            \def\LWR@latexcmd{\LWR@latexmkcmd{-xelatex}}
        \else% \ifXeTeX
```

For *latexmk* with DVI *latex*:

```
            \ifbool{LWR@dvipdfm}{
                \def\LWR@latexcmd{%
                    \LWR@latexmkcmd{%
                        \LWR@latexmkdvipdfm{dvipdfm}%
                    }
                }
            }{
                \ifbool{LWR@dvipdfmx}{
                    \def\LWR@latexcmd{%
                        \LWR@latexmkcmd{%
                            \LWR@latexmkdvipdfm{dvipdfmx}%
                        }
```

```
                    }
                }{
                    \def\LWR@latexcmd{\LWR@latexmkcmd{-pdfps}}
                }
            }
        \fi
    \fi% \ifpdf
```

The final assignment if *latexmk*:

```
    \def\LWR@tempprintlatexcmd{\LWR@latexcmd \space \jobname}
    \def\LWR@tempHTMLlatexcmd{\LWR@latexcmd \space \jobname_html}
}% latexmk
```

Without *latexmk*, the compiling command is simply the compiler name and the optional shell escape:

```
{% not latexmk
    \ifpdf
```

For *pdflatex* or *lualatex*:

```
        \ifPDFTeX
```

For *pdflatex*:

```
            \def\LWR@tempprintlatexcmd{\LWR@compilecmd{pdflatex}{}}
            \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{pdflatex}{_html}}
        \else
            \ifLuaTeX
```

For *lualatex*:

```
                \def\LWR@tempprintlatexcmd{\LWR@compilecmd{lualatex}{}}
                \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{lualatex}{_html}}
            \else
                \LWR@unknownengine
            \fi
        \fi
    \else% \ifpdf
```

For DVI *latex* or *xelatex*:

```
        \ifXeTeX
```

For *xelatex*:

```
            \def\LWR@tempprintlatexcmd{\LWR@compilecmd{xelatex}{}}
            \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{xelatex}{_html}}
        \else
```

For DVI *latex*. Default to *dvips*, unless told to use *dvipdfm* or *dvipdfmx*:

```
            \ifbool{LWR@dvipdfm}{
```

For DVI *latex* with *dvipdfm*:

```
                \def\LWR@tempprintlatexcmd{%
                    \LWR@compilecmd{latex}{}
                    \LWR@addcompilecmd{dvipdfm}{}
                }
                \def\LWR@tempHTMLlatexcmd{%
                    \LWR@compilecmd{latex}{_html}
                    \LWR@addcompilecmd{dvipdfm}{_html}
                }
            }{
                \ifbool{LWR@dvipdfmx}{
```

For DVI *latex* with *dvipdfmx*:

```
                    \def\LWR@tempprintlatexcmd{%
                        \LWR@compilecmd{latex}{}
                        \LWR@addcompilecmd{dvipdfmx}{}
                    }
                    \def\LWR@tempHTMLlatexcmd{%
                        \LWR@compilecmd{latex}{_html}
                        \LWR@addcompilecmd{dvipdfmx}{_html}
                    }
                }{% dvips
```

For DVI *latex* with *dvips* and *ps2pdf*:

```
                    \def\LWR@tempprintlatexcmd{%
                        \LWR@compilecmd{latex}{}
                        \LWR@addcompilecmd{dvips}{}
                        \LWR@addcompilecmd{ps2pdf}{}.ps
                    }
                    \def\LWR@tempHTMLlatexcmd{%
                        \LWR@compilecmd{latex}{_html}
                        \LWR@addcompilecmd{dvips}{_html}
                        \LWR@addcompilecmd{ps2pdf}{_html}.ps
                    }
                }
            }
        \fi% \ifXeTeX
    \fi% \ifpdf
}% latexmk
```

For ujarticle, utarticle, and related, using upLaTeX and *dvipdfmx*:

```
\@ifclassloaded{ujarticle}{\LWR@compileuplatex}{}
\@ifclassloaded{ujbook}{\LWR@compileuplatex}{}
\@ifclassloaded{ujreport}{\LWR@compileuplatex}{}
\@ifclassloaded{utarticle}{\LWR@compileuplatex}{}
\@ifclassloaded{utbook}{\LWR@compileuplatex}{}
\@ifclassloaded{utreport}{\LWR@compileuplatex}{}
```

Only make the setting permanent if the original was empty:

```
\ifdefempty{\LWR@PrintLatexCmd}{
    \def\LWR@PrintLatexCmd{\LWR@tempprintlatexcmd}
}{}
\ifdefempty{\LWR@HTMLLatexCmd}{
    \def\LWR@HTMLLatexCmd{\LWR@tempHTMLlatexcmd}
}{}
```

`\LWR@writeconf` {⟨*filename*⟩}

Common code for each of `lwarpmk.conf` and `<project>.lwarpmkconf`. Each entry is a variable name, the equal sign, and a quoted string inside `[[` and `]]`, which are *lua*'s long quote characters, allowing the use of single and double quotes inside.

```
\newcommand{\LWR@writeconf}[1]{
\ifcsdef{LWR@quickfile}{}{\newwrite{\LWR@quickfile}}
\immediate\openout\LWR@quickfile=#1
\immediate\write\LWR@quickfile{confversion = [[\LWR@lwarpconfversion]]}
\ifbool{usingOSWindows}{
    \immediate\write\LWR@quickfile{opsystem = [[Windows]]}
}{
    \immediate\write\LWR@quickfile{opsystem = [[Unix]]}
}
\immediate\write\LWR@quickfile{sourcename = [[\jobname]]}
\immediate\write\LWR@quickfile{homehtmlfilename = [[\HomeHTMLFilename]]}
\immediate\write\LWR@quickfile{htmlfilename = [[\HTMLFilename]]}
\immediate\write\LWR@quickfile{imagesdirectory = [[\LWR@ImagesDirectory]]}
\immediate\write\LWR@quickfile{imagesname = [[\LWR@ImagesName]]}
\immediate\write\LWR@quickfile{latexmk = [[\ifbool{LWR@latexmk}{true}{false}]]}
\immediate\write\LWR@quickfile{printlatexcmd = [[\LWR@PrintLatexCmd]]}
\immediate\write\LWR@quickfile{HTMLlatexcmd = [[\LWR@HTMLLatexCmd]]}
\immediate\write\LWR@quickfile{printindexcmd = [[\LWR@PrintIndexCmd]]}
\immediate\write\LWR@quickfile{HTMLindexcmd = [[\LWR@HTMLIndexCmd]]}
\immediate\write\LWR@quickfile{latexmkindexcmd = [[\LWR@LatexmkIndexCmd]]}
\immediate\write\LWR@quickfile{glossarycmd = [[\LWR@GlossaryCmd]]}
\immediate\write\LWR@quickfile{pdftotextenc = [[\LWR@pdftotextEnc]]}
\immediate\closeout\LWR@quickfile
}


\end{LWRwriteconf}
```

40.3.2 `lwarpmk.conf`

File `lwarpmk.conf` `lwarpmk.conf` is automatically (re-)created by the lwarp package when executing
`pdflatex <project.tex>`,
or similar for *xelatex* or *lualatex*, in print-document generation mode, which is the default unless the `warpHTML` option is given. `lwarpmk.conf` is then used by the utility *lwarpmk*.

Config file:

```
\begin{LWRwriteconf}

\AtBeginDocument{\LWR@writeconf{lwarpmk.conf}}
```

```
1606
1607 \end{LWRwriteconf}
```

40.3.3 <project>.lwarpmkconf

File project.lwarpmkconf A project-specific configuration file for *lwarpmk*.

The makeindex and xindy options have already been handled for lwarp.conf.

Config file:
```
1608 \begin{LWRwriteconf}
1609
1610 \AtBeginDocument{\LWR@writeconf{\jobname.lwarpmkconf}}
1611
1612 \end{LWRwriteconf}
```

40.4 lwarp.css

File lwarp.css This is the base css layer used by lwarp.

This must be present both when compiling the project and also when distributing the HTML files.

Config file:
```
1613 \begin{LWRwriteconf}
1614 \begin{filecontents*}{lwarp.css}
1615 /*
1616   CSS stylesheet for the LaTeX lwarp package
1617   Copyright 2016-2018 Brian Dunn --- BD Tech Concepts LLC
1618 */
1619
1620
1621 /* a fix for older browsers: */
1622 header, section, footer, aside, nav, main,
1623     article, figure { display: block; }
1624
1625
1626 A:link {color:#000080 ; text-decoration: none ; }
1627 A:visited {color:#800000 ; }
1628 A:hover {color:#000080 ; text-decoration: underline ;}
1629 A:active {color:#800000 ; }
1630
1631 a.tocpart {display: inline-block ; margin-left: 0em ;
1632     font-weight: bold ;}
1633 a.tocchapter {display: inline-block ; margin-left: 0em ;
1634     font-weight: bold ;}
1635 a.tocsection {display: inline-block ; margin-left: 1em ;
1636     text-indent: -.5em ; font-weight: bold ; }
1637 a.tocsubsection {display: inline-block ; margin-left: 2em ;
1638     text-indent: -.5em ; }
1639 a.tocsubsubsection {display: inline-block ; margin-left: 3em ;
1640     text-indent: -.5em ; }
1641 a.tocparagraph {display: inline-block ; margin-left: 4em ;
1642     text-indent: -.5em ; }
```

```
a.tocsubparagraph {display: inline-block ; margin-left: 5em ;
    text-indent: -.5em ; }
a.tocfigure {margin-left: 0em}
a.tocsubfigure {margin-left: 2em}
a.toctable {margin-left: 0em}
a.tocsubtable {margin-left: 2em}
a.toctheorem {margin-left: 0em}
a.toclstlisting {margin-left: 0em}

body {
    font-family: "DejaVu Serif", "Bitstream Vera Serif",
        "Lucida Bright", Georgia, serif;
    background: #FAF7F4 ;
    color: black ;
    margin:0em ;
    padding:0em ;
    font-size: 100% ;
    line-height: 1.2 ;
}

p {margin: 1.5ex 0em 1.5ex 0em ;}
table p {margin: .5ex 0em .5ex 0em ;}

/* Holds a section number */
span.sectionnumber { margin-right: 0em }

/* Inserted in front of index lines */
span.indexitem {margin-left: 0em}
span.indexsubitem {margin-left: 2em}
span.indexsubsubitem {margin-left: 4em}

div.hidden, span.hidden { display: none ; }

kbd, span.texttt {
    font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
        "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
        "Courier New", monospace;
    font-size: 100% ;
}

pre { padding: 3pt ; }

span.strong, span.textbf, div.strong, div.textbf { font-weight: bold; }

span.textit, div.textit { font-style: italic; }

span.textmd, div.textmd { font-weight: normal; }

span.textsc, div.textsc {
    font-variant: small-caps;
    font-variant-numeric: oldstyle-nums ;
}

span.textsi, div.textsi {
    font-style: italic ;
```

```
    font-variant: small-caps;
    font-variant-numeric: oldstyle-nums ;
}

span.textsl, div.textsl { font-style: oblique; }

span.textup, div.textup {
    font-style: normal;
    font-variant: normal;
    font-variant-numeric: normal ;
}

span.textrm, div.textrm {
    font-family: "DejaVu Serif", "Bitstream Vera Serif",
    "Lucida Bright", Georgia, serif;
}

span.textsf, div.textsf {
     font-family: "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
}

span.textcircled { border: 1px solid black ; border-radius: 1ex ; }

span.underline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
}

span.overline {
    text-decoration: overline ;
    text-decoration-skip: auto ;
}


/* for vertical text: */
div.verticalrl { writing-mode: vertical-rl }
div.horizontaltb { writing-mode: horizontal-tb }


/* for diagbox */
div.diagboxtitleN { border-bottom: 1px solid gray }
div.diagboxtitleS { border-top: 1px solid gray }

div.diagboxE {
    padding-left: 2em ;
    text-align: right ;
}

div.diagboxW {
    padding-right: 2em ;
    text-align: left ;
}


```

```
1753
1754 /* For realscripts */
1755 .supsubscript {
1756     display: inline-block;
1757     text-align:left ;
1758 }
1759
1760 .supsubscript sup,
1761 .supsubscript sub {
1762     position: relative;
1763     display: block;
1764     font-size: .5em;
1765     line-height: 1;
1766 }
1767
1768 .supsubscript sup {
1769     top: .5em;
1770 }
1771
1772 .supsubscript sub {
1773     top: .5em;
1774 }
1775
1776 div.attribution p {
1777     text-align: right ;
1778     font-size: 80%
1779 }
1780
1781 span.poemtitle {
1782   font-size: 120% ; font-weight: bold;
1783 }
1784
1785 pre.tabbing {
1786     font-family: "Linux Libertine Mono O", "Lucida Console",
1787         "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
1788         "Liberation Mono", "FreeMono", "Andale Mono",
1789         "Nimbus Mono L", "Courier New", monospace;
1790 }
1791
1792 blockquote {
1793     display: block ;
1794     margin-left: 2em ;
1795     margin-right: 2em ;
1796 }
1797
1798 blockquotation {
1799     display: block ;
1800     margin-left: 2em ;
1801     margin-right: 2em ;
1802 }
1803
1804 /* quotchap is for the quotchap package */
1805 div.quotchap {
1806     display: block ;
1807     font-style: oblique ;
```

```
1808     overflow-x: auto ;
1809     margin-left: 2em ;
1810     margin-right: 2em ;
1811 }
1812
1813 blockquote p, blockquotation p, div.quotchap p {
1814     line-height: 1.5;
1815     text-align: left ;
1816     font-size: .85em ;
1817 }
1818
1819 /* qauthor is for the quotchap package */
1820 div.qauthor {
1821   display: block ;
1822   text-align: right ;
1823   margin-left: auto ;
1824   margin-right: 2em ;
1825   font-size: 80% ;
1826   font-variant: small-caps;
1827 }
1828
1829 div.qauthor p {
1830   text-align: right ;
1831 }
1832
1833 div.epigraph, div.dictum {
1834   line-height: 1.2;
1835     text-align: left ;
1836     padding: 3ex 1em 0ex 1em ;
1837 /*     margin: 3ex auto 3ex auto ; */ /* Epigraph centered */
1838     margin: 3ex 1em 3ex auto ; /* Epigraph to the right */
1839 /*    margin: 3ex 1em 3ex 1em ; */ /* Epigraph to the left */
1840     font-size: .85em ;
1841     max-width: 27em ;
1842 }
1843
1844 div.epigraphsource, div.dictumauthor {
1845     text-align:right ;
1846     margin-left:auto ;
1847 /*     max-width: 50% ; */
1848     border-top: 1px solid #A0A0A0 ;
1849     padding-bottom: 3ex ;
1850     line-height: 1.2;
1851 }
1852
1853 div.epigraph p, div.dictum p { padding: .5ex ; margin: 0ex ;}
1854 div.epigraphsource p, div.dictumauthor p { padding: .5ex 0ex 0ex 0ex ; margin: 0ex ;}
1855 div.dictumauthor { font-style:italic }
1856
1857
1858 /* copyrightbox package */
1859 div.copyrightbox { margin: .5ex .5em }
1860 div.copyrightbox p {margin: 0px .5em ; padding: 0px}
1861 div.copyrightboxnote {text-align: left ; font-size: 60%}
1862
```

```
1863
1864 /* lettrine package: */
1865 span.lettrine { font-size: 4ex ; float: left ; }
1866 span.lettrinetext { font-variant: small-caps ; }
1867
1868 /* ulem, soul, umoline packages: */
1869 span.uline {
1870     text-decoration: underline ;
1871     text-decoration-skip: auto ;
1872 }
1873
1874 span.uuline {
1875     text-decoration: underline ;
1876     text-decoration-skip: auto ;
1877     text-decoration-style: double ;
1878 }
1879
1880 span.uwave {
1881     text-decoration: underline ;
1882     text-decoration-skip: auto ;
1883     text-decoration-style: wavy ;
1884 }
1885
1886 span.sout {
1887     text-decoration: line-through ;
1888 }
1889
1890 span.oline {
1891     text-decoration: overline ;
1892     text-decoration-skip: auto ;
1893 }
1894
1895 span.xout {
1896     text-decoration: line-through ;
1897 }
1898
1899 span.dashuline {
1900     text-decoration: underline ;
1901     text-decoration-skip: auto ;
1902     text-decoration-style: dashed ;
1903 }
1904
1905 span.dotuline {
1906     text-decoration: underline ;
1907     text-decoration-skip: auto ;
1908     text-decoration-style: dotted ;
1909 }
1910
1911 span.letterspacing { letter-spacing: .2ex ; }
1912
1913 span.capsspacing {
1914     font-variant: small-caps ;
1915     letter-spacing: .1ex ;
1916 }
1917
```

```
span.highlight { background: #F8E800 ; }



html body {
  margin: 0 ;
  line-height: 1.2;
}


body div {
  margin: 0ex;
}


h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    font-style: normal ;
    font-weight: bold ;
    text-align: left ;
}

h1 {    /* title of the entire website, used on each page */
    text-align: center ;
    font-size: 2.5em ;
    padding: .4ex 0em 0ex 0em ;
}
h2 { font-size: 2.25em }
h3 { font-size: 2em }
h4 { font-size: 1.75em }
h5 { font-size: 1.5em }
h6 { font-size: 1.25em }
span.paragraph {font-size: 1em ; font-variant: normal ;
    margin-right: 1em ; }
span.subparagraph {font-size: 1em ; font-variant: normal ;
    margin-right: 1em ;  }

div.minisec {
    font-family: "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
    font-style: normal ;
    font-weight: bold ;
    text-align: left ;
}

h1 {
  margin: 0ex 0em 0ex 0em ;
  line-height: 1.3;
  text-align: center ;
}
```

```
1973
1974 h2 {
1975   margin: 1ex 0em 1ex 0em ;
1976   line-height: 1.3;
1977   text-align: center ;
1978 }
1979
1980 h3 {
1981   margin: 3ex 0em 1ex 0em ;
1982   line-height: 1.3;
1983 }
1984
1985 h4 {
1986   margin: 3ex 0em 1ex 0em ;
1987   line-height: 1.3;
1988 }
1989
1990 h5 {
1991   margin: 3ex 0em 1ex 0em ;
1992   line-height: 1.3;
1993 }
1994
1995 h6 {
1996   margin: 3ex 0em 1ex 0em ;
1997   line-height: 1.3;
1998 }
1999
2000
2001 div.titlepage {
2002   text-align: center ;
2003 }
2004
2005 .footnotes {
2006     text-align: left ;
2007     font-size: .85em ;
2008     margin: 3ex 2em 0ex 2em ;
2009     border-top: 1px solid silver ;
2010 }
2011
2012 .marginpar, .marginparblock {
2013     max-width: 50%;
2014     float: right ;
2015     clear: both ;
2016     text-align: left ;
2017     margin: 1ex 0.5em 1ex 1em ;
2018     padding: 1ex 0.5em 1ex 0.5em ;
2019     font-size: 85% ;
2020     border-top: 1px solid silver ;
2021     border-bottom: 1px solid silver ;
2022     overflow-x: auto ;
2023 }
2024
2025 .marginpar br { margin-bottom: 2ex ; }
2026
2027 div.marginblock, div.marginparblock {
```

```
    max-width:50%;
    float:right;
    text-align:left;
    margin: 1ex 0.5em 1ex 1em ;
    padding: 1ex 0.5em 1ex 0.5em ;
    overflow-x: auto;
}

div.marginblock div.minipage,
div.marginparblock div.minipage {
    display: block ;
    margin: 0pt auto 0pt auto ;
}

div.marginblock div.minipage p ,
div.marginparblock div.minipage p
    { font-size: 85%}

div.marginblock br ,
div.marginparblock br
    { margin-bottom: 2ex ; }

div.bodycontainer {
    float: left ;
    width: 80% ;
}

div.bodywithoutsidetoc div.bodycontainer {
    float: none ;
    width: 100% ;
}

section.textbody div.footnotes{
    margin: 3ex 2em 0ex 2em ;
    border-bottom: 2px solid silver ;
}

.footnoteheader {
    border-top: 2px solid silver ;
    margin-top: 3ex ;
    padding-top: 1ex ;
    font-weight: bold ;
}

.mpfootnotes {
    text-align: left ;
    font-size: .85em ;
    margin-left: 1em ;
    border-top: 1px solid silver ;
}

/* Remove footnote top border in the title page. */
div.titlepage div.mpfootnotes {
    border-top: none ;
}
```

```
2083
2084
2085
2086 ul, ol {
2087   margin: 1ex 1em 1ex 0em;
2088   line-height: 1.2;
2089 }
2090
2091 body dir, body menu {
2092   margin: 3ex 1em 3ex 0em;
2093   line-height: 1.2;
2094 }
2095
2096 li { margin: 0ex 0em 1ex 0em; }
2097
2098 html {
2099   margin: 0;
2100   padding: 0;
2101 }
2102
2103 .programlisting {
2104   font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
2105         "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
2106         "Courier New", monospace;
2107   margin: 1ex 0ex 1ex 0ex ;
2108   padding: .5ex 0pt .5ex 0pt ;
2109   overflow-x: auto;
2110 }
2111
2112 section.textbody>pre.programlisting {
2113 border-top: 1px solid silver ;
2114 border-bottom: 1px solid silver ;
2115 }
2116
2117
2118 div.displaymath {
2119     text-align: center ;
2120 }
2121
2122 div.displaymathnumbered {
2123     text-align: right ;
2124     margin-left: 5% ;
2125     margin-right: 5% ;
2126     min-width: 2.5in ;
2127 }
2128
2129 @media all and (min-width: 400px) {
2130     div.displaymathnumbered {
2131         margin-left: 10% ;
2132         margin-right: 10% ;
2133     }
2134 }
2135
2136 @media all and (min-width: 800px) {
2137     div.displaymathnumbered {
```

```
2138         margin-right: 20% ;
2139     }
2140 }
2141
2142 @media all and (min-width: 1200px) {
2143     div.displaymathnumbered {
2144         margin-right: 30% ;
2145     }
2146 }
2147
2148
2149 .inlineprogramlisting {
2150   font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
2151         "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
2152         "Courier New", monospace;
2153   overflow-x: auto;
2154 }
2155
2156 span.listinglabel {
2157     display: inline-block ;
2158     font-size: 70% ;
2159     width: 4em ;
2160     text-align: right ;
2161     margin-right: 2em ;
2162 }
2163
2164 div.abstract {
2165   margin: 2em 5% 2em 5% ;
2166   padding: 1ex 1em 1ex 1em ;
2167 /*  font-weight: bold ; */
2168   font-size: 90% ;
2169     text-align: left ;
2170 }
2171
2172 div.abstract dl {line-height:1.5;}
2173 div.abstract dt {color:#304070;}
2174
2175 div.abstracttitle{
2176     font-family: "URW Classico", Optima, "Linux Biolinum O",
2177         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
2178         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2179     font-weight:bold;
2180     font-size:1.25em;
2181     text-align: center ;
2182 }
2183
2184 span.abstractrunintitle{
2185     font-family: "URW Classico", Optima, "Linux Biolinum O",
2186         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
2187         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2188     font-weight:bold;
2189 }
2190
2191
2192 .verbatim {
```

```
2193     overflow-x: auto ;
2194 }
2195
2196 .alltt {
2197     overflow-x: auto ;
2198 }
2199
2200
2201 .bverbatim {
2202     margin: 1ex 0pt 1ex 0pt ;
2203     padding: .5ex 0pt .5ex 0pt ;
2204     overflow-x: auto ;
2205 }
2206
2207 .lverbatim {
2208     margin: 1ex 0pt 1ex 0pt ;
2209     padding: .5ex 0pt .5ex 0pt ;
2210     overflow-x: auto ;
2211 }
2212
2213 .fancyvrb {
2214     font-size:.85em ;
2215     margin: 3ex 0pt 3ex 0pt
2216 }
2217
2218 .fancyvrblabel {
2219     font-weight:bold;
2220     text-align: center ;
2221 }
2222
2223
2224 .verse {
2225     font-family: "Linux Libertine Mono O", "Lucida Console",
2226         "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
2227         "Liberation Mono", "FreeMono", "Andale Mono",
2228         "Nimbus Mono L", "Courier New", monospace;
2229     margin-left: 1em ;
2230 }
2231
2232
2233 div.singlespace { line-height: 1.2 ; }
2234 div.onehalfspace { line-height: 1.5 ; }
2235 div.doublespace { line-height: 2 ; }
2236
2237
2238 /* Word processor format output: */
2239 div.wpfigure { border: 1px solid red ; margin: .5ex ; padding: .5ex ; }
2240 div.wptable { border: 1px solid blue ; margin: .5ex ; padding: .5ex ; }
2241 div.wpminipage { border: 1px solid green ; margin: .5ex ; padding: .5ex ;}
2242
2243
2244
2245
2246 /* Minipage environments, vertically aligned to top, center, bottom: */
2247 .minipage, .fminipage, .fcolorminipage {
```

```
    /* display: inline-block ; */
        /* Mini pages which follow each other will be tiled. */
    margin: .25em .25em .25em .25em;
    padding: .25em .25em .25em .25em;
    display: inline-flex;
    flex-direction: column ;
    overflow: auto;
}

/* Paragraphs in the flexbox did not collapse their margins. */
/* Have not yet researched this. */
.minipage p {margin: .75ex 0em .75ex 0em ;}

.fboxBlock .minipage, .colorbox .minipage, .colorboxBlock .minipage,
.fcolorbox .minipage, .fcolorboxBlock .minipage
    {border: none ; background: none;}

.fbox, .fboxBlock { border: 1px solid black ; }

.fbox, .fboxBlock, .fcolorbox, .fcolorboxBlock, .colorbox, .colorboxBlock,
.fminipage, .fcolorminipage
    {display: inline-block}

.shadowbox, .shabox {
   border: 1px solid black;
    box-shadow: 3px 3px 3px #808080 ;
     border-radius: 0px ;
    padding: .4ex .3em .4ex .3em ;
    margin: 0pt .3ex 0pt .3ex ;
  display: inline-block ;
}

.doublebox {
   border: 3px double black;
     border-radius: 0px ;
    padding: .4ex .3em .4ex .3em ;
    margin: 0pt .3ex 0pt .3ex ;
  display: inline-block ;
}

.ovalbox, .Ovalbox {
   border: 1px solid black;
     border-radius: 1ex ;
    padding: .4ex .3em .4ex .3em ;
    margin: 0pt .3ex 0pt .3ex ;
  display: inline-block ;
}

.Ovalbox { border-width: 2px ; }

.framebox {
   border: 1px solid black;
     border-radius: 0px ;
    padding: .3ex .2em 0ex .2em ;
    margin: 0pt .1ex 0pt .1ex ;
```

```
  display: inline-block ;
}


.mdframed {
    padding: 0ex ;
    margin: 2ex 0em 2ex 0em ;
}

.mdframed p { padding: 0ex .5em 0ex .5em ; }

.mdframed dl { padding: 1ex .5em 0ex .5em ; }

.mdframedtitle {
    padding: .5ex 0pt 0pt 0pt ;
    border-radius: 10pt 10pt 0pt 0pt ;
    display: block ;
    margin-bottom: 1ex ;
}

.mdframedsubtitle {
    display: block ;
}

.mdframedsubsubtitle {
    display: block ;
}

.mdtheorem {
    padding: 0ex .5em 0ex .5em ;
    margin: 3ex 5% 3ex 5% ;
}


/* framed package */
.framed, pre.boxedverbatim, fcolorbox {
    margin: 3ex 0em 3ex 0em ;
   border: 1px solid black;
     border-radius: 0px ;
    padding: .3ex 1em 0ex 1em ;
  display: block ;
}

.shaded {
    margin: 3ex 0em 3ex 0em ;
    padding: .3ex 1em .3ex 1em ;
    display: block ;
}

.snugframed {
    margin: 3ex 0em 3ex 0em ;
   border: 1px solid black;
     border-radius: 0px ;
  display: block ;
}
```

```
2358
2359 .framedleftbar {
2360     margin: 3ex 0em 3ex 0em ;
2361    border-left: 3pt solid black;
2362      border-radius: 0px ;
2363     padding: .3ex .2em .3ex 1em ;
2364   display: block ;
2365 }
2366
2367 .framedtitle {
2368     margin: 0em ;
2369     padding: 0em ;
2370     font-size: 130%
2371 }
2372
2373 .framedtitle p { padding: .3em }
2374
2375
2376 /* For the niceframe package: */
2377
2378 div.niceframe, div.curlyframe, div.artdecoframe, div.generalframe {
2379     padding: 1ex ;
2380     margin: 2ex auto ;
2381     border-radius: 2ex ;
2382 }
2383
2384 div.niceframe {
2385     border: 6px groove black ;
2386 }
2387
2388 div.curlyframe {
2389     border-left: 3px dotted black ;
2390     border-right: 3px dotted black ;
2391     border-radius: 6ex ;
2392 }
2393
2394 div.artdecoframe {
2395     border-left: 10px double black ;
2396     border-right: 10px double black ;
2397     border-radius: 6ex ;
2398 }
2399
2400 div.generalframe {
2401     border: 6px groove black ;
2402 }
2403
2404
2405
2406 dl {
2407   margin: 1ex 2em 1ex 0em;
2408   line-height: 1.3;
2409 }
2410
2411 dl dt {
2412     display: block ;
```

```
    float:left ;
    font-weight: bold;
    padding-right: 1em ;
}

dl dd { display: block ; }

dl dd:after { content: "" ; display: block ; clear: both }

dl dd p { margin-top: 0em; }

dd ul, dd ol, dd dl { clear: both ; padding-top: 1ex }


nav {
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
    margin-bottom: 4ex ;
}

nav p {
    line-height: 1.2 ;
    margin-top:.5ex ;
    margin-bottom:.5ex;
    font-size: .9em ;
}



img, img.hyperimage, img.borderimage {
    max-width: 600px;
    border: 1px solid silver;
    box-shadow: 3px 3px 3px #808080 ;
    padding: .5% ;
    margin: .5% ;
    background: none ;
}

img.inlineimage{
    padding: 0px ;
    box-shadow: none ;
    border: none ;
    background: none ;
    margin: 0px ;
    display: inline-block ;
    border-radius: 0px ;
}

img.logoimage{
    max-width: 300px ;
    box-shadow: 3px 3px 3px #808080 ;
    border: 1px solid black ;
    background:none ;
    padding:0 ;
```

```
    margin:.5ex ;
    border-radius: 10px ;
}


.section {
/*
    To have each section float relative to each other:
*/
/*
    display: block ;
    float: left ;
    position: relative ;
    background: white ;
    border: 1px solid silver ;
    padding: .5em ;
*/
    margin: 0ex .5em 0ex .5em ;
    padding: 0 ;
}


figure {
    margin: 5ex auto 5ex auto ;
    padding: 1ex 1em 1ex 1em ;
    overflow-x: auto ;
}


/* To automatically center images in figures: */
/*
figure img.inlineimage {
    margin: 0ex auto 0ex auto ;
    display: block ;
}
*/

/* To automatically center minipages in figures: */
/*
figure div.minipage, figure div.minipage div.minipage {
    margin: 1ex auto 1ex auto ;
    display: block ;
}
*/

figure figure { margin: 0pt }

figure div.minipage p { font-size: 85% ; }

figure.subfigure, figure.subtable  {
    display: inline-block ; margin: 3ex 1em 3ex 1em ;
}

div.figurecaption .minipage { margin:0 ; padding: 0 }

```

```
div.minipage figure { border: none ; box-shadow: none ; }
div.minipage figure.table { margin: 0ex }
div.minipage div.footnotes { margin: 1ex 2em 0ex 2em }

div.floatrow { text-align: center; }

div.floatrow figure { display: inline-block ; margin: 1ex 2% ; }

div.floatfoot { font-size: .85em ;
    border-top: 1px solid silver ; line-height: 1.2 ; }

div.figurecaption , .lstlistingtitle {
    font-size: .85em ;
    text-align: center ;
    font-weight: bold ;
    margin-top: 1ex ;
    margin-bottom: 1ex ;
}

figure.subfigure div.figurecaption, figure.subtable div.figurecaption  {
    border-bottom: none ; background: none ;
}

div.nonfloatcaption {
    margin: 1ex auto 1ex auto ;
    font-size: .85em ;
    text-align: center ;
    font-weight: bold ;
}

/* For a \RawCaption inside a minipage inside a figure's floatrow: */
figure div.floatrow div.minipage div.figurecaption {
    border: none ;
    background: none ;
}


/* For packages such as float, rotfloat, and algorithm2e: */

figure.boxed, figure.boxruled {
    border: 1px solid black ;
}

figure.ruled {
    border-top: 1px solid black ;
    border-bottom: 1px solid black ;
    border-left: 0px ;
    border-right: 0px ;
    border-radius: 0px ;
    background: none ;
    box-shadow: none ;
}

figure.ruled div.figurecaption, figure.boxruled div.figurecaption {
    border-top: 1px solid silver ;
```

```
    border-bottom: 1px solid silver ;
}


table {
    margin: 1ex auto 1ex auto ;
    border-collapse: separate ;
    border-spacing: 0px ;
    line-height: 1.3 ;
    }

tr.hline td {border-top: 1px solid #808080 ; margin-top: 0ex ;
    margin-bottom: 0ex ; } /* for \hline */

tr.tbrule td {border-top: 1px solid black ; margin-top: 0ex ;
    margin-bottom: 0ex ; } /* for \toprule, \bottomrule */

td {padding: .5ex .5em .5ex .5em ;}

table td.tdl { text-align: left ; vertical-align: middle ; }
table td.tdc { text-align: center ; vertical-align: middle ; }
table td.tdat { text-align: center ; vertical-align: middle ; padding: 0px ; margin: 0px ; }
table td.tdbang { text-align: center ; vertical-align: middle ; }
table td.tdr { text-align: right ; vertical-align: middle ; }
table td.tdp { text-align: left ; vertical-align: bottom ; }
table td.tdm { text-align: left ; vertical-align: middle ; }
table td.tdb { text-align: left ; vertical-align: top ; }
table td.tdP { text-align: center ; vertical-align: bottom ; }
table td.tdM { text-align: center ; vertical-align: middle ; }
table td.tdB { text-align: center ; vertical-align: top ; }

table td.tvertbarl { border-left: 1px solid black }
table td.tvertbarldouble { border-left: 4px double black }
table td.tvertbarr { border-right: 1px solid black }
table td.tvertbarrdouble { border-right: 4px double black }

table td.tvertbarldash { border-left: 1px dashed black }
table td.tvertbarldoubledash { border-left: 2px dashed black }
table td.tvertbarrdash { border-right: 1px dashed black }
table td.tvertbarrdoubledash { border-right: 2px dashed black }


/* for cmidrules: */
table td.tdrule {
    border-top: 1px solid #A0A0A0 ;
}

table td.tdrulel {
    border-top-left-radius:.5em ;
    border-top: 1px solid #A0A0A0 ;
}

table td.tdruler {
    border-top-right-radius:.5em ;
    border-top: 1px solid #A0A0A0 ;
```

```
}

table td.tdrulelr {
    border-top-left-radius:.5em ;
    border-top-right-radius:.5em ;
    border-top: 1px solid #A0A0A0 ;
}


/* Margins of paragraphs inside table cells: */
td.tdp p , td.tdprule p , td.tdP p , td.tdPrule p { padding-top: 1ex ;
    padding-bottom: 1ex ; margin: 0ex ; }
td.tdm p , td.tmbrule p , td.tdM p , td.tdMrule p { padding-top: 1ex ;
    padding-bottom: 1ex ; margin: 0ex ; }
td.tdb p , td.tdbrule p , td.tdB p , td.tdBrule p { padding-top: 1ex ;
    padding-bottom: 1ex ; margin: 0ex ; }

td.tdp , td.tdprule , td.tdP , td.tdPrule
    { padding: 0ex .5em 0ex .5em ; }
td.tdm , td.tdmrule , td.tdM , td.tdMrule
    { padding: 0ex .5em 0ex .5em ; }
td.tdb , td.tdbrule , td.tdB , td.tdBrule
    { padding: 0ex .5em 0ex .5em ; }


/* table notes: */
.tnotes {
    margin: 0ex 5% 1ex 5% ;
    padding: 0.5ex 1em 0.5ex 1em;
    font-size:.80em;
    text-align: left ;
}

.minipage .tnotes {
    margin: 0pt ;
    padding: 0pt ;
}

.tnotes dl dt p {margin-bottom:0px;}

.tnoteitemheader {margin-right: 1em;}


/* for colortbl and cell color */
div.cellcolor {
    width: 100% ;
    padding: .5ex .5em .5ex .5em ;
    margin: -.5ex -.5em -.5ex -.5em ;
}


/* for bigdelim */
.ldelim, .rdelim { font-size: 200% }

```

```
/* center, flushleft, flushright environments */
div.center{text-align:center;}
div.center table {margin-left:auto;margin-right:auto;}
div.flushleft{text-align:left;}
div.flushleft table {margin-left:0em ; margin-right:auto;}
div.flushright{text-align:right;}
div.flushright table {margin-left:auto ; margin-right: 0em ;}


/* Fancybox */
div.Btrivlist table tr td {
    padding: .2ex 0em ;
}


/* program listing callouts: */
span.callout {
     font-family: "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
    border-radius: .5em;
    background-color:black;
    color:white;
    padding:0px .25em 0px .25em;
    margin: 0 ;
    font-weight: bold;
    font-size:.72em ;
}

div.programlisting pre.verbatim span.callout{
    font-size: .85em ;
}

span.verbatim {
    font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
        "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
        "Courier New", monospace;
}



div.published
{
    text-align: center ;
    font-variant: normal ;
    font-style: italic ;
    font-size: 1em ;
    margin: 1ex 0em 1ex 0em ;
}

div.subtitle
{
    text-align: center ;
    font-variant: normal ;
    font-style: italic ;
    font-size: 1.25em ;
```

```
    margin: 1ex 0em 1ex 0em ;
}

div.subtitle p { margin: 1ex ; }

div.author
{
    font-variant: normal ;
    font-style: normal ;
    font-size: 1em ;
    margin: 1ex 0em 1ex 0em ;
}

div.oneauthor {
    display: inline-block ;
    margin: 0ex 1em 0ex 1em ;
}

/*
div.author table {
    margin: 1ex auto 0ex auto ;
    background: none ;
}

div.author table tbody tr td { padding: .25ex ; }
*/

span.affiliation {font-size: .85em ; font-variant: small-caps; }

div.titledate {
    text-align: center ;
    font-size: .85em ;
    font-style: italic;
    margin: 1ex 0em 1ex 0em ;
}


nav.topnavigation{
    text-align: left ;
    padding: 0.5ex 1em 0.5ex 1em ;
/*     margin: 2ex 0em 3ex 0em ; */
    margin: 0 ;
    border-bottom: 1px solid silver ;
    border-top: 1px solid silver ;
    clear:both ;
}

nav.botnavigation{
    text-align: left ;
    padding: 0.5ex 1em 0.5ex 1em ;
/*     margin: 3ex 0em 2ex 0em ; */
    margin: 0 ;
    border-top: 1px solid silver ;
    border-bottom: 1px solid silver ;
    clear:both ;
```

```
}


header {
    line-height: 1.2 ;
    font-size: 1em ;
    border-bottom: 1px solid silver ;
    margin: 0px ;
    padding: 2ex 1em 2ex 1em ;
    text-align:left ;
}


footer {
    font-size: .85em ;
    line-height: 1.2 ;
    margin-top: 1ex ;
    border-top: 1px solid silver ;
    padding: 2ex 1em 2ex 1em ;
    clear:both ;
    text-align:left ;
}


a.linkhome { font-weight:bold ; font-size: 1em ;}


div.lateximagesource { padding: 0px ; margin: 0px ; display: none; }

img.lateximage{
    padding: 0pt ;
    margin: 0pt ;
    box-shadow: none ;
    border: none ;
    background: none ;
    max-width: 100% ;
    border-radius: 0ex ;
    border: none ;
}


/* The -1px right margin compensates for the 1px right border. */
/* Without this -1px margin, the body container appears below instead */
/* of floating to the side. */
div.sidetoccontainer {
    font-family: "DejaVu Serif", "Bitstream Vera Serif",
        "Lucida Bright", Georgia, serif;
    float: left ;
    width: 20%;
    margin: 0pt -1px 3ex 0pt ;
    border-right: 1px solid silver;
    border-bottom: 1px solid silver;
    background: #FAF7F4 ;
    font-size:.9em ;
    border-radius: 0px 0px 20px 0px ;
```

```
}

div.sidetoccontents {
    overflow-y: auto ;
    width: 100% ;
    text-align: left ;
}


nav.sidetoc p {line-height:1.2 ; margin: 1ex .5em 1ex .5em ;
    text-indent: 0 ; }

nav.sidetoc p a {color:black ; font-size: .7em ;}

div.sidetoctitle {font-size: 1.2em; font-weight:bold; text-align:center;
    border-bottom: 1px solid silver ;    }

nav.sidetoc a:hover {text-decoration: underline ; }



section.textbody { margin: 0ex 1em 0ex 1em ;}


div.multicolsheading { -webkit-column-span: all;
    -moz-column-span: all; column-span: all; }
div.multicols { -webkit-columns: 3 380px ;
    -moz-columns: 3 380px ; columns: 3 380px ; }
div.multicols p {margin-top: 0ex}


/* Used for xfrac and nicefrac: */
span.numerator {
    font-size: 60% ;
    vertical-align: .4em ;
}

span.denominator {
    font-size: 60%
}


/* Used for algorithm2e: */
div.alg2evline{
    margin-left: 1em ;
    padding-left: 1em ;
    border-left: 1px solid black ;
    border-radius: 0px 0px 0px 1ex ;
}

div.alg2evsline{
    margin-left: 1em ;
    padding-left: 1em ;
    border-left: 1px solid black ;
}
```

```
2908
2909 div.alg2enoline{
2910     margin-left: 1em ;
2911     padding-left: 1em ;
2912 }
2913
2914 span.alg2elinenumber{
2915     margin-right: .5em ;
2916     font-size: 50% ;
2917     color: red ;
2918 }
2919
2920
2921 /* Used for algorithmicx: */
2922 span.floatright { float: right ; }
2923
2924
2925
2926
2927 /* Native LaTeX theorems: */
2928
2929 .theoremcontents { font-style: italic; margin-top: 3ex ; margin-bottom: 3ex ; }
2930 .theoremlabel { font-style: normal; font-weight: bold ; margin-right: .5em ; }
2931
2932
2933 /* theorem, amsthm, and ntheorem packages */
2934
2935 span.theoremheader,
2936 span.theoremheaderplain,
2937 span.theoremheaderdefinition,
2938 span.theoremheaderbreak,
2939 span.theoremheadermarginbreak,
2940 span.theoremheaderchangebreak,
2941 span.theoremheaderchange,
2942 span.theoremheadermargin
2943 {
2944     font-style:normal ; font-weight: bold ; margin-right: 1em ;
2945 }
2946
2947 span.amsthmnameplain,
2948 span.amsthmnamedefinition,
2949 span.amsthmnumberplain,
2950 span.amsthmnumberdefinition
2951 {
2952     font-style:normal ; font-weight: bold ;
2953 }
2954
2955
2956 span.amsthmnameremark,
2957 span.amsthmnumberremark
2958 {font-style:italic ; font-weight: normal ; }
2959
2960
2961 span.amsthmnoteplain,
2962 span.amsthmnotedefinition
```

```
{font-style:normal ;}


span.theoremheaderremark,
span.theoremheaderproof,
span.amsthmproofname
{font-style:italic ; font-weight: normal ; margin-right: 1em ; }

span.theoremheadersc
{
    font-style:normal ;
    font-variant: small-caps ;
    font-weight: normal ;
    margin-right: 1em ;
}

.theoremendmark {float:right}

div.amsthmbodyplain, div.theorembodyplain, div.theorembodynonumberplain,
div.theorembodybreak, div.theorembodynonumberbreak,
div.theorembodymarginbreak,
div.theorembodychangebreak,
div.theorembodychange,
div.theorembodymargin
{
    font-style:italic;
    margin-top: 3ex ; margin-bottom: 3ex ;
}

div.theorembodydefinition, div.theorembodyremark, div.theorembodyproof,
div.theorembodyplainupright, nonumberplainuprightsc,
div.amsthmbodydefinition, div.amsthmbodyremark,
div.amsthmproof
{
    font-style: normal ;
    margin-top: 3ex ; margin-bottom: 3ex ;
}

span.amsthmnoteremark {}


/* For the notes package: */
div.notesimportantnote, div.noteswarningnote, div.notesinformationnote {
    clear: both ;
    margin: 2ex 2em 2ex 2em ;
    border: 1px solid silver ;
}

div.notesicon {
    float:left ;
    display: inline-block ;
    background: gold ;
    padding: 0ex 1em 0ex 1em ;
    margin-right: 1em ;
    font-weight: bold ;
```

```
}

div.notescontents { font-style: italic }


/*
For CSS LaTeX and related logos:
Based on spacing demonstrated by the metafont package.
*/

.latexlogofont {
    font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-variant: normal ;
}

.latexlogo {
    font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-size: 1.1em;
}

.latexlogosup {
  text-transform: uppercase;
  letter-spacing: .03em ;
  font-size: 0.7em;
  vertical-align: 0.25em;
  margin-left: -0.4em;
  margin-right: -0.15em;
}

.latexlogosub {
  text-transform: uppercase;
  vertical-align: -0.27ex;
  margin-left: -0.08em;
  margin-right: -0.07em;
  font-size: 1em;
}

.latexlogotwoe {
  text-transform: none ;
  font-variant-numeric: oldstyle-nums ;
}

.latexlogotwoesub {
  font-style:italic ;
  vertical-align: -0.27ex;
  margin-left: -0.11em;
  margin-right: -0.1em;
  font-size: 1em;
}

.xelatexlogo {
    font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
```

```
    letter-spacing: .03em ;
    font-size: 1.1em;
}

.xelatexlogosub {
  vertical-align: -0.27ex;
  margin-left: -0.0667em;
  margin-right: -.05em;
  font-size: 1em;
  letter-spacing: .03em ;
}

.amslogo {
    font-family: "TeXGyreChorus","URW Chancery L",
        "Apple Chancery","ITC Zapf Chancery","Monotype Corsiva",
        "Linux Libertine O", "Nimbus Roman No 9 L",  "FreeSerif",
        "Hoefler Text", Times, "Times New Roman", serif ;
    font-style: italic ;
}

.lyxlogo {
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "DejaVu Sans", "Bitstream Vera Sans", Geneva,
        Verdana, sans-serif ;
}


/* Only display top and bottom navigation if a small screen: */
/* Hide the sidetoc if a small screen: */
nav.topnavigation { display:none; }
nav.botnavigation { display:none; }

/* Only display the sidetoc's webpage title if a small screen */
span.sidetocthetitle { display: none }

@media screen and (max-width: 50em) {
    div.sidetoccontainer {
        float: none ;
        width: 100% ;
        padding: 0 ;
        border-radius: 0 ;
        border-bottom: 1px solid black ;
        border-top: 1px solid black ;
        box-shadow: none ;
    }
    span.sidetocthetitle { display: inline }
    nav.botnavigation { display:block }
    div.bodycontainer { width: 100% }
    .marginpar {
        max-width: 100%;
        float: none;
        display:block ;
        margin: 1ex 1em 1ex 1em ;
    }
}
```

```
3128
3129 @media print {
3130     body {
3131         font-family: "Linux Libertine O",
3132         "DejaVu Serif", "Bitstream Vera Serif",
3133         "Liberation Serif", "Nimbus Roman No 9 L",
3134         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3135     }
3136     div.sidetoccontainer { display:none; }
3137     nav.topnavigation { display: none; }
3138     nav.botnavigation { display: none; }
3139     div.bodycontainer { width: 100% }
3140 }
3141
3142 @media handheld {
3143     div.sidetoccontainer { display:none; }
3144     nav.topnavigation { display:block }
3145     nav.botnavigation { display:block }
3146     div.bodycontainer { width: 100% }
3147 }
3148
3149 @media projection {
3150     div.sidetoccontainer { display:none; }
3151     nav.topnavigation { display:block }
3152     nav.botnavigation { display:block }
3153     div.bodycontainer { width: 100% }
3154 }
3155 \end{filecontents*}
3156 % \end{Verbatim}% for syntax highlighting
3157 \end{LWRwriteconf}
```

40.5 lwarp_sagebrush.css

File lwarp_sagebrush.css

An optional CSS which may be used for a semi-modern appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
3158 \begin{LWRwriteconf}
3159 \begin{filecontents*}{lwarp_sagebrush.css}
3160 @import url("lwarp.css") ;
3161
3162
3163 A:link {color:#105030 ; text-decoration: none ; }
3164 A:visited {color:#705030 ; text-shadow:1px 1px 2px #a0a0a0;}
3165 A:hover {color:#006000 ; text-decoration: underline ; text-shadow:0px 0px 2px #a0a0a0;}
3166 A:active {color:#00C000 ; text-shadow:1px 1px 2px #a0a0a0;}
3167
3168
3169
3170 h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
3171 {
3172     font-family: "URW Classico", Optima, "Linux Biolinum O",
3173         "Linux Libertine O", "Liberation Serif",
```

```
        "Nimbus Roman No 9 L",  "FreeSerif",
        "Hoefler Text", Times, "Times New Roman", serif;
    font-variant: small-caps ;
    font-weight: normal ;
    color: #304070 ;
    text-shadow: 2px 2px 3px #808080;
}

h1 {    /* title of the entire website, used on each page */
    font-variant: small-caps ;
    color: #304070 ;
    text-shadow: 2px 2px 3px #808080;
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C4);
}

h1 {
  border-bottom: 1px solid #304070;
/*  border-top: 2px solid #304070; */
}

h2 {
  border-bottom: 1px solid #304070;
/*  border-top: 2px solid #304070; */
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to bottom, #F7F7F0, #DAD0C0);
}



div.abstract {
    background: #f5f5eb ;
    background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);

  border: 1px solid silver;
    border-radius: 1em ;
}

div.abstract dl {line-height:1.5;}
div.abstract dt {color:#304070;}

div.abstracttitle{
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-weight:bold;
    font-variant: small-caps ;
    font-size:1.5em;
    border-bottom: 1px solid silver ;
    color: #304070 ;
    text-align: center ;
    text-shadow: 1px 1px 2px #808080;
}

span.abstractrunintitle{
```

```
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-weight:bold;
}


div.epigraph, div.dictum {
    background: #f5f5eb ;
    background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);

    border: 1px solid silver ;
    border-radius: 1ex ;
    box-shadow: 3px 3px 3px #808080 ;
}


.example {
    background-color: #f5f5eb ;
    background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);

}

div.exampletitle{
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-weight:bold;
    font-variant: small-caps ;
    border-bottom: 1px solid silver ;
    color: #304070 ;
    text-align: center ;
    text-shadow: 1px 1px 2px #808080;
}


.sidebar {
    background-color: #f5f5eb ;
    background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);

}

div.sidebartitle{
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-weight:bold;
    font-variant: small-caps ;
    border-bottom: 1px solid silver ;
    color: #304070 ;
    text-align: center ;
    text-shadow: 1px 1px 2px #808080;
}


```

```
.fancyvrblabel {
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-weight:bold;
    font-variant: small-caps ;
    font-size: 1.5em ;
    color: #304070 ;
    text-align: center ;
    text-shadow: 1px 1px 2px #808080;
}

div.minipage {
    background-color: #eeeee7 ;
    border: 1px solid silver ;
    border-radius: 1ex ;
}

table div.minipage { background: none ; border: none ; }

div.framebox div.minipage {border:none ; background:none}

section.textbody > div.minipage {
    box-shadow: 3px 3px 3px #808080 ;
}

div.fboxBlock div.minipage { box-shadow: none ; }

.framed .minipage , .framedleftbar .minipage {
    border: none ;
    background: none ;
    padding: 0ex ;
    margin: 0ex ;
}

figure.figure .minipage, div.figurecaption .minipage { border: none; }

div.marginblock div.minipage ,
div.marginparblock div.minipage
    { border: none; }

figure , div.marginblock {
    background-color: #eeeee7 ;
    border: 1px solid silver ;
    border-radius: 1ex ;
    box-shadow: 3px 3px 3px #808080 ;
}

figure figure {
    border: 1px solid silver ;
    margin: 0em ;
    box-shadow: none ;
}

/*
```

```
3339 div.figurecaption {
3340     border-top: 1px solid silver ;
3341     border-bottom: 1px solid silver ;
3342     background-color: #e8e8e8 ;
3343 }
3344 */
3345
3346
3347 div.table {
3348     box-shadow: 3px 3px 3px #808080 ;
3349 }
3350
3351 /*
3352 .tnotes {
3353     background: #e8e8e8;
3354     border: 1px solid silver;
3355 }
3356 */
3357
3358
3359 nav.topnavigation{
3360     background-color: #b0b8b0 ;
3361     background-image: linear-gradient(to bottom,#e0e0e0,#b0b8b0) ;
3362 }
3363
3364 nav.botnavigation{
3365     background-color: #b0b8b0 ;
3366     background-image: linear-gradient(to top,#e0e0e0,#b0b8b0) ;
3367 }
3368
3369
3370
3371 header{
3372     background-color: #F7F7F0 ;
3373     background-image: linear-gradient(to top, #F7F7F0, #b0b8b0);
3374 }
3375
3376 footer{
3377     background-color: #F7F7F0 ;
3378     background-image: linear-gradient(to bottom, #F7F7F0, #b0b8b0);
3379 }
3380
3381
3382
3383 div.sidetoccontainer {
3384     background-color: #F7F7F0 ;
3385     background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C0);
3386     box-shadow: 3px 3px 3px #808080 ;
3387     }
3388
3389 div.sidetoctitle {color: #304070 ; }
3390
3391 nav.sidetoc a:hover {
3392     color:#006000 ;
3393     text-decoration: none ;
```

```
    text-shadow:0px 0px 2px #a0a0a0;
}


@media screen and (max-width: 45em) {
    div.sidetoccontainer { border-radius: 0 ; }
}


\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.6 lwarp_formal.css

File lwarp_formal.css An optional css which may be used for a more formal appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp_formal.css}
@import url("lwarp.css") ;


A:link {color:#802020 ; text-decoration:none; }
A:visited {color:#802020 ; text-shadow:none ;}
A:hover {color:#400000 ; text-shadow:none ;}
A:active {color:#C00000 ; text-shadow:none ;}


body {
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    background: #fffcf5;
}

span.textrm {
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
}

span.textsf {
     font-family: "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
}
```

```
h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: #800000 ;
    text-shadow: none ;
}

h1, h2 {
    background-color: #fffcf5 ;
    background-image: none ;
    border-bottom: 1px solid #808080;
/*    border-top: 2px solid #808080; */
}

div.abstracttitle {
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: black ;
    text-shadow: none ;
}

span.abstractrunintitle {
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: black ;
    text-shadow: none ;
}

div.abstract { font-size: 100% }

.sidebar {
    background: #fffcf5;
    background-image: none ;
  margin: 2em 5% 2em 5%;
  padding: 0.5em 1em;
  border: none ;
  border-top : 1px solid silver;
  border-bottom : 1px solid silver;
  font-size: 90% ;
}

div.sidebartitle{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: #800000 ;
    text-shadow: none ;
```

```
3495     border: none ;
3496 }
3497
3498 .example {
3499     background: #fffcf5;
3500     background-image: none ;
3501   margin: 2em 5% 2em 5%;
3502   padding: 0.5em 1em;
3503   border: none ;
3504   border-top : 1px solid silver;
3505   border-bottom : 1px solid silver;
3506 }
3507
3508 div.exampletitle{
3509     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3510         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3511         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
3512         "Times New Roman", serif;
3513     color: #800000 ;
3514     text-shadow: none ;
3515     border: none ;
3516 }
3517
3518 div.fancyvrblabel{
3519     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3520         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3521         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
3522         "Times New Roman", serif;
3523     color: #800000 ;
3524     text-shadow: none ;
3525     border: none ;
3526 }
3527
3528
3529
3530 figure {
3531     margin: 5ex 5% 5ex 5% ;
3532     padding: 1ex 1em 1ex 1em ;
3533     background-color: #fffcf5 ;
3534     overflow-x: auto ;
3535     border: none ;
3536 /*     border-top: 1px solid silver; */
3537 /*     border-bottom: 1px solid silver; */
3538 }
3539
3540
3541 div.figurecaption , .lstlisting {
3542     border: none ;
3543 /*     border-top: 1px solid silver ; */
3544 /*     border-bottom: 1px solid silver ; */
3545     background-color: #fffcf5 ;
3546 }
3547
3548 .tnotes {
3549     background: #fffcf5 ;
```

```
    border-top: 1px solid silver ;
    border-bottom: 1px solid silver ;
}

.theorem {
        background: none ;
}

.minipage {
    background-color: #fffcf5 ;
    border: none ;
}

div.floatrow figure { border: none ; }

figure figure { border: none ; }


nav.toc, nav.lof, nav.lot, nav.lol {
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
}

div.sidetoccontainer {
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    background-image: linear-gradient(to bottom, #fffcf5, #C0C0C0);
}

div.sidetoctitle{
    color: #800000 ;
}

header{
    background-color: #e0e0e0 ;
    background-image: linear-gradient(to top, #fffcf5, #b0b0b0);
    text-align:center ;
}

footer{
    background-color: #e0e0e0 ;
    background-image: linear-gradient(to bottom, #fffcf5, #b0b0b0);
    padding: 2ex 1em 2ex 1em ;
    text-align:left ;
}

nav.botnavigation {
    background: #dedcd5 ;
    border-top: 1px solid black ;
}
\end{filecontents*}
```

```
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.7 sample_project.css

File sample_project.css The project-specific css file. Use with \CSSFilename.

If used, this must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{sample_project.css}
/* ( --- Start of project.css --- ) */
/* ( --- A sample project-specific CSS file for lwarp --- ) */

/* Uncomment one of the following: */
@import url("lwarp.css") ;
/* @import url("lwarp_formal.css") ; */
/* @import url("lwarp_sagebrush.css") ; */

/* Project-specific CSS setting follow here. */
/* . . . */

/* ( --- End of project.css --- ) */
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.8 lwarp.ist

File lwarp.ist Used to modify the index for lwarp.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

The page compositor line is for memoir's \specialindex.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp.ist}
preamble
"\\begin{theindex}
  \\providecommand*\\lettergroupDefault[1]{}
  \\providecommand*\\lettergroup[1]{%
      \\par\\textbf{#1}\\par
      \\nopagebreak
  }
"
headings_flag 1
heading_prefix "
  \\lettergroup{"
heading_suffix "}"
delim_0 ", \\hyperindexref{"
```

```
delim_1 ", \\hyperindexref{"
delim_2 ", \\hyperindexref{"
delim_n "}, \\hyperindexref{"
delim_r "} -- \\hyperindexref{"
delim_t "}"
page_compositor "."
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.9 lwarp.xdy

File lwarp.xdy Used to modify the index for lwarp.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

See:
https://tex.stackexchange.com/questions/80300/how-can-i-convince-hyperref-and-xindy-to-play-together-nicely

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp.xdy}
(require "tex/inputenc/latin.xdy")
(merge-rule "\\PS *" "Postscript")
(require "texindy.xdy")
(require "page-ranges.xdy")
(require "book-order.xdy")
(define-location-class "arabic-page-numbers"
    ("arabic-numbers") :min-range-length 1)
(require "makeindex.xdy")
(define-attributes (("hyperindexref")))
(markup-locref :open "\hyperindexref{" :close "}")
(markup-locref :open "\hyperindexref{" :close "}" :attr "hyperpage")
(markup-locref :open "\textbf{\hyperindexref{" :close "}}" :attr "textbf")
(markup-locref :open "\textit{\hyperindexref{" :close "}}" :attr "textit")
(define-location-class-order ("roman-page-numbers"
                  "arabic-page-numbers"
                  "alpha-page-numbers"
                  "Roman-page-numbers"
                  "Alpha-page-numbers"
                  "see"
                  "seealso"))
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.10 lwarp_one_limage.cmd

File lwarp_one_limage.cmd Used by lwarp to help make lateximages when using WINDOWS.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

The arguments are each of the three fields from `<project>-images.txt`, and also the base name of the source file.

MiKTeX does not allow file `lwarp_one_limage.cmd` to be created directly by *lwarpmk*, so `lwarp_one_limage.txt` is created instead, then copied to `lwarp_one_limage.cmd` by *lwarpmk*. This occurs each time *lwarpmk* used to create `latexmkimages`.

Config file:

```
\begin{LWRwriteconf}
\immediate\openout\LWR@quickfile=lwarp_one_limage.txt
\immediate\write\LWR@quickfile{%
    pdfseparate -f \LWRpercent 1 -l \LWRpercent 1 \LWRpercent 4_html.pdf %
   \LWR@ImagesDirectory\OSPathSymbol latexmkimagetemp-\LWRpercent\LWRpercent d.pdf%
}
\immediate\write\LWR@quickfile{%
   pdfcrop --hires  \LWR@ImagesDirectory\OSPathSymbol latexmkimagetemp-\LWRpercent 1.pdf %
    \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf%
}
\immediate\write\LWR@quickfile{%
   pdftocairo -svg -noshrink  \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf %
    \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.svg%
}
\immediate\write\LWR@quickfile{%
    del \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf%
}
\immediate\write\LWR@quickfile{%
    del \LWR@ImagesDirectory\OSPathSymbol latexmkimagetemp-\LWRpercent 1.pdf%
}
\immediate\write\LWR@quickfile{exit}
\immediate\closeout\LWR@quickfile
\end{LWRwriteconf}
```

40.11 `lwarp_mathjax.txt`

File `lwarp_mathjax.txt` Used by lwarp when using MathJax.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp_mathjax.txt}
<!-- https://groups.google.com/forum/#!topic/
                                mathjax-users/jUtewUcE2bY -->
<script type="text/x-mathjax-config">
MathJax.Hub.Register.StartupHook("TeX AMSmath Ready",function () {
    var seteqsectionDefault = {name: "", num: 0};
    var seteqsections = {}, seteqsection = seteqsectionDefault;
    var TEX = MathJax.InputJax.TeX, PARSE = TEX.Parse;
    var AMS = MathJax.Extension["TeX/AMSmath"];
    TEX.Definitions.Add({
    macros: {
        seteqsection: "mySection",
```

```
        seteqnumber: "mySetEqNumber"
    }
    });

    PARSE.Augment({
    mySection: function (name) {
        seteqsection.num = AMS.number;
        var n = this.GetArgument(name);
        if (n === "") {
            seteqsection = seteqsectionDefault;
        } else {
            if (!seteqsections["_"+n])
                seteqsections["_"+n] = {name:n, num:0};
            seteqsection = seteqsections["_"+n];
        }
        AMS.number = seteqsection.num;
    },
    mySetEqNumber: function (name) {
        var n = this.GetArgument(name);
        if (!n || !n.match(/^ *[0-9]+ *$/))
            n = "";
        else
            n = parseInt(n)-1;
        <!-- $ syntax highlighting -->
        if (n === "" || n < 1)
            TEX.Error
            ("Argument to "+name+" should be a positive integer");
        AMS.number = n;
    }
    });
    MathJax.Hub.Config({
    TeX: {
        equationNumbers: {
            formatTag: function (n) {
                <!-- if not numeric, don't include the chapter -->
                if (!n.match(/^ *[0-9]+ *$/ ))
                <!-- $ syntax highlighting -->
                    return "("+(n).replace(/^\./,"")+")" ;
                else
                  return "("+(seteqsection.name+"."+n).replace(/^\./,"")+")" ;
            },
            formatID: function (n) {
                n = (seteqsection.name+'.'+n).replace
                    (/[:"'<>&]/g,"").replace(/^\./,"");
                return 'mjx-eqn-' + n;
            }
        }
    }
    });
});
</script>

<!-- http://docs.mathjax.org/en/latest/options/ThirdParty.html -->
<script type="text/x-mathjax-config">
  MathJax.Ajax.config.path["Contrib"] =
```

```
    "https://cdn.mathjax.org/mathjax/contrib";
</script>

<script type="text/x-mathjax-config">
MathJax.Hub.Config({
    TeX: {
    equationNumbers: {
        autoNumber: "AMS"
    }
    }
});
</script>

<!-- Alternative CDN provider: -->
<script type="text/javascript" async
src="https://cdnjs.cloudflare.com/ajax/libs/mathjax/2.7.4/MathJax.js?config=TeX-AMS_HTML-full">
</script>

<!-- No longer supported after April 30, 2017: -->
<!--
<script
 src="https://cdn.mathjax.org/mathjax/latest/MathJax.js?config=TeX-AMS_HTML-full">
</script>
-->

\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.12 `lwarpmk.lua` — `lwarpmk` option

Opt `lwarpmk` Creates a local copy of *lwarpmk*.

Prog `lwarpmk` Command-line utility to process lwarp files and images.

parallel processing `latexi`images and SVG math images are generated using multiple processes in parallel. For UNIX and LINUX, every 32 images the `wait` command is issued to wait for the previous batch of images to finish processing before starting a new batch. For WINDOWS, every 32 images one task is dispatched with

```
START /B /WAIT /BELOWNORMAL
```

which causes the operating system to wait until this lesser-priority tasks finishes, hopefully also waiting for the normal priority tasks which were already in progress to also complete. Afterwards, the next batch of images is started.

The following is only generated if the `lwarpmk` option was given to lwarp.

```
\begin{LWR@createlwarpmk}

\begin{filecontents*}{lwarpmk.lua}
#!/usr/bin/env texlua

```

```
-- Copyright 2016-2018 Brian Dunn


printversion = "v0.68"
requiredconfversion = "2" -- also at *lwarpmk.conf

function printhelp ()
print ("lwarpmk: Use lwarpmk -h or lwarpmk --help for help.") ;
end


function printusage ()
--
-- Print the usage of the lwarpmk command:
--
print ( [[

lwarpmk print [-p project]: Compile the print version if necessary.
lwarpmk print1 [-p project]: Forced single compile of the print version.
lwarpmk printindex [-p project]: Process print indexes.
lwarpmk printglossary [-p project]: Process the glossary for the print version.
lwarpmk html [-p project]: Compile the HTML version if necessary.
lwarpmk html1 [-p project]: Forced single compile of the HTML version.
lwarpmk htmlindex [-p project]: Process HTML indexes.
lwarpmk htmlglossary [-p project]: Process the glossary for the html version.
lwarpmk again [-p project]: Touch the source code to trigger recompiles.
lwarpmk limages [-p project]: Process the "lateximages" created by lwarp.sty.
lwarpmk pdftohtml [-p project]:
    For use with latexmk or a Makefile:
    Converts project_html.pdf to project_html.html and individual HTML files.
    Finishes the HTML conversion even if there was a compile error.
lwarpmk pdftosvg <list of file names>: Converts each PDF file to SVG.
lwarpmk epstopdf <list of file names>: Converts each EPS file to PDF.
lwarpmk clean [-p project]: Remove *.aux, *.toc, *.lof/t,
    *.idx, *.ind, *.log, *_html_inc.*, .gl*
lwarpmk cleanall [-p project]: Remove auxiliary files, project.pdf, *.html
lwarpmk cleanlimages: Removes all images from the "lateximages" directory.
lwarpmk -h: Print this help message.
lwarpmk --help: Print this help message.

]] )
-- printconf ()
end


function splitfile (destfile,sourcefile)
--
-- Split one large sourcefile into a number of files,
-- starting with destfile.
-- The file is split at each occurance of <!--|Start file|newfilename|*
--
print ("lwarpmk: Splitting " .. sourcefile .. " into " .. destfile) ;
local sfile = io.open(sourcefile)
io.output(destfile)
for line in sfile:lines() do
```

```
i,j,copen,cstart,newfilename = string.find (line,"(.*)|(.*)|(.*)|") ;
if ( (i~= nil) and (copen == "<!--") and (cstart == "Start file")) then
    -- split the file
    io.output(newfilename) ;
else
    -- not a splitpoint
    io.write (line .. "\n") ;
end
end -- do
io.close(sfile)
end -- function


function cvalueerror ( line, linenum , cvalue )
--
-- Incorrect value, so print an error and exit.
--
    print ("lwarpmk: ===")
    print ("lwarpmk: " .. linenum .. " : " .. line ) ;
    print (
        "lwarpmk: incorrect variable value \"" .. cvalue ..
        "\" in lwarpmk.conf.\n"
    ) ;
    print ("lwarpmk: ===")
--    printconf () ;
    os.exit(1) ;
end


function ignoreconf ()
-- Global argument index
argindex = 2
end

function loadconf ()
--
-- Load settings from the project's "lwarpmk.conf" file:
--
-- Default configuration filename:
local conffile = "lwarpmk.conf"
local confroot = "lwarpmk"
-- Global argument index
argindex = 2
-- Optional configuration filename:
if ( arg[argindex] == "-p" ) then
    argindex = argindex + 1
    confroot = arg[argindex]
    conffile = confroot..".lwarpmkconf"
    argindex = argindex + 1
end
-- Additional defaults:
confversion = "0"
opsystem = "Unix"
imagesdirectory = "lateximages"
imagesname = "image-"
```

```
latexmk = "false"
printlatexcmd = ""
HTMLlatexcmd = ""
printindexcmd = ""
HTMLindexcmd = ""
latexmkindexcmd = ""
-- to be removed:
-- indexprog = "makeindex"
-- makeindexstyle = "lwarp.ist"
-- xindylanguage = "english"
-- xindycodepage = "utf8"
-- xindystyle = "lwarp.xdy"
-- pdftotextenc = "UTF-8"
glossarycmd = "makeglossaries"
-- Verify the file exists:
if (lfs.attributes(conffile,"mode")==nil) then
    -- file not exists
    print ("lwarpmk: ===")
    print ("lwarpmk: File \"" .. conffile .."\" does not exist.")
    print ("lwarpmk: Move to the project's source directory,")
    print ("lwarpmk: recompile using pdflatex, xelatex, or lualatex,")
    print ("lwarpmk: then try using lwarpmk again.")
    if ( arg[argindex] ~= nil ) then
        print (
            "lwarpmk: (\"" .. confroot ..
            "\" does not appear to be a project name.)"
        )
    end
    print ("lwarpmk: ===")
    printhelp () ;
    os.exit(1) -- exit the entire lwarpmk script
else -- file exists
-- Read the file:
print ("lwarpmk: Reading " .. conffile ..".")
local cfile = io.open(conffile)
-- Scan each line, parsing each line as: name = [[string]]
local linenum = 0
for line in cfile:lines() do -- scan lines
linenum = linenum + 1
i,j,cvarname,cvalue = string.find (line,"([%w-_]*)%s*=%s*%[%[([^%]]*)%]%]") ;
-- Error if incorrect enclosing characters:
if ( i == nil ) then
    print ("lwarpmk: ===")
    print ("lwarpmk: " ..  linenum .. " : " .. line ) ;
    print ("lwarpmk: Incorrect entry in " .. conffile ..".\n" ) ;
    print ("lwarpmk: ===")
--    printconf () ;
    os.exit(1) ;
end -- nil
if ( cvarname == "confversion" ) then
    confversion = cvalue
elseif ( cvarname == "opsystem" ) then
    -- Verify choice of opsystem:
    if ( (cvalue == "Unix") or (cvalue == "Windows") ) then
        opsystem = cvalue
```

```
    else
        cvalueerror ( line, linenum , cvalue )
    end
elseif ( cvarname == "sourcename" ) then sourcename = cvalue
elseif ( cvarname == "homehtmlfilename" ) then homehtmlfilename = cvalue
elseif ( cvarname == "htmlfilename" ) then htmlfilename = cvalue
elseif ( cvarname == "imagesdirectory" ) then imagesdirectory = cvalue
elseif ( cvarname == "imagesname" ) then imagesname = cvalue
elseif ( cvarname == "latexmk" ) then latexmk = cvalue
elseif ( cvarname == "printlatexcmd" ) then printlatexcmd = cvalue
elseif ( cvarname == "HTMLlatexcmd" ) then HTMLlatexcmd = cvalue
elseif ( cvarname == "printindexcmd" ) then printindexcmd = cvalue
elseif ( cvarname == "HTMLindexcmd" ) then HTMLindexcmd = cvalue
elseif ( cvarname == "latexmkindexcmd" ) then latexmkindexcmd = cvalue
elseif ( cvarname == "glossarycmd" ) then glossarycmd = cvalue
elseif ( cvarname == "pdftotextenc" ) then pdftotextenc = cvalue
else
    print ("lwarpmk: ===")
    print ("lwarpmk: " .. linenum .. " : " .. line ) ;
    print (
        "lwarpmk: Incorrect variable name \"" .. cvarname .. "\" in " ..
        conffile ..".\n"
    ) ;
    print ("lwarpmk: ===")
--    printconf () ;
os.exit(1) ;
end -- cvarname
end -- do scan lines
io.close(cfile)
end -- file exists
-- Error if sourcename is "lwarp".
-- This could happen if a local copy of lwarp has recently been recompiled.
if sourcename=="lwarp" then
    print ("lwarpmk: ===")
   print ("lwarpmk: lwarp.sty has recently been recompiled in this directory,")
   print ("lwarpmk: and \"lwarpmk.conf\" is no longer set for your own project.")
  print ("lwarpmk: Recompile your own project using pdf/lua/xelatex <projectname>.")
  print ("lwarpmk: After a recompile, \"lwarpmk.conf\" will be set for your project,")
    print ("lwarpmk: and you may again use lwarpmk.")
    print ("lwarpmk: ===")
    os.exit(1)
end -- sourcename of "lwarp"
-- Select some operating-system commands:
if opsystem=="Unix" then  -- For Unix / Linux / Mac OS:
    rmname = "rm"
    mvname = "mv"
    cpname = "cp"
    touchnamepre = "touch"
    touchnamepost = ""
    newtouchname = "touch"
    dirslash = "/"
    opquote= "\'"
    cmdgroupopenname = " ( "
    cmdgroupclosename = " ) "
    seqname = " && "
```

```
4016     bgname = " &"
4017 elseif opsystem=="Windows" then -- For Windows
4018     rmname = "DEL"
4019     mvname = "MOVE"
4020     cpname = "COPY"
4021     touchnamepre = "COPY /b"
4022     touchnamepost = "+,,"
4023     newtouchname = "echo empty >"
4024     dirslash = "\\"
4025     opquote= "\""
4026     cmdgroupopenname = ""
4027     cmdgroupclosename = ""
4028     seqname = " & "
4029     bgname = ""
4030 else
4031     print ("lwarpmk: ===")
4032     print ("lwarpmk: Select Unix or Windows for opsystem." )
4033     print ("lwarpmk: ===")
4034     os.exit(1)
4035 end --- for Windows
4036 -- Warning if the operating system does not appear to be correct,
4037 -- in case files were transferred to another system.
4038 if ( (package.config:sub(1,1)) ~= dirslash ) then
4039     print ("lwarpmk: ===")
4040    print ("lwarpmk: It appears that lwarpmk.conf is for a different operating system." )
4041     print ("lwarpmk: To adjust lwarpmk.conf for the current operating system," )
4042     print ("lwarpmk:   recompile the original document using xe/lua/pdflatex." )
4043     print ("lwarpmk: ")
4044     print ("lwarpmk: lwarpmk shall attempt to continue...")
4045     print ("lwarpmk: ===")
4046 end
4047 -- Error if the configuration file's version is not current:
4048 if ( confversion ~= requiredconfversion ) then
4049     print ("lwarpmk: ===")
4050    print ("lwarpmk: The configuration files lwarpmk.conf and "..sourcename..".lwarpmkconf" )
4051     print ("lwarpmk:   must be updated.  To update the configuration files," )
4052     print ("lwarpmk:   recompile "..sourcename..".tex using xe/lua/pdflatex," )
4053     print ("lwarpmk:   then use lwarpmk again.")
4054     print ("lwarpmk: ===")
4055     os.exit(1)
4056 end
4057 end -- loadconf
4058
4059
4060 function executecheckerror ( executecommands , errormessage )
4061 --
4062 -- Execute an operating system call,
4063 -- and maybe exit with an error message.
4064 --
4065 local err
4066 err = os.execute ( executecommands )
4067 if ( err ~= 0 ) then
4068     print ("lwarpmk: ===")
4069     print ("lwarpmk: " .. errormessage )
4070     print ("lwarpmk: ===")
```

```
4071     os.exit(1)
4072 end
4073 end -- executecheckerror
4074
4075
4076 function refreshdate ()
4077 os.execute(touchnamepre .. " " .. sourcename .. ".tex " .. touchnamepost)
4078 end
4079
4080
4081
4082 function reruntoget (filesource)
4083 --
4084 -- Scan the LaTeX log file for the phrase "Rerun to get",
4085 -- indicating that the file should be compiled again.
4086 -- Return true if found.
4087 --
4088 local fsource = io.open(filesource)
4089 for line in fsource:lines() do
4090 if ( string.find(line,"Rerun to get") ~= nil ) then
4091     io.close(fsource)
4092     return true
4093 end -- if
4094 end -- do
4095 io.close(fsource)
4096 return false
4097 end
4098
4099
4100
4101 function onetime (latexcmd, fsuffix)
4102 --
4103 -- Compile one time, return true if should compile again.
4104 -- fsuffix is "" for print, "_html" for HTML output.
4105 --
4106 print("lwarpmk: Compiling with: " .. latexcmd)
4107 executecheckerror (
4108     latexcmd ,
4109     "Compile error."
4110 )
4111 return (reruntoget(sourcename .. fsuffix .. ".log") ) ;
4112 end
4113
4114
4115 function manytimes (latexcmd, fsuffix)
4116 --
4117 -- Compile up to five times.
4118 -- fsuffix is "" for print, "_html" for HTML output
4119 --
4120 if onetime(latexcmd, fsuffix) == true then
4121 if onetime(latexcmd, fsuffix) == true then
4122 if onetime(latexcmd, fsuffix) == true then
4123 if onetime(latexcmd, fsuffix) == true then
4124 if onetime(latexcmd, fsuffix) == true then
4125 end end end end end
```

```
4126 end
4127
4128
4129 function verifyfileexists (filename)
4130 --
4131 -- Exit if the given file does not exist.
4132 --
4133 if (lfs.attributes ( filename , "modification" ) == nil ) then
4134     print ("lwarpmk: ===")
4135     print ("lwarpmk: " .. filename .. " not found." ) ;
4136     print ("lwarpmk: ===")
4137     os.exit (1) ;
4138 end
4139 end
4140
4141
4142
4143 function pdftohtml ()
4144 --
4145 -- Convert <project>_html.pdf into HTML files:
4146 --
4147 -- Convert to text:
4148 print ("lwarpmk: Converting " .. sourcename
4149     .."_html.pdf to " .. sourcename .. "_html.html")
4150 os.execute("pdftotext  -enc " .. pdftotextenc .. "  -nopgbrk  -layout "
4151     .. sourcename .. "_html.pdf " .. sourcename .. "_html.html")
4152 -- Split the result into individual HTML files:
4153 splitfile (homehtmlfilename .. ".html" , sourcename .. "_html.html")
4154 end
4155
4156
4157 function removeaux ()
4158 --
4159 -- Remove auxiliary files:
4160 -- All .aux files are removed since there may be many bbl*.aux files.
4161 --
4162 os.execute ( rmname .. " *.aux " ..
4163     sourcename ..".toc " .. sourcename .. "_html.toc " ..
4164     sourcename ..".lof " .. sourcename .. "_html.lof " ..
4165     sourcename ..".lot " .. sourcename .. "_html.lot " ..
4166     " *.idx " ..
4167     " *.ind " ..
4168     sourcename ..".ps " .. sourcename .."_html.ps " ..
4169     sourcename ..".log " .. sourcename .. "_html.log " ..
4170     sourcename ..".gl* " .. sourcename .. "_html.gl* " ..
4171     " *_html_inc.* "
4172     )
4173 end
4174
4175 function checkhtmlpdfexists ()
4176 --
4177 -- Error if the HTML document does not exist.
4178 -- The lateximages are drawn from the HTML PDF version of the document,
4179 -- so "lwarpmk html" must be done before "lwarpmk limages".
4180 --
```

```
local htmlpdffile = io.open(sourcename .. "_html.pdf", "r")
if ( htmlpdffile == nil ) then
    print ("")
    print ("lwarpmk: ===")
    print ("lwarpmk: The HTML version of the document does not exist.")
    print ("lwarpmk: Enter \"lwarpmk html\" to compile the HTML version.")
    print ("lwarpmk: ===")
    os.exit(1)
end
io.close (htmlpdffile)
end -- checkhtmlpdfexists


function warnlimages ()
--
-- Warning of a missing <sourcename>-images.txt file:
    print ("lwarpmk: ===")
    print ("lwarpmk: \"" .. sourcename .. "-images.txt\" does not exist.")
    print ("lwarpmk: Your project does not use SVG math or other lateximages,")
    print ("lwarpmk: or the file has been deleted somehow.")
    print ("lwarpmk: Use \"lwarpmk html\" to recompile your project")
    print ("lwarpmk: and recreate \"" .. sourcename .. "-images.txt\".")
   print ("lwarpmk: If your project does not use SVG math or other lateximages,")
   print ("lwarpmk: then \"" .. sourcename .. "-images.txt\" will never exist, and")
    print ("lwarpmk: \"lwarpmk limages\" will not be necessary.")
    print ("lwarpmk: ===")
end -- warnlimages


function warnlimagesrecompile ()
-- Warning if must recompile before creating limages:
    print ("")
    print ("lwarpmk: ===")
   print ("lwarpmk: The document must be recompiled before creating the lateximages.")
   print ("lwarpmk: Enter \"lwarpmk html\" again, then try \"lwarpmk limages\" again.")
    print ("lwarpmk: ===")
end --warnlimagesrecompile


function checklimages ()
--
-- Check <sourcename>.txt to see if need to recompile first.
-- If any entry has a page number of zero, then there were incorrect images.
--
print ("lwarpmk: Checking for a valid " .. sourcename .. "-images.txt file.")
local limagesfile = io.open(sourcename .. "-images.txt", "r")
if ( limagesfile == nil ) then
    warnlimages ()
    os.exit(1)
end
-- Track warning to recompile if find a page 0
local pagezerowarning = false
-- Scan <sourcename>.txt
for line in limagesfile:lines() do
    -- lwimgpage is the page number in the PDF which has the image
```

```
4236     -- lwimghash is true if this filename is a hash
4237     -- lwimgname is the lateximage filename root to assign for the image
4238     i,j,lwimgpage,lwimghash,lwimgname = string.find (line,"|(.*)|(.*)|(.*)|")
4239     -- For each entry:
4240     if ( (i~=nil) ) then
4241         -- If the page number is 0, image references are incorrect
4242         --  and must recompile the soure document:
4243         if ( lwimgpage == "0" ) then
4244             pagezerowarning = true
4245         end
4246     end -- if i~=nil
4247 end -- do
4248 -- The last line should be |end|end|end|.
4249 -- If not, the compile must have aborted, and the images are incomplete.
4250 if ( lwimgpage ~= "end" ) then
4251     warnlimagesrecompile()
4252     os.exit(1) ;
4253 end
4254 if ( pagezerowarning ) then
4255     warnlimagesrecompile()
4256     os.exit(1) ;
4257 end -- pagezerowarning
4258 end -- checklimages
4259
4260
4261 function createuniximage ( lwimgfullname )
4262 --
4263 -- Create one lateximage for Unix / Linux / Mac OS.
4264 --
4265 executecheckerror (
4266     cmdgroupopenname ..
4267     "pdfseparate -f " .. lwimgpage .. " -l " .. lwimgpage .. " " ..
4268         sourcename .."_html.pdf " ..
4269         imagesdirectory .. dirslash .."lateximagetemp-%d" .. ".pdf" ..
4270         seqname ..
4271     -- Crop the image:
4272     "pdfcrop  --hires  " .. imagesdirectory .. dirslash .. "lateximagetemp-" ..
4273         lwimgpage .. ".pdf " ..
4274         imagesdirectory .. dirslash .. lwimgname .. ".pdf" ..
4275         seqname ..
4276     -- Convert the image to svg:
4277    "pdftocairo -svg  -noshrink  " .. imagesdirectory .. dirslash .. lwimgname .. ".pdf " ..
4278         imagesdirectory .. dirslash .. lwimgname ..".svg" ..
4279         seqname ..
4280     -- Remove the temporary files:
4281    rmname .. " " .. imagesdirectory .. dirslash .. lwimgname .. ".pdf" .. seqname ..
4282    rmname .. " " .. imagesdirectory .. dirslash .. "lateximagetemp-" .. lwimgpage .. ".pdf" ..
4283     cmdgroupclosename .. " >/dev/null " .. bgname
4284     ,
4285     "File error trying to convert " .. lwimgfullname
4286 )
4287 -- Every 32 images, wait for completion at below normal priority,
4288 --  allowing other image tasks to catch up.
4289 numimageprocesses = numimageprocesses + 1
4290 if ( numimageprocesses > 32 ) then
```

```
4291     numimageprocesses = 0
4292     print ( "lwarpmk: waiting" )
4293     executecheckerror ( "wait" , "File error trying to wait.")
4294 end
4295 end -- createuniximage
4296
4297
4298 function createwindowsimage ( lwimgfullname )
4299 --
4300 -- Create one lateximage for Windows.
4301 --
4302 -- Every 32 images, wait for completion at below normal priority,
4303 --  allowing other image tasks to catch up.
4304 numimageprocesses = numimageprocesses + 1
4305 if ( numimageprocesses > 32 ) then
4306     numimageprocesses = 0
4307     thiswaitcommand = "/WAIT /BELOWNORMAL"
4308     print ( "lwarpmk: waiting" )
4309 else
4310     thiswaitcommand = ""
4311 end
4312 -- Execute the image generation command
4313 executecheckerror (
4314     "start /B " .. thiswaitcommand .. " \"\" lwarp_one_limage " ..
4315     lwimgpage .. " " ..
4316     lwimghash .. " " ..
4317     lwimgname .. " " ..
4318     sourcename .. " <nul >nul"
4319     ,
4320     "File error trying to create image."
4321 )
4322 end -- createwindowsimage
4323
4324
4325 function createonelateximage ( line )
4326 --
4327 -- Given the next line of <sourcename>.txt, convert a single image.
4328 --
4329 -- lwimgpage is the page number in the PDF which has the image
4330 -- lwimghash is true if this filename is a hash
4331 -- lwimgname is the lateximage filename root to assign for the image
4332 i,j,lwimgpage,lwimghash,lwimgname = string.find (line,"|(.*)|(.*)|(.*)|")
4333 -- For each entry:
4334 if ( (i~=nil) ) then
4335     -- Skip if the page number is 0:
4336     if ( lwimgpage == "0" ) then
4337         pagezerowarning = true
4338     -- Skip if the page number is "end":
4339     else if ( lwimgpage == "end" ) then
4340     else
4341         -- Skip is this image is hashed and already exists:
4342        local lwimgfullname = imagesdirectory .. dirslash .. lwimgname .. ".svg"
4343         if (
4344             (lwimghash ~= "true") or
4345             (lfs.attributes(lwimgfullname,"mode")==nil) -- file not exists
```

```
        )
        then -- not hashed or not exists:
            -- Print the name of the file being generated:
            print ( "lwarpmk: " .. lwimgname )
          -- Touch/create the dest so that only once instance tries to build it:
            executecheckerror (
                newtouchname .. " " .. lwimgfullname ,
                "File error trying to touch " .. lwimgfullname
            )
            -- Separate out the image into its own single-page pdf:
            if opsystem=="Unix" then
                createuniximage (lwimgfullname)
            elseif opsystem=="Windows" then
                createwindowsimage (lwimgfullname)
            end
        end -- not hashed or not exists
    end -- not page "end"
    end -- not page 0
end -- not nil
end -- createonelateximage


function createlateximages ()
--
-- Create lateximages based on <sourcename>-images.txt:
--
-- See if the document must be recompiled first:
checklimages ()
-- See if the print version exists:
checkhtmlpdfexists ()
-- Attempt to create the lateximages:
print ("lwarpmk: Creating lateximages.")
local limagesfile = io.open(sourcename .. "-images.txt", "r")
if ( limagesfile == nil ) then
    warnlimages ()
    os.exit(1)
end
-- Create the lateximages directory, ignore error if already exists
err = os.execute("mkdir " .. imagesdirectory)
-- For Windows, create lwarp_one_limage.cmd from lwarp_one_limage.txt:
if opsystem=="Windows" then
    executecheckerror (
        cpname .. " lwarp_one_limage.txt lwarp_one_limage.cmd" ,
       "File error trying to copy lwarp_one_limage.txt to lwarp_one_limage.cmd"
    )
end -- create lwarp_one_limage.cmd
-- Track the number of parallel processes
numimageprocesses = 0
-- Track warning to recompile if find a page 0
pagezerowarning = false
-- Scan <sourcename>.txt
for line in limagesfile:lines() do
    createonelateximage ( line )
end -- do
io.close(limagesfile)
```

```
print ( "lwarpmk limages: ===")
print ( "lwarpmk limages: Wait a moment for the images to complete" )
print ( "lwarpmk limages:   before reloading the page." )
print ( "lwarpmk limages: ===")
print ( "lwarpmk limages: Done." )
if ( pagezerowarning == true ) then
    print ( "lwarpmk limages: WARNING: Images will be incorrect." )
    print ( "lwarpmk limages:   Enter \"lwarpmk cleanlimages\", then" )
    print ( "lwarpmk limages:   recompile the document one more time, then" )
    print ( "lwarpmk limages:   repeat \"lwarpmk images\" again." )
end -- pagezerowarning
end -- function


function convertepstopdf ()
--
-- Converts EPS files to PDF files.
-- The filenames are arg[argindex] and up.
-- arg[1] is the command "pdftosvg".
--
ignoreconf ()
for i = argindex , #arg do
    if (lfs.attributes(arg[i],"mode")==nil) then
        print ("lwarpmk: File \"" .. arg[i] .. "\" does not exist.")
    else
        print ("lwarpmk: Converting \"" .. arg[i] .. "\"")
        os.execute ( "epstopdf " .. arg[i] )
    end -- if
end -- do
end --function


function convertpdftosvg ()
--
-- Converts PDF files to SVG files.
-- The filenames are arg[argindex] and up.
-- arg[1] is the command "pdftosvg".
--
ignoreconf ()
for i = argindex , #arg do
    if (lfs.attributes(arg[i],"mode")==nil) then
        print ("lwarpmk: File \"" .. arg[i] .. "\" does not exist.")
    else
        print ("lwarpmk: Converting \"" .. arg[i] .. "\"")
        os.execute ( "pdftocairo -svg " .. arg[i] )
    end -- if
end -- do
end --function


-- Force an update and conclude processing:
function updateanddone ()
print ("lwarpmk: Forcing an update of " .. sourcename ..".tex.")
refreshdate ()
print ("lwarpmk: " .. sourcename ..".tex is ready to be recompiled.")
```

```
print ("lwarpmk: Done.")
end -- function


-- Start of the main code: --


-- lwarpmk --version :

if (arg[1] == "--version") then
print ( "lwarpmk: " .. printversion )

else -- not --version


-- print intro:

print ("lwarpmk: " .. printversion .. "  Automated make for the LaTeX lwarp package.")


-- lwarpmk print:

if arg[1] == "print" then
loadconf ()
if ( latexmk == "true" ) then
    print ("lwarpmk: Compiling with: " .. printlatexcmd)
    executecheckerror (
        printlatexcmd ,
        "Compile error."
    )
    print ("lwarpmk: Done.")
else -- not latexmk
    verifyfileexists (sourcename .. ".tex") ;
    -- See if up to date:
    if (
        ( lfs.attributes ( sourcename .. ".pdf" , "modification" ) == nil ) or
        (
            lfs.attributes ( sourcename .. ".tex" , "modification" ) >
            lfs.attributes ( sourcename .. ".pdf" , "modification" )
        )
    ) then
        -- Recompile if not yet up to date:
        manytimes(printlatexcmd, "")
        print ("lwarpmk: Done.") ;
    else
        print ("lwarpmk: " .. sourcename .. ".pdf is up to date.") ;
    end
end -- not latexmk


-- lwarpmk print1:

elseif arg[1] == "print1" then
    loadconf ()
    verifyfileexists (sourcename .. ".tex") ;
```

```
4511     onetime(printlatexcmd, "")
4512     print ("lwarpmk: Done.") ;
4513
4514
4515 -- lwarpmk printindex:
4516 -- Compile the index then touch the source
4517 -- to trigger a recompile of the document:
4518
4519 elseif arg[1] == "printindex" then
4520 loadconf ()
4521 os.execute ( printindexcmd )
4522 print ("lwarpmk: -------")
4523 updateanddone ()
4524
4525
4526 -- lwarpmk printglossary:
4527 -- Compile the glossary then touch the source
4528 -- to trigger a recompile of the document:
4529
4530 elseif arg[1] == "printglossary" then
4531 loadconf ()
4532 print ("lwarpmk: Processing the glossary.")
4533
4534 os.execute(glossarycmd .. " " .. sourcename)
4535 updateanddone ()
4536
4537
4538 -- lwarpmk html:
4539
4540 elseif arg[1] == "html" then
4541 loadconf ()
4542 if ( latexmk == "true" ) then
4543     print ("lwarpmk: Compiling with: " .. HTMLlatexcmd)
4544     executecheckerror (
4545         HTMLlatexcmd ,
4546         "Compile error."
4547     )
4548     pdftohtml ()
4549     print ("lwarpmk: Done.")
4550 else -- not latexmk
4551     verifyfileexists ( sourcename .. ".tex" ) ;
4552     -- See if exists and is up to date:
4553     if (
4554       ( lfs.attributes ( homehtmlfilename .. ".html" , "modification" ) == nil ) or
4555         (
4556             lfs.attributes ( sourcename .. ".tex" , "modification" ) >
4557             lfs.attributes ( homehtmlfilename .. ".html" , "modification" )
4558         )
4559     ) then
4560         -- Recompile if not yet up to date:
4561         manytimes(HTMLlatexcmd, "_html")
4562         pdftohtml ()
4563         print ("lwarpmk: Done.")
4564     else
4565         print ("lwarpmk: " .. homehtmlfilename .. ".html is up to date.")
```

```
4566     end
4567 end -- not latexmk
4568
4569
4570 -- lwarpmk html1:
4571
4572 elseif arg[1] == "html1" then
4573     loadconf ()
4574     verifyfileexists ( sourcename .. ".tex" ) ;
4575     onetime(HTMLlatexcmd, "_html")
4576     pdftohtml ()
4577     print ("lwarpmk: Done.")
4578
4579
4580 -- lwarpmk pdftohtml:
4581 elseif arg[1] == "pdftohtml" then
4582     loadconf ()
4583     pdftohtml ()
4584
4585
4586 -- lwarpmk htmlindex:
4587 -- Compile the index then touch the source
4588 -- to trigger a recompile of the document:
4589
4590 elseif arg[1] == "htmlindex" then
4591 loadconf ()
4592 os.execute ( HTMLindexcmd )
4593 print ("lwarpmk: -------")
4594 updateanddone ()
4595
4596
4597 -- lwarpmk htmlglossary:
4598 -- Compile the glossary then touch the source
4599 -- to trigger a recompile of the document.
4600 -- The <sourcename>.xdy file is created by the glossaries package.
4601
4602 elseif arg[1] == "htmlglossary" then
4603 loadconf ()
4604 print ("lwarpmk: Processing the glossary.")
4605 os.execute(glossarycmd .. " " .. sourcename .. "_html")
4606 updateanddone ()
4607
4608
4609 -- lwarpmk limages:
4610 -- Scan the <sourcename>.txt file to create lateximages.
4611
4612 elseif arg[1] == "limages" then
4613 loadconf ()
4614 print ("lwarpmk: Processing images.")
4615 createlateximages ()
4616 print ("lwarpmk: Done.")
4617
4618
4619 -- lwarpmk again:
4620 -- Touch the source to trigger a recompile.
```

```
4621
4622 elseif arg[1] == "again" then
4623 loadconf ()
4624 updateanddone ()
4625
4626
4627 -- lwarpmk clean:
4628 -- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.*, .gl*
4629
4630 elseif arg[1] == "clean" then
4631 loadconf ()
4632 removeaux ()
4633 print ("lwarpmk: Done.")
4634
4635
4636 -- lwarpmk cleanall
4637 -- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.*, .gl*
4638 --    and also project.pdf, project.dvi, *.html
4639
4640 elseif arg[1] == "cleanall" then
4641 loadconf ()
4642 removeaux ()
4643 os.execute ( rmname .. " " ..
4644     sourcename .. ".pdf " .. sourcename .. "_html.pdf " ..
4645     sourcename .. ".dvi " .. sourcename .. "_html.dvi " ..
4646     "*.html"
4647     )
4648 print ("lwarpmk: Done.")
4649
4650
4651 -- lwarpmk cleanlimages
4652 -- Remove images from the imagesdirectory.
4653
4654 elseif arg[1] == "cleanlimages" then
4655 loadconf ()
4656 os.execute ( rmname .. " " .. imagesdirectory .. dirslash .. "*" )
4657 print ("lwarpmk: Done.")
4658
4659 -- lwarpmk epstopdf <list of file names>
4660 -- Convert EPS files to PDF using epstopdf
4661 elseif arg[1] == "epstopdf" then
4662 convertepstopdf ()
4663 print ("lwarpmk: Done.")
4664
4665
4666 -- lwarpmk pdftosvg <list of file names>
4667 -- Convert PDF files to SVG using pdftocairo
4668 elseif arg[1] == "pdftosvg" then
4669 convertpdftosvg ()
4670 print ("lwarpmk: Done.")
4671
4672
4673 -- lwarpmk with no argument :
4674
4675 elseif (arg[1] == nil) then
```

```
printhelp ()


-- lwarpmk -h or lwarpmk --help :

elseif (arg[1] == "-h" ) or (arg[1] == "--help") then
printusage ()


-- Unknown command:

else
printhelp ()
print ("\nlwarpmk: ****** Unknown command \""..arg[1].."\". ******\n")
end

end -- not --version
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting

\end{LWR@createlwarpmk}
```

41 Stacks

for HTML output:

```
\begin{warpHTML}
```

Stacks are used to remember how to close sections and list items. Before a new section is started, previously nested sections and items must be closed out (un-nested) in proper order. Note that starting a new section may close several levels of previously nested items at the same time. For example, starting a new `\section` would close any currently open subsection, subsubsection, and paragraph. General environments are not nested on the stack since they have their own close mechanism. List environments are nested, and items inside those environments are nested one level deeper still. List environments may be nested inside other list environments, and list items are nested inside list environments as well. Thus, the stack may have items which are not necessarily in order, since a description may contain an enumerate, for example. Depths to be recorded in `\LWR@closedepthone`, etc.

41.1 Assigning depths

initial depths for empty stack entries:

```
\newcommand*{\LWR@depthnone}{-5}
```

all sectioning depths are deeper than `LWR@depthfinished`:

```
\newcommand*{\LWR@depthfinished}{-4}
\newcommand*{\LWR@depthpart}{-1}
\newcommand*{\LWR@depthchapter}{0}
```

```
\newcommand*{\LWR@depthsection}{1}
\newcommand*{\LWR@depthsubsection}{2}
\newcommand*{\LWR@depthsubsubsection}{3}
\newcommand*{\LWR@depthparagraph}{4}
\newcommand*{\LWR@depthsubparagraph}{5}
```

used by `\itemize`, `\enumerate`, `\description`:

```
\newcommand*{\LWR@depthlist}{6}
```

used by `\item`:

```
\newcommand*{\LWR@depthlistitem}{7}
```

41.2 Closing actions

A stack to record the action to take to close each nesting level: Add more levels of stack if necessary for a very deeply nested document, adding to `\pushclose` and `\popclose` as well.

```
\newcommand*{\LWR@closeone}{}% top of the stack
\newcommand*{\LWR@closetwo}{}
\newcommand*{\LWR@closethree}{}
\newcommand*{\LWR@closefour}{}
\newcommand*{\LWR@closefive}{}
\newcommand*{\LWR@closesix}{}
\newcommand*{\LWR@closeseven}{}
\newcommand*{\LWR@closeeight}{}
\newcommand*{\LWR@closenine}{}
\newcommand*{\LWR@closeten}{}
\newcommand*{\LWR@closeeleven}{}
\newcommand*{\LWR@closetwelve}{}
```

41.3 Closing depths

A stack to record the depth of each level:

Note that nested LaTeX structures may push depths which are non-sequential.

Ex:

```
\begin{itemize}
   \item{A}
   \begin{description}
      \item{B}
   \end{description}
\end{itemize}
```

```
\newcommand*{\LWR@closedepthone}{\LWR@depthnone}% top of the stack
\newcommand*{\LWR@closedepththwo}{\LWR@depthnone}
\newcommand*{\LWR@closedepththree}{\LWR@depthnone}
\newcommand*{\LWR@closedepthfour}{\LWR@depthnone}
\newcommand*{\LWR@closedepthfive}{\LWR@depthnone}
\newcommand*{\LWR@closedepthsix}{\LWR@depthnone}
\newcommand*{\LWR@closedepthseven}{\LWR@depthnone}
\newcommand*{\LWR@closedeptheight}{\LWR@depthnone}
\newcommand*{\LWR@closedepthnine}{\LWR@depthnone}
\newcommand*{\LWR@closedepththen}{\LWR@depthnone}
\newcommand*{\LWR@closedepththeleven}{\LWR@depthnone}
\newcommand*{\LWR@closedepththtwelve}{\LWR@depthnone}
```

41.4 Pushing and popping the stack

\pushclose {⟨*action*⟩} {⟨*depth*⟩}

Pushes one return action and its LaTeX depth onto the stacks.

```
\NewDocumentCommand{\pushclose}{m m}
{
\global\let\LWR@closetwelve\LWR@closeeleven
\global\let\LWR@closeeleven\LWR@closeten
\global\let\LWR@closeten\LWR@closenine
\global\let\LWR@closenine\LWR@closeeight
\global\let\LWR@closeeight\LWR@closeseven
\global\let\LWR@closeseven\LWR@closesix
\global\let\LWR@closesix\LWR@closefive
\global\let\LWR@closefive\LWR@closefour
\global\let\LWR@closefour\LWR@closethree
\global\let\LWR@closethree\LWR@closetwo
\global\let\LWR@closetwo\LWR@closeone
\global\let\LWR@closeone#1
\global\let\LWR@closedepththtwelve\LWR@closedepththeleven
\global\let\LWR@closedepththeleven\LWR@closedepththten
\global\let\LWR@closedepththten\LWR@closedepthnine
\global\let\LWR@closedepthnine\LWR@closedeptheight
\global\let\LWR@closedeptheight\LWR@closedepthseven
\global\let\LWR@closedepthseven\LWR@closedepthsix
\global\let\LWR@closedepthsix\LWR@closedepthfive
\global\let\LWR@closedepthfive\LWR@closedepthfour
\global\let\LWR@closedepthfour\LWR@closedepththree
\global\let\LWR@closedepththree\LWR@closedepthtwo
\global\let\LWR@closedepthtwo\LWR@closedepthone
\global\let\LWR@closedepthone#2
}
```

\popclose Pops one action and its depth off the stacks.

```
\newcommand*{\popclose}
{
\global\let\LWR@closeone\LWR@closetwo
```

```
\global\let\LWR@closetwo\LWR@closethree
\global\let\LWR@closethree\LWR@closefour
\global\let\LWR@closefour\LWR@closefive
\global\let\LWR@closefive\LWR@closesix
\global\let\LWR@closesix\LWR@closeseven
\global\let\LWR@closeseven\LWR@closeeight
\global\let\LWR@closeeight\LWR@closenine
\global\let\LWR@closenine\LWR@closeten
\global\let\LWR@closeten\LWR@closeeleven
\global\let\LWR@closeeleven\LWR@closetwelve
\global\let\LWR@closedepthone\LWR@closedepthtwo
\global\let\LWR@closedepthtwo\LWR@closedepththree
\global\let\LWR@closedepththree\LWR@closedepthfour
\global\let\LWR@closedepthfour\LWR@closedepthfive
\global\let\LWR@closedepthfive\LWR@closedepthsix
\global\let\LWR@closedepthsix\LWR@closedepthseven
\global\let\LWR@closedepthseven\LWR@closedeptheight
\global\let\LWR@closedeptheight\LWR@closedepthnine
\global\let\LWR@closedepthnine\LWR@closedepthten
\global\let\LWR@closedepthten\LWR@closedeptheleven
\global\let\LWR@closedeptheleven\LWR@closedepthtwelve
}

\end{warpHTML}
```

42 Data arrays

These macros are similar to the arrayjobx package, except that `\LWR@setexparray`'s argument is expanded only once when assigned.

`name` has no backslash, `index` can be a number or a text name, and an empty `value` must be `\relax` instead of empty.

To assign an empty value:

```
\LWR@setexparray{name}{index}{}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@setexparray` {⟨*name*⟩} {⟨*index*⟩} {⟨*contents*⟩}

```
\NewDocumentCommand{\LWR@setexparray}{m m m}{%
    \begingroup%
    \let\par\relax%
    \xdef\LWR@thisexparrayname{#1#2}%
    \ifstrempty{#3}%
    {\csgdef{\LWR@thisexparrayname}{}}%
    {\csxdef{\LWR@thisexparrayname}{#3}}%
    \endgroup%
}
```

`\LWR@getexparray` {⟨*name*⟩} {⟨*index*⟩}

```
\newcommand*{\LWR@getexparray}[2]{%
    \@nameuse{#1#2}%
}
```

```
\end{warpHTML}
```

43 Localizing catcodes

for HTML & PRINT:

```
\begin{warpall}
```

⚠ Misplaced alignment tab character &

Place `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros or environments which include the tabular & character in their definitions.

The catcode of & must be changed before the definitions begin, and must be restored afterwards. Doing so avoids the error

```
Misplaced alignment tab character &.
```

`\StartDefiningTabulars` Place before defining something with & in it.

```
\newcommand{\StartDefiningTabulars}{%
\LWR@traceinfo{StartDefiningTabulars}%
\warpHTMLonly{\catcode`\&=\active}%
}
```

`\StopDefiningTabulars` Place after defining something with & in it.

```
\newcommand{\StopDefiningTabulars}{%
\LWR@traceinfo{StopDefiningTabulars}%
\warpHTMLonly{\catcode`\&=4}%
}
```

Bool `LWR@mathmacro` True if currently defining math macros. Used to disable SVG math hashing and MathJax math contents while defining a macro using inline math. Begin a macro, it is not guaranteed that the contents are static, and so the image must be unique. The contents also almost certainly will not be parsed correctly by MathJax.

```
\newbool{LWR@mathmacro}
\boolfalse{LWR@mathmacro}
```

`\StartDefiningMath` Place before defining something with $ in it.

```
\newcommand{\StartDefiningMath}{%
\LWR@traceinfo{StartDefiningMath}%
\warpHTMLonly{\catcode`\$=\active}%
}
```

\StopDefiningMath Place after defining something with $ in it.

```
\newcommand{\StopDefiningMath}{%
\LWR@traceinfo{StopDefiningMath}%
\warpHTMLonly{\catcode`\$=3}% math shift
}

\end{warpall}
```

44 Localizing dynamic math

Inline SVG math usually uses a hash of its contents to generate `lateximages` which are reusable for multiple instances with the same contents. If the contents may change for each use, such as depending on the current value of a counter, then `\inlinemathother` must be used before the inline math expression, and `\inlinemathnormal` must be used after.

For MathJax, the inline math expression is usually printed for MathJax to interpret. When marked as dynamic math, the following inline math expression will be displayed as an unhashed inline SVG image instead.

For existing code and packages, it may be possible to patch macros after they have been defined, using the xpatch package, which is pre-loaded by lwarp:

```
\xpatchcmd{\macroname}
    {$math expression$}
    {\inlinemathother$math expression$\inlinemathnormal}
    {}
    {\typeout{Error patching macroname.}}
```

for HTML & PRINT:

```
\begin{warpall}
```

Bool LWR@dynamicmath Default: false — True to mark inline math which is dynamic in nature, thus should not be hashed for reuse.

```
\newbool{LWR@dynamicmath}
\boolfalse{LWR@dynamicmath}
```

\inlinemathother Place before using $ … $ or \(… \) if the contents of the math are not static, depending on counters or dynamic macros.

```
\newcommand{\inlinemathother}{%
\LWR@traceinfo{inlinemathother}%
\booltrue{LWR@dynamicmath}%
}
```

\inlinemathnormal Place after using $ … $ or \(… \) with dynamic contents.

```
\newcommand{\inlinemathnormal}{%
\LWR@traceinfo{inlinemathnormal}%
\boolfalse{LWR@dynamicmath}%
}

\end{warpall}
```

45 HTML entities

for HTML output:

```
\begin{warpHTML}
```

HTML Unicode entities:

```
\let\LWR@origampersand\&
```

`\HTMLentity` {⟨*entitytag*⟩}

```
\newcommand*{\HTMLentity}[1]{%
% \LWR@traceinfo{HTMLentity \detokenize{#1}}%
\begingroup%
\LWR@FBcancel%
\LWR@origampersand#1;%
\endgroup%
% \LWR@traceinfo{HTMLentity done}%
}
```

`\HTMLunicode` {⟨*hex_unicode*⟩}

```
\newcommand*{\HTMLunicode}[1]{\HTMLentity{\LWR@origpound{}x#1}}
```

`\&`

```
\renewrobustcmd*{\&}{\HTMLentity{amp}}
```

`\textless`

```
\let\LWR@origtextless\textless
\renewrobustcmd*{\textless}{\HTMLentity{lt}}
```

`\textgreater`

```
\let\LWR@origtextgreater\textgreater
\renewrobustcmd*{\textgreater}{\HTMLentity{gt}}

\end{warpHTML}
```

46 HTML filename generation

The filename of the homepage is set to `\HomeHTMLFilename.html`. The filenames of additional sections start with `\HTMLFilename`, to which is appended a section number or a simplified section name, depending on `FileSectionNames`.

for HTML & PRINT:

```
\begin{warpall}
```

`\BaseJobname` The `\jobname` of the printed version, even if currently compiling the HTML version. I.e. this is the `\jobname` without `_html` appended. This is used to set `\HomeHTMLFilename` if the user did not provide one.

```
\providecommand*{\BaseJobname}{\jobname}
```

`\HTMLFilename` The prefix for all generated HTML files other than the home page, defaulting to empty. See section 8.4.1.

```
\providecommand*{\HTMLFilename}{}
```

`\HomeHTMLFilename` The filename of the home page, defaulting to the `\BaseJobname`. See section 8.4.1.

```
\providecommand*{\HomeHTMLFilename}{\BaseJobname}
```

`\SetHTMLFileNumber` {⟨*number*⟩}

Sets the file number for the next file to be generated. 0 is the home page. Use just before the next sectioning command, and set it to one less than the desired number of the next section. May be used to generate numbered groups of nodes such as 100+ for one chapter, 200+ for another chapter, etc.

```
\newcommand*{\SetHTMLFileNumber}[1]{%
\setcounter{LWR@htmlfilenumber}{#1}%
}
```

Bool `FileSectionNames` Selects how to create HTML file names.

Defaults to use section names in the filenames.

```
\newbool{FileSectionNames}
\booltrue{FileSectionNames}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Ctr `LWR@htmlfilenumber` Records the number of each HTML file as it is being created. Number 0 is the home page.

```
\newcounter{LWR@htmlfilenumber}
\setcounter{LWR@htmlfilenumber}{0}
```

\LWR@htmlsectionfilename {⟨*htmlfilenumber or name*⟩}

Prints the filename for a given section: \HTMLFilename{}filenumber/name.html

```
\newcommand*{\LWR@htmlsectionfilename}[1]{%
\LWR@traceinfo{LWR@htmlsectionfilename A !\detokenize{#1}!}%
```

Section 0 or empty is given the home filename. The filename must be detokenized for underscores.

```
% \LWR@traceinfo{about to assign temp}%
\LWR@sanitize{#1}%
\LWR@traceinfo{about to compare with ??}%
\ifthenelse{\equal{\LWR@sanitized}{??}}%
    {\LWR@traceinfo{found ??}}%
    {\LWR@traceinfo{not found ??}}%
\LWR@traceinfo{about to compare with zero or empty}%
\ifthenelse{%
    \equal{\LWR@sanitized}{0}%
    \OR \equal{\LWR@sanitized}{}%
    \OR \equal{\LWR@sanitized}{??}%
}%
{%
    \LWR@traceinfo{LWR@htmlsectionfilename B \HomeHTMLFilename.html}%
    \HomeHTMLFilename.html%
}%
```

For a LaTeX section named “Index” or “index” without a prefix, create a filename with a leading underscore to avoid colliding with the HTML filename index.html:

```
{%
    \LWR@traceinfo{LWR@htmlsectionfilename C \LWR@sanitized}%
    \ifthenelse{%
        \equal{\HTMLFilename}{} \AND
        \equal{\LWR@sanitized}{Index} \OR
        \equal{\LWR@sanitized}{index}%
    }%
    {%
        \LWR@traceinfo{Prefixing the index name with an underscore.}%
        \_\LWR@sanitized.html%
    }%
```

Otherwise, create a filename with the chosen prefix:

```
    {%
        \HTMLFilename\LWR@isolate{\LWR@sanitized}.html%
    }%
}%
\LWR@traceinfo{LWR@htmlsectionfilename Z}%
}
```

\LWR@htmlrefsectionfilename {⟨*label*⟩}

Prints the filename for the given label

```
\newcommand*{\LWR@htmlrefsectionfilename}[1]{%
\LWR@traceinfo{LWR@htmlrefsectionfilename: !\detokenize{#1}!}%
```

`\LWR@nullfonts` to allow math in a section name.

```
\begingroup%
\LWR@nullfonts%
\LWR@htmlsectionfilename{\LWR@htmlfileref{#1}}%
\endgroup%
\LWR@traceinfo{LWR@htmlrefsectionfilename: done}%
}
```

```
\end{warpHTML}
```

47 Homepage link

for HTML & PRINT:

```
\begin{warpall}
```

`\linkhomename` Holds the default name for the home link.

```
\newcommand{\linkhomename}{Home}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

`\LinkHome` May be used wherever you wish to place a link back to the homepage. The filename must be detokenized for underscores.

```
\newcommand*{\LinkHome}{%
\LWR@subhyperrefclass{\HomeHTMLFilename.html}{\linkhomename}{linkhome}%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

`\LinkHome` May be used wherever you wish to place a link back to the homepage. For print output, if hyperref is available a hyperlink to the first page is used, named by `\linkhomename`. If hyperref is not available, a pageref is used instead.

`\BaseJobname` is included in the link label in case multiple documents are cross-referenced.

```
\AtBeginDocument{
```

```
\@ifundefined{hyperref}{
    \newcommand*{\LinkHome}{%
        \linkhomename\ --- page \pageref{\BaseJobname-page-LWRfirstpage}%
    }
}{
    \newcommand*{\LinkHome}{%
        \hyperref[\BaseJobname-page-LWRfirstpage]{\linkhomename}%
    }
}
}

\AfterEndPreamble{\label{\BaseJobname-page-LWRfirstpage}}

\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@topnavigation` Creates a link to the homepage at the top of the page for use when the window is too narrow for the sideTOC.

```
\newcommand*{\LWR@topnavigation}{
\LWR@htmlelementclassline{nav}{topnavigation}{\LinkHome}
}
```

`\LWR@botnavigation` Creates a link to the homepage at the bottom of the page for use when the window is too narrow for the sideTOC.

```
\newcommand*{\LWR@botnavigation}{
\LWR@htmlelementclassline{nav}{botnavigation}{\LinkHome}
}

\end{warpHTML}
```

48 \LWRPrintStack diagnostic tool

⚠ Diagnostics tool: Prints the LaTeX nesting depth values for the stack levels. `\LWR@startpars` is used before printing the stack, so that `\LWRPrintStack` may be called from anywhere in the normal text flow.

for HTML output:

```
\begin{warpHTML}
```

`\LWRPrintStack` Prints the closedepth stack.

```
\newcommand*{\LWR@subprintstack}{
\LWR@closedepthone\ \LWR@closedepththwo\ \LWR@closedepththree\
\LWR@closedepthfour\ \LWR@closedepthfive\ \LWR@closedepthsix\
\LWR@closedepthseven\ \LWR@closedeptheight\ \LWR@closedepthnine\
\LWR@closedepthten\ \LWR@closedeptheleven\ \LWR@closedepthtwelve\
}
```

```
4943
4944 \newcommand*{\LWRPrintStack}{
4945 \LWR@startpars
4946 \LWR@subprintstack
4947 }
```

```
4948 \end{warpHTML}
```

for PRINT output:

```
4949 \begin{warpprint}
```

```
4950 \newcommand*{\LWRPrintStack}{}
```

```
4951 \end{warpprint}
```

49 Closing stack levels

for HTML output:

```
4952 \begin{warpHTML}
```

Close one nested level:

```
4953 \newcommand*{\LWR@closeoneprevious}{%
4954
4955 \LWR@closeone
4956
4957 \popclose
4958 }
```

`\LWR@closeprevious` {⟨*depth*⟩} Close everything up to the given depth:

```
4959 \newcommand*{\LWR@closeprevious}[1]{
4960 \LWR@traceinfo{LWR@closeprevious to depth #1, depths are \LWR@subprintstack}%
```

Close any pending paragraph:

```
4961 \LWR@stoppars%
```

Close anything nested deeper than the desired depth. First close anything deeper, then at most one of the same level.

```
4962 \whileboolexpr{test{\ifnumcomp{\LWR@closedepthone}{>}{#1}}}%
4963 {%
4964     \LWR@traceinfo{LWR@closeprevious: closing out depth \LWR@closedepthone}%
4965     \LWR@closeoneprevious%
4966 }%
4967 \ifboolexpr{test{\ifnumcomp{\LWR@closedepthone}{=}{#1}}}%
4968 {%
4969     \LWR@traceinfo{LWR@closeprevious: closing out depth \LWR@closedepthone}%
4970     \LWR@closeoneprevious%
4971 }{}%
4972 \LWR@traceinfo{LWR@closeprevious: done, depths are \LWR@subprintstack}%
4973 }
```

```
\end{warpHTML}
```

50 PDF pages and styles

for HTML output:

```
\begin{warpHTML}
```

`\LWR@forcenewpage` New PDF page a before major environment.

This is used just before major environments, such as `verse`. Reduces the chance of an environment overflowing the HTML PDF output page.

```
\newcommand{\LWR@forcenewpage}{%
\LWR@traceinfo{LWR@forcenewpage}%
\ifinner\else%
\LWR@stoppars\LWR@orignewpage\LWR@startpars%
\fi%
}
```

`\pagestyle`, etc. are nullified for HTML output.

`\pagestyle` {⟨*style*⟩}

```
\renewcommand*{\pagestyle}[1]{}
```

`\thispagestyle` {⟨*style*⟩}

```
\renewcommand*{\thispagestyle}[1]{}
```

`\markboth` {⟨*left*⟩} {⟨*right*⟩}

```
\renewcommand*{\markboth}[2]{}
```

`\markright` {⟨*right*⟩}

```
\renewcommand*{\markright}[1]{}
```

`\raggedbottom`

```
\renewcommand*{\raggedbottom}{}
```

`\flushbottom`

```
\renewcommand*{\flushbottom}{}
```

`\sloppy`

```
\renewcommand*{\sloppy}{}
```

\fussy

```
\renewcommand*{\fussy}{}
```

\pagenumbering * {⟨*commands*⟩}

```
\RenewDocumentCommand{\pagenumbering}{s m}{}
```

```
\end{warpHTML}
```

51 HTML tags, spans, divs, elements

for HTML output:

```
\begin{warpHTML}
```

51.1 Mapping LaTeX sections to HTML sections

```
\newcommand*{\LWR@tagtitle}{h1}
\newcommand*{\LWR@tagtitleend}{/h1}
\newcommand*{\LWR@tagpart}{h2}
\newcommand*{\LWR@tagpartend}{/h2}
\newcommand*{\LWR@tagchapter}{h3}
\newcommand*{\LWR@tagchapterend}{/h3}
\newcommand*{\LWR@tagsection}{h4}
\newcommand*{\LWR@tagsectionend}{/h4}
\newcommand*{\LWR@tagsubsection}{h5}
\newcommand*{\LWR@tagsubsectionend}{/h5}
\newcommand*{\LWR@tagsubsubsection}{h6}
\newcommand*{\LWR@tagsubsubsectionend}{/h6}
\newcommand*{\LWR@tagparagraph}{span class="paragraph"}
\newcommand*{\LWR@tagparagraphend}{/span}
\newcommand*{\LWR@tagsubparagraph}{span class="subparagraph"}
\newcommand*{\LWR@tagsubparagraphend}{/span}

\newcommand*{\LWR@tagregularparagraph}{p}
```

51.2 Babel-French tag modifications

Adjust babel-french for HTML spaces. So far, this only works for *pdflatex* and *xelatex*.

(*Emulates or patches code by* Daniel Flipo.)

```
\providecommand*{\LWR@FBcancel}{}

\AtBeginDocument{%
\@ifundefined{frenchbsetup}%
{}%
{%
    \frenchbsetup{FrenchFootnotes=false}%
```

```
%
    \LetLtxMacro\LWR@FBcancel\NoAutoSpacing%
    \renewrobustcmd*{\FBcolonspace}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand{}nbsp;%
        \endgroup%
    }%
    \renewrobustcmd*{\FBthinspace}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand\LWR@origpound{}x202f;% \,
        \endgroup%
    }%
    \renewrobustcmd*{\FBguillspace}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand{}nbsp;% ~,  for \og xyz \fg{}
        \endgroup%
    }%
    \DeclareDocumentCommand{\FBmedkern}{}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand\LWR@origpound{}x202f;% \,
        \endgroup%
    }%
    \DeclareDocumentCommand{\FBthickkern}{}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand{}nbsp;% ~
        \endgroup%
    }%
    \renewrobustcmd*{~}{\HTMLentity{nbsp}}% was overwritten by babel-french
    \ifFBunicode%
    \else%
        \DeclareTextSymbol{\FBtextellipsis}{LY1}{133}%
        \DeclareTextCommandDefault{\FBtextellipsis}{\textellipsis\xspace}%
    \fi%
}%
}
```

51.3 HTML output formatting

Helps format the output HTML code for human readability.

\LWR@indentHTML Newline and indent the output HTML code.

```
\newcommand*{\LWR@indentHTML}{%
    \LWR@orignewline\LWR@origrule{2em}{0pt}%
}
```

51.4 HTML tags

\LWR@htmltagc {⟨*tag*⟩} Break ligatures and use upright apostrophes in HTML tags.

\protect is in case the tag appears in TOC, LOF, LOT.

```
\newcommand*{\LWR@htmltagc}[1]{%
\LWR@traceinfo{LWR@htmltagc !\detokenize{#1}!}%
\begingroup%
\LWR@FBcancel%
\ifmmode\else\protect\LWR@origttfamily\fi%
\protect\LWR@origtextless%
\LWR@isolate{#1}%
\protect\LWR@origtextgreater%
\endgroup%
}
```

Env LWR@nestspan Disable minipage, \parbox, and HTML s inside a .

⚠ \begin{LWR@nestspan} must follow the opening tag to allow a paragraph to start if the span is at the beginning of a new paragraph.

⚠ \end{LWR@nestspan} must follow the or a <p> may appear inside the span.

```
\newcommand*{\LWR@nestspanitem}{%
\if@newlist\else{\LWR@htmltagc{br /}}\fi%
\LWR@origitem%
}

\newenvironment*{LWR@nestspan}
{%
\LWR@traceinfo{LWR@nestspan starting}%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{%
    \LWR@traceinfo{LWR@nestspan: inside a lateximage}%
}%
{% not in a lateximage
    \LWR@traceinfo{LWR@nestspan: NOT inside a lateximage}%
    \addtocounter{LWR@spandepth}{1}%
    \RenewDocumentEnvironment{minipage}{O{t} o O{t} m}{}{}%
    \RenewDocumentEnvironment{BlockClass}{o m}{}{}%
    \renewcommand{\BlockClassSingle}[2]{##2}%
    \renewcommand{\LWR@forcenewpage}{}%
    \renewcommand{\LWR@liststart}{%
        \let\item\LWR@nestspanitem%
    }%
    \renewcommand{\LWR@listend}{\LWR@htmltagc{br /}\LWR@htmltagc{br /}}%
}% not in a lateximage
\LWR@traceinfo{LWR@nestspan starting: done}%
}% starting env
{% ending env
\LWR@traceinfo{LWR@nestspan ending}%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{}%
```

```
{\addtocounter{LWR@spandepth}{-1}}%
\LWR@traceinfo{LWR@nestspan ending: done}%
}

\AfterEndEnvironment{LWR@nestspan}{\global\let\par\LWR@closeparagraph}
```

`\LWR@htmlspan` {⟨*tag*⟩} {⟨*text*⟩}

`\LWR@spandepth` is used to ensure that paragraph tags are not generated inside a span. The exact sequence of when to add and subtract the counter is important to correctly handle the paragraph tags before and after the span.

```
\NewDocumentCommand{\LWR@htmlspan}{m +m}{%
\LWR@ensuredoingapar%
\LWR@htmltagc{#1}%
\begin{LWR@nestspan}%
#2%
\LWR@htmltagc{/#1}%
\end{LWR@nestspan}%
}
```

`\LWR@htmlspanclass` [⟨*style*⟩] {⟨*class*⟩} {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@htmlspanclass}{o m +m}{%
\LWR@traceinfo{LWR@htmlspanclass |#1|#2|}%
\LWR@ensuredoingapar%
\LWR@subhtmlelementclass{span}[#1]{#2}%
\begin{LWR@nestspan}%
#3%
\LWR@htmltagc{/span}%
\LWR@traceinfo{LWR@htmlspanclass done}%
\end{LWR@nestspan}%
}
```

`\LWR@htmltag` {⟨*tag*⟩}

Print an HTML tag: <tag>

```
\newcommand*{\LWR@htmltag}[1]{%
% \LWR@traceinfo{LWR@htmltagb !\detokenize{#1}!}%
\LWR@htmltagc{#1}%
% \LWR@traceinfo{LWR@htmltagb: done}%
}
```

51.5 Block tags and comments

In the following, `\origttfamily` breaks ligatures, which may not be used for HTML codes:

\LWR@htmlopencomment
\LWR@htmlclosecomment

```
\newcommand*{\LWR@htmlopencomment}{%
{%
% \LWR@traceinfo{LWR@htmlopencomment}%
\begingroup%
\LWR@FBcancel%
\ifmmode\else\protect\LWR@origttfamily\fi%
\LWR@print@mbox{\LWR@origtextless{}!-\/-}%
\endgroup%
}%
}

\newcommand*{\LWR@htmlclosecomment}{%
{%
% \LWR@traceinfo{LWR@htmlclosecomment}%
\begingroup%
\LWR@FBcancel%
\ifmmode\else\protect\LWR@origttfamily\fi%
\LWR@print@mbox{-\/-\LWR@origtextgreater}%
\endgroup%
}%
}
```

\LWR@htmlcomment {⟨*comment*⟩}

```
\newcommand{\LWR@htmlcomment}[1]{%
\LWR@htmlopencomment{}%
{%
\LWR@origttfamily% break ligatures
#1%
}%
\LWR@htmlclosecomment{}}
```

\LWR@htmlblockcomment {⟨*comment*⟩}

```
\newcommand{\LWR@htmlblockcomment}[1]
{\LWR@stoppars\LWR@htmlcomment{#1}\LWR@startpars}
```

\LWR@htmlblocktag {⟨*tag*⟩} print a stand-alone HTML tag

```
\newcommand*{\LWR@htmlblocktag}[1]{%
\LWR@stoppars%
\LWR@htmltag{#1}%
\LWR@startpars%
}
```

51.6 Div class and element class

\LWR@subhtmlelementclass {⟨*element*⟩} [⟨*style*⟩] {⟨*class*⟩}

Factored and reused in several places.

The trailing spaces allow more places for a line break.

The use of `\textquotedbl` instead of " provides improved compatibility with xeCJK.

```
\NewDocumentCommand{\LWR@subhtmlelementclass}{m O{} m}{%
\LWR@traceinfo{LWR@subhtmlelementclass !#1!#2!#3!}%
\ifblank{#2}%
{% empty option
    \LWR@htmltag{%
        #1 % space
        class=\textquotedbl#3\textquotedbl\ % space
    }%
}%
{% non-empty option
    \LWR@htmltag{%
        #1\LWR@indentHTML%
        class=\textquotedbl#3\textquotedbl\LWR@indentHTML%
        style=\textquotedbl#2\textquotedbl\LWR@orignewline%
    }%
}%
\LWR@traceinfo{LWR@subhtmlelementclass done}%
}
```

`\LWR@htmlelementclass` {⟨*element*⟩} {⟨*class*⟩} [⟨*style*⟩]

```
\NewDocumentCommand{\LWR@htmlelementclass}{m o m}{%
\LWR@stoppars%
\LWR@subhtmlelementclass{#1}[#2]{#3}%
\LWR@startpars%
}
```

`\LWR@htmlelementclassend` {⟨*element*⟩} {⟨*class*⟩}

```
\newcommand*{\LWR@htmlelementclassend}[2]{%
\LWR@stoppars%
\LWR@htmltag{/#1}%
\ifbool{HTMLDebugComments}{%
    \LWR@htmlcomment{End of #1 ‘‘#2’’}%
}{}%
\LWR@startpars%
}
```

`\LWR@htmldivclass` [⟨*style*⟩] {⟨*class*⟩}

```
\NewDocumentCommand{\LWR@htmldivclass}{o m}{%
\LWR@htmlelementclass{div}[#1]{#2}%
}
```

`\LWR@htmldivclassend` {⟨*class*⟩}

```
\newcommand*{\LWR@htmldivclassend}[1]{%
\LWR@htmlelementclassend{div}{#1}%
}
```

51.7 Single-line elements

A single-line element, without a paragraph tag for the line of text:

`\LWR@htmlelementclassline` {⟨*element*⟩} [⟨*style*⟩] {⟨*class*⟩} {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@htmlelementclassline}{m o m +m}{%
\LWR@stoppars
\LWR@subhtmlelementclass{#1}[#2]{#3}%
#4%
\LWR@htmltag{/#1}
\LWR@startpars
}
```

51.8 HTML5 semantic elements

`\LWR@htmlelement` {⟨*element*⟩}

```
\newcommand*{\LWR@htmlelement}[1]{%
\LWR@htmlblocktag{#1}
}
```

`\LWR@htmlelementend` {⟨*element*⟩}

```
\newcommand*{\LWR@htmlelementend}[1]{%
\LWR@stoppars
\LWR@htmltag{/#1}
\LWR@startpars
}

\end{warpHTML}
```

51.9 High-level block and inline classes

These are high-level commands which allow the creation of arbitrary block or inline sections which may be formatted with CSS.

Nullified versions are provided for print mode.

For other direct-formatting commands, see section 89.

Env `BlockClass` [⟨*style*⟩] {⟨*class*⟩} High-level interface for classes.

Ex: \begin{BlockClass}{class} text \end{BlockClass}

for PRINT output:

```
\begin{warpprint}
\NewDocumentEnvironment{BlockClass}{o m}{}{}%
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
\NewDocumentEnvironment{LWR@print@BlockClass}{o m}{}{}%
\NewDocumentEnvironment{LWR@HTML@BlockClass}{o m}%
{%
    \LWR@origpar%
    \LWR@htmldivclass[#1]{#2}%
}
{\LWR@htmldivclassend{#2}}

\LWR@formattedenv{BlockClass}
\end{warpHTML}
```

`\BlockClassSingle` {⟨*class*⟩} {⟨*text*⟩} A single-line , without a paragraph tag for the line of text.

for HTML & PRINT:

```
\begin{warpall}
\newcommand{\BlockClassSingle}[2]{#2}
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
\newcommand{\LWR@HTML@BlockClassSingle}[2]{%
\LWR@origpar%
\LWR@htmlelementclassline{div}{#1}{#2}%
}

\LWR@formatted{BlockClassSingle}
\end{warpHTML}
```

`\InlineClass` (⟨*WP style*⟩) [⟨*style*⟩] {⟨*class*⟩} {⟨*text*⟩}

High-level interface for inline span classes.

(⟨*WP style*⟩) is css styling to add when formatting for a word processor import.

[⟨*style*⟩] is the css styling to add when not formatting for a word processor.

for PRINT output:

```
\begin{warpprint}
\NewDocumentCommand{\InlineClass}{D{(}{)}{} o m +m}{#4}%
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
\NewDocumentCommand{\LWR@print@InlineClass}{D{(}{)}{} o m +m}{#4}%

\NewDocumentCommand{\LWR@HTML@InlineClass}{D{(}{)}{} o m +m}{%
\ifbool{FormatWP}{%
    \LWR@htmlspanclass[#1]{#3}{#4}%
}{%
```

```
    \LWR@htmlspanclass[#2]{#3}{#4}%
}%
}

\LWR@formatted{InlineClass}
\end{warpHTML}
```

Env LWR@BlockClassWP {⟨*WPstyle*⟩} {⟨*HTMLstyle*⟩} {⟨*class*⟩} Low-level interface for classes with an automatic float ID. These are often used when \ifbool{FormatWP}.

The use of \textquotedbl instead of " provides improved compatibility with xeCJK.

for PRINT output:

```
\begin{warpprint}
\NewDocumentEnvironment{LWR@BlockClassWP}{m m m}{}{}%
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
\NewDocumentEnvironment{LWR@print@LWR@BlockClassWP}{m m m}{}{}%
\NewDocumentEnvironment{LWR@HTML@LWR@BlockClassWP}{m m m}%
{%
\LWR@stoppars%
\ifbool{FormatWP}%
{%
    \addtocounter{LWR@thisautoidWP}{1}%

    \LWR@htmltag{%
        div class=\textquotedbl#3\textquotedbl\ % space
        id=\textquotedbl%
            \LWR@print@mbox{autoidWP-\arabic{LWR@thisautoidWP}}%
        \textquotedbl%
        \ifblank{#1}{}{ style=\textquotedbl#1\textquotedbl}%
    }%
}% FormatWP
{% not FormatWP
    \LWR@htmltag{%
        div class=\textquotedbl#3\textquotedbl%
        \ifblank{#2}{}{ style=\textquotedbl#2\textquotedbl}%
    }%
}% not FormatWP
\LWR@startpars%
}
{\LWR@htmldivclassend{#3}}

\LWR@formattedenv{LWR@BlockClassWP}
\end{warpHTML}
```

51.10 Closing HTML tags

for HTML output:

```
\begin{warpHTML}
```

Sections H1, H2, etc. do not need a closing HTML tag, but we add a comment for readability:

```
\newcommand*{\LWR@printclosepart}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing part}}{}}
\newcommand*{\LWR@printclosechapter}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing chapter}}{}}
\newcommand*{\LWR@printclosesection}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing section}}{}}
\newcommand*{\LWR@printclosesubsection}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsection}}{}}
\newcommand*{\LWR@printclosesubsubsection}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsubsection}}{}}
\newcommand*{\LWR@printcloseparagraph}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing paragraph}}{}}
\newcommand*{\LWR@printclosesubparagraph}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subparagraph}}{}}
```

Lists require closing HTML tags:

```
\newcommand*{\LWR@printcloselistitem}
    {\LWR@htmltag{/li}}
\newcommand*{\LWR@printclosedescitem}
    {\LWR@htmltag{/dd}}
\newcommand*{\LWR@printcloseitemize}
    {\LWR@htmltag{/ul}}
\newcommand*{\LWR@printcloseenumerate}
    {\LWR@htmltag{/ol}}
\newcommand*{\LWR@printclosedescription}
    {\LWR@htmltag{/dl}}
```

```
\end{warpHTML}
```

52 Paragraph handling

These commands generate the HTML paragraph tags when allowed and required.

Paragraph tags are or are not allowed depending on many conditions. Section 53 has high-level commands which allow paragraph-tag generation to start/stop. Even when allowed (`\LWR@doingstartpars`), tags are not generated until a LaTeX paragraph is being used (`\LWR@doingapar`). `LWR@lateximagedepth` is used to prevent nesting tags inside a `lateximage`. `LWR@spandepth` is used to prevent nesting paragraph tags inside a paragraph, which became important inside `\fbox` commands and other spans.

for HTML output:

```
\begin{warpHTML}
```

Ctr `LWR@spandepth` Do not create paragraph tags inside of an HTML span.

```
\newcounter{LWR@spandepth}
\setcounter{LWR@spandepth}{0}
```

Bool LWR@doingstartpars Tells whether paragraphs may be generated.

```
\newbool{LWR@doingstartpars}
\boolfalse{LWR@doingstartpars}
```

Bool LWR@doingapar Tells whether have actually generated and are currently processing paragraph text.

```
\newbool{LWR@doingapar}
\global\boolfalse{LWR@doingapar}
```

\LWR@ensuredoingapar If are about to print something visible, and if allowed to start a new paragraph, ensure that are LWR@doingapar, so that paragraph tags are placed:

```
\newcommand*{\LWR@ensuredoingapar}{%
\ifbool{LWR@doingstartpars}%
{\global\booltrue{LWR@doingapar}}%
{}%
}
```

\PN@parnotes@auto Redefined by parnotes to print paragraph notes at the end of each paragraph.

```
\def\PN@parnotes@auto{}%
```

\LWR@openparagraph

```
\newcommand*{\LWR@openparagraph}
{%
```

See if paragraph handling is enabled:

```
\ifbool{LWR@doingstartpars}%
{% handling pars
```

See if have already started a lateximage or a . If so, do not generate nested paragraph tags.

```
    \ifboolexpr{
        test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
        test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
    }% nested par tags?
```

If so: Do nothing if already started a lateximage page. Cannot nest a lateximage. Also do nothing if already inside a . Do not nest paragraph tags inside a .

```
    {}% no nested par tags
```

Else: No lateximage or has been started yet, so it's OK to generate paragraph tags.

```
    {% yes nest par tags
```

If parnotes is used, paragraph notes are inserted before starting the next paragraph:

```
        \PN@parnotes@auto%
```

The opening paragraph tag:

```
        \LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline%
```

Now have started a paragraph.

```
        \global\booltrue{LWR@doingapar}%
```

At the endof each paragraph, generate closing tag and do regular /par stuff. (Attempting to use the everyhook cr hook for \LWR@closeparagraph does not work well.)

```
        \let\par\LWR@closeparagraph%
    }% end of yes nest par tags
}% end of handling pars
{}% not handling pars
}
```

\LWR@closeparagraph@br Add an HTML break if in a span, and not in a lateximage, and not in tabular metadata. Factored from \LWR@closeparagraph.

```
\newcommand*{\LWR@closeparagraph@br}
{%
    \ifboolexpr{
        test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}} and
        test {\ifnumcomp{\value{LWR@lateximagedepth}}{=}{0}} and
        not bool {LWR@intabularmetadata}
    }%
        {\unskip\LWR@htmltagc{br /}}%
        {}%
}
```

\LWR@closeparagraph

```
\newcommand*{\LWR@closeparagraph}
{%
% \LWR@traceinfo{LWR@closeparagraph}%
```

See if paragraph handling is enabled:

```
\ifbool{LWR@doingapar}%
```

If currently in paragraph mode:

```
{% handling pars
```

See if already started a lateximage or a :

```
    \ifboolexpr{
```

```
        test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
        test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
    }%
```

Add a parbreak if in a span, not in a lateximage, and not in table metadata.

```
    {% no nested par tags
        \LWR@closeparagraph@br%
    }% no nested par tags
```

If have not already started a `lateximage` or a :

```
    {% yes nest par tags
```

Print a closing tag and some extra vertical space.

```
        \leavevmode\LWR@orignewline%
        \LWR@htmltagc{/\LWR@tagregularparagraph}%
        \LWR@orignewline%
```

No longer doing a paragraph:

```
        \global\boolfalse{LWR@doingapar}%
```

Disable the special `minipage` & `\hspace` interaction until a new minipage is found:

```
        \global\boolfalse{LWR@minipagethispar}%
```

If parnotes is used, paragraph notes are inserted after ending the previous paragraph:

```
        \PN@parnotes@auto%
    }% end of yes nest par tags
}% end of handling pars
```

Add a parbreak if in a span, not in a lateximage, and not in table metadata.

```
{% not handling pars
    \LWR@closeparagraph@br%
}% not handling pars
```

In most cases, finish with a LaTeX `\par`, but in the case of paragraphs between lines in a tabular fetch the next token instead:

```
\ifboolexpr{%
    not bool {LWR@doingapar} and
    test {\ifnumcomp{\value{LWR@tabulardepth}}{>}{0}} and
    test {
        \ifnumcomp{\value{LWR@tabulardepth}}{=}{\value{LWR@tabularpardepth}}
    } and
    bool {LWR@intabularmetadata} and
    not bool {LWR@tableparcell} and
    test {\ifnumcomp{\value{LWR@lateximagedepth}}{=}{0}}
```

```
}%
{%
    \LWR@getmynexttoken%
}{%
    \LWR@origpar%
}%
}
```

```
\end{warpHTML}
```

53 Paragraph start/stop handling

These commands allow/disallow the generation of HTML paragraph tags.

Section 52 has the commands which actually generate the tags.

The everyhook package is used to generate the opening paragraph tags. The closing tags are generated by \par.

for HTML output:

```
\begin{warpHTML}
```

\LWR@startpars

Begin handling HTML paragraphs. This allows an HTML paragraph to start, but one has not yet begun.

```
\newcommand*{\LWR@startpars}%
{%
% \LWR@traceinfo{LWR@startpars}%
```

Ignore if inside a span:

```
\ifnumcomp{\value{LWR@spandepth}}{>}{0}%
{}%
{%
```

See if currently handling HTML paragraphs:

```
    \ifbool{LWR@doingstartpars}%
```

If already in paragraph mode, do nothing.

```
    {}%
```

If not currently in paragraph mode:

```
    {%
```

At the start of each paragraph, generate an opening tag:

```
        \PushPreHook{par}{\LWR@openparagraph}%
```

At the end of each paragraph, generate closing tag then do regular /par actions:

```
        \let\par\LWR@closeparagraph

    }% an intentionally blank line
```

Are now handling paragraphs, but have not yet actually started one:

```
    \global\setbool{LWR@doingstartpars}{true}%
```

No <par> tag yet to undo:

```
    \global\boolfalse{LWR@doingapar}%
}% nestspan
% \LWR@traceinfo{LWR@startpars: done}%
}
```

\LWR@stoppars Stop handling HTML paragraphs. Any currently open HTML paragraph is closed, and no more will be opened.

```
\newcommand*{\LWR@stoppars}%
{%
```

Ignore if inside a span:

```
\ifnumcomp{\value{LWR@spandepth}}{>}{0}%
{}%
{%
```

See if currently handling HTML paragraphs:

```
    \ifbool{LWR@doingapar}%
```

if currently in an HTML paragraph:

```
    {%
```

Print a closing tag:

```
        \leavevmode\LWR@orignewline%
        \LWR@htmltagc{/\LWR@tagregularparagraph}%
        \LWR@orignewline%
```

No longer have an open HTML paragraph:

```
        \global\boolfalse{LWR@doingapar}%
```

Disable the special minipage & \hspace interaction until a new minipage is found:

```
        \global\boolfalse{LWR@minipagethispar}

    }% an intentionally blank line
```

If was not in an HTML paragraph:

```
    {}%
```

See if currently allowing HTML paragraphs:

```
    \ifbool{LWR@doingstartpars}%
```

If so: clear the par hook to no longer catch paragraphs:

```
        {\ClearPreHook{par}}%
```

Else: Do nothing:

```
        {}%
```

No longer in paragraph mode:

```
    \global\setbool{LWR@doingstartpars}{false}%
```

No <p> tag to undo:

```
    \global\boolfalse{LWR@doingapar}%
}% nestspan
}

\end{warpHTML}
```

54 Indentfirst

Pkg indentfirst indentfirst redefines `\@afterindentfalse` to be `\@afterindenttrue`. This is reversed `\AtBeginDocument` here.

for HTML output:

```
\begin{warpHTML}

\AtBeginDocument{
\def\@afterindentfalse{\let\if@afterindent\iffalse}
\@afterindentfalse
}
\let\LWR@afterindent@syntaxhighlight\fi% syntax highlighting

\end{warpHTML}
```

55 Page headers and footers

for HTML & PRINT:

```
\begin{warpall}
```

In the following, catcode is manually changed back and forth without groups, since new macros are being defined which must not be contained within the groups.

```
\newcommand{\LWR@firstpagetop}{} % for the home page alone
\newcommand{\LWR@pagetop}{} % for all other pages
\newcommand{\LWR@pagebottom}{}
```

`\HTMLFirstPageTop` {⟨*text and logos*⟩}

```
\newcommand{\HTMLFirstPageTop}[1]{%
    \renewcommand{\LWR@firstpagetop}{#1}%
}
```

`\HTMLPageTop` {⟨*text and logos*⟩}

```
\newcommand{\HTMLPageTop}[1]{%
    \renewcommand{\LWR@pagetop}{#1}%
}
```

`\HTMLPageBottom` {⟨*text and logos*⟩}

```
\newcommand{\HTMLPageBottom}[1]{%
    \renewcommand{\LWR@pagebottom}{#1}%
}

\end{warpall}
```

56 css

for HTML output:

```
\begin{warpHTML}
```

`\LWR@currentcss` The css filename to use. This may be changed mid-document using `\CSSFilename`, allowing different css files to be used for different sections of the document.

```
\newcommand*{\LWR@currentcss}{lwarp.css}
```

`\CSSFilename` {⟨*new-css-filename.css*⟩} Assigns the css file to be used by the following HTML pages.

```
\newcommand*{\CSSFilename}[1]{%
\renewcommand*{\LWR@currentcss}{#1}%
\@onelevel@sanitize\LWR@currentcss%
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand*{\CSSFilename}[1]{}
\end{warpprint}
```

57 Title, HTML meta author, HTML meta description

for HTML output:

```
\begin{warpHTML}
```

`\title` {⟨*title*⟩} Modified to remember `\thetitle`, which is used to set the HTML page titles.

```
\let\LWR@origtitle\title

\renewcommand*{\title}[1]{%
    \LWR@origtitle{#1}%
    \begingroup%
        \renewcommand{\thanks}[1]{}%
        \protected@xdef\thetitle{#1}%
    \endgroup%
}
```

```
\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

`\HTMLTitle` {⟨*Titlename*⟩} The Title to place into an HTML meta tag. The default is to use the document `\title`'s setting.

```
\providecommand{\thetitle}{}

\newcommand{\theHTMLTitle}{\thetitle}

\newcommand{\HTMLTitle}[1]{\renewcommand{\theHTMLTitle}{#1}}
```

`\HTMLAuthor` {⟨*authorname*⟩} The author to place into an HTML meta tag. If none given, the default is `\theauthor`, which is empty unless the titling package is used.

```
\providecommand{\theauthor}{}

\newcommand{\theHTMLAuthor}{\theauthor}

\newcommand{\HTMLAuthor}[1]{\renewcommand{\theHTMLAuthor}{#1}}
```

This is placed inside an HTML meta tag at the start of each file. This may be changed mid-document using `\HTMLDescription`, allowing different HTML descriptions to be used for different sections of the document.

⚠ HTML author Do not use double quotes, and do not exceed 150 characters.

`\HTMLDescription` {⟨*New HTML meta description.*⟩} Assigns the HTML file's description meta tag.

```
\newcommand{\LWR@currentHTMLDescription}{}

\newcommand{\HTMLDescription}[1]{%
```

```
\renewcommand{\LWR@currentHTMLDescription}{#1}
}

\end{warpall}
```

58 Footnotes

lwarp uses native LaTeX footnote code, although with its own \box to avoid the LaTeX output routine. The usual functions mostly work as-is.

footnote numbering

To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For bigfoot, manyfoot, or perpage:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by FootnoteDepth, which is not necessarily by HTML page. This is recommended for \alph, \Alph, or \fnsymbol footnotes, due to the limited number of symbols which are available.

footmisc

The footmisc stable option is emulated by lwarp.

⚠ sectioning commands

When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the footmisc package with the stable option, provide a short TOC entry, and \protect the \footnote:

```
\usepackage[stable]{footmisc}
. . .
\subsection[Subsection Name]
    {Subsection Name\protect\footnote{A footnote.}}
```

memoir with footmisc

⚠ memoir

If using memoir class, with which lwarp preloads footmisc, the stable option must be declared before lwarp is loaded:

```
\PassOptionsToPackage{stable}{footmisc}
\usepackage{lwarp}
. . .
```

Do not use a starred sectioning command. As an alternative, it may be possible to adjust \secnumdepth instead.

Several kinds of footnotes are used: in a regular page, in a minipage, or as thanks in the titlepage. Each of these is handle differently.

58.1 Regular page footnotes

In HTML documents, footnotes are placed at the bottom of the web page or the section, depending on `FootnoteDepth`, using the LaTeX box `\LWR@footnotebox`. Using this instead of the original `\footins` box avoids having footnotes be printed by the output routine, since footnotes should be printed per HTML page instead of per PDF page.

See section 58.4 for the implementation.

58.2 Minipage footnotes

See section 58.5 for how minipage footnotes are gathered. See section 88.3 for how minipage footnotes are placed into the document.

58.3 Titlepage thanks

See section 65.7 for titlepage footnotes.

58.4 Regular page footnote implementation

for HTML & PRINT:

```
\begin{warpall}
```

Ctr `FootnoteDepth` Default: 3

Determines how deeply to place footnotes in the HTML files, similar to `tocdepth`. The default of 3 places footnotes before each `\subsubsection` or higher. See table 9 for a table of LaTeX section headings.

```
\newcounter{FootnoteDepth}
\setcounter{FootnoteDepth}{3}
```

Ctr `footnoteReset` Default: `0`

If non-zero, the `footnote` counter is reset to this value each time the footnotes are printed, as controlled by `FootnoteDepth`. For the manyfoot and bigfoot packages, additional counters such as `footnote<suffix>Reset` will be defined as well. These counters may be set non-zero by the user, and are also set if the perpage's `\MakePerPage` or `\MakeSortedPerPage` macros are used for the `footnote` or `footnote<suffix>` counters.

(The name is not capitalized because it is made from the counter's name with "Reset" appended.)

```
\newcounter{footnoteReset}
\setcounter{footnoteReset}{0}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@footnotebox Patch LaTeX footnotes to use a new \box instead of an insert for lwarp footnotes. This avoids having the original \footins appear at the bottom of a lateximage, which is on its own new page.

```
\newbox\LWR@footnotebox
```

Much of the following has unneeded print-mode formatting removed.

\@makefntext {⟨*text*⟩}

```
\long\def\@makefntext#1{\textsuperscript{\@thefnmark}~#1}
```

\@makefnmark

```
\def\@makefnmark{%
    \textsuperscript{\@thefnmark}%
}
```

Footnotes may be in regular text, in which case paragraphs are tagged, or in a table data cell or lateximage, in which case paragraph tags must be added manually.

In a lateximage during HTML output, the lateximage is placed inside a print-mode minipage, but the footnotes are broken out by:

```
\def\@mpfn{footnote}
\def\thempfn{\thefootnote}
\let\@footnotetext\LWR@footnotetext
```

\LWR@@footnotetext {⟨*text*⟩} {⟨*footnote box name*⟩}

Factored to allow multiple footnote boxes for manyfoot.

```
\long\def\LWR@@footnotetext#1#2{%
\LWR@traceinfo{LWR@footnotetext}%
\global\setbox\csname #2\endcsname=\vbox{%
```

Add to any current footnotes:

```
    \unvbox\csname #2\endcsname%
```

Remember the footnote number for \ref:

```
    \protected@edef\@currentlabel{%
        \csname p@footnote\endcsname\@thefnmark%
    }% @currentlabel
```

Open a group:

```
    \color@begingroup%
```

Use HTML superscripts in the footnote even inside a lateximage:

```
    \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a lateximage:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {}%
        {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote to the list:

```
    \@makefntext{#1}%
```

Closing paragraph tag:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {\par}%
        {%
            \LWR@htmltagc{/\LWR@tagregularparagraph}%
            \LWR@orignewline%
        }%
```

Close the group:

```
    \color@endgroup%
}% vbox
```

Paragraph handling:

```
\LWR@ensuredoingapar%
}%
```

\LWR@footnotetext {⟨*text*⟩}

```
\long\def\LWR@footnotetext#1{\LWR@@footnotetext{#1}{LWR@footnotebox}}
```

\@footnotetext {⟨*text*⟩}

```
\LetLtxMacro\@footnotetext\LWR@footnotetext
```

58.5 Minipage footnote implementation

Patch LaTeX minipage footnotes to use a new \box instead of an insert for lwarp minipage footnotes. This avoids having the original \@mpfootins appear at the bottom of a lateximage, which is on its own new page.

```
\newbox\LWR@mpfootnotes
```

\@mpfootnotetext {⟨*text*⟩}

```
\long\def\@mpfootnotetext#1{%
\LWR@traceinfo{@mpfootnotetext}%
\global\setbox\LWR@mpfootnotes\vbox{%
    \unvbox\LWR@mpfootnotes%
    \reset@font\footnotesize%
    \hsize\columnwidth%
    \@parboxrestore%
    \protected@edef\@currentlabel%
        {\csname p@mpfootnote\endcsname\@thefnmark}%
    \color@begingroup%
```

Use paragraph tags if in a tabular data cell or a lateximage:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
    {}%
    {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%

    \@makefntext{%
        \ignorespaces#1%
    }%
```

Don't add the closing paragraph tag if are inside a lateximage:

```
    \ifthenelse{\cnttest{\value{LWR@lateximagedepth}}{>}{0}}%
        {}%
        {%
            \LWR@htmltagc{/\LWR@tagregularparagraph}%
            \LWR@orignewline%
        }%
    \color@endgroup%
}% vbox
```

Paragraph handling:

```
\LWR@ensuredoingapar%
\LWR@traceinfo{@mpfootnotetext: done}%
}
```

\thempfootnote Redefined to remove the \itshape, which caused an obscure compiling error in some situations.

```
\AtBeginDocument{
\def\thempfootnote{\@alph\c@mpfootnote}
}
```

58.6 Printing pending footnotes

\LWR@@printpendingfootnotes {⟨*footnote counter name*⟩}

```
\newcommand*{\LWR@@printpendingfootnotes}[1]{%
\expandafter\ifvoid\csname LWR@#1box\endcsname\else
    \LWR@forcenewpage
    \begin{BlockClass}{footnotes}
    \LWR@origmedskip
    \unvbox\csuse{LWR@#1box}
    \setbox\csuse{LWR@#1box}=\vbox{}
    \end{BlockClass}
    \ifltxcounter{#1Reset}{%
        \ifnumgreater{\value{#1Reset}}{0}{%
            \setcounter{#1}{\value{#1Reset}}%
            \addtocounter{#1}{-1}%
        }{}%
    }{}%
\fi
}
```

\LWR@printpendingfootnotes Enclose the footnotes in a class, print, then clear. For manynotes, new footnotes may be added via \appto.

```
\newcommand*{\LWR@printpendingfootnotes}{%
    \LWR@@printpendingfootnotes{footnote}%
}
```

\LWR@maybeprintpendingfootnotes {⟨*depth*⟩} Used to print footnotes before sections only if formatting for an EPUB or word processor:

```
\newcommand*{\LWR@maybeprintpendingfootnotes}[1]{%
\ifboolexpr{
    not test{\ifnumcomp{#1}{>}{\value{FootnoteDepth}}} or
    bool{FormatEPUB} or
    bool{FormatWP}
}%
{\LWR@printpendingfootnotes}%
{}%
}
```

\LWR@printpendingmpfootnotes Enclose the minipage footnotes in a class, print, then clear.

```
\newcommand*{\LWR@printpendingmpfootnotes}{%
\ifvoid\LWR@mpfootnotes\else
    \LWR@forcenewpage
    \begin{BlockClass}{footnotes}
    \LWR@print@vspace*{\baselineskip}
    \unvbox\LWR@mpfootnotes
    \setbox\LWR@mpfootnotes=\vbox{}
    \end{BlockClass}
\fi
}

\end{warpHTML}
```

59 Marginpars

`\marginpar` `[`⟨*left*⟩`]` `{`⟨*right*⟩`}` `\marginpar` may contains paragraphs, but in order to remain inline with the surrounding text lwarp nullifies block-related macros inside the `\marginpar`. Paragraph breaks are converted to `<br />` tags.

`\marginparBlock` `[`⟨*left*⟩`]` `{`⟨*right*⟩`}` To include block-related macros, use `\marginparBlock`, which takes the same arguments but creates a `<div>` instead of a `<span>`. A line break will occur in the text where the `\marginBlock` occurs.

for HTML output:

```
\begin{warpHTML}
```

`\marginpar` `[`⟨*left*⟩`]` `{`⟨*right*⟩`}`

```
\renewcommand{\marginpar}[2][]{%
\ifbool{FormatWP}%
{%
\begin{LWR@BlockClassWP}{width:2in; float:right; margin:10pt}{}{marginblock}
#2
\end{LWR@BlockClassWP}
}%
{%
    \LWR@htmlspanclass{marginpar}{#2}%
}%
}
```

`\marginparBlock` `[`⟨*left*⟩`]` `{`⟨*right*⟩`}`

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

HTML version.

```
\newcommand{\marginparBlock}[2][]{%
\ifbool{FormatWP}%
{%
\begin{LWR@BlockClassWP}{width:2in; float:right; margin:10pt}{}{marginblock}
```

```
#2
\end{LWR@BlockClassWP}
}%
{%
\begin{BlockClass}[width:2in; float:right; margin:10pt]{marginparblock}
#2
\end{BlockClass}
}%
}
```

\reversemarginpar

```
\renewcommand*{\reversemarginpar}{}
```

\normalmarginpar

```
\renewcommand*{\normalmarginpar}{}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

\marginparBlock `[`⟨*left*⟩`]` `{`⟨*right*⟩`}`

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

Print version.

```
\LetLtxMacro\marginparBlock\marginpar
```

```
\end{warpprint}
```

60 Splitting HTML files

- Files are split according to `FileDepth` and `CombineHigherDepths`.
- Filenames are sanitized by `\LWR@filenamenoblanks`.
- `\LWR@newhtmlfile` finishes an HTML page, adds a comment to tell where and how to split the file, then starts a new HTML page.

for HTML & PRINT:

```
\begin{warpall}
```

Ctr FileDepth `{`⟨*section depth*⟩`}` determines how deeply to break into new HTML files, similar to `tocdepth`. The default of -5 produces one large HTML file.

```
\newcounter{FileDepth}
\setcounter{FileDepth}{-5}
```

Bool CombineHigherDepths Combile higher-level sections together into one file?

```
\newbool{CombineHigherDepths}
\booltrue{CombineHigherDepths}
```

\FilenameLimit Maximum length of the generated filenames.

```
\newcommand*{\FilenameLimit}{80}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@thisfilename The currently-active filename or number. At first, this is the homepage.

```
\AtBeginDocument{
\ifbool{FileSectionNames}%
    {\newcommand*{\LWR@thisfilename}{\HomeHTMLFilename}}
    {\newcommand*{\LWR@thisfilename}{0}}
}
```

\LWR@thisnewfilename The filename being sanitized.

```
\newcommand*{\LWR@thisnewfilename}{}
```

\LWR@simplifyname * {⟨*expression*⟩} Simplify \LWR@thisnewfilename.

If starred, detokenizes the input expression. If found, changes the expression to a single detokenized dash.

```
\NewDocumentCommand{\LWR@simplifyname}{s m}{%
\IfBooleanTF{#1}{%
    \StrSubstitute{\LWR@thisnewfilename}%
        {\detokenize{#2}}%
        {\detokenize{-}}[\LWR@thisnewfilename]%
}{%
    \StrSubstitute{\LWR@thisnewfilename}%
        {#2}%
        {\detokenize{-}}[\LWR@thisnewfilename]%
}
}
```

\LWR@simplifycustom User-defined filename simplifications. Redefine with \newcommand.

```
\newcommand*{\LWR@simplifycustom}{}
```

\FilenameSimplify * {⟨*phrase*⟩} Assign a user-defined filename simplification. Appends to \LWR@simplifycustom.

```
\NewDocumentCommand{\FilenameSimplify}{s m}{%
```

```
\IfBooleanTF{#1}{%
    \appto{\LWR@simplifycustom}{%
        \LWR@simplifyname*{#2}%
    }%
}{%
    \appto{\LWR@simplifycustom}{%
        \LWR@simplifyname{#2}%
    }%
}%
}
```

\LWR@filenamenoblanks {⟨*filename*⟩}

Convert blanks into dashes, removes short words, store result in \LWR@thisfilename.

Also see \LWR@nullfonts for nullified macros.

```
\newcommand*{\LWR@filenamenoblanks}[1]{%
\begingroup
```

Locally temporarily disable direct-formatting commands, not used in filenames:

```
\LWR@nullfonts%
\renewcommand*{\LWR@htmltagc}[1]{}%
```

```
\edef\LWR@thisnewfilename{#1}%
```

Replaces common macros with hyphens. (\& is done by \LWR@nullfonts.)

```
\RenewDocumentCommand{\LWR@subsingledollar}{s m m m}{}%
\LWR@simplifyname{\_}
\LWR@simplifyname{\#}
\LWR@simplifyname{\textbackslash}
\LWR@simplifyname{\protect}
\LWR@simplifyname{\ }
\LWR@simplifyname{\textless}
\LWR@simplifyname{\textgreater}
```

```
\edef\LWR@thisnewfilename{\detokenize\expandafter{\LWR@thisnewfilename}}%
```

```
\LWR@traceinfo{LWR@filenamenoblanks edef: !\LWR@thisnewfilename!}%
\fullexpandarg%
```

Convert spaces into hyphens:

```
\LWR@simplifyname*{ }
```

Convert punctutation into hyphens:

```
\LWR@simplifyname*{!}
\LWR@simplifyname*{,}
```

```
\LWR@simplifyname*{'}
\LWR@simplifyname*{+}
\LWR@simplifyname*{,}
\LWR@simplifyname*{/}
\LWR@simplifyname*{:}
\LWR@simplifyname*{;}
\LWR@simplifyname*{=}
\LWR@simplifyname*{?}
\LWR@simplifyname*{@}
\LWR@simplifyname*{^}
\LWR@simplifyname*{&}
\LWR@simplifyname*{"}
\LWR@simplifyname*{<}
\LWR@simplifyname*{>}

\LWR@simplifyname{\LWRbackslash}
```

Braces are removed entirely to avoid extra dashes in the result.

```
\StrSubstitute{\LWR@thisnewfilename}%
    {\LWRleftbrace}{}[\LWR@thisnewfilename]%
\StrSubstitute{\LWR@thisnewfilename}%
    {\LWRrightbrace}{}[\LWR@thisnewfilename]%

\LWR@simplifyname{\LWRpercent}
\LWR@simplifyname{\LWRdollar}

\LWR@simplifyname*{|}
\LWR@simplifyname*{^}
\LWR@simplifyname*{~}
\LWR@simplifyname*{[}
\LWR@simplifyname*{]}
\LWR@simplifyname*{`}
```

Convert short words:

```
\LWR@simplifyname*{-s-}
\LWR@simplifyname*{-S-}
\LWR@simplifyname*{-a-}
\LWR@simplifyname*{-A-}
\LWR@simplifyname*{-an-}
\LWR@simplifyname*{-AN-}
\LWR@simplifyname*{-to-}
\LWR@simplifyname*{-TO-}
\LWR@simplifyname*{-by-}
\LWR@simplifyname*{-BY-}
\LWR@simplifyname*{-of-}
\LWR@simplifyname*{-OF-}
\LWR@simplifyname*{-and-}
\LWR@simplifyname*{-AND-}
\LWR@simplifyname*{-for-}
\LWR@simplifyname*{-FOR-}
\LWR@simplifyname*{-the-}
\LWR@simplifyname*{-THE-}
```

Convert custom words:

```
\LWR@simplifycustom%
```

Convert multiple hyphens:

```
\LWR@simplifyname*{-----}
\LWR@simplifyname*{----}
\LWR@simplifyname*{---}
\LWR@simplifyname*{--}
```

If pdfLaTeX and not `utf8` encoding, don't try to convert emdash, endash:

```
\ifPDFTeX% pdflatex or dvi latex
\ifdefstring{\inputencodingname}{utf8}{%
\LWR@simplifyname*{---}
%     emdash
\LWR@simplifyname*{--}
%     endash
}{}%
\else% not PDFTeX
\LWR@simplifyname*{---}
\LWR@simplifyname*{--}
\fi%
```

If starts with a dash, remove the leading dash:

```
\IfBeginWith{\LWR@thisnewfilename}{\detokenize{-}}{%
    \StrGobbleLeft{\LWR@thisnewfilename}{1}[\LWR@thisnewfilename]%
}{}%
```

If ends with a dash, remove the trailing dash:

```
\IfEndWith{\LWR@thisnewfilename}{\detokenize{-}}{%
    \StrGobbleRight{\LWR@thisnewfilename}{1}[\LWR@thisnewfilename]%
}{}%
```

Limits the length of the filename:

```
\StrLeft{\LWR@thisnewfilename}{\FilenameLimit}[\LWR@thisnewfilename]%
```

Return the global result:

```
\global\let\LWR@thisfilename\LWR@thisnewfilename%
\endgroup%
\LWR@traceinfo{LWR@filenamenoblanks: result is \LWR@thisfilename}%
}
```

Ctr `LWR@previousautopagelabel`

Remembers which autopage label was most recently generated. Used to avoid duplicates.

```
\newcounter{LWR@previousautopagelabel}
\setcounter{LWR@previousautopagelabel}{-1}
```

File *_html.aux A new entry in the *_html.aux file is used to help cross-references:

```
\newlabel{autopage-<nnn>}{{<x>}{<y>}}
```

\LWR@newautopagelabel {⟨*pagenumber counter*⟩}

```
\newcommand*{\LWR@newautopagelabel}[1]{%
\ifnumequal{\value{LWR@previousautopagelabel}}{\value{page}}%
{}% no action if this autopage label has already been defined
{%
    \label{autopage-\arabic{#1}}%
    \setcounter{LWR@previousautopagelabel}{\value{page}}
}%
}
```

60.1 Customizing MathJax

\LWR@customizedMathJax Additional MathJax definitions to be added to the start of each html page.

```
\newcommand*{\LWR@customizedMathJax}{}
```

\CustomizeMathJax MathJax does not have preexisting support every possible math function. Additional MathJax function definitions may be defined. These will be declared at the start of each html page, and thus will have a global effect.

Examples:

```
\CustomizeMathJax{
    \newcommand{\expval}[1]{\langle#1\rangle}
    \newcommand{\abs}[1]{\lvert#1\rvert}
}
\CustomizeMathJax{\newcommand{\arsinh}{\text{arsinh}}}
\CustomizeMathJax{\newcommand{\arcosh}{\text{arcosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
```

```
\newcommand*{\CustomizeMathJax}[1]{%
    \appto{\LWR@customizedMathJax}{%
        \(#1\)\par
    }%
}
```

\LWR@customizeMathJax

```
\newcommand{\LWR@customizeMathJax}{%
\ifbool{mathjax}{

\LWR@stoppars
\LWR@htmlcomment{Nullify \textbackslash{}ensuremath, footnotes for MathJax:}

```

```
\(\newcommand\ensuremath[1]{##1}\)

\(\newcommand\footnote[2][]{\text{( Footnote ##1 )}}\)

\(\newcommand\footnotemark[1][]{\text{( Footnote ##1 )}}\)

\LWR@htmlcomment{Additional customizations for MathJax:}

\LWR@customizedMathJax

\LWR@startpars
}{}
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

`\CustomizeMathJax` The print-mode version:

```
\newcommand*{\CustomizeMathJax}[1]{}
```

`\FilenameSimplify` * {⟨*expression*⟩}

```
\NewDocumentCommand{\FilenameSimplify}{s m}{}
```

```
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@newhtmlfile` {⟨*section name*⟩}

Finishes the current HTML page with footnotes, footer, navigation, then starts a new HTML page with an HTML comment telling where to split the page and what the new filename and CSS are, then adds navigation, side TOC, header, and starts the text body.

```
\newcommand*{\LWR@newhtmlfile}[1]{
\LWR@traceinfo{LWR@newhtmlfile}
```

At the bottom of the ending file:

```
\LWR@htmlelementclassend{section}{textbody}
\LWR@htmlelementclassend{div}{bodycontainer}
\LWR@htmlelementclassend{div}{bodyandsidetoc}

\LWR@printpendingfootnotes

```

No footer between files if EPUB:

```
\ifbool{FormatEPUB}
```

```
{}
{
    \LWR@htmlelement{footer}

    \LWR@pagebottom

    \LWR@htmlelementend{footer}
}
```

No bottom navigation if are finishing the home page or formatting for EPUB or a word-processor.

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {\ifnumcomp{\value{LWR@htmlfilenumber}}{>}{0}{\LWR@botnavigation}{}}
```

End of this HTML file:

```
\LWR@stoppars
\LWR@htmltag{/body}\LWR@orignewline
\LWR@htmltag{/html}\LWR@orignewline
\LWR@traceinfo{LWR@newhtmlfile: about to LWR@orignewpage}
\LWR@orignewpage

\addtocounter{LWR@htmlfilenumber}{1}%
```

If using a filename based on section name, create a version without blanks. The filename without blanks will be placed into `\LWR@thisfilename`. Duplicates will be detected using MD5 hashes.

If not using a filename, the file number will be used instead.

```
\ifbool{FileSectionNames}%
{%
```

Convert the section name to a filename with blanks and common words removed. The resulting filename is in `\LWR@thisfilename`.

```
    \LWR@filenamenoblanks{#1}%
```

Create a macro name from the MD5 hash of the file name, to detect duplicates:

```
    \edef\LWR@hashedname{\LWR@mdfive{\LWR@thisfilename}}%
```

If the macro name is not yet defined, this filename is unique.

```
    \ifcsundef{LWR@filename\LWR@hashedname}{%
```

If the filename is unique, create a macro using the hashed name, to be used to test for additional duplicates in the future.

```
        \csdef{LWR@filename\LWR@hashedname}{}%
    }{%
```

If the filename is not unique, create an error.

```
        \PackageError{lwarp}
            {
                Section name ``#1'', at the line number listed below,
                generates the filename ``\LWR@thisfilename'',
                which appears to be a duplicate.
               There is a previous section with an identical or similar name.%
            }
            {
                Lwarp sanitizes most symbols and a few common short words
                when generating file names, and this may cause a conflict.
            }
    }
}
```

If using file numbers instead of names, the name is set to the next file number.

```
{\renewcommand*{\LWR@thisfilename}{\arabic{LWR@htmlfilenumber}}}
```

Include an HTML comment to instruct lwarpmk where to split the files apart. Uses pipe-separated fields for `split_html.gawk`. Uses monospaced font with ligatures disabled for everything except the title.

```
\LWR@traceinfo{LWR@newhtmlfile: about to print start file}%
```

`\LWR@nullfonts` to allow math in a section name.

```
\begingroup%
\LWR@nullfonts%
\LWR@htmlblockcomment{%
|Start file|%
\LWR@htmlsectionfilename{\LWR@thisfilename}|%
}
\endgroup%
```

At the top of the starting file:

```
\LWR@stoppars

```

Start a new file with the given section name:

```
\LWR@filestart[#1]

```

Track the page numbers:

```
\setcounter{LWR@latestautopage}{\value{page}}%
\LWR@newautopagelabel{LWR@latestautopage}%
```

No navigation between files if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {\LWR@topnavigation}

```

No header if between files if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {
        \LWR@htmlelement{header}

        \LWR@pagetop

        \LWR@htmlelementend{header}
    }

```

The container for the sidetoc and text body:

```
\LWR@htmlelementclass{div}{bodyandsidetoc}
```

No sideTOC if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {\LWR@sidetoc}

```

Start of the <textbody>:

```
\LWR@htmlelementclass{div}{bodycontainer}
\LWR@htmlelementclass{section}{textbody}

```

Print title only if there is one. Skip if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}%
    {}%
    {%
        \ifcsvoid{thetitle}{}{%
            \LWR@printthetitle%
        }%
    }%

```

Keep paragraph tags disabled for now:

```
\LWR@stoppars

```

If using MATHJAX, disable \ensuremath by printing a nullified definition at the start of each file, and add further customizations:

```
\LWR@customizeMathJax
```

```
\LWR@traceinfo{LWR@newhtmlfile: done}
}

\end{warpHTML}
```

61 Sectioning

Sectioning and cross-references have been emulated from scratch, rather than try to patch several layers of existing LaTeX code and packages. Formatting is handled by CSS, so the emulated code has much less work to do than the print versions.

Unicode

⚠ accents in filenames

Section names and the resulting filenames with accented characters are partially supported, depending on the ability of *pdflatex* to generate characters and *pdftotext* to read them. If extra symbols appear in the text, it may be that *pdflatex* is actually producing a symbol over or under a character, resulting in *pdftotext* picking up the accent symbol separately.

XeLaTeX and LuaLaTeX directly support accented section and file names.

for HTML output:

```
\begin{warpHTML}
```

61.1 User-level starred section commands

`\ForceHTMLPage`

For HTML output, forces the next section to be on its own HTML page, if `FileDepth` allows, even if starred. For use with `\printindex` and others which generate a starred section which should be on its own HTML page. Also see `\ForceHTMLTOC`.

For print output, no effect.

```
\newbool{LWR@forcinghtmlpage}
\boolfalse{LWR@forcinghtmlpage}

\newcommand*{\ForceHTMLPage}{%
\global\booltrue{LWR@forcinghtmlpage}%
}
```

`\ForceHTMLTOC`

For HTML output, forces the next section to have a TOC entry, even if starred. For use with `\printindex` and others which generate a starred section which should be in the TOC so that it may be accessed via HTML. Not necessary if used with tocbibind. Also see `\ForceHTMLPage`.

For print output, no effect.

```
\newbool{LWR@forcinghtmltoc}
\boolfalse{LWR@forcinghtmltoc}

\newcommand*{\ForceHTMLTOC}{%
\global\booltrue{LWR@forcinghtmltoc}%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand*{\ForceHTMLPage}{}
\newcommand*{\ForceHTMLTOC}{}
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

61.2 Book class commands

`\mainmatter` ⚠ Declare the main matter section of the document. Does not reset the page number, which must be consecutive arabic numbers for the HTML conversion.

```
\newbool{LWR@mainmatter}
\DeclareDocumentCommand{\mainmatter}{}{%
\booltrue{LWR@mainmatter}%
}
```

`\frontmatter` Declare the front matter section of the document, using arabic numbering for the internal numbering. Does not reset the page number.

```
\DeclareDocumentCommand{\frontmatter}{}{%
\boolfalse{LWR@mainmatter}%
}
```

`\backmatter` Declare the back matter section of the document. Does not reset the page number.

```
\DeclareDocumentCommand{\backmatter}{}{%
\boolfalse{LWR@mainmatter}
}
```

61.3 Sectioning support macros

`\LWR@sectionumber` {⟨*section type*⟩}

Typeset a section number and its trailing space with CSS formatting:

```
\newcommand*{\LWR@sectionnumber}[1]{%
\InlineClass{sectionnumber}{#1}%
}
```

`autosec` A tag used by the TOC and index.

`\LWR@createautosec` {⟨*section type*⟩}

Create an autosection tag.

```
\newcommand*{\LWR@createautosec}[1]{%
\LWR@htmltag{%
    #1 % space
    id=\textquotedbl\LWR@print@mbox{autosec-\arabic{page}}\textquotedbl%
}%
}
```

`\LWR@pushoneclose` {⟨*depth*⟩} {⟨*printclose*⟩} Stacks the new sectioning level's closing tag, to be used when this section is closed some time later.

⚠ `\LWR@stoppars` must be executed first.

```
\NewDocumentCommand{\LWR@pushoneclose}{m m}{%
\LWR@traceinfo{LWR@pushoneclose #1}%
    \pushclose{#2}{#1}%
}
```

`\LWR@startnewdepth` {⟨*depth*⟩} {⟨*printclose*⟩}

Closes currently stacked tags of a lesser level, then opens the new nesting level by saving this new sectioning level's closing tag for later use.

⚠ `\LWR@stoppars` must be executed first.

```
\NewDocumentCommand{\LWR@startnewdepth}{m m}{%
```

Close any stacked sections up to this new one.

```
\LWR@closeprevious{#1}%
```

Push a new section depth:

```
\LWR@pushoneclose{#1}{#2}%
}
```

Ctr `LWR@prevFileDepth` Remembers the previous `LWR@FileDepth`.

Initialized to a deep level so that any section will trigger a new HTML page after the home page.

```
\newcounter{LWR@prevFileDepth}
\setcounter{LWR@prevFileDepth}{\LWR@depthsubparagraph}
```

`\@seccntformat` {⟨*sectiontype*⟩}

```
\def\@seccntformat#1{\csname the#1\endcsname\quad}
```

`\simplechapterdelim` Used by tocbibind and anonchap.

```
\newcommand*{\simplechapterdelim}{}
```

\@chapcntformat {⟨*sectiontype*⟩}

\let to \@seccntformat by default, but may be redefined by \simplechapter and \restorechapter from tocbibind or anonchap.

```
\let\@chapcntformat\@seccntformat
```

\@partcntformat {⟨*sectiontype*⟩}

\let to \@seccntformat by default, but may be redefined by ctex.

```
\let\@partcntformat\@seccntformat
```

\@partnameformat Prints "Part" for part sections.

Nullified by ctex.

```
\newcommand*{\@partnameformat}{\LWR@isolate{\partname}~}%
```

Ctr LWR@currentautosec Records the page number when the section was created. If a math expression is included in the section name, and SVG math is used, the corresponding lateximage will cause the page number to change by the time the following autosec label is created.

```
\newcounter{LWR@currentautosec}
\setcounter{LWR@currentautosec}{1}
```

\LWR@section * [⟨*TOC name*⟩] {⟨*name*⟩} {⟨*sectiontype*⟩}

The common actions for the high-level sectioning commands.

```
\DeclareDocumentCommand{\LWR@section}{m m m m}{%
\LWR@traceinfo{LWR@section: starting}%
\LWR@stoppars%
```

Cancel special minipage horizontal space interaction:

```
\global\boolfalse{LWR@minipagethispar}%
```

Start a new HTML file unless starred, and if is a shallow sectioning depth.

Exception: Also start a new HTML file for \part*, for appendix.

Generate a new LaTeX page so that TOC and index page number points to the section:

```
\LWR@traceinfo{LWR@section: testing whether to start a new HTML file}%
\IfBooleanT{#1}{\LWR@traceinfo{LWR@section: starred}}%
\ifbool{LWR@forcinghtmlpage}{\LWR@traceinfo{LWR@section: forcinghtmlpage}}{}%
\ifthenelse{%
    \(%
        \(\NOT\equal{#1}{\BooleanTrue}\)\OR%
```

```
        \(\cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}\)\OR%
        \(\boolean{LWR@forcinghtmlpage}\)%
    \)%
    \AND%
    \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{FileDepth}}%
    \AND%
    \(%
        \NOT\boolean{CombineHigherDepths}\OR%
        \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{LWR@prevFileDepth}}%
    \)%
    \AND%

    \(% phantomsection
        \NOT\isempty{#3}%
        \OR%
        \(\NOT\equal{#1}{\BooleanTrue}\)%
    \)%
}%
```

If so: start a new HTML file:

```
{% new file
    \LWR@traceinfo{LWR@section: new HTML file}%
```

See if there was an optional TOC name entry:

```
    \IfNoValueTF{#2}%
```

If no optional entry

```
        {\LWR@newhtmlfile{#3}}%
```

If yes an optional entry

```
        {\LWR@newhtmlfile{#2}}%
}% new file
```

Else: No new HTML file:

```
{% not new file
```

Generate a new LaTeX page so that TOC and index page number points to the section:

```
    \LWR@traceinfo{LWR@section: not a new HTML file, about to LWR@orignewpage}%
    \LWR@orignewpage%
}% not new file

```

Remember this section's name for `\nameref`:

```
\IfValueT{#3}{%
    \LWR@traceinfo{LWR@section: about to LWR@setlatestname}%
    \IfValueTF{#2}{\LWR@setlatestname{#2}}{\LWR@setlatestname{#3}}%
}%
```

Print an opening comment with the level and the name; ex: “section” “Introduction” Footnotes may be used in section names, which would also appear in the HTML section opening comments, so the short TOC entry is used if possible, and a limited opening comment is made if the sectional unit is starred.

```
\ifbool{HTMLDebugComments}{%
    \begingroup%
    \LWR@nullfonts%
    \IfBooleanTF{#1}% starred
    {\LWR@htmlcomment{Opening #4*}}%
    {%
        \IfNoValueTF{#2}% short TOC
            {\LWR@htmlcomment{Opening #4 ‘‘#3’’}}%
            {\LWR@htmlcomment{Opening #4 ‘‘#2’’}}%
    }\LWR@orignewline%
    \endgroup%
}{}
```

For inline sections paragraph and subparagraph, start a new paragraph now:

```
\ifthenelse{%
    \cnttest{\@nameuse{LWR@depth#4}}{>=}{\LWR@depthparagraph}%
}%
    {\LWR@startpars}%
    {}%
```

Create the opening tag with an autosec:

```
\LWR@traceinfo{LWR@section: about to LWR@createautosec}%
\LWR@createautosec{\@nameuse{LWR@tag#4}}%

\setcounter{LWR@currentautosec}{\value{page}}%
```

Check if starred:

```
\IfBooleanTF{#1}%
{%
    \LWR@traceinfo{LWR@section: starred}%
```

Starred, but also forcing a TOC entry, so add unnumbered TOC name or regular name:

```
    \ifbool{LWR@forcinghtmltoc}%
    {%
        \addcontentsline{toc}{#4}{%
            \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
        }%
    }%
    {}%
}% starred
```

Not starred, so step counter and add to TOC:

```
{% not starred
```

Only add a numbered TOC entry if section number is not too deep:

```
    \ifthenelse{%
        \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{secnumdepth}}%
    }%
    {% if secnumdepth
```

If in the main matter, step the counter and add the TOC entry. For `article` class, lwarp assumes that all is mainmatter.

```
        \LWR@traceinfo{LWR@section: about to test main matter}%
        \ifbool{LWR@mainmatter}%
        {%
            \LWR@traceinfo{LWR@section: yes mainmatter}%
            \refstepcounter{#4}%
```

Add main matter numbered TOC entry with the TOC name or the regular name:

```
            \LWR@traceinfo{LWR@section: about to addcontentsline}%
            \addcontentsline{toc}{#4}%
            {%
                \protect\numberline{%
                    \@nameuse{pre#4name}%
                    \@nameuse{the#4}%
                    \@nameuse{post#4name}%
                }%
                {%
                    \ignorespaces%
              \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}\protect\relax%
                }%
            }%
            \LWR@traceinfo{LWR@section: finished addcontentsline}%
        }% end of if main matter
```

If not main matter, add unnumbered TOC name or regular name:

```
        {% not main matter
            \LWR@traceinfo{LWR@section: no main matter}%
            \addcontentsline{toc}{#4}{%
                \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
            }%
        }% end of not main matter
    }% end of secnumdepth
```

Deeper than secnumdepth, so add an unnumbered TOC entry:

```
    {%
        \addcontentsline{toc}{#4}{%
            \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
        }%
    }%
```

For part, print “Part”:

```
    \ifbool{LWR@mainmatter}%
    {%
        \ifthenelse{%
            \(\cnttest{\@nameuse{LWR@depth#4}}{<=}%
                {\value{secnumdepth}}\) \AND%
            \(\cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}\)%
        }%
            {\@partnameformat}%
            {}%
```

Print the section number:

```
        \LWR@traceinfo{LWR@section: about to print section number}%
        \ifthenelse{%
            \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{secnumdepth}}%
        }%
            {%
                \ifstrequal{#4}{part}%
                {\protect\LWR@sectionnumber{\@partcntformat{#4}}}%
                {%
                    \ifstrequal{#4}{chapter}%
                        {\protect\LWR@sectionnumber{\@chapcntformat{#4}}}%
                        {\protect\LWR@sectionnumber{\@seccntformat{#4}}}%
                }%
            }%
            {}%
        \LWR@traceinfo{LWR@section: finished print section number}%
    }{}%
}% end of not starred
```

Print the section name:

```
\LWR@traceinfo{LWR@section: about to print the section name}%
\LWR@isolate{#3}%
```

Close the heading tag, such as /H2:

```
\LWR@traceinfo{LWR@section: about to close the heading tag}%
\LWR@htmltag{\@nameuse{LWR@tag#4end}}%
\LWR@orignewline%
```

Generate a LaTeX label:

```
\LWR@traceinfo{LWR@section: about to create the LaTeX label}%
\setcounter{LWR@latestautopage}{\value{page}}%
\LWR@newautopagelabel{LWR@currentautosec}\LWR@orignewline%
```

Start paragraph handing unless is an inline paragraph or subparagraph:

```
\ifthenelse{%
    \cnttest{\@nameuse{LWR@depth#4}}{<}{\LWR@depthparagraph}%
}%
    {\LWR@startpars}%
    {}%
```

If not starred, remember the previous depth to possibly trigger a new HTML page.

HOWEVER, allow a \part* to start a new HTML page. This is used by appendix.

A starred section does not trigger a new HTML page at the beginning of this macro, so it should not affect it here at the end either. This became an issue when a \listoftables was tested in the middle of the document. The \chapter* for the list was not allowing a new HTML page for the section following it while CombineHigherDepths was true.

```
\ifthenelse{%
    \NOT\equal{#1}{\BooleanTrue}\OR%
    \cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}%
}%
    {% not starred
        \setcounter{LWR@prevFileDepth}{\@nameuse{LWR@depth#4}}%
    }% not starred
    {}%
```

Reset to defaults if not a phantomsection:

```
\ifstrempty{#3}%
    {}%
    {%
        \global\boolfalse{LWR@forcinghtmlpage}%
        \global\boolfalse{LWR@forcinghtmltoc}%
    }%
%
\LWR@traceinfo{LWR@section: done}%
}
```

61.4 Pre- and post- sectioning names

\prepartname
\postpartname

Usually null, but is used by uj* and ut* Japanese classes.

```
\providecommand*{\prepartname}{}
\providecommand*{\postpartname}{}
```

\prechaptername
\postchaptername

Usually null, but is used by uj* and ut* Japanese classes.

```
\providecommand*{\prechaptername}{}
\providecommand*{\postchaptername}{}
```

\presectionname
\postsectionname

Always null, but provided here for algorithmic simplicity in \LWR@section.

```
\providecommand*{\presectionname}{}
\let\postsectionname\presectionname

\let\presubsectionname\presectionname
\let\postsubsectionname\postsectionname

\let\presubsubsectionname\presectionname
```

```
\let\postsubsubsectionname\postsectionname

\let\preparagraphname\presectionname
\let\postparagraphname\postsectionname

\let\presubparagraphname\presectionname
\let\postsubparagraphname\postsectionname
```

61.5 \section and friends

\part * [⟨*TOC name*⟩] {⟨*name*⟩}

```
\newcommand{\part@preamble}{}% for koma-script

\DeclareDocumentCommand{\part}{s o m}{%
\LWR@maybeprintpendingfootnotes{\LWR@depthpart}%
\LWR@stoppars%

\LWR@startnewdepth{\LWR@depthpart}{\LWR@printclosepart}%

\LWR@section{#1}{#2}{#3}{part}%

\part@preamble% for koma-script
\renewcommand{\part@preamble}{}%
}
```

\chapter * [⟨*TOC name*⟩] [⟨*heading name*⟩] {⟨*name*⟩}

```
\let\@printcites\relax% for quotchap package

\newcommand{\chapter@preamble}{}% for koma-script

\@ifundefined{chapter}
{}
{%
\DeclareDocumentCommand{\chapter}{s o o m}{%
\IfValueTF{#2}{
\LWR@traceinfo{chapter #2}%
}{
\LWR@traceinfo{chapter #4}%
}
\LWR@maybeprintpendingfootnotes{\LWR@depthchapter}%
\LWR@stoppars%

\LWR@startnewdepth{\LWR@depthchapter}{\LWR@printclosechapter}%

\LWR@section{#1}{#2}{#4}{chapter}%

\@printcites% for quotchap package

\chapter@preamble% for koma-script
\renewcommand{\chapter@preamble}{}%
```

```
}
}
```

`\section` `*` `[`⟨*TOC name*⟩`]` `[`⟨*heading name*⟩`]` `{`⟨*name*⟩`}`

```
\DeclareDocumentCommand{\section}{s o o m}{%
\LWR@traceinfo{section: starting}%
\LWR@maybeprintpendingfootnotes{\LWR@depthsection}%
\LWR@stoppars%

\LWR@startnewdepth{\LWR@depthsection}{\LWR@printclosesection}%

\LWR@section{#1}{#2}{#4}{section}%
}
```

`\subsection` `*` `[`⟨*TOC name*⟩`]` `{`⟨*name*⟩`}`

```
\DeclareDocumentCommand{\subsection}{s o m}{%
\LWR@maybeprintpendingfootnotes{\LWR@depthsubsection}%
\LWR@stoppars%

\LWR@startnewdepth{\LWR@depthsubsection}{\LWR@printclosesubsection}%

\LWR@section{#1}{#2}{#3}{subsection}%
}
```

`\subsubsection` `*` `[`⟨*TOC name*⟩`]` `{`⟨*name*⟩`}`

```
\DeclareDocumentCommand{\subsubsection}{s o m}{%
\LWR@maybeprintpendingfootnotes{\LWR@depthsubsubsection}%
\LWR@stoppars%

\LWR@startnewdepth{\LWR@depthsubsubsection}%
{\LWR@printclosesubsubsection}%

\LWR@section{#1}{#2}{#3}{subsubsection}%
}
```

`\paragraph` `*` `[`⟨*TOC name*⟩`]` `{`⟨*name*⟩`}`

```
\DeclareDocumentCommand{\paragraph}{s o m}{%
\LWR@maybeprintpendingfootnotes{\LWR@depthparagraph}%
\LWR@stoppars%

\LWR@startnewdepth{\LWR@depthparagraph}{\LWR@printcloseparagraph}%

\LWR@section{#1}{#2}{#3}{paragraph}%
}
```

`\subparagraph` `*` `[`⟨*TOC name*⟩`]` `{`⟨*name*⟩`}`

```
\DeclareDocumentCommand{\subparagraph}{s o m}{%
\LWR@maybeprintpendingfootnotes{\LWR@depthsubparagraph}%
\LWR@stoppars%

\LWR@startnewdepth{\LWR@depthsubparagraph}{\LWR@printclosesubparagraph}%

\LWR@section{#1}{#2}{#3}{subparagraph}%
}

\end{warpHTML}
```

62 Starting a new file

for HTML & PRINT:

```
\begin{warpall}
```

\HTMLLanguage Default language for the HTML lang tag.

```
\newcommand*{\LWR@currentHTMLLanguage}{en-US}

\newcommand*{\HTMLLanguage}[1]{%
\renewcommand*{\LWR@currentHTMLLanguage}{#1}%
}
```

\theHTMLTitleSeparator May be used inside \theHTMLTitleSection to separate the website's overall HTML title and the particular page's section name.

```
\ifPDFTeX% pdflatex or dvi latex
    \ifdefstring{\inputencodingname}{utf8}{%
        \newcommand*{\theHTMLTitleSeparator}{ --- }% EMdash
    }{%
        \newcommand*{\theHTMLTitleSeparator}{ - }% hyphen
    }%
\else%
    \ifpTeX
        \newcommand*{\theHTMLTitleSeparator}{ - }% hyphen
    \else
        \newcommand*{\theHTMLTitleSeparator}{ --- }% EMdash
    \fi%
\fi%
```

\HTMLTitleBeforeSection Sets the HTML page's meta title tag to show the website title before the section name.

```
\newcommand*{\HTMLTitleBeforeSection}{%
    \def\theHTMLTitleSection{%
        \theHTMLTitle\theHTMLTitleSeparator\theHTMLSection%
    }%
}
```

\HTMLTitleAfterSection Sets the HTML page's meta title tag to show the section name before the website title.

```
\newcommand*{\HTMLTitleAfterSection}{%
    \def\theHTMLTitleSection{%
        \theHTMLSection\theHTMLTitleSeparator\theHTMLTitle%
    }%
}
```

\theHTMLTitleSection Forms the HTML page's meta `title` tag. The default is to show the website title before the section name.

```
\HTMLTitleBeforeSection
```

\theHTMLSection The section name is passed to `\LWR@filestart`, which then sets `\theHTMLSection` for use inside `\theHTMLTitleSection` to create an HTML meta `title` tag.

```
\newcommand*{\theHTMLSection}{}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@filestart `[`⟨*sectionname*⟩`]` Creates the opening HTML tags.

```
\newcommand*{\LWR@filestart}[1][]{%
\LWR@traceinfo{LWR@filestart !#1!}%
```

Locally temporarily disable direct-formatting commands:

```
\begingroup%
\LWR@nullfonts%
```

Save the section name for use while creating the HTML meta `title` tag:

```
\edef\theHTMLSection{#1}%
```

Create the page's HTML header:

```
\LWR@htmltag{!DOCTYPE html}\LWR@orignewline
```

The language is user-adjustable:

```
\LWR@htmltag{%
   html lang=\LWR@orig@textquotedbl\LWR@currentHTMLLanguage\LWR@orig@textquotedbl%
}\LWR@orignewline
```

Start of the meta data:

```
\LWR@htmltag{head}\LWR@orignewline
```

Charset is fixed at UTF-8:

```
\LWR@htmltag{%
    meta charset=\LWR@orig@textquotedbl{}UTF-8\LWR@orig@textquotedbl\ /%
}\LWR@orignewline
```

Author:

```
\ifthenelse{\equal{\theHTMLAuthor}{}}%
    {}%
    {%
        \LWR@htmltag{%
        meta name=\LWR@orig@textquotedbl{}author\LWR@orig@textquotedbl\ % space
         content=\LWR@orig@textquotedbl\theHTMLAuthor\LWR@orig@textquotedbl\ /%
        }\LWR@orignewline%
    }%
```

lwarp is the generator:

```
\LWR@htmltag{%
    meta % space
    name=\LWR@orig@textquotedbl{}generator\LWR@orig@textquotedbl\ % space
   content=\LWR@orig@textquotedbl{}LaTeX lwarp package\LWR@orig@textquotedbl\ /%
}\LWR@orignewline%
```

If there is a description, add it now:

```
\ifdefempty{\LWR@currentHTMLDescription}{}{%
    \LWR@htmltag{%
      meta name=\LWR@orig@textquotedbl{}description\LWR@orig@textquotedbl\ % space
      content=\LWR@orig@textquotedbl\LWR@currentHTMLDescription\LWR@orig@textquotedbl\ /%
    }\LWR@orignewline
}%
```

Mobile-friendly viewport:

```
\LWR@htmltag{%
    meta % space
    name=\LWR@orig@textquotedbl{}viewport\LWR@orig@textquotedbl\ % space
   content=\LWR@orig@textquotedbl{}width=device-width, initial-scale=1.0\LWR@orig@textquotedbl\ /%
}\LWR@orignewline
```

IE patch:

```
\LWR@htmltag{!-\/-[if lt IE 9]}\LWR@orignewline
\LWR@htmltag{%
    script % space
    src=\LWR@orig@textquotedbl{}%
        http://html5shiv.googlecode.com/svn/trunk/html5.js%
    \LWR@orig@textquotedbl%
}%
\LWR@htmltag{/script}\LWR@orignewline
\LWR@htmltag{![endif]-\/-}\LWR@orignewline
```

The page's title, if there is one. A section name is also added if given.

```
\ifthenelse{\equal{\theHTMLTitle}{}}%
    {}%
    {%
        \LWR@htmltag{title}%
        \ifdefempty{\theHTMLSection}%
            {\theHTMLTitle}%
            {\theHTMLTitleSection}%
        \LWR@htmltag{/title}\LWR@orignewline%
    }%
```

The page's stylesheet:

```
\LWR@htmltag{%
    link % space
    rel=\LWR@orig@textquotedbl{}stylesheet\LWR@orig@textquotedbl\ % space
    type=\LWR@orig@textquotedbl{}text/css\LWR@orig@textquotedbl\ % space
    href=\LWR@orig@textquotedbl\LWR@currentcss\LWR@orig@textquotedbl\ /%
}%
\LWR@orignewline
```

Optional MathJax support. The HTML tags must be turned off during the verbatim input, and the paragraph handling which was turned on at the end of verbatim input must be immediately turned off again.

```
\ifbool{mathjax}%
{%
    \begingroup%
    \LWR@restoreoriglists%
    \boolfalse{LWR@verbtags}%

        \verbatiminput{lwarp_mathjax.txt}%

    \booltrue{LWR@verbtags}%
    \endgroup%
    \LWR@stoppars%
}% end of mathjax
{}%
```

End of the header:

```
\LWR@htmltag{/head}\LWR@orignewline
```

Start of the body:

```
\LWR@htmltag{body}\LWR@orignewline
\endgroup
\LWR@traceinfo{LWR@filestart: done}
}

\end{warpHTML}
```

63 Starting HTML output

for HTML output:

```
\begin{warpHTML}
```

`\LWR@LwarpStart` Executed at the beginning of the entire document.

The use of `\textquotedbl` instead of " improves compatibility with xeCJK.

```
\catcode`\$=\active
\newcommand*{\LWR@LwarpStart}
{%
\LWR@traceinfo{LWR@lwarpStart}
```

If formatting for a word processor, force filedepth to single-file only, force HTML debug comments off.

```
\ifbool{FormatWP}{%
    \setcounter{FileDepth}{-5}%
    \boolfalse{HTMLDebugComments}%
}{}
```

Expand and detokenize `\HomeHTMLFilename` and `\HTMLFilename`:

```
\edef\LWR@strresult{\HomeHTMLFilename}
\edef\HomeHTMLFilename{\detokenize\expandafter{\LWR@strresult}}
\edef\LWR@strresult{\HTMLFilename}
\edef\HTMLFilename{\detokenize\expandafter{\LWR@strresult}}
```

Force onecolumn and empty page style:

```
\LWR@origonecolumn%
\LWR@origpagestyle{empty}%
```

No black box for overfull lines:

```
\overfullrule=0pt
```

Reduce chance of line overflow when HTML tags are added:

```
\LWR@print@footnotesize%
```

In PDF output, don't allow line breaks to interfere with HTML tags:

```
\LWR@print@raggedright%
\LetLtxMacro{\\}{\LWR@endofline}%
```

Spread the lines for *pdftotext* to read them well:

```
\linespread{1.3}%
```

For *pdftotext* to reliably identify paragraph splits:

```
\setlength{\parindent}{0pt}
\setlength{\parskip}{2ex}
```

For the lateximage record file:

```
\immediate\openout\LWR@lateximagesfile=\BaseJobname-images.txt
```

Removes space around the caption in the HTML:

```
\setlength{\belowcaptionskip}{0ex}
\setlength{\abovecaptionskip}{0ex}
```

Redefine the plain page style to be empty when used by index pages:

```
\renewcommand{\ps@plain}{}
```

Plug in some new actions. This is done just before the document start so that they won't be over-written by some other package.

Float captions:

```
\let\LWR@origcaption\caption
```

Labels: `\ltx@label` is used in amsmath environments and is also patched by cleveref.

Label in HTML

```
\let\LWR@origltx@label\ltx@label
\let\ltx@label\LWR@htmlmathlabel
```

Logos:

```
\LetLtxMacro\TeX\LWR@TeX
\LetLtxMacro\LaTeX\LWR@LaTeX
\LetLtxMacro\LuaTeX\LWR@LuaTeX
\LetLtxMacro\LuaLaTeX\LWR@LuaLaTeX
\LetLtxMacro\XeTeX\LWR@XeTeX
\LetLtxMacro\XeLaTeX\LWR@XeLaTeX
\LetLtxMacro\ConTeXt\LWR@ConTeXt
```

Not yet started any paragraph handling:

```
\global\boolfalse{LWR@doingapar}
\global\boolfalse{LWR@doingstartpars}
```

Document and page settings:

```
\mainmatter
\LWR@origpagenumbering{arabic}
```

Start a new HTML file and a header:

```
\LWR@traceinfo{LWR@lwarpStart: Starting new file.}
\LWR@filestart
```

```
\LWR@traceinfo{LWR@lwarpStart: Generating first header.}
\LWR@htmltag{header}\LWR@orignewline
\LWR@startpars
\LWR@firstpagetop
\LWR@stoppars
\LWR@htmltag{/header}\LWR@orignewline

\LWR@htmlelementclass{div}{bodywithoutsidetoc}
\LWR@htmlelementclass{div}{bodycontainer}
\LWR@traceinfo{LWR@lwarpStart: Generating textbody.}
\LWR@htmlelementclass{section}{textbody}
```

Patch the `itemize`, `enumerate`, and `description` environments and `\item`. This works with the native LaTeX environments, as well as those provided by enumitem, enumerate, and paralist.

```
\LWR@patchlists
```

Ensure that math mode is active to call lwarp's patches:

```
\catcode`\$=\active
```

Required for `\nameref` to work with SVG math:

```
\immediate\write\@mainaux{\catcode`\string$\active}%
\LetLtxMacro\LWR@syntaxhighlightone$% balance for editor syntax highlighting
```

Allow HTML paragraphs to begin:

```
\LWR@startpars
```

If using MathJax, disable `\ensuremath` by printing a nullified definition at the start of each file, and add further customizations:

```
\LWR@customizeMathJax
```

First autopage label in case a figure occurs early.

```
\setcounter{LWR@latestautopage}{\value{page}}%
\LWR@newautopagelabel{LWR@currentautosec}%

\LWR@traceinfo{LWR@lwarpStart: done}
}
\catcode`\$=3% math shift until lwarp starts

\end{warpHTML}
```

64 Ending HTML output

for HTML output:

```
\begin{warpHTML}
```

\LWR@requesttoc {⟨*boolean*⟩} {⟨*suffix*⟩} Requests that a TOC, LOF, or LOTbe generated.

```
\newcommand*{\LWR@requesttoc}[2]{%
\ifbool{#1}
{
    \expandafter\newwrite\@nameuse{tf@#2}
    \immediate\openout \@nameuse{tf@#2} \jobname.#2\relax
}{}
}
```

\LWR@LwarpEnd Final stop of all HTML output:

```
\newcommand*{\LWR@LwarpEnd}
{
\LWR@stoppars
\LWR@closeprevious{\LWR@depthfinished}
```

At the bottom of the ending file:

Close the textbody:

```
\LWR@htmlelementclassend{section}{textbody}
\LWR@htmlelementclassend{div}{bodycontainer}
\LWR@htmlelementclassend{div}{bodyandsidetoc}
```

Print any pending footnotes:

```
\LWR@printpendingfootnotes
```

Create the footer:

```
\LWR@htmlelement{footer}

\LWR@pagebottom

\LWR@htmlelementend{footer}
```

No bottom navigation if are finishing the home page, or if formatting for an EPUB or word processor.

Presumably has a table-of-contents.

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {
        \ifnumcomp{\value{LWR@htmlfilenumber}}{>}{0}{\LWR@botnavigation}{}
    }
```

```
\LWR@stoppars% final stop of all paragraphs
```

Finish the HTML file:

```
\LWR@htmltag{/body}\LWR@orignewline
\LWR@htmltag{/html}\LWR@orignewline
```

Seems to be required sometimes:

```
\LWR@orignewpage
```

For `lateximage` commands:

```
\immediate\write\LWR@lateximagesfile{%
    |end|end|end|%
}%
\immediate\closeout\LWR@lateximagesfile
}
```

```
\end{warpHTML}
```

65 Title page

package support
⚠ load order

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

`\published` and `\subtitle`

If using the titling package, additional titlepage fields for `\published` and `\subtitle` may be added by using `\AddSubtitlePublished` in the preamble. See section 65.8.

affiliation

lwarp provides for the `\author` macro an additional `\affiliation` macro to provide an affiliation and other additional information for each author in the title page. The affiliation information is removed when using titlingpage's `\theauthor` in the main text.

reusing titlepage information

The titling package maintains the definitions of `\thetitle`, `\theauthor`, etc., after the title has been typeset. These commands are to be used to refer to the document's title and author, etc., in the main text. These definitions have the `\thanks` and `\affiliation` removed, and for `\author` the `\and` is replaced to generate a simple inline list of authors separated by commas. Note: `\theauthor` does not work well with authblk unless the traditional LaTeX syntax is used.

⚠ `\theauthor`, authblk

custom titlepages

`\printtitle`, `\printauthor`, etc., are provided for use inside a custom `titlepage` or `titlingpage` environment, and these retain the `\thanks` and `\affiliation`.

`\printthanks`

`\printthanks` has been added to force the printing of thanks inside a `titlingpage` environment when `\maketitle` is not used.

⚠ `\thanks`

Inside a `\titlepage` or `\titlingpage` environment, use `\thanks` instead of `\footnote` for acknowledgements, etc.

65.1 Setting the title, etc.

The following provide setting commands for both HTML and print outputs.

\author \and {⟨*author*⟩} While using \maketitle and print mode, the author is treated as a single-column tabular and the \and feature finishes the current tabular then starts a new one for the next author. Each author thus is placed into its own tabular, and an affiliation may be placed on its own line such as

```
\author{Name \\ Affiliation \and Second Name \\ Second Affiliation}
```

For HTML, the entire author block is placed inside a of class author, and each individual author is inside a of class oneauthor.

\@title \@author \@date \@title, \@author, etc. store the values as originally assigned, including any \thanks, \and, or \affiliation. These are low-level macros intended to be used by other macros only inside a titlepage or titlingpage, and are used by \maketitle. The author is printed inside a single-column tabular, which becomes multiple single-column tabulars if multiples authors are included. For HTML, these tabulars become side-by-side s of class oneauthor, all of which are combined into one of class author.

\printtitle \printauthor \printdate \printtitle, etc. are user-level macros intended to be used in custom titlepage or titlingpage environments in cases where \maketitle is not desired. These commands preserve the \thanks, etc., and should not be used in the main text.

\thetitle \theauthor \thedate \thetitle, \theauthor, and \thedate are available if titling has been loaded, and are sanitized user-level versions from which have been removed the \thanks and \affiliation, and \and is changed for inline text usage. The author is printed inline without \affiliation or \thanks, with \and placing commas between multiple authors. Thus, these commands are to be used in the main text whenever the user wishes to refer to the document's title and such. One practical use for this is to place the authors at the bottom of each HTML page, such as:

\HTMLPageBottom {⟨*text*⟩}

```
\HTMLPageBottom{
\begin{center}\textcopyright~2016 \theauthor\end{center}
}
```

⚠ \theauthor, authblk \theauthor does not work well if authblk is used. If \theauthor is important, it is recommended to use the standard LaTeX syntax for \author, optionally with lwarp's \affiliation macro as well.

⚠ affiliations After \maketitle has completed, \theauthor retains the definition of the author, but \and is changed to become a comma and a space, intending to print the authors names separated by spaces. This fails when affiliations are included on their own table rows.

\affiliation A solution, provide here, is to define a macro \affiliation which, during \maketitle, starts a new row and adds the affiliation, but after \maketitle is finished \affiliation is re-defined to discard its argument, thus printing only the author names when \author is later used inline.

65.2 \if@titlepage

for HTML & PRINT:

```
\begin{warpall}
```

\if@titlepage Some classes do not provide \if@titlepage. In this case, provide it and force it false.

```
\ifcsvoid{@titlepagefalse}{
    \newif\if@titlepage
    \@titlepagefalse
}{}

\end{warpall}
```

65.3 Changes for \affiliation

\affiliation {⟨*text*⟩}

Adds the affiliation to the author for use in \maketitle.

Inside titlepage, this macro prints its argument. Outside, it is null.

for HTML & PRINT:

```
\begin{warpall}
\providerobustcmd{\affiliation}[1]{}
\end{warpall}
```

for PRINT output:

```
\begin{warpprint}

\AtBeginEnvironment{titlepage}{
\renewrobustcmd{\affiliation}[1]{\\ \textsc{\small#1}}
}

\AtBeginDocument{
\@ifpackageloaded{titling}{
\AtBeginEnvironment{titlingpage}{
\renewrobustcmd{\affiliation}[1]{\\ \textsc{\small#1}}
}
}{}% titling loaded
}% AtBeginDocument

\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

Env titlepage Sets up a of class titlepage. Provided even for memoir class, since it is used by \maketitle.

```
\DeclareDocumentEnvironment{titlepage}{}
{
\renewrobustcmd{\affiliation}[1]{\\ \InlineClass{affiliation}{##1}}
```

```
\LWR@printpendingfootnotes
\LWR@forcenewpage
\BlockClass{titlepage}
}
{
\endBlockClass
\LWR@printpendingfootnotes
}

\end{warpHTML}
```

65.4 Printing the thanks

for HTML & PRINT:

```
\begin{warpall}
```

`\printthanks` Forces the `\thanks` to be printed.

This is necessary in a `titlingpage` environment when `\maketitle` was not used.

```
\newcommand*{\printthanks}{\@thanks}

\end{warpall}
```

65.5 Printing the title, etc. in HTML

The following are for printing the title, etc. in a `titlepage` or a `titlingpage` in HTML:

for HTML output:

```
\begin{warpHTML}
```

`\printtitle`

```
\newcommand*{\printtitle}
{%
    \LWR@stoppars%
    \LWR@htmltag{\LWR@tagtitle}%
    \@title%
    \LWR@htmltag{\LWR@tagtitleend}%
    \LWR@startpars%
}
```

`\LWR@printthetitle` A private version which prints the title without footnotes, used to title each HTML page.

```
\newcommand*{\LWR@printthetitle}
{%
    \LWR@stoppars%
    \LWR@htmltag{\LWR@tagtitle}%
    \thetitle%
    \LWR@htmltag{\LWR@tagtitleend}%
    \LWR@startpars%
}
```

\printauthor HTML version.

```
\newcommand*{\printauthor}{
```

The entire author block is contained in a named author:

```
\begin{BlockClass}{author}
```

\and finishes one author and starts the next:

```
\renewcommand{\and}{%
\end{BlockClass}
\begin{BlockClass}{oneauthor}
}
```

Individual authors are contained in a named oneauthor:

```
\begin{BlockClass}{oneauthor}
\@author
\end{BlockClass}
\end{BlockClass}
}
```

\printdate

```
\newcommand*{\printdate}{%
\begin{BlockClass}{titledate}
\@date
\end{BlockClass}
}
```

```
\end{warpHTML}
```

65.6 Printing the title, etc. in print form

The following are for printing the title, etc. in a titlepage or a titlingpage in print form:

for PRINT output:

```
\begin{warpprint}
```

\printtitle

```
\newcommand*{\printtitle}{{\Huge\@title}}
```

\printauthor Print mode.

```
\newcommand*{\printauthor}
    {{\large\begin{tabular}[t]{c}\@author\end{tabular}}}
```

\printdate

```
\newcommand*{\printdate}{{\small\textit{\@date}}}
\end{warpprint}
```

65.7 \maketitle for HTML output

An HTML of class titlepage is used.

\thanks are a form of footnotes used in the title page. See section 58 for other kinds of footnotes.

See \thanksmarkseries{series}, below, to set the style of the footnote marks.

for HTML output:

```
\begin{warpHTML}
\@ifclassloaded{memoir}
{
\newcommand{\LWR@setfootnoteseries}{%
    \renewcommand\thefootnote{\@arabic\c@footnote}%
}
}{% not memoir
\if@titlepage
\newcommand{\LWR@setfootnoteseries}{%
    \renewcommand\thefootnote{\@arabic\c@footnote}%
}
\else
\newcommand{\LWR@setfootnoteseries}{%
    \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
}
\fi
}% not memoir
```

\LWR@maketitlesetup

Patches \thanks macros.

```
\newcommand*{\LWR@maketitlesetup}{%
```

Redefine the footnote mark:

```
\LWR@setfootnoteseries%
\def\@makefnmark{\textsuperscript{\thefootnote}}
```

\thefootnote ⇒ \nameuse{arabic}{footnote}, or
\thefootnote ⇒ \nameuse{fnsymbol}{footnote}

Redefine the footnote text:

```
\long\def\@makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```
\textsuperscript{\@thefnmark}~%
```

\makethanksmark ⇒ \thanksfootmark ⇒ \tamark ⇒ \@thefnmark ⇒ \itshape a (or similar)

Print the text:

```
##1%
}%
}
```

`\@fnsymbol` {⟨*counter*⟩}

Re-defined to use an HTML entity for the double vertical bar symbol. The original definition used `\|` which was not being seen by *pdftotext*.

```
\def\@fnsymbol#1{\ifcase#1\or *\or \HTMLentity{dagger}\or \HTMLentity{Dagger}\or
   \HTMLentity{sect}\or \HTMLentity{para}\or \text{\HTMLunicode{2016}}\or
   **\or \HTMLentity{dagger}\HTMLentity{dagger} \or
   \HTMLentity{Dagger}\HTMLentity{Dagger} \else\@ctrerr\fi}
```

`\maketitle` HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the titling package is adapted, simplified, and modified for HTML output.

```
\renewcommand*{\maketitle}{%
```

An HTML titlepage is used for all classes.

```
\begin{titlepage}
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any `\thanks` footnotes:

```
\@thanks
```

Close the HTML titlepage div and cleanup:

```
\end{titlepage}
\setcounter{footnote}{0}%
\global\let\thanks\relax
\global\let\maketitle\relax
```

```
\global\let\@maketitle\relax
\global\let\@thanks\@empty
\global\let\@author\@empty
\global\let\@date\@empty
\global\let\@title\@empty
\global\let\title\relax
\global\let\author\relax
\global\let\date\relax
\global\let\and\relax
}
```

\@maketitle HTML mode. Typesets the title, etc.:

```
\DeclareDocumentCommand{\@maketitle}{}{%
    \LWR@stoppars\LWR@htmltag{\LWR@tagtitle}%
    \@title%
    \LWR@htmltag{\LWR@tagtitleend}\LWR@startpars%
    \begin{BlockClass}{author}%
```

For IEEEtran class:

```
    \renewcommand*{\cr}{}%
    \renewcommand*{\crcr}{}%
    \renewcommand*{\noalign}{}%

        \renewcommand{\and}{%
            \end{BlockClass}%
            \begin{BlockClass}{oneauthor}%
        }%
        \begin{BlockClass}{oneauthor}%
            \@author%
        \end{BlockClass}%
    \end{BlockClass}%
    \begin{BlockClass}{titledate}%
    \@date%
    \end{BlockClass}%
}
```

\LWR@titlingmaketitle \maketitle for use inside an HTML titlingpage environment.

```
\newcommand*{\LWR@titlingmaketitle}{%
```

Keep pending footnotes out of the title block:

```
\@thanks
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any \thanks footnotes:

```
\@thanks
}
```

```
\end{warpHTML}
```

65.8 \published and \subtitle

\subtitle and \published

To add \subtitle and \published to the titlepage, load the titling package and use \AddSubtitlePublished in the preamble.

The default lwarp.css has definitions for the published and subtitle classes.

If titling is loaded, \AddSubtitlePublished creates a number of additional macros, and also assigns some of the titling hooks. If titling is not loaded, \AddSubtitlePublished creates null macros.

⚠ titling hooks

Do not use \AddSubtitlePublished if the user has patched the titling hooks for some other reason. Portions are marked \warpprintonly to reduce extra tags in HTML. Similarly, BlockClass has no effect in print mode. Thus, the following may be marked warpall.

for HTML & PRINT:

```
\begin{warpall}
```

\AddSubtitlePublished

Adds \published and \subtitle, and related.

```
\newcommand*{\AddSubtitlePublished}{%
\@ifpackageloaded{titling}{% yes titling package
    \newcommand{\@published}{}%
    \newcommand{\published}[1]{\gdef\@published{##1}}%
    \renewcommand*{\maketitlehooka}{\printpublished}%
    \newcommand*{\printpublished}{%
        \warpprintonly{\begin{center}\unskip}%
        \begin{BlockClass}{published}%
        \warpprintonly{\large\itshape}%
        \@published%
        \end{BlockClass}%
        \warpprintonly{\end{center}}%
    }%
    \newcommand{\@subtitle}{}%
    \newcommand{\subtitle}[1]{\gdef\@subtitle{##1}}%
    \renewcommand*{\maketitlehookb}{\printsubtitle}%
    \newcommand*{\printsubtitle}{%
        \warpprintonly{\begin{center}\unskip}%
        \begin{BlockClass}{subtitle}%
        \warpprintonly{\Large\itshape}%
        \@subtitle%
        \end{BlockClass}%
        \warpprintonly{\end{center}}%
    }%
}% yes titling package
```

```
{% no titling package
    \newcommand{\published}[1]{}%
    \newcommand*{\printpublished}{}%
    \newcommand{\subtitle}{}%
    \newcommand*{\printsubtitle}%
}% no titling package
}% \AddSubtitlePublished

\end{warpall}
```

66 Abstract

The following code replaces the LaTeX default, and will itself be replaced later if the abstract package is loaded.

for HTML output:

```
\begin{warpHTML}
```

`\abstractname` User-redefinable title for the abstract.

Also over-written by the babel package.

```
\providecommand*{\abstractname}{Abstract}
```

Some classes allow an optional name, so it is allowed here.

Env `abstract`

```
\DeclareDocumentEnvironment{abstract}{O{\abstractname}}
{
\LWR@forcenewpage
\BlockClass{abstract}
\BlockClassSingle{abstracttitle}{#1}
}
{
\endBlockClass
}

\end{warpHTML}
```

67 Quote and verse

67.1 Attributions

`\attribution` For use with quote, quotation, verse:

Ex: `"A quotation." \attribution{\textsc{Author Name}\\\textsl{Book Title}}`

for HTML output:

```
\begin{warpHTML}
\newcommand{\attribution}[1]{%
    \begin{BlockClass}{attribution}
    #1
    \end{BlockClass}
}
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand{\attribution}[1]{
    \begin{flushright}
    \unskip
    #1
    \end{flushright}%
}
\end{warpprint}
```

67.2 Quotes, quotations

for HTML output:

```
\begin{warpHTML}
```

Env `quote`

```
\renewenvironment*{quote}
{
\LWR@forcenewpage
\LWR@htmlblocktag{blockquote}
}
{\LWR@htmlblocktag{/blockquote}}

\renewenvironment*{quotation}
{
\LWR@forcenewpage
\LWR@htmlblocktag{blockquotation}
}
{\LWR@htmlblocktag{/blockquotation}}

\end{warpHTML}
```

67.3 Verse

When using verse or memoir, always place a `\\` after each line.

`\attrib` The documentation for the verse and memoir packages suggest defining an `\attrib` command, which may already exist in current documents, but it will only work for print output. lwarp provides `\attribution`, which works for both print and HTML output. To combine the two so that `\attrib` is used for print and `\attribution` is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len \vleftskip
Len \vleftmargini
Len \HTMLvleftskip
Len \HTMLleftmargini

These lengths are used by verse and memoir to control the left margin, and they may already be set by the user for print output. New lengths \HTMLvleftskip and \HTMLleftmargini are provided to control the margins in HTML output. These new lengths may be set by the user before any verse environment, and persist until they are manually changed again. One reason to change \HTMLleftmargini is if there is a wide \flagverse in use, such as the word "Chorus", in which case the value of \HTMLleftmargini should be set to a wide enough length to contain "Chorus". The default is wide enough for a stanza number.

⚠ spacing

Horizontal spacing relies on *pdftotext*'s ability to discern the layout (-layout option) of the text in the HTML-tagged PDF output. For some settings of \HTMLleftmargini or \HTMLleftskip the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

67.3.1 LaTeX core verse environment

for HTML output:

```
\begin{warpHTML}
```

Env verse

```
\renewenvironment{verse}
               {\let\\\newline% lwarp
                \list{}{\itemsep      \z@
                        \itemindent   -1.5em%
                        \listparindent\itemindent
                        \rightmargin  \leftmargin
                        \advance\leftmargin 1.5em}%
                \item\relax}
               {\endlist}
```

```
\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

67.3.2 verse and memoir

The following lengths are used by verse and memoir. They may be set in either print or HTML output, but are only used in HTML. This allows the user to set \vleftskip and \leftmargini for print output, and optionally select different values for HTML.

Len \HTMLvleftskip

Sets \vleftskip inside a verse environment in HTML.

```
\newlength{\HTMLvleftskip}
\setlength{\HTMLvleftskip}{1em}
```

Len \HTMLleftmargini

Sets \leftmargini inside a verse environment in HTML.

```
\newlength{\HTMLleftmargini}
\setlength{\HTMLleftmargini}{4.5em}

\end{warpall}
```

68 Verbatim and tabbing

for HTML & PRINT:

```
\begin{warpall}
```

Len `\VerbatimHTMLWidth` Width to use in HTML `Verbatim` environment.

This width is used when placing line numbers to the right. Ignored during print output.

```
\newlength{\VerbatimHTMLWidth}
\setlength{\VerbatimHTMLWidth}{4in}
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Bool `LWR@verbtags` Used to temporarily turn off verbatim tags while doing `\verbatiminput` in the HTML head.

```
\newbool{LWR@verbtags}
\booltrue{LWR@verbtags}
```

`\LWR@atbeginverbatim` `[`⟨*1: style*⟩`]` {⟨*2: negative* `\baselineskip` `\vspace`⟩} {⟨*3: class*⟩}

Encloses a verbatim environment with the given CSS class.

The use of `\textquotedbl` instead of " improves compatibility with XeCJK.

```
\newcommand*{\LWR@atbeginverbatim}[3][]
{%
```

Avoid excessive space between lines:

```
\setlength{\parskip}{0ex}%
```

Stop generating HTML paragraph tags:

```
\LWR@stoppars%
```

Create a new `pre` of the given class. The tags may temporarily be turned off for internal use, such as loading the MathJax script.

```
\ifbool{LWR@verbtags}{%
    \LWR@htmltag{pre class=\textquotedbl#3\textquotedbl%
        \ifthenelse{\equal{#1}{}}{}{ style=\textquotedbl#1\textquotedbl}%
    }%
    \LWR@orignewline% pre
```

```
6708     \leavevmode\unskip\LWR@print@vspace*{-#2\baselineskip}%
6709 }{}%
```

Use a mono-spaced font to preserve horizontal positioning. If horizontal alignment is important for the user, use a mono-spaced font in the CSS for the `verse` class.

```
6710 \begingroup%
```

```
6711 % \LWR@print@normalsize%
6712 \LWR@origttfamily%
6713 \LWR@print@small%
```

Since inside a <pre>, restore the original list processing:

```
6714 \LWR@restoreoriglists%
```

Turn off babel-french extra space before punctuation:

```
6715 \LWR@FBcancel%
```

Do not produce HTML tags for `\hspace` inside a verse `par`. Restore plain LaTeX `\hspace` functionality:

```
6716 \LWR@select@print@hspace%
6717 }
```

`\LWR@afterendverbatim` {⟨*negative* `\baselineskip` `\vspace`⟩}

Finishes enclosing a verbatim environment.

```
6718 \newcommand*{\LWR@afterendverbatim}[1]{%
6719 \endgroup%
6720 \par%
```

At the end of the environment, close the `pre`:

```
6721 \ifbool{LWR@verbtags}{%
6722     \LWR@print@vspace*{-#1\baselineskip}%
6723     \noindent\LWR@htmltag{/pre}\LWR@orignewline% pre
6724 }{}%
```

Resume regular paragraph handling:

```
6725 \LWR@startpars%
6726 }
```

`\verbatiminput` {⟨*filename*⟩}

Patch `\verbatiminput` to add HTML tags:

```
6727 \let\LWRV@origverbatim@input\verbatim@input
```

```
\renewcommand{\verbatim@input}[2]{%
\ifbool{LWR@verbtags}{\LWR@forcenewpage}{}%
\LWR@atbeginverbatim{2.5}{Verbatim}%
\LWRV@origverbatim@input{#1}{#2}%
\LWR@afterendverbatim{1.5}%
}
```

Env verbatim

```
\AfterEndPreamble{
\LWR@traceinfo{Patching verbatim.}
\AtBeginEnvironment{verbatim}{%
\LWR@forcenewpage%
\LWR@atbeginverbatim{2.5}{verbatim}%
}
\AfterEndEnvironment{verbatim}{%
    \LWR@afterendverbatim{1}%
}
}
```

Env tabbing The tabbing environment works, except that SVG math and lateximages do not yet work inside the environment.

⚠ math in tabbing If math is used inside tabbing, place tabbing inside a lateximage environment, which will render the entire environment as a single SVG image.

```
\newcommand*{\LWR@HTML@tabbing}{%
\LWR@forcenewpage%
\LWR@atbeginverbatim{3}{tabbing}%
\LWR@print@tabbing%
}

\newcommand*{\LWR@HTML@endtabbing}{%
    \LWR@print@endtabbing%
    \LWR@afterendverbatim{1}%
}

\LWR@formatted{tabbing}
\LWR@formatted{endtabbing}

\end{warpHTML}
```

69 Theorems

\newtheorem {⟨*text*⟩} [⟨*counter*⟩] -or- [⟨*oldname*⟩] {⟨*text*⟩}

A few minor changes are made to supply HTML tags.

- The entire theorem is placed into a of class theoremcontents.

- The label for each theorem is placed inside a of class theoremlabel.
- The contents are placed inside a of class theoremcontents.

for HTML output:

```
\begin{warpHTML}
```

\@begintheorem {⟨*name*⟩} {⟨*number*⟩}

```
\renewcommand{\@begintheorem}[2]{%
\LWR@forcenewpage
\BlockClass{theoremcontents}
\trivlist
\item[\InlineClass{theoremlabel}{#1\ #2\ }]\itshape
}
```

\@opargbegintheorem {⟨*name*⟩} {⟨*number*⟩} {⟨*oparg*⟩}

```
\renewcommand{\@opargbegintheorem}[3]{%
\LWR@forcenewpage
\BlockClass{theoremcontents}
\trivlist
\item[\InlineClass{theoremlabel}{#1\ #2\ (#3)\ }]\itshape
}
```

\@endtheorem

```
\renewcommand*{\@endtheorem}{%
\endtrivlist
\endBlockClass% theoremcontents
}

\end{warpHTML}
```

70 Lists

The environments itemize, enumerate, and description are patched when lwarp is started. These patches support the standard LaTeX environments, as well as those of enumerate, enumitem, and paralist, and at least the French version of babel. Additional patches are done on a package-specific basis.

The LaTeX source for itemize and enumerate are found in source2e, but the source for description is found in article.cls, etc.

empty item

To have an empty item,use \mbox{} or a trailing backslash. This forces a new line in print output, matching the new line which will appear in HTML output. Ex:

```
begin{itemize}
item \mbox{}
```

```
    \begin{itemize}
...
    \end{itemize}
item \
    \begin{itemize}
  ...
    \end{itemize}
```

\makelabel While inside a list environment, lwarp nullifies a number of TEX horizontal skip and fill commands, allowing the user to define \makelabel for print mode while HTML mode ignores those commands.

⚠ label font When defining \makelabel in a list environment, use \textbf etc. instead of \bfseries.

70.1 List environment

for HTML output:
```
\begin{warpHTML}
```

\LWR@printcloselist May be locally redefined by enumerate or description.

```
\newcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
```

\LWR@printopenlist May be locally redefined by enumerate or description.

```
\newcommand*{\LWR@printopenlist}{ul style="\LWR@print@mbox{list-style-type:none}"}
```

\@mklab Removes PDF spacing.

```
\AtBeginDocument{
\def\@mklab#1{%
%     \hfil %
    #1}
\let\makelabel\@mklab
}
```

\@donoparitem Modified for HTML output by replacing TEX boxes with plain text. Also removes PDF spacing.

```
\def\@donoparitem{%
  \@noparitemfalse
%   \global\setbox\@labels\hbox{\hskip -\leftmargin
%                               \unhbox\@labels
%                                \hskip \leftmargin}%
%   \if@minipage\else
%     \@tempskipa\lastskip
%     \vskip -\lastskip
%     \advance\@tempskipa\@outerparskip
%     \advance\@tempskipa -\parskip
```

```
%     \vskip\@tempskipa
%   \fi
}
```

\@item Modified for HTML output by replacing TEX boxes with plain text. Also removes PDF spacing.

```
\def\LWR@HTML@item[#1]{%
\LWR@traceinfo{@item}
  \if@noparitem
    \@donoparitem
  \else
%     \if@inlabel
%       \indent
        \par
%     \fi
    \ifhmode
%       \unskip\unskip
        \par
    \fi
    \if@newlist
      \if@nobreak
        \@nbitem
      \else
%         \addpenalty\@beginparpenalty
%         \addvspace\@topsep
%         \addvspace{-\parskip}%
      \fi
    \else
%       \addpenalty\@itempenalty
%       \addvspace\itemsep
    \fi
    \global\@inlabeltrue
  \fi
%   \everypar{%
    \@minipagefalse
    \global\@newlistfalse

%     \if@inlabel
%       \global\@inlabelfalse

%       {\setbox\z@\lastbox
%        \ifvoid\z@
%          \kern-\itemindent
%        \fi}%

%       \box\@labels
%       \penalty\z@
%     \fi

%     \if@nobreak
%       \@nobreakfalse
%       \clubpenalty \@M
%     \else
```

```
%       \clubpenalty \@clubpenalty
%       \everypar{}%
%     \fi}%

  \if@noitemarg
    \@noitemargfalse
    \if@nmbrlist

      \refstepcounter\@listctr
    \fi
  \fi


    \makelabel{#1} % extra space
%   \sbox\@tempboxa{\makelabel{#1}%
%   \global\setbox\@labels\hbox{%
%     \unhbox\@labels
%     \hskip \itemindent
%     \hskip -\labelwidth
%     \hskip -\labelsep
%     \ifdim \wd\@tempboxa >\labelwidth
%       \box\@tempboxa

%     \else
%       \hbox to\labelwidth {\unhbox\@tempboxa}%
%     \fi
%     \hskip \labelsep}%
  \ignorespaces%
}
```

\@nbitem

```
\def\@nbitem{%
%   \@tempskipa\@outerparskip
%   \advance\@tempskipa -\parskip
%   \addvspace\@tempskipa
}
```

\LWR@listitem [⟨*label*⟩]

Handles \item inside a list, itemize, or enumerate.

See \LWR@openparagraph where extra \hspace is used to leave room for the label while inside a list during paragraph construction.

```
\newcommand*{\LWR@listitem}{%
\LWR@stoppars%
\LWR@startnewdepth{\LWR@depthlistitem}{\LWR@printcloselistitem}%
\LWR@htmltag{li}%
\LWR@startpars%
\LWR@origitem%
}
```

\LWR@nulllistfills Nullifies various TEX fill commands, in case they are used inside \makelabel. Problems are caused when these are nullified all the time.

```
\newcommand*{\LWR@nulllistfills}{%
\renewcommand*{\hss}{}%
\renewcommand*{\llap}[1]{##1}%
\renewcommand*{\rlap}[1]{##1}%
\renewcommand*{\hfil}{}%
\renewcommand*{\hfilneg}{}%
\renewcommand*{\hfill}{}%
}
```

Env list {⟨*label*⟩} {⟨*commands*⟩}

```
\newcommand*{\LWR@liststart}{%
\LWR@traceinfo{LWR@liststart}%
\LWR@stoppars%
\LWR@pushoneclose{\LWR@depthlist}{\LWR@printcloselist}%
\LWR@htmltag{\LWR@printopenlist}\LWR@orignewline%
\LWR@startpars%
\setlength{\topsep}{0pt}%
\setlength{\partopsep}{0pt}%
\setlength{\itemsep}{0pt}%
\setlength{\parsep}{0pt}%
\setlength{\leftmargin}{0pt}%
\setlength{\rightmargin}{0pt}%
\setlength{\listparindent}{0pt}%
\setlength{\itemindent}{0pt}%
\setlength{\labelsep}{1em}%
\LWR@nulllistfills%
}
```

```
\newcommand*{\LWR@listend}{%
\LWR@traceinfo{LWR@listend}%
\LWR@stoppars%
\LWR@closeprevious{\LWR@depthlist}%
\LWR@startpars%
}
```

70.2 Itemize

\LWR@itemizeitem [⟨*label*⟩]

Handles \item inside an itemize or enumerate.

See \LWR@openparagraph where extra \hspace is used to leave room for the label while inside a list during paragraph construction.

```
\newcommand*{\LWR@itemizeitem}{%
\LWR@stoppars%
\LWR@startnewdepth{\LWR@depthlistitem}{\LWR@printcloselistitem}%
```

```
\LWR@htmltag{li}%
\LWR@startpars%
\LWR@origitem%
}
```

Env `itemize` [⟨*options*⟩]

```
\newcommand*{\LWR@itemizestart}{%
\renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
\renewcommand*{\LWR@printopenlist}{ul style="\LWR@print@mbox{list-style-type:none}"}
\let\item\LWR@itemizeitem%
\LWR@nulllistfills%
}
```

70.3 Enumerate

An HTML unordered list is used with customized LaTeX-generated labels.

Env `enumerate` [⟨*options*⟩]

```
\newcommand*{\LWR@enumeratestart}{%
\renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
\renewcommand*{\LWR@printopenlist}{ul style="\LWR@print@mbox{list-style-type:none}"}
\let\item\LWR@itemizeitem%
\LWR@nulllistfills%
}
```

70.4 Description

`\LWR@descitem` [⟨*label*⟩] Handles an `\item` inside a description.

```
\newcommand*{\LWR@descitem}[1][]%
{%
\LWR@stoppars%
\LWR@setlatestname{#1}%
\LWR@startnewdepth{\LWR@depthlistitem}{\LWR@printclosedescitem}%
```

Temporarily disable `\hspace`, which `article.cls`, etc. use per `\item` for `descriptions` only. This causes lwarp to mistakenly place an empty span between HTML list tags.

```
\LWR@select@html@nohspace%
```

Process the original `\item` code:

```
\LWR@origitem[]%
```

Restore `\hspace` for use in the item text:

```
\LWR@select@html@hspace%
```

```
\LWR@htmltag{dt}#1\LWR@htmltag{/dt}%
\LWR@orignewline%
\LWR@htmltag{dd}%
\LWR@startpars%
}
```

Env description [⟨*options*⟩]

```
\newcommand*{\LWR@descriptionstart}{%
\renewcommand*{\LWR@printcloselist}{\LWR@printclosedescription}
\renewcommand*{\LWR@printopenlist}{dl}
\let\item\LWR@descitem%
\LWR@nulllistfills%
}
```

70.5 Patching the lists

\LWR@patchlists Patches list environments.

\LWR@patchlists remembers \item as defined by whatever packages have been loaded, then patches the itemize, enumerate, and description environments and \item. This works with the native LaTeX environments, as well as those provided by enumitem, enumerate, and paralist.

```
\newcommand*{\LWR@patchlists}{%
    \LetLtxMacro\item\LWR@listitem%
    \LetLtxMacro\@item\LWR@HTML@item%
    \renewcommand*{\@trivlist}{%
        \LWR@traceinfo{@trivlist start}%
        \LWR@liststart%
        \LWR@orig@trivlist%
        \LWR@traceinfo{@trivlist done}%
    }%
    \renewcommand*{\trivlist}{%
        \LWR@traceinfo{trivlist}%
        \LWR@origtrivlist%
    }%
    \renewcommand*{\endtrivlist}{%
        \LWR@traceinfo{endtrivlist start}%
        \LWR@origendtrivlist\LWR@listend%
        \LWR@traceinfo{endtrivlist done}%
    }%
    \renewcommand*{\itemize}{%
        \LWR@itemizestart\LWR@origitemize%
    }%
    \renewcommand*{\enumerate}{%
        \LWR@enumeratestart\LWR@origenumerate%
    }%
    \renewcommand*{\description}{%
        \LWR@descriptionstart\LWR@origdescription%
    }%
}
```

\LWR@restoreoriglists Restores the original `trivlist` environment.

```
\newcommand*{\LWR@restoreoriglists}{%
\LWR@traceinfo{LWR@restoreoriglists}%
\LetLtxMacro\item\LWR@origitem%
\LetLtxMacro\@item\LWR@orig@item%
\let\@trivlist\LWR@orig@trivlist%
\let\trivlist\LWR@origtrivlist%
\let\endtrivlist\LWR@origendtrivlist%
\LetLtxMacro\itemize\LWR@origitemize%
\LetLtxMacro\enditemize\LWR@endorigitemize%
\LetLtxMacro\enumerate\LWR@origenumerate%
\LetLtxMacro\endenumerate\LWR@endorigenumerate%
\LetLtxMacro\description\LWR@origdescription%
\LetLtxMacro\enddescription\LWR@endorigdescription%
\let\@mklab\LWR@orig@mklab%
\let\makelabel\LWR@origmakelabel%
\let\@donoparitem\LWR@orig@donoparitem%
\let\@nbitem\LWR@orig@nbitem%
}

\end{warpHTML}
```

71 Tabular

This is arguably the most complicated part of the entire package. Numerous tricks are employed to handle the syntax of the LaTeX core and the various tabular-related packages.

71.1 Limitations

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, * column specifiers, siunitx S columns, or the packages multirow, longtable, supertabular, or xtab.

Defining macros and environments:

⚠ Misplaced alignment tab character &

- When defining environments or macros which include `tabular` and instances of the & character, it may be necessary to make & active before the environment or macro is defined, then restore & to its default catcode after, using the following commands. These are are ignored in print mode.

```
\StartDefiningTabulars
<define macros or environments using tabular and & here>
\StopDefiningTabulars
```

⚠ floatrow

This includes before and after defining any macro which used `\ttabbox` from floatrow.

⚠ `tabular` inside another environment

- When creating a new environment which contains a `tabular` environment, lwarp's emulation of the tabular does not automatically resume when the

containing enviroment ends, resulting in corrupted HTML rows. To fix this, use \ResumeTabular as follows. This is ignored in print mode.

```
\StartDefiningTabulars  % because  &  is  used  in  a
definition
\newenvironment{outerenvironment}
{
\tabular{cc}
left & right \\
}
{
\TabularMacro\ResumeTabular
left & right \\
\endtabular
}
\StopDefiningTabulars
```

Cell contents:

⚠ \multirow

- For multirow, insert \mrowcell into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output.

```
... &  \multirow{2}{.5in}{text}  & ...
... &  \mrowcell                 & ...
```

vposn

Note that recent versions of multirow include a new optional vposn argument.

- The multirow documentation regarding colored cells recommends using a negative number of rows. This will not work with lwarp, so \warpprintonly and \warpHTMLonly must be used to make versions for print and HTML.
- See section 319.2 for \multicolumrow.

⚠ \multicolumn & \multirow

lwarp does not support directly combining \multicolumn and \multirow. Use \multicolumnrow instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}
```

The two arguments for \multicolumn come first, followed by the five arguments for \multirow, many of which are optional, followed by the contents.

⚠ skipped cells

As per \multirow, skipped cells to the right of the \multicolumnrow statement are not included in the source code on the same line. On the following

⚠ empty cells

lines, \mcolrowcell must be used for each cell of each column and each row to be skipped:

```
... &  \multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}  & ...
... &  \mcolrowcell          &          \mcolrowcell   & ...
... &  \mcolrowcell          &          \mcolrowcell   & ...
```

vposn

Note that recent versions of multirow include a new optional vposn argument.

⚠ macro in a table

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use \TabularMacro just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \\
```

Column specifiers:

⚠ * column specification
- `*` in a column specification is not used (so far). Repeat the column type the correct number of times.

`@` and `!`
- Only one each of `@` and `!` is used at each column, and they are used in that order.

`\multirow`
- In `\multirow` cells, the print version may have extra instances of `<`, `>`, `@`, and `!` cells on the second and later rows in the `\multirow` which do not appear in the HTML version.

⚠ `\newcolumntype`
- `\newcolumntype` is ignored; unknown column types are set to `l`.

Rules:

- Doubled `\hlines`, `\midrules`, and vertical rules are supported.

vertical rules
- Vertical rules next to either side of an `@` or `!` column are displayed on both sides of the column.

width and trim
- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with `@` or `!` columns, and full-width rules ignore trim.

full-width rules
- `\toprule`, `\midrule`, `\bottomrule`, and `\hline` ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

combined rules
- If you wish to use `\cmidrule` followed by `\bottomrule`, it may be necessary to use:
  ```
  \cmidrule{2-3} \\[-2ex]
  \bottomrule
  ```
  The optional `-2ex` is ignored in HTML, but improves the visual formatting in the print output.

⚠ `\warpprintonly`
⚠ Misplaced `\noalign`
- For `\toprule` and `\bottomrule`, when combined with a `warpprint` or `warpHTML` environment, if a "Misplaced `\noalign`" error occurs, change
  ```
  This & That \endhead
  ```
  to
  ```
  \warpprintonly{This & That \endhead}
  ```
  and likewise with the other `\end` headings. Keep the `\endfirsthead` row unchanged, as it is still relevent to HTML output.

colortbl:

⚠ row/cell color

Only use `\rowcolor` and `\cellcolor` at the start of a row, in that order.

colortbl ignores the overhang arguments.

Other:

- tabularx ignores the width, but `X` columns do produce paragraph columns or multicolumns.

`longtable` headings
- For longtable, place headings and footings which do not apply to HTML inside `\warpprintonly{}`.

⚠ S columns

- For S columns (from the siunitx package), while producing print output, anything non-numeric must be placed inside { } braces, including commands such as \multirow. While producing HTML output, though, anything placed inside braces is not seen by lwarp's tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

```
\warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
\warpHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
```

for HTML output:

```
\begin{warpHTML}
```

71.2 Temporary package-related macros

These macros are temporary placeholders for macros defined by various packages. If the relevent package is not loaded, these placeholders are used instead.

71.2.1 arydshln

Emualated by the original LaTeX non-dashed versions.

```
\LetLtxMacro\hdashline\hline
\LetLtxMacro\cdashline\cline
\LetLtxMacro\firsthdashline\hline
\LetLtxMacro\lasthdashline\hline
```

71.3 Token lookahead

Used by \LWR@futurenonspacelet to look at the next token.

\LWR@mynexttoken

```
\newcommand\LWR@mynexttoken\relax
```

\futurelet copies the next token then executes a function to analyze

\LWR@futurenonspacelet does the same, but ignores intervening white space

Based on the booktabs style:

\LWR@futurenonspacelet

```
\def\LWR@futurenonspacelet#1{\def\LWR@cs{#1}%
\afterassignment\LWR@fnslone\let\nexttoken= }
\def\LWR@fnslone{\expandafter\futurelet\LWR@cs\LWR@fnsltwo}
\def\LWR@fnsltwo{%
```

```
\expandafter\ifx\LWR@cs\@sptoken\let\next=\LWR@fnslthree%
\else\let\next=\nexttoken\fi\next}
\def\LWR@fnslthree{\afterassignment\LWR@fnslone\let\next= }
```

`\LWR@getmynexttoken` Looks ahead and copies the next token into `\LWR@mynexttoken`.

```
\newcommand*{\LWR@getmynexttoken}{%
\LWR@traceinfo{LWR@getmynexttoken}%
% nothing must follow this next line
\LWR@futurenonspacelet\LWR@mynexttoken\LWR@tabledatacolumntag
}
```

71.4 Tabular variables

Bool `LWR@startedrow` True if should print a row tag before this column.

```
\newbool{LWR@startedrow}
\boolfalse{LWR@startedrow}
```

Bool `LWR@tabularcelladded` True if have added a data cell for this position.

```
\newbool{LWR@tabularcelladded}
\boolfalse{LWR@tabularcelladded}
```

Ctr `LWR@hlines` Number of `\hlines` or `\midrules` above the next row.

```
\newcounter{LWR@hlines}
```

Ctr `LWR@hdashedlines` Number of arydshln dashed lines above the next row.

```
\newcounter{LWR@hdashedlines}
```

Bool `LWR@doingtbrule` True if the next row will have a top/bottom rule above it.

```
\newbool{LWR@doingtbrule}
\boolfalse{LWR@doingtbrule}
```

Bool `LWR@doingcmidrule` True if the next row will have a cmidrule above it.

This is used by `\LWR@tabularfinishrow` to force a final empty row to create the border for the `\cmidrule`.

```
\newbool{LWR@doingcmidrule}
\boolfalse{LWR@doingcmidrule}
```

Bool `LWR@tableparcell` True if are handling a paragraph inside a table cell, so must close the paragraph tag before moving on.

```
\newbool{LWR@tableparcell}
```

Bool LWR@skippingmrowcell — True if are doing an empty \multirow cell, and thus there is no data tag to close.

```
\newbool{LWR@skippingmrowcell}
```

Bool LWR@skippingmcolrowcell — True if are doing an empty \multicolumnrow cell, and thus there is no data tag to close, and do not print @ and ! columns.

```
\newbool{LWR@skippingmcolrowcell}
```

Bool LWR@skipatbang — True if just finished a \multicolumn so should not create the trailing @ or ! columns table data cells.

```
\newbool{LWR@skipatbang}
```

Bool LWR@emptyatbang — True if finishing a row and should print empty @ or ! column table data cells.

```
\newbool{LWR@emptyatbang}
```

Bool LWR@intabularmetadata — True if are in a tabular but not in a data cell. Used to prevent extra HTML breaks if not inside table data.

```
\newbool{LWR@intabularmetadata}
\boolfalse{LWR@intabularmetadata}
```

Ctr LWR@tabularDepth — Tracks whether & is being used inside a tabular.

```
\newcounter{LWR@tabulardepth}
\setcounter{LWR@tabulardepth}{0}
```

Ctr LWR@tabularpardepth — Tracks whether should look ahead at the next token when encountering a \par while processing tabular contents.

When LWR@tabularpardepth is deeper than LWR@tabulardepth then lwarp has started looking at the contents of the tabular, and thus any \pars encountered must be followed by another token lookahead.

```
\newcounter{LWR@tabularpardepth}
\setcounter{LWR@tabularpardepth}{0}
```

```
\newcommand*{\LWR@colsresult}{}%temp storage for column format results
\newcommand*{\LWR@pposition}{}
\newcommand*{\LWR@pleft}{}
\newcommand*{\LWR@pright}{}
```

LWR@tablecolspec — Holds the parsed column specification, of total width LWR@tabletotalLaTeXcols, not counting @ and ! columns.

Will contain a string such as llrrccpc, exactly one letter per LaTeX table column, without @, !, >, <, or the vertical bar.

\LWR@strresult — Holds the result of Str functions.

```
\providecommand*{\LWR@strresult}{}
\providecommand*{\LWR@strresulttwo}{}
```

`\LWR@origcolspec` Holds the original column specs given to `tabular`.

```
\newcommand*{\LWR@origcolspec}{}
```

Ctr `LWR@tablecolspecwidth` Holds the number of tokens in the table columns specification.

This is includes one for each `@`, `!`, <, > column, and also one for each of the parameters of p, `@`, `!`, <, > columns, and three for each `D` column.

(This is not the total # of LaTeX columns in the table.)

```
\newcounter{LWR@tablecolspecwidth}
```

Ctr `LWR@tablecolspecindex` While parsing the LaTeX table column specification, starts at 1 and is incremented per token of the specification.

```
\newcounter{LWR@tablecolspecindex}
```

Ctr `LWR@tableLaTeXcolindex` While producing the table, resets to 1 at the start of the table and also at each end of line, and is incremented by 1 by each ampersand.

```
\newcounter{LWR@tableLaTeXcolindex}
```

Ctr `LWR@tabletotalLaTeXcols` While parsing a table column specification, begins at 0 and increments by 1 per LaTeX table column. Eventually holds the final number of LaTeX table columns in each row, not counting `@` and `!` columns. (In HTML, `@` and `!` cells become their own columns, but are not included in `LWR@tabletotalLaTeXcols`.)

```
\newcounter{LWR@tabletotalLaTeXcols}
```

Ctr `LWR@tabletotalLaTeXcolsnext` Holds the next LaTeX table column index while parsing, equal to one more than `LWR@tabletotalLaTeXcols`.

```
\newcounter{LWR@tabletotalLaTeXcolsnext}
```

`LWR@colatspec` A data array of specifications for `@` columns. The leftmost's index is `leftedge`, the others are counter values. See section 42.

`LWR@colbangspec` A data array of specifications for `!` columns. The leftmost's index is `leftedge`, the others are counter values. See section 42.

`LWR@colbeforespec` A data array of specifications for > columns.

`LWR@colafterspec` A data array of specifications for < columns.

`LWR@colbarspec` A data array of specifications for vertical rules.

71.5 Handling &, @, !, and bar

For technical discussion regarding problems redefining \&, See:
http://tex.stackexchange.com/questions/11638/
where-do-i-find-futurelets-nasty-behaviour-documented/11860#11860

\LWR@instertatbangcols

```
\newcommand*{\LWR@insertatbangcols}{%
\ifbool{LWR@skipatbang}%
{}%
{%
    \LWR@printatbang{at}{\arabic{LWR@tableLaTeXcolindex}}%
    \LWR@printatbang{bang}{\arabic{LWR@tableLaTeXcolindex}}%
}%
}
```

\LWR@closetabledatacell If LWR@skippingmrowcell or LWR@skippingmcolrowcell then there is no data tag to close. Otherwise, close any paragraphs, then close the data tag.

```
\newcommand*{\LWR@closetabledatacell}{%
\LWR@stoppars%
\global\booltrue{LWR@intabularmetadata}%
\ifbool{LWR@exitingtabular}{}%
{% not exiting tabular
    \ifboolexpr{bool{LWR@skippingmrowcell} or bool{LWR@skippingmcolrowcell}}%
    {%
```

If not skipping a \multicolumnrow cell, insert the @ and ! columns after this non-existant column.

```
        \ifbool{LWR@skippingmcolrowcell}%
            {}%
            {\LWR@insertatbangcols}%
    }%
    {% not skippingmrowcell
```

Insert any < then any @ and ! column contents, unless muted for the \bottomrule or a \multicolumn:

```
        \unskip%
        \ifboolexpr{%
            bool{LWR@tabularmutemods} or
            bool{LWR@skipatbang} or
            bool{LWR@emptyatbang}
        }%
        {}%
        {\LWR@getexparray{LWR@colafterspec}{\arabic{LWR@tableLaTeXcolindex}}}%
```

Close paragraphs:

```
        \ifbool{LWR@tableparcell}{\LWR@stoppars}{}%
        \global\boolfalse{LWR@tableparcell}%
```

Close the table data cell.

Close any color s.

```
        \whileboolexpr{test {\ifnumcomp{\value{LWR@cellcolordepth}}{>}{0}}}{%
            \LWR@htmltag{/div}\LWR@orignewline%
            \addtocounter{LWR@cellcolordepth}{-1}%
        }%
```

Skip the @ and ! cells if are closing a multicolumn cell.

```
        \leavevmode\unskip\LWR@htmltag{/td}\LWR@orignewline%
        \global\booltrue{LWR@tabularcelladded}%
        \LWR@insertatbangcols%
    }% not skipping mrowcell
}% not exiting tabular
\global\boolfalse{LWR@skippingmrowcell}%
\global\boolfalse{LWR@skippingmcolrowcell}%
\global\boolfalse{LWR@skipatbang}%
```

Color control. Column is set by >{} for each cell, so it must be cleared here.

```
\gdef\LWR@cellHTMLcolor{}
\gdef\LWR@columnHTMLcolor{}
\setcounter{LWR@cellcolordepth}{0}
}
```

When not used inside a tabular, & performs its original function as recorded here (with catcode 4).

```
\let\LWR@origampmacro&
```

```
\end{warpHTML}
```

71.5.1 Handling &

for HTML output:

```
\begin{warpHTML}
```

& Will behave depending on whether it is being used inside tabular.

& is redefined to test whether it is inside a tabular environment, in which case it performs special processing for HTML conversion. If not, it behaves normally.

```
\newcommand*{\LWR@tabularampersand}{%
\LWR@traceinfo{LWR@tabularampersand}%
\ifnumcomp{\value{LWR@tabulardepth}}{>}{0}%
{%
```

If not skipping a multirow cell, close the current data cell.

```
    \unskip%
    \LWR@closetabledatacell%
```

Move to the next column.

```
    \addtocounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
    \global\boolfalse{LWR@tabularcelladded}%
```

Look at the next token to decide multi or single column data tag.

```
    \LWR@getmynexttoken%
}%
```

If not inside a tabular, performs the original action:

```
{\LWR@origampmacro}%
}
```

& is left with its original catcode for now.

tikz package seems to require & be left alone until after tikz has been loaded. Also, cleveref uses the ampersand in one of its options.

& is made active inside a `tabular`.

& is left alone when in math alignments.

71.5.2 Filling an unfinished row

`\LWR@tabularfinishrow` Adds empty table cells if necessary to finish the row.

At the end of the table, if any bottom rules are requested then an empty row must be generated to form the borders which show the rules.

```
\newcommand*{\LWR@tabularfinishrow}{%
```

If not exiting the tabular, or doing a rule, or have already started a row, finish this row:

```
\ifboolexpr{%
    not bool {LWR@exitingtabular} or%
    bool{LWR@doingtbrule} or%
    bool{LWR@doingcmidrule} or%
    test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
    test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}} or%
    bool{LWR@startedrow}%
}{%
```

To temporarily turn off `LWR@exitingtabular` so that table data tags will still be generated:

If generating a final row for the `\bottomrule` borders, turn off the `@`, `!`, <, and > column output:

```
\ifbool{LWR@exitingtabular}{%
    \global\booltrue{LWR@tabularmutemods}%
}{%
    \global\boolfalse{LWR@tabularmutemods}%
}%
```

Locally reenable the table data tags until finished with the final row:

```
\global\boolfalse{LWR@exitingtabular}%
```

Generate table data tags and ampersands until the right edge:

```
\whileboolexpr{%
    test {
      \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}
    } or %
    (%
        bool{LWR@intabularmetadata} and%
        not bool{LWR@tabularcelladded} and%
        test {
        \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{\value{LWR@tabletotalLaTeXcols}}
        }%
    )%
}%
{%
    \LWR@tabledatasinglecolumntag%
```

The following is essentially `\LWR@tabularampersand` with `LWR@emptyatbang` added to empty the following cells:

```
    \LWR@closetabledatacell%
    \addtocounter{LWR@tableLaTeXcolindex}{1}%
    \global\boolfalse{LWR@tabularcelladded}%
    \global\booltrue{LWR@emptyatbang}%
```

Starts the next cell:

```
   \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}%
        {\LWR@getmynexttoken}%
        {}%
}%
```

Reenable the original `LWR@exitingtabular` to close the entire table:

```
\ifbool{LWR@tabularmutemods}{%
    \global\booltrue{LWR@exitingtabular}%
}{%
    \global\boolfalse{LWR@exitingtabular}%
}%
\global\boolfalse{LWR@tabularmutemods}%

\global\boolfalse{LWR@emptyatbang}%
}{}% ifboolexpr
}
```

71.6 Handling \\

Inside tabular, \\ is redefined to \LWR@tabularendofline

Throws away options \\[dim] or *

\LWR@tabularendofline

```
\NewDocumentCommand{\LWR@tabularendofline}{s o}{%
```

Finish the row:

```
\ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}%
    {\LWR@tabularfinishrow}%
    {\LWR@closetabledatacell}%
\LWR@htmltag{/tr}\LWR@orignewline%
```

xcolor row color support:

```
\@rowc@lors%
```

No longer inside a data cell:

```
\global\booltrue{LWR@intabularmetadata}%
```

Not yet started a table row:

```
\global\boolfalse{LWR@startedrow}%
```

Additional setup:

```
\setcounter{LWR@hlines}{0}%
\setcounter{LWR@hdashedlines}{0}%
\global\boolfalse{LWR@doingtbrule}%
\global\boolfalse{LWR@doingcmidrule}%
\LWR@clearmidrules%
\gdef\LWR@rowHTMLcolor{}%
```

Start at first column:

```
\setcounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
\global\boolfalse{LWR@tabularcelladded}%
```

Allow TEX to flush the pending paragraph. Not doing so causes a slowdown for very large tables.

```
\LWR@stoppars
\LWR@origpar
```

Look at the next token to decide between single column data tag or a special case:

```
\LWR@getmynexttoken%
}
```

71.7 Looking ahead in the column specifications

\LWR@columnspeclookahead {⟨*offset*⟩}

Looks `offset` tokens ahead in the column specification, setting `\LWR@strresulttwo`.

The `w` column alignment will be seen as a single unit such as `{c}`.

```
\newcommand*{\LWR@columnspeclookahead}[1]{%
\setcounter{LWR@tempcountone}{\value{LWR@tablecolspecindex}}%
\addtocounter{LWR@tempcountone}{#1}%
\fullexpandarg%
\StrChar{\LWR@origcolspec}{\arabic{LWR@tempcountone}}[\LWR@strresulttwo]%
```

Get the contents of the first group in `\LWR@strresulttwo`:

```
\exploregroups%
\StrChar{\LWR@strresulttwo}{1}[\LWR@strresulttwo]%
\noexploregroups%
}
```

71.8 Parsing @, >, <, !, bar columns

Holds the parsed argument for `@`, `>`, `<`, or `!` columns:

```
\newcommand*{\LWR@colparameter}{}
```

\LWR@parseatcolumn Handles `@{text}` columns.

```
\newcommand*{\LWR@parseatcolumn}{%
```

Move to the next token after the '@':

```
\LWR@traceinfo{at column}%
\addtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token into `\LWR@colparameter`, expanding once:

```
\LWR@traceinfo{about to read the next token:}%
\expandarg%
\StrChar{\LWR@origcolspec}%
    {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]
\fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
\LWR@traceinfo{have now read the next token}%
\ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
{% left edge of the table:
    \LWR@traceinfo{at the left edge}%
    \LWR@setexparray{LWR@colatspec}{leftedge}{\LWR@colparameter}%
    \LWR@traceinfo{at the left edge: %
    \LWR@getexparray{LWR@colatspec}{leftedge}}%
}%
{% not at the left edge:
    \LWR@traceinfo{not at the left edge}%
    \LWR@setexparray{LWR@colatspec}%
        {\arabic{LWR@tabletotalLaTeXcols}}{\LWR@colparameter}%
    \LWR@traceinfo{at \arabic{LWR@tabletotalLaTeXcols}: %
    \LWR@getexparray{LWR@colatspec}{\arabic{LWR@tabletotalLaTeXcols}}}%
}%
\let\LWR@colparameter\relax%
\global\booltrue{LWR@validtablecol}%
}
```

\LWR@parsebangcolumn Handles !{text} columns.

```
\newcommand*{\LWR@parsebangcolumn}{%
```

Move to the next token after the '!':

```
\LWR@traceinfo{bang column}%
\addtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token into \LWR@colparameter, expanding once:

```
\LWR@traceinfo{about to read the next token:}%
\expandarg%
\StrChar{\LWR@origcolspec}%
    {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]
\fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
\LWR@traceinfo{have now read the next token}%
\ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
{% left edge of the table:
    \LWR@traceinfo{at the left edge}%
    \LWR@setexparray{LWR@colbangspec}{leftedge}{\LWR@colparameter}%
}%
{% not at the left edge:
    \LWR@traceinfo{not at the left edge}%
    \LWR@setexparray{LWR@colbangspec}%
        {\arabic{LWR@tabletotalLaTeXcols}}{\LWR@colparameter}%
    \LWR@traceinfo{bang \arabic{LWR@tabletotalLaTeXcols}: \LWR@colparameter!}%
}%
\let\LWR@colparameter\relax%
\global\booltrue{LWR@validtablecol}%
```

```
}
```

\LWR@parsebeforecolumn Handles >{text} columns.

```
\newcommand*{\LWR@parsebeforecolumn}{%
```

Move to the next token after the '>':

```
\addtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token, expanding once into \LWR@colparameter:

```
\expandarg%
\StrChar{\LWR@origcolspec}%
    {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]%
\fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
\LWR@setexparray{LWR@colbeforespec}%
    {\arabic{LWR@tabletotalLaTeXcolsnext}}{\LWR@colparameter}%
\let\LWR@colparameter\relax%
\global\booltrue{LWR@validtablecol}%
}
```

\LWR@parseaftercolumn Handles <{text} columns.

```
\newcommand*{\LWR@parseaftercolumn}{%
```

Move to the next token after the '<':

```
\addtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token, expanding once into \LWR@colparameter:

```
\expandarg%
\StrChar{\LWR@origcolspec}%
    {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]%
\fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
\LWR@setexparray{LWR@colafterspec}%
    {\arabic{LWR@tabletotalLaTeXcols}}{\LWR@colparameter}%
\let\LWR@colparameter\relax%
\global\booltrue{LWR@validtablecol}%
}
```

\LWR@parsebarcolumn Handles vertical rules.

```
\newcommand*{\LWR@parsebarcolumn}{%
\LWR@traceinfo{LWR@parsebarcolumn}%
```

Remember the bar at this position:

```
\ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
{% left edge of the table:
    \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
    \ifdefstring{\LWR@tempone}{tvertbarl}%
    {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldouble}}%
    {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarl}}%
}%
{% not at the left edge:
    \edef\LWR@tempone{%
        \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcols}}%
    }%
    \ifdefstring{\LWR@tempone}{tvertbarr}%
    {%
        \LWR@setexparray{LWR@colbarspec}%
            {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdouble}%
    }%
    {%
        \LWR@setexparray{LWR@colbarspec}%
            {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarr}%
    }%
}%
\global\booltrue{LWR@validtablecol}%
}
```

`\LWR@parsecoloncolumn` Handles vertical rules.

```
\newcommand*{\LWR@parsecoloncolumn}{%
\LWR@traceinfo{LWR@parsecoloncolumn}%
```

Remember the bar at this position:

```
\ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
{% left edge of the table:
    \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
    \ifdefstring{\LWR@tempone}{tvertbarldash}%
    {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldoubledash}}%
    {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldash}}%
}%
{% not at the left edge:
    \edef\LWR@tempone{%
        \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcols}}%
    }%
    \ifdefstring{\LWR@tempone}{tvertbarrdash}%
    {\LWR@setexparray{LWR@colbarspec}%
        {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdoubledash}}%
    {\LWR@setexparray{LWR@colbarspec}%
        {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdash}}%
}%
\global\booltrue{LWR@validtablecol}%
}
```

\LWR@parsesemicoloncolumn Handles vertical rules.

```
\newcommand*{\LWR@parsesemicoloncolumn}{%
```

Treat ; as a : column:

```
\LWR@parsecoloncolumn%
```

Skip the following width token:

```
\addtocounter{LWR@tablecolspecindex}{1}%
}
```

71.9 Parsing 'l', 'c', or 'r' columns

\LWR@parsenormalcolumn {⟨*thiscolumn*⟩}

Add to the accumulated column specs, advance counters, and pre-clear another column of at, before, and after specs.

```
\newcommand*{\LWR@parsenormalcolumn}[1]{%
\addtocounter{LWR@tabletotalLaTeXcols}{1}%
\addtocounter{LWR@tabletotalLaTeXcolsnext}{1}%

\LWR@setexparray{LWR@tablecolspec}{\arabic{LWR@tabletotalLaTeXcols}}{#1}%

\LWR@traceinfo{normal column \arabic{LWR@tabletotalLaTeXcols}: #1}%
\LWR@setexparray{LWR@colatspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\LWR@setexparray{LWR@colbangspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\LWR@setexparray{LWR@colbeforespec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\LWR@setexparray{LWR@colafterspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\LWR@setexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\global\booltrue{LWR@validtablecol}%
}
```

71.10 Parsing 'p', 'm', or 'b' columns

\LWR@parsepcolumn {⟨*thiscolumn*⟩} The width will be ignored.

```
\newcommand*{\LWR@parsepcolumn}[1]{%
```

Converts to the given column type:

```
\LWR@parsenormalcolumn{#1}%
```

Skips the following width token:

```
\addtocounter{LWR@tablecolspecindex}{1}%
}
```

71.11 Parsing 'w' columns

\LWR@parsewcolumn The width will be ignored.

```
\newcommand*{\LWR@parsewcolumn}{%
\LWR@columnspeclookahead{1}%
\expandafter\LWR@parsenormalcolumn\expandafter{\LWR@strresulttwo}%
```

Skips the following width and alignment tokens:

```
\addtocounter{LWR@tablecolspecindex}{2}%
}
```

71.12 Parsing 'D' columns

From the dcolumn package.

\LWR@parseDcolumn {⟨*thiscolumn*⟩} The three parameters will be ignored.

```
\newcommand*{\LWR@parseDcolumn}[1]{%
```

Converts to the given column type.

```
\LWR@parsenormalcolumn{#1}%
```

Skips the following three parameters.

```
\addtocounter{LWR@tablecolspecindex}{3}%
}
```

71.13 Parsing the column specifications

⚠ tabular baselines HTML CSS cannot exactly match the LaTeX concept of a baseline for a table row. Table 10 shows the LaTeX results for various vertical-alignment choices, with the baseline of the first column drawn across all the columns for comparison. See the p column specification in table 11 for details.

Table 11 describes how each kind of column is converted to HTML.

Bool LWR@validtablecol True if found a valid table column type.

```
\newbool{LWR@validtablecol}
```

Bool LWR@opttablecol True if found a table column optional argument.

```
\newbool{LWR@opttablecol}
```

Table 10: Tabular baseline

l	p	m	b	r
			bot	
		mid	bot	
l	par	mid	bot	r
	par	mid		
	par			

Table 11: Tabular HTML column conversions

l, r, c: Converted to table cells without paragraph tags.
Uses CSS `vertical-align:middle` so that top or bottom-aligned cells may go above or below this cell.

p: Converted to table cells with paragraph tags. Ref: Table 10, LaTeX places the top line of a parbox aligned with the rest of the text line, so CSS `vertical-align:bottom` is used to have the HTML result appear with the paragraph extending below the L, R, C cells at the middle, if possible. This may be confusing as a P cell may not top-align with an L,R,C cell in the HTML conversion, especially in the presence of a B cell, and two P cells side-by-side will be aligned at the bottom instead of the top. Some adjustment of the CSS may be desired, changing `td.tdp`, `td.tdP`, `td.tdprule`, and `td.tdPrule` to `vertical-align: middle`. Another possibility is to change L,R,C, and P to `vertical-align: top` and not worry about the alignment of B and M cells or trying to approximate LaTeX baselines.

m: With paragraph tags, CSS `vertical-align:middle`.

b: With paragraph tags, CSS `vertical-align:top` so that the bottom of the text is closest to the middle of the text line.

P, M, B: Horizontally-centered versions.

S: Converted to 'r'. Ignores optional argument. From the siunitx package.

D: Converted to 'c'. From the dcolumn package.

@, !, >, <: One each, in that order.

|: Vertical rule.

Unknown: Converted to 'l'.

`\newcolumn`: Currently treated as unknown.

\LWR@parsetablecols {⟨*colspecs*⟩}

Scans the column specification left to right.

Builds \LWR@tablecolspec with the final specification, one LaTeX column per entry. The final number of LaTeX columns in each row is stored in LWR@tabletotalLaTeXcols, which is the number of & and \\ in each line, but which does not include @, !, <, > specifications in the count.

```
\newcommand*{\LWR@parsetablecols}[1]{%
\LWR@traceinfo{LWR@parsetablecols}%
```

Remember the original supplied column spec:

```
\renewcommand*{\LWR@origcolspec}{#1}%
```

Remove spaces:

```
\expandarg%
\StrSubstitute{\LWR@origcolspec}{ }{}[\LWR@origcolspec]%
```

The parsed column spec data array, LWR@tablecolspec, will be overwritten with new values.

Total number of columns found so far. Also pre-initialize the first several columns of specs:

```
\setcounter{LWR@tabletotalLaTeXcols}{0}%
\setcounter{LWR@tabletotalLaTeXcolsnext}{1}%
\LWR@setexparray{LWR@colatspec}{leftedge}{}%
\LWR@setexparray{LWR@colatspec}{1}{}%
\LWR@setexparray{LWR@colatspec}{2}{}%
\LWR@setexparray{LWR@colatspec}{3}{}%
\LWR@setexparray{LWR@colbangspec}{leftedge}{}%
\LWR@setexparray{LWR@colbangspec}{1}{}%
\LWR@setexparray{LWR@colbangspec}{2}{}%
\LWR@setexparray{LWR@colbangspec}{3}{}%
\LWR@setexparray{LWR@colbeforespec}{1}{}%
\LWR@setexparray{LWR@colbeforespec}{2}{}%
\LWR@setexparray{LWR@colbeforespec}{3}{}%
\LWR@setexparray{LWR@colafterspec}{1}{}%
\LWR@setexparray{LWR@colafterspec}{2}{}%
\LWR@setexparray{LWR@colafterspec}{3}{}%
\LWR@setexparray{LWR@colbarspec}{leftedge}{}%
\LWR@setexparray{LWR@colbarspec}{1}{}%
\LWR@setexparray{LWR@colbarspec}{2}{}%
\LWR@setexparray{LWR@colbarspec}{3}{}%
```

Starting at the first column specification:

```
\setcounter{LWR@tablecolspecindex}{1}%
```

Place the colspecs string length into \LWR@strresult, and remember the number of characters in the column specification:

```
\expandarg%
\StrLen{\LWR@origcolspec}[\LWR@strresult]%
\fullexpandarg%
\LWR@traceinfo{original column spec length: \LWR@strresult}%
\setcounter{LWR@tablecolspecwidth}{\LWR@strresult}%
```

Haven't seen any optional arguments so far

```
\global\boolfalse{LWR@opttablecol}%
```

Scan through the column specifications:

```
\whileboolexpr{%
    not test{%
        \ifnumcomp{\value{LWR@tablecolspecindex}}{>}%
            {\value{LWR@tablecolspecwidth}}%
    }%
}%
{%
```

Place the next single-character column type into \LWR@strresult:

```
\expandarg%
\StrChar{\LWR@origcolspec}{\arabic{LWR@tablecolspecindex}}[\LWR@strresult]%
\LWR@traceinfo{position \arabic{LWR@tablecolspecindex}: \LWR@strresult}%
\fullexpandarg%
```

Not yet found a valid column type:

```
\global\boolfalse{LWR@validtablecol}%
```

Skip over any optional arguments, such as siunitx S column:

```
\IfStrEq{\LWR@strresult}{[}{\global\booltrue{LWR@opttablecol}}{}%
```

Throw away anything found inside the optional argument:

```
\ifbool{LWR@opttablecol}%
{}% inside an optional argument
{% not an optional tabular argument
```

Not inside an optional argument, so consider the column type:

```
\IfStrEq{\LWR@strresult}{l}{\LWR@parsenormalcolumn{l}}{}%
\IfStrEq{\LWR@strresult}{c}{\LWR@parsenormalcolumn{c}}{}%
\IfStrEq{\LWR@strresult}{r}{\LWR@parsenormalcolumn{r}}{}%
\IfStrEq{\LWR@strresult}{L}{\LWR@parsenormalcolumn{l}}{}%
\IfStrEq{\LWR@strresult}{C}{\LWR@parsenormalcolumn{c}}{}%
\IfStrEq{\LWR@strresult}{R}{\LWR@parsenormalcolumn{r}}{}%
\IfStrEq{\LWR@strresult}{J}{\LWR@parsenormalcolumn{l}}{}%
```

```
\IfStrEq{\LWR@strresult}{S}{\LWR@parsenormalcolumn{c}}{}%
\IfStrEq{\LWR@strresult}{s}{\LWR@parsenormalcolumn{c}}{}%

\IfStrEq{\LWR@strresult}{\detokenize{@}}{\LWR@parseatcolumn}{}%
\IfStrEq{\LWR@strresult}{!}{\LWR@parsebangcolumn}{}%
\IfStrEq{\LWR@strresult}{>}{\LWR@parsebeforecolumn}{}%
\IfStrEq{\LWR@strresult}{<}{\LWR@parseaftercolumn}{}%
\IfStrEq{\LWR@strresult}{|}{\LWR@parsebarcolumn}{}%
\IfStrEq{\LWR@strresult}{:}{\LWR@parsecoloncolumn}{}%
\IfStrEq{\LWR@strresult}{;}{\LWR@parsesemicoloncolumn}{}%

\IfStrEq{\LWR@strresult}{p}{\LWR@parsepcolumn{p}}{}%
\IfStrEq{\LWR@strresult}{m}{\LWR@parsepcolumn{m}}{}%
\IfStrEq{\LWR@strresult}{b}{\LWR@parsepcolumn{b}}{}%

\IfStrEq{\LWR@strresult}{w}{\LWR@parsewcolumn}{}%
\IfStrEq{\LWR@strresult}{W}{\LWR@parsewcolumn}{}%
```

From the dcolumn package:

```
\IfStrEq{\LWR@strresult}{D}{\LWR@parseDcolumn{c}}{}%
```

From the tabularx package. X column has no parameter, but will be given paragraph tags.

```
\IfStrEq{\LWR@strresult}{X}{\LWR@parsenormalcolumn{X}}{}%
```

Many people define centered versions "P", "M", and "B":

```
\newcolumntype{P}[1]{>{\centering\arraybackslash}p{#1}}
```

```
\IfStrEq{\LWR@strresult}{P}{\LWR@parsepcolumn{P}}{}%
\IfStrEq{\LWR@strresult}{M}{\LWR@parsepcolumn{M}}{}%
\IfStrEq{\LWR@strresult}{B}{\LWR@parsepcolumn{B}}{}%
```

If this column was an invalid column type, convert it to an l column:

```
\ifbool{LWR@validtablecol}{}{%
    \LWR@traceinfo{invalid column type: \LWR@strresult}%
    \LWR@parsenormalcolumn{l}%
}%
}% not an optional column argument
```

If read the closing bracket, no longer inside the optional argument:

```
\IfStrEq{\LWR@strresult}{]}{\global\boolfalse{LWR@opttablecol}}{}%
```

Move to the next character:

```
\addtocounter{LWR@tablecolspecindex}{1}%
}% whiledo
}%
```

71.14 colortbl and xparse tabular color support

These macros provide a minimal emulation of some colortbl macros which might appear between table cells. If colortbl is loaded, these macros will be replaced with functional versions.

For each of the HTML colors below, the text for the HTML color is set if requested, but the macro is empty if none has been set.

`\rownum` Reserve a counter register.

```
\@ifundefined{rownum}{\newcount\rownum}{}
```

`\@rowcolors` Emulated in case xcolor is not used.

```
\newcommand*{\@rowcolors}{}
```

`\@rowc@lors` Emulated in case xcolor is not used.

```
\newcommand*{\@rowc@lors}{}
```

`\LWR@xcolorrowHTMLcolor` Emulated xcolor row color.

```
\newcommand*{\LWR@xcolorrowHTMLcolor}{}
```

`\LWR@columnHTMLcolor` HTMLstyle code for the column color.

```
\def\LWR@columnHTMLcolor{}
```

`\LWR@rowHTMLcolor` HTMLstyle code for the row color.

```
\def\LWR@rowHTMLcolor{}
```

`\LWR@cellHTMLcolor` HTMLstyle code for the cell color.

```
\def\LWR@cellHTMLcolor{}
```

`\LWR@ruleHTMLcolor` HTMLstyle code for the cell color.

```
\newcommand*{\LWR@ruleHTMLcolor}{}
```

\rowcolor [⟨*model*⟩] {⟨*color*⟩} [⟨*left overhang*⟩] [⟨*right overhang*⟩] Print version. The HTML version is in lwarp-colortbl. Used before starting a tabular data cell, thus \LWR@getmynexttoken.

```
\newcommand*{\rowcolor}{\LWR@getmynexttoken}%
```

\arrayrulecolor [⟨*model*⟩] {⟨*color*⟩}

\arrayrulecolornexttoken [⟨*model*⟩] {⟨*color*⟩}

Print versions for use outside and inside a tabular:

```
\newcommand{\arrayrulecolor}[2][named]{}
\newcommand{\arrayrulecolornexttoken}[2][named]{\LWR@getmynexttoken}
```

\doublerulesepcolor [⟨*model*⟩] {⟨*color*⟩}

\doublerulesepcolornexttoken [⟨*model*⟩] {⟨*color*⟩}

Print versions for use inside and outside a tabular:

```
\newcommand{\doublerulesepcolor}[2][named]{}
\newcommand{\doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}
```

71.15 Starting a new row

\LWR@maybenewtablerow If have not yet started a new table row, begin one now. Creates a new row tag, adding a class for hline or tbrule if necessary.

```
\newcommand*{\LWR@maybenewtablerow}
{%
\ifbool{LWR@startedrow}%
{}% started the row
{% not started the row
```

Remember that now have started the row:

```
    \global\booltrue{LWR@startedrow}%
```

Create the row tag, with a class if necessary.

```
    \global\booltrue{LWR@intabularmetadata}%
    \ifboolexpr{%
        test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
        test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}}%
    }%
    {%
        \LWR@htmltag{tr class="hline" }%
        \LWR@orignewline%
    }%
```

```
    {% not doing hline
        \ifbool{LWR@doingtbrule}%
        {%
            \ifdefvoid{\LWR@ruleHTMLcolor}{%
                \LWR@htmltag{tr class="tbrule"}%
            }{%
                \LWR@htmltag{%
                    tr class="tbrule" % space
                    style="border-top: 1px solid % space
                        \LWR@origpound\LWR@ruleHTMLcolor "%
                }%
            }%
            \LWR@orignewline%
        }%
        {\LWR@htmltag{tr}\LWR@orignewline}%
    }% end of not doing hline
}% end of not started the row
}
```

71.16 Printing vertical bar tags

\LWR@printbartag {⟨*index*⟩}

Adds to a tabular data cell an HTML class name for a left/right vertical bar.

```
\newcommand*{\LWR@printbartag}[1]{%
\LWR@traceinfo{LWR@printbartag !#1!}%
\ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
{}% muting or empty
{% not muting
    \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{#1}}%
    \ifdefempty{\LWR@tempone}{}{ \LWR@tempone}%
}% not muting
\LWR@traceinfo{LWR@printbartag done}%
}
```

71.17 Printing at or bang tags

\LWR@printatbang {⟨*at -or- bang*⟩} {⟨*index*⟩}

```
\newcommand*{\LWR@printatbang}[2]{%
```

Fetch the column at or bang spec:

```
\xdef\LWR@atbangspec{\LWR@getexparray{LWR@col#1spec}{#2}}%
\LWR@traceinfo{atbang: #2 !\LWR@atbangspec!}%
```

Only generate if is not empty;

```
\ifdefempty{\LWR@atbangspec}%
{}%
{% not empty
    \LWR@htmltag{%
        td class="td#1%
        \LWR@subaddcmidruletrim{}{}%
        \LWR@printbartag{#2}%
        "%
        \LWR@tdstartstyles%
        \LWR@addcmidrulewidth%
        \LWR@addcdashline%
        \LWR@addtabularrulecolors%
        \LWR@tdendstyles%
    }%
```

Create an empty cell if muting for the \bottomrule:

```
    \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
    {}%
    {\LWR@atbangspec}%
%
    \LWR@htmltag{/td}\LWR@orignewline%
    \global\booltrue{LWR@tabularcelladded}%
}% not empty
}%
```

\LWR@addleftmostbartag

```
\newcommand*{\LWR@addleftmostbartag}{%
\ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{1}{%
    \LWR@printbartag{leftedge}%
}{}%
}
```

\LWR@tabularleftedge

```
\newcommand*{\LWR@tabularleftedge}{%
\ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{1}%
{%
    \LWR@printatbang{at}{leftedge}%
    \LWR@printatbang{bang}{leftedge}%
}% left edge
{}% not left edge
}
```

71.18 Data opening tag

\LWR@thiscolspec Temporary storage.

```
\newcommand*{\LWR@thiscolspec}{}
```

\LWR@tabledatasinglecolumntag Print a table data opening tag with style for alignment and color.

```
\newcommand*{\LWR@tabledatasinglecolumntag}%
{%
\LWR@traceinfo{LWR@tabledatasinglecolumntag}%
\LWR@maybenewtablerow%
```

Don't start a new paragraph tag if have already started one:

```
\ifbool{LWR@intabularmetadata}%
{%
```

If have found the end of tabular command, do not create the next data cell:

```
    \ifbool{LWR@exitingtabular}{}%
    {% not exiting tabular
```

Print the `@` and `!` contents before first column:

```
        \LWR@tabularleftedge%
```

Fetch the current column's alignment character into `\LWR@strresult`:

```
        \xdef\LWR@strresult{%
          \LWR@getexparray{LWR@tablecolspec}{\arabic{LWR@tableLaTeXcolindex}}%
        }%
```

print the start of a new table data cell:

```
\LWR@traceinfo{LWR@tabledatasinglecolumntag: about to print td tag}%
        \LWR@htmltag{td class="td%
```

append this column's spec:

```
        \LWR@strresult%
```

If this column has a cmidrule, add "rule" to the end of the HTML class tag. Also add vertical bar tags.

```
        \LWR@addcmidruletrim%
        \LWR@addleftmostbartag%
        \LWR@printbartag{\arabic{LWR@tableLaTeXcolindex}}%
        "%
```

Add styles for rules, alignment:

```
        \LWR@tdstartstyles%
        \LWR@addcmidrulewidth%
        \LWR@addcdashline%


        \xdef\LWR@thiscolspec{%
          \LWR@getexparray{LWR@tablecolspec}{\arabic{LWR@tableLaTeXcolindex}}%
```

```
        }%
        \LWR@addformatwpalignment{\LWR@thiscolspec}%
```

Add styles for cell and rule colors:

```
        \LWR@addtabularrowcolor%
        \LWR@addtabularrulecolors%

        \LWR@tdendstyles%
        }% HTML td
        \LWR@traceinfo{LWR@tabledatasinglecolumntag: done printing td tag}%
```

If this is a `p`, `m`, `b`, or `X` column, allow paragraphs:

```
        \ifboolexpr{%
            test{ \ifdefstring{\LWR@strresult}{p} } or
            test{ \ifdefstring{\LWR@strresult}{m} } or
            test{ \ifdefstring{\LWR@strresult}{b} } or
            test{ \ifdefstring{\LWR@strresult}{P} } or
            test{ \ifdefstring{\LWR@strresult}{M} } or
            test{ \ifdefstring{\LWR@strresult}{B} } or
            test{ \ifdefstring{\LWR@strresult}{X} }
        }%
        {% allow pars
          \LWR@traceinfo{LWR@tabledatasinglecolumntag: about to LWR@startpars}%
            \global\booltrue{LWR@tableparcell}%
            \LWR@startpars%
         \LWR@traceinfo{LWR@tabledatasinglecolumntag: done with LWR@startpars}%
        }% allow pars
        {}% no pars
```

Print the > contents unless muted for the `\bottomrule`:

```
        \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
        {}%
        {%
         \LWR@getexparray{LWR@colbeforespec}{\arabic{LWR@tableLaTeXcolindex}}%
        }%
        \global\boolfalse{LWR@intabularmetadata}%
    }% not exiting tabular
}{}% in tabular metadata
\LWR@traceinfo{LWR@tabledatasinglecolumntag: done}%
}%
```

71.19 Midrules

`LWR@midrules` `LWR@midrules` is a data array (section 42) of columns each containing a non-zero width if a midrule should be created for this column.

`LWR@trimlrules` `LWR@trimlrules` is a data array (section 42) of columns containing `l` if a midrule should be left trimmed for each column.

LWR@trimrrules — LWR@trimrrules is a data array (section 42) of columns containing r if a midrule should be right trimmed for each column.

LWR@cdashlines — LWR@cdashlines is a data array (section 42) of columns each containing a Y if an arydshln package "cdashed line" should be created for this column.

Ctr LWR@midrulecounter — Indexes across the LWR@midrules and LWR@trim<l/r>rules data arrays.

```
\newcounter{LWR@midrulecounter}
```

Len \LWR@heavyrulewidth — The default width of the rule.

```
\newlength{\LWR@heavyrulewidth}
\setlength{\LWR@heavyrulewidth}{.08em}
```

Len \LWR@lightrulewidth — The default width of the rule.

```
\newlength{\LWR@lightrulewidth}
\setlength{\LWR@lightrulewidth}{.05em}
```

Len \LWR@cmidrulewidth — The default width of the rule.

```
\newlength{\LWR@cmidrulewidth}
\setlength{\LWR@cmidrulewidth}{.03em}
```

Len \LWR@thiscmidrulewidth — The width of the next rule, defaulting to \LWR@cmidrulewidth.

If not \LWR@cmidrulewidth, a style will be used to generate the custom width.

Assigned from the LWR@midrules array.

```
\newlength{\LWR@thiscmidrulewidth}
\setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}
```

\LWR@clearmidrules — Start new midrules. Called at beginning of tabular and also at \\.

Clears all LWR@midrules and LWR@trimrules markers for this line.

```
\newcommand*{\LWR@clearmidrules}
{%
\setcounter{LWR@midrulecounter}{1}%
\whileboolexpr{%
    not test{%
        \ifnumcomp{\value{LWR@midrulecounter}}{>}%
            {\value{LWR@tabletotalLaTeXcols}}%
    }%
}%
{%
    \LWR@setexparray{LWR@midrules}{\arabic{LWR@midrulecounter}}{0pt}%
    \setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
    \LWR@setexparray{LWR@trimlrules}{\arabic{LWR@midrulecounter}}{}%
    \LWR@setexparray{LWR@trimrrules}{\arabic{LWR@midrulecounter}}{}%
    \LWR@setexparray{LWR@cdashlines}{\arabic{LWR@midrulecounter}}{N}%
    \addtocounter{LWR@midrulecounter}{1}%
```

```
}%
}
```

`\LWR@subcmidrule` {⟨*width*⟩} {⟨*trim*⟩} {⟨*leftcolumn*⟩} {⟨*rightcolumn*⟩}

Marks `LWR@midrules` data array elements to be non-zero widths from left to right columns. Also marks trimming for the L and/or R columns.

`LWR@doingcmidrule` is set to force an empty row at the end of the tabular to create the rule.

```
\newcommand*{\LWR@subcmidrule}[4]{%
\setcounter{LWR@midrulecounter}{#3}%
\whileboolexpr{%
    not test {%
        \ifnumcomp{\value{LWR@midrulecounter}}{>}{#4}%
    }%
}%
{%
    \LWR@setexparray{LWR@midrules}{\arabic{LWR@midrulecounter}}{#1}%
    \addtocounter{LWR@midrulecounter}{1}%
}% whiledo
\IfSubStr{#2}{l}{\LWR@setexparray{LWR@trimlrules}{#3}{l}}{}%
\IfSubStr{#2}{r}{\LWR@setexparray{LWR@trimrrules}{#4}{r}}{}%
\global\booltrue{LWR@doingcmidrule}%
}
```

`\LWR@docmidrule` [⟨*width*⟩] (⟨*trim*⟩) {⟨*leftcolumn-rightcolumn*⟩}

Marks `LWR@midrules` array elements to be a non-zero width from left to right columns. Also marks trimming for the L and/or R columns.

```
\NewDocumentCommand{\LWR@docmidrule}
    {O{\LWR@cmidrulewidth} D(){} >{\SplitArgument{1}{-}}m}
    {\LWR@subcmidrule{#1}{#2}#3}
```

`\LWR@subcdashline` {⟨*leftcolumn*⟩} {⟨*rightcolumn*⟩}

Marks `LWR@cdashlines` data array elements to be `Y` from left to right columns.

`LWR@doingcmidrule` is set to force an empty row at the end of the tabular to create the rule.

```
\newcommand*{\LWR@subcdashline}[2]{%
\setcounter{LWR@midrulecounter}{#1}%
\whileboolexpr{%
    not test {%
        \ifnumcomp{\value{LWR@midrulecounter}}{>}{#2}%
    }%
}%
{%
    \LWR@setexparray{LWR@cdashlines}{\arabic{LWR@midrulecounter}}{Y}%
    \addtocounter{LWR@midrulecounter}{1}%
```

```
}% whiledo
\global\booltrue{LWR@doingcmidrule}%
}
```

`\LWR@docdashline` {⟨*leftcolumn-rightcolumn*⟩}

Marks `LWR@cdashlines` data array elements to be `Y` from left to right columns.

```
\NewDocumentCommand{\LWR@docdashline}
    {>{\SplitArgument{1}{-}}m}%
    {%
        \LWR@subcdashline#1%
    }
```

Used to compute margins, tabular trims, column offsets:

```
\newlength{\LWR@templengthone}
\newlength{\LWR@templengthtwo}
\newlength{\LWR@templengththree}
\newcounter{LWR@tempcountone}
```

Used to add a style to a table data cell:

```
\newbool{LWR@tdhavecellstyle}
```

`\LWR@tdstartstyles` Begins possibly adding a table data cell style.

```
\newcommand*{\LWR@tdstartstyles}{\global\boolfalse{LWR@tdhavecellstyle}}
```

`\LWR@tdaddstyle` Starts adding a table data cell style.

```
\newcommand*{\LWR@tdaddstyle}{%
\ifbool{LWR@tdhavecellstyle}%
{; }%
{ style="}%
\booltrue{LWR@tdhavecellstyle}%
}
```

`\LWR@tdendstyles` Finishes possibly adding a table data cell style. Prints the closing quote.

```
\newcommand*{\LWR@tdendstyles}{%
\ifbool{LWR@tdhavecellstyle}{%
    "%
    \global\boolfalse{LWR@tdhavecellstyle}%
}{}%
}
```

`\LWR@subaddcmidruletrim` {⟨*lefttrim*⟩} {⟨*righttrim*⟩} Adds a `\cmidrule` with optional trim.

```
\newcommand*{\LWR@subaddcmidruletrim}[2]{%
```

```
\setlength{\LWR@templengthone}{%
        \LWR@getexparray{LWR@midrules}{\arabic{LWR@tableLaTeXcolindex}}%
}%
\ifdimcomp{\LWR@templengthone}{>}{0pt}%
{%
```

Print the class with left and right trim letters appended:

```
    \LWR@origtilde tdrule#1#2%
```

Remember the width of the rule:

```
    \setlength{\LWR@thiscmidrulewidth}{\LWR@templengthone}%
}%
{%
    \setlength{\LWR@thiscmidrulewidth}{0pt}%
}%
}
```

`\LWR@addcmidruletrim` Adds left or right trim to a `\cmidrule`.

```
\newcommand*{\LWR@addcmidruletrim}{%
\LWR@subaddcmidruletrim%
{\LWR@getexparray{LWR@trimlrules}{\arabic{LWR@tableLaTeXcolindex}}}%
{\LWR@getexparray{LWR@trimrrules}{\arabic{LWR@tableLaTeXcolindex}}}%
}
```

`\LWR@addrulewidth` {⟨*thiswidth*⟩} {⟨*defaultwidth*⟩}

If not default width, add a custom style with width and color depending on `thiswidth`.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
\newcommand{\LWR@addrulewidth}[2]{%
```

Only add a custom width if `thiswidth` is different than the `defaultwidth`, or if a color is being used:

```
\ifboolexpr{%
    test{\ifdimcomp{#1}{=}{0pt}} or
    (
        ( test{\ifdimcomp{#1}{=}{#2}} and not bool{FormatWP} )
        and ( test {\ifdefvoid{\LWR@ruleHTMLcolor}} )
    )
}%
{}% default width and color
{% custom width and/or color
```

Ensure that the width is wide enough to display in the browser:

```
    \LWR@forceminwidth{#1}%
```

Begin adding another style:

```
    \LWR@tdaddstyle%
```

The style itself:

```
    border-top:\LWR@printlength{\LWR@atleastonept} solid %
```

If default gray, the darkness of the color depends on the thickness of the rule:

```
    \ifdefvoid{\LWR@ruleHTMLcolor}{%
        \ifdimcomp{#1}{<}{\LWR@lightrulewidth}%
        {\LWR@origpound{}A0A0A0}%
        {% lightrule or heaver
            \ifdimcomp{#1}{<}{\LWR@heavyrulewidth}%
            {\LWR@origpound{}808080}%
            {black}%
        }% lightrule or heavier
    }{%
        \LWR@origpound\LWR@ruleHTMLcolor%
    }
}% custom width and/or color
}
```

`\LWR@addcmidrulewidth` Adds a `style` for the rule width.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
\newcommand{\LWR@addcmidrulewidth}{%
\LWR@addrulewidth{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
}
```

`\LWR@addcdashline` Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
\newcommand{\LWR@addcdashline}{%
\edef\LWR@tempone{%
    \LWR@getexparray{LWR@cdashlines}{\arabic{LWR@tableLaTeXcolindex}}%
}%
\ifdefstring{\LWR@tempone}{Y}{%
    \LWR@tdaddstyle%
    border-top: 1pt dashed %
    \ifdefvoid{\LWR@ruleHTMLcolor}%
        {black}%
        {\LWR@origpound\LWR@ruleHTMLcolor}%
}{}%
}
```

`\LWR@WPcell` {⟨*text-align*⟩} {⟨*vertical-align*⟩}

```
\newcommand*{\LWR@WPcell}[2]{%
\LWR@tdaddstyle%
\LWR@print@mbox{text-align:#1}; \LWR@print@mbox{vertical-align:#2}%
}
```

\LWR@addformatwpalignment If FormatWP, adds a style for the alignment.

Must be placed between \LWR@tdstartstyles and \LWR@tdendstyles.

```
\newcommand*{\LWR@addformatwpalignment}[1]{%
\ifbool{FormatWP}{%
\IfSubStr{#1}{l}{\LWR@WPcell{left}{middle}}{}%
\IfSubStr{#1}{c}{\LWR@WPcell{center}{middle}}{}%
\IfSubStr{#1}{r}{\LWR@WPcell{right}{middle}}{}%
\IfSubStr{#1}{p}{\LWR@WPcell{left}{bottom}}{}%
\IfSubStr{#1}{m}{\LWR@WPcell{left}{middle}}{}%
\IfSubStr{#1}{b}{\LWR@WPcell{left}{top}}{}%
\IfSubStr{#1}{P}{\LWR@WPcell{center}{bottom}}{}%
\IfSubStr{#1}{M}{\LWR@WPcell{center}{middle}}{}%
\IfSubStr{#1}{B}{\LWR@WPcell{center}{top}}{}%
}{}%
}
```

71.20 Cell colors

\LWR@addtabularrowcolor Adds a cell's row color style, if needed.

No color is added for the final row of empty cells which finishes each tabular.

```
\newcommand*{\LWR@addtabularrowcolor}{%
\ifbool{LWR@tabularmutemods}{}{%
    \ifdefvoid{\LWR@rowHTMLcolor}{%
        \ifdefvoid{\LWR@xcolorrowHTMLcolor}{}%
        {% xcolor row color
            \LWR@tdaddstyle%
            background:\LWR@origpound\LWR@xcolorrowHTMLcolor%
        }%
    }%
    {% explicit row color
        \LWR@tdaddstyle%
        background:\LWR@origpound\LWR@rowHTMLcolor%
    }%
}%
}
```

\LWR@addtabularhrulecolor Adds a cell's horizontal rule color style, if needed.

```
\newcommand*{\LWR@addtabularhrulecolor}{%
```

If either form of horizontal rule is requested:

```
\ifboolexpr{%
    test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
    test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}} or%
    bool{LWR@doingtbrule}%
}{%
```

If there is a no custom color:

```
    \ifdefvoid{\LWR@ruleHTMLcolor}%
    {%
        \ifnumcomp{\value{LWR@hlines}}{>}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 4px double%
        }{% else
        \ifnumcomp{\value{LWR@hdashedlines}}{>}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 2px dashed%
        }{% else
        \ifnumcomp{\value{LWR@hdashedlines}}{=}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 1px dashed%
        }{}}}%
```

If no color and not doubled or dashed, then add nothing, since a simpler rule is the default.

```
    }%
```

If there is a custom color:

```
    {%
        \ifnumcomp{\value{LWR@hlines}}{>}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 4px double \LWR@origpound\LWR@ruleHTMLcolor%
        }{% else
        \ifnumcomp{\value{LWR@hdashedlines}}{>}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 2px dashed \LWR@origpound\LWR@ruleHTMLcolor%
        }{% else
        \ifnumcomp{\value{LWR@hdashedlines}}{=}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 1px dashed \LWR@origpound\LWR@ruleHTMLcolor%
        }{% else
            \LWR@tdaddstyle%
            border-top: 1px solid \LWR@origpound\LWR@ruleHTMLcolor%
        }}}%
    }%
}{}%
}
```

`\LWR@addtabularrulecolors` Adds a cell's rule color styles, if needed.

No color is added for the final row of empty cells which finishes each `tabular`.

```
\newcommand*{\LWR@addtabularrulecolors}{%
```

Custom horizonal rule color:

```
\LWR@addtabularhrulecolor%
```

No vertical rules if finishing the `tabular` with a row of empty cells:

```
\ifbool{LWR@tabularmutemods}{}{%
```

If at the leftmost cell, possibly add a leftmost vertical rule:

```
    \ifnumequal{\value{LWR@tableLaTeXcolindex}}{1}{%
```

Fetch the left edge's vertical bar specification:

```
        \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
```

Add a custom style if a vertical bar was requested:

```
        \ifdefstring{\LWR@tempone}{tvertbarl}{%
                \LWR@tdaddstyle%
                border-left: 1px solid % space
                    \LWR@vertruleHTMLcolor%
        }{}%
        \ifdefstring{\LWR@tempone}{tvertbarldouble}{%
                \LWR@tdaddstyle%
                border-left: 4px double % space
                    \LWR@vertruleHTMLcolor%
        }{}%
        \ifdefstring{\LWR@tempone}{tvertbarldash}{%
                \LWR@tdaddstyle%
                border-left: 1px dashed % space
                    \LWR@vertruleHTMLcolor%
        }{}%
        \ifdefstring{\LWR@tempone}{tvertbarldoubledash}{%
                \LWR@tdaddstyle%
                border-left: 2px dashed % space
                    \LWR@vertruleHTMLcolor%
        }{}%
    }{}%
```

Possibly add a right vertical rule for this cell:

```
    \edef\LWR@tempone{%
        \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tableLaTeXcolindex}}%
    }%
    \ifdefstring{\LWR@tempone}{tvertbarr}{%
```

Add a custom style if a vertical bar was requested:

```
            \LWR@tdaddstyle%
            border-right: 1px solid \LWR@vertruleHTMLcolor%
    }{}%
```

```
    \ifdefstring{\LWR@tempone}{tvertbarrdouble}{%
            \LWR@tdaddstyle%
            border-right: 4px double \LWR@vertruleHTMLcolor%
    }{}%
    \ifdefstring{\LWR@tempone}{tvertbarrdash}{%
            \LWR@tdaddstyle%
            border-right: 1px dashed \LWR@vertruleHTMLcolor%
    }{}%
    \ifdefstring{\LWR@tempone}{tvertbarrdoubledash}{%
            \LWR@tdaddstyle%
            border-right: 2px dashed \LWR@vertruleHTMLcolor%
    }{}%
}%
}
```

Ctr `LWR@cellcolordepth` Counts how many cell color s were added to the current tabular data cell.

```
\newcounter{LWR@cellcolordepth}
```

`\LWR@subaddtabularcellcolor` {⟨*HTML color*⟩}

```
\newcommand*{\LWR@subaddtabularcellcolor}[1]{%
\LWR@htmltag{div class="cellcolor" style="%
    background:\LWR@origpound{}{}#1 %
" }%
\addtocounter{LWR@cellcolordepth}{1}%
}
```

`\LWR@addtabularcellcolor` Adds a cell color style, if needed.

```
\newcommand*{\LWR@addtabularcellcolor}{%
\ifdefvoid{\LWR@cellHTMLcolor}%
{%
    \ifdefvoid{\LWR@rowHTMLcolor}%
    {%
        \ifdefvoid{\LWR@xcolorrowHTMLcolor}%
        {%
            \ifdefvoid{\LWR@columnHTMLcolor}%
            {}%
            {\LWR@subaddtabularcellcolor{\LWR@columnHTMLcolor}}%
        }%
        {\LWR@subaddtabularcellcolor{\LWR@xcolorrowHTMLcolor}}%
    }%
    {\LWR@subaddtabularcellcolor{\LWR@rowHTMLcolor}}%
}%
{\LWR@subaddtabularcellcolor{\LWR@cellHTMLcolor}}%
}
```

71.21 Multicolumns

71.21.1 Parsing multicolumns

```
\newcounter{LWR@tablemulticolswidth}
```

Indexes into the multicolumn specification:

```
\newcounter{LWR@tablemulticolspos}
```

Remembers multicolumn vertical rules if found in the column spec.

```
\newcounter{LWR@mcolvertbarsl}
\newcounter{LWR@mcolvertbarsr}
\newcounter{LWR@mcolvertbarsldash}
\newcounter{LWR@mcolvertbarsrdash}
\newbool{LWR@mcolvertbaronleft}%
```

`\LWR@printmccoltype` {⟨*colspec*⟩} Print any valid column type found. Does not print `@`, `!`, `>`, or `<` columns or their associated tokens.

This is printed as part of the table data tag's `class`.

```
\newcommand*{\LWR@printmccoltype}[1]{%
\LWR@traceinfo{lwr@printmccoltype -#1-}%
```

Get one token of the column spec:

```
\StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
```

Add to the HTML tag depending on which column type is found:

```
\IfStrEq{\LWR@strresult}{l}{l}{}%
\IfStrEq{\LWR@strresult}{c}{c}{}%
\IfStrEq{\LWR@strresult}{r}{r}{}%
\IfStrEq{\LWR@strresult}{p}{p}{}%
\IfStrEq{\LWR@strresult}{m}{m}{}%
\IfStrEq{\LWR@strresult}{b}{b}{}%
\IfStrEq{\LWR@strresult}{P}{P}{}%
\IfStrEq{\LWR@strresult}{M}{M}{}%
\IfStrEq{\LWR@strresult}{B}{B}{}%

\IfStrEq{\LWR@strresult}{w}{w}{}%
\IfStrEq{\LWR@strresult}{W}{W}{}%

\IfStrEq{\LWR@strresult}{S}{c}{}%
\IfStrEq{\LWR@strresult}{s}{c}{}%

\IfStrEq{\LWR@strresult}{X}{p}{}%

\IfStrEq{\LWR@strresult}{|}%
{%
```

```
    \ifbool{LWR@mcolvertbaronleft}%
        {\addtocounter{LWR@mcolvertbarsl}{1}}% left edge
        {\addtocounter{LWR@mcolvertbarsr}{1}}% not left edge
}%
{%
    \IfStrEq{\LWR@strresult}{:}%
    {%
        \ifbool{LWR@mcolvertbaronleft}%
            {\addtocounter{LWR@mcolvertbarsldash}{1}}% left edge
            {\addtocounter{LWR@mcolvertbarsrdash}{1}}% not left edge
    }%
    {%
        \IfStrEq{\LWR@strresult}{;}%
        {%
            \ifbool{LWR@mcolvertbaronleft}%
                {\addtocounter{LWR@mcolvertbarsldash}{1}}% left edge
                {\addtocounter{LWR@mcolvertbarsrdash}{1}}% not left edge
        }%
        {\boolfalse{LWR@mcolvertbaronleft}}%
    }%
}%
\LWR@traceinfo{lwr@printmccoltype done}%
}
```

`\LWR@multicolpartext` {⟨*num parameters*⟩} Print the data with paragraph tags, advance to bypass the given number of parameters.

```
\newcommand*{\LWR@multicolpartext}[1]{%
\LWR@startpars%
\LWR@multicoltext%
\addtocounter{LWR@tablemulticolspos}{#1}%
\LWR@stoppars%
}
```

`\LWR@multicolother` {⟨*colspec*⟩} For `@`, `!`, `>`, `<`, print the next token without paragraph tags:

```
\newcommand*{\LWR@multicolother}[1]{%
\addtocounter{LWR@tablemulticolspos}{1}%
\StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
\LWR@strresult%
```

A valid column data type was found:

```
\global\booltrue{LWR@validtablecol}%
}
```

`\LWR@multicolskip` Nothing to print for this column type.

```
\newcommand*{\LWR@multicolskip}{%
```

A valid column data type was found:

```
\global\booltrue{LWR@validtablecol}%
```

```
}
```

`\LWR@printmccoldata` {⟨*colspec*⟩} Print the data for any valid column type found.

```
\newcommand*{\LWR@printmccoldata}[1]{%
\LWR@traceinfo{lwr@printmccoldata -#1}%
```

Not yet found a valid column type:

```
\global\boolfalse{LWR@validtablecol}%
```

Get one token of the column spec:

```
\StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
```

Print the text depending on which column type is found. Also handles `@`, `>`, `<` as it comes to them.

```
\IfStrEq{\LWR@strresult}{l}{\LWR@multicoltext}{}%
\IfStrEq{\LWR@strresult}{c}{\LWR@multicoltext}{}%
\IfStrEq{\LWR@strresult}{r}{\LWR@multicoltext}{}%
\IfStrEq{\LWR@strresult}{D}{%
\addtocounter{LWR@tablemulticolspos}{3}% skip parameters
\LWR@multicoltext%
}{}%

\IfStrEq{\LWR@strresult}{p}{\LWR@multicolpartext{0}}{}%
\IfStrEq{\LWR@strresult}{m}{\LWR@multicolpartext{0}}{}%
\IfStrEq{\LWR@strresult}{b}{\LWR@multicolpartext{0}}{}%
\IfStrEq{\LWR@strresult}{P}{\LWR@multicolpartext{0}}{}%
\IfStrEq{\LWR@strresult}{M}{\LWR@multicolpartext{0}}{}%
\IfStrEq{\LWR@strresult}{B}{\LWR@multicolpartext{0}}{}%

\IfStrEq{\LWR@strresult}{w}{\LWR@multicolpartext{3}}{}%
\IfStrEq{\LWR@strresult}{W}{\LWR@multicolpartext{3}}{}%

\IfStrEq{\LWR@strresult}{S}{\LWR@multicoltext}{}%
\IfStrEq{\LWR@strresult}{s}{\LWR@multicoltext}{}%

\IfStrEq{\LWR@strresult}{X}{\LWR@multicolpartext{0}}{}%
\IfStrEq{\LWR@strresult}{|}{\LWR@multicolskip}{}%
\IfStrEq{\LWR@strresult}{:}{\LWR@multicolskip}{}%
\IfStrEq{\LWR@strresult}{;}{%
    \LWR@multicolskip%
    \addtocounter{LWR@tablemulticolspos}{1}% skip parameter
}{}%
\IfStrEq{\LWR@strresult}{\detokenize{@}}{\LWR@multicolother{#1}}{}%
\IfStrEq{\LWR@strresult}{\detokenize{!}}{\LWR@multicolother{#1}}{}%
\IfStrEq{\LWR@strresult}{\detokenize{>}}{\LWR@multicolother{#1}}{}%
\IfStrEq{\LWR@strresult}{\detokenize{<}}{\LWR@multicolother{#1}}{}%
```

If an invalid column type:

```
\ifbool{LWR@validtablecol}{}{\LWR@multicoltext}%
```

Tracing:

```
\LWR@traceinfo{lwr@printmccoldata done}%
}
```

\parsemulticolumnalignment {⟨*1: colspec*⟩} {⟨*2: printresults*⟩}

Scan the multicolumn specification and execute the printfunction for each entry.

Note that the spec for a p{spec} column, or @, >, <, is a token list which will NOT match l, c, r, or p.

```
\newcommand*{\LWR@parsemulticolumnalignment}[2]{%
\setcounter{LWR@tablemulticolspos}{1}%
\StrLen{#1}[\LWR@strresult]%
\setcounter{LWR@tablemulticolswidth}{\LWR@strresult}%
```

Scan across the tokens in the column spec:

```
\whileboolexpr{%
    not test {%
        \ifnumcomp{\value{LWR@tablemulticolspos}}{>}%
            {\value{LWR@tablemulticolswidth}}%
    }%
}%
{%
```

Execute the assigned print function for each token in the column spec:

```
#2{#1}%
```

Move to the next token in the column spec:

```
\addtocounter{LWR@tablemulticolspos}{1}%
}%
}
```

71.21.2 Multicolumn factored code

\LWR@addmulticolvertrulecolor

```
\newcommand*{\LWR@addmulticolvertrulecolor}{%
```

No vertical rules if finishing the tabular with a row of empty cells:

```
\ifbool{LWR@tabularmutemods}{}{%
```

Left side:

```
    \ifnumcomp{\value{LWR@mcolvertbarsl}}{=}{1}{%
        \LWR@tdaddstyle%
        border-left: 1px solid \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsl}}{>}{1}{%
        \LWR@tdaddstyle%
        border-left: 4px double \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{%
        \LWR@tdaddstyle%
        border-left: 1px dashed \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}{%
        \LWR@tdaddstyle%
        border-left: 2px dashed \LWR@vertruleHTMLcolor%
    }{}%
```

Right side:

```
    \ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{%
        \LWR@tdaddstyle%
        border-right: 1px solid \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{%
        \LWR@tdaddstyle%
        border-right: 4px double \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{%
        \LWR@tdaddstyle%
        border-right: 1px dashed \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}{%
        \LWR@tdaddstyle%
        border-right: 2px dashed \LWR@vertruleHTMLcolor%
    }{}%
}%
}
```

```
\newcommand{\LWR@multicoltext}{}
```

To find multicolumn right trim:

```
\newcounter{LWR@lastmulticolumn}
```

`\LWR@domulticolumn` `[`⟨*1: vpos*⟩`]` `[`⟨*2: #rows*⟩`]` {⟨*3: numLaTeXcols*⟩} {⟨*4: numHTMLcols*⟩} {⟨*5: colspec*⟩} {⟨*6: text*⟩}

```
\NewDocumentCommand{\LWR@domulticolumn}{o o m m m +m}{%
\LWR@traceinfo{LWR@domulticolumn -#1- -#2- -#4- -#5-}%
```

Remember the text to be inserted, and remember that a valid column type was found:

```
\renewcommand{\LWR@multicoltext}{%
#6%
\global\booltrue{LWR@validtablecol}%
}%
```

Compute the rightmost column to be included. This is used to create the right trim.

```
\setcounter{LWR@lastmulticolumn}{\value{LWR@tableLaTeXcolindex}}%
\addtocounter{LWR@lastmulticolumn}{#3}%
\addtocounter{LWR@lastmulticolumn}{-1}%
```

Row processing:

```
\LWR@maybenewtablerow%
```

Begin the opening table data tag:

```
\LWR@htmltag{td colspan="#4" %

\IfValueT{#2}{ % rows?
rowspan="#2" %


\IfValueT{#1}{% vpos?
\ifstrequal{#1}{b}{style="\LWR@print@mbox{vertical-align:bottom}" }{}%
\ifstrequal{#1}{t}{style="\LWR@print@mbox{vertical-align:top}" }{}%
}% vpos?
}% rows?

 class="td%
```

Print the column type and vertical bars:

```
\setcounter{LWR@mcolvertbarsl}{0}%
\setcounter{LWR@mcolvertbarsr}{0}%
\setcounter{LWR@mcolvertbarsldash}{0}%
\setcounter{LWR@mcolvertbarsrdash}{0}%
\booltrue{LWR@mcolvertbaronleft}%
\LWR@parsemulticolumnalignment{#5}{\LWR@printmccoltype}%
```

If this column has a cmidrule, add "rule" to the end of the HTML class tag.

If this position had a "Y" then add "rule" for a horizontal rule:

```
\LWR@subaddcmidruletrim%
{\LWR@getexparray{LWR@trimlrules}{\arabic{LWR@tableLaTeXcolindex}}}%
{\LWR@getexparray{LWR@trimrrules}{\arabic{LWR@lastmulticolumn}}}%
```

Also add vertical bar class.

```
\ifnumcomp{\value{LWR@mcolvertbarsl}}{=}{1}{ tvertbarl}{}%
\ifnumcomp{\value{LWR@mcolvertbarsl}}{>}{1}{ tvertbarldouble}{}%
\ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{ tvertbarr}{}%
\ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{ tvertbarrdouble}{}%
```

```
\ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{ tvertbarldash}{}%
\ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}{ tvertbarldoubledash}{}%
\ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{ tvertbarrdash}{}%
\ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}{ tvertbarrdoubledash}{}%
```

Close the class tag's opening quote: " NOT A TYPO

```
%
```

```
\LWR@tdstartstyles%
```

```
\LWR@addtabularrowcolor%
```

```
\LWR@addcmidrulewidth%
\LWR@addcdashline%
\LWR@addtabularhrulecolor%
\LWR@addmulticolvertrulecolor%
\LWR@addformatwpalignment{#5}%
\LWR@tdendstyles%
}% end of the opening table data tag
\global\boolfalse{LWR@intabularmetadata}%
\LWR@parsemulticolumnalignment{#5}{\LWR@printmccoldata}%
}
```

71.21.3 Multicolumn

`\LWR@htmlmulticolumn` {⟨*numcols*⟩} {⟨*alignment*⟩} {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@htmlmulticolumn}{m m +m}%
{%
```

Figure out how many extra HTML columns to add for `@` and `!` columns:

```
\LWR@tabularhtmlcolumns{\arabic{LWR@tableLaTeXcolindex}}{#1}
```

Create the multicolumn tag:

```
\LWR@domulticolumn{#1}{\arabic{LWR@tabhtmlcoltotal}}{#2}{#3}%
```

Move to the next LaTeX column:

```
\addtocounter{LWR@tableLaTeXcolindex}{#1}%
\addtocounter{LWR@tableLaTeXcolindex}{-1}%
```

Skip any trailing `@` or `!` columns for this cell:

```
\global\booltrue{LWR@skipatbang}%
}
```

71.21.4 Longtable captions

longtable captions use `\multicolumn`.

Bool `LWR@starredlongtable` Per the caption pacakge, step the counter if `longtable*`.

```
\newbool{LWR@starredlongtable}
\boolfalse{LWR@starredlongtable}
```

Per the caption package. User-redefinable float type.

```
\providecommand*{\LTcaptype}{table}
```

`\LWR@longtabledatacaptiontag` * [⟨*toc entry*⟩] {⟨*caption*⟩}

```
\NewDocumentCommand{\LWR@longtabledatacaptiontag}{s o +m}
{%
```

Remember the latest name for `\nameref`:

```
\IfValueTF{#2}{% optional given?
    \ifblank{#2}% optional empty?
    {\LWR@setlatestname{#3}}% empty
    {\LWR@setlatestname{#2}}% given and non-empty
}% optional given
{\LWR@setlatestname{#3}}% no optional
```

Create a multicolumn across all the columns:

Figure out how many extra HTML columns to add for `@` and `!` columns found between the first and the last column:

```
\LWR@tabularhtmlcolumns{1}{\arabic{LWR@tabletotalLaTeXcols}}
```

Create the multicolumn tag:

```
\LWR@domulticolumn{\arabic{LWR@tabletotalLaTeXcols}}%
    {\arabic{LWR@tabhtmlcoltotal}}%
    {P}%
{% \LWR@domulticolumn
\IfBooleanTF{#1}% star?
```

Star version, show a caption but do not make a LOT entry:

```
{% yes star
    \LWR@figcaption%
    \LWR@isolate{#3}%
    \endLWR@figcaption%
}%
{% No star:
```

Not the star version:

Don't step the counter if `\caption[]{A caption.}`

```
    \ifbool{LWR@starredlongtable}%
    {%
        \ifblank{#2}% TOC entry
        {}%
        {%
            \refstepcounter{\LTcaptype}%
            \protected@edef\@currentlabel{%
                \@nameuse{p@\LTcaptype}\@nameuse{the\LTcaptype}%
            }%
        }%
    }{}%
```

Create an HTML caption. Afterwards, maybe make a LOT entry.

```
    \LWR@figcaption%
    \LWR@isolate{\@nameuse{fnum@\LTcaptype}}%
    \CaptionSeparator%
    \LWR@isolate{#3}%
    \endLWR@figcaption%
```

See if an optional caption was given:

```
    \ifblank{#2}% TOC entry empty
```

if the optional caption was given, but empty, do not form a TOC entry

```
    {}%
```

If the optional caption was given, but might only be `[]`:

```
    {% TOC entry not empty
        \IfNoValueTF{#2}% No TOC entry?
```

The optional caption is `[]`:

```
        {% No TOC entry
            \addcontentsline%
            {\@nameuse{ext@\LTcaptype}}%
            {\LTcaptype}%
            {%
                \protect\numberline%
              {\LWR@isolate{\@nameuse{p@\LTcaptype}}\@nameuse{the\LTcaptype}}%
                {\ignorespaces \LWR@isolate{#3}\protect\relax}%
            }%
        }% end of No TOC entry
```

The optional caption has text enclosed:

```
        {% yes TOC entry
            \addcontentsline%
            {\@nameuse{ext@\LTcaptype}}%
            {\LTcaptype}%
```

```
            {%
                \protect\numberline%
              {\LWR@isolate{\@nameuse{p@\LTcaptype}}\@nameuse{the\LTcaptype}}%
                {\ignorespaces \LWR@isolate{#2}\protect\relax}%
            }%
        }% end of yes TOC entry
    }% end of TOC entry not empty
}% end of no star
```

Skip any trailing `@` or `!` columns for this cell:

```
\global\booltrue{LWR@skipatbang}%
}% end of \LWR@domulticolumn

\addtocounter{LWR@tableLaTeXcolindex}{\arabic{LWR@tabletotalLaTeXcols}}
\addtocounter{LWR@tableLaTeXcolindex}{-1}

}
```

71.21.5 Counting HTML tabular columns

The LaTeX specification for a table includes a number of columns separated by the `&` character. These columns differ in content from line to line. Additional virtual columns may be specified by the special `@` and `!` columns. These columns are identical from line to line, but may be skipped during a multicolumn cell.

For HTML output, `@` and `!` columns are placed into their own tabular columns. Thus, a LaTeX `\multicolumn` command may span several additional `@` and `!` columns in HTML output. These additional columns must be added to the total number of columns spanned by an HTML multi-column data cell.

```
\newcounter{LWR@tabhtmlcolindex}
\newcounter{LWR@tabhtmlcolend}
\newcounter{LWR@tabhtmlcoltotal}
```

`\LWR@subtabularhtmlcolumns` {⟨*index*⟩}

Factored from `\LWr@tabularhtmlcolumns`, which follows.

```
\newcommand*{\LWR@subtabularhtmlcolumns}[1]{%
```

Temporarily define a macro equal to the `@` specification for this column:

```
    \edef\LWR@atbangspec{\LWR@getexparray{LWR@colatspec}{#1}}%
```

If the `@` specification is not empty, add to the count:

```
    \ifdefempty{\LWR@atbangspec}%
        {}%
        {\addtocounter{LWR@tabhtmlcoltotal}{1}}%
```

Likewise for the ! columns:

```
    \edef\LWR@atbangspec{\LWR@getexparray{LWR@colbangspec}{#1}}%
    \ifdefempty{\LWR@atbangspec}%
        {}%
        {\addtocounter{LWR@tabhtmlcoltotal}{1}}%
}
```

\LWR@tabularhtmlcolumns {⟨*starting LaTeX column*⟩} {⟨*number LaTeX columns*⟩}

Compute the total number of HTML columns being spanned, considering the starting LaTeX table column and the number of LaTeX tabular columns being spanned. Any @ and ! columns within this span are included in the total count. The resulting number of HTML columns is returned in the counter LWR@tabhtmlcoltotal.

```
\newcommand*{\LWR@tabularhtmlcolumns}[2]{%
```

Count the starting index, compute ending index, and begin with the count being the LaTeX span, to which additional @ and ! columns may be added:

```
\setcounter{LWR@tabhtmlcolindex}{#1}%
\setcounter{LWR@tabhtmlcoltotal}{#2}%
\setcounter{LWR@tabhtmlcolend}{#1}%
\addtocounter{LWR@tabhtmlcolend}{#2}%
```

If at the left edge, add the at/bang columns for the left edge:

```
\ifnumcomp{\value{LWR@tabhtmlcolindex}}{=}{1}{%
    \LWR@subtabularhtmlcolumns{leftedge}%
}{}%
```

Walk across the LaTeX columns looking for @ and ! columns:

```
\whileboolexpr{%
    test {%
        \ifnumcomp{\value{LWR@tabhtmlcolindex}}{<}{\value{LWR@tabhtmlcolend}}%
    }%
}%
{%
    \LWR@subtabularhtmlcolumns{\arabic{LWR@tabhtmlcolindex}}%
    \addtocounter{LWR@tabhtmlcolindex}{1}%
}% whiledo
}
```

```
\end{warpHTML}
```

71.22 Multirow if not loaded

A default defintion in case multirow is not loaded. This is used during table parsing.

```
\begin{warpHTML}
```

```
\newcommand{\multirow}[2][c]{}
\end{warpHTML}
```

71.23 Multicolumnrow

A print-mode version is defined here, and is also used during HTML output while inside a `latexmage`.

See section 319 for the HTML versions.

for HTML & PRINT:

```
\begin{warpall}
```

`\multicolumnrow` {⟨*1:cols*⟩} {⟨*2:halign*⟩} [⟨*3:vpos*⟩] {⟨*4:numrows*⟩} [⟨*5:bigstruts*⟩] {⟨*6:width*⟩} [⟨*7:fixup*⟩] {⟨*8:text*⟩}

For discussion of the use of `\DeclareExpandableDocumentCommand`, see:
https://tex.stackexchange.com/questions/168434/problem-with-abbreviation-of-multirow-and-multicolumn-latex

`\AtBeginDocument` to adjust after the user may have loaded multirow, which requires several tests to determine which version is loaded and thus which options are available.

```
\AtBeginDocument{
```

`\@ifundefined{@xmultirow}` determines if multirow was never loaded.

Null action if not loaded:

```
\@ifundefined{@xmultirow}
{
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {}%
}% no version of multirow was loaded
{% \@xmultirow defined, so some version of multirow was loaded
```

`\@ifpackageloaded{multirow}` determines if v2.0 or later of multirow was used, which included the `\ProvidesPackage` macro.

The print version:

```
\@ifpackageloaded{multirow}{% v2.0 or newer
\@ifpackagelater{multirow}{2016/09/01}% 2016/09/27 for v2.0
{% v2.0+:
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {\multicolumn{#1}{#2}{\@xmultirow[#3]{#4}[#5]{#6}[#7]{#8}}}%
}
{% loaded but older, probably not executed:
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {\multicolumn{#1}{#2}{\@xmultirow{#4}[#5]{#6}[#7]{#8}}}%
```

```
}
}% packageloaded{multirow}
```

If not `\@ifpackageloaded{multirow}` but `\@xmultirow` is defined, then this must be v1.6 or earlier, which did not `\ProvidesPackage{multirow}`, and did not have the vposn option.

```
{% v1.6 or older did not \ProvidePackage
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {\multicolumn{#1}{#2}{\@xmultirow{#4}[#5]{#6}[#7]{#8}}}%
}

}% \@ifundefined{@xmultirow}

\providecommand*{\multicolumnrow}{\LWR@print@multicolumnrow}

}% AtBeginDocument

\end{warpall}
```

71.24 Utility macros inside a table

for HTML output:

```
\begin{warpHTML}
```

Used to prevent opening a tabular data cell if the following token is one which does not create tabular data:

```
\newcommand*{\LWR@donothing}{}
```

In case array is not loaded:

```
\let\firsthline\relax
\let\lasthline\relax
\newcommand*{\firsthline}{}
\newcommand*{\lasthline}{}
```

In case bigdelim is not loaded:

```
\newcommand*{\ldelim}{}
\newcommand*{\rdelim}{}

\end{warpHTML}
```

71.25 Special-case tabular markers

for HTML & PRINT:

```
\begin{warpall}
```

\TabularMacro Place this just before inserting a custom macro in a table data cell. Doing so tells lwarp not to automatcally start a new HTML table data cell yet. See section 9.10.

```
\newcommand*{\TabularMacro}{}
```

```
\end{warpall}
```

\ResumeTabular Used to resume tabular entries after resuming an environment.

⚠ tabular inside another environment When creating a new environment which contains a tabular environment, lwarp's emulation of the tabular does not automatically resume when the containing enviroment ends, resulting in corrupted HTML rows. To fix this, use \ResumeTabular as follows. This is ignored in print mode.

```
\StartDefiningTabulars % because & is used in a definition
\newenvironment{outerenvironment}
{
\tabular{cc}
left & right \\
}
{
\TabularMacro\ResumeTabular
left & right \\
\endtabular
}
\StopDefiningTabulars
```

for HTML output:

```
\begin{warpHTML}
```

```
\newcommand*{\ResumeTabular}{%
\global\boolfalse{LWR@exitingtabular}%
\global\boolfalse{LWR@tabularmutemods}%
\LWR@getmynexttoken%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

```
\newcommand*{\ResumeTabular}{}
```

```
\end{warpprint}
```

71.26 Checking for a new table cell

for HTML output:

```
\begin{warpHTML}
```

Bool LWR@exitingtabular When \end is found, turns off the next opening data tag.

```
\newbool{LWR@exitingtabular}
```

Bool LWR@tabularmutemods Mutes HTML output for @, !, < and >.

This is used while printing the final row to generate \bottomrules.

```
\newbool{LWR@tabularmutemods}
```

\LWR@tabledatacolumntag Open a new HTML table cell unless the next token is for a macro which does not create data, such as \hline, \toprule, etc:

```
\newcommand*{\LWR@tabledatacolumntag}%
{%
\LWR@traceinfo{LWR@tabledatacolumntag}%
```

\show\LWR@mynexttoken to see what tokens to look for

If not any of the below, start a new table cell:

```
\global\let\LWR@mynextaction\LWR@tabledatasinglecolumntag%
```

If exiting the tabular:

```
\ifdefequal{\LWR@mynexttoken}{\end}%
    {\global\booltrue{LWR@exitingtabular}}{}%
```

longtable can have a caption in a cell

```
\ifdefequal{\LWR@mynexttoken}{\caption}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

Look for other things which would not start a table cell:

```
\ifdefequal{\LWR@mynexttoken}{\multicolumn}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
\ifdefequal{\LWR@mynexttoken}{\multirow}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
\ifdefequal{\LWR@mynexttoken}{\multicolumnrow}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
\ifdefequal{\LWR@mynexttoken}{\noalign}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

If an \mrowcell, this is a cell to be skipped over:

```
\ifdefequal{\LWR@mynexttoken}{\mrowcell}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

If an \mcolrowcell, this is a cell to be skipped over:

```
\ifdefequal{\LWR@mynexttoken}{\mcolrowcell}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\TabularMacro}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

```
\ifdefequal{\LWR@mynexttoken}{\hline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\firsthline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\lasthline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\toprule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\midrule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\cmidrule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%


\ifdefequal{\LWR@mynexttoken}{\morecmidrules}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\specialrule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\cline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\bottomrule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\rowcolor}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\arrayrulecolor}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\doublerulesepcolor}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\warpprintonly}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\warpHTMLonly}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\ldelim}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\rdelim}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

For arydshln:

```
\ifdefequal{\LWR@mynexttoken}{\hdashline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\cdashline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\firsthdashline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\lasthdashline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

Ignore an empty line between rows:

```
\ifdefequal{\LWR@mynexttoken}{\par}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

No action for an \end token.

Add similar to the above for any other non-data tokens which might appear in the table.

Start the new table cell if was not any of the above:

```
\LWR@traceinfo{LWR@tabledatacolumntag: about to do mynext}%
\LWR@mynextaction%
\LWR@traceinfo{LWR@tabledatacolumntag: done}%
}
```

```
\end{warpHTML}
```

71.27 \mrowcell

for HTML & PRINT:

```
\begin{warpall}
```

\mrowcell

⚠ multirow cells

The user must insert \mrowcell into any \multirow cells which must be skipped. This command has no action during print output.

```
\newcommand*{\mrowcell}{}
```

```
\end{warpall}
```

71.28 \mcolrowcell

for HTML & PRINT:

```
\begin{warpall}
```

\mcolrowcell ⚠ multirow cells The user must insert \mcolrowcell into any \multicolumnrow cells which must be skipped. This command has no action during print output.

```
\newcommand*{\mcolrowcell}{}
```

```
\end{warpall}
```

71.29 HTML tabular environment

for HTML output:

```
\begin{warpHTML}
```

These are default defininitions in case booktabs is not loaded, and are not expected to used, but must exist as placeholders. They are pre-deleted in case memoir has already loaded booktabs.

```
\LetLtxMacro\toprule\relax
\LetLtxMacro\midrule\relax
\LetLtxMacro\cmidrule\cline
\LetLtxMacro\bottomrule\relax
\LetLtxMacro\addlinespace\relax
\LetLtxMacro\morecmidrules\relax
\LetLtxMacro\specialrule\relax

\newcommand*{\toprule}[1][]{\hline}
\newcommand*{\midrule}[1][]{\hline}
\LetLtxMacro\cmidrule\cline
\newcommand*{\bottomrule}[1][]{\hline}
\newcommand*{\addlinespace}[1][]{}
\newcommand*{\morecmidrules}{}
\newcommand*{\specialrule}[3]{\hline}
```

\noalign {⟨*text*⟩} Redefined for use inside tabular.

```
\LetLtxMacro\LWR@orignoalign\noalign

\newcommand{\LWR@tabularnoalign}[1]{%
\begingroup%
\global\advance\rownum\m@ne%
\renewcommand*{\LWR@xcolorrowHTMLcolor}{}%
\multicolumn{\value{LWR@tabletotalLaTeXcols}}{l}{#1} \\
\endgroup%
% \@rowc@lors%
\LWR@getmynexttoken%
}
```

\LWR@HTMLhline The definition of \hline depends on whether tabls has been loaded. If so, optional space below the line may be specified, but will be ignored.

```
\AtBeginDocument{
\@ifpackageloaded{lwarp-tabls}
```

```
{
\newcommand*{\LWR@HTMLhline}[1][]{%
    \ifbool{FormatWP}%
    {\LWR@docmidrule{1-\arabic{LWR@tabletotalLaTeXcols}}}%
    {\addtocounter{LWR@hlines}{1}}%
    \LWR@getmynexttoken}%
}
{
\newcommand*{\LWR@HTMLhline}{%
    \ifbool{FormatWP}%
    {\LWR@docmidrule{1-\arabic{LWR@tabletotalLaTeXcols}}}%
    {\addtocounter{LWR@hlines}{1}}%
    \LWR@getmynexttoken}%
}
}% AtBeginDocument
```

`\LWR@HTMLcline` {⟨*columns*⟩}

```
\NewDocumentCommand{\LWR@HTMLcline}{m}%
{\LWR@docmidrule{#1}\LWR@getmynexttoken}%
```

`\LWR@tabular@warpprintonly` {⟨*contents*⟩}

Only process the contents if producing printed output. Modified inside a `tabular` to grab the next token.

```
\newcommand{\LWR@tabular@warpprintonly}[1]{%
    \ifbool{warpingprint}{#1}{}%
    \LWR@getmynexttoken%
}
```

`\LWR@nullifyNoAutoSpacing` For babel-french, turn off auto spacing at the start of the tabular, then nullify the autospacing commands inside the tabular, since they were not compatible with the tabular column parsing code, which uses xstring.

```
\AtBeginDocument{
\@ifundefined{frenchbsetup}%
{% no babel-french
    \newcommand*{\LWR@nullifyNoAutoSpacing}{}
}% no babel-french
{% yes babel-french
    \newcommand*{\LWR@nullifyNoAutoSpacing}{%
        \NoAutoSpacing%
        \renewcommand*{\NoAutoSpacing}{}%
        \renewcommand*{\LWR@FBcancel}{}%
    }
}% yes babel-french
}% AtBeginDocument
```

Env `tabular` `<direction>` [⟨*vertposition*⟩] {⟨*colspecs*⟩}

The `<direction>` is from plext for Japanese documents, and is ignored.

```
\StartDefiningTabulars

\NewDocumentCommand{\LWR@HTML@@tabular}{d<> o m}
{%
\LWR@traceinfo{LWR@HTML@@tabular started}%
\addtocounter{LWR@tabulardepth}{1}%
```

Not yet started a table row:

```
\global\boolfalse{LWR@startedrow}%
```

Not yet doing any rules:

```
\setcounter{LWR@hlines}{0}%
\setcounter{LWR@hdashedlines}{0}%
\global\boolfalse{LWR@doingtbrule}%
\global\boolfalse{LWR@doingcmidrule}%
```

For babel-french, turn off auto spacing one time, then nullify the autospacing commands since were not compatible with the tabular parsing code.

```
\LWR@nullifyNoAutoSpacing%
```

Have not yet found the end of tabular command. Unmute the `@` and `!` columns.

```
\global\boolfalse{LWR@exitingtabular}%
\global\boolfalse{LWR@tabularmutemods}%
```

Create the `table` tag:

```
\global\booltrue{LWR@intabularmetadata}%
\LWR@traceinfo{LWR@@tabular: About to LWR@forecenewpage.}%
\LWR@forcenewpage
\LWR@htmlblocktag{table}%
```

Parse the table columns:

```
\LWR@parsetablecols{#3}%
```

Table col spec is: `\LWR@tablecolspec` which is a string of `llccrr`, etc.

Do not place the table inside a paragraph:

```
\LWR@stoppars%
```

Track column #:

```
\setcounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
\global\boolfalse{LWR@tabularcelladded}%
```

Start looking for midrules:

```
\LWR@clearmidrules%
```

\\ becomes a macro to end the table row:

```
\LetLtxMacro{\\}{\LWR@tabularendofline}%
```

\warpprintonly inside a tabular must grab the next token.

```
\LetLtxMacro\warpprintonly\LWR@tabular@warpprintonly%
```

The following adjust for colortbl.

```
\LetLtxMacro\arrayrulecolor\arrayrulecolornexttoken%
\LetLtxMacro\doublerulesepcolor\doublerulesepcolornexttoken%
\gdef\LWR@columnHTMLcolor{}%
\gdef\LWR@rowHTMLcolor{}%
\gdef\LWR@cellHTMLcolor{}%
\@rowcolors%
```

The vertical rules are set to the color active at the start of the tabular. \arrayrulecolor will then affect horizontal rules inside the tabular, but not the vertical rules.

```
\ifdefvoid{\LWR@ruleHTMLcolor}%
    {\edef\LWR@vertruleHTMLcolor{black}}%
    {\edef\LWR@vertruleHTMLcolor{\LWR@origpound\LWR@ruleHTMLcolor}}%
```

Tracking the depth of cell color s:

```
\setcounter{LWR@cellcolordepth}{0}%
```

The following may appear before a data cell is created, so after doing their actions, we look ahead with \LWR@getmynextoken to see if the next token might create a new data cell:

The optional parameter for \hline supports the tabls package.

```
\LWR@traceinfo{LWR@@HTML@tabular: redefining macros}%
\LetLtxMacro\noalign\LWR@tabularnoalign%
\LetLtxMacro\hline\LWR@HTMLhline%
\LetLtxMacro\cline\LWR@HTMLcline%

\DeclareDocumentCommand{\hdashline}{o}{%
    \ifbool{FormatWP}%
        {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {\addtocounter{LWR@hdashedlines}{1}}%
    \LWR@getmynexttoken%
}%

\DeclareDocumentCommand{\cdashline}{m}{%
    \LWR@docdashline{##1}\LWR@getmynexttoken%
}%
```

```
\DeclareDocumentCommand{\firsthdashline}{o}{%
    \ifbool{FormatWP}%
        {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {\addtocounter{LWR@hdashedlines}{1}}%
    \LWR@getmynexttoken%
}%

\DeclareDocumentCommand{\lasthdashline}{o}{%
    \ifbool{FormatWP}%
        {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {\addtocounter{LWR@hdashedlines}{1}}%
    \LWR@getmynexttoken%
}%
```

The following create data cells and will have no more data in this cell, so we do not want to look ahead for a possible data cell, so do not want to use `\LWR@getmynexttoken`.

```
\renewcommand{\multicolumn}{\LWR@htmlmulticolumn}%
\renewcommand*{\mrowcell}{%
    \LWR@maybenewtablerow%
    \LWR@tabularleftedge%
    \global\booltrue{LWR@skippingmrowcell}%
}%
\renewcommand*{\mcolrowcell}{%
    \LWR@maybenewtablerow%
    \global\booltrue{LWR@skippingmcolrowcell}%
}%
\LetLtxMacro\caption\LWR@longtabledatacaptiontag%
```

Reset for new processing:

```
\global\boolfalse{LWR@tableparcell}%
\global\boolfalse{LWR@skippingmrowcell}%
\global\boolfalse{LWR@skippingmcolrowcell}%
\global\boolfalse{LWR@skipatbang}%
\global\boolfalse{LWR@emptyatbang}%
```

Set `&` for its special meaning inside the tabular:

```
\StartDefiningTabulars%
\protected\gdef&{\LWR@tabularampersand}%
```

Locally force any minipages to be fullwidth, until the end of the `tabular`:

```
\booltrue{LWR@forceminipagefullwidth}
```

Nest one level deeper of tabular paragraph handling:

```
\addtocounter{LWR@tabularpardepth}{1}%
```

Look ahead for a possible table data cell:

```
\LWR@traceinfo{LWR@@HTML@tabular: about to LWR@getmynexttoken}%
```

```
\LWR@getmynexttoken%
}%
```

Ending the environment:

```
\newcommand*{\LWR@HTML@endtabular}
{%
\LWR@traceinfo{LWR@HTML@endtabular}%
```

Unnest one level of tabular paragraph handling:

```
\addtocounter{LWR@tabularpardepth}{-1}%
\ifboolexpr{%
    test {%
      \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}
    } or %
    (%
        bool{LWR@intabularmetadata} and%
        not bool{LWR@tabularcelladded} and%
        test {%
        \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{\value{LWR@tabletotalLaTeXcols}}%
        }%
    )%
}%
{%
    \LWR@tabularfinishrow%
}%
{%
    \LWR@closetabledatacell%
}%
\LWR@htmlblocktag{/tr}%
```

xcolor row color support:

```
\@rowc@lors%
```

```
\LWR@htmlblocktag{/table}%
\global\boolfalse{LWR@intabularmetadata}%
```

Unnest one level of tabular:

```
\addtocounter{LWR@tabulardepth}{-1}%
```

Restore & to its usual meaning:

```
\protected\gdef&{\LWR@origampmacro}%
\StopDefiningTabulars%
\LWR@traceinfo{LWR@HTML@endtabular finished}%
}

\csletcs{LWR@HTML@endtabular*}{LWR@HTML@endtabular}

\StopDefiningTabulars
```

siunitx may redefine `tabular`, so set the following later:

```
\AtBeginDocument{
    \LetLtxMacro\LWR@origendtabular\endtabular
    \csletcs{LWR@origendtabular*}{endtabular*}
    \LWR@formatted{@tabular}
    \LWR@formatted{endtabular}
    \LWR@formatted{endtabular*}
}
```

```
\end{warpHTML}
```

72 Cross-references

Sectioning commands have been emulated from scratch, so the cross-referencing commands are custom-written for them. Emulating both avoids several layers of patches.

File `*_html.aux` A new entry in `*_html.aux` is used to remember section name, file, and lateximage depth and number for each label:

```
\newlabel{<labelname>@lwarp}{{<section name>}{<filename>}
                                    {<limagedepth>}{<limagenumber>}}
```

Table 12 shows the data structures related to cross-referencing.

for HTML output:

```
\begin{warpHTML}
```

72.1 Setup

`\@currentlabelname` To remember the most recently defined section name, description, or caption, for `\nameref`.

```
\providecommand*{\@currentlabelname}{}
```

`\LWR@stripperiod` {⟨*text*⟩} [⟨.⟩]

Removes a trailing period.

```
\def\LWR@stripperiod#1.\ltx@empty#2\@nil{#1}%
```

`\LWR@setlatestname` {⟨*object name*⟩}

Removes `\label`, strips any final period, and remembers the result.

```
\newcommand*{\LWR@setlatestname}[1]{%
```

Table 12: Cross-referencing data structures

Original LaTeX: (print and HTML)

\refstepcounter: Steps the couunter and sets \@currentlabel.

\@currentlabel: \p@<ctr>\the<ctr> Updated by \refstepcounter.

\label: Writes to the .aux file:
\newlabel{<label>}{{\@currentlabel}{\thepage}}

\newlabel: When the .aux file is read, sets \r@<label>.

\r@<label>: Set to: {{\@currentlabel}{\thepage}}

\ref: Returns the first part of \r@<label>.

\pageref: Returns the second part of \r@<label>.

Added by lwarp: (HTML only)

\label: Adds HTML tags (section 72.3), and another .aux entry (section 72.2).

\newlabel: Unchanged. When the .aux file is read, sets \r@<label>@lwarp.

\r@<label>@lwarp: Set to {{section_name}{file_name}{depth}{number}}:

\LWR@nameref: The section name for this label.

\LWR@htmlfileref: The filenumber or name for this label.

\LWR@lateximagedepthref: The lateximagedepth for this label.

\LWR@lateximagenumberref: The lateximagenumber for this label.

\nameref: Emualted from hyperref for lwarp. See section 72.4.

\ref and \nameref: Adds HTML tags. See section 72.4.

Added by amsmath: (print and HTML)

\label: Execution is delayed until the math environment is completed.

\ltx@label: LaTeX \label, (HTML: patched by lwarp,) later patched by cleveref.

Added by cleveref: (print and HTML)

\refstepcounter: Added: sets \cref@currentlabel.

\cref@currentlabel: (<type>=<ctr> unless an alias is used):
[<type>][\arabic{<ctr>}][<parent ctrs>]{\p@<ctr>\the<ctr>} Also see section 58.4 for use with footnotes.

\label: Writes to the .aux file:
\newlabel{<label>@cref}{{\cref@currentlabel}{\thepage}}

\newlabel: Unchanged. When the .aux file is read, sets \r@<label>@cref.

\r@<label>@cref: Set to: {{\cref@currentlabel}{\thepage}}

Utility functions: See \cref@getlabel, \cref@gettype, \cref@getcounter, \cref@getprefix.

Cross-referencing names: \crefname and \Crefname assign human-readable names for references to this counter type.

Additionally patched by lwarp: (HTML only)

\cref, etc.: Modified for lwarp. See section 86.

\label inside math: See section 78.7.1.

Footnotes: See \noteentry in section 58.4.

Remove `\label` and other commands from the name, the strip any final period. See gettitlestring.

```
\GetTitleStringExpand{#1}%
\edef\@currentlabelname{\detokenize\expandafter{\GetTitleStringResult}}%
\edef\@currentlabelname{%
    \expandafter\LWR@stripperiod\@currentlabelname%
    \ltx@empty.\ltx@empty\@nil%
}%
}
```

72.2 New lwarp labels.

File *_html.aux A new entry in *_html.aux is used to remember section name, file, and latexmage depth and number for each label:

```
\newlabel{<labelname>@lwarp}{{<section name>}{<filename>}
                                    {<limagedepth>}{<limagenumber>}}
```

See:
http://tex.stackexchange.com/questions/57194/extract-section-number-from-equation-reference

\LWR@setref {⟨*args list*⟩} {⟨*selector*⟩} {⟨*label*⟩}

\@setref without the \null (\hbox), and without the warning messages. Each caused problems with lwarp references. The regular reference will cause the warning.

```
\def\LWR@setref#1#2#3{%
  \ifx#1\relax%
    ??%
  \else%
   \expandafter#2#1%
  \fi}
```

\LWR@nameref {⟨*label*⟩} Returns the section name for this label:

```
\newcommand*{\LWR@nameref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@firstoffour{#1}%
}
```

\LWR@htmlfileref {⟨*label*⟩} Returns the file number or name for this label:

```
\newcommand*{\LWR@htmlfileref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@secondoffour{#1}%
}
```

\LWR@lateximagedepthref {⟨*label*⟩} Returns the lateximagedepth for this label:

```
\newcommand*{\LWR@lateximagedepthref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@thirdoffour{#1}%
}
```

`\LWR@lateximagenumberref` {⟨*label*⟩} Returns the `lateximagenumber` for this label:

```
\newcommand*{\LWR@lateximagenumberref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@fourthoffour{#1}%
}
```

`\LWR@lwarplabel` {⟨*label*⟩} Sanitize the name and then creates the label:

```
\newcommand*{\LWR@lwarplabel}[1]{%
\LWR@traceinfo{LWR@lwarplabel !#1!}%
\LWR@setlatestname{\@currentlabelname}%
    \@bsphack%
    \protected@write\@auxout{}%
        {\string\newlabel{#1@lwarp}{%
            {\@currentlabelname}%
        {\ifbool{FileSectionNames}{\LWR@thisfilename}{\arabic{LWR@htmlfilenumber}}}%
            {\arabic{LWR@lateximagedepth}}%
            {\arabic{LWR@lateximagenumber}}%
        }}%
    \@esphack%
}
```

72.3 Labels

`\LWR@sublabel` {⟨*label*⟩} Creates an HTML id tag.

`\detokenize` is used to allow underscores in the labels.

```
\newcommand*{\LWR@sublabel}[1]{%
\LWR@traceinfo{LWR@sublabel !#1!}%
```

Create an HTML id tag unless are inside a lateximage, since it would appear in the image:

```
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{}%
{% not lateximage
```

If not doing a lateximage, create an HTML ID tag: (To be factored…)

```
    \LWR@sanitize{#1}%
    \ifbool{LWR@doingstartpars}%
    {% pars allowed
        \ifbool{LWR@doingapar}%
        {% par started
         \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}\LWR@htmltag{/a}%
```

```
        }% par started
        {% par not started
            \LWR@stoppars%
         \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}\LWR@htmltag{/a}%
            \LWR@startpars%
        }% par not started
    }% pars allowed
    {% pars not allowed
        \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}\LWR@htmltag{/a}%
    }% pars not allowed
}% not lateximage
}
```

`\LWR@new@label` `(`⟨*bookmark*⟩`)` `{`⟨*label*⟩`}` `[`⟨*type*⟩`]`

`\label` during HTML output when not in SVG math mode, removing extra spaces around the label, as done by a regular LaTeX `\label`.

The is also used during a `lateximage`, including SVG math, since the special label handling is required, but `\LWR@sublabel` does not generate HTML tags inside a `lateximage`.

clevereref later encases this to add its own cross-referencing.

The optional ⟨*bookmark*⟩ is per the memoir class, and is ignored.

The optional ⟨*type*⟩ is per the ntheorem package, and is ignored.

```
\NewDocumentCommand{\LWR@new@label}{d() m o}{%
\LWR@traceinfo{LWR@new@label: starting}%
\LWR@traceinfo{LWR@new@label: !#2!}%
% \@bsphack%
```

Create a traditional LaTeX label, as modified by cleveref:

```
\LWR@orig@label{#2}%
```

Create a special label which holds the section number, `LWR@htmlfilenumber`, `LWR@lateximagedepth`, and `LWR@lateximagenumber`:

```
\LWR@traceinfo{LWR@new@label: filesectionnames is \ifbool{FileSectionNames}{true}{false}}%
\LWR@traceinfo{LWR@new@label: LWR@thisfilename is !\LWR@thisfilename!}%
\LWR@traceinfo{LWR@new@label: LWR@htmlfilenumber is \arabic{LWR@htmlfilenumber}}%
\LWR@lwarplabel{#2}%
\LWR@sublabel{#2}%
% \@esphack%
\LWR@traceinfo{LWR@new@label: done}%
}
```

72.4 References

`\LWR@startref` `{`⟨*label*⟩`}` (Common code for `\ref` and `\nameref`.)

Open an HTML tag reference to a filename, # character, and a label.

```
\newcommand*{\LWR@startref}[1]
{%
\LWR@sanitize{#1}%
\LWR@traceinfo{LWR@startref A: !#1!}%
```

Create the filename part of the link:

```
\LWR@htmltag{a href="%
\LWR@traceinfo{LWR@startref B}%
\LWR@print@mbox{\LWR@htmlrefsectionfilename{#1}}%
\LWR@traceinfo{LWR@startref C}%
\LWR@origpound%
```

Create the destination id:

See if `LWR@lateximagedepth` is unknown:

```
\LWR@traceinfo{LWR@startref D: !#1!}%
\ifcsundef{r@#1@lwarp}%
```

"??" if `LWR@lateximagedepth` is unknown, so create a link with an unknown destination:

```
{%
    \LWR@traceinfo{LWR@startref D0: ??}%
    ??%
}%
```

If `LWR@lateximagedepth` is known. Use a lateximage if the depth is greater than zero, or a regular link otherwise:

```
{%
    \ifthenelse{\cnttest{\LWR@lateximagedepthref{#1}}{>}{0}}%
        {%
            \LWR@ImagesName\LWR@lateximagenumberref{#1}%
        }%
        {%
            \LWR@traceinfo{LWR@startref D3}%
```

`\detokenize` is used to allow underscores in the labels:

```
            \LWR@print@mbox{\LWR@sanitized}%
        }%
}%
\LWR@traceinfo{LWR@startref E}%
```

Closing quote:

```
"}%
\LWR@traceinfo{LWR@startref F}%
}
```

\LWR@subnewref {⟨*label*⟩} {⟨*label or sub@label*⟩}

Factored for the subfig package. Uses the original label for the hyper-reference, but prints its own text, such as "1(b)".

```
\NewDocumentCommand{\LWR@subnewref}{m m}{%
\LWR@traceinfo{LWR@subnewref #1 #2}%
\LWR@startref{#1}%
\LWR@print@ref{#2}%
\LWR@htmltag{/a}%
}
```

\ref * {⟨*label*⟩} \ref is redefined to \LWR@HTML@ref, except inside the text part of a \hyperref, where it is redefined to \LWR@ref@ignorestar.

\LWR@HTML@ref * {⟨*label*⟩} Create an internal document reference link, or without a link if starred per hyperref.

```
\NewDocumentCommand{\LWR@HTML@ref}{s m}{%
\LWR@traceinfo{LWR@HTML@ref !#2!}%
\IfBooleanTF{#1}%
{\LWR@print@ref{#2}}%
{\LWR@subnewref{#2}{#2}}%
}

\LWR@formatted{ref}
```

\LWR@ref@ignorestar * {⟨*label*⟩} For use inside \hyperref. Ignores the star, then uses the original \ref.

```
\NewDocumentCommand{\LWR@ref@ignorestar}{s m}{%
    \LWR@print@ref{#2}%
}
```

\pagerefPageFor Text for page references.

```
\newcommand*{\pagerefPageFor}{see }
```

\pageref * {⟨*label*⟩} Create an internal document reference, or just the unlinked number if starred, per hyperref.

```
\NewDocumentCommand{\LWR@new@pageref}{s m}{%
\IfBooleanTF{#1}%
{(\pagerefPageFor\LWR@print@ref{#2})}%
{(\cpageref{#2})}%
}
```

\nameref {⟨*label*⟩}

```
\newrobustcmd*{\nameref}[1]{%
```

```
\LWR@traceinfo{nameref}%
\LWR@startref{#1}%
\LWR@traceinfo{nameref B}%
\LWR@nameref{#1}%
\LWR@traceinfo{nameref C}%
\LWR@htmltag{/a}%
\LWR@traceinfo{nameref: done}%
}
```

`\Nameref` {⟨*label*⟩} In print, adds the page number. In HTML, does not.

```
\LetLtxMacro\Nameref\nameref
```

72.5 Hyper-references

⚠ Note that the code currently only sanitizes the underscore character. Additional characters should be rendered inert as well. See the `hyperref.sty` definition of `\gdef\hyper@normalise` for an example.

`Pkg` `hyperref`

⚠ Do not tell other packages that hyperref is emulated. Some packages patch various commands if hyperref is present, which will probably break something, and the emulation already handles whatever may be emulated anyhow.

```
% DO NOT TELL OTHER PACKAGES TO ASSUME HYPERREF, lest they attempt to patch it:
% \EmulatesPackage{hyperref}[2015/08/01]% Disabled.  Do not do this.
```

Emulates hyperref:

`\@currentHref` Added to support backref.

```
\AtBeginDocument{
\def\@currentHref{%
autopage-\theLWR@currentautosec%
}
}
```

`\LWR@subhyperref` {⟨*URL*⟩}

Starts a link for `\LWR@hrefb`. A group must have been opened first, with nullified catcodes. The text name is printed afterwards, after the group is closed and catcodes restored.

```
\NewDocumentCommand{\LWR@subhyperref}{m}{%
\LWR@traceinfo{LWR@subhyperref !#1!}%
\LWR@sanitize{#1}%
\LWR@htmltag{%
    a href="\LWR@sanitized" % space
    target="\_{}blank" % space
```

```
}%
}
```

`\LWR@subhyperreftext` {⟨*text*⟩}

Finishes the hyperref for `\LWR@hrefb`. Catcodes must have been restored already. To be used after `\LWR@subhyperref`, and after its group has been closed.

```
\newcommand{\LWR@subhyperreftext}[1]{%
#1%
\LWR@htmltag{/a}%
\LWR@ensuredoingapar%
}
```

`\LWR@subhyperrefclass` {⟨*URL*⟩} {⟨*text*⟩} {⟨*htmlclass*⟩}

```
\NewDocumentCommand{\LWR@subhyperrefclass}{m +m m}{%
\LWR@htmltag{%
    a % space
    href="\begingroup\@sanitize#1\endgroup" % space
    class="#3" % space
}\LWR@orignewline%
#2\LWR@orignewline%
\LWR@htmltag{/a}%
\LWR@ensuredoingapar%
}
```

`\href` [⟨*options*⟩] {⟨*URL*⟩}

Create a link with accompanying text:

```
\DeclareDocumentCommand{\LWR@hrefb}{O{} m}{%
\LWR@ensuredoingapar%
\LWR@subhyperref{#2}%
\endgroup% restore catcodes
\LWR@subhyperreftext%
}

\newrobustcmd*{\href}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hrefb%
}
```

`\nolinkurl` {⟨*URL*⟩}

Print the name of the link without creating the link:

```
\newcommand*{\LWR@nolinkurlb}[1]{%
\LWR@ensuredoingapar%
\def\LWR@templink{#1}%
\@onelevel@sanitize\LWR@templink%
\LWR@templink%
\endgroup%
}

\newrobustcmd*{\nolinkurl}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@nolinkurlb%
}
```

`\url` {⟨*URL*⟩}

Create a link whose text name is the address of the link.

The url package may redefine `\url`, so it is `\let` to `\LWR@urla`here and also redefined by lwarp-url.

```
\DeclareDocumentCommand{\LWR@urlb}{m}{%
\LWR@ensuredoingapar%
\def\LWR@templink{#1}%
\@onelevel@sanitize\LWR@templink%
\href{\LWR@templink}{\LWR@templink}%
\endgroup%
}

\newrobustcmd*{\url}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@urlb%
}
```

`\LWR@subinlineimage` [⟨*alttag*⟩] {⟨*class*⟩} {⟨*filename*⟩} {⟨*extension*⟩} {⟨*style*⟩}

```
\newcommand*{\LWR@subinlineimage}[5][]{%
\ifblank{#1}%
{%
    \LWR@htmltag{img \LWR@indentHTML
        src="#3.#4" \LWR@indentHTML
        alt="#3" \LWR@indentHTML
        style="#5" \LWR@indentHTML
        class="#2" \LWR@orignewline
    }%
```

```
}%
{%
    \LWR@htmltag{img \LWR@indentHTML
        src="#3.#4" \LWR@indentHTML
        alt="#1" \LWR@indentHTML
        style="#5" \LWR@indentHTML
        class="#2" \LWR@orignewline
    }%
}%
}

\end{warpHTML}
```

Table 13: Float data structures

For each <type> of float (figure, table, etc.) there exists the following:

counter <type>: A counter called <type>, such as figure, table.

\<type>name: Name. \figurename prints "Figure", etc.

\ext@<type>: File extension. \ext@figure prints "lof", etc.

\fps@<type>: Placement.

\the<type>: Number. \thetable prints the number of the table, etc.

\p@<type>: Parent's number. Prints the number of the [within] figure, etc.

\fnum@<type>: Prints the figure number for the caption.
\<type>name \the<type>, "Figure 123".

\<type>: Starts the float environment. \figure or \begin{figure}

\end<type>: Ends the float environment. \endfigure or \end{figure}

\tf@<ext>: The LaTeX file identifier for the output file.

LWR@have<type>: A boolean remembering whether a \listof was requested for a float of this type.

File with extension lo<f,t,a-z>: An output file containing the commands to build the \listof<type> "table-of-contents" structure.

Cross-referencing names: For cleveref's \cref and related, \crefname and \Crefname assign human-readable names for references to this float type.

73 Floats

Floats are supported, although partially through emulation.

Table 13 shows the data structure associated with each <type> of float.

\@makecaption is redefined to print the float number and caption text, separated by \CaptionSeparator, which works with the babel package to adjust the caption separator according to the language. French, for example, uses an en-dash instead of a colon: "Figure 123 – Caption text".

73.1 Float environment

for HTML output: 8735 \begin{warpHTML}

\LWR@floatbegin {⟨*type*⟩} [⟨*placement*⟩] Begins a \newfloat environment.

```
\NewDocumentCommand{\LWR@floatbegin}{m o}{%
\ifbool{FormatWP}{\newline}{}%
\LWR@stoppars
```

There is a new float, so increment the unique float counter:

```
\addtocounter{LWR@thisautoid}{1}%
\booltrue{LWR@freezethisautoid}%

\begingroup%
```

Settings while inside the environment:

```
\LWR@print@raggedright%
```

Open an HTML `figure` tag. The figure is assigned a `class` equal to its type, and another class according to the float package style, if used. Note that `\csuse` returns an empty string if `\LWR@floatstyle@<type>` is not defined.

```
\LWR@htmltag{%
    figure id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}" % space
    class="#1 \@nameuse{LWR@floatstyle@#1}"%
}%
\ifbool{FormatWP}{%
    \LWR@orignewline%
    \LWR@BlockClassWP{}{}{wp#1}%
}{}%
```

Update the caption type:

```
\renewcommand*{\@captype}{#1}%
\caption@settype{#1}%
```

Mark the float for a word processor conversion:

```
\LWR@startpars%
\ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%

=== begin #1 ===

}{}%
```

Look for `\centering`, etc:

```
\LWR@futurenonspacelet\LWR@mynexttoken\LWR@floatalignment%
}
```

For koma-script. The following does not work for tables.

```
\AtBeginDocument{
\@ifpackageloaded{tocbasic}{
\appto\figure@atbegin{%
```

```
\LWR@futurenonspacelet\LWR@mynexttoken\LWR@floatalignment%
}
}{}
}
```

\@float
\@dlbfloat

Support packages which create floats directly.

```
\let\@float\LWR@floatbegin
\let\@dblfloat\LWR@floatbegin
```

\LWR@floatend

Ends a \newfloat environment.

```
\newcommand*{\LWR@floatend}{%
```

If saw a \centering, finish the center environment:

```
\LWR@endfloatalignment%
```

Mark the float end for a word processor conversion:

```
\ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%

=== end ===

}{}%
\LWR@stoppars%
```

Close an HTML figure tag:

```
\ifbool{FormatWP}{\endLWR@BlockClassWP}{}%
\LWR@htmlelementend{figure}%
\endgroup%
\boolfalse{LWR@freezethisautoid}%
\LWR@startpars%
\ifbool{FormatWP}{\newline}{}%
}
```

\end@float
\end@dlbfloat

Support packages which create floats directly.

```
\let\end@float\LWR@floatend
\let\end@dblfloat\LWR@floatend
```

73.2 Float tracking

Ctr LWR@thisautoid

A sequential counter for all floats and theorems. This is used to identify the float or theorem then reference it from the List of Figures and List of Tables.

```
\newcounter{LWR@thisautoid}
```

Ctr `LWR@thisautoidWP` A sequential counter for all word processor conversion s. This is used to convince LibreOffice to form a frame around this element.

```
\newcounter{LWR@thisautoidWP}
```

Bool `LWR@freezethisautoid` Prevents multiple increments of `\LWR@thisautoid` inside a float.

```
\newbool{LWR@freezethisautoid}
\boolfalse{LWR@freezethisautoid}
```

`\LWR@newautoidanchor` Adds a new <autoid> anchor.

```
\newcommand*{\LWR@newautoidanchor}{%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{}%
{
    \ifbool{LWR@freezethisautoid}{}{%
        \addtocounter{LWR@thisautoid}{1}%
        \LWR@htmltag{a id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}"}%
            \LWR@htmltag{/a}%
    }%
}
}
```

`\@captype` Remembers which float type is in use.

```
\newcommand*{\@captype}{}
```

`\LWR@floatalignmentname` Set to `center`, `flushleft`, or `flushright` if saw `\centering`, `\raggedright`, or `\raggedleft`.

```
\newcommand*{\LWR@floatalignmentname}{}
```

`\LWR@floatalignment` If sees a `\centering`, `\raggedleft`, or `\raggedright`, creates a `center`, `flushright`, or `flushleft` environment.

```
\newcommand*{\LWR@floatalignment}{%
\ifdefstrequal{\LWR@mynexttoken}{\centering}{%
    \center%
    \renewcommand*{\LWR@floatalignmentname}{center}%
}{}%
\ifdefstrequal{\LWR@mynexttoken}{\raggedright}{%
    \flushleft%
    \renewcommand*{\LWR@floatalignmentname}{flushleft}%
}{}%
\ifdefstrequal{\LWR@mynexttoken}{\raggedleft}{%
    \flushright%
    \renewcommand*{\LWR@floatalignmentname}{flushright}%
}{}%
}
```

`\LWR@endfloatalignment` Closes an environment from `\LWR@floatalignment`.

```
\newcommand*{\LWR@endfloatalignment}{%
\ifdefvoid{\LWR@floatalignmentname}{}{\@nameuse{end\LWR@floatalignmentname}}%
\renewcommand*{\LWR@floatalignmentname}{}%
}
```

73.3 Caption inside a float environment

\CaptionSeparator How to separate the float number and the caption text.

```
\AtBeginDocument{\providecommand*{\CaptionSeparator}{:~}}
```

\@makecaption {⟨*name and num*⟩} {⟨*text*⟩}

Prints the float type and number, the caption separator, and the caption text.

```
\AtBeginDocument{\renewcommand{\@makecaption}[2]{%
    \LWR@traceinfo{@makecaption}%
    \LWR@isolate{#1}\CaptionSeparator\LWR@isolate{#2}%
    \LWR@traceinfo{@makecaption: done}%
}%
}
```

73.4 Caption and LOF linking and tracking

When a new HTML file is marked in the LaTeX PDF file, the LaTeX page number at that point is stored in LWR@latestautopage, (and the associated filename is remembered by the special LaTeX labels). This page number is used to generate an autopage HTML <id> in the HTML output at the start of the new HTML file. Meanwhile, there is a float counter used to generate an HTML autoid <id> at the start of the float itself in the HTML file. The autopage and autoid values to use for each float are written to the .lof, etc. files just before each float's entry. These values are used by \l@figure, etc. to create the HTML links in the List of Figures, etc.

Ctr LWR@nextautoid Tracks autoid for floats. Tracks autopage for floats.

Ctr LWR@nextautopage These are updated per float as the .lof, .lot file is read.

```
\newcounter{LWR@nextautoid}
\newcounter{LWR@nextautopage}
```

\LWRsetnextfloat {⟨*autopage*⟩} {⟨*float autoid*⟩}

File *_html.lof This is written to the *_html.lof or *_html.lot file just before each float's usual entry. The autopage and the float's autoid are remembered for \l@figure to use when creating the HTML links.

File *_html.lot

```
\newcommand*{\LWRsetnextfloat}[2]{%
```

```
    \setcounter{LWR@nextautopage}{#1}%
    \setcounter{LWR@nextautoid}{#2}%
}
```

Ctr LWR@latestautopage

Updated each time a new HTML file is begun. \LWRsetnextfloat is written with this and the autoid by the modified \addcontentsline just before each float's entry.

```
\newcounter{LWR@latestautopage}
\setcounter{LWR@latestautopage}{1}
```

Env LWR@figcaption

An HTML <figcaption> is not allowed in places where LaTeX does allow a figure caption, such as inside a longtable where the tabular has already started, or inside a center environment. Therefore, a of class figurecaption is used instead.

```
\newenvironment*{LWR@figcaption}
    {
        \ifbool{FormatWP}{%
            \BlockClass[font-style:italic]{figurecaption}
%             \LWR@print@vspace*{\baselineskip}
        }{
            \BlockClass{figurecaption}
        }%
    }
    {\endBlockClass}
```

\LWR@HTML@caption@begin {⟨*type*⟩}

Low-level code to create HTML tags for captions.

The print versions are from the caption package.

```
\newcommand*{\LWR@HTML@caption@begin}[1]
{
\LWR@traceinfo{LWR@HTML@caption@begin}%
```

Keep par and minipage changes local:

```
\begingroup%
```

The caption code was not allowing the closing par tag:

```
\@setpar{\LWR@closeparagraph\@@par}%
```

No need for a minipage or \parbox inside the caption:

```
\RenewDocumentEnvironment{minipage}{O{t} o O{t} m}{}{}%
\RenewDocumentCommand{\parbox}{O{t} O{} O{t} m +m}{##5}%
```

Enclose the original caption code inside an HTML tag:

```
\LWR@figcaption%
\LWR@traceinfo{LWR@HTML@caption@begin: about to LWR@origcaption@begin}%
```

```
\LWR@print@caption@begin{#1}%
\LWR@traceinfo{LWR@HTML@caption@begin: done}%
}
```

\LWR@HTML@caption@end Low-level patches to create HTML tags for captions.

```
\newcommand*{\LWR@HTML@caption@end}
{%
\LWR@traceinfo{LWR@HTML@caption@end}%
\LWR@print@caption@end%
```

Closing tag:

```
\endLWR@figcaption%
\endgroup%
% \leavevmode% avoid bad space factor (0) error
\LWR@traceinfo{LWR@HTML@caption@end: done}%
}
```

\caption@begin
\caption@end Low-level patches to create HTML tags for captions. These are assigned \AtBeginDocument so that other packages which modify captions will have already been loaded before saving the print-mode version.

```
\AtBeginDocument{
\LWR@formatted{caption@begin}
\LWR@formatted{caption@end}
}
```

\captionlistentry Tracks the float number for this caption used outside a float. Patched to create an HTML anchor.

```
\let\LWR@origcaptionlistentry\captionlistentry

\renewcommand*{\captionlistentry}{%
\LWR@ensuredoingapar%
\LWR@origcaptionlistentry%
}

\def\LWR@LTcaptionlistentry{%
\LWR@ensuredoingapar%
\LWR@htmltag{a id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}"}\LWR@htmltag{/a}%
  \bgroup
  \@ifstar{\egroup\LWR@LT@captionlistentry}% gobble *
          {\egroup\LWR@LT@captionlistentry}}%
\def\LWR@LT@captionlistentry#1{%
  \caption@listentry\@firstoftwo[\LTcaptype]{#1}}%
```

\addcontentsline Patched to write the autopage and autoid before each float's entry. No changes if writing .toc For a theorem, automatically defines \ext@<type> as needed, to mimic and reuse the float mechanism.

f

```
\let\LWR@origaddcontentsline\addcontentsline

\renewcommand*{\addcontentsline}[3]{%
\ifstrequal{#1}{toc}{}{% not TOC

\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
    {}%
    {\LWR@newautoidanchor}%

    \ifcsvoid{ext@#2}{\csdef{ext@#2}{#1}}{}%

    \addtocontents{\@nameuse{ext@#2}}{%
        \protect\LWRsetnextfloat%
        {\arabic{LWR@latestautopage}}%
        {\arabic{LWR@thisautoid}}%
    }%
}% not TOC
\LWR@origaddcontentsline{#1}{#2}{#3}%
}
```

Pkg capt-of
Pkg caption

Either package provides `\captionof`, which is later patched at the beginning of the document.

\captionof

Patched to handle paragraph tags.

```
\AtBeginDocument{
\let\LWR@origcaptionof\captionof

\renewcommand*{\captionof}{%
\LWR@stoppars
\LWR@origcaptionof%
}
}

\end{warpHTML}
```

74 Table of Contents, LOF, LOT

This section controls the generation of the TOC, LOF, and LOT.

The `.toc`, `.lof`, and `.lot` files are named by the source code `\jobname`.

In HTML, the printed tables are placed inside a `<div>` of class `toc`, `lof`, or `lot`.

A "sidetoc" is provided which prints a subset of the TOC on the side of each page other than the homepage.

The regular LaTeX infrastructure is used for TOC, along with some patches to generate HTML output.

for HTML output:
```
\begin{warpHTML}
```

74.1 Reading and printing the TOC

`\LWR@myshorttoc` {⟨*toc/lof/lot/sidetoc*⟩}

Reads in and prints the TOC/LOF/LOT at the current position. While doing so, makes the `@` character into a normal letter to allow formatting commands in the section names.

Unlike in regular LaTeX, the file is not reset after being read, since the sideTOC may be referred to again in each HTML page.

```
\newcommand*{\LWR@myshorttoc}[1]{%
\LWR@traceinfo{LWR@myshorttoc: #1}%
\LWR@ensuredoingapar%
```

Only if the file exists:

```
\IfFileExists{\jobname.#1}{%
\LWR@traceinfo{LWR@myshorttoc: loading}%
```

⚠ Many of the commands in the file will have `@` characters in them, so `@` must be made a regular letter.

```
\begingroup%
\makeatletter%
```

Read in the TOC file:

```
\@input{\jobname.#1}%
\endgroup%
}%
{}%
\LWR@traceinfo{LWR@myshorttoc: done}%
}
```

`\LWR@subtableofcontents` {⟨*toc/lof/lot*⟩} {⟨*sectionstarname*⟩}

Places a TOC/LOF/LOT at the current position.

```
\NewDocumentCommand{\LWR@subtableofcontents}{m m}{%
```

Closes previous levels:

```
\@ifundefined{chapter}
{\LWR@closeprevious{\LWR@depthsection}}
{\LWR@closeprevious{\LWR@depthchapter}}
```

Prints any pending footnotes so that they appear above the potentially large TOC:

```
\LWR@printpendingfootnotes
```

Place the list into its own chapter (if defined) or section:

```
\@ifundefined{chapter}{\section*{#2}}{\chapter*{#2}}
```

Create a new HTML nav containing the TOC/LOF/LOT:

```
\LWR@htmlelementclass{nav}{#1}
```

Create the actual list:

```
\LWR@myshorttoc{#1}
```

Close the nav:

```
\LWR@htmlelementclassend{nav}{#1}
}
```

`\@starttoc` {⟨*ext*⟩}

Patch `\@starttoc` to encapsulate the TOC inside HTML tags:

```
\let\LWR@orig@starttoc\@starttoc

\renewcommand{\@starttoc}[1]{
\LWR@htmlelementclass{nav}{#1}
\LWR@orig@starttoc{#1}
\LWR@htmlelementclassend{nav}{#1}
}
```

Bool `LWR@copiedsidetoc` Used to only copy the TOC file to the sidetoc a single time.

(listings and perhaps other packages would re-use `\tableofcontents` for their own purposes, causing the sidetoc to be copied more than once, and thus end up empty.)

```
\newbool{LWR@copiedsidetoc}
\boolfalse{LWR@copiedsidetoc}
```

`\tableofcontents` Patch `\tableofcontents`, etc. to print footnotes first. newfloat uses `\listoffigures` for all future float types.

```
\AtBeginDocument{
\let\LWR@origtableofcontents\tableofcontents

\renewcommand*{\tableofcontents}{%
```

Do not print the table of contents if formatting for a word processor, which will presumably auto-generate its own updated table of contents:

```
\ifboolexpr{bool{FormatWP} and bool{WPMarkTOC}}{

=== table of contents ===

```

```
}
{
```

Copy the .toc file to .sidetoc for printing the sideTOC. The original .toc file is renewed when \tableofcontents is finished.

```
    \ifbool{LWR@copiedsidetoc}{}{%
        \LWR@copyfile{\jobname.toc}{\jobname.sidetoc}%
        \booltrue{LWR@copiedsidetoc}%
    }%
    \LWR@printpendingfootnotes
    \LWR@origtableofcontents
}
}% \tableofcontents
}% AtBeginDocument
```

\listoffigures

```
\let\LWR@origlistoffigures\listoffigures

\renewcommand*{\listoffigures}{
\ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{

=== list of figures ===

}
{
    \LWR@printpendingfootnotes
    \LWR@origlistoffigures
}
}
```

\listoftables

```
\let\LWR@origlistoftables\listoftables

\renewcommand*{\listoftables}{
\ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{

=== list of tables ===

}
{
    \LWR@printpendingfootnotes
    \LWR@origlistoftables
}
}
```

74.2 High-level TOC commands

\listof {⟨*type*⟩} {⟨*title*⟩}

Emulate the \listof command from the float package (section 223). Used to create lists of custom float types. Also used to redefine the standard LaTeX \listoffigures and \listoftables commands.

```
\NewDocumentCommand{\listof}{m +m}{%
\@ifundefined{l@#1}{%
    \csdef{l@#1}##1##2{\hypertocfloat{1}{#1}{\@nameuse{ext@#1}}{##1}{##2}}%
}{}%
\LWR@subtableofcontents{\@nameuse{ext@#1}}{#2}
\expandafter\newwrite\csname tf@\csname ext@#1\endcsname\endcsname
\immediate\openout \csname tf@\csname ext@#1\endcsname\endcsname
    \jobname.\@nameuse{ext@#1}\relax
}
```

74.3 Side TOC

The "side TOC" is a table-of-contents positioned to the side.

It may be renamed by redefining \sidetocname, and may contain paragraphs.

CSS may be used to format the sideTOC:

CSS related to sideTOC:

div.sidetoccontainer: The entire sideTOC.
div.sidetoctitle: The title.
div.sidetoccontents: The table of contents.

```
\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Ctr SideTOCDepth — Controls how deep the side-TOC gets. Use a standard LaTeX section level similar to tocdepth.

```
\newcounter{SideTOCDepth}
\setcounter{SideTOCDepth}{1}
```

\sidetocname — Holds the default name for the sideTOC.

```
\newcommand{\sidetocname}{Contents}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@sidetoc Creates the actual side-TOC.

```
\newcommand*{\LWR@sidetoc}{
\LWR@forcenewpage
\LWR@stoppars

```

The entire sideTOC is placed into a nav of class sidetoc.

```
\LWR@htmlelementclass{div}{sidetoccontainer}
\LWR@htmlelementclass{nav}{sidetoc}

\setcounter{tocdepth}{\value{SideTOCDepth}}

```

The title is placed into a of class sidetoctitle, and may contain paragraphs.

```
\begin{BlockClass}{sidetoctitle}
\ifcsvoid{thetitle}{}{\InlineClass{sidetocthetitle}{\thetitle}\par}
\sidetocname
\end{BlockClass}
```

The table of contents is placed into a of class sidetoccontents.

```
\begin{BlockClass}{sidetoccontents}
\LinkHome

\LWR@myshorttoc{sidetoc}
\end{BlockClass}
\LWR@htmlelementclassend{nav}{sidetoc}
\LWR@htmlelementclassend{div}{sidetoccontainer}
}
```

74.4 Low-level TOC line formatting

\numberline {⟨*number*⟩}

(Called from each line in the .aux, .lof files.)

Record this section number for further use:

```
\newcommand*{\LWR@numberline}[1]{%
\LWR@sectionnumber{#1}\quad%
}

\LetLtxMacro\numberline\LWR@numberline
```

\hypertoc {⟨*1: depth*⟩} {⟨*2: type*⟩} {⟨*3: name*⟩} {⟨*4: page*⟩}

Called by \l@section, etc. to create a hyperlink to a section.

The autopage label is always created just after the section opens.

#1 is depth

#2 is `section`, `subsection`, etc.

#3 the text of the caption

#4 page number

```
\NewDocumentCommand{\hypertoc}{m m +m m}{%
\LWR@traceinfo{hypertoc !#1!#2!#3!#4!}%
```

Respond to `tocdepth`:

```
\ifthenelse{\cnttest{#1}{<=}{\value{tocdepth}}}%
    {%
        \LWR@startpars%
```

Create an HTML link to `<filename>#autosec-(page)`, with the name, of the given HTML class.

```
        \LWR@subhyperrefclass{%
            \LWR@htmlrefsectionfilename{autopage-#4}%
                \LWR@origpound\LWR@print@mbox{autosec-#4}%
        }{#3}{toc#2}%
        \LWR@stoppars%
    }%
    {}%
\LWR@traceinfo{hypertoc done}%
}
```

Ctr `lofdepth` TOC depth for figures.

```
\@ifclassloaded{memoir}{}{
\newcounter{lofdepth}
\setcounter{lofdepth}{1}
}
```

Ctr `lotdepth` TOC depth for tables.

```
\@ifclassloaded{memoir}{}{
\newcounter{lotdepth}
\setcounter{lotdepth}{1}
}
```

`\hypertocfloat` {⟨*1: depth*⟩} {⟨*2: type*⟩} {⟨*3: ext of parent*⟩} {⟨*4: caption*⟩} {⟨*5: page*⟩}

#1 is depth

#2 is `figure`, `table`, etc.

#3 is `lof`, `lot`, of the parent.

#4 the text of the caption

#5 page number

```
\newcommand{\hypertocfloat}[5]{%
\LWR@startpars
```

If some float-creation package has not yet defined the float type's `lofdepth` counter, etc, define it here:

```
\@ifundefined{c@#3depth}{%
\newcounter{#3depth}%
\setcounter{#3depth}{1}%
}{}%
```

Respond to `lofdepth`, etc.:

```
\LWR@traceinfo{hypertocfloat depth is #1 #3depth is \arabic{#3depth}}%
\ifthenelse{\cnttest{#1}{<=}{\arabic{#3depth}}}%
    {%
        \LWR@startpars%
```

Create an HTML link to filename#autoid-(float number), with text of the caption, of the given HTML class.

```
        \LWR@subhyperrefclass{%
        \LWR@htmlrefsectionfilename{autopage-\arabic{LWR@nextautopage}}%
        \LWR@origpound\LWR@print@mbox{autoid-\arabic{LWR@nextautoid}}}%
        {#4}{toc#2}%
        \LWR@stoppars%
    }%
    {}%
}
```

Automatically called by `\contentsline`:

`\l@part` {⟨*name*⟩} {⟨*page*⟩}

Uses `\DeclareDocumentCommand` in case the class does not happen to have a `\part`.

```
\DeclareDocumentCommand{\l@part}{m m}{\hypertoc{-1}{part}{#1}{#2}}
```

`\l@chapter` {⟨*name*⟩} {⟨*page*⟩}

Uses `\DeclareDocumentCommand` in case the class does not happen to have a `\chapter`.

```
\@ifundefined{chapter}
{}
{
\DeclareDocumentCommand{\l@chapter}{m m}
    {\hypertoc{0}{chapter}{#1}{#2}}
}
```

\l@section {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@section}[2]{\hypertoc{1}{section}{#1}{#2}}
```

\l@subsection {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@subsection}[2]{\hypertoc{2}{subsection}{#1}{#2}}
```

\l@subsubsection {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@subsubsection}[2]{\hypertoc{3}{subsubsection}{#1}{#2}}
```

\l@paragraph {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@paragraph}[2]{\hypertoc{4}{paragraph}{#1}{#2}}
```

\l@subparagraph {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@subparagraph}[2]{\hypertoc{5}{subparagraph}{#1}{#2}}
```

\l@figure {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@figure}[2]{\hypertocfloat{1}{figure}{lof}{#1}{#2}}
```

\l@table {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@table}[2]{\hypertocfloat{1}{table}{lot}{#1}{#2}}
```

```
\end{warpHTML}
```

75 Index and glossary

See:
http://tex.stackexchange.com/questions/187038/how-to-mention-section-number-in-index-created-by-imakeidx

Index links are tracked by the counter LWR@autoindex. This counter is used to create a label for each index entry, and a reference to this label for each entry in the index listing. This method allows each index entry to link directly to its exact position in the document.

for HTML output:

```
\begin{warpHTML}
```

```
\newcounter{LWR@autoindex}
\setcounter{LWR@autoindex}{0}

\newcounter{LWR@autoglossary}
\setcounter{LWR@autoglossary}{0}
```

Env theindex

```
\@ifundefined{chapter}
{\newcommand*{\LWR@indexsection}[1]{\section*{#1}}}
{\newcommand*{\LWR@indexsection}[1]{\chapter*{#1}}}

\AtBeginDocument{
\renewenvironment*{theindex}{%
    \LWR@indexsection{\indexname}%
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}{}
}% AtBeginDocument
```

\LWR@indexitem [⟨*index key*⟩] The optional argument is added to support repeatindex.

```
\newcommand{\LWR@indexitem}[1][\@empty]{

\InlineClass{indexitem}{}#1%
}
```

\LWR@indexsubitem

```
\newcommand{\LWR@indexsubitem}{

\InlineClass{indexsubitem}{}
}
```

\LWR@indexsubsubitem

```
\newcommand{\LWR@indexsubsubitem}{

\InlineClass{indexsubsubitem}{}
}
```

\@wrindex {⟨*term*⟩} Redefined to write the LWR@autoindex counter instead of page.

```
\def\LWR@wrindex#1{%
\addtocounter{LWR@autoindex}{1}%
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
\protected@write\@indexfile{}%
{\string\indexentry{#1}{\arabic{LWR@autoindex}}}%
\endgroup
\@esphack}

\AtBeginDocument{
\let\@wrindex\LWR@wrindex
}
```

\@wrglossary {⟨*term*⟩} Redefined to write the LWR@latestautopage counter instead of page.

```
\def\@wrglossary#1{%
\addtocounter{LWR@autoglossary}{1}%
\LWR@new@label{LWRglossary-\theLWR@autoglossary}%
\protected@write\@glossaryfile{}%
{\string\glossaryentry{#1}{\theLWR@autoglossary}}%
\endgroup
\@esphack}
```

`\LWR@indexnameref` {⟨*LWR@autoindex*⟩}

Creates a hyperlink based on the given entry's autoindex.

```
\newcommand*{\LWR@indexnameref}[1]{\nameref{LWRindex-#1}}
```

`\LWR@doindexentry` {⟨*LWR@autoindex, or macros.*⟩}

Creates a hyperlink, or handles `\see`, `\textbf`, etc.

```
\newrobustcmd{\LWR@doindexentry}[1]{%
\IfInteger{#1}%
    {\LWR@indexnameref{#1}}%
    {#1}%
}
```

`\LWR@hyperindexrefnullified` Handles macros commonly seen inside an `\index` entry. Each macro is redefined to create and format a link to its entry.

⚠ index formatting To handle additional macros:

```
\appto\LWR@hyperindexrefnullified{. . . }
```

```
\newcommand{\LWR@hyperindexrefnullified}{%
\renewrobustcmd{\emph}[1]{\LWR@HTML@emph{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textbf}[1]{\LWR@HTML@textbf{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textrm}[1]{\LWR@HTML@textrm{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textsf}[1]{\LWR@HTML@textsf{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\texttt}[1]{\LWR@HTML@texttt{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textup}[1]{\LWR@HTML@textup{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textsc}[1]{\LWR@HTML@textsc{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textsi}[1]{\LWR@HTML@textsi{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textit}[1]{\LWR@HTML@textit{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textsl}[1]{\LWR@HTML@textsl{\LWR@doindexentry{##1}}}%
}
```

`\hyperindexref` {⟨*LWR@autoindex*⟩}

`\hyperindexref{LWR@autoindex}` is inserted into `*.ind` by the makeindex style file `lwarp.ist` or the xindy style file `lwarp.xdy`.

```
\newcommand{\hyperindexref}[1]{%
```

In long index lines with numerous entries, *makeindex* can insert a newline before the page number, resulting in an extra space before the first digit. If the first character is a space, remove it first.

```
\def\LWR@tempone{#1}%
\IfBeginWith{\LWR@tempone}{ }{%
    \StrGobbleLeft{\LWR@tempone}{1}[\LWR@tempone]%
}{}%
```

If a numeric entry, create a link. If not numeric, such as `\see`, use the entry as-is. `\emph`, `\textit`, etc. have been redefined above to create and format the entry.

```
\IfInteger{\LWR@tempone}%
    {\LWR@indexnameref{\LWR@tempone}}%
    {%
        \begingroup%
        \LWR@hyperindexrefnullified
        #1%
        \endgroup%
    }%
}
```

```
\end{warpHTML}
```

for PRINT output: A null command for print mode, in case hyperref was not used:

```
\begin{warpprint}
\newcommand{\hyperindexref}[1]{#1}
\end{warpprint}
```

for HTML & PRINT: For the glossaries package, try to prevent an error where `\glo@name` was not found:

```
\begin{warpall}
\providecommand{\glo@name}{}
\end{warpall}
```

76 Bibliography presentation

for HTML output:
```
\begin{warpHTML}
```

`\bibliography` {⟨*filenames*⟩}

Modified to use the base jobname instead of the `_html` jobname.

```
\def\bibliography#1{%
    \if@filesw
    \immediate\write\@auxout{\string\bibdata{#1}}%
    \fi
%     \@input@{\jobname.bbl}% original
    \begingroup%
```

```
    \@input@{\BaseJobname.bbl}% lwarp
    \endgroup%
}
```

`\@biblabel` {⟨*text-refnumber*⟩}

```
\renewcommand{\@biblabel}[1]{[#1]\quad}
```

Env `thebibliography` To emphasize document titles in the bibliography, the following redefines `\em` inside `thebibliography` to gather everything until the next closing brace, then display these tokens with `\textit`.

Adapted from `embracedef.sty`, *which is by* Takayuki YATO*:*
https://gist.github.com/zr-tex8r/b72555e3e7ad2f0a37f1

```
\AtBeginDocument{
\AtBeginEnvironment{thebibliography}{
\providecommand*{\LWR@newem}[1]{\textit{#1}}

\renewrobustcmd{\em}{%
  \begingroup
    \gdef\LWR@em@after{\LWR@em@finish\LWR@newem}%
    \afterassignment\LWR@em@after
    \toks@\bgroup
}

\def\LWR@em@finish#1{%
    \xdef\LWR@em@after{\noexpand#1{\the\toks@}}%
  \endgroup
  \LWR@em@after\egroup
}
}% \AtBeginEnvironment{thebibliography}
}% \AtBeginDocument

\end{warpHTML}
```

77 Restoring original formatting

`\LWR@restoreorigformatting` Used to temporarily restore the print-mode meaning of a number of formatting, graphics, and symbols-related macros while generating SVG math or a `lateximage`.

Must be used inside a group.

Sets `\LWR@formatting` to `print` until the end of the group.

A number of packages will `\appto` additional actions to this macro.

Various packages add to this macro using `\appto`.

for HTML output:

```
\begin{warpHTML}
```

```
\newcommand*{\LWR@restoreorigformatting}{%
\LWR@traceinfo{LWR@restoreorigformatting}%
```

Numerous macros change their print/HTML meaning depending on `\LWR@formatting`:

```
\renewcommand*{\LWR@formatting}{print}%
\linespread{1}%

\let\par\LWR@origpar%

\LWR@select@print@hspace%

\LetLtxMacro\hfil\LWR@orighfil%
\let\hss\LWR@orighss%
\let\llap\LWR@origllap%
\let\rlap\LWR@origrlap%
\let\hfilneg\LWR@orighfilneg%

\let\,\LWR@origcomma% disable HTML short unbreakable space
\let\thinspace\LWR@origthinspace% disable HTML short unbreakable space
\let\negthinspace\LWR@orignegthinspace% disable HTML negative short unbreakable space
\let\textellipsis\LWR@origtextellipsis%
\let\textless\LWR@origtextless%
\let\textgreater\LWR@origtextgreater%
\LetLtxMacro\rmfamily\LWR@origrmfamily%
\LetLtxMacro\sffamily\LWR@origsffamily%
\LetLtxMacro\ttfamily\LWR@origttfamily%
\LetLtxMacro\bfseries\LWR@origbfseries%
\LetLtxMacro\mdseries\LWR@origmdseries%
\LetLtxMacro\upshape\LWR@origupshape%
\LetLtxMacro\slshape\LWR@origslshape%
\LetLtxMacro\scshape\LWR@origscshape%

\LetLtxMacro\sishape\LWR@origsishape%

\LetLtxMacro\itshape\LWR@origitshape%
\LetLtxMacro\em\LWR@origem%
\LetLtxMacro\normalfont\LWR@orignormalfont%
\let\sp\LWR@origsp%
\let\sb\LWR@origsb%
\LetLtxMacro\textsuperscript\LWR@origtextsuperscript%
\LetLtxMacro\@textsuperscript\LWR@orig@textsuperscript%
\LetLtxMacro\textsubscript\LWR@origtextsubscript%
\LetLtxMacro\@textsubscript\LWR@orig@textsubscript%
\LetLtxMacro\underline\LWR@origunderline%
\let~\LWR@origtilde%
\let\enskip\LWR@origenskip%
\let\quad\LWR@origquad%
\let\qquad\LWR@origqquad%
```

`\endtabular` must be restored to its original, instead of relying on lwarp's `\LWR@formatted` mechanism:

```
\LetLtxMacro\endtabular\LWR@origendtabular%
\csletcs{endtabular*}{LWR@origendtabular*}%

\LetLtxMacro\noalign\LWR@orignoalign%
\LetLtxMacro\hline\LWR@orighline%

\let\newline\LWR@orignewline%
\LetLtxMacro\includegraphics\LWR@origincludegraphics%
\let\TeX\LWR@origTeX%
\let\LaTeX\LWR@origLaTeX%
\let\LaTeXe\LWR@origLaTeXe%
\renewcommand*{\Xe}{X\textsubscript{E}}%

\LetLtxMacro\@ensuredmath\LWR@origensuredmath%
%
\LWR@restoreorigaccents%
\LWR@restoreoriglists%
%
\LWR@FBcancel%
}

\end{warpHTML}
```

78 Math

78.1 Limitations

78.1.1 Math in section names

⚠ math in section names

If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring`:

```
\section{A math \texorpdfstring{$1+2=3$}{text description} name}
```

78.1.2 Rendering tradeoffs

Math rendering

Math may be rendered as SVG graphics or using the MATHJAX JavaScript display engine.

SVG files

Rendering math as images creates a new SVG file for each expression, except that an MD5 hash is used to combine identical duplicates of the same inline math expression into a single file, which must be converted to SVG only once. Display math is still handled as individual files, since it may contain labels or references which are likely to change.

SVG inline

The SVG images are currently stored separately, but they could be encoded in-line

directly into the HTML document. This may reduce the number of files and potentially speed loading the images, but slows the display of the rest of the document before the images are loaded.

PNG files

Others LaTeX-to-HTML converters have used PNG files, sometimes pre-scaled for print resolution but displayed on-screen at a scaled down size. This allows high-quality print output at the expense of larger files, but SVG files are the preferred approach for scalable graphics.

MathML

Conversion to MathML might be a better approach, among other things allowing a more compact representation of math than SVG drawings. Problems with MathML include limited browser support and some issues with the fine control of the appearance of the result. Also see section 11 regarding EPUB output with MathJax.

78.1.3 SVG option

SVG math option

For SVG math, math is rendered as usual by LaTeX into the initial PDF file using the current font[18], then is captured from the PDF and converted to SVG graphics via a number of utility programs. The SVG format is a scalable-vector web format, so math may be typeset by LaTeX with its fine control and precision, then displayed or printed at any size, depending on (sometimes broken) browser support. An HTML `alt` attribute carries the LaTeX code which generated the math, allowing copy/paste of the LaTeX math expression into other documents.

SVG image font size

For the `lateximage` environment, the size of the math and text used in the SVG image may be adjusted by setting `\LateximageFontSizeName` to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline SVG math, font size is instead controlled by `\LateximageFontScale`, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

SVG math copy/paste

For SVG math, text copy/paste from the HTML `<alt>` tags lists the equation number or tag for single equations, along with the LaTeX code for the math expression. For $\mathcal{AMS}$ environments with multiple numbers in the same environment, only the first and last is copy/pasted, as a range. No tags are listed inside a starred $\mathcal{AMS}$ environment, although the `\tag` macro will still appear inside the LaTeX math expression.

⚠ SVG math in TeX boxes

SVG math does not work inside TeX boxes, since a `\newpage` is required before and after each image.

78.1.4 MathJax option

MathJax math option

Prog MathJax

The popular MathJax alternative (`mathjax.org`) may be used to display math.

When MathJax is enabled, math is rendered twice:

[18] See section 491 regarding fonts and fractions.

1. As regular LaTeX PDF output placed inside an HTML comment, allowing equation numbering and cross referencing to be almost entirely under the control of LaTeX, and
2. As detokenized printed LaTeX commands placed directly into the HTML output for interpretation by the MathJax display scripts. An additional script is used to pre-set the equation number format and value according to the current LaTeX values, and the MathJax cross-referencing system is ignored in favor of the LaTeX internal system, seamlessly integrating with the rest of the LaTeX code.

78.1.5 Customizing MathJax

MathJax does not have preexisting support every possible math function. Additional MathJax function definitions may be defined. These will be declared at the start of each HTML page, and thus will have a global effect.

Examples:

```
\CustomizeMathJax{
    \newcommand{\expval}[1]{\langle#1\rangle}
    \newcommand{\abs}[1]{\lvert#1\rvert}
}
\CustomizeMathJax{\newcommand{\arsinh}{\text{arsinh}}}
\CustomizeMathJax{\newcommand{\arcosh}{\text{arcosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
```

78.1.6 MathJax limitations

MathJax limitations

Prog MathJax

Limitations when using MathJax include:

subequations

- MathJax itself does not support subequations. This may be improved by parsing the LaTeX math expression to manually insert tags, but this has not yet been done.

footnotes in math

- Footnotes inside equations are not yet supported while using MathJax.

lateximage

- Math appearing inside a lateximage, and therefore also inside a Ti*k*z or `picture` environment, is rendered as SVG math even if MathJax is used in the rest of the document.

siunitx

- Usage of siunitx inside a math equation is supported via a third-party MathJax extension. While inside a math expression, do not use `\SI` or `\si` inside `\text`, where it will be rendered as normal text.

  ⚠ siunitx inside an equation

  https://github.com/burnpanck/MathJax-siunitx

  Also see section 9.7.11.

tabbing

- A `tabbing` environment is emulated using an HTML <pre>.While MathJax is enabled inside `tabbing`, the browser may not correctly render the horizontal alignment of the math and text following after on the same line.

⚠ other macros and packages

- Other math-related macros and packages are not supported by MathJax, including `\ensuremath` and bigdelim, along with occasionally-used macros such as `\relax`. lwarp emulates footnotes, units, and nicefrac for MathJax.

78.1.7 Catcode changes

preamble macros with math

The math shift character `$` is not set for HTML output until after the preamble. Macros defined in the preamble which contain `$` must be enclosed between `\StartDefiningMath` and `\StopDefiningMath` to temporarily change to the HTML meaning of `$`:

```
\StartDefiningMath
\newcommand{. . . }
\StopDefiningMath
```

As an alternative, use `\(` and `\)` instead of `$`, in which case `\StartDefiningMath` and `\StopDefiningMath` are not necessary.

If a package defines macros using `$`, it may be nessary to use `\StartDefiningMath` and `\StopDefiningMath` before and after loading the package.

78.1.8 Complicated inline math objects

`\inlinemathnormal` `\inlinemathother`

changing contents

complicated `alt` tag

An inline math expression is usually converted to a reusable hashed SVG math image, or a MathJax expression. The hash or expression depends on the contents of the math expression. In most cases this math expression is static, such as `$x+1$`, so the image can be reused for multiples instances of the same expression. In some cases, the math expression includes a counter or other object which may change between uses. Another problem is complicated contents which do not expand well in an `alt` tag. The macro `\inlinemathother` may be used before a dynamic math expression, and `\inlinemathnormal` after. Doing so tells lwarp to use an unhashed SVG math image, even if MathJax is in use. See section 44.

78.1.9 Complicated display math objects

`\displaymathnormal`

By default, or when selecting `\displaymathnormal`, MathJax math display environments print their contents as text into HTML, and SVG display math environments render their contents as SVG images and use their contents as the `alt` tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Ti*k*z pictures, compilation will fail.

`\displaymathother`

MathJax unsupported

complicated `alt` tag

When selecting `\displaymathother`, it is assumed that the contents are more complicated than "pure" math. An example is an elaborate Ti*k*z picture, which will not render in MathJax and will not make sense as an HTML `alt` tag. In this mode, MathJax is turned off, math display environments become SVG images, even if MathJax is selected, and the HTML `alt` tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Ti*k*z pictures are more likely to compile successfully.

78.2 HTML alt tag names

Redefinable names for the HTML alt tags, for translation according to the reader's native language.

for HTML & PRINT:

```
\begin{warpall}
```

\mathimagename
Default: ``math image''

The HTML alt tag for an SVG math image.

```
\newcommand*{\mathimagename}{math image}
```

\packagediagramname
Default: ``diagram''

Appended to the lateximage HTML alt tag for the images generated by many packages.

```
\newcommand*{\packagediagramname}{diagram}
```

```
\end{warpall}
```

78.3 Inline and display math

for HTML output:

```
\begin{warpHTML}
```

Ctr LWR@externalfilecnt

Counter for the external files which are generated and then referenced from the HTML:

```
\newcounter{LWR@externalfilecnt}
```

Bool LWR@indisplaymathimage

True if processing display math for SVG output. Inside a lateximage, display math is only set to print-mode output if LWR@indisplaymathimage is false. Used to avoid nullifying display math before it has been completed.

```
\newbool{LWR@indisplaymathimage}
```

Bool LWR@xfakebold

True if xfakebold \setBold is in use.

```
\newbool{LWR@xfakebold}
\boolfalse{LWR@xfakebold}
```

\LWR@orig@setBold

Redefined by lwarp-xfakebold.

```
\newcommand*{\LWR@orig@setBold}{}
```

\LWR@orig@unsetBold

Redefined by lwarp-xfakebold.

```
\newcommand*{\LWR@orig@unsetBold}{}
```

\LWR@applyxfakebold

Redefined by lwarp-xfakebold.

```
\newcommand*{\LWR@applyxfakebold}{}
```

\$ Plain dollar signs appearing in the HTML output may be interpreted by MathJax to be math shifts. For a plain text dollar \$, use an HTML entity to avoid it being interpreted by MathJax, unless are inside a lateximage, in which case it will not be seen by MathJax.

```
\let\LWR@origtextdollar\$

\renewcommand*{\$}{%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{\LWR@origtextdollar}%
{\HTMLentity{dollar}}%
}
```

File lwarp_baseline_marker.png
File lwarp_baseline_marker.eps

A marker to be used to help *pdfcrop* identify the inline math baseline and width. If either graphicx or graphics is loaded, this marker is placed at the lower left and lower right corners of the inline math. *pdfcrop* is then able to identify the width of the image, and also the height of an image such as a horizontal dash which does not otherwise touch the baseline.

A marker with alpha or opacity of 0% is not registered by *pdfcrop*, so the marker is a small square block of 1% alpha, which seems to work while still being effectively invisible in the final SVG image.

If graphicx is loaded, this marker is sized as a tiny 1 sp square. If graphics is loaded, this marker is used at its default size of around .25 pt. If neither graphics package is loaded, the marker is replaced by a 10 sp horizontal space, and there is no assistance for determining baseline or width of the inline math image. The best results are obtained when using graphicx.

\LWR@addbaselinemarker Places a small marker in an SVG inline image. If graphics or graphicx are loaded, the marker is a mostly transparent image. If neither is loaded, no marker is used.

```
\AtBeginDocument{

\ifpdf
    \newcommand*{\LWR@baselinename}{lwarp_baseline_marker.png}
\else
    \ifXeTeX
        \newcommand*{\LWR@baselinename}{lwarp_baseline_marker.png}
    \else
        \newcommand*{\LWR@baselinename}{lwarp_baseline_marker.eps}
    \fi
\fi

\IfFileExists{\LWR@baselinename}%
{
    \@ifpackageloaded{graphicx}{
        \newcommand*{\LWR@addbaselinemarker}{%
            \LWR@origincludegraphics{\LWR@baselinename}%
        }
    }{
        \@ifpackageloaded{graphics}{
            \newcommand*{\LWR@addbaselinemarker}{%
                \LWR@origincludegraphics{\LWR@baselinename}%
```

```
            }
        }{
            \PackageWarning{lwarp}{Load graphicx or graphics
                for improved SVG math baselines,}
            \newcommand*{\LWR@addbaselinemarker}{}
        }
    }
}{% lwarp_baseline_marker.png or .eps is not present
   \PackageWarning{lwarp}{File \LWR@baselinename\space is not installed alongside
        the lwarp-*.sty files, so SVG math baselines may not be accurate,}
    \newcommand*{\LWR@addbaselinemarker}{}
}

}% AtBeginDocument
```

\LWR@subsingledollar * {⟨*2: alt text*⟩} {⟨*3: add'l hashing*⟩} {⟨*4: math expression*⟩}

For inline math. Uses MathJax, or for SVG math the image is measured and ajusted to the baseline of the HTML output, and placed inside a `lateximage`.

image filename hashing

If starred, a hashed filename is used.If so, the hash is based on the `alt` tag and also the additional hashing argument.

This may be used to provide an expression with a simple `alt` tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated TEX expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is duplicated in the additional hashing argument.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing argument in order to make the hash unique according to the set of options, even if the simple `alt` tag is still the same.

```
\newlength{\LWR@singledollarwidth}
\newlength{\LWR@singledollarheight}
\newlength{\LWR@singledollardepth}

\newsavebox{\LWR@singledollarbox}

\NewDocumentCommand{\LWR@subsingledollar}{s m m m}{%
\LWR@traceinfo{LWR@subsingledollar}%

\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{%
\LWR@traceinfo{LWR@subsingledollar: already in a lateximage}%
    #4% contents
}%
{% not in a lateximage
\begingroup%
```

Support for xfakebold:

```
\LWR@applyxfakebold%
```

MathJax cannot parse the often complicated TEX expressions which appear in the various uses of `\ensuredmath`. `\ensuremath` forces the `alt` tag to "`(math image)`", as translated according to `\mathimagename`. If this is the case, force the use of a `lateximage` even if MathJax. Likewise for siunitx if `parse-numbers=false`.

If MathJax, or if formatting math for a word processor, and not `\ensuredmath`, and not a dynamic math expression, print the math expression:

```
\ifboolexpr{%
    (
        bool{mathjax} or
        ( bool{FormatWP} and bool{WPMarkMath} )
    ) and
   ( not test { \ifstrequal {#2} {(\mathimagename)} } ) and % from \ensuredmath
    ( not bool{LWR@dynamicmath} )
}%
```

For MathJax, print the math between `\(` and `\)`:

```
{%
    \LWR@traceinfo{LWR@subsingledollar: Mathjax}%
    {\textbackslash(\LWR@HTMLsanitize{#4}\textbackslash)}%
}% mathjax
```

For SVG, print the math inside a `lateximage`, with an `<alt>` tag of the LATEX code, and a CSS style to control the baseline adjustment.

```
{% not mathjax
\LWR@traceinfo{LWR@subsingledollar: NOT mathjax, or is ensuremath, or is dynamic}%
```

Measure the depth, width, and height of the math image:

```
    \begingroup%
```

Temporarily disable formatting while measuring the image parameters:

```
    \LWR@restoreorigformatting%
    \RenewDocumentEnvironment{lateximage}{s o o o}{}{}% inside group
    \LWR@print@normalsize%
```

Temporarily set font for the HTML PDF output:

```
    \LWR@traceinfo{Using font family \LWR@f@family}%
    \@nameuse{LWR@orig\LWR@f@family family}%
    \LWR@traceinfo{Using font series \LWR@f@series}%
    \@nameuse{LWR@orig\LWR@f@series series}%
    \LWR@traceinfo{Using font shape \LWR@f@shape}%
    \@nameuse{LWR@orig\LWR@f@shape shape}%
```

`lateximagedepth` must be nested to avoid generating paragraph tags. $\mathcal{AMS}$ math modifies the `\text` macro such that `\addtocounter` does not always occur as expected. Lower-level code is used instead.

```
    \global\advance\c@LWR@lateximagedepth 1\relax%
```

Typeset and save the contents, depending on how they were generated:

SVG math: `\LWR@origensuredmath` is part of argument #4.

SVG math `\ensuremath`: `\LWR@origensuredmath` is part of argument #4.

SVG dynamic math: `\LWR@origensuredmath` is part of argument #4.

Mathjax: Argument #4 is the contents of the math expression without `\LWR@origensuredmath`. This case is handled above.

Mathjax `\ensuremath`: `\LWR@origensuredmath` is part of argument #4.

Mathjax dynamic math: Argument #4 is the contents of the math expression without `\LWR@origensuredmath`, so `\LWR@origensuredmath` is added below.

`\ifmmode`: Included "just in case".

```
    \ifmmode%
        \global\sbox{\LWR@singledollarbox}{#4}%
    \else%
        \ifbool{LWR@dynamicmath}{%
            \ifbool{mathjax}{%
                \global\sbox{\LWR@singledollarbox}{\LWR@origensuredmath{#4}}%
            }{%
                \global\sbox{\LWR@singledollarbox}{#4}%
            }%
        }{%
            \global\sbox{\LWR@singledollarbox}{#4}%
        }%
    \fi%
```

Add a small and almost transparent marker at the depth of the image.

A math minus sign has the same depth as a plus, even though it does not draw anything below the baseline. This means that *pdfcrop* would crop the image without depth. The marker below the baseline is seen by *pdfcrop* and preserves the depth.

```
    \global\sbox{\LWR@singledollarbox}{%
        \usebox{\LWR@singledollarbox}%
        \raisebox{-\dp\LWR@singledollarbox}{%
            \LWR@addbaselinemarker%
        }%
    }%
```

More low-level code to undo the counter change.

```
    \global\advance\c@LWR@lateximagedepth -1\relax% Due to AmS \text macro.
```

Measure the depth:

```
    \setlength{\LWR@singledollardepth}{%
        \LateximageFontScale\dp\LWR@singledollarbox%
    }%
```

Make the length a global change:

```
    \global\LWR@singledollardepth=\LWR@singledollardepth%
```

Likewise for width:

```
    \setlength{\LWR@singledollarwidth}{%
        \LateximageFontScale\wd\LWR@singledollarbox%
    }%
    \global\LWR@singledollarwidth=\LWR@singledollarwidth%
```

Likewise for total height:

```
    \setlength{\LWR@singledollarheight}{%
        \LateximageFontScale\ht\LWR@singledollarbox%
    }%
    \addtolength{\LWR@singledollarheight}{%
        \LateximageFontScale\dp\LWR@singledollarbox%
    }%
    \global\LWR@singledollarheight=\LWR@singledollarheight%

    \endgroup%
```

Set a style for the the height or width. The `em` unit is used so that the math scales according to the user's selected font size.

Start with the greater of the width or the height, biased towards the width:

```
    \ifdimgreater{\LWR@singledollarwidth}{.7\LWR@singledollarheight}{%
        \def\LWR@singledollarstyle{%
            width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
        }%
    }{%
        \def\LWR@singledollarstyle{%
            height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
        }%
    }%
```

If a very narrow width, use the height.

```
    \ifdimless{\LWR@singledollarwidth}{.2em}%
    {%
        \def\LWR@singledollarstyle{%
            height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
        }%
    }%
    {}%
```

If very wide and short, use the width:

```
    \ifdimless{\LWR@singledollarheight}{.2em}%
    {%
        \def\LWR@singledollarstyle{%
            width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
        }%
    }%
    {}%
```

If there is significant text depth, add the depth to the style.

```
    \ifdimgreater{\LWR@singledollardepth}{0.05ex}{%
        \def\LWR@singledollardepthstyle{%
            \ ; % extra space
            \LWR@print@mbox{%
            vertical-align:-\LWR@convertto{em}{\the\LWR@singledollardepth} em%
            } % extra space
        }%
    }{%
        \def\LWR@singledollardepthstyle{}%
    }%
```

Create the `lateximage` using the alternate tag and the computed size and depth. The star causes `lateximage` to use an MD5 hash as the filename. When hashing, also include the current font and color in the hash.

```
    \ifbool{LWR@dynamicmath}{%
        \LWR@traceinfo{subsingledollar: dynamic}%
        \begin{lateximage}% no hashing
            [(\mathimagename)]% alt tag
            []% no add'l hashing
            [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
    }{%
        \LWR@traceinfo{subsingledollar: static}%
        \IfValueTF{#1}{%
            \LWR@findcurrenttextcolor% sets \LWR@tempcolor
```

Support for xfakebold:

```
            \ifbool{LWR@xfakebold}%
                {\def\LWR@tempone{Y}}%
                {\def\LWR@tempone{N}}%

            \begin{lateximage}*% use hashing
                [#2]% alt
                [% addl' hashing
                    #3%
                    FM\LWR@f@family%
                    SR\LWR@f@series%
                    SH\LWR@f@shape%
                    CL\LWR@tempcolor%
                    FB\LWR@tempone% xfakebold
                ]%
```

```
                [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
        }{%
            \begin{lateximage}% no hashing
                [#2]% alt
                []% no add'l hashing
                [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
        }%
    }%
```

Place small and almost transparent markers on the baseline at the left and right edges of the image. These markers are seen by *pdfcrop*, and force vertically-centered objects such as a dash to be raised off the baseline in the cropped image, and also force the total width and left / right margins to be correct. (Except that in some fonts a character may exceed the bounding box, and thus may appear wider than expected when converted to an image.)

```
    \LWR@addbaselinemarker%
```

Support for xfakebold:

```
    \LWR@applyxfakebold%
```

Typeset the contents:

```
    \usebox{\LWR@singledollarbox}%
```

The closing baseline marker:

```
    \LWR@addbaselinemarker%

    \end{lateximage}%
%
}% not mathjax
\endgroup%
}% not in a lateximage
\LWR@traceinfo{LWR@subsingledollar: done}%
}

\LetLtxMacro\LWR@origdollar$
\LetLtxMacro\LWR@secondorigdollar$% balance for editor syntax highlighting

\LetLtxMacro\LWR@origopenparen\(
\LetLtxMacro\LWR@origcloseparen\)
\LetLtxMacro\LWR@origopenbracket\[
\LetLtxMacro\LWR@origclosebracket\]
```

$
$$

Redefine the dollar sign to place math inside a `lateximage`, or use MathJax:

```
\begingroup
\catcode`\$=\active%
\protected\gdef${\@ifnextchar$\LWR@doubledollar\LWR@singledollar}%
```

Used by chemformula to escape single-dollar math:

```
\protected\gdef\LWR@newsingledollar{\@ifnextchar$\LWR@doubledollar\LWR@singledollar}%
```

\LWR@doubledollar Redefine the double dollar sign to place math inside a lateximage, or use MathJax:

```
\protected\gdef\LWR@doubledollar$#1$${%
```

If MathJax or formatting for a word processor, print the LaTeX expression:

```
\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
```

For MathJax, print the math between \[and \]:

```
{

    \textbackslash[%
    \LWR@HTMLsanitize{#1}%
    \textbackslash]

}% mathjax
```

For SVG, print the math inside a lateximage, with an <alt> tag of the LaTeX code:

```
{% not mathjax
    \begin{BlockClass}{displaymath}%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}%
    [%
        \textbackslash{[} % extra space
        \LWR@HTMLsanitize{#1} % extra space
        \textbackslash{]}%
    ]%
```

Support for xfakebold:

```
    \LWR@applyxfakebold%

    \LWR@origdollar\LWR@origdollar#1\LWR@origdollar\LWR@origdollar%
    \end{lateximage}%
    \end{BlockClass}%
}% not mathjax
}%
```

\LWR@singledollar {⟨*alt text*⟩} {⟨*math expression*⟩}

```
\protected\gdef\LWR@singledollar#1${%
\ifbool{mathjax}{%
    \LWR@subsingledollar*%
    {% alt tag
        \textbackslash( %
        \LWR@HTMLsanitize{#1} % extra space
```

```
        \textbackslash)%
    }%
    {singledollar}% add'l hashing
    {#1}% contents
}{% not mathjax
    \LWR@subsingledollar*%
    {% alt tag
        \textbackslash( %
        \LWR@HTMLsanitize{#1} % extra space
        \textbackslash)%
    }%
    {singledollar}% add'l hashing
    {\LWR@origensuredmath{#1}}% contents
}% not mathjax
}
```

`\(` `\[` Redefine to the above dollar macros.

```
\AtBeginDocument{
\protected\gdef\(#1\){$#1$}
\protected\gdef\[#1\]{$$#1$$}
}

\endgroup


\AtBeginDocument{
\LetLtxMacro\LWR@openbracketnormal\[
\LetLtxMacro\LWR@closebracketnormal\]
}
```

`\@ensuredmath` {⟨*expression*⟩}

If MathJax, a `lateximage` is used, since `\ensuremath` is often used for complex TEX expressions which MathJax may not render. If SVG math, a hashed file is used with a simple `alt` tag, but additional hashing provided by the contents.

```
\LetLtxMacro\LWR@origensuredmath\@ensuredmath

\renewcommand{\@ensuredmath}[1]{%
\ifbool{mathjax}{%
    \LWR@subsingledollar*{(\mathimagename)}{%
            \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
    }{\relax%
        \LWR@origensuredmath{#1}%
    }%
}{% SVG math
```

If already inside a `lateximage` in math mode, continue as-is.

```
\ifmmode%
    \LWR@origensuredmath{#1}%
\else%
```

Create an inline math `lateximage` with a simple `alt` tag and additional hashing according to the contents.

```
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
    {\LWR@origensuredmath{#1}}%
    {%
        \LWR@subsingledollar*{(\mathimagename)}{%
           \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
        }{%
            \LWR@origensuredmath{#1}%
        }%
    }%
\fi%
}%
}
```

Remove the old `math` and `displaymath` environments:

```
\let\math\relax
\let\endmath\relax
\let\displaymath\relax
\let\enddisplaymath\relax
```

Env `math` Set math mode then typeset the body of what was between the begin/end. See the environ package for `\BODY`.

```
\NewEnviron{math}{\expandafter\(\BODY\)}
```

Env `LWR@displaymathnormal` Set math mode then typeset the body of what was between the begin/end. See the environ package for `\BODY`.

```
\NewEnviron{LWR@displaymathnormal}{\expandafter\[\BODY\]\@ignoretrue}
```

Set the default displaymath to the normal version:

```
\LetLtxMacro\[\LWR@openbracketnormal%
\LetLtxMacro\]\LWR@closebracketnormal%
\LetLtxMacro\displaymath\LWR@displaymathnormal%
\LetLtxMacro\enddisplaymath\endLWR@displaymathnormal%
```

Env `LWR@displaymathother` A version of `displaymath` which can handle complicated objects, but does not supply MathJax or HTML `alt` tags.

```
\newenvironment{LWR@displaymathother}
{%
    \begin{BlockClass}{displaymath}%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}%
    [(display math)]%
    \LWR@origdollar\LWR@origdollar%
```

```
}
{%
    \LWR@origdollar\LWR@origdollar%
    \end{lateximage}%
    \end{BlockClass}%
}
```

Env LWR@equationother A version of displaymath which can handle complicated objects, but does not supply MathJax or HTML alt tags.

```
\newenvironment{LWR@equationother}
{%
    \begin{BlockClass}{displaymathnumbered}%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}%
    [(display math)]%
    \LWR@origequation%
}
{%
    \LWR@origendequation%
    \end{lateximage}%
    \end{BlockClass}%
}
```

78.4 MathJax support

Ctr LWR@nextequation Used to add one to compute the next equation number.

```
\newcounter{LWR@nextequation}
```

\LWR@syncmathjax Sets the MathJax equation format and number for the following equations.

These MathJax commands are printed inside "\(" and "\)" characters. They are printed to HTML output, not interpreted by LaTeX.

```
\newcommand*{\LWR@syncmathjax}{%
```

If using chapters, place the chapter number in front of the equation. Otherwise, use the simple equation number.

```
\ifcsdef{thechapter}{
    \InlineClass{hidden}{
        \textbackslash(
        \textbackslash{}seteqsection \{\thechapter\}
        \textbackslash)
    }
}
{}% not using chapters
```

MathJax doesn't allow setting the equation number to 1:

```
\ifthenelse{\cnttest{\value{equation}}>0}
{
```

Tell MathJax that the next set of equations begins with the current LaTeX equation number, plus one.

```
    \setcounter{LWR@nextequation}{\value{equation}}
    \addtocounter{LWR@nextequation}{1}
```

Place the MathJax command inside "\(" and "\)" characters, to be printed to HTML, not interpreted by LaTeX.

```
    \InlineClass{hidden}{
        \textbackslash(
        \textbackslash{}seteqnumber \{\arabic{LWR@nextequation}\}
        \textbackslash)
    }
}{}% not eq > 0
}
```

`\LWR@hidelatexequation` {⟨*environment*⟩} {⟨*contents*⟩}

Creates the LaTeX version of the equation inside an HTML comment.

```
\NewDocumentCommand{\LWR@hidelatexequation}{m +m}{%
```

Stop HTML paragraph handling and open an HTML comment:

```
\LWR@stoppars
\LWR@htmlopencomment

```

Start the LaTeX math environment inside the HTML comment:

```
\begingroup
\@nameuse{LWR@orig#1}
```

While in the math environment, restore various commands to their LaTeX meanings.

```
\LWR@restoreorigformatting
```

See `\LWR@htmlmathlabel` in section 78.7.1.

Print the contents of the equation:

```
#2
```

End the LaTeX math environment inside the HTML comment:

```
\@nameuse{LWR@origend#1}
\endgroup

```

Close the HTML comment and resume HTML paragraph handling:

```
\LWR@htmlclosecomment
\LWR@startpars
}
```

`\LWR@addmathjax` {⟨*environment*⟩} {⟨*contents*⟩}

Given the name of a math environment and its contents, create a MathJax instance. The contents are printed to HTML output, not interpreted by LaTeX.

```
\NewDocumentCommand{\LWR@addmathjax}{m +m}{%
```

Enclose the MathJax environment inside printed "`\(`" and "`\)`" characters.

```
\LWR@origtilde\LWR@orignewline
\textbackslash{}begin\{#1\}
```

Print the contents, sanitizing for HTML special characters.

```
\LWR@HTMLsanitizeexpand{\detokenize\expandafter{#2}}
```

Close the MathJax environment:

```
\textbackslash{}end\{#1\}
\LWR@orignewline
}
```

78.5 Equation environment

Remember existing `equation` environment:

```
\AtBeginDocument{
\let\LWR@origequation\equation
\let\LWR@origendequation\endequation
\csletcs{LWR@origequation*}{equation*}
\csletcs{LWR@origendequation*}{endequation*}
}
```

`\LWR@doequation` {⟨*env contents*⟩} {⟨*env name*⟩}

For SVG math output, the contents are typeset using the original `equation` inside a `latexmage`, along with an `<alt>` tag containing a detokenized copy of the LaTeX source for the math.

For MathJax output, the contents are typeset in an original `equation` environment placed inside a HTML comment, with special processing for `\labels`. The contents are also printed to the HTML output for processing by the MathJax script.

```
\newcommand*{\LWR@doequation}[2]{%

```

If mathjax or FormatWP, print the LaTeX expression:

```
\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
```

MathJax output:

```
{
```

Print commands to syncronize MathJax's equation number and format to the current LaTeX chapter/section and equation number:

```
    \LWR@syncmathjax
```

Print the LaTeX math inside an html comment:

```
    \LWR@hidelatexequation{#2}{#1}
}
```

SVG output: Create the lateximage along with an html <alt> tag having an equation number, the LaTeX equation environment commmands, and the contents of the environment's \BODY.

```
{% not mathjax
```

Begin the lateximage with an <alt> tag containing the math source:

```
    \ifstrequal{#2}{equation*}{%
        \begin{BlockClass}{displaymath}%
    }{%
        \begin{BlockClass}{displaymathnumbered}%
    }%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[%
        \ifstrequal{#2}{equation*}{%
            \ifdefequal{\LWR@equationtag}{\theequation}{%
% no tag was given
            }{%
                (\LWR@equationtag) % tag was given
            }%
        }{%
            (\LWR@equationtag) % automatic numbering
        }%
        \textbackslash{begin\{#2\}} % extra space
        \LWR@HTMLsanitizeexpand{\detokenize\expandafter{#1}} % extra space
        \textbackslash{end\{#2\}}%
    ]% alt tag
```

Support for xfakebold:

```
    \LWR@applyxfakebold%
```

Create the actual LaTeX-formatted equation inside the `lateximage` using the contents of the environment.

```
    \@nameuse{LWR@orig#2}%
    #1% contents collected by \collect@body
    \@nameuse{LWR@origend#2}%
    \end{lateximage}%
    \end{BlockClass}%
}% not mathjax
}
```

After the environment, if MathJax, print the math to the HTML output for MathJax processing:

```
\newcommand*{\LWR@doendequation}[1]{%
    \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
    {%
        \LWR@addmathjax{#1}{\BODY}%
    }{}%

}
```

Remove existing `equation` environment:

```
\AtBeginDocument{
\let\equation\relax
\let\endequation\relax
\csletcs{equation*}{relax}
\csletcs{endequation*}{relax}
}
```

Env `equation` The new `equation` environment is created with `\NewEnviron` (from the environ package), which stores the contents of its environment in a macro called `\BODY`.

```
\AtBeginDocument{
\NewEnviron{equation}%
{\LWR@doequation{\BODY}{equation}}%
[\LWR@doendequation{equation}]

\LetLtxMacro\LWR@equationnormal\equation
\LetLtxMacro\endLWR@equationnormal\endequation
}
```

Env `equation*`

```
\AtBeginDocument{
\NewEnviron{equation*}%
{\LWR@doequation{\BODY}{equation*}}%
[\LWR@doendequation{equation*}]

\csletcs{LWR@equationnormalstar}{equation*}
\csletcs{LWR@endequationnormalstar}{endequation*}
}
```

Remember the "less" version of equation, which uses MathJax and alt tags, but does not support complicated contents such as some Ti*k*z expressions.

```
\AtBeginDocument{
\LetLtxMacro\LWR@equationless\equation
\LetLtxMacro\endLWR@equationless\endequation
\csletcs{LWR@equationlessstar}{equation*}
\csletcs{LWR@endequationlessstar}{endequation*}
}
```

78.6 \displaymathnormal and \displaymathother

\displaymathnormal

By default, or when selecting \displaymathnormal, MathJax math display environments print their contents as text into HTML, and SVG display math environments render their contents as SVG images and use their contents as the alt tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Ti*k*z pictures, compilation will fail.

\displaymathother
MathJax unsupported complicated alt tag

When selecting \displaymathother, it is assumed that the contents are more complicated than "pure" math. An example is an elaborate Ti*k*z picture, which will not render in MathJax and will not make sense as an HTML alt tag. In this mode, MathJax is turned off, math display environments become SVG images, even if MathJax is selected, and the HTML alt tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Ti*k*z pictures are more likely to compile successfully.

\displaymathnormal
simple math objects

Use when display math environments have simple math which is to sent to MathJax or included in HTML alt tags.

```
\newcommand*{\displaymathnormal}{%
\ifbool{LWR@origmathjax}{\booltrue{mathjax}}{\boolfalse{mathjax}}%
\LetLtxMacro\[\LWR@openbracketnormal%
\LetLtxMacro\]\LWR@closebracketnormal%
\LetLtxMacro\displaymath\LWR@displaymathnormal%
\LetLtxMacro\enddisplaymath\endLWR@displaymathnormal%
\LetLtxMacro\equation\LWR@equationnormal%
\LetLtxMacro\endequation\endLWR@equationnormal%
\csletcs{equation*}{LWR@equationnormalstar}%
\csletcs{endequation*}{LWR@endequationnormalstar}%
}
```

\displaymathother
complicated math objects

Use when display math environments have complicated objects which will not work with MathJax or should not be included in HTML alt tags. Complicated contents are more likely to compile correctly.

```
\newcommand*{\displaymathother}{%
\boolfalse{mathjax}%
\LetLtxMacro\displaymath\LWR@displaymathother%
\LetLtxMacro\enddisplaymath\endLWR@displaymathother%
\LetLtxMacro\[\LWR@displaymathother%
\LetLtxMacro\]\endLWR@displaymathother%
```

```
\LetLtxMacro\equation\LWR@equationother%
\LetLtxMacro\endequation\endLWR@equationother%
\csletcs{equation*}{displaymath}%
\csletcs{endequation*}{enddisplaymath}%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

Print-mode versions:

```
\newcommand*{\displaymathnormal}{}
\newcommand*{\displaymathother}{}
```

```
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

78.7 AMS Math environments

78.7.1 Support macros

Bool `LWR@amsmultline` True if processing a multline environment.

To compensate for `multline`-spefific code, `LWR@amsmultline` is used to add extra horizontal space in `\LWR@htmlmathlabel` if is used in an amsmath environment which is not a `multline` environment and not an `equation`.

```
\newbool{LWR@amsmultline}
\boolfalse{LWR@amsmultline}
```

`\LWR@htmlmathlabel` {⟨*label*⟩}

lwarp points `\ltx@label` here. This is used by `\label` when inside a LaTeX AMS math environment's math display environment.

`\LWR@origltx@label` points to the LaTeX original, modified by lwarp, then by amsmath, then by cleveref.

```
\newcommand*{\LWR@htmlmathlabel}[1]{%
\LWR@traceinfo{LWR@htmlmathlabelb #1}%
```

If `mathjax` or `FormatWP`, print the LaTeX expression:

```
\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{%
```

The combined LaTeX & HTML label is printed in a `\text` field:

```
    \text{%
```

Shift the label over to the right side of the environment to avoid over-printing the math:

```
    \ifbool{LWR@amsmultline}{}{\hspace*{\totwidth@}}%
```

Temporarily end the HTML comment, insert the LaTeX & HTML label, then resume the HTML comment. `\@firstofone` is required to remove extra braces introduced by the amsmath package.)

```
    \LWR@htmlclosecomment%
    \LWR@origltx@label{#1}%
    \LWR@htmlopencomment%
    }% text
}% mathjax
{%
    \LWR@origltx@label{#1}%
}%
}
```

`\LWR@beginhideamsmath` Starts hiding LaTeX math inside an HTML comment.

```
\newcommand*{\LWR@beginhideamsmath}{
\LWR@stoppars
\LWR@origtilde\LWR@orignewline
\LWR@htmlopencomment

\begingroup
\LWR@restoreorigformatting
}
```

`\LWR@endhideamsmath` Ends hiding LaTeX math inside an HTML comment.

```
\newcommand*{\LWR@endhideamsmath}{
\endgroup

\LWR@htmlclosecomment
\LWR@orignewline
\LWR@startpars
}
```

78.7.2 Environment patches

The amsmath environments already collect their contents in `\@envbody` for further processing. `eqnarray` is not an $\mathcal{AMS}$ package, and thus requires special handling.

For SVG math: Each envrionment is encapsulated inside a `lateximage` environment, along with a special optional argument of `\LWR@amsmathbody` or `\LWR@amsmathbodynumbered` telling `lateximage` to use as the HTML `<alt>` tag the environment's contents which were automatically captured by the $\mathcal{AMS}$ environment.

For MathJax: Each environment is syched with LaTeX's equation numbers, typeset with LaTeX inside an HTML comment, then printed to HTML output for MathJax to process.

Env eqnarray This environmnet is not an $\mathcal{AMS}$ environment and thus its body is not automatically captured, so the environ package is used to capture the environment into \BODY.

```
\let\LWR@origeqnarray\eqnarray
\let\LWR@origendeqnarray\endeqnarray
```

To remember whether the starred environment was used, and thus whether to number the equations:

```
\newbool{LWR@numbereqnarray}
\booltrue{LWR@numbereqnarray}
```

Common code used by eqnarray and Beqnarray (from fancybox):

```
\newcommand{\LWR@eqnarrayfactor}{%
```

If mathjax or FormatWP, print the LaTeX expression:

```
\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{%
```

If MathJax, the environment contents (the \BODY) are executed in a HTML comment to trigger the correct equation number increment (if not starred), then are included verbatim in the output for MathJax to interpret:

```
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \ifbool{LWR@numbereqnarray}
    {
```

If numbering the equations, execute a copy inside an HTML comment block:

```
        \LWR@beginhideamsmath
        \LWR@origeqnarray
        \BODY
        \LWR@origendeqnarray
        \LWR@endhideamsmath
```

Then print the (sanitized) contents to the output for MathJax to interpret:

```
        \LWR@addmathjax{eqnarray}{\BODY}
    }%
    {% not LWR@numbereqnarray
```

If not numbering equations, just create the contents for MathJax:

```
    \LWR@addmathjax{eqnarray*}{\BODY}
    }% LWR@numbereqnarray
```

```
}% mathjax
{% not mathjax
    \ifbool{LWR@numbereqnarray}
    {
```

For numbered SVG equations, first create a `lateximage` with an `alt` attribute containing sanitized copy of the source code:

```
        \begin{BlockClass}{displaymathnumbered}%
        \LWR@newautoidanchor%
        \booltrue{LWR@indisplaymathimage}%
        \begin{lateximage}[(\LWR@startingequationtag--\LWR@equationtag)
            \LWR@addmathjax{eqnarray}{\BODY}]
```

Support for xfakebold:

```
        \LWR@applyxfakebold%
```

Create the image contents using an actual `eqnarray`:

```
        \LWR@origeqnarray
        \BODY
        \LWR@origendeqnarray
        \end{lateximage}
        \end{BlockClass}
    }%
    {% not LWR@numbereqnarray
```

If not numbered, do the same, but an extra `\nonumber` seems to be required:

```
        \begin{BlockClass}{displaymath}
        \LWR@newautoidanchor%
        \booltrue{LWR@indisplaymathimage}%
        \begin{lateximage}[\LWR@addmathjax{eqnarray*}{\BODY}]
```

Support for xfakebold:

```
        \LWR@applyxfakebold%

        \LWR@origeqnarray
        \BODY
        \nonumber
        \LWR@origendeqnarray
        \end{lateximage}
        \end{BlockClass}
    }% LWR@numbereqnarray
}% not mathjax
```

Default to number equations in the future:

```
\booltrue{LWR@numbereqnarray}
}
```

eqnarray itself is made with a blank line before and after to force it to be on its own line:

```
\RenewEnviron{eqnarray}
{%

\LWR@eqnarrayfactor

}
```

The starred version is patched to turn off the numbering:

```
\csgpreto{eqnarray*}{\boolfalse{LWR@numbereqnarray}}

\end{warpHTML}
```

79 Lateximages

79.1 Description

Env lateximage

A lateximage is a piece of the document which is typeset in LaTeX then included in the HTML output as an image. This is used for math if SVG math is chosen, and also for the picture, tikzpicture, and other environments.

Before typesetting the lateximage a large number of formatting, graphics, and symbols-related macros are temporarily restored to their print-mode meaning by \LWR@restoreorigformatting. (See section 77.)

A lateximage is typeset on its own PDF page inside an HTML comment which starts on the preceeding page and ends on following page, and instructions are written to lateximage.txt for *lwarpmk* to extract the lateximage from the page of the PDF file then generate an accompanying .svg file image file. Meanwhile, instructions to show this image are placed into the HTML file after the comment.

An HTML is created to hold both the HTML comment, which will have the *pdftotext* conversion, and also the link to the final .svg image.

A LaTeX label is used to remember which PDF page has the image. A label is used because footnotes, endnotes, and pagenotes may cause the image to appear at a later time. The label is declared along with the image, and so it correctly remembers where the image finally ended up.

HTML alt tag

The HTML alt tag is set to the LaTeX source for SVG math, some chemistry expressions, and perhaps some other expressions which make sense for text copy/paste. In some other cases, the alt tag is set according to the package name.

When creating an SVG math image, its alt tag may be set to the math expression, which may be hashed for image reuse. In the case of \ensuremath or after \inlinemathother, where the contents require a unique image for each instance of the same expression, the alt tag is set to \mathimagename, and the image is not reused.

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “math image”, and it may be changed according to the document’s language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following SVG math images.

For many packages, the output is placed inside a `lateximage` with an HTML `alt` tag set to the package name followed by `\packagediagramname`. For example:

```
(-xy- diagram)
```

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “diagram”, and may it be changed according to the document’s language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following `lateximages`.

SVG image font size

For the `lateximage` environment, the size of the math and text used in the SVG image may be adjusted by setting `\LateximageFontSizeName` to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline SVG math, font size is instead controlled by `\LateximageFontScale`, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

79.2 Support counters and macros

for HTML output:

```
\begin{warpHTML}
```

Ctr `LWR@lateximagenumber`

Sequence the images.

```
\newcounter{LWR@lateximagenumber}
\setcounter{LWR@lateximagenumber}{0}
```

Ctr `LWR@lateximagedepth`

Do not create `\lateximage` inside of `\lateximage`.

```
\newcounter{LWR@lateximagedepth}
\setcounter{LWR@lateximagedepth}{0}
```

A few utility macros to write special characters:

```
\edef\LWR@hashmark{\string#} % for use in \write
\edef\LWR@percent{\@percentchar} % for use in \write
```

Ctr `LWR@LIpage`

Used to reference the PDF page number of a lateximage to be written into `<project>-images.txt`.

```
\newcounter{LWR@LIpage}
```

```
\end{warpHTML}
```

79.3 Font size

for HTML & PRINT:

```
9849 \begin{warpall}
```

`\LateximageFontSizeName` Declares how large to write text in `\lateximages`. The `.svg` file text size should blend well with the surrounding HTML text size.

⚠ no backslash *Do not include the leading backslash in the name.*

```
9850 \newcommand*{\LateximageFontSizeName}{normalsize}
```

`\LateximageFontScale` Declares how large to scale inline SVG math images. The `.svg` file text size should blend well with the surrounding HTML text size. The default is .75, but it may be redefined as needed depending on the HTML font.

```
9851 \newcommand*{\LateximageFontScale}{.75}
```

```
9852 \end{warpall}
```

79.4 Sanitizing math expressions for HTML

for HTML output:

```
9853 \begin{warpHTML}
```

`\LWR@HTMLsanitize` {⟨*text*⟩}

Math expressions are converted to `lateximages`, and some math environments may contain &, <, or >, which should not be allowed inside an HTML <alt> tag, so must convert them to HTML entities.

Two versions follow, depending on expansion needs. There may be a better way…

```
9854 \newrobustcmd{\LWR@HTMLsanitize}[1]{%
```

Cancel French babel character handling, and fully expand the strings:

```
9855 \begingroup%
9856 \LWR@FBcancel%
9857 \fullexpandarg%
```

The &, <, and > may be interpreted by the browser:

```
9858 \protect\StrSubstitute{\detokenize{#1}}%
9859 {\detokenize{&}}{\detokenize{&amp;}}[\LWR@strresult]%

9860 \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
9861 {\detokenize{<}}{\detokenize{&lt;}}[\LWR@strresult]%

9862 \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
9863 {\detokenize{>}}{\detokenize{&gt;}}[\LWR@strresult]%
```

The double quote occasionally causes problems.

```
\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{"}}{\detokenize{&quot;}}[\LWR@strresult]%
```

MathJax allows expressions to be defined with \newcommand. These expressions would appear with ## for each argument, and each must be changed to a single #. This must be done after all the above changes. Attempting another conversion after this causes an error upon further expansion.

```
\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{##}}{\LWR@origpound}[\LWR@strresult]%

\LWR@strresult%
\endgroup%
}
```

\LWR@HTMLsanitizeexpand {⟨*text*⟩}

This version expands the argument before sanitizing it.

```
\newrobustcmd{\LWR@HTMLsanitizeexpand}[1]{%
```

Cancel French babel character handling, and fully expand the strings:

```
\begingroup%
\LWR@FBcancel%
\fullexpandarg%
```

The difference between this and \LWR@HTMLsanitize (without "expand") is the following \expandafter:

```
\protect\StrSubstitute{\detokenize\expandafter{#1}}%
{\detokenize{&}}{\detokenize{&amp;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{<}}{\detokenize{&lt;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{>}}{\detokenize{&gt;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{"}}{\detokenize{&quot;}}[\LWR@strresult]%
```

\LWR@HTMLsanitizeexpand is not used for defining new MathJax macros, so the ## conversion is not needed here.

```
\LWR@strresult%
\endgroup%
}
```

79.5 Equation numbers

Ctr LWR@startingequation — For use with lateximage and multi-line numbered equations. Remembers the next equation number so that it may be printed in the alt tag.

```
\newcounter{LWR@startingequation}

\@ifundefined{chapter}
{
\renewcommand{\theLWR@startingequation}{%
\arabic{LWR@startingequation}%
}
}
{% chapter defined
\renewcommand{\theLWR@startingequation}{%
\ifnumcomp{\value{chapter}}{>}{0}{\arabic{chapter}.}{}%
\arabic{LWR@startingequation}%
}
}
```

Bool LWR@isstartingequation — True for the first equation tag, false for later tags in the same environment.

```
\newbool{LWR@isstartingequation}
```

\LWR@startingequationtag — Prints the starting equation number or tag.

```
\let\LWR@startingequationtag\theLWR@startingequation
```

\LWR@equationtag — Prints the ending equation number or tag.

This is reset by lateximage, may be temporarily overwritten by \tag calling \LWR@remembertag.

```
\newcommand*{\LWR@equationtag}{}
```

Only if SVG math, patch \tag after packages have loaded, in case someone else modified \tag.

```
\AtBeginDocument{

\ifbool{mathjax}{}{% not mathjax
```

\LWR@remembertag {⟨*tag*⟩}

For use inside the math environments while using SVG math. Sets \theLWR@startingequation and \theequation to the given tag.

```
\NewDocumentCommand{\LWR@remembertag}{m}{%
\ifbool{LWR@isstartingequation}%
{%
    \global\boolfalse{LWR@isstartingequation}%
    \xdef\LWR@startingequationtag{#1}%
```

```
}{}%
\xdef\LWR@equationtag{#1}%
}%

}% not mathjax
}% AtBeginDocument
```

79.6 HTML alt tags

\LWR@amsmathbody {⟨*envname*⟩} For use inside the optional argument to a lateximage to add the contents of a AMS math environment to the <alt> tag.

```
\newcommand*{\LWR@amsmathbody}[1]
{%
\textbackslash\{begin\}\{#1\} % extra space
\LWR@HTMLsanitizeexpand{\detokenize\expandafter{\the\@envbody}}%
\textbackslash\{end\}\{#1\}%
}
```

\LWR@amsmathbodynumbered {⟨*envname*⟩} For use inside the optional argument to a lateximage to add the contents of a AMS math environment to the alt tag, prefixed by the equation numbers.

```
\newcommand*{\LWR@amsmathbodynumbered}[1]
{%
\ifnumcomp{\value{LWR@startingequation}}{=}{\value{equation}}%
{(\LWR@equationtag)}%
{(\LWR@startingequationtag--\LWR@equationtag)} % extra space
\LWR@amsmathbody{#1} % extra space
}
```

79.7 lateximage environment

Env lateximage * [⟨*2:* <alt> *tag*⟩] [⟨*3: add'l hashing*⟩] [⟨*4: css style*⟩]

Typesets the contents and then renders the result as an SVG file. Star causes the image to be hashed for reuse.

The optional <alt> tag is included in the HTML code for use with copy/paste.

image filename hashing If starred, a hashed filename is used.If so, the hash is based on the alt tag and also the additional hashing argument.

This may be used to provide an expression with a simple alt tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated TEX expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is duplicated in the additional hashing argument.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing argument in order to make the hash unique according to the set of options, even if the simple `alt` tag is still the same.

File *_html.aux A new label is placed into the file *_html.aux:

```
\newlabel{LWRlateximage-<BaseJobname>-<number>}{{<x>}{<y>}}
```

This is used to find the image in the PDF file, according to its name.

File *-images.txt A list of images to generate is created in <jobname>-images.txt. Each line has three pipe-delimited fields, containing the PDF page number from <jobname>_html.pdf, where the image is located, a boolean indicating whether the image is hashed, and the filename of the image. The last line has "end" in each field, and is used to detect an incomplete compile.

```
\catcode`\$=\active%

\NewDocumentEnvironment{lateximage}{s O{(image)} O{} O{}}
{%
\LWR@traceinfo{lateximage: starting on \jobname.pdf page \arabic{page}}%
\LWR@traceinfo{lateximage: entering depth is \arabic{LWR@lateximagedepth}}%
```

Nested lateximages remain one large lateximage:

```
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
```

If nesting inside an already-existing lateximage, simply record one more level. $\mathcal{AMS}$ packages redefine \addtocounter to do nothing if inside a \text, so lower-level TEX macros are used for tracking nested lateximages.

```
{%
%     \addtocounter{LWR@lateximagedepth}{1}%
    \global\advance\c@LWR@lateximagedepth 1\relax% Due to AmS \text macro.
}%
```

Otherwise, this is the outer-most lateximage:

```
{% start of outer-most lateximage
```

Remember the next equation number to be allocated, in case it must be printed in a multi-equation environment:

```
\LWR@traceinfo{lateximage: starting outer-most lateximage}%
    \setcounter{LWR@startingequation}{\value{equation}}%
    \addtocounter{LWR@startingequation}{1}%
    \booltrue{LWR@isstartingequation}%
    \let\LWR@startingequationtag\theLWR@startingequation%
```

The default equation tag, unless overwritten by \tag:

```
    \let\LWR@equationtag\theequation%
```

Starting a new lateximage:

```
    \addtocounter{LWR@lateximagenumber}{1}%
  \LWR@traceinfo{lateximage: LWR@lateximagenumber is \arabic{LWR@lateximagenumber}}%
```

While inside a lateximage, locally do not use mathjax:

```
    \boolfalse{mathjax}%
```

Be sure that are doing a paragraph:

```
    \LWR@ensuredoingapar%
```

Next file:

```
    \addtocounter{LWR@externalfilecnt}{1}%
  \LWR@traceinfo{lateximage: LWR@externalfilecnt is \arabic{LWR@externalfilecnt}}%
```

Figure out what the next page number will be. `\setcounterpageref` assigns `LWR@LIpage` to the page number for the reference `LWRlateximage-BaseJobname-XXX`:

```
    \setcounterpageref{LWR@LIpage}{%
        LWRlateximage-\BaseJobname-\arabic{LWR@lateximagenumber}%
    }%
    \LWR@traceinfo{lateximage: LWR@LIpage is \arabic{LWR@LIpage}}%
```

Create an HTML span which will hold the comment which contains the *pdftotext* translation of the image's page, and also will hold the link to the `.svg` file:

```
    \LWR@htmltag{span\LWR@indentHTML%
     id="lateximage-\BaseJobname-\arabic{LWR@lateximagenumber}"\LWR@indentHTML
        class="lateximagesource"\LWR@orignewline
    }%
```

Write instructions to the `<ImagesDirectory>.txt` file:

```
    \LWR@traceinfo{lateximage: about to write to \BaseJobname-images.txt}%
    \IfBooleanTF{#1}% starred
    {% hash
        \LWR@traceinfo{lateximage: hash true, adding %
            !\detokenize\expandafter{#2}!\detokenize\expandafter{#3}!}%
```

Compute and save the hashed file name for later use:

```
        \edef\LWR@hashedname{%
            \LWR@mdfive{\detokenize\expandafter{#2}-!-#3}%
        }%
        \LWR@traceinfo{lateximage: hash is \LWR@hashedname}%
```

Write the page, hashing, and hashed name:

```
        \immediate\write\LWR@lateximagesfile{%
            |\arabic{LWR@LIpage}|true|\LWR@hashedname|%
```

```
        }%
    }% hash
    {% no hash
```

No hash, so write the page, no hashing, and the image number:

```
        \LWR@traceinfo{lateximage: hash false}%
        \immediate\write\LWR@lateximagesfile{%
        |\arabic{LWR@LIpage}|false|\LWR@ImagesName\arabic{LWR@externalfilecnt}|%
        }%
    }% no hash
```

Place an open comment tag. This will hide any traces of the lateximage PDF page which were picked up by *pdftotext*.

```
    \LWR@traceinfo{lateximage: about to create open comment}%
    \LWR@htmlopencomment%
```

One level deeper. At this outer-most `lateximage`, it is known that this is not being used inside an $\mathcal{AMS}$ `\text`, since the outer-most level will never be in math mode.

```
     \addtocounter{LWR@lateximagedepth}{1}%
```

Start the new PDF page:

```
    \LWR@traceinfo{lateximage: about to create a new page}%
    \LWR@orignewpage%
```

Typeset the image in a "standard" width page and font size:

```
    \LWR@traceinfo{lateximage: about to create minipage}%
    \LWR@print@minipage{6in}%
    \@nameuse{LWR@print@\LateximageFontSizeName}%
```

Temporarily restore formatting to its PDF definitions: Do not produce HTML tags for \hspace, etc. inside a lateximage.

```
    \LWR@traceinfo{lateximage: about to temporarily restore formatting}%
    \LWR@restoreorigformatting%
```

Use full-page footnotes instead of minipage footnotes. These become HTML footnotes.

```
    \def\@mpfn{footnote}%
    \def\thempfn{\thefootnote}%
    \LetLtxMacro\@footnotetext\LWR@footnotetext%
```

Create the `LWRlateximage<number>` label:

```
    \LWR@traceinfo{lateximage: about to create label}%
    \LWR@orig@label{LWRlateximage-\BaseJobname-\arabic{LWR@lateximagenumber}}%
    \LWR@traceinfo{lateximage: finished creating the label}%
```

Enable print-mode math functions:

```
    \LetLtxMacro$\LWR@origdollar%
    \catcode`\$=3% math shift
    \LetLtxMacro\(\LWR@origopenparen%
    \LetLtxMacro\)\LWR@origcloseparen%
```

Only enable print-mode display math if are not already inside display math:

```
    \ifbool{LWR@indisplaymathimage}{}{% not in display math
        \LetLtxMacro\[\LWR@origopenbracket%
        \LetLtxMacro\]\LWR@origclosebracket%
        \let\equation\LWR@origequation%
        \let\endequation\LWR@origendequation%
        \csletcs{equation*}{LWR@origequation*}%
        \csletcs{endequation*}{LWR@origendequation*}%
    }% not in display math
```

For chemformula:

```
    \LetLtxMacro\LWR@newsingledollar$%
    \LetLtxMacro\LWR@newsingledollar$% syntax highlighting

}% end of outer-most lateximage
\LWR@traceinfo{lateximage: finished start of environment}%
}% end of \begin{lateximage}
```

\endlateximage When the environment closes:

```
{% start of \end{lateximage}
\LWR@traceinfo{lateximage: starting end of lateximage}%
```

Nested more than one deep?

```
\LWR@traceinfo{lateximage: internal depth was \arabic{LWR@lateximagedepth}}%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{1}%
```

If nesting inside an already existing lateximage, simply record one less level. Uses a lower-level TEX macro due to $\mathcal{AMS}$ \text change of \addtocounter.

```
{%
    \LWR@traceinfo{lateximage: unnesting}%
    \global\advance\c@LWR@lateximagedepth -1\relax%
}%
```

If this is the outer-most lateximage:

```
{% end of outer-most lateximage
```

Finish the lateximage minipage and start a new PDF page:

```
\LWR@traceinfo{lateximage: ending outer-most lateximage}%
    \endLWR@print@minipage%
    \LWR@orignewpage%
    \LWR@print@scriptsize%
```

Close the HTML comment which encapsulated any traces of the lateximage picked up by *pdftotext*:

```
    \LWR@print@vspace*{.5\baselineskip}%
    \LWR@htmlclosecomment%
    \LWR@traceinfo{lateximage: The page after the image is \arabic{page}}%
```

Create a link to the lateximage, allowing its natural height:

```
    \IfBooleanTF{#1}% starred
    {% hash
        \LWR@subinlineimage[#2]{lateximage}%
        {%
            \LWR@ImagesDirectory\OSPathSymbol%
            \LWR@print@mbox{\LWR@hashedname}%
        }{svg}{#4}%
    }% hash
    {% no hash
        \LWR@subinlineimage[#2]{lateximage}%
        {%
            \LWR@ImagesDirectory\OSPathSymbol%
            \LWR@print@mbox{\LWR@ImagesName\theLWR@externalfilecnt}%
        }{svg}{#4}%
    }% no hash
```

Be sure that are doing a paragraph:

```
    \LWR@ensuredoingapar%
```

Close the HTML span which has the *pdftotext* comment and also the link to the `.svg` image:

```
    \LWR@htmltag{/span}%
    \ifbool{HTMLDebugComments}{%
        \LWR@htmlcomment{End of lateximage}%
    }{}%
```

Undo one lateximage level. This is not inside an $\mathcal{AMS}$ `\text`, so regular `\addtocounter` may be used here.

```
    \addtocounter{LWR@lateximagedepth}{-1}%
}% end of outer-most lateximage
\LWR@traceinfo{lateximage: exiting depth is \arabic{LWR@lateximagedepth}}%
\LWR@traceinfo{lateximage: done}%
}%
\catcode`\$=3% math shift
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

Env `lateximage` [⟨<alt> *tag*⟩] [⟨*css style*⟩]

`varwidth` is used to create a box of the natural width of its contents.

```
\NewDocumentEnvironment{lateximage}{s o o o}
    {\begin{varwidth}[b]{\linewidth}}
    {\end{varwidth}}

\end{warpprint}
```

80 center, flushleft, flushright

for HTML output:

```
\begin{warpHTML}
```

Env center Replace center functionality with CSS tags:

```
\renewenvironment*{center}
{
\LWR@forcenewpage
\ifbool{FormatWP}
{\BlockClass[\LWR@print@mbox{text-align:center}]{center}}
{\BlockClass{center}}
}
{\endBlockClass}
```

Env flushright

```
\renewenvironment*{flushright}
{
\LWR@forcenewpage
\ifbool{FormatWP}
{\BlockClass[\LWR@print@mbox{text-align:right}]{flushright}}
{\BlockClass{flushright}}
}
{\endBlockClass}
```

Env flushleft

```
\renewenvironment*{flushleft}
{
\LWR@forcenewpage
\ifbool{FormatWP}
{\BlockClass[\LWR@print@mbox{text-align:left}]{flushleft}}
{\BlockClass{flushleft}}
}
{\endBlockClass}
```

\centering, \raggedleft, and \raggedright usually have no effect on the HTML output, but they may be used to compare with the next token to identify their use at the start of a float. See \LWR@floatalignment.

\centering

```
\newcommand*{\LWR@HTML@centering}{%
\ifbool{HTMLDebugComments}{%
    \LWR@htmlcomment{centering}%
}{}%
}
\LWR@formatted{centering}
```

\raggedleft

```
\newcommand*{\LWR@HTML@raggedleft}{%
\ifbool{HTMLDebugComments}{%
    \LWR@htmlcomment{raggedleft}%
}{}%
}
\LWR@formatted{raggedleft}
```

\raggedright

```
\newcommand*{\LWR@HTML@raggedright}{%
\ifbool{HTMLDebugComments}{%
    \LWR@htmlcomment{raggedright}%
}{}%
}
\LWR@formatted{raggedright}
```

\leftline {⟨*text*⟩}

```
\renewcommand{\leftline}[1]{\begin{flushleft}#1\end{flushleft}}
```

\centerline {⟨*text*⟩}

```
\renewcommand{\centerline}[1]{\begin{center}#1\end{center}}
```

\rightline {⟨*text*⟩}

```
\renewcommand{\rightline}[1]{\begin{flushright}#1\end{flushright}}
```

```
\end{warpHTML}
```

81 Preloaded packages

for HTML output:

```
\begin{warpHTML}
```

If the given package was loaded before or by lwarp, load the lwarp version as well.

\LWR@PreloadedPackage {⟨*packagename*⟩}

```
\newcommand*{\LWR@PreloadedPackage}[1]{%
    \@ifpackageloaded{#1}%
        {%
            \AtBeginDocument{
                \LWR@origRequirePackage{lwarp-#1}%
            }
        }%
        {}%
}
```

If textcomp was loaded before lwarp, perhaps as part of the font-related packages, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{textcomp}
```

If xunicode was loaded before lwarp, perhaps as part of the font-related packages, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{xunicode}
```

If graphics or graphicx were loaded before lwarp, perhaps by xunicode, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{graphics}
\LWR@PreloadedPackage{graphicx}
```

ulem may be preloaded by ctex, ctexart, and related classes.

```
\LWR@PreloadedPackage{ulem}
```

xetexko-vertical may be preloaded by xetexko.

```
\LWR@PreloadedPackage{xetexko-vertical}
```

geometry is preloaded by lwarp, and perhaps by various classes.

```
\LWR@PreloadedPackage{geometry}
```

plext is preloaded by some CJK classes.

```
\LWR@PreloadedPackage{plext}
```

stfloats is preloaded by ltj* classes.

```
\LWR@PreloadedPackage{stfloats}
```

lltjext is preloaded by ltj* classes.

```
\LWR@PreloadedPackage{lltjext}
```

```
\end{warpHTML}
```

82 siunitx

Pkg siunitx The lwarp core passes a few options to siunitx.

fractions Due to *pdftotext* limitations, fraction output is replaced by symbol output for `per-mode` and `quotient-mode`.

⚠ math mode required Some units will require that the expression be placed inside math mode.

NOTE: As of this writing, the siunitx extension for MathJax is not currently hosted at any public CDN, thus siunitx is not usable with MathJax unless a local copy of this extension is created first.

⚠ tabular Tabular `S` columns are rendered as simple `c` columns, and tabular `s` columns are not supported. These may be replaced by `c` columns with each cell contained in `\num` or `\si`.

for HTML output:

```
\begin{warpHTML}
```

Options for siunitx:

```
\newrobustcmd{\LWR@siunitx@textcelsius}{\HTMLentity{deg}C}
\newrobustcmd{\LWR@siunitx@textdegree}{\HTMLentity{deg}}
\newrobustcmd{\LWR@siunitx@textprime}{\HTMLunicode{2032}}
\newrobustcmd{\LWR@siunitx@textdblprime}{\HTMLunicode{2033}}
\newrobustcmd{\LWR@siunitx@textplanckbar}{\text{\textit{\HTMLunicode{0127}}}}

\appto\LWR@restoreorigformatting{%
\renewrobustcmd{\LWR@siunitx@textcelsius}{\text{\ensuremath{^\circ}C}}%
\renewrobustcmd{\LWR@siunitx@textdegree}{\text{\ensuremath{^\circ}}}%
\renewrobustcmd{\LWR@siunitx@textprime}{\text{\ensuremath{^\prime}}}%
\renewrobustcmd{\LWR@siunitx@textdblprime}{\text{\ensuremath{^{\prime\prime}}}}%
\renewrobustcmd{\LWR@siunitx@textplanckbar}{\text{\ensuremath{\hbar}}}%
}

\PassOptionsToPackage{
    detect-mode=true,
    per-mode=symbol,% fraction is not seen by pdftotext
    text-celsius = {\LWR@siunitx@textcelsius},
    text-degree = {\LWR@siunitx@textdegree},
    text-arcminute = {\LWR@siunitx@textprime} ,
    text-arcsecond = {\LWR@siunitx@textdblprime} ,
}{siunitx}

\end{warpHTML}
```

83 Graphics print-mode modifications

83.1 General limitations

⚠ scale

Avoid using the `\includegraphics` `scale` option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

\includegraphics file formats

For `\includegraphics` with `.pdf` or `.eps` files, the user must provide a `.pdf` or `.eps` image file for use in print mode, and also a `.svg`, `.png`, or `.jpg` version of the same image for use in HTML.

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, lwarp will automatically choose the `.pdf` or `.eps` format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a `.pdf` or `.eps` image is referred to with its file extension, the extension will be changed to `.svg` for HTML:

```
\includegraphics{filename.pdf} % uses .svg in html
\includegraphics{filename.eps} % uses .svg in html
```

Prog pdftocairo

PDF to SVG

To convert a PDF image to SVG, use the utility *pdftocairo*:

Enter ⇒ **`pdftocairo -svg filename.pdf`**

Prog lwarpmk pdftosvg

For a large number of images, use *lwarpmk*:

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of filenames)**

Prog lwarpmk epstopdf

Prog epstopdf

epstopdf package

For EPS images converted to PDF using the package epstopdf, use

Enter ⇒ **`lwarpmk pdftosvg *.PDF`**

to convert to SVG images.

DVI latex

When using DVI *latex*, it is necessary to convert EPS to PDF and then to SVG:

Enter ⇒ **`lwarpmk epstopdf *.eps`** **(or a list of filenames)**

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of filenames)**

PNG and JPG

For PNG or JPGwhile using *pdflatex*, *lualatex*, or *xelatex*, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

GIF

GIF files may be used for HTML, but another format must also be provided for print output.

file extension priorities

If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

⚠ graphics vs. graphicx

If using the older graphics syntax, use both optional arguments for `\includegraphics`. A single optional parameter is interpreted as the newer graphicx syntax. Note that viewports are not supported by lwarp — the entire image will be shown.

⚠ viewport

⚠ viewport units

For `\includegraphics`, avoid `px` and % units for width and height, or enclose them inside `warpHTML` environments. For font-proportional image sizes, use `ex` or `em`. For fixed-sized images, use `cm`, `mm`, `in`, `pt`, or `pc`. Use the keys `width=.5\linewidth`, or similar for `\textwidth` or `\textheight` to give fixed-sized images proportional to a 6 by 9 inch text area. Do not use the `scale` option, since it is not well supported by HTML browsers.

options

`\includegraphics` accepts `width` and `height`, `origin`, `rotate` and `scale`, plus new `class` and `alt` keys.

HTML class

With HTML output, `\includegraphics` accepts an optional `class=xyz` keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

HTML `alt` tags

Likewise, the `\includegraphics` `alt` key adds an HTML `alt` tag to an image, and is ignored for print output. If not assigned, each image is given an `alt` tag of "`(image)`".

`\rotatebox`

`\rotatebox` accepts the optional `origin` key.

⚠ browser support

`\rotatebox`, `\scalebox`, and `\reflectbox` depend on modern browser support. The CSS3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike LaTeX, so expect some ugly results for scaling and rotating.

83.2 Print-mode modifications

for PRINT output:

For print output, accept and then discard the new `class` key:

```
\begin{warpprint}
\define@key{Gin}{class}{}
\define@key{Gin}{alt}{}
```

Print-mode additions for the overpic package. See section 339 for the HTML version.

```
\AtBeginDocument{
\@ifpackageloaded{overpic}{
\newcommand*{\overpicfontsize}{12}
\newcommand*{\overpicfontskip}{14}
}{}
}
\end{warpprint}
```

84 xcolor boxes

Pkg xcolor A few new definitions are provided for enhanced HTML colored boxes, and \fcolorbox is slightly modified. Print-mode version are also provided.

Print-mode versions of new xcolor defintions. These are defined inside warpall because they are also used for HTML while inside a lateximage. They are defined \AtBeginDocument so that the xcolor originals may first be loaded and saved for reuse.

The framed versions are modified to allow a background color of none, in which case only the frame is drawn, allowing the background page color to show.

for HTML & PRINT:

```
\begin{warpall}
```

After xparse may have been loaded …

```
\AtBeginDocument{
```

… and *only* if xcolor was loaded:

```
\@ifpackageloaded{xcolor}{
\LWR@traceinfo{patching xcolor}
```

The print version:

\colorboxBlock \colorboxBlock is the same as \colorbox:

```
\LetLtxMacro\colorboxBlock\colorbox
```

The original definition is reused by the new versions:

```
\LetLtxMacro\LWR@orig@print@fcolorbox\fcolorbox
```

\fcolorbox [⟨*framemodel*⟩] {⟨*framecolor*⟩} [⟨*boxmodel*⟩] {⟨*boxcolor*⟩} {⟨*text*⟩}

In print mode, \fcolorbox is modified to accept a background color of none.

(\fcolorbox is particular about its optional arguments, thus the elaborate combinations of \ifthenelse.)

```
\newsavebox{\LWR@colorminipagebox}

\NewDocumentCommand{\LWR@print@fcolorbox}{o m o m +m}{%
\LWR@traceinfo{LWR@print@fcolorbox #2 #4}%
```

Pre-load the contents into an LR box so that they can be used inside a \fcolorbox:

```
\begin{lrbox}{\LWR@colorminipagebox}%
#5%
\end{lrbox}%
```

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a \fcolorbox.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```
\ifstrequal{#4}{none}%
{% #4 none
    \LWR@traceinfo{background is none}%
    {% scope the \colorlet
        \colorlet{LWR@currentcolor}{.}%
        \color{#2}%
        \fbox{%
            \color{LWR@currentcolor}%
            \usebox{\LWR@colorminipagebox}%
        }% fbox
    }% colorlet
}% #4 none
{% #4 not none
\LWR@traceinfo{background not none}%
\IfValueTF{#1}%
{%
    \IfValueTF{#3}%
  {\LWR@orig@print@fcolorbox[#1]{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox[#1]{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
}%
{% no value #1
    \IfValueTF{#3}%
    {\LWR@orig@print@fcolorbox{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
}% no value #1
}% #4 not none
\LWR@traceinfo{LWR@print@fcolorbox done}%
}

\renewcommand*{\fcolorbox}{\LWR@print@fcolorbox}
```

\fcolorboxBlock [⟨*framemodel*⟩] {⟨*framecolor*⟩} [⟨*boxmodel*⟩] {⟨*boxcolor*⟩} {⟨*text*⟩}

In print mode, \fcolorboxBlock is the same as \fcolorbox.

```
\newcommand*{\LWR@print@fcolorboxBlock}{\LWR@print@fcolorbox}
\newcommand*{\fcolorboxBlock}{\LWR@print@fcolorboxBlock}
```

Env fcolorminipage [⟨*1:framemodel*⟩] {⟨*2:framecolor*⟩} [⟨*3:boxmodel*⟩] {⟨*4:boxcolor*⟩} [⟨*5:align*⟩] [⟨*6:height*⟩] [⟨*7:inner-align*⟩] {⟨*8:width*⟩}

In print mode, becomes a \fcolorbox containing a minipage:

```
\NewDocumentEnvironment{LWR@print@fcolorminipage}{o m o m O{c} O{} o m}
{%
\LWR@traceinfo{*** fcolorminipage: #2 #4 #8}%
```

Pre-load the contents into an LR box so that they can be used inside a \fcolorbox:

```
\begin{lrbox}{\LWR@colorminipagebox}%
```

If inner alignment is not given, use the outer alignment instead:

```
\IfValueTF{#7}%
{\begin{minipage}[#5][#6][#7]{#8}}%
{\begin{minipage}[#5][#6][#5]{#8}}%
}%
{%
\end{minipage}%
\end{lrbox}%
\LWR@traceinfo{*** starting end fcolorminipage #1 #2 #3 #4 #8}%
```

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a \fcolorbox.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```
\ifstrequal{#4}{none}%
{% #4 none
    {% scope the \colorlet
        \colorlet{LWR@currentcolor}{.}%
        \color{#2}%
        \fbox{%
            \color{LWR@currentcolor}%
            \usebox{\LWR@colorminipagebox}%
        }% fbox
    }% colorlet
}% #4 none
{% #4 not none
    \IfValueTF{#1}%
    {%
    \IfValueTF{#3}%
   {\LWR@orig@print@fcolorbox[#1]{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox[#1]{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
    }%
    {% no value #1
    \IfValueTF{#3}%
    {\LWR@orig@print@fcolorbox{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
    }% no value #1
}% #4 not none
\LWR@traceinfo{*** finished end fcolorminipage}%
}

\newenvironment*{fcolorminipage}
    {\LWR@print@fcolorminipage}
    {\endLWR@print@fcolorminipage}

\LWR@traceinfo{xcolor patches done}
}{}% xcolor loaded
}% AtBeginDocument
```

```
\end{warpall}
```

85 chemmacros environments

\makepolymerdelims and redox reactions must be enclosed in a lateximage during HTML output. These environments are provided here in print mode, and in the chemmacros code in HTML mode, as a high-level semantic syntax which automatically embeds the contents in a lateximage with an appropriate alt tag.

for PRINT output:

```
\begin{warpprint}

\AtBeginDocument{
\@ifpackageloaded{chemmacros}{
```

Env polymerdelims

```
\DeclareDocumentEnvironment{polymerdelims}{}
    {}{}
```

Env redoxreaction {⟨*space above*⟩} {⟨*space below*⟩}

For print output, extra space is include above and below the image, and a lateximage is not necessary. This extra space must be enforced, even inside a float, so zero-width rules are used.

For the HTML version, see section 164.4.

```
\DeclareDocumentEnvironment{redoxreaction}{m m}
    {\rule{0pt}{#1}}{\rule[-#2]{0pt}{#2}}

}{}% chemmacros
}% AtBeginDocument

\end{warpprint}
```

86 cleveref

Pkg cleveref cleveref package is used as-is with minor patches.

⚠ cleveref page numbers cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for \cpageref and \cpagerefrange. This phrase includes \cpagerefFor, which defaults to “for”.

Ex:

```
    \cpageref{tab:first,tab:second}
 in html becomes:
```
"pages **for** table 4.1 and **for** table 4.2"

See `\cpagerefFor` at page 535 to redefine the message which is printed for page number references.

loading order

cleveref and the following associated macro patches are automatically preloaded at the end of the preamble via `\AtEndPreamble` and `\AfterEndPreamble`. This is done because the HTML conversion requires cleveref. The user's document may not require cleveref, thus the user may never explicitly load it, so during HTML output lwarp loads it last. If the user's document preamble uses cleveref options, or functions such as `\crefname`, then cleveref may be loaded in the user's preamble near the end, and lwarp's additional loading of cleveref will have no effect.

Table 12 on page 457 shows the data structure of the label/reference system as revised by lwarp and cleveref.

A few patches allow cleveref to work as-is:

for HTML output:

```
\begin{warpHTML}
```

`\AtEndPreable` forces cleveref to be loaded last:

```
\AtEndPreamble{
\RequirePackage{cleveref}
}
```

The following patches are applied after cleveref has loaded, and after `\AtBeginDocument`. Print-mode versions are not required since they all come down to `\ref` eventually, and `\ref` has a print-mode version.

```
\AfterEndPreamble{
\LWR@traceinfo{Patching cleveref.}
```

`\@@@setcref` {⟨*kindofref*⟩} {⟨*label*⟩}

`\@templabel` becomes the section number.

```
\def\LWR@orig@@@setcref#1#2{\cref@getlabel{#2}{\@templabel}#1{\@templabel}{}{}}%

\ifdefequal{\@@setcref}{\LWR@orig@@@setcref}{% before v0.21
    \renewcommand*{\@@setcref}[2]{#1{\ref{#2}}{}{}}
}{
    \ifdefequal{\@@@setcref}{\LWR@orig@@@setcref}{% as of v0.21
        \renewcommand*{\@@@setcref}[2]{#1{\ref{#2}}{}{}}
    }{
        \PackageWarning{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\cref\space will fail.
        }%
```

```
    }
}
```

`\@@@setcrefrange` {⟨*text*⟩} {⟨*label*⟩} {⟨*label*⟩}

```
\def\LWR@orig@@@setcrefrange#1#2#3{%
  \cref@getlabel{#2}{\@labela}%
  \cref@getlabel{#3}{\@labelb}%
  #1{\@labela}{\@labelb}{}{}{}{}}%

\ifdefequal{\@@setcrefrange}{\LWR@orig@@@setcrefrange}{
    \renewcommand{\@@setcrefrange}[3]{%
        #1{\ref{#2}}{\ref{#3}}{}{}{}{}%
    }
}{
    \ifdefequal{\@@@setcrefrange}{\LWR@orig@@@setcrefrange}{
        \renewcommand{\@@@setcrefrange}[3]{%
            #1{\ref{#2}}{\ref{#3}}{}{}{}{}%
        }
    }{
        \PackageWarning{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\crefrange\space will fail.
        }
    }
}

```

`\cpagerefFor` Redefinable word between “page(s)” and the page numbers.

```
\newcommand*{\cpagerefFor}{for}
```

`\@@@setcpageref` {⟨*typeofref*⟩} {⟨*label*⟩}, where typeofref is “page” or “pages”

```
\def\LWR@orig@@setcpageref#1#2{% before v0.21
  \cref@getpageref{#2}{\@temppage}#1{\@temppage}{}{}}%

\def\LWR@orig@@@setcpageref#1#2{% as of v0.21
  \cpageref@getlabel{#2}{\@temppage}#1{\@temppage}{}{}}%

\ifdefequal{\@@setcpageref}{\LWR@orig@@setcpageref}{
    \renewcommand*{\@@setcpageref}[2]{%
        #1{\cpagerefFor\ \cref{#2}}{}{}%
    }
}{
    \ifdefequal{\@@@setcpageref}{\LWR@orig@@@setcpageref}{
        \renewcommand*{\@@@setcpageref}[2]{%
            #1{\cpagerefFor\ \cref{#2}}{}{}%
        }
    }
    {
        \PackageWarning{lwarp-cleveref}{
```

```
            Unknown version of cleveref.
            \protect\cpageref\space will fail.
        }
    }
}

\def\LWR@orig@@setcpagerefrange#1#2#3{% before v0.21
  \cref@getpageref{#2}{\@pagea}%
  \cref@getpageref{#3}{\@pageb}%
  #1{\@pagea}{\@pageb}{}{}{}{}%

\def\LWR@orig@@@setcpagerefrange#1#2#3{% as of v0.21
  \cpageref@getlabel{#2}{\@pagea}%
  \cpageref@getlabel{#3}{\@pageb}%
  #1{\@pagea}{\@pageb}{}{}{}{}%

\ifdefequal{\@@setcpagerefrange}{\LWR@orig@@setcpagerefrange}{
    \renewcommand*{\@@setcpagerefrange}[3]{%
        #1{\cpagerefFor\ \cref{#2}}{\cref{#3}}{}{}{}{}%
    }
}{
    \ifdefequal{\@@@setcpagerefrange}{\LWR@orig@@@setcpagerefrange}{
        \renewcommand*{\@@@setcpagerefrange}[3]{%
            #1{\cpagerefFor\ \cref{#2}}{\cref{#3}}{}{}{}{}%
        }
    }
    {
        \PackageWarning{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\cpagerefrange\space will fail.
        }
    }
}

}% AfterEndPreamble
```

Remember and patch some label-related defintions. These will be further encased and patched by other packages later.

`\label` and `\pageref` do NOT change their behavior according to print or HTML output, and thus do not use the `\LWR@formatted` system.

```
\LetLtxMacro\LWR@orig@label\label
\RenewDocumentCommand{\label}{}{\LWR@new@label}

\LetLtxMacro\LWR@orig@pageref\pageref
\RenewDocumentCommand{\pageref}{}{\LWR@new@pageref}
\end{warpHTML}
```

87 `picture` environment

Env `picture` The `picture` environment is enclosed inside a `\lateximage`.

for HTML output:
```
\begin{warpHTML}
```

Env `picture`

```
\BeforeBeginEnvironment{picture}{\begin{lateximage}[(picture)]}

\AfterEndEnvironment{picture}{\end{lateximage}}
```

```
\end{warpHTML}
```

88 Minipages and Boxes

A css flexbox is used for minipages and parboxes, allowing external and internal vertical positioning.

⚠ inline — A line of text with an inline `minipage` or `\parbox` will have the `minipage` or `\parbox` placed onto its own line, because a paragraph is a block element and cannot be made `inline-block`.

placement — `minipages` and `\parboxes` will be placed side-by-side in HTML unless you place a `\newline` between them.

side-by-side — Side-by-side `minipages` may be separated by `\quad`, `\qquad`, `\enskip`, `\hspace`, `\hfill`, or a `\rule`. When inside a `center` environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side `minipages` and these spacing commands, but not at the start or end of the paragraph.

⚠ minipage in a span — There is limited support for `minipages` inside an HTML . An HTML cannot appear inside a . While in a , `minipages`, and `\parboxes`, and any enclosed lists have limited HTML tags, resulting in an "inline" format, without markup except for HTML breaks. Use `\newline` or `\par` for an HTML break.

⚠ minipage size — When using `\linewidth`, `\textwidth`, and `\textheight`, widths and heights in HTML are scaled proportionally to a 6×9 inch text area, and inside a `multicols` `\linewidth` is divided by the specified number of columns.

if width is `\linewidth` — If a `minipage` or `\parbox` is assigned a width of exactly `\linewidth`, in HTML it is automatically given no HTML width, thus allowed to fill the line as needed, similar to how it appears in print output.

full-width if HTML — A new macro `\minipagefullwidth` requests that, during HTML output, the next single `minipage` or `\parbox` be generated without an HTML `width` attribute, allowing it to be the full width of the display rather than the declared print-output width. This may be useful where the printed version's width makes no sense in HTML.

⚠ `tabular`, `multicols` — Inside a `tabular` or `multicols` environment, where the width depends on the browser window, `\minipagefullwidth` is effectively used by default for every `minipage` or `\parbox` inside the environment. `\UseMinipageWidths` may be used to tell lwarp to honor the specified widths of all following `minipages` and `\parboxes` until the end of

`\UseMinipageWidths`
`\IgnoreMinipageWidths`

the local scope, and \IgnoreMinipageWidths may be used to tell lwarp to ignore the specified widths.

⚠ text alignment Nested minipages adopt their parent's text alignment in HTML, whereas in regular LaTeX PDF output they do not. Use a flushleft or similar environment in the child minipage to force a text alignment.

for HTML output:
```
\begin{warpHTML}
```

88.1 Counters and lengths

Ctr LWR@minipagedepth Used to only reset the line width at the outermost minipage.

```
\newcounter{LWR@minipagedepth}
\setcounter{LWR@minipagedepth}{0}
```

Len \LWR@minipagewidth Used to convert the width into printable units.

```
\newlength{\LWR@minipagewidth}
```

Len \LWR@minipageheight Used to convert the height into printable units.

```
\newlength{\LWR@minipageheight}
```

88.2 Footnote handling

Also see section 58 for other forms of footnotes. Minipage footnotes are gathered in section 58.5, and then placed into the document in section 88.3.

88.3 Minipage handling

Bool LWR@minipagefullwidth Should the next minipage have no HTML width?

```
\newbool{LWR@minipagefullwidth}
\boolfalse{LWR@minipagefullwidth}
```

Bool LWR@forceminipagefullwidth Should the next minipage have no HTML width? Used to force full width for all minipages in an environment such as tabular or multicols, where the actual width depends on the browser width. Controlled by \useminipagewidths and \ignoreminipagewidths.

```
\newbool{LWR@forceminipagefullwidth}
\boolfalse{LWR@forceminipagefullwidth}
```

\minipagefullwidth Requests that the next minipage have no width tag in HTML:

for HTML output:
```
\newcommand*{\minipagefullwidth}{\global\booltrue{LWR@minipagefullwidth}}
```

\UseMinipageWidths Locally requests that minipage widths be honored.

```
\newcommand*{\UseMinipageWidths}{\boolfalse{LWR@forceminipagefullwidth}}
```

\IgnoreMinipageWidths Locally requests that minipage widths be honored.

```
\newcommand*{\IgnoreMinipageWidths}{\booltrue{LWR@forceminipagefullwidth}}
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand*{\minipagefullwidth}{}
\newcommand*{\UseMinipageWidths}{}
\newcommand*{\IgnoreMinipageWidths}{}
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

Bool LWR@minipagethispar Has a minipage been seen this paragraph? If true, prevents paragraph tags around horizontal space between minipages.

```
\newbool{LWR@minipagethispar}
\boolfalse{LWR@minipagethispar}
```

Env minipage [⟨*vert position*⟩] [⟨*height*⟩] [⟨*inner vert position*⟩] {⟨*width*⟩}

The vertical positions may be 'c', 't', or 'b'. The inner position may also be 's'.

When using \linewidth, \textwidth, or \textheight, these are scaled proportionally to a 6×9 inch text area.

```
\NewDocumentEnvironment{LWR@HTML@sub@minipage}{m m m m}
{%
\LWR@traceinfo{minipage}%
```

Temporarily open a group, in which width and height is computed based on a virtual page size instead of the extra-large PDF page used during HTML tag generation.

The following used to be an actual LaTeX minipage.

```
\begingroup
```

Compute width, adjusted for frames:

```
\setlength{\LWR@minipagewidth}{#4}%
\ifthenelse{\cnttest{\value{LWR@minipagedepth}}{=}{0}}{%
```

Only create a new page if not yet nested:

```
    \LWR@orignewpage%
```

Adjust virtual page size:

```
    \addtolength{\LWR@minipagewidth}{3em}% room for frames
    \setlength{\linewidth}{6in}%
    \setlength{\textwidth}{6in}%
    \setlength{\textheight}{9in}%
}{}%
\LWR@traceinfo{computed width is \LWR@printlength{\LWR@minipagewidth}}%
```

Compute height:

```
\setlength{\LWR@minipageheight}{\textheight}% default unless specified
\ifblank{#2}{}{\setlength{\LWR@minipageheight}{#2}}%
```

Track nesting depth:

```
\addtocounter{LWR@minipagedepth}{1}%
```

LaTeX wants to start a paragraph for the virtual minipage, then start a paragraph again for the contents of the minipage, so cancel the paragraph tag handling until the minipage has begun.

```
\ifbool{FormatWP}{\newline}{}%
\LWR@stoppars%
```

If `FormatWP`, add a text frame:

```
\ifbool{FormatWP}{%

\addtocounter{LWR@thisautoidWP}{1}%
\LWR@htmltag{%
    div id="\LWR@print@mbox{autoidWP-\arabic{LWR@thisautoidWP}}" %
    class="wpminipage"%
}%

}{}%
```

Create the tag with optional alignment style:

```
\LWR@traceinfo{minipage: creating div class}%
\LWR@htmltag{div class="minipage" style="%
\ifthenelse{\equal{#1}{t}}{\LWR@print@mbox{vertical-align:bottom} ; }{}%
\ifthenelse{\equal{#1}{c}}{\LWR@print@mbox{vertical-align:middle} ; }{}%
\ifthenelse{\equal{#1}{b}}{\LWR@print@mbox{vertical-align:top} ; }{}%
\ifthenelse{\equal{#3}{t}}{\LWR@print@mbox{justify-content:flex-start} ; }{}%
\ifthenelse{\equal{#3}{c}}{\LWR@print@mbox{justify-content:center} ; }{}%
\ifthenelse{\equal{#3}{b}}{\LWR@print@mbox{justify-content:flex-end} ; }{}%
\ifthenelse{\equal{#3}{s}}{\LWR@print@mbox{justify-content:space-between} ; }{}%
```

Print the width and optional height styles:

```
\LWR@traceinfo{minipage: about to print the width of \LWR@printlength{\LWR@minipagewidth}}%
\ifbool{LWR@minipagefullwidth}%
{\global\boolfalse{LWR@minipagefullwidth}}%
{%
    \ifbool{LWR@forceminipagefullwidth}%
```

```
        {}%
        {%
            \ifthenelse{\lengthtest{#4}=\linewidth}%
                {}%
                {width:\LWR@printlength{\LWR@minipagewidth} ; }%
        }%
}%
\LWR@traceinfo{minipage: about to print the height}%
\ifblank{#2}{}{height:\LWR@printlength{\LWR@minipageheight} ; }%
"}%
```

Finish with an empty line to start the contents on a new line.

```

% The preceding empty line is required.
```

Set the user-accessible line and text width and height values inside the virtual minipage. These do not affect the actual size of the PDF output, but are used by any reference to `\linewidth`, etc. inside the virtual minipage being created here.

```
\setlength{\linewidth}{#4}% the original width
\setlength{\textwidth}{6in}%
\setlength{\textheight}{9in}%
```

`\raggedright` cancels hyphenation, which will be done by HTML instead.

```
\LWR@print@raggedright%
```

Set minipage footnotes:

```
\def\@mpfn{mpfootnote}%
\def\thempfn{\thempfootnote}\c@mpfootnote\z@%
\let\@footnotetext\@mpfootnotetext%
```

Resume paragraph tag handling for the contents of the minipage:

```
\LWR@startpars%
\ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{%

=== begin minipage ===

}{}%
\LWR@traceinfo{minipage: finished starting the minipage}%
}% finished \minipage
{% \endminipage
```

Print pending minipage footnotes:

```
\LWR@printpendingmpfootnotes%
```

End the environment with closing tag:

```
\ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{%

```

```
=== end minipage ===

}{}%
\LWR@stoppars%
```

The following used to be an actual LaTeX minipage.

```
\endgroup%

\ifbool{FormatWP}{%

\LWR@htmlelementend{div}%

}{}%
\LWR@htmldivclassend{minipage}%

\addtocounter{LWR@minipagedepth}{-1}%
\LWR@startpars%
\ifbool{FormatWP}{\newline}{}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
\LWR@traceinfo{LWR@minipage: done}%
}

\NewDocumentEnvironment{LWR@HTML@minipage}{O{t} O{} O{t} m}
    {\LWR@HTML@sub@minipage{#1}{#2}{#3}{#4}}
    {\endLWR@HTML@sub@minipage}

\LWR@formattedenv{minipage}
```

88.4 \parbox, \mbox, \makebox, \framebox, \fbox, \raisebox

for HTML output:

\parbox [⟨*pos*⟩] [⟨*height*⟩] [⟨*inner-pos*⟩] {⟨*width*⟩} {⟨*text*⟩}

A parbox uses the minipage code:

```
\NewDocumentCommand{\LWR@HTML@parbox}{O{t} O{} O{t} m +m}
{
\LWR@traceinfo{parbox of width #4}%
\begin{minipage}[#1][#2][#3]{#4}%
#5
\end{minipage}%
}

\LWR@formatted{parbox}
```

\mbox {⟨*text*⟩} Nullified for HTML.

```
\newcommand*{\LWR@HTML@mbox}[1]{#1}

\LWR@formatted{mbox}
```

\makebox (⟨*(*⟩)posn) [⟨*width*⟩] [⟨*pos*⟩] {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@HTML@makebox}{d() o o m}{%
```

Check for the optional width:

```
\IfValueTF{#2}%
{%
```

Check for the horizontal text alignment. For stretched, the best HTML can do is `justified` alignment.

```
    {% scope
    \def\LWR@align{center}%
    \ifstrequal{#3}{l}{\def\LWR@align{left}}{}%
    \ifstrequal{#3}{r}{\def\LWR@align{right}}{}%
    \ifstrequal{#3}{s}{\def\LWR@align{justify}}{}%
```

To print the `width` argument:

```
    \setlength{\LWR@tempwidth}{#2}%
```

`inline-block` allows `width` and `text-alignment` to be used in a .

```
    \InlineClass[%
        \LWR@print@mbox{display:inline-block} ; %
        \LWR@print@mbox{text-align}:\LWR@align\ ; %
        width:\LWR@printlength{\LWR@tempwidth}%
    ]%
    {makebox}%


    {#4}%
    }% scope
}%
```

Without a width argument, the text is simply used inline:

```
{#4}% no width
}

\LWR@formatted{makebox}
```

\framebox [⟨*width*⟩] [⟨*pos*⟩] {⟨*text*⟩}

```
\LetLtxMacro\LWR@origframebox\framebox
```

```
10523
10524 \NewDocumentCommand{\LWR@HTML@framebox}{o o m}{%
10525 \fbox{\makebox[#1][#2]{#3}}%
10526 }
10527
10528 \LWR@formatted{framebox}
```

\LWR@forceminwidth {⟨*legth*⟩}

Sets \LWR@atleastonept to be at least 1pt.

```
10529 \newlength{\LWR@atleastonept}
10530
10531 \newcommand*{\LWR@forceminwidth}[1]{%
10532 \setlength{\LWR@atleastonept}{#1}%
10533 \ifthenelse{%
10534     \lengthtest{\LWR@atleastonept>0pt}\AND%
10535     \lengthtest{\LWR@atleastonept<1pt}%
10536 }%
10537     {\setlength{\LWR@atleastonept}{1pt}}%
10538     {}%
10539 }
```

\LWR@fboxstyle Prints the HTML attributes for a black border and padding.

\LWR@forceminwidth must be used first in order to set the border width.

```
10540 \newcommand*{\LWR@fboxstyle}{%
10541 \LWR@findcurrenttextcolor%
10542 border:\LWR@printlength{\LWR@atleastonept} solid \LWR@origpound\LWR@tempcolor ; %
10543 padding:\LWR@printlength{\fboxsep} ; %
10544 color:\LWR@origpound\LWR@tempcolor%
10545 }
```

\fbox {⟨*text*⟩}

Creates a framed inline span enclosing the text.

Create a new HTML version, but don't use it until after xcolor may have loaded:

```
10546 \newcommand{\LWR@HTML@fbox}[1]{%
10547 \LWR@traceinfo{HTML fbox}%
10548 \LWR@forceminwidth{\fboxrule}%
10549 \InlineClass[%
10550 \LWR@fboxstyle%
10551 ]{fbox}{#1}%
10552 }
```

xcolor \lets things to \fbox when it is loaded, and this must remain even for HTML output while in a lateximage, so \fbox is not modified until \AtBeginDocument:

```
10553 \AtBeginDocument{\LWR@formatted{fbox}}
```

\fboxBlock {⟨*text*⟩} Creates a framed HTML of the text.

First, a print-mode version. This is newly defined for print mode, so it is defined inside warpall.

for HTML & PRINT:

```
\end{warpHTML}
\begin{warpall}
\let\fboxBlock\fbox
\end{warpall}

\begin{warpHTML}
```

for HTML output: Next, an HTML version:

```
\newcommand{\LWR@HTML@fboxBlock}[1]{%
\LWR@forceminwidth{\fboxrule}%
\begin{BlockClass}[%
\LWR@fboxstyle%
]{fboxBlock}
#1
\end{BlockClass}
}

\LWR@formatted{fboxBlock}

\end{warpHTML}
```

Env fminipage [⟨*align*⟩] [⟨*height*⟩] [⟨*align*⟩] {⟨*width*⟩}

Creates a framed HTML around its contents.

for HTML & PRINT: Print version:

```
\begin{warpall}

\newsavebox{\LWR@fminipagebox}

\NewDocumentEnvironment{LWR@print@fminipage}{O{t} o O{t} m}
{%
```

An outer minipage will be used for vertical alignment. An inner minipage will be framed with \fbox.

If the optional inner alignment is not given, use the outer instead:

```
\IfValueTF{#3}%
{\def\LWR@thisalign{#3}}
{\def\LWR@thisalign{#1}}%
```

Form the outer minipage depending on whether a height was given. Make the outer minipage larger to compensate for the frame.

```
\IfValueTF{#2}%
{\minipage[#1][#2+2\fboxsep+2\fboxrule][\LWR@thisalign]{#4+2\fboxsep+2\fboxrule}}%
{\minipage[#1]{#4+2\fboxsep+2\fboxrule}}%
```

Capture the contents of the environment:

```
\begin{lrbox}{\LWR@fminipagebox}%
```

Nest the contents inside an inner minipage of the desired size:

```
\IfValueTF{#2}%
{\minipage[#1][#2][\LWR@thisalign]{#4}}%
{\minipage[#1]{#4}}%
}
{%
```

Close the inner minipage and the LR box with the contents:

```
\endminipage%
\end{lrbox}%
```

Create a frame around the contents of the environment:

```
\fbox{\usebox{\LWR@fminipagebox}}%
```

The entire thing is placed inside the outer minipage:

```
\endminipage%
}

\LetLtxMacro\fminipage\LWR@print@fminipage
\LetLtxMacro\endfminipage\endLWR@print@fminipage
% \newenvironment{fminipage}{\LWR@print@fminipage}{\endLWR@print@fminipage}

\end{warpall}
```

for HTML output:

```
\ifLWR@isHTML
\begin{warpHTML}

\NewDocumentEnvironment{LWR@HTML@fminipage}{O{t} o O{t} m}
{%
\LWR@traceinfo{fminipage #1 #2 #3 #4}%
\LWR@forceminwidth{\fboxrule}%
\setlength{\LWR@tempwidth}{#4}%
\IfValueT{#2}{\setlength{\LWR@tempheight}{#2}}%


\LWR@stoppars%


\begin{BlockClass}[%
\LWR@fboxstyle ; %
\IfValueT{#2}{height:\LWR@printlength{\LWR@tempheight} ; }%
width:\LWR@printlength{\LWR@tempwidth}%
]{fminipage}%
}
{%
\end{BlockClass}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
\LWR@traceinfo{fminipage done}%
}

\LWR@formattedenv{fminipage}

\end{warpHTML}
```

`\raisebox` `{⟨raiselen⟩}` `[⟨height⟩]` `[⟨depth⟩]` `{⟨text⟩}`

```
\begin{warpHTML}

\NewDocumentCommand{\LWR@HTML@raisebox}{m o o m}{%
#4%
}

\LWR@formatted{raisebox}

\end{warpHTML}
```

89 Direct formatting

⚠ `\bfseries`, etc. `\textbf`, etc. are supported, but `\bfseries`, etc. work only in some situations.

⚠ HTML special chars &, <, and > have special meanings in HTML. If `\&`, `\textless`, and `\textgreater` are used, proper HTML entities will be used, but there may be HTML parsing problems if these special characters occur unescaped in program listings or other verbatim text.

program listings For program listings, the listings package is supported, and its `literate` option is used to convert &, <, and > to proper HTML entities.

verbatim The various `verbatim`-related environments do not convert &, <, and >, so care must be taken to avoid accidentally including valid HTML code inside these environments. Adding a space on either side may be sufficient.

For high-level block and inline custom CSS classes, see section 51.9.

for HTML output:

```
\begin{warpHTML}
```

`\emph` `{⟨text⟩}`

```
\DeclareRobustCommand{\LWR@HTML@emph}[1]{%
    {%
        \itshape%
        \LWR@htmlspan{em}{#1}%
    }%
}
```

```
\LWR@formatted{emph}

\DeclareRobustCommand{\LWR@null@emph}[1]{#1}
```

\textmd {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textmd}[1]{%
    {%
        \mdseries%
        \InlineClass(font-weight:normal){textmd}{#1}%
    }%
}
\LWR@formatted{textmd}

\DeclareRobustCommand{\LWR@null@textmd}[1]{#1}
```

\textbf {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textbf}[1]{%
    {%
        \bfseries%
        \LWR@htmlspan{b}{#1}%
    }%
}
\LWR@formatted{textbf}

\DeclareRobustCommand{\LWR@null@textbf}[1]{#1}
```

\textrm {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textrm}[1]{%
    {%
        \rmfamily%
        \InlineClass(font-family:serif){textrm}{#1}%
    }%
}
\LWR@formatted{textrm}

\DeclareRobustCommand{\LWR@null@textrm}[1]{#1}
```

\textsf {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textsf}[1]{%
    {%
        \sffamily%
        \InlineClass(font-family:sans){textsf}{#1}%
    }%
}
\LWR@formatted{textsf}

\DeclareRobustCommand{\LWR@null@textsf}[1]{#1}
```

\texttt {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@texttt}[1]{%
    {%
        \ttfamily%
        \LWR@htmlspan{kbd}{#1}%
    }%
}
\LWR@formatted{texttt}

\DeclareRobustCommand{\LWR@null@texttt}[1]{#1}
```

\textup {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textup}[1]{%
    {%
        \upshape%
        \InlineClass(font-style:normal){textup}{#1}%
    }%
}
\LWR@formatted{textup}

\DeclareRobustCommand{\LWR@null@textup}[1]{#1}
```

\textit {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textit}[1]{%
    {%
        \itshape%
        \LWR@htmlspan{i}{#1}%
    }%
}
\LWR@formatted{textit}

\DeclareRobustCommand{\LWR@null@textit}[1]{#1}
```

\textsc {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textsc}[1]{%
    {%
        \scshape%
        \InlineClass(
            font-variant: small-caps ;
            font-variant-numeric: oldstyle-nums ;
        ){textsc}{#1}%
    }%
}
\LWR@formatted{textsc}

\DeclareRobustCommand{\LWR@null@textsc}[1]{#1}
```

\textsi {⟨*text*⟩}

```
\@ifundefined{textsi}{
    \LetLtxMacro\LWR@print@textsi\LWR@print@textsc
}{}

\DeclareRobustCommand{\LWR@HTML@textsi}[1]{%
    {%
        \sishape%
        \InlineClass(
            font-style: italic;
            font-variant: small-caps ;
            font-variant-numeric: oldstyle-nums ;
        ){textsi}{#1}%
    }%
}
\LWR@formatted{textsi}

\DeclareRobustCommand{\LWR@null@textsi}[1]{#1}
```

`\textsl` {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textsl}[1]{%
    {%
        \slshape%
        \InlineClass(font-style:oblique){textsl}{#1}%
    }%
}
\LWR@formatted{textsl}

\DeclareRobustCommand{\LWR@null@textsl}[1]{#1}
```

`\textnormal` {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textnormal}[1]{\textmd{\textrm{\textup{#1}}}}
\LWR@formatted{textnormal}

\DeclareRobustCommand{\LWR@null@textnormal}[1]{#1}

\DeclareRobustCommand{\LWR@null@rmfamily}{}
\DeclareRobustCommand{\LWR@null@sffamily}{}
\DeclareRobustCommand{\LWR@null@ttfamily}{}
\DeclareRobustCommand{\LWR@null@bfseries}{}
\DeclareRobustCommand{\LWR@null@mdseries}{}
\DeclareRobustCommand{\LWR@null@upshape}{}
\DeclareRobustCommand{\LWR@null@slshape}{}
\DeclareRobustCommand{\LWR@null@scshape}{}
\DeclareRobustCommand{\LWR@null@itshape}{}
\DeclareRobustCommand{\LWR@null@normalfont}{}


\DeclareRobustCommand{\LWR@null@em}{}
```

`\LWR@nullfonts` Removes formatting during filename operations, file references, and HTML comments.

⚠ Use only inside a group.

The following are *not* made robust, since they must be expanded to their nullified versions.

```
\catcode`\$=\active% redefining $ below
\catcode`\_=12% redefining \_ below
\newcommand*{\LWR@nullfonts}{%
\LetLtxMacro\emph\LWR@null@emph%
\LetLtxMacro\textmd\LWR@null@textmd%
\LetLtxMacro\textbf\LWR@null@textbf%
\LetLtxMacro\textrm\LWR@null@textrm%
\LetLtxMacro\textsf\LWR@null@textsf%
\LetLtxMacro\texttt\LWR@null@texttt%
\LetLtxMacro\textup\LWR@null@textup%
\LetLtxMacro\textit\LWR@null@textit%
\LetLtxMacro\textsc\LWR@null@textsc%
\LetLtxMacro\textsi\LWR@null@textsi%
\LetLtxMacro\textsl\LWR@null@textsl%
\LetLtxMacro\textnormal\LWR@null@textnormal%
\LetLtxMacro\rmfamily\LWR@null@rmfamily%
\LetLtxMacro\sffamily\LWR@null@sffamily%
\LetLtxMacro\ttfamily\LWR@null@ttfamily%
\LetLtxMacro\bfseries\LWR@null@bfseries%
\LetLtxMacro\mdseries\LWR@null@mdseries%
\LetLtxMacro\upshape\LWR@null@upshape%
\LetLtxMacro\slshape\LWR@null@slshape%
\LetLtxMacro\scshape\LWR@null@scshape%
\LetLtxMacro\sishape\LWR@null@sishape%
\LetLtxMacro\itshape\LWR@null@itshape%
\LetLtxMacro\normalfont\LWR@null@normalfont%
\LetLtxMacro\em\LWR@null@em%
```

Various built-in symbols.

```
\renewcommand*{\$}{-}%
\renewcommand*{\%}{-}%
\renewcommand*{\_}{-}%
\renewcommand*{\}}{-}%
\renewcommand*{\{}{-}%
\renewcommand*{\&}{and}%
\renewcommand*{\#}{-}%
\renewcommand*{\,}{-}%
\renewcommand*{~}{-}%
\renewcommand*{\^}[1]{-}%
\renewcommand*{\~}[1]{-}%
\renewcommand*{\newline}{-}%
\renewcommand*{\textasciicircum}{-}%
\renewcommand*{\textasciitilde}{-}%
\renewcommand*{\textasteriskcentered}{-}%
\renewcommand*{\textbackslash}{-}%
\renewcommand*{\textbar}{-}%
\renewcommand*{\textbardbl}{-}%
\renewcommand*{\textbigcircle}{-}%
```

```
\renewcommand*{\textbraceleft}{-}%
\renewcommand*{\textbraceright}{-}%
\renewcommand*{\textbullet}{-}%
\renewcommand*{\textcopyright}{-}%
\renewcommand*{\textdagger}{-}%
\renewcommand*{\textdaggerdbl}{-}%
\renewcommand*{\textdollar}{-}%
\renewcommand*{\textellipsis}{-}%
\renewcommand*{\textemdash}{-}%
\renewcommand*{\textendash}{-}%
\renewcommand*{\textexclamdown}{-}%
\renewcommand*{\textgreater}{-}%
\renewcommand*{\textless}{-}%
\renewcommand*{\textordfeminine}{-}%
\renewcommand*{\textordmasculine}{-}%
\renewcommand*{\textparagraph}{-}%
\renewcommand*{\textperiodcentered}{-}%
\renewcommand*{\textpertenthousand}{-}%
\renewcommand*{\textperthousand}{-}%
\renewcommand*{\textquestiondown}{-}%
\renewcommand*{\textquotedblleft}{-}%
\renewcommand*{\textquotedblright}{-}%
\renewcommand*{\textquoteleft}{-}%
\renewcommand*{\textquoteright}{-}%
\renewcommand*{\textregistered}{-}%
\renewcommand*{\textsection}{-}%
\renewcommand*{\textsterling}{-}%
\renewcommand*{\texttrademark}{-}%
\renewcommand*{\textunderscore}{-}%
\renewcommand*{\textvisiblespace}{-}%
\renewcommand*{\copyright}{-}%
\renewcommand*{\dag}{-}%
\renewcommand*{\ddag}{-}%
\renewcommand*{\dots}{-}%
\renewcommand*{\P}{-}%
\renewcommand*{\pounds}{-}%
\renewcommand*{\S}{-}%
\renewcommand*{\aa}{a}%
\renewcommand*{\AA}{A}%
\renewcommand*{\AE}{AE}%
\renewcommand*{\ae}{ae}%
\renewcommand*{\dh}{d}%
\renewcommand*{\DH}{D}%
\renewcommand*{\DJ}{D}%
\renewcommand*{\dj}{d}%
\renewcommand*{\IJ}{IJ}%
\renewcommand*{\ij}{ij}%
\renewcommand*{\L}{L}%
\renewcommand*{\l}{l}%
\renewcommand*{\NG}{NG}%
\renewcommand*{\ng}{ng}%
\renewcommand*{\O}{O}%
\renewcommand*{\o}{o}%
\renewcommand*{\oe}{oe}%
\renewcommand*{\OE}{OE}%
```

```
\renewcommand*{\ss}{ss}%
\renewcommand*{\SS}{SS}%
\renewcommand*{\th}{th}%
\renewcommand*{\TH}{TH}%
\renewcommand*{\guillemotleft}{}%
\renewcommand*{\guilsinglleft}{}%
\renewcommand*{\quotedblbase}{}%
\renewcommand*{\textquotedbl}{}%
\renewcommand*{\guillemotright}{}%
\renewcommand*{\guilsinglright}{}%
\renewcommand*{\quotesinglbase}{}%

\renewcommand*{\HTMLunicode}[1]{}%
\renewcommand*{\HTMLentity}[1]{}%

\renewcommand{\textsuperscript}[1]{##1}%
\renewcommand{\textsubscript}[1]{##1}%


\renewcommand{\underline}[1]{##1}%

\RenewDocumentCommand{\LWR@htmlspanclass}{o m +m}{##3}%
\DeclareExpandableDocumentCommand{\InlineClass}{D{(}{)}{} o m +m}{##4}%
```

Nullify math macros.

```
\def\(##1\){}%
\def\[##1\]{}%
\RenewDocumentCommand{\LWR@subsingledollar}{s m m m}{}%
\protected\def$##1${}%
```

Nullify logos:

```
\renewcommand*{\TeX}{TeX}%
\renewcommand*{\LaTeX}{LaTeX}%
\renewcommand*{\LaTeXe}{LaTeX2e}%
\renewcommand*{\LuaTeX}{LuaTeX}%
\renewcommand*{\LuaLaTeX}{LuaLaTeX}%
\renewcommand*{\XeTeX}{XeTeX}%
\renewcommand*{\XeLaTeX}{XeLaTeX}%
\renewcommand*{\ConTeXt}{ConTeXt}%
\renewcommand*{\BibTeX}{BibTeX}%
\renewcommand*{\MakeIndex}{MakeIndex}%
\renewcommand*{\AmS}{AmS}%
\renewcommand*{\MiKTeX}{MiKTeX}%
\renewcommand*{\LyX}{LyX}%
```

Use the simpler form with `\texorpdfstring`:

```
\let\texorpdfstring\relax%
\newcommand{\texorpdfstring}[2]{##2}%
}
\catcode`\$=3%
\catcode`\_=8%
```

\FilenameNullify {⟨*redefinitions*⟩}

Adds more nullifying definitions for filename generation.

```
\newcommand*{\FilenameNullify}[1]{%
    \appto{\LWR@nullfonts}{#1}%
}
```

Remembers the current font family, series, and shape.

```
\newcommand*{\LWR@f@family}{rm}
\newcommand*{\LWR@f@series}{md}
\newcommand*{\LWR@f@shape}{up}
```

\LWR@textcurrentfont {⟨*text*⟩}

Prints the text with the current font choices. Avoids nesting repeated font selections.

```
\newcounter{LWR@textcurrentfontdepth}
\setcounter{LWR@textcurrentfontdepth}{0}

\newcommand*{\LWR@textcurrentfont}[1]{%
    \ifnumcomp{\value{LWR@textcurrentfontdepth}}{>}{0}%
        {%
            \addtocounter{LWR@textcurrentfontdepth}{1}%
            #1%
            \addtocounter{LWR@textcurrentfontdepth}{-1}%
        }%
        {%
            \addtocounter{LWR@textcurrentfontdepth}{1}%
            \InlineClass{%
                    text\LWR@f@family\LWR@origtilde{}%
                    text\LWR@f@series\LWR@origtilde{}%
                    text\LWR@f@shape%
                }%
                {#1}%
            \addtocounter{LWR@textcurrentfontdepth}{-1}%
        }%
}
```

Env LWR@blocktextcurrentfont Prints the contents with the current font choices.

```
\newenvironment*{LWR@blocktextcurrentfont}{%
\BlockClass{%
        text\LWR@f@family\LWR@origtilde{}%
        text\LWR@f@series\LWR@origtilde{}%
        text\LWR@f@shape%
    }%
}{\endBlockClass}
```

\mdseries

```
\renewrobustcmd*{\mdseries}{\renewcommand*{\LWR@f@series}{md}}
```

\bfseries

```
\renewrobustcmd*{\bfseries}{\renewcommand*{\LWR@f@series}{bf}}
```

\rmfamily

```
\renewrobustcmd*{\rmfamily}{\renewcommand*{\LWR@f@family}{rm}}
```

\sffamily

```
\renewrobustcmd*{\sffamily}{\renewcommand*{\LWR@f@family}{sf}}
```

\ttfamily

```
\renewrobustcmd*{\ttfamily}{\renewcommand*{\LWR@f@family}{tt}}
```

\upshape

```
\renewrobustcmd*{\upshape}{\renewcommand*{\LWR@f@shape}{up}}
```

\itshape

```
\renewrobustcmd*{\itshape}{\renewcommand*{\LWR@f@shape}{it}}
```

\scshape

```
\renewrobustcmd*{\scshape}{\renewcommand*{\LWR@f@shape}{sc}}
```

\sishape

```
\@ifundefined{sishape}{
    \newrobustcmd*{\sishape}{\renewcommand*{\LWR@f@shape}{si}}
}{
    \renewrobustcmd*{\sishape}{\renewcommand*{\LWR@f@shape}{si}}
}
```

\slshape

```
\renewrobustcmd*{\slshape}{\renewcommand*{\LWR@f@shape}{sl}}
```

\normalfont

```
\renewrobustcmd*{\normalfont}{\rmfamily\mdseries\upshape}
```

\sp {⟨*text*⟩}

For siunitx. Must work in math mode.

```
\renewcommand{\sp}[1]{\text{<sup>#1</sup>}{}}
```

\sb {⟨*text*⟩}

For siunitx. Must work in math mode.

```
\renewcommand{\sb}[1]{\text{<sub>#1</sub>}{}}
```

\textsuperscript {⟨*text*⟩}

```
\renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}
```

\@textsuperscript {⟨*text*⟩}

```
\renewcommand{\@textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}
```

\textsubscript {⟨*text*⟩}

```
\AtBeginDocument{
\renewrobustcmd{\textsubscript}[1]{\LWR@htmlspan{sub}{#1}}
}
```

\@textsubscript {⟨*text*⟩}

```
\AtBeginDocument{
\renewcommand{\@textsubscript}[1]{\LWR@htmlspan{sub}{#1}}
}
```

\up {⟨*text*⟩} Prints superscript.

This is `\let` at the beginning of the document in case some other package has changed the definition.

```
\AtBeginDocument{\let\up\textsuperscript}
```

\fup {⟨*text*⟩} Prints superscript.

Supports fmtcount package.

This is `\let` at the beginning of the document in case some other package has changed the definition.

```
\AtBeginDocument{\let\fup\textsuperscript}
```

\underline {⟨*text*⟩}

```
\renewcommand{\underline}[1]{%
    \InlineClass%
        (text-decoration:underline; text-decoration-skip: auto)%
        {underline}{#1}%
}
```

\LWR@overline {⟨*text*⟩}

```
\newcommand{\LWR@overline}[1]{%
    \InlineClass%
        (text-decoration:overline; text-decoration-skip: auto)%
        {overline}{#1}%
}
```

\LWR@currenttextcolor The color to use for text and \rule, defaulting to black:

```
\newcommand*{\LWR@currenttextcolor}{black}
```

\LWR@tempcolor The color converted to HTML colorspace.
\LWR@tempcolortwo

```
\newcommand*{\LWR@tempcolor}{}
\newcommand*{\LWR@tempcolortwo}{}
```

\LWR@findcurrenttextcolor Sets \LWR@tempcolor to the current color.

```
\newcommand*{\LWR@findcurrenttextcolor}{%
\renewcommand{\LWR@tempcolor}{000000}%
}
```

\LWR@textcurrentcolor {⟨*text*⟩} Like \textcolor but uses the current \color instead.

```
\NewDocumentCommand{\LWR@textcurrentcolor}{m}{%
    \renewcommand*{\LWR@currenttextcolor}{black}%
    #1%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

\LWR@textcurrentfont {⟨*text*⟩}

Prints the text with the current font choices.

```
\newcommand*{\LWR@textcurrentfont}[1]{#1}
```

Env LWR@blocktextcurrentfont Prints the contents with the current font choices.

```
\newenvironment*{LWR@blocktextcurrentfont}{}{}
```

\FilenameNullify {⟨*macros to nullify*⟩}

```
\newcommand*{\FilenameNullify}[1]{}
```

```
\end{warpprint}
```

90 Skips, spaces, font sizes

for HTML output:

```
\begin{warpHTML}
```

`\,` and `\thinspace` may be redefined by other packages, so are redefined `\AtBeginDocument` here.

Direct-formatting space commands become HTML entities:

```
\AtBeginDocument{
\renewrobustcmd*{\,}{\HTMLunicode{202f}} % HTML thin non-breakable space
\renewrobustcmd*{\thinspace}{\HTMLunicode{202f}}   % HTML thin non-breakable space
\renewrobustcmd*{\negthinspace}{\HTMLunicode{202f}}   % HTML thin non-breakable space
\renewrobustcmd*{~}{\HTMLentity{nbsp}}
\renewrobustcmd*{\textellipsis}{\HTMLunicode{2026}}
}
```

Direct-formatting font sizes are ignored:

```
\newrobustcmd*{\LWR@HTML@normalsize}{}
\LWR@formatted{normalsize}

\newrobustcmd*{\LWR@HTML@small}{}
\LWR@formatted{small}

\newrobustcmd*{\LWR@HTML@footnotesize}{}
\LWR@formatted{footnotesize}

\newrobustcmd*{\LWR@HTML@scriptsize}{}
\LWR@formatted{scriptsize}

\newrobustcmd*{\LWR@HTML@tiny}{}
\LWR@formatted{tiny}

\newrobustcmd*{\LWR@HTML@large}{}
\LWR@formatted{large}

\newrobustcmd*{\LWR@HTML@Large}{}
\LWR@formatted{Large}

\newrobustcmd*{\LWR@HTML@LARGE}{}
\LWR@formatted{LARGE}

\newrobustcmd*{\LWR@HTML@huge}{}
\LWR@formatted{huge}

\newrobustcmd*{\LWR@HTML@Huge}{}
\LWR@formatted{Huge}


\DeclareDocumentCommand{\onecolumn}{}{}

\DeclareDocumentCommand{\twocolumn}{O{}}{
```

```
#1
}
```

\hfill

```
\newcommand*{\LWR@HTML@hfill}{\qquad}
\LWR@formatted{hfill}
```

\hrulefill

```
\newcommand*{\LWR@HTML@hrulefill}{\rule{1in}{1pt}}
\LWR@formatted{hrulefill}
```

\dotfill

```
\newcommand*{\LWR@HTML@dotfill}{\dots}
\LWR@formatted{dotfill}
```

\newpage

```
\renewcommand*{\newpage}{
}
```

\newline Uses the HTML <br /> element.

```
\newrobustcmd*{\LWR@newlinebr}{\unskip\LWR@htmltag{br /}\LWR@orignewline}%
\LetLtxMacro\newline\LWR@newlinebr
```

\\ Redefined to \LWR@endofline or \LWR@tabularendofline.

\LWR@endofline * [⟨*len*⟩]

\\ is assigned to \LWR@endofline at \LWR@LwarpStart.

Inside tabular, \\ is temporarily changed to \LWR@tabularendofline.

```
\LetLtxMacro\LWR@origendofline\\
\NewDocumentCommand{\LWR@endofline}{s O{0pt}}
{%
\newline%
```

```
\setlength{\LWR@templengthone}{#2}%
\ifdimgreater{\LWR@templengthone}{0pt}{\newline}{}%
}
```

\LWR@minipagestartpars Minipages are often placed side-by-side inside figures, with a bit of horizontal space to separate them. Since HTML does not allow a to be inside a p, paragraphs must

be turned off during the generation of the minipage, then turned on after the minipage is complete. When this occurs between side-by-side minipages, lwarp correctly suppresses the paragraph tags between the minipages, unless some other text is between the minipages. Such text forms its own paragraph, resulting in text after a minipage to be on its own line. Since people often place small horizontal space between minipages, it is desirable to maintain this space if possible. lwarp tries to do this by remembering that a minipage has been seen, in which case paragraph tags are suppressed around \hspace, \enskip, \quad, and \qquad until the end of the paragraph, when the closing p tag is created.

\hspace
\enskip
\quad
\qquad

When a minipage is seen, the boolean LWR@minipagethispar is set, telling the following horizontal whitespace commands to try to suppress their surrounding paragraph tags. LWR@minipagethispar is cleared at the next end of paragraph, when the HTML paragraph closing tag is generated.

Placed just before \hspace, \quad, or \qquad's HTML output.

```
\newcommand*{\LWR@minipagestartpars}{%
\ifbool{LWR@minipagethispar}{\LWR@startpars}{}%
}
```

\LWR@minipagestoppars

Placed just after \hspace, \quad, or \qquad's HTML output.

```
\newcommand*{\LWR@minipagestoppars}{%
\ifbool{LWR@minipagethispar}{\LWR@stoppars}{}%
}
```

\quad

Handles special minipage & horizontal space interactions. Uses 2003 EM SPACE to pass validation.

```
\renewrobustcmd*{\quad}{%
\LWR@minipagestoppars%
\HTMLunicode{2003}%
\LWR@minipagestartpars%
}
```

\qquad

Handles special minipage & horizontal space interactions.

```
\renewrobustcmd*{\qquad}{\quad\quad}
```

\enskip

Handles special minipage & horizontal space interactions.

```
\renewrobustcmd*{\enskip}{%
\LWR@minipagestoppars%
\HTMLunicode{2002}%
\LWR@minipagestartpars%
}
```

Len \LWR@tempwidth
Len \LWR@tempheight
Len \LWR@tempraise

Used to compute span width, height, raise for \hspace and \rule:

```
\newlength{\LWR@tempwidth}
```

```
\newlength{\LWR@tempheight}
\newlength{\LWR@tempraise}
```

`\LWR@select@html@hspace` * {⟨*length*⟩} * {⟨*length*⟩}

`\hspace`

Handles special minipage & horizontal space interactions.

Prints a span of a given width. Ignores the optional star.

`\hspace{\fill}` is converted to `\hspace{2em}`, equal to `\qquad`.

```
\newcommand{\LWR@select@html@hspace}{%
\RenewDocumentCommand{\hspace}{s m}{%
\setlength{\LWR@tempwidth}{##2}%
```

If `\fill`, change to `\qquad`:

```
\ifnum\gluestretchorder\LWR@tempwidth>0%
\setlength{\LWR@tempwidth}{2em}%
\fi%
```

Only if the width is not zero:

```
\ifdimcomp{\LWR@tempwidth}{=}{0pt}{}{%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
    \LWR@minipagestoppars%
```

Support the HTML thin wrappable space:

```
    \ifdimcomp{\LWR@tempwidth}{=}{.16667em}%
    {%
        \HTMLunicode{2009}% thin breakable space
    }%
```

Print the span with the converted width. Not rounded.

```
    {%
        \LWR@htmltagc{%
            span style="width:\LWR@printlength{\LWR@tempwidth};  % extra space
                display:inline-block"%
        }%
```

If formatting for a word processor, approximate with a number of `\quad`s, in case a span of a given width is not supported:

```
        \ifbool{FormatWP}{%
            \setlength{\LWR@templengthone}{\LWR@tempwidth}%
            \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
                \quad%
                \addtolength{\LWR@templengthone}{-1em}%
```

```
11090             }%
11091         }{}%
```

Close the span:

```
11092         \LWR@htmltagc{/span}%
11093     }%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
11094     \LWR@minipagestartpars%
11095 }% width not 0
11096 }%
11097 }
```

\LWR@select@html@nohspace * {⟨*length*⟩}
\hspace

Used to disable \hspace while creating description \items.

```
11098 \newcommand{\LWR@select@html@nohspace}{%
11099     \RenewDocumentCommand{\hspace}{s m}{}%
11100 }
```

\LWR@select@print@hspace

```
11101 \newcommand*{\LWR@select@print@hspace}{%
11102     \renewrobustcmd\hspace{\@ifstar\@hspacer\@hspace}%
11103 }
```

\hspace * {⟨*length*⟩}

Handles special minipage & horizontal space interactions.

```
11104 \LWR@select@html@hspace
```

\LWR@vspace * {⟨*length*⟩} Nullified vspace.

```
11105 \NewDocumentCommand{\LWR@HTML@vspace}{s m}{}
11106
11107 \LWR@formatted{vspace}
```

\linebreak [⟨*num*⟩] Inserts an HTML br tag.

```
11108 \renewcommand*{\linebreak}[1][]{\newline}
```

\nolinebreak [⟨*num*⟩]

```
11109 \renewcommand*{\nolinebreak}[1][]{}
```

`\pagebreak` `[`⟨*num*⟩`]` Starts a new paragraph.

```
\renewcommand*{\pagebreak}[1][]{
}
```

`\nopagebreak` `[`⟨*num*⟩`]`

```
\renewcommand*{\nopagebreak}[1][]{}
```

`\enlargethispage` `*` `{`⟨*len*⟩`}`

```
\RenewDocumentCommand{\enlargethispage}{s m}{}
```

`\clearpage`
`\cleardoublepage`

```
\renewcommand*{\clearpage}{}
\renewcommand*{\cleardoublepage}{}
```

`\rule` `[`⟨*raise*⟩`]` `{`⟨*width*⟩`}` `{`⟨*height*⟩`}`

Handles special minipage & horizontal space interactions.

Creates a span of a given width and height. Ignores the optional star.

`\fill` is zero-width, so `\hspace{\fill}` is ignored.

```
\newcommand*{\LWR@HTML@rule}[3][]{%
```

The width is copied into a temporary LaTeX length, from which comparisons and conversions may be made:

```
\setlength{\LWR@tempwidth}{#2}%
```

If it's zero-width then skip the entire rule:

```
\ifthenelse{\lengthtest{\LWR@tempwidth=0pt}}%
{}% zero- width
{% non-zero width
```

If it's non-zero width, set a minimal thickness so that it more reliably shows in the browser:

```
    \ifthenelse{%
        \lengthtest{\LWR@tempwidth>0pt}\AND%
        \lengthtest{\LWR@tempwidth<1pt}%
    }%
        {\setlength{\LWR@tempwidth}{1pt}}%
        {}%
```

Likewise with height:

```
    \setlength{\LWR@tempheight}{#3}%
    \ifthenelse{%
        \lengthtest{\LWR@tempheight>0pt}\AND%
        \lengthtest{\LWR@tempheight<1pt}%
    }%
        {\setlength{\LWR@tempheight}{1pt}}%
        {}%
```

If had a minipage this paragraph, try to inline the rule without generating paragraph tags:

```
    \LWR@minipagestoppars%
```

Print the span with the converted width and height. The width and height are NOT rounded, since a height of less than 1pt is quite common in LaTeX code.

```
    \LWR@findcurrenttextcolor%
    \LWR@htmltagc{%
    span\LWR@indentHTML%
    style="%
```

The background color is used to draw the filled rule. The color may be changed by `\textcolor`.

```
    \ifbool{FormatWP}{}{background:\LWR@currenttextcolor ; }%
```

The width and height are printed, converted to PT:

```
    width:\LWR@printlength{\LWR@tempwidth} ; %
    height:\LWR@printlength{\LWR@tempheight} ; %
```

The raise height is converted to a CSS transform. The `*2` raise multiplier is to approximately match HTML output's X height. Conversion to a LaTeX length allows a typical LaTeX expression to be used as an argument for the raise, whereas printing the raise argument directly to HTML output without conversion to a LaTeX length limits the allowable syntax. To do: A superior method would compute a ratio of LaTeX ex height, then print that to HTML with an ex unit.

```
    \ifblank{#1}%
    {}%
    {%
        \setlength{\LWR@tempraise}{0pt-#1}%
        \setlength{\LWR@tempraise}{\LWR@tempraise*2}%
        \LWR@indentHTML%
        -ms-transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
        \LWR@indentHTML%
        -webkit-transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
        \LWR@indentHTML%
        transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
        \LWR@indentHTML%
    }%
```

Display inline-block to place the span inline with the text:

```
    display:inline-block;"\LWR@orignewline%
    }%
```

If formatting for a word processor, approximate with a number of underscores, in case a span of a given width is not supported:

```
        \ifbool{FormatWP}{%
            \setlength{\LWR@templengthone}{\LWR@tempwidth}%
            \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
                \_{}%
                \addtolength{\LWR@templengthone}{-1em}%
            }%
        }{}%
```

Close the span:

```
    \LWR@htmltagc{/span}%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
    \LWR@minipagestartpars%
}% non-zero width
}

\LWR@formatted{rule}

\end{warpHTML}
```

91 \phantomsection

for HTML output:

```
\begin{warpHTML}
```

\phantomsection

Emulate the hyperref \phantomsection command, often used to insert the bibliography into the table of contents. Ignores \ForceHTMLTOC.

```
\DeclareDocumentCommand{\phantomsection}{}{%
\begingroup%
\boolfalse{LWR@forcinghtmltoc}%
\section*{}%
\endgroup%
}

\end{warpHTML}
```

92 \LaTeX and other logos

Logos for HTML and print modes:

Some of these logos may be redefined in a later package, so after loading other packages, and at the beginning of the document, their definitions are finally `\let` in `\LWR@LwarpStart`.

For css conversions, see:
http://edward.oconnor.cx/2007/08/tex-poshlet
http://nitens.org/taraborelli/texlogo
and the spacing described in the metafont package documentation.

92.1 HTML logos

for HTML output:
```
\begin{warpHTML}
```

`\TeX` TEX

`latexlogo` is a css class used to properly typeset the E and A in LATEX and friends.

`latexlogofont` is a css class used to select the font for the rest of the logo in LATEX, LuaTEX, ConTEXt, etc.

```
\LetLtxMacro\LWR@origTeX\TeX

\newrobustcmd*{\LWR@TeX}
{%
    \InlineClass{latexlogofont}%
    {%
        \InlineClass{latexlogo}%
        {%
            T%
            \InlineClass{latexlogosub}{e}%
            X%
        }%
    }%
}
```

`\LaTeX` LATEX, LATEX 2_ε
`\LaTeXe`

```
\LetLtxMacro\LWR@origLaTeX\LaTeX

\newrobustcmd*{\LWR@LaTeX}
{%
    \InlineClass{latexlogofont}%
    {%
        \InlineClass{latexlogo}%
        {%
            L%
            \InlineClass{latexlogosup}{a}%
            T%
            \InlineClass{latexlogosub}{e}%
            X%
        }%
    }%
```

```
}

\LetLtxMacro\LWR@origLaTeXe\LaTeXe

\renewrobustcmd*{\LaTeXe}
{%
    \LaTeX%
    \InlineClass{latexlogofont}{%
        \InlineClass{latexlogotwoe}{%
            2%
            \InlineClass{latexlogotwoesub}{\HTMLunicode{03B5}}%
        }%
    }%
}
```

\LuaTeX \LuaLaTeX LuaTEX, LuaLATEX

```
\newrobustcmd*{\LWR@LuaTeX}{\InlineClass{latexlogofont}{Lua}\TeX}
\newrobustcmd*{\LWR@LuaLaTeX}{\InlineClass{latexlogofont}{Lua}\LaTeX}
```

\XeTeX \XeLaTeX XƎTEX, XƎLATEX

xetexlogo is a css class which aligns the backwards E in XƎTEX and spaces TEX appropriately.

xelatexlogo is a css class which aligns the backwards E in XƎLATEX and spaces LATEX appropriately.

```
\newrobustcmd*{\Xe}
    {%
        X%
        \InlineClass{xelatexlogosub}{\HTMLunicode{18e}}%
    }

\newrobustcmd*{\LWR@XeTeX}{\InlineClass{xelatexlogo}{\Xe}\TeX}

\newrobustcmd*{\LWR@XeLaTeX}{\InlineClass{xelatexlogo}{\Xe}\LaTeX}
```

\ConTeXt ConTEXt

```
\newrobustcmd*{\LWR@ConTeXt}
{\InlineClass{latexlogofont}{Con}\TeX{}%
\InlineClass{latexlogofont}{t}}
```

\BibTeX \MakeIndex BIBTEX, *MakeIndex*

```
\providerobustcmd*{\BibTeX}
{\InlineClass{latexlogofont}{B\textsc{ib}}\TeX}

\newrobustcmd*{\MakeIndex}
{\InlineClass{latexlogofont}{\textit{MakeIndex}}}
```

\AmS $\mathcal{AMS}$

amslogo is a css class used for the $\mathcal{AMS}$ logo.

```
\AtBeginDocument{%
\DeclareDocumentCommand{\AmS}{}
{%
    \InlineClass{amslogo}{%
        \textit{%
            A%
            \InlineClass{latexlogosub}{M}%
            S%
        }%
    }%
}%
}
```

\MiKTeX MiKTEX

```
\newrobustcmd*{\MiKTeX}{\InlineClass{latexlogofont}{MiK}\TeX}
```

\LyX LyX

lyxlogo is a css class used for the LyX logo.

```
\newrobustcmd*{\LyX}{\InlineClass{lyxlogo}{LyX}}
```

```
\end{warpHTML}
```

92.2 Print logos

for PRINT output:

```
\begin{warpprint}

\newrobustcmd*{\XeTeXrevE}
    {\hspace{-.1667em}\raisebox{-.5ex}{E}\hspace{-.125em}}

\AtBeginDocument{
\@ifpackageloaded{graphics}{
    \renewrobustcmd*{\XeTeXrevE}
        {\hspace{-.1667em}\raisebox{-.5ex}{\reflectbox{E}}\hspace{-.125em}}
}{
    \PackageWarning{lwarp}{Load graphicx or graphics
        for improved XeTeX logo}
}
}

\providerobustcmd*{\XeTeX}{\mbox{X\XeTeXrevE\TeX}}
\providerobustcmd*{\XeLaTeX}{\mbox{X\XeTeXrevE\LaTeX}}
\providerobustcmd*{\AmS}{%
    \leavevmode\hbox{$\mathcal A\kern-.2em\lower.376ex%
    \hbox{$\mathcal M$}\kern-.2em\mathcal S$}%
}
```

```
\newrobustcmd*{\LyX}{\textsf{LyX}}
\providerobustcmd*{\LuaTeX}{\mbox{Lua\TeX}}
\providerobustcmd*{\LuaLaTeX}{\mbox{Lua\LaTeX}}
\providerobustcmd*{\BibTeX}{\mbox{B\textsc{ib}\TeX}}
\providerobustcmd*{\MakeIndex}{\mbox{\textit{MakeIndex}}}
\providerobustcmd*{\ConTeXt}{\mbox{Con\TeX{}t}}
\providerobustcmd*{\MiKTeX}{\mbox{MiK\TeX}}
\end{warpprint}
```

93 \AtBeginDocument, \AtEndDocument

for HTML output:

```
\begin{warpHTML}
```

\LWR@LwarpStart
\LWR@LwarpEnd

Automatically sets up the HTML-related actions for the start and end of the document.

```
\AfterEndPreamble{\LWR@LwarpStart}
\AtEndDocument{\LWR@LwarpEnd}

\end{warpHTML}
```

94 Loading KOMA-SCRIPT class patches

Load patches to koma-script.

for HTML output:

```
\begin{warpHTML}

\@ifclassloaded{scrbook}{\RequirePackage{lwarp-patch-komascript}}{}
\@ifclassloaded{scrartcl}{\RequirePackage{lwarp-patch-komascript}}{}
\@ifclassloaded{scrreprt}{\RequirePackage{lwarp-patch-komascript}}{}

\end{warpHTML}
```

95 Loading MEMOIR class patches

Load patches to memoir.

for HTML output:

```
\begin{warpHTML}

\@ifclassloaded{memoir}{\RequirePackage{lwarp-patch-memoir}}{}

\end{warpHTML}
```

96 ut* class patches

Load patches to uj* and ut* classes, as well as ltj* classes.

for HTML output:
```
\begin{warpHTML}
\newcommand*{\LWR@patchujtclasses}{
```

uj/t does not use \partname

```
    \def\@partnameformat{}

    \def\@partcntformat##1{%
        \prepartname%
        \csname the##1\endcsname%
        \postpartname%
        \quad%
    }
    \@ifundefined{chapter}{}{
        \def\@chapcntformat##1{%
            \prechaptername%
            \csname the##1\endcsname%
            \postchaptername%
            \quad%
        }
    }
```

Use decimal points instead of centered dots:

```
    \renewcommand{\thepart}{\@Roman\c@part}
    \@ifundefined{chapter}{
        \renewcommand{\thesection}{\@arabic\c@section}
    }{
        \renewcommand{\thechapter}{\@arabic\c@chapter}
        \renewcommand{\thesection}{\thechapter.\@arabic\c@section}
    }
    \renewcommand{\thesubsection}{\thesection.\@arabic\c@subsection}
    \renewcommand{\thesubsubsection}{%
    \thesubsection.\@arabic\c@subsubsection}
    \renewcommand{\theparagraph}{%
    \thesubsubsection.\@arabic\c@paragraph}
    \renewcommand{\thesubparagraph}{%
    \theparagraph.\@arabic\c@subparagraph}
    \@ifundefined{chapter}{
        \renewcommand{\thefigure}{\@arabic\c@figure}
        \renewcommand{\thetable}{\@arabic\c@table}
    }{
        \renewcommand{\thefigure}{%
        \ifnum\c@chapter>\z@\thechapter.\fi\@arabic\c@figure}
        \renewcommand{\thetable}{%
        \ifnum\c@chapter>\z@\thechapter.\fi\@arabic\c@table}
    }
}
```

```
\@ifclassloaded{ujarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ujbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ujreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{utarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{utbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{utreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjsarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjsbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjsreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjskiyou}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjspf}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjtarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjtbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjtreport}{\LWR@patchujtclasses}{}

\end{warpHTML}
```

97 CTEX patches

Patches for ctex and related classes, which are loaded before lwarp.

All CTEX classes and the ctex package seem to load ctexpatch, so its presence is used to decide whether to have lwarp patch CTEX.

for HTML output:

```
\begin{warpHTML}
```

`\AtBeginDocument` in case the user set `FileSectionNames` in the preamble.

```
\AtBeginDocument{
    \@ifpackageloaded{ctexpatch}{%
        \def\@partcntformat#1{%
            \LWR@isolate{\CTEX@partname}~%
            \CTEX@part@aftername%
        }%

        \def\@partnameformat{}

        \def\@chapcntformat#1{%
            \LWR@isolate{\CTEX@chaptername}~%
            \CTEX@chapter@aftername%
        }%
    }{}
}

\end{warpHTML}
```

98 kotexutf patches

Patch for kotexutf, which is loaded before lwarp.

kotexutf's `\@setref` was conflicting with lwarp's cross references.

for HTML output:

```
\begin{warpHTML}
```

If kotexutf's version of `\@setref` is detected, it is reverted to the original.

```
\AtBeginDocument{
\@ifpackageloaded{kotexutf}{%
    \def\LWR@kotexutf@setref#1#2#3{%
        \@setref@dhucs@orig{#1}{#2}{#3}%
      \ifx#1\relax\else
        \bgroup
        \dhucs@make@cjkchar@null
        \edef\@temp{\expandafter#2#1}\global\josatoks\expandafter{\@temp}%
        \egroup
      \fi%
    }%

    \ifdefequal{\@setref}{\LWR@kotexutf@setref}{
        \let\@setref\@setref@dhucs@orig
    }{}
}{}
}

\end{warpHTML}
```

File 2 **lwarp-2in1.sty**

§ 99 Package 2in1

Pkg 2in1 2in1 is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{2in1}
```

File 3 **lwarp-2up.sty**

§ 100 Package 2up

Pkg 2up 2up is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{2up}[2010/05/15]

\def\source#1#2#3{}
\def\target#1#2#3{}
\def\targetlayout#1{}
\newdimen\pageseplength
\newdimen\pagesepwidth
\newdimen\pagesepoffset
\def\twoupemptypage{}
\def\twoupclearpage{}
\def\twoupeject{}
\def\twouparticle{}
\def\twoupplain{}
\def\twouplegaltarget{}
\def\twouplandscape{}
\def\TwoupWrites{}
```

File 4 **lwarp-a4.sty**

§ 101 Package a4

Pkg a4 a4 is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{a4}[2004/04/15]

\newcommand*{\WideMargins}{}
```

File 5 **lwarp-a4wide.sty**

§ 102 Package a4wide

Pkg a4wide a4wide is ignored.

for HTML output:
```
\LWR@ProvidesPackageDrop{a4wide}[1994/08/30]
```

File 6 **lwarp-a5comb.sty**

§ 103 Package a5comb

Pkg a5comb a5comb is ignored.

for HTML output:
```
\LWR@ProvidesPackageDrop{a5comb}
```

File 7 **lwarp-abstract.sty**

§ 104 Package abstract

(*Emulates or patches code by* Peter Wilson.)

Pkg abstract abstract is supported and patched by lwarp.

⚠ missing TOC If using the `number` option with file splits, be sure to place the table of contents before the abstract. The `number` option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

for HTML output: memoir provides an `abstract` environment even though it is not an article or report class. Meanwhile, lwarp loads book to emulate memoir, but book does not have an `abstract` environment, so when the abstract package is loaded for emulation there is no pre-existing `abstract` to redefine, which would cause an error. Thus, a null `abstract` is provide here:

```
\ProvideDocumentEnvironment{abstract}{}{}{}
```

Accept all options for lwarp-abstract:

```
\LWR@ProvidesPackagePass{abstract}[2009/06/08]

\AtBeginDocument{
\BeforeBeginEnvironment{abstract}{
\LWR@forcenewpage
\BlockClass{abstract}
}
```

```
\AfterEndEnvironment{abstract}{\endBlockClass}
}

\renewcommand{\@bsrunintitle}{%
\hspace*{\abstitleskip}%
{\abstractnamefont%
\InlineClass{abstractrunintitle}{\abstractname}%
\@bslabeldelim}%
}

\@ifclassloaded{memoir}
{
  \renewenvironment{abstract}{%
%     \titlepage
    \null\vfil
    \@beginparpenalty\@lowpenalty
    \if@bsrunin
    \else
      \if@bsstyle
        \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
      \else
        \ifnumber@bs
          \num@bs
        \else
          \begin{\absnamepos}%
  \abstractnamefont \BlockClassSingle{abstracttitle}{\abstractname}
            \@endparpenalty\@M
          \end\absnamepos%
%%        \vspace{\abstitleskip}%
        \fi
      \fi
      \vspace{\abstitleskip}%
    \fi
    \put@bsintoc%
    \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
    {\par\end{@bstr@ctlist}\vfil\null%\endtitlepage
    }
}{% not memoir
\if@titlepage
  \renewenvironment{abstract}{%
%     \titlepage
    \null\vfil
    \@beginparpenalty\@lowpenalty
    \if@bsrunin
    \else
      \if@bsstyle
        \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
      \else
        \ifnumber@bs
          \num@bs
        \else
          \begin{\absnamepos}%
  \abstractnamefont \BlockClassSingle{abstracttitle}{\abstractname}
            \@endparpenalty\@M
          \end\absnamepos%
```

```
%%        \vspace{\abstitleskip}%
        \fi
      \fi
      \vspace{\abstitleskip}%
    \fi
    \put@bsintoc%
    \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
    {\par\end{@bstr@ctlist}\vfil\null%\endtitlepage
    }
\else
  \renewenvironment{abstract}{%
    \if@bsrunin
    \else
      \if@bsstyle
        \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
      \else
        \ifnumber@bs
          \num@bs
        \else
\begin{\absnamepos}%
\abstractnamefont\BlockClassSingle{abstracttitle}{\abstractname}%
\end\absnamepos%
%%        \vspace{\abstitleskip}%
        \fi
      \fi
      \vspace{\abstitleskip}%
    \fi
    \put@bsintoc%
    \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
    {\par\end{@bstr@ctlist}}
\fi
}% not memoir
```

File 8 **lwarp-academicons.sty**

§ 105 Package

academicons

(*Emulates or patches code by* Diogo A. B. Fernandes.)

Pkg academicons academicons is patched for use by lwarp.

If \aiicon is used, the name of the icon is used in the alt tag. Otherwise, for each of the individual icon macros, a generic alt tag is used.

for HTML output:

```
\LWR@ProvidesPackagePass{academicons}[2018/06/27]

\LetLtxMacro\LWR@orig@symbol\symbol

\let\LWR@academicons@orig@AI\AI

\newcommand*{\LWR@academicons@symbol}[1]{%
    \begin{lateximage}*[(academicon)][academicons#1]%
    \begingroup%
```

```
    \LWR@academicons@orig@AI%
    \LWR@orig@symbol{#1}%
    \endgroup%
    \end{lateximage}%
}

\renewcommand*{\AI}{%
    \LetLtxMacro\symbol\LWR@academicons@symbol%
}

\renewcommand*{\aiicon}[1]
{%
    \begin{lateximage}*[(#1 icon)][academicons#1]%
    \AI\csname aiicon@#1\endcsname%
    \end{lateximage}%
}
```

File 9 **lwarp-accsupp.sty**

§ 106 Package accsupp

Pkg accsupp accsupp is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{accsupp}[2018/03/28]

\newcommand*{\BeginAccSupp}[1]{}
\newcommand*{\EndAccSupp}[1]{}
```

File 10 **lwarp-acro.sty**

§ 107 Package acro

(*Emulates or patches code by* Clemens Niederberger.)

Pkg acro acro is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{acro}[2017/01/30]
```

\DeclareAcronym is used in the preamble, where lwarp has not yet made the dollar active, so temporarily enable lwarp math catcode just for this definition:

```
\ExplSyntaxOn
\NewDocumentCommand \LWR@DeclareAcronym {mm}
{
    \acro_declare_acronym:nn {#1} {#2}
    \catcode`\$=3% lwarp
}
\ExplSyntaxOff

```

```
\RenewDocumentCommand{\DeclareAcronym}{}{
    \catcode`\$=\active% lwarp
    \LWR@DeclareAcronym
}
```

Modified to activate the current font:

```
\ExplSyntaxOn
\cs_gset_protected:Npn \acro_write_short:nn #1#2
  {
    \mode_if_horizontal:F { \leavevmode }
    \group_begin:
      \bool_if:NTF \l__acro_custom_format_bool
        { \l__acro_custom_format_tl }
        { \l__acro_short_format_tl }
      {\LWR@textcurrentfont{#2}}% lwarp
    \group_end:
  }

\cs_gset_protected:Npn \acro_write_alt:nn #1#2
  {
    \mode_if_horizontal:F { \leavevmode }
    \group_begin:
      \bool_if:NTF \l__acro_custom_format_bool
        { \l__acro_custom_format_tl }
        { \l__acro_alt_format_tl }
      {\LWR@textcurrentfont{#2}}% lwarp
    \group_end:
  }

\cs_gset_protected:Npn \acro_write_long:nn #1#2
  {
    \mode_if_horizontal:F { \leavevmode }
    \group_begin:
      \bool_if:NTF \l__acro_custom_long_format_bool
        { \l__acro_custom_long_format_tl }
        { \use:n }
      {
        \use:x
          {
            \exp_not:n {#1}
            {
              \bool_if:NTF \l__acro_first_upper_bool
                { \exp_not:N \__acro_first_upper_case:n { \exp_not:n {
                    \LWR@textcurrentfont{#2}% lwarp
                } } }
                { \exp_not:n {\LWR@textcurrentfont{#2}} }% lwarp
            }
          }
      }
    \group_end:
  }
\ExplSyntaxOff
```

File 11 **lwarp-acronym.sty**

§ 108 Package

acronym

(*Emulates or patches code by* Tobias Oetiker.)

Pkg acronym acronym is patched for use by lwarp.

⚠ multiply-defined labels `\acresetall` does not work with cleveref, causing multiply-defined labels. lwarp patches acronym for HTML, but not for print mode.

for HTML output:

```
\LWR@ProvidesPackagePass{acronym}[2015/03/21]
```

Uses `\textit` instead of `\itshape`:

```
\renewcommand{\acfia}[1]{%
  {\textit{\AC@acl{#1}}} (\ifAC@starred\acs*{#1}\else\acs{#1}\fi)}
```

Removes the mbox to allow math inside:

```
\renewcommand*\AC@acs[1]{%
%     \mbox{
 \expandafter\AC@get\csname fn@#1\endcsname\@firstoftwo{#1}}
% }
```

Fix for acronym labels in the captions of floats.

```
\renewcommand{\@starttoc}[1]{
\LWR@htmlelementclass{nav}{#1}
\LetLtxMacro\@verridelabel\@gobble
\LWR@orig@starttoc{#1}
\LWR@htmlelementclassend{nav}{#1}
}
```

Modified for cleveref and lwarp:

```
\renewcommand*\AC@und@newl@bel[3]{%
    \@ifundefined{#1@#3}%
    {%
        \global\expandafter\let\csname#2@#3\endcsname\@nnil
        \global\expandafter\let\csname#2@#3@lwarp\endcsname\@nnil% lwarp
        \global\expandafter\let\csname#2@#3@cref\endcsname\@nnil% lwarp
    }%
    {%
        \global\expandafter\let\csname#1@#3\endcsname\relax
        \global\expandafter\let\csname#1@#3@lwarp\endcsname\relax% lwarp
        \global\expandafter\let\csname#1@#3@cref\endcsname\relax% lwarp
    }%
}%
```

File 12 **lwarp-adjmulticol.sty**

§ 109 Package

adjmulticol

(*Emulates or patches code by* Boris Veytsman.)

Pkg adjmulticol adjmulticol is emulated.

Emulation similar to multicols is used, with adjusted margins. If the number of columns is specified as 1, it is set so, but if two or greater are used, lwarp allows a variable number of columns up to three.

for HTML output:

```
\LWR@ProvidesPackageDrop{adjmulticol}[2012/01/20]
\RequirePackage{multicol}
```

adjmulticols * {⟨*numcols*⟩} {⟨*left margi*⟩} {⟨*right margin*⟩}

```
\NewDocumentEnvironment{adjmulticols}{s m m m}
{%
```

Compute the margins, and limit to positive only:

```
\setlength{\LWR@templengthone}{#3}%
\ifdimcomp{\LWR@templengthone}{<}{0pt}{\setlength{\LWR@templengthone}{0pt}}{}%
\setlength{\LWR@templengthtwo}{#4}
\ifdimcomp{\LWR@templengthtwo}{<}{0pt}{\setlength{\LWR@templengthtwo}{0pt}}{}%
```

If one column is specified, use a of class singlecolumn, else use multicols:

```
\newcommand*{\LWR@mcolstype}{multicols}%
\ifnumcomp{#2}{=}{1}{\renewcommand*{\LWR@mcolstype}{singlecolumn}}{}%
```

Help avoid page overflow:

```
\LWR@forcenewpage%
```

Create the with the given margin and class:

```
\BlockClass[%
\LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
\LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}%
]{\LWR@mcolstype}%
}
{\endBlockClass}
```

File 13 **lwarp-addlines.sty**

§ 110 Package addlines

(*Emulates or patches code by* Will Robertson.)

Pkg addlines addlines is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{addlines}[2018/12/05]

\newcommand\addlines{\@ifstar\addlines@a\addlines@a}
\newcommand\addlines@a[1][1]{}
\let\addline\addlines
\newcommand\removelines{\@ifstar\removelines@a\removelines@a}
\newcommand\removelines@a[1][1]{}
\let\removeline\removelines
\newcommand\squeezepage[1][0]{}
```

File 14 **lwarp-afterpage.sty**

§ 111 Package afterpage

(*Emulates or patches code by* David Carlisle.)

Pkg afterpage Emulated.

for HTML output: Discard all options for lwarp-afterpage:

```
\LWR@ProvidesPackageDrop{afterpage}[2014/10/28]

\newcommand{\afterpage}[1]{#1}
```

File 15 **lwarp-algorithm2e.sty**

§ 112 Package algorithm2e

(*Emulates or patches code by* Christophe Fiorio.)

Pkg algorithm2e algorithm2e is patched for use by lwarp.

For print output, captions are placed according to package options, but for HTML output captions are placed where used. Therefore, to have captions appear at the top of the algorithms for both print and HTML, place each captions at the top of each algorithm.

for HTML output:

```
\LWR@ProvidesPackagePass{algorithm2e}[2017/07/18]
```

For the list-of entries:

```
\renewcommand{\l@algocf}[2]{\hypertocfloat{1}{algocf}{loa}{#1}{#2}}
```

Select the lwarp float style according to the algorithm2e style:

```
\newcommand*{\LWR@floatstyle@algocf}{ruled}

\ifdefstring{\algocf@style}{boxed}{%
\renewcommand*{\LWR@floatstyle@algocf}{boxed}
}{}

\ifdefstring{\algocf@style}{boxruled}{%
\renewcommand*{\LWR@floatstyle@algocf}{boxruled}
}{}

\ifdefstring{\algocf@style}{plain}{%
\renewcommand*{\LWR@floatstyle@algocf}{plain}
}{}
```

Paragraph handling to allow line numbers under certain conditions:

```
\newbool{LWR@algocf@dopars}
\booltrue{LWR@algocf@dopars}

\renewcommand{\algocf@everypar}{%
\ifbool{LWR@algocf@dopars}{%
    \ifbool{LWR@doingstartpars}{%
        \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
            {}%
            {%
                \algocf@everyparnl\algocf@everyparhanging%
            }%
    }{}%
}{}%
}
```

lwarp caption handling:

```
\renewcommand{\algocf@makecaption}[2]{%
\LWR@HTML@caption@begin{algocf}%
\LWR@isolate{\algocf@captiontext{#1}{#2}}%
\LWR@HTML@caption@end%
}
```

Print any caption where it is declared:

```
\renewcommand{\algocf@makecaption@plain}[2]{%
    \LWR@HTML@caption@begin{algocf}%
    \LWR@isolate{\algocf@captiontext{#1}{#2}}%
    \LWR@HTML@caption@end%
}

\renewcommand{\algocf@makecaption@boxed}[2]{%
    \LWR@HTML@caption@begin{algocf}%
```

```
    \LWR@isolate{\algocf@captiontext{#1}{#2}}%
    \LWR@HTML@caption@end%
}

\renewcommand{\algocf@makecaption@ruled}[2]{%
    \LWR@HTML@caption@begin{algocf}%
    \LWR@isolate{\algocf@captiontext{#1}{#2}}%
    \LWR@HTML@caption@end%
}
```

Turn off line numbering while making the caption:

```
\long\def\algocf@latexcaption#1[#2]#3{% original definition of caption
\boolfalse{LWR@algocf@dopars}%  lwarp
  \par%
  \addcontentsline{\csname ext@#1\endcsname}{#1}%
 {\protect\numberline{\csname the#1\endcsname}{\ignorespaces \LWR@isolate{#2}}}%
  \begingroup%
  \@parboxrestore%
  \if@minipage%
    \@setminipage%
  \fi%
  \normalsize%
  \@makecaption{\csname fnum@#1\endcsname}{\ignorespaces #3}\par%
  \endgroup%
\booltrue{LWR@algocf@dopars}%   lwarp
}
```

Line numbers are printed in a of class `alg2elinenumber`:

```
\renewcommand{\algocf@printnl}[1]{%
    \InlineClass{alg2elinenumber}{\NlSty{#1}}~%
}%
```

While initializing an algorithm environment, locally declare the style of a regular figure to be the same as the algorithm style, in case the `figure` option was used.

```
\preto\@algocf@init{%
  \edef\LWR@floatstyle@figure{\LWR@floatstyle@algocf}%
}
```

For lwarp, the algorithm is not assembled inside a box, since `latexi`mages would not work, so the captions are printed where declared.

```
\renewcommand{\@algocf@start}{%
    \let\@mathsemicolon=\;\def\;{\ifmmode\@mathsemicolon\else\@endalgoln\fi}%
%     \raggedright%
    \AlFnt{}%
    \booltrue{LWR@algocf@dopars}% lwarp
}

\renewcommand{\@algocf@finish}{%
    \boolfalse{LWR@algocf@dopars}% lwarp
    \lineskip\normallineskip\setlength{\skiptotal}{\@defaultskiptotal}%
```

```
    \let\;=\@mathsemicolon%
    \let\]=\@emathdisplay%
}
```

Use an HTML break:

```
\renewcommand{\BlankLine}{%
\LWR@stoppars%
\LWR@htmltagc{br /}%
\LWR@startpars%
}
```

Simplified for HTML. The paragraph handling must be preserved.

```
\renewcommand{\SetKwInOut}[2]{%
  \algocf@newcommand{#1}[1]{%
    \ifthenelse{\boolean{algocf@hanginginout}}%
        {\relax}%
        {\algocf@seteveryparhanging{\relax}}%
    \ifthenelse{\boolean{algocf@inoutnumbered}}%
        {\relax}%
        {\algocf@seteveryparnl{\relax}}%
    {%
            \KwSty{#2\algocf@typo:}%
        ~##1\par%
    }%
    \algocf@linesnumbered% reset the numbering of the lines
    \ifthenelse{\boolean{algocf@hanginginout}}%
        {\relax}%
        {\algocf@reseteveryparhanging}%
  }%
}%

\renewcommand{\ResetInOut}[1]{}%
```

Each of the following creates a of a given class, and turns off line numbering while creating the tags:

```
\renewcommand{\algocf@Vline}[1]{%
\boolfalse{LWR@algocf@dopars}%
\begin{BlockClass}{alg2evline}
\booltrue{LWR@algocf@dopars}%
#1
\boolfalse{LWR@algocf@dopars}%
\end{BlockClass}
\booltrue{LWR@algocf@dopars}%
}

\renewcommand{\algocf@Vsline}[1]{%
\boolfalse{LWR@algocf@dopars}%
\begin{BlockClass}{alg2evsline}
\booltrue{LWR@algocf@dopars}%
#1
\boolfalse{LWR@algocf@dopars}%
\end{BlockClass}
```

```
\booltrue{LWR@algocf@dopars}%
}

\renewcommand{\algocf@Noline}[1]{%
\boolfalse{LWR@algocf@dopars}%
\begin{BlockClass}{alg2enoline}
\booltrue{LWR@algocf@dopars}%
#1
\boolfalse{LWR@algocf@dopars}%
\end{BlockClass}
\booltrue{LWR@algocf@dopars}%
}
```

The [H] environment is converted to a regular float, which in HTML is placed where declared. Reusing the regular float allows the [H] version to reuse the ruled and boxed options.

```
\LetLtxMacro\algocf@Here\algocf
\LetLtxMacro\endalgocf@Here\endalgocf
```

File 16 **lwarp-algorithmicx.sty**

§ 113 Package

algorithmicx

(*Emulates or patches code by* Szász János.)

Pkg algorithmicx algorithmicx is supported with minor adjustments.

for HTML output:

```
\LWR@ProvidesPackagePass{algorithmicx}[2005/04/27]
```

Inside the algorithmic environment, level indenting is converted to a of the required length, and comments are placed inside a which is floated right.

⚠ package conflicts If using \newfloat, trivfloat, and/or algorithmicx together, see section 460.1.

for HTML output:

```
\begin{warpHTML}

\AtBeginEnvironment{algorithmic}{%
%
\let\origALG@doentity\ALG@doentity%
%
\renewcommand*{\ALG@doentity}{%
\origALG@doentity%
\LWR@htmltagc{%
span style="width:\LWR@printlength{\ALG@thistlm}; display:inline-block;"%
}%
\ifbool{FormatWP}{%
\setlength{\LWR@templengthone}{\the\ALG@thistlm}%
\whiledo{\lengthtest{\LWR@templengthone>1em}}{%
\quad%
\addtolength{\LWR@templengthone}{-1em}%
}%
```

```
}{}%
\LWR@htmltagc{/span}%
}%

\let\LWR@origComment\Comment%

\renewcommand{\Comment}[1]{%
    \InlineClass{floatright}{\LWR@origComment{#1}}%
}%
}

\renewcommand\algorithmiccomment[1]{%
\hfill\HTMLunicode{25B7} #1% white right triangle
}%

\end{warpHTML}
```

File 17 **lwarp-alltt.sty**

§ 114 Package alltt

(*Emulates or patches code by* Johannes Braams.)

Pkg alltt alltt is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{alltt}[1997/06/16]

\AfterEndPreamble{
\LWR@traceinfo{Patching alltt.}
\AtBeginEnvironment{alltt}{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{alltt}%
}
\AfterEndEnvironment{alltt}{%
    \LWR@afterendverbatim{2}%
}
}
```

File 18 **lwarp-amsmath.sty**

§ 115 Package amsmath

(*Emulates or patches code by* American Mathematical Society, LaTeX3 Project.)

Pkg amsmath amsmath is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{amsmath}[2017/09/02]
```

Patches to allow `\eqref` inside a caption:

```
\def\maketag@@@#1{\text{#1}}
\def\tagform@#1{\maketag@@@{(\ignorespaces#1\unskip)}}
```

Patches for $\mathcal{AMS}$ math \tag macro to remember the first tag:

```
\ifbool{mathjax}{}{% not mathjax

\LetLtxMacro\LWR@origmake@df@tag@@\make@df@tag@@
\LetLtxMacro\LWR@origmake@df@tag@@@\make@df@tag@@@

\renewcommand*{\make@df@tag@@}[1]{%
\LWR@remembertag{#1}%
\LWR@origmake@df@tag@@{#1}%
}

\renewcommand*{\make@df@tag@@@}[1]{%
\LWR@remembertag{#1}%
\LWR@origmake@df@tag@@@{#1}%
}

}% not mathjax
```

The following $\mathcal{AMS}$ environments are more easily patched in-place:

Env multline

```
\BeforeBeginEnvironment{multline}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \booltrue{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbodynumbered{multline}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{multline}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \boolfalse{LWR@amsmultline}
    \LWR@addmathjax{multline}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

Env multline*

```
\BeforeBeginEnvironment{multline*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \booltrue{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbody{multline*}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{multline*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \boolfalse{LWR@amsmultline}
    \LWR@addmathjax{multline*}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}

```

Env gather

```
\BeforeBeginEnvironment{gather}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbodynumbered{gather}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{gather}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
```

```
    \LWR@endhideamsmath
    \LWR@addmathjax{gather}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

Env gather*

```
\BeforeBeginEnvironment{gather*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbody{gather*}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{gather*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \LWR@addmathjax{gather*}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

Env align

```
\BeforeBeginEnvironment{align}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbodynumbered{align}]
    \LWR@applyxfakebold%
}
```

```
}

\AfterEndEnvironment{align}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \LWR@addmathjax{align}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

Env `align*`

```
\BeforeBeginEnvironment{align*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbody{align*}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{align*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \LWR@addmathjax{align*}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

Env `flalign`

```
\BeforeBeginEnvironment{flalign}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
```

```
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbodynumbered{flalign}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{flalign}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \LWR@addmathjax{flalign}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

Env flalign*

```
\BeforeBeginEnvironment{flalign*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbody{flalign*}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{flalign*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \LWR@addmathjax{flalign*}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

Env alignat

```
\BeforeBeginEnvironment{alignat}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
```

```
{
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbodynumbered{alignat}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{alignat}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \LWR@addmathjax{alignat}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

Env alignat*

```
\BeforeBeginEnvironment{alignat*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbody{alignat*}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{alignat*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \LWR@addmathjax{alignat*}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

File 19 **lwarp-amsthm.sty**

§ 116 Package

amsthm

(*Emulates or patches code by* Publications Technical Group — American Mathematical Society.)

The original source code is located in amsclass.dtx, and printed in amsclass.pdf.

Pkg amsthm amsthm is patched for use by lwarp.

Table 14: amsthm package — css styling of theorems and proofs

Theorem: of class amsthmbody<theoremstyle>

Theorem Name: of class amsthmname<theoremtyle>

Theorem Number: of class amsthmnumber<theoremstyle>

Theorem Note: of class amsthmnote<theoremstyle>

Proof: of class amsthmproof

Proof Name: of class amsthmproofname

where <theoremstyle> is plain, definition, etc.

for HTML output: amsthm must be loaded before mdframed:

```
\@ifpackageloaded{mdframed}{
    \PackageError{lwarp}
    {Package mdframed must be loaded after package amsthm.}
    {%
     Move \detokenize{\usepackage}{amsthm} before \detokenize{\usepackage}{mdframed}.
       Package amsthm may be loaded by something else, which must also be moved
        before mdframed.%
    }
}
{}

\LWR@ProvidesPackagePass{amsthm}[2017/10/31]
```

Storage for the style being used for new theorems:

```
\newcommand{\LWR@newtheoremstyle}{plain}
```

Patched to remember the style being used for new theorems:

```
\renewcommand{\theoremstyle}[1]{%
  \@ifundefined{th@#1}{%
    \PackageWarning{amsthm}{Unknown theoremstyle `#1'}%
```

```
    \thm@style{plain}%
    \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
  }{%
    \thm@style{#1}%
    \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
  }%
}
```

Patched to remember the style for this theorem type:

```
\def\@xnthm#1#2{%
  \csedef{LWR@thmstyle#2}{\LWR@newtheoremstyle}% lwarp
  \let\@tempa\relax
  \@xp\@ifdefinable\csname #2\endcsname{%
    \global\@xp\let\csname end#2\endcsname\@endtheorem
    \ifx *#1% unnumbered, need to get one more mandatory arg
      \edef\@tempa##1{%
        \gdef\@xp\@nx\csname#2\endcsname{%
          \@nx\@thm{\@xp\@nx\csname th@\the\thm@style\endcsname}%
            {}{##1}}}%
    \else % numbered theorem, need to check for optional arg
      \def\@tempa{\@oparg{\@ynthm{#2}}[]}%
    \fi
   \AtBeginEnvironment{#2}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#2}}}% lwarp
  }%
  \@tempa
}
```

Patched to enclose with css:

```
\newcommand{\LWR@haveamsthmname}{
\renewcommand{\thmname}[1]{\InlineClass{amsthmname\LWR@thisthmstyle}{##1}}
}

\newcommand{\LWR@haveamsthmnumber}{
\renewcommand{\thmnumber}[1]{\InlineClass{amsthmnumber\LWR@thisthmstyle}{##1}}
}

\newcommand{\LWR@haveamsthmnote}{
\renewcommand{\thmnote}[1]{\InlineClass{amsthmnote\LWR@thisthmstyle}{##1}}
}

\LWR@haveamsthmname
\LWR@haveamsthmnumber
\LWR@haveamsthmnote
```

Patches for css:

```
\def\@begintheorem#1#2[#3]{%
    \item[
%   \deferred@thm@head{
%     \the\thm@headfont \thm@indent
    \@ifempty{#1}{\let\thmname\@gobble}{\LWR@haveamsthmname}% lwarp
    \@ifempty{#2}{\let\thmnumber\@gobble}{\LWR@haveamsthmnumber}% lwarp
    \@ifempty{#3}{\let\thmnote\@gobble}{\LWR@haveamsthmnote}% lwarp
```

```
    \thm@swap\swappedhead\thmhead{#1}{#2}{#3}%
    \the\thm@headpunct~
    \thmheadnl % possibly a newline.
    \hskip\thm@headsep
%   }%
    ]
  \ignorespaces}
```

Patched for css:

```
\def\@thm#1#2#3{%
  \ifhmode\unskip\unskip\par\fi
  \normalfont
  \LWR@forcenewpage% lwarp
  \BlockClass{amsthmbody\LWR@thisthmstyle}% lwarp
  \trivlist
  \let\thmheadnl\relax
  \let\thm@swap\@gobble
  \thm@notefont{\fontseries\mddefault\upshape}%
  \thm@headpunct{.}% add period after heading
  \thm@headsep 5\p@ plus\p@ minus\p@\relax
  \thm@space@setup
  #1% style overrides
  \@topsep \thm@preskip               % used by thm head
  \@topsepadd \thm@postskip           % used by \@endparenv
  \def\@tempa{#2}\ifx\@empty\@tempa
    \def\@tempa{\@oparg{\@begintheorem{#3}{}}[]}%
  \else
    \refstepcounter{#2}%
    \def\@tempa{\@oparg{\@begintheorem{#3}{\csname the#2\endcsname}}[]}%
  \fi
  \@tempa
}
```

cleveref patches `\@thm` to do `\cref@thmoptarg` if an optional argument is given. lwarp then patches `\cref@thmoptarg` `\AtBeginDocument`.

```
\AtBeginDocument{%
\def\cref@thmoptarg[#1]#2#3#4{%
    \ifhmode\unskip\unskip\par\fi%
    \normalfont%
    \LWR@forcenewpage% lwarp
    \BlockClass{amsthmbody\LWR@thisthmstyle}% lwarp
    \trivlist%
    \let\thmheadnl\relax%
    \let\thm@swap\@gobble%
    \thm@notefont{\fontseries\mddefault\upshape}%
    \thm@headpunct{.}% add period after heading
    \thm@headsep 5\p@ plus\p@ minus\p@\relax%
    \thm@space@setup%
    #2% style overrides
    \@topsep \thm@preskip               % used by thm head
    \@topsepadd \thm@postskip           % used by \@endparenv
    \def\@tempa{#3}\ifx\@empty\@tempa%
        \def\@tempa{\@oparg{\@begintheorem{#4}{}}[]}%
```

```
    \else%
        \refstepcounter[#1]{#3}%  <<< cleveref modification
        \def\@tempa{\@oparg{\@begintheorem{#4}{\csname the#3\endcsname}}[]}%
    \fi%
    \@tempa
}%
}% AtBeginDocument

\def\@endtheorem{\endtrivlist\endBlockClass\@endpefalse }
```

Proof QED symbol:

```
\AtBeginDocument{
\@ifundefined{LWR@orig@openbox}{
\LetLtxMacro\LWR@orig@openbox\openbox
\LetLtxMacro\LWR@orig@blacksquare\blacksquare
\LetLtxMacro\LWR@orig@Box\Box

\def\openbox{\text{\HTMLunicode{25A1}}}% UTF-8 white box
\def\blacksquare{\text{\HTMLunicode{220E}}}% UTF-8 end-of-proof
\def\Box{\text{\HTMLunicode{25A1}}}% UTF-8 white box

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\openbox\LWR@orig@openbox%
\LetLtxMacro\blacksquare\LWR@orig@blacksquare%
\LetLtxMacro\Box\LWR@orig@Box%
}% appto
}{}% @ifundefined
}% AtBeginDocument
```

Patched for css:

```
\renewenvironment{proof}[1][\proofname]{\par
\LWR@forcenewpage% lwarp
    \BlockClass{amsthmproof}% lwarp
  \pushQED{\qed}%
  \normalfont \topsep6\p@\@plus6\p@\relax
  \trivlist
  \item[
        \InlineClass{amsthmproofname}{#1\@addpunct{.}}]\ignorespaces% changes
}{%
  \InlineClass{theoremendmark}{\popQED}\endtrivlist%
  \endBlockClass% lwarp
  \@endpefalse
}
```

File 20 **lwarp-anonchap.sty**

§ 117 Package anonchap

(*Emulates or patches code by* Peter Wilson.)

Pkg anonchap anonchap is emulated.

Pkg tocloft

⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

The code is shared by tocbibind.

for HTML output:

```
\LWR@ProvidesPackageDrop{anonchap}[2009/08/03]

\newcommand{\simplechapter}[1][\@empty]{%
    \def\@chapcntformat##1{%
        #1~\csname the##1\endcsname\simplechapterdelim\quad%
    }%
}

\newcommand{\restorechapter}{%
\let\@chapcntformat\@seccntformat%
}
```

File 21 **lwarp-anysize.sty**

§ 118 Package

anysize

(*Emulates or patches code by* Michael Salzenberg, Thomas Esser.)

Pkg anysize

anysize is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{anysize}[1994/08/13]

\def\papersize#1#2{}
\def\marginsize#1#2#3#4{}
```

File 22 **lwarp-appendix.sty**

§ 119 Package

appendix

(*Emulates or patches code by* Peter Wilson.)

Pkg appendix

appendix is patched for use by lwarp.

⚠ incorrect TOC link

During HTML conversion, the option `toc` without the option `page` results in a TOC link to whichever section was before the `appendices` environment. It is recommended to use both `toc` and also `page` at the same time.

for HTML output:

```
\LWR@ProvidesPackagePass{appendix}[2009/09/02]

\renewcommand*{\@chap@pppage}{%
\part*{\appendixpagename}
 \if@dotoc@pp
 \addappheadtotoc
```

```
 \fi
}

\renewcommand*{\@sec@pppage}{%
\part*{\appendixpagename}
 \if@dotoc@pp
 \addappheadtotoc
 \fi
}
```

File 23 **lwarp-ar.sty**

§ 120 Package

ar

(*Emulates or patches code by* Agostino De Marco.)

Pkg ar ar is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{ar}[2012/01/23]
```

Measure and print the width of the supplied glyph.

```
\newlength{\LWR@ar@width}

\newcommand*{\LWR@ar@printwidth}[1]{%
    \setlength{\LWR@ar@width}{\widthof{#1}}%
    width:%
    \LWR@convertto{em}{\the\LWR@ar@width}em%
}
```

The HTML version of \AR:

```
\newrobustcmd*{\LWR@HTML@AR}{%
```

Start a hashed `lateximage`, additionally hashed by the font series, with a width depending on the given glyph:

```
    \begin{lateximage}*[AR][\LWR@f@series][\LWR@ar@printwidth{\LWR@print@AR}]%
```

For text mode, set the font series according to the HTML font series:

```
    \ifmmode\else\csuse{LWR@orig\LWR@f@series series}\fi%
```

Print the original glyph using the newly set font series:

```
    \LWR@print@AR%
```

Done.

```
    \end{lateximage}%
}
```

Combine the print and HTML versions:

```
\LWR@formatted{AR}

\newrobustcmd*{\LWR@HTML@ARb}{%
    \begin{lateximage}*[AR][b][\LWR@ar@printwidth{\LWR@print@ARb}]%
    \LWR@print@ARb%
    \end{lateximage}%
}
\LWR@formatted{ARb}

\newrobustcmd*{\LWR@HTML@ARss}{%
  \begin{lateximage}*[ARss][\LWR@f@series][\LWR@ar@printwidth{\LWR@print@ARss}]%
    \ifmmode\else\csuse{LWR@orig\LWR@f@series series}\fi%
    \LWR@print@ARss%
    \end{lateximage}%
}
\LWR@formatted{ARss}

\newrobustcmd*{\LWR@HTML@ARssb}{%
    \begin{lateximage}*[AR][ssb][\LWR@ar@printwidth{\LWR@print@ARssb}]%
    \LWR@print@ARssb%
    \end{lateximage}%
}
\LWR@formatted{ARssb}

\newrobustcmd*{\LWR@HTML@ARtt}{%
    \begin{lateximage}*[AR][tt][\LWR@ar@printwidth{\LWR@print@ARtt}]%
    \LWR@print@ARtt%
    \end{lateximage}%
}
\LWR@formatted{ARtt}
```

File 24 **lwarp-arabicfront.sty**

§ 121 Package arabicfront

Pkg arabicfront arabicfront is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{arabicfront}[2006/09/03]
```

File 25 **lwarp-array.sty**

§ 122 Package array

Pkg array array is used as-is for print output, and emulated for HTML.

plarray and plextarray do not affect `\firsthline` or `\lasthline`, and so are not affected by the following.

for HTML output: Remove the default nullfied macros:

```
\let\firsthline\relax
\let\lasthline\relax

\LWR@ProvidesPackagePass{array}[2018/12/30]

\newcommand*{\LWR@HTML@firsthline}{\LWR@HTMLhline}%
\LWR@expandableformatted{firsthline}

\newcommand*{\LWR@HTML@lasthline}{\LWR@HTMLhline}%
\LWR@expandableformatted{lasthline}
```

File 26 **lwarp-arydshln.sty**

§ 123 Package

arydshln

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg arydshln arydshln heavily patches tabular code, so the actual package is not used. arydshln is emulated for HTML `tabular`, and reverts to solid rules for SVG math `array` and `tabular` in a `lateximage`.

CSS is not able to display a double-dashed border, so a single-dashed rule is displayed as a single-dashed border, and a double-dashed rule is displayed as a thicker single-dashed border.

for HTML output: array is required to allow `\newcolumn` below.

```
\RequirePackage{array}

\LWR@ProvidesPackageDrop{arydshln}[2018/09/26]
```

Ignored, but included for source compatibility:

```
\newdimen\dashlinedash \dashlinedash4pt %
\newdimen\dashlinegap \dashlinegap4pt %
\let\hdashlinewidth\dashlinedash
\let\hdashlinegap\dashlinegap

\def\ADLnullwide{}
\def\ADLsomewide{}
\def\ADLnullwidehline{}
\def\ADLsomewidehline{}

\def\ADLactivate{}
\def\ADLinactivate{}
\newcommand*{\ADLdrawingmode}[1]{}
\newcommand*{\ADLnoshorthanded}{}
\newcommand*{\dashgapcolor}[2][]{}
\newcommand*{\nodashgapcolor}{}
```

In a `lateximage`, revert to solid vertical rules:

```
\appto\LWR@restoreorigformatting{%
\newcolumntype{:}{|}%
\newcolumntype{;}[1]{|}%
\LetLtxMacro\hdashline\hline%
}
```

Some of these macros are already defined as temporary placeholders in the lwarp core, so they must be redefined here.

The emulated defaults also work for an emulated print mode inside a `lateximage`:

```
\def\hdashline{
%     \adl@hdashline\adl@ihdashline
    \adl@hdashline\adl@inactivehdl
}
\def\adl@hdashline#1{\noalign{\ifnum0=`}\fi
%         \ifadl@zwhrule \vskip-\arrayrulewidth
%         \else
%             \adl@hline\adl@connect\arrayrulewidth
                \hrule \@height \arrayrulewidth% lwarp
%         \fi
        \@ifnextchar[%]
                    {#1}%
                    {#1[%
%                         \dashlinedash/\dashlinegap
                       1pt/1pt
                    ]}}
% \def\adl@ihdashline[#1/#2]{\ifnum0=`{\fi}%
%         \multispan{\adl@columns}\unskip \adl@hcline\z@[#1/#2]%
%         \noalign{\ifnum0=`}\fi
%         \futurelet\@tempa\adl@xhline}
\def\adl@inactivehdl[#1/#2]{
%         \ifadl@zwhrule \vskip-\arrayrulewidth \fi
        \hrule\@height\arrayrulewidth
        \futurelet\@tempa\adl@xhline}
\def\adl@xhline{\ifx\@tempa\hline \adl@ixhline\fi
        \ifx\@tempa\hdashline \adl@ixhline\fi
        \ifnum0=`{\fi}}
\def\adl@ixhline{\vskip\doublerulesep \adl@hline\relax\doublerulesep}
\def\adl@hline#1#2{%
% \@tempcnta#2
%         \global\advance\adl@totalheight\@tempcnta
%         \xdef\adl@rowsL{\adl@rowsL
%                 (#1/\number\@tempcnta);}%
%         \xdef\adl@rowsR{\adl@rowsR
%                 (#1/\number\@tempcnta);}
}

\def\cdashline#1{\noalign{\ifnum0=`}\fi
        \@ifnextchar[%]
%                     {\adl@cdline[#1]}%
%                     {\adl@cdline[#1][\dashlinedash/\dashlinegap]}
                    {\adl@inactivecdl[#1]}%
```

```
                    {\adl@inactivecdl[#1][\dashlinedash/\dashlinegap]}
}

\def\adl@inactivecdl[#1-#2][#3]{\ifnum0=‘{\fi}\cline{#1-#2}}
```

File 27 **lwarp-asymptote.sty**

§ 124 Package

asymptote

(*Emulates or patches code by* Andy Hammerlindl, John Bowman, Tom Prince.)

Pkg asymptote asymptote is patched for use by lwarp.

To compile:

```
pdflatex project.tex
asy project-*.asy
pdflatex project.tex

lwarpmk print
asy project-*.asy
lwarpmk print1
lwarpmk print1

lwarpmk html
asy project_html-*.asy
lwarpmk html1
lwarpmk html1
lwarpmk limages
```

for HTML output:

```
\LWR@ProvidesPackagePass{asymptote}[2016/11/26]

\BeforeBeginEnvironment{asy}{\begin{lateximage}[(-asymptote-~\packagediagramname)]}
\AfterEndEnvironment{asy}{\end{lateximage}}

\xpatchcmd{\asyinclude}
    {\begingroup}
    {\begin{lateximage}[(-asymptote-~\packagediagramname)]}
    {}
    {\LWR@patcherror{asymptote}{asyinclude-begingroup}}

\xpatchcmd{\asyinclude}
    {\endgroup}
    {\end{lateximage}}
    {}
    {\LWR@patcherror{asymptote}{asyinclude-endgroup}}
```

File 28 **lwarp-atbegshi.sty**

§ 125 Package

atbegshi

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg atbegshi Emulated.

for HTML output: Discard all options for lwarp-atbegshi:

```
\LWR@ProvidesPackageDrop{atbegshi}[2011/10/05]

\newcommand*{\AtBeginShipout}[1]{}
\newbox\AtBeginShipoutBox
\newcommand*{\AtBeginShipoutNext}[1]{}
\newcommand*{\AtBeginShipoutFirst}[1]{}
\newcommand*{\AtBeginShipoutDiscard}{}
\newcommand*{\AtBeginShipoutInit}{}
\newcommand*{\AtBeginShipoutAddToBox}[1]{}
\newcommand*{\AtBeginShipoutAddToBoxForeground}[1]{}
\newcommand*{\AtBeginShipoutUpperLeft}[1]{}
\newcommand*{\AtBeginShipoutUpperLeftForeground}[1]{}
\newcommand*{\AtBeginShipoutOriginalShipout}[1]{}
\def\AtBeginShipoutBoxWidth{0pt}
\def\AtBeginShipoutBoxHeight{0pt}
\def\AtBeginShipoutBoxDepth{0pt}

```

File 29 **lwarp-attachfile.sty**

§ 126 Package

attachfile

(*Emulates or patches code by* Scott Pakin.)

Pkg attachfile attachfile is patched for use by lwarp.

⚠ Metadata is ignored for now.

for HTML output:

```
\LWR@ProvidesPackagePass{attachfile}[2016/09/18]
```

Encloses each icon:

```
\newenvironment*{LWR@attachfile@icon}
{
    \begin{lateximage}*%
        [-attachfile-]%
        [%
            \detokenize\expandafter{\atfi@icon@icon}-%
```

```
            \detokenize\expandafter{\atfi@color@rgb}%
        ]%
}
{
    \end{lateximage}
}
```

Each icon is enclosed inside a LWR@attachfile@icon environment:

```
\xpretocmd{\atfi@acroGraph}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroGraph}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPaperclip}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPaperclip}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPushPin}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPushPin}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}
```

Disable PDF file embedding:

```
\DeclareRobustCommand{\atfi@embedfile}[1]{}
```

The displayed output for an \attachfile reference:

```
\newcommand*{\LWR@attachfile@appearance}{}

\DeclareRobustCommand{\atfi@set@appearance}[1]{%
    \def\LWR@attachfile@appearance{#1}%
}
```

A file annotation becomes a reference:

```
\DeclareRobustCommand{\atfi@insert@file@annot}[1]{%
    \href{#1}{\LWR@attachfile@appearance}%
}
```

File 30 **lwarp-attachfile2.sty**

§ 127 Package

attachfile2

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg attachfile2 attachfile2 is patched for use by lwarp.

⚠ Metadata is ignored for now.

for HTML output:

```
\LWR@ProvidesPackagePass{attachfile2}[2016/05/16]
```

Adds memory of the selected color:

```
\def\LWR@attachfiletwo@color{}%

\define@key{AtFi}{color}{%
    \def\LWR@attachfiletwo@color{#1}%   lwarp
  \HyColor@AttachfileColor{#1}%
          \atfi@color@tex\atfi@color@inline\atfi@color@annot
          {attachfile2}{color}%
}
```

Encloses each icon:

```
\newenvironment*{LWR@attachfile@icon}
{
    \begin{lateximage}*%
        [-attachfile-]%
        [%
            \detokenize\expandafter{\atfi@icon@icon}-%
            \detokenize\expandafter{\LWR@attachfiletwo@color}%
        ]%
}
{
    \end{lateximage}
}
```

Each icon is enclosed inside a `LWR@attachfile@icon` environment:

```
\xpretocmd{\atfi@acroGraph}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroGraph}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPaperclip}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPaperclip}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPushPin}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPushPin}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}
```

Disable PDF file embedding:

```
\DeclareRobustCommand{\atfi@embedfile}[1]{}
```

The displayed output for an `\attachfile` reference:

```
\newcommand*{\LWR@attachfile@appearance}{}

\def\atfi@set@appearance@icon{%
    \atfi@set@appearance{\csname atfi@acro\atfi@icon@icon\endcsname}%
}

\DeclareRobustCommand{\atfi@set@appearance}[1]{%
    \def\LWR@attachfile@appearance{#1}%
}
```

A file annotation becomes a reference:

```
\DeclareRobustCommand{\atfi@insert@file@annot}[1]{%
    \href{#1}{\LWR@attachfile@appearance}%
}
```

Modified for text color:

```
\DeclareRobustCommand{\notextattachfile}[2][]{%
  \begingroup
    \atfi@setup{#1}%
    \ifatfi@print
      \leavevmode
      \begingroup
        \HyColor@UseColor\atfi@color@tex
        \LWR@textcurrentcolor{#2}%      lwarp
% \strut
      \endgroup
%     \else
%       \sbox\ltx@zero{#2\strut}%
%       \makebox[\wd0]{}%
    \fi
  \endgroup
}
```

Modified to draw the icon:

```
\DeclareRobustCommand{\noattachfile}[1][]{%
  \begingroup
    \atfi@setup{#1}%
    \atfi@set@appearance@icon
    \ifatfi@print
        \LWR@attachfile@appearance%     lwarp
%       \expandafter
%       \atfi@refxform\csname atfi@appobj@\atfi@icon@icon\endcsname
%     \else
%       \makebox[\atfi@appearancewidth]{}%
    \fi
  \endgroup
}
```

File 31 **lwarp-authblk.sty**

§ 128 Package

authblk

(*Emulates or patches code by* Patrick W. Daly.)

Pkg authblk

authblk is patched for HTML.

package support

⚠ load order

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

\published and \subtitle

If using the titling package, additional titlepage fields for \published and \subtitle

may be added by using \AddSubtitlePublished in the preamble. See section 65.8.

(*Emulates or patches code by* Patrick W. Daly.)

for HTML output: Require that authblk be loaded before titling:

```
\@ifpackageloaded{titling}{
\PackageError{lwarp-authblk}
{Package authblk must be loaded before titling}
{Titling appends authblk's author macro, so authblk must be loaded first.}
}
{}
```

Load authblk:

```
\LWR@ProvidesPackagePass{authblk}[2001/02/27]
```

Patch to add a class for the affiliation:

```
\LetLtxMacro\LWRAB@affil\affil

\renewcommand{\affil}[2][]{%
\LWRAB@affil[#1]{\protect\InlineClass{affiliation}{#2}}
}
```

Create an HTML break for an \authorcr:

```
\renewcommand*{\authorcr}{\protect\LWR@newlinebr}
```

File 32 **lwarp-axessibility.sty**

§ 129 Package axessibility

Pkg axessibility axessibility is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{axessibility}

\newcommand{\wrap}[1]{}
```

File 33 **lwarp-axodraw2.sty**

§ 130 Package axodraw2

(*Emulates or patches code by* John C. Collins, J.A.M. Vermaseren.)

Pkg axodraw2 axodraw2 is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{axodraw2}[2018/02/15]
```

```
\BeforeBeginEnvironment{axopicture}{\begin{lateximage}[(-axopicture-~\packagediagramname)]}

\AfterEndEnvironment{axopicture}{\end{lateximage}}
```

File 34 **lwarp-backref.sty**

§ 131 Package backref

(*Emulates or patches code by* David Carlisle and Sebastian Rahtz.)

Pkg backref backref is patched for use by lwarp.

⚠ loading Note that backref must be explicitly loaded, and is not automatically loaded by hyperref when generating HTML output.

for HTML output:

```
\LWR@ProvidesPackagePass{backref}[2016/05/21]
```

Force the hyperref option:

```
\def\backref{}\let\backrefxxx\hyper@section@backref
```

File 35 **lwarp-balance.sty**

§ 132 Package balance

(*Emulates or patches code by* Patrick W. Daly.)

Pkg balance Emulated.

for HTML output: Discard all options for lwarp-balance:

```
\LWR@ProvidesPackageDrop{balance}[1999/02/23]

\newcommand*{\balance}{}
\newcommand*{\nobalance}{}
```

File 36 **lwarp-bbding.sty**

§ 133 Package bbding

(*Emulates or patches code by* Karel Horak, Peter Møller Neergaard.)

Pkg bbding bbding is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bbding}[1999/04/15]
```

```
\newcommand*{\LWR@bbdingsymbol}[2]{\HTMLunicode{#2}}

\newcommand{\LWR@HTML@ScissorRightBrokenBottom}{\LWR@bbdingsymbol{000}  {2701}}
\newcommand{\LWR@HTML@ScissorRight}{\LWR@bbdingsymbol{001}              {2702}}
\newcommand{\LWR@HTML@ScissorRightBrokenTop}{\LWR@bbdingsymbol{002}    {2703}}
\newcommand{\LWR@HTML@ScissorLeftBrokenBottom}{\LWR@bbdingsymbol{003}  {2701}}
\newcommand{\LWR@HTML@ScissorLeft}{\LWR@bbdingsymbol{004}              {2702}}
\newcommand{\LWR@HTML@ScissorLeftBrokenTop}{\LWR@bbdingsymbol{005}     {2703}}
\newcommand{\LWR@HTML@ScissorHollowRight}{\LWR@bbdingsymbol{006}       {2704}}
\newcommand{\LWR@HTML@ScissorHollowLeft}{\LWR@bbdingsymbol{007}        {2704}}
\newcommand{\LWR@HTML@Phone}{\LWR@bbdingsymbol{010}                    {260E}}
\newcommand{\LWR@HTML@PhoneHandset}{\LWR@bbdingsymbol{011}             {2706}}
\newcommand{\LWR@HTML@Tape}{\LWR@bbdingsymbol{012}                     {2707}}
\newcommand{\LWR@HTML@Plane}{\LWR@bbdingsymbol{013}                    {2708}}
\newcommand{\LWR@HTML@Envelope}{\LWR@bbdingsymbol{014}                 {2709}}
\newcommand{\LWR@HTML@HandCuffRight}{\LWR@bbdingsymbol{015}            {261B}}
\newcommand{\LWR@HTML@HandCuffLeft}{\LWR@bbdingsymbol{016}             {261A}}
\newcommand{\LWR@HTML@HandCuffRightUp}{\LWR@bbdingsymbol{017}          {261D}}
\newcommand{\LWR@HTML@HandCuffLeftUp}{\LWR@bbdingsymbol{020}           {261F}}
\newcommand{\LWR@HTML@HandRight}{\LWR@bbdingsymbol{021}                {261E}}
\newcommand{\LWR@HTML@HandLeft}{\LWR@bbdingsymbol{022}                 {261C}}
\newcommand{\LWR@HTML@HandRightUp}{\LWR@bbdingsymbol{023}              {261D}}
\newcommand{\LWR@HTML@HandLeftUp}{\LWR@bbdingsymbol{024}               {261F}}
\newcommand{\LWR@HTML@Peace}{\LWR@bbdingsymbol{025}                    {270C}}
\newcommand{\LWR@HTML@HandPencilLeft}{\LWR@bbdingsymbol{026}           {270D}}
\newcommand{\LWR@HTML@PencilRight}{\LWR@bbdingsymbol{027}              {270F}}
\newcommand{\LWR@HTML@PencilLeft}{\LWR@bbdingsymbol{030}               {270F}}
\newcommand{\LWR@HTML@PencilRightUp}{\LWR@bbdingsymbol{031}            {2710}}
\newcommand{\LWR@HTML@PencilLeftUp}{\LWR@bbdingsymbol{032}             {2710}}
\newcommand{\LWR@HTML@PencilRightDown}{\LWR@bbdingsymbol{033}          {270E}}
\newcommand{\LWR@HTML@PencilLeftDown}{\LWR@bbdingsymbol{034}           {270E}}
\newcommand{\LWR@HTML@NibRight}{\LWR@bbdingsymbol{035}                 {2711}}
\newcommand{\LWR@HTML@NibLeft}{\LWR@bbdingsymbol{036}                  {2711}}
\newcommand{\LWR@HTML@NibSolidRight}{\LWR@bbdingsymbol{037}            {2712}}
\newcommand{\LWR@HTML@NibSolidLeft}{\LWR@bbdingsymbol{040}             {2712}}
\newcommand{\LWR@HTML@Checkmark}{\LWR@bbdingsymbol{041}                {2713}}
\newcommand{\LWR@HTML@CheckmarkBold}{\LWR@bbdingsymbol{042}            {2714}}
\newcommand{\LWR@HTML@XSolid}{\LWR@bbdingsymbol{043}                   {2715}}
\newcommand{\LWR@HTML@XSolidBold}{\LWR@bbdingsymbol{044}               {2716}}
\newcommand{\LWR@HTML@XSolidBrush}{\LWR@bbdingsymbol{045}              {2717}}
\newcommand{\LWR@HTML@PlusOutline}{\LWR@bbdingsymbol{046}              {2719}}
\newcommand{\LWR@HTML@Plus}{\LWR@bbdingsymbol{047}                     {271A}}
\newcommand{\LWR@HTML@PlusCenterOpen}{\LWR@bbdingsymbol{050}           {271C}}
\newcommand{\LWR@HTML@PlusThinCenterOpen}{\LWR@bbdingsymbol{051}       {271B}}
\newcommand{\LWR@HTML@Cross}{\LWR@bbdingsymbol{052}                    {271D}}
\newcommand{\LWR@HTML@CrossOpenShadow}{\LWR@bbdingsymbol{053}          {271E}}
\newcommand{\LWR@HTML@CrossOutline}{\LWR@bbdingsymbol{054}             {271F}}
\newcommand{\LWR@HTML@CrossBoldOutline}{\LWR@bbdingsymbol{055}         {271F}}
\newcommand{\LWR@HTML@CrossMaltese}{\LWR@bbdingsymbol{056}             {2720}}
\newcommand{\LWR@HTML@DavidStarSolid}{\LWR@bbdingsymbol{057}           {2721}}
\newcommand{\LWR@HTML@DavidStar}{\LWR@bbdingsymbol{060}                {2721}}
\newcommand{\LWR@HTML@FourAsterisk}{\LWR@bbdingsymbol{061}             {2722}}
\newcommand{\LWR@HTML@JackStar}{\LWR@bbdingsymbol{062}                 {2723}}
\newcommand{\LWR@HTML@JackStarBold}{\LWR@bbdingsymbol{063}             {2724}}
\newcommand{\LWR@HTML@CrossClowerTips}{\LWR@bbdingsymbol{064}          {2725}}
```

```
\newcommand{\LWR@HTML@FourStar}{\LWR@bbdingsymbol{065}                  {2726}}
\newcommand{\LWR@HTML@FourStarOpen}{\LWR@bbdingsymbol{066}              {2727}}
\newcommand{\LWR@HTML@FiveStarLines}{\LWR@bbdingsymbol{067}             {2729}}
\newcommand{\LWR@HTML@FiveStar}{\LWR@bbdingsymbol{070}                  {2605}}
\newcommand{\LWR@HTML@FiveStarOpen}{\LWR@bbdingsymbol{071}              {2729}}
\newcommand{\LWR@HTML@FiveStarOpenCircled}{\LWR@bbdingsymbol{072}       {272A}}
\newcommand{\LWR@HTML@FiveStarCenterOpen}{\LWR@bbdingsymbol{073}        {272B}}
\newcommand{\LWR@HTML@FiveStarOpenDotted}{\LWR@bbdingsymbol{074}        {272C}}
\newcommand{\LWR@HTML@FiveStarOutline}{\LWR@bbdingsymbol{075}           {272D}}
\newcommand{\LWR@HTML@FiveStarOutlineHeavy}{\LWR@bbdingsymbol{076}      {272E}}
\newcommand{\LWR@HTML@FiveStarConvex}{\LWR@bbdingsymbol{077}            {272F}}
\newcommand{\LWR@HTML@FiveStarShadow}{\LWR@bbdingsymbol{100}            {2730}}
\newcommand{\LWR@HTML@AsteriskBold}{\LWR@bbdingsymbol{101}              {2731}}
\newcommand{\LWR@HTML@AsteriskCenterOpen}{\LWR@bbdingsymbol{102}        {2732}}
\newcommand{\LWR@HTML@AsteriskThin}{\LWR@bbdingsymbol{103}              {273B}}
\newcommand{\LWR@HTML@AsteriskThinCenterOpen}{\LWR@bbdingsymbol{104}    {273C}}
\newcommand{\LWR@HTML@EightStarTaper}{\LWR@bbdingsymbol{105}            {2733}}
\newcommand{\LWR@HTML@EightStarConvex}{\LWR@bbdingsymbol{106}           {2735}}
\newcommand{\LWR@HTML@SixStar}{\LWR@bbdingsymbol{107}                   {2736}}
\newcommand{\LWR@HTML@EightStar}{\LWR@bbdingsymbol{110}                 {2737}}
\newcommand{\LWR@HTML@EightStarBold}{\LWR@bbdingsymbol{111}             {2738}}
\newcommand{\LWR@HTML@TwelweStar}{\LWR@bbdingsymbol{112}                {2739}}
\newcommand{\LWR@HTML@SixteenStarLight}{\LWR@bbdingsymbol{113}          {273A}}
\newcommand{\LWR@HTML@SixFlowerPetalRemoved}{\LWR@bbdingsymbol{114}     {273B}}
\newcommand{\LWR@HTML@SixFlowerOpenCenter}{\LWR@bbdingsymbol{115}       {273C}}
\newcommand{\LWR@HTML@Asterisk}{\LWR@bbdingsymbol{116}                  {273D}}
\newcommand{\LWR@HTML@SixFlowerAlternate}{\LWR@bbdingsymbol{117}        {273E}}
\newcommand{\LWR@HTML@FiveFlowerPetal}{\LWR@bbdingsymbol{120}           {273F}}
\newcommand{\LWR@HTML@SixFlowerPetalDotted}{\LWR@bbdingsymbol{121}      {2740}}
\newcommand{\LWR@HTML@FiveFlowerOpen}{\LWR@bbdingsymbol{122}            {2740}}
\newcommand{\LWR@HTML@EightFlowerPetal}{\LWR@bbdingsymbol{123}          {2741}}
\newcommand{\LWR@HTML@SunshineOpenCircled}{\LWR@bbdingsymbol{124}       {2742}}
\newcommand{\LWR@HTML@SixFlowerAltPetal}{\LWR@bbdingsymbol{125}         {2743}}
\newcommand{\LWR@HTML@FourClowerOpen}{\LWR@bbdingsymbol{126}            {273F}}
\newcommand{\LWR@HTML@FourClowerSolid}{\LWR@bbdingsymbol{127}           {273F}}
\newcommand{\LWR@HTML@AsteriskRoundedEnds}{\LWR@bbdingsymbol{130}       {2749}}
\newcommand{\LWR@HTML@EightFlowerPetalRemoved}{\LWR@bbdingsymbol{131}   {274A}}
\newcommand{\LWR@HTML@EightAsterisk}{\LWR@bbdingsymbol{132}             {274B}}
\newcommand{\LWR@HTML@SixFlowerRemovedOpenPetal}{\LWR@bbdingsymbol{133}  {2740}}
\newcommand{\LWR@HTML@SparkleBold}{\LWR@bbdingsymbol{134}                {2748}}
\newcommand{\LWR@HTML@Sparkle}{\LWR@bbdingsymbol{135}                    {2747}}
\newcommand{\LWR@HTML@SnowflakeChevron}{\LWR@bbdingsymbol{136}           {2744}}
\newcommand{\LWR@HTML@SnowflakeChevronBold}{\LWR@bbdingsymbol{137}       {2746}}
\newcommand{\LWR@HTML@Snowflake}{\LWR@bbdingsymbol{140}                  {2744}}
\newcommand{\LWR@HTML@CircleSolid}{\LWR@bbdingsymbol{141}                {25CF}}
\newcommand{\LWR@HTML@Ellipse}{\LWR@bbdingsymbol{142}                    {274D}}
\newcommand{\LWR@HTML@EllipseSolid}{\LWR@bbdingsymbol{143}               {25CF}}
\newcommand{\LWR@HTML@CircleShadow}{\LWR@bbdingsymbol{144}               {274D}}
\newcommand{\LWR@HTML@EllipseShadow}{\LWR@bbdingsymbol{145}              {274D}}
\newcommand{\LWR@HTML@Square}{\LWR@bbdingsymbol{146}                     {25A1}}
\newcommand{\LWR@HTML@SquareSolid}{\LWR@bbdingsymbol{147}                {25A0}}
\newcommand{\LWR@HTML@SquareShadowBottomRight}{\LWR@bbdingsymbol{150}    {2751}}
\newcommand{\LWR@HTML@SquareShadowTopRight}{\LWR@bbdingsymbol{151}       {2752}}
\newcommand{\LWR@HTML@SquareShadowTopLeft}{\LWR@bbdingsymbol{152}        {2752}}
\newcommand{\LWR@HTML@SquareCastShadowBottomRight}{\LWR@bbdingsymbol{153} {2751}}
```

```
\newcommand{\LWR@HTML@SquareCastShadowTopRight}{\LWR@bbdingsymbol{154}   {2752}}
\newcommand{\LWR@HTML@SquareCastShadowTopLeft}{\LWR@bbdingsymbol{155}   {2752}}
\newcommand{\LWR@HTML@TriangleUp}{\LWR@bbdingsymbol{156}                {25B2}}
\newcommand{\LWR@HTML@TriangleDown}{\LWR@bbdingsymbol{157}              {25BC}}
\newcommand{\LWR@HTML@DiamondSolid}{\LWR@bbdingsymbol{160}              {25C6}}
\newcommand{\LWR@HTML@OrnamentDiamondSolid}{\LWR@bbdingsymbol{161}     {2756}}
\newcommand{\LWR@HTML@HalfCircleRight}{\LWR@bbdingsymbol{162}           {25D7}}
\newcommand{\LWR@HTML@HalfCircleLeft}{\LWR@bbdingsymbol{163}            {25D6}}
\newcommand{\LWR@HTML@RectangleThin}{\LWR@bbdingsymbol{164}             {2758}}
\newcommand{\LWR@HTML@Rectangle}{\LWR@bbdingsymbol{165}                 {2759}}
\newcommand{\LWR@HTML@RectangleBold}{\LWR@bbdingsymbol{166}             {275A}}
\newcommand{\LWR@HTML@ArrowBoldRightStrobe}{\LWR@bbdingsymbol{167}     {27A0}}
\newcommand{\LWR@HTML@ArrowBoldUpRight}{\LWR@bbdingsymbol{170}         {27A6}}
\newcommand{\LWR@HTML@ArrowBoldDownRight}{\LWR@bbdingsymbol{171}       {27A5}}
\newcommand{\LWR@HTML@ArrowBoldRightShort}{\LWR@bbdingsymbol{172}      {27A7}}
\newcommand{\LWR@HTML@ArrowBoldRightCircled}{\LWR@bbdingsymbol{173}    {27B2}}


\LWR@formatted{ScissorRightBrokenBottom}
\LWR@formatted{ScissorRight}
\LWR@formatted{ScissorRightBrokenTop}
\LWR@formatted{ScissorLeftBrokenBottom}
\LWR@formatted{ScissorLeft}
\LWR@formatted{ScissorLeftBrokenTop}
\LWR@formatted{ScissorHollowRight}
\LWR@formatted{ScissorHollowLeft}
\LWR@formatted{Phone}
\LWR@formatted{PhoneHandset}
\LWR@formatted{Tape}
\LWR@formatted{Plane}
\LWR@formatted{Envelope}
\LWR@formatted{HandCuffRight}
\LWR@formatted{HandCuffLeft}
\LWR@formatted{HandCuffRightUp}
\LWR@formatted{HandCuffLeftUp}
\LWR@formatted{HandRight}
\LWR@formatted{HandLeft}
\LWR@formatted{HandRightUp}
\LWR@formatted{HandLeftUp}
\LWR@formatted{Peace}
\LWR@formatted{HandPencilLeft}
\LWR@formatted{PencilRight}
\LWR@formatted{PencilLeft}
\LWR@formatted{PencilRightUp}
\LWR@formatted{PencilLeftUp}
\LWR@formatted{PencilRightDown}
\LWR@formatted{PencilLeftDown}
\LWR@formatted{NibRight}
\LWR@formatted{NibLeft}
\LWR@formatted{NibSolidRight}
\LWR@formatted{NibSolidLeft}
\LWR@formatted{Checkmark}
\LWR@formatted{CheckmarkBold}
\LWR@formatted{XSolid}
\LWR@formatted{XSolidBold}
```

```
\LWR@formatted{XSolidBrush}
\LWR@formatted{PlusOutline}
\LWR@formatted{Plus}
\LWR@formatted{PlusCenterOpen}
\LWR@formatted{PlusThinCenterOpen}
\LWR@formatted{Cross}
\LWR@formatted{CrossOpenShadow}
\LWR@formatted{CrossOutline}
\LWR@formatted{CrossBoldOutline}
\LWR@formatted{CrossMaltese}
\LWR@formatted{DavidStarSolid}
\LWR@formatted{DavidStar}
\LWR@formatted{FourAsterisk}
\LWR@formatted{JackStar}
\LWR@formatted{JackStarBold}
\LWR@formatted{CrossClowerTips}
\LWR@formatted{FourStar}
\LWR@formatted{FourStarOpen}
\LWR@formatted{FiveStarLines}
\LWR@formatted{FiveStar}
\LWR@formatted{FiveStarOpen}
\LWR@formatted{FiveStarOpenCircled}
\LWR@formatted{FiveStarCenterOpen}
\LWR@formatted{FiveStarOpenDotted}
\LWR@formatted{FiveStarOutline}
\LWR@formatted{FiveStarOutlineHeavy}
\LWR@formatted{FiveStarConvex}
\LWR@formatted{FiveStarShadow}
\LWR@formatted{AsteriskBold}
\LWR@formatted{AsteriskCenterOpen}
\LWR@formatted{AsteriskThin}
\LWR@formatted{AsteriskThinCenterOpen}
\LWR@formatted{EightStarTaper}
\LWR@formatted{EightStarConvex}
\LWR@formatted{SixStar}
\LWR@formatted{EightStar}
\LWR@formatted{EightStarBold}
\LWR@formatted{TwelweStar}
\LWR@formatted{SixteenStarLight}
\LWR@formatted{SixFlowerPetalRemoved}
\LWR@formatted{SixFlowerOpenCenter}
\LWR@formatted{Asterisk}
\LWR@formatted{SixFlowerAlternate}
\LWR@formatted{FiveFlowerPetal}
\LWR@formatted{SixFlowerPetalDotted}
\LWR@formatted{FiveFlowerOpen}
\LWR@formatted{EightFlowerPetal}
\LWR@formatted{SunshineOpenCircled}
\LWR@formatted{SixFlowerAltPetal}
\LWR@formatted{FourClowerOpen}
\LWR@formatted{FourClowerSolid}
\LWR@formatted{AsteriskRoundedEnds}
\LWR@formatted{EightFlowerPetalRemoved}
\LWR@formatted{EightAsterisk}
\LWR@formatted{SixFlowerRemovedOpenPetal}
```

```
\LWR@formatted{SparkleBold}
\LWR@formatted{Sparkle}
\LWR@formatted{SnowflakeChevron}
\LWR@formatted{SnowflakeChevronBold}
\LWR@formatted{Snowflake}
\LWR@formatted{CircleSolid}
\LWR@formatted{Ellipse}
\LWR@formatted{EllipseSolid}
\LWR@formatted{CircleShadow}
\LWR@formatted{EllipseShadow}
\LWR@formatted{Square}
\LWR@formatted{SquareSolid}
\LWR@formatted{SquareShadowBottomRight}
\LWR@formatted{SquareShadowTopRight}
\LWR@formatted{SquareShadowTopLeft}
\LWR@formatted{SquareCastShadowBottomRight}
\LWR@formatted{SquareCastShadowTopRight}
\LWR@formatted{SquareCastShadowTopLeft}
\LWR@formatted{TriangleUp}
\LWR@formatted{TriangleDown}
\LWR@formatted{DiamondSolid}
\LWR@formatted{OrnamentDiamondSolid}
\LWR@formatted{HalfCircleRight}
\LWR@formatted{HalfCircleLeft}
\LWR@formatted{RectangleThin}
\LWR@formatted{Rectangle}
\LWR@formatted{RectangleBold}
\LWR@formatted{ArrowBoldRightStrobe}
\LWR@formatted{ArrowBoldUpRight}
\LWR@formatted{ArrowBoldDownRight}
\LWR@formatted{ArrowBoldRightShort}
\LWR@formatted{ArrowBoldRightCircled}
```

File 37 **lwarp-biblatex.sty**

§ 134 Package

biblatex

(*Emulates or patches code by* Philipp Lehman.)

Pkg biblatex When biblatex is used, modifications from newfloat may have to be undone.

for HTML output:

1. lwarp uses newfloat.
2. For classes with chapters which newfloat does not know about, such as CTEX-related classes, newfloat may modify `\addtocontents`.
3. biblatex, though, wants to patch `\addtocontents`, which causes an error if `\addtocontents` has been changed.
4. Therefore, `\addtocontents` is restored to its original here, since biblatex is about to be loaded.
5. This means that the newfloat's `chapterlistsgaps` option may no longer work.

```
\ifdef{\newfloat@addtocontents@ORI}{
    \let\addtocontents\newfloat@addtocontents@ORI
}{}

\LWR@ProvidesPackagePass{biblatex}[2018/03/04]
```

File 38 **lwarp-bibunits.sty**

§ 135 Package

bibunits

(*Emulates or patches code by* Thorsten Hansen.)

Pkg bibunits bibunits is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bibunits}[2004/05/12]

\def\bu@bibdata{\BaseJobname}
```

File 39 **lwarp-bigdelim.sty**

§ 136 Package

bigdelim

(*Emulates or patches code by* Piet van Oostrum, Øystein Bache, Jerry Leichter.)

Pkg bigdelim bigdelim is used as-is for print or `lateximage`, and patched for HTML.

The delimiters are displayed in HTML by printing the delimiter, the text, and a thick border across the side of the `\multirow` which indicates the actual height of the delimiter. The delimiter character is given a `<span>` class of `ldelim` or `rdelim`, and the default CSS sets this to `font-size:200%`

⚠ use \mrowcell

`\ldelim` and `\rdelim` use `\multirow`, so `\mrowcell` must be used in the proper number of empty cells in the same column below `\ldelim` or `\rdelim`, but not in cells which are above or below the delimiter:

```
\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\{}{2}{.25in}[left ] & c & d \\
\mrowcell & e & f \\
<empty> & g & h \\
\end{tabular}
```

<>	a	b
left {	c	d
	e	f
<>	g	h

for HTML output: First, remove the temporary definitions of `\ldelim` and `\rdelim`, which were previously defined for tabular scanning in case bigdelim was not loaded:

```
\let\ldelim\relax
\let\rdelim\relax
```

Next, load the package's new definitions:

```
\LWR@ProvidesPackagePass{bigdelim}[2018/08/03]
```

`\ldelim` `\rdelim` {⟨*1:delimiter*⟩} {⟨*2:#rows*⟩} {⟨*3:width*⟩} [⟨*4:text*⟩]

```
\NewDocumentCommand{\LWR@HTML@ldelim}{m m m O{}}{%
\renewcommand{\LWR@multirowborder}{right}%
\multirow{#2}{#3}{#4 \InlineClass{ldelim}{#1}}%
}

\LWR@formatted{ldelim}

\NewDocumentCommand{\LWR@HTML@rdelim}{m m m O{}}{%
\renewcommand{\LWR@multirowborder}{left}%
\multirow{#2}{#3}{\InlineClass{rdelim}{#1} #4}%
}

\LWR@formatted{rdelim}
```

File 40 **lwarp-bigfoot.sty**

§ 137 Package

bigfoot

Pkg bigfoot bigfoot is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{bigfoot}[2015/08/30]

\RequirePackage{manyfoot}
\RequirePackage{perpage}

\def\RestyleFootnote#1#2{}
\def\FootnoteSpecific#1{}
\def\DefineFootnoteStack#1{}
\def\PushFootnoteMark#1{}
\def\PopFootnoteMark#1{}
\def\hfootfraction{0.9}
\def\vtypefraction{0.7}
\def\FootnoteMinimum{1sp}
\def\FootnoteMainMinimum{0pt}
\newcount\bigfoottolerance
\bigfoottolerance=100
\providecommand\footnotecarryratio{2}
```

File 41 **lwarp-bigstrut.sty**

§ 138 Package bigstrut

(*Emulates or patches code by* Piet van Oostrum, Øystein Bache, Jerry Leichter.)

Pkg bigstrut bigstrut is used as-is for print or lateximage, and patched for HTML.

for HTML output:

```
\LWR@ProvidesPackagePass{bigstrut}[2018/08/03]

\LetLtxMacro\LWR@origbigstrut\bigstrut

\renewcommand\bigstrut[1][x]{}

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\bigstrut\LWR@origbigstrut%
}
```

File 42 **lwarp-bitpattern.sty**

§ 139 Package bitpattern

(*Emulates or patches code by* Jean-Marc Bourguet.)

Pkg bitpattern bitpattern is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bitpattern}[2015/12/11]

\xpatchcmd{\bitpattern}
    {\begingroup}
    {\begin{lateximage}[(-bitpattern-~\packagediagramname)]}
    {}
    {\LWR@patcherror{bitpattern}{bitpattern}}

\xpatchcmd{\bp@Done}
    {\endgroup}
    {\end{lateximage}}
    {}
    {\LWR@patcherror{bitpattern}{bp@Done}}
```

File 43 **lwarp-blowup.sty**

§ 140 Package blowup

Pkg blowup blowup is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{blowup}[2018/01/02]
\newcommand*\blowUp[1]{}
```

File 44 **lwarp-booklet.sty**

§ 141 Package booklet

(*Emulates or patches code by* Peter Wilson.)

Pkg booklet booklet is nullified.

for HTML output:

```
\LWR@ProvidesPackageDrop{booklet}[2009/09/02]
\newdimen\pageseplength
\newdimen\pagesepwidth
\newdimen\pagesepoffset
\newif\ifsidebyside     \sidebysidetrue
\newif\ifuselandscape   \uselandscapefalse
\newif\ifprintoption    \printoptionfalse
\newcommand*{\pagespersignature}[1]{}
\def\magstepminus#1{}
\newcommand*{\target}[3]{}
\newcommand*{\source}[3]{}
\newcommand*{\setpdftargetpages}{}
\newcommand*{\setdvipstargetpages}{}
\newcommand*{\targettopbottom}{}
\newcommand*{\twoupemptypage}{}
\newcommand*{\twoupclearpage}{}
\newcommand*{\checkforlandscape}{}
```

File 45 **lwarp-bookmark.sty**

§ 142 Package bookmark

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg bookmark bookmark is emulated.

for HTML output: Discard all options for lwarp-bookmark:

```
\LWR@ProvidesPackageDrop{bookmark}[2016/05/17]
\newcommand*{\bookmarksetup}[1]{}
\newcommand*{\bookmarksetupnext}[1]{}
\newcommand*{\bookmark}[2][]{}
\newcommand*{\bookmarkdefinestyle}[2]{}
\newcommand*{\bookmarkget}[1]{}
\newcommand{\BookmarkAtEnd}[1]{}
```

File 46 **lwarp-booktabs.sty**

§ 143 Package

booktabs

(*Emulates or patches code by* Simon Fear.)

Pkg booktabs

booktabs is emulated during HTML output, and used as-is during print output and inside an HTML lateximage.

for HTML output:

First, forget the placeholder macros:

```
\LetLtxMacro\toprule\relax
\LetLtxMacro\midrule\relax
\LetLtxMacro\cmidrule\cline
\LetLtxMacro\bottomrule\relax
\LetLtxMacro\addlinespace\relax
\LetLtxMacro\morecmidrules\relax
\LetLtxMacro\specialrule\relax

\LWR@ProvidesPackagePass{booktabs}[2016/04/27]


\DeclareDocumentCommand{\LWR@HTML@toprule}{o d()}%
    {%
        \IfValueTF{#1}%
            {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
            {%
                \ifbool{FormatWP}%
                {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
                {\global\booltrue{LWR@doingtbrule}}%
            }%
    \LWR@getmynexttoken}

\LWR@expandableformatted{toprule}

\DeclareDocumentCommand{\LWR@HTML@midrule}{o d()}%
    {%
        \IfValueTF{#1}%
            {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
            {%
                \ifbool{FormatWP}%
                {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
                {\addtocounter{LWR@hlines}{1}}%
            }%
    \LWR@getmynexttoken}

\LWR@expandableformatted{midrule}

\DeclareDocumentCommand{\LWR@HTML@cmidrule}{O{\LWR@cmidrulewidth} d() m}{%
    \LWR@docmidrule[#1](#2){#3}%
    \LWR@getmynexttoken%
}%
```

```
\LWR@expandableformatted{cmidrule}

\DeclareDocumentCommand{\LWR@HTML@bottomrule}{o d()}{%
    \IfValueTF{#1}%
        {\LWR@docmidrule[#1]()}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {%
            \ifbool{FormatWP}%
            {\LWR@docmidrule[#1]()}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
            {\global\booltrue{LWR@doingtbrule}}%
        }%
    \LWR@getmynexttoken%
}%

\LWR@expandableformatted{bottomrule}

\DeclareDocumentCommand{\LWR@HTML@addlinespace}{o}{}%

\LWR@expandableformatted{addlinespace}

\DeclareDocumentCommand{\LWR@HTML@morecmidrules}{}{}%

\LWR@expandableformatted{morecmidrules}

\DeclareDocumentCommand{\LWR@HTML@specialrule}{m m m d()}%
  {\LWR@docmidrule[#1]()}{1-\arabic{LWR@tabletotalLaTeXcols}}\LWR@getmynexttoken}%

\LWR@expandableformatted{specialrule}
```

File 47 **lwarp-bophook.sty**

§ 144 Package bophook

Pkg bophook bophook is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bophook}[2001/03/29]

\newcommand*{\AtBeginPage}[1]{}
\newcommand*{\PageLayout}[1]{}
```

File 48 **lwarp-bounddvi.sty**

§ 145 Package bounddvi

Pkg bounddvi bounddvi is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bounddvi}[2016/12/28]
```

File 49 **lwarp-boxedminipage2e.sty**

§ 146 Package boxedminipage2e

(*Emulates or patches code by* Scott Pakin.)

Pkg boxedminipage2e boxedminipage2e is emulated.

for HTML output: Discard all options for lwarp-boxedminipage2e:

```
\LWR@ProvidesPackageDrop{boxedminipage2e}[2015/03/09]

\newenvironment{boxedminipage}{%
\begin{BlockClass}{framebox}%
\minipage%
}
{
\endminipage%
\end{BlockClass}
}
```

File 50 **lwarp-breakurl.sty**

§ 147 Package breakurl

(*Emulates or patches code by* Vilar Camara Neto.)

Pkg breakurl breakurl is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{breakurl}[2013/04/10]

\LetLtxMacro\burl\url

\NewDocumentCommand{\LWR@burlaltb}{O{} +m m}{%
\LWR@ensuredoingapar%
\LWR@subhyperref{#2}%
\LWR@subhyperreftext{#3}%
\endgroup% restore catcodes
}

\newrobustcmd*{\burlalt}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@burlaltb%
```

```
}

\LetLtxMacro\urlalt\burlalt
```

File 51 **lwarp-breqn.sty**

§ 148 Package

breqn

(*Emulates or patches code by* Michael J. Downes, Morten Høgholm.)

Pkg breqn breqn is patched for use by lwarp.

⚠ darray darray is not supported.

⚠ MathJax MathJax does not support breqn.

for HTML output:

```
\LWR@ProvidesPackagePass{breqn}[2017/01/27]

\setkeys{breqn}{spread={5pt}}

\def\eqnumside{R}
% \def\eqnumplace{T}

\BeforeBeginEnvironment{dmath}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dmath- \mathimagename]
}

\AfterEndEnvironment{dmath}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dmath*}{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dmath*- \mathimagename]
}

\AfterEndEnvironment{dmath*}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dseries}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dseries- \mathimagename]
}

\AfterEndEnvironment{dseries}{
```

```
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dseries*}{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dseries*- \mathimagename]
}

\AfterEndEnvironment{dseries*}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dgroup}{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dgroup- \mathimagename]
}

\AfterEndEnvironment{dgroup}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dgroup*}{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dgroup*- \mathimagename]
}

\AfterEndEnvironment{dgroup*}{
    \end{lateximage}\end{BlockClass}
}
```

File 52 **lwarp-bsheaders.sty**

§ 149 Package bsheaders

Pkg bsheaders bsheaders is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bsheaders}[1997/10/06]
```

File 53 **lwarp-bxpapersize.sty**

§ 150 Package bxpapersize

Pkg bxpapersize bxpapersize is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bxpapersize}[2017/10/08]

\providecommand*\papersizesetup{\bxpapersizesetup}
\newcommand*\bxpapersizesetup[1]{}
```

File 54 **lwarp-bytefield.sty**

§ 151 Package bytefield

(*Emulates or patches code by* Scott Pakin.)

Pkg bytefield bytefield is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bytefield}[2017/09/15]

\BeforeBeginEnvironment{bytefield}{\begin{lateximage}[(-bytefield-~\packagediagramname)]}

\AfterEndEnvironment{bytefield}{\end{lateximage}}
```

File 55 **lwarp-cancel.sty**

§ 152 Package cancel

Pkg cancel cancel is used as-is for SVG math, and emulated for HTML text output.

for HTML output:

```
\LWR@origRequirePackage{lwarp-xcolor}% for \convertcolorspec
\LWR@ProvidesPackagePass{cancel}[2013/04/12]
```

\cancelto is math-only, so is used as-is.

```
\LetLtxMacro\LWR@origcancel\cancel
\LetLtxMacro\LWR@origbcancel\bcancel
\LetLtxMacro\LWR@origxcancel\xcancel

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\cancel\LWR@origcancel%
\LetLtxMacro\bcancel\LWR@origbcancel%
\LetLtxMacro\xcancel\LWR@origxcancel%
}
```

\LWR@cancelcolor {⟨*text*⟩} {⟨*color*⟩} {⟨*class*⟩} {⟨*colorstyle*⟩} {⟨*FormatWPstyle*⟩}

Add colors if not empty:

```
\newcommand{\LWR@cancelcolor}[5]{%
\ifcsempty{#2}%
{\InlineClass(#5){#3}{#1}}%
{\LWR@htmlspanclass[#5;#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}}%
}
```

\cancel {⟨*text*⟩}

```
\DeclareRobustCommand{\cancel}[1]{%
\begingroup%
\CancelColor%
\LWR@findcurrenttextcolor%
\color{black}%
\LWR@cancelcolor{#1}{LWR@tempcolor}{sout}{text-decoration-color}%
    {text-decoration:line-through}%
\endgroup%
}

\LetLtxMacro\bcancel\cancel
\LetLtxMacro\xcancel\cancel
```

File 56 **lwarp-canoniclayout.sty**

§ 153 Package canoniclayout

Pkg canoniclayout canoniclayout is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{canoniclayout}[2011/11/05]

\newcommand*{\currentfontletters}{}
\newcommand*{\charactersperpage}{}
```

File 57 **lwarp-caption.sty**

§ 154 Package caption

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg caption caption is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{caption}[2018/10/05]

\renewcommand\caption@ibox[3]{%
  \@testopt{\caption@iibox{#1}{#2}{#3}}{%
%         \wd\@tempboxa%
        \linewidth% lwarp
  }%
% \LWR@traceinfo{caption@ibox: done}%
}

\long\def\caption@iibox#1#2#3[#4]{%
  \@testopt{\caption@iiibox{#1}{#2}{#3}{#4}}\captionbox@hj@default
}

\long\def\caption@iiibox#1#2#3#4[#5]#6{%
```

```
%   \setbox\@tempboxa\hbox{#6}%
  \begingroup
  #1*% set \caption@position
  \caption@iftop{%
    \LWR@traceinfo{caption@iiibox top}%
    \endgroup
    \parbox[t]{#4}{%
      #1\relax
      \caption@setposition t%
%       \vbox{\caption#2{#3}}%
      {\caption#2{#3}}% lwarp
%       \captionbox@hrule
%       \csname caption@hj@#5\endcsname
%       \unhbox\@tempboxa
       #6% lwarp
    }%
  }{%
    \LWR@traceinfo{caption@iiibox bottom}%
    \endgroup
    \parbox[b]{#4}{%
      #1\relax
      \caption@setposition b%
%       \csname caption@hj@#5\endcsname
%       \unhbox\@tempboxa
         #6% lwarp
%       \captionbox@hrule
%       \vtop{\caption#2{#3}}%
      {\caption#2{#3}}% lwarp
     }%
  }%
\LWR@traceinfo{caption@iiibox: done}%
}

\def\caption@caption{%
  \caption@iftype
    {%
     \caption@checkgrouplevel\@empty\caption
     \caption@star
       {\caption@refstepcounter\@captype}%
       {\caption@dblarg{\@caption\@captype}}}%
    {\caption@Error{\noexpand\caption outside float}%
     \caption@gobble}%
}

\long\def\caption@@caption#1[#2]#3{%

  \ifcaption@star \else
    \caption@prepareanchor{#1}{#2}%
    \memcaptioninfo{#1}{\csname the#1\endcsname}{#2}{#3}%
    \@nameuse{nag@hascaptiontrue}%
  \fi

  \par
  \caption@beginex{#1}{#2}{#3}%
    \caption@setfloatcapt{%
```

```
      \caption@boxrestore
      \if@minipage
        \@setminipage
      \fi
      \caption@normalsize
      \ifcaption@star
        \let\caption@makeanchor\@firstofone
      \fi
      \@makecaption{\csname fnum@#1\endcsname}%
                   {\ignorespaces\caption@makeanchor{#3}}\par
      \caption@if@minipage\@minipagetrue\@minipagefalse}%
  \caption@end%
}
```

\caption@@@make {⟨*caption label*⟩}{⟨*caption text*⟩}

```
\renewcommand\caption@@@make[2]{%
\LWR@startpars% lwarp
%   \sbox\@tempboxa{#1}%
%   \ifdim\wd\@tempboxa=\z@
%     \let\caption@lsep\relax
%   \fi
  \caption@ifempty{#2}{%
    \let\caption@lsep\@empty
    \let\caption@tfmt\@firstofone
  }%
  \@setpar{\LWR@closeparagraph\@@par}% lwarp
  \caption@applyfont
  \caption@fmt
    {\ifcaption@star\else
       \begingroup
         \captionlabelfont
         #1%
       \endgroup
     \fi}%
    {\ifcaption@star\else
       \begingroup
         \caption@iflf\captionlabelfont
         \relax\caption@lsep
       \endgroup
     \fi}%
    {{\captiontextfont
      \caption@ifstrut
        {\vrule\@height\ht\strutbox\@width\z@}%
        {}%
      \nobreak\hskip\z@skip % enable hyphenation
      \caption@tfmt{#2}
    \LWR@ensuredoingapar% lwarp
      \caption@ifstrut
        {\ifhmode\@finalstrut\strutbox\fi}%
        {}%
      \par}}
\LWR@stoppars% lwarp
}
```

\caption@@make@ {⟨⟩} {⟨⟩}

```
\renewcommand{\caption@@make@}[2]{%
  \caption@stepthecounter
  \caption@beginhook
      \caption@@@make{#1}{#2}%
  \caption@endhook
}

% \DeclareCaptionBox{none}{#2}
\DeclareCaptionBox{parbox}{%
#2%
}
\DeclareCaptionBox{colorbox}{%
#2%
}
```

File 58 **lwarp-cases.sty**

§ 155 Package **cases**

(*Emulates or patches code by* Donald Arseneau.)

Pkg cases cases is patched for use by lwarp.

⚠ MathJax MathJax does not support cases.

for HTML output:

```
\LWR@ProvidesPackagePass{cases}[2002/05/02]

\BeforeBeginEnvironment{numcases}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-cases- \mathimagename]
}

\AfterEndEnvironment{numcases}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{subnumcases}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-cases- \mathimagename]
}

\AfterEndEnvironment{subnumcases}{
    \end{lateximage}\end{BlockClass}
}
```

File 59 **lwarp-changebar.sty**

§ 156 Package

changebar

Pkg changebar changebar is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{changebar}[2018/03/09]

\newcommand*{\cbstart}{}
\newcommand*{\cbend}{}
\newenvironment*{\changebar}{}{}
\newcommand*{\cbdelete}{}
\newcommand*{\nochnagebars}{}
\newcommand*{\cbcolor}[1]{}
\newlength{\changebarwidth}
\newlength{\deletebarwidth}
\newlength{\changebarsep}
\newcounter{changebargrey}
```

File 60 **lwarp-changepage.sty**

§ 157 Package

changepage

(*Emulates or patches code by* Peter Wilson.)

Pkg changepage changepage is emulated.

for HTML output: Discard all options for lwarp-changepage:

```
\LWR@ProvidesPackageDrop{changepage}[2009/10/20]

\newif\ifoddpage
\DeclareRobustCommand{\checkoddpage}{\oddpagetrue}
\DeclareRobustCommand{\changetext}[5]{}
\DeclareRobustCommand{\changepage}[9]{}

\@ifundefined{adjustwidth}{
\newenvironment{adjustwidth}[2]{}{}
\newenvironment{adjustwidth*}[2]{}{}
}{
\renewenvironment{adjustwidth}[2]{}{}
\renewenvironment{adjustwidth*}[2]{}{}
}

\DeclareDocumentCommand{\strictpagecheck}{}{}
\DeclareDocumentCommand{\easypagecheck}{}{}
```

File 61 **lwarp-changes.sty**

§ 158 Package

changes

(*Emulates or patches code by* Ekkart Kleinod.)

Pkg changes changes is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{changes}[2015/04/27]

\xpatchcmd{\Changes@output}
    {#1}
    {\LWR@textcurrentcolor{#1}}
    {}
    {\LWR@patcherror{changes}{Changes@output}}

\xpatchcmd{\listofchanges}
    {
        \ifthenelse{\equal{\Changes@InID}{\@empty}}
        {\changesauthorname: \changesanonymousname}
        {%
        \changesauthorname: \Changes@InID
        \ifthenelse{\equal{\Changes@InName}{\@empty}}
        {}
        { (\Changes@InName)}
        }
    }
    {
        \LWR@textcurrentcolor{% lwarp
            \ifthenelse{\equal{\Changes@InID}{\@empty}}
            {\changesauthorname: \changesanonymousname}
            {%
            \changesauthorname: \Changes@InID
            \ifthenelse{\equal{\Changes@InName}{\@empty}}
            {}
            { (\Changes@InName)}
            }
        }
    }
    {}
    {\LWR@patcherror{changes}{listofchanges}}

\xpatchcmd{\listofchanges}
    {\parbox{\Changes@Len@summ}}
    {}
    {}
    {\LWR@patcherror{changes}{listofchanges}}

\xpatchcmd{\listofchanges}
    {\parbox{\Changes@Len@summ}}
    {}
```

```
    {}
    {\LWR@patcherror{changes}{listofchanges}}

\xpatchcmd{\listofchanges}
    {\parbox{\Changes@Len@summ}}
    {}
    {}
    {\LWR@patcherror{changes}{listofchanges}}
```

File 62 **lwarp-chappg.sty**

§ 159 Package chappg

(*Emulates or patches code by* Robin Fairbairns.)

Pkg chappg chappg is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{chappg}[2006/05/09]

\renewcommand{\pagenumbering}[2][]{}
\providecommand{\chappgsep}{--}
```

File 63 **lwarp-chapterbib.sty**

§ 160 Package chapterbib

(*Emulates or patches code by* Donald Arseneau.)

Pkg chapterbib chapterbib is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{chapterbib}[2010/09/18]

\xdef\@savedjobname{\BaseJobname}
\let\@currentipfile\@savedjobname
```

File 64 **lwarp-chemfig.sty**

§ 161 Package chemfig

(*Emulates or patches code by* Christian Tellechea.)

Pkg chemfig chemfig is patched for use by lwarp.

If using `\polymerdelim` to add delimiters to a `\chemfig`, wrap both inside a single `lateximage`:

```
\begin{lateximage}[(-chemfig-~\packagediagramname)]
\chemfig{. . . }
\polymerdelim[. . . ]{. . . }
\end{lateximage}
```

The images are not hashed because they depend on external settings which may be changed at any time, and are unlikely to be reused inline anyhow.

for HTML output:

```
\LWR@ProvidesPackagePass{chemfig}

\LetLtxMacro\LWR@chemfig@origchemfig\chemfig

\DeclareDocumentCommand\chemfig{s O{} O{} m}{%
    \begin{lateximage}[(-chemfig-~\packagediagramname)]%
    \IfBooleanTF{#1}{%
        \LWR@chemfig@origchemfig*[#2][#3]{#4}%
    }{%
        \LWR@chemfig@origchemfig[#2][#3]{#4}%
    }
    \end{lateximage}%
}

\LetLtxMacro\LWR@chemfig@origCF@lewis@b\CF@lewis@b

\def\CF@lewis@b#1#2{%
\begin{lateximage}[(-chemfig-~\packagediagramname)]%
\LWR@chemfig@origCF@lewis@b{#1}{#2}%
\end{lateximage}%
}

\preto{\schemestart}{\begin{lateximage}[(-chemfig-~\packagediagramname)]}
\appto{\CF@schemestop}{\end{lateximage}}

\LetLtxMacro\LWR@chemfig@origchemleft\chemleft

\def\chemleft#1#2\chemright#3{%
\begin{lateximage}[(-chemfig-~\packagediagramname)]%
\LWR@chemfig@origchemleft#1#2\chemright#3%
\end{lateximage}%
}

\LetLtxMacro\LWR@chemfig@origchemup\chemup

\def\chemup#1#2\chemdown#3{%
\begin{lateximage}[(-chemfig-~\packagediagramname)]%
\LWR@chemfig@origchemup#1#2\chemdown#3%
\end{lateximage}%
}
```

File 65 **lwarp-chemformula.sty**

§ 162 Package

chemformula

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemformula chemformula is patched for use by lwarp.

The SVG images are hashed according to contents and local options. Global options are assumed to be constant document-wide.

⚠ chemformula with MathJax chemformula works best without MathJax. If MathJax is used, `\displaymathother` must be used before `array`, and then `\displaymathnormal` may be used after. (The chemformula package adapts to `array`, but does not know about MathJax, and MathJax does not know about chemformula.)

While using MathJax, `\displaymathother` may also be used for other forms of display and inline math which contain chemformula expressions.

for HTML output:

```
\LWR@ProvidesPackagePass{chemformula}[2017/03/23]
\ExplSyntaxOn
```

`\ch` Enclose in an inline SVG image or MathJax. The `alt` tag is is the contents of the `\ch` expression. The filename is hashed, and also has additional hashing information based on the local options.

```
\RenewDocumentCommand \ch { O{}m }
 {%
```

To work inside `align` with `\displaymathother`, a simple version must be used to work with chemformula's adaptation to `align`.

```
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%  lwarp
    {
        \chemformula_ch:nn {#1} {#2}%   original
    }
```

If used as the outer level, must temporarily ensure MathJax is disabled:

```
    {
        \begingroup%
        \boolfalse{mathjax}%
```

An inline image is used, adjusted for the baseline:

```
        \LWR@subsingledollar*{% lwarp
            \textbackslash{}ch\{\LWR@HTMLsanitize{#2}\}% alt text
        }{%
         \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}% add'l hashing
        }%
        {%
```

```
            \chemformula_ch:nn {#1} {#2}%   original
        }%
        \endgroup%
    }
  }
```

\chcpd Similar to \ch.

```
\cs_gset_protected:Npn \chemformula_chcpd:nn #1#2
  {
    \begingroup%
    \boolfalse{mathjax}%
    \LWR@subsingledollar*{% lwarp
        \textbackslash{}chcpd\{\LWR@HTMLsanitize{#2}\}%
    }{%
        \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
    }{% original
    \group_begin:
      \tl_if_blank:nF {#2}
        {
          \keys_set:nn {chemformula} {#1}
          \__chemformula_save_catcodes:
          \__chemformula_sanitize:Nn
            \l__chemformula_chemformula_tmpa_tl
            {#2}
          \__chemformula_input_compound_no_check:NV
            \l__chemformula_compound_tl
            \l__chemformula_chemformula_tmpa_tl
          \__chemformula_prepare_output:N \l__chemformula_compound_tl
          \chemformula_write:V \l__chemformula_compound_tl
        }
    \group_end:
    }
    \endgroup
  }
```

\charrow If standalone, appears in a regular lateximage.

```
\RenewDocumentCommand \charrow { mO{}O{} }
{
    \begin{lateximage}[(-chemformula- charrow)]
    \group_begin:
      \__chemformula_draw_arrow:nnn {#1} {#2} {#3}
    \group_end:
    \end{lateximage}
}
```

\chname If standalone, appears in a regular lateximage, hashed according to contents.

```
\RenewDocumentCommand \chname { R(){}R(){} }
  {
    \begin{lateximage}*[%
        \textbackslash{}chname(\LWR@HTMLsanitize{#1})(\LWR@HTMLsanitize{#2})
    ]%
        \chemformula_chwritebelow:nn {#1} {#2}
```

```
    \end{lateximage}
  }
```

\chlewis Placed inline, hashed according to contents and options.

```
\RenewDocumentCommand \chlewis { O{}mm }
  {
    \begingroup%
    \boolfalse{mathjax}%
    \LWR@subsingledollar*{\textbackslash{}chlewis\{#2\}\{#3\}}%
    {
        \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
    }{
        \chemformula_lewis:nnn {#1} {#2} {#3}
    }
    \endgroup%
  }
```

lwarp redefines the $ character, so special handling is required to escape math expressions inside \ch.

This boolean tracks a new kind of escaped math:

```
\bool_new:N      \l__chemformula_first_last_LWRdollar_bool
```

\chemformula_input_escape_math

Adds additional escaping for the new dollar definition:

```
\cs_gset_protected:Npn \__chemformula_input_escape_math:n #1
  {
    \__chemformula_first_last_math:n {#1}
    \bool_if:NT \l__chemformula_first_last_dollar_bool
      {
        \bool_set_true:N \l__chemformula_first_last_math_bool
        \__chemformula_read_escape_dollar:w #1 \q_nil
      }
    \bool_if:NT \l__chemformula_first_last_mathbraces_bool
      {
        \bool_set_true:N \l__chemformula_first_last_math_bool
        \__chemformula_read_escape_mathbraces:w #1 \q_nil
      }
```

Added by lwarp:

```
    \bool_if:NT \l__chemformula_first_last_LWRdollar_bool%      lwarp
      {
        \bool_set_true:N \l__chemformula_first_last_math_bool%  lwarp
        \__chemformula_read_escape_LWRdollar:w #1 \q_nil%       lwarp
      }
  }
```

\chemformula_read_escape_LWRdollar

The following parses the contents inside the new dollars.

lwarp keeps the dollar as its original math shift until the document starts. While chemmacros is being patched, the dollar must temporarily be set to its new meaning during the following definition.

```
\begingroup
\catcode`\$=\active

\cs_new_protected:Npn \__chemformula_read_escape_LWRdollar:w $#1$ \q_nil
{
    \__chemformula_read_escape_math:n {#1}
}

\endgroup
```

\chemformula_bool_set_if_first_last

The following looks at the first and last tokens for delimiters to escape math inside \ch. The original definition is modified to look for the control sequences which are used by the new meaning of $.

```
\cs_new_protected:Npn \__chemformula_bool_cs_set_if_first_last:NnNN #1#2#3#4
  {
    \int_zero:N \l__chemformula_tmpa_int
    \int_zero:N \l__chemformula_tmpb_int
    \int_set:Nn \l__chemformula_tmpa_int { \tl_count:n {#2} }
    \tl_map_inline:nn {#2}
      {
        \int_incr:N \l__chemformula_tmpb_int
        \int_compare:nT { \l__chemformula_tmpb_int = 1 }
          {
```

At the start, the cs_ version compares control sequences:

```
            \ifdefstrequal{##1}{#3}% lwarp
                {
                    \bool_set_true:N #1
                }% lwarp
                {}
          }
```

At the end, compare more control sequences:

```
        \int_compare:nT { \l__chemformula_tmpb_int = \l__chemformula_tmpa_int }
          {
            \ifdefstrequal{##1}{#4}
                {}
                {
                    \bool_set_false:N #1
                }
          }
      }
  }
```

\chemformula_first_last_math

Modified to check for the new meaning of $ at first/last:

```
\cs_gset_protected:Npn \__chemformula_first_last_math:n #1
 {
   \bool_set_false:N \l__chemformula_first_last_math_bool
   \bool_set_false:N \l__chemformula_first_last_dollar_bool
   \bool_set_false:N \l__chemformula_first_last_LWRdollar_bool%    lwarp
   \bool_set_false:N \l__chemformula_first_last_mathbraces_bool
   \__chemformula_bool_set_if_first_last:Nnnn
     \l__chemformula_first_last_dollar_bool
     {#1}
     { $ } { $ }
   \bool_if:NF \l__chemformula_first_last_dollar_bool
     {
       \__chemformula_bool_set_if_first_last:Nnnn
         \l__chemformula_first_last_mathbraces_bool
         {#1}
         { \( } { \) }
```

Added by lwarp:

```
         \bool_if:NF \l__chemformula_first_last_mathbraces_bool%   lwarp
           {
               \__chemformula_bool_cs_set_if_first_last:NnNN
               \l__chemformula_first_last_LWRdollar_bool
               {#1}
               { \LWR@newsingledollar } { \LWR@newsingledollar }
           }%  lwarp
     }
 }

\ExplSyntaxOff
```

File 66 **lwarp-chemgreek.sty**

§ 163 Package

chemgreek

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemgreek

chemgreek is patched for use by lwarp.

Greek symbols

⚠ package selection

To use text-mode symbols, use packages textalpha or textgreek. Using the other packages supported by chemgreek will result in math-mode greek characters, which will result in svg images being used. These images will be hashed.

⚠ XeLaTeX, LuaLaTeX

If using XeLaTeX or LuaLaTeX, select the fontspec mapping:

```
\selectchemgreekmapping{fontspec}
```

for HTML output:

```
\LWR@ProvidesPackagePass{chemgreek}[2016/02/10]

\ExplSyntaxOn
```

```
3
4 \cs_gset_protected:Npn \chemgreek_text:n #1
5   { { \text {#1} } }
6
7 \appto\LWR@restoreorigformatting{%
8 \cs_set_protected:Npn \chemgreek_text:n #1%
9   { \ensuremath { \text {#1} } }%
10 }
11
12 \ExplSyntaxOff
```

File 67 **lwarp-chemmacros.sty**

§ 164 Package

chemmacros

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemmacros chemmacros is patched for use by lwarp.

for HTML output:

```
1 \LWR@ProvidesPackagePass{chemmacros}[2017/08/28]
```

SVG file hashing assumes that the relevent options are constant for the entire document.

§ 164.1 Changes to the user's document

⚠ \makepolymerdelims When using \makepolymerdelims, enclose the entire expression inside a polymerdelims environment, such as (from the chemmacros manual):

```
\begin{polymerdelims}
\chemfig{-[@{op,.75}]CH_2-CH(-[6]Cl)-[@{cl,0.25}]}
\makepolymerdelims{5pt}[27pt]{op}{cl}
\end{polymerdelims}
```

⚠ redox reactions Redox reactions must be enclosed inside a redoxreaction environment. For print output, extra space must be included above and/or below the result, so they are declared as arguments to the environment, instead of being manually entered as per the chemmacros manual. For HTML output, the extra space is ignored and a latexmage is used instead.

```
\begin{redoxreaction}{7mm}{7mm}
\OX{a,Na} $\rightarrow$ \OX{b,Na}\pch\redox(a,b){oxidation}
\end{redoxreaction}
```

§ 164.2 Code

§ 164.3 Loading modules

Patching chemmacros modules must be done `\AtBeginDocument`, since modules are invoked by the user in the preamble, and each patch is only done if the module is loaded.

```
\ExplSyntaxOn

\newcommand{\@ifchemmacrosmoduleloaded}[1]{%
\@ifl@aded{\c__chemmacros_module_extension_tl}{\c__chemmacros_module_prefix_tl.#1}%
}

\ExplSyntaxOff
```

§ 164.4 New environments

`\makepolymerdelims` and redox reactions must be enclosed in a `lateximage` during HTML output. These environments are provided here in HTML mode, and in the lwarp core in print mode, as a high-level semantic syntax which automatically embeds the contents in a `lateximage` with an appropriate `alt` tag.

Env `polymerdelims`

```
\DeclareDocumentEnvironment{polymerdelims}{}
{\begin{lateximage}[(-chemmacros- polymer)]}
{\end{lateximage}}
```

Env `redoxreaction` {⟨*space above*⟩} {⟨*space below*⟩}

For HTML output, the above and below space is ignored, and a `lateximage` is used instead. For the print output version, see section 85.

```
\DeclareDocumentEnvironment{redoxreaction}{m m}
{\begin{lateximage}[(-chemmacros- redoxreaction)]}
{\end{lateximage}}
```

```
\ExplSyntaxOn
```

§ 164.5 Acid-base

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{acid-base}{
\PackageInfo{lwarp}{Patching~chemmacros~module~acid-base}

\cs_gset_protected:Npn \chemmacros_p:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{
        \textbackslash{}p\{\LWR@HTMLsanitize{#1}\}
    }{
        chemmacrosp\protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
```

```
    }{
    \group_begin:
      \mbox
        {
          \chemmacros_p_style:n {p}
          \ensuremath {#1}
        }
    \group_end:
    }
    \endgroup
  }

\RenewDocumentCommand \pH  {} {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pH}{chemmacros}{
        \chemmacros_p:n { \chemmacros_chemformula:n {H} }
    }
    \endgroup
}

\RenewDocumentCommand \pOH {} {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pOH}{chemmacros}{
        \chemmacros_p:n { \chemmacros_chemformula:n {OH} }
    }
    \endgroup
}

\RenewDocumentCommand \pKa {O{}}
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pKa{[}#1{]}}{chemmacros #1}{
        \chemmacros_p:n
        {
            \Ka \ifblank {#1} {}
            { {} \c_math_subscript_token { \chemmacros_bold:n {#1} } }
        }
    }
    \endgroup
  }

\RenewDocumentCommand \pKb {O{}}
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pKb{[}#1{]}}{chemmacros #1}{
        \chemmacros_p:n
        {
            \Kb \ifblank {#1} {}
            { {} \c_math_subscript_token { \chemmacros_bold:n {#1} } }
        }
    }
```

```
    \endgroup
  }

\LetLtxMacro\LWR@chemmacros@origKa\Ka
\renewcommand*{\Ka}{%
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}Ka}{chemmacros}{%
        \LWR@chemmacros@origKa%
    }%
    \endgroup
}

\LetLtxMacro\LWR@chemmacros@origKb\Kb
\renewcommand*{\Kb}{%
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}Kb}{chemmacros}{%
        \LWR@chemmacros@origKb%
    }%
    \endgroup
}

\LetLtxMacro\LWR@chemmacros@origKw\Kw
\renewcommand*{\Kw}{%
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}Kw}{chemmacros}{
        \LWR@chemmacros@origKw
    }
    \endgroup
}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.6 Charges

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{charges}{
\PackageInfo{lwarp}{Patching~chemmacros~module~charges}

\cs_gset_protected:Npn \fplus  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}fplus}{chemmacros}
    { \LWR@origensuredmath{\chemformula_fplus:}  }
    \endgroup
}
\cs_gset_protected:Npn \fminus {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}fminus}{chemmacros}
    { \LWR@origensuredmath{\chemformula_fminus:} }
    \endgroup
```

```
}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.7 Nomenclature

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{nomenclature}{
\PackageInfo{lwarp}{Patching~chemmacros~module~nomenclature}

\cs_gset_protected:Npn \chemmacros_charge:n #1
  {
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}
    {\chemmacros_chemformula:n { {}^{#1} }}
    {
        \ifmmode
            {\chemmacros_chemformula:n { {}^{#1} }}
        \else
            { \textsuperscript{\ensuremath{#1}} }
        \fi
    }
  }


\LetLtxMacro\LWR@chemmacros@origchemprime\chemprime

\protected\def\chemprime { \HTMLunicode{2032} }

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\chemprime\LWR@chemmacros@origchemprime%
}

\ChemCompatibilityFrom{5.8}
\cs_gset_protected:Npn \__chemmacros_cip:n #1
  {
    \tl_set:Nn \l__chemmacros_tmpa_tl {#1}
    \int_step_inline:nnnn {0} {1} {9}
      {
        \tl_replace_all:Nnn \l__chemmacros_tmpa_tl
          {##1}
          { { \l__chemmacros_cip_number_tl ##1} }
      }
    {
        \l__chemmacros_cip_inner_tl
        \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
            \l__chemmacros_tmpa_tl
        }}% lwarp
    }
  }
\EndChemCompatibility

\RenewDocumentCommand \Sconf { O{S} } {
\begin{lateximage}[\textbackslash{}Sconf{[}#1{]}]
    \chemmacros_sconf:n {#1}
\end{lateximage}
```

```
}

\RenewDocumentCommand \Rconf { O{R} } {
\begin{lateximage}[\textbackslash{}Rconf{[}#1{]}]
    \chemmacros_rconf:n {#1}
\end{lateximage}
}

\cs_gset_protected:Npn \chemmacros_hapto:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}hapto\{#1\}}{chemmacros}{
        \chemmacros_coordination_symbol:nnnn
        { \l__chemmacros_coord_use_hyphen_bool }
        {
            \chemmacros_if_compatibility:nnTF {>} {5.7}
            { \c_true_bool }
            { \c_false_bool }
        }
        { \chemeta }
        {#1}
    }
    \endgroup
  }

\cs_gset_protected:Npn \chemmacros_dento:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}dento\{#1\}}{chemmacros}{
        \chemmacros_coordination_symbol:nnnn
        { \l__chemmacros_coord_use_hyphen_bool }
        {
            \chemmacros_if_compatibility:nnTF {>} {5.7}
            { \c_true_bool }
            { \c_false_bool }
        }
        { \chemkappa }
        {#1}
    }
    \endgroup
  }

\cs_gset_protected:Npn \chemmacros_bridge:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}bridge\{#1\}}{chemmacros}{
        \chemmacros_coordination_symbol:nnnn
        { \l__chemmacros_coord_use_hyphen_bool }
        { \l__chemmacros_bridge_super_bool }
        { \chemmu }
        {#1}
    }
    \endgroup
```

```
  }
}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.8 Particles

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{particles}{
\PackageInfo{lwarp}{Patching~chemmacros~module~particles}

\cs_gset_protected:Npn \chemmacros_declare_nucleophile:Nn #1#2
  {
    \cs_set_protected:cpn {__chemmacros_ \chemmacros_remove_backslash:N #1:}
      {
        \bool_if:NTF \l__chemmacros_nucleophile_elpair_bool
          {
            \chemmacros_elpair:n { #2 }
            \chemmacros_if_compatibility:nnT {>=} {5.3}
              { \skip_horizontal:N \l__chemmacros_nucleophile_dim }
            \chemmacros_chemformula:n { {}^{-} }
          }
          { \chemmacros_chemformula:n { #2^{-} } }
      }
    \DeclareDocumentCommand #1 {o}
      {%
        \begin{lateximage}%
        \group_begin:%
          \IfNoValueF {##1}%
            { \chemmacros_set_keys:nn {particles} {##1} }%
          \use:c {__chemmacros_ \chemmacros_remove_backslash:N #1:}%
        \group_end:%
        \end{lateximage}%
      }
  }

\RenewChemNucleophile \Nuc {Nu}
\RenewChemNucleophile \ba  {ba}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.9 Phases

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{phases}{
\PackageInfo{lwarp}{Patching~chemmacros~module~phases}

\cs_undefine:N \chemmacros_phase:n
\cs_new_protected:Npn \chemmacros_phase:n #1
  {
    \chemmacros_leave_vmode:
    \bool_if:NTF \l__chemmacros_phases_sub_bool
      {
        \ifnumequal{\value{LWR@lateximagedepth}}{0}
        {
```

```
            \textsubscript{ (#1) }
        }
        {
            \chemformula_subscript:n { (#1) }
        }
      }
      {
        \skip_horizontal:N \l__chemmacros_phases_space_dim
        \chemmacros_text:n { (#1) }
      }
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.10 Mechanisms

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{mechanisms}{
\PackageInfo{lwarp}{Patching~chemmacros~module~mechanisms}

\chemmacros_define_keys:nn {textmechanisms}
  {
    type      .choice: ,
    type /    .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { S }
          {
              \textsubscript{N}
          }
          { }
      } ,
    type / 1  .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { S }
          {
              \textsubscript{N}
            1
          }
          { }
      } ,
    type / 2  .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { S }
          {
              \textsubscript{N}
            2
          }
          { }
      } ,
    type / se .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { S }
          {
              \textsubscript{E}
```

```
          }
          { }
      } ,
    type / 1e .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { S }
          {
              \textsubscript{E}
            1
          }
          { }
      } ,
    type / 2e .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { S }
          {
              \textsubscript{E}
            2
          }
          { }
      } ,
    type / ar .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { S }
          {
              \textsubscript{E}
          }
          { Ar - }
      } ,
    type / e  .code:n    =
      { \__chemmacros_set_mechanisms:nnn { E } { } { } } ,
    type / e1 .code:n    =
      { \__chemmacros_set_mechanisms:nnn { E } { 1 } { } } ,
    type / e2 .code:n    =
      { \__chemmacros_set_mechanisms:nnn { E } { 2 } { } } ,
    type / cb .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { E }
          {
            1
              \textsubscript{cb}
          }
          { }
      } ,
    type      .default:n =
  }

\cs_gset_protected:Npn \chemmacros_mechanisms:n #1
  {
    \tl_if_blank:nTF {#1}
      { \chemmacros_set_keys:nn {textmechanisms} { type } }
      { \chemmacros_set_keys:nn {textmechanisms} { type = #1 } }
    \mbox
      {
        \tl_use:N \l__chemmacros_mechanisms_ar_tl
```

```
        \tl_use:N \l__chemmacros_mechanisms_type_tl
        \tl_use:N \l__chemmacros_mechanisms_mol_tl
      }
  }

\appto\LWR@restoreorigformatting{%
\cs_set_protected:Npn \chemmacros_mechanisms:n #1%
  {%
    \tl_if_blank:nTF {#1}%
      { \chemmacros_set_keys:nn {mechanisms} { type } }%
      { \chemmacros_set_keys:nn {mechanisms} { type = #1 } }%
    \mbox%
      {%
        \tl_use:N \l__chemmacros_mechanisms_ar_tl%
        \tl_use:N \l__chemmacros_mechanisms_type_tl%
        \tl_use:N \l__chemmacros_mechanisms_mol_tl%
      }%
  }%
}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.11 Newman

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{newman}{
\PackageInfo{lwarp}{Patching~chemmacros~module~newman}

\RenewDocumentCommand \newman {od()m}%
  {
    \IfValueTF{#2}
    {\begin{lateximage}[\textbackslash{}newman(#2)\{#3\}]}
    {\begin{lateximage}[\textbackslash{}newman\{#3\}]}
    \group_begin:
      \IfNoValueF  {#1} { \chemmacros_set_keys:nn {newman} {#1} }
      \IfNoValueTF {#2}
        { \chemmacros_newman:nn {  } {#3} }
        { \chemmacros_newman:nn {#2} {#3} }
    \group_end:
    \end{lateximage}
  }%

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.12 Orbital

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{orbital}{
\PackageInfo{lwarp}{Patching~chemmacros~module~orbital}

\RenewDocumentCommand \orbital {om}
  {
    \IfValueTF{#1}
```

```
    {
        \begin{lateximage}[%
            \textbackslash{}orbital{[}\LWR@HTMLsanitize{#1}{]}\{#2\}%
        ][][margin-left: 1em ; margin-right: 1em]
    }
    {
        \begin{lateximage}[%
            \textbackslash{}orbital\{#2\}%
        ][][margin-left: 1em ; margin-right: 1em]
    }
    \group_begin:
      \chemmacros_set_keys:nn {orbital/type} {#2}
      \IfNoValueTF {#1}
        { \chemmacros_orbital:n {  } }
        { \chemmacros_orbital:n {#1} }
    \group_end:
    \end{lateximage}
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.13 Reactions

`\chemmacros_declare_reaction_env` {⟨*chem*⟩} {⟨*math*⟩} {⟨*args number*⟩} {⟨*argument list (#2}{#3}...)*⟩}

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{reactions}{
\PackageInfo{lwarp}{Patching~chemmacros~module~reactions}

\cs_gset_protected:Npn \chemmacros_declare_reaction_env:nnnn #1#2#3#4
  {
   \exp_args:Nnx \DeclareDocumentEnvironment {#1} { O{} \prg_replicate:nn {#3+0} {m} }
      {
        \boolfalse{mathjax}%    lwarp
        \chemmacros_add_reaction_description:n {##1}
        \__chemmacros_begin_reaction:
        \chemmacros_reaction_read:nnw {#2} {#4}
      }
      {
        \__chemmacros_end_reaction:
      }
  }
\cs_generate_variant:Nn \chemmacros_declare_reaction_env:nnnn {nnnV}

\RenewChemReaction {reaction}   {equation}
\RenewChemReaction {reaction*}  {equation*}
\RenewChemReaction {reactions}  {align}
\RenewChemReaction {reactions*} {align*}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.14 Redox

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{redox}{
\PackageInfo{lwarp}{Patching~chemmacros~module~redox}

\NewDocumentCommand \LWR@chemmacros@ox { s m >{\SplitArgument{1}{,}}m }
  {
    \IfBooleanTF {#1}
      { \chemmacros_ox:nnnn {#1} {#2} #3 }
      { \chemmacros_ox:nnnn {  } {#2} #3 }
  }

\RenewDocumentCommand \ox { s O{} m }
  {
    \begingroup
    \boolfalse{mathjax}
    \IfBooleanTF {#1}
      {
        \LWR@subsingledollar*{% yes hash
            \textbackslash{}ox*\{\LWR@HTMLsanitize{#3}\}% alt
        }{%
            star \protect\LWR@HTMLsanitize{\detokenize\expandafter{#2}}%
        }{%
            \LWR@chemmacros@ox* {#2} {#3}% contents
        }%
      }
      {
        \LWR@subsingledollar*{% yes hash
            \textbackslash{}ox*\{\LWR@HTMLsanitize{#3}\}% alt
        }{%
            \protect\LWR@HTMLsanitize{\detokenize\expandafter{#2}}%
        }{%
            \LWR@chemmacros@ox {#2} {#3}% contents
        }%
      }
    \endgroup
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.15 Scheme

Fix for chemmacros as of v5.8b, when using newfloat and babel:

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{scheme}{
\PackageInfo{lwarp}{Patching~chemmacros~module~scheme}

\ifdefstring{\schemename}{los}{
\SetupFloatingEnvironment{scheme}{
name = \chemmacros_translate:n {scheme-name}
}
}{}
```

```
}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.16 Spectroscopy

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{spectroscopy}{
\PackageInfo{lwarp}{Patching~chemmacros~module~spectroscopy}

\ChemCompatibilityTo{5.8}
\cs_gset_protected:Npn \__chemmacros_nmr_base:nn #1#2
  {
    \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
      {
        \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl { \{ }
        \tl_put_right:Nn \g__chemmacros_nmr_element_coupled_tl { \} }
      }
    \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl {#2}
%     \chemmacros_chemformula:n { ^{#1} }
    \textsuperscript{#1}
    \bool_if:NTF \l__chemmacros_nmr_parse_bool
      { \chemformula_ch:nV {} \g__chemmacros_nmr_element_coupled_tl }
      { \chemmacros_chemformula:V \g__chemmacros_nmr_element_coupled_tl }
    \tl_use:N \l__chemmacros_nmr_element_method_connector_tl
    \tl_use:N \l__chemmacros_nmr_method_tl
  }
\EndChemCompatibility
\ChemCompatibilityFrom{5.8}
\cs_gset_protected:Npn \__chemmacros_nmr_base:nn #1#2
  {
    \group_begin:
      \tl_use:N \l__chemmacros_nmr_base_format_tl
      \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
        {
          \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl { \{ }
          \tl_put_right:Nn \g__chemmacros_nmr_element_coupled_tl { \} }
        }
      \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl {#2}
%       \chemmacros_chemformula:n { ^{#1} }
      \textsuperscript{#1}
      \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
        {
          \bool_if:NTF \l__chemmacros_nmr_parse_bool
            { \chemformula_ch:nV {} \g__chemmacros_nmr_element_coupled_tl }
            { \chemmacros_chemformula:V \g__chemmacros_nmr_element_coupled_tl }
        }
      \tl_use:N \l__chemmacros_nmr_element_method_connector_tl
      \tl_use:N \l__chemmacros_nmr_method_tl
    \group_end:
  }
\EndChemCompatibility


\cs_gset_protected:Npn \chemmacros_nmr_position:n #1
```

```
  {
    \chemmacros_chemformula:x
      {
        \exp_not:V \g__chemmacros_nmr_element_tl
        \bool_if:NF \l__chemmacros_nmr_position_side_bool
          {
            \tl_if_eq:NnTF \l__chemmacros_nmr_position_tl {^}% lwarp
            { \textsuperscript{\exp_not:n { {#1} }} }% lwarp
            { \textsubscript{\exp_not:n { {#1} }} }% lwarp
%             \exp_not:V \l__chemmacros_nmr_position_tl
%             \exp_not:n { {#1} }
          }
      }
    \bool_if:NT \l__chemmacros_nmr_position_side_bool
      {
        \tl_use:N \l__chemmacros_nmr_position_tl
        \__chemmacros_nmr_position:n {#1}
      }
  }

\cs_gset_protected:Npn \__chemmacros_nmr_coupling:w (#1;#2)
  {
    \tl_set:Nn \l__chemmacros_nmr_coupling_bonds_tl
      {
        \l__chemmacros_nmr_coupling_bonds_pre_tl
        #1
        \l__chemmacros_nmr_coupling_bonds_post_tl
      }
    \bool_if:NTF \l__chemmacros_nmr_coupling_nuclei_sub_bool
      {
        \tl_set:Nn \l__chemmacros_nmr_coupling_nuclei_tl
          {
%             \c_math_subscript_token
            \textsubscript% lwarp
              {
                \l__chemmacros_nmr_coupling_nuclei_pre_tl
                \chemmacros_chemformula:n {#2}
                \l__chemmacros_nmr_coupling_nuclei_post_tl
              }
          }
      }
      {
        \tl_set:Nn \l__chemmacros_nmr_coupling_nuclei_tl
          {
            \l__chemmacros_nmr_coupling_nuclei_pre_tl
            \chemmacros_chemformula:n {#2}
            \l__chemmacros_nmr_coupling_nuclei_post_tl
          }
      }
    \__chemmacros_nmr_coupling_aux_i:w
  }

\AfterEndPreamble{% After \AtBeginDocument
% \NMR{<num>,<elem>}(<num>,<unit>)[<solvent>] ALL arguments are optional
% \NMR* same but without ": $\delta$" at end
```

```
\cs_gset_protected:Npn \chemmacros_nmr:nnnn #1#2#3#4
    {
    \bool_if:NT \l__chemmacros_nmr_list_bool { \item \scan_stop: }
    \group_begin:
        \chemmacros_leave_vmode:
        \bool_set_false:N \l__chemmacros_nmr_frequency_bool
        \bool_set_false:N \l__chemmacros_nmr_solvent_bool
        \tl_if_empty:nF {#3}
        { \bool_set_true:N \l__chemmacros_nmr_frequency_bool }
        \tl_if_empty:nF {#4}
        { \bool_set_true:N \l__chemmacros_nmr_solvent_bool }
        \bool_if:nT
        {
            \l__chemmacros_nmr_frequency_bool
            ||
            \l__chemmacros_nmr_solvent_bool
        }
        { \bool_set_true:N \l__chemmacros_nmr_delimiters_bool }
        \bool_if:nT
        {
            \l__chemmacros_nmr_frequency_bool
            &&
            \l__chemmacros_nmr_solvent_bool
        }
        { \bool_set_true:N \l__chemmacros_nmr_comma_bool }
        \tl_if_empty:nTF {#2}
        {
            \__chemmacros_nmr_nucleus:VV
            \l__chemmacros_nmr_isotope_default_tl
            \l__chemmacros_nmr_element_default_tl
        }
        { \__chemmacros_nmr_nucleus:w #2 \q_stop }
        \mode_if_math:TF
        {
            \text
            {
                \group_begin:
                \tl_use:N \l__chemmacros_nmr_format_tl
\LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
                \__chemmacros_nmr_base:VV
                    \g__chemmacros_nmr_isotope_tl
                    \g__chemmacros_nmr_element_tl
                \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                    { ~ ( }
                \bool_if:NT \l__chemmacros_nmr_frequency_bool
                    { \__chemmacros_nmr_frequency:n {#3} }
                \bool_if:NT \l__chemmacros_nmr_comma_bool
                    { , ~ }
                \bool_if:NT \l__chemmacros_nmr_solvent_bool
                    { \chemmacros_chemformula:n {#4} }
                \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                    { ) }
                \tl_if_blank:nT {#1} {:~}
}}% lwarp
                \group_end:
```

```
            }
            \tl_if_blank:nT {#1}
            {
                \delta
                \text { \l__chemmacros_nmr_delta_tl }
                \bool_if:NT \l__chemmacros_nmr_use_equal_bool {=}
            }
        }
        {
            \group_begin:
            \tl_use:N \l__chemmacros_nmr_format_tl
\LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
            \__chemmacros_nmr_base:VV
                \g__chemmacros_nmr_isotope_tl
                \g__chemmacros_nmr_element_tl
            \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                {~(}
            \bool_if:NT \l__chemmacros_nmr_frequency_bool
                { \__chemmacros_nmr_frequency:n {#3} }
            \bool_if:NT \l__chemmacros_nmr_comma_bool
                {,~}
            \bool_if:NT \l__chemmacros_nmr_solvent_bool
                {
                \bool_if:NTF \l__chemmacros_nmr_parse_bool

% lwarp
                    { \chemformula_ch:nn { } {#4} }%  original
                    {\ch{#4}}%  lwarp
                    {#4}
                }
            \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                {)}
}}% lwarp
            \tl_if_blank:nT {#1} {:}
            \group_end:
            \tl_if_blank:nT {#1}
            {
                \tl_use:N \c_space_tl
                \c_math_toggle_token
                \delta
                \c_math_toggle_token
                \l__chemmacros_nmr_delta_tl
                \bool_if:NT \l__chemmacros_nmr_use_equal_bool {~=}
            }
        }
    \group_end:
    }
}% AfterEndPremble


\RenewDocumentCommand \chemmacros_data:w { smo }
  {
    \bool_if:NT \l__chemmacros_nmr_list_bool { \item }
      {
% lwarp
        \tl_use:N \l__chemmacros_nmr_format_tl #2
        \tl_use:N \l__chemmacros_nmr_format_tl
```

```
        \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
            #2
            \IfNoValueF {#3} { ~ ( #3 ) }
         \IfBooleanT {#1} { \bool_if:NT \l__chemmacros_nmr_use_equal_bool { : } }
        }}% lwarp
      }
    \IfBooleanF {#1} { \bool_if:NT \l__chemmacros_nmr_use_equal_bool { ~ = } }
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.17 Thermodynamics

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{thermodynamics}{
\PackageInfo{lwarp}{Patching~chemmacros~module~thermodynamics}

\cs_gset_protected:Npn \chemmacros_state:nn #1#2
  {
    \group_begin:
      \boolfalse{mathjax}
      \chemmacros_set_keys:nn {thermodynamics} {#1}
        \LWR@subsingledollar*{% yes hashing
            \textbackslash{}state\{\LWR@HTMLsanitize{#2}\}% alt
        }{%
            chemmacros_state% add'l hashing
            #1% options
            LSP \tl_use:N \l__chemmacros_state_sp_left_tl% super/subscripts
            LSB \tl_use:N \l__chemmacros_state_sb_left_tl
            RSP \tl_use:N \l__chemmacros_state_sp_right_tl
            RSB \tl_use:N \l__chemmacros_state_sb_right_tl
        }
        {
         \LWR@origensuredmath{
          \chemmacros_text:V \l__chemmacros_state_pre_tl
          \c_math_superscript_token
            { \chemmacros_text:V \l__chemmacros_state_sp_left_tl }
```

Only add the subscripts if they are being used. This avoids causing an incorrect depth, as the empty subscript will be measured by TEX but cropped out by *pdfcrop*.

```
          \tl_if_empty:NTF \l__chemmacros_state_sb_left_tl
          {}
          {
            \c_math_subscript_token
            { \chemmacros_text:V \l__chemmacros_state_sb_left_tl }
          }
          #2
          \c_math_superscript_token
            { \chemmacros_text:V \l__chemmacros_state_sp_right_tl }
          \tl_if_empty:NTF \l__chemmacros_state_sb_right_tl
          {}
          {
            \c_math_subscript_token
```

```
            { \chemmacros_text:V \l__chemmacros_state_sb_right_tl }
          }
          \chemmacros_text:V \l__chemmacros_state_post_tl
         }
        }
    \group_end:
  }
\cs_generate_variant:Nn \chemmacros_state:nn { nV }

\cs_gset_protected:Npn \chemmacros_declare_state:Nn #1#2
  {
    \chemmacros_define_keys:xn
      {thermodynamics/\chemmacros_remove_backslash:N #1}
      {
        pre               .meta:nn = {chemmacros/thermodynamics} { pre = ##1 } ,
        post              .meta:nn = {chemmacros/thermodynamics} { post = ##1 } ,
      superscript-left  .meta:nn = {chemmacros/thermodynamics} { superscript-left = ##1 } ,
      superscript-right .meta:nn = {chemmacros/thermodynamics} { superscript-right = ##1 } ,
        superscript       .meta:n  = { superscript-right = ##1 } ,
      subscript-left   .meta:nn = {chemmacros/thermodynamics} { subscript-left = ##1 } ,
      subscript-right  .meta:nn = {chemmacros/thermodynamics} { subscript-right = ##1 } ,
        subscript         .meta:n     = { subscript-left = ##1 } ,
        subscript-pos     .choices:nn =
          { left , right }
          { \tl_set_eq:NN \l__chemmacros_state_sb_pos_tl \l_keys_choice_tl } ,
        symbol            .tl_set:N = \l__chemmacros_state_symbol_tl ,
        unit              .tl_set:N = \l__chemmacros_state_unit_tl
      }
    \DeclareDocumentCommand #1 { sO{}D(){}m }
      {
        \group_begin:
          \chemmacros_set_keys:xn
            {thermodynamics/\chemmacros_remove_backslash:N #1}
            {#2}
          \tl_if_blank:nF {##3}
            {
              \chemmacros_set_keys:nx {thermodynamics}
                { subscript-\l__chemmacros_state_sb_pos_tl = \exp_not:n {##3} }
            }
              \chemmacros_state:nV {##2} \l__chemmacros_state_symbol_tl
             \chemmacros_set_keys_groups:nnn {thermodynamics} {variables} {##2}
            \IfBooleanF {##1} {  = ~ \SI {##4} { \l__chemmacros_state_unit_tl } }
        \group_end:
      }
  }
```

The pre-existing macros are redefined with the new definition:

```
\RenewChemState \enthalpy { symbol = H , unit = \kilo\joule\per\mole }
\RenewChemState \entropy  { symbol = S , unit = \joule\per\kelvin\per\mole , pre = }
\RenewChemState \gibbs    { symbol = G , unit = \kilo\joule\per\mole }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument

\ExplSyntaxOff
```

File 68 **lwarp-chemnum.sty**

§ 165 Package

chemnum

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemnum chemnum is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{chemnum}[2016/04/14]

\ExplSyntaxOn

\cs_gset_protected:Npn \chemnum_compound_write:n #1
  {
    \chemnum_get_compound_property:nn {#1} {pre-main-label-code}
    \group_begin:
      \bool_if:NTF \l__chemnum_compound_local_bool
        { \l__chemnum_local_label_format_tl }
        { \chemnum_get_compound_property:nn {#1} {label-format} }
      {
        \LWR@textcurrentfont{
            \chemnum_get_compound_property:nn {#1} {counter-representation}
        }
      }
    \group_end:
    \chemnum_get_compound_property:nn {#1} {post-main-label-code}
  }

\cs_gset_protected:Npn \chemnum_subcompound_write:nn #1#2
  {
    \group_begin:
      \bool_if:NTF \l__chemnum_compound_local_bool
        { \l__chemnum_local_label_format_tl }
        { \chemnum_get_compound_property:nn {#1} {label-format} }
      {
        \LWR@textcurrentfont{
            \chemnum_get_subcompound_property:nnn {#1} {#2}
            {counter-representation}
        }
      }
    \group_end:
  }

\ExplSyntaxOff
```

File 69 **lwarp-chkfloat.sty**

§ 166 Package chkfloat

Pkg chkfloat chkfloat is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{chkfloat}[2012/08/19]
```

File 70 **lwarp-chngpage.sty**

§ 167 Package chngpage

(*Emulates or patches code by* Peter Wilson.)

Pkg chngpage chngpage is emulated.

for HTML output: Discard all options for lwarp-chngpage:

```
\LWR@ProvidesPackageDrop{chngpage}[2009/10/20]
\LWR@origRequirePackage{lwarp-changepage}
```

File 71 **lwarp-cite.sty**

§ 168 Package cite

(*Emulates or patches code by* Donald Arseneau.)

Pkg cite cite is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{cite}[2015/02/27]
```

For the [super] option, the \kern must be removed:

```
\def\LWRCT@biblabel#1{\@citess{#1}\kern-\labelsep\,}

\ifdefstrequal{\@biblabel}{\LWRCT@biblabel}
{
    \def\@biblabel#1{\@citess{#1}}
}{}
```

For the [super] option, \textsuperscript is used instead of math superscript:

```
\def\@citess#1{\textsuperscript{#1}}

\DeclareDocumentCommand\citepunct{}{,\,\relax}
```

File 72 **lwarp-CJK.sty**

§ 169 Package CJK

Pkg CJK CJK does not work with lwarp unless called from ctex.

for HTML output:

```
\@ifpackageloaded{xeCJK}{}{
    \LWR@loadnever{CJK}{ctex, xeCJK}
}

\LWR@ProvidesPackagePass{CJK}[2015/04/18]
```

File 73 **lwarp-CJKutf8.sty**

§ 170 Package CJKutf8

Pkg CJKutf8 CJKutf8 does not work with lwarp unless called from ctex.

for HTML output:

```
\@ifpackageloaded{xeCJK}{}{
    \LWR@loadnever{CJKutf8}{ctex, xeCJK}
}

\LWR@ProvidesPackagePass{CJKutf8}[2015/04/18]
```

File 74 **lwarp-clrdblpg.sty**

§ 171 Package clrdblpg

Pkg clrdblpg clrdblpg is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{clrdblpg}[2018/04/21]
```

File 75 **lwarp-cmdtrack.sty**

§ 172 Package cmdtrack

Pkg cmdtrack cmdtrack is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{cmdtrack}[2012/12/18]

\newcommand{\untrack}[1]{}
```

File 76 **lwarp-color.sty**

§ 173 Package color

Pkg color Allowed but ignored. xcolor is then required as well.

color is superceded by xcolor, and lwarp requires several of the features of xcolor. When color is requested, xcolor is loaded as well.

for HTML output:

```
\LWR@ProvidesPackageDrop{color}[2016/07/10]
\RequirePackage{xcolor}
```

File 77 **lwarp-colortbl.sty**

§ 174 Package colortbl

Pkg colortbl colortbl is used as-is for print output, and emulated for HTML.

⚠ row/cell color Only use `\rowcolor` and `\cellcolor` at the start of a row, in that order.

colortbl ignores the overhang arguments.

for HTML output: A placeholder definition is forgotten first:

```
\let\rowcolor\relax

\LWR@ProvidesPackagePass{colortbl}[2018/12/12]
```

The following `\LWR@HTML` versions are used inside an HTML `tabular`.

`\columncolor` `[`⟨*model*⟩`]` `{`⟨*color*⟩`}` `[`⟨*left overhang*⟩`]` `[`⟨*right overhang*⟩`]`

`\LWR@getmynexttoken` is not used here because `\columncolor` is not used inside the data area of the tabular.

```
\NewDocumentCommand{\LWR@HTML@columncolor}{O{named} m o o}{%
\convertcolorspec{#1}{#2}{HTML}\LWR@columnHTMLcolor%
\LWR@addtabularcellcolor%
}

\AtBeginDocument{\LWR@formatted{columncolor}}
```

`\LWR@getmynexttoken` is used for `\rowcolor` because it is used inside the data area of the tabular.

`\rowcolor` `[`⟨*model*⟩`]` `{`⟨*color*⟩`}` `[`⟨*left overhang*⟩`]` `[`⟨*right overhang*⟩`]`

```
\NewDocumentCommand{\LWR@HTML@rowcolor}{O{named} m o o}{%
```

```
\convertcolorspec{#1}{#2}{HTML}\LWR@rowHTMLcolor%
\LWR@getmynexttoken%
}

\AtBeginDocument{\LWR@expandableformatted{rowcolor}}
```

\cellcolor [⟨*model*⟩] {⟨*color*⟩} [⟨*left overhang*⟩] [⟨*right overhang*⟩]

```
\NewDocumentCommand{\LWR@HTML@cellcolor}{O{named} m o o}{%
\convertcolorspec{#1}{#2}{HTML}\LWR@cellHTMLcolor%
\LWR@addtabularcellcolor%
}

\AtBeginDocument{\LWR@formatted{cellcolor}}
```

\arrayrulecolor [⟨*model*⟩] {⟨*color*⟩}

The HTML version for use outside a `tabular`. Inside a `tabular`, `\LWR@HTML@arrayrulecolornexttoken` is used instead.

```
\newcommand{\LWR@HTML@arrayrulecolor}[2][named]{%
\convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
}

\AtBeginDocument{\LWR@expandableformatted{arrayrulecolor}}
```

\LWR@arrayrulecolornexttoken [⟨*model*⟩] {⟨*color*⟩}

The HTML version for use inside a `tabular`.

```
\newcommand{\LWR@HTML@arrayrulecolornexttoken}[2][named]{%
\convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
\LWR@getmynexttoken%
}

\AtBeginDocument{\LWR@expandableformatted{arrayrulecolornexttoken}}
```

\doublerulesepcolor [⟨*model*⟩] {⟨*color*⟩}

The version for use outside a `tabular`.

```
\newcommand{\LWR@HTML@doublerulesepcolor}[2][named]{}

\AtBeginDocument{\LWR@expandableformatted{doublerulesepcolor}}
```

\LWR@doublerulesepcolornexttoken [⟨*model*⟩] {⟨*color*⟩}

The version for use inside a `tabular`.

```
\newcommand{\LWR@HTML@doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}

\AtBeginDocument{\LWR@expandableformatted{doublerulesepcolornexttoken}}
```

File 78 **lwarp-continue.sty**

§ 175 Package continue

Pkg continue continue is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{continue}}[2018/12/09]

\newcommand*{\flagcont}{}
\newcommand*{\flagend}{}
\newcommand*{\flagword}{}
\newcommand*{\preflagword}{}
\newcommand*{\postflagword}{}
\newlength\contsep
\newlength\contdrop
```

File 79 **lwarp-copyrightbox.sty**

§ 176 Package copyrightbox

(*Emulates or patches code by* Thomas Fischer, Ives van der Flaas.)

Pkg copyrightbox copyrightbox is emulated for use by lwarp.

The entire copyright box is placed inside a of class copyrightbox.

The contents are placed inside a of class copyrightboxcontents.

The copyright notice is placed inside a of class copyrightboxnote.

for HTML output:

```
\LWR@ProvidesPackageDrop{copyrightbox}[2011/11/27]

\newcommand{\copyrightbox}[3][r]{%
\begin{BlockClass}[
    display: inline-flex;
    flex-direction: column ;
]{copyrightbox}
\begin{BlockClass}{copyrightboxcontents}
#2
\end{BlockClass}
\begin{BlockClass}{copyrightboxnote}
#3
\end{BlockClass}
\end{BlockClass}
}

\newcommand{\CRB@setcopyrightfont}{}
\newcommand{\CRB@setcopyrightparagraphstyle}{}
```

File 80 **lwarp-crop.sty**

§ 177 Package crop

(*Emulates or patches code by* Melchior FRANZ.)

Pkg crop Emulated.

for HTML output: Discard all options for lwarp-crop:

```
\LWR@ProvidesPackageDrop{crop}[2003/05/20]

\newcommand*{\crop}[1][]{}
\newcommand*{\cropdef}[6][]{}
```

File 81 **lwarp-cuted.sty**

§ 178 Package cuted

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg cuted cuted is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{cuted}[2012/10/04]

\newenvironment{strip}{}{}
\newskip\stripsep
\def\oldcolsbreak#1{}
```

File 82 **lwarp-cutwin.sty**

§ 179 Package cutwin

(*Emulates or patches code by* Peter Wilson and Alan Hoenig.)

Pkg cutwin Emulated.

for HTML output: Discard all options for lwarp-cutwin:

```
\LWR@ProvidesPackageDrop{cutwin}[2010/09/29]

\newcommand*{\opencutleft}{}
\newcommand*{\opencutright}{}
\newcommand*{\opencutcenter}{}
\newcommand*{\cutfuzz}{}

```

```
\newenvironment{cutout}[4]
{\marginpar{\windowpagestuff}}
{}

\newcommand*{\windowpagestuff}{}

\newcommand*{\pageinwindow}{%
% \begin{minipage}{.3\linewidth}
\windowpagestuff
% \end{minipage}
}

\newenvironment{shapedcutout}[3]
{\marginpar{\picinwindow}}
{}

\newcommand*{\putstuffinpic}{}

\newcommand*{\picinwindow}{%
\begin{picture}(0,0)
\putstuffinpic
\end{picture}}
```

File 83 **lwarp-dblfloatfix.sty**

§ 180 Package dblfloatfix

Pkg dblfloatfix dblfloatfix is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{dblfloatfix}[2012/12/31]
```

File 84 **lwarp-dblfnote.sty**

§ 181 Package dblfnote

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg dblfnote dblfnote is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{dblfnote}[1999/07/14]

\newcounter{DFNsloppiness}
\newdimen\DFNcolumnsep
\newdimen\DFNcolumnwidth
\def\DFNallowcbreak{}
\def\DFNinhibitcbreak{}
\def\DFNtrysingle{}
\def\DFNalwaysdouble{}
\def\DFNruleboth{}
\def\DFNruleleft{}
```

File 85 **lwarp-dcolumn.sty**

§ 182 Package dcolumn

Pkg dcolumn dcolumn is emulated by the lwarp core.

```
\LWR@ProvidesPackageDrop{dcolumn}[2014/10/28]
```

File 86 **lwarp-diagbox.sty**

§ 183 Package diagbox

(*Emulates or patches code by* Leo Liu.)

Pkg diagbox diagbox is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{diagbox}[2016/12/28]
```

To restore print-mode inside a `lateximage`:

```
\LetLtxMacro\LWR@origdiagbox@double\diagbox@double
\LetLtxMacro\LWR@origdiagbox@triple\diagbox@triple

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\diagbox@double\LWR@origdiagbox@double%
\LetLtxMacro\diagbox@triple\LWR@origdiagbox@triple%
}
```

`\LWR@diagbox@AB` {⟨*E/W*⟩} {⟨*A*⟩} {⟨*E/W*⟩} {⟨*B*⟩}

```
\newcommand{\LWR@diagbox@AB}[4]{
\begingroup%
\LetLtxMacro\\\newline%
\BlockClassSingle{diagbox#1}{#2}%
\BlockClassSingle{diagbox#3}{#4}%
\endgroup%
\LWR@stoppars%
}
```

`\LWR@diagboxNW` {⟨*A*⟩} {⟨*B*⟩}

```
\newcommand{\LWR@diagboxNW}[2]{%
\LWR@diagbox@AB{E}{#2}{W}{#1}%
}
```

Likewise for NE, SW, SE:

```
\newcommand{\LWR@diagboxNE}[2]{%
\LWR@diagbox@AB{W}{#1}{E}{#2}%
}

\let\LWR@diagboxSW\LWR@diagboxNE
\let\LWR@diagboxSE\LWR@diagboxNW
```

`\diagbox@double` {⟨*keys*⟩} {⟨*A*⟩} {⟨*B*⟩}

```
\def\diagbox@double#1#2#3{%
\setkeys{diagbox}{dir=NW,#1}%
\@nameuse{LWR@diagbox\diagbox@dir}{#2}{#3}%
}
```

`\LWR@diagboxTNW` {⟨*title*⟩} {⟨*A*⟩} {⟨*B*⟩}

```
\newcommand{\LWR@diagboxTNW}[3]{%
\BlockClassSingle{diagboxtitleN}{#1}
\LWR@diagboxNW{#2}{#3}
}
```

Likewise for NE, SW, SE:

```
\newcommand{\LWR@diagboxTNE}[3]{%
\BlockClassSingle{diagboxtitleN}{#1}
\LWR@diagboxNE{#2}{#3}
}

\newcommand{\LWR@diagboxTSW}[3]{%
\LWR@diagboxSW{#2}{#3}
\BlockClassSingle{diagboxtitleS}{#1}
\LWR@stoppars%
}

\newcommand{\LWR@diagboxTSE}[3]{%
\LWR@diagboxSE{#2}{#3}
\BlockClassSingle{diagboxtitleS}{#1}
\LWR@stoppars%
}
```

`\diagbox@triple` {⟨*keys*⟩} {⟨*A*⟩} {⟨*T*⟩} {⟨*B*⟩}

```
\def\diagbox@triple#1#2#3#4{%
\setkeys{diagbox}{dir=NW,#1}%
\@nameuse{LWR@diagboxT\diagbox@dir}{#3}{#2}{#4}%
}
```

File 87 **lwarp-dingbat.sty**

§ 184 Package dingbat

(*Emulates or patches code by* Scott Pakin.)

Pkg dingbat dingbat is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{dingbat}[2001/04/27]

\newcommand*{\LWR@dingbatsymbol}[1]{\HTMLunicode{#1}}

\newcommand{\LWR@HTML@rightpointright}{\LWR@dingbatsymbol{261E}}
\newcommand{\LWR@HTML@leftpointright}{\LWR@dingbatsymbol{261E}}
\newcommand{\LWR@HTML@leftthumbsdown}{\LWR@dingbatsymbol{1F44E}}
\newcommand{\LWR@HTML@leftthumbsup}{\LWR@dingbatsymbol{1F44D}}
\newcommand{\LWR@HTML@rightpointleft}{\LWR@dingbatsymbol{261C}}
\newcommand{\LWR@HTML@rightthumbsdown}{\LWR@dingbatsymbol{1F44E}}
\newcommand{\LWR@HTML@rightthumbsup}{\LWR@dingbatsymbol{1F44D}}
\newcommand{\LWR@HTML@squarewithdots}{\LWR@dingbatsymbol{25C7}}
\newcommand{\LWR@HTML@filledsquarewithdots}{\LWR@dingbatsymbol{25C6}}
\newcommand{\LWR@HTML@Sborder}{\LWR@dingbatsymbol{271A}}
\newcommand{\LWR@HTML@Zborder}{\LWR@dingbatsymbol{274B}}
\newcommand{\LWR@HTML@largepencil}{\LWR@dingbatsymbol{270E}}
\newcommand{\LWR@HTML@anchor}{\LWR@dingbatsymbol{2693}}
\newcommand{\LWR@HTML@carriagereturn}{\LWR@dingbatsymbol{23CE}}
\newcommand{\LWR@HTML@checkmark}{\LWR@dingbatsymbol{2713}}
\newcommand{\LWR@HTML@eye}{\LWR@dingbatsymbol{1F441}}
\newcommand{\LWR@HTML@satellitedish}{\LWR@dingbatsymbol{1F4E1}}
\newcommand{\LWR@HTML@smallpencil}{\LWR@dingbatsymbol{270E}}

\LWR@formatted{rightpointright}
\LWR@formatted{leftpointright}
\LWR@formatted{leftthumbsdown}
\LWR@formatted{leftthumbsup}
\LWR@formatted{rightpointleft}
\LWR@formatted{rightthumbsdown}
\LWR@formatted{rightthumbsup}
\LWR@formatted{squarewithdots}
\LWR@formatted{filledsquarewithdots}
\LWR@formatted{Sborder}
\LWR@formatted{Zborder}
\LWR@formatted{largepencil}
\LWR@formatted{anchor}
\LWR@formatted{carriagereturn}
\LWR@formatted{checkmark}
\LWR@formatted{eye}
\LWR@formatted{satellitedish}
\LWR@formatted{smallpencil}
```

File 88 **lwarp-dprogress.sty**

§ 185 Package dprogress

Pkg dprogress dprogress is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{dprogress}[2008/02/21]
```

File 89 **lwarp-draftcopy.sty**

§ 186 Package draftcopy

Pkg draftcopy draftcopy is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{draftcopy}[2002/02/25]

\newcommand{\draftcopyVersion}[1]{}
\newcommand{\draftcopySetGrey}[1]{}
\newcommand{\draftcopySetScale}[1]{}
\newcommand{\draftcopySetScaleFactor}[1]{}
\newcommand{\draftcopyFirstPage}[1]{}
\newcommand{\draftcopyLastPage}[1]{}
\newcommand{\draftcopyName}[2]{}
\newcommand{\draftcopyPageTransform}[1]{}
\newcommand{\draftcopyBottomTransform}[1]{}
\newcommand{\draftcopyPageX}[1]{}
\newcommand{\draftcopyPageY}[1]{}
\newcommand{\draftcopyBottomX}[1]{}
\newcommand{\draftcopyBottomY}[1]{}
```

File 90 **lwarp-draftfigure.sty**

§ 187 Package draftfigure

Pkg draftfigure draftfigure is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{draftfigure}[2017/07/19]
\RequirePackage{xkeyval}

\define@key{draftfigure}{code}{}
\define@key{draftfigure}{noframe}[true]{}
\define@key{draftfigure}{filename}[true]{}
\define@key{draftfigure}{content}[]{}
\define@key{draftfigure}{style}[normal]{}
\define@key{draftfigure}{position}[left]{}
\define@key{draftfigure}{size}[normal]{}
\newcommand\setdf[1]{\setkeys{draftfigure}{#1}}
```

File 91 **lwarp-draftwatermark.sty**

§ 188 Package draftwatermark

(*Emulates or patches code by* Sergio Callegari.)

Pkg draftwatermark draftwatermark is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{draftwatermark}[2015/02/19]

\newcommand{\SetWatermarkAngle}[1]{}
\newcommand{\SetWatermarkColor}[1]{}
\newcommand{\SetWatermarkLightness}[1]{}
\newcommand{\SetWatermarkFontSize}[1]{}
\newcommand{\SetWatermarkScale}[1]{}
\newcommand{\SetWatermarkHorCenter}[1]{}
\newcommand{\SetWatermarkVertCenter}[1]{}
\newcommand{\SetWatermarkText}[1]{}
```

File 92 **lwarp-easy-todo.sty**

§ 189 Package easy-todo

(*Emulates or patches code by* Juan Rada-Vilela.)

Pkg easy-todo easy-todo is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{easy-todo}[2014/01/01]
```

\listoftodos Modified to correct buggy use of \flushright.

```
\let\LWR@origlistoftodos\listoftodos

\renewcommand{\listoftodos}{%
\begingroup
\renewcommand{\flushright}{}
\LWR@origlistoftodos
\endgroup
}
```

\todoii Modified to use \textcolor instead of \color.

```
\renewcommand{\todoii}[2]{%
\ifthenelse{\equal{\@todoobeyfinal}{true}}%
    {%
        \ifoptionfinal{\todoenable{false}}{\todoenable{true}}%
    }%
    {}%
\ifthenelse{\equal{\@todoenable}{true}}%
    {%
        \refstepcounter{todos}%
        \noindent{%
            \todocolor%
            \LWR@textcurrentcolor{%
                \normalfont\scriptsize{\bfseries{\thetodos.#1}}%
            }%
        }%
        \addcontentsline{lod}{todos}{\protect{\thetodos. }\LWR@isolate{#2}}%
```

```
    }%
    {}%
}
```

File 93 **lwarp-ebook.sty**

§ 190 Package ebook

(*Emulates or patches code by* Jørgen Steensgaard.)

Pkg ebook ebook is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{ebook}

\setcounter{secnumdepth}{0}
\setcounter{tocdepth}{2}

\providecommand{\pagefill}[1][0.001mm]{\noindent}

\providecommand{\ebook}{
\setcounter{secnumdepth}{0}
\setcounter{tocdepth}{2}
}
```

File 94 **lwarp-ed.sty**

§ 191 Package ed

(*Emulates or patches code by* Michael Kohlhase.)

Pkg ed ed is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{ed}[2012/01/29]
```

Bugs:

1. `todolist` fails with the `hide` option, as does `\edexplanation`.
2. `\edstubURI` is actually `\edstuURI`.

```
\RequirePackage{xcolor}

\renewenvironment{edstub}[2][The following blue text]
{%
    \def\@test{#1}%
    \begin{center}%
        \huge%
        \textcolor{red}{%
            #1 is only a provisional stub\\\Large
```

```
            the Office document
            \ifx\ed@stubURI\@empty{#2}\else\href{\ed@stubURI}{#2}\fi\
            contains more text\\which will be merged for the final document%
        }%
    \end{center}%
    \BlockClass[color:blue]{edstub}%
}
{\endBlockClass}
```

File 95 **lwarp-ellipsis.sty**

§ 192 Package ellipsis

(*Emulates or patches code by* Peter J. Heslin.)

Pkg ellipsis ellipsis is emulated.

```
\LWR@ProvidesPackageDrop{ellipsis}[2004/09/28]

\newcommand{\ellipsisgap}{0.1em}

\newcommand*{\midwordellipsis}{\,\textellipsis\,}
```

File 96 **lwarp-embrac.sty**

§ 193 Package embrac

(*Emulates or patches code by* Clemens Niederberger.)

Pkg embrac embrac is nullfied for HTML and used as-is for print.

for HTML output:

```
\LWR@ProvidesPackagePass{embrac}[2017/07/04]

\LetLtxMacro\LWR@orig@HTML@emph\LWR@HTML@emph
\RenewDocumentCommand{\LWR@HTML@emph}{s m}{\LWR@orig@HTML@emph{#2}}

\LetLtxMacro\LWR@orig@HTML@textit\LWR@HTML@textit
\RenewDocumentCommand{\LWR@HTML@textit}{s m}{\LWR@orig@HTML@textit{#2}}

\LetLtxMacro\LWR@orig@HTML@textsl\LWR@HTML@textsl
\RenewDocumentCommand{\LWR@HTML@textsl}{s m}{\LWR@orig@HTML@textsl{#2}}

\ifxetexorluatex
    \LetLtxMacro\LWR@orig@HTML@textsi\LWR@HTML@textsi
    \RenewDocumentCommand{\LWR@HTML@textsi}{s m}{%
    \LWR@orig@HTML@textsi{#2}}
\fi

\AtBeginDocument{
    \LWR@formatted{emph}
```

```
    \LWR@formatted{textit}
    \LWR@formatted{textsl}
    \ifxetexorluatex
        \LWR@formatted{textsi}
    \fi
}

\newcommand{\LWR@HTML@EmbracOff}{}
\LWR@formatted{EmbracOff}

\newcommand{\LWR@HTML@EmbracOn}{}
\LWR@formatted{EmbracOn}
```

File 97 **lwarp-emptypage.sty**

§ 194 Package emptypage

Pkg emptypage emptypage is ignored.

for HTML output: Discard all options for lwarp-emptypage:

```
\LWR@ProvidesPackageDrop{emptypage}[2010/05/30]
```

File 98 **lwarp-endfloat.sty**

§ 195 Package endfloat

Pkg endfloat endfloat is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{endfloat}[2018/03/24]

\newcommand\figureplace{}
\newcommand\tableplace{}
\newcommand\floatplace[1]{}
\newcounter{posttable}
\newcounter{postfigure}
\newcommand*{\theposttbl}{}
\newcommand*{\thepostfig}{}
\newcommand{\AtBeginFigures}[1]{}
\newcommand{\AtBeginTables}[1]{}
\newcommand{\AtBeginDelayedFloats}[1]{}
\newcommand*{\processdelayedfloats}{}
\newcommand*{\efloatseparator}{}
\def\efloattype{}
\providecommand\efloatheading[1]{}
\providecommand\efloatpreamble{}
\providecommand\efloatpostamble{}
```

File 99 **lwarp-endheads.sty**

§ 196 Package

endheads

Pkg endheads endheads is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{endheads}[2017/04/06]

\newcommand{\changesinglepageabbrev}[1]{}
\newcommand{\changemultiplepageabbrev}[1]{}
\newcommand{\changenotesname}[1]{}
\newcommand{\changenotesheader}[1]{}
\newcommand{\changenotescontentsname}[1]{}
\newcommand{\changechapternotesline}[1]{}
\newcommand{\checknoteheaders}{}
\newif\ifnotesincontentson \notesincontentsonfalse
\newcommand{\notesincontents}{\notesincontentsontrue}
\newif\ifendnoteheaderson \endnoteheadersonfalse
\newcommand{\setupendnoteheaders}{%
    \endnoteheadersontrue%
}
\newif\iftitleinnotes \titleinnotestrue
\newcommand{\styleforchapternotebegin}{}
\newcommand{\styleforchapternoteend}{}
\newcommand{\setstyleforchapternotebegin}[1]{%
    \renewcommand{\styleforchapternotebegin}{#1}%
}
\newcommand{\setstyleforchapternoteend}[1]{%
    \renewcommand{\styleforchapternoteend}{#1}%
}
\newcommand{\resetendnotes}{}
\newif\ifnotesbychapteron \notesbychapteronfalse
\newcommand{\notesbychapter}{\notesbychapterontrue}
```

File 100 **lwarp-endnotes.sty**

§ 197 Package

endnotes

(*Emulates or patches code by* John Lavagnino.)

Pkg endnotes Used as-is.

table of contents To place the endnotes in the TOC, use:

```
\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*{\notesname}{Endnotes} % optional
```

HTML page To additionally have the endnotes on their own HTML page, if `FileDepth` allows:

```
\ForceHTMLPage
\theendnotes
```

for HTML output:

```
\LWR@ProvidesPackagePass{endnotes}

\def\enoteformat{%
% \rightskip\z@ \leftskip\z@ \parindent=1.8em
\leavevmode
% \llap{
\makeenmark
% }
}

\def\@makeenmark{\hbox{\LWR@htmlspan{sup}{\normalfont\theenmark}}}
\def\makeenmark{\@makeenmark}
```

File 101 **lwarp-enumerate.sty**

§ 198 Package enumerate

Pkg enumerate enumerate is supported with no changes.

This package is only required because it was used in the past to drop and then emulate the package. It cannot be removed because an older version which dropped the package may still remain, for example in a local vs. distribution directory, but it is now supported directly by lwarp and thus must no longer be dropped.

for HTML output:

```
\LWR@ProvidesPackagePass{enumerate}[2015/07/23]
```

File 102 **lwarp-enumitem.sty**

§ 199 Package enumitem

(*Emulates or patches code by* Javier Bezos.)

Pkg enumitem enumitem is supported with minor adjustments.

for HTML output:

```
\LWR@ProvidesPackagePass{enumitem}[2018/11/30]
```

for HTML output:

```
\begin{warpHTML}
```

`\newlist` {⟨*name*⟩} {⟨*type*⟩} {⟨*maxdepth*⟩}
`\renewlist` {⟨*name*⟩} {⟨*type*⟩} {⟨*maxdepth*⟩}

For enumitem lists, new lists must have the start and end actions assigned to the new environment. Renewed lists already have their actions assigned, and thus need no changes.

```
\let\LWR@enumitem@orignewlist\newlist

\renewcommand*{\newlist}[3]{%
\LWR@enumitem@orignewlist{#1}{#2}{#3}%
\AtBeginEnvironment{#1}{\@nameuse{LWR@#2start}}%
\AtEndEnvironment{#1}{\@nameuse{LWR@#2end}}%
}

\def\DrawEnumitemLabel{}

\end{warpHTML}
```

File 103 **lwarp-epigraph.sty**

§ 200 Package

epigraph

(*Emulates or patches code by* Peter Wilson.)

Pkg epigraph epigraph is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{epigraph}[2009/09/02]

\DeclareDocumentCommand{\qitem}{m m}
{
\begin{BlockClass}{qitem}
#1
\ifbool{FormatWP}
{\begin{BlockClass}[border-top:1px solid gray]{epigraphsource}}
{\begin{BlockClass}{epigraphsource}}
#2
\end{BlockClass}
\end{BlockClass}
}


\DeclareDocumentCommand{\epigraph}{m m}
{
\begin{LWR@BlockClassWP}{\LWR@print@mbox{text-align:right}}{}{epigraph}
\qitem{#1}{#2}
\end{LWR@BlockClassWP}
}

\DeclareDocumentEnvironment{epigraphs}{}
{\LWR@BlockClassWP{\LWR@print@mbox{text-align:right}}{}{epigraph}}
{\endLWR@BlockClassWP}
```

Use css to format epigraphs.

The following are null commands for source compatibility:

```
\newenvironment*{flushepinormal}{}{}
```

```
\@ifclassloaded{memoir}{
\setlength{\epigraphwidth}{.5\linewidth}
\renewcommand{\textflush}{flushepinormal}
\renewcommand{\epigraphhead}[2][0]{#2}
\renewcommand{\dropchapter}[1]{}
\renewcommand*{\undodrop}{}
}{% not memoir
\newlength{\epigraphwidth}
\setlength{\epigraphwidth}{.5\linewidth}
\newcommand{\textflush}{flushepinormal}
\newcommand{\epigraphflush}{flushright}
\newcommand{\sourceflush}{flushright}
\newcommand*{\epigraphsize}{\small}
\newlength{\epigraphrule}
\newlength{\beforeepigraphskip}
\newlength{\afterepigraphskip}
\newcommand{\epigraphhead}[2][0]{#2}
\newcommand{\dropchapter}[1]{}
\newcommand*{\undodrop}{}
}% not memoir

\let\cleartoevenpage\relax% also in nextpage
\newcommand{\cleartoevenpage}[1][]{}
```

File 104 **lwarp-epsfig.sty**

§ 201 Package

epsfig

Pkg epsfig epsfig is emulated for use by lwarp.

⚠ Only the LaTeX2e syntax is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{epsfig}[2017/06/25]
```

A few additional keys to capture the filename:

```
\RequirePackage{graphics}

\define@key{igraph}{file}{%
    \xdef\LWR@epsfig@filename{#1}%
}

\define@key{igraph}{figure}{%
    \xdef\LWR@epsfig@filename{#1}%
}

\define@key{igraph}{prolog}{}

\define@key{igraph}{silent}[]{}
```

The captured filename is used as the argument to `\includegraphics`:

```
\newcommand{\epsfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}

\newcommand{\psfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}
```

File 105 **lwarp-epstopdf.sty**

§ 202 Package

epstopdf

Pkg epstopdf

Previous versions of lwarp had a nullfied version, but now epstopdf-base is supported. lwarp-epstopdf becomes a placeholder to overwrite previous versions.

See package epstopdf-base for details.

for HTML output:

```
\LWR@ProvidesPackagePass{epstopdf}[2016/05/15]
```

File 106 **lwarp-epstopdf-base.sty**

§ 203 Package

epstopdf-base

Pkg epstopdf-base

⚠ convert to .svg

Images with an .eps extension will be converted to .pdf. The HTML output uses the .svg version, so use

Enter ⇒ **lwarpmk pdftosvg <listofPDFfiles>**

to generate .svg versions.

for HTML output:

```
\LWR@ProvidesPackagePass{epstopdf-base}[2016/05/15]
```

Redefine to remember the image filename, replacing .pdf with .svg. Use the epstopdf print version inside a latexmage.

```
\newcommand*{\LWR@HTML@ETE@OrgGin@setfile}[3]{%
    \edef\LWR@tempone{#3}%
    \StrSubstitute{\LWR@tempone}{.pdf}{.svg}[\LWR@tempone]%
    \StrSubstitute{\LWR@tempone}{.PDF}{.SVG}[\LWR@tempone]%
    \xdef\LWR@parsedfilename{\LWR@tempone}%
}

\LWR@formatted{ETE@OrgGin@setfile}
```

\includegraphics in HTML mode redefines \Gin@setfile to be \LWR@HTML@Gin@setfile, which is now redirected to epstopdf's version:

```
\renewcommand*{\LWR@HTML@Gin@setfile}[3]{%
    \ETE@Gin@setfile{#1}{#2}{#3}%
}
```

Allow .eps images to be found if a suffix is not provided:

```
\AtBeginDocument{
\DeclareGraphicsExtensions{%
    .eps,.EPS,.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
}
\DeclareGraphicsRule{.svg}{svg}{.svg}{}
\DeclareGraphicsRule{.SVG}{svg}{.SVG}{}
}
```

Likewise when inside a `lateximage`:

```
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{%
    .eps,.EPS,.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
}%
}
```

File 107 **lwarp-errata.sty**

§ 204 Package

errata

(*Emulates or patches code by* Michael Kohlhase.)

Pkg errata errata is patched for use by lwarp.

This is for v0.3 of errata. A newer version of errata with more features is under development, at which time the lwarp version will have to be updated.

for HTML output: Macros are being defined with the math dollar, so enable the HTML version during package loading:

```
\StartDefiningMath
```

Now load the package:

```
\LWR@ProvidesPackagePass{errata}[2006/11/12]
```

Patches for dynamic inline math:

```
\xpatchcmd{\erratumAdd}
    {$_a^{\arabic{erratum}}$}
%     {\inlinemathother$_a^{\arabic{erratum}}$\inlinemathnormal}
    {\textsubscript{a}\textsuperscript{\arabic{erratum}}}
    {}
    {\LWR@patcherror{erratum}{erratumAdd}}

\xpatchcmd{\erratumDelete}
    {$_d^{\arabic{erratum}}$}
%     {\inlinemathother$_d^{\arabic{erratum}}$\inlinemathnormal}
    {\textsubscript{d}\textsuperscript{\arabic{erratum}}}
    {}
```

```
    {\LWR@patcherror{erratum}{erratumDelete}}

\xpatchcmd{\erratumReplace}
    {$_r^{\arabic{erratum}}$}
%     {\inlinemathother$_r^{\arabic{erratum}}$\inlinemathnormal}
    {\textsubscript{r}\textsuperscript{\arabic{erratum}}}
    {}
    {\LWR@patcherror{erratum}{erratumReplace}}

\xpatchcmd{\erratum}
    {$_a$}
%     {\inlinemathother$_a$\inlinemathnormal}
    {\textsubscript{a}}
    {}
    {\LWR@patcherror{erratum}{erratumDelete}}

\xpatchcmd{\erratum}
    {$_d^{\@thefnmark}$}
%     {\inlinemathother$_d^{\@thefnmark}$\inlinemathnormal}
    {\textsubscript{d}\textsuperscript{\@thefnmark}}
    {}
    {\LWR@patcherror{erratum}{eDelete}}

\xpatchcmd{\erratum}
    {$_r^{\@thefnmark}$}
%     {\inlinemathother$_r^{\@thefnmark}$\inlinemathnormal}
    {\textsubscript{r}\textsuperscript{\@thefnmark}}
    {}
    {\LWR@patcherror{erratum}{eReplace}}
```

Finish the current page's errata before closing and reloading the list:

```
\preto\PrintErrata{\LWR@orignewpage}
```

No longer defining math macros with the HTML $:

```
\StopDefiningMath
```

File 108 **lwarp-eso-pic.sty**

§ 205 Package eso-pic

(*Emulates or patches code by* Rolf Niepraschk.)

Pkg eso-pic eso-pic is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{eso-pic}[2018/04/12]

\newcommand*{\LenToUnit}{}
\newcommand{\AtPageUpperLeft}[1]{}
\newcommand{\AtPageLowerLeft}[1]{}
\newcommand{\AtPageCenter}[1]{}
```

```
\newcommand{\AtStockLowerLeft}[1]{}
\newcommand{\AtStockUpperLeft}[1]{}
\newcommand{\AtStockCenter}[1]{}
\newcommand{\AtTextUpperLeft}[1]{}
\newcommand{\AtTextLowerLeft}[1]{}
\newcommand{\AtTextCenter}[1]{}
\NewDocumentCommand{\AddToShipoutPictureBG}{s +m}{}

\newcommand{\AddToShipoutPicture}{\AddToShipoutPictureBG}
\NewDocumentCommand{\AddToShipoutPictureFG}{s +m}{}
\newcommand*{\ClearShipoutPictureBG}{}
\newcommand*{\ClearShipoutPicture}{}
\newcommand*{\ClearShipoutPictureFG}{}
\newcommand{\gridSetup}[6][]{}
```

File 109 **lwarp-eurosym.sty**

§ 206 Package eurosym

(*Emulates or patches code by* Henrik Theiling.)

Pkg eurosym eurosym is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{eurosym}[1998/08/06]

\renewrobustcmd\officialeuro{\HTMLentity{euro}}
\let\geneuro\officialeuro
\let\geneuronarrow\officialeuro
\let\geneurowide\officialeuro
\let\euro\officialeuro
\renewrobustcmd\eurobars{}
\renewrobustcmd\eurobarsnarrow{}
\renewrobustcmd\eurobarswide{}
```

File 110 **lwarp-everypage.sty**

§ 207 Package everypage

(*Emulates or patches code by* Sergio Callegari.)

Pkg everypage everypage is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{everypage}[2007/06/20]

\newcommand*{\AddEverypageHook}[1]{}
\newcommand*{\AddThispageHook}[1]{}
```

File 111 **lwarp-everyshi.sty**

§ 208 Package everyshi

(*Emulates or patches code by* Martin Schröder.)

Pkg everyshi Emulated.

for HTML output: Discard all options for lwarp-everyshi:

```
\LWR@ProvidesPackageDrop{everyshi}[2001/05/15]

\newcommand*{\EveryShipout}[1]{}
\newcommand*{\AtNextShipout}[1]{}
```

File 112 **lwarp-extramarks.sty**

§ 209 Package extramarks

(*Emulates or patches code by* Piet van Oostrum.)

Pkg extramarks extramarks is emulated.

for HTML output: Discard all options for lwarp-extramarks:

```
\LWR@ProvidesPackageDrop{extramarks}[2019/01/31]

\newcommand*{\extramarks}[2]{}
\newcommand*{\firstleftxmark}{}
\newcommand*{\lastleftxmark}{}
\newcommand*{\firstrightxmark}{}
\newcommand*{\lastrightxmark}{}
\newcommand*{\firstxmark}{}
\newcommand*{\lastxmark}{}
\newcommand*{\topxmark}{}
\newcommand*{\topleftxmark}{}
\newcommand*{\toprightxmark}{}
\newcommand*{\firstleftmark}{}
\newcommand*{\lastrightmark}{}
\newcommand*{\firstrightmark}{}
\newcommand*{\lastleftmark}{}
```

File 113 **lwarp-fancybox.sty**

§ 210 Package fancybox

(*Emulates or patches code by* Timothy Van Zandt.)

Pkg fancybox

fancybox is supported with some patches.

framed equation example

fancybox's documentation has an example FramedEqn environment which combines math, \Sbox, a minipage, and an \fbox. This combination requires that the entire environment be enclosed inside a lateximage, which is done by adding \lateximage at the very start of FramedEqn's beginning code, and \endlateximage at the very end of the ending code. Unfortunately, the HTML alt attribute is not used here.

```
\newenvironmentFramedEqn
{
\lateximage% NEW
\setlength{\fboxsep}{15pt}
. . . }{. . .
\[\fbox{\TheSbox}\]
\endlateximage% NEW
}
```

framing alternatives

\fbox works with fancybox. Also see lwarp's \fboxBlock macro and fminipage environment for alternatives to \fbox for framing environments.

framed table example

The fancybox documentation's example framed table using an \fbox containing a tabular does not work with lwarp, but the FramedTable environment does work if \fbox is replaced by \fboxBlock. This method loses HTML formatting. A better method is to enclose the table's contents inside a fminipage environment. The caption may be placed either inside or outside the fminipage:

```
\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
. . .
\end{tabular}
\end{fminipage}
\end{table}
```

⚠ framed verbatim

lwarp does not support the verbatim environment inside a span, box, or fancybox's \Sbox, but a verbatim may be placed inside a fminipage. The fancybox documentation's example FramedVerb may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
\VerbatimEnvironment
\fminipage{#1}
\beginVerbatim
}{
\endVerbatim
\endfminipage
}
```

framed \VerbBox

fancybox's \VerbBox may be used inside \fbox.

indented alignment

LVerbatim, \LVerbatimInput, and \LUseVerbatim indent with horizontal space which may not line up exactly with what *pdftotext* detects. Some lines may be off slightly in their left edge.

fancybox, fancyvrb
⚠ \VerbatimFootnotes
⚠ sectioning or displaymath

If using fancybox or fancyvrb with \VerbatimFootnotes, and using footnotes in a sectioning command or display math, use \footnotemark and \footnotetext:

```
\subsection[Subsection Name]
    {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when \VerbatimFootnotes are selected. The browser usually compensates.

```
\LWR@ProvidesPackagePass{fancybox}[2010/05/15]
```

After the preamble is loaded, after any patches to Verbatim:

```
\AfterEndPreamble{
\LWR@traceinfo{Patching fancybox.}
```

\VerbatimFootnotes

Patched to use the new version.

```
\def\VerbatimFootnotes{%
\let\@footnotetext\V@footnotetext%
\let\LWR@footnotetext\V@footnotetext% lwarp
}
```

\V@@footnotetext

Patches in a subset of lwarp's \LWR@footnotetext to the fancyvrb version of \V@@footnotetext.

```
\def\V@@footnotetext{%
\LWR@traceinfo{V@footnotetext}%
\global\setbox\LWR@footnotebox=\vbox\bgroup%
```

Add to any current footnotes:

```
    \unvbox\LWR@footnotebox%
```

Remember the footnote number for \ref:

```
    \protected@edef\@currentlabel{%
        \csname p@footnote\endcsname\@thefnmark%
    }% @currentlabel
```

Use HTML superscripts in the footnote even inside a lateximage:

```
    \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a lateximage:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {}%
        {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote to the list:

```
    \@makefntext{}%
  \bgroup%
  \aftergroup{\V@@@footnotetext}%
  \ignorespaces%
}%
}% AfterEndPreamble
\renewcommand*{\@shadowbox}[1]{%
\ifbool{FormatWP}%
{\InlineClass[border:1px solid black]{shadowbox}{#1}}%
{\InlineClass{shadowbox}{#1}}%
}
\renewcommand*{\@doublebox}[1]{%
\ifbool{FormatWP}%
{\InlineClass[border:1px double black]{doublebox}{#1}}%
{\InlineClass{doublebox}{#1}}%
}
\renewcommand*{\@ovalbox}[2]{%
\ifbool{FormatWP}%
{\InlineClass[border:1px solid black; border-radius:1ex]{ovalbox}{#2}}%
{%
    \ifthenelse{\isequivalentto{#1}{\thinlines}}%
        {\InlineClass{ovalbox}{#2}}%
        {\InlineClass{Ovalbox}{#2}}%
}%
}
```

Convert minipages, parboxes, and lists into linear text using the `LWR@nestspan` environment:

```
\let\LWR@origSbox\Sbox
\def\Sbox{\LWR@origSbox\LWR@nestspan}
\let\LWR@origendSbox\endSbox
\def\endSbox{\endLWR@nestspan\LWR@origendSbox}
```

`Beqnarray` is adapted for MathJax or enclosed inside a `lateximage`:

```
\RenewEnviron{Beqnarray}
{\LWR@eqnarrayfactor}
\csgpreto{Beqnarray*}{\boolfalse{LWR@numbereqnarray}}
```

`\GenericCaption` is enclosed in an HTML block:

```
\renewcommand{\GenericCaption}[1]{%
\LWR@figcaption%
```

```
\LWR@isolate{#1}%
\endLWR@figcaption%
}
```

`Btrivlist` is enclosed in an HTML block. This is a tabular, and does not use `\item`.

`\trivlist` `{`⟨*l/c/r*⟩`}` `[`⟨*t/c/b*⟩`]`

```
\RenewDocumentEnvironment{Btrivlist}{m o}
{%
    \begin{BlockClass}{Btrivlist}%
    \tabular{#1}%
}
{%
    \endtabular%
    \end{BlockClass}%
}
```

`Btrivlist` is also neutralized when used inside a span:

```
\AtBeginEnvironment{LWR@nestspan}{%
\RenewDocumentEnvironment{Btrivlist}{m o}{}{}%
}
```

lwarp's handling of `\item` is patched to accept fancybox's optional arguments:

```
\let\LWRFB@origitemizeitem\LWR@itemizeitem
\let\LWRFB@origdescitem\LWR@descitem

\RenewDocumentCommand{\LWR@itemizeitem}{d()o}{%
    \IfValueTF{#2}{%
        \LWRFB@origitemizeitem[#2]%
    }{%
        \LWRFB@origitemizeitem%
    }%
}

\RenewDocumentCommand{\LWR@descitem}{d()o}{%
    \IfValueTF{#2}{%
        \LWRFB@origdescitem[#2]~%
    }{%
        \LWRFB@origdescitem%
    }%
}


\RenewDocumentCommand{\LWR@nestspanitem}{d()}{%
\if@newlist\else{\LWR@htmltagc{br /}}\fi%
\LWR@origitem%
}
```

The various boxed lists become regular lists:

```
\renewenvironment{Bitemize}[1][]{\begin{itemize}}{\end{itemize}}
```

```
\renewenvironment{Benumerate}[1][]{\begin{enumerate}}{\end{enumerate}}
\renewenvironment{Bdescription}[1][]{\begin{description}}{\end{description}}
```

`\boxput` simply prints one then the other argument, side-by-side instead of above and behind:

```
\RenewDocumentCommand{\boxput}{s d() m m}{%
\IfBooleanTF{#1}{#3\quad#4}{#4\quad#3}%
}
```

Neutralized commands:

```
\RenewDocumentCommand{\fancyput}{s d() m}{}
\RenewDocumentCommand{\thisfancyput}{s d() m}{}

\RenewDocumentCommand{\fancypage}{m m}{}
\RenewDocumentCommand{\thisfancypage}{m m}{}

\def\LandScape#1{}
\def\endLandScape{}
\def\@Landscape#1#2#3{}
\def\endLandscape{}
```

Low-level patches for `UseVerbatim` and friends:

```
\let\LWRFB@UseVerbatim\UseVerbatim
\renewcommand*{\UseVerbatim}[1]{%
\LWR@atbeginverbatim{3}{Verbatim}%
\LWRFB@UseVerbatim{#1}%
\LWR@afterendverbatim{.5}%
}

\let\LWRFB@LUseVerbatim\LUseVerbatim

\renewcommand*{\LUseVerbatim}[1]{%
\LWR@atbeginverbatim{3}{LVerbatim}%
\noindent%
\LWRFB@LUseVerbatim{#1}%
\LWR@afterendverbatim{.5}%
}

\def\@BUseVerbatim[#1]#2{%
\LWR@atbeginverbatim{3}{BVerbatim}%
\LWRFB@UseVerbatim{#2}%
\LWR@afterendverbatim{.5}%
}
```

File 114 **lwarp-fancyhdr.sty**

§ 211 Package fancyhdr

(*Emulates or patches code by* Piet van Oostrum.)

Pkg fancyhdr fancyhdr is nullified.

for HTML output: Discard all options for lwarp-fancyhdr:

```
\LWR@ProvidesPackageDrop{fancyhdr}[2019/01/31]

\newcommand*{\fancyhead}[2][]{}
\newcommand*{\fancyfoot}[2][]{}
\newcommand*{\fancyhf}[2][]{}
\newcommand*{\fancypagestyle}[2]{}
\newcommand*{\lhead}[2][]{}
\newcommand*{\chead}[2][]{}
\newcommand*{\rhead}[2][]{}
\newcommand*{\lfoot}[2][]{}
\newcommand*{\cfoot}[2][]{}
\newcommand*{\rfoot}[2][]{}
\newcommand*{\headrulewidth}{}
\newcommand*{\footrulewidth}{}
\newcommand*{\headrule}{}
\newcommand*{\footrule}{}
\newlength{\headwidth}
\newcommand*{\fancyheadoffset}[2][]{}
\newcommand*{\fancyfootoffset}[2][]{}
\newcommand*{\fancyhfoffset}[2][]{}
\newcommand*{\iffloatpage}[2]{#2}
\newcommand*{\ifftopfloat}[2]{#2}
\newcommand*{\iffbotfloat}[2]{#2}
\newcommand*{\iffootnote}[2]{#2}
```

File 115 **lwarp-fancyref.sty**

§ 212 Package fancyref

Pkg fancyref fancyref is emulated.

for HTML output:

```
\LWR@ProvidesPackagePass{fancyref}[1999/02/03]
```

To remove the margin option, if \fancyrefhook is anything other than the paren option, then force it to the default instead. (Comparing to the margin option was not possible since lwarp has revised the meaning of \mbox so the comparison failed.)

```
\newcommand*{\LWRfref@parenfancyrefhook}[1]{(#1)}

\ifdefstrequal{\fancyrefhook}{\LWRfref@parenfancyrefhook}
{}{
    \renewcommand*{\fancyrefhook}[1]{#1}%
}
```

Modified to ignore the page number and varioref.

```
\renewcommand*{\@f@ref}[4]{%
  \@ifundefined{#1r@#2@#3}{%
```

```
    \PackageError{fancyref}{%
      \backslashchar#1ref\space format ‘‘#2’’
      undefined\MessageBreak
      for label type ‘‘#3’’%
    }{%
      The format ‘‘#2’’ was not defined for the label type
      ‘‘#3’’\MessageBreak
      and the \backslashchar#1ref\space command.  Perhaps
      you have only misspelled its name.\MessageBreak
      Otherwise you will have to define it with
      \protect\new#1refformat\MessageBreak
      prior to using it.%
    }%
  }{%
    \fancyrefhook{%
      \@nameuse{#1r@#2@#3}%
        {\ref{#3\fancyrefargdelim#4}}%
%         {\pageref{#3\fancyrefargdelim#4}}% original
%         {\@fancyref@page@ref{#3\fancyrefargdelim#4}}% original
        {}% lwarp
        {}% lwarp
    }%
  }%
}%
```

File 116 **lwarp-fancytabs.sty**

§ 213 Package

fancytabs

Pkg fancytabs fancytabs is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fancytabs}[2016/03/29]

\newcommand{\fancytab}[3][RIGHT]{}
\newcommand{\fancytabsStyle}[1]{}
\newcommand{\fancytabsHeight}[1]{}
\newcommand{\fancytabsWidth}[1]{}
\newcommand{\fancytabsCount}[1]{}
\newcommand{\fancytabsLeftColor}[1]{}
\newcommand{\fancytabsRightColor}[1]{}
\newcommand{\fancytabsTop}[1]{}
\newcommand{\fancytabsTextVPos}[1]{}
\newcommand{\fancytabsTextHPos}[1]{}
\newcommand{\fancytabsGap}[1]{}
\newcommand{\fancytabsFloor}[1]{}
\newcommand{\fancytabsRotate}[1]{}
```

File 117 **lwarp-fancyvrb.sty**

§ 214 Package

fancyvrb

(*Emulates or patches code by* Timothy Van Zandt.)

Pkg fancyvrb

fancyvrb is supported with some patches.

fancybox, fancyvrb
⚠ \VerbatimFootnotes
⚠ sectioning or displaymath

If using fancybox or fancyvrb with \VerbatimFootnotes, and using footnotes in a sectioning command or display math, use \footnotemark and \footnotetext:

```
\subsection[Subsection Name]
    {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when \VerbatimFootnotes are selected. The browser usually compensates.

```
\RequirePackage{xcolor}% for \convertcolorspec

\LWR@ProvidesPackagePass{fancyvrb}[2008/02/07]
```

Initial default patch for fancyvrb:

```
\fvset{frame=none}%
```

After the preamble is loaded, after any patches to Verbatim:

```
\AfterEndPreamble{
\LWR@traceinfo{Patching fancyvrb.}
```

\VerbatimFootnotes

Patched to use the new version.

```
\def\VerbatimFootnotes{%
\let\@footnotetext\V@footnotetext%
\let\footnote\V@footnote%
\let\LWR@footnotetext\V@footnotetext% lwarp
}
```

\V@@footnotetext

Patches in a subset of lwarp's \LWR@footnotetext to the fancyvrb version of \V@@footnotetext.

```
\def\V@@footnotetext{%
\LWR@traceinfo{V@footnotetext}%
\global\setbox\LWR@footnotebox=\vbox\bgroup%
```

Add to any current footnotes:

```
    \unvbox\LWR@footnotebox%
```

Remember the footnote number for `\ref`:

```
    \protected@edef\@currentlabel{%
        \csname p@footnote\endcsname\@thefnmark%
    }% @currentlabel
```

Use HTML superscripts in the footnote even inside a `lateximage`:

```
    \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a `lateximage`:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {}%
        {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote to the list:

```
    \@makefntext{}%
  \bgroup%
  \aftergroup{\V@@@footnotetext}%
  \ignorespaces%
}%

\preto\FVB@Verbatim{\LWR@forcenewpage}
\preto\FVB@LVerbatim{\LWR@forcenewpage}
% \preto\FVB@BVerbatim{\LWR@forcenewpage}% Fails, so done below.
```

Simplified to remove PDF formatting:

```
\def\FV@BeginListFrame@Single{%
  \FV@SingleFrameLine{\z@}%
}

\def\FV@EndListFrame@Single{%
  \FV@SingleFrameLine{\@ne}%
}

\def\FV@BeginListFrame@Lines{%
  \FV@SingleFrameLine{\z@}%
}

\def\FV@EndListFrame@Lines{%
    \FV@SingleFrameLine{\@ne}%
}

\renewcommand*{\FV@SingleFrameSep}{}
```

Adds HTML formatting:

```
\def\FV@BUseVerbatim#1{%
    \LWR@atbeginverbatim[\LWR@FVstyle]{0}{verbatim}%
```

```
    \FV@BVerbatimBegin#1\FV@BVerbatimEnd%
    \LWR@afterendverbatim{0}%
}
```

`\LWR@FVstyle` Holds the style of the verbatim.

```
\newcommand*{\LWR@FVstyle}{}
```

The following patches to `Verbatim` are executed at the start and end of the environment, depending on the choice of `frame`. Original code is from the fancyvrb package.

```
\newcommand*{\LWR@fvstartnone}{%
\LWR@traceinfo{fvstartnone}%
% \hbox to\z@{
\LWR@atbeginverbatim[\LWR@FVstyle]{0}{verbatim}%
% }%
}

\newcommand*{\LWR@fvendnone}{%
\LWR@traceinfo{fvendnone}%
% \hbox to\z@{
\LWR@afterendverbatim{0}%
% }%
}

\newcommand*{\LWR@fvstartsingle}{%
\LWR@traceinfo{fvstartsingle}%
\LWR@fvstartnone%
\FV@BeginListFrame@Single%
}

\newcommand*{\LWR@fvendsingle}{%
\LWR@traceinfo{fvendsingle}%
\FV@EndListFrame@Single%
\LWR@fvendnone%
}

\newcommand*{\LWR@fvstartline}{%
\LWR@traceinfo{fvstartline}%
\LWR@fvstartnone%
% \setlength{\LWR@templengthone}{\baselineskip}%
\FV@BeginListFrame@Lines%
% \setlength{\baselineskip}{\LWR@templengthone}%
% \setlength{\baselineskip}{5pt}%
}

\newcommand*{\LWR@fvendline}{%
\LWR@traceinfo{fvendline}%
\FV@EndListFrame@Lines%
\LWR@fvendnone%
}
```

The following patches select the start/left/right/end behaviors depending on `frame`. Original code is from the fancyvrb package.

```
\newcommand*{\LWR@FVfindbordercolor}{%
\FancyVerbRuleColor%
\LWR@findcurrenttextcolor%
\color{black}%
}

% border width of \FV@FrameRule
\newcommand*{\LWR@FVborderstyle}[1]{%
padding#1: \strip@pt\dimexpr \FV@FrameSep\relax\relax pt ; %
\LWR@FVfindbordercolor %
border#1: \strip@pt\dimexpr \FV@FrameRule\relax\relax pt %
solid \LWR@origpound\LWR@tempcolor ; %
}

\def\FV@Frame@none{%
\renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle}%
\let\FV@BeginListFrame\LWR@fvstartnone%
\let\FV@LeftListFrame\relax%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendnone}

\FV@Frame@none% default values

\def\FV@Frame@single{%
\renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle\LWR@FVborderstyle{}}%
\let\FV@BeginListFrame\LWR@fvstartsingle%
\let\FV@LeftListFrame\FV@LeftListFrame@Single%
\let\FV@RightListFrame\FV@RightListFrame@Single%
\let\FV@EndListFrame\LWR@fvendsingle}

\def\FV@Frame@lines{%
\renewcommand*{\LWR@FVstyle}{%
  \LWR@currenttextcolorstyle\LWR@FVborderstyle{-top}\LWR@FVborderstyle{-bottom}%
}%
\let\FV@BeginListFrame\LWR@fvstartline%
\let\FV@LeftListFrame\relax%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendline}

\def\FV@Frame@topline{%
\renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle\LWR@FVborderstyle{-top}}%
\let\FV@BeginListFrame\LWR@fvstartline%
\let\FV@LeftListFrame\relax%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendnone}

\def\FV@Frame@bottomline{%
\renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle\LWR@FVborderstyle{-bottom}}%
\let\FV@BeginListFrame\LWR@fvstartnone%
\let\FV@LeftListFrame\relax%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendline}
```

```
\def\FV@Frame@leftline{%
\renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle\LWR@FVborderstyle{-left}}%
% To define the \FV@FrameFillLine macro (from \FV@BeginListFrame)
\ifx\FancyVerbFillColor\relax%
\let\FV@FrameFillLine\relax%
\else%
\@tempdima\FV@FrameRule\relax%
\multiply\@tempdima-\tw@%
\edef\FV@FrameFillLine{%
{\noexpand\FancyVerbFillColor{\vrule\@width\number\@tempdima sp}%
\kern-\number\@tempdima sp}}%
\fi%
\let\FV@BeginListFrame\LWR@fvstartnone%
\let\FV@LeftListFrame\FV@LeftListFrame@Single%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendnone}
```

Adds the optional label to the top and bottom edges. Original code is from the fancyvrb package.

```
\def\FV@SingleFrameLine#1{%
%   \hbox to\z@{%
%     \kern\leftmargin
    \ifnum#1=\z@\relax
      \let\FV@Label\FV@LabelBegin
    \else
      \let\FV@Label\FV@LabelEnd
    \fi
    \ifx\FV@Label\relax
%       \FancyVerbRuleColor{\vrule \@width\linewidth \@height\FV@FrameRule}%
    \else
      \ifnum#1=\z@
%         \setbox\z@\hbox{\strut\enspace\FV@LabelBegin\enspace\strut}%
        \ifx\FV@LabelPositionTopLine\relax
        \else
        \LWR@FVfindbordercolor
        \LWR@htmltagc{%
            div class="fancyvrblabel" % extra space
                style="color: \LWR@origpound\LWR@tempcolor"%
        }
        \LWR@print@textrm{\FV@LabelBegin}% \textrm preserves emdash
        \LWR@htmltagc{/div}
        \fi
      \else
%         \setbox\z@\hbox{\strut\enspace\FV@LabelEnd\enspace\strut}%
        \ifx\FV@LabelPositionBottomLine\relax
        \else
        \LWR@FVfindbordercolor

        \LWR@htmltagc{%
            div class="fancyvrblabel" % extra space
                style="color: \LWR@origpound\LWR@tempcolor"%
        }
        \LWR@print@textrm{\FV@LabelEnd}
```

```
        \LWR@htmltagc{/div}
        \fi
      \fi
    \fi
% \hss
% }
}
```

Processes each line, adding optional line numbers. Original code is from the fancyvrb package.

```
\def\FV@ListProcessLine#1{%
  \hbox to \hsize{%
%     \kern\leftmargin
      \hbox to \VerbatimHTMLWidth {%
       \ifcsvoid{FV@LeftListNumber}{}{\kern 2.5em}%
        \FV@LeftListNumber%
%       \FV@LeftListFrame
      \FancyVerbFormatLine{#1}%
      \hss%
%       \FV@RightListFrame
      \FV@RightListNumber%
    }%
      \hss% required to avoid underfull hboxes
}
}
```

Env `BVerbatim`

```
\AtBeginEnvironment{BVerbatim}
{%
\LWR@forcenewpage% instead of \preto
\LWR@atbeginverbatim{0}{bverbatim}%
}

\AfterEndEnvironment{BVerbatim}
{%
\LWR@afterendverbatim{0}%
}
```

End of the modifications to make at the end of the preamble:

```
} % \AfterEndPreamble
```

File 118 **`lwarp-figcaps.sty`**

§ 215 Package figcaps

(*Emulates or patches code by* Patrick W. Daly.)

Pkg `figcaps` Emulated.

for HTML output: Discard all options for lwarp-figcaps:

```
\LWR@ProvidesPackageDrop{figcaps}[1999/02/23]

\newcommand*{\figcapson}{}
\newcommand*{\figcapsoff}{}
\newcommand*{\printfigures}{}
\newcommand*{\figmarkon}{}
\newcommand*{\figmarkoff}{}
\def\figurecapname{Figure Captions}
\def\tablepagename{Tables}
\def\figurepagename{Figures}
```

File 119 **lwarp-figsize.sty**

§ 216 Package figsize

(*Emulates or patches code by* Anthony A. Tanbakuchi.)

Pkg figsize figsize is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{figsize}[2002/03/18]
```

Emulates a virtual 6×9 inch textsize.

```
\newlength{\figwidth}
\newlength{\figheight}

\newcommand{\SetFigLayout}[3][0]{%
\setlength{\figheight}{8in}%
\setlength{\figheight}{\figheight / #2}%
%
\setlength{\figwidth}{5.5in}%
\setlength{\figwidth}{\figwidth / #3}%
}
```

File 120 **lwarp-fitbox.sty**

§ 217 Package fitbox

Pkg fitbox fitbox is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fitbox}[2019/02/20]

\NewDocumentCommand{\fitbox}{s o m}{%
    \begin{BlockClass}{fitbox}
    #3
    \end{BlockClass}
}
```

```
7
8 \newcommand*{\fitboxset}[1]{}
9
10 \newdimen\fitboxnatheight
11 \newdimen\fitboxnatwidth
12
13 \newcommand\SetFitboxLayout[3][]{}
```

File 121 **lwarp-fix2col.sty**

§ 218 Package fix2col

Pkg fix2col fix2col is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{fix2col}[2015/11/13]
```

File 122 **lwarp-fixme.sty**

§ 219 Package fixme

(*Emulates or patches code by* Didier Verna.)

Pkg fixme fixme is patched for use by lwarp.

⚠ external layouts External layouts (`\fxloadlayouts`) are not supported.

User control is provided for setting the HTML styling of the "faces". The defaults are as follows, and may be changed in the preamble after fixme is loaded:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}
```

for HTML output:

```
1 \LWR@ProvidesPackagePass{fixme}[2017/03/05]
```

Restore lwarp's version of `\@wrindex`, ignoring the fixme package's `target` option:

```
2 \let\@wrindex\LWR@wrindex
```

Float-related macros required by lwarp:

```
3 \newcommand{\ext@fixme}{lox}
4
5 \renewcommand{\l@fixme}[2]{\hypertocfloat{1}{fixme}{lox}{#1}{#2}}
```

Other modifications:

```
6 \def\FXFaceInlineHTMLStyle{font-weight:bold}
```

```
\renewcommand*\FXLayoutInline[3]{ %
\InlineClass[\FXFaceInlineHTMLStyle]{fixmeinline}%
    {\@fxtextstd{#1}{#2}{#3}}%
}

\def\FXFaceEnvHTMLStyle{font-weight:bold}

\renewcommand*\FXEnvLayoutPlainBegin[2]{%
\BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}
\ignorespaces#2 \fxnotename{#1}: \ignorespaces}

\renewcommand*\FXEnvLayoutPlainEnd[2]{\endBlockClass}

\renewcommand*\FXEnvLayoutSignatureBegin[2]{%
\BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}
\fxnotename{#1}: \ignorespaces}

\renewcommand*\FXEnvLayoutSignatureEnd[2]{\@fxsignature{#2}\endBlockClass}

\def\FXFaceSignatureHTMLStyle{font-style:italic}

\DeclareRobustCommand*\@fxsignature[1]{%
\ifthenelse{\equal{#1}{}}%
    {}%
    { -- {\InlineClass[\FXFaceSignatureHTMLStyle]{fixmesignature}{#1}}}%
}


\def\FXFaceTargetHTMLStyle{font-style:italic}

\renewcommand\FXTargetLayoutPlain[2]{%
    \InlineClass[\FXFaceTargetHTMLStyle]{fixmetarget}{#2}%
}
```

File 123 **lwarp-fixmetodonotes.sty**

§ 220 Package

fixmetodonotes

(*Emulates or patches code by* Gioele Barabucci.)

Pkg fixmetodonotes fixmetodonotes is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{fixmetodonotes}[2013/04/28]

\renewcommand{\NOTES@addtolist}[2]{%
    \refstepcounter{NOTES@note}%
%   \phantomsection% REMOVED
    \addcontentsline{notes}{NOTES@note}{%
        \protect\numberline{\theNOTES@note}{{#1}: {#2}}%
    }%
}

```

```
\renewcommand{\NOTES@marker}[2]{\fbox{%
    \textcolor{#2}{% WAS \color
        \textbf{#1}}%
    }}

\renewcommand{\NOTES@colorline}[2]{%
  \bgroup%
    \ULon{\LWR@backgroundcolor{#1}{#2}}%
}
```

File 124 **lwarp-flafter.sty**

§ 221 Package

flafter

Pkg flafter flafter is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{flafter}[2018/01/08]
\providecommand\fl@trace[1]{}
```

File 125 **lwarp-flippdf.sty**

§ 222 Package

flippdf

Pkg flippdf flippdf is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{flippdf}[2006/06/30]

\newcommand\FlipPDF{}
\newcommand\UnFlipPDF{}
```

File 126 **lwarp-float.sty**

§ 223 Package

float

(*Emulates or patches code by* Anselm Lingnau.)

Pkg float float is emulated.

Float styles `boxed` and `ruled` are emulated by CSS and a float class according to style.

The HTML `<figure>` `class` is set to the float type, so CSS may also be used to format the float and its caption, according to float type. Furthermore, an additional class is set to the float style: `plain`, `plaintop`, `boxed`, or `ruled`, so CSS may be used to format by float style as well. Default formatting by CSS is provided for `ruled` and `boxed` styles.

for HTML output:

```
\LWR@ProvidesPackageDrop{float}[2001/11/08]
```

`\listof` See section 74.2 for the `\listof` command.

`\LWR@floatstyle` The default float style:

```
\newcommand*{\LWR@floatstyle}{plain}
```

`\newfloat` {⟨*1: type*⟩} {⟨*2: placement*⟩} {⟨*3: ext*⟩} [⟨*4: within*⟩]

Emulates the `\newfloat` command from the float package.

"placement" is ignored.

```
\NewDocumentCommand{\newfloat}{m m m o}{%
\IfValueTF{#4}%
{\DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}}%
{\DeclareFloatingEnvironment[fileext=#3]{#1}}%
```

Remember the float style:

```
\csedef{LWR@floatstyle@#1}{\LWR@floatstyle}%
```

newfloat package automatically creates the `\listof` command for new floats, but float does not, so remove `\listof` here in case it is manually created later.

```
\cslet{listof#1s}\relax%
\cslet{listof#1es}\relax%
```

Likesize, newfloat also creates `\l@<type>`, but float does not, so remove it here:

```
\cslet{l@#1}\relax%
}
```

`\floatname` {⟨*type*⟩} {⟨*name*⟩}

Sets the text name of the float, such as "Figure".

```
\NewDocumentCommand{\floatname}{m +m}{%
    \SetupFloatingEnvironment{#1}{name=#2}%
}
```

`\floatplacement` {⟨*type*⟩} {⟨*placement*⟩}

Float placement is ignored.

```
\newcommand*{\floatplacement}[2]{%
    \SetupFloatingEnvironment{#1}{placement=#2}%
}
```

`\floatstyle` {⟨*style*⟩}

Remember the style for future floats:

```
\newcommand{\floatstyle}[1]{%
    \def\LWR@floatstyle{#1}%
}
```

`\restylefloat` * {⟨*type*⟩}

Remember the style for this float:

```
\NewDocumentCommand{\restylefloat}{s m}{%
    \csedef{LWR@floatstyle@#2}{\LWR@floatstyle}%
}
```

File 127 **lwarp-floatflt.sty**

§ 224 Package

floatflt

(*Emulates or patches code by* Mats Dahlgren.)

Pkg `floatflt` Emulated.

for HTML output: Discard all options for lwarp-floatflt:

```
\LWR@ProvidesPackageDrop{floatflt}[1997/07/16]
```

Env `[⟨⟩]` offset {⟨*type*⟩} {⟨*width*⟩} Borrowed from the lwarp version of keyfloat:

```
\NewDocumentEnvironment{KFLTfloatflt@marginfloat}{O{-1.2ex} m m}
{%
\setlength{\LWR@templengthone}{#3}%
\LWR@BlockClassWP{%
    float:right; %
    width:\LWR@printlength{\LWR@templengthone};  % extra space
    margin:10pt%
}{%
    width:\LWR@printlength{\LWR@templengthone}%
}%
{marginblock}%
\captionsetup{type=#2}%
}
{%
\endLWR@BlockClassWP%
}
```

Env `floatingfigure` [⟨*placement*⟩] {⟨*width*⟩}

```
\DeclareDocumentEnvironment{floatingfigure}{o m}
  {\begin{KFLTfloatflt@marginfloat}{figure}{#2}}
  {\end{KFLTfloatflt@marginfloat}}
```

Env `floatingtable` [⟨*placement*⟩]

```
\DeclareDocumentEnvironment{floatingtable}{o}
  {\begin{KFLTfloatflt@marginfloat}{table}{1.5in}}
  {\end{KFLTfloatflt@marginfloat}}
```

File 128 **lwarp-floatpag.sty**

§ 225 Package floatpag

(*Emulates or patches code by* Vytas Statulevičius and Sigitas Tolušis.)

Pkg floatpag Emulated.

for HTML output: Discard all options for lwarp-floatpag:

```
\LWR@ProvidesPackageDrop{floatpag}[2012/05/29]

\newcommand*{\floatpagestyle}[1]{}
\newcommand*{\rotfloatpagestyle}[1]{}
\newcommand*{\thisfloatpagestyle}[1]{}
```

File 129 **lwarp-floatrow.sty**

§ 226 Package floatrow

(*Emulates or patches code by* Olga Lapko.)

Pkg floatrow floatrow is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{floatrow}[2008/08/02]
```

⚠ Misplaced alignment tab character &

Use `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros using `\ttabbox` with a tabular inside. See section 9.10.

⚠ subfig package

When combined with the subfig package, while inside a `subfloatrow` `\ffigbox` and `\ttabbox` must have the caption in the first of the two of the mandatory arguments.

⚠ `\FBwidth`, `\FBheight`

The emulation of floatrow does not support `\FBwidth` or `\FBheight`. These values are pre-set to `.3\linewidth` and `2in`. Possible solutions include:

- Use fixed lengths. lwarp will scale the HTML lengths appropriately.
- Use `warpprint` and `warpHTML` environments to select appropriate values for each case.
- Inside a `warpHTML` environment, manually change `\FBwidth` or `\FBheight` before the `\ffigbox` or `\ttabbox`. Use `\FBwidth` or `\FBheight` normally afterwards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

After everything has loaded, remember whether subcaption was loaded. If not, it is assumed that subfig is used instead:

```
\newbool{LWR@subcaptionloaded}

\AtBeginDocument{
\@ifpackageloaded{subcaption}
{\booltrue{LWR@subcaptionloaded}}
{\boolfalse{LWR@subcaptionloaded}}
}
```

\floatbox [⟨*1 preamble*⟩] {⟨*2 captype*⟩} [⟨*3 width*⟩] [⟨*4 height*⟩] [⟨*5 vert pos*⟩] {⟨*6 caption*⟩} {⟨*7 object*⟩}

Only parameters for captype, width, caption, and object are used.

LWR@insubfloatrow is true if inside a subfloatrow environment.

There are two actions, depending on the use of subcaption or subfig.

```
\NewDocumentCommand{\floatbox}{o m o o o +m +m}{%
\ifbool{LWR@subcaptionloaded}%
{% subcaption
```

For subcaption:

```
    \ifbool{LWR@insubfloatrow}%
    {% subcaption in a subfloatrow
```

subfigure and subtable environments take width as an argument.

```
        \IfValueTF{#3}%
        {\@nameuse{sub#2}{#3}}%
        {\@nameuse{sub#2}{\linewidth}}%
    }% subcaption in a subfloatrow
    {% subcaption not in subfloatrow
```

figure and table environments do not take a width argument.

```
        \@nameuse{#2}%
    }% subcaption not in subfloatrow
    #6

    #7
```

End the environments:

```
    \ifbool{LWR@insubfloatrow}%
    {\@nameuse{endsub#2}}%
    {\@nameuse{end#2}}%
}% subcaption
{% assume subfig
```

For subfig:

```
\ifbool{LWR@insubfloatrow}%
{% subfig in a subfloatrow
```

\subfloat is a macro, not an environment.

Package subfig's \subfloat command takes an optional argument which is the caption, but \floatbox argument #6 contains commands to create the caption and label,

not the caption itself. Thus, \caption is temporarily disabled to return its own argument without braces.

```
    \begingroup
    \let\caption\@firstofone
    \subfloat[#6]{#7}
    \endgroup
}% subfig in a subfloatrow
{% subfig package, but not a subfig
```

figure and table are environments:

```
\@nameuse{#2}
#6

#7
\@nameuse{end#2}
}% subfig package, but not a subfig
}% assume subfig
}
```

Not used:

```
\newcommand*{\nocapbeside}{}
\newcommand*{\capbeside}{}
\newcommand*{\captop}{}
\newlength{\FBwidth}
\setlength{\FBwidth}{.3\linewidth}
\newlength{\FBheight}
\setlength{\FBheight}{2in}
\newcommand*{\useFCwidth}{}
\newcommand{\floatsetup}[2][]{}
\newcommand{\thisfloatsetup}[1]{}
\newcommand{\clearfloatsetup}[1]{}
\newcommand*{\killfloatstyle}{}
```

\newfloatcommand {⟨*1 command*⟩} {⟨*2 captype*⟩} [⟨*3 preamble*⟩] [⟨*4 default width*⟩]

Preamble and default width are ignored.

```
\NewDocumentCommand{\newfloatcommand}{m m o o}{%
\@namedef{#1}{
\floatbox{#2}
}
}
```

\renewfloatcommand {⟨*1 command*⟩} {⟨*2 captype*⟩} [⟨*3 preamble*⟩] [⟨*4 default width*⟩]

Preamble and default width are ignored.

```
\NewDocumentCommand{\renewfloatcommand}{m m o o}{%
\@namedef{#1}{%
\floatbox{#2}
}
}
```

\ffigbox [⟨*width*⟩] [⟨*height*⟩] [⟨*vposn*⟩] {⟨*caption commands*⟩} {⟨*contents*⟩}

```
\newfloatcommand{ffigbox}{figure}[\nocapbeside][]
```

`\ttabbox` [⟨*width*⟩] [⟨*height*⟩] [⟨*vposn*⟩] {⟨*caption commands*⟩} {⟨*contents*⟩}

```
\newfloatcommand{ttabbox}{table}[\captop][\FBwidth]
```

`\fcapside` [⟨*width*⟩] [⟨*height*⟩] [⟨*vposn*⟩] {⟨*caption commands*⟩} {⟨*contents*⟩}

```
\newfloatcommand{fcapside}{figure}[\capbeside][]
```

Env `floatrow` [⟨*numfloats*⟩]

The row of floats is placed into a `<div>` of class `floatrow`.

```
\newenvironment*{floatrow}[1][2]
{
\LWR@forcenewpage
\BlockClass{floatrow}
```

While inside the floatrow, divide the `\linewidth` by the number of floats.

```
\booltrue{LWR@infloatrow}
\setlength{\linewidth}{6in/#1}
}
{
\boolfalse{LWR@infloatrow}
\endBlockClass
}
```

Keys for `\DeclareNewFloatType`:

```
\newcommand*{\LWR@frowkeyplacement}{}
\newcommand*{\LWR@frowkeyname}{}
\newcommand*{\LWR@frowkeyfileext}{}
\newcommand*{\LWR@frowkeywithin}{}
\newcommand*{\LWR@frowkeycapstyle}{}

\define@key{frowkeys}{placement}{}%
\define@key{frowkeys}{name}{\renewcommand{\LWR@frowkeyname}{#1}}%
\define@key{frowkeys}{fileext}{\renewcommand{\LWR@frowkeyfileext}{#1}}%
\define@key{frowkeys}{within}{\renewcommand{\LWR@frowkeywithin}{#1}}%
\define@key{frowkeys}{relatedcapstyle}{}%
```

`\DeclareNewFloatType` {⟨*type*⟩} {⟨*options*⟩}

Use `\listof{type}{Title}` to print a list of the floats.

```
\newcommand*{\DeclareNewFloatType}[2]{%
```

Reset key values:

```
\renewcommand*{\LWR@frowkeyplacement}{}%
\renewcommand*{\LWR@frowkeyname}{}%
\renewcommand*{\LWR@frowkeyfileext}{}%
\renewcommand*{\LWR@frowkeywithin}{}%
\renewcommand*{\LWR@frowkeycapstyle}{}%
```

Read new key values:

```
\LWR@traceinfo{about to setkeys frowkeys}%
\setkeys{frowkeys}{#2}%
\LWR@traceinfo{finished setkeys frowkeys}%
```

Create a new float with optional [within]:

```
\ifthenelse{\equal{\LWR@frowkeywithin}{}}%
{%
    \LWR@traceinfo{about to newfloat #1 \LWR@frowkeyplacement\ %
        \LWR@frowkeyfileext}%
    \newfloat{#1}{\LWR@frowkeyplacement}{\LWR@frowkeyfileext}%
}%
{%
    \LWR@traceinfo{about to newfloat #1\ \LWR@frowkeyplacement\ %
        \LWR@frowkeyfileext\ \LWR@frowkeywithin}%
    \newfloat{#1}{\LWR@frowkeyplacement}%
    {\LWR@frowkeyfileext}[\LWR@frowkeywithin]%
    \LWR@traceinfo{finished newfloat #1}%
}%
```

Rename the float if a name was given:

```
\ifthenelse{\equal{\LWR@frowkeyname}{}}%
    {}%
    {\floatname{#1}{\LWR@frowkeyname}}%
}
```

Not used:

```
\newcommand{\buildFBBOX}[2]{}
\newcommand*{\CenterFloatBoxes}{}
\newcommand*{\TopFloatBoxes}{}
\newcommand*{\BottomFloatBoxes}{}
\newcommand*{\PlainFloatBoxes}{}

\newcommand{\capsubrowsettings}{}

\NewDocumentCommand{\RawFloats}{o o}{}
```

`\RawCaption` {⟨*text*⟩}

To be used inside a minipage or parbox.

```
\newcommand{\RawCaption}[1]{#1}
```

`\floatfoot` {⟨*text*⟩}

Places additional text inside a float, inside a CSS `<div>` of class `floatfoot`.

```
\NewDocumentCommand{\floatfoot}{s +m}{%
\begin{BlockClass}{floatfoot}
#2
\end{BlockClass}
}
```

Used to compute \linewidth.

```
\newbool{LWR@insubfloatrow}
\boolfalse{LWR@insubfloatrow}
```

Env subfloatrow [⟨*num_floats*⟩]

```
\newenvironment*{subfloatrow}[1][2]
{
```

The row of floats is placed into a of class floatrow:

```
\LWR@forcenewpage
\BlockClass{floatrow}
```

While inside the floatrow, LWR@insubfloatrow is set true, which tells \floatbox to use \subfigure or \subtable.

```
\begingroup
\booltrue{LWR@insubfloatrow}
}
{
\endgroup
\endBlockClass
\boolfalse{LWR@insubfloatrow}
}
```

File 130 **lwarp-fltrace.sty**

§ 227 Package

fltrace

Pkg fltrace fltrace is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fltrace}[2018/01/08]
```

```
\def\tracefloats{}
\def\tracefloatsoff{}
\def\tracefloatvals{}
```

File 131 **lwarp-flushend.sty**

§ 228 Package

flushend

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg flushend Emulated.

for HTML output: Discard all options for lwarp-flushend:

```
\LWR@ProvidesPackageDrop{flushend}[2017/03/27]
```

```
\newcommand*{\flushend}{}
\newcommand*{\raggedend}{}
\newcommand*{\flushcolsend}{}
\newcommand*{\raggedcolsend}{}
\newcommand*{\atColsBreak}[1]{}
\newcommand*{\atColsEnd}[1]{}
\newcommand*{\showcolsendrule}{}
```

File 132 **lwarp-fnbreak.sty**

§ 229 Package fnbreak

Pkg fnbreak fnbreak is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnbreak}[2012/01/01]
```

```
\newcommand*{\fnbreakverbose}{}
\newcommand*{\fnbreaknonverbose}{}
\newcommand*{\fnbreaklabel}{}
\newcommand*{\fnbreaknolabel}{}
```

File 133 **lwarp-fncychap.sty**

§ 230 Package fncychap

(*Emulates or patches code by* Ulf A. Lindgren.)

Pkg fncychap fncychap is emulated.

for HTML output: Discard all options for lwarp-fncychap:

```
\LWR@ProvidesPackageDrop{fncychap}[2007/07/30]
```

```
\def\mghrulefill#1{}
\def\ChNameLowerCase{}
\def\ChNameUpperCase{}
\def\ChNameAsIs{}
\def\ChTitleLowerCase{}
\def\ChTitleUpperCase{}
\def\ChTitleAsIs{}
\newcommand{\ChRuleWidth}[1]{}
\newcommand{\ChNameVar}[1]{}
\newcommand{\ChNumVar}[1]{}
\newcommand{\ChTitleVar}[1]{}
\newcommand{\TheAlphaChapter}{}
\newcommand{\DOCH}{}
\newcommand{\DOTI}[1]{}
\newcommand{\DOTIS}[1]{}
\newlength{\mylen}
\newlength{\myhi}
```

```
\newlength{\px}
\newlength{\py}
\newlength{\pyy}
\newlength{\pxx}
\newlength{\RW}
\newcommand{\FmN}[1]{#1}
\newcommand{\FmTi}[1]{#1}
```

File 134 **lwarp-fnlineno.sty**

§ 231 Package fnlineno

Pkg fnlineno fnlineno is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnlineno}[2011/01/07]
```

File 135 **lwarp-fnpara.sty**

§ 232 Package fnpara

Pkg fnpara fnpara is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnpara}
```

File 136 **lwarp-fnpos.sty**

§ 233 Package fnpos

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg fnpos fnpos is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnpos}[1999/07/14]

\newcommand*{\makeFNbottom}{}
\newcommand*{\makeFNmid}{}
\newcommand*{\makeFNbelow}{}
\newcommand*{\makeFNabove}{}
```

File 137 **lwarp-fontawesome.sty**

§ 234 Package fontawesome

(*Emulates or patches code by* Xavier Danaux.)

Pkg fontawesome

fontawesome is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

⚠ *poppler* syntax warning

If using pdfLaTeX, *poppler* may issue a syntax warning regarding parsing a ligature component. XeLaTeX or LuaLaTeX may be used to avoid this warning.

In the following, the general strategy is to intercept `\symbol` and embed it inside a `lateximage`. These changes are done inside a local group.

For pdfLaTeX, the `alt` tag includes the icon (symbol) number. For XeLaTeX and LuaLaTeX, the `alt` tag is generic.

for HTML output:

```
\LWR@ProvidesPackagePass{fontawesome}[2016/05/15]

\LetLtxMacro\LWR@orig@symbol\symbol

\ifxetexorluatex

\newfontfamily{\LWR@orig@FA}{FontAwesome}

\newcommand*{\LWR@fontawesome@xelatex@symbol}[1]{%
\begin{lateximage}*[(icon)][fontawesomexetex#1]%
\begingroup%
\LWR@orig@FA%
\LWR@orig@symbol{#1}%
\endgroup%
\end{lateximage}%
}

\RenewDocumentCommand{\FA}{}{%
    \LetLtxMacro\symbol\LWR@fontawesome@xelatex@symbol%
}

\else

\newcommand*{\LWR@fontawesome@symbolone}[1]{%
\begin{lateximage}*[(icon #1)][fontawesomeone#1]%
\begingroup%
\fontencoding{U}\fontfamily{fontawesomeone}\selectfont%
\LWR@orig@symbol{#1}%
\endgroup%
\end{lateximage}%
}

\newcommand*{\LWR@fontawesome@symboltwo}[1]{%
\begin{lateximage}*[(icon #1)][fontawesometwo#1]%
\begingroup%
\fontencoding{U}\fontfamily{fontawesometwo}\selectfont%
\LWR@orig@symbol{#1}%
\endgroup%
\end{lateximage}%
}

\newcommand*{\LWR@fontawesome@symbolthree}[1]{%
```

```
\begin{lateximage}*[(icon #1)][fontawesomethree#1]%
\begingroup%
\fontencoding{U}\fontfamily{fontawesomeonethree}\selectfont%
\LWR@orig@symbol{#1}%
\endgroup%
\end{lateximage}%
}

\renewrobustcmd\FAone{%
    \LetLtxMacro\symbol\LWR@fontawesome@symbolone%
}

\renewrobustcmd\FAtwo{%
    \LetLtxMacro\symbol\LWR@fontawesome@symboltwo%
}

\renewrobustcmd\FAthree{%
    \LetLtxMacro\symbol\LWR@fontawesome@symbolthree%
}
\fi
```

File 138 **lwarp-fontawesome5.sty**

§ 235 Package

fontawesome5

(*Emulates or patches code by* Marcel Krüger.)

Pkg fontawesome5

fontawesome5 is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

The `alt` tag has the name of the icon.

for HTML output:

```
\LWR@ProvidesPackagePass{fontawesome5}[2018/07/27]

\ExplSyntaxOn
\cs_set:Nn\fontawesome_use_icon:nn{
  \cs_if_exist:cTF{c__fontawesome_slot_#2_tl}{
    \begin{lateximage}*[(#2)][#1]
    \exp_last_unbraced:Nv
      \__fontawesome_icon_at:nnnn
      {c__fontawesome_slot_#2_tl}
        {#1}{#2}
    \end{lateximage}
  }{
    \msg_error:nnxx{fontawesome5}{icon-not-found}{#2}{#1}
  }
}
\ExplSyntaxOff
```

File 139 **lwarp-fontenc.sty**

§ 236 Package fontenc

Pkg fontenc If using pdfLaTeX, lwarp used to require fontenc be loaded before lwarp, but now lwarp itself loads `\fontenc` with T1 encoding, which lwarp requires. fontenc is now allowed to be loaded with another encoding after lwarp.

lwarp-fontenc is no longer necessary, but is still provided to overwrite older versions.

for HTML output:

```
\LWR@ProvidesPackagePass{fontenc}[2017/04/05]
```

File 140 **lwarp-footmisc.sty**

§ 237 Package footmisc

(*Emulates or patches code by* Robin Fairbairns.)

Pkg footmisc footmisc is emulated.

lwarp incidentally happens to emulate the `stable` option.

```
\LWR@ProvidesPackageDrop{footmisc}[2011/06/06]
```

Some nullified commands:

```
\newcommand{\footnotelayout}{}
\newcommand{\setfnsymbol}[1]{}
\NewDocumentCommand{\DefineFNsymbols}{s m o m}{}

\newdimen\footnotemargin
\footnotemargin1.8em\relax

\newcommand*\hangfootparskip{0.5\baselineskip}
\newcommand*\hangfootparindent{0em}%

\let\pagefootnoterule\footnoterule
\let\mpfootnoterule\footnoterule
\def\splitfootnoterule{\kern-3\p@ \hrule \kern2.6\p@}

\providecommand*{\multiplefootnotemarker}{3sp}
\providecommand*{\multfootsep}{,}
```

Using cleveref:

```
\providecommand*{\footref}[1]{\labelcref{#1}}
```

The following work as-is:

```
\newcommand\mpfootnotemark{%
  \@ifnextchar[%
    \@xmpfootnotemark%
    {%
      \stepcounter\@mpfn%
      \protected@xdef\@thefnmark{\thempfn}%
      \@footnotemark%
    }%
}
\def\@xmpfootnotemark[#1]{%
  \begingroup%
    \csname c@\@mpfn\endcsname #1\relax%
    \unrestored@protected@xdef\@thefnmark{\thempfn}%
  \endgroup%
  \@footnotemark%
}
```

File 141 **lwarp-footnote.sty**

§ 238 Package

footnote

(*Emulates or patches code by* Mark Wooding.)

Pkg footnote footnote is used with minor patches.

for HTML output:

```
\LWR@ProvidesPackagePass{footnote}[1997/01/28]
```

Removed print-version formatting:

```
\def\fn@startnote{%
%   \@parboxrestore%
  \protected@edef\@currentlabel{\csname p@\@mpfn\endcsname\@thefnmark}%
%   \color@begingroup% *** conflicts with lwarp
}

% \let\fn@endnote\color@endgroup% *** conflicts with lwarp
\def\fn@endnote{%
\LWR@htmltagc{/\LWR@tagregularparagraph}%
\LWR@orignewline%
}
```

Removed print-version formatting:

```
\def\fn@startfntext{%
  \setbox\z@\vbox\bgroup%
    \fn@startnote%
    \fn@prefntext%
    \ignorespaces%
}
```

Removed print-version formatting, added closing paragraph tag:

```
\def\fn@endfntext{%
   \LWR@htmltagc{/\LWR@tagregularparagraph}%
   \LWR@orignewline%
   \fn@postfntext%
 \egroup%
 \begingroup%
   \let\@makefntext\@empty%
   \let\@finalstrut\@gobble%
   \LetLtxMacro\rule\@gobbletwo% *8* also the optional argument?
   \@footnotetext{\unvbox\z@}%
 \endgroup%
}
```

These have been redefined, so re-`\let` them again:

```
\let\endfootnote\fn@endfntext
\let\endfootnotetext\endfootnote
```

File 142 **lwarp-footnotebackref.sty**

§ 239 Package

footnotebackref

Pkg footnotebackref

footnotebackref is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{footnotebackref}[2012/07/01]
```

File 143 **lwarp-footnotehyper.sty**

§ 240 Package

footnotehyper

Pkg footnotehyper

footnotehyper is a hyperref-safe version of footnote. For lwarp, footnotehyper is emulated.

for HTML output:

Discard all options for lwarp-footnotehyper:

```
\RequirePackage{footnote}
\LWR@ProvidesPackageDrop{footnotehyper}[2018/01/23]
```

File 144 **lwarp-footnoterange.sty**

§ 241 Package

footnoterange

(*Emulates or patches code by* H.-Martin Münch.)

Pkg footnoterange

footnoterange is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{footnoterange}[2012/02/17]

\csletcs{footnoterange}{footnoterange*}
\csletcs{endfootnoterange}{endfootnoterange*}
```

File 145 **lwarp-footnpag.sty**

§ 242 Package footnpag

Pkg footnpag footnpag is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{footnpag}
```

File 146 **lwarp-foreign.sty**

§ 243 Package foreign

(*Emulates or patches code by* Philip G. Ratcliffe.)

Pkg foreign foreign is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{foreign}[2012/09/25]

\renewcommand\foreignabbrfont{\emph}
```

File 147 **lwarp-forest.sty**

§ 244 Package forest

(*Emulates or patches code by* Sašo Živanović.)

Pkg forest forest is patched for use by lwarp.

⚠ \Forest* The starred version of the macro \Forest* is not supported. lwarp encases each lateximage in an environment, so the global results of the starred \Forest* are lost.

for HTML output:

```
\LWR@ProvidesPackagePass{forest}[2017/07/14]

\BeforeBeginEnvironment{forest}{\begin{lateximage}[forest]}

\AfterEndEnvironment{forest}{\end{lateximage}}

\RenewDocumentCommand{\Forest}{s D(){} m}{%
  \forest@config{#2}%
  \IfBooleanTF{#1}{%
        \PackageError{lwarp-forest}%
```

```
      {Starred \Forest is not supported}%
    {Lwarp uses an environment for images, but \Forest* cannot work in an environment.}%
      \let\forest@next\forest@env%
   }{\let\forest@next\forest@group@env}%
   \begin{lateximage}[forest]%     lwarp
 \forest@next{#3}%
   \end{lateximage}%               lwarp
}
```

File 148 **lwarp-framed.sty**

§ 245 Package

framed

(*Emulates or patches code by* Donald Arseneau.)

Pkg framed framed is supported and patched by lwarp.

for HTML output: Accept all options for lwarp-framed:

```
\LWR@ProvidesPackagePass{framed}[2011/10/22]
\RequirePackage{xcolor}% for \convertcolorspec

\renewenvironment{framed}{%
\LWR@forcenewpage
\BlockClass{framed}%
}
{\endBlockClass}

\renewenvironment{oframed}{%
\LWR@forcenewpage
\BlockClass{framed}%
}
{\endBlockClass}


\renewenvironment{shaded}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
}
{\endBlockClass}

\renewenvironment{shaded*}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
}
{\endBlockClass}


\renewenvironment{leftbar}{%
\LWR@forcenewpage
```

```
    \BlockClass{framedleftbar}
  \def\FrameCommand{}%
  \MakeFramed {}
}%
 {\endMakeFramed\endBlockClass}


\renewenvironment{snugshade}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
}
{\endBlockClass}

\renewenvironment{snugshade*}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
}
{\endBlockClass}

\let\oframed\framed
\let\endoframed\endframed


\RenewEnviron{titled-frame}[1]{%
\CustomFBox{#1}{}{0pt}{0pt}{0pt}{0pt}{\BODY}
}
```

\CustomFBox {⟨*toptitle*⟩} {⟨*bottitle*⟩} {⟨*thicknesstop*⟩} {⟨*bottom*⟩} {⟨*left*⟩} {⟨*right*⟩} {⟨*text contents*⟩}

```
\renewcommand{\CustomFBox}[7]{%
\convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\begin{BlockClass}[border: 3px solid \LWR@origpound\LWR@tempcolor]{framed}%
\ifthenelse{\isempty{#1}}{}{% not empty
    \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
    \textcolor{TFTitleColor}{\textbf{#1}}%
    \end{BlockClass}
}% not empty

#7

\ifthenelse{\isempty{#2}}{}{% not empty
    \convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
    \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
    \textcolor{TFTitleColor}{\textbf{#2}}%
    \end{BlockClass}
}% not empty
\end{BlockClass}
}
```

\TitleBarFrame [⟨*marker*⟩] {⟨*title*⟩} {⟨*contents*⟩}

```
\renewcommand\TitleBarFrame[3][]{
\CustomFBox
    {#2}{}%
    \fboxrule\fboxrule\fboxrule\fboxrule
    {#3}%
}

\renewcommand{\TF@Title}[1]{#1}
```

MakeFramed {⟨*settings*⟩}

```
\let\MakeFramed\relax
\let\endMakeFramed\relax

\NewEnviron{MakeFramed}[1]{%
\FrameCommand{\begin{minipage}{\linewidth}\BODY\end{minipage}}%
}
```

\fb@put@frame {⟨*frame cmd no split*⟩} {⟨*frame cmd split*⟩}

```
\renewcommand*{\fb@put@frame}[2]{%
\relax%
\@tempboxa%
}
```

File 149 **lwarp-ftnright.sty**

§ 246 Package ftnright

Pkg ftnright ftnright is ignored.

for HTML output: Discard all options for lwarp-ftnright:

```
\LWR@ProvidesPackageDrop{ftnright}[2014/10/28]
```

File 150 **lwarp-fullminipage.sty**

§ 247 Package fullminipage

Pkg fullminipage fullminipage is nullified.

for HTML output:

```
\LWR@ProvidesPackageDrop{fullminipage}[2014/07/06]

\newenvironment{fullminipage}[1][]{}{}
```

File 151 **lwarp-fullpage.sty**

§ 248 Package fullpage

Pkg fullpage fullpage is ignored.

for HTML output: Discard all options for lwarp-fullpage:

```
\LWR@ProvidesPackageDrop{fullpage}[1994/06/01]
```

File 152 **lwarp-fullwidth.sty**

§ 249 Package fullwidth

(*Emulates or patches code by* Marco Daniel.)

Pkg fullwidth fullwidth is emulated.

A minipage is used, of no HTML width.

for HTML output:

```
\LWR@ProvidesPackageDrop{fullwidth}[2011/11/18]
\newenvironment*{fullwidth}[1][]{%
\minipagefullwidth%
\minipage{\linewidth}%
}
{%
\endminipage%
}
```

File 153 **lwarp-fwlw.sty**

§ 250 Package fwlw

Pkg fwlw fwlw is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fwlw}
\newbox\FirstWordBox      \global\setbox\FirstWordBox\hbox{}
\newbox\NextWordBox       \global\setbox\NextWordBox\hbox{}
\newbox\LastWordBox       \global\setbox\LastWordBox\hbox{}
\def\ps@fwlwhead{}
\def\ps@NextWordFoot{}
```

File 154 **lwarp-gentombow.sty**

§ 251 Package gentombow

Pkg gentombow gentombow is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{gentombow}[2018/05/17]

\newcommand{\settombowbanner}[1]{}
\newcommand{\settombowbannerfont}[1]{}
\newcommand{\settombowwidth}[1]{}
\newcommand{\settombowbleed}[1]{}
\newcommand{\settombowcolor}[1]{}
```

File 155 **lwarp-geometry.sty**

§ 252 Package geometry

(*Emulates or patches code by* Hideo Umeki.)

Pkg geometry geometry is preloaded by lwarp, but must be nullified as seen by the user's source code.

for HTML output: Discard all options for lwarp-geometry:

```
\LWR@ProvidesPackageDrop{geometry}[2018/04/16]

\renewcommand*{\geometry}[1]{}
\renewcommand*{\newgeometry}[1]{}
\renewcommand*{\restoregeometry}{}
\renewcommand*{\savegeometry}[1]{}
\renewcommand*{\loadgeometry}[1]{}
```

File 156 **lwarp-gloss.sty**

§ 253 Package gloss

(*Emulates or patches code by* Jose Luis Díiaz, Javier Bezos.)

Pkg gloss gloss is patched for use by lwarp.

To process the HTML glossary:

```
bibtex <projectname>_html.gls
```

for HTML output:

```
\LWR@ProvidesPackagePass{gloss}[2002/07/26]
```

```
\xpatchcmd{\gls@gloss@iii}
    {\thepage}
    {\theLWR@previousautopagelabel}
    {}
    {\LWR@patcherror{gloss}{gls@gloss@iii}}

\def\gls@page@i#1#2{%
  \endgroup
  \global\@namedef{glsp@#1}{\nameref{autopage-#2}}}
```

File 157 **lwarp-glossaries.sty**

§ 254 Package

glossaries

(*Emulates or patches code by* Nicola L.C. Talbot.)

Pkg glossaries

processing glossaries

Opt GlossaryCmd

Default: makeglossaries

Opt [lwarpmk] printglossary

Opt [lwarpmk] htmlglossary

lwarpmk has the commands `lwarpmk printglossary` and `lwarpmk htmlglossary`, which process the glossaries created by the glossaries package using that package's *makeglossaries* program.

The shell command to execute is set by the lwarp option `GlossaryCmd`, which defaults to **`makeglossaries`**. The print or HTML glossary filename is appended to this command.

⚠ *makeglossaries* not found

In some situations it may be required to modify the default command, such as to add the **`perl`** command in front:

```
\usepackage[
   GlossaryCmd={perl makeglossaries},
] {lwarp}
```

xindy language

To set the language to use for processing glossaries with *xindy*:

```
\usepackage[
   GlossaryCmd={makeglossaries -L english},
] {lwarp}
```

Other options for *makeglossaries* may be set as well.

placement and TOC options

The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

Numbered section, on its own HTML page:

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
. . .
\printglossaries
```

Unnumbered section, inline with the current HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\printglossaries
```

Unnumbered section, on its own HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\ForceHTMLPage
\printglossaries
```

⚠ glossary style — The default `style=item` option for glossaries conflicts with lwarp, so the style is forced to `index` instead.

⚠ number list — The page number list in the printed form would become `\namerefs` in HTML, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

print/HTML versions — The print and HTML versions of the glossary differ in their internal page numbers. Separate commands for generating print and HTML glossaries are used, even though the page number is currently ignored.

for HTML output:

```
\PassOptionsToPackage{xindy}{glossaries}

\LWR@ProvidesPackagePass{glossaries}[2018/07/23]

\setupglossaries{nonumberlist}
\setglossarystyle{index}
```

Patched to fix TOC pointing to the previous page:

```
\renewcommand*{\@p@glossarysection}[2]{%
  \glsclearpage
  \phantomsection
  \ifdefempty\@@glossarysecstar
  {%
    \csname\@@glossarysec\endcsname{#2}%
  }%
  {%
```

In the original, the TOC entry was made before the section, thus linking to the phantomsection in the printed version, but for HTML, this caused the link to point to the page before the glossaries, which could be a different HTML file. Here, the TOC entry is made after the section is created:

```
      \csname\@@glossarysec\endcsname*{#2}%
    \@gls@toc{#1}{\@@glossarysec}% Moved after the previous line.
  }%
  \@@glossaryseclabel
}
```

lwarp's sectioning commands cannot handle robust macros when splitting HTML into named filenames. glossaries uses `\translate` in sectioning names, and `\translate` is robust and cannot be expanded. The following pre-expands the translations at this moment, making use of `\translatelet`.

```
\newcommand*{\LWR@comp@glossaryname}{\translate{Glossary}}

\ifdefstrequal{\glossaryname}{\LWR@comp@glossaryname}{
```

```
    \translatelet\LWR@translatetemp{Glossary}
    \edef\glossaryname{\LWR@translatetemp}
}{}

\newcommand*{\LWR@comp@acronymname}{\translate{Acronym}}

\ifdefstrequal{\acronymname}{\LWR@comp@acronymname}{
    \translatelet\LWR@translatetemp{Acronym}
    \edef\acronymname{\LWR@translatetemp}
}{}

\newcommand*{\LWR@comp@glssymbolsgroupname}{\translate{Symbols (glossaries)}}

\ifdefstrequal{\glssymbolsgroupname}{\LWR@comp@glssymbolsgroupname}{
    \translatelet\LWR@translatetemp{Symbols (glossaries)}
    \edef\glssymbolsgroupname{\LWR@translatetemp}
}{}

\newcommand*{\LWR@comp@glsnumbersgroupname}{\translate{Numbers (glossaries)}}

\ifdefstrequal{\glsnumbersgroupname}{\LWR@comp@glsnumbersgroupname}{
    \translatelet\LWR@translatetemp{Numbers (glossaries)}
    \edef\glsnumbersgroupname{\LWR@translatetemp}
}{}
```

File 158 **lwarp-gmeometric.sty**

§ 255 Package gmeometric

Pkg gmeometric gmeometric is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{gmeometric}[2008/11/22]
```

File 159 **lwarp-graphics.sty**

§ 256 Package graphics

(*Emulates or patches code by* D. P. Carlisle.)

Pkg graphics graphics is emulated.

for HTML output:

```
\LWR@ProvidesPackagePass{graphics}[2017/06/25]
```

§ 256.1 Graphics extensions

\DeclareGraphicsExtensions {⟨*list*⟩}

\AtBeginDocument allow SVG files instead of PDF:

```
\AtBeginDocument{
\DeclareGraphicsExtensions{.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}
\DeclareGraphicsRule{.svg}{svg}{.svg}{}
\DeclareGraphicsRule{.SVG}{svg}{.SVG}{}
}
```

Inside a lateximage, allow PDF instead of SVG:

```
\ifpdf
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
}
\else% \ifpdf
        \ifXeTeX
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
}
        \else
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{.eps,.EPS,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
}
        \fi
\fi
```

§ 256.2 Length conversions and graphics options

⚠ whitespace

A scaled image in LaTeX by default takes only as much space on the page as it requires, but HTML browsers use as much space as the original unscaled image would have taken, with the scaled image over- or under-flowing the area.

Used to store the user's selected dimensions and HTML class.

The class defaults to "inlineimage" unless changed by a class=xyx option.

```
\newlength{\LWR@igwidth}
\newlength{\LWR@igheight}
\newcommand*{\LWR@igwidthstyle}{}
\newcommand*{\LWR@igheightstyle}{}
\newcommand*{\LWR@igorigin}{}
\newcommand*{\LWR@igangle}{}
\newcommand*{\LWR@igxscale}{1}
\newcommand*{\LWR@igyscale}{1}
\newcommand*{\LWR@igclass}{inlineimage}
```

```
\newcommand*{\LWR@igalt}{(image)}
```

Set the actions of each of the key/value combinations for \includegraphics. Many are ignored.

If an optional width was given, set an HTML style:

```
\define@key{igraph}{width}{%
\setlength{\LWR@igwidth}{#1}%
\ifthenelse{\lengthtest{\LWR@igwidth > 0pt}}%
{%
```

Default to use the converted fixed length given:

```
    \renewcommand*{\LWR@igwidthstyle}{width:\LWR@printlength{\LWR@igwidth}}%
```

If ex or em dimensions were given, use those instead:

```
    \IfEndWith{#1}{ex}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes ex
    {}% not ex
    \IfEndWith{#1}{em}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes em
    {}% not em
    \IfEndWith{#1}{\%}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes percent
    {}% not percent
    \IfEndWith{#1}{px}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes px
    {}% not px
}{}% end of length > 0pt
}
```

If an optional height was given, set an HTML style:

```
\define@key{igraph}{height}{%
\setlength{\LWR@igheight}{#1}%
\ifthenelse{\lengthtest{\LWR@igheight > 0pt}}%
{%
```

Default to use the converted fixed length given:

```
    \renewcommand*{\LWR@igheightstyle}{%
    height:\LWR@printlength{\LWR@igheight} % extra space
    }%
```

If ex or em dimensions were given, use those instead:

```
    \IfEndWith{#1}{ex}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes ex
    {}% not ex
    \IfEndWith{#1}{em}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes em
    {}% not em
    \IfEndWith{#1}{\%}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes percent
    {}% not percent
    \IfEndWith{#1}{px}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes px
```

```
    {}% not px
}{}% end of length > 0pt
}
```

Handle origin key:

```
\define@key{igraph}{origin}[c]{%
    \renewcommand*{\LWR@igorigin}{#1}%
}
```

Handle angle key:

```
\define@key{igraph}{angle}{\renewcommand*{\LWR@igangle}{#1}}
```

Handle class key:

```
\define@key{igraph}{class}{\renewcommand*{\LWR@igclass}{#1}}
```

Handle alt key:

```
\define@key{igraph}{alt}{\renewcommand*{\LWR@igalt}{#1}}
```

It appears that graphicx does not have separate keys for `xscale` and `yscale`. `scale` adjusts both at the same time.

```
\define@key{igraph}{scale}{%
    \renewcommand*{\LWR@igxscale}{#1}%
    \renewcommand*{\LWR@igyscale}{#1}%
}
```

Numerous ignored keys:

```
\define@key{igraph}{bb}{}
\define@key{igraph}{bbllx}{}
\define@key{igraph}{bblly}{}
\define@key{igraph}{bburx}{}
\define@key{igraph}{bbury}{}
\define@key{igraph}{natwidth}{}
\define@key{igraph}{natheight}{}
\define@key{igraph}{hiresbb}[true]{}
\define@key{igraph}{viewport}{}
\define@key{igraph}{trim}{}
\define@key{igraph}{totalheight}{}
\define@key{igraph}{keepaspectratio}[true]{}
\define@key{igraph}{clip}[true]{}
\define@key{igraph}{draft}[true]{}
\define@key{igraph}{type}{}
\define@key{igraph}{ext}{}
\define@key{igraph}{read}{}
\define@key{igraph}{command}{}
```

New in v1.1a:

```
\define@key{igraph}{quite}{}
```

```
\define@key{igraph}{page}{}
\define@key{igraph}{pagebox}{}
\define@key{igraph}{interpolate}[true]{}
```

New in v1.1b:

```
\define@key{igraph}{decodearray}{}
```

§ 256.3 Printing HTML styles

`\LWR@rotstyle` {⟨*prefix*⟩} {⟨*degrees*⟩}

Prints the rotate style with the given prefix.

`prefix` is `-ms-` or `-webkit-` or nothing, and is used to generate three versions of the `transform:rotate` style.

```
\newcommand*{\LWR@rotstyle}[2]{%
 #1transform:rotate(-#2deg);
}
```

`\LWR@scalestyle` {⟨*prefix*⟩} {⟨*xscale*⟩} {⟨*yscale*⟩}

Prints the scale style with the given prefix.

`prefix` is `-ms-` or `-webkit-` or nothing, and is used to generate three versions of the `transform:scale` style.

```
\newcommand*{\LWR@scalestyle}[3]{%
 #1transform:scale(#2,#3);
}
```

§ 256.4 `\includegraphics`

Bool `LWR@infloatrow` Used to compute `\linewidth`.

```
\newbool{LWR@infloatrow}
\boolfalse{LWR@infloatrow}
```

`\LWR@opacity` For HTML, used only for `\includegraphics`.

`\LWR@opacity` may be set by the transparent package.

```
\def\LWR@opacity{1}
```

`\LWR@imagesizebox` Used to determine the actual image size if needed.

```
\newsavebox{\LWR@imagesizebox}
```

`\LWR@HTML@Gin@setfile` {⟨*w*⟩} {⟨*h*⟩} {⟨*filename*⟩} Sets the parsed filename for HTML output.

```
\newcommand*{\LWR@HTML@Gin@setfile}[3]{%
    \xdef\LWR@parsedfilename{#3}%
}
```

Key [Gin] `class` CSS class for the image.

Define the new class key for the print-mode version of `\includegraphics`, which is enabled inside a `lateximage`.

```
\AtBeginDocument{
\define@key{Gin}{class}{}
\define@key{Gin}{alt}{}
}
```

`\LWR@replaceEPSSVG` Usually, references to EPS files become SVG files, but if the epstopdf package is being used, it automatically converts EPS to PDF, and the following must NOT be done.

```
\AtBeginDocument{
\@ifpackageloaded{epstopdf}
{
    \newcommand*{\LWR@replaceEPSSVG}{}
}{%
    \newcommand*{\LWR@replaceEPSSVG}{%
        \StrSubstitute{\LWR@tempone}{.eps}{.svg}[\LWR@tempone]%
        \StrSubstitute{\LWR@tempone}{.EPS}{.SVG}[\LWR@tempone]%
    }
}%
}
```

`\LWR@includegraphicsb` * [⟨*2: options*⟩] [⟨*3: options*⟩] {⟨*4: filename*⟩}

graphics syntax is `\includegraphics` * [⟨*llx,lly*⟩] [⟨*urx,ury*⟩] {⟨*file*⟩}

graphicx syntax is `\includegraphics` [⟨*key values*⟩] {⟨*file*⟩}

If `#3` is empty, only one optional argument was given, thus graphicx syntax.

If using `\epsfig` or `\psfig` from the epsfig package, `#4` will be `\LWR@epsfig@filename`, which will have been set by the `file` or `figure` keys. Therefore, `#4` must not be used until after the keys have been processed.

```
\NewDocumentCommand{\LWR@includegraphicsb}{s o o m}
{%
```

Start the image tag on a new line, allow PDF output word wrap:

```
\LWR@origtilde \LWR@orignewline%
```

Temporarily compute `\linewidth`, `\textwidth`, `\textheight` arguments with a 6x9 inch size until the next `\endgroup`.

```
\begingroup%
```

```
\ifthenelse{\cnttest{\value{LWR@minipagedepth}}{=}{0}}%
{%
    \ifbool{LWR@infloatrow}%
    {}
    {% not in a minipage or a floatrow:
        \setlength{\linewidth}{6in}%
        \setlength{\textwidth}{6in}%
        \setlength{\textheight}{9in}%
    }%
}{}%
```

For correct em sizing during the width and height conversions:

```
\large%
```

Reset some defaults, possibly will be changed below if options were given:

```
\setlength{\LWR@igwidth}{0pt}%
\setlength{\LWR@igheight}{0pt}%
\renewcommand*{\LWR@igwidthstyle}{}%
\renewcommand*{\LWR@igheightstyle}{}%
\renewcommand*{\LWR@igorigin}{}%
\renewcommand*{\LWR@igangle}{}%
\renewcommand*{\LWR@igxscale}{1}%
\renewcommand*{\LWR@igyscale}{1}%
\renewcommand*{\LWR@igclass}{inlineimage}%


\renewcommand*{\LWR@igalt}{(image)}%
```

If `#3` is empty, only one optional argument was given, thus graphicx syntax:

```
\IfValueF{#3}{%
    \IfValueTF{#2}%
        {\setkeys{igraph}{#2}}%
        {\setkeys{igraph}{}}%
}%
```

Fully expand and detokenize the filename, changing the file extension to `.svg` if necessary.

```
\begingroup%
\LetLtxMacro\Gin@setfile\LWR@HTML@Gin@setfile%
\edef\LWR@tempone{#4}%
\StrSubstitute{\LWR@tempone}{.pdf}{.svg}[\LWR@tempone]%
\StrSubstitute{\LWR@tempone}{.PDF}{.SVG}[\LWR@tempone]%
\LWR@replaceEPSSVG%
\xdef\LWR@parsedfilename{\LWR@tempone}%
\Ginclude@graphics{\detokenize\expandafter{\LWR@tempone}}%
\endgroup%
\filename@parse{\LWR@parsedfilename}%
\LWR@traceinfo{LWR@parsedfilename is \LWR@parsedfilename}%
% \LWR@sanitize{\LWR@parsedfilename}%
```

If formatting for a word processor, find and set the actual image size, without rotation, using PDF instead of SVG to find the original bounding box:

```
\ifbool{FormatWP}{%
   \begingroup%
   \LWR@restoreorigformatting%
   \ifpdf%
   \appto\LWR@restoreorigformatting{%
  \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
   }%
   \else% \ifpdf
           \ifXeTeX%
   \appto\LWR@restoreorigformatting{%
  \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
   }%
           \else%
   \appto\LWR@restoreorigformatting{%
  \DeclareGraphicsExtensions{.eps,.EPS,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
   }%
           \fi%
   \fi% \ifpdf
   \define@key{Gin}{angle}{}%
   \IfBooleanTF{#1}%
   {% starred
       \IfValueTF{#3}%
       {%
       \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics*[#2][#3]{#4}}%
       }%
       {%
           \IfValueTF{#2}%
           {%
          \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics*[#2]{#4}}%
           }{%
              \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics*{#4}}%
           }%
       }%
   }% starred
   {% not starred
       \IfValueTF{#3}%
       {%
       \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics[#2][#3]{#4}}%
       }%
       {%
           \IfValueTF{#2}%
           {%
           \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics[#2]{#4}}%
           }{%
               \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics{#4}}%
           }%
       }%
   }% not starred
   \endgroup%
   \settowidth{\LWR@igwidth}{\usebox{\LWR@imagesizebox}}%
  \global\renewcommand*{\LWR@igwidthstyle}{width:\LWR@printlength{\LWR@igwidth}}%
   \settoheight{\LWR@igheight}{\usebox{\LWR@imagesizebox}}%
```

```
   \global\renewcommand*{\LWR@igheightstyle}{height:\LWR@printlength{\LWR@igheight}}%
}{}% FormatWP
```

Create the HTML reference with the graphicspath, filename, extension, alt tag, style, and class.

The \LWR@origtilde adds space between tags in case this is being done inside a \savebox where \newline has no effect.

```
\LWR@traceinfo{LWR@includegraphicsb: about to create href}%
\href{\LWR@parsedfilename}%
{% start of href
\LWR@traceinfo{LWR@includegraphicsb: about to LWR@htmltag}%
\LWR@htmltag{% start of image tags
img\LWR@indentHTML%
src="%

\detokenize\expandafter{\LWR@parsedfilename}%

"\LWR@indentHTML%
```

Only include a style tag if a width, height, angle, or scale was given:

```
\ifthenelse{
    \NOT\equal{\LWR@igwidthstyle}{} \OR
    \NOT\equal{\LWR@igheightstyle}{} \OR
    \NOT\equal{\LWR@igorigin}{} \OR
    \NOT\equal{\LWR@igangle}{} \OR
    \NOT\equal{\LWR@igxscale}{1} \OR
    \NOT\equal{\LWR@igyscale}{1}
}%
{%
    style="\LWR@indentHTML
    \ifthenelse{\NOT\equal{\LWR@igwidthstyle}{}}%
        {\LWR@igwidthstyle;\LWR@indentHTML}{}%
    \ifthenelse{\NOT\equal{\LWR@igheightstyle}{}}%
        {\LWR@igheightstyle;\LWR@indentHTML}{}%
    \ifthenelse{\NOT\equal{\LWR@igorigin}{}}%
        {%
            transform-origin: \LWR@originnames{\LWR@igorigin};\LWR@indentHTML%
        }{}%
    \ifthenelse{\NOT\equal{\LWR@igangle}{}}%
    {%
        \LWR@rotstyle{-ms-}{\LWR@igangle}\LWR@indentHTML
        \LWR@rotstyle{-webkit-}{\LWR@igangle}\LWR@indentHTML
        \LWR@rotstyle{}{\LWR@igangle }\LWR@indentHTML
    }{}%
    \ifthenelse{%
        \NOT\equal{\LWR@igxscale}{1}\OR%
        \NOT\equal{\LWR@igyscale}{1}%
    }%
    {%
        \LWR@scalestyle{-ms-}{\LWR@igxscale}{\LWR@igyscale}\LWR@indentHTML
        \LWR@scalestyle{-webkit-}{\LWR@igxscale}{\LWR@igyscale}\LWR@indentHTML
```

```
        \LWR@scalestyle{}{\LWR@igxscale}{\LWR@igyscale}\LWR@indentHTML
    }{}%
    %
    \ifthenelse{\NOT\equal{\LWR@opacity}{1}}%
        {opacity:\LWR@opacity;\LWR@indentHTML}{}%
    %
    "\LWR@indentHTML%
}{}%
```

Set the class and alt tag:

```
class="\LWR@igclass"\LWR@indentHTML%
alt="\LWR@igalt" \LWR@orignewline%
}% end of image tags
}% end of href
```

Return to original page size and font size:

```
\endgroup
\LWR@traceinfo{LWR@includegraphicsb done}%
}
```

`\includegraphics` `[`⟨*key=val*⟩`]` `{`⟨*filename*⟩`}`

Handles width and height, converted to fixed width and heights.

The user should always use no file suffix in the document source.

```
\AtBeginDocument{

\LWR@traceinfo{Patching includegraphics.}

\LetLtxMacro\LWR@origincludegraphics\includegraphics

\renewcommand*{\includegraphics}
{%
```

This graphic should trigger an HTML paragraph even if alone, so ensure that are doing paragraph handling:

```
\LWR@traceinfo{includegraphics}%
\LWR@ensuredoingapar%
\LWR@includegraphicsb%
}% includegraphics
}% AtBeginDocument
```

§ 256.5 Boxes

\LWR@rotboxorigin Holds the origin key letters.

```
\newcommand*{\LWR@rotboxorigin}{}
```

\LWR@originname {⟨*letter*⟩}

Given one LaTeX origin key value, translate into an HTML origin word:

```
\newcommand*{\LWR@originname}[1]{%
    \ifthenelse{\equal{#1}{t}}{top}{}%
    \ifthenelse{\equal{#1}{b}}{bottom}{}%
    \ifthenelse{\equal{#1}{c}}{center}{}%
    \ifthenelse{\equal{#1}{l}}{left}{}%
    \ifthenelse{\equal{#1}{r}}{right}{}%
}
```

\LWR@originnames {⟨*letters*⟩}

Given one- or two-letter LaTeX origin key values, translate into HTML origin words:

```
\newcommand*{\LWR@originnames}[1]{%
\StrChar{#1}{1}[\LWR@strresult]%
\LWR@originname{\LWR@strresult}
\StrChar{#1}{2}[\LWR@strresult]%
\LWR@originname{\LWR@strresult}
}
```

Handle the origin key for \rotatebox:

```
\define@key{krotbox}{origin}{%
\renewcommand*{\LWR@rotboxorigin}{#1}%
}
```

These keys are ignored:

```
\define@key{krotbox}{x}{}
\define@key{krotbox}{y}{}
\define@key{krotbox}{units}{}
```

\rotatebox [⟨*keyval list*⟩] {⟨*angle*⟩} {⟨*text*⟩}

```
\AtBeginDocument{
```

The HTML version:

```
\NewDocumentCommand{\LWR@HTML@rotatebox}{O{} m +m}{%
```

Reset the origin to “none-given”:

```
\renewcommand*{\LWR@rotboxorigin}{}
```

Process the optional keys, which may set \LWR@rotateboxorigin:

```
\setkeys{krotbox}{#1}%
```

Select inline-block so that HTML will transform this span:

```
\LWR@htmltagc{%
    span\LWR@indentHTML
    style="\LWR@indentHTML
    display: inline-block;\LWR@indentHTML
```

If an origin was given, translate and print the origin information:

```
    \ifthenelse{\NOT\equal{\LWR@rotboxorigin}{}}%
      {transform-origin: \LWR@originnames{\LWR@rotboxorigin};\LWR@indentHTML}%
        {}%
```

Print the rotation information:

```
    \LWR@rotstyle{-ms-}{#2}\LWR@indentHTML
    \LWR@rotstyle{-webkit-}{#2}\LWR@indentHTML
    \LWR@rotstyle{}{#2}"\LWR@orignewline%
}\LWR@orignewline%
```

Print the text to be rotated:

```
\begin{LWR@nestspan}%
#3%
```

Close the span:

```
\LWR@htmltagc{/span}%
\end{LWR@nestspan}%
}
```

The high-level interface:

```
\LWR@formatted{rotatebox}

}% AtBeginDocument
```

\scalebox {⟨*h-scale*⟩} [⟨*v-scale*⟩] {⟨*text*⟩}

```
\AtBeginDocument{
```

The HTML version:

```
\NewDocumentCommand{\LWR@HTML@scalebox}{m o m}{%
```

Select inline-block so that HTML will transform this span:

```
\LWR@htmltagc{%
```

```
    span\LWR@indentHTML
    style="\LWR@indentHTML
    display: inline-block;\LWR@indentHTML
```

Print the scaling information:

```
    \LWR@scalestyle{-ms-}{#1}{\IfNoValueTF{#2}{#1}{#2}}\LWR@indentHTML
    \LWR@scalestyle{-webkit-}{#1}{\IfNoValueTF{#2}{#1}{#2}}\LWR@indentHTML
    \LWR@scalestyle{}{#1}{\IfNoValueTF{#2}{#1}{#2}}
    "\LWR@orignewline
}\LWR@orignewline%
```

Print the text to be scaled:

```
\begin{LWR@nestspan}%
#3%
```

Close the span:

```
\LWR@htmltagc{/span}%
\end{LWR@nestspan}%
}
```

The high-level interface:

```
\LWR@formatted{scalebox}

}% AtBeginDocument
```

\reflectbox {⟨*text*⟩}

```
\AtBeginDocument{

\newcommand{\LWR@HTML@reflectbox}[1]{%
\scalebox{-1}[1]{#1}%
}% \reflectbox

\LWR@formatted{reflectbox}

}% AtBeginDocument
```

\resizebox {⟨*h-length*⟩} {⟨*v-length*⟩} {⟨*text*⟩}

Simply prints its text argument.

```
\AtBeginDocument{

\NewDocumentCommand{\LWR@HTML@resizebox}{s m m m}{%
#4%
}

\LWR@formatted{resizebox}

}% AtBeginDocument
```

File 160 **lwarp-graphicx.sty**

§ 257 Package graphicx

Pkg graphicx graphicx is emulated.

graphicx loads graphics, which also loads lwarp-graphics, which remembers the original graphics definitions for use inside a `lateximage`, and then patches them `\AtBeginDocument` for HTML output.

lwarp-graphics handles the syntax of either graphics or graphicx.

for HTML output:

```
1 \LWR@ProvidesPackagePass{graphicx}[2017/06/01]
```

File 161 **lwarp-grffile.sty**

§ 258 Package grffile

Pkg grffile

⚠ matching PDF and SVG

grffile is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

lwarp-grffile now exists as a placeholder since grffile used to be emulated by lwarp, and thus older versions of lwarp-grffile may exist and should be overwritten by this newer version.

for HTML output:

```
1 \LWR@ProvidesPackagePass{grffile}[2017/06/30]
```

File 162 **lwarp-grid.sty**

§ 259 Package grid

Pkg grid grid is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{grid}[2009/06/16]
2 \newenvironment*{gridenv}{}{}
```

File 163 **lwarp-grid-system.sty**

§ 260 Package grid-system

(*Emulates or patches code by* Marcus Bitzl.)

Pkg grid-system grid-system is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{grid-system}[2014/02/16]
```

(`\ifdef` is in case the older syntax is removed.)

```
\AtBeginEnvironment{Row}{\setlength{\linewidth}{6in}}

\ifdef{\endrow}{
    \AtBeginEnvironment{row}{\setlength{\linewidth}{6in}}
}{}

\renewcommand{\gridsystem@finishcell}{\hspace{\gridsystem@cellsep}}
```

File 164 **lwarp-gridset.sty**

§ 261 Package gridset

Pkg gridset gridset is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{gridset}

\newcommand*{\gridbase}{}
\newcommand*{\gridinterval}{}
\newcommand*{\savepos}[1]{}
\newcounter{gridcnt}
\newcommand*{\vskipnextgrid}{}
\newcommand*{\thegridinfo}[1]{}
\newcommand*{\theposinfo}[1]{}
\newcommand*{\theypos}[1]{}
```

File 165 **lwarp-hang.sty**

§ 262 Package hang

(*Emulates or patches code by* Andreas Nolda.)

Pkg hang hang is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{hang}[2017/02/18]

\newlength{\hangingindent}
\setlength{\hangingindent}{1em}
\newlength{\hangingleftmargin}
\setlength{\hangingleftmargin}{0em}

\newcommand*{\LWR@findhangingleftmargin}{%
\setlength{\LWR@templengthone}{\hangingleftmargin}%
\addtolength{\LWR@templengthone}{\hangingindent}%
```

```
}

\newenvironment{hangingpar}
{
    \LWR@findhangingleftmargin%
    \BlockClass[%
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
        \LWR@print@mbox{text-indent:-\LWR@printlength{\hangingindent}}%
    ]%
    {hangingpar}%
}
{\endBlockClass}

\newenvironment{hanginglist}
{%
    \renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}%
    \renewcommand*{\LWR@printopenlist}{%
        \LWR@findhangingleftmargin%
        ul style="%
            \LWR@print@mbox{list-style-type:none;} % extra space
            \LWR@print@mbox{%
                margin-left:\LWR@printlength{\LWR@templengthone}%
            } ; % extra space
            \LWR@print@mbox{%
                text-indent:-\LWR@printlength{\hangingindent}%
            }%
        "%
    }%
    \let\item\LWR@itemizeitem%
    \list{}{}%
}
{\endlist}

\newenvironment{compacthang}
{\hanginglist}
{\endhanginglist}

\newlength{\labeledleftmargin}
\setlength{\labeledleftmargin}{0em}

\newenvironment{labeledpar}[2]
{%
    \BlockClass[%
        \LWR@findhangingleftmargin%
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
        \LWR@print@mbox{text-indent:-\LWR@printlength{\hangingindent}}%
    ]{labeledpar}#2%
}
{\endBlockClass}

\newenvironment{labeledlist}[1]
{\hanginglist}
{\endhanginglist}

\newenvironment{compactlabel}[1]
```

```
{\hanginglist}
{\endhanginglist}
```

File 166 **lwarp-hanging.sty**

§ 263 Package

hanging

Pkg hanging hanging is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{hanging}[2009/09/02]

\@ifclassloaded{memoir}{
\let\hangpara\relax
\let\hangparas\relax
\let\endhangparas\relax
\let\hangpunct\relax
\let\endhangpunct\relax
}{}
```

\hangpara {⟨*indent*⟩} {⟨*afternum*⟩}

Use hangparas instead.

```
\newcommand*{\hangpara}[2]{}
```

Env hangparas {⟨*indent*⟩} {⟨*afternum*⟩}

```
\newenvironment*{hangparas}[2]
{%
    \BlockClass[%
        \LWR@print@mbox{margin-left:\LWR@printlength{#1}} ; %
        \LWR@print@mbox{text-indent:-\LWR@printlength{#1}}%
    ]%
    {hangingpar}%
}
{\endBlockClass}
```

Env hangpunct

```
\newenvironment*{hangpunct}
{\BlockClass{hangpunct}}
{\endBlockClass}

\newcommand{\nhpt}{.}
\newcommand{\nhlq}{‘}
\newcommand{\nhrq}{’}
```

File 167 **lwarp-hypcap.sty**

§ 264 Package hypcap

Pkg hypcap hypcap is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{hypcap}[2016/05/16]

\newcommand*{\capstart}{}
\newcommand*{\hypcapspace}{}
\newcommand*{\hypcapredef}[1]{}
\newcommand*{\capstartfalse}{}
\newcommand*{\capstarttrue}{}
```

File 168 **lwarp-hypdestopt.sty**

§ 265 Package hypdestopt

Pkg hypdestopt hypdestopt is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{hypdestopt}[2016/05/21]
```

File 169 **lwarp-hypernat.sty**

§ 266 Package hypernat

Pkg hypernat hypernat is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{hypernat}[2001/07/09]
```

File 170 **lwarp-hyperref.sty**

§ 267 Package hyperref

(*Emulates or patches code by* Sebastian Rahtz, Heiko Oberdiek.)

Pkg hyperref hyperref is emulated.

for HTML output:

```
% \LWR@ProvidesPackageDrop{hyperref}
\typeout{Using the lwarp html version of package ‘hyperref’, discarding options.}
\typeout{    Are not using ProvidesPackage, so that other packages}
\typeout{    do not attempt to patch lwarp’s version of ‘hyperref’.}
```

```
% \ProvidesPackage{lwarp-#1-#2}
\DeclareOption*{}

% \ProcessOptions\relax
\let\ds@\@empty%         from the original \ProcessOptions
\edef\@curroptions{}%    lwarp modification to \ProcessOptions
\@process@ptions\relax%  from the original \ProcessOptions

\newcommand*{\hypersetup}[1]{}
\newcommand*{\hyperbaseurl}[1]{}
```

\hyperimage {⟨*URL*⟩} {⟨*alt text*⟩}

Insert an image with alt text:

```
\NewDocumentCommand{\LWR@hyperimageb}{m +m}{%
\LWR@ensuredoingapar%
\def\LWR@templink{#1}%
\@onelevel@sanitize\LWR@templink%
\LWR@htmltag{img src="\LWR@templink" alt="#2" class="hyperimage"}%
\LWR@ensuredoingapar%
\endgroup%
}

\newrobustcmd*{\hyperimage}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hyperimageb%
}

```

\hyperdef {⟨*1: category*⟩} {⟨*2: name*⟩} {⟨*3: text*⟩}

Creates an HTML anchor to `category.name` with the given text.

```
\NewDocumentCommand{\LWR@hyperdefb}{m m +m}{%
\LWR@ensuredoingapar%
\LWR@sublabel{#1.#2}%
#3%
\endgroup%
}

\newcommand*{\hyperdef}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hyperdefb%
}
```

```
48
```

`\LWR@hyperrefb` {⟨*1: URL*⟩} {⟨*2: category*⟩} {⟨*3: name*⟩} {⟨*4: text*⟩}

Creates an HTML link to `URL#category.name` with the given text.

```
49 \newcommand{\LWR@hyperreffinish}[1]{%
50 \begingroup%
51 \RenewDocumentCommand{\ref}{}{\LWR@ref@ignorestar}%
52 #1%
53 \endgroup%
54 \LWR@htmltag{/a}%
55 }
56
57 \newcommand*{\LWR@hyperrefbb}[3]{%
58 \LWR@htmltag{%
59     a href="%
60         \detokenize\expandafter{#1}\LWR@hashmark%
61         \detokenize\expandafter{#2}.\detokenize\expandafter{#3}%
62     "%
63 }%
64 \endgroup%
65 \LWR@hyperreffinish%
66 }
67
68 \newrobustcmd*{\LWR@hyperrefb}{%
69 \begingroup%
70 \catcode`\#=12%
71 \catcode`\%=12%
72 \catcode`\&=12%
73 \catcode`\~=12%
74 \catcode`\_=12%
75 \LWR@hyperrefbb%
76 }
```

`\LWR@hyperrefc` [⟨*label*⟩] {⟨*text*⟩}

Creates text as an HTML link to the LaTeX label.

```
77
78 \NewDocumentCommand{\LWR@hyperrefcb}{O{label}}{%
79 \LWR@startref{#1}%
80 \endgroup%
81 \LWR@hyperreffinish%
82 }
83
84 \newcommand*{\LWR@hyperrefc}{%
85 \begingroup%
86 \catcode`\#=12%
87 \catcode`\%=12%
88 \catcode`\&=12%
89 \catcode`\~=12%
90 \catcode`\_=12%
91 \LWR@hyperrefcb%
92 }
```

\hyperref {⟨*1: URL*⟩} {⟨*2: category*⟩} {⟨*3: name*⟩} {⟨*4: text*⟩} — or — [⟨*1: label*⟩] {⟨*2: text*⟩}

```
\DeclareRobustCommand*{\hyperref}{%
\LWR@ensuredoingapar%
\@ifnextchar[\LWR@hyperrefc\LWR@hyperrefb%
}
```

\hypertarget {⟨*name*⟩} {⟨*text*⟩}

Creates an anchor to name with the given text.

```
\NewDocumentCommand{\LWR@hypertargetb}{m +m}{%
\label{LWR-ht-#1}%
#2%
\endgroup%
}

\newcommand*{\hypertarget}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hypertargetb%
}
```

\hyperlink {⟨*name*⟩} {⟨*text*⟩}

Creates a link to the anchor created by hypertarget, with the given link text.

Declared because also defined by memoir.

```
\DeclareDocumentCommand{\LWR@hyperlinkb}{m}{%
\LWR@hyperrefcb[LWR-ht-#1]%
}

\DeclareDocumentCommand{\hyperlink}{}{%
\LWR@ensuredoingapar%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hyperlinkb%
}
```

\autoref * {⟨*label*⟩}

For HTML, \cleveref is used instead.

```
\NewDocumentCommand{\autoref}{s m}{%
    \IfBooleanTF{#1}{\ref{#2}}{\cref{#2}}%
}
```

\autopageref {⟨*label*⟩}

For HTML, \cleveref is used instead.

```
\NewDocumentCommand{\autopageref}{s m}{%
    \IfBooleanTF{#1}{\cpageref{#2}}{\cref{#2}}%
}
```

\pdfstringdef {⟨*macroname*⟩} {⟨*TEXstring*⟩}

```
\newcommand{\pdfstringdef}[2]{}
```

\pdfbookmark [⟨*level*⟩] {⟨*text*⟩} {⟨*name*⟩}

```
\newcommand{\pdfbookmark}[3][]{}
```

\currentpdfbookmark {⟨*text*⟩} {⟨*name*⟩}

```
\newcommand{\currentpdfbookmark}[2]{}
```

\subpdfbookmark {⟨*text*⟩} {⟨*name*⟩}

```
\newcommand{\subpdfbookmark}[2]{}
```

\belowpdfbookmark {⟨*text*⟩} {⟨*name*⟩}

```
\newcommand{\belowpdfbookmark}[2]{}
```

\texorpdfstring {⟨*TEXstring*⟩} {⟨*PDFstring*⟩}

```
\newcommand{\texorpdfstring}[2]{#1}
```

\hypercalcbp {⟨*dimen*⟩} From hyperref.

```
\def\hypercalcbp#1{%
\strip@pt\dimexpr 0.99626401\dimexpr(#1)\relax\relax
}%
```

\Acrobatmenu {⟨*menuoption*⟩} {⟨*text*⟩}

```
\newcommand{\Acrobatmenu}[2]{}
```

\TextField [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\TextField}[2][]{}
```

\CheckBox [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\CheckBox}[2][]{}
```

\ChoiceMenu [⟨*parameters*⟩] {⟨*label*⟩} {⟨*choices*⟩}

```
\DeclareRobustCommand{\ChoiceMenu}[3][]{}
```

\PushButton [⟨*parameters*⟩] {⟨*label*⟩}

```
145 \DeclareRobustCommand{\PushButton}[2][]{}
```

\Submit [⟨*parameters*⟩] {⟨*label*⟩}

```
146 \DeclareRobustCommand{\Submit}[2][]{}
```

\Reset [⟨*parameters*⟩] {⟨*label*⟩}

```
147 \DeclareRobustCommand{\Reset}[2][]{}
```

\Gauge [⟨*parameters*⟩] {⟨*label*⟩}

```
148 \DeclareRobustCommand{\Gauge}[2][]{}
```

\LayoutTextField {⟨*label*⟩} {⟨*field*⟩}

```
149 \newcommand*{\LayoutTextField}[2]{}
```

\LayoutChoiceField {⟨*label*⟩} {⟨*field*⟩}

```
150 \newcommand*{\LayoutChoiceField}[2]{}
```

\LayoutCheckField {⟨*label*⟩} {⟨*field*⟩}

```
151 \newcommand*{\LayoutCheckField}[2]{}
```

\MakeRadioField {⟨*width*⟩} {⟨*height*⟩}

```
152 \newcommand*{\MakeRadioField}[2]{}
```

\MakeCheckField {⟨*width*⟩} {⟨*height*⟩}

```
153 \newcommand*{\MakeCheckField}[2]{}
```

\MakeTextField {⟨*width*⟩} {⟨*height*⟩}

```
154 \newcommand*{\MakeTextField}[2]{}
```

\MakeChoiceField {⟨*width*⟩} {⟨*height*⟩}

```
155 \newcommand*{\MakeChoiceField}[2]{}
```

\MakeFieldButton {⟨*text*⟩}

```
156 \newcommand{\MakeFieldButton}[1]{}
```

File 171 **lwarp-hyperxmp.sty**

§ 268 Package hyperxmp

Pkg hyperxmp Emulated.

for HTML output: Discard all options for lwarp-hyperxmp:

```
\LWR@ProvidesPackageDrop{hyperxmp}[2018/11/27]
```

File 172 **lwarp-hyphenat.sty**

§ 269 Package hyphenat

Pkg hyphenat hyphenat is emulated during HTML output, while the print-mode version is used inside a lateximage.

for HTML output:

```
\LWR@ProvidesPackagePass{hyphenat}[2009/09/02]

\LetLtxMacro\LWRHYNAT@origtextnhtt\textnhtt
\LetLtxMacro\LWRHYNAT@orignhttfamily\nhttfamily
\LetLtxMacro\LWRHYNAT@orignohyphens\nohyphens
\LetLtxMacro\LWRHYNAT@origbshyp\bshyp
\LetLtxMacro\LWRHYNAT@origfshyp\fshyp
\LetLtxMacro\LWRHYNAT@origdothyp\dothyp
\LetLtxMacro\LWRHYNAT@origcolonhyp\colonhyp
\LetLtxMacro\LWRHYNAT@orighyp\hyp

\LetLtxMacro\textnhtt\texttt
\LetLtxMacro\nhttfamily\ttfamily

\renewcommand{\nohyphens}[1]{#1}
\renewrobustcmd{\bshyp}{%
    \ifmmode\backslash\else\textbackslash\fi%
}
\renewrobustcmd{\fshyp}{/}
\renewrobustcmd{\dothyp}{.}
\renewrobustcmd{\colonhyp}{:}
\renewrobustcmd{\hyp}{-}

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\textnhtt\LWRHYNAT@origtextnhtt%
\LetLtxMacro\nhttfamily\LWRHYNAT@orignhttfamily%
\LetLtxMacro\nohyphens\LWRHYNAT@orignohyphens%
\LetLtxMacro\bshyp\LWRHYNAT@origbshyp%
\LetLtxMacro\fshyp\LWRHYNAT@origfshyp%
\LetLtxMacro\dothyp\LWRHYNAT@origdothyp%
\LetLtxMacro\colonhyp\LWRHYNAT@origcolonhyp%
```

```
\LetLtxMacro\hyp\LWRHYNAT@orighyp%
}
```

File 173 **lwarp-idxlayout.sty**

§ 270 Package idxlayout

(*Emulates or patches code by* Thomas Titz.)

Pkg idxlayout Emulated.

for HTML output: Discard all options for lwarp-idxlayout:

```
\LWR@ProvidesPackageDrop{idxlayout}[2012/03/30]

\newcommand{\LWR@indexprenote}{}

\preto\printindex{

\LWR@orignewpage
\LWR@startpars

\LWR@indexprenote

}

\newcommand{\setindexprenote}[1]{\renewcommand{\LWR@indexprenote}{#1}}
\newcommand*{\noindexprenote}{\renewcommand{\LWR@indexprenote}{}}

\newcommand{\idxlayout}[1]{}
\newcommand*{\indexfont}{}
\newcommand*{\indexjustific}{}
\newcommand*{\indexsubsdelim}{}
\newcommand*{\indexstheadcase}{}
```

File 174 **lwarp-ifoddpage.sty**

§ 271 Package ifoddpage

(*Emulates or patches code by* Martin Scharrer.)

Pkg ifoddpage ifoddpage is emulated.

for HTML output: Discard all options for lwarp-ifoddpage:

```
\LWR@ProvidesPackageDrop{ifoddpage}[2016/04/23]

\newif\ifoddpage

\newif\ifoddpageoroneside
```

```
\DeclareRobustCommand{\checkoddpage}{\oddpagetrue\oddpageoronesidetrue}

\def\oddpage@page{1}

\def\@ifoddpage{%
        \expandafter\@firstoftwo
}

\def\@ifoddpageoroneside{%
        \expandafter\@firstoftwo
}
```

File 175 **lwarp-imakeidx.sty**

§ 272 Package

imakeidx

(*Emulates or patches code by* Enrico Gregorio.)

Pkg imakeidx imakeidx is patched for use by lwarp.

letter headings When using *makeindex*, to match the print and HTML output's display of index letter headings, specify the `lwarp.ist` style:

```
\makeindex[options={-s lwarp.ist}]
```

(For HTML the `lwarp.ist` style is used automatically, which displays letter headings. When using *xindy* the default style also displays letter headings.)

index setup See section 9.6.17 for how to setup *lwarpmk* to process the indexes with imakeidx, both with and without shell escape.

for HTML output:

```
\LWR@ProvidesPackagePass{imakeidx}[2016/10/15]
```

Use the new HTML suffix:

```
\catcode`\_=12%
\define@key{imki}{name}{\def\imki@name{#1_html}}
\catcode`\_=8%
```

\printindex The HTML version of `\printindex`:

```
\catcode`\_=12%

\renewcommand*{\printindex}[1][\imki@jobname]{%
\LWR@orignewpage%
\LWR@startpars%
\ifstrequal{#1}{\imki@jobname}{%
  \@ifundefined{#1@idxfile}{%
        \imki@error{#1}%
    }{%
        \imki@putindex{#1}%
```

```
    }%
}{%
 \@ifundefined{#1_html@idxfile}{\imki@error{#1_html}}{\imki@putindex{#1_html}}%
}%
}

\catcode`\_=8%
```

\@index The HTML version of \index:

```
\catcode`\_=12%

\def\@index[#1]{%
    \ifstrequal{#1}{\imki@jobname}%
    {%
        \@ifundefined{#1@idxfile}%
        {%
            \PackageWarning{imakeidx}{Undefined index file `#1'}%
            \begingroup
            \@sanitize
            \imki@nowrindex%
        }%
        {%
            \edef\@idxfile{#1}%
            \begingroup
            \@sanitize
            \@wrindex\@idxfile%
        }%
    }%
    {%
        \@ifundefined{#1_html@idxfile}%
        {%
            \PackageWarning{imakeidx}{Undefined index file `#1_html'}%
            \begingroup
            \@sanitize
            \imki@nowrindex%
        }%
        {%
            \edef\@idxfile{#1_html}%
            \begingroup
            \@sanitize
            \@wrindex\@idxfile%
        }%
    }%
}

\catcode`\_=8%
```

\item
\subitem
\subsubitem HTML versions of \item, etc.:

```
\appto\theindex{%
    \let\item\LWR@indexitem%
```

```
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}
```

\imki@wrindexentrysplit {⟨*file*⟩} {⟨*entry*⟩} {⟨*page*⟩}

\imki@wrindexentryunique {⟨*file*⟩} {⟨*entry*⟩} {⟨*page*⟩}

While writing index entries, adds an HTML label, and writes the label's index instead of the page number:

```
\renewcommand\imki@wrindexentrysplit[3]{%
\addtocounter{LWR@autoindex}{1}%
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
  \expandafter\protected@write\csname#1@idxfile\endcsname{}%
    {\string\indexentry{#2}{\arabic{LWR@autoindex}}}%
}

\renewcommand\imki@wrindexentryunique[3]{%
\addtocounter{LWR@autoindex}{1}%
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
  \protected@write\@indexfile{}%
    {\string\indexentry[#1]{#2}{\arabic{LWR@autoindex}}}%
}

\def\imki@wrindexsplit#1#2{%
\imki@wrindexentrysplit{#1}{#2}{\thepage}%
\endgroup\imki@showidxentry{#1}{#2}%
  \@esphack%
}

\def\imki@wrindexunique#1#2{%
\imki@wrindexentryunique{#1}{#2}{\thepage}%
\endgroup\imki@showidxentry{#1}{#2}%
  \@esphack%
  }

```

\LWR@imki@setxdydefopts

Sets the xindy HTML options, ignoring the user's settings.

```
\newcommand*{\LWR@imki@setxdydefopts}{%
    \edef\imki@options{ \space %
        -M \space \LWR@xindyStyle\space %
        -L \space \LWR@xindyLanguage\space %
        -C \space \LWR@xindyCodepage\space %
    }%
}
```

\LWR@imki@setdefopts {⟨*user options*⟩}

Sets the HTML options, added to the user's settings, depending on whether makeindex or xindy are used.

For *makeindex*, the user's choice is ignored, and only the lwarp version is used. (Only one style at a time is possible.)

For *xindy*, multiple modules may be specified, and the lwarp version is appended.

```
\newcommand*{\LWR@imki@setdefopts}[1]{%
\ifblank{#1}{%
    \edef\imki@options{\space -s \space \LWR@makeindexStyle \space}%
    \ifdefstring{\imki@progdefault}{xindy}{\LWR@imki@setxdydefopts}{}%
    \ifdefstring{\imki@progdefault}{texindy}{\LWR@imki@setxdydefopts}{}%
    \ifdefstring{\imki@progdefault}{truexindy}{\LWR@imki@setxdydefopts}{}%
}{%
    \edef\imki@options{\space #1 \space}%
}%
}
```

\imki@makeindex Use the new HTML options:

```
\xpatchcmd{\imki@makeindex}
    {\let\imki@options\space}
    {\LWR@imki@setdefopts{}}%
    {}
    {\LWR@patcherror{imakeidx}{makeindex}}
```

Use the new HTML options.

```
\define@key{imki}{options}{\LWR@imki@setdefopts{#1}}
```

\imki@resetdefaults Use the new HTML options:

```
\xpatchcmd{\imki@resetdefaults}
    {\def\imki@options{ }}
    {\LWR@imki@setdefopts{}}
    {}
    {\LWR@patcherror{imakeidx}{resetdefaults}}
```

theindex was already defined \AtBeginDocument by the lwarp core, so it must be redefined here similarly, but patched for imakeidx:

Env theindex

```
\AtBeginDocument{
\renewenvironment*{theindex}{%
    \imki@maybeaddtotoc
     \imki@indexlevel{\indexname}
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}{}
}% AtBeginDocument
```

Update to the new defaults:

```
\imki@resetdefaults
```

Update to the new patches:

`\AtBeginDocument` is because `\@wrindex` is previously defined as `\AtBeginDocument` in the lwarp core.

```
\ifimki@splitindex
  \let\imki@startidx\imki@startidxunique
  \AtBeginDocument{\let\@wrindex\imki@wrindexunique}
  \let\imki@putindex\imki@putindexunique
  \let\imki@wrindexentry\imki@wrindexentryunique
  \let\imki@startidxsplit\@undefined
  \let\imki@wrindexsplit\@undefined
  \let\imki@putindexsplit\@undefined
\else
  \let\imki@startidx\imki@startidxsplit
  \AtBeginDocument{\let\@wrindex\imki@wrindexsplit}
  \let\imki@putindex\imki@putindexsplit
  \let\imki@wrindexentry\imki@wrindexentrysplit
  \let\imki@startidxunique\@undefined
  \let\imki@wrindexunique\@undefined
  \let\imki@putindexunique\@undefined
\fi
```

File 176 **`lwarp-index.sty`**

§ 273 Package

index

(*Emulates or patches code by* David M. Jones.)

Pkg index index is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{index}[2004/01/20]
```

Use `\theLWR@autoindex` instead of `\thepage`. `\@tempswatrue` is used to force an immediate write to the index file instead of waiting until the end of the page.

```
\xpatchcmd{\newindex}
    {\x@newindex[thepage]}
    {%
        \@tempswatrue%
        \x@newindex[theLWR@autoindex]%
    }
    {}
    {\LWR@patcherror{index}{newindex}}

\xpatchcmd{\renewindex}
    {\x@renewindex[thepage]}
    {%
        \@tempswatrue%
        \x@renewindex[theLWR@autoindex]%
    }
    {}
    {\LWR@patcherror{index}{renewindex}}
```

Patched to set a new autoindex:

```
\xpatchcmd{\@wrindex}
    {\begingroup}
    {%
        \addtocounter{LWR@autoindex}{1}%                    lwarp
        \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%    lwarp
        \begingroup%
    }
    {}
    {\LWR@patcherror{index}{@wrindex}}
```

`\AtBeginDocument` lwarp core `\lets` `\@wrindex` to `\LWR@wrindex`. Since the index package has been loaded, `\let` to its version instead:

```
\let\LWR@index@wrindex\@wrindex

\AtBeginDocument{
\let\@wrindex\LWR@index@wrindex
}
```

Modified to add `\index@prologue`:

```
\AtBeginDocument{
\renewenvironment*{theindex}{%
    \LWR@indexsection{\indexname}%
    \ifx\index@prologue\@empty\else
        \index@prologue
        \bigskip
    \fi
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}{}
}% AtBeginDocument
```

Disabled:

```
\def\@showidx#1{}
\let\@texttop\relax
\renewcommand*{\raggedbottom}{}
\renewcommand*{\flushbottom}{}
\renewcommand*{\markboth}[2]{}
\renewcommand*{\markright}[1]{}
```

File 177 **lwarp-intopdf.sty**

§ 274 Package

intopdf

Pkg intopdf intopdf is emulated.

The MIME type and description are ignored for now.

for HTML output:

```
\LWR@ProvidesPackageDrop{intopdf}[2018/03/15]

\NewDocumentCommand{\attachandlink}{m o m m}{%
    \href{#1}{#4}%
}
```

File 178 **lwarp-karnaugh-map.sty**

§ 275 Package

karnaugh-map

(*Emulates or patches code by* Mattias Jacobsson.)

Pkg karnaugh-map karnaugh-map is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{karnaugh-map}[2017/02/20]
```

(It is hard to patch this macro, so the entire thing is redefined here, with the lwarp modificaitions identified in comments.)

```
\RenewDocumentEnvironment{karnaugh-map}{s O{4} O{4} O{1} O{$X_1X_0$} O{$X_3X_2$} O{$X_5X_4$}} {%
  \begingroup
    % store map size {[START]
      \renewcommand{\@karnaughmap@var@mapsizex@}{#2}%
      \renewcommand{\@karnaughmap@var@mapsizey@}{#3}%
      \renewcommand{\@karnaughmap@var@mapsizez@}{#4}%
    % [END]}
    % determinate if markings should be color or black and white
    \IfBooleanTF{#1}{%
      % should be black and white
      \renewcommand{\@karnaughmap@var@bw@}{1}%
    }{%
      % should be color
      \renewcommand{\@karnaughmap@var@bw@}{0}%
    }%
    %
    % find matching matrix template and alignment parameters {[START]
    \newcommand{\@karnaughmap@local@matrixtemplate@}{0}% '0' is considered as missing matrix template
      \newcommand{\@karnaughmap@local@maprealignmentx@}{0}%
      \newcommand{\@karnaughmap@local@maprealignmenty@}{0}%
    \ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=221
        \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
                  \&                  0 \&                   1 \& \phantom{0} \\
             0 \& |(000000)|  \phantom{0} \& |(000001)|  \phantom{0} \&         \\
             1 \& |(000010)|  \phantom{0} \& |(000011)|  \phantom{0} \&         \\
        \phantom{0}  \&                   \&                   \&          \\
        }%
      \fi
    \ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=241
        \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
                 \&                  0 \&                   1 \& \phantom{00} \\
            00 \& |(000000)|  \phantom{0} \& |(000001)|  \phantom{0} \&         \\
            01 \& |(000010)|  \phantom{0} \& |(000011)|  \phantom{0} \&         \\
```

```
            11 \& |(000110)| \phantom{0} \& |(000111)| \phantom{0} \&          \\
            10 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \&          \\
      \phantom{00} \&                  \&                  \&           \\
      }%
    \fi
  \ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=421
      \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
             \&              00 \&              01 \&              11 \&              10 \& \phanto
           0  \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(00001
           1  \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(00011
     \phantom{00} \&                \&                \&                \&                \&
      }%
    \fi
  \ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=441
      \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
             \&              00 \&              01 \&              11 \&              10 \& \phanto
           00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(0000
           01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(0001
           11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(0011
           10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(0010
     \phantom{00} \&                \&                \&                \&                \&
      }%
    \fi
  \ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=442
      \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
             \&              00 \&              01 \&              11 \&              10 \& \phanto
           00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(0000
           01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(0001
           11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(0011
           10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(0010
     \phantom{00} \&                \&                \&                \&                \&
      }%
      \renewcommand{\@karnaughmap@local@maprealignmentx@}{2.5}%
    \fi
  \ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=444
      \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
             \&              00 \&              01 \&              11 \&              10 \& \phanto
           00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(0000
           01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(0001
           11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(0011
           10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(0010
     \phantom{00} \&                \&                \&                \&                \&
           00 \& |(100000)| \phantom{0} \& |(100001)| \phantom{0} \& |(100011)| \phantom{0} \& |(1000
           01 \& |(100100)| \phantom{0} \& |(100101)| \phantom{0} \& |(100111)| \phantom{0} \& |(1001
           11 \& |(101100)| \phantom{0} \& |(101101)| \phantom{0} \& |(101111)| \phantom{0} \& |(1011
           10 \& |(101000)| \phantom{0} \& |(101001)| \phantom{0} \& |(101011)| \phantom{0} \& |(1010
     \phantom{00} \&                \&                \&                \&                \&
      }%
      \renewcommand{\@karnaughmap@local@maprealignmentx@}{2.5}%
      \renewcommand{\@karnaughmap@local@maprealignmenty@}{-2.5}%
    \fi
  % [END]}
 % test if a matrix template is found or not(aka "\@karnaughmap@local@matrixtemplate@" equals to '0')
  \ifdefstring{\@karnaughmap@local@matrixtemplate@}{0}{%  lwarp
%   \ifnum0=\@karnaughmap@local@matrixtemplate@%  original
```

```
90      % print error if no template could be found
91      \PackageError{karnaugh-map}{%
92       Can not find a template fitting your specification (\@karnaughmap@var@mapsizex@\space x \@karnaughma
93      }{%
94       Existing templates have the following dimensions: 2x2x1, 2x4x1, 4x2x1, 4x4x1, 4x4x2, and 4x4x4.
95      }%
96 %    \fi   original
97    }{}%    lwarp
98    \begin{tikzpicture}
99      % grid
100     % for all dimensions
101   \draw[color=black, ultra thin] (0,0) grid (\@karnaughmap@var@mapsizex@,\@karnaughmap@var@mapsizey@);
102     % when there are 2 sub maps
103     \ifnum\@karnaughmap@var@mapsizez@=2
104       \draw[color=black, ultra thin] (5,0) grid (9,4);
105     \fi
106     % when there are 4 sub maps
107     \ifnum\@karnaughmap@var@mapsizez@=4
108       \draw[color=black, ultra thin] (5,0) grid (9,4);
109       \draw[color=black, ultra thin] (0,-5) grid (4,-1);
110       \draw[color=black, ultra thin] (5,-5) grid (9,-1);
111     \fi
112     % labels
113     % for all dimensions
114   \node[above] at (\@karnaughmap@var@mapsizex@*0.5,\@karnaughmap@var@mapsizey@+0.9) {\small{#5}};
115     \node[left] at (-0.9,\@karnaughmap@var@mapsizey@*0.5) {\small{#6}};
116     % when there are 2 sub maps
117     \ifnum\@karnaughmap@var@mapsizez@=2
118       \node[above] at (7,4.9) {\small{#5}};
119       % extra sub maps labels
120       \node[below] at (2,-0.1) {\small{#7$=0$}};
121       \node[below] at (7,-0.1) {\small{#7$=1$}};
122     \fi
123     % when there are 4 sub maps
124     \ifnum\@karnaughmap@var@mapsizez@=4
125       \node[above] at (7,4.9) {\small{#5}};
126       \node[left] at (-0.9,-3) {\small{#6}};
127       % extra sub maps labels
128       \node[below] at (2,-0.1) {\small{#7$=00$}};
129       \node[below] at (7,-0.1) {\small{#7$=01$}};
130       \node[below] at (2,-5.1) {\small{#7$=10$}};
131       \node[below] at (7,-5.1) {\small{#7$=11$}};
132     \fi
133     % data
134     \matrix[
135       matrix of nodes,
136       ampersand replacement=\&,
137       column sep={1cm,between origins},
138       row sep={1cm,between origins},
139   ] at (\@karnaughmap@var@mapsizex@*0.5+\@karnaughmap@local@maprealignmentx@,\@karnaughmap@var@mapsiz
140       \@karnaughmap@local@matrixtemplate@%
141     };
142 }{
143   \end{tikzpicture}
144  \endgroup
```

```
145 }
```

File 179 **lwarp-keyfloat.sty**

§ 276 Package

keyfloat

(*Emulates or patches code by* Brian Dunn.)

Pkg keyfloat keyfloat is supported with minor adjustments.

⚠ keywrap If placing a `\keyfig[H]` inside a `keywrap`, use an absolute width for `\keyfig`, instead of `lw`-proportional widths. (The `[H]` option forces the use of a minipage, which internally adjusts for a virtual 6-inch wide minipage, which then corrupts the `lw` option.)

for HTML output:

```
1 \LWR@ProvidesPackagePass{keyfloat}[2017/05/12]
```

After keyfloat has loaded:

```
2 \AtBeginDocument{


3 \RenewDocumentCommand{\KFLT@onefigureimage}{}
4 {%
5 \LWR@traceinfo{KFLT@onefigureimage}%
6 % \begin{lrbox}{\KFLT@envbox}%
7 \ifthenelse{\NOT\equal{\KFLT@lw}{}}%
8     {%
9         \includegraphics%
10        [scale=\KFLT@s,width=\KFLT@imagewidth]{\KFLT@i}%
11    }%
12    {% not linewidth
13        \ifthenelse{\dimtest{\KFLT@w}{>}{0pt}}%
14        {% width is given
15            \ifthenelse{\dimtest{\KFLT@h}{>}{0pt}}%
16            {% w and h
17                \includegraphics%
18                [scale=\KFLT@s,%
19                width=\KFLT@imagewidth,height=\KFLT@h]{\KFLT@i}%
20            }% w and h
21            {% only w
22                \includegraphics%
23                [scale=\KFLT@s,width=\KFLT@imagewidth]{\KFLT@i}%
24            }% only w
25        }% width is given
26        {% width is not given
27            \ifthenelse{\dimtest{\KFLT@h}{>}{0pt}}%
28            {%
29                \includegraphics%
30                [scale=\KFLT@s,height=\KFLT@h]{\KFLT@i}%
31            }%
32            {%
33                \includegraphics%
34                [scale=\KFLT@s]{\KFLT@i}%
```

```
            }%
        }% width is not given
    }% not linewidth
% \end{lrbox}%
% \unskip%
% \KFLT@findenvboxwidth%
% \begin{turn}{\KFLT@r}%
% \KFLT@frame{\usebox{\KFLT@envbox}}%
% \unskip%
% \end{turn}%
\LWR@traceinfo{KFLT@onefigureimage: done}%
}

\RenewDocumentEnvironment{KFLT@boxinner}{}
{%
\LWR@traceinfo{KFLT@boxinner}%
\LWR@stoppars%
}
{
\LWR@startpars%
\LWR@traceinfo{KFLT@boxinner: done}%
}


\DeclareDocumentEnvironment{KFLT@marginfloat}{O{-1.2ex} m}
{%
\LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}{marginblock}%
\captionsetup{type=#2}%
}
{%
\endLWR@BlockClassWP%
}

\DeclareDocumentEnvironment{marginfigure}{o}
  {\begin{KFLT@marginfloat}{figure}}
  {\end{KFLT@marginfloat}}

\DeclareDocumentEnvironment{margintable}{o}
  {\begin{KFLT@marginfloat}{table}}
  {\end{KFLT@marginfloat}}

\DeclareDocumentEnvironment{keywrap}{m +m}
{%
\LWR@ensuredoingapar%
\setlength{\LWR@templengthone}{#1}%
\begin{LWR@BlockClassWP}{%
    float:right; width:\LWR@printlength{\LWR@templengthone};  % extra space
    margin:10pt%
}%
{%
    width:\LWR@printlength{\LWR@templengthone}%
}%
{marginblock}%
\setlength{\linewidth}{.95\LWR@templengthone}%
#2%
```

```
\end{LWR@BlockClassWP}%
}
{%
}

}% AtBeginDocument
```

File 180 **lwarp-layaureo.sty**

§ 277 Package layaureo

Pkg layaureo layaureo is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{layaureo}[2004/09/16]
```

File 181 **lwarp-layout.sty**

§ 278 Package layout

Pkg layout layout is ignored.

for HTML output: Discard all options for lwarp-layout:

```
\LWR@ProvidesPackageDrop{layout}[2014/10/28]

\NewDocumentCommand{\layout}{s}{}
```

File 182 **lwarp-layouts.sty**

§ 279 Package layouts

Pkg layouts layouts is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{layouts}[2009/09/02]

\newif\ifoddpagelayout
  \oddpagelayouttrue
\newif\iftwocolumnlayout
  \twocolumnlayoutfalse
\newif\ifdrawmarginpars
  \drawmarginparstrue
\newif\ifdrawparameters
  \drawparameterstrue
\newif\iflistaspara
  \listasparatrue
\newif\ifruninhead
```

```
  \runinheadfalse
\newif\ifprintparameters
  \printparameterstrue
\newif\ifdrawdimensions
  \drawdimensionsfalse
\newif\ifprintheadings
  \printheadingstrue
\newcommand{\testdrawdimensions}{}
\newcommand{\testprintparameters}{}
\newcommand{\setlabelfont}[1]{}
\newcommand{\setparametertextfont}[1]{}
\newcommand{\setvaluestextsize}[1]{}
\newcommand{\setlayoutscale}[1]{}
\newcommand{\setuplayouts}{}
\newcommand{\printinunitsof}[1]{}
\newcommand{\prntlen}[1]{}
\newcommand{\trypaperwidth}[1]{}
\newcommand{\trypaperheight}[1]{}
\newcommand{\tryhoffset}[1]{}
\newcommand{\tryvoffset}[1]{}
\newcommand{\trytopmargin}[1]{}
\newcommand{\tryheadheight}[1]{}
\newcommand{\tryheadsep}[1]{}
\newcommand{\trytextheight}[1]{}
\newcommand{\tryfootskip}[1]{}
\newcommand{\tryoddsidemargin}[1]{}
\newcommand{\tryevensidemargin}[1]{}
\newcommand{\trytextwidth}[1]{}
\newcommand{\trymarginparsep}[1]{}
\newcommand{\trymarginparwidth}[1]{}
\newcommand{\trymarginparpush}[1]{}
\newcommand{\trycolumnsep}[1]{}
\newcommand{\trycolumnseprule}[1]{}
\newcommand{\setfootbox}[2]{}
\newcommand{\currentpage}{}
\newcommand{\drawpage}{(draw page)}
\newcommand{\pagediagram}{(page diagram)}
\newcommand{\pagedesign}{(page design)}
\newcommand{\pagevalues}{(page values)}
\newcommand{\trystockwidth}[1]{}
\newcommand{\trystockheight}[1]{}
\newcommand{\trytrimedge}[1]{}
\newcommand{\trytrimtop}[1]{}
\newcommand{\tryuppermargin}[1]{}
\newcommand{\tryspinemargin}[1]{}
\newcommand{\currentstock}{}
\newcommand{\drawstock}{(draw stock)}
\newcommand{\stockdiagram}{(stock diagram)}
\newcommand{\stockdesign}{(stock design)}
\newcommand{\stockvalues}{(stock values)}
\newcommand{\tryitemindent}[1]{}
\newcommand{\trylabelwidth}[1]{}
\newcommand{\trylabelsep}[1]{}
\newcommand{\tryleftmargin}[1]{}
\newcommand{\tryrightmargin}[1]{}
```

```
\newcommand{\trylistparindent}[1]{}
\newcommand{\trytopsep}[1]{}
\newcommand{\tryparskip}[1]{}
\newcommand{\trypartopsep}[1]{}
\newcommand{\tryparsep}[1]{}
\newcommand{\tryitemsep}[1]{}
\newcommand{\currentlist}{}
\newcommand{\drawlist}{(draw list)}
\newcommand{\listdiagram}{(list diagram)}
\newcommand{\listdesign}{(list design)}
\newcommand{\listvalues}{(list values)}
\newcommand{\tryfootins}[1]{}
\newcommand{\tryfootnotesep}[1]{}
\newcommand{\tryfootnotebaseline}[1]{}
\newcommand{\tryfootruleheight}[1]{}
\newcommand{\tryfootrulefrac}[1]{}
\newcommand{\currentfootnote}{}
\newcommand{\drawfootnote}{(draw footnote)}
\newcommand{\footnotediagram}{(footnote diagram)}
\newcommand{\footnotedesign}{(footnote design)}
\newcommand{\footnotevalues}{(footnote values)}
\newcommand{\tryparindent}[1]{}
\newcommand{\tryparlinewidth}[1]{}
\newcommand{\tryparbaselineskip}[1]{}
\newcommand{\currentparagraph}{}
\newcommand{\drawparagraph}{(draw paragraph)}
\newcommand{\paragraphdiagram}{(paragraph diagram)}
\newcommand{\paragraphdesign}{(paragraph design)}
\newcommand{\paragraphvalues}{(paragraph values)}
\newcommand{\trybeforeskip}[1]{}
\newcommand{\tryafterskip}[1]{}
\newcommand{\tryindent}[1]{}
\newcommand{\currentheading}{}
\newcommand{\drawheading}[1]{(draw heading)}
\newcommand{\headingdiagram}[1]{(heading diagram)}
\newcommand{\headingdesign}[1]{(heading design)}
\newcommand{\headingvalues}{(heading values)}
\newcommand{\trytextfloatsep}[1]{}
\newcommand{\tryfloatsep}[1]{}
\newcommand{\tryintextsep}[1]{}
\newcommand{\trytopfigrule}[1]{}
\newcommand{\trybotfigrule}[1]{}
\newcommand{\currentfloat}{}
\newcommand{\drawfloat}{(draw float)}
\newcommand{\floatdiagram}{(float diagram)}
\newcommand{\floatdesign}{(float design)}
\newcommand{\floatvalues}{(float values)}
\newcommand{\trytotalnumber}[1]{}
\newcommand{\trytopnumber}[1]{}
\newcommand{\trybottomnumber}[1]{}
\newcommand{\trytopfraction}[1]{}
\newcommand{\trytextfraction}[1]{}
\newcommand{\trybottomfraction}[1]{}
\newcommand{\currentfloatpage}{}
\newcommand{\drawfloatpage}{(draw floatpage)}
```

```
\newcommand{\floatpagediagram}{(floatpage diagram)}
\newcommand{\floatpagedesign}{(floatpage design)}
\newcommand{\floatpagevalues}{(floatpage values)}
\newcommand{\trytocindent}[1]{}
\newcommand{\trytocnumwidth}[1]{}
\newcommand{\trytoclinewidth}[1]{}
\newcommand{\trytocrmarg}[1]{}
\newcommand{\trytocpnumwidth}[1]{}
\newcommand{\trytocdotsep}[1]{}
\newcommand{\currenttoc}{}
\newcommand{\drawtoc}{(draw toc)}
\newcommand{\tocdiagram}{(toc diagram)}
\newcommand{\tocdesign}{(toc design)}
\newcommand{\tocvalues}{(toc values)}
\newcommand{\drawaspread}[8][0]{(a spread)}
\newcommand{\drawfontframe}[1]{(font frame)}
\newcommand{\drawfontframelabel}[1]{}
```

File 183 **lwarp-leading.sty**

§ 280 Package

leading

Pkg leading leading is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{leading}[2008/12/11]
```

```
\newcommand\leading[1]{}
```

File 184 **lwarp-letterspace.sty**

§ 281 Package

letterspace

(*Emulates or patches code by* R Schlicht.)

Pkg letterspace letterspace is a subset of microtype, which is pre-loaded by lwarp. All user options and macros are ignored and disabled.

for HTML output: Discard all options for lwarp-letterspace:

```
\LWR@ProvidesPackageDrop{letterspace}[2018/01/14]
```

```
\newcommand*\lsstyle{}
\newcommand\textls[2][]{}
\def\textls#1#{}
\newcommand*\lslig[1]{#1}
```

File 185 **lwarp-lettrine.sty**

§ 282 Package

lettrine

(*Emulates or patches code by* Daniel Flipo.)

Pkg lettrine Emulated.

for HTML output: Discard all options for lwarp-lettrine:

```
\LWR@ProvidesPackageDrop{lettrine}[2018-08-28]
```

The initial letter is in a of class `lettrine`, and the following text is in a of class `lettrinetext`. `\lettrine` [⟨*keys*⟩] {⟨*letter*⟩} {⟨*additional text*⟩}

```
\DeclareDocumentCommand{\lettrine}{o m m}{%
\InlineClass{lettrine}{#2}\InlineClass{lettrinetext}{#3} % extra space
}

\newcounter{DefaultLines}
\setcounter{DefaultLines}{2}
\newcounter{DefaultDepth}
\newcommand*{\DefaultOptionsFile}{\relax}
\newcommand*{\DefaultLoversize}{0}
\newcommand*{\DefaultLraise}{0}
\newcommand*{\DefaultLhang}{0}
\newdimen\DefaultFindent
\setlength{\DefaultFindent}{\z@}
\newdimen\DefaultNindent
\setlength{\DefaultNindent}{0.5em}
\newdimen\DefaultSlope
\setlength{\DefaultSlope}{\z@}
\newdimen\DiscardVskip
\setlength{\DiscardVskip}{0.2\p@}
\newif\ifLettrineImage
\newif\ifLettrineOnGrid
\newif\ifLettrineRealHeight

\newcommand*{\LettrineTextFont}{\scshape}
\newcommand*{\LettrineFontHook}{}
\newcommand*{\LettrineFont}[1]{\InlineClass{lettrine}{#1}}
\newcommand*{\LettrineFontEPS}[1]{\includegraphics[height=1.5ex]{#1}}
```

File 186 **lwarp-lineno.sty**

§ 283 Package

lineno

(*Emulates or patches code by* Stephan I. Böttcher.)

Pkg lineno lineno is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{lineno}[2005/11/02]

\newcommand*\resetlinenumber[1][\@ne]{}

\def\linenumbers{%
     \@ifnextchar[{\resetlinenumber}%]
                  {\@ifstar{\resetlinenumber}{}}%
     }

\newcommand*{\nolinenumbers}{}

\@namedef{linenumbers*}{\par\linenumbers*}
\@namedef{runninglinenumbers*}{\par\runninglinenumbers*}

\def\endlinenumbers{\par}
\let\endrunninglinenumbers\endlinenumbers
\let\endpagewiselinenumbers\endlinenumbers
\expandafter\let\csname endlinenumbers*\endcsname\endlinenumbers
\expandafter\let\csname endrunninglinenumbers*\endcsname\endlinenumbers
\let\endnolinenumbers\endlinenumbers

\def\pagewiselinenumbers{\linenumbers\setpagewiselinenumbers}

\def\runninglinenumbers{\setrunninglinenumbers\linenumbers}

\def\setpagewiselinenumbers{}

\def\setrunninglinenumbers{}

\def\linenomath{}%
\@namedef{linenomath*}{}%
\def\endlinenomath{}
\expandafter\let\csname endlinenomath*\endcsname\endlinenomath

\let\linelabel\label

\def\switchlinenumbers{\@ifstar{}{}}
\def\setmakelinenumbers#1{\@ifstar{}{}}

\def\leftlinenumbers{\@ifstar{}{}}
\def\rightlinenumbers{\@ifstar{}{}}

\newcounter{linenumber}
\newcount\c@pagewiselinenumber
\let\c@runninglinenumber\c@linenumber

\def\runningpagewiselinenumbers{}
\def\realpagewiselinenumbers{}


\NewDocumentCommand\modulolinenumbers{s o}{}

\chardef\c@linenumbermodulo=5
```

```
\modulolinenumbers[1]

\newcommand*\firstlinenumber[1]{}

\newcommand\internallinenumbers{}
\let\endinternallinenumbers\endlinenumbers
\@namedef{internallinenumbers*}{\internallinenumbers*}
\expandafter\let\csname endinternallinenumbers*\endcsname\endlinenumbers

\newcommand*{\linenoplaceholder}[1]{% redefine per language
    (line number reference for \detokenize\expandafter{#1})
}

\newcommand*{\lineref}[2][]{\linenoplaceholder{#2}}
\newcommand*{\linerefp}[2][]{\linenoplaceholder{#2}}
\newcommand*{\linerefr}[2][]{\linenoplaceholder{#2}}

\newcommand\quotelinenumbers
   {\@ifstar\linenumbers{\@ifnextchar[\linenumbers{\linenumbers*}}}

\newdimen\linenumbersep
\newdimen\linenumberwidth
\newdimen\quotelinenumbersep

\quotelinenumbersep=\linenumbersep
\let\quotelinenumberfont\linenumberfont

\def\linenumberfont{\normalfont\tiny\sffamily}


\linenumberwidth=10pt
\linenumbersep=10pt

\def\thelinenumber{}

\def\LineNumber{}
\def\makeLineNumber{}
\def\makeLineNumberLeft{}
\def\makeLineNumberRight{}
\def\makeLineNumberOdd{}
\def\makeLineNumberEven{}
\def\makeLineNumberRunning{}


\newenvironment{numquote}     {\quote}{\endquote}
\newenvironment{numquotation} {\quotation}{\endquotation}
\newenvironment{numquote*}    {\quote}{\endquote}
\newenvironment{numquotation*}{\quotation}{\endquotation}

\newdimen\bframerule
\bframerule=\fboxrule

\newdimen\bframesep
\bframesep=\fboxsep

```

```
\newenvironment{bframe}
{%
    \LWR@forceminwidth{\bframerule}%
    \BlockClass[
        border:\LWR@printlength{\LWR@atleastonept} solid black ; %
        padding:\LWR@printlength{\bframesep}%
    ]{bframe}
}
{\endBlockClass}
```

File 187 **lwarp-lips.sty**

§ 284 Package lips

(*Emulates or patches code by* Matt Swift.)

Pkg lips lips is emulated.

```
% \LWR@ProvidesPackageDrop{lips}
\PackageInfo{lwarp}{Using the lwarp version of package ‘lips’.}%
\ProvidesPackage{lwarp-lips}[2001/08/31]

\NewDocumentCommand{\Lips}{}{\textellipsis}

\NewDocumentCommand{\BracketedLips}{}{[\textellipsis]}

\let\lips\Lips
\let\olips\lips

\DeclareOption*{}
\DeclareOption{mla}{
\let\lips\BracketedLips
}
\ProcessOptions\relax

\newcommand \LPNobreakList {}
```

File 188 **lwarp-listings.sty**

§ 285 Package listings

(*Emulates or patches code by* Carsten Heinz, Brooks Moses, Jobst Hoffmann.)

Pkg listings listings is supported with some limitations. Text formatting is not yet supported.

for HTML output:

```
\begin{warpHTML}

\LWR@ProvidesPackagePass{listings}[2018/09/02]
```

Force flexible columns. Fixed columns inserts spaces in the PDF output.

```
\lst@column@flexible
```

Patches to embed listings inside pre tags:

```
\let\LWR@origlst@Init\lst@Init
\let\LWR@origlst@DeInit\lst@DeInit

\let\LWR@origlsthkEveryPar\lsthk@EveryPar

\renewcommand{\l@lstlisting}[2]{\hypertocfloat{1}{lstlisting}{lol}{#1}{#2}}
```

`\lstset` {⟨*options*⟩}

Use the listings `literate` option to replace HTML entities:

```
\def\lstset@#1{\endgroup%
%  \ifx\@empty#1%
%         \@empty%
%     \else%
        \setkeys{lst}{%
            #1%
            ,literate=%
            {<}{\HTMLentity{lt}}{4}%
            {>}{\HTMLentity{gt}}{4}%
            {\&}{\HTMLentity{amp}}{5}%
        }%
%     \fi%
}
```

`\lst@Init` {⟨*backslash-processing*⟩} Done at the start of a listing.

```
\renewcommand{\lst@Init}[1]{%
```

Perform the listings initialization:

```
\LWR@traceinfo{lst@Init}%
\renewcommand*{\@captype}{lstlisting}%
\let\lst@aboveskip\z@\let\lst@belowskip\z@%
\gdef\lst@boxpos{t}%
\let\lst@frame\@empty
    \let\lst@frametshape\@empty
    \let\lst@framershape\@empty
    \let\lst@framebshape\@empty
    \let\lst@framelshape\@empty
\lstframe@\lst@frameround ffff\relax%
\lst@multicols\@empty%
\LWR@origlst@Init{#1}\relax%
```

Avoids extra horizontal space:

```
\def\lst@framelr{}%
```

```
\LWR@traceinfo{finished origlst@Init}%
\lst@ifdisplaystyle%
```

Creating a display.

Disable line numbers, produce the <pre>, then reenable line numbers.

```
\LWR@traceinfo{About to create verbatim.}%
\let\lsthk@EveryPar\relax%
\LWR@forcenewpage
\LWR@atbeginverbatim{2}{programlisting}%

\let\lsthk@EveryPar\LWR@origlsthkEveryPar%
\else%
```

Inline, so open a :

```
\ifbool{LWR@verbtags}{\LWR@htmltag{span class="inlineprogramlisting"}}{}%
\fi%
}

```

`\lst@DeInit` Done at the end of a listing.

```
\renewcommand*{\lst@DeInit}{%
\lst@ifdisplaystyle%
```

Creating a display.

Disable line numbers, produce the </pre>, then reenable line numbers:

```
\let\lsthk@EveryPar\relax%
\LWR@afterendverbatim{0}%
\let\lsthk@EveryPar\LWR@origlsthkEveryPar%
\else%
```

Inline, so create the closing :

```
\ifbool{LWR@verbtags}{\noindent\LWR@htmltag{/span}}{}%
\fi%
```

Final listings deinit:

```
\LWR@origlst@DeInit%
}
```

`\lst@MakeCaption` {⟨*t/b*⟩}

This is called BOTH at the top and at the bottom of each listing.

Patched for lwarp.

```
\def\lst@MakeCaption#1{%
\LWR@traceinfo{MAKING CAPTION at #1}%
  \lst@ifdisplaystyle
\LWR@traceinfo{making a listings display caption}%
    \ifx #1t%
         \ifx\lst@@caption\@empty\expandafter\lst@HRefStepCounter \else
                                    \expandafter\refstepcounter
         \fi {lstlisting}%
\LWR@traceinfo{About to assign label: !\lst@label!}%
%         \ifx\lst@label\@empty\else
% \label{\lst@label}\fi
\LWR@traceinfo{Finished assigning the label.}%
```

```
        \let\lst@arg\lst@intname \lst@ReplaceIn\lst@arg\lst@filenamerpl
        \global\let\lst@name\lst@arg \global\let\lstname\lst@name
        \lst@ifnolol\else
            \ifx\lst@@caption\@empty
                \ifx\lst@caption\@empty
                    \ifx\lst@intname\@empty \else \def\lst@temp{ }%
                    \ifx\lst@intname\lst@temp \else
```

This code places a contents entry for a non-float. This would have to be modified for lwarp:

```
\LWR@traceinfo{addcontents lst@name: -\lst@name-}%
%                           \addcontentsline{lol}{lstlisting}{\lst@name}
                    \fi\fi
                \fi
            \else
```

This would have to be modified for lwarp:

```
\LWR@traceinfo{addcontents lst@@caption: -\lst@@caption-}%
                 \addcontentsline{lol}{lstlisting}%
{\protect\numberline{\thelstlisting}%
{\protect\ignorespaces \LWR@isolate{\lst@@caption} \protect\relax}}%
            \fi
         \fi
     \fi
    \ifx\lst@caption\@empty\else
\LWR@traceinfo{lst@caption not empty-}%
        \lst@IfSubstring #1\lst@captionpos
            {\begingroup
\LWR@traceinfo{at the selected position}%
```

These space and box commands are not needed for HTML output:

```
%             \let\@@vskip\vskip
%             \def\vskip{\afterassignment\lst@vskip \@tempskipa}%
%             \def\lst@vskip{\nobreak\@@vskip\@tempskipa\nobreak}%
%             \par\@parboxrestore\normalsize\normalfont % \noindent (AS)
%             \ifx #1t\allowbreak \fi
             \ifx\lst@title\@empty
```

New lwarp code to create a caption:

```
                 \lst@makecaption\fnum@lstlisting{\ignorespaces \lst@caption}
             \else
```

New lwarp code to create a title:

```
%                  \lst@maketitle\lst@title % (AS)
\LWR@traceinfo{Making title: \lst@title}%
\begin{BlockClass}{lstlistingtitle}% lwarp
\lst@maketitle\lst@title% lwarp
\end{BlockClass}% lwarp
             \fi
\LWR@traceinfo{About to assign label: !\lst@label!}%
        \ifx\lst@label\@empty\else
\leavevmode% gets rid of bad space factor error
\GetTitleStringExpand{\lst@caption}%
\edef\LWR@lntemp{\GetTitleStringResult}%
\edef\@currentlabelname{\detokenize\expandafter{\LWR@lntemp}}%
```

```
\label{\lst@label}\fi
\LWR@traceinfo{Finished assigning the label.}%
```

Not needed for lwarp:

```
%              \ifx #1b\allowbreak \fi
             \endgroup}{}%
    \fi
\LWR@traceinfo{end of making a listings display caption}%
  \else
\LWR@traceinfo{INLINE}%
  \fi
\LWR@traceinfo{DONE WITH CAPTION at #1}%
}
```

line numbers Patched to keep left line numbers outside of the left margin, and place right line numbers in a field `\VerbatimHTMLWidth` wide.

```
\lst@Key{numbers}{none}{%
    \let\lst@PlaceNumber\@empty
    \lstKV@SwitchCases{#1}%
    {none:\\%
     left:\def\lst@PlaceNumber{%
```

For now, lwarp places left line numbers inline. Ideally the entire line would be moved to the right, but conflicts with list indenting occurs.

```
%         \LWR@origllap{
            \LWR@orignormalfont%
            \lst@numberstyle{\thelstnumber}\kern\lst@numbersep%
%         }
    }\\%
     right:\def\lst@PlaceNumber{\LWR@origrlap{\LWR@orignormalfont
                \kern 6in \kern\lst@numbersep
                \lst@numberstyle{\thelstnumber}}}%
    }{\PackageError{Listings}{Numbers #1 unknown}\@ehc}}

\end{warpHTML}
```

File 189 **lwarp-lltjext.sty**

§ 286 Package

lltjext

(*Emulates or patches code by* The LuaTeX-ja project team.)

Pkg lltjext lltjext is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{lltjext}[2018/10/07]

\protected\def\yoko{%
  \directlua{luatexja.direction.set_list_direction(4, 'yoko')}%
}
```

```
\protected\def\tate{\yoko}
\protected\def\dtou{\yoko}
\protected\def\utod{\yoko}

\define@key[ltj]{japaram}{direction}{}

\yoko

\DeclareExpandableDocumentCommand{\rensuji}{s o m}{#3}

\DeclareDocumentCommand{\layoutfloat}{d() o m}{}

\DeclareDocumentCommand{\DeclareLayoutCaption}{m d<> d() o}{}

\LetLtxMacro\pcaption\caption

\DeclareDocumentCommand{\layoutcaption}{d<> d() o}{}

\let\captiondir\relax
\RenewDocumentEnvironment{LWR@HTML@minipage}{d<> O{t} O{} O{t} m}
    {\LWR@HTML@sub@minipage{#2}{#3}{#4}{#5}}
    {\endLWR@HTML@sub@minipage}

\RenewDocumentCommand{\LWR@HTML@parbox}{d<> O{t} O{} O{t} m +m}
{
\LWR@traceinfo{parbox of width #4}%
\begin{minipage}[#2][#3][#4]{#5}%
#6
\end{minipage}%
}

\RenewDocumentCommand{\pbox}{d<> O{0pt} O{c} m}{%
\global\booltrue{LWR@minipagefullwidth}%
\parbox{#2}{#4}%
}
```

File 190 **lwarp-longtable.sty**

§ 287 Package

longtable

(*Emulates or patches code by* David Carlisle.)

Pkg longtable longtable is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{longtable}[2014/10/28]
```

Use one of either \endhead or \endfirsthead for both print and HTML, and use a \warpprintonly macro to disable the other head phrase, and also the \endfoot and \endfirstfoot phrases. (See section 9.10.2 if using threeparttablex.)

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{         % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  [ <lastfoot macros> ] \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{
  [ <lastfoot macros> ]   % HTML last footer, without \endfoot
                                                % or \endlastfoot.
}
\end{longtable}
```

⚠ Misplaced \noalign Use the \warpprintonly macro instead of the warpprint environment. Doing so helps avoid "Misplaced \noalign." when using \begin{warpprint}.

⚠ \kill \kill is ignored, place a \kill line inside

```
\begin{warpprint} . . .  \end{warpprint}
```

or place it inside \warpprintonly.

⚠ lateximage longtable is not supported inside a lateximage.

See:
http://tex.stackexchange.com/questions/43006/why-is-input-not-expandable

Used to detect more than one of \endhead and \endfirsthead in use for HTML at the same time.

```
\newbool{LWR@longtable@havehead}
\boolfalse{LWR@longtable@havehead}
```

Env longtable * [⟨*horizalignment*⟩] {⟨*colspec*⟩} Emulates the longtable environment.

Per the caption package, the starred version steps the counter per caption. The unstarred version steps the counter once at the beginning, but not at each caption.

Options [c], [l], and [r] are ignored.

```
\newenvironment{longtable*}[2][]{%
\LWR@floatbegin{table}%
\setcaptiontype{\LTcaptype}%
\caption@setoptions{longtable}%
\caption@setoptions{@longtable}%
\caption@LT@setup%
\booltrue{LWR@starredlongtable}%
\boolfalse{LWR@longtable@havehead}%
\let\captionlistentry\LWR@LTcaptionlistentry%
\tabular{#2}
}
{\endtabular\LWR@floatend}

```

```
\newenvironment{longtable}[2][]{%
\LWR@floatbegin{table}%
\setcaptiontype{\LTcaptype}%
\caption@setoptions{longtable}%
\caption@setoptions{@longtable}%
\caption@LT@setup%
\refstepcounter{\LTcaptype}%
\boolfalse{LWR@longtable@havehead}%
\let\captionlistentry\LWR@LTcaptionlistentry%
\tabular{#2}
}
{\endtabular\LWR@floatend}
```

Provided for compatibility, but ignored:

```
\newcounter{LTchunksize}
```

Error for heads which should have been in `\warpprintonly`:

```
\newcommand*{\LWR@longtable@headerror}{%
    \PackageError{lwarp}
    {For longtable:\MessageBreak
    1: Keep either one of an \protect\endhead\space or
        \protect\endfirsthead\space\MessageBreak
        \space phrase as-is, to be used by both print and HTML.\MessageBreak
    2: Place any other \protect\end... phrases inside a\MessageBreak
        \space\protect\warpprintonly\space macro,
            to be ignored by HTML.\MessageBreak
    3: Add a final footer for HTML at the end of the table\MessageBreak
        \space inside a \protect\warpHTMLonly\space macro.
            This can be\MessageBreak
        \space a copy of an \protect\endfoot\space or
            \protect\endfirstfoot\space phrase,\MessageBreak
        \space but without the actual \protect\endfoot\space
            or \protect\endfirstfoot\MessageBreak
        \space macros.  If using threeparttablex, add\MessageBreak
        \space \protect\insertTableNotes\space here,
            optionally with\MessageBreak
        \space \protect\UseMinipageWidths\space in front.\MessageBreak
    See the lwarp documentation regarding longtables\MessageBreak
    and threeparttablex}
    {See the lwarp documentation regading longtables and threeparttablex.}
}
```

Error if more than one of `\endhead` or `\endfirsthead` is outside of `warpprintonly`.

```
\newcommand*{\LWR@longtable@maybeheaderror}{%
\ifbool{LWR@longtable@havehead}%
    {\LWR@longtable@headerror}%
    {%
        \booltrue{LWR@longtable@havehead}
        \LWR@tabularendofline% throws away options //[dim] and //*
    }%
}
```

Error if more than one of these is outside of warppprint.

```
\def\endhead{\LWR@longtable@maybeheaderror}
\def\endfirsthead{\LWR@longtable@maybeheaderror}
```

Error if ANY of these is outside of warppprint.

```
\def\endfoot{\LWR@longtable@headerror}
\def\endlastfoot{\LWR@longtable@headerror}
```

```
\newcommand\tabularnewline{\LWR@tabularendofline}
\newcommand{\setlongtables}{}% Obsolete command, does nothing.
\newlength{\LTleft}
\newlength{\LTright}
\newlength{\LTpre}
\newlength{\LTpost}
\newlength{\LTcapwidth}
```

```
\LetLtxMacro\LWR@origkill\kill
\renewcommand*{\kill}{\LWR@tabularendofline}
\appto\LWR@restoreorigformatting{%
\LetLtxMacro\kill\LWR@origkill%
}
```

File 191 **lwarp-lscape.sty**

§ 288 Package lscape

(*Emulates or patches code by* D. P. Carlisle.)

Pkg lscape lscape is emulated.

for HTML output: Discard all options for lwarp-lscape.

```
\LWR@ProvidesPackageDrop{lscape}[2000/10/22]
```

```
\newenvironment*{landscape}{}{}
```

File 192 **lwarp-ltablex.sty**

§ 289 Package ltablex

(*Emulates or patches code by* Anil K. Goel.)

Pkg ltablex ltablex is emulated by lwarp.

for HTML output: Relies on tabularx.

```
\RequirePackage{tabularx}
```

```
2
3 \LWR@ProvidesPackageDrop{ltablex}[2014/08/13]
4
5 \DeclareDocumentEnvironment{tabularx}{m o m}
6 {\longtable{#3}}
7 {\endlongtable}
8
9 \DeclareDocumentEnvironment{tabularx*}{m o m}
10 {\longtable{#3}}
11 {\endlongtable}
12
13 \newcommand*{\keepXColumns}{}
14 \newcommand*{\convertXColumns}{}
```

File 193 **lwarp-ltcaption.sty**

§ 290 Package ltcaption

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg ltcaption ltcaption is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{ltcaption}[2018/08/26]
```

\LTcaptype is already defined by lwarp.

longtable* is already defined by lwarp-longtable.

```
2 \newlength{\LTcapskip}
3 \newlength{\LTcapleft}
4 \newlength{\LTcapright}
5 \newcommand*{\LTcapmarginsfalse}{}
```

File 194 **lwarp-ltxgrid.sty**

§ 291 Package ltxgrid

Pkg ltxgrid ltxgrid is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{ltxgrid}[2010/07/25]
```

```
2 \newcommand*{\onecolumngrid}{}
3 \newcommand*{\twocolumngrid}{}
4 \newcommand*{\removestuff}{}
5 \newcommand*{\addstuff}[2]{}
6 \newcommand*{\replacestuff}[2]{}
```

File 195 **lwarp-ltxtable.sty**

§ 292 Package

ltxtable

Pkg ltxtable ltxtable is emulated.

⚠ table numbering The print version does not seem to honor `longtable*` from the caption package, while lwarp does.

for HTML output:

```
\LWR@ProvidesPackageDrop{ltxtable}[1995/12/11]
```

\LTXtable {⟨*width*⟩} {⟨*file*⟩}

```
\newcommand*{\LTXtable}[2]{%
\input{#2}%
}
```

File 196 **lwarp-lua-check-hyphen.sty**

§ 293 Package

lua-check-hyphen

Pkg lua-check-hyphen lua-check-hyphen is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{lua-check-hyphen}[2018/04/19]
```

```
\newcommand*{\LuaCheckHyphen}[1]{}
```

File 197 **lwarp-lua-visual-debug.sty**

§ 294 Package

lua-visual-debug

Pkg lua-visual-debug lua-visual-debug is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{lua-visual-debug}[2016/05/30]
```

File 198 **lwarp-luacolor.sty**

§ 295 Package

luacolor

Pkg luacolor luacolor is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{luacolor}[2016/05/16]
```

```
\newcommand{\luacolorProcessBox}[1]{}
```

File 199 **lwarp-luatodonotes.sty**

§ 296 Package

luatodonotes

(*Emulates or patches code by* Fabian Lipp.)

Pkg luatodonotes luatodonotes is emulated.

The documentation for todonotes and luatodonotes have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

for HTML output:

```
\LWR@ProvidesPackagePass{luatodonotes}[2017/09/30]
```

Nullify options:

```
\@todonotes@additionalMarginEnabledfalse

\if@todonotes@disabled
\else

\newcommand{\ext@todo}{tdo}

\renewcommand{\l@todo}[2]{\hypertocfloat{1}{todo}{ldo}{#1}{#2}}

\let\LWRTODONOTES@orig@todototoc\todototoc

\renewcommand*{\todototoc}{%
\phantomsection%
\LWRTODONOTES@orig@todototoc%
}


\renewcommand{\@todonotes@drawMarginNoteWithLine}{%
\fcolorbox
    {\@todonotes@currentbordercolor}
    {\@todonotes@currentbackgroundcolor}
    {\arabic{@todonotes@numberoftodonotes}}
\marginpar{\@todonotes@drawMarginNote}
}

\renewcommand{\@todonotes@drawInlineNote}{%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \if@todonotes@authorgiven%
        {\@todonotes@author:\,}%
        \fi%
```

```
        \@todonotes@text%
    }%
}

\newcommand{\@todonotes@drawMarginNote}{%
    \if@todonotes@authorgiven%
        \@todonotes@author\par%
    \fi%
    \arabic{@todonotes@numberoftodonotes}: %
    \fcolorbox%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \@todonotes@sizecommand%
        \@todonotes@text %
    }%
}%

\renewcommand{\missingfigure}[2][]{%
\setkeys{todonotes}{#1}%
\addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentfigcolor}%
    {%
        \setlength{\fboxrule}{4pt}%
        \fcolorbox{red}{white}{Missing figure} \quad #2%
    }
}

\LetLtxMacro\LWRTODONOTES@orig@todocommon\@todocommon

\RenewDocumentCommand{\@todocommon}{m m}{%
\begingroup%
\renewcommand*{\phantomsection}{}%
\LWRTODONOTES@orig@todocommon{#1}{#2}%
\endgroup%
}

\renewcommand{\@todoarea}[3][]{%
    \@todonotes@areaselectedtrue%
    \@todocommon{#1}{#2}%
    \todonotes@textmark@highlight{#3}%
    \zref@label{@todonotes@\arabic{@todonotes@numberoftodonotes}@end}%
}%


\DeclareDocumentCommand{\todonotes@textmark@highlight}{m}{%
\InlineClass[background:\LWR@origpound{}B3FFB3]{highlight}{#1}%
}

\fi% \if@todonotes@disabled
```

File 200 **lwarp-magaz.sty**

§ 297 Package

magaz

Pkg magaz magaz is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{magaz}[2011/11/24]

\newcommand\FirstLine[1]{%
    \begingroup%
    \FirstLineFont{%
        \LWR@textcurrentcolor{%
            \LWR@textcurrentfont{%
                #1%
            }%
        }%
    }%
    \endgroup%
}

\providecommand\FirstLineFont{\scshape}
```

File 201 **lwarp-makeidx.sty**

§ 298 Package

makeidx

(*Emulates or patches code by* LaTeX Project Team.)

Pkg makeidx makeidx is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{makeidx}[2014/09/29]
```

\@wrindex is redefined \AtBeginDocument by the lwarp core.

\printindex

```
\preto\printindex{%
    \LWR@orignewpage%
    \LWR@startpars%
}
```

File 202 **lwarp-manyfoot.sty**

§ 299 Package

manyfoot

Pkg manyfoot

manyfoot is emulated.

bigfoot, manyfoot

If using the bigfoot package, and possibly also manyfoot, problems may occur with counter allocation because lwarp uses many counters, and there is a difference in how counters numbered 256 and up are handled in pdfLaTeX. With bigfoot this has been known to show up as an error related to one footnote insert being forbidden inside another. Another problem showed up as a input stack error, and which of these problems occurred depended on how many counters were allocated.

As a possible solution, try creating several new counters before defining bigfoot or manyfoot footnotes, hoping to shift the problematic counter above the 256 threshold. It may instead be necessary to use XeLaTeX or LuaLaTeX instead of pdfLaTeX.

lwarp's emulation of bigfoot uses manyfoot, so some of the bigfoot enhancements are included here.

The bigfoot "default" footnote is ignored, using the lwarp version instead.

for HTML output:

```
\LWR@ProvidesPackageDrop{manyfoot}[2005/09/11]

\RequirePackage{nccfoots}

\newcommand{\extrafootnoterule}{}

\let\defaultfootnoterule\footnoterule

\newcommand*{\SelectFootnoteRule}[2][0]{}

\newcommand{\footnoterulepriority}{1}

\newcommand{\SetFootnoteHook}[1]{}
\@onlypreamble\SetFootnoteHook

\newcommand{\SplitNote}{}

\newcommand*\ExtraParaSkip[1]{}

\newcommand*{\newfootnote}[2][plain]{%
    \ifstrequal{#2}{default}{}{% not "default"
        \expandafter\newbox\csname LWR@footnote#2box\endcsname%
        \appto{\LWR@printpendingfootnotes}{%
            \LWR@@printpendingfootnotes{footnote#2}%
        }
        \long\csdef{Footnotetext#2}##1##2{%
            \NCC@makefnmark{##1}%
            \LWR@@footnotetext{##2}{LWR@footnote#2box}%
        }%
```

```
        \long\csdef{Footnotetext#2+}##1##2{%
            \NCC@makefnmark{##1}%
            \LWR@@footnotetext{##2}{LWR@footnote#2box}%
        }%
    }% not "default"
}
\@onlypreamble\newfootnote

\newcommand*{\DeclareNewFootnote}[2][plain]{%
  \@ifnextchar[%
        {\LWR@manyfoot@declare{#1}{#2}}%
        {\LWR@manyfoot@declare{#1}{#2}[arabic]}%
}

\def\LWR@manyfoot@declare#1#2[#3]{%
\ifstrequal{#2}{default}{}{% not "default"
  \newfootnote[#1]{#2}%
  \newcounter{footnote#2}%
    \newcounter{footnote#2Reset}%
    \setcounter{footnote#2Reset}{0}%
    \csdef{thefootnote#2}{%
      \expandafter\noexpand\csname @#3\endcsname%
      \expandafter\noexpand\csname c@footnote#2\endcsname%
    }%
```

For bigfoot, the footnote commands may be appended with one or two plusses or one or two minuses, which are ignored in HTML.

```
   \expandafter\NewDocumentCommand\csname footnote#2\endcsname{t{+}t{+}t{-}t{-}}{%
        \stepcounter{footnote#2}%
        \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
        \@footnotemark%
        \csuse{Footnotetext#2}{\@thefnmark}% absorbs the footnote contents
    }%
    \csdef{footnotemark#2}{%
        \stepcounter{footnote#2}%
        \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
        \@footnotemark%
    }%
   \expandafter\NewDocumentCommand\csname footnotetext#2\endcsname{t{+}t{+}t{-}t{-}}{%
        \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
        \csuse{Footnotetext#2}{\@thefnmark}% absorbs the footnote contents
    }%
    \csdef{Footnotemark#2}{%
      \Footnotemark%
    }%
    \csdef{Footnote#2}##1{%
      \Footnotemark{##1}%
      \csuse{Footnotetext#2}{##1}%
    }%
}% not "default"
}
\@onlypreamble\DeclareNewFootnote
```

File 203 **lwarp-marginal.sty**

§ 300 Package marginal

Pkg marginal marginal is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{marginal}

\newcommand*{\showlostmarginals}{}
\newcommand*{\enlargefreelist}{}
\newcommand*{\onesidemarginals}{}
```

File 204 **lwarp-marginfit.sty**

§ 301 Package marginfit

Pkg marginfit marginfit is ignored.

for HTML output: Discard all options for lwarp-marginfit:

```
\LWR@ProvidesPackageDrop{marginfit}[2018/06/08]
```

File 205 **lwarp-marginfix.sty**

§ 302 Package marginfix

(*Emulates or patches code by* Stephen Hicks.)

Pkg marginfix Emulated.

for HTML output: Discard all options for lwarp-marginfix:

```
\LWR@ProvidesPackageDrop{marginfix}[2013/09/08]

\newcommand*{\marginskip}[1]{}
\newcommand*{\clearmargin}{}
\newcommand*{\softclearmargin}{}
\newcommand*{\extendmargin}[1]{}
\newcommand*{\mparshift}[1]{}
\newdimen\marginheightadjustment
\newdimen\marginposadjustment
\newcommand*{\blockmargin}[1][]{}
\newcommand*{\unblockmargin}[1][]{}
\newcommand*{\marginphantom}[2][]{}
```

File 206 **lwarp-marginnote.sty**

§ 303 Package marginnote

(*Emulates or patches code by* Markus Kohm.)

Pkg marginnote Emulated.

for HTML output: Discard all options for lwarp-marginnote:

```
\LWR@ProvidesPackageDrop{marginnote}[2018/08/09]

\NewDocumentCommand{\marginnote}{+o +m o}{\marginpar{#2}}

\newcommand*{\marginnoteleftadjust}{}
\newcommand*{\marginnoterightadjust}{}
\newcommand*{\marginnotetextwidth}{}
\let\marginnotetextwidth\textwidth
\newcommand*{\marginnotevadjust}{}
\newcommand*{\marginfont}{}
\newcommand*{\raggedleftmarginnote}{}
\newcommand*{\raggedrightmarginnote}{}
```

File 207 **lwarp-marvosym.sty**

§ 304 Package marvosym

(*Emulates or patches code by* Thomas Henlich, Mojca Miklavec.)

Pkg marvosym marvosym is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

for HTML output:

```
\LWR@ProvidesPackagePass{marvosym}[2011/07/20]

\renewcommand{\mvchr}[1]{%
    \begin{lateximage}*[(symbol #1)][marvosym #1]%
    \mvs\char#1%
    \end{lateximage}%
}

\renewcommand{\textmvs}[1]{%
    \begin{lateximage}%
    \mvs #1%
    \end{lateximage}%
}
```

File 208 **lwarp-mcaption.sty**

§ 305 Package mcaption

(*Emulates or patches code by* Stephan Hennig.)

Pkg mcaption mcaption is nullified.

for HTML output: Discard all options for lwarp-mcaption:

```
\LWR@ProvidesPackageDrop{mcaption}[2009/03/13]

\newenvironment{margincap}{}{}
\newcommand*{\margincapalign}{}
\newlength{\margincapsep}
```

File 209 **lwarp-mdframed.sty**

§ 306 Package mdframed

(*Emulates or patches code by* Marco Daniel, Elke Schubert.)

Pkg mdframed mdframed is loaded with options forced to `framemethod=none`.

§ 306.1 Limitations

support Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for mdframed environments and frame titles.

⚠ loading When used, lwarp loads mdframed in HTML with `framemethod=none`.

font For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where `\textbf` must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the mdframed source). Since lwarp does not support `\bfseries` and friends, only one font selection may be made at a time.

theoremtitlefont `theoremtitlefont` is not supported, since the following text is not in braces in the mdframed source.

ignored options

`userdefinedwidth` and `align` are currently ignored.

css classes

Environments created or encapsulated by mdframed are enclosed in a `<div>` of class `mdframed`, and also class `md<environmentname>` for new environments.

Frame titles are placed in a `<div>` of class |mdframedtitle|. Subtitles are in a `<div>` of class |mdframedsubtitle|, and likewise for subsubtitles.

Pre-existing hooks are used to patch extra functions before and after the frames.

§ 306.2 Package loading

for HTML output:

```
\RequirePackage{xcolor}% for \convertcolorspec

\LWR@ProvidesPackageDrop{mdframed}[2013/07/01]
```

Do not require Ti*k*z or pstricks:

```
\LWR@origRequirePackage[framemethod=none]{mdframed}
```

§ 306.3 Patches

Patch to remove PDF formatting and add HTML tags:

```
\AtBeginDocument{
\def\mdf@trivlist#1{%
  \edef\mdf@temp{%
%     \topsep=\the\topsep\relax%
%     \partopsep=\the\partopsep\relax%
%     \parsep=\the\parsep\relax%
  }%
%   \setlength{\topsep}{#1}%
%   \topskip\z@%
%   \partopsep\z@%
%   \parsep\z@%
%   \@nmbrlistfalse%
%   \@trivlist%
%   \labelwidth\z@%
%   \leftmargin\z@%
%   \itemindent\z@%
  \let\@itemlabel\@empty%
  \def\makelabel##1{##1}%
%   \item\relax\mdf@temp\relax%
}

\renewcommand*{\endmdf@trivlist}{%
\LWR@traceinfo{endmdf@trivlist}%
% \endtrivlist%
\LWR@listend%
}
}% AtBeginDocument
```

§ 306.4 Initial setup

To handle css and paragraphs, patch code at start and end of environment and contents. `\LWR@print@raggedright` helps avoid hyphenation.

```
\mdfsetup{
startcode={\LWR@mdframedstart\LWR@print@raggedright},
endcode={\LWR@mdframedend},
startinnercode={\LWR@startpars\LWR@print@raggedright},
endinnercode={\LWR@stoppars},
}
```

§ 306.5 Color and length HTML conversion

`\LWR@mdfprintcolor` {⟨*mdfcolorkey*⟩}

Given the mdframed key, print the color.

```
\newcommand*{\LWR@mdfprintcolor}[1]{%
\convertcolorspec{named}{\@nameuse{mdf@#1}}{HTML}\LWR@tempcolor%
\LWR@origpound\LWR@tempcolor
}
```

`\LWR@mdfprintlength` {⟨*mdflengthkey*⟩}

Given the mdframed key, print the length.

```
\newcommand*{\LWR@mdfprintlength}[1]{%
\LWR@forceminwidth{\@nameuse{mdf@#1@length}}%
\LWR@printlength{\LWR@atleastonept}%
}
```

§ 306.6 Environment encapsulation

`\LWR@mdframedstart` Actions before an mdframe starts.

Encapsulate a frame inside a `<div>` of the desired `class`.

```
\newcommand*{\LWR@mdframedstart}{%
\LWR@traceinfo{LWR@mdframedstart start}%
```

Turn off paragraph handling during the generation of the encapsulating tags:

```
\LWR@stoppars%
```

Open a `<div>` and with custom `class` and custom `style`. A `BlockClass` environment is not used because this `<div>` is created by the mdframed `startcode` and `endcode` settings, which do not properly nest the `<div>` inside the `mdframed` environment.

```
\LWR@htmltagc{div class="%
mdframed%
\ifdefstring{\LWR@mdthisenv}{mdframed}{}{ \LWR@mdthisenv}%
" \LWR@orignewline
style=" \LWR@orignewline
```

Convert and print the background color:

```
background: \LWR@mdfprintcolor{backgroundcolor} ; \LWR@orignewline
```

Convert and print the border color and width:

```
border: \LWR@mdfprintlength{linewidth} solid
\LWR@mdfprintcolor{linecolor} ; \LWR@orignewline
```

Convert and print the border radius:

```
border-radius: \LWR@mdfprintlength{roundcorner} ; \LWR@orignewline
```

Convert and print the shadow:

```
\ifbool{mdf@shadow}{%
    box-shadow:
    \LWR@mdfprintlength{shadowsize}
    \LWR@mdfprintlength{shadowsize}
    \LWR@mdfprintlength{shadowsize}
    \LWR@mdfprintcolor{shadowcolor} ;
}
{box-shadow: none ;}
\LWR@orignewline

"}
% \LWR@htmldivclass{\LWR@mdthisenv}
```

mdframed environment may not work with the HTML versions of the following, so restore them to their originals while inside mdframed:

```
\LWR@select@print@hspace%
\renewcommand*{\rule}{\LWR@print@rule}
\LetLtxMacro\makebox\LWR@print@makebox%

\LWR@startpars%
\LWR@traceinfo{LWR@mdframedstart done}%
}
```

\LWR@mdframedend Actions after an mdframe ends.

After closing the , globally restore to the default environment type:

```
\newcommand*{\LWR@mdframedend}{
\LWR@traceinfo{LWR@mdframedend start}%
```

Close the custom :

```
\LWR@htmldivclassend{\LWR@mdthisenv}
```

Reset future custom class to the default:

```
\gdef\LWR@mdthisenv{mdframed}
```

Resume paragraph handling:

```
\LWR@startpars%
\LWR@traceinfo{LWR@mdframedend done}%
}
```

§ 306.7 Mdframed environment

```
\renewenvironment{mdframed}[1][]{%
 \color@begingroup%
   \mdfsetup{userdefinedwidth=\linewidth,#1}%
   \mdf@startcode%
   \mdf@preenvsetting%
   \ifdefempty{\mdf@firstframetitle}{}%
           {\let\mdf@frametitlesave\mdf@frametitle%
            \let\mdf@frametitle\mdf@firstframetitle%
           }%
   \ifvmode\nointerlineskip\fi%
        \ifdefempty{\mdf@frametitle}{}%
            {\mdfframedtitleenv{\mdf@frametitle}%
% \mdf@@frametitle@use%
            }%
   \mdf@trivlist{\mdf@skipabove@length}%%
   \mdf@settings%
%    \mdf@lrbox{\mdf@splitbox@one}%
%    \mdf@startinnercode%
  }%
  {%
%    \mdf@@ignorelastdescenders%
   \par%
%     \unskip\ifvmode\nointerlineskip\hrule \@height\z@ \@width\hsize\fi%%
   \ifmdf@footnoteinside%
      \def\mdf@reserveda{%
        \mdf@footnoteoutput%
%         \mdf@endinnercode%
%         \endmdf@lrbox%
%         \ifdefempty{\mdf@frametitle}{}%
%             {\mdfframedtitleenv{\mdf@frametitle}\mdf@@frametitle@use}%
%         \detected@mdf@put@frame
      }%
   \else%
      \def\mdf@reserveda{%
%         \mdf@endinnercode%
%         \endmdf@lrbox%
%         \ifdefempty{\mdf@frametitle}{}%
%             {\mdfframedtitleenv{\mdf@frametitle}\mdf@@frametitle@use}%
%         \detected@mdf@put@frame%
        \mdf@footnoteoutput%
        }%
   \fi%
   \mdf@reserveda%
  \aftergroup\endmdf@trivlist%
 \color@endgroup%
 \mdf@endcode%
}
```

\mdf@footnoteoutput

```
\renewrobustcmd*\mdf@footnoteoutput{%
    \LWR@printpendingmpfootnotes%
}
```

§ 306.8 Titles and subtitles

`\mdfframedtitleenv` {⟨*title*⟩}

Place the title inside a of class mdframedtitle:

```
\newlength{\LWR@titleroundcorner}

\renewrobustcmd\mdfframedtitleenv[1]{%
\LWR@traceinfo{LWR@mdframedtitleenv start}%
```

Open a with a custom class and custom style:

```
\begin{BlockClass}[%
```

Convert and print the title background color:

```
background:
\LWR@mdfprintcolor{frametitlebackgroundcolor}
; \LWR@orignewline
```

Convert and print the title rule:

```
\ifbool{mdf@frametitlerule}{%
    border-bottom:
    \LWR@mdfprintlength{frametitlerulewidth}
    solid
    \LWR@mdfprintcolor{frametitlerulecolor}
    ; \LWR@orignewline
}{}%
```

Finish the custom style and the opening tag:

```
]{mdframedtitle}%
```

Print the title inside the :

```
\mdf@frametitlefont{\LWR@textcurrentfont{#1}}%
```

Close the :

```
\end{BlockClass}%
\LWR@traceinfo{LWR@mdframedtitleenv end}%
}
```

`\LWR@mdfsubtitlecommon` {⟨*sub -or- subsub*⟩} [⟨*options*⟩] {⟨*title*⟩}

Common code for \LWR@mdfsubtitle and \LWR@mdfsubsubtitle.

Encapsulate the subtitle inside a of class mdframedsubtitle:

```
\NewDocumentCommand{\LWR@mdfsubtitlecommon}{m o m}
{% the following empty line is required

\LWR@traceinfo{LWR@mdframedsubtitlecommon start}%
```

Open a with a custom class and custom style:

```
\begin{BlockClass}[%
```

Convert and print the background color:

```
background:
\LWR@mdfprintcolor{#1titlebackgroundcolor}
; \LWR@orignewline
```

Convert and print the above line:

```
\ifbool{mdf@#1titleaboveline}{%
    border-top:
    \LWR@mdfprintlength{#1titleabovelinewidth}
    solid
    \LWR@mdfprintcolor{#1titleabovelinecolor}
    ; \LWR@orignewline
}{}%
```

Convert and print the below line:

```
\ifbool{mdf@#1titlebelowline}{%
    border-bottom:
    \LWR@mdfprintlength{#1titlebelowlinewidth}
    solid
    \LWR@mdfprintcolor{#1titlebelowlinecolor}
    ; \LWR@orignewline
}{}%
```

Finish the custom style and the opening tag:

```
]{mdframed#1title}%
```

Perform the original subtitle action:

```
\IfNoValueTF{#2}
{\@nameuse{LWR@origmdf#1title}{\csuse{mdf@#1titlefont}{\LWR@textcurrentfont{#3}}}}%
{\@nameuse{LWR@origmdf#1title}[#2]{\csuse{mdf@#1titlefont}{\LWR@textcurrentfont{#3}}}}%
```

Close the :

```
\end{BlockClass}%
\LWR@traceinfo{LWR@mdframedsubtitlecommon end}%
}
```

`\LWR@mdfsubtitle` `[`⟨*options*⟩`]` `{`⟨*title*⟩`}`

```
\newcommand*{\LWR@mdfsubtitle}{%
\LWR@mdfsubtitlecommon{sub}%
}
\let\mdfsubtitle\LWR@mdfsubtitle
```

`\LWR@mdfsubsubtitle` `[`⟨*options*⟩`]` `{`⟨*title*⟩`}`

```
\newcommand*{\LWR@mdfsubsubtitle}{%
\LWR@mdfsubtitlecommon{subsub}%
}
\let\mdfsubsubtitle\LWR@mdfsubsubtitle
```

§ 306.9 New environments

\LWR@mdthisenv Stores the environment of the frame about to be created:

```
\newcommand*{\LWR@mdthisenv}{mdframed}
```

\newmdenv [⟨*options*⟩] {⟨*env-name*⟩}

Modified from the original to remember the environment.

```
\renewrobustcmd*\newmdenv[2][]{%
\newenvironment{#2}%
{%
\mdfsetup{#1}%
\renewcommand*{\LWR@mdthisenv}{md#2}%
\begin{mdframed}%
}
{\end{mdframed}}%
}
```

\surroundwithmdframed [⟨*options*⟩] {⟨*environment*⟩}

Modified from the original to remember the environment.

```
\renewrobustcmd*{\surroundwithmdframed}[2][]{%
\BeforeBeginEnvironment{#2}{%
\renewcommand*{\LWR@mdthisenv}{md#2}%
\begin{mdframed}[#1]}%
\AfterEndEnvironment{#2}{\end{mdframed}}%
}
```

\mdtheorem [⟨*mdframed-options*⟩] {⟨*envname*⟩} [⟨*numberedlike*⟩] {⟨*caption*⟩} [⟨*within*⟩]

Modified from the original to remember the environment.

```
\DeclareDocumentCommand{\mdtheorem}{ O{} m o m o }%
 {\ifcsdef{#2}%
   {\mdf@PackageWarning{Environment #2 already exits\MessageBreak}}%
   {%
    \IfNoValueTF {#3}%
     {%#3 not given -- number relationship
      \IfNoValueTF {#5}%
        {%#3+#5 not given
        \@definecounter{#2}%
        \expandafter\xdef\csname the#2\endcsname{\@thmcounter{#2}}%
        \newenvironment{#2}[1][]{%
          \refstepcounter{#2}%
          \ifstrempty{##1}%
            {\let\@temptitle\relax}%
            {%
             \def\@temptitle{\mdf@theoremseparator%
                             \mdf@theoremspace%
                             \mdf@theoremtitlefont%
                             \LWR@textcurrentfont{##1}}% lwarp
             \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
             }%
          \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
```

```
                                        \@temptitle}]}%
      {\end{mdframed}}%
    \newenvironment{#2*}[1][]{%
      \ifstrempty{##1}{\let\@temptitle\relax}{\def\@temptitle{:\ ##1}}%
      \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]}%
      {\end{mdframed}}%
    }%
    {%#5 given -- reset counter
    \@definecounter{#2}\@newctr{#2}[#5]%
    \expandafter\xdef\csname the#2\endcsname{\@thmcounter{#2}}%
    \expandafter\xdef\csname the#2\endcsname{%
           \expandafter\noexpand\csname the#5\endcsname \@thmcountersep%
              \@thmcounter{#2}}%
    \newenvironment{#2}[1][]{%
      \refstepcounter{#2}%
      \ifstrempty{##1}%
        {\let\@temptitle\relax}%
        {%
         \def\@temptitle{\mdf@theoremseparator%
                         \mdf@theoremspace%
                         \mdf@theoremtitlefont%
                         \LWR@textcurrentfont{##1}}% lwarp
         \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
         }
      \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
                                        \@temptitle}]}%
      {\end{mdframed}}%
    \newenvironment{#2*}[1][]{%
      \ifstrempty{##1}%
        {\let\@temptitle\relax}%
        {%
         \def\@temptitle{\mdf@theoremseparator%
                         \mdf@theoremspace%
                         \mdf@theoremtitlefont%
                         \LWR@textcurrentfont{##1}}% lwarp
         \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
         }%
      \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]}%
      {\end{mdframed}}%
    }%
  }%
  {%#3 given -- number relationship
    \global\@namedef{the#2}{\@nameuse{the#3}}%
    \newenvironment{#2}[1][]{%
      \refstepcounter{#3}%
      \ifstrempty{##1}%
        {\let\@temptitle\relax}%
        {%
         \def\@temptitle{\mdf@theoremseparator%
                         \mdf@theoremspace%
                         \mdf@theoremtitlefont%
                         \LWR@textcurrentfont{##1}}% lwarp
         \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
         }
      \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
```

```
                                          \@temptitle}]}%
      {\end{mdframed}}%
    \newenvironment{#2*}[1][]{%
      \ifstrempty{##1}{\let\@temptitle\relax}{\def\@temptitle{:\ ##1}}%
      \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]}%
      {\end{mdframed}}%
  }%
  \BeforeBeginEnvironment{#2}{\renewcommand*{\LWR@mdthisenv}{md#2}}% lwarp
  \BeforeBeginEnvironment{#2*}{\renewcommand*{\LWR@mdthisenv}{md#2}}% lwarp
 }%
}
```

`\newmdtheoremenv` [⟨*1: mdframed-options*⟩] {⟨*2: envname*⟩} [⟨*3: numberedlike*⟩] {⟨*4: caption*⟩} [⟨*5: within*⟩]

Modified from the original to remember the environment.

```
\DeclareDocumentCommand\newmdtheoremenv{O{} m o m o }{%
 \ifboolexpr{ test {\IfNoValueTF {#3}} and test {\IfNoValueTF {#5}} }%
   {\newtheorem{#2}{#4}}%
   {%
    \IfValueT{#3}{\newtheorem{#2}[#3]{#4}}%
    \IfValueT{#5}{\newtheorem{#2}{#4}[#5]}%
   }%
\BeforeBeginEnvironment{#2}{%
\renewcommand*{\LWR@mdthisenv}{md#2}%
\begin{mdframed}[#1]}%
\AfterEndEnvironment{#2}{%
\end{mdframed}}%
}
```

File 210 **lwarp-memhfixc.sty**

§ 307 Package memhfixc

Pkg memhfixc memhfixc is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{memhfixc}[2013/05/30]
```

File 211 **lwarp-metalogo.sty**

§ 308 Package metalogo

(*Emulates or patches code by* Andrew Gilbert Moschou.)

Pkg metalogo metalogo is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{metalogo}[2010/05/29]
\newcommand\setlogokern[2]{}
```

```
\newcommand\setlogodrop[2][XeTeX]{}
\newcommand\setLaTeXa[1]{}
\newcommand\setLaTeXee[1]{}
\newcommand\seteverylogo[1]{}
\newcommand\everylogo[1]{}
```

File 212 **lwarp-mhchem.sty**

§ 309 Package

mhchem

(*Emulates or patches code by* Martin Hensel.)

Pkg mhchem

mhchem is patched for use by lwarp.

mhchem expressions are converted to SVG math. Inline expressions use hashed filenames to allow reuse, and assume that any mhchem options are global.

⚠ MathJax and mhchem

The MathJax mhchem extension is not yet used. If MathJax is used for math in the rest of the document, lwarp converts standalone mhchem expressions into SVG math images, but expressions inside math must be placed between `\displaymathother` and `\displaymathnormal`:

```
\displaymathother
\[ \ce{ . . . } \]     . . .     $ \ce { . . . } $
\displaymathnormal
```

⚠ nested math

When producing HTML output, lwarp does not support the use of nested dollar signs in mhchem expressions.

For some examples from the mhchem manual, change as follows:

```
$\ce{NaOH(aq,$\infty$)}$            % old
$\ce{NaOH(aq,\infty)}$              % new

$\ce{Fe(CN)_{$\frac{6}{2}$}$}$      % old
$\ce{Fe(CN)_{\frac{6}{2}}}$         % new

$\ce{NO_$x$}$                       % old
$\ce{NO_x}$                         % new

$\ce{NO_${x}$}$                     % old
$\ce{NO_{x}}$                       % new

$\ce{$cis${-}[PtCl2(NH3)2]}$        % old
$\ce{\mathit{cis}{-}[PtCl2(NH3)2]}$ % new
```

for HTML output:

```
\LWR@ProvidesPackagePass{mhchem}[2018/06/22]
```

The original definition of `\ce`:

```
\LetLtxMacro\LWR@mhchem@origce\ce
```

The new definition, called from the new \ce after math shift is set. The starred lateximage uses a hashed filename for the SVG image. The alt tag is set to the mhchem expression.

```
\newcommand{\LWR@mhchem@HTML@ce}[1]{%
\begin{lateximage}*[\textbackslash{}ce\{\LWR@HTMLsanitize{#1}\}]%
\LWR@mhchem@origce{#1}%
\end{lateximage}%
\endgroup%
\addtocounter{LWR@mhchem@cedepth}{-1}%
}
```

Only set math shift if outer depth:

```
\newcounter{LWR@mhchem@cedepth}
\setcounter{LWR@mhchem@cedepth}{0}
```

The new \ce. Sets math shift then continues.

```
\renewcommand{\ce}{%
\begingroup%
\ifnumequal{\value{LWR@mhchem@cedepth}}{0}{%
    \catcode`\$=3% math shift
}{}%
\addtocounter{LWR@mhchem@cedepth}{1}%
\LWR@mhchem@HTML@ce%
}
```

The original definition of \cesplit:

```
\LetLtxMacro\LWR@mhchem@origcesplit\cesplit
```

The new definition, called from the new \cesplit after math shift is set. The starred lateximage uses a hashed filename for the SVG image. The alt tag is set to the mhchem expression.

```
\newcommand*{\LWR@mhchem@HTML@cesplit}[2]
{%
\begin{lateximage}*[\textbackslash{}cesplit\{\LWR@HTMLsanitize{#2}\}]%
\LWR@mhchem@origcesplit{#1}{#2}%
\end{lateximage}%
\endgroup%
}
```

Only set math shift if outer depth:

```
\newcounter{LWR@mhchem@cesplitdepth}
\setcounter{LWR@mhchem@cesplitdepth}{0}
```

The new \cesplit. Sets math shift then continues.

```
\renewcommand{\cesplit}{%
\begingroup%
\ifnumequal{\value{LWR@mhchem@cesplitdepth}}{0}{%
```

```
    \catcode`\$=3% math shift
}{}%
\addtocounter{LWR@mhchem@cesplitdepth}{1}%
\LWR@mhchem@HTML@cesplit%
}
```

Resore originals inside a `lateximage`:

```
\appto\LWR@restoreorigformatting{%
\LetLtxMacro\ce\LWR@mhchem@origce%
\LetLtxMacro\cesplit\LWR@mhchem@origcesplit%
}
```

File 213 **lwarp-microtype.sty**

§ 310 Package

microtype

(*Emulates or patches code by* R Schlicht.)

Pkg microtype

microtype is pre-loaded by lwarp. All user options and macros are ignored and disabled.

for HTML output:

Discard all options for lwarp-microtype:

```
\LWR@ProvidesPackageDrop{microtype}[2018/01/14]
```

```
\DeclareDocumentCommand{\DeclareMicrotypeSet}{o m m}{}
\DeclareDocumentCommand{\UseMicrotypeSet}{o m}{}
\DeclareDocumentCommand{\DeclareMicrotypeSetDefault}{o m}{}
\DeclareDocumentCommand{\SetProtrusion}{o m m}{}
\DeclareDocumentCommand{\SetExpansion}{o m m}{}
\DeclareDocumentCommand{\SetTracking}{o m m}{}
\DeclareDocumentCommand{\SetExtraKerning}{o m m}{}
\DeclareDocumentCommand{\SetExtraSpacing}{o m m}{}
\DeclareDocumentCommand{\DisableLigatures}{o m}{}
\DeclareDocumentCommand{\DeclareCharacterInheritance}{o m m}{}
\DeclareDocumentCommand{\DeclareMicrotypeVariants}{m}{}
\DeclareDocumentCommand{\DeclareMicrotypeAlias}{m m}{}
\DeclareDocumentCommand{\LoadMicrotypeFile}{m}{}
\DeclareDocumentCommand{\DeclareMicrotypeBabelHook}{m m}{}
\DeclareDocumentCommand{\microtypesetup}{m}{}
\DeclareDocumentCommand{\microtypecontext}{m}{}
\DeclareDocumentCommand{\textmicrotypecontext}{m m}{#2}
\@ifpackageloaded{letterspace}{\let\MT@textls\relax}{%
\DeclareDocumentCommand{\lsstyle}{}{}
\DeclareDocumentCommand{\textls}{o +m}{}
\DeclareDocumentCommand{\lslig}{m}{#1}
}
\def\DeclareMicrotypeSet#1#{\@gobbletwo}
\def\DeclareMicrotypeVariants#1#{\@gobble}
\@onlypreamble\DeclareMicrotypeSet
\@onlypreamble\UseMicrotypeSet
\@onlypreamble\DeclareMicrotypeSetDefault
```

```
\@onlypreamble\DisableLigatures
\@onlypreamble\DeclareMicrotypeVariants
\@onlypreamble\DeclareMicrotypeBabelHook
```

File 214 **lwarp-midfloat.sty**

§ 311 Package midfloat

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg midfloat midfloat is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{midfloat}[2012/05/29]

\newenvironment{strip}[1][]{}{}
\newskip\stripsep
```

File 215 **lwarp-midpage.sty**

§ 312 Package midpage

Pkg midpage midpage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{midpage}[2009/09/03]

\newenvironment{midpage}
{\begin{BlockClass}[%
    \LWR@print@mbox{margin-top:6ex} ; \LWR@print@mbox{margin-bottom:6ex}%
]{midpage}}
{\end{BlockClass}}
```

File 216 **lwarp-morefloats.sty**

§ 313 Package morefloats

Pkg morefloats morefloats is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{morefloats}[2015/07/22]
```

File 217 **lwarp-moreverb.sty**

§ 314 Package moreverb

(*Emulates or patches code by* Robin Fairbairns.)

Pkg moreverb moreverb is supported with some patches.

for HTML output:

```
\begin{warpHTML}

\LWR@ProvidesPackagePass{moreverb}[2008/06/03]

\BeforeBeginEnvironment{verbatimtab}{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{Verbatim}%
}
\AfterEndEnvironment{verbatimtab}{%
\LWR@afterendverbatim{1}%
}


\LetLtxMacro\LWRMV@orig@verbatimtabinput\@verbatimtabinput

\renewcommand{\@verbatimtabinput}[2][]{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{Verbatim}%
\LWRMV@orig@verbatimtabinput[#1]{#2}%
\LWR@afterendverbatim{1}%
}

\BeforeBeginEnvironment{listing}{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{programlisting}%
}

\AfterEndEnvironment{listing}{%
\LWR@afterendverbatim{1}%
}

\BeforeBeginEnvironment{listingcont}{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{programlisting}%
}

\AfterEndEnvironment{listingcont}{%
\LWR@afterendverbatim{1}%
}


\LetLtxMacro\LWRMV@@listinginput\@listinginput

\renewcommand{\@listinginput}[3][]{
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{programlisting}%
\LWRMV@@listinginput[#1]{#2}{#3}%
\LWR@afterendverbatim{1}%
}


\renewenvironment*{boxedverbatim}
{
\LWR@forcenewpage
```

```
\LWR@atbeginverbatim{3}{boxedverbatim}%
\verbatim%
}
{
\endverbatim%
\LWR@afterendverbatim{1}%
}

\end{warpHTML}
```

File 218 **lwarp-mparhack.sty**

§ 315 Package mparhack

Pkg mparhack Ignored.

for HTML output: Discard all options for lwarp-mparhack:

```
\LWR@ProvidesPackageDrop{mparhack}[2005/04/17]
```

File 219 **lwarp-multicap.sty**

§ 316 Package multicap

Pkg multicap multicap is emualted.

for HTML output:

```
\LWR@ProvidesPackageDrop{multicap}[2002/05/04]

\newcommand*{\mfcaption}{\captionof{figure}}
\newcommand*{\mtcaption}{\captionof{table}}
\newcounter{mcapsize}
\newcounter{mcapskip}
\newlength{\abvmcapskip}
\newlength{\blwmcapskip}
```

File 220 **lwarp-multicol.sty**

§ 317 Package multicol

(*Emulates or patches code by* Frank Mittelbach.)

Pkg multicol multicol is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{multicol}[2018/12/27]
```

Multicols are converted into a 1–3 column display, browser-supported.

The optional multicols heading is placed inside a of class multicolsheading.

The content is placed inside a of class multicols.

```
\begin{warpHTML}
```

Env multicols * {⟨*numcols*⟩} [⟨*heading*⟩]

```
\NewDocumentEnvironment{multicols}{s m o}
```

HTML class to contain everything:

```
{
    \LWR@forcenewpage
    \BlockClass{multicols}
```

Optional HTML class for the heading:

```
    \IfValueT{#3}{\begin{BlockClass}{multicolsheading}#3\end{BlockClass}}%
```

Change \linewidth to compensate for expected size:

```
    \setlength{\linewidth}{\linewidth/#2}
```

Locally force any minipages to be fullwidth:

```
    \booltrue{LWR@forceminipagefullwidth}
}
```

When done with the environment, close the :

```
{\endBlockClass}
```

Emulated null functions which are not used in HTML:

```
\newcommand*{\columnbreak}{}
\newcommand*{\RLmulticolcolumns}{}
\newcommand*{\LRmulticolcolumns}{}

\newlength{\premulticols}
\newlength{\postmulticols}
\newlength{\multicolsep}
\newlength{\multicolbaselineskip}
\newlength{\multicoltolerance}
\newlength{\multicolpretolerance}
\newcommand*{\columnseprulecolor}{\normalcolor}
\newcounter{columnbadness}
\newcounter{finalcolumnbadness}
\newcounter{collectmore}
\newcounter{unbalance}
\newlength{\multicolovershoot}
\newlength{\multicolundershoot}

\NewDocumentCommand{\docolaction}{s o m m m}{%
    \IfValueTF{#2}{#2}{#3}%
}

\end{warpHTML}
```

File 221 **lwarp-multicolrule.sty**

§ 318 Package
# multicolrule

Pkg multicolrule multicolrule is ignored.

for HTML output:

```
\RequirePackage{multicol}

\LWR@ProvidesPackageDrop{multicolrule}[2019/01/01]

\newcommand*{\SetMCRule}[1]{}
\NewDocumentCommand{\DeclareMCRulePattern}{m m}{}
```

File 222 **lwarp-multirow.sty**

§ 319 Package
# multirow

(*Emulates or patches code by* Piet van Oostrum, Øystein Bache, Jerry Leichter.)

Pkg multirow multirow is emulated during HTML output, and used as-is while inside a `lateximage`.

In a `lateximage`, the original print-mode versions are temporarily restored by `\LWR@restoreorigformatting`.

See section 71.23 for the print-mode versions.

for HTML output: Remove the placeholder macro which was used if multirow was not loaded:

```
\LetLtxMacro\multirow\relax

\LWR@ProvidesPackagePass{multirow}[2018/08/03]
```

\LWR@multirowborder Set to `left` or `right` to create a thick border for the cell, for use by bigdelim:

```
\newcommand{\LWR@multirowborder}{}
```

§ 319.1 Multirow

\multirow `[`⟨*vpos*⟩`]` `{`⟨*numrows*⟩`}` `[`⟨*bigstruts*⟩`]` `{`⟨*width*⟩`}` `[`⟨*fixup*⟩`]` `{`⟨*text*⟩`}`

```
\NewDocumentCommand{\LWR@HTML@multirow}{O{c} m o m o +m}%
{%
\LWR@traceinfo{*** LWR@HTML@multirow #1 #2 #4}%
\LWR@maybenewtablerow%
\LWR@tabularleftedge%
```

Print the start of a new table data cell:

```
\LWR@htmltag{td rowspan="#2" %
```

The vertical alignment, if given:

```
\IfValueT{#1}{%
\ifstrequal{#1}{b}{style="\LWR@print@mbox{vertical-align:bottom}" }{}%
\ifstrequal{#1}{t}{style="\LWR@print@mbox{vertical-align:top}" }{}%
}%
```

The left/right border, if given:

```
\ifdefvoid{\LWR@multirowborder}{}{%
style="\LWR@print@mbox{border-\LWR@multirowborder:} 2px dotted black ; %
\LWR@print@mbox{padding-\LWR@multirowborder:} 2px" %
}%
```

A class adds the column spec and the rule:

```
class="td%
```

Append this column's spec:

```
\LWR@getexparray{LWR@tablecolspec}{\arabic{LWR@tableLaTeXcolindex}}%
```

If this column has a cmidrule, add "rule" to the end of the HTML class tag. Also add the vertical bar class.

```
\LWR@addcmidruletrim%
\LWR@addleftmostbartag%
\LWR@printbartag{\arabic{LWR@tableLaTeXcolindex}}%
"%


\LWR@tdstartstyles%
\LWR@addcmidrulewidth%
\LWR@addcdashline%
\LWR@addtabularrulecolors%
\LWR@tdendstyles%
}%
```

The column's < spec:

```
\LWR@getexparray{LWR@colbeforespec}{\arabic{LWR@tableLaTeXcolindex}}%
```

While printing the text, redefine \\ to generate a new line

```
\begingroup\LetLtxMacro{\\}{\LWR@endofline}#6\endgroup%
\LWR@stoppars%
\global\boolfalse{LWR@intabularmetadata}%
\renewcommand{\LWR@multirowborder}{}%
\LWR@traceinfo{*** LWR@HTML@multirow done}%
}%

\LWR@formatted{multirow}
```

§ 319.2 Combined multicolumn and multirow

⚠ \multicolumn & \multirow

lwarp does not support directly combining \multicolumn and \multirow. Use \multicolumnrow instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}
```

The two arguments for \multicolumn come first, followed by the five arguments for \multirow, many of which are optional, followed by the contents.

⚠ skipped cells

As per \multirow, skipped cells to the right of the \multicolumnrow statement are not included in the source code on the same line. On the following lines, \mcolrowcell

⚠ empty cells

must be used for each cell of each column and each row to be skipped:

```
. . . &  \multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}  & . . .
. . . &  \mcolrowcell          &          \mcolrowcell   & . . .
. . . &  \mcolrowcell          &          \mcolrowcell   & . . .
```

vposn

Note that recent versions of multirow include a new optional vposn argument.

\multicolumnrow {⟨*1:cols*⟩} {⟨*2:halign*⟩} [⟨*3:vpos*⟩] {⟨*4:numrows*⟩} [⟨*5:bigstruts*⟩] {⟨*6:width*⟩} [⟨*7:fixup*⟩] {⟨*8:text*⟩}

\@ifpackageloaded{multirow} determines if v2.0 or later of multirow was used, which included the \ProvidesPackage macro.

The HTML version follows.

\AtBeginDocument because the print version had to see if multirow was loaded before determining how to define \LWR@print@multicolumnrow.

```
\AtBeginDocument{
\NewExpandableDocumentCommand{\LWR@HTML@multicolumnrow}{m m O{} m O{} m O{} +m}{%
```

Figure out how many extra HTML columns to add for @ and ! columns:

```
\LWR@tabularhtmlcolumns{\arabic{LWR@tableLaTeXcolindex}}{#1}
```

Create the multicolumn/multirow tag:

```
\begingroup%
\LetLtxMacro{\\}{\LWR@endofline}%
\LWR@domulticolumn[#3][#4]{#1}{\arabic{LWR@tabhtmlcoltotal}}{#2}{#8}%
\endgroup%
```

Move to the next LaTeX column:

```
\addtocounter{LWR@tableLaTeXcolindex}{#1}%
\addtocounter{LWR@tableLaTeXcolindex}{-1}%
```

Skip any trailing @ or ! columns for this cell:

```
\global\booltrue{LWR@skipatbang}%
}

\LWR@expandableformatted{multicolumnrow}

}% \AtBeginDocument
```

File 223 **lwarp-multitoc.sty**

§ 320 Package multitoc

Pkg multitoc multitoc is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{multitoc}[1999/06/08]

\newcommand{\multicolumntoc}{2}
\newcommand{\multicolumnlot}{2}
\newcommand{\multicolumnlof}{2}
\newcommand*{\immediateaddtocontents}[2]{}
```

File 224 **lwarp-musicography.sty**

§ 321 Package musicography

(*Emulates or patches code by* Andrew A. Cashner.)

Pkg musicography musicography is patched for use by lwarp.

Images are used for the meter symbols, since the HTML fonts tend not to be the correct size. The HTML `alt` tag copies `C` and `3/2`, etc. Hashes are used for the meter images, which are then reused as necessary.

⚠ Note that browser support for musical symbols may be buggy. Copy/paste into a text editor works well.

for HTML output:

```
\LWR@ProvidesPackagePass{musicography}[2018/05/21]

\RenewDocumentCommand{\musSymbol}{ O{\musFont} m m m m }{%
\begin{lateximage}%
{#1\kern#2\raisebox{#3}{#5}\kern#4}%
\end{lateximage}%
}

\RenewDocumentCommand{\musStemmedNote}{ m }{%
\begin{lateximage}%
\musSymbol{0.05em}{0.5ex}{0.2em}{#1\musStem}%
\end{lateximage}%
}

```

```
\RenewDocumentCommand{\musFlaggedNote}{ m m }{%
\begin{lateximage}%
\musSymbol{0.05em}{0.5ex}{0pt}{#1\musStem}%
\musSymbol{0pt}{0pt}{0.9em}{#2}%
\end{lateximage}%
}

\RenewDocumentCommand{\musDottedNote}{ m }{%
\begin{lateximage}%
#1\musDot%
\end{lateximage}%
}

\RenewDocumentCommand{\musMeter}{ m m }{%
\begin{lateximage}*[#1/#2][#1#2]%
\musStack{#1}{#2}\kern0.05em%
\end{lateximage}%
}

\RenewDocumentCommand{\meterCplus}{ m }{%
\begin{lateximage}*[C#1]%
    \meterC{}\kern-0.7pt#1%
\end{lateximage}%
}

\RenewDocumentCommand{\meterC}{}{%
\begin{lateximage}*[C]%
\musSymbolMeter{\symbol{83}}%
\end{lateximage}%
}

\RenewDocumentCommand{\meterCutC}{}{%
\begin{lateximage}*[C|]%
\musSymbolMeter{\symbol{82}}%
\end{lateximage}%
}

\RenewDocumentCommand{\meterCThreeTwo}{}{%
\begin{lateximage}*[C3/2]%
\meterCplus{\musStack{3}{2}}%
\end{lateximage}%
}

\RenewDocumentCommand{\musFlat}       {}{\HTMLunicode{266D}}
\RenewDocumentCommand{\musDoubleFlat} {}{\HTMLunicode{1D12B}}
\RenewDocumentCommand{\musSharp}      {}{\HTMLunicode{266F}}
\RenewDocumentCommand{\musDoubleSharp}{}{\HTMLunicode{1D12A}}
\RenewDocumentCommand{\musNatural}    {}{\HTMLunicode{266E}}

\RenewDocumentCommand{\musWhole}{}{\HTMLunicode{1D15D}}
\RenewDocumentCommand{\musHalf}{}{\HTMLunicode{1D15E}}
\RenewDocumentCommand{\musQuarter}{}{\HTMLunicode{1D15F}}
\RenewDocumentCommand{\musEighth}{}{\HTMLunicode{1D160}}
\RenewDocumentCommand{\musSixteenth}{}{\HTMLunicode{1D161}}

```

```
\RenewDocumentCommand{\musWholeDotted}{}{\HTMLunicode{1D15D}\HTMLunicode{1D16D}}
\RenewDocumentCommand{\musHalfDotted}{}{\HTMLunicode{1D15E}\HTMLunicode{1D16D}}
\RenewDocumentCommand{\musQuarterDotted}{}{\HTMLunicode{1D15F}\HTMLunicode{1D16D}}
\RenewDocumentCommand{\musEighthDotted}{}{\HTMLunicode{1D160}\HTMLunicode{1D16D}}
\RenewDocumentCommand{\musSixteenthDotted}{}{\HTMLunicode{1D161}\HTMLunicode{1D16D}}
```

File 225 **lwarp-nameauth.sty**

§ 322 Package nameauth

(*Emulates or patches code by* Charles P. Schaum.)

Pkg nameauth nameauth is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{nameauth}[2017/03/22]
```

lwarp formatting is inserted in the following.

```
\renewcommand*\@nameauth@Hook[1]
{%
  \if@nameauth@Lock
    \@nameauth@InHooktrue%
    \protected@edef\test{#1}%
    \expandafter\@nameauth@TestDot\expandafter{\test}%
    \if@nameauth@InAKA
      \if@nameauth@AlwaysFormat
        \@nameauth@FirstFormattrue%
      \else
        \unless\if@nameauth@AKAFormat
        \@nameauth@FirstFormatfalse\fi
      \fi
      \if@nameauth@MainFormat
        \if@nameauth@FirstFormat
          \bgroup\NamesFormat{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \else
          \bgroup\MainNameHook{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \fi
      \else
        \if@nameauth@FirstFormat
          \bgroup\FrontNamesFormat{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \else
          \bgroup\FrontNameHook{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \fi
      \fi
    \else
```

```
    \if@nameauth@AlwaysFormat
      \@nameauth@FirstFormattrue%
    \fi
    \if@nameauth@MainFormat
      \if@nameauth@FirstFormat
        \bgroup\NamesFormat{%
          \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
        }\egroup%
      \else
        \bgroup\MainNameHook{%
          \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
        }\egroup%
      \fi
    \else
      \if@nameauth@FirstFormat
        \bgroup\FrontNamesFormat{%
          \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
        }\egroup%
      \else
        \bgroup\FrontNameHook{%
          \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
        }\egroup%
      \fi
    \fi
  \fi
  \@nameauth@FirstFormatfalse%
  \@nameauth@InHookfalse%
 \fi
}
```

File 226 **lwarp-nameref.sty**

§ 323 Package nameref

Pkg nameref nameref is emulated by lwarp.

for HTML output: Discard all options for lwarp-nameref:

```
\typeout{Using the lwarp html version of package ‘nameref’, discarding options.}
\typeout{    Are not using ProvidesPackage, so that other packages}
\typeout{    do not attempt to patch lwarp’s version of ‘nameref’.}
\DeclareOption*{}
\ProcessOptions\relax
```

File 227 **lwarp-natbib.sty**

§ 324 Package natbib

(*Emulates or patches code by* Patrick W. Daly.)

Pkg natbib natbib is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{natbib}[2010/09/13]
```

Replace math < and > with `\textless` and `\textgreater`:

A macro to compare:

```
\newcommand{\LWRNB@NAT@open}{$<$}
```

To patch `\NAT@open` and `\NAT@close`

```
\newcommand{\LWRNB@patchnatbibopenclose}{
\ifdefstrequal{\NAT@open}{\LWRNB@NAT@open}
{
    \renewcommand{\NAT@open}{\textless}
    \renewcommand{\NAT@close}{\textgreater}
}{}
}
```

Do it now in case `angle` was selected as an option:

```
\LWRNB@patchnatbibopenclose
```

Also patch `\setcitestyle` to patch after settings are made:

```
\let\LWRNB@origsetcitestyle\setcitestyle

\renewcommand{\setcitestyle}[1]{%
\LWRNB@origsetcitestyle{#1}%
\LWRNB@patchnatbibopenclose%
}
```

File 228 **lwarp-nccfancyhdr.sty**

§ 325 Package nccfancyhdr

(*Emulates or patches code by* Alexander I. Rozhenko.)

Pkg nccfancyhdr nccfancyhdr is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{nccfancyhdr}[2004/12/07]

\newcommand*{\headrulewidth}{}
\newcommand*{\footrulewidth}{}
\newcommand{\headstrutheight}{}
\newcommand{\footstrutheight}{}
\newcommand*{\headrule}{}
\newcommand*{\footrule}{}

\newdimen\headwidth
\newcommand*{\extendedheaders}{}
\newcommand*{\normalheaders}{}

```

```
\newcommand*{\fancyhead}[2][]{}
\newcommand*{\fancyfoot}[2][]{}
\newcommand*{\fancyhf}[2][]{}
\newcommand*{\fancypagestyle}[2]{}
\newcommand*{\lhead}[2][]{}
\newcommand*{\chead}[2][]{}
\newcommand*{\rhead}[2][]{}
\newcommand*{\lfoot}[2][]{}
\newcommand*{\cfoot}[2][]{}
\newcommand*{\rfoot}[2][]{}

\newcommand{\nouppercase}[1]{#1}

\NewDocumentCommand{\fancycenter}{o o m m m}{}

\NewDocumentCommand{\newpagestyle}{m o m}{}

\newcommand*{\iffloatpage}[2]{#2}
\newcommand*{\ifftopfloat}[2]{#2}
\newcommand*{\iffbotfloat}[2]{#2}
```

File 229 **lwarp-needspace.sty**

§ 326 Package needspace

(*Emulates or patches code by* Peter Wilson.)

Pkg needspace needspace is not used during HTML conversion.

for HTML output: Discard all options for lwarp-needspace:

```
\LWR@ProvidesPackageDrop{needspace}[2010/09/12]

\DeclareDocumentCommand{\needspace}{m}{}
\DeclareDocumentCommand{\Needspace}{s m}{}
```

File 230 **lwarp-nextpage.sty**

§ 327 Package nextpage

(*Emulates or patches code by* Peter Wilson.)

Pkg nextpage nextpage is nullified.

for HTML output: Discard all options for lwarp-nextpage.

```
\LWR@ProvidesPackageDrop{nextpage}[2009/09/03]

\DeclareDocumentCommand{\cleartoevenpage}{o}{}
\DeclareDocumentCommand{\movetoevenpage}{o}{}
\DeclareDocumentCommand{\cleartooddpage}{o}{}
```

```
\DeclareDocumentCommand{\movetooddpage}{o}{}
```

File 231 **lwarp-nicefrac.sty**

§ 328 Package nicefrac

(*Emulates or patches code by* Axel Reichert.)

Pkg nicefrac nicefrac is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{nicefrac}[1998/08/04]

\DeclareRobustCommand*{\LWR@HTML@@UnitsNiceFrac}[3][]{%
    {% localize font selection
        #1{%
            \LWR@textcurrentfont{%
                \InlineClass{numerator}{#2}%
                /%
                \InlineClass{denominator}{#3}%
            }%
        }%
    }%
}

\LWR@formatted{@UnitsNiceFrac}

\DeclareRobustCommand*{\LWR@HTML@@UnitsUglyFrac}[3][]{%
    {% localize font selection
        #1{\LWR@textcurrentfont{#2/#3}}%
    }%
}

\LWR@formatted{@UnitsUglyFrac}
```

For Mathjax:

```
\CustomizeMathJax{\newcommand{\nicefrac}[3][]{#2/#3}}
```

File 232 **lwarp-niceframe.sty**

§ 329 Package niceframe

Pkg niceframe niceframe is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{niceframe}% the original date is in yyyy/dd/mm format

\newcommand{\LWR@niceframe}[3]{
    \setlength{\LWR@templengthone}{#1}
    \begin{BlockClass}[max-width:\LWR@printlength{\LWR@templengthone}]{#3}
```

```
    #2
    \end{BlockClass}
}

\newcommand{\niceframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{niceframe}}
\newcommand{\curlyframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{curlyframe}}
\newcommand{\artdecoframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{artdecoframe}}

\newcommand{\generalframe}[9]{\LWR@niceframe{\textwidth}{#9}{generalframe}}
```

File 233 **lwarp-nomencl.sty**

§ 330 Package nomencl

(*Emulates or patches code by* Boris Veytsman, Bernd Schandl, Lee Netherton, CV Radhakrishnan.)

Pkg nomencl nomencl is patched for use by lwarp.

To process the HTML nomenclature:

```
makeindex <project>_html.nlo -s nomencl.ist -o <project>_html.nls
```

for HTML output:

```
\LWR@ProvidesPackagePass{nomencl}[2005/09/22]

\def\@@@nomenclature[#1]#2#3{%
 \def\@tempa{#2}\def\@tempb{#3}%
 \protected@write\@nomenclaturefile{}%
  {\string\nomenclatureentry{#1\nom@verb\@tempa @[{\nom@verb\@tempa}]%
      \begingroup\nom@verb\@tempb\protect\nomeqref{\theequation}%
        |nompageref}{\theLWR@previousautopagelabel}}%   lwarp
 \endgroup
 \@esphack}

\renewcommand*{\pagedeclaration}[1]{, \nameref{autopage-#1}}
```

File 234 **lwarp-nonfloat.sty**

§ 331 Package nonfloat

(*Emulates or patches code by* Kai Rascher.)

Pkg nonfloat nonfloat is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{nonfloat}[1999/07/05]

\LetLtxMacro\topcaption\caption
\newcommand{\figcaption}{\def\@captype{figure}\caption}
\newcommand{\tabcaption}{\def\@captype{table}\topcaption}
\newenvironment{narrow}[2]{}{}
```

File 235 **lwarp-nonumonpart.sty**

§ 332 Package nonumonpart

Pkg nonumonpart nonumonpart is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{nonumonpart}[2011/04/15]
```

File 236 **lwarp-nopageno.sty**

§ 333 Package nopageno

Pkg nopageno nopageno is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{nopageno}[1989/01/01]
```

File 237 **lwarp-notes.sty**

§ 334 Package notes

Pkg notes notes is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{notes}[2002/10/29]

\newcommand*{\LWR@notes@onenote}[2]{%
\newenvironment{#1}
    {
        \BlockClass{notes#1}
        \begin{BlockClass}{notesicon}\textcircled{~#2~}\end{BlockClass}
        \BlockClass{notescontents}
    }
    {\endBlockClass\endBlockClass}
}

\LWR@notes@onenote{importantnote}{!}

\LWR@notes@onenote{warningnote}{--}

\LWR@notes@onenote{informationnote}{i}
```

File 238 **lwarp-notespages.sty**

§ 335 Package notespages

Pkg notespages notespages is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{notespages}[2016/08/21]

\newcommand*{\npnotesname}{}
\newcommand*{\npnotestext}{}
\newcommand*{\remainingtextheight}{}
\newdimen\remainingtextheight
\newcommand*{\notestitletext}{}
\newcommand*{\notesareatext}{}
\newcommand*{\npnpinfo}[1]{}
\newcommand*{\tracingnpmarks}{}
\newcommand*{\notespage}[1][]{}
\newcommand*{\notespages}[1][]{}
\newcommand*{\notesfill}[1][]{}
\newcommand*{\setnotespages}[1]{}
\newcommand*{\definenotesoption}[2]{}
\newcommand{\definenotesstyle}[2]{}
\newcommand{\definetitlestyle}[2]{}
\newcommand{\nppatchchapter}[1]{}
\newcommand{\npunpatchchapter}{}
```

File 239 **lwarp-nowidow.sty**

§ 336 Package nowidow

(*Emulates or patches code by* Raphaël Pinson.)

Pkg nowidow nowidow is not used during HTML conversion.

Discard all options for lwarp-nowidow:

for HTML output:

```
\LWR@ProvidesPackageDrop{nowidow}[2011/09/20]
```

\nowidow [⟨*lines*⟩]

\setnowidow [⟨*lines*⟩]

```
\newcommand*{\nowidow}[1][]{}
\newcommand*{\setnowidow}[1][]{}
```

\noclub [⟨*lines*⟩]

\setnoclub [⟨*lines*⟩]

```
\newcommand*{\noclub}[1][]{}
\newcommand*{\setnoclub}[1][]{}
```

File 240 **lwarp-ntheorem.sty**

§ 337 Package ntheorem

(*Emulates or patches code by* Wolfgang May, Andreas Schedler.)

Pkg ntheorem ntheorem is patched for use by lwarp.

Table 15: Ntheorem package — css styling of theorems and proofs

Theorem: of class theorembody<theoremstyle>

Theorem Header: of class theoremheader<style>

where <theoremstyle> is plain, break, etc.

§ 337.1 Limitations

⚠ Font control This conversion is not total. Font control is via css, and the custom LaTeX font settings are ignored.

⚠ Equation numbering ntheorem has a bug with equation numbering in $\mathcal{AMS}$ environmentswhen the option thref is used. lwarp does not share this bug, so equations with \split, etc, are numbered correctly with lwarp's HTML output, but not with the print output. It is recommended to use cleveref instead of ntheorem's thref option.

§ 337.2 Options

Options amsthm or standard choose which set of theorems and proofs to initialize.

⚠ Disabled options The options thmmarks and amsmath are disabled, since they heavily modify the underlying math code. Theorem marks are emulated. The AMS-math modifications are not done.

Option thref is disabled because cleveref functions are used instead. \thref is emulated.

Option hyperref is disabled because lwarp emulated hyperref.

for HTML output: Some disabled options:

```
\DeclareOption{thref}{}


\newbool{LWR@ntheoremmarks}
\boolfalse{LWR@ntheoremmarks}

\DeclareOption{thmmarks}{
\booltrue{LWR@ntheoremmarks}
```

```
\newif\ifsetendmark\setendmarktrue
}


\newbool{LWR@ntheoremamsthm}
\boolfalse{LWR@ntheoremamsthm}

\DeclareOption{amsthm}{\booltrue{LWR@ntheoremamsthm}}


\DeclareOption{amsmath}{}
\DeclareOption{hyperref}{}

\LWR@ProvidesPackagePass{ntheorem}[2011/08/15]
```

§ 337.3 Remembering the theorem style

Storage for the style being used for new theorems.

```
\newcommand{\LWR@newtheoremstyle}{plain}


\AtBeginDocument{
\@ifpackageloaded{cleveref}{
\gdef\@thm#1#2#3{%
   \if@thmmarks
     \stepcounter{end\InTheoType ctr}%
   \fi
   \renewcommand{\InTheoType}{#1}%
   \if@thmmarks
     \stepcounter{curr#1ctr}%
     \setcounter{end#1ctr}{0}%
   \fi
   \refstepcounter[#1]{#2}%  <<< cleveref modification
   \theorem@prework
    \LWR@forcenewpage% lwarp
    \BlockClass{theorembody#1}%\LWR@thisthmstyle% lwarp
   \trivlist % latex's \trivlist, calling latex's \@trivlist unchanged
   \ifuse@newframeskips  % cf. latex.ltx for topsepadd: \@trivlist
     \ifthm@inframe
       \thm@topsep\theoreminframepreskipamount
       \thm@topsepadd\theoreminframepostskipamount
      \else
       \thm@topsep\theorempreskipamount
       \thm@topsepadd\theorempostskipamount
      \fi
    \else% oldframeskips
      \thm@topsep\theorempreskipamount
      \thm@topsepadd \theorempostskipamount
      \ifvmode\advance\thm@topsepadd\partopsep\fi
   \fi
   \@topsep\thm@topsep
   \@topsepadd\thm@topsepadd
   \advance\linewidth -\theorem@indent
   \advance\linewidth -\theorem@rightindent
   \advance\@totalleftmargin \theorem@indent
```

```
   \parshape \@ne \@totalleftmargin \linewidth
   \@ifnextchar[{\@ythm{#1}{#2}{#3}}{\@xthm{#1}{#2}{#3}}
}
}{% not @ifpackageloaded{cleveref}
\gdef\@thm#1#2#3{%
   \if@thmmarks
     \stepcounter{end\InTheoType ctr}%
   \fi
   \renewcommand{\InTheoType}{#1}%
   \if@thmmarks
     \stepcounter{curr#1ctr}%
     \setcounter{end#1ctr}{0}%
   \fi
   \refstepcounter{#2}%
   \theorem@prework
    \LWR@forcenewpage% lwarp
    \BlockClass{theorembody#1}%\LWR@thisthmstyle% lwarp
   \trivlist % latex's \trivlist, calling latex's \@trivlist unchanged
   \ifuse@newframeskips  % cf. latex.ltx for topsepadd: \@trivlist
     \ifthm@inframe
       \thm@topsep\theoreminframepreskipamount
       \thm@topsepadd\theoreminframepostskipamount
      \else
       \thm@topsep\theorempreskipamount
       \thm@topsepadd\theorempostskipamount
      \fi
    \else% oldframeskips
      \thm@topsep\theorempreskipamount
      \thm@topsepadd \theorempostskipamount
      \ifvmode\advance\thm@topsepadd\partopsep\fi
   \fi
   \@topsep\thm@topsep
   \@topsepadd\thm@topsepadd
   \advance\linewidth -\theorem@indent
   \advance\linewidth -\theorem@rightindent
   \advance\@totalleftmargin \theorem@indent
   \parshape \@ne \@totalleftmargin \linewidth
   \@ifnextchar[{\@ythm{#1}{#2}{#3}}{\@xthm{#1}{#2}{#3}}
}
}
}% AtBeginDocument
```

Patched to remember the style being used for new theorems:

```
\gdef\theoremstyle#1{%
   \@ifundefined{th@#1}{\@warning
          {Unknown theoremstyle `#1'. Using `plain'}%
          \theorem@style{plain}
            \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
            }%
      {
        \theorem@style{#1}
        \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
        }
}
```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```
\gdef\@xnthm#1#2[#3]{%
  \ifthm@tempif
     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
     \expandafter\@ifundefined{c@#1}%
        {\@definecounter{#1}}{}%
     \@newctr{#1}[#3]%
     \expandafter\xdef\csname the#1\endcsname{%
       \expandafter\noexpand\csname the#3\endcsname \@thmcountersep
          {\noexpand\csname\the\theoremnumbering\endcsname{#1}}}%
     \expandafter\gdef\csname mkheader@#1\endcsname
       {\csname setparms@#1\endcsname
        \@thm{#1}{#1}{#2}
        }%
     \global\@namedef{end#1}{\@endtheorem}
    \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
  \fi
}

\gdef\@ynthm#1#2{%
  \ifthm@tempif
     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
     \expandafter\@ifundefined{c@#1}%
        {\@definecounter{#1}}{}%
     \expandafter\xdef\csname the#1\endcsname
        {\noexpand\csname\the\theoremnumbering\endcsname{#1}}%
     \expandafter\gdef\csname mkheader@#1\endcsname
       {\csname setparms@#1\endcsname
        \@thm{#1}{#1}{#2}
        }%
     \global\@namedef{end#1}{\@endtheorem}
    \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
  \fi
}

\gdef\@othm#1[#2]#3{%
  \@ifundefined{c@#2}{\@nocounterr{#2}}%
   {\ifthm@tempif
     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
     \global\@namedef{the#1}{\@nameuse{the#2}}%
     \expandafter\protected@xdef\csname num@addtheoremline#1\endcsname{%
              \noexpand\@num@addtheoremline{#1}{#3}}%
     \expandafter\protected@xdef\csname nonum@addtheoremline#1\endcsname{%
              \noexpand\@nonum@addtheoremline{#1}{#3}}%
    \theoremkeyword{#3}%
    \expandafter\protected@xdef\csname #1Keyword\endcsname
             {\the\theoremkeyword}%
     \expandafter\gdef\csname mkheader@#1\endcsname
       {\csname setparms@#1\endcsname
                \@thm{#1}{#2}{#3}
        }%
     \global\@namedef{end#1}{\@endtheorem}
```

```
    \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
  \fi}
}
```

§ 337.4 HTML cross-referencing

Mimics a float by incrementing the float counter and generating an HTML anchor. These are used for list-of-theorem cross-references.

```
\newcommand{\LWR@inctheorem}{%
\addtocounter{LWR@thisautoid}{1}%
\LWR@stoppars%
\LWR@htmltag{a id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}"}\LWR@htmltag{/a}%
\LWR@startpars%
}
```

§ 337.5 \newtheoremstyle

The following are patched for CSS.

These were in individual files `thp.sty` for plain, `thmb.sty` for margin break, etc. They are gathered together here.

Each theorem is encased in a `BlockClass` environment of class `theorembody<style>`.

Each header is encased in an `\InlineClass` of class `theoremheader<style>`.

```
\gdef\newtheoremstyle#1#2#3{%
  \expandafter\@ifundefined{th@#1}%
   {\expandafter\gdef\csname th@#1\endcsname{%
    \def\@begintheorem####1####2{%
    \LWR@inctheorem% lwarp
    #2}%
    \def\@opargbegintheorem####1####2####3{%
    \LWR@inctheorem% lwarp
    #3}%
}%
}%
{\PackageError{\basename}{Theorem style #1 already defined}\@eha}
}
```

§ 337.6 Standard styles

```
\renewtheoremstyle{plain}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\ ##2\theorem@separator}]}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\ ##2\ (##3)\theorem@separator}]}

\renewtheoremstyle{break}%
  {\item[
    \InlineClass{theoremheaderbreak}{##1\ ##2\theorem@separator}\newline
    ]}%
  {\item[
    \InlineClass{theoremheaderbreak}%
```

```
        {##1\ ##2\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{change}%
  {\item[
    \InlineClass{theoremheaderchange}{##2\ ##1\theorem@separator}]}%
  {\item[
    \InlineClass{theoremheaderchange}{##2\ ##1\ (##3)\theorem@separator}]}

\renewtheoremstyle{changebreak}%
  {\item[
        \InlineClass{theoremheaderchangebreak}%
            {##2\ ##1\theorem@separator}\newline
    ]}%
  {\item[
        \InlineClass{theoremheaderchangebreak}%
            {##2\ ##1\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{margin}%
  {\item[
        \InlineClass{theoremheadermargin}{##2 \qquad ##1\theorem@separator}
    ]}%
  {\item[
     \InlineClass{theoremheadermargin}{##2 \qquad ##1\ (##3)\theorem@separator}
    ]}

\renewtheoremstyle{marginbreak}%
  {\item[
    \InlineClass{theoremheadermarginbreak}%
        {##2 \qquad ##1\theorem@separator}\newline
    ]}%
  {\item[
    \InlineClass{theoremheadermarginbreak}%
        {##2 \qquad ##1\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{nonumberplain}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\theorem@separator}]}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\ (##3)\theorem@separator}]}

\renewtheoremstyle{nonumberbreak}%
  {\item[
    \InlineClass{theoremheaderbreak}{##1\theorem@separator}\newline
    ]}%
  {\item[
    \InlineClass{theoremheaderbreak}{##1\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{empty}%
  {\item[]}%
  {\item[
    \InlineClass{theoremheaderplain}{##3}]}
```

```
\renewtheoremstyle{emptybreak}%
  {\item[]}%
  {\item[
    \InlineClass{theoremheaderplain}{##3}] \ \newline}
```

§ 337.7 Additional objects

The following manually adjust the css for the standard configuration objects which are not a purely plain style:

```
\ifbool{LWR@ntheoremamsthm}{}{%
```

Upright text via CSS:

```
    \newtheoremstyle{plainupright}%
    {\item[
        \InlineClass{theoremheaderplain}{##1\ ##2\theorem@separator}]}%
    {\item[
        \InlineClass{theoremheaderplain}{##1\ ##2\ (##3)\theorem@separator}]}
```

Upright text and small caps header via CSS:

```
    \newtheoremstyle{nonumberplainuprightsc}%
    {\item[
        \InlineClass{theoremheadersc}{##1\theorem@separator}]}%
    {\item[
        \InlineClass{theoremheadersc}{##1\ (##3)\theorem@separator}]}
}% not amsthm
```

§ 337.8 Renewed standard configuration

The following standard configuration is renewed using the new css:

```
\ifbool{LWR@ntheoremamsthm}{}{%
```

```
\ifx\thm@usestd\@undefined
\else
    \theoremnumbering{arabic}
    \theoremstyle{plain}
    \RequirePackage{latexsym}
    \theoremsymbol{\Box}
    \theorembodyfont{\itshape}
    \theoremheaderfont{\normalfont\bfseries}
    \theoremseparator{}
    \renewtheorem{Theorem}{Theorem}
    \renewtheorem{theorem}{Theorem}
    \renewtheorem{Satz}{Satz}
    \renewtheorem{satz}{Satz}
    \renewtheorem{Proposition}{Proposition}
    \renewtheorem{proposition}{Proposition}
    \renewtheorem{Lemma}{Lemma}
    \renewtheorem{lemma}{Lemma}
    \renewtheorem{Korollar}{Korollar}
```

```
    \renewtheorem{korollar}{Korollar}
    \renewtheorem{Corollary}{Corollary}
    \renewtheorem{corollary}{Corollary}

    \theoremstyle{plainupright}
    \theorembodyfont{\upshape}
    \theoremsymbol{\HTMLunicode{25A1}}% UTF-8 white box
    \renewtheorem{Example}{Example}
    \renewtheorem{example}{Example}
    \renewtheorem{Beispiel}{Beispiel}
    \renewtheorem{beispiel}{Beispiel}
    \renewtheorem{Bemerkung}{Bemerkung}
    \renewtheorem{bemerkung}{Bemerkung}
    \renewtheorem{Anmerkung}{Anmerkung}
    \renewtheorem{anmerkung}{Anmerkung}
    \renewtheorem{Remark}{Remark}
    \renewtheorem{remark}{Remark}
    \renewtheorem{Definition}{Definition}
    \renewtheorem{definition}{Definition}

    \theoremstyle{nonumberplainuprightsc}
    \theoremsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof
    \renewtheorem{Proof}{Proof}
    \renewtheorem{proof}{Proof}
    \renewtheorem{Beweis}{Beweis}
    \renewtheorem{beweis}{Beweis}
    \qedsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof

    \theoremsymbol{}
\fi
}% not amsthm
```

§ 337.9 amsthm option

Only if the amsthm option was given:

```
\ifbool{LWR@ntheoremamsthm}{

\gdef\th@plain{%
  \def\theorem@headerfont{\normalfont\bfseries}\itshape%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderplain}{##1\ ##2.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderplain}{##1\ ##2\ (##3).}
        ]}}

\gdef\th@nonumberplain{%
  \def\theorem@headerfont{\normalfont\bfseries}\itshape%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
```

```
      \item[
  \InlineClass{theoremheaderplain}{##1.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderplain}{##1\ (##3).}
        ]}}

\gdef\th@definition{%
  \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderdefinition}{##1\ ##2.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderdefinition}{##1\ ##2\ (##3).}
        ]}}

\gdef\th@nonumberdefinition{%
  \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderdefinition}{##1.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderdefinition}{##1\ (##3).}
        ]}}

\gdef\th@remark{%
  \def\theorem@headerfont{\itshape}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderremark}{##1\ ##2.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderremark}{##1\ ##2\ (##3).}
        ]}}

\gdef\th@nonumberremark{%
  \def\theorem@headerfont{\itshape}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderremark}{##1.}
        ]}%
```

```
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderremark}{##1\ (##3).}
        ]}}

\gdef\th@proof{%
  \def\theorem@headerfont{\normalfont\bfseries}\itshape%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderproof}{##1.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderproof}{##1\ (##3).}
        ]}}



\newcounter{proof}%
\if@thmmarks
    \newcounter{currproofctr}%
    \newcounter{endproofctr}%
\fi

\gdef\proofSymbol{\openbox}

\newcommand{\proofname}{Proof}

\newenvironment{proof}[1][\proofname]{
    \th@proof
    \def\theorem@headerfont{\itshape}%
    \normalfont
    \theoremsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof
    \@thm{proof}{proof}{#1}
}%
{\@endtheorem}

}{}% amsthm option
```

§ 337.10 Ending a theorem

Patched for css:

```
\let\LWR@origendtheorem\@endtheorem
\renewcommand{\@endtheorem}{%
\ifbool{LWR@ntheoremmarks}{%
    \ifsetendmark%
    \InlineClass{theoremendmark}{\csname\InTheoType Symbol\endcsname}%
    \setendmarkfalse%
    \fi%
}{}%
\LWR@origendtheorem% also does \@endtrivlist
```

```
\ifbool{LWR@ntheoremmarks}{\global\setendmarktrue}{}%
\endBlockClass%
}
```

§ 337.11 \NoEndMark

```
\gdef\NoEndMark{\global\setendmarkfalse}
```

§ 337.12 List-of

Redefined to reuse the float mechanism to add list-of-theorem links:

`\thm@thmline` {⟨*1: printed type*⟩} {⟨*2: #*⟩} {⟨*3: optional*⟩} {⟨*4: page*⟩}

```
\renewcommand{\thm@@thmline@noname}[4]{%
\hypertocfloat{1}{theorem}{thm}{#2 #3}{}%
}

\renewcommand{\thm@@thmline@name}[4]{%
\hypertocfloat{1}{theorem}{thm}{#1 #2 #3}{}%
}
```

This was redefined by ntheorem when loaded, so it is now redefined for lwarp:

```
\def\thm@@thmline{\thm@@thmline@name}
```

Patch for css:

```
\def\listtheorems#1{
\LWR@htmlelementclass{nav}{lothm}%
\begingroup
\c@tocdepth=-2%
\def\thm@list{#1}\thm@processlist
\endgroup
\LWR@htmlelementclassend{nav}{lothm}%
}
```

§ 337.13 Symbols

Proof QED symbol:

```
\newcommand{\qed}{\qquad\the\qedsymbol}

\AtBeginDocument{
\@ifundefined{LWR@orig@openbox}{
\LetLtxMacro\LWR@orig@openbox\openbox
\LetLtxMacro\LWR@orig@blacksquare\blacksquare
\LetLtxMacro\LWR@orig@Box\Box

\def\openbox{\text{\HTMLunicode{25A1}}}% UTF-8 white box
\def\blacksquare{\text{\HTMLunicode{220E}}}% UTF-8 end-of-proof
\def\Box{\text{\HTMLunicode{25A1}}}% UTF-8 white box

\appto\LWR@restoreorigformatting{%
```

```
\LetLtxMacro\openbox\LWR@orig@openbox%
\LetLtxMacro\blacksquare\LWR@orig@blacksquare%
\LetLtxMacro\Box\LWR@orig@Box%
}% appto
}{}% @ifundefined
}% AtBeginDocument
```

§ 337.14 Cross-referencing

`\thref {`⟨*label*⟩`}`

```
\newcommand*{\thref}[1]{\cref{#1}}%
```

File 241 **lwarp-octave.sty**

§ 338 Package octave

(*Emulates or patches code by* Andrew A. Cashner.)

Pkg octave octave is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{octave}[2017/10/31]
```

Remove the leading 1pt kern:

```
\RenewDocumentCommand{\@PrintTicks}{ m }{%
\kern-1pt%  lwarp
\@TickNum = #1%
\loop
\@Tick{}%
\advance\@TickNum by -1
\ifnum\@TickNum > 0
\repeat
}
```

Use unicode for the prime character:

```
\RenewDocumentCommand{\@Tick}{}{\HTMLunicode{2032}}
```

Catch the inline font:

```
\RenewDocumentCommand{\pitch}{ m o m }{%
\if@OctaveNumber%
{%
    \pitchfont{%
        \LWR@textcurrentfont{%  lwarp
            \MakeUppercase{#1}%
            \IfValueTF{#2}{#2}{}\textsubscript{#3}%
        }%
    }%
}%
\else%
```

```
{%
    \pitchfont{%
        \LWR@textcurrentfont{%  lwarp
            \@GetOctaveTick{#1}[#2]{#3}%
        }%
    }%
}%
\fi%
}
```

The original was hard to adapt to lwarp's handling of &.

```
\StartDefiningTabulars
\renewcommand{\octavetable}{%
\begin{tabular}{ll}
\octaveprimes \pitch{C}{0} & \octavenumbers \pitch{C}{0} \\
\octaveprimes \pitch{C}{1} & \octavenumbers \pitch{C}{1} \\
\octaveprimes \pitch{C}{2} & \octavenumbers \pitch{C}{2} \\
\octaveprimes \pitch{C}{3} & \octavenumbers \pitch{C}{3} \\
\octaveprimes \pitch{C}{4} & \octavenumbers \pitch{C}{4} \\
\octaveprimes \pitch{C}{5} & \octavenumbers \pitch{C}{5} \\
\octaveprimes \pitch{C}{6} & \octavenumbers \pitch{C}{6} \\
\octaveprimes \pitch{C}{7} & \octavenumbers \pitch{C}{7} \\
\end{tabular}
}
\StopDefiningTabulars
```

File 242 **lwarp-overpic.sty**

§ 339 Package

overpic

(*Emulates or patches code by* Rolf Niepraschk.)

Pkg overpic overpic is patched for use by lwarp.

⚠ scaling The macros \overpicfontsize and \overpicfontskip are used during HTML generation. These are sent to \fontsize to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the overpic and Overpic environments.

See section 83.2 for the print-mode version of \overpicfontsize and \overpicfontskip.

for HTML output:

```
\LWR@ProvidesPackagePass{overpic}[2017/10/06]
```

```
\newcommand*{\overpicfontsize}{12}
\newcommand*{\overpicfontskip}{14}

\BeforeBeginEnvironment{overpic}{%
    \begin{lateximage}%
    \fontsize{\overpicfontsize}{\overpicfontskip}%
    \selectfont%
}
```

```
10
11 \AfterEndEnvironment{overpic}{\end{lateximage}}
12
13 \BeforeBeginEnvironment{Overpic}{%
14     \begin{lateximage}%
15     \fontsize{\overpicfontsize}{\overpicfontskip}%
16     \selectfont%
17 }
18
19 \AfterEndEnvironment{Overpic}{\end{lateximage}}
```

File 243 **lwarp-pagegrid.sty**

§ 340 Package pagegrid

Pkg pagegrid pagegrid is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{pagegrid}[2016/05/16]

2 \newcommand*{\pagegridsetup}[1]{}
```

File 244 **lwarp-pagenote.sty**

§ 341 Package pagenote

Pkg pagenote pagenote works as-is, but the page option is disabled.

for HTML output:

```
1 \DeclareOption{page}{}
2 \LWR@ProvidesPackagePass{pagenote}[2009/09/03]
```

File 245 **lwarp-pagesel.sty**

§ 342 Package pagesel

Pkg pagesel pagesel is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{pagesel}[2016/05/16]
```

File 246 **lwarp-paralist.sty**

§ 343 Package paralist

(*Emulates or patches code by* Bernd Schandl.)

Pkg paralist paralist is supported with minor changes.

for HTML output:

```
\LWR@ProvidesPackagePass{paralist}[2017/01/22]
```

The compact environments are identical to the regular ones:

```
\LetLtxMacro\compactitem\itemize
\LetLtxMacro\compactenum\enumerate
\LetLtxMacro\compactdesc\description
\LetLtxMacro\endcompactitem\enditemize
\LetLtxMacro\endcompactenum\endenumerate
\LetLtxMacro\endcompactdesc\enddescription
```

For the inline environments, revert `\item` to its original print-mode version:

```
\AtBeginEnvironment{inparaitem}{\LetLtxMacro\item\LWR@origitem}
\AtBeginEnvironment{inparaenum}{\LetLtxMacro\item\LWR@origitem}
\AtBeginEnvironment{inparadesc}{\LetLtxMacro\item\LWR@origitem}
```

Manual formatting of the description labels:

```
\def\paradescriptionlabel#1{{\normalfont\textbf{#1}}}
```

File 247 **lwarp-parnotes.sty**

§ 344 Package

parnotes

(*Emulates or patches code by* Chelsea Hughes.)

Pkg parnotes parnotes is supported with some patches.

for HTML output:

```
\LWR@ProvidesPackagePass{parnotes}[2016/08/15]

\long\def\PN@parnote@real#1#2{%
    \parnotemark{#1}%
    % Unless this is the first parnote in \PN@text, add a separator first
    \unless\ifx\PN@text\@empty\g@addto@macro\PN@text{\parnoteintercmd}\fi
    % Redefine \@currentlabel to the parnote label, so \label works
    \g@addto@macro\PN@text{%
%         \phantomsection%
        \def\@currentlabel{#1}%
        \def\cref@currentlabel{%        lwarp
            [parnotemark][\arabic{parnotemark}][]\theparnotemark%
        }%
    }%
    \g@addto@macro\PN@text{%
        \LWR@textcurrentfont{%          lwarp
            \parnotemark{#1}\nolinebreak\thinspace#2%
        }%
    }%
}

```

```
\def\PN@parnotes@real{%
    % We call \par later, so this avoids recursion with \PN@parnotes@auto
    \PN@inparnotestrue
    \unless\ifvmode\par\fi
    % Avoid page breaks between a paragraph and its parnotes
    \nopagebreak\addvspace{\parnotevskip}%
    \LWR@forcenewpage%                  lwarp
    \begin{BlockClass}{footnotes}%      lwarp
    {\parnotefmt{\PN@text}\par}%
    \end{BlockClass}%                   lwarp
    \global\def\PN@text{}%
    \addvspace{\parnotevskip}%
    %
    % These can be enabled or disabled by package options
    %
    \PN@disable@indent
    \PN@reset@optional
    \PN@inparnotesfalse
}

\AtBeginDocument{
\crefname{parnotemark}{paragraph note}{paragraph notes}%
\Crefname{parnotemark}{Paragraph note}{Paragraph notes}
}
```

File 248 **lwarp-parskip.sty**

§ 345 Package parskip

Pkg parskip parskip is ignored.

for HTML output: Discard all options for lwarp-parskip.

```
\LWR@ProvidesPackageDrop{parskip}[2001/04/09]
```

File 249 **lwarp-pbox.sty**

§ 346 Package pbox

(*Emulates or patches code by* Simon Law.)

Pkg pbox pbox is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{pbox}[2011/12/07]

\NewDocumentCommand{\pbox}{O{t} O{} O{t} m +m}{%
\global\booltrue{LWR@minipagefullwidth}%
\parbox[#1][#2][#3]{#4}{#5}%
}

```

```
\newcommand{\settominwidth}[3][\columnwidth]{%
\settowidth{#2}{#3}%
}

\newcommand{\widthofpbox}[1]{%
\widthof{#1}%
}
```

File 250 **lwarp-pdfcomment.sty**

§ 347 Package pdfcomment

Pkg pdfcomment pdfcomment is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfcomment}[2016/06/13]

\newenvironment{pdfsidelinecomment}[2][]{}{}
\newcommand{\pdfcomment}[2][]{}
\newcommand{\pdfmargincomment}[2][]{}
\newcommand{\pdfmarkupcomment}[3][]{#2}
\newcommand{\pdffreetextcomment}[2][]{}
\newcommand{\pdfsquarecomment}[2][]{}
\newcommand{\pdfcirclecomment}[2][]{}
\newcommand{\pdflinecomment}[2][]{}
\newcommand{\pdftooltip}[3][]{#2}
\newcommand{\pdfcommentsetup}[2][]{}
\newcommand{\listofpdfcomments}[1][]{}
\newcommand{\setliststyle}[1]{}
\newcommand{\defineliststyle}[2]{}
\newcommand{\defineavatar}[2]{}
\newcommand{\definestyle}[2]{}
```

File 251 **lwarp-pdflscape.sty**

§ 348 Package pdflscape

Pkg pdflscape pdflscape is ignored.

for HTML output: Discard all options for lwarp-pdflscape:

```
\LWR@ProvidesPackageDrop{pdflscape}[2016/05/14]
```

File 252 **lwarp-pdfmarginpar.sty**

§ 349 Package pdfmarginpar

Pkg pdfmarginpar pdfmarginpar is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfmarginpar}[2011/08/05]

\newcommand{\pdfmarginpar}[2][]{}
\newcommand{\pdfmarginparset}[1]{}
```

File 253 **lwarp-pdfpages.sty**

§ 350 Package

pdfpages

(*Emulates or patches code by* Andreas Matthias.)

Pkg pdfpages

pdfpages is patched for use by lwarp.

Option `link` and `linkname` work:

```
\hyperlink{<filename>.pdf.<pagenubmer}}{some text}
\hyperlink{<linkname>.<pagenubmer}}{some text}
```

Options which make no sense in HTML are disabled.

for HTML output:

```
\LWR@ProvidesPackagePass{pdfpages}[2017-10-31]
```

Disable option which have no meaning for HTML output:

```
\define@key{pdfpages}{fitpaper}[false]{}
\define@key{pdfpages}{landscape}[false]{}
\define@key{pdfpages}{openright}[false]{}
\define@key{pdfpages}{signature}{}
\define@key{pdfpages}{signature*}{}
\define@key{pdfpages}{booklet}[false]{}
\define@key{pdfpages}{rotateoversize}[false]{}
\define@key{pdfpages}{doublepages}[false]{}
\define@key{pdfpages}{doublepagestwist}[false]{}
\define@key{pdfpages}{doublepagestwistodd}[false]{}
\define@key{pdfpages}{doublepagestwist*}[false]{}
\define@key{pdfpages}{doublepagestwistodd*}[false]{}
\define@key{pdfpages}{duplicatepages}[2]{}
\define@key{pdfpages}{thread}[false]{}
\define@key{pdfpages}{threadname}{}
\define@key{pdfpages}{linkfit}{}
\define@key{pdfpages}{linktodoc}[false]{}
\define@key{pdfpages}{linktodocfit}{}
\define@key{pdfpages}{linkfilename}{}
\define@key{pdfpages}{survey}[false]{}
\define@key{pdfpages}{survey-nolink}[false]{}
\define@key{pdfpages}{newwindow}[false]{}
```

Use print mode while measuring the page numbers:

```
\xpretocmd{\AM@getpagecount}{\LWR@restoreorigformatting}{}{}
```

Emulate a bit of eso-pic:

```
\newif\ifESO@texcoord

\newcommand{\ESO@HookIIBG}{}

\renewcommand{\AM@AddToShipoutPicture}{\g@addto@macro\ESO@HookIIBG}

\renewcommand{\ClearShipoutPicture}{}
```

\LWR@esopic@newpage At each \newpage.

```
\newcommand*{\LWR@esopic@newpage}{%
```

Is there something to draw?

```
\ifdefvoid{\ESO@HookIIBG}%
{}%
{%
```

If the link option was specified, add a hyper taraget:

```
    \ifAM@link%
        \hypertarget{\AM@linkname.\AM@page}{}%
    \fi%
```

Draw inside a picture environment of the size of a virtual page:

```
    \begingroup%
    \setlength{\unitlength}{1in}%
    \begin{picture}(8,10.5)%
    \ESO@HookIIBG%
    \end{picture}%
    \endgroup%
    \global\let\ESO@HookIIBG\@empty%
}
}
```

\AM@output Patched to use \LWR@esopic@newpage.

```
\xpatchcmd{\AM@output}
    {\newpage}
    {\LWR@esopic@newpage}
    {}
    {\LWR@patcherror{pdfpages}{AM@output-1}}

\xpatchcmd{\AM@output}
    {\newpage}
    {\LWR@esopic@newpage}
    {}
    {\LWR@patcherror{pdfpages}{AM@output-2}}

\xpatchcmd{\AM@output}
    {\newpage}
    {\LWR@esopic@newpage}
    {}
    {\LWR@patcherror{pdfpages}{AM@output-3}}
```

\includepdf Patched to set a reasonable paper size.

```
\xpretocmd{\includepdf}{%
    \begingroup%
    \setlength{\paperwidth}{8in}%
    \setlength{\paperheight}{10.5in}%
}{}{}

\xapptocmd{\includepdf}{%
    \endgroup%
}{}{}
```

\includepdfmerge Patched to set a reasonable paper size.

```
\xpretocmd{\includepdfmerge}{%
    \begingroup%
    \setlength{\paperwidth}{8in}%
    \setlength{\paperheight}{10.5in}%
}{}{}

\xapptocmd{\includepdfmerge}{%
    \endgroup%
}{}{}
```

\AM@hyper@begin@i Hyper links are created by \LWR@esopic@newpage, so don't create them here:

```
\renewcommand{\AM@hyper@begin@i}{}
```

File 254 **lwarp-pdfprivacy.sty**

§ 351 Package pdfprivacy

Pkg pdfprivacy pdfprivacy is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfprivacy}[2017/12/03]
```

File 255 **lwarp-pdfrender.sty**

§ 352 Package pdfrender

Pkg pdfrender pdfrender is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfrender}[2016/05/17]

\newcommand*{\pdfrender}[1]{}
\newcommand{\textpdfrender}[2]{#2}
```

File 256 **lwarp-pdfsync.sty**

§ 353 Package pdfsync

(*Emulates or patches code by* J. Laurens.)

Pkg pdfsync Emulated.

for HTML output: Discard all options for lwarp-pdfsync:

```
\LWR@ProvidesPackageDrop{pdfsync}[2008/01/26]

\newcommand*{\pdfsync}{}
\newcommand*{\pdfsyncstart}{}
\newcommand*{\pdfsyncstop}{}
```

File 257 **lwarp-pdftricks.sty**

§ 354 Package pdftricks

(*Emulates or patches code by* C. V. Radhakrishnan, C. V. Rajagopal, Antoine Chambert-Loir.)

Pkg pdftricks pdftricks is patched for use by lwarp.

⚠ convert image files The pdftricks image files <jobname>-fig*.pdf must be converted to .svg, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

Enter ⇒ **lwarpmk pdftosvg <jobname>-fig*.pdf**

for HTML output:

```
\LWR@ProvidesPackagePass{pdftricks}[2003/08/10]
```

Reuse the print-mode images:

```
\def\PDFTfigname{\BaseJobname-fig\thepsfig}
```

If the .pdf images have not yet been converted to .svg then an error about a missing file will occur. Warn the user to convert the images.

```
\PackageWarning{lwarp-pdftricks}{
When the pdftricks images change,
remember to convert PDF images to SVG using 'lwarpmk pdftosvg *-fig.pdf',
}

\AfterEndDocument{\typeout{***}}
\AfterEndDocument{\typeout{*** Note: If pdftricks images are not found, new, or updated,}}
\AfterEndDocument{\typeout{*** \space use 'lwarpmk pdftosvg \BaseJobname-fig*.pdf'}}
\AfterEndDocument{\typeout{***}}
```

File 258 **lwarp-pdfx.sty**

§ 355 Package pdfx

Pkg pdfx pdfx is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfx}[2017/05/18]
```

File 259 **lwarp-perpage.sty**

§ 356 Package perpage

(*Emulates or patches code by* David Kastrup.)

Pkg perpage perpage is mostly ignored, but support is added for footnote counters.

There is no page number in HTML, so most counters are not reset. If the document redefines `\the<countername>` to include `\theperpage`, it is necessary to place that redefininition inside a `warpprint` environment to avoid modifying the HTML defintions.

`\AddAbsoluteCounter` must not be inside `warpprint`, as the counter must be added for HTML also, although it is not incremented.

footnote numbering To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For bigfoot, manyfoot, or perpage:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by `FootnoteDepth`, which is not necessarily by HTML page. This is recommended for `\alph`, `\Alph`, or `\fnsymbol` footnotes, due to the limited number of symbols which are available.

for HTML output:

```
\LWR@ProvidesPackageDrop{perpage}[2014/10/25]

\newcommand\AddAbsoluteCounter[1]
{
    \@ifundefined{c@abs#1}{%
        \expandafter\newcount\csname c@abs#1\endcsname
        \global\value{abs#1}\@ne
%         \global\expandafter\let\csname cl@abs#1\endcsname\@empty
        \expandafter\xdef\csname theabs#1\endcsname{%
%             \noexpand\number \csname c@abs#1\endcsname
```

```
        }%
%         \global\@namedef{c@pabs@#1}{\pp@cl@begin
%         \stepcounter{abs#1}%
%         \pp@cl@end}%
%         \@addtoreset{pabs@#1}{#1}
    }
    {}
}

\AddAbsoluteCounter{page}
\def\theabspage{1}

\newcommand*\MakePerPage[2][1]{%
    \ifltxcounter{#2Reset}{%
        \setcounter{#2Reset}{#1}%
    }{

}%
}

\newcommand*\MakeSorted[1]{}

\newcommand*\MakeSortedPerPage[2][1]{%
    \ifltxcounter{#2Reset}{%
        \setcounter{#2Reset}{#1}%
    }{
}%
}

\newcommand*{\theperpage}{1}
```

File 260 **lwarp-pfnote.sty**

§ 357 Package

pfnote

Pkg pfnote pfnote is emulated.

pfnote

⚠ pfnote numbers While emulating pfnote, lwarp is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. lwarp therefore uses continuous footnote numbering even for pfnote.

for HTML output:

```
\LWR@ProvidesPackageDrop{pfnote}[1999/07/14]
```

File 261 **lwarp-phfqit.sty**

§ 358 Package

phfqit

(*Emulates or patches code by* PHILIPPE FAIST.)

Pkg phfqit phfqit is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{phfqit}[2017/08/16]

\LetLtxMacro\LWR@origbitstring\bitstring

\renewcommand\bitstring[1]{%
\InlineClass[%
    text-decoration: overline underline ;
]{bitstring}{#1}%
% \phfqit@bitstring{#1}%
}

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\bitstring\LWR@origbitstring%
}
```

File 262 **lwarp-pifont.sty**

§ 359 Package pifont

(*Emulates or patches code by* Walter Schmidt.)

Pkg pifont pifont is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

for HTML output:

```
\LWR@ProvidesPackagePass{pifont}[2005/04/12]

\renewcommand{\Pisymbol}[2]{%
    \begin{lateximage}*[(Pisymbol)][pisymbol#1#2]%
    {\Pifont{#1}\char#2}%
    \end{lateximage}%
}

\newcommand{\LWR@HTML@Pifill}[2]{
    \Pisymbol{#1}{#2} \Pisymbol{#1}{#2} \Pisymbol{#1}{#2}
}
\LWR@formatted{Pifill}

\newcommand{\LWR@HTML@Piline}[2]{%
    \par\noindent\hspace*{0.5in}
    \Pifill{#1}{#2} \Pifill{#1}{#2} \Pifill{#1}{#2}
}
\LWR@formatted{Piline}
```

File 263 **lwarp-placeins.sty**

§ 360 Package placeins

(*Emulates or patches code by* Donald Arseneau.)

Pkg placeins placeins is not used during HTML conversion.

Discard all options for lwarp-placeins:

for HTML output:

```
\LWR@ProvidesPackageDrop{placeins}[2005/04/18]
\newcommand*{\FloatBarrier}{}
```

File 264 **lwarp-plarydshln.sty**

§ 361 Package plarydshln

Pkg plarydshln plarydshln is emulated by lwarp-arydshln.

for HTML output:

```
\LWR@ProvidesPackageDrop{plarydshln}[2018/10/20]
\LWR@origRequirePackage{lwarp-arydshln}
```

File 265 **lwarp-plext.sty**

§ 362 Package plext

Pkg plext plext is preloaded by jtarticle and related classes.

for HTML output:

```
\LWR@loadbefore{plext}

\LWR@ProvidesPackagePass{plext}[2017/07/21]

\let\tate\relax

\DeclareExpandableDocumentCommand{\rensuji}{s o m}{#3}

% \layoutfloat(width,height)[pos]#4
\DeclareDocumentCommand{\layoutfloat}{d() o m}{}

% \DeclareLayoutCaption{type} <dir>(width)[pos1pos2]
\DeclareDocumentCommand{\DeclareLayoutCaption}{m d<> d() o}{}

\LetLtxMacro\pcaption\caption

% \layoutcaption<dir>(width)[pos]
\DeclareDocumentCommand{\layoutcaption}{d<> d() o}{}

\let\captiondir\relax
```

Add the optional <t/y> direction:

```
\RenewDocumentEnvironment{LWR@HTML@minipage}{d<> O{t} O{} O{t} m}
    {\LWR@HTML@sub@minipage{#2}{#3}{#4}{#5}}
```

```
    {\endLWR@HTML@sub@minipage}

\RenewDocumentCommand{\LWR@HTML@parbox}{d<> O{t} O{} O{t} m +m}
{
\LWR@traceinfo{parbox of width #4}%
\begin{minipage}[#2][#3][#4]{#5}%
#6
\end{minipage}%
}

% \pbox <t/y> [width] [l/r] {contents}
\RenewDocumentCommand{\pbox}{d<> O{0pt} O{c} m}{%
\global\booltrue{LWR@minipagefullwidth}%
\parbox{#2}{#4}%
}
```

picture, as modified by pext, is encapsulated by the lwarp core.

File 266 **lwarp-plextarydshln.sty**

§ 363 Package plextarydshln

Pkg plextarydshln plextarydshln is emulated by lwarp-arydshln.

for HTML output:

```
\LWR@ProvidesPackageDrop{plextarydshln}[2018/10/20]

\LWR@origRequirePackage{lwarp-arydshln}
```

File 267 **lwarp-plextcolortbl.sty**

§ 364 Package plextcolortbl

Pkg plextcolortbl plextcolortbl is emulated by lwarp-colortbl.

for HTML output:

```
\LWR@ProvidesPackageDrop{plextcolortbl}[2018/09/19]

\LWR@origRequirePackage{lwarp-colortbl}
```

File 268 **lwarp-prelim2e.sty**

§ 365 Package prelim2e

(*Emulates or patches code by* Martin Schröder.)

Pkg prelim2e Emulated.

for HTML output:

Discard all options for lwarp-prelim2e:

```
\LWR@ProvidesPackageDrop{prelim2e}[2009/05/29]

\newcommand{\PrelimText}{}
\newcommand{\PrelimTextStyle}{}
\newcommand{\PrelimWords}{}
```

File 269 **lwarp-prettyref.sty**

§ 366 Package prettyref

(*Emulates or patches code by* Kevin S. Ruland.)

Pkg prettyref prettyref is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{prettyref}[1998/07/09]

\newrefformat{fig}{Figure \ref{#1}}
\newrefformat{tab}{Table \ref{#1}}
```

File 270 **lwarp-preview.sty**

§ 367 Package preview

Pkg preview preview is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{preview}[2017/04/24]

\newenvironment{preview}{}{}
\newenvironment{nopreview}{}{}
\NewDocumentCommand{\PreviewMacro}{s o o +m}{}
\NewDocumentCommand{\PreviewEnvironment}{s o o +m}{}
\newcommand{\PreviewSnarfEnvironment}[2][]{}
\NewDocumentCommand{\PreviewOpen}{s o}{}
\NewDocumentCommand{\PreviewClose}{s o}{}
\let\ifPreview\iffalse% \fi for syntax highlighting
```

File 271 **lwarp-psfrag.sty**

§ 368 Package psfrag

(*Emulates or patches code by* Michael C. Grant, David Carlisle.)

Pkg psfrag psfrag is patched for use by lwarp.

⚠ use psfrags The psfrags environment is modified to use lateximage to encapsulate the image.

Always use a psfrags environment to contain any local \psfrag macros and the associated \includegraphics or \epsfig calls. Outside of a psfrags environment, psfrags adjustments will not be seen by lwarp.

⚠ Tip: Use a mono-spaced font for the tags in the EPS file.

for HTML output:

```
\LWR@ProvidesPackagePass{psfrag}[1998/04/11]
```

A lateximage captures the modified image from the document.

```
\BeforeBeginEnvironment{psfrags}{%
    \begin{lateximage}[(-psfrags-~\packagediagramname)]%
}

\AfterEndEnvironment{psfrags}{\end{lateximage}}
```

File 272 **lwarp-psfragx.sty**

§ 369 Package psfragx

(*Emulates or patches code by* PASCAL KOCKAERT.)

Pkg psfragx psfragx is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{psfragx}[2012/05/02]
```

A lateximage captures the modified image from the document.

```
\def\pfx@includegraphicx#1#2{%
    \begin{lateximage}[(-psfragx-~\packagediagramname)]%
    \mbox{\pfx@overpix{#1}{#2}\endpfx@overpix}%
    \end{lateximage}%
}

\def\@@@overpix[#1]<#2>[#3]#4{%
    \begin{lateximage}[(-psfragx-~\packagediagramname)]%
    \pfx@overpix{#1,ovpfgd={#2},ovpbgd={#3}}{#4}%
}

\def\endoverpix{%
    \endpfx@overpix%
    \end{lateximage}%
}
```

File 273 **lwarp-pst-eps.sty**

§ 370 Package pst-eps

(*Emulates or patches code by* HERBERT VOSS.)

Pkg pst-eps pst-eps is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{pst-eps}[2005/05/20]

\renewenvironment{TeXtoEPS}{}{}
\renewcommand{\PSTtoEPS}[3][]{}
```

File 274 **lwarp-pstool.sty**

§ 371 Package pstool

(*Emulates or patches code by* Zebb Prime, Will Robertson.)

Pkg pstool pstool is patched for use by lwarp.

\graphicspath is ignored, and the file directory must be stated.

⚠ path and filename The filename must not have a file extension.

Use

Enter ⇒ **lwarpmk html**

followed by

Enter ⇒ **lwarpmk limages**

.

for HTML output:

```
\LWR@ProvidesPackagePass{pstool}[2018/01/20]
```

Each image is placed inside a lateximage to capture the results of psfrag.

```
\renewcommand\pstool@alwaysprocess[3][]{%
    \begin{lateximage}[(-pstool-~\packagediagramname)]%
    \includegraphics{#2.pdf}%
    \end{lateximage}%
}
\LetLtxMacro\pstool@neverprocess\pstool@alwaysprocess
\LetLtxMacro\pstool@maybeprocess\pstool@alwaysprocess

\renewcommand\pstool@@psfragfig[4]{%
    \begin{lateximage}[(-pstool-~\packagediagramname)]%
    \includegraphics{#2.pdf}%
    \end{lateximage}%
}
```

File 275 **lwarp-pstricks.sty**

§ 372 Package pstricks

(*Emulates or patches code by* Timothy Van Zandt.)

Pkg pstricks pstricks is patched for use by lwarp.

⚠ use pspicture All pstricks content should be contained inside a pspicture environment.

for HTML output:

```
\LWR@ProvidesPackagePass{pstricks}[2018/01/06]

\BeforeBeginEnvironment{pspicture}{\begin{lateximage}[(pspicture)]}
\AfterEndEnvironment{pspicture}{\end{lateximage}}
```

File 276 **lwarp-pxatbegshi.sty**

§ 373 Package pxatbegshi

Pkg pxatbegshi pxatbegshi is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxatbegshi}[2017/11/04]

\LWR@origRequirePackage{lwarp-atbegshi}
```

File 277 **lwarp-pxeveryshi.sty**

§ 374 Package pxeveryshi

Pkg pxeveryshi pxeveryshi is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxeveryshi}[2012/05/19]

\LWR@origRequirePackage{lwarp-everyshi}
```

File 278 **lwarp-pxftnright.sty**

§ 375 Package pxftnright

Pkg pxftnright pxftnright is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxftnright}[2017/02/28]
```

```
\LWR@origRequirePackage{lwarp-ftnright}
```

File 279 **lwarp-pxjahyper.sty**

§ 376 Package

pxjahyper

Pkg pxjahyper pxjahyper is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxjahyper}[2018/07/15]
```

File 280 **lwarp-quotchap.sty**

§ 377 Package

quotchap

(*Emulates or patches code by* Karsten Tinnefeld, Jan Klever.)

Pkg quotchap quotchap is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{quotchap}[2012/10/20]

\newcommand{\@quotchap}{}
\newlength{\LWR@quotchapwidth}

\let\@printcites\relax

\newcommand*{\@iprintcites}{%
```

Place the quotes inside a of class quotchap, of the maximum selected width:

```
\begin{BlockClass}[max-width: \LWR@printlength{\LWR@quotchapwidth}]{quotchap}
%\begin{minipage}{\LWR@quotchapwidth}
\@quotchap
%\end{minipage}
\end{BlockClass}
```

Deactivate the quote printing:

```
\global\let\@printcites\relax
}

\NewEnviron{savequote}[1][\linewidth]{%
```

Remember the width, adjusted for HTML, and make the length assignment global, per: https://tex.stackexchange.com/questions/300823/why-is-setlength-ineffective-inside-a-tabular-environment

```
\setlength{\LWR@quotchapwidth}{#1*2}%
\global\LWR@quotchapwidth=\LWR@quotchapwidth%
```

Remember the body, and activate the quote printing:

```
\global\let\@quotchap\BODY
\global\let\@printcites\@iprintcites%
}
```

The quotation author is placed inside a of class qauthor:

```
\newcommand{\qauthor}[1]{\begin{BlockClass}{qauthor}{#1}\end{BlockClass}}
```

\qsetcnfont is ignored:

```
\newcommand{\qsetcnfont}[1]{}
```

File 281 **lwarp-quoting.sty**

§ 378 Package quoting

(*Emulates or patches code by* Thomas Titz.)

Pkg quoting quoting is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{quoting}[2014/01/28]

\xpatchcmd{\quoting}{\quo@begintext}
    {\begin{LWR@blocktextcurrentfont}\quo@begintext}
    {}
    {\LWR@patcherror{quoting}{quoting}}

\xpatchcmd{\endquoting}{\quo@endtext}
    {\quo@endtext\end{LWR@blocktextcurrentfont}}
    {}
    {\LWR@patcherror{imakeidx}{endquoting}}
```

File 282 **lwarp-ragged2e.sty**

§ 379 Package ragged2e

(*Emulates or patches code by* Martin Schröder.)

Pkg ragged2e ragged2e is not used during HTML conversion.

Discard all options for lwarp-ragged2e:

for HTML output:

```
\LWR@ProvidesPackageDrop{ragged2e}[2009/05/21]

\LetLtxMacro\Centering\centering
\LetLtxMacro\RaggedLeft\raggedleft
\LetLtxMacro\RaggedRight\raggedright
```

```
\newcommand*{\justifying}{}
\newlength{\CenteringLeftskip}
\newlength{\RaggedLeftLeftskip}
\newlength{\RaggedRightLeftskip}
\newlength{\CenteringRightskip}
\newlength{\RaggedLeftRightskip}
\newlength{\RaggedRightRightskip}
\newlength{\CenteringParfillskip}
\newlength{\RaggedLeftParfillskip}
\newlength{\RaggedRightParfillskip}
\newlength{\JustifyingParfillskip}
\newlength{\CenteringParindent}
\newlength{\RaggedLeftParindent}
\newlength{\RaggedRightParindent}
\newlength{\JustifyingParindent}
\newenvironment*{Center}{\center}{\endcenter}
\newenvironment*{FlushLeft}{\flushleft}{\endflushleft}
\newenvironment*{FlushRight}{\flushright}{\endflushright}
\newenvironment*{justify}{\justifying}{\endjustifying}
```

File 283 **lwarp-realscripts.sty**

§ 380 Package

realscripts

(*Emulates or patches code by* Will Robertson.)

Pkg realscripts realscripts is emulated. See lwarp.css for the of class supsubscript.

for HTML output:

```
\LWR@ProvidesPackageDrop{realscripts}[2016/02/13]

\let\realsuperscript\textsuperscript
\let\realsubscript\textsubscript

\let\fakesuperscript\textsuperscript
\let\fakesubscript\textsubscript

\newlength{\subsupersep}

\newcommand*{\LWR@realscriptsalign}{}

\newcommand*{\LWR@setrealscriptsalign}[1]{%
    \renewcommand*{\LWR@realscriptsalign}{}%
    \ifthenelse{\equal{#1}{c}}{%
        \renewcommand{\LWR@realscriptsalign}{%
            \LWR@print@mbox{text-align:center} ; %
        }%
    }{}%
    \ifthenelse{\equal{#1}{r}}{%
        \renewcommand{\LWR@realscriptsalign}{%
            \LWR@print@mbox{text-align:right} ; %
        }%
    }{}%
}
```

```
25
26 \DeclareDocumentCommand \textsubsuperscript {s O{l} mm} {%
27     \LWR@setrealscriptsalign{#2}%
28     \InlineClass[\LWR@realscriptsalign]{supsubscript}{%
29         \textsuperscript{#4}\textsubscript{#3}%
30     }%
31 }
32
33 \DeclareDocumentCommand \textsupersubscript {s O{l} mm} {%
34     \LWR@setrealscriptsalign{#2}%
35     \InlineClass[\LWR@realscriptsalign]{supsubscript}{%
36         \textsubscript{#4}\textsuperscript{#3}%
37     }%
38 }
```

File 284 **lwarp-refcheck.sty**

§ 381 Package refcheck

Pkg refcheck refcheck is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{refcheck}[2013/02/14]

2 \def\showrefnames{}
3 \def\norefnames{}
4 \def\showcitenames{}
5 \def\nocitenames{}
6 \def\setonmsgs{}
7 \def\setoffmsgs{}
8 \def\checkunlbld{}
9 \def\ignoreunlbld{}
10 \newcommand*{\refcheckxrdoc}[2][]{}
```

File 285 **lwarp-register.sty**

§ 382 Package register

(*Emulates or patches code by* Matthew Lovell.)

Pkg register register is patched for use by lwarp.

for HTML output:

```
1 \LWR@ProvidesPackagePass{register}[2019/01/01]

2 \xpatchcmd{\register}
3     {\centering}
4     {\begin{center}\begin{lateximage}[(-register-~\packagediagramname)]}
5     {}
6     {\LWR@patcherror{register}{register}}
7
```

```
\xpatchcmd{\endregister}
    {\leftskip}
    {%
        \end{lateximage}\end{center}%
        \leftskip%
    }%
    {}
    {\LWR@patcherror{register}{endregister}}

\expandafter\xapptocmd\csname register*\endcsname
    {\begin{center}\begin{lateximage}[(-register-~\packagediagramname)]}
    {}
    {\LWR@patcherror{register}{register*}}

\expandafter\xpatchcmd\csname endregister*\endcsname
    {\leftskip}
    {%
        \end{lateximage}\end{center}%
        \leftskip%
    }%
    {}
    {\LWR@patcherror{register}{endregister*}}

\setlength{\regWidth}{5in}
```

File 286 **lwarp-relsize.sty**

§ 383 Package

relsize

(*Emulates or patches code by* Donald Arseneau, Bernie Cosell, Matt Swift.)

Pkg relsize relsize is patched for use by lwarp.

For HTML, only the inline macros are supported: `\textlarger`, `\textsmaller`, and `\textscale`. Each becomes an inline span of a modified `font-size`.

`\relsize`, `\larger`, `\smaller`, and `\relscale` are ignored.

While creating SVG math for HTML, the original definitions are temporarilty restored, and so should work as expected.

⚠ not small The HTML browser's setting for minumum font size may limit how small the output will be displayed.

for HTML output:

```
\LWR@ProvidesPackagePass{relsize}[2013/03/29]

\let\LWR@origrelsize\relsize
\LetLtxMacro\LWR@origlarger\larger
\LetLtxMacro\LWR@origsmaller\smaller
\let\LWR@relscale\relscale
\LetLtxMacro\LWR@origtextlarger\textlarger
\LetLtxMacro\LWR@origtextsmaller\textsmaller
\let\LWR@textscale\textscale
```

```
\appto\LWR@restoreorigformatting{%
\let\relsize\LWR@origrelsize%
\LetLtxMacro\larger\LWR@origlarger%
\LetLtxMacro\smaller\LWR@origsmaller%
\let\relscale\LWR@relscale%
\LetLtxMacro\textlarger\LWR@origtextlarger%
\LetLtxMacro\textsmaller\LWR@origtextsmaller%
\let\textscale\LWR@textscale%
}

\newcounter{LWR@relsizetemp}

\renewcommand*{\relsize}[1]{}
\renewcommand*{\larger}[1][]{}
\renewcommand*{\smaller}[1][]{}
\renewcommand*{\relscale}[1]{}

\renewcommand*{\textlarger}[2][1]{%
\setcounter{LWR@relsizetemp}{100+(#1*20)}%
\InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textlarger}{#2}%
}

\renewcommand*{\textsmaller}[2][1]{%
\setcounter{LWR@relsizetemp}{100-(#1*20)}%
\InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textsmaller}{#2}%
}

\renewcommand*{\textscale}[2]{%
\setcounter{LWR@relsizetemp}{100*\real{#1}}%
\InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textscale}{#2}%
}
```

File 287 **lwarp-repeatindex.sty**

§ 384 Package

repeatindex

Pkg repeatindex repeatindex is emulated for lwarp.

⚠ style file lwarp must be used with a special style file:

```
\usepackage[makeindex,makeindexStyle={lwarp_repeatindex}]{lwarp}
```

where `lwarp_repeatindex.ist` may be copied from the following modified version of `lwarp.ist`:

```
preamble
"\\begin{theindex}
  \\providecommand*\\lettergroupDefault[1]{}
  \\providecommand*\\lettergroup[1]{%
      \\par\\textbf{#1}\\par
      \\nopagebreak
```

```
  }
"
headings_flag 1
heading_prefix "
  \\lettergroup{"
heading_suffix "}"
delim_0 "], \\hyperindexref{"
delim_1 ", \\hyperindexref{"
delim_2 ", \\hyperindexref{"
delim_n "}, \\hyperindexref{"
delim_r "} -- \\hyperindexref{"
delim_t "}"

item_0 "\n  \\item ["
```

(The modifications are the `delim_0` and `item_0` entries.)

for HTML output:

```
\LWR@ProvidesPackageDrop{repeatindex}[2001/10/13]
```

In the lwarp core, `\LWR@indexitem` is modified to accept the optional `\item` argument.

```
\RequirePackage{makeidx}
\def\entryprefix{\itshape}
\def\entrypostfix{\dots}
```

File 288 **lwarp-resizegather.sty**

§ 385 Package resizegather

Pkg resizegather resizegather is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{resizegather}[2016/05/16]

\newcommand*{\resizegathersetup}[1]{}
```

File 289 **lwarp-rmpage.sty**

§ 386 Package rmpage

Pkg rmpage rmpage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{rmpage}[1997/09/29]
```

File 290 **lwarp-romanbar.sty**

§ 387 Package romanbar

(*Emulates or patches code by* H.-Martin Münch.)

Pkg romanbar romanbar is patched for use by lwarp.

An inline class with an overline and underline is used.

for HTML output:

```
\LWR@ProvidesPackagePass{romanbar}[2012/01/01]

\DeclareRobustCommand{\Roman@bar}[1]{% #1 is in Roman, i.e. MMXII
\InlineClass[%
    text-decoration: overline underline ;
]{romanbar}{#1}%
}
```

File 291 **lwarp-romanbarpagenumber.sty**

§ 388 Package romanbarpagenumber

Pkg romanbarpagenumber romanbarpagenumber is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{romanbarpagenumber}[2015/02/06]
```

File 292 **lwarp-rotating.sty**

§ 389 Package rotating

(*Emulates or patches code by* Robin Fairbairns, Sebastian Rahtz, Leonor Barroca.)

Pkg rotating rotating is emulated.

All rotations are ignored in HTML output.

for HTML output:

```
\LWR@ProvidesPackageDrop{rotating}[2016/08/11]

\LetLtxMacro\sidewaystable\table
\let\endsidewaystable\endtable

\LetLtxMacro\sidewaysfigure\figure
\let\endsidewaysfigure\endfigure

\newenvironment*{sideways}{}{}
```

```
\newenvironment*{turn}[1]{}{}
\newenvironment*{rotate}[1]{}{}
\NewDocumentCommand{\turnbox}{m +m}{#2}
\let\rotcaption\caption
\let\@makerotcaption\@makecaption
```

File 293 **lwarp-rotfloat.sty**

§ 390 Package

rotfloat

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg rotfloat rotfloat is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{rotfloat}[2004/01/04]

\RequirePackage{float}
```

\newfloat {⟨*1: type*⟩} {⟨*2: placement*⟩} {⟨*3: ext*⟩} [⟨*4: within*⟩]

Emulates the \newfloat command from the float package. Sideways floats are \let to the same as regular floats.

"placement" is ignored.

```
\RenewDocumentCommand{\newfloat}{m m m o}{%
\IfValueTF{#4}%
{%
    \DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}%
}%
{%
    \DeclareFloatingEnvironment[fileext=#3]{#1}%
}%
\csletcs{sideways#1}{#1}%
\csletcs{endsideways#1}{end#1}%
```

Remember the float style:

```
\csedef{LWR@floatstyle@#1}{\LWR@floatstyle}%
\csedef{LWR@floatstyle@sideways#1}{\LWR@floatstyle}%
```

newfloat package automatically creates the \listof command for new floats, but float does not, so remove \listof here in case it is manually created later:

```
\cslet{listof#1s}\relax%
\cslet{listof#1es}\relax%
\cslet{listofsideways#1s}\relax%
\cslet{listofsideways#1es}\relax%
}
```

File 294 **lwarp-rviewport.sty**

§ 391 Package rviewport

Pkg rviewport rviewport is honored inside a `lateximage`, and otherwise ignored for HTML output.

If rviewport is important for an image, enclose the image inside a `lateximage` environment.

for HTML output:

```
\LWR@ProvidesPackagePass{rviewport}[2011/08/27]
\define@key{igraph}{rviewport}{}
```

File 295 **lwarp-savetrees.sty**

§ 392 Package savetrees

Pkg savetrees Emulated.

for HTML output: Discard all options for lwarp-savetrees:

```
\LWR@ProvidesPackageDrop{savetrees}[2016/04/13]
```

File 296 **lwarp-scalefnt.sty**

§ 393 Package scalefnt

(*Emulates or patches code by* D. Carlisle.)

Pkg scalefnt scalefnt is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{scalefnt}
\DeclareRobustCommand\scalefont[1]{}
```

File 297 **lwarp-schemata.sty**

§ 394 Package schemata

(*Emulates or patches code by* Charles P. Schaum.)

Pkg schemata schemata is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{schemata}[2016/01/25]
```

```
\LetLtxMacro\LWR@schemata@origschema\schema
\LetLtxMacro\LWR@schemata@origSchema\Schema

\renewcommand{\schema}[3][open]{%
\begin{lateximage}%
\LWR@print@normalsize
\LWR@schemata@origschema[#1]{#2}{#3}%
\end{lateximage}%
}

\renewcommand{\Schema}[5][open]{%
\begin{lateximage}%
\LWR@print@normalsize
\LWR@schemata@origSchema[#1]{#2}{#3}{#4}{#5}%
\end{lateximage}%
}
```

File 298 **lwarp-scrextend.sty**

§ 395 Package

scrextend

Pkg scrextend

scrextend is emulated.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. \DeclareDocumentCommand is used to overwrite the koma-script definitions.

for HTML output:

```
\LWR@ProvidesPackageDrop{scrextend}[2018/03/30]

\DeclareDocumentCommand{\setkomafont}{m m}{}
\DeclareDocumentCommand{\addkomafont}{m m}{}
\DeclareDocumentCommand{\usekomafont}{m}{}

\DeclareDocumentCommand{\usefontofkomafont}{m}{}
\DeclareDocumentCommand{\useencodingofkomafont}{m}{}
\DeclareDocumentCommand{\usesizeofkomafont}{m}{}
\DeclareDocumentCommand{\usefamilyofkomafont}{m}{}
\DeclareDocumentCommand{\useseriesofkomafont}{m}{}
\DeclareDocumentCommand{\useshapeofkomafont}{m}{}

\AtBeginDocument{
\let\LWR@maketitle\maketitle
\DeclareDocumentCommand{\maketitle}{o}{\LWR@maketitle}
}

\DeclareDocumentCommand{\extratitle}{m}{}
\DeclareDocumentCommand{\titlehead}{m}{}
\DeclareDocumentCommand{\subject}{m}{}
\DeclareDocumentCommand{\publishers}{m}{\published{#1}}
\DeclareDocumentCommand{\uppertitleback}{m}{}
\DeclareDocumentCommand{\lowertitleback}{m}{}
\DeclareDocumentCommand{\dedication}{m}{}
```

```
25
26 \DeclareDocumentCommand{\ifthispageodd}{m m}{#1}
27
28 \DeclareDocumentCommand{\titlepagestyle}{}{}
29
30 \DeclareDocumentCommand{\cleardoublepageusingstyle}{m}{}
31 \DeclareDocumentCommand{\cleardoubleemptypage}{}{}
32 \DeclareDocumentCommand{\cleardoubleplainpage}{}{}
33 \DeclareDocumentCommand{\cleardoublestandardpage}{}{}
34 \DeclareDocumentCommand{\cleardoubleoddpage}{}{}
35 \DeclareDocumentCommand{\cleardoubleoddpageusingstyle}{m}{}
36 \DeclareDocumentCommand{\cleardoubleoddemptypage}{}{}
37 \DeclareDocumentCommand{\cleardoubleoddplainpage}{}{}
38 \DeclareDocumentCommand{\cleardoubleoddstandardpage}{}{}
39 \DeclareDocumentCommand{\cleardoubleevenpage}{}{}
40 \DeclareDocumentCommand{\cleardoubleevenpageusingstyle}{m}{}
41 \DeclareDocumentCommand{\cleardoubleevenemptypage}{}{}
42 \DeclareDocumentCommand{\cleardoubleevenplainpage}{}{}
43 \DeclareDocumentCommand{\cleardoubleevenstandardpage}{}{}
44
45 \DeclareDocumentCommand{\multiplefootnoteseparator}{}{%
46   \begingroup\let\thefootnotemark\multfootsep\@makefnmark\endgroup
47 }
48
49 \DeclareDocumentCommand{\multfootsep}{}{,}
50
51 \DeclareDocumentCommand{\footref}{m}{%
52   \begingroup
53     \unrestored@protected@xdef\@thefnmark{\ref{#1}}%
54   \endgroup
55   \@footnotemark
56 }
57
58 \DeclareDocumentCommand{\deffootnote}{o m m m}{}
59 \DeclareDocumentCommand{\deffootnotemark}{m}{}
60 \DeclareDocumentCommand{\setfootnoterule}{o m}{}
61 \DeclareDocumentCommand{\raggedfootnote}{}{}
62
63 \DeclareDocumentCommand{\dictum}{o m}{
64 \begin{LWR@BlockClassWP}{\LWR@print@mbox{text-align:right}}{}{dictum}
65     #2
66     \IfValueT{#1}
67     {
68         \ifbool{FormatWP}
69       {\begin{BlockClass}[\LWR@print@mbox{border-top:} 1px solid gray]{dictumauthor}}
70         {\begin{BlockClass}{dictumauthor}}
71         \dictumauthorformat{#1}
72         \end{BlockClass}
73     }
74 \end{LWR@BlockClassWP}
75 }
76
77 \DeclareDocumentCommand{\dictumwidth}{}{}
78 \DeclareDocumentCommand{\dictumauthorformat}{m}{(#1)}
79 \DeclareDocumentCommand{\dictumrule}{}{}
```

```
\DeclareDocumentCommand{\raggeddictum}{}{}
\DeclareDocumentCommand{\raggeddictumtext}{}{}
\DeclareDocumentCommand{\raggeddictumauthor}{}{}

\DeclareDocumentEnvironment{labeling}{o m}
{%
\def\sc@septext{#1}%
\list{}{}%
\let\makelabel\labelinglabel%
}
{
\endlist
}

\DeclareDocumentCommand{\labelinglabel}{m}{%
#1 \qquad \sc@septext%
}

\let\addmargin\relax
\let\endaddmargin\relax
\cslet{addmargin*}{\relax}
\cslet{endaddmargin*}{\relax}

\NewDocumentEnvironment{addmargin}{s O{} m}
{
\setlength{\LWR@templengthtwo}{#3}
\ifblank{#2}
{
    \begin{BlockClass}[
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthtwo}} ;
        \LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}
    ]{addmargin}
}
{
    \setlength{\LWR@templengthone}{#2}
    \begin{BlockClass}[
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ;
        \LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}
    ]{addmargin}
}
}
{\end{BlockClass}}
```

Ref to create a starred environment:
https://tex.stackexchange.com/questions/45401/use-the-s-star-argument-with-newdocumentenvironment

```

\ExplSyntaxOn
\cs_new:cpn {addmargin*} {\addmargin*}
\cs_new_eq:cN {endaddmargin*} \endaddmargin
\ExplSyntaxOff

\DeclareDocumentCommand{\marginline}{m}{\marginpar{#1}}
```

File 299 **lwarp-scrhack.sty**

§ 396 Package scrhack

Pkg scrhack scrhack is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{scrhack}[2018/03/30]
```

File 300 **lwarp-scrlayer.sty**

§ 397 Package scrlayer

(*Emulates or patches code by* Markus Kohm.)

Pkg scrlayer scrlayer is emulated.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrlayer}[2018/03/30]

\newcommand*{\DeclareSectionNumberDepth}[2]{}
\newcommand*{\DeclareLayer}[2][]{}
\newcommand*{\DeclareNewLayer}[2][]{}
\newcommand*{\ProvideLayer}[2][]{}
\newcommand*{\RedeclareLayer}[2][]{}
\newcommand*{\ModifyLayer}[2][]{}
\newcommand*{\layerhalign}{}
\newcommand*{\layervalign}{}
\newcommand*{\layerxoffset}{}
\newcommand*{\layeryoffset}{}
\newcommand*{\layerwidth}{}
\newcommand*{\layerheight}{}
\providecommand*{\LenToUnit}[1]{\strip@pt\dimexpr#1*\p@/\unitlength}
\newcommand*{\putUL}[1]{}
\newcommand*{\putUR}[1]{}
\newcommand*{\putLL}[1]{}
\newcommand*{\putLR}[1]{}
\newcommand*{\putC}[1]{}
\newcommand*{\GetLayerContents}[1]{}
\newcommand{\IfLayerExists}[3]{#3}
\newcommand*{\DestroyLayer}[1]{}
\newcommand*{\layercontentsmeasure}{}
\newcommand*{\currentpagestyle}{}
\newcommand*{\BeforeSelectAnyPageStyle}[1]{}
\newcommand*{\AfterSelectAnyPageStyle}[1]{}
\newcommand*{\DeclarePageStyleAlias}[2]{}
\newcommand*{\DeclareNewPageStyleAlias}[2]{}
\newcommand*{\ProvidePageStyleAlias}[2]{}
```

```
\newcommand*{\RedeclarePageStyleAlias}[2]{}
\newcommand*{\DestroyPageStyleAlias}[1]{}
\newcommand*{\GetRealPageStyle}[1]{}
\newcommand*{\DeclarePageStyleByLayers}[3][]{}
\newcommand*{\DeclareNewPageStyleByLayers}[3][]{}
\newcommand*{\ProvidePageStyleByLayers}[3][]{}
\newcommand*{\RedeclarePageStyleByLayers}[3][]{}
\NewDocumentCommand{\ForEachLayerOfPageStyle}{s m m}{}
\newcommand*{\AddLayersToPageStyle}[2]{}
\newcommand*{\AddLayersAtBeginOfPageStyle}[2]{}
\newcommand*{\AddLayersAtEndOfPageStyle}[2]{}
\newcommand*{\RemoveLayersFromPageStyle}[2]{}
\newcommand*{\AddLayersToPageStyleBeforeLayer}[3]{}
\newcommand*{\AddLayersToPageStyleAfterLayer}[3]{}
\newcommand*{\UnifyLayersAtPageStyle}[1]{}
\newcommand*{\ModifyLayerPageStyleOptions}[2]{}
\newcommand*{\AddToLayerPageStyleOptions}[2]{}
\newcommand{\IfLayerPageStyleExists}[3]{#3}
\newcommand{\IfRealLayerPageStyleExists}[3]{#3}
\newcommand{\IfLayerAtPageStyle}[4]{#4}
\newcommand{\IfSomeLayerAtPageStyle}[4]{#4}
\newcommand{\IfLayersAtPageStyle}[4]{#4}
\newcommand*{\DestroyRealLayerPageStyle}[1]{}
\@ifundefined{footheight}{\newlength\footheight}{}
\DeclareDocumentCommand{\automark}{s o m}{}
\DeclareDocumentCommand{\manualmark}{}{}
\DeclareDocumentCommand{\MakeMarkcase}{m}{#1}


\newcommand{\partmarkformat}{}
\if@chapter
\newcommand{\chaptermarkformat}{}
\fi
\newcommand{\sectionmarkformat}{}
\DeclareDocumentCommand{\GenericMarkFormat}{m}{}

\newcommand*{\@mkleft}[1]{}
\newcommand*{\@mkright}[1]{}
\newcommand*{\@mkdouble}[1]{}
\newcommand*{\@mkboth}[2]{}
\newcommand*{\scrlayerInitInterface}[1][]{}
\newcommand{\scrlayerAddToInterface}[3][]{}
\newcommand{\scrlayerAddCsToInterface}[3][]{}
\newcommand{\scrlayerOnAutoRemoveInterface}[2][]{}
```

File 301 **lwarp-scrlayer-notecolumn.sty**

§ 398 Package scrlayer-notecolumn

(*Emulates or patches code by* Markus Kohm.)

Pkg scrlayer-notecolumn scrlayer-notecolumn is emulated.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrlayer-notecolumn}[2018/02/02]

\newcommand*{\DeclareNoteColumn}[2][]{}
\newcommand*{\DeclareNewNoteColumn}[2][]{}
\newcommand*{\ProvideNoteColumn}[2][]{}
\newcommand*{\RedeclareNoteColumn}[2][]{}
\NewDocumentCommand{\makenote}{s o m}{\marginpar{#3}}
\newcommand*{\syncwithnotecolumn}[1][]{}
\newcommand*{\syncwithnotecolumns}[1][]{}
\newcommand*{\clearnotecolumn}[1][]{}
\newcommand*{\clearnotecolumns}[1][]{}
```

File 302 **lwarp-scrlayer-scrpage.sty**

§ 399 Package

scrlayer-scrpage

(*Emulates or patches code by* Markus Kohm.)

Pkg scrlayer-scrpage scrlayer-scrpage is emulated.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrlayer-scrpage}[2018/03/30]

\@ifundefined{footheight}{\newlength\footheight}{}
\NewDocumentCommand{\lehead}{s o m}{}
\NewDocumentCommand{\cehead}{s o m}{}
\NewDocumentCommand{\rehead}{s o m}{}
\NewDocumentCommand{\lohead}{s o m}{}
\NewDocumentCommand{\cohead}{s o m}{}
\NewDocumentCommand{\rohead}{s o m}{}
\NewDocumentCommand{\lefoot}{s o m}{}
\NewDocumentCommand{\cefoot}{s o m}{}
\NewDocumentCommand{\refoot}{s o m}{}
\NewDocumentCommand{\lofoot}{s o m}{}
\NewDocumentCommand{\cofoot}{s o m}{}
\NewDocumentCommand{\rofoot}{s o m}{}
\NewDocumentCommand{\ohead}{s o m}{}
\NewDocumentCommand{\chead}{s o m}{}
\NewDocumentCommand{\ihead}{s o m}{}
\NewDocumentCommand{\ofoot}{s o m}{}
\NewDocumentCommand{\cfoot}{s o m}{}
\NewDocumentCommand{\ifoot}{s o m}{}
\DeclareDocumentCommand{\MakeMarkcase}{m}{#1}
\newcommand*{\defpairofpagestyles}[3][]{}
\newcommand*{\newpairofpagestyles}[3][]{}
\newcommand*{\renewpairofpagestyles}[3][]{}
\newcommand*{\providepairofpagestyles}[3][]{}

\newcommand*{\clearmainofpairofpagestyles}{}
```

```
\newcommand*{\clearplainofpairofpagestyles}{}
\newcommand*{\clearpairofpagestyles}{}
\newcommand*{\clearscrheadings}{}
\newcommand*{\clearscrheadfoot}{}
\newcommand*{\clearscrplain}{}

\NewDocumentCommand{\deftriplepagestyle}{m o o m m m m m m}{}
\NewDocumentCommand{\newtriplepagestyle}{m o o m m m m m m}{}
\NewDocumentCommand{\renewtriplepagestyle}{m o o m m m m m m}{}
\NewDocumentCommand{\providetriplepagestyle}{m o o m m m m m m}{}
\newcommand*{\defpagestyle}[3]{}
\newcommand*{\newpagestyle}[3]{}
\newcommand*{\providepagestyle}[3]{}
\newcommand*{\renewpagestyle}[3]{}
```

File 303 **lwarp-scrpage2.sty**

§ 400 Package scrpage2

(*Emulates or patches code by* Markus Kohm.)

Pkg scrpage2 scrpage2 is emulated.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrpage2}[2018/03/30]

\@ifundefined{footheight}{\newlength\footheight}{}
\NewDocumentCommand{\lehead}{o m}{}
\NewDocumentCommand{\cehead}{o m}{}
\NewDocumentCommand{\rehead}{o m}{}
\NewDocumentCommand{\lohead}{o m}{}
\NewDocumentCommand{\cohead}{o m}{}
\NewDocumentCommand{\rohead}{o m}{}
\NewDocumentCommand{\lefoot}{o m}{}
\NewDocumentCommand{\cefoot}{o m}{}
\NewDocumentCommand{\refoot}{o m}{}
\NewDocumentCommand{\lofoot}{o m}{}
\NewDocumentCommand{\cofoot}{o m}{}
\NewDocumentCommand{\rofoot}{o m}{}
\NewDocumentCommand{\ohead}{o m}{}
\NewDocumentCommand{\chead}{o m}{}
\NewDocumentCommand{\ihead}{o m}{}
\NewDocumentCommand{\ofoot}{o m}{}
\NewDocumentCommand{\cfoot}{o m}{}
\NewDocumentCommand{\ifoot}{o m}{}
\DeclareDocumentCommand{\automark}{o m}{}
\DeclareDocumentCommand{\manualmark}{}{}
\DeclareDocumentCommand{\MakeMarkcase}{m}{#1}
\NewDocumentCommand{\deftripstyle}{m o o m m m m m m}{}
\NewDocumentCommand{\defpagestyle}{s m m m}{}
\NewDocumentCommand{\newpagestyle}{s m m m}{}
```

```
\NewDocumentCommand{\renewpagestyle}{s m m m}{}
\NewDocumentCommand{\providepagestyle}{s m m m}{}
\newcommand{\partmarkformat}{}
\if@chapter
\newcommand{\chaptermarkformat}{}
\fi
\newcommand{\sectionmarkformat}{}
\newcommand{\subsectionmarkformat}{}
\newcommand{\subsubsectionmarkformat}{}
\newcommand{\paragraphmarkformat}{}
\newcommand{\subparagraphmarkformat}{}

\newcommand*{\clearscrheadings}{}
\newcommand*{\clearscrheadfoot}{}
\newcommand*{\clearscrplain}{}
```

File 304 **lwarp-section.sty**

§ 401 Package

section

Pkg section section is ignored.

(*Emulates or patches code by* Oliver Pretzel.)

for HTML output:

```
\LWR@ProvidesPackageDrop{section}

\ifx\chapter\undefined
 \def\chsize{\Large}\def\hdsize{\huge}\else
 \def\chsize{\huge}\def\hdsize{\Huge}
\fi
\let\ttsize\LARGE
\let\ausize\large
\let\dasize\large
\let\secsize\Large
\let\subsize\large
\let\hdpos\raggedright
\newcounter{hddepth}
\let\fpind\relax
\def\ttfnt{}
\def\hdfnt{}
\def\fefnt{}
\def\thfnt{}
\def\pgfnt{}
\def\hmkfnt{}
\let\mkcse\uppercase
\def\hddot{}
\def\cpdot{:}
\def\nmdot{}
\ifx\secindent\undefined
 \newdimen\secindent
 \newskip\secpreskp
 \newskip\secpstskp
 \newdimen\subindent
```

```
\newskip\subpreskp
\newskip\subpstskp
\newskip\parpstskp
\newcount\c@hddepth
\fi
```

File 305 **lwarp-sectionbreak.sty**

§ 402 Package sectionbreak

(*Emulates or patches code by* Michal Hoftich.)

Pkg sectionbreak sectionbreak is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{sectionbreak}[2018-01-03]

\renewcommand\asterism{\HTMLunicode{2042}}

\renewcommand\pre@sectionbreak{}
\renewcommand\post@sectionbreak{}

\renewcommand\print@sectionbreak[1]{%
\begin{center}
#1
\end{center}
}

```

File 306 **lwarp-sectsty.sty**

§ 403 Package sectsty

(*Emulates or patches code by* Rowland McDonnell.)

Pkg sectsty sectsty is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{sectsty}[2002/02/25]

\newcommand*{\partfont}          [1] {}
\newcommand*{\partnumberfont}    [1] {}
\newcommand*{\parttitlefont}     [1] {}
\newcommand*{\chapterfont}       [1] {}
\newcommand*{\chapternumberfont} [1] {}
\newcommand*{\chaptertitlefont}  [1] {}
\newcommand*{\sectionfont}       [1] {}
\newcommand*{\subsectionfont}    [1] {}
\newcommand*{\subsubsectionfont} [1] {}
\newcommand*{\paragraphfont}     [1] {}
\newcommand*{\subparagraphfont}  [1] {}
\newcommand*{\minisecfont}  [1] {}
```

```
\newcommand*{\allsectionsfont}[1] {}
\newcommand{\nohang}{}
```

`\sectionrule` is only to be used in `*font` commands, thus it is ignored.

```
\newcommand*{\sectionrule}[5]{}

\def\ulemheading#1#2{}
```

File 307 **lwarp-semantic-markup.sty**

§ 404 Package

semantic-markup

(*Emulates or patches code by* Andrew A. Cashner.)

Pkg semantic-markup semantic-markup is patched for use by lwarp.

⚠ If using the `endnotes` option, add `\theendnotes` where desired.

for HTML output:

```
\LWR@ProvidesPackagePass{semantic-markup}[2018/05/21]
```

The endnotes must be printed by the user before the end of the document, since the end is after the HTML footer, etc.

```
\ifendnotes
\RenewDocumentCommand{\SetupEndnotes}{}{%
    \let\footnote=\endnote
%     \AtEndDocument{\DoBeforeEndnotes{\EndnoteFont\theendnotes}}%
}
\fi
```

HTML unicode characters from musicography are used.

```
\RequirePackage{musicography}

\let\fl\musFlat
\let\sh\musSharp
\let\na\musNatural
```

The `\musfig` is placed inside a hashed image, with a simple `alt` tag.

```
\RequirePackage{amsmath}

\RenewDocumentCommand{\musfig}{ m m }{%
    \LWR@subsingledollar*%
        {#1/#2}% alt tag
        {musfig}% addl' hashing
        {% contents
            \LWR@origensuredmath{%
                \genfrac{}{}{0pt}{1}{\text{#1}}{\text{#2}}%
            }%
        }%
```

```
}
```

The `\meter` is taken from musicography, and becomes a hashed image with a simple `alt` tag.

```
\RenewDocumentCommand{\meter}{ m m }{%
    \musMeter{#1}{#2}%
}
```

File 308 **lwarp-setspace.sty**

§ 405 Package

setspace

(*Emulates or patches code by* Robin Fairbairns.)

Pkg setspace setspace is not used during HTML conversion.

Discard all options for lwarp-setspace:

for HTML output:

```
\LWR@ProvidesPackageDrop{setspace}[2011/12/19]

\newcommand*{\setstretch}[1]{}
\newcommand*{\SetSinglespace}[1]{}
\newcommand*{\singlespacing}{}
\newcommand*{\onehalfspacing}{}
\newcommand*{\doublespacing}{}

\newenvironment*{singlespace}
{
\LWR@forcenewpage
\BlockClass{singlespace}
}
{\endBlockClass}

\newenvironment*{singlespace*}
{
\LWR@forcenewpage
\BlockClass{singlespace}
}
{\endBlockClass}

\newenvironment*{spacing}[1]{

}{

}

\newenvironment*{onehalfspace}
{
\LWR@forcenewpage
\BlockClass{onehalfspace}
}
{\endBlockClass}
```

```
35
36 \newenvironment*{doublespace}
37 {
38 \LWR@forcenewpage
39 \BlockClass{doublespace}
40 }
41 {\endBlockClass}
```

File 309 **lwarp-shadow.sty**

§ 406 Package shadow

(*Emulates or patches code by* Mauro Orlandini.)

Pkg shadow shadow is emulated.

for HTML output: Discard all options for lwarp-shadow:

```
1 \LWR@ProvidesPackageDrop{shadow}[2003/02/19]

2 \newdimen\sboxsep
3 \newdimen\sboxrule
4 \newdimen\sdim
5
6 \newcommand{\shabox}[1]{%
7 \InlineClass{shabox}{#1}%
8 }
```

File 310 **lwarp-showidx.sty**

§ 407 Package showidx

Pkg showidx showidx is ignored.

for HTML output: Discard all options for lwarp-showidx:

```
1 \LWR@ProvidesPackageDrop{showidx}[2014/09/29]
```

`\@wrindex` is redefined `\AtBeginDocument` by the lwarp core.

File 311 **lwarp-showkeys.sty**

§ 408 Package showkeys

(*Emulates or patches code by* David Carlisle, Morten Høgholm.)

Pkg showkeys showkeys is ignored.

for HTML output: Discard all options for lwarp-showkeys:

```
\LWR@ProvidesPackageDrop{showkeys}[2014/10/28]
\NewDocumentCommand{\showkeys}{s}{}
```

File 312 **lwarp-showtags.sty**

§ 409 Package showtags

Pkg showtags showtags is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{showtags}% no version is given
\newcommand{\thecitetag}[1]{}
```

File 313 **lwarp-sidecap.sty**

§ 410 Package sidecap

(*Emulates or patches code by* Rolf Niepraschk, Hubert Gässlein.)

Pkg sidecap sidecap is emulated.

for HTML output: Discard all options for lwarp-sidecap.

```
\LWR@ProvidesPackageDrop{sidecap}[2003/06/06]
```

See:
http://tex.stackexchange.com/questions/45401/use-the-s-star-argument-with-newdocumentenvironment
regarding the creation of starred environments with xparse.

```
\NewDocumentEnvironment{SCtable}{soo}
{\IfValueTF{#3}{\table[#3]}{\table}}
{\endtable}

\ExplSyntaxOn
\cs_new:cpn {SCtable*} {\SCtable*}
\cs_new_eq:cN {endSCtable*} \endSCtable
\ExplSyntaxOff


\NewDocumentEnvironment{SCfigure}{soo}
{\IfValueTF{#3}{\figure[#3]}{\figure}}
{\endfigure}

\ExplSyntaxOn
\cs_new:cpn {SCfigure*} {\SCfigure*}
```

```
\cs_new_eq:cN {endSCfigure*} \endSCfigure
\ExplSyntaxOff


\newenvironment*{wide}{}{}
```

File 314 **lwarp-sidenotes.sty**

§ 411 Package

sidenotes

(*Emulates or patches code by* Andy Thomas, Oliver Schebaum.)

Pkg sidenotes Patched for lwarp.

for HTML output: Load the original package:

```
\LWR@ProvidesPackagePass{sidenotes}
```

The following patch sidenotes for use with lwarp:

\sidecaption * [⟨*entry*⟩] [⟨*offset*⟩] {⟨*text*⟩}

```
\RenewDocumentCommand \sidecaption {s o o +m}
{
    \LWR@stoppars
    \begingroup
  \captionsetup{style=sidecaption}
  \IfBooleanTF{#1}
  { % starred
    \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}
    \caption*{#4}
    \end{BlockClass}
  }
  { % unstarred
  \IfNoValueOrEmptyTF{#2}
    {\def\@sidenotes@sidecaption@tof{#4}}
    {\def\@sidenotes@sidecaption@tof{#2}}
    \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}
    \caption[\@sidenotes@sidecaption@tof]{#4}
    \end{BlockClass}
  }
    \endgroup
    \LWR@startpars
}
```

Borrowed from the lwarp version of keyfloat:

```
\NewDocumentEnvironment{KFLTsidenotes@marginfloat}{O{-1.2ex} m}
{% start
\LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}{marginblock}%
\captionsetup{type=#2}%
}
{%
```

```
\endLWR@BlockClassWP%
}

\RenewDocumentEnvironment{marginfigure}{o}
  {\begin{KFLTsidenotes@marginfloat}{figure}}
  {\end{KFLTsidenotes@marginfloat}}

\RenewDocumentEnvironment{margintable}{o}
  {\begin{KFLTsidenotes@marginfloat}{table}}
  {\end{KFLTsidenotes@marginfloat}}
```

The following were changed by sidenotes, and now are reset back to their lwarp-supported originals:

Restoring the definition from the LaTeX 2$_\varepsilon$ `article.cls` source:

```
\renewenvironment{figure*}
               {\@dblfloat{figure}}
               {\end@dblfloat}

\renewenvironment{table*}
               {\@dblfloat{table}}
               {\end@dblfloat}
```

File 315 **lwarp-SIunits.sty**

§ 412 Package

SIunits

(*Emulates or patches code by* Marcel Heldoorn.)

Pkg SIunits SIunits is patched for use by lwarp.

It is recommended to use `\unit` where possible, which combines the entire expression into a single `lateximage`, and adds the `alt` tag containing the LaTeX code, allowing for copy/paste. When units are used outside of the `\unit` macro, each unit macro will have its own `lateximage`, and each will have the `alt` tag set to "`(<\mathimagename>)`", which defaults to "`(math image)`".

for HTML output:

```
\LWR@ProvidesPackagePass{SIunits}[2007/12/02]
```

Patched for copy/paste with the HTML `alt` tag:

```
\DeclareRobustCommand{\unit}[2]{%
\@inunitcommandtrue%    original
\LWR@subsingledollar*%  lwarp
{% alt tag
    \textbackslash{}unit\{\LWR@HTMLsanitize{#1}\}%
        \{ \LWR@HTMLsanitize{#2}\}% extra space
}%
{SIunits}% add'l hashing
{%
    \LWR@origensuredmath{%  lwarp modification
```

```
        \SI@fstyle{#1\@qsk\period@active{#2}}%  original
    }%
}% contents
\@inunitcommandfalse%   original
}
```

File 316 **lwarp-siunitx.sty**

§ 413 Package

siunitx

(*Emulates or patches code by* Joseph Wright.)

Pkg siunitx siunitx is patched for use by lwarp.

fractions Due to *pdftotext* limitations, fraction output is replaced by symbol output for `per-mode` and `quotient-mode`.

⚠ math mode required Some units will require that the expression be placed inside math mode.

NOTE: As of this writing, the siunitx extension for MathJax is not currently hosted at any public CDN, thus siunitx is not usable with MathJax unless a local copy of this extension is created first.

⚠ tabular Tabular `S` columns are rendered as simple `c` columns, and tabular `s` columns are not supported. These may be replaced by `c` columns with each cell contained in `\num` or `\si`.

for HTML output:

```
\RequirePackage{xcolor}% for \convertcolorspec

\LWR@ProvidesPackagePass{siunitx}[2018/05/17]


\AtBeginDocument{% in case textcomp was not loaded
\DeclareSIUnit\bohr{\textit{a}\textsubscript{0}}
\DeclareSIUnit\clight{\textit{c}\textsubscript{0}}
\DeclareSIUnit\elementarycharge{\textit{e}}
\DeclareSIUnit\electronmass{\textit{m}\textsubscript{e}}
\DeclareSIUnit\hartree{\textit{E}\textsubscript{h}}
\DeclareSIUnit\planckbar{\LWR@siunitx@textplanckbar}
}% AtBeginDocument
```

`\@ensuredmath` is not supported inside an `\hbox`, so it must temporarily be restored to its original. Similar for `\mbox`. SVG math is created explicitly when necessary, using `\LWR@subsingledollar`.

```

\ExplSyntaxOn
%
```

Modified to set set HTML `\textcolor` if not black:

```
\cs_undefine:N \__siunitx_print_aux:
```

```
\cs_new_protected:Npn \__siunitx_print_aux:
  {
    \text
      {
        \__siunitx_ensure_ltr:n
          {
            \color@begingroup
            \__siunitx_print_color:
            \__siunitx_font_shape:
            \__siunitx_font_weight:
            \use:c
              {
                @@_ \l__siunitx_print_type_tl _
                text \l__siunitx_font_family_tl :
              }
            \bool_if:NTF \l__siunitx_font_math_mode_bool
              { \__siunitx_print_math: }
              {
                \LWR@findcurrenttextcolor% lwarp
                \ifdefstring{\LWR@tempcolor}{000000}% lwarp
                {\__siunitx_print_text:}% lwarp
                {% lwarp
                    \LWR@textcurrentcolor{% lwarp
                        \__siunitx_print_text:
                    }% lwarp
                }% lwarp
              }
            \color@endgroup
          }
      }
  }


\cs_undefine:N \__siunitx_set_math_fam:n
\cs_new_protected:Npn \__siunitx_set_math_fam:n #1 {
  \int_new:c { c__siunitx_math #1 _int }
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \hbox_set:Nn \l__siunitx_tmp_box
      {
        \ensuremath
          {
            \use:c { math #1 }
              {
                \int_gset:cn { c__siunitx_math #1 _int } { \fam }
              }
          }
      }
  \group_end:% lwarp
}

\cs_undefine:N \__siunitx_combined_output:n
\cs_new_protected:Npn \__siunitx_combined_output:n #1 {
    \group_begin:% lwarp
```

```
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
  \bool_if:NTF \l__siunitx_number_parse_bool
    {
      \tl_clear:N \l__siunitx_number_out_tl
      \bool_set_false:N \l__siunitx_number_compound_bool
      \__siunitx_number_output_parse:n {#1}
    }
    {
      \__siunitx_unit_output_pre_print:
```

For `parse-numbers=false`:

```
%       \__siunitx_print:nn { number } { \ensuremath {#1} }
        \LWR@subsingledollar{% lwarp
            \textbackslash( \LWR@HTMLsanitize{#1} \textbackslash)% lwarp
        }{siunitx}{%
            \__siunitx_print:nn { number } {%
                \LWR@origensuredmath{#1}%
            }%
        }% lwarp

      \__siunitx_unit_output_print:
    }
    \group_end:% lwarp
}
%
```

For quotients, the fraction code is replaced by the symbol code:

```
\cs_undefine:N \__siunitx_number_output_quotient_fraction:
\cs_new_protected:Npn \__siunitx_number_output_quotient_fraction: {
  \bool_set_true:N \l__siunitx_number_compound_bool
  \__siunitx_number_output_quotient_aux_i:
  \tl_set_eq:NN \l__siunitx_number_out_tl
    \l__siunitx_number_numerator_tl
  \tl_put_right:NV \l__siunitx_number_out_tl \l__siunitx_output_quotient_tl
  \tl_put_right:NV \l__siunitx_number_out_tl
    \l__siunitx_number_denominator_tl
  \__siunitx_number_output_single_aux:
}
```

For units, the fraction code is replaced by the symbol code:

```
\cs_undefine:N \__siunitx_unit_format_fraction_fraction:
\cs_new_protected:Npn \__siunitx_unit_format_fraction_fraction: {
  \__siunitx_unit_format_fraction_symbol_aux:
  \int_compare:nNnT { \l__siunitx_unit_denominator_int } > { 1 }
    {
      \bool_if:NT \l__siunitx_unit_denominator_bracket_bool
        {
       \tl_put_left:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_open_tl
       \tl_put_right:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_close_tl
        }
```

```
    }
  \tl_set_eq:NN \l__siunitx_unit_tl \l__siunitx_unit_numerator_tl
  \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_per_symbol_tl
  \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_unit_denominator_tl
}

\cs_undefine:N \__siunitx_angle_print_astronomy_aux:
\cs_new_protected:Npn \__siunitx_angle_print_astronomy_aux: {
  \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-integer }
    \l__siunitx_tmpa_tl
    { \__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}% lwarp
 {% lateximage
  \hbox_set:Nn \l__siunitx_angle_marker_box
    {
      \__siunitx_print:nn { number } { { \l__siunitx_output_decimal_tl } }
    }
  \hbox_set:Nn \l__siunitx_angle_unit_box
    {
      \__siunitx_print:nV { unit } \l__siunitx_unit_tl
      \skip_horizontal:n { -\scriptspace }
    }
  \__siunitx_angle_print_astronomy_aux:n { marker }
  \__siunitx_angle_print_astronomy_aux:n { unit }
  \hbox_set:Nn \l__siunitx_angle_marker_box
    {
      \box_use:N \l__siunitx_angle_marker_box
      \box_use:N \l__siunitx_angle_unit_box
    }
  \dim_compare:nNnTF
    { \l__siunitx_angle_marker_dim } > { \l__siunitx_angle_unit_dim }
    { \__siunitx_angle_print_astronomy_marker: }
    { \__siunitx_angle_print_astronomy_unit: }
 }% lateximage
 {% not a lateximage
      \__siunitx_print:nV { unit } \l__siunitx_unit_tl
      \__siunitx_print:nn { number } { { \l__siunitx_output_decimal_tl } }
 }% not a lateximage
  \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-decimal }
    \l__siunitx_tmpa_tl
    { \__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
}

\RenewDocumentCommand \num { o m } {
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueF {#1}
      { \keys_set:nn { siunitx } {#1} }
    \__siunitx_number_output:n {#2}
  \group_end:% lwarp
}

```

```
\RenewDocumentCommand \numrange { o m m } {
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueF {#1}
      { \keys_set:nn { siunitx } {#1} }
    \__siunitx_range_numbers:nn {#2} {#3}
  \group_end:% lwarp
}

\RenewDocumentCommand \ang { o > { \SplitArgument { 2 } { ; } } m } {
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \IfNoValueF {#1}
      { \keys_set:nn { siunitx } {#1} }
    \__siunitx_angle_output:nnn #2
  \group_end:% lwarp
}

\RenewDocumentCommand \si { o m } {
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueTF {#1}
      { \__siunitx_unit_output:nn {#2} { } }
      {
        \keys_set:nn { siunitx } {#1}
        \__siunitx_unit_output:nn {#2} {#1}
      }
  \group_end:% lwarp
}


\RenewDocumentCommand{\SIrange}{o m m m}
{%
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueTF {#1}
      { \__siunitx_range_unit:nnnn {#4} { } {#2} {#3} }
      {
        \keys_set:nn { siunitx } {#1}
        \__siunitx_range_unit:nnnn {#4} {#1} {#2} {#3}
      }
  \group_end:% lwarp
}

\ExplSyntaxOff
```

File 317 **lwarp-soul.sty**

§ 414 Package **soul**

(*Emulates or patches code by* Melchior FRANZ.)

Pkg soul Emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{soul}[2003/11/17]
\RequirePackage{xcolor}% for \convertcolorspec
```

Storage for the colors to use:

```
\newcommand*{\LWR@soululcolor}{}

\newcommand*{\LWR@soulstcolor}{}

% \definecolor{LWR@soulhlcolordefault}{HTML}{F8E800}
% \newcommand*{\LWR@soulhlcolor}{LWR@soulhlcolordefault}
\newcommand*{\LWR@soulhlcolor}{}
```

\so {⟨*text*⟩}

Basic markup with CSS:

```
\newcommand{\so}[1]{%
\InlineClass(letter-spacing:.2ex){letterspacing}{#1}%
}
```

\caps {⟨*text*⟩}

```
\newcommand{\caps}[1]{%
    \InlineClass%
        (font-variant:small-caps;letter-spacing:.1ex)%
        {capsspacing}{#1}%
}
```

\LWR@soulcolor {⟨*text*⟩} {⟨*color*⟩} {⟨*class*⟩} {⟨*colorstyle*⟩} {⟨*FormatWPstyle*⟩}

Add colors if not empty:

```
\newcommand{\LWR@soulcolor}[5]{%
\ifcsempty{#2}%
{%
    \InlineClass(#5){#3}{#1}%
}%
{%
    \convertcolorspec{named}{\@nameuse{#2}}{HTML}\LWR@tempcolor%
    \LWR@htmlspanclass[#5;#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}%
}%
}
```

```
\newcommand{\ul}[1]{%
\LWR@soulcolor{#1}{LWR@soululcolor}{uline}{text-decoration-color}%
    {text-decoration:underline; text-decoration-skip: auto;}%
}

\newcommand{\st}[1]{
\LWR@soulcolor{#1}{LWR@soulstcolor}{sout}{text-decoration-color}%
    {text-decoration:line-through}%
}

\newcommand{\hl}[1]{
\LWR@soulcolor{#1}{LWR@soulhlcolor}{highlight}{background-color}%
    {background:\LWR@origpound{}F8E800}
}
```

Nullified:

```
\newcommand*{\soulaccent}[1]{}
\newcommand*{\soulregister}[2]{}
\newcommand{\sloppyword}[1]{#1}
\newcommand*{\sodef}[5]{\DeclareRobustCommand*#1[1]{\so{##1}}}
\newcommand*{\resetso}{}
\newcommand*{\capsdef}[5]{}
\newcommand*{\capsreset}{}
\newcommand*{\capssave}[1]{}
\newcommand*{\capsselect}[1]{}
\newcommand*{\setul}[2]{}
\newcommand*{\resetul}{}
\newcommand*{\setuldepth}[1]{}
\newcommand*{\setuloverlap}[1]{}
```

Set colors:

```
\newcommand*{\setulcolor}[1]{\renewcommand{\LWR@soululcolor}{#1}}
\newcommand*{\setstcolor}[1]{\renewcommand{\LWR@soulstcolor}{#1}}
\newcommand*{\sethlcolor}[1]{\renewcommand{\LWR@soulhlcolor}{#1}}
```

Long versions of the user-level macros:

```
\let\textso\so
\let\textul\ul
\let\texthl\hl
\let\textcaps\caps
```

File 318 **lwarp-soulpos.sty**

§ 415 Package soulpos

(*Emulates or patches code by* Javier Bezos.)

Pkg soulpos soulpos is emulated.

for HTML output:

```
\RequirePackage{soul}
\RequirePackage{soulutf8}
\LWR@ProvidesPackageDrop{soulpos}[2012/02/25]

\NewDocumentCommand{\ulposdef}{m o m}{}

\newdimen\ulwidth

\newcommand\ifulstarttype[1]{%
\expandafter\@secondoftwo%
}

\newcommand\ifulendtype[1]{%
\expandafter\@secondoftwo%
}

\newcommand{\ulstarttype}{0}
\newcommand{\ulendtype}{0}
\newcommand\ulpostolerance{0}%
```

File 319 **lwarp-soulutf8.sty**

§ 416 Package soulutf8

Pkg soulutf8 soulutf8 is emulated.

lwarp's HTML output naturally supports UTF-8 encoding.

for HTML output:

```
\LWR@ProvidesPackageDrop{soulutf8}[2016/05/16]
```

File 320 **lwarp-splitidx.sty**

§ 417 Package splitidx

(*Emulates or patches code by* Markus Kohm.)

Pkg splitidx splitidx is patched for use by lwarp.

If the `latexmk` option is selected for lwarp, *latexmk* will compile the document but will *not* compile the indexes. **`lwarpmk printindex`** and **`lwarpmk htmlindex`** will still be required.

⚠ `\thepage` When using `\AtWriteToIndex` or `\AtNextWriteToIndex`, the user must not refer to `\thepage` during HTML output, as the concept of a page number is meaningless. Instead, do

```
\addtocounter{LWR@autoindex}{1}
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}
```

where the \index-like action occurs, and then refer to \arabic{LWR@autoindex} instead of \thepage where the reference should occur.

See section 504.17 in the lwarp-patch-memoir package for the \@@wrspindexhyp macro as an example.

for HTML output:

```
\LWR@ProvidesPackagePass{splitidx}[2016/02/18]

\catcode`\_=12%
\xpatchcmd{\newindex}
    {\jobname-#2.idx}
    {\jobname-#2_html.idx}
    {}
    {\LWR@patcherror{splitidx}{@newindex}}
\catcode`\_=8%
```

Patched to use lwarp's automatic indexing counter instead of \thepage:

```
\renewcommand*{\@wrsindex}[2][]{%
  \ifx\relax#1\relax
    \if@splitidx
      \@wrsindex[idx]{#2}%
    \else
      \def\@tempa{#2}%
      \if@verbindex\@onelevel@sanitize\@tempa\fi
      \@wrindex{\@tempa}%
    \fi
  \else
    \def\@tempa{#2}%
    \csname index@#1@hook\endcsname
%     \expandafter\ifx\csname @@wrsindex\endcsname\relax
    \addtocounter{LWR@autoindex}{1}%                    lwarp
    \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%    lwarp
%       \@@@wrsindex{#1}{{\@tempa}{\thepage}}%
      \@@@wrsindex{#1}{{\@tempa}{\arabic{LWR@autoindex}}}%
%     \else
%       \def\@tempb{\@@wrsindex{#1}}%
%       \expandafter\@tempb\@tempa||\\%
%     \fi
    \endgroup
    \@esphack
  \fi
}
```

lwarp defines sectioning commands with xparse, so the below patches are done as temporary redefinitions instead of being \let.

```
\xpatchcmd{\printsubindex}
    {\let\section\subsection}
    {\renewcommand*{\section}{\subsection}}
    {}
    {\LWR@patcherror{splitidx}{printsubindex-section}}

\xpatchcmd{\printsubindex}
    {\let\chapter\section}
```

```
    {\renewcommand*{\chapter}{\section}}
    {}
    {\LWR@patcherror{splitidx}{printsubindex-chapter}}

\xpatchcmd{\printsubindex}
    {\let\@makechapterhead\section}
    {\def\@makechapterhead{\section}}
    {}
    {\LWR@patcherror{splitidx}{printsubindex-chapter}}
```

File 321 **lwarp-srcltx.sty**

§ 418 Package srcltx

Pkg srcltx srcltx is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{srcltx}[2006/11/12]

\newif\ifSRCOK \SRCOKfalse
\newcommand*\srcIncludeHook[1]{}
\newcommand*\srcInputHook[1]{}
\newcommand*\MainFile{}
\def\MainFile{\jobname.tex}
\newcommand*\CurrentInput{}
\gdef\CurrentInput{\MainFile}
\newcommand\Input{}
\let\Input\input
```

File 322 **lwarp-srctex.sty**

§ 419 Package srctex

Pkg srctex srctex is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{srctex}[2006/11/12]
\LWR@origRequirePackage{lwarp-srcltx}
```

File 323 **lwarp-stabular.sty**

§ 420 Package stabular

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg stabular stabular is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{stabular}[2014/03/20]
```

Env stabular [⟨*vpos*⟩] {⟨*colspec*⟩}

```
\newenvironment{stabular}[2][c]
{
\begin{tabular}[#1]{#2}
\renewcommand{\noalign}[1]{}
}
{\end{tabular}}
```

Env stabular {⟨*width*⟩} [⟨*vpos*⟩] {⟨*colspec*⟩}

```
\NewDocumentEnvironment{stabular*}{m o m}
{
\begin{tabular}[#2]{#3}
\renewcommand{\noalign}[1]{}
}
{\end{tabular}}
```

File 324 **lwarp-stfloats.sty**

§ 421 Package stfloats

Pkg stfloats stfloats is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{stfloats}[2017/03/27]
```

stfloats may have been preloaded by a ltj* class.

The following are provided in case they have not yet been defined:

```
\providecommand*{\fnbelowfloat}{}
\providecommand*{\fnunderfloat}{}
\providecommand*{\setbaselinefloat}{}
\providecommand*{\setbaselinefixed}{}
```

Nullified for HTML:

```
\renewcommand*{\fnbelowfloat}{}
\renewcommand*{\fnunderfloat}{}
\renewcommand*{\setbaselinefloat}{}
\renewcommand*{\setbaselinefixed}{}
```

File 325 **lwarp-struktex.sty**

§ 422 Package struktex

(*Emulates or patches code by* Jobst Hoffmann.)

Pkg struktex struktex is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{struktex}[2018/06/04]

\BeforeBeginEnvironment{struktogramm}{\begin{lateximage}[(struktogramm)]}
\AfterEndEnvironment{struktogramm}{\end{lateximage}}

\newenvironment{LWR@HTML@centernss}{\begin{center}}{\end{center}}
\LWR@formattedenv{centernss}

\newcommand{\LWR@HTML@CenterNssFile}[1]{%
    \begin{center}
    \input{#1.nss}
    \end{center}
}
\LWR@formatted{CenterNssFile}

\newcommand{\LWR@HTML@centernssfile}{\LWR@HTML@CenterNssFile}
\LWR@formatted{centernssfile}
```

File 326 **lwarp-subcaption.sty**

§ 423 Package

subcaption

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg subcaption

subcaption is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{subcaption}[2018/05/01]
```

Tells lwarp to ignore minipage widths inside a subfigure or subtable. In print mode the minipages are used to place the items next to each other. In HTML they are placed side-by-side automatically.

```
\ifdef{\subcaption@minipage}{
    \xpatchcmd{\subcaption@minipage}
        {\minipage}
        {\minipagefullwidth\minipage}
        {}
        {\LWR@patcherror{subcaption}{subcaption@minipage}}
}{}
```

Likewise for a \subcaptionbox:

```
\ifdef{\subcaptionbox}{
    \xpretocmd{\subcaptionbox}
        {\minipagefullwidth}
        {}
        {\LWR@patcherror{subcaption}{subcaptionbox}}
}{}
```

File 327 **lwarp-subfig.sty**

§ 424 Package

subfig

(*Emulates or patches code by* Steven Douglas Cochran.)

Pkg subfig subfig is supported and patched by lwarp.

⚠ lof/lotdepth At present, the package options for lofdepth and lotdepth are not working. These counters must be set separately after the package has been loaded.

In the document source, use \hfill and \hspace* subfig>inline between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

for HTML output: Accept all options for lwarp-subfig:

```
\LWR@ProvidesPackagePass{subfig}[2005/06/28]
```

\sf@@@subfloat {⟨*1 type*⟩} [⟨*2 LOF entry*⟩] [⟨*3 caption*⟩] {⟨*4 contents*⟩}

The outer minipage allows side-by-side subfloats with \hfill between.

```
\long\def\sf@@@subfloat#1[#2][#3]#4{%
\begin{minipage}{\linewidth}% lwarp

\IfValueTF{#2}{%
    \LWR@setlatestname{#2}%
}{%
    \IfValueTF{#3}{%
        \LWR@setlatestname{#3}%
    }{}%
}%
\LWR@stoppars% lwarp
    \@ifundefined{FBsc@max}{}%
        {\FB@readaux{\let\FBsuboheight\relax}}%
    \@tempcnta=\@ne
    \if@minipage
      \@tempcnta=\z@
    \else\ifdim \lastskip=\z@ \else
      \@tempcnta=\tw@
    \fi\fi
    \ifmaincaptiontop
      \sf@top=\sf@nearskip
      \sf@bottom=\sf@farskip
    \else
      \sf@top=\sf@farskip
      \sf@bottom=\sf@nearskip
    \fi
    \leavevmode
```

```
%     \setbox\@tempboxa \hbox{#4}%
%     \@tempdima=\wd\@tempboxa
%     \@ifundefined{FBsc@max}{}%
%         {\global\advance\Xhsize-\wd\@tempboxa
%          \dimen@=\ht\@tempboxa
%          \advance\dimen@\dp\@tempboxa
%          \ifdim\dimen@>\FBso@max
%            \global\FBso@max\dimen@
%          \fi}%
```

Do not use boxes, which interfere with `lateximages`:

```
%     \vtop%
   \bgroup
%       \vbox%
      \bgroup
        \ifcase\@tempcnta
          \@minipagefalse
        \or
%           \vskip\sf@top
        \or
          \ifdim \lastskip=\z@ \else
%             \@tempskipb\sf@top\relax\@xaddvskip
          \fi
        \fi
        \sf@ifpositiontop{%
          \ifx \@empty#3\relax \else
            \sf@subcaption{#1}{#2}{#3}%
%             \vskip\sf@capskip
%             \vskip\sf@captopadj
          \fi\egroup
%           \hrule width0pt height0pt depth0pt
            \LWR@startpars% lwarp
%  \box\@tempboxa
            #4
            \LWR@stoppars% lwarp
        }{%
        \LWR@startpars% lwarp
        \@ifundefined{FBsc@max}%
            {
%  \box\@tempboxa
                #4
            }%
            {\ifx\FBsuboheight\relax
%                \box\@tempboxa
                #4
             \else
%                 \vbox to \FBsuboheight{\FBafil\box\@tempboxa\FBbfil}%
                #4
             \fi}%
        \LWR@stoppars% lwarp
          \egroup
          \ifx \@empty#3\relax \else
%             \vskip\sf@capskip
%             \hrule width0pt height0pt depth0pt
            \sf@subcaption{#1}{#2}{#3}%
```

```
          \fi
        }%
%       \vskip\sf@bottom
    \egroup
    \@ifundefined{FBsc@max}{}%
        {\addtocounter{FRobj}{-1}%
         \ifnum\c@FRobj=0\else
           \subfloatrowsep
         \fi}%
    \ifmaincaptiontop\else
      \global\advance\@nameuse{c@\@captype}\m@ne
    \fi
\end{minipage}% lwarp
\LWR@startpars% lwarp
  \endgroup\ignorespaces%
}%
```

\sf@subcaption {⟨*1 type*⟩} {⟨*2* LOF *entry*⟩} {⟨*3 caption*⟩}

```
\long\def\sf@subcaption#1#2#3{%
\LWR@stoppars% lwarp
  \ifx \relax#2\relax \else
    \bgroup
      \let\label=\@gobble
      \let\protect=\string
      \def\@subcaplabel{%
        \caption@lstfmt{\@nameuse{p@#1}}{\@nameuse{the#1}}}%
      \sf@updatecaptionlist{#1}{#2}{\the\value{\@captype}}{\the\value{#1}}%
    \egroup
  \fi
  \bgroup
    \ifx \relax#3\relax
      \let\captionlabelsep=\relax
    \fi
%     \setbox0\vbox{%
%        \hb@xt@\the\@tempdima{%
%
% %          \hss
% %         \parbox[t]{\the\@tempdima}{%
%           \caption@make
%               {\@nameuse{sub\@captype name}}%
%               {\@nameuse{thesub\@captype}}%
%               {#3}
% %  }%
% %            \hss
%   }
%  }%
    \@ifundefined{FBsc@max}%
%         {\box0}%
        {
%  \parbox[t]{\the\@tempdima}{%
\LWR@traceinfo{sfsubcap B1}% lwarp
            \LWR@figcaption% lwarp
            \caption@make
                {\@nameuse{sub\@captype name}}%
```

```
                {\@nameuse{thesub\@captype}}%
                {\LWR@isolate{#3}}%

            \endLWR@figcaption% lwarp
\LWR@traceinfo{sfsubcap B2}% lwarp
%  }%
        }%
        {\dimen@\ht0%
         \advance\dimen@\dp0%
         \ifdim\dimen@>\FBsc@max
           \global\FBsc@max\dimen@
         \fi
         \FB@readaux{\let\FBsubcheight\relax}%
         \ifx\FBsubcheight\relax
           \def\next{
%  \parbox[t]{\the\@tempdima}
            }%
         \else
           \def\next{
%  \parbox[t][\FBsubcheight][t]{\the\@tempdima}
            }%
         \fi
%          \vbox{%
%            \hb@xt@\the\@tempdima{%

%              \hss
%              \next{%
\LWR@traceinfo{sfsubcap C1}% lwarp
                \caption@make
                    {\@nameuse{sub\@captype name}}%
                    {\@nameuse{thesub\@captype}}%
                    {#3}
\LWR@traceinfo{sfsubcap C1}% lwarp
%  }%
%              \hss

%  }
%           }
        }%
  \egroup
\LWR@startpars% lwarp
}
```

\subfloat@label Patches for \sf@sub@label:

```
\def\subfloat@label{%
\LWR@ensuredoingapar% lwarp
  \@ifnextchar(%   %) match left parenthesis
    {\sf@sub@label}
    {\sf@sub@label(Sub\@captype\space
                   \@ifundefined{thechapter}{}{\@nameuse{thechapter}\space}%
                   \@nameuse{p@sub\@captype}%
                   \@nameuse{thesub\@captype}.)}}
```

Patches for \subref.

\sf@subref {⟨*label*⟩}

The unstarred version uses a \ref link whose printed text comes from the sub@<label>:

```
\renewcommand{\sf@subref}[1]{%
\LWR@subnewref{#1}{sub@#1}%
}
```

\sf@@subref {⟨*label*⟩}

The starred version uses the printed sub@<label> which is stored as if it were a page number:

```
\renewcommand{\sf@@subref}[1]{\LWR@orig@pageref{sub@#1}}
```

Defining new subfloats. The l@sub<type> for each is redefined.

\@newsubfloat [⟨*keys/values*⟩] {⟨*float name*⟩}

```
\LetLtxMacro\LWR@orig@newsubfloat\@newsubfloat

\def\@newsubfloat[#1]#2{%
\LWR@orig@newsubfloat[#1]{#2}%
\renewcommand{\l@sub#2}[2]{\hypertocfloat{2}{sub#2}{\ext@sub#2}{##1}{##2}}%
}
```

Pre-defined for figures and tables:

\l@subfigure {⟨*text*⟩} {⟨*pagenum*⟩}

```
\renewcommand{\l@subfigure}[2]{\hypertocfloat{2}{subfigure}{lof}{#1}{#2}}
```

\l@subtable {⟨*text*⟩} {⟨*pagenum*⟩}

```
\renewcommand{\l@subtable}[2]{\hypertocfloat{2}{subtable}{lot}{#1}{#2}}
```

File 328 **lwarp-subfigure.sty**

§ 425 Package

subfigure

Pkg subfigure

subfigure is emulated by subfig.

for HTML output:

```
\LWR@ProvidesPackageDrop{subfigure}[2002/03/15]
\RequirePackage{subfig}

\LetLtxMacro\subfigure\subfloat
\LetLtxMacro\subtable\subfloat
\LetLtxMacro\Subref\subref
\@ifundefined{figuretopcaptrue}{\newif\iffiguretopcap}{}
\newif\ifsubfiguretopcap
\newif\ifsubcaphang
\newif\ifsubcapcenter
```

```
\newif\ifsubcapcenterlast
\newif\ifsubcapnooneline
\newif\ifsubcapraggedright
\newskip\subfigtopskip
\newskip\subfigcapskip
\newdimen\subfigcaptopadj
\newskip\subfigbottomskip
\newdimen\subfigcapmargin
\newskip\subfiglabelskip
\newcommand*{\subcapsize}{}
\newcommand*{\subcaplabelfont}{}
\newcommand*{\subcapfont}{}
```

File 329 **lwarp-supertabular.sty**

§ 426 Package

supertabular

(*Emulates or patches code by* Johannes Braams, Theo Jurriens.)

Pkg supertabular supertabular is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{supertabular}[2004/02/20]
```

⚠ Misplaced alignment tab character &

For `\tablefirsthead`, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
. . .
\StopDefiningTabulars
```

See section 9.10.

⚠ lateximage supertabular and xtab are not supported inside a `lateximage`.

```
\newcommand{\LWRST@firsthead}{}

\newcommand{\tablefirsthead}[1]{%
    \long\gdef\LWRST@firsthead{#1}%
}

\newcommand{\tablehead}[1]{}
\newcommand{\tabletail}[1]{}

\newcommand{\LWRST@lasttail}{}

\newcommand{\tablelasttail}[1]{%
    \long\gdef\LWRST@lasttail{#1}%
}


\newcommand{\tablecaption}[2][]{%
    \long\gdef\LWRST@caption{%
        \ifblank{#1}%
```

```
            {\caption{#2}}%
            {\caption[#1]{#2}}%
    }%
}

\let\topcaption\tablecaption
\let\bottomcaption\tablecaption


\newcommand*{\LWRST@caption}{}

\newcommand*{\shrinkheight}[1]{}

\NewDocumentEnvironment{supertabular}{s o m}
{%
\LWR@traceinfo{supertabular}%
\begin{table}%
\LWRST@caption%
\begin{tabular}{#3}%
\TabularMacro\ifdefvoid{\LWRST@firsthead}%
{\LWR@getmynexttoken}%
{\expandafter\LWR@getmynexttoken\LWRST@firsthead}%
}%
{%
\ifdefvoid{\LWRST@lasttail}%
{}%
{%
\TabularMacro\ResumeTabular%
\LWRST@lasttail%
}%
\end{tabular}%
\end{table}%
\LWR@traceinfo{supertabular done}%
}

\NewDocumentEnvironment{mpsupertabular}{s o m}
{\minipage{\linewidth}\supertabular{#3}}
{\endsupertabular\endminipage}
```

File 330 **lwarp-syntonly.sty**

§ 427 Package

syntonly

(*Emulates or patches code by* Frank Mittelbach, Rainer Schöpf.)

Pkg syntonly Emulated.

for HTML output: Discard all options for lwarp-syntonly:

```
\LWR@ProvidesPackageDrop{syntonly}[2017/06/30]

\newif\ifsyntax@
\syntax@false
```

```
4
5 \newcommand*{\syntaxonly}{}
6
7 \@onlypreamble\syntaxonly
```

File 331 **lwarp-tablefootnote.sty**

§ 428 Package tablefootnote

Pkg tablefootnote tablefootnote is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{tablefootnote}[2014/01/26]
```

This works because in HTML tables are no longer floats.

```
2 \LetLtxMacro\tablefootnote\footnote
```

File 332 **lwarp-tabls.sty**

§ 429 Package tabls

(*Emulates or patches code by* Donald Arseneau.)

Pkg tabls tabls is emulated. `\LWR@hline` is used to handle the optional argument when tabls is loaded.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{tabls}

2 \newdimen\tablinesep
3 \newdimen\arraylinesep
4 \newdimen\extrarulesep
```

File 333 **lwarp-tabularx.sty**

§ 430 Package tabularx

(*Emulates or patches code by* David Carlisle.)

Pkg tabularx tabularx is emulated by lwarp.

for HTML output: Discard all options for lwarp-tabularx:

```
1 \LWR@ProvidesPackageDrop{tabularx}[2016/02/03]

2 \DeclareDocumentEnvironment{tabularx}{m o m}
3 {\tabular{#3}}
4 {\endtabular}
```

```
5
6 \DeclareDocumentEnvironment{tabularx*}{m o m}
7 {\tabular{#3}}
8 {\endtabular}
```

File 334 **lwarp-tabulary.sty**

§ 431 Package tabulary

(*Emulates or patches code by* David Carlisle.)

Pkg tabulary tabulary is emulated by lwarp.

for HTML output: Discard all options for lwarp-tabulary.

Column types L, C, R, and J are emulated by lwarp core code.

```
1 \LWR@ProvidesPackageDrop{tabulary}[2014/06/11]

2 \NewDocumentEnvironment{tabulary}{m o m}
3 {\tabular{#3}}
4 {\endtabular}
5
6 \NewDocumentEnvironment{tabulary*}{m o m}
7 {\tabular{#3}}
8 {\endtabular}
9
10 \newdimen\tymin
11 \newdimen\tymax
12 \def\tyformat{}
```

File 335 **lwarp-tascmac.sty**

§ 432 Package tascmac

Pkg tascmac tascmac is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{tascmac}[2018/03/09]

2 \newenvironment*{boxnote}
3     {
4         \BlockClass[
5             padding: .5ex ;
6             border: 1px solid black ;
7             border-top: 1px dashed black ;
8         ]{boxnote}
9     }
10    {\endBlockClass}
11
12 \newenvironment*{screen}[1][]
```

```
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid gray ;
            border-radius: 8pt
        ]{boxnote}
    }
    {\endBlockClass}

\newenvironment*{itembox}[2][]
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid gray ;
            border-radius: 8pt
        ]{boxnote}
        \InlineClass{itemboxtitle}{#2}\par
    }
    {\endBlockClass}

\newenvironment*{shadebox}
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid black ;
            box-shadow: 3px 3px 3px \#808080 ;
        ]{boxnote}
    }
    {\endBlockClass}

\newcommand*{\mask}[2]{%
    \InlineClass[background: lightgray]{mask}{#1}%
}

\newcommand*{\maskbox}[5]{%
    \InlineClass[background: lightgray]{mask}{#5}%
}

\newcommand*{\Maskbox}[6]{%
    \InlineClass[
        background: lightgray ;
        border: #5 solid black
    ]{mask}{#6}%
}

\newcommand*{\keytop}[2][]{%
    \InlineClass[%
        padding: .2ex ;
        border: 1px solid black ;
        border-radius: .7ex ;
    ]{keytop}{#2}%
}

\def\yen{\HTMLunicode{00A5}}

```

```
\def\return{\HTMLunicode{23CE}}

\def\Return{\HTMLunicode{23CE}}

\def\ascii{ASCII Corporation}

\def\Ascii{ASCII Corporation}

\def\ASCII{ASCII Corporation}
```

File 336 **lwarp-textarea.sty**

§ 433 Package textarea

(*Emulates or patches code by* Alexander I. Rozhenko.)

Pkg textarea textarea is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{textarea}[2005/12/26]

\newcommand\StartFromTextArea{}
\newcommand\StartFromHeaderArea{}
\newcommand*\RestoreTextArea{}
\newcommand*\ExpandTextArea[1][*]{}
\let\NCC@restoretextarea\@empty
```

File 337 **lwarp-textcomp.sty**

§ 434 Package textcomp

(*Emulates or patches code by* Frank Mittelbach, Robin Fairbairns, Werner Lemberg.)

Pkg textcomp textcomp is patched for use by lwarp.

§ 434.1 Limitations

Some textcomp symbols do not have Unicode equivalents, and thus are not supported.

⚠ missing symbols Many textcomp symbols are not supported by many fonts. In the css try referencing fonts which are more complete, but expect to see gaps in coverage.

§ 434.2 Package loading

for HTML output:

```
\LWR@ProvidesPackagePass{textcomp}[2017/04/05]
```

§ 434.3 HTML symbols

For HTML, use HTML entities or direct Unicode, depending on the engine.

`\AtBeginDocument` improves support for LuaLaTeX and XeLaTeX.

§ 434.3.1 pdfLaTeX symbols

```
\AtBeginDocument{
\ifPDFTeX% pdflatex or dvi latex
\newcommand*{\LWR@HTML@textdegree}{\HTMLentity{deg}}
\newcommand*{\LWR@HTML@textcelsius}{\HTMLunicode{2103}}
\newcommand*{\LWR@HTML@textohm}{\HTMLunicode{2126}}
\newcommand*{\LWR@HTML@textmu}{\HTMLunicode{00B5}}
\newcommand*{\LWR@HTML@textlquill}{\HTMLunicode{2045}}
\newcommand*{\LWR@HTML@textrquill}{\HTMLunicode{2046}}
\newcommand*{\LWR@HTML@textcircledP}{\HTMLunicode{2117}}
\newcommand*{\LWR@HTML@texttwelveudash}{\HTMLunicode{2014}}% emdash
\newcommand*{\LWR@HTML@textthreequartersemdash}{\HTMLunicode{2014}}% emdash
\newcommand*{\LWR@HTML@textmho}{\HTMLunicode{2127}}
\newcommand*{\LWR@HTML@textnaira}{\HTMLunicode{20A6}}
\newcommand*{\LWR@HTML@textpeso}{\HTMLunicode{20B1}}
\newcommand*{\LWR@HTML@textrecipe}{\HTMLunicode{211E}}
\newcommand*{\LWR@HTML@textinterrobangdown}{\HTMLunicode{2E18}}
\newcommand*{\LWR@HTML@textperthousand}{\HTMLunicode{2030}}
\newcommand*{\LWR@HTML@textpertenthousand}{\HTMLunicode{2031}}
\newcommand*{\LWR@HTML@textbaht}{\HTMLunicode{0E3F}}
\newcommand*{\LWR@HTML@textdiscount}{\%}
\newcommand*{\LWR@HTML@textservicemark}{\HTMLunicode{2120}}
\else
```

§ 434.3.2 XeLaTeX and LuaLaTeX symbols

NOTE: Some of the following do not print well in the listing. Consult the .dtx or .sty file for the actual characters.

```
\newcommand*{\LWR@HTML@textdegree}{°}
\newcommand*{\LWR@HTML@textcelsius}{}
\newcommand*{\LWR@HTML@textohm}{}
\newcommand*{\LWR@HTML@textmu}{µ}
\newcommand*{\LWR@HTML@textlquill}{}
\newcommand*{\LWR@HTML@textrquill}{}
\newcommand*{\LWR@HTML@textcircledP}{}
\newcommand*{\LWR@HTML@texttwelveudash}{---}% emdash
\newcommand*{\LWR@HTML@textthreequartersemdash}{---}% emdash
\newcommand*{\LWR@HTML@textmho}{}
\newcommand*{\LWR@HTML@textnaira}{}
\newcommand*{\LWR@HTML@textpeso}{}
\newcommand*{\LWR@HTML@textrecipe}{}
```

```
\newcommand*{\LWR@HTML@textinterrobangdown}{}
\newcommand*{\LWR@HTML@textperthousand}{%}
\newcommand*{\LWR@HTML@textpertenthousand}{%}
\newcommand*{\LWR@HTML@textbaht}{}
\newcommand*{\LWR@HTML@textdiscount}{\%}
\newcommand*{\LWR@HTML@textservicemark}{}
\fi

\LWR@formatted{textdegree}
\LWR@formatted{textcelsius}
\LWR@formatted{textohm}
\LWR@formatted{textmu}
\LWR@formatted{textlquill}
\LWR@formatted{textrquill}
\LWR@formatted{textcircledP}
\LWR@formatted{texttwelveudash}
\LWR@formatted{textthreequartersemdash}
\LWR@formatted{textmho}
\LWR@formatted{textnaira}
\LWR@formatted{textpeso}
\LWR@formatted{textrecipe}
\LWR@formatted{textinterrobangdown}
\LWR@formatted{textperthousand}
\LWR@formatted{textpertenthousand}
\LWR@formatted{textbaht}
\LWR@formatted{textdiscount}
\LWR@formatted{textservicemark}
```

§ 434.4 HTML diacritics

For HTML, Unicode diacritical marks are used:

```
\newcommand*{\LWR@HTML@capitalcedilla}[1]{#1\HTMLunicode{0327}}
\newcommand*{\LWR@HTML@capitalogonek}[1]{#1\HTMLunicode{0328}}
\newcommand*{\LWR@HTML@capitalgrave}[1]{#1\HTMLunicode{0300}}
\newcommand*{\LWR@HTML@capitalacute}[1]{#1\HTMLunicode{0301}}
\newcommand*{\LWR@HTML@capitalcircumflex}[1]{#1\HTMLunicode{0302}}
\newcommand*{\LWR@HTML@capitaltilde}[1]{#1\HTMLunicode{0303}}
\newcommand*{\LWR@HTML@capitaldieresis}[1]{#1\HTMLunicode{0308}}
\newcommand*{\LWR@HTML@capitalhungarumlaut}[1]{#1\HTMLunicode{30B}}
\newcommand*{\LWR@HTML@capitalring}[1]{#1\HTMLunicode{30A}}
\newcommand*{\LWR@HTML@capitalcaron}[1]{#1\HTMLunicode{30C}}
\newcommand*{\LWR@HTML@capitalbreve}[1]{#1\HTMLunicode{306}}
\newcommand*{\LWR@HTML@capitalmacron}[1]{#1\HTMLunicode{304}}
\newcommand*{\LWR@HTML@capitaldotaccent}[1]{#1\HTMLunicode{307}}
```

`\textcircled` becomes a span with a rounded border. `\providecommand` is used to avoid conflict with xunicode.

```
\providecommand*{\LWR@HTML@textcircled}[1]{%
\InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{#1}%
}

\LWR@formatted{capitalcedilla}
\LWR@formatted{capitalogonek}
```

```
\LWR@formatted{capitalgrave}
\LWR@formatted{capitalacute}
\LWR@formatted{capitalcircumflex}
\LWR@formatted{capitaltilde}
\LWR@formatted{capitaldieresis}
\LWR@formatted{capitalhungarumlaut}
\LWR@formatted{capitalring}
\LWR@formatted{capitalcaron}
\LWR@formatted{capitalbreve}
\LWR@formatted{capitalmacron}
\LWR@formatted{capitaldotaccent}
\LWR@formatted{textcircled}
```

Nullify textcomp macros when generating filenames:

```
\FilenameNullify{%
    \renewcommand*{\textdegree}{}%
    \renewcommand*{\textcelsius}{}%
    \renewcommand*{\textohm}{}%
    \renewcommand*{\textmu}{}%
    \renewcommand*{\textlquill}{}%
    \renewcommand*{\textrquill}{}%
    \renewcommand*{\textcircledP}{}%
    \renewcommand*{\texttwelveudash}{}%
    \renewcommand*{\textthreequartersemdash}{}%
    \renewcommand*{\textmho}{}%
    \renewcommand*{\textnaira}{}%
    \renewcommand*{\textpeso}{}%
    \renewcommand*{\textrecipe}{}%
    \renewcommand*{\textinterrobangdown}{}%
    \renewcommand*{\textperthousand}{}%
    \renewcommand*{\textpertenthousand}{}%
    \renewcommand*{\textbaht}{}%
    \renewcommand*{\textdiscount}{}%
    \renewcommand*{\textservicemark}{}%
    \renewcommand*{\textcircled}[1]{#1}%
    \renewcommand*{\capitalcedilla}[1]{#1}%
    \renewcommand*{\capitalogonek}[1]{#1}%
    \renewcommand*{\capitalgrave}[1]{#1}%
    \renewcommand*{\capitalacute}[1]{#1}%
    \renewcommand*{\capitalcircumflex}[1]{#1}%
    \renewcommand*{\capitaltilde}[1]{#1}%
    \renewcommand*{\capitaldieresis}[1]{#1}%
    \renewcommand*{\capitalhungarumlaut}[1]{#1}%
    \renewcommand*{\capitalring}[1]{#1}%
    \renewcommand*{\capitalcaron}[1]{#1}%
    \renewcommand*{\capitalbreve}[1]{#1}%
    \renewcommand*{\capitalmacron}[1]{#1}%
    \renewcommand*{\capitaldotaccent}[1]{#1}%
}% FilenameNullify

}% AtBeginDocument
```

File 338 **lwarp-textfit.sty**

§ 435 Package textfit

Pkg textfit textfit is emulated.

Text is placed into a of class `textfit`. Sizes are approximated, and also limited by browser min/max font-size settings.

for HTML output:

```
\LWR@ProvidesPackageDrop{textfit}[1994/04/15]

\newsavebox{\LWR@textfitbox}

\newcommand*{\LWR@textfitscale}[2]{%
\setlength{\LWR@templengthone}{#1}%
\setlength{\LWR@templengthone}{%
    1em*\ratio{\LWR@templengthone}{\LWR@templengthtwo}%
}%
\InlineClass[font-size:\LWR@printlength{\LWR@templengthone}]{textfit}{#2}%
}

\newcommand*{\scaletowidth}[2]{%
\sbox{\LWR@textfitbox}{#2}%
\settowidth{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
\LWR@textfitscale{#1}{#2}%
}

\newcommand*{\scaletoheight}[2]{%
\sbox{\LWR@textfitbox}{#2}%
\settoheight{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
\LWR@textfitscale{#1}{#2}%
}
```

File 339 **lwarp-textpos.sty**

§ 436 Package textpos

(*Emulates or patches code by* Norman Gray.)

Pkg textpos textpos is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{textpos}[2016/06/07]

\NewDocumentEnvironment{textblock}{m r()}{}{}
\NewDocumentEnvironment{textblock*}{m o r()}{}{}
\newcommand*{\TPGrid}[3][]{}
\NewDocumentCommand{\TPMargin}{s o}{}
\newcommand*{\textblockcolour}[1]{}
```

```
\newcommand*{\textblockrulecolour}[1]{}
\newcommand*{\textblockcolor}[1]{}
\newcommand*{\textblockrulecolor}[1]{}
\newcommand*{\tekstblokkulur}[1]{}
\newcommand*{\tekstblokrulekulur}[1]{}
\newlength{\TPHorizModule}
\newlength{\TPVertModule}
\newlength{\TPboxrulesize}
\newcommand{\textblocklabel}[1]{}
\newcommand*{\showtextsize}{}
\newcommand{\textblockorigin}[2]{}
```

File 340 **lwarp-theorem.sty**

§ 437 Package theorem

(*Emulates or patches code by* Frank Mittelbach.)

Pkg theorem theorem is patched for use by lwarp.

Table 16: Theorem package — css styling of theorems and proofs

Theorem: of class theorembody<theoremstyle>

Theorem Header: of class theoremheader

where <theoremstyle> is plain, break, etc.

for HTML output:

```
\LWR@ProvidesPackagePass{theorem}[2014/10/28]
```

§ 437.1 Remembering the theorem style

Storage for the style being used for new theorems:

```
\newcommand{\LWR@newtheoremstyle}{plain}
```

Patched to remember the style being used for new theorems:

```
\gdef\theoremstyle#1{%
   \@ifundefined{th@#1}{\@warning
          {Unknown theoremstyle `#1'. Using `plain'}%
          \theorem@style{plain}%
           \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
          }%
      {%
          \theorem@style{#1}%
          \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
      }%
      \begingroup
        \csname th@\the\theorem@style \endcsname
      \endgroup}
```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```
\gdef\@xnthm#1#2[#3]{%
   \expandafter\@ifdefinable\csname #1\endcsname
   {%
    \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
    \@definecounter{#1}\@newctr{#1}[#3]%
    \expandafter\xdef\csname the#1\endcsname
      {\expandafter \noexpand \csname the#3\endcsname
       \@thmcountersep \@thmcounter{#1}}%
    \def\@tempa{\global\@namedef{#1}}%
    \expandafter \@tempa \expandafter{%
      \csname th@\the \theorem@style
            \expandafter \endcsname \the \theorem@bodyfont
     \@thm{#1}{#2}}%
    \global \expandafter \let \csname end#1\endcsname \@endtheorem
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
   }}

\gdef\@ynthm#1#2{%
    \expandafter\@ifdefinable\csname #1\endcsname
   {
    \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
    \@definecounter{#1}%
    \expandafter\xdef\csname the#1\endcsname{\@thmcounter{#1}}%
    \def\@tempa{\global\@namedef{#1}}\expandafter \@tempa
     \expandafter{\csname th@\the \theorem@style \expandafter
     \endcsname \the\theorem@bodyfont \@thm{#1}{#2}}%
    \global \expandafter \let \csname end#1\endcsname \@endtheorem
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
   }}

\gdef\@othm#1[#2]#3{%
  \expandafter\ifx\csname c@#2\endcsname\relax
   \@nocounterr{#2}%
  \else
   \expandafter\@ifdefinable\csname #1\endcsname
   {
    \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
    \expandafter \xdef \csname the#1\endcsname
     {\expandafter \noexpand \csname the#2\endcsname}%
    \def\@tempa{\global\@namedef{#1}}\expandafter \@tempa
     \expandafter{\csname th@\the \theorem@style \expandafter
     \endcsname \the\theorem@bodyfont \@thm{#2}{#3}}%
    \global \expandafter \let \csname end#1\endcsname \@endtheorem
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
    }%
  \fi}
```

§ 437.2 css patches

The following are patched for css.

These were in individual files `thp.sty` for plain, `thmb.sty` for margin break, etc. They are gathered together here.

Each theorem is encased in a `BlockClass` environment of class `theorembody<style>`.

Each header is encased in an `\InlineClass` of class `theoremheader`.

```
\gdef\th@plain{%
  \def\@begintheorem##1##2{%
        \item[
            \InlineClass{theoremheader}{##1\ ##2}
        ]
    }%
\def\@opargbegintheorem##1##2##3{%
   \item[
        \InlineClass{theoremheader}{##1\ ##2\ (##3)}
    ]
    }
}

\gdef\th@break{%
  \def\@begintheorem##1##2{%
    \item[
        \InlineClass{theoremheader}{##1\ ##2}\newline%
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
  \item[
        \InlineClass{theoremheader}{##1\ ##2\ (##3)}\newline
    ]
    }
}

\gdef\th@marginbreak{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2 \qquad ##1}\newline
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
        \InlineClass{theoremheader}{##2 \qquad ##1\ %
        (##3)}\newline
    ]
    }
}

\gdef\th@changebreak{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2\ ##1}\newline
    ]
```

```
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
        \InlineClass{theoremheader}{ ##2\ ##1\ %
        (##3)}\newline
    ]
    }
}

\gdef\th@change{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2\ ##1}
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
        \InlineClass{theoremheader}{##2\ ##1\ (##3)}
    ]
    }
}

\gdef\th@margin{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2 \qquad ##1}
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
            \InlineClass{theoremheader}{##2 \qquad ##1\ (##3)}
    ]
    }
}
```

Patched for css:

```
\gdef\@thm#1#2{\refstepcounter{#1}%
\LWR@forcenewpage% lwarp
    \BlockClass{theorembody\LWR@thisthmstyle}% lwarp
   \trivlist
   \@topsep \theorempreskipamount               % used by first \item
   \@topsepadd \theorempostskipamount           % used by \@endparenv
   \@ifnextchar [%
   {\@ythm{#1}{#2}}%
   {\@begintheorem{#2}{\csname the#1\endcsname}\ignorespaces}}

\gdef\@endtheorem{%
\endtrivlist
\endBlockClass
}
```

File 341 **lwarp-thinsp.sty**

§ 438 Package thinsp

Pkg thinsp thinsp is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{thinsp}[2016/10/02]

\AtBeginDocument{
\let\thinthinspace\relax% defined by some packages
\newcommand*{\thinthinspace}{\thinspace}
}

\newcommand*{\stretchthinspace}{\thinspace}
\newcommand*{\stretchthinthinspace}{\thinthinspace}
\newcommand*{\stretchnegthinspace}{\negthinspace}
```

File 342 **lwarp-threadcol.sty**

§ 439 Package threadcol

Pkg threadcol threadcol is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{threadcol}[2013/01/06]

\newcommand{\setthreadname}[1]{}
```

File 343 **lwarp-threeparttable.sty**

§ 440 Package threeparttable

(*Emulates or patches code by* Donald Arseneau.)

Pkg threeparttable threeparttable is emulated.

Table note are contained inside a css of class tnotes. If enumitem is used, the note item labels are also individually highlighted with an additional css of class tnoteitemheader, otherwise they are plain text.

for HTML output:

```
\LWR@ProvidesPackageDrop{threeparttable}[2003/06/13]
```

Env threeparttable [⟨*alignment*⟩] To emulate threeparttable:

```
\newenvironment*{threeparttable}[1][b]
```

```
3     {\def\@captype{table}}
4     {}
```

Env tablenotes [⟨*options*⟩]

```
5 \newenvironment*{tablenotes}[1][]
6 {%
7 \LWR@forcenewpage
8 \BlockClass{tnotes}%
9 \description%
10 }
11 {%
12 \enddescription%
13 \endBlockClass%
14 }
```

\tnote {⟨*text*⟩}

```
15 \newcommand{\tnote}[1]{\LWR@htmlspan{sup}{#1}}
```

File 344 **lwarp-threeparttablex.sty**

§ 441 Package

threeparttablex

Pkg threeparttablex threeparttablex is patched for use by lwarp.

threeparttablex is used with longtable and booktabs as follows:

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{          % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  \bottomrule \insertTableNotes \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{   % HTML last footer
  \bottomrule
  \UseMinipageWidths     % optional
  \insertTableNotes
  \endlastfoot
}
\end{longtable}
```

table width The table notes are created using a \multicolumn. By default the width is not specified to the browser, so long table notes can cause the table to be spread out horizontally. For HTML output, lwarp guesses the width of the table depending on the number of columns, then restricts its guess to a min/max range. To use this guess for the width of the table notes, use \UseMinipageWidths before \insertTableNotes. The width is then specified, and in many cases the result is an improvement in overall table layout.

for HTML output:

```
\LWR@ProvidesPackagePass{threeparttablex}[2013/07/23]
```

The width is guessed depending on the number of columns, then limited to a min/max.

```
\renewcommand\insertTableNotes{%
    \setlength{\LWR@templengthone}{.375in*\value{LWR@tabletotalLaTeXcols}}%
    \setlength{\LWR@templengthone}{\minof{\textwidth}{\LWR@templengthone}}%
    \setlength{\LWR@templengthone}{\maxof{2.5in}{\LWR@templengthone}}%
  \multicolumn{\value{LWR@tabletotalLaTeXcols}}{c}{%
      \parbox{\LWR@templengthone}{%
        \begin{tablenotes}[\TPTL@optarg]%
          \TPTL@font%
          \TPTL@body%
        \end{tablenotes}%
      }%
  }%
}

\renewcommand\TPTL@tnotex[2]{\tnote{\nameref{#2}}}
```

File 345 **lwarp-thumb.sty**

§ 442 Package thumb

Pkg thumb thumb is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{thumb}[1997/12/24]
```

```
\newcommand*{\Overviewpage}{}
\newlength{\thumbheight}
\newlength{\thumbwidth}
```

File 346 **lwarp-thumbs.sty**

§ 443 Package thumbs

Pkg thumbs thumbs is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{thumbs}[2014/03/09]
```

```
\newcommand{\addthumb}[4]{}
\newcommand{\addtitlethumb}[5]{}
\newcommand{\stopthumb}{}
\newcommand{\continuethumb}{}
\newcommand{\thumbsoverview}[1]{}
\newcommand{\thumbsoverviewback}[1]{}
\newcommand{\thumbsoverviewverso}[1]{}
\newcommand{\thumbsoverviewdouble}[1]{}
\newcommand{\thumbnewcolumn}{}
```

```
\newcommand{\addthumbsoverviewtocontents}[2]{}
\newcommand{\thumbsnophantom}{}
```

File 347 **lwarp-tikz.sty**

§ 444 Package

tikz

(*Emulates or patches code by* Till Tantau.)

Pkg tikz tikz is supported.

⚠ displaymath and matrices

If using display math with `tikzpicture` or `\tikz`, along with matrices with the `&` character, the document must be modified as follows:

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of `&` in the tikz expression must be replaced with `\&`.

Accept all options for lwarp-tikz:

```
\LWR@ProvidesPackagePass{tikz}[2015/08/07]
```

catcodes

lwarp changes the catcode of `$` for its own use. The Ti*k*z `babel` library temporarily changes catcodes back to normal for Ti*k*z's use. tikz v3.0.0 introduced the `babel` library which handles catcode changes. For older versions, lwarp must change `$`'s catcode itself.

Also see:
https://tex.stackexchange.com/questions/16199/test-if-a-package-or-package-option-is-loaded

```
\newbool{LWR@tikzbabel}

\@ifpackagelater{tikz}{2013/12/20}% Test for Tikz version v3.0.0
{\usetikzlibrary{babel}\booltrue{LWR@tikzbabel}}
{\boolfalse{LWR@tikzbabel}}
```

Env pgfpicture

The `\pgfpicture` environment is enclosed inside a `\lateximage`. Enclose the low-level `\pgfpicture` in a `lateximage`. This is also used by the higher-level `\tikz` and `tikzpicture`.

```
\preto\pgfpicture{%
    \begin{lateximage}%
    \ifbool{LWR@tikzbabel}% Test for Tikz version v3.0.0
    {}%
    {\catcode`\$=3}% dollar sign is math shift
}

\appto\endpgfpicture{\end{lateximage}}
```

Ti*k*z is placed inside an SVG image, so use the original meanings of the following:

```
\LetLtxMacro\pgfutil@minipage\LWR@print@minipage
\let\pgfutil@endminipage\endLWR@print@minipage

\let\pgfutil@raggedleft\LWR@print@raggedleft
\let\pgfutil@raggedright\LWR@print@raggedright

\def\pgfutil@font@tiny{\LWR@printtiny}
\def\pgfutil@font@scriptsize{\LWR@printscriptsize}
\def\pgfutil@font@footnotesize{\LWR@printfootnotesize}
\def\pgfutil@font@small{\LWR@print@small}
\def\pgfutil@font@normalsize{\LWR@print@normalsize}
\def\pgfutil@font@large{\LWR@printlarge}
\def\pgfutil@font@Large{\LWR@printLarge}
\def\pgfutil@font@huge{\LWR@printhuge}
\def\pgfutil@font@Huge{\LWR@printHuge}

\def\pgfutil@font@itshape{\LWR@origitshape}
\def\pgfutil@font@bfseries{\LWR@origbfseries}

\def\pgfutil@font@normalfont{\LWR@orignormalfont}
```

File 348 **lwarp-titleps.sty**

§ 445 Package

titleps

(*Emulates or patches code by* Javier Bezos.)

Pkg titleps

titleps is loaded and used by lwarp during HTML output. All user options and macros are ignored and disabled.

Discard all options for lwarp-titleps:

for HTML output:

```
\LWR@ProvidesPackageDrop{titleps}[2016/03/15]
```

\pagestyle and \thispagestyle are already disabled in the lwarp code.

\newpagestyle {⟨*name*⟩} [⟨*style*⟩] {⟨*commands*⟩}

```
\NewDocumentCommand{\newpagestyle}{m o m}{}
```

\renewpagestyle {⟨*name*⟩} [⟨*style*⟩] {⟨*commands*⟩}

```
\NewDocumentCommand{\renewpagestyle}{m o m}{}
```

\sethead [⟨*el*⟩] [⟨*ec*⟩] [⟨*er*⟩] {⟨*ol*⟩} {⟨*oc*⟩} {⟨*or*⟩}

```
\NewDocumentCommand{\sethead}{o o o m m m}{}
```

\setfoot [⟨*el*⟩] [⟨*ec*⟩] [⟨*er*⟩] {⟨*ol*⟩} {⟨*oc*⟩} {⟨*or*⟩}

```
\NewDocumentCommand{\setfoot}{o o o m m m}{}
```

\settitlemarks * {⟨*names*⟩}

```
\NewDocumentCommand{\settitlemarks}{s m}{}
```

\headrule

```
\newcommand*{\headrule}{}
```

\footrule

```
\newcommand*{\footrule}{}
```

\setheadrule {⟨*length*⟩}

```
\newcommand*{\setheadrule}[1]{}
```

\setfootrule {⟨*length*⟩}

```
\newcommand*{\setfootrule}[1]{}
```

\makeheadrule

```
\newcommand*{\makeheadrule}{}
```

\makefootrule

```
\newcommand*{\makefootrule}{}
```

\setmarkboth {⟨*code*⟩}

```
\newcommand{\setmarkboth}[1]{}
```

\widenhead

```
\NewDocumentCommand{\widenhead}{s o o m m}{}
```

\bottitlemarks

```
\newcommand*{\bottitlemarks}{}
```

\toptitlemarks

```
\newcommand*{\toptitlemarks}{}
```

\firsttitlemarks

```
\newcommand*{\firsttitlemarks}{}
```

\nexttitlemarks

```
18 \newcommand*{\nexttoptitlemarks}{}
```

\outertitlemarks

```
19 \newcommand*{\outertitlemarks}{}
```

\innertitlemarks

```
20 \newcommand*{\innertitlemarks}{}
```

\newtitlemark * {⟨*name*⟩}

```
21 \NewDocumentCommand{\newtitlemark}{s m}{}
```

\pretitlemark * {⟨*section*⟩} {⟨*text*⟩}

```
22 \NewDocumentCommand{\pretitlemark}{s m m}{}
```

\ifsamemark {⟨*group*⟩} {⟨*command*⟩} {⟨*true*⟩} {⟨*false*⟩}

```
23 \newcommand{\ifsamemark}[4]{}
```

\setfloathead * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
24 \NewDocumentCommand{\setfloathead}{s o o o m m m m m}{}
```

\setfloatfoot * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
25 \NewDocumentCommand{\setfloatfoot}{s o o o m m m m m}{}
```

\nextfloathead * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
26 \NewDocumentCommand{\nextfloathead}{s o o o m m m m m}{}
```

\nextfloatfoot * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
27 \NewDocumentCommand{\nextfloatfoot}{s o o o m m m m m}{}
```

\newmarkset {⟨*markset*⟩}

```
28 \newcommand{\newmarkset}[1]{}
```

\newextramark * {⟨*markset*⟩} {⟨*macro-name*⟩}

```
29 \NewDocumentCommand{\newextramarkset}{s m m}{}
```

\botextramarks {⟨*markset*⟩}

```
30 \newcommand{\botextramarks}[1]{}
```

\topextramarks {⟨*markset*⟩}

```
\newcommand{\topextramarks}[1]{}
```

\firstextramarks {⟨*markset*⟩}

```
\newcommand{\firstextramarks}[1]{}
```

\nextextramarks {⟨*markset*⟩}

```
\newcommand{\nexttopextramarks}[1]{}
```

\outerextramarks {⟨*markset*⟩}

```
\newcommand{\outerextramarks}[1]{}
```

\innerextramarks {⟨*markset*⟩}

```
\newcommand{\innerextramarks}[1]{}
```

File 349 **lwarp-titleref.sty**

§ 446 Package

titleref

Pkg titleref titleref is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{titleref}[2001/04/05]

\LetLtxMacro\titleref\nameref

\providecounter{LWR@currenttitle}

\newcommand*{\currenttitle}{%
    \addtocounter{LWR@currenttitle}{1}%
    \label{currenttitle\arabic{LWR@currenttitle}}%
    \nameref{currenttitle\arabic{LWR@currenttitle}}%
}

\newcommand*{\theTitleReference}[2]{}
```

File 350 **lwarp-titlesec.sty**

§ 447 Package

titlesec

(*Emulates or patches code by* Javier Bezos.)

Pkg titlesec titlesec is emulated. All user options and macros are ignored and disabled.

Discard all options for lwarp-titlesec:

for HTML output:

```
\LWR@ProvidesPackageDrop{titlesec}[2016/03/21]
```

\titlelabel {⟨*label-format*⟩}

```
\newcommand*{\titlelabel}[1]{}
```

\titleformat* {⟨*command*⟩} {⟨*format*⟩}

\titleformat {⟨*command*⟩} [⟨*shape*⟩] {⟨*format*⟩} {⟨*label*⟩} {⟨*sep*⟩} {⟨*begfore*⟩} [⟨*after*⟩]

```
\newcommand\titleformat{%
  \@ifstar{\ttl@format@s}%
          {\ttl@format@i}}
\newcommand{\ttl@format@s}[1]{}
\NewDocumentCommand{\ttl@format@i}{m o m m m m o}{}
```

\chaptertitlename

```
\@ifundefined{@chapapp}{\let\@chapapp\chaptername}{}
\newcommand\chaptertitlename{\@chapapp}
```

\titlespacing * {⟨*command*⟩} {⟨*left*⟩} {⟨*before*⟩} {⟨*after*⟩} [⟨*right*⟩]

```
\NewDocumentCommand{\titlespacing}{s m m m m o}{}
```

\filright

```
\newcommand*{\filright}{}
```

\filcenter

```
\newcommand*{\filcenter}{}
```

\filleft

```
\newcommand*{\filleft}{}
```

\fillast

```
\newcommand*{\fillast}{}
```

\filinner

```
\newcommand*{\filinner}{}
```

\filouter

```
\newcommand*{\filouter}{}
```

\wordsep

```
\newcommand\wordsep{\fontdimen\tw@\font \@plus
  \fontdimen\thr@@\font \@minus \fontdimen4\font}
```

\titleline * [⟨*align*⟩] {⟨*material*⟩}

```
\NewDocumentCommand{\titleline}{s o m}{}
```

\titlerule [⟨*height*⟩]

```
\providecommand*\titlerule{\@ifstar{\ttl@row}{\ttl@rule}}
\newcommand*{\ttl@rule}[1][]{}
\newcommand*{\ttl@row}[2][]{}
```

\iftitlemeasuring {⟨*true*⟩} {⟨*false*⟩}

```
\newcommand{\iftitlemeasuring}[2]{#2}
```

\assignpagestyle {⟨*command*⟩} {⟨*pagestyle*⟩}

```
\newcommand{\assignpagestyle}[2]{#2}
```

\titleclass {⟨*name*⟩} [⟨*startlevel*⟩] {⟨*class*⟩} [⟨*cmd*⟩]

```
\NewDocumentCommand{\titleclass}{m o m o}
```

File 351 **lwarp-titletoc.sty**

§ 448 Package

titletoc

(*Emulates or patches code by* Javier Bezos.)

Pkg titletoc titletoc is emulated. All user options and macros are ignored and disabled.

Discard all options for lwarp-titletoc:

for HTML output:

```
\LWR@ProvidesPackageDrop{titletoc}[2011/12/15]
```

\dottedcontents {⟨*section*⟩} [⟨*left*⟩] {⟨*above*⟩} {⟨*label*⟩} {⟨*leader*⟩}

```
\NewDocumentCommand{\dottedcontents}{m o m m m}{}
```

\titlecontents * {⟨*section*⟩} [⟨*left*⟩] {⟨*above*⟩} {⟨*numbered*⟩} {⟨*numberless*⟩} {⟨*filler*⟩} [⟨*below or begin*⟩] [⟨*separator*⟩] [⟨*end*⟩]

```
\newcommand{\titlecontents}{\@ifstar{\ttl@tcstar}{\ttl@tcnostar}}
\NewDocumentCommand{\ttl@tcstar}{m o m m m m o o o}{}
\NewDocumentCommand{\ttl@tcnostar}{m o m m m m o}{}
```

\contentsmargin [⟨*correction*⟩] {⟨*right*⟩}

```
\newcommand{\contentsmargin}[2][]{}
```

\thecontentslabel

```
7 \newcommand*{\thecontentslabel}{thecontentslabel}
```

\thecontentspage

```
8 \newcommand*{\thecontentspage}{thecontentspage}
```

\contentslabel [⟨*format*⟩] {⟨*space*⟩}

```
9 \newcommand{\contentslabel}[2][]{\thecontentslabel}
```

\contentspage [⟨*format*⟩]

```
10 \newcommand{\contentspage}[1][]{\thecontentspage}
```

\contentspush {⟨*text*⟩}

```
11 \newcommand{\contentspush}[1]{}
```

\contentsuse {⟨*name*⟩} {⟨*text*⟩}

```
12 \newcommand{\contentsuse}[2]{}
```

\startcontents [⟨*name*⟩]

```
13 \newcommand*{\startcontents}[1][]{}
```

\stopcontents [⟨*name*⟩]

```
14 \newcommand*{\stopcontents}[1][]{}
```

\resumecontents [⟨*name*⟩]

```
15 \newcommand*{\resumecontents}[1][]{}
```

\printcontents [⟨*name*⟩] {⟨*prefix*⟩} {⟨*start*⟩} {⟨*code*⟩}

```
16 \newcommand{\printcontents}[4][]{}
```

\startlist [⟨*name*⟩] {⟨*list*⟩}

```
17 \newcommand{\startlist}[2][]{}
```

\stoplist [⟨*name*⟩] {⟨*list*⟩}

```
18 \newcommand{\stoplist}[2][]{}
```

\resumelist [⟨*name*⟩] {⟨*list*⟩}

```
19 \newcommand{\resumelist}[2][]{}
```

\printlist [⟨*name*⟩] {⟨*list*⟩} {⟨*prefix*⟩} {⟨*code*⟩}

```
\newcommand{\printlist}[4][]{}
```

File 352 **lwarp-titling.sty**

§ 449 Package

titling

(*Emulates or patches code by* Peter Wilson.)

Pkg titling

package support
⚠ load order

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

\published and \subtitle

If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 65.8.

The various titling footnote restyling commands have no effect.

Pass all options to lwarp-titling:

for HTML output:

```
\LWR@ProvidesPackagePass{titling}[2009/09/04]
```

\@bsmtitlempty

Patch \@bsmtitlempty:

```
\let\LWR@orig@bsmtitlempty\@bsmtitlempty
\renewcommand*{\@bsmtitlempty}{%
\LWR@orig@bsmtitlempty%
}
```

\keepthetitle

Patch \keepthetitle:

```
\let\LWR@origkeepthetitle\keepthetitle
\renewcommand*{\keepthetitle}{%
\LWR@orig@keepthetitle%
}
```

\killtitle

Patch \killtitle:

```
\let\LWR@origkilltitle\killtitle
\renewcommand*{\killtitle}{%
\LWR@orig@killtitle%
}
```

Env titlingpage

```
\renewenvironment*{titlingpage}
{%
```

Start an HTML titlepage div:

```
\LWR@printpendingfootnotes
\begin{titlepage}
```

Prepare for a custom version of `\maketitle` inside the `titlingpage`:

```
\LWR@maketitlesetup
\let\maketitle\LWR@titlingmaketitle
}
{
```

At the end of the environment, end the HTML titlepage div:

```
\end{titlepage}
}
```

Patch the pre/post title/author/date to add HTML tags, then initilize:

```

\pretitle{}
\posttitle{}

\preauthor{}
\postauthor{}

\predate{}
\postdate{}
```

`\LWR@maketitlesetup` Patches `\thanks` macros.

```
\renewcommand*{\LWR@maketitlesetup}{%
```

Redefine the footnote mark:

```
\def\@makefnmark{\textsuperscript{\@thefnmark}}
```

`\thefootnote` ⇒ `\nameuse`{arabic}{footnote}, or
`\thefootnote` ⇒ `\nameuse`{fnsymbol}{footnote}

Redefine the footnote text:

```
\long\def\@makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```
\makethanksmark~%
```

`\makethanksmark` ⇒ `\thanksfootmark` ⇒ `\tamark` ⇒
`\@thefnmark` ⇒ `\itshape` a (or similar)

Print the text:

```
##1%
}% \@makefntext
}
```

\thanksfootmark

```
\renewcommand{\thanksfootmark}{%
%   \hb@xt@\thanksmarkwidth{\hfil\normalfont%
        \thanksscript{%
            \thanksfootpre \tamark \thanksfootpost%
        }%
%   }%
}
```

\maketitle HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the titling package is adapted, simplified, and modified for HTML output.

```
\renewcommand*{\maketitle}{%
```

An HTML titlepage is used for all classes.

```
\begin{titlepage}
```

Select which kind of footnote marks to use:

```
\@bsmarkseries
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any \thanks footnotes:

```
\@thanks
```

Close the HTML titlepage div:

```
\end{titlepage}
```

Reset the footnote counter:

```
\@bscontmark
}
```

\@maketitle Typesets the title, etc. Patched for HTML.

```
\DeclareDocumentCommand{\@maketitle}{}{%
    \maketitlehooka
    {
        \LWR@stoppars\LWR@htmltag{\LWR@tagtitle}%
```

```
        \@bspretitle \@title \@bsposttitle%
        \LWR@htmltag{\LWR@tagtitleend}\LWR@startpars%
    }
    \maketitlehookb
    {
        \begin{BlockClass}{author}
        \renewcommand{\and}{%
            \end{BlockClass}%
            \begin{BlockClass}{oneauthor}%
        }
        \begin{BlockClass}{oneauthor}%
        \@bspreauthor \@author  \@bspostauthor%
        \end{BlockClass}%
        \end{BlockClass}%
    }
    \maketitlehookc
    {
        \begin{BlockClass}{titledate}%
        \@bspredate \@date \@bspostdate%
        \end{BlockClass}%
    }
    \maketitlehookd
}
```

\LWR@titlingmaketitle `\maketitle` for use inside an HTML `titlingpage` environment.

```
\renewcommand*{\LWR@titlingmaketitle}{%
```

Keep pending footnotes out of the title block:

```
\@thanks
```

Select which kind of footnote marks to use:

```
\@bsmarkseries
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any `\thanks` footnotes:

```
\@thanks
```

Reset the footnote counter:

```
\@bscontmark
}
```

\thanksmarkseries {⟨*series*⟩}

Sets the type of footnote marks used by \thanks, where type is 'arabic', 'roman', 'fnsymbol', etc.

```
\renewcommand{\thanksmarkseries}[1]{%
\def\@bsmarkseries{\renewcommand{\thefootnote}{\@nameuse{#1}{footnote}}}%
}
```

Set default titlepage thanks footnote marks. See section 65.7.

```
\@ifclassloaded{memoir}{
   \thanksmarkseries{arabic}
}{% not memoir
\if@titlepage
   \thanksmarkseries{arabic}
\else
   \thanksmarkseries{fnsymbol}
\fi
}% not memoir
```

File 353 **lwarp-tocbasic.sty**

§ 450 Package

tocbasic

(*Emulates or patches code by* Markus Kohm.)

Pkg tocbasic tocbasic is nullified for lwarp.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. \DeclareDocumentCommand is used to overwrite the koma-script definitions.

for HTML output:

```
\LWR@ProvidesPackagePass{tocbasic}[2018/12/30]
```

```
\DeclareDocumentCommand{\usetocbasicnumberline}{o}{}
\DeclareDocumentCommand{\DeclareTOCStyleEntry}{o m m}{}
\DeclareDocumentCommand{\DeclareTOCStyleEntries}{o m m}{}
\DeclareDocumentCommand{\DeclareTOCEntryStyle}{m o m}{}
\DeclareDocumentCommand{\DefineTOCEntryOption}{m o m}{}
\DeclareDocumentCommand{\DefineTOCEntryBooleanOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryCommandOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryIfOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryLengthOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryNumberOption}{m o m m m}{}
\DeclareDocumentCommand{\CloneTOCEntryStyle}{m m}{}
\DeclareDocumentCommand{\TOCEntryStyleInitCode}{m m}{}
\DeclareDocumentCommand{\TOCEntryStyleStartInitCode}{m m}{}
```

File 354 **lwarp-tocbibind.sty**

§ 451 Package

tocbibind

(*Emulates or patches code by* Peter Wilson.)

Pkg tocbibind tocbibind is patched for use by lwarp.

placement and TOC options An index may be placed inline with other HTML text, or on its own HTML page:

Pkg makeidx **Inline, with a manual TOC entry:**

A commonly-used method to introduce an index in a LaTeX document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\printindex
```

Pkg makeidx **On its own HTML page, with a manual TOC entry:**

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex
```

Pkg tocbibind **Inline, with an automatic TOC entry:**

The tocbibind package may be used to automatically place an entry in the TOC.

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex
```

Pkg tocbibind **On its own HTML page, with an automatic TOC entry:**

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex
```

Opt [tocbibind] numindex numbered index section Use the tocbibind numindex option to generate a numbered index. Without this option, the index heading has no number.

Other packages, such as imakeidx, may also have options for including the index in the Table of Contents.

for HTML output:

```
\let\simplechapterdelim\relax

\LWR@ProvidesPackagePass{tocbibind}[2010/10/13]

\renewenvironment{theindex}%
{%
     \if@bibchapter
        \if@donumindex
            \chapter{\indexname}
        \else
          \if@dotocind
            \chapter*{\indexname}
            \addcontentsline{toc}{chapter}{\LWR@isolate{\indexname}}
          \else
            \chapter*{\indexname}
          \fi
        \fi
     \else
        \if@donumindex
            \section{\indexname}
        \else
          \if@dotocind
            \section*{\indexname}
            \addcontentsline{toc}{\@tocextra}{\LWR@isolate{\indexname}}
          \else
            \section*{\indexname}
          \fi
        \fi
     \fi
\let\item\LWR@indexitem%
\let\subitem\LWR@indexsubitem%
\let\subsubitem\LWR@indexsubsubitem%
}{}
```

The following code is shared by anonchap.

```
\DeclareDocumentCommand{\simplechapter}{O{\@empty}}{%
    \def\@chapcntformat##1{%
        #1~\csname the##1\endcsname\simplechapterdelim\quad%
    }%
}

\DeclareDocumentCommand{\restorechapter}{}{%
\let\@chapcntformat\@seccntformat%
}
```

File 355 **lwarp-tocenter.sty**

§ 452 Package

tocenter

Pkg tocenter

tocenter is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{tocenter}[2004/12/09]

\NewDocumentCommand{\ToCenter}{s o m m}{}
\NewDocumentCommand{\FromMargins}{s o m m m m}{}
```

File 356 **lwarp-tocloft.sty**

§ 453 Package

tocloft

(*Emulates or patches code by* Peter Wilson.)

Pkg tocloft

tocloft is emulated. Most user options and macros are ignored and disabled. `\newlistof` and `\cftchapterprecis` are supported.

Pkg tocloft

⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

Discard all options for lwarp-tocloft:

for HTML output:

```
\LWR@ProvidesPackageDrop{tocloft}[2017/08/31]
```

`\tocloftpagestyle` {⟨*style*⟩}

```
\newcommand{\tocloftpagestyle}[1]{}
```

`\cftmarktoc`

```
\newcommand*{\cftmarktoc}{}
```

`\cfttoctitlefont`

```
\newcommand*{\cfttoctitlefont}{}
```

`\cftaftertoctitle`

```
\newcommand*{\cftaftertoctitle}{}

\newlength{\cftbeforetoctitleskip}
\newlength{\cftaftertoctitleskip}
```

`\cftmarklof`

```
\newcommand*{\cftmarklof}{}
```

`\cftloftitlefont`

```
\newcommand*{\cftloftitlefont}{}
```

\cftafterloftitle

```
\newcommand*{\cftafterloftitle}{}

\newlength{\cftbeforeloftitleskip}
\newlength{\cftafterloftitleskip}
```

\cftmarklot

```
\newcommand*{\cftmarklot}{}
```

\cftlottitlefont

```
\newcommand*{\cftlottitlefont}{}
```

\cftafterlottitle

```
\newcommand*{\cftafterlottitle}{}

\newlength{\cftbeforelottitleskip}
\newlength{\cftafterlottitleskip}
```

\cftdot

```
\providecommand*{\cftdot}{.}
```

\cftdotsep

```
\providecommand*{\cftdotsep}{1}
```

\cftnodots

```
\providecommand*{\cftnodots}{5000}
```

\cftdotfill {⟨*sep*⟩}

```
\providecommand{\cftdotfill}[1]{}
```

\cftsetpnumwidth {⟨*length*⟩}

```
\DeclareDocumentCommand{\cftsetpnumwidth}{m}{}
```

\cftsetrmarg {⟨*length*⟩}

```
\DeclareDocumentCommand{\cftsetrmarg}{m}{}
```

\cftpnumalign {⟨*alignment*⟩}

```
\DeclareDocumentCommand{\cftpnumalign}{m}{}

\LWR@providelength{\cftparskip}
```

The part-related items are also provided by memoir:

```
\LWR@providelength{\cftbeforepartskip}
\LWR@providelength{\cftpartindent}
\LWR@providelength{\cftpartnumwidth}
\providecommand*{\cftpartfont}{}
\providecommand*{\cftpartpresnum}{}
\providecommand*{\cftpartaftersnum}{}
\providecommand*{\cftpartaftersnumb}{}
\providecommand*{\cftpartleader}{}
\providecommand*{\cftpartdotsep}{1}
\providecommand*{\cftpartpagefont}{}
\providecommand*{\cftpartafterpnum}{}
```

memoir uses the full name “chapter” instead of “chap”:

```
\LWR@providelength{\cftbeforechapskip}
\LWR@providelength{\cftchapindent}
\LWR@providelength{\cftchapnumwidth}
\newcommand*{\cftchapfont}{}
\newcommand*{\cftchappresnum}{}
\newcommand*{\cftchapaftersnum}{}
\newcommand*{\cftchapaftersnumb}{}
\newcommand*{\cftchapleader}{}
\newcommand*{\cftchapdotsep}{1}
\newcommand*{\cftchappagefont}{}
\newcommand*{\cftchapafterpnum}{}
```

The following do not appear in memoir:

```
\LWR@providelength{\cftbeforesecskip}
\LWR@providelength{\cftsecindent}
\LWR@providelength{\cftsecnumwidth}
\newcommand*{\cftsecfont}{}
\newcommand*{\cftsecpresnum}{}
\newcommand*{\cftsecaftersnum}{}
\newcommand*{\cftsecaftersnumb}{}
\newcommand*{\cftsecleader}{}
\newcommand*{\cftsecdotsep}{1}
\newcommand*{\cftsecpagefont}{}
\newcommand*{\cftsecafterpnum}{}

\LWR@providelength{\cftbeforesubsecskip}
\LWR@providelength{\cftsubsecindent}
\LWR@providelength{\cftsubsecnumwidth}
\newcommand*{\cftsubsecfont}{}
\newcommand*{\cftsubsecpresnum}{}
\newcommand*{\cftsubsecaftersnum}{}
\newcommand*{\cftsubsecaftersnumb}{}
\newcommand*{\cftsubsecleader}{}
\newcommand*{\cftsubsecdotsep}{1}
\newcommand*{\cftsubsecpagefont}{}
\newcommand*{\cftsubsecafterpnum}{}

\LWR@providelength{\cftbeforesubsubsecskip}
```

```
\LWR@providelength{\cftsubsubsecindent}
\LWR@providelength{\cftsubsubsecnumwidth}
\newcommand*{\cftsubsubsecfont}{}
\newcommand*{\cftsubsubsecpresnum}{}
\newcommand*{\cftsubsubsecaftersnum}{}
\newcommand*{\cftsubsubsecaftersnumb}{}
\newcommand*{\cftsubsubsecleader}{}
\newcommand*{\cftsubsubsecdotsep}{1}
\newcommand*{\cftsubsubsecpagefont}{}
\newcommand*{\cftsubsubsecafterpnum}{}

\LWR@providelength{\cftbeforeparaskip}
\LWR@providelength{\cftparaindent}
\LWR@providelength{\cftparanumwidth}
\newcommand*{\cftparafont}{}
\newcommand*{\cftparapresnum}{}
\newcommand*{\cftparaaftersnum}{}
\newcommand*{\cftparaaftersnumb}{}
\newcommand*{\cftparaleader}{}
\newcommand*{\cftparadotsep}{1}
\newcommand*{\cftparapagefont}{}
\newcommand*{\cftparaafterpnum}{}

\LWR@providelength{\cftbeforesubparaskip}
\LWR@providelength{\cftsubparaindent}
\LWR@providelength{\cftsubparanumwidth}
\newcommand*{\cftsubparafont}{}
\newcommand*{\cftsubparapresnum}{}
\newcommand*{\cftsubparaaftersnum}{}
\newcommand*{\cftsubparaaftersnumb}{}
\newcommand*{\cftsubparaleader}{}
\newcommand*{\cftsubparadotsep}{1}
\newcommand*{\cftsubparapagefont}{}
\newcommand*{\cftsubparaafterpnum}{}

\LWR@providelength{\cftbeforefigskip}
\LWR@providelength{\cftfigindent}
\LWR@providelength{\cftfignumwidth}
\newcommand*{\cftfigfont}{}
\newcommand*{\cftfigpresnum}{}
\newcommand*{\cftfigaftersnum}{}
\newcommand*{\cftfigaftersnumb}{}
\newcommand*{\cftfigleader}{}
\newcommand*{\cftfigdotsep}{1}
\newcommand*{\cftfigpagefont}{}
\newcommand*{\cftfigafterpnum}{}

\LWR@providelength{\cftbeforesubfigskip}
\LWR@providelength{\cftsubfigindent}
\LWR@providelength{\cftsubfignumwidth}
\newcommand*{\cftsubfigfont}{}
\newcommand*{\cftsubfigpresnum}{}
\newcommand*{\cftsubfigaftersnum}{}
\newcommand*{\cftsubfigaftersnumb}{}
\newcommand*{\cftsubfigleader}{}
```

```
\newcommand*{\cftsubfigdotsep}{1}
\newcommand*{\cftsubfigpagefont}{}
\newcommand*{\cftsubfigafterpnum}{}

\LWR@providelength{\cftbeforetabskip}
\LWR@providelength{\cfttabindent}
\LWR@providelength{\cfttabnumwidth}
\newcommand*{\cfttabfont}{}
\newcommand*{\cfttabpresnum}{}
\newcommand*{\cfttabaftersnum}{}
\newcommand*{\cfttabaftersnumb}{}
\newcommand*{\cfttableader}{}
\newcommand*{\cfttabdotsep}{1}
\newcommand*{\cfttabpagefont}{}
\newcommand*{\cfttabafterpnum}{}

\LWR@providelength{\cftbeforesubtabskip}
\LWR@providelength{\cftsubtabindent}
\LWR@providelength{\cftsubtabnumwidth}
\newcommand*{\cftsubtabfont}{}
\newcommand*{\cftsubtabpresnum}{}
\newcommand*{\cftsubtabaftersnum}{}
\newcommand*{\cftsubtabaftersnumb}{}
\newcommand*{\cftsubtableader}{}
\newcommand*{\cftsubtabdotsep}{1}
\newcommand*{\cftsubtabpagefont}{}
\newcommand*{\cftsubtabafterpnum}{}

\DeclareDocumentCommand{\cftsetindents}{m m m}{}

\newcommand{\pagenumbersoff}[1]{}
\newcommand{\pagenumberson}[1]{}
```

\newlistentry [⟨*within*⟩] {⟨*counter*⟩} {⟨*ext*⟩} {⟨*level-1*⟩}

```
\DeclareDocumentCommand{\newlistentry}{o m m m}
{%
\LWR@traceinfo{newlistentry #2 #3 #4}%
\IfValueTF{#1}%
{%
    \@ifundefined{c@#2}{%
        \newcounter{#2}[#1]%
        \expandafter\edef\csname the#2\endcsname{%
            \expandafter\noexpand\csname the#1\endcsname.\noexpand\arabic{#2}%
        }%
    }{}%
}%
{%
    \@ifundefined{c@#2}{%
        \newcounter{#2}%
    }{}%
}%
\@namedef{l@#2}##1##2{%
    \hypertocfloat{1}{#2}{#3}{##1}{##2}%
```

```
    \def\cftwhatismyname{#2}% from memoir
}%
\expandafter\newlength\csname cftbefore#2skip\endcsname%
\expandafter\newlength\csname cft#2indent\endcsname%
\expandafter\newlength\csname cft#2numwidth\endcsname%
\@namedef{cft#2font}{}%
\@namedef{cft#2presnum}{}%
\@namedef{cft#2aftersnum}{}%
\@namedef{cft#2aftersnumb}{}%
\@namedef{cft#2leader}{}%
\@namedef{cft#2dotsep}{1}%
\@namedef{cft#2pagefont}{}%
\@namedef{cft#2afterpnum}{}%
\@namedef{toclevel@#2}{#4}%
\@namedef{cft#2fillnum}##1{}%
\LWR@traceinfo{newlistentry done}%
}
```

\newlistof [⟨*within*⟩] {⟨*type*⟩} {⟨*ext*⟩} {⟨*listofname*⟩}

Emulated through the \newfloat mechanism.

```
\DeclareDocumentCommand{\newlistof}{o m m m}
{%
\IfValueTF{#1}
{\newlistentry[#1]{#2}{#3}{0}}
{\newlistentry{#2}{#3}{0}}
\@namedef{ext@#2}{#3}
\@ifundefined{c@#3depth}{\newcounter{#3depth}}{}
\setcounter{#3depth}{1}
\@namedef{cftmark#3}{}
\@namedef{listof#2}{\listof{#2}{#4}}
\@namedef{@cftmake#3title}{}
\expandafter\newlength\csname cftbefore#3titleskip\endcsname
\expandafter\newlength\csname cftafter#3titleskip\endcsname
\@namedef{cft#3titlefont}{}
\@namedef{cftafter#3title}{}
\@namedef{cft#3prehook}{}
\@namedef{cft#3posthook}{}
}
```

\cftchapterprecis {⟨*text*⟩}

```
\newcommand{\cftchapterprecis}[1]{%
  \cftchapterprecishere{#1}
  \cftchapterprecistoc{#1}}
\newcommand{\cftchapterprecishere}[1]{%
  \begin{quote}\textit{#1}\end{quote}}
\newcommand{\cftchapterprecistoc}[1]{
  \addtocontents{toc}{%
  {
     \protect\begin{quote}#1\protect\end{quote}}
  }
}
```

File 357 **lwarp-tocstyle.sty**

§ 454 Package tocstyle

Pkg tocstyle tocstyle is ignored.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{tocstyle}[2017/02/23]

\newcommand*{\usetocstyle}[2][]{}
\newcommand*{\deactivatetocstyle}[1][]{}
\newcommand*{\reactivatetocstyle}[1][]{}
\NewDocumentCommand{\settocfeature}{o o m m}{}
\NewDocumentCommand{\settocstylefeature}{o m m}{}
\NewDocumentCommand{\newtocstyle}{o o m m}{}
\newcommand*{\aliastoc}[2]{}
\newcommand*{\showtoc}[2][]{}
\newcommand{\iftochasdepth}[4]{}
```

File 358 **lwarp-todo.sty**

§ 455 Package todo

(*Emulates or patches code by* Federico Garcia.)

Pkg todo todo is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{todo}[2010/03/31]

\renewcommand\todoitem[2]{%
    \refstepcounter{todo}%
    \item[%
        \HTMLunicode{2610} \quad
        \ref{todopage:\thetodo}
     ] : {\todoformat\ifx#1\todomark\else\textbf{#1} \fi}#2%
    \label{todolbl:\thetodo}%
}%

\renewcommand\doneitem[2]{%
    \stepcounter{todo}%
    \item[%
        \HTMLunicode{2611} \quad
        \ref{todopage:\thetodo}
    ] \@nameuse{@done\the\c@todo}:
        {\todoformat\ifx#1\todomark\else\textbf{#1} \fi}#2%
}

```

```
\xpatchcmd{\@displaytodo}
    {\todoformat #1}{\todoformat \textbf{#1}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch @displaytodo.}}

\xpatchcmd{\@displayfulltodo}
    {\todoformat #1}{\todoformat \textbf{#1}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch @displayfulltodo.}}

\patchcmd{\todoenv}{\itshape see text.}{\textit{see text.}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch todoenv.}}

\patchcmd{\astodos}{\todoformat #1}{\todoformat \textbf{#1}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch astodos.}}

\AtBeginDocument{
    \crefname{todo}{todo}{todos}
    \Crefname{todo}{Todo}{Todos}
}
```

File 359 **lwarp-todonotes.sty**

§ 456 Package

todonotes

(*Emulates or patches code by* Henrik Skov Midtiby.)

Pkg todonotes todonotes is emulated.

The documentation for todonotes and luatodonotes have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

for HTML output:

```
\LWR@ProvidesPackagePass{todonotes}[2012/07/25]

\if@todonotes@disabled
\else

\newcommand{\ext@todo}{tdo}

\renewcommand{\l@todo}[2]{\hypertocfloat{1}{todo}{ldo}{#1}{#2}}

\let\LWRTODONOTES@orig@todototoc\todototoc

\renewcommand*{\todototoc}{%
\phantomsection%
\LWRTODONOTES@orig@todototoc%
}

\renewcommand{\@todonotes@drawMarginNoteWithLine}{
\fcolorbox
    {\@todonotes@currentbordercolor}
    {\@todonotes@currentbackgroundcolor}
    {\arabic{@todonotes@numberoftodonotes}}
```

```
\marginpar{\@todonotes@drawMarginNote}
}

\renewcommand{\@todonotes@drawInlineNote}{%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \if@todonotes@authorgiven%
        {\@todonotes@author:\,}%
        \fi%
        \@todonotes@text%
    }%
}

\renewcommand{\@todonotes@drawMarginNote}{%
    \if@todonotes@authorgiven%
        \@todonotes@author\par%
    \fi%
    \arabic{@todonotes@numberoftodonotes}: %
    \fcolorbox%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \@todonotes@sizecommand%
        \@todonotes@text %
    }%
}%

\renewcommand{\@todonotes@drawLineToRightMargin}{}

\renewcommand{\@todonotes@drawLineToLeftMargin}{}

\renewcommand{\missingfigure}[2][]{%
\setkeys{todonotes}{#1}%
\addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentfigcolor}%
    {%
        \setlength{\fboxrule}{4pt}%
        \fcolorbox{red}{white}{Missing figure} \quad #2%
    }
}

\LetLtxMacro\LWRTODONOTES@orig@todo\@todo

\RenewDocumentCommand{\@todo}{o m}{%
\begingroup%
\renewcommand*{\phantomsection}{}%
\IfValueTF{#1}{%
    \LWRTODONOTES@orig@todo[#1]{#2}%
}{%
    \LWRTODONOTES@orig@todo{#2}%
}
```

```
\endgroup%
}

\fi% \if@todonotes@disabled
```

File 360 **lwarp-tram.sty**

§ 457 Package

tram

Pkg tram tram is emulated.

⚠ block only The HTML emulation uses a , which must not appear inside an HTML or an HTML paragraph. For this reason, the tram environment should only be used to contain paragraphs inside a \parbox or minipage. tram should not be used to mark up inline text.

To disable tram, allowing source compatibility with inline uses:

```
\begin{warpHTML}
\renewenvironment{tram}[1][]{}{}
\end{warpHTML}
```

for HTML output:

```
\LWR@ProvidesPackageDrop{tram}[2013/04/04]

\newenvironment{tram}[1][]%
    {\BlockClass[background:lightgray]{tram}}
    {\endBlockClass}
```

File 361 **lwarp-transparent.sty**

§ 458 Package

transparent

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg transparent Emulated. \texttransparent works for inline objects. \transparent only works for \includegraphics.

⚠ Not XeLaTeX! Note that transparent does not work with XeLaTeX.

for HTML output: Discard all options for lwarp-transparent:

```
\LWR@ProvidesPackageDrop{transparent}[2016/05/16]

\newcommand*{\transparent}[1]{\edef\LWR@opacity{#1}}

\newcommand*{\texttransparent}[2]{%
\begingroup%
\transparent{#1}%
\InlineClass[opacity: #1]{transparent}{#2}%
```

```
\endgroup%
}
```

File 362 **lwarp-trimclip.sty**

§ 459 Package trimclip

Pkg trimclip trimclip is nullified.

for HTML output:

```
\LWR@ProvidesPackageDrop{trimclip}[2018/04/08]
```

The third argument, the text, is not touched. This allows \bgroup / \egroup, and verbatim content.

```
\csdef{trimbox}{\@ifstar\@gobble\@gobble}
\csletcs{trimbox*}{trimbox}
\def\endtrimbox{}
\csletcs{endtrimbox*}{endtrimbox}

\csletcs{clipbox}{trimbox}
\csletcs{clipbox*}{trimbox}
\csletcs{endclipbox}{endtrimbox}
\csletcs{endclipbox*}{endtrimbox}

\csletcs{marginbox}{trimbox}
\csletcs{marginbox*}{trimbox}
\csletcs{endmarginbox}{endtrimbox}
\csletcs{endmarginbox*}{endtrimbox}
```

File 363 **lwarp-trivfloat.sty**

§ 460 Package trivfloat

(*Emulates or patches code by* Joseph Wright.)

Pkg trivfloat trivfloat is forced to use the built-in lwarp emulation for floats.

To create a new float type and change its name:

```
\trivfloat{example}
\renewcommand{\examplename}{Example Name}
\crefname{example}{example}{examples}
\Crefname{example}{Example}{Examples}
```

Discard all options for lwarp-trivfloat. This tells trivfloat not to use floatrow or memoir.

```
\LWR@ProvidesPackageDrop{trivfloat}[2009/04/23]
\LWR@origRequirePackage{trivfloat}
```

`\tfl@chapter@fix` Nullified at the beginning of the document. Is used by trivfloat to correct float chapter numbers, but is not needed for lwarp.

for HTML output:

```
\begin{warpHTML}
\AtBeginDocument{\DeclareDocumentCommand{\tfl@chapter@fix}{m m}{}}
\end{warpHTML}
```

§ 460.1 Combining `\newfloat`, `\trivfloat`, and algorithmicx

for HTML & PRINT:

```
\begin{warpall}
```

For both print and HTML output:

⚠ When using float, trivfloat, or algorithmicx at the same time, be aware of conflicting file usage. algorithmicx uses `.loa`. trivfloat by default starts with `.loa` and goes up for additional floats, skipping `.lof` and `.lot`.

⚠ When using `\newfloat`, be sure to manually assign higher letters to the `\newfloat` files to avoid `.loa` used by algorithmicx, and any files used by trivfloat. Also avoid using `.lof` and `.lot`.

⚠ When using `\trivfloat`, you may force it to avoid conflicting with algorithmicx by starting trivfloat's file extensions with `.lob`:

```
\makeatletter
\setcounter{tfl@float@cnt}{1} % start trivfloats with .lob
\makeatletter
```

```
\end{warpall}
```

File 364 **`lwarp-truncate.sty`**

§ 461 Package truncate

`Pkg truncate` truncate is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{truncate}[2001/08/20]
\providecommand{\TruncateMarker}{}
\newcommand{\truncate}[3][\TruncateMarker]{#3}
```

File 365 **lwarp-turnthepage.sty**

§ 462 Package turnthepage

Pkg turnthepage turnthepage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{turnthepage}[2011/03/24]
\newcommand{\turnthepage}{}
```

File 366 **lwarp-twoup.sty**

§ 463 Package twoup

Pkg twoup twoup is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{twoup}[2007/02/26]
\newcommand{\cleartolastpage}{}
```

File 367 **lwarp-typearea.sty**

§ 464 Package typearea

(*Emulates or patches code by* Markus Kohm.)

Pkg typearea typearea is emulated.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. \DeclareDocumentCommand is used to overwrite the koma-script definitions.

for HTML output:

```
\LWR@ProvidesPackageDrop{typearea}[2018/03/30]
\DeclareDocumentCommand{\typearea}{o m}{}
\DeclareDocumentCommand{\recalctypearea}{}{}
\@ifundefined{footheight}{\newlength\footheight}{}
\DeclareDocumentCommand{\areaset}{o m m}{}
\DeclareDocumentCommand{\activateareas}{}{}
\DeclareDocumentCommand{\storeareas}{m}{}
\DeclareDocumentCommand{\BeforeRestoreareas}{s m}{}
\DeclareDocumentCommand{\AfterRestoreareas}{s m}{}
\DeclareDocumentCommand{\AfterCalculatingTypearea}{s m}{}
\DeclareDocumentCommand{\AfterSettingArea}{s m}{}
```

File 368 **lwarp-typicons.sty**

§ 465 Package

typicons

(*Emulates or patches code by* Arthur Vigil, Xavier Danaux.)

Pkg typicons typicons is patched for use by lwarp.

If \ticon is used, the name of the icon is used in the alt tag. Otherwise, for each of the individual icon macros, a generic alt tag is used.

for HTML output:

```
\LWR@ProvidesPackagePass{typicons}[2015/05/20]

\LetLtxMacro\LWR@orig@symbol\symbol

\let\LWR@orig@typicon@TI\TI

\newcommand*{\LWR@typicon@symbol}[1]{%
    \begin{lateximage}*[(typicon)][typicon#1]%
    \begingroup%
    \LWR@orig@typicon@TI%
    \LWR@orig@symbol{#1}%
    \endgroup%
    \end{lateximage}%
}

\renewcommand*{\TI}{%
    \LetLtxMacro\symbol\LWR@typicon@symbol%
}

\renewcommand*{\ticon}[1]
{%
    \begin{lateximage}*[(#1 icon)][typicon#1]%
    \TI\csname ticon@#1\endcsname%
    \end{lateximage}%
}
```

File 369 **lwarp-ulem.sty**

§ 466 Package

ulem

(*Emulates or patches code by* Donald Arseneau.)

Pkg ulem Patched for use by lwarp.

for HTML output: Use the original package:

```
\LWR@ProvidesPackagePass{ulem}[2012/05/18]
```

Basic markup commands, using css:

```
\NewDocumentCommand{\LWR@HTML@uline}{+m}{%
    \InlineClass%
        (text-decoration:underline; text-decoration-skip: auto)%
        {uline}{\LWR@isolate{#1}}%
}
\LWR@formatted{uline}

\NewDocumentCommand{\LWR@HTML@uuline}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline; text-decoration-skip: auto;%
            text-decoration-style:double%
        )%
        {uuline}{\LWR@isolate{#1}}%
}
\LWR@formatted{uuline}

\NewDocumentCommand{\LWR@HTML@uwave}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline; text-decoration-skip: auto;%
            text-decoration-style:wavy%
        )%
        {uwave}{\LWR@isolate{#1}}%
}
\LWR@formatted{uwave}

\NewDocumentCommand{\LWR@HTML@sout}{+m}{%
    \InlineClass%
        (text-decoration:line-through)%
        {sout}{\LWR@isolate{#1}}%
}
\LWR@formatted{sout}

\NewDocumentCommand{\LWR@HTML@xout}{+m}{%
    \InlineClass%
        (text-decoration:line-through)%
        {xout}{\LWR@isolate{#1}}%
}

\NewDocumentCommand{\LWR@HTML@dashuline}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline;%
            text-decoration-skip: auto;%
            text-decoration-style:dashed%
        )%
        {dashuline}{\LWR@isolate{#1}}%
}
\LWR@formatted{xout}

\NewDocumentCommand{\LWR@HTML@dotuline}{+m}{%
    \InlineClass%
```

```
        (%
            text-decoration:underline;%
            text-decoration-skip: auto;%
            text-decoration-style: dotted%
        )%
        {dotuline}{\LWR@isolate{#1}}%
}
\LWR@formatted{dotuline}
```

Nullified/emulated macros:

```
\NewDocumentCommand{\LWR@HTML@markoverwith}{m}{}
\LWR@formatted{markoverwith}

\NewDocumentCommand{\LWR@HTML@ULon}{+m}{\uline{#1}\egroup}
\LWR@formatted{ULon}
```

File 370 **lwarp-umoline.sty**

§ 467 Package

umoline

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg umoline umoline is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{umoline}[2000/07/11]

\newcommand*{\LWR@HTML@Underline}[1]{%
    \InlineClass{uline}{#1}%
}
\LWR@formatted{Underline}

\newcommand*{\LWR@HTML@Midline}[1]{%
    \InlineClass{sout}{#1}%
}
\LWR@formatted{Midline}

\newcommand*{\LWR@HTML@Overline}[1]{%
    \InlineClass{oline}{#1}%
}
\LWR@formatted{Overline}

\newcommand*{\LWR@HTML@UMOline}[2]{%
    \InlineClass{uline}{#2}%
}
\LWR@formatted{UMOline}

\NewDocumentCommand{\LWR@HTML@UMOspace}{s m o}{\hspace*{#2}}
\LWR@formatted{UMOspace}

\NewDocumentCommand{\LWR@HTML@UMOnewline}{s}{\newline}
\LWR@formatted{UMOnewline}
```

File 371 **lwarp-underscore.sty**

§ 468 Package underscore

Pkg underscore underscore is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{underscore}[2006/09/13]
```

File 372 **lwarp-units.sty**

§ 469 Package units

(*Emulates or patches code by* Axel Reichert.)

Pkg units units is patched for use by lwarp.

Values are not styled by css, and take the style of the surrounding HTML text.

Units are styled according to the print version, so they will be forced to upright roman in HTML if the print version does so. It may be necessary to adjust the document's body css to match the print version.

for HTML output:

```
\LWR@ProvidesPackagePass{units}[1998/08/04]

\DeclareRobustCommand*{\LWR@HTML@unit}[2][]{%
\ifblank{#1}%
    {\LWR@textcurrentfont{#2}}%
    {%
        #1%
        \ifthenelse{\boolean{B@UnitsLoose}}{~}{\,}%
        \LWR@textcurrentfont{#2}%
    }%
}
\LWR@formatted{unit}

\DeclareRobustCommand*{\LWR@HTML@unitfrac}[3][]{%
\ifblank{#1}%
    {%
            \nicefrac{#2}{#3}%
    }%
    {%
            #1%
            \ifthenelse{\boolean{B@UnitsLoose}}{~}{\,}%
            \nicefrac{#2}{#3}%
    }%
}

\LWR@formatted{unitfrac}
```

For Mathjax:

```
\CustomizeMathJax{\newcommand{\unit}[2][]{#1 #2}}
\CustomizeMathJax{\newcommand{\unitfrac}[3][]{#1 #2/#3}}
```

File 373 **lwarp-unitsdef.sty**

§ 470 Package

unitsdef

(*Emulates or patches code by* Patrick Happel.)

Pkg unitsdef unitsdef is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{unitsdef}[2005/01/04]

\renewcommand{\unitvaluesep}{\,}

\renewcommand{\unittimes}{\@@setunitsepfalse\HTMLunicode{22c5}}% \cdot

\renewunit{\arcmin}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {\ensuremath{{}^\prime}}%
        {\HTMLunicode{2032}}% prime
}

\renewunit{\arcsec}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {\ensuremath{{}^{\prime\prime}}}%
        {\HTMLunicode{2033}}% dbl prime
}

\renewrobustcmd{\SI}[2]{%
  \begingroup%
    \let\unit@@xspace\relax%
    \unitSIdef\selectfont%
      \LWR@textcurrentfont{#1#2}% lwarp
  \endgroup%
}
```

File 374 **lwarp-upref.sty**

§ 471 Package

upref

Pkg upref Ignored.

for HTML output: Discard all options for lwarp-upref:

```
\LWR@ProvidesPackageDrop{upref}[2007/03/14]
```

File 375 **lwarp-url.sty**

§ 472 Package url

(*Emulates or patches code by* Donald Arseneau.)

Pkg url url is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{url}[2013/09/16]
```

url uses math mode to print its string inside a group, so the original meaning of math is restored first.

```
\LetLtxMacro\LWR@url@origUrl@FormatString\Url@FormatString

\renewcommand*{\Url@FormatString}{%
    \InlineClass{verbatim}{%
        \LWR@restoreorigformatting%
        \LWR@url@origUrl@FormatString%
    }%
}
```

File 376 **lwarp-uspace.sty**

§ 473 Package uspace

Pkg uspace uspace is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{uspace}[2016/11/06]
```

File 377 **lwarp-verse.sty**

§ 474 Package verse

(*Emulates or patches code by* Peter Wilson.)

Pkg verse verse is supported and patched by lwarp.

for HTML output: Pass all options for lwarp-verse:

```
\LWR@ProvidesPackagePass{verse}[2009/09/04]
```

When using verse or memoir, always place a \\ after each line.

\attrib The documentation for the verse and memoir packages suggest defining an \attrib

command, which may already exist in current documents, but it will only work for print output. lwarp provides \attribution, which works for both print and HTML output. To combine the two so that \attrib is used for print and \attribution is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len \vleftskip
Len \vleftmargini
Len \HTMLvleftskip
Len \HTMLleftmargini

These lengths are used by verse and memoir to control the left margin, and they may already be set by the user for print output. New lengths \HTMLvleftskip and \HTMLleftmargini are provided to control the margins in HTML output. These new lengths may be set by the user before any verse environment, and persist until they are manually changed again. One reason to change \HTMLleftmargini is if there is a wide \flagverse in use, such as the word "Chorus", in which case the value of \HTMLleftmargini should be set to a wide enough length to contain "Chorus". The default is wide enough for a stanza number.

⚠ spacing

Horizontal spacing relies on *pdftotext*'s ability to discern the layout (-layout option) of the text in the HTML-tagged PDF output. For some settings of \HTMLleftmargini or \HTMLleftskip the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

Env verse

The verse environment will be placed inside a HTML <pre>.

```
\AfterEndPreamble{
\LWR@traceinfo{Patching verse.}
```

At the beginning of the verse environment:

```
\AtBeginEnvironment{verse}
{%
```

Use the original list environment inside a <pre> to attempt to preserve formatting.

```
\LWR@restoreoriglists%
```

Pkg verse
Cls memoir
\flagverse
Len \vleftskip

The verse or memoir packages can place stanza numbers to the left with their \flagverse command. Do not allow them to go into the left margin, which would cause *pdfcrop* to crop the entire page further to the left:

```
\ifdef{\vleftskip}{%
\setlength{\vleftskip}{\HTMLvleftskip}
\setlength{\leftmargini}{\HTMLleftmargini}
}{}
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{verse}%
}
```

After the end of the verse environment, which places the <pre> tag at the regular left margin:

```
\AtEndEnvironment{verse}{%
\leavevmode%
\LWR@afterendverbatim{1}%
}
```

Patch to place poemtitle inside an HTML of class poemtitle:

```
\ifdef{\poemtitle}{
\DeclareDocumentCommand{\@vstypeptitle}{m}{%
   \vspace{\beforepoemtitleskip}%
   {\InlineClass{poemtitle}{\poemtitlefont #1}\par}%
   \vspace{\afterpoemtitleskip}%
 }
}{}

\LWR@traceinfo{Finished patching verse.}
}% AfterEndPreamble
```

File 378 **lwarp-versonotes.sty**

§ 475 Package versonotes

(*Emulates or patches code by* Norman Gray.)

Pkg versonotes versonotes is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{versonotes}[2015/12/08]

\newcommand{\versonote}[1]{\marginpar{#1}}
\newdimen\versotextwidth
\newdimen\versoleftmargin
\newcommand*{\versolayout}{}
```

File 379 **lwarp-vertbars.sty**

§ 476 Package vertbars

(*Emulates or patches code by* Peter Wilson.)

Pkg vertbars vertbars is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{vertbars}[2010/11/27]

\newlength{\barwidth}
\setlength{\barwidth}{0.4pt}
\newlength{\barspace}
\setlength{\barspace}{1em}

\newenvironment{vertbar}{
```

```
    \LWR@forcenewpage
    \LWR@forceminwidth{\barwidth}
    \begin{BlockClass}[%
        border-left: \LWR@printlength{\LWR@atleastonept} solid black ; %
        padding-left: \LWR@printlength{\barspace}%
    ]{vertbar}
}{
    \end{BlockClass}
}
```

File 380 **lwarp-vmargin.sty**

§ 477 Package

vmargin

Pkg vmargin vmargin is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{vmargin}[2004/07/15]
```

```
\newcommand*{\LWRVM@customsize}[2]{}
\newcommand*{\setpapersize}[2][]{\ifstrequal{#2}{custom}{\LWRVM@customsize}{}}
\newcommand*{\setmargins}[8]{}
\newcommand*{\setmarginsrb}[8]{}
\newcommand*{\setmargnohf}[4]{}
\newcommand*{\setmargnohfrb}[4]{}
\newcommand*{\setmarg}[4]{}
\newcommand*{\setmargrb}[4]{}
\newlength{\PaperWidth}
\setlength{\PaperWidth}{8.5in}
\newlength{\PaperHeight}
\setlength{\PaperHeight}{11in}
\newif\ifLandscape
```

File 381 **lwarp-vowel.sty**

§ 478 Package

vowel

(*Emulates or patches code by* FUKUI REI.)

Pkg vowel vowel is patched for use by lwarp.

This package has been tested with *pdflatex* and the Type 1 TIPA fonts using the following package load sequence:

```
\usepackage[T3,T1]{fontenc}
\usepackage[utf8]{inputenc}
\usepackage[noenc]{tipa}
\usepackage{vowel}
```

for HTML output:

```
\LWR@ProvidesPackagePass{vowel}[2002/08/08]
```

```
\renewenvironment{vowel}[1][]
    {%
        \begin{lateximage}[(-vowel-~\packagediagramname)]%
        \@vowel[#1]%
    }
    {%
        \@@vowel%
        \end{lateximage}%
    }
```

File 382 **lwarp-vpe.sty**

§ 479 Package vpe

Pkg vpe vpe is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{vpe}[2012/04/18]
```

File 383 **lwarp-vwcol.sty**

§ 480 Package vwcol

(*Emulates or patches code by* Will Robertson.)

Pkg vwcol vwcol is patched for use with lwarp.

The `width` option is ignored. All `vwcol` environments adjust to 1–3 equal-width columns, depening on the width of the browser window.

The remaining options are supported, except for `lines` and `maxrecursion`.

for HTML output:

```
\LWR@ProvidesPackagePass{vwcol}[2015/02/10]
```

Factored from `\vwcol`. Each is given a style tag to append to the final style.

`\LWR@vwcol@addrule` {⟨*style tag*⟩}

```
\newcommand*{\LWR@vwcol@addrule}[1]{%
    \appto{\LWR@vwcolstyle}{%
        #1: %
     \LWR@printlength{\vwcol@rule} solid \LWR@origpound\LWR@vwcol@rulecolor ; %
    }%
}
```

`\LWR@vwcol@addrule` {⟨*style tag*⟩}

```
\newcommand*{\LWR@vwcol@addgap}[1]{%
    \appto{\LWR@vwcolstyle}{%
        #1: %
```

```
        \LWR@printlength{\vwcol@sep} ; %
    }%
}
```

Env vwcol {⟨*key/values*⟩}

Redefine the environment to add a HTML style. The style is built depending on the required options.

```
\renewenvironment*{vwcol}[1][]{%
```

New paragraph, and process the options:

```
\par\noindent%
\vwcolsetup{#1}%
```

Begin with no style:

```
\newcommand*{\LWR@vwcolstyle}{}
```

presep and postsep are created with HTML margins:

```
\if@vwcol@presep
    \appto{\LWR@vwcolstyle}{margin-left: 1em ; padding-left: .5em ; }
\fi
\if@vwcol@postsep
    \appto{\LWR@vwcolstyle}{margin-right: 1em ; padding-right: .5em ; }
\fi
```

sep becomes column-gap:

```
\ifdimgreater{\vwcol@sep}{1sp}{
    \LWR@vwcol@addgap{column-gap}
    \LWR@vwcol@addgap{-moz-column-gap}
    \LWR@vwcol@addgap{-webkit-column-gap}
}{}
```

rule become column-rule, while prerule and postrule become HTML borders:

```
\convertcolorspec{named}{\vwcol@rulecol}{HTML}\LWR@vwcol@rulecolor%
\ifdimgreater{\vwcol@rule}{0pt}{
    \ifdimless{\vwcol@rule}{1pt}{
        \setlength{\vwcol@rule}{1pt}
    }{}
    \LWR@vwcol@addrule{column-rule}
    \LWR@vwcol@addrule{-moz-column-rule}
    \LWR@vwcol@addrule{-webkit-column-rule}
    \if@vwcol@prerule\LWR@vwcol@addrule{border-left}\fi
    \if@vwcol@postrule\LWR@vwcol@addrule{border-right}\fi
}{}
```

Each of the justify options becomes a text-align. Indentation is added where appropriate.

```
\ifdefequal{\vwcol@justify}{\RaggedRight}{
    \appto{\LWR@vwcolstyle}{text-align: left ; }
    \ifdimgreater{\vwcol@parindent}{0pt}{
        \appto{\LWR@vwcolstyle}{%
            text-indent: \LWR@printlength{\vwcol@parindent} ; %
        }
    }{}
```

```
}{}
\ifdefequal{\vwcol@justify}{\RaggedLeft}{
    \appto{\LWR@vwcolstyle}{text-align: right ; }
}{}
\ifdefequal{\vwcol@justify}{\Centering}{
    \appto{\LWR@vwcolstyle}{text-align: center ; }
}{}
\ifdefequal{\vwcol@justify}{\justifying}{
    \appto{\LWR@vwcolstyle}{text-align: justify ; }
    \ifdimgreater{\vwcol@parindent}{0pt}{
        \appto{\LWR@vwcolstyle}{%
            text-indent: \LWR@printlength{\vwcol@parindent} ; %
        }
    }{}
}{}
```

Create the with the assembled style:

```
\BlockClass[\LWR@vwcolstyle]{multicols}
}
```

When the environment ends:

```
{
\endBlockClass
}
```

File 384 **lwarp-wallpaper.sty**

§ 481 Package

wallpaper

(*Emulates or patches code by* Michael H.F. Wilkinson.)

Pkg wallpaper wallpaper is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{wallpaper}[2005/01/18]

\newcommand*{\CenterWallPaper}[2]{}
\newcommand*{\ThisCenterWallPaper}[2]{}
\newcommand*{\TileWallPaper}[3]{}
\newcommand*{\ThisTileWallPaper}[3]{}
\newcommand*{\TileSquareWallPaper}[2]{}
\newcommand*{\ThisTileSquareWallPaper}[2]{}
\newcommand*{\ULCornerWallPaper}[2]{}
\newcommand*{\ThisULCornerWallPaper}[2]{}
\newcommand*{\LLCornerWallPaper}[2]{}
\newcommand*{\ThisLLCornerWallPaper}[2]{}
\newcommand*{\URCornerWallPaper}[2]{}
\newcommand*{\ThisURCornerWallPaper}[2]{}
\newcommand*{\LRCornerWallPaper}[2]{}
\newcommand*{\ThisLRCornerWallPaper}[2]{}
\newcommand*{\ClearWallPaper}{}
\newlength{\wpXoffset}
```

```
\newlength{\wpYoffset}
```

File 385 **lwarp-watermark.sty**

§ 482 Package watermark

(*Emulates or patches code by* Alexander I. Rozhenko.)

Pkg watermark watermark is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{watermark}[2004/12/09]

\newcommand{\watermark}[1]{}
\newcommand{\leftwatermark}[1]{}
\newcommand{\rightwatermark}[1]{}
\newcommand{\thiswatermark}[1]{}
\newcommand{\thispageheading}[1]{}
```

File 386 **lwarp-widows-and-orphans.sty**

§ 483 Package widows-and-orphans

Pkg widows-and-orphans widows-and-orphans is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{widows-and-orphans}[2018/09/01]

\NewDocumentCommand\WaOsetup{m}{}
\NewDocumentCommand\WaOparameters{}{}
\NewDocumentCommand\WaOignorenext{}{}
```

File 387 **lwarp-wrapfig.sty**

§ 484 Package wrapfig

(*Emulates or patches code by* Donald Arseneau.)

Pkg wrapfig wrapfig is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{wrapfig}[2003/01/31]

\newcommand*{\LWR@wrapposition}{}

\newcommand*{\LWR@subwrapfigure}[2]{%
\renewcommand*{\LWR@wrapposition}{}%
\ifthenelse{%
    \equal{#1}{r}\OR\equal{#1}{R}\OR%
```

```
    \equal{#1}{o}\OR\equal{#1}{O}%
}%
    {\renewcommand*{\LWR@wrapposition}{float:right}}%
    {\renewcommand*{\LWR@wrapposition}{float:left}}%
\setlength{\LWR@templengthone}{#2}%
\LWR@BlockClassWP{%
    width:\LWR@printlength{\LWR@templengthone}; \LWR@wrapposition; %
    margin:10pt%
}%
{%
    width:\LWR@printlength{\LWR@templengthone}; \LWR@wrapposition%
}%
{marginblock}%
}


\NewDocumentEnvironment{wrapfigure}{o m o m}
{%
\LWR@subwrapfigure{#2}{#4}%
\captionsetup{type=figure}%
}
{%
\endLWR@BlockClassWP%
}


\NewDocumentEnvironment{wraptable}{o m o m}
{%
\LWR@subwrapfigure{#2}{#4}%
\captionsetup{type=table}%
}
{%
\endLWR@BlockClassWP%
}


\NewDocumentEnvironment{wrapfloat}{m o m o m}
{%
\LWR@subwrapfigure{#3}{#5}%
\captionsetup{type=#1}%
}
{%
\endLWR@BlockClassWP%
}

\newlength{\wrapoverhang}
```

File 388 **lwarp-xbmks.sty**

§ 485 Package xbmks

Pkg xbmks xbmks is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{xbmks}[2018/07/04]

\newcommand{\xbmksetup}[1]{}
\NewDocumentCommand{\pdfbookmarkx}{o m o m}{}
\NewDocumentCommand{\currentpdfbookmarkx}{m o m}{}
\NewDocumentCommand{\subpdfbookmarkx}{m o m}{}
\NewDocumentCommand{\belowpdfbookmarkx}{m o m}{}
```

File 389 **lwarp-xcolor.sty**

§ 486 Package xcolor

(*Emulates or patches code by* Dr. Uwe Kern.)

Pkg xcolor xcolor is supported by lwarp.

§ 486.1 Limitations

\colorboxBlock and \fcolorboxBlock

\colorboxBlock and \fcolorboxBlock are provided for increased HTML compatibility, and they are identical to \colorbox and \fcolorbox in print mode. In HTML mode they place their contents into a instead of a . These s are set to display: inline-block so adjacent \colorboxBlocks appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for \colorboxBlock and \fcolorboxBlock are created by lwarp's core if xcolor is loaded.

background: none

\fcolorbox and \fcolorboxBlock allow a background color of none, in which case only the frame is drawn, which can be useful for HTML.

color support

Color definitions, models, and mixing are fully supported without any changes required.

colored tables

\rowcolors is supported, except that the optional argument is ignored so far.

colored text and boxes

\textcolor, \colorbox, and \fcolorbox are supported.

\color and \pagecolor

\color and \pagecolor are ignored. Use CSS or \textcolor where possible.

§ 486.2 xcolor definitions: location and timing

The lwarp core and its lwarp-xcolor package are tightly integrated to allow comparable results for print, HTML, and print inside an HTML lateximage. This requires a number of definitions and redefintions depending on whether each of xcolor and lateximage is being used, and whether print or HTML is being generated. Some of these actions are one-time when xcolor is loaded, and others are temporary as lateximage is used.

When xcolor is loaded in print mode: No special actions are taken at the time that xcolor is loaded in print mode, but see \AtBeginDocument below.

When lwarp-xcolor is loaded in HTML mode: xcolor's original definitions are saved for later restoration. \LWR@restoreorigformatting is appended to restore these

definitions for use inside a lateximage. New HTML-mode definitions are created for \textcolor, \pagecolor, \nopagecolor, \colorbox, \colorboxBlock, \fcolorbox, \fcolorboxBlock, and fcolorminipage.

\AtBeginDocument in print or HTML mode: See Section 84. If xcolor has been loaded, the print-mode \fcolorbox is modified to accept a background color of none, and additional definitions are created for lwarp's new macros print-mode macros \colorboxBlock, \fcolorboxBlock, and fcolorminipage. The HTML versions of these macros will already have been created by lwarp-xcolor if it has been loaded.

For use inside an HTML lateximage, \LWR@restoreorigformatting is appended to temporarily set these functions to their print-mode versions.

In a lateximage in HTML mode: \LWR@restoreorigformatting temporarily restores the print-mode definitions of xcolor's functions. See \LWR@restoreorigformatting on page 486.

\color:

Print: Used as-is.

HTML: Ignored by *pdftotext*, and will not appear.

HTML lateximage: Colors will appear in a lateximage.

\textcolor:

Print: Used as-is.

HTML: Redefined by lwarp-xcolor, page 946.

HTML lateximage: Remembers and reuses the print version.

\pagecolor:

Print: Used as-is.

HTML: Ignored.

HTML lateximage: Colors will be picked up in a lateximage.

\nopagecolor:

Print: Used as-is.

HTML: Ignored.

HTML lateximage: Colors will be picked up in a lateximage.

\colorbox:

Print: Used as-is.

HTML: Redefined by lwarp-xcolor, page 947.

HTML lateximage: Remembers and reuses the print version.

\colorboxBlock:

Print: Becomes \colorbox.

HTML: Newly defined by lwarp-xcolor to use a , page 947.

HTML lateximage: Remembers and reuses the print version \colorbox.

\fcolorbox:

Print: Modified to allow a background of none.
\LWR@print@fcolorbox at section 84

HTML: Redefined by lwarp-xcolor, page 948.

HTML lateximage: Remembers and reuses the print version.

\fcolorboxBlock:

Print: Becomes \fcolorbox. Section 84

HTML: Newly defined by lwarp-xcolor to use a , page 948.

HTML lateximage: Remembers and reuses the print version \fcolorbox.

fcolorminipage:

Print: Newly defined in the lwarp core.
LWR@print@fcolorminipage at section 84

HTML: Newly defined by lwarp-xcolor, page 949.

HTML lateximage: Uses the print version.

\boxframe:

Print: Used as-is.

HTML: Redefined by lwarp-xcolor, page 950.

HTML lateximage: Remembers and reuses the print version.

§ 486.3 Package loading

for HTML output:

```
\LWR@ProvidesPackagePass{xcolor}[2016/05/11]
\begin{warpHTML}
```

§ 486.4 Remembering and restoring original definitions

Remember the following print-mode actions to be restored when inside a lateximage environment:

```
\LetLtxMacro\LWR@print@pagecolor\pagecolor
\LetLtxMacro\LWR@print@nopagecolor\nopagecolor
```

\LWR@restoreorigformatting Inside a lateximage the following gets restored to their print-mode actions:

```
\appto\LWR@restoreorigformatting{%
\LetLtxMacro\pagecolor\LWR@print@pagecolor%
\LetLtxMacro\nopagecolor\LWR@print@nopagecolor%
}
```

§ 486.5 HTML color style

\LWR@findcurrenttextcolor Sets \LWR@tempcolor to the current color.

```
\renewcommand*{\LWR@findcurrenttextcolor}{%
\protect\colorlet{LWR@current@color}{.}%
\protect\convertcolorspec{named}{LWR@current@color}{HTML}\LWR@tempcolor%
}
```

\LWR@currenttextcolorstyle Prints a color style for the current color.

```
\newcommand*{\LWR@currenttextcolorstyle}{%
\LWR@findcurrenttextcolor%
\ifdefstring{\LWR@tempcolor}{000000}%
{}%
{color: \LWR@origpound\LWR@tempcolor ; }%
}
```

\LWR@textcurrentcolor {⟨*text*⟩} Like \textcolor but uses the current \color instead.

```
\DeclareDocumentCommand{\LWR@textcurrentcolor}{m}{%
\begingroup%
\LWR@FBcancel%
\LWR@findcurrenttextcolor%
\InlineClass[color:\LWR@origpound\LWR@tempcolor]{textcolor}{%
    \renewcommand*{\LWR@currenttextcolor}{\LWR@origpound\LWR@tempcolor}%
    #1%
}%
\endgroup%
}
```

\LWR@colorstyle {⟨*2: model*⟩} {⟨*3: color*⟩}

For a color style, prints the color converted to HTML colors.

```
\NewDocumentCommand{\LWR@colorstyle}{m m}{%
\begingroup%
\LWR@FBcancel%
```

Use the xcolor package to convert to an HTML color space:

```
\convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
```

Print the converted color:

```
\LWR@origpound\LWR@tempcolor%
\endgroup%
}
```

\LWR@backgroundcolor [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Similar to \textcolor, but prints black text against a color background.

Converted into an HTML hex color span.

```
\NewDocumentCommand{\LWR@backgroundcolor}{O{named} m m}{%
\begingroup%
\LWR@FBcancel%
\InlineClass[background:\LWR@colorstyle{#1}{#2}]{backgroundcolor}{%
#3%
}%
\endgroup%
}
```

§ 486.6 HTML border

\LWR@borderpadding {⟨*colorstyle*⟩} {⟨*color*⟩} Prints the HTML attributes for a black border and padding. \LWR@forceminwidth must be used first in order to set the border width.

```
\newcommand*{\LWR@borderpadding}[2]{%
border:\LWR@printlength{\LWR@atleastonept} solid \LWR@colorstyle{#1}{#2} ; %
padding:\LWR@printlength{\fboxsep}%
}
```

§ 486.7 High-level macros

\textcolor [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Converted into an HTML hex color span.

```
\NewDocumentCommand{\LWR@HTML@textcolor}{o m m}{%
\begingroup%
```

Set the PDF color, to be picked up by SVG math if possible.

The print-mode \color command cannot accept the named option with color mixing, but it works with no option at all.

```
\IfValueTF{#1}{%
    \color[#1]{#2}%
}{%
    \color{#2}%
}%

\LWR@FBcancel%
\IfValueTF{#1}{%
\InlineClass[color:\LWR@colorstyle{#1}{#2}]{textcolor}{%
\renewcommand*{\LWR@currenttextcolor}{\LWR@origpound\LWR@tempcolor}%
#3%
}%
}{%
\InlineClass[color:\LWR@colorstyle{named}{#2}]{textcolor}{%
\renewcommand*{\LWR@currenttextcolor}{\LWR@origpound\LWR@tempcolor}%
#3%
}%
}%
\endgroup%
}

```

```
\LWR@formatted{textcolor}
```

\pagecolor [⟨*model*⟩] {⟨*color*⟩}

Ignored. Use css instead.

```
\renewcommand*{\pagecolor}[2][named]{}
```

\nopagecolor Ignored.

```
\renewcommand*{\nopagecolor}{}
```

\colorbox [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Converted into an HTML hex background color .

```
\NewDocumentCommand{\LWR@HTML@colorbox}{O{named} m +m}{%
\begingroup%
\LWR@FBcancel%
\InlineClass[%
background:\LWR@colorstyle{#1}{#2} ; %
padding:\LWR@printlength{\fboxsep}%
]{colorbox}{#3}%
\endgroup%
}

\AtBeginDocument{
\LWR@formatted{colorbox}
}
```

\colorboxBlock [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Converted into an HTML hex background color .

```
\NewDocumentCommand{\LWR@HTML@colorboxBlock}{O{named} m +m}{%
\begingroup%
\LWR@FBcancel%

\LWR@stoppars%

\begin{BlockClass}[%
background:\LWR@colorstyle{#1}{#2} ; %
padding:\LWR@printlength{\fboxsep}%
]{colorboxBlock}
#3
\end{BlockClass}%
\endgroup%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
}

\AtBeginDocument{
\LWR@formatted{colorboxBlock}
}
```

\fcolorbox `[`⟨*framemodel*⟩`]` `{`⟨*framecolor*⟩`}` `[`⟨*boxmodel*⟩`]` `{`⟨*boxcolor*⟩`}` `{`⟨*text*⟩`}`

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```
\NewDocumentCommand{\LWR@HTML@fcolorbox}{O{named} m O{named} m +m}{%
\LWR@traceinfo{HTML fcolorbox #2 #4}%
\begingroup%
\LWR@FBcancel%
\LWR@forceminwidth{\fboxrule}%
\ifthenelse{\equal{#4}{none}}%
    {% no background color
        \InlineClass[%
        \LWR@borderpadding{#1}{#2}%
        ]{fcolorbox}{#5}%
    }%
    {% yes background color
        \InlineClass[%
        \LWR@borderpadding{#1}{#2} ; %
        background:\LWR@colorstyle{#3}{#4}%
        ]{fcolorbox}{#5}%
    }%
\endgroup%
}

\AtBeginDocument{
\LWR@formatted{fcolorbox}
}
```

\fcolorboxBlock `[`⟨*framemodel*⟩`]` `{`⟨*framecolor*⟩`}` `[`⟨*boxmodel*⟩`]` `{`⟨*boxcolor*⟩`}` `{`⟨*text*⟩`}`

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```
\NewDocumentCommand{\LWR@HTML@fcolorboxBlock}{O{named} m O{named} m +m}{%
\LWR@traceinfo{HTML fcolorboxBlock #2 #4}%
\begingroup%
\LWR@FBcancel%
\LWR@forceminwidth{\fboxrule}%

\LWR@stoppars%
```

```
\ifthenelse{\equal{#4}{none}}%
    {% no background color
        \begin{BlockClass}[%
            \LWR@borderpadding{#1}{#2}%
        ]{fcolorboxBlock}
        #5
        \end{BlockClass}%
    }%
    {% yes background color
        \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
        \begin{BlockClass}[%
            background:\LWR@origpound\LWR@tempcolortwo\ ; %
            \LWR@borderpadding{#1}{#2}%
        ]{fcolorboxBlock}
        #5
        \end{BlockClass}%
    }%
\endgroup%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
\LWR@traceinfo{HTML fcolorboxBlock done}%
}

\AtBeginDocument{
\LWR@formatted{fcolorboxBlock}
}
```

Creates a framed HTML around its contents.

A print-output version is defined in the lwarp core: section 84

\LWR@subfcolorminipage {⟨*framemodel*⟩} {⟨*framecolor*⟩} {⟨*background tag*⟩} {⟨*height*⟩}

```
\NewDocumentCommand{\LWR@subfcolorminipage}{m m m m}{%

\LWR@stoppars%

\begin{BlockClass}[%
#3%
\LWR@borderpadding{#1}{#2} ; %
\IfValueT{#4}{height:\LWR@printlength{\LWR@tempheight} ; }%
width:\LWR@printlength{\LWR@tempwidth}%
]{fcolorminipage}%
}
```

Env fcolorminipage [⟨*1:framemodel*⟩] {⟨*2:framecolor*⟩} [⟨*3:boxmodel*⟩] {⟨*4:boxcolor*⟩} [⟨*5:align*⟩] [⟨*6:height*⟩] [⟨*7:inner-align*⟩] {⟨*8:width*⟩}

```
\NewDocumentEnvironment{LWR@HTML@fcolorminipage}{O{named} m O{named} m O{c} o o m}
{%
```

```
\LWR@FBcancel%
\setlength{\LWR@tempwidth}{#8}%
\IfValueT{#6}{\setlength{\LWR@tempheight}{#6}}%
\LWR@forceminwidth{\fboxrule}%
\convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
\ifthenelse{\equal{#4}{none}}%
    {\LWR@subfcolorminipage{#1}{#2}{}{#6}}%
    {%
        \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
        \LWR@subfcolorminipage{#1}{#2}%
            {background:\LWR@origpound\LWR@tempcolortwo\ ; }%
            {#6}%
    }%
}%
{%
    \end{BlockClass}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
    \global\booltrue{LWR@minipagethispar}%
}

\AtBeginDocument{
\LWR@formattedenv{fcolorminipage}
}
```

`\boxframe` {⟨*width*⟩} {⟨*height*⟩} {⟨*depth*⟩}

The depth is added to the height, but the box is not decended below by the depth. `\textcolor` is honored.

```
\newcommand*{\LWR@HTML@boxframe}[3]{%
{%
\setlength{\LWR@tempwidth}{#1}%
\setlength{\LWR@tempheight}{#2}%
\addtolength{\LWR@tempheight}{#3}%
\LWR@forceminwidth{\fboxrule}%
\LWR@findcurrenttextcolor%
\InlineClass[%
display:inline-block ; %
border:\LWR@printlength{\LWR@atleastonept} solid \LWR@currenttextcolor{} ; %
width:\LWR@printlength{\LWR@tempwidth} ; %
height:\LWR@printlength{\LWR@tempheight}%
]{boxframe}{}%
}%
}

\LWR@formatted{boxframe}
```

§ 486.8 Row colors

\rowc@l@rs [⟨*cmds*⟩] {⟨*startrow*⟩} {⟨*odd color*⟩} {⟨*even color*⟩}

```
\newcommand*{\LWR@xcolortempcolor}{}

\def\rowc@l@rs[#1]#2#3#4%
{
\global\rownum=1
   \global\@rowcolorstrue
   \@ifxempty{#3}%
     {\def\@oddrowcolor{\@norowcolor}}%
     {%
        \convertcolorspec{named}{#3}{HTML}\LWR@xcolortempcolor%
        \edef\@oddrowcolor{%
            \csdef{LWR@xcolorrowHTMLcolor}{\LWR@xcolortempcolor}%
        }%
     }%
   \@ifxempty{#4}%
     {\def\@evenrowcolor{\@norowcolor}}%
     {%
        \convertcolorspec{named}{#4}{HTML}\LWR@xcolortempcolor%
        \edef\@evenrowcolor{%
            \csdef{LWR@xcolorrowHTMLcolor}{\LWR@xcolortempcolor}%
        }%
     }%
   \if@rowcmd
     \def\@rowcolors
     {%
%          #1%
        \if@rowcolors
%         \noalign{%
            \relax\ifnum\rownum<#2\@norowcolor\else
            \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi\fi%
%          }%
        \fi%
     }%
   \else
     \def\@rowcolors
     {%
        \if@rowcolors
            \ifnum\rownum<#2%
%            \noalign{%
                \@norowcolor
%             }
            \else
%            #1%
%            \noalign{%
               \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi%
%             }%
            \fi
        \fi%
     }%
   \fi
   \ignorespaces%
}
```

\@norowcolor Turns off color for this row.

```
\def\@norowcolor{%
\renewcommand{\LWR@xcolorrowHTMLcolor}{}%
}
```

\@rowc@lors Executed at the end of each row.

```
\def\@rowc@lors{%
%   \noalign{%
        \global\advance\rownum\@ne%
%   }%
    \@rowcolors%
}

\end{warpHTML}
```

File 390 **lwarp-xechangebar.sty**

§ 487 Package xechangebar

Pkg xechangebar xechangebar is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{xechangebar}[2017/08/03]
\LWR@origRequirePackage{lwarp-changebar}
```

File 391 **lwarp-xellipsis.sty**

§ 488 Package xellipsis

(*Emulates or patches code by* Donald P. Goodman III.)

Pkg xellipsis xellipsis is patched for use by lwarp.

When non-zero, each of the spaces is converted to an HTML thin unbreakable space.

for HTML output:

```
\LWR@ProvidesPackagePass{xellipsis}[2015/11/01]

\newcommand*{\LWR@xellipsespace}[1]{%
\ifdim#1=0pt\else%
    \ifdim#1<\fontdimen2\font%
        \,%
    \else%
        ~%
    \fi%
\fi%
}

```

```
\def\xelip{%
\mbox{%
    \LWR@xellipsespace{\xelipprebef}%
    \xelipprechar%
    \LWR@xellipsespace{\xelippreaft}%
    \LWR@xellipsespace{\xelipbef}%
    \xelipchar%
    \xel@loopi = 1%
    \loop\ifnum\xelipnum>\xel@loopi%
        \advance\xel@loopi by1%
        \LWR@xellipsespace{\xelipgap}%
        \xelipchar%
    \repeat%
    \LWR@xellipsespace{\xelipaft}%
    \LWR@xellipsespace{\xelippostbef}%
    \xelippostchar%
    \LWR@xellipsespace{\xelippostaft}%
}%
}%
```

File 392 **lwarp-xetexko-vertical.sty**

§ 489 Package

xetexko-vertical

(*Emulates or patches code by* Dohyun Kim.)

Pkg xetexko-vertical xetexko-vertical is patched for use by lwarp.

for HTML output:

```
\LWR@loadbefore{xetexko-vertical}

\LWR@ProvidesPackagePass{xetexko-vertical}[2018/04/06]

\renewcommand{\verticaltypesetting}{}
\renewenvironment{vertical}[1]{\BlockClass{verticalrl}}{\endBlockClass}
\renewenvironment{horizontal}[1]{\BlockClass{horizontaltb}}{\endBlockClass}
\renewcommand{\vertlatin}[1]{#1}
```

File 393 **lwarp-xfakebold.sty**

§ 490 Package

xfakebold

(*Emulates or patches code by* Herbert Voss.)

Pkg xfakebold xfakebold is patched for use by lwarp, and additional underlying support is found in the lwarp core.

⚠ page breaks Note that the print version resets to unbold at each page break, whereas the HTML version maintains the bold state until it is undone.

for HTML output:

```
\LWR@ProvidesPackagePass{xfakebold}[2018/07/25]
```

```
\let\LWR@orig@setBold\setBold
\let\LWR@orig@unsetBold\unsetBold
\renewcommand*{\setBold}{\booltrue{LWR@xfakebold}}
\renewcommand*{\unsetBold}{\boolfalse{LWR@xfakebold}}

\renewcommand*{\LWR@applyxfakebold}{%
    \ifbool{LWR@xfakebold}{\LWR@orig@setBold}{\LWR@orig@unsetBold}%
}
```

File 394 **lwarp-xfrac.sty**

§ 491 Package

xfrac

(*Emulates or patches code by* The LaTeX3 Project.)

Pkg xfrac Supported by adding xfrac instances.

for HTML output:

```
\LWR@ProvidesPackagePass{xfrac}[2018-08-23]
```

⚠ font size In the user's document preamble, lwarp should be loaded after font-related setup. During HTML conversion, this font is used by lwarp to generate its initial PDF output containing HTML tags, later to be converted by *pdftotext* to a plain text file. While the text may be in any font which *pdftotext* can read, the math is directly converted into SVG images using this same user-selected font. xfrac below is set for the Latin Modern (lmr) font. If another font is used, it may be desirable to redefine \xfracHTMLfontsize with a different em size.

\sfrac [⟨*instance*⟩] {⟨*num*⟩} [⟨*sep*⟩] {⟨*denom*⟩}

A text-mode instance for the default font is provided below. The numerator and denominator formats are adjusted to encase everything in HTML tags. \scalebox is made null inside the numerator and denominator, since the HTML tags should not be scaled, and we do not want to introduce additional HTML tags for scaling.

In math mode, which will appear inside a lateximage, no adjustments are necessary.

for HTML & PRINT:

```
\begin{warpall}
```

\xfracHTMLfontsize User-redefinable macro which controls the font size of the fraction.

```
\newcommand*{\xfracHTMLfontsize}{.6em}

\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

instances Instances of xfrac for various font choices:

Produce CSS for a small raised numerator and a small denominator.

Scaling is turned off so that *pdftotext* correctly reads the result.

```
\DeclareInstance{xfrac}{default}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}

\DeclareInstance{xfrac}{lmr}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}

\DeclareInstance{xfrac}{lmss}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
```

```
}

\DeclareInstance{xfrac}{lmtt}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}


\end{warpHTML}
```

File 395 **lwarp-xltabular.sty**

§ 492 Package

xltabular

(*Emulates or patches code by* Rolf Niepraschk, Herbert Voss.)

Pkg xltabular xltabular is emulated by lwarp.

for HTML output: Relies on tabularx.

⚠ table numbering At present, an `xltabular` without a caption or with only a `\caption*` may be misnumbered in HTML, so it may be necessary to place at the end of the table:

```
\warpHTMLonly{\addtocounter{table}{-1}}
```

```
\RequirePackage{tabularx}

\LWR@ProvidesPackageDrop{xltabular}[2018/05/23]

\DeclareDocumentEnvironment{xltabular}{o m m}
{\longtable{#3}}
{\endlongtable}
```

File 396 **lwarp-xltxtra.sty**

§ 493 Package xltxtra

(*Emulates or patches code by* Will Robertson, Jonathan Kew.)

Pkg xltxtra xltxtra is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{xltxtra}[2016/01/21]

\RequirePackage{realscripts}
\RequirePackage{metalogo}
\newcommand*\TeX@logo@spacing[6]{}

\newcommand*{\vfrac}[2]{%
\textsuperscript{#1}/\textsubscript{#2}%
}

\newcommand\namedglyph[1]{%
  \@tempcnta=\XeTeXglyphindex "#1"\relax
  \ifnum\@tempcnta>0
    \XeTeXglyph\@tempcnta
  \else
    \xxt@namedglyph@fallback{#1}%
  \fi}

\newcommand\xxt@namedglyph@fallback[1]{[#1]}

\DeclareDocumentCommand{\showhyphens}{m}{}
```

File 397 **lwarp-xmpincl.sty**

§ 494 Package xmpincl

(*Emulates or patches code by* Maarten Sneep.)

Pkg xmpincl Emulated.

for HTML output: Discard all options for lwarp-xmpincl:

```
\LWR@ProvidesPackageDrop{xmpincl}[2008/05/10]

\newcommand*{\includexmp}[1]{}
```

File 398 **lwarp-xpiano.sty**

§ 495 Package xpiano

(*Emulates or patches code by* Enrico Gregorio.)

Pkg xpiano xpiano is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{xpiano}

\ExplSyntaxOn
\NewDocumentCommand{\LWR@print@keyboard}{ O{}m }
{
\xpiano_keyboard:nn { #1 } { #2 }
}

\NewDocumentCommand{\LWR@HTML@keyboard}{ O{}m }
{
\begin{lateximage}*
    [(-xpiano-~\packagediagramname{}: \detokenize\expandafter{#2})]
    [\detokenize\expandafter{#1}]
\xpiano_keyboard:nn { #1 } { #2 }
\end{lateximage}
}
\ExplSyntaxOff

\LWR@formatted{keyboard}
```

File 399 **lwarp-xpinyin.sty**

§ 496 Package xpinyin

(*Emulates or patches code by* Soben Lee.)

Pkg xpinyin xpinyin is partly supported. `\xpinyin` and `pinyinscope` are nullified, but `\pinyin` works.

for HTML output:

```
\LWR@ProvidesPackagePass{xpinyin}[2018/01/28]

\RenewDocumentEnvironment{pinyinscope}{O{}}{}{}

\RenewDocumentCommand{\xpinyin}{s O{} m}{%
    \IfBooleanTF{#1}{#3}{\@firstoftwo#3}%
}

\RenewDocumentCommand{\enablepinyin}{}{}
```

File 400 **lwarp-xtab.sty**

§ 497 Package

xtab

(*Emulates or patches code by* Peter Wilson.)

Pkg xtab xtab is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{xtab}[2011/07/31]
```

⚠ Misplaced alignment tab character &

For `\tablefirsthead`, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
. . .
\StopDefiningTabulars
```

See section 9.10.

⚠ lateximage supertabular and xtab are not supported inside a `lateximage`.

```
\newcommand{\LWRXT@firsthead}{}

\newcommand{\tablefirsthead}[1]{%
    \long\gdef\LWRXT@firsthead{#1}%
}

\newcommand{\tablehead}[1]{}

\newcommand{\tablelasthead}[1]{}

\newcommand{\notablelasthead}{}

\newcommand{\tabletail}[1]{}

\newcommand{\LWRXT@lasttail}{}

\newcommand{\tablelasttail}[1]{%
    \long\gdef\LWRXT@lasttail{#1}%
}


\newcommand{\tablecaption}[2][]{%
    \long\gdef\LWRXT@caption{%
        \ifblank{#1}%
            {\caption{#2}}%
            {\caption[#1]{#2}}%
    }%
}

\let\topcaption\tablecaption
\let\bottomcaption\tablecaption
```

```
\newcommand*{\LWRXT@caption}{}

\newcommand*{\shrinkheight}[1]{}

\newcommand*{\xentrystretch}[1]{}

\NewDocumentEnvironment{xtabular}{s o m}
{%
\LWR@traceinfo{xtabular}%
\table%
\LWRXT@caption%
\begin{tabular}{#3}%
\TabularMacro\ifdefvoid{\LWRXT@firsthead}%
{\LWR@getmynexttoken}%
{\expandafter\LWR@getmynexttoken\LWRXT@firsthead}%
}%
{%
\ifdefvoid{\LWRXT@lasttail}%
{}%
{%
\TabularMacro\ResumeTabular%
\LWRXT@lasttail%
}%
\end{tabular}%
\endtable%
\LWR@traceinfo{xtabular done}%
}

\NewDocumentEnvironment{mpxtabular}{s o m}
{\minipage{\linewidth}\xtabular{#3}}
{\endxtabular\endminipage}
```

File 401 **lwarp-xunicode.sty**

§ 498 Package

xunicode

Pkg xunicode

Error if xunicode is loaded after lwarp.

Patch lwarp-xunicode, but also verify that is was loaded before lwarp:

for HTML output:

```
\LWR@loadbefore{xunicode}%

\LWR@ProvidesPackagePass{xunicode}[2011/09/09]
```

\textcircled becomes a span with a rounded border. \providecommand is used to avoid conflict with textcomp.

```
\providecommand*{\LWR@HTML@textcircled}[1]{%
    \InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{#1}%
}

\LWR@formatted{textcircled}
```

Nullify textcomp macros when generating filenames:

```
\FilenameNullify{%
    \renewcommand*{\textdegree}{}%
    \renewcommand*{\textcelsius}{}%
    \renewcommand*{\textohm}{}%
    \renewcommand*{\textmu}{}%
    \renewcommand*{\textlquill}{}%
    \renewcommand*{\textrquill}{}%
    \renewcommand*{\textcircledP}{}%
    \renewcommand*{\texttwelveudash}{}%
    \renewcommand*{\textthreequartersemdash}{}%
    \renewcommand*{\textmho}{}%
    \renewcommand*{\textnaira}{}%
    \renewcommand*{\textpeso}{}%
    \renewcommand*{\textrecipe}{}%
    \renewcommand*{\textinterrobangdown}{}%
    \renewcommand*{\textperthousand}{}%
    \renewcommand*{\textpertenthousand}{}%
    \renewcommand*{\textbaht}{}%
    \renewcommand*{\textdiscount}{}%
    \renewcommand*{\textservicemark}{}%
    \renewcommand*{\textcircled}[1]{#1}%
    \renewcommand*{\capitalcedilla}[1]{#1}%
    \renewcommand*{\capitalogonek}[1]{#1}%
    \renewcommand*{\capitalgrave}[1]{#1}%
    \renewcommand*{\capitalacute}[1]{#1}%
    \renewcommand*{\capitalcircumflex}[1]{#1}%
    \renewcommand*{\capitaltilde}[1]{#1}%
    \renewcommand*{\capitaldieresis}[1]{#1}%
    \renewcommand*{\capitalhungarumlaut}[1]{#1}%
    \renewcommand*{\capitalring}[1]{#1}%
    \renewcommand*{\capitalcaron}[1]{#1}%
    \renewcommand*{\capitalbreve}[1]{#1}%
    \renewcommand*{\capitalmacron}[1]{#1}%
    \renewcommand*{\capitaldotaccent}[1]{#1}%
}% FilenameNullify
```

File 402 **lwarp-xurl.sty**

§ 499 Package **xurl**

Pkg xurl xurl is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{xurl}[2018/06/02]
```

File 403 **lwarp-xy.sty**

§ 500 Package xy

(*Emulates or patches code by* Kristoffer H. Rose, Ross Moore.)

Pkg xy xy is patched for use by lwarp.

⚠ \xypolygon \xypolygon must be used inside the xy environment, or inside \xy ... \endxy.

for HTML output:

```
\LWR@ProvidesPackagePass{xy}[2013/10/06]

\AtBeginDocument{

\preto{\xy}{\begin{lateximage}[(-xy-~\packagediagramname)]}
\appto{\endxy}{\end{lateximage}}

\@ifundefined{xymatrix}{}{
\LetLtxMacro\LWR@origxymatrix\xymatrix

\renewcommand{\xymatrix}[1]{%
\begin{lateximage}[(-xy- xymatrix \packagediagramname)]
\LWR@origxymatrix{#1}
\end{lateximage}
}
}

\@ifundefined{xygraph}{}{
\LetLtxMacro\LWR@origxygraph\xygraph

\renewcommand{\xygraph}[1]{%
\begin{lateximage}[(-xy- xygraph \packagediagramname)]
\LWR@origxygraph{#1}
\end{lateximage}
}
}

}
```

File 404 **lwarp-zhlineskip.sty**

§ 501 Package zhlineskip

Pkg zhlineskip zhlineskip is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{zhlineskip}[2018/11/30]

\newcommand*\SetTextEnvironmentSinglespace[1]{}
```

```
\newcommand*\RestoreTextEnvironmentLeading{}
\newcommand*\SetMathEnvironmentSinglespace[1]{}
\newcommand*\RestoreMathEnvironmentLeading{}
```

File 405 **lwarp-zwpagelayout.sty**

§ 502 Package zwpagelayout

(*Emulates or patches code by* Zdeněk Wagner.)

Pkg zwpagelayout zwpagelayout is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{zwpagelayout}[2013/01/13]

\def\noBboxes{}
\@onlypreamble\noBboxes

\expandafter\ifx\csname definecolor\endcsname\relax \else
  \definecolor{cmykblack}{cmyk}{0,0,0,1}
  \definecolor{grblack}{gray}{0}
%   \ifzwpl@redefineblack
%     \definecolor{black}{cmyk}{0,0,0,1}\color{black}
%   \fi
  \definecolor{cmykred}{cmyk}{0,1,1,0}
  \definecolor{cmykgreen}{cmyk}{1,0,1,0}
  \definecolor{cmykblue}{cmyk}{1,1,0,0}
  \definecolor{rgbred}{rgb}{1,0,0}
  \definecolor{rgbgreen}{rgb}{0,1,0}
  \definecolor{rgbblue}{rgb}{0,0,1}
%   \ifzwpl@redefinetocmyk
%     \definecolor{red}{cmyk}{0,1,1,0}
%     \definecolor{green}{cmyk}{1,0,1,0}
%     \definecolor{blue}{cmyk}{1,1,0,0}
%   \fi
\fi

\let\OverprintXeTeXExtGState\relax

\DeclareRobustCommand\SetOverprint{\ignorespaces}
\DeclareRobustCommand\SetKnockout{\ignorespaces}
\DeclareRobustCommand\textoverprint[1]{{\SetOverprint#1}}
\DeclareRobustCommand\textknockout[1]{{\SetKnockout#1}}

\def\SetPDFminorversion#1{}
\@onlypreamble\SetPDFminorversion

\newcommand*\Vcorr{}

\DeclareRobustCommand\vb[1][]{}
\NewDocumentCommand{\NewOddPage}{* o}{}
\NewDocumentCommand{\NewEvenPage}{* o}{}
\def\SetOddPageMessage#{\gdef\ZW@oddwarning}
\def\SetEvenPageMessage#{\gdef\Z@@evenwarning}
```

```
\def\ZW@oddwarning{Empty page inserted}\let\ZW@evenwarning\ZW@oddwarning

\def\clap#1{#1}

\def\CropFlap{2in}
\def\CropSpine{1in}
\def\CropXSpine{1in}
\def\CropXtrim{.25in}
\def\CropYtrim{.25in}
\def\UserWidth{5in}
\def\UserLeftMargin{1in}
\def\UserRightMargin{1in}
\def\UserTopMargin{1in}
\def\UserBotMargin{1in}
\def\thePageNumber{\LWR@origpound\,\arabic{page}}
\ifXeTeX
\def\ifcaseZWdriver{\ifcase2}
\else
\def\ifcaseZWdriver{\ifcase1}
\fi
\DeclareRobustCommand\ZWifdriver[2]{}
```

File 406 **lwarp-patch-komascript.sty**

§ 503 Package

patch-komascript

Pkg lwarp-patch-komascript

Patches for komascript classes.

lwarp loads this package when scrbook, scrartcl, or scrreprt classes are detected.

Many features are ignored during the HTML conversion. The goal is source-level compatibility.

\titlehead, \subject, \captionformat, \figureformat, and \tableformat are not yet emulated.

⚠ Not fully tested! Please send bug reports!

Some features have not yet been tested. Please contact the author with any bug reports.

for HTML output:

```
\ProvidesPackage{lwarp-patch-komascript}
```

typearea is emulated.

```
\RequirePackage{lwarp-typearea}
```

tocbasic is emulated.

```
\RequirePackage{lwarp-tocbasic}
```

scrextend patches most of the new macros.

```
\RequirePackage{lwarp-scrextend}
```

Indexing macros, simplified for lwarp:

```
\AtBeginDocument{

\renewcommand*{\idx@heading}{%
  \idx@@heading{\indexname}%
}

\renewenvironment{theindex}{%
  \idx@heading%
  \index@preamble\par\nobreak
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}
{}

\renewcommand*\indexspace{}

}% AtBeginDocument
```

The \minisec is placed inside a of class minisec.

```
\renewcommand*{\minisec}[1]{
\begin{BlockClass}{minisec}
#1
\end{BlockClass}
}
```

The part and chapter preambles are placed as plain text just after each heading.

```
\@ifundefined{setpartpreamble}{}{
\RenewDocumentCommand{\setpartpreamble}{o o +m}{%
\renewcommand{\part@preamble}{#3}%
}
}

\@ifundefined{setchapterpreamble}{}{
\RenewDocumentCommand{\setchapterpreamble}{o o +m}{%
\renewcommand{\chapter@preamble}{#3}%
}
}
```

Simple captions are used in all cases.

```
\LetLtxMacro\captionbelow\caption
\LetLtxMacro\captionabove\caption

\LetLtxMacro\captionofbelow\captionof
\LetLtxMacro\captionofabove\captionof

\RenewDocumentEnvironment{captionbeside}{o m o o o s}
{}
```

```
{%
\IfValueTF{#1}%
{\caption[#1]{#2}}%
{\caption{#2}}%
}

\RenewDocumentEnvironment{captionofbeside}{m o m o o o s}
{}
{%
\IfValueTF{#2}%
{\captionof{#1}[#2]{#3}}%
{\captionof{#1}{#3}}%
}

\RenewDocumentCommand{\setcapindent}{s m}{}
\renewcommand*{\setcaphanging}{}
\renewcommand*{\setcapwidth}[2][]{}
\renewcommand*{\setcapdynwidth}[2][]{}
\RenewDocumentCommand{\setcapmargin}{s o m}{}
```

File 407 **lwarp-patch-memoir.sty**

§ 504 Package

patch-memoir

(*Emulates or patches code by* Peter Wilson.)

Pkg lwarp-patch-memoir Patches for memoir class.

⚠ Not fully tested! Please send bug reports!

lwarp loads this package when the memoir class is detected.

⚠ options clash While emulating memoir, lwarp pre-loads a number of packages (section 504.1). This can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading lwarp:

```
\documentclass{memoir}
. . .
\PassOptionsToPackage{options_list}{package_name}
. . .
\usepackage{lwarp}
. . .
\usepackage{package_name}
```

⚠ version numbers memoir emulates a number of packages, and declares a version date for each which often does not match the date of the corresponding freestanding package. This can cause warnings about incorrect version numbers. Since lwarp is intended to support the freestanding packages, which are often newer than the date declared by memoir, it is hoped that memoir will update and change its emulated version numbers to match.

`\verbfootnote` is not supported.

`\newfootnoteseries`, etc. are not supported.

lwarp loads pagenote to perform memoir's pagenote functions, but there are minor differences in \pagenotesubhead and related macros.

Poem numbering is not supported.

The verbatim environment does not yet support the memoir enhancements. It is currently recommended to load and use fancyvrb instead.

The memoir glossary system is not yet supported by *lwarpmk*. The glossaries package may be used instead, but does require the glossary entries be changed from the memoir syntax to the glossaries syntax.

for HTML output:

```
\ProvidesPackage{lwarp-patch-memoir}
```

§ 504.1 Packages

These are pre-loaded to provide emulation for many of memoir's functions. memoir pretends that abstract, etc. are already loaded, via its "emulated" package mechanism, but lwarp is directly loading the "lwarp-" version of each, which happens to avoid memoir's emulation system.

```
\RequirePackage{lwarp-abstract}% req'd
\RequirePackage{lwarp-array}% req'd
\RequirePackage{lwarp-booktabs}% req'd
% \RequirePackage{lwarp-ccaption}% emualated below
\RequirePackage{lwarp-changepage}% req'd
\RequirePackage{lwarp-crop}
\RequirePackage{lwarp-dcolumn}% req'd
\RequirePackage{lwarp-enumerate}% req'd
\RequirePackage{lwarp-epigraph}% req'd
\RequirePackage{lwarp-fancyvrb}% req'd
\RequirePackage{lwarp-footmisc}% req'd
\RequirePackage{lwarp-framed}% req'd
\RequirePackage{lwarp-hanging}% req'd
\RequirePackage{lwarp-makeidx}% req'd
\DisemulatePackage{moreverb}
\RequirePackage{lwarp-moreverb}
\RequirePackage{lwarp-mparhack}
\RequirePackage{lwarp-needspace}% req'd
\RequirePackage{lwarp-nextpage}% req'd
\RequirePackage{lwarp-pagenote}% req'd
\RequirePackage{lwarp-parskip}
\RequirePackage{lwarp-setspace}% req'd
\RequirePackage{lwarp-showidx}
\RequirePackage{lwarp-subfigure}% red'q
\makeindex
```

subfigure is emulated via subfig, which pre-defines subfigure and subtable, but memoir does not, so they must be tested for here:

```
\LetLtxMacro\LWR@memorignewsubfloat\newsubfloat
\RenewDocumentCommand{\newsubfloat}{O{} m}{%
    \@ifundefined{c@sub#2}{%
        \LWR@memorignewsubfloat[#1]{#2}%
```

```
    }{}%
}

\RequirePackage{lwarp-tabularx}% req'd
\RequirePackage{lwarp-titling}% req'd
% \RequirePackage{lwarp-tocbibind}% not emulated by memoir
\RequirePackage{lwarp-tocloft}% req'd
\RequirePackage{lwarp-verse}% req'd
```

§ 504.2 Preliminary setup

Bypass the memoir package mechanism:

```
\LetLtxMacro\LWR@orig@label\@mem@old@label
```

memoir already set the page size to a default, so it must be forced large for lwarp's use, to avoid tag overflows off the page.

```
\setstocksize{190in}{20in}
\setlrmarginsandblock{2in}{2in}{*}
\setulmarginsandblock{1in}{1in}{*}
```

§ 504.3 Laying out the page

```
\renewcommand*{\stockavi}{}
\renewcommand*{\stockav}{}
\renewcommand*{\stockaiv}{}
\renewcommand*{\stockaiii}{}
\renewcommand*{\stockbvi}{}
\renewcommand*{\stockbv}{}
\renewcommand*{\stockbiv}{}
\renewcommand*{\stockbiii}{}
% \renewcommand*{\stockmetriccrownvo}{}% in docs but not in the package
\renewcommand*{\stockmlargecrownvo}{}
\renewcommand*{\stockmdemyvo}{}
\renewcommand*{\stockmsmallroyalvo}{}
\renewcommand*{\pageavi}{}
\renewcommand*{\pageav}{}
\renewcommand*{\pageaiv}{}
\renewcommand*{\pageaiii}{}
\renewcommand*{\pagebvi}{}
\renewcommand*{\pagebv}{}
\renewcommand*{\pagebiv}{}
\renewcommand*{\pagebiii}{}
% \renewcommand*{\pagemetriccrownvo}{}% in docs but not in the package
\renewcommand*{\pagemlargecrownvo}{}
\renewcommand*{\pagemdemyvo}{}
\renewcommand*{\pagemsmallroyalvo}{}

\renewcommand*{\stockdbill}{}
\renewcommand*{\stockstatement}{}
\renewcommand*{\stockexecutive}{}
\renewcommand*{\stockletter}{}
\renewcommand*{\stockold}{}
\renewcommand*{\stocklegal}{}
```

```
\renewcommand*{\stockledger}{}
\renewcommand*{\stockbroadsheet}{}
\renewcommand*{\pagedbill}{}
\renewcommand*{\pagestatement}{}
\renewcommand*{\pageexecutive}{}
\renewcommand*{\pageletter}{}
\renewcommand*{\pageold}{}
\renewcommand*{\pagelegal}{}
\renewcommand*{\pageledger}{}
\renewcommand*{\pagebroadsheet}{}

\renewcommand*{\stockpottvo}{}
\renewcommand*{\stockfoolscapvo}{}
\renewcommand*{\stockcrownvo}{}
\renewcommand*{\stockpostvo}{}
\renewcommand*{\stocklargecrownvo}{}
\renewcommand*{\stocklargepostvo}{}
\renewcommand*{\stocksmalldemyvo}{}
\renewcommand*{\stockdemyvo}{}
\renewcommand*{\stockmediumvo}{}
\renewcommand*{\stocksmallroyalvo}{}
\renewcommand*{\stockroyalvo}{}
\renewcommand*{\stocksuperroyalvo}{}
\renewcommand*{\stockimperialvo}{}
\renewcommand*{\pagepottvo}{}
\renewcommand*{\pagefoolscapvo}{}
\renewcommand*{\pagecrownvo}{}
\renewcommand*{\pagepostvo}{}
\renewcommand*{\pagelargecrownvo}{}
\renewcommand*{\pagelargepostvo}{}
\renewcommand*{\pagesmalldemyvo}{}
\renewcommand*{\pagedemyvo}{}
\renewcommand*{\pagemediumvo}{}
\renewcommand*{\pagesmallroyalvo}{}
\renewcommand*{\pageroyalvo}{}
\renewcommand*{\pagesuperroyalvo}{}
\renewcommand*{\pageimperialvo}{}

\renewcommand*{\memfontfamily}{}
\renewcommand*{\memfontenc}{}
\renewcommand*{\memfontpack}{}

\renewcommand*{\anyptfilebase}{}
\renewcommand*{\anyptsize}{10}

\renewcommand*{\setstocksize}[2]{}
\renewcommand*{\settrimmedsize}[3]{}
\renewcommand*{\settrims}[2]{}

% \newlength{\lxvchars}
% \setlength{\lxvchars}{305pt}
% \newlength{\xlvchars}
% \setlength{\xlvchars}{190pt}
\renewcommand*{\setxlvchars}[1]{}
\renewcommand*{\setlxvchars}[1]{}
```

```
129
130 \renewcommand*{\settypeblocksize}[3]{}
131 \renewcommand*{\setlrmargins}[3]{}
132 \renewcommand*{\setlrmarginsandblock}[3]{}
133 \renewcommand*{\setbinding}[1]{}
134 \renewcommand*{\setulmargins}[3]{}
135 \renewcommand*{\setulmarginsandblock}[3]{}
136 \renewcommand*{\setcolsepandrule}[2]{}
137
138 \renewcommand*{\setheadfoot}[2]{}
139 \renewcommand*{\setheaderspaces}[3]{}
140 \renewcommand*{\setmarginnotes}[3]{}
141 \renewcommand*{\setfootins}[2]{}
142 \renewcommand*{\checkandfixthelayout}[1][]{}
143 \renewcommand*{\checkthelayout}[1]{}
144 \renewcommand*{\fixthelayout}{}
145 %
146 % \newlength{\stockheight}
147 % \newlength{\trimtop}
148 % \newlength{\trimedge}
149 % \newlength{\stockwidth}
150 % \newlength{\spinemargin}
151 % \newlength{\foremargin}
152 % \newlength{\uppermargin}
153 % \newlength{\headmargin}
154 %
155 \renewcommand*{\typeoutlayout}{}
156 \renewcommand*{\typeoutstandardlayout}{}
157 \renewcommand*{\settypeoutlayoutunit}[1]{}
158 \renewcommand*{\fixpdflayout}{}
159 \renewcommand*{\fixdvipslayout}{}
160
161 \renewcommand*{\medievalpage}[1][]{}
162 \renewcommand*{\isopage}[1][]{}
163 \renewcommand*{\semiisopage}[1][]{}
164
165 \renewcommand{\setpagebl}[3]{}
166 \renewcommand{\setpageml}[3]{}
167 \renewcommand{\setpagetl}[3]{}
168 \renewcommand{\setpagetm}[3]{}
169 \renewcommand{\setpagetr}[3]{}
170 \renewcommand{\setpagemr}[3]{}
171 \renewcommand{\setpagebr}[3]{}
172 \renewcommand{\setpagebm}[3]{}
173 \renewcommand{\setpagecc}[3]{}
```

§ 504.4 Text and fonts

```
174 \let\miniscule\tiny
175 \let\HUGE\Huge
176
177 \renewcommand*{\abnormalparskip}[1]{}
178 \renewcommand*{\nonzeroparskip}{}
179 \renewcommand*{\traditionalparskip}{}
180
```

```
\let\onelineskip\baselineskip

\let\OnehalfSpacing\onehalfspacing
\let\DoubleSpacing\doublespacing
\renewcommand*{\setPagenoteSpacing}[1]{}
\renewcommand*{\setFloatSpacing}[1]{}
\let\SingleSpacing\singlespacing
\let\setSingleSpace\SetSinglespace
\let\SingleSpace\singlespace
\let\endSingleSpace\endsinglespace
\let\Spacing\spacing
\let\endSpacing\endspacing
\let\OnehalfSpace\onehalfspace
\let\endOnehalfSpace\endonehalfspace
\csletcs{OnehalfSpace*}{onehalfspace}
\csletcs{endOnehalfSpace*}{endonehalfspace}
\let\DoubleSpace\doublespace
\let\endDoubleSpace\enddoublespace
\csletcs{DoubleSpace*}{doublespace}
\csletcs{endDoubleSpace*}{enddoublespace}
\renewcommand*{\setDisplayskipStretch}[1]{}
\renewcommand*{\memdskipstretch}{}
\renewcommand*{\noDisplayskipStretch}{}
\renewcommand*{\memdskips}{}

\renewcommand*{\midsloppy}{}
\renewenvironment*{midsloppypar}{}{}

\renewcommand*{\sloppybottom}{}
```

§ 504.5 Titles

```
\csletcs{titlingpage*}{titlingpage}
\csletcs{endtitlingpage*}{endtitlingpage}
\let\titlingpageend\relax
\newcommand{\titlingpageend}[2]{}
\let\andnext\and
\renewcommand*{\thanksmarkstyle}[1]{}
\renewcommand{\thanksfootmark}{%
\thanksscript{\tamark}%
}

% \newlength{\thanksmarksep}
```

§ 504.6 Abstracts

```
\renewcommand*{\abstractcol}{}
\renewcommand*{\abstractintoc}{}
\renewcommand*{\abstractnum}{}
\renewcommand*{\abstractrunin}{}
```

§ 504.7 Docment divisions

```

\def\@apppage{%
```

```
    \part*{\appendixpagename}
}
\renewcommand\mempreaddapppagetotochook{}
\renewcommand\mempostaddapppagetotochook{}

\def\@sapppage{%
    \part*{\appendixpagename}
}

\csletcs{frontmatter*}{frontmatter}
\csletcs{mainmatter*}{mainmatter}
\renewcommand*{\raggedbottomsection}{}
\renewcommand*{\normalbottomsection}{}
\renewcommand*{\bottomsectionskip}{}
\renewcommand*{\bottomsectionpenalty}{}
\csletcs{appendixpage*}{appendixpage}
\renewcommand*{\namedsubappendices}{}
\renewcommand*{\unnamedsubappendices}{}
\renewcommand*{\setsecnumdepth}[1]{}% todo tocvsec2
\renewcommand*{\maxsecnumdepth}[1]{}% todo tocvsec2
\renewcommand*{\beforebookskip}{}
\renewcommand*{\afterbookskip}{}
\renewcommand*{\beforepartskip}{}
\renewcommand*{\afterpartskip}{}
\renewcommand*{\midbookskip}{}
\renewcommand*{\midpartskip}{}
\renewcommand*{\printbookname}{}
\renewcommand*{\booknamefont}{}
\renewcommand*{\booknamenum}{}
\renewcommand*{\printbooknum}{}
\renewcommand*{\booknumfont}{}
\renewcommand*{\printpartname}{}
\renewcommand*{\partnamefont}{}
\renewcommand*{\partnamenum}{}
\renewcommand*{\printpartnum}{}
\renewcommand*{\partnumfont}{}
\renewcommand*{\printbooktitle}[1]{}
\renewcommand*{\booktitlefont}{}
\renewcommand{\printparttitle}[1]{}
\renewcommand*{\parttitlefont}{}
\renewcommand*{\bookpageend}{}
\renewcommand*{\bookblankpage}{}
\renewcommand*{\nobookblankpage}{}
\renewcommand*{\partpageend}{}
\renewcommand*{\partblankpage}{}
\renewcommand*{\nopartblankpage}{}
\RenewDocumentCommand{\newleadpage}{s o m m}{}% todo
\RenewDocumentCommand{\renewleadpage}{s o m m}{}% todo
\renewcommand*{\leadpagetoclevel}{chapter}

\renewcommand*{\openright}{}
\renewcommand*{\openleft}{}
\renewcommand*{\openany}{}
\renewcommand*{\clearforchapter}{}
\renewcommand*{\memendofchapterhook}{}
```

```
\renewcommand*{\chapterheadstart}{}
% \newlength{\beforechapskip}
\renewcommand*{\afterchapternum}{}
% \newlength{\midchapskip}
\renewcommand*{\afterchaptertitle}{}
% \newlength{\afterchapskip}
\renewcommand*{\printchaptername}{}
\renewcommand*{\chapnamefont}{}
\renewcommand*{\chapternamenum}{}
\renewcommand*{\printchapternum}{}
\renewcommand*{\chapnumfont}{}
\renewcommand{\printchaptertitle}[1]{}
\renewcommand*{\chaptitlefont}{}
\renewcommand*{\printchapternonum}{}
\renewcommand*{\indentafterchapter}{}
\renewcommand*{\noindentafterchapter}{}
\renewcommand*{\insertchapterspace}{}

\renewcommand*{\chapterstyle}[1]{}
\renewcommand{\makechapterstyle}[2]{}
\renewcommand*{\chapindent}{}
\let\chapterprecis\cftchapterprecis
\let\chapterprecishere\cftchapterprecishere
\let\chapterprecistoc\cftchapterprecistoc
\renewcommand*{\precisfont}{}
\renewcommand*{\prechapterprecis}{}
\renewcommand*{\postchapterprecis}{}
\renewcommand{\precistoctext}[1]{}
\renewcommand*{\precistocfont}{}
\renewcommand*{\precistocformat}{}
% \newlength{\prechapterprecisshift}

\renewcommand*{\setbeforesecskip}[1]{}
\renewcommand*{\setaftersecskip}[1]{}
\renewcommand*{\setsecindent}[1]{}
\renewcommand*{\setsecheadstyle}[1]{}
\renewcommand*{\setbeforesubsecskip}[1]{}
\renewcommand*{\setaftersubsecskip}[1]{}
\renewcommand*{\setsubsecindent}[1]{}
\renewcommand*{\setsubsecheadstyle}[1]{}
\renewcommand*{\setbeforesubsubsecskip}[1]{}
\renewcommand*{\setaftersubsubsecskip}[1]{}
\renewcommand*{\setsubsubsecindent}[1]{}
\renewcommand*{\setsubsubsecheadstyle}[1]{}
\renewcommand*{\setbeforeparaskip}[1]{}
\renewcommand*{\setafterparaskip}[1]{}
\renewcommand*{\setparaindent}[1]{}
\renewcommand*{\setparaheadstyle}[1]{}
\renewcommand*{\setbeforesubparaskip}[1]{}
\renewcommand*{\setaftersubparaskip}[1]{}
\renewcommand*{\setsubparaindent}[1]{}
\renewcommand*{\setsubparaheadstyle}[1]{}
\renewcommand{\@hangfrom}[1]{#1}
\renewcommand{\sethangfrom}[1]{}
\renewcommand{\setsecnumformat}[1]{}
```

```
\renewcommand*{\hangsecnum}{}
\renewcommand*{\defaultsecnum}{}

\renewcommand*{\sechook}{}
\renewcommand{\setsechook}[1]{}
\renewcommand*{\subsechook}{}
\renewcommand{\setsubsechook}[1]{}
\renewcommand*{\subsubsechook}{}
\renewcommand{\setsubsubsechook}[1]{}
\renewcommand*{\parahook}{}
\renewcommand{\setparahook}[1]{}
\renewcommand*{\subparahook}{}
\renewcommand{\setsubparahook}[1]{}

\RenewDocumentCommand{\plainbreak}{s m}{\begin{center}~\end{center}}

\RenewDocumentCommand{\fancybreak}{s +m}{%
\begin{center}#2\end{center}%
}

\RenewDocumentCommand{\plainfancybreak}{s m m +m}{%
\begin{center}#4\end{center}%
}

\RenewDocumentCommand{\pfbreak}{s}{%
\begin{center}
\pfbreakdisplay
\end{center}
}

% \newlength{\pfbreakskip}
\renewcommand{\pfbreakdisplay}{*\quad*\quad*}

\renewcommand{\makeheadstyles}[2]{}
\renewcommand*{\headstyles}[1]{}
```

§ 504.8 Pagination and headers

```
\renewcommand*{\savepagenumber}{}
\renewcommand*{\restorepagenumber}{}
\renewcommand*{\uppercaseheads}{}
\renewcommand*{\nouppercaseheads}{}

\renewcommand*{\bookpagemark}[1]{}
\renewcommand*{\partmark}[1]{}
\renewcommand*{\bibmark}{}
\renewcommand*{\indexmark}{}
\renewcommand*{\glossarymark}{}

\LWR@origpagestyle{empty}
\renewcommand*{\ps@empty}{}
\renewcommand*{\makepagestyle}[1]{}
\renewcommand*{\emptypshook}{}%
% \renewcommand*{\empty@oddhead}{}
```

```
% \renewcommand*{\empty@oddfoot}{}
% \renewcommand*{\empty@evenhead}{}
% \renewcommand*{\empty@evenfoot}{}
\renewcommand*{\@oddhead}{}
\renewcommand*{\@oddfoot}{}
\renewcommand*{\@evenhead}{}
\renewcommand*{\@evenfoot}{}
\renewcommand*{\aliaspagestyle}[2]{}
\renewcommand*{\copypagestyle}[2]{}

\renewcommand*{\makeevenhead}[4]{}
\renewcommand*{\makeoddhead}[4]{}
\renewcommand*{\makeevenfoot}[4]{}
\renewcommand*{\makeoddfoot}[4]{}
\renewcommand*{\makerunningwidth}[3]{}
% \newlength{\headwidth}
\renewcommand*{\makeheadrule}[3]{}
\renewcommand*{\makefootrule}[3]{}
\renewcommand*{\makeheadfootruleprefix}[3]{}
% \newlength{\normalrulethickness}
% \setlength{\normalrulethickness}{.4pt}
% \newlength{\footruleheight}
% \newlength{\footruleskip}
\renewcommand*{\makeheadposition}[5]{}
\renewcommand{\makepsmarks}[2]{}
\renewcommand*{\makeheadfootstrut}[3]{}

\renewcommand{\createplainmark}[3]{}
\renewcommand{\memUChead}[1]{}
\renewcommand{\createmark}[5]{}
\renewcommand*{\clearplainmark}[1]{}
\renewcommand*{\clearmark}[1]{}
\renewcommand{\addtopsmarks}[3]{}
\renewcommand{\ifonlyfloats}[2]{#2}
\renewcommand*{\mergepagefloatstyle}[3]{}

\renewcommand*{\framepichead}{}
\renewcommand*{\framepictextfoot}{}
\renewcommand*{\framepichook}{}
\renewcommand*{\showheadfootlocoff}{}
\renewcommand*{\showtextblocklocoff}{}
```

§ 504.9 Paragraphs and lists

```
\renewcommand{\hangfrom}[1]{#1}
\let\centerfloat\centering
\renewcommand*{\raggedyright}[1][]{}
% \newlength{\ragrparindent}
\renewcommand{\sourceatright}[2][]{\attribution{#2}}
\let\memorigdbs\LWR@endofline
\let\memorigpar\par
\let\atcentercr\LWR@endofline

\renewcommand*{\linenottooshort}[1][]{}
\renewcommand*{\russianpar}{}
```

```
\renewcommand*{\lastlinerulefill}{}
\renewcommand*{\lastlineparrule}{}
\renewcommand*{\justlastraggedleft}{}
\renewcommand*{\raggedrightthenleft}{}
\renewcommand*{\leftcenterright}{}

\renewcommand{\leftspringright}[4]{%
\begin{minipage}{#1\linewidth}#3\end{minipage}\qquad%
\begin{minipage}{#2\linewidth}\begin{flushright}#4\end{flushright}\end{minipage}%
}

\renewenvironment*{blockdescription}
{\LWR@descriptionstart\LWR@origdescription}
{\enddescription}
\renewcommand*{\blockdescriptionlabel}[1]{\textbf{#1}}
\renewenvironment*{labelled}[1]{\begin{description}}{\end{description}}
\renewenvironment*{flexlabelled}[6]{\begin{description}}{\end{description}}
\renewcommand*{\tightlists}{}
\renewcommand*{\defaultlists}{}
\RenewDocumentCommand{\firmlists}{s}{}
\renewcommand*{\firmlist}{}
\renewcommand*{\tightlist}{}
\renewcommand*{\zerotrivseps}{}
\renewcommand*{\savetrivseps}{}
\renewcommand*{\restoretrivseps}{}
```

§ 504.10 Contents lists

```
\csletcs{tableofcontents*}{tableofcontents}
\csletcs{listoffigures*}{listoffigures}
\csletcs{listoftables*}{listoftables}
\renewenvironment{KeepFromToc}{}{}
\renewcommand*{\onecoltocetc}{}
\renewcommand*{\twocoltocetc}{}
\renewcommand*{\ensureonecol}{}
\renewcommand*{\restorefromonecol}{}
\renewcommand*{\doccoltocetc}{}
\renewcommand*{\maxtocdepth}[1]{}% tocvsec2
\renewcommand*{\settocdepth}[1]{}% tocvsec2

\renewcommand{\tocheadstart}{}
\renewcommand{\printtoctitle}[1]{}
\renewcommand{\tocmark}{}
\renewcommand{\aftertoctitle}{}
\renewcommand{\lofheadstart}{}
\renewcommand{\printloftitle}[1]{}
\renewcommand{\lofmark}{}
\renewcommand{\afterloftitle}{}
\renewcommand{\lotheadstart}{}
\renewcommand{\printlottitle}[1]{}
\renewcommand{\lotmark}{}
\renewcommand{\afterlottitle}{}

\renewcommand*{\setpnumwidth}[1]{}
\renewcommand*{\setrmarg}[1]{}
```

```
\renewcommand*{\cftbookbreak}{}
\renewcommand*{\cftpartbreak}{}
\renewcommand*{\cftchapterbreak}{}

% \newlength{\cftbeforebookskip}
% \newlength{\cftbookindent}
% \newlength{\cftbooknumwidth}
\renewcommand*{\cftbookfont}{}
\renewcommand*{\cftbookname}{}
\renewcommand*{\cftbookpresnum}{}
\renewcommand*{\cftbookaftersnum}{}
\renewcommand*{\cftbookaftersnumb}{}
\renewcommand*{\cftbookleader}{}
\renewcommand*{\cftbookdotsep}{1}
\renewcommand*{\cftbookpagefont}{}
\renewcommand*{\cftbookafterpnum}{}
\renewcommand*{\cftbookformatpnum}[1]{}
\renewcommand*{\cftbookformatpnumhook}[1]{}
```

Part is already defined by tocloft.

```
% \newlength{\cftbeforechapterskip}
% \newlength{\cftchapterindent}
% \newlength{\cftchapternumwidth}
\renewcommand*{\cftchapterfont}{}
\renewcommand*{\cftchaptername}{}
\renewcommand*{\cftchapterpresnum}{}
\renewcommand*{\cftchapteraftersnum}{}
\renewcommand*{\cftchapteraftersnumb}{}
\renewcommand*{\cftchapterleader}{}
\renewcommand*{\cftchapterdotsep}{1}
\renewcommand*{\cftchapterpagefont}{}
\renewcommand*{\cftchapterafterpnum}{}
\renewcommand*{\cftchapterformatpnum}[1]{}
\renewcommand*{\cftchapterformatpnumhook}[1]{}

% \newlength{\cftbeforesectionskip}
% \newlength{\cftsectionindent}
% \newlength{\cftsectionnumwidth}
\renewcommand*{\cftsectionfont}{}
\renewcommand*{\cftsectionname}{}
\renewcommand*{\cftsectionpresnum}{}
\renewcommand*{\cftsectionaftersnum}{}
\renewcommand*{\cftsectionaftersnumb}{}
\renewcommand*{\cftsectionleader}{}
\renewcommand*{\cftsectiondotsep}{1}
\renewcommand*{\cftsectionpagefont}{}
\renewcommand*{\cftsectionafterpnum}{}
\renewcommand*{\cftsectionformatpnum}[1]{}
\renewcommand*{\cftsectionformatpnumhook}[1]{}

% \newlength{\cftbeforesubsectionskip}
% \newlength{\cftsubsectionindent}
% \newlength{\cftsubsectionnumwidth}
\renewcommand*{\cftsubsectionfont}{}
\renewcommand*{\cftsubsectionname}{}
```

```
\renewcommand*{\cftsubsectionpresnum}{}
\renewcommand*{\cftsubsectionaftersnum}{}
\renewcommand*{\cftsubsectionaftersnumb}{}
\renewcommand*{\cftsubsectionleader}{}
\renewcommand*{\cftsubsectiondotsep}{1}
\renewcommand*{\cftsubsectionpagefont}{}
\renewcommand*{\cftsubsectionafterpnum}{}
\renewcommand*{\cftsubsectionformatpnum}[1]{}
\renewcommand*{\cftsubsectionformatpnumhook}[1]{}

% \newlength{\cftbeforesubsubsectionskip}
% \newlength{\cftsubsubsectionindent}
% \newlength{\cftsubsubsectionnumwidth}
\renewcommand*{\cftsubsubsectionfont}{}
\renewcommand*{\cftsubsubsectionname}{}
\renewcommand*{\cftsubsubsectionpresnum}{}
\renewcommand*{\cftsubsubsectionaftersnum}{}
\renewcommand*{\cftsubsubsectionaftersnumb}{}
\renewcommand*{\cftsubsubsectionleader}{}
\renewcommand*{\cftsubsubsectiondotsep}{1}
\renewcommand*{\cftsubsubsectionpagefont}{}
\renewcommand*{\cftsubsubsectionafterpnum}{}
\renewcommand*{\cftsubsubsectionformatpnum}[1]{}
\renewcommand*{\cftsubsubsectionformatpnumhook}[1]{}

% \newlength{\cftbeforeparagraphskip}
% \newlength{\cftparagraphindent}
% \newlength{\cftparagraphnumwidth}
\renewcommand*{\cftparagraphfont}{}
\renewcommand*{\cftparagraphname}{}
\renewcommand*{\cftparagraphpresnum}{}
\renewcommand*{\cftparagraphaftersnum}{}
\renewcommand*{\cftparagraphaftersnumb}{}
\renewcommand*{\cftparagraphleader}{}
\renewcommand*{\cftparagraphdotsep}{1}
\renewcommand*{\cftparagraphpagefont}{}
\renewcommand*{\cftparagraphafterpnum}{}
\renewcommand*{\cftparagraphformatpnum}[1]{}
\renewcommand*{\cftparagraphformatpnumhook}[1]{}

% \newlength{\cftbeforesubparagraphskip}
% \newlength{\cftsubparagraphindent}
% \newlength{\cftsubparagraphnumwidth}
\renewcommand*{\cftsubparagraphfont}{}
\renewcommand*{\cftsubparagraphname}{}
\renewcommand*{\cftsubparagraphpresnum}{}
\renewcommand*{\cftsubparagraphaftersnum}{}
\renewcommand*{\cftsubparagraphaftersnumb}{}
\renewcommand*{\cftsubparagraphleader}{}
\renewcommand*{\cftsubparagraphdotsep}{1}
\renewcommand*{\cftsubparagraphpagefont}{}
\renewcommand*{\cftsubparagraphafterpnum}{}
\renewcommand*{\cftsubparagraphformatpnum}[1]{}
\renewcommand*{\cftsubparagraphformatpnumhook}[1]{}

% \newlength{\cftbeforefigureskip}
```

```
% \newlength{\cftfigureindent}
% \newlength{\cftfigurenumwidth}
\renewcommand*{\cftfigurefont}{}
\renewcommand*{\cftfigurename}{}
\renewcommand*{\cftfigurepresnum}{}
\renewcommand*{\cftfigureaftersnum}{}
\renewcommand*{\cftfigureaftersnumb}{}
\renewcommand*{\cftfigureleader}{}
\renewcommand*{\cftfiguredotsep}{1}
\renewcommand*{\cftfigurepagefont}{}
\renewcommand*{\cftfigureafterpnum}{}
\renewcommand*{\cftfigureformatpnum}[1]{}
\renewcommand*{\cftfigureformatpnumhook}[1]{}

% \newlength{\cftbeforesubfigureskip}
% \newlength{\cftsubfigureindent}
% \newlength{\cftsubfigurenumwidth}
\newcommand*{\cftsubfigurefont}{}
\newcommand*{\cftsubfigurename}{}
\newcommand*{\cftsubfigurepresnum}{}
\newcommand*{\cftsubfigureaftersnum}{}
\newcommand*{\cftsubfigureaftersnumb}{}
\newcommand*{\cftsubfigureleader}{}
\newcommand*{\cftsubfiguredotsep}{1}
\newcommand*{\cftsubfigurepagefont}{}
\newcommand*{\cftsubfigureafterpnum}{}
\newcommand*{\cftsubfigureformatpnum}[1]{}
\newcommand*{\cftsubfigureformatpnumhook}[1]{}

% \newlength{\cftbeforetableskip}
% \newlength{\cfttableindent}
% \newlength{\cfttablenumwidth}
\renewcommand*{\cfttablefont}{}
\renewcommand*{\cfttablename}{}
\renewcommand*{\cfttablepresnum}{}
\renewcommand*{\cfttableaftersnum}{}
\renewcommand*{\cfttableaftersnumb}{}
\renewcommand*{\cfttableleader}{}
\renewcommand*{\cfttabledotsep}{1}
\renewcommand*{\cfttablepagefont}{}
\renewcommand*{\cfttableafterpnum}{}
\renewcommand*{\cfttableformatpnum}[1]{}
\renewcommand*{\cfttableformatpnumhook}[1]{}

% \newlength{\cftbeforesubtableskip}
% \newlength{\cftsubtableindent}
% \newlength{\cftsubtablenumwidth}
\newcommand*{\cftsubtablefont}{}
\newcommand*{\cftsubtablename}{}
\newcommand*{\cftsubtablepresnum}{}
\newcommand*{\cftsubtableaftersnum}{}
\newcommand*{\cftsubtableaftersnumb}{}
\newcommand*{\cftsubtableleader}{}
\newcommand*{\cftsubtabledotsep}{1}
\newcommand*{\cftsubtablepagefont}{}
\newcommand*{\cftsubtableafterpnum}{}
```

```
\newcommand*{\cftsubtableformatpnum}[1]{}
\newcommand*{\cftsubtableformatpnumhook}[1]{}

\renewcommand*{\booknumberline}[1]{}
\renewcommand*{\partnumberline}[1]{}
\renewcommand*{\chapternumberline}[1]{}
\renewcommand*{\numberlinehook}[1]{}
% \renewcommand*{\cftwhatismyname}{}%
\renewcommand*{\booknumberlinehook}[1]{}
\renewcommand*{\partnumberlinehook}[1]{}
\renewcommand*{\chapternumberlinehook}[1]{}
\renewcommand{\numberlinebox}[2]{}
\renewcommand{\booknumberlinebox}[2]{}
\renewcommand{\partnumberlinebox}[2]{}
\renewcommand{\chapternumberlinebox}[2]{}
%
% \newlength{\cftparfillskip}
\renewcommand*{\cftpagenumbersoff}[1]{}
\renewcommand*{\cftpagenumberson}[1]{}
\renewcommand*{\cftlocalchange}[3]{}
\renewcommand*{\cftaddtitleline}[4]{}
\renewcommand*{\cftaddnumtitleline}[4]{}
\renewcommand{\cftinsertcode}[2]{}
\renewcommand{\cftinserthook}[2]{}
\renewcommand{\settocpreprocessor}[2]{}
\DeclareRobustCommand{\cftpagenumbersoff}[1]{}
\DeclareRobustCommand{\cftpagenumberson}[1]{}
```

§ 504.11 Floats and captions

`\newfloat` `[`⟨*1: within*⟩`]` {⟨*2: type*⟩} {⟨*3: ext*⟩} {⟨*4: capname*⟩}

```
\RenewDocumentCommand{\newfloat}{o m m m}{%
\IfValueTF{#1}%
{\DeclareFloatingEnvironment[fileext=#3,within=#1,name={#4}]{#2}}%
{\DeclareFloatingEnvironment[fileext=#3,name={#4}]{#2}}%
```

newfloat package automatically creates the `\listof` command for new floats, but float does not, so remove `\listof` here in case it is manually created later.

```
\cslet{listof#2s}\relax%
\cslet{listof#2es}\relax%
}
```

`\newlistof` `[`⟨*within*⟩`]` {⟨*type*⟩} {⟨*ext*⟩} {⟨*listofname*⟩}

Emulated through the `\newfloat` mechanism. Note that memoir uses a different syntax than tocloft for the name.

```
\RenewDocumentCommand{\newlistof}{o m m m}
{%
\IfValueTF{#1}
{\newlistentry[#1]{#2}{#3}{0}}
{\newlistentry{#2}{#3}{0}}
\@namedef{ext@#2}{#3}%
\@ifundefined{c@#3depth}{\newcounter{#3depth}}{}%
\setcounter{#3depth}{1}%
```

```
\@namedef{#3mark}{}%
\@namedef{#2}{\listof{#2}{#4}}
\@namedef{@cftmake#3title}{}
\@ifundefined{cftbefore#3titleskip}{
    \expandafter\newlength\csname cftbefore#3titleskip\endcsname
    \expandafter\newlength\csname cftafter#3titleskip\endcsname
}{}
\@namedef{cft#3titlefont}{}
\@namedef{cftafter#3title}{}
\@namedef{cft#3prehook}{}
\@namedef{cft#3posthook}{}
}

\renewcommand{\setfloatadjustment}[2]{}
```

Borrowed from the lwarp version of keyfloat:

```
\NewDocumentEnvironment{KFLTmemoir@marginfloat}{O{-1.2ex} m}
{% start
\LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}{marginblock}%
\captionsetup{type=#2}%
}
{%
\endLWR@BlockClassWP%
}

\DeclareDocumentEnvironment{marginfigure}{o}
  {\begin{KFLTmemoir@marginfloat}{figure}}
  {\end{KFLTmemoir@marginfloat}}

\DeclareDocumentEnvironment{margintable}{o}
  {\begin{KFLTmemoir@marginfloat}{table}}
  {\end{KFLTmemoir@marginfloat}}

\renewcommand{\setmarginfloatcaptionadjustment}[2]{}
\renewcommand{\setmpjustification}[2]{}
\renewcommand*{\mpjustification}{}
\renewcommand*{\setfloatlocations}[2]{}
\DeclareDocumentCommand{\suppressfloats}{o}{}
\renewcommand*{\FloatBlock}{}
\renewcommand*{\FloatBlockAllowAbove}{}
\renewcommand*{\FloatBlockAllowBelow}{}
\renewcommand*{\setFloatBlockFor}{}

\renewcommand{\captiontitlefinal}[1]{}

\renewcommand{\flegtable}{\tablename}
\renewcommand{\flegfigure}{\figurename}
\renewcommand{\flegtoctable}{}
\renewcommand{\flegtocfigure}{}


\renewcommand{\subcaption}[2][]{%
\ifblank{#1}{\subfloat[#2]{}}{\subfloat[#1][#2]{}}%
}
```

```
\renewcommand{\contsubcaption}{\ContinuedFloat\subcaption}

\LetLtxMacro\subcaptionref\subref

\renewcommand*{\tightsubcaptions}{}
\renewcommand*{\loosesubcaptions}{}

\renewcommand*{\subcaptionsize}[1]{}
\renewcommand*{\subcaptionlabelfont}[1]{}
\renewcommand*{\subcaptionfont}[1]{}
\renewcommand*{\subcaptionstyle}[1]{}

\renewcommand*{\hangsubcaption}{}
\renewcommand*{\shortsubcaption}{}
\renewcommand*{\normalsubcaption}{}

\RenewDocumentEnvironment{sidecaption}{o m o}
{}
{
\IfValueTF{#1}{\caption[#1]{#2}}{\caption{#2}}%
\IfValueT{#3}{\label{#3}}%
}

% \newlength{\sidecapwidth}
% \newlength{\sidecapsep}
\renewcommand*{\setsidecaps}[2]{}
\renewcommand*{\sidecapmargin}[1]{}
% \newif\ifscapmargleft
\scapmargleftfalse
\renewcommand*{\setsidecappos}[1]{}

\RenewDocumentEnvironment{sidecontcaption}{m o}
{}
{%
\ContinuedFloat%
\caption{#1}%
```

Without `\@captype`, the section is referred to instead.

```
\IfValueT{#2}{\label[\@captype]{#2}}%
}
```

`\sidenamedlegend` does not appear to use the TOC argument.

```
\renewenvironment{sidenamedlegend}[2][]{
\begin{center}
\@nameuse{\@captype name}\CaptionSeparator#2
\end{center}
}
{}

\renewenvironment{sidelegend}[1]
{\begin{center}
#1
```

```
788
789 }
790 {\end{center}}
791
792 \renewcommand*{\sidecapstyle}{}
793 \renewcommand*{\overridescapmargin}[1]{}
794 % \newlength{\sidecapraise}
795 \renewcommand*{\sidecapfloatwidth}{\linewidth}
796
797 \LetLtxMacro\ctabular\tabular
798 \LetLtxMacro\endctabular\endtabular
799
800 \renewcommand{\autorows}[5][]{%
801 #5
802 }
803
804 \renewcommand{\autocols}[5][]{%
805 #5
806 }
```

§ 504.12 Page notes

```
807 \renewcommand*{\feetabovefloat}{}
808 \renewcommand*{\feetbelowfloat}{}
809 \renewcommand*{\feetatbottom}{}
810
811 \renewcommand*{\verbfootnote}[2][]{
812 \PackageError{lwarp,memoir}
813 {Verbatim footnotes are not yet supported by lwarp.}
814 {This may be improved some day.}
815 }
816
817 \renewcommand*{\plainfootnotes}{}
818 \renewcommand*{\twocolumnfootnotes}{}
819 \renewcommand*{\threecolumnfootnotes}{}
820 \renewcommand*{\paragraphfootnotes}{}
821 \renewcommand*{\footfudgefiddle}{}
822
823 \renewcommand*{\newfootnoteseries}[1]{
824 \PackageError{lwarp,memoir}
825 {Memoir footnote series are not yet supported by lwarp.}
826 {This may be improved some day.}
827 }
828
829 \renewcommand*{\plainfootstyle}[1]{}
830 \renewcommand*{\twocolumnfootstyle}[1]{}
831 \renewcommand*{\threecolumnfootstyle}[1]{}
832 \renewcommand*{\paragraphfootstyle}[1]{}
833
834 \renewcommand*{\footfootmark}{}
835 \renewcommand*{\footmarkstyle}[1]{}
836
837 % \newlength{\footmarkwidth}
838 % \newlength{\footmarksep}
839 % \newlength{\footparindent}
```

```
\renewcommand*{\foottextfont}{}

\renewcommand*{\marginparmargin}[1]{}
\renewcommand*{\sideparmargin}[1]{}

\LetLtxMacro\sidepar\marginpar
\renewcommand*{\sideparfont}{}
\renewcommand*{\sideparform}{}
\LWR@providelength{\sideparvshift}

\renewcommand*{\parnopar}{}

\renewcommand{\sidebar}[1]{\begin{quote}#1\end{quote}}
\renewcommand*{\sidebarmargin}[1]{}
\renewcommand*{\sidebarfont}{}
\renewcommand*{\sidebarform}{}
% \newlength{\sidebarhsep}
% \newlength{\sidebarvsep}
% \newlength{\sidebarwidth}
% \newlength{\sidebartopsep}
\renewcommand{\setsidebarheight}[1]{}
\renewcommand*{\setsidebars}[6]{}
\renewcommand*{\footnotesatfoot}{}
\renewcommand*{\footnotesinmargin}{}

\LetLtxMacro\sidefootnote\footnote
\LetLtxMacro\sidefootnotemark\footnotemark
\LetLtxMacro\sidefootnotetext\footnotetext

\renewcommand*{\sidefootmargin}[1]{}
% \newlength{\sidefoothsep}
% \newlength{\sidefootvsep}
% \newlength{\sidefootwidth}
% \newlength{\sidefootadjust}
% \newlength{\sidefootheight}
\renewcommand*{\setsidefootheight}[1]{}
% \renewcommand*{\sidefootfont}{}% in docs but not in the package
\renewcommand*{\setsidefeet}[6]{}
\renewcommand*{\sidefootmarkstyle}[1]{}
\renewcommand*{\sidefoottextfont}{}
\renewcommand*{\sidefootform}{}

\renewcommand*{\continuousnotenums}{\pncontopttrue}% from pagenote
\renewcommand*{\notepageref}{}
\renewcommand*{\prenotetext}{}
\renewcommand*{\postnotetext}{}
\renewcommand*{\idtextinnotes}[1]{}
\renewcommand*{\printpageinnotes}[1]{}
\renewcommand*{\printpageinnoteshyperref}[1]{}
\renewcommand*{\foottopagenote}{}
\renewcommand*{\pagetofootnote}{}
```

§ 504.13 Decorative text

```
\renewcommand*{\epigraphposition}[1]{}
\renewcommand*{\epigraphtextposition}[1]{}
\renewcommand*{\epigraphsourceposition}[1]{}
\renewcommand*{\epigraphfontsize}[1]{}
\renewcommand*{\epigraphforheader}[2][]{}
\renewcommand*{\epigraphpicture}{}
```

§ 504.14 Poetry

```
\renewcommand*{\vinphantom}{}
\renewcommand*{\vleftofline}[1]{#1}
% \let\linenumberfrequency\poemlines
% \renewcommand*{\linenumberfont}[1]{}

\DeclareDocumentCommand{\PoemTitle}{s o o m}{%
\IfValueTF{#2}%
{\poemtitle[#2]{#4}}%
{\poemtitle{#4}}%
}

\renewcommand*{\NumberPoemTitle}{}
\renewcommand*{\PlainPoemTitle}{}
\renewcommand*{\poemtitlepstyle}{}
\renewcommand*{\poemtitlestarmark}[1]{}
\renewcommand*{\poemtitlestarpstyle}{}
\renewcommand*{\PoemTitleheadstart}{}
\renewcommand*{\printPoemTitlenonum}{}
\renewcommand*{\printPoemTitlenum}{}
\renewcommand*{\afterPoemTitlenum}{}
\renewcommand*{\printPoemTitletitle}[1]{}
\renewcommand*{\afterPoemTitle}{}
\newlength{\midpoemtitleskip}
\renewcommand*{\PoemTitlenumfont}{}
\renewcommand*{\PoemTitlefont}{}
```

§ 504.15 Boxes, verbatims and files

```
\renewenvironment{qframe}{\framed}{\endframed}
\renewenvironment{qshade}{\shaded}{\endshaded}
```

Use the comment package:

```
\renewcommand*{\commentsoff}[1]{\includecomment{#1}}
\renewcommand*{\commentson}[1]{\excludecomment{#1}}
\LetLtxMacro\renewcomment\commentson

\renewcommand*{\setverbatimfont}[1]{}
\renewcommand*{\tabson}[1]{}
\renewcommand*{\tabsoff}{}
\renewcommand*{\wrappingon}{}
\renewcommand*{\wrappingoff}{}
\renewcommand*{\verbatimindent}{}
\renewcommand*{\verbatimbreakchar}[1]{}

\DefineVerbatimEnvironment{fboxverbatim}{Verbatim}{frame=single}
```

boxedverbatim is already defined by moreverb. boxedverbatim* does not appear to work at all, even in a minimal print memoir document.

```
\renewcommand*{\bvbox}{}
\renewcommand*{\bvtopandtail}{}
\renewcommand*{\bvsides}{}
\renewcommand*{\nobvbox}{}
% \newlength\bvboxsep
\renewcommand*{\bvtoprulehook}{}
\renewcommand*{\bvtopmidhook}{}
\renewcommand*{\bvendrulehook}{}
\renewcommand*{\bvleftsidehook}{}
\renewcommand*{\bvrightsidehook}{}
\renewcommand*{\bvperpagetrue}{}
\renewcommand*{\bvperpagefalse}{}
\renewcommand{\bvtopofpage}[1]{}
\renewcommand{\bvendofpage}[1]{}
\renewcommand*{\linenumberfrequency}[1]{}
\renewcommand*{\resetbvlinenumber}{}
\renewcommand*{\setbvlinenums}[2]{}
\renewcommand*{\linenumberfont}[1]{}
\renewcommand*{\bvnumbersinside}{}
\renewcommand*{\bvnumbersoutside}{}
```

§ 504.16 Cross referencing

```
\renewcommand*{\fref}[1]{\cref{#1}}
\renewcommand*{\tref}[1]{\cref{#1}}
\renewcommand*{\pref}[1]{\cpageref{#1}}
\renewcommand*{\Aref}[1]{\cref{#1}}
\renewcommand*{\Bref}[1]{\cref{#1}}
\renewcommand*{\Pref}[1]{\cref{#1}}
\renewcommand*{\Sref}[1]{\cref{#1}}
\renewcommand*{\figurerefname}{Figure}
\renewcommand*{\tablerefname}{Table}
\renewcommand*{\pagerefname}{page}
\renewcommand*{\bookrefname}{Book~}
\renewcommand*{\partrefname}{Part~}
\renewcommand*{\chapterrefname}{Chapter~}
\renewcommand*{\sectionrefname}{\S}
\renewcommand*{\appendixrefname}{Appendix~}
\LetLtxMacro\titleref\nameref
\renewcommand*{\headnameref}{}
\renewcommand*{\tocnameref}{}

\providecounter{LWR@currenttitle}

\renewcommand*{\currenttitle}{%
    \addtocounter{LWR@currenttitle}{1}%
    \label{currenttitle\arabic{LWR@currenttitle}}%
    \nameref{currenttitle\arabic{LWR@currenttitle}}%
}

\renewcommand*{\theTitleReference}[2]{}
\renewcommand*{\namerefon}{}
```

```
\renewcommand*{\namerefoff}{}
```

§ 504.17 Back matter

Redefined to write the LWR@autoindex counter instead of page. Note that memoir has two versions, depending on the use of hyperref.

```
\AtBeginDocument{

\def\@@wrindexhyp#1||\\{%
    \addtocounter{LWR@autoindex}{1}%
    \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
%     \ifshowindexmark\@showidx{#1}\fi
    \protected@write\@auxout{}%
    {\string\@@wrindexm@m{\@idxfile}{#1}{\arabic{LWR@autoindex}}}%
    \endgroup
    \@esphack}%
```

\specialindex behaves like a regular \index, pointing to where \specialindex is used. If \specialindex is used inside a figure or table after the \caption, then the hyperlink will be given the name of that particular figure or table.

```
\def\@@wrspindexhyp#1||\\{%
    \addtocounter{LWR@autoindex}{1}%
    \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
%     \ifshowindexmark\@showidx{#1}\fi
    \protected@write\@auxout{}%
    {%
%         \string\@@wrindexm@m{\@idxfile}{#1}{\@nameuse{the\@sptheidx}}%
        \string\@@wrindexm@m{\@idxfile}{#1}{\arabic{LWR@autoindex}}%
    }%
    \endgroup
    \@esphack}%

}% \AtBeginDocument
```

Patched to use _html filename and \BaseJobname:

```
\catcode`\_=12%
\renewcommand*{\makeindex}[1][\BaseJobname]{%
  \if@filesw
    \def\gindex{\@bsphack%
      \@ifnextchar [{\@index}{\@index[\BaseJobname]}}
    \def\specialindex{\@bsphack\@spindex}%
    \makememindexhook
    \expandafter\newwrite\csname #1@idxfile\endcsname
   \expandafter\immediate\openout \csname #1@idxfile\endcsname #1_html.idx\relax
    \typeout{Writing index file #1_html.idx }%
  \fi}
\catcode`\_=8%
```

Patched to use _html filename and \BaseJobname. This will later be patched by the lwarp core.

```
\catcode`\_=12%
\renewcommand{\printindex}[1][\BaseJobname]{\@input@{#1_html.ind}}
\catcode`\_=8%

\DeclareDocumentCommand{\newblock}{}{}
%
\renewcommand*{\showindexmarks}{}
\renewcommand*{\hideindexmarks}{}

\renewcommand*{\xindyindex}{}
```

§ 504.18 Miscellaneous

```
\renewcommand*{\changemarks}{}
\renewcommand*{\nochangemarks}{}
\renewcommand*{\added}[1]{}
\renewcommand*{\deleted}[1]{}
\renewcommand*{\changed}[1]{}

\renewcommand*{\showtrimsoff}{}
\renewcommand*{\showtrimson}{}
\renewcommand*{\trimXmarks}{}
\renewcommand*{\trimLmarks}{}
\renewcommand*{\trimFrame}{}
\renewcommand*{\trimNone}{}
\renewcommand*\trimmarkscolor{}
\renewcommand*{\trimmarks}{}
\renewcommand*{\tmarktl}{}
\renewcommand*{\tmarktr}{}
\renewcommand*{\tmarkbr}{}
\renewcommand*{\tmarkbl}{}
\renewcommand*{\tmarktm}{}
\renewcommand*{\tmarkmr}{}
\renewcommand*{\tmarkbm}{}
\renewcommand*{\tmarkml}{}
\renewcommand*{\trimmark}{}
\renewcommand*{\quarkmarks}{}
\renewcommand*{\registrationColour}[1]{}

\renewcommand*{\leavespergathering}[1]{}

\renewcommand*{\noprelistbreak}{}

\renewcommand*{\cleartorecto}{}
\renewcommand*{\cleartoverso}{}

\renewenvironment{vplace}[1][]{}{}
```

§ 504.19 ccaption emulation

```
\renewcommand*{\captiondelim}[1]{\renewcommand*{\CaptionSeparator}{#1}}
\renewcommand*{\captionnamefont}[1]{}
\renewcommand*{\captiontitlefont}[1]{}
\renewcommand*{\flushleftright}{}
\renewcommand*{\centerlastline}{}
```

```
\renewcommand*{\captionstyle}[2][]{}
\DeclareDocumentCommand{\captionwidth}{m}{}
\renewcommand*{\changecaptionwidth}{}
\renewcommand*{\normalcaptionwidth}{}
\renewcommand*{\hangcaption}{}
\renewcommand*{\indentcaption}[1]{}
\renewcommand*{\normalcaption}{}
\renewcommand{\precaption}[1]{}
\renewcommand{\postcaption}[1]{}
\renewcommand{\midbicaption}[1]{}
\renewcommand{\contcaption}[1]{%
% \ContinuedFloat%
% \caption{#1}%
\begin{LWR@figcaption}% later becomes \caption*
\LWR@isolate{\@nameuse{\@captype name}}~%
\thechapter.\the\value{\@captype}\CaptionSeparator\LWR@isolate{#1}%
\end{LWR@figcaption}
}

\newlength{\abovelegendskip}
\setlength{\abovelegendskip}{0.5\baselineskip}
\newlength{\belowlegendskip}
\setlength{\belowlegendskip}{\abovelegendskip}
```

The extra \\ here forces a <br> in HTML when \legend is used in a \marginpar.

```
\renewcommand{\legend}[1]{\begin{center}#1\\\end{center}}

\renewcommand{\namedlegend}[2][]{
\begin{center}
\@nameuse{fleg\@captype}\CaptionSeparator#2\\
\end{center}
\@nameuse{flegtoc\@captype}{#1}
}

\renewcommand{\newfixedcaption}[3][\caption]{%
  \renewcommand{#2}{\def\@captype{#3}#1}}
\renewcommand{\renewfixedcaption}[3][\caption]{%
  \renewcommand{#2}{\def\@captype{#3}#1}}
\renewcommand{\providefixedcaption}[3][\caption]{%
  \providecommand{#2}{\def\@captype{#3}#1}}

\renewcommand{\bitwonumcaption}[6][]{%
\ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
\addtocounter{\@captype}{-1}%
\begingroup%
\csdef{\@captype name}{#4}%
\ifblank{#5}{\caption{#6}}{\caption[#5]{#6}}%
\endgroup%
\ifblank{#1}{}{\label{#1}}%
}

\LetLtxMacro\bionenumcaption\bitwonumcaption% todo

\renewcommand{\bicaption}[5][]{%
\ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
```

```
\begin{LWR@figcaption}% later becomes \caption*
\LWR@isolate{#4} \thechapter.\the\value{\@captype}\CaptionSeparator\LWR@isolate{#5}%
\end{LWR@figcaption}
\ifblank{#1}{}{\label{#1}}%
}

\renewcommand{\bicontcaption}[3]{%
\contcaption{#1}%
\begingroup%
\csdef{\@captype name}{#2}%
\contcaption{#3}%
\endgroup%
}

% only in ccaption, not in memoir:
% \LetLtxMacro\longbitwonumcaption\bitwonumcaption%
% \LetLtxMacro\longbionenumcaption\bitwonumcaption%
% \LetLtxMacro\longbicaption\bicaption%

\RenewDocumentCommand{\subtop}{O{} O{} m}{%
\subfloat[#1][#2]{#3}%
}

\RenewDocumentCommand{\subbottom}{O{} O{} m}{%
\subfloat[#1][#2]{#3}%
}

\renewcommand{\contsubtop}{%
\ContinuedFloat\addtocounter{\@captype}{1}%
\subtop}

\renewcommand{\contsubbottom}{%
\ContinuedFloat\addtocounter{\@captype}{1}%
\subbottom}

\renewcommand{\subconcluded}{}

\let\subfigure\subbottom
\let\subtable\subtop

\let\contsubtable\contsubtop
\let\contsubfigure\contsubbottom

\newcommand{\newfloatentry}[4][\@empty]{TODO: newfloatentry}
\newcommand{\newfloatlist}[5][\@empty]{TODO: newfloatlist}
\newcommand{\newfloatenv}[4][\@empty]{TODO: newfloatenv}
\DeclareRobustCommand{\newfloatpagesoff}[1]{}
\DeclareRobustCommand{\newfloatpageson}[1]{}
\newcommand{\setnewfloatindents}[3]{}
```

§ 504.20 Final patchwork

```
\newlistof{tableofcontents}{toc}{\contentsname}
\newlistof{listoffigures}{lof}{\listfigurename}
\newlistof{listoftables}{lot}{\listtablename}
```

Change History

§ 505 ## Chg Hist

For the most recent changes, see page 1016.

v0.10
General: 2016/03/08 Initial version . . 1
v0.11
General: 2016/03/11 1
Added section: Operating-System portability. 209
Added section: Selecting the operating system. 120
Test Suite: MS-WINDOWS in README.txt 1
Test Suite: limages and index in README.txt 1
v0.12
\LWR@newhtmlfile: Bugfix: TOC with numbered files. 352
General: 2016/03/14 1
Global: Uses \p@(type) in float captions. 1
Test Suite: Sub-figures 1
v0.13
\CaptionSeparator: Fix for newer babel package. 471
\LWR@LwarpStart: \up and \fup . . . 371
General: 2016/03/24 1
Fix dollar-redefined bug for newer package. 900
Removed package: subfig 1
Test Suite: Ordinals, Subcaption . . . 1
v0.14
\LWR@htmlsectionfilename: Fix: Links to home page. 315
General: 2016/03/31 1
floatrow: Added. 699
Docs: Commands for a successful HTML conversion. 123
Docs: Commands into a warpprint environment. 121
Docs: Newclude limitations. . . . 166
Docs: Table: Cross-referencing data structures. 456
Docs: Table: Float data structures. 467
Docs: Trademarks section. 190
Docs: Troubleshooting cross-references. 185
Test Suite: Assigned cleveref name for Test Float. 1
Test Suite: Floatrow 1
v0.15
General: 2016/04/06 1
Added. 704
Ampersand (&): Fixed handling when passed as an argument. . . 404
Docs: Added warning icons for items needing special attention. 193
Docs: Clarify print/HTML output. 120
Docs: Moved the supported features table to the introduction. 76
Files: lwarp_formal.css added. 1
Fix: steps counter 703
Fixed & handling. 702
Test Suite: test_suite_formal.css file added. 1
v0.16
General: 2016/04/11 1
\titlingpage: Improved print-output spacing. 378
xfrac: Adjusted for the use of any font: 954
Added XeLaTeX, LuaLaTeX support. 194
Docs: Font and UTF-8 support. . 107
Docs: Moved location of \usepackage{lwarp}. 109
Docs: Text not converting. 185
Lwarp no longer selects fonts. 107, 218
Removed package: suffix 1
Test Suite: Improved titlingpage. 378
Test Suite: Lwarp no longer selects fonts. 1
Test Suite: Supports XeLaTeX, LuaLaTeX. 1
v0.17
\LWR@htmlsectionfilename: Fix: Links when entire doc is one HTML page. 315
General: 2016/04/14 1
mdframed: Added. 781

Test Suite: Fix: Print-version front-matter page numbers. 1
Test Suite: Mdframed 1
v0.18
\LWR@includegraphicsb: Add: svgz file extension. 725
em, ex, %, px dimensions preserved. 725
Fix: \linewidth, \textwidth, \textheight inside a minipage. 725
Improved HTML output linebreaks. 725
\LWR@myshorttoc: Reorganize \HomeHTMLFilename logic. 475
\LWR@newhtmlfile: sideTOC after title, improving responsive design. . . 351
\LWR@requesttoc: Reorganize \HomeHTMLFilename logic. 373
\LWR@subhyperref: Improved HTML output linebreaks. 463
\LWR@subhyperrefclass: Improved HTML output linebreaks. 464
\LWR@subinlineimage: Suppress extra space. 465
\hspace: \hspace supported. 561
General: 2016/05/19 1
File: lwarp.css: Improved TOC outline display. 1
Files: lwarp.css and lwarp_formal.css: Improved responsive design. 1
Microtype disabled during HTML generation 219
PDF Unicode input characters. . 207
Test Suite: Verse package 1
lateximage: pdfcrop: --hires added. 519
Reorganize \HomeHTMLFilename logic. 519
Suppress extra space. 519
verse: Supports verse, memoir packages. 934
minipage: Fix: \linewidth, \textwidth, \textheight inside a minipage. 539
v0.19
\HTMLFilename: Docs: Escape filename underscores. 314
\HomeHTMLFilename: Docs: Escape filename underscores. 314
\LWR@LwarpStart: Enabled \\ equal to \newline. 370
\LWR@doequation: MathJax support. 505
\LWR@doubledollar: MathJax support. 500
\LWR@filestart: lwarp_mathjax.txt loaded. 367
\LWR@minipagestartpars: Suppresses paragraph tags between minipages. 559
\LWR@subsingledollar: MathJax support. 494
\LateximageFontSizeName: Add: User-adjustable math/lateximage font size. 515
\hspace: Fix: \hspace length computations. 561
\minipagefullwidth: Added: No width tag for the next minipage in HTML. 538
\warpHTMLonly: Added. 217
\warpprintonly: Replaces \rowprintedonly. 217
\xfracHTMLfontsize: Added. 954
General: 2016/06/08 1
CSS for table note item. 898
MathJax support added. 503, 509, 510
multirow: Added optional args. . 798
Adapts to tikz version. 900
Avoids MathJax. 493
cleveref: Loaded \AtEndPreamble. 534
Docs: Math options. 109
Docs: Table: Cross-referencing data structures, updated. 456
File: lwarp.css: tnoteitemheader added. 1
File: lwarp_mathjax.txt added. . . 1
Introduction: MathJax support mentioned. 73
Options: mathsvg and mathjax . 212
Supports colored \rule. 945
titleps: null \pagestyle and \thispagestyle for HTML. . . . 901
v0.20
\BlockClassSingle: Renamed from "LWR@htmldivclassline". 327
\HTMLDescription: Added \NewHTMLdescription. (Renamed in v0.30.) 337
\HTMLFilename: No longer escape underscores. 314
\HomeHTMLFilename: No longer escape underscores. 314
\InlineClass: Renamed from "inlineclass". 327
\LWR@LwarpStart: Fix: math cross references. 371
\LWR@closeparagraph: \unskip extra spaces. 331
No break tags in the start/end of a tabular. 331
\LWR@endofline: Fix: \\ 559

\LWR@filestart: Adds meta description. 367
\LWR@htmldivclass: Added optional style. 325
\LWR@htmlelementclass: Added optional style. 325
\LWR@htmlsectionfilename: HTMLFilename: removed additional trailing '-', and may be empty. 315
Sections called "Index" or "index" have an underscore prepended to their filenames if no prefix. 315
\LWR@includegraphicsb: Fix: \linewidth in a floatrow. 725
Fix: Expands filename. 725
\LWR@longtabledatacaptiontag: Fix: Pars in captions. 440
\LWR@section: Combined higher-level sections together into files. 358
\LWR@setOSWindows: Auto-detects operating system. 211
\LWR@subhtmlelementclass: Factored code. 325
\SetHTMLFileNumber: Add: Control file numbers. 314
\cpagerefFor: User-redefinable word for page references. 535
\dotfill: Inserts an ellipsis. 559
\hfill: Inserts a \qquad. 559
\hrulefill: Inserts a short rule. . . 559
\hspace: Add: Supports HTML thin breakable space. 561
\hyperindexref: Print mode provided in case hyperref not used. 484
\pageref: Added. 462
\tracinglwarp: Added. 230
General: 2017/02/09 1
afterpage: Added. 581
alltt: Added. 586
bookmark: Added. 617
caption and subcaption supported. 1
cleveref and referencing patches: Applied \AfterEndPreamble. . . . 534
draftwatermark: Added. 666
eso-pic: Added. 677
everypage: Added. 678
extramarks: Added. 679
fancyhdr: Added. 685
float: Improved float caption type handling. 696
hyperref: Additional user macros. 737
keyfloat: Added. 754
letterspace: User-interface emulated. 759
listings: Added. 763
ltcaption: Added. 772
lwarp-newproject: Added. 241
microtype: User-interface emulated. 793
needspace: Added. 806
nowidow: Added. 810
placeins: Added. 835
ragged2e: Added. 842
setspace: Improved support. . . 861
textpos: Added. 892
titleps: Added. 901
titlesec: Added. 904
titletoc: Added. 906
titling: Improved compatibility. . 908
tocloft: Added. 915
wallpaper: Added. 939
wrapfig: Added. 940
xetexko-vertical: Added. 953
Added @, <, > columns. 399
Added single-expansion data arrays. 310
Code factored into independent lwarp_html files. 572
Docs: Examples for generating HTML file names. 118
Docs: Improved index. 1
Enhanced titling support. 377
File: lwarp.css: Minor fixes for validation. 1
File: lwarpmk used to compile print, HTML, indexes, and latexmages. 1
Fix: \linewidth in a floatrow. . . 702
Moved sidebar and example code to test suite. 1
Page geometry set to 6in wide with large margins. 219
Parallel versions of aux files for print/HTML. 1
Removed reliance on make, grep, gawk. 1
Tabular: \unskip extra spaces. . . 399
Test Suite: HTML meta descriptions. 1
verbatim: Added. 388
BlockClass: Added optional style. . 327
Renamed from "blockclass". . . . 327
LWR@nestspan: Fix: Minipages inside a span. 322
v0.21
\LWR@LwarpStart: Changed latexmages to a .txt file. 370

\LWR@filestart: Skip title if not given. 367
\LWR@newhtmlfile: Skip title if not given. 351
\marginpar: Fixed source listing. . . 344
\marginparBlock: Fixed source listing. 344
General: 2017/02/23 1
fontenc: Added. 709
lwarpmk: Fix: **lwarpmk again** for WINDOWS. 290
lwarpmk: Fix: **lwarpmk limages** for WINDOWS. 290
lwarpmk: Fix: *lwarpmk* uses lateximages text file instead of shell script. 290
Add: Errors for misplaced packages. 194
Docs: Added internet class. 82
Docs: Added TeX2page, GladTeX. . 82
Docs: Installing on WINDOWS. . . . 88
File: lwarp_tutorial.txt added. . 92
v0.22
\LWR@parseDcolumn: Added tabular D column. 413
\LWR@parsebangcolumn: Added tabular ! column. 409
\LWR@parsetablecols: Unknown table column types become l. Added tabular D, !, X columns. . 415
\LWR@printmccoldata: Added tabular D, !, and X columns. 435
General: 2017/03/02 1
abstract: Added. 574
changepage: Added. 628
dcolumn: Added. 663
ftnright: Added. 715
geometry: Nullified commands. . 717
layout: Added. 756
lscape: Added. 771
mcaption: Added. 781
nameref: Added. 804
nextpage: Added. 806
parskip: Added. 826
showkeys: Added. 862
sidecap: Added. 863
tabularx: Added. 885
varioref: Supported. 132
verse: Added. 933
v0.23
\LWR@parsetablecols: Fix for vert bar column type. 415
\LWR@printmccoldata: Fix for vert bar column type. 435
General: 2017/03/02 1
v0.24
\LWR@htmlfileref: Fix: Index links while \tracinglwarp. 458
\hspace: Add: \hspace \fill converts to 2em 561
\hypertocfloat: List of floats responds to lofdepth, lotdepth. 481
General: 2017/03/15 1
floatrow: Support for subfig. . . . 699
subfig: Added. 878
tikz: For tikz v3.0.0 or later, auto-loads tikz babel library if necessary. 900
Docs: Filename underscore. 113, 126
Fix for inline images. 900
No longer preloads subcaption; conflicted with subfig. 221
picture: Fix for inline images. . . . 537
v0.25
\LWR@loadnever: Added the ability to prevent conflicting packages. . . 196
\addcontentsline: Handles theorems. 473
General: 2016/03/22 1
amsthm: Added. 593
ellipsis: Added. 669
emptypage: Added. 670
framed: Added. 713
lips: Added. 763
mdframed: Help avoid hyphenation. 783
ntheorem: Added. 811
showidx: Added. 862
theorem: Added. 893
Basic LaTeX theorems: improved css. 388
Docs: Adds credits for patched code. 1
Docs: Testing lwarp. 183
Fix: Allows XeLaTeX and LuaLaTeX to preload graphics and graphicx. 198
v0.26
General: 2017/03/31 1
lwarp.css: Improved responsive marginpar and marginblock. . . 249
cutwin: Added. 661
endnotes: Added. 672
floatflt: Added. 698
footmisc: Added. 709
footnotehyper: Added. 711
footnote: Added. 710
marginfix: Added. 779
marginnote: Added. 780
mparhack: Added. 796
pagenote: Supported as-is. 824

sidenotes: Added. 864
Docs: Improved MiKTEX install instructions. 87, 89
Dollar span avoided in a lateximage. 493
Footnotes now are LATEX boxes instead of pagenotes. 338
lateximage: Labels track page numbers of lateximages. 519
Print mode now uses a minipage of \linewidth. 519
picture: Fix for \makebox in picture. 537
v0.27
\LWR@@footnotetext: Fix for table footnote par tags. 340
General: 2017/04/04 1
lettrine: Added. 760
microtype: Fix with XeLATEX, LuaLATEX. 793
soul: Added. 871
ulem: Added. 928
Docs: Installing utilities for MACOS. 90
Docs: Limitations of saveboxes. . 126
Page geometry modified to reduce line overflow. 219
v0.28
\@wrindex: Improved indexing. . . . 483
\HTMLAuthor: Added \HTMLauthor. (Renamed in v0.30.) 337
\LWR@LwarpEnd: If FormatEPUB or FormatWP, no bottom nav. 373
\LWR@LwarpStart: FormatWordProcessor forces single-file output. 370
\LWR@filestart: Adds HTML meta author. 367
\LWR@forcenewpage: Forces new PDF page before major environments. 319
\LWR@htmlcomment: Breaks ligatures in HTML comments. 324
\LWR@includegraphicsb: Adapts to graphics syntax. 725
\LWR@newhtmlfile: If FormatEPUB or FormatWP: skips headers, footers, nav. 351
\LWR@parsetablecols: Added L, C, R, J column types. 415
\LWR@startref: Removed space. . . 461
\chapter: If EPUB, prints footnotes before each section. 364
\hyperindexref: Improved indexing. 484
\textup: Fixed span class. 549
General: 2017/04/14 1
glossaries: Added. 719
graphics: Added. 720
tabularx: Fix for optional pos. . . 885
tabulary: Added. 886
lwarpmk: Add: **printglossary** and **htmlglossary** commands. . . . 290
Added boolean FormatEPUB. . . . 235
Added boolean FormatWP. 235
Added boolean HTMLDebugComments. 230
Added boolean HTMLMarkFloats, changed to WPMarkFloats as of v0.42. 235
Docs: Modfying lwarpmk and index processing. 183
File: lwarp_mathjax.txt: Updated CDN repository. 288
Forced oneside to maintain large right margin. 219
v0.29
\LWR@includegraphicsb: Fix: Error when no optional arguments. . . 725
General: 2017/04/15 1
*.lwarpmkconf: Add: language option for config files. 249
lwarpmk.conf: Add: language option for config files. 248
lwarpmk: Add: language option for config files. 290
Add: lwarpmklang option for lwarp. 213
Docs: Using a glossary 103
v0.30
\CSSFilename: Renamed from \NewCSS. 336
\HTMLAuthor: Renamed from \HTMLauthor. 337
\HTMLDescription: Renamed from \NewHTMLdescription. 337
\HTMLFirstPageTop: Renamed from \SetFirstPageTop. 336
\HTMLLanguage: Renamed from \MetaLanguage. 366
\HTMLPageBottom: Renamed from \SetPageBottom. 336
\HTMLPageTop: Renamed from \SetPageTop. 336
General: 2017/04/29 1
lwarp-newproject removed, and combined with lwarp. 241
lwarpmk: Add: xdyfile configuration option. 290
lwarpmk: Fix: *xindy* and *texindy* adjusted for *pdflatex*, *xelatex* and *lualatex*. 290

lwarpmk: Fix: *xindy* now used for print index generation with *latexmk*. 290
lwarpmk: `language` now used for both index and glossary generation. 290
File: `lwarp_html.xdy` renamed to `lwarp.xdy`. 287
Fix: `*.css` files only written in print mode. 249
Fix: `lwarp.xdy` only written in print mode. 287
Fix: `lwarp_mathjax.txt`: Only written in print mode. 288
Option `lwarpmklang` changed to `IndexLanguage`. 213
Option `OSWindows` replaces macro `\warpOSwindows`. 214
Option `xdyFilename` added. 213
Option *latexmk* replaces macro `\UseLatexmk`. 215
Options `HomeHTMLFilename` and `HTMLFilename` replace macros `\HomeHTMLFilename` and `\HTMLFilename`. 214

v0.31

General: 2017/05/15 1
keyfloat: Improved compatibility. 754

v0.32

`\RequirePackage`: Fix: Ignores blanks in package list. 225
General: 2016/06/09 1
glossaries: Prevent error with `\glo@name` not defined. 485
lwarpmk: Fix: **`io.lines()`** changed to **`file:lines()`** due to *luatex* changes. 290

v0.33

`\HTMLAuthor`: Fix: Provides empty default author if none given. . . . 337
`\LWR@loadbefore`: Fix: No `\PackageError` if already loaded. 196
`\LWR@parseatcolumn`: Fix: Column alignment with leftmost `@`. 408
`\LWR@tabledatasinglecolumntag`: Fix: Macros in tabular could cause extra data cell. 422
`\LWR@vspace`: Add: `\vspace` nullified. 562
`\StartDefiningTabulars`: Add: Avoids error: `Misplaced alignment tab character &`. . . 311
General: 2017/07/10 1
amsmath: Removed `fleqn` option. 586
fancyhdr: Fix: Optional args for `\lhead`, etc. 685
Add: Tabular at and bang columns now have their own HTML columns. 399
cleveref: Fix: Loaded `\AtEndPreamble`. 534
Fix: Incorrectly-inline math environments. 510
New handling of `&` to localize catcode changes. 399

v0.34

`\@fnsymbol`: Text symbols instead of math. 380
`\InlineClass`: Moved optional argument in front of mandatory. 327
`\LWR@htmldivclass`: Moved optional argument in front of mandatory. 325
`\LWR@htmlelementclass`: Moved optional argument in front of mandatory. 325
`\LWR@htmlelementclassline`: Moved optional argument in front of mandatory. 326
`\LWR@htmlspanclass`: Moved optional argument in front of mandatory. 323
`\LWR@nullfonts`: Improved font control. 551
`\LWR@restoreorigformatting`:
booktabs: Works inside `lateximage`. 486
Improved font control. 486
`\LWR@subhtmlelementclass`: Moved optional argument in front of mandatory. 325
`\LWR@tabledatacolumntag`:
booktabs: Works inside `lateximage`. 447
`\fboxBlock`: Added. 545
`\makebox`: Fix: Handles paren arg. . 543
General: 2017/08/08 1
babel-french: Adds fixed-width HTML spaces to punctuation. . . 320
balance: Added. 608
booktabs: Works inside `lateximage`. 450, 618
boxedminipage2e: Added. . . . 620
crop: Added. 661
enumerate: Added. 672
enumitem: Added, no longer required. 672
everyshi: Added. 679
fancybox: Added. 681
fancyvrb: Added, no longer required. 687
figcaps: Added. 692

filecontents: Required. Patched for morewrites. 221
floatpag: Added. 699
flushend: Added. 704
fullpage: Added. 716
hyperxmp: Added. 743
idxlayout: Added. 744
marginfit: Added. 779
mdframed: Improved mdtheorem patch. 788
moreverb: Added. 795
paralist: Added. 825
pdflscape: Added. 827
pdfsync: Added. 831
prelim2e: Added. 836
rotfloat: Added. 849
savetrees: Added. 850
shadow: Added. 862
syntonly: Added. 884
titleps: No longer required. 901
titleref: Prevented. 904
xmpincl: Added. 957
Added. 949
Docs: Horizontal space limitations. 1
Docs: Misplaced alignment character. 185
File: lwarp_mathjax.txt: Version change. 288
File: README.txt: updated. 1
Fix: Added the eqnarray environments. 510
Improved font control. 547
Lists refactored to remove enumitem requirement. 390
Verbatim refactored to remove fancyvrb requirement. 386
tabular: booktabs: Works inside lateximage. 451
lateximage: Fix: lateximage with minipage, \parbox, \makebox, \fbox, \framebox, \raisebox, \scalebox, \reflectbox. 519
BlockClass: Moved optional argument in front of mandatory. 327
fminipage: Added. 545
LWR@nestspan: Fix: Minipages, BlocksClass, and lists inside a span. 322
v0.35
General: 2017/08/08 1
Fix: \textbf and related. 547
v0.36
\LWR@@footnotetext: Extra HTML source space after paragraphs. . 340
Force HTML superscripts. 340
\LWR@HTMLsanitize: Fix for babel-french. 515
\LWR@HTMLsanitizeexpand: Fix for babel-french. 516
\LWR@closeparagraph: Extra HTML source space after paragraphs. . 331
\LWR@currenttextcolor: Fix for \rule when xcolor not loaded. . 557
\LWR@nullfonts: Fix: Filenames while using MathJax. 551
\LWR@restoreorigformatting: siunitx: Improved super/subscripts in a lateximage. 486
\LWR@section: Improved spacing. . 358
\LWR@stoppars: Extra HTML source space after paragraphs. 334
\fbox: Fix: Uses \fboxrule and \fboxsep. 544
\framebox: Fix: Handles width and horiz position. 543
\makebox: Fix: Handles width and horiz position. 543
General: 2017/08/17 1
babel-french: Adjustements for French variants, load order, footnotes, ellipses. 320
footnote: Extra HTML source space after paragraphs. 710
siunitx: Fix for babel-french. . . . 527
siunitx: Improved symbol support. 866
transparent: Added. 924
upref: Added. 932
xcolor: Added \fcolorboxBlock, \colorboxBlock. 942
xcolor: Fix: Background none in print mode. 942
xcolor: Refactored \LWR@colorstyle. 945
xcolor: Uses \fboxrule and \fboxsep. 942
xcolor: \fcolorbox etc. now work inside lateximage. 942
Docs: Reorganized: Special cases and limitations. 123
Source: Improved formatting. . . . 1
tabular: Fix for babel-french. . . . 451
lateximage: Footnotes appear in regular text instead of the lateximage minipage. 519
v0.37
\include: Maintains independent aux files for HTML. 228
General: 2017/08/19 1
LaTeX accents: Added. 240

babel-french: Adjustment for load order. 320
color: Prevented. 658
comment: Maintains independent cutfiles for print, HTML. 218
siunitx: Improved symbol support. 866
textcomp: Improved support. . . 889
lwarpmk: Removes additional HTML aux files. 290
File handles reorganized. 227
v0.38
\@seccntformat: Added for appendix. 357
\ForceHTMLPage: Added. 355
\ForceHTMLTOC: Added. 355
\LWR@section: \part* starts a new HTML page, for appendix. 358
Modified spacing, uses \numberline. 358
\numberline: Added trailing \quad. 479
\part: Fix with article class. 364
General: 2017/08/27 1
appendix: Added. 597
arabicfront: Added. 599
chappg: Added. 630
color: Forces xcolor as well. 658
fix2col: Added. 694
fncychap: Added. 705
grffile: Added. 733
metalogo: Added. 790
nonumonpart: Added. 809
nopageno: Added. 809
pagenote: Option page disabled. 824
realscripts: Added. 843
relsize: Added. 845
romanbarpagenumber: Added. . 848
romanbar: Added. 848
scalefnt: Added. 850
siunitx: Removed from lwarp core. 866
textcomp: Removed from lwarp core. 889
tocbibind: Added. 913
xltxtra: Added. 957
lwarpmk: Added **print1** and **html1** actions. 290
Added \markboth, \sloppy, etc. . 319
Docs: Enhanced *Supported Features* table. 76
Docs: Index, tocbibind. 138
Docs: Starred sections. 134
v0.39
\@maketitle: titling version. 910
Native LaTeX version. 381
Removed minipages. 381, 910
Supports authblk with s of class oneauthor instead of tabular. 381, 910
\AddSubtitlePublished: Added. . . 382
\LWR@domulticolumn: Add: Optional vpos and # rows. 437
\LWR@restoreorigformatting: Appended with \appto instead of calling various macros. 486
\LWR@tabledatacolumntag: Don't start a data cell if see \TabularMacro. 447
\ResumeTabular: Added. 446
\TabularMacro: Added. 446
\multicolumnrow: Added. . . . 444, 800
\printauthor: Removed minipages. 378
Supports authblk with s of class oneauthor instead of tabular. 378
\thanksmarkseries: Removed minipage footnotes. 912
General: 2017/09/05 1
a4wide: Added. 574
a4: Added. 573
a5comb: Added. 574
addlines: Added. 581
anysize: Added. 597
authblk: Added. 606
bigdelim: Added. 614
bigstrut: Added. 616
ebook: Added. 668
fullwidth: Added. 716
midpage: Added. 794
multirow: Add: New optional vpos argument. 798
multirow: Add: Supports left/right border for bigdelim. 798
multirow: Fix: Long text argument. 798
supertabular: Added. 883
textarea: Added. 888
titling: Improved compatibility. . 908
titling: Removed extraneous center environments. 909
typearea: Added. 927
xtabular: Added. 959
zwpagelayout: Added. 963
Docs: Reorganized tabular discussion. 159
Titlepage \published and \subtitle removed. \AddSubtitlePublished restores. 382
titlepage: Clear pending footnotes. 376
Removed minipages. 376
titlingpage: Clear pending footnotes. 908

v0.40
\@chapcntformat: Added for tocbibind, anonchap. 358
\LWR@HTMLhline: Added. 450
\LWR@includegraphicsb: Add: Full \graphicspath support. 725
\LWR@nullfonts: Fix: Long arguments for expandable command. . . . 551
\LWR@restoreorigformatting: Improved LaTeX logos inside a lateximage. 486
Improved symbols inside a lateximage. 486
Nullified \InlineClass, etc. inside a lateximage. 486
\LWR@tabledatacolumntag: Fix for bigdelim: \ldelim, \rdelim. . . . 447
\chapter: Added support for quotchap. 364
\multicolumnrow: Fix: Adapts to older multirow and xparse. 444
\simplechapterdelim: Added for tocbibind, anonchap. 357
\underline: Added. 556
General: 2017/09/25 1
adjmulticol: Added. 580
anonchap: Added. 597
bigdelim: Improved documentation. 614
cuted: Added. 661
dblfnote: Added. 662
fnpos: Added. 706
graphics: Moved out of the lwarp core. 720
graphics: Restores \includegraphics and \DeclareGraphicsExtensions in a lateximage. 720
graphicx: Moved out of the lwarp core. 733
grffile: Directly supported. 733
midfloat: Added. 794
multirow: Improved bigdelim borders. 798
pfnote: Added. 833
quotchap: Added. 841
sectsty: Added. 859
stabular: Added. 875
tabls: Added. 885
textcomp: Additional symbols, improved XeLaTeX and LuaLaTeX support. 889
tocbibind: Improved for \simplechapter. 913
xfrac: No longer preloaded. 222
xltxtra: Fix for \showhyphens with XeLaTeX. 957
v0.41
\LWR@addcmidruletrim: Add: \cmidrule trims. 427
\LWR@clearmidrules: Add: \cmidrule trims. 424
\LWR@closetabledatacell: Add: Mute > for \bottomrule. 403
Fix: At/bang column with \multirow. 403
Fix: Cancel < for \multicolumn. . 403
\LWR@domulticolumn: Add: \cmidrule trims. 437
Added vertical rules. 438
\LWR@nullifyNoAutoSpacing: Fix: \NoAutoSpacing in a tabular with babel-french. 451
\LWR@parsebarcolumn: Added vertical rules. 410
\LWR@printatbang: Add: \cmidrule trims. 420
Add: Mute at and bang columns for \bottomrule. 420
\LWR@printbartag: Added vertical rules. 420
\LWR@subaddcmidruletrim: Added. 426
\LWR@subcmidrule: Add: \cmidrule trims. 425
\LWR@tabledatasinglecolumntag: Add: \cmidrule trims. 422
Add: Mute < for \bottomrule. . . 422
\LWR@tabularfinishrow: Unfinished tabular rows automatically filled. 405
\mcolrowcell: Added for \multicolumnrow cells. 450
General: 2017/10/07 1
multirow: Add: \cmidrule trims. 798
Added vertical rules. 799
Fix: < spec. 799
Improved rules. 618
tabular: Fix: \NoAutoSpacing in a tabular with babel-french. . . . 452
v0.42
\@ensuredmath: Improved \ensuremath. 501
\@textsubscript: Added. 556
\@textsuperscript: Added. 556
\LWR@HTMLhline: If FormatWP force explicit border. 450
\LWR@addformatwpalignment: If FormatWP add explicit style for cell alignment. 429
\LWR@addrulewidth: If FormatWP force explicit border. 427

\LWR@amsmathbody: Fix: Numbering and naming AMS math environments. 518
\LWR@amsmathbodynumbered: Fix: Numbering and naming AMS math environments. 518
\LWR@doequation: If FormatWP print LaTeX expression. 506
\LWR@domulticolumn: If FormatWP add cell alignment. 439
\LWR@doubledollar: If FormatWP print LaTeX expression. 500
Improved \ensuremath. 500
Improved line spacing with mathjax. 500
\LWR@floatbegin: If FormatWP add a text frame. 468
\LWR@floatend: If FormatWP add a text frame. 469
\LWR@htmlmathlabel: If FormatWP print LaTeX expression. 509
\LWR@includegraphicsb: Fix: Filename expansion. 725
If FormatWP, use explicit size. . . . 727
\LWR@rememberтag: Fix: Numbering and naming AMS math environments. 517
\LWR@restoreorigformatting: Improved \ensuremath. 488
\LWR@subaddcmidruletrim: 0pt if no rule given. 426
\LWR@subsingledollar: If FormatWP print LaTeX expression. 494
\LWR@tabledatasinglecolumntag: If FormatWP add cell alignment. . . 422
\LaTeX: If FormatWP use explicit style. 566
\TeX: If FormatWP use explicit style. 566
\hspace: If FormatWP add \quads. . . 561
\listoffigures: Added boolean WPMarkLOFT. 477
\listoftables: Added boolean WPMarkLOFT. 477
\marginpar: If FormatWP emulate a wrapfig. 344
\marginparBlock: If FormatWP emulate a wrapfig. 344
\rule: If FormatWP add \quads. . . . 565
\tableofcontents: Added boolean WPMarkTOC. 476
\underline: If FormatWP, use explicit styles for \underline, etc. 556
General: 2017/10/30 1
\textbf and related: If FormatWP, use explicit styles for \textsc, etc. 547
algorithmicx: If FormatWP add \quads. 585
epigraph: If FormatWP add HTML styles. 673
fancybox: If FormatWP add HTML styles. 681
floatflt: Added width. 698
includegraphics: Fix: Class key. . . 725
keyfloat: If FormatWP add explicit HTML style. 755
moreverb: Simplified formatting of listings. 795
multirow: If FormatWP add cell alignment. 799
overpic: Added. 823
realscripts: Fix for subscripts in a lateximage. 843
sidenotes: If FormatWP add explicit HTML style. 864
siunitx: Improved \ensuremath. . . 866
soul: If FormatWP, add explicit styles. 871
textcomp: Improved \interrobangdown. 889
wrapfig: If FormatWP add explicit HTML style. 940
Added boolean WPMarkLOFT. . . . 236
Added boolean WPMarkMath. . . . 236
Added boolean WPMarkMinipages. 236
Added boolean WPMarkTOC. 236
Added boolean WPTitleHeading. 236
Docs: Added support page. 2
Docs: Improper \prevdepth. . . . 185
Docs: Reorganized math limitations 150
File: lwarp_mathjax.txt: Updated siunitx script. 288
Fix: Numbering and naming AMS math environments. 517
If FormatWP force explicit border. 618
If FormatWP, shift section headings. 237
tabbing: Added. 388
lateximage: Fix: Numbering and naming AMS math environments. 519
center: If FormatWP use explicit text-align. 524
minipage: Added boolean WPMarkMinipages. 541
If FormatWP add a text frame. . . . 540
eqnarray: Fix: Numbering and naming AMS math environments. 512
If FormatWP print LaTeX expression. 511
LWR@BlockClassWP: Added to factor code. 328

LWR@figcaption: If FormatWP forces italic captions. 472
v0.43
\LWR@domulticolumn: Fix for vertical rules. 438
Fix: Multicolumn trim. 438
\LWR@maybeprintpendingfootnotes: Added FootnoteDepth. 343
\LWR@nullfonts: Fix: Nullify dollar inside filesnames. 551
\LWR@parsetablecols: Ignore spaces in col spec. 415
\LWR@printmccoltype: Added vertical rules. 433
\LWR@section: Fix: Expansion in comparison. 359
Fix: Math in section name. . 360, 362
Fix: Nullify fonts inside HTML comment. 360
\TabularMacro: \newcommand instead of \relax to fix supertabular and xtab. 446
\href: Made robust. 464
\nameref: Made robust. 462
\nolinkurl: Made robust. 464
\url: Made robust. 465
General: 2017/11/08 1
LWR@currentautosec: Added. . . . 358
breakurl: Added. 620
hyperref: Made robust. 738, 740, 741
hyperref: \Gauge added. 742
luatodonotes: Added. 774
todonotes: Added. 922
Added FootnoteDepth. 339
Docs: HTML settings table. 113
Docs: Reorganized HTML customization. 113
v0.44
\@currentlabelname: Adjustment for koma-script. 456
\HTMLTitle: Added. 337
\LWR@addformatwpalignment: Fix for multicolumn alignment if FormatWP. 429
\LWR@backgroundcolor: Added. . . . 945
\LWR@filestart: Add \HTMLTitle. . 368
Fix \HTMLAuthor. 368
\LWR@listitem: Added list and trivlist. 392
\LWR@patchlists: Added list and trivlist. 395
\LWR@strresult: Fix: \providecommand. 401
\LWR@textcurrentcolor: xcolor: Added \LWR@textcurrentcolor. 945
\addcontentsline: Automatic \LWR@newfloatanchor. 473
\chapter: Add preamble for koma-script. 364
\marginparBlock: Added. 344
\nopagecolor: xcolor: Fix for \nopagecolor. 947
\part: Add preamble for koma-script. 364
\title: Added \thetitle. 337
General: 2017/11/22 1
algorithmicx: Improved comment symbol. 585
atbegshi: Added. 603
cancel: Added. 623
changepage: Additional options. 628
easy-todo: Added. 667
fancyref: Added. 685
fixmetodonotes: Added. 695
fixme: Added. 694
fontenc: Allowed after lwarp. . . . 709
hang: Added. 734
ifoddpage: Added. 744
ltxtable: Added. 773
luatodonotes: Improved. 774
lwarp-patch-komascript: Added. 964
overpic: Fix: Groups for lateximages. 823
pdfsync: Fixes. 831
preview: Added. 837
scrextend: Added. 851
scrhack: Added. 854
scrlayer-notecolumn: Added. . . 856
scrlayer-scrpage: Added. 856
scrlayer: Added. 854
section: Added. 858
soulpos: Added. 872
soulutf8: Added. 873
supertabular: Fix for caption. . . 884
tikz: Fix: Groups for lateximages. 900
tocbasic: Added. 912
tocloft: Added \newlistentry. . 919
tocloft: Improved \newlistof. . . 920
tocstyle: Added. 921
todonotes: Improved. 922
todo: Added. 921
typearea: Added expert commands. 927
watermark: Added. 940
xcolor: Added \LWR@currenttextcolorstyle. . 945
xcolor: Added \LWR@findcurrenttextcolor. . . 945
xtab: Fix for caption. 960
Adjustment for koma-script. . . . 205

AMS environments: Fix: Groups for lateximages. 587
If pdfLaTeX, require T1 and UTF-8 encoding. 206
picture: overpic: Fix: Groups for lateximages. 537
list: Added list and trivlist. . . 393
LWR@nestspan: Added list and trivlist. 322
v0.45
\@currentHref: Added. 463
\@donoparitem: Modified for HTML. 390
\@item: Modified for HTML. 391
\@mklab: Modified for HTML. 390
\CSSFilename: Improved filenames with underscores. 336
\LWR@LwarpStart: Fix: Lateximages on incorrect pages with Mathjax. 371
\LWR@includegraphicsb: Improved URLs with underscores. 725
\LWR@newautoidanchor: Fix: No anchor if frozen autoid. 470
\LWR@notmemoirloadafter: Added. 195
\LWR@printpendingmpfootnotes: Added. 343
\LWR@startref: Fix: Labels with underscores. 461
\LWR@subhyperref: Improved URLs with underscores. 463
\LWR@subhyperrefclass: Improved URLs with underscores. 464
\LWR@sublabel: Fix: Labels with underscores. 459
\LWR@tabledatacolumntag: Fix: Empty line between rows. 449
\chapter: Add optional heading title for memoir. 364
\newpage: Added. 559
\nolinkurl: Fix: Underscore in URL. 464
\normalmarginpar: Added. 345
\reversemarginpar: Added. 345
\section: Add optional heading title for memoir. 365
\tableofcontents: Fix: Empty sidetoc. 476
Fix: Patch \AtBeginDocument. . . 476
\url: Improved URLs with underscores. 465
General: 2018/01/14 1
array: Added. 599
babel-french: Robust commands. 320
backref: Added. 608
breakurl: Fix: Underscore in URL. 620
changebar: Added. 628
cite: Added. 656
continue: Added. 660
endfloat: Added. 670
epigraph: Support for memoir. . 674
fancyvrb: Improvements. . . 687, 688
flafter: Added. 696
fltrace: Added. 704
footnpag: Added. 712
fwlw: Added. 716
hanging: Added. 736
hyperref: Fix: Underscore in URL. 738, 739
lwarp-patch-memoir: Added. . . . 967
memhfixc: Added. 790
memoir: Added. 569
natbib: Added. 804
pagesel: Added. 824
prettyref: Added. 837
subfigure: Added. 882
subfig: Fix for subcaption end tag. 881
subfig: Fix: Math in subcaptions. 879
textfit: Added. 892
titleref: Added. 904
turnthepage: Added. 927
Allows memoir's preloaded packages. 198
Docs: xparse warnings. 168
Docs: Fix for double hyphens. . . . 90
Docs: Improved install instructions. 91
Docs: Improved MiKTEX install instructions. 87
Docs: Moved table so doesn't interfere with install docs. 86
File: lwarp_mathjax.txt: Allow MathJax inside tabbing. 288
File: lwarp_mathjax.txt: Allow MathJax inside verse. 288
Fix: Empty sidetoc. 476
Improved: Robust \, \ , and \textellipsis commands. 558
Separate LWR@thisautoidWP for word processor s. 470
thebibliography: Patched to emphasize titles. 486
minipage: Fix: Improper \prevdepth. 539, 541, 542
v0.46
\LWR@closeparagraph: Fix: Tabular empty lines. 332
\LWR@closeprevious: Fix: Stack unnesting. 318
\LWR@forcenewpage: Fix: Improper \prevdepth. 319
\LWR@lookforpackagename: Fix: Spaces in \usepackage. 225
\LWR@providelength: Added. . . . 208

\LWRPrintStack: Name changed from \PrintStack. 317
\makebox: Fix: Lateximage in a \makebox. 543
\popclose: Fix: Stack unnesting. . . 309
\pushclose: Fix: Stack unnesting. . 309
General: 2018/01/23 1
LWR@tabularpardepth added. . . 401
amsthm: Adapted to trivlist changes. 595
mdframed: Fixes for SVG math or lateximage in title. 785
mdframed: Fixes for footnotes. . 785
ntheorem: Adapted to trivlist changes. 811
theorem: Adapt to trivlist changes. 895, 896
tabular: Fix: Tabular empty lines. 454, 455
list: Fix: Stack unnesting. 393
v0.47
\LWR@HTML@caption@begin: Fix: Argument passed to \LWR@origcaption@begin. . . . 472
\LWR@LwarpStart: Fix for SVG math in \nameref. 372
\LWR@WPcell: Fix: Line wrap at HTML hyphen. 428
\LWR@createautosec: Fix: Line wrap at HTML hyphen. 357
\LWR@domulticolumn: Fix: Line wrap at HTML hyphen. 438
\LWR@floatbegin: Fix: Line wrap at HTML hyphen. 468
\LWR@htmlclosecomment: Add \mbox to prevent line breaks. 323
\LWR@newautoidanchor: Fix: Line wrap at HTML hyphen. 470
\LWR@printopenlist: Fix: Line wrap at HTML hyphen. 390
\LWR@startref: Fix: Line wrap at HTML hyphen. 461
\LWR@sublabel: Fix: Line wrap at HTML hyphen. 459
\LWR@subsingledollar: Added SVG math image baseline adjust and em sizing. 494
Fix: Line wrap at HTML hyphen. . 498
\captionlistentry: Fix: Line wrap at HTML hyphen. 473
\hypertoc: Fix: Line wrap at HTML hyphen. 480
\hypertocfloat: Fix: Line wrap at HTML hyphen. 481
\makebox: Fix: Line wrap at HTML hyphen. 543
General: 2018/01/30 1
adjmulticol: Fix: Line wrap at HTML hyphen. 580
blowup: Added. 616
caption: Added. 624
caption: Also loads lwarp-caption. 227
changepage: Fix for pagecheck macros. 628
endheads: Added. 671
epigraph: Fix: Line wrap at HTML hyphen. 673
hanging: Fix: Line wrap at HTML hyphen. 736
hang: Fix: Line wrap at HTML hyphen. 734
keyfloat: Fix for SVG math in captions. 754
midpage: Fix: Line wrap at HTML hyphen. 794
multirow: Fix: Line wrap at HTML hyphen. 798
multitoc: Added. 801
ntheorem: Fix: Line wrap at HTML hyphen. 815
realscripts: Fix: Line wrap at HTML hyphen. 843
scrextend: Fix: Line wrap at HTML hyphen. 851
sectionbreak: Added. 859
sidenotes: Fix for SVG math in captions. 864
subfig: Fix for SVG math in captions. 879
subfig: Fix: Support \nameref. . . 878
xurl: Added. 961
lwarpmk: *pdfcrop*: Removed hires option for improved crop accuracy. 290
lateximage: Added CSS style option. 519
Fix: Line wrap at HTML hyphen. . 523
center: Fix: Line wrap at HTML hyphen. 524
minipage: Fix: Line wrap at HTML hyphen. 540
flushleft: Fix: Line wrap at HTML hyphen. 524
flushright: Fix: Line wrap at HTML hyphen. 524
enumerate: Fix: Line wrap at HTML hyphen. 394
itemize: Fix: Line wrap at HTML hyphen. 394

LWR@BlockClassWP: Fix: Line wrap at HTML hyphen. 328
v0.48
\@@@setcpageref: Fix for new v0.21 of cleveref. 535
\@@@setcref: Fix for new v0.21 of cleveref. 534
\@@@setcrefrange: Fix for new v0.21 of cleveref. 535
\@biblabel: Improved bibliography label. 486
\@item: Honors \makelabel. 391
\@maketitle: Fix: Errors with IEEEtran class. 381
\LWR@LwarpStart: Adjusted space around captions. 371
\LWR@ProvidesPackageDrop: Fix: Options with braces. 227
\LWR@addtabularhrulecolor: colortbl: Added. 429
\LWR@addtabularrulecolors: colortbl: Added. 430
\LWR@closetabledatacell: colortbl: Added. 404
\LWR@includegraphicsb: Fix: Virtual page size limited to a group. 725, 729
\LWR@lookforpackagename: Fix: Parsing similar package names. . 224
\LWR@newautopagelabel: Fix: TOC, LOF, LOT links. 350
\LWR@newhtmlfile: Fix: TOC, LOF, LOT links. 353
\LWR@nullfonts: Fix: \newline in title. 551
\LWR@parsedrequirepackagenames: Fix: Parsing similar package names. 223
\LWR@parsetablecols: Fix: Ignore optional tabular column arguments. 416
\LWR@restoreorigformatting: Fix: Spacing in SVG math, lateximage, Ti*k*z. 487
\LWR@section: Fix: TOC, LOF, LOT links. 362
\LWR@tabledatasinglecolumntag: colortbl: Added. 423
\LWR@textcurrentfont: Added. Improves font control. 554
\bibliography: Fix: \BaseJobname for bibliography. 485
\centerline: Added. 525
\l@part: Adapts to classes without \part. 481
\leftline: Added. 525
\mbox: Nullified for HTML. 543
\rightline: Added. 525
\thempfootnote: Removed \itshape. 343
General: 2018/02/14 1
acronym: Added. 579
acro: Added. 577
chapterbib: Added. 630
colortbl: Added. 418, 429, 658
fancyref: Now directly supported. 685
hypcap: Added. 737
hypernat: Added. 737
hyperref: \texorpdfstring now uses the TEX string. 741
luatodonotes: Improved \todototoc. 774
siunitx: Changes fraction to symbol. 868
siunitx: Improved SVG math. 866, 868
siunitx: Improved color output. . 866
stfloats: Added. 876
todonotes: Improved \todototoc. 922
vmargin: Added. 936
xfrac: Fix: Added groups around super/subscripts to localize LWR@nestspan changes. 954
Docs: Converting an existing document. 106
Improved font control. 554
tabular: colortbl: Added. 453
lateximage: Print mode boxed to natural width. 523
abstract: Allow optional name. . . . 383
v0.49
\LWR@addtabularcellcolor: xcolor: Added tabular row colors. 432
\LWR@domulticolumn: xcolor: Added tabular row colors. 439
\LWR@printlength: Fix: Group printlen changes. 222
\affiliation: Fix: Adapts to classes which already provide. 376
\href: Fix: Adapt to classes. 464
\noalign: Fix: \noalign inside tabular. 450
\url: Fix: Adapt to classes. 465
General: 2018/02/19 1
amsmath: Fix: Patches for \eqref. 586
eso-pic: Fix for \AddToShipoutPicture. 678
figsize: Added. 693
fnlineno: Added. 706
hypdestopt: Added. 737
hyphenat: Added. 743
lineno: Added. 761
luacolor: Added. 773

pagegrid: Added. 824
pdfrender: Added. 830
resizegather: Added. 847
vertbars: Added. 935
vwcol: Added. 937
xcolor: Added tabular row colors. 418, 951
Fix: Adapt to classes. 558
v0.50
\@ensuredmath: Fix: Use lateximage even if MathJax. 501
Improved SVG math alt tags. . . . 501
\LWR@@footnotetext: Robustify macros. 341
\LWR@atbeginverbatim: Improved column alignment. 387
\LWR@doequation: Improved SVG math display. 506
\LWR@doubledollar: Improved SVG math alt tags. 500
Improved SVG math display. 500
\LWR@htmlrefsectionfilename: Fix: SVG math in a section name. . . 316
\LWR@newhtmlfile: Fix: SVG math in a section name. 353
\LWR@nullfonts: Fix: \underline in sectioning file name. 553
\LWR@overline: Added. 557
\LWR@subsingledollar: Fix: Use lateximage even if MathJax. . . . 494
Improved SVG math alt tags. . . . 494
MD5 hash avoids duplicate SVG math. 498
\LWR@vspace: Robustify macros. . . . 562
\newline: Robustify macros. 559
\textsubscript: Robustify macros. 556
\textsuperscript: Robustify macros. 556
General: 2018/03/03 1
lwarp.css: Improved SVG display math centering. 249
lwarp_one_limage.txt: Added. . 288
amsmath: Fix: Upright tags for SVGmath. 586
axodraw2: Added. 607
bytefield: Added. 623
dblfloatfix: Added. 662
diagbox: Added. 663
epstopdf: Added. 675
listings: Force flexible columns. . 764
morefloats: Added. 794
nonfloat: Added. 808
ntheorem: Fix: Not standard nor amsthm selected. 817
pbox: Added. 826
phfqit: Added. 833
schemata: Added. 850
siunitx: Fix: Loads xcolor. 866
siunitx: Improved SVG math alt tags. 868
siunitx: Improved units. 527, 866, 869
xy: Added. 962
lwarpmk: Error if lateximages.txt does not exist. 290
lwarpmk: Error if lwarpmk.conf points to lwarp. 290
lwarpmk: Improved error messages. 290
lwarpmk: MD5 hash avoids duplicate SVG math. 290
lwarpmk: Multiprocess support making lateximages. 290
AMS environments: Improved SVG math display. 587
Fix: Load fontspec if necessary. . 219
Robustify macros. 554
lateximage: Fix: SVG math in a section name. 521
MD5 hash avoids duplicate SVG math. 520, 523
eqnarray: Improved SVG math display. 512
v0.51
\@ensuredmath: Hashes \ensuremath. 501
\@item: Restored list label space. . . 392
\LWR@HTMLsanitize: Fix: Escapes double quotes. 515
\LWR@HTMLsanitizeexpand: Fix: Escapes double quotes. 516
\LWR@LwarpStart: MathJax: Nullifies \ensuremath. 372
\LWR@addbaselinemarker: Improved SVG math baseline. 493
\LWR@atbeginverbatim: Adds vertical offset. 386
\LWR@customizeMathJax: MathJax: Nullifies \ensuremath. 350
\LWR@doequation: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. 506
\LWR@doubledollar: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. 500
\LWR@findcurrenttextcolor: Added \LWR@findcurrenttextcolor when no xcolor. 557
\LWR@newautoidanchor: Fix: No autoid is inside a lateximage. . . 470

\LWR@newhtmlfile: MathJax: Nullifies \ensuremath. 354
\LWR@subsingledollar: Fix: \ensuredmath inside SVG image. 495
Fix: lateximage inside $\mathcal{AMS}$ \text. 496
Fix: Honors text font around SVG math. 495
Fix: SVG math with enclosed lateximage. 495
Improved SVG math baseline. . . . 496
SVG math baseline improved with invisible rule at corner. 499
Typeset SVG math only once during measurement. 496
\LWR@textcurrentcolor: xcolor: \LWR@textcurrentcolor if xcolor not loaded. 557
\addcontentsline: Add missing support for float mechanism if necessary. 474
No anchor ID if inside SVG image. 474
\displaymathnormal: Processing for complicated display math. . . . 508
\displaymathother: Processing for complicated display math. . . . 508
\textcolor: Fix: SVG math color. . . 946
General: 2018/03/24 1
HTML entity used for text dollar. . 493
lwarp_one_limage.txt: *pdftocairo -noshrink* added. 288
afterpackage: No longer required. 220
chemfig: Added. 631
chemformula: Added. 632
chemgreek: Added. 636
chemmacros: Added. 637
chemnum: Added. 655
epstopdf-base: Added. 675
fancybox: Fix: Optional tag for \item in a span. 683
grid: Added. 733
listings: Forces cleared options. . 764
ltxgrid: Added. 772
mhchem: Added. 791
tikz: Fix for \tikz macro. 900
tikz: Fix for tikz with optional argument. 900
titling: Fix for \thanks mark. . . . 910
lwarpmk: *pdfcrop*: Restored hires option. 290
lwarpmk: *pdftocairo* -noshrink added. 290
AMS environments: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. 587
Docs: tikz limitations. 156
Docs: Multiple authors and affiliations. 134
Docs: Things to avoid. 124
Docs: Updated Converting an existing document. 106
Fix: Remember original \# in case is redefined. 238
lateximage: Added additional hashing option. 519
Fix: lateximage inside $\mathcal{AMS}$ \text. 519
Processing for complicated display math. 522
alignat: Fix: Added. 591
eqnarray: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. 512
LWR@displaymathother: Processing for complicated display math. . . 502
LWR@equationother: Processing for complicated display math. . . . 503
v0.52
\@ensuredmath: Improved hashing expansion. 501
\@mpfootnotetext: Fix: Paragraph handling. 342
\CustomizeMathJax: Added. 350
\LWR@@footnotetext: Fix: Paragraph handling. 341
\LWR@addbaselinemarker: Warnings if lwarp_baseline_marker.png is not present or if graphicx/s not loaded. 493
\LWR@customizedMathJax: Added. . 350
\LWR@doequation: Fix: equation* now based on equation instead of displaymath. 506
Fix: equation* with split. 505
\LWR@filenamenoblanks: Fix: \FileDepth with non-utf8 encoding. 349
\LWR@nullfonts: Fix: \texorpdfstring in section names. 553
\LWR@section: Fix: Footnote numbering: Limited HTML comment if starred. 360
Fix: Footnote numbering: Use short TOC entry for HTMLDebug comments. 360
\LWR@subsingledollar: Added user-adjustable SVG math font scaling. 497

\LateximageFontScale: Added user-adjustable SVG math font scaling. 515
\href: Fix: #, %, &, ~, _ in URL. 464
\nolinkurl: Fix: #, %, &, ~, _ in URL. 464
\theHTMLTitleSeparator: Fix: \FileDepth with non-utf8 encoding. 366
\url: Fix: #, %, &, ~, _ in URL. 465
General: 2018/04/01 1
breakurl: Fix: #, %, &, ~, _ in URL. . 620
endfloat: Updated for v2.6. 670
fancyvrb: Initial support for \VerbatimFootnotes. 681, 687
hyperref: Fix: #, %, &, ~, _ in URL. 738–740
nicefrac: Added. 807
url: Added. 933
lwarpmk: Fix: Memory overflow when spawning tasks. 290
lwarpmk: Fix: Skip image generation if from page 0. 290
Changed FootnoteDepth default to \subsbusection. 339
Docs: Improved install instructions. 88
Fix: MathJax script line wraps. Reduced right margin. 219
If pdfLaTeX, allow other input encoding. 206
pkggraphics: Added defaults. . . . 723
pkggraphicx: Updated for v1.1a. . 723
pkggraphicx: Updated for v1.1b. . 724
Restore \kill in a lateximage. . 771
tabbing: Fix to allow inside lateximage. 388
lateximage: Fix for hash expansion. 520
v0.53
General: 2018/04/01 1
lwarpmk: Added **lwarpmk cleanlimages**. 290
lwarpmk: Added warning for corrupted images. 290
Docs: **lwarpmk cleanlimages**. . . 104
Docs: **lwarpmk pdftohtml**. . . . 104
v0.54
\LWR@afterendverbatim: Added vspace argument. 387
\LWR@atbeginverbatim: Improved column alignment. 387
\LWR@earlyloadnever: Added. 197
\LWR@endfloatalignment: Honor \centering, etc. in floats. 470
\LWR@floatalignment: Honor \centering, etc. in floats. 470
\LWR@floatbegin: Honor \centering, etc. in floats. 468
\LWR@floatend: Honor \centering, etc. in floats. 469
\LateximageFontSizeName: Defaults to normalsize. 515
\centering: Added debug comment. 524
\raggedleft: Added debug comment. 525
\raggedright: Added debug comment. 525
General: 2018/04/22 1
*.lwarpmkconf: Option IndexLanguage changed to xindyLanguage. 249
*.lwarpmkconf: Option pdftotextEnc added. 249
*.lwarpmkconf: Option xdyFilename changed to xindyStyle. 249
*.lwarpmkconf: Option xindyCodepage added. 249
lwarp.css: Fix: Text-decoration-skip: auto. . . . 249
lwarpmk.conf: Option IndexLanguage changed to xindyLanguage. 248
lwarpmk.conf: Option pdftotextEnc added. 248
lwarpmk.conf: Option xdyFilename changed to xindyStyle. 248
lwarpmk.conf: Option xindyCodepage added. 248
bibunits: Added. 614
chngpage: Added. 656
forest: Added. 712
glossaries: Fix when not using babel or polyglossia. 719
gridset: Added. 734
hyperref: Fix: \hyperref and \hyperlink with special chars in text. 740
hyperref: Fix: \ref in \hyperref and \hyperlink caused nested link. 740
lwarp-patch-memoir: Update for v3.7g. 971
magaz: Added. 776
ragged2e: Fix: \centering, etc. . 842
textcomp: Fix for \textperthousand. 889
tikz: Fixes for \pgfpicture, minipages, fit, align, font. 900
lwarpmk: Added pdftotextenc. . 290

lwarpmk: Added xindycodepage. 290
lwarpmk: Changed language to xindylanguage. 290
lwarpmk: Changed xdyfile to xindystyle. 290
lwarpmk: Improved error if configuration file does not exist. 290
lwarpmk: Increased prominence for error for an unknown command. 290
lwarpmk: Verifies HTML version exists before lwarpmk limages. . 290
lwarpmk: Verifies image references before lwarpmk limages. 290
Add: pdftotextEnc. 214
Add: xindyCodepage. 213
Added early check for disallowed packages. 197
Docs: BibTeX. 136
Docs: Macros in sectioning names. 124
Never load aecompl. 197
Option IndexLanguage changed to xindyLanguage. 213
Option xdyFilename changed to xindyStyle. 213
verse: Fix: Line spacing. 385
v0.55
\LWR@LwarpStart: Fix: Overfull boxes in lateximages. 370
\LWR@floatbegin: Fix: Float optional args. 468
\LWR@nullfonts: Removed extraneous space which appeared in file links. 553
\phantomsection: Fix: \ForceHTMLTOC with \phantomsection. 565
General: 2018/04/26 1
clrdblpg: Added. 657
Fix: \centering, etc. for koma-script. 468
Fix: QED symbols in lateximage. 596, 821
v0.56
\LWR@addcdashline: arydshln: Added. 428
\LWR@addmulticolvertrulecolor: Adds support for dashed vertical rules. 436
Adds support for double vertical rules. 436
\LWR@addtabularhrulecolor: Adds support for arydshln dashed rules. 429
Adds support for double \hlines and \midrules. 429
\LWR@addtabularrulecolors: Adds support for dashed vertical rules. 430
Adds support for double vertical rules. 430
\LWR@closeparagraph: Added support for parnotes. 332
\LWR@domulticolumn: Adds support for dashed vertical rules. 438
Adds support for double vertical rules. 438
\LWR@floatbegin: Adds a <class> per float package style. 468
\LWR@multicolpartext: Fix: \multicolumn parameters. . . . 434
\LWR@openparagraph: Added support for parnotes. 331
\LWR@parsebarcolumn: Adds support for double vertical rules. 410
\LWR@parsecoloncolumn: arydshln: Added. 411
\LWR@parsesemicoloncolumn: arydshln: Added. 412
\LWR@parsetablecols: Added array W column. 417
\LWR@printmccoldata: Added array W column. 435
Fix: \multicolumn parameters. . . 435
\LWR@printmccoltype: Added array W column. 433
Adds support for dashed vertical rules. 433
Adds support for double vertical rules. 433
\LWR@tabledatacolumntag: Fix: \morecmidrules 448
\LWR@textcurrentfont: Added span.textbf, etc. 554
General: 2018/05/12 1
*.lwarpmkconf: Records --shell-escape. 249
lwarp.css: Added div.textbf, etc. 249
lwarp.css: Added span.textbf, etc. 249
lwarpmk.conf: Records --shell-escape. 248
arydshln: Added. 399, 600
lua-check-hyphen: Added. 773
paralist: Fixes for compactenum, compactitem, compactdesc. . . . 825
parnotes: Added. 825
quoting: Added. 842
tocenter: Added. 914
underscore: Added. 931

lwarpmk: Added `lwarpmk pdftosvg`. 290
lwarpmk: Supports `--shell-escape`. 290
Added `\thinspace`. 558
Docs: **`lwarpmk pdftosvg`**. 104
`LWR@blocktextcurrentfont`: Added `div.textbf`, etc. 554
v0.57
`\BlockClassSingle`: Improved print/HTML output selection. . . 327
`\InlineClass`: Improved print/HTML output selection. 327
`\LWR@customizeMathJax`: MathJax: Supports `\footnote`, `\footnotemark`. 350
`\LWR@ref@ignorestar`: subcaption: Fix: `\subref`. 462
`\LWR@subhyperref`: Fix: Text catcodes. 463
`\LWR@subhyperreftext`: Fix: Text catcodes. 464
`\LWR@subsingledollar`: Fix: Dynamic inline math expressions. 495, 496, 498
`\LWR@vspace`: Improved print/HTML output selection. 562
`\StartDefiningMath`: Added. 311
`\boxframe`: xcolor: Fix: Colored `\boxframe`. 950
`\colorbox`: xcolor: New system for switching print and HTML outputs. 947
`\colorboxBlock`: xcolor: New system for switching print and HTML outputs. 947
`\fboxBlock`: Improved print/HTML output selection. 545
`\fcolorbox`: xcolor: New system for switching print and HTML outputs. 948
`\framebox`: Improved print/HTML output selection. 543
`\href`: Fix: Text catcodes. 464
`\inlinemathother`: Added. 312
`\listof`: Fix: Provide `\l@name` if not defined. 478
`\makebox`: Improved print/HTML output selection. 543
`\mathimagename`: Added. 492
`\mbox`: Improved print/HTML output selection. 543
`\multicolumnrow`: multirow: Improved print/HTML output selection. 800
Improved print/HTML output selection. 444
`\newfloat`: rotfloat: Added float styles. 849
rotfloat: Fix for listof sideways floats. 849
`\packagediagramname`: Added. . . . 492
`\parbox`: Improved print/HTML output selection. 542
`\raisebox`: Improved print/HTML output selection. 547
`\reflectbox`: Improved print/HTML output selection. 732
`\resizebox`: Improved print/HTML output selection. 732
`\rotatebox`: Improved print/HTML output selection. 730
`\rule`: Fix: Colored rules. 564
`\scalebox`: Improved print/HTML output selection. 731
`\textcolor`: xcolor: New system for switching print and HTML outputs. 946
General: 2018/06/06 1
`lwarp.css`: Added ruled, boxed, boxruled floats. 249
`lwarp.css`: Increased float vertical margins. 249
algorithm2e: Added. 581
bigdelim: Improved print/HTML output selection. 614
breakurl: Fix: Text catcodes. . . . 620
colortbl: New system for switching print and HTML outputs. . . 658, 659
ellipsis: Added `\midwordellipsis`. 669
errata: Added. 676
float: Added float styles. 697
float: Fix: Do not pre-define `\l@name`. 697
ltablex: Added. 771
marginnote: Fix: Long optional argument. 780
multirow: Improved print/HTML output selection. 798
register: Added. 844
subcaption: Fix: `\subref`. 739
trimclip: Added. 925
vowel: Added. 936
xellipsis: Added. 952
xfrac: Improved print/HTML `\scalebox` control. 954
xltabular: Added. 956
xpiano: Added. 958
lwarpmk: Improved code factoring. 290

lwarpmk: Improved error handling. 290
Docs: Recompiling *lwarpmk* or CSS files. 183
Docs: Recreating the index for lwarp source. 180
New system for switching print and HTML outputs. 233
minipage: Improved print/HTML output selection. 539
BlockClass: Improved print/HTML output selection. 327
fminipage: Improved print/HTML output selection. 545
LWR@BlockClassWP: Improved print/HTML output selection. . . 328
v0.58
\LWR@HTML@caption@begin: Improved print/HTML output selection. . . 472
\LWR@HTML@caption@end: Improved print/HTML output selection. . . 473
\LWR@HTML@ref: Improved print/HTML output selection. 462
\LWR@doindexentry: Adds support for \see, \seealso, \emph, \textbf, etc. 484
\LWR@hyperindexrefnullified: Adds support for \see, \seealso, \emph, \textbf, etc. 484
\LWR@indexitem: Accepts optional arg for repeatindex. 483
\dotfill: Improved print/HTML output selection. 559
\hfill: Improved print/HTML output selection. 559
\hrulefill: Improved print/HTML output selection. 559
\hyperindexref: Adds support for \see, \seealso, \emph, \textbf, etc. 484
\printindex: Fix: Extra \newpage to flush pending \index writes. . . . 776
General: 2018/07/07 1
*.lwarpmkconf: Added option makeindexstyle. 249
*.lwarpmkconf: Added options makeindex and xindy. 249
*.lwarpmkconf: Generated \AtBeginDocument. 249
lwarp.xdy: Requires makeindex.xdy. 287
lwarp.xdy: Supports bold, italic. 287
lwarp_html.ist: Added. 286
lwarpmk.conf: Added option makeindexstyle. 248
lwarpmk.conf: Added options makeindex and xindy. 248
lwarpmk.conf: Generated \AtBeginDocument. 248
array: Improved print/HTML output selection. 599
attachfile2: Added. 604
attachfile: Added. 603
cases: Added. 627
imakeidx: Added. 745
index: Added. 749
intopdf: Added. 750
lwarp-patch-komascript: Modified indexing. 965
lwarp-patch-memoir: Fix for \specialindex. 987
lwarp-patch-memoir: Fix for multiple indexes. 987
makeidx: Added. Moved from lwarp core. 776
memoir: Fix for \firsthlline, \lasthline. 445
memoir: Fix for booktabs. 450
pdfpages: Added. 828
pdfx: Added. 832
repeatindex: Added. 847
splitidx: Added. 874
textcomp: Improved print/HTML output selection. 889
lwarpmk: Added makeindex and xindy options. 290
lwarpmk: Added -p option for project name. 290
lwarpmk: Added optional list of names for **lwarpmk printindex** and /cmdslwarpmk htmlindex. . 290
lwarpmk: Glossary generation now uses *makeglossaries*. 290
lwarpmk: **lwarpmk clean** removes all *.ind and *.idx files. 290
Added makeindex option. 215
Added xindy option. 215
Added option makeindexStyle. . 213
Docs: Index, *makeindex*, imakeidx. 138
Docs: Misplaced \omit. 185
Fix: memoir and ccaption. . . . 198
Improved print/HTML output selection. 558
Replaced each \csuse with \@nameuse to force error if undefined. 1
tabbing: Improved print/HTML output selection. 388

v0.59
\LWR@addbaselinemarker: Uses .eps if DVI *latex*. 493
\LWR@includegraphicsb: Fix: Expand filename. 726
Now works with .pdf and .eps filename extensions. 725
\LWR@latexmkcmd: Fix: --shell-escape with *latexmk*. . 244
\LWR@writeconf: Compilation commands now preassigned by lwarp instead of being computed by *lwarpmk*. 248
\[: Fix with \displaymathnormal. . 501
General: 2018/09/07 1
Slunits: Added. 865
accsupp: Added. 577
amsmath: Moved from the lwarp core. 586
asymptote: Added. 602
axessibility: Added. 607
breqn: Added. 621
bxpapersize: Added. 622
canoniclayout: Added. 624
chemformula: Fix for \NMR. 652
draftcopy: Added. 666
epstopdf-base: Improved. 675
epstopdf: Improved. 675
fnbreak: Added. 705
nccfancyhdr: Added. 805
pdftricks: Added. 831
pst-eps: Added. 839
pstricks: Added. 840
units: Added support for MathJax. 931
xunicode: Added. 960
lwarpmk: Added **lwarpmk epstopdf**. 290
lwarpmk: Consolidated compiling options into printlatexcmd and HTMLlatexcmd. 290
lwarpmk: Double insead of single-dashed --shell-escape option. 290
lwarpmk: Error if lwarpmk.conf format changed. 290
lwarpmk: Warning if operating system changed. 290
Added option dvipdfmx. 215
Added option dvipdfm. 215
Added option dvips. 215
Docs: **lwarpmk epstopdf**. 104
File: lwarp_mathjax.txt: Fix: Removed chapter number from tagged non-numeric MathJax equations. 288
File: lwarp_mathjax.txt: Updated to MathJax v2.7.4. 288
picture: Added an alt tag. 537
v0.60
\LWR@clearmidrules: tabular: Fix for midrules. 424
\LWR@parsenormalcolumn: tabular: Improved memory management: Not using xstring. 412
\LWR@tabledatasinglecolumntag: tabular: Improved memory management: Not using xstring. 422
\LWR@tabularendofline: Fix: Slowdown for long tables. 407
General: 2018/09/19 1
tabular: Improved memory management: Global boolean. . 400
tabular: Improved memory management: Not using xstring. 401, 799
2up: Added. 573
booklet: Added. 617
bophook: Added. 619
diagbox: Fix for par tags. 664
draftfigure: Added. 666
fancytabs: Added. 686
fullminipage: Added. 715
grid-system: Added. 734
layaureo: Added. 756
leading: Added. 759
listings: Fix for HTML entities. . . 764
listings: Fix if inside a list. . . 764, 767
thumbs: Added. 899
thumb: Added. 899
widows-and-orphans: Added. . . 940
v0.61
\DeclareGraphicsExtensions: Fix: EPS for DVI LaTeX. 721
\LWR@HTMLLatexCmd: Added HTMLLatexCmd option. 247
Added PrintLatexCmd option. . . 247
\LWR@addcompilecmd: Removed spaces. 243
\LWR@closetabledatacell: Fix: Par tags in tabular. 403
\LWR@hyperindexrefnullified: Made robust, ... 484
\LWR@includegraphicsb: Fix: EPS for DVI LaTeX. 727
Set keys before using filename, for epsfig. 726
\LWRopseq: Added spaces. 210
\RequirePackage: Support up to 20 packages. 225

\inlinemathnormal: Changed name from \StopDynamicMath to \inlinemathnormal. 312
\inlinemathother: Changed name from \StartDynamicMath to \inlinemathother. 312
\listof: Fix: newfloat lists. 478
\lwarpsetup: Added. 212
General: 2018/10/13 1
lwarp.css: Footnotes text align left. 249
lwarp.css: Minipage table and footnotes: tighter margin. 249
chkfloat: Added. 656
cmdtrack: Added. 657
copyrightbox: Added. 660
dprogress: Added. 665
epsfig: Added. 674
lua-visual-debug: Added. 773
pdfprivacy: Added. 830
psfragx: Added. 838
psfrag: Added. 838
pstool: Added. 839
refcheck: Added. 844
srcltx: Added. 875
srctex: Added. 875
supertabular: Fix for caption w/o opt arg. 883
thinsp: Added. 897
threadcol: Added. 897
uspace: Added. 933
vpe: Added. 937
xbmks: Added. 941
xtab: Fix for caption w/o opt arg. 959
Added HTMLLatexCmd option. . . . 214
Added PrintLatexCmd option. . . 214
Docs: \tracinglwarp 230
Docs: HTML entities. 124
Docs: Compiling using custom shell commands. 169
Docs: Fonts. 107
Docs: HTMLDebugComments 113, 230
Docs: Multiple indexes. 190
Don't write configuration files if processing pstool image. 242
Spaces redefined \AtBeginDocument. 558
v0.62
\@partcntformat: Added for ctex. . 358
\@partnameformat: Added for ctex. 358
\InlineClass: Added optional word-processing style. Replaces \LWR@HTMLtextstyle. 327
\LWR@PreloadedPackage: Added. . . 525
\LWR@ProvidesPackagePass: Fix: Unknown option error. 226
\LWR@endofline: Extra space if optional arg. 559
\LWR@filestart: Refactored. 368
\LWR@includegraphicsb: Fix: FormatWP. 727
Fix: Filename expansion. 728
\LWR@isolate: Added. 208
\LWR@textcurrentfont: Added print version. 557
Tracks depth to avoid nesting repeated font changes. 554
\colorboxBlock: Fix: Horiz white space. 947, 948
\fcolorbox: Fix: No longer requires xifthen. 531
\fcolorboxBlock: Fix: Horiz white space. 948, 949
\l@chapter: Don't define if no \chapter. Fix for algorithm2e. . 481
\slshape: Added. 555
\textup: Fixed WP span class. . . . 549
\theHTMLSection: Added. 367
\theHTMLTitleSection: Added. . . . 367
\theHTMLTitleSeparator: Refactored. 366
General: 2018/11/19 1
\textbf and related: Improved font detection. 547
lwarp.css: Added css for xfrac, nicefrac. 249
lwarp.css: Fixed css for \textup. 249
lwarp.css: Reduced margins in titlepage. 249
lwarp_formal.css: Fix: Font for verse. 282
2in1: Added. 573
CJKutf8: Prevented unless xeCJK. 657
CJK: Prevented unless xeCJK. . . 657
asymptote: Improved alt tags. . . 602
bitpattern: Added. 616
calc: Fix: Required for print version. 220
chngpage: Fix: Loads lwarp-chngpage. 656
ctexpatch: Added patch. 571
flippdf: Added. 696
musicography: Added. 801
nicefrac: Improved font control and css, honors nice, ugly. . . . 807
notespages: Added. 810
octave: Added. 822
pdfcomment: Added. 827
pdfmarginpar: Added. 827

register: Updated to v1.8. 844
rviewport: Added. 850
semantic-markup: Added. 860
textcomp: Fix conflict with xunicode. 890
tram: Added. 924
twoup: Added. 927
ulem: Improved compatibility with CJKulem. 928
ulem: Now works in a lateximage. 928
unitsdef: Added. 932
units: Improved font control and css, honors loose, tight. 931
xechangebar: Added. 952
xfrac: Improved css. 954
xunicode: Fix conflict with textcomp. 960
Added early checks for CJK, CJKutf8. 197
Docs: asymptote. 158
Docs: miktex-poppler-bin-* 91
Docs: *MiKTeX Console* 87
Docs: Improved MiKTEX install instructions. 87
Docs: UTF-8 locale. 172
File: lwarp_mathjax.txt: Removed inoperable siunitx extension. . . 288
Fix for \em. 550
Fix: Horiz white space. 949
Logos: CSS instead of <sup>, <sub>. 566
Logos: Fix for XƎTEX logo if graphics is not loaded. 568
Logos: Improved CSS. 566
Logos: Made robust. 566
fcolorminipage: Fix: Horiz white space. 950
Fix: No longer requires xifthen. . 532
fminipage: Fix: Horiz white space. 546, 547
LWR@blocktextcurrentfont: Added print version. 557
v0.63
\LWR@HTMLLatexCmd: ujarticle and related: Compile options. 247
\LWR@LwarpStart: Fixes for xeCJK. 370
\LWR@atbeginverbatim: Fix for xeCJK. 386
\LWR@checkloadbefore: Added. . . . 196
\LWR@checkloadfilename: Added to reduce number of lwarp-* files. 223
\LWR@checkloadnever: Added. 196
\LWR@compileuplatex: Added. 244
\LWR@createautosec: Fix for xeCJK. 357
\LWR@earlyclassloadnever: Added. 197
\LWR@filestart: Fix: Break ligature for luatexko. 368
\LWR@firstoffour: Added. 209
\LWR@htmlclosecomment: Fix: Break ligature for luatexko. 323
\LWR@isolate: Fix for xeCJK. 208
\LWR@notltjloadafter: Added more classes. 195
Added. 195
\LWR@subhtmlelementclass: Fix for xeCJK. 325
\LinkHome: Fix: Print version. . . . 316
\linkhomename: Added. 316
General: 2018/12/03 1
lwarp.css: Added css for vertical writing. 249
lwarp.css: Improved css for mdframed. 249
amsthm, mdframed: Fix for enforced load order. 593
emumitem: v3.6: Nullifiy \DrawEnumitemLabel. 672
everyhook: Fix for bxjs* classes. . 220
geometry: Fix for bxjs* classes. . 220
mdframed: Avoid thin rules. . . . 783
mdframed: Improved font control. 786–788
stfloats: Adapted to ltj* classes. . 876
xpinyin: Added. 958
zhlineskip: Added. 962
Added pTEXsupport. 194
Docs: \linkhomename. 113
Docs: \sidetocname. 115
Fix: Default \LWR@mdfive. 206
Improved titles. 786
pTEX: Encoding. 206
pTEX: Load upquote. 208
pTEX: No newunicodechar. 207
LWR@BlockClassWP: Fix for xeCJK. . 328
v0.64
\LWR@HTMLLatexCmd: utarticle and related: Added. 247
\LWR@checkloadfilename: Prevented bitfield, doublespace, newthm, rplain, si. 223
\LWR@section: Support for ujarticle and related. 361
\enskip: Made robust. 560
\qquad: Made robust. 560
\quad: Made robust. 560
\theHTMLTitleSeparator: Added utarticle and related. 366
General: 2018/12/08 1
addlines: Updated to v0.3. 581
biblatex: Added patch for CTEX. . 613

bsheaders: Added. 622
gmeometric: Added. 720
marginal: Added. 779
rmpage: Added. 847
scrlayer-scrpage: Fixes. 856
scrlayer: Fixes. 855
scrpage2: Added. 857
ujarticle and related: Improved \today. 570
Added utarticle and related. . . . 570
v0.65
\LWR@LwarpEnd: Improved CSS for page layout. 373
\LWR@LwarpStart: Improved CSS for page layout. 372
\LWR@PreloadedPackage: \AtBeginDocument to avoid option clashes. 525
\LWR@hyperindexrefnullified: Added \textsi. 484
\LWR@includegraphicsb: graphics: Added \includegraphics alt key. 726, 729
\LWR@newhtmlfile: Error if duplicate file name. 352
Improved CSS for page layout. 351, 354
\LWR@nullfonts: Added \sishape. . 551
Added \textsi. 551
\LWR@restoreorigformatting: Added \sishape. 487
Fix: tabular*. 487
\enskip: Changed to Unicode EN SPACE. 560
\quad: Changed to Unicode EM SPACE. 560
\sishape: Added \sishape. 555
\textsi: Added. 549
General: 2018/12/22 1
lwarp.css: Added \sishape, \textsi. 249
lwarp.css: Improved CSS for page layout. 249
lwarp.css: Improved CSS for quotations. 249
lwarp.css: SideTOCto left for improved \marginpars. 249
lwarp_formal.css: SideTOCto left for improved \marginpars. . . . 282
lwarp_sagebrush.css: SideTOCto left for improved \marginpars. . 277
bounddvi: Added. 619
embrac: Added. 669
footnoterange: Added. 711
gentombow: Added. 717
geometry: Fix for bxjs* classes. . 220
graphics: Added \includegraphics alt key. 529, 721, 723, 725
lltjext: Added. 767
multicolrule: Added. 798
multicol: Added \docolaction. . 797
plarydshln: Added. 835
plextarydshln: Added. 836
plextcolortbl: Added. 836
plext: Added. 835
pxatbegshi: Added. 840
pxeveryshi: Added. 840
pxftnright: Added. 840
pxjahyper: Added. 841
tascmac: Added. 886
versonotes: Added. 935
Added \sishape. 239
Added early checks for jarticle, tarticle, and related. 197
Fix for \rensuji. 570
Fix space between class and id. . 328
tabular: Added support for plext. . 451
Fix: tabular*. 451
Fix: Rule color. 453
minipage: Refactored to later allow Japanese <t/y> argument. 539
LWR@figcaption: Uses <figurecaption> instead of <figcaption>. 472
v0.66
\@mpfootnotetext: Improved HTML formatting. 342
\IgnoreMinipageWidths: Added, . . 539
\LWR@@footnotetext: Improved HTML formatting. 341
\LWR@LwarpStart: Fix: TOC, LOF, LOT links. 372
\LWR@checkloadfilename: Prevented colortab, epsf, hyper, picinpar, picins, sistyle, ucs. 223
\LWR@closeparagraph: Fix: Combined span, tabular, and lateximage. 332
Improved HTML formatting. . . . 332
\LWR@closeparagraph@br: Factored. 331
\LWR@fboxstyle: Use current text color. 544
\LWR@filenamenoblanks: Fix: Section names detokenized. 347
Fix: Section names with macros. 348
Fix: Section names with percent. 348
Improved file name generation. . 347
Limits filename length. 349
\LWR@findcurrenttextcolor: Fix: Color if xcolor not loaded. . . . 557

\LWR@htmlfileref: No longer use zref. 458
\LWR@htmlsectionfilename: Sanitize underscores. 315
\LWR@includegraphicsb: Improved HTML formatting. 725
\LWR@indentHTML: Added. 321
\LWR@lateximagedepthref: No longer use zref. 458
\LWR@lateximagenumberref: No longer use zref. 459
\LWR@lwarplabel: No longer use zref. 459
\LWR@nameref: No longer use zref. . 458
\LWR@nullfonts: Logos. 553
\LWR@openparagraph: Improved HTML formatting. 331
\LWR@section: Fix: TOC, LOF, LOT links. 362
Improved HTML formatting. 362
\LWR@setexparray: Fix with \par. . 310
\LWR@setref: No longer use zref. . . 458
\LWR@simplifyname: Added. 346
\LWR@startref: No longer use zref. 461
\LWR@stoppars: Improved HTML formatting. 334
\LWR@subhtmlelementclass: Improved HTML formatting. . . 325
\LWR@subhyperrefclass: Improved HTML formatting. 464
\LWR@subinlineimage: Improved HTML formatting. 465
\LWR@writeconf: Added ImagesDirectory and ImagesName. 248
\LinkHome: Fix: Document cross-references. 316
\UseMinipageWidths: Added, ... 539
\fbox: Fix: Removed extra space. . . 544
\hyperindexref: Fix: Long index entries. 484
\minipagefullwidth: Made \global. 538
\rotatebox: Improved HTML formatting. 731
\rule: Improved HTML formatting. . 564
\scalebox: Improved HTML formatting. 731
\textgreater: Made robust. 313
\textless: Made robust. 313
General: 2019/02/08 1
LWR@currentautosec: Fix for LOF, LOTfloat in home page. 358
lwarp.css: Added niceframe. . . 249
lwarp.css: Improved CSS for definition lists. 249
lwarp_formal.css: Improved CSS for table notes. 282
lwarp_one_limage.txt: Image directory and prefix. 288
acronym: Fix for acronym in caption. 579
acronym: No longer uses zref. . . 579
ar: Added. 598
caption: Fix for options clash. . . 227
ed: Added. 668
extramarks: Updated to v3.10. . . 679
fancyhdr: Updated to v3.10. . . . 685
kotexutf: Patch for references. . . 572
memoir: Docs re: version numbers. 165
multicolrule: Updated for v1.2. . 798
nameauth: Added. 803
register: Verified for v1.9. 844
subcaption: Added. 877
tocbasic: Updated to v3.26a. . . . 912
truncate: Added. 926
zref: No longer used. 222
lwarpmk: Added ImagesDirectory and ImagesName. 290
lwarpmk: Fix for **cleanlimages**. . 290
Added early checks for colortab, epsf, hyper, picinpar, picins, sistyle, ucs. 197
Added option ImagesDirectory. 213
Added option ImagesName. 213
Added support for indentfirst. . . 335
Docs: Updated Converting an existing document. 106
Fix: Minipages inside multicols. 797
Improved HTML formatting. . 681, 688
Package dates added where possible. 573
Sanitize filenames. 216
tabular: Fix: Minipages inside tabular. 454
lateximage: Adds \BaseJobname for multiple projects. 519
Improved HTML formatting. . . . 520
minipage: Honor \LWR@forceminipagefullwidth. 540
v0.67
\FilenameNullify: Added. . . . 554, 557
\FilenameSimplify: Added. . . 346, 351
\LWR@doequation: xfakebold: Added support. 506
\LWR@doubledollar: xfakebold: Added support. 500
\LWR@filenamenoblanks: Improved file name generation. 347

\LWR@lookforpackagename:
easyReview: Supported. 224
\LWR@nullfonts: Add'l symbols. . . 551
\LWR@simplifycustom: Added. 346
\LWR@subsingledollar: xfakebold:
Added support. 494, 498, 499
General: 2019/02/23 1
academicons: Added. 576
bbding: Added. 608
changes: Added. 629
color: Fix for version number. . . 658
dingbat: Added. 665
eurosym: Added. 678
fitbox: Added. 693
fontawesome5: Added. 708
fontawesome: Added. 707
foreign: Added. 712
gloss: Added. 717
karnaugh-map: Added. 751
marvosym: Added. 780
multicap: Added. 796
nomencl: Added. 808
notes: Added. 809
pifont: Added. 834
struktex: Added. 876
textcomp: Nullify in filenames. . 891
typicons: Added. 928
umoline: Added. 930
xfakebold: Added support. . . . 492
xfakebold: Added. 953
xunicode: Nullify in filenames. . 961
AMS environments: Added
xfakebold support. 587
eqnarray: xfakebold: Added support. 512
v0.68
\LWR@@footnotetext: Factored for
multiple foot boxes. 340
\LWR@checkloadfilename: Prevented
alg, algorithmic, fncylab,
pdfcprot. 223
\LWR@printpendingfootnotes:
Factored for multiple footnote
boxes. 343
\LWR@tabular@warpprintonly:
Added. 451
General: 2019/03/05 1
bigfoot: Added. 615
fnpara: Added. 706
footnotebackref: Added. 711
hyperref: Fix for options with
braces. 738
layouts: Added. 756
listings: Fix for listings v1.7. . . 767
longtable: Improved error
handling. 770
manyfoot: Added. 777
niceframe: Added. 807
perpage: Added. 832
showtags: Added. 863
tablefootnote: Added. 885
threeparttablex: Added. 898
threeparttable: Fix for caption
type. 897
lwarpmk: Improved error handling
if incomplete compile. 290
Prevented alg, algorithmic,
fncylab, pdfcprot. 197
tabular: Fix: \warpprintonly inside
tabular. 453

Index of Objects

This is an index of macros, environments, booleans, counters, lengths, packages, classes, options, keys, files, and various other programming objects. Each is listed by itself, and also by category. In some cases, they are further subdivided by [class].

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition.

Symbols

\$ *493*
\& *313*, 7094
\(. 9526
*-images.txt (file) *519*
*_html.aux (file) *350*, *456*, *458*, *519*
*_html.lof (file) *471*
*_html.lot (file) *471*
*_html.tex (file) *242*
\, ... *125*
--shell-escape (option) *107*
\@@@setcpageref 10307
\@@@setcref 10270
\@@@setcrefrange 10284
\@author *375*
\@begintheorem 6760
\@biblabel 9184
\@captype 8802
\@chapcntformat 5963
\@currentHref 8637
\@currentlabelname 8496
\@date *375*
\@dlbfloat 8768
\@donoparitem 6786
\@endtheorem 6772
\@ensuredmath 9536
\@float 8768
\@fnsymbol 6549
\@footnotetext 5543
\@include 1057
\@item 6799
\@makecaption 8823
\@makefnmark 5510
\@makefntext 5509
\@maketitle 56, 6572
\@mklab 6780
\@mpfootnotetext 5545
\@nbitem 6866
\@opargbegintheorem 6766
\@partcntformat 5964
\@partnameformat 5965
\@rowc@lors 7415
\@rowcolors 7414
\@seccntformat 5961
\@starttoc 8936
\@textsubscript 10955
\@textsuperscript 10951
\@title *375*
\@wrglossary 9128
\@wrindex 9117
\[. 9526
\\ *559*
$ *499*
$$ *499*
2in1 (package) *573*
2up (package) *573*

A

a4 (package) *573*
a4wide (package) *574*
a5comb (package) *574*
abstract (environment) 6635
abstract (package) *135*, *574*
\abstractname *116*, 6634
academicons (package) *576*
accsupp (package) *577*
acro (package) *577*
acronym (package) *579*
\addcontentsline 8887
addlines (package) *581*
\AddSubtitlePublished 6600
adjmulticol (package) *580*
Adobe (program) *83*
\affiliation 6452
afterpage (package) *581*
algorithm2e (package) *581*
algorithmicx (package) *163*, *585*
align (environment) 131
align* (environment) 158
alignat (environment) 239
alignat* (environment) 266
alltt (package) *586*
\AmS 11243

amsmath (package) 586
amsthm (package) 593
\and 375
anonchap (package) 596
anysize (package) 597
appendix (package) 135, 597
ar (package) 598
arabicfront (package) 599
array (package) 599
\arrayrulecolor 7422
\arrayrulecolornexttoken 7422
arydshln (package) 600
AsciiDoc (program) 83
AsciiDoctor (program) 83
Asciidoctor-LaTeX (program) 83
asymptote (package) 158, 602
atbegshi (package) 603
attachfile (package) 603
attachfile2 (package) 604
\attrib 166, 384, 933
\attribution 6645
authblk (package) 135, 606
\author 122, 375
autosec 356
axessibility (package) 607
axodraw2 (package) 607

B

babel (package) 167
\backmatter 5939
backref (package) 608
balance (package) 608
\BaseJobname 4849
BaseJobname (option) 112, 213
bbding (package) 608
\bfseries 10934
biblatex (package) 613
\bibliography 9175
\BibTeX 11238
bibunits (package) 614
bigdelim (package) 163, 614
bigfoot (package) 615
bigstrut (package) 616
bitpattern (package) 616
BlockClass (environment) 5218
\BlockClassSingle 5232
blowup (package) 616
booklet (package) 617
bookmark (package) 617
booktabs (package) 618
boolean:
  CombineHigherDepths 115, 346
  FileSectionNames 116, 314
  FormatEPUB 173, 235
  FormatWP 175, 235
  HTMLDebugComments 116, 230
  LWR@amsmultline 509
  LWR@copiedsidetoc 476
  LWR@doingapar 330
  LWR@doingcmidrule 400
  LWR@doingstartpars 330
  LWR@doingtbrule 400
  LWR@dynamicmath 312
  LWR@emptyatbang 401
  LWR@exitingtabular 446
  LWR@forceminipagefullwidth 538
  LWR@freezethisautoid 470
  LWR@indisplaymathimage 492
  LWR@infloatrow 724
  LWR@intabularmetadata 401
  LWR@isstartingequation 517
  LWR@mathmacro 311
  LWR@minipagefullwidth 538
  LWR@minipagethispar 539
  LWR@opttablecol 413
  LWR@origmathjax 212
  LWR@skipatbang 401
  LWR@skippingmcolrowcell 401
  LWR@skippingmrowcell 401
  LWR@starredlongtable 440
  LWR@startedrow 400
  LWR@tableparcell 400
  LWR@tabularcelladded 400
  LWR@tabularmutemods 447
  LWR@tracinglwarp 230
  LWR@validtablecol 413
  LWR@verbtags 386
  LWR@xfakebold 492
  mathjax 212
  usingOSWindows 211
  warpingHTML 212
  warpingprint 212
  WPMarkFloats 176, 235
  WPMarkLOFT 177, 236
  WPMarkMath 177, 236
  WPMarkMinipages 177, 236
  WPMarkTOC 177, 236
  WPTitleHeading 178, 236
bophook (package) 619
bounddvi (package) 619
boxedminipage2e (package) 620
\boxframe 190
breakurl (package) 620
breqn (package) 621
bsheaders (package) 622
BVerbatim (environment) 222
bxpapersize (package) 622
bytefield (package) 623

C

calc (package) 220
cancel (package) 623

canoniclayout (package) 624
capt-of (package) 474
caption (package) 163, 227, 474, 624
\caption@begin 8868
\caption@end 8868
\captionlistentry 8872
\captionof 8903
\CaptionSeparator 8822
cases (package) 627
center (environment) 10062
\centering 10086
\centerline 10105
changebar (package) 628
changepage (package) 628
changes (package) 629
chappg (package) 630
\chapter 6165
chapterbib (package) 630
chemfig (package) 630
chemformula (package) 632
chemgreek (package) 636
chemmacros (package) 637
chemnum (package) 655
chkfloat (package) 656
chngpage (package) 656
cite (package) 656
CJK (package) 657
CJKutf8 (package) 657
class (key) [Gin] 725
class:
  internet 82
  komascript 165
  memoir 165, 166, 934
\cleardoublepage 11115
\clearpage 11115
cleveref (package) 132, 533
clrdblpg (package) 657
cm-super (package) 107
cmap (package) 108
cmdtrack (package) 657
color (package) 156, 658
\colorbox 73
\colorboxBlock 86, 10167
colortbl (package) 658
CombineHigherDepths (boolean) . . 115, 346
comment (package) 218
\ConTeXt 11235
continue (package) 660
copyrightbox (package) 660
counter:
  FileDepth 115, 345
  FootnoteDepth 116, 339
  footnoteReset 339
  lofdepth 480
  lotdepth 480
  LWR@cellcolordepth 432
  LWR@currentautosec 358
  LWR@externalfilecnt 492
  LWR@hdashedlines 400
  LWR@hlines 400
  LWR@htmlfilenumber 314
  LWR@latestautopage 472
  LWR@lateximagedepth 514
  LWR@lateximagenumber 514
  LWR@LIpage 514
  LWR@midrulecounter 424
  LWR@minipagedepth 538
  LWR@nextautoid 471
  LWR@nextautopage 471
  LWR@nextequation 503
  LWR@prevFileDepth 357
  LWR@previousautopagelabel 349
  LWR@spandepth 329
  LWR@startingequation 517
  LWR@tablecolspecindex 402
  LWR@tablecolspecwidth 402
  LWR@tableLaTeXcolindex 402
  LWR@tabletotalLaTeXcols 402
  LWR@tabletotalLaTeXcolsnext . . . 402
  LWR@tabularDepth 401
  LWR@tabularpardepth 401
  LWR@thisautoid 469
  LWR@thisautoidWP 470
  SideTOCDepth 115, 478
  tocdepth 115
\cpagerefFor 10306
crop (package) 661
\CSSFilename 116, 119, 5463
\CustomizeMathJax 5787, 5812
cuted (package) 661
cutwin (package) 661

D

\date 122
dblfloatfix (package) 662
dblfnote (package) 662
dcolumn (package) 663
\DeclareGraphicsExtensions 2
dejavu (package) 107
description (environment) 6941
diagbox (package) 663
dingbat (package) 665
\displaymathnormal . . 153, 491, 508, 9719
\displaymathother . . . 153, 491, 508, 9730
ditaa (package) 172
\dotfill 11034
\doublerulesepcolor 7424
\doublerulesepcolornexttoken 7424
dprogress (package) 665
draftcopy (package) 666
draftfigure (package) 666

draftwatermark (package) *667*
dvipdfm (option) *109*, *215*
dvipdfmx (option) *109*, *215*
dvips (option) *109*, *215*

E

easy-todo (package) *667*
ebook (package) *668*
ed (package) *668*
ellipsis (package) *669*
embrac (package) *669*
\emph 10633
emptypage (package) *670*
\end@dlbfloat 8785
\end@float 8785
endfloat (package) *670*
endheads (package) *671*
endnotes (package) *135*, *671*
\enlargethispage 11114
\enskip *560*, 11060
enumerate (environment) 6922
enumerate (package) *672*
enumitem (package) *672*
environ (package) *222*
environment:
  fminipage *128*
  lateximage *513*
  picture *536*
  titlepage *122*
  titlingpage *122*
  warpall *121*
  warpHTML *118*, *120*
  warpprint *118*, *121*
environments:
  abstract 6635
  align 131
  align* 158
  alignat 239
  alignat* 266
  BlockClass 5218
  BVerbatim 222
  center 10062
  description 6941
  enumerate 6922
  eqnarray 9779
  equation 9697
  equation* 9705
  fcolorminipage 166, 10208
  flalign 185
  flalign* 212
  flushleft 10078
  flushright 10070
  fminipage 10572
  gather 77
  gather* 104
  itemize 6916
  lateximage 9929, 10057
  list 6886
  longtable 4
  LWR@BlockClassWP 5259
  LWR@blocktextcurrentfont 10926, 10983
  LWR@displaymathnormal 9566
  LWR@displaymathother 9571
  LWR@equationother 9585
  LWR@figcaption 8837
  LWR@nestspan 5071
  math 9565
  minipage 10391
  multline 20
  multline* 48
  picture 10366
  quote 6661
  tabbing 6745
  tabular 8369
  thebibliography 9185
  theindex 9093
  titlepage 6469
  titlingpage 14
  verbatim 6735
  verse 2, 6676
  warpall 801
  warpHTML 802
  warpprint 802
epigraph (package) *673*
epsfig (package) *674*
epstopdf (package) *157*, *675*
epstopdf (program) *155*, *528*
epstopdf-base (package) *675*
eqnarray (environment) 9779
equation (environment) 9697
equation* (environment) 9705
errata (package) *676*
eso-pic (package) *677*
\etalchar *136*
etoolbox (package) *194*
eurosym (package) *678*
everyhook (package) *220*
everypage (package) *678*
everyshi (package) *679*
expl3 (package) *220*
extramarks (package) *679*

F

fancybox (package) *129*, *680*
fancyhdr (package) *685*
fancyref (package) *685*
fancytabs (package) *686*
fancyvrb (package) *687*
\fbox *128*, 10546
\fboxBlock *128*, 10554
\fcolorbox 103, 10169
\fcolorboxBlock 126, 10206

fcolorminipage (environment) . 166, 10208
figcaps (package) 692
figsize (package) 693
file:
*-images.txt 519
*_html.aux 350, 456, 458, 519
*_html.lof 471
*_html.lot 471
*_html.tex 242
glyphtounicode.tex 108
lwarp.css 120, 249
lwarp.ist 147, 286
lwarp.xdy 148, 287
lwarp_baseline_marker.eps 493
lwarp_baseline_marker.png 493
lwarp_formal.css 282
lwarp_mathjax.txt 288
lwarp_one_limage.cmd 287
lwarp_sagebrush.css 277
lwarp_tutorial.txt 92
lwarpmk.conf 248
lwarpmk.lua 183
project.css 120
project.lwarpmkconf 249
sample_project.css 120, 286
tutorial.tex 92
filecontents (package) 221
FileDepth (counter) 115, 345
\FilenameLimit 116, 5653
\FilenameNullify 131, 10899, 10984
\FilenameSimplify 131, 5674, 5813
FileSectionNames (boolean) 116, 314
fitbox (package) 693
fix2col (package) 694
fixme (package) 167, 694
fixmetodonotes (package) 695
flafter (package) 696
\flagverse 934
flalign (environment) 185
flalign* (environment) 212
Flare (program) 83
flippdf (package) 696
float (package) 163, 696
floatflt (package) 698
floatpag (package) 699
floatrow (package) 164, 699
fltrace (package) 704
\flushbottom 4987
flushend (package) 704
flushleft (environment) 10078
flushright (environment) 10070
fminipage (environment) 128, 10572
fnbreak (package) 705
fncychap (package) 705
fnlineno (package) 706
fnpara (package) 706
fnpos (package) 706
fontawesome (package) 707
fontawesome5 (package) 708
fontenc (package) 108, 709
fontspec (package) 108
footmisc (package) 709
footnote (package) 710
footnotebackref (package) 711
FootnoteDepth (counter) 116, 339
footnotehyper (package) 711
footnoterange (package) 711
footnoteReset (counter) 339
footnpag (package) 712
\ForceHTMLPage 134, 5914
\ForceHTMLTOC 135, 5920
foreign (package) 712
forest (package) 712
FormatEPUB (boolean) 173, 235
FormatWP (boolean) 175, 235
\framebox 10522
framed (package) 713
FrameMaker (program) 83
\frontmatter 5936
ftnright (package) 715
fullminipage (package) 715
fullpage (package) 716
fullwidth (package) 716
\fup 10959
\fussy 4989
fwlw (package) 716

G

gather (environment) 77
gather* (environment) 104
GELLMU (program) 82
gentombow (package) 717
geometry (package) 219, 717
gettitlestring (package) 220
[Gin]:
class (key) 725
GladTeX (program) 82
gloss (package) 136, 717
glossaries (package) 136, 718
GlossaryCmd (option) . . . 112, 136, 215, 718
glyphtounicode.tex (file) 108
gmeometric (package) 720
graphics (package) 154, 720
graphicx (package) 154, 733
grffile (package) 156, 733
grid (package) 733
grid-system (package) 734
gridset (package) 734

H

hang (package) 734

hanging (package) *736*
Hevea (program) *82*
\hfill 11030
\HomeHTMLFilename 4851
HomeHTMLFilename (option) . *109*, *113*, *214*
\href 8665
\hrulefill 11032
\hskip *125*
\hspace *125*, *560*, 11068, 11098, 11104
htlatex (program) *82*
\HTMLAuthor *117*, *123*, 5489
HTMLDebugComments (boolean) *116*, *230*
\HTMLDescription *117*, *123*, 5494
\HTMLentity 4833
\HTMLFilename 4850
HTMLFilename (option) *109*, *113*, *214*
\HTMLFirstPageTop *117*, 5451
htmlglossary (option) [lwarpmk] . *136*, *718*
HTMLIndexCmd (option) *111*, *215*
\HTMLLanguage *116*, 6235
HTMLLatexCmd (option) *109*, *169*, *214*
\HTMLleftmargini (length) . . *166*, *385*, *934*
\HTMLPageBottom *117*, *375*, 5457
\HTMLPageTop *117*, 5454
\HTMLTitle *116*, *123*, 5484
\HTMLTitleAfterSection *116*, 6258
\HTMLTitleBeforeSection *116*, 6253
\HTMLunicode 4841
\HTMLvleftskip (length) . . . *166*, *385*, *934*
hypcap (package) *737*
hypdestopt (package) *737*
\hyperindexref 9153
hypernat (package) *737*
hyperref (package) *132*, *463*, *737*
\hypertoc 9032
\hypertocfloat 9054
hyperxmp (package) *743*
hyphenat (package) *743*

I

idxlayout (package) *744*
\if@titlepage 6447
ifoddpage (package) *744*
ifplatform (package) *194*
\IgnoreMinipageWidths . . . *127*, *537*, 10381
ImagesDirectory (option) *213*
ImagesName (option) *213*
imakeidx (package) *745*
\include 1057
\includegraphics 284
indentfirst (package) *335*
InDesign (program) *83*
index (package) *749*
\InlineClass 5243
\inlinemathnormal *153*, *491*, 4826
\inlinemathother *153*, *491*, 4822
inputenc (package) *108*
inputenx (package) *108*
internet (class) *82*
intopdf (package) *750*
itemize (environment) 6916
\itshape 10939

K

karnaugh-map (package) *751*
\kern *125*
key:
  [Gin]:
    class *725*
keyfloat (package) *164*, *754*
komascript (class) *165*
kotex (package) *168*
kvoptions (package) *211*

L

\l@chapter 9073
\l@figure 9084
\l@paragraph 9082
\l@part 9072
\l@section 9079
\l@subparagraph 9083
\l@subsection 9080
\l@subsubsection 9081
\l@table 9085
\LaTeX 11195
LaTeX2HTML (program) *82*
\LaTeXe 11195
lateximage (environment) *513*, 9929, 10057
\LateximageFontScale 9851
\LateximageFontSizeName 9850
latexmk (option) *109*, *113*, *215*
latexmk (program) *170*
LatexmkIndexCmd (option) *111*, *215*
LaTeXML (program) *82*
layaureo (package) *756*
layout (package) *756*
layouts (package) *756*
leading (package) *759*
\leftline 10104
length:
  \HTMLleftmargini *166*, *385*, *934*
  \HTMLvleftskip *166*, *385*, *934*
  \LWR@cmidrulewidth *424*
  \LWR@heavyrulewidth *424*
  \LWR@lightrulewidth *424*
  \LWR@minipageheight *538*
  \LWR@minipagewidth *538*
  \LWR@tempheight *560*
  \LWR@tempraise *560*
  \LWR@tempwidth *560*
  \LWR@thiscmidrulewidth *424*
  \VerbatimHTMLWidth *386*

\vleftmargini 166, 385, 934
\vleftskip 166, 385, 934
letltxmacro (package) 194
letterspace (package) 759
lettrine (package) 760
LibreOffice (program) 83
\linebreak 11108
lineno (package) 761
\LinkHome 4909, 4914
\linkhomename 113, 4906
Linux (program) 120, 209
lips (package) 763
list (environment) 6886
listings (package) 763
\listof 8990
\listoffigures 8964
\listoftables 8977
lltjext (package) 767
lmodern (package) 107, 108
lofdepth (counter) 480
longtable (environment) 4
longtable (package) 161, 768
lotdepth (counter) 480
lscape (package) 771
ltablex (package) 771
ltcaption (package) 772
ltxgrid (package) 772
ltxtable (package) 773
lua-check-hyphen (package) 773
lua-visual-debug (package) 773
luacolor (package) 773
\LuaLaTeX 11224
LuaLaTeX (program) [requirement] 86
\LuaTeX 11224
luatodonotes (package) 167, 774
lwarp (package) 109
lwarp-patch-komascript (package) . . 964
lwarp-patch-memoir (package) 966
lwarp.css (file) 120, 249
lwarp.ist (file) 147, 286
lwarp.xdy (file) 148, 287
lwarp_baseline_marker.eps (file) 493
lwarp_baseline_marker.png (file) 493
lwarp_formal.css (file) 282
lwarp_mathjax.txt (file) 288
lwarp_one_limage.cmd (file) 287
lwarp_sagebrush.css (file) 277
lwarp_tutorial.txt (file) 92
[lwarpmk]:
htmlglossary (option) 136, 718
printglossary (option) 136, 718
lwarpmk (option) 112, 214, 290
lwarpmk (program) 183, 290
lwarpmk epstopdf (program) 155, 528
lwarpmk pdftosvg (program) 155, 528
lwarpmk.conf (file) 248
lwarpmk.lua (file) 183
\lwarpsetup 665
\LWR@@footnotetext 5513
\LWR@@printpendingfootnotes 5578
\LWR@addbaselinemarker 9282
\LWR@addcdashline 7693
\LWR@addcmidruletrim 7659
\LWR@addcmidrulewidth 7690
\LWR@addcompilecmd 1436
\LWR@addformatwpalignment 7709
\LWR@addleftmostbartag 7494
\LWR@addmathjax 9634
\LWR@addmulticolvertrulecolor . . . 7968
\LWR@addrulewidth 7664
\LWR@addtabularcellcolor 7837
\LWR@addtabularhrulecolor 7737
\LWR@addtabularrowcolor 7722
\LWR@addtabularrulecolors 7783
\LWR@afterendverbatim 6718
\LWR@amsmathbody 9916
\LWR@amsmathbodynumbered 9922
LWR@amsmultline (boolean) 509
\LWR@applyxfakebold 9274
\LWR@atbeginverbatim 6699
\LWR@backgroundcolor 36
\LWR@beginhideamsmath 9764
LWR@BlockClassWP (environment) . . . 5259
LWR@blocktextcurrentfont (environment) 10926, 10983
\LWR@botnavigation 4932
LWR@cdashlines 424
LWR@cellcolordepth (counter) 432
\LWR@cellHTMLcolor 7419
\LWR@checkloadbefore 59
\LWR@checkloadfilename 909
\LWR@checkloadnever 73
\LWR@clearmidrules 7574
\LWR@closeparagraph 5357
\LWR@closeparagraph@br 5347
\LWR@closeprevious 4959
\LWR@closetabledatacell 7053
\LWR@cmidrulewidth (length) 424
LWR@colafterspec 402
LWR@colatspec 402
LWR@colbangspec 402
LWR@colbarspec 402
LWR@colbeforespec 402
\LWR@columnHTMLcolor 7417
\LWR@columnspeclookahead 7172
\LWR@compilecmd 1433
\LWR@compileuplatex 1465
\LWR@convertto 604
LWR@copiedsidetoc (boolean) 476
\LWR@copyfile 1092

\LWR@createautosec 5945
LWR@currentautosec (counter) 358
\LWR@currentcss 5462
\LWR@currenttextcolor 10970
\LWR@customizedMathJax 5786
\LWR@customizeMathJax 5792
\LWR@descitem 6928
LWR@displaymathnormal (environment) 9566
LWR@displaymathother (environment) 9571
\LWR@docdashline 7623
\LWR@docmidrule 7607
\LWR@doequation 9647
\LWR@doindexentry 9136
LWR@doingapar (boolean) 330
LWR@doingcmidrule (boolean) 400
LWR@doingstartpars (boolean) 330
LWR@doingtbrule (boolean) 400
\LWR@domulticolumn 8006
\LWR@doubledollar 9480
LWR@dynamicmath (boolean) 312
\LWR@earlyclassloadnever 89
\LWR@earlyloadnever 79
LWR@emptyatbang (boolean) 401
\LWR@endfloatalignment 8818
\LWR@endhideamsmath 9772
\LWR@endofline 11041
\LWR@ensuredoingapar 5323
LWR@equationother (environment) . . 9585
\LWR@equationtag 9902
LWR@exitingtabular (boolean) 446
\LWR@expandableformatted 1154
\LWR@expandableformattedenv 1179
LWR@externalfilecnt (counter) 492
\LWR@fboxstyle 10540
LWR@figcaption (environment) 8837
\LWR@filenamenoblanks 5685
\LWR@filestart 6267
\LWR@findcurrenttextcolor 10973
\LWR@findword 906
\LWR@firstoffour 619
\LWR@floatalignment 8804
\LWR@floatalignmentname 8803
\LWR@floatbegin 8736
\LWR@floatend 8770
\LWR@floatstyle 2
\LWR@footnotebox 5508
\LWR@footnotetext 5542
LWR@forceminipagefullwidth (boolean) 538
\LWR@forceminwidth 10529
\LWR@forcenewpage 4976
\LWR@formatted 1139
\LWR@formattedenv 1169
\LWR@formatting 1138
\LWR@fourthoffour 619
LWR@freezethisautoid (boolean) 470
\LWR@futurenonspacelet 7000
\LWR@FVstyle 56
\LWR@getexparray 4795
\LWR@getmynexttoken 7007
LWR@hdashedlines (counter) 400
\LWR@heavyrulewidth (length) 424
\LWR@hidelatexequation 9620
LWR@hlines (counter) 400
\LWR@HTML@caption@begin 8847
\LWR@HTML@caption@end 8859
\LWR@HTML@Gin@setfile 115
\LWR@HTML@ref 8608
\LWR@htmlblockcomment 5157
\LWR@htmlblocktag 5159
\LWR@HTMLcline 8350
\LWR@htmlclosecomment 5129
\LWR@htmlcomment 5150
\LWR@htmldivclass 5195
\LWR@htmldivclassend 5198
\LWR@htmlelement 5208
\LWR@htmlelementclass 5182
\LWR@htmlelementclassend 5187
\LWR@htmlelementclassline 5201
\LWR@htmlelementend 5211
LWR@htmlfilenumber (counter) 314
\LWR@htmlfileref 8515
\LWR@HTMLhline 8333
\LWR@HTMLLatexCmd 1475
\LWR@htmlmathlabel 9749
\LWR@htmlmulticolumn 8055
\LWR@htmlopencomment 5129
\LWR@htmlrefsectionfilename 4896
\LWR@HTMLsanitize 9854
\LWR@HTMLsanitizeexpand 9871
\LWR@htmlsectionfilename 4861
\LWR@htmlspan 5106
\LWR@htmlspanclass 5114
\LWR@htmltag 5124
\LWR@htmltagc 5061
\LWR@hyperindexrefnullified 9141
\LWR@imagesizebox 114
\LWR@includegraphicsb 133
\LWR@indentHTML 5058
\LWR@indexitem 9105
\LWR@indexnameref 9135
\LWR@indexsubitem 9109
\LWR@indexsubsubitem 9113
LWR@indisplaymathimage (boolean) . . 492
LWR@infloatrow (boolean) 724
\LWR@instertatbangcols 7045
LWR@intabularmetadata (boolean) . . . 401
\LWR@isolate 610
LWR@isstartingequation (boolean) . . 517
\LWR@itemizeitem 6909
LWR@latestautopage (counter) 472

LWR@lateximagedepth (counter) *514*
\LWR@lateximagedepthref 8518
LWR@lateximagenumber (counter) *514*
\LWR@lateximagenumberref 8521
\LWR@lateximagesfile 1054
\LWR@latexmkcmd 1451
\LWR@latexmkdvipdfm 1456
\LWR@latexmkvar 1445
\LWR@lightrulewidth (length) *424*
LWR@LIpage (counter) *514*
\LWR@listitem 6871
\LWR@loadafter 23
\LWR@loadbefore 50
\LWR@loadnever 65
\LWR@longtabledatacaptiontag 8066
\LWR@lookforpackagename 951
\LWR@lwarpconfversion 1427
\LWR@LwarpEnd 6418, 11288
\LWR@lwarplabel 8524
\LWR@LwarpStart 6347, 11288
\LWR@maketitlesetup 33, 6541
LWR@mathmacro (boolean) *311*
\LWR@maybenewtablerow 7426
\LWR@maybeprintpendingfootnotes . 5597
LWR@midrulecounter (counter) *424*
LWR@midrules *423*
LWR@minipagedepth (counter) *538*
LWR@minipagefullwidth (boolean) . . . *538*
\LWR@minipageheight (length) *538*
\LWR@minipagestartpars 11048
\LWR@minipagestoppars 11051
LWR@minipagethispar (boolean) *539*
\LWR@minipagewidth (length) *538*
\LWR@multicolother 7909
\LWR@multicolpartext 7903
\LWR@multicolskip 7915
\LWR@multirowborder 3
\LWR@mynexttoken 6999
\LWR@myshorttoc 8913
\LWR@nameref 8512
LWR@nestspan (environment) 5071
\LWR@new@label 8560
\LWR@newautoidanchor 8791
\LWR@newautopagelabel 5778
\LWR@newhtmlfile 5816
LWR@nextautoid (counter) *471*
LWR@nextautopage (counter) *471*
LWR@nextequation (counter) *503*
\LWR@notltjloadafter 37
\LWR@notmemoirloadafter 34
\LWR@nullfonts 10758
\LWR@nullifycomment 900
\LWR@nullifyNoAutoSpacing 8356
\LWR@nulllistfills 6878
\LWR@opacity 113
\LWR@openparagraph 5329
LWR@opttablecol (boolean) *413*
\LWR@orig@setBold 9272
\LWR@orig@unsetBold 9273
\LWR@origcolspec 7039
\LWR@originname 298
\LWR@originnames 305
LWR@origmathjax (boolean) *212*
\LWR@overline 10965
\LWR@parseaftercolumn 7242
\LWR@parseatcolumn 7182
\LWR@parsebangcolumn 7208
\LWR@parsebarcolumn 7253
\LWR@parsebeforecolumn 7231
\LWR@parsecoloncolumn 7278
\LWR@parseDcolumn 7324
\LWR@parsedrequirepackagenames . . . 899
\LWR@parsenormalcolumn 7303
\LWR@parsepcolumn 7315
\LWR@parsesemicoloncolumn 7299
\LWR@parsetablecols 7330
\LWR@parsewcolumn 7319
\LWR@patcherror 605
\LWR@patchlists 6947
\LWR@pdfencoding 561
\LWR@PreloadedPackage 10109
LWR@prevFileDepth (counter) *357*
LWR@previousautopagelabel (counter) *349*
\LWR@printatbang 7469
\LWR@printbartag 7459
\LWR@printcloselist 6778
\LWR@PrintLatexCmd 1475
\LWR@printlength 881
\LWR@printmccoldata 7918
\LWR@printmccoltype 7861
\LWR@printopenlist 6779
\LWR@printpendingfootnotes 5594
\LWR@printpendingmpfootnotes 5606
\LWR@printthetitle 6493
\LWR@providelength 601
\LWR@ProvidesPackageDrop 1034
\LWR@ProvidesPackagePass 1021
\LWR@pushoneclose 5951
\LWR@quickfile 1051
\LWR@ref@ignorestar 8616
\LWR@rememberbtag 9906
\LWR@replaceEPSSVG 122
\LWR@requesttoc 6411
\LWR@requirepackagenames 898
\LWR@restoreorigaccents 1384
\LWR@restoreorigformatting 9204
\LWR@restoreoriglists 6975
\LWR@rotboxorigin 297
\LWR@rotstyle 105
\LWR@rowHTMLcolor 7418

\LWR@ruleHTMLcolor 7420
\LWR@sanitize 736
\LWR@sanitized 735
\LWR@scalestyle 108
\LWR@secondoffour 619
\LWR@section 5968
\LWR@sectionumber 5942
\LWR@select@html@hspace 11068
\LWR@select@html@nohspace 11098
\LWR@select@print@hspace 11101
\LWR@setexparray 4786
\LWR@setlatestname 8498
\LWR@setOSWindows 653
\LWR@setref 8506
\LWR@shellescapecmd 1428
\LWR@sidetoc 9006
\LWR@simplifycustom 5673
\LWR@simplifyname 5662
\LWR@singledollar 9505
LWR@skipatbang (boolean) *401*
LWR@skippingmcolrowcell (boolean) . . *401*
LWR@skippingmrowcell (boolean) *401*
LWR@spandepth (counter) *329*
LWR@starredlongtable (boolean) *440*
LWR@startedrow (boolean) *400*
LWR@startingequation (counter) *517*
\LWR@startingequationtag 9901
\LWR@startnewdepth 5955
\LWR@startpars 5399
\LWR@startref 8573
\LWR@stoppars 5417
\LWR@stripperiod 8497
\LWR@strresult 7037
\LWR@subaddcmidruletrim 7646
\LWR@subaddtabularcellcolor 7831
\LWR@subcdashline 7610
\LWR@subcmidrule 7592
\LWR@subhtmlelementclass 5164
\LWR@subhyperref 8642
\LWR@subhyperrefclass 8655
\LWR@subhyperreftext 8650
\LWR@subinlineimage 8715
\LWR@sublabel 8537
\LWR@subnewref 8602
\LWR@subsingledollar 9318
\LWR@subtableofcontents 8926
\LWR@subtabularhtmlcolumns 8138
\LWR@syncmathjax 9600
LWR@tablecolspec *401*
LWR@tablecolspecindex (counter) . . . *402*
LWR@tablecolspecwidth (counter) . . . *402*
\LWR@tabledatacolumntag 8229
\LWR@tabledatasinglecolumntag . . . 7508
LWR@tableLaTeXcolindex (counter) . . . *402*
LWR@tableparcell (boolean) *400*
LWR@tabletotalLaTeXcols (counter) . . *402*
LWR@tabletotalLaTeXcolsnext (counter) *402*
\LWR@tabular@warpprintonly 8352
LWR@tabularcelladded (boolean) *400*
LWR@tabularDepth (counter) *401*
\LWR@tabularendofline 7152
\LWR@tabularfinishrow 7106
\LWR@tabularhtmlcolumns 8148
\LWR@tabularleftedge 7499
LWR@tabularmutemods (boolean) *447*
LWR@tabularpardepth (counter) *401*
\LWR@tdaddstyle 7634
\LWR@tdendstyles 7640
\LWR@tdstartstyles 7633
\LWR@tempcolor 10971
\LWR@tempcolortwo 10971
\LWR@tempheight (length) *560*
\LWR@tempraise (length) *560*
\LWR@tempwidth (length) *560*
\LWR@textcurrentcolor 19, 10976
\LWR@textcurrentfont 10905, 10982
\LWR@thirdoffour 619
LWR@thisautoid (counter) *469*
LWR@thisautoidWP (counter) *470*
\LWR@thiscmidrulewidth (length) *424*
\LWR@thiscolspec 7507
\LWR@thisfilename 5656
\LWR@thisnewfilename 5661
\LWR@titlingmaketitle 83, 6592
\LWR@topnavigation 4929
\LWR@traceinfo 1120
LWR@tracinglwarp (boolean) *230*
LWR@trimlrules *423*
LWR@trimrrules *424*
\LWR@unknownengine 1440
LWR@validtablecol (boolean) *413*
LWR@verbtags (boolean) *386*
\LWR@vspace 11105
\LWR@WPcell 7705
\LWR@writeconf 1577
\LWR@xcolorrowHTMLcolor 7416
LWR@xfakebold (boolean) *492*
\LWRopquote 648
\LWRopseq 649
\LWRPrintStack 4937
\LWRsetnextfloat 8831
\LyX 11256

M

Mac OS (program) *120*, *209*
Madcap (program) *83*
magaz (package) *776*
\mainmatter 5932
make (program) *172*
\makebox 10500
makeidx (package) *149*, *776*, *913*

\MakeIndex 11238
makeindex (option) 109, 113, 215
makeindex (program) 147
makeindexStyle (option) . . . 109, 147, 213
\makelabel 390
\maketitle 47, 122, 6553
manyfoot (package) 777
marginal (package) 779
marginfit (package) 779
marginfix (package) 779
marginnote (package) 780
\marginpar 126, 344, 5618
\marginparBlock 126, 344, 5629, 5646
\markboth 4984
\markright 4985
marvosym (package) 780
math (environment) 9565
\mathimagename 117, 9264
MathJax (program) 151, 152, 489, 490
MathJax (program) [requirement] 86
mathjax (boolean) 212
mathjax (option) 109, 113, 213
mathsvg (option) 109, 113, 212
\mbox 10497
mcaption (package) 781
\mcolrowcell 8304
mdframed (package) 130, 781
\mdseries 10933
memhfixc (package) 790
memoir (class) 165, 166, 934
metalogo (package) 790
mhchem (package) 791
microtype (package) 219, 793
midfloat (package) 794
midpage (package) 794
\MiKTeX 11255
minipage (environment) 10391
\minipagefullwidth 10379
morefloats (package) 794
moreverb (package) 795
mparhack (package) 796
\mrowcell 8301
MS-Windows (program) 120, 209
multicap (package) 796
multicol (package) 796
multicolrule (package) 798
\multicolumnrow 39, 8171
\multirow 798
multirow (package) 798
multitoc (package) 801
multline (environment) 20
multline* (environment) 48
musicography (package) 801

N

nameauth (package) 803
\Nameref 8634
\nameref 8625
nameref (package) 804
natbib (package) 804
nccfancyhdr (package) 805
needspace (package) 806
newclude (package) 166
\newfloat 4
newfloat (package) 221
\newline 11039
\newpage 11036
\newtheorem 388
newtxmath (package) 154
newunicodechar (package) 108
nextpage (package) 806
nicefrac (package) 154, 807
niceframe (package) 807
\noalign 8322
\nolinebreak 11109
\nolinkurl 8681
nomencl (package) 137, 808
nonfloat (package) 808
nonumonpart (package) 809
\nopagebreak 11113
\nopagecolor 72
nopageno (package) 809
\normalfont 10947
\normalmarginpar 5643
notes (package) 809
notespages (package) 810
nowidow (package) 810
ntheorem (package) 153, 811
\numberline 9027
numindex (option) [tocbibind] 150, 913

O

octave (package) 822
OpenOffice (program) 83
option:
  --shell-escape 107
  [lwarpmk]:
    htmlglossary 136, 718
    printglossary 136, 718
  [tocbibind]:
    numindex 150, 913
  [tocloft]:
    titles 135
  BaseJobname 112, 213
  dvipdfm 109, 215
  dvipdfmx 109, 215
  dvips 109, 215
  GlossaryCmd 112, 136, 215, 718
  HomeHTMLFilename 109, 113, 214
  HTMLFilename 109, 113, 214
  HTMLIndexCmd 111, 215
  HTMLLatexCmd 109, 169, 214

ImagesDirectory 213
ImagesName 213
latexmk 109, 113, 215
LatexmkIndexCmd 111, 215
lwarpmk 112, 214, 290
makeindex 109, 113, 215
makeindexStyle 109, 147, 213
mathjax 109, 113, 213
mathsvg 109, 113, 212
OSWindows 112, 120, 209, 214
pdftotextEnc 112, 214
PrintIndexCmd 109, 214
PrintLatexCmd 109, 169, 214
warpHTML 112, 212
warpprint 112, 212
xindy 109, 113, 215
xindyCodepage 109, 213
xindyLanguage 109, 213
xindyStyle 109, 148, 213
\OSPathSymbol 652
OSWindows (option) 112, 120, 209, 214
overpic (package) 158, 823

P

package:
2in1 573
2up 573
a4 573
a4wide 574
a5comb 574
abstract 135, 574
academicons 576
accsupp 577
acro 577
acronym 579
addlines 581
adjmulticol 580
afterpage 581
algorithm2e 581
algorithmicx 163, 585
alltt 586
amsmath 586
amsthm 593
anonchap 596
anysize 597
appendix 135, 597
ar 598
arabicfront 599
array 599
arydshln 600
asymptote 158, 602
atbegshi 603
attachfile 603
attachfile2 604
authblk 135, 606
axessibility 607
axodraw2 607
babel 167
backref 608
balance 608
bbding 608
biblatex 613
bibunits 614
bigdelim 163, 614
bigfoot 615
bigstrut 616
bitpattern 616
blowup 616
booklet 617
bookmark 617
booktabs 618
bophook 619
bounddvi 619
boxedminipage2e 620
breakurl 620
breqn 621
bsheaders 622
bxpapersize 622
bytefield 623
calc 220
cancel 623
canoniclayout 624
capt-of 474
caption 163, 227, 474, 624
cases 627
changebar 628
changepage 628
changes 629
chappg 630
chapterbib 630
chemfig 630
chemformula 632
chemgreek 636
chemmacros 637
chemnum 655
chkfloat 656
chngpage 656
cite 656
CJK 657
CJKutf8 657
cleveref 132, 533
clrdblpg 657
cm-super 107
cmap 108
cmdtrack 657
color 156, 658
colortbl 658
comment 218
continue 660
copyrightbox 660
crop 661

cuted 661
cutwin 661
dblfloatfix 662
dblfnote 662
dcolumn 663
dejavu 107
diagbox 663
dingbat 665
ditaa 172
dprogress 665
draftcopy 666
draftfigure 666
draftwatermark 667
easy-todo 667
ebook 668
ed 668
ellipsis 669
embrac 669
emptypage 670
endfloat 670
endheads 671
endnotes 135, 671
enumerate 672
enumitem 672
environ 222
epigraph 673
epsfig 674
epstopdf 157, 675
epstopdf-base 675
errata 676
eso-pic 677
etoolbox 194
eurosym 678
everyhook 220
everypage 678
everyshi 679
expl3 220
extramarks 679
fancybox 129, 680
fancyhdr 685
fancyref 685
fancytabs 686
fancyvrb 687
figcaps 692
figsize 693
filecontents 221
fitbox 693
fix2col 694
fixme 167, 694
fixmetodonotes 695
flafter 696
flippdf 696
float 163, 696
floatflt 698
floatpag 699
floatrow 164, 699
fltrace 704
flushend 704
fnbreak 705
fncychap 705
fnlineno 706
fnpara 706
fnpos 706
fontawesome 707
fontawesome5 708
fontenc 108, 709
fontspec 108
footmisc 709
footnote 710
footnotebackref 711
footnotehyper 711
footnoterange 711
footnpag 712
foreign 712
forest 712
framed 713
ftnright 715
fullminipage 715
fullpage 716
fullwidth 716
fwlw 716
gentombow 717
geometry 219, 717
gettitlestring 220
gloss 136, 717
glossaries 136, 718
gmeometric 720
graphics 154, 720
graphicx 154, 733
grffile 156, 733
grid 733
grid-system 734
gridset 734
hang 734
hanging 736
hypcap 737
hypdestopt 737
hypernat 737
hyperref 132, 463, 737
hyperxmp 743
hyphenat 743
idxlayout 744
ifoddpage 744
ifplatform 194
imakeidx 745
indentfirst 335
index 749
inputenc 108
inputenx 108
intopdf 750

karnaugh-map 751
keyfloat 164, 754
kotex 168
kvoptions 211
layaureo 756
layout 756
layouts 756
leading 759
letltxmacro 194
letterspace 759
lettrine 760
lineno 761
lips 763
listings 763
lltjext 767
lmodern 107, 108
longtable 161, 768
lscape 771
ltablex 771
ltcaption 772
ltxgrid 772
ltxtable 773
lua-check-hyphen 773
lua-visual-debug 773
luacolor 773
luatodonotes 167, 774
lwarp 109
lwarp-patch-komascript 964
lwarp-patch-memoir 966
magaz 776
makeidx 149, 776, 913
manyfoot 777
marginal 779
marginfit 779
marginfix 779
marginnote 780
marvosym 780
mcaption 781
mdframed 130, 781
memhfixc 790
metalogo 790
mhchem 791
microtype 219, 793
midfloat 794
midpage 794
morefloats 794
moreverb 795
mparhack 796
multicap 796
multicol 796
multicolrule 798
multirow 798
multitoc 801
musicography 801
nameauth 803
nameref 804
natbib 804
nccfancyhdr 805
needspace 806
newclude 166
newfloat 221
newtxmath 154
newunicodechar 108
nextpage 806
nicefrac 154, 807
niceframe 807
nomencl 137, 808
nonfloat 808
nonumonpart 809
nopageno 809
notes 809
notespages 810
nowidow 810
ntheorem 153, 811
octave 822
overpic 158, 823
pagegrid 824
pagenote 135, 824
pagesel 824
paralist 825
parnotes 825
parskip 826
pbox 826
pdfcomment 827
pdflscape 827
pdfmarginpar 827
pdfpages 828
pdfprivacy 830
pdfrender 830
pdfsync 831
pdftricks 157, 831
pdfx 832
perltex 171
perpage 832
pfnote 833
phfqit 833
pifont 834
placeins 835
plarydshln 835
plext 835
plextarydshln 836
plextcolortbl 836
polyglossia 167
prelim2e 836
prettyref 837
preview 837
printlen 222
psfrag 157, 837
psfragx 838
pst-eps 839

pstool 158, 839
pstricks 157, 840
pxatbegshi 840
pxeveryshi 840
pxftnright 840
pxjahyper 841
pythontex 171
quotchap 841
quoting 842
ragged2e 842
realscripts 843
refcheck 844
refcount 221
register 844
relsize 126, 845
repeatindex 846
resizegather 847
rmpage 847
romanbar 848
romanbarpagenumber 848
rotating 848
rotfloat 849
rterface 171
rviewport 850
sagetex 171
savetrees 850
scalefnt 850
schemata 850
scrextend 851
scrhack 854
scrlayer 854
scrlayer-notecolumn 855
scrlayer-scrpage 856
scrpage2 857
section 858
sectionbreak 859
sectsty 859
semantic-markup 860
setspace 861
shadow 862
showidx 862
showkeys 862
showtags 863
sidecap 863
sidenotes 864
SIunits 865
siunitx 154, 527, 866
soul 871
soulpos 872
soulutf8 873
splitidx 873
srcltx 875
srctex 875
stabular 875
stfloats 876
struktex 876
subcaption 163, 877
subfig 164, 878
subfigure 882
supertabular 162, 883
sympytex 171
syntonly 884
tablefootnote 885
tabls 885
tabularx 885
tabulary 886
tascmac 886
textarea 888
textcomp 108, 125, 888
textfit 892
textpos 892
theorem 893
thinsp 897
threadcol 897
threeparttable 897
threeparttablex 162, 898
thumb 899
thumbs 899
tikz 156, 900
titleps 901
titleref 904
titlesec 904
titletoc 906
titling 135, 908
tocbasic 912
tocbibind 149, 150, 913
tocenter 914
tocloft 135, 150, 597, 915
tocstyle 921
todo 921
todonotes 167, 922
tram 924
transparent 924
trimclip 925
trivfloat 163, 925
truncate 926
turnthepage 927
twoup 927
typearea 927
typicons 928
ulem 928
umoline 930
underscore 931
units 154, 931
unitsdef 932
upref 932
url 132, 933
uspace 933
varioref 132
varwidth 222

verbatim 221
verse 166, 933, 934
versonotes 935
vertbars 935
vmargin 936
vowel 936
vpe 937
vwcol 937
wallpaper 939
watermark 940
widows-and-orphans 940
wrapfig 940
xbmks 941
xcolor 156, 530, 942
xechangebar 952
xellipsis 952
xetexko-vertical 953
xfakebold 953
xfrac 954
xifthen 221
xltabular 956
xltxtra 957
xmpincl 957
xparse 168, 220
xpatch 194
xpiano 958
xpinyin 958
xstring 221
xtab 162, 959
xunicode 960
xurl 961
xy 962
zhlineskip 962
zwpagelayout 963
\packagediagramname 117, 9265
\pagebreak 11110
\pagecolor 71
pagegrid (package) 824
pagenote (package) 135, 824
\pagenumbering 4990
\pageref 8620
\pagerefPageFor 8619
pagesel (package) 824
\pagestyle 4982
Pandoc (program) 83
\paragraph 6217
paralist (package) 825
\parbox 10488
parnotes (package) 825
\parsemulticolumnalignment 7953
parskip (package) 826
\part 6152
pbox (package) 826
pdfcomment (package) 827
pdfcrop (program) [requirement] 86
pdfLaTeX (program) [requirement] 86
pdflscape (package) 827
pdfmarginpar (package) 827
pdfpages (package) 828
pdfprivacy (package) 830
pdfrender (package) 830
pdfseparate (program) [requirement] 86, 91
pdfsync (package) 831
pdftocairo (program) 155, 528
pdftocairo (program) [requirement] 86, 91
pdftotext (program) [requirement] . 86, 91
pdftotextEnc (option) 112, 214
pdftricks (package) 157, 831
pdfx (package) 832
perl (program) [requirement] 91
perltex (package) 171
perpage (package) 832
pfnote (package) 833
\phantomsection 11173
phfqit (package) 833
picture (environment) 536, 10366
pifont (package) 834
placeins (package) 835
plarydshln (package) 835
Plastex (program) 82
plext (package) 835
plextarydshln (package) 836
plextcolortbl (package) 836
\PN@parnotes@auto 5328
polyglossia (package) 167
\popclose 4759
\postchaptername 6136
\postpartname 6134
\postsectionname 6138
\prechaptername 6136
prelim2e (package) 836
\prepartname 6134
\presectionname 6138
prettyref (package) 837
preview (package) 837
\printauthor 375, 6501, 6520
\printdate 375, 6512, 6522
printglossary (option) [lwarpmk] 136, 718
\printindex 2
PrintIndexCmd (option) 109, 214
PrintLatexCmd (option) 109, 169, 214
printlen (package) 222
\printthanks 374, 377
\printtitle 375, 6485, 6519
program:
  [requirement]:
    LuaLaTeX 86
    MathJax 86
    pdfcrop 86
    pdfLaTeX 86

pdfseparate 86, 91
pdftocairo 86, 91
pdftotext 86, 91
perl 91
XeLaTeX 86
Adobe 83
AsciiDoc 83
AsciiDoctor 83
Asciidoctor-LaTeX 83
epstopdf 155, 528
Flare 83
FrameMaker 83
GELLMU 82
GladTeX 82
Hevea 82
htlatex 82
InDesign 83
LaTeX2HTML 82
latexmk 170
LaTeXML 82
LibreOffice 83
Linux 120, 209
lwarpmk 183, 290
lwarpmk epstopdf 155, 528
lwarpmk pdftosvg 155, 528
Mac OS 120, 209
Madcap 83
make 172
makeindex 147
MathJax 151, 152, 489, 490
MS-Windows 120, 209
OpenOffice 83
Pandoc 83
pdftocairo 155, 528
Plastex 82
TeX2page 82
TeX4ht 82
TeXMaths 177
TtH 82
Unix 120, 209
Windows 120, 209
Word 83
xindy 148
project.css (file) 120
project.lwarpmkconf (file) 249
psfrag (package) 157, 837
psfragx (package) 838
pst-eps (package) 839
pstool (package) 158, 839
pstricks (package) 157, 840
\pushclose 4732
pxatbegshi (package) 840
pxeveryshi (package) 840
pxftnright (package) 840
pxjahyper (package) 841
pythontex (package) 171

Q

\qquad 560, 11059
\quad 560, 11054
quotchap (package) 841
quote (environment) 6661
quoting (package) 842

R

ragged2e (package) 842
\raggedbottom 4986
\raggedleft 10092
\raggedright 10098
\raisebox 10624
realscripts (package) 843
\ref 8608
refcheck (package) 844
refcount (package) 221
\reflectbox 359
register (package) 844
relsize (package) 126, 845
repeatindex (package) 846
[requirement]:
LuaLaTeX (program) 86
MathJax (program) 86
pdfcrop (program) 86
pdfLaTeX (program) 86
pdfseparate (program) 86, 91
pdftocairo (program) 86, 91
pdftotext (program) 86, 91
perl (program) 91
XeLaTeX (program) 86
\RequirePackage 983
\resizebox 368
resizegather (package) 847
\ResumeTabular 8216
\reversemarginpar 5642
\rightline 10106
\rmfamily 10935
rmpage (package) 847
romanbar (package) 848
romanbarpagenumber (package) 848
\rotatebox 317
rotating (package) 848
rotfloat (package) 849
\rowcolor 7421
\rownum 7413
rterface (package) 171
\rule 11117
rviewport (package) 850

S

sagetex (package) 171
sample_project.css (file) 120, 286
savetrees (package) 850

\sb 10949
\scalebox 340
scalefnt (package) 850
schemata (package) 850
scrextend (package) 851
scrhack (package) 854
scrlayer (package) 854
scrlayer-notecolumn (package) 855
scrlayer-scrpage (package) 856
scrpage2 (package) 857
\scshape 10940
\section 6191
section (package) 858
sectionbreak (package) 859
sectsty (package) 859
semantic-markup (package) 860
\SetHTMLFileNumber 4852
setspace (package) 861
\sffamily 10936
\sfrac 954
shadow (package) 862
showidx (package) 862
showkeys (package) 862
showtags (package) 863
sidecap (package) 863
sidenotes (package) 864
SideTOCDepth (counter) 115, 478
\sidetocname 115, 9003
\simplechapterdelim 5962
\sishape 10941
SIunits (package) 865
siunitx (package) 154, 527, 866
\sloppy 4988
\slshape 10946
soul (package) 871
soulpos (package) 872
soulutf8 (package) 873
\sp 10948
splitidx (package) 873
srcltx (package) 875
srctex (package) 875
stabular (package) 875
\StartDefiningMath 4810
\StartDefiningTabulars 4800
stfloats (package) 876
\StopDefiningMath 4814
\StopDefiningTabulars 4804
struktex (package) 876
subcaption (package) 163, 877
subfig (package) 164, 878
subfigure (package) 882
\subparagraph 6225
\subsection 6200
\subsubsection 6208
supertabular (package) 162, 883
sympytex (package) 171
syntonly (package) 884

T

tabbing (environment) 6745
tablefootnote (package) 885
\tableofcontents 117, 8945
tabls (package) 885
tabular (environment) 8369
\TabularMacro 8214
tabularx (package) 885
tabulary (package) 886
tascmac (package) 886
\TeX 11181
TeX2page (program) 82
TeX4ht (program) 82
TeXMaths (program) 177
textarea (package) 888
\textbf 10651
\textcolor 48
textcomp (package) 108, 125, 888
textfit (package) 892
\textgreater 4845
\textit 10696
\textless 4843
\textmd 10642
\textnormal 10743
textpos (package) 892
\textrm 10660
\textsc 10705
\textsf 10669
\textsi 10717
\textsl 10734
\textsubscript 10952
\textsuperscript 10950
\texttt 10678
\textup 10687
\tfl@chapter@fix 926
\thanks 122
\thanksmarkseries 91
\theauthor 375
thebibliography (environment) 9185
\thedate 375
\theHTMLSection 6264
\theHTMLTitleSection 6263
\theHTMLTitleSeparator 6240
theindex (environment) 9093
\thempfootnote 5575
theorem (package) 893
\thetitle 375
thinsp (package) 897
\thispagestyle 4983
threadcol (package) 897
threeparttable (package) 897
threeparttablex (package) 162, 898
thumb (package) 899

thumbs (package) 899
tikz (package) 156, 900
\title 122, 5473
titlepage (environment) 122, 6469
titleps (package) 901
titleref (package) 904
titles (option) [tocloft] 135
titlesec (package) 904
titletoc (package) 906
titling (package) 135, 908
titlingpage (environment) 14, 122
tocbasic (package) 912
[tocbibind]:
numindex (option) 150, 913
tocbibind (package) 149, 150, 913
tocdepth (counter) 115
tocenter (package) 914
[tocloft]:
titles (option) 135
tocloft (package) 135, 150, 597, 915
tocstyle (package) 921
todo (package) 921
todonotes (package) 167, 922
\tracinglwarp 188, 1119
tram (package) 924
transparent (package) 924
trimclip (package) 925
trivfloat (package) 163, 925
truncate (package) 926
\ttfamily 10937
TtH (program) 82
turnthepage (package) 927
tutorial.tex (file) 92
twoup (package) 927
typearea (package) 927
typicons (package) 928

U

ulem (package) 928
umoline (package) 930
\underline 10960
underscore (package) 931
units (package) 154, 931
unitsdef (package) 932
Unix (program) 120, 209
\up 10958
upref (package) 932
\upshape 10938
\url 8698
url (package) 132, 933
\UseMinipageWidths 127, 537, 10380
usingOSWindows (boolean) 211
uspace (package) 933

V

varioref (package) 132
varwidth (package) 222
verbatim (environment) 6735
verbatim (package) 221
\VerbatimHTMLWidth (length) 386
\verbatiminput 6727
verse (environment) 2, 6676
verse (package) 166, 933, 934
versonotes (package) 935
vertbars (package) 935
\vleftmargini (length) 166, 385, 934
\vleftskip (length) 166, 385, 934
vmargin (package) 936
vowel (package) 936
vpe (package) 937
vwcol (package) 937

W

wallpaper (package) 939
warpall (environment) 121, 801
warpHTML (environment) 118, 120, 802
warpHTML (option) 112, 212
\warpHTMLonly 118, 121, 792
warpingHTML (boolean) 212
warpingprint (boolean) 212
warpprint (environment) . . . 118, 121, 802
warpprint (option) 112, 212
\warpprintonly 118, 121, 791
watermark (package) 940
widows-and-orphans (package) 940
Windows (program) 120, 209
Word (program) 83
WPMarkFloats (boolean) 176, 235
WPMarkLOFT (boolean) 177, 236
WPMarkMath (boolean) 177, 236
WPMarkMinipages (boolean) 177, 236
WPMarkTOC (boolean) 177, 236
WPTitleHeading (boolean) 178, 236
wrapfig (package) 940

X

xbmks (package) 941
xcolor (package) 156, 530, 942
xechangebar (package) 952
\XeLaTeX 11226
XeLaTeX (program) [requirement] 86
xellipsis (package) 952
\XeTeX 11226
xetexko-vertical (package) 953
xfakebold (package) 953
xfrac (package) 954
\xfracHTMLfontsize 3
xifthen (package) 221
xindy (option) 109, 113, 215
xindy (program) 148
xindyCodepage (option) 109, 213
xindyLanguage (option) 109, 213

xindyStyle (option) 109, 148, 213
xltabular (package) 956
xltxtra (package) 957
xmpincl (package) 957
xparse (package) 168, 220
xpatch (package) 194
xpiano (package) 958
xpinyin (package) 958
xstring (package) 221
xtab (package) 162, 959
xunicode (package) 960
xurl (package) 961
xy (package) 962

Z

zhlineskip (package) 962
zwpagelayout (package) 963

General Index

This is an index of instructions and concepts. Look here when wondering how to do something, and check the Troubleshooting Index when something goes wrong.

Symbols

\, ... 125
~ 125

A

accents
  in section & file names 355
adapting
  class 182
  document 106
  package 181
affiliation
  multiple authors 134
algorithmicx
  with newfloat, trivfloat 926
array
  mhchem 791
author
  HTML meta tag 123, 337
  multiple 134

B

baseline
  tabular 414
bibliography
  HTML page and TOC 134
bitmapped fonts 107
bugs 185

C

Calibre 173
chemistry
  Greek symbols 636
class
  modifying for lwarp 182
code listings 124
compiling
  custom 169
Computer Modern 107
converting
  class 182
  document 106
  package 181
CSS
  file selection 119
  lwarp.css 120
  per HTML page 119
  project-specific changes 120

D

danger icon 193
debugging 185
  HTML debug comments 230
  tracing log 230
Deja Vu 107
description
  HTML meta tag 123, 337
display math
  complicated objects 153
document
  convert existing 106
DVI LaTeX 102, 107
dynamic math 153
dynamic math expressions 312

E

endnotes
  HTML page and TOC 134
EPS image
  converting 104
  using 154, 528
EPUB
  conversion software 173
  HTML conversion settings 173, 235
error messages 185
export
  to word processor 175

F

FAQ 185
filename
  accent in 355
  hashed 494, 518
  international languages 165
  length 116
  simplify 131
  underscore in 113, 126
  unique 116
font
  Computer Modern 107
  Deja Vu 107
  ligatures 108

packages 108
selection 107
size
lateximage 151, 489, 514
math, SVG 151, 489, 514
xfrac 954
type 1 vector 107
type 3 bitmapped 107
footnotes 338
numbering 132
foreign
section names 165
framed objects 128
Frequently Asked Questions 185

G

generator
HTML meta tag 368
GIF images 155, 528
gloss 136
glossaries
HTML page and TOC 134
language 136
options 136
processing 103
graphics
formats 154, 528
Greek
chemistry symbols 636

H

hash
SVG image filename 494, 518
heading, word processor 178
horizontal space 125
between minipages 559
HTML
conversion settings 113
debug comments 230
EPUB 173, 235
word processor 175, 235
conversion suggestions 123
entities, conversion 124
filename generation 118
headings 192
meta tag
author 123, 337
description 123, 337
generator 368
title 116, 123, 337
viewport 368
selecting print/HTML definitions . . 231
tabular column conversion 414
verbatim, in 124
hyperref
and xindy 138

I

icon
warning 193
image
GIF 155, 528
graphicx package 528
hashed filename 494, 518
PDF or EPS
converting 104, 155, 528
using 154, 528
PNG and JPG 155, 528
processing 290
\includegraphics
using 154, 528
index
custom makeindex style file 147
custom xindy style file 148
custom display styles 149
formatting 484
HTML page and TOC 134
letter headings 745
placement and TOC options . . . 149, 913
processing 96, 97, 138
see, seealso, ranges 138
source code 138
table of contents 149, 913
UTF-8 108
xindy and hyperref 138
inline math
complicated objects 153
international
section names 165
item
empty 389

J

JAVASCRIPT
MATHJAX 150, 488
JPG images 155, 528

L

label
in HTML 371
math environment 509
language
glossaries 136
language HTML metadata 366
lateximage
font size 151, 489, 514
processing 290
Latin Modern font 107
LIBREOFFICE
conversion recommendations 178
import into 175
section headings 178
ligatures 108, 219

line numbers 193
list
  empty item 389
  filename 126
listings, program code 124
locale 172
LualaTeX
  detection 194
  file & section names 355
lwarp
  loading 109
  options 109
lwarp.ist
  customizing 147
lwarp.xdy
  customizing 148
lwarpmk
  customizing 183

M

make utility 172
makeindex
  customizing 147
margin
  numbers 193
  tags 193
markup languages 83
math
  display with complicated objects . . 153
  dynamic 153, 312
  font size — SVG 151, 489, 514
  inline with complicated objects . . . 153
  MathJax custom functions . . . 152, 490
  MathJax summary 151, 489
  mathjax option 213
  mathsvg option 212
  mhchem 791
  SVG summary 151, 489
  word processor conversion 177
MathJax
  custom functions 152, 490
  mathjax option 213
  summary 151, 489
MD5 hash
  SVG image filename 494, 518
memoir
  verse 934
meta tag, HTML
  author 123, 337
  description 123, 337
  generator 368
  title 123, 337
  viewport 368
minipage
  framed 128
  horizontal space between 559
modifying
  class 182
  document 106
  package 181
\multicolumn
  with \multirow 800
\multirow
  with \multicolumn 800

N

newfloat
  with trivfloat, algorithmicx 926
nomencl 137
numbers
  left margin 193

P

package
  modifying for lwarp 181
  required 218
\par
  hooks 333
PDF image
  converting 104
  using 154, 528
Perl 91
PNG images 155, 528
Poppler 86, 91
print
  selecting print/HTML definitions . . 231
problems 185
program listings 124
programs
  utility 85
\published 382

S

section
  depths 192
  file names 131
  heading, word processor 178
  international languages 165
settings
  CSS project-specific 120
  CSS selection 119
  HTML conversion 113
  lwarp package options 109
  selecting output 120
  title page 122
shell escape 107
siunitx
  with *TeXMaths* 177
space
  horizontal 125
    between minipages 559
stack depths 192
\subtitle 382

SVG
converting from PDF or EPS 104
dynamic math 312
image processing 290
math summary 151, 489
mathsvg option 212

T

tabular
baseline 414
HTML columnn conversion 414
macros inside 160, 397
\multicolumn with \multirow 800
tikz
catcodes 900
dollar redefined 900
title
HTML meta tag 123, 337
titlepage
\subtitle and \published 382
tracing log 230
trivfloat
with newfloat, algorithmicx 926
troubleshooting 185
HTML debug comments 230
tracing log 230
type 1 vector fonts 107
type 3 bitmapped fonts 107

U

underscore
filename 113, 126
Unicode
enhanced coverage 107
file & section names 355
input characters 207
selection 107
UTF-8
enhanced coverage 107
file & section names 355
index 108
locale 172
selection 107
utility
programs 85

V

vector fonts 107
verbatim
code and HTML tags 124
viewport
HTML meta tag 368

W

warning icon 193
word processor
conversion recommendations 178
HTML conversion settings 175, 235
section headings 178

X

XeLaTeX
detection 194
file & section names 355
xindy
and hyperref 138
customizing 148
xparse
warnings 168

Troubleshooting Index

This index is a sorted reference of problems and solutions. In order to make it easier to locate a solution, the same issue may be addressed by more than one entry.

Entries with higher page numbers are often duplicates of entries with lower page numbers, as the same warning may occur within the user manual and again within the source code for a given package.

A

abstract
- missing TOC . . . 135, 574

acronym
- multiply-defined labels . . . 579

\AddSubtitlePublished . . . 382
affiliation . . . 375
alt tags . . . 153, 186
AMSmath
- ntheorem
  - numbering . . . 154, 811

appendix
- incorrect TOC link . . . 135, 597

array
- chemformula . . . 168

authblk
- \theauthor . . . 374, 375
- titling . . . 135, 374, 606, 908

author
- affiliation . . . 375
- formatting . . . 122

B

babel
- French . . . 167

backref . . . 608
backref . . . 132
bibliography
- HTML page and TOC . . . 134

bibtex
- \etalchar . . . 136
- Improper \prevdepth . . . 136

bigdelim . . . 163, 614
bigfoot . . . 133, 777
boxes . . . 126
breqn
- darray . . . 621
- MATHJAX . . . 621

C

Calibre
- EPUB conversion . . . 173

caption
- numbering . . . 163
- options . . . 163

cases
- MATHJAX . . . 627

chemfig . . . 168
chemformula
- MATHJAX . . . 168, 632

chemgreek
- fontspec mapping . . . 636
- text-mode symbols . . . 636

chemmacros
- \makepolymerdelims . . . 637
- redox reactions . . . 637

colortbl . . . 161, 398, 658
cross reference
- incorrect link . . . 187
- missing . . . 186

CSS . . . 188

D

ditaa . . . 172
duplcate filename . . . 131

E

\endhead, etc. . . . 161
endnotes
- HTML page and TOC . . . 134

\ensuremath . . . 185
epstopdf . . . 157, 675
EPUB
- encoding . . . 173
- page order . . . 173
- search order . . . 173
- section breaks . . . 174

\etalchar . . . 136

F

fancybox
- \VerbatimFootnotes . . . 133, 681, 687

fancyvrb
- \VerbatimFootnotes . . . 133, 681, 687

figure
macro in name . . . 186
file
inaccessible . . . 115
filename
accents . . . 355
corrupted . . . 131, 165
duplicate . . . 131
international, UTF-8 . . . 165
Korean . . . 168
macro in name . . . 131
math in . . . 106, 131, 150, 488
Missing $ inserted . . . 185
fixme . . . 167, 694
float
alignment . . . 125, 163
out of sequence . . . 187
floatrow
\FBwidth and \FBheight . . . 164, 699
with subfig . . . 164, 699
floatrow
\ttabbox . . . 159, 396
font
ligatures . . . 108
missing symbols . . . 125, 888
monospace . . . 108
package conflicts . . . 107
selection . . . 107
UTF-8 . . . 107
fontspec . . . 107
footmisc . . . 133, 338
footnote
displaymath . . . 133, 681, 687
in math . . . 133
in sectioning command . . . 132
memoir . . . 133, 338
numbering . . . 132
paragraph tags . . . 133, 681, 687
sectioning, footmisc . . . 133, 338
sectioning, verbatim . . . 133, 681, 687
title . . . 374
verbatim . . . 133
\VerbatimFootnotes . . . 133, 681, 687
forest . . . 712
formatting
\bfseries etc. . . . 124, 547
frames . . . 128

G

gloss . . . 136
glossaries
HTML page and TOC . . . 134
makeglossaries not found . . . 136, 718
page numbers . . . 137, 719
style . . . 137, 719
graphics
\rotatebox, \scalebox, \reflectbox . . . 156, 529
image format priorities . . . 155, 529
images out of order . . . 98, 187
optional arguments . . . 155, 529
scale option . . . 106, 154, 528
scaled . . . 721
viewport . . . 155, 529
Greek packages . . . 636
grffile . . . 156, 733

H

horizontal spacing . . . 164, 878
HTML
&, <, > . . . 124, 547
alt tags . . . 153
author . . . 337
corrupted . . . 122, 126, 185, 188
entities . . . 124, 547
image appear as HTML code . . . 98, 187
inaccessible pages . . . 115, 117
starred section . . . 134
invalid . . . 124
missing pages
filename not unique . . . 116
recompile . . . 188
SideTOCDepth and FileDepth . . . 115
SideTOCDepth and tocdepth . . . 115
page did not update . . . 115, 188
settings
changed . . . 113
undefined . . . 185
validation . . . 124
\HTMLAuthor . . . 337
HTMLIndexCmd
filenames . . . 111
hyperref
backref . . . 132
comments between arguments . . . 132
incorrect link . . . 187

I

image
appears as HTML code . . . 98, 187
format priorities . . . 155, 529
incorrect . . . 98, 187
viewport . . . 155, 529
Improper \prevdepth
bibtex . . . 136
boxes . . . 185
\includegraphics
optional arguments . . . 155, 529
scale . . . 106, 154, 528
index
empty . . . 149

empty link 131, 186
formatting 484
HTML page and TOC 134
missing entries 138
numbers, not links 221
reference ranges 148
see and seealso 148
styling references 148
xindy and hyperref 148
xstring bug 221

K

keyfloat 164, 754

L

label
\nameref empty 131, 186
characters 131, 186
Label(s) may have changed 185
\LateximageFontSizeName 515
Leaders not followed by proper glue . . 185
LibreOffice
import 175
ligatures 108
LINUX 120, 209
list
empty item 126, 389
listings 187
lists
label formatting 390
locale 172
longtable
\endhead, etc. 161
ltxtable
numbering 773
lualaTeX 107
\LWRbackslash 169
\LWRdollar 169
\LWRhash 169
\LWRopquote 169
\LWRopseq 169
\LWRpercent 169

M

MAC OS 120, 209
makeglossaries
not found 136, 718
\makelabel 390
manyfoot 133, 777
\marginpar 126, 344
math
alt tags 186
appears as HTML code 98, 187
chemformula 168
custom macros 186
dynamic 312
equation numbering
ntheorem 154, 811
file name 106, 131, 150, 488
footnote 133
in TeX boxes 151, 489
incorrect 98, 187, 312
non-math contents 186
section name 106, 131, 150, 488
slow or failed compile 186
subequations 152, 490
tabbing 158, 388
Ti*k*z 153
MATHJAX
breqn 621
cases 627
chemformula 168, 632
errors 153, 186, 312
mhchem 791
siunitx 152, 154, 490, 527, 866
subequations 152, 490
unsupported packages . . 152, 186, 491
memoir
footmisc 133, 338
options clash 165, 966
version clash 165, 966
mhchem
MATHJAX 791
nested dollar signs 791
minipage
alignment 127, 538
horizontal space between 559
in a span 127, 537
inline 127, 537
multicols, width in 127, 537
size 127, 537
tabular, width in 127, 537
Misplaced \noalign 161, 769
tabular
rules 161, 398
Misplaced \omit
tabular 233
Misplaced alignment tab character &
floatrow 164, 699
frames 128
supertabular 162, 883, 959
tabular
macros 159, 311, 396
Missing $ inserted
filename or URL 185
morewrites 185
morewrites 149
MS-WINDOWS 120, 209
multiply-defined labels
acronym 579
\multirow and \multicolumn 160, 397, 800

multirow 159, 397

N

newclude 166
newtxmath 154
nicefrac 154
No room for a new \write 185
nomencl 137
ntheorem 811
  font 153, 811
  numbering 154, 811

O

operating system 120, 209
options clash
  memoir 165, 966
overpic 158, 823

P

package
  version numbers with memoir . 165, 966
page
  inacessible 115
page counter
  references 132
  SVG images 98, 187
page numbers 132, 187, 533
pdftricks 157, 831
perltex 171
pfnote
  numbering 133, 833
polyglossia
  Undefined control sequence 167
poppler
  Syntax Warning (ligature) 707
PrintIndexCmd 111
psfrag 157
pstool 158, 839
pstricks 157, 840
pythontex 171

R

reference
  % character between arguments . . 187
  empty link 131, 186
  incorrect link 187
  label characters 131, 186
  missing or incorrect 186
  page number 132, 187, 533
repeatindex 846
rterface 172

S

sample_projects.css
  overwritten 119
scale (\includegraphics option) 106, 154, 528
sectioning
  accents 355
  duplicate name 131
  international language 165
  macro in name 131, 186
  math in name 106, 131, 150, 488
  missing 115
  starred section 134
  word processor import 178
siunitx
  MathJax 154, 527, 866
  with TeXMaths 177
siunitx 154, 527, 866
  MathJax 152, 490
  S column 161, 399
  tabular S and s columns . 154, 527, 866
splitidx
  \thepage and \AtWriteToIndex 139, 873
subcaption
  numbering 163
subfig
  options 164, 878
  with floatrow 164, 699
SVG image
  appears as HTML code 98, 187
  incorrect 98, 187
  math incorrect 312
  out of order 98, 187
sympytex 172
Syntax Warning (ligature) 707

T

tabbing
  math 158, 388
table
  macro in name 186
  numbering 773
Table of Contents
  missing 117
tabular
  * column specification 160, 398
  baselines 413
  corrupt rows 159, 396, 446
  \endhead, \endfoot, \endlastfoot 161, 768
  inside an environment . . 159, 396, 446
  \kill 162, 769
  macro inside 160, 397
  Misplaced \noalign 161, 398
  Misplaced alignment tab character &
    macros 159, 396
    rules 311
  \multicolumn with \multirow 800
  \multirow 449, 450

multirow 159, 397
\newcolumntype 160, 398
numbering 956
row corruption 160, 397
rules 161, 398
S column 161, 399
TeXMaths 177
text
&, <, > 124, 547
\bfseries etc. 124, 547
corrupted 107
textcomp
missing symbols 125, 888
\theauthor and authblk 374, 375
threeparttablex 162
tikz
in math 153
matrices, & 156, 900
title
affiliation 375
newlines 122
\thanks 374
titling
authblk 135, 374, 606, 908
hooks 382
tocloft
chapter titles 135, 150, 597, 915
todonotes 167, 774, 922
tracing lwarp 188
tram 924
transparent 924

U

Undefined control sequence
polyglossia 167
Unicode
fonts 107
UTF-8 locale 172
units 154
UNIX 120, 209
URL
Missing $ inserted 185
UTF-8
locale 172

V

verbatim
footnote 133
framed 129, 680
VerbatimFootnotes 133, 681, 687
verse
spacing 166, 385, 934
version numbers
with memoir 165, 966
viewport 155, 529

W

warpall 185
warpHTML 121, 185
warpprint 121, 185
WINDOWS 120, 209
word processor
import 175
sectioning headings 178

X

xeLaTeX 107
xfakebold 953
xfrac 954
xindy
hyperref 148
options
HTMLIndexCmd 111
LatexmkIndexCmd 111
PrintIndexCmd 111
xltabular
numbering 956
xparse 168
xstring 221
xy 962

Index of Indexes

C

Change History 991

G

General Index 1037

I

Index of Objects 1017

T

Troubleshooting Index 1041