



# The l warp package

LATEX to HTML

v0.41 — 2017/10/07

© 2016–2017 Brian Dunn  
bd@BDTechConcepts.com

## Abstract

The l warp package allows LATEX to directly produce HTML output, using external utility programs only for the final conversion of text and images. Math may be represented by SVG files or MathJax.

Documents may be produced by pdfLATEX, LuaLATEX, or XeLATEX. A `texlua` script removes the need for system utilities such as `make` and `gawk`, and also supports `xindy` and `latexmk`. Configuration is automatic at the first manual compile.

Print and HTML versions of each document may coexist, each with its own set of auxiliary files. Support files are self-generated on request. Assistance is provided for import into EPUB conversion software and word processors.

A modular package-loading system uses the l warp version of a package for HTML when available. More than a hundred LATEX packages are supported with these high-level source compatibility replacements, and many others work as-is.

A tutorial is provided to quickly introduce the user to the major components of the package.

To update existing projects, see section 1, Updates.

Note that this is still an “alpha” version of l warp, and some things may change in response to user feedback and further project development.

## License:

This work may be distributed and/or modified under the conditions of the LaTeX Project Public License, either version 1.3 of this license or (at your option) any later version. The latest version of this license is in <http://www.latex-project.org/lppl.txt> and version 1.3 or later is part of all distributions of LaTeX version 2005/12/01 or later.

# Contents

<b>1</b>	<b>l warp.sty</b>	<b>29</b>
<b>1</b>	<b>Updates</b>	<b>29</b>
<b>2</b>	<b>Introduction</b>	<b>36</b>
2.1	Supported packages and features . . . . .	37
<b>3</b>	<b>Alternatives</b>	<b>41</b>
3.1	Internet class . . . . .	41
3.2	TeX4ht . . . . .	41
3.3	Translators . . . . .	41
3.4	AsciiDoc . . . . .	42
3.5	Pandoc . . . . .	42
3.6	Word processors . . . . .	42
3.7	Commercial systems . . . . .	43
3.8	Comparisons . . . . .	43
<b>4</b>	<b>Installation</b>	<b>44</b>
4.1	Installing the l warp package . . . . .	44
4.2	Installing the l warpmk utility . . . . .	47
4.2.1	Using a local copy of l warpmk . . . . .	48
4.3	Installing additional utilities . . . . .	49
<b>5</b>	<b>Tutorial</b>	<b>51</b>
5.1	Starting a new project . . . . .	51
5.2	Compiling the print version with l warpmk . . . . .	55
5.3	Compiling the HTML version with l warpmk . . . . .	56
5.4	Generating the SVG images . . . . .	57
5.5	Using MathJax for math . . . . .	58
5.6	Changing the CSS style . . . . .	59
5.7	Customizing the HTML output . . . . .	60
5.8	Using latexmk . . . . .	65
5.9	Using XeLaTeX or LuaLaTeX . . . . .	66
5.10	Using a glossary . . . . .	67
5.11	Cleaning auxiliary files . . . . .	68
5.12	Cleaning auxiliary and output files . . . . .	68
5.13	Processing multiple projects in the same directory . . . . .	68
5.14	Using the make utility . . . . .	68
<b>6</b>	<b>Additional details</b>	<b>69</b>
6.1	Font and UTF-8 support . . . . .	69
6.1.1	Indexes and UTF-8 . . . . .	70
6.2	l warp package loading and options . . . . .	70
6.3	Selecting the operating system . . . . .	71

6.4	Selecting actions for print or HTML output . . . . .	72
6.5	Commands to be placed into the <code>warpprint</code> environment . . . . .	73
6.6	Title page . . . . .	73
6.7	HTML page meta descriptions . . . . .	74
6.8	HTML page meta author . . . . .	74
6.9	CSS . . . . .	75
6.10	Modifying <code>xindy</code> index processing . . . . .	75
<b>7</b>	<b>Special cases and limitations</b>	<b>76</b>
7.1	Formatting . . . . .	76
7.1.1	Text formatting . . . . .	76
7.1.2	Horizontal space . . . . .	76
7.1.3	Text alignment . . . . .	76
7.1.4	Accents . . . . .	77
7.1.5	<code>Textcomp</code> . . . . .	77
7.1.6	Superscripts and other non-math uses of math mode . . . . .	77
7.1.7	Empty <code>\item</code> followed by a new line of text or a nested list: . . . . .	77
7.1.8	Filenames in lists . . . . .	77
7.1.9	<code>relsize</code> package . . . . .	77
7.2	Boxes and minipages . . . . .	78
7.2.1	Save Boxes . . . . .	78
7.2.2	Minipages . . . . .	78
7.2.3	Side-by-side minipages . . . . .	79
7.2.4	Framed minipages and other environments . . . . .	79
7.2.5	<code>fancybox</code> package . . . . .	80
7.2.6	<code>mdframed</code> package . . . . .	81
7.3	Cross-references . . . . .	82
7.3.1	Page references . . . . .	82
7.3.2	<code>cleveref</code> and <code>variorref</code> packages . . . . .	82
7.3.3	Hyperlinks, <code>hyperref</code> , and <code>url</code> . . . . .	83
7.3.4	Footnotes and page notes . . . . .	83
7.4	Front and back matter . . . . .	83
7.4.1	Starred chapters and sections . . . . .	83
7.4.2	<code>abstract</code> package . . . . .	84
7.4.3	<code>titling</code> and <code>authblk</code> . . . . .	84
7.4.4	<code>tocloft</code> package . . . . .	84
7.4.5	<code>appendix</code> package . . . . .	85
7.4.6	<code>pagenote</code> package . . . . .	85
7.4.7	<code>endnotes</code> package . . . . .	85
7.4.8	<code>glossaries</code> package . . . . .	85
7.4.9	Index and the <code>tocbibind</code> package . . . . .	86
7.5	Math . . . . .	87
7.5.1	<code>ntheorem</code> package . . . . .	89
7.5.2	<code>siunitx</code> package . . . . .	89
7.5.3	<code>units</code> and <code>nicerfrac</code> packages . . . . .	89
7.5.4	<code>newtxmath</code> package . . . . .	89

7.6	Graphics . . . . .	90
7.6.1	grffile package . . . . .	91
7.6.2	color package . . . . .	91
7.6.3	xcolor package . . . . .	91
7.7	Tabular . . . . .	92
7.7.1	longtable package . . . . .	94
7.7.2	supertabular and xtab packages . . . . .	95
7.7.3	bigdelim package . . . . .	95
7.8	Floats . . . . .	96
7.8.1	float, trivfloat, and/or algorithmicx together . . . . .	96
7.8.2	caption and subcaption packages . . . . .	96
7.8.3	subfig package . . . . .	96
7.8.4	floatrow package . . . . .	96
7.9	Miscellaneous . . . . .	97
7.9.1	verse and memoir . . . . .	97
7.9.2	newclude package . . . . .	97
7.9.3	babel package . . . . .	98
<b>8</b>	<b>EPUB conversion</b>	<b>99</b>
<b>9</b>	<b>Word-processor conversion</b>	<b>101</b>
<b>10</b>	<b>Modifying l warp</b>	<b>103</b>
10.1	Creating an l warp version of a package . . . . .	103
10.2	Adding a package to the l warp.dtx file . . . . .	104
10.3	Testing l warp . . . . .	104
10.4	Modifying l warpmk . . . . .	104
<b>11</b>	<b>Troubleshooting</b>	<b>106</b>
11.1	Using the l warp.sty package . . . . .	106
11.1.1	Debug tracing output . . . . .	108
11.2	Compiling the l warp.dtx file . . . . .	108
<b>12</b>	<b>Implementation</b>	<b>109</b>
<b>13</b>	<b>Stack depths</b>	<b>109</b>
<b>14</b>	<b>Source Code</b>	<b>111</b>
<b>15</b>	<b>Detecting the T<sub>E</sub>X Engine — pdflatex, lualatex, xelatex</b>	<b>112</b>
<b>16</b>	<b>Unicode Input Characters</b>	<b>112</b>
<b>17</b>	<b>Early package requirements</b>	<b>113</b>
<b>18</b>	<b>Operating-System portability</b>	<b>114</b>
18.1	Common portability code . . . . .	114

18.2 Unix, Linux, and Mac OS . . . . .	114
18.3 MS-Windows . . . . .	114
<b>19 Package options</b>	<b>115</b>
19.1 Conditional compilation . . . . .	118
<b>20 Misplaced packages</b>	<b>119</b>
<b>21 Required packages</b>	<b>123</b>
<b>22 Loading packages</b>	<b>128</b>
<b>23 File handles</b>	<b>131</b>
<b>24 Include a file</b>	<b>131</b>
<b>25 Copying a file</b>	<b>132</b>
<b>26 Debugging messages</b>	<b>133</b>
<b>27 HTML-conversion output modifications</b>	<b>134</b>
<b>28 Remembering original formatting macros</b>	<b>135</b>
<b>29 Accents</b>	<b>136</b>
<b>30 Configuration Files</b>	<b>138</b>
30.1 project_html.tex . . . . .	138
30.2 lwarpmk.conf . . . . .	138
30.3 project.lwarpmkconf . . . . .	139
30.4 l warp.css . . . . .	140
30.5 l warp_sagebrush.css . . . . .	166
30.6 l warp_formal.css . . . . .	171
30.7 sample_project.css . . . . .	176
30.8 l warp.xdy . . . . .	176
30.9 l warp_mathjax.txt . . . . .	177
30.10 lwarpmk option . . . . .	179
<b>31 Stacks</b>	<b>190</b>
31.1 Assigning depths . . . . .	191
31.2 Closing actions . . . . .	191
31.3 Closing depths . . . . .	192
31.4 Pushing and popping the stack . . . . .	192
<b>32 Data arrays</b>	<b>194</b>
<b>33 HTML entities</b>	<b>194</b>

<b>34</b>	<b>HTML filename generation</b>	<b>195</b>
<b>35</b>	<b>Homepage link</b>	<b>198</b>
<b>36</b>	<b>\PrintStack diagnostic tool</b>	<b>198</b>
<b>37</b>	<b>Closing stack levels</b>	<b>199</b>
<b>38</b>	<b>PDF pages and styles</b>	<b>199</b>
<b>39</b>	<b>HTML tags, spans, divs, elements</b>	<b>201</b>
39.1	Mapping L <sup>A</sup> T <sub>E</sub> X Sections to HTML Sections . . . . .	201
39.2	Babel-French . . . . .	201
39.3	HTML tags . . . . .	202
39.4	Block tags and comments . . . . .	205
39.5	Div class and element class . . . . .	206
39.6	Single-line elements . . . . .	207
39.7	HTML5 semantic elements . . . . .	207
39.8	High-level block and inline classes . . . . .	208
39.9	Closing HTML tags . . . . .	209
<b>40</b>	<b>Paragraph handling</b>	<b>210</b>
<b>41</b>	<b>Paragraph start/stop handling</b>	<b>213</b>
<b>42</b>	<b>Page headers and footers</b>	<b>216</b>
<b>43</b>	<b>CSS</b>	<b>217</b>
<b>44</b>	<b>HTML meta description and author</b>	<b>218</b>
<b>45</b>	<b>Footnotes</b>	<b>218</b>
45.1	Regular page footnotes . . . . .	219
45.2	Minipage footnotes . . . . .	219
45.3	Titlepage thanks . . . . .	219
45.4	Regular page footnote implementation . . . . .	219
45.5	Minipage footnote implementation . . . . .	221
45.6	Printing pending footnotes . . . . .	222
<b>46</b>	<b>Marginpars</b>	<b>222</b>
<b>47</b>	<b>Splitting HTML files</b>	<b>223</b>
<b>48</b>	<b>Sectioning</b>	<b>228</b>
48.1	User-level starred section commands . . . . .	228
48.2	Book class commands . . . . .	229
48.3	Sectioning support macros . . . . .	230
48.4	\section and friends . . . . .	236

<b>49 Starting a new file</b>	<b>238</b>
<b>50 Starting HTML output</b>	<b>241</b>
<b>51 Ending HTML output</b>	<b>244</b>
<b>52 Title page</b>	<b>245</b>
52.1 Setting the title, etc. . . . .	246
52.2 Changes for \affiliation . . . . .	247
52.3 Printing the thanks . . . . .	248
52.4 Printing the title, etc. in HTML . . . . .	248
52.5 Printing the title, etc. in print form . . . . .	250
52.6 \maketitle for HTML output . . . . .	250
52.7 \published and \subtitle . . . . .	253
<b>53 Abstract</b>	<b>254</b>
<b>54 Quote and verse</b>	<b>255</b>
54.1 Citations and attributions . . . . .	255
54.2 Quotes, quotations . . . . .	256
54.3 Verse . . . . .	256
<b>55 Verbatim</b>	<b>257</b>
<b>56 Theorems</b>	<b>259</b>
<b>57 Lists</b>	<b>260</b>
57.1 Itemize . . . . .	261
57.2 Enumerate . . . . .	262
57.3 Description . . . . .	262
<b>58 Tabular</b>	<b>264</b>
58.1 Limitations . . . . .	264
58.2 Token lookahead . . . . .	267
58.3 Booleans . . . . .	268
58.4 Handling &, @, !, and bar . . . . .	269
58.4.1 Localizing & catcodes . . . . .	271
58.4.2 Handling & . . . . .	271
58.4.3 Filling an unfinished row . . . . .	272
58.5 Handling \\ . . . . .	273
58.6 Variables . . . . .	274
58.7 Parsing @, >, <, !, bar columns . . . . .	276
58.8 Parsing 't', 'c', or 'r' columns . . . . .	278
58.9 Parsing 'p', 'm', or 'b' columns . . . . .	279
58.10 Parsing 'D' columns . . . . .	279
58.11 Parsing the column specifications . . . . .	280
58.12 Starting a new row . . . . .	284

58.13	Printing vertical bar tags . . . . .	285
58.14	Printing at or bang tags . . . . .	285
58.15	Data opening tag . . . . .	286
58.16	Midrules . . . . .	288
58.17	Multicolumns . . . . .	291
58.17.1	Parsing multicolumns . . . . .	291
58.17.2	Multicolumn factored code . . . . .	294
58.17.3	Multicolumn . . . . .	295
58.17.4	Longtable captions . . . . .	296
58.17.5	Counting HTML tabular columns . . . . .	298
58.18	Multicolumnrow . . . . .	300
58.19	Utility macros inside a table . . . . .	301
58.20	Special-case tabular markers . . . . .	301
58.21	Checking for a new table cell . . . . .	303
58.22	\mrowcell . . . . .	305
58.23	\mcolrowcell . . . . .	305
58.24	New \tabular definition . . . . .	305
58.25	Array . . . . .	310
<b>59</b>	<b>Cross-references</b>	<b>310</b>
59.1	Setup . . . . .	310
59.2	Zref setup . . . . .	312
59.3	Labels . . . . .	314
59.4	References . . . . .	315
59.5	Hyper-references . . . . .	317
<b>60</b>	<b>FLOATS</b>	<b>320</b>
60.1	Float captions . . . . .	321
60.1.1	Caption inside a float environment . . . . .	322
60.1.2	Caption and LOF linking and tracking . . . . .	323
<b>61</b>	<b>Table of Contents, LOF, LOT</b>	<b>326</b>
61.1	Reading and printing the TOC . . . . .	326
61.2	High-level TOC commands . . . . .	328
61.3	Side TOC . . . . .	329
61.4	Low-level TOC line formatting . . . . .	330
<b>62</b>	<b>Index and glossary</b>	<b>333</b>
<b>63</b>	<b>Math</b>	<b>335</b>
63.1	Inline and display math . . . . .	337
63.2	MathJax support . . . . .	339
63.3	Equation environment . . . . .	343
63.4	AMS Math environments . . . . .	345
63.4.1	Support macros . . . . .	345
63.4.2	Environment patches . . . . .	346

<b>64</b>	<b>Lateximages</b>	<b>353</b>
<b>65</b>	<b>center, flushleft, flushright</b>	<b>359</b>
<b>66</b>	<b>Pre-loaded packages</b>	<b>360</b>
<b>67</b>	<b>Siunitx</b>	<b>361</b>
<b>68</b>	<b>Graphics</b>	<b>361</b>
68.1	xcolor print-mode additions . . . . .	362
<b>69</b>	<b>Cleveref</b>	<b>366</b>
<b>70</b>	<b>Picture</b>	<b>368</b>
<b>71</b>	<b>Boxes and Minipages</b>	<b>368</b>
71.1	Counters and lengths . . . . .	369
71.2	Footnote handling . . . . .	369
71.3	Minipage handling . . . . .	370
71.4	Parbox, makebox, framebox, fbox, raisebox . . . . .	373
<b>72</b>	<b>Direct formatting</b>	<b>378</b>
<b>73</b>	<b>Skips, spaces, font sizes</b>	<b>383</b>
<b>74</b>	<b>\phantomsection</b>	<b>390</b>
<b>75</b>	<b>\LaTeX{} and other logos</b>	<b>390</b>
75.1	HTML logos . . . . .	391
75.2	Print logos . . . . .	392
<b>76</b>	<b>\AtBeginDocument, \AtEndDocument</b>	<b>393</b>
<b>77</b>	<b>Trademarks</b>	<b>394</b>
<b>2</b>	<b>lwarf-a4.sty</b>	<b>395</b>
<b>78</b>	<b>a4</b>	<b>395</b>
<b>3</b>	<b>lwarf-a4wide.sty</b>	<b>395</b>
<b>79</b>	<b>a4wide</b>	<b>395</b>
<b>4</b>	<b>lwarf-a5comb.sty</b>	<b>395</b>
<b>80</b>	<b>a5comb</b>	<b>395</b>

<b>5 l warp-abstract.sty</b>	<b>395</b>
<b>81 abstract</b>	<b>395</b>
<b>6 l warp-adjmulticol.sty</b>	<b>397</b>
<b>82 adjmulticol</b>	<b>397</b>
<b>7 l warp-addlines.sty</b>	<b>398</b>
<b>83 addlines</b>	<b>398</b>
<b>8 l warp-afterpage.sty</b>	<b>398</b>
<b>84 afterpage</b>	<b>398</b>
<b>9 l warp-algorithmicx.sty</b>	<b>399</b>
<b>85 algorithmicx</b>	<b>399</b>
<b>10 l warp-alltt.sty</b>	<b>399</b>
<b>86 alltt</b>	<b>399</b>
<b>11 l warp-amsthm.sty</b>	<b>400</b>
<b>87 amsthm</b>	<b>400</b>
<b>12 l warp-anonchap.sty</b>	<b>402</b>
<b>88 anonchap</b>	<b>402</b>
<b>13 l warp-any size.sty</b>	<b>403</b>
<b>89 anysize</b>	<b>403</b>
<b>14 l warp-appendix.sty</b>	<b>403</b>
<b>90 appendix</b>	<b>403</b>

<b>15 l warp-arabicfront.sty</b>	<b>404</b>
91 arabicfront	404
<b>16 l warp-authblk.sty</b>	<b>404</b>
92 authblk	404
<b>17 l warp-balance.sty</b>	<b>405</b>
93 balance	405
<b>18 l warp-bigdelim.sty</b>	<b>405</b>
94 bigdelim	405
<b>19 l warp-bigstrut.sty</b>	<b>407</b>
95 bigstrut	407
<b>20 l warp-bookmark.sty</b>	<b>407</b>
96 bookmark	407
<b>21 l warp-booktabs.sty</b>	<b>407</b>
97 booktabs	407
<b>22 l warp-boxedminipage.sty</b>	<b>408</b>
98 boxedminipage	408
<b>23 l warp-boxedminipage2e.sty</b>	<b>408</b>
99 boxedminipage2e	408
<b>24 l warp-caption2.sty</b>	<b>409</b>
100 caption2	409

<b>25 lwarf-ccaption.sty</b>	<b>409</b>
<b>101 ccaption</b>	<b>409</b>
<b>26 lwarf-changepage.sty</b>	<b>409</b>
<b>102 changepage</b>	<b>409</b>
<b>27 lwarf-chngpage.sty</b>	<b>409</b>
<b>103 chngpage</b>	<b>409</b>
<b>28 lwarf-chappg.sty</b>	<b>410</b>
<b>104 chappg</b>	<b>410</b>
<b>29 lwarf-color.sty</b>	<b>410</b>
<b>105 color</b>	<b>410</b>
<b>30 lwarf-crop.sty</b>	<b>410</b>
<b>106 crop</b>	<b>410</b>
<b>31 lwarf-cuted.sty</b>	<b>411</b>
<b>107 cuted</b>	<b>411</b>
<b>32 lwarf-cutwin.sty</b>	<b>411</b>
<b>108 cutwin</b>	<b>411</b>
<b>33 lwarf-dblfnote.sty</b>	<b>412</b>
<b>109 dblfnote</b>	<b>412</b>
<b>34 lwarf-dcolumn.sty</b>	<b>412</b>
<b>110 dcolumn</b>	<b>412</b>

<b>35 lwarf-draftwatermark.sty</b>	<b>412</b>
<b>111 draftwatermark</b>	<b>412</b>
<b>36 lwarf-ebook.sty</b>	<b>413</b>
<b>112 ebook</b>	<b>413</b>
<b>37 lwarf-ellipsis.sty</b>	<b>413</b>
<b>113 ellipsis</b>	<b>413</b>
<b>38 lwarf-emptypage.sty</b>	<b>414</b>
<b>114 emptypage</b>	<b>414</b>
<b>39 lwarf-endnotes.sty</b>	<b>414</b>
<b>115 endnotes</b>	<b>414</b>
<b>40 lwarf-enumerate.sty</b>	<b>415</b>
<b>116 enumerate</b>	<b>415</b>
<b>41 lwarf-enumitem.sty</b>	<b>415</b>
<b>117 enumitem</b>	<b>415</b>
<b>42 lwarf-epigraph.sty</b>	<b>416</b>
<b>118 epigraph</b>	<b>416</b>
<b>43 lwarf-eso-pic.sty</b>	<b>417</b>
<b>119 eso-pic</b>	<b>417</b>
<b>44 lwarf-everypage.sty</b>	<b>417</b>
<b>120 everypage</b>	<b>417</b>

<b>45 lwarf-everyshi.sty</b>	<b>418</b>
121 everyshi	418
<b>46 lwarf-extramarks.sty</b>	<b>418</b>
122 extramarks	418
<b>47 lwarf-fancybox.sty</b>	<b>418</b>
123 fancybox	418
<b>48 lwarf-fancyhdr.sty</b>	<b>422</b>
124 fancyhdr	422
<b>49 lwarf-fancyvrb.sty</b>	<b>423</b>
125 fancyvrb	423
<b>50 lwarf-figcaps.sty</b>	<b>428</b>
126 figcaps	428
<b>51 lwarf-fix2col.sty</b>	<b>429</b>
127 fix2col	429
<b>52 lwarf-float.sty</b>	<b>429</b>
128 float and \newfloat	429
<b>53 lwarf-floatflt.sty</b>	<b>430</b>
129 floatflt	430
<b>54 lwarf-floatpag.sty</b>	<b>431</b>
130 floatpag	431

<b>55 lwarf-floatrow.sty</b>	<b>431</b>
131 floatrow	431
<b>56 lwarf-flushend.sty</b>	<b>437</b>
132 flushend	437
<b>57 lwarf-fncychap.sty</b>	<b>437</b>
133 fncychap	437
<b>58 lwarf-fnpos.sty</b>	<b>438</b>
134 fnpos	438
<b>59 lwarf-fontenc.sty</b>	<b>438</b>
135 fontenc	438
<b>60 lwarf-fontspec.sty</b>	<b>439</b>
136 fontspec	439
<b>61 lwarf-footmisc.sty</b>	<b>439</b>
137 footmisc	439
<b>62 lwarf-footnote.sty</b>	<b>440</b>
138 footnote	440
<b>63 lwarf-footnotehyper.sty</b>	<b>441</b>
139 footnotehyper	441
<b>64 lwarf-framed.sty</b>	<b>441</b>
140 framed	441

<b>65 l warp-ftnright.sty</b>	<b>444</b>
141 ftnright	444
<b>66 l warp-fullpage.sty</b>	<b>444</b>
142 fullpage	444
<b>67 l warp-fullwidth.sty</b>	<b>444</b>
143 fullwidth	444
<b>68 l warp-geometry.sty</b>	<b>445</b>
144 geometry	445
<b>69 l warp-glossaries.sty</b>	<b>445</b>
145 glossaries	445
<b>70 l warp-graphics.sty</b>	<b>447</b>
146 graphics	447
146.1 Graphics extensions . . . . .	447
146.2 Length conversions and graphics options . . . . .	448
146.3 \includegraphics . . . . .	451
<b>71 l warp-graphicx.sty</b>	<b>457</b>
147 graphicx	457
<b>72 l warp-grffile.sty</b>	<b>457</b>
148 grffile	457
<b>73 l warp-hyperref.sty</b>	<b>457</b>
149 hyperref	457

<b>74 lwarf-hyperxmp.sty</b>	<b>462</b>
<b>150 hyperxmp</b>	<b>462</b>
<b>75 lwarf-idxlayout.sty</b>	<b>462</b>
<b>151 idxlayout</b>	<b>462</b>
<b>76 lwarf-indentfirst.sty</b>	<b>463</b>
<b>152 indentfirst</b>	<b>463</b>
<b>77 lwarf-inputenc.sty</b>	<b>463</b>
<b>153 inputenc</b>	<b>463</b>
<b>78 lwarf-keyfloat.sty</b>	<b>463</b>
<b>154 keyfloat</b>	<b>463</b>
<b>79 lwarf-layout.sty</b>	<b>464</b>
<b>155 layout</b>	<b>464</b>
<b>80 lwarf-letterspace.sty</b>	<b>465</b>
<b>156 letterspace</b>	<b>465</b>
<b>81 lwarf-lettrine.sty</b>	<b>465</b>
<b>157 lettrine</b>	<b>465</b>
<b>82 lwarf-lips.sty</b>	<b>466</b>
<b>158 lips</b>	<b>466</b>

<b>83 lwarf-listings.sty</b>	<b>467</b>
159 listings	467
<b>84 lwarf-longtable.sty</b>	<b>470</b>
160 longtable	470
<b>85 lwarf-lscape.sty</b>	<b>472</b>
161 lscape	472
<b>86 lwarf-ltcaption.sty</b>	<b>472</b>
162 ltcaption	472
<b>87 lwarf-marginfit.sty</b>	<b>473</b>
163 marginfit	473
<b>88 lwarf-marginfix.sty</b>	<b>473</b>
164 marginfix	473
<b>89 lwarf-marginnote.sty</b>	<b>473</b>
165 marginnote	473
<b>90 lwarf-mcaption.sty</b>	<b>474</b>
166 mcaption	474
<b>91 lwarf-mdframed.sty</b>	<b>474</b>
167 mdframed	474

<b>92 l warp-metalogo.sty</b>	<b>483</b>
<b>168 metalogo</b>	<b>483</b>
<b>93 l warp-microtype.sty</b>	<b>483</b>
<b>169 microtype</b>	<b>483</b>
<b>94 l warp-midfloat.sty</b>	<b>484</b>
<b>170 midfloat</b>	<b>484</b>
<b>95 l warp-moreverb.sty</b>	<b>484</b>
<b>171 moreverb</b>	<b>484</b>
<b>96 l warp-mparhack.sty</b>	<b>486</b>
<b>172 mparhack</b>	<b>486</b>
<b>97 l warp-multicol.sty</b>	<b>486</b>
<b>173 multicol</b>	<b>486</b>
<b>98 l warp-multirow.sty</b>	<b>487</b>
<b>174 multirow</b>	<b>487</b>
174.1 Multirow . . . . .	488
174.2 Combined multicolumn and multirow . . . . .	490
<b>99 l warp-nameref.sty</b>	<b>491</b>
<b>175 nameref</b>	<b>491</b>
<b>100 l warp-needspace.sty</b>	<b>491</b>
<b>176 needspace</b>	<b>491</b>

<b>101 lwarf-newclude.sty</b>	<b>491</b>
<b>177 newclude</b>	<b>491</b>
<b>102 lwarf-newunicodechar.sty</b>	<b>492</b>
<b>178 newunicodechar</b>	<b>492</b>
<b>103 lwarf-nextpage.sty</b>	<b>492</b>
<b>179 nextpage</b>	<b>492</b>
<b>104 lwarf-nonumonpart.sty</b>	<b>492</b>
<b>180 nonumonpart</b>	<b>492</b>
<b>105 lwarf-nopageno.sty</b>	<b>493</b>
<b>181 nopageno</b>	<b>493</b>
<b>106 lwarf-nowidow.sty</b>	<b>493</b>
<b>182 nowidow</b>	<b>493</b>
<b>107 lwarf-ntheorem.sty</b>	<b>493</b>
<b>183 ntheorem</b>	<b>493</b>
<b>108 lwarf-pagenote.sty</b>	<b>504</b>
<b>184 pagernote</b>	<b>504</b>
<b>109 lwarf-paralist.sty</b>	<b>504</b>
<b>185 paralist</b>	<b>504</b>
<b>110 lwarf-parskip.sty</b>	<b>505</b>
<b>186 parskip</b>	<b>505</b>

<b>111 l warp-pdfescape.sty</b>	<b>505</b>
<b>187 pdfescape</b>	<b>505</b>
<b>112 l warp-pdfsync.sty</b>	<b>505</b>
<b>188 pdfsync</b>	<b>505</b>
<b>113 l warp-pfnote.sty</b>	<b>506</b>
<b>189 pfnote</b>	<b>506</b>
<b>114 l warp-placeins.sty</b>	<b>506</b>
<b>190 placeins</b>	<b>506</b>
<b>115 l warp-prelim2e.sty</b>	<b>506</b>
<b>191 prelim2e</b>	<b>506</b>
<b>116 l warp-quotchap.sty</b>	<b>507</b>
<b>192 quotchap</b>	<b>507</b>
<b>117 l warp-ragged2e.sty</b>	<b>508</b>
<b>193 ragged2e</b>	<b>508</b>
<b>118 l warp-realscripts.sty</b>	<b>509</b>
<b>194 realscripts</b>	<b>509</b>
<b>119 l warp-relsize.sty</b>	<b>510</b>
<b>195 relsize</b>	<b>510</b>

<b>120 lwarf-romanbar.sty</b>	<b>511</b>
<b>196 romanbar</b>	<b>511</b>
<b>121 lwarf-romanbarpagenumber.sty</b>	<b>511</b>
<b>197 romanbarpagenumber</b>	<b>511</b>
<b>122 lwarf-rotating.sty</b>	<b>512</b>
<b>198 rotating</b>	<b>512</b>
<b>123 lwarf-rotfloat.sty</b>	<b>512</b>
<b>199 rotfloat</b>	<b>512</b>
<b>124 lwarf-savetrees.sty</b>	<b>513</b>
<b>200 savetrees</b>	<b>513</b>
<b>125 lwarf-scalefnt.sty</b>	<b>513</b>
<b>201 scalefnt</b>	<b>513</b>
<b>126 lwarf-sectsty.sty</b>	<b>513</b>
<b>202 sectsty</b>	<b>513</b>
<b>127 lwarf-setspace.sty</b>	<b>514</b>
<b>203 setspace</b>	<b>514</b>
<b>128 lwarf-shadow.sty</b>	<b>515</b>
<b>204 shadow</b>	<b>515</b>
<b>129 lwarf-showidx.sty</b>	<b>516</b>
<b>205 showidx</b>	<b>516</b>

<b>130 l warp-showkeys.sty</b>	<b>516</b>
<b>206 showkeys</b>	<b>516</b>
<b>131 l warp-sidecap.sty</b>	<b>516</b>
<b>207 sidecap</b>	<b>516</b>
<b>132 l warp-sidenotes.sty</b>	<b>517</b>
<b>208 sidenotes</b>	<b>517</b>
<b>133 l warp-siunitx.sty</b>	<b>519</b>
<b>209 siunitx</b>	<b>519</b>
<b>134 l warp-soul.sty</b>	<b>519</b>
<b>210 soul</b>	<b>519</b>
<b>135 l warp-stabular.sty</b>	<b>521</b>
<b>211 stabular</b>	<b>521</b>
<b>136 l warp-subfig.sty</b>	<b>521</b>
<b>212 subfig</b>	<b>521</b>
<b>137 l warp-supertabular.sty</b>	<b>527</b>
<b>213 supertabular</b>	<b>527</b>
<b>138 l warp-syntonly.sty</b>	<b>528</b>
<b>214 syntonly</b>	<b>528</b>
<b>139 l warp-tables.sty</b>	<b>529</b>
<b>215 tabs</b>	<b>529</b>

<b>140 l warp-tabularx.sty</b>	<b>529</b>
<b>216 tabularx</b>	<b>529</b>
<b>141 l warp-tabulary.sty</b>	<b>530</b>
<b>217 tabulary</b>	<b>530</b>
<b>142 l warp-textarea.sty</b>	<b>530</b>
<b>218 textarea</b>	<b>530</b>
<b>143 l warp-textcomp.sty</b>	<b>531</b>
<b>219 textcomp</b>	<b>531</b>
<b>144 l warp-textpos.sty</b>	<b>534</b>
<b>220 textpos</b>	<b>534</b>
<b>145 l warp-theorem.sty</b>	<b>534</b>
<b>221 theorem</b>	<b>534</b>
<b>146 l warp-threeparttable.sty</b>	<b>538</b>
<b>222 threeparttable</b>	<b>538</b>
<b>147 l warp-tikz.sty</b>	<b>539</b>
<b>223 tikz</b>	<b>539</b>
<b>148 l warp-titleps.sty</b>	<b>540</b>
<b>224 titleps</b>	<b>540</b>
<b>149 l warp-titleref.sty</b>	<b>543</b>
<b>225 titleref</b>	<b>543</b>

<b>150 l warp-titlesec.sty</b>	<b>543</b>
<b>226 titlesec</b>	<b>543</b>
<b>151 l warp-tocletoc.sty</b>	<b>545</b>
<b>227 titletoc</b>	<b>545</b>
<b>152 l warp-titling.sty</b>	<b>546</b>
<b>228 titling</b>	<b>546</b>
<b>153 l warp-tocbibind.sty</b>	<b>551</b>
<b>229 tocbibind</b>	<b>551</b>
<b>154 l warp-tocloft.sty</b>	<b>553</b>
<b>230 tocloft</b>	<b>553</b>
<b>155 l warp-transparent.sty</b>	<b>558</b>
<b>231 transparent</b>	<b>558</b>
<b>156 l warp-trivfloat.sty</b>	<b>559</b>
<b>232 trivfloat</b>	<b>559</b>
232.1 Combining \newfloat, \trivfloat, and algorithmicx . . . . .	560
<b>157 l warp-typearea.sty</b>	<b>560</b>
<b>233 typearea</b>	<b>560</b>
<b>158 l warp-ulem.sty</b>	<b>560</b>
<b>234 ulem</b>	<b>560</b>

<b>159 l warp-upref.sty</b>	<b>562</b>
<b>235 upref</b>	<b>562</b>
 <b>160 l warp-verse.sty</b>	<b>562</b>
<b>236 verse</b>	<b>562</b>
 <b>161 l warp-wallpaper.sty</b>	<b>564</b>
<b>237 wallpaper</b>	<b>564</b>
 <b>162 l warp-wrapfig.sty</b>	<b>565</b>
<b>238 wrapfig</b>	<b>565</b>
 <b>163 l warp-xcolor.sty</b>	<b>566</b>
<b>239 xcolor</b>	<b>566</b>
239.1 Xcolor definitions: location and timing . . . . .	567
239.2 Code . . . . .	569
 <b>164 l warp-xfrac.sty</b>	<b>574</b>
<b>240 xfrac</b>	<b>574</b>
 <b>165 l warp-xltextra.sty</b>	<b>576</b>
<b>241 xltextra</b>	<b>576</b>
 <b>166 l warp-xmpincl.sty</b>	<b>577</b>
<b>242 xmpincl</b>	<b>577</b>
 <b>167 l warp-xtab.sty</b>	<b>577</b>
<b>243 xtab</b>	<b>577</b>

**168 l warp-zw pagelayout.sty** **579**

**244 zw pagelayout** **579**

**Change History and Index** **581**

## List of Figures

1	tutorial.tex listing	52
---	----------------------	----

## List of Tables

1	l <sup>A</sup> T <sub>E</sub> X–HTML generation — l warp package — Supported functions	37
2	Required software programs	45
3	Files created along with the print version	54
4	Package options	71
5	Section depths and HTML headings	110
6	Tabular baseline	280
7	Tabular HTML column conversions	281
8	Cross-referencing data structures	311
9	Float data structures	320

## File 1 **l warp.sty**

### 1 Updates

The following is intended for those updating existing projects which use l warp, highlighting any special changes which must be made due to improvements or modifications in l warp itself.

For a detailed list of changes, see the Change History on page 581.

#### v0.41:

- tabular**
- Added tabular vertical rules, subject to some limitations. See the rules section of section 7.7.
  - Improved booktabs: Width and trim are honored.
  - Added `\mcolrowcell` for empty cells inside a `\multicolumnrow`. Use `\mcolrowcell` instead of `\mrowcell` for two-dimensional cells created by `\multicolumnrow`. Continue to use `\mrowcell` for empty cells in a `\multirow`. See section 174.2 on page 490.
  - Fix: Unfinished tabular rows are automatically filled.
  - Fix for tabular column specifiers while using babel-french. (`\NoAutoSpacing` is activated then nullified inside the tabular, due to a conflict with the tabular column parsing code.)
- ⚠ new syntax**

#### v0.40:

- graphics, graphicx**
- graphics and graphicx have been moved from the l warp core, and are only loaded if requested with `\usepackage`.
- ⚠ \includegraphics path**
- Improved graphics `\graphicspath` support. Multiple image directories may now be used. Refer to .pdf files without a file extension to allow the HTML version to use a .svg, .png, .jpg, or .gif version instead. See section 7.6.
  - `grffile` is now directly supported instead of emulated.
- bigdelim**
- symbols**
- fixes**
- Fix for bigdelim, and improved documentation. See section 94.
  - Improved  $\mathbb{E}$  and `textcomp` symbols.
  - Fix for  $\mathbb{E}$  logos and `\InlineClass`, etc. inside a `lateximage`.
  - Fix for `xltextra` with  $\mathbb{E}$ .
  - Fixes for `tocbibind` with `\simplechapter`, etc.

- Fixes for `\multicolumnrow` and `\nullfonts` with older versions of `multirow` and `xparse`.

[margins](#)  
[columns](#)  
[footnotes](#)  
[tabular](#)  
[sectioning](#)

- Added `\underline`.
- Added `adjmulticol`.
- Added `cuted`, `midfloat`.
- Added `pfnote`, `fnpos`, `dblfnote`.
- Added `stabular`, `tbls`.
- Added `sectsty`, `anonchap`, `quotchap`.

#### v0.39:

[title pages](#)

⚠ `\published` and  
`\subtitle`  
⚠ load order  
`tabular`  
`multi column/row cell`

- Improved the titlepage HTML code, `\thanks` notes, and `\maketitle`. `titling` is no longer required, but is still supported. The `\published` and `\subtitle` fields are no longer provided, but `\AddSubTitlePublished` replicates them using `titling`. See section 52.7. `authblk` is added, and should be loaded before `titling`. See section 52.

- `\multirow` now supports the new optional `vpos` argument.
- Added `\multicolumnrow` for combined `\multicolumn` and `\multirow`. See section 174.2.

- Tabular special cases:
  - Added `\TabularMacro` to mark custom macros inside tabular data cells, avoiding row corruption. See section 7.7.
  - Added `\ResumeTabular` for use when a `tabular` environment is defined inside another environment. See section 7.7.

- Added `supertabular`, `xtab`, `bigstrut`, `bigdelim`.
- Added `fullwidth`.
- Added `addlines`, `anysize`, `a4`, `a4wide`, `a5comb`, `textarea`, `zwpagelayout`, `typearea`, `ebook`.

#### v0.38:

[forced single-pass compile](#)

- Added `lwarfpmk print1` and `lwarfpmk html1` actions to force a compile of the project a single time. Useful when multiple passes are not needed, or changes were not detected.

[starred sections](#)

- Added `\ForceHTMLPage` and `\ForceHTMLTOC` to force a starred sectional unit onto its own HTML page and with its own TOC entry. See section 7.4.1.
- Modified the tutorial to use the new `\ForceHTMLPage` and `\ForceHTMLTOC` macros.

[updated tutorial](#)  
[packages](#)  
[font size](#)

- Added `appendix`, `tocbibind`, `fncychap`, `fix2col`.
- Added `relsize`, `scalefnt`.
- Added `realscripts`, `metalogo`, `xltxtra`.

- Added grffile, romanbar.
- [page numbering](#)
- Added arabicfront, chappg, nonumonpart, nopageno, romanbarpagenumber.
- [front & back matter](#)
- Docs: Improved description of the use of front/back matter. See section [7.4](#).
  - Fix: color requests xcolor.
  - Fix: \part for article class.
- v0.37:**
- \include now maintains independent .aux files for HTML versions.
  - comment, used by lwarf, now maintains independent cut files for print and HTML versions, helping latexmk to better know whether to recompile.
  - Improved support for L<sup>A</sup>T<sub>E</sub>X accents, textcomp, siunitx symbols.
  - Improved babel-french handling for load order and ~ tilde.
- v0.36:**
- Recorganized the documentation section regarding special cases and limitations. (Section [7](#))
  - Improved source formatting.
  - \fbox and related now use \fboxsep and \fboxrule.
  - \makebox and \framebox now use width and position.
  - \fcolorbox and related now work inside a lateximage.
  - babel-french: Improvements for French variants, load order, footnotes, ellipses.
  - Improved footnote numbering. lateximage footnotes now appear as regular footnotes to match the numbering of the print version. Also fixed a regression with MathJax.
  - Improved siunitx units.
  - Fix for filenames while using MathJax.
  - Fix for \rule when xcolor is not loaded.
  - Added transparent, upref.
- v0.35:** Fix: \textbf and related.
- v0.34:**
- ⚠ [Optional arguments](#)
- BlockClass's optional argument has been moved in front of the mandatory argument:  
 $\text{BlockClass}[style]\{class\}$  (NEW)  
instead of:  
 $\text{BlockClass}\{class\}[style]$  (OLD)
- This change makes it more consistent with L<sup>A</sup>T<sub>E</sub>X standards, and avoids problems with space between arguments.

## ⚠ Optional arguments

[spans with minipages](#)

- Likewise, `\InlineClass`'s optional argument now comes before the mandatory arguments:

```
\InlineClass[style]{class}{text}
```

[framing minipages](#)

- Improved compatibility between spans, minipages, lists, frames, and math. Handles minipages and lists inside an `HTML` span, such as an `\fbox` containing a minipage, although with minimal `HTML` fomatting. See section [7.2.2.](#) `\fboxBlock` is added to frame minipages, tables, and lists with full `HTML` formatting but no longer inline, and behaves as `\fbox` for print output. The `fminipage` environment is added for framed minipages, as an environment with full `HTML` formatting, and draws a framed minipage in print output. See section [7.2.4.](#) `\fbox` and minipages now often work in `SVG` math and `latextimages`. MathJax supports `\fbox`, but not `\fboxBlock` nor `fminipage`.

[latextimage, SVG math, tabular](#)

- Improved compatibility between `latextimage` and `minipage`, `\parbox`, `\makebox`, `\fbox`, `\framebox`, `\raisebox`, `\scalebox`, `\reflectbox`, `tabular`, `booktabs`.

[eqnarray](#)

- Improved font control for `latextimagees` and `SVG` math.

[verbatim packages](#)

- Added the `eqnarray` environments.

[framing packages](#)

- `fancyvrb` is no longer required (preloaded), but is still supported.

[list packages](#)

- Added `verbatim` and `moreverb`.

[babel-french](#)

- Added `fancybox`, `boxedminipage2e` and `shadow`.

- `enumitem` is no longer required, but is still supported.

- Added `enumerate` and `paralist`.

- `titleps` is no longer required, but is still supported.

- Added `crop`.

- Added `rotfloat`, `marginfit`, and several minor packages; see the change log.

- Adds fixed-width `HTML` spaces around punctuation when using `babel-french`. `LuaTeX` does not yet use the extra punctuation spacing.

## v0.33:

- `Tabular @` and `!` columns now have their own `HTML` columns.
- & catcode changes are localized, perhaps causing errors about the tab alignment character `&`, so any definitions of macros or environments which themselves contain `tabular` and `&` must be enclosed within `\StartDefiningTabulars` and `\EndDefiningTabulars`. See section [58.4.1.](#) This change is not required for the routine use of tables, but only when a table is defined inside another macro or environment, and while also using the `&` character inside the definition. This may include the use inside conditional expressions.

- Several math environments were incorrectly placed inline. Also, for amsmath with SVG math, the `fleqn` option has been removed, resulting in improved spacing for aligned equations.
- Bug fixes; see the changelog.

**v0.32:** Bug fixes; no source changes needed:

- `lwarpmk` has been adjusted to work with the latest luatex.
- Spaces in the `\usepackage` and `\RequirePackage` package lists are now accepted and ignored.
- Fix for the `glossaries` package and `\glo@name`.

**v0.31:** Bug fix; no source changes needed:

- Improved compatibility with `keyfloat`, including the new `keywrap` environment.

**v0.30:**

 **lwarp-newproject**

- `lwarp-newproject` has been removed, and its functions have been combined with `lwarp`.

To modify existing documents, remove from the document source:

```
\usepackage{lwarp-newproject}
```

The `lwarp` package now produces the configuration files during print output, and also accepts the option `lwarpmk` if desired.

 **HTML setup changes.**

- A number of macros related to `HTML` settings have been converted to options, and other macros and options have been renamed to create a consistent syntax:

Old Macro	New Package Option
\HomeHTMLFileName	HomeHTMLfilename
\HTMLFileName	HTMLfilename
\useLatexmk	latexmk
\warpOSwindows	OSWindows
Old Package Option	New Package Option
lwarpmklang (new)	IndexLanguage xdyFilename
Old Macro	New Macro
\MetaLanguage	\HTMLLanguage
\HTMLAuthor	\HTMLAuthor
\NewHTMLDescription	\HTMLDescription
\SetFirstPageTop	\HTMLFirstPageTop
\SetPageTop	\HTMLPageTop
\SetPageBottom	\HTMLPageBottom
\NewCSS	\CSSfilename

- Per the above changes, in existing documents, modify the package load of lwarf, such as:

```
\usepackage[
    HomeHTMLfilename=index,
    HTMLfilename={},
    IndexLanguage=english
]{lwarf}
```

- The file lwarf\_html.xdy has been renamed lwarf.xdy. To update each document's project:
  1. Make the changes shown above.
  2. Recompile the document in print mode. This updates the project's configuration files, and also generates the new file lwarf.xdy.
  3. The old file lwarf\_html.xdy may be deleted.
- The new lwarf package option xdyFilename may be used to tell lwarpmk to use a custom .xdy file instead of lwarf.xdy. See section 6.10.
- Improvements in index processing:
  - xindy's language is now used for index processing as well as glossary.
  - Print mode without latexmk now uses xindy instead of makeindex.
  - texindy/xindy usage depends on pdflatex vs xelatex, lualatex.
  - For pdflatex and texindy, the -C utf8 option is used. This is supported in modern distributions, but a customized lwarpmk.lua may need to be created for use with older distributions.

**v0.29:**

- Add: `lwarpmklang` option for `lwarf-newproject` and `lwarf`. Sets the language to use while processing the glossary. (As of v0.30, this has been changed to the `IndexLanguage` option.)
- Fix: `\includegraphics` when no optional arguments.

**v0.28:**

- `\HTMLAuthor {\<name>}` assigns HTML meta author if non-empty. Defaults to `\theauthor`.
- Boolean `HTMLDebugComments` controls whether HTML comments are added for closing `<div>`s, opening and closing sections, etc.
- Boolean `FormatEPUB` changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.
- Boolean `FormatWordProcessor` changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments.
- Boolean `HTMLMarkFloats` adds text marks around floats only if `FormatWordProcessor`. These make it easier to identify float boundaries, which are to be manually converted to word-processor frames.
- Updated for the new MathJax CDN repository.
- Adds tabulary.
- Supports the options syntax for graphics.
- Improved index references, now pointing exactly to their target.
- Adds glossaries. `lwarpmk` is modified to add `printglossary` and `htmlglossary` actions.

## 2 Introduction

The lwarp project aims to allow a rich  $\text{\LaTeX}$  document to be converted to a reasonable HTML interpretation. No attempt has been made to force  $\text{\LaTeX}$  to provide for every HTML-related possibility, and HTML cannot exactly render every possible  $\text{\LaTeX}$  concept. Where compromise is necessary, it is desirable to allow the print output to remain typographically rich, and compromise only in the HTML conversion.

Several “modern” features of HTML, CSS, and SVG are employed to allow a fairly feature-rich document without relying on the use of Javascript. Limited testing on older browsers show that these new features degrade gracefully, although the SVG format for math may not be available on small cell phones.

`pdflatex`, `xelatex`, or `lualatex` is used, allowing lwarp to process the usual image formats. While generating HTML output, SVG files are used in place of PDF. Other formats such as JPG are used as-is.

SVG images may be used for math, and are also used for `picture`, and `Tikz` environments, as this format has better browser and e-book support than MathML (as of this writing), while still allowing for the high-quality display and printing of images (again, subject to potentially bug-ridden<sup>1</sup> browser support).

Furthermore, SVG images allow math to be presented with the same precise formatting as in the print version. Math is accompanied by ALT tags holding the  $\text{\LaTeX}$  source for the expression, allowing it to be copy/pasted into other documents.<sup>2</sup> Custom  $\text{\LaTeX}$  macros may be used as-is in math expressions, since the math is evaluated entirely inside  $\text{\LaTeX}$ .

The MATHJAX JavaScript display engine may be selected for math display instead of using SVG images. Subject to browser support and Internet access, MathJax allows an HTML page to display math without relying on a large number of external image files, one per math expression. lwarp maintains  $\text{\LaTeX}$  control for cross-referencing and equation numbering / formatting.

---

The lwarp package allows  $\text{\LaTeX}$  to directly generate HTML tags from a  $\text{\LaTeX}$  source document, with only minor intervention on the user’s part. A `texlua` program called `lwarpmk` is used to process either the print or HTML version of the document. A few external utility programs are used to finish the conversion from a  $\text{\LaTeX}$ -generated PDF file which happens to have HTML tags, to a number of HTML plain-text files and accompanying images.

<sup>1</sup>Firefox has had an on-again/off-again bug for quite some time regarding printing svgs at high resolution.

<sup>2</sup>There seems to be some debate as to whether MathML is actually an improvement over  $\text{\LaTeX}$  for sharing math. The author has no particular opinion on the matter, except to say that in this case  $\text{\LaTeX}$  is much easier to implement!

lwarp automatically generates the extra files necessary for the HTML conversion, such as css and .xdy files, and configuration files for the utility `lwarpmk`. Also included is a parallel version of the user's source document, `<sourcename>-html.tex`, which selects HTML output and then inputs the user's own source. This process allows both the printed and HTML versions to co-exist side-by-side, each with their own auxiliary files.

When requesting packages during HTML conversion, lwarp first looks to see if it has its own modified version to use instead of the usual  $\text{\TeX}$  version. These `lwarp-pagename.sty` files contain code used to emulate or replace functions for HTML output.

Enough functionality is provided to convert a typical article containing technical content. Not every package has been tested, but many of the most useful ones are known to work, either as-is or through emulation with replacement code. (See table 1 on page 37.)

Assistance is provided for modifying the HTML output to suite the creation of EPUB documents, and for modifying the HTML output to ease import into a word processor.

## 2.1 Supported packages and features

Supported classes include book, report, and article. memoir is planned, but in the meantime many of the packages used by memoir are already supported.

Table 1 lists some of the various  $\text{\TeX}$  features which may be used. *Supported* means that the package or macro may be used as-is, perhaps with minor limitations. *Emulated* means that the original package or macro is not used, but similar functionality is provided in a way which is intended to be compatible with the user's  $\text{\TeX}$  code.

Table 1:  $\text{\TeX}$ -HTML generation — lwarp package — Supported functions

Category	Status
Engines:	<code>pdf<math>\text{\TeX}</math></code> , <code>X<math>\text{\TeX}</math></code> , <code>Lua<math>\text{\TeX}</math></code>
Classes:	book, report, or article. memoir is planned.
Page layout:	Emulates geometry, fancyhdr, titleps, addlines, any-size, a4, a4wide, a5comb, textarea, zwpagelayout, typearea, ebook.

## lwarf Supported Functions — continued

Category	Status
Sectioning:	Supported, with hyperlinks. Honors <code>tocdepth</code> and <code>secnumdepth</code> . Adds <code>FileDepth</code> for splitting the HTML output. Files may be numbered sequentially or named according to section name. Common short words and punctuation is removed from the filenames. Emulates <code>titlesec</code> , <code>fncychap</code> , <code>sectsty</code> , <code>anonchap</code> , <code>quotchap</code> .
Table of contents, figures, tables:	Supported, with hyperlinks. Supports <code>tocbibind</code> . Emulates <code>titletoc</code> and <code>tocloft</code> .
Title page:	<code>\maketitle</code> , <code>titlepage</code> , <code>titling</code> , <code>authblk</code> .
Front & back matter:	<code>abstract</code> , <code>appendix</code>
Indexing:	<code>texindy</code> is used, with hyperlinks. <code>idxlayout</code> is emulated.
Glossary:	<code>glossaries</code> and <code>xindy</code> are used.
Bibliography:	Supported text-only.
Cross-references:	Emulated, with hyperlinks. <code>hyperref</code> , <code>cleveref</code> , <code>varioref</code> , <code>url</code> .
Languages:	<code>babel</code> . ( <code>polyglossia</code> is untested.)
Margin notes:	<code>marginfit</code> , <code>marginfix</code> .
Footnotes:	<code>footnote</code> , <code>footmisc</code> , <code>marginnote</code> , <code>sidenote</code> , <code>pagenote</code> , <code>endnotes</code> .
Math:	Supported. Converted to SVG images with HTML ALT tags containing the $\text{\LaTeX}$ source for the math expression. MathJax supported as an alternative. $\mathcal{AMS}$ environments are supported. User-defined macros are available during conversion, due to native $\text{\LaTeX}$ processing.
Theorems:	Support for native $\text{\LaTeX}$ theorems, plus <code>theorem</code> , <code>amsthm</code> , <code>ntheorem</code> .
Add'l math:	<code>delarray</code> , <code>bm</code> , math fonts via SVG images.
Units and fractions:	<code>siunitx</code> , <code>xfrac</code> , <code>nicefrac</code> , <code>units</code>

## lwarf Supported Functions — continued

Category	Status
Floats:	Appear where declared. <code>float</code> , <code>rotfloat</code> , <code>newfloat</code> , <code>caption</code> and <code>subcaption</code> , <code>subfig</code> , <code>capt-of</code> , <code>placeins</code> , <code>trivfloat</code> , <code>floatrow</code> , <code>subfloat</code> , <code>keyfloat</code> , <code>wrapfig</code> , <code>cutwin</code> , <code>floatlt</code> .
Tabular	<code>tabular</code> environment, <code>array</code> , <code>tabularx</code> , <code>tabulary</code> , <code>threeparttable</code> , <code>multirow</code> , <code>longtable</code> , <code>supertabular</code> , <code>xtab</code> , <code>booktabs</code> .
Graphics	<code>graphics</code> and <code>graphicx</code> are emulated. <code>\includegraphics</code> supports <code>width</code> , <code>height</code> , <code>origin</code> , <code>angle</code> , and <code>scale</code> tags, and adds <code>class</code> . References to PDF files are changed to SVG, other image types are accepted as well. <code>\rotatebox</code> and <code>\scalebox</code> are supported as well as HTML can handle. <code>grffile</code> is supported.
rotating:	Emulated. All objects are displayed unrotated.
picture and tikz:	Converted to an SVG image.
xcolor:	<b>Supported.</b> Full package color names, any color models, and <code>mixing</code> . <code>\textcolor</code> , <code>\colorbox</code> , <code>\fcolorbox</code> . Enhanced for HTML compatibility.
Lists:	Standard $\text{\TeX}$ environments are supported, along with <code>enumitem</code> , <code>enumerate</code> , <code>paralist</code> . Spacing is still controlled by <code>css</code> .
Environments:	Standard $\text{\TeX}$ environments are supported.
<code>minipage</code> :	Supported with some HTML-imposed limitations. Nested minipages are supported. Footnotes appear at the bottom of the HTML page.
Quotations:	<code>verse</code> , <code>csquotes</code> , <code>epigraph</code>
Verbatim:	<code>verbatim</code> , <code>moreverb</code> , <code>fancyvrb</code> (except for <code>verbatim</code> footnotes).
Frames:	<code>framed</code> , <code>fancybox</code> , <code>mdframed</code> , <code>boxedminipage2e</code> , <code>shadow</code> .

## l warp Supported Functions — continued

Category	Status
multicol:	Emulated, with css. Converted to up to three columns with an optional heading, per browser support. Single-column if unsupported.
fullwidth:	Emulated.
Direct formatting:	\emph, \textsuperscript, \textbf, etc are supported. \bfseries, etc. are not yet supported. lettertrine, ulem, soul, relsize, scalefnt, and realscripts are supported.
Ordinals:	nth, fmtcount, and engord are supported.
Text ligatures:	Ligatures for symbols are supported. Ligatures for f, q, t are intentionally turned off because many simpler browsers do not display them correctly. Modern full-featured browsers re-create these ligatures on-the-fly.
Horizontal space:	HTML output for thin-unbreakable, unbreakable, \enskip, \quad, \qquad, \hspace.
Rules:	\rule with width, height, raise, text color.
HTML reserved characters:	\&, \textless, and \textgreater are converted to HTML entities.
Fonts:	Used as-is. Appear in math expressions or embedded image environments.
Symbols:	Native L <sup>A</sup> T <sub>E</sub> X diacriticals, textcomp.
Working as-is:	Various utility, calculation, file, and text-only packages, such as calc, fileerr, somedefs, trace, xspace.
Where:	
<b>Supported:</b>	The existing L <sup>A</sup> T <sub>E</sub> X package is used.
<b>Emulated:</b>	The L <sup>A</sup> T <sub>E</sub> X package is not used, but some/all of its functions are emulated. Null functions, lengths, and counters are provided for source compatibility.

### 3 Alternatives

Summarized below are several other ways to convert a  $\text{\LaTeX}$  or other document to HTML. Where an existing  $\text{\LaTeX}$  document is to be converted to HTML, lwarf may be a good choice. For new projects with a large number of documents, it may be worth investigating the alternatives before decided which path to take.

#### 3.1 Internet class

Cls **internet** The closest to lwarf in design principle is the `internet` class by Andrew Stacey (<https://github.com/loopspace/latex-to-internet>), an interesting project which directly produces several versions of markdown, and also HTML and EPUB.

#### 3.2 TeX4ht

Prog **TeX4ht** <http://tug.org/tex4ht/>

This system uses native  $\text{\LaTeX}$  processing to produce a DVI file containing special commands, and then uses additional post-processing for the HTML conversion by way of numerous configuration files. In some cases, lwarf provides a better HTML conversion, and it supports a different set of packages. TeX4ht produces several other forms of output beyond HTML.

#### 3.3 Translators

These systems use external programs to translate a subset of  $\text{\LaTeX}$  syntax into HTML. Search for each on CTAN (<http://ctan.org>).

Prog **Hevea** **H<sup>E</sup>v<sup>E</sup>a:** <http://hevea.inria.fr/> (not on CTAN)

Prog **TtH** **T<sub>T</sub>H:** <http://hutchinson.belmont.ma.us/tth/>

Prog **GELLMU** **GELLMU:** <http://www.albany.edu/~hammond/gellmu/>

Prog **LaTeXML** **LT<sub>E</sub>XML:** <http://dlmf.nist.gov/LaTeXML/>

Prog **Plastex** **PlasTeX:** <https://github.com/tiarno/plastex>

Prog **LaTeX2HTML** **LT<sub>E</sub>X2HTML:** <http://www.latex2html.org/>  
and <http://ctan.org/pkg/latex2html>.

Prog **TeX2page** **TeX2page:** <http://ds26gte.github.io/tex2page/index.html>

Finally, Glad $\text{\TeX}$  may used to directly insert  $\text{\TeX}$  math into HTML:

Prog Glad $\text{\TeX}$  **Glad $\text{\TeX}$ :** <http://humenda.github.io/GladTeX/>

### 3.4 AsciiDoc

AsciiDoc is one of the most capable markup languages, providing enough features to produce the typical technical-writing document with cross-references, and it writes  $\text{\TeX}$  and HTML.

Prog AsciiDoc **Asciidoctor:** <http://asciidoctor.org/> (More active.)

Prog AsciiDoctor **AsciiDoc:** <http://asciidoc.org/> (The original version.)

The Asciidoctor-LaTeX project is adding additional  $\text{\TeX}$ -related features.

#### Asciidoctor-Latex:

<http://www.noteshare.io/book/asciidoctor-latex-manual>

Prog Asciidoctor-LaTeX <https://github.com/asciidoctor/asciidoctor-latex>

### 3.5 Pandoc

Prog Pandoc

A markup system which also reads and writes  $\text{\TeX}$  and HTML.

**Pandoc:** <http://pandoc.org/>

(Watch for improvements in cross-references to figures and tables.)

### 3.6 Word processors

Prog Word It should be noted that the popular word processors have advanced through the years in their abilities to represent math with a  $\text{\TeX}$ -ish input syntax, unicode math fonts, and high-quality output, and also generate HTML with varying success. See recent developments in Microsoft® Word® and LibreOffice™ Writer.  
Prog LibreOffice  
Prog OpenOffice

### 3.7 Commercial systems

Prog Adobe Likewise, several professional systems exist whose abilities have been advancing in the areas of typesetting, cross-referencing, and HTML generation. See Adobe® FrameMaker®, Adobe® InDesign®, and Madcap Flare™.

Prog InDesign

Prog Flare

Prog Madcap

### 3.8 Comparisons

AsciiDoc, Pandoc, and various other markup languages typically have a syntax which tries to be natural and human-readable, but the use of advanced features tends to require many combinations of special characters, resulting in a complicated mess of syntax. By contrast, L<sup>A</sup>T<sub>E</sub>X spells things out in readable words but takes longer to type, although integrated editors exist which can provide faster entry and a graphic user interface. For those functions which are covered by the typical markup language it is arguable that L<sup>A</sup>T<sub>E</sub>X is comparably easy to learn, while L<sup>A</sup>T<sub>E</sub>X provides many more advanced features where needed, along with a large number of pre-existing packages which provide solutions to numerous common tasks.

Text-based document-markup systems share some of the advantages of L<sup>A</sup>T<sub>E</sub>X vs. a typical word processor. Documents formats are stable. The documents themselves are portable, work well with revision control, do not crash or become corrupted, and are easily generated under program control. Formatting commands are visible, cross-referencing is automatic, and editing is responsive. Search/replace with regular expressions provides a powerful tool for the manipulation of both document contents and structure. Markup systems and some commercial systems allow printed output through a L<sup>A</sup>T<sub>E</sub>X back end, yielding high-quality results especially when the L<sup>A</sup>T<sub>E</sub>X template is adjusted, but they lose the ability to use L<sup>A</sup>T<sub>E</sub>X macros and other L<sup>A</sup>T<sub>E</sub>X source-document features.

The effort required to customize the output of each markup system varies. For print output, L<sup>A</sup>T<sub>E</sub>X configuration files are usually used. For HTML output, a css file will be available, but additional configuration may require editing some form of control file with a different syntax, such as XML. In the case of lwarf, CSS is used, and much HTML output is adjusted through the usual L<sup>A</sup>T<sub>E</sub>X optional macro parameters, but further customization may require patching L<sup>A</sup>T<sub>E</sub>X code.

The popular word processors and professional document systems each has a large base of after-market support including pre-designed styles and templates, and often include content-management systems for topic reuse.

## 4 Installation

Table 2 shows the tools which are used for the  $\text{\LaTeX}$  to HTML conversion. In most cases, these will be available via the standard package-installation tools.

### 4.1 Installing the lwarf package

There are several ways to install lwarf. These are listed here with the preferred methods listed first:

**Pre-installed:** Try entering into a command line:

Enter ⇒ kpsewhich lwarf.sty

If a path to lwarf.sty is shown, then lwarf is already installed.

**T<sub>E</sub>X Live:** If using a T<sub>E</sub>X Live distribution, try installing via tlmgr:

Enter ⇒ tlmgr install lwarf

**MiK<sub>T</sub>E<sub>X</sub>:** If using MiK<sub>T</sub>E<sub>X</sub>, try using the package installer to install the package lwarf. Also update the package `miktex-misc`, which will install the `lwarpmk` executable.

**Operating-system package:** The operating-system package manager may already have lwarf, perhaps as part of a set of T<sub>E</sub>X-related packages.

**CTAN TDS archive:** lwarf may be downloaded from the Comprehensive T<sub>E</sub>X Archive:

1. See <http://ctan.org/pkg/lwarf> for the lwarf package.
2. Download the TDS archive: `lwarf.tds.zip`
3. Find the T<sub>E</sub>X local directory:

**T<sub>E</sub>X Live:**

Enter ⇒ kpsewhich -var-value TEXMFLOCAL

**MiK<sub>T</sub>E<sub>X</sub>:**

In the “Settings” window, “Roots” tab, look for a local TDS root.

This should be something like:

`/usr/local/texlive/texmf-local/`

4. Unpack the archive in the TDS local directory.
5. Renew the cache:

Enter ⇒ mktexlsr

— or —

Enter ⇒ texhash

Table 2: Required software programs

**Provided by your  $\text{\LaTeX}$  distribution:**

From T<sub>E</sub>XLive: <http://tug.org/texlive/>.

**$\text{\LaTeX}$ :** pdflatex, xelatex, or lualatex.

**The `lwarf` package:** This package.

**The `lwarpmk` utility:** Provided along with this package. This should be an operating-system executable in the same way that pdflatex or latexmk is. It is possible to have the lwarf package generate a local copy of `lwarpmk` called `lwarpmk.lua`. See table 3.

**luatex:** Used by the `lwarpmk` program to simplify and automate document generation.

**xindy:** The xindy package is used by lwarf to create indexes. On a MiK<sub>T</sub>E<sub>X</sub> system this may have to be acquired separately, but it is part of the regular installer as of mid 2015.

**latexmk:** Optionally used by `lwarpmk` to compile  $\text{\LaTeX}$  code. On a MiK<sub>T</sub>E<sub>X</sub> system, Perl may need to be installed first.

**pdfcrop:** Used to pull images out of the  $\text{\LaTeX}$  PDF.

**Poppler PDF utilities:**

**pdftotext:** Used to convert PDF to text.

**pdfseparate:** Used to pull images out of the  $\text{\LaTeX}$  PDF.

**pdftocairo:** Used to convert images to SVG.

These might be provided by your operating-system package manager.

From Poppler: [poppler.freedesktop.org](http://poppler.freedesktop.org).

For MacOS®, see <https://brew.sh/>, install Homebrew, then

```
Enter ⇒ brew install poppler
```

For Windows, see:

<https://sourceforge.net/projects/poppler-win32/> and:  
<http://blog.alivate.com.au/poppler-windows/>

**Perl:**

This may be provided by your operating-system package manager, and is required for some of the Poppler PDF utilities.

[perl.org](http://perl.org), [strawberryperl.com](http://strawberryperl.com)

**Automatically downloaded from the internet as required:**

**MathJax:** Optionally used to display math. Automatically loaded from the MathJax website when needed.

From: [mathjax.org](http://mathjax.org)

Or, for Windows MiK<sub>T</sub>E<sub>X</sub>, start the program called MiK<sub>T</sub>E<sub>X</sub> Settings (Admin) and click on the button called Refresh FNDB.

**CTAN .dtx and .ins files:** Another form of T<sub>E</sub>X package is the .dtx and .ins source files. These files are used to create the documentation and .sty files.

1. See <http://ctan.org/pkg/lwarp> for the l warp package.

2. Download the zip archive l warp.zip into your own l warp directory.

3. Unpack l warp.zip.

4. Locate the contents l warp.dtx and l warp.ins

5. Create the documentation:

Enter ⇒ pdflatex l warp.dtx

(several times)

6. Create the .sty files:

Enter ⇒ pdflatex l warp.ins

7. Copy the .sty files somewhere such as the T<sub>E</sub>X Live local tree found in the previous CTAN TDS section, under the subdirectory:

<texlocal>/tex/latex/local/l warp

8. Copy the documentation l warp.pdf to a source directory in the local tree, such as:

<texlocal>/doc/local/l warp

9. Renew the cache:

Enter ⇒ mktexlsr

— or —

Enter ⇒ texhash

Or, for Windows MiK<sub>T</sub>E<sub>X</sub>, start the program called MiK<sub>T</sub>E<sub>X</sub> Settings (Admin) and click on the button called Refresh FNDB.

10. See section 4.2.1 to generate your local copy of l warpmk.

11. Once the local version of l warpmk.lua is installed, it may be made available system-wide as per section 4.2.

**Project-local CTAN .dtx and .ins files:** The .dtx and .ins files may be downloaded to a project directory, then compiled right there, alongside the document source files. The resultant \*.sty and l warpmk.lua files may be used as-is, so long as they are in the same directory as the document source. This approach is especially useful if you would like to temporarily test l warp before deciding whether to permanently install it.

## 4.2 Installing the lwarpmk utility

(Note: If `lwarpmk` is not already installed, it is easiest to use a local copy instead of installing it system-wide. See section 4.2.1.)

After the `lwarf` package is installed, you may need to setup the `lwarpmk` utility:

1. At a command line, try executing `lwarpmk`. If the `lwarpmk` help message appears, then `lwarpmk` is already set up. If not, it is easiest to generate and use a local copy. See section 4.2.1.
2. For MiK $\text{\TeX}$ , try updating the `miktex-misc` package. This may install the `lwarpmk` executable for you.

Otherwise, continue with the following:

3. Locate the file `lwarpmk.lua`, which should be in the `scripts` directory of the TDS tree. On a  $\text{\TeX}$  Live or MiK $\text{\TeX}$  system you may use

Enter  $\Rightarrow$  `kpsewhich lwarpmk.lua`

(If the file is not found, you may also generate a local copy and use it instead. See section 4.2.1.)

4. Create `lwarpmk`:

**Unix:** Create a symbolic link and make it executable:

- (a) Locate the  $\text{\TeX}$  Live binaries:

Enter  $\Rightarrow$  `kpsewhich -var-value TEXMFROOT`

This will be something like:

`/usr/local/texlive/<year>`

The binaries are then located in the `bin/<arch>` directory under the root:

`/usr/local/texlive/<year>/bin/<architecture>/`

In this directory you will find programs such as `pdflatex` and `makeindex`.

- (b) In the binaries directory, create a new symbolic link from the binaries directory to `lwarpmk.lua`:

Enter  $\Rightarrow$  `ln -s <path to lwarpmk.lua> lwarpmk`

- (c) Make the link executable:

Enter  $\Rightarrow$  `chmod 0755 lwarpmk`

**Windows  $\text{\TeX}$  Live:** Create a new `lwarpmk.exe` file:

- (a) Locate the  $\text{\TeX}$  Live binaries as shown above for Unix.

- (b) In the binaries directory, make a *copy* of `runscript.exe` and call it `lwarpmk.exe`. This will call the copy of `lwarpmk.lua` which is in the `scripts` directory of the distribution.

**Windows MiK $\text{\TeX}$ :** Create a new `lwarpmk.bat` file:

- (a) Locate the binaries. These will be in a directory such as:

C:\Program Files\MiKTeX 2.9\miktex\bin\x64

In this directory you will find programs such as pdflatex.exe and makeindex.exe.

- (b) Create a new file named l warpmk.bat containing:

```
texlua "C:\Program Files\MiKTeX 2.9\scripts\l warp\l warpmk.texlua" %*
```

This will call the copy of l warpmk.lua which is in the scripts directory of the distribution.

#### 4.2.1 Using a local copy of l warpmk

It is also possible to use a local version of l warpmk:

1. When compiling the tutorial in section 5, use the l warpmk option for the l warp package:

```
\usepackage[l warpmk]{l warp}
```

2. When the tutorial is compiled with pdflatex, the file l warpmk.lua will be generated along with the other configuration files.

3. l warpmk.lua may be used for this project:

##### Unix:

- (a) Make l warpmk.lua executable:

Enter ⇒ chmod 0755 l warpmk.lua

- (b) Compile documents with

Enter ⇒ ./l warpmk.lua html

Enter ⇒ ./l warpmk.lua print

etc.

- (c) It may be useful to rename or link to a version without the .lua suffix.

##### Windows:

Compile documents with either of the following, depending on which command shell is being used:

Enter ⇒ texlua l warpmk.lua html

Enter ⇒ texlua l warpmk.lua print

etc.

Or:

Enter ⇒ l warpmk.html

Enter ⇒ l warpmk.print

etc.

### 4.3 Installing additional utilities

**To test for the existence of the additional utilities:**

Enter the following in a command line. If each programs' version is displayed, then that utility is already installed. See table 2 on page 45.

```
Enter ⇒ luatex -version
Enter ⇒ xindy -version
Enter ⇒ latexmk -version
Enter ⇒ perl -version
Enter ⇒ pdfcrop -version
Enter ⇒ pdftotext -v
Enter ⇒ pdfseparate -version
Enter ⇒ pdftocairo -v
```

**To install xindy, latexmk, and pdfcrop:**

The TeX utilities xindy, latexmk, and pdfcrop may be provided by your operating system's package manager, and are also provided by the CTAN archive:

```
http://ctan.org/pkg/xindy
http://ctan.org/pkg/latexmk
http://ctan.org/pkg/pdfcrop
```

Prog pdftotext **To install the Poppler utilities to a Unix/Linux system:**

Prog pdfseparate The tools from the POPPLER project should be provided by your operating system's package manager.  
Prog pdftocairo

**To install the Poppler utilities to a MacOS machine:**

1. Install Homebrew from <https://brew.sh/>:  
Enter ⇒  
`/usr/bin/ruby -e "$(curl -fsSL https://raw.githubusercontent.com/Homebrew/install/master/install)"`
2. Install the Poppler utilities:  
Enter ⇒ `brew install poppler`

**To install the Poppler utilities to a Windows machine:**

1. See table 2 on page 45.
2. Download and extract the Poppler utilities pdftotext, pdfseparate, and pdftocairo to a directory, such as Poppler.
3. In the Start window, type "Path" to search for results related to Path. Or, open the control panel and search for "Path".
4. Choose "Edit the system environment variables" in the control panel.
5. Choose the "Environment Variables" button.

6. Choose the "Path" variable, then the "Edit" button.

7. Choose the "New" button to make an additional entry.

8. Enter the bin directory of the Poppler utilities, such as:

C:\Users\<myname>\Desktop\Poppler\poppler-0.5\_x86\poppler-0.5\bin

Be sure to include \bin.

9. Click "Ok" when done.

Prog perl **To install Perl to a Windows machine:**

1. Download and install a version of Perl, such as Strawberry Perl, to a directory without a space in its name, such as C:\Strawberry.

2. Edit the Path as seen above for the Poppler utilities.

3. Enter the bin directory of the Perl utility, such as:

C:\Strawberry\perl\bin

Be sure to include \bin.

4. Click "Ok" when done.

**Any utilities installed by hand must be added to the PATH.**

## 5 Tutorial

This section shows an example of how to create an lwarp document.

### 5.1 Starting a new project

1. Create a new project directory called `tutorial`.
- File `tutorial.tex` 2. Inside the `tutorial` directory, create a new file called `tutorial.tex`. This may be done several ways:

#### Copy from the documentation PDF:

A listing is in fig. 1, which may be copied/pasted from the figure directly into your own editor, depending on the quality of the PDF viewer and editor, or:

#### Copy from the lwarp documentation directory:

Another copy may be found by entering into a command line:

Enter ⇒ `texdoc -l lwarp_tutorial.txt`

This should be in the `doc/latex/lwarp/` directory along with this PDF documentation. Copy `lwarp_tutorial.txt` directly into your `tutorial` directory, renamed as `tutorial.tex`.

#### ⚠️ Bad formatting!

*When using Windows, use an editor other than Notepad, since Notepad does not accept the end-of-line from a Unix text file.*

3. Compile the project:  
Enter ⇒ `pdflatex tutorial.tex`  
(several times)  
(`xelatex` or `lualatex` may be used as well.)
4. View the resulting `tutorial.pdf` with a PDF viewer.

A number of new files are created when `tutorial.tex` is compiled, as shown in table 3. These files are created by the `lwarp` package.

(Two of the new files are configuration files for the helper program `lwarpmk`. Whenever a print version of the document is created, the configuration files for `lwarpmk` are updated to record the operating system, L<sup>A</sup>T<sub>E</sub>X program (`pdflatex`, `xelatex`, or `lualatex`), the filenames of the source code and HTML output, and whether the additional helper program `latexmk` will be used to compile the document.)

Figure 1: tutorial.tex listing

Note: There are two pages!

```
% Save this as tutorial.tex for the lwarp package tutorial.

\documentclass{book}

\usepackage{iftex}

% --- LOAD FONT SELECTION AND ENCODING BEFORE LOADING LWARP ---

\ifPDFTeX
\usepackage{lmodern} % pdflatex
\usepackage[T1]{fontenc}
\usepackage[utf8]{inputenc}
\else
\usepackage{fontspec} % XeLaTeX or LuaLaTeX
\fi

% --- LWARP IS LOADED NEXT ---
\usepackage[
%   HomeHTMLFilename=index,      % Filename of the homepage.
%   HTMLFilename={node-},        % Filename prefix of other pages.
%   IndexLanguage=english,       % Language for xindy index, glossary.
%   latexmk,                   % Use latexmk to compile.
%   OSWindows,                 % Force Windows. (Usually automatic.)
%   mathjax,                   % Use MathJax to display math.
]{lwarp}
% \boolfalse{FileSectionNames} % If false, numbers the files.

% --- OTHER PACKAGES ARE LOADED AFTER LWARP ---
\usepackage{makeidx} \makeindex
\usepackage{xcolor} % (Demonstration purposes only.)
\usepackage{hyperref,cleveref} % LOAD THESE LAST!

% --- LATEX AND HTML CUSTOMIZATION ---
\title{The Lwarp Tutorial}
\author{Some Author}
\setcounter{tocdepth}{2} % Include subsections in the \TOC.
\setcounter{secnumdepth}{2} % Number down to subsections.
\setcounter{FileDepth}{1} % Split \HTML\ files at sections
\booltrue{CombineHigherDepths} % Combine parts/chapters/sections
\setcounter{SideTOCDepth}{1} % Include subsections in the side\TOC
\HTMLAuthor{Some Author} % Sets the HTML meta author tag.
\HTMLLanguage{en-US} % Sets the HTML meta language.
\HTMLDescription{A description.}% Sets the HTML meta description.
\HTMLFirstPageTop{Name and \fbox{HOMEPAGE LOGO}}
```

```

\HTMLPageTop{\fbox{LOGO}}
\HTMLPageBottom{Contact Information and Copyright}
\CSSFilename{l warp_sagebrush.css}

\begin{document}

\maketitle % Or titlepage/titlingpage environment.

% An article abstract would go here.

\tableofcontents % MUST BE BEFORE THE FIRST SECTION BREAK!
\listoffigures

\chapter{First chapter}

\section{A section}

This is some text which is indexed.\index{Some text.}

\subsection{A subsection}

See \cref{fig:withtext}.

\begin{figure}\begin{center}
\fbox{\textcolor{blue!50!green}{Text in a figure.}}
\caption{A figure with text\label{fig:withtext}}
\end{center}\end{figure}

\section{Some math}

Inline math: $r = r_0 + vt - \frac{1}{2}at^2$ followed by display math:
\begin{equation}
a^2 + b^2 = c^2
\end{equation}

\begin{warpprint} % For print output ...
\cleardoublepage % ... a common method to place index entry into TOC.
\phantomsection
\addcontentsline{toc}{chapter}{\indexname}
\end{warpprint}
\ForceHTMLPage % HTML index will be on its own page.
\ForceHTMLTOC % HTML index will have its own toc entry.
\printindex

\end{document}

```

---

Table 3: Files created along with the print version

**tutorial.pdf:** The PDF output from L<sup>A</sup>T<sub>E</sub>X. The print version of the document.

**tutorial\_html.tex:** A small .tex file used to create a parallel HTML version of the document, which co-exists with usual the PDF version, and which will have its own auxiliary files. In this way, both PDF and HTML documents may co-exist side-by-side.

**Auxiliary files:** The usual L<sup>A</sup>T<sub>E</sub>X files .aux, .log, .out, .toc, .lof, .idx. When an HTML version of the document is created, \_html versions of the auxiliary files will also be generated.

**lwarpmk.conf:** A configuration file for lwarpmk, which is used to automate the compilation of PDF or HTML versions of the document.

**tutorial.lwarpmkconf:** Another configuration file used by lwarpmk, which is only useful if you wish to have several projects residing in the same directory.

**.css files:** lwarf.css, lwarf\_formal.css, lwarf\_sagebrush.css These files are standard for lwarf, and are not meant to be modified by the user.

**sample\_project.css:** An example of a user-customized css file, which may be used for project-specific changes to the lwarf defaults.

**lwarf.xdy:** Used by lwarf while creating an index. This file should not be modified by the user. A custom file may be used instead, if necessary.

**lwarf\_mathjax.txt:** Inserted into the HTML files when MathJax is used to display math. This file should not be modified by the user.

**comment.cut:** A temporary file used by lwarf to conditionally process blocks of text. This file may be ignored.

---

When the lwarpmk option is given to the lwarf package:

**lwarpmk.lua:** A local copy of the lwarpmk utility.

On Unix-related operating systems this file must be made executable:

```
chmod u+x lwarpmk.lua
```

This may be useful to have to archive with a project for future use.

## 5.2 Compiling the print version with `lwarpmk`

The `lwarpmk` utility program is used to compile either the printed or the HTML version of the document.

`lwarpmk print` is used to recompile a printed version of the document.

1. Re-compile the print version:

Enter ⇒ `lwarpmk print`

`lwarpmk` prints an introduction then checks to see if the document must be recompiled. If it seems that the files are up-to-date, then `lwarpmk` informs you of that fact and then exits.

2. Make a small change in the original document, such as adding a space character.
3. Recompile again.

Enter ⇒ `lwarpmk print`

The document is recompiled when a change is seen in the source. Several compilations may be necessary to resolve cross-references.

4. Force a recompile to occur.

Enter ⇒ `lwarpmk again`

Enter ⇒ `lwarpmk print`

`lwarpmk again` updates the date code for the file, triggering a recompile the next time the document is made.<sup>3</sup>

5. Process the index.<sup>45</sup>

Enter ⇒ `lwarpmk printindex`

6. Recompile again to include the index.

Enter ⇒ `lwarpmk print`

7. To force a single recompile when needed, even if no changes were detected:

Enter ⇒ `lwarpmk print1`

Note that the HTML customization commands are ignored while making the print version.

---

<sup>3</sup>Although, when using the utility `latexmk` (introduced later), the changed date is ignored and an actual change in contents must occur to cause a recompile.

<sup>4</sup>A `lwarpmk printglossary` command is also available to process a glossary produced with the `glossaries` package. See section 7.4.8.

<sup>5</sup>Also see section 7.4.9 for index options.

### 5.3 Compiling the HTML version with lwarpmk

`lwarpmk html` is used to recompile an HTML version of the document.

1. Compile the HTML version:

Enter ⇒ `lwarpmk html`

- (a) `lwarpmk` uses  $\text{\LaTeX}$  to process `tutorial_html.tex` to create `tutorial_html.pdf`.
- (b) `pdftotext` is then used to convert to the file `tutorial_html.html`. This file is a plain-text file containing HTML tags and content for the entire document.
- (c) `lwarpmk` manually splits `tutorial_html.html` into individual HTML files according to the HTML settings. For this tutorial, the result is `tutorial.html` (the home page), along with `First-chapter.html`<sup>6</sup>, `Some-math.html`, and the document's index in `_Index.html`.<sup>7</sup>

2. View the homepage in a web browser.

Open the file `tutorial.html` in a web browser.

#### math

Note that math is still displayed as its plain-text  $\text{\LaTeX}$  source until the images of the math expressions have been generated. Math may be displayed as SVG images or by a MathJax script, as seen in sections 5.4 and 5.5.

3. Force a recompile:

Enter ⇒ `lwarpmk again`

Enter ⇒ `lwarpmk html`

Enter ⇒ `lwarpmk print`

4. Process the HTML index and recompile.<sup>89</sup>

Enter ⇒ `lwarpmk htmlindex`

Enter ⇒ `lwarpmk html`

`_Index.html` is updated for the new  $\text{\LaTeX}$  index.

5. Reload the web page to see the added index.

6. To force a single recompile when needed, even if no changes were detected:

Enter ⇒ `lwarpmk html1`

---

<sup>6</sup>`First-chapter.html` also contains the first section, even though the second section is its own HTML page. This behavior is controlled by the boolean `CombineHigherDepths`.

<sup>7</sup>`index.html` is commonly used as a homepage, so the document index is in `_Index.html`.

<sup>8</sup>A `lwarpmk htmlglossary` command is also available to process a glossary produced with the `glossaries` package. See section 7.4.8.

<sup>9</sup>Also see section 7.4.9 for index options.

## 5.4 Generating the SVG images

### math as svg images

By default lwarf represents math as svg images with the  $\text{\LaTeX}$  source included in `alt` attributes. In this way, the math displays as it was drawn by  $\text{\LaTeX}$ , and the  $\text{\LaTeX}$  source may be copied and pasted into some other document.

### picture and Tikz

lwarf uses the same mechanism for `picture` and `Tikz` environments.

1. Create the svg images:

Enter  $\Rightarrow$  `lwarfpmk limages`

Enter  $\Rightarrow$  `lwarfpmk html`

2. Move to the tutorial's math page and reload.
3. The math images are displayed using the same font and formatting as the printed version.
4. Copy/paste a math expression into a text editor to see the  $\text{\LaTeX}$  source.

### Adding/removing

When a math expression, `picture`, or `Tikz` environment is added or removed, the svg images must be re-created with `lwarfpmk limages` to maintain the proper image file sequence numbers.

### HTML instead of images

If `HTML` appears where an svg image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time.

Expressing math as svg images has the advantage of representing the math exactly as  $\text{\LaTeX}$  would, but has the disadvantage of requiring an individual file for each

### Lots of files!

math expression. There is no attempt at reusing the same file each time the same expression occurs, so each time `$x$` is used, for example, yet another file is created. For a document with a large amount of math, see section 5.5 to use MathJax instead.

## 5.5 Using MathJax for math

[math with MathJax](#) Math may also be represented using the MathJax Javascript project.

1. In the tutorial's source code, uncomment the `mathjax` package option for `lwarf`:

```
mathjax, % Use MathJax to display math.
```

2. Recompile

Enter ⇒ `lwarfpmk html`

3. Reload the math page.

⚠ **MathJax requirements**

MathJax requires web access unless a local copy of MathJax is available, and it also requires that Javascript is enabled for the web page. The math is rendered by MathJax. Right-click on math to see several options for rendering, and for copying the  $\text{\LaTeX}$  source.

While using MathJax has many advantages, it may not be able to represent complex expressions or spacing adjustments as well as  $\text{\LaTeX}$ , and it may not support some math-related packages.

## 5.6 Changing the CSS style

`\CSSFilename` `\CSSFilename` may be used to choose which .css file is used to display each section of the web page. Use `\CSSFilename` before `\begin{document}` to assign the style of the home page. If different parts of the website should have different styles, call `\CSSFilename` again before each section heading which creates a new file.

The styles provided by lwarf include:

`lwarf.css`: A default style if `\CSSFilename` is not used. This style is comparable to a plain L<sup>A</sup>T<sub>E</sub>X document. To set this style, you may use `\CSSFilename{lwarf.css}`, or no `\CSSFilename` call at all.

`lwarf_formal.css`: A formal style with a serif fonts and a traditional look.

`lwarf_sagebrush.css`: A style with muted colors, gradient backgrounds, additional borders, and rounded corners.

To see each style in use, change the `\CSSFilename` entry in the tutorial, `lwarpmk html` again, and then reload the webpage.

**Custom css** A customized style may also be created. For each new project a file called `sample_project.css` is generated. This may be renamed to `<project>.css` then used by assigning `\CSSFilename{<project>.css}`.

 **Rename it!** Note that `sample_project.css` is overwritten whenever lwarf is loaded in print mode. It is therefore important to rename the file to something like `<project>.css` before using it, so that your own changes are not overwritten.

`<project>.css` has an entry which loads `lwarf.css`, and this entry may be changed to load `lwarf_formal.css` or `lwarf_sagebrush.css` if desired. Additional changes to the css may be made by making entries later in the `<project>.css` file.

## 5.7 Customizing the HTML output

Several settings may be used to customize the HTML output. Watch for the correct placement of each!

**⚠ Placement!** Note that if changes are made, it is best to first:

1. Clear all the HTML, PDF, and auxiliary files:

Enter ⇒ `lwarpmk clearall`

2. Recompile the print version in order to recreate the configuration files for `lwarpmk`:

Enter ⇒ `lwarpmk print`

3. Finally, recompile the HTML version with the new settings:

Enter ⇒ `lwarpmk html`

### Options for the `lwarp` package:

Use the following as options for `\usepackage[<options>]{lwarp}`:

Opt `HomeHTMLFilename`

**HomeHTMLFilename:** Filename of the homepage, without the “.html” suffix.  
Defaults to the `\BaseJobname`. A common setting is:

`HomeHTMLFilename=index`

filename underscores

causing the homepage to be the file `index.html`. Underscores are allowed in `HomeHTMLFilename` and `HTMLFilename` options, but may need to be escaped elsewhere, such as when appearing in a list:

`\item [\href{file\_name.pdf}{text}] \`

Opt `HTMLFilename`

**HTMLFilename:** A filename prefix for the rest of the HTML web pages. Useful for numbered web pages with a common prefix. May be empty.

Opt `latexmk`

**latexmk:** Controls whether `lwarp` uses `latexmk` to compile the document.  
This setting is written to `lwarpmk`'s configuration files. Defaults to false.

Opt `mathsvg`

**mathsvg:** Selects SVG display for math output. (The default.)

Opt `mathjax`

**mathjax:** Selects MathJax for math output.

### Placed in the preamble before `\begin{document}`:

Ctr `tocdepth`

**tocdepth:** Sectioning depth of the table of contents. See section 13 for a list of `LATEX` stack depths.

Ctr **SideTOCDepth** **SideTOCDepth:** Sectioning depth of the sidetoc. Defaults to 1, causing the sidetoc to show sections but not subsections.

**sidetoc** Each subpage of the website has its own small table of contents on the side (the “sidetoc”). Its depth is set by SideTOCDepth. This sidetoc is only shown if the web page is wide enough. When using a narrow web browser window, “responsive web design” is used to show the sidetoc at the top of the page and a link back to “Home” at the bottom.

It is recommended to set:

`SideTOCDepth = FileDepth`

or

`SideTOCDepth = FileDepth+1`



If `SideTOCDepth < FileDepth`, web pages will be inaccessible via the sidetoc.

Ctr **FileDepth** **FileDepth:** Sectioning depth of file splits. Defaults to -5, causing the entire HTML website to be one single file.

- To place the entire file into one HTML page, use:  
`\setcounter{FileDepth}{-5}`
- To split the HTML file at \section depth, use:  
`\setcounter{FileDepth}{1}`
- To ensure that the HTML pages/files are accessible:  
Place a `\tableofcontents` somewhere before the first section break (therefore in the “home page”), and set  
`tocdepth >= FileDepth`



Bool **CombineHigherDepths**

**CombineHigherDepths:** Combine a higher section with its first lower subsections, down to the FileDepth. Defaults to true. Set to false to simulate the concept of a chapter opening on its own page, for example.

The file splits are controlled by the counter FileDepth and the boolean CombineHigherDepths. Setting FileDepth to 0 splits the file at chapters, 1 at sections, etc. CombineHigherDepths controls whether to combine pages at levels higher than the chosen FileDepth, such as in this tutorial where the page which opens the chapter also contains the first section. Be careful to set tocdepth and SideTOCDepth to allow access to each page of the website. Set tocdepth and SideTOCDepth to be greater than or equal to FileDepth.

Inaccesible pages!

Lost in an old page!

When making changes to the file structure, it is possible to end up with the web browser pointing to an old file which is no longer in use. When this occurs, changes to the web site will not appear in the browser, even if reloading the page, because that page is no longer in use. It is best to return to the home page, clean the files (`lwarpmk cleanall`), change

FileDepth and/or CombineHigherDepths, then finally recompile and renavigate to the desired page using the new file structure.

**Bool FileSectionNames** If true, web page filenames are derived from a sanitized version of the section names. If false, web pages are numbered. Either way, the HTMLFilename option is used as a prefix.

**HTML filenames** Example HTML filenames:

**Numbered HTML nodes:**

Example: Homepage index.html, and node-1, node-2.<sup>10</sup>

---

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={node-}
]{lwarp}
\boolfalse{FileSectionNames}
```

---

**Named HTML sections, no prefix:**

Example: index.html, and About.html, Products.html

---

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={}
]{lwarp}
\booltrue{FileSectionNames}
```

---

**Named HTML sections, with prefix:**

Example: Homepage mywebsite.html, and additional pages such as mywebsite-About.html, etc.

---

```
\usepackage[
    HomeHTMLFilename=mywebsite,
    HTMLFilename={mywebsite-}
]{lwarp}
\booltrue{FileSectionNames}
```

---

**\abstractname** \abstractname: The name of the abstract. This may also be over-written by the babel package. Defaults to “Abstract”.

**Placed before \begin{document}, or before any sectioning command which causes a file break:**

**\CSSFilename** \CSSFilename: {<filename.css>} Sets the css file to use for the following files. May be changed before each each sectioning command which would cause a file split.

---

<sup>10</sup>See \SetHTMLFileName to number grouped by chapter, for example.

The css styles of the web pages are set by the \CSSFilename command. If \CSSFilename is not used, a default plain style is used to mimic printed L<sup>A</sup>T<sub>E</sub>X output. lwarp\_sagebrush.css is a semi-fancy colored style as shown in this tutorial. Change it to lwarp\_formal.css for a more formal look, or comment out the \CSSFilename command to see the default. \CSSFilename may be used before each file break to set the css for individual pages of the website.

\HTMLLanguage	\HTMLLanguage: The HTML file's html lang tag. Defaults to en-US.
\HTMLAuthor	\HTMLAuthor: The HTML header's meta author. Defaults to \theauthor.
\HTMLDescription	\HTMLDescription: {\<description>} Sets the HTML description tag for the following files. May be changed before each sectioning command which would cause a file split.
\HTMLFirstPageTop	\HTMLFirstPageTop: {\<contents>} A user-definable custom action applied to the top of the home page. Useful for logos, etc. Defaults empty. Ignored in print output.
\HTMLPageTop	\HTMLPageTop: {\<contents>} A user-definable custom action applied to the top of pages other than the home page. Useful for logos, etc. Defaults empty. \LinkHome may be used to place a link back to the homepage. Ignored in print output.
\HTMLPageBottom	\HTMLPageBottom: {\<contents>} A user-definable custom action applied to the bottom of each web page. Useful for authors, copyright notices, contact information, etc. Defaults empty. \LinkHome may be used to place a link back to the homepage. Ignored in print output.

**Placed in the home page before the first sectioning command which causes a file break:**

\tableofcontents ⚠ TOC on the homepage!	\tableofcontents: Used to place a table of contents on the home page. This command must be used before the first file split, so that a way is available to navigate to other files from the homepage.  Links to each chapter/section are provided, as selected by tocdepth.
--	---

**Placed in the document wherever necessary:**

Env warpprint	warpprint: An environment which is only used while generating print output. Place here anything which does not apply to HTML and which may cause problems with lwarp. If lwarp knows about and emulates or supports a package then its related macros, lengths, counters, etc. probably won't have to be placed inside a warpprint environment, but unknown packages may cause problems which may be isolated from lwarp using this environment.
---------------	--

Env \warpHTML	<b>warpHTML:</b> An environment which is only used while generating HTML output. This is useful for website logos and other items which have no purpose in printed output.
\warpprintonly	\warpprintonly: { <i>contents</i> } A macro version of the warpprint environment.
\warpHTMLonly	\warpHTMLonly: { <i>contents</i> } A macro version of the warpHTML environment.

## 5.8 Using `latexmk`

`latexmk` is a L<sup>A</sup>T<sub>E</sub>X utility used to monitor changes in source files and recompile as needed.

1. In the tutorial's source code uncomment the `latexmk` option for the `lwarp` package:

```
latexmk, % Use latexmk to compile.
```

2. Recompile the printed version of the document.

Enter ⇒ `lwarpmk print`

`lwarp` updates its own configuration files (`lwarpmk.conf` and `tutorial.lwarpmkconf`) whenever the printed version of the document is compiled. These configuration files remember that `lwarpmk` should use `latexmk` to compile the document.

3. Recompile the document.

Enter ⇒ `lwarpmk print`

and/or

Enter ⇒ `lwarpmk html`

Changes are detected by comparing checksums rather than modification times, so `lwarpmk` again will not trigger a recompile, but `latexmk` has a much better awareness of changes than the `lwarpmk` utility does and it is likely to correctly know when to recompile. A recompile may be forced by making a small change to the source.

[forced single-pass recompile](#) A single recompile may be forced with:

Enter ⇒ `lwarpmk print1`

and/or

Enter ⇒ `lwarpmk html1`

## 5.9 Using XeLaTeX or LuaLaTeX

Xe $\text{\TeX}$  or Lua $\text{\TeX}$  may be used instead of  $\text{\TeX}$ .

1. Remove the auxiliary files for the project:

Enter  $\Rightarrow$  lwarfmk cleanall

2. Use xelatex or lualatex to recompile the printed version.

Enter  $\Rightarrow$  xelatex tutorial.tex

-or-

Enter  $\Rightarrow$  lualatex tutorial.tex

When the recompile occurs, the configuration files for lwarfmk are modified to remember which  $\text{\TeX}$  engine was used. Xe $\text{\TeX}$  or Lua $\text{\TeX}$  will be used for future runs of lwarfmk.

3. To recompile the document:

Enter  $\Rightarrow$  lwarfmk print

-and-

Enter  $\Rightarrow$  lwarfmk html

4. Also rememeber to update the indexes and recompile again.

## 5.10 Using a glossary

lwarf supports the glossaries package, although this tutorial does not supply an example.

- Opt `IndexLanguage` To assign a language to be used while processing the index and glossary, use the `IndexLanguage` option:

---

```
\usepackage[IndexLanguage=english]{lwarf}
```

---

To process the glossary for the print version:

Enter ⇒ `lwarfmk printglossary`

To process the glossary for the HTML version:

Enter ⇒ `lwarfmk htmlglossary`

In each case, the document will have to be recompiled afterwards.

## 5.11 Cleaning auxiliary files

To remove the auxiliary files .aux, .toc, .lof, .lot, .idx, .ind, .log, and .gl\*:

Enter ⇒ lwarpmk clean

## 5.12 Cleaning auxiliary and output files

To remove the auxiliary files, and also remove the .pdf and .html files:

Enter ⇒ lwarpmk cleanall

## 5.13 Processing multiple projects in the same directory

It is possible to have several projects in the same directory. `lwarpmk` has an optional parameter which is the document to compile.

To create each project:

Enter ⇒ pdflatex project\_a

Enter ⇒ pdflatex project\_b

Each project is given its own configuration file:

project\_a.lwarpmkconf, project\_b.lwarpmkconf

To compile each project with `lwarkmk`:

Enter ⇒ lwarpmk print project\_a

Enter ⇒ lwarpmk html project\_b

## 5.14 Using the make utility

`lwarpmk` has an action which may be useful for integration with the common `make` utility:

lwarpmk pdftohtml [project]

`make` may be used to compile the code to PDF with HTML tags (`project_html.pdf`), then `lwarpmk` may be used to convert each target to HTML files.

## 6 Additional details

### 6.1 Font and UTF-8 support

lwarf uses pdftotext to convert PDF output into UTF-8-encoded text. This process requires that UTF-8 information be embedded in the PDF file, which usually prevents the use of bit-mapped fonts.

**vector fonts**  
**Computer Modern** While using pdflatex, if no font-related package is specified, the default bit-mapped Computer Modern font is used, so simply add



```
\usepackage{lmodern}
```

to the preamble to enable the related vector font instead, or use

```
\usepackage{dejavu}
```

or other other font packages, which may provide an increased coverage of Unicode mappings. Avoid bit-mapped fonts.



X<sub>E</sub>T<sub>E</sub>X and Lua<sub>E</sub>T<sub>E</sub>X users must use the fontspec package. Do NOT use fontenc!

Place fontspec or fontenc and other font and UTF-8 related commands after the \documentclass command and before \usepackage{lwarf}:

1. `documentclass{article/book/report}` goes here, followed by any of:
2. Font and UTF-8 related commands:

- For X<sub>E</sub>T<sub>E</sub>X or Lua<sub>E</sub>T<sub>E</sub>X:

Pkg **fontspec**

- fontspec and font choices

**ligatures**

lwarf sets the following to turn off T<sub>E</sub>X ligatures during the generation of HTML tags, and turn off common ligatures in regular text, since older browsers may not display them correctly and newer browsers can automatically re-create them.

---

```
\defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
```

---

- For pdflatex:

Pkg **lmodern**

- lmodern or other font-related packages

Pkg **fontenc**

- fontenc

Pkg **inputenc**

- inputenc

Pkg **newunicodechar**

- newunicodechar

File	<code>glyptounicode</code>	- \input glyptounicode.tex - \input glyptounicode-cmr.tex% from the pdfx package - \pdfgentounicode=1
Pkg	<code>cmap</code>	- cmap
Pkg	<code>textcomp</code>	- textcomp
Pkg	<code>microtype</code> <code>ligatures</code>	- microtype is automatically used by lwarf to turn off f,q,t,TQ ligatures for the same browser-related reasons shown above. Also, the monospaced font is used during HTML tag generation to turn off $\text{\TeX}$ ligatures.

3. `\usepackage{lwarf}` (section 6.2) goes after any of the above, followed by:
4. ... the rest of the preamble and the main document.

### 6.1.1 Indexes and UTF-8

lwarf uses the `xindy` program to processes indexes.

While using `xelatex` or `lualatex`, `xindy` is used for the index. Everything is handled in UTF-8 encoding, and should work as expected.

While using `pdflatex`, the `texindy` program is used with the `-C utf8` option, which is newly supported in recent distributions of  $\text{\TeX}$ . This option correctly sorts index entries into headings while using Latin languages, but will not work well with others. `X\TeX` or `Lua\TeX` are recommended for non-Latin languages.

For an older distribution of  $\text{\TeX}$ , it may be necessary to generate a local version of `lwarpmk.lua` and modify it to remove the `-C utf8` option from the `texindy` call. See section 10.4.

## 6.2 lwarf package loading and options

lwarf supports `book`, `report`, and `article` classes.

Pkg	<code>lwarf</code>	Load the lwarf package immediately after the font and UTF-8 setup commands.
Opt	<code>warpprint</code>	Select the <code>warpprint</code> option to generate print output (default), or the <code>warpHTML</code> option to generate HTML output. The default is print output, so the print version may be compiled with the usual <code>pdflatex</code> , etc. When lwarf is loaded in print mode, it creates <code>&lt;project&gt;.html.tex</code> , which sets the <code>warpHTML</code> option before calling the user's source code <code>&lt;project&gt;.tex</code> . In this way, <code>&lt;project&gt;.tex</code> can <code>\usepackage{lwarf}</code> without any options to create a printed version, while <code>&lt;project&gt;.html.tex</code> will create an HTML version.
Opt	<code>mathsvg</code>	For math display, select <code>mathsvg</code> (default), or <code>mathjax</code> . For more information about
Opt	<code>mathjax</code>	

Table 4: Package options

Option	Description
<code>warpprint</code>	Generate print output, and also generate configuration files.
<code>warpHTML</code>	Generate HTML output.
<code>mathsvg</code>	Show math using SVG images.
<code>mathjax</code>	Show math using MathJax.
<code>OSWindows</code>	Force compatibility with MS-Windows.
<code>BaseJobname</code>	The <code>\jobname</code> to use. Set to the <code>\jobname</code> of the printed version even while generating HTML.
<code>HomeHTMLFilename</code>	The filename of the home page.
<code>HTMLFilename</code>	A prefix for the filenames of the remaining web pages.
<code>IndexLanguage</code>	The <code>xindy</code> language option used for index and glossary generation.
<code>latexmk</code>	Boolean for <code>lwarpmk</code> to use <code>latexmk</code> for compiling documents. Otherwise, <code>lwarpmk</code> attempts to recompile several times by itself.
<code>lwarpmk</code>	Generate a local copy of <code>lwarpmk.lua</code> .
<code>xdyFilename</code>	Tells <code>lwarpmk</code> to use a custom filename for <code>xindy</code> , instead of <code>lwarf.xdy</code> .

the math options, see section [7.5](#).

See table [4](#) for the full list of options.

### 6.3 Selecting the operating system

Prog Unix	<code>lwarf</code> tries to detect which operating system is being used. UNIX / MAC OS / LINUX is the default (collectively referred to as “UNIX” in the configuration files), and MS-WINDOWS is supported as well.
Prog Mac OS	
Prog Linux	
Prog MS-Windows	If WINDOWS is not correctly detected, use the <code>lwarf</code> option <code>OSWindows</code> .
Prog Windows	
Opt OSWindows	When detected or specified, the operating-system path separator used by <code>lwarf</code> is modified, the boolean <code>usingOSWindows</code> is set true. This boolean may be tested by the user for later use.

## 6.4 Selecting actions for print or HTML output

The following environments and macros are used to select actions which only apply to either traditional L<sup>A</sup>T<sub>E</sub>X print-formatted PDF generation, or to HTML generation.

For most of built-in L<sup>A</sup>T<sub>E</sub>X and many additional packages there is user-level source code support or emulation, so no special handling will be required. For those cases which lwarp does not handle by itself, the following environments and macros may be used to isolate sections of code for print-only or HTML-only.

These environments are also useful for creating a special version of the titlepage for print and another for HTML.

Env `warpHTML` Anything which is to be done only for HTML output is surrounded by a `warpHTML` environment:

---

```
\begin{warpHTML}
  ... something to be done only during HTML generation
\end{warpHTML}
```

---

Env `warpprint` Anything which is to be done only for print output is surrounded by a `warpprint` environment:

---

```
\begin{warpprint}
  ... something to be done only during traditional PDF generation
\end{warpprint}
```

---

Env `warpall` Anything which is to be done for any output may be surrounded by a `warpall` environment. Doing so is optional.

---

```
\begin{warpall}
  ... something to be done during print PDF or HTML output
\end{warpall}
```

---

Macros are also provided for print-only or HTML-only code:

`\warpprintonly {<actions>}`

Performs the given actions only when print output is being generated.

`\warpHTMLonly {<actions>}`

Performs the given actions only when HTML output is being generated.

## 6.5 Commands to be placed into the warpprint environment

Certain print-related commands should always be placed inside a warpprint environment, or may need other special handling. These are unrelated to HTML output, but are hard to isolate automatically. For example:

- Paragraph formatting: \parindent \parskip
- Manual page positions such as the textpos package, which is emulated but only in a limited way.

Some packages require additional setup commands. Where these packages are emulated for HTML, setup commands may work for the emulated HTML output as well as for print output. See the details for each package in this document for more information.

Also see section 11: [Troubleshooting](#).

## 6.6 Title page

In the preamble, place an additional block of code to set the following:

---

```
\title{Document Title} % One line only
\author{Author One\affiliation{Affiliation One} \and
        Author Two\affiliation{Affiliation Two} }
\date{Optional date}
```

---

The title is used in the meta tags in the HTML files, and the rest are used in \maketitle. To use a \subtitle or \published field, see section 52.7.

\maketitle Use \maketitle just after the \begin{document}, as this will establish the title of the homepage. Optionally, use a titlepage environment instead.

Env titlepage The titlepage environment may be used to hold a custom title page. The titlepage will be set in a <div> class titlepage, and \printtitle, etc. may be used inside this environment.

Env titlingpage Another form of custom title page, where \maketitle is allowed, and additional information may be included as well.

\title {\(title)}

 Avoid newlines in the \title; these will interfere with the file break and css detection. Use a \subtitle command instead (section 52.7). In HTML, the title will appear in a

heading <h1>.

\author {\langle author \rangle}

 In \author, use \protect before formatting commands such as \textsc. In HTML, the author will appear in a <div> class author. \affiliation is a new addition to \warp.

\date {\langle date \rangle}

\date works as expected. In HTML, this will appear in a <div> class titledate.

\thanks {\langle text \rangle}

\thanks are allowed in the titlepage fields, and will be rendered as HTML notes at the bottom of the title page.

## 6.7 HTML page meta descriptions

\HTMLDescription {\langle A description of the web page. \rangle} The default is no description.

**limitations** Each page of HTML output should have its own HTML meta description, which usually shows up in web search results, is limited to around 150 characters in length, and should not include the ASCII double quote character (").

**placement** Use \HTMLDescription just before \begin{document} to set the description of the home page, and also just before each sectioning command such as \chapter or \section where a new file will be generated, depending on FileDepth. For example, if FileDepth is 1, use \HTMLDescription just before each \section command, and that description will be placed inside the HTML page for that \section. The same description will be used for all following HTML files as well, until reset by a new \HTMLDescription. It is best to use a unique description for each HTML file.

**disabling** To disable the generation of HTML description meta tags, use:  
\HTMLDescription{}

## 6.8 HTML page meta author

\HTMLAuthor {\langle author \rangle} Sets the contents of the web page <meta name="author"> element. Defaults to \HTMLAuthor{\theauthor}. May be set empty to cancel the meta author tag.

## 6.9 CSS

File `lwarp.css` It is best to make a local project-specific css file such as `project.css`, containing only things which are different from `lwarp.css`. `project.css` should refer to `lwarp.css` as follows:

---

```
/* ( --- Start of project.css --- ) */
/* A sample project-specific CSS file for lwarp --- ) */

/* Load default lwarp settings: */
@import url("lwarp.css") ;
/* or lwarp_formal.css, lwarp_sagebrush.css */

/* Project-specific CSS setting follow here. */
/* . . . */

/* ( --- End of project.css --- ) */
```

---

An example file called `sample_project.css` is provided, and may be renamed `project.css`.

`\CSSFilename` For each section at which HTML files are split, `\CSSFilename` may be used before the sectioning command to select a css file for that and all following sections. This may be changed numerous times throughout the file, resulting in different HTML pages having different css files assigned:

```
...
\newCSS{myCSS.css}
\chapter{Another Chapter}
...
```

## 6.10 Modifying xindy index processing

Prog `xindy` `lwarpmk` uses the file `lwarp.xdy` to process the index. This file is over-written by `lwarp` whenever a print version of the document is processed.

To customize index processing:

1. Copy `lwarp.xdy` to a new filename such as `projectname.xdy`
2. Make changes to `projectname.xdy`. Keep the line which says

```
(markup-locref :open "\hyperindexref{" :close "}")
```

This line creates the hyperlinks for the HTML index. During print output `\hyperindexref` becomes a null function.

`Opt xdyFilename` 3. In the document source use the `xdyFilename` option for `lwarp`:

```
\usepackage[
    ... other options ...
    xdyFilename=projectname.xdy,
]{lwarp}
```

4. Recompile the print version, which causes `lwarp` to rewrite the `lwarpmk.conf` configuration file. This tells `lwarpmk` to use the custom `projectname.xdy` file instead of `lwarp.xdy`.

## 7 Special cases and limitations

Also see section 11: [Troubleshooting](#).

Some commonly-used L<sup>A</sup>T<sub>E</sub>X expressions should be modified to allow for a smooth conversion to both HTML and print-formatted outputs:

### 7.1 Formatting

#### 7.1.1 Text formatting

`\textbf`, etc. are supported, but `\bfseries`, etc. are not yet supported.

#### 7.1.2 Horizontal space

`\hspace` `\hspace` is converted to an inline HTML span of the given width, except that 0 width is ignored, a width of `.16667em` is converted to an HTML thin breakable space (U+2009), and a `\fill` is converted to a `\qquad`.

`\,`, `\~` and `\,`, are converted to HTML entities.

`\kern` `\kern` and `\hskip` are treated as a single normal space.  
`\hskip`

#### 7.1.3 Text alignment

Use the environments `center`, `flushright`, `flushleft` instead of the macros `\centering`, `\raggedright`, `\raggedleft`.

### 7.1.4 Accents

Native  $\text{\LaTeX}$  accents such as  $\text{\texttt{"}}$  will work, but many more kinds of accents are available when using Unicode-aware  $\text{\XeLaTeX}$  and  $\text{\LuaLaTeX}$ .

### 7.1.5 Textcomp

Some textcomp symbols do not have Unicode equivalents, and thus are not supported.

-  **Missing symbols** Many textcomp symbols are not supported by many fonts. Try using more complete fonts in the `css`, but expect to see gaps in coverage.

### 7.1.6 Superscripts and other non-math uses of math mode

Use `\textsuperscript{x}` instead of `$^x$`

### 7.1.7 Empty `\item` followed by a new line of text or a nested list:

Use a trailing backslash: `\item[label] \`

### 7.1.8 Filenames in lists

- filename underscore** Escape underscores in the filenames:

```
\item[\text{\ href{file\_name.pdf}}{text}]
```

### 7.1.9 `relsize` package

For `HTML` only the inline macros are supported: `\textlarger`, `\textsmaller`, and `\textscale`. Each becomes an inline span of a modified `font-size`.

`\relsize`, `\larger`, `\smaller`, and `\relscale` are ignored.

While creating `SVG` math for `HTML`, the original definitions are temporarily restored, and so should work as expected.

-  **not small** The `HTML` browser's setting for minimum font size may limit how small the output will be displayed.

## 7.2 Boxes and minipages

### 7.2.1 Save Boxes

TEX boxes are placed inline and do not allow line breaks, so boxes with long contents may overflow the line during HTML conversion. This is mostly a problem when the boxes contain objects which themselves hold large HTML tags, such as rotation commands with long contents. When this object overflows the line, some HTML code will be lost and the page will be corrupted.

### 7.2.2 Minipages

 **inline** A line of text with an inline minipage or parbox will have the minipage or parbox placed onto its own line, because a paragraph is a block element and cannot be made `inline-block`.

**placement** Minipages and parboxes will be placed side-by-side in HTML unless you place a `\newline` between them.

**side-by-side** Side-by-side minipages may be separated by `\quad`, `\quad`, `\enskip`, `\hspace`, `\hfill`, or a `\rule`. When inside a `center` environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side minipages and these spacing commands, but not at the start or end of the paragraph.

**in a span** There is limited support for minipages inside an HTML `<span>`. An HTML `<div>` cannot appear inside a `<span>`. While in a `<span>`, minipages, and parboxes, and any enclosed lists have limited HTML tags, resulting in an “inline” format, without markup except for HTML breaks. Use `\newline` or `\par` for an HTML break.

**size** When using `\ linewidth`, `\ textwidth`, and `\ textheight`, widths and heights are scaled proportionally to a 6×9 inch text area.

**no-width minipages** A minipage of width exactly `\ linewidth` is automatically given no HTML width.

**full-width minipages** A new macro `\minipagefullwidth` requests that the next minipage be generated without an HTML `width` attribute, allowing it to be the full width of the display rather than the fixed width given.

 **text alignment** Nested minipages adopt their parent’s text alignment in HTML, whereas in regular TEX PDF output they do not. Use a `flushleft` or similar environment in the child minipage to force a text alignment.

### 7.2.3 Side-by-side minipages

Place side-by-side minipages inside a `center` environment, with horizontal space between them, such as `\quad`, `\quad`, `\hspace`, or `\hfill`. The result is similar in print and HTML. Do not use space commands at the start or end of the line.

### 7.2.4 Framed minipages and other environments

`\fbox` can only be used around inline `<span>` items during HTML output, but HTML cannot place a block element such as a `<div>` for a minipage or a list inside of a `<span>`. Several options are provided for framing an object, depending on which kind of object and which packages are loaded:

- `\fbox` For a framed object, options include:  
`\fboxBlock`
- Env `fminipage` **To remove the frame in HTML output:** Place the `\fbox` command and its closing brace inside `\warpprint` environments. This will nullify the frame for HTML output.

- For inline text: **To frame the contents inline with some formatting losses in HTML:** This is the default action of `\fbox` when enclosing a minipage. During HTML output, `\fbox` nullifies the HTML tags for `minipage`, `\parbox`, and lists. The contents are included as inline text inside the `\fbox`'s `<span>` of class `framebox`. For lists, line breaks are converted to HTML breaks. The result is a plain-text inline version of the contents, framed inline with the surrounding text, but lacking any extra HTML markup.

- For inline `minipage` and lists: **To frame the contents on their own line with improved formatting in HTML:** A new command `\fboxBlock` is included, intended to be a direct replacement for `\fbox` for cases where the `\fbox` surrounds a minipage, table, or list. For print output, this behaves as `\fbox`. For HTML output, the contents are placed inside an HTML `<div>` with the class `framed`, resulting in the contents being placed on their own line with a frame surrounding them. The contents preserve their HTML formatting, so lists and minipages look nicer, and valid HTML is created for a `tabular`. While an `\fbox` containing a `tabular` is valid L<sup>A</sup>T<sub>E</sub>X code, the result in HTML is problematic since a table is a `<div>` not a `<span>`, so use `\fboxBlock` around a `tabular`, or else place the `tabular` inside a `minipage`, or use `fminipage`, described next. Also see below regarding the “Misplaced alignment tab character &” error.

- For display `tabular`, `minipages`, and lists: **To create a framed minipage in both print and HTML:** A new environment `fminipage` is included. For print output, this is identical to `minipage`, except that it is also framed. For HTML output, this forms a `<div>` of class `framed`, the contents preserve their HTML formatting, and valid HTML is created for a `tabular`. Also see below regarding the “Misplaced alignment tab character &” error.

**colored boxes and frames:** **To create colored frames and boxes:** See section 239 for xcolor's \colorbox and \fcolorbox, and lwarp's additional \colorboxBlock and \fcolorboxBlock.

**⚠ Misplaced alignment tab character &** **To frame tables or verbatim environments:** Place the contents inside a fminipage, or perhaps a \fboxBlock for a tabular. Also, if using \fboxblock with tabular, you will have to use \StartDefiningTabulars before the start of the macro which uses \fboxBlock and the tabular, and \EndDefiningTabulars afterwards. Also see the lwarp documentation for the fancybox package.

**To frame equations:** See section 123 for the fancybox package.

**For fancy framed minipages:** See packages boxedminipage, shadow, fancybox, framed, mdframed.

**Custom environments:** Use a custom environment to create a sidebar, containing a BlockClass environment with custom css formatting, and \warpprintonly{\hrule} command:

---

```
\begin{BlockClass}{frameminipage}% ignored in print output
    % use CSS to format div class ``framedminipage''
    \warpprintonly{\hrule} % only appears in print output
    Contents
    \warpprintonly{\hrule} % only appears in print output
\end{BlockClass}
```

---

### 7.2.5 fancybox package

**framed equation example** fancybox's documentation has an example FramedEqn environment which combines math, \Sbox, a minipage, and an \fbox. This combination requires that the entire environment be enclosed inside a lateximage, which is done by adding \lateximage at the very start of FramedEqn's beginning code, and \endlateximage at the very end of the ending code. Unfortunately, the HTML alt attribute is not used here.

```
\newenvironment{FramedEqn}
{
    \lateximage% NEW
    \setlength{\fboxsep}{15pt}
    ...}{...
    \[\fbox{\TheSbox}\]
    \endlateximage% NEW
}
```

**framing alternatives** \fbox works with fancybox. Also see lwarp's \fboxBlock macro and fminipage environment for alternatives to \fbox for framing environments.

**framed table example** The fancybox documentation's example framed table using an \fbox containing a

`tabular` does not work with `lwarf`, but the `FramedTable` environment does work if `\fbox` is replaced by `\fboxBlock`. This method loses `HTML` formatting. A better method is to enclose the table's contents inside a `fminipage` environment. The caption may be placed either inside or outside the `fminipage`:

```
\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
...
\end{tabular}
\end{fminipage}
\end{table}
```

**framed verbatim** `lwarf` does not support the `verbatim` environment inside a span, box, or `fancybox`'s `\Sbox`, but a `verbatim` may be placed inside a `fminipage`. The `fancybox` documentation's example `FramedVerb` may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
\VerbatimEnvironment
\fminipage{#1}
\begin{Verbatim}
\end{Verbatim}
\endfminipage
}
```

**framed \VerbBox** `fancybox`'s `\VerbBox` may be used inside `\fbox`.

**indented alignment** `LVerbatim`, `\LVerbatimInput`, and `\LUseVerbatim` indent with horizontal space which may not line up exactly with what `pdftotext` detects. Some lines may be off slightly in their left edge.

### 7.2.6 mdframed package

**support** Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for `mdframed` environments and frame titles.

 **loading** When used, `lwarf` loads `mdframed` in `HTML` with `framemethod=none`.

**font** For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where `\textbf` must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the `mdframed` source). Since `lwarf` does not support `\bfseries` and friends, only one font selection may be made at a time.

**theoremtitlefont** `theoremtitlefont` is not supported, since the following text is not in braces in the `mdframed` source.

**footnotes** Footnotes are currently placed at the bottom of the HTML page.

**ignored options** `userdefinedwidth` and `align` are currently ignored.

## 7.3 Cross-references

 **empty link** `\nameref` refers to the most recently-used section where the `\label` was defined. If no section has been defined before the `\label`, the link will be empty. Index entries also use `\nameref` and have the same limitation.

### 7.3.1 Page references

 **TeX page numbers** The printed page does not translate to the HTML page, so `\pageref` references are converted to parentheses containing `\pagerefPageFor`, which defaults to “see”, followed by a hyperlink to the appropriate object.

Ex:

```
\ref{sec:name} on page \pageref{sec:name}
in HTML becomes:
“Sec. 1.23 on page (see sec. 1.23)”.
```

`\pagerefPageFor` may be redefined to “page for”, empty, etc. See page 317.

### 7.3.2 cleveref and varioref packages

 **cleveref page numbers** `cleveref` and `varioref` are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to “for”.

Ex:

```
\cpageref{tab:first,tab:second}
in HTML becomes:
"pages for table 4.1 and for table 4.2"
```

See `\cpagerefFor` at page 367 to redefine the message which is printed for page number references.

### 7.3.3 Hyperlinks, `hyperref`, and `url`

lwarf emulates `hyperref`, including the creation of active hyperlinks, but does not require that `hyperref` be loaded by the document.

lwarf can also load `url`, but `url` should not be used at the same time as `hyperref`, since they both define the `\url` command. lwarf does not (yet) attempt to convert `url` links into hyperlinks during `HTML` output, nor does `url` create hyperlinks during print output.

### 7.3.4 Footnotes and page notes

lwarf uses native `LATEX` footnote code, although with its own `\box` to avoid the `LATEX` output routine. The usual functions work as-is.

 **pfnote numbers** While emulating `pfnote`, lwarf is not able to reset `HTML` footnote numbers per page number to match the printed version, as `HTML` has no concept of page numbers. lwarf therefore uses continuous footnote numbering even for `pfnote`.

## 7.4 Front and back matter

### 7.4.1 Starred chapters and sections

The following describes `\ForceHTMLPage` and `\ForceHTMLTOC`, which may be used for endnotes, glossaries, `tocbibind`, and the index. See the following sections where applicable. Continue here if interested in the reason for adding these commands to lwarf.

Some packages use `\chapter*` or `\section*` to introduce reference material such as notes or lists, often to be placed in the back matter of a book. These starred sections are placed inline instead of on their own `HTML` pages, and they are not given TOC entries.

lwarf provides a method to cause a starred section to be on its own HTML page, subject to `FileDepth`, and also a method to cause the starred section to have its own TOC entry during HTML output.

`\ForceHTMLPage` To place a starred section on its own HTML page, use `\ForceHTMLPage` just before the `\chapter*` or `\section*`. lwarf will create a new page for the starred sectional unit.

A starred sectional unit does not have a TOC entry unless one is placed manually. The typical method using `\phantomsection` and `\addcontentsline` works for inline text but fails when the new starred section is given its own webpage after the TOC entry is created. If the starred section has its own HTML page but no correct TOC entry pointing to that page, the page will be inaccessible unless some other link is created.

`\ForceHTMLTOC` To automatically force the HTML version of the document to have a TOC entry for a starred section, use `\ForceHTMLTOC` just before the `\chapter*` or `\section*`. The TOC will only be assigned for HTML output, not for print output, and it will appear in the main TOC and also the sidetoc per page.

For print output, `\ForceHTMLTOC` and `\ForceHTMLPage` have no effect.

#### 7.4.2 abstract package

`\missing TOC` If using the `number` option with file splits, be sure to place the table of contents before the abstract. The `number` option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

#### 7.4.3 titling and authblk

`package support` lwarf supports the native L<sup>A</sup>T<sub>E</sub>X titling commands, and also supports the packages `authblk` and `titling`. If both are used, `authblk` should be loaded before `titling`.

`\published` and `\subtitle` If using the `titling` package, additional titlepage fields for `\published` and `\subtitle` may be added by using `\AddSubtitlePublished` in the preamble. See section 52.7.

#### 7.4.4 tocloft package

`\Opt{tocloft}{titles}` If using `tocloft` with `tocbibind`, `anonchap`, `fncychap`, or other packages which change chapter title formatting, load `tocloft` with its `titles` option, which tells `tocloft` to use standard L<sup>A</sup>T<sub>E</sub>X commands to create the titles, allowing other packages to work with it.

`\tocloft & other packages`

#### 7.4.5 **appendix** package

-  **incorrect toc link** During HTML conversion, the option `toc` without the option `page` results in a toc link to whichever section was before the `appendices` environment. It is recommended to use both `toc` and also `page` at the same time.

#### 7.4.6 **pagenote** package

`pagenote` works as-is, but the `page` option is disabled.

#### 7.4.7 **endnotes** package

- table of contents** To place the endnotes in the TOC, use:

```
\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*\notesname{Endnotes} % optional
```

- HTML page** To additionally have the endnotes on their own HTML page, if `FileDepth` allows:

```
\ForceHTMLPage
\theendnotes
```

#### 7.4.8 **glossaries** package

- Pkg** `glossaries` `xindy` is required for `glossaries`.

The default `style=item` option for `glossaries` conflicts with `lwarf`, so the style is forced to `index` instead.

The page number list in the printed form would become `\nameref`s in HTML, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

- placement and toc options** The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

##### **Numbered section, on its own HTML page:**

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
...
\printglossaries
```

##### **Unnumbered section, inline with the current HTML page:**

---

```
\usepackage[xindy,toc]{glossaries}
...
\printglossaries
```

**Unnumbered section, on its own HTML page:**

```
\usepackage[xindy,toc]{glossaries}
...
\ForceHTMLPage
\printglossaries
```

**Opt IndexLanguage** The `lwarp` package takes an option `IndexLanguage=english` to set the language used by `xindy`. This is passed to `xindy` using its `-L` option, and is used for both index and glossary generation.

**Opt `lwarpmk printglossary`** `lwarpmk` has the commands `lwarpmk printglossary` and `lwarpmk htmlglossary` to process the glossaries created by `glossaries` using `xindy`.

**7.4.9 Index and the `tocbibind` package**

**Opt IndexLanguage** The `lwarp` package takes an option `IndexLanguage=english` to set the language used by `xindy`. This is passed to `xindy` using its `-L` option, and is used for both index and glossary generation.

**⚠ tocloft & other packages** If using `tocloft` with `tocbibind`, `anonchap`, `fncychap`, or other packages which change chapter title formatting, load `tocloft` with its `titles` option, which tells `tocloft` to use standard `LATEX` commands to create the titles, allowing other packages to work with it.

**placement and TOC options** An index may be placed inline with other HTML text, or on its own HTML page:

**Inline, with a manual TOC entry:**

A commonly-used method to introduce an index in a `LATEX` document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname} or \chapter
\printindex
```

**On its own HTML page, with a manual TOC entry:**

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname} or \chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex
```

### Inline, with an automatic TOC entry:

```
Pkg  tocbibind      The tocbibind package may be used to automatically place an entry in the toc.
          \usepackage[nottoc]{tocbibind}
          ...
          \cleardoublepage
          \phantomsection % to fix print-version index link
          \printindex
```

### On its own HTML page, with an automatic TOC entry:

```
\usepackage[nottoc]{tocbibind}
...
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex
```

**Opt tocbibind numindex** Use the tocbibind numindex option to generate a numbered index. Without this option, the index heading has no number.

See section 62 for lwarf's core index and glossary code, and section 229 for tocbibind.

## 7.5 Math

- ⚠ **Equation numbering** ntheorem has a bug with equation numbering in  $\mathcal{AM}$ S environments when the option thref is used. lwarf does not share this bug, so equations with \split, etc, are numbered correctly with lwarf's HTML output, but not with the print output. It is recommended to use cleveref instead of ntheorem's thref option.
- Math rendering** Math may be rendered as SVG graphics or using the MATHJAX JavaScript display engine.
- SVG math option** For SVG math, math is rendered as usual by  $\text{\LaTeX}$  into the initial PDF file using the current font<sup>11</sup>, then is captured from the PDF and converted to SVG graphics via a number of utility programs. The SVG format is a scalable-vector web format, so math may be typeset by  $\text{\LaTeX}$  with its fine control and precision, then displayed or printed at any size, depending on (sometimes broken) browser support. An HTML alt attribute carries the  $\text{\LaTeX}$  code which generated the math, allowing copy/paste of the  $\text{\LaTeX}$  math expression into other documents.
- SVG image font size** The size of the math and text used in the SVG image may be adjusted by setting \LateximageFontSizeName to a font size name — *without the backslash*, for ex:  
 $\renewcommand{\LateximageFontSizeName}{\large}$
- SVG files** As currently implemented, each instance of math creates a new SVG file. In text

---

<sup>11</sup>See section 240 regarding fonts and fractions.

with many references to math variables, this can result in a large number of files with duplicate content. In the future, some method of content-based naming and checksumming may be used to remove the need for duplicate files.

**SVG inline** Another approach would be to in-line the SVG files directly into the HTML. This avoids having a large number of files and potentially speeds loading the images, but dis-allows the possibility of sharing one file among many instances without user intervention.

**PNG files** Others have used PNG files, sometimes pre-scaled for print resolution but displayed on-screen at a scaled down size. This allows high-quality print output at the expense of larger files, but SVG files are also larger as well.

**MathML** Conversion to MathML might be a better approach, among other things allowing a more compact representation of math than SVG drawings. Problems with MathML include limited browser support and some issues with the fine control of the appearance of the result. Also see section 8 regarding EPUB output with MathJax.

**MathJax math option** The popular MathJax alternative ([mathjax.org](http://mathjax.org)) may be used to display math.

Prog MathJax

When MathJax is enabled, math is rendered twice:

1. As regular L<sup>A</sup>T<sub>E</sub>X PDF output placed inside an HTML comment, allowing equation numbering and cross referencing to be almost entirely under the control of L<sup>A</sup>T<sub>E</sub>X, and
2. As detokenized printed L<sup>A</sup>T<sub>E</sub>X commands placed directly into the HTML output for interpretation by the MathJax display scripts. An additional script is used to pre-set the equation number format and value according to the current L<sup>A</sup>T<sub>E</sub>X values, and the MathJax cross-referencing system is ignored in favor of the L<sup>A</sup>T<sub>E</sub>X internal system, seamlessly integrating with the rest of the L<sup>A</sup>T<sub>E</sub>X code.

**MathJax limitations** Limitations when using MathJax include:

Prog MathJax

**chapter numbers**

- In document classes which have chapters, \tagged equations have the chapter number prepended in HTML output, unlike L<sup>A</sup>T<sub>E</sub>X. \tag\*{equations} (correctly) do not. This may be improved with future versions of the MathJax support script.

<https://groups.google.com/forum/#!topic/mathjax-users/jUtewUcE2bY>

**subequations**

- MathJax itself does not support subequations. This may be improved by parsing the L<sup>A</sup>T<sub>E</sub>X math expression to manually insert tags, but this has not yet been done.

**footnotes in math**

- Footnotes inside equations are not yet supported while using MathJax.

- lateximage** • Math appearing inside a `lateximage`, and therefore also inside a `Tikz` or `picture` environment, is rendered as SVG math even if MathJax is used in the rest of the document.
- siunitx** • Usage of `siunitx` inside a math equation is supported via a third-party MathJax extension. While inside a math expression, do not use `\SI` or `\si` inside `\text`, where it will be rendered as normal text.  
[https://github.com/mathjax/MathJax-third-party-extensions/  
tree/master/siunitx](https://github.com/mathjax/MathJax-third-party-extensions/tree/master/siunitx)
- TeX macros** • MathJax does not automatically support custom `\TeX` macros, but they may be set up by the user.

**custom MathJax macros** For an example of using custom `\TeX` macros with MathJax, see page [337](#).

### 7.5.1 ntheorem package

- Font control** This conversion is not total. Font control is via `css`, and the custom `\TeX` font settings are ignored.
- Equation numbering** `ntheorem` has a bug with equation numbering in `\AMS` environments when the option `thref` is used. `lwarf` does not share this bug, so equations with `\split`, etc, are numbered correctly with `lwarf`'s `HTML` output, but not with the `print` output. It is recommended to use `cleveref` instead of `ntheorem`'s `thref` option.

### 7.5.2 siunitx package

- Pkg siunitx** Do not use `per-mode=fraction`, which cannot be seen by the final `pdftotext` conversion.
- per-mode** Some units will require that the expression be placed inside math mode.

### 7.5.3 units and nicefrac packages

- Pkg units** `units` and `nicefrac` work as-is with `lwarf`, but MathJax does not have an extension for `units` or `nicefrac`. These packages do work with `lwarf`'s option `svgmath`.
- Pkg nicefrac**

### 7.5.4 newtxmath package

- Pkg newtxmath** The proper load order is:
- loading sequence**

1. ...
2. \usepackage{lwarf}
3. ...
4. \usepackage{amsthm}
5. \usepackage{newtxmath}
6. ...

## 7.6 Graphics

- ⚠ **.pdf image files** For \includegraphics with .pdf files, the user should provide a .pdf image file, and also a .svg, .png, or .jpg version of the same image. **These should be referred to without a file extension:**

```
\includegraphics{filename} % print:.pdf, HTML:.svg or other
```

For print output, lwarf will automatically choose the .pdf if available, other some other format otherwise. For HTML, one of the other formats is used instead.

If a .pdf file is explicitly referred to with its file extension, a link to the .pdf file will appear in the HTML output.

```
\includegraphics{filename.pdf} % creates a link in HTML
```

- other image files** For .png, .jpg, or .gif image files, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

- ⚠ **graphics vs. graphicx** If using the older graphics syntax, use both optional arguments for \includegraphics. A single optional parameter is interpreted as the newer graphicx syntax. Note that viewports are not supported by warp; the entire image will be shown.

- units** For \includegraphics, avoid px and % units for width and height, or enclose them inside warpHTML environments. For font-proportional image sizes, use ex or em. For fixed-sized images, use cm, mm, in, pt, or pc. Use the keys width=.5\linewidth, or similar for \textwidth or \textheight to give fixed-sized images proportional to a 6 by 9 inch text area.

- options** \includegraphics accepts width and height, origin, rotate and scale, plus a new class key.

- HTML class** With HTML output, \includegraphics accepts an optional class=xyz keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

`\rotatebox` `\rotatebox` accepts the optional `origin` key.

- ⚠ **browser support** `\rotatebox`, `\scalebox`, and `\reflectbox` depend on modern browser support. The CSS standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike L<sup>A</sup>T<sub>E</sub>X, so expect some ugly results for scaling and rotating.

### 7.6.1 grffile package

- ⚠ **matching PDF and SVG** `grffile` is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

### 7.6.2 color package

`color` is superceded by `xcolor`, and `lwarp` requires several of the features of `xcolor`.

- ⚠ **missing colors** It should be sufficient for the user's document to load `color` then load `xcolor` as well.

### 7.6.3 xcolor package

`\colorboxBlock` and `\fcolorboxBlock` `\colorboxBlock` and `\fcolorboxBlock` are provided for increased HTML compatibility, and they are identical to `\colorbox` and `\fcolorbox` in print mode. In HTML mode they place their contents into a `<div>` instead of a `<span>`. These `<div>`s are set to `display: inline-block` so adjacent `\colorboxBlocks` appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for `\colorboxBlock` and `\fcolorboxBlock` are created by `lwarp`'s core if `xcolor` is loaded.

`background: none` `\fcolorbox` and `\fcolorboxBlock` allow a background color of `none`, in which case only the frame is drawn, which can be useful for HTML.

`color support` Color definitions, models, and mixing are fully supported without any changes required.

`tables` Colored tables are ignored so far. Use CSS to style tables.

`colored text and boxes` `\textcolor`, `\colorbox`, and `\fcolorbox` are supported.

`\color` and `\pagecolor` `\color` and `\pagecolor` are ignored. Use CSS or `\textcolor` where possible.

## 7.7 Tabular

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, \* column specifiers, siunitx S columns, or the packages multirow, longtable, supertabular, or xtab.

### Defining environments:

⚠️ misplaced alignment  
alignment tab character &

- When defining environments or macros which include `tabular` and instances of the `&` character, it may be necessary to make `&` active before the environment or macro is defined, then restore `&` to its default catcode after, using the following commands. These are ignored in print mode.

```
\StartDefiningTabulars
```

```
<define macros or environments using tabular and &  
here>
```

```
\EndDefiningTabulars
```

⚠️ tabular inside another  
environment

- When creating a new environment which contains a `tabular` environment, lwarp's emulation of the `tabular` does not automatically resume when the containing environment ends, resulting in corrupted HTML rows. To fix this, use `\ResumeTabular` as follows. This is ignored in print mode.

```
\StartDefiningTabulars % because & is used in a
```

```
definition
```

```
\newenvironment{outerenvironment}
```

```
{
```

```
\tabular{cc}
```

```
left & right \\
```

```
}
```

```
{
```

```
\TabularMacro\ResumeTabular
```

```
left & right \\
```

```
\endtabular
```

```
}
```

```
\EndDefiningTabulars
```

### Cell contents:

⚠️ paragraphs

- Multiple paragraphs in one cell of a `p`, `b`, `m` column must have `\newline` between paragraphs.

⚠️ `\multirow`

- For `multirow`, insert `\mrowcell` into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output.

```
... & \multirow{2}{.5in}{text} & ...
```

```
... & \mrowcell & ...
```

**vposn**

Note that recent versions of multirow include a new optional vposn argument.

- The multirow documentation regarding colored cells recommends using a negative number of rows. This will not work with l warp, so \warpprintonly and \warpHTMLonly must be used to make versions for print and HTML.
- See section 174.2 for \multicolumnrow.

 \multicolumn & \multirow

l warp does not support directly combining \multicolumn and \multirow. Use \multicolumnrow instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}{c}{3}{0}{1in}{Text}
```

The two arguments for \multicolumn come first, followed by the five arguments for \multirow, many of which are optional, followed by the contents.

 skipped cells

As per \multirow, skipped cells to the right of the \multicolumnrow statement are not included in the source code on the same line. On the following lines, \mcolrowcell must be used for each cell of each column and each row to be skipped:

```
... & \multicolumnrow{2}{c}{c}{3}{0}{1in}{Text} & ...
... & \mcolrowcell & \mcolrowcell & ...
... & \mcolrowcell & \mcolrowcell & ...
```

**vposn**

Note that recent versions of multirow include a new optional vposn argument.

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use \TabularMacro just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \\
```

**Column specifiers:**

 \* column specification

- \* in a column specification is not used (so far). Repeat the column type the correct number of times.

 @ and !

- Only one each of @ and ! is used at each column, and they are used in that order.

 \multirow

- In \multirow cells, the print version may have extra instances of <, >, @, and ! cells on the second and later rows in the \multirow which do not appear in the HTML version.

- \newcolumntype is ignored; unknown column types are set to 1.

**Rules:****vertical rules**

- Vertical rules next to either side of an @ or ! column are displayed on both sides of the column.

**width and trim**

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with @ or ! columns, and full-width rules ignore trim.

**full-width rules**

- \toprule, \midrule, \bottomrule, and \hline ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

**combined rules**

- If you wish to use \cmidrule followed by \bottomrule, it may be necessary to use:

```
\cmidrule{2-3} \\[-2ex]
\bottomrule
```

The optional -2ex is ignored in HTML but improves the visual formatting in the print output.

- For \toprule and \bottomrule, when combined with a warpprint or warpHTML environment, if a “misplaced \noalign” error occurs, change

This & That \endhead

to

**\warpprintonly{This & That \endhead}**

and likewise with the other \end headings. Keep the \endfirsthead row unchanged, as it is still relevant to HTML output.

**Other:**

- tabularx ignores the width, but X columns do produce paragraph columns or multicolumns.

**longtable headings**

- For longtable, place headings and footings which do not apply to HTML inside \warpprintonly{}.

**⚠ S columns**

- For S columns (from the siunitx package), while producing print output, anything non-numeric must be placed inside {} braces, including commands such as \multirow. While producing HTML output, though, anything placed inside braces is not seen by lwarp’s tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

```
\warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
\warpHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
```

**7.7.1 longtable package**

Longtable \endhead, \endfoot, and \endlastfoot rows are not used for HTML, and these rows should be disabled. Use

```
\warpprintonly{row contents}
```

instead of

```
\begin{warpprint} ... \end{warpprint}
```

Doing so helps avoid “Misplaced \noalign.” when using `\begin{warpprint}`.

Keep the `\endfirsthead` row, which is still relevant to HTML output.

 `\kill` is ignored, place a `\kill` line inside

```
\begin{warpprint} ... \end{warpprint}
```

or place it inside `\warpingprintonly`.

### 7.7.2 supertabular and xtab packages

 misplaced alignment  
alignment tab character &

For `\tablefirsthead`, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
...
\EndDefiningTabulars
```

See section 7.7.

### 7.7.3 bigdelim package

 use `\mrowcell` `\ldelim` and `\rdelim` use `\multirow`, so `\mrowcell` must be used in the proper number of empty cells in the same column below `\ldelim` or `\rdelim`, but not in cells which are above or below the delimiter:

---

```
\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\{}{2}{.25in}[left ] & c & d \\
\mrowcell & e & f \\
<empty> & g & h \\
\end{tabular}
```

---

a	b
c	d
e	f
g	h

## 7.8 Floats

### 7.8.1 float, trivfloat, and/or algorithmicx together

⚠️ package conflicts If using `\newfloat`, `trivfloat`, and/or `algorithmicx` together, see section 232.1.

### 7.8.2 caption and subcaption packages

To ensure proper float numbering, set caption positions such as:

```
\captionsetup[table]{position=top}
\captionsetup[figure]{position=bottom}
```

Similarly for `subtable`, `subfigure`, and `longtable`.

### 7.8.3 subfig package

⚠️ lof/lotdepth At present, the package options for `lofdepth` and `lotdepth` are not working. These counters must be set separately after the package has been loaded.

horizontal spacing In the document source, use `\hfill` and `\hspace*` between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

### 7.8.4 floatrow package

⚠️ subfig package When combined with the `subfig` package, while inside a `subfloatrow` `\ffigbox` and `\ttabbox` must have the caption in the first of the two of the mandatory arguments.

⚠️ \FBwidth, \FBheight The emulation of `floatrow` does not support `\FBwidth` or `\FBheight`. These values are pre-set to `.3\linewidth` and `2in`. Possible solutions include:

- Use fixed lengths. `lwarp` will scale the `HTML` lengths appropriately.
- Use `warpprint` and `warpHTML` environments to select appropriate values for each case.
- Inside a `warpHTML` environment, manually change `\FBwidth` or `\FBheight` before the `\ffigbox` or `\ttabbox`. Use `\FBwidth` or `\FBheight` normally afterwards; it will be used as expected in print output, and will use your custom-selected value in `HTML` output. This custom value will be used repeatedly, until it is manually changed to a new value.

## 7.9 Miscellaneous

### 7.9.1 verse and memoir

- \attrib The documentation for the `verse` and `memoir` packages suggest defining an `\attrib` command, which may already exist in current documents, but it will only work for print output. `lwarp` provides `\attribution`, which works for both print and HTML output. To combine the two so that `\attrib` is used for print and `\attribution` is used for HTML:

---

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

---

- Len \leftskip Len \leftmargini Len \TMLleftskip Len \TMLleftmargini These lengths are used by `verse` and `memoir` to control the left margin, and they may already be set by the user for print output. New lengths `\HTMLvleftskip` and `\HTMLleftmargini` are provided to control the margins in HTML output. These new lengths may be set by the user before any `verse` environment, and persist until they are manually changed again. One reason to change `\HTMLleftmargini` is if there is a wide `\flagverse` in use, such as the word “Chorus”, in which case the value of `\HTMLleftmargini` should be set to a wide enough length to contain “Chorus”. The default is wide enough for a stanza number.

Horizontal spacing relies on `pdftotext`'s ability to discern the layout (-layout option) of the text in the HTML-tagged PDF output. For some settings of `\HTMLleftmargini` or `\HTMLleftskip` the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

### 7.9.2 newclude package

- Pkg `newclude` `newclude` modifies `\label` in a non-adaptive way, so `newclude` must be loaded before `lwarp` is loaded.



*Ex:*

---

```
\documentclass{article}
...<font setup>
\usepackage{newclude}
\usepackage[warpHTML]{lwarp}
...
...
```

---

### 7.9.3 babel package

Pkg babel

\CaptionSeparator When French is used, the caption separator is changed to a dash. The following may be used to restore it to a colon:

```
\renewcommand*\CaptionSeparator}{:~}
```

punctuation spaces Also when French is used, lwarp creates fixed-width space around punctuation by patching \FBcolonspace, \FBthinspace, \FBguillspace, \FBmedkern, \FBthickkern, \FBtextellipsis, and the tilde. If the user's document also changes these parameters, the user's changes should be placed inside a warpprint environment so that the user's changes do not affect the HTML output.

⚠ customized spacing

## 8 EPUB conversion

lwarf does not produce EPUB documents, but it may be told to modify its HTML output to greatly assist in the conversion. An external program may then be used to finish the conversion to EPUB.

**<meta> author** To assign the author's name for regular lwarf HTML files, and also for the EPUB, use \HTMLAuthor {\<name>}. This assigns the name to the <meta> author element. It may be set empty, and it defaults to \theauthor.

A special boolean is provided to simplify the process of converting lwarf HTML output to EPUB:

---

Bool FormatEPUB Default false. FormatEPUB changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.

---

To help convert lwarf HTML output to EPUB, add

```
\booltrue{FormatEPUB}
```

to the project's source preamble after \usepackage{lwarf}. The EPUB version of the document cannot co-exist with the regular HTML version, so

```
Enter ⇒ lwarfmk cleanall
```

then

```
Enter ⇒ lwarfmk html
```

to recompile with the FormatEPUB boolean turned on. Several changes are then made to the HTML output:

- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each file split.

**Calibre** The resulting files will be ready to be loaded into an EPUB conversion program, such as the open-source program Calibre (<https://calibre-ebook.com/>).

 **search order** The EPUB conversion program must know what order the files are included. For lwarf projects, set the EPUB conversion software to do a breadth-first search of the files. For Calibre, this option is found in

Preferences → Plugins → File type plugins → HTML to Zip

Check the box Add linked files in breadth first order.

### ⚠ section breaks

The EPUB-conversion program must also know where the section breaks are located. For a list of lwarp's section headings, see table 5. For example, an article class document would break at \section, which is mapped to HTML heading level <h4>, whereas a book class document would break at \chapter, which is HTML heading level <h3>. For Calibre, this option is found in

Preferences → Conversion (Common Options) → Structure Detection → Detect chapters at (XPath expression)

Select the “magic wand” to the right of this entry box, and set the first entry

Match HTML tags with tag name:

to <h4>. (Or <h3> for document classes with \chapters.) The Detect chapters at field should then show

//h:h4 — or — //h:h3

This option is also available on the main tool bar at the Convert books button.

Once these settings have been made, the lwarp-generated HTML files may be loaded by Calibre, and then converted to an EPUB.

---

### *MathJax support*

MathJax may be used in EPUB documents. Some e-readers include MathJax, but any given reader may or may not have a recent version, and may or may not include extensions such as support for siunitx.

lwarp adds some modifications to MathML to support equations numbered by chapter. These modifications may not be compatible with the e-reader's version of MathJax, so lwarp requests that a known version be loaded instead. In some cases chapter numbering of equations still doesn't work.

Until math support in EPUB documents is improved, it is recommended to use SVG images instead of MathJax, especially for equations numbered by chapter, or where siunitx support is important.

---

## 9 Word-processor conversion

lwarf may be told to modify its HTML output to make it easier to import the HTML document into a word processor. At the time of this writing, it seems that LibreOffice works best at preserving table layout, but it still has some limitations, such as an inability to automatically assign figure and table frames and captions according to user-selected HTML classes. lwarf provides some assistance in locating these frame boundaries, as shown below.

A special boolean is provided to simplify the process of converting lwarf HTML output to EPUB:

Bool FormatWordProcessor

---

Default false. Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments.

---

To help modify lwarf HTML output for easier import to a word processor, add

\booltrue{FormatWordProcessor}

to the project's source preamble after lwarf is loaded. Several changes are then made to the HTML output:

- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each file split. These will have to be manually moved to their proper place in the document. lwarf does not know where the page breaks will be in the word processor's document, so the footnotes are simply moved to the end of each sectional break.
- Forces single-file output.
- Turns off HTML debugging comments. These are comments appearing inside the HTML code, marking the opening/closing of sections and <div>s, but they are no longer useful when the document has been imported into a word processor.

An additional boolean may be set to help mark float boundaries:

---

Default true. Adds

```
    === table begin
    ...
    === end
Bool  HTMLMarkFloats  or
    === figure begin
    ...
    === end
```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames.

---

When enabled, markers are placed around each float, helping the user to identify float boundaries for further conversion to word processor frames and captions.

## 10 Modifying l warp

Purely text-based packages probably will work as-is when generating HTML.

Look to existing code for ideas on how to expand into new code.

An environment may be converted to a `\latextimage` then displayed with an image of the resulting `\TeX` output. See section 70 for an example of the `picture` environment.

To create a custom HTML block or inline css class, see section 39.8.

### 10.1 Creating an l warp version of a package

When creating HTML, l warp redefines the `\usepackage` and `\RequirePackage` macros such that it first looks to see if a `l warp-<packagename>.sty` version exists. If so, the l warp version is used instead. This modular system allows users to create their own versions of packages for l warp to use for HTML, simply by creating a new package with a `l warp-` prefix. If placed in the local directory along with the source code, it will be seen by that project alone. If placed alongside the other `l warp-` packages where `\TeX` can see it, then the user's new package will be seen by any documents using l warp. (Remember `mktexlsr` or `texhash`.)

An `l warp-<packagename>.sty` package is only used during HTML generation. Its purpose is to pretend to be the original package, while modify anything necessary to create a successful HTML conversion. For many packages it is sufficient to simply provide nullified macros, lengths, counters, etc. for anything which the original package does, while passing the raw text on to be typeset. See the pre-existing `l warp-` packages for examples.

Anything the user might expect of the original package must be replaced or emulated by the new `l warp-` package, including package options, user-adjustable counters, lengths, and booleans, and conditional behaviors. In many of these packages, most of the new definitions have a “local” prefix according to the package name, and @ characters inside the name, which hides these names from the user. In most cases these macros will not need to be emulated for HTML output. Only the “user-facing” macros need to be nullified or emulated.

Each `l warp-` package should first call either

```
\LWR@ProvidesPackageDrop
```

or

```
\LWR@ProvidesPackagePass
```

If Dropped, the original print-version package is ignored, and only the lwarp- version is used. Use this where the original print version is useless for HTML. If Passed, the original package is loaded first, with the user-supplied options, then the lwarp-version continues loading as well. See section 183 (ntheorem) for an example of selectively disabling user options for a package. Use this when HTML output only requires some modifications of the original package. For a case where the original package is usable without changes, there is no need to create a lwarp- version.

## 10.2 Adding a package to the `lwarp.dtx` file

When adding a package to `lwarp.dtx` for permanent including in `lwarp`, provide the `lwarp-<packagename>` code in `lwarp.dtx`, add its entry into `lwarp.ins`, and also remember to add

```
\LWR@loadafter{<packagename>}
```

to `lwarp.dtx` in section 20. This causes `lwarp` to stop with an error if `packagename` is loaded before `lwarp`.

## 10.3 Testing `lwarp`

When changes have been made, test the print output before testing the HTML. The print output compiles faster, and any errors in the printed version will be easier to figure out than the HTML version.

Remember that the configuration files are only rewritten when compiling the printed version of the document.

Sometimes it is worth checking the `<project>_html.pdf` file, which is the PDF containing HTML tags. Also, `<project>_html.html` has the text conversion of these tags, before the file is split into individual HTML files.

It is also worth checking the browser's tools for verifying the correctness of HTML and css code.

## 10.4 Modifying `lwarpmk`

Prog `lwarpmk` In most installations, `lwarpmk.lua` is an executable file located somewhere the operating system knows about, and it is called by typing “`lwarpmk`” into a terminal.  
File `lwarpmk.lua`

A project-local copy of `lwarpmk.lua` may be generated, modified, and then used to compile documents:

1. Add the `lwarpmk` option to the `lwarp` package.
2. Recompile the printed version of the document. The `lwarpmk` option causes `lwarp` to create a local copy of `lwarpmk.lua`.
3. The `lwarpmk` option may now be removed from the `lwarp` package.
4. Copy and rename `lwarpmk.lua` to a new file such as `mymake.lua`.
5. Modify `mymake.lua` as desired.
6. If necessary, make `mymake.lua` executable.
7. Use `mymake.lua` instead of `lwarpmk.lua`.

To adjust the command-line arguments for compiling the document, look in `mymake.lua` for “`latexname`”.

To adjust the command-line arguments for processing the index, look for “`xindy`”.

## 11 Troubleshooting

### 11.1 Using the lwarf.sty package

Also see:

Section 6.5: Commands to be placed into the warpprint environment

Section 7: Special cases and limitations

Section 7: Special cases and limitations

**Text is not converting:**

- Font-related UTF-8 information must be embedded in the PDF file. See section 6.1 regarding vector fonts.

**Undefined HTML settings:**

- See the warning regarding the placement of the HTML settings at section 5.7.

**Tabular problems:** See section 7.7.

**Obscure error messages:**

- Be sure that a print version of the document compiles and that your document's L<sup>A</sup>T<sub>E</sub>X code is correct, before attempting to generate an HTML version.

**Missing sections:**

- See section 5.7 regarding the FileDepth and SideTOCDepth counters, and the use of \tableofcontents in the home page.

**Missing HTML files:**

See the warning regarding changes to the HTML settings at section 5.7.

**Missing / incorrect cross-references:**

- Use lwarpmk again followed by lwarpmk html or lwarpmk print to compile the document one more time.
- \nameref refers to the most recently-used section where the \label was defined. If no section has been defined before the \label, the link will be empty. Index entries also use \nameref and have the same limitation.
- cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for \cpageref and \cpagerefrange. This phrase includes \cpagerefFor, which defaults to "for".

 empty link

 cleveref page numbers

Ex:  
`\cpageref{tab:first,tab:second}`  
 in HTML becomes:  
 “pages **for** table 4.1 and **for** table 4.2”  
 See `\cpagerefFor` at page 367 to redefine the message which is printed  
 for page number references.

#### Em-dashes or En-dashes in listing captions and titles:

Use X<sub>E</sub>T<sub>E</sub>X or Lua<sub>E</sub>T<sub>E</sub>X.

#### FLOATS OUT OF SEQUENCE:

**Mixed “Here” and floating:** Floats [H]ere and regular floats may become out of order. `\clearpage` if necessary.

**Caption setup:** With `\captionsetup` set the positions for the captions above or below to match their use in the source code.

#### Print document contains HTML tags:

- Be sure that the document selects `\usepackage[warpprint]{lwarf}` instead of `[warpHTML]`.

#### HTML document contains a single unformatted print document:

- Be sure that the document selects `\usepackage[warpHTML]{lwarf}` instead of `[warpprint]`.

#### Images are appearing in strange places:

- `lwarfmk` `limages` to refresh the `lateximage` images.

 **Adding/removing SVG images:** When a math expression, `picture`, or `Tikz` environment is added or removed, the SVG images must be re-created with `lwarfmk` `limages` to maintain the proper image file sequence numbers.

 **HTML instead of images** If HTML appears where an SVG image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time.

 **Lots of files!** Expressing math as SVG images has the advantage of representing the math exactly as `ETEX` would, but has the disadvantage of requiring an individual file for each math expression. There is no attempt at reusing the same file each time the same expression occurs, so each time `$x$` is used, for example, yet another file is created. For a document with a large amount of math, see section 5.5 to use MathJax instead.

**“Leaders not followed by proper glue”:** This can be caused by a missing `l@<floattype>` or `l@<sectiontype>` definition. See lwarf’s definitions for examples.

#### Plain-looking document:

- The document's css stylesheet may not be available, or may be linked incorrectly. Verify any `\CSSFilename` statements point to a valid css file.

**Broken fragments of HTML:**

- Check the `PDF` file used to create `HTML` to see if the tags overflowed the margin. (This is why such large page size and margins are used.)

**Changes do not seem to be taking effect:**

- Be sure to `lwarpmk clean`, recompile, then start by reloading the home page. You may have been looking at an older version of the document. If you changed a section name, you may have been looking at the file for the old name.
- See the warning regarding changes to the `HTML` settings at section [5.7](#).
- Verify that the proper css is actually being used.
- The browser may compensate for some subtle changes, such as automatically generating ligatures, reflowing text, etc.

**Un-matched conditional compiles:**

- Verify the proper begin/end of `warpprint`, `warpHTML`, and `warpall` environments.

### 11.1.1 Debug tracing output

`\tracingl warp` When `\tracingl warp` is used, `l warp` will add extra tracing messages to the `.log` file. The last several messages may help track down errors.

Place `\tracingl warp` just after `\usepackage{l warp}` to activate tracing.

## 11.2 Compiling the `l warp.dtx` file

`l warp_tutorial.tex`: Copy or link `l warp_tutorial.txt` from the `TD S doc` directory to the source directory, or wherever you wish to compile the documentation. This file is included verbatim into the documentation, but is in the `doc` directory so that it may be found by `texdoc` and copied by the user.

**Illogical error messages caused by an out-of-sync `l warp.sty` file:**

1. Delete the `l warp.sty` file.
2. `pdflatex l warp.ins` to generate a new `l warp.sty` file.
3. `pdflatex l warp.dtx` to recompile the `l warp.pdf` documentation.

**Un-nested environments:**

Be sure to properly nest:

- `\begin{macrocode}` and `\end{macrocode}`
- `\begin{macro}` and `\end{macro}`
- `\begin{environment}` and `\end{environment}`

## 12 Implementation

This package is perhaps best described as a large collection of smaller individual technical challenges, in many cases solved through a number of erude-haeks clever tricks. Reference sources are given for many of the solutions, and a quick internet search will provide additional possibilities.

Judgement calls were made, and are often commented. Improvements are possible. The author is open to ideas and suggestions.

Packages were patched for re-use where they provided significant functionality. Examples include xcolor with its color models and conversion to HTML color output, and siunitx which provides many number and unit-formatting options, almost all of which are available in pure-text form, and thus easily used by pdftotext.

Packages were emulated where their primary purpose was visual formatting which is not relevant to HTML output. For example, packages related to sectioning are already patched by numerous other packages, creating a difficult number of combinations to try to support, and yet in HTML output all of the formatting is thrown away, so these packages are merely emulated.

Packages with graphical output are allowed as-is, but must be nested inside a `lateximage` environment to preserve the graphics.

Testing has primarily been done with the Iceweasel/Firefox browser.

## 13 Stack depths

Stacks are created to track depth inside the L<sup>A</sup>T<sub>E</sub>X document structure. This depth is translated to HTML headings as shown in table 5. “Depth” here is not depth in the traditional computer-science stack-usage sense, but rather a representation of the nesting depth inside the L<sup>A</sup>T<sub>E</sub>X document structure.

When starting a new section, the program first must close out any existing sections and lists of a deeper level to keep the HTML tags nested correctly.

Table 5: Section depths and HTML headings

Section	$\text{\LaTeX}$ depth	HTML headings
title of the entire website		<h1>
none	-5	new for this package
book	-2	<b>not yet used</b>
part	-1	<h2>
chapter	0	<h3>
section	1	<h4>
subsection	2	<h5>
subsubsection	3	<h6>
paragraph	4	<span class = "paragraph">
subparagraph	5	<span class = "subparagraph">
listitem	7	new for this package, used for list items

Support for the memoir package will require the addition of a book level, which may push the HTML headings down a step, and also cause subsubsection to become a <div> due to a limit of six HTML headings.

It is possible to use HTML <section> and <h1> for all levels, but this may not be well-recognized by older browsers.

Fixed levels for parts and chapters allow the css to remain fixed as well.

## 14 Source Code

This is where the documented source code for lwarf begins, continuing through the following sections all the way to the change log and index at the end of this document.

The following sections document the actual implementation of the lwarf package.

**line numbers** The small numbers at the left end of a line refer to line numbers in the `lwarf.sty` file.

**subjects** Blue-colored tags in the left margin aid in quickly identifying the subject of each paragraph.

**objects** Black-colored tags in the left margin are used to identify programming objects such as files, packages, environments, booleans, and counters. Items without a tag are

**index entries** command macros. Each of these also appears in the index as individual entries, and are also listed together under “files”, “packages”, “environments”, “booleans”, and “counters”.

 **warnings** Special warnings are marked with a warning icon.

**for HTML output:** Green-colored tags in the left margin show which sections of source code apply to the generation of HTML, print, or both forms of output.  
**for PRINT output:**  
**for HTML & PRINT:**

## 15 Detecting the $\text{\TeX}$ Engine — pdflatex, lualatex, xelatex

```

1 \RequirePackage{iftex}
2
3 \ifLuaTeX
4 \RequirePackage{lualatex85}% until the geometry package is updated
5 \fi

```

## 16 Unicode Input Characters

**for HTML & PRINT:** If using pdflatex, convert a minimal set of Unicode characters. Additional characters may be defined by the user, as needed.

A commonly-used multiply symbol is declared to be `\texttimes`.

The first arguments of `\newunicodechar` below are text ligatures in the source code, even though they are not printed in the following listing.

```

6
7 \RequirePackage{newunicodechar}
8
9 \newunicodechar{x}{\texttimes}
10
11 \ifPDFTeX
12 \newunicodechar{ff}{ff}% the first arguments are ligatures
13 \newunicodechar{fi}{fi}
14 \newunicodechar{fl}{fl}
15 \newunicodechar{ffi}{ffi}
16 \newunicodechar{ffl}{ffl}
17 \newunicodechar{--}{--}
18 \newunicodechar{-}{--}

```

In PDFT $\text{\TeX}$ , preserve upright quotes in verbatim text:

```

19 \RequirePackage{upquote}
20 \else
21 \fi

```

## 17 Early package requirements

Pkg `etoolbox` Provides `\ifbool` and other functions.

22 \RequirePackage{etoolbox}[2011/01/03]  
23 % requires v2.6 for \BeforeBeginEnvironment, etc.

Pkg `ifplatform` Provides `\ifwindows` to try to automatically detect Windows OS.

24 \RequirePackage{ifplatform}% sense op-system platform

Pkg `letltmacro` Used to redefine `\textbf` and friends.

25 \RequirePackage{letltmacro}

## 18 Operating-System portability

Prog Unix	lwarp tries to detect which operating system is being used. UNIX / MAC OS / LINUX is the default (collectively referred to as “UNIX” in the configuration files), and MS-WINDOWS is supported as well.
Prog Mac OS	
Prog Linux	
Prog MS-Windows	If WINDOWS is not correctly detected, use the lwarp option <code>OSWindows</code> .
Prog Windows	
Opt OSWindows	When detected or specified, the operating-system path separator used by lwarp is modified, the boolean <code>usingOSWindows</code> is set true. This boolean may be tested by the user for later use.

### 18.1 Common portability code

Bool `usingOSWindows` Set if the `OSWindows` option is used.

```
26 \newbool{usingOSWindows}
27 \boolfalse{usingOSWindows}
```

### 18.2 Unix, Linux, and Mac OS

\OSPathSymbol Symbol used to separate directories in a path.

```
28 \newcommand*{\OSPathSymbol}{/}
```

### 18.3 MS-Windows

For MS-Windows:

\LWR@setOSWindows Set defaults for the MS-Windows operating system. lwarp attempts to auto-detect the operating system, and the `OSWindows` option may also be used to force MS-Windows compatibility.

```
29 \newcommand*{\LWR@setOSWindows}
30 {
31 \booltrue{usingOSWindows}
32 \renewcommand*{\OSPathSymbol}{\@backslashchar}
33 }
```

Test for windows during compile. The user may also specify OSWindows package option in case this test fails.

```
34 \ifwindows
35 \LWR@setOSWindows
36 \fi
```

## 19 Package options

**Pkg kvoptions** Allows key/value package options.

```
37 \RequirePackage{kvoptions}
38 \SetupKeyvalOptions{family=LWR,prefix=LWR@}
```

**Bool warpingprint**

**Bool warpingHTML** Set to true/false depending on the package option selections for print/HTML/EPUB output and mathsvg/mathjax:

```
39 \newbool{warpingprint}
40 \newbool{warpingHTML}
41 \newbool{mathjax}
```

**defaults** The default is print output, and svg math if the user chose HTML output.

```
42 \booltrue{warpingprint}%
43 \boolfalse{warpingHTML}%
44 \boolfalse{mathjax}%
```

**Opt warpprint** If the warpprint option is given, boolean warpingprint is true and boolean warpingHTML is false, and may be used for \ifbool tests.

```
45 \DeclareVoidOption{warpprint}{%
46 \PackageInfo{lwarp}{Using option 'warpprint'}
47 \booltrue{warpingprint}%
48 \boolfalse{warpingHTML}%
49 }
```

**Env warpHTML** Anything in the warpHTML environment will be generated for HTML output only.

**Opt warpHTML** If the warpHTML option is given, boolean warpingHTML is true and boolean warpingprint is false, and may be used for \ifbool tests.

```
50 \DeclareVoidOption{warpHTML}{%
51 \PackageInfo{lwarp}{Using option 'warpHTML'}%
```

---

```

52 \booltrue{warpingHTML}%
53 \boolfalse{warpingprint}%
54 }

```

- Opt `mathsvg` Option `mathsvg` selects SVG math display: If the `mathsvg` option is given, boolean `mathjax` is false, and may be used for `\ifbool` tests.

```

55 \DeclareVoidOption{mathsvg}{%
56 \PackageInfo{l warp}{Using option 'mathsvg'}%
57 \boolfalse{mathjax}%
58 }

```

- Opt `mathjax` Option `mathjax` selects MathJax math display: If the `mathjax` option is given, boolean `mathjax` is true, may be used for `\ifbool` tests.

```

59 \DeclareVoidOption{mathjax}{%
60 \PackageInfo{l warp}{Using option 'mathjax'}%
61 \booltrue{mathjax}%
62 }

```

- Opt `BaseJobname` Option `BaseJobname` sets the `\BaseJobname` for this document.

This is the `\jobname` of the printed version, even if currently compiling the HTML version. I.e. this is the `\jobname` without `_html` appended. This is used to set `\HomeHTMLFilename` if the user did not provide one.

```
63 \DeclareStringOption[\jobname]{BaseJobname}
```

- Opt `IndexLanguage` Sets the language to be assigned in `lwarpmk`'s configuration files. This is then used by `lwarpmk` while processing the index and glossary.

```
64 \DeclareStringOption[english]{IndexLanguage}
```

- Opt `xdyFilename` Selects a custom `.xdy` file. The default is `l warp.xdy`. A customized file should be based on `l warp.xdy`, and must retain the line

```
(markup-locref :open "\hyperindexref{" :close "})
```

```
65 \DeclareStringOption[l warp.xdy]{xdyFilename}
```

- Opt `lwarpmk` Tells `l warp` to generate a local copy of `lwarpmk` called `lwarpmk.lua`. Useful for archiving for future use. This file may be made executable and acts just like `lwarpmk`.

If `lwarpmk` option, creates a local copy of `lwarpmk.lua`:

---

```

66 \newbool{LWR@creatinglwarpmk}
67 \boolfalse{LWR@creatinglwarpmk}
68
69 \DeclareVoidOption{lwarpmk}{
70 \PackageInfo{lwarp}{Using option 'lwarpmk'}
71 \booltrue{LWR@creatinglwarpmk}
72 }

```

- Opt `OSWindows` Tells `lwarp` to use MS-Windows compatibility. Auto-detection of the operating system is attempted, and this option is only necessary if the auto-detection fails. See the automatically-generated `lwarpmk.conf` file to find out whether the operating system was detected correctly.

```

73 \DeclareVoidOption{OSWindows}{
74 \PackageInfo{lwarp}{Using option 'OSWindows'}
75 \LWR@setOSWindows
76 }

```

- Opt `HomeHTMLFilename` The filename of the homepage. The default is the jobname. This option is stored into `\LWR@HomeHTMLFilename`, and later transferred into `\HomeHTMLFilename` for internal use.

```
77 \DeclareStringOption[] {HomeHTMLFilename}
```

- Opt `HTMLFilename` The filename prefix of web pages after the homepage. The default is empty, no prefix. This option is stored into `\LWR@HTMLFilename`, and later transferred into `\HTMLFilename` for internal use.

```
78 \DeclareStringOption[] {HTMLFilename}
```

- Opt `latexmk` Option `latexmk` tells `lwarpmk` to use `latexmk` when compiling documents.

```
79 \DeclareBoolOption[false]{latexmk}
```

- Execute options** Execute the package options, with the defaults which have been set just above:

```
80 \ProcessKeyvalOptions*\relax
```

Assign the `\BaseJobname` if the user hasn't provided one:

```
81 \providecommand*{\BaseJobname}{\LWR@BaseJobname}
```

Defaults unless already over-ridden by the user:

```
82 \ifcsempty{\LWR@HomeHTMLFilename}{
83 \newcommand*{\HomeHTMLFilename}{\BaseJobname}
```

---

```

84 }{
85 \csedef{HomeHTMLFilename}{\LWR@HomeHTMLFilename}
86 }
87
88 \csedef{HTMLFilename}{\LWR@HTMLFilename}

```

## 19.1 Conditional compilation

\warpprintonly {\langle contents \rangle}

Only process the contents if producing printed output.

```
89 \newcommand{\warpprintonly}[1]{\ifbool{warpingprint}{#1}{}}
```

\warpHTMLonly {\langle contents \rangle}

Only process the contents if producing HTML output.

```
90 \newcommand{\warpHTMLonly}[1]{\ifbool{warpingHTML}{#1}{}}
```

Pkg comment Provides conditional code blocks.

```
91 \RequirePackage{comment}
```

Use `comment_print.cut` for print mode, and `comment_html.cut` for HTML mode. This helps `latexmk` to more reliably know whether to recompile.

```

92 \ifbool{warpingHTML}{
93 \def\DefaultCutFileName{\def\CommentCutFile{comment_html.cut}}
94 }{}
95
96 \ifbool{warpingprint}{
97 \def\DefaultCutFileName{\def\CommentCutFile{comment_print.cut}}
98 }{}
99 \excludecomment{testing}

```

Env warpall Anything in the `warpall` environment will be generated for print or HTML outputs.

```
100 \includecomment{warpall}
```

Env warpprint Anything in the `warpprint` environment will be generated for print output only.  
 Env warpHTML

For HTML output:

```

101 \ifbool{warpingHTML}{%
102 \includecomment{warpHTML}
103 }
104 {\excludecomment{warpHTML}}%

105 \ifbool{warpingprint}
106 {\includecomment{warpprint}}
107 {\excludecomment{warpprint}}

```

Optionally generate a local copy of l warpmk. Default to no.

```

108 \ifbool{LWR@creatinglwarpmk}
109 {\includecomment{LWR@createlwarpmk}}
110 {\excludecomment{LWR@createlwarpmk}}

```

## 20 Misplaced packages

Several packages should only be loaded before l warp, and others should only be loaded after.

Packages which should only be loaded before l warp have their own

`l warp-<packagename>.sty`

which will trigger an error if they are loaded after l warp. Examples include fontspec, inputenc, fontenc, and newunicodechar.

`\LWR@loadafter {<packagename>}` Error if this package was loaded before l warp.

```

111 \newcommand*{\LWR@loadafter}[1]{%
112 \@ifpackageloaded{#1}{%
113 {%
114 \PackageError{l warp}{%
115 {Package #1, or one which uses #1, must be loaded after l warp}%
116 {Move \detokenize{\usepackage}{#1} after \detokenize{\usepackage}{l warp}.}%
117 Package #1 may also be loaded by something else, which must also be moved%
118 after l warp.}%
119 }%
120 {}%
121 }

```

`\LWR@loadbefore {<packagename>}` Error if this package is after l warp.

```

122 \newcommand*{\LWR@loadbefore}[1]{%
123 \@ifpackageloaded{#1}%
124 {}%
125 {%
126 \PackageError{lwarp}%
127 {Package #1 must be loaded before lwarp}%
128 {Move \detokenize{\usepackage}{#1} before \detokenize{\usepackage}{lwarp}.}%
129 }%
130 }

```

\LWR@loadnever {\langle badpackagename\rangle} {\langle replacementpkgnname\rangle}

The first packages is not supported, so tell the user to use the second instead.

```

131 \newcommand*{\LWR@loadnever}[2]{%
132 \PackageError{lwarp}%
133 {Package #1 is not supported by lwarp's HTML conversion.%
134 Package(s) #2 may be useful instead}%
135 {Package #1 might conflict with lwarp in some way,%
136 or is superceded by another package.%
137 For a possible alternative, see package(s) #2.}%
138 }

```

Packages which should only be loaded after lwarp are tested here to trip an error of they have already been loaded.

The following packages must be loaded after lwarp:

```

139 \LWR@loadafter{a4}%
140 \LWR@loadafter{a4wide}%
141 \LWR@loadafter{a5comb}%
142 \LWR@loadafter{abstract}%
143 \LWR@loadafter{adjmulticol}%
144 \LWR@loadafter{addlines}%
145 \LWR@loadafter{afterpage}%
146 \LWR@loadafter{algorithmicx}%
147 \LWR@loadafter{alltt}%
148 \LWR@loadafter{amsthm}%
149 \LWR@loadafter{anonchap}%
150 \LWR@loadafter{anyfontsize}%
151 \LWR@loadafter{appendix}%
152 \LWR@loadafter{arabicfront}%
153 \LWR@loadafter{array}%
154 \LWR@loadafter{authblk}%
155 \LWR@loadafter{balance}%
156 \LWR@loadafter{bigdelim}%
157 \LWR@loadafter{bigstrut}%
158 \LWR@loadafter{bookmark}%

```

```
159 \LWR@loadaft{booktabs}
160 \LWR@loadaft{boxedminipage}
161 \LWR@loadaft{boxedminipage2e}
162 \LWR@loadaft{ccaption}
163 \LWR@loadaft{changepage}
164 \LWR@loadaft{chngpage}
165 \LWR@loadaft{chapg}
166 \LWR@loadaft{color}
167 \LWR@loadaft{crop}
168 \LWR@loadaft{cuted}
169 \LWR@loadaft{cutwin}
170 \LWR@loadaft{dblfnote}
171 \LWR@loadaft{dcolumn}
172 \LWR@loadaft{draftwatermark}
173 \LWR@loadaft{ebook}
174 \LWR@loadaft{ellipsis}
175 \LWR@loadaft{emptypage}
176 \LWR@loadaft{enumerate}
177 \LWR@loadaft{enumitem}
178 \LWR@loadaft{epigraph}
179 \LWR@loadaft{eso-pic}
180 \LWR@loadaft{everypage}
181 \LWR@loadaft{everyshi}
182 \LWR@loadaft{extramarks}
183 \LWR@loadaft{fancybox}
184 \LWR@loadaft{fancyhdr}
185 \LWR@loadaft{fancyvrb}
186 \LWR@loadaft{figcaps}
187 \LWR@loadaft{fix2col}
188 \LWR@loadaft{float}
189 \LWR@loadaft{floatflt}
190 \LWR@loadaft{floatpag}
191 \LWR@loadaft{floatrow}
192 \LWR@loadaft{flushend}
193 \LWR@loadaft{fncychap}
194 \LWR@loadaft{fnpos}
195 \LWR@loadaft{ftnright}
196 \LWR@loadaft{fullpage}
197 \LWR@loadaft{fullwidth}
198 \LWR@loadaft{geometry}
199 \LWR@loadaft{glossaries}
200 % \LWR@loadaft{graphics}%
201 % \LWR@loadaft{graphicx}%
202 \LWR@loadaft{grffile}
203 \LWR@loadaft{hyperref}
204 \LWR@loadaft{hyperxmp}
205 \LWR@loadaft{idxlayout}
206 \LWR@loadaft{indentfirst}
207 \LWR@loadaft{keyfloat}
208 \LWR@loadaft{layout}
```

```
209 \LWR@loadaft{letterspace}
210 \LWR@loadaft{lettrine}
211 \LWR@loadaft{lips}
212 \LWR@loadaft{listings}
213 \LWR@loadaft{longtable}
214 \LWR@loadaft{lscape}
215 \LWR@loadaft{ltcaption}
216 \LWR@loadaft{marginfit}
217 \LWR@loadaft{marginfix}
218 \LWR@loadaft{marginnote}
219 \LWR@loadaft{mcaption}
220 \LWR@loadaft{mdframed}
221 \LWR@loadaft{metalogo}
222 \LWR@loadaft{microtype}
223 \LWR@loadaft{midfloat}
224 \LWR@loadaft{moreverb}
225 \LWR@loadaft{mparhack}
226 \% \LWR@loadaft{multicol} % loaded by ltxdoc
227 \LWR@loadaft{multirow}
228 \LWR@loadaft{nameref}
229 \LWR@loadaft{needspace}
230 \LWR@loadaft{newtxmath}
231 \LWR@loadaft{nextpage}
232 \LWR@loadaft{nonumonpart}
233 \LWR@loadaft{nopageno}
234 \LWR@loadaft{nowidow}
235 \LWR@loadaft{ntheorem}
236 \LWR@loadaft{pagenote}
237 \LWR@loadaft{paralist}
238 \LWR@loadaft{parskip}
239 \LWR@loadaft{pdflscape}
240 \LWR@loadaft{pdfsync}
241 \LWR@loadaft{pfnote}
242 \LWR@loadaft{placeins}
243 \LWR@loadaft{prelim2e}
244 \LWR@loadaft{quotchap}
245 \LWR@loadaft{ragged2e}
246 \LWR@loadaft{realscripts}
247 \LWR@loadaft{relsizet}
248 \LWR@loadaft{romanbar}
249 \LWR@loadaft{romanbarpagenumber}
250 \LWR@loadaft{rotating}
251 \LWR@loadaft{rotfloat}
252 \LWR@loadaft{savetrees}
253 \% \LWR@loadaft{scalefnt} % loaded by babel-french
254 \LWR@loadaft{sectsty}
255 \LWR@loadaft{setspace}
256 \LWR@loadaft{shadow}
257 \LWR@loadaft{showidx}
258 \LWR@loadaft{showkeys}
```

```
259 \LWR@loadafter{sidecap}
260 \LWR@loadafter{sidenotes}
261 \LWR@loadafter{siunitx}
262 \LWR@loadafter{soul}
263 \LWR@loadafter{stabular}
264 \LWR@loadafter{subfig}
265 \LWR@loadafter{supertabular}
266 \LWR@loadafter{tabls}
267 \LWR@loadafter{tabularx}
268 \LWR@loadafter{tabulary}
269 \LWR@loadafter{textarea}
270 % \LWR@loadafter{textcomp}% maybe before lwarf with font packages
271 \LWR@loadafter{textpos}
272 \LWR@loadafter{theorem}
273 \LWR@loadafter{threeparttable}
274 \LWR@loadafter{tikz}
275 \LWR@loadafter{titleps}
276 \LWR@loadafter{titlesec}
277 \LWR@loadafter{titletoc}
278 \LWR@loadafter{titling}
279 \LWR@loadafter{tocbibind}
280 \LWR@loadafter{tocloft}
281 \LWR@loadafter{transparent}
282 \LWR@loadafter{trivfloat}
283 \LWR@loadafter{typearea}
284 \LWR@loadafter{ulem}
285 \LWR@loadafter{upref}
286 \LWR@loadafter{varioref}
287 \LWR@loadafter{verse}
288 \LWR@loadafter{wallpaper}
289 \LWR@loadafter{wrapfig}
290 \LWR@loadafter{xcolor}
291 \LWR@loadafter{xfrac}
292 \LWR@loadafter{xltextra}
293 \LWR@loadafter{xmpincl}
294 \LWR@loadafter{xtab}
295 \LWR@loadafter{zwpagelayout}
```

## 21 Required packages

These packages are automatically loaded by lwarf when generating HTML output. Some of them are also automatically loaded when generating print output, but some are not.

In the document preamble, create a `warpprint` environment, and place inside it any of the following packages which are required and which are labeled as “Print: OK

to Load in a warpprint environment". Those packages which are labeled as "Print: Pre-Loaded" need not be placed into the document preamble.

**for HTML & PRINT:** 296 \begin{warpall}

See: <http://tex.stackexchange.com/a/47579>.

Detects X<sub>E</sub>T<sub>E</sub>X and LuaT<sub>E</sub>X:

```
297 \RequirePackage{iftex}
298 \newif\ifxetexorluatex
299 \ifXeTeX
300     \xetexorluatextrue
301 \else
302     \ifLuaTeX
303         \xetexorluatextrue
304     \else
305         \xetexorluatexfalse
306     \fi
307 \fi

308 \end{warpall}
```

**for HTML output:** 309 \begin{warpHTML}

```
310 \ifxetexorluatex
311 % ^~A      \usepackage[no-math]{fontspec}
```

The monospaced font is used for HTML tags, so turn off its TeX ligatures and common ligatures:

```
312 \defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
313 \defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
314 \defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
315 \else
```

**pdflatex only:** Only pre-loaded if pdflatex is being used.

Pkg microtype

**ligatures** Older browsers don't display ligatures. Turn off letter ligatures, keeping T<sub>E</sub>X dash and quote ligatures, which may fail on older browsers but at least won't corrupt written words.

```
316 \RequirePackage{microtype}
317
318 \microtypesetup{
319     protrusion=false,
```

```

320     expansion=false,
321     tracking=false,
322     kerning=false,
323     spacing=false}
324
325 \DisableLigatures[f,q,t,T,Q]{encoding = *,family = *}
326 \fi
327 \end{warpHTML}

```

Pkg `geometry` Tactics to avoid unwanted page breaks and margin overflow:

- Uses a very long and wide page to minimize page breaks and margin overflow.
- Uses a scriptsize font.
- Uses extra space at the margin to avoid HTML tag overflow off the page.
- Forces a new PDF page before some environments.
- Forces line break between major pieces of long tags.

**for HTML output:** 328 `\begin{warpHTML}`  
 329 `\RequirePackage[paperheight=190in,paperwidth=20in,%`  
`330 left=2in,right=12in,%`  
`331 top=1in,bottom=1in,%`  
`332 ]{geometry}`  
`333 \@twosidefalse`  
`334 \mparswitchfalse`  
`335 \end{warpHTML}`

**for HTML & PRINT:** 336 `\begin{warpall}`

Pkg `xparse`

TeX3 command argument parsing

```
337 \RequirePackage{xparse}
```

Pkg `afterpackage` Used to patch titling to add `\AddSubtitlePublished`.

```
338 \RequirePackage{afterpackage}
```

```
339 \end{warpall}
```

**for HTML output:** 340 `\begin{warpHTML}`

Pkg **expl3**

TeX3 programming

341 \RequirePackage{expl3}

Pkg **gettitlestring**

Used to emulate \nameref.

342 \RequirePackage{gettitlestring}

Pkg **everyhook**

everyhook is used to patch paragraph handling.

343 \RequirePackage{everyhook}  
344 \end{warpHTML}

**for HTML & PRINT:** 345 \begin{warpall}

Pkg **filecontents**

Used to write helper files, done in print mode.

Patched to work with morewrites, per <https://tex.stackexchange.com/questions/312830/does-morewrites-not-support-filecontents-and-can-i-write-body-of-environment-us/312910>

346 \RequirePackage{filecontents}  
347  
348 \@ifpackagelater{filecontents}{2011/10/09} %  
349 {}  
350 {  
351 \newwrite\fcwrite  
352 \let\LWR@origfilec@ntents\filec@ntents  
353 \def\filec@ntents{\def\chardef##1\write{\let\reserved@c\fcwrite}\LWR@origfilec@ntents}  
354 }  
  
355 \end{warpall}

**for HTML output:** 356 \begin{warpHTML}

Pkg **xifthen**

357 \RequirePackage{xifthen}

Pkg **xstring**

```
358 \RequirePackage{xstring}

Pkg  xstring

359 \RequirePackage{verbatim}

Pkg  makeidx

360 \RequirePackage{makeidx}
361 \makeindex

Pkg  calc

362 \RequirePackage{calc}

Pkg  refcount

363 \RequirePackage{refcount}

Pkg  newfloat

364 \RequirePackage{newfloat}

Pkg  caption

365 \RequirePackage{caption}

366 \end{warpHTML}

for HTML & PRINT: 367 \begin{warpall}

Pkg  environ

Used to encapsulate math environments for re-use in HTML ALT text.

368 \RequirePackage{environ}

369 \end{warpall}

for HTML output: 370 \begin{warpHTML}

Pkg  zref

Used for cross-references.

371 \RequirePackage{zref}
```

Pkg amsmath

Equation numbers are placed to the left for HTML.

newtxmath automatically loads amsmath, so the options leqno and fleqn are passed beforehand to be picked up both here and by newtxmath if it is used.

```
372 \PassOptionsToPackage{leqno}{amsmath}
373 \RequirePackage{amsmath}
```

Used to convert lengths for image width/height options.

```
374 \RequirePackage{printlen}
375 \end{warpHTML}
```

## 22 Loading packages

**for HTML output:** 376 \begin{warpHTML}

Remember the original \RequirePackage:

```
377 \LetLtxMacro{\LWR@origRequirePackage}{\RequirePackage}
```

\LWR@requirepackagenames Stores the list of required package names.

```
378 \newcommand*{\LWR@requirepackagenames}{}%
```

\LWR@findword [*1: separator*] [*2: list*] [*3: index*] [*4: destination*]

Note that argument 4 is passed directly to \StrBetween.

```
379 \newcommand*\LWR@findword[3][,]{%
380     \StrBetween[#3,\numexpr#3+1]{#1#2#1}{#1}%
381 }
```

\LWR@lookforpackagename [*index*] If this is a package name, re-direct it to the lwarp version by renaming it lwarp- followed by the original name.

```
382 \newcommand*{\LWR@lookforpackagename}[1]{%
```

Find the n'th package name from the list:

```
383 \LWR@findword{\LWR@requirepackagenames}{#1}[\LWR@strresult]%
```

Remove blanks. The original name with blanks is in `LWR@strresult` and the final name with no blanks goes into `LWR@strresulttwo`.

```
384 \StrSubstitute[100]{\LWR@strresult}{ }{ }[\LWR@strresulttwo]%
```

See if the package name was found:

```
385 \IfStrEq{\LWR@strresulttwo}{}%
386 {}% no filename
387 {}% yes filename
```

If found, and if an `l warp`-equivalent name exists, use `l warp-*` instead.

```
388 \IfFileExists{l warp-\LWR@strresulttwo.sty}%
389 {}% l warp-* file found
390     \StrSubstitute%
391         {\LWR@requirepackagenames}%
392         {\LWR@strresult}%
393         {l warp-\LWR@strresulttwo}[\LWR@requirepackagenames]%
394 }%
395 {}% no l warp-* file
396 {}% yes filename
397 }
```

`\RequirePackage` [*1: options*] [*2: package names*] [*3: version*]

For each of many package names in a comma-separated list, if an `l warp` version of a package exists, select it instead of the `LETX` version.

```
398 \RenewDocumentCommand{\RequirePackage}{o m o}{%
```

Redirect up to nine names:

```
399 \renewcommand*{\LWR@requirepackagenames}{#2}
400 \LWR@lookforpackagename{1}
401 \LWR@lookforpackagename{2}
402 \LWR@lookforpackagename{3}
403 \LWR@lookforpackagename{4}
404 \LWR@lookforpackagename{5}
405 \LWR@lookforpackagename{6}
406 \LWR@lookforpackagename{7}
407 \LWR@lookforpackagename{8}
408 \LWR@lookforpackagename{9}
```

`\RequirePackage` depending on the options and version:

```
409 \IfValueTF{#1}
410 {}% options given
```

```

411      \IfValueTF{#3}{% version given?
412      {\LWR@origRequirePackage[#1]{\LWR@requirepackagenames}[#3]}
413      {\LWR@origRequirePackage[#1]{\LWR@requirepackagenames}}
414 }
415 {%
416     \IfValueTF{#3}{% version given?
417     {\LWR@origRequirePackage{\LWR@requirepackagenames}[#3]}
418     {\LWR@origRequirePackage{\LWR@requirepackagenames}}
419 }
420 }
421 \LetLtxMacro{\usepackage}{\RequirePackage}

```

\LWR@ProvidesPackagePass {*pkgnname*} [*version*]

Uses the original package, including options.

```

422 \NewDocumentCommand{\LWR@ProvidesPackagePass}{m o}{
423 \PackageInfo{lwarp}{Using package '#1' and adding lwarp modifications, including options,}%
424 \IfValueTF{#2}
425 {\ProvidesPackage{lwarp-#1}[#2]}
426 {\ProvidesPackage{lwarp-#1}}
427 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{#1}}
428 \ProcessOptions\relax
429
430 \IfValueTF{#2}
431 {\LWR@origRequirePackage[#1][#2]}
432 {\LWR@origRequirePackage[#1]}
433 }

```

\LWR@ProvidesPackageDrop {*pkgnname*} [*version*]

Ignores the original package and uses lwarp's version instead. Drops/discards all options.

```

434 \NewDocumentCommand{\LWR@ProvidesPackageDrop}{m o} {
435 \PackageInfo{lwarp}{Replacing package '#1' with the lwarp version, discarding options,}%
436 \IfValueTF{#2}
437 {\ProvidesPackage{lwarp-#1}[#2]}
438 {\ProvidesPackage{lwarp-#1}}
439 \DeclareOption*{}
440 \ProcessOptions\relax
441 }

442 \end{warpHTML}

```

## 23 File handles

Defines file handles for writes.

**for HTML & PRINT:** 443 `\begin{warpall}`

`\LWR@quickfile` For quick temporary use only. This is reused in several places.

```
444 \newwrite\LWR@quickfile%
445 \end{warpall}
```

**for HTML output:** 446 `\begin{warpHTML}`

`\LWR@lateximagesfile` For `lateximages.txt`.

```
447 \newwrite\LWR@lateximagesfile
448 \end{warpHTML}
```

## 24 Include a file

During HTML output, `\include{<filename>}` causes the following to occur:

1. lwarp creates `<filename>_html_inc.tex` whose contents are:  
`\input <filename>.tex`
2. `<filename>_html_inc.tex` is then `\included` instead of `<filename>.tex`.
3. `<filename>_html_inc.aux` is automatically generated and used by L<sup>A</sup>T<sub>E</sub>X.

**for HTML output:** 449 `\begin{warpHTML}`

`\include {\langle filename \rangle}`

`\@include {\langle filename \rangle}` Modified to load `_html_inc` files.

```
450 \def\@include#1 {%
451 \immediate\openout\LWR@quickfile #1_html_inc.tex% new
452 \immediate\write\LWR@quickfile{\string\input{#1.tex}}% new
```

```

453 \immediate\closeout\LWR@quickfile% new
454 \LWR@origclearpage% \changed
455 \if@files w
456   \immediate\write\@mainaux{\string\@input{#1_html_inc.aux}}% changed
457 \fi
458 \tempswat rue
459 \if@partsw
460   \tempswaf al se
461   \edef\reserved@b{#1}%
462   \for\reserved@a:=\partlist\do
463     {\ifx\reserved@a\reserved@b\tempswat rue\fi}%
464 \fi
465 \if@tempswa
466   \let\auxout\partaux
467   \if@files w
468     \immediate\openout\partaux #1_html_inc.aux % changed
469     \immediate\write\partaux{\relax}%
470   \fi
471   \input{#1_html_inc.tex}% changed
472   \LWR@origclearpage% changed
473   \writeckpt{#1}%
474   \if@files w
475     \immediate\closeout\partaux
476   \fi
477 \else
478   \deadcycles{z@}
479   \nameuse{cp@#1}%
480 \fi
481 \let\auxout\mainaux%
482 }

483 \end{warpHTML}

```

## 25 Copying a file

**for HTML output:** 484 \begin{warpHTML}

\LWR@copyfile {<source filename>} {<destination filename>}

Used to copy the .toc file to .sidetoc to re-print the toc in the sidetoc navigation pane.

```

485 \newwrite\LWR@copyoutfile % open the file to write to
486 \newread\LWR@copyinfile % open the file to read from
487
488 \newcommand*\LWR@copyfile[2]{%

```

```

489 \immediate\openout\LWR@copyoutfile=#2
490 \openin\LWR@copyinfile=#1
491 \begingroup\endlinechar=-1
492 \makeatletter
493 \loop\unless\ifeof\LWR@copyinfile
494   \read\LWR@copyinfile to\LWR@fileline % Read one line and store it into \LWR@fileline
495 %   \LWR@fileline\par % print the content into the pdf
496 % print the content:
497   \immediate\write\LWR@copyoutfile{\unexpanded\expandafter{\LWR@fileline}}%
498 \repeat
499 \closeout\LWR@copyoutfile
500 \endgroup
501 }

502 \end{warpHTML}

```

## 26 Debugging messages

```
503 \begin{warpall}
```

Bool LWR@tracinglwarp True if tracing is turned on.

```
504 \newbool{LWR@tracinglwarp}
```

\tracinglwarp Turns on the debug tracing messages.

```
505 \newcommand{\tracinglwarp}{\booltrue{LWR@tracinglwarp}}
```

\LWR@traceinfo {\text} If tracing is turned on, writes the text to the .log file.

```

506 \newcommand{\LWR@traceinfo}[1]{%
507 \ifbool{LWR@tracinglwarp}{%
508 {%
509   \typeout{*** lwarp: #1}%
510   % \PackageInfo{lwarp}{#1 : }%
511 }%
512 {}%
513 }

```

Bool HTMLDebugComments Default false. Add comments in HTML about closing <div>s, sections, etc.

```

514 \newbool{HTMLDebugComments}
515 \boolfalse{HTMLDebugComments}

```

If \tracinglwarp, show where preamble hooks occur:

```
516 \AfterEndPreamble{
517 \LWR@traceinfo{AfterEndPreamble}
518 }
519
520 \AtBeginDocument{
521 \LWR@traceinfo{AtBeginDocument}
522 }
```

## 27 HTML-conversion output modifications

These booleans modify the HTML output in various ways to improve conversion to EPUB or word processor imports.

Bool FormatEPUB Default false. Changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.

```
523 \newbool{FormatEPUB}
524 \boolfalse{FormatEPUB}
```

Bool FormatWordProcessor Default false. Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments.

```
525 \newbool{FormatWordProcessor}
526 \boolfalse{FormatWordProcessor}
```

Bool HTMLMarkFloats Default true. Adds

```
    === table begin
    ...
    === end
```

or

```
    === figure begin
    ...
    === end
```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames.<sup>12</sup>

---

```
527 \newbool{HTMLMarkFloats}
528 \booltrue{HTMLMarkFloats}
```

<sup>12</sup>Perhaps some day word processors will have HTML import options for identifying <div> classes for figures and tables, along with the associated captions.

```
529 \end{warpall}
```

## 28 Remembering original formatting macros

for HTML output: 530 \begin{warpHTML}

Remember original definitions of formatting commands. Will be changed to `HTML` commands for most uses. Will be temporarily restored to original meaning inside any `lateximage` environment. Also nullify unused commands.

```
531 \LetLtxMacro{\LWR@origtextrm}{\textrm}
532 \LetLtxMacro{\LWR@origtextsfsf}{\textsf}
533 \LetLtxMacro{\LWR@origtexttt}{\texttt}
534 \LetLtxMacro{\LWR@origtextnormal}{\textnormal}
535 \LetLtxMacro{\LWR@origtextbf}{\textbf}
536 \LetLtxMacro{\LWR@origtextmd}{\textmd}
537 \LetLtxMacro{\LWR@origtextit}{\textit}
538 \LetLtxMacro{\LWR@origtextsl}{\textsl}
539 \LetLtxMacro{\LWR@origtextsc}{\textsc}
540 \LetLtxMacro{\LWR@origtextup}{\textup}
541 \LetLtxMacro{\LWR@origemph}{\emph}
542
543 \LetLtxMacro{\LWR@origrmfamily}{\rmfamily}
544 \LetLtxMacro{\LWR@origsffamily}{\sffamily}
545 \LetLtxMacro{\LWR@origttfamily}{\ttfamily}
546 \LetLtxMacro{\LWR@origbfseries}{\bfseries}
547 \LetLtxMacro{\LWR@origmdseries}{\mdseries}
548 \LetLtxMacro{\LWR@origupshape}{\upshape}
549 \LetLtxMacro{\LWR@origslshape}{\slshape}
550 \LetLtxMacro{\LWR@origscshape}{\scshape}
551 \LetLtxMacro{\LWR@origitshape}{\itshape}
552 \LetLtxMacro{\LWR@origem}{\em}
553 \LetLtxMacro{\LWR@orignormalfont}{\normalfont}
554
555 \let\LWR@origraggedright\raggedright
556 \let\LWR@origonecolumn\onecolumn
557
558 \let\LWR@origsp\sp
559 \let\LWR@origsb\sb
560 \let\LWR@origtextsuperscript\textsuperscript
561 \let\LWR@origtextsubscript\textsubscript
562 \LetLtxMacro{\LWR@origunderline}{\underline}
563
564 \let\LWR@origscriptsize\scriptsize
565
566 \let\LWR@orignewpage\newpage
```

```

567
568 \let\LWR@origpagestyle\pagestyle
569 \let\LWR@origthispagestyle>thispagestyle
570 \let\LWR@origpagenumbering\pagenumbering
571
572 \LetLtxMacro{\LWR@origminipage}{\minipage}
573 \let\LWR@origendminipage\endminipage
574 \LetLtxMacro{\LWR@origparbox}{\parbox}
575
576 \let\LWR@orignewline\newline
577
578 \LetLtxMacro{\LWR@origitem}{\item}
579
580 \LetLtxMacro{\LWR@origitemize}{\itemize}
581 \LetLtxMacro{\LWR@endorigitemize}{\enditemize}
582 \LetLtxMacro{\LWR@origenumerate}{\enumerate}
583 \LetLtxMacro{\LWR@endorigenumerate}{\endenumerate}
584 \LetLtxMacro{\LWR@origdescription}{\description}
585 \LetLtxMacro{\LWR@endorigdescription}{\enddescription}
586
587 \let\LWR@origpar\par
588
589 \LetLtxMacro{\LWR@origfootnote}{\footnote}
590 \let\LWR@orig@mpfootnotetext\@mpfootnotetext
591
592 \let\LWR@origclearpage\clearpage
593 \let\clearpage\relax
594 \let\cleardoublepage\relax

595 \end{warpHTML}

```

## 29 Accents

Native  $\text{\TeX}$  accents such as  $\text{\^n}$  will work, but many more kinds of accents are available when using Unicode-aware  $\text{Xe}\text{\TeX}$  and  $\text{Lua}\text{\TeX}$ .

**for HTML output:** 596 \begin{warpHTML}

Without  $\text{\AtBeginDocument}$ ,  $\text{\t}$  was being re-defined somewhere.

597 \AtBeginDocument{

The following are restored for print when inside a  $\text{lateximage}$ .

For Unicode engines, only  $\text{\t}$  needs to be redefined:

---

```
598 \LetLtxMacro{\LWR@origt}{\t}
```

For pdf $\text{\TeX}$ , additional work is required:

```
599 \ifPDFTeX
600 \LetLtxMacro{\LWR@origequalaccent}{\=}
601 \LetLtxMacro{\LWR@origdotaccent}{\.\.}
602 \LetLtxMacro{\LWR@origu}{\u}
603 \LetLtxMacro{\LWR@origv}{\v}
604 \LetLtxMacro{\LWR@origc}{\c}
605 \LetLtxMacro{\LWR@origd}{\d}
606 \LetLtxMacro{\LWR@origb}{\b}
```

The HTML redefinitions follow.

For pdf $\text{\TeX}$ , Unicode diacritical marks are used:

```
607 \renewcommand*{\=}[1]{\#1\HTMLunicode{0305}}
608 \renewcommand*{\.\.}[1]{\#1\HTMLunicode{0307}}
609 \renewcommand*{\u}[1]{\#1\HTMLunicode{0306}}
610 \renewcommand*{\v}[1]{\#1\HTMLunicode{030C}}
611 \renewcommand*{\c}[1]{\#1\HTMLunicode{0327}}
612 \renewcommand*{\d}[1]{\#1\HTMLunicode{0323}}
613 \renewcommand*{\b}[1]{\#1\HTMLunicode{0331}}
614 \fi
```

For all engines, a Unicode diacritical tie is used:

```
615 \def\LWR@t{\#1\HTMLunicode{0361}\#2}
616 \renewcommand*{\t}[1]{\LWR@t}
```

`\LWR@restoreorigaccents` Called from `\restoreoriginalformatting` when a `lateximage` is begun.

```
617 \ifPDFTeX
618 \newcommand*{\LWR@restoreorigaccents}{%
619 \LetLtxMacro{\=}{\LWR@origequalaccent}%
620 \LetLtxMacro{\.\.}{\LWR@origdotaccent}%
621 \LetLtxMacro{\u}{\LWR@origu}%
622 \LetLtxMacro{\v}{\LWR@origv}%
623 \LetLtxMacro{\t}{\LWR@origt}%
624 \LetLtxMacro{\c}{\LWR@origc}%
625 \LetLtxMacro{\d}{\LWR@origd}%
626 \LetLtxMacro{\b}{\LWR@origb}%
627 }
628 \else% XeLaTeX, LuaLaTeX:
629 \newcommand*{\LWR@restoreorigaccents}{%
630 \LetLtxMacro{\t}{\LWR@origt}%
631 }
632 \fi
```

---

633 }% AtBeginDocument

634 \end{warpHTML}

## 30 Configuration Files

635 \begin{warpprint}  
636 \typeout{l warp: generating configuration files}  
637 \end{warpprint}

### 30.1 project\_html.tex

File `project_html.tex` Used to allow an HTML version of the document to exist alongside the print version.

Only write `\jobname_html.tex` if generating the print version.

638 \begin{warpprint}  
639 \immediate\openout\LWR@quickfile=\jobname\_html.tex  
640 \immediate\write\LWR@quickfile{  
641 \detokenize{\PassOptionsToPackage}{%  
642 {warpHTML,BaseJobname=\jobname}{l warp}}%  
643 }  
644 \immediate\write\LWR@quickfile{  
645 \detokenize{\input}\string{\jobname.tex}\string }%  
646 }  
647 \immediate\closeout\LWR@quickfile  
648 \end{warpprint}

### 30.2 lwarpmk.conf

File `lwarpmk.conf` `lwarpmk.conf` is automatically (re-)created by the `l warp` package when executing `pdflatex <project.tex>`, or similar for `xelatex` or `lualatex`, in print-document generation mode, which is the default unless the `warpHTML` option is given. `lwarpmk.conf` is then used by the utility `lwarpmk`.

An example `lwarpmk.conf`:

---

```
opsystem = "Unix" -- or "Windows"
latexname = "pdflatex" -- or "lualatex" or "xelatex"
sourcename = "projectname" -- your .tex source
homehtmlfilename = "index" -- or "projectname"
htmlfilename = "" -- or "projectname" if numbered HTML files
```

---

```

for PRINT output: 649 \begin{warpprint}
650 \ifcsdef{LWR@quickfile}{}{\newwrite{\LWR@quickfile}}
651 \immediate\openout\LWR@quickfile=lwarpmk.conf
652 \ifbool{usingOSWindows}{
653 \immediate\write{\LWR@quickfile{opsystem = "Windows"}}
654 }{
655 \immediate\write{\LWR@quickfile{opsystem = "Unix"}}
656 }
657 \ifPDFTeX
658 \immediate\write{\LWR@quickfile{latexname = "pdflatex"}}
659 \fi
660 \ifXeTeX
661 \immediate\write{\LWR@quickfile{latexname = "xelatex"}}
662 \fi
663 \ifLuaTeX
664 \immediate\write{\LWR@quickfile{latexname = "lualatex"}}
665 \fi
666 \immediate\write{\LWR@quickfile{sourcename = "\jobname"}
667 \immediate\write{\LWR@quickfile{%
668 homehtmlfilename = "\HomeHTMLFilename"%
669 }
670 \immediate\write{\LWR@quickfile{htmlfilename = "\HTMLFilename"}
671 \immediate\write{\LWR@quickfile{latexmk = "\ifbool{LWR@latexmk}{true}{false}"}
672 \immediate\write{\LWR@quickfile{language = "\LWR@IndexLanguage"}
673 \immediate\write{\LWR@quickfile{xdyfile = "\LWR@xdyFilename"}
674 \immediate\closeout{\LWR@quickfile
675 \end{warpprint}
```

### 30.3 project.lwarpmkconf

File project.lwarpmkconf A project-specific configuration file for lwarpmk.

```

676 \begin{warpprint}
677 \ifcsdef{LWR@quickfile}{}{\newwrite{\LWR@quickfile}}
678 \immediate\openout{\LWR@quickfile=\jobname.lwarpmkconf
679 \ifbool{usingOSWindows}{
680 \immediate\write{\LWR@quickfile{opsystem = "Windows"}}
681 }{
682 \immediate\write{\LWR@quickfile{opsystem = "Unix"}}
683 }
684 \ifPDFTeX
685 \immediate\write{\LWR@quickfile{latexname = "pdflatex"}}
686 \fi
687 \ifXeTeX
688 \immediate\write{\LWR@quickfile{latexname = "xelatex"}
```

```
689 \fi
690 \ifLuaTeX
691 \immediate\write\LWR@quickfile{latexname = "lualatex"}
692 \fi
693 \immediate\write\LWR@quickfile{sourcename = "\jobname"}
694 \immediate\write\LWR@quickfile{%
695 homehtmlfilename = "\HomeHTMLFilename"%
696 }
697 \immediate\write\LWR@quickfile{htmlfilename = "\HTMLFilename"}
698 \immediate\write\LWR@quickfile{latexmk = "\ifbool{LWR@latexm}{true}{false}"}
699 \immediate\write\LWR@quickfile{language = "\LWR@IndexLanguage"}
700 \immediate\write\LWR@quickfile{xdfyfile = "\LWR@xdfyFilename"}
701 \immediate\closeout\LWR@quickfile
702 \end{warpprint}
```

### 30.4 lwarp.css

File `lwarp.css` This is the base css layer used by lwarp.

This must be present both when compiling the project and also when distributing the HTML files.

```
703 \begin{warpprint}
704 \begin{filecontents*}{lwarp.css}
705 /*
706   CSS stylesheet for the LaTeX lwarp package
707   Copyright 2016-2017 Brian Dunn -- BD Tech Concepts LLC
708 */
709
710
711 /* a fix for older browsers: */
712 header, section, footer, aside, nav, main,
713   article, figure { display: block; }
714
715
716 A:link {color:#000080 ; text-decoration: none ; }
717 A:visited {color:#800000 ; }
718 A:hover {color:#000080 ; text-decoration: underline ;}
719 A:active {color:#800000 ; }
720
721 a.tocpart {display: inline-block ; margin-left: 0em ;
722   font-weight: bold ;}
723 a.tocchapter {display: inline-block ; margin-left: 0em ;
724   font-weight: bold ;}
725 a.tocsection {display: inline-block ; margin-left: 1em ;
726   text-indent: -.5em ; font-weight: bold ;}
727 a.tocsubsection {display: inline-block ; margin-left: 2em ;
```

```
728     text-indent: -.5em ; }
729 a.tocsubsubsection {display: inline-block ; margin-left: 3em ;
730     text-indent: -.5em ; }
731 a.tocparagraph {display: inline-block ; margin-left: 4em ;
732     text-indent: -.5em ; }
733 a.tocsubparagraph {display: inline-block ; margin-left: 5em ;
734     text-indent: -.5em ; }
735 a.tocfigure {margin-left: 0em}
736 a.tocsubfigure {margin-left: 2em}
737 a.toctable {margin-left: 0em}
738 a.tocsubtable {margin-left: 2em}
739 a.toctheorem {margin-left: 0em}
740 a.toclstlisting {margin-left: 0em}
741
742
743 body {
744     font-family: "DejaVu Serif", "Bitstream Vera Serif",
745             "Lucida Bright", Georgia, serif;
746     background: #FAF7F4 ;
747     color: black ;
748     margin:0em ;
749     padding:0em ;
750     font-size: 100% ;
751     line-height: 1.2 ;
752 }
753
754 p {margin: 1.5ex 0em 1.5ex 0em ;}
755
756 /* Holds a section number to add space between it and the name */
757 span.sectionnumber { margin-right: 0em }
758
759 /* Inserted in front of index lines */
760 span.indexitem {margin-left: 0em}
761 span.indexsubitem {margin-left: 2em}
762 span.indexsubsubitem {margin-left: 4em}
763
764 div.hidden, span.hidden { display: none ; }
765
766 kbd {
767     font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
768             "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
769             "Courier New", monospace;
770     font-size: 100% ;
771 }
772
773 pre { padding: 3pt ; }
774
775 span.strong { font-weight: bold; }
776
777 span.textmd { font-weight: normal; }
```

```
778
779 span.textsc { font-variant: small-caps; }
780
781 span.textsl { font-style: oblique; }
782
783 span.textup { font-variant: normal; }
784
785 span.textrm {
786     font-family: "DejaVu Serif", "Bitstream Vera Serif",
787     "Lucida Bright", Georgia, serif;
788 }
789
790 span.textsf {
791     font-family: "DejaVu Sans", "Bitstream Vera Sans",
792     Geneva, Verdana, sans-serif ;
793 }
794
795 span.textcircled { border: 1px solid black ; border-radius: 1ex ; }
796
797 span.underline {
798     text-decoration: underline ;
799     text-decoration-skip ;
800 }
801
802
803 /* For realscripts */
804 .supsubscript {
805     display: inline-block;
806     text-align:left ;
807 }
808
809 .supsubscript sup,
810 .supsubscript sub {
811     position: relative;
812     display: block;
813     font-size: .5em;
814     line-height: 1;
815 }
816
817 .supsubscript sup {
818     top: .5em;
819 }
820
821 .supsubscript sub {
822     top: .5em;
823 }
824
825 span.attribution {
826     margin-left: 1em ; font-size: 80% ; font-variant: small-caps;
827 }
```

```
828
829 span.citetitle {
830   margin-left: 1em ; font-size: 80% ; font-style: oblique;
831 }
832
833 span.poemtitle {
834   font-size: 120% ; font-weight: bold;
835 }
836
837 blockquote {
838   margin-left: 0px ;
839   margin-right: 0px ;
840 }
841
842 /* quotchap is for the quotchap package */
843 div.quotchap {
844   font-style: oblique ;
845   overflow-x: auto ;
846   margin-left: 2em ;
847   margin-right: 2em ;
848 }
849
850 blockquote p, div.quotchap p {
851   line-height: 1.5;
852   text-align: left ;
853   font-size: .85em ;
854   margin-left: 3em ;
855   margin-right: 3em ;
856 }
857
858 /* qauthor is for the quotchap package */
859 div.qauthor {
860   display: block ;
861   text-align: right ;
862   margin-left: auto ;
863   margin-right: 2em ;
864   font-size: 80% ;
865   font-variant: small-caps;
866 }
867
868 div.qauthor p {
869   text-align: right ;
870 }
871
872 blockquotation {
873   margin-left: 0px ;
874   margin-right: 0px ;
875 }
876
877 blockquotation p {
```

```
878 line-height: 1.5;
879   text-align: left ;
880   font-size: .85em ;
881   margin-left: 3em ;
882   margin-right: 3em ;
883 }
884
885 div.epigraph {
886   line-height: 1.2;
887   text-align: left ;
888   padding: 3ex 1em 0ex 1em ;
889 /*    margin: 3ex auto 3ex auto ; */ /* Epigraph centered */
890   margin: 3ex 1em 3ex auto ; /* Epigraph to the right */
891 /*    margin: 3ex 1em 3ex 1em ; */ /* Epigraph to the left */
892   font-size: .85em ;
893   max-width: 27em ;
894 }
895
896
897
898 div.epigraphsource{
899   text-align:right ;
900   margin-left:auto ;
901 /*    max-width: 50% ; */
902   border-top: 1px solid #AOAOAO ;
903   padding-bottom: 3ex ;
904   line-height: 1.2;
905 }
906
907 div.epigraph p { padding: .5ex ; margin: 0ex ;}
908 div.epigraphsource p { padding: .5ex 0ex 0ex 0ex ; margin: 0ex ;}
909
910
911 /* lettrine package: */
912 span.lettrine { font-size: 3ex ; float: left ; }
913 span.lettrinetext { font-variant: small-caps ; }
914
915 /* ulem and soul packages: */
916 span.uline {
917   text-decoration: underline ;
918   text-decoration-skip ;
919 }
920
921 span.uline {
922   text-decoration: underline ;
923   text-decoration-skip ;
924   text-decoration-style: double ;
925 }
926
927 span.uwave {
```

```
928     text-decoration: underline ;
929     text-decoration-skip ;
930     text-decoration-style: wavy ;
931 }
932
933 span.sout {
934     text-decoration: line-through ;
935 }
936
937 span.xout {
938     text-decoration: line-through ;
939 }
940
941 span.dashuline {
942     text-decoration: underline ;
943     text-decoration-skip ;
944     text-decoration-style: dashed ;
945 }
946
947 span.dotuline {
948     text-decoration: underline ;
949     text-decoration-skip ;
950     text-decoration-style: dotted ;
951 }
952
953 span.letterspacing { letter-spacing: .2ex ; }
954
955 span.capsspacing {
956     font-variant: small-caps ;
957     letter-spacing: .1ex ;
958 }
959
960 span.highlight { background: #F8E800 ; }
961
962
963
964
965 html body {
966     margin: 0 ;
967     line-height: 1.2;
968 }
969
970
971 body div {
972     margin: 0ex;
973 }
974
975
976 h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
977 {
```

```
978     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
979         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
980         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
981         "Times New Roman", serif;
982     font-style: normal ;
983     font-weight: bold ;
984     text-align: left ;
985 }
986
987 h1 { /* title of the entire website, used on each page */
988     text-align: center ;
989     font-size: 2.5em ;
990     padding: .4ex 0em 0ex 0em ;
991 }
992 h2 { font-size: 2.25em }
993 h3 { font-size: 2em }
994 h4 { font-size: 1.75em }
995 h5 { font-size: 1.5em }
996 h6 { font-size: 1.25em }
997 span.paragraph {font-size: 1em ; font-variant: normal ;
998     margin-right: 1em ; }
999 span.subparagraph {font-size: 1em ; font-variant: normal ;
1000     margin-right: 1em ; }
1001
1002
1003
1004 /* Title of the file */
1005 h1 {
1006     margin: 0ex 0em 0ex 0em ;
1007     line-height: 1.3;
1008     text-align: center ;
1009 }
1010
1011 /* Part */
1012 h2 {
1013     margin: 1ex 0em 1ex 0em ;
1014     line-height: 1.3;
1015     text-align: center ;
1016 }
1017
1018 /* Chapter */
1019 h3 {
1020     margin: 3ex 0em 1ex 0em ;
1021     line-height: 1.3;
1022 }
1023
1024 /* Section */
1025 h4 {
1026     margin: 3ex 0em 1ex 0em ;
1027     line-height: 1.3;
```

```
1028 }
1029
1030 /* Sub-Section */
1031 h5 {
1032   margin: 3ex 0em 1ex 0em ;
1033   line-height: 1.3;
1034 }
1035
1036 /* Sub-Sub-Section */
1037 h6 {
1038   margin: 3ex 0em 1ex 0em ;
1039   line-height: 1.3;
1040 }
1041
1042
1043 div.titlepage {
1044   text-align: center ;
1045 }
1046
1047 .footnotes {
1048   font-size: .85em ;
1049   margin: 3ex 1em 0ex 1em ;
1050   padding-bottom: 1ex ;
1051   border-top: 1px solid silver ;
1052 }
1053
1054 .marginpar {
1055   max-width:50%;
1056   float:right;
1057   text-align:left;
1058   margin: 1ex 0.5em 1ex 1em ;
1059   padding: 1ex 0.5em 1ex 0.5em ;
1060   font-size: 85% ;
1061   border-top: 1px solid silver ;
1062   border-bottom: 1px solid silver ;
1063   overflow-x: auto;
1064 }
1065
1066 .marginpar br { margin-bottom: 2ex ; }
1067
1068 div.marginblock {
1069   max-width:50%;
1070   float:right;
1071   text-align:left;
1072   margin: 1ex 0.5em 1ex 1em ;
1073   padding: 1ex 0.5em 1ex 0.5em ;
1074   overflow-x: auto;
1075 }
1076
1077 div.marginblock div.minipage {
```

```
1078     display: block ;
1079     margin: Opt auto Opt auto ;
1080 }
1081
1082 div.marginblock div.minipage p { font-size: 85%}
1083
1084 div.marginblock br { margin-bottom: 2ex ; }
1085
1086
1087 section.textbody div.footnotes{
1088     margin: 3ex 0em 0ex 0em ;
1089     border-bottom: 2px solid silver ;
1090 }
1091
1092 .footnoteheader {
1093     border-top: 2px solid silver ;
1094     margin-top: 3ex ;
1095     padding-top: 1ex ;
1096     font-weight: bold ;
1097 }
1098
1099 .mpfootnotes {
1100     text-align: left ;
1101     font-size: .85em ;
1102     margin-left: 1em ;
1103     border-top: 1px solid silver ;
1104 }
1105
1106 /* Remove footnote top border in the title page. */
1107 div.titlepage div.mpfootnotes {
1108     border-top: none ;
1109 }
1110
1111
1112
1113 ol {
1114     margin: 1ex 1em 1ex 0em;
1115     line-height: 1.2;
1116 }
1117
1118 ul, body dir, body menu {
1119     margin: 1ex 1em 1ex 0em;
1120     line-height: 1.2;
1121 }
1122
1123 li { margin: 0ex 0em 1ex 0em; }
1124
1125 html {
1126     margin: 0;
1127     padding: 0;
```

```
1128 }
1129
1130 .programlisting {
1131   font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
1132         "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
1133         "Courier New", monospace;
1134   margin: 1ex 0ex 1ex 0ex ;
1135   padding: .5ex 0pt .5ex 0pt ;
1136   overflow-x: auto;
1137 }
1138
1139 section.textbody>pre.programlisting {
1140 border-top: 1px solid silver ;
1141 border-bottom: 1px solid silver ;
1142 }
1143
1144
1145 .inlineprogramlisting {
1146   font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
1147         "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
1148         "Courier New", monospace;
1149   overflow-x: auto;
1150 }
1151
1152 span.listinglabel {
1153   display: inline-block ;
1154   font-size: 70% ;
1155   width: 4em ;
1156   text-align: right ;
1157   margin-right: 2em ;
1158 }
1159
1160 div.abstract {
1161   margin: 2em 5% 2em 5% ;
1162   padding: 1ex 1em 1ex 1em ;
1163 /* font-weight: bold ; */
1164   font-size: 90% ;
1165   text-align: left ;
1166 }
1167
1168 div.abstract dl {line-height:1.5;}
1169 div.abstract dt {color:#304070;}
1170
1171 div.abstracttitle{
1172   font-family: "URW Classico", Optima, "Linux Biolinum O",
1173         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
1174         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
1175   font-weight:bold;
1176   font-size:1.25em;
1177   text-align: center ;
```

```
1178 }
1179
1180 span.abstractrunintitle{
1181     font-family: "URW Classico", Optima, "Linux Biolinum 0",
1182         "Linux Libertine 0", "Liberation Serif", "Nimbus Roman No 9 L",
1183         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
1184     font-weight:bold;
1185 }
1186
1187
1188 .verbatim {
1189     overflow-x: auto ;
1190 }
1191
1192 .alltt {
1193     overflow-x: auto ;
1194 }
1195
1196
1197 .bverbatim {
1198     margin: 1ex 0pt 1ex 0pt ;
1199     padding: .5ex 0pt .5ex 0pt ;
1200     overflow-x: auto ;
1201 }
1202
1203 .lverbatim {
1204     margin: 1ex 0pt 1ex 0pt ;
1205     padding: .5ex 0pt .5ex 0pt ;
1206     overflow-x: auto ;
1207 }
1208
1209 .fancyvrb {
1210     font-size:.85em ;
1211     margin: 3ex 0pt 3ex 0pt
1212 }
1213
1214 .fancyvrblabel {
1215     font-weight:bold;
1216     text-align: center ;
1217 }
1218
1219
1220 .verse {
1221     font-family: "Linux Libertine Mono 0", "Lucida Console",
1222         "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
1223         "Liberation Mono", "FreeMono", "Andale Mono",
1224         "Nimbus Mono L", "Courier New", monospace;
1225     margin-left: 1em ;
1226 }
1227
```

```
1228
1229 div.singlespace { line-height: 1.2 ; }
1230 div.onehalfspace { line-height: 1.5 ; }
1231 div.doublespace { line-height: 2 ; }
1232
1233
1234
1235
1236
1237 /* Minipage environments, vertically aligned to top, center, bottom: */
1238 .minipage, .fminipage, .fcolorminipage {
1239     /* display: inline-block ; */
1240     /* Mini pages which follow each other will be tiled. */
1241     margin: .25em .25em .25em;
1242     padding: .25em .25em .25em;
1243     display: inline-flex;
1244     flex-direction: column ;
1245     overflow: auto;
1246 }
1247
1248 /* Paragraphs in the flexbox did not collapse their margins. */
1249 /* Have not yet researched this. */
1250 .minipage p {margin: .75ex 0em .75ex 0em ;}
1251
1252 .fboxBlock .minipage, .colorbox .minipage, .colorboxBlock .minipage,
1253 .fcolorbox .minipage, .fcolorboxBlock .minipage
1254     {border: none ; background: none;}
1255
1256 .fbox, .fboxBlock { border: 1px solid black ; }
1257
1258 .fbox, .fboxBlock, .fcolorbox, .fcolorboxBlock, .colorbox, .colorboxBlock,
1259 .fminipage, .fcolorminipage
1260     {display: inline-block}
1261
1262 .shadowbox, .shabox {
1263     border: 1px solid black;
1264     box-shadow: 3px 3px 3px #808080 ;
1265     border-radius: 0px ;
1266     padding: .4ex .3em .4ex .3em ;
1267     margin: 0pt .3ex 0pt .3ex ;
1268     display: inline-block ;
1269 }
1270
1271 .doublebox {
1272     border: 3px double black;
1273     border-radius: 0px ;
1274     padding: .4ex .3em .4ex .3em ;
1275     margin: 0pt .3ex 0pt .3ex ;
1276     display: inline-block ;
1277 }
```

```
1278
1279 .ovalbox, .Ovalbox {
1280   border: 1px solid black;
1281   border-radius: 1ex ;
1282   padding: .4ex .3em .4ex .3em ;
1283   margin: 0pt .3ex 0pt .3ex ;
1284   display: inline-block ;
1285 }
1286
1287 .Ovalbox { border-width: 2px ; }
1288
1289 .framebox {
1290   border: 1px solid black;
1291   border-radius: 0px ;
1292   padding: .3ex .2em 0ex .2em ;
1293   margin: 0pt .1ex 0pt .1ex ;
1294   display: inline-block ;
1295 }
1296
1297
1298 .mdframed {
1299 /*   padding: 0ex ; */
1300 /*   border: 1px solid blafck; */
1301 /*   border-radius: 0px ; */
1302   padding: 0ex ;
1303   margin: 3ex 5% 3ex 5% ;
1304 /*   display: inline-block ; */
1305 }
1306
1307 .mdframed p { padding: 0ex .5em 0ex .5em ; }
1308
1309 .mdframed dl { padding: 0ex .5em 0ex .5em ; }
1310
1311 .mdframedtitle {
1312   padding: .5em ;
1313   display: block ;
1314   font-size: 130%
1315 }
1316
1317 .mdframedsubtitle {
1318   padding: 0ex .5em 0ex .5em ;
1319   display: block ;
1320   font-size: 115% ;
1321 }
1322
1323 .mdframedsubsubtitle {
1324   padding: 0ex .5em 0ex .5em ;
1325   display: block ;
1326 }
1327
```

```
1328 .mdtheorem {
1329     padding: 0ex .5em 0ex .5em ;
1330     margin: 3ex 5% 3ex 5% ;
1331 /*   display: inline-block ; */
1332 }
1333
1334
1335 /* framed package */
1336 .framed, pre.boxedverbatim, fcolorbox {
1337     margin: 3ex 0em 3ex 0em ;
1338     border: 1px solid black;
1339     border-radius: 0px ;
1340     padding: .3ex 1em 0ex 1em ;
1341     display: block ;
1342 }
1343
1344 .snugframed {
1345     margin: 3ex 0em 3ex 0em ;
1346     border: 1px solid black;
1347     border-radius: 0px ;
1348     display: block ;
1349 }
1350
1351 .framedleftbar {
1352     margin: 3ex 0em 3ex 0em ;
1353     border-left: 3pt solid black;
1354     border-radius: 0px ;
1355     padding: .3ex .2em .3ex 1em ;
1356     display: block ;
1357 }
1358
1359 .framedtitle {
1360     margin: 0em ;
1361     padding: 0em ;
1362     font-size: 130%
1363 }
1364
1365 .framedtitle p { padding: .3em }
1366
1367
1368
1369 dl {
1370     margin: 1ex 2em 1ex 0em;
1371     line-height: 1.3;
1372 }
1373
1374 dl dt {
1375     margin-top: 1ex;
1376     margin-left: 1em ;
1377     font-weight: bold;
```

```
1378 }
1379
1380 dl dd p { margin-top: 0em; }
1381
1382
1383 nav.toc, nav.lof, nav.lot, nav.lol, nav.lothm {
1384     font-family: "URW Classico", Optima, "Linux Biolinum 0",
1385             "DejaVu Sans", "Bitstream Vera Sans",
1386             Geneva, Verdana, sans-serif ;
1387     margin-bottom: 4ex ;
1388 }
1389
1390 nav.toc p, nav.lof p, nav.lot p, nav.lol p, nav.lothm p {
1391     line-height: 1.2 ;
1392     margin-top:.5ex ;
1393     margin-bottom:.5ex;
1394     font-size: .9em ;
1395 }
1396
1397
1398
1399 img, img.hyperimage, img.borderimage {
1400     max-width: 600px;
1401     border: 1px solid silver;
1402     box-shadow: 3px 3px 3px #808080 ;
1403     padding: .5% ;
1404     margin: .5% ;
1405     background: none ;
1406 }
1407
1408 img.inlineimage{
1409     padding: 0px ;
1410     box-shadow: none ;
1411     border: none ;
1412     background: none ;
1413     margin: 0px ;
1414     display: inline-block ;
1415     border-radius: 0px ;
1416 }
1417
1418 img.logoimage{
1419     max-width: 300px ;
1420     box-shadow: 3px 3px 3px #808080 ;
1421     border: 1px solid black ;
1422     background:none ;
1423     padding:0 ;
1424     margin:.5ex ;
1425     border-radius: 10px ;
1426 }
1427
```

```
1428
1429 .section {
1430 /*
1431     To have each section float relative to each other:
1432 */
1433 /*
1434     display: block ;
1435     float: left ;
1436     position: relative ;
1437     background: white ;
1438     border: 1px solid silver ;
1439     padding: .5em ;
1440 */
1441     margin: 0ex .5em 0ex .5em ;
1442     padding: 0 ;
1443 }
1444
1445
1446 figure {
1447     margin: 3ex auto 3ex auto ;
1448     padding: 1ex 1em 1ex 1em ;
1449     overflow-x: auto ;
1450 }
1451
1452
1453 /* To automatically center images in figures: */
1454 /*
1455 figure img.inlineimage {
1456     margin: 0ex auto 0ex auto ;
1457     display: block ;
1458 }
1459 */
1460
1461 /* To automatically center minipages in figures: */
1462 /*
1463 figure div.minipage, figure div.minipage div.minipage {
1464     margin: 1ex auto 1ex auto ;
1465     display: block ;
1466 }
1467 */
1468
1469 figure div.minipage p { font-size: 85% ; }
1470
1471 figure.subfigure, figure.subtable {
1472     display: inline-block ; margin: 3ex 1em 3ex 1em ;
1473 }
1474
1475 figcaption .minipage { margin:0 ; padding: 0 }
1476
1477 div.minipage figure { border: none ; box-shadow: none ; }
```

```
1478
1479 div.floatrow { text-align: center; }
1480
1481 div.floatrow figure { display: inline-block ; margin: 1ex 2% ; }
1482
1483 div.floatfoot { font-size: .85em ;
1484     border-top: 1px solid silver ; line-height: 1.2 ; }
1485
1486 figcaption , .lstlistingtitle {
1487     font-size: .85em ;
1488     text-align: center ;
1489     font-weight: bold ;
1490     margin-top: 1ex ;
1491     margin-bottom: 1ex ;
1492 }
1493
1494 figure.subfigure figcaption, figure.subtable figcaption {
1495     border-bottom: none ; background: none ;
1496 }
1497
1498 div.nonfloatcaption {
1499     margin: 1ex auto 1ex auto ;
1500     font-size: .85em ;
1501     text-align: center ;
1502     font-weight: bold ;
1503 }
1504
1505 /* For a \RawCaption inside a minipage inside a figure's floatrow: */
1506 figure div.floatrow div.minipage figcaption {
1507     border: none ;
1508     background: none ;
1509 }
1510
1511
1512 table {
1513     margin: 1ex auto 1ex auto ;
1514     border-collapse: separate ;
1515     border-spacing: 0px ;
1516     line-height: 1.3 ;
1517 }
1518
1519 tr.hline td {border-top: 1px solid #808080 ; margin-top: 0ex ;
1520     margin-bottom: 0ex ; } /* for \hline */
1521
1522 tr.tbrule td {border-top: 1px solid black ; margin-top: 0ex ;
1523     margin-bottom: 0ex ; } /* for \toprule, \bottomrule */
1524
1525 td {padding: 1ex .5em 1ex .5em ;}
1526
1527 table td.tdl { text-align: left ; vertical-align: middle ; }
```

```
1528 table td.tdc { text-align: center ; vertical-align: middle ; }
1529 table td.tdat { text-align: center ; vertical-align: middle ; padding: 0px ; margin: 0px ; }
1530 table td.tdbang { text-align: center ; vertical-align: middle ; }
1531 table td.tdr { text-align: right ; vertical-align: middle ; }
1532 table td.tdp { text-align: left ; vertical-align: bottom ; }
1533 table td.tdm { text-align: left ; vertical-align: middle ; }
1534 table td.tdb { text-align: left ; vertical-align: top ; }
1535 table td.tdP { text-align: center ; vertical-align: bottom ; }
1536 table td.tdM { text-align: center ; vertical-align: middle ; }
1537 table td.tdB { text-align: center ; vertical-align: top ; }
1538
1539 table td.tvertbarl { border-left: 1px solid black }
1540 table td.tvertbarr { border-right: 1px solid black }
1541
1542
1543 /* for cmidrules: */
1544 table td.tdrule {
1545     border-top: 1px solid #AOAOAO ;
1546 }
1547
1548 table td.tdrulel {
1549     border-top-left-radius:.5em ;
1550     border-top: 1px solid #AOAOAO ;
1551 }
1552
1553 table td.tdruler {
1554     border-top-right-radius:.5em ;
1555     border-top: 1px solid #AOAOAO ;
1556 }
1557
1558 table td.tdrulelr {
1559     border-top-left-radius:.5em ;
1560     border-top-right-radius:.5em ;
1561     border-top: 1px solid #AOAOAO ;
1562 }
1563
1564
1565 /* Margins of paragraphs inside table cells: */
1566 td.tdp p , td.tdprule p , td.tdP p , td.tdPrule p { padding-top: 1ex ;
1567     padding-bottom: 1ex ; margin: 0ex ; }
1568 td.tdm p , td.tdmrule p , td.tdM p , td.tdMrule p { padding-top: 1ex ;
1569     padding-bottom: 1ex ; margin: 0ex ; }
1570 td.tdb p , td.tdbrule p , td.tdB p , td.tdBrule p { padding-top: 1ex ;
1571     padding-bottom: 1ex ; margin: 0ex ; }
1572
1573 td.tdp , td.tdprule , td.tdP , td.tdPrule
1574     { padding: 0ex .5em 0ex .5em ; }
1575 td.tdm , td.tdmrule , td.tdM , td.tdMrule
1576     { padding: 0ex .5em 0ex .5em ; }
1577 td.tdb , td.tdbrule , td.tdB , td.tdBrule
```

```
1578     { padding: 0ex .5em 0ex .5em ; }
1579
1580
1581 /* table notes: */
1582 .tnotes {
1583     margin: 0ex 5% 1ex 5% ;
1584     padding: 0.5ex 1em 0.5ex 1em;
1585     font-size:.85em;
1586     text-align: left ;
1587 }
1588
1589 .tnotes dl dt p {margin-bottom:0px;}
1590
1591 .tnoteitemheader {margin-right: 1em;}
1592
1593
1594 /* for bigdelim */
1595 .ldelim, .rdelim { font-size: 200% }
1596
1597
1598 /* center, flushleft, flushright environments */
1599 div.center{text-align:center;}
1600 div.center table {margin-left:auto;margin-right:auto;}
1601 div.flushleft{text-align:left;}
1602 div.flushleft table {margin-left:0em ; margin-right:auto;}
1603 div.flushright{text-align:right;}
1604 div.flushright table {margin-left:auto ; margin-right: 0em ;}
1605
1606
1607 /* Fancybox */
1608 div.Btrivlist table tr td { padding: .2ex 0em ; }
1609
1610
1611 /* program listing callouts: */
1612 span.callout {
1613     font-family: "DejaVu Sans", "Bitstream Vera Sans",
1614             Geneva, Verdana, sans-serif ;
1615     border-radius: .5em;
1616     background-color:black;
1617     color:white;
1618     padding:0px .25em 0px .25em;
1619     margin: 0 ;
1620     font-weight: bold;
1621     font-size:.72em ;
1622 }
1623
1624 div.programlisting pre.verbatim span.callout{
1625     font-size: .85em ;
1626 }
1627
```

```
1628
1629
1630
1631
1632 div.published
1633 {
1634     text-align: center ;
1635     font-variant: normal ;
1636     font-style: italic ;
1637     font-size: 1em ;
1638     margin: 3ex 0em 3ex 0em ;
1639 }
1640
1641 div.subtitle
1642 {
1643     text-align: center ;
1644     font-variant: normal ;
1645     font-style: italic ;
1646     font-size: 1.25em ;
1647     margin: 3ex 0em 3ex 0em ;
1648 }
1649
1650 div.subtitle p { margin: 1ex ; }
1651
1652 div.author
1653 {
1654     font-variant: normal ;
1655     font-style: normal ;
1656     font-size: 1em ;
1657     margin: 3ex 0em 3ex 0em ;
1658 }
1659
1660 div.oneauthor {
1661     display: inline-block ;
1662     margin: 3ex 1em 0ex 1em ;
1663 }
1664
1665 /*
1666 div.author table {
1667     margin: 3ex auto 0ex auto ;
1668     background: none ;
1669 }
1670
1671 div.author table tbody tr td { padding: .25ex ; }
1672 */
1673
1674 span.affiliation {font-size: .85em ; font-variant: small-caps; }
1675
1676 div.titledate {
1677     text-align: center ;
```

```
1678     font-size: .85em ;
1679     font-style: italic;
1680     margin: 6ex 0em 6ex 0em ;
1681 }
1682
1683
1684 nav.topnavigation{
1685     text-align: left ;
1686     padding: 0.5ex 1em 0.5ex 1em ;
1687 /*     margin: 2ex 0em 3ex 0em ; */
1688     margin: 0 ;
1689     border-bottom: 1px solid silver ;
1690     border-top: 1px solid silver ;
1691     clear:right ;
1692 }
1693
1694 nav.botnavigation{
1695     text-align: left ;
1696     padding: 0.5ex 1em 0.5ex 1em ;
1697 /*     margin: 3ex 0em 2ex 0em ; */
1698     margin: 0 ;
1699     border-top: 1px solid silver ;
1700     border-bottom: 1px solid silver ;
1701     clear:right ;
1702 }
1703
1704
1705 header{
1706     line-height: 1.2 ;
1707     font-size: 1em ;
1708 /*     border-bottom: 2px solid silver ; */
1709     margin: 0px ;
1710     padding: 0ex 1em 0ex 1em ;
1711     text-align:center ;
1712 }
1713
1714 header p {margin:0ex;padding:4ex 0em 2ex 0em ;text-align:center;}
1715
1716
1717 footer{
1718     font-size: .85em ;
1719     line-height: 1.2 ;
1720     margin-top: 1ex ;
1721     border-top: 2px solid silver ;
1722     padding: 2ex 1em 2ex 1em ;
1723     clear:right ;
1724     text-align:left ;
1725 }
1726
1727
```

```
1728 a.linkhome { font-weight:bold ; font-size: 1em ;}
1729
1730
1731 div.lateximagesource { padding: 0px ; margin: 0px ; display: none; }
1732
1733 img.lateximage{
1734     padding: 0px 0px 0px 0px ;
1735     box-shadow: none ;
1736     border: none ;
1737     background: none ;
1738     margin: 0px 0px -.15ex 0px ;
1739     /* pdfcrop leaves a slight margin, adjust to baseline */
1740     max-width: 100% ;
1741     border-radius: 0ex ;
1742     border: none ;
1743 }
1744
1745
1746
1747 nav.sidetoc {
1748     font-family: "DejaVu Serif", "Bitstream Vera Serif",
1749         "Lucida Bright", Georgia, serif;
1750     float:right ;
1751     width: 20%;
1752     border-left: 1px solid silver;
1753     border-top: 1px solid silver;
1754     border-bottom: 1px solid silver;
1755 /*     border-top: 2px solid #808080 ; */
1756     background: #FAF7F4 ;
1757     padding: 2ex 0em 2ex 1em ;
1758     margin: 0em 0em 2ex 1em ;
1759     font-size:.9em ;
1760     border-radius: 20px 0px 0px 20px ;
1761 }
1762
1763 div.sidetoccontents {
1764 /*     border-top: 1px solid silver ; */
1765     overflow-y: auto ;
1766     width: 100% ;
1767     text-align: left ;
1768 }
1769
1770
1771 nav.sidetoc p {line-height:1.2 ; margin: 1ex .5em 1ex .5em ;
1772     text-indent: 0 ; }
1773
1774 nav.sidetoc p a {color:black ; font-size: .7em ;}
1775
1776 div.sidetoctitle {font-size: 1.2em; font-weight:bold; text-align:center;
1777     border-bottom: 1px solid silver ; }
```

```
1778
1779 nav.sidetoc a:hover {text-decoration: underline ; }
1780
1781
1782
1783 section.textbody { margin: 0ex 1em 0ex 1em ;}
1784
1785
1786 div.multicolsheading { -webkit-column-span: all;
1787     -moz-column-span: all; column-span: all; }
1788 div.multicols { -webkit-columns: 3 380px ;
1789     -moz-columns: 3 380px ; columns: 3 380px ; }
1790 div.multicols p {margin-top: 0ex}
1791
1792
1793
1794 /* Used to support algorithmicx: */
1795 span.floatright { float: right ; }
1796
1797
1798
1799
1800 /* Native LaTeX theorems: */
1801
1802 .theoremcontents { font-style: italic; margin-top: 3ex ; margin-bottom: 3ex ; }
1803 .theoremlabel { font-style: normal; font-weight: bold ; margin-right: .5em ; }
1804
1805
1806 /* theorem, amsthm, and ntheorem packages */
1807
1808 span.theoremheader,
1809 span.theoremheaderplain,
1810 span.theoremheaderdefinition,
1811 span.theoremheaderbreak,
1812 span.theoremheadermarginbreak,
1813 span.theoremheaderchangebreak,
1814 span.theoremheaderchange,
1815 span.theoremheadermargin
1816 {
1817     font-style:normal ; font-weight: bold ; margin-right: 1em ;
1818 }
1819
1820 span.amsthmnameplain,
1821 span.amsthmnamedefinition,
1822 span.amsthmnumberplain,
1823 span.amsthmnumberdefinition
1824 {
1825     font-style:normal ; font-weight: bold ;
1826 }
1827
```

```
1828
1829 span.amsthmnameremark,
1830 span.amsthmnumberremark
1831 {font-style:italic ; font-weight: normal ; }
1832
1833
1834 span.amsthmnoteplain,
1835 span.amsthmnotedefinition
1836 {font-style:normal ;}
1837
1838
1839 span.theoremheaderremark,
1840 span.theoremheaderproof,
1841 span.amsthmproofname
1842 {font-style:italic ; font-weight: normal ; margin-right: 1em ; }
1843
1844 span.theoremheadersc
1845 {
1846     font-style:normal ;
1847     font-variant: small-caps ;
1848     font-weight: normal ;
1849     margin-right: 1em ;
1850 }
1851
1852 .theoremendmark {float:right}
1853
1854 div.amsthmbodyplain, div.theorembodyplain, div.theorembodynonumberplain,
1855 div.theorembodybreak, div.theorembodynonumberbreak,
1856 div.theorembodymarginbreak,
1857 div.theorembodychangebreak,
1858 div.theorembodychange,
1859 div.theorembodymargin
1860 {
1861     font-style:italic;
1862     margin-top: 3ex ; margin-bottom: 3ex ;
1863 }
1864
1865 div.theorembodydefinition, div.theorembodyremark, div.theorembodyproof,
1866 div.theorembodyplainupright, nonumberplainuprightsc,
1867 div.amsthmbodydefinition, div.amsthmbodyremark,
1868 div.amsthmproof
1869 {
1870     font-style: normal ;
1871     margin-top: 3ex ; margin-bottom: 3ex ;
1872 }
1873
1874 span.amsthmnoteremark {}
1875
1876
1877
```

```
1878 /*
1879 For CSS LaTeX and related logos:
1880 Based on:
1881 http://edward.oconnor.cx/2007/08/tex-poshlet
1882 http://nitens.org/taraborelli/texlogo
1883 */
1884
1885 .latexlogofont {
1886     font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
1887                 "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
1888     font-variant: normal ;
1889 }
1890
1891 .latexlogo {
1892     font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
1893                 "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
1894     letter-spacing: .03em ;
1895     font-size: 1.1em;
1896 }
1897
1898 .latexlogo sup {
1899     text-transform: uppercase;
1900     letter-spacing: .03em ;
1901     font-size: 0.85em;
1902     vertical-align: 0.15em;
1903     margin-left: -0.36em;
1904     margin-right: -0.15em;
1905 }
1906
1907 .latexlogo sub {
1908     text-transform: uppercase;
1909     vertical-align: -0.5ex;
1910     margin-left: -0.1667em;
1911     margin-right: -0.125em;
1912     font-size: 1em;
1913 }
1914
1915 .xetexlogo {
1916     font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
1917                 "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
1918     letter-spacing: .03em ;
1919     font-size: 1.1em;
1920 }
1921
1922 /* A smaller gap between Xe and Tex v.s. LaTeX: */
1923 .xetexlogo sub {
1924     text-transform: uppercase;
1925     vertical-align: -0.5ex;
1926     margin-left: -0.0667em;
1927     margin-right: -0.2em;
```

```
1928   font-size: 1em;
1929   letter-spacing: .03em ;
1930 }
1931
1932 /* A large gap between Xe and LaTeX v.s. TeX: */
1933 .xelatexlogo sub {
1934   text-transform: uppercase;
1935   vertical-align: -0.5ex;
1936   margin-left: -0.0667em;
1937   margin-right: -.05em;
1938   font-size: 1em;
1939   letter-spacing: .03em ;
1940 }
1941
1942 .amslogo {
1943   font-family: "TeXGyreChorus", "URW Chancery L",
1944         "Apple Chancery", "ITC Zapf Chancery", "Monotype Corsiva",
1945         "Linux Libertine O", "Nimbus Roman No 9 L", "FreeSerif",
1946         "Hoefler Text", Times, "Times New Roman", serif;
1947   font-style: italic;
1948 }
1949
1950 .lyxlogo {
1951   font-family: "URW Classico", Optima, "Linux Biolinum O",
1952         "DejaVu Sans", "Bitstream Vera Sans", Geneva,
1953         Verdana, sans-serif ;
1954 }
1955
1956
1957
1958
1959 /* Only display top and bottom navigation if a small screen: */
1960 /* Hide the sidetoc if a small screen: */
1961 nav.topnavigation { display:none; }
1962 nav.botnavigation { display:none; }
1963
1964 @media screen and (max-width: 45em) {
1965 /*     nav.sidetoc {display:none;} */
1966     nav.sidetoc {
1967       float: none ;
1968       width: 100% ;
1969       margin: 5ex 0px 5ex 0px ;
1970       padding: 0 ;
1971       border-radius: 0 ;
1972       border-bottom: 1px solid black ;
1973       border-top: 1px solid black ;
1974       box-shadow: none ;
1975     }
1976 /*     nav.topnavigation { display:block } */
1977     nav.botnavigation { display:block }
```

```

1978     .marginpar {
1979         max-width: 100%;
1980         float: none;
1981         display: block ;
1982         margin: 1ex 1em 1ex 1em ;
1983     }
1984 }
1985
1986 @media print {
1987     body {
1988         font-family: "Linux Libertine O",
1989             "DejaVu Serif", "Bitstream Vera Serif",
1990             "Liberation Serif", "Nimbus Roman No 9 L",
1991             "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
1992     }
1993     nav.sidetoc { display:none; }
1994     nav.topnavigation { display: none; }
1995     nav.botnavigation { display: none; }
1996 }
1997
1998 @media handheld {
1999     nav.sidetoc { display:none; }
2000     nav.topnavigation { display:block }
2001     nav.botnavigation { display:block }
2002 }
2003
2004 @media projection {
2005     nav.sidetoc { display:none; }
2006     nav.topnavigation { display:block }
2007     nav.botnavigation { display:block }
2008 }
2009 \end{filecontents*}
2010 % \end{Verbatim}%
2011 \end{warpprint}

```

### 30.5 lwarp\_sagebrush.css

File `lwarp_sagebrush.css` An optional css which may be used for a semi-modern appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

```

2012 \begin{warpprint}
2013 \begin{filecontents*}{lwarp_sagebrush.css}
2014 @import url("lwarp.css") ;
2015
2016

```

```
2017 A:link {color:#105030 ; text-decoration: none ; }
2018 A:visited {color:#705030 ; text-shadow:1px 1px 2px #a0a0a0;}
2019 A:hover {color:#006000 ; text-decoration: underline ; text-shadow:0px 0px 2px #a0a0a0;}
2020 A:active {color:#00C000 ; text-shadow:1px 1px 2px #a0a0a0;}
2021
2022
2023
2024 h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
2025 {
2026     font-family: "URW Classico", Optima, "Linux Biolinum 0",
2027         "Linux Libertine O", "Liberation Serif",
2028         "Nimbus Roman No 9 L", "FreeSerif",
2029         "Hoefler Text", Times, "Times New Roman", serif;
2030     font-variant: small-caps ;
2031     font-weight: normal ;
2032     color: #304070 ;
2033     text-shadow: 2px 2px 3px #808080;
2034 }
2035
2036 h1 { /* title of the entire website, used on each page */
2037     font-variant: small-caps ;
2038     color: #304070 ;
2039     text-shadow: 2px 2px 3px #808080;
2040     background-color: #F7F7F0 ;
2041     background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C4);
2042 }
2043
2044 h1 {
2045     border-bottom: 1px solid #304070;
2046     border-top: 2px solid #304070;
2047 }
2048
2049 h2 {
2050     border-bottom: 1px solid #304070;
2051     border-top: 2px solid #304070;
2052     background-color: #F7F7F0 ;
2053     background-image: linear-gradient(to bottom, #F7F7F0, #DADOC0);
2054 }
2055
2056
2057
2058 div.abstract {
2059     background: #f5f5eb ;
2060     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
2061
2062     border: 1px solid silver;
2063     border-radius: 1em ;
2064 }
2065
2066 div.abstract dl {line-height:1.5;}
```

```
2067 div.abstract dt {color:#304070;}
```

```
2068
```

```
2069 div.abstracttitle{
```

```
2070     font-family: "URW Classico", Optima, "Linux Biolinum 0",
```

```
2071         "Linux Libertine 0", "Liberation Serif", "Nimbus Roman No 9 L",
```

```
2072         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
```

```
2073     font-weight:bold;
```

```
2074     font-variant: small-caps ;
```

```
2075     font-size:1.5em;
```

```
2076     border-bottom: 1px solid silver ;
```

```
2077     color: #304070 ;
```

```
2078     text-align: center ;
```

```
2079     text-shadow: 1px 1px 2px #808080;
```

```
2080 }
```

```
2081
```

```
2082 span.abstractrunintitle{
```

```
2083     font-family: "URW Classico", Optima, "Linux Biolinum 0",
```

```
2084         "Linux Libertine 0", "Liberation Serif", "Nimbus Roman No 9 L",
```

```
2085         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
```

```
2086     font-weight:bold;
```

```
2087 }
```

```
2088
```

```
2089
```

```
2090 div.epigraph {
```

```
2091     background: #f5f5eb ;
```

```
2092     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
```

```
2093
```

```
2094     border: 1px solid silver ;
```

```
2095     border-radius: 1ex ;
```

```
2096     box-shadow: 3px 3px 3px #808080 ;
```

```
2097 }
```

```
2098
```

```
2099
```

```
2100 .example {
```

```
2101     background-color: #f5f5eb ;
```

```
2102     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
```

```
2103
```

```
2104 }
```

```
2105
```

```
2106 div.exampletitle{
```

```
2107     font-family: "URW Classico", Optima, "Linux Biolinum 0",
```

```
2108         "Linux Libertine 0", "Liberation Serif", "Nimbus Roman No 9 L",
```

```
2109         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
```

```
2110     font-weight:bold;
```

```
2111     font-variant: small-caps ;
```

```
2112     border-bottom: 1px solid silver ;
```

```
2113     color: #304070 ;
```

```
2114     text-align: center ;
```

```
2115     text-shadow: 1px 1px 2px #808080;
```

```
2116 }
```

```
2117
2118
2119 .sidebar {
2120     background-color: #f5f5eb ;
2121     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
2122
2123 }
2124
2125 div.sidebartitle{
2126     font-family: "URW Classico", Optima, "Linux Biolinum 0",
2127         "Linux Libertine 0", "Liberation Serif", "Nimbus Roman No 9 L",
2128         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2129     font-weight:bold;
2130     font-variant: small-caps ;
2131     border-bottom: 1px solid silver ;
2132     color: #304070 ;
2133     text-align: center ;
2134     text-shadow: 1px 1px 2px #808080;
2135 }
2136
2137
2138 .fancyvrblabel {
2139     font-family: "URW Classico", Optima, "Linux Biolinum 0",
2140         "Linux Libertine 0", "Liberation Serif", "Nimbus Roman No 9 L",
2141         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2142     font-weight:bold;
2143     font-variant: small-caps ;
2144     font-size: 1.5em ;
2145     color: #304070 ;
2146     text-align: center ;
2147     text-shadow: 1px 1px 2px #808080;
2148 }
2149
2150
2151
2152 div.minipage {
2153     background-color: #eeeeee7 ;
2154     border: 1px solid silver ;
2155     border-radius: 1ex ;
2156 }
2157
2158 section.textbody > div.minipage {
2159     box-shadow: 3px 3px 3px #808080 ;
2160 }
2161
2162 div.fboxBlock div.minipage { box-shadow: none ; }
2163
2164 .framed .minipage , .framedleftbar .minipage {
2165     border: none ;
2166     background: none ;
```

```
2167     padding: 0ex ;
2168     margin: 0ex ;
2169 }
2170
2171 figure.figure .minipage, figcaption .minipage { border: none; }
2172
2173 div.marginblock div.minipage { border: none; }
2174
2175 figure , div.marginblock {
2176     background-color: #eeeeee7 ;
2177     border: 1px solid silver ;
2178     border-radius: 1ex ;
2179     box-shadow: 3px 3px 3px #808080 ;
2180 }
2181
2182 figure figure {
2183     border: 1px solid silver ;
2184     margin: 0em ;
2185     box-shadow: none ;
2186 }
2187
2188 /*
2189 figcaption {
2190     border-top: 1px solid silver ;
2191     border-bottom: 1px solid silver ;
2192     background-color: #e8e8e8 ;
2193 }
2194 */
2195
2196
2197 div.table {
2198     box-shadow: 3px 3px 3px #808080 ;
2199 }
2200
2201 /*
2202 .tnotes {
2203     background: #e8e8e8;
2204     border: 1px solid silver;
2205 }
2206 */
2207
2208
2209 nav.topnavigation{
2210     background-color: #b0b8b0 ;
2211     background-image: linear-gradient(to bottom,#e0e0e0,#b0b8b0) ;
2212 }
2213
2214 nav.botnavigation{
2215     background-color: #b0b8b0 ;
2216     background-image: linear-gradient(to top,#e0e0e0,#b0b8b0) ;
```

```
2217 }
2218
2219
2220
2221 header{
2222     background-color: #F7F7F0 ;
2223     background-image: linear-gradient(to top, #F7F7F0, #b0b8b0);
2224 }
2225
2226 footer{
2227     background-color: #F7F7F0 ;
2228     background-image: linear-gradient(to bottom, #F7F7F0, #b0b8b0);
2229 }
2230
2231
2232
2233 nav.sidetoc {
2234     background-color: #F7F7F0 ;
2235     background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C0);
2236     box-shadow: 3px 3px 3px #808080 ;
2237     border-radius: 0px 0px 0px 20px ;
2238 }
2239
2240 div.sidetoctitle {color: #304070 ; }
2241
2242 nav.sidetoc a:hover {
2243     color:#006000 ;
2244     text-decoration: none ;
2245     text-shadow:0px 0px 2px #a0a0a0;
2246 }
2247
2248
2249 @media screen and (max-width: 45em) {
2250     nav.sidetoc { border-radius: 0 ; }
2251 }
2252
2253
2254 \end{filecontents*}
2255 % \end{Verbatim}%
2256 \end{warpprint}
```

## 30.6 lwarf\_formal.css

File lwarf\_formal.css An optional css which may be used for a more formal appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

```
2257 \begin{warpprint}
2258 \begin{filecontents*}{lwarp_formal.css}
2259 @import url("lwarp.css") ;
2260
2261
2262
2263 A:link {color:#802020 ; text-decoration:none; }
2264 A:visited {color:#802020 ; text-shadow:none ;}
2265 A:hover {color:#400000 ; text-shadow:none ;}
2266 A:active {color:#C00000 ; text-shadow:none ;}
2267
2268
2269 body {
2270     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
2271             "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
2272             "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
2273             "Times New Roman", serif;
2274     background: #fffcf5;
2275 }
2276
2277 span.textrm {
2278     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
2279             "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
2280             "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
2281             "Times New Roman", serif;
2282 }
2283
2284 span.textsf {
2285     font-family: "DejaVu Sans", "Bitstream Vera Sans",
2286             Geneva, Verdana, sans-serif ;
2287 }
2288
2289
2290
2291 h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
2292 {
2293     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
2294             "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
2295             "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
2296             "Times New Roman", serif;
2297     color: #800000 ;
2298     text-shadow: none ;
2299 }
2300
2301 h1, h2 {
2302     background-color: #fffcf5 ;
```

```
2303     background-image: none ;
2304     border-bottom: 1px solid #808080;
2305     border-top: 2px solid #808080;
2306 }
2307
2308 div.abstracttitle {
2309     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
2310         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
2311         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
2312         "Times New Roman", serif;
2313     color: black ;
2314     text-shadow: none ;
2315 }
2316
2317 span.abstractrunintitle {
2318     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
2319         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
2320         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
2321         "Times New Roman", serif;
2322     color: black ;
2323     text-shadow: none ;
2324 }
2325
2326 div.abstract { font-size: 100% }
2327
2328 .sidebar {
2329     background: #fffcf5;
2330     background-image: none ;
2331     margin: 2em 5% 2em 5%;
2332     padding: 0.5em 1em;
2333     border: none ;
2334     border-top : 1px solid silver;
2335     border-bottom : 1px solid silver;
2336     font-size: 90% ;
2337 }
2338
2339 div.sidebartitle{
2340     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
2341         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
2342         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
2343         "Times New Roman", serif;
2344     color: #800000 ;
2345     text-shadow: none ;
2346     border: none ;
2347 }
2348
2349 .example {
2350     background: #fffcf5;
2351     background-image: none ;
2352     margin: 2em 5% 2em 5%;
```

```
2353 padding: 0.5em 1em;
2354 border: none ;
2355 border-top : 1px solid silver;
2356 border-bottom : 1px solid silver;
2357 }
2358
2359 div.exampletitle{
2360     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
2361         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
2362         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
2363         "Times New Roman", serif;
2364     color: #800000 ;
2365     text-shadow: none ;
2366     border: none ;
2367 }
2368
2369 div.fancyvrblabel{
2370     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
2371         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
2372         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
2373         "Times New Roman", serif;
2374     color: #800000 ;
2375     text-shadow: none ;
2376     border: none ;
2377 }
2378
2379
2380
2381 .verse {
2382     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
2383         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
2384         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
2385         "Times New Roman", serif;
2386 }
2387
2388
2389 figure {
2390     margin: 3ex 5% 3ex 5% ;
2391     padding: 1ex 1em 1ex 1em ;
2392     background-color: #ffffcf5 ;
2393     overflow-x: auto ;
2394     border: none ;
2395 /*     border-top: 1px solid silver; */
2396 /*     border-bottom: 1px solid silver; */
2397 }
2398
2399
2400 figcaption , .lstlisting {
2401     border: none ;
2402 /*     border-top: 1px solid silver ; */
```

```
2403 /*      border-bottom: 1px solid silver ; */
2404     background-color: #fffcf5 ;
2405 }
2406
2407 .tnotes {
2408     background: #fffcf5 ;
2409 }
2410
2411 .theorem {
2412     background: none ;
2413 }
2414
2415 .minipage {
2416     background-color: #fffcf5 ;
2417     border: none ;
2418 }
2419
2420 div.floatrow figure { border: none ; }
2421
2422 figure figure { border: none ; }
2423
2424
2425 nav.toc, nav.lof, nav.lot, nav.lol {
2426     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
2427         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
2428         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
2429         "Times New Roman", serif;
2430 }
2431
2432 nav.sidetoc {
2433     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
2434         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
2435         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
2436         "Times New Roman", serif;
2437     background-image: linear-gradient(to bottom, #fffcf5, #C0C0C0);
2438     border-radius: 0px 0px 0px 20px ;
2439 }
2440
2441 div.sidetoctitle{
2442     color: #800000 ;
2443 }
2444
2445 header{
2446     background-color: #e0e0e0 ;
2447     background-image: linear-gradient(to top, #fffcf5, #b0b0b0);
2448     text-align:center ;
2449 }
2450
2451 footer{
2452     background-color: #e0e0e0 ;
```

```
2453     background-image: linear-gradient(to bottom, #ffffcf5, #b0b0b0);
2454     padding: 2ex 1em 2ex 1em ;
2455     clear:right ;
2456     text-align:left ;
2457 }
2458
2459 nav.botnavigation {
2460     background: #dedcd5 ;
2461     border-top: 1px solid black ;
2462 }
2463 \end{filecontents*}
2464 % \end{Verbatim}%
2465 \end{warpprint}
```

### 30.7 sample\_project.css

File `sample_project.css` The project-specific css file. Use with `\CSSFilename`.

If used, this must be present both when compiling the project and also when distributing the HTML files.

```
2466 \begin{warpprint}
2467 \begin{filecontents*}{sample_project.css}
2468 /* ( --- Start of project.css --- ) */
2469 /* A sample project-specific CSS file for lwarp --- ) */
2470
2471 /* Load default lwarp settings: */
2472 @import url("lwarp.css") ;
2473 /* or lwarp_formal.css, lwarp_sagebrush.css */
2474
2475 /* Project-specific CSS setting follow here. */
2476 /* . . . */
2477
2478 /* ( --- End of project.css --- ) */
2479 \end{filecontents*}
2480 % \end{Verbatim}%
2481 \end{warpprint}
```

### 30.8 lwarp.xdy

File `lwarp.xdy` Used to modify the index for lwarp.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

```

2482 \begin{warpprint}
2483 \begin{filecontents*}{lwarp.xdy}
2484 (require "tex/inputenc/latin.xdy")
2485 (merge-rule "\PS *" "Postscript")
2486 (require "texindy.xdy")
2487 (require "page-ranges.xdy")
2488 (require "book-order.xdy")
2489 (markup-locref :open "\hyperindexref{" :close "}")
2490 \end{filecontents*}
2491 % \end{Verbatim} for syntax highlighting
2492 \end{warpprint}

```

### 30.9 lwarp\_mathjax.txt

File `lwarp_mathjax.txt` Used by `lwarp` when using MathJax.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

```

2493 \begin{warpprint}
2494 \begin{filecontents*}{lwarp_mathjax.txt}
2495 <!-- https://groups.google.com/forum/#!topic/
2496   mathjax-users/jUtewUcE2bY -->
2497 <script type="text/x-mathjax-config">
2498 MathJax.Hub.Register.StartupHook("TeX AMSmath Ready",function () {
2499   var seteqsectionDefault = {name: "", num: 0};
2500   var seteqsections = {}, seteqsection = seteqsectionDefault;
2501   var TEX = MathJax.InputJax.TeX, PARSE = TEX.Parse;
2502   var AMS = MathJax.Extension["TeX/AMSmash"];
2503   TEX.Definitions.Add({
2504     macros: {
2505       seteqsection: "mySection",
2506       seteqnumber: "mySetEqNumber"
2507     }
2508   });
2509 
2510   PARSE.Augment({
2511     mySection: function (name) {
2512       seteqsection.num = AMS.number;
2513       var n = this.GetArgument(name);
2514       if (n === "") {
2515         seteqsection = seteqsectionDefault;
2516       } else {
2517         if (!seteqsections["_"+n])
2518           seteqsections["_"+n] = {name:n, num:0};
2519         seteqsection = seteqsections["_"+n];
2520       }
2521     }
2522   });
2523 }
2524 
```

```
2521     AMS.number = seteqsection.num;
2522 },
2523 mySetEqNumber: function (name) {
2524     var n = this.GetArgument(name);
2525     if (!n || !n.match(/^\*[0-9]+\*$/))
2526         n = ""; else n = parseInt(n)-1;
2527     <!-- $ syntax highlighting -->
2528     if (n === "" || n < 1)
2529         TEX.Error
2530         ("Argument to "+name+" should be a positive integer");
2531     AMS.number = n;
2532 }
2533 });
2534 MathJax.Hub.Config({
2535     TeX: {
2536         equationNumbers: {
2537             formatTag: function (n)
2538                 {return "("+(seteqsection.name+"."+n).replace(/\.\./,"")+")"}, 
2539             formatID: function (n) {
2540                 n = (seteqsection.name+'.'+n).replace
2541                     (/[:>&]/g,"").replace(/\.\./,"");
2542                 return 'mjax-eqn-' + n;
2543             }
2544         }
2545     }
2546 });
2547 });
2548 </script>
2549
2550 <!-- http://docs.mathjax.org/en/latest/options/ThirdParty.html -->
2551 <script type="text/x-mathjax-config">
2552     MathJax.Ajax.config.path["Contrib"] =
2553         "https://cdn.mathjax.org/mathjax/contrib";
2554 </script>
2555
2556 <!-- https://github.com/mathjax/MathJax-third-party-extensions/
2557             tree/master/siunitx -->
2558 <script type="text/x-mathjax-config">
2559     MathJax.Hub.Config({
2560         extensions: ["tex2jax.js","[Contrib]/siunitx/siunitx.js"],
2561         jax: ["input/TeX","output/HTML-CSS"],
2562         tex2jax: {inlineMath: [[[$,$],[\\(,\\)]]]},
2563         TeX: {extensions: ["AMSmath.js","AMSSymbols.js", "sinuitx.js"]}
2564     });
2565 </script>
2566
2567 <script type="text/x-mathjax-config">
2568 MathJax.Hub.Config({
2569     TeX: {
2570         equationNumbers: {
```

```
2571     autoNumber: "AMS"
2572   }
2573 }
2574 });
2575 </script>
2576
2577 <!-- Alternative CDN provider: -->
2578 <script type="text/javascript" async
2579 src="https://cdnjs.cloudflare.com/ajax/libs/mathjax/2.7.1/MathJax.js?config=TeX-AMS_HTML-full">
2580 </script>
2581
2582 <!-- No longer supported after April 30, 2017: -->
2583 <!--
2584 <script
2585 src="https://cdn.mathjax.org/mathjax/latest/MathJax.js?config=TeX-AMS_HTML-full">
2586 </script>
2587 -->
2588
2589 \end{filecontents*}
2590 % \end{Verbatim}%
2591 \end{warpprint}
```

## 30.10 lwarpmk option

The following is only generated if the `lwarpmk` option was given to `l warp`.

```
2592 \begin{LWR@createlwarpmk}
```

Prog `lwarpmk` Creates a local copy of `lwarpmk`:

```
2593 \begin{filecontents*}{lwarpmk.lua}
2594 #!/usr/bin/env texlua
2595
2596 -- Copyright 2016-2017 Brian Dunn
2597
2598 -- Print the usage of the lwarpmk command:
2599
2600 printversion = "v0.41"
2601
2602 function printhelp ()
2603 print ("lwarpmk: Use lwarpmk -h or lwarpmk --help for help." );
2604 end
2605
2606 function printusage ()
2607 print ( [[
2608
2609 lwarpmk print [project]: Compile the print version if necessary.
```

```
2610 lwarpmk print1 [project]: Forced single compile of the print version.
2611 lwarpmk printindex [project]: Process the index for the print version.
2612 lwarpmk printglossary [project]: Process the glossary for the print version.
2613 lwarpmk html [project]: Compile the HTML version if necessary.
2614 lwarpmk html1 [project]: Forced single compile of the HTML version.
2615 lwarpmk htmlindex [project]: Process the index for the html version.
2616 lwarpmk htmlglossary [project]: Process the glossary for the html version.
2617 lwarpmk again [project]: Touch the source code to trigger recompiles.
2618 lwarpmk limages [project]: Process the "lateximages" created by lwarp.sty.
2619 lwarpmk pdftohtml [project]:
2620     For use with latexmk or a Makefile:
2621     Convert project_html.pdf to project_html.html and
2622         individual HTML files.
2623 lwarpmk clean [project]: Remove project.aux, .toc, .lof/t, .idx, .ind, .log, *_html_inc.*., .gl*
2624 lwarpmk cleanall [project]: Remove auxiliary files and also project.pdf, *.html
2625 lwarpmk -h: Print this help message.
2626 lwarpmk --help: Print this help message.
2627
2628 ]] )
2629 printconf ()
2630 end
2631
2632 -- Print the format of the configuration file lwarpmk.conf:
2633
2634 function printconf ()
2635 print ( [[
2636 An example lwarpmk.conf or <project>.lwarpmkconf project file:
2637 --
2638 opsystem = "Unix"    (or "Windows")
2639 latexname = "pdflatex" (or "lualatex", or "xelatex")
2640 sourcename = "projectname" (the source-code filename w/o .tex)
2641 homehtmlfilename = "index" (or perhaps the project name)
2642 htmlfilename = "" (or "projectname" - filename prefix)
2643 latexmk = "false" (or "true" to use latexmk to build PDFs)
2644 languge = "english" (use a language supported by xindy)
2645 xdyfile = "lwarp.xdy" (or a custom file based on lwarp.xdy)
2646 --
2647 Filenames must contain only letters, numbers, underscore, or dash.
2648 Values must be in "quotes".
2649
2650 ]] );
2651 end
2652
2653
2654 -- Split one large sourcefile into a number of files,
2655 -- starting with destfile.
2656 -- The file is split at each occurance of <!--|Start file|newfilename|*
2657
2658 function splitfile (destfile,sourcefile)
2659 print ("lwarpmk: Splitting " .. sourcefile .. " into " .. destfile) ;
```

```
2660 local sfile = io.open(sourcefile)
2661 io.output(destfile)
2662 for line in sfile:lines() do
2663 i,j,copen,cstart,newfilename = string.find (line,"(.*)|(.*)|(.*)|") ;
2664 if ( (i~= nil) and (copen == "<!--") and (cstart == "Start file")) then -- split the file
2665 io.output(newfilename) ;
2666 else -- not a splitpoint
2667 io.write (line .. "\n") ;
2668 end
2669 end -- do
2670 io.close(sfile)
2671 end -- function
2672
2673 -- Incorrect value, so print an error and exit.
2674
2675 function cvalueerror ( line, linenum , cvalue )
2676     print ( linenum .. " : " .. line ) ;
2677     print ("lwarpmk: incorrect variable value \".. cvalue .. \" in lwarpmk.conf.\n" ) ;
2678     printconf () ;
2679     os.exit(1) ;
2680 end
2681
2682 -- Load settings from the project's "lwarpmk.conf" file:
2683
2684 function loadconf ()
2685 -- Default configuration filename:
2686 local conffile = "lwarpmk.conf"
2687 -- Optional configuration filename:
2688 if arg[2] ~= nil then conffile = arg[2].."lwarpmkconf" end
2689 -- Default language:
2690 language = "english"
2691 -- Default xdyfile:
2692 xdyfile = "lwarp.xdy"
2693 -- Verify the file exists:
2694 if (lfs.attributes(conffile,"mode")==nil) then -- file not exists
2695 print("lwarpmk: .. conffile .. does not exist.")
2696 print("lwarpmk: .. arg[2] .. does not appear to be a project name.\n")
2697 printhelp () ;
2698 os.exit(1) -- exit the entire lwarpmk script
2699 else -- file exists
2700 -- Read the file:
2701 print ("lwarpmk: Reading " .. conffile ..".")
2702 local cfile = io.open(conffile)
2703 -- Scan each line:
2704 local linenum = 0
2705 for line in cfile:lines() do -- scan lines
2706 linenum = linenum + 1
2707 i,j,cvarname,cvalue = string.find (line,"(%w-%_)*%s*=%s*\"(%w%-_.%)*)\\\"") ;
2708 -- Error if incorrect enclosing characters:
2709 if ( i == nil ) then
```

```
2710 print ( linenum .. " : " .. line ) ;
2711 print ( "lwarpmk: Incorrect entry in " .. conffile .. ".\n" ) ;
2712 printconf () ;
2713 os.exit(1) ;
2714 end
2715 if ( cvarname == "opsystem" ) then
2716     -- Verify choice of opsystem:
2717     if ( (cvalue == "Unix") or (cvalue == "Windows") ) then
2718         opsystem = cvalue
2719     else
2720         cvalueerror ( line, linenum , cvalue )
2721     end
2722 elseif ( cvarname == "latexname" ) then
2723     -- Verify choice of LaTeX compiler:
2724     if (
2725         (cvalue == "pdflatex") or
2726         (cvalue == "xelatex") or
2727         (cvalue == "lualatex")
2728     ) then
2729         latexname = cvalue
2730     else
2731         cvalueerror ( line, linenum , cvalue )
2732     end
2733 elseif ( cvarname == "sourcename" ) then sourcename = cvalue
2734 elseif ( cvarname == "homehtmlfilename" ) then homehtmlfilename = cvalue
2735 elseif ( cvarname == "htmlfilename" ) then htmlfilename = cvalue
2736 elseif ( cvarname == "latexmk" ) then latexmk = cvalue
2737 elseif ( cvarname == "language" ) then language = cvalue
2738 elseif ( cvarname == "xdyfile" ) then xdyfile = cvalue
2739 else
2740 print ( linenum .. " : " .. line ) ;
2741 print ("lwarpmk: Incorrect variable name \"\" .. cvarname .. "\" in " .. conffile .. ".\n" ) ;
2742 printconf () ;
2743 os.exit(1) ;
2744 end
2745 end -- do scan lines
2746 io.close(cfile)
2747 end -- file exists
2748 -- Select some operating-system commands:
2749 if opsystem=="Unix" then -- For Unix / Linux / Mac OS:
2750 rmname = "rm"
2751 mvname = "mv"
2752 touchnamepre = "touch"
2753 touchnamepost = ""
2754 dirslash = "/"
2755 opquote= "\`"
2756 elseif opsystem=="Windows" then -- For Windows
2757 rmname = "DEL"
2758 mvname = "MOVE"
2759 touchnamepre = "COPY /b"
```

```
2760 touchnamepost = "+,,"
2761 dirslash = "\\\""
2762 opquote= "\""
2763 else print ( "lwarpmk: Select Unix or Windows for opsystem" )
2764 end --- for Windows
2765
2766 -- set xindycmd according to pdflatex vs xelatex/lualatex:
2767 if ( latexname == "pdflatex" ) then
2768   xindycmd = "texindy -C utf8"
2769   glossarycmd = "xindy -C utf8"
2770 else
2771   xindycmd = "xindy -M texindy -C utf8"
2772   glossarycmd = "xindy -C utf8"
2773 end
2774
2775 end -- loadconf
2776
2777
2778 function refreshdate ()
2779 os.execute(touchnamepre .. " " .. sourcename .. ".tex" .. touchnamepost)
2780 end
2781
2782
2783 -- Scan the LaTeX log file for the phrase "Rerun to get",
2784 -- indicating that the file should be compiled again.
2785 -- Return true if found.
2786
2787 function reruntoget (filesource)
2788 local fsource = io.open(filesource)
2789 for line in fsource:lines() do
2790 if ( string.find(line,"Rerun to get") ~= nil ) then
2791   io.close(fsource)
2792   return true
2793 end
2794 end
2795 io.close(fsource)
2796 return false
2797 end
2798
2799
2800 -- Compile one time, return true if should compile again.
2801 -- fsuffix is "" for print, "_html" for HTML output.
2802
2803 function onetime (fsuffix)
2804 print("lwarpmk: Compiling with " .. latexname .. " " .. sourcename..fsuffix)
2805 err = os.execute(
2806   "echo " ..
2807   latexname .. " " .. sourcename..fsuffix )
2808 if ( err ~= 0 ) then print ( "lwarpmk: Compile error." ) ; os.exit(1) ; end
2809 return (reruntoget(sourcename .. fsuffix .. ".log") ) ;
```

```
2810 end
2811
2812
2813 -- Compile up to five times.
2814 -- fsuffix is "" for print, "_html" for HTML output
2815
2816 function manytimes (fsuffix)
2817 if onetime(fsuffix) == true then
2818 if onetime(fsuffix) == true then
2819 if onetime(fsuffix) == true then
2820 if onetime(fsuffix) == true then
2821 if onetime(fsuffix) == true then
2822 end end end end end
2823 end
2824
2825 -- Exit if the given file does not exist.
2826
2827 function verifyfileexists (filename)
2828 if (lfs.attributes ( filename , "modification" ) == nil ) then
2829 print ( "lwarpmk: " .. filename .. " not found." ) ;
2830 os.exit (1) ;
2831 end
2832 end
2833
2834
2835 -- Convert <project>_html.pdf into HTML files:
2836
2837 function pdftohtml ()
2838     -- Convert to text:
2839     print ("lwarpmk: Converting " .. sourcename
2840           .. "_html.pdf to " .. sourcename .. "_html.html")
2841     os.execute("pdftotext -enc UTF-8 -nopgbrk -layout "
2842               .. sourcename .. "_html.pdf " .. sourcename .. "_html.html")
2843     -- Split the result into individual HTML files:
2844     splitfile (homehtmlfilename .. ".html" , sourcename .. "_html.html")
2845 end
2846
2847
2848 -- Remove auxiliary files:
2849
2850 function removeauxs ()
2851     os.execute ( rmname .. " " ..
2852                 sourcename .. ".aux " .. sourcename .. "_html.aux " ..
2853                 sourcename .. ".toc " .. sourcename .. "_html.toc " ..
2854                 sourcename .. ".lof " .. sourcename .. "_html.lof " ..
2855                 sourcename .. ".lot " .. sourcename .. "_html.lot " ..
2856                 sourcename .. ".idx " .. sourcename .. "_html.idx " ..
2857                 sourcename .. ".ind " .. sourcename .. "_html.ind " ..
2858                 sourcename .. ".log " .. sourcename .. "_html.log " ..
2859                 sourcename .. ".gl* " .. sourcename .. "_html.gl* " ..
```

```
2860      "*_html_inc.*"
2861      )
2862 end
2863
2864
2865
2866 -- Create lateximages based on lateximages.txt:
2867 function createlateximages ()
2868 print ("lwarpmk: Creating lateximages.")
2869 local limagesfile = io.open("lateximages.txt")
2870 -- Create the lateximages directory, ignore error if already exists
2871 err = os.execute("mkdir lateximages")
2872 -- Scan lateximages.txt
2873 for line in limagesfile:lines() do
2874 -- lwimgpage is the page number in the PDF which has the image
2875 -- lwimgnum is the sequential lateximage number to assign for the image
2876 i,j,lwimgpage,lwimgnum = string.find (line,"|(.*)|(.*)|")
2877 -- For each entry:
2878 if ( (i~=nil) ) then
2879 -- Separate out the image into its own single-page pdf:
2880 err = os.execute(
2881 "pdfseparate -f " .. lwimgpage .. " -l " ..
2882 lwimgpage .. " " .. sourcename .."_html.pdf lateximagetemp-%d.pdf")
2883 -- Crop the image:
2884 err = os.execute(
2885 "pdfcrop --hires lateximagetemp-" .. lwimgpage ..".pdf lateximage-" .. lwimgnum ..".pdf")
2886 if ( err ~= 0 ) then print ( "lwarpmk: File error." ) ; os.exit(1) ; end
2887 -- Convert the image to svg:
2888 err = os.execute(
2889 "pdftocairo -svg lateximage-" .. lwimgnum ..".pdf lateximage-" .. lwimgnum ..".svg")
2890 if ( err ~= 0 ) then print ( "lwarpmk: File error." ) ; os.exit(1) ; end
2891 -- Move the result into lateximages/:
2892 err = os.execute(
2893 mvname .. " lateximage-" .. lwimgnum ..".svg lateximages" .. dirslash )
2894 if ( err ~= 0 ) then print ( "lwarpmk: File error." ) ; os.exit(1) ; end
2895 -- Remove the temporary files:
2896 err = os.execute(
2897 rmname .. " lateximage-" .. lwimgnum ..".pdf lateximagetemp-" .. lwimgpage ..".pdf")
2898 if ( err ~= 0 ) then print ( "lwarpmk: File error." ) ; os.exit(1) ; end
2899 end
2900 end -- do
2901 io.close(limagesfile)
2902 end -- function
2903
2904
2905 -- Use latexmk to compile source and index:
2906 -- fsuffix is "" for print, or "_html" for HTML
2907 function compilelatexmk ( fsuffix )
2908     -- The recorder option is required to detect changes in <project>.tex
2909     -- while we are loading <project>_html.tex.
```

```
2910     err=os.execute ( "latexmk -pdf -dvi- -ps- -recorder "
2911             .. "-e "
2912             .. opquote
2913             .. "$makeindex = q/" -- $
2914             .. xindycmd
2915             .. " -M " .. xdyfile
2916             .. " -L " .. language .. " /"
2917             .. opquote
2918             .. " -pdflatex="" .. latexname .. "%0 %S\" "
2919             .. sourcename..fsuffix ..".tex" ) ;
2920     if ( err ~= 0 ) then print ( "lwarpmk: Compile error." ) ; os.exit(1) ; end
2921 end
2922
2923
2924
2925 -- lwarpmk --version :
2926
2927 if (arg[1] == "--version") then
2928 print ( "lwarpmk: " .. printversion )
2929
2930 else -- not --version
2931
2932 -- print intro:
2933
2934 print ("lwarpmk: " .. printversion .. " Automated make for the LaTeX lwarf package.")
2935
2936 -- lwarpmk print:
2937
2938 if arg[1] == "print" then
2939 loadconf ()
2940 if ( latexmk == "true" ) then
2941     compilelatexmk ("")
2942     print ("lwarpmk: Done.")
2943 else -- not latexmk
2944     verifyfileexists (sourcename .. ".tex") ;
2945     -- See if up to date:
2946     if (
2947         ( lfs.attributes ( sourcename .. ".pdf" , "modification" ) == nil ) or
2948         (
2949             lfs.attributes ( sourcename .. ".tex" , "modification" ) >
2950             lfs.attributes ( sourcename .. ".pdf" , "modification" )
2951         )
2952     ) then
2953         -- Recompile if not yet up to date:
2954         manytimes("")
2955         print ("lwarpmk: Done.") ;
2956     else
2957         print ("lwarpmk: " .. sourcename .. ".pdf is up to date.") ;
2958     end
2959 end -- not latexmk
```

```
2960
2961 elseif arg[1] == "print1" then
2962     loadconf ()
2963     verifyfileexists (sourcename .. ".tex") ;
2964     onetime("")
2965     print ("lwarpmk: Done.") ;
2966
2967 -- lwarp printindex:
2968 -- Compile the index then touch the source
2969 -- to trigger a recompile of the document:
2970
2971 elseif arg[1] == "printindex" then
2972 loadconf ()
2973 print ("lwarpmk: Processing the index.")
2974 os.execute(
2975     xindycmd
2976     .. " -M " .. xdyfile
2977     .. " -L " .. language
2978     .. " " .. sourcename .. ".idx")
2979 print ("lwarpmk: Forcing an update of " .. sourcename .. ".tex.")
2980 refreshdate ()
2981 print ("lwarpmk: " .. sourcename .. ".tex is ready to be recompiled.")
2982 print ("lwarpmk: Done.")
2983
2984 -- lwarp printglossary:
2985 -- Compile the glossary then touch the source
2986 -- to trigger a recompile of the document:
2987
2988 elseif arg[1] == "printglossary" then
2989 loadconf ()
2990 print ("lwarpmk: Processing the glossary.")
2991
2992 os.execute(glossarycmd .. " -L " .. language .. " -I xindy -M " .. sourcename ..
2993     " -t " .. sourcename .. ".glg -o " .. sourcename .. ".gls"
2994     .. sourcename .. ".glo")
2995 print ("lwarpmk: Forcing an update of " .. sourcename .. ".tex.")
2996 refreshdate ()
2997 print ("lwarpmk: " .. sourcename .. ".tex is ready to be recompiled.")
2998 print ("lwarpmk: Done.")
2999
3000 -- lwarpmk html:
3001
3002 elseif arg[1] == "html" then
3003 loadconf ()
3004 if ( latexmk == "true" ) then
3005     compilelatexmk ("_html")
3006     pdftohtml ()
3007     print ("lwarpmk: Done.")
3008 else -- not latexmk
3009     verifyfileexists ( sourcename .. ".tex" ) ;
```

```
3010    -- See if exists and is up to date:
3011    if (
3012        ( lfs.attributes ( homehtmlfilename .. ".html" , "modification" ) == nil ) or
3013        (
3014            lfs.attributes ( sourcename .. ".tex" , "modification" ) >
3015            lfs.attributes ( homehtmlfilename .. ".html" , "modification" )
3016        )
3017    ) then
3018        -- Recompile if not yet up to date:
3019        manytimes("_html")
3020        pdftohtml ()
3021        print ("lwarpmk: Done.")
3022    else
3023        print ("lwarpmk: " .. homehtmlfilename .. ".html is up to date.")
3024    end
3025 end -- not latexmk
3026
3027 elseif arg[1] == "html1" then
3028     loadconf ()
3029     verifyfileexists ( sourcename .. ".tex" ) ;
3030     onetime("_html")
3031     pdftohtml ()
3032     print ("lwarpmk: Done.")
3033
3034 elseif arg[1] == "pdftohtml" then
3035     loadconf ()
3036     pdftohtml ()
3037
3038 -- lwarpmk htmlindex:
3039 -- Compile the index then touch the source
3040 -- to trigger a recompile of the document:
3041
3042 elseif arg[1] == "htmlindex" then
3043 loadconf ()
3044 print ("lwarpmk: Processing the index.")
3045 os.execute(
3046     xindycmd
3047     .. " -M " .. xdyfile
3048     .. " -L " .. language
3049     .. " " .. sourcename .. "_html.idx"
3050 )
3051 print ("lwarpmk: Forcing an update of " .. sourcename .. ".tex.")
3052 refreshdate ()
3053 print ("lwarpmk: " .. sourcename .. ".tex is ready to be recompiled.")
3054 print ("lwarpmk: Done.")
3055
3056 -- lwarpmk htmlglossary:
3057 -- Compile the glossary then touch the source
3058 -- to trigger a recompile of the document:
3059
```

```
3060 elseif arg[1] == "htmlglossary" then
3061 loadconf ()
3062 print ("lwarfpmk: Processing the glossary.")
3063
3064 os.execute(glossarycmd .. " -L " .. language .. " -I xindy -M " ..sourcename ..
3065     "_html -t " .. sourcename .. "_html.glg -o " ..sourcename ..
3066     "_html.gls " ..sourcename .. "_html.glo")
3067
3068 print ("lwarfpmk: Forcing an update of " .. sourcename ..".tex.")
3069 refreshdate ()
3070 print ("lwarfpmk: " .. sourcename ..".tex is ready to be recompiled.")
3071 print ("lwarfpmk: Done.")
3072
3073 -- lwarfpmk limages:
3074 -- Scan the lateximages.txt file to create lateximages,
3075 -- then touch the source to trigger a recompile.
3076
3077 elseif arg[1] == "limages" then
3078 loadconf ()
3079 print ("lwarfpmk: Processing images.")
3080 createlateximages ()
3081 print ("lwarfpmk: Forcing an update of " .. sourcename ..".tex.")
3082 refreshdate ()
3083 print ("lwarfpmk: " .. sourcename ..".tex is ready to be recompiled.")
3084 print ("lwarfpmk: Done.")
3085
3086 -- lwarfpmk again:
3087 -- Touch the source to trigger a recompile.
3088
3089 elseif arg[1] == "again" then
3090 loadconf ()
3091 print ("lwarfpmk: Forcing an update of " .. sourcename ..".tex.")
3092 refreshdate ()
3093 print ("lwarfpmk: " .. sourcename ..".tex is ready to be recompiled.")
3094 print ("lwarfpmk: Done.")
3095
3096 -- lwarfpmk clean:
3097 -- Remove project.aux, .toc, .lof, .lot, .idx, .ind, .log, *_html_inc.*., .gl*
3098
3099 elseif arg[1] == "clean" then
3100 loadconf ()
3101 removeaux ()
3102 print ("lwarfpmk: Done.")
3103
3104 -- lwarfpmk cleanall
3105 -- Remove project.aux, .toc, .lof, .lot, .idx, .ind, .log, *_html_inc.*., .gl*
3106 -- and also project.pdf, *.html
3107
3108 elseif arg[1] == "cleanall" then
3109 loadconf ()
```

```

3110 removeaux ()
3111 os.execute ( rmname .. " " ..
3112     sourcename .. ".pdf" .. sourcename .. "_html.pdf" ..
3113     "*.html"
3114     )
3115 print ("lwarpmk: Done.")
3116
3117 -- lwarpmk with no argument :
3118
3119 elseif (arg[1] == nil) then
3120 printhelp ()
3121
3122 -- lwarpmk -h or lwarpmk --help :
3123
3124 elseif (arg[1] == "-h" ) or (arg[1] == "--help") then
3125 printusage ()
3126
3127 else
3128 print ("lwarpmk: Unknown command \"..arg[1]..\".\n")
3129 printhelp ()
3130 end
3131
3132 end -- not --version
3133 \end{filecontents*}
3134 % \end{Verbatim} for syntax highlighting
3135 \end{LWR@createlwarpmk}

```

## 31 Stacks

**for HTML output:** 3136 \begin{warpHTML}



Stacks are used to remember how to close sections and list items. Before a new section is started, previously nested sections and items must be closed out (un-nested) in proper order. Note that starting a new section may close several levels of previously nested items at the same time. For example, starting a new \section would close any currently open subsection, subsubsection, and paragraph. General environments are not nested on the stack since they have their own close mechanism. List environments are nested, and items inside those environments are nested one level deeper still. List environments may be nested inside other list environments, and list items are nested inside list environments as well. Thus, the stack may have items which are not necessarily in order, since a description may contain an enumerate, for example. Depths to be recorded in \LWR@closedepthone, etc.

### 31.1 Assigning depths

initial depths for empty stack entries:

```
3137 \newcommand*{\LWR@depthnone}{-5}
```

all sectioning depths are deeper than LWR@depthfinished:

```
3138 \newcommand*{\LWR@depthfinished}{-4}
3139 \newcommand*{\LWR@depthpart}{-1}
3140 \newcommand*{\LWR@depthchapter}{0}
3141 \newcommand*{\LWR@depthsection}{1}
3142 \newcommand*{\LWR@depthsubsection}{2}
3143 \newcommand*{\LWR@depthsubsubsection}{3}
3144 \newcommand*{\LWR@depthparagraph}{4}
3145 \newcommand*{\LWR@depthsubparagraph}{5}
```

used by \itemize, \enumerate, \description:

```
3146 \newcommand*{\LWR@depthlist}{6}
```

used by \item:

```
3147 \newcommand*{\LWR@depthlistitem}{7}
```

### 31.2 Closing actions

A stack to record the action to take to close each nesting level: Add more levels of stack if necessary for a very deeply nested document, adding to \pushclose and \popclose as well.

```
3148 \newcommand*{\LWR@closeone}{}% top of the stack
3149 \newcommand*{\LWR@closetwo}{}
3150 \newcommand*{\LWR@closethree}{}
3151 \newcommand*{\LWR@closefour}{}
3152 \newcommand*{\LWR@closefive}{}
3153 \newcommand*{\LWR@closesix}{}
3154 \newcommand*{\LWR@closeseven}{}
3155 \newcommand*{\LWR@closeeight}{}
3156 \newcommand*{\LWR@closenine}{}
3157 \newcommand*{\LWR@closeten}{}
3158 \newcommand*{\LWR@closeeleven}{}
3159 \newcommand*{\LWR@closetwelve}{}
```

### 31.3 Closing depths

A stack to record the depth of each level:

-  Note that nested L<sup>A</sup>T<sub>E</sub>X structures may push depths which are non-sequential.

*Ex:*

---

```
\begin{itemize}
  \item{A}
    \begin{description}
      \item{B}
    \end{description}
\end{itemize}
```

---

```
3160 \newcommand*{\LWR@closedepthonen}{\LWR@depthnone}%
3161 \newcommand*{\LWR@closedepthtwo}{\LWR@depthnone}
3162 \newcommand*{\LWR@closedepththree}{\LWR@depthnone}
3163 \newcommand*{\LWR@closedepthfour}{\LWR@depthnone}
3164 \newcommand*{\LWR@closedepthfive}{\LWR@depthnone}
3165 \newcommand*{\LWR@closedepthsix}{\LWR@depthnone}
3166 \newcommand*{\LWR@closedepthseven}{\LWR@depthnone}
3167 \newcommand*{\LWR@closedeptheight}{\LWR@depthnone}
3168 \newcommand*{\LWR@closedepthnine}{\LWR@depthnone}
3169 \newcommand*{\LWR@closedepthten}{\LWR@depthnone}
3170 \newcommand*{\LWR@closedeptheleven}{\LWR@depthnone}
3171 \newcommand*{\LWR@closedepthtwelve}{\LWR@depthnone}
```

### 31.4 Pushing and popping the stack

```
\pushclose {<action>} {<depth>}
```

Pushes one return action and its L<sup>A</sup>T<sub>E</sub>X depth onto the stacks.

```
3172 \NewDocumentCommand{\pushclose}{m m}
3173 {
3174 \let\LWR@closedetwelve\LWR@closeeleven
3175 \let\LWR@closeeleven\LWR@closeten
3176 \let\LWR@closeten\LWR@closenine
3177 \let\LWR@closenine\LWR@closeeight
3178 \let\LWR@closeeight\LWR@closeseven
3179 \let\LWR@closeseven\LWR@closesix
3180 \let\LWR@closesix\LWR@closefive
3181 \let\LWR@closefive\LWR@closefour
```

---

```

3182 \let\LWR@closefour\LWR@closethree
3183 \let\LWR@closethree\LWR@closetwo
3184 \let\LWR@closetwo\LWR@closeone
3185 \let\LWR@closeone#1
3186 \let\LWR@closedepthtwelve\LWR@closedeptheleven
3187 \let\LWR@closedepthelevel\LWR@closedepthten
3188 \let\LWR@closedepthten\LWR@closedepthnine
3189 \let\LWR@closedepthnine\LWR@closedeptheight
3190 \let\LWR@closedeptheight\LWR@closedepthseven
3191 \let\LWR@closedepthseven\LWR@closedepthsix
3192 \let\LWR@closedepthsix\LWR@closedepthfive
3193 \let\LWR@closedepthfive\LWR@closedepthfour
3194 \let\LWR@closedepthfour\LWR@closedepththree
3195 \let\LWR@closedepththree\LWR@closedepthtwo
3196 \let\LWR@closedepthtwo\LWR@closedepthonne
3197 \let\LWR@closedepthonne#2
3198 }

```

`\popclose` Pops one action and its depth off the stacks.

```

3199 \newcommand*{\popclose}
3200 {
3201 \let\LWR@closeone\LWR@closetwo
3202 \let\LWR@closetwo\LWR@closethree
3203 \let\LWR@closethree\LWR@closefour
3204 \let\LWR@closefour\LWR@closefive
3205 \let\LWR@closefive\LWR@closesix
3206 \let\LWR@closesix\LWR@closeseven
3207 \let\LWR@closeseven\LWR@closeeight
3208 \let\LWR@closeeight\LWR@closenine
3209 \let\LWR@closenine\LWR@closeten
3210 \let\LWR@closeten\LWR@closeeleven
3211 \let\LWR@closeeleven\LWR@closetwelve
3212 \let\LWR@closedepthonne\LWR@closedepthtwo
3213 \let\LWR@closedepthtwo\LWR@closedepththree
3214 \let\LWR@closedepththree\LWR@closedepthfour
3215 \let\LWR@closedepthfour\LWR@closedepthfive
3216 \let\LWR@closedepthfive\LWR@closedepthsix
3217 \let\LWR@closedepthsix\LWR@closedepthseven
3218 \let\LWR@closedepthseven\LWR@closedeptheight
3219 \let\LWR@closedeptheight\LWR@closedepthnine
3220 \let\LWR@closedepthnine\LWR@closedepthten
3221 \let\LWR@closedepthten\LWR@closedeptheleven
3222 \let\LWR@closedeptheleven\LWR@closedepthtwelve
3223 }

3224 \end{warpHTML}

```

## 32 Data arrays

These macros are similar to the arrayjobx package, except that \LWR@setexpparray's argument is expanded only once when assigned.

`name` has no backslash, `index` can be a number or a text name, and an empty `value` must be `\relax` instead of empty.

To assign an empty value:

```
\LWR@setexpparray{name}{index}{}  

for HTML output: 3225 \begin{warpHTML}  

  

\LWR@setexpparray {<name>} {<index>} {<contents>}  

  

3226 \NewDocumentCommand{\LWR@setexpparray}{m m} {%
3227 \ifthenelse{\isempty{#3}}{%
3228 {\csdef{#1#2}{}}
3229 {\expandafter\edef\csname #1#2\endcsname{\expandonce{#3}}}}{%
3230 }  

  

\LWR@getexpparray {<name>} {<index>}  

  

3231 \newcommand*{\LWR@getexpparray}[2]{\csuse{#1#2}}  

  

3232 \end{warpHTML}
```

## 33 HTML entities

**for HTML output:** 3233 \begin{warpHTML}

HTML entities and HTML Unicode entities:

```
3234 \let\LWR@origampersand\&  

  

\HTMLentity {<entitytag>}  

  

3235 \newcommand*{\HTMLentity}[1]{%
3236 % \LWR@traceinfo{\HTMLentity \detokenize{#1}}%
3237 \begingroup%
3238 \LWR@FBcancel%
3239 \LWR@origampersand#1;%
```

```

3240 \endgroup
3241 % \LWR@traceinfo{HTMLentity done}%
3242 }

\HTMLunicode {⟨hex_unicode⟩}

3243 \newcommand*{\HTMLunicode}[1]{\HTMLentity{\#x#1}}

\&

3244 \renewcommand*{\&}{\HTMLentity{amp}}


\textless
\textgreater
3245 \let\LWR@origtextless\textless
3246 \renewcommand*{\textless}{\HTMLentity{lt}}
3247
3248 \let\LWR@origtextgreater\textgreater
3249 \renewcommand*{\textgreater}{\HTMLentity{gt}}


3250 \end{warpHTML}

```

## 34 HTML filename generation

The filename of the homepage is set to `\HomeHTMLfilename.html`. The filenames of additional sections start with `\HTMLfilename`, to which is appended a section number or a simplified section name, depending on `FileSectionNames`.

**for HTML & PRINT:** 3251 `\begin{warpall}`

`\BaseJobname` The `\jobname` of the printed version, even if currently compiling the HTML version. I.e. this is the `\jobname` without `_html` appended. This is used to set `\HomeHTMLfilename` if the user did not provide one.

3252 `\providecommand*{\BaseJobname}{\jobname}`

`\HTMLfilename` The prefix for all generated HTML files other than the home page, defaulting to empty. See section 5.7.

3253 `\providecommand*{\HTMLfilename}{}{}`

\HomeHTMLFilename The filename of the home page, defaulting to the \BaseJobname. See section 5.7.

```
3254 \providecommand*\{\HomeHTMLFilename}{\BaseJobname}
```

\SetHTMLFileName {<number>}

Sets the file number for the next file to be generated. 0 is the home page. Use just before the next sectioning command, and set it to one less than the desired number of the next section. May be used to generate numbered groups of nodes such as 100+ for one chapter, 200+ for another chapter, etc.

```
3255 \newcommand*\{\SetHTMLFileName}[1]{%
3256 \setcounter{LWR@htmlfilename}{#1}%
3257 }
```

Bool FileSectionNames Selects how to create HTML file names.

Defaults to use section names in the filenames.

```
3258 \newbool{FileSectionNames}
3259 \booltrue{FileSectionNames}
```

```
3260 \end{warpall}
```

**for HTML output:** 3261 \begin{warpHTML}

Ctr LWR@htmlfilename Records the number of each HTML file as it is being created. Number 0 is the home page.

```
3262 \newcounter{LWR@htmlfilename}
3263 \setcounter{LWR@htmlfilename}{0}
```

\LWR@htmlsectionfilename {<htmlfilename or name>}

Prints the filename for a given section: \HTMLFilename{}filename/name.html

```
3264 \newcommand*\{\LWR@htmlsectionfilename}[1]{%
3265 \LWR@traceinfo{\LWR@htmlsectionfilename A}%
}
```

Section 0 or empty is given the home filename. The filename must be detokenized for underscores.

```
3266 \LWR@traceinfo{about to assign temp}%
3267 \edef\LWR@tempone{\#1}%
3268 \LWR@traceinfo{about to compare with ??}%
3269 \ifthenelse{\equal{\LWR@tempone}{??}}{%
```

```

3270 {\LWR@traceinfo{found ??}}%
3271 {\LWR@traceinfo{not found ??}}%
3272 \LWR@traceinfo{about to compare with zero or empty}%
3273 \ifthenelse{%
3274     \equal{\LWR@tempone}{0}%
3275     \OR \equal{\LWR@tempone}{}%
3276     \OR \equal{\LWR@tempone}{??}%
3277 }%
3278 {%
3279     \LWR@traceinfo{LWR@htmlsectionfilename B \HomeHTMLFilename.html}%
3280     \HomeHTMLFilename.html%
3281 }%

```

For a  $\text{\LaTeX}$  section named “Index” or “index” without a prefix, create a filename with a leading underscore to avoid colliding with the HTML filename `index.html`:

```

3282 {%
3283     \LWR@traceinfo{LWR@htmlsectionfilename C \LWR@tempone}%
3284     \ifthenelse{%
3285         \equal{\HTMLFilename}{} \AND
3286         \equal{\LWR@tempone}{Index} \OR
3287         \equal{\LWR@tempone}{index}%
3288     }%
3289     {%
3290         \LWR@traceinfo{prefixing the index name with an underscore.}%
3291         \_#1.html%
3292     }%

```

Otherwise, create a filename with the chosen prefix:

```

3293     {\HTMLFilename#1.html}%
3294 }%
3295 \LWR@traceinfo{LWR@htmlsectionfilename Z}%
3296 }

```

`\LWR@htmlrefsectionfilename {<label>}`

Prints the filename for the given label

```

3297 \newcommand*{\LWR@htmlrefsectionfilename}[1]{%
3298 \LWR@traceinfo{LWR@htmlrefsectionfilename A: !#1!}%
3299 \LWR@htmlsectionfilename{\LWR@htmlfileref{#1}}%
3300 \LWR@traceinfo{LWR@htmlrefsectionfilename B}%
3301 }%
3302 \end{warpHTML}

```

## 35 Homepage link

**for HTML output:** 3303 \begin{warpHTML}

\LinkHome \LinkHome may be used wherever you wish to place a link back to the homepage.  
The filename must be detokenized for underscores.

```
3304 \newcommand*\{\LinkHome\}{%
3305 \LWR@subhyperrefclass{%
3306 \HomeHTMLfilename.html}%
3307 {Home}{linkhome}%
3308 }
```

\LWR@topnavigation Creates a link to the homepage at the top of the page for use when the window is too narrow for the sidetoc.

```
3309 \newcommand*\{\LWR@topnavigation\}{%
3310 \LWR@htmlelementclassline{nav}{topnavigation}\{\LinkHome\}%
3311 }
```

\LWR@botnavigation Creates a link to the homepage at the bottom of the page for use when the window is too narrow for the sidetoc.

```
3312 \newcommand*\{\LWR@botnavigation\}{%
3313 \LWR@htmlelementclassline{nav}{botnavigation}\{\LinkHome\}%
3314 }
```

```
3315 \end{warpHTML}
```

## 36 \PrintStack diagnostic tool



Diagnostics tool: Prints the L<sup>A</sup>T<sub>E</sub>X nesting depth values for the stack levels. Must have \LWR@startpars active while printing the stack, so \PrintStack may be called from anywhere in the normal text flow.

**for HTML output:** 3316 \begin{warpHTML}

\PrintStack Prints the closeddepth stack.

```
3317 \newcommand*\{\PrintStack\}{%
3318 \LWR@startpars
3319 \LWR@closedepthone{} \LWR@closedepthtwo{} \LWR@closedepththree{}}
```

---

```

3320 \LWR@closedepthfour{} \LWR@closedepthfive{} \LWR@closedepthsix{}
3321 \LWR@closedepthseven{} \LWR@closedeptheight{} \LWR@closedepthnine{}
3322 \LWR@closedepthten{} \LWR@closedeptheleven{} \LWR@closedepthtwelve{}
3323 }

3324 \end{warpHTML}

```

## 37 Closing stack levels

**for HTML output:** 3325 \begin{warpHTML}

Close one nested level:

```

3326 \newcommand*{\LWR@closeoneprevious}{%
3327
3328 \LWR@closeone{}%
3329
3330 \popclose{}%
3331 }

```

\LWR@closeprevious {*depth*} Close everything up to the given depth:

```
3332 \newcommand*{\LWR@closeprevious}[1]{
```

Close any pending paragraph:

```
3333 \LWR@stoppars
```

Close anything nested deeper than the desired depth:

```

3334 \whiledo{\not{(\LWR@closedepthonenumber<#1)}}{\LWR@closeoneprevious}
3335 }

```

```
3336 \end{warpHTML}
```

## 38 PDF pages and styles

**for HTML output:** 3337 \begin{warpHTML}

\LWR@forcenewpage New PDF page a before major environment.

This is used just before major environments, such as `verse`. Reduces the chance of an environment overflowing the HTML PDF output page.

```
3338 \newcommand{\LWR@forcenewpage}{%
3339 \LWR@stoppars\LWR@orignewpage\LWR@startpars%
3340 }
```

`\pagestyle`, etc. are nullified for HTML output.

```
\pagestyle {\langle style\rangle}
3341 \renewcommand*{\pagestyle}[1]{}
```

```
\thispagestyle {\langle style\rangle}
3342 \renewcommand*{\thispagestyle}[1]{}
```

```
\markboth {\langle left\rangle} {\langle right\rangle}
3343 \renewcommand*{\markboth}[2]{}
```

```
\markright {\langle right\rangle}
3344 \renewcommand*{\markright}[1]{}
```

```
\raggedbottom
3345 \renewcommand*{\raggedbottom}{}{}
```

```
\flushbottom
3346 \renewcommand*{\flushbottom}{}{}
```

```
\sloppy
3347 \renewcommand*{\sloppy}{}{}
```

```
\fussy
3348 \renewcommand*{\fussy}{}{}
```

```
\pagenumbering {\langle commands\rangle}
3349 \renewcommand*{\pagenumbering}[1]{}
```

---

3350 \end{warpHTML}

## 39 HTML tags, spans, divs, elements

for HTML output: 3351 \begin{warpHTML}

### 39.1 Mapping L<sup>A</sup>T<sub>E</sub>X Sections to HTML Sections

```
3352 \newcommand*{\LWR@tagpart}{h2}
3353 \newcommand*{\LWR@tagpartend}{/h2}
3354 \newcommand*{\LWR@tagchapter}{h3}
3355 \newcommand*{\LWR@tagchapterend}{/h3}
3356 \newcommand*{\LWR@tagsection}{h4}
3357 \newcommand*{\LWR@tagsectionend}{/h4}
3358 \newcommand*{\LWR@tagsubsection}{h5}
3359 \newcommand*{\LWR@tagsubsectionend}{/h5}
3360 \newcommand*{\LWR@tagsubsubsection}{h6}
3361 \newcommand*{\LWR@tagsubsubsubsection}{/h6}
3362 \newcommand*{\LWR@tagparagraph}{span class="paragraph"{}}
3363 \newcommand*{\LWR@tagparagraphend}{/span}
3364 \newcommand*{\LWR@tag subparagraph}{span class="subparagraph"{}}
3365 \newcommand*{\LWR@tag subparagraphend}{/span}
3366
3367 \newcommand*{\LWR@tag regular paragraph}{p}
```

### 39.2 Babel-French

Adjust babel-french for HTML spaces. So far, this only works for pdflatex and xelatex.

(Based on original code by DANIEL FLIPO.)

```
3368 \providecommand*{\LWR@FBcancel}{}%
3369
3370 \AtBeginDocument{%
3371   @ifundefined{frenchbsetup}{%
3372     {}%
3373   {}%
3374     \frenchbsetup{FrenchFootnotes=false}}%
3375 %
3376   \LetLtxMacro{\LWR@FBcancel}{\NoAutoSpacing}%
3377   \renewcommand*{\FBcolonspace}{%
```

```

3378     \begingroup%
3379     \LWR@FBcancel%
3380     \LWR@origampersand{}nbsp;%
3381     \endgroup%
3382   }%
3383   \renewcommand*{\FBthinspace}{%
3384     \begingroup%
3385     \LWR@FBcancel%
3386     \LWR@origampersand\x202f;% ,
3387     \endgroup%
3388   }%
3389   \renewcommand*{\FBguillspace}{%
3390     \begingroup%
3391     \LWR@FBcancel%
3392     \LWR@origampersand{}nbsp;% ~, for \og xyz \fg{}%
3393     \endgroup%
3394   }%
3395   \DeclareDocumentCommand{\FBmedkern}{}{%
3396     \begingroup%
3397     \LWR@FBcancel%
3398     \LWR@origampersand\x202f;% ,
3399     \endgroup%
3400   }%
3401   \DeclareDocumentCommand{\FBthickkern}{}{%
3402     \begingroup%
3403     \LWR@FBcancel%
3404     \LWR@origampersand{}nbsp;% ~
3405     \endgroup%
3406   }%
3407   \renewcommand*{\~}{\HTMLentity{nbsp}}% was overwritten by babel-french
3408   \ifFBunicode%
3409   \else%
3410     \DeclareTextSymbol{\FBtextellipsis}{LY1}{133}%
3411     \DeclareTextCommandDefault{\FBtextellipsis}{\textellipsis\xspace}%
3412   \fi%
3413 }%
3414 }

```

### 39.3 HTML tags

\LWR@htmlltagc {\langle tag \rangle} Break ligatures and use upright apostrophes in HTML tags.

\protect is in case the tag appears in TOC, LOF, LOT.

```

3415 \newcommand*{\LWR@htmlltagc}[1]{%
3416 {%
3417 % \LWR@traceinfo{\LWR@htmlltagc \detokenize{#1}}%

```

```

3418 \begingroup%
3419 \LWR@FBcancel%
3420 \ifmmode\else\protect\LWR@origttfamily\fi%
3421 \protect\LWR@origtextless#1\protect\LWR@origtextgreater%
3422 \endgroup%
3423 }%
3424 }

```

Env `LWR@nestspan` Disable `minipage`, `\parbox`, and HTML `<div>`s inside a `<span>`.

- ⚠ `\begin{LWR@nestspan}` must follow the opening `<span>` tag to allow a paragraph to start if the span is at the beginning of a new paragraph.
- ⚠ `\end{LWR@nestspan}` must follow the `</span>` or a `<p>` may appear inside the span.

```

3425 \newcommand*\LWR@nestspanitem{%
3426 \if@newlist\else{\LWR@htmltagc{br /}}\fi%
3427 \LWR@origitem%
3428 }
3429
3430 \newenvironment*{LWR@nestspan}
3431 {%
3432 \LWR@traceinfo{LWR@nestspan}%
3433 \ifthenelse{\cnttest{\value{LWR@lateximagedepth}}{>}{0}}{%
3434 {%
3435 \LWR@traceinfo{LWR@nestspan: inside a lateximage}%
3436 }%
3437 {%
3438 \LWR@traceinfo{LWR@nestspan: NOT inside a lateximage}%
3439 \addtocounter{LWR@spandepth}{1}%
3440 \RenewDocumentEnvironment{minipage}{O{t} o O{t} m}{\{}{\}}
3441 \RenewDocumentEnvironment{BlockClass}{o m}{\{}{\}}
3442 \renewcommand{\BlockClassSingle}[2]{##2}%
3443 \renewcommand{\LWR@forcenewpage}{}%
3444 \renewcommand{\LWR@itemizestart}{%
3445 \let\item\LWR@nestspanitem%
3446 }%
3447 \renewcommand{\LWR@itemizeend}{}%
3448 \renewcommand{\LWR@enumeratestart}{%
3449 \let\item\LWR@nestspanitem%
3450 }%
3451 \renewcommand{\LWR@enumerateend}{}%
3452 \renewcommand{\LWR@descriptionstart}{%
3453 \let\item\LWR@nestspanitem%
3454 }%
3455 \renewcommand{\LWR@descriptionend}{}%
3456 }%
3457 }%
3458 {%

```

```

3459 \ifthenelse{\cnttest{\value{LWR@lateximagedepth}}{>}{0}}{%
3460 {}%
3461 {\addtocounter{LWR@spandepth}{-1}}%
3462 \LWR@traceinfo{LWR@nestspan: done}%
3463 }%
3464
3465 \AfterEndEnvironment{LWR@nestspan}{\global\let\par\LWR@closeparagraph}

```

\LWR@htmlspan {⟨tag⟩} {⟨text⟩}

- ⚠ \LWR@spandepth is used to ensure that paragraph tags are not generated inside a span. The exact sequence of when to add and subtract the counter is important to correctly handle the paragraph tags before and after the span.

```

3466 \NewDocumentCommand{\LWR@htmlspan}{m +m}{%
3467 \LWR@ensuredoingapar%
3468 \LWR@htmlltagc{#1}%
3469 \begin{LWR@nestspan}%
3470 #2%
3471 \LWR@htmlltagc{/#1}%
3472 \end{LWR@nestspan}%
3473 }

```

\LWR@htmlspanclass [⟨style⟩] {⟨class⟩} {⟨text⟩}

```

3474 \NewDocumentCommand{\LWR@htmlspanclass}{o m +m}{%
3475 \LWR@traceinfo{LWR@htmlspanclass #2}%
3476 \LWR@ensuredoingapar%
3477 \LWR@subhtmlelementclass{span}[#1]{#2}%
3478 \begin{LWR@nestspan}%
3479 #3%
3480 \LWR@htmlltagc{/span}%
3481 \LWR@traceinfo{LWR@htmlspanclass done}%
3482 \end{LWR@nestspan}%
3483 }

```

\LWR@htmlltag {⟨tag⟩}

Print an HTML tag: <tag>

```

3484 \newcommand*{\LWR@htmlltagb}[1]{%
3485 \LWR@htmlltagc{#1}%
3486 \endgroup%
3487 }%
3488
3489 \newcommand*{\LWR@htmlltag}{%
3490 \begingroup\catcode`\_=12

```

```
3491 \LWR@htmntagb%
3492 }
```

### 39.4 Block tags and comments

In the following, \origttfamily breaks ligatures, which may not be used for HTML codes:

```
\LWR@htmlopencomment
\LWR@htmlclosecomment
3493 \newcommand*\{\LWR@htmlopencomment\}{%
3494 {%
3495 % \LWR@traceinfo{\LWR@htmlopencomment}%
3496 \begingroup%
3497 \LWR@FBcancel%
3498 \ifmmode\else\protect\LWR@origttfamily\fi%
3499 \LWR@origtextless{}!{-}{-}%
3500 \endgroup%
3501 }%
3502 }
3503
3504 \newcommand*\{\LWR@htmlclosecomment\}{%
3505 {%
3506 % \LWR@traceinfo{\LWR@htmlclosecomment}%
3507 \begingroup%
3508 \LWR@FBcancel%
3509 \ifmmode\else\protect\LWR@origttfamily\fi%
3510 {-}{-}\LWR@origtextgreater{}%
3511 \endgroup%
3512 }%
3513 }

\LWR@htmlcomment {<comment>}
3514 \newcommand{\LWR@htmlcomment}[1]{%
3515 \LWR@htmlopencomment{}%
3516 {%
3517 \LWR@origttfamily% break ligatures
3518 #1%
3519 }%
3520 \LWR@htmlclosecomment{}}

\LWR@htmlblockcomment {<comment>}
```

```

3521 \newcommand{\LWR@htmlblockcommentb}[1]
3522 {\LWR@stopars\LWR@htmlcomment{\#1}\LWR@startpars\endgroup}
3523
3524 \newcommand{\LWR@htmlblockcomment}{%
3525 {%
3526 \begingroup\catcode`\_=12%
3527 \LWR@htmlblockcommentb%
3528 }

```

\LWR@htmlblocktag {*tag*} print a stand-alone HTML tag

```

3529 \newcommand*\{\LWR@htmlblocktag}[1]{%
3530 \LWR@stopars%
3531 \LWR@htmlltag{\#1}%
3532 \LWR@startpars%
3533 }

```

## 39.5 Div class and element class

\LWR@subhtmlelementclass {*element*} [*style*] {*class*}

Factored and reused in several places.

The trailing spaces allow more places for a line break.

```

3534 \NewDocumentCommand{\LWR@subhtmlelementclass}{m o m}{%
3535 \LWR@traceinfo{\LWR@subhtmlelementclass #1 #3}%
3536 \IfValueTF{\#2}{%
3537 {%
3538     \ifthenelse{\equal{\#2}{}}{%
3539         {\LWR@htmlltag{\#1 class="#3"}% empty option
3540         {\LWR@htmlltag{\#1 class="#3" style="#2"}% non-empty option
3541 }% option
3542 {\LWR@htmlltag{\#1 class="#3"}% no option
3543 \LWR@traceinfo{\LWR@subhtmlelementclass done}%
3544 }

```

\LWR@htmlelementclass {*element*} {*class*} [*style*]

```

3545 \NewDocumentCommand{\LWR@htmlelementclass}{m o m}{%
3546 \LWR@stopars%
3547 \LWR@subhtmlelementclass{\#1}[\#2][\#3]%
3548 \LWR@startpars%
3549 }

```

```
\LWR@htmlelementclassend  {\langle element\rangle} {\langle class\rangle}

3550 \newcommand*{\LWR@htmlelementclassend}[2]{%
3551 \LWR@stoppars%
3552 \LWR@htmltag{/\#1}%
3553 \ifbool{HTMLDebugComments}{%
3554     \LWR@htmlcomment{End of #1 ``#2''}%
3555 }{}%
3556 \LWR@startpars%
3557 }

\LWR@htmldivclass  [\langle style\rangle] {\langle class\rangle}

3558 \NewDocumentCommand{\LWR@htmldivclass}{o m}{%
3559 \LWR@htmlelementclass{div}[\#1]{\#2}%
3560 }

\LWR@htmldivclassend  {\langle class\rangle}

3561 \newcommand*{\LWR@htmldivclassend}[1]{%
3562 \LWR@htmlelementclassend{div}{\#1}%
3563 }
```

## 39.6 Single-line elements

A single-line element, without a paragraph tag for the line of text:

```
\LWR@htmlelementclassline  {\langle element\rangle} [\langle style\rangle] {\langle class\rangle} {\langle text\rangle}

3564 \NewDocumentCommand{\LWR@htmlelementclassline}{m o m +m}{%
3565 \LWR@stoppars%
3566 \LWR@subhtmlelementclass{\#1}{\#2}{\#3}%
3567 #4%
3568 \LWR@htmltag{/\#1}%
3569 \LWR@startpars%
3570 }
```

## 39.7 HTML5 semantic elements

```
\LWR@htmlelement  {\langle element\rangle}
```

```

3571 \newcommand*\LWR@htmlelement}[1]{%
3572 \LWR@htmlblocktag{#1}%
3573 }

\LWR@htmlelementend {<element>}

3574 \newcommand*\LWR@htmlelementend}[1]{%
3575 \LWR@stoppars
3576 \LWR@htmlltag{/#1}
3577 \LWR@startpars
3578 }
3579
3580 \end{warpHTML}

```

## 39.8 High-level block and inline classes

These are high-level commands which allow the creation of arbitrary block or inline sections which may be formatted with css.

Nullified versions are provided for print mode.

For other direct-formatting commands, see section [72](#).

**Env** **BlockClass** [*style*] {*class*} High-level interface for <div> classes.

Ex: \begin{BlockClass}{class} text \end{BlockClass}

**for HTML output:** 3581 \begin{warpHTML}
3582 \NewDocumentEnvironment{BlockClass}{o m}%
3583 {
3584 \LWR@htmldivclass[#1]{#2}%
3585 }
3586 {
3587 \LWR@htmldivclassend{#2}%
3588 }
3589 \end{warpHTML}

**for PRINT output:** 3590 \begin{warpprint}
3591 \NewDocumentEnvironment{BlockClass}{o m}{}{}%
3592 \end{warpprint}

**\BlockClassSingle** {*class*} {*text*} A single-line <div>, without a paragraph tag for the line of text.

**for HTML output:** 3593 \begin{warpHTML}
3594 \newcommand{\BlockClassSingle}[2]{%
3595 \LWR@htmlelementclassline{div}{#1}{#2}}%

```

3596 }
3597 \end{warpHTML}

for PRINT output: 3598 \begin{warpprint}
3599 \newcommand{\BlockClassSingle}[2]{#2}
3600 \end{warpprint}

\InlineClass [⟨style⟩] {⟨class⟩} {⟨text⟩} High-level interface for inline span classes.

for HTML output: 3601 \begin{warpHTML}
3602 \NewDocumentCommand{\InlineClass}{o m +m}{%
3603 \LWR@htmlspanclass[#1]{#2}{#3}%
3604 }
3605 \end{warpHTML}

for PRINT output: 3606 \begin{warpprint}
3607 \NewDocumentCommand{\InlineClass}{o m +m}{#3}%
3608 \end{warpprint}

```

## 39.9 Closing HTML tags

**for HTML output:** 3609 \begin{warpHTML}

Sections H1, H2, etc. do not need a closing HTML tag, but we add a comment for readability:

```

3610 \newcommand*\LWR@printclosepart{%
3611   \ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing part}}{}}
3612 \newcommand*\LWR@printclosechapter{%
3613   \ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing chapter}}{}}
3614 \newcommand*\LWR@printclosesection{%
3615   \ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing section}}{}}
3616 \newcommand*\LWR@printclosesubsection{%
3617   \ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsection}}{}}
3618 \newcommand*\LWR@printclosesubsubsection{%
3619   \ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsubsection}}{}}
3620 \newcommand*\LWR@printcloseparagraph{%
3621   \ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing paragraph}}{}}
3622 \newcommand*\LWR@printclosesubparagraph{%
3623   \ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subparagraph}}{}}

```

Lists require closing HTML tags:

```

3624 \newcommand*\LWR@printcloselistitem{%
3625   \LWR@htmltag{/li}}
3626 \newcommand*\LWR@printclosedescitem{%

```

---

```

3627     {\LWR@htmltag{/dd}}
3628 \newcommand*{\LWR@printcloseitemize}
3629     {\LWR@htmltag{/ul}}
3630 \newcommand*{\LWR@printcloseenumerate}
3631     {\LWR@htmltag{/ol}}
3632 \newcommand*{\LWR@printclosedescription}
3633     {\LWR@htmltag{/dl}}
3634 \end{warpHTML}

```

## 40 Paragraph handling

These commands generate the HTML paragraph tags when allowed and required.

Paragraph tags are or are not allowed depending on many conditions. Section 41 has high-level commands which allow paragraph-tag generation to start/stop. Even when allowed (`\LWR@doingstartpars`), tags are not generated until a L<sup>A</sup>T<sub>E</sub>X paragraph is being used (`\LWR@doingapar`). `\LWR@lateximagedepth` is used to prevent nesting tags inside a `\textrm`. `\LWR@spandepth` is used to prevent nesting paragraph tags inside a paragraph, which became important inside `\fbox` commands and other spans.

**for HTML output:** 3635 `\begin{warpHTML}`

Ctr `\LWR@spandepth` Do not create paragraph tags inside of an HTML span.

```

3636 \newcounter{\LWR@spandepth}
3637 \setcounter{\LWR@spandepth}{0}

```

Bool `\LWR@doingstartpars` Tells whether paragraphs may be generated.

```

3638 \newbool{\LWR@doingstartpars}
3639 \boolfalse{\LWR@doingstartpars}

```

Bool `\LWR@doingapar` Tells whether have actually generated and are currently processing paragraph text.

```

3640 \newbool{\LWR@doingapar}
3641 \global\boolfalse{\LWR@doingapar}

```

`\LWR@ensuredoingapar` If are about to print something visible, and if allowed to start a new paragraph, ensure that are `\LWR@doingapar`, so that paragraph tags are placed:

```

3642 \newcommand*{\LWR@ensuredoingapar}{%
3643 \ifbool{\LWR@doingstartpars}{%

```

---

```
3644 {\global\booltrue{LWR@doingapar}}%
3645 {}%
3646 }
```

\LWR@openparagraph

```
3647 \newcommand*{\LWR@openparagraph}{%
3648 {}%
```

See if paragraph handling is enabled:

```
3649 \ifbool{LWR@doingstartpars}{%
3650 {}% handling pars}
```

See if have already started a `lateximage` or a `<span>`. If so, do not generate nested paragraph tags.

```
3651 \ifthenelse{%
3652   \cnttest{\value{LWR@lateximagedepth}}{>}{0} \OR%
3653   \cnttest{\value{LWR@spandepth}}{>}{0}%
3654 }% nested par tags?
```

If so: Do nothing if already started a `lateximage` page. Cannot nest a `lateximage`. Also do nothing if already inside a `<span>`. Do not nest paragraph tags inside a `<span>`.

```
3655 {}% no nested par tags
```

Else: No `lateximage` or `<span>` has been started yet, so it's OK to generate paragraph tags.

```
3656 {}% yes nest par tags
3657 \LWR@htmltagc{\LWR@tagregularparagraph}{%
```

Manually indent item list labels to avoid left margin intrustion:

See if are nested inside an item list:

```
3658 \ifnumcomp{\@listdepth}{>}{0}{%
3659 {}%
```

If so, leave some horizontal room in the `LATEX` PDF output for list labels:

```
3660 \LWR@orighspace{1in}{%
3661 }%
3662 {}%
```

Now have started a paragraph.

```
3663 \global\booltrue{LWR@doingapar}%
```

At the endof each paragraph, generate closing tag and do regular /par stuff. (Attempting to use the everyhook cr hook for \LWR@closeparagraph does not work well.)

```
3664 \let\par\LWR@closeparagraph%
3665 }% end of yes nest par tags
3666 }% end of handling pars
3667 {}% not handling pars
3668 }
```

\LWR@closeparagraph

```
3669 \newcommand*\LWR@closeparagraph{%
3670 {}%
```

See if paragraph handling is enabled:

```
3671 \ifbool{LWR@doingapar}{%
```

If currently in paragraph mode:

```
3672 {}% handling pars
```

See if already started a `lateximage` or a `<span>`:

```
3673 \ifthenelse{%
3674   \cnttest{\value{LWR@lateximagedepth}}{>}{}{0} \OR%
3675   \cnttest{\value{LWR@spandepth}}{>}{}{0}%
3676 }%
```

Do nothing if already started a `lateximage` or a `<span>`, but add a `parbreak` if in a `span` but not a `lateximage`.

```
3677 {}% no nested par tags
3678 \ifthenelse{%
3679   \cnttest{\value{LWR@spandepth}}{>}{}{0}%
3680   \AND%
3681   \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
3682 }%
3683 {\ifbool{LWR@intabularmetadata}{}{\unskip\LWR@htmltagc{br /}}{}}
3684 {}%
3685 }% no nested par tags
```

If have not already started a `\teximage` or a `<span>`:

```
3686      {%
```

Print a closing tag and some extra vertical space:

```
3687          \unskip%
3688          \LWR@htmlltagc{/\LWR@tagregularparagraph}%
3689          \LWR@orignewline%
```

No longer doing a paragraph:

```
3690          \global\boolfalse{LWR@doingapar}%
3691 % Disable the special \env{minipage} \& \cs{hspace} interaction
3692 % until a new minipage is found:
3693 %   \begin{macrocode}
3694         \global\boolfalse{LWR@minipagethispar}%
3695     }% end of yes nest par tags
3696 }% end of handling pars
```

Add a parbreak if in a span, but not in a table outside a row:

```
3697 {%
3698     not handling pars
3699     \ifthenelse{\cnttest{\value{LWR@spandepth}}>0}{%
3700     \ifbool{LWR@intabularmetadata}{}{\unskip\LWR@htmlltagc{br /}}}}%
3701 }% not handling pars
```

Finish with regular paragraph processing

```
3702 \LWR@origpar%
3703 }

3704 \end{warpHTML}
```

## 41 Paragraph start/stop handling

These commands allow/disallow the generation of HTML paragraph tags.

Section 40 has the commands which actually generate the tags.

The `everyhook` package is used to generate the opening paragraph tags. The closing tags are generated by `\par`.

**for HTML output:** 3705 `\begin{warpHTML}`

\LWR@startpars Begin handling HTML paragraphs. This allows an HTML paragraph to start, but one has not yet begun.

```
3706 \newcommand*\LWR@startpars{%
3707 {%
```

Ignore if inside a span:

```
3708 \ifthenelse{\cnttest{\value{\LWR@spandepth}}{>}{0}}{%
3709 {}%
3710 {}%
```

See if currently handling HTML paragraphs:

```
3711 \ifbool{\LWR@doingstartpars}{%
```

If already in paragraph mode, do nothing.

```
3712 {}%
```

If not currently in paragraph mode:

```
3713 {}%
```

At the start of each paragraph, generate an opening tag:

```
3714 \PushPreHook{par}{\LWR@openparagraph}{%
```

At the end of each paragraph, generate closing tag and do regular /par actions:

```
3715 \let\par\LWR@closeparagraph
3716 }% an intentionally blank line
```

Are now handling paragraphs, but have not yet actually started one:

```
3718 \global\setbool{\LWR@doingstartpars}{true}{%
```

No <par> tag yet to undo:

```
3719 \global\boolfalse{\LWR@doingapar}{%
3720 }% nestspan
3721 }
```

\LWR@stopars Stop handling HTML paragraphs. Any currently open HTML paragraph is closed, and no more will be opened.

```
3722 \newcommand*{\LWR@stoppars}{%
3723 {%
```

Ignore if inside a span:

```
3724 \ifthenelse{\cnttest{\value{LWR@spandepth}}{>}{0}}{%
3725 {}{%
3726 {}{%
```

See if currently handling HTML paragraphs:

```
3727 \ifbool{LWR@doingapar}{%
```

if currently in an HTML paragraph:

```
3728 {}{%
```

Print a closing tag:

```
3729 \unskip{%
3730 \LWR@htmlltagc{/LWR@tagregularparagraph}{%
3731 \LWR@orignewline}{%
```

No longer have an open HTML paragraph:

```
3732 \global\boolfalse{LWR@doingapar}{%
```

Disable the special `\minipage` & `\hspace` interaction until a new minipage is found:

```
3733 \global\boolfalse{LWR@minipagethispar}{%
3734 }{%
3735 }% an intentionally blank line
```

If was not in an HTML paragraph:

```
3736 {}{%
```

See if currently allowing HTML paragraphs:

```
3737 \ifbool{LWR@doingstartpars}{%
```

If so: clear the par hook to no longer catch paragraphs:

```
3738 {\ClearPreHook{par}}{%
```

Else: do nothing

```
3739 {}{%
```

no longer in paragraph mode

```
3740     \global\setbool{LWR@doingstartpars}{false}%
3741     \global\boolfalse{LWR@doingapar}%
3742 }% nestspan
3743 }

3744 \end{warpHTML}
```

## 42 Page headers and footers

**for HTML & PRINT:** 3745 \begin{warpall}

In the following, catcode is manually changes back and forth without groups, since new macros are being defined which must not be contained within the groups.

```
3746 \newcommand{\LWR@firstpagetop}{} % for the home page alone
3747 \newcommand{\LWR@pagetop}{} % for all other pages
3748 \newcommand{\LWR@pagebottom}{}%
3749
3750 \newcommand{\LWR@setfirstpagetopb}[1]{%
3751 \renewcommand{\LWR@firstpagetop}{#1}
3752 \catcode`\_=8
3753 }
```

\HTMLFirstPageTop {*text and logos*}

```
3754 \newcommand{\HTMLFirstPageTop}{%
3755 \catcode`\_=12
3756 \LWR@setfirstpagetopb
3757 }

3758 \newcommand{\LWR@setpagetopb}[1]{%
3759 \renewcommand{\LWR@pagetop}{#1}
3760 \catcode`\_=8
3761 }
```

\HTMLPageTop {*text and logos*}

```
3762 \newcommand{\HTMLPageTop}{%
3763 \catcode`\_=12
```

```

3764 \LWR@setpagetopb
3765 }

3766 \newcommand{\LWR@setpagebottomb}[1]{%
3767 \renewcommand{\LWR@pagebottom}{#1}
3768 \catcode`\_=8
3769 }

\HTMLPageBottom {<text and logos>}

3770 \newcommand{\HTMLPageBottom}{%
3771 \catcode`\_=12
3772 \LWR@setpagebottomb
3773 }

3774 \end{warpall}

```

## 43 CSS

**for HTML output:** 3775 \begin{warpHTML}

\LWR@currentcss The css filename to use. This may be changed mid-document using \CSSFilename, allowing different css files to be used for different sections of the document.

```
3776 \newcommand*{\LWR@currentcss}{lwarp.css}
```

\CSSFilename {<new-css-filename.css>} Assigns the css file to be used by the following HTML pages.

```

3777 \newcommand*{\LWR@newcssb}[1]{%
3778 \renewcommand*{\LWR@currentcss}{#1}
3779 \catcode`\_=8
3780 }
3781
3782 \newcommand*{\CSSFilename}{%
3783 \catcode`\_=12
3784 \LWR@newcssb
3785 }
3786 \end{warpHTML}

```

**for PRINT output:** 3787 \begin{warpprint}
3788 \newcommand\*{\CSSFilename}[1]{}
3789 \end{warpprint}

## 44 HTML meta description and author

**for HTML & PRINT:** 3790 \begin{warpall}

\HTMLAuthor {\<authorname>} The author to place into an HTML meta tag.

```
3791 \providecommand{\theauthor}{}  
3792 \newcommand{\theHTMLAuthor}{\theauthor}  
3793  
3794 \newcommand{\HTMLAuthor}[1]{\renewcommand{\theHTMLAuthor}{#1}}  
  
3795 \end{warpall}
```

**for HTML & PRINT:** 3796 \begin{warpall}

This is placed inside an HTML meta tag at the start of each file. This may be changed mid-document using \HTMLDescription, allowing different HTML descriptions to be used for different sections of the document.

- ⚠ Do not use double quotes, and do not exceed 150 characters.

\HTMLDescription {\<New HTML meta description.>} Assigns the HTML file's description meta tag.

```
3797 \newcommand{\LWR@currentHTMLDescription}{}  
3798  
3799 \newcommand{\HTMLDescription}[1]{%  
3800 \renewcommand{\LWR@currentHTMLDescription}{#1}  
3801 }  
3802  
3803 \end{warpall}
```

## 45 Footnotes

lwarf uses native  $\text{\LaTeX}$  footnote code, although with its own \box to avoid the  $\text{\LaTeX}$  output routine. The usual functions work as-is.

- ⚠ **pfnote numbers** While emulating pfnote, lwarf is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. lwarf therefore uses continuous footnote numbering even for pfnote.

Several kinds of footnotes are used: in a regular page, in a minipage, or as thanks in the titlepage. Each of these is handle differently.

## 45.1 Regular page footnotes

In HTML documents, footnotes are placed at the bottom of the web page using the L<sup>A</sup>T<sub>E</sub>X box \LWR@footnotes. Using this instead of the original \footins box avoids having footnotes be printed by the output routine, since footnotes should be printed per HTML page instead of per PDF page.

See section 45.4 for the implementation.

## 45.2 Minipage footnotes

See section 45.5 for how minipage footnotes are gathered. See section 71.3 for how minipage footnotes are placed into the document.

## 45.3 Titlepage thanks

See section 52.6 for titlepage footnotes.

## 45.4 Regular page footnote implementation

**for HTML output:** 3804 \begin{warpHTML}

Patch L<sup>A</sup>T<sub>E</sub>X footnotes to use a new \box for lwarp footnotes.

3805 \newbox{\LWR@footnotes}

Much of the following has unneeded print-mode formatting removed.

```
\@makefntext {⟨text⟩}
3806 \long\def\@makefntext#1{\textsuperscript{\@thefnmark} #1}
\@makefnmark
3807 \def\@makefnmark{\hbox{\textsuperscript{\@thefnmark}}}
```

Footnotes may be in regular text, in which case paragraphs are tagged, or in a table data cell or `lateximage`, in which case paragraph tags must be added manually.

In a `lateximage` during HTML output, the `lateximage` is placed inside a print-mode `minipage`, but the footnotes are broken out by:

```

\def\@mpfn{footnote}
\def\thempfn{\thefootnote}
\let\@footnotetext\LWR@footnotetext

\LWR@footnotetext {\langle text\rangle}

3808 \long\def\LWR@footnotetext#1{%
3809 \global\setbox\LWR@footnotes=\vbox{%

```

Add to any current footnotes:

```
3810 \unvbox\LWR@footnotes%
```

Remember the footnote number for \ref:

```

3811 \protected@edef\@currentlabel{%
3812   \csname p@footnote\endcsname\@thefnmark%
3813 }% @currentlabel

```

Open a group:

```
3814 \color@begingroup%
```

Use HTML superscripts even inside a `lateximage`:

```
3815 \renewcommand{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a `lateximage`:

```

3816 \ifthenelse{%
3817   \boolean{LWR@doingstartpars} \AND%
3818   \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
3819 }%
3820 {}%
3821 {\LWR@htmlltagc{\LWR@tagregularparagraph}}%

```

Append the footnote to the list:

```
3822 \@makefntext{\#1}%
```

Closing paragraph tag:

```

3823 \ifthenelse{%
3824   \boolean{LWR@doingstartpars} \AND%
3825   \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
3826 }%
3827 {\par}%

```

```

3828      {%
3829      \LWR@htmntagc{\LWR@tagregularparagraph}%
3830      \LWR@orignewline%
3831      }%

```

Close the group:

```

3832      \color@endgroup%
3833 }% vbox
3834 }%
\@footnotetext {\langle text\rangle}
3835 \let\@footnotetext\LWR@footnotetext

```

## 45.5 Minipage footnote implementation

```

\@mpfootnotetext {\langle text\rangle}
3836 \long\def\@mpfootnotetext#1{%
3837 \global\setbox\@mpfootins\vbox{%
3838     \unvbox\@mpfootins
3839     \reset@font\footnotesize
3840     \hsize\columnwidth
3841     \parboxrestore
3842     \protected@edef\@currentlabel
3843     {\csname p@mpfootnote\endcsname\@thefnmark}%
3844     \color@begingroup

```

Use paragraph tags if in a tabular data cell or a `lateximage`:

```

3845 \ifthenelse{%
3846     \boolean{LWR@doingstartpars} \AND%
3847     \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
3848 }%
3849 {}%
3850 {\LWR@htmntagc{\LWR@tagregularparagraph}}%
3851 \@makefntext{%
3852     \ignorespaces#1%
3853 }%

```

Don't add the closing paragraph tag if are inside a `lateximage`:

```

3854 \ifthenelse{\cnttest{\value{LWR@lateximagedepth}}{>}{0}}{%

```

```

3855      {}%
3856      {%
3857          \LWR@htmntag{\LWR@tagregularparagraph}%
3858          \LWR@orignewline%
3859      }%
3860      \color@endgroup%
3861 }% vbox
3862 }

```

## 45.6 Printing pending footnotes

\LWR@printpendingfootnotes Enclose the footnotes in a class, print, then clear.

```

3863 \newcommand*{\LWR@printpendingfootnotes}{%
3864 \ifvoid\LWR@footnotes\else
3865     \LWR@forcenewpage
3866     \begin{BlockClass}{footnotes}
3867     \LWR@origmedskip
3868     \unvbox\LWR@footnotes
3869     \setbox\LWR@footnotes=\vbox{}
3870     \end{BlockClass}
3871 \fi
3872 }

```

\LWR@epubprintpendingfootnotes Used to print footnotes before sections only if formatting for an EPUB or word processor:

```

3873 \newcommand*{\LWR@epubprintpendingfootnotes}{%
3874 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWordProcessor}}{%
3875 {\LWR@printpendingfootnotes}%
3876 {}%
3877 }
3878 \end{warpHTML}

```

## 46 Marginpars

**for HTML output:** 3879 \begin{warpHTML}

```

\marginpar [⟨left⟩] {⟨right⟩}

3880 \renewcommand{\marginpar}[2] [] {%

```

---

```
3881 \LWR@htmlspanclass{marginpar}{#2}%
3882 }

3883 \end{warpHTML}
```

## 47 Splitting HTML files

- Files are split according to `FileDepth` and `CombineHigherDepths`.
- Filenames are sanitized by `\LWR@filenamenoblanks`.
- `\LWR@newhtmlfile` finishes an HTML page, adds a comment to tell where and how to split the file, then starts a new HTML page.

**for HTML & PRINT:** 3884 `\begin{warpall}`

`Ctr FileDepth` {*<section depth>*} determines how deeply to break into new HTML files, similar to `tocdepth`. The default of -5 produces one large HTML file.

```
3885 \newcounter{FileDepth}
3886 \setcounter{FileDepth}{-5}
```

`Bool CombineHigherDepths` Combiile higher-level sections together into one file?

```
3887 \newbool{CombineHigherDepths}
3888 \booltrue{CombineHigherDepths}
```

```
3889 \end{warpall}
```

**for HTML output:** 3890 `\begin{warpHTML}`

`\LWR@thisfilename` The currently-active filename or number.

```
3891 \newcommand*{\LWR@thisfilename}{}%
```

`\LWR@thisnewfilename` The filename being sanitized.

```
3892 \newcommand*{\LWR@thisnewfilename}{}%
```

`\LWR@filenamenoblanks` {*<filename>*}

Convert blanks into dashes, removes short words, store result in `\LWR@thisfilename`.



Be sure that this does not result in filename collisions! Use the optional TOC caption entry parameter for formatting. Remember to \protect \TeX commands which appear in section names and TOC captions.

```
3893 \newcommand*{\LWR@filenamenoblanks}[1]{%
3894 \begingroup
```

Locally temporarily disable direct-formatting commands, not used in filenames:

```
3895 \LWR@nullfonts
3896 \renewcommand*{\LWR@htmllagc}[1]{}%
```

Replaces common symbols and short words with hyphens:

```
3897 \edef\LWR@thisnewfilename{#1}
3898 \fullexpandarg
```

Convert spaces into hyphens:

```
3899 \StrSubstitute{\LWR@thisnewfilename}{ }{-}[\LWR@thisnewfilename]
```

Convert punctuation into hyphens:

```
3900 \StrSubstitute{\LWR@thisnewfilename}{,-}[\LWR@thisnewfilename]
3901 \StrSubstitute{\LWR@thisnewfilename}{'}{-}[\LWR@thisnewfilename]
3902 \StrSubstitute{\LWR@thisnewfilename}%
3903 {\LWR@origampersand}{-}[\LWR@thisnewfilename]
3904 \StrSubstitute{\LWR@thisnewfilename}{+}{-}[\LWR@thisnewfilename]
3905 \StrSubstitute{\LWR@thisnewfilename}{,}{-}[\LWR@thisnewfilename]
3906 \StrSubstitute{\LWR@thisnewfilename}{/}{-}[\LWR@thisnewfilename]
3907 \StrSubstitute{\LWR@thisnewfilename}{:}{-}[\LWR@thisnewfilename]
3908 \StrSubstitute{\LWR@thisnewfilename}{;}{-}[\LWR@thisnewfilename]
3909 \StrSubstitute{\LWR@thisnewfilename}{=}{-}[\LWR@thisnewfilename]
3910 \StrSubstitute{\LWR@thisnewfilename}{?}{-}[\LWR@thisnewfilename]
3911 \StrSubstitute{\LWR@thisnewfilename}{@}{-}[\LWR@thisnewfilename]
3912 \StrSubstitute{\LWR@thisnewfilename}{"}{-}[\LWR@thisnewfilename]
3913 \StrSubstitute{\LWR@thisnewfilename}%
3914 {\textless}{-}[\LWR@thisnewfilename]
3915 \StrSubstitute{\LWR@thisnewfilename}%
3916 {\textgreater}{-}[\LWR@thisnewfilename]
3917 \StrSubstitute{\LWR@thisnewfilename}{\#}{-}[\LWR@thisnewfilename]
3918 \StrSubstitute{\LWR@thisnewfilename}{\%}{-}[\LWR@thisnewfilename]
3919 \StrSubstitute{\LWR@thisnewfilename}{\{}{-}[\LWR@thisnewfilename]
3920 \StrSubstitute{\LWR@thisnewfilename}{\}}{-}[\LWR@thisnewfilename]
3921 \StrSubstitute{\LWR@thisnewfilename}{\|}{-}[\LWR@thisnewfilename]
3922 \StrSubstitute{\LWR@thisnewfilename}%
3923 {\textbackslash}{-}[\LWR@thisnewfilename]
3924 \StrSubstitute{\LWR@thisnewfilename}{^}{-}[\LWR@thisnewfilename]
```

```

3925 \StrSubstitute{\LWR@thisnewfilename}{~-{}~-}[\LWR@thisnewfilename]
3926 %      "~{}" for babel
3927 \StrSubstitute{\LWR@thisnewfilename}{[]~-}[\LWR@thisnewfilename]
3928 \StrSubstitute{\LWR@thisnewfilename}{[]}~-[\LWR@thisnewfilename]
3929 \StrSubstitute{\LWR@thisnewfilename}{`~-}[\LWR@thisnewfilename]

```

Convert short words:

```

3930 \StrSubstitute{\LWR@thisnewfilename}{-s~-}[-] [\LWR@thisnewfilename]
3931 \StrSubstitute{\LWR@thisnewfilename}{-S~-}[-] [\LWR@thisnewfilename]
3932 \StrSubstitute{\LWR@thisnewfilename}{-a~-}[-] [\LWR@thisnewfilename]
3933 \StrSubstitute{\LWR@thisnewfilename}{-A~-}[-] [\LWR@thisnewfilename]
3934 \StrSubstitute{\LWR@thisnewfilename}{-an~-}[-] [\LWR@thisnewfilename]
3935 \StrSubstitute{\LWR@thisnewfilename}{-AN~-}[-] [\LWR@thisnewfilename]
3936 \StrSubstitute{\LWR@thisnewfilename}{-to~-}[-] [\LWR@thisnewfilename]
3937 \StrSubstitute{\LWR@thisnewfilename}{-TO~-}[-] [\LWR@thisnewfilename]
3938 \StrSubstitute{\LWR@thisnewfilename}{-by~-}[-] [\LWR@thisnewfilename]
3939 \StrSubstitute{\LWR@thisnewfilename}{-BY~-}[-] [\LWR@thisnewfilename]
3940 \StrSubstitute{\LWR@thisnewfilename}{-of~-}[-] [\LWR@thisnewfilename]
3941 \StrSubstitute{\LWR@thisnewfilename}{-OF~-}[-] [\LWR@thisnewfilename]
3942 \StrSubstitute{\LWR@thisnewfilename}{-and~-}[-] [\LWR@thisnewfilename]
3943 \StrSubstitute{\LWR@thisnewfilename}{-AND~-}[-] [\LWR@thisnewfilename]
3944 \StrSubstitute{\LWR@thisnewfilename}{-for~-}[-] [\LWR@thisnewfilename]
3945 \StrSubstitute{\LWR@thisnewfilename}{-FOR~-}[-] [\LWR@thisnewfilename]
3946 \StrSubstitute{\LWR@thisnewfilename}{-the~-}[-] [\LWR@thisnewfilename]
3947 \StrSubstitute{\LWR@thisnewfilename}{-THE~-}[-] [\LWR@thisnewfilename]

```

Convert multiple hyphens:

```

3948 \StrSubstitute{\LWR@thisnewfilename}{-----}[-] [\LWR@thisnewfilename]
3949 \StrSubstitute{\LWR@thisnewfilename}{----}[-] [\LWR@thisnewfilename]
3950 \StrSubstitute{\LWR@thisnewfilename}{---}[-] [\LWR@thisnewfilename]
3951 \StrSubstitute{\LWR@thisnewfilename}{--}[-] [\LWR@thisnewfilename]
3952 \StrSubstitute{\LWR@thisnewfilename}{--}[-] [\LWR@thisnewfilename]
3953 %      emdash
3954 \StrSubstitute{\LWR@thisnewfilename}{-}[-] [\LWR@thisnewfilename]
3955 %      endash
3956 \global\let\LWR@thisfilename\LWR@thisnewfilename% return a global result
3957 \endgroup
3958 }

```

\LWR@newhtmlfile {*section name*}

Finishes the current HTML page with footnotes, footer, navigation, then starts a new HTML page with an HTML comment telling where to split the page and what the new filename and css are, then adds navigation, side TOC, header, and starts the text body.

```
3959 \newcommand*{\LWR@newhtmlfile}[1]{
```

At the bottom of the ending file:

```
3960 \LWR@htmlelementclassend{section}{textbody}
3961
3962 \LWR@printpendingfootnotes
3963
```

No footer between files if EPUB:

```
3964 \ifbool{FormatEPUB}
3965 {}
3966 {
3967     \LWR@htmlelement{footer}
3968
3969     \LWR@pagebottom
3970
3971     \LWR@htmlelementend{footer}
3972 }
```

No bottom navigation if are finishing the home page or formatting for EPUB or a word-processor.

```
3973 \ifthenelse{\boolean{FormatEPUB} \OR \boolean{FormatWordProcessor}}
3974 {}
3975 {\ifnumcomp{\value{LWR@htmlfilename}}{>}{0}{\LWR@botnavigation}{}}
```

End of this HTML file:

```
3976 \LWR@stopars
3977 \LWR@htmlelement{/body}\LWR@orignewline
3978 \LWR@htmlelement{/html}\LWR@orignewline
3979 \LWR@orignewline
3980
3981 \addtocounter{LWR@htmlfilename}{1}%
```

If using a filename, create a version without blanks. The filename without blanks will be placed into \LWR@thisfilename. If not using a filename, the file number will be used instead.

```
3982 \ifbool{FileSectionNames}{%
3983 {\LWR@filenamenoblanks{\#1}}
3984 {\renewcommand*{\LWR@thisfilename}{\theLWR@htmlfilename}}}
```

Include an HTML comment to instruct lwarpmk where to split the files apart. Uses pipe-separated fields for split\_html.gawk. Uses monospaced font with ligatures disabled for everything except the title.

```
3985 \LWR@htmlblockcomment{%
3986 |Start file|%
3987 \LWR@htmlsectionfilename{\LWR@thisfilename}|%
3988 }
```

At the top of the starting file:

```
3989 \LWR@stopars
3990

3991 \LWR@filestart{ -- #1}% there is an EMdash in front of the #1
3992
```

No navigation between files if formatting for an EPUB or word processor:

```
3993 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWordProcessor}}
3994 {}
3995 {\LWR@topnavigation}
3996
```

No header if between files if formatting for an EPUB or word processor:

```
3997 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWordProcessor}}
3998 {}
3999 {
4000     \LWR@htmlelement{header}
4001
4002     \LWR@pagetop
4003
4004     \LWR@htmlelementend{header}
4005 }
4006
```

Print title only if there is one. Skip if formatting for an EPUB or word processor:

```
4007 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWordProcessor}}
4008 {}
4009 {\ifcvoid{\thetitle}{}{\LWR@printthetitle}}
4010
```

No sidetoc if formatting for an EPUB or word processor:

```
4011 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWordProcessor}}
4012 {}
4013 {\LWR@sidetoc}
4014
```

Start of the <textbody>:

---

```
4015 \LWR@htmlelementclass{section}{textbody}
4016
```

Keep paragraph tags disabled for now:

```
4017 \LWR@stopars
4018
```

Track the page numbers:

```
4019 \setcounter{LWR@latestautopage}{\value{page}}
4020 }

4021 \end{warpHTML}
```

## 48 Sectioning

Sectioning and cross-references have been emulated from scratch, rather than try to patch several layers of existing  $\text{\TeX}$  code and packages. Formatting is handled by css, so the emulated code has much less work to do than the print versions.

**Unicode** Section names and the resulting filenames with accented characters are partially supported, depending on the ability of pdflatex to generate characters and pdftotext to read them. If extra symbols appear in the text, it may be that pdflatex is actually producing a symbol over or under a character, resulting in pdftotext picking up the accent symbol separately.

$\text{\XeTeX}$  and  $\text{\LuaTeX}$  directly support accented section and file names.

**for HTML output:** 4022 \begin{warpHTML}

### 48.1 User-level starred section commands

**\ForceHTMLPage** For HTML output, forces the next section to be on its own HTML page, if FileDepth allows, even if starred. For use with \printindex and others which generate a starred section which should be on its own HTML page. Also see \ForceHTMLTOC.

For print output, no effect.

```
4023 \newbool{LWR@forcinghtmlpage}
4024 \boolfalse{LWR@forcinghtmlpage}
4025
4026 \newcommand*\{\ForceHTMLPage}\{%
```

---

```
4027 \global\booltrue{LWR@forcinghtmlpage}%
4028 }
```

**\ForceHTMLTOC** For HTML output, forces the next section to have a TOC entry, even if starred. For use with `\printindex` and others which generate a starred section which should be in the TOC so that it may be accessed via HTML. Not necessary if used with `tocbibind`. Also see `\ForceHTMLPage`.

For print output, no effect.

```
4029 \newbool{LWR@forcinghtmltoc}
4030 \boolfalse{LWR@forcinghtmltoc}
4031
4032 \newcommand*{\ForceHTMLTOC}{%
4033 \global\booltrue{LWR@forcinghtmltoc}%
4034 }
```

```
4035 \end{warpHTML}
```

**for PRINT output:** 4036 `\begin{warpprint}`  
 4037 `\newcommand*{\ForceHTMLPage}{}`  
 4038 `\newcommand*{\ForceHTMLTOC}{}`  
 4039 `\end{warpprint}`

**for HTML output:** 4040 `\begin{warpHTML}`

## 48.2 Book class commands

**\mainmatter** Declare the main matter section of the document. Does not reset the page number, which must be consecutive arabic numbers for the HTML conversion.

```
4041 \newbool{LWR@mainmatter}
4042 \DeclareDocumentCommand{\mainmatter}{}{%
4043 \booltrue{LWR@mainmatter}%
4044 }
```

**\frontmatter** Declare the front matter section of the document, using arabic numbering for the internal numbering. Does not reset the page number.

```
4045 \DeclareDocumentCommand{\frontmatter}{}{%
4046 \boolfalse{LWR@mainmatter}%
4047 }
```

**\backmatter** Declare the back matter section of the document. Does not reset the page number.

---

```
4048 \DeclareDocumentCommand{\backmatter}{}{%
4049 \boolfalse{LWR@mainmatter}%
4050 }
```

### 48.3 Sectioning support macros

`\LWR@sectionnumber {<section type>}`

Typeset a section number and its trailing space with CSS formatting:

```
4051 \newcommand*{\LWR@sectionnumber}[1]{%
4052 \InlineClass{sectionnumber}{#1}%
4053 }
```

`autosec` A tag used by the TOC and index.

`\LWR@createautosec {<section type>}`

Create an autosection tag.

```
4054 \newcommand*{\LWR@createautosec}[1]{%
4055 \LWR@htmntag{#1 id="autosec-\thepage"}%
4056 }
```

`\LWR@pushoneclose {<depth>} {<printclose>}` Stacks the new sectioning level's closing tag, to be used when this section is closed some time later.

 `\LWR@stoppars` must be executed first.

```
4057 \NewDocumentCommand{\LWR@pushoneclose}{m m}{\pushclose{#2}{#1}}
```

`\LWR@startnewdepth {<depth>} {<printclose>}`

Closes currently stacked tags of a lesser level, then opens the new nesting level by saving this new sectioning level's closing tag for later use.

 `\LWR@stoppars` must be executed first.

```
4058 \NewDocumentCommand{\LWR@startnewdepth}{m m}{%
```

Close any stacked sections up to this new one.

```
4059 \LWR@closeprevious{#1}%
```

Push a new section depth:

```
4060 \LWR@pushoneclose{#1}{#2}%
4061 }
```

**Ctr LWR@prevFileDepth** Remembers the previous LWR@FileDepth.

Initialized to a deep level so that any section will trigger a new HTML page after the home page.

```
4062 \newcounter{LWR@prevFileDepth}
4063 \setcounter{LWR@prevFileDepth}{\LWR@depthsubparagraph}
```

**\@seccntformat {<sectiontype>}**

```
4064 \def\@seccntformat#1{\csname the#1\endcsname\protect\quad}
```

**\simplechapterdelim** Used by tocbind and anonchap.

```
4065 \newcommand*\simplechapterdelim{}
```

**\@chapcntformat {<sectiontype>}**

\let to \@seccntformat by default, but may be redefined by \simplechapter and \restorechapter from tocbind or anonchap.

```
4066 \let\@chapcntformat\@seccntformat
```

**\LWR@section \* [<TOC name>] {<name>} {<sectiontype>}**

The common actions for the high-level sectioning commands.

```
4067 \DeclareDocumentCommand{\LWR@section}{m m m}{%
4068 \LWR@traceinfo{\LWR@section |#2| |#3|}%
4069 % \ifthenelse{%
4070 % % \equal{#2}{-NoValue-}\AND%
4071 % \isempty{#3}%
4072 % }%
4073 % {} empty section name
4074 % \LWR@traceinfo{\LWR@section: empty section}%
4075 % }% empty section name
4076 % {} not an empty section name
4077 \LWR@traceinfo{\LWR@section: not an empty section}%
4078 \LWR@stopars%
```

Cancel special `minipage` horizontal space interaction:

```
4079 \global\boolefalse{LWR@minipagethispar}%
```

Start a new HTML file unless starred, and if is a shallow sectioning depth.

Exception: Also start a new HTML file for `\part*`, for appendix.

Generate a new L<sup>A</sup>T<sub>E</sub>X page so that toc and index page number points to the section:

```
4080 \LWR@traceinfo{LWR@section: testing whether to start a new HTML file}%
4081 \IfBooleanTF{#1}{\LWR@traceinfo{LWR@section: starred}}{%
4082 \ifbool{LWR@forcinghtmlpage}{\LWR@traceinfo{LWR@section: forcinghtmlpage}}{}%
4083 \ifthenelse{%
4084   \%
4085   (\NOT\equal{#1}{\BooleanTrue})\OR%
4086   (\cnttest{\csuse{LWR@depth#4}}{=}{\LWR@depthpart})\OR%
4087   (\boolean{LWR@forcinghtmlpage})\%
4088 }%
4089 \AND%
4090 \cnttest{\csuse{LWR@depth#4}}{<=}{\value{FileDepth}}\%
4091 \AND%
4092 \%
4093 \NOT\boolean{CombineHigherDepths}\OR%
4094 \cnttest{\csuse{LWR@depth#4}}{<=}{\value{LWR@prevFileDepth}}\%
4095 }%
4096 \AND%
4097 \NOT\equal{#3}{% phantomsection
4098 }%
```

If so: start a new HTML file:

```
4099 {%
4100   new file
4101   \LWR@traceinfo{LWR@section: new HTML file}%
}
```

See if there was an optional TOC name entry:

```
4101 \IfNoValueTF{#2}{%
```

If no optional entry

```
4102 {\LWR@newhtmlfile{#3}}%
```

If yes an optional entry

```
4103 {\LWR@newhtmlfile{#2}}%
4104 }% new file
```

Else: No new HTML file:

```
4105 { % not new file
```

Generate a new L<sup>A</sup>T<sub>E</sub>X page so that toc and index page number points to the section:

```
4106     \LWR@traceinfo{LWR@section: not a new HTML file}%
4107     \LWR@orignewpage%
4108
4109 } % not new file
```

Remember this section's name for \nameref:

```
4110 \IfValueT{#3}{%
4111 \LWR@traceinfo{LWR@section: about to LWR@setlatestname}%
4112 \IfValueTF{#2}{\LWR@setlatestname{#2}}{\LWR@setlatestname{#3}}%
4113 }%
```

Print an opening comment with the level and the name; ex: "section" "Introduction"

```
4114
4115 \ifbool{HTMLDebugComments}{%
4116     \LWR@htmlcomment{Opening #4 ``#3''{}}%
4117 }{}%
4118
```

For inline sections paragraph and subparagraph, start a new paragraph now:

```
4119 \ifthenelse{%
4120     \cnttest{\csuse{LWR@depth#4}}{>=}{\LWR@depthparagraph}%
4121 }%
4122 {\LWR@startpars}%
4123 }%
```

Create the opening tag with an autosec:

```
4124 \LWR@createautosec{\csuse{LWR@tag#4}}%
```

Check if starred:

```
4125 \IfBooleanTF{#1}%
4126 { %
```

Starred, but also forcing a TOC entry, so add unnumbered TOC name or regular name:

```
4127 \ifbool{LWR@forcinghtmtoc}{%
4128 {\addcontentsline{toc}{#4}{\IfValueTF{#2}{#2}{#3}}}}%
```

```
4129 {}%
4130 }% starred
```

Not starred, so step counter and add to TOC:

```
4131 {%
  not starred
```

Only add a numbered TOC entry if section number is not too deep:

```
4132     \ifthenelse{%
 4133       \cnttest{\csuse{LWR@depth#4}}{<=}{\value{secnumdepth}}}{%
 4134     }%
 4135     {%
       if secnumdepth
```

If in the main matter, step the counter and add the TOC entry. For article class, lwarp assumes that all is mainmatter.

```
4136     \LWR@traceinfo{LWR@section: about to test main matter}%
4137     \ifbool{LWR@mainmatter}{%
 4138     }%
 4139     \LWR@traceinfo{LWR@section: yes mainmatter}%
4140     \refstepcounter{#4}%

```

Add main matter numbered TOC entry with the TOC name or the regular name:

```
4141     \LWR@traceinfo{LWR@section: about to addcontentsline}%
4142     \addcontentsline{toc}{#4}%
4143     }%
 4144     \protect\numberline{\csuse{the#4}}%
 4145     \ignorespaces\IfValueTF{#2}{#2}{#3}\protect\relax}%
4146   }%
 4147   \LWR@traceinfo{LWR@section: finished addcontentsline}%
4148 }% end of if main matter
```

If not main matter, add unnumbered TOC name or regular name:

```
4149     {%
 4150       not main matter
 4151       \LWR@traceinfo{LWR@section: no main matter}%
 4152       \addcontentsline{toc}{#4}{\IfValueTF{#2}{#2}{#3}}%
 4153     }% end of not main matter
 4154   }% end of secnumdepth
```

Deeper than secnumdepth, so add an unnumbered TOC entry:

```
4154   {%
 4155     \addcontentsline{toc}{#4}{\IfValueTF{#2}{#2}{#3}}%
 4156   }%
```

For part, print the section type:

```

4157      \ifbool{LWR@mainmatter}%
4158      {%
4159          \ifthenelse{%
4160              \(\cnttest{\csuse{LWR@depth#4}}{<=}\%
4161                  {\value{secnumdepth}}\)} \AND%
4162              \(\cnttest{\csuse{LWR@depth#4}}{<}{\LWR@depthpart}\)%
4163          }%
4164          {\csuse{#4name}~{}}
4165      }%

```

Print the section number:

```

4166      \LWR@traceinfo{LWR@section: about to print section number}%
4167      \ifthenelse{%
4168          \cnttest{\csuse{LWR@depth#4}}{<=}{\value{secnumdepth}}}%
4169      }%
4170      \{%
4171          \ifstreqal{#4}{chapter}%
4172              {\protect\LWR@sectionnumber{\chapcntformat{#4}}}%
4173              {\protect\LWR@sectionnumber{\secntformat{#4}}}%
4174          }%
4175          \}%
4176      \LWR@traceinfo{LWR@section: finished print section number}%
4177  }{%
4178 }% end of not starred

```

Print the section name:

```
4179 #3%
```

Close the heading tag, such as /H2:

```
4180 \LWR@htmntag{\csuse{LWR@tag#4end}}%
```

Generate a L<sup>A</sup>T<sub>E</sub>X label:

```
4181 \label{autopage-\thepage}%
```

Start paragraph handing unless is an inline paragraph or subparagraph:

```

4182 \ifthenelse{%
4183     \cnttest{\csuse{LWR@depth#4}}{<}{\LWR@depthparagraph}%
4184 }%
4185 {\LWR@startpars}%
4186 }%

```

If not starred, remember the previous depth to possibly trigger a new HTML page.

HOWEVER, allow a `\part*` to start a new HTML page. This is used by appendix.

A starred section does not trigger a new HTML page at the beginning of this macro, so it should not affect it here at the end either. This became an issue when a `\listoftables` was tested in the middle of the document. The `\chapter*` for the list was not allowing a new HTML page for the section following it while `CombineHigherDepths` was true.

```

4187 \ifthenelse{%
4188     \NOT\equal{#1}{\BooleanTrue}\OR%
4189     \cnttest{\csuse{LWR@depth#4}}{=}{\LWR@depthpart}%
4190 }%
4191 {%
4192     \setcounter{LWR@prevFileDepth}{\csuse{LWR@depth#4}}%
4193 }%
4194 }%

```

Reset to defaults if not a phantomsection:

```

4195 \ifstrempty{#3}%
4196 {}%
4197 {%
4198 \global\boolfalse{LWR@forcinghtmlpage}%
4199 \global\boolfalse{LWR@forcinghtmltoc}%
4200 }%
4201 %
4202 }%
4203 \LWR@traceinfo{LWR@section: done}%
4204 }

```

## 48.4 \section and friends

`\part * [<TOC name>] {<name>}`

```

4205 \DeclareDocumentCommand{\part}{s o m}{%
4206 \LWR@epubprintpendingfootnotes%
4207 \LWR@stopars%
4208 %
4209 \LWR@startnewdepth{\LWR@depthpart}{\LWR@printclosepart}%
4210 %
4211 \LWR@section{#1}{#2}{#3}{part}%
4212 }

```

`\chapter * [<TOC name>] {<name>}`

```
4213 \let\@printcites\relax% for quotchap package
4214
4215 \@ifundefined{chapter}
4216 {}
4217 {%
4218 \DeclareDocumentCommand{\chapter}{s o m}{%
4219 \LWR@traceinfo{chapter #3}%
4220 \LWR@epubprintpendingfootnotes%
4221 \LWR@stoppars%
4222
4223 \LWR@startnewdepth{\LWR@depthchapter}{\LWR@printclosechapter}%
4224
4225 \LWR@section{#1}{#2}{#3}{chapter}%
4226 \@printcites% for quotchap package
4227 }
4228 }

\section * [<TOC name>] {<name>}

4229 \DeclareDocumentCommand{\section}{s o m}{%
4230 \LWR@epubprintpendingfootnotes%
4231 \LWR@stoppars%
4232
4233 \LWR@startnewdepth{\LWR@depthsection}{\LWR@printclosesection}%
4234
4235 \LWR@section{#1}{#2}{#3}{section}%
4236 }

\subsection * [<TOC name>] {<name>}

4237 \DeclareDocumentCommand{\subsection}{s o m}{%
4238 \LWR@epubprintpendingfootnotes%
4239 \LWR@stoppars%
4240
4241 \LWR@startnewdepth{\LWR@depthsubsection}{\LWR@printclosesubsection}%
4242
4243 \LWR@section{#1}{#2}{#3}{subsection}%
4244 }

\subsubsection * [<TOC name>] {<name>}

4245 \DeclareDocumentCommand{\subsubsection}{s o m}{%
4246 \LWR@epubprintpendingfootnotes%
4247 \LWR@stoppars%
4248
4249 \LWR@startnewdepth{\LWR@depthsubsubsection}%
4250 {\LWR@printclosesubsubsection}%
4251
```

```

4252 \LWR@section{#1}{#2}{#3}{subsubsection}%
4253 }

\paragraph * [<TOC name>] {<name>}

4254 \DeclareDocumentCommand{\paragraph}{s o m}{%
4255 \LWR@epubprintpendingfootnotes%
4256 \LWR@stoppars%
4257
4258 \LWR@startnewdepth{\LWR@depthparagraph}{\LWR@printcloseparagraph}%
4259
4260 \LWR@section{#1}{#2}{#3}{paragraph}%
4261 }

\subparagraph * [<TOC name>] {<name>}

4262 \DeclareDocumentCommand{\subparagraph}{s o m}{%
4263 \LWR@epubprintpendingfootnotes%
4264 \LWR@stoppars%
4265
4266 \LWR@startnewdepth{\LWR@depthsubparagraph}{\LWR@printclosesubparagraph}%
4267
4268 \LWR@section{#1}{#2}{#3}{subparagraph}%
4269 }

4270 \end{warpHTML}

```

## 49 Starting a new file

**for HTML & PRINT:** 4271 \begin{warpall}

\HTMLLanguage Default language for the HTML lang tag.

```

4272 \newcommand*{\LWR@currentHTMLLanguage}{en-US}
4273
4274 \newcommand*{\HTMLLanguage}[1]{%
4275 \renewcommand*{\LWR@currentHTMLLanguage}{#1}%
4276 }

```

4277 \end{warpall}

**for HTML output:** 4278 \begin{warpHTML}

```
\LWR@filestart {\langle title\_suffix\rangle}
```

Creates the opening HTML tags.

```
4279 \newcommand*\LWR@filestart[1]{  
4280 \LWR@traceinfo{\LWR@filestart}}
```

Locally temporarily disable direct-formatting commands:

```
4281 \begingroup  
4282 \LWR@traceinfo{\LWR@filestart: A}  
4283 \LWR@nullfonts  
4284 \LWR@traceinfo{\LWR@filestart: B}
```

Create the page's HTML header:

```
4285 \LWR@htmlltag{!DOCTYPE html}\LWR@orignewline  
4286 \LWR@traceinfo{\LWR@filestart: C}
```

The language is user-adjustable:

```
4287 \LWR@htmlltag{html lang="\LWR@currentHTMLLanguage"{} }\LWR@orignewline
```

Start of the meta data:

```
4288 \LWR@htmlltag{head}\LWR@orignewline
```

Charset is fixed at UTF-8:

```
4289 \LWR@htmlltag{meta charset="UTF-8" /}\LWR@orignewline
```

Author:

```
4290 \ifcsempty{\theHTMLAuthor}{}{  
4291 \LWR@htmlltag{meta name="author" content="\theHTMLAuthor" /}\LWR@orignewline  
4292 }
```

lwarp is the generator:

```
4293 \LWR@htmlltag{meta name="generator" content="LaTeX lwarp package" /}%  
4294 \LWR@orignewline
```

If there is a description, add it now:

```
4295 \ifdefempty{\LWR@currentHTMLDescription}{}{  
4296 \LWR@htmlltag{  
4297 meta name="description" content="\LWR@currentHTMLDescription" /}%  
4298 \LWR@orignewline
```

```
4299 }%
```

Mobile-friendly viewport:

```
4300 \LWR@htmltag{meta name="viewport" %
4301 content="width=device-width, initial-scale=1.0" /}%
4302     \LWR@orignewline
```

IE patch:

```
4303 \LWR@htmltag{!{-}{-}[if lt IE 9]}\LWR@orignewline
4304 \LWR@htmltag{%
4305 script src="http://html5shiv.googlecode.com/svn/trunk/html5.js"{}}
4306 \LWR@htmltag{/script}\LWR@orignewline
4307 \LWR@htmltag{![-endif]{-}{-}}\LWR@orignewline
```

The page's title:

```
4308 \ifcvoid{thetitle}{}{%
4309 \LWR@htmltag{title}\thetitle#\LWR@htmltag{/title}\LWR@orignewline%
4310 }%
```

The page's stylesheet:

```
4311 \LWR@htmltag{%
4312 link rel="stylesheet" type="text/css" href="\LWR@currentcss" /}%
4313 \LWR@orignewline
```

Optional MathJax support. The HTML tags must be turned off during the verbatim input, and the paragraph handling which was turned on at the end of verbatim input must be immediately turned off again.

```
4314 \ifbool{mathjax}%
4315 {%
4316     \boolfalse{LWR@verbtags}
4317     \verbatiminput{lwarp_mathjax.txt}%
4318     \booltrue{LWR@verbtags}
4319     \LWR@stoppars
4320 }% end of mathjax
4321 {}%
```

End of the header:

```
4322 \LWR@htmltag{/head}\LWR@orignewline
```

Start of the body:

```
4323 \LWR@htmltag{body}\LWR@orignewline
```

---

```

4324 \endgroup
4325 \LWR@traceinfo{LWR@filestart: done}
4326 }

4327 \end{warpHTML}

```

## 50 Starting HTML output

**for HTML output:** 4328 \begin{warpHTML}

\LWR@LwarpStart Executed at the beginning of the entire document.

```

4329 \catcode`\$=\active
4330 \newcommand*{\LWR@LwarpStart}{%
4331 {%
4332 \LWR@traceinfo{LWR@l warpStart}}

```

If formatting for a word processor, force filedepth to single-file only, force HTML debug comments off.

```

4333 \ifbool{FormatWordProcessor}{%
4334     \setcounter{FileDepth}{-5}%
4335     \boolexpr{HTMLDebugComments}%
4336 }{%

```

Expand and detokenize \HomeHTMLFilename and \HTMLFilename:

```

4337 \edef\LWR@strresult{\HomeHTMLFilename}
4338 \edef\HomeHTMLFilename{\detokenize\expandafter{\LWR@strresult}}
4339 \edef\LWR@strresult{\HTMLFilename}
4340 \edef\HTMLFilename{\detokenize\expandafter{\LWR@strresult}}

```

Force onecolumn and empty page style:

```

4341 \LWR@origonecolumn%
4342 \LWR@origpagestyle{empty}

```

Reduce chance of line overflow in verbatim environments:

```
4343 \LWR@origscriptsize%
```

In PDF output, don't allow line breaks to interfere with HTML tags:

```

4344 \LWR@origraggedright%
4345 \LetLtxMacro{\\"{\LWR@endofline}}%

```

Spread the lines for pdftotext to read them well:

```
4346 \linespread{1.3}%
```

For pdftotext to reliably identify paragraph splits:

```
4347 \setlength{\parindent}{0pt}
4348 \setlength{\parskip}{2ex}
```

For the lateximages record file:

```
4349 \immediate\openout\LWR@lateximagesfile=lateximages.txt
```

Removes space after the caption in the HTML:

```
4350 \setlength{\belowcaptionskip}{-3ex}
```

Redefine the plain page style to be empty when used by index pages:

```
4351 \renewcommand{\ps@plain}{}%
```

\centering Not used in the HTML environment:  
 \raggedleft  
 \raggedright 4352 \renewcommand\*{\centering}{}  
 4353 \renewcommand\*{\raggedleft}{}  
 4354 \renewcommand\*{\raggedright}{}%

Plug in some new actions. This is done just before the document start so that they won't be over-written by some other package.

Tabular:

```
4355 \LetLtxMacro{\LWR@origtabular}{\tabular}
4356 \LetLtxMacro{\LWR@origendtabular}{\endtabular}
4357 \LetLtxMacro{\tabular}{\LWR@tabular}
4358 \LetLtxMacro{\endtabular}{\endLWR@tabular}
```

Float captions:

```
4359 \let\LWR@origcaption\caption
```

Labels: \ltx@label is used in amsmath environments and is also patched by cleveref.

### Label in HTML

```
4360 \let\LWR@origltx@label\ltx@label
4361 \let\ltx@label\LWR@htmlmathlabel
```

Logos:

```
4362 \let\TeX\LWR@TeX
4363 \let\LaTeX\LWR@LaTeX
4364 \let\LuaTeX\LWR@LuaTeX
4365 \let\LuaLaTeX\LWR@LuaLaTeX
4366 \let\XeTeX\LWR@XeTeX
4367 \let\XeLaTeX\LWR@XeLaTeX
4368 \let\ConTeXt\LWR@ConTeXt
```

Not yet started any paragraph handling:

```
4369 \global\boolearn{LWR@doingapar}
4370 \global\boolearn{LWR@doingstartpars}
```

Start a new HTML file and a header:

```
4371 \LWR@traceinfo{LWR@lwarpStart: Starting new file.}
4372 \LWR@filestart{}
4373 \LWR@traceinfo{LWR@lwarpStart: Generating first header.}
4374 \LWR@htmltag{header}\LWR@orignewline
4375 \LWR@startpars
4376 \LWR@firstpagetop
4377 \LWR@stoppars
4378 \LWR@htmltag{/header}\LWR@orignewline
4379 \LWR@traceinfo{LWR@lwarpStart: Generating textbody.}
4380 \LWR@htmltag{section class="textbody"{}}
```

Document and page settings:

```
4381 \mainmatter
4382 \LWR@origpagenumbering{arabic}
```

Patch the `itemize`, `enumerate`, and `description` environments and `\item`. This works with the native `\TeX` environments, as well as those provided by `enumitem`, `enumerate`, and `paralist`.

```
4383 \LWR@patchlists
```

Ensure that math mode is active to call lwarp's patches:

```
4384 \catcode`$=\active
```

Allow HTML paragraphs to begin:

```
4385 \LWR@startpars
4386 \LWR@traceinfo{LWR@lwarpStart: done}
4387 }
4388 \catcode`$=3% math shift until lwarp starts
```

---

```
4389 \end{warpHTML}
```

## 51 Ending HTML output

**for HTML output:** 4390 \begin{warpHTML}

\LWR@requesttoc {<boolean>} {<suffix>} Requests that a toc, lof, or lot be generated.

```
4391 \newcommand*{\LWR@requesttoc}[2]{%
4392 \ifbool{#1}{%
4393 {%
4394     \expandafter\newwrite\csuse{tf@#2}%
4395     \immediate\openout \csuse{tf@#2} \jobname.#2\relax%
4396 }{}%
4397 }
```

\LWR@LwarpEnd Final stop of all HTML output:

```
4398 \newcommand*{\LWR@LwarpEnd}{%
4399 {%
4400 \LWR@stopars%
4401 \LWR@closeprevious{\LWR@depthfinished}}
```

At the bottom of the ending file:

Close the textbody:

```
4402 \LWR@htmlelementclassend{section}{textbody}
```

Print any pending footnotes:

```
4403 \LWR@printpendingfootnotes
```

Create the footer:

```
4404 \LWR@htmlelement{footer}%
4405 %
4406 \LWR@pagebottom%
4407 %
4408 \LWR@htmlelementend{footer}
```

No bottom navigation if are finishing the home page, or if formatting for an EPUB or word processor.

Presumably has a table-of-contents.

```
4409 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWordProcessor}}
4410 {}
4411 {
4412     \ifnumcomp{\value{LWR@htmfilename}}{>}{0}{\LWR@botnavigation}{}
4413 }

4414 \LWR@stoppars% final stop of all paragraphs
```

Finish the HTML file:

```
4415 \LWR@htmtag{/body}\LWR@orignewline
4416 \LWR@htmtag{/html}\LWR@orignewline
```

Seems to be required sometimes:

```
4417 \LWR@orignewpage
```

For `\teximage` commands:

```
4418 \immediate\closeout\LWR@teximagesfile
4419 }

4420 \end{warpHTML}
```

## 52 Title page

**package support** lwarp supports the native L<sup>A</sup>T<sub>E</sub>X titling commands, and also supports the packages `authblk` and `titling`. If both are used, `authblk` should be loaded before `titling`.

**\published and \subtitle** If using the `titling` package, additional titlepage fields for `\published` and `\subtitle` may be added by using `\AddSubtitlePublished` in the preamble. See section 52.7.

**affiliation** lwarp provides for the `\author` macro an additional `\affiliation` macro to provide an affiliation and other additional information for each author in the title page. The affiliation information is removed when using `titlingpage`'s `\theauthor` in the main text.

**reusing titlepage information** The `titling` package maintains the definitions of `\thetitle`, `\theauthor`, etc., after the title has been typeset. These commands are to be used to refer to the document's title and author, etc., in the main text. These definitions have the `\thanks` and `\affiliation` removed, and for `\author` the `\and` is replaced to generate a simple inline list of authors separated by commas. Note: `\theauthor` does not work well with `authblk` unless the traditional L<sup>A</sup>T<sub>E</sub>X syntax is used.

 `\theauthor, authblk`

- custom titlepages** `\printtitle, \printauthor, etc.`, are provided for use inside a custom `titlepage` or `titlingpage` environment, and these retain the `\thanks` and `\affiliation`.
- \printthanks** `\printthanks` has been added to force the printing of thanks inside a `titlingpage` environment when `\maketitle` is not used.
- ⚠** Inside a `\titlepage` or `\titlingpage` environment, use `\thanks` instead of `\footnote` for acknowledgements, etc.

## 52.1 Setting the title, etc.

The following provide setting commands for both `HTML` and print outputs.

- \author** `{<author>}` While using `\maketitle` and print mode, the author is treated as a single-column tabular and the `\and` feature finishes the current tabular then starts a new one for the next author. Each author thus is placed into its own tabular, and an affiliation may be placed on its own line such as
- ```
\author{Name \\ Affiliation \and Second Name \\ Second Affiliation}
```
- For `HTML`, the entire author block is placed inside a `<div>` of class `author`, and each individual author is inside a `<div>` of class `oneauthor`.
- \@title** `\@title, \@author, etc.` store the values as originally assigned, including any `\thanks, \and, or \affiliation`. These are low-level macros intended to be used by other macros only inside a `titlepage` or `titlingpage`, and are used by `\maketitle`. The author is printed inside a single-column tabular, which becomes multiple single-column tabulars if multiples authors are included. For `HTML` these tabulars become side-by-side `<div>`s of class `oneauthor`, all of which are combined into one `<div>` of class `author`.
- \printtitle** `\printtitle, etc.` are user-level macros intended to be used in custom `titlepage` or `titlingpage` environments in cases where `\maketitle` is not desired. These `\printdate` commands preserve the `\thanks, etc.,` and should not be used in the main text.
- \thetitle** `\thetitle, \theauthor, and \thedate` are available if `titling` has been loaded, and are sanitized user-level versions from which have been removed the `\thanks` and `\affiliation`, and `\and` is changed for inline text usage. The author is printed inline without `\affiliation` or `\thanks`, with `\and` placing commas between multiple authors. Thus, these commands are to be used in the main text whenever the user wishes to refer to the document's title and such. One practical use for this is to place the authors at the bottom of each `HTML` page, such as:
- ```
\HTMLPageBottom {<text>}
```

---

```
\HTMLPageBottom{
```

---

```
\begin{center}\textcopyright~2016 \theauthor\end{center}
}
```

---

⚠ **\theauthor** `\theauthor` does not work well if `authblk` is used. If `\theauthor` is important, it is recommended to use the standard L<sup>A</sup>T<sub>E</sub>X syntax for `\author`, optionally with `lwarp`'s `\affiliation` macro as well.

⚠ **affiliations** After `\maketitle` has completed, `\theauthor` retains the definition of the author, but `\and` is changed to become a comma and a space, intending to print the authors names separated by spaces. This fails when affiliations are included on their own table rows.

**\affiliation** A solution, provide here, is to define a macro `\affiliation` which, during `\maketitle`, starts a new row and adds the affiliation, but after `\maketitle` is finished `\affiliation` is re-defined to discard its argument, thus printing only the author names when `\author` is later used inline.

## 52.2 Changes for `\affiliation`

**\affiliation** `{<text>}`

Adds the affiliation to the author for use in `\maketitle`.

Inside `titlepage`, this macro prints its argument. Outside, it is null.

**for HTML & PRINT:** 4421 `\begin{warpall}`  
4422 `\newrobustcmd{\affiliation}[1]{}`  
4423 `\end{warpall}`

**for PRINT output:** 4424 `\begin{warpprint}`  
  
4425 `\AtBeginEnvironment{titlepage}{`  
4426 `\renewrobustcmd{\affiliation}[1]{\textsc{\small#1}}`  
4427 `}`  
4428  
4429 `\AtBeginDocument{`  
4430 `@ifpackageloaded{titling}{`  
4431 `\AtBeginEnvironment{titlingpage}{`  
4432 `\renewrobustcmd{\affiliation}[1]{\textsc{\small#1}}`  
4433 `}`  
4434 `}{}% titling loaded`  
4435 `}% AtBeginDocument  
  
4436 \end{warpprint}  
  
for HTML output: 4437 \begin{warpHTML}`

Env `titlepage` Sets up a `<div>` of class `titlepage`.

```

4438 \renewenvironment*{titlepage}
4439 {
4440 \renewrobustcmd{\affiliation}[1]{\InlineClass{affiliation}{##1}}
4441 \LWR@printpendingfootnotes
4442 \LWR@forcenewpage
4443 \BlockClass{titlepage}
4444 }
4445 {
4446 \endBlockClass
4447 \LWR@printpendingfootnotes
4448 }

4449 \end{warpHTML}

```

### 52.3 Printing the thanks

**for HTML & PRINT:** 4450 `\begin{warpall}`

`\printthanks` Forces the `\thanks` to be printed.

This is necessary in a `titlingpage` environment when `\maketitle` was not used.

```

4451 \newcommand*{\printthanks}{\@thanks}
4452 \end{warpall}

```

### 52.4 Printing the title, etc. in HTML

The following are for printing the title, etc. in a `titlepage` or a `titlingpage` in HTML:

**for HTML output:** 4453 `\begin{warpHTML}`

```

\printtitle

4454 \newcommand*{\printtitle}
4455 {
4456 \LWR@stopars
4457 \LWR@htmlltag{h1}%
4458 \@title%
4459 \LWR@htmlltag{/h1}
4460 \LWR@startpars
4461 }

```

\LWR@printthetitle A private version which prints the title without footnotes, used to title each HTML page.

```
4462 \newcommand*\{\LWR@printthetitle\}
4463 {
4464 \LWR@stoppars
4465 \LWR@htmlltag{h1}%
4466 \thetitle%
4467 \LWR@htmlltag{/h1}
4468 \LWR@startpars
4469 }
```

\printauthor HTML version.

```
4470 \newcommand*\{\printauthor\}{
```

The entire author block is contained in a <div> named author:

```
4471 \begin{BlockClass}{author}
```

\and finishes one author and starts the next:

```
4472 \renewcommand{\and}{%
4473 \end{BlockClass}
4474 \begin{BlockClass}{oneauthor}
4475 }
```

Individual authors are contained in a <div> named oneauthor:

```
4476 \begin{BlockClass}{oneauthor}
4477 @author
4478 \end{BlockClass}
4479 \end{BlockClass}
4480 }
```

\printdate

```
4481 \newcommand*\{\printdate\}{%
4482 \begin{BlockClass}{titledate}
4483 @date
4484 \end{BlockClass}
4485 }
```

```
4486 \end{warpHTML}
```

## 52.5 Printing the title, etc. in print form

The following are for printing the title, etc. in a `titlepage` or a `titlingpage` in print form:

**for PRINT output:** 4487 `\begin{warpprint}`

`\printtitle`

4488 `\newcommand*{\printtitle}{\Huge\titler}`

`\printauthor` Print mode.

4489 `\newcommand*{\printauthor}`

4490 `{\large\begin{tabular}[t]{c}\author\end{tabular}}`

`\printdate`

4491 `\newcommand*{\printdate}{\small\textrit{\@date}}`

4492 `\end{warpprint}`

## 52.6 \maketitle for HTML output

An HTML `<div>` of class `titlepage` is used.

`\thanks` are a form of footnotes used in the title page. See section 45 for other kinds of footnotes.

See `\thanksmarkseries{series}`, below, to set the style of the footnote marks.

**for HTML output:** 4493 `\begin{warpHTML}`

4494 `\if@titlepage`

4495 `\newcommand{\LWR@setfootnoteseries}{%`

4496 `\renewcommand{\thefootnote}{\@arabic\c@footnote}%`

4497 `}`

4498 `\else`

4499 `\newcommand{\LWR@setfootnoteseries}{%`

4500 `\renewcommand{\thefootnote}{\@fnsymbol\c@footnote}%`

4501 `}`

4502 `\fi`

\LWR@maketitlesetup Patches \thanks macros.

```
4503 \newcommand*{\LWR@maketitlesetup}{%
```

Redefine the footnote mark:

```
4504 \LWR@setfootnoteseries%
4505 \def\@makefnmark{\textsuperscript{\thefootnote}}
```

```
\thefootnote \Rightarrow \nameuse{arabic}{footnote}, or
\thefootnote \Rightarrow \nameuse{fnsymbol}{footnote}
```

Redefine the footnote text:

```
4506 \long\def\@makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```
4507 \textsuperscript{\@thefnmark} \LWR@orighspace{1in}
```

```
\makethanksmark \Rightarrow \thanksfootmark \Rightarrow \tamark \Rightarrow
\@thefnmark \Rightarrow \itshape a (or similar)
```

Print the text:

```
4508 ##1%
4509 }%
4510 }
```

\@fnsymbol {\langle counter\rangle}

Re-defined to use an HTML entity for the double vertical bar symbol. The original definition used \| which was not being seen by pdftotext.

```
4511 \def\@fnsymbol#1{\ifcase#1\or *\or \HTMLentity{dagger}\or \HTMLentity{Dagger}\or
4512   \HTMLentity{sect}\or \HTMLentity{para}\or \text{\HTMLunicode{2016}}\or
4513   **\or \HTMLentity{dagger}\HTMLentity{dagger}\or
4514   \HTMLentity{Dagger}\HTMLentity{Dagger}\else\@ctrerr\fi}
```

\maketitle HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the titling package is adapted, simplified, and modified for HTML output.

```
4515 \renewcommand*{\maketitle}{%
```

An HTML titlepage <div> is used for all classes.

```
4516 \begin{titlepage}
```

Set up special patches:

```
4517 \LWR@maketitlesetup
```

Typeset the title, etc:

```
4518 \@maketitle
```

Immediately generate any \thanks footnotes:

```
4519 \@thanks
```

Close the HTML titlepage div and cleanup:

```
4520 \end{titlepage}
4521 \setcounter{footnote}{0}%
4522 \global\let\thanks\relax
4523 \global\let\maketitle\relax
4524 \global\let \@maketitle\relax
4525 \global\let \@thanks\@empty
4526 \global\let \@author\@empty
4527 \global\let \@date\@empty
4528 \global\let \@title\@empty
4529 \global\let \@title\relax
4530 \global\let \@author\relax
4531 \global\let \@date\relax
4532 \global\let \and\relax
4533 }
```

\@maketitle HTML mode. Typesets the title, etc.:

```
4534 \DeclareDocumentCommand{\@maketitle}{}{%
4535   \LWR@stopars\LWR@htmltag{h1}
4536   \@title
4537   \LWR@htmltag{/h1}\LWR@startpars
4538   \begin{BlockClass}{author}
4539     \renewcommand{\and}{%
4540       \end{BlockClass}
4541       \begin{BlockClass}{oneauthor}
4542     }
4543     \begin{BlockClass}{oneauthor}
4544       \@author
4545     \end{BlockClass}
4546   \end{BlockClass}}
```

---

```
4547     \begin{BlockClass}{titledate}
4548     \@date
4549     \end{BlockClass}
4550 }
```

\LWR@titlingmaketitle \maketitle for use inside an `HTML titlingpage` environment.

```
4551 \newcommand*{\LWR@titlingmaketitle}{%
```

Keep pending footnotes out of the title block:

```
4552 \@thanks
```

Set up special patches:

```
4553 \LWR@maketitlesetup
```

Typeset the title, etc:

```
4554 \@maketitle
```

Immediately generate any `\thanks` footnotes:

```
4555 \@thanks
4556 }
```

```
4557 \end{warpHTML}
```

## 52.7 \published and \subtitle

**\subtitle and \published** To add `\subtitle` and `\published` to the `titlepage`, load the `titling` package and use `\AddSubTitlePublished` in the preamble.

The default `lwarp.css` has definitions for the `published` and `subtitle` classes.

After `titling` is loaded, `\AddSubTitlePublished` is created, which when used then creates a number of additional macros, and also assigns some of the `titling` hooks.

**⚠ titling hooks** Do not use `\AddSubTitlePublished` if the user has patched the `titling` hooks for some other reason. Portions are marked `\warpprintonly` to reduce extra tags in `HTML`. Similarly, `BlockClass` has no effect in print mode. Thus, the following may be marked `warpall`.

**for HTML & PRINT:** 4558 `\begin{warpall}`

\AddSubtitlePublished Adds \published and \subtitle, and related.

```

4559 \AfterPackage{titling}%
4560 \newcommand*\AddSubtitlePublished{%
4561
4562 \newcommand{\@published}{}
4563
4564 \newcommand{\published}[1]{\gdef\@published{##1}}
4565
4566 \renewcommand*{\maketitlehooka}{\printpublished}
4567
4568 \newcommand*{\printpublished}{%
4569 \warpprintonly{\begin{center}\unskip}%
4570 \begin{BlockClass}{published}%
4571 \warpprintonly{\large\itshape}%
4572 \@published%
4573 \end{BlockClass}%
4574 \warpprintonly{\end{center}}%
4575 }
4576
4577 \newcommand{\@subtitle}{}
4578
4579 \newcommand{\subtitle}[1]{\gdef\@subtitle{##1}}
4580
4581 \renewcommand*{\maketitlehookb}{\prints_subtitle}
4582
4583 \newcommand*{\prints_subtitle}{%
4584 \warpprintonly{\begin{center}\unskip}%
4585 \begin{BlockClass}{subtitle}%
4586 \warpprintonly{\Large\itshape}%
4587 \@subtitle%
4588 \end{BlockClass}%
4589 \warpprintonly{\end{center}}%
4590 }
4591
4592 }% \AddSubtitlePublished
4593 }% AfterPackage

4594 \end{warpall}

```

## 53 Abstract

The following code replaces the L<sup>A</sup>T<sub>E</sub>X default, and will itself be replaced later if the abstract package is loaded.

**for HTML output:** 4595 \begin{warpHTML}

\abstractname User-redefinable title for the abstract.  
 Also over-written by the babel package.

4596 \providecommand\*\{\abstractname\}{Abstract}

```
Env  abstract

4597 \DeclareDocumentEnvironment{abstract}{}{%
4598 {%
4599 \LWR@forcenewpage%
4600 \BlockClass{abstract}%
4601 \BlockClassSingle{abstracttitle}{\abstractname}%
4602 }%
4603 {%
4604 \endBlockClass%
4605 }%
4606 \end{warpHTML}
```

## 54 Quote and verse

### 54.1 Citations and attributions

\attribution for use inside quote, quotation, verse:

ex: \attribution{author name} --- \citetitle{book name}

**for HTML output:** 4607 \begin{warpHTML}  
 4608 \newcommand{\attribution}[1]{%  
 4609 \InlineClass{\attribution}{--\,\#1}}% emdash  
 4610 \end{warpHTML}

**for PRINT output:** 4611 \begin{warpprint}  
 4612 \newcommand{\attribution}[1]{\textsc{---\,\#1}}  
 4613 \end{warpprint}

\citetitle for use inside quote, quotation, verse:

**for HTML output:** 4614 \begin{warpHTML}  
 4615 \newcommand{\citetitle}[1]{%  
 4616 \InlineClass{\citetitle}{--\,\#1}}% emdash  
 4617 \end{warpHTML}

```
for PRINT output: 4618 \begin{warpprint}
4619 \newcommand{\citetitle}[1]{\textsf{---},#1}
4620 \end{warpprint}
```

## 54.2 Quotes, quotations

for HTML output: 4621 \begin{warpHTML}

```
Env quote
4622 \renewenvironment*{quote}
4623 {
4624 \LWR@forcenewpage
4625 \LWR@htmlblocktag{blockquote}
4626 }
4627 {\LWR@htmlblocktag{/blockquote}}
4628
4629 \renewenvironment*{quotation}
4630 {
4631 \LWR@forcenewpage
4632 \LWR@htmlblocktag{blockquotation}
4633 }
4634 {\LWR@htmlblocktag{/blockquotation}}
4635 \end{warpHTML}
```

## 54.3 Verse

\attrib The documentation for the verse and memoir packages suggest defining an \attrib command, which may already exist in current documents, but it will only work for print output. lwarp provides \attribution, which works for both print and HTML output. To combine the two so that \attrib is used for print and \attribution is used for HTML:

---

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

---

Len \leftskip These lengths are used by verse and memoir to control the left margin, and they  
 Len \leftmargini may already be set by the user for print output. New lengths \HTMLvleftskip and  
 Len \TMLvleftskip  
 Len \TMLleftmargini

\HTMLleftmargini are provided to control the margins in HTML output. These new lengths may be set by the user before any `verse` environment, and persist until they are manually changed again. One reason to change \HTMLleftmargini is if there is a wide \flagverse in use, such as the word “Chorus”, in which case the value of \HTMLleftmargini should be set to a wide enough length to contain “Chorus”. The default is wide enough for a stanza number.

Horizontal spacing relies on `pdftotext`'s ability to discern the layout (-layout option) of the text in the HTML-tagged PDF output. For some settings of \HTMLleftmargini or \HTMLleftskip the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

**for HTML & PRINT:** 4636 \begin{warpall}

The following lengths may be set in either print or HTML output, but are only used in HTML. This allows the user to set \vleftskip and \leftmargini for print output, and optionally select different values for HTML.

Len \TMLvleftskip Sets \vleftskip inside a `verse` environment in HTML.

```
4637 \newlength{\HTMLvleftskip}
4638 \setlength{\HTMLvleftskip}{1em}
```

Len \TMLleftmargini Sets \leftmargini inside a `verse` environment in HTML.

```
4639 \newlength{\HTMLleftmargini}
4640 \setlength{\HTMLleftmargini}{4.5em}
```

```
4641 \end{warpall}
```

## 55 Verbatim

**for HTML & PRINT:** 4642 \begin{warpall}

Len \VerbatimHTMLWidth Width to use in HTML `Verbatim` environment.

This width is used when placing line numbers to the right. Ignored during print output.

```
4643 \newlength{\VerbatimHTMLWidth}
4644 \setlength{\VerbatimHTMLWidth}{4in}
4645 \end{warpall}
```

**for HTML output:** 4646 \begin{warpHTML}

`Bool LWR@verbtags` Used to temporarily turn off verbatim tags while doing `\verbatiminput` in the HTML head.

```
4647 \newbool{LWR@verbtags}
4648 \booltrue{LWR@verbtags}
```

`\LWR@atbeginverbatim [⟨style⟩] {⟨class⟩}`

Encloses a verbatim environment with the given css class.

```
4649 \newcommand*{\LWR@atbeginverbatim}[2] []
4650 {%
```

Avoid excessive space between lines:

```
4651 \setlength{\parskip}{0ex} %
```

Stop generating HTML paragraph tags:

```
4652 \LWR@stoppars%
```

Create a new `pre` of the given class. The tags may temporarily be turned off for internal use, such as loading the MathJax script.

```
4653 \ifbool{LWR@verbtags}{%
4654     \LWR@htmltag{pre class="#2"
4655         \ifthenelse{\equal{#1}{}}{}{style="#1"}}
4656 }% pre
4657 }{}%
```

Use a mono-spaced font to preserve horizontal positioning. If horizontal alignment is important for the user, use a mono-spaced font in the css for the `verse` class.

Also turn off babel-french extra space before punctuation:

```
4658 \begingroup%
4659 \LWR@origtfamily%
4660 \LWR@FBcancel%
```

Do not produce HTML tags for `\hspace` inside a `verse` par. Restore plain `\hspace` functionality:

```
4661 \LetLtxMacro{\hspace}{\LWR@orighspace}%
4662 }
```

`\LWR@afterendverbatim` Finishes enclosing a verbatim environment.

```
4663 \newcommand*{\LWR@afterendverbatim}{%
```

Remove excess vertical space at the end of the pre:

```
4664 \endgroup%
4665 \unskip%
```

At the end of the environment, close the pre:

```
4666 \ifbool{LWR@verbtags}{\noindent\LWR@htmltag{/pre}}
4667
4668 }{}%
```

Resume regular paragraph handling:

```
4669 \LWR@startpars%
4670 }
```

\verbatiminput {<filename>}

Patch \verbatiminput to add HTML tags:

```
4671 \let\LWRV@origverbatim@input\verbatim@input
4672
4673 \renewcommand{\verbatim@input}[2]{%
4674 \ifbool{LWR@verbtags}{\LWR@forcenewpage}{}%
4675 \LWR@atbeginverbatim{Verbatim}\unskip\LWR@origvspace*{-\baselineskip}%%
4676 \LWRV@origverbatim@input{\#1}{\#2}%
4677 \unskip\LWR@origvspace*{-\baselineskip}\LWR@afterendverbatim%
4678 }
```

Env verbatim

```
4679 \AfterEndPreamble{
4680 \LWR@traceinfo{Patching verbatim.}
4681 \AtBeginEnvironment{verbatim}{%
4682 \LWR@forcenewpage
4683 \LWR@atbeginverbatim{verbatim}\unskip\LWR@origvspace*{-\baselineskip}%
4684 }
4685 \AfterEndEnvironment{verbatim}{\unskip\LWR@origvspace*{-\baselineskip}\LWR@afterendverbatim}
4686 }

4687 \end{warpHTML}
```

## 56 Theorems

\newtheorem {<text>} [<counter>] -or- [<oldname>] {<text>}

A few minor changes are made to supply HTML tags.

- The entire theorem is placed into a <div> of class theoremcontents.
- The label for each theorem is placed inside a <span> of class theoremlabel.
- The contents are placed inside a <div> of class theoremcontents.

**for HTML output:** 4688 \begin{warpHTML}

```
\@begintheorem {⟨name⟩} {⟨number⟩}

4689 \renewcommand{\@begintheorem}[2]{%
4690 \LWR@forcenewpage
4691 \BlockClass{theoremcontents}
4692 \InlineClass{theoremlabel}{#1\ #2\ }%
4693 }

\@opargbegintheorem {⟨name⟩} {⟨number⟩} {⟨oparg⟩}

4694 \renewcommand{\@opargbegintheorem}[3]{%
4695 \LWR@forcenewpage
4696 \BlockClass{theoremcontents}
4697 \InlineClass{theoremlabel}{#1\ #2\ (#3)\ }%
4698 }

\@endtheorem

4699 \renewcommand*{\@endtheorem}{%
4700 \endBlockClass% theoremcontents
4701 }

4702 \end{warpHTML}
```

## 57 Lists

The environments `itemize`, `enumerate`, and `description` are patched when `lwarp` is started. These patches support the standard `LATEX` environments, as well as those of `enumerate`, `enumitem`, and `paralist`, and at least the French version of `babel`. Additional patches are done on a package-specific basis.

The `LATEX` source for `itemize` and `enumerate` are found in `source2e`, but the source for `description` is found in `article.cls`, etc.

**empty item** To have an empty item, use `\mbox{}` or a trailing backslash. This forces a new line in print output, matching the new line which will appear in HTML output. Ex:

---

```
begin{itemize}
item \mbox{}
\begin{itemize}
...
\end{itemize}
item \
\begin{itemize}
...
\end{itemize}
```

---

## 57.1 Itemize

**for HTML output:** 4703 `\begin{warpHTML}`

`\LWR@itemizeitem [<label>]`

Handles `\item` inside an itemize or enumerate.

See `\LWR@openparagraph` where extra `\hspace` is used to leave room for the label while inside a list during paragraph construction.

```
4704 \newcommand*{\LWR@itemizeitem}{%
4705 \LWR@stoppars%
4706 \LWR@startnewdepth{\LWR@depthlistitem}{\LWR@printcloselistitem{}}%
4707 \LWR@htmlltag{li}%
4708 \LWR@startpars%
4709 \LWR@origitem%
4710 }
```

**Env** `itemize [<options>]`

```
4711 \newcommand*{\LWR@itemizestart}{%
4712 \LWR@stoppars%
4713 \LWR@pushoneclose{\LWR@depthlist}{\LWR@printcloseitemize{}}%
4714 \LWR@htmlltag{ul style="list-style-type:none"}{}}%
4715 \LWR@startpars%
4716 \let\item\LWR@itemizeitem%
4717 }
4718
4719 \newcommand*{\LWR@itemizeend}{%
```

```

4720 \LWR@stoppars%
4721 \LWR@closeprevious{\LWR@depthlistitem}%
4722 \LWR@closeoneprevious{}%
4723 \LWR@startpars%
4724 }

```

## 57.2 Enumerate

An HTML unordered list is used with customized L<sup>A</sup>T<sub>E</sub>X-generated labels.

Env `enumerate` [*<options>*]

```

4725 \newcommand*{\LWR@enumeratestart}{%
4726 \LWR@stoppars%
4727 \LWR@pushoneclose{\LWR@depthlist}{\LWR@printcloseitemize{}}%
4728 \LWR@htmlltag{ul style="list-style-type:none"}{%
4729 \LWR@startpars%
4730 \let\item\LWR@itemizeitem%
4731 }
4732
4733 \newcommand*{\LWR@enumerateend}{%
4734 \LWR@stoppars%
4735 \LWR@closeprevious{\LWR@depthlistitem}%
4736 \LWR@closeoneprevious{}%
4737 \LWR@startpars%
4738 }

```

## 57.3 Description

`\LWR@descitem` [*<label>*] Handles an `\item` inside a description.

```

4739 \newcommand*{\LWR@descitem}[1] []%
4740 {%
4741 \LWR@stoppars%
4742 \LWR@setlatestname{#1}%
4743 \LWR@startnewdepth{\LWR@depthlistitem}{\LWR@printclosedescitem{}}%

```

Temporarily disable `\hspace`, which `article.cls`, etc. use per `\item` for descriptions only. This causes `l warp` to mistakenly place an empty span between HTML list tags.

```
4744 \LetLtxMacro{\hspace}{\LWR@nohspace}%
```

Process the original \item code:

```
4745 \LWR@origitem[]%
```

Restore \hspace for use in the item text:

```
4746 \LetLtxMacro{\hspace}{\LWR@hspace}%
```

Be sure the label doesn't print to the left of the rest of the file:

```
4747 \LWR@orighspace{in}
4748 \LWR@htmlltag{dt}#1\LWR@htmlltag{/dt}%
4749 \LWR@orignewline%
4750 \LWR@htmlltag{dd}%
4751 \LWR@startpars%
4752 }
```

`Env description [⟨options⟩]`

```
4753 \newcommand*{\LWR@descriptionstart}{%
4754 \LWR@stoppars%
4755 \LWR@pushoneclose{\LWR@depthlist}{\LWR@printclosedescription{}}%
4756 \LWR@htmlltag{dl}%
4757 \LWR@startpars%
4758 \let\item{\LWR@descitem}%
4759 }
4760
4761 \newcommand*{\LWR@descriptionend}{%
4762 \LWR@stoppars%
4763 \LWR@closeprevious{\LWR@depthlistitem}%
4764 \LWR@closeoneprevious{}%
4765 \LWR@startpars%
4766 }
```

`\LWR@patchlists` Patches list environments.

`\LWR@patchlists` remembers `\item` as defined by whatever packages have been loaded, then patches the `itemize`, `enumerate`, and `description` environments and `\item`. This works with the native L<sup>A</sup>T<sub>E</sub>X environments, as well as those provided by `enumitem`, `enumerate`, and `paralist`.

```
4767 \newcommand*{\LWR@patchlists}{%
4768 \LetLtxMacro{\LWR@origitem}{\item}
4769 \AtBeginEnvironment{itemize}{\LWR@itemizestart}
4770 \AtEndEnvironment{itemize}{\LWR@itemizeend}
4771 \AtBeginEnvironment{enumerate}{\LWR@enumeratestart}
4772 \AtEndEnvironment{enumerate}{\LWR@enumerateend}
```

---

```

4773 \AtBeginEnvironment{description}{\LWR@descriptionstart}
4774 \AtEndEnvironment{description}{\LWR@descriptionend}
4775 }

4776 \end{warpHTML}

```

## 58 Tabular

This is arguably the most complicated part of the entire package. Numerous tricks are employed to handle the syntax which is involved.

### 58.1 Limitations

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, \* column specifiers, siunitx S columns, or the packages multirow, longtable, supertabular, or xtab.

#### Defining environments:

⚠ misplaced alignment  
alignment tab character &

- When defining environments or macros which include tabular and instances of the & character, it may be necessary to make & active before the environment or macro is defined, then restore & to its default catcode after, using the following commands. These are ignored in print mode.

```

\StartDefiningTabulars
<define macros or environments using tabular and &
here>
\EndDefiningTabulars

```

⚠ tabular inside another  
environment

- When creating a new environment which contains a tabular environment, lwarf's emulation of the tabular does not automatically resume when the containing environment ends, resulting in corrupted HTML rows. To fix this, use \ResumeTabular as follows. This is ignored in print mode.

```
\StartDefiningTabulars % because & is used in a
definition
\newenvironment{outerenvironment}
{
\begin{tabular}{cc}
left & right \\
\end{tabular}
}
{
\TabularMacro\ResumeTabular
left & right \\
\end{tabular}
}
\EndDefiningTabulars
```

**Cell contents:****⚠️ paragraphs**

- Multiple paragraphs in one cell of a p, b, m column must have \newline between paragraphs.

**⚠️ \multirow**

- For multirow, insert \mrowcell into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output.

```
... & \multirow{2}{.5in}{text} & ...
... & \mrowcell & ...
```

**vposn**

Note that recent versions of multirow include a new optional vposn argument.

- The multirow documentation regarding colored cells recommends using a negative number of rows. This will not work with l warp, so \warpprintonly and \warpHTMLonly must be used to make versions for print and HTML.
- See section 174.2 for \multicolumnrow.

l warp does not support directly combining \multicolumn and \multirow. Use \multicolumnrow instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}{c}{3}{0}{1in}[0pt]{Text}
```

The two arguments for \multicolumn come first, followed by the five arguments for \multirow, many of which are optional, followed by the contents.

**⚠️ skipped cells**

As per \multirow, skipped cells to the right of the \multicolumnrow statement are not included in the source code on the same line. On the following lines, \mcolrowcell must be used for each cell of each column and each row to be skipped:

```
... & \multicolumnrow{2}{c}{c}{3}{0}{1in}[0pt]{Text} & ...
... & \mcolrowcell & \mcolrowcell & ...
... & \mcolrowcell & \mcolrowcell & ...
```

**⚠️ empty cells**

**vposn**

Note that recent versions of multirow include a new optional vposn argument.

**⚠ macro in a table  
custom macros**

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use \TabularMacro just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \\
```

**Column specifiers:**

**⚠ \* column specification**

- \* in a column specification is not used (so far). Repeat the column type the correct number of times.

**@ and !**

- Only one each of @ and ! is used at each column, and they are used in that order.

**\multirow**

- In \multirow cells, the print version may have extra instances of <, >, @, and ! cells on the second and later rows in the \multirow which do not appear in the HTML version.

**⚠ \newcolumntype**

- \newcolumntype is ignored; unknown column types are set to 1.

**Rules:**

**vertical rules**

- Vertical rules next to either side of an @ or ! column are displayed on both sides of the column.

**width and trim**

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with @ or ! columns, and full-width rules ignore trim.

**full-width rules**

- \toprule, \midrule, \bottomrule, and \hline ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

**combined rules**

- If you wish to use \cmidrule followed by \bottomrule, it may be necessary to use:

```
\cmidrule{2-3} \\[-2ex]
\bottomrule
```

The optional -2ex is ignored in HTML but improves the visual formatting in the print output.

**⚠ \warpprintonly  
misplaced \noalign**

- For \toprule and \bottomrule, when combined with a warpprint or warpHTML environment, if a “misplaced \noalign” error occurs, change

```
This & That \endhead
```

to

```
\warpprintonly{This & That \endhead}
```

and likewise with the other \end headings. Keep the \endfirsthead row unchanged, as it is still relevant to HTML output.

**Other:**

- tabularx ignores the width, but X columns do produce paragraph columns or multicolumns.
- `longtable` headings
- For longtable, place headings and footings which do not apply to HTML inside `\warpprintonly{}`.
- ⚠ `S` columns
- For S columns (from the siunitx package), while producing print output, anything non-numeric must be placed inside {} braces, including commands such as `\multirow`. While producing HTML output, though, anything placed inside braces is not seen by lwarp's tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:
- ```
\warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
\warpHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
```

## 58.2 Token lookahead

Used by `\LWR@futureonospacelet` to look at the next token.

**for HTML output:** 4777 `\begin{warpHTML}`

`\LWR@mynexttoken`

4778 `\newcommand{\LWR@mynexttoken}{\relax}`

`\futurelet` copies the next token then executes a function to analyze

`\LWR@futureonospacelet` does the same, but ignores intervening white space

Based on the booktabs style:

`\LWR@futureonospacelet`

```
4779 \def\LWR@futureonospacelet#1{\def\LWR@cs{#1}%
4780 \afterassignment\LWR@fnalone\let\nexttoken= }
4781 \def\LWR@fnalone{\expandafter\futurelet\LWR@cs\LWR@fnsltwo}%
4782 \def\LWR@fnsltwo{%
4783 \expandafter\ifx\LWR@cs\@spoken\let\next=\LWR@fnslthree\%
4784 \else\let\next=\nexttoken\fi\next}
4785 \def\LWR@fnslthree{\afterassignment\LWR@fnalone\let\next= }
```

`\LWR@getmynexttoken` Looks ahead and copies the next token into `\LWR@mynexttoken`.

4786 `\newcommand*{\LWR@getmynexttoken}{%`

---

```

4787 \LWR@traceinfo{\LWR@getmynexttoken}%
4788 % nothing must follow this next line
4789 \LWR@futureonospacelet\LWR@mynexttoken\LWR@tabledatacolumnntag
4790 }

```

### 58.3 Booleans

Bool `LWR@startedrow` True if should print a row tag before this column.

```

4791 \newbool{\LWR@startedrow}
4792 \boolfalse{\LWR@startedrow}

```

Bool `LWR@doinghline` True if the next row will have an hline or midrule above it. Also used for `\midrule`.

```

4793 \newbool{\LWR@doinghline}
4794 \boolfalse{\LWR@doinghline}

```

Bool `LWR@doingtbrule` True if the next row will have a top/bottom rule above it.

```

4795 \newbool{\LWR@doingtbrule}
4796 \boolfalse{\LWR@doingtbrule}

```

Bool `LWR@doingcmidrule` True if the next row will have a cmidrule above it.

This is used by `\LWR@tabularfinishrow` to force a final empty row to create the border for the `\cmidrule`.

```

4797 \newbool{\LWR@doingcmidrule}
4798 \boolfalse{\LWR@doingcmidrule}

```

Bool `LWR@tableparcell` True if are handling a paragraph inside a table cell, so must close the paragraph tag before moving on.

```
4799 \newbool{\LWR@tableparcell}
```

Bool `LWR@skippingmrowcell` True if are doing an empty `\multirow` cell, and thus there is no data tag to close.

```
4800 \newbool{\LWR@skippingmrowcell}
```

Bool `LWR@skippingmcolrowcell` True if are doing an empty `\multicolumn` cell, and thus there is no data tag to close, and do not print @ and ! columns.

```
4801 \newbool{\LWR@skippingmcolrowcell}
```

Bool `LWR@skipatbang` True if just finished a `\multicolumn` so should not create the trailing @ or ! columns

table data cells.

```
4802 \newbool{LWR@skipatbang}
```

Bool LWR@emptyatbang True if finishing a row and should print empty @ or ! column table data cells.

```
4803 \newbool{LWR@emptyatbang}
```

Bool LWR@intabularmetadata True if are in a tabular but not in a data cell. Used to prevent extra HTML breaks if not inside table data.

```
4804 \newbool{LWR@intabularmetadata}
```

```
4805 \boolfalse{LWR@intabularmetadata}
```

## 58.4 Handling &, @, !, and bar

For technical discussion regarding problems redefining \&, See:

<http://tex.stackexchange.com/questions/11638/where-do-i-find-futurelets-nasty-behaviour-documented/11860#11860>

```
\LWR@instertatbangcols
```

```
4806 \newcommand*{\LWR@insertatbangcols}{%
4807 \ifbool{LWR@skipatbang}{%
4808 {}{%
4809 {}{%
4810   \LWR@printatbang{at}{\theLWR@tablecolspos}{%
4811   \LWR@printatbang{bang}{\theLWR@tablecolspos}{%
4812 }{%
4813 }}
```

\LWR@closetabledatacell If LWR@skippingmrowcell or LWR@skippingmcolrowcell then there is no data tag to close. Otherwise, close any paragraphs, then close the data tag.

```
4814 \newcommand*{\LWR@closetabledatacell}{%
4815 \global\booltrue{LWR@intabularmetadata}{%
4816 \ifbool{LWR@exittingtabular}{%
4817 {}{%
4818   \ifboolexpr{bool{LWR@skippingmrowcell} \or bool{LWR@skippingmcolrowcell}}{%
4819     {}{%
```

If not skipping a \multicolumnrow cell, insert the @ and ! columns after this non-existent column.

```

4820      \ifboolexpr{LWR@skippingmcolrowcell}%
4821      {}%
4822      {\LWR@insertatbangcols}%
4823      }%
4824      {%
4825      not skippingmrowcell

```

Insert any < then any @ and ! column contents, unless muted for the \bottomrule or a \multicolumn:

```

4825      \unskip%
4826      \ifboolexpr{%
4827          bool{LWR@tabularmutemods} or
4828          bool{LWR@skipatbang} or
4829          bool{LWR@emptyatbang}
4830      }%
4831      {}%
4832      {\LWR@getexpparray{LWR@col afterspec}{\theLWR@tablecolspos}}%

```

Close paragraphs:

```

4833      \ifboolexpr{LWR@tableparcell}{\LWR@stoppars}{}%
4834      \global\boolexfalse{LWR@tableparcell}%

```

Close the table data cell. Skip the @ and ! cells if are closing a multicolumn cell.

```

4835      \leavevmode\unskip\LWR@htmlltag{/td}\LWR@orignewline%
4836      \LWR@insertatbangcols%
4837      }%
4838      not skipping mrowcell
4839 \global\boolexfalse{LWR@skippingmrowcell}%
4840 \global\boolexfalse{LWR@skippingmcolrowcell}%
4841 \global\boolexfalse{LWR@skipatbang}%
4842 }

```

LWR@tabulardepth tracks whether & is being used inside a tabular.

```

4843 \newcounter{LWR@tabulardepth}
4844 \setcounter{LWR@tabulardepth}{0}
4845

```

When not used inside a tabular, & performs its original function as recorded here ( with catcode 4 ).

```

4846 \let\LWR@origampmacro&
4847 \end{warpHTML}

```

### 58.4.1 Localizing & catcodes

**for HTML & PRINT:** 4848 \begin{warpall}

**⚠ misplaced alignment tab character &** Place \StartDefiningTabulars and \EndDefiningTabulars before and after defining macros or environments which include the tabular & character in their definitions.

The catcode of & must be changed before the definitions begin, and must be restored afterwards. Doing so avoids the error

```
misplaced alignment tab character &
```

\StartDefiningTabulars Place before defining something with & in it.

```
4849 \newcommand{\StartDefiningTabulars}{%
4850 \LWR@traceinfo{StartDefiningTabulars}%
4851 \warpHTMLonly{\catcode`\&=\active}%
4852 }
```

\EndDefiningTabulars Place after defining something with & in it.

```
4853 \newcommand{\EndDefiningTabulars}{%
4854 \LWR@traceinfo{EndDefiningTabulars}%
4855 \warpHTMLonly{\catcode`\&=4}%
4856 }
```

```
4857 \end{warpall}
```

### 58.4.2 Handling &

**for HTML output:** 4858 \begin{warpHTML}

& Will behave depending on whether it is being used inside tabular.

& is redefined to test whether it is inside a tabular environment, in which case it performs special processing for HTML conversion. If not, it behaves normally.

```
4859 \newcommand*{\LWR@tabularampersand}{%
4860 \LWR@traceinfo{\LWR@tabularampersand}%
4861 \ifthenelse{\cnttest{\value{\LWR@tabulardepth}}{>}{}{0}}{%
4862 {}}
```

If not skipping a multirow cell, close the current data cell.

```
4863 \unskip%
4864 \LWR@closetabledatacell%
```

Move to the next column.

```
4865 \addtocounter{LWR@tablecolspos}{1}%
```

Look at the next token to decide multi or single column data tag.

```
4866 \LWR@getmynexttoken%
4867 }%
```

If not inside a tabular, performs the original action:

```
4868 {\LWR@origampmacro}%
4869 }
```

& is left with its original catcode for now.

tikz package seems to require & be left alone until after tikz has been loaded. Also, cleveref uses the ampersand in one of its options.

& is made active inside a tabular.

& is left alone when in math alignments.

#### 58.4.3 Filling an unfinished row

\LWR@tabularfinishrow Adds empty table cells if necessary to finish the row.

At the end of the table, if any bottom rules are requested then an empty row must be generated to form the borders which show the rules.

```
4870 \newcommand*{\LWR@tabularfinishrow}{%
```

If not exiting the tabular, or doing a rule, or have already started a row, finish this row:

```
4871 \ifboolexpr{%
4872   not \LWR@exittingtabular\ or%
4873   \LWR@doingtbrule\ or%
4874   \LWR@doingcmidrule\ or%
4875   \LWR@doingshline\ or%
4876   \LWR@startedrow\}%
4877 }{%
```

To locally temporarily turn off \LWR@exittingtabular so that table data tags will still be generated:

```
4878 \begingroup%
```

If generating a final row for the \bottomrule borders, turn off the @, !, <, and > column output:

```
4879 \ifbool{LWR@exittingtabular}{%
4880     \booltrue{LWR@tabularmutemods}%
4881 }{}%
```

Reenable the table data tags until finished with the final row:

```
4882 \boolfalse{LWR@exittingtabular}%
```

Generate table data tags and ampersands until the right edge:

```
4883 \whiledo{\value{LWR@tablecolspos}<\value{LWR@tabletotalcols}}{%
4884 \LWR@tabledatasinglecolumntag%
```

The following is essentially \LWR@tabularampersand with LWR@emptyatbang added to empty the following cells:

```
4885     \LWR@closetabledatacell%
4886     \addtocounter{LWR@tablecolspos}{1}%
4887     \global\booltrue{LWR@emptyatbang}%
```

Starts the next cell:

```
4888     \LWR@getmynexttoken%
4889 }%
```

Required to close the final cell:

```
4890 \LWR@closetabledatacell%
```

Reenable the original LWR@exittingtabular to close the entire table:

```
4891 \endgroup%
4892 \global\boolfalse{LWR@emptyatbang}%
4893 }{}% ifboolexpr
4894 }
```

## 58.5 Handling \\

Inside tabular, \\ is redefined to \LWR@tabularendofline

Throws away options \\[dim] or \\\*

```
\LWR@tabularendofline

4895 \NewDocumentCommand{\LWR@tabularendofline}{s o}
4896 {%
4897 \ifthenelse{\value{LWR@tablecolspos}<\value{LWR@tabletotalcols}}{%
4898     \LWR@tabularfinishrow%
4899 }%
4900 {%
4901     \LWR@closetabledatacell%
4902 }%
4903 %    \begin{macrocode}
4904 \LWR@htmlltag{/tr}\LWR@newline
4905 \global\booltrue{LWR@intabularmetadata}
```

Not yet started a table row:

```
4906 \global\boolfalse{LWR@startedrow}
```

Additional setup:

```
4907 \global\boolfalse{LWR@doinghline}%
4908 \global\boolfalse{LWR@doingtbrule}%
4909 \global\boolfalse{LWR@doingcmidrule}%
4910 \LWR@clearmidrules%
```

Start at first column:

```
4911 \setcounter{LWR@tablecolspos}{1}
```

Look at the next token to decide between single column data tag or a special case:

```
4912 \LWR@getmynexttoken%
4913 }
```

## 58.6 Variables

```
4914 \newcommand*{\LWR@colsresult}{}%temp storage for column format results
4915 \newcommand*{\LWR@pposition}{}%
4916 \newcommand*{\LWR@pleft}{}%
4917 \newcommand*{\LWR@pright}{}%
```

`\LWR@tablecolspec` Holds the parsed column specification, of total width `LWR@tabletotalcols`, not counting @ and ! columns.

Will contain a string such as `llrrccpc`, exactly one letter per  $\text{\TeX}$  table column, without @, !, >, <, or the vertical bar.

```
4918 \newcommand*{\LWR@tablecolspec}{}%
```

`\LWR@strresult` Holds the result of Str functions.

```
4919 \newcommand*{\LWR@strresult}{}%
4920 \newcommand*{\LWR@strresulttwo}{}%
```

`\LWR@origcolspec` Holds the original column specs given to `tabular`.

```
4921 \newcommand*{\LWR@origcolspec}{}%
```

Ctr `\LWR@tablecolwidth` Holds the width of the table columns specification.

This is the number of tokens, including one for each @ etc. column, and also one each for the parameters of p, @, etc. columns, and three for each D column.

(This is not the total # of  $\text{\TeX}$  columns in the table.)

```
4922 \newcounter{\LWR@tablecolwidth}
```

Ctr `\LWR@tablecolpos` Where are currently looking into the table column specification. Index starts at 1.

```
4923 \newcounter{\LWR@tablecolpos}
```

Ctr `\LWR@tabletotalcols` Holds the final number of table columns, not counting @ and ! columns. This is equal to the number of cells in each row.

```
4924 \newcounter{\LWR@tabletotalcols}
```

Ctr `\LWR@tabletotalcolsnext` Holds the next column while parsing. Is one more than `\LWR@tabletotalcols`.

```
4925 \newcounter{\LWR@tabletotalcolsnext}
```

`\LWR@colatspec` A data array of specifications for @ columns. The leftmost's index is `leftedge`, the others are counter values. See section 32.

`\LWR@colbangspec` A data array of specifications for ! columns. The leftmost's index is `leftedge`, the others are counter values. See section 32.

`\LWR@colbeforespec` A data array of specifications for > columns.

`\LWR@colafterspec` A data array of specifications for < columns.

`\LWR@colbarspec` A data array of specifications for vertical rules.

## 58.7 Parsing @, >, <, !, bar columns

Holds the parsed argument for @, >, <, or ! columns:

```
4926 \newcommand*{\LWR@colparameter}{}%
```

\LWR@parseatcolumn Handles @{text} columns.

```
4927 \newcommand*{\LWR@parseatcolumn}{%
```

Move to the next token after the '@':

```
4928 \LWR@traceinfo{at column}%
4929 \addtocounter{\LWR@tablecolspos}{1}%
```

Read the next token into \LWR@strresult, expanding once:

```
4930 \LWR@traceinfo{about to read the next token}%
4931 \expandarg%
4932 \StrChar{\LWR@origcolspec}{\the\LWR@tablecolspos}{\LWR@colparameter}
4933 \fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@strresult:

```
4934 \LWR@traceinfo{have now read the next token}%
4935 \ifthenelse{\cnttest{\value{\LWR@tabletotalcols}}=0}%
4936 {%
4937   \LWR@traceinfo{at the left edge}%
4938   \LWR@setexpparray{\LWR@colatspec}{leftedge}{\LWR@colparameter}%
4939   \LWR@traceinfo{at the left edge: \%}
4940   \LWR@getexpparray{\LWR@colatspec}{leftedge}%
4941 }%
4942 {%
4943   \LWR@traceinfo{not at the left edge}%
4944   \LWR@setexpparray{\LWR@colatspec}{\the\LWR@tabletotalcols}{\LWR@colparameter}%
4945   \LWR@traceinfo{at \the\LWR@tabletotalcols: \%}
4946   \LWR@getexpparray{\LWR@colatspec}{\the\LWR@tabletotalcols}%
4947 }%
4948 \let\LWR@colparameter\relax%
4949 \booltrue{\LWR@validtablecol}%
4950 }
```

\LWR@parsebangcolumn Handles !{text} columns.

```
4951 \newcommand*{\LWR@parsebangcolumn}{%
```

Move to the next token after the '!':

```
4952 \LWR@traceinfo{bang column}%
4953 \addtocounter{\LWR@tablecolspos}{1}%
```

Read the next token into \LWR@strresult, expanding once:

```
4954 \LWR@traceinfo{about to read the next token}%
4955 \expandarg%
4956 \StrChar{\LWR@origcolspec}{\the\LWR@tablecolspos}[\LWR@colparameter]
4957 \fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@strresult:

```
4958 \LWR@traceinfo{have now read the next token}%
4959 \ifthenelse{\cnttest{\value{\LWR@tabletotalcols}}=0}
4960 {%
  left edge of the table:
  \LWR@traceinfo{at the left edge}%
  \LWR@setexpparray{\LWR@colbangspec}{leftedge}{\LWR@colparameter}%
}%
4964 {%
  not at the left edge:
  \LWR@traceinfo{not at the left edge}%
  \LWR@setexpparray{\LWR@colbangspec}{\the\LWR@tabletotalcols}{\LWR@colparameter}%
  \LWR@traceinfo{bang \the\LWR@tabletotalcols: \LWR@colparameter!}%
}%
4968 }%
4969 \let\LWR@colparameter\relax%
4970 \booltrue{\LWR@validtablecol}%
4971 }
```

\LWR@parsebeforecolumn Handles >{text} columns.

```
4972 \newcommand*{\LWR@parsebeforecolumn}{%
```

Move to the next token after the '>':

```
4973 \addtocounter{\LWR@tablecolspos}{1}%
```

Read the next token, expanding once into \LWR@strresult:

```
4974 \expandarg%
4975 \StrChar{\LWR@origcolspec}{\the\LWR@tablecolspos}[\LWR@colparameter]%
4976 \fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@strresult:

```
4977 \LWR@setexpparray{\LWR@colbeforespec}{\the\LWR@tabletotalcolsnext}{\LWR@colparameter}%
4978 \let\LWR@colparameter\relax%
```

```
4979 \booltrue{LWR@validtablecol}%
4980 }
```

\LWR@parseaftercolumn Handles <{text} columns.

```
4981 \newcommand*\LWR@parseaftercolumn{%
```

Move to the next token after the '<':

```
4982 \addtocounter{LWR@tablecolspos}{1}%
```

Read the next token, expanding once into \LWR@strresult:

```
4983 % \StrChar{\theLWR@tablecolspos}[\LWR@colparameter]
4984 \expandarg%
4985 \StrChar{\LWR@origcolspec}{\theLWR@tablecolspos}[\LWR@colparameter]%
4986 \fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@strresult:

```
4987 \LWR@setexpparray{\LWR@col afterspec}{\theLWR@tabletotalcols}{\LWR@colparameter}%
4988 \let\LWR@colparameter\relax%
4989 \booltrue{LWR@validtablecol}%
4990 }
```

\LWR@parsebarcolumn Handles vertical rules.

```
4991 \newcommand*\LWR@parsebarcolumn{%
4992 \LWR@traceinfo{bar column}%
```

Remember the bar at this position:

```
4993 \ifthenelse{\cndtest{\value{\LWR@tabletotalcols}}=0}%
4994 {%
4995   \LWR@setexpparray{\LWR@colbarspec}{leftedge}{tvertbarl}%
4996 }%
4997 {%
4998   \LWR@setexpparray{\LWR@colbarspec}{\theLWR@tabletotalcols}{tvertbarr}%
4999 }%
5000 \booltrue{LWR@validtablecol}%
5001 }
```

## 58.8 Parsing 'l', 'c', or 'r' columns

\LWR@parsenormalcolumn {\langle thiscolumn\rangle}

Add to the accumulated column specs, advance counters, and pre-clear another column of at, before, and after specs.

```
5002 \newcommand*{\LWR@parsenormalcolumn}[1]{%
5003 \appto{\LWR@tablecolspec}{#1}%
5004 \addtocounter{\LWR@tabletotalcols}{1}%
5005 \addtocounter{\LWR@tabletotalcolsnext}{1}%
5006 \LWR@traceinfo{normal column \the\LWR@tabletotalcols: #1}%
5007 \LWR@setexpparray{\LWR@colatspec}{\the\LWR@tabletotalcolsnext}{}%
5008 \LWR@setexpparray{\LWR@colbangspec}{\the\LWR@tabletotalcolsnext}{}%
5009 \LWR@setexpparray{\LWR@colbeforespec}{\the\LWR@tabletotalcolsnext}{}%
5010 \LWR@setexpparray{\LWR@colafterspec}{\the\LWR@tabletotalcolsnext}{}%
5011 \LWR@setexpparray{\LWR@colbarspec}{\the\LWR@tabletotalcolsnext}{}%
5012 \booltrue{\LWR@validtablecol}%
5013 }
```

## 58.9 Parsing ‘p’, ‘m’, or ‘b’ columns

\LWR@parsepcolumn {*thiscolumn*} The width will be ignored.

```
5014 \newcommand*{\LWR@parsepcolumn}[1]{%
```

Converts to the given column type:

```
5015 \LWR@parsenormalcolumn{#1}%
```

Skips the following width token:

```
5016 \addtocounter{\LWR@tablecolspos}{1}%
5017 }
```

## 58.10 Parsing ‘D’ columns

From the `dcolumn` package.

\LWR@parseDcolumn {*thiscolumn*} The three parameters will be ignored.

```
5018 \newcommand*{\LWR@parseDcolumn}[1]{%
```

Converts to the given column type.

```
5019 \LWR@parsenormalcolumn{#1}%
```

Table 6: Tabular baseline

| l | p   | m   | b   | r |
|---|-----|-----|-----|---|
|   |     |     | bot |   |
|   |     | mid | bot |   |
| l | par | mid | bot | r |
|   | par | mid |     |   |
|   | par |     |     |   |

Skips the following three parameters.

```
5020 \addtocounter{LWR@tablecolspos}{3}%
5021 }
```

## 58.11 Parsing the column specifications



HTML CSS cannot exactly match the L<sup>A</sup>T<sub>E</sub>X concept of a baseline for a table row. Table 6 shows the L<sup>A</sup>T<sub>E</sub>X results for various vertical-alignment choices, with the baseline of the first column drawn across all the columns for comparison. See the p column specification in table 7 for details.

Table 7 describes how each kind of column is converted to HTML.

Bool LWR@validtablecol True if found a valid table column type.

```
5022 \newbool{LWR@validtablecol}
```

```
\LWR@parsetablecols {\langle colspecs\rangle}
```

Scans the column specification left to right.

Builds LWR@tablecolspec with the final specification, one column per entry. The final number of cells in each row is stored in LWR@tabletotalcols.

```
5023 \newcommand*{\LWR@parsetablecols}[1]{%
5024 \LWR@traceinfo{LWR@parsetablecols started}}%
```

Remember the original supplied column spec:

```
5025 \renewcommand*{\LWR@origcolspec}{#1}%
```

Table 7: Tabular HTML column conversions

- 
- l, r, c:** Converted to table cells without paragraph tags.  
Uses css `vertical-align:middle` so that top or bottom-aligned cells may go above or below this cell.
- p:** Converted to table cells with paragraph tags. Ref: Table 6, L<sup>A</sup>T<sub>E</sub>X places the top line of a parbox aligned with the rest of the text line, so css `vertical-align:bottom` is used to have the HTML result appear with the paragraph extending below the L, R, C cells at the middle, if possible. This may be confusing as a P cell may not top-align with an L,R,C cell in the HTML conversion, especially in the presence of a B cell, and two P cells side-by-side will be aligned at the bottom instead of the top. Some adjustment of the css may be desired, changing `td.tdp`, `td.tdP`, `td.tdprule`, and `td.tdPrule` to `vertical-align: middle`. Another possibility is to change L,R,C, and P to `vertical-align: top` and not worry about the alignment of B and M cells or trying to approximate L<sup>A</sup>T<sub>E</sub>X baselines.
- m:** With paragraph tags, css `vertical-align:middle`.
- b:** With paragraph tags, css `vertical-align:top` so that the bottom of the text is closest to the middle of the text line.
- P, M, B:** Horizontally-centered versions.
- S:** Converted to 'r'. From the `siunitx` package.
- D:** Converted to 'c'. From the `dcolumn` package.
- @, !, >, <:** One each, in that order.
- Unknown:** Converted to 'l'.
- \newcolumn:** Currently treated as unknown.
-

Clear the parsed resulting column spec:

```
5026 \renewcommand*\{LWR@tablecolspec}\{}%
```

Total number of columns found so far. Also pre-initialize the first several columns of specs:

```
5027 \setcounter{LWR@tabletotalcols}{0}%
5028 \setcounter{LWR@tabletotalcolsnext}{1}%
5029 \LWR@setexpparray{LWR@colatspec}{leftedge}\{}%
5030 \LWR@setexpparray{LWR@colatspec}{1}\{}%
5031 \LWR@setexpparray{LWR@colatspec}{2}\{}%
5032 \LWR@setexpparray{LWR@colatspec}{3}\{}%
5033 \LWR@setexpparray{LWR@colbangspec}{leftedge}\{}%
5034 \LWR@setexpparray{LWR@colbangspec}{1}\{}%
5035 \LWR@setexpparray{LWR@colbangspec}{2}\{}%
5036 \LWR@setexpparray{LWR@colbangspec}{3}\{}%
5037 \LWR@setexpparray{LWR@colbeforespec}{1}\{}%
5038 \LWR@setexpparray{LWR@colbeforespec}{2}\{}%
5039 \LWR@setexpparray{LWR@colbeforespec}{3}\{}%
5040 \LWR@setexpparray{LWR@col afterspec}{1}\{}%
5041 \LWR@setexpparray{LWR@col afterspec}{2}\{}%
5042 \LWR@setexpparray{LWR@col afterspec}{3}\{}%
5043 \LWR@setexpparray{LWR@col barspec}{leftedge}\{}%
5044 \LWR@setexpparray{LWR@col barspec}{1}\{}%
5045 \LWR@setexpparray{LWR@col barspec}{2}\{}%
5046 \LWR@setexpparray{LWR@col barspec}{3}\{}%
```

Starting at the first column specification:

```
5047 \setcounter{LWR@tablecolspos}{1}%
```

Place the colspecs string length into \LWR@strresult, and remember the number of characters in the column specification:

```
5048 \LWR@traceinfo{about to StrLen}%
5049 \noexpandarg%
5050 \StrLen{\#1}[\LWR@strresult]%
5051 \fullexpandarg%
5052 \LWR@traceinfo{finished StrLen}%
5053 \setcounter{LWR@tablecolswidth}{\LWR@strresult}%
```

Scan through the column specifications:

```
5054 \whiledo{\not\value{LWR@tablecolspos}>\value{LWR@tablecolswidth}}{%
```

Place the next single-character column type into \LWR@strresult:

---

```

5055 \noexpandarg%
5056 \StrChar{#1}{\theLWR@tablecolspos}[\LWR@strresult]%
5057 \LWR@traceinfo{position \arabic{LWR@tablecolspos}: \LWR@strresult}%
5058 \fullexpandarg%

```

Not yet found a valid column type

```
5059 \boolfalse{LWR@validtablecol}%
```

 Note that the parameter for a p{spec} column is a token list which will NOT match l,c,r,p.

```

5060 \IfStrEq{\LWR@strresult}{l}{\LWR@parsenormalcolumn{l}}{%
5061 \IfStrEq{\LWR@strresult}{c}{\LWR@parsenormalcolumn{c}}{%
5062 \IfStrEq{\LWR@strresult}{r}{\LWR@parsenormalcolumn{r}}{%
5063 \IfStrEq{\LWR@strresult}{L}{\LWR@parsenormalcolumn{l}}{%
5064 \IfStrEq{\LWR@strresult}{C}{\LWR@parsenormalcolumn{c}}{%
5065 \IfStrEq{\LWR@strresult}{R}{\LWR@parsenormalcolumn{r}}{%
5066 \IfStrEq{\LWR@strresult}{J}{\LWR@parsenormalcolumn{j}}{%
5067 \IfStrEq{\LWR@strresult}{S}{\LWR@parsenormalcolumn{r}}{%
5068 \IfStrEq{\LWR@strresult}{\detokenize{c}}{\LWR@parseatcolumn}{%
5069 \IfStrEq{\LWR@strresult}{!}{\LWR@parsebangcolumn}{%
5070 \IfStrEq{\LWR@strresult}{>}{\LWR@parsebeforecolumn}{%
5071 \IfStrEq{\LWR@strresult}{<}{\LWR@parseaftercolumn}{%
5072 \IfStrEq{\LWR@strresult}{|}{\LWR@parsebarcolumn}{%
5073 \IfStrEq{\LWR@strresult}{p}{\LWR@parsepcolumn{p}}{%
5074 \IfStrEq{\LWR@strresult}{m}{\LWR@parsepcolumn{m}}{%
5075 \IfStrEq{\LWR@strresult}{b}{\LWR@parsepcolumn{b}}{%

```

From the dcolumn package:

```
5076 \IfStrEq{\LWR@strresult}{D}{\LWR@parseDcolumn{c}}{%
```

From the tabularx package. X column has no parameter, but will be given paragraph tags.

```
5077 \IfStrEq{\LWR@strresult}{X}{\LWR@parsenormalcolumn{X}}{%
```

---

Many people define centered versions “P”, “M”, and “B”:  
`\newcolumntype{P}[1]{>{\centering\arraybackslash}p{#1}}`

---

```

5078 \IfStrEq{\LWR@strresult}{P}{\LWR@parsepcolumn{P}}{%
5079 \IfStrEq{\LWR@strresult}{M}{\LWR@parsepcolumn{M}}{%
5080 \IfStrEq{\LWR@strresult}{B}{\LWR@parsepcolumn{B}}{%

```

If this column was an invalid column type, convert it to an l column:

```

5081 \ifbool{LWR@validtablecol}{}{%
5082     \LWR@traceinfo{invalid column type: \LWR@strresult}%
5083     \LWR@parsenormalcolumn{l}%
5084 }%
5085 \addtocounter{LWR@tablecolspos}{1}%
5086 }%
5087 }%

```

## 58.12 Starting a new row

\LWR@maybenewtablerow If have not yet started a new table row, begin one now. Creates a new row tag, adding a class for `hline` or `tbrule` if necessary.

```

5088 \newcommand*\LWR@maybenewtablerow{%
5089 {%
5090 \ifbool{LWR@startedrow}{}%
5091 {}% started the row
5092 {}% not started the row

```

Remember that now have started the row:

```
5093 \global\booltrue{LWR@startedrow}%
```

Create the row tag, with a class if necessary.

```

5094 \global\booltrue{LWR@intabularmetadata}%
5095 \ifbool{LWR@doinghline}{}{%
5096 {%
5097     \LWR@htmlltag{tr class="hline"}%
5098     \LWR@orignewline%
5099 }%
5100 {%
5101     \ifbool{LWR@doingtbrule}{}{%
5102         \LWR@htmlltag{tr class="tbrule"}%
5103         \LWR@orignewline%
5104     }%
5105 }%
5106 {%
5107     \LWR@htmlltag{tr}\LWR@orignewline%
5108 }%
5109 }%
5108 }% end of not doing hline
5109 }% end of not started the row

```

### 58.13 Printing vertical bar tags

```
\LWR@printbartag {<index>}
```

Adds to a tabular data cell an HTML class name for a left/right vertical bar.

```
5110 \newcommand*{\LWR@printbartag}[1]{%
5111 \ifboolexpr{bool{\LWR@tabularmutemods} or bool{\LWR@emptyatbang}}{%
5112 }{%
5113 }{%
5114 { % not muting
5115     \ifstreq{\#1}{leftedge}{%
5116         \LWR@getexpparray{\LWR@colbarspec}{leftedge} %
5117     }{%
5118     {%
5119         \LWR@getexpparray{\LWR@colbarspec}{#1} %
5120         \edef\LWR@tempone{\LWR@getexpparray{\LWR@colbarspec}{#1}}{%
5121     } %
5122 }{ % not muting
5123 }}
```

### 58.14 Printing at or bang tags

```
\LWR@printatbang {<at -or- bang>} {<index>}
```

```
5124 \newcommand*{\LWR@printatbang}[2]{%
```

Fetch the column at or bang spec:

```
5125 \edef\LWR@atbangspec{\LWR@getexpparray{\LWR@col#1spec}{#2}}{%
5126 \LWR@traceinfo{atbang: #2 !\LWR@atbangspec!}}{%
```

Only generate if is not empty;

```
5127 \ifdefempty{\LWR@atbangspec}{%
5128 }{%
5129 { % not empty
5130     \LWR@htmltag{%
5131         td class="td#1%
5132             \LWR@subaddcmidruletrim{}{}%
5133             \LWR@printbartag{#2}%
5134             "%
5135             \LWR@addcmidrulewidth%
5136     }{}}
```

Create an empty cell if muting for the \bottomrule:

```

5137     \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}{%
5138         {}%
5139         {\LWR@atbangspec}%
5140 }%
5141         \LWR@htmltag{/td}\LWR@orignewline%
5142 }% not empty
5143 }%

```

\LWR@addleftmostbartag

```

5144 \newcommand*{\LWR@addleftmostbartag}{%
5145 \ifnumcomp{\value{LWR@tablecolspos}}{=}{1}{%
5146     \LWR@printbartag{leftedge}%
5147 }{}%
5148 }

```

\LWR@tabularleftedge

```

5149 \newcommand*{\LWR@tabularleftedge}{%
5150 \ifthenelse{\cnttest{\value{LWR@tablecolspos}}=1}{%
5151 {}%
5152     \LWR@printatbang{at}{leftedge}%
5153     \LWR@printatbang{bang}{leftedge}%
5154 }% left edge
5155 }% not left edge
5156 }

```

## 58.15 Data opening tag

\LWR@tabledatasinglecolumntag Print a table data opening tag with style for alignment

```

5157 \newcommand*{\LWR@tabledatasinglecolumntag}{%
5158 {}%
5159 \LWR@maybenewtablerow%

```

Don't start a new paragraph tag if have already started one:

```

5160 \ifbool{LWR@intabularmetadata}{%
5161 {}%

```

If have found the end of tabular command, do not create the next data cell:

```
5162     \ifboolexitingtabular{}{%
5163         {%
5164             \LWR@tabularleftedge%
```

Print the @ and ! contents before first column:

```
5164             \LWR@tabularleftedge%
```

Fetch the current column's alignment character into \LWR@strresult:

```
5165             \StrChar{\LWR@tablecols}{\theLWR@tablecolspos}[\LWR@strresult]{%
```

print the start of a new table data cell:

```
5166             \LWR@htmlltag{td class="td%"}
```

append this column's spec:

```
5167             \LWR@strresult%
```

If this column has a cmidrule, add “rule” to the end of the HTML class tag. Also add vertical bar tags.

```
5168             \LWR@addcmidruletrim%
5169             \LWR@addleftmostbartag%
5170             \LWR@printbartag{\theLWR@tablecolspos}%
5171             "%%
5172             \LWR@addcmidrulewidth%
5173             }%
```

If this is a p, m, b, or X column, allow paragraphs:

```
5174             \ifthenelse{%
5175                 \equal{\LWR@strresult}{p}\OR%
5176                 \equal{\LWR@strresult}{m}\OR%
5177                 \equal{\LWR@strresult}{b}\OR%
5178                 \equal{\LWR@strresult}{P}\OR%
5179                 \equal{\LWR@strresult}{M}\OR%
5180                 \equal{\LWR@strresult}{B}\OR%
5181                 \equal{\LWR@strresult}{X}%
5182             }%
5183             {%
5184                 \allowpars
5185                 \LWR@startpars%
5186                 \global\booltrue{LWR@tableparcell}%
5187             }%
5188             {%
5189                 \allowpars
5190             }%
5191             {%
5192                 \nopars
5193             }
```

Print the > contents unless muted for the \bottomrule:

---

```

5188     \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
5189     {}%
5190     {\LWR@getexpparray{LWR@colbeforespec}{\theLWR@tablecolspos}}%
5191     \global\boolfalse{LWR@intabularmetadata}%
5192     }% not exiting tabular
5193 }{}% in tabular metadata
5194 }%

```

## 58.16 Midrules

**LWR@midrules** LWR@midrules is a data array (section 32) of columns each containing a non-zero width if a midrule should be created for this column.

**LWR@trimlrules** LWR@trimlrules is a data array (section 32) of columns containing 1 if a midrule should be left trimmed for each column.

**LWR@trimrrules** LWR@trimrrules is a data array (section 32) of columns containing r if a midrule should be right trimmed for each column.

**Ctr LWR@midrulecounter** Indexes across the LWR@midrules and LWR@trim<l/r>rules data arrays.

```
5195 \newcounter{LWR@midrulecounter}
```

**Len \LWR@heavyrulewidth** The default width of the rule.

```

5196 \newlength{\LWR@heavyrulewidth}
5197 \setlength{\LWR@heavyrulewidth}{.08em}
```

**Len \LWR@lightrulewidth** The default width of the rule.

```

5198 \newlength{\LWR@lightrulewidth}
5199 \setlength{\LWR@lightrulewidth}{.05em}
```

**Len \LWR@cmidrulewidth** The default width of the rule.

```

5200 \newlength{\LWR@cmidrulewidth}
5201 \setlength{\LWR@cmidrulewidth}{.03em}
```

**Len \LWR@thiscmidrulewidth** The width of the next rule, defaulting to \lightrulewidth.

If not \lightrulewidth, a style will be used to generate the custom width.

Assigned from the LWR@midrules array.

```

5202 \newlength{\LWR@thiscmidrulewidth}
5203 \setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}
```

\LWR@clearmidrules Start new midrules. Called at beginning of tabular and also at \\.

Clears all LWR@midrules and LWR@trimrule markers for this line.

```

5204 \newcommand*{\LWR@clearmidrules}{%
5205 {%
5206 \setcounter{LWR@midrulecounter}{1}%
5207 \whiledo{%
5208 \cnttest{\value{LWR@midrulecounter}}{<=}{\value{LWR@tablecolswidth}}}%
5209 }%
5210 {%
5211 \LWR@setexpparray{LWR@midrules}{\theLWR@midrulecounter}{0pt}%
5212 \setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
5213 \LWR@setexpparray{LWR@trimlrules}{\theLWR@midrulecounter}{}%
5214 \LWR@setexpparray{LWR@trimrrules}{\theLWR@midrulecounter}{}%
5215 \addtocounter{LWR@midrulecounter}{1}%
5216 }%
5217 }

```

\LWR@subcmidrule {\langle width\rangle} {\langle trim\rangle} {\langle leftcolumn\rangle} {\langle rightcolumn\rangle}

Marks LWR@midrules data array elements to be non-zero widths from left to right columns. Also marks trimming for the L and/or R columns.

LWR@doingcmidrule is set to force an empty row at the end of the tabular to create the rule.

```

5218 \newcommand*{\LWR@subcmidrule}[4]{%
5219 \setcounter{LWR@midrulecounter}{#3}%
5220 \whiledo{\cnttest{\value{LWR@midrulecounter}}{<=}{#4}}{%
5221 {%
5222 \LWR@setexpparray{LWR@midrules}{\theLWR@midrulecounter}{#1}%
5223 \addtocounter{LWR@midrulecounter}{1}%
5224 }% whiledo
5225 \IfSubStr{#2}{1}{\LWR@setexpparray{LWR@trimlrules}{#3}{1}}{}%
5226 \IfSubStr{#2}{r}{\LWR@setexpparray{LWR@trimrrules}{#4}{r}}{}%
5227 \booltrue{LWR@doingcmidrule}%
5228 }

```

\LWR@docmidrule [{\langle width\rangle}] {\langle trim\rangle} {\langle leftcolumn-rightcolumn\rangle}

Marks LWR@midrules array elements to be "Y" from left to right columns. Also marks trimming for the L and/or R columns.

```

5229 \NewDocumentCommand{\LWR@docmidrule}{O{\LWR@cmidrulewidth} D(){} >{\SplitArgument{1}{-}m}%
5230 {\LWR@subcmidrule{#1}{#2}{#3}}

```

Used to compute margins, tabular trims

```
5231 \newlength{\LWR@templengthone}%
5232 \newlength{\LWR@templengthtwo}%
```

\LWR@subaddcmidruletrim {<lefttrim>} {<righttrim>} Adds a \cmidrule with optional trim.

```
5233 \newcommand*{\LWR@subaddcmidruletrim}[2]{%
5234 \setlength{\LWR@templengthone}{\LWR@getexparray{\LWR@midrules}{\theLWR@tablecolspos}}%
5235 \ifdimcomp{\LWR@templengthone}{>}{0pt}%
5236 {%
```

Print the class without left and right trim letters appended:

```
5237 \LWR@origtilde tdrule#1#2%
```

Remember the width of the rule:

```
5238 \setlength{\LWR@thiscmidrulewidth}{\LWR@templengthone}%
5239 }{}}%
5240 }
```

\LWR@addcmidruletrim Adds left or right trim to a \cmidrule.

```
5241 \newcommand*{\LWR@addcmidruletrim}{{%
5242 \LWR@subaddcmidruletrim}%
5243 {\LWR@getexparray{\LWR@trimlrules}{\theLWR@tablecolspos}}%
5244 {\LWR@getexparray{\LWR@trimrrules}{\theLWR@tablecolspos}}%
5245 }
```

\LWR@addrulewidth {<thiswidth>} {<defaultwidth>}

If not default width, add a custom style with width and color depending on thiswidth.

```
5246 \newcommand{\LWR@addrulewidth}[2]{%
```

Only add a custom width if thiswidth is different than the defaultwidth:

```
5247 \ifdimcomp{#1}{=}{#2}%
5248 {}% default width
5249 {}% custom width
```

Ensure that the width is wide enough to display in the browser:

```
5250 \LWR@forceminwidth{#1}%
```

```
5251     \uselengthunit{PT} % explicit space
5252     style="border-top:\rndprintlength{\LWR@atleastonept} solid %
```

The darkness of the color depends on the thickness of the rule:

```
5253     \ifdimcomp{#1}{<}{\LWR@lightrulewidth}%
5254     {\#AOAOAO}%
5255     {%
5256         \ifdimcomp{#1}{<}{\LWR@heavyrulewidth}%
5257         {\#808080}%
5258         {black}%
5259     }%
5260     {%
5261 }%
5262 }
```

\LWR@addcmidrulewidth

```
5263 \newcommand{\LWR@addcmidrulewidth}{%
5264 \LWR@addrulewidth{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
5265 }
```

## 58.17 Multicolumns

### 58.17.1 Parsing multicolumns

5266 \newcounter{LWR@tablemulticolswidth}

Indexes into the multicolumn specification:

5267 \newcounter{LWR@tablemulticolspos}

\LWR@printmccoltype {{<colspec>}} Print any valid column type found. Does not print @, !, >, or < columns or their associated tokens.

This is printed as part of the table data tag's class.

```
5268 \newcommand*{\LWR@printmccoltype}[1]{%
5269 \LWR@traceinfo{lwr@printmccoltype -#1-}%
}
```

Get one token of the column spec:

5270 \StrChar{#1}{\theLWR@tablemulticolspos}[\LWR@strresult]

Add to the HTML tag depending on which column type is found:

```

5271 \IfStrEq{\LWR@strresult}{1}{\}%
5272 \IfStrEq{\LWR@strresult}{c}{\}%
5273 \IfStrEq{\LWR@strresult}{r}{\}%
5274 \IfStrEq{\LWR@strresult}{p}{\}%
5275 \IfStrEq{\LWR@strresult}{m}{\}%
5276 \IfStrEq{\LWR@strresult}{b}{\}%
5277 \IfStrEq{\LWR@strresult}{P}{\}%
5278 \IfStrEq{\LWR@strresult}{M}{\}%
5279 \IfStrEq{\LWR@strresult}{B}{\}%
5280 \IfStrEq{\LWR@strresult}{S}{\}%
5281 \IfStrEq{\LWR@strresult}{X}{\}%
5282 \LWR@traceinfo{lwr@printmccoltype done}%
5283 }
```

\LWR@multicolpartext Print the data with paragraph tags:

```

5284 \newcommand*\LWR@multicolpartext{%
5285 \LWR@startpars%
5286 \LWR@multicoltext%
5287 \LWR@stoppars%
5288 }
```

\LWR@multicolother {\(*colspec*) For @, !, >, <, print the next token without paragraph tags:

```

5289 \newcommand*\LWR@multicolother[1]{%
5290 \addtocounter{LWR@tablemulticolpos}{1}%
5291 \StrChar{#1}{\theLWR@tablemulticolpos}[\LWR@strresult]%
5292 \LWR@strresult%
```

A valid column data type was found:

```

5293 \booltrue{LWR@validtablecol}%
5294 }
```

\LWR@multicolskip Nothing to print for this column type.

```
5295 \newcommand*\LWR@multicolskip{%
```

A valid column data type was found:

```

5296 \booltrue{LWR@validtablecol}%
5297 }
```

\LWR@printmccoldata {\(*colspec*) Print the data for any valid column type found.

---

```
5298 \newcommand*{\LWR@printmccoldata}[1]{%
5299 \LWR@traceinfo{lwr@printmccoldata -#1}%
```

Not yet found a valid column type:

```
5300 \boolfalse{LWR@validtablecol}%
```

Get one token of the column spec:

```
5301 \StrChar{#1}{\theLWR@tablemulticolspos}[\LWR@strresult]%
```

Print the text depending on which column type is found. Also handles @, >, < as it comes to them.

```
5302 \IfStrEq{\LWR@strresult}{l}{\LWR@multicoltext}{}%
5303 \IfStrEq{\LWR@strresult}{c}{\LWR@multicoltext}{}%
5304 \IfStrEq{\LWR@strresult}{r}{\LWR@multicoltext}{}%
5305 \IfStrEq{\LWR@strresult}{D}{}%
5306 \addtocounter{LWR@tablemulticolspos}{3}%
5307 \LWR@multicoltext%
5308 }{}%
5309 \IfStrEq{\LWR@strresult}{p}{\LWR@multicolpartext}{}%
5310 \IfStrEq{\LWR@strresult}{m}{\LWR@multicolpartext}{}%
5311 \IfStrEq{\LWR@strresult}{b}{\LWR@multicolpartext}{}%
5312 \IfStrEq{\LWR@strresult}{P}{\LWR@multicolpartext}{}%
5313 \IfStrEq{\LWR@strresult}{M}{\LWR@multicolpartext}{}%
5314 \IfStrEq{\LWR@strresult}{B}{\LWR@multicolpartext}{}%
5315 \IfStrEq{\LWR@strresult}{S}{\LWR@multicolpartext}{}%
5316 \IfStrEq{\LWR@strresult}{X}{\LWR@multicolpartext}{}%
5317 \IfStrEq{\LWR@strresult}{|}{\LWR@multicolskip}{}%
5318 \IfStrEq{\LWR@strresult}{\detokenize{@}}{\LWR@multicolother{#1}}{}%
5319 \IfStrEq{\LWR@strresult}{\detokenize{!}}{\LWR@multicolother{#1}}{}%
5320 \IfStrEq{\LWR@strresult}{\detokenize{>}}{\LWR@multicolother{#1}}{}%
5321 \IfStrEq{\LWR@strresult}{\detokenize{<}}{\LWR@multicolother{#1}}{}%
```

If an invalid column type:

```
5322 \ifbool{LWR@validtablecol}{}{\LWR@multicoltext}%
```

Tracing:

```
5323 \LWR@traceinfo{lwr@printmccoldata done}%
5324 }
```

\parsemulticolumnalignment {⟨1: colspec⟩} {⟨2: printresults⟩}

Scan the multicolumn specification and execute the printfunction for each entry.

Note that the spec for a p{spec} column, or @, >, <, is a token list which will NOT match l, c, r, or p.

```
5325 \newcommand*\LWR@parsemulticolumnalignment}[2]{%
5326 \setcounter{LWR@tablemulticolspos}{1}%
5327 \StrLen{#1}[\LWR@strresult]%
5328 \setcounter{LWR@tablemulticolswidth}{\LWR@strresult}%
```

Scan across the tokens in the column spec:

```
5329 \whiledo{%
5330 \not\value{LWR@tablemulticolspos}>\value{LWR@tablemulticolswidth}}%
5331 }%
5332 {%
```

Execute the assigned print function for each token in the column spec:

```
5333 #2{#1}%
```

Move to the next token in the column spec:

```
5334 \addtocounter{LWR@tablemulticolspos}{1}%
5335 }%
5336 }
```

### 58.17.2 Multicolumn factored code

```
5337 \newcommand{\LWR@multicoltext}{}%
\LWR@domulticolumn [⟨1: vpos⟩] [⟨2: #rows⟩] {⟨3: numcols⟩} {⟨4: colspec⟩} {⟨5: text⟩}%
5338 \NewDocumentCommand{\LWR@domulticolumn}{o o m m +m}{%
5339 \LWR@traceinfo{lwr@domulticolumn -#1- -#2- -#3- -#4-}%
}
```

Remember the text to be inserted, and remember that a valid column type was found:

```
5340 \renewcommand{\LWR@multicoltext}{}%
5341 #5%
5342 \booltrue{LWR@validtablecol}%
5343 }%
```

Row processing:

```
5344 \LWR@maybenewtablerow%
5345 \LWR@tabularleftedge%
```

Begin the opening table data tag:

```

5346 \LWR@htmlltag{td colspan="#3" %
5347 \IfValueT{#2}{ % rows?
5348 rowspan="#2" %

5349 \IfValueT{#1}{% vpos?
5350 \ifstrequal{#1}{b}{style="vertical-align:bottom" }{}%
5351 \ifstrequal{#1}{t}{style="vertical-align:top" }{}%
5352 }% vpos?
5353 }% rows?

5354 class="td%

```

Print the column type:

```
5355 \LWR@parsemulticolumnalignment{#4}{\LWR@printmccoltype}%

```

If this column has a cmidrule, add “rule” to the end of the HTML class tag.

If this position had a “Y” then add “rule”. Also add vertical bar class.

```

5356 \LWR@addcmidruletrim%
5357 \LWR@addleftmostbartag%
5358 \LWR@printbartag{\theLWR@tablecolspos}%

```

Close the class tag’s opening quote:

```

5359 "%
5360 \LWR@addcmidrulewidth%
5361 }% end of the opening table data tag
5362 \global\boolearnfalse{\LWR@intabularmetadata}%
5363 \LWR@parsemulticolumnalignment{#4}{\LWR@printmccoldata}%
5364 }

```

### 58.17.3 Multicolumn

```
\LWR@htmlmulticolumn {<numcols>} {<alignment>} {<text>}
5365 \NewDocumentCommand{\LWR@htmlmulticolumn}{m m +m}%
5366 {%

```

Figure out how many extra HTML columns to add for @ and ! columns:

```
5367 \LWR@tabularhtmlcolumns{\theLWR@tablecolspos}{#1}
```

Create the multicolumn tag:

```
5368 \LWR@domulticolumn{\theLWR@tabhtmlcoltotal}{#2}{#3}%
```

Move to the next L<sup>A</sup>T<sub>E</sub>X column:

```
5369 \addtocounter{LWR@tablecolspos}{#1}%
5370 \addtocounter{LWR@tablecolspos}{-1}%
```

Skip any trailing @ or ! columns for this cell:

```
5371 \booltrue{LWR@skipatbang}%
5372 }
```

#### 58.17.4 Longtable captions

longtable captions use \multicolumn.

Bool LWR@starredlongtable Per the caption pacakge, step the counter if longtable\*.

```
5373 \newbool{LWR@starredlongtable}%
5374 \boolfalse{LWR@starredlongtable}
```

Per the caption package. User-redefinable float type.

```
5375 \providetcommand*{\LTcaptive}{table}
```

```
\LWR@longtabledatacaptiontag * [(toc entry)] {(caption)}

5376 \NewDocumentCommand{\LWR@longtabledatacaptiontag}{s o +m}%
5377 {%
```

Remember the latest name for \nameref:

```
5378 \IfValueTF{#2}{% optional given?
5379   \ifthenelse{\equal{#2}{}}% optional empty?
5380   {\LWR@setlatestname{#3}}% empty
5381   {\LWR@setlatestname{#2}}% given and non-empty
5382 }% optional given
5383 {\LWR@setlatestname{#3}}% no optional
```

Create a multicolumn across all the columns:

Figure out how many extra HTML columns to add for @ and ! columns found between the first and the last column:

```
5384 \LWR@tabularhtmlcolumns{1}{\theLWR@tabletotalcols}
```

Create the multicolumn tag:

```
5385 \LWR@domulticolumn{\theLWR@tabhtmlcoltotal}{P}{%
5386 \IfBooleanTF{#1}{ star? }
```

Star version, show a caption but do not make a LOT entry:

```
5387 {%
5388   yes star
5389   \LWR@htmlblocktag{figcaption}%
5390   #3%
5391   \LWR@htmlblocktag{/figcaption}%
5392 }%
5392 {%
5392   No star:
```

Not the star version:

Don't step the counter if \caption[] {A caption.}

```
5393 \ifbool{\LWR@starredlongtable}{%
5394   {%
5395     \ifthenelse{\equal{#2}{}}{%
5396       {}%
5397     }{%
5398       \refstepcounter{LTcaptive}%
5399       \protected@edef\@currentlabel{%
5400         \csuse{p@\LTcaptive}\csuse{the\LTcaptive}%
5401       }%
5402     }%
5402 }{}
```

Create an HTML caption. Afterwards, maybe make a LOT entry.

```
5403 \LWR@htmlblocktag{figcaption}%
5404 \csuse{fnum@\LTcaptive}\CaptionSeparator#3%
5405 \LWR@htmlblocktag{/figcaption}%
```

See if an optional caption was given:

```
5406 \ifthenelse{\equal{#2}{}}{%
5406   TOC entry empty}
```

if the optional caption was given, but empty, do not form a TOC entry

```
5407 {}%
```

If the optional caption was given, but might only be []:

```
5408 {%
5408   TOC entry not empty
5409   \IfNoValueTF{#2}{%
5409     No TOC entry? }
```

The optional caption is []:

```

5410      {%
5411          No TOC entry
5412          \addcontentsline%
5413          {\csuse{ext@\LTcaptype}}%
5414          {\LTcaptype}%
5415          {%
5416              \protect\numberline%
5417              {\csuse{p@\LTcaptype}\csuse{the\LTcaptype}}%
5418              {\ignorespaces #3\protect\relax}%
5419          }%
5420      }% end of No TOC entry

```

The optional caption has text enclosed:

```

5420      {%
5421          yes TOC entry
5422          \addcontentsline%
5423          {\csuse{ext@\LTcaptype}}%
5424          {\LTcaptype}%
5425          {%
5426              \protect\numberline%
5427              {\csuse{p@\LTcaptype}\csuse{the\LTcaptype}}%
5428              {\ignorespaces #2\protect\relax}%
5429          }%
5430      }% end of yes TOC entry
5431  }% end of TOC entry not empty
5432 }% end of no star

```

Skip any trailing @ or ! columns for this cell:

```

5432 \booltrue{LWR@skipatbang}%
5433 }% end of \LWR@domulticolumn
5434
5435 \addtocounter{LWR@tablecolspos}{\theLWR@tabletotalcols}
5436 \addtocounter{LWR@tablecolspos}{-1}
5437
5438 }

```

### 58.17.5 Counting HTML tabular columns

The  $\text{\LaTeX}$  specification for a table includes a number of columns separated by the & character. These columns differ in content from line to line. Additional virtual columns may be specified by the special @ and ! columns. These columns are identical from line to line, but may be skipped during a multicolumn cell.

For HTML output, @ and ! columns are placed into their own tabular columns. Thus, a  $\text{\LaTeX}$  \multicolumn command may span several additional @ and ! columns in HTML

output. These additional columns must be added to the total number of columns spanned by an HTML multi-column data cell.

```
5439 \newcounter{LWR@tabhtmlcolindex}
5440 \newcounter{LWR@tabhtmlcolend}
5441 \newcounter{LWR@tabhtmlcoltotal}
```

\LWR@tabularhtmlcolumns {*starting L<sup>E</sup>T<sub>E</sub>X column*} {*number L<sup>E</sup>T<sub>E</sub>X columns*}

Compute the total number of HTML columns being spanned, considering the starting L<sup>E</sup>T<sub>E</sub>X table column and the number of L<sup>E</sup>T<sub>E</sub>X tabular columns being spanned. Any @ and ! columns within this span are included in the total count. The resulting number of HTML columns is returned in the counter LWR@tabhtmlcoltotal.

```
5442 \newcommand*{\LWR@tabularhtmlcolumns}[2]{%
```

Count the starting index, compute ending index, and begin with the count being the L<sup>E</sup>T<sub>E</sub>X span, to which additional @ and ! columns may be added:

```
5443 \setcounter{LWR@tabhtmlcolindex}{#1}%
5444 \setcounter{LWR@tabhtmlcoltotal}{#2}%
5445 \setcounter{LWR@tabhtmlcolend}{#1}%
5446 \addtocounter{LWR@tabhtmlcolend}{#2}%
```

Walk across the L<sup>E</sup>T<sub>E</sub>X columns looking for @ and ! columns:

```
5447 \whiledo{\value{LWR@tabhtmlcolindex}<\value{LWR@tabhtmlcolend}}{%
```

Temporarily define a macro equal to the @ specification for this column:

```
5448 \edef\LWR@atbangspec{\LWR@getexparray{LWR@colatspec}%
5449 {\theLWR@tabhtmlcolindex}}%
```

If the @ specification is not empty, add to the count:

```
5450 \ifdefempty{\LWR@atbangspec}{%
5451 {}%
5452 {\addtocounter{LWR@tabhtmlcoltotal}{1}}}%
```

Likewise for the ! columns:

```
5453 \edef\LWR@atbangspec{\LWR@getexparray{LWR@colbangspec}%
5454 {\theLWR@tabhtmlcolindex}}%
5455 \ifdefempty{\LWR@atbangspec}{%
5456 {}%
5457 {\addtocounter{LWR@tabhtmlcoltotal}{1}}}%
```

Move to the next L<sup>A</sup>T<sub>E</sub>X column:

```
5458     \addtocounter{LWR@tabhtmlcolindex}{1}%
5459 }% whiledo
5460 }

5461 \end{warpHTML}
```

## 58.18 Multicolumnrow

A print-mode version is defined here, and is also used during HTML output while inside a `lateximage`.

See section 174 for the HTML versions.

**for HTML & PRINT:** 5462 `\begin{warpall}`

```
\multicolumnrow {<1:cols>} {<2:halign>} [<3:vpos>] {<4:numrows>} [<5:bigstruts>] {<6:width>} [<7:fixup>]
{<8:text>}
```

For discussion of the use of `\DeclareExpandableDocumentCommand`, see:  
<https://tex.stackexchange.com/questions/168434/problem-with-abbreviation-of-multirow-and-multicolumn-latex>

After the user may have

```
5463 \AtBeginDocument{
    \@ifundefined{@xmultirow} determines if multirow was never loaded.
```

```
5464 \ifundefined{@xmultirow}
5465 {}% no version of multirow was loaded
5466 {}% @xmultirow defined, so some version of multirow was loaded
```

`\@ifpackageloaded{multirow}` determines if v2.0 or later of multirow was used, which included the `\ProvidesPackage` macro.

```
5467 \ifpackageloaded{multirow}{% v2.0 or newer
5468 \@ifpackagelater{multirow}{2016/09/01}{2016/09/27 for v2.0
5469 {}% v2.0+:
5470 \DeclareExpandableDocumentCommand{\LWR@origmulticolumnrow}{%
5471     +m +m +O{c} +m +O{O} +m +O{Opt} +m}%
5472 {\multicolumn{#1}{#2}{\@xmultirow[#3]{#4}{#5}{#6}{#7}{#8}}}}%
5473 }
5474 {}% loaded but older, probably not executed:
```

---

```

5475 \DeclareExpandableDocumentCommand{\LWR@origmulticolumnrow}{%
5476   {+m +m +O{c} +m +O{0} +m +O{Opt} +m}%
5477 {\multicolumn{#1}{#2}{\@xmultirow{#4}{#5}{#6}{#7}{#8}}}}%
5478 }%
5479 }% package loaded{multirow}

```

If not `\@ifpackageloaded{multirow}` but `\@xmultirow` is defined, then this must be v1.6 or earlier, which did not `\ProvidesPackage{multirow}`, and did not have the `vposn` option.

```

5480 {%
5481   v1.6 or older did not \ProvidePackage
5482 \DeclareExpandableDocumentCommand{\LWR@origmulticolumnrow}{%
5483   {+m +m +O{c} +m +O{0} +m +O{Opt} +m}%
5484 {\multicolumn{#1}{#2}{\@xmultirow{#4}{#5}{#6}{#7}{#8}}}}%

```

The user-level interface. This is provided if the HTML version was not already given.

```

5485 \providecommand*{\multicolumnrow}{\LWR@origmulticolumnrow}%
5486 }% \@xmultirow defined, so multirow was loaded
5487 }% AtBeginDocument
5488 \end{warpall}

```

## 58.19 Utility macros inside a table

**for HTML output:** 5489 `\begin{warpHTML}`

```

5490 \newcommand*{\LWR@donothing}{}

```

In case `bigdelim` is not loaded:

```

5491 \newcommand*{\ldelim}{}
5492 \newcommand*{\rdelim}{}
5493 \end{warpHTML}

```

## 58.20 Special-case tabular markers

**for HTML & PRINT:** 5494 `\begin{warpall}`

\TabularMacro Place this just before inserting a custom macro in a table data cell. Doing so tells lwarp not to automatically start a new HTML table data cell yet. See section 7.7.

```
5495 \let\TabularMacro\relax
5496 \end{warpall}
```

\ResumeTabular Used to resume tabular entries after resuming an environment.

**⚠ tabular inside another environment** When creating a new environment which contains a `tabular` environment, lwarp's emulation of the `tabular` does not automatically resume when the containing environment ends, resulting in corrupted HTML rows. To fix this, use `\ResumeTabular` as follows. This is ignored in print mode.

```
\StartDefiningTabulars % because & is used in a definition
\newenvironment{outerenvironment}
{
\begin{tabular}{cc}
left & right \\
\end{tabular}
\TabularMacro\ResumeTabular
left & right \\
\end{tabular}
\EndDefiningTabulars
```

**for HTML output:** 5497 \begin{warpHTML}

```
5498 \newcommand*\ResumeTabular{}%
5499 \global\boolfalse{LWR@exittingtabular}%
5500 \global\boolfalse{LWR@tabularmutemods}%
5501 \LWR@getmynexttoken%
5502 }

5503 \end{warpHTML}
```

**for PRINT output:** 5504 \begin{warpprint}

```
5505 \newcommand*\ResumeTabular{}%
5506 \end{warpprint}
```

## 58.21 Checking for a new table cell

**for HTML output:** 5507 \begin{warpHTML}

Bool LWR@exittingtabular When \end is found, turns off the next opening data tag.

5508 \newbool{LWR@exittingtabular}

Bool LWR@tabularmutemods Mutes HTML output for @, !, < and >.

This is used while printing the final row to generate \bottomrules.

5509 \newbool{LWR@tabularmutemods}

\LWR@tabledatacolumntag Open a new HTML table cell unless the next token is for a macro which does not create data, such as \hline, \toprule, etc:

5510 \newcommand\*\{\LWR@tabledatacolumntag\}%
 5511 {%
 5512 \LWR@traceinfo{\LWR@tabledatacolumntag\}%

\show\LWR@mynexttoken to see what tokens to look for

If not any of the below, start a new table cell:

5513 \let\mynext\LWR@tabledatasinglecolumntag\%

If exiting the tabular:

5514 \ifdefequal{\LWR@mynexttoken}{\end}%
 5515 {\booltrue{LWR@exittingtabular}}{}%

longtable can have a caption in a cell

5516 \ifdefequal{\LWR@mynexttoken}{\caption}%
 5517 {\let\mynext\LWR@donothing}{}%

Look for other things which would not start a table cell:

5518 \ifdefequal{\LWR@mynexttoken}{\multicolumn}%
 5519 {\let\mynext\LWR@donothing}{}%
 5520 \ifdefequal{\LWR@mynexttoken}{\multirow}%
 5521 {\let\mynext\LWR@donothing}{}%
 5522 \ifdefequal{\LWR@mynexttoken}{\multicolumnrow}%
 5523 {\let\mynext\LWR@donothing}{}%

If an \mrowcell, this is a cell to be skipped over:

```
5524 \ifdefeql{\LWR@mynexttoken}{\mrowcell}%
5525     {\let\mynext\LWR@donothing}{}%
```

If an \mcolrowcell, this is a cell to be skipped over:

```
5526 \ifdefeql{\LWR@mynexttoken}{\mcolrowcell}%
5527     {\let\mynext\LWR@donothing}{}%
5528 %
5529 \ifdefeql{\LWR@mynexttoken}{\TabularMacro}%
5530     {\let\mynext\LWR@donothing}{}%
5531 %
5532 \ifdefeql{\LWR@mynexttoken}{\hline}%
5533     {\let\mynext\LWR@donothing}{}%
5534 %
5535 \ifdefeql{\LWR@mynexttoken}{\toprule}%
5536     {\let\mynext\LWR@donothing}{}%
5537 %
5538 \ifdefeql{\LWR@mynexttoken}{\midrule}%
5539     {\let\mynext\LWR@donothing}{}%
5540 %
5541 \ifdefeql{\LWR@mynexttoken}{\cmidrule}%
5542     {\let\mynext\LWR@donothing}{}%
5543 %
5544 \ifdefeql{\LWR@mynexttoken}{\specialrule}%
5545     {\let\mynext\LWR@donothing}{}%
5546 %
5547 \ifdefeql{\LWR@mynexttoken}{\cline}%
5548     {\let\mynext\LWR@donothing}{}%
5549 %
5550 \ifdefeql{\LWR@mynexttoken}{\bottomrule}%
5551     {\let\mynext\LWR@donothing}{}%
5552 %
5553 \ifdefeql{\LWR@mynexttoken}{\warpprintonly}%
5554     {\let\mynext\LWR@donothing}{}%
5555 %
5556 \ifdefeql{\LWR@mynexttoken}{\warpHTMLonly}%
5557     {\let\mynext\LWR@donothing}{}%
5558 %
5559 \ifdefeql{\LWR@mynexttoken}{\ldelim}%
5560     {\let\mynext\LWR@donothing}{}%
5561 %
5562 \ifdefeql{\LWR@mynexttoken}{\rdelim}%
5563     {\let\mynext\LWR@donothing}{}%
```

no action for an \end token

Add similar to the above for any other non-data tokens which might appear in the table.

Start the new table cell if was not any of the above:

```
5564 \mynext%
5565 }

5566 \end{warpHTML}
```

## 58.22 \mrowcell

**for HTML & PRINT:** 5567 \begin{warpall}

\mrowcell The user must insert \mrowcell into any \multirow cells which must be skipped.  
⚠ This command has no action during print output.

```
5568 \newcommand*{\mrowcell}{}}

5569 \end{warpall}
```

## 58.23 \mcolrowcell

**for HTML & PRINT:** 5570 \begin{warpall}

\mcolrowcell The user must insert \mcolrowcell into any \multicolumn cells which must be skipped. This command has no action during print output.  
⚠

```
5571 \newcommand*{\mcolrowcell}{}}

5572 \end{warpall}
```

## 58.24 New \tabular definition

**for HTML output:** 5573 \begin{warpHTML}

These are default definitions in case booktabs is not loaded, and are not expected to used, but must exist as placeholders.

---

```

5574 \newcommand*{\LWR@origtoprule}[1]{\hline}
5575 \newcommand*{\LWR@origmidrule}[1]{\hline}
5576 \LetLtxMacro{\LWR@origcmidrule}{\cline}
5577 \newcommand*{\LWR@origbottomrule}[1]{\hline}
5578 \newcommand*{\LWR@origaddlinespace}[1][]{}
5579 \newcommand*{\LWR@origmorecmidrules}(){}
5580 \newcommand*{\LWR@origspecialrule}[3]{\hline}

```

**\LWR@hline** The definition of \hline depends on whether tabls has been loaded. If so, optional space below the line may be specified, but will be ignored.

```

5581 \AtBeginDocument{
5582 \@ifpackageloaded{l warp-tables}
5583 {\newcommand*{\LWR@hline}[1][]{%
5584     \booltrue{\LWR@doinghline}%
5585     \LWR@getmynexttoken}%
5586 {\newcommand*{\LWR@hline}{}%
5587     \booltrue{\LWR@doinghline}%
5588     \LWR@getmynexttoken}%
5589 }% AtBeginDocument

```

**\LWR@nullifyNoAutoSpacing** For babel-french, turn off auto spacing at the start of the tabular, then nullify the autospacing commands inside the tabular, since they were not compatible with the tabular column parsing code, which uses xstring.

```

5590 \AtBeginDocument{
5591 \@ifundefined{frenchbsetup}%
5592 {%
5593     no babel-french
5594     \newcommand*{\LWR@nullifyNoAutoSpacing}{}%
5595 }%
5596 yes babel-french
5597     \newcommand*{\LWR@nullifyNoAutoSpacing}{}%
5598     \NoAutoSpacing%
5599     \renewcommand*{\NoAutoSpacing}{}%
5600     \renewcommand*{\LWR@FBcancel}{}%
5601 }%
5602 yes babel-french
5603 }% AtBeginDocument

```

Env **\LWR@tabular** [*vertposition*] {[*colspeсs*}]

The new tabular environment will be \let in \LWR@LwarpStart, since siunitx might redefine tabular in the user's document.

```

5603 \StartDefiningTabulars
5604
5605 \newenvironment*{\LWR@tabular}[2][]{}

```

---

```
5606 {%
5607 \LWR@traceinfo{LWR@tabular started}%
5608 \addtocounter{LWR@tabulardepth}{1}%
```

Not yet started a table row:

```
5609 \global\boolfalse{LWR@startedrow}%
```

Not yet doing any rules:

```
5610 \global\boolfalse{LWR@doinghline}%
5611 \global\boolfalse{LWR@doingtbrule}%
5612 \global\boolfalse{LWR@doingscmidrule}%
```

For babel-french, turn off auto spacing one time, then nullify the autospacing commands since were not compatible with the tabular parsing code.

```
5613 \LWR@nullifyNoAutoSpacing%
```

Have not yet found the end of tabular command. Unmute the @ and ! columns.

```
5614 \boolfalse{LWR@exittingtabular}%
5615 \boolfalse{LWR@tabularmutemods}%
```

Create the table tag:

```
5616 \global\booltrue{LWR@intabularmetadata}%
5617 \LWR@forcenewpage
5618 \LWR@htmlblocktag{table}%
```

Parse the table columns:

```
5619 \LWR@parsetablecols{#2}%
```

Table col spec is: \LWR@tablecols which is a string of llccrr, etc.

Do not place the table inside a paragraph:

```
5620 \LWR@stopars%
```

Track column # for setting text-align:

```
5621 \setcounter{LWR@tablecolspos}{1}%
```

Start looking for midrules:

```
5622 \LWR@clearmidrules%
```

\\" becomes a macro to end the table row:

```
5623 \LetLtxMacro{\\"}{\LWR@tabularendofline}%
```

The following may appear before a data cell is created, so after doing their actions, we look ahead with \LWR@getmynexttoken to see if the next token might create a new data cell:

The optional parameter for \hline supports the tabls package.

```
5624 \LWR@traceinfo{LWR@tabular: redefining macros}%
5625 \renewcommand*{\hline}{\LWR@hline}%
5626 %
5627 \RenewDocumentCommand{\cline}{m}%
5628 {\LWR@docmidrule{##1}\LWR@getmynexttoken}%

5629 \DeclareDocumentCommand{\toprule}{o d()}%
5630   {%
5631     \IfValueTF{##1}%
5632       {\LWR@docmidrule[##1](){1-\theLWR@tabletotalcols}}%
5633       {\booltrue{\LWR@doingtbrule}}%
5634     \LWR@getmynexttoken}%
5635 %
5636 \DeclareDocumentCommand{\midrule}{o d()}%
5637   {%
5638     \IfValueTF{##1}%
5639       {\LWR@docmidrule[##1](){1-\theLWR@tabletotalcols}}%
5640       {\booltrue{\LWR@doingshline}}%
5641     \LWR@getmynexttoken}%
5642 %
5643 \DeclareDocumentCommand{\cmidrule}{O{\LWR@cmidrulewidth} d() m}%
5644 {\LWR@docmidrule[##1](##2)(##3)\LWR@getmynexttoken}%
5645 %
5646 \DeclareDocumentCommand{\bottomrule}{o d()}%
5647   {%
5648     \IfValueTF{##1}%
5649       {\LWR@docmidrule[##1](){1-\theLWR@tabletotalcols}}%
5650       {\booltrue{\LWR@doingtbrule}}%
5651     \LWR@getmynexttoken}%
5652 %
5653 \DeclareDocumentCommand{\addlinespace}{o}{}%
5654 \DeclareDocumentCommand{\morecmidrules}{}{}%
5655 \DeclareDocumentCommand{\specialrule}{m m m d()}%
5656   {\LWR@docmidrule[##1](){1-\theLWR@tabletotalcols}\LWR@getmynexttoken}%

```

The following create data cells and will have no more data in this cell, so we do not want to look ahead for a possible data cell, so do not want to use \LWR@getmynexttoken.

```

5657 \renewcommand{\multicolumn}{\LWR@htmlemulticolumn}%
5658 \renewcommand*{\mrowcell}{%
5659     \LWR@maybenewtablerow%
5660     \LWR@tabularleftedge%
5661     \global\booltrue{\LWR@skippingmrowcell}%
5662 }%
5663 \renewcommand*{\mcolrowcell}{%
5664     \LWR@maybenewtablerow%
5665     \LWR@tabularleftedge%
5666     \global\booltrue{\LWR@skippingmcolrowcell}%
5667 }%
5668 \LetLtxMacro{\caption}{\LWR@longtabledatacaptiontag}%

```

Reset for new processing:

```

5669 \global\boolfalse{\LWR@tableparcell}%
5670 \global\boolfalse{\LWR@skippingmrowcell}%
5671 \global\boolfalse{\LWR@skippingmcolrowcell}%
5672 \global\boolfalse{\LWR@skipatbang}%
5673 \global\boolfalse{\LWR@emptyatbang}%

```

Set & for its special meaning inside the tabular:

```

5674 \StartDefiningTabulars%
5675 \protected\gdef&{\LWR@tabularampersand}%

```

Look ahead for a possible table data cell:

```

5676 \LWR@traceinfo{\LWR@tabular: about to \LWR@getmynexttoken}%
5677 \LWR@getmynexttoken%
5678 }%

```

Ending the environment:

```

5679 {%
5680 \LWR@traceinfo{\LWR@tabular ending}%
5681 \ifthenelse{\value{\LWR@tablecolspos}<\value{\LWR@tablecolswidth}}{%
5682     \LWR@tabularfinishrow}%
5683 }%
5684 {%
5685     \LWR@closetabledatacell%
5686 }%
5687 \LWR@htmlblocktag{/tr}%
5688 \LWR@htmlblocktag{/table}%
5689 \global\boolfalse{\LWR@intabularmetadata}%

```

Unnest one level of tabular:

```

5690 \addtocounter{\LWR@tabulardepth}{-1}%

```

Restore & to its usual meaning:

```
5691 \protected\gdef&{\LWR@origampmacro}%
5692 \EndDefiningTabulars%
5693 \LWR@traceinfo{LWR@tabular finished ending}%
5694 }
5695
5696 \EndDefiningTabulars

5697 \end{warpHTML}
```

## 58.25 Array

Pkg array

array is also automatically loaded by siunitx.

## 59 Cross-references

Sectioning commands have been emulated from scratch, so the cross-referencing commands are custom-written for them. Emulating both avoids several layers of patches.

The zref package is used to remember section name, file, and lateximage depth and number for each label.

Table 8 shows the data structures related to cross-referencing.

**for HTML output:** 5698 \begin{warpHTML}

### 59.1 Setup

\@currentlabelname To remember the most recently defined section name, description, or caption, for \nameref.

```
5699 \newcommand*{\@currentlabelname}{}%
```

\LWR@stripperiod {⟨text⟩} [⟨.⟩]

Removes a trailing period.

```
5700 \def\LWR@stripperiod#1.\ltx@empty#2@nil{#1}%
```

Table 8: Cross-referencing data structures

|                                                                                                                                                                               |                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| <b>Original L<sup>A</sup>T<sub>E</sub>X:</b>                                                                                                                                  | (print and HTML) |
| \refstepcounter: Steps the counter and sets \currentlabel.                                                                                                                    |                  |
| \currentlabel: \p@<ctr>\the<ctr> Updated by \refstepcounter.                                                                                                                  |                  |
| \label: Writes to the .aux file:<br>\newlabel{<label>}{{\currentlabel}{\thepage}}                                                                                             |                  |
| \newlabel: When the .aux file is read, sets \r@<label>.                                                                                                                       |                  |
| \r@<label>: Set to: {{\currentlabel}{\thepage}}                                                                                                                               |                  |
| \ref: Returns the first part of \r@<label>.                                                                                                                                   |                  |
| \pageref: Returns the second part of \r@<label>.                                                                                                                              |                  |
| <b>Added by l warp:</b>                                                                                                                                                       | (HTML only)      |
| \label: Adds HTML tags (section 59.3), plus \splabel data (section 59.2):                                                                                                     |                  |
| zLWR@name: The section name for this label.                                                                                                                                   |                  |
| zLWR@htmlfilenumber: The filenumber or name for this label.                                                                                                                   |                  |
| zLWR@teximagedepth: The teximagedepth for this label.                                                                                                                         |                  |
| zLWR@teximagenumber: The teximagenumber for this label.                                                                                                                       |                  |
| \nameref: Emulated from hyperref for l warp. See section 59.4.                                                                                                                |                  |
| \ref and \nameref: Adds HTML tags. See section 59.4.                                                                                                                          |                  |
| <b>Added by amsmath:</b>                                                                                                                                                      | (print and HTML) |
| \label: Execution is delayed until the math environment is completed.                                                                                                         |                  |
| \ltx@label: L <sup>A</sup> T <sub>E</sub> X \label, (HTML: patched by l warp,) later patched by cleveref.                                                                     |                  |
| <b>Added by cleveref:</b>                                                                                                                                                     | (print and HTML) |
| \refstepcounter: Added: sets \cref@currentlabel.                                                                                                                              |                  |
| \cref@currentlabel: (<type>=<ctr> unless an alias is used):<br>[<type>] [<arabic{<ctr>}>] [<parent ctrs>]{\p@<ctr>\the<ctr>} Also see<br>section 45.4 for use with footnotes. |                  |
| \label: Writes to the .aux file:<br>\newlabel{<label>@\cref}{{\cref@currentlabel}{\thepage}}                                                                                  |                  |
| \newlabel: (Unchanged.) When the .aux file is read, sets \r@<label>@\cref.                                                                                                    |                  |
| \r@<label>@\cref: Set to: {{\cref@currentlabel}{\thepage}}                                                                                                                    |                  |
| <b>Utility functions:</b> See \cref@getlabel, \cref@gettype, \cref@getcounter,<br>\cref@getprefix.                                                                            |                  |
| <b>Cross-referencing names:</b> \crefname and \Crefname assign human-readable<br>names for references to this counter type.                                                   |                  |
| <b>Additionally patched by l warp:</b>                                                                                                                                        | (HTML only)      |
| \cref, etc.: Modified for l warp. See section 69.                                                                                                                             |                  |
| \label inside math: See section 63.4.1.                                                                                                                                       |                  |
| <b>Footnotes:</b> See \noteentry in section 45.4.                                                                                                                             |                  |

```
\LWR@setlatestname {<object name>}
```

Removes \label, strips any final period, and remembers the result.

```
5701 \newcommand*{\LWR@setlatestname}[1]{%
```

Remove \label and other commands from the name, the strip any final period. See zref-titleref and gettitlestring.

```
5702 \GetTitleStringExpand{#1}%
5703 \edef@\currentlabelname{\detokenize\expandafter{\GetTitleStringResult}}%
5704 \edef@\currentlabelname{%
5705 \expandafter\LWR@stripperiod@\currentlabelname%
5706 \ltx@empty.\ltx@empty@nil%
5707 }%
5708 }
```

## 59.2 Zref setup

See:

<http://tex.stackexchange.com/questions/57194/extract-section-number-from-equation-reference>

Create a new property list called special:

```
5709 \zref@newlist{special}
```

Define a new property which has the name of the most recently declared section:

```
5710 \zref@newprop{zLWR@name}{\@currentlabelname}
```

Define a new property which has either a filename or a file number:

```
5711 \zref@newprop{zLWR@htmlfilename}{%
5712 \ifbool{FileSectionNames}{\LWR@thisfilename}{\theLWR@htmlfilename}%
5713 }%
```

Additional properties for lateximages:

```
5714 \zref@newprop{zLWR@lateximagedepth}{\arabic{LWR@lateximagedepth}}%
5715 \zref@newprop{zLWR@lateximagefilename}{\arabic{LWR@lateximagefilename}}
```

zLWR@htmlfilename property holds the file number or name

Add a LWR@htmlfilename property, and lateximage properties to special:

---

```

5716 \zref@addprop{special}{zLWR@name}
5717 \zref@addprop{special}{zLWR@htmlfilename}
5718 \zref@addprop{special}{zLWR@lateximagedepth}
5719 \zref@addprop{special}{zLWR@lateximagenumber}

```

Returns the selected field:

```

5720 \newcommand*\{\LWR@sref\}[2]{%
5721 \zref@extractdefault{\#1}{\#2}{??}}

```

`\LWR@nameref {<label>}` Returns the section name for this label:

```

5722 \newcommand*\{\LWR@nameref\}[1]{%
5723 \LWR@sref{\#1}{zLWR@name}%
5724 }

```

`\LWR@htmlfileref {<label>}` Returns the file number for this label:

```

5725 \newcommand*\{\LWR@htmlfileref\}[1]{%
5726 % DO NOT USE \LWR@traceinfo HERE! Will be expanded.
5727 \LWR@sref{\#1}{zLWR@htmlfilename}%
5728 }

```

`\LWR@lateximagedepthref {<label>}` Returns the `lateximagedepth` for this label:

```

5729 \newcommand*\{\LWR@lateximagedepthref\}[1]{%
5730 \LWR@sref{\#1}{zLWR@lateximagedepth}%
5731 }

```

`\LWR@lateximagenumberref {<label>}` Returns the `lateximagenumber` for this label:

```

5732 \newcommand*\{\LWR@lateximagenumberref\}[1]{%
5733 \LWR@sref{\#1}{zLWR@lateximagenumber}%
5734 }

```

`\LWR@splabel {<label>}` Sanitize the name and then creates the label:

```

5735 \newcommand*\{\LWR@splabel\}[1]{%
5736 \LWR@setlatestname{@currentlabelname}%
5737 \zref@labelbylist{\#1}{special}}

```

### 59.3 Labels

\LWR@subsublabel {*label*} Creates an HTML id tag.

```
5738 \newcommand*{\LWR@subsublabel}[1]{%
```

Create an HTML id tag unless are inside a lateximage, since it would appear in the image:

```
5739 \ifthenelse{\cnttest{\value{LWR@lateximagedepth}}>}{0}%
5740 {}%
5741 {% not lateximage
```

If not doing a lateximage, create an HTML ID tag: (To be factored...)

```
5742 \ifbooleq{\LWR@doingstartpars}{%
5743   {}% pars allowed
5744   \ifbooleq{\LWR@doingapar}{%
5745     {}% par started
5746     \LWR@htmltag{a id="#1"\}\LWR@htmltag{/a}}%
5747   }% par started
5748   {}% par not started
5749   \LWR@stoppars%
5750   \LWR@htmltag{a id="#1"\}\LWR@htmltag{/a}%
5751   \LWR@startpars%
5752 }% par not started
5753 }% pars allowed
5754 {}% pars not allowed
5755 \LWR@htmltag{a id="#1"\}\LWR@htmltag{/a}%
5756 }% pars not allowed
5757 }% not lateximage
5758 }
```

\LWR@newlabel {*label*} [*type*]

\label during HTML output when not in math mode, removing extra spaces around the label, as done by regular L<sup>A</sup>T<sub>E</sub>X \label.

clevereref later encases this to add its own cross-referencing.

The optional *type* is per the ntheorem package, and is ignored.

```
5759 \NewDocumentCommand{\LWR@newlabel}{m o}{%
5760 \LWR@traceinfo{\LWR@newlabel: starting}%
5761 \LWR@traceinfo{\LWR@newlabel: !#1!}%
5762 % \@bsphack%
```

Create a traditional L<sup>A</sup>T<sub>E</sub>X label, as modified by cleveref:

```
5763 \LWR@origlabel{#1}%
```

Create a special label which holds the section number, LWR@htmlfilename, LWR@lateximagedepth, and LWR@lateximagenumber:

```
5764 \LWR@traceinfo{LWR@newlabel: filesectionnames is \ifbool{FileSectionNames}{true}{false}}%
5765 \LWR@traceinfo{LWR@newlabel: LWR@thisfilename is !\LWR@thisfilename!}%
5766 \LWR@traceinfo{LWR@newlabel: LWR@htmlfilename is \theLWR@htmlfilename}%
5767 \LWR@splabel{#1}%
5768 \LWR@subsublabel{#1}%
5769 % \@esphack%
5770 \LWR@traceinfo{LWR@newlabel: done}%
5771 }
```

## 59.4 References

\LWR@startref {<label>} (Common code for \ref and \nameref.)

Open an HTML tag reference to a filename, # character, and a label.

```
5772 \newcommand*{\LWR@startref}[1]
5773 {%
5774 \edef\LWR@lidref{\LWR@lateximagedepthref{#1}}%
5775 \LWR@traceinfo{LWR@startref A: !#1!}%
```

Create the filename part of the link:

```
5776 \LWR@htmlltag{a href="%"
5777 \LWR@traceinfo{LWR@startref B}%
5778 \LWR@htmllrefsectionfilename{#1}%
5779 \LWR@traceinfo{LWR@startref C}%
5780 %#%
```

Create the destination id:

See if LWR@lateximagedepth is unknown:

```
5781 \LWR@traceinfo{LWR@startref D: !#1!}%
5782 \ifthenelse{\equal{\LWR@lidref}{??}}{%
```

“??” if LWR@lateximagedepth is unknown, so create a link with an unknown destination:

```

5783 {%
5784     \LWR@traceinfo{\LWR@startref D0: ??}%
5785     ??%
5786 }%

```

If `\LWR@lateximagedepth` is known. Use a `lateximage` if the depth is greater than zero, or a regular link otherwise:

```

5787 {%
5788     \LWR@traceinfo{\LWR@startref D1: \LWR@lidref}%
5789     \ifthenelse{\cnttest{\LWR@lidref}{>}{0}}{%
5790         {%
5791             \LWR@traceinfo{\LWR@startref D2: \LWR@lidref}%
5792             lateximage\LWR@lateximagenumberref{#1}%
5793         }%
5794         {%
5795             \LWR@traceinfo{\LWR@startref D3}%
5796             #1%
5797         }%
5798 }%
5799 \LWR@traceinfo{\LWR@startref E}%

```

Closing quote:

```

5800 "}{}%
5801 \LWR@traceinfo{\LWR@startref F}%
5802 }

```

`\LWR@subnewref {<label>} {<label or sub@label>}`

Factored for the `subfig` package. Uses the original label for the hyper-reference, but prints its own text, such as “1(b)”.

```

5803 \NewDocumentCommand{\LWR@subnewref}{m m}{%
5804 \LWR@traceinfo{\LWR@subnewref #1 #2}%
5805 \LWR@startref{#1}%
5806 \LWR@origref{#2}%
5807 \LWR@htmltag{/a}%
5808 }

```

`\ref * {<label>} \ref is \let to \LWR@newref`

`\LWR@newref * {<label>}` Create an internal document reference link, or without a link if starred per `hyperref`.

```

5809 \NewDocumentCommand{\LWR@newref}{s m}{%
5810 \LWR@traceinfo{\LWR@newref #2}%

```

```

5811 \IfBooleanTF{#1}%
5812 {\LWR@origref{#2}}%
5813 {\LWR@subnewref{#2}{#2}}%
5814 }

```

\pagerefPageFor Text for page references.

```
5815 \newcommand*{\pagerefPageFor}{\see }
```

\pageref \* {*label*} Create an internal document reference, or just the unlinked number if starred, per hyperref.

```

5816 \NewDocumentCommand{\LWR@newpageref}{s m}{%
5817 \IfBooleanTF{#1}%
5818 {(\pagerefPageFor\LWR@origref{#2})}%
5819 {(\cpageref{#2})}%
5820 }

```

\nameref {*label*}

```

5821 \newcommand*{\nameref}[1]{%
5822 \LWR@traceinfo{\nameref A}%
5823 \LWR@startref{#1}%
5824 \LWR@traceinfo{\nameref B}%
5825 \LWR@nameref{#1}%
5826 \LWR@traceinfo{\nameref C}%
5827 \LWR@htmltag{/a}%
5828 \LWR@traceinfo{\nameref D}%
5829 }

```

\Nameref {*label*} In print, adds the page number. In HTML, does not.

```
5830 \let\Nameref\nameref
```

## 59.5 Hyper-references

 Note that the code currently only sanitizes the underscore character. Additional characters should be rendered inert as well. See the `hyperref.sty` definition of `\gdef\hyper@normalise` for an example.

Pkg `hyperref`

 Do not tell other packages that `hyperref` is emulated. Some packages patch various

commands if `hyperref` is present, which will probably break something, and the emulation already handles whatever may be emulated anyhow.

Any reference to `\usepackage{hyperref}` must be placed inside a `warpprint` environment.

```
5831 % DO NOT TELL OTHER PACKAGES TO ASSUME HYPERREF, lest they attempt to patch it:
5832 % \EmulatesPackage{hyperref}[2015/08/01]%. Disabled. Do not do this.
```

Create a link with a text name:

```
\LWR@subhyperref {⟨URL⟩} {⟨text⟩}
```

```
5833 \NewDocumentCommand{\LWR@subhyperref}{m +m}{%
5834 \LWR@htmltag{a href="#" target="\_\_blank"\LWR@orignewline}#2\LWR@htmltag{/a}%
5835 \LWR@ensuredoingapar%
5836 }
```

```
\LWR@subhyperrefclass {⟨URL⟩} {⟨text⟩} {⟨htmlclass⟩}
```

```
5837 \NewDocumentCommand{\LWR@subhyperrefclass}{m +m m}{%
5838 \LWR@htmltag{a href="#"%
5839 class="#3"\LWR@orignewline}#2\LWR@htmltag{/a}%
5840 \LWR@ensuredoingapar%
5841 }
```

```
\href [⟨options⟩] {⟨URL⟩} {⟨text⟩}
```

Create a link with accompanying text:

```
5842 \NewDocumentCommand{\LWR@hrefb}{O{} m +m}{%
5843 \LWR@subhyperref{#2}{#3}%
5844 \endgroup%
5845 \LWR@ensuredoingapar%
5846 }
5847
5848 \newcommand{\href}{%
5849 \LWR@ensuredoingapar%
5850 \begingroup%
5851 \catcode`\_=12
5852 \LWR@hrefb%
5853 }
```

```
\nolinkurl {⟨URL⟩}
```

Print the name of the link without creating the link:

```
5854 \newcommand*{\LWR@nolinkurlb}[1]{#1\endgroup\LWR@ensuredoingapar}
5855
5856 \newcommand{\nolinkurl}{%
5857 \LWR@ensuredoingapar%
5858 \begingroup\catcode`\_=12
5859 \LWR@nolinkurlb%
5860 }
```

```
\url {<URL>}
```

Create a link whose text name is the address of the link. The `url` package may redefine `\url`, so it is `\let` to `\LWR@urlahere` and also redefined by `lwarp-url`.

```
5861 \newcommand*{\LWR@urlb}[1]{%
5862 \href{#1}{#1}%
5863 \endgroup%
5864 \LWR@ensuredoingapar%
5865 }
5866
5867 \newcommand{\LWR@urla}{%
5868 \LWR@ensuredoingapar%
5869 \begingroup\catcode`\_=12
5870 \LWR@urlb%
5871 }
5872
5873 \let\url\LWR@urla
```

```
\LWR@subinlineimage [<alttag>] {<class>} {<filename>} {<extension>} {<style>}
```

```
5874 \newcommand*{\LWR@subinlineimage}[5]{[]}{%
5875 \ifthenelse{\equal{#1}{}}{%
5876 {\LWR@htmlltag{img src="#3.#4" alt="#3" style="#5" class="#2"{} }}%
5877 {\LWR@htmlltag{img src="#3.#4" alt="#1" style="#5" class="#2"{} }}%
5878 }%
5879 \end{warpHTML}
```

Table 9: Float data structures

---

For each <type> of float (figure, table, etc.) there exists the following:

**counter <type>:** A counter called <type>, such as `figure`, `table`.

`\<type>name`: Name. `\figurename` prints “Figure”, etc.

`\ext@<type>`: File extension. `\ext@figure` prints “lof”, etc.

`\fps@<type>`: Placement.

`\the<type>`: Number. `\thetable` prints the number of the table, etc.

`\p@<type>`: Parent’s number. Prints the number of the [within] figure, etc.

`\fnum@<type>`: Prints the figure number for the caption.

`\<type>name \the<type>`, “Figure 123”.

`\<type>`: Starts the float environment. `\figure` or `\begin{figure}`

`\end<type>`: Ends the float environment. `\endfigure` or `\end{figure}`

`\tf@<ext>`: The L<sup>A</sup>T<sub>E</sub>X file identifier for the output file.

`\LWR@have<type>`: A boolean rememebering whether a `\listof` was requested for a float of this type.

**File with extension lo<f,t,a-z>:** An output file containing the commands to build the `\listof<type><name>` “table-of-contents” structure.

**Cross-referencing names:** For `cleveref`’s `\cref` and related, `\crefname` and `\Crefname` assign human-readable names for references to this float type.

---

## 60 Floats

Floats are supported, although partially through emulation.

Table 9 shows the data structure associated with each <type> of float.

`\@makecaption` is redefined to print the float number and caption text, separated by `\CaptionSeparator`, which works with the `babel` package to adjust the caption separator according to the language. French, for example, uses an en-dash instead of a colon: “Figure 123 – Caption text”.

## 60.1 Float captions

**for HTML output:** 5880 \begin{warpHTML}

\LWR@floatbegin {*type*} [*placement*]

Begins a \newfloat environment.

```
5881 \NewDocumentCommand{\LWR@floatbegin}{m o}{%
5882 \ifthenelse{\boolean{FormatWordProcessor}}\AND\boolean{HTMLMarkFloats}}{%
5883
5884 === #1 begin
5885
5886 }{}%
5887 \LWR@stoppars
```

There is a new float, so increment the unique float counter:

```
5888 \addtocounter{\LWR@thisfloat}{1}%
5889 \booltrue{\LWR@freezethisfloat}%
```

5890 \begingroup

Settings while inside the environment:

5891 \LWR@origraggedright

Open an HTML figure tag:

```
5892 \LWR@htmntag{figure id="autofloat-\arabic{\LWR@thisfloat}" class="#1"}%
5893 \renewcommand*{\@capttype}{#1}
5894 \caption@settype{#1}
5895 \LWR@startpars
5896 }
```

\@float Support packages which create floats directly.  
\@dblfloat  
5897 \let\@float\LWR@floatbegin  
5898 \let\@dblfloat\LWR@floatbegin

\LWR@floatend Ends a \newfloat environment.

```
5899 \newcommand*{\LWR@floatend}{%
5900 \LWR@stoppars%
5901 \LWR@htmlelementend{figure}}%
```

```

5902 \endgroup%
5903 \boolfalse{LWR@freezethisfloat}%
5904 \LWR@startpars%
5905 \ifthenelse{\boolean{FormatWordProcessor}}{\AND\boolean{HTMLMarkFloats}}{%
5906
5907 === end
5908
5909 }{}%
5910 }

```

\end@float Support packages which create floats directly.

```

\end@dblfloat
5911 \let\end@float\LWR@floatend
5912 \let\end@dblfloat\LWR@floatend

```

Ctr LWR@thisfloat A sequential counter for all floats and theorems. This is used to identify the float or theorem then reference it from the List of Figures and List of Tables.

```
5913 \newcounter{LWR@thisfloat}
```

Bool LWR@freezethisfloat Prevents multiple increments of \LWR@thisfloat inside a float.

```

5914 \newbool{LWR@freezethisfloat}
5915 \boolfalse{LWR@freezethisfloat}

```

\LWR@maybeincthisfloat

```

5916 \newcommand*{\LWR@maybeincthisfloat}{%
5917 \ifbool{LWR@freezethisfloat}{}{\addtocounter{LWR@thisfloat}{1}}%
5918 }

```

\@captype Remembers which float type is in use.

```
5919 \newcommand*{\@captype}{}%
```

### 60.1.1 Caption inside a float environment

\CaptionSeparator How to separate the float number and the caption text.

```
5920 \AtBeginDocument{\providecommand*{\CaptionSeparator}{:~}}
```

\@makecaption {\langle name and num \rangle} {\langle text \rangle}

Prints the float type and number, the caption separator, and the caption text.

```
5921 \AtBeginDocument{\renewcommand{\@makecaption}[2]{#1\CaptionSeparator#2}}
```

### 60.1.2 Caption and LOF linking and tracking

When a new `HTML` file is marked in the `LTEX` PDF file, the `LTEX` page number at that point is stored in `LWR@latestautopage`, (and the associated filename is remembered by the special `LTEX` labels). This page number is used to generate an `autofloat` `HTML` `<id>` in the `HTML` output at the start of the new `HTML` file. Meanwhile, there is a float counter used to generate an `HTML` `autofloat <id>` at the start of the float itself in the `HTML` file. The `autopage` and `autofloat` values to use for each float are written to the `.lof`, etc. files just before each float's entry. These values are used by `\l@figure`, etc. to create the `HTML` links in the List of Figures, etc.

- Ctr `LWR@nextautofloat` Tracks autofloat for floats. Tracks autopage for floats.
- Ctr `LWR@nextautopage` These are updated per float as the `.lof` file is read.

```
5922 \newcounter{LWR@nextautofloat}
5923 \newcounter{LWR@nextautopage}
```

`\LWRsetnextfloat {<autopage>} {<autofloat>}`

This is written to the `.lof` file just before each float's usual entry. The `autopage` and `autofloat` are remembered for `\l@figure` to use when creating the `HTML` links.

```
5924 \newcommand*\LWRsetnextfloat[2]{%
5925 \setcounter{LWR@nextautopage}{#1}%
5926 \setcounter{LWR@nextautofloat}{#2}%
5927 }
```

- Ctr `LWR@latestautopage` Updated each time a new `HTML` file is begun. `\LWRsetnextfloat` is written with this and the `autofloat` by the modified `\addcontentsline` just before each float's entry.

```
5928 \newcounter{LWR@latestautopage}
5929 \setcounter{LWR@latestautopage}{1}

5930 \let\LWR@origcaption@begin\caption@begin
5931 \let\LWR@origcaption@end\caption@end
5932 \let\LWR@orig@@par\@@par
```

`\LWR@caption@begin` Low-level patches to create `HTML` tags for captions.

```
5933 \newcommand{\LWR@caption@begin}{%
5934 %
5935 \LWR@traceinfo{\LWR@caption@begin}%
}
```

Keep `par` and `minipage` changes local:

```
5936 \begingroup%
```

The caption code was not allowing the closing par tag:

```
5937 \renewcommand{\@@par}{\LWR@closeparagraph\LWR@orig@@par}%
```

No need for a `minipage` or `\parbox` inside the caption:

```
5938 \RenewDocumentEnvironment{minipage}{O{t} o O{t} m}{}{%
5939 \RenewDocumentCommand{\parbox}{O{t} o O{t} m +m}{{\#5}}%
```

Enclose the original caption code inside an HTML tag:

```
5940 \LWR@htmlblocktag{figcaption}%
5941 \LWR@origcaption@begin%
5942 }
```

`\LWR@caption@end` Low-level patches to create HTML tags for captions.

```
5943 \newcommand{\LWR@caption@end}%
5944 {%
5945 \LWR@origcaption@end%
```

Subcaptions were being over-written by the closing HTML tag:

```
5946 \LWR@origvspace*\{\baselineskip}%
```

Closing tag:

```
5947 \LWR@htmlblocktag{/figcaption}%
5948 \endgroup%
5949 % \leavevmode% avoid bad space factor (0) error
5950 \LWR@traceinfo{\LWR@caption@end: done}%
5951 }
```

`\caption@begin` Low-level patches to create HTML tags for captions.

```
\caption@end
5952 \AtBeginDocument{%
5953 \let\caption@begin\LWR@caption@begin
5954 \let\caption@end\LWR@caption@end
5955 }
```

`\captionlistentry` Tracks the float number for this caption used outside a float. Patched to create an HTML anchor.

```
5956 \let\LWR@origcaptionlistentry\captionlistentry
5957
5958 \renewcommand*{\captionlistentry}{%
```

```

5959 \LWR@maybeincthisfloat%
5960 \LWR@ensuredoingapar%
5961 \LWR@htmlltag{a id="autofloat-\arabic{\LWR@thisfloat}"}\LWR@htmlltag{/a}%
5962 \LWR@origcaptionlistentry%
5963 }
5964
5965 \def\LWR@LTcaptionlistentry{%
5966 \LWR@ensuredoingapar%
5967 \LWR@htmlltag{a id="autofloat-\arabic{\LWR@thisfloat}"}\LWR@htmlltag{/a}%
5968 \bgroup
5969 \ifstar{\egroup\LWR@LT@captionlistentry}{%
5970 {\egroup\LWR@LT@captionlistentry}}%
5971 \def\LWR@LT@captionlistentry#1{%
5972 \caption@listentry\firsofttwo[\LTcaptype]{#1}}%

```

- \addcontentsline** Patched to write the autopage and autofloat before each float's entry. No changes if writing .toc For a theorem, automatically defines \ext@<type> as needed, to mimic and reuse the float mechanism.

```

5973 \let\LWR@origaddcontentsline\addcontentsline
5974
5975 \renewcommand*\addcontentsline[3]{%
5976 \ifthenelse{\equal{#1}{toc}}{}{%
5977 \ifthenelse{\equal{#1}{thm}}{\csdef{ext@#2}{thm}}{%
5978 \addtocontents{\nameuse{ext@#2}}{%
5979 \protect\LWRsetnextfloat{%
5980 {\arabic{\LWR@latestautopage}}{%
5981 {\arabic{\LWR@thisfloat}}{%
5982 }}}{addtocontents{%
5983 }}{not toc}}{%
5984 \LWR@origaddcontentsline{#1}{#2}{#3}}{%
5985 }{%

```

- \captionof** Patched to track the float number since this is used outside a float, and also create an HTML anchor for the virtual float.

```

5986 \AtBeginDocument{
5987 \let\LWR@origcaptionof\captionof
5988
5989 \renewcommand*\captionof{%
5990 \LWR@maybeincthisfloat%
5991 \LWR@stopars
5992 \LWR@htmlltag{a id="autofloat-\arabic{\LWR@thisfloat}"}\LWR@htmlltag{/a}%
5993 \LWR@origcaptionof%
5994 }
5995 }

5996 \end{warpHTML}

```

## 61 Table of Contents, LOF, LOT

This section controls the generation of the TOC, LOF, and LOT.

The .toc, .lof, and .lot files are named by the source code \jobname.

In HTML, the printed tables are placed inside a <div> of class toc, lof, or lot.

A “sidetoc” is provided which prints a subset of the TOC on the side of each page other than the homepage.

The regular L<sup>A</sup>T<sub>E</sub>X infrastructure is used for toc, along with some patches to generate HTML output.

**for HTML output:** 5997 \begin{warpHTML}

### 61.1 Reading and printing the TOC

\LWR@myshorttoc {\langle toc/lof/lot\rangle}

Reads in and prints the TOC/LOF/LOT at the current position. While doing so, makes the @ character into a normal letter to allow formatting commands in the section names.

Unlike in regular L<sup>A</sup>T<sub>E</sub>X, the file is not reset after being read, since the TOC may be referred to again in each HTML page, and is used for the sidetoc.

```
5998 \newcommand*{\LWR@myshorttoc}[1]{  
5999 \LWR@ensuredoingapar
```

Only if the file exists:

```
6000 \IfFileExists{\jobname.#1}{
```

 Make @ a regular letter. Many of the commands in the file will have @ characters in them, so @ must be made a regular letter.

 **disabled** For pdflatex, also change to latin1 encoding. When reading back a file with accented characters, the encoding change seems to be required, rather than leaving it utf8.

```
6001 \begingroup  
6002 % \ifxetexorluatex%  
6003 % \else  
6004 % \inputencoding{latin1}% currently disabled  
6005 % \fi
```

```
6006 \makeatletter
```

Read in the TOC file:

```
6007 \@input{\jobname.#1}
6008 % \makeatother
6009 \endgroup
6010 }%
6011 {%
6012 }
```

```
\LWR@subtableofcontents {\langle toc/lof/lot\rangle} {\langle sectionstarname\rangle}
```

Places a TOC/LOF/LOT at the current position.

```
6013 \NewDocumentCommand{\LWR@subtableofcontents}{m m}{%
```

Closes previous levels:

```
6014 \@ifundefined{chapter}
6015 {\LWR@closeprevious{\LWR@depthsection}}
6016 {\LWR@closeprevious{\LWR@depthchapter}}
```

Prints any pending footnotes so that they appear above the potentially large TOC:

```
6017 \LWR@printpendingfootnotes
```

Place the list into its own chapter (if defined) or section:

```
6018 \@ifundefined{chapter}{\section*{#2}}{\chapter*{#2}}
```

Create a new HTML nav containing the TOC/LOF/LOT:

```
6019 \LWR@htmlelementclass{nav}{#1}
```

Create the actual list:

```
6020 \LWR@myshorttoc{#1}
```

Close the nav:

```
6021 \LWR@htmlelementclassend{nav}{#1}
6022 }
```

Patch \starttoc to encapsulate the TOC inside HTML tags:

```
6023 \let\LWR@orig@starttoc\@starttoc
```

---

```

6024
6025 \renewcommand{\@starttoc}[1]{
6026 \LWR@htmlelementclass{nav}{#1}
6027 \LWR@orig@starttoc{#1}
6028 \LWR@htmlelementclassend{nav}{#1}
6029 }

```

Patch `\tableofcontents`, etc. to print footnotes first. `newfloat` uses `\listoffigures` for all future float types.

```

6030 \let\LWR@origtableofcontents\tableofcontents
6031 \let\LWR@origlistoffigures\listoffigures
6032 \let\LWR@origlistoftables\listoftables
6033
6034 \renewcommand*{\tableofcontents}{%

```

Do not print the table of contents if formatting for a word processor, which will presumably auto-generate its own updated table of contents:

```
6035 \ifbool{FormatWordProcessor}{}{
```

Copy the `.toc` file to `.sidetoc` for printing the `sideroc`. The original `.toc` file is renewed when `\tableofcontents` is finished.

```

6036     \LWR@copyfile{\jobname.toc}{\jobname.sidetoc}%
6037     \LWR@printpendingfootnotes
6038     \LWR@origtableofcontents
6039 }
6040 }
6041 \renewcommand*{\listoffigures}{%
6042 \ifbool{FormatWordProcessor}{}{%
6043     \LWR@printpendingfootnotes
6044     \LWR@origlistoffigures
6045 }
6046 }
6047
6048 \renewcommand*{\listoftables}{%
6049 \ifbool{FormatWordProcessor}{}{%
6050     \LWR@printpendingfootnotes
6051     \LWR@origlistoftables
6052 }
6053 }

```

## 61.2 High-level TOC commands

```
\listof {<type>} {<title>}
```

Emulate the `\listof` command from the `float` package (section 128). Used to create lists of custom float types. Also used to redefine the standard L<sup>A</sup>T<sub>E</sub>X `\listoffigures` and `\listoftables` commands.

```
6054 \NewDocumentCommand{\listof}{m +m}{%
6055 \LWR@subtableofcontents{\@nameuse{ext@\#1}}{\#2}
6056 \expandafter\newwrite\csname tf@\csname ext@\#1\endcsname\endcsname
6057 \immediate\openout \csname tf@\csname ext@\#1\endcsname\endcsname
6058   \jobname.\csname ext@\#1\relax
6059 }
```

### 61.3 Side TOC

The “side TOC” is a table-of-contents positioned to the side.

It may be renamed by redefining `\sidetocname`, and may contain paragraphs.

`css` may be used to format the sideTOC:

*CSS related to sideTOC:*

---

`nav.sidetoc`: The entire sidetoc.  
`div.sidetoctitle`: The title.  
`div.sidetoccontents`: The table of contents.

---

```
6060 \end{warpHTML}
```

**for HTML & PRINT:** 6061 `\begin{warpall}`

**Ctr SideTOCDepth** Controls how deep the side-TOC gets. Use a standard L<sup>A</sup>T<sub>E</sub>X section level similar to `tocdepth`.

```
6062 \newcounter{SideTOCDepth}
6063 \setcounter{SideTOCDepth}{1}
```

`\sidetocname` Holds the default name for the sidetoc.

```
6064 \newcommand{\sidetocname}{Contents}
6065 \end{warpall}
```

**for HTML output:** 6066 `\begin{warpHTML}`

---

\LWR@sidetoc Creates the actual side-TOC.

```
6067 \newcommand*\LWR@sidetoc{%
6068 \LWR@forcenewpage
6069 \LWR@stoppars
6070
```

The entire sidetoc is placed into a nav of class sidetoc.

```
6071 \LWR@htmlelementclass{nav}{sidetoc}
6072
6073 \setcounter{tocdepth}{\value{SideTOCDepth}}
6074
```

The title is placed into a <div> of class sidetoctitle, and may contain paragraphs.

```
6075 \begin{BlockClass}{sidetoctitle}
6076 \sidetocname
6077 \end{BlockClass}
```

The table of contents is placed into a <div> of class sidetoccontents.

```
6078 \begin{BlockClass}{sidetoccontents}
6079 \LinkHome
6080
6081 \LWR@myshorttoc{sidetoc}
6082 \end{BlockClass}
6083 \LWR@htmlelementclassend{nav}{sidetoc}
6084 }
```

## 61.4 Low-level TOC line formatting

\numberline {⟨number⟩}

(Called from each line in the .aux, .lof files.)

Record this section number for further use:

```
6085 \renewcommand*\numberline[1]{%
6086 \LWR@sectionnumber{\#1}\quad%
6087 }
```

\hypertoc {⟨1: depth⟩} {⟨2: type⟩} {⟨3: name⟩} {⟨4: page⟩}

Called by \l@section, etc. to create a hyperlink to a section.

---

The autopage label is always created just after the section.

- #1 is depth
- #2 is section, subsection, etc.
- #3 the text of the caption
- #4 page number

```
6088 \NewDocumentCommand{\hypertoc}{m m +m m}{%
```

Respond to tocdepth:

```
6089 \ifthenelse{\cnttest{#1}{<=}{\value{tocdepth}}}{%
6090     \LWR@startpars%
```

Create an HTML link to filename#autosec-(page), with text of the caption, of the given HTML class.

```
6091     \LWR@subhyperrefclass{%
6092         \LWR@htmlrefsectionfilename{autopage-#4}\#autosec-#4}{#3}{toc#2}%
6093         \LWR@stoppars%
6094 }
6095 {}
6096 }
```

Ctr lofdepth TOC depth for figures.

```
6097 \newcounter{lofdepth}
6098 \setcounter{lofdepth}{1}
```

Ctr lotdepth TOC depth for tables.

```
6099 \newcounter{lotdepth}
6100 \setcounter{lotdepth}{1}
```

```
\hypertocfloat {<1: depth>} {<2: type>} {<3: ext of parent>} {<4: caption>} {<5: page>}
```

- #1 is depth
- #2 is figure, table, etc.
- #3 is lof, lot, of the parent.
- #4 the text of the caption

---

#5 page number

```
6101 \newcommand{\hypertocfloat}[5]{%
6102 \LWR@startpars
```

If some float-creation package has not yet defined the float type's `lofdepth` counter, etc, define it here:

```
6103 \@ifundefined{c@#3depth}{%
6104 \newcounter{#3depth}%
6105 \setcounter{#3depth}{1}%
6106 }{}}%
```

Respond to `lofdepth`, etc.:

```
6107 \LWR@traceinfo{hypertocfloat depth is #1 #3depth is \arabic{#3depth}}%
6108 \ifthenelse{\cnttest{#1}{<=}{\arabic{#3depth}}}{%
6109   \LWR@startpars%
```

Create an HTML link to `filename#autofloat-(float number)`, with text of the caption, of the given HTML class.

```
6110   \LWR@subhyperrefclass{%
6111     \LWR@htmlrefsectionfilename{autopage-\arabic{\LWR@nextautopage}}%
6112     \#autofloat-\arabic{\LWR@nextautofloat}}%
6113     {#4}{toc#2}%
6114   \LWR@stoppars%
6115 }{}}%
6116 }
```

Automatically called by `\contentsline`:

```
6117 \renewcommand{\l@part}[2]{\hypertoc{-1}{part}{#1}{#2}}
6118 \DeclareDocumentCommand{\l@chapter}{m m}
6119   {\hypertoc{0}{chapter}{#1}{#2}}
6120 \renewcommand{\l@section}[2]{\hypertoc{1}{section}{#1}{#2}}
6121 \renewcommand{\l@subsection}[2]{\hypertoc{2}{subsection}{#1}{#2}}
6122 \renewcommand{\l@subsubsection}[2]
6123   {\hypertoc{3}{subsubsection}{#1}{#2}}
6124 \renewcommand{\l@paragraph}[2]{\hypertoc{4}{paragraph}{#1}{#2}}
6125 \renewcommand{\l@ subparagraph}[2]{\hypertoc{5}{subparagraph}{#1}{#2}}
6126 \renewcommand{\l@figure}[2]{\hypertocfloat{1}{figure}{lof}{#1}{#2}}
6127 \renewcommand{\l@table}[2]{\hypertocfloat{1}{table}{lot}{#1}{#2}}
```

6128 \end{warpHTML}

## 62 Index and glossary

See:

[http://tex.stackexchange.com/questions/187038/  
how-to-mention-section-number-in-index-created-by-imakeidx](http://tex.stackexchange.com/questions/187038/how-to-mention-section-number-in-index-created-by-imakeidx)

Index links are tracked by the counter LWR@autoindex. This counter is used to create a label for each index entry, and a reference to this label for each entry in the index listing. This method allows each index entry to link directly to its exact position in the document.

```
for HTML output: 6129 \begin{warpHTML}

6130 \newcounter{LWR@autoindex}
6131 \setcounter{LWR@autoindex}{0}
6132
6133 \newcounter{LWR@autoglossary}
6134 \setcounter{LWR@autoglossary}{0}

\printindex

6135 \let\LWR@origprintindex\printindex
6136
6137 \renewcommand*\printindex{
6138 {
6139 \LWR@startpars
6140 \LWR@origprintindex
6141 }

Env theindex

6142 \@ifundefined{chapter}
6143 {\newcommand*{\LWR@indexsection}[1]{\section*{#1}}}
6144 {\newcommand*{\LWR@indexsection}[1]{\chapter*{#1}}}
6145
6146 \renewenvironment*{theindex}{%
6147 \LWR@indexsection{\indexname}%
6148 \let\item\LWR@indexitem%
6149 \let\subitem\LWR@indexsubitem%
6150 \let\subsubitem\LWR@indexsubsubitem%
6151 }{}}
```

\LWR@indexitem

```
6152 \newcommand{\LWR@indexitem}{%
6153 }
```

---

```

6154 \InlineClass{indexitem}{}
6155 }

\LWR@indexitem

6156 \newcommand{\LWR@indexsubitem}{%
6157
6158 \InlineClass{indexsubitem}{}
6159 }

\LWR@indexitem

6160 \newcommand{\LWR@indexsubsubitem}{%
6161
6162 \InlineClass{indexsubsubitem}{}
6163 }

\@wrindex {⟨term⟩}      Redefined to write the LWR@latestautopage counter instead of page

6164 \def\@wrindex#1{%
6165 \addtocounter{LWR@autoindex}{1}%
6166 \LWR@newlabel{LWRindex-\theLWR@autoindex}%
6167 \protected@write\@indexfile{}}%
6168 {\string\indexentry{#1}{\theLWR@autoindex}}%
6169 \endgroup
6170 \@esphack}

\@wrglossary {⟨term⟩}      Redefined to write the LWR@latestautopage counter instead of page

6171 \def\@wrglossary#1{%
6172 \addtocounter{LWR@autoglossary}{1}%
6173 \LWR@newlabel{LWRglossary-\theLWR@autoglossary}%
6174 \protected@write\@glossaryfile{}}%
6175 {\string\glossaryentry{#1}{\theLWR@autoglossary}}%
6176 \endgroup
6177 \@esphack}

\hyperindexref {⟨autosecnumber⟩}

\hyperindexref{web address} is inserted into *.ind by the xindy style file lwarp.xdy

6178 \newcommand*{\hyperindexref}[1]{\nameref{LWRindex-#1}]

6179 \end{warpHTML}

```

**for PRINT output:** A null command for print mode, in case hyperref was not used:

```
6180 \begin{warpprint}
6181 \newcommand{\hyperindexref}[1]{#1}
6182 \end{warpprint}
```

**for HTML & PRINT:** For the glossaries package, try to prevent an error where `\glo@name` was not found:

```
6183 \begin{warpall}
6184 \providecommand{\glo@name}{}%
6185 \end{warpall}
```

## 63 Math

- ⚠ Equation numbering** ntheorem has a bug with equation numbering in  $\mathcal{AMS}$  environments when the option `thref` is used. lwarp does not share this bug, so equations with `\split`, etc, are numbered correctly with lwarp's HTML output, but not with the print output. It is recommended to use `cleveref` instead of ntheorem's `thref` option.
- Math rendering** Math may be rendered as SVG graphics or using the MATHJAX JavaScript display engine.
- SVG math option** For SVG math, math is rendered as usual by L<sup>A</sup>T<sub>E</sub>X into the initial PDF file using the current font<sup>13</sup>, then is captured from the PDF and converted to SVG graphics via a number of utility programs. The SVG format is a scalable-vector web format, so math may be typeset by L<sup>A</sup>T<sub>E</sub>X with its fine control and precision, then displayed or printed at any size, depending on (sometimes broken) browser support. An HTML `alt` attribute carries the L<sup>A</sup>T<sub>E</sub>X code which generated the math, allowing copy/paste of the L<sup>A</sup>T<sub>E</sub>X math expression into other documents.
- SVG image font size** The size of the math and text used in the SVG image may be adjusted by setting `\LateximageFontSizeName` to a font size name — *without the backslash*, for ex:  
`\renewcommand{\LateximageFontSizeName}{large}`
- SVG files** As currently implemented, each instance of math creates a new SVG file. In text with many references to math variables, this can result in a large number of files with duplicate content. In the future, some method of content-based naming and checksumming may be used to remove the need for duplicate files.
- SVG inline** Another approach would be to in-line the SVG files directly into the HTML. This avoids having a large number of files and potentially speeds loading the images, but dis-allows the possibility of sharing one file among many instances without user intervention.

---

<sup>13</sup>See section 240 regarding fonts and fractions.

**PNG files** Others have used PNG files, sometimes pre-scaled for print resolution but displayed on-screen at a scaled down size. This allows high-quality print output at the expense of larger files, but SVG files are also larger as well.

**MathML** Conversion to MathML might be a better approach, among other things allowing a more compact representation of math than SVG drawings. Problems with MathML include limited browser support and some issues with the fine control of the appearance of the result. Also see section 8 regarding EPUB output with MathJax.

**MathJax math option** The popular MathJax alternative ([mathjax.org](http://mathjax.org)) may be used to display math.

Prog MathJax

When MathJax is enabled, math is rendered twice:

1. As regular  $\text{\TeX}$  PDF output placed inside an HTML comment, allowing equation numbering and cross referencing to be almost entirely under the control of  $\text{\TeX}$ , and
2. As detokenized printed  $\text{\TeX}$  commands placed directly into the HTML output for interpretation by the MathJax display scripts. An additional script is used to pre-set the equation number format and value according to the current  $\text{\TeX}$  values, and the MathJax cross-referencing system is ignored in favor of the  $\text{\TeX}$  internal system, seamlessly integrating with the rest of the  $\text{\TeX}$  code.

**MathJax limitations** Limitations when using MathJax include:

Prog MathJax

**chapter numbers**

- In document classes which have chapters, \tagged equations have the chapter number prepended in HTML output, unlike  $\text{\TeX}$ . \tag\* equations (correctly) do not. This may be improved with future versions of the MathJax support script.

<https://groups.google.com/forum/#!topic/mathjax-users/jUtewUcE2bY>

**subequations**

- MathJax itself does not support subequations. This may be improved by parsing the  $\text{\TeX}$  math expression to manually insert tags, but this has not yet been done.

**footnotes in math**

**lateximage**

- Footnotes inside equations are not yet supported while using MathJax.

- Math appearing inside a lateximage, and therefore also inside a Tikz or picture environment, is rendered as SVG math even if MathJax is used in the rest of the document.

**siunitx**

- Usage of siunitx inside a math equation is supported via a third-party MathJax extension. While inside a math expression, do not use \SI or \si inside \text, where it will be rendered as normal text.

<https://github.com/mathjax/MathJax-third-party-extensions/tree/master/siunitx>

 **siunitx inside an equation**

- \TeX macros**
- MathJax does not automatically support custom \TeX macros, but they may be set up by the user.

**custom MathJax macros** As an example of using custom \TeX macros with MathJax, place the following at the start of the document, after \begin{document}:

---

```
\begin{warpHTML} % Only for HTML output,
\ifbool{mathjax} % and only for MathJax output:
{
  % New macros for MathJax are placed inside a math expression:
  \newcommand{\expval}[1]{\langle #1\rangle}
  \newcommand{\abs}[1]{\lvert#1\rvert}
}
\end{warpHTML}
```

---

**for HTML output:** 6186 \begin{warpHTML}

\\$ Plain dollar signs appearing in the HTML output may be interpreted by MathJax to be math shifts. For a plain text dollar \\$, print it inside a span to avoid it being interpreted by MathJax, unless are inside a lateximage, in which case it will not be seen by MathJax.

```
6187 \let\LWR@origtextdollar\
6188
6189 \renewcommand*{\$}{%
6190 \ifthenelse{\cnttest{\value{\LWR@lateximagedepth}}{>}{0}}{%
6191 {\LWR@origtextdollar}%
6192 {\LWR@htmltagc{span}\LWR@origtextdollar\LWR@htmltagc{/span}}%
6193 }}
```

Ctr LWR@externalfilecnt Counter for the external files which are generated and then referenced from the HTML:

```
6194 \newcounter{LWR@externalfilecnt}
```

### 63.1 Inline and display math

```
6195 \LetLtxMacro{\LWR@origdollar$}%
6196 \LetLtxMacro{\LWR@secondorigdollar$}{% balance for editor syntax highlighting
6197 \LetLtxMacro{\LWR@origopenparen}{%
6198 \LetLtxMacro{\LWR@origcloseparen}{%
```

---

```
6199 \LetLtxMacro{\LWR@origopenbracket}{[}
6200 \LetLtxMacro{\LWR@origclosebracket}{]}
```

\$ Redefine the dollar sign to place math inside a `lateximage`, or use MathJax:  
 \$\$

```
6201 \begingroup
6202 \catcode`\$=\active%
6203 \protected\gdef\$`{@ifnextchar${\LWR@doubledollar}{\LWR@singledollar}}%
```

`\LWR@doubledollar` Redefine the double dollar sign to place math inside a `lateximage`, or use MathJax:

```
6204 \gdef\LWR@doubledollar##1$${
6205 \ifbool{mathjax}{}
```

For MathJax, print the math between `\[` and `\]`:

```
6206 {\textbackslash[\LWR@HTMLsanitize[#1]\textbackslash]}
```

For SVG, print the math inside a `lateximage`, with an ALT tag of the `\textrm` code:

```
6207 {%
  not mathjax
6208
6209 \begin{lateximage}%
6210 [\textbackslash[\LWR@HTMLsanitize[]\textbackslash]]%
6211 \LWR@origdollar\LWR@origdollar#1\LWR@origdollar\LWR@origdollar%
6212 \end{lateximage}
6213
6214 }
6215 }%
```

`\LWR@singledollar` Redefine the single dollar sign to place math inside a `lateximage`, or use MathJax:

```
6216 \gdef\LWR@subsingledollar#1{%
6217 \ifbool{mathjax}{}
```

For MathJax, print the math between `\(` and `\)`:

```
6218 {\textbackslash(\LWR@HTMLsanitize[#1]\textbackslash)}
```

For SVG, print the math inside a `lateximage`, with an ALT tag of the `\textrm` code:

```
6219 {%
  not mathjax
6220   \begin{lateximage}%
6221     [\textbackslash(\LWR@HTMLsanitize[#1]\textbackslash)]%
6222     \LWR@origdollar#1\LWR@origdollar%
6223   \end{lateximage}
6224 }%
6225 }
```

```

6226
6227 \gdef\LWR@singledollar#1${%
6228 \LWR@subsingledollar{#1}%
6229 }

```

```

\(\ Redefine to the above dollar macros.
\)
6230 \gdef\(#1\){$#1$}
6231 \gdef\[#1\]{$$#1$$}
6232
6233 \endgroup
6234
6235
6236

```

\@ensuredmath {*expression*} Not yet adapted to \warp.

```

6237 \let\LWR@orig@ensuredmath\@ensuredmath
6238
6239 \newcommand*{\LWR@ensuredmath}[1]{%
6240 \LWR@traceinfo{@ensuredmath: page \thepage: \detokenize{#1}}%
6241 \LWR@subsingledollar{#1}%
6242 }

```

Remove the old `math` and `displaymath` environments:

```

6243 \let\math\relax
6244 \let\endmath\relax
6245 \let\displaymath\relax
6246 \let\enddisplaymath\relax

```

`Env math` Set math mode then typeset the body of what was between the begin/end. See the `environ` package for \BODY.

```
6247 \NewEnviron{math}{\expandafter\(\BODY\)}
```

`Env displaymath` Set math mode then typeset the body of what was between the begin/end. See the `environ` package for \BODY.

```
6248 \NewEnviron{displaymath}{\expandafter\[\BODY\]\@ignoretrue}
```

## 63.2 MathJax support

`Ctr LWR@nextequation` Used to add one to compute the next equation number.

---

```
6249 \newcounter{LWR@nextequation}
```

\LWR@syncmathjax Sets the MathJax equation format and number for the following equations.

These MathJax commands are printed inside “ $\left($ ” and “ $\right)$ ” characters. They are printed to **HTML** output, not interpreted by **LATEX**.

```
6250 \newcommand*\LWR@syncmathjax{}%
```

If using chapters, place the chapter number in front of the equation. Otherwise, use the simple equation number.

```
6251 \ifcsdef{thechapter}{
6252   \InlineClass{hidden}{
6253     \textbackslash(
6254     \textbackslash) \seteqsection {\thechapter}
6255   \textbackslash)
6256 }
6257 }
6258 {}% not using chapters
```

MathJax doesn't allow setting the equation number to 1:

```
6259 \ifthenelse{\cnttest{\value{equation}}>0}
6260 {
```

Tell MathJax that the next set of equations begins with the current **LATEX** equation number, plus one.

```
6261 \setcounter{LWR@nextequation}{\value{equation}}
6262 \addtocounter{LWR@nextequation}{1}
```

Place the MathJax command inside “ $\left($ ” and “ $\right)$ ” characters, to be printed to **HTML**, not interpreted by **LATEX**.

```
6263 \InlineClass{hidden}{
6264   \textbackslash(
6265   \textbackslash) \seteqnumber {\arabic{LWR@nextequation}}
6266   \textbackslash)
6267 }
6268 {}% not eq > 0
6269 }
```

\LWR@restoreorigformatting While producing **SVG** math or a **lateximage**, use regular **LATEX** formatting instead of **HTML** tags.

Various packages add to this macro using **\appto**.

```
6270 \newcommand*\{LWR@restoreorigformatting}{%
6271 \LWR@traceinfo{LWR@restoreorigformatting}%
6272 \RenewDocumentCommand{\InlineClass}{o m +m}{##3}%
6273 \RenewDocumentEnvironment{BlockClass}{o m}{}{}%
6274 \renewcommand{\BlockClassSingle}[2]{##2}%
6275 \LetLtxMacro{\hspace}{\LWR@orighspace}%
6276 \LetLtxMacro{\rule}{\LWR@origrule}%
6277 \let\,\LWR@origcomma% disable HTML short unbreakable space
6278 \let\textellipsis\LWR@origtextellipsis%
6279 \let\textless\LWR@origtextless%
6280 \let\textgreater\LWR@origtextgreater%
6281 \LetLtxMacro{\textrm}{\LWR@origtextrm}%
6282 \LetLtxMacro{\textsf}{\LWR@origtextsf}%
6283 \LetLtxMacro{\texttt}{\LWR@origtexttt}%
6284 \LetLtxMacro{\textbf}{\LWR@origtextbf}%
6285 \LetLtxMacro{\textmd}{\LWR@origtextmd}%
6286 \LetLtxMacro{\textit}{\LWR@origtextit}%
6287 \LetLtxMacro{\textsl}{\LWR@origtextsl}%
6288 \LetLtxMacro{\textsc}{\LWR@origtextsc}%
6289 \LetLtxMacro{\textup}{\LWR@origtextup}%
6290 \LetLtxMacro{\textnormal}{\LWR@origtextnormal}%
6291 \LetLtxMacro{\emph}{\LWR@origemph}%
6292 \LetLtxMacro{\rmfamily}{\LWR@origrmfamily}%
6293 \LetLtxMacro{\sffamily}{\LWR@origsffamily}%
6294 \LetLtxMacro{\ttfamily}{\LWR@origttfamily}%
6295 \LetLtxMacro{\bfseries}{\LWR@origbfseries}%
6296 \LetLtxMacro{\mdseries}{\LWR@origmdseries}%
6297 \LetLtxMacro{\upshape}{\LWR@origupshape}%
6298 \LetLtxMacro{\slshape}{\LWR@origslshape}%
6299 \LetLtxMacro{\scshape}{\LWR@origscshape}%
6300 \LetLtxMacro{\itshape}{\LWR@origitshape}%
6301 \LetLtxMacro{\em}{\LWR@origem}%
6302 \LetLtxMacro{\normalfont}{\LWR@orignormalfont}%
6303 \let\sp\LWR@origsp%
6304 \let\sb\LWR@origsb%
6305 \let\textsuperscript{\LWR@origtextsuperscript}%
6306 \let\textsubscript{\LWR@origtextsubscript}%
6307 \LetLtxMacro{\underline}{\LWR@origunderline}%
6308 \let~\LWR@origtilde%
6309 \let\enskip\LWR@origenskip%
6310 \let\quad\LWR@origquad%
6311 \let\qquad\LWR@origqquad%
6312 \LetLtxMacro{\tabular}{\LWR@origtabular}%
6313 \LetLtxMacro{\endtabular}{\LWR@origendtabular}%
6314 \LetLtxMacro{\toprule}{\LWR@origtoprule}%
6315 \LetLtxMacro{\midrule}{\LWR@origmidrule}%
6316 \LetLtxMacro{\cmidrule}{\LWR@origcmidrule}%
6317 \LetLtxMacro{\bottomrule}{\LWR@origbottomrule}%
6318 \LetLtxMacro{\addlinespace}{\LWR@origaddlinespace}%
6319 \LetLtxMacro{\morecmidrules}{\LWR@origmorecmidrules}%
```

```

6320 \LetLtxMacro{\specialrule}{\LWR@origspecialrule}%
6321 \let\newline{\LWR@orignewline}%
6322 \LetLtxMacro{\raisebox}{\LWR@origraisebox}%
6323 \LetLtxMacro{\includegraphics}{\LWR@origincludegraphics}%
6324 \LetLtxMacro{\scalebox}{\LWR@origscalebox}%
6325 \LetLtxMacro{\rotatebox}{\LWR@origrotatebox}%
6326 \let\reflectbox{\LWR@origreflectbox}%
6327 \LetLtxMacro{\resizebox}{\LWR@origresizebox}%
6328 \let\framebox{\LWR@origframebox}%
6329 \let\makebox{\LWR@origmakebox}%
6330 \let\fbox{\LWRprint@fbox}%
6331 \let\fboxBlock{\LWRprint@fbox}%
6332 \LetLtxMacro{\fminipage}{\LWRprint@fminipage}%
6333 \LetLtxMacro{\endfminipage}{\endLWRprint@fminipage}%
6334 \LetLtxMacro{\minipage}{\LWR@origminipage}%
6335 \let\endminipage{\LWR@endminipage}%
6336 \LetLtxMacro{\parbox}{\LWR@origparbox}%
6337 \let\TeX{\LWR@origTeX}%
6338 \let\LaTeX{\LWR@origLaTeX}%
6339 \let\LaTeXe{\LWR@origLaTeXe}%
6340 \renewcommand*{\Xe}[X]{\textsubscript{E}}%
6341 %
6342 \LWR@restoreorigaccents%
6343 %
6344 \LWR@FBcancel%
6345 }

```

\LWR@hidelatexequation {*environment*} {*contents*}

Creates the  $\text{\TeX}$  version of the equation inside an HTML comment.

```
6346 \NewDocumentCommand{\LWR@hidelatexequation}{m +m}-%
```

Stop HTML paragraph handling and open an HTML comment:

```

6347 \LWR@stopars
6348 \LWR@htmlopencomment
6349

```

Start the  $\text{\TeX}$  math environment inside the HTML comment:

```

6350 \begingroup
6351 \csuse{\LWR@orig#1}

```

While in the math environment, restore various commands to their  $\text{\TeX}$  meanings.

```
6352 \LWR@restoreorigformatting
```

See \LWR@htmlmathlabel in section 63.4.1.

Print the contents of the equation:

6353 #2

End the  $\text{\TeX}$  math environment inside the HTML comment:

```
6354 \csuse{LWR@origend#1}
6355 \endgroup
6356
```

Close the HTML comment and resume HTML paragraph handling:

```
6357 \LWR@htmlclosecomment
6358 \LWR@startpars
6359 }
```

`\LWR@addmathjax {<environment>} {<contents>}`

Given the name of a math environment and its contents, create a MathJax instance. The contents are printed to HTML output, not interpreted by  $\text{\TeX}$ .

6360 \NewDocumentCommand{\LWR@addmathjax}{m +m}{%

Enclose the MathJax environment inside printed “\(” and “\)” characters.

```
6361 \LWR@origtilde\LWR@orignewline
6362 \textbackslash{}begin\{\#1\}
```

Print the contents, sanitizing for HTML special characters.

6363 \LWR@HTMLsanitizeexpand{\detokenize\expandafter{\#2}}

Close the MathJax environment:

```
6364 \textbackslash{}end\{\#1\}
6365 \LWR@orignewline
6366 }
```

### 63.3 Equation environment

Remember existing `equation` environment:

```
6367 \let\LWR@origequation\equation
6368 \let\LWR@origendequation\endequation
```

Remove existing equation environment:

```
6369 \let\equation\relax
6370 \let\endequation\relax
```

**Env equation** The new equation environment is created with `\NewEnviron` (from the `environ` package), which stores the contents of its environment in a macro called `\BODY`.

For SVG math output, the contents are typeset using the original `equation` inside a `lateximage`, along with an `ALT` tag containing a detokenized copy of the `LATEX` source for the math.

For MathJax output, the contents are typeset in an original `equation` environment placed inside a `HTML` comment, with special processing for `\labels`. The contents are also printed to the `HTML` output for processing by the MathJax script.

```
6371 \NewEnviron{equation}{%
6372   \ifbool{mathjax}{%
6373     \begin{HTML}<!--</pre>

```

MathJax output:

```
6374 {
```

Print commands to synchronize MathJax's equation number and format to the current `LATEX` chapter/section and equation number:

```
6375   \LWR@syncmathjax
```

Print the `LATEX` math inside an `HTML` comment:

```
6376   \LWR@hidelatexequation{equation}{\BODY}
6377 }
```

SVG output: Create the `lateximage` along with an `HTML` `ALT` tag having an equation number, the `LATEX` equation environment commands, and the contents of the environment's `\BODY`.

```
6378 {%
```

Begin the `lateximage` with an `ALT` tag containing the math source:

```
6379   \begin{lateximage}[(\theequation) \textbackslash begin\{equation\}]%
6380     \LWR@HTMLsanitizeexpand{\detokenize\expandafter{\BODY}}%
6381     \textbackslash end\{equation\}]% alt tag
```

Create the actual  $\text{\TeX}$ -formatted equation inside the `lateximage` using the contents of the environment.

```
6382     \LWR@origequation
6383     \BODY% contents collected by NewEnviron
6384     \LWR@origendequation
6385     \end{lateximage}%
6386 }
6387
```

After the environment, if MathJax, print the math to the HTML output for MathJax processing:

```
6388 }[\ifbool{mathjax}{\LWR@addmathjax{equation}{\BODY}}{}]
```

## 63.4 AMS Math environments

### 63.4.1 Support macros

`Bool LWR@amsmultiline` True if processing a multiline environment.

To compensate for `multiline`-specific code, `LWR@amsmultiline` is used to add extra horizontal space in `\LWR@htmlmathlabel` if it is used in an `amsmath` environment which is not a `multiline` environment and not an `equation`.

```
6389 \newbool{LWR@amsmultiline}
6390 \boolfalse{LWR@amsmultiline}
```

`\LWR@htmlmathlabel {<label>}`

`lwarp` points `\ltx@label` here. This is used by `\label` when inside a  $\text{\TeX}$  AMS math environment's math display environment.

`\LWR@origltx@label` points to the  $\text{\TeX}$  original, modified by `lwarp`, then by `amsmath`, then by `cleveref`.

```
6391 \newcommand*{\LWR@htmlmathlabel}[1]{%
6392 \LWR@traceinfo{\LWR@htmlmathlabel #1}%
6393 \ifbool{mathjax}{%
```

The combined  $\text{\TeX}$  & HTML label is printed in a `\text` field:

```
6394 \text{
```

Shift the label over to the right side of the environment to avoid over-printing the math:

```
6395 \ifbool{LWR@amsmultline}{}{\hspace*{\totwidth@}}
```

Temporarily end the HTML comment, insert the L<sup>E</sup>T<sub>E</sub>X & HTML label, then resume the HTML comment. \@firstofone is required to remove extra braces introduced by the amsmath package.)

```
6396 \LWR@htmlclosecomment%
6397 \LWR@origltx@label{#1}%
6398 \LWR@htmlopencomment%
6399 }% text
6400 }% mathjax
6401 {%
6402 \LWR@origltx@label{#1}%
6403 }%
6404 }
```

\LWR@beginhideamsmath Starts hiding L<sup>E</sup>T<sub>E</sub>X math inside an HTML comment.

```
6405 \newcommand*{\LWR@beginhideamsmath}{%
6406 \LWR@stoppars
6407 \LWR@origtilde\LWR@orignewline
6408 \LWR@htmlopencomment
6409
6410 \begingroup
6411 \LWR@restoreorigformatting
6412 }
```

\LWR@endhideamsmath Ends hiding L<sup>E</sup>T<sub>E</sub>X math inside an HTML comment.

```
6413 \newcommand*{\LWR@endhideamsmath}{%
6414 \endgroup
6415
6416 \LWR@htmlclosecomment
6417 \LWR@orignewline
6418 \LWR@startpars
6419 }
```

### 63.4.2 Environment patches

The following amsmath environments already collect their contents in \@envbody for further processing. eqnarray is not an *AMS* package, and thus requires special handling.

For SVG math: Each environment is encapsulated inside a `lateximage` environment, along with a special `LWR@AMS@MATHBODY` argument telling `lateximage` to use as the HTML ALT tag the environment's contents which were automatically captured by the `\AMS` environment.

For MathJax: Each environment is synched with L<sup>A</sup>T<sub>E</sub>X's equation numbers, typeset with L<sup>A</sup>T<sub>E</sub>X inside an HTML comment, then printed to HTML output for MathJax to process.

Env `eqnarray` This environment is not an `\AMS` environment and thus its body is not automatically captured, so the `environ` package is used to capture the environment into `\BODY`.

```
6420 \let\LWR@origeqnarray\eqnarray
6421 \let\LWR@origendeqnarray\endeqnarray
```

To remember whether the starred environment was used, and thus whether to number the equations:

```
6422 \newbool{LWR@numbereqnarray}
6423 \booltrue{LWR@numbereqnarray}
```

Common code used by `eqnarray` and `Beqnarray` (from `fancybox`):

```
6424 \newcommand{\LWR@eqnarrayfactor}{%
```

Different behavior depending on MathJax vs SVG math:

```
6425 \ifbool{mathjax}
6426 {
```

If MathJax, the environment contents (the `\BODY`) are executed in a HTML comment to trigger the correct equation number increment (if not starred), then are included verbatim in the output for MathJax to interpret:

```
6427     \LWR@syncmathjax
6428     \boolfalse{LWR@amsmultiline}
6429     \ifbool{LWR@numbereqnarray}
6430     {
```

If numbering the equations, execute a copy inside an HTML comment block:

```
6431     \LWR@beginhideamsmath
6432     \LWR@origeqnarray
6433     \BODY
6434     \LWR@origendeqnarray
6435     \LWR@endhideamsmath
```

Then print the (sanitized) contents to the output for MathJax to interpret:

```
6436      \LWR@addmathjax{eqnarray}{\BODY}
6437      }%
6438      {%
6439      \LWR@addmathjax{eqnarray*}{\BODY}
```

If not numbering equations, just create the contents for MathJax:

```
6440      }% LWR@numbereqnarray
6441 }% mathjax
6442 {%
6443      \ifbool{LWR@numbereqnarray}
6444      {
```

For numbered SVG equations, first create a `lateximage` with an `alt` attribute containing sanitized copy of the source code:

```
6445      \begin{lateximage}[\LWR@addmathjax{eqnarray}{\BODY}]
```

Then create the image contents using an actual `eqnarray`:

```
6446      \LWR@origeqnarray
6447      \BODY
6448      \LWR@origendeqnarray
6449      \end{lateximage}
6450      }%
6451      {%
6452      \LWR@origeqnarray
```

If not numbered, do the same, but an extra `\nonumber` seems to be required:

```
6452      \begin{lateximage}[\LWR@addmathjax{eqnarray*}{\BODY}]
6453      \LWR@origeqnarray
6454      \BODY
6455      \nonumber
6456      \LWR@origendeqnarray
6457      \end{lateximage}
6458      }% LWR@numbereqnarray
6459 }% not mathjax
```

Default to number equations in the future:

```
6460 \booltrue{LWR@numbereqnarray}
6461 }
```

`eqnarray` itself is made with a blank line before and after to force it to be on its own line:

```

6462 \RenewEnviron{eqnarray}
6463 {%
6464
6465 \LWR@eqnarrayfactor
6466
6467 }

```

The starred version is patched to turn off the numbering:

```
6468 \csgpreto{eqnarray*}{\boolfalse{LWR@numbereqnarray}}
```

The following *AMS* environments are more easily patched in-place:

Env **multiline**

```

6469 \BeforeBeginEnvironment{multiline}{
6470
6471 \ifbool{mathjax}
6472 {
6473     \LWR@syncmathjax
6474     \booltrue{LWR@amsmultiline}
6475     \LWR@beginhideamsmath
6476 }
6477 {
6478     \latexitimage[LWRAMSMATHBODY]
6479 }
6480 }
6481
6482 \AfterEndEnvironment{multiline}{
6483
6484 \ifbool{mathjax}
6485 {
6486     \LWR@endhideamsmath
6487     \boolfalse{LWR@amsmultiline}
6488     \LWR@addmathjax{multiline}{\the\@envbody}
6489 }
6490 {\endlatexitimage}
6491
6492 }

```

Env **multiline\***

```

6493 \BeforeBeginEnvironment{multiline*}{
6494
6495 \ifbool{mathjax}
6496 {
6497     \LWR@syncmathjax

```

```
6498     \booltrue{LWR@amsmultiline}
6499     \LWR@beginhideamsmath
6500 }
6501 {
6502     \lateximage[LWRAMSMATHBODY]
6503 }
6504 }
6505
6506 \AfterEndEnvironment{multline*}{
6507
6508 \ifbool{mathjax}
6509 {
6510     \LWR@endhideamsmath
6511     \boolfalse{LWR@amsmultiline}
6512     \LWR@addmathjax{multline*}{\the\@envbody}
6513 }
6514 {\endlatexitimage}
6515
6516 }
6517
```

Env gather

```
6518 \BeforeBeginEnvironment{gather}{
6519
6520 \ifbool{mathjax}
6521 {
6522     \LWR@syncmathjax
6523     \boolfalse{LWR@amsmultiline}
6524     \LWR@beginhideamsmath
6525 }
6526 {
6527     \latexitimage[LWRAMSMATHBODY]
6528 }
6529 }
6530
6531 \AfterEndEnvironment{gather}{
6532
6533 \ifbool{mathjax}
6534 {
6535     \LWR@endhideamsmath
6536     \LWR@addmathjax{gather}{\the\@envbody}
6537 }
6538 {\endlatexitimage}
6539
6540 }
```

Env gather\*

```
6541 \BeforeBeginEnvironment{gather*}{

6542
6543 \ifbool{mathjax}
6544 {
6545     \LWR@syncmathjax
6546     \boolexpr{\LWR@amsmultiline}
6547     \LWR@beginhideamsmath
6548 }
6549 {
6550     \latextimage[LWRAMSMATHBODY]
6551 }
6552 }
6553
6554 \AfterEndEnvironment{gather*}{

6555
6556 \ifbool{mathjax}
6557 {
6558     \LWR@endhideamsmath
6559     \LWR@addmathjax{gather*}{\the\@envbody}
6560 }
6561 {\endlatextimage}
6562
6563 }
```

Env align

```
6564 \BeforeBeginEnvironment{align}{

6565
6566 \ifbool{mathjax}
6567 {
6568     \LWR@syncmathjax
6569     \boolexpr{\LWR@amsmultiline}
6570     \LWR@beginhideamsmath
6571 }
6572 {
6573     \latextimage[LWRAMSMATHBODY]
6574 }
6575 }
6576
6577 \AfterEndEnvironment{align}{

6578
6579 \ifbool{mathjax}
6580 {
6581     \LWR@endhideamsmath
6582     \LWR@addmathjax{align}{\the\@envbody}
6583 }
6584 {\endlatextimage}
```

```
6585
6586 }

Env  align*
6587 \BeforeBeginEnvironment{align*}{

6588
6589 \ifbool{mathjax}
6590 {
6591     \LWR@syncmathjax
6592     \boolefalse{\LWR@amsmultiline}
6593     \LWR@beginhideamsmath
6594 }
6595 {
6596     \lateximage[LWRAMSMATHBODY]
6597 }
6598 }
6599
6600 \AfterEndEnvironment{align*}{

6601
6602 \ifbool{mathjax}
6603 {
6604     \LWR@endhideamsmath
6605     \LWR@addmathjax{align*}{\the\@envbody}
6606 }
6607 {\endlatexitimage}
6608
6609 }
```

Env flalign

```
6610 \BeforeBeginEnvironment{flalign}{

6611
6612 \ifbool{mathjax}
6613 {
6614     \LWR@syncmathjax
6615     \boolefalse{\LWR@amsmultiline}
6616     \LWR@beginhideamsmath
6617 }
6618 {
6619     \latexitimage[LWRAMSMATHBODY]
6620 }
6621 }
6622
6623 \AfterEndEnvironment{flalign}{

6624
6625 \ifbool{mathjax}
6626 {
```

```

6627      \LWR@endhideamsmath
6628      \LWR@addmathjax{flalign}{\the\@envbody}
6629 }
6630 {\endlateximage}
6631
6632 }

Env flalign*
6633 \BeforeBeginEnvironment{flalign*}{

6634
6635 \ifbool{mathjax}
6636 {
6637     \LWR@syncmathjax
6638     \boolexpr{LWR@amsmultiline}
6639     \LWR@beginhideamsmath
6640 }
6641 {
6642     \latexitimage[LWRAMSMATHBODY]
6643 }
6644 }
6645
6646 \AfterEndEnvironment{flalign*}{

6647
6648 \ifbool{mathjax}
6649 {
6650     \LWR@endhideamsmath
6651     \LWR@addmathjax{flalign*}{\the\@envbody}
6652 }
6653 {\endlateximage}
6654
6655 }

6656 \end{warpHTML}

```

## 64 Lateximages

A `\latexitimage` is typeset on its own PDF page inside an HTML comment which starts on the preceding page and ends on following page, and instructions are written to `latexitimage.txt` for `lwarfpmk` to extract the `\latexitimage` from the page of the PDF file then generate an accompanying `.svg` file image file. Meanwhile, instructions to show this image are placed into the HTML file after the comment.

An HTML span is created to hold both the HTML comment, which will have the `pdftotext` conversion, and also the link to the final `.svg` image.

A  $\text{\LaTeX}$  label is used to remember which PDF page has the image. A label is used because footnotes, endnotes, and pagenotes may cause the image to appear at a later time. The label is declared along with the image, and so it correctly remembers where the image finally ended up.

**SVG image font size** The size of the math and text used in the svg image may be adjusted by setting `\LateximageFontSizeName` to a font size name — *without the backslash*, for ex:  
`\renewcommand{\LateximageFontSizeName}{large}`

**for HTML output:** 6657 `\begin{warpHTML}`

Ctr `LWR@lateximagenumber` Sequence the images.

```
6658 \newcounter{LWR@lateximagenumber}
6659 \setcounter{LWR@lateximagenumber}{0}
```

Ctr `LWR@lateximagedepth` Do not create `\lateximage` inside of `\latexitimage`.

```
6660 \newcounter{LWR@lateximagedepth}
6661 \setcounter{LWR@lateximagedepth}{0}
```

A few utility macros to write special characters:

```
6662 \edef\LWR@hashmark{\string#} % for use in \write
6663 \edef\LWR@percent{\@percentchar} % for use in \write
```

Ctr `LWR@LIpage` Used to reference the PDF page number of a `latexitimage` to be written into `latexitimages.txt`.

```
6664 \newcounter{LWR@LIpage}
```

```
6665 \end{warpHTML}
```

**for HTML & PRINT:** 6666 `\begin{warpall}`

`\LateximageFontSizeName` Declares how large to write text in the `\latexitimage`. The `.svg` file text size should blend well with the surrounding HTML text size.

*Do not include the leading backslash in the name.*

```
6667 \newcommand*{\LateximageFontSizeName}{large}
```

```
6668 \end{warpall}
```

**for HTML output:** 6669 `\begin{warpHTML}`

```
\LWR@HTMLsanitize {\langle text\rangle}
```

Math expressions are converted to `lateximages`, and some math environments may contain “&”, “<”, or “>”, which should not be allowed inside an HTML ALT tag, so must convert them to HTML entities.

Two versions follow, depending on expansion needs. There may be a better way...

```

6670 \newcommand{\LWR@HTMLsanitize}[1]{%
6671 \begingroup%
6672 \LWR@FBcancel%
6673 \protect\StrSubstitute{\detokenize{#1}}{%
6674 {\detokenize{&}}}{%
6675 {\detokenize{&#38;}}[\LWR@strresult]}{%
6676 \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}{%
6677 {\detokenize{<}}}{%
6678 {\detokenize{&lt;}}}{%
6679 [\LWR@strresult]}{%
6680 \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}{%
6681 {\detokenize{>}}}{%
6682 {\detokenize{&gt;}}}{%
6683 [\LWR@strresult]}{%
6684 \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}{%
6685 {\detokenize{##}}}{%
6686 {\#}}}{%
6687 [\LWR@strresult]}{%
6688 \LWR@strresult}%
6689 \endgroup%
6690 }

```

```
\LWR@HTMLsanitizeexpand {<text>}
```

This version expands the argument before sanitizing it.

```

6691 \newcommand{\LWR@HTMLsanitizeexpand}[1]{%
6692 \begingroup%
6693 \LWR@FBcancel%
6694 \protect\StrSubstitute{\detokenize\expandafter{#1}}{%
6695 {\detokenize{&}}}{%
6696 {\detokenize{&#38;}}[\LWR@strresult]}{%
6697 [\LWR@strresult]}{%
6698 \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}{%
6699 {\detokenize{<}}}{%
6700 {\detokenize{&lt;}}}{%
6701 [\LWR@strresult]}{%
6702 \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}{%
6703 {\detokenize{>}}}{%
6704 {\detokenize{&gt;}}}{%
6705 [\LWR@strresult]}{%
6706 \LWR@strresult}%
6707 \endgroup%

```

---

6708 }

Env  `lateximage [⟨alttag⟩]`

```
6709 \catcode`\$=\active%
6710
6711 \NewDocumentEnvironment{lateximage}{O{image}}
6712 {%
6713 \LWR@traceinfo{lateximage: starting on page \arabic{page}}%
6714 \ifthenelse{\cnttest{\value{\LWR@lateximagedepth}}{>}{0}}%
```

If nesting inside an already-existing `lateximage`, simply record one more level:

```
6715 {%
6716     \addtocounter{\LWR@lateximagedepth}{1}%
6717 }%
```

Otherwise, this is the outer-most `lateximage`:

```
6718 { % start of outer-most lateximage
```

Starting a new `lateximage`:

```
6719     \addtocounter{\LWR@lateximagenumber}{1}%
6720     \LWR@traceinfo{lateximage: LWR@lateximagenumber is \arabic{\LWR@lateximagenumber}}%
```

While inside a `lateximage`, locally do not use `mathjax`:

```
6721     \boolearn{mathjax}
```

Be sure that are doing a paragraph:

```
6722     \LWR@ensuredoingapar%
```

Next file:

```
6723     \addtocounter{\LWR@externalfilecnt}{1}%
6724     \LWR@traceinfo{lateximage: LWR@externalfilecnt is \arabic{\LWR@externalfilecnt}}%
```

Figure out what the next page number will be:

```
6725     \setcounter{LWR@LIPage}{\LWR@lateximage\the\LWR@lateximagenumber}%
6726     \LWR@traceinfo{lateximage: LWR@LIPage is \arabic{LWR@LIPage}}%
```

Create an `HTML` span which will hold the comment which contains the `pdftotext` translation of the image's page, and also will hold the link to the `.svg` file:

---

```
6727     \LWR@htmltag{span id="lateximage\arabic{\LWR@lateximagenumber}" %
6728     class="lateximagesource"{} } \LWR@orignewline
```

Write instructions to the `lateximages.txt` file:

```
6729     \LWR@traceinfo{lateximage: about to write to lateximages.txt}%
6730     \immediate\write\LWR@lateximagesfile{| \theLWR@LIpage | \theLWR@externalfilecnt |}%
```

Place an open comment tag at the bottom of page; footnotes will be above this tag. This will hide any traces of the `lateximage` PDF page which were picked up by `pdftotext`.

```
6731     \LWR@traceinfo{lateximage: about to create open comment}%
6732     \LWR@htmlopencomment%
```

One level deeper:

```
6733     \addtocounter{\LWR@lateximagedepth}{1}%
```

Start the new PDF page:

```
6734     \LWR@traceinfo{lateximage: about to create new page}%
6735     \LWR@orignewpage%
```

Typeset the image in a “standard” width page and font size:

```
6736     \LWR@traceinfo{lateximage: about to create minipage}%
6737     \LWR@origminipage{6in}%
6738     \csuse{\LWR@orig\LateximageFontSizeName}%
```

Temporarily restore formatting to its PDF definitions: Do not produce HTML tags for `\hspace`, etc. inside a `lateximage`.

```
6739     \LWR@traceinfo{lateximage: about to temporarily restore formatting}%
6740     \LWR@restoreorigformatting%
```

Use full-page footnotes instead of minipage footnotes. These become HTML footnotes.

```
6741     \def\@mpfn{footnote}%
6742     \def\thempfn{\thefootnote}%
6743     \let\@footnotetext\LWR@footnotetext%
```

Create the `LWRlateximage<number>` label:

```
6744     \LWR@traceinfo{lateximage: about to create label}%
6745     \LWR@origlabel{\LWRlateximage\arabic{\LWR@lateximagenumber}}%
6746     \LWR@traceinfo{lateximage: finished creating the label}%
```

Enable print-mode math functions:

```

6747 \LetLtxMacro$\LWR@origdollar%
6748 \catcode`\$=3% math shift
6749 \LetLtxMacro\(\LWR@origopenparen%
6750 \LetLtxMacro\)\LWR@origcloseparen%
6751 \LetLtxMacro\[ \LWR@origopenbracket%
6752 \LetLtxMacro\] \LWR@origclosebracket%
6753 \let\@ensuredmath\LWR@orig@ensuredmath%
6754 }% end of outer-most lateximage
6755 \LWR@traceinfo{lateximage: finished start of environment}%
6756 }% end of \begin{lateximage}

```

When the environment closes:

```

6757 { % start of \end{lateximage}
6758 \LWR@traceinfo{lateximage: starting end of environment}%

```

Nested more than one deep?

```
6759 \ifthenelse{\cnttest{\value{LWR@lateximagedepth}}>}{1}{}%
```

If nesting inside an already-existing lateximage, simply record one more level:

```
6760 {\addtocounter{LWR@lateximagedepth}{-1}}%
```

If this is the outer-most lateximage:

```
6761 { % end of outer-most lateximage
```

Finish the lateximage minipage and start a new PDF page:

```

6762 \LWR@origendminipage%
6763 \LWR@orignewline%
6764 \LWR@origscriptsize%

```

Close the HTML comment which encapsulated any traces of the lateximage picked up by pdftotext:

```

6765 \LWR@htmclosecomment{} \LWR@orignewline%
6766 \LWR@traceinfo{lateximage: The page after the image is \arabic{page}}%

```

Create a link to the lateximage, allowing its natural height:

If the alt tag is given as “LWRAMSMATHBODY”, then use the text collected by the amsmath multiline, gather, or align environments.

```
6767 \ifthenelse{\equal{#1}{LWRAMSMATHBODY}}{%
```

```

6768      {%
6769      \LWR@subinlineimage[%
6770      \LWR@HTMLsanitizeexpand{\detokenize\expandafter{\the\@envbody}}%
6771      ]%
6772      {lateximage}%
6773      {lateximages\OSPathSymbol{}lateximage-\the\LWR@externalfilecnt}%
6774      {svg}%
6775      {}%
6776      }%
6777      {%
6778      \LWR@subinlineimage[#1]{lateximage}%
6779      {lateximages\OSPathSymbol{}lateximage-\the\LWR@externalfilecnt}{svg}{}%
6780      }%
6781 \% \LWR@orignewline% Removed to prevent extra space.

```

Be sure that are doing a paragraph:

```
6782      \LWR@ensuredoingapar%
```

Close the HTML span which has the pdftotext comment and also the link to the .svg image:

```

6783      \LWR@htmlltag{/span}%
6784      \ifbool{HTMLDebugComments}{%
6785          \LWR@htmlcomment{End of lateximage}%
6786      }{}%
6787 \% \LWR@orignewline% Removed to prevent extra space.

```

Undo one lateximage level:

```

6788      \addtocounter{LWR@lateximagedepth}{-1}%
6789  }% end of outer-most lateximage
6790 \LWR@traceinfo{lateximage: done}%
6791 }%
6792 \catcode`\$=3% math shift
6793 \end{warpHTML}

```

**for PRINT output:**

```

6794 \begin{warpprint}
6795 \% \newenvironment{lateximage}[1][]{\minipage{\linewidth}}{\endminipage}
6796 \newenvironment{lateximage}[1][]{\begin{array}{c}}
6797 \end{warpprint}

```

## 65 center, flushleft, flushright

**for HTML output:**

```
6798 \begin{warpHTML}
```

Env `center` Replace center functionality with css tags:

```
6799 \renewenvironment*{center}
6800 {
6801 \LWR@forcenewpage
6802 \BlockClass{center}
6803 }
6804 {\endBlockClass}
```

Env `flushright`

```
6805 \renewenvironment*{flushright}
6806 {
6807 \LWR@forcenewpage
6808 \BlockClass{flushright}
6809 }
6810 {\endBlockClass}
```

Env `flushleft`

```
6811 \renewenvironment*{flushleft}
6812 {
6813 \LWR@forcenewpage
6814 \BlockClass{flushleft}
6815 }
6816 {\endBlockClass}

6817 \end{warpHTML}
```

## 66 Pre-loaded packages

**for HTML output:** 6818 \begin{warpHTML}

If `textcomp` was loaded before `l warp`, perhaps as part of the font-related packages, explicitly load the `l warp` patches now:

```
6819 \@ifpackageloaded{textcomp}
6820 {
6821 \LWR@origRequirePackage{l warp-textcomp}
6822 }
6823 {}
```

If `graphics` or `graphicx` were loaded before `l warp`, perhaps by `xunicode`, explicitly load the `l warp` patches now:

```

6824 \@ifpackageloaded{graphics}
6825 {
6826 \LWR@origRequirePackage{lwarp-graphics}
6827 }
6828 {}

6829 \end{warpHTML}

```

## 67 Siunitx

Pkg **siunitx**

⚠ **per-mode** Do not use `per-mode=fraction`, which cannot be seen by the final `pdftotext` conversion.

Some units will require that the expression be placed inside math mode.

**for HTML output:** 6830 \begin{warpHTML}

Options for siunitx:

```

6831 \PassOptionsToPackage{
6832   detect-mode=true,
6833   per-mode=symbol,% fraction is not seen by pdftotext
6834 %   text-celsius = {\protect\LWRsiunitx@degree{}C},
6835 %   text-degree = {\protect\LWRsiunitx@degree},
6836 }{siunitx}
6837

6838 \end{warpHTML}

```

## 68 Graphics

Pkg **graphics**

Pkg **graphicx**

⚠ **.pdf image files** For `\includegraphics` with .pdf files, the user should provide a .pdf image file, and also a .svg, .png, or .jpg version of the same image. **These should be referred to without a file extension:**

```
\includegraphics{filename} % print:.pdf, HTML:.svg or other
```

For print output, `lwarp` will automatically choose the `.pdf` if available, other some other format otherwise. For `HTML`, one of the other formats is used instead.

If a `.pdf` file is explicitly referred to with its file extension, a link to the `.pdf` file will appear in the `HTML` output.

```
\includegraphics{filename.pdf} % creates a link in HTML
```

**other image files** For `.png`, `.jpg`, or `.gif` image files, the same file may be used in both print or `HTML` versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

**⚠️ graphics vs. graphicx** If using the older `graphics` syntax, use both optional arguments for `\includegraphics`. A single optional parameter is interpreted as the newer `graphicx` syntax. Note that viewports are not supported by `warp`; the entire image will be shown.

**units** For `\includegraphics`, avoid `px` and `%` units for width and height, or enclose them inside `warpHTML` environments. For font-proportional image sizes, use `ex` or `em`. For fixed-sized images, use `cm`, `mm`, `in`, `pt`, or `pc`. Use the keys `width=.5\linewidth`, or similar for `\textwidth` or `\textheight` to give fixed-sized images proportional to a 6 by 9 inch text area.

**options** `\includegraphics` accepts `width` and `height`, `origin`, `rotate` and `scale`, plus a new `class` key.

**HTML class** With `HTML` output, `\includegraphics` accepts an optional `class=xyz` keyval combination, and if this is given then the `HTML` output will include that class for the image. The class is ignored for print output.

**\rotatebox** `\rotatebox` accepts the optional `origin` key.

**⚠️ browser support** `\rotatebox`, `\scalebox`, and `\reflectbox` depend on modern browser support. The css standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike `LATEX`, so expect some ugly results for scaling and rotating.

**for PRINT output:** For print output, accept and then discard the new `class` key:

```
6839 \begin{warpprint}
6840 \define@key{Gin}{class}{}%
6841 \end{warpprint}
```

## 68.1 xcolor print-mode additions

Print-mode versions of new `xcolor` definitions. These are defined inside `warpall` because they are also used for `HTML` while inside a `lateximage`. They are defined

---

\AtBeginDocument so that the xcolor originals may first be loaded and saved for reuse.

The framed versions are modified to allow a background color of none, in which case only the frame is drawn, allowing the background page color to show.

**for HTML & PRINT:** 6842 \begin{warpall}

After xparses may have been loaded ...

6843 \AtBeginDocument{

... and *only* if xcolor was loaded:

6844 \@ifpackageloaded{xcolor}{  
6845 \LWR@traceinfo{patching xcolor}}

\colorboxBlock \colorboxBlock is the same as \colorbox:

6846 \LetLtxMacro\colorboxBlock\colorbox

In HTML mode, the following is done when xcolor is loaded. Following is the print-mode action:

6847 \warpprintonly{  
6848 \LetLtxMacro\LWRprint@colorboxBlock\colorbox  
6849 \LetLtxMacro\LWRorigprint@fcolorbox\fcolorbox  
6850 \LetLtxMacro\LWRorigprint@fcolorboxBlock\fcolorbox  
6851 }

\fcolorbox [⟨framemode⟩] {⟨framecolor⟩} [⟨boxmodel⟩] {⟨boxcolor⟩} {⟨text⟩}

In print mode, \fcolorbox is modified to accept a background color of none.

(\fcolorbox is particular about its optional arguments, thus the elaborate combinations of \ifthenelse.)

6852 \newsavebox{\LWR@colorminipagebox}  
6853  
6854 \DeclareDocumentCommand{\LWRprint@fcolorbox}{o m o m +m}{%  
6855 \LWR@traceinfo{\LWRprint@fcolorbox #2 #4}%"

Pre-load the contents into an LR box so that they can be used inside a \fcolorbox:

6856 \begin{lrbox}{\LWR@colorminipagebox}%"  
6857 #5%"  
6858 \end{lrbox}%"

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a \fcolorbox.

```

6859 \ifthenelse{\equal{#4}{none}}%
6860 {%
6861   \LWR@traceinfo{background is none}%
6862   {%
6863     \colorlet{LWR@currentcolor}{.}%
6864     \color{#2}%
6865     \fbox{%
6866       \color{LWR@currentcolor}%
6867       \usebox{\LWR@colorminipagebox}%
6868     }%
6869   }%
6870 }%
6871 {%
6872 \LWR@traceinfo{background not none}%
6873 \IfValueTF{#1}{%
6874 {%
6875   \IfValueTF{#3}{%
6876     {\LWRorigprint@fcolorbox[#1]{#2}{#3}{#4}{\usebox{\LWR@colorminipagebox}}}%
6877     {\LWRorigprint@fcolorbox[#1]{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
6878 }%
6879 {%
6880   \IfValueTF{#3}{%
6881     {\LWRorigprint@fcolorbox[#2]{#3}{#4}{\usebox{\LWR@colorminipagebox}}}%
6882     {\LWRorigprint@fcolorbox[#2]{#4}{\usebox{\LWR@colorminipagebox}}}%
6883 }%
6884 }%
6885 \LWR@traceinfo{LWRprint@fcolorbox done}%
6886 }

```

\fcolorboxBlock [*framemode*] [*framecolor*] [*boxmodel*] [*boxcolor*] [*text*]

In print mode, \fcolorboxBlock is the same as \fcolorbox.

```
6887 \LetLtxMacro{\LWRprint@fcolorboxBlock}{\LWRprint@fcolorbox}
```

**Env** **fcolorminipage** [*1:framemode*] [*2:framecolor*] [*3:boxmodel*] [*4:boxcolor*] [*5:align*] [*6:height*] [*7:inner-align*] [*8:width*]

In print mode, becomes a \fcolorbox containing a minipage:

```

6888 \NewDocumentEnvironment{\LWRprint@fcolorminipage}{o m o m O{c} O{} o m}
6889 {%
6890 \LWR@traceinfo{*** fcolorminipage: #2 #4 #8}%

```

Pre-load the contents into an LR box so that they can be used inside a \fcolorbox:

```
6891 \begin{lrbox}{\LWR@colorminipagebox}%
```

If inner alignment is not given, use the outer alignment instead:

```
6892 \IfValueTF{#7}%
6893 {\begin{minipage}[#5][#6][#7]{#8}%
6894 {\begin{minipage}[#5][#6][#5]{#8}%
6895 }%
6896 {%
6897 \end{minipage}%
6898 \end{lrbox}%
6899 \LWR@traceinfo{*** starting end fcolorminipage #1 #2 #3 #4 #8}%
```

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a \fcolorbox.

```
6900 \ifthenelse{\equal{#4}{none}}%
6901 {%
6902     {%
6903         \colorlet{\LWR@currentcolor}{.}%
6904         \color{#2}%
6905         \fbox{%
6906             \color{\LWR@currentcolor}%
6907             \usebox{\LWR@colorminipagebox}%
6908         }%
6909     }%
6910 }%
6911 {%
6912     \IfValueTF{#1}%
6913     {%
6914         \IfValueTF{#3}%
6915             {\LWRorigprint@fcolorbox[#1][#2][#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
6916             {\LWRorigprint@fcolorbox[#1][#2]{#4}{\usebox{\LWR@colorminipagebox}}}%
6917     }%
6918     {%
6919         \IfValueTF{#3}%
6920             {\LWRorigprint@fcolorbox[#2][#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
6921             {\LWRorigprint@fcolorbox[#2]{#4}{\usebox{\LWR@colorminipagebox}}}%
6922     }%
6923 }%
6924 \LWR@traceinfo{*** finished end fcolorminipage}%
6925 }
```

\LWR@restoreorigprintxcolor Used to activate print-mode additions for xcolor. In print mode, this is used immediately following. In HTML mode, this is used inside a lateximage.

---

```

6926 \newcommand*{\LWR@restoreorigprintxcolor}{%
6927 \LWR@traceinfo{\LWR@restoreorigprintxcolor}%
6928 \LetLtxMacro\colorboxBlock\LWRprint@colorboxBlock%
6929 \LetLtxMacro\fcolorbox\colorboxBlock%
6930 \LetLtxMacro\fcolorboxBlock\LWRprint@fcolorboxBlock%
6931 \LetLtxMacro\fcolorminipage\LWRprint@fcolorminipage%
6932 \LetLtxMacro\endfcolorminipage\endLWRprint@fcolorminipage%
6933 }%
6934
6935 \appto{\LWR@restoreorigformatting}{%
6936 \LWR@restoreorigprintxcolor}%
6937 }

```

If print mode, immediately activate the print-mode enhancements for xcolor:

```

6938 \warpprintonly{\LWR@restoreorigprintxcolor}
6939
6940 \LWR@traceinfo{xcolor patches done}
6941 }{}% xcolor loaded
6942 }% AtBeginDocument
6943 \end{warpall}

```

## 69 Cleveref

Pkg cleveref cleveref package is used as-is with minor patches.

⚠ cleveref page numbers cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for \cpageref and \cpagerefrange. This phrase includes \cpagerefFor, which defaults to “for”.

Ex:

```

\cpageref{tab:first,tab:second}
in HTML becomes:
“pages for table 4.1 and for table 4.2”

```

See \cpagerefFor at page 367 to redefine the message which is printed for page number references.

loading order cleveref and the following associated macro patches are automatically preloaded at the end of the preamble via \AtEndPreamble and \AfterEndPreamble. This is done because the HTML conversion requires cleveref. The user’s document may not require cleveref, thus the user may never explicitly load it, so during HTML output lwarf loads it last. If the user’s document preamble uses cleveref options, or functions such

as `\crefname`, then `cleveref` may be loaded in the user's preamble near the end, and `l warp`'s additional loading of `cleveref` will have no effect.

Table 8 on page 311 shows the data structure of the label/reference system as revised by `l warp` and `cleveref`.

A few patches allow `cleveref` to work as-is:

**for HTML output:** 6944 `\begin{warpHTML}`

`\AtEndPreamble` forces `cleveref` to be loaded last:

```
6945 \AtEndPreamble{  
6946 \RequirePackage{cleveref}  
6947 }
```

The following patches are applied after `cleveref` has loaded, and after `\AtBeginDocument`:

```
6948 \AfterEndPreamble{  
6949 \LWR@traceinfo{Patching cleveref.}}
```

`\@@setcref {<kindofref>} {<label>}`

```
6950 \renewcommand*{\@@setcref}[2]{#1{\ref{#2}}{}{}}
```

`\@@setcrefrange {<text>} {<label>} {<label>}`

```
6951 \renewcommand{\@@setcrefrange}[3]{%  
6952 #1{\ref{#2}}{\ref{#3}}{}{}{}}
```

`\cpagerefFor` Redefinable word between “page(s)” and the page numbers.

```
6953 \newcommand*{\cpagerefFor}{for}
```

`\@@setcpageref {<typeofref>} {<label>}`, where `typeofref` is “page” or “pages”

```
6954 \renewcommand*{\@@setcpageref}[2]{%  
6955 #1{\cpagerefFor\ \cref{#2}}{}{}%  
6956 }
```

```
6957 \renewcommand{\@@setcpagerefrange}[3]{%  
6958 #1{\cpagerefFor\ \cref{#2}}{\cref{#3}}{}{}{}{}}  
6959 }% AfterEndPreamble
```

Remember and patch some label-related definitions. These will be further encased and patched by other packages later.

```
6960 \let\LWR@origlabel\label
6961 \let\label\LWR@newlabel
6962 \let\LWR@origref\ref
6963 \let\ref\LWR@newref% \end{ syntax highlighting
6964 \let\LWR@origpageref\pageref
6965 \let\pageref\LWR@newpageref
6966
6967
6968
6969 \end{warpHTML}
```

## 70 Picture

**Env picture** The picture environment is enclosed inside a `\lateximage`.

**for HTML output:** 6970 `\begin{warpHTML}`

```
Env picture

6971 \BeforeBeginEnvironment{picture}{\lateximage}
6972
6973 \AfterEndEnvironment{picture}{\endlateximage}

6974 \end{warpHTML}
```

## 71 Boxes and Minipages

A css flexbox is used for minipages and parboxes, allowing external and internal vertical positioning.

- ⚠ **inline** A line of text with an inline minipage or parbox will have the minipage or parbox placed onto its own line, because a paragraph is a block element and cannot be made `inline-block`.
- placement** Minipages and parboxes will be placed side-by-side in HTML unless you place a `\newline` between them.
- side-by-side** Side-by-side minipages may be separated by `\quad`, `\qquad`, `\enskip`, `\hspace`, `\hfill`, or a `\rule`. When inside a `center` environment, the result is similar in print

and `HTML`. Paragraph tags are suppressed between side-by-side minipages and these spacing commands, but not at the start or end of the paragraph.

**in a `span`** There is limited support for minipages inside an `HTML <span>`. An `HTML <div>` cannot appear inside a `<span>`. While in a `<span>`, minipages, and parboxes, and any enclosed lists have limited `HTML` tags, resulting in an “inline” format, without markup except for `HTML` breaks. Use `\newline` or `\par` for an `HTML` break.

**size** When using `\ linewidth`, `\ textwidth`, and `\ textheight`, widths and heights are scaled proportionally to a 6×9 inch text area.

**no-width minipages** A minipage of width exactly `\ linewidth` is automatically given no `HTML` width.

**full-width minipages** A new macro `\minipagefullwidth` requests that the next minipage be generated without an `HTML width` attribute, allowing it to be the full width of the display rather than the fixed width given.

**⚠ text alignment** Nested minipages adopt their parent’s text alignment in `HTML`, whereas in regular `TEX PDF` output they do not. Use a `flushleft` or similar environment in the child minipage to force a text alignment.

**for `HTML` output:** 6975 `\begin{warpHTML}`

## 71.1 Counters and lengths

**Ctr** `\LWR@minipagedepth` Used to only reset the line width at the outermost minipage.

```
6976 \newcounter{\LWR@minipagedepth}
6977 \setcounter{\LWR@minipagedepth}{0}
```

**Len** `\WR@minipagewidth` Used to convert the width into printable units.

```
6978 \newlength{\LWR@minipagewidth}
```

**Len** `\WR@minipageheight` Used to convert the height into printable units.

```
6979 \newlength{\LWR@minipageheight}
```

## 71.2 Footnote handling

Also see section 45 for other forms of footnotes. Minipage footnotes are gathered in section 45.5, and then placed into the document in section 71.3.

### 71.3 Minipage handling

\LWR@endminipage Used to close a minipage.

Copied the L<sup>A</sup>T<sub>E</sub>X definition and modified to create a <div> of class mpfootnotes:

```

6980 \def\LWR@endminipage{%
6981   \par
6982   \unskip
6983   \ifvoid\@mpfootins\else
6984     \vskip\skip\@mpfootins
6985     \normalcolor
6986     \LWR@htmldivclass{mpfootnotes}
6987     \LWR@origmedskip
6988     \unvbox\@mpfootins
6989     \LWR@htmldivclassend{mpfootnotes}
6990   \fi
6991   \ominipagetrue
6992 \color@endgroup
6993 \egroup
6994 \expandafter\@iiiparbox\@mpargs{\unvbox\@tempboxa}}

```

\LWR@subminipage Used to create a PDF minipage without creating an HTML minipage. This allows footnotes to appear at the bottom of the minipage instead of the bottom of the HTML page.

```

6995 \newcommand*\LWR@subminipage{%
6996 \LWR@stoppars
6997 \LWR@origminipage{6in}

```

\raggedright cancels hyphenation, which will be done by HTML instead.

```
6998 \LWR@origraggedright%
```

Resume paragraph tag handling for the contents of the minipage:

```

6999 \LWR@startpars%
7000 }

```

\LWR@endsubminipage Closes the subminipage.

```

7001 \newcommand*\LWR@endsubminipage{%
7002 \LWR@stoppars%
7003 \LWR@endminipage% The following empty line is required:
7004
7005 }

```

Bool LWR@minipagefullwidth Should the next minipage have no HTML width?

```
7006 \newbool{LWR@minipagefullwidth}
7007 \boolefalse{LWR@minipagefullwidth}
```

\minipagefullwidth Requests that the next minipage have no width tag in HTML:

**for HTML output:** 7008 \newcommand\*{\minipagefullwidth}{\booltrue{LWR@minipagefullwidth}}
 7009 \end{warpHTML}

**for PRINT output:** 7010 \begin{warpprint}
 7011 \newcommand\*{\minipagefullwidth}{}%
 7012 \end{warpprint}

**for HTML output:** 7013 \begin{warpHTML}

Bool LWR@minipagethispar Has a minipage been seen this paragraph? If true, prevents paragraph tags around horizontal space between minipages.

```
7014 \newbool{LWR@minipagethispar}
7015 \boolefalse{LWR@minipagethispar}
```

Env minipage [*vert position*] [*height*] [*inner vert position*] {[*width*}]

The vertical positions may be 'c', 't', or 'b'. The inner position may also be 's'.

When using \linewidth, \textwidth, or \textheight, these are scaled proportionally to a 6x9 inch text area.

```
7016 \RenewDocumentEnvironment{minipage}{O{t} o O{t} m}
7017 {%
7018 \uselengthunit{in}%
7019 \setlength{\LWR@minipagewidth}{#4}%
7020 \ifthenelse{\cnttest{\value{LWR@minipagedepth}}{=}{0}}{%
7021   \addtolength{\LWR@minipagewidth}{3em}%
7022   \setlength{\linewidth}{6in}%
7023   \setlength{\textwidth}{6in}%
7024   \setlength{\textheight}{9in}%
7025 }{%
7026 \LWR@traceinfo{computed width is \rndprintlength{\LWR@minipagewidth}}%
7027 \addtocounter{LWR@minipagedepth}{1}%
7028 \setlength{\LWR@minipageheight}{\textheight}%
7029 \IfValueT{#2}{\setlength{\LWR@minipageheight}{#2}}%
```

*lwe* wants to start a paragraph for the new minipage, then start a paragraph again for the contents of the minipage, so cancel the paragraph tag handling until the minipage has begun.

---

```
7030 \LWR@stoppars%
```

Create the <div> tag with optional alignment style:

```
7031 \LWR@traceinfo{minipage: creating div class}%
7032 \LWR@orignewpage%
7033 \LWR@htmntag{div class="minipage" style="%"
7034 \ifthenelse{\equal{#1}{t}}{vertical-align:bottom ; }{}%
7035 \ifthenelse{\equal{#1}{c}}{vertical-align:middle ; }{}%
7036 \ifthenelse{\equal{#1}{b}}{vertical-align:top ; }{}%
7037 \ifthenelse{\equal{#3}{t}}{justify-content:flex-start ; }{}%
7038 \ifthenelse{\equal{#3}{c}}{justify-content:center ; }{}%
7039 \ifthenelse{\equal{#3}{b}}{justify-content:flex-end ; }{}%
7040 \ifthenelse{\equal{#3}{s}}{justify-content:space-between ; }{}%
```

Print the width and optional height styles:

```
7041 \LWR@traceinfo{minipage: about to print the width of \rndprintlength{\LWR@minipagewidth}}%
7042 \uselengthunit{PT}%
7043 \ifbool{\LWR@minipagefullwidth}%
7044 {\boolfalse{\LWR@minipagefullwidth}}%
7045 {%
7046     \ifthenelse{\lengthtest{#4}=\linewidth}%
7047     {}%
7048     {width:\rndprintlength{\LWR@minipagewidth} ; }%
7049 }%
7050 \LWR@traceinfo{minipage: about to print the height}%
7051 \IfValueT{#2}{height:\rndprintlength{\LWR@minipageheight} ; }%
7052 "{}"}
```

Finish with an empty line to start L<sup>A</sup>T<sub>E</sub>X minipage processing on a new line. Use a large minipage area to avoid the unnecessary wrapping of tags.

```
7053
7054 \LWR@origminipage{6in}%
The preceding empty line is required.
```

Set the user-accessible minipage and text width and height values inside the minipage. These do not affect the actual size of the large minipage created by \LWR@origminipage above, but are used by any reference to \linewidth, etc. inside the PDF minipage being created here.

```
7055 \setlength{\linewidth}{#4}%
the original width
7056 \setlength{\textwidth}{6in}%
7057 \setlength{\textheight}{9in}%

```

\raggedright cancels hyphenation, which will be done by HTML instead.

```
7058 \LWR@origraggedright%
```

Resume paragraph tag handling for the contents of the minipage:

```
7059 \LWR@startpars%
7060 \LWR@traceinfo{minipage: finished starting the minipage}%
7061 }
```

End the environment with L<sup>A</sup>T<sub>E</sub>X processing and closing tag:

```
7062 {%
7063 \LWR@stoppars%
7064 \LWR@endminipage% The following empty line is required:
7065
7066 \LWR@htmldivclassend{minipage}%
7067 \LWR@origvspace{1\baselineskip}%
7068 \addtocounter{LWR@minipagedepth}{-1}%
7069 \LWR@startpars%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
7070 \global\booltrue{LWR@minipagethispar}%
7071 }
```

## 71.4 Parbox, makebox, framebox, fbox, raisebox

**for HTML output:** \parbox [⟨pos⟩] [⟨height⟩] [⟨inner-pos⟩] {⟨width⟩} {⟨text⟩}

A parbox uses the minipage code:

```
7072 \RenewDocumentCommand{\parbox}{O{t} O{t} m +m}
7073 {
7074 \LWR@traceinfo{parbox of width #4}%
7075 \begin{minipage}[#1][#2][#3]{#4}
7076 #5
7077 \end{minipage}
7078 }
```

\makebox (⟨⟩)posn) [⟨width⟩] [⟨pos⟩] {⟨text⟩}

```
7079 \LetLtxMacro{\LWR@origmakebox}{\makebox}
7080
7081 \RenewDocumentCommand{\makebox}{d() o o m}{%
```

Check for the optional width:

```
7082 \IfValueTF{#2}%
7083 {%
```

Check for the horizontal text alignment. For stretched, the best HTML can do is justified alignment.

```
7084      {%
7085          \def\LWR@align{center}%
7086          \ifstreq{\#3}{l}{\def\LWR@align{left}}{}%
7087          \ifstreq{\#3}{r}{\def\LWR@align{right}}{}%
7088          \ifstreq{\#3}{s}{\def\LWR@align{justify}}{}%
```

To print the `width` argument:

```
7089      \setlength{\LWR@tempwidth}{#2}%
```

inline-block allows width and text-align to be used in a <span>.

```
7090      \uselengthunit{PT}%
7091      \InlineClass[%
7092          display:inline-block ; %
7093          text-align:\LWR@align\ ; %
7094          width:\rndprintlength{\LWR@tempwidth}%
7095      ]%
7096      {makebox}%
```

Without a width argument, the text is simply used inline:

```
7097      {\mbox{#4}}%
7098  }% scope
7099 }%
7100 {\mbox{#4}}%
7101 }
```

```
\framebox [⟨width⟩] [⟨pos⟩] {⟨text⟩}
```

```
7102 \LetLtxMacro{\LWR@origframebox}\framebox
7103
7104 \RenewDocumentCommand{\framebox}{o o m}{%
7105 \fbox{\makebox[#1][#2]{#3}}%
7106 }
```

```
\LWR@forceminwidth {⟨length⟩}
```

Sets `\LWR@atleastonept` to be at least 1pt.

```
7107 \newlength{\LWR@atleastonept}
```

```

7108
7109 \newcommand*{\LWR@forceminwidth}[1]{%
7110 \setlength{\LWR@atleastonept}{#1}%
7111 \ifthenelse{%
7112     \lengthtest{\LWR@atleastonept>0pt}\AND%
7113     \lengthtest{\LWR@atleastonept<1pt}%
7114 }%
7115 {\setlength{\LWR@atleastonept}{1pt}}%
7116 {}%
7117 }

```

\LWR@blackborderpadding Prints the HTML attributes for a black border and padding.

\LWR@forceminwidth must be used first in order to set the border width.

```

7118 \newcommand*{\LWR@blackborderpadding}{%
7119 \uselengthunit{PT}%
7120 border:\rndprintlength{\LWR@atleastonept} solid black ; %
7121 padding:\rndprintlength{\fboxsep}%
7122 }

```

\fbox {<text>}

Creates a framed inline span enclosing the text.

Remember the print-mode version:

```
7123 \let\LWRprint\fbox\fbox
```

Create a new HTML version, but don't use it until after xcolor may have loaded:

```

7124 \newcommand{\LWRhtml@fbox}[1]{%
7125 \LWR@traceinfo{HTML fbox}%
7126 \LWR@forceminwidth{\fboxrule}%
7127 \InlineClass[%
7128 \LWR@blackborderpadding%
7129 ]{\fbox}{#1}%
7130 }

```

xcolor \lets things to \fbox when it is loaded, and this must remain even for HTML output while in a `lateximage`, so \fbox is not modified until \AtBeginDocument:

```
7131 \AtBeginDocument{\let\fbox\LWRhtml@fbox}
```

\fboxBlock {<text>} Creates a framed HTML <div> of the text.

A print-output version is also supplied below.

```

7132 \newcommand{\fboxBlock}[1]{%
7133 \LWR@forceminwidth{\fboxrule}%
7134 \begin{BlockClass}[%
7135 \LWR@blackborderpadding%
7136 ]{\fboxBlock}
7137 #1
7138 \end{BlockClass}
7139 }

```

**Env** `fminipage` [*align*] [*height*] [*align*] {*width*}

Creates a framed HTML <div> around its contents.

A print-output version is also supplied below.

```

7140 \NewDocumentEnvironment{fminipage}{O{t} o O{t} m}%
7141 {%
7142 \LWR@traceinfo{fminipage #1 #2 #3 #4}%
7143 \LWR@forceminwidth{\fboxrule}%
7144 \setlength{\LWR@tempwidth}{#4}%
7145 \IfValueT{#2}{\setlength{\LWR@tempheight}{#2}}%
7146 \begin{BlockClass}[%
7147 \LWR@blackborderpadding ; %
7148 \uselengthunit{PT}%
7149 \IfValueT{#2}{height:\rndprintlength{\LWR@tempheight} ; }%
7150 width:\rndprintlength{\LWR@tempwidth}%
7151 ]{\fminipage}%
7152 }%
7153 {%
7154 \end{BlockClass}%
7155 \LWR@traceinfo{fminipage done}%
7156 }

```

`\raisebox` {*raiselen*} [*height*] [*depth*] {*text*}

```

7157 \LetLtxMacro{\LWR@origraisebox}{\raisebox}%
7158
7159 \RenewDocumentCommand{\raisebox}{m o o m}{%
7160 #4%
7161 }

```

7162 \end{warpHTML}

**for HTML & PRINT:** 7163 \begin{warpall}

`LWRprint@fminipage` is defined inside `warpall`. For print output, it is `\let` to `fminipage`. For HTML output, the HTML version of `fminipage` is used instead, but the print version is still available for use inside a `lateximage`.

---

Env LWRprint@fminipage [*1:align*] [*2:height*] [*3:inner-align*] [*4:width*]

Creates a frame around its contents.

```
7164 \newsavebox{\LWR@fminipagebox}
7165
7166 \NewDocumentEnvironment{LWRprint@fminipage}{O{t} o O{t} m}
7167 {%
```

An outer minipage will be used for vertical alignment. An inner minipage will be framed with \fbox.

If the optional inner alignment is not given, use the outer instead:

```
7168 \IfValueTF{#3}%
7169 {\def\LWR@thisalign{#3}}
7170 {\def\LWR@thisalign{#1}}%
```

Form the outer minipage depending on whether a height was given. Make the outer minipage larger to compensate for the frame.

```
7171 \IfValueTF{#2}%
7172 {\minipage[#1][#2+2\fboxsep+2\fboxrule][\LWR@thisalign]{#4+2\fboxsep+2\fboxrule}}%
7173 {\minipage[#1]{#4+2\fboxsep+2\fboxrule}}%
```

Capture the contents of the environment:

```
7174 \begin{lrbox}{\LWR@fminipagebox}%
```

Nest the contents inside an inner minipage of the desired size:

```
7175 \IfValueTF{#2}%
7176 {\minipage[#1][#2][\LWR@thisalign]{#4}}%
7177 {\minipage[#1]{#4}}%
7178 }
7179 {%
```

Close the inner minipage and the LR box with the contents:

```
7180 \endminipage%
7181 \end{lrbox}%
```

Create a frame around the contents of the environment:

```
7182 \fbox{\usebox{\LWR@fminipagebox}}%
```

The entire thing is placed inside the outer minipage:

```

7183 \end{minipage}%
7184 }

7185 \end{warpall}

for PRINT output: 7186 \begin{warpprint}

```

For print output, the following are \let to become active.

```
\fboxBlock {<text>}

Creates a framed HTML <div> around the text.
```

```
7187 \let\fboxBlock\fbox
```

```
Env fminipage [<align>] [<height>] [<align>] {<width>}

Creates a frame around its contents.
```

```
7188 \LetLtxMacro{\fminipage}{\LWRprint@fminipage}
7189 \LetLtxMacro{\endfminipage}{\endLWRprint@fminipage}

7190 \end{warpprint}
```

## 72 Direct formatting

\textbf{etc.} are supported, but \bfseries, etc. are not yet supported.

For high-level block and inline custom CSS classes, see section 39.8.

```
for HTML output: 7191 \begin{warpHTML}
```

```
\emph {<text>}

7192 \DeclareRobustCommand{\LWR@HTMLemph}[1]{\LWR@htmlspan{em}{#1}}
7193 \DeclareRobustCommand{\LWR@nullemph}[1]{#1}
7194 \LetLtxMacro{\emph}{\LWR@HTMLemph}
```

```
\textmd {<text>}

7195 \DeclareRobustCommand{\LWR@HTMLtextmd}[1]{\LWR@htmlspanclass{textmd}{#1}}
7196 \DeclareRobustCommand{\LWR@nulltextmd}[1]{#1}
7197 \LetLtxMacro{\textmd}{\LWR@HTMLtextmd}
```

```
\textbf {⟨text⟩}

7198 \DeclareRobustCommand{\LWR@HTMLtextbf}[1]{\LWR@htmlspan{b}{#1}}
7199 \DeclareRobustCommand{\LWR@nulltextbf}[1]{#1}
7200 \LetLtxMacro{\textbf}{\LWR@HTMLtextbf}

\textrm {⟨text⟩}

7201 \DeclareRobustCommand{\LWR@HTMLtextrm}[1]{\LWR@htmlspanclass{textrm}{#1}}
7202 \DeclareRobustCommand{\LWR@nulltextrm}[1]{#1}
7203 \LetLtxMacro{\textrm}{\LWR@HTMLtextrm}

\textsf {⟨text⟩}

7204 \DeclareRobustCommand{\LWR@HTMLtextsfsf}[1]{\LWR@htmlspanclass{textsf}{#1}}
7205 \DeclareRobustCommand{\LWR@nulltextsfsf}[1]{#1}
7206 \LetLtxMacro{\textsf}{\LWR@HTMLtextsfsf}

\texttt {⟨text⟩}

7207 \DeclareRobustCommand{\LWR@HTMLtexttt}[1]{\LWR@htmlspan{kbd}{#1}}
7208 \DeclareRobustCommand{\LWR@nulltexttt}[1]{#1}
7209 \LetLtxMacro{\texttt}{\LWR@HTMLtexttt}

\textup {⟨text⟩}

7210 \DeclareRobustCommand{\LWR@HTMLtextup}[1]{\LWR@htmlspanclass{textup}{#1}}
7211 \DeclareRobustCommand{\LWR@nulltextup}[1]{#1}
7212 \LetLtxMacro{\textup}{\LWR@HTMLtextup}

\textit {⟨text⟩}

7213 \DeclareRobustCommand{\LWR@HTMLtextit}[1]{\LWR@htmlspan{i}{#1}}
7214 \DeclareRobustCommand{\LWR@nulltextit}[1]{#1}
7215 \LetLtxMacro{\textit}{\LWR@HTMLtextit}

\textsc {⟨text⟩}

7216 \DeclareRobustCommand{\LWR@HTMLtextsc}[1]{\LWR@htmlspanclass{textsc}{#1}}
7217 \DeclareRobustCommand{\LWR@nulltextsc}[1]{#1}
7218 \LetLtxMacro{\textsc}{\LWR@HTMLtextsc}

\textsl {⟨text⟩}
```

```
7219 \DeclareRobustCommand{\LWR@HTMLtextsl}[1]{\LWR@htmlspanclass{tests1}{#1}}
7220 \DeclareRobustCommand{\LWR@nulltextsl}[1]{#1}
7221 \LetLtxMacro{\textsl}{\LWR@HTMLtextsl}

\textnormal {<text>}

7222 \DeclareRobustCommand{\LWR@HTMLtextnormal}[1]{\textmd{\textrm{\textup{#1}}}}
7223 \DeclareRobustCommand{\LWR@nulltextnormal}[1]{#1}
7224 \LetLtxMacro{\textnormal}{\LWR@HTMLtextnormal}

7225 \DeclareRobustCommand{\LWR@nullrmfamily}{}
7226 \DeclareRobustCommand{\LWR@nullsffamily}{}
7227 \DeclareRobustCommand{\LWR@nullttfamily}{}
7228 \DeclareRobustCommand{\LWR@nullbfseries}{}
7229 \DeclareRobustCommand{\LWR@nullmdseries}{}
7230 \DeclareRobustCommand{\LWR@nullupshape}{}
7231 \DeclareRobustCommand{\LWR@nullslshape}{}
7232 \DeclareRobustCommand{\LWR@nullscshape}{}
7233 \DeclareRobustCommand{\LWR@nullitshape}{}
7234 \DeclareRobustCommand{\LWR@nullem}[1]{}
7235 \DeclareRobustCommand{\LWR@nullnormalfont}{}
```

\LWR@nullfonts Removes formatting during filename operations.

```
7236 \newcommand*{\LWR@nullfonts}{%
7237 \LetLtxMacro{\emph}{\LWR@nullemph}%
7238 \LetLtxMacro{\textmd}{\LWR@nulltextmd}%
7239 \LetLtxMacro{\textbf}{\LWR@nulltextbf}%
7240 \LetLtxMacro{\textrm}{\LWR@nulltextrm}%
7241 \LetLtxMacro{\textsf}{\LWR@nulltextsf}%
7242 \LetLtxMacro{\texttt}{\LWR@nulltexttt}%
7243 \LetLtxMacro{\textup}{\LWR@nulltextup}%
7244 \LetLtxMacro{\textit}{\LWR@nulltextit}%
7245 \LetLtxMacro{\textsc}{\LWR@nulltextsc}%
7246 \LetLtxMacro{\textsl}{\LWR@nulltextsl}%
7247 \LetLtxMacro{\textnormal}{\LWR@nulltextnormal}%
7248 \LetLtxMacro{\rmfamily}{\LWR@nullrmfamily}%
7249 \LetLtxMacro{\sffamily}{\LWR@nullsffamily}%
7250 \LetLtxMacro{\ttfamily}{\LWR@nullttfamily}%
7251 \LetLtxMacro{\bfseries}{\LWR@nullbfseries}%
7252 \LetLtxMacro{\mdseries}{\LWR@nullmdseries}%
7253 \LetLtxMacro{\upshape}{\LWR@nullupshape}%
7254 \LetLtxMacro{\slshape}{\LWR@nullslshape}%
7255 \LetLtxMacro{\scshape}{\LWR@nullscshape}%
7256 \LetLtxMacro{\itshape}{\LWR@nullitshape}%
7257 \LetLtxMacro{\em}{\LWR@nullem}%
7258 \LetLtxMacro{\normalfont}{\LWR@nullnormalfont}%
7259 \renewcommand*{\HTMLunicode}[1]{}%
```

```
7260 \renewcommand*{\HTMLentity}[1] {}%
```

Ampersand becomes “and”, which is a short word and is then removed from the filename.

```
7261 \renewcommand*{\&}{and}%
7262 \renewcommand{\textsuperscript}[1]{##1}%
7263 \renewcommand{\textsubscript}[1]{##1}%
7264 \LetLtxMacro{\underline}{\LWR@origunderline}%
7265 \RenewDocumentCommand{\LWR@htmlspanclass}{o m +m}{{##3}}%
7266 \DeclareExpandableDocumentCommand{\InlineClass}{+o +m +m}{{##3}}%
7267 }
```

\mdseries

```
7268 \renewcommand*{\mdseries}{}%
```

\bfseries

```
7269 \renewcommand*{\bfseries}{}%
```

\rmfamily

```
7270 \renewcommand*{\rmfamily}{}%
```

\sffamily

```
7271 \renewcommand*{\sffamily}{}%
```

\ttfamily

```
7272 \renewcommand*{\ttfamily}{}%
```

\upshape

```
7273 \renewcommand*{\upshape}{}%
```

\itshape

```
7274 \renewcommand*{\itshape}{}%
```

\scshape

```
7275 \renewcommand*{\scshape}{}%
```

\normalfont

7276 \renewcommand\*{\normalfont}{}{}

\sp {⟨text⟩}

For siunitx. Must work in math mode.

7277 \renewcommand{\sp}[1]{\text{<sup>#1</sup>}}

\sb {⟨text⟩}

For siunitx. Must work in math mode.

7278 \renewcommand{\sb}[1]{\text{<sub>#1</sub>}}

\textsuperscript {⟨text⟩}

7279 \renewcommand{\textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}

\textsubscript {⟨text⟩}

7280 \renewcommand{\textsubscript}[1]{\LWR@htmlspan{sub}{#1}}

\up {⟨text⟩} Prints superscript.

This is \let at the beginning of the document in case some other package has changed the definition.

7281 \AtBeginDocument{\let\up\textsuperscript}

\fup {⟨text⟩} Prints superscript.

Supports fmtcount package.

This is \let at the beginning of the document in case some other package has changed the definition.

7282 \AtBeginDocument{\let\fup\textsuperscript}

\underline {⟨text⟩}

7283 \renewcommand{\underline}[1]{\InlineClass{underline}{#1}}

```
\hfill
7284 \renewcommand*{\hfill}{\qquad}
\hrulefill
7285 \renewcommand*{\hrulefill}{\rule{1in}{1pt}}
\dotfill
7286 \renewcommand*{\dotfill}{\dots}
7287 \end{warpHTML}
```

## 73 Skips, spaces, font sizes

**for HTML output:** 7288 \begin{warpHTML}

```
\, must be redefined after \RequirePackage{printlen}
7289 \let\LWR@origcomma\
7290 \let\LWR@origtilde\
7291 \let\LWR@origskip\enskip
7292 \let\LWR@origquad\quad
7293 \let\LWR@origqquad\qquad
7294 \let\LWR@orighspace\hspace
7295 \let\LWR@origvspace\vspace
7296 \let\LWR@origrule\rule
7297 \let\LWR@origmedskip\medskip
7298 \let\LWR@origtextellipsis\textellipsis
```

Direct-formatting space commands become HTML entities:

```
7299 \renewcommand*{\,}{\HTMLunicode{202f}} % HTML thin non-breakable space
7300
7301 \renewcommand*{~}{\HTMLentity{nbsp}}
7302
7303 \renewcommand*{\textellipsis}{\HTMLunicode{2026}}
```

Direct-formatting font sizes are ignored:

```
7304 \let\LWR@orignormalsize\normalsize
7305 \let\LWR@origsmall\small
```

```

7306 \let\LWR@origfootnotesize\footnotesize
7307 \let\LWR@origscriptsize\scriptsize
7308 \let\LWR@origtiny\tiny
7309 \let\LWR@origlarge\large
7310 \let\LWR@origLarge\Large
7311 \let\LWR@origLARGE\LARGE
7312 \let\LWR@orighuge\huge
7313 \let\LWR@origHuge\Huge
7314 \renewcommand*{\normalsize}{}
7315 \renewcommand*{\small}{}
7316 \renewcommand*{\footnotesize}{}
7317 \renewcommand*{\scriptsize}{}
7318 \renewcommand*{\tiny}{}
7319 \renewcommand*{\large}{}
7320 \renewcommand*{\Large}{}
7321 \renewcommand*{\LARGE}{}
7322 \renewcommand*{\huge}{}
7323 \renewcommand*{\Huge}{}
7324
7325 \renewcommand*{\onecolumn}{}
7326
7327 \renewcommand{\twocolumn}[1][]{%
7328
7329 #1
7330
7331 }

```

\newline Uses the HTML <br /> element.

```

7332 \newcommand*{\LWR@newlinebr}{\unskip\LWR@htmltag{br /}\LWR@orignewline}%
7333 \let\newline\LWR@newlinebr

```

\\" Redefined to \LWR@endofline or \LWR@tabularendofline.

\LWR@endofline \* [<len>]

\\" is assigned to \LWR@endofline at \LWR@LwarpStart.

Inside tabular, \\" is temporarily changed to \LWR@tabularendofline.

```

7334 \LetLtxMacro{\LWR@origendofline} \\
7335 \NewDocumentCommand{\LWR@endofline}{s o}%
7336 {%
7337 \newline%
7338 }

```

\LWR@minipagestartpars Minipages are often placed side-by-side inside figures, with a bit of horizontal space to separate them. Since HTML does not allow a <div> to be inside a p, paragraphs

must be turned off during the generation of the minipage, then turned on after the minipage is complete. When this occurs between side-by-side minipages, l warp correctly suppresses the paragraph tags between the minipages, unless some other text is between the minipages. Such text forms its own paragraph, resulting in text after a minipage to be on its own line. Since people often place small horizontal space between minipages, it is desirable to maintain this space if possible. l warp tries to do this by remembering that a minipage has been seen, in which case paragraph tags are suppressed around \hspace, \enskip, \quad, and \quadquad until the end of the paragraph, when the closing p tag is created.

When a minipage is seen, the boolean LWR@minipagethispar is set, telling the following horizontal whitespace commands to try to suppress their surrounding paragraph tags. LWR@minipagethispar is cleared at the next end of paragraph, when the HTML paragraph closing tag is generated.

Placed just before \hspace, \quad, or \quadquad's HTML output.

```
7339 \newcommand*{\LWR@minipagestartpars}{%
7340 \ifbool{LWR@minipagethispar}{\LWR@startpars}{()}%
7341 }
```

\LWR@minipagestoppars Placed just after \hspace, \quad, or \quadquad's HTML output.

```
7342 \newcommand*{\LWR@minipagestoppars}{%
7343 \ifbool{LWR@minipagethispar}{\LWR@stoppars}{()}%
7344 }
```

\quad Handles special minipage & horizontal space interactions.

```
7345 \renewcommand*{\quad}{%
7346 \LWR@minipagestoppars%
7347 \HTMLunicode{2001}%
7348 \LWR@minipagestartpars%
7349 }
```

\quadquad Handles special minipage & horizontal space interactions.

```
7350 \renewcommand*{\quadquad}{\quad\quad}
```

\enskip Handles special minipage & horizontal space interactions.

```
7351 \renewcommand*{\enskip}{%
7352 \LWR@minipagestoppars%
7353 \HTMLunicode{2000}%
7354 \LWR@minipagestartpars%
7355 }
```

Len \WR@tempwidth Used to compute span width, height, raise for \hspace and \rule:

```
7356 \newlength{\LWR@tempwidth}
7357 \newlength{\LWR@tempheight}
7358 \newlength{\LWR@tempraise}
```

\LWR@hspace \* {*length*}

Handles special minipage & horizontal space interactions.

Prints a span of a given width. Ignores the optional star.

\hspace{\fill} is converted to \hspace{2em}, equal to \qqquad.

```
7359 \NewDocumentCommand{\LWR@hspace}{s m}{%
7360 \setlength{\LWR@tempwidth}{#2}}%
```

If \fill, change to \qqquad:

```
7361 \ifnum\gluestretchorder\LWR@tempwidth>0%
7362 \setlength{\LWR@tempwidth}{2em}%
7363 \fi%
```

Only if the width is not zero:

```
7364 \ifthenelse{\dimtest{\LWR@tempwidth}{=}{0pt}}{}{%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
7365 \LWR@minipagestoppars%
```

Support the HTML thin wrappable space:

```
7366 \ifthenelse{\dimtest{\LWR@tempwidth}{=.16667em}}%
7367 {}%
7368 \HTMLunicode{2009}% thin breakable space
7369 }%
```

Print the span with the converted width. Not rounded.

```
7370 {}%
7371 \uselengthunit{PT}%
7372 \LWR@htmltagc{%
7373 span style="width:\printlength{\LWR@tempwidth}; display:inline-block;"%
7374 }%
7375 \LWR@htmltagc{/span}%
7376 }%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
7377     \LWR@minipagestartpars%
7378 }% width not 0
7379 }
```

\LWR@nohspace \* {*<length>*}

Used to disable \hspace while creating description \items.

```
7380 \NewDocumentCommand{\LWR@nohspace}{s m}{}{}
```

\hspace \* {*<length>*}

Handles special minipage & horizontal space interactions.

```
7381 \LetLtxMacro{\hspace}{\LWR@hspace}
```

\LWR@vspace \* {*<length>*} Nullified vspace.

```
7382 \NewDocumentCommand{\LWR@vspace}{s m}{}{}
```

\vspace \* {*<length>*} Nullified.

```
7383 \let\vspace\LWR@vspace
```

\linebreak [*num*] Inserts an HTML br tag.

```
7384 \renewcommand*{\linebreak}[1][]{\newline}
```

\nolinebreak [*num*]

```
7385 \renewcommand*{\nolinebreak}[1][]{}
```

\pagebreak [*num*] Starts a new paragraph.

```
7386 \renewcommand*{\pagebreak}[1][]{%
7387
7388 }
```

\nopagebreak [*num*]

```
7389 \renewcommand*{\nopagebreak}[1][]{}
```

```
\enlargethispage * {<len>}
7390 \RenewDocumentCommand{\enlargethispage}{s m}{}
```

`\LWR@currenttextcolor` The color to use for text and `\rule`, defaulting to black:

```
7391 \newcommand*{\LWR@currenttextcolor}{black}
```

`\LWR@rule` [<raise>] {<width>} {<height>}

Handles special minipage & horizontal space interactions.

Creates a span of a given width and height. Ignores the optional star.

`\fill` is zero-width, so `\hspace{\fill}` is ignored.

```
7392 \NewDocumentCommand{\LWR@rule}{o m m}{%
```

The width is copied into a temporary `\TeX` length, from which comparisons and conversions may be made:

```
7393 \setlength{\LWR@tempwidth}{#2}%
```

If it's zero-width then skip the entire rule:

```
7394 \ifthenelse{\lengthtest{\LWR@tempwidth=0pt}}
7395 {}% zero-width
7396 {}% non-zero width
```

If it's non-zero width, set a minimal thickness so that it more reliably shows in the browser:

```
7397 \ifthenelse{%
7398   \lengthtest{\LWR@tempwidth>0pt}\AND%
7399   \lengthtest{\LWR@tempwidth<1pt}%
7400 }%
7401 {\setlength{\LWR@tempwidth}{1pt}}%
```

Likewise with height:

```
7402 \setlength{\LWR@tempheight}{#3}%
7403 \ifthenelse{%
7404   \lengthtest{\LWR@tempheight>0pt}\AND%
7405   \lengthtest{\LWR@tempheight<1pt}%
7406 }%
7407 {\setlength{\LWR@tempheight}{1pt}}%
```

If had a minipage this paragraph, try to inline the rule without generating paragraph tags:

```
7408 \LWR@minipagestopars%
```

Print the span with the converted width and height. The width and height are NOT rounded, since a height of less than 1pt is quite common in  $\text{\LaTeX}$  code.

```
7409 \uselengthunit{PT}%
7410 \LWR@htmltagc{%
7411 span
7412 style=""}
```

The background color is used to draw the filled rule. The color may be changed by `\textcolor`.

```
7413 background:\LWR@currenttextcolor; %
```

The width and height are printed, converted to PT:

```
7414 width:\printlength{\LWR@tempwidth}; %
7415 height:\printlength{\LWR@tempheight}; %
```

The raise height is converted to a css transform. The \*2 raise multiplier is to approximately match **HTML** output's X height. Conversion to a  $\text{\LaTeX}$  length allows a typical  $\text{\LaTeX}$  expression to be used as an argument for the raise, whereas printing the raise argument directly to **HTML** output without conversion to a  $\text{\LaTeX}$  length limits the allowable syntax. To do: A superior method would compute a ratio of  $\text{\LaTeX}$  ex height, then print that to **HTML** with an ex unit.

```
7416 \IfValueT{#1}%
7417 {%
7418   \setlength{\LWR@tempraise}{\Opt-#1}%
7419   \setlength{\LWR@tempraise}{\LWR@tempraise*2}%
7420   \LWR@orignewline%
7421   -ms-transform: translate(\Opt,\printlength{\LWR@tempraise}); %
7422   \LWR@orignewline%
7423   -webkit-transform: translate(\Opt,\printlength{\LWR@tempraise}); %
7424   \LWR@orignewline%
7425   transform: translate(\Opt,\printlength{\LWR@tempraise}); %
7426   \LWR@orignewline%
7427 }%
```

Display inline-block to place the span inline with the text:

```
7428 display:inline-block;"%
7429 }%
7430 \LWR@htmltagc{/span}%
```

---

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
7431     \LWR@minipagestartpars%
7432 }% non-zero width
7433 }
```

```
\rule [⟨raise⟩] {⟨width⟩} {⟨height⟩}
```

Handles special minipage & horizontal space interactions.

```
7434 \renewcommand{\rule}{\LWR@rule}
```

```
7435 \end{warpHTML}
```

## 74 \phantomsection

**for HTML output:** 7436 \begin{warpHTML}

\phantomsection Emulate the hyperref \phantomsection command, often used to insert the bibliography into table of contents:

```
7437 \newcommand*{\phantomsection}{%
7438 \section*{}%
7439 }
```

```
7440 \end{warpHTML}
```

## 75 \LaTeX and other logos

Logos for HTML and print modes:

Some of these logos may be redefined in a later package, so after loading other packages, and at the beginning of the document, their definitions are finally \let in \LWR@LwarpStart.

For css conversions, see:

<http://edward.oconnor.cx/2007/08/tex-poshlet>

<http://nitens.org/taraborelli/texlogo>

## 75.1 HTML logos

**for HTML output:** 7441 \begin{warpHTML}

\TeX \TeX

latexlogo is a css class used to properly typeset the E and A in \TeX and friends.

latexlogofont is a css class used to select the font for the rest of the logo in \TeX, LuaTeX, ConTeXt, etc.

```
7442 \let\LWR@origTeX\TeX
7443
7444 \newcommand*\{\LWR@TeX\}
7445 {\InlineClass{latexlogofont}%
7446 {\InlineClass{latexlogo}{T\textsubscript{e}X}}}
```

\LaTeX \TeX, \TeX2e

\LaTeXe

```
7447 \let\LWR@origLaTeX\LaTeX
7448
7449 \newcommand*\{\LWR@LaTeX\}
7450 {\InlineClass{latexlogofont}%
7451 {\InlineClass{latexlogo}%
7452 {L\textsuperscript{a}T\textsubscript{e}X}}}
7453
7454 \let\LWR@origLaTeXe\LaTeXe
7455
7456 \renewcommand*\{\LaTeXe\}
7457 {\LaTeX\InlineClass{latexlogofont}%
7458 {\textit{\HTMLunicode{3B5}}}}}
```

\LuaTeX \LuaTeX, \LuaTeX

\LuaLaTeX

```
7459 \newcommand*\{\LWR@LuaTeX\}{\InlineClass{latexlogofont}{Lua}\TeX}
7460 \newcommand*\{\LWR@LuaLaTeX\}{\InlineClass{latexlogofont}{Lua}\LaTeX}
```

\XeTeX \XeTeX, \XeTeX

\XeLaTeX

xetexlogo is a css class which aligns the backwards E in \XeTeX and spaces \TeX appropriately.

xelatexlogo is a css class which aligns the backwards E in \XeTeX and spaces \TeX appropriately.

```
7461 \newcommand*\{\Xe\}
```

```
7462 {X\textsubscript{\HTMLunicode{18e}}}
7463 \newcommand*{\LWR@XeTeX}{\InlineClass{xetexlogo}{\Xe}\TeX}
7464 \newcommand*{\LWR@XeLaTeX}{\InlineClass{xelatexlogo}{\Xe}\LaTeX}
```

## \ConTeXt ConTeXt

```
7465 \newcommand*{\LWR@ConTeXt}
7466 {\InlineClass{latexlogofont}{Con}\TeX{}}
7467 \InlineClass{latexlogofont}{t}}
```

\BibTeX BIB<sub>E</sub>X, *MakeIndex*

```
\MakeIndex
7468 \providecommand*{\BibTeX}
7469 {\InlineClass{latexlogofont}{B\textsc{ib}}}\TeX}
7470
7471 \newcommand*{\MakeIndex}
7472 {\InlineClass{latexlogofont}{\textit{MakeIndex}}}
```

## \AmS \mathcal{AM}S

`amslogo` is a css class used for the  $\mathcal{AM}S$  logo.

```
7473 \AtBeginDocument{\DeclareDocumentCommand{\AmS}{}
7474 {\InlineClass{amslogo}{\textit{A}\textsubscript{M}S}}}}
```

\MiKTeX MiK<sub>E</sub>X

```
7475 \newcommand*{\MiKTeX}{\InlineClass{latexlogofont}{MiK}\TeX}
```

## \LyX LyX

`lyxlogo` is a css class used for the LyX logo.

```
7476 \newcommand*{\LyX}{\InlineClass{lyxlogo}{LyX}}
7477 \end{warpHTML}
```

## 75.2 Print logos

**for PRINT output:**

```
7478 \begin{warpprint}
7479 \newcommand*{\XeTeXrevE}
7480 {\hspace{-.1667em}\raisebox{-.5ex}{\reflectbox{E}}\hspace{-.125em}}
7481 \providecommand*{\XeTeX}{\mbox{X}\XeTeXrevE\TeX}
7482 \providecommand*{\XeLaTeX}{\mbox{X}\XeTeXrevE\LaTeX}
```

```
7483 \providecommand*\AmS{}%
7484 \leavevmode\hbox{$\mathcal{A}\kern-.2em\lower.376ex%
7485 \hbox{$\mathcal{M}$}\kern-.2em\mathcal{S}$}%
7486 \newcommand*\LyX{\textsf{LyX}}%
7487 \providecommand*\LuaTeX{\mbox{Lua\TeX}}%
7488 \providecommand*\LuaLaTeX{\mbox{Lua\LaTeX}}%
7489 \providecommand*\BibTeX{\mbox{B\textit{e}TeX}}%
7490 \providecommand*\MakeIndex{\mbox{\textit{MakeIndex}}}%
7491 \providecommand*\ConTeXt{\mbox{Con\TeX{}t}}%
7492 \providecommand*\MiKTeX{\mbox{MiK\TeX}}%
7493 \end{warpprint}
```

## 76 \AtBeginDocument, \AtEndDocument

**for HTML output:** 7494 \begin{warpHTML}

\LWR@LwarpStart Automatically sets up the HTML-related actions for the start and end of the document.

```
\LWR@LwarpEnd
7495 \AfterEndPreamble{\LWR@LwarpStart}
7496 \AtEndDocument{\LWR@LwarpEnd}

7497 \end{warpHTML}
```

## 77 Trademarks

- TeX is a trademark of American Mathematical Society.
- Adobe® and Adobe Framemaker® are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.
- Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries.
- Mac OS® is a trademark of Apple Inc.
- MadCap Flare™ is the property of MadCap Software, Inc.
- MathJax is copyright 2009 and later. The MathJax Consortium is a joint venture of the American Mathematical Society (AMS) and the Society for Industrial and Applied Mathematics (SIAM) to advance mathematical and scientific content on the web.
- Microsoft®, Encarta, MSN, and Windows® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
- UNIX® is a registered trademark of The Open Group.

---

File 2 **l warp-a4.sty**

§ 78 Package **a4**

Pkg a4 a4 is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{a4}

2 \newcommand\*{\WideMargins}{}

---

File 3 **l warp-a4wide.sty**

§ 79 Package **a4wide**

Pkg a4wide a4wide is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{a4wide}

---

File 4 **l warp-a5comb.sty**

§ 80 Package **a5comb**

Pkg a5comb a5comb is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{a5comb}

---

File 5 **l warp-abstract.sty**

§ 81 Package **abstract**

(Based on original code by PETER WILSON.)

Pkg abstract abstract is supported and patched by l warp.

 **missing TOC** If using the number option with file splits, be sure to place the table of contents before the abstract. The number option causes a section break which may cause a

file split, which would put a table of contents out of the home page if it is after the abstract.

**for HTML output:** Accept all options for \warp-abstract:

```
1 \LWR@ProvidesPackagePass{abstract}

2 \AtBeginDocument{
3 \BeforeBeginEnvironment{abstract}{
4 \LWR@forcenewpage
5 \BlockClass{abstract}
6 }
7 \AfterEndEnvironment{abstract}{\endBlockClass}
8 }
9
10 \renewcommand{\@bsrunintitle}{%
11 \hspace*{\abstitleskip}%
12 {\abstractnamefont{%
13 \InlineClass{abstractrunintitle}{\abstractname}%
14 \@bslabeldelim}%
15 }%
16
17 \if@titlepage
18 \ renewenvironment{abstract}{%
19 % \titlepage
20 \null\vfil
21 \begin{parpenalty}\lowpenalty
22 \if@bsrunin
23 \else
24 \if@bsstyle
25 \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}%
26 \else
27 \ifnumber@bs
28 \num@bs
29 \else
30 \begin{absnamepos}%
31 \abstractnamefont \BlockClassSingle{abstracttitle}{\abstractname}%
32 \end{parpenalty}\OM
33 \end{absnamepos}%
34 %% \vspace{\abstitleskip}%
35 \fi
36 \fi
37 \vspace{\abstitleskip}%
38 \fi
39 \put@bsintoc%
40 \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
41 {\par\end{@bstr@ctlist}\vfil\null%\endtitlepage
42 }
43 \else
44 \renewenvironment{abstract}{%
```

---

```

45      \if@bsrunin
46      \else
47          \if@bsstyle
48              \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
49          \else
50              \ifnumber@bs
51                  \num@bs
52              \else
53 \begin{\absnamepos}%
54 \abstractnamefont\BlockClassSingle{abstracttitle}{\abstractname}%
55 \end\absnamepos%
56 %%           \vspace{\abstitleskip}%
57           \fi
58           \fi
59           \vspace{\abstitleskip}%
60           \fi
61           \put@bsintoc%
62 \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
63 {\par\end{@bstr@ctlist}}
64 \fi
65

```

---

File 6 **l warp-adjmulticol.sty**

## § 82 Package **adjmulticol**

Pkg adjmulticol adjmulticol is emulated.

Emulation similar to multicols is used, with adjusted margins. If the number of columns is specified as 1, it is set so, but if two or greater are used, l warp allows a variable number of columns up to three.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{adjmulticol}

2 \RequirePackage{multicol}

adjmulticols * {\langle numcols\rangle} {\langle left margi\rangle} {\langle right margin\rangle}

3 \NewDocumentEnvironment{adjmulticols}{s m m m}
4 {%

```

Compute the margins, and limit to positive only:

```

5 \setlength{\LWR@templengthone}{#3}%
6 \ifdimcomp{\LWR@templengthone}{<}{0pt}{\setlength{\LWR@templengthone}{0pt}}{}%
7 \setlength{\LWR@templengthtwo}{#4}%
8 \ifdimcomp{\LWR@templengthtwo}{<}{0pt}{\setlength{\LWR@templengthtwo}{0pt}}{}%

```

---

If one column is specified, use a <div> of class `singlecolumn`, else use `multicols`:

```
9 \newcommand*{\LWR@mcolltype}{multicols}%
10 \ifnumcomp{#2}{=}{1}{\renewcommand*{\LWR@mcolltype}{singlecolumn}}{}%
```

Help avoid page overflow:

```
11 \LWR@forcenewpage%
```

Print margins in points:

```
12 \uselengthunit{PT}%
```

Create the <div> with the given margin and class:

```
13 \BlockClass[%
14 margin-left:\rndprintlength{\LWR@templengthone} ; %
15 margin-right:\rndprintlength{\LWR@templengthtwo}%
16 ]{\LWR@mcolltype}%
17 }
18 {\endBlockClass}
```

---

#### File 7 lwarf-addlines.sty

### § 83 Package **addlines**

Pkg `addlines` `addlines` is emulated.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{addlines}

2 \newcommand*\addlines[1][1] {}
3 \let\addline\addlines
4 \newcommand*\removelines[1][1] {}
5 \let\removeline\removelines
```

---

#### File 8 lwarf-afterpage.sty

### § 84 Package **afterpage**

Pkg `afterpage` Emulated.

**for HTML output:** Discard all options for `lwarf-afterpage`:

```
1 \LWR@ProvidesPackageDrop{afterpage}
```

---

```
2 \newcommand{\afterpage}[1]{#1}
```

---

File 9 **lwarp-algorithmicx.sty**

§ 85 Package **algorithmicx**

Pkg **algorithmicx** algorithmicx is supported with minor adjustments.

**for HTML output:** 1 \LWR@ProvidesPackagePass{algorithmicx}

Inside the `algorithmic` environment, level indenting is converted to a `<span>` of the required length, and comments are placed inside a `<span>` which is floated right.

⚠️ package conflicts If using `\newfloat`, `trivfloat`, and/or `algorithmicx` together, see section 232.1.

**for HTML output:** 2 \begin{warpHTML}

```
3 \AtBeginEnvironment{algorithmic}{%
4 %
5 \let\origALG@doentity\ALG@doentity%
6 %
7 \renewcommand*\ALG@doentity{%
8 \origALG@doentity%
9 \uselengthunit{PT}%
10 \LWR@htmntagc{%
11 span style="width:\rndprintlength{\ALG@thistlm}; display:inline-block;"%
12 }%
13 \LWR@htmntagc{/span}%
14 }%
15 %
16 \let\origComment\Comment%
17 %
18 \renewcommand{\Comment}[1]{\InlineClass{floatright}{\origComment{#1}}{}}%
19 }
```

20 \end{warpHTML}

---

File 10 **lwarp-alltt.sty**

§ 86 Package **alltt**

Pkg **alltt** alltt is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{alltt}

---

```

2 \AfterEndPreamble{
3 \LWR@traceinfo{Patching alltt.}
4 \AtBeginEnvironment{alltt}{%
5 \LWR@forcenewpage
6 \LWR@atbeginverbatim{alltt}\unskip\LWR@origvspace*{-\baselineskip}%
7 }
8 \AfterEndEnvironment{alltt}{\unskip\LWR@origvspace*{-\baselineskip}\LWR@afterendverbatim}
9 }

```

---

File 11 **l warp-amsthm.sty**

§ 87 Package **amsthm**

*(Based on original code by PUBLICATIONS TECHNICAL GROUP — AMERICAN MATHEMATICAL SOCIETY.)*

Pkg amsthm amsthm is patched for use by l warp.

**CSS styling of theorems and proofs:**

**Theorem:** <div> of class amsthmbody<theoremstyle>  
**Theorem Name:** <span> of class amsthmname<theoremstyle>  
**Theorem Number:** <span> of class amsthmnumber<theoremstyle>  
**Theorem Note:** <span> of class amsthmnote<theoremstyle>  
**Proof:** <div> of class amsthmproof  
**Proof Name:** <span> of class amsthmproofname  
where <theoremstyle> is plain, definition, etc.

**for HTML output:** 1 \LWR@ProvidesPackagePass{amsthm}

Storage for the style being used for new theorems:

```
2 \newcommand{\LWR@newtheoremstyle}{plain}
```

Patched to remember the style being used for new theorems:

```

3 \renewcommand{\theoremstyle}[1]{%
4   \@ifundefined{th@#1}{%
5     \PackageWarning{amsthm}{Unknown theoremstyle '#1'}%
6     \thm@style{plain}%
7     \renewcommand{\LWR@newtheoremstyle}{plain}%
8   }{%
9     \thm@style{#1}%
}

```

```

10      \renewcommand{\LWR@newtheoremstyle}{#1}%
11  }%
12 }

```

Patched to remember the style for this theorem type:

```

13 \def\@xnthm#1#2{%
14   \csedef{\LWR@thmstyle#2}{\LWR@newtheoremstyle}%
15   \let\@tempa\relax
16   \xp@ifdefinable\csname #2\endcsname{%
17     \global\xp\let\csname end#2\endcsname\@endtheorem
18     \ifx *#1% unnumbered, need to get one more mandatory arg
19       \edef\@tempa##1{%
20         \gdef\xp\@nx\csname#2\endcsname{%
21           \@nx\@thm{\xp\@nx\csname th@\the\thm@style\endcsname}%
22             {}{##1}}%
23       \else % numbered theorem, need to check for optional arg
24         \def\@tempa{\oparg{\cynthm{#2}}[]}%
25       \fi
26     \AtBeginEnvironment{#2}{\edef{\LWR@thisthmstyle}{\csuse{\LWR@thmstyle#2}}}%
27   }%
28   \atempa
29 }

```

Patched to enclose with css:

```

30 \newcommand{\LWR@haveamsthmname}{%
31 \renewcommand{\thmname}[1]{\InlineClass{amsthmname}\LWR@thisthmstyle{##1}}
32 }%
33
34 \newcommand{\LWR@haveamsthmnumber}{%
35 \renewcommand{\thmnumber}[1]{\InlineClass{amsthmnumber}\LWR@thisthmstyle{##1}}
36 }%
37
38 \newcommand{\LWR@haveamsthmnote}{%
39 \renewcommand{\thmnote}[1]{\InlineClass{amsthmnote}\LWR@thisthmstyle{##1}}
40 }%
41
42 \LWR@haveamsthmname
43 \LWR@haveamsthmnumber
44 \LWR@haveamsthmnote

```

Patches for css:

```

45 \def\@begintheorem#1#2[#3]{%
46 \LWR@forcenewpage% new
47   \BlockClass{amsthmbody}\LWR@thisthmstyle}% new
48   \deferred@thm@head{%
49     \the\thm@headfont \thm@indent

```

```

50  \@ifempty{#1}{\let\thmname\@gobble}{\LWR@haveamsthmname}\% new
51  \@ifempty{#2}{\let\thmnumber\@gobble}{\LWR@haveamsthmnumber}\% new
52  \@ifempty{#3}{\let\thmnote\@gobble}{\LWR@haveamsthmnote}\% new
53  \thm@swap\swappedhead\thmhead{#1}{#2}{#3}\%
54  \the\thm@headpunct-
55  \thmheadnl % possibly a newline.
56  \hskip\thm@headsep
57 }\%
58 \ignorespaces}

```

Patched for css:

```
59 \def\@endtheorem{\endBlockClass\endtrivlist\@endpefalse }
```

Proof QED symbol:

```

60 \AtBeginDocument{
61 \def\openbox{\text{\HTMLunicode{25A1}}}\% UTF-8 white box
62 \def\blacksquare{\text{\HTMLunicode{220E}}}\% UTF-8 end-of-proof
63 \def\Box{\text{\HTMLunicode{25A1}}}\% UTF-8 white box
64 }

```

Patched for css:

```

65 \renewenvironment{proof}[1][\proofname]{\par
66 \LWR@forcenewpage\% new
67 \BlockClass{amsthmproof}\% new
68 \pushQED{\qed}\%
69 \normalfont \topsep6\p@\oplus6\p@\relax
70 \trivlist
71 \item[\hskip\labelsep
72 \quad\quad\quad\InLineClass{amsthmproofname}{\#1\@addpunct{.}}]\ignorespaces\% changes
73 }\%
74 \InLineClass{theoremendmark}{\popQED}\endtrivlist%
75 \endBlockClass\% new
76 \@endpefalse
77 }

```

File 12 **lwarf-anonchap.sty**

§ 88 Package **anonchap**

Pkg **anonchap** **anonchap** is emulated.

⚠ **tocloft & other packages** If using **tocloft** with **tocbibind**, **anonchap**, **fncychap**, or other packages which change chapter title formatting, load **tocloft** with its **titles** option, which tells **tocloft** to use standard **LATEX** commands to create the titles, allowing other packages to work with it.

The code is shared by tocbibind.

```
for HTML output: 1 \LWR@ProvidesPackageDrop{anonchap}

2 \newcommand{\simplechapter}[1] [\\empty]{%
3   \def\@chapcntformat##1{%
4     #1~\csname the##1\endcsname\simplechapterdelim\protect\quad%
5   }%
6 }
7
8 \newcommand{\restorechapter}{%
9 \let\@chapcntformat\@secntformat%
10 }
```

---

File 13 l warp-anysize.sty

## § 89 Package **anysize**

Pkg **anysize** anysize is emulated.

```
for HTML output: 1 \LWR@ProvidesPackageDrop{anysize}

2 \def\papersize#1#2{}
3 \def\marginsize#1#2#3#4{}
```

---

File 14 l warp-appendix.sty

## § 90 Package **appendix**

Pkg **appendix** appendix is patched for use by l warp.

- ⚠ **incorrect toc link** During HTML conversion, the option `toc` without the option `page` results in a `toc` link to whichever section was before the `appendices` environment. It is recommended to use both `toc` and also `page` at the same time.

```
for HTML output: 1 \LWR@ProvidesPackagePass{appendix}

2 \renewcommand*{\@chap@pppage}{%
3 \part*{\appendixpagename}
4 \if@dotoc@pp
5 \addappheadtotoc
6 \fi
7 }
```

---

```

8
9 \renewcommand*{\@sec@pppage}{%
10 \part*{\appendixpagename}
11 \if@dotoc@pp
12 \addappheadtotoc
13 \fi
14 }

```

---

File 15 **lwarf-arabicfront.sty**

§91 Package **arabicfront**

Pkg **arabicfront** arabicfront is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{arabicfront}

---

File 16 **lwarf-authblk.sty**

§92 Package **authblk**

Pkg **authblk** authblk is patched for HTML.

**package support** lwarf supports the native L<sup>A</sup>T<sub>E</sub>X titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

**\published and \subtitle** If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 52.7.

(Based on original code by PATRICK W. DALY.)

**for HTML output:** Require that authblk be loaded before titling:

```

1 \@ifpackageloaded{titling}{
2 \PackageError{lwarf-authblk}{%
3 Package authblk must be loaded before titling}%
4 {Titling appends authblk's author macro, so authblk must be loaded first.}%
5 }%
6 {}

```

Load authblk:

```
7 \LWR@ProvidesPackagePass{authblk}
```

Patch to add a class for the affiliation:

---

```

8 \LetLtxMacro\LWRAB@affil\affil
9
10 \renewcommand{\affil}[2][]{%
11 \LWRAB@affil[#1]{\protect\InlineClass{affiliation}{#2}}%
12 }

```

Create an HTML break for an \authorcr:

```
13 \renewcommand*{\authorcr}{\protect\LWR@newlinebr}
```

---

#### File 17 **lwarf-balance.sty**

### § 93 Package **balance**

Pkg **balance** Emulated.

**for HTML output:** Discard all options for lwarf-balance:

```

1 \LWR@ProvidesPackageDrop{balance}
2 \newcommand*{\balance}{}%
3 \newcommand*{\nobalance}{}%

```

---

#### File 18 **lwarf-bigdelim.sty**

### § 94 Package **bigdelim**

Pkg **bigdelim** **bigdelim** is used as-is for print or *lateximage*, and patched for HTML.

The delimiters are displayed in HTML by printing the delimiter, the text, and a thick border across the side of the *\multirow* which indicates the actual height of the delimiter. The delimiter character is given a *<span>* class of *ldelim* or *rdelim*, and the default css sets this to *font-size:200%*.

⚠ **use *\mrowcell*** *\ldelim* and *\rdelim* use *\multirow*, so *\mrowcell* must be used in the proper number of empty cells in the same column below *\ldelim* or *\rdelim*, but not in cells which are above or below the delimiter:

---

```
\begin{tabular}{lll}
<empty> & a & b \\
\l delim{\{}{2}{.25in}[left ] & c & d \\
\mrowcell & e & f \\
<empty> & g & h \\
\end{tabular}
```

---

|        |   |   |
|--------|---|---|
|        | a | b |
| left { | c | d |
|        | e | f |
|        | g | h |

**for HTML output:** First, remove the temporary definitions of \l delim and \r delim, which were previously defined for tabular scanning in case bigdelim was not loaded:

```
1 \let\l delim\relax
2 \let\r delim\relax
```

Next, load the package's new definitions:

```
3 \LWR@ProvidesPackagePass{bigdelim}
```

Remember the print-mode versions:

```
4 \LetLtxMacro{\LWR@origl delim}{\l delim}
5 \LetLtxMacro{\LWR@origr delim}{\r delim}
```

```
\l delim {{1:delimiter}} {(2:#rows)} {(3:width)} [(4:text)]
\r delim
6 \RenewDocumentCommand{\l delim}{m m m O{} }{%
7 \renewcommand{\LWR@multirowborder}{right}%
8 \multirow{#2}{#3}{#4} \InlineClass{l delim}{#1} }%
9 }
10
11 \RenewDocumentCommand{\r delim}{m m m O{} }{%
12 \renewcommand{\LWR@multirowborder}{left}%
13 \multirow{#2}{#3}{\InlineClass{r delim}{#1} #4}%
14 }
```

When entering a `lateximage`, restore the print-mode versions:

```
15 \appto{\LWR@restoreorigformatting}{%
16 \LetLtxMacro{\l delim}{\LWR@origl delim}%
17 \LetLtxMacro{\r delim}{\LWR@origr delim}%
18 }
```

---

File 19 **l warp-bigstrut.sty**

§ 95 Package **bigstrut**

Pkg **bigstrut** **bigstrut** is used as-is for print or `lateximage`, and patched for HTML.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{bigstrut}
2 \LetLtxMacro{\LWR@origbigstrut}{\bigstrut}
3
4 \renewcommand{\bigstrut}[1][x]{}
5
6 \appto{\LWR@restoreorigformatting}{%
7 \LetLtxMacro{\bigstrut}{\LWR@origbigstrut}%
8 }
```

---

File 20 **l warp-bookmark.sty**

§ 96 Package **bookmark**

Pkg **bookmark** **bookmark** is emulated during HTML output, and the `bookmark` package is ignored.

**for HTML output:** Discard all options for `l warp-bookmark`:

```
1 \LWR@ProvidesPackageDrop{bookmark}
2 \newcommand*{\bookmarksetup}[1]{}
3 \newcommand*{\bookmarksetupnext}[1]{}
4 \newcommand*{\bookmark}[2][]{}
5 \newcommand*{\bookmarkdefinestyle}[2]{}
6 \newcommand*{\bookmarkget}[1]{}
7 \newcommand{\BookmarkAtEnd}[1]{}
```

---

File 21 **l warp-booktabs.sty**

§ 97 Package **booktabs**

Pkg **booktabs** **booktabs** is emulated during HTML output, and used as-is during print output and inside an HTML `lateximage`.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{booktabs}
```

Booktabs emulation is spread among the tabular code. The original definitions are saved here for use in HTML lateximages. The HTML versions temporarily overwrite these print versions when tabular is started.

```
2 \LetLtxMacro{\LWR@origtoprule}{\toprule}
3 \LetLtxMacro{\LWR@origmidrule}{\midrule}
4 \LetLtxMacro{\LWR@origcmidrule}{\cmidrule}
5 \LetLtxMacro{\LWR@origbottomrule}{\bottomrule}
6 \LetLtxMacro{\LWR@origaddlinespace}{\addlinespace}
7 \LetLtxMacro{\LWR@origmorecmidrules}{\morecmidrules}
8 \LetLtxMacro{\LWR@origspecialrule}{\specialrule}
```

---

File 22 **l warp-boxedminipage.sty**

§ 98 Package **boxedminipage**

Pkg **boxedminipage** boxedminipage is superceded by boxedminipage2e.

**for HTML output:** 1 \LWR@loadnever{boxedminipage}{boxedminipage2e}

---

File 23 **l warp-boxedminipage2e.sty**

§ 99 Package **boxedminipage2e**

Pkg **boxedminipage2e** boxedminipage2e is emulated.

**for HTML output:** Discard all options for l warp-boxedminipage2e:

```
1 \LWR@ProvidesPackageDrop{boxedminipage2e}

2 \newenvironment{boxedminipage}{%
3 \begin{BlockClass}{framebox}%
4 \minipage{%
5 }%
6 {%
7 \endminipage{%
8 \end{BlockClass}%
9 }}
```

---

File 24 **l warp-caption2.sty**

§ 100 Package **caption2**

Pkg caption2 caption2 is not used. The user is recommended to use caption instead.

for HTML output: 1 \LWR@loadnever{caption2}{caption}

---

File 25 **l warp-ccaption.sty**

§ 101 Package **ccaption**

Pkg ccaption ccaption is not used. The user is recommended to use caption instead.

for HTML output: 1 \LWR@loadnever{ccaption}{caption}

---

File 26 **l warp-changepage.sty**

§ 102 Package **changepage**

Pkg changepage changepage is ignored.

for HTML output: Discard all options for l warp-changepage:

```
1 \LWR@ProvidesPackageDrop{changepage}

2 \newif\ifoddpage
3 \DeclareRobustCommand{\checkoddpage}{\oddpage=true}
4 \DeclareRobustCommand{\changetext}[5]{}
5 \DeclareRobustCommand{\changepage}[9]{}
6 \newenvironment{adjustwidth}[2]{}{}
7 \newenvironment{adjustwidth*}[2]{}{}
```

---

File 27 **l warp-chngpage.sty**

§ 103 Package **chngpage**

Pkg chngpage chngpage is superceded by changepage.

**for HTML output:** 1 \LWR@loadnever{chngpage}{changepage}

---

File 28 **lwarf-chappg.sty**

§ 104 Package **chappg**

Pkg chappg chappg is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{chappg}

2 \renewcommand{\pagenumbering}[2] [] {}  
3 \providecommand{\chappgsep}{--}

---

File 29 **lwarf-color.sty**

§ 105 Package **color**

Pkg color Allowed but ignored. xcolor is then required as well.

color is superceded by xcolor, and lwarf requires several of the features of xcolor.

⚠ **missing colors** It should be sufficient for the user's document to load color then load xcolor as well.

**for HTML output:** 1 \LWR@ProvidesPackagePass{color}  
2 \RequirePackage{xcolor}

---

File 30 **lwarf-crop.sty**

§ 106 Package **crop**

Pkg crop Emulated.

**for HTML output:** Discard all options for lwarf-crop:

1 \LWR@ProvidesPackageDrop{crop}  
2 \newcommand\*{\crop}[1] [] {}  
3 \newcommand\*{\cropdef}[6] [] {}

---

File 31 **l warp-cuted.sty**

§ 107 Package **cuted**

Pkg cuted cuted is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{cuted}

2 \newenvironment{strip}{}{}
3 \newskip\stripsep
4 \def\oldcolsbreak#1{}
```

---

File 32 **l warp-cutwin.sty**

§ 108 Package **cutwin**

Pkg cutwin Emulated.

for HTML output: Discard all options for l warp-cutwin:

```
1 \LWR@ProvidesPackageDrop{cutwin}

2 \newcommand*\opencutleft{}
3 \newcommand*\opencutright{}
4 \newcommand*\opencutcenter{}
5 \newcommand*\cutfuzz{}

6
7 \newenvironment{cutout}[4]
8 {\marginpar{\windowpagestuff}}
9 {}

10 \newcommand*\windowpagestuff{}

12 \newcommand*\pageinwindow{%
13 % \begin{minipage}{.3\linewidth}
14 % \begin{minipage}{.3\linewidth}
15 \windowpagestuff
16 % \end{minipage}
17 }

18 \newenvironment{shapedcutout}[3]
19 {\marginpar{\picinwindow}}
20 {}

21 {}
```

```
22
23 \newcommand*{\putstuffinpic}{}%
24
25 \newcommand*{\picinwindow}{%
26 \begin{picture}(0,0)
27 \putstuffinpic
28 \end{picture}}
```

---

File 33 **l warp-dblfnote.sty**

§ 109 Package **dblfnote**

Pkg dblfnote dblfnote is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{dblfnote}

2 \newcounter{DFNsloppiness}
3 \newdimen\DFNcolumnsep
4 \newdimen\DFNcolumnwidth
5 \def\DFNallowcbreak{}
6 \def\DFNinhibitcbreak{}
7 \def\DFNtrysingle{}
8 \def\DFNalwaysdouble{}
9 \def\DFNruleboth{}
10 \def\DFNruleleft{}
```

---

File 34 **l warp-dcolumn.sty**

§ 110 Package **dcolumn**

Pkg dcolumn dcolumn is emulated during HTML output, and the dcolumn package is ignored.

```
1 \LWR@ProvidesPackageDrop{dcolumn}
```

---

File 35 **l warp-draftwatermark.sty**

§ 111 Package **draftwatermark**

Pkg draftwatermark draftwatermark is emulated during HTML output, and the draftwatermark package is ignored.

for HTML output:

---

```

1 \LWR@ProvidesPackageDrop{draftwatermark}

2 \newcommand{\SetWatermarkAngle}[1]{}
3 \newcommand{\SetWatermarkColor}[1]{}
4 \newcommand{\SetWatermarkLightness}[1]{}
5 \newcommand{\SetWatermarkFontSize}[1]{}
6 \newcommand{\SetWatermarkScale}[1]{}
7 \newcommand{\SetWatermarkHorCenter}[1]{}
8 \newcommand{\SetWatermarkVertCenter}[1]{}
9 \newcommand{\SetWatermarkText}[1]{}

```

---

File 36 **lwarf-ebook.sty**

§ 112 Package **ebook**

Pkg **ebook** ebook is emulated.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{ebook}

2 \setcounter{secnumdepth}{0}
3 \setcounter{tocdepth}{2}
4
5 \providecommand{\pagefill}[1][0.001mm]{\noindent}
6
7 \providecommand{\ebook}{%
8 \setcounter{secnumdepth}{0}
9 \setcounter{tocdepth}{2}
10 }

```

---

File 37 **lwarf-ellipsis.sty**

§ 113 Package **ellipsis**

Pkg **ellipsis** ellipsis is emulated during HTML output, and the ellipsis package is ignored.

```

1 \LWR@ProvidesPackageDrop{ellipsis}
2
3 \newcommand{\ellipsisgap}{0.1em}

```

---

File 38 **l warp-emptypage.sty**

§ 114 Package **emptypage**

Pkg **emptypage** emptypage is ignored.

**for HTML output:** Discard all options for l warp-emptypage:

```
1 \LWR@ProvidesPackageDrop{emptypage}
```

---

File 39 **l warp-endnotes.sty**

§ 115 Package **endnotes**

(Based on original code by JOHN LAVAGNINO.)

Pkg **endnotes** Used as-is.

**table of contents** To place the endnotes in the TOC, use:

```
\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*\notesname{Endnotes} % optional
```

**HTML page** To additionally have the endnotes on their own HTML page, if FileDepth allows:

```
\ForceHTMLPage
\theendnotes
```

**for HTML output:** 1 \LWR@ProvidesPackagePass{endnotes}

```
2 \def\enoteformat{%
3 % \rightskip\z@ \leftskip\z@ \parindent=1.8em
4 \leavevmode
5 % \llap{
6 \makeenmark
7 %
8 }
9
10 \def\@makeenmark{\hbox{\LWR@htmlspan{sup}{\normalfont\theenmark}}}
11 \def\makeenmark{\@makeenmark}
```

---

File 40 **lwarf-enumerate.sty**

§ 116 Package **enumerate**

Pkg **enumerate** **enumerate** is supported with no changes.

This package is only required because it was used in the past to drop and then emulate the package. It cannot be removed because an older version which dropped the package may still remain, for example in a local vs. distribution directory, but it is now supported directly by lwarf and thus must no longer be dropped.

**for HTML output:** 1 \LWR@ProvidesPackagePass{enumerate}

---

File 41 **lwarf-enumitem.sty**

§ 117 Package **enumitem**

Pkg **enumitem** **enumitem** is supported with minor adjustments.

**for HTML output:** 1 \LWR@ProvidesPackagePass{enumitem}

**for HTML output:** 2 \begin{warpHTML}

```
\newlist {\name} {\type} {\maxdepth}
\renewlist {\name} {\type} {\maxdepth}
```

For enumitem lists, new lists must have the start and end actions assigned to the new environment. Renewed lists already have their actions assigned, and thus need no changes.

```
3 \let\LWR@orignewlist\newlist
4
5 \renewcommand*\newlist[3]{%
6 \LWR@orignewlist{#1}{#2}{#3}%
7 \AtBeginEnvironment{#1}{\csuse{\LWR@#2start}}%
8 \AtEndEnvironment{#1}{\csuse{\LWR@#2end}}%
9 }

10 \end{warpHTML}
```

---

File 42 **lwarf-epigraph.sty**

## § 118 Package **epigraph**

Pkg epigraph epigraph is emulated during HTML output, and the epigraph package is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{epigraph}

2 \newcommand{\qitem}[2]
3 {
4 \begin{BlockClass}{qitem}
5 #1
6 \begin{BlockClass}{epigraphsource}
7 #2
8 \end{BlockClass}
9 \end{BlockClass}
10 }

11 \newcommand{\epigraph}[2]
12 {
13 \begin{BlockClass}{epigraph}
14 \qitem{#1}{#2}
15 \end{BlockClass}
16 }
17
18 \newenvironment*{epigraphs}
19 {\BlockClass{epigraph}}
20 {\endBlockClass}
```

Use CSS to format epigraphs.

The following are null commands for source compatibility:

```

21 \newlength{\epigraphwidth}
22 \setlength{\epigraphwidth}{.5\linewidth}
23 \newenvironment*{\flushepinormal}{}{}
24 \newcommand{\textflush}[1]{\flushepinormal}
25 \newcommand{\epigraphflush}[1]{\flushright}
26 \newcommand{\sourceflush}[1]{\flushright}
27 \newcommand*{\epigraphsize}{\small}
28 \newlength{\epigrphrule}
29 \newlength{\beforeepigraphskip}
30 \newlength{\afterepigraphskip}
31 \newcommand{\epigraphhead}[2][0]{#2}
32 \newcommand{\dropchapter}[1]{}  

```

---

```
33 \newcommand*{\undodrop}{}  
34 \newcommand{\cleartoevenpage}[1] [] {}
```

---

File 43 **lwarf-eso-pic.sty**

§ 119 Package **eso-pic**

Pkg **eso-pic** **eso-pic** is emulated during HTML output, and the **eso-pic** package is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{eso-pic}  
  
2 \newcommand*{\LenToUnit}{}  
3 \newcommand{\AtPageUpperLeft}[1] {}  
4 \newcommand{\AtPageLowerLeft}[1] {}  
5 \newcommand{\AtPageCenter}[1] {}  
6 \newcommand{\AtStockLowerLeft}[1] {}  
7 \newcommand{\AtStockUpperLeft}[1] {}  
8 \newcommand{\AtStockCenter}[1] {}  
9 \newcommand{\AtTextUpperLeft}[1] {}  
10 \newcommand{\AtTextLowerLeft}[1] {}  
11 \newcommand{\AtTextCenter}[1] {}  
12 \NewDocumentCommand{\AddToShipoutPictureBG}{s +m} {}  
13 \renewcommand{\AddToShipoutPicture}{\AddToShipoutPictureBG}  
14 \NewDocumentCommand{\AddToShipoutPictureFG}{s +m} {}  
15 \newcommand*{\ClearShipoutPictureBG}{}  
16 \newcommand*{\ClearShipoutPicture}{}  
17 \newcommand*{\ClearShipoutPictureFG}{}  
18 \newcommand{\gridSetup}[6] [] {}
```

---

File 44 **lwarf-everypage.sty**

§ 120 Package **everypage**

Pkg **everypage** **everypage** is emulated during HTML output, and the **everypage** package is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{everypage}  
  
2 \newcommand*{\AddEverypageHook}[1] {}  
3 \newcommand*{\AddThispageHook}[1] {}
```

---

File 45 **l warp-everyshi.sty**

§ 121 Package **everyshi**

Pkg **everyshi** Emulated.

**for HTML output:** Discard all options for l warp-everyshi:

```
1 \LWR@ProvidesPackageDrop{everyshi}
2 \newcommand*\{\EveryShipout}[1]{}
3 \newcommand*\{\AtNextShipout}[1]{}
```

---

File 46 **l warp-extramarks.sty**

§ 122 Package **extramarks**

Pkg **extramarks** extramarks is not used.

**for HTML output:** Discard all options for l warp-extramarks:

```
1 \LWR@ProvidesPackageDrop{extramarks}
2 \newcommand*\{\extramarks}[2]{}
3 \newcommand*\{\firstleftxmark\}{}
4 \newcommand*\{\lastleftxmark\}{}
5 \newcommand*\{\firstrightxmark\}{}
6 \newcommand*\{\lastrightxmark\}{}
7 \newcommand*\{\firstxmark\}{}
8 \newcommand*\{\lastxmark\}{}
9 \newcommand*\{\topxmark\}{}
10 \newcommand*\{\topleftxmark\}{}
11 \newcommand*\{\firstleftmark\}{}
12 \newcommand*\{\lastrightmark\}{}
```

---

File 47 **l warp-fancybox.sty**

§ 123 Package **fancybox**

(Based on original code by TIMOTHY VAN ZANDT.)

Pkg fancybox fancybox is supported with some patches.

**framed equation example** fancybox's documentation has an example `FramedEqn` environment which combines `math`, `\Sbox`, a `minipage`, and an `\fbox`. This combination requires that the entire environment be enclosed inside a `latextimage`, which is done by adding `\latextimage` at the very start of `FramedEqn`'s beginning code, and `\endlatextimage` at the very end of the ending code. Unfortunately, the `HTML alt` attribute is not used here.

```
\newenvironment{FramedEqn}
{
  \latextimage% NEW
  \setlength{\fboxsep}{15pt}
  ... }{...
  \[\fbox{\TheSbox}\]}
  \endlatextimage% NEW
}
```

**framing alternatives** `\fbox` works with fancybox. Also see lwarf's `\fboxBlock` macro and `fminipage` environment for alternatives to `\fbox` for framing environments.

**framed table example** The fancybox documentation's example framed table using an `\fbox` containing a `tabular` does not work with lwarf, but the `FramedTable` environment does work if `\fbox` is replaced by `\fboxBlock`. This method loses HTML formatting. A better method is to enclose the table's contents inside a `fminipage` environment. The caption may be placed either inside or outside the `fminipage`:

```
\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
...
\end{tabular}
\end{fminipage}
\end{table}
```

**framed verbatim** lwarf does not support the `verbatim` environment inside a span, box, or fancybox's `\Sbox`, but a `verbatim` may be placed inside a `fminipage`. The fancybox documentation's example `FramedVerb` may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
  \VerbatimEnvironment
  \fminipage{#1}
  \begin{Verbatim}
  \end{Verbatim}
  \endfminipage
}
```

**framed \VerbBox** fancybox's \VerbBox may be used inside \fbox.

**indented alignment** LVerbatim, \LVerbatimInput, and \LUseVerbatim indent with horizontal space which may not line up exactly with what pdftotext detects. Some lines may be off slightly in their left edge.

**for HTML output:**

```

1 \begin{warpHTML}

2 \LWR@ProvidesPackagePass{fancybox}

3 \renewcommand*{\@shadowbox}[1]{\InlineClass{shadowbox}{#1}}
4
5 \renewcommand*{\@doublebox}[1]{\InlineClass{doublebox}{#1}}
6
7 \renewcommand*{\@ovalbox}[2]{%
8 \ifthenelse{\isequivalentto{#1}{\thinlines}}%
9 {\InlineClass{ovalbox}{#2}}
10 {\InlineClass{Ovalbox}{#2}}
11 }

```

Convert minipages, parboxes, and lists into linear text using the \LWR@nestspan environment:

```

12 \let\LWR@origSbox\Sbox
13
14 \def\Sbox{\LWR@origSbox\LWR@nestspan}
15
16
17 \let\LWR@origendSbox\endSbox
18
19 \def\endSbox{\endLWR@nestspan\LWR@origendSbox}

```

\Beqnarray is adapted for MathJax or enclosed inside a \latexitimage:

```

20 \RenewEnviron{Beqnarray}
21 {\LWR@eqnarrayfactor}
22
23 \csgpreto{Beqnarray*}{\boolfalse{LWR@numbereqnarray}}

```

\GenericCaption is enclosed in an HTML block:

```

24 \renewcommand{\GenericCaption}[1]{%
25 \LWR@htmlblocktag{figcaption}%
26 #1%
27 \LWR@htmlblocktag{/figcaption}%
28 }

```

\Btrivlist is enclosed in an HTML block:

---

```

29 \RenewDocumentEnvironment{Btrivlist}{m o}
30 {\begin{BlockClass}{Btrivlist}\tabular{\#1}}
31 {\endtabular\end{BlockClass}}

```

Btrivlist is also neutralized when used inside a span:

```

32 \AtBeginEnvironment{LWR@nestspan}{%
33 \RenewDocumentEnvironment{Btrivlist}{m o}{}{}%
34 \RenewDocumentCommand{\LWR@origitem}{d()}{\LWRFB@origitem}%
35 }

```

lwarf's handling of \item is patched to accept fancybox's optional arguments:

```

36 \let\LWRFB@origitemizeitem\LWR@itemizeitem
37 \let\LWRFB@origdescitem\LWR@descitem
38 \LetLtxMacro{\LWRFB@origitem}{\LWR@origitem}
39
40 \RenewDocumentCommand{\LWR@itemizeitem}{d()}{\LWRFB@origitemizeitem}
41 \RenewDocumentCommand{\LWR@descitem}{d()}{\LWRFB@origdescitem}

```

The various boxed lists become regular lists:

```

42 \renewenvironment{Bitemize}[1][]{\begin{itemize}}{\end{itemize}}
43 \renewenvironment{Benumerate}[1][]{\begin{enumerate}}{\end{enumerate}}
44 \renewenvironment{Bdescription}[1][]{\begin{description}}{\end{description}}

```

\boxput simply prints one then the other argument, side-by-side instead of above and behind:

```

45 \RenewDocumentCommand{\boxput}{s d() m m}{%
46 \IfBooleanTF{#1}{#3\quad#4}{#4\quad#3}%
47 }

```

Neutralized commands:

```

48 \RenewDocumentCommand{\fancyput}{s d() m}{}
49 \RenewDocumentCommand{\thisfancyput}{s d() m}{}
50
51 \RenewDocumentCommand{\fancypage}{m m}{}
52 \RenewDocumentCommand{\thisfancypage}{m m}{}
53
54 \def\LandScape#1{}
55 \def\endLandScape{}
56 \def\@Landscape#1#2#3{}
57 \def\endLandscape{}

```

Low-level patches for Verbatim, VerbatimInput, UseVerbatim:

```

58 \let\LWRFB@UseVerbatim\UseVerbatim
59 \renewcommand*\USeVerbatim}[1]{%
60 \LWR@atbeginverbatim{Verbatim}\unskip\LWR@origvspace*{-.5\baselineskip}%%
61 \LWRFB@UseVerbatim{#1}%
62 \LWR@afterendverbatim%
63 }
64
65 \let\LWRFB@LUseVerbatim\LUseVerbatim
66
67 \renewcommand*\LUseVerbatim}[1]{%
68 \LWR@atbeginverbatim{LVerbatim}\% \unskip\LWR@origvspace*{-\baselineskip}%%
69 \noindent%
70 \LWRFB@LUseVerbatim{#1}%
71 \LWR@afterendverbatim%
72 }
73
74 \def\@BUseVerbatim[#1]#2{%
75 \LWR@atbeginverbatim{BVerbatim}\unskip\LWR@origvspace*{-.5\baselineskip}%%
76 \LWRFB@UseVerbatim{#2}%
77 \LWR@afterendverbatim%
78 }

79 \end{warpHTML}

```

File 48 **l warp-fancyhdr.sty**

§ 124      Package **fancyhdr**

Pkg **fancyhdr** fancyhdr is nullified.

**for HTML output:** Discard all options for l warp-fancyhdr:

```

1 \LWR@ProvidesPackageDrop{fancyhdr}

2 \newcommand*\fancyhead}[2][]{}
3 \newcommand*\fancyfoot}[2][]{}
4 \newcommand*\fancyhf}[2][]{}
5 \newcommand*\fancypagestyle}[2][]{}
6 \newcommand*\lhead}[2][]{}
7 \newcommand*\chead}[2][]{}
8 \newcommand*\rhead}[2][]{}
9 \newcommand*\lfoot}[2][]{}
10 \newcommand*\cfoot}[2][]{}
11 \newcommand*\rfoot}[2][]{}

```

---

```

12 \newcommand*{\headrulewidth}{}
13 \newcommand*{\footrulewidth}{}
14 \newcommand*{\fancyheadoffset}[2][]{}
15 \newcommand*{\fancyfootoffset}[2][]{}
16 \newcommand*{\fancyhoffset}[2][]{}
17 \newcommand*{\iffloatpage}[2]{#2}
18 \newcommand*{\ifftopfloat}[2]{#2}
19 \newcommand*{\iffbotfloat}[2]{#2}

```

---

File 49 **l warp-fancyvrb.sty**

§ 125 Package **fancyvrb**

*(Based on original code by TIMOTHY VAN ZANDT.)*

Pkg fancyvrb fancyvrb is supported with some patches.

**for HTML output:** 1 \RequirePackage{xcolor}%; for \convertcolorspec  
2 \LWR@ProvidesPackagePass{fancyvrb}

**for HTML output:** 3 \begin{warpHTML}

Initial default patch for fancyvrb:

4 \fvset{frame=none}%;

For \VerbatimFootnotes:

```

5 \renewcommand{\VerbatimFootnotes}{%
6 \PackageError{l warp}{%
7 Verbatim footnotes are not yet supported by l warp.}%
8 {This may be improved some day.}%
9 }

```

After the preamble is loaded, after any patches to Verbatim:

```

10 \AfterEndPreamble{%
11 \LWR@traceinfo{Patching Verbatim.}}

```

Remember the original defintion of Verbatim:

```
12 \let\LWR@FV@origVerbatim\Verbatim
```

Env Verbatim Patched to place the environment in a fancyvrb div, and the label in a fancyvrblabel div. Also corrects the left margin for line numbers. Also uses VerbatimHTMLWidth to

control placement of line numbers on the right. Aligning the right margin requires knowing the width.

```
13 \renewcommand*\{\\Verbatim\}{%
14 \\LWR@forcenewpage%
15 \\LWRFV@origVerbatim%
16 }
```

**\LWR@FVstyle** Holds the style of the verbatim.

```
17 \\newcommand*\{\\LWR@FVstyle\}{}
```

The following patches to Verbatim are executed at the start and end of the environment, depending on the choice of frame. Original code is from the fancyvrb package.

```
18 \\newcommand*\{\\LWR@fvstartnone\}{%
19 \\LWR@traceinfo{fvstartnone}%
20 \\hbox to\\z@{\\LWR@atbeginverbatim[\\LWR@FVstyle]{verbatim}}%
21 }
22
23 \\newcommand*\{\\LWR@fvendnone\}{%
24 \\LWR@traceinfo{fvendnone}%
25 \\hbox to\\z@{\\LWR@afterendverbatim}%
26 }
27
28 \\newcommand*\{\\LWR@fvstartsingle\}{%
29 \\LWR@traceinfo{fvstartsingle}%
30 \\LWR@fvstartnone%
31 \\FV@BeginListFrame@Single%
32 }
33
34 \\newcommand*\{\\LWR@fvendsingle\}{%
35 \\LWR@traceinfo{fvendsingle}%
36 \\FV@EndListFrame@Single%
37 \\LWR@fvendnone%
38 }
39
40 \\newcommand*\{\\LWR@fvstartline\}{%
41 \\LWR@traceinfo{fvstartline}%
42 \\LWR@fvstartnone%
43 \\FV@BeginListFrame@Lines%
44 }
45
46 \\newcommand*\{\\LWR@fvendline\}{%
47 \\LWR@traceinfo{fvendline}%
48 \\FV@EndListFrame@Lines%
49 \\LWR@fvendnone%
```

50 }

The following patches select the start/left/right/end behaviors depending on frame. Original code is from the fancyvrb package.

```
51
52 \newcommand*{\LWR@FVfindcurrentcolor}{%
53 \protect\colorlet{LWR@current@color}{.}%
54 \protect\convertcolorspec[named]{LWR@current@color}{HTML}{LWR@tempcolor}%
55 }
56
57 \newcommand*{\LWR@FVtextstyle}{%
58 \LWR@FVfindcurrentcolor
59 \ifdefstring{\LWR@tempcolor}{000000}%
60 {}%
61 {color: \#\LWR@tempcolor ; }%
62 }
63
64
65 \newcommand*{\LWR@FVfindbordercolor}{%
66 \FancyVerbRuleColor%
67 \LWR@FVfindcurrentcolor
68 \color{black}%
69 }
70
71 % border width of \FV@FrameRule
72 \newcommand*{\LWR@FVborderstyle}[1]{%
73 padding#1: \strip@pt\dimexpr \FV@FrameSep\relax\relax pt ;
74 \LWR@FVfindbordercolor
75 border#1: \strip@pt\dimexpr \FV@FrameRule\relax\relax pt solid \#\LWR@tempcolor ;
76 }
77
78 \def\FV@Frame@none{%
79 \renewcommand*{\LWR@FVstyle}{\LWR@FVtextstyle}%
80 \let\FV@BeginListFrame\LWR@fvstartnone%
81 \let\FV@LeftListFrame\relax%
82 \let\FV@RightListFrame\relax%
83 \let\FV@EndListFrame\LWR@fvendnone}
84
85 \FV@Frame@none% default values
86
87 \def\FV@Frame@singles{%
88 \renewcommand*{\LWR@FVstyle}{\LWR@FVtextstyle\LWR@FVborderstyle{}}%
89 \let\FV@BeginListFrame\LWR@fvstartsingle%
90 \let\FV@LeftListFrame\FV@LeftListFrame@Single%
91 \let\FV@RightListFrame\FV@RightListFrame@Single%
92 \let\FV@EndListFrame\LWR@fvendsingle}
93
94 \def\FV@Frame@lines{%
```

```

95 \renewcommand*{\LWR@FVstyle}{%
96   \LWR@FVtextstyle\LWR@FVborderstyle{-top}\LWR@FVborderstyle{-bottom}%
97 }%
98 \let\FV@BeginListFrame\LWR@fvstartline%
99 \let\FV@LeftListFrame\relax%
100 \let\FV@RightListFrame\relax%
101 \let\FV@EndListFrame\LWR@fvendline}
102
103 \def\FV@Frame@topline{%
104 \renewcommand*{\LWR@FVstyle}{\LWR@FVtextstyle\LWR@FVborderstyle{-top}}%
105 \let\FV@BeginListFrame\LWR@fvstartline%
106 \let\FV@LeftListFrame\relax%
107 \let\FV@RightListFrame\relax%
108 \let\FV@EndListFrame\LWR@fvendnone}
109
110 \def\FV@Frame@bottomline{%
111 \renewcommand*{\LWR@FVstyle}{\LWR@FVtextstyle\LWR@FVborderstyle{-bottom}}%
112 \let\FV@BeginListFrame\LWR@fvstartnone%
113 \let\FV@LeftListFrame\relax%
114 \let\FV@RightListFrame\relax%
115 \let\FV@EndListFrame\LWR@fvendline}
116
117 \def\FV@Frame@leftline{%
118 \renewcommand*{\LWR@FVstyle}{\LWR@FVtextstyle\LWR@FVborderstyle{-left}}%
119 % To define the \FV@FrameFillLine macro (from \FV@BeginListFrame)
120 \ifx\fancyVerbFillColor\relax%
121 \let\FV@FrameFillLine\relax%
122 \else%
123 \tempdima\FV@FrameRule\relax%
124 \multiply\tempdima-\tw@%
125 \edef\FV@FrameFillLine{%
126 {\noexpand\fancyVerbFillColor{\vrule\width\number\tempdima sp}%
127 \kern-\number\tempdima sp}}%
128 \fi%
129 \let\FV@BeginListFrame\LWR@fvstartnone%
130 \let\FV@LeftListFrame\FV@LeftListFrame@Single%
131 \let\FV@RightListFrame\relax%
132 \let\FV@EndListFrame\LWR@fvendnone}

```

Adds the optional label to the top and bottom edges. Original code is from the fancyvrb package.

```

133 \def\FV@SingleFrameLine#1{%
134   \hbox to\z@{%
135 %     \kern\leftmargin
136     \ifnum#1=\z@\relax
137       \let\FV@Label\FV@LabelBegin
138     \else
139       \let\FV@Label\FV@LabelEnd

```

```

140      \fi
141      \ifx\FV@Label\relax
142 %         \FancyVerbRuleColor{\vrule \width\linewidth \height\FV@FrameRule}%
143     \else
144     \ifnum#1=\z@
145 %         \setbox\z@\hbox{\strut\enspace\FV@LabelBegin\enspace\strut}%
146         \ifx\FV@LabelPositionTopLine\relax
147         \else
148         \LWR@FVfindbordercolor
149         \LWR@htmltagc{div class="fancyvrblabel" style="color: \#\LWR@tempcolor"}%
150         \LWR@origtextrm{\FV@LabelBegin}%
151         \LWR@origtextrm{\FV@LabelEnd}%
152         \LWR@htmltagc{/div}
153         \fi
154     \else
155         \setbox\z@\hbox{\strut\enspace\FV@LabelEnd\enspace\strut}%
156         \ifx\FV@LabelPositionBottomLine\relax
157         \else
158         \LWR@FVfindbordercolor
159         \LWR@htmltagc{div class="fancyvrblabel" style="color: \#\LWR@tempcolor"}%
160         \LWR@origtextrm{\FV@LabelEnd}%
161         \LWR@htmltagc{/div}
162         \fi
163     \fi
164     \fi
165     \hss
166   }
167 }
```

Processes each line, adding optional line numbers. Original code is from the fancyvrb package.

```

168 \def\FV@ListProcessLine#1{%
169   \hbox to \hsize{%
170 %     \kern\leftmargin
171     \hbox to \VerbatimHTMLWidth {%
172       \ifcsvoid{FV@LeftListNumber}{}{\kern 2.5em}%
173       \FV@LeftListNumber%
174       \FV@LeftListFrame
175       \FancyVerbFormatLine{#1}%
176       \hss%
177       \FV@RightListFrame
178       \FV@RightListNumber%
179     }%
180     \hss% required to avoid underfull hboxes
181   }
182 }
```

Env **BVerbatim**

```

183 \AtBeginEnvironment{BVerbatim}
184 {
185 \LWR@forcenewpage
186 \LWR@atbeginverbatim{bverbatim}
187
188 }
189
190 \AfterEndEnvironment{BVerbatim}
191 {
192 \leavevmode\par\LWR@origvspace{-\baselineskip}
193 \LWR@afterendverbatim
194 }
```

End of the modifications to make at the end of the preamble:

```

195 } % \AfterEndPreamble

196 \end{warpHTML}
```

---

File 50 **lwarp-figcaps.sty**

§ 126 Package **figcaps**

Pkg **figcaps** Emulated.

**for HTML output:** Discard all options for lwarp-figcaps:

```

1 \LWR@ProvidesPackageDrop{figcaps}

2 \newcommand*\{\figcapson\}={}
3 \newcommand*\{\figcapsoff\}={}
4 \newcommand*\{\printfigures\}={}
5 \newcommand*\{\figmarkon\}={}
6 \newcommand*\{\figmarkoff\}={}
7 \def\figurecapname{Figure Captions}
8 \def\tablepagename{Tables}
9 \def\figurepagename{Figures}
```

---

File 51 **l warp-fix2col.sty**

§ 127 Package **fix2col**

Pkg fix2col fix2col is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{fix2col}

---

File 52 **l warp-float.sty**

§ 128 Package **float and \newfloat**

Pkg float float is emulated during HTML output, and the float package is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{float}[2016/03/04]

See section 61.2 for the \listof command.

\newfloat {\langle 1: type\rangle} {\langle 2: placement\rangle} {\langle 3: ext\rangle} [{\langle 4: within\rangle}]

Emulates the \newfloat command from the float package.

“placement” is ignored.

```
2 \NewDocumentCommand{\newfloat}{m m m o}{%
3 \IfValueTF{#4}{%
4 {\\DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}}%
5 {\\DeclareFloatingEnvironment[fileext=#3]{#1}}%
```

newfloat package automatically creates the \listof command for new floats, but float does not, so remove \listof here in case it is manually created later.

```
6 \cslet{listof#1s}\relax
7 \cslet{listof#1es}\relax
8 }
```

\floatname {\langle type\rangle} {\langle name\rangle}

Sets the text name of the float, such as “Figure”.

```
9 \NewDocumentCommand{\floatname}{m +m}{%
```

```

10 \SetupFloatingEnvironment{#1}{name=#2}%
11 }

\floatplacement {⟨type⟩} {⟨placement⟩}
Float placement is ignored.

12 \newcommand*{\floatplacement}[2]{%
13 \SetupFloatingEnvironment{#1}{placement=#2}%
14 }

\floatstyle {⟨style⟩}
Float styles are ignored.

15 \newcommand{\floatstyle}[1]{%
16 }

\restylefloat * {⟨style⟩}
Float styles are ignored.

17 \NewDocumentCommand{\restylefloat}{s m}{%
18 }

```

### File 53 lwarf-floatflt.sty

## § 129 Package **floatflt**

Pkg floatflt Emulated.

**for HTML output:** Discard all options for lwarf-floatflt:

```
1 \LWR@ProvidesPackageDrop{floatflt}
```

Borrowed from the lwarf version of keyfloat:

```

2 \NewDocumentEnvironment{KFLTfloatflt@marginfloat}{O{-1.2ex} m}
3 {%
4 \LWR@maybeinthisfloat%
5 \LWR@forcenewpage%
6 \LWR@stoppars%
7 \LWR@htmlltag{div class="marginblock" id="autofloat-\arabic{LWR@thisfloat}"}
8 \LWR@startpars%
9 \captionsetup{type=#2}%

```

---

```

10 }
11 {
12 \LWR@htmldivclassend{div}
13 }
14
15 \DeclareDocumentEnvironment{floatingfigure}{o m}
16   {\begin{KFLTfloatfltnomarginfloat}{figure}}
17   {\end{KFLTfloatfltnomarginfloat}}
18
19 \DeclareDocumentEnvironment{floatingtable}{o +m}
20   {\begin{KFLTfloatfltnomarginfloat}{table}\#2}
21   {\end{KFLTfloatfltnomarginfloat}}

```

---

File 54 **lwarf-floatpag.sty**

§ 130 Package **floatpag**

Pkg **floatpag** Emulated.

**for HTML output:** Discard all options for lwarf-floatpag:

```

1 \LWR@ProvidesPackageDrop{floatpag}

2 \newcommand*{\floatpagestyle}[1]{}
3 \newcommand*{\rotfloatpagestyle}[1]{}
4 \newcommand*{\thisfloatpagestyle}[1]{}

```

---

File 55 **lwarf-floatrow.sty**

§ 131 Package **floatrow**

Pkg **floatrow** floatrow is emulated during HTML output, and the floatrow package is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{floatrow}

⚠ **subfig package** When combined with the subfig package, while inside a subfloatrow \ffigbox and \ttabbox must have the caption in the first of the two of the mandatory arguments.

⚠ **\FBwidth, \FBheight** The emulation of floatrow does not support \FBwidth or \FBheight. These values are pre-set to .3\linewidth and 2in. Possible solutions include:

- Use fixed lengths. lwarf will scale the HTML lengths appropriately.

- Use `warpprint` and `warpHTML` environments to select appropriate values for each case.
- Inside a `warpHTML` environment, manually change `\FBwidth` or `\FBheight` before the `\ffigbox` or `\ttabbox`. Use `\FBwidth` or `\FBheight` normally afterwards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

After everything has loaded, remember whether `subcaption` was loaded. If not, it is assumed that `subfig` is used instead:

```

2 \newbool{LWR@subcaptionloaded}
3
4 \AtBeginDocument{
5 \@ifpackageloaded{subcaption}
6 {\booltrue{LWR@subcaptionloaded}}
7 {\boolfalse{LWR@subcaptionloaded}}
8 }

\floobox  [{<1 preamble>} {<2 captype>} [<3 width>] [<4 height>] [<5 vert pos>] {<6 caption>}
{<7 object>}
```

Only parameters for `captype`, `width`, `caption`, and `object` are used.

`LWR@insubfloatrow` is true if inside a `subfloatrow` environment.

There are two actions, depending on the use of `subcaption` or `subfig`.

```

9 \NewDocumentCommand{\floobox}{o m o o +m +m}{%
10 \ifbool{LWR@subcaptionloaded}{%
11 {}% subcaption
```

For `subcaption`:

```

12 \ifbool{LWR@insubfloatrow}{%
13 {}% subcaption in a subfloatrow
```

`subfigure` and `subtable` environments take `width` as an argument.

```

14 \IfValueTF{#3}{%
15 {\@nameuse{sub#2}{#3}}%
16 {\@nameuse{sub#2}{\linewidth}}%
17 }% subcaption in a subfloatrow
18 {}% subcaption not in subfloatrow
```

`figure` and `table` environments do not take a `width` argument.

```

19 \IfValueTF{#3}{%
20 {\@nameuse{#2}{#3}}%
21 }% subcaption not in subfloatrow
22 #6
23 #7
```

End the environments:

```
24     \ifbool{LWR@insubfloatrow}%
25     {\@nameuse{endsub#2}}%
26     {\@nameuse{end#2}}%
27 }% subcaption
28 { % assume subfig
```

For subfig:

```
29 \ifbool{LWR@insubfloatrow}%
30 { % subfig in a subfloatrow
```

\subfloat is a macro, not an environment.

Package subfig's \subfloat command takes an optional argument which is the caption, but \floatbox argument #6 contains commands to create the caption and label, not the caption itself. Thus, \caption is temporarily disabled to return its own argument without braces.

```
31     \begingroup
32     \let\caption\@firstofone
33     \subfloat[#6]{#7}
34     \endgroup
35 }% subfig in a subfloatrow
36 { % subfig package, but not a subfig
```

figure and table are environments:

```
37 \@nameuse{#2}
38 #6
39
40 #7
41 \@nameuse{end#2}
42 }% subfig package, but not a subfig
43 { % assume subfig
44 }
```

Not used:

```
45 \newcommand*{\nocapbeside}{}%
46 \newcommand*{\capbeside}{}%
47 \newcommand*{\caption}{}%
48 \newlength{\FBwidth}%
49 \setlength{\FBwidth}{.3\linewidth}%
50 \newlength{\FBheight}%
51 \setlength{\FBheight}{2in}%
52 \newcommand*{\useFCwidth}{}%
53 \newcommand{\floatsetup}[2][]{}
54 \newcommand{\thisfloatsetup}[1]{}%
55 \newcommand{\clearfloatsetup}[1]{}%
56 \newcommand*{\killfloatstyle}{}%
```

---

\newfloatcommand {⟨1 command⟩} {⟨2 captype⟩} [⟨3 preamble⟩] [⟨4 default width⟩]  
Preamble and default width are ignored.

```
57 \NewDocumentCommand{\newfloatcommand}{m m o o}{%
58 \CnameDef{#1}{%
59 \floatbox{#2}{%
60 }%
61 }}
```

\renewfloatcommand {⟨1 command⟩} {⟨2 captype⟩} [⟨3 preamble⟩] [⟨4 default width⟩]  
Preamble and default width are ignored.

```
62 \NewDocumentCommand{\renewfloatcommand}{m m o o}{%
63 \CnameDef{#1}{%
64 \floatbox{#2}{%
65 }%
66 }}
```

\ffigbox [⟨width⟩] [⟨height⟩] [⟨vposn⟩] {⟨caption commands⟩} {⟨contents⟩}  
67 \newfloatcommand{ffigbox}{figure}[\nocapbeside] []

\ttabbox [⟨width⟩] [⟨height⟩] [⟨vposn⟩] {⟨caption commands⟩} {⟨contents⟩}  
68 \newfloatcommand{ttabbox}{table}[\captop] [\FBwidth]

\fcapside [⟨width⟩] [⟨height⟩] [⟨vposn⟩] {⟨caption commands⟩} {⟨contents⟩}  
69 \newfloatcommand{fcapside}{figure}[\capbeside] []

Env floatrow [⟨numfloats⟩]

The row of floats is placed into a <div> of class floatrow.

```
70 \newenvironment*{floatrow}[1][2]{%
71 {%
72 \LWR@forcenewpage%
73 \BlockClass{floatrow}}
```

While inside the floatrow, divide the \linewidth by the number of floats.

```
74 \booltrue{\LWR@infloatrow}%
75 \setlength{\linewidth}{\dimexpr 6in/\the\value{floatrow}\relax}%
76 }%
77 {%
78 \boolfalse{\LWR@infloatrow}%
79 \endBlockClass%
80 }
```

Keys for \DeclareNewFloatType:

```

81 \newcommand*{\LWR@frowkeyplacement}{}
82 \newcommand*{\LWR@frowkeyname}{}
83 \newcommand*{\LWR@frowkeyfileext}{}
84 \newcommand*{\LWR@frowkeywithin}{}
85 \newcommand*{\LWR@frowkeycapstyle}{}
86
87 \define@key{frowkeys}{placement}{}
88 \define@key{frowkeys}{name}{\renewcommand{\LWR@frowkeyname}{#1}}
89 \define@key{frowkeys}{fileext}{\renewcommand{\LWR@frowkeyfileext}{#1}}
90 \define@key{frowkeys}{within}{\renewcommand{\LWR@frowkeywithin}{#1}}
91 \define@key{frowkeys}{relatedcapstyle}{}

```

\DeclareNewFloatType {*<type>*} {*<options>*}

Use \listof{*type*}[Title] to print a list of the floats.

```
92 \newcommand*{\DeclareNewFloatType}[2]{}
```

Reset key values:

```

93 \renewcommand*{\LWR@frowkeyplacement}{}
94 \renewcommand*{\LWR@frowkeyname}{}
95 \renewcommand*{\LWR@frowkeyfileext}{}
96 \renewcommand*{\LWR@frowkeywithin}{}
97 \renewcommand*{\LWR@frowkeycapstyle}{}

```

Read new key values:

```

98 \LWR@traceinfo{about to setkeys frowkeys}
99 \setkeys{frowkeys}{#2}
100 \LWR@traceinfo{finished setkeys frowkeys}

```

Create a new float with optional [within]:

```

101 \ifthenelse{\equal{\LWR@frowkeywithin}{}}{
102 {
103     \LWR@traceinfo{about to newfloat #1 \LWR@frowkeyplacement \
104                 \LWR@frowkeyfileext}%
105     \newfloat{#1}{\LWR@frowkeyplacement}{\LWR@frowkeyfileext}
106 }%
107 {%
108     \LWR@traceinfo{about to newfloat #1\ \LWR@frowkeyplacement \
109                 \LWR@frowkeyfileext\ \LWR@frowkeywithin}%
110     \newfloat{#1}{\LWR@frowkeyplacement}%
111     {\LWR@frowkeyfileext}{\LWR@frowkeywithin}%
112     \LWR@traceinfo{finished newfloat #1}
113 }%

```

Rename the float if a name was given:

```
114 \ifthenelse{\equal{\LWR@frowkeyname}{}}{
```

```
115 {}
116 {\floatname{\#1}{\LWR@frowkeyname}}%
117 }
```

Not used:

```
118 \newcommand{\buildFBBOX}[2]{}
119 \newcommand*{\CenterFloatBoxes}(){}
120 \newcommand*{\TopFloatBoxes}){}
121 \newcommand*{\BottomFloatBoxes}){}
122 \newcommand*{\PlainFloatBoxes}){}
123
124 \newcommand{\capsubrowsettings}){}
125
126 \NewDocumentCommand{\RawFloats}{o o}{}
```

`\RawCaption {<text>}`

To be used inside a minipage or parbox.

```
127 \newcommand{\RawCaption}[1]{#1}
```

`\floatfoot {<text>}`

Places additional text inside a float, inside a css <div> of class `floatfoot`.

```
128 \NewDocumentCommand{\floatfoot}{s +m}{%
129 \begin{BlockClass}{floatfoot}
130 #2
131 \end{BlockClass}
132 }
```

Used to compute `\linewidth`.

```
133 \newbool{\LWR@insubfloatrow}
134 \boolfalse{\LWR@insubfloatrow}
```

`Env subfloatrow [<num_floats>]`

```
135 \newenvironment*{subfloatrow}[1][2]
136 {
```

The row of floats is placed into a <div> of class `floatrow`:

```
137 \LWR@forcenewpage
138 \BlockClass{floatrow}
```

While inside the `floatrow`, `LWR@insubfloatrow` is set true, which tells `\floatbox` to use `\subfigure` or `\subtable`.

```
139 \begingroup
```

---

```

140 \booltrue{LWR@insubfloatrow}
141 }
142 {
143 \endgroup
144 \endBlockClass
145 \boolfalse{LWR@insubfloatrow}
146 }

```

---

File 56 **l warp-flushend.sty**

§ 132 Package **flushend**

Pkg **flushend** Emulated.

**for HTML output:** Discard all options for l warp-flushend:

```

1 \LWR@ProvidesPackageDrop{flushend}
2 %     \end{ma-crocode}
3 %
4 %     \begin{macrocode}
5 \newcommand*\flushend{}%
6 \newcommand*\raggedend{}%
7 \newcommand*\flushcolsend{}%
8 \newcommand*\raggedcolsend{}%
9 \newcommand*\atColsBreak[1]{}%
10 \newcommand*\atColsEnd[1]{}%
11 \newcommand*\showcolsendlrule{}%

```

---

File 57 **l warp-fncychap.sty**

§ 133 Package **fncychap**

Pkg **fncychap** fncychap is ignored.

**for HTML output:** Discard all options for l warp-fncychap:

```

1 \LWR@ProvidesPackageDrop{fncychap}

2 \def\mghrulefill#1{}
3 \def\ChNameLowerCase{}
4 \def\ChNameUpperCase{}
5 \def\ChNameAsIs{}
6 \def\ChTitleLowerCase{}
7 \def\ChTitleUpperCase{}
8 \def\ChTitleAsIs{}

```

---

```

9 \newcommand{\ChRuleWidth}[1]{}
10 \newcommand{\ChNameVar}[1]{}
11 \newcommand{\ChNumVar}[1]{}
12 \newcommand{\ChTitleVar}[1]{}
13 \newcommand{\TheAlphaChapter}{}
14 \newcommand{\DOCH}{}
15 \newcommand{\DOTI}[1]{}
16 \newcommand{\DOTIS}[1]{}
17 \newlength{\mylen}
18 \newlength{\myhi}
19 \newlength{\px}
20 \newlength{\py}
21 \newlength{\pyy}
22 \newlength{\pxx}
23 \newlength{\RW}
24 \newcommand{\FmN}[1]{#1}
25 \newcommand{\FmTi}[1]{#1}

```

---

File 58 **lwarf-fnpos.sty**

§ 134 Package **fnpos**

Pkg **fnpos** **fnpos** is emulated.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{fnpos}

2 \newcommand*{\makeFNbottom}={}
3 \newcommand*{\makeFNmid}={}
4 \newcommand*{\makeFNbelow}={}
5 \newcommand*{\makeFNabove}={}

```

---

File 59 **lwarf-fontenc.sty**

§ 135 Package **fontenc**

Pkg **fontenc** Error if **fontenc** is loaded after **lwarf**.

Discard all options for **lwarf-fontenc**:

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{fontenc}

2 \LWR@loadbefore{fontenc}

```

---

File 60 **l warp-fontspec.sty**

§ 136 Package **fontspec**

Pkg **fontspec** Error if fontspec is loaded after l warp.

Discard all options for l warp-fontspec:

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{fontspec}
2 \LWR@loadbefore{fontspec}
```

---

File 61 **l warp-footmisc.sty**

§ 137 Package **footmisc**

(Based on original code by ROBIN FAIRBAIRNS.)

Pkg **footmisc** footmisc is emulated during HTML output, and the footmisc package is ignored.

```
1 \LWR@ProvidesPackageDrop{footmisc}
```

Some nullified commands:

```
2 \newcommand{\footnotelayout}{}
3 \newcommand{\setfnsymbol}[1]{}
4 \NewDocumentCommand{\DefineFNsymbols}{s m o m}{}
5
6 \newdimen\footnotemargin
7 \footnotemargin1.8em\relax
8
9 \newcommand*\hangfootparskip{0.5\baselineskip}
10 \newcommand*\hangfootparindent{0em}%
11
12 \let\pagefootnoterule\footnoterule
13 \let\mpfootnoterule\footnoterule
14 \def\splitfootnoterule{\kern-3\p@ \hrule \kern2.6\p@}
15
16 \providecommand*\multiplefootnotemarker{3sp}
17 \providecommand*\multfootsep{}{}
```

Using cleveref:

```
18 \providecommand*{\footref}[1]{\labelcref{#1}}
```

The following work as-is:

```
19 \newcommand\mpfootnotemark{%
20   \@ifnextchar[%%
21     \xmpfootnotemark
22   \f%
23     \stepcounter\thempfn
24     \protected@xdef\thefnmark{\thempfn}%
25     \footnotemark
26   }%
27 }
28 \def\xmpfootnotemark[#1]{%
29   \begingroup
30   \csname c@\thempfn\endcsname #1\relax
31   \unrestored@protected@xdef\thefnmark{\thempfn}%
32   \endgroup
33   \footnotemark
34 }
```

File 62 **l warp-footnote.sty**

## § 138 Package **footnote**

Pkg **footnote** footnote is used with minor patches.

**for HTML output:** 1 \LWR@ProvidesPackagePass{footnote}

Removed print-version formatting:

```
2 \def\fn@startnote{%
3   \parboxrestore%
4   \protected@edef\currentlabel{\csname p@\thempfn\endcsname\thefnmark}%
5   \color@begingroup% *** conflicts with l warp
6 }
7
8 \% \let\fn@endnote\color@endgroup% *** conflicts with l warp
9 \newcommand*{\fn@endnote}{%
10 \LWR@htmltagc{/LWR@tagregularparagraph}%
11 \LWR@orignewline%
12 }
```

Removed print-version formatting:

```
13 \def\fn@startfntext{%
14   \setbox\z@\vbox\bgroup%
```

```

15      \fn@startnote%
16      \fn@prefntext%
17      \ignorespaces%
18 }

```

Removed print-version formatting, added closing paragraph tag:

```

19 \def\fn@endfntext{%
20     \LWR@htmltagc{\LWR@tagregularparagraph}%
21     \LWR@orignewline%
22     \fn@postfntext%
23     \egroup%
24     \begingroup%
25     \let\@makefntext\@empty%
26     \let\@finalstrut\@gobble%
27     \LetLtxMacro\rule\@gobbletwo% *8* also the optional argument?
28     \@footnotetext{\unvbox\z@}%
29     \endgroup%
30 }

```

These have been redefined, so re-\let them again:

```

31 \let\endfootnote\fn@endfntext
32 \let\endfootnotetext\endfootnote

```

#### File 63 l warp-footnotehyper.sty

### § 139 Package **footnotehyper**

Pkg **footnotehyper** footnotehyper is a hyperref-safe version of footnote. For l warp, footnotehyper is emulated.

**for HTML output:** Discard all options for l warp-footnotehyper:

```

1 \RequirePackage{footnote}
2 \LWR@ProvidesPackageDrop{footnotehyper}

```

#### File 64 l warp-framed.sty

### § 140 Package **framed**

(Based on original code by DONALD ARSENEAU.)

Pkg **framed** framed is supported and patched by l warp.

**for HTML output:** Accept all options for l warp-framed:

```
1 \LWR@ProvidesPackagePass{framed}
2 \RequirePackage{xcolor}%
3
4 \renewenvironment{framed}{%
5 \LWR@forcenewpage
6 \BlockClass{framed}%
7 }
8 {\endBlockClass}
9
10 \renewenvironment{oframed}{%
11 \LWR@forcenewpage
12 \BlockClass{framed}%
13 }
14 {\endBlockClass}
15
16
17 \renewenvironment{shaded}{%
18 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
19 \LWR@forcenewpage
20 \BlockClass[background: \#\LWR@tempcolor]{framed}%
21 }
22 {\endBlockClass}
23
24 \renewenvironment{shaded*}{%
25 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
26 \LWR@forcenewpage
27 \BlockClass[background: \#\LWR@tempcolor]{framed}%
28 }
29 {\endBlockClass}
30
31
32 \renewenvironment{leftbar}{%
33 \LWR@forcenewpage
34     \BlockClass{framedleftbar}
35     \def\FrameCommand{}%
36     \MakeFramed {}
37 }%
38 {\endMakeFramed\endBlockClass}
39
40
41 \renewenvironment{snugshade}{%
42 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
43 \LWR@forcenewpage
44 \BlockClass[background: \#\LWR@tempcolor]{snugframed}%
45 }
46 {\endBlockClass}
47
```

```
48 \renewenvironment{snugshade}{%
49 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
50 \LWR@forcenewpage
51 \BlockClass[background: \#\LWR@tempcolor]{snugframed}%
52 }
53 {\endBlockClass}
54
55 \let\oframed\framed
56 \let\endoframed\endframed
57
58
59 \RenewEnviron{titled-frame}[1]{%
60 \CustomFBox{#1}{}{Opt}{Opt}{Opt}{\BODY}%
61 }

\CustomFBox {\langle toptitle\rangle} {\langle bottitle\rangle} {\langle thickness top\rangle} {\langle bottom\rangle} {\langle left\rangle} {\langle right\rangle}
{\langle text contents\rangle}

62 \renewcommand{\CustomFBox}[7]{%
63 \convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
64 \LWR@forcenewpage
65 \begin{BlockClass}[border: 3px solid \#\LWR@tempcolor]{framed}%
66 \ifthenelse{\isempty{#1}}{}{%
67   \begin{BlockClass}[background: \#\LWR@tempcolor]{framedtitle}%
68     \textcolor{TFTTitleColor}{\textbf{#1}}%
69   \end{BlockClass}%
70 }%
71 }%
72 #7
73
74 \ifthenelse{\isempty{#2}}{}{%
75   \convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
76   \begin{BlockClass}[background: \#\LWR@tempcolor]{framedtitle}%
77     \textcolor{TFTTitleColor}{\textbf{#2}}%
78   \end{BlockClass}%
79 }%
80 \end{BlockClass}
81 }

\TitleBarFrame [\langle marker\rangle] {\langle title\rangle} {\langle contents\rangle}

82 \renewcommand\TitleBarFrame[3][]{%
83 \CustomFBox
84   {#2}{}%
85   \fboxrule\fboxrule\fboxrule\fboxrule
86   {#3}%
87 }

88 \renewcommand{\TF@Title}[1]{#1}
```

```
MakeFramed {\langle settings\rangle}

89 \let\MakeFramed\relax
90 \let\endMakeFramed\relax
91
92 \NewEnviron{MakeFramed}[1]{%
93 \FrameCommand{\begin{minipage}{\linewidth}\BODY\end{minipage}}%
94 }

\fbox@put@frame {\langle frame cmd no split\rangle} {\langle frame cmd split\rangle}

95 \renewcommand*\fbox@put@frame[2]{%
96 \relax%
97 \tempboxa%
98 }
```

---

## File 65 l warp-ftnright.sty

§ 141 Package **ftnright**

Pkg ftnright ftnright is ignored.

for HTML output: Discard all options for l warp-ftnright:

```
1 \LWR@ProvidesPackageDrop{ftnright}
```

---

## File 66 l warp-fullpage.sty

§ 142 Package **fullpage**

Pkg fullpage Emulated.

for HTML output: Discard all options for l warp-fullpage:

```
1 \LWR@ProvidesPackageDrop{fullpage}
```

---

## File 67 l warp-fullwidth.sty

§ 143 Package **fullwidth**

Pkg fullwidth fullwidth is emulated.

A minipage is used, of no HTML width.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{fullwidth}
2 \newenvironment*{fullwidth}[1] []{%
3 \minipage{fullwidth}%
4 \minipage{\linewidth}%
5 }%
6 {%
7 \endminipage%
8 }
```

---

#### File 68 l warp-geometry.sty

### § 144 Package **geometry**

Pkg **geometry** geometry is preloaded by l warp, but must be nullified as seen by the user's source code.

**for HTML output:** Discard all options for l warp-geometry:

```
1 \LWR@ProvidesPackageDrop{geometry}
2 \renewcommand*{\geometry}{}
3 \renewcommand*{\newgeometry}{}
4 \renewcommand*{\restoregeometry}{}
5 \renewcommand*{\savegeometry}{}
6 \renewcommand*{\loadgeometry}{}
```

---

#### File 69 l warp-glossaries.sty

### § 145 Package **glossaries**

Pkg **glossaries** xindy is required for glossaries.

The default `style=item` option for glossaries conflicts with l warp, so the style is forced to `index` instead.

The page number list in the printed form would become `\nameref`s in HTML, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

**placement and toc options** The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

**Numbered section, on its own HTML page:**

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
...
\printglossaries
```

**Unnumbered section, inline with the current HTML page:**

```
\usepackage[xindy,toc]{glossaries}
...
\printglossaries
```

**Unnumbered section, on its own HTML page:**

```
\usepackage[xindy,toc]{glossaries}
...
\ForceHTMLPage
\printglossaries
```

**Opt IndexLanguage** The `lwarp` package takes an option `IndexLanguage=english` to set the language used by `xindy`. This is passed to `xindy` using its `-L` option, and is used for both index and glossary generation.

**Opt `lwarpmk` `printglossary`** `lwarpmk` has the commands `lwarpmk printglossary` and `lwarpmk htmlglossary` to process the glossaries created by `glossaries` using `xindy`.

**for HTML output:**

```
1 \PassOptionsToPackage{xindy}{glossaries}
2 \LWR@ProvidesPackagePass{glossaries}
3 \setupglossaries{nonumberlist}
4 \setglossarystyle{index}
```

Patched to fix toc pointing to the previous page:

```
5 \renewcommand*\@p@glossarysection}[2]{%
6   \glsclearpage
7   \phantomsection
8   \ifdef\empty\@@glossarysecstar
9   {%
10     \csname\@@glossarysec\endcsname{#2}%
11   }%
12 }
```

In the original, the `toc` entry was made before the section, thus linking to the `phantomsection` in the printed version, but for `HTML` this caused the link to point to the page before the glossaries. Here, the `toc` entry is made after the section is created:

```
13   \csname\@@glossarysec\endcsname*{#2}%
14   \gls@toc{\#1}{\@@glossarysec}%. Moved after the previous line.
15 }%
16 \@@glossaryseclabel
17 }
```

---

File 70 **l warp-graphics.sty**

§ 146 Package **graphics**

Pkg **graphics** **graphics** is emulated.

**for HTML output:** 1 \LWR@ProvidesPackagePass{graphics}

§ 146.1 **Graphics extensions**

\DeclareGraphicsExtensions {⟨list⟩}

\AtBeginDocument allow SVG files instead of PDF:

2 \AtBeginDocument{  
3 \DeclareGraphicsExtensions{.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}  
4 \DeclareGraphicsRule{.svg}{svg}{.svg}{}  
5 \DeclareGraphicsRule{.SVG}{svg}{.SVG}{}  
6 }

Inside a **lateximage**, allow PDF instead of SVG:

7 \appto\LWR@restoreorigformatting{  
8 \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}}%  
9 }

## § 146.2 Length conversions and graphics options

 **whitespace** A scaled image in L<sup>A</sup>T<sub>E</sub>X by default takes only as much space on the page as it requires, but HTML browsers use as much space as the original unscaled image would have taken, with the scaled image over- or under-flowing the area.

```
10 \AtBeginDocument{
11 \renewcommand*{\unitspace}{}
12 }
```

Used to store the user's selected dimensions and HTML class.

The class defaults to "inlineimage" unless changed by a `class=xyx` option.

```
13 \newlength{\LWR@igwidth}
14 \newlength{\LWR@igheight}
15 \newcommand*{\LWR@igwidthstyle}={}
16 \newcommand*{\LWR@igheightstyle}={}
17 \newcommand*{\LWR@igorigin}={}
18 \newcommand*{\LWR@igangle}={}
19 \newcommand*{\LWR@igxscale}{1}
20 \newcommand*{\LWR@igyscale}{1}
21 \newcommand*{\LWR@igclass}{inlineimage}
```

Set the actions of each of the key/value combinations for `\includegraphics`. Many are ignored.

If an optional width was given, set an HTML style:

```
22 \define@key{igraph}{width}{%
23 \setlength{\LWR@igwidth}{#1}%
24 \ifthenelse{\lengthtest{\LWR@igwidth > 0pt}}{%
25 {%
```

Default to use the converted fixed length given:

```
26 \uselengthunit{PT}%
27 \renewcommand*{\LWR@igwidthstyle}[width:\rndprintlength{\LWR@igwidth}]%
```

If ex or em dimensions were given, use those instead:

```
28 \IfEndWith{#1}{ex}{%
29 {\renewcommand*{\LWR@igwidthstyle}[width:#1]{} yes ex
30 {}% not ex
31 \IfEndWith{#1}{em}{%
32 {\renewcommand*{\LWR@igwidthstyle}[width:#1]{} yes em
33 {}% not em
34 \IfEndWith{#1}{\%}{%
35 {\renewcommand*{\LWR@igwidthstyle}[width:#1]{} yes percent
```

```

36      {}% not percent
37      \IfEndWith{#1}{px}%
38      {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes px
39      {}% not px
40 }{}% end of length > 0pt
41 }

```

If an optional height was given, set an HTML style:

```

42 \define@key{igraph}{height}{%
43 \setlength{\LWR@igheight}{#1}%
44 \ifthenelse{\lengthtest{\LWR@igheight > 0pt}}{%
45 {%

```

Default to use the converted fixed length given:

```

46      \uselengthunit{PT}%
47      \renewcommand*{\LWR@igheightstyle}{%
48      height:\rndprintlength{\LWR@igheight} \%%
49      }%

```

If ex or em dimensions were given, use those instead:

```

50      \IfEndWith{#1}{ex}%
51      {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes ex
52      {}% not ex
53      \IfEndWith{#1}{em}%
54      {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes em
55      {}% not em
56      \IfEndWith{#1}{\%}%
57      {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes percent
58      {}% not percent
59      \IfEndWith{#1}{px}%
60      {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes px
61      {}% not px
62 }{}% end of length > 0pt
63 }

```

Handle origin key:

```

64 \define@key{igraph}{origin}{%
65 \renewcommand*{\LWR@igorigin}{#1}%
66 }

```

Handle angle key:

```

67 \define@key{igraph}{angle}{\renewcommand*{\LWR@igangle}{#1}}

```

Handle class key:

```
68 \define@key{igraph}{class}{\renewcommand*{\LWR@igclass}{#1}}
69
```

It appears that `graphicx` does not have separate keys for `xscale` and `yscale`. `scale` adjusts both at the same time.

```
70 \define@key{igraph}{scale}{%
71 \renewcommand*{\LWR@igxscale}{#1}%
72 \renewcommand*{\LWR@igyscale}{#1}}
```

Numerous ignored keys:

```
73 \define@key{igraph}{bb}{}
74 \define@key{igraph}{bbllx}{}
75 \define@key{igraph}{bbly}{}
76 \define@key{igraph}{bburx}{}
77 \define@key{igraph}{bbury}{}
78 \define@key{igraph}{natwidth}{}
79 \define@key{igraph}{natheight}{}
80 \define@key{igraph}{hiresbb}{}
81 \define@key{igraph}{viewport}{}
82 \define@key{igraph}{trim}{}
83 \define@key{igraph}{totalheight}{}
84 \define@key{igraph}{keepaspectratio}{}
85 \define@key{igraph}{clip}{}
86 \define@key{igraph}{draft}{}
87 \define@key{igraph}{type}{}
88 \define@key{igraph}{ext}{}
89 \define@key{igraph}{read}{}
90 \define@key{igraph}{command}{}
```

```
\LWR@rotstyle {<prefix>} {<degrees>}
```

Prints the rotate style with the given prefix.

`prefix` is `-ms-` or `-webkit-` or nothing, and is used to generate three versions of the `transform:rotate` style.

```
91 \newcommand*{\LWR@rotstyle}[2]{%
92 #1transform:rotate(-#2deg);%
93 }
```

```
\LWR@scalestyle {<prefix>} {<xscale>} {<yscale>}
```

Prints the scale style with the given prefix.

prefix is `-ms-` or `-webkit-` or nothing, and is used to generate three versions of the `transform:scale` style.

```
94 \newcommand*{\LWR@scalestyle}[3]{%
95 #1transform:scale(#2,#3);%
96 }
```

### § 146.3 `\includegraphics`

Bool `LWR@infloatrow` Used to compute `\linewidth`.

```
97 \newbool{LWR@infloatrow}%
98 \boolfalse{LWR@infloatrow}
```

`\LWR@opacity` may be set by the `transparent` package. For HTML it is only used for `\includegraphics`.

```
99 \def\LWR@opacity{1}
```

```
\LWR@includegraphicsb * [<2: options>] [<3: options>] {<4: filename>}%
graphics syntax is \includegraphics * [<llx, lly>] [<urx, ury>] {<file>}%
graphicx syntax is \includegraphics [<key values>] {<file>}
```

If #3 is empty, only one optional argument was given, thus graphicx syntax.

```
100 \NewDocumentCommand{\LWR@includegraphicsb}{s o o m}%
101 {%
102 \LWR@traceinfo{\LWR@includegraphicsb #4}%

```

Start the image tag on a new line, allow PDF output word wrap:

```
103 \LWR@origtilde \LWR@orignewline%
```

Temporarily compute `\ linewidth`, `\ textwidth`, `\ textheight` arguments with a 6x9 inch size until the next `\endgroup`.

```
104 \ifthenelse{\cnttest{\value{LWR@minipagedepth}}{=}{0}}{%
105 {%
106   \ifbool{LWR@infloatrow}{%
107     {}%
108     {%
109       \setlength{\linewidth}{6in}%
110       \setlength{\textwidth}{6in}%
111       \setlength{\textheight}{9in}%
112     }%
113 }{}}
```

```

114 \renewcommand*{\Gin@setfile}[3]{%
115 \LWR@traceinfo{Gin@setfile ##3}%
116 \xdef\LWR@parsedfilename{##3}%
117 }%
118 \Ginclusion@graphics{\detokenize{#4}}%
119 \filename@parse{\LWR@parsedfilename}%

```

For correct em sizing during the width and height conversions:

```
120 \large%
```

Reset some defaults, possibly will be changed below if options were given:

```

121 \setlength{\LWR@igwidth}{0pt}%
122 \setlength{\LWR@igheight}{0pt}%
123 \renewcommand*{\LWR@igwidthstyle}{}%
124 \renewcommand*{\LWR@igheightstyle}{}%
125 \renewcommand*{\LWR@igorigin}{}%
126 \renewcommand*{\LWR@igangle}{}%
127 \renewcommand*{\LWR@igxscale}{1}%
128 \renewcommand*{\LWR@igyscale}{1}%
129 \renewcommand*{\LWR@igclass}{inlineimage}%

```

If #3 is empty, only one optional argument was given, thus graphicx syntax:

```

130 \IfValueF{#3}{%
131 \IfValueTF{#2}{%
132 {\setkeys{igraph}{#2}}%
133 {\setkeys{igraph}{}}
134 }%

```

Create the HTML reference with the graphicspath, filename, extension, alt tag, style, and class.

The \LWR@origtilde adds space between tags in case this is being done inside a \savebox where \newline has no effect.

```

135 \LWR@traceinfo{LWR@includegraphicsb: about to create href}%
136 \href{\LWR@parsedfilename}%
137 {%
138 \LWR@traceinfo{LWR@includegraphicsb: about to LWR@htmlltag}%
139 \LWR@htmlltag{%
140 img src="\LWR@parsedfilename" \LWR@orignewline%
141 \LWR@origtilde{} alt="[\filename@base]" \LWR@orignewline%

```

Only include a style tag if a width, height, angle, or scale was given:

```
142 \ifthenelse{
```

```

143   \NOT\equal{\LWR@igwidthstyle}{} \OR
144   \NOT\equal{\LWR@igheightstyle}{} \OR
145   \NOT\equal{\LWR@igorigin}{} \OR
146   \NOT\equal{\LWR@igangle}{} \OR
147   \NOT\equal{\LWR@igxscale}{1} \OR
148   \NOT\equal{\LWR@igyscale}{1}
149 }%
150 {\LWR@origtilde{} style="%"
151 \ifthenelse{\NOT\equal{\LWR@igwidthstyle}{} }{%
152 {\LWR@igwidthstyle;}}{%
153 \ifthenelse{\NOT\equal{\LWR@igheightstyle}{} }{%
154 {\LWR@igheightstyle;}}{%
155 \ifthenelse{\NOT\equal{\LWR@igorigin}{} }{%
156 {\LWR@origtilde{} transform-origin: \LWR@originnames{\LWR@igorigin}; \LWR@orignewline;} }{%
157 \ifthenelse{\NOT\equal{\LWR@igangle}{} }{%
158 {%
159 \LWR@rotstyle{-ms-}{\LWR@igangle}%
160 \LWR@rotstyle{-webkit-}{\LWR@igangle}%
161 \LWR@rotstyle{}{\LWR@igangle}%
162 }}{%
163 \ifthenelse{\NOT\equal{\LWR@igxscale}{1}\OR%}
164 \NOT\equal{\LWR@igyscale}{1}}{%
165 {\LWR@scalestyle{-ms-}{\LWR@igxscale}{\LWR@igyscale}}%
166 {\LWR@scalestyle{-webkit-}{\LWR@igxscale}{\LWR@igyscale}}%
167 {\LWR@scalestyle{}{\LWR@igxscale}{\LWR@igyscale}}}{}%
168 }%
169 \ifthenelse{\NOT\equal{\LWR@opacity}{1}}{%
170 {\opacity:\LWR@opacity;}}{%
171 }}{%
172 }%
173 " \LWR@orignewline}{}%

```

Set the class:

```

174 \LWR@origtilde{} class="\LWR@igclass" \LWR@orignewline%
175 }% end of image tags
176 }% end of href
177 \endgroup

```

Return to small-sized output:

```

178 \LWR@origscriptsize
179 \LWR@traceinfo{\LWR@includegraphicsb done}%
180 }

```

`\includegraphics [⟨key=val⟩] {⟨filename⟩}`

Handles width and height, converted to fixed width and heights.

Converts any .pdf references to .svg for HTML

The user should always refer to .pdf in the document source.

```
181 \LetLtxMacro{\LWR@origin}{\includegraphics{}}
```

```
182
```

```
183 \AtBeginDocument{
```

```
184 \renewcommand*{\includegraphics}{%
```

This graphic should trigger an HTML paragraph even if alone, so ensure that are doing paragraph handling:

```
186 \LWR@traceinfo{\includegraphics}
```

```
187 \LWR@ensuredoingapar%
```

```
188 \begingroup%
```

```
189 \catcode`\_=12%
```

```
190 \LWR@includegraphicsb%
```

```
191 }% includegraphics
```

```
192 }% AtBeginDocument
```

\LWR@rotboxorigin Holds the origin key letters.

```
193 \newcommand*{\LWR@rotboxorigin}{}%
```

\LWR@originname {<letter>}

Given one L<sup>A</sup>T<sub>E</sub>X origin key value, translate into an HTML origin word:

```
194 \newcommand*{\LWR@originname}[1]{%
```

```
195 \ifthenelse{\equal{#1}{t}}{top}{}%
```

```
196 \ifthenelse{\equal{#1}{b}}{bottom}{}%
```

```
197 \ifthenelse{\equal{#1}{c}}{center}{}%
```

```
198 \ifthenelse{\equal{#1}{l}}{left}{}%
```

```
199 \ifthenelse{\equal{#1}{r}}{right}{}%
```

```
200 }
```

\LWR@originnames {<letters>}

Given one- or two-letter L<sup>A</sup>T<sub>E</sub>X origin key values, translate into HTML origin words:

```
201 \newcommand*{\LWR@originnames}[1]{%
```

```
202 \StrChar{#1}{1}[\LWR@strresult]%
```

```
203 \LWR@originname{\LWR@strresult}
```

```
204 \StrChar{#1}{2}[\LWR@strresult]%
```

```
205 \LWR@originname{\LWR@strresult}
```

```
206 }
```

Handle the origin key for \rotatebox:

```
207 \define@key{krotbox}{origin}{%
208 \renewcommand*\{LWR@rotboxorigin}{#1}%
209 }
```

These keys are ignored:

```
210 \define@key{krotbox}{x}{}
211 \define@key{krotbox}{y}{}
212 \define@key{krotbox}{units}{}
```

```
\rotatebox [⟨keyval list⟩] {⟨angle⟩} {⟨text⟩}

213 \LetLtxMacro\LWR@origrotatebox\rotatebox
214
215 \AtBeginDocument{
216 \RenewDocumentCommand{\rotatebox}{O{} m +m}{%
```

Reset the origin to “none-given”:

```
217 \renewcommand*\{LWR@rotboxorigin}{}
```

Process the optional keys, which may set \LWR@rotateboxorigin:

```
218 \setkeys{krotbox}{#1}%
```

Select inline-block so that HTML will transform this span:

```
219 \LWR@htmlltagc{span style="display: inline-block; %
```

If an origin was given, translate and print the origin information:

```
220 \ifthenelse{\NOT\equal{\LWR@rotboxorigin}{}}{%
221 {transform-origin: \LWR@originnames{\LWR@rotboxorigin};\LWR@origtilde}{}}{}
```

Print the rotation information:

```
222 \LWR@rotstyle{-ms-}{#2} %
223 \LWR@rotstyle{-webkit-}{#2} %
224 \LWR@rotstyle{}{#2} %
225 "{}"\LWR@orignewline%
```

Print the text to be rotated:

```
226 \begin{LWR@nestspan}%
227 #3%
```

Close the span:

```
228 \LWR@htmltagc{/span}%
229 \end{LWR@nestspan}%
230 }%
231 }% AtBeginDocument
```

\scalebox {⟨h-scale⟩} [⟨v-scale⟩] {⟨text⟩}

```
232 \LetLtxMacro{\LWR@origscalebox}{\scalebox}
233
234 \AtBeginDocument{
235 \RenewDocumentCommand{\scalebox}{m o m}{%
```

Select inline-block so that HTML will transform this span:

```
236 \LWR@htmltagc{span style="display: inline-block; "%
```

Print the scaling information:

```
237 \LWR@scalestyle{-ms-}{#1}{\IfNoValueTF{#2}{#1}{#2}} %
238 \LWR@scalestyle{-webkit-}{#1}{\IfNoValueTF{#2}{#1}{#2}} %
239 \LWR@scalestyle{}{#1}{\IfNoValueTF{#2}{#1}{#2}} %
240 "{}"}%
```

Print the text to be scaled:

```
241 \begin{LWR@nestspan}%
242 #3%
```

Close the span:

```
243 \LWR@htmltagc{/span}%
244 \end{LWR@nestspan}%
245 }%
246 }% AtBeginDocument
```

\reflectbox {⟨text⟩}

```
247 \let\LWR@origreflectbox{\reflectbox}
248
249 \AtBeginDocument{
250 \renewcommand{\reflectbox}[1]{\scalebox{-1}{[1]{#1}}}
251 }
```

\resizebox {⟨h-length⟩} {⟨v-length⟩} {⟨text⟩}

Simply prints its text argument.

```
252 \LetLtxMacro{\LWR@origresizebox}{\resizebox}
253
254 \AtBeginDocument{
255 \renewcommand{\resizebox}[3]{#3}
256 }
```

---

#### File 71 lwarf-graphicx.sty

### § 147 Package **graphicx**

Pkg **graphicx** **graphicx** is emulated.

**graphicx** loads **graphics**, which also loads **lwarf-graphics**, which remembers the original **graphics** definitions for use inside a **lateximage**, and then patches them **\AtBeginDocument** for **HTML** output.

**lwarf-graphics** handles the syntax of either **graphics** or **graphicx**.

**for HTML output:** 1 \LWR@ProvidesPackagePass{graphicx}

---

#### File 72 lwarf-grffile.sty

### § 148 Package **grffile**

Pkg **grffile** **grffile** is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each **PDF** image for print mode should be accompanied by an **SVG**, **PNG**, or **JPG** version for **HTML**.

**lwarf-grffile** now exists as a placeholder since **grffile** used to be emulated by **lwarf**, and thus older versions of **lwarf-grffile** may exist and should be overwritten by this newer version.

**for HTML output:** 1 \LWR@ProvidesPackagePass{grffile}

---

#### File 73 lwarf-hyperref.sty

### § 149 Package **hyperref**

Pkg **hyperref** **hyperref** is emulated during **HTML** output, and the **hyperref** package is ignored.

**for HTML output:**

```

1 % \LWR@ProvidesPackageDrop{hyperref}
2 \typeout{Using the lwarf html version of package 'hyperref' -- discarding options.}
3 \typeout{    Are not using ProvidesPackage, so that other packages}
4 \typeout{    do not attempt to patch lwarf's version of 'hyperref'.}
5 % \ProvidesPackage{lwarf-#1-#2}
6 \DeclareOption*{}
7 \ProcessOptions\relax

8 \newcommand*\hypersetup[1]{}
9 \newcommand*\hyperbaseurl[1]{}

\hyperimage  {\langle url \rangle} {\langle alt text \rangle}
Insert an image with alt text:

10 \NewDocumentCommand{\hyperimageb}{m +m}{%
11 \LWR@htmlltag{img src="#1" alt="#2" class="hyperimage"}{}%
12 \endgroup%
13 \LWR@ensuredoingapar%
14 }
15
16 \newcommand{\hyperimage}{%
17 \LWR@ensuredoingapar%
18 \begingroup\catcode`\_=12
19 \LWR@hyperimageb%
20 }

\hyperdef   {\langle 1: category \rangle} {\langle 2: name \rangle} {\langle 3: text \rangle}
Creates an HTML anchor to category.name with the given text.

21 \NewDocumentCommand{\hyperdef}{m m +m}{%
22 \LWR@ensuredoingapar%
23 \LWR@subsublabel{\#1.\#2}%
24 #3%
25 }

\LWR@hyperrefb {\langle I: URL \rangle} {\langle 2: category \rangle} {\langle 3: name \rangle} {\langle 4: text \rangle}
Creates an HTML link to URL#category.name with the given text.

26 \NewDocumentCommand{\hyperrefb}{m m m +m}{%
27 \LWR@htmlltag{a href="#1\LWR@hashmark#2.#3"}%
28 #4%
29 \LWR@htmlltag{/a}%
30 \endgroup%
31 }

\LWR@hyperrefc  [\langle label \rangle] {\langle text \rangle}

```

Creates text as an HTML link to the L<sup>A</sup>T<sub>E</sub>X label.

```
32 \NewDocumentCommand{\LWR@hyperrefc}{O{label} +m}{
33 \LWR@startref{#1}%
34 #2%
35 \LWR@htmltag{/a}%
36 \endgroup%
37 }
```

\hyperref {⟨1: URL⟩} {⟨2: category⟩} {⟨3: name⟩} {⟨4: text⟩} — or —  
[⟨1: label⟩] {⟨2: text⟩}

```
38 \newcommand{\hyperref}{%
39 \LWR@ensuredoingapar%
40 \begingroup\catcode`\_=12%
41 \@ifnextchar[\LWR@hyperrefc\LWR@hyperrefb%
42 }
```

\hypertarget {⟨name⟩} {⟨text⟩}

Creates an anchor to name with the given text.

```
43 \NewDocumentCommand{\hypertarget}{m +m}%
44 \label{#1}%
45 #2%
46 }
```

\hyperlink {⟨name⟩} {⟨text⟩}

Creates a link to the anchor created by hypertarget, with the given link text.

```
47 \NewDocumentCommand{\hyperlink}{s m +m}%
48 \hyperref[#1]{#2}%
49 }
```

\autoref \* {⟨label⟩}

For HTML, \cleveref is used instead.

```
50 \NewDocumentCommand{\autoref}{s m}%
51 \IfBooleanTF{#1}{\ref{#2}}{\cref{#2}}%
52 }
```

\autopageref {⟨label⟩}

For HTML, \cleveref is used instead.

```
53 \NewDocumentCommand{\autopageref}{s m}%
54 \IfBooleanTF{#1}{\pageref{#2}}{\cref{#2}}%
55 }
```

```
\pdfstringdef  {\langle macroname\rangle} {\langle TEXstring\rangle}
56 \newcommand{\pdfstringdef}[2]{}

\pdfbookmark [{\langle level\rangle}] {\langle text\rangle} {\langle name\rangle}
57 \newcommand{\pdfbookmark}[3][]{}

\currentpdfbookmark {\langle text\rangle} {\langle name\rangle}
58 \newcommand{\currentpdfbookmark}[2][]{}

\subpdfbookmark {\langle text\rangle} {\langle name\rangle}
59 \newcommand{\subpdfbookmark}[2][]{}

\belowpdfbookmark {\langle text\rangle} {\langle name\rangle}
60 \newcommand{\belowpdfbookmark}[2][]{}

\texorpdfstring {\langle TEXstring\rangle} {\langle PDFstring\rangle}
61 \newcommand{\texorpdfstring}[2]{#2}

\hypercalcbp {\langle dimen\rangle} From hyperref.
62 \def\hypercalcbp#1{%
63 \strip@pt\dimexpr 0.99626401\dimexpr#1\relax\relax
64 }%

\Acrobatmenu {\langle menuoption\rangle} {\langle text\rangle}
65 \newcommand{\Acrobatmenu}[2][]{}

\TextField [{\langle parameters\rangle}] {\langle label\rangle}
66 \newcommand*\TextField[2][]{}

\CheckBox [{\langle parameters\rangle}] {\langle label\rangle}
67 \newcommand*\CheckBox[2][]{}

\ChoiceMenu [{\langle parameters\rangle}] {\langle label\rangle} {\langle choices\rangle}
68 \newcommand{\ChoiceMenu}[3][]{}
```

```
\PushButton  [{parameters}]{label}  
69 \newcommand*{\PushButton}[2][]{}  
  
\Submit    [{parameters}]{label}  
70 \newcommand*{\Submit}[2][]{}  
  
\Reset    [{parameters}]{label}  
71 \newcommand*{\Reset}[2][]{}  
  
\LayoutTextField  {label} {field}  
72 \newcommand*{\LayoutTextField}[2]{}  
  
\LayoutChoiceField {label} {field}  
73 \newcommand*{\LayoutChoiceField}[2]{}  
  
\LayoutCheckField {label} {field}  
74 \newcommand*{\LayoutCheckField}[2]{}  
  
\MakeRadioField {width} {height}  
75 \newcommand*{\MakeRadioField}[2]{}  
  
\MakeCheckField {width} {height}  
76 \newcommand*{\MakeCheckField}[2]{}  
  
\MakeTextField {width} {height}  
77 \newcommand*{\MakeTextField}[2]{}  
  
\MakeChoiceField {width} {height}  
78 \newcommand*{\MakeChoiceField}[2]{}  
  
\MakeFieldButton {text}  
79 \newcommand{\MakeFieldButton}[1]{}  

```

---

File 74 **lwarf-hyperxmp.sty**

§ 150 Package **hyperxmp**

Pkg **hyperxmp** Emulated.

**for HTML output:** Discard all options for lwarf-hyperxmp:

```
1 \LWR@ProvidesPackageDrop{hyperxmp}
```

---

File 75 **lwarf-idxlayout.sty**

§ 151 Package **idxlayout**

Pkg **idxlayout** Emulated.

**for HTML output:** Discard all options for lwarf-idxlayout:

```
1 \LWR@ProvidesPackageDrop{idxlayout}

2 \newcommand{\LWR@indexprenote}{{}}
3
4 \renewcommand*{\printindex}{}
5 {
6 \LWR@startpars
7
8 \LWR@indexprenote
9
10 \LWR@origprintindex
11 }
12
13 \newcommand{\setindexprenote}[1]{\renewcommand{\LWR@indexprenote}{#1}}
14 \newcommand*{\noindexprenote}{\renewcommand{\LWR@indexprenote}{}}
15
16 \newcommand{\idxlayout}[1]{}
17 \newcommand*{\indexfont}{{}}
18 \newcommand*{\indexjustific}{{}}
19 \newcommand*{\indexsubsdelim}{{}}
20 \newcommand*{\indexstheadcase}{{}}
```

---

File 76 **l warp-indentfirst.sty**

§ 152 Package **indentfirst**

Pkg indentfirst indentfirst is ignored.

Discard all options for l warp-indentfirst:

for HTML output: 1 \LWR@ProvidesPackageDrop{indentfirst}

---

File 77 **l warp-inputenc.sty**

§ 153 Package **inputenc**

Pkg inputenc Error if inputenc is loaded after l warp.

Discard all options for l warp-inputenc:

for HTML output: 1 \LWR@ProvidesPackageDrop{inputenc}

2 \LWR@loadbefore{inputenc}

---

File 78 **l warp-keyfloat.sty**

§ 154 Package **keyfloat**

Pkg keyfloat keyfloat is supported with minor adjustments.

for HTML output: 1 \LWR@ProvidesPackagePass{keyfloat}

After keyfloat has loaded:

2 \AtBeginDocument{  
3 \let\KFLT@boxinner\relax  
4 \let\endKFLT@boxinner\relax  
5  
6 \NewEnviron{KFLT@boxinner}  
7 {%

```
8 \LWR@traceinfo{kflt@boxinner}%
9 \LWR@stopars%
10 \KFLT@frame{\BODY}%
11 \LWR@startpars%
12 \LWR@traceinfo{ended kflt@boxinner}%
13 }

14 \DeclareDocumentEnvironment{KFLT@marginfloat}{O{-1.2ex} m}
15 {%
16   \LWR@maybeinthisfloat%
17   \LWR@forcenewpage%
18   \LWR@stopars%
19   \LWR@htmlltag{div class="marginblock" id="autofloat-\arabic{LWR@thisfloat}"}%
20   \LWR@startpars%
21   \captionsetup{type=#2}%
22 }
23 {
24   \LWR@htmldivclassend{div}
25 }

26 \DeclareDocumentEnvironment{marginfigure}{o}
27   {\begin{KFLT@marginfloat}{figure}}
28   {\end{KFLT@marginfloat}}
29
30 \DeclareDocumentEnvironment{margintable}{o}
31   {\begin{KFLT@marginfloat}{table}}
32   {\end{KFLT@marginfloat}}

33 \DeclareDocumentEnvironment{keywrap}{m +m}
34 {%
35   \begin{BlockClass}{marginblock}
36   \setlength{\linewidth}{#1}
37 #2%
38   \end{BlockClass}
39 }
40 {%
41 }

42 }% AtBeginDocument
```

---

File 79 lwarf-layout.sty

§ 155      Package **layout**

Pkg layout layout is ignored.

**for HTML output:** Discard all options for l warp-layout:

```
1 \LWR@ProvidesPackageDrop{layout}
2 \NewDocumentCommand{\layout}{s}{}

---


```

File 80 **l warp-letterspace.sty**

§ 156 Package **letterspace**

Pkg **letterspace** letterspace is a subset of microtype, which is pre-loaded by l warp. All user options and macros are ignored and disabled.

**for HTML output:** Discard all options for l warp-letterspace:

```
1 \LWR@ProvidesPackageDrop{letterspace}
2 \newcommand*\lsstyle{}
3 \newcommand\textls[2][]{}
4 \def\textls#1#2{#1\textlsstyle{#2}}
5 \newcommand*\lslig[1]{\textls{#1}}

---


```

File 81 **l warp-lettrine.sty**

§ 157 Package **lettrine**

(Based on original code by DANIEL FLIPO.)

Pkg **lettrine** Emulated.

**for HTML output:** Discard all options for l warp-lettrine:

```
1 \LWR@ProvidesPackageDrop{lettrine}
```

The initial letter is in a <span> of class lettrine, and the following text is in a <span> of class lettrinetext. \lettrine [<keys>] {<letter>} {<additional text>}

```
2 \DeclareDocumentCommand{\lettrine}{o m m}{%
3   \InlineClass{lettrine}{#2}\InlineClass{lettrinetext}{#3} %
4 }
5
6 \newcounter{DefaultLines}
7 \setcounter{DefaultLines}{2}
8 \newcounter{DefaultDepth}
```

---

```

9 \newcommand*{\DefaultOptionsFile}{\relax}
10 \newcommand*{\DefaultLoversize}{0}
11 \newcommand*{\DefaultLraise}{0}
12 \newcommand*{\DefaultLhang}{0}
13 \newdimen\DefaultFindent
14 \setlength{\DefaultFindent}{\z@}
15 \newdimen\DefaultNindent
16 \setlength{\DefaultNindent}{0.5em}
17 \newdimen\DefaultSlope
18 \setlength{\DefaultSlope}{\z@}
19 \newdimen\DiscardVskip
20 \setlength{\DiscardVskip}{0.2\p@}
21 \newif\ifLettrineImage
22 \newif\ifLettrineOnGrid
23 \newif\ifLettrineRealHeight
24
25 \newcommand*{\LettrineTextFont}{\scshape}
26 \newcommand*{\LettrineFontHook}{}
27 \newcommand*{\LettrineFont}[1]{\InlineClass{lettrine}{#1}}
28 \newcommand*{\LettrineFontEPS}[1]{\includegraphics[height=1.5ex]{#1}}

```

---

File 82 **l warp-lips.sty**

§ 158 Package **lips**

Pkg lips lips is emulated during HTML output, and the lips package is ignored.

```

1 % \LWR@ProvidesPackageDrop{lips}
2 \PackageInfo{l warp}{Using the l warp version of package 'lips'.}%
3 \ProvidesPackage{l warp-lips}
4
5 \NewDocumentCommand{\Lips}{}{\textellipsis}
6
7 \NewDocumentCommand{\BracketedLips}{}{[\textellipsis]}
8
9 \let\lips\Lips
10 \let\olips\lips
11
12 \DeclareOption*{}
13 \DeclareOption{mla}{%
14 \let\lips\BracketedLips
15 }
16 \ProcessOptions\relax
17
18 \newcommand \LPNobreakList {}

```

---

File 83 **lwarp-listings.sty**

§ 159 Package **listings**

*(Based on original code by CARSTEN HEINZ, BROOKS MOSES, JOBST HOFFMANN.)*

Pkg **listings** **listings** is supported with some limitations. Text formatting is not yet supported.

**for HTML output:** 1 \begin{warpHTML}

2 \LWR@ProvidesPackagePass{listings}

Patches to embed listings inside pre tags:

```
3 \let\LWR@origlst@Init\lst@Init
4 \let\LWR@origlst@DeInit\lst@DeInit
5
6 \let\LWR@origlst@EveryPar\lst@EveryPar
7
8 \renewcommand{\l@lstlisting}[2]{\hypertocfloat{1}{lstlisting}{lol}{#1}{#2}}
```

\lst@Init {*backslash-processing*} Done at the start of a listing.

9 \renewcommand{\lst@Init}[1]{%

First, perform the listings initialization:

```
10 \LWR@traceinfo{lst@Init}%
11 \renewcommand*{@captype}{lstlisting}%
12 \LWR@origlst@Init{#1}%
13 \LWR@traceinfo{finished origlst@Init}%
14 \lst@ifdisplaystyle%
```

Creating a display.

Disable line numbers, produce the <pre>, then reenable line numbers.

```
15 \LWR@traceinfo{About to create verbatim.}%
16 \let\lst@EveryPar\relax%
17 \LWR@forcenewpage
18 \LWR@atbeginverbatim{programlisting}%
19
20 \let\lst@EveryPar\LWR@origlst@EveryPar%
21 \else%
```

Inline, so open a <span>:

---

```

22 \ifbool{LWR@verbtags}{\LWR@htmltag{span class="inlineprogramlisting"}{}}{%
23 \fi%
24 }

```

\lst@DeInit     Done at the end of a listing.

```

25 \renewcommand*{\lst@DeInit}{%
26 \lst@ifdisplaystyle%

```

Creating a display.

Disable line numbers, produce the </pre>, then reenable line numbers:

```

27 \let\lsthk@EveryPar\relax%
28
29 \LWR@afterendverbatim%
30 \let\lsthk@EveryPar\LWR@origlsthkEveryPar%
31 \else%

```

Inline, so create the closing </span>:

```

32 \ifbool{LWR@verbtags}{\noindent\LWR@htmltag{/span}{}}{%
33 \fi%

```

Final listings deinit:

```

34 \LWR@origlst@DeInit%
35 }

```

\lst@MakeCaption     {\it{(t/b)}}

This is called BOTH at the top and at the bottom of each listing.

Patched for lwarp.

```

36 \def\lst@MakeCaption#1{%
37 \LWR@traceinfo{MAKING CAPTION at #1}%
38 \lst@ifdisplaystyle%
39 \LWR@traceinfo{making a listings display caption}%
40 \ifx #1t%
41 \ifx\lst@@caption\empty\expandafter\lst@HRefStepCounter \else
42 \expandafter\refstepcounter%
43 \fi {\lstlisting}%
44 \LWR@traceinfo{About to assign label: !\lst@label!}%
45 \ifx\lst@label\empty\else
46 \label{\lst@label}\fi
47 \LWR@traceinfo{Finished assigning the label.}%
48 \let\lst@arg\lst@intname \lst@ReplaceIn\lst@arg\lst@filenamerpl
49 \global\let\lst@name\lst@arg \global\let\lstname\lst@name
50 \lst@ifnolol\else
51 \ifx\lst@@caption\empty
52 \ifx\lst@caption\empty
53 \ifx\lst@intname\empty \else \def\lst@temp{ }%
54 \ifx\lst@intname\lst@temp \else

```

This code places a contents entry for a non-float. This would have to be modified for lwarp:

```

55 \LWR@traceinfo{addcontents lst@name: -\lst@name-}%
56 %                                \addcontentsline{loll}{\lst@name}%
57         \fi\fi
58     \fi
59     \else

```

This would have to be modified for lwarp:

```

60 \LWR@traceinfo{addcontents lst@@caption: -\lst@@caption-}%
61             \addcontentsline{loll}{\lstlisting}%
62 {\protect\numberline{\thelstlisting}%
63 {\protect\ignorespaces \lst@@caption \protect\relax}}%
64         \fi
65     \fi
66     \fi
67     \ifx\lst@caption\@empty\else
68 \LWR@traceinfo{\lst@caption not empty-}%
69     \lst@ifSubstring #1\lst@captionpos
70     {\begin{group}
71 \LWR@traceinfo{at the selected position}%

```

These space and box commands are not needed for HTML output:

```

72 %          \let@\vskip\vskip
73 %          \def\vskip{\afterassignment\lst@vskip \tempskipa}%
74 %          \def\lst@vskip{\nobreak\@vskip\tempskipa\nobreak}%
75 %          \par\@parboxrestore\normalsize\normalfont \% \noindent (AS)
76 %          \ifx #1\allowbreak \fi
77          \ifx\lst@title\@empty

```

New lwarp code to create a caption:

```

78          \lst@makecaption\fnam@lstlisting{\ignorespaces \lst@caption}%
79      \else

```

New lwarp code to create a title:

```

80 %          \lst@maketitle\lst@title \% (AS)
81 \LWR@traceinfo{Making title: \lst@title}%
82 \begin{BlockClass}{\lstlistingtitle}\% lwarp
83 \lst@maketitle\lst@title\% lwarp
84 \end{BlockClass}\% lwarp
85         \fi
86 \LWR@traceinfo{About to assign label: !\lst@label!}%
87     \ifx\lst@label\@empty\else
88 \leavevmode% gets rid of bad space factor error
89 \GetTitleStringExpand{\lst@caption}%
90 \edef\LWR@lntemp{\GetTitleStringResult}%
91 \edef@\currentlabelname{\detokenize\expandafter{\LWR@lntemp}}%
92 \label{\lst@label}\fi
93 \LWR@traceinfo{Finished assigning the label.}%

```

Not needed for lwarp:

```

94 %           \ifx #1b\allowbreak \fi
95   \endgroup{}%
96   \fi
97 \LWR@traceinfo{end of making a listings display caption}%
98 \else
99 \LWR@traceinfo{INLINE}%
100 \fi
101 \LWR@traceinfo{DONE WITH CAPTION at #1}%
102 }
```

Patched to keep left line numbers outside of the left margin, and place right line numbers in a field \VerbatimHTMLWidth wide.

```

103 \lst@Key{numbers}{none}{%
104   \let\lst@PlaceNumber\empty
105   \lstKV@SwitchCases{#1}{%
106     {none}&\%
107     left&\def\lst@PlaceNumber{%
108 \% \llap{%
109 \LWR@orignormalfont%
110 \lst@numberstyle{\the\lstnumber}\kern\lst@numbersep%
111 \% }%
112 }%
113 \\%
114   right&\def\lst@PlaceNumber{\rlap{\LWR@orignormalfont%
115             \kern\VerbatimHTMLWidth \kern\lst@numbersep%
116             \lst@numberstyle{\the\lstnumber}}}}%
117 }{\PackageError{Listings}{Numbers #1 unknown}@ehc}%
118 \end{warpHTML}
```

File 84 **lwarp-longtable.sty**

## § 160 Package **longtable**

Pkg **longtable** longtable is emulated during HTML output, and the longtable package is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop[longtable]

 Longtable \endhead, \endfoot, and \endlastfoot rows are not used for HTML, and these rows should be disabled. Use

\warpprintonly{row contents}

instead of

---

```
\begin{warpprint} ... \end{warpprint}
```

Doing so helps avoid “Misplaced `\noalign`.” when using `\begin{warpprint}`.

Keep the `\endfirsthead` row, which is still relevant to HTML output.



`\kill` is ignored, place a `\kill` line inside

```
\begin{warpprint} ... \end{warpprint}
```

or place it inside `\warpingprintonly`.

See:

<http://tex.stackexchange.com/questions/43006/why-is-input-not-expandable>

Env `longtable` \* [*horizontalignment*] {*colspec*} Emulates the `longtable` environment.

Per the `caption` package, the starred version steps the counter per caption. The unstarred version steps the counter once at the beginning, but not at each caption.

Options [c], [l], and [r] are thrown away.

```

2 \newenvironment{longtable*}[2] []{%
3 \LWR@floatbegin{table}%
4 \setcaptiontype{\LTcaptype}%
5 \caption@setoptions{longtable}%
6 \caption@setoptions{@longtable}%
7 \caption@LT@setup%
8 \booltrue{\LWR@starredlongtable}%
9 \let\captionlistentry{\LWR@LTcaptionlistentry}%
10 \LWR@tabular{#2}%
11 }%
12 {\endLWR@tabular\endLWR@floatend}%
13 %
14 \newenvironment{longtable}[2] []{%
15 \LWR@floatbegin{table}%
16 \setcaptiontype{\LTcaptype}%
17 \caption@setoptions{longtable}%
18 \caption@setoptions{@longtable}%
19 \caption@LT@setup%
20 \refstepcounter{\LTcaptype}%
21 \let\captionlistentry{\LWR@LTcaptionlistentry}%
22 \LWR@tabular{#2}%
23 }%
24 {\endLWR@tabular\endLWR@floatend}%
25 
```

Provided for compatibility, but ignored:

```

26 \newcounter{LTchunksize}
27 \def\endhead{\LWR@tabularendofline}% throws away options // [dim] and /**
28 \def\endfirsthead{\LWR@tabularendofline}
29 \def\endfoot{\LWR@tabularendofline}
30 \def\endlastfoot{\LWR@tabularendofline}
31 \newcommand\tabularnewline{\LWR@tabularendofline}
32 \newcommand{\setlongtables}{}% Obsolete command, does nothing.
33 \newlength{\LTleft}
34 \newlength{\LTright}
35 \newlength{\LTpre}
36 \newlength{\LTpost}
37 \newlength{\LTcapwidth}

38 \renewcommand*{\kill}{\LWR@tabularendofline}

```

---

#### File 85 l warp-lscape.sty

### § 161 Package **lscape**

Pkg lscape lscape is nullified.

**for HTML output:** Discard all options for l warp-lscape.

```

1 \LWR@ProvidesPackageDrop{lscape}

2 \newenvironment*[landscape]{}{}

```

---

#### File 86 l warp-ltcaption.sty

### § 162 Package **ltcaption**

Pkg ltcaption ltcaption is emulated during HTML output, and the ltcaption package is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{ltcaption}

\LTcaptype is already defined by l warp.

longtable\* is already defined by l warp-longtable.

```

2 \newlength{\LTcapskip}
3 \newlength{\LTcapleft}
4 \newlength{\LTcapright}

```

```
5 \newcommand*{\LTcapmarginsfalse}{}{}
```

---

File 87 **l warp-marginfit.sty**

§ 163 Package **marginfit**

Pkg **marginfit** Emulated.

**for HTML output:** Discard all options for l warp-marginfit:

```
1 \LWR@ProvidesPackageDrop{marginfit}
```

---

File 88 **l warp-marginfix.sty**

§ 164 Package **marginfix**

Pkg **marginfix** Emulated.

**for HTML output:** Discard all options for l warp-marginfix:

```
1 \LWR@ProvidesPackageDrop{marginfix}
```

```
2 \newcommand*{\marginskip}[1]{}{}
3 \newcommand*{\clearmargin}{}{}
4 \newcommand*{\softclearmargin}{}{}
5 \newcommand*{\extendmargin}[1]{}{}
6 \newcommand*{\mparshift}[1]{}{}
7 \newdimen\marginheightadjustment
8 \newdimen\marginposadjustment
9 \newcommand*{\blockmargin}[1]{}{}{}
10 \newcommand*{\unblockmargin}[1]{}{}{}
11 \newcommand*{\marginphantom}[2]{}{}{}
```

---

File 89 **l warp-marginnote.sty**

§ 165 Package **marginnote**

Pkg **marginnote** Emulated.

**for HTML output:** Discard all options for l warp-marginnote:

```
1 \LWR@ProvidesPackageDrop{marginnote}
```

---

```

2 \NewDocumentCommand{\marginnote}{o +m o}{\marginpar{#2}}
3 \newcommand*{\marginnoteleftadjust}={}
4 \newcommand*{\marginnoterightadjust}={}
5 \newcommand*{\marginnotetextwidth}={}
6 \let\marginnotetextwidth\textwidth
7 \newcommand*{\marginnotevadjust}={}
8 \newcommand*{\marginfont}={}
9 \newcommand*{\raggedleftmarginnote}={}
10 \newcommand*{\raggedrightmarginnote}{}

```

---

File 90 **lwarp-mcaption.sty**

§ 166 Package **mcaption**

Pkg **mcaption** **mcaption** is nullified.

**for HTML output:** Discard all options for **lwarp-mcaption**:

```

1 \LWR@ProvidesPackageDrop{mcaption}

2 \newenvironment{margincap}{}{}
3 \newcommand*{\margincapalign}{}
4 \newlength{\margincapsep}

```

---

File 91 **lwarp-mdframed.sty**

§ 167 Package **mdframed**

Pkg **mdframed** **mdframed** is loaded with options forced to **framemethod=none**.

**for HTML output:**
 1 \RequirePackage{xcolor}%
 2 \LWR@ProvidesPackageDrop{mdframed}

**support** Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for **mdframed** environments and frame titles.

**⚠ loading** When used, **lwarp** loads **mdframed** in **HTML** with **framemethod=none**.

**font** For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where `\textbf` must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the `mdframed` source). Since `lwarf` does not support `\bfseries` and friends, only one font selection may be made at a time.

**theoremtitlefont** `theoremtitlefont` is not supported, since the following text is not in braces in the `mdframed` source.

**footnotes** Footnotes are currently placed at the bottom of the HTML page.

**ignored options** `userdefinedwidth` and `align` are currently ignored.

**CSS classes** Environments created or encapsulated by `mdframed` are enclosed in a `<div>` of class `md<environmentname>`, or `mdframed` otherwise.

Frame titles are placed into a `<span>` of class `mdframedtitle`. Subtitles are in a `<span>` of class `mdframedsubtitle`, and likewise for subsubtitles.

Pre-existing hooks are used to patch extra functions before and after the frames.

`amsthm` must be loaded before `mdframed`

```
3 \LWR@origRequirePackage{amsthm}
```

Do not require `Tikz` or `pstricks`:

```
4 \LWR@origRequirePackage[framemethod=none]{mdframed}
```

To handle CSS and paragraphs, patch code at start and end of environment and contents. `\LWR@origraggedright` helps avoid hyphenation.

```
5 \mdfsetup{
6 startcode={\LWR@mdframedstart\LWR@origraggedright},
7 endcode={\LWR@mdframedend},
8 startinnercode={\LWR@startpars\LWR@origraggedright},
9 endinnercode={\LWR@stoppars},
10 }
```

`\LWR@mdfprintcolor` `\{<mdcolorkey>\}`

Given the `mdframed` key, print the color.

```
11 \newcommand*{\LWR@mdfprintcolor}[1]{%
12 \convertcolorspec[named]{\csuse{mdf@\#1}}{HTML}\LWR@tempcolor%
13 \#\LWR@tempcolor
```

14 }

\LWR@mdfprintlength {*mdflengthkey*}

Given the mdframed key, print the length.

```
15 \newcommand*{\LWR@mdfprintlength}[1]{%
16 \rndprintlength{\csuse{mdf@#1@length}}%
17 }
```

\LWR@mdframedstart Actions before an mdframe starts.

Encapsulate a frame inside a <div> of the desired class.

```
18 \newcommand*{\LWR@mdframedstart}{%
```

Turn off paragraph handling during the generation of the encapsulating tags:

```
19 \LWR@stopars%
```

Below, print HTML pt units:

```
20 \uselengthunit{PT}%
```

Open a <div> and with custom class and custom style:

```
21 \LWR@htmtagc{div class="\LWR@mdthisenv" \LWR@orignewline%
22 style=" \LWR@orignewline
```

Convert and print the background color:

```
23 background: \LWR@mdfprintcolor{backgroundcolor} ; \LWR@orignewline
```

Convert and print the border color and width:

```
24 border: \LWR@mdfprintlength{linewidth} solid%
25 \LWR@mdfprintcolor{linecolor} ; \LWR@orignewline
```

Convert and print the border radius:

```
26 border-radius: \LWR@mdfprintlength{roundcorner} ; \LWR@orignewline
```

Convert and print the shadow:

```
27 \ifbool{mdf@shadow}{%
28   box-shadow:
29   \LWR@mdfprintlength{shadowsize}
30   \LWR@mdfprintlength{shadowsize}
31   \LWR@mdfprintlength{shadowsize}
32   \LWR@mdfprintcolor{shadowcolor} ;
33 }
34 {box-shadow: none ;}
35 \LWR@orignewline
36 "}
37 % \LWR@htmldivclass{\LWR@mdthisenv}
```

`mdframed` environment may not work with the HTML versions of the following, so restore them to their originals while inside `mdframed`:

```
38 \LetLtxMacro{\hspace}{\LWR@orighspace}%
39 \LetLtxMacro{\rule}{\LWR@origrule}%
40 \LetLtxMacro{\makebox}{\LWR@origmakebox}%
41 }
```

`\LWR@mdframedend` Actions after an mdframe ends.

After closing the `<div>`, globally restore to the default environment type:

```
42 \newcommand*{\LWR@mdframedend}{
```

Close the custom `<div>`:

```
43 \LWR@htmldivclassend{\LWR@mdthisenv}
```

Reset future custom class to the default:

```
44 \gdef\LWR@mdthisenv{mdframed}
```

Resume paragraph handling:

```
45 \LWR@startpars%
46 }
```

`\mdfframedtitleenv {<title>}`

Encapsulation of the original which places the title inside a `<span>` of class `mdframedtitle`:

```
47 \LetLtxMacro{\LWR@origmdfframedtitleenv}{\mdfframedtitleenv}
48
49 \newlength{\LWR@titleroundcorner}
50
51 \renewrobustcmd{\mdfframedtitleenv[1]}{%
52 \LWR@origmdfframedtitleenv{%
```

Below, print HTML pt lengths:

```
53 \uselengthunit{PT}%
```

Open a `<span>` with a custom class and custom style:

```
54 \LWR@htmllagc{span class="mdframedtitle" \LWR@orignewline
55 style=" \LWR@orignewline
```

Convert and print the title background color:

```
56 background:
57 \LWR@mdfprintcolor{frametitlebackgroundcolor}
58 ; \LWR@orignewline
```

Convert and print the title rule:

```
59 \ifbool{mdf@frametitlerule}{%
60   border-bottom:
```

```

61      \LWR@mdfprintlength{frametitlerulewidth}
62      solid
63      \LWR@mdfprintcolor{frametitlerulecolor}
64      ; \LWR@orignewline
65 }{}%

```

The title's top border radius is adjusted for the line width:

```

66 border-radius:
67 \setlength{\LWR@titleroundcorner}
68   {\maxof{\mdf@roundcorner@length-\mdf@linewidth@length}{0pt}}
69   \rndprintlength{\LWR@titleroundcorner}
70   \rndprintlength{\LWR@titleroundcorner}
71   0pt 0pt
72   \LWR@orignewline

```

Finish the custom style and the opening span tag:

```

73 " \LWR@orignewline
74 }% span

```

Restrict paragraph tags inside a span:

```
75 \begin{\LWR@nestspan}%
```

Print the title inside the span:

```
76 #1%
```

Cloosee the span and unnest the paragraph tag restriction:

```

77 \LWR@htmtagc{/span}%
78 \end{\LWR@nestspan}%
79 }
80 }

```

\LWR@mdfsubtitlecommon {*sub -or- subsub*} [*options*] {*title*}

Common code for \LWR@mdfsubtitle and \LWR@mdfsubsubtitle.

Encapsulate the subtitle inside a <span> of class mdframedsubtitle:

```

81 \NewDocumentCommand{\LWR@mdfsubtitlecommon}{m o m}
82 {%
83   the following empty line is required
84 }

```

Special handling for mdframed: Subtitles have \pars around them, so temporarily disable them here.

```
84 \let\par\LWR@origpar%
```

Open a <span> with a custom class and custom style:

```

85 \LWR@htmtagc{span class="mdframed#1title"
86 style=" \LWR@orignewline

```

Convert and print the background color:

```
87 background:
88 \LWR@mdfprintcolor{#1titlebackgroundcolor}
89 ; \LWR@orignewline
```

Convert and print the above line:

```
90 \ifbool{mdf@#1titleaboveline}{%
91   border-top:
92   \LWR@mdfprintlength{#1titleabovelinewidth}
93   solid
94   \LWR@mdfprintcolor{#1titleabovelinecolor}
95   ; \LWR@orignewline
96 }{}}
```

Convert and print the below line:

```
97 \ifbool{mdf@#1titlebelowline}{%
98   border-bottom:
99   \LWR@mdfprintlength{#1titlebelowlinewidth}
100  solid
101  \LWR@mdfprintcolor{#1titlebelowlinecolor}
102  ; \LWR@orignewline
103 }{}}
```

Finish the custom style and the opening span tag:

```
104 "}% span
```

Restrict paragraph tags inside a span:

```
105 \begin{[LWR@nestspan]}
```

Perform the original subtitle action:

```
106 \IfNoValueTF{#2}
107 {\csuse{LWR@origmdf#1title}{#3}}
108 {\csuse{LWR@origmdf#1title}[#2]{#3}}
```

Close the span and unnest the paragraph tag restriction:

```
109 \LWR@htmlltagc{/span}%
110 the following empty line is required
111 \end{[LWR@nestspan]}%
112 }
```

```
\LWR@mdfsubtitle  [<options>] {<title>}
113 \let\LWR@origmdfsubtitle\mdfsubtitle
114
115 \newcommand*{\LWR@mdfsubtitle}{%
116 \LWR@mdfsubtitlecommon{sub}}
117 }
118 \let\mdfsubtitle\LWR@mdfsubtitle
```

```
\LWR@mdfsubsubtitle  [<options>] {<title>}
119 \let\LWR@origmdfsubsubtitle\mdfsubsubtitle
120
121 \newcommand*\LWR@mdfsubsubtitle{%
122 \LWR@mdfsubtitlecommon{subsub}%
123 }
124 \let\mdfsubsubtitle\LWR@mdfsubsubtitle
```

\LWR@mdthisenv Stores the environment of the frame about to be created:

```
125 \newcommand*\LWR@mdthisenv{mdframed}
```

\newmdenv [<options>] {<env-name>}

Modified from the original to remember the environment.

```
126 \renewrobustcmd*\newmdenv[2] []{%
127 \newenvironment{#2}%
128 {%
129 \mdfsetup{#1}%
130 \renewcommand*\LWR@mdthisenv{md#2}%
131 \begin{mdframed}%
132 }
133 {\end{mdframed}}%
134 }
```

\surroundwithmdframed [<options>] {<environment>}

Modified from the original to remember the environment.

```
135 \renewrobustcmd*\surroundwithmdframed[2] []{%
136 \BeforeBeginEnvironment{#2}{%
137 \renewcommand*\LWR@mdthisenv{md#2}%
138 \begin{mdframed}[#1]}%
139 \AfterEndEnvironment{#2}{\end{mdframed}}%
140 }
```

\mdtheorem [<mdframed-options>] envname [<numberedlike>] {<caption>} [<within>]

Modified from the original to remember the environment.

```
141 \DeclareDocumentCommand{\mdtheorem}{ O{} m o m o }{%
142 {\ifcsdef{#2}{%
143 {\mdf@PackageWarning{Environment #2 already exists\MessageBreak}}%
144 {%
145 \IfNoValueTF{#3}{%
146 {#3 not given -- number relationship}%
147 \IfNoValueTF{#5}{%
148 {#3+#5 not given}}
```

```
149      \@definecounter{#2}%
150      \expandafter\xdef\csname the#2\endcsname{\@thmcounter{#2}}%
151      \newenvironment{#2}[1][]{%
152          \refstepcounter{#2}%
153          \ifstrempty{##1}%
154              {\let\@temptitle\relax}%
155              {%
156                  \def\@temptitle{\mdf@theoremseparator}%
157                  \mdf@theoremspace%
158                  \mdf@theoremtitlefont%
159                  ##1}%
160                  \mdf@thm@caption{#2}{\#4}{\csname the#2\endcsname}{##1}}%
161              }%
162          \begin{mdframed}[#1,frametitle={\strut\#4\ \csname the#2\endcsname}%
163                           \@temptitle}]%%
164          \end{mdframed}%
165          \newenvironment{#2*}[1][]{%
166              \ifstrempty{##1}{\let\@temptitle\relax}{\def\@temptitle{: \ ##1}}%
167              \begin{mdframed}[#1,frametitle={\strut\#4\@temptitle}]%%
168              \end{mdframed}%
169          }%
170          {##5 given -- reset counter
171          \@definecounter{#2}\@newctr{#2}[\#5]%
172          \expandafter\xdef\csname the#2\endcsname{\@thmcounter{#2}}%
173          \expandafter\xdef\csname the#2\endcsname{%
174              \expandafter\noexpand\csname the#5\endcsname \@thmcountersep%
175              \atthmcounter{#2}}%
176          \newenvironment{#2}[1][]{%
177              \refstepcounter{#2}%
178              \ifstrempty{##1}%
179                  {\let\@temptitle\relax}%
180                  {%
181                      \def\@temptitle{\mdf@theoremseparator}%
182                      \mdf@theoremspace%
183                      \mdf@theoremtitlefont%
184                      ##1}%
185                      \mdf@thm@caption{#2}{\#4}{\csname the#2\endcsname}{##1}}%
186                  }%
187          \begin{mdframed}[#1,frametitle={\strut\#4\ \csname the#2\endcsname}%
188                           \atthmcounter{#2}]%%
189          \end{mdframed}%
190          \newenvironment{#2*}[1][]{%
191              \ifstrempty{##1}%
192                  {\let\@temptitle\relax}%
193                  {%
194                      \def\@temptitle{\mdf@theoremseparator}%
195                      \mdf@theoremspace%
196                      \mdf@theoremtitlefont%
197                      ##1}%
198                      \mdf@thm@caption{#2}{\#4}{\csname the#2\endcsname}{##1}}%
```

```

199      }%
200      \begin{mdframed}[\#1,frametitle={\strut#4\@temptitle}]}%
201      \end{mdframed}}%
202  }%
203 }%
204 {%% given -- number relationship
205   \global\@namedef{the#2}{\cnameuse{the#3}}%
206   \newenvironment{#2}[1][]{%
207     \refstepcounter{#3}%
208     \ifstrempty{##1}%
209       {\let\@temptitle\relax}%
210     {%
211       \def\@temptitle{\mdf@theoremseparator}%
212         \mdf@theoremspace%
213         \mdf@theoremtitlefont%
214         ##1}%
215       \mdf@thm@caption{#2}{\#4}{\csname the#2\endcsname{##1}}%
216     }%
217     \begin{mdframed}[\#1,frametitle={\strut#4\ \csname the#2\endcsname\%
218                                     \@temptitle}]}%
219     \end{mdframed}}%
220   \newenvironment{#2*}[1][]{%
221     \ifstrempty{##1}{\let\@temptitle\relax}{\def\@temptitle{: \ ##1}}%
222     \begin{mdframed}[\#1,frametitle={\strut#4\@temptitle}]}%
223     \end{mdframed}}%
224 }%
225 \BeforeBeginEnvironment{#2}{\renewcommand*{\LWR@mdthisenv}{md#2}}% new
226 \BeforeBeginEnvironment{#2*}{\renewcommand*{\LWR@mdthisenv}{md#2}}% new
227 }%
228 }

```

\newmdtheoremenv [⟨mdframed-options⟩] envname [⟨numberedlike⟩] {⟨caption⟩} [⟨within⟩]

Modified from the original to remember the environment.

```

229 \DeclareDocumentCommand\newmdtheoremenv{O{} m o m o }{%
230   \ifboolexpr{ test {\IfNoValueTF {#3}} and test {\IfNoValueTF {#5}} }{%
231     {\newtheorem{#2}{#4}}%
232     {%
233       \IfValueT{#3}{\newtheorem{#2}[#3]{#4}}%
234       \IfValueT{#5}{\newtheorem{#2}{#4}[#5]}%
235     }%
236   \BeforeBeginEnvironment{#2}{%
237     \renewcommand*{\LWR@mdthisenv}{md#2}%
238     \begin{mdframed}[\#1]}%
239   \AfterEndEnvironment{#2}{%
240     \end{mdframed}}%
241 }

```

---

File 92 **l warp-metalogo.sty**

§ 168 Package **metalogo**

Pkg **metalogo** metalogo is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{metalogo}

2 \newcommand\setlogokern[2]{}
3 \newcommand\setlogodrop[2][XeTeX]{}
4 \newcommand\setLaTeXa[1]{}
5 \newcommand\setLaTeXe[1]{}
6 \newcommand\seteverylogo[1]{}
7 \newcommand\everylogo[1]{}
```

---

File 93 **l warp-microtype.sty**

§ 169 Package **microtype**

Pkg **microtype** microtype is pre-loaded by l warp. All user options and macros are ignored and disabled.

**for HTML output:** Discard all options for l warp-microtype:

```
1 \LWR@ProvidesPackageDrop{microtype}

2 \DeclareDocumentCommand{\DeclareMicrotypeSet}{o m m}{}
3 \DeclareDocumentCommand{\UseMicrotypeSet}{o m}{}
4 \DeclareDocumentCommand{\DeclareMicrotypeSetDefault}{o m}{}
5 \DeclareDocumentCommand{\SetProtrusion}{o m m}{}
6 \DeclareDocumentCommand{\SetExpansion}{o m m}{}
7 \DeclareDocumentCommand{\SetTracking}{o m m}{}
8 \DeclareDocumentCommand{\SetExtraKerning}{o m m}{}
9 \DeclareDocumentCommand{\SetExtraSpacing}{o m m}{}
10 \DeclareDocumentCommand{\DisableLigatures}{o m}{}
11 \DeclareDocumentCommand{\DeclareCharacterInheritance}{o m m}{}
12 \DeclareDocumentCommand{\DeclareMicrotypeVariants}{m}{f}
13 \DeclareDocumentCommand{\DeclareMicrotypeAlias}{m m}{}
14 \DeclareDocumentCommand{\LoadMicrotypeFile}{m}{}
15 \DeclareDocumentCommand{\DeclareMicrotypeBabelHook}{m m}{}
16 \DeclareDocumentCommand{\microtypesetup}{m}{}
17 \DeclareDocumentCommand{\microtypecontext}{m}{}
```

---

```

18 \DeclareDocumentCommand{\textmicrotypecontext}{m m}{#2}
19 \@ifpackageloaded{letterspace}{\let\MT@textls\relax}{%
20 \DeclareDocumentCommand{\lsstyle}{}{}}
21 \DeclareDocumentCommand{\textls}{o +m}{}
22 \DeclareDocumentCommand{\lslig}{m}{#1}
23 }
24 \def\DeclareMicrotypeSet#1{\gobbletwo}
25 \def\DeclareMicrotypeVariants#1{\gobbleone}
26 \onlypreamble\DeclareMicrotypeSet
27 \onlypreamble\UseMicrotypeSet
28 \onlypreamble\DeclareMicrotypeSetDefault
29 \onlypreamble\DisableLigatures
30 \onlypreamble\DeclareMicrotypeVariants
31 \onlypreamble\DeclareMicrotypeBabelHook

```

---

File 94 **l warp-midfloat.sty**

§ 170 Package **midfloat**

Pkg **midfloat** midfloat is emulated.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{midfloat}

2 \newenvironment{strip}[1][]{\{}{\}}
3 \newskip\stripsep

```

File 95 **l warp-moreverb.sty**

§ 171 Package **moreverb**

Pkg **moreverb** moreverb is supported with some patches.

**for HTML output:**

```

1 \begin{warpHTML}

2 \LWR@ProvidesPackagePass{moreverb}

3 \BeforeBeginEnvironment{verbatimtab}{%
4 \LWR@forcenewpage
5 \LWR@atbeginverbatim{Verbatim}\unskip\LWR@origvspace*{-\baselineskip}%
6 }
7 \AfterEndEnvironment{verbatimtab}{%
8 \LWR@afterendverbatim%
9 }

```

```
10
11
12 \LetLtxMacro{\LWRMV@orig@verbatimtabinput}{\verb+@+verbatimtabinput}
13
14 \renewcommand{\@verbatimtabinput}[2][]{%
15   \LWR@forcenewpage
16   \LWR@atbeginverbatim{Verbatim}\unskip\LWR@origvspace*{-\baselineskip}%
17   \LWRMV@orig@verbatimtabinput[#1]{#2}%
18   \LWR@afterendverbatim%
19 }
20
21 \BeforeBeginEnvironment{listing}{%
22   \LWR@forcenewpage
23   \LWR@atbeginverbatim{programlisting}\unskip\LWR@origvspace*{-\baselineskip}%
24 }
25
26 \AfterEndEnvironment{listing}{%
27   \unskip\LWR@origvspace*{-\baselineskip}%
28   \LWR@afterendverbatim%
29 }
30
31 \BeforeBeginEnvironment{listingcont}{%
32   \LWR@forcenewpage
33   \LWR@atbeginverbatim{programlisting}\unskip\LWR@origvspace*{-\baselineskip}%
34 }
35
36 \AfterEndEnvironment{listingcont}{%
37   \unskip\LWR@origvspace*{-\baselineskip}%
38   \LWR@afterendverbatim%
39 }
40
41 \renewcommand{\listinglabel}[1]{\InlineClass{listinglabel}{\the#1}}
42
43 \def\thelisting@line{%
44   \tempcnta=\listing@line%
45   \divide\tempcnta\listing@step \multiply\tempcnta\listing@step%
46   \ifnum\listing@line=\@ne%
47     \listinglabel\listing@line%
48   \else%
49     \ifnum\tempcnta=\listing@line%
50       \listinglabel\listing@line%
51     \else%
52       \InlineClass{listinglabel}{}%
53     \fi%
54   \fi%
55 }
56 \LetLtxMacro{\LWRMV@listinginput}{\@listinginput}
57
58 \renewcommand{\@listinginput}[3][]{%
59   \LWR@forcenewpage
```

---

```

60 \LWR@atbeginverbatim{programlisting}\unskip\LWR@origvspace*{-\baselineskip}%
61 \LWRMVA@listinginput[#1]{#2}{#3}
62 \LWR@afterendverbatim%
63 }
64
65
66 \renewenvironment*{boxedverbatim}
67 {
68 \LWR@forcenewpage
69 \LWR@atbeginverbatim{boxedverbatim}\unskip\LWR@origvspace*{-\baselineskip}%
70 \verbatim%
71 }
72 {
73 \endverbatim%
74 \LWR@afterendverbatim%
75 }
76
77

78 \end{warpHTML}

```

---

File 96 **lwarf-mparhack.sty**

§ 172 Package **mparhack**

Pkg **mparhack** Emulated.

**for HTML output:** Discard all options for lwarf-mparhack:

```
1 \LWR@ProvidesPackageDrop{mparhack}
```

---

File 97 **lwarf-multicol.sty**

§ 173 Package **multicol**

Pkg **multicol** multicol is emulated during HTML output, and the multicol package is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{multicol}[2015/09/13]

Multicols are converted into a 1–3 column display, browser-supported.

The optional multicols heading is placed inside a <div> of class `multicolsheading`.

The content is placed inside a <div> of class `multicols`.

---

```

2 \begin{warpHTML}

Env  multicol  * {\<numcols>} [<heading>]
3 \NewDocumentEnvironment{multicol}{s m o}
HTML <div> class to contain everything:
4 {
5 \LWR@forcenewpage
6 \BlockClass{multicol}

Optional HTML <div> class for the heading:
7 \IfValueT{#3}{\begin{BlockClass}{multicolheading}#3\end{BlockClass}}}

When done with the environment, close the <div>:
8 {\endBlockClass}

Emulated null functions which are not used in HTML:

9 \newcommand*{\columnbreak} {}
10 \newcommand*{\RLmulticolcolumns} {}
11 \newcommand*{\LRmulticolcolumns} {}
12
13 \newlength{\premulticols}
14 \newlength{\postmulticols}
15 \newlength{\multicolssep}
16 \newlength{\multicolbaselineskip}
17 \newlength{\multicoltolerance}
18 \newlength{\multicolpretolerance}
19 \newcommand*{\columnseprulecolor}{\normalcolor}
20 \newcounter{columnbadness}
21 \newcounter{finalcolumnbadness}
22 \newcounter{collectmore}
23 \newcounter{unbalance}
24 \newlength{\multicolovershoot}
25 \newlength{\multicolundershoot}

26 \end{warpHTML}

```

---

File 98 **lwarp-multirow.sty**

§ 174 Package **multirow**

Pkg **multirow** multirow is emulated during HTML output, and used as-is while inside a `\textrimage`.

In a `\teximage`, the original print-mode versions are temporarily restored by `\LWR@restoreorigformatting`.

See section 58.18 for the print-mode versions.

**for HTML output:** 1 `\LWR@ProvidesPackagePass{multirow}`

Remember the print-mode version:

2 `\LetLtxMacro{\LWR@origmultirow}{\multirow}`

`\LWR@multirowborder` Set to `left` or `right` to create a thick border for the cell, for use by `bigdelim`:

3 `\newcommand{\LWR@multirowborder}{}%`

#### § 174.1 Multirow

```
\multirow  [\langle vpos \rangle] {\langle numrows \rangle} [\langle bigstruts \rangle] {\langle width \rangle} [\langle fixup \rangle] {\langle text \rangle}

4 \RenewDocumentCommand{\multirow}{O{c} m o m o +m}%
5 {%
6 \LWR@traceinfo{*** multirow #1 #2 #4}%
7 \LWR@maybenewtablerow%
8 \LWR@tabularleftedge%
```

Print the start of a new table data cell:

9 `\LWR@htmlltag{td rowspan="#2" %`

The vertical alignment, if given:

```
10 \IfValueT{\#1}{%
11 \ifstreq{\#1}{b}{\style="vertical-align:bottom" }{}%
12 \ifstreq{\#1}{t}{\style="vertical-align:top" }{}%
13 }%
```

The left/right border, if given:

```
14 \ifdefvoid{\LWR@multirowborder}{}{%
15 style="border-\LWR@multirowborder: 2px dotted black ; %
16 padding-\LWR@multirowborder: 2px" %
17 }%
```

A class adds the column spec and the rule:

18 `class="td%"`

Append this column's spec:

```
19 \StrChar{\LWR@tablecols}{\theLWR@tablecolspos}%
```

If this column has a cmidrule, add “rule” to the end of the HTML class tag. Also add the vertical bar class.

```
20 \LWR@addcmidruletrim%
21 \LWR@addleftmostbartag%
22 \LWR@printbartag{\theLWR@tablecolspos}%
23 "%
24 \LWR@addcmidrulewidth%
25 }%
```

The column's < spec:

```
26 \LWR@getexparray{\LWR@colbeforespec}{\theLWR@tablecolspos}%
```

While printing the text, redefine \\ to generate a new line

```
27 \begingroup\LetLtxMacro{\{}{\LWR@endofline}#6\endgroup%
28 \LWR@stoppars%
29 \global\boolfalse{\LWR@intabularmetadata}%
30 \renewcommand{\LWR@multirowborder}{}%
31 \LWR@traceinfo{*** multirow done}%
32 }%
```

## § 174.2 Combined multicolumn and multirow

**⚠ \multicolumn & \multirow** l warp does not support directly combining `\multicolumn` and `\multirow`. Use `\multicolumnrow` instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}
```

The two arguments for `\multicolumn` come first, followed by the five arguments for `\multirow`, many of which are optional, followed by the contents.

- ⚠ skipped cells** As per `\multirow`, skipped cells to the right of the `\multicolumnrow` statement are not included in the source code on the same line. On the following lines, `\mcolrowcell` must be used for each cell of each column and each row to be skipped:
- ⚠ empty cells**

```
... & \multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text} & ...
... & \mcolrowcell & \mcolrowcell & ...
... & \mcolrowcell & \mcolrowcell & ...
```

**vposn** Note that recent versions of `multirow` include a new optional `vposn` argument.

```
\multicolumnrow {\{1:cols\}} {\{2:halign\}} [\{3:vpos\}] {\{4:numrows\}} [\{5:bigstruts\}] {\{6:width\}} [\{7:fixup\}]
{\{8:text\}}
```

33 `\NewDocumentCommand{\multicolumnrow}{m m 0{} m 0{} m 0{} +m}{%`

Figure out how many extra HTML columns to add for @ and ! columns:

34 `\LWR@tabularhtmlcolumns{\theLWR@tablecolspos}{#1}`

Create the multicolumn/multirow tag:

35 `\begingroup\LetLtxMacro{\}{\LWR@endofline}%`  
 36 `\LWR@domulticolumn[#3][#4]{\theLWR@tabhtmlcoltotal}{#2}{#8}%`  
 37 `\endgroup%`

Move to the next L<sup>T</sup>E<sub>X</sub> column:

38 `\addtocounter{LWR@tablecolspos}{#1}%`  
 39 `\addtocounter{LWR@tablecolspos}{-1}%`

Skip any trailing @ or ! columns for this cell:

40 `\booltrue{LWR@skipatbang}%`  
 41 `}`

```
42 \appto{\LWR@restoreorigformatting}{%
43 \LetLtxMacro\multirow{\LWR@origmultirow}%
44 \renewcommand{\multicolumnrow}{\LWR@origmulticolumnrow}%
45 }
```

---

File 99 **l warp-nameref.sty**

§ 175 Package **nameref**

Pkg **nameref** nameref is emulated by l warp.

**for HTML output:** Discard all options for l warp-nameref:

```
1 \typeout{Using the l warp html version of package 'nameref' -- discarding options.}
2 \typeout{    Are not using ProvidesPackage, so that other packages}
3 \typeout{    do not attempt to patch l warp's version of 'nameref'.}
4 \DeclareOption*{}
5 \ProcessOptions\relax
```

---

File 100 **l warp-needspace.sty**

§ 176 Package **needspace**

Pkg **needspace** needspace is not used during HTML conversion.

**for HTML output:** Discard all options for l warp-needspace:

```
1 \LWR@ProvidesPackageDrop{needspace}
2
3 \newcommand*{\needspace}[1]{}
4 \DeclareDocumentCommand{\Needspace}{s m}{}  


---


```

File 101 **l warp-newclude.sty**

§ 177 Package **newclude**

Pkg **newclude** Error if newclude is loaded after l warp.

**for HTML output:** Discard all options for l warp-newclude:

```
1 \LWR@ProvidesPackageDrop{newclude}
```

```
2 \LWR@loadbefore{newclude}
```

---

File 102 **l warp-newunicodechar.sty**

§ 178      Package **newunicodechar**

Pkg **newunicodechar** Error if **newunicodechar** is loaded after **l warp**.

Discard all options for **l warp-newunicodechar**:

**for HTML output:**    1 \LWR@ProvidesPackageDrop{newunicodechar}  
                      2 \LWR@loadbefore{newunicodechar}

---

File 103 **l warp-nextpage.sty**

§ 179      Package **nextpage**

Pkg **nextpage** **nextpage** is nullified.

**for HTML output:** Discard all options for **l warp-nextpage**.

```
1 \LWR@ProvidesPackageDrop{nextpage}  
  
2 \newcommand{\cleartoevenpage}[1] {}  
3 \newcommand{\movetoevenpage}[1] {}  
4 \newcommand{\cleartooddpage}[1] {}  
5 \newcommand{\movetooddpage}[1] {}
```

---

File 104 **l warp-nonumonpart.sty**

§ 180      Package **nonumonpart**

Pkg **nonumonpart** **nonumonpart** is ignored.

**for HTML output:**    1 \LWR@ProvidesPackageDrop{nonumonpart}

---

File 105 **lwarf-nopageno.sty**

§ 181 Package **nopageno**

Pkg **nopageno** **nopageno** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{nopageno}

---

File 106 **lwarf-nowidow.sty**

§ 182 Package **nowidow**

Pkg **nowidow** **nowidow** is not used during HTML conversion.

Discard all options for **lwarf-nowidow**:

**for HTML output:** 1 \LWR@ProvidesPackageDrop{nowidow}

```
\nowidow  [⟨lines⟩]
\setnowidow [⟨lines⟩]
            2 \newcommand*{\nowidow}[1] []
            3 \newcommand*{\setnowidow}[1] []

\noclub   [⟨lines⟩]
\setnoclub [⟨lines⟩]
            4 \newcommand*{\noclub}[1] []
            5 \newcommand*{\setnoclub}[1] []
```

---

File 107 **lwarf-ntheorem.sty**

§ 183 Package **ntheorem**

(Based on original code by WOLFGANG MAY, ANDREAS SCHEDLER.)

Pkg **ntheorem** **ntheorem** is patched for use by **lwarf**.

**CSS styling of theorems and proofs:**

**Theorem:** <div> of class theorembody<theoremstyle>

**Theorem Header:** <span> of class theoremheader<style>

where <theoremstyle> is plain, break, etc.

**⚠️ Font control** This conversion is not total. Font control is via css, and the custom L<sup>A</sup>T<sub>E</sub>X font settings are ignored.

**⚠️ Equation numbering** ntheorem has a bug with equation numbering in *AMS* environments when the option `thref` is used. lwarp does not share this bug, so equations with `\split`, etc, are numbered correctly with lwarp's HTML output, but not with the print output. It is recommended to use `cleveref` instead of ntheorem's `thref` option.

Options `amsthm` or `standard` choose which set of theorems and proofs to initialize.

**⚠️ Disabled options** The options `thmmarks` and `amsmath` are disabled, since they heavily modify the underlying math code. Theorem marks are emulated. The AMS-math modifications are not done.

Option `thref` is disabled because `cleveref` functions are used instead. `\thref` is emulated.

Option `hyperref` is disabled because lwarp emulated `hyperref`.

**for HTML output:** Some disabled options:

```

1 \DeclareOption{thref}{}  

2  

3  

4 \newbool{LWR@ntheoremmarks}  

5 \boolfalse{LWR@ntheoremmarks}  

6  

7 \DeclareOption{thmmarks} {  

8 \booltrue{LWR@ntheoremmarks}  

9 \newif\ifsetendmark\setendmarktrue  

10 }  

11  

12  

13 \newbool{LWR@ntheoremamsthm}  

14 \boolfalse{LWR@ntheoremamsthm}  

15  

16 \DeclareOption{amsthm}{\booltrue{LWR@ntheoremamsthm}}  

17  

18  

19 \DeclareOption{amsmath}{}  

20 \DeclareOption{hyperref}{}  

21  

22  

23 \LWR@ProvidesPackagePass{ntheorem}
```

Storage for the style being used for new theorems.

```
24 \newcommand{\LWR@newtheoremstyle}{plain}
```

Patched to remember the style being used for new theorems:

```
25 \gdef\theoremstyle#1{%
26   \@ifundefined{th@#1}{\@warning
27     {Unknown theoremstyle '#1'. Using 'plain'}%
28     \theorem@style{plain}
29     \renewcommand{\LWR@newtheoremstyle}{plain}%
30   }%
31   {
32     \theorem@style{#1}
33     \renewcommand{\LWR@newtheoremstyle}{#1}%
34   }
35 }
```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```
36
37 \gdef@\xnthm#1#2[#3]{%
38   \ifthm@tempif
39     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}%
40     \expandafter\@ifundefined{c@#1}%
41       {\@definecounter{#1}}{%
42         \newctr{#1}[#3]%
43         \expandafter\xdef\csname the#1\endcsname{%
44           \expandafter\noexpand\csname the#3\endcsname \thmcOUNTERsep
45             {\noexpand\csname the\the\theoremnumbering\endcsname{#1}}}%
46         \expandafter\gdef\csname mkheader@#1\endcsname
47           {\csname setparms@#1\endcsname
48             \thm{#1}{#1}{#2}
49           }%
50         \global\@namedef{end#1}{\endtheorem}
51         \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\csuse{LWR@thmstyle#1}}}%
52       \fi
53   }
54
55 \gdef@\ynthm#1#2{%
56   \ifthm@tempif
57     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}%
58     \expandafter\@ifundefined{c@#1}%
59       {\@definecounter{#1}}{%
60         \expandafter\xdef\csname the#1\endcsname
61           {\noexpand\csname the\the\theoremnumbering\endcsname{#1}}%
62         \expandafter\gdef\csname mkheader@#1\endcsname
63           {\csname setparms@#1\endcsname
```

```

64      \@thm{\#1}{\#1}{\#2}
65      }%
66      \global\@namedef{end#1}{\@endtheorem}
67      \AtBeginEnvironment{\#1}{\edef\LWR@thisthmstyle{\csuse{LWR@thmstyle#1}}}\% new
68  \fi
69 }
70
71 \gdef\@othm#1[#2]{%
72   \ifundefined{c@#2}{\nocounterr{#2}}{%
73     \ifthm@tempif
74       \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}\% new
75       \global\@namedef{the#1}{\nameuse{the#2}}%
76       \expandafter\protected\xdef\csname num@addtheoremline#1\endcsname{%
77         \noexpand\@num@addtheoremline{\#1}{\#3}}%
78       \expandafter\protected\xdef\csname nonum@addtheoremline#1\endcsname{%
79         \noexpand\@nonum@addtheoremline{\#1}{\#3}}%
80     \theoremkeyword{\#3}%
81     \expandafter\protected\xdef\csname #1Keyword\endcsname
82       {\the\theoremkeyword}%
83     \expandafter\gdef\csname mkheader@#1\endcsname
84       {\csname setparms@#1\endcsname
85         \@thm{\#1}{\#2}{\#3}}
86     }%
87   \global\@namedef{end#1}{\@endtheorem}
88   \AtBeginEnvironment{\#1}{\edef\LWR@thisthmstyle{\csuse{LWR@thmstyle#1}}}\% new
89 \fi
90 }

```

Mimics a float by incrementing the float counter and generating an HTML anchor. These are used for list-of-theorem cross-references.

```

91 \newcommand{\LWR@inctheorem}{%
92 \addtocounter{LWR@thisfloat}{1}}%
93 \LWR@stoppars%
94 \LWR@htmlltag{a id="autofloat-\arabic{LWR@thisfloat}"[]}\LWR@htmlltag{/a}%
95 \LWR@startpars%
96 }

```

The following are patched for css.

These were in individual files thp.sty for plain, thmb.sty for margin break, etc. They are gathered together here.

Each theorem is encased in a `BlockClass` environment of class `theorembody<style>`.

Each header is encased in an `\InlineClass` of class `theoremheader<style>`.

```

97 \gdef\newtheoremstyle#1#2#3{%
98   \expandafter\ifundefined{th@#1}{%
99     \expandafter\gdef\csname th@#1\endcsname{%

```

```
100      \def\@begintheorem####1####2{%
101 \LWR@forcenewpage% new
102 \BlockClass{theorembody#1}\LWR@thisthmstyle% new
103 \LWR@inctheorem% new
104 #2}%
105      \def\@opargbegintheorem####1####2####3{%
106 \LWR@forcenewpage% new
107 \BlockClass{theorembody#1}\LWR@thisthmstyle% new
108 \LWR@inctheorem% new
109 #3}%
110 }%
111 }%
112 {\PackageError{\basename}{Theorem style #1 already defined}\@eha}
113 }
114
115 \renewtheoremstyle{plain}%
116  {\item[\hspace{\labelsep} \theorem@headerfont
117    \InlineClass{theoremheaderplain}{##1\ ##2\theorem@separator}]}%
118  {\item[\hspace{\labelsep} \theorem@headerfont
119    \InlineClass{theoremheaderplain}{##1\ ##2\ (##3)\theorem@separator}]}
120
121 \renewtheoremstyle{break}%
122  {\item[
123 %  \rlap{\vbox{\hbox{
124    \hspace{\labelsep} \theorem@headerfont
125    \InlineClass{theoremheaderbreak}{##1\ ##2\theorem@separator}\newline
126 % } \hbox{\strut}}}}
127  ]}%
128  {\item[
129 %  \rlap{\vbox{\hbox{
130    \hspace{\labelsep} \theorem@headerfont
131    \InlineClass{theoremheaderbreak}{##1\ ##2\ (##3)\theorem@separator}\newline
132 % } \hbox{\strut}}}}
133  ]}%
134
135 \renewtheoremstyle{change}%
136  {\item[\hspace{\labelsep}
137    \theorem@headerfont
138    \InlineClass{theoremheaderchange}{##2\ ##1\theorem@separator}]}%
139  {\item[\hspace{\labelsep}
140    \theorem@headerfont
141    \InlineClass{theoremheaderchange}{##2\ ##1\ (##3)\theorem@separator}]}
142
143 \renewtheoremstyle{changebreak}%
144  {\item[
145 %  \rlap{\vbox{\hbox{
146    \hspace{\labelsep} \theorem@headerfont
147    \InlineClass{theoremheaderchangebreak}{##2\ ##1\theorem@separator}\newline
148 % } \hbox{\strut}}}}
149  ]}%
```

```
150  {\item[  
151 %  \rlap{\vbox{\hbox{  
152      \hskip\labelsep \theorem@headerfont  
153      \InlineClass{\theoremheaderchangebreak}{##2\ ##1\ (##3)\theorem@separator}\newline  
154 %  }\hbox{\strut}}}  
155  ]}  
156  
157 \renewtheoremstyle{margin}{  
158  {\item[\hskip\labelsep\theorem@headerfont  
159      \InlineClass{\theoremheadermargin}{##2 \qquad ##1\theorem@separator}  
160  ]}%  
161  {\item[\hskip\labelsep\theorem@headerfont  
162      \InlineClass{\theoremheadermargin}{##2 \qquad ##1\ (##3)\theorem@separator}  
163  ]}  
164  
165 \renewtheoremstyle{marginbreak}{  
166  {\item[\hskip\labelsep\theorem@headerfont  
167      \InlineClass{\theoremheadermarginbreak}{##2 \qquad ##1\theorem@separator}\newline  
168  ]}%  
169  {\item[\hskip\labelsep\theorem@headerfont  
170      \InlineClass{\theoremheadermarginbreak}{##2 \qquad ##1\ (##3)\theorem@separator}\newline  
171  ]}  
172  
173 \renewtheoremstyle{nonumberplain}{  
174  {\item[\theorem@headerfont\hskip\labelsep  
175      \InlineClass{\theoremheaderplain}{##1\theorem@separator}]}%  
176  {\item[\theorem@headerfont\hskip \labelsep  
177      \InlineClass{\theoremheaderplain}{##1\ (##3)\theorem@separator}}}  
178  
179 \renewtheoremstyle{nonumberbreak}{  
180  {\item[  
181 %  \rlap{\vbox{\hbox{  
182      \hskip\labelsep \theorem@headerfont  
183      \InlineClass{\theoremheaderbreak}{##1\theorem@separator}\newline  
184 %  }\hbox{\strut}}}  
185  ]}%  
186  {\item[  
187 %  \rlap{\vbox{\hbox{  
188      \hskip\labelsep \theorem@headerfont  
189      \InlineClass{\theoremheaderbreak}{##1\ (##3)\theorem@separator}\newline  
190 %  }\hbox{\strut}}}  
191  ]}  
192  
193 \renewtheoremstyle{empty}{  
194  {\item[]}}%  
195  {\item[\theorem@headerfont \hskip\labelsep\relax  
196      \InlineClass{\theoremheaderplain}{##3}]}  
197  
198 \renewtheoremstyle{emptybreak}{  
199  {\item[]}}%
```

```
200  {\item[\theoremlabelsep \relax
201    \InlineClass{theoremlabelplain}{##3}] \newline}
```

The following manually adjust the css for the standard configuration objects which are not a purely plain style:

```
202 \ifbool{LWR@ntheoremamsthm}{}{%
203 % upright text via CSS
204   \newtheoremstyle{plainupright}%
205   {\item[\theoremlabelsep \theoremlabelfont
206     \InlineClass{theoremlabelplain}{##1\ ##2\theoremseparator}]}%
207   {\item[\theoremlabelsep \theoremlabelfont
208     \InlineClass{theoremlabelplain}{##1\ ##2\ (#3)\theoremseparator}]}%
209
210 % upright text and small caps header via CSS
211   \newtheoremstyle{nonumberplainuprightsc}%
212   {\item[\theoremlabelfont\theoremlabelsep
213     \InlineClass{theoremlabelsc}{##1\theoremseparator}]}%
214   {\item[\theoremlabelfont\theoremlabelsep
215     \InlineClass{theoremlabelsc}{##1\ (#3)\theoremseparator}}}
```

The following standard configuration is renewed using the new css:

```
216 \theoremstyle{plainupright}
217 \theorembodyfont{\upshape}
218 \theoremsymbol{\HTMLUnicode{25A1}}% UTF-8 white box
219 \renewtheorem{Example}{Example}
220 \renewtheorem{example}{Example}
221 \renewtheorem{Beispiel}{Beispiel}
222 \renewtheorem{beispiel}{Beispiel}
223 \renewtheorem{Bemerkung}{Bemerkung}
224 \renewtheorem{bemerkung}{Bemerkung}
225 \renewtheorem{Anmerkung}{Anmerkung}
226 \renewtheorem{anmerkung}{Anmerkung}
227 \renewtheorem{Remark}{Remark}
228 \renewtheorem{remark}{Remark}
229 \renewtheorem{Definition}{Definition}
230 \renewtheorem{definition}{Definition}
231
232 \theoremstyle{nonumberplainuprightsc}
233 \theoremsymbol{\HTMLUnicode{220E}}% UTF-8 end-of-proof
234 \renewtheorem{Proof}{Proof}
235 \renewtheorem{proof}{Proof}
236 \renewtheorem{Beweis}{Beweis}
237 \renewtheorem{beweis}{Beweis}
238 \qedsymbol{\HTMLUnicode{220E}}% UTF-8 end-of-proof
239
240 \theoremsymbol{}
241 }% not amsthm
```

Only if the `amsthm` option was given:

```
242 \ifbool{LWR@ntheoremamsthm}{
243   \gdef\th@plain{%
244     \def\theorem@headerfont{\normalfont\bfseries}\itshape%
245     \def\@begintheorem##1##2{%
246       \LWR@forcenewpage% new
247       \BlockClass{\theorembodyplain}% new
248       \LWR@inctheorem% new
249       \item[\hspace{\labelsep}
250         \theorem@headerfont
251       ]}%
252     \InlineClass{\theoremheaderplain}{##1\ ##2.}%
253   }%
254   \def\@opargbegintheorem##1##2##3{%
255     \LWR@forcenewpage% new
256     \BlockClass{\theorembodyplain}% new
257     \LWR@inctheorem% new
258     \item[\hspace{\labelsep}
259       \theorem@headerfont
260       \InlineClass{\theoremheaderplain}{##1\ ##2\ (###3).}%
261     ]}%
262   \gdef\th@nonumberplain{%
263     \def\theorem@headerfont{\normalfont\bfseries}\itshape%
264     \def\@begintheorem##1##2{%
265       \LWR@forcenewpage% new
266       \BlockClass{\theorembodyplain}% new
267       \LWR@inctheorem% new
268       \item[\hspace{\labelsep}
269         \theorem@headerfont
270       ]}%
271     \InlineClass{\theoremheaderplain}{##1.}%
272   }%
273   \def\@opargbegintheorem##1##2##3{%
274     \LWR@forcenewpage% new
275     \BlockClass{\theorembodyplain}% new
276     \LWR@inctheorem% new
277     \item[\hspace{\labelsep}
278       \theorem@headerfont
279       \InlineClass{\theoremheaderplain}{##1\ (###3).}%
280     ]}%
281   \gdef\th@definition{%
282     \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
283     \def\@begintheorem##1##2{%
284       \LWR@forcenewpage% new
285       \BlockClass{\theorembodydefinition}% new
286       \LWR@inctheorem% new
287       \item[\hspace{\labelsep}
288         \theorem@headerfont
289       ]}%
290   }
```

```
290 \InlineClass{theoremheaderdefinition}{##1\ ##2.}
291     ]}%
292 \def\@opargbegintheorem##1##2##3{%
293 \LWR@forcenewpage% new
294     \BlockClass{theorembodydefinition}{% new
295     \LWR@inctheorem% new
296     \item[\hspace{\labelsep}
297 % \theorem@headerfont
298 \InlineClass{theoremheaderdefinition}{##1\ ##2\ (###3).}
299     ]}%
300
301 \gdef\th@nonumberdefinition{%
302 \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
303 \def\@begintheorem##1##2{%
304 \LWR@forcenewpage% new
305     \BlockClass{theorembodydefinition}{% new
306     \LWR@inctheorem% new
307     \item[\hspace{\labelsep}
308 % \theorem@headerfont
309 \InlineClass{theoremheaderdefinition}{##1.}
310     ]}%
311 \def\@opargbegintheorem##1##2##3{%
312 \LWR@forcenewpage% new
313     \BlockClass{theorembodydefinition}{% new
314     \LWR@inctheorem% new
315     \item[\hspace{\labelsep}
316 % \theorem@headerfont
317 \InlineClass{theoremheaderdefinition}{##1\ (###3).}
318     ]}%
319
320 \gdef\th@remark{%
321 \def\theorem@headerfont{\itshape}\normalfont%
322 \def\@begintheorem##1##2{%
323 \LWR@forcenewpage% new
324     \BlockClass{theorembodyremark}{% new
325     \LWR@inctheorem% new
326     \item[\hspace{\labelsep}
327 % \theorem@headerfont
328 \InlineClass{theoremheaderremark}{##1\ ##2.}
329     ]}%
330 \def\@opargbegintheorem##1##2##3{%
331 \LWR@forcenewpage% new
332     \BlockClass{theorembodyremark}{% new
333     \LWR@inctheorem% new
334     \item[\hspace{\labelsep}
335 % \theorem@headerfont
336 \InlineClass{theoremheaderremark}{##1\ ##2\ (###3).}
337     ]}%
338
339 \gdef\th@nonumberremark{%
```

```
340 \def\theorem@headerfont{\itshape}\normalfont%
341 \def\@begintheorem##1##2{%
342 \LWR@forcenewpage% new
343 \BlockClass{theorembodyremark}% new
344 \LWR@inctheorem% new
345 \item[\hspace{\labelsep}
346 % \theorem@headerfont
347 \InlineClass{theoremheaderremark}{##1.}%
348 ]}%
349 \def\@opargbegintheorem##1##2##3{%
350 \LWR@forcenewpage% new
351 \BlockClass{theorembodyremark}% new
352 \LWR@inctheorem% new
353 \item[\hspace{\labelsep}
354 % \theorem@headerfont
355 \InlineClass{theoremheaderremark}{##1\ (###3).}%
356 ]}%
357
358 \gdef\th@proof{%
359 \def\theorem@headerfont{\normalfont\bfseries}\itshape%
360 \def\@begintheorem##1##2{%
361 \LWR@forcenewpage% new
362 \BlockClass{theorembodyproof}% new
363 \LWR@inctheorem% new
364 \item[\hspace{\labelsep}
365 % \theorem@headerfont
366 \InlineClass{theoremheaderproof}{##1.}%
367 ]}%
368 \def\@opargbegintheorem##1##2##3{%
369 \LWR@forcenewpage% new
370 \BlockClass{theorembodyproof}% new
371 \LWR@inctheorem% new
372 \item[\hspace{\labelsep}
373 % \theorem@headerfont
374 \InlineClass{theoremheaderproof}{##1\ (###3).}%
375 ]}%
376
377
378
379 \newcounter{proof}%
380 \if@thmmarks
381 \newcounter{currproofctr}%
382 \newcounter{endproofctr}%
383 \fi
384
385 \gdef\proofSymbol{\openbox}%
386
387 \newcommand{\proofname}{Proof}%
388
389 \newenvironment{proof}[1][\proofname]{
```

```

390     \th@proof
391     \def\theorem@headerfont{\itshape}%
392     \normalfont
393     \theoremsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof
394     \@thm{proof}{proof}{#1}
395 }%
396 {\endtheorem}
397
398 }{}% amsthm option

```

Patched for css:

```

399 \let\LWR@origendtheorem\endtheorem
400 \renewcommand{\endtheorem}{%
401 \ifbool{\LWR@ntheoremmarks}{%
402   \ifsetendmark{%
403     \InlineClass{\theoremdmark}{\csname\InTheoType Symbol\endcsname}%
404     \setendmarkfalse%
405   }fi%
406 }{}%
407 \LWR@origendtheorem%
408 \ifbool{\LWR@ntheoremmarks}{\global\setendmarktrue}{%
409 \endBlockClass%
410 }

411 \gdef\NoEndMark{\global\setendmarkfalse}

```

Redefined to reuse the float mechanism to add list-of-theorem links:

```

\thm@thmline {\langle 1: printed type \rangle} {\langle 2: # \rangle} {\langle 3: optional \rangle} {\langle 4: page \rangle}

412 \renewcommand{\thm@@thmline@noname}[4]{%
413 \hypertocfloat{1}{theorem}{thm}{#2 #3}{}%
414 }
415
416 \renewcommand{\thm@@thmline@name}[4]{%
417 \hypertocfloat{1}{theorem}{thm}{#1 #2 #3}{}%
418 }

```

This was redefined by ntheorem when loaded, so it is now redefined for lwarp:

```
419 \def\thm@@thmline{\thm@@thmline@name}
```

Patch for css:

```

420 \def\listtheorems#1{
421 \LWR@htmlelementclass{nav}{lothm}%
422 \begingroup
423 \c@tocdepth=-2%

```

---

```

424 \def\thm@list{\#1}\thm@processlist
425 \endgroup
426 \LWR@htmlelementclassend{nav}{lothm}%
427 }
```

Proof QED symbol:

```

428
429 \newcommand{\qed}{\qquad\the\quedsymbol}
430
431 \AtBeginDocument{
432 \def\openbox{\text{\HTMLUnicode{25A1}}}% UTF-8 white box
433 \def\blacksquare{\text{\HTMLUnicode{220E}}}% UTF-8 end-of-proof
434 \def\Box{\text{\HTMLUnicode{25A1}}}% UTF-8 white box
435 }

\thref {\langle label\rangle}

436 \newcommand*\thref[1]{\cref{#1}}
```

---

File 108 **lwarp-pagenote.sty**

§ 184 Package **pagenote**

Pkg pagenote pagenote works as-is, but the page option is disabled.

**for HTML output:**

- 1 \DeclareOption{page}{}%
- 2 \LWR@ProvidesPackagePass{pagenote}

---

File 109 **lwarp-paralist.sty**

§ 185 Package **paralist**

Pkg paralist paralist is supported with minor changes.

**for HTML output:**

- 1 \LWR@ProvidesPackagePass{paralist}
- 2 \AtBeginEnvironment{compactitem}{\LWR@itemizestart}
- 3 \AtEndEnvironment{compactitem}{\LWR@itemizeend}
- 4 \AtBeginEnvironment{compactenum}{\LWR@enumeratestart}
- 5 \AtEndEnvironment{compactenum}{\LWR@enumerateend}
- 6 \AtBeginEnvironment{compactdesc}{\LWR@descriptionstart}
- 7 \AtEndEnvironment{compactdesc}{\LWR@descriptionend}
- 8 \def\paradescriptionlabel#1{{\normalfont\textbf{#1}}}}

---

File 110 **lwarf-parskip.sty**

§ 186 Package **parskip**

Pkg **parskip** **parskip** is ignored.

**for HTML output:** Discard all options for lwarf-parskip.

```
1 \LWR@ProvidesPackageDrop{parskip}
```

---

File 111 **lwarf-pdfescape.sty**

§ 187 Package **pdfescape**

Pkg **pdfescape** Emulated.

**for HTML output:** Discard all options for lwarf-pdfescape:

```
1 \LWR@ProvidesPackageDrop{pdfescape}
```

---

File 112 **lwarf-pdfsync.sty**

§ 188 Package **pdfsync**

Pkg **pdfsync** Emulated.

**for HTML output:** Discard all options for lwarf-pdfsync:

```
1 \LWR@ProvidesPackageDrop{pdfsync}
```

```
2 \let\pdfsync\relax
3 \let\pdfsyncstart\relax
4 \let\pdfsyncstop\relax
```

---

File 113 **lwarf-pfnote.sty**

§ 189 Package **pfnote**

Pkg **pfnote** pfnote is emulated.

- ⚠ **pfnote numbers** While emulating pfnote, lwarf is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. lwarf therefore uses continuous footnote numbering even for pfnote.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pfnote}

---

File 114 **lwarf-placeins.sty**

§ 190 Package **placeins**

Pkg **placeins** placeins is not used during HTML conversion.

Discard all options for lwarf-placeins:

**for HTML output:** 1 \LWR@ProvidesPackageDrop{placeins}  
2 \newcommand\*{\FloatBarrier}{}

---

File 115 **lwarf-prelim2e.sty**

§ 191 Package **prelim2e**

Pkg **prelim2e** Emulated.

**for HTML output:** Discard all options for lwarf-prelim2e:

1 \LWR@ProvidesPackageDrop{prelim2e}  
2 \newcommand{\PrelimText}{}  
3 \newcommand{\PrelimTextStyle}{}  
4 \newcommand{\PrelimWords}{}

---

---

File 116 **l warp-quotchap.sty**

§ 192 Package **quotchap**

Pkg **quotchap** **quotchap** is emulated.

*(Based on original code by KARSTEN TINNEFELD, JAN KLEVER.)*

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{quotchap}

2 \newcommand{\@quotchap}{}%
3 \newlength{\LWR@quotchapwidth}
4
5 \let\@printcites\relax
6
7 \newcommand*{\@iprintcites}{%

```

Place the quotes inside a `<div>` of class `quotchap`, of the maximum selected width:

```

8 \uselengthunit{PT}%
9 \begin{BlockClass}[max-width: \rndprintlength{\LWR@quotchapwidth}]{quotchap}
10 \% \begin{minipage}{\LWR@quotchapwidth}
11 \@quotchap
12 \% \end{minipage}
13 \end{BlockClass}

```

Deactivate the quote printing:

```

14 \global\let\@printcites\relax
15 }
16
17 \NewEnviron{savequote}[1][\linewidth]{%

```

Remember the width, adjusted for HTML, and make the length assignment global, per:

<https://tex.stackexchange.com/questions/300823/why-is-setlength-ineffective-inside-a-tabular-environment>

```

18 \setlength{\LWR@quotchapwidth}{#1*2}%
19 \global\LWR@quotchapwidth=\LWR@quotchapwidth%

```

Remember the body, and activate the quote printing:

```

20 \global\let\@quotchap\BODY

```

---

```
21 \global\let\@printcites\@iprintcites%
22 }
```

The quotation author is placed inside a <div> of class qauthor:

```
23 \newcommand{\qauthor}[1]{\begin{BlockClass}{qauthor}{#1}\end{BlockClass}}
\qsetcnfont is ignored:
```

```
24 \newcommand{\qsetcnfont}[1]{}
```

---

File 117 **l warp-ragged2e.sty**

## § 193 Package **ragged2e**

Pkg **ragged2e** ragged2e is not used during HTML conversion.

Discard all options for l warp-ragged2e:

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{ragged2e}

2 \newcommand*{\Centering}{\centering}
3 \newcommand*{\RaggedLeft}{\raggedleft}
4 \newcommand*{\RaggedRight}{\raggedright}
5 \newcommand*{\justifying}={}
6 \newlength{\CenteringLeftskip}
7 \newlength{\RaggedLeftLeftskip}
8 \newlength{\RaggedRightLeftskip}
9 \newlength{\CenteringRightskip}
10 \newlength{\RaggedLeftRightskip}
11 \newlength{\RaggedRightRightskip}
12 \newlength{\CenteringParfillskip}
13 \newlength{\RaggedLeftParfillskip}
14 \newlength{\RaggedRightParfillskip}
15 \newlength{\JustifyingParfillskip}
16 \newlength{\CenteringParindent}
17 \newlength{\RaggedLeftParindent}
18 \newlength{\RaggedRightParindent}
19 \newlength{\JustifyingParindent}
20 \newenvironment*{Center}{\center}{\endcenter}
21 \newenvironment*{FlushLeft}{\flushleft}{\endflushleft}
22 \newenvironment*{FlushRight}{\flushright}{\endflushright}
23 \newenvironment*{justify}{\justifying}{\endjustifying}
```

---

File 118 **lwarf-realscripts.sty**

§ 194 Package **realscripts**

Pkg **realscripts** **realscripts** is emulated. See **lwarf.css** for the <span> of class **supsubscript**.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{realscripts}

2 \let\LWR@origtextsuperscript{textsuperscript}
3 \let\LWR@origtextsubscript{textsubscript}
4
5 \RenewDocumentCommand{\textsuperscript}{s}{\LWR@origtextsuperscript}
6 \RenewDocumentCommand{\textsubscript}{s}{\LWR@origtextsubscript}
7
8 \let\realsuperscript{textsuperscript}
9 \let\realsubscript{textsubscript}
10
11 \let\fakesuperscript{textsuperscript}
12 \let\fakesubscript{textsubscript}
13
14 \newlength{\subsupersep}
15
16 \newcommand*{\LWR@realscriptsalign}{}
17
18 \newcommand*{\LWR@setrealscriptsalign}[1]{%
19 \renewcommand*{\LWR@realscriptsalign}{}%
20 \ifthenelse{\equal{#1}{c}}{\renewcommand{\LWR@realscriptsalign}{text-align:center;}}{}%
21 \ifthenelse{\equal{#1}{r}}{\renewcommand{\LWR@realscriptsalign}{text-align:right;}}{}%
22 }
23
24 \DeclareDocumentCommand \textsubsuperscript {s O{1} mm} {%
25 \LWR@setrealscriptsalign{#2}%
26 \InlineClass[\LWR@realscriptsalign]{supsubscript}{%
27 \textsuperscript{#4}\textsubscript{#3}}%
28 }%
29 }
30
31 \DeclareDocumentCommand \textsupersubscript {s O{1} mm} {%
32 \LWR@setrealscriptsalign{#2}%
33 \InlineClass[\LWR@realscriptsalign]{supsubscript}{%
34 \textsubscript{#4}\textsuperscript{#3}}%
35 }%
36 }
```

---

File 119 **l warp-relsize.sty**

§ 195 Package **relsize**

Pkg **relsize** **relsize** is patched for use by **l warp**.

For **HTML** only the inline macros are supported: **\textlarger**, **\textsmaller**, and **\textscale**. Each becomes an inline span of a modified **font-size**.

**\relsize**, **\larger**, **\smaller**, and **\relscale** are ignored.

While creating **SVG** math for **HTML**, the original definitions are temporarily restored, and so should work as expected.

 **not small** The **HTML** browser's setting for minimum font size may limit how small the output will be displayed.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{relsize}

2 \let\LWR@origrelsize\relsize
3 \LetLtxMacro{\LWR@origlarger}{\larger}
4 \LetLtxMacro{\LWR@origsmaller}{\smaller}
5 \let\LWR@relscale\relscale
6 \LetLtxMacro{\LWR@origtextlarger}{\textlarger}
7 \LetLtxMacro{\LWR@origtextsmaller}{\textsmaller}
8 \let\textscale\textscale
9
10 \appto{\LWR@restoreorigformatting}{%
11 \let\relsize{\LWR@origrelsize}%
12 \LetLtxMacro{\larger}{\LWR@origlarger}%
13 \LetLtxMacro{\smaller}{\LWR@origsmaller}%
14 \let\relscale{\LWR@relscale}%
15 \LetLtxMacro{\textlarger}{\LWR@origtextlarger}%
16 \LetLtxMacro{\textsmaller}{\LWR@origtextsmaller}%
17 \let\textscale{\LWR@textscale}%
18 }
19
20 \newcounter{LWR@relsizetemp}
21
22 \renewcommand*{\relsize}[1]{}
23 \renewcommand*{\larger}[1][]{}
24 \renewcommand*{\smaller}[1][]{}
25 \renewcommand*{\relscale}[1]{}
26
27 \renewcommand*{\textlarger}[2][1]{%
```

---

```

28 \setcounter{LWR@relsizetemp}{100+(#1*20)}%
29 \InlineClass [font-size:\arabic{LWR@relsizetemp}\%]{textlarger}{#2}%
30 }
31
32 \renewcommand*\{\textsmaller}[2][1]{%
33 \setcounter{LWR@relsizetemp}{100-(#1*20)}%
34 \InlineClass [font-size:\arabic{LWR@relsizetemp}\%]{textsmaller}{#2}%
35 }
36
37 \renewcommand*\{\textscale}[2]{%
38 \setcounter{LWR@relsizetemp}{100*\real{#1}}%
39 \InlineClass [font-size:\arabic{LWR@relsizetemp}\%]{textscale}{#2}%
40 }

```

---

File 120 **lwarf-romanbar.sty**

§ 196 Package **romanbar**

Pkg **romanbar** romanbar is patched for use by lwarf.

An inline class with an overline and underline is used.

**for HTML output:** 1 \LWR@ProvidesPackagePass{romanbar}

```

2 \DeclareRobustCommand{\Roman@bar}[1]{% #1 is in Roman, i.e. MMXII
3 \InlineClass[%
4   text-decoration: overline underline ;
5 ]{\romanbar}{#1}%
6 }

```

---

File 121 **lwarf-romanbarpagenumber.sty**

§ 197 Package **romanbarpagenumber**

Pkg **romanbarpagenumber** romanbarpagenumber is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{romanbarpagenumber}

---

File 122 **l warp-rotating.sty**

§ 198 Package **rotating**

Pkg **rotating** rotating is emulated during HTML output, and the rotating package is ignored.

All rotations are ignored in HTML output.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{rotating}
2 \LetLtxMacro{\sidewaystable}{\table}
3 \let\endsidewaystable\endtable
4
5 \LetLtxMacro{\sidewaysfigure}{\figure}
6 \let\endsidewaysfigure\endfigure
7
8 \newenvironment*{sideways}{}{}
9 \newenvironment*{turn}[1]{}{}
10 \newenvironment*{rotate}[1]{}{}
11 \NewDocumentCommand{\turnbox}{m +m}{#2}
12 \let\rotcaption\caption
13 \let\@makerotcaption\@makecaption
```

---

File 123 **l warp-rotfloat.sty**

§ 199 Package **rotfloat**

Pkg **rotfloat** rotfloat is emulated during HTML output, and the rotfloat package is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{rotfloat}
2
3 \RequirePackage{float}
```

\newfloat {\langle 1: type \rangle} {\langle 2: placement \rangle} {\langle 3: ext \rangle} [{\langle 4: within \rangle}]

Emulates the \newfloat command from the float package. Sideways floats are \let to the same as regular floats.

“placement” is ignored.

```
4 \RenewDocumentCommand{\newfloat}{m m m o}{%
5 \IfValueTF{#4}{%
```

```
6 {
7   \DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}
8 }
9 {
10  \DeclareFloatingEnvironment[fileext=#3]{#1}
11  \DeclareFloatingEnvironment[fileext=#3]{sideways#1}
12 }
13 \csletcs{sideways#1}{#1}
14 \csletcs{endsideways#1}{end#1}
```

newfloat package automatically creates the \listof command for new floats, but float does not, so remove \listof here in case it is manually created later.

```
15 \cslet{\listof#1s}\relax
16 \cslet{\listof#1es}\relax
17 }
```

---

File 124 **l warp-savetrees.sty**

§ 200 Package **savetrees**

Pkg **savetrees** Emulated.

**for HTML output:** Discard all options for l warp-savetrees:

```
1 \LWR@ProvidesPackageDrop{savetrees}
```

---

File 125 **l warp-scalefnt.sty**

§ 201 Package **scalefnt**

Pkg **scalefnt** scalefnt is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{scalefnt}

```
2 \DeclareRobustCommand\scalefont[1]{}
```

---

File 126 **l warp-sectsty.sty**

§ 202 Package **sectsty**

Pkg **sectsty** sectsty is emulated.

```

for HTML output: 1 \LWR@ProvidesPackageDrop{sectsty}

2 \newcommand*{\partfont} [1] {}
3 \newcommand*{\partnumberfont} [1] {}
4 \newcommand*{\parttitlefont} [1] {}
5 \newcommand*{\chapterfont} [1] {}
6 \newcommand*{\chapternumberfont} [1] {}
7 \newcommand*{\chaptertitlefont} [1] {}
8 \newcommand*{\sectionfont} [1] {}
9 \newcommand*{\subsectionfont} [1] {}
10 \newcommand*{\subsubsectionfont} [1] {}
11 \newcommand*{\paragraphfont} [1] {}
12 \newcommand*{\ subparagraphfont} [1] {}
13 \newcommand*{\minisecfont} [1] {}
14 \newcommand*{\allsectionsfont}[1] {}
15 \newcommand{\nohang}{}{}
```

\sectionrule is only to be used in \*font commands, thus it is ignored.

```

16 \newcommand*{\sectionrule}[5] {}
17
18 \def\ulemheading#1#2{}
```

File 127 **lwarf-setspace.sty**

## § 203 Package **setspace**

Pkg **setspace** setspace is not used during HTML conversion.

Discard all options for lwarf-setspace:

```

for HTML output: 1 \LWR@ProvidesPackageDrop{setspace}
2
3 \newcommand*{\setstretch}[1] {}
4 \newcommand*{\SetSinglespace}[1] {}
5 \newcommand*{\singlespacing} {}
6 \newcommand*{\onehalfspacing} {}
7 \newcommand*{\doublespacing} {}
8
9 \newenvironment*{singlespace}
10 {
11 \LWR@forcenewpage
12 \BlockClass{singlespace}
13 }
14 {\endBlockClass}
15
16 \newenvironment*{singlespace*}
```

```
17 {
18 \LWR@forcenewpage
19 \BlockClass{singlespace}
20 }
21 {\endBlockClass}
22
23 \newenvironment*{spacing}[1]{
24
25 }{
26
27 }
28
29 \newenvironment*{onehalfspace}
30 {
31 \LWR@forcenewpage
32 \BlockClass{onehalfspace}
33 }
34 {\endBlockClass}
35
36 \newenvironment*{doublespace}
37 {
38 \LWR@forcenewpage
39 \BlockClass{doublespace}
40 }
41 {\endBlockClass}
```

---

File 128 **lwarf-shadow.sty**

§ 204      Package **shadow**

Pkg **shadow** shadow is emulated.

**for HTML output:** Discard all options for lwarf-shadow:

```
1 \LWR@ProvidesPackageDrop{shadow}

2 \newdimen\sboxsep
3 \newdimen\sboxrule
4 \newdimen\sdim
5
6 \newcommand{\shabox}[1]{%
7 \InlineClass{shabox}{#1}%
8 }
```

---

File 129 **l warp-showidx.sty**

§ 205 Package **showidx**

Pkg **showidx** **showidx** is ignored.

**for HTML output:** Discard all options for l warp-showidx:

```
1 \LWR@ProvidesPackageDrop{showidx}
```

---

File 130 **l warp-showkeys.sty**

§ 206 Package **showkeys**

Pkg **showkeys** **showkeys** is ignored.

**for HTML output:** Discard all options for l warp-showkeys:

```
1 \LWR@ProvidesPackageDrop{showkeys}
2 \NewDocumentCommand{\showkeys}{s}{}

---


```

File 131 **l warp-sidecap.sty**

§ 207 Package **sidecap**

Pkg **sidecap** **sidecap** is nullified.

**for HTML output:** Discard all options for l warp-sidecap.

```
1 \LWR@ProvidesPackageDrop{sidecap}
```

See:

[http://tex.stackexchange.com/questions/45401/  
use-the-s-star-argument-with-newdocumentenvironment](http://tex.stackexchange.com/questions/45401/use-the-s-star-argument-with-newdocumentenvironment)  
regarding the creation of starred environments with xparse.

```
2 \NewDocumentEnvironment{SCtable}{s}
3 {\IfValueTF{#3}{\table[#3]}{\table}}
4 {\endtable}
```

```

5
6 \ExplSyntaxOn
7 \cs_new:cpx {SCtable*} {\SCtable*}
8 \cs_new_eq:cN {\endSCtable*} \endSCtable
9 \ExplSyntaxOff
10
11
12 \NewDocumentEnvironment{SCfigure}{soo}
13 {\IfValueTF{#3}{\figure[#3]}{\figure}}
14 {\endfigure}
15
16 \ExplSyntaxOn
17 \cs_new:cpx {SCfigure*} {\SCfigure*}
18 \cs_new_eq:cN {\endSCfigure*} \endSCfigure
19 \ExplSyntaxOff
20
21
22 \newenvironment*{wide}{}{}

```

File 132 **l warp-sidenotes.sty**

## § 208 Package **sidenotes**

*(Based on original code by ANDY THOMAS, OLIVER SCHEBAUM.)*

Pkg **sidenotes** Patched for l warp.

**for HTML output:** Load the original package:

```
1 \LWR@ProvidesPackagePass{sidenotes}
```

The following patch sidenotes for use with l warp:

Stop paragraph handling while creating the caption:

```

2 \RenewDocumentCommand \sidecaption {s o o m}
3 {
4     \LWR@stoppars
5     \captionsetup{style=sidecaption}
6     \IfBooleanTF{#1}
7     { % starred
8         \IfNoValueOrEmptyTF{#2}
9         {\marginnote{\caption*{#4}}}
10        {\marginnote{\caption*{#4}}[#2]}
11    }
12    { % unstarred
13        \IfNoValueOrEmptyTF{#2}
14        {\def\@sidenotes@sidecaption@tof{#4}}

```

```

15   {\def\@sidenotes@sidedcaption@tof{#2}}
16   \IfNoValueOrEmptyTF{#3}
17   {\marginnote{\caption[\@sidenotes@sidedcaption@tof]{#4}}}
18   {\marginnote{\caption[\@sidenotes@sidedcaption@tof]{#4}}[#3]}
19 }
20   \LWR@startpars
21 }

```

Borrowed from the lwarp version of keyfloat:

```

22 \NewDocumentEnvironment{KFLTsidenotes@marginfloat}{0{-1.2ex} m}
23 {%
24 \LWR@maybeinthisfloat%
25 \LWR@forcenewpage%
26 \LWR@stoppars%
27 \LWR@htmlltag{div class="marginblock" id="autofloat-\arabic{LWR@thisfloat}"}
28 \LWR@startpars%
29 \captionsetup{type=#2}%
30 }%
31 {
32 \LWR@htmldivclassend{div}
33 }%
34
35 \RenewDocumentEnvironment{marginfigure}{o}
36 {\begin{KFLTsidenotes@marginfloat}{figure}}
37 {\end{KFLTsidenotes@marginfloat}}
38
39 \RenewDocumentEnvironment{margintable}{o}
40 {\begin{KFLTsidenotes@marginfloat}{table}}
41 {\end{KFLTsidenotes@marginfloat}}

```

The following were changed by sidenotes, and now are reset back to their lwarp-supported originals:

Restoring the definition from the  $\text{\LaTeX}2\epsilon$  article.cls source:

```

42 \renewenvironment{figure*}
43   {@dblfloat{figure}}
44   {\end{@dblfloat}}
45
46 \renewenvironment{table*}
47   {@dblfloat{table}}
48   {\end{@dblfloat}}

```

---

File 133 **l warp-siunitx.sty**

§ 209 Package **siunitx**

Pkg **siunitx** siunitx is patched for use by l warp.

△ **per-mode** Do not use per-mode=fraction, which cannot be seen by the final pdftotext conversion.

Some units will require that the expression be placed inside math mode.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{siunitx}

2 \AtBeginDocument{%
 3   \DeclareSIUnit\bohr{\textit{a}\textsubscript{0}}
 4   \DeclareSIUnit\clight{\textit{c}\textsubscript{0}}
 5   \DeclareSIUnit\elementarycharge{\textit{e}}
 6   \DeclareSIUnit\electronmass{\textit{m}\textsubscript{e}}
 7   \DeclareSIUnit\hartree{\textit{E}\textsubscript{h}}
 8 }% AtBeginDocument
 9

```

---

File 134 **l warp-soul.sty**

§ 210 Package **soul**

(Based on original code by MELCHIOR FRANZ.)

Pkg **soul** Emulated.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{soul}
2 \RequirePackage{xcolor}%

```

Storage for the colors to use:

```

3 \newcommand*\{\LWR@soululcolor\}{}%
4
5 \newcommand*\{\LWR@soulstcolor\}{}%
6
7 \% \definecolor{\LWR@soulhlcolordefault}{HTML}{F8E800}
8 \% \newcommand*\{\LWR@soulhlcolor\}{\LWR@soulhlcolordefault}
9 \newcommand*\{\LWR@soulhlcolor\}{}%

```

Basic markup with css:

```
10 \newcommand{\so}[1]{\InlineClass{letterspacing}{#1}}
11 \newcommand{\caps}[1]{\InlineClass{capsspacing}{#1}}
```

Add colors if not empty:

```
12 \newcommand{\LWR@soulcolor}[4]{%
13 \ifcsempty{#2}%
14 {%
15 \InlineClass{#3}{#1}}%
16 {%
17 \convertcolorspec{named}{\csuse{#2}}{HTML}\LWR@tempcolor%
18 \InlineClass[#4: \#\LWR@tempcolor]{#3}{#1}%
19 }%
20 }%
21
22 \newcommand{\ul}[1]{%
23 \LWR@soulcolor{#1}{\LWR@soululcolor}{\underline}{text-decoration-color}%
24 }%
25
26 \newcommand{\st}[1]{%
27 \LWR@soulcolor{#1}{\LWR@soulstcolor}{\sout}{text-decoration-color}%
28 }%
29
30 \newcommand{\hl}[1]{%
31 \LWR@soulcolor{#1}{\LWR@soulhlcolor}{\highlight}{background-color}%
32 }
```

Nullified:

```
33 \newcommand*\soulaccent}[1]{}
34 \newcommand*\soulregister}[2]{}
35 \newcommand{\sloppyword}[1]{#1}
36 \newcommand*\sodef}[5]{\DeclareRobustCommand#1[1]{\so{##1}}}
37 \newcommand*\resetso(){}
38 \newcommand*\capsdef}[5]{}
39 \newcommand*\capsreset(){}
40 \newcommand*\capssave}[1]{}
41 \newcommand*\capsselect}[1]{}
42 \newcommand*\setul}[2]{}
43 \newcommand*\resetul){}
44 \newcommand*\setuldepth}[1]{}
45 \newcommand*\setuloverlap}[1]{}
```

Set colors:

```
46 \newcommand*\setulcolor}[1]{\renewcommand{\LWR@soululcolor}{#1}}
47 \newcommand*\setstcolor}[1]{\renewcommand{\LWR@soulstcolor}{#1}}
```

---

```
48 \newcommand*{\sethlcolor}[1]{\renewcommand{\LWR@soulhlcolor}{#1}}
```

Long versions of the user-level macros:

```
49 \let\textso\so
50 \let\textul\ul
51 \let\texthl\hl
52 \let\textcaps\caps
```

---

File 135 **lwarp-stabular.sty**

§ 211 Package **stabular**

Pkg **stabular** **stabular** is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{stabular}

Env **stabular** [ $\langle vpos \rangle$ ] [ $\langle colspec \rangle$ ]

```
2 \newenvironment{stabular}[2][c]
3 {
4 \renewcommand{\noalign}{[1]{}
5 \begin{tabular}[#1]{#2}
6 }
7 {\end{tabular}}
```

Env **stabular** [ $\langle width \rangle$ ] [ $\langle vpos \rangle$ ] [ $\langle colspec \rangle$ ]

```
8 \NewDocumentEnvironment{stabular*}{m o m}
9 {
10 \renewcommand{\noalign}{[1]{}
11 \begin{tabular}[#2]{#3}
12 }
13 {\end{tabular}}
```

---

File 136 **lwarp-subfig.sty**

§ 212 Package **subfig**

(Based on original code by STEVEN DOUGLAS COCHRAN.)

Pkg **subfig** **subfig** is supported and patched by **lwarp**.

⚠ **lof/lotdepth** At present, the package options for **lofdepth** and **lotdepth** are not working. These

counters must be set separately after the package has been loaded.

**horizontal spacing** In the document source, use `\hfill` and `\hspace*` between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

**for HTML output:** Accept all options for `lwarp-subfig`:

```
1 \LWR@ProvidesPackagePass{subfig}

\sf@@@subfloat {1 type} [2 lof entry] [3 caption] {4 contents}
```

The outer minipage allows side-by-side subfloats with `\hfill` between.

```
2 \long\def\sf@@@subfloat#1[#2][#3]{#4}%
3 \begin{minipage}{\linewidth}%
4 \LWR@stopars%
5 \@ifundefined{FBsc@max}{}%
6 {\FB@readaux{\let\FBsubheight\relax}}%
7 \tempcnta=\@ne
8 \ifminipage
9 \tempcnta=\z@%
10 \else\ifdim \lastskip=\z@ \else
11 \tempcnta=\tw@%
12 \fi\fi
13 \ifmaincaptiontop
14 \sf@top=\sf@nearskip
15 \sf@bottom=\sf@farskip
16 \else
17 \sf@top=\sf@farskip
18 \sf@bottom=\sf@nearskip
19 \fi
20 \leavevmode
21 \setbox\tempboxa \hbox{#4}%
22 \tempdima=\wd\tempboxa
23 \ifundefined{FBsc@max}{}%
24 {\global\advance\Xhsize-\wd\tempboxa
25 \dimen@\ht\tempboxa
26 \advance\dimen@\dp\tempboxa
27 \ifdim\dimen@>\FBso@max
28 \global\FBso@max\dimen@
29 \fi}%
30 \vtop\bgroup
31 \vbox\bgroup
32 \ifcase\tempcnta
33 \minipagefalse
34 \or
35 \vskip\sf@top
36 \or
```

```
37      \ifdim \lastskip=\z@ \else
38          \@tempskipb\sf@top\relax\@xaddvskip
39      \fi
40      \fi
41      \sf@ifpositiontop{%
42          \ifx \empty#3\relax \else
43              \sf@subcaption{#1}{#2}{#3}%
44              \vskip\sf@capskip
45              \vskip\sf@captopadj
46          \fi\egroup
47          \hrule width0pt height0pt depth0pt
48          \LWR@startpars% new
49 % \box\@tempboxa
50          #4
51          \LWR@stoppars% new
52      }%
53      \LWR@startpars% new
54      \@ifundefined{FBsc@max}%
55      {
56 % \box\@tempboxa
57          #4
58      }%
59      {\ifx\FBsubohight\relax
60 %         \box\@tempboxa
61          #4
62      \else
63 %         \vbox to \FBsubohight{\FBafil\box\@tempboxa\FBbfil}%
64          #4
65      \fi}%
66      \LWR@stoppars% new
67      \egroup
68      \ifx \empty#3\relax \else
69          \vskip\sf@capskip
70          \hrule width0pt height0pt depth0pt
71          \sf@subcaption{#1}{#2}{#3}%
72      \fi
73  }%
74  \vskip\sf@bottom
75  \egroup
76  \ifundefined{FBsc@max}{}%
77  {\addtocounter{FRobj}{-1}%
78  \ifnum\c@FRobj=0\else
79      \subfloatrowsep
80  \fi}%
81  \ifmaincaptiontop\else
82      \global\advance\@nameuse{c@\@capttype}\m@ne
83  \fi
84 \end{minipage}%
85 \LWR@startpars% new
86 \endgroup\ignorespaces%
```

```
87 }%  
  
\sf@subcaption {\{1 type\}} {\{2 lof entry\}} {\{3 caption\}}  
  
88 \long\def\sf@subcaption#1#2#3{  
89 \LWR@stopars% new  
90 \ifx \relax#2\relax \else  
91 \bgroup  
92 \let\label=\@gobble  
93 \let\protect=\string  
94 \def\@subcaplabel{  
95 \caption@lstdfmt{\@nameuse{p@#1}}{\@nameuse{the#1}}}%  
96 \sf@updatecaptionlist{#1}{#2}{\the\value{\@capttype}}{\the\value{#1}}%  
97 \egroup  
98 \fi  
99 \bgroup  
100 \ifx \relax#3\relax  
101 \let\captionlabelsep=\relax  
102 \fi  
103 % \setbox0\vbox{  
104 % \hb@xt@\the\@tempdima{  
105 %  
106 % \hss  
107 % \parbox[t]{\the\@tempdima}{  
108 % \caption@make  
109 % {\@nameuse{sub\@capttype name}}%  
110 % {\@nameuse{thesub\@capttype}}%  
111 % {#3}  
112 % }%  
113 % \hss  
114 % }  
115 % }%  
116 \@ifundefined{FBsc@max}{  
117 % {\box0}}%  
118 {  
119 % \parbox[t]{\the\@tempdima}{  
120 \LWR@traceinfo{sfsubcap B1}}% new  
121 \LWR@htmlblocktag{figcaption}}% new  
122 \caption@make  
123 {\@nameuse{sub\@capttype name}}%  
124 {\@nameuse{thesub\@capttype}}%  
125 {#3}  
126 \LWR@htmlblocktag{/figcaption}}% new  
127 \LWR@traceinfo{sfsubcap B2}}% new  
128 }%  
129 }%  
130 {\dimen@\ht0%  
131 \advance\dimen@\dp0%  
132 \ifdim\dimen@>{FBsc@max}  
133 \global\FBsc@max\dimen@
```

```
134          \fi
135          \FB@readaux{\let\FBsubcheight\relax}%
136          \ifx\FBsubcheight\relax
137              \def\next{
138 %   \parbox[t]{\the\@tempdima}
139 % }
140          \else
141              \def\next{
142 %   \parbox[t][\FBsubcheight][t]{\the\@tempdima}
143 % }
144          \fi
145          \vbox{%
146 %           \hb@xt@\the\@tempdima{%
147 %
148 %           \hss
149 %           \next{%
150 \LWR@traceinfo{sfsubcap C1}{ new
151             \caption@make
152                 {\@nameuse{sub\@capttype name}}%
153                 {\@nameuse{thesub\@capttype}}%
154                 {#3}}
155 \LWR@traceinfo{sfsubcap C1}{ new
156 % }
157 %           \hss
158
159 %   }
160   }
161   }%
162   \egroup
163 \LWR@startpars% new
164 }

\caption@@make {<caption label>} {<caption text>}

165 \renewcommand\caption@@make[2]{%
166 \LWR@startpars% new
167   \sbox\@tempboxa{#1}%
168   \ifdim\wd\@tempboxa=\z@
169     \let\caption@lsep\relax
170   \fi
171   \caption@ifempty{#2}{%
172     \let\caption@lsep\empty
173     \let\caption@tfmt\@firstofone
174   }%
175 %   \setpar{\@par\caption@par}\caption@@par
176 \renewcommand{\@par}{\LWR@closeparagraph\LWR@orig@@par}% new
177   \caption@applyfont
178   \caption@fmt
179   {\ifcaption@star\else
180     \begingroup
```

```

181      \captionlabelfont
182      #1%
183      \endgroup
184      \fi}%
185      {\ifcaption@star\else
186          \begingroup
187              \caption@iflf\captionlabelfont
188              \relax\caption@lsep
189          \endgroup
190      \fi}%
191      {{\captiontextfont
192          \caption@ifstrut
193              {\vrule\@height\ht\strutbox\@width\z@}%
194              {}}%
195          \nobreak\hskip\z@skip % enable hyphenation
196          \caption@tfmt{\#2}
197      \LWR@ensuredoingapar% new
198          \caption@ifstrut
199              {\ifhmode\@finalstrut\strutbox\fi}%
200              {}}%
201          \par}%
202 \LWR@stoppars% new
203 }

```

Patches for \sf@sub@label:

```

204 \def\subfloat@label{%
205 \LWR@ensuredoingapar% new
206 \@ifnextchar(% %) match left parenthesis
207 {\sf@sub@label}
208 {\sf@sub@label(Sub\@capttype\space
209             \ifundefined{thechapter}{}{\nameuse{thechapter}\space}%
210             \nameuse{p@sub\@capttype}%
211             \nameuse{thesub\@capttype}.)}}}

```

Patches for \subref.

The unstarred version uses a \ref link whose printed text comes from the sub@<label>:

```

212 \renewcommand{\sf@subref}[1]{%
213 \LWR@subnewref{\#1}{sub@\#1}%
214 }

```

The starred version uses the printed sub@<label> which is stored as if it were a page number:

```

215 \renewcommand{\sf@subref}[1]{\LWR@origpageref{sub@\#1}}

```

Defining new subfloats. The `\@sub<type>` for each is redefined.

```
216 \LetLtxMacro{\LWR@orig}{\newsubfloat}{\newsubfloat}
217
218 \def{\@newsubfloat[#1]{%
219   \LWR@orig{\newsubfloat[#1]{#2}}%
220   \renewcommand{\@sub#2}[2]{\hypertocfloat{2}{sub#2}{\ext@sub#2}{##1}{##2}}%
221 }}
```

Pre-defined for figures and tables:

```
222 \renewcommand{\@subfigure}[2]{\hypertocfloat{2}{subfigure}{lof}{#1}{#2}}
223 \renewcommand{\@subtable}[2]{\hypertocfloat{2}{subtable}{lot}{#1}{#2}}
224 % \def{\subfigure}{\subfloat}
225 % \def{\subtable}{\subfloat}
```

---

File 137 **lwarf-supertabular.sty**

## § 213 Package **supertabular**

Pkg **supertabular** supertabular is emulated during HTML output.

**for HTML output:** `\LWR@ProvidesPackageDrop{supertabular}`

⚠ misplaced alignment  
alignment tab character &

For `\tablefirsthead`, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
...
\EndDefiningTabulars
```

See section 7.7.

```
2 \newcommand{\LWRST@firsthead}{}
3
4 \newcommand{\tablefirsthead}[1]{%
5   \long\gdef{\LWRST@firsthead}{#1}%
6 }
7
8 \newcommand{\tablehead}[1]{}
9 \newcommand{\tabletail}[1]{}
10
11 \newcommand{\LWRST@lasttail}{}
12
13 \newcommand{\tablelasttail}[1]{%
14   \long\gdef{\LWRST@lasttail}{#1}%
15 }
```

```

16
17 \newcommand{\tablecaption}[2][]{%
18     \long\gdef\LWRST@caption{\caption[#1]{#2}}%
19 }
20
21 \let\topcaption\tablecaption
22 \let\bottomcaption\tablecaption
23
24 \global\let\LWRST@caption\relax
25
26 \newcommand*\shrinkheight[1]{}
27
28 \NewDocumentEnvironment{supertabular}{s o m}
29 {
30 \LWR@traceinfo{supertabular}
31 \table
32 \LWRST@caption
33 \begin{tabular}{#3}
34 \TabularMacro\ifdefvoid{\LWRST@firsthead}{%
35 {\LWR@getmynexttoken}%
36 {\expandafter\LWR@getmynexttoken\LWRST@firsthead}%
37 }%
38 {%
39 \ifdefvoid{\LWRST@lasttail}{%
40 {}}%
41 {%
42 \TabularMacro\ResumeTabular%
43 \LWRST@lasttail%
44 }%
45 \end{tabular}
46 \endtable
47 \LWR@traceinfo{supertabular done}
48 }
49
50 \NewDocumentEnvironment{mpsupertabular}{s o m}
51 {\minipage{\linewidth}\supertabular{#3}%
52 {\endsupertabular\endminipage}

```

File 138 **lwarf-syntonly.sty**

## § 214 Package **syntonly**

Pkg **syntonly** Emulated.

**for HTML output:** Discard all options for lwarf-syntonly:

```
1 \LWR@ProvidesPackageDrop{syntonly}
```

```
2 \newif\ifsyntax@  
3 \syntax@false  
4  
5 \newcommand*{\syntaxonly}{}  
6  
7 \onlypreamble\syntaxonly
```

---

File 139 **l warp-tables.sty**

§ 215 Package **tables**

Pkg **tables** tables is emulated. `\LWR@hline` is used to handle the optional argument when tables is loaded.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{tables}  
  
2 \newdimen\tablinesep  
3 \newdimen\arraylinesep  
4 \newdimen\extrarulesep
```

---

File 140 **l warp-tabularx.sty**

§ 216 Package **tabularx**

Pkg **tabularx** tabularx is emulated by l warp.

**for HTML output:** Discard all options for l warp-tabularx:

```
1 \LWR@ProvidesPackageDrop{tabularx}  
  
2 \NewDocumentEnvironment{tabularx}{m o m}  
3 {\tabular{#3}}  
4 {\endtabular}  
5  
6 \NewDocumentEnvironment{tabularx*}{m o m}  
7 {\tabular{#3}}  
8 {\endtabular}
```

---

File 141 **l warp-tabulary.sty**

§ 217 Package **tabulary**

Pkg **tabulary** tabulary is emulated by l warp.

**for HTML output:** Discard all options for l warp-tabulary.

Column types L, C, R, and J are emulated by l warp core code.

```
1 \LWR@ProvidesPackageDrop{tabulary}

2 \NewDocumentEnvironment{tabulary}{m o m}
3 {\begin{array}{#3}}
4 {\end{array}}
5
6 \NewDocumentEnvironment{tabulary*}{m o m}
7 {\begin{array}{#3}}
8 {\end{array}}
9
10 \newdimen\tymin
11 \newdimen\tymax
12 \def\tyformat{}

---


```

---

File 142 **l warp-textarea.sty**

§ 218 Package **textarea**

Pkg **textarea** textarea is emulated.

**for HTML output:** \LWR@ProvidesPackageDrop{textarea}

```
1 \newcommand\StartFromTextArea{}
2 \newcommand\StartFromHeaderArea{}
3 \newcommand*\RestoreTextArea{}
4 \newcommand*\ExpandTextArea[1][*]{}
5 \let\NCC@restoretarea\empty

---


```

---

File 143 **l warp-textcomp.sty**

§ 219 Package **textcomp**

Pkg **textcomp** **textcomp** is patched for use by **l warp**.

Some **textcomp** symbols do not have Unicode equivalents, and thus are not supported.

- ⚠ **Missing symbols** Many **textcomp** symbols are not supported by many fonts. Try using more complete fonts in the **css**, but expect to see gaps in coverage.

**for HTML output:** 1 \LWR@ProvidesPackagePass{textcomp}

The following are restored for print when inside a **lateximage**:

```
2 \let\LWR@origtextdegree\textdegree
3 \let\LWR@origtextcelsius\textcelsius
4 \let\LWR@origtextohm\textohm
5 \let\LWR@origtextmu\textmu
6 \let\LWR@origtextlquill\textlquill
7 \let\LWR@origtextrquill\textrquill
8 \let\LWR@origtextcircledP\textcircledP
9 \let\LWR@origtexttwelveudash\texttwelveudash
10 \let\LWR@origtextthreequartersemdash\textthreequartersemdash
11 \let\LWR@origtextmho\textmho
12 \let\LWR@origtextnaira\textnaira
13 \let\LWR@origtextpeso\textpeso
14 \let\LWR@origtextrecipe\textrecipe
15 \let\LWR@origtextpertenthousand\textpertenthousand
16 \let\LWR@origtextbaht\textbaht
17 \let\LWR@origtextdiscount\textdiscount
18 \let\LWR@origtextservicemark\textservicemark
19 \LetLtxMacro{\LWR@origcapitalcedilla}{\capitalcedilla}
20 \LetLtxMacro{\LWR@origcapitalogonek}{\capitalogonek}
21 \LetLtxMacro{\LWR@origcapitalgrave}{\capitalgrave}
22 \LetLtxMacro{\LWR@origcapitalacute}{\capitalacute}
23 \LetLtxMacro{\LWR@origcapitalcircumflex}{\capitalcircumflex}
24 \LetLtxMacro{\LWR@origcapitaltilde}{\capitaltilde}
25 \LetLtxMacro{\LWR@origcapitaldieresis}{\capitaldieresis}
26 \LetLtxMacro{\LWR@origcapitalhungarumlaut}{\capitalhungarumlaut}
27 \LetLtxMacro{\LWR@origcapitalring}{\capitalring}
28 \LetLtxMacro{\LWR@origcapitalcaron}{\capitalcaron}
29 \LetLtxMacro{\LWR@origcapitalbreve}{\capitalbreve}
30 \LetLtxMacro{\LWR@origcapitalmacron}{\capitalmacron}
```

---

```
31 \LetLtxMacro{\LWR@origcapitaldotaccent}{\capitaldotaccent}
32 \LetLtxMacro{\LWR@origtextcircled}{\textcircled}
```

For HTML, use HTML entities or direct Unicode, depending on the engine.

\AtBeginDocument improves support for Lua<sup>T</sup>E<sub>X</sub> and X<sup>E</sup><sub>T</sub>E<sub>X</sub>.

```
33 \AtBeginDocument{
34 \ifPDFTeX
35 \renewcommand*{\textdegree}{\HTMLentity{deg}}
36 \renewcommand*{\textcelsius}{\HTMLunicode{2103}}
37 \renewcommand*{\textohm}{\HTMLunicode{2126}}
38 \renewcommand*{\textmu}{\HTMLunicode{00B5}}
39 \renewcommand*{\textlquill}{\HTMLunicode{2045}}
40 \renewcommand*{\textrquill}{\HTMLunicode{2046}}
41 \renewcommand*{\textcircledP}{\HTMLunicode{2117}}
42 \renewcommand*{\texttwelvedash}{\HTMLunicode{2014}}% emdash
43 \renewcommand*{\textthreequartersemdash}{\HTMLunicode{2014}}% emdash
44 \renewcommand*{\textmho}{\HTMLunicode{2127}}
45 \renewcommand*{\textnaira}{\HTMLunicode{20A6}}
46 \renewcommand*{\textpeso}{\HTMLunicode{20B1}}
47 \renewcommand*{\textrecipe}{\HTMLunicode{211E}}
48 \renewcommand*{\textpertenthousand}{\HTMLunicode{2031}}
49 \renewcommand*{\textbaht}{\HTMLunicode{0E3F}}
50 \renewcommand*{\textdiscount}{\%}
51 \renewcommand*{\textservicemark}{\HTMLunicode{2120}}
52 \else
```

NOTE: Some of the following do not print well in the listing. Consult the .dtx or .sty file for the actual characters.

```
53 \renewcommand*{\textdegree}{°}
54 \renewcommand*{\textcelsius}{°C}
55 \renewcommand*{\textohm}{Ω}
56 \renewcommand*{\textmu}{μ}
57 \renewcommand*{\textlquill}{ℓ}
58 \renewcommand*{\textrquill}{ℓ}
59 \renewcommand*{\textcircledP}{®}
60 \renewcommand*{\texttwelvedash}{--}% emdash
61 \renewcommand*{\textthreequartersemdash}{--}% emdash
62 \renewcommand*{\textmho}{ℳ}
63 \renewcommand*{\textnaira}{₦}
64 \renewcommand*{\textpeso}{₱}
65 \renewcommand*{\textrecipe}{℞}
66 \renewcommand*{\textpertenthousand}{‰}
67 \renewcommand*{\textbaht}{฿}
68 \renewcommand*{\textdiscount}{%}
69 \renewcommand*{\textservicemark}{}
70 \fi
```

For HTML, Unicode diacritical marks are used:

```

71 \renewcommand*{\capitalcedilla}[1]{\#1\HTMLunicode{0327}}
72 \renewcommand*{\capitalogonek}[1]{\#1\HTMLunicode{0328}}
73 \renewcommand*{\capitalgrave}[1]{\#1\HTMLunicode{0300}}
74 \renewcommand*{\capitalacute}[1]{\#1\HTMLunicode{0301}}
75 \renewcommand*{\capitalcircumflex}[1]{\#1\HTMLunicode{0302}}
76 \renewcommand*{\capitaltilde}[1]{\#1\HTMLunicode{0303}}
77 \renewcommand*{\capitaldieresis}[1]{\#1\HTMLunicode{0308}}
78 \renewcommand*{\capitalhungarumlaut}[1]{\#1\HTMLunicode{30B}}
79 \renewcommand*{\capitalring}[1]{\#1\HTMLunicode{30A}}
80 \renewcommand*{\capitalcaron}[1]{\#1\HTMLunicode{30C}}
81 \renewcommand*{\capitalbreve}[1]{\#1\HTMLunicode{306}}
82 \renewcommand*{\capitalmacron}[1]{\#1\HTMLunicode{304}}
83 \renewcommand*{\capitaldotaccent}[1]{\#1\HTMLunicode{307}}

```

\textcircled becomes a span with a rounded border:

```

84 \renewcommand*{\textcircled}[1]{%
85 \InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{\#1}%
86 }
87 }% AtBeginDocument

```

When a `lateximage` is begun:

```

88 \appto{\LWR@restoreorigformatting}{%
89 \let\textdegree{\LWR@origtextdegree}
90 \let\textcelsius{\LWR@origtextcelsius}
91 \let\textohm{\LWR@origtextohm}
92 \let\textmu{\LWR@origtextmu}
93 \let\textlquill{\LWR@origtextlquill}
94 \let\textrquill{\LWR@origtextrquill}
95 \let\textcircledP{\LWR@origtextcircledP}
96 \let\texttwelveudash{\LWR@origtexttwelveudash}
97 \let\textthreequartersemdash{\LWR@origtextthreequartersemdash}
98 \let\textmho{\LWR@origtextmho}
99 \let\textnaira{\LWR@origtextnaira}
100 \let\textpeso{\LWR@origtextpeso}
101 \let\textrecipe{\LWR@origtextrecipe}
102 \let\textpertenthousand{\LWR@origtextpertenthousand}
103 \let\textbaht{\LWR@origtextbaht}
104 \let\textdiscount{\LWR@origtextdiscount}
105 \let\textservicemark{\LWR@origtextservicemark}
106 \LetLtxMacro{\capitalcedilla}{\LWR@origcapitalcedilla}
107 \LetLtxMacro{\capitalogonek}{\LWR@origcapitalogonek}
108 \LetLtxMacro{\capitalgrave}{\LWR@origcapitalgrave}
109 \LetLtxMacro{\capitalacute}{\LWR@origcapitalacute}
110 \LetLtxMacro{\capitalcircumflex}{\LWR@origcapitalcircumflex}
111 \LetLtxMacro{\capitaltilde}{\LWR@origcapitaltilde}

```

---

```

112 \LetLtxMacro{\capitaldieresis}{\LWR@origcapitaldieresis}
113 \LetLtxMacro{\capitalhungarumlaut}{\LWR@origcapitalhungarumlaut}
114 \LetLtxMacro{\capitalring}{\LWR@origcapitalring}
115 \LetLtxMacro{\capitalcaron}{\LWR@origcapitalcaron}
116 \LetLtxMacro{\capitalbreve}{\LWR@origcapitalbreve}
117 \LetLtxMacro{\capitalmacron}{\LWR@origcapitalmacron}
118 \LetLtxMacro{\capitaldotaccent}{\LWR@origcapitaldotaccent}
119 \LetLtxMacro{\textcircled}{\LWR@origtextcircled}
120 }

```

---

File 144 **l warp-textpos.sty**

§ 220 Package **textpos**

Pkg **textpos** **textpos** is emulated during HTML output, and the **textpos** package is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{textpos}

2 \NewDocumentEnvironment{textblock}{m r(){}{}}
3 \NewDocumentEnvironment{textblock*}{m o r(){}{}}
4 \newcommand*\{\\TPGrid}[3][]{}
5 \NewDocumentCommand{\TPMargin}{s o}{}
6 \newcommand*\{\\textblockcolour}[1]{}
7 \newcommand*\{\\textblockrulecolour}[1]{}
8 \newcommand*\{\\textblockcolor}[1]{}
9 \newcommand*\{\\textblockrulecolor}[1]{}
10 \newcommand*\{\\tekstblokkulur}[1]{}
11 \newcommand*\{\\tekstblokrulekulur}[1]{}
12 \newlength{\TPHorizModule}
13 \newlength{\TPVertModule}
14 \newlength{\TPboxrulesize}
15 \newcommand{\textblocklabel}[1]{}
16 \newcommand*\{\\showtextsize}{}
17 \newcommand{\textblockorigin}[2]{}

```

---

File 145 **l warp-theorem.sty**

§ 221 Package **theorem**

(Based on original code by FRANK MITTELBACH.)

Pkg **theorem** **theorem** is patched for use by l warp.

**CSS styling of theorems and proofs:**

**Theorem:** <div> of class theorembody<theoremstyle>

**Theorem Header:** <span> of class theoremheader

where <theoremstyle> is plain, break, etc.

**for HTML output:** 1 \LWR@ProvidesPackagePass{theorem}

Storage for the style being used for new theorems:

2 \newcommand{\LWR@newtheoremstyle}{plain}

Patched to remember the style being used for new theorems:

```

3 \gdef\theoremstyle#1{%
4   \@ifundefined{th@#1}{\@warning
5     {Unknown theoremstyle '#1'. Using 'plain'}%
6     \theorem@style{plain}%
7     \renewcommand{\LWR@newtheoremstyle}{plain}%
8   }%
9   {%
10    \theorem@style{#1}%
11    \renewcommand{\LWR@newtheoremstyle}{#1}%
12  }%
13  \begingroup
14    \csname th@\the\theorem@style \endcsname
15  \endgroup

```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```

16 \gdef\xnthy#1#2[#3]{%
17   \expandafter\@ifdefinable\csname #1\endcsname
18   {%
19     \csedef{\LWR@thmstyle#1}{\LWR@newtheoremstyle}%
20     \@definecounter{#1}\@newctr{#1}[#3]%
21     \expandafter\xdef\csname the#1\endcsname
22     {\expandafter\noexpand\csname the#3\endcsname
23      \thmcntsep\thmcnt{#1}}%
24     \def\@tempa{\global\@namedef{#1}}%
25     \expandafter\@tempa\expandafter{%
26       \csname th@\the\theorem@style
27         \expandafter\endcsname\the\theorem@bodyfont
28       \thm{#1}{#2}}%
29     \global\expandafter\let\csname end#1\endcsname\endtheorem
30     \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\csuse{LWR@thmstyle#1}}%
31   }%
32 }
33 \gdef\ynthy#1#2{%

```

```

34     \expandafter\@ifdefinable\csname #1\endcsname
35     {
36       \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% new
37       \@definecounter{#1}%
38       \expandafter\xdef\csname the#1\endcsname{\@thmcnter{#1}}%
39       \def\@tempa{\global\@namedef{#1}}\expandafter \atempa
40       \expandafter{\csname th@\the \theorem@style \expandafter
41       \endcsname \the\theorem@bodyfont \@thm{#1}{#2}}%
42       \global \expandafter \let \csname end#1\endcsname \endtheorem
43       \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\csuse{LWR@thmstyle#1}}}% new
44     }%
45
46 \gdef\@othm#1[#2]#3{%
47   \expandafter\ifx\csname c@#2\endcsname\relax
48   \nocounterr{#2}%
49   \else
50   \expandafter\@ifdefinable\csname #1\endcsname
51   {
52     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% new
53     \expandafter \xdef \csname the#1\endcsname
54     {\expandafter\noexpand \csname the#2\endcsname}%
55     \def\@tempa{\global\@namedef{#1}}\expandafter \atempa
56     \expandafter{\csname th@\the \theorem@style \expandafter
57     \endcsname \the\theorem@bodyfont \@thm{#2}{#3}}%
58     \global \expandafter \let \csname end#1\endcsname \endtheorem
59     \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\csuse{LWR@thmstyle#1}}}% new
60   }%
61   \fi}

```

The following are patched for css.

These were in individual files thp.sty for plain, thmb.sty for margin break, etc. They are gathered together here.

Each theorem is encased in a `\BlockClass` environment of class `theorembody<style>`.

Each header is encased in an `\InlineClass` of class `theoremheader`.

```

62 \gdef\th@plain{\%normalfont\itshape
63   \def\@begintheorem##1##2{%
64     \LWR@forcenewpage% new
65     \BlockClass{theorembody}\LWR@thisthmstyle}% new
66     \item[\hskip\labelsep
67       \InlineClass{theoremheader}{##1\ ##2}%
68     ]}%
69 \def\@opargbegintheorem##1##2##3{%
70 \LWR@forcenewpage% new
71   \BlockClass{theorembody}\LWR@thisthmstyle}% new
72   \item[\hskip\labelsep
73     \InlineClass{theoremheader}{##1\ ##2\ (#3)}%

```

```
74      ]}
75 }
76
77 \gdef\th@break{\normalfont\slshape
78   \def\@begintheorem##1##2{%
79 \LWR@forcenewpage% new
80   \BlockClass{theorembody}\LWR@thisthmstyle}% new
81   \item[\hspace{0pt}\labelsep
82     \InlineClass{theoremheader}{##1\ ##2}\newline%
83   ]}%
84 \def\@opargbegintheorem##1##2##3{%
85 \LWR@forcenewpage% new
86   \BlockClass{theorembody}\LWR@thisthmstyle}% new
87   \item[\hspace{0pt}\labelsep
88     \InlineClass{theoremheader}{##1\ ##2\ (#3)}\newline%
89   ]}%
90 }
91
92 \gdef\th@marginbreak{\normalfont\slshape
93   \def\@begintheorem##1##2{%
94 \LWR@forcenewpage% new
95   \BlockClass{theorembody}\LWR@thisthmstyle}% new
96   \item[\hspace{0pt}\labelsep %
97     \InlineClass{theoremheader}{##2 \qquad ##1}\newline%
98   ]}%
99 \def\@opargbegintheorem##1##2##3{%
100 \LWR@forcenewpage% new
101   \BlockClass{theorembody}\LWR@thisthmstyle}% new
102   \item[\hspace{0pt}\labelsep %
103     \InlineClass{theoremheader}{##2 \qquad ##1\ %
104     (#3)}\newline%
105   ]}%
106 }
107
108 \gdef\th@changebreak{\normalfont\slshape
109   \def\@begintheorem##1##2{%
110 \LWR@forcenewpage% new
111   \BlockClass{theorembody}\LWR@thisthmstyle}% new
112   \item[\hspace{0pt}\labelsep
113     \InlineClass{theoremheader}{##2\ ##1}\newline%
114   ]}%
115 \def\@opargbegintheorem##1##2##3{%
116 \LWR@forcenewpage% new
117   \BlockClass{theorembody}\LWR@thisthmstyle}% new
118   \item[\hspace{0pt}\labelsep %
119     \InlineClass{theoremheader}{##2\ ##1\ %
120     (#3)}\newline%
121   ]}%
122 }
123
```

```

124 \gdef\th@change{%\normalfont\slshape
125   \def\@begintheorem##1##2{
126     \LWR@forcenewpage% new
127     \BlockClass{theorembody}\LWR@thisthmstyle)% new
128     \item[\hspace{\labelsep}
129       \InlineClass{theoremheader}{##2\ ##1}
130     ]}%
131 \def\@opargbegintheorem##1##2##3{%
132 \LWR@forcenewpage% new
133   \BlockClass{theorembody}\LWR@thisthmstyle)% new
134   \item[\hspace{\labelsep}
135     \InlineClass{theoremheader}{##2\ ##1\ (###3)}
136   ]}%
137 }%
138
139 \gdef\th@margin{%\normalfont\slshape
140   \def\@begintheorem##1##2{
141     \LWR@forcenewpage% new
142     \BlockClass{theorembody}\LWR@thisthmstyle)% new
143     \item[\hspace{\labelsep}
144       \InlineClass{theoremheader}{##2 \qquad ##1}
145     ]}%
146 \def\@opargbegintheorem##1##2##3{%
147 \LWR@forcenewpage% new
148   \BlockClass{theorembody}\LWR@thisthmstyle)% new
149   \item[\hspace{\labelsep}
150     \InlineClass{theoremheader}{##2 \qquad ##1\ (###3)}
151   ]}%
152 }

```

Patched for css:

```
153 \gdef\@endtheorem{\endBlockClass\endtrivlist}
```

File 146 **lwarf-threeparttable.sty**

## § 222 Package **threeparttable**

Pkg **threeparttable** threeparttable is emulated during HTML output, and the threeparttable package is ignored.

Table note are contained inside a css <div> of class tnotes. If enumitem is used, the note item labels are also individually highlighted with an additional css <span> of class tnoteitemheader, otherwise they are plain text.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{threeparttable}

---

```
\LWR@printtablenote  {\langle text\rangle}
    Prints the table note item header inside a css class of tnoteitemheader.
    2 \newcommand{\LWR@printtablenote}[1]{\InlineClass{tnoteitemheader}{#1}}
```

Env **threeparttable** [\langle alignment\rangle] To emulate threeparttable:

```
3 \newenvironment*{threeparttable}[1][b]{}{}
```

Env **tablenotes** [\langle options\rangle]

```
4 \newenvironment*{tablenotes}[1] []
5 {%
6 \LWR@forcenewpage
7 \BlockClass{tnotes}%
8 \ltx@ifpackageloaded{enumitem}{%
9 \setlist[description]{format=\LWR@printtablenote}%
10 }{%
11 \description%
12 }%
13 {%
14 \enddescription%
15 \endBlockClass%
16 }
```

\tnote {\langle text\rangle}

```
17 \newcommand{\tnote}[1]{\LWR@htmlspan{sup}{#1}}
```

---

#### File 147 **lwarf-tikz.sty**

§ 223 Package **tikz**

Pkg **tikz** tikz is supported.

Accept all options for lwarf-tikz:

```
1 \LWR@ProvidesPackagePass{tikz}
```

**catcodes** lwarf changes the catcode of \$ for its own use. The Tikz babel library temporarily changes catcodes back to normal for Tikz's use. tikz v3.0.0 introduced the babel library which handles catcode changes. For older versions, lwarf must change \$'s catcode itself.

Also see:

<https://tex.stackexchange.com/questions/16199/test-if-a-package-or-package-option-is-loaded>

for HTML output:

```

2 \begin{warpHTML}

3 \newboolean{LWR@tikzbabel}
4
5 \@ifpackagelater{tikz}{2013/12/20}%
6 {\usetikzlibrary{babel}\booltrue{LWR@tikzbabel}}
7 {\boolfalse{LWR@tikzbabel}}
```

Env tikzpicture tikzpicture environment is enclosed inside a \lateximage. May be used as-is, and its contents will be converted to an image.

```

8 \BeforeBeginEnvironment{tikzpicture}{%
9 \latexitimage%
10 \ifbool{LWR@tikzbabel}%
11 {}%
12 {\catcode`\$=3} % dollar sign is math shift
13 }
14
15 \AfterEndEnvironment{tikzpicture}{%
16 \endlatexitimage%
17 \ifbool{LWR@tikzbabel}%
18 {}%
19 {\catcode`\$=\active}%
20 }
```

```
21 \end{warpHTML}
```

File 148 lwarp-titleps.sty

## § 224 Package **titleps**

Pkg titleps titleps is loaded and used by lwarp during HTML output. All user options and macros are ignored and disabled.

Discard all options for lwarp-titleps:

for HTML output:

```
1 \LWR@ProvidesPackageDrop{titleps}
```

\pagestyle and \thispagestyle are already disabled in the lwarp code.

```
\newpagestyle {<name>} [<style>] {<commands>}
```

```
\renewpagestyle  {\langle name\rangle} [\langle style\rangle] {\langle commands\rangle}
                2 \NewDocumentCommand{\newpagestyle}{m o m}{}{}
                3 \NewDocumentCommand{\renewpagestyle}{m o m}{}{}

\sethead    [\langle el\rangle] [\langle ec\rangle] [\langle er\rangle] {\langle ol\rangle} {\langle oc\rangle} {\langle or\rangle}
\setfoot    [\langle el\rangle] [\langle ec\rangle] [\langle er\rangle] {\langle ol\rangle} {\langle oc\rangle} {\langle or\rangle}
                4 \NewDocumentCommand{\sethead}{o o m m m}{}{}
                5 \NewDocumentCommand{\setfoot}{o o m m m}{}{}

\settlemarks * {\langle names\rangle}
                6 \NewDocumentCommand{\settlemarks}{s m}{}{}

\headrule
\footrule
                7 \newcommand*{\headrule}{}{}
                8 \newcommand*{\footrule}{}{}

\setheadrule {\langle length\rangle}
\setfootrule {\langle length\rangle}
                9 \newcommand*{\setheadrule}[1]{}{}
                10 \newcommand*{\setfootrule}[1]{}{}

\makeheadrule
\makefootrule
                11 \newcommand*{\makeheadrule}{}{}
                12 \newcommand*{\makefootrule}{}{}

\setmarkboth {\langle code\rangle}
                13 \newcommand{\setmarkboth}[1]{}{}

\widenhead
                14 \NewDocumentCommand{\widenhead}{s o o m m}{}{}

\bottlemarks
\toptitlemarks
\firsttitlemarks
\nexttitlemarks
```

```

\outertitlemarks
\innertitlemarks

15 \newcommand*\bottitlemarks{}
16 \newcommand*\toptitlemarks{}
17 \newcommand*\firsttitlemarks{}
18 \newcommand*\nexttoptitlemarks{}
19 \newcommand*\outertitlemarks{}
20 \newcommand*\innertitlemarks{}

\newtitlemark * {\langle name\rangle}
21 \NewDocumentCommand{\newtitlemark}{s m}{}

\pretitlemark * {\langle section\rangle} {\langle text\rangle}
22 \NewDocumentCommand{\pretitlemark}{s m m}{}

\ifsamemark {\langle group\rangle} {\langle command\rangle} {\langle true\rangle} {\langle false\rangle}
23 \newcommand{\ifsamemark}[4]{}

\setfloathead * [(.)] [(.)] [(.)] {(.)} {(.)} {\langle extra\rangle} [⟨ which⟩]
\setfloatfoot * [(.)] [(.)] [(.)] {(.)} {(.)} {\langle extra\rangle} [⟨ which⟩]
24 \NewDocumentCommand{\setfloathead}{s o o o m m m m m}{}
25 \NewDocumentCommand{\setfloatfoot}{s o o o m m m m m}{}

\nextfloathead * [(.)] [(.)] {(.)} {(.)} {\langle extra\rangle} [⟨ which⟩]
\nextfloatfoot * [(.)] [(.)] {(.)} {(.)} {\langle extra\rangle} [⟨ which⟩]
26 \NewDocumentCommand{\nextfloathead}{s o o o m m m m m}{}
27 \NewDocumentCommand{\nextfloatfoot}{s o o o m m m m m}{}

\newmarkset {\langle markset\rangle}
28 \newcommand{\newmarkset}[1]{}

\newextramark * {\langle markset\rangle} {\langle macro-name\rangle}
29 \NewDocumentCommand{\newextramark}{s m m}{}

\botextramarks {\langle markset\rangle}
\topextramarks {\langle markset\rangle}
\firsextramarks {\langle markset\rangle}

```

---

```
\nextextramarks  {⟨markset⟩}
\outerextramarks {⟨markset⟩}
\innerextramarks {⟨markset⟩}

30 \newcommand{\botextramarks}[1]{}
31 \newcommand{\topextramarks}[1]{}
32 \newcommand{\firstextramarks}[1]{}
33 \newcommand{\nexttopextramarks}[1]{}
34 \newcommand{\outerextramarks}[1]{}
35 \newcommand{\innerextramarks}[1]{}
```

---

File 149 **l warp-titleref.sty**

§ 225 Package **titleref**

Pkg titleref titleref is superceded by hyperref and nameref.

**for HTML output:** 1 \LWR@loadnever{titleref}{hyperref and nameref}

---

File 150 **l warp-titlesec.sty**

§ 226 Package **titlesec**

Pkg titlesec titlesec is emulated. All user options and macros are ignored and disabled.

Discard all options for l warp-titlesec:

**for HTML output:** 1 \LWR@ProvidesPackageDrop{titlesec}

```
\titlelabel  {⟨label-format⟩}
2 \newcommand*{\titlelabel}[1]{}

\titleformat* {⟨command⟩} {⟨format⟩}

\titleformat {⟨command⟩} [⟨shape⟩] {⟨format⟩} {⟨label⟩} {⟨sep⟩} {⟨begfore⟩} [⟨after⟩]
3 \newcommand{\titleformat}{%
4   \@ifstar{\ttl@format@s}{%
5     {\ttl@format@i}}}
6 \newcommand{\ttl@format@s}[1]{}
7 \NewDocumentCommand{\ttl@format@i}{m o m m m o}{}
```

```
\chaptertitlename
 8 \@ifundefined{@chapapp}{\let\@chapapp\chaptename}{}%
 9 \newcommand\chaptertitlename{\@chapapp}

\titlespacing * {\langle command\rangle} {\langle left\rangle} {\langle before\rangle} {\langle after\rangle} [{\langle right\rangle}]
 10 \NewDocumentCommand{\titlespacing}{s m m m m o}{}

\filright
\filcenter
\filleft
\fillast
\filinner
\filouter
 11 \newcommand*\{\filright\}{}%
 12 \newcommand*\{\filcenter\}{}%
 13 \newcommand*\{\filleft\}{}%
 14 \newcommand*\{\fillast\}{}%
 15 \newcommand*\{\filinner\}{}%
 16 \newcommand*\{\filouter\}{}%

\wordsep
 17 \newcommand\wordsep{\fontdimen\tw@\font \oplus
 18   \fontdimen\thr@@\font \ominus \fontdimen4\font}

\titleline * [{\langle align\rangle}] {\langle material\rangle}
 19 \NewDocumentCommand{\titleline}{s o m}{}

\titlerule [{\langle height\rangle}]
 20 \providecommand*\titlerule{\@ifstar{\ttl@row}{\ttl@rule}}
 21 \newcommand*\{\ttl@rule\}[1][]{}
 22 \newcommand*\{\ttl@row\}[2][]{}

\iftitlemeasuring {\langle true\rangle} {\langle false\rangle}
\assignpagestyle {\langle command\rangle} {\langle pagestyle\rangle}
\titleclass {\langle name\rangle} [{\langle startlevel\rangle}] {\langle class\rangle} [{\langle cmd\rangle}]
 23 \newcommand{\iftitlemeasuring}[2]{#2}
 24 \newcommand{\assignpagestyle}[2]{#2}
 25 \NewDocumentCommand{\titleclass}{m o m o}
```

---

File 151 **l warp-titletoc.sty**

§ 227 Package **titletoc**

Pkg titletoc titletoc is emulated. All user options and macros are ignored and disabled.

Discard all options for l warp-titletoc:

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{titletoc}

\dottedcontents {\langle section\rangle} [{\langle left\rangle}] {\langle above\rangle} {\langle label\rangle} {\langle leader\rangle}
2 \NewDocumentCommand{\dottedcontents}{m o m m m}{}{}

\titlecontents * {\langle section\rangle} [{\langle left\rangle}] {\langle above\rangle} {\langle numbered\rangle} {\langle numberless\rangle} {\langle filler\rangle} [{\langle below\rangle} or {\langle begin\rangle}] [{\langle separator\rangle}] [{\langle end\rangle}]
3 \newcommand{\titlecontents}{\@ifstar{\ttl@tcstar}{\ttl@tcnostar}}
4 \NewDocumentCommand{\ttl@tcstar}{m o m m m o o o}{}{}
5 \NewDocumentCommand{\ttl@tcnostar}{m o m m m o}{}{}

\contentsmargin [{\langle correction\rangle}] {\langle right\rangle}
6 \newcommand{\contentsmargin}[2][]{}

\thecontentslabel
\thecontentspage
7 \newcommand*{\thecontentslabel}{\thecontentslabel}
8 \newcommand*{\thecontentspage}{\thecontentspage}

\contentslabel [{\langle format\rangle}] {\langle space\rangle}
\contentspage [{\langle format\rangle}]
9 \newcommand{\contentslabel}[2][]{\thecontentslabel}
10 \newcommand{\contentspage}[1][]{\thecontentspage}

\contentspush {\langle text\rangle}
11 \newcommand{\contentspush}[1]{}{}

\contentsuse {\langle name\rangle} {\langle text\rangle}
```

---

```

12 \newcommand{\contentsuse}[2]{}

\startcontents [name]
\stopcontents [name]
\resumecontents [name]

13 \newcommand*\startcontents[1] []
14 \newcommand*\stopcontents[1] []
15 \newcommand*\resumecontents[1] []

\printcontents [name] {prefix} {start} {code}
16 \newcommand{\printcontents}[4] []

\startlist [name] {list}
\stoplist [name] {list}
\resumelist [name] {list}

17 \newcommand{\startlist}[2] []
18 \newcommand{\stoplist}[2] []
19 \newcommand{\resumelist}[2] []

\printlist [name] {list} {prefix} {code}
20 \newcommand{\printlist}[4] []

```

---

File 152 **lwarp-titling.sty**

§ 228 Package **titling**

Pkg **titling**

**package support**

**⚠ load order**

lwarp supports the native L<sup>A</sup>T<sub>E</sub>X titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

**\published and \subtitle**

If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 52.7.

The various titling footnote restyling commands have no effect.

Pass all options to lwarp-titling:

**for HTML output:** 1 \LWR@ProvidesPackagePass{titling}

\@bsmtitleempty Patch \@bsmtitleempty:

```
2 \let\LWR@orig@bsmtitleempty@\bsmtitleempty
3 \renewcommand*{\@bsmtitleempty}{%
4 \LWR@orig@bsmtitleempty%
5 }
```

\keepthetitle Patch \keepthetitle:

```
6 \let\LWR@origkeepthetitle\keepthetitle
7 \renewcommand*{\keepthetitle}{%
8 \LWR@orig@keepthetitle%
9 }
```

\killtitle Patch \killtitle:

```
10 \let\LWR@origkilltitle\killtitle
11 \renewcommand*{\killtitle}{%
12 \LWR@orig@killtitle%
13 }
```

Env titlingpage

```
14 \renewenvironment*{titlingpage}{%
15 {%
```

Start an HTML titlepage div:

```
16 \LWR@printpendingfootnotes
17 \begin{titlepage}
```

Prepare for a custom version of \maketitle inside the titlingpage:

```
18 \LWR@maketitlesetup
19 \let\maketitle\LWR@titlingmaketitle
20 }
21 {
```

At the end of the environment, end the HTML titlepage div:

```
22 \end{titlepage}
23 }
```

Patch the pre/post title/author/date to add HTML tags, then initialize:

```
24
25 \pretitle{}
26 \posttitle{}
27
```

```
28 \preauthor{}  
29 \postauthor{}  
30  
31 \predate{}  
32 \postdate{}
```

\LWR@maketitlesetup Patches \thanks macros.

```
33 \renewcommand*{\LWR@maketitlesetup}{%
```

Redefine the footnote mark:

```
34 \def\@makefnmark{\textsuperscript{\@thefnmark}}
```

```
\thefootnote \Rightarrow \nameuse{arabic}{footnote}, or  
\thefootnote \Rightarrow \nameuse{fnsymbol}{footnote}
```

Redefine the footnote text:

```
35 \long\def\@makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```
36 \makethanksmark \LWR@orighspace{1in}
```

```
\makethanksmark \Rightarrow \thanksfootmark \Rightarrow \tamark \Rightarrow  
\@thefnmark \Rightarrow \itshape a (or similar)
```

Print the text:

```
37 ##1%  
38 }%  
39 }
```

\maketitle HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the titling package is adapted, simplified, and modified for HTML output.

```
40 \renewcommand*{\maketitle}{%
```

An HTML titlepage <div> is used for all classes.

```
41 \begin{titlepage}
```

Select which kind of footnote marks to use:

42 \@bsmarkseries

Set up special patches:

43 \LWR@maketitlesetup

Typeset the title, etc:

44 \@maketitle

Immediately generate any \thanks footnotes:

45 \@thanks

Close the HTML titlepage div:

46 \end{titlepage}

Reset the footnote counter:

47 \@bscontmark

48 }

\@maketitle Typesets the title, etc. Patched for HTML.

```

49 \DeclareDocumentCommand{\@maketitle}{}
50   \maketitlehooka
51   {
52     \LWR@stoppars\LWR@htmltag{h1}
53     \@bspretitle \@title \@bsposttitle
54     \LWR@htmltag{/h1}\LWR@startpars
55   }
56   \maketitlehookb
57   {
58     \begin{BlockClass}{author}
59     \renewcommand{\and}{%
60       \end{BlockClass}
61       \begin{BlockClass}{oneauthor}
62     }
63     \begin{BlockClass}{oneauthor}
64     \@bspreauthor \@author \@bspostauthor
65     \end{BlockClass}
66     \end{BlockClass}
67   }
68   \maketitlehookc
69   {

```

```
70      \begin{BlockClass}{titledate}
71      \@bspredate \@date \@bspostdate
72      \end{BlockClass}
73  }
74  \maketitlehookd
75 }
```

\LWR@titlingmaketitle \maketitle for use inside an HTML titlingpage environment.

```
76 \renewcommand*\LWR@titlingmaketitle{%
```

Keep pending footnotes out of the title block:

```
77 \@thanks
```

Select which kind of footnote marks to use:

```
78 \bsmarkseries
```

Set up special patches:

```
79 \LWR@maketitlesetup
```

Typeset the title, etc:

```
80 \@maketitle
```

Immediately generate any \thanks footnotes:

```
81 \@thanks
```

Reset the footnote counter:

```
82 \bscontmark
83 }
```

\thanksmarkseries {\langle series\rangle}

Sets the type of footnote marks used by \thanks, where type is ‘arabic’, ‘roman’, ‘fnsymbol’, etc.

```
84 \renewcommand{\thanksmarkseries}[1]{%
85 \def\bsmarkseries{\renewcommand{\thefootnote}{\nameuse{\#1}{footnote}}}}
86 }
```

Set default titlepage thanks footnote marks. See section 52.6.

---

```

87 \if@titlepage
88   \thanksmarkseries{arabic}
89 \else
90   \thanksmarkseries{fnsymbol}
91 \fi

```

---

File 153 **lwarf-tocbibind.sty**

§ 229      Package **tocbibind**

Pkg **tocbibind** **tocbibind** is patched for use by **lwarf**.

Opt **IndexLanguage** The **lwarf** package takes an option **IndexLanguage=english** to set the language used by **xindy**. This is passed to **xindy** using its **-L** option, and is used for both index and glossary generation.

⚠ **tocloft & other packages** If using **tocloft** with **tocbibind**, **anonchap**, **fncychap**, or other packages which change chapter title formatting, load **tocloft** with its **titles** option, which tells **tocloft** to use standard **L<sup>A</sup>T<sub>E</sub>X** commands to create the titles, allowing other packages to work with it.

**placement and toc options** An index may be placed inline with other HTML text, or on its own HTML page:

**Inline, with a manual TOC entry:**

A commonly-used method to introduce an index in a **L<sup>A</sup>T<sub>E</sub>X** document:

```

\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname} or chapter
\printindex

```

**On its own HTML page, with a manual TOC entry:**

```

\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname} or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex

```

**Inline, with an automatic TOC entry:**

Pkg **tocbibind** The **tocbibind** package may be used to automatically place an entry in the TOC.

---

```
\usepackage[nottoc]{tocbibind}
...
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex
```

**On its own HTML page, with an automatic TOC entry:**

```
\usepackage[nottoc]{tocbibind}
...
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex
```

**Opt tocbibind numindex** Use the `tocbibind numindex` option to generate a numbered index. Without this option, the index heading has no number.

**for HTML output:**

```
1 \let\simplechapterdelim\relax
2
3 \LWR@ProvidesPackagePass{tocbibind}

4 \renewenvironment{theindex}%
5 {%
6   \if@bibchapter
7     \if@donumindex
8       \chapter{\indexname}
9     \else
10    \if@dotocind
11      \chapter*{\indexname}
12      \addcontentsline{toc}{chapter}{\indexname}
13    \else
14      \chapter*{\indexname}
15    \fi
16  \fi
17 \else
18   \if@donumindex
19     \section{\indexname}
20   \else
21     \if@dotocind
22       \section*{\indexname}
23       \addcontentsline{toc}{\@tocextra}{\indexname}
24     \else
25       \section*{\indexname}
26     \fi
27   \fi
28 \fi
29 \let\item\LWR@indexitem%
30 \let\subitem\LWR@indexsubitem%
31 \let\subsubitem\LWR@indexsubsubitem%
```

---

32 }

The following code is shared by anonchap.

```

33 \renewcommand{\simplechapter}[1][\@empty]{%
34     \def\@chapcntformat##1{%
35         #1\csname the##1\endcsname\simplechapterdelim\protect\quad\%
36     }%
37 }%
38
39 \renewcommand{\restorechapter}{%
40 \let\@chapcntformat\@seccntformat%
41 }

```

---

File 154 **lwarf-tocloft.sty**

§ 230 Package **tocloft**

Pkg **tocloft** tocloft is emulated. Most user options and macros are ignored and disabled. `\newlistof` and `\cftchapterprecis` are supported.

⚠ **tocloft & other packages** If using tocloft with tocibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard L<sup>A</sup>T<sub>E</sub>X commands to create the titles, allowing other packages to work with it.

Discard all options for lwarf-tocloft:

**for HTML output:** 1 \LWR@ProvidesPackageDrop{tocloft}

```

\tocloftpagestyle {\langle style\rangle}
2 \newcommand{\tocloftpagestyle}[1] {}

\cftmarktoc
\cfttoctitlefont
\cftaftertoctitle

3 \newcommand*\cftmarktoc{}%
4 \newcommand*\cfttoctitlefont{}%
5 \newcommand*\cftaftertoctitle{}%

6 \newlength{\cftbeforetoctitleskip}
7 \newlength{\cftaftertoctitleskip}

```

```
\cftmarklof
\cftloftitlefont
\cftafterloftitle
 8 \newcommand*{\cftmarklof}={}
 9 \newcommand*{\cftloftitlefont}={}
10 \newcommand*{\cftafterloftitle}={}

11 \newlength{\cftbeforeloftitleskip}
12 \newlength{\cftafterloftitleskip}

\cftmarklot
\cftlottitlefont
\cftafterlottitle
13 \newcommand*{\cftmarklot}={}
14 \newcommand*{\cftlottitlefont}={}
15 \newcommand*{\cftafterlottitle}={}

16 \newlength{\cftbeforelottitleskip}
17 \newlength{\cftafterlottitleskip}

\cftdot
\cftdotsep
\cftnodots
18 \newcommand*{\cftdot}{.}
19 \providecommand*{\cftdotsep}{1}
20 \newcommand*{\cftnodots}{5000}

\cftdotfill {⟨sep⟩}
21 \providecommand{\cftdotfill}[1] {}

\cftsetpnumwidth {⟨length⟩}
\cftsetrmarg {⟨length⟩}
22 \newcommand*{\cftsetpnumwidth}[1]{}
23 \newcommand*{\cftsetrmarg}[1]{}

\cftpnumalign {⟨alignment⟩}
24 \newcommand*{\cftpnumalign}[1]{}

25 \newlength{\cftparskip}
```

```
26 \newlength{\cftbeforepartskip}
27 \newlength{\cftpartindent}
28 \newlength{\cftpartnumwidth}
29 \newcommand*\cftpartfont{}
30 \newcommand*\cftpartpresnum(){}
31 \newcommand*\cftpartaftersnum(){}
32 \newcommand*\cftpartaftersnumb(){}
33 \newcommand*\cftpartleader(){}
34 \newcommand*\cftpartdotsep{1}
35 \newcommand*\cftpartpagefont){}
36 \newcommand*\cftpartafterpnum{}


37 \newlength{\cftbeforechapskip}
38 \newlength{\cftchapindent}
39 \newlength{\cftchapnumwidth}
40 \newcommand*\cftchapfont{}
41 \newcommand*\cftchappresnum(){}
42 \newcommand*\cftchapaftersnum){}
43 \newcommand*\cftchapaftersnumb){}
44 \newcommand*\cftchapleader){}
45 \newcommand*\cftchapdotsep{1}
46 \newcommand*\cftchappagefont){}
47 \newcommand*\cftchapafterpnum{}


48 \newlength{\cftbeforesecskip}
49 \newlength{\cftsecindent}
50 \newlength{\cftsecnumwidth}
51 \newcommand*\cftsecfont{}
52 \newcommand*\cftsecpresnum){}
53 \newcommand*\cftsecaftersnum}{}
54 \newcommand*\cftsecaftersnumb}{}
55 \newcommand*\cftsecleader){}
56 \newcommand*\cftsecdotsep{1}
57 \newcommand*\cftsecpagefont){}
58 \newcommand*\cftsecafterpnum{}


59 \newlength{\cftbeforesubsecskip}
60 \newlength{\cftsubsecindent}
61 \newlength{\cftsubsecnumwidth}
62 \newcommand*\cftsubsecfont){}
63 \newcommand*\cftsubsecpresnum){}
64 \newcommand*\cftsubsecaftersnum}{}
65 \newcommand*\cftsubsecaftersnumb}{}
66 \newcommand*\cftsubsecleader){}
67 \newcommand*\cftsubsecdotsep{1}
68 \newcommand*\cftsubsecpagefont){}
69 \newcommand*\cftsubsecafterpnum{}


70 \newlength{\cftbeforesubsubsecskip}
```

```
71 \newlength{\cftsubsubsecindent}
72 \newlength{\cftsubsubsecnumwidth}
73 \newcommand*{\cftsubsubsecfont}{}%
74 \newcommand*{\cftsubsubsecpresnum}{}%
75 \newcommand*{\cftsubsubsecaftersnum}{}%
76 \newcommand*{\cftsubsubsecaftersnumb}{}%
77 \newcommand*{\cftsubsubsecleader}{}%
78 \newcommand*{\cftsubsubsecdotsep}{1}%
79 \newcommand*{\cftsubsubsecpagefont}{}%
80 \newcommand*{\cftsubsubsecafterpnum}{}%

81 \newlength{\cftbeforeparaskip}
82 \newlength{\cftpaiindent}
83 \newlength{\cftpnumwidth}
84 \newcommand*{\cftpafont}{}%
85 \newcommand*{\cftparapresnum}{}%
86 \newcommand*{\cftparaftersnum}{}%
87 \newcommand*{\cftparaftersnumb}{}%
88 \newcommand*{\cftparaleader}{}%
89 \newcommand*{\cftparadotsep}{1}%
90 \newcommand*{\cftparapagefont}{}%
91 \newcommand*{\cftparaafterpnum}{}%

92 \newlength{\cftbeforesubparaskip}
93 \newlength{\cftsubparaindent}
94 \newlength{\cftsubparanumwidth}
95 \newcommand*{\cftsubparafont}{}%
96 \newcommand*{\cftsubparapresnum}{}%
97 \newcommand*{\cftsubparaftersnum}{}%
98 \newcommand*{\cftsubparaftersnumb}{}%
99 \newcommand*{\cftsubparaleader}{}%
100 \newcommand*{\cftsubparadotsep}{1}%
101 \newcommand*{\cftsubparapagefont}{}%
102 \newcommand*{\cftsubparaafterpnum}{}%

103 \newlength{\cftbeforfigskip}
104 \newlength{\cftfigindent}
105 \newlength{\cftfignumwidth}
106 \newcommand*{\cftfigfont}{}%
107 \newcommand*{\cftfigpresnum}{}%
108 \newcommand*{\cftfigaftersnum}{}%
109 \newcommand*{\cftfigaftersnumb}{}%
110 \newcommand*{\cftfigleader}{}%
111 \newcommand*{\cftfigdotsep}{1}%
112 \newcommand*{\cftfigpagefont}{}%
113 \newcommand*{\cftfigafterpnum}{}%

114 \newlength{\cftbeforesubfigskip}
115 \newlength{\cftsubfigindent}
```

```

116 \newlength{\cftsubfignumwidth}
117 \newcommand*{\cftsubfigfont}{}}
118 \newcommand*{\cftsubfigpresnum}{}}
119 \newcommand*{\cftsubfigaftersnum}{}}
120 \newcommand*{\cftsubfigaftersnumb}{}}
121 \newcommand*{\cftsubfigleader}{}}
122 \newcommand*{\cftsubfigdotsep}{1}
123 \newcommand*{\cftsubfigpagefont}{}}
124 \newcommand*{\cftsubfigafterpnum}{}}

125 \newlength{\cftbeforetabskip}
126 \newlength{\cfttabindent}
127 \newlength{\cfttabnumwidth}
128 \newcommand*{\cfttabfont}{}}
129 \newcommand*{\cfttabpresnum}{}}
130 \newcommand*{\cfttabaftersnum}{}}
131 \newcommand*{\cfttabaftersnumb}{}}
132 \newcommand*{\cfttableader}{}}
133 \newcommand*{\cfttabdotsep}{1}
134 \newcommand*{\cfttabpagefont}{}}
135 \newcommand*{\cfttabafterpnum}{}}

136 \newlength{\cftbeforesubtabskip}
137 \newlength{\cftsubtabindent}
138 \newlength{\cftsubtabnumwidth}
139 \newcommand*{\cftsubtabfont}{}}
140 \newcommand*{\cftsubtabpresnum}{}}
141 \newcommand*{\cftsubtabaftersnum}{}}
142 \newcommand*{\cftsubtabaftersnumb}{}}
143 \newcommand*{\cftsubtableader}{}}
144 \newcommand*{\cftsubtabdotsep}{1}
145 \newcommand*{\cftsubtabpagefont}{}}
146 \newcommand*{\cftsubtabafterpnum}{}}

147 \newcommand{\cftsetindents}[3] {}

148 \newcommand{\pagenumbersoff}[1]{}
149 \newcommand{\pagenumberson}[1]{}

\newlistof [⟨within⟩] {⟨type⟩} {⟨ext⟩} {⟨listofname⟩}
Emulated through the \newfloat mechanism.

150 \NewDocumentCommand{\newlistof}{o m m}
151 {%
152 \IfValueTF{#1}{%
153 {\newfloat{#2}{tbp}{#3}{#1}}%
154 {\newfloat{#2}{tbp}{#3}}%
155 \namedef{listof#2}{\listof{#2}{#4}}}

```

```

156 \@namedef{#2depth}{1}
157 \expandafter\newlength\csuse{cftbefore#2skip}
158 \expandafter\newlength\csuse{cft#2indent}
159 \expandafter\newlength\csuse{cft#2numwidth}
160 \@namedef{cft#2font}={}
161 \@namedef{cft#2presnum}={}
162 \@namedef{cft#2aftersnum}={}
163 \@namedef{cft#2aftersnumb}={}
164 \@namedef{cft#2leader}={}
165 \@namedef{cft#2dotsep}{1}
166 \@namedef{cft#2pagefont}={}
167 \@namedef{cft#2afterpnum}={}
168 }

```

\cftchapterprecis from tocloft:

```

169 \newcommand{\cftchapterprecis}[1]{%
170   \cftchapterprecishere{#1}
171   \cftchapterprecistoc{#1}}
172 \newcommand{\cftchapterprecishere}[1]{%
173   \begin{quote}\textit{#1}\end{quote}}
174 \newcommand{\cftchapterprecistoc}[1]{%
175   \addtocontents{toc}{%
176     \protect\begin{quote}#1\protect\end{quote}}}
177   }
178 }
179 }

```

File 155 **lwarf-transparent.sty**

## § 231 Package **transparent**

(Based on original code by HEIKO OBERDIEK.)

Pkg **transparent** Emulated. `\texttransparent` works for inline objects. `\transparent` only works for `\includegraphics`.

⚠ Not **X<sub>E</sub>T<sub>E</sub>X**: Note that `transparent` does not work with X<sub>E</sub>T<sub>E</sub>X.

**for HTML output:** Discard all options for lwarf-transparent:

```

1 \LWR@ProvidesPackageDrop{transparent}

2 \newcommand*{\transparent}[1]{\edef\LWR@opacity{#1}}
3
4 \newcommand*{\texttransparent}[2]{%
5 \begingroup%

```

---

```

6 \transparent{#1}%
7 \InlineClass[opacity: #1]{transparent}{#2}%
8 \endgroup%
9 }

```

---

File 156 **lwarp-trivfloat.sty**

§ 232 Package **trivfloat**

**Pkg trivfloat** trivfloat is forced to use the built-in lwarp emulation for floats.

Discard all options for lwarp-trivfloat. This tells trivfloat not to use floatrow or memoir.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{trivfloat}  
2 \LWR@origRequirePackage{trivfloat}

**for HTML & PRINT:** 3 \begin{warpall}

To create a new float type and change its name:

---

```

\trivfloat{example}
\renewcommand{\examplename}{Example Name}
\crefname{example}{example}{examples}
\Crefname{example}{Example}{Examples}

```

---

4 \end{warpall}

**\tfl@chapter@fix** Nullified at the beginning of the document. Is used by trivfloat to correct float chapter numbers, but is not needed for lwarp.

**for HTML output:** 5 \begin{warpHTML}

6 \AtBeginDocument{\DeclareDocumentCommand{\tfl@chapter@fix}{m m}{}}

7 \end{warpHTML}

### § 232.1 Combining `\newfloat`, `\trivfloat`, and `algorithmicx`

**for HTML & PRINT:** 8 `\begin{warpall}`

For both print and HTML output:

- ⚠ When using float, trivfloat, or algorithmicx at the same time, be aware of conflicting file usage. algorithmicx uses .loa. trivfloat by default starts with .loa and goes up for additional floats, skipping .lof and .lot.
- ⚠ When using `\newfloat`, be sure to manually assign higher letters to the `\newfloat` files to avoid .loa used by algorithmicx, and any files used by trivfloat. Also avoid using .lof and .lot.
- ⚠ When using `\trivfloat`, you may force it to avoid conflicting with algorithmicx by starting trivfloat's file extensions with .lob:

---

```
\makeatletter
\setcounter{tfl@float@cnt}{1} % start trivfloats with .lob
\makeatletter
```

---

9 `\end{warpall}`

---

File 157 **lwarf-typearea.sty**

### § 233 Package **typearea**

Pkg `typearea` typearea is emulated.

**for HTML output:** 1 `\LWR@ProvidesPackageDrop{typearea}`

```
2 \newcommand*\typearea[2][\z@]{}
3 \newcommand*\recalctypearea(){}
4 \@ifundefined{footheight}{\newlength\footheight}{}
5 \newcommand*\areaset[3][\z@]{}
```

---

File 158 **lwarf-ulem.sty**

### § 234 Package **ulem**

(Based on original code by DONALD ARSENEAU.)

Pkg ulem Emulated.

**for HTML output:** Original \warp definitions:

```
1 \LetLtxMacro{\LWR@ulemorig}{\emph}
2 \LetLtxMacro{\LWR@ulemorigtextbf}{\textbf}
```

Basic markup commands, using css:

```
3 \NewDocumentCommand{\uline}{+m}{%
4 \InlineClass{uline}{#1}%
5 }%
6
7 \NewDocumentCommand{\uuline}{+m}{%
8 \InlineClass{uuline}{#1}%
9 }%
10
11 \NewDocumentCommand{\uwave}{+m}{%
12 \InlineClass{uwave}{#1}%
13 }%
14
15 \NewDocumentCommand{\sout}{+m}{%
16 \InlineClass{sout}{#1}%
17 }%
18
19 \NewDocumentCommand{\xout}{+m}{%
20 \InlineClass{xout}{#1}%
21 }%
22
23 \NewDocumentCommand{\dashuline}{+m}{%
24 \InlineClass{dashuline}{#1}%
25 }%
26
27 \NewDocumentCommand{\dotuline}{+m}{%
28 \InlineClass{dotuline}{#1}%
29 }
```

Nullified parameters:

```
30 \NewDocumentCommand{\ULthickness}{}{%
31 \newlength{\ULdepth}}
```

Nullified/emulated macros:

```
32 \NewDocumentCommand{\markoverwith}{m}{%
33 \NewDocumentCommand{\ULon}{+m}{\uline{#1}\egroup}
```

\useunder only works with \textbf, etc, but not \bfseries, etc.

---

```

34 \NewDocumentCommand{\useunder}{m m m}{%
35 \relax%
36 \ifx\relax#3\relax\else % argumentative command
37   \def#3{#1}\MakeRobust{#3}%
38 }

```

Triggered by package options, also available for the users:

```

39 \newcommand*{\normalem}{\LetLtxMacro{\emph}{\LWR@ulemorigemph}}
40 \newcommand*{\ULforem}{\LetLtxMacro{\emph}{\underline}}
41 \ULforem% default

```

Package options:

```

42 \DeclareOption{normalem}{\normalem}
43 \DeclareOption{ULforem}{\ULforem}
44 \DeclareOption{normalbf}{}
45 \DeclareOption{UWforbf}{\useunder{\uwave}{\bf}{\textbf}}

```

Emulate the original package:

```
46 \LWR@ProvidesPackageDrop{ulem}
```

---

#### File 159 **lwarf-upref.sty**

#### § 235 Package **upref**

Pkg **upref** Ignored.

**for HTML output:** Discard all options for lwarf-upref:

```
1 \LWR@ProvidesPackageDrop{upref}
```

---

#### File 160 **lwarf-verse.sty**

#### § 236 Package **verse**

(Based on original code by PETER WILSON.)

Pkg **verse** **verse** is supported and patched by lwarf.

**for HTML output:** Pass all options for lwarf-verse:

```
1 \LWR@ProvidesPackagePass{verse}
```

- \attrib The documentation for the `verse` and `memoir` packages suggest defining an `\attrib` command, which may already exist in current documents, but it will only work for print output. `lwarp` provides `\attribution`, which works for both print and `HTML` output. To combine the two so that `\attrib` is used for print and `\attribution` is used for `HTML`:

---

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

---

- Len \leftskip These lengths are used by `verse` and `memoir` to control the left margin, and they  
 Len \leftmargini may already be set by the user for print output. New lengths `\HTMLvleftskip` and  
 Len \TMLvleftskip `\HTMLleftmargini` are provided to control the margins in `HTML` output. These new  
 Len \TMLleftmargini lengths may be set by the user before any `verse` environment, and persist until they  
 are manually changed again. One reason to change `\HTMLleftmargini` is if there  
 is a wide `\flagverse` in use, such as the word “Chorus”, in which case the value of  
`\HTMLleftmargini` should be set to a wide enough length to contain “Chorus”. The  
 default is wide enough for a stanza number.

Horizontal spacing relies on `pdftotext`'s ability to discern the layout (`-layout` option) of the text in the `HTML`-tagged PDF output. For some settings of `\HTMLleftmargini` or `\HTMLvleftskip` the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

- Env `verse` The `verse` environment will be placed inside a `HTML pre`.

```
2 \AfterEndPreamble{
3 \LWR@traceinfo{Patching verse.}
```

At the beginning of the `verse` environment:

```
4 \AtBeginEnvironment{verse}
5 {%
```

- Pkg `verse` The `verse` or `memoir` packages can place stanza numbers to the left with their  
 Pkg `memoir` `\flagverse`  
 Len \leftskip `\flagverse` command. Do not allow them to go into the left margin, which would  
 cause `pdfcrop` to crop the entire page further to the left:
- ```
6 \ifdef{\vleftskip}{%
7 \setlength{\vleftskip}{\HTMLvleftskip}
8 \setlength{\leftmargini}{\HTMLleftmargini}
9 }{%
10 \LWR@forcenewpage
```

---

```

11 \LWR@atbeginverbatim{verse}
12 \unskip\LWR@origvspace{-\baselineskip}
13 }

```

After the end of the `verse` environment, which places the `pre` tag at the regular left margin:

```

14 \AfterEndEnvironment{verse}{
15 \unskip\LWR@origvspace{-\baselineskip}
16 \LWR@afterendverbatim
17 }

```

Patch to place `poemtitle` inside an HTML span of class `poemtitle`:

```

18 \ifdef{\poemtitle}{%
19 \DeclareDocumentCommand{\vstypepoemtitle}{m}{%
20   \vspace{\beforepoemtitleskip}%
21   {\InlineClass{poemtitle}{\poemtitlefont #1}\par}%
22   \vspace{\afterpoemtitleskip}%
23 }
24 }{}%
25
26 }% AfterEndPreamble

```

---

File 161 `lwarf-wallpaper.sty`

## § 237 Package **Wallpaper**

Pkg `wallpaper` `wallpaper` is emulated during HTML output, and the `wallpaper` package is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{wallpaper}

2 \newcommand*\CenterWallPaper[2]{}
3 \newcommand*\ThisCenterWallPaper[2]{}
4 \newcommand*\TileWallPaper[3]{}
5 \newcommand*\ThisTileWallPaper[3]{}
6 \newcommand*\TileSquareWallPaper[2]{}
7 \newcommand*\ThisTileSquareWallPaper[2]{}
8 \newcommand*\ULCornerWallPaper[2]{}
9 \newcommand*\ThisULCornerWallPaper[2]{}
10 \newcommand*\LLCornerWallPaper[2]{}
11 \newcommand*\ThisLLCornerWallPaper[2]{}
12 \newcommand*\URCornerWallPaper[2]{}
13 \newcommand*\ThisURCornerWallPaper[2]{}
14 \newcommand*\LRCornerWallPaper[2]{}
15 \newcommand*\ThisLRCornerWallPaper[2]{}

```

```
16 \newcommand*\ClearWallPaper{}{}  
17 \newlength{\wpXoffset}  
18 \newlength{\wpYoffset}
```

---

File 162 l warp-wrapfig.sty

§ 238 Package **wrapfig**

Pkg wrapfig wrapfig is emulated during HTML output, and the wrapfig package is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{wrapfig}  
  
Computed width of a wrapped object. Used to print the HTML style.  
  
2 \newlength{\LWR@wrapwidth}  
  
3 \newcommand*\LWR@wrapposition{}{}  
4  
5 \newcommand*\LWR@subwrapfigure}[2]{%  
6 \LWR@maybeinthisfloat%  
7 \renewcommand*\LWR@wrapposition{}%  
8 \ifthenelse{  
9     \equal{#1}{r}\OR\equal{#1}{R}\OR%  
10    \equal{#1}{o}\OR\equal{#1}{O}%  
11 }%  
12 {\renewcommand*\LWR@wrapposition{float:right}}%  
13 {\renewcommand*\LWR@wrapposition{float:left}}%  
14 \setlength{\LWR@wrapwidth}{#2}%  
15 \addtolength{\LWR@wrapwidth}{4em}%  
16 \uselengthunit{PT}%  
17 \LWR@forcenewline  
18 \LWR@stoppars%  
19 \LWR@htmntag{div class="marginblock" id="autofloat-\arabic{\LWR@thisfloat}"  
20 style="width:\rndprintlength{\LWR@wrapwidth} ; "%  
21 \LWR@wrapposition"}%  
22 }%  
23 \LWR@startpars  
24 }  
25  
26  
27 \NewDocumentEnvironment{wrapfigure}{o m o m}  
28 {  
29 \LWR@subwrapfigure[#2]{#4}%  
30 \captionsetup{type=figure}%  
31 }  
32 {  
33 \LWR@htmldivclassend{div}
```

---

```

34 }
35
36
37 \NewDocumentEnvironment{wraptable}{o m o m}
38 {%
39 \LWR@subwrapfigure{#2}{#4}%
40 \captionsetup{type=table}%
41 }
42 {%
43 \LWR@htmldivclassend{div}
44 }
45
46
47 \NewDocumentEnvironment{wrapfloat}{m o m o m}
48 {%
49 \LWR@subwrapfigure{#3}{#5}%
50 \captionsetup{type=#1}%
51 }
52 {%
53 \LWR@htmldivclassend{div}
54 }
55
56 \newlength{\wrapoverhang}

```

---

File 163 **lwarf-xcolor.sty**

§ 239 Package **xcolor**

Pkg **xcolor** xcolor is supported by lwarf.

**\colorboxBlock and \fcolorboxBlock** \colorboxBlock and \fcolorboxBlock are provided for increased HTML compatibility, and they are identical to \colorbox and \fcolorbox in print mode. In HTML mode they place their contents into a <div> instead of a <span>. These <div>s are set to display: inline-block so adjacent \colorboxBlocks appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for \colorboxBlock and \fcolorboxBlock are created by lwarf's core if xcolor is loaded.

**background: none** \fcolorbox and \fcolorboxBlock allow a background color of none, in which case only the frame is drawn, which can be useful for HTML.

**color support** Color definitions, models, and mixing are fully supported without any changes required.

**tables** Colored tables are ignored so far. Use css to style tables.

colored text and boxes	\textcolor, \colorbox, and \fcolorbox are supported.
\color and \pagecolor	\color and \pagecolor are ignored. Use css or \textcolor where possible.

### § 239.1 Xcolor definitions: location and timing

The l warp core and its l warp-xcolor package are tightly integrated to allow comparable results for print, HTML and print inside an HTML lateximage. This requires a number of definitions and redefinitions depending on whether each of xcolor and lateximage is being used, and whether print or HTML is being generated. Some of these actions are one-time when xcolor is loaded, and others are temporary as lateximage is used.

**When xcolor is loaded in print mode:** No special actions are taken at the time that xcolor is loaded in print mode, but see \AtBeginDocument below.

**When l warp-xcolor is loaded in HTML mode:** xcolor's original definitions are saved for later restoration. \LWR@restoreorigformatting is appended to restore these definitions for use inside a lateximage. New HTML-mode definitions are created for \textcolor, \pagecolor, \nopagecolor, \colorbox, \colorboxBlock, \fcolorbox, \fcolorboxBlock, and fcolorminipage.

**\AtBeginDocument in print or HTML mode:** See Section 68.1. If xcolor has been loaded, the print-mode \fcolorbox is modified to accept a background color of none, and additional definitions are created for l warp's new macros print-mode macros \colorboxBlock, \fcolorboxBlock, and fcolorminipage. The HTML versions of these macros will already have been created by l warp-xcolor if it has been loaded.

For use inside an HTML lateximage, \LWR@restoreorigformatting is appended to temporarily set these functions to their print-mode versions.

**In a lateximage in HTML mode:** \LWR@restoreorigformatting temporarily restores the print-mode definitions of xcolor's functions. See \LWR@restoreorigformatting on page 340.

\color:

**Print:** Used as-is.

**HTML:** Ignored by pdftotext, and will not appear.

**HTML lateximage:** Colors will appear in a lateximage.

\textcolor:

**Print:** Used as-is.

**HTML:** Redefined by l warp-xcolor, page 570.

**HTML lateximage:** Remembers and reuses the print version.

\pagecolor:

**Print:** Used as-is.

**HTML:** Ignored.

**HTML lateximage:** Colors will be picked up in a `lateximage`.

\nopagecolor:

**Print:** Used as-is.

**HTML:** Ignored.

**HTML lateximage:** Colors will be picked up in a `lateximage`.

\colorbox:

**Print:** Used as-is.

**HTML:** Redefined by `lwarp-xcolor`, page [570](#).

**HTML lateximage:** Remembers and reuses the print version.

\colorboxBlock:

**Print:** Becomes \colorbox.

**HTML:** Newly defined by `lwarp-xcolor` to use a `<div>`, page [571](#).

**HTML lateximage:** Remembers and reuses the print version \colorbox.

\fcolorbox:

**Print:** Modified to allow a background of `none`.

  \WRprint@fcolorbox at section [68.1](#)

**HTML:** Redefined by `lwarp-xcolor`, page [571](#).

**HTML lateximage:** Remembers and reuses the print version.

\fcolorboxBlock:

**Print:** Becomes \fcolorbox. Section [68.1](#)

**HTML:** Newly defined by `lwarp-xcolor` to use a `<div>`, page [572](#).

**HTML lateximage:** Remembers and reuses the print version \fcolorbox.

fcolorminipage:

**Print:** Newly defined in the `lwarp` core.

  \WRprint@fcolorminipage at section [68.1](#)

**HTML:** Newly defined by `lwarp-xcolor`, page [572](#).

**HTML lateximage:** Uses the print version.

\boxframe:

**Print:** Used as-is.

**HTML:** Redefined by `lwarp-xcolor`, page [573](#).

**HTML lateximage:** Remembers and reuses the print version.

## § 239.2 Code

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{xcolor}
2 \begin{warpHTML}
```

Remember the following print-mode actions to be restored when inside a `lateximage` environment:

```

3 \LetLtxMacro{\LWRprint@textcolor}{\textcolor}
4 \LetLtxMacro{\LWRprint@pagecolor}{\pagecolor}
5 \LetLtxMacro{\LWRprint@nopagecolor}{\nopagecolor}
6 \LetLtxMacro{\LWRprint@colorbox}{\colorbox}
7 \LetLtxMacro{\LWRprint@colorboxBlock}{\colorbox}
8 \LetLtxMacro{\LWRorigprint@fcolorbox}{\fcolorbox}
9 \LetLtxMacro{\LWRorigprint@fcolorboxBlock}{\fcolorbox}
10 \LetLtxMacro{\LWRorigprint@boxframe}{\boxframe}
```

`\LWR@restoreorigformatting` Inside a `lateximage` the following gets restored to their print-mode actions:

```

11 \appto{\LWR@restoreorigformatting}{%
12 \LetLtxMacro{\textcolor}{\LWRprint@textcolor}%
13 \LetLtxMacro{\pagecolor}{\LWRprint@pagecolor}%
14 \LetLtxMacro{\nopagecolor}{\LWRprint@nopagecolor}%
15 \LetLtxMacro{\colorbox}{\LWRprint@colorbox}%
16 \LetLtxMacro{\fcolorbox}{\LWRprint@fcolorbox}%
17 \LetLtxMacro{\boxframe}{\LWRorigprint@boxframe}%
18 }
```

`\LWR@tempcolor` The color converted to HTML colorspace.

```

19 \newcommand*{\LWR@tempcolor}{}%
20 \newcommand*{\LWR@tempcolortwo}{}%
```

`\LWR@colorstyle` {<1: styletext>} {<2: model>} {<3: color>}

For a color style, prints the color converted to HTML colors.

```

21 \NewDocumentCommand{\LWR@colorstyle}{m m}{%
22 \begingroup%
23 \LWR@FBcancel%
```

Use the `xcolor` package to convert to an HTML color space:

```
24 \convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
```

Print the converted color:

```

25 \#\LWR@tempcolor%
26 \endgroup%
27 }
```

---

\LWR@borderpadding {*colorstyle*} {*color*} Prints the `HTML` attributes for a black border and padding.  
 \LWR@forceminwidth must be used first in order to set the border width.

```
28 \newcommand*{\LWR@borderpadding}[2]{%
29 \uselengthunit{PT}%
30 border:\rndprintlength{\LWR@atleastonept} solid \LWR@colorstyle{#1}{#2} ; %
31 padding:\rndprintlength{\fboxsep}%
32 }
```

\color \color appears in the `LATEX` PDF output, but is ignored by `pdftotext` and thus is ignored in the `HTML` file. Text styling by local group is not yet supported.

Each of the following macros is given a temporary name, and is \let to the final name once the `HTML` conversion starts.

\textcolor [*model*] {*color*} {*text*}

Converted into an `HTML` hex color span.

```
33 \RenewDocumentCommand{\textcolor}{O{named} m m}{%
34 \begingroup%
35 \LWR@FBcancel%
36 \convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
37 \InlineClass[color:\LWR@colorstyle{#1}{#2}]{textcolor}{%
38 \renewcommand*{\LWR@currenttextcolor}{\#\LWR@tempcolor}%
39 #3%
40 }%
41 \endgroup%
42 }
```

\pagecolor [*model*] {*color*}

Ignored. Use \CSSFilename instead.

```
43 \renewcommand*{\pagecolor}[2][named]{}
```

\nopagecolor Ignored.

```
44 \let\nopagecolor\relax
```

\colorbox [*model*] {*color*} {*text*}

Converted into an `HTML` hex background color <span>.

```
45 \RenewDocumentCommand{\colorbox}{O{named} m +m}{%
```

```

46 \begingroup%
47 \LWR@FBcancel%
48 \uselengthunit{PT}%
49 \InlineClass[%]
50 background:\LWR@colorstyle{\#1}{\#2} ; %
51 padding:\rndprintlength{\fboxsep}%
52 ]{\colorbox}{\#3}%
53 \endgroup%
54 }

```

\colorboxBlock [*model*] {*color*} {*text*}

Converted into an HTML hex background color <div>.

```

55 \NewDocumentCommand{\colorboxBlock}{O{named} m +m}{%
56 \begingroup%
57 \LWR@FBcancel%
58 \uselengthunit{PT}%
59 \begin{BlockClass}[%]
60 background:\LWR@colorstyle{\#1}{\#2} ; %
61 padding:\rndprintlength{\fboxsep}%
62 ]{\colorboxBlock}
63 \#3
64 \end{BlockClass}%
65 \endgroup%
66 }

```

\fcolorbox [*framemodel*] {*framecolor*} [*boxmodel*] {*boxcolor*} {*text*}

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```

67 \RenewDocumentCommand{\fcolorbox}{O{named} m O{named} m +m}{%
68 \LWR@traceinfo{HTML fcolorbox #2 #4}%
69 \begingroup%
70 \LWR@FBcancel%
71 \uselengthunit{PT}%
72 \LWR@forceminwidth{\fboxrule}%
73 \ifthenelse{\equal{\#4}{none}}{%
74 % no background color
75 \InlineClass[%]
76 \LWR@borderpadding{\#1}{\#2}%
77 ]{\fcolorbox}{\#5}%
78 }%
79 % yes background color
80 \InlineClass[%]

```

```

81      \LWR@borderpadding{#1}{#2} ; %
82      background:\LWR@colorstyle{#3}{#4}%
83      ]{fcolorbox}{#5}%
84 }%
85 \endgroup%
86 }

```

\fcolorboxBlock [*framemode*] {*framecolor*} [*boxmode*] {*boxcolor*} {*text*}

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```

87 \NewDocumentCommand{\fcolorboxBlock}{O{named} m O{named} m +m}{%
88 \LWR@traceinfo{HTML fcolorboxBlock #2 #4}%
89 \begingroup%
90 \LWR@FBcancel%
91 \uselengthunit{PT}%
92 \LWR@forceminwidth{\fboxrule}%
93 \ifthenelse{\equal{#4}{none}}{%
94 {%
95   \begin{BlockClass}[%
96     \LWR@borderpadding{#1}{#2}%
97   ]{fcolorboxBlock}%
98   #5
99   \end{BlockClass}%
100 }%
101 {%
102   \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
103   \begin{BlockClass}[%
104     background:\#\LWR@tempcolortwo; %
105     \LWR@borderpadding{#1}{#2}%
106   ]{fcolorboxBlock}%
107   #5
108   \end{BlockClass}%
109 }%
110 \endgroup%
111 \LWR@traceinfo{HTML fcolorboxBlock done}%
112 }

```

Creates a framed HTML <div> around its contents.

A print-output version is defined in the l warp core: section 68.1

```

\LWR@subfcolorminipage {framemode} {framecolor} {background tag} {height}%
113 \NewDocumentCommand{\LWR@subfcolorminipage}{m m m}{%
114 \begin{BlockClass}[%

```

```

115 #3%
116 \LWR@borderpadding{#1}{#2} ; %
117 \IfValueT{#4}{height:\rndprintlength{\LWR@tempheight} ; }%
118 width:\rndprintlength{\LWR@tempwidth}%
119 ] {fcolorminipage}%
120 }

Env fcolorminipage [<1:framemode>] [<2:framecolor>] [<3:boxmodel>] [<4:boxcolor>] [<5:align>] [<6:height>]
[<7:inner-align>] [<8:width>]

121 \NewDocumentEnvironment{fcolorminipage}{O{named} m O{named} m O{c} o o m}
122 {%
123 \LWR@FBcancel%
124 \setlength{\LWR@tempwidth}{#8}%
125 \IfValueT{#6}{\setlength{\LWR@tempheight}{#6}}%
126 \uselengthunit{PT}%
127 \LWR@forceminwidth{\fboxrule}%
128 \convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
129 \ifthenelse{\equal{#4}{none}}%
130 {\LWR@subfcolorminipage{#1}{#2}{}{#6}}%
131 {%
132   \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
133   \LWR@subfcolorminipage{#1}{#2}{background:\#\LWR@tempcolortwo\ ; }{#6}%
134 }%
135 }
136 {\end{BlockClass}}

```

\boxframe {*<width>*} {*<height>*} {*<depth>*}

The depth is added to the height, but the box is not descended below by the depth.  
\textcolor is honored.

```

137 \renewcommand*{\boxframe}[3]{%
138 {%
139 \setlength{\LWR@tempwidth}{#1}%
140 \setlength{\LWR@tempheight}{#2}%
141 \addtolength{\LWR@tempheight}{#3}%
142 \uselengthunit{PT}%
143 \LWR@forceminwidth{\fboxrule}%
144 \InlineClass[%
145 display:inline-block ; %
146 border:\rndprintlength{\LWR@atleastonept} solid \LWR@currenttextcolor{} ; %
147 width:\rndprintlength{\LWR@tempwidth} ; %
148 height:\rndprintlength{\LWR@tempheight}%
149 ] {boxframe}{}%
150 }%
151 }

```

---

```
152 \end{warpHTML}
```

---

File 164 **l warp-xfrac.sty**

§ 240 Package **xfrac**

Pkg **xfrac** Supported by adding xfrac instances.

**for HTML output:** 1 \LWR@ProvidesPackagePass{xfrac}

⚠ **font size** In the user's document preamble, l warp should be loaded after font-related setup. During HTML conversion, this font is used by l warp to generate its initial PDF output containing HTML tags, later to be converted by pdftotext to a plain text file. While the text may be in any font which pdftotext can read, the math is directly converted into SVG images using this same user-selected font. xfrac below is set for the Latin Modern (lmr) font. If another font is used, it may be desirable to redefine \xfracHTMLfontsize with a different em size.

\sfrac [⟨instance⟩] {⟨num⟩} [⟨sep⟩] {⟨denom⟩}

A text-mode instance for the default font is provided below. The numerator and denominator formats are adjusted to encase everything in HTML tags. \scalebox is made null inside the numerator and denominator, since the HTML tags should not be scaled, and we do not want to introduce additional HTML tags for scaling.

In math mode, which will appear inside a `lateximage`, no adjustments are necessary.

**for HTML & PRINT:** 2 \begin{warpall}

\xfracHTMLfontsize User-redefinable macro which controls the font size of the fraction.

3 \newcommand\*\{\xfracHTMLfontsize\}{.6em}

4 \end{warpall}

**for HTML output:** 5 \begin{warpHTML}

**font size** A span for a small font, used in the numerator and denominator:

```
6 \newcommand*\{\LWR@htmlsmallfontstart\}{%
7 \LWR@htmlltagc{span style="font-size:\xfracHTMLfontsize\{}%\n8 \LWR@nestspan\%
9 %
10 }
11
```

```

12 \newcommand*{\LWR@htmlsmallfontend}{%
13 \LWR@htmlltagc{/span}%
14 \endLWR@nestspan%
15 }

```

**\scalebox** A nullified `\scalebox` command, to avoid introducing HTML scaling tags:

```
16 \NewDocumentCommand{\LWR@noscalebox}{m o m}{#3}
```

**instances** Instances of `xfrac` for various font choices:

Produce HTML tags for a small superscript numerator and a small (non-subscript) denominator.

Scaling is turned off so that `pdftotext` correctly reads the result.

```

17 \DeclareInstance{xfrac}{default}{text}{%
18 numerator-format = {%
19 \LetLtxMacro{\scalebox}{\LWR@noscalebox}%
20 \LWR@htmlsmallfontstart{textsuperscript{#1}\,,\LWR@htmlsmallfontend},%
21 denominator-format = {%
22 \LetLtxMacro{\scalebox}{\LWR@noscalebox}%
23 \LWR@htmlsmallfontstart{}\,,#1\LWR@htmlsmallfontend},

```

For `pdftotext`, do not scale the text:

```

24 scaling = false
25 }
26
27 \DeclareInstance{xfrac}{lmr}{text}{%
28 numerator-format = {%
29 \LetLtxMacro{\scalebox}{\LWR@noscalebox}%
30 \LWR@htmlsmallfontstart{textsuperscript{#1}\,,\LWR@htmlsmallfontend},%
31 denominator-format = {%
32 \LetLtxMacro{\scalebox}{\LWR@noscalebox}%
33 \LWR@htmlsmallfontstart{}\,,#1\LWR@htmlsmallfontend},

```

For `pdftotext`, do not scale the text:

```

34 scaling = false
35 }
36
37 \DeclareInstance{xfrac}{lmss}{text}{%
38 numerator-format = {%
39 \LetLtxMacro{\scalebox}{\LWR@noscalebox}%
40 \LWR@htmlsmallfontstart{textsuperscript{#1}\,,\LWR@htmlsmallfontend},%
41 denominator-format = {%
42 \LetLtxMacro{\scalebox}{\LWR@noscalebox}%
43 \LWR@htmlsmallfontstart{}\,,#1\LWR@htmlsmallfontend},

```

For pdftotext, do not scale the text:

```
44 scaling = false
45 }
46
47 \DeclareInstance{xfrac}{lmtt}{text}{
48   numerator-format = {%
49     \LetLtxMacro{\scalebox}{\LWR@noscalebox}%
50     \LWR@htmlsmallfontstart{textsuperscript{#1}\,,\LWR@htmlsmallfontend},%
51   denominator-format = {%
52     \LetLtxMacro{\scalebox}{\LWR@noscalebox}%
53     \LWR@htmlsmallfontstart{}\,,#1\LWR@htmlsmallfontend},%
```

For pdftotext, do not scale the text:

```
54 scaling = false
55 }

56 \end{warpHTML}
```

File 165 **lwarp-xltxttra.sty**

## § 241 Package **xltxttra**

Pkg xltxttra xltxttra is emulated.

(Based on original code by WILL ROBERTSON, JONATHAN KEW.)

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{xltxttra}

2 \RequirePackage{realscripts}
3 \RequirePackage{metalogo}
4 \newcommand*\TeX@logo@spacing[6]{}
5
6 \newcommand*{\vfrac}[2]{%
7   \textsuperscript{#1}/\textsubscript{#2}%
8 }
9
10 \newcommand\namedglyph[1]{%
11   \tempcnta=\XeTeXglyphindex "#1"\relax
12   \ifnum\tempcnta>0
13     \XeTeXglyph\tempcnta
14   \else
15     \xxt@namedglyph@fallback{#1}%
16   \fi}
17
```

---

```

18 \newcommand\xxt@namedglyph@fallback[1]{[#1]}
19
20 \DeclareDocumentCommand{\showhyphens}{m}{}

```

---

File 166 **lwarf-xmpincl.sty**

§ 242 Package **xmpincl**

Pkg **xmpincl** Emulated.

**for HTML output:** Discard all options for lwarf-xmpincl:

```

1 \LWR@ProvidesPackageDrop{xmpincl}

2 \newcommand*\{\include{xmp}[1]{}

```

---

File 167 **lwarf-xtab.sty**

§ 243 Package **xtab**

Pkg **xtab** xtab is emulated during HTML output.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{xtab}

⚠ misplaced alignment  
alignment tab character &

```

\StartDefiningTabulars
\tablefirsthead
...
\EndDefiningTabulars

```

See section 7.7.

```

2 \newcommand{\LWRXT@firsthead}{}%
3
4 \newcommand{\tablefirsthead}[1]{%
5   \long\gdef\LWRXT@firsthead{#1}%
6 }
7
8 \newcommand{\tablehead}[1]{}
9
10 \newcommand{\tablelasthead}[1]{}
11
12 \newcommand{\notablelasthead}{}%

```

```
13
14 \newcommand{\tabletail}[1]{}
15
16 \newcommand{\LWRXT@lasttail}{}
17
18 \newcommand{\tablelasttail}[1]{%
19     \long\gdef\LWRXT@lasttail{#1}%
20 }
21
22 \newcommand{\tablecaption}[2][]{%
23     \long\gdef\LWRXT@caption{\caption[#1]{#2}}%
24 }
25
26 \let\topcaption\tablecaption
27 \let\bottomcaption\tablecaption
28
29 \global\let\LWRXT@caption\relax
30
31 \newcommand*\shrinkheight[1]{}
32
33 \newcommand*\xentrystretch[1]{}
34
35 \NewDocumentEnvironment{xtabular}{s o m}
36 {
37 \LWR@traceinfo{xtabular}
38 \table
39 \LWRXT@caption
40 \begin{tabular}{#3}
41 \TabularMacro\ifdefvoid{\LWRXT@firsthead}{%
42 {\LWR@getmynexttoken}%
43 {\expandafter\LWR@getmynexttoken\LWRXT@firsthead}%
44 }
45 {%
46 \ifdefvoid{\LWRXT@lasttail}{%
47 {}%
48 {%
49 \TabularMacro\ResumeTabular%
50 \LWRXT@lasttail%
51 }%
52 \end{tabular}
53 \endtable
54 \LWR@traceinfo{xtabular done}
55 }
56
57 \NewDocumentEnvironment{mpxtabular}{s o m}
58 {\minipage{\linewidth}\xtabular{#3}}
59 {\endxtabular\endminipage}
```

---

File 168 **lwarf-zwpagelayout.sty**

§ 244 Package **zwpagelayout**

Pkg **zwpagelayout** zwpagelayout is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{zwpagelayout}

2 \def\noBboxes{}
3 \onlypreamble\noBboxes
4
5 \expandafter\ifx\csname definecolor\endcsname\relax \else
6   \definecolor{cmykblack}{cmyk}{0,0,0,1}
7   \definecolor{grblack}{gray}{0}
8 %   \ifzwpl@redefineblack
9 %     \definecolor{black}{cmyk}{0,0,0,1}\color{black}
10%   \fi
11  \definecolor{cmykred}{cmyk}{0,1,1,0}
12  \definecolor{cmykgreen}{cmyk}{1,0,1,0}
13  \definecolor{cmykblue}{cmyk}{1,1,0,0}
14  \definecolor{rgbred}{rgb}{1,0,0}
15  \definecolor{rgbgreen}{rgb}{0,1,0}
16  \definecolor{rgbbblue}{rgb}{0,0,1}
17%   \ifzwpl@redefinecmyk
18%     \definecolor{red}{cmyk}{0,1,1,0}
19%     \definecolor{green}{cmyk}{1,0,1,0}
20%     \definecolor{blue}{cmyk}{1,1,0,0}
21%   \fi
22\fi
23
24 \let\OverprintTeXExtGState\relax
25
26 \DeclareRobustCommand\SetOverprint{\ignorespaces}
27 \DeclareRobustCommand\SetKnockout{\ignorespaces}
28 \DeclareRobustCommand\textoverprint[1]{\SetOverprint#1}
29 \DeclareRobustCommand\textknockout[1]{\SetKnockout#1}
30
31 \def\SetPDFminorversion#1{}
32 \onlypreamble\SetPDFminorversion
33
34 \newcommand*\Vcorr{}
35
36 \DeclareRobustCommand\vb[1][]{}
37 \NewDocumentCommand{\NewOddPage}{* o}{}
38 \NewDocumentCommand{\NewEvenPage}{* o}{}
```

```
39 \def\SetOddPageMessage{\gdef\ZW@oddwarning}
40 \def\SetEvenPageMessage{\gdef\Z@evenwarning}
41 \def\ZW@oddwarning{Empty page inserted}\let\Z@evenwarning\ZW@oddwarning
42
43 \def\clap#1{#1}
44
45 \def\CropFlap{2in}
46 \def\CropSpine{1in}
47 \def\CropXSpine{1in}
48 \def\CropXtrim{.25in}
49 \def\CropYtrim{.25in}
50 \def\UserWidth{5in}
51 \def\UserLeftMargin{1in}
52 \def\UserRightMargin{1in}
53 \def\UserTopMargin{1in}
54 \def\UserBotMargin{1in}
55 \def\thePageNumber{\#\!,\arabic{page}}
56 \ifXeTeX
57 \def\ifcaseZWdriver{\ifcase2}
58 \else
59 \def\ifcaseZWdriver{\ifcase1}
60 \fi
61 \DeclareRobustCommand\ZWifdriver[2]{}  

```

# Change History and Index

## § 244 Change History

---

v0.10	General: 2016/03/08 Initial version . . 1	Docs: Table: Float data structures. 320	
v0.11	General: 2016/03/11 . . . . . 1	Docs: Trademarks section. . . . . 394	
	Added section: Operating-System portability. . . . . 114	Docs: Troubleshooting cross-references. . . . . 106	
	Added section: Selecting the operating system. . . . . 71	Test Suite: Assigned cleveref name for Test Float. . . . . 1	
	Test Suite: limages and index in README.txt . . . . . 1	Test Suite: Floatrow . . . . . 1	
	Test Suite: MS-Windows in README.txt . . . . . 1		
v0.12	\LWR@newhtmlfile: Bugfix: TOC with numbered files. . . . . 226	General: 2016/04/06 . . . . . 1	
	General: 2016/03/14 . . . . . 1	Added . . . . . 436	
	Global: Uses \p@(type) in float captions. . . . . 1	Ampersand (&): Fixed handling when passed as an argument. . 271	
	Test Suite: Sub-figures . . . . . 1	Docs: Added warning icons for items needing special attention. 111	
v0.13	\CaptionSeparator: Fix for newer babel package. . . . . 322	Docs: Clarify print/HTML output. 72	
	\LWR@LwarpStart: \up and \fup . . 242	Docs: Moved the supported functions table to the introduction. . . . . 37	
	General: 2016/03/24 . . . . . 1	Files: lwarp_formal.css added. . . 1	
	Removed package: subfig . . . . . 1	Fix: steps counter . . . . . 436	
	Test Suite: Ordinals, Subcaption . . 1	Fixed & handling. . . . . 434	
	tikzpicture: Fix dollar-redefined bug for newer package. . . . . 540	Test Suite: test_suite_formal.css file added. . . . . 1	
v0.14	\LWR@htmlsectionfilename: Fix: Links to home page. . . . . 196	v0.16	General: 2016/04/11 . . . . . 1
	General: 2016/03/31 . . . . . 1	\titlingpage: Improved print-output spacing. . . . . 250	
	floatrow: Added. . . . . 431	Added XeLaTeX, LuaLaTeX support. . . . . 124	
	Docs: Commands for a successful HTML conversion. . . . . 76	Docs: Font and UTF-8 support. . 69	
	Docs: Commands into a warpprint environment. . . . . 73	Docs: Moved location of \usepackage{lwarp}. . . . . 70	
	Docs: Newclude limitations. . . . 97	Docs: Text not converting. . . . . 106	
	Docs: Table: Cross-referencing data structures. . . . . 310	Fix: amsmath options clash . . . . . 128	
		Fix: newtxmath compatibility. . . . . 128	
		Lwarp no longer selects fonts. 69, 123	
		Removed package: suffix . . . . . 1	
		Test Suite: Improved titlingpage. 250	
		Test Suite: Lwarp no longer selects fonts. . . . . 1	

Test Suite: Supports XeLaTeX,	
LuaTeX. . . . .	1
xfrac: Adjusted for the use of any	
font. . . . .	575
v0.17	
\LWR@htmlsectionfilename: Fix:	
Links when entire doc is one	
HTML page. . . . .	196
General: 2016/04/14 . . . . .	1
mdframed: Added. . . . .	474
Test Suite: Fix: Print-version	
front-matter page numbers. . . . .	1
Test Suite: Mdframed . . . . .	1
v0.18	
\LWR@hspace: \hspace supported. .	386
\LWR@includegraphicsb: Add: svgz	
file extension. . . . .	451
em, ex, %, px dimensions	
preserved. . . . .	451
Fix: \linewidth, \textwidth,	
\textheight inside a minipage. .	451
Improved HTML output linebreaks. .	451
\LWR@myshorttoc: Reorganize	
\HomeHTMLfilename logic. . . . .	326
\LWR@newhtmlfile: sidetoc after	
title, improving responsive	
design. . . . .	225
\LWR@requesttoc: Reorganize	
\HomeHTMLfilename logic. . . . .	244
\LWR@subhyperref: Improved HTML	
output linebreaks. . . . .	318
\LWR@subhyperrefclass: Improved	
HTML output linebreaks. . . . .	318
\LWR@subinlineimage: Surpress	
extra space. . . . .	319
General: 2016/05/19 . . . . .	1
File: l warp.css: Improved TOC	
outline display. . . . .	1
Files: l warp.css and	
l warp_formal.css: Improved	
responsive design. . . . .	1
Microtype disabled during HTML	
generation . . . . .	124
PDF Unicode input characters. .	112
Test Suite: Verse package . . . . .	1
lateximage: pdfcrop: --hires added.	356
Reorganize \HomeHTMLfilename	
logic. . . . .	356
Surpress extra space. . . . .	356
verse: Supports verse, memoir	
packages. . . . .	563
minipage: Fix: \ linewidth,	
\textwidth, \textheight	
inside a minipage. . . . .	371
v0.19	
\HTMLfilename: Docs: Escape	
filename underscores. . . . .	195
\HomeHTMLfilename: Docs: Escape	
filename underscores. . . . .	196
\LWR@l warpStart: Enabled \\ equal	
to \newline. . . . .	241
\LWR@doubledollar: MathJax	
support. . . . .	338
\LWR@filestart: l warp_mathjax.txt	
loaded. . . . .	239
\LWR@hspace: Fix: \hspace length	
computations. . . . .	386
\LWR@minipagestartpars:	
Surpresses paragraph tags	
between minipages. . . . .	384
\LWR@singledollar: MathJax	
support. . . . .	338
\LateximageFontSizeName: Add:	
User-adjustable math/lateximage	
font size. . . . .	354
\minipagefullwidth: Added: No	
width tag for the next minipage	
in HTML. . . . .	371
\rule: Added . . . . .	390
\warpHTMLonly: Added. . . . .	118
\warpprintonly: Replaces	
\rowprintedonly. . . . .	118
\xfracHTMLfontsize: Added. . . . .	574
General: 2016/06/08 . . . . .	1
Added optional args. . . . .	488
Avoids MathJax. . . . .	337
cleveref: Loaded	
\AtEndPreamble. . . . .	367
CSS for table note item. . . . .	539
Docs: Math options. . . . .	70
Docs: Table: Cross-referencing	
data structures, updated. . . . .	310
File: l warp_mathjax.txt added. .	1
File: l warp.css: tnoteitemheader	
added . . . . .	1
Introduction: MathJax support	
mentioned. . . . .	36
MathJax support added. .	339, 345, 346
Options: mathsvg and mathjax .	116

Supports colored \rule. . . . .	569
titleps: null \pagestyle and \thispagestyle for HTML . . .	540
tikzpicture: Adapts to tikz version.	540
equation: MathJax support. . . . .	344
v0.20	
\BlockClassSingle: Renamed from "LWR@htmldivclassline". . . . .	208
\HTMLDescription: Added \NewHTMLdescription. (Renamed in v0.30.) . . . . .	218
\HTMLFilename: No longer escape underscores. . . . .	195
\HomeHTMLFilename: No longer escape underscores. . . . .	196
\InlineClass: Renamed from "inlineclass". . . . .	209
\LWR@LwarpStart: Fix: math cross references. . . . .	242
\LWR@closeparagraph: \unskip extra spaces. . . . .	212
No break tags in the start/end of a tabular . . . . .	212
\LWR@endofline: Fix: \\ . . . . .	384
\LWR@filestart: Adds meta description. . . . .	239
\LWR@hspace: Add: Supports HTML thin breakable space. . . . .	386
\LWR@htmldivclass: Added optional style. . . . .	207
\LWR@htmlelementclass: Added optional style. . . . .	206
\LWR@htmlsectionfilename: HTMLFilename: removed additional trailing ' - ', and may be empty. . . . .	196
Sections called "Index" or "index" have an underscore prepended to their filenames if no prefix. . . .	196
\LWR@includegraphicsb: Fix: \linewidth in a floatrow. . . . .	451
Fix: Expands filename. . . . .	451
\LWR@longtabledatacaptiontag: Fix: Pars in captions. . . . .	296
\LWR@section: Combined higher-level sections together into files. . . . .	231
\LWR@setOSWindows: Auto-detects operating system. . . . .	114
\LWR@subhtmlelementclass: Factored code. . . . .	206
\SetHTMLFileName: Add: Control file numbers. . . . .	196
\cpagerefFor: User-redefinable word for page references. . . . .	367
\dotfill: Inserts an ellipsis. . . . .	383
\hfill: Inserts a \quad. . . . .	383
\hrulefill: Inserts a short rule. . . . .	383
\hyperindexref: Print mode provided in case hyperref not used. . . . .	334
\pageref: Added. . . . .	317
\tracingl warp: Added. . . . .	133
General: 2017/02/09 . . . . .	1
afterpage: Added. . . . .	398
alltt: Added. . . . .	399
bookmark: Added. . . . .	407
caption and subcaption supported. . . . .	1
cleveref and referencing patches: Applied \AfterEndPreamble. . . . .	367
draftwatermark: Added. . . . .	412
eso-pic: Added. . . . .	417
everypage: Added. . . . .	417
extramarks: Added. . . . .	418
fancyhdr: Added. . . . .	422
hyperref: Additional user macros. .	457
keyfloat: Added. . . . .	463
letterspace: User-interface emulated. . . . .	465
listings: Added. . . . .	467
ltcaption: Added. . . . .	472
lwarp-newproject: Added. . . . .	138
microtype: User-interface emulated. . . . .	483
needspace: Added. . . . .	491
nowidow: Added. . . . .	493
placeins: Added. . . . .	506
ragged2e: Added. . . . .	508
setspace: Improved support. . . . .	514
textpos: Added. . . . .	534
titleps: Added. . . . .	540
titlesec: Added. . . . .	543
titletoc: Added. . . . .	545
titling: Improved compatibility. .	546
tocloft: Added. . . . .	553
wallpaper: Added. . . . .	564
wrapfig: Added. . . . .	565
Added @, <, > columns. . . . .	267

Added single-expansion data arrays. ....	194
Code factored into independent <code>l warp_html</code> files. ....	394
Docs: Examples for generating HTML file names. ....	62
Docs: Improved index. ....	1
Enhanced titling support. ....	248
File: <code>l warp.css</code> : Minor fixes for validation. ....	1
File: <code>l warpmk</code> used to compile print, HTML, indexes, and <code>lateximages</code> . ....	1
Fix: <code>\ linewidth</code> in a <code>floatrow</code> . . .	434
Improved float caption type handling. ....	429
Moved sidebar and example code to test suite. ....	1
Page geometry set to 6in wide with large margins. ....	125
Parallel versions of aux files for print/HTML. ....	1
Removed reliance on make, grep, gawk. ....	1
Tabular: <code>\unskip</code> extra spaces. . .	267
Test Suite: HTML meta descriptions. ....	1
Verbatim: Added. ....	424
verbatim: Added. ....	259
BlockClass: Added optional style. . 208 Renamed from "blockclass". . .	208
LWR@nestspan: Fix: Minipages inside a span. ....	203
v0.21	
<code>\LWR@L warpStart</code> : Changed <code>latexitimages</code> to a .txt file. . .	241
<code>\LWR@filestart</code> : Skip title if not given. ....	239
<code>\LWR@newhtmlfile</code> : Skip title if not given. ....	225
<code>\marginpar</code> : Fixed source listing. . .	222
General: 2017/02/23 ....	1
fontenc: Added. ....	438
fontspec: Added. ....	439
inputenc: Added. ....	463
newclude: Added. ....	491
newunicodechar: Added. ....	492
<code>l warpmk</code> : Fix: <code>l warpmk</code> again for Windows. ....	179
v0.22	
<code>\LWR@parseDcolumn</code> : Added tabular D column. ....	279
<code>\LWR@parsebangcolumn</code> : Added tabular ! column. ....	276
<code>\LWR@parsetablecols</code> : Unknown table column types become 1. Added tabular D, !, X columns. . .	280
<code>\LWR@printmccoldata</code> : Added tabular D, !, and X columns. . .	292
General: 2017/03/02 ....	1
abstract: Added. ....	396
changepage: Added. ....	409
dcolumn: Added. ....	412
ftnright: Added. ....	444
geometry: Nullified commands. .	445
indentfirst: Added. ....	463
layout: Added. ....	464
l escape: Added. ....	472
mcaption: Added. ....	474
nameref: Added. ....	491
nextpage: Added. ....	492
parskip: Added. ....	505
showkeys: Added. ....	516
sidecap: Added. ....	516
tabularx: Added. ....	529
variorref: Supported. ....	82
verse: Added. ....	562
v0.23	
<code>\LWR@parsetablecols</code> : Fix for vert bar column type. ....	280
<code>\LWR@printmccoldata</code> : Fix for vert bar column type. ....	292
General: 2017/03/02 ....	1
v0.24	
<code>\LWR@hspace</code> : Add: <code>\hspace \fill</code> converts to 2em ....	386
<code>\LWR@htmlfileref</code> : Fix: Index links while <code>\tracingl warp</code> . . .	313

\hypertocfloat: List of floats	
responds to <code>lofdepth</code> ,	
<code>lotdepth</code> . . . . .	332
General: 2017/03/15 . . . . .	1
floatrow: Support for <code>subfig</code> . . . . .	431
subfig: Added. . . . .	521
tikz: For tikz v3.0.0 or later,	
auto-loads tikz babel library if	
necessary. . . . .	539
Docs: Filename underscore. . . . .	60, 77
No longer preloads <code>subcaption</code> ;	
conflicted with <code>subfig</code> . . . . .	127
picture: Fix for inline images. . . . .	368
tikzpicture: Fix for inline images	
. . . . .	540
v0.25	
\LWR@loadnever: Added the ability	
to prevent conflicting packages.	120
\addcontentsline: Handles	
theorems. . . . .	325
General: 2016/03/22 . . . . .	1
amsthm: Added. . . . .	400
ccaption: Prevented. . . . .	409
ellipsis: Added. . . . .	413
emptypage: Added. . . . .	414
framed: Added. . . . .	441
lips: Added. . . . .	466
mdframed: Help avoid	
hyphenation. . . . .	475
ntheorem: Added. . . . .	493
showidx: Added. . . . .	516
theorem: Added. . . . .	534
Basic L <sup>A</sup> T <sub>E</sub> X theorems: improved	
css. . . . .	259
Docs: Adds credits for patched	
code. . . . .	1
Docs: Testing <code>lwarp</code> . . . . .	104
Fix: Allows XE <sup>A</sup> T <sub>E</sub> X and Lua <sup>A</sup> T <sub>E</sub> X to	
preload graphics and graphicx.	120
v0.26	
General: 2017/03/31 . . . . .	1
cutwin: Added. . . . .	411
endnotes: Added. . . . .	414
floatflt: Added. . . . .	430
footmisc: Added. . . . .	439
footnotehyper: Added. . . . .	441
footnote: Added. . . . .	440
marginfix: Added. . . . .	473
marginnote: Added. . . . .	473
mparhack: Added. . . . .	486
pagenote: Supported as-is. . . . .	504
sidenotes: Added. . . . .	517
1warp.css: Improved responsive	
<code>marginpar</code> and <code>marginblock</code> . . . . .	140
Docs: Improved MiK <sub>T</sub> E <sub>X</sub> install	
instructions. . . . .	44, 47
Dollar span avoided in a	
<code>latextimage</code> . . . . .	337
Footnotes now are L <sup>A</sup> T <sub>E</sub> X boxes	
instead of pagenotes. . . . .	218
latextimage: Labels track page	
numbers of <code>latextimages</code> . . . . .	356
Print mode now uses a <code>minipage</code>	
of <code>\ linewidth</code> . . . . .	356
picture: Fix for <code>\makebox</code> in	
<code>picture</code> . . . . .	368
v0.27	
\LWR@footnotetext: Fix for table	
footnote par tags. . . . .	220
General: 2017/04/04 . . . . .	1
letterine: Added. . . . .	465
microtype: Fix with Xe <sup>A</sup> T <sub>E</sub> X,	
Lua <sup>A</sup> T <sub>E</sub> X. . . . .	483
soul: Added. . . . .	519
ulem: Added. . . . .	561
Docs: Installing utilities for	
MacOS. . . . .	49
Docs: Limitations of saveboxes. . . . .	78
Page geometry modified to reduce	
line overflow. . . . .	125
v0.28	
\@rindex: Improved indexing. . . . .	334
\HTMLAuthor: Added \HTMLauthor.	
(Renamed in v0.30.) . . . . .	218
\LWR@LwarpEnd: If FormatEPUB or	
FormatWordProcessor, no	
bottom nav. . . . .	244
\LWR@LwarpStart:	
FormatWordProcessor forces	
single-file output. . . . .	241
\LWR@filestart: Adds HTML meta	
author. . . . .	239
\LWR@forcenewpage: Forces new	
PDF page before major	
environments. . . . .	200
\LWR@htmlcomment: Breaks ligatures	
in HTML comments. . . . .	205
\LWR@includegraphicsb: Adapts to	
graphics syntax. . . . .	451

\LWR@newhtmlfile: If FormatEPUB or FormatWordProcessor: skips headers, footers, nav. . . . .	225	\HTMLFirstPageTop: Renamed from \SetFirstPageTop. . . . .	216	
\LWR@parsetablecols: Added L, C, R, J column types. . . . .	280	\HTMLLanguage: Renamed from \MetaLanguage. . . . .	238	
\LWR@startref: Removed space. . . . .	315	\HTMLPageBottom: Renamed from \SetPageBottom. . . . .	217	
\chapter: If EPUB, prints footnotes before each section. . . . .	236	\HTMLPageTop: Renamed from \SetPageTop. . . . .	216	
\hyperindexref: Improved indexing. . . . .	334	General: 2017/04/29 . . . . .	1	
\textup: Fixed span class. . . . .	379	l warp-newproject removed, and combined with l warp. . . . .	138	
General: 2017/04/14 . . . . .	1	l warpmk: Add: xdyfile configuration option. . . . .	179	
glossaries: Added. . . . .	446	l warpmk: Fix: xindy and texindy adjusted for pdflatex, xelatex and lualatex. . . . .	179	
graphics: Added. . . . .	447	l warpmk: Fix: xindy now used for print index generation with latexmk. . . . .	179	
tabularx: Fix for optional pos. . . . .	529	l warpmk: language now used for both index and glossary generation. . . . .	179	
tabulary: Added. . . . .	530	File: l warp_html.xdy renamed to l warp.xdy. . . . .	176	
l warpmk: Add: printglossary and htmlglossary commands. . . . .	179	Fix: *.css files only written in print mode. . . . .	140	
Added boolean FormatEPUB. . . . .	134	Fix: l warp.xdy only written in print mode. . . . .	176	
Added boolean FormatWordProcessor. . . . .	134	Fix: l warp_mathjax.txt only written in print mode. . . . .	177	
Added boolean HTMLDebugComments. . . . .	133	Option OSWindows replaces macro \warpOSwindows. . . . .	117	
Added boolean HTMLMarkFloats. . . . .	134	Option latexmk replaces macro \UseLatexmk. . . . .	117	
Docs: Modfyng l warpmk and index processing. . . . .	104	Option l warpmklang changed to IndexLanguage. . . . .	116	
File l warp_mathjax.txt: Updated CDN repository. . . . .	177	Option xdyFilename added. . . . .	116	
Forced oneside to maintain large right margin. . . . .	125	Options HomeHTMLFilename and HTMLFilename replace macros \HomeHTMLFilename and \HTMLFilename. . . . .	117	
v0.29		v0.31	General: 2017/05/15 . . . . .	1
\LWR@includegraphicsb: Fix: Error when no optional arguments. . . . .	451	keyfloat: Improved compatibility. . . . .	463	
General: 2017/04/15 . . . . .	1	v0.32	\RequirePackage: Fix: Ignores blanks in package list. . . . .	129
l warpmk: Add: language option for config files. . . . .	179	General: 2016/06/09 . . . . .	1	
Add: l warpmklang option for l warp. . . . .	116	glossaries: Prevent error with \glo@name not defined. . . . .	335	
Docs: Using a glossary. . . . .	67			
File *.l warpmkconf: Add: language option for config files. . . . .	139			
File l warpmk.conf: Add: language option for config files. . . . .	139			
v0.30				
\CSSFilename: Renamed from \NewCSS. . . . .	217			
\HTMLAuthor: Renamed from \HTMLauthor. . . . .	218			
\HTMLDescription: Renamed from \NewHTMLdescription. . . . .	218			

\lwarpmk: Fix: <code>io.lines()</code> changed to <code>file:lines()</code> due to luatex changes. . . . .	179
<b>v0.33</b>	
\HTMLAuthor: Fix: Provides empty default author if none given. . . . .	218
\LWR@loadbefore: Fix: No \PackageError if already loaded. . . . .	119
\LWR@parseatcolumn: Fix: Column alignment with leftmost @. . . . .	276
\LWR@tableddatasinglecolumntag: Fix: Macros in tabular could cause extra data cell. . . . .	286
\LWR@vspace: Add: \vspace nullified. . . . .	387
\StartDefiningTabulars: Add: Avoids error: misplaced alignment tab character &. . . . .	271
General: 2017/07/10 . . . . .	1
amsmath: Removed <code>fleqn</code> option. . . . .	128
fancyhdr: Fix: Optional args for \lhead, etc. . . . .	422
Add: Tabular at and bang columns now have their own HTML columns. . . . .	267
cleveref: Fix: Loaded \AtEndPreamble. . . . .	367
Fix: Incorrectly-inline math environments. . . . .	346
New handling of & to localize catcode changes. . . . .	267
<b>v0.34</b>	
\@fnsymbol: Text symbols instead of math. . . . .	251
\InlineClass: Moved optional argument in front of mandatory. . . . .	209
\LWR@htmldivclass: Moved optional argument in front of mandatory. . . . .	207
\LWR@htmlelementclass: Moved optional argument in front of mandatory. . . . .	206
\LWR@htmlelementclassline: Moved optional argument in front of mandatory. . . . .	207
\LWR@htmlspanclass: Moved optional argument in front of mandatory. . . . .	204
\LWR@nullfonts: Improved font control. . . . .	380
\LWR@restoreorigformatting: booktabs: Works inside \lateximage. . . . .	340
Improved font control. . . . .	340
\LWR@subhtmelementclass: Moved optional argument in front of mandatory. . . . .	206
\LWR@tabledatacolumntag: booktabs: Works inside \lateximage. . . . .	303
\fboxBlock: Added. . . . .	375
\makebox: Fix: Handles paren arg. . . . .	373
General: 2017/08/08 . . . . .	1
babel-french: Adds fixed-width HTML spaces to punctuation. . . . .	201
balance: Added. . . . .	405
booktabs: Works inside \lateximage. . . . .	305, 407
boxedminipage2e: Added. . . . .	408
boxedminipage: Prevented. . . . .	408
crop: Added. . . . .	410
enumerate: Added. . . . .	415
enumitem: Added, no longer required. . . . .	415
everyshi: Added. . . . .	418
fancybox: Added. . . . .	420
fancyvrb: Added, no longer required. . . . .	423
figcaps: Added. . . . .	428
filecontents: Required. Patched for morewrites. . . . .	126
floatpag: Added. . . . .	431
flushend: Added. . . . .	437
fullpage: Added. . . . .	444
hyperxmp: Added. . . . .	462
idxlayout: Added. . . . .	462
marginfit: Added. . . . .	473
mdframed: Improved <code>mdtheorem</code> patch. . . . .	480
moreverb: Added. . . . .	484
paralist: Added. . . . .	504
pdflscape: Added. . . . .	505
pdfsync: Added. . . . .	505
prelim2e: Added. . . . .	506
rotfloat: Added. . . . .	512
savetrees: Added. . . . .	513
shadow: Added. . . . .	515
syntonly: Added. . . . .	528

titleps: No longer required. . . . .	540
titleref: Prevented. . . . .	543
xmpincl: Added. . . . .	577
Added. . . . .	572
Docs: Horizontal space limitations. . . . .	1
Docs: Misplaced alignment character. . . . .	106
File: README.txt: updated. . . . .	1
File: 1warp_mathjax.txt version change. . . . .	177
Fix: Added the eqnarray environments. . . . .	346
Improved font control. . . . .	378
Lists refactored to remove enumitem requirement. . . . .	261
Verbatim refactored to remove fancyvrb requirement. . . . .	257
lateximage: Fix: lateximage with minipage, \parbox, \makebox, \fbox, \framebox, \raisebox, \scalebox, \reflectbox. . . . .	356
BlockClass: Moved optional argument in front of mandatory. . . . .	208
fminipage: Added. . . . .	376
LWR@nestspan: Fix: Minipages, BlocksClass, and lists inside a span. . . . .	203
LWR@tabular: booktabs: Works inside lateximage. . . . .	306
v0.35	
General: 2017/08/08 . . . . .	1
Fix: \textbf and related. . . . .	378
v0.36	
\LWR@HTMLsanitize: Fix for babel-french. . . . .	355
\LWR@HTMLsanitizeexpand: Fix for babel-french. . . . .	355
\LWR@closeparagraph: Extra HTML source space after paragraphs. . . . .	212
\LWR@currenttextcolor: Fix for \color when xcolor not loaded. . . . .	388
\LWR@footnotetext: Extra HTML source space after paragraphs. . . . .	220
Force HTML superscripts. . . . .	220
\LWR@nullfonts: Fix: Filenames while using MathJax. . . . .	380
\LWR@restoreorigformatting: siunitx: Improved	
super/subscripts in a lateximage. . . . .	340
\LWR@section: Improved spacing. . . . .	231
\LWR@stopars: Extra HTML source space after paragraphs. . . . .	214
\fbox: Fix: Uses \fboxrule and \fboxsep. . . . .	375
\framebox: Fix: Handles width and horiz position. . . . .	374
\makebox: Fix: Handles width and horiz position. . . . .	373
General: 2017/08/17 . . . . .	1
babel-french: Adjustements for French variants, load order, footnotes, ellipses. . . . .	201
footnote: Extra HTML source space after paragraphs. . . . .	440
siunitx: Fix for babel-french. . . . .	361
siunitx: Improved symbol support. . . . .	519
transparent: Added. . . . .	558
upref: Added. . . . .	562
xcolor: Added \fcolorboxBlock, \colorboxBlock. . . . .	567
xcolor: Fix: Background none in print mode. . . . .	567
xcolor: Refactored \LWR@colorstyle. . . . .	569
xcolor: Uses \fboxrule and \fboxsep. . . . .	567
xcolor: \fcolorbox etc. now work inside lateximage. . . . .	567
Docs: Reorganized: Special cases and limitations. . . . .	76
Source: Improved formatting. . . . .	1
lateximage: Footnotes appear in regular text instead of the lateximage minipage. . . . .	356
LWR@tabular: Fix for babel-french. . . . .	306
v0.37	
\include: Maintains independent .aux files for HTML. . . . .	131
General: 2017/08/19 . . . . .	1
\TeX accents: Added. . . . .	136
babel-french: Adjustment for load order. . . . .	201
color: Prevented. . . . .	410
comment: Maintains independent cutfiles for print, HTML. . . . .	118
siunitx: Improved symbol support. . . . .	519
textcomp: Improved support. . . . .	531

\lwarpmk: Removes additional HTML aux files. . . . .	179
File handles reorganized. . . . .	131
<b>v0.38</b>	
\@secntformat: Added for appendix. . . . .	231
\ForceHTMLPage: Added. . . . .	228
\ForceHTMLTOC: Added. . . . .	229
\LWR@section: \part* starts a new HTML page, for appendix. . . . .	231
Modified spacing, uses \newline. . . . .	231
\newline: Added trailing \quad. . . . .	330
\part: Fix with article class. . . . .	236
General: 2017/08/27 . . . . .	1
appendix: Added. . . . .	403
arabicfront: Added. . . . .	404
caption2: Prevented. . . . .	409
chappg: Added. . . . .	410
color: Forces xcolor as well. . . . .	410
fix2col: Added. . . . .	429
fncychap: Added. . . . .	437
grffile: Added. . . . .	457
metalogo: Added. . . . .	483
nonumonpart: Added. . . . .	492
nopageno: Added. . . . .	493
pagenote: Option page disabled. . . . .	504
realscripts: Added. . . . .	509
relsize: Added. . . . .	510
romanbarpage: Added. . . . .	511
romanbar: Added. . . . .	511
scalefnt: Added. . . . .	513
siunitx: Removed from lwarpm core. . . . .	519
textcomp: Removed from lwarpm core. . . . .	531
tocbibind: Added. . . . .	552
xltextra: Added. . . . .	576
\lwarpmk: Added print1 and html1 actions. . . . .	179
Added \markboth, \sloppy, etc. . . . .	199
Docs: Enhanced <i>Supported   Functions</i> table. . . . .	37
Docs: Index, tocbibind. . . . .	86
Docs: Starred sections. . . . .	83
<b>v0.39</b>	
\@maketitle: titling version. . . . .	549
Native L <sup>A</sup> T <sub>E</sub> X version. . . . .	252
Removed minipages. . . . .	252, 549
Supports authblk with <div>s of class oneauthor instead of tabular. . . . .	252, 549
\AddSubtitlePublished: Added. . . . .	254
\LWR@domulticolumn: Add: Optional vpos and # rows. . . . .	294
\LWR@restoreorigformatting: Appended with \appto instead of calling various macros. . . . .	340
\LWR@tabledatacolumntag: Don't start a data cell if see \TabularMacro. . . . .	303
\ResumeTabular: Added. . . . .	302
\TabularMacro: Added. . . . .	302
\multicolumnrow: Added. . . . .	300, 490
\printauthor: Removed minipages. . . . .	249
Supports authblk with <div>s of class oneauthor instead of tabular. . . . .	249
\thanksmarkseries: Removed minipage footnotes. . . . .	550
General: 2017/09/05 . . . . .	1
a4wide: Added. . . . .	395
a4: Added. . . . .	395
a5comb: Added. . . . .	395
addlines: Added. . . . .	398
anysize: Added. . . . .	403
authblk: Added. . . . .	404
bigdelim: Added. . . . .	406
bigstrut: Added. . . . .	407
chngpage: Prevented. . . . .	409
ebook: Added. . . . .	413
fullwidth: Added. . . . .	445
supertabular: Added. . . . .	527
textarea: Added. . . . .	530
titling: Improved compatibility. . . . .	546
titling: Removed extraneous center environments. . . . .	547
typearea: Added. . . . .	560
xtabular: Added. . . . .	577
zwpagelayout: Added. . . . .	579
Add: New optional vpos argument. . . . .	488
Add: Supports left/right border for bigdelim. . . . .	488
Docs: Reorganized tabular discussion. . . . .	92
Fix: Long text argument. . . . .	488
Titlepage \published and \subtitle removed.	

\AddSubtitlePublished	507
restores.	253
titlepage: Clear pending footnotes.	248
Removed minipages.	248
titlingpage: Clear pending	
footnotes.	547
v0.40	
{@chapcntformat: Added for	
tocbibind, anonchap.	231
\LWR@hline: Added.	306
\LWR@includegraphicsb: Add: Full	
\graphicspath support.	451
\LWR@nullfonts: Fix: Long	
arguments for expandable	
command.	380
\LWR@restoreorigformatting:	
Improved L <sup>A</sup> T <sub>E</sub> X logos inside a	
lateximage.	340
Improved symbols inside a	
lateximage.	340
Nullified \InlineClass, etc.	
inside a lateximage.	340
\LWR@tabledatacolumntag: Fix for	
bigdelim: \ldelem, \rdelem...	303
\chapter: Added support for	
quotchap.	236
\multicolumnrow: Fix: Adapts to	
older multirow and xparse.	300
\simplechapterdelim: Added for	
tocbibind, anonchap.	231
\underline: Added.	382
General: 2017/09/25	1
adjmulticol: Added.	397
anonchap: Added.	403
bigdelim: Improved	
documentation.	406
cuted: Added.	411
dblfnote: Added.	412
fnpos: Added.	438
graphics: Moved out of the lwrap	
core.	447
graphics: Restores	
\includegraphics and	
\DeclareGraphicsExtensions	
in a lateximage.	447
graphicx: Moved out of the lwrap	
core.	457
grffile: Directly supported.	457
midfloat: Added.	484
pfnote: Added.	506
quotchap: Added.	507
sectsty: Added.	513
stabular: Added.	521
tabls: Added.	529
textcomp: Additional symbols,	
improved XeLaTeX and LuaLaTeX	
support.	531
tocbibind: Improved for	
\simplechapter.	552
xltxta: Fix for \showhyphens with	
XeLaTeX.	576
Improved bigdelim borders.	488
No longer preloads xfrac.	128
v0.41	
\LWR@addcmidruletrim: Add:	
\cmidrule trims.	290
\LWR@clearmidrules: Add:	
\cmidrule trims.	289
\LWR@closetabledatacell: Add:	
Mute > for \bottomrule.	269
Fix: At/bang column with	
\multirow.	269
Fix: Cancel < for \multicolumn.	270
\LWR@domulticolumn: Add:	
\cmidrule trims.	294
Added vertical rules.	295
\LWR@nullifyNoAutoSpacing: Fix:	
\NoAutoSpacing in a tabular	
with babel-french.	306
\LWR@parsebarcolumn: Added	
vertical rules.	278
\LWR@printatbang: Add: \cmidrule	
trims.	285
Add: Mute at and bang columns	
for \bottomrule.	285
\LWR@printbartag: Added vertical	
rules.	285
\LWR@subaddcmidruletrim: Added.	290
\LWR@subcmidrule: Add: \cmidrule	
trims.	289
\LWR@tabledatasinglecolumntag:	
Add: \cmidrule trims.	286
Add: Mute < for \bottomrule...	286
\LWR@tabularfinishrow:	
Unfinished tabular rows	
automatically filled.	272
\mcolrowcell: Added for	
\multicolumnrow cells.	305
General: 2017/10/07	1
Add: \cmidrule trims.	488

Added vertical rules. . . . .	489	LWR@tabular: Fix: \NoAutoSpacing in a tabular with babel-french. . .	307
Fix: < spec. . . . .	489	Improved rules. . . . .	308

## § 244 Index

---

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		A	
\\$ . . . . .	<u>337</u>	a4 (package) . . . . .	395
\& . . . . .	<u>195</u> , <u>4859</u>	a4wide (package) . . . . .	395
\( . . . . .	<u>6230</u>	a5comb (package) . . . . .	395
\) . . . . .	<u>6230</u>	abstract (environment) . . . . .	4597
\, . . . . .	<u>76</u>	abstract (package) . . . . .	395
\@osetpageref . . . . .	<u>6954</u>	\abstractname . . . . .	<u>62</u> , 4596
\@osetref . . . . .	<u>6950</u>	accents . . . . .	228
\@osetrefrange . . . . .	<u>6951</u>	\addcontentsline . . . . .	<u>5973</u>
\@author . . . . .	<u>246</u>	addlines (package) . . . . .	398
\@begintheorem . . . . .	<u>4689</u>	\AddSubtitlePublished . . . . .	<u>4559</u>
\@capttype . . . . .	<u>5919</u>	adjmulticol (package) . . . . .	397
\@chapcntformat . . . . .	<u>4066</u>	Adobe (program) . . . . .	43
\@currentlabelname . . . . .	<u>5699</u>	\affiliation . . . . .	4421
\@date . . . . .	<u>246</u>	afterpackage (package) . . . . .	125
\@dilbfloat . . . . .	<u>5897</u>	afterpage (package) . . . . .	398
\@endtheorem . . . . .	<u>4699</u>	algorithmic	
\@ensuredmath . . . . .	<u>6237</u>	with newfloat, trivfloat . . . . .	560
\@float . . . . .	<u>5897</u>	algorithmicx (package) . . . . .	399
\@fnsymbol . . . . .	<u>4511</u>	align (environment) . . . . .	6564
\@footnotetext . . . . .	<u>3835</u>	align* (environment) . . . . .	6587
\@include . . . . .	<u>450</u>	alignment tab character &, misplaced . . . . .	
\@makecaption . . . . .	<u>5921</u>	. . . . .	92, 264, 271
\@makefnmark . . . . .	<u>3807</u>	alltt (package) . . . . .	399
\@makefntext . . . . .	<u>3806</u>	\AmS . . . . .	7473
\@maketitle . . . . .	<u>49</u> , <u>4534</u>	AMSmath	
\@mpfootnotetext . . . . .	<u>3836</u>	split miss-numbered . . . . .	87, 89, 335, 494
\@opargbegintheorem . . . . .	<u>4694</u>	amsmath (package) . . . . .	128
\@seccntformat . . . . .	<u>4064</u>	amsthm (package) . . . . .	400
\@title . . . . .	<u>246</u>	\and . . . . .	246
\@wrglossary . . . . .	<u>6171</u>	anonchap (package) . . . . .	402
\@wrindex . . . . .	<u>6164</u>	any size (package) . . . . .	403
\\" . . . . .	<u>384</u>	appendix (package) . . . . .	403
\\$ . . . . .	<u>338</u>	arabicfront (package) . . . . .	404
\\$\\$ . . . . .	<u>338</u>	array (package) . . . . .	310
\~ . . . . .	<u>76</u>	AsciiDoc (program) . . . . .	42
		AsciiDoctor (program) . . . . .	42

Asciidoctor–LaTeX (program) . . . . .	42	LWR@tableparcell . . . . .	268	
\attrib . . . . .	97, 256, 563	LWR@tabularmutemods . . . . .	303	
\attribution . . . . .	4607	LWR@tracinglwarp . . . . .	133	
authblk (package) . . . . .	404	LWR@validtablecol . . . . .	280	
author		LWR@verbtags . . . . .	258	
HTML meta tag . . . . .	74, 218	mathjax . . . . .	115	
\author . . . . .	74, 246	usingOSWindows . . . . .	114	
autosec . . . . .	230	warpingHTML . . . . .	115	
		warpingprint . . . . .	115	
<b>B</b>				
babel (package) . . . . .	98	boxedminipage (package) . . . . .	408	
\backmatter . . . . .	4048	boxedminipage2e (package) . . . . .	408	
balance (package) . . . . .	405	\boxframe . . . . .	137	
\BaseJobname . . . . .	3252	bugs . . . . .	106	
BaseJobname (option) . . . . .	116	BVerbatim (environment) . . . . .	183	
baseline		<b>C</b>		
tabular . . . . .	280	calc (package) . . . . .	127	
\bfseries . . . . .	7269	Calibre . . . . .	99	
\BibTeX . . . . .	7468	caption (package) . . . . .	127	
bigdelim (package) . . . . .	405	caption2 (package) . . . . .	409	
bigstrut (package) . . . . .	407	\caption@begin . . . . .	5952	
BlockClass (environment) . . . . .	3581	\caption@end . . . . .	5952	
\BlockClassSingle . . . . .	3593	\captionlistentry . . . . .	5956	
bookmark (package) . . . . .	407	\captionof . . . . .	5986	
booktabs (package) . . . . .	407	\CaptionSeparator . . . . .	5920	
booleans:		ccaption (package) . . . . .	409	
CombineHigherDepths . . . . .	61, 223	center (environment) . . . . .	6799	
FileSectionNames . . . . .	62, 196	\centering . . . . .	242	
FormatEPUB . . . . .	99, 134	changepage (package) . . . . .	409	
FormatWordProcessor . . . . .	101, 134	chappg (package) . . . . .	410	
HTMLDebugComments . . . . .	133	\chapter . . . . .	4213	
HTMLMarkFloats . . . . .	102, 134	chngpage (package) . . . . .	409	
LWR@amsmultiline . . . . .	345	\citetitle . . . . .	4614	
LWR@doingapar . . . . .	210	class:		
LWR@doingscmidrule . . . . .	268	internet . . . . .	41	
LWR@doinghline . . . . .	268	cleveref (package) . . . . .	366	
LWR@doingstartpars . . . . .	210	cmap (package) . . . . .	70	
LWR@doingtbrule . . . . .	268	\color . . . . .	570	
LWR@emptyatbang . . . . .	269	color (package) . . . . .	410	
LWR@existingtabular . . . . .	303	\colorbox . . . . .	45	
LWR@freezethisfloat . . . . .	322	\colorboxBlock . . . . .	55, 6846	
LWR@infloatrow . . . . .	451	CombineHigherDepths (boolean) .	61, 223	
LWR@intabularmetadata . . . . .	269	comment (package) . . . . .	118	
LWR@minipagefullwidth . . . . .	371	Computer Modern . . . . .	69	
LWR@minipagethispar . . . . .	371	\ConTeXt . . . . .	7465	
LWR@skipatbang . . . . .	268	counters:		
LWR@skippingmcolrowcell . . . . .	268	FileDepth . . . . .	61, 223	
LWR@skippingmrowcell . . . . .	268	lofdepth . . . . .	331	
LWR@starredlongtable . . . . .	296	lotdepth . . . . .	331	
LWR@startedrow . . . . .	268	LWR@externalfilecnt . . . . .	337	

LWR@htmlfilename	196	ellipsis (package)	413
LWR@latesautopage	323	\emph	7192
LWR@lateximagedepth	354	emptypage (package)	414
LWR@lateximagenumber	354	\end@dblfloat	5911
LWR@LIPage	354	\end@float	5911
LWR@midrulecounter	288	\EndDefiningTabulars	4853
LWR@minipagedepth	369	endnotes (package)	414
LWR@nextautofloat	323	\enlargethispage	7390
LWR@nextautopage	323	\enskip	385, 7351
LWR@nextequation	339	enumerate (environment)	4725
LWR@prevFileDepth	231	enumerate (package)	415
LWR@spandepth	210	enumitem (package)	415
LWR@tablecolspos	275	environ (package)	127
LWR@tablecolswidth	275	environments:	
LWR@tabletotalcols	275	abstract	4597
LWR@tabletotalcolsnext	275	align	6564
LWR@thisfloat	322	align*	6587
SideTOCDepth	61, 329	BlockClass	3581
tocdepth	60	BVerbatim	183
\cpagerefFor	6953	center	6799
crop (package)	410	description	4753
cross-references		displaymath	6248
missing or incorrect	106	enumerate	4725
CSS		eqnarray	6420
file selection	75	equation	6371
lwarf.css	75	fcolorminipage	121, 6888
per HTML page	75	flalign	6610
project-specific changes	75	flalign*	6633
\CSSFilename	59, 62, 75, 3777	flushleft	6811
cuted (package)	411	flushright	6805
cutwin (package)	411	fminipage	79, 7140, 7188
<b>D</b>		gather	6518
danger icon	111	gather*	6541
\date	74	itemize	4711
dblfnote (package)	412	lateximage	6709
dcolumn (package)	412	longtable	2
debugging	106	LWR@nestspan	3425
HTML debug comments	133	LWR@tabular	5603
\DeclareGraphicsExtensions	2	LWRprint@fminipage	7164
Deja Vu	69	math	6247
description		minipage	7016
HTML meta tag	74, 218	multiline	6469
description (environment)	4753	multiline*	6493
displaymath (environment)	6248	picture	368, 6971
\dotfill	7286	quote	4622
draftwatermark (package)	412	theindex	6142
<b>E</b>		tikzpicture	8
ebook (package)	413	titlepage	73, 4438
titlingpage	14, 73	Verbatim	13

verbatim . . . . .	4679	project.css . . . . .	75
verse . . . . .	2	project.lwarpmkconf . . . . .	139
warpall . . . . .	72, 100	project_html.tex . . . . .	138
warpHTML . . . . .	50, 64, 72, 101	sample_project.css . . . . .	75, 176
warpprint . . . . .	63, 72, 101	tutorial.tex . . . . .	51
epigraph (package) . . . . .	416	FileSectionNames (boolean) . . . . .	62, 196
EPUB		fix2col (package) . . . . .	429
conversion software . . . . .	99	\flagverse . . . . .	563
HTML conversion settings . . . . .	99, 134	flalign (environment) . . . . .	6610
eqnarray (environment) . . . . .	6420	flalign* (environment) . . . . .	6633
equation		Flare (program) . . . . .	43
miss-numbered . . . . .	87, 89, 335, 494	float (package) . . . . .	429
equation (environment) . . . . .	6371	floatflt (package) . . . . .	430
error messages . . . . .	106	\floatname . . . . .	9
eso-pic (package) . . . . .	417	floatpag (package) . . . . .	431
etoolbox (package) . . . . .	113	\floatplacement . . . . .	12
everyhook (package) . . . . .	126	floatrow (package) . . . . .	431
everypage (package) . . . . .	417	\floatstyle . . . . .	15
everyshi (package) . . . . .	418	\flushbottom . . . . .	3346
expl3 (package) . . . . .	126	flushend (package) . . . . .	437
extramarks (package) . . . . .	418	flushleft (environment) . . . . .	6811
F		flushright (environment) . . . . .	6805
fancybox (package) . . . . .	419	fminipage (environment) . . . . .	79, 7140, 7188
fancyhdr (package) . . . . .	422	fncychap (package) . . . . .	437
fancyvrb (package) . . . . .	423	fnpos (package) . . . . .	438
FAQ . . . . .	106	font	
fbox		bitmapped . . . . .	69
around a minipage . . . . .	79	Computer Modern . . . . .	69
\fbox . . . . .	79, 7123	Deja Vu . . . . .	69
\fboxBlock . . . . .	79, 7132, 7187	ligatures . . . . .	69, 70
\fcolorbox . . . . .	67, 6852	packages . . . . .	69
\fcolorboxBlock . . . . .	87, 6887	selection . . . . .	69
fcolorminipage (environment)	121, 6888	size — lateximage . . . . .	87, 335, 354
figcaps (package) . . . . .	428	size — math, SVG . . . . .	87, 335, 354
file		size — xfrac . . . . .	574
inaccessible . . . . .	61	fontenc (package) . . . . .	69, 438
underscore . . . . .	60, 77	fontspec (package) . . . . .	69, 439
filecontents (package) . . . . .	126	footmisc (package) . . . . .	439
FileDepth (counter) . . . . .	61, 223	footnote (package) . . . . .	440
files:		footnotehyper (package) . . . . .	441
glyptounicode . . . . .	70	footnotes . . . . .	218
lwarp.css . . . . .	75, 140	for	
lwarp.xdy . . . . .	75, 176	HTML & PRINT . . . . .	111
lwarp_formal.css . . . . .	171	HTML output . . . . .	111
lwarp_mathjax.txt . . . . .	177	PRINT output . . . . .	111
lwarp_sagebrush.css . . . . .	166	\ForceHTMLPage . . . . .	84, 4023
lwarp_tutorial.txt . . . . .	51	\ForceHTMLTOC . . . . .	84, 4029
lwarpmk.conf . . . . .	138	FormatEPUB (boolean) . . . . .	99, 134
lwarpmk.lua . . . . .	104	FormatWordProcessor (boolean) . . . . .	101, 134
		\framebox . . . . .	7102

framed (package) . . . . .	441
framed objects . . . . .	79
FrameMaker (program) . . . . .	43
Frequently Asked Questions . . . . .	106
\frontmatter . . . . .	4045
ftnright (package) . . . . .	444
fullpage (package) . . . . .	444
fullwidth (package) . . . . .	444
\fup . . . . .	7282
\fussy . . . . .	3348
<b>G</b>	
gather (environment) . . . . .	6518
gather* (environment) . . . . .	6541
GELLMU (program) . . . . .	41
generator	
HTML meta tag . . . . .	239
geometry (package) . . . . .	125, 445
gettitlestring (package) . . . . .	126
GladTeX (program) . . . . .	42
glossaries (package) . . . . .	85, 445
glossary	
language . . . . .	67
processing . . . . .	67
glyptounicode (file) . . . . .	70
graphics (package) . . . . .	361, 447
graphicx (package) . . . . .	361, 457
grffile (package) . . . . .	457
<b>H</b>	
Hevea (program) . . . . .	41
\hfill . . . . .	7284
\HomeHTMLFilename . . . . .	3254
HomeHTMLFilename (option) . . . . .	60, 117
horizontal space . . . . .	76
between minipages . . . . .	384
\href . . . . .	5842
\rulefill . . . . .	7285
\hskip . . . . .	76
\hspace . . . . .	76, 385, 7381
HTML	
commands for a successful conver-	
sion . . . . .	76
conversion settings . . . . .	60
debug comments . . . . .	133
EPUB . . . . .	99, 134
word processor . . . . .	101, 102, 134
filename generation . . . . .	62
headings . . . . .	109
in place of SVG images . . . . .	57, 107
meta tag	
author . . . . .	74, 218
description . . . . .	74, 218
generator . . . . .	239
viewport . . . . .	240
tabular column conversion . . . . .	281
\HTMLAuthor . . . . .	63, 74, 3791
HTMLDebugComments (boolean) . . . . .	133
\HTMLDescription . . . . .	63, 74, 3797
\HTMLEntity . . . . .	3235
\HTMLFilename . . . . .	3253
HTMLFilename (option) . . . . .	60, 117
\HTMLFirstPageTop . . . . .	63, 3754
htmlglossary (option) [lwarpmk] . . . . .	86, 446
\HTMLLanguage . . . . .	63, 4272
HTMLleftmargini (length) . . . . .	97, 256, 257, 563
HTMLMarkFloats (boolean) . . . . .	102, 134
\HTMLPageBottom . . . . .	63, 246, 3770
\HTMLPageTop . . . . .	63, 3762
\HTMLUnicode . . . . .	3243
HTMLvleftskip (length) . . . . .	97, 256, 257, 563
\hyperindexref . . . . .	6178
hyperref (package) . . . . .	317, 457
\hypertoc . . . . .	6088
\hypertocfloat . . . . .	6101
hyperxmp (package) . . . . .	462
<b>I</b>	
icon	
warning . . . . .	111
\idxlayout (package) . . . . .	462
ifplatform (package) . . . . .	113
images	
graphicx package . . . . .	361
in strange places . . . . .	107
showing as HTML . . . . .	57, 107
\include . . . . .	450
\includegraphics . . . . .	181
indentfirst (package) . . . . .	463
InDesign (program) . . . . .	43
index	
language . . . . .	67
placement and toc options . . . . .	86
processing . . . . .	55, 56
UTF-8 . . . . .	70
IndexLanguage (option) . . . . .	67, 86, 116, 446, 551
\InlineClass . . . . .	3601
inputenc (package) . . . . .	69, 463
internet (class) . . . . .	41

item		LibreOffice (program) . . . . .	42	
empty	. . . . .	ligatures . . . . .	69, 70, 124	
itemize (environment)	. . . . .	line numbers . . . . .	111	
\itshape	. . . . .	\linebreak . . . . .	7384	
		\LinkHome . . . . .	3304	
		Linux (program) . . . . .	71, 114	
J		lips (package) . . . . .	466	
JavaScript		list item, empty . . . . .	77, 261	
MathJax	. . . . .	listings (package) . . . . .	467	
		\listof . . . . .	6054	
K		lmodern (package) . . . . .	69	
\kern	. . . . .	lofdepth (counter) . . . . .	331	
keyfloat (package)	. . . . .	longtable (environment) . . . . .	2	
kvoptions (package)	. . . . .	longtable (package) . . . . .	470	
		lotdepth (counter) . . . . .	331	
L		lscape (package) . . . . .	472	
label		ltcaption (package) . . . . .	472	
in HTML	. . . . .	LuaTeX		
glossary	. . . . .	detection . . . . .	124	
index	. . . . .	file & section names . . . . .	228	
language HTML metadata	. . . . .	\LuaTeX	. . . . .	7459
\LaTeX	. . . . .	LuaTeX (program) [requirement]	. . . . .	45
\LaTeX2HTML (program)	. . . . .	\LuaTeX	. . . . .	7459
\LaTeXe	. . . . .	lwarp		
lateximage (environment)	. . . . .	loading . . . . .	70	
\LateximageFontSizeName	. . . . .	options . . . . .	70	
lateximages		lwarp (package) . . . . .	70	
font size	. . . . .	lwarp.css (file) . . . . .	75, 140	
latexmk (option)	. . . . .	lwarp.xdy		
customizing . . . . .	75			
LaTeXML (program)	. . . . .	lwarp.xdy (file) . . . . .	75, 176	
layout (package)	. . . . .	lwarp_formal.css (file) . . . . .	171	
lengths:		lwarp_mathjax.txt (file) . . . . .	177	
HTMLleftmargini	. . . . .	lwarp_sagebrush.css (file) . . . . .	166	
HTMLvleftskip	. . . . .	lwarp_tutorial.txt (file) . . . . .	51	
LWR@minipageheight	. . . . .	lwarpmk		
LWR@minipagewidth	. . . . .	customizing . . . . .	104	
LWR@tempheight	. . . . .	[lwarpmk]:		
LWR@tempraise	. . . . .	htmlglossary (option) . . . . .	86, 446	
LWR@tempwidth	. . . . .	printglossary (option) . . . . .	86, 446	
\LWR@cmidrulewidth	. . . . .	lwarpmk (option) . . . . .	116	
\LWR@heavyrulewidth	. . . . .	lwarpmk (program) . . . . .	104, 179	
\LWR@lightrulewidth	. . . . .	lwarpmk.conf (file) . . . . .	138	
\LWR@thiscmidrulewidth	. . . . .	lwarpmk.lua (file) . . . . .	104	
\VerbatimHTMLWidth	. . . . .	\LWR@addcmidruletrim . . . . .	5241	
vleftmargini	. . . . .	\LWR@addcmidrulewidth . . . . .	5263	
vleftskip	. . . . .	\LWR@addleftmostbartag . . . . .	5144	
letltxmacro (package)	. . . . .	\LWR@addmathjax . . . . .	6360	
letterspace (package)	. . . . .	\LWR@addrulewidth . . . . .	5246	
lettrine (package)	. . . . .	\LWR@afterendverbatim . . . . .	4663	

\LWR@amsmultiline (boolean) . . . . .	<a href="#">345</a>	\LWR@getexparray . . . . .	<a href="#">3231</a>
\LWR@atbeginverbatim . . . . .	<a href="#">4649</a>	\LWR@getmynexttoken . . . . .	<a href="#">4786</a>
\LWR@beginhideamsmath . . . . .	<a href="#">6405</a>	\LWR@heavyrulewidth (length) . . . . .	<a href="#">288</a>
\LWR@blackborderpadding . . . . .	<a href="#">7118</a>	\LWR@hidelatexequation . . . . .	<a href="#">6346</a>
\LWR@botnavigation . . . . .	<a href="#">3312</a>	\LWR@hline . . . . .	<a href="#">5581</a>
\LWR@caption@begin . . . . .	<a href="#">5933</a>	\LWR@hspace . . . . .	<a href="#">7359</a>
\LWR@caption@end . . . . .	<a href="#">5943</a>	\LWR@htmlblockcomment . . . . .	<a href="#">3521</a>
\LWR@clearmidrules . . . . .	<a href="#">5204</a>	\LWR@htmlblocktag . . . . .	<a href="#">3529</a>
\LWR@closeparagraph . . . . .	<a href="#">3669</a>	\LWR@htmlclosecomment . . . . .	<a href="#">3493</a>
\LWR@closeprevious . . . . .	<a href="#">3332</a>	\LWR@htmlcomment . . . . .	<a href="#">3514</a>
\LWR@closetabledatacell . . . . .	<a href="#">4814</a>	\LWR@htmldivclass . . . . .	<a href="#">3558</a>
\LWR@cmidrulewidth (length) . . . . .	<a href="#">288</a>	\LWR@htmldivclassend . . . . .	<a href="#">3561</a>
\LWR@col afterspec . . . . .	<a href="#">275</a>	\LWR@htmlelement . . . . .	<a href="#">3571</a>
\LWR@colat spec . . . . .	<a href="#">275</a>	\LWR@htmlelementclass . . . . .	<a href="#">3545</a>
\LWR@colbangspec . . . . .	<a href="#">275</a>	\LWR@htmlelementclassend . . . . .	<a href="#">3550</a>
\LWR@colbarspec . . . . .	<a href="#">275</a>	\LWR@htmlelementclassline . . . . .	<a href="#">3564</a>
\LWR@colbefore spec . . . . .	<a href="#">275</a>	\LWR@htmlelementend . . . . .	<a href="#">3574</a>
\LWR@copyfile . . . . .	<a href="#">485</a>	\LWR@htmlfilenumber (counter) . . . . .	<a href="#">196</a>
\LWR@createautosec . . . . .	<a href="#">4054</a>	\LWR@htmlfileref . . . . .	<a href="#">5725</a>
\LWR@currentcss . . . . .	<a href="#">3776</a>	\LWR@htmlmathlabel . . . . .	<a href="#">6391</a>
\LWR@currenttextcolor . . . . .	<a href="#">7391</a>	\LWR@htmlmulticolumn . . . . .	<a href="#">5365</a>
\LWR@descitem . . . . .	<a href="#">4739</a>	\LWR@htmlopencomment . . . . .	<a href="#">3493</a>
\LWR@docmidrule . . . . .	<a href="#">5229</a>	\LWR@htmlrefsectionfilename . . . . .	<a href="#">3297</a>
\LWR@doingapar (boolean) . . . . .	<a href="#">210</a>	\LWR@HTMLsanitize . . . . .	<a href="#">6670</a>
\LWR@doingcmidrule (boolean) . . . . .	<a href="#">268</a>	\LWR@HTMLsanitizeexpand . . . . .	<a href="#">6691</a>
\LWR@doinghline (boolean) . . . . .	<a href="#">268</a>	\LWR@htmlsectionfilename . . . . .	<a href="#">3264</a>
\LWR@doingstartpars (boolean) . . . . .	<a href="#">210</a>	\LWR@htmlspan . . . . .	<a href="#">3466</a>
\LWR@doingtbrule (boolean) . . . . .	<a href="#">268</a>	\LWR@htmlspanclass . . . . .	<a href="#">3474</a>
\LWR@domulticolumn . . . . .	<a href="#">5338</a>	\LWR@htmntag . . . . .	<a href="#">3484</a>
\LWR@doubledollar . . . . .	<a href="#">6204</a>	\LWR@htmntagc . . . . .	<a href="#">3415</a>
\LWR@emptyatbang (boolean) . . . . .	<a href="#">269</a>	\LWR@includegraphicsb . . . . .	<a href="#">100</a>
\LWR@endhideamsmath . . . . .	<a href="#">6413</a>	\LWR@indexitem . . . . .	<a href="#">6152, 6156, 6160</a>
\LWR@endminipage . . . . .	<a href="#">6980</a>	\LWR@infloatatrow (boolean) . . . . .	<a href="#">451</a>
\LWR@endofline . . . . .	<a href="#">7334</a>	\LWR@instartatbangcols . . . . .	<a href="#">4806</a>
\LWR@endsubminipage . . . . .	<a href="#">7001</a>	\LWR@intabularmetadata (boolean) . . . . .	<a href="#">269</a>
\LWR@ensuredoingapar . . . . .	<a href="#">3642</a>	\LWR@itemizeitem . . . . .	<a href="#">4704</a>
\LWR@epubprintpendingfootnotes .	<a href="#">3873</a>	\LWR@latestautopage (counter) . . . . .	<a href="#">323</a>
\LWR@exittingtabular (boolean) . . . . .	<a href="#">303</a>	\LWR@latexitimagedepth (counter) . . . . .	<a href="#">354</a>
\LWR@externalfilecnt (counter) . . . . .	<a href="#">337</a>	\LWR@latexitimagedepthref . . . . .	<a href="#">5729</a>
\LWR@filenamenoblocks . . . . .	<a href="#">3893</a>	\LWR@latexitimagenumber (counter) . . . . .	<a href="#">354</a>
\LWR@filestart . . . . .	<a href="#">4279</a>	\LWR@latexitimagenumberref . . . . .	<a href="#">5732</a>
\LWR@findword . . . . .	<a href="#">379</a>	\LWR@latexitimagesfile . . . . .	<a href="#">447</a>
\LWR@floatbegin . . . . .	<a href="#">5881</a>	\LWR@lightrulewidth (length) . . . . .	<a href="#">288</a>
\LWR@floatend . . . . .	<a href="#">5899</a>	\LWR@LIpage (counter) . . . . .	<a href="#">354</a>
\LWR@footnotetext . . . . .	<a href="#">3808</a>	\LWR@loadafter . . . . .	<a href="#">111</a>
\LWR@forceminwidth . . . . .	<a href="#">7107</a>	\LWR@loadbefore . . . . .	<a href="#">122</a>
\LWR@forcenewpage . . . . .	<a href="#">3338</a>	\LWR@loadnever . . . . .	<a href="#">131</a>
\LWR@freezethisfloat (boolean) . . . . .	<a href="#">322</a>	\LWR@longtabledatacaptiontag . . . . .	<a href="#">5376</a>
\LWR@futurenonospacelet . . . . .	<a href="#">4779</a>	\LWR@lookforpackagename . . . . .	<a href="#">382</a>
\LWR@FVstyle . . . . .	<a href="#">17</a>	\LWR@LwarpEnd . . . . .	<a href="#">4398, 7495</a>

\LWR@LwarpStart . . . . .	4329, 7495	\LWR@printthetitle . . . . .	4462
\LWR@maketitlesetup . . . . .	33, 4503	\LWR@ProvidesPackageDrop . . . . .	434
\LWR@maybeinthisfloat . . . . .	5916	\LWR@ProvidesPackagePass . . . . .	422
\LWR@maybenewtablerow . . . . .	5088	\LWR@pushoneclose . . . . .	4057
LWR@midrulecounter (counter) . . . . .	288	\LWR@quickfile . . . . .	444
LWR@midrules . . . . .	288	\LWR@requesttoc . . . . .	4391
LWR@minipagedepth (counter) . . . . .	369	\LWR@requirepackagenames . . . . .	378
LWR@minipagefullwidth (boolean) . . . . .	371	\LWR@restoreorigaccents . . . . .	617
LWR@minipageheight (length) . . . . .	369	\LWR@restoreorigformatting . . . . .	6270
\LWR@minipagestartpars . . . . .	7339	\LWR@restoreorigprintxcolor . . . . .	6926
\LWR@minipagestoppars . . . . .	7342	\LWR@rotboxorigin . . . . .	193
LWR@minipagethispar (boolean) . . . . .	371	\LWR@rotstyle . . . . .	91
LWR@minipagewidth (length) . . . . .	369	\LWR@rule . . . . .	7392
\LWR@multicolother . . . . .	5289	\LWR@scalesstyle . . . . .	94
\LWR@multicolpartext . . . . .	5284	\LWR@section . . . . .	4067
\LWR@multicolskip . . . . .	5295	\LWR@sectionnumber . . . . .	4051
\LWR@multirowborder . . . . .	3	\LWR@setexparray . . . . .	3226
\LWR@mynexttoken . . . . .	4778	\LWR@setlatestname . . . . .	5701
\LWR@myshorttoc . . . . .	5998	\LWR@setOSWindows . . . . .	29
\LWR@nameref . . . . .	5722	\LWR@sidetoc . . . . .	6067
LWR@nestspan (environment) . . . . .	3425	\LWR@singledollar . . . . .	6216
\LWR@newhtmlfile . . . . .	3959	\LWR@skipatbang (boolean) . . . . .	268
\LWR@newlabel . . . . .	5759	\LWR@skippingmcolrowcell (boolean) . . . . .	268
\LWR@newref . . . . .	5809	\LWR@skippingmrowcell (boolean) . . . . .	268
LWR@nextautofloat (counter) . . . . .	323	\LWR@spandepth (counter) . . . . .	210
LWR@nextautopage (counter) . . . . .	323	\LWR@splabel . . . . .	5735
LWR@nextequation (counter) . . . . .	339	\LWR@starredlongtable (boolean) . . . . .	296
\LWR@nohspace . . . . .	7380	\LWR@startedrow (boolean) . . . . .	268
\LWR@nullfonts . . . . .	7236	\LWR@startnewdepth . . . . .	4058
\LWR@nullifyNoAutoSpacing . . . . .	5590	\LWR@startpars . . . . .	3706
\LWR@openparagraph . . . . .	3647	\LWR@startref . . . . .	5772
\LWR@origcolspec . . . . .	4921	\LWR@stoppars . . . . .	3722
\LWR@originname . . . . .	194	\LWR@stripperiod . . . . .	5700
\LWR@originnames . . . . .	201	\LWR@strresult . . . . .	4919
\LWR@parseaftercolumn . . . . .	4981	\LWR@subaddcmidruletrim . . . . .	5233
\LWR@parseatcolumn . . . . .	4927	\LWR@subcmidrule . . . . .	5218
\LWR@parsebangcolumn . . . . .	4951	\LWR@subhtmlelementclass . . . . .	3534
\LWR@parsebarcolumn . . . . .	4991	\LWR@subhyperref . . . . .	5833
\LWR@parsebeforecolumn . . . . .	4972	\LWR@subhyperrefclass . . . . .	5837
\LWR@parseDcolumn . . . . .	5018	\LWR@subinlineimage . . . . .	5874
\LWR@parsenormalcolumn . . . . .	5002	\LWR@subminipage . . . . .	6995
\LWR@parsepcolumn . . . . .	5014	\LWR@subnewref . . . . .	5803
\LWR@parsetablecols . . . . .	5023	\LWR@subsublabel . . . . .	5738
\LWR@patchlists . . . . .	4767	\LWR@subtableofcontents . . . . .	6013
LWR@prevFileDepth (counter) . . . . .	231	\LWR@syncmathjax . . . . .	6250
\LWR@printatbang . . . . .	5124	\LWR@tablecolspec . . . . .	4918
\LWR@printbartag . . . . .	5110	\LWR@tablecolspos (counter) . . . . .	275
\LWR@printmcoldata . . . . .	5298	\LWR@tablecolswidth (counter) . . . . .	275
\LWR@printmcolttype . . . . .	5268	\LWR@tabledatacolumntag . . . . .	5510
\LWR@printpendingfootnotes . . . . .	3863	\LWR@tabledatasinglecolumntag . . . . .	5157

LWR@tableparcell (boolean) . . . . .	268	MathJax summary . . . . .	88, 336
LWR@tabletotalcols (counter) . . . . .	275	mathsvg option . . . . .	116
LWR@tabletotalcolsnext (counter) . . .	275	showing as HTML . . . . .	57, 107
LWR@tabular (environment) . . . . .	5603	SVG summary . . . . .	87, 335
\LWR@tabularendofline . . . . .	4895	math (environment) . . . . .	6247
\LWR@tabularfinishrow . . . . .	4870	MathJax	
\LWR@tabularhtmlcolumns . . . . .	5442	mathjax option . . . . .	116
\LWR@tabularleftedge . . . . .	5149	subequations . . . . .	88, 336
LWR@tabularmutemods (boolean) . . . . .	303	summary . . . . .	88, 336
LWR@tempheight (length) . . . . .	386	tagged equations . . . . .	88, 336
LWR@temppraise (length) . . . . .	386	MathJax (program) . . . . .	88, 336
LWR@tempwidth (length) . . . . .	386	MathJax (program) [requirement] . . . . .	45
\LWR@thiscmidrulewidth (length) . . . .	288	mathjax (boolean) . . . . .	115
\LWR@thisfilename . . . . .	3891	mathjax (option) . . . . .	60, 70, 116
LWR@thisfloat (counter) . . . . .	322	mathsvg (option) . . . . .	60, 70, 116
\LWR@thisnewfilename . . . . .	3892	mcaption (package) . . . . .	474
\LWR@titlingmaketitle . . . . .	76, 4551	\mcolrowcell . . . . .	5571
\LWR@topnavigation . . . . .	3309	mdframed (package) . . . . .	474
\LWR@traceinfo . . . . .	506	\mdseries . . . . .	7268
LWR@tracingl warp (boolean) . . . . .	133	memoir	
LWR@triml rules . . . . .	288	verse . . . . .	563
LWR@trimrrules . . . . .	288	memoir (package) . . . . .	563
LWR@validtablecol (boolean) . . . . .	280	meta tag, HTML	
LWR@verbtags (boolean) . . . . .	258	author . . . . .	74, 218
\LWR@vspace . . . . .	7382	description . . . . .	74, 218
LWRprint@fminipage (environment) . . .	7164	generator . . . . .	239
\LWRsetnextfloat . . . . .	5924	viewport . . . . .	240
\LyX . . . . .	7476	metalogo (package) . . . . .	483
		microtype (package) . . . . .	70, 124, 483
		midfloat (package) . . . . .	484
		\MiKTeX . . . . .	7475
		minipage	
		framed . . . . .	79
		horizontal space between . . . . .	384
		minipage (environment) . . . . .	7016
		\minipagewidth . . . . .	7008
		misplaced \noalign . . . . .	94, 266
		misplaced alignment tab character & . . . . .	
		. . . . .	92, 264, 271
		missing sections . . . . .	61
		moreverb (package) . . . . .	484
		\mparhack (package) . . . . .	486
		\mrowcell . . . . .	5568
		MS-Windows (program) . . . . .	71, 114
		multicol (package) . . . . .	486
		multicolumn	
		with multirow . . . . .	490
		\multicolumnrow . . . . .	33, 5463
		multirow	
		with multicolumn . . . . .	490

\multirow	488	lwarpmk	116
multirow (package)	487	mathjax	60, 70, 116
multline (environment)	6469	mathsvg	60, 70, 116
multline* (environment)	6493	OSWindows	71, 114, 117
<b>N</b>			
\Nameref	5830	warpHTML	70, 115
\nameref	5821	warpprint	70, 115
nameref (package)	491	xdyFilename	76, 116
needspace (package)	491	\OSPathSymbol	28
newclude (package)	97, 491	OSWindows (option)	71, 114, 117
newfloat		<b>P</b>	
with trivfloat, algorithmic	560	packages	
\newfloat	2, 4	required	123
\newfloat (package)	127	packages:	
\newline	7332	a4	395
\newtheorem	259	a4wide	395
newtxmath (package)	89	a5comb	395
newunicodechar (package)	69, 492	abstract	395
nextpage (package)	492	addlines	398
nicefrac (package)	89	adjmulticol	397
\nolinebreak	7385	afterpackage	125
\nolinkurl	5854	afterpage	398
nonumonpart (package)	492	algorithmicx	399
\nopagebreak	7389	alltt	399
\nopagecolor	44	amsmath	128
nopageno (package)	493	amsthm	400
\normalfont	7276	anonchap	402
nowidow (package)	493	any size	403
ntheorem (package)	493	appendix	403
\numberline	6085	arabicfront	404
numbers		array	310
left margin	111	authblk	404
numindex (option) [tocbibind]	87, 552	babel	98
<b>O</b>			
OpenOffice (program)	42	balance	405
options:		bigdelim	405
[lwarpmk]:		bigstrut	407
htmlglossary	86, 446	bookmark	407
printglossary	86, 446	booktabs	407
[tocbibind]:		boxedminipage	408
numindex	87, 552	boxedminipage2e	408
[tocloft]:		calc	127
titles	84	caption	127
BaseJobname	116	caption2	409
HomeHTMLFilename	60, 117	ccaption	409
HTMLFilename	60, 117	change page	409
IndexLanguage	67, 86, 116, 446, 551	chappg	410
latexmk	60, 117	chngpage	409
		cleveref	366
		cmap	70
		color	410

comment	118	hyperref	317, 457
crop	410	hyperxmp	462
cuted	411	idxlayout	462
cutwin	411	ifplatform	113
dblifnote	412	indentfirst	463
dcolumn	412	inputenc	69, 463
draftwatermark	412	keyfloat	463
ebook	413	kvoptions	115
ellipsis	413	layout	464
emptypage	414	letltxmacro	113
endnotes	414	letterspace	465
enumerate	415	lettrine	465
enumitem	415	lips	466
environ	127	listings	467
epigraph	416	lmodern	69
eso-pic	417	longtable	470
etoolbox	113	lscape	472
everyhook	126	ltcaption	472
everypage	417	lwarp	70
everyshi	418	makeidx	127
expl3	126	margininfit	473
extramarks	418	marginifix	473
fancybox	419	marginnote	473
fancyhdr	422	mcaption	474
fancyvrb	423	mdframed	474
figcaps	428	memoir	563
filecontents	126	metalogo	483
fix2col	429	microtype	70, 124, 483
float	429	midfloat	484
floatflt	430	moreverb	484
floatpag	431	mparhack	486
floatrow	431	multicol	486
flushend	437	multirow	487
fncychap	437	nameref	491
fnpos	438	needspace	491
fontenc	69, 438	newclude	97, 491
fontspec	69, 439	newfloat	127
footmisc	439	newtxmath	89
footnote	440	newunicodechar	69, 492
footnotehyper	441	nextpage	492
framed	441	nicefrac	89
ftnright	444	nonumonpart	492
fullpage	444	nopageno	493
fullwidth	444	nowidow	493
geometry	125, 445	ntheorem	493
gettitlestring	126	pagenote	504
glossaries	85, 445	paralist	504
graphics	361, 447	parskip	505
graphicx	361, 457	pdflscape	505
grffile	457	pdfsync	505

pfnote	506	wallpaper	564
placeins	506	wrapfig	565
prelim2e	506	xcolor	566
quotchap	507	xfrac	574
ragged2e	508	xifthen	126
realscripts	509	xltextra	576
refcount	127	xmpincl	577
relsize	510	xparse	125
romanbar	511	xstring	126, 127
romanbarpagenumber	511	xtab	577
rotating	512	zref	127
rotfloat	512	zwpagelayout	579
savetrees	513	page	
scalefnt	513	inaccessible	61
sectsty	513	\pagebreak	7386
setspace	514	\pagecolor	43
shadow	515	pagenote (package)	504
showidx	516	\pagenumbering	3349
showkeys	516	\pageref	5816
sidecap	516	\pagerefPageFor	5815
sidenotes	517	\pagestyle	3341
siunitx	89, 361, 519	Pandoc (program)	42
soul	519	\paragraph	4254
stabular	521	paralist (package)	504
subfig	521	\parbox	7072
supertabular	527	\parsemulticolumnalignment	5325
syntonly	528	parskip (package)	505
tabls	529	\part	4205
tabularx	529	pdfcrop (program) [requirement]	45
tabulary	530	pdfLaTeX (program) [requirement]	45
textarea	530	pdflscape (package)	505
textcomp	70, 531	pdfseparate (program) [requirement]	
textpos	534		45, 49
theorem	534	pdfsync (package)	505
threeparttable	538	pdftocairo (program) [requirement]	45, 49
tikz	539	pdftotext (program) [requirement]	45, 49
titleps	540	Perl	50
titleref	543	perl (program) [requirement]	50
titlesec	543	pfnote (package)	506
titletoc	545	\phantomsection	7437
titling	546	picture (environment)	368, 6971
tocbibind	87, 551	placeins (package)	506
tocloft	553	Plastex (program)	41
transparent	558	\popclose	3199
trivfloat	559	Poppler	45, 49
typearea	560	prelim2e (package)	506
ulem	561	\printauthor	246, 4470, 4489
units	89	\printdate	246, 4481, 4491
upref	562	printglossary (option) [lwarpmk]	86, 446
verse	562, 563	\printindex	6135

\PrintStack . . . . .	3317	\pushclose . . . . .	3172
\printthanks . . . . .	246, 248		
\printtitle . . . . .	246, 4454, 4488		
problems . . . . .	106	\qqquad . . . . .	385, 7350
programs		\quad . . . . .	385, 7345
utility . . . . .	44	quotchap (package) . . . . .	507
programs:		quote (environment) . . . . .	4622
[requirement]:			
LuaLaTeX . . . . .	45		<b>R</b>
MathJax . . . . .	45	ragged2e (package) . . . . .	508
pdfcrop . . . . .	45	\raggedbottom . . . . .	3345
pdfLaTeX . . . . .	45	\raggedleft . . . . .	242
pdfseparate . . . . .	45, 49	\raggedright . . . . .	242
pdftocairo . . . . .	45, 49	\raisebox . . . . .	7157
pdftotext . . . . .	45, 49	realscripts (package) . . . . .	509
perl . . . . .	50	\ref . . . . .	5809
XeLaTeX . . . . .	45	refcount (package) . . . . .	127
Adobe . . . . .	43	\reflectbox . . . . .	247
AsciiDoc . . . . .	42	relsize (package) . . . . .	510
AsciiDoctor . . . . .	42	[requirement]:	
Asciidoc-LaTeX . . . . .	42	LuaLaTeX (program) . . . . .	45
Flare . . . . .	43	MathJax (program) . . . . .	45
FrameMaker . . . . .	43	pdfcrop (program) . . . . .	45
GELLMU . . . . .	41	pdfLaTeX (program) . . . . .	45
GladTeX . . . . .	42	pdfseparate (program) . . . . .	45, 49
Hevea . . . . .	41	pdftocairo (program) . . . . .	45, 49
InDesign . . . . .	43	pdftotext (program) . . . . .	45, 49
LaTeX2HTML . . . . .	41	perl (program) . . . . .	50
LaTeXML . . . . .	41	XeLaTeX (program) . . . . .	45
LibreOffice . . . . .	42	\RequirePackage . . . . .	398
Linux . . . . .	71, 114	\resizebox . . . . .	252
lwarpmk . . . . .	104, 179	\restylefloat . . . . .	17
Mac OS . . . . .	71, 114	\ResumeTabular . . . . .	5497
Madcap . . . . .	43	\rmfamily . . . . .	7270
MathJax . . . . .	88, 336	romanbar (package) . . . . .	511
MS-Windows . . . . .	71, 114	romanbarpagenumber (package) . . . . .	511
OpenOffice . . . . .	42	\rotatebox . . . . .	213
Pandoc . . . . .	42	rotating (package) . . . . .	512
Plastex . . . . .	41	rotfloat (package) . . . . .	512
TeX2page . . . . .	41	\rule . . . . .	7434
TeX4ht . . . . .	41		<b>S</b>
TtH . . . . .	41		
Unix . . . . .	71, 114	sample_project.css (file) . . . . .	75, 176
Windows . . . . .	71, 114	savetrees (package) . . . . .	513
Word . . . . .	42	\sb . . . . .	7278
xindy . . . . .	75	\scalebox . . . . .	232
project.css (file) . . . . .	75	scalefnt (package) . . . . .	513
project.lwarpmkconf (file) . . . . .	139	\scshape . . . . .	7275
project_html.tex (file) . . . . .	138	section	
published . . . . .	253	depths . . . . .	109



tikzpicture (environment) . . . . .	8	file & section names . . . . .	228
\title . . . . .	73	index . . . . .	70
titlepage		selection . . . . .	69
subtitle and published . . . . .	253	utility	
titlepage (environment) . . . . .	73, 4438	programs . . . . .	44
titleps (package) . . . . .	540	V	
titleref (package) . . . . .	543	Verbatim (environment) . . . . .	13
titles (option) [tocloft] . . . . .	84	verbatim (environment) . . . . .	4679
titlesec (package) . . . . .	543	\VerbatimHTMLWidth (length) . . . . .	257
titletoc (package) . . . . .	545	\verbatiminput . . . . .	4671
titling (package) . . . . .	546	verse (environment) . . . . .	2
titlingpage (environment) . . . . .	14, 73	verse (package) . . . . .	562, 563
[tocbibind]:		viewport	
numindex (option) . . . . .	87, 552	HTML meta tag . . . . .	240
tocbibind (package) . . . . .	87, 551	vleftmargini (length) . . . . .	97, 256, 563
tocdepth (counter) . . . . .	60	vleftskip (length) . . . . .	97, 256, 563
[tocloft]:		\vspace . . . . .	7383
titles (option) . . . . .	84	W	
tocloft (package) . . . . .	553	wallpaper (package) . . . . .	564
\tracingl warp . . . . .	108, 505	warning icon . . . . .	111
transparent (package) . . . . .	558	warpall (environment) . . . . .	72, 100
trivfloat		warpHTML (environment) . . . . .	50, 64, 72, 101
with newfloat, algorithmic . . . . .	560	warpHTML (option) . . . . .	70, 115
trivfloat (package) . . . . .	559	\warpHTMLonly . . . . .	64, 72, 90
troubleshooting . . . . .	106	warpingHTML (boolean) . . . . .	115
HTML debug comments . . . . .	133	warpingprint (boolean) . . . . .	115
\ttfamily . . . . .	7272	warpprint (environment) . . . . .	63, 72, 101
TtH (program) . . . . .	41	warpprint (option) . . . . .	70, 115
tutorial.tex (file) . . . . .	51	\warpprintonly . . . . .	64, 72, 89
typearea (package) . . . . .	560	Windows (program) . . . . .	71, 114
U		Word (program) . . . . .	42
ulem (package) . . . . .	561	word processor	
\underline . . . . .	7283	HTML conversion settings	101, 102, 134
underscore		wrapfig (package) . . . . .	565
filename . . . . .	60, 77	X	
Unicode		xcolor (package) . . . . .	566
enhanced coverage . . . . .	69	xdyFilename (option) . . . . .	76, 116
file & section names . . . . .	228	XeTeX	
input characters . . . . .	112	detection . . . . .	124
selection . . . . .	69	file & section names . . . . .	228
units (package) . . . . .	89	\XeTeX . . . . .	7461
Unix (program) . . . . .	71, 114	XeTeX (program) [requirement] . . . . .	45
\up . . . . .	7281	\XeTeX . . . . .	7461
upref (package) . . . . .	562	xfrac (package) . . . . .	574
\upshape . . . . .	7273	\xfracHTMLfontsize . . . . .	3
\url . . . . .	5861	xifthen (package) . . . . .	126
usingOSWindows (boolean) . . . . .	114		
UTF-8			
enhanced coverage . . . . .	69		

xindy		xstring (package) . . . . .	<i>126, 127</i>
customizing . . . . .	<i>75</i>	xtab (package) . . . . .	<i>577</i>
xindy (program) . . . . .	<i>75</i>		
xltextra (package) . . . . .	<i>576</i>		<b>Z</b>
xmpincl (package) . . . . .	<i>577</i>	zref (package) . . . . .	<i>127</i>
xpars e (package) . . . . .	<i>125</i>	zwpagelayout (package) . . . . .	<i>579</i>