

The magaz package*

Donald Arseneau, `asnd@triumf.ca`, Vancouver, Canada

04-Sep-2003

This software is free to distribute, unaltered, and to use in any application. It may be altered and incorporated in other software freely.

This version is just a single tool from a larger body of tools I might try to implement if I ever have the spare time. I'm writing this part now [1999] in response to a request on `comp.text.tex`.

- Yes Special formatting for first line of text in a paragraph
- No Special formatting for for first n lines (allow each different)
- No Also for first character (drop caps) (working together)
- No "Continued on"/"continued from" markers
- No wrapfig spanning columns
- No wrapfig placed at fixed location on page
- NO! Piecing together fragments of gallies to fit page

Instructions:

The `"\FirstLine"` command takes one argument: Some text.

The first line of this text will be formatted according to `"\FirstLineFont"`; but if the text occupies less than a line, all that text (and no more) will be affected by `"\FirstLineFont"`. The argument should be ordinary text, not lists and displayed equations. Such things will give you a 'Bad text' error.

This command is intended to be used in a replacement for a normal sectioning command in a document class; `"\paragraph"` would be appropriate. In particular, this `"\paragraph"` (or whatever) should insert vertical space and penalties etc., and probably `"\noindent"` at the start of the argument. The document class should also define `"\FirstLineFont"` appropriately as either a switch or a text-command; as in `"\renewcommand\FirstLineFont{\MakeUppercase}"`. The default definition is `"\providecommand\FirstLineFont{\scshape}"`.

*This manual corresponds to `magaz` v0.2, dated 04-Sep-2003.