The mathastext package

JEAN-FRANÇOIS BURNOL jfbu (at) free (dot) fr Package version: 1.3p (2016/05/13)

The mathastext package changes the fonts which are used in math mode for letters, digits and a few other punctuation and symbol signs to replace them with the font as used for the document text. Thus, the package makes it possible to use a quite arbitrary font without worrying too much that it does not have specially designed accompanying math fonts. Also, mathastext provides a simple mechanism in order to use more than one math-as-text font in the same document.

'mathastext' is a LaTeX package

\usepackage{mathastext}

The document will use in math mode the text font as configured at package loading time, for these characters:

abcdefghijklmnopqrstuvwxyz
ABCDEFGHIJKLMNOPQRSTUVWXYZ
0123456789
!?,.:;+-=()[]/#\$%&<>|{}\

The command \MTsetmathskips allows to set up extra spacings around each given letter.

Use multiple \Mathastext[name]'s to define in the preamble various math versions using each a given text font, to be later activated in the document body via the command \MTversion{name}.

With the subdued option, mathastext will be active only inside such math versions distinct from the normal and bold.

Main options: italic, defaultmathsizes, subdued, asterisk, LGRgreek.

Documentation generated from the source file with Time-stamp: <13-05-2016 13:28:47 CEST>.

Contents

Package history and installation instructions 1, p. 2	Extended scope of the math alphabets commands 2.8, p. 18
Changes 1.1, p. 2	Greek letters 2.9, p. 21 Shape of Greek letters.
Installation 1.2, p. 4	Unicode engines 2.10, p. 23
What mathastext does 2, p. 5	Compatibility issues 2.11, p. 25
Examples 2.1, p. 5 Overview 2.2, p. 7	Package options and commands
Basic use-always load mathastext last-sans in math-using mathastext with beamer-option LGRgreek-avoid OT1 encoding.	Summary of main options . 3.1, p. 27
Main options 2.3, p. 10 The italic option—The defaultmathsizes option—The subdued option.	Miscellaneous 3.2, p. 28 Commands 3.3, p. 30 Preamble-only commands – Commands usable only outside of math mode – Commands usable
Math versions 2.4, p. 11	everywhere – Body-only commands.
Extra spaces around letters 2.5, p. 14	Complete list of options 3.4, p. 41
Italic corrections 2.6, p. 14 Extra glue after \exists, \forall, and	Change log 4, p. 44
before the prime glyph 2.7, p. 17	Implementation 5, p. 48

1 Package history and installation instructions

1.1 Changes

See section 4 for the detailed change log.

- Changes for release 1.3p of 2016/05/13 bugfix: release 1.3n had forgotten to activate by default its new customization of the amsmath macro \newmcodes@ (it was done from using \MTversion in the document body but not by default at start of body.)
 - public name \MTfixmathfonts for a 1.30 macro.
- Changes for release 1.30 of 2016/05/03 mathastext fixes an issue related to a feature of LualateX and luaotfload that OpenType fonts are declared in one of two modes: node and base, and only the latter is functional in math mode. But by default text fonts are declared in mode node. Thus mathastext now intervenes to make it so that the font it declares in math mode will use mode basic. This fixes issues with for example old style figures being used while the text font used lining figures (or vice versa, depending on the font). But see the code comments for more.
- Changes for release 1.3n of 2016/04/22 at long last, mathastext takes care properly of annoying and perplexing amsmath's \newmcodes@. The very recent change in amsopn.sty finally made it compatible with Unicode engines,

but anyhow, mathastext must do its own patch to use the correct font. All of this taking into account the various options passed to the package. Lots of trouble for a tiny thing.

- Changes for release 1.31 of 2016/01/29 compatibility with fontspec's switch from EU1/EU2 to TU common to both Unicode engines.
- Changes for release 1.3j of 2016/01/15 \MTeverymathoff (renamed) and \MTeverymathdefault added.
 - subdued mode is a bit stronger: also the asterisk reverts to the default (if it was modified due to option asterisk), the added extra \mskip's (useful with upright fonts) for ', ∃, and ∀ are suppressed rather than re-configured to use Omu. Related new commands \MTexistsdoesskip, \MTforalldoesskip, \MTprimedoesskip, \MTnormalexists, \MTnormalforall, \MTnormalprime.
 - the toggle for using mathematically active letters is only emitted once during package loading; the \Mathastext command does not do it anymore; the use in the preamble of \MTmathstandardletters, or \MTnoicinmath and related commands is not overruled by later use of \Mathastext.
 - quite a few documentation improvements and rewrites, particularly in the description of commands (section 3.3.2) which are related to the modifications of mathcodes (mainly for math activation of characters or letters) as done by mathastext at \everymath or \everydisplay.
- Changes for release 1.3i of 2016/01/06 \url from url.sty as well as \url and \nolinkurl from hyperref.sty use math mode and (by default) the monospace text font. To avoid mathastext overwriting the special preparation done by {url,hyperref}.sty the commands \url/\nolinkurl are patched to do automatically \MTactivemathoff (now \MTeverymathoff) before entering math mode.
 - the extra skips specified by \MTsetmathskips (see 2.5) are not inserted around letters if inside the arguments of math alphabet commands, or within operator names.
 - the added explicit italic corrections (for non-oblique fonts; see 2.6) were disabled within math alphabet scopes, except \mathnormal; they are now disabled within all math alphabets, inclusive of \mathnormal.
- Changes for release 1.3g of 2015/10/15 following 2015/10/01 LaTeX release, removal of the "luatex" prefix from the names of LuaLaTeX math primitives. Compatibility maintained with older LaTeX formats.
- Changes for release 1.3d of 2014/05/23 new commands \MTstandardgreek and \MTcustomgreek in relation to the options LGRgreek(s), selfGreek(s), eulergreek, symbolgreek.
- Changes for release 1.3c of 2013/12/14 \Mathastext and \MTDeclareVer sion both accept a final optional argument, a math version name whose

settings regarding things not otherwise changed by mathastext (like most symbols and large symbols) will be inherited by the declared math version (first optional argument of \Mathastext or first mandatory argument of \MT DeclareVersion). Typical use will be with this final optional argument set to be [bold].

• \MTversion has a starred variant which will not modify the document text fonts, but only the math fonts (for those characters treated by mathastext).

Changes for release 1.3a of 2013/09/04 • (see subsection 2.5) new command \MTsetmathskips allows to specify, on a letter by letter basis, extra spaces (expressed in terms of 'mu' units, or as \thinmuskip for example) to be inserted automatically in math mode around the specified letter.

The 1.2x series: the main new features were the extended scope of the math alphabets and, respectively, added italic corrections in math mode. Both use mathematically active characters and some (thorny) technical problems related to globally active characters were finally solved to (almost) complete satisfaction (let's hope) only in the 1.2e version. These issues are commented upon in the compatibility section, in the test file mathastexttestalphabets.tex and in the commented source code. Also the asterisk option was introduced and compatibility with amsmath improved.

1.15 introduced the concept of the subdued math versions.

Initial release 1.0 was on 2011/01/25.

1.2 Installation

The fastest way is: unzip -d <destfolder> mathastext.tds.zip, where <destfolder> could be \sim /texmf or, on mac os x, \sim /Library/texmf.

Else, download mathastext.dtx, possibly also mathastext.ins, and follow these instructions:

- * with mathastext.ins: run tex on mathastext.ins to generate the package style file mathastext.sty as well as mathastext.tex and some test files.
- * without mathastext.ins: run tex on mathastext.dtx to generate the package style file mathastext.sty as well as mathastext.tex and some test files. (and also mathastext.ins)

Move the style file mathastext.sty to a location where TeX can find it. In a TDS compliant hierarchy this will be <TDS>:tex/latex/mathastext/mathastext.sty

documentation: run latex thrice on mathastext.tex then dvipdfmx. Or, run pdflatex thrice on mathastext.dtx. In the former case the documentation is

with source code included, in the latter without. The file mathastext.tex can be customized to change the font size or set other options therein.

(One cannot use lualatex/xelatex to compile the documentation.)

2 What mathastext does

2.1 Examples

mathastext's basic aim is to have the same font for text and mathematics. With hundreds of free text fonts packaged for LATEX and only a handful of math ones, chances are your favorite text font does not mix so well with the available math ones; mathastext may then help. Note that mathastext was initially developed for the traditional TEX fonts and engines, and that compatibility with Unicode engines and OpenType fonts is partial.

Here is an example with Latin Modern typewriter proportional:

Let (X,Y) be two functions of a variable a. If they obey the differential system $(VI_{\nu,n})$:

$$\begin{split} & a\frac{d}{da}X = \nu X - (1 - X^2)\frac{2na}{1 - a^2}\frac{aX + Y}{1 + aXY} \\ & a\frac{d}{da}Y = -(\nu + 1)Y + (1 - Y^2)\frac{2na}{1 - a^2}\frac{X + aY}{1 + aXY} \end{split}$$

then the quantity $q=a\frac{aX+Y}{X+aY}$ satisfies as function of $b=a^2$ the P_{VI} differential equation:

$$\begin{split} \frac{d^2q}{db^2} &= \frac{1}{2} \left\{ \frac{1}{q} + \frac{1}{q-1} + \frac{1}{q-b} \right\} \left(\frac{dq}{db} \right)^2 - \left\{ \frac{1}{b} + \frac{1}{b-1} + \frac{1}{q-b} \right\} \frac{dq}{db} \\ &+ \frac{q(q-1)(q-b)}{b^2(b-1)^2} \left\{ \alpha + \frac{\beta b}{q^2} + \frac{\gamma(b-1)}{(q-1)^2} + \frac{\delta b(b-1)}{(q-b)^2} \right\} \end{split}$$

with parameters $(\alpha,\beta,\gamma,\delta)=(\frac{(\nu+n)^2}{2},\frac{-(\nu+n+1)^2}{2},\frac{n^2}{2},\frac{1-n^2}{2}).$ Notice that the Latin (and Greek letters) are in upright shape. But perhaps we

Notice that the Latin (and Greek letters) are in upright shape. But perhaps we insist on obeying the standardized habits:

Let (X, Y) be two functions of a variable a. If they obey the differential system $(VI_{v,n})$:

$$a\frac{d}{da}X = vX - (1 - X^2)\frac{2na}{1 - a^2}\frac{aX + Y}{1 + aXY}$$

$$a\frac{d}{da}Y = -(\nu+1)Y + (1-Y^2)\frac{2na}{1-a^2}\frac{X+aY}{1+aXY}$$

then the quantity $q = a \frac{aX+Y}{X+aY}$ satisfies as function of $b = a^2$ the P_{VI} differential equation:

$$\frac{d^2q}{db^2} = \frac{1}{2} \left\{ \frac{1}{q} + \frac{1}{q-1} + \frac{1}{q-b} \right\} \left(\frac{dq}{db} \right)^2 - \left\{ \frac{1}{b} + \frac{1}{b-1} + \frac{1}{q-b} \right\} \frac{dq}{db} + \frac{q(q-1)(q-b)}{b^2(b-1)^2} \left\{ \alpha + \frac{\beta b}{q^2} + \frac{\gamma(b-1)}{(q-1)^2} + \frac{\delta b(b-1)}{(q-b)^2} \right\}$$

with parameters $(\alpha, \beta, \gamma, \delta) = (\frac{(\nu+n)^2}{2}, \frac{-(\nu+n+1)^2}{2}, \frac{n^2}{2}, \frac{1-n^2}{2})$. This was typeset using the Times font (available in any TEX distribution). Let us now be a bit more original and have our mathematics with italic letters from the sans serif font Helvetica, while the letters in text use New Century Schoolbook.

Let (X, Y) be two functions of a variable a. If they obey the differential system ($VI_{\nu,n}$):

$$a\frac{d}{da}X = \nu X - (1 - X^{2})\frac{2na}{1 - a^{2}}\frac{aX + Y}{1 + aXY}$$

$$a\frac{d}{da}Y = -(\nu + 1)Y + (1 - Y^{2})\frac{2na}{1 - a^{2}}\frac{X + aY}{1 + aXY}$$

then the quantity $q = a \frac{aX+Y}{X+aY}$ satisfies as function of $b = a^2$ the

$$\frac{d^2q}{db^2} = \frac{1}{2} \left\{ \frac{1}{q} + \frac{1}{q-1} + \frac{1}{q-b} \right\} \left(\frac{dq}{db} \right)^2 - \left\{ \frac{1}{b} + \frac{1}{b-1} + \frac{1}{q-b} \right\} \frac{dq}{db} + \frac{q(q-1)(q-b)}{b^2(b-1)^2} \left\{ \alpha + \frac{\beta b}{q^2} + \frac{\gamma(b-1)}{(q-1)^2} + \frac{\delta b(b-1)}{(q-b)^2} \right\}$$

with parameters $(\alpha, \beta, \gamma, \delta) = (\frac{(\nu+n)^2}{2}, \frac{-(\nu+n+1)^2}{2}, \frac{n^2}{2}, \frac{1-n^2}{2})$. And after all that, we may wish to return to the default math type setting (let's shorten the extract here in case the reader makes an indigestion ...):

> Let (X,Y) be two functions of a variable a. If they obey the differential system $(VI_{\nu,n})$:

$$a\frac{d}{da}X = \nu X - (1 - X^2) \frac{2na}{1 - a^2} \frac{aX + Y}{1 + aXY}$$
$$a\frac{d}{da}Y = -(\nu + 1)Y + (1 - Y^2) \frac{2na}{1 - a^2} \frac{X + aY}{1 + aXY}$$

then the quantity $q=a\frac{aX+Y}{X+aY}$ satisfies as function of $b=a^2$ the P_{VI} differential equation with parameters $(\alpha,\beta,\gamma,\delta)=(\frac{(\nu+n)^2}{2},\frac{-(\nu+n+1)^2}{2},\frac{n^2}{2},\frac{1-n^2}{2})$.

Notice that the Greek letters also changed according to the *math version*: mathastext has indeed some (limited) capabilities to this effect, with its LGRgreek option. This document uses the LGR encoded fonts cmtt, cmss, and txr, which are part of standard T_EX distributions.¹

2.2 Overview

2.2.1 Basic use

The initial ideology of **mathastext** was to produce mathematical texts with a very uniform look, not separating math from text as strongly as is usually done.

As soon as one tries out other fonts for text than the Computer Modern ones one realizes how extremely "thin" are the default TEX fonts for mathematics: they definitely do not fit well visually with the majority of text fonts. With mathastext one can get one's (simple... or not) mathematics typeset in a manner more compatible with the text, without having to look for an especially designed font.

Here is a minimal example of what may go into the preamble:

\usepackage[T1]{fontenc}
\usepackage{times}
\usepackage[italic]{mathastext}

The package records which font is set up for text, at the time it is loaded,² and then arranges things in order for this text font to be used in math mode as well. So, with the preamble as above all letters, digits, and punctuation signs inside math mode will then be typeset in Times.³ The exact list of characters concerned by mathastext is a subset of the basic ASCII set:

abcdefghijklmnopqrstuvwxyz
ABCDEFGHIJKLMNOPQRSTUVWXYZ
0123456789
!?*.:;+-=()[]/#\$% & <>|{} and \

As one can see, this is a very limited list! some possibilities are offered by mathastext for Greek letters and will be described later.

The text characters ' and - are not used, and the asterisk is done optionally:

¹The first two are available (with no need to load explicitely any package in the document) via the combination cbfonts (cbgreek-complete) & babel, and the LGR encoded txr font (again no package loading is necessary) is part of the files of the txfontsb package.

²alternatively it is possible to configure the text font after loading mathastext, and then the command \Mathastext will accomplish the necessary changes to the font for letters, digits and a few extra ascii symbols in math mode

³let's do as if we did not know the excellent txfonts package which employs Times for text and has a very complete math support, including many additional mathematical glyphs in comparison to the CM fonts.

- the derivative sign ' is left to its default as the text font glyph ' is not, as a rule, a satisfying alternative.⁴
- for the minus sign mathastext uses the endash character –, if available, and not the hyphen character -,
- the option asterisk is necessary for mathastext to replace the binary math operator * (and the equivalent control sequence \ast) with a version which uses the text asterisk * suitably lowered⁵ (and with the correct spaces around it as binary operator). The reason for making it optional is that after this \$R^** or \$R^\ast\$ do not work and have to be written \$R^{*}\$ or \$R^{*}\$.

Nothing is changed to the "large" math symbols, except for Π and Σ in inline math which, like here: $\Pi \Sigma$, will be taken from the Symbol Font if option symbol misc was used.

The left and right delimiters are taken from the text font only for the base size: any \big, \big1, \bigr, etc...reverts to the original math symbols.

2.2.2 always load mathastext last

The "large" math symbols are not modified in any way by mathastext. Only loading some math font packages such as fourier, kpfonts, mathabx, mathdesign, txfonts, newtxmath, etc... will change them. Think of loading these packages before mathastext, else they might undo what mathastext did.

More generally any package (such as amsmath) dealing with math mode should be loaded before mathastext.

2.2.3 sans in math

The following set-up often gives esthetically pleasing results: it is to use the sansserif member of the font family for math, and the serif for text.

\renewcommand\familydefault\sfdefault
\usepackage{mathastext}
\renewcommand\familydefault\rmdefault
\begin{document}

2.2.4 using mathastext with beamer

Starting with release 3.34 of beamer, mathastext is recognized as a "math font package".

 $^{^4}$ v1.2 adds a customizable tiny space before $^\prime$ to separate it from the previous letter, this is really needed when using upright letters in math mode with the CM derivative glyph.Compare f^\prime with f^\prime .

 $^{^{5}}$ the amount of lowering can be customized.

```
Only with earlier beamer versions is it necessary to issue \usefonttheme{professionalfonts}
```

in the preamble. Example:

```
\documentclass{beamer}
%\usefonttheme{professionalfonts}% obsolete for mathastext since beamer 3.34
\usepackage{newcent}
\usepackage[scaled=.9]{helvet}
\renewcommand{\familydefault}{\rmdefault}
\usepackage[defaultmathsizes,symbolgreek]{mathastext}
\renewcommand{\familydefault}{\sfdefault}
\begin{document}
\begin{frame}
 This is some text and next comes some math: $E=mc^2$
 E=mc^2=a^n+b^n-c^n=\alpha\beta\gamma
  \begin{align}
   E&=mc^2\\
   E&=h\nu
  \end{align}
 And again some text.
\end{frame}
\end{document}
```

2.2.5 option LGRgreek

There is the issue of Greek letters. Sometimes the text font has Greek glyphs, in LGR encoding (this will be mentioned in the documentation of the font package). Then option LGRgreek tells mathastext to pick up these Greek letters. And it is possible to specify whether the Greek letters should be upright, or "italic".⁶

It is naturally possible to leave the responsability to set up Greek letters to some other packages loaded previously to mathastext. And even if mathastext has been loaded with one of its Greek related options the command \MTstandardgreek will locally cancel its customization of Greek letters. See also \MTcustomgreek.

2.2.6 avoid OT1 encoding

We specified in our minimal working example a T1 encoding (LY1 would have been ok, too) because the default OT1 does not have the $<>|\{\}|$ and $|\{\}|$ glyphs. If mathastext detects OT1 as the default encoding it will leave these characters to their defaults from the math fonts.

⁶a more detailed discussion comes next. Note that the default CM and its replacement Latin Modern for european languages are (transparently to the user) extended with LGR encoded fonts from the cbfonts (cbgreek-complete) package.

⁷the <u>subdued</u> option, described next, acts a bit otherwise, it forces, contrarily to its usual low-key character, the replacement of OT1 by T1 for the fonts ultimately used with letters and digits in math

If $\mathtt{mathastext}$ detects the obsolete OT1 encoding it does not do anything with <,>,|, $\{,$ and $\}$ which (except for monospace fonts) are not available in that encoding. To fully benefit from $\mathtt{mathastext}$ it is recommended to use some other encoding having these glyphs such as T1 or LY1.

2.3 Main options

2.3.1 The italic option

In the initial version 1.0, the Latin letters in mathematical mode assumed the exact same shape as in text mode, and this meant, generally speaking, that they would turn up upright. Doing this gives a very uniform look to the document, so that one has to make an effort and read it with attention, and this was one of the design goals of mathastext.

Nevertheless, soon after I posted the initial version of the package to CTAN, I was overwhelmed by numerous⁸ questions⁹ on how to have the letters be in italic shape.

The default is still, as in version 1.0, for everything to be in upright shape, but it suffices to pass to the package the option italic to have the Latin letters in math mode in italic shape.¹⁰ There is also an option frenchmath to make the uppercase letters nevertheless upright, because this is the way of traditional French mathematical typography.¹¹

2.3.2 The defaultmathsizes option

The default sizes give for subscripts of subscripts barely legible glyphs (author's opinion!). So mathastext makes more reasonable choices. It also redefines \Huge and defines a \HUGE size, copied from the moresize package. To cancel all of this use option defaultmathsizes.

2.3.3 The subdued option

This option was introduced in v1.15. It provides a manner to switch on the mathastext-ification only for limited portions of the document, with the help of the mechanism of math versions. Without the subdued option, the mathastextification applies by default to the whole of the document (and one may also define additional math versions in the preamble); with the subdued option the mathastextification is done only in math versions distinct from the standard and bold ones.

mode.

⁸this means "more then one."

⁹I thank in particular Tariq Perwez and Kevin Klement for their kind remarks (chronological order)

 $^{^{10}\}mathrm{more}$ precisely stated, the value of \itdefault is used.

¹¹more precisely stated, the value of \shapedefault is used.

The previous description is in fact a bit optimistic: mathastext was not written initially in order to allow its action to be completely canceled, and achieving this would require a complete rewrite of large portions of the code.

To get the displayed math (almost) as if mathastext had not been loaded, one must also use the option defaultmathsizes. But this does not quite suffice, as, for example, the colon, the dot, and the minus sign belong in the default LATEX math mode set-up to three distinct fonts whereas mathastext will pick (even subdued) the three of them in the same font, and although it will make a reasonable choice of this font, this is not a return to the previously prevailing situation. And then arbitrary packages could have done arbitrary things... so to be on the safe side one needs the basic option which limits the mathastextification to letters and digits (and should also be accompanied by defaultimath which prevents redefinition of the \imath macro, and nohbar which prevents redefinition of the \hbar macro...). And even then, in some circumstances, this will still not suffice; for example the euler package puts the digits in the same font as the Latin letters in math mode, but the subdued mathastext will pick them up in the same font as used in operator names, and in the case of the euler package, this is the main document font. So, even subdued, mathastext still kicks. But, as I think is illustrated by the examples given at the start of this document, the subdued option has its utility, and works reasonably well.

Starting with package version 1.3d, the subdued mode does extinguish in the normal and bold math versions the action of options selfGreek, eulergreek, and symbolgreek (previously only LGRgreek was subdue-able).

2.4 Math versions

IATEX has the concept of math versions, but most font packages do not define any such version beyond the default normal and bold (that they possibly customize to use such or such math font). The package unicode-math for unicode engines fruitfully uses this concept. mathastext uses math versions in order to allow the math mode fonts (for letters, digits, punctuation and a few other ascii symbols) used in the different parts of the document to be kept in sync with the text fonts. However the other math symbols (sums, products, integrals, logical signs, etc...) will be the same throughout the document as it is not in mathastext power to modify them. There are some possibilities to use different sets of fonts for the Greek letters, though.

The present document illustrated the use of various fonts, here is its preamble (slightly stripped-down):

```
\usepackage{lmodern}
\usepackage[T1]{fontenc}
\usepackage[subdued,italic,defaultmathsizes]{mathastext}
\MTDeclareVersion[n]{lmvtt}{T1}{lmvtt}{m}{n}
\usepackage{newcent}
\Mathastext[newcent]
\usepackage{times}
\Mathastext[times]
\usepackage[scaled]{helvet}
\renewcommand\familydefault\sfdefault
\Mathastext[helvet]
\begin{document}\MTversion{normal}
```

Let us examine this code: it uses once the command \MTDeclareVersion and three times the command \Mathastext, thus defining four math versions¹²: lmvtt, newcent, times, and helvet. The names can be taken arbitrarily (they only need to be suitable arguments to the LATEX \DeclareMathVersion command which is invoked internally). Two additional math versions preexist: the normal and bold, which, because there was the subdued option, were left untouched by mathastext.

Once these math versions are defined, \MTversion{name_of_version}, or equivalently \Mathastextversion{name_of_version}, enacts the font switches in the body of the document. As is usual with LATEX one can limit the scope to the inside of a group, or also switch back to the main set-up through issuing \Mathastextversion{normal}.

When \Mathastext is used in the preamble, it records the current font defaults and (except for the normal and bold versions under the subdued regime) sets up the math font to be used in that version to be the text font as found in \familydefault. But it is still possible for a mathastext-declared math version to have distinct fonts for text and math:

- 1. in the body of the TeX source, an optional argument (the name of a mathastext-declared math version) to \MTversion is allowed, and for example we used in the source of this document \MTversion[newcent]{helvet} meaning "New Century Schoolbook for the text and Helvetica for the math."
- 2. there are preamble-only commands \MTencoding, \MTfamily, \MTseries, \MTshape, \MTlettershape which tell mathastext what to do (for math only) in each math version declared afterwards, independently of the text fonts.

The native IATEX command \mathversion{\langle version_name \rangle} would change only the fonts used in math mode. It is recommended to use instead the package command \mathversion (or one of its synonyms \mathastextversion, \mathastextversion, \mathastextversion, \mathastextversion), with a mandatory argument {\langle version_name \rangle}, which does additional actions:

 $^{^{12}\}mathtt{math}$ versions are discussed in the document <code>fntguide.pdf</code> from your <code>TEX</code> distribution.

- it sets the font for math mode (letters, math operator names, digits, punctuations, some other symbols) according to the version name given as mandatory argument,
- it resets the text font of the document and the \((family,rm,sf,...)\)defaults to their values as registered at the time of definition of the version. *Use the starred variant in case this is not desired.* It is possible to also specify within brackets an extra optional version name, and the text font will be set according to it,
- (see sections 2.5 and 2.6) it re-issues the command \MTmathactiveletters to let a to z, A to Z, be mathematically active in order to automatically insert the skips as defined by the user with \MTsetmathskips, and the italic corrections (if the font is not italic or slanted),
- (see section 2.7) it resets the extra spaces after the symbols ∃, ∀ and before
 the derivative ' to the values as decided by the user in the preamble on a per
 version basis,
- (see section 2.8) it re-issues the commands \MTmathoperatorsobeymathxx and \MTeasynonlettersobeymathxx to let the math operator names and ('easy') non letter characters obey the math alphabets,
- in case of option asterisk, it re-issues \MTactiveasterisk,
- it does the additional set-up for Greek letters in case of the package received one of the Greek related options.

The scope is limited to the current LATEX environment or group. When switching to the *normal* or *bold* math versions under option **subdued** most of the above is canceled.

It is sometimes not compatible with mathastext to load a font package after it, as the font package may contain instructions which will modify the math setup. This may be a bit hidden to the user: for example the epigrafica package loads pxfonts. Hence it will interfere with mathastext if it is loaded after it. But one can use instead \renewcommand{\rmdefault}{epigrafica}, followed with \Mathastext, or also \MTfamily{epigrafica}\Mathastext which will only change the font in math.

To use epigrafica for Greek in math mode one can use the package option LGRgreek and the command \MTgreekfont{epigrafica}\Mathastext. Or \usepackage{epigrafica} followed with \usepackage[LGRgreek]{mathastext}.

¹³may typically give a 'too many math alphabets' error message.

¹⁴sometimes one needs to look in the .sty file of the font package to figure out the font name (it is rarely as epigrafica, the same as the package name), and, if one does not know the arcanes of finding .fd files in one's TEX distribution, one should look at the log file of a test document to see if for example T1 is available for that font; for epigrafica it is not, only OT1 and LGR are possible.

2.5 Extra spaces around letters

This is a new feature added with release 1.3: the command \MTsetmathskips allows the user to set up some spaces (more precisely, 'mu glue'; but stretch and shrink are discarded) to be automatically inserted around the letters in math mode. Some (very) unrealistic uses:

% this may be anywhere in the document (also within a math group):

\MTsetmathskips{x}{20.33mu}{15.66mu}% 20.33mu before all x's and 15.66mu after.

\MTsetmathskips{y}{\thickmuskip}{{\thickmuskip}}%

\MTsetmathskips{z}{10mu}{5mu}% stretch and shrink are anyhow without effect.

 $\label{thm:linear_loss} $$ \T\end{1.0mu}_{5mu}^{5mu}^{\mbox{stretch and shrink are anyhow without effect.} $$ MT\estmathskips{A}_{\mbox{muexpr }\mbox{linear}_{2}^{\mbox{muexpr }\mbox{linear}_{2}^{\mbox{linear}_{2}}^{\mbox{li$

Here is what $\text{wxtytz}=BAC^{BAC}$ then gives using the Times font: $w \times t y t z^{w \times t y t z} = B A C^{B A C}$. Any TeX group or LATeX environment limits as usual the scope of this command. Furthermore the command \MTunsetmath skips cancels previous use of \MTsetmathskips for a given letter.

The implementation relies on the 'mathematical activation' of letters, which is done by default by the package since release 1.2b. Should this cause compatibility problems, the command \MTmathstandardletters cancels it entirely. To reactivate it, there is \MTmathactiveletters. Note that \MTmathactiveletters is done automatically by mathastext when loaded, and also each time the package enhanced math-version-switch command \MTversion is used, except for the normal and bold math versions under the subdued option.

The extra skips are set at natural width; they do not contribute to the overall stretchability or shrinkability of the math formula and do not create break points.

Changed with 1.3i: they are *not* applied within the scope of math alphabet commands.

2.6 Italic corrections

Note: this is somewhat technical discussion which may well be skipped in its entirety on first reading.

With the italic option the letters in math will be generally in italic shape (and, normally, upright in operator names).

For the built-in placement routines of T_EX in math mode to work as well as they usually do, the characters from the math italic font obviously should have their bounding boxes wide enough for the glyphs not to collide with other symbols. A letter from a text italic font such as f extends way out of its declared bounding box; let us compare the bounding boxes¹⁵ for the letter f in the math italic font to the one from the text italic font: f vs. f.

¹⁵let's be honest, we are lying here about what exactly the first of these is bounding; this is explained later!

This could make us think that attempting to use in math a text italic font will lead to disaster. Well, surprisingly the situation is not that bad. Sure f(x) is wider with the standard math italic f(x) (21.31474pt) than it is with the text italic font used in math: f(x) (19.74986pt) but we should be surprised that our text italic f(x) did not end up even closer to the opening parenthesis. Why is it so?

The explanation is that T_EX uses in such a situation the *italic correction* for the letter f. The italic correction also exists and is used for the math italic font, it was inserted in f without us having to ask anything. Its value is 1.17865pt for the math italic f and 1.8919pt for the text italic f. With the italic corrections included our bounding boxes are indeed more alike: f vs f.

Without the italic corrections 18 it is \mathcal{J} vs \mathcal{J} . I said that f included the italic correction automatically, but if we tell f to use the text italic in math, and typeset the alphabet, we obtain something exactly identical to typing the letters in text, hence without any italic correction:

```
abcdefghijklmnopqrstuvwxyz text italic in text abcdefghijklmnopqrstuvwxyz text italic in math abcdefghijklmnopqrstuvwxyz math italic in math abcdefghijklmnopqrstuvwxyz math italic in text
```

Where are our italic corrections gone? the last line was done with \use font{OML}{1mm}{it} and confirms that italic corrections have been used for the math italic in math.

Turning to the TEXbook (and its Appendix G) we learn that in such circumstances, for the italic corrections to be put in from the font, one of its parameters, the interword space (aka \fontdimen2), should be zero. It is indeed zero for the math italic font, not for the text italic.

It is possible to make T_EX believe it is. Doing so, we obtain in math mode with the text italic:

```
abcdefghijklmnopqrstuvwxyz text italic in math abcdefghijklmnopqrstuvwxyz math italic in math
```

We saw that the italic correction was taken into acount automatically (independently of the value of the interword space font parameter) in expressions such as f(x). Another clever thing done by f(x) is to use it for the placement of superscripts; the next examples systematically use the text italic in math. We see that f^j is very different from f^j ... where the latter was coded with \hat{f}^j is f^j . The inputs \hat{f}^j is f^j . Where the latter was coded with \hat{f}^j and \hat{f}^j give almost identical results: f^j vs. f^j . Close examination reveals that the horizontal spacing is exactly identical, however the exponent in the second case is a bit lower. Anyway, the point is that in the second case the italic correction for f was indeed used.

Subscripts are another matter: they do not take into account the italic cor-

¹⁶we used simply $\mathbf{mathit}\{f(x)\}$ \$.

¹⁷these values are for the Latin Modern fonts of course.

¹⁸here we give correctly the bounding box for the math italic f... without its italic correction!

rection. For example $\mathbf{f_i}$ gives the same horizontal positions as $\mathbf{f_i}$ and reveals (use the zoom of your viewer!) that only the vertical placement was affected, not the horizontal placement.

We learn in Appendix G of the T_EX book that the italic correction is used for the horizontal shift of the superscript with respect to the position of the subscript: f_i^j , or, going back now to the standard math italics f_i^j . In the next paragraphs we use f_i^i for more accurate comparison of the positioning of the sub- and superscript.

If we try something like this: f'_i is we obtain f_i^i . Our overlapping game with Γ_i if f'_i if gives f_i^i . We discover that the effect of the explicit italic correction has mainly been to translate the subscript horizontally to be positioned exactly below the superscript! We most probably do *not* want this to happen for our indices and exponents in math mode. So perhaps we can rejoice in how astute T_{EX} has been in judiciously using the italic correction data, and there seems to be no need into fiddling with this algorithm which seems to work well even when applied to a text italic font. Actually we may even be of the opinion that the text italic version f_i^i is a bit better-looking than the true math italic f_i^i ...

But wait... mathastext was initially developed to easily use in math mode the document text font not in its italic variant, but as is, so, usually, upright. And upright TEX fonts may also have italic correction data! And what I just said about the shift of the superscript with respect to the subscript apply equally well to such a font, if TEX has been told to use it. Let's try Latin Modern Upright for letters in math: f_i^i now gives f_i^i . We see the italic correction in action for the positioning of the superscript! Compare with \mathbf{f}_i^i now f_i^i overlapping with \mathbf{f}_i^i mathrm f_i^i has an italic correction which was used to shift the superscript to the right (and it is now in a slightly lower position). Let's now do \mathbf{f}_i^i and the subscript is shifted to the right, and is now on the same vertical axis as the superscript. There are also some slight vertical displacements, \mathbf{f}_i^i hathrm f_i^i hathrm f_i^i hathrm f_i^i .

People will tell me crazy, but if we decide for using upright fonts in math, wouldn't it be satisfying to have the subscript and superscript positioned on the same vertical axis? the letter has no slant, why should the indices display one?

We end up in this strange situation that it is attractive to systematically incorporate the italic corrections after the upright Latin letters in math! But we don't want to do this inside the arguments to math alphabets as this would make impossible the formation of ligatures (the standard \$\mathrm{ff}\$, \$\mathit{ff}\$, \$\mathbf{ff}, and ff and we would like to preserve this behavior).

¹⁹there are also some tiny vertical displacements of the sub- and superscripts.

 $^{^{20}}$ we just use $\mathbf{mathrm\{f_i^i\}}$

Starting with version v1.2b, mathastext adds the italic correction automatically after each letter of the Latin alphabet in math mode, except when these letters are italic or slanted.²¹

These italic corrections are canceled inside the arguments to the math alphabet commands, to allow the formation of ligatures as is expected in the standard default $T_{\rm E}X$ font set-up in math.²²

The feature-implementing commands \MTicinmath, \MTnoicinmath, \MTical soinmathxx are described in section 3.3.3.

Note: from brief testing on 2012/12/28, XaTeX seems not to create fake italic corrections for OpenType fonts. Hence the TeX placement algorithms for math mode described in this section do not work well when an OpenType (text) font is used for the letters in math mode, and the document is compiled with the XaTeX engine. On the other hand LualATeX seems to implement the italic corrections when using OpenType fonts, but only with italic fonts (as far as I could tell). Try the following (which will use the OpenType Latin Modern font) on a recent TeX installation and compare the output of both engines:

```
\documentclass{article}
\usepackage{fontspec}
\begin{document}
\Huge
$\mathit{f_i^i}$\par $\mathrm{f_i^i}$
\end{document}
```

Comment out the fontspec line and use pdfIATEX. All three outputs are different on my TeX installation. XaTeXdoes not have the italic corrections. LuaIATEX does, but only for the italic font. pdfIATEX has them for both the italic and the upright font.

2.7 Extra glue after \exists, \forall, and before the prime glyph

MTforallskip, MTexistsskip, and MTprimeskip are three commands with each a mandatory argument like for example 3mu plus 1mu minus 1mu or just 2.5mu. They are especially useful when using an upright font in math mode. The mu is a unit length used in math mode ('math unit', 1/18th of the 'quad' value of the symbol font in the current style). Its value is relative to the current math style. Its use is mandatory in the commands described here.

²¹the situation is rather ironical! by the way, the warnings in section 2.8 with \$x^?\$ or similar are less of an issue here, because the letter is only *followed* by \/ and anyhow the whole is put by mathastext within group braces, so no surprises with \$x^y\$ or \$\mathbin x\$. Nevertheless it is still true that (in math mode only) the letters a-z, A-Z, expand to composite objects, something which could surprise other packages. The command \MTmathstandardletters cancels this mechanism.

nged! ²²Prior to 1.3i, italic corrections were added to the \mathnormal arguments.

- compare ∀B with ∀B, typeset after \MTforallskip{2mu},
- compare $\exists N \text{ with } \exists N, \text{ typeset after } \texttt{MTexistsskip{2mu}},$
- and finally compare f' with f', typeset after \MTprimeskip{2mu}.

These three commands may be used throughout the document, or also in the preamble, in which case the declared math versions will record the then current values of the skips. mathastext applies the following (small) default skips: 0.6667mu for the skip after \forall , 1mu for the skip after \exists , and 0.5mu for the skip before the prime. The examples above become $\forall B, \exists N$ and $f'.^{23}$

With the **italic** option the defaults are set to zero. Indeed $\forall B, \exists N$ and f' look fine without additional skips. If the document decides then to declare in the preamble a math version with an upright font it is thus recommended to use the commands in the preamble before the $\texttt{Mathastext}[\langle version_name \rangle]$ (or MTDeclareVersion) command defining the version. They will be remembered when this math version is entered in the document. The commands may also be used directly in the document body.

Under the **subdued** option, the *normal* math version (at the start of the document body, or after \MTversion{normal}) and the *bold* math version (either at the start of the document body after \MTversion{bold}) do not have any extra skip inserted (even one of zero width) after \forall , \exists , or before the '.24

2.8 Extended scope of the math alphabets commands

Ever since the initial version of the package, some characters usually unaffected by the math alphabet commands \mathbf, \mathtt, \mathsf... are declared to be of 'variable family type', in order for them to obey these commands: for example the hash sign # gives # if input as \$\mathbf{\#}\$ (mathastext, especially in its beginnings, wanted as many characters as possible to be picked up from the text font and to behave similarly to letters and digits).

So it was especially frustrating that mathematical characters such as +, or <, or] could not be declared of 'variable family' (in addition to being picked up in the text font) as this would, for reasons of the inner workings of TEX, not be compatible with the automatically inserted spaces around them.

A revolutionary ;-) novelty is introduced with version 1.2 of the package:

1. the pre-declared or user-declared (using the amsmath \DeclareMathOperator or equivalent) operator names obey the math alphabet commands, 25

Changed!

²³the derivative glyph from the txfonts math symbols adapts itself better to an upright letter, no skip seems to be needed then.

²⁴Prior to 1.3j skips of zero widths were inserted.

²⁵contrarily to the next feature, this one is not likely to create incompatibilities with other packages, so it is activated by default.

2. and, optionally, all non alphabetical characters²⁶ treated by mathastext, i.e., if not disabled by options, $!?,:;+-=()[]<>\{\}$, the asterisk *, and $./|/\# \% \&^{27}$ will also obey the math alphabet commands (when not used as delimiters). The important thing is that the spaces added by TEX before and after are not modified.

Let us compare, for example, the new behavior of \mathtt and \mathbf

$$(\sin(n!) < \cos(m-p)?) \qquad [\sin(x+y) = \cos(z-t)]$$

with the traditional default behavior:

$$(\sin(n!) < \cos(m-p)?)$$
 $[\sin(x+y) = \cos(z-t)]$

The first feature is activated by default, except of course for the normal and bold math versions when the package was given the *subdued* option. The second feature is *off* by default for the characters listed first. It is *on* for the 'easy' cases # % & . / | \ (activating the feature for them puts no constraint on the user input and should not be too upsetting to other packages), and also for * but only if this was required explicitly by the option **asterisk**, as the user then is supposed to know that \$R^*\$ is no valid input anymore and should be replaced by \$R^{*}\$. The remaining 'difficult' cases create similar constraints, which will be commented more upon next. The relevant commands are

\MTmathoperatorsdonotobeymathxx \MTnonlettersdonotobeymathxx \MTeasynonlettersdonotobeymathxx

for deactivation and

\MTmathoperatorsobeymathxx \MTnonlettersobeymathxx \MTeasynonlettersobeymathxx

for activation.²⁸ ²⁹

²⁶of course some of them are input preceded by a backslash, and the backslash itself is input as \backslash.

²⁷#\$% & obey the math alphabets since the initial version of mathastext; the dot., the slash /, the vertical bar | and the backslash \ do not have specific spacings inserted by TEX around them, and the procedure is then not a devilish one, this is why it is made the default for these characters which are listed apart. The math symbols \mid (which is | with type \mathrel) and \setminus (\ with type \mathbin) are counted among the 'difficult' cases, not the 'easy non-letters'.

²⁸these commands are to be used outside of math mode. Their scope is limited to the current LATEX environment or group. They use the \everymath and \everydisplay mechanism so if the document needs to modify these token lists it has to do so in a responsible manner, extending not annihilating their previous contents.

²⁹when in subdued mode, the math alphabets are the default ones, not the ones modified by mathastext to use the document text fonts. As a result, matters of font encodings may then give unexpected results, for example for —. On the present document page we switched to a math version to escape from the subdued mode and avoid the problem with \mathbf{-} giving in the normal (subdued) math version ~, when 'non-letters' are declared to obey math alphabets.

Important: the package does \MTnonlettersdonotobeymathxx by default. The reason is that activating the mechanism adds some constraints to the way things must be input, adding \usepackage{mathastext}\MTnonlettersobeymathxx to a pre-existing document might well create errors: all these characters treated by mathastext, such as ?, [, < now represent (in math mode only!) two 'tokens' and this will utterly confuse T_EX if some precautions are not taken: $x^?$, R^+ or $mathopen<A\mathbb T_EX$ in some precautions are not taken: $x^?$, R^+ and $mathopen<A\mathbb T_EX$ (the rule is to do as if ?, +, < or > were each really two characters).

Even if this rule is respected in the document source, it is still a possibility that incompatibilities with other packages will arise because mathastext does a mathematical activation of the characters which could be unexpected and unchecked for by other packages. This is precisely the case with the amsmath package, and the problem goes away by just making sure that amsmath is loaded before mathastext (generally speaking, mathastext should be loaded last after all packages dealing with math things).

The braces $\{$ and $\}$ remain unresponsive to the alphabet changing commands even after \M Tnonlettersobeymathxx. One must issue also \M Texplicitbrace sobeymathxx, but it has the disadvantage that $\{$ and $\}$ become then unusable as variable-size delimiters: $\$ or $\$ create errors and one must make use of $\$ big $\$ brace and $\$ big $\$ but one can now enjoy $\{a, a > b\}$, $\{a, a > b\}$, $\{a, a > b\}$, or even $\{a, a > b\}$.

Even with \MTnonlettersobeymathxx, the parenthese-like symbols (,), [,], < and > and the slashes /, \, if used as left/right delimiters (i.e. with \left/\right) do not react to math alphabet commands. This is mainly explained by the fact that the text font will not contain suitable glyphs, hence no attempt was made to make the delimiters pick up their glyphs there.

But mathastext does try to pick up most of the 'small variants' of the delimiters from the text font: $\alpha < x \le 0$ (but $\beta \le 0$). Notice that this differs from standard LATEX for which $\beta \le 0$ (but $\beta \le 0$). As it is perhaps a bit strange to have $\beta \le 0$ (but $\beta \le 0$) there is option nosmalldelims: with this option the small-sized variants of the delimiters are not modified by mathastext (option nosmalldelims has the side effect that, for the non-delimiter uses of $\beta \in 0$ to be mathastext-ified it is necessary to issue $\beta \in 0$.

At any rate, as said above, whether 'small' or not, delimiters are unresponsive to math alphabet commands, due to technical aspects of T_EX , and the way mathastext handles these things. Examples: \mathbf{ $\langle a,b \rangle \}$ gives $\langle a,b \rangle$

³⁰this last example uses the \mathnormalbold additional alphabet defined by mathastext.

³¹Let me recall that braces will anyhow not be handled at all by mathastext if the document font encoding is OT1, except under option alldelims.

(no use of $\left\langle a,b\right\rangle$ hence brackets do obey the math alphabets — as we issued \MT nonlettersobeymathxx a bit earlier), \mt do not obey the math alphabets), gives $\langle a,b\rangle$ (brackets used with $\left\langle a,b\right\rangle$ gives $\langle a,b\rangle$ (no \l gives $\langle a,b\rangle$ (no \l gives, brackets do obey the math alphabets).

For comparison, the LATEX standard behavior for \mathbf{\mathopen{<}a,b\mathclose{>}}

is $\langle \mathbf{a}, \mathbf{b} \rangle$ (neither brackets nor the comma do respond).

2.9 Greek letters

The Computer Modern fonts are very light and thin in comparison to many text fonts, and as a result rarely mix well with them (particularly if the Latin letters in math mode are upright). The following options are provided by mathastext:

no option: nothing is done by the package, Greek letters are the default Computer Modern ones or have been set-up by other packages; for example by the fourier package with option 'upright', which gives upright Greek letters.

LGRgreek: this is for fonts which additionally to Latin letters also provide Greek letters in LGR encoding. Here is a list from a 2012 standard TeX installation: the Computer Modern, Latin Modern, and the CM-LGC fonts; the Greek Font Society fonts (such as GFS Didot), the epigrafica and kerkis packages, the txfontsb package which extends the txfonts package with LGR-encoded Greek letters; the Droid fonts, the DejaVu fonts, the Comfortaa font, and the Open Sans font. The LGR encoded CM/LM fonts (in serif, sans-serif and typewriter family) give the nice Greek letters in upright shape from the cbfonts package. To get these letters in your mathastext math mode, you can do the following:

% instructions to load the document fonts:

\usepackage{nice_font}

% and then the following:

\renewcommand{\familydefault}{cmr} % or cmss or cmtt for sans resp. mono \usepackage[LGRgreek]{mathastext}

\renewcommand{\familydefault}{\rmdefault}

\Mathastext % this re-initializes mathastext with the nice_font,

% without changing the LGR font cmr/cmss/cmtt used for Greek letters % in math mode.

\begin{document}

If you use the italic option note that the italic Greek letters from the cbfonts are not the same glyphs as the default Greek letters from the OML encoded font cmmi.

eulergreek: the Greek letters will be taken from the Euler font (the document does not have to load the eulervm package, mathastext directly uses some file included in this package, as it provides a mechanism to scale by an arbitrary factor the Euler font.) The letters are upright. symbolgreek: the Greek letters will be taken from the (Adobe Postscript) Symbol font. A command is provided so that the user can scale the Symbol font to let it better fit with the text font. The letters are upright.

selfGreek: this option concerns only the eleven Greek capitals from the OT1-encoding. It does nothing for the lowercase Greek letters. The encoding used in the document does not have to be OT1.

There is also LGRgreeks which tells mathastext to pick up in each math version the letters from the LGR encoded font used in that version, and selfGreeks to tell mathastext to do as for selfGreek but separately in all math versions.

Under the **subdued** option the Greek letters in the normal and bold math versions are kept to their defaults as found at the time of loading the package.

The commands \MTstandardgreek allow at any point in the document to turn inactive any Greek related option passed to mathastext. And conversely \MTcustomgreek reactivates it.

2.9.1 Shape of Greek letters

Classic T_EX uses in math mode italic lowercase and upright uppercase Greek letters. French typography uses upright shape for both lowercase and uppercase. And the ISO standard is to use italic shape for both lowercase and uppercase.

The Euler and Symbol fonts not being available in other than their default upright shape, this question of shapes for Greek letters raises issues only in the case of the options LGRgreek and selfGreek.

The options frenchmath, itgreek, upgreek, itGreek and upGreek modify the Greek letter shapes according to the following rules, listed from the lowest to the highest priority:

no option: the lowercase Greek letters are in the same shape as Latin letters, and the uppercase in the same shape as applied to digits and operator names,

frenchmath: both lowercase and uppercase are in the same shape as the digits and operator names (most of the time this means "upright shape", but it can be otherwise),

itgreek, upgreek: both lowercase and uppercase are in the \itdefault, respectively the \updefault shape (at the time of loading the package or at the time of a subsequent call to \Mathastext or \MathastextWillUse),

itGreek, upGreek: same as above, but only for the uppercase letters.

So, the default gives the classic TEX behavior when option italic was passed. Each call to \Mathastext (or \MathastextWillUse) macros (described in a later section) reinitializes the computation of the shapes.

As mentioned already the package allows to define various "math versions". In the case of eulergreek or symbolgreek they apply to all these versions. In the case

of the options LGRgreeks or selfGreeks (notice the additional "s"), each math version is assumed to have its text font available in LGR (or OT1 encoding) and also the shapes will be local to the math version.

Finally version 1.15c of mathastext introduces new preamble-only commands to change the shapes, and even the font, used for Greek letters, in case of package options LGRgreek/selfGreek. They are \MTitgreek, \MTupgreek, \MTitgreek, \MTupgreek, \MTitgreek, \MTupgreek for the math versions which will be declared next in the preamble; and \MTgreek font{name_of_font} will tell the next math versions to use that font family. To use this command you need to know the (little) name of a suitable font family available in LGR encoding: for example lmr, txr (needs txfontsb package on your system), DejaVuSerif-TLF (needs dejavu package on your system), etc...

2.10 Unicode engines

mathastext has been made minimally unicode-aware and can be used with X_HT_EX or LuaL^AT_EX.

With XATEX the user is strongly advised to first consider using the mathspec package, which is designed for Unicode, with a key-value interface. With both XATEX and LualATEX, unicode-math is recommended for OpenType math fonts.

Particularly in the latter case you probably don't need, don't want, and should not use mathastext: it is extremely far from being able to define a math font, as it applies basically only to a subset of the 32-127 ascii range, and in particular it does not know how to use a given Unicode font simultaneously for Latin and Greek letters. Again the user is strongly advised to look at mathspec and unicode-math.

Let me point out explicitly that mathastext has not been tested in any systematic manner under the Unicode engines; and that it is expected to be most definitely incompatible with unicode-math, although your mileage may vary and some features may appear to work.

When using mathastext with either X_HT_EX or LuaL^AT_EX it is recommended to use the fontspec package. Else, some of the encoding dependent things done by mathastext like using the en-dash character to get a minus sign in math mode will not work correctly. Furthermore, it is necessary to load fontspec with its no-math option, and this must happen before loading mathastext.

Use fontspec with its *no-math* option, and load it *prior* to mathastext. For example, when using polyglossia one should presumably say:

\PassOptionsToPackage{no-math}{fontspec}

before the \usepackage{polyglossia} as fontspec will then be loaded in a manner compatible with mathastext.

Starting with release 1.3 of mathastext, the luatex engine binary must be at least as recent as the one which was provided with the TL2013 distribution.

The amsmath package, if used, must be loaded prior to mathastext. Under lualatex engine, it is recommended to also load the package lualatex-math.

I already mentioned in the section 2.6 the fact that the italic corrections were not available for OpenType fonts under the X_{\textstyle{T}EX} engine and only partially available for the LualateX engine, with the result that the spacings in math mode when using for the letters an upright text font will be less satisfying than with the standard pdfetex engine (the OpenType fonts not being usable with the latter engine, this is not a criterion of choice anyhow).

To specify math versions using unicode fonts, use the fontspec \setmainfont command (with arbitrary optional features). This command can be issued before loading mathastext, or after and then will be followed by a \Mathastext command with the name of the version in square brackets.

It is possible to mix unicode fonts and classical TEX fonts. But this is definitely not recommended as mathastext decides once and for all what is the font slot of things such as the text endash (used for the minus sign) and this is encoding dependent. So it is best to have either only unicode fonts, or only old-fashioned TEX fonts in a fixed encoding (T1, or LY1 for example).

The package was not extensively tested with unicode engines. I include here two examples which compiled successfully with X_HT_EX and LuaL^AT_EX, the first one on a Linux machine, the second one on a Mac OS X machine.³²

```
\documentclass{article}
\usepackage[hscale=0.8]{geometry}
\usepackage{multicol}
\usepackage[no-math]{fontspec}
\usepackage{lmodern}
\usepackage[subdued,italic]{mathastext}
\setmainfont[Color=999999]{Verdana}
                                         \Mathastext[Verdana]
\setmainfont[Color=0000FF]{Arial}
                                         \Mathastext[Arial]
\setmainfont[Color=00FF00]{DejaVu Serif} \Mathastext[DejaVu]
\MTDeclareVersion{times}{T1}{ptm}{m}{n}
\setmainfont[Color=FF0000]{Andale Mono} \Mathastext[Andale]
\begin{document}
\newcommand\TEST[1]{\MTversion{#1}%
\begin{multicols}{2}
\hbox to\columnwidth{\hbox to\columnwidth{\hfil
                $abcdefghijklmnopqrstuvwxyz$\hfil}\kern-2.5em{#1}}
   \centerline{ $ABCDEFGHIJKLMNOPQRSTUVWXYZ$ }
   \centerline{ $0123456789$ }
```

³²running tex (in a temporary repertory) on a copy of the file mathastext.dtx will extract extended versions of these examples as test files.

```
\$\,\%\,\&\,<\,>\,|\,\{\,\}\,\backslash$ }
\columnbreak
  \centerline{ abcdefghijklmnopqrstuvwxyz }
  \centerline{ ABCDEFGHIJKLMNOPQRSTUVWXYZ }
  \centerline{ 0123456789}
  \ \,\%\,\&\,<\,>\,\\\,\\\\,\\char92 \
\end{multicols}}
\begin{multicols}{2}
  \centerline{\textbf{math mode}}
\columnbreak
  \centerline{ \textbf{text} }
\end{multicols}
\TEST{DejaVu}\TEST{Verdana}\TEST{times}\TEST{Andale}
\TEST{Arial}\TEST{bold}\TEST{normal}
\end{document}
And now the same thing with fonts available on Mac OS X:
\documentclass{article}
\usepackage[hscale=0.8]{geometry}
\usepackage{multicol}
\usepackage[no-math]{fontspec}
\usepackage{lmodern}
\usepackage[subdued,italic]{mathastext}
\setmainfont[Color=FF0000]{Hoefler Text} \Mathastext[Hoefler]
\setmainfont[Color=336633]{American Typewriter}\Mathastext[Typewriter]
\setmainfont[Color=0000FF]{Herculanum}
                                      \Mathastext[Herculanum]
\setmainfont[Color=FF00FF]{Didot}
                                      \Mathastext[Didot]
\setmainfont[Color=999999]{Comic Sans MS} \Mathastext[Comic]
\begin{document}
  --- copy here the code from the previous example ---
\TEST{Didot}\TEST{Comic}\TEST{normal}\TEST{Herculanum}
\TEST{Hoefler}\TEST{Typewriter}\TEST{bold}
\end{document}
```

2.11 Compatibility issues

Compatibility issues (or just questions of who decides last) are naturally to be expected with packages dealing with the math setting; the fix is simply to load mathastext last. And one should always load amsmath before mathastext (this is especially true when using Unicode engines but applies in general as well).

Any definition made in a package loaded before mathastext of the font to be used for letters or for the common characters in the ascii basic range will be overruled by the loading of mathastext (this includes the case when the earlier package had made the character 'mathematically active'). Conversely most of the set-up done by mathastext may well be overruled by packages loaded later which do math related things.

In case of a 'too many math alphabets' message try the defaultalphabets option or one of its defaultnormal, defaulttt, etc... sub-options.

Starting with version 1.2, mathastext makes some characters 'mathematically active' to achieve certain effects: automatic insertion of the italic corrections when using an upright text font in math, extended scope of the math alphabet commands which now apply to non-letter symbols (and also to math operator names, but this is much easier to achieve). And the (already mathematically active) right quote is modified to have some extra space added before the derivative glyph '.

This is compatible with using \label and \ref in and outside of math mode. But a difficulty arises when some other package has made the character 'globally active' everywhere in the document. The action of mathastext is made anew at each mathematical inline or displayed formula. If it is detected that a character has been activated then nothing further will be done (so the mathastext feature³³ for that character is lost) except if it appears that this activation was done by the Babel system. In that case mathastext does not make the character mathematically active but it modifies in the appropriate manner the action of Babel for that character in math mode. Furthermore mathastext makes the character mathematically inactive.³⁴

Here is indeed some code that you should **not** try at home:

```
\documentclass{article}
\usepackage[french]{babel}
\usepackage{mathtools}\mathtoolsset{centercolon}
\begin{document}
$:$
\end{document}
```

DO NOT DO THIS AT HOME: it creates an infinite loop.³⁵ This is due to the fact that the colon is simultaneously active (this is made by babel+frenchb at begin document) and mathematically active (done by mathtools in the preamble). The interaction gives an infinite loop. Such a situation will be cured by mathastext, even loaded before mathtools, if use is made of \MTnonlettersobeymathxx. At each math formula mathastext will detect that Babel has activated the colon, and will cancel the mathematical activation (the precise definition done by mathtools was already lost at begin document due to overwriting by babel but the fact that the character was mathematically active remained true).

So far I have briefly described the problem of document active characters (see the test file mathastexttestalphabets.tex for more explanations and illustrations,

³³italic correction insertion for the latin letters, receptivity to the math alphabet action for the other characters.

³⁴only the characters ; ,:!?+-=<>()[]* mentioned in section 2.8 as 'difficult non letters' (and the right quote ') and the latin letters are concerned here; it seems highly unprobable that a latin letter $\in \{a-z, A-Z\}$ will have been made globally active (only letters never being used in command names are possible candidates), but mathastext has been designed to cope with it, should it happen ...

³⁵This seems to still be the case with Babel 3.9f and frenchb.ldf 2.6e, as tested on Sep. 2, 2013. Again tested with up-to-date TL2015 Vendredi 15 janvier 2016 à 11:10:30, with same result.

and the commented source code of the package). Pure mathematical activation revealed an incompatibility of another type with amsmath. To fix it, mathastext now replaces an inner macro of amsmath (\resetMathstrut0) with its own version.

Always load amsmath before mathastext.

Actually this last commandment was already made necessary by the use of the text endash to represent the minus sign in math mode, and, especially for Unicode engines, some aspects of the \DeclareMathOperator macro from amsmath.

Important! As is mentioned in the section 2.8, after command \MTnon lettersobeymathxx, characters such as ?, or [, now represent two 'tokens' and this will utterly confuse TeX if some precautions are not taken. Examples: \$0^+\$ or \$x\mathbb{7}^*\$ or \$R^*\$ must be input now as \$0^{+}\$ and, respectively, \$x\mathbb{?}y\$ or \$R^{*}\$. This is why the package does \MTnonlettersdonotobeymathxx by default.

One thing to take note of is that this mechanism uses the \everymath and \everydisplay, so if it is needed to add to these TEX 'token lists' some additional things this should be done in a way preserving the former contents.

If one issues (after \begin{document}) \everymath={} and \everydisplay={} this annihilates not only all the mathastext (evil ?) doings with math active characters but also everything else some other package might have put in these token registers, so it is better, if the need arises to cancel the math activation of characters done by mathastext to use the command \MTeverymathoff, which does all of \MTmathoperatorsdonotobeymathxx, \MTnonlettersdonotobeymathxx (already default), \MTmathstandardletters, \MTnormalprime, and \MTnormalas terisk. This is supposed to be used in a group or environment (as there is no \MTactivemathon). It must be used prior to entering math mode.

New with 1.3i: the command \url of package url, and the commands \url/\nolinkurl of package hyperref use math mode and a monospace font (by default). mathastext patches these commands in order for them to do automatically \MTeverymathoff.

3 Package options and commands

3.1 Summary of main options

italic, frenchmath: italic letters in math, upright uppercase if frenchmath.

subdued: acts in a subdued way. The IATEX normal and bold math versions are left (quasi) unchanged. With version 1.15e of the package this statement applies

also to the math alphabets \mathbf, \mathit, \mathsf, and \mathtt (and not only to \mathnormal and \mathrm as in previous versions.)

LGRgreek, eulergreek, symbolgreek: the Greek letters will be taken, respectively from the text font itself (in LGR encoding), or from the Euler font, or from the Postscript Symbol font.

symbolmax: all characters other than letters and digits, are taken from the Symbol font. This option also makes a number of further glyphs available, such as some basic mathematical arrows, and the sum and product signs. For documents with very simple needs in mathematical symbols, mathastext with option symbolmax may give in the end a PDF file quite smaller than the one one would get without the package.

defaultmathsizes: mathastext sets up bigger sizes for subscripts (it also copies code from the moresize package to redefine \Huge and define \HUGE). Use this option to prevent it from doing so.

defaultalphabets: by default, mathastext redeclares the math alphabets \mathrm, \mathit, \mathit etc... (but not \mathcal of course) to refer to the current document text fonts (at the time of loading the package and in each mathastext math version). Use this option to prevent it from doing so (each alphabet also has its own disabling option).

3.2 Miscellaneous

the en-dash as minus sign: very often the - character from the text font does not give a good minus sign. So by default, the package uses the en-dash sign -. Use noendash to deactivate it. Starting with version 1.12 of the package this 'en-dash as minus' should work in all encodings, including Unicode (if fontspec has been loaded).

Changed!

amsmath: the behaviour of the \DeclareMathOperator command of amsmath is modified by mathastext for it to use the correct font. Additionally, release 1.3n of mathastext at long last also handles an extra operation done by amsmath for '.:/-* to be used in operator names without the extra math spacing. This customization is suppressed in subdued mode for the normal and bold math versions.

hbar: the definition of \hbar inherited from default LATEX will in our context make use of the h of the current math font (so for us, it is also the text font, perhaps

³⁶To the experts: there is a long story here that \newmcodes@ hardcodes the font, that it was not compatible with Unicode engines, that during some time (2013-2016) lualatex-math fixed that and very recently amsopn.sty 2016/03/08 v2.02 also, so now lualatex-math 1.6 does nothing as it is already fixed "upstream" in amsopn.sty, but anyhow in both cases, this still hardcoded the font, so finally mathastext does the right thing from its point of view. See the code comments for more, there is an issue here with LualaTFX applying the curly right quote contrarily to X=LATFX.

in italic shape), but the bar accross the h will come from the original default math font for letters (usually cmmi), and furthermore its placement on the h can be odd-looking. So we redefine \hbar to use only the text font (and this will be aware of the italic option). Our construction does not always give an optimal result (and its scope is limited to the OT1, LY1 and T1 encodings), so an option nohbar deactivates it. There is no \hslash provided by the package, though. The version 1.12 of the package when dealing with a Unicode font tries to get the \hbar directly as a glyph from the font.

dotless i and j: by default the package redefines \i and \j to give the dotless i and j (if it exists at all), also in math mode, in the text font. Will overwrite the default commands \imath and \jmath. In version 1.12 of the package this should work in all encodings, including Unicode (it is then assumed that fontspec has been loaded, and of course that the glyphs are indeed in the font).

asterisk: versions of mathastext earlier than 1.2d [2013/01/02] did not do anything with the \ast control sequence but did pick the asterisk * in the document text font, and this often was a rather silly thing as the text asterisk is generally in a raised position. Furthermore, the * lost its status of a binary operator and was treated as an 'ordinary' symbol. An option noasterisk turned this feature off. Starting with 1.2d, the noasterisk option is deprecated and the new default is to do nothing. But when option asterisk is received by the package, then both \ast and * are simultaneously modified to use (as binary operators) the text asterisk, slightly lowered. The amount of lowering³⁷ is decided by the mandatory argument to the command \MT $lowerast{\langle dimen \rangle}$. The package initially does \MTlowerast{.3\height}. Doing \MTlowerast{.5ex} is not a good idea as it does not scale properly in the script and scriptscript styles. With an argument given as a multiple of \height, the asterisk will behave as expected in subscripts and subscripts of subscripts. But * is now 'mathematically active' 38 and \$R^*\$ or \$R^\ast\$ must be input as \$R^{*}\$ and \$R^{\ast}\$. Furthermore, they will obey the math alphabet commands.

X₃T_EX and Lual^AT_EX: for the en-dash and the dotless i and j, the package expects to detect either the EU1 encoding for X₃T_EX or the EU2 encoding for Lual^AT_EX (this will be true if fontspec was loaded), or one of OT1, LY1 or T1, else it will renounce and not attempt to access the en-dash or the dotless i and j glyphs. With I^AT_EX and PdfI^AT_EX, there is no such limitation and all 8bit-encodings (containing these glyphs) should be ok.

³⁷with the option symbolmisc, the asterisk is picked from the Symbol font, and the amount of lowering is non-customizable; however if a math alphabet command is used, the asterisk is then again from a text font and the lowering will be as specified by \MTlowerast.

 $^{^{38} \}text{in a hopefully safe way, for example }\abel{eq*1}\$ is ok.

fontspec: one more note to users of X_HT_EX/LuaL^AT_EX with **fontspec**: it has to be loaded with the option **no-math**, and before **mathastext**.

vec accent: The default \vec accent is not appropriate for upright letters, so math astext provides a \fouriervec which takes its glyph in a Fourier font, and an Ersatz \pmvec which is reasonably good looking on upright letters and works with the \rightarrow glyph. Contrarily to version 1.0, the default \vec is not overwritten with \fouriervec. And contrarily to version 1.1, one now needs to pass the option fouriervec to have the math accent \fouriervec defined by the package.

math alphabets: • We define a new math alphabet command \mathnormalbold which gives direct access to the bold version of the \mathnormal alphabet (rather than using either the \bm command from the bm package or the \boldsymbol command from the amsbsy package). As it does not exist in the default LATEX math font set-up, this alphabet is not subjected to the subdued option action.

- The other math alphabet changing commands defined by the package are \MathEulerBold, \MathEuler and \MathPSymbol.
- \mathnormal, \mathrm, \mathbf, \mathit, \mathsf and \mathtt are modified to make reference to the document text fonts (this can be disabled by suitable package options).
- version 1.2 of mathastext has extended the scope of the math alphabets to apply to non-alphabetical characters and to operator names. This respects the automatic white spaces added by TeX around math symbols.

math accents: an option mathaccents is provided to pick up the accents in math mode from the text font, but the package knows only T1, LY1 or OT1-compatible encodings.

Regarding the encoding-dependent glyphs: the en-dash, the dotless i and j, the math accents, the hbar, are encoding dependent and the relevant decisions are made once by mathastext at the time it is loaded and are applied to all declared math versions. So you can use math versions with different encodings but, regarding these characters only those with the same encoding as the normal math version will display them correctly.

It is thus recommended that all declared mathastext math versions use the same font encoding.

3.3 Commands

A few preliminary comments, mainly destined to advanced users aware of some TeX innards (more extensive explanations are to be found in the code comments).

The timing for actions of mathastext falls into three cases:

- 1. things done during the loading of the package, or delayed to \AtBeginDocument,
- 2. things done as the result of user commands, either in the preamble or in the body of the document,
- 3. things done everytime math mode is entered.

The second category overlaps with the others, as the (preamble) use of some commands can have either immediate effect or only trigger some actions in \AtBeginDocument or perhaps only influence the things done later by mathastext each time math mode is entered.

The third category deserves some brief additional comments: it mainly (but not exclusively) regards the "math activation" of characters, and conversely all "math activations" fall into this category. The package re-checks each time math mode is entered if some characters have been made in-between catcode active, or math active, and takes appropriate decisions: one important aspect of this issue is that babel's mechanism for activating character was not, last time I checked, very robust against math active characters. I now checked again (on January 15, 2016) that

```
\documentclass{article}
\usepackage[french]{babel}
\usepackage{mathtools}\mathtoolsset{centercolon}
\begin{document}
$:$
\end{document}
```

creates an infinite loop (see section 2.11 where this was mentioned already, some years ago). Thus mathastext has (since 1.2e 2013/01/10) a somewhat elaborate mechanism related to these issues (see the code comments), installed into the list of things done by TEX systematically each time it enters math mode. For some legacy reason the package also puts into this list a few other things which could arguably be done elsewhere once and for all. The command \MTeverymathoff cancels all such actions done by mathastext each time math mode is entered.

3.3.1 Preamble-only commands

These commands mainly facilitate the definition of math versions, in a mathastext extended sense. It is not necessary to use them to activate the package basic functionalities, as loading mathastext is enough (except with the subdued option).

• \Mathastext (or \mathastext) reinitializes mathastext: it sets the fonts used in math mode (in versions normal and bold) for letters, digits and a few ascii symbols to the *current* defaults of encoding, family, series and shape. 39 Both the normal and bold math version are modified by this action of \Mathastext.

Mathastext updates also the font and shapes for the Greek letters (LGRgreek option), and the skips to be inserted after the symbols \forall and \exists , see *infra*.

- math versions: \Mathastext accepts an optional argument [\(\name\)]. With this (within square brackets) argument, rather than redefining the fonts for math mode, \Mathastext declares a new math version, and it is this math version which will use the then current text font in math mode.
- inheritance: starting with version 1.3c a second optional argument [\langle other_version \rangle] will transfer its set-up for things not affected by math astext action, like large symbols, to the declared math version whose name was given as first optional argument. The main use will be with [bold] in order for the symbols and large symbols to be typeset as in the bold math version. For example, this document has in its preamble:

\MTseries{b} % next \Mathastext will use a bold font

\Mathastext[boldnewcent][bold]% large symbols, etc, will be bold too We can check that it does work:

 $\label{eq:model} $$ \MTversion{newcent}: abcde \oint \bigvee \biguplus \bigotimes \bigoplus \\ MTversion{boldnewcent}: abcde \oint \bigvee \biguplus \bigotimes \bigoplus \\$

Naturally, for this one needs an initial math font setup with some nice bold fonts also for large symbols. This is the case with the excellent txfonts package of Young Ryu. As the present document must use many fonts and declares many math alphabets, we did not load the full package and fonts but only the largesymbols:

\DeclareSymbolFont{largesymbols}{OMX}{txex}{m}{n} \SetSymbolFont{largesymbols}{bold}{OMX}{txex}{n} \DeclareFontSubstitution{OMX}{txex}{m}{n}

- \Mathastext may be preceded optionally by one or more of \(41 \MTencoding{\langle}(enc)\rangle, \MTfamily{\langle}(fam\rangle), \MTseries{\langle}(ser\rangle), \MTshape{\langle}(sh\rangle), and \MTlettershape{\langle}(sh\rangle). For example valid values are, respectively, \(\langle T1\rangle, \langle phv\rangle, \langle m\rangle, \langle n\rangle, and \langle it\rangle: this is the Helvetica font in T1-encoding, regular (medium) series, upright shape, and the letters will be in italic shape. Once used their effect applies to all succeeding calls to \Mathastext, and can only be undone by using them again.
- \MTWillUse [\langle ltsh \rangle] \{\langle enc \rangle} \{\langle fam \rangle} \{\langle ser \rangle} \{\langle ser \rangle} \{\langle sh \rangle}\$ tells mathastext to use the font with the specified encoding, family, series, and shape for the letters and digits (and all other afflicted characters) in math mode. The optional argument \langle ltsh \rangle specifies a shape for the letters, for example \itdefault, or directly \langle it \rangle or \langle sc.

The allowed version names are as for the LATEX \DeclareMathVersion macro. Do not use \Mathastext[foo] with foo equal to "normal" or "bold"; this is already taken care of by the initial loading of the package or a later command \Mathastext without any optional argument.

⁴¹these commands exist also with long names: \Mathastextencoding, etc... The same applies to the other commands mentioned in this section.

• \MTDeclareVersion [$\langle ltsh \rangle$] { $\langle name \rangle$ } { $\langle enc \rangle$ } { $\langle ser \rangle$ } { $\langle sh \rangle$ } [$\langle other_version \rangle$]: declares that the document will have access to the font with the specified characteristics, under the math version name $\langle name \rangle$. For example:

\MTDeclareVersion[sc]{palatino}{T1}{ppl}{b}{sl}

declares under the name palatino a version where mathematics will be typeset using the Palatino font in T1-encoding, bold, slanted, and the letters will in fact be in caps and small caps (and bold).⁴² When the initial optional argument is absent, and mathastext was loaded with the italic option, then the default letter shape will be it,⁴³ else letters will have the same shape as used for digits and operator-names.

Another optional argument may be used as last argument. Similarly as its use with \Mathastext this makes the declared math version inherit, for things not modified by mathastext like large symbols, the font set up of the math version whose name was passed as optional argument (typical use will be with [bold]).

- \MTboldvariant{\(\sigma var\)}: when used before \Mathastext, specifies which bold (b, sb, bx, ...) to be used by \mathbf (and \boldmath). Default is the \bfdefault at the time of loading mathastext. When used before the declaration of a version, decides the way \mathbf will act in this version.
- $\MTEulerScale{\langle factor \rangle}$: scales the Euler font by $\langle factor \rangle$.
- $\MTSymbolScale{\langle factor \rangle}$: scales the Symbol font by $\langle factor \rangle$.
- \MTitgreek, \MTupgreek, \MTitGreek, \MTupGreek: optional commands, active only in the case of the LGRgreek option, to decide the shape of the Greek letters in the versions which will be declared next.
- \MTgreekfont{\(\fontfamily\)\}: optional command with a mandatory argument which specifies the font for Greek letters in all mathastext math versions declared afterwards via \Mathastext or \MTDeclareVersion. Only effective with LGRgreek option.

3.3.2 Commands usable only outside of math mode

They are usable only from outside math mode because they act via turning on or off the execution, each time math mode is entered, of certain macros added by mathastext to the \everymath and \everydisplay token list variables.

• \MTmathactiveletters: activates the 'math activation' of Latin letters. This is done by the package during loading, except under the subdued option. 44 It

⁴²I do not especially recommend to use this in real life!

⁴³more precisely, the shape is the latest value passed in one of the previously used package commands to specify the shape of letters, or the \itdefault of the time of loading the package.

 $^{^{44}\}mbox{Prior}$ to 1.3j, it was also executed from each \Mathastext in the preamble.

is again executed in the body at each \MTversion, except under the subdued option when switching to the *normal* or *bold* math versions.

The letters are made mathematically active⁴⁵ to insert the extra skips as specified by \MTsetmathskips (see section 2.5), and also possibly the italic corrections when using upright fonts (see section 2.6).

- \MTmathstandardletters: cancels the 'math activation' of the letters. Must be re-issued after each \MTversion, but see \MTeverymathdefault.
- \MTicinmath: this command is executed by default by mathastext except in case of option subdued or if the user chosen letter shape is oblique (it or s1). It tells mathastext to add italic corrections after all letters in math mode, except within the scope of math alphabets.⁴⁶

This command and the next ones in this item can be used in the preamble as well as in the body of the document (in case of subdued option, using the commands from within the preamble will remain without effect, as the document body will start in the subdued normal math version anyhow.) But each \MTversion in the body will re-emit \MTicinmath (in case of non-oblique letter shape), except if the subdued option was used and the chosen math version is normal or bold.

The effect of this and the other commands of this item is local to the group or environment in which it has been issued.

It may theoretically be used from inside math mode, but the included \MTmathactiveletters will have an effect only if issued prior to entering math mode.

\MTnoicinmath: this command deactivates the package added italic corrections. It can be used inside as well as outside of math mode (or in the preamble of the document).

\MTICinmath, \MTnoICinmath: these commands activate the italic corrections only for the uppercase letters (but recall that \MTicinmath is done by default, thus this will typically have to follow \MTnoicinmath.)

\MTicalsoinmathxx: this command de-activates the de-activation of the italic corrections inside the arguments to the math alphabet commands. It can be issued inside as well as outside of math mode. Will be effective only if \MTicinmath or \MTICinmath is in force. To cancel its effect either enclose it in a group or environment or re-issue \MTicinmath after it.

- \MTnormalasterisk, \MTactiveasterisk: the latter will use for * and \ast the text font asterisk, suitably lowered; the former tells mathastext to not modify the LATEX default. Both are no-op without option asterisk.
- \MTeasynonlettersobeymathxx, \MTeasynonlettersdonotobeymathxx: the former is done by default, it makes characters ., /, |, \, #, \$, %, and & (if not excluded by package options) obey math alphabet commands. See also section 2.8. This functionality does *not* make the characters "math active" (but it does modify \mathcode's, naturally).

 $^{^{45}}$ the mathcode's are only modified at the time of execution of \everymath, \everydisplay.

⁴⁶Prior to 1.3i, italic corrections were added to the (non-oblique) letters of \mathnormal arguments.

- \MTnonlettersobeymathxx, \MTnonlettersdonotobeymathxx: the former will make (except if excluded by relevant package options) !,?,.,:,;+,-,=,(,)[,], <, and > obey the math alphabet commands (when not used as delimiters). These characters are made "math active", and each one now expands to two tokens. This makes for example \$a^!\$ illegal input and it will have to be coded \$a^{!}\$. Hence, by default, the package does \MTnonlettersdonotobeymathxx. \MTexplicitbracesobeymathxx extends an earlier \MTnonlettersobeymathxx to also treat \{ and \}. But then \left\{, \right\} must be coded \left\lbrace, \right\rbrace rather. There is also \MTexplicitbracesdonotobeymathxx.
- \MTnormalprime, \MTprimedoesskip: the latter (done by default if not subdued, New! (1.3j) and also on each use of \MTversion in the body of the document except for the subdued normal and bold math version) makes it so that ' takes into account the math glue as specified by \MTprimeskip. The former is its opposite. In all cases the right quote ', is a mathematically active character producing ' as is the default in TeX, it is only its meaning which changes to include or not an extra skip. For some (legacy) reason, this change of meaning is done anew by mathastext each time math mode is entered. The commands of this item are thus no-op from inside math mode.
- \MTeverymathdefault: this hook is executed by \MTversion{\langle version_name \rangle}, New! (1.3j) except under option subdued when switching to the normal or bold math versions. Its default meaning is:

```
\MTactiveasterisk % this has no effect without option asterisk
\MTprimedoesskip % this makes prime glyph obey extra space
\MTeasynonlettersobeymathxx
\MTicinmath
                 % this does \MTmathactiveletters, hence also skips from
```

% \MTsetmathskips are obeyed. \MTfixfonts % only operant under LuaLaTeX.

Notice that under subdued option, switching to the normal or bold version does \MTeverymath off which includes \MTnonlettersdonotobeymathxx. But the default \MTeverymathdefault which is issued when going back to a non-normal or bold math version doesn't do \MTnon lettersobeymathxx. It is up to the user to correct this if needed (no issue without subdued

Notice also that \MTversion{\(\lambda\) version name\\}, except for normal or bold if subdued does \MT foralldoesskip and \MTexistsdoesskip, which are not included in \MTeverymathdefault actions as they are not related to \everymath and \everydisplay.

• \MTeverymathoff: does \MTnormalasterisk, \MTnormalprime, \MTnonletters New! (1.3j) donotobeymathxx, \MTeasynonlettersdonotobeymathxx, \MTmathstandardlet ters and \MTdonotfixfonts.

The commands \url/\nolinkurl of package hyperref and url from url.sty (which use math New! (1.3i) mode under the hood) are patched by mathastext to do \MTeverymathoff automatically: this is needed because mathastext modifies anew some mathcodes each time math mode is entered, hence may overwrite to some extent the specific preparation done by {url,hyperref}.sty.

Automatically done by MTversion under option subdued if switching to the normal or bold math versions; and \MTversion then does also \MTnormalexists and \MTnormalforall.

- \MTfixfonts: this is operant only under LuaLATFX. It has the effect that each time math New! (1.30) mode is entered macro \MTfixmathfonts will be executed. The latter forces so-called base mode for the used text font in math mode, in an effort to (only partially, see code comments) fix the fact that OpenType features such as Lining Figures were in some cases not being applied in math mode when one uses text fonts there (text fonts are declared by LuaTFX+luaotfload to use node mode, which is non-functional in math.) It is invoked automatically by the package (except for normal and bold math versions under subdued option), and in normal situations, there is no reason to use it directly.
- \MTdonotfixfonts: cancels the job of \MTfixfonts. Done automatically in subdued New! (1.30) mode when in the normal or bold math version; in normal contexts, there is no reason to use this command. Only operant under LuaLATEX.

• \MTfixmathfonts: this used to be an inner macro but it is given a public name by 1.3p because New! (1.3p) I discovered that \.\hbox{\MTversion{foo}\\$..\\$\ (same with \mathversion) causes an issue and one needs to invoke again \MTfixmathfonts after the box, for some reason. To be used only under LuaLATEX and only for such rare cases where it may be needed.

3.3.3 Commands usable everywhere

• $MTsetmathskips{\langle a-z/A-Z\rangle}{\langle muglue before\rangle}{\langle muglue after\rangle}$: is used to specify extra skips (or rather mu glue) to be inserted in math mode, before and after a letter. The rationale is that standard text fonts used in math mode may sometimes cause glyph (near-) collisions with math symbols, as TFX has some implicit expectations on the design of fonts for math letters.

These extra skips around letters are set at their natural width and do not add any stretchability or shrinkability to the math formula as a whole, nor do they result in extra potential break points.

Random (silly) examples:

\MTsetmathskips{x}{\medmuskip}{\thickmuskip} $\label{local_model} $$ MTsetmathskips{A}_{.5mu}_{2.3mu}$$

and the effect: $vw \times yzABC^{vw \times yzAB\hat{C}}$. The effect obeys the usual LATEX scoping rules.

The first argument of \MTsetmathskips may be any expandable code giving a letter; this facilitates use of \MTsetmathskip in \Ofor loops such as this one:

\makeatletter

\@for\@tempa:=a,b,c,d,e,f,g,h,i,j,k,l,m,n,o,p,q,r,s,t,u,v,w,x,y,z\do{% \MTsetmathskips{\@tempa}{2mu}{2mu}}%

\makeatother

Starting with v1.3i: the extra skips are not applied to the letters within the scope of math alphabet commands, or the letters from operator names (pre-defined or user declared).

Note that contrarily to the \MTexistsskip, \MTforallskip, and \MTprimeskip commands described next, these extra skips (which may be specified in the preamble) are not recorded in the definition of the math version (as defined via \Mathastext with its optional argument or via \MTDeclareVersion). The declared skips hold thoughout the document until modified or canceled, independently of math versions (of course, mathastext cancels the skips in the normal and bold math versions if package option subdued was used).

• \MTunsetmathskips $\{\langle a-z/A-Z\rangle\}$: cancels the skips for that letter (they are not set to Omu but completely removed).

The argument may be a macro (or any expandable code) expanding to a letter.

- \MTexistsskip{\(math \ qlue\)}: specifies the amount of skip or more generally glue to put after each ∃ math symbol. Indeed, upright letters (or digits for that matter) often appear to be positioned a bit too close to the quantifier: ∃B. The package default is to add a 1mu skip (this default is set to zero in the case of italic): ∃B. One can change the default with the following syntax: \MTexistsskip{2mu plus 1mu minus 1mu}, which if used in the preamble and followed with a \Mathastext command (or \MTDeclareVersion), will be recorded in the definition of this math version (and subsequent ones). One may also use the command at any time in the document. In the case of the option subdued, the skip is canceled in the normal and bold math versions.⁴⁷ In the case of the option italic, the default skip is set to zero.
- \MTnormalexists, \MTexistsdoesskip: the latter (done by default if not New! (1.3j) subdued, and also on each use of \MTversion in the body of the document) makes it so that ∃ takes into account the math glue as specified by \MTexistsskip. The former is its opposite.

- $MTforallskip{(math glue)}$: the default is to add a .6667mu math skip after each \forall (except with the option italic for which the default skip is set to zero). Compare $\forall F$ (has the skip) with $\forall F$ (has no skip). Use this command in the preamble to set up the skip or glue to be used in the next to be declared math versions. In the case of the option subdued, the skip is canceled in the normal and bold math versions.⁴⁸ In the case of the option italic, the default skip is zero for all math versions. One may use the command at any location in the document.
- \MTnormalforall, \MTforalldoesskip: the latter (done by default if not New! (1.3j) subdued, and also on each use of \MTversion in the body of the document) makes it so that ∀ takes into account the math glue as specified by \MTforall skip. The former is its opposite.

Changed! Changed!

⁴⁷Prior to 1.3j, it was set to 0mu.

⁴⁸Prior to 1.3j, it was set to 0mu.

- $\MTprimeskip{\langle math qlue \rangle}$: the default is to add a 0.5mu skip before the derivative glyph, except for the italic option. In the case of the option subdued, the skip is canceled in the *normal* and *bold* math versions.⁴⁹
- $\MTlowerast{\langle dimen \rangle}$: a \raisebox command is used to lower the text asterisk to produce a reasonable math asterisk. The package uses this command initially with argument 0.3\height, this will have to be fine-tuned for each given text font but worked out ok with the fonts we tried. Note that the dimension argument will be used also in sub-scripts and sub-sub-scripts, so it is best not to use an absolute dimension.
- \MTmathoperatorsobeymathxx, \MTmathoperatorsdonotobeymathxx: the former is done by default, it makes operator names obey math alphabets. See also section 2.8. This functionality does **not** rely on "math active characters". Automatically issued by each \MTversion, except under option subdued when switching to normal or bold.
- \MTcustomgreek: in case mathastext has been loaded with one of its Greek related options, this activates the corresponding customization of Greek letters in math mode. It is issued automatically by the package in the preamble (except if loaded with subdued option) and at each switch of math version via \MTversion or \MTversion* (except for the normal and bold math versions in subdued mode). Also available as \Mathastextcustomgreek. May be used even inside of math mode.
- \MTstandardgreek: in case mathastext was loaded with one of the Greek related options this command reverts the customization, it resets the Greek letters to their definitions in force at package loading time. Can be used in the preamble, but is mainly for the document body (may even be used inside math mode ...). Done automatically under the subdued option when switching to the normal or bold math version. Also available as \Mathastextstandardgreek.

3.3.4 Body-only commands

- $\MTversion[\langle nametext \rangle] \{\langle namemath \rangle\}, \MTversion*\{\langle namemath \rangle\},$ also known as \Mathastextversion (and as \MTVersion, and \mathastextversion):
 - the non-starred version changes both the document text fonts and the math fonts (for those characters treated by mathastext): the mandatory argument is the math version to be used for math; the optional argument is the name of (another) mathastext-declared math version, the font which was chosen during its declaration will be set as document text font (and \familydefault etc...also are redefined). In the absence of the optional argument, the mandatory one is used. The versions must be either normal,

⁴⁹Prior to 1.3j, it was set to 0mu.

or bold, or previously declared ones via \Mathastext or \MTDeclareVer sion.

• the starred variant does the math set-up, but changes *nothing* to the text fonts (see subsection 2.4 for a description of the math set-up, which summarizes what is done additionally to only using LATEX's \mathversion).

\MTversion[\(\lambda\)] {\(\lambda\)} does \MTeverymathdefault\) (except for \MTversion{normal} and \MTversion{bold} under package option subdued), which in particular activates the insertion of skips around letters specified by \MTsetmathskips\) and also, if the font used is not oblique the insertion of italic corrections (for better positioning of subscripts; see the discussion in subsection 2.6). Under the frenchmath option the package checks separately the letter shape for lowercase and uppercase.

\MTversion also does \MTexistsdoesskip, \MTforalldoesskip, and also \MT New! (1.3j) primedoesskip, \MTmathoperatorsobeymathxx, except under the subdued option for *normal* and *bold*, in which case it does the opposite actions.

All further commands are usable only inside math mode.

- \hbar: this is constructed (in a way compatible with the italic option) from the h letter and the accent from the mathastext font. Note that \mathrm{\hbar} and \mathbf{\hbar} should work and that \hbar does scale in subscripts and exponents. Only for T1 and OT1 (or LY1) encodings.
- \fouriervec: this is a \vec accent taken from the Fourier font; the fourier package need not be loaded. Active only if option fouriervec.
- \pmvec: this provides a poor man \vec accent command, for upright letters. It uses the right arrow. Does not change size in subscripts and exponents.
- \mathnormal, \mathrm, \mathbf, \mathit, \mathsf, \mathit: modifications of the original \mathnormal, \mathrm, \mathbf, \mathit, \mathsf, \mathit to use the mathastextified font. The underlying internal LATEX structures related to the original commands are not overwritten, so the original commands can be saved under other names before \usepackage{mathastext}, to be used in case of necessity (this is what option subdued does.)
- \mathnormalbold: a bold version of \mathnormal. Differs from \mathbf when the italic option has been used, or when use has been made of \MTlet tershape to specify a shape for letters distinct from the one for digits and operator names, or similarly when the math version has been declared via \MTDeclareVersion with its optional parameter for shape of letters.
- \inodot, \jnodot: the corresponding glyphs in the chosen font for math mode. By default, will overwrite \imath and \jmath. With version 1.12 by

default \i and \j work also in math mode and give then \inodot, resp. \jn odot. This should work for all 8bit-encodings having these glyphs, and also in Unicode.

- \MathEuler, \MathEulerBold: math alphabets to access all the glyphs of the Euler font, if option eulergreek (or eulerdigits was passed to the package.
- \MathPSymbol: math alphabet to access the Symbol font.
- when one of the options symbolgreek, eulergreek, or selfGreek is passed to the package the capital Greek letters which look like their Latin counterparts acquire names: \Digamma, \Alpha, \Beta, \Epsilon, \Zeta, \Eta, \Iota, \Kappa, \Mu, \Nu, \Omicron, \Rho, \Tau, \Chi (no \Digamma for Symbol). Also an \omicron control sequence is provided.
- LGR Greek and 'var'-letters: only the \varsigma is available in this encoding, so using for example \varphi will load the previous default math font. It might thus be suitable when recompiling already written LATEX sources to add to the preamble \let\varphi=\phi, \let\varepsilon=\epsilon, etc..., in case only the 'variant' form of the letter was used in the documents.
- Miscelleneous mathematical symbols from the postscript Symbol font are made available (or replaced) by option symbolmisc.⁵⁰ They are \prod ∏ \sum ∑ \implies ⇒ \impliedby ← \iff ←⇒ \shortiff ⇔ \to → \longto → \mapsto → \longmapsto → \aleph ¼ \inftypsy ∞ \emp tyset Ø \surd √ \nabla ∇ \angle ∠ \forall ∀ \exists ∃ \neg ¬ \club suit ♣ \diamondsuit ♠ \heartsuit ♥ \spadesuit ♠ \smallint ∫ \wedge ∧ \vee ∨ \cap ∩ \cup ∪ \bullet \div ÷ \otimes ⊗ \oplus ⊕ \pm ± \ast * \times × \proptopsy ∞ \mid | \leq ≤ \geq ≥ \approx ≈ \supset ⊃ \sub set ⊂ \supseteq ⊇ \subseteq ⊆ \in ∈ \sim ~ \cong ≅ \perp ⊥ \equiv ≡ \notin ∉ \langle ⟨ \rangle ⟩. And a \DotTriangle ∴ is made available by option symbolre (which overwrites \Re and \Im: ℜ, ℑ). The \inftypsy and \proptopsy have these names to leave up to the user the choice to replace (or no) the original (larger) \infty ∞ and \propto ∞.

Regarding the \prod and \sum commands: they will use the Symbol glyphs $\Pi\Sigma$ in inline math, and in display math the Computer Modern ones (or whatever is set up by other packages; here we have the symbols from txfonts):

$\prod \sum$

The package provides \prodpsy and \sumpsy: if one really wants in all situations the Symbol glyphs, one can do \let\prod\prodpsy and \let\sum\sumpsy. Also \MToriginalprod and \MToriginalsum will refer to the \prod and

⁵⁰option asterisk is also required to treat the *. Recall from subsection 2.8 that the asterisk in math mode (also when using the control sequence \ast) appears then to TFX to be a composite object.

\sum before redefinition by the package: this is to allow constructs such as \$\displaystyle\MToriginalprod\$ or \[\textstyle\MToriginalprod\], because they would not work with the \prod and \sum as re-defined by the package.

3.4 Complete list of options

- basic: only mathastextify letters and digits.
- subdued: do not change the default fonts or the math alphabets in math mode for the normal and bold math versions, turn on the mathastext-ification only after an explicit \MTversion (or \mathastextversion) command activating an additional math version as declared in the preamble. With option subdued \MTversion{normal} and \MTversion{bold} do \MTmathoperators donotobeymathxx, \MTeasynonlettersdonotobeymathxx, \MTmonlettersdono tobeymathxx, \MTmathstandardletters.
- italic: the letters default to italic shape in math mode.
- frenchmath: italic lowercase Latin letters, but uppercase Latin letters in the same font as for digits and operator names. In general this means that they will be upright. In case of the LGRgreek option, frenchmath influences also the shape of the Greek letters.
- endash, emdash: use the text font en-dash (—) or even the em-dash (—, but this seems crazy) for the minus sign rather than -. endash option is default for the package.
- asterisk: use the text font (or the Symbol font) asterisk in math mode.
- noendash: the minus sign will be the from the text font, not the en-dash -.
- nohbar: prevents mathastext from defining its own \hbar.
- nolessnomore: besides !?, ...; +-=()[]/# % & mathastext treats also <>| { } and \. Use this option to let it not do it. This is the default in case of OT1-encoding.
- further excluding options: noexclam!? nopunctuation,.:; noplus, nominus, noplusnominus +- noequal = noparenthesis()[]/ nospecials #\$%& and nodigits.
- alldelims: true by default, means that the characters excluded by nolessnomore are treated. Use this option in case of a mono-width OT1-encoded font.
- nosmalldelims: this prevents mathastext from trying to pick up in the text font the 'small variants' of some math delimiters; it only affects what happens when a character such as a left parenthesis (or [is used as a delimiter, and in

the event that T_EX has chosen the smallest sized variant. This has no impact on what happens when they are not used as delimiters: then, and if not disabled by the corresponding options, these characters are always picked up from the text font.⁵¹

- symbolgreek, symboldigits: to let Greek letters (digits) use the Symbol font.
- symbolre: replaces \Re and \Im by the Symbol glyphs \Re , \Im and defines a \Dot Triangle command (...).
- symbolmisc: takes quite a few glyphs, including logical arrows, product and sum signs from Symbol. They are listed *supra*. Doing \renewcommand{\int}{\smallint} will maximize even more the use of the Symbol font.
- symboldelimiters: the characters apart from letters and digits will be taken from the Symbol font.
- symbol: combines symbolgreek, symbolre, and symbolmisc.
- symbolmax: combines symbol and symboldelimiters.
- eulergreek, eulerdigits: to let Greek letters (digits) use the Euler font.
- LGRgreek: this is for a font which is also available in LGR-encoding. It is possible to change the font per math version, via the use of the \MTgreekfont command in the preamble.
- LGRgreeks: each declared math version will be supposed to be with a font which is also available in LGR-encoding.
- selfGreek: this is for a font which is also available in OT1-encoding and contains the glyphs for the default eleven capital Greek letters.
- selfGreeks: each declared math version will be supposed to be with a font with the eleven capital Greek letters in its OT1-encoded version.
- upgreek, itgreek, upGreek, itGreek: options to tell to use \itdefault or \up default for the lowercase and uppercase (or only the uppercase) Greek letters. Only operant in the case of the LGRgreek(s) and selfGreek(s) options.
- mathaccents: use the text font also for the math accents. As in vanilla LATEX, they are taken from the font for the digits and \log-like names. Obey the alphabet changing commands. Will work only for T1, LY1, or OT1-compatible encodings.

⁵¹in this very special situation of option nosmalldelims, the braces are an exception to this rule and they require both of \MTnonlettersobeymathxx and \MTexplicitbracesobeymathxx for being picked up from the text font when not used as delimiters.

- defaultbf, defaultit, defaultsf, defaulttt: do not set up, respectively, the \mathbf, \mathit, \mathsf, and \mathtt commands to use the mathastext-ified font. This also prevents mathastext to create internally \Mathxx alphabets (it never overwrites the original \mathxx things but let \mathxx point to \Mathxx instead), so one can use these options if one encounters a 'too many math alphabets' LATEX error.
- defaulnormal, defaultrm: do not identify the default \mathnormal (resp. \mathrm) with the newly created \Mathnormal (resp. \Mathrm) commands which use the mathastextified fonts in each math version.
- defaultalphabets: all the defaultxx options together, and additionally tells mathastext not to create the \mathnormalbold alphabet either.
- defaultimath: do not overwrite \imath and \jmath, do not extend \i and \j to math mode use.
- defaultmathsizes: do not change the LATEX defaults for the sizes of exponents and subscripts.
- fouriervec: provides a \fouriervec command. The user can then add in the preamble \let\vec=\fouriervec. There is also always available a "poor man" vec accent \pmvec for upright letters.

Thanks to Kevin Klement, Tariq Perwez and Ricard Torres for sending bug reports and feature requests when the first version of the package was issued.

Numerous examples will be found there:

http://jf.burnol.free.fr/mathastext.html
http://jf.burnol.free.fr/showcase.html

4 Change log

1.3p [2016/05/13]

- * bugfix: release 1.3n had forgotten to activate by default its new customization of the amsmath macro \newmcodes@ (it was done from using \MTversion in the document body but not by default at start of body.)
- * public name $\backslash \mathsf{MTfixmathfonts}$ for a 1.30 macro.

1.3o [2016/05/03]

* mathastext fixes an issue related to a feature of LuaLaTeX and luaotfload that OpenType fonts are declared in one of two modes: node and base, and only the latter is functional in math mode. But by default text fonts are declared in mode node. Thus mathastext now intervenes to make it so that the font it declares in math mode will use mode basic. This fixes issues with for example old style figures being used while the text font used lining figures (or vice versa, depending on the font). But see the code comments for more.

1.3n [2016/04/22]

* at long last, mathastext takes care properly of annoying and perplexing amsmath's \newmcodes@. The very recent change in amsopn.sty finally made it compatible with Unicode engines, but anyhow, mathastext must do its own patch to use the correct font. All of this taking into account the various options passed to the package. Lots of trouble for a tiny thing.

1.3m [2016/04/02]

 \ast minor code maintenance before annual TL freeze.

1.3I [2016/01/29]

 \ast compatibility with fontspec's upcoming switch from EU1/EU2 to TU common to both Unicode engines.

1.3k [2016/01/24]

* typos fixed in the documentation. In particular, the README link to the package homepage had remained broken from day one of the package releases: mathastext.html therein was misspelled as mathastext.html! (but the pdf documentation had the correct link; as well as the CTAN catalogue).

1.3j [2016/01/15]

- * renamed and modified recent 1.3i's \MTactivemathoff into \MTeverymathoff. Added \MTeverymathdefault.
- * subdued mode is a bit stronger: also the asterisk reverts to the default (if it was modified due to option asterisk), the added extra \mskip's (useful with upright fonts) for ', \exists, and \forall are suppressed rather than re-configured to use 0mu. Related new commands \MTexistsdoesskip, \MT-foralldoesskip, \MT-primedoesskip, \MT-normalexists, \MT-normalforall, \MT-normalprime.
- * the toggle for using mathematically active letters is only emitted once during package loading; the \Mathastext command does not do it anymore; the use in the preamble of \MTmathstandardletters, or \MTnoicinmath and related commands is not overruled by later use of \Mathastext.
- * quite a few documentation improvements and rewrites, particularly in the description of commands which are related to the modifications of mathcodes (mainly for math activation of characters or letters) as done by mathastext at \everymath or \everydisplay.

1.3i [2016/01/06]

- * \url from url.sty as well as \url and \no-linkurl from hyperref.sty use math mode and (by default) the monospace text font. To avoid math-astext overwriting the special preparation done by \url,hyperref\understate{.sty the commands \url/\nolinkurl are patched to do automatically \MTactivemath-off (now \MTeverymathoff) before entering math mode
- * the extra skips specified by \MTsetmathskips are not inserted around letters if inside the arguments of math alphabet commands, or within operator names.
- * the added explicit italic corrections (for nonoblique fonts) were disabled within math alphabet scopes, except mathnormal; they are now disabled within all math alphabets, inclusive of mathnormal

1.3h [2015/10/31]

* bugfixes: since 1.3d 2014/05/23 the option symbolgreek caused \ell to become undefined,

and, similarly but far worse, options selfGreek, self-Greeks caused all lowercase Greek letters \alpha, \beta, etc.. to become undefined.

1.3g [2015/10/15]

* following 2015/10/01 LaTeX release, removal of the "luatex" prefix from the names of the LuaLaTeX math primitives. Compatibility maintained with older LaTeX formats.

1.3f [2015/09/12]

- * the replacement of amsmath's \resetMathstrut@, when it is done, emits an Info rather than a Warning as this could be potentially stressful to some users.
- * the README self-extracts from the dtx source, as a text file README.md with Markdown syntax.

1.3e [2015/09/10]

* bugfix: under option nosmalldelims, \lbrace and \rbrace were redefined as math symbols and could not be used as delimiters.

1.3d [2015/02/26]

* the documentation mentions the improved compatibility of mathastext with the latest (3.34) beamer release: no more need for \usefont-theme{professionalfonts}.

1.3d [2014/05/23]

- * new commands \MTstandardgreek and \MTcustomgreek .
- * The Greek letters, in case of use of one of the package related options, are left to their defaults in the normal and bold math versions if the subdued option was also used (this was so far the case only with options LGRgreek/LGRgreeks).
- * \newmcodes@ of amsmath is left untouched if package lualatex-math is detected.

1.3c [2013/12/14]

- * added a starred variant to $\backslash MT$ version which tells mathastext to only do the math set-up and not modify the text fonts.
- * added second optional version name argument to \Mathastext and to \MTDeclareVersion, to transfer settings for things not otherwise changed by mathastext from a math version to the one declared. This is mainly for symbols and large symbols to be the bold ones when the user sets up

the series of a mathastextified font to be bold in a mathastext-declared version.

- * renamed \defaultprod to \MToriginalprod, \defaultsum to \MToriginalsum, (this is in case of option symbolmisc).
- * changes to the dtx organization; options for generating the documentation can be customized in generated mathastext.tex file.
- * 1.2d code for #, \$, %, and & modified erroneously the earlier correct 1.2c code and created a bug showing up with more than 16 math families (a possibility only with lualatex or xelatex).

1.3a [2013/09/04]

- * the somewhat silly \string's are removed from the \MTsetmathskips command of release 1.3, thus allowing its first argument to be a macro, or any expandable code, giving a letter.
- * the amsmath \resetMathstrut@, which is incompatible with a mathematically active parenthesis (is now modified only if necessary (i.e. only when \MTnonlettersobeymathxx is issued) and is restored to its original value if not needed anymore (i.e. after \MTnonlettersdonotobeymathxx, as for example when switching to the normal version under option subdued).
- * improved documentation.

1.3 [2013/09/02]

- * commands \MTsetmathskips and \MTunsetmathskips added.
- * commands \MTmathactiveletters and \MTmathstandardletters to govern the math activation of letters independently of its use for insertion of the italic corrections (\MTicinmath and \MTnoicinmath correspondingly modified).
- * the new \luatexUmathcodenum as available since TL2013 allows identical treatment by mathastext of = and under both LuaTeX and XeTeX.
- * \newmcodes@ of amsmath is left untouched in case of option basic.
- * a sentence containing | which was written to the log during the loading caused a problem if | was active (typically if $MakeShortVerb\{\|\}$ was added to the preamble prior to the loading of mathastext).
- * some preemptive measures taken regarding things such as \mid, \lbrace, and \rbrace, as some packages define these things in manners which

made the re-definitions done by mathastext issue errors.

1.2f [2013/01/21]

* minor code improvements. Change log added to the user manual.

1.2e [2013/01/10]

This version should be the last one in the 1.2 series as it seems to correct most of the main problems which were introduced with the massive use of mathematically active characters in versions 1.2 and 1.2b

* It is indeed a thorny point when one wants to modify an active character in math mode only (without breaking usage in label's and ref's for example). The package now does that _only_ if the activation originated in the Babel system as it is then possible to modify appropriately the Babel macros \user@active<char> and \normal@char<char>, at the time of entering math mode (mathastext does all its activation job at \everymath and \everydisplay).

The relevant issues are discussed in section 2.10 of the user manual, in the test file mathastexttestal-phabets.tex, and in the source code comments for macro \mst@mathactivate. The inherent incompatibility of Babel with packages having made mathematically active the characters itself makes document active is circumvented by this interference of mathastext. A generally applicable Babel patch could be derived from the method used by mathastext.

For the non catcode active characters, mathematical activation is used. This is done at the entrance in math mode.

- * Sadly, the feature of added italic corrections introduced in version 1.2b did not behave as described in the user manual, due to forgotten group braces. Fixed.
- * The command \MTlowerast from the user manual of v1.2d was not the one implemented in the source code. Fixed.
- * The test files automatically extracted from a latex run on the dtx file have been revised and extended
- * The code is better documented.

1.2d [2013/01/02]

* an incompatibility with amsmath (its macro \rowniangle \rowniangle resetMathstrut@), exists since version 1.2 of the package. This is fixed here.

- * various improvements in dealing with the asterisk and in the mechanism of letting non-letter symbols obey the math alphabet commands.
- * documentation extended and improved.

1.2c [2012/12/31]

- * mathastext now inserts automatically after all (latin) letters in math mode their italic corrections, if the font used is upright (sic). This improves the spacings for the positioning of subscripts. The feature is de-activated inside the math alphabets commands (apart from \mathnormal), so as to not prohibit the formation of ligatures.
- * the documentation has been extended to explain in detail the issues which are relevant to the new feature of added italic corrections.
- \ast version 1.2 had some bad bugs when confronted to active characters. This is corrected and additionally \MTnonlettersdonotobeymathxx is made the default, as the user input is too much constrained in its absence.
- * a less fatal, but still annoying, typo had made the dot in 1.2 of type \mathpunct rather than \mathord.
- * the inner namespace has been rationalized a bit.

1.2 [2012/12/20]

- * a new command sets up the amount of space to be automatically inserted before the derivative glyph (useful when using an upright font).
- * the scope of the math alphabets has been extended to apply to the non-alphabetical characters, and also to operator names.
- * the format of the dtx file has changed. The package file is self-extracting from the dtx, and four additional test files are also produced during latex mathastext.dtx.

1.15f and 1.15g [2012/10/25]

- * \S , #, &, and \S had been re-defined by mathastext since its inception in a rather strange (but working) way, which could cause surprises to other packages. Fixed.
- * the subdued mechanism for the math alphabets is implemented in a simpler and more efficient manner than in 1.15e.
- * the defaultxx options act a bit differently, and are more useful in case of a too many math alphabets situation.

- * various improvements in the documentation.
- * general clean up and better commenting of the source code.

1.15e [2012/10/22]

- * new user commands to specify skip or glue to be inserted after the math symbols $\ensuremath{\backslash}$ exists and $\ensuremath{\backslash}$ forall
- * complete (user transparent) rewrite of the code implementing the subdued option; and its action has been extended to apply also to the \mathbf, \mathit, \mathsf, \mathtt alphabets and not only to \mathrm and \mathnormal as in the previous versions.
- * improvements in the documentation.

1.15d [2012/10/13]

- * the Unicode situation is now correctly treated, throughout the code (this had been left in a half-done way from version 1.14 of April 2011).
- * this includes an issue related to amsmath and its DeclareMathOperator macro which has been fixed.
- * and the code related to \relbar and \Relbar (and \models) has been revised.

1.15c [2012/10/05]

- * it is now possible to use distinct fonts in LGR encoding for the Greek letters according to the current math version.
- * improvements to the documentation.

1.15b

- * corrected a 'feature' of 1.15 which was backward-incompatible
- * improvements to the pdf documentation

1.15 [2012/09/26]

- * the subdued option allows the mathastextification to act only locally.
- * some measures taken to deal with amsmath related issues when using xetex or luatex.

1.14c

* a bug is fixed: the \Mathastext macro reinitializes the fonts in the normal and bold math versions, but it also erroneously redeclared the math alphabet changing commands which could have been set up in previously defined math versions (via earlier calls to \Mathastext\[version_name\]).

1.14b [2011/04/03]

- * there was a bug with \S , #, &, % in math mode which showed up when ten or more math families had been declared. This bug affected also the minus sign under the same circumstances, when Unicode engines were used. Fixed.
- * the options LGRgreek and selfGreek act now a bit differently, and new options LGRgreeks and selfGreeks have been defined.
- * I also cleaned up a bit the code, for a more structured namespace.

1.14

* mathastext now modifies also the math alphabets \mathit, \mathsf and \mathtt, thus making it a quite generic complete manner to adapt the math configuration to fonts provided with no math support.

1.13b

* when the Symbol font is used for \prod and \sum this will be only for inline math; display math will use the default glyphs

1.13 [2011/03/11]

- * the LGRgreek option is added.
- * internal changes for better readability of the code.

1.12

- * various bugs have been corrected.
- * the endash and alldelims options are active by default.
- * the package is more Unicode aware.
- * the \Mathastext command has been improved to facilitate the mechanism of math versions also when using XeTeX or LuaTeX (with package fontspec.)
- * the en-dash and dotless i and j now work with all encodings, Unicode inclusive.

1.11 [2011/02/06]

* optional argument to \Mathastext macro.

1.1 [2011/02/01]

* options italic and frenchmath.

1.0 [2011/01/25]

* Initial version.

5 Implementation

The usual catcode regime for letters and digits is assumed and some characters such as *, ', ", = are supposed to be of catcode other at the time of loading of mathastext. The source of mathastext takes precautions for some other characters such as the right quote ', which may thus be active with no harm at the time of loading. By the way, I think LATEX2e should have provided to authors a standard macro to be used at the beginning of a style file to make sure the catcodes are standard. Shorthands created by Babel should be mostly no problem as Babel does the activation only at the \begin{document}.

The comments have been accumulating through successive versions with only partial efforts to achieve some sort of coherence; as a result some are a bit strange or obsolete to various degrees. And the similar remark applies to some ancient parts of the code itself!

```
1 \NeedsTeXFormat{LaTeX2e}
2 \ProvidesPackage {mathastext}
3 [2016/05/13 v1.3p Use the text font in math mode (JFB)]
```

Testing for X₇T_FX and LuaI⁴T_FX.

1.3g 2015/10/15: update for the naming of primitives, the situation has evolved both on X_HT_EX side and on the Lual^AT_EX side (LaTeX base 2015/10/01): I was told "U" named math primitives were always available for Lual^AT_EX. For X_HT_EX, the XeTeX prefix got replaced by U prefix with 0.99.. a certain number of 9. I opted for rather simple approach of just trying the "modern" names and if they don't exist fall back on earlier (and in danger of being deprecated) names.

```
\let\mst@Umathcharnumdef\Umathcharnumdef
5
    \let\mst@Umathcodenum
                             \Umathcodenum
    \let\mst@Umathcode
                             \Umathcode
    \let\mst@Umathchardef
                             \Umathchardef
8 \newif\ifmst@XeTeX
9 \ifx\XeTeXinterchartoks\@undefined
    \mst@XeTeXfalse
11 \else
    \mst@XeTeXtrue
12
    \ifx\mst@Umathcharnumdef\@undefined
13
      \let\mst@Umathcharnumdef\XeTeXmathcharnumdef
15
      \let\mst@Umathcodenum
                               \XeTeXmathcodenum
      \let\mst@Umathcode
                               \XeTeXmathcode
16
      \let\mst@Umathchardef
                               \XeTeXmathchardef
17
18
    \fi
19\fi
20 \newif\ifmst@LuaTeX
21 \ifx\directlua\@undefined
    \mst@LuaTeXfalse
23 \else
24
    \mst@LuaTeXtrue
25
    \ifx\mst@Umathcharnumdef\@undefined
      \let\mst@Umathcharnumdef\luatexUmathcharnumdef
26
27
      \let\mst@Umathcodenum
                               \luatexUmathcodenum
      \let\mst@Umathcode
                               \luatexUmathcode
28
      \let\mst@Umathchardef
29
                               \luatexUmathchardef
```

```
30 \fi
31 \fi
32 \newif\ifmst@XeOrLua
33 \ifmst@LuaTeX\mst@XeOrLuatrue\fi
34 \ifmst@XeTeX \mst@XeOrLuatrue\fi
```

- 1.2: all inner macros of mathastext now starts with \mst@ for a cleaner name-space.
- 1.31 2016/01/29: hmmm... at this late stage where nobody would expect me to still look at the code, I have found at least two macros which still didn't: \do@the@endashstuff and \do@the@emdashstuff.

Ok, doing something more serious: compatibility with upcoming TL2016 fontspec and its switch to 'TU' NFSS font encoding in replacement of 'EU1/EU2'. Anyhow, the code in mathastext has been common to the two Unicode engines for a while, hence it is not hard to adapt to the replacement of EU1/EU2 by TU, maintaining compatibility with legacy installations.

\mst@OneifUniEnc

```
35 \def\mst@oti{OT1}\def\mst@ti{T1}\def\mst@lyi{LY1}
36 \def\mst@eui{EU1}\def\mst@euii{EU2}\def\mst@tu{TU}
37 \def\mst@OneifUniEnc {%
38 \ifx \mst@tmp@enc\mst@tu 1\else
39 \ifx \mst@tmp@enc\mst@eui 1\else
40 \ifx \mst@tmp@enc\mst@eui 1\else 0\fi\fi\fi }
41 \newif\ifmst@goahead
42 \newif\ifmst@abort
```

\mst@enc Macros to store the font settings, each math version will store its own records.

```
\mst@fam 43 \def\mst@enc{\encodingdefault}
\mst@ser 44 \def\mst@fam{\familydefault}
\mst@opsh 45 \def\mst@ser{\seriesdefault}
```

\mst@bold 46 \def\mst@opsh{\shapedefault}

\mst@ltsh 47 \def\mst@bold{\bfdefault}

48 \def\mst@ltsh{\shapedefault} %% will be default shape for letters

\mst@greekfont

1.15c: for use by the LGRgreek and selfGreek options. Defined as an \edef in order to be able to set-up once and for all the Greek at the time of \usepackage. Modifiable in the preamble via \MTgreekfont{\(\lambda font_name \)}\Mathastext.

%% will be default shape for operator names

49 \edef\mst@greekfont{\familydefault} %% v 1.15c

Package options

2011/03/09: 1.13 introduces the option LGR greek and systematic use of \inf ... conditionals, for better readability (by myself) of the code.

```
50 \newif\ifmst@italic
51 \newif\ifmst@frenchmath
      \DeclareOption{italic}{\mst@italictrue
52
53
          \def\mst@ltsh{\itdefault}}
      \DeclareOption{frenchmath}{\mst@frenchmathtrue\mst@italictrue
54
        \def\mst@ltsh{\itdefault}}
55
56 %%
57 \newif\ifmst@endash\mst@endashtrue
      \DeclareOption{endash}{\mst@endashtrue}
58
      \DeclareOption{noendash}{\mst@endashfalse}
59
```

```
60 \newif\ifmst@emdash
       \DeclareOption{emdash}{\mst@emdashtrue\mst@endashfalse}
62 %%
63 \newif\ifmst@alldelims
64 \edef\mst@tmp\encodingdefault}\ifx\mst@oti\mst@tmp\else\mst@alldelimstrue\fi
       \DeclareOption{alldelims}{\mst@alldelimstrue}
       \DeclareOption{nolessnomore}{\mst@alldelimsfalse}
67 %% new with 1.2
68 \newif\ifmst@nosmalldelims
       \DeclareOption{nosmalldelims}{\mst@nosmalldelimstrue}
70 %%
71 \newif\ifmst@noplus
       \DeclareOption{noplus}{\mst@noplustrue}
73 \newif\ifmst@nominus
       \DeclareOption{nominus}{\mst@nominustrue}
75 \DeclareOption{noplusnominus}{\ExecuteOptions{noplus,nominus}}
77 \newif\ifmst@noparen
       \DeclareOption{noparenthesis}{\mst@noparentrue}
79 \newif\ifmst@nopunct
       \DeclareOption{nopunctuation}{\mst@nopuncttrue}
81 \newif\ifmst@noequal
       \DeclareOption{noequal}{\mst@noequaltrue}
83 \newif\ifmst@noexclam
       \DeclareOption{noexclam}{\mst@noexclamtrue}
85 \newif\ifmst@asterisk
       \DeclareOption{noasterisk}{\PackageWarningNoLine{mathastext}}
87
           {option 'noasterisk\string' is deprecated.^^J\space\space\
88
            Check the documentation}}
       \DeclareOption{asterisk}{\mst@asterisktrue}
89
90 \newif\ifmst@nospecials
       \DeclareOption{nospecials}{\mst@nospecialstrue}
92 \newif\ifmst@basic % 1.3 to avoid unnecessary patch of amsmath \newmcodes@
93 \DeclareOption{basic}{\mst@basictrue
       \ExecuteOptions{noparenthesis,nopunctuation,%
94
95
                       noplusnominus, noequal, noexclam, nospecials, nolessnomore}}
96 %%
97 \newif\ifmst@nohbar
       \DeclareOption{nohbar}{\mst@nohbartrue}
99 \newif\ifmst@nodigits
       \DeclareOption{nodigits}{\mst@nodigitstrue}
101 \newif\ifmst@defaultimath
       \DeclareOption{defaultimath}{\mst@defaultimathtrue}
103 \newif\ifmst@mathaccents
       \DeclareOption{mathaccents}{\mst@mathaccentstrue}
104
105 %%
106 \newif\ifmst@needsymbol
107 \newif\ifmst@symboldelimiters
       \verb|\DeclareOption{symboldelimiters}{\mbolltrue\mbolltrue\mboldelimiterstrue}| \\
```

```
109 \newif\ifmst@symboldigits
       \DeclareOption{symboldigits}{\mst@needsymboltrue\mst@symboldigitstrue}
111 \newif\ifmst@symbolgreek
112 \newif\ifmst@customgreek %% new with 1.3d
       \DeclareOption{symbolgreek}{\mst@needsymboltrue\mst@symbolgreektrue
114
                                    \mst@customgreektrue }
115 \newif\ifmst@symbolre
       \DeclareOption{symbolre}{\mst@needsymboltrue\mst@symbolretrue}
117 \newif\ifmst@symbolmisc
       \DeclareOption{symbolmisc}{\mst@needsymboltrue\mst@symbolmisctrue}
119 \DeclareOption{symbol}{\ExecuteOptions{symbolgreek,symbolmisc,symbolre}}
120 \DeclareOption{symbolmax}{\ExecuteOptions{symbol,symboldelimiters}}
121 %%
122 \newif\ifmst@needeuler
123 \newif\ifmst@eulerdigits
       \DeclareOption{eulerdigits}{\mst@needeulertrue\mst@eulerdigitstrue}
125 \newif\ifmst@eulergreek
       \DeclareOption{eulergreek}{\mst@needeulertrue\mst@eulergreektrue
126
127
                                   \mst@customgreektrue }
128 %%
129 \newif\ifmst@selfGreek
       \DeclareOption{selfGreek}{\mst@selfGreektrue\mst@customgreektrue}
131 \newif\ifmst@selfGreeks
       \DeclareOption{selfGreeks}{\mst@selfGreekstrue\mst@selfGreektrue
132
133
                                   \mst@customgreektrue }
134 \newif\ifmst@LGRgreek
       \DeclareOption{LGRgreek}{\mst@LGRgreektrue\mst@customgreektrue}
136 \newif\ifmst@LGRgreeks
137
       \DeclareOption{LGRgreeks}{\mst@LGRgreekstrue\mst@LGRgreektrue
138
                                  \mst@customgreektrue}
139 %%
140 \def\mst@greek@select{0}
141 \newif\ifmst@itgreek
142 \newif\ifmst@upgreek
       \DeclareOption{itgreek}{\mst@itgreektrue}
143
144
       \DeclareOption{upgreek}{\mst@upgreektrue}
145
       \DeclareOption{itGreek}{\def\mst@greek@select{1}}
       \DeclareOption{upGreek}{\def\mst@greek@select{2}}
146
147 %%
Starting with 1.15f the meaning of the 'defaultxx' options has changed. They now prevent
mathastext from defining additional alphabets rather than prevent it from identifying the
 'mathxx' with the new 'Mathxx'. The 'Mathnormal' and 'Mathrm' alphabet commands are al-
ways created as they are SymbolFontAlphabets.
148 \newif\ifmst@defaultnormal
       \DeclareOption{defaultnormal}{\mst@defaultnormaltrue}
150 \newif\ifmst@defaultrm
       \DeclareOption{defaultrm}{\mst@defaultrmtrue}
152 \newif\ifmst@defaultbf
       \DeclareOption{defaultbf}{\mst@defaultbftrue}
```

```
154 \newif\ifmst@defaultit
       \DeclareOption{defaultit}{\mst@defaultittrue}
156 \newif\ifmst@defaultsf
157
       \DeclareOption{defaultsf}{\mst@defaultsftrue}
158 \newif\ifmst@defaulttt
       \DeclareOption{defaulttt}{\mst@defaultttrue}
160 \newif\ifmst@nonormalbold
161 \DeclareOption{defaultalphabets}{\ExecuteOptions{defaultnormal,defaultrm,%
162 defaultbf, defaultit, defaultsf, defaulttt}\mst@nonormalboldtrue}
mathastext considers the default script and especially scriptscript sizes to be far too small, and
it will modify them. An option maintains the default.
163 \newif\ifmst@defaultsizes
       \DeclareOption{defaultmathsizes}{\mst@defaultsizestrue}
165 \newif\ifmst@twelve
       \DeclareOption{12pt}{\mst@twelvetrue}
166
167 \newif\ifmst@fouriervec
       \DeclareOption{fouriervec}{\mst@fouriervectrue}
1.15: the subdued option.
169 \newif\ifmst@subdued
       \DeclareOption{subdued}{\mst@subduedtrue}
171 \DeclareOption*{\PackageWarningNoLine{mathastext}
       {Unknown option '\CurrentOption\string'}}
173 \ProcessOptions\relax
```

\exists
\mst@exists@skip
\forall
\mst@forall@skip
\MTnormalexists
\MTexistsdoesskip
\MTnormalforall
\MTforalldoesskip

1.15e 2012/10/21: math skip/glue after \exists and \forall, this is useful with upright letters in math mode. Each math version has its own user defined values for the skips, stored as macros. The redefinitions of \exists and \forall are done only at the end of the package as the symbol option will also want to redefine these math symbols.

The subdued option (later and only for the normal and bold math version) and the italic option (here) set to zero the package default skips. With 1.2 the skips can be modified on the fly in the document, they are not necessarily set in the preamble once and for all for each math version.

1.3j adds \MTnormalexists, \MTexistsdoesskip, \MTnormalforall, \MTforalldoesskip. Earlier to 1.3j, \let\mst@stdexists\exists was done at End of Package, now it is done at Begin Document, and same for \forall. We pay attention that use of \MTnormalexists etc... inside the preamble does not create self-let's.

Also subdued mode will do \MTnormalexists, \MTnormalforall (earlier than 1.3j, it only set the muskips to Omu.) Same when using \MTversion{normal}, if subdued.

For some (random, legacy) reason, the handling of \exists and \forall is part of the things (also \MTmath operatorsobeymathxx not included inside \everymath/\everydisplay.

```
174 \newmuskip\mst@exists@muskip %% v 1.15e
175 \newmuskip\mst@forall@muskip
176 \def\mst@exists@skip{1mu}
177 \def\mst@forall@skip{.6667mu}
178 \ifmst@italic\ifmst@frenchmath\else
179 \def\mst@exists@skip{0mu}
180 \def\mst@forall@skip{0mu}
```

```
\def\mst@prime@skip {0mu}
181
182 \fi\fi
183 \def\mst@exists\\mst@stdexists\\mskip\\mst@exists@muskip}
184 \def\mst@forall{\mst@stdforall\mskip\mst@forall@muskip}
185 \AtBeginDocument{%
      \let\mst@stdexists\exists
186
      \let\mst@stdforall\forall
187
      \def\MTnormalexists {\let\exists\mst@stdexists }%
188
      \def\MTexistsdoesskip {\let\exists\mst@exists }%
189
190
      \def\MTnormalforall {\let\forall\mst@stdforall }%
      \def\MTforalldoesskip {\let\forall\mst@forall }%
191
```

The document body starts in the normal math version, whether or not \Mathastext command as been used in the preamble (which either re-defines the normal/bold math version or defines another one in case of optional argument), and in case of subdued option should use the standard \forall and \exists .

```
\ifmst@subdued
192
      \else
193
194
        \MTexistsdoesskip
        \MTforalldoesskip
195
196
      \fi
197 }%
198 \newcommand*\MTnormalexists
                                   {\AtBeginDocument {\MTnormalexists}
                                                                          }}
199 \newcommand*\MTexistsdoesskip {\AtBeginDocument {\MTexistsdoesskip }}
200 \newcommand*\MTnormalforall
                                  {\AtBeginDocument {\MTnormalforall
201 \newcommand*\MTforalldoesskip {\AtBeginDocument {\MTforalldoesskip }}
```

\prime
\mst@prime@skip
\active@math@prime
\MTnormalprime
\MTprimedoesskip

1.2 2012/12/17: math skip/glue before the \prime glyph. This is useful with the default CM glyph and upright letters (in contrast the prime from txfonts works fine with upright letters). For this we replace the \prime kernel $\active@math@prime$ with our own skip-enhanced version $\mbox{mst@active@math@prime}$.

1.2b 2012/12/31: doing

```
{\catcode'\'=\active \global\let'\mst@active@math@prime}
```

is awfully wrong when the right quote is made active at begin document by some other package (as happens with babel for some languages). So mathastext treats now the right quote with the same method as applied to the other characters it makes mathematically active. This uses the macro \mst@mathactivate which is defined later in the package.

Babel does \let\prim@s\bbl@prim@s when ' is made active via its services (the czech and slovak languages also store the initial version of \prim@s, else the quote would not work correctly when being again of catcode 12), and it doesn't matter if mathastext is loaded before or after this happens, as the \mst@mathactivate does its job only as part of the \everymath and \everydisplay token lists.

- 1.2e being paranoid, we take precautions against a possibly catcode active right quote at the time of loading mathastext.
 - 1.3i adds \MTactiveprime.
- 1.3j renames it to \MTprimedoesskip. Besides, it makes use in the preamble of \MTnormal prime or \MTprimedoesskip.

```
202 \newmuskip\mst@prime@muskip %% v 1.2
203 \def\mst@prime@skip{.5mu}
204 \ifmst@italic\ifmst@frenchmath\else\def\mst@prime@skip{0mu}\fi\fi
```

```
205 \def\mst@active@math@prime{\sp\bgroup\mskip\mst@prime@muskip\prim@s}
206 {\catcode'\'=12
207 \gdef\mst@@modifyprime{\mst@mathactivate'{}\mst@active@math@prime}}
208 \newcommand*\MTnormalprime
                               {\let\mst@modifyprime\@empty }
209 \newcommand*\MTprimedoesskip {\let\mst@modifyprime\mst@@modifyprime}
210 \ifmst@subdued
       \MTnormalprime
211
212 \else
       \MTprimedoesskip
213
214\fi
215 \AtBeginDocument{%
     \everymath\expandafter
              {\the\everymath
                                  \mst@modifyprime \MTnormalprime}%
217
     \everydisplay\expandafter
218
219
              {\the\everydisplay \mst@modifyprime \MTnormalprime}%
220 }
```

\MTforallskip \MTprimeskip

- \MTexistsskip 1.15e: These user macros set up the amount of muglue after \exists or \forall. The normal and bold math versions inherit the same skips; these skips are set to zero in case of the subdued, or the italic option. Each command \Mathastext[\langle version_name \rangle] stores the current values in the definition of the math version.
 - 1.2: \MTprimeskip added, the silly \@onlypreamble are removed and the macros are modified to have immediate effect in the document, independently of their possible use in the preamble for the math versions to store values.

Note (september 2013): the names were badly chosen; \MTsetprimeskipto for example would have been a better choice.

```
221 \newcommand*\MTexistsskip[1]{\edef\mst@exists@skip{#1}%
       \mst@exists@muskip\mst@exists@skip\relax}
223 \newcommand*\MTforallskip[1]{\edef\mst@forall@skip{#1}%
224
       \mst@forall@muskip\mst@forall@skip\relax}
225 \newcommand*\MTprimeskip[1]{\edef\mst@prime@skip{#1}%
       \mst@prime@muskip\mst@prime@skip\relax}
227 \let\Mathastextexistsskip\MTexistsskip
228 \let\Mathastextforallskip\MTforallskip
229 \let\Mathastextprimeskip\MTprimeskip
230 \let\mathastextexistsskip\MTexistsskip
231 \let\mathastextforallskip\MTforallskip
232 \let\mathastextprimeskip\MTprimeskip
```

\resetMathstrut@

2012/12/31: The amsmath macro \resetMathstrut@ is not compatible with a mathematically active opening parenthesis: it does

\mathchardef\@tempa\mathcode'\(\relax

and is made a part of the hook \every@math@size inside \glb@settings. This is called from \check@mathfonts which is done in particular in \frozen@everymath, hence before (but wait) what mathastext puts in \everymath. Also, \glb@settings is triggered by \mathversion which must be done outside of math mode.

Alas, with things such as \$...\hbox{...\$..}...\$ mathastext will have already made the parenthesis (mathematically) active. And \boldsymbol from amsbsy disables the \@nomath switch and executes \mathversion{bold} directly in math mode. So we have a problem with \resetMathstrut@.

lualatex-math replaces \resetMathstrut@ with its own version (which also looks at)) and no error is signaled when mathastext has done \mathcode'(="8000, but the \Mathstrutbox@ created by mathastext is then wrong.

The replacement macro avoids a potentially math active (. It assumes that there is still some appropriate glyph in slot 40 of operators and it sets the height and depth of \Mathstrutbox@ to be large enough to accommodate both this glyph and the one from the mathastext font (both in the current math version). If option noparenthesis was used, we leave everything untouched.

In 1.3a, 2013/09/04, the modification is done only at the time of \MTnonlettersobeymathxx. It is canceled by \MTnonlettersdonotobeymathxx. So the code has been moved to these macros and here we just store at the begin document the then meaning of \resetMathstrut@, and check also if \MTnonlettersobeymathxx has been invoked in the preamble.

1.3f 2015/09/12 issues only an Info message not a Warning, as I am becoming aware from another context (etoc) that Warnings are stressful to users, in some integrated environments for editing and compiling IATEX source files.

```
233 \ifmst@noparen\else
234 \AtBeginDocument{%
235
       \@ifundefined{resetMathstrut@}{% nothing to do, no amsmath
       }{% amsmath loaded, and possibly patched by things such as lualatex-math
236
       \let\mst@savedresetMathstrut@\resetMathstrut@
237
       \PackageInfo{mathastext}{current meaning of amsmath
238
         \string\resetMathstrut@\space saved}%
239
       \ifx\mst@the\the % means that \MTnonlettersobeymathxx was used in preamble
240
241
         \let\mst@the\@gobble\MTnonlettersobeymathxx
      fi}
242
243\fi
```

1.2 2012/12/20 does some rather daring math activation of ; , : ! ? + - = < > () [] in math mode to achieve something I wanted to do since a long time: overcome the mutually excluding relation between the variable-family concept and the automatic spacing concept. After loading <code>mathastext</code>, these characters now obey the math alphabets commands but still have the automatic spacing. The use as delimiters for those concerned is also ok.

The activation is done via setting the \mathcode to "8000 through the macro \mst@mathactivate which in turn is put into the \everymath and \everydisplay token lists. No character is made active in the sense of the \catcode (the issues with catcode active characters at the entrance of the math mode are discussed later),

```
but the concerned characters will now expand in math mode to two tokens.
```

1.2c 2012/12/31: hence, this current implementation puts constraints on the input: $x^?$ or $x\rightarrow x$ now create errors. They must be input $x^?$, respectively $x\rightarrow x$.

```
The disactivating macro \MTnonlettersdonotobeymathxx is made the default.
```

The mechanism is (even more) off by default for \{ and \} as this is not compatible with their use as delimiters (\lbrace and \rbrace should be used instead) but it can be activated for them too.

\mst@mathactivate

1.2b 2012/12/30: there were bad oversights in the 1.2 code for \mst@mathactivate related to the possibility for some characters to have been made active (in the sense of the catcode) elsewhere (something which often is done by language definition files of the babel system). The code from v1.2b tried to provide correct behavior using a prefix called \mst@fork (its definition and its use has since been modified) which let the active character expand to the mathastext re-definition only in math mode and only if \protect was \@typeset@protect. This indeed

took care of situations such as \$\hbox{?}\$ with an active ? or \$\label{eq:1}\$ with an active : (assuming for the latter that things would have worked ok before the twiddling by mathastext).

1.2e 2013/01/09: alas \ref{eq:1}\\$ still was a problem. Indeed in that case the mathastext prefix had no means to know it was inside a \ref so it made the character expand to its mathastext redefinition, which is not acceptable inside a \csname...\endcsname. What happens with Babel is that it patches things such as \ref, \newlabel,... we can test the \ifCsafeCactives flag to detect it in that case, but this is Babel specific. After having thought hard about this I see no general solution except patching all macros such as \ref...(in an imitation of what Babel does). So the final decision is to not do anything when the character is catcode active except it it seems that Babel is behind the scenes.

Incidently, Babel and TikZ are buggy with characters which are mathcode actives. For example the combination of [french] {babel} and mathtools with its centercolon turns \$:\$ into an infinite loop!!

In the case of Babel the reason is that, generally (but not always, the right quote ' is an exception), the $\normal@char(char)$ fall-back is $\string(char)$. But this is wrong if the mathcode is 32768! The fall-back becomes the default if the user switches to a language where (char) is 'normal' and then an infinite loop arises.

As a further example (I am not familiar with other languages from the Babel system) with frenchb the active !?;: expand in math mode to \string! or ? or ; or :. This creates an infinite loop if the mathcode is 32768.

For the special case of the right quote 'when it is made active by Babel, its fall-back does not invoke \string' so being still of mathcode 32768 is not a problem.

I have posted on TeX StackExchange how Babel should possibly modify its definitions and I use this here. I simplify a bit my proposed replacement of \normal@char\char\ as the check for \protect is superfluous, I think, having been done already at the level of the Babel prefix.

Replacing $\user@active\langle char\rangle$ is indeed not enough, and $\normal@char\langle char\rangle$ also must be changed, because when the user switches back to a language where the character is 'normal' it remains catcode active. The crucial thing is the test of ∞ is the replacement of the $\normal@char\langle char\rangle$, besides of course the test for math mode in both replacements.

When the character is not catcode active, then mathastext uses the math activation method. As the mathcode is not looked at in \edef, \write or inside \csname...\endcsname nothing special needs to be done, I think, in terms of protection against premature expansion. (I did not know that initially).

So, to recapitulate, mathastext will use the mechanism of the active mathcode if the character is not catcode active, and in the opposite case will do something only in the context of Babel, modifying directly its \user@active\char\ and its \normal@char\char\ macros and it does NOT then set the mathcode to 32768!!, rather it makes sure the character is not mathematically active.

- As 1.2e is a bit paranoid it takes precautions against the possibility of characters it treats being active at the time of its loading. Excepted from the scope of the paranoia are the latin letters (that would be crazy!) and also *, " and the left quote '.
- 1.2f 2013/01/21 with earlier versions (*) it was important not to do twice the business of \mst@mathactivate (think \$\hbox{\$?\$}\$), so I used (this was a bit wasteful) some sort of boolean macro for each character. But now that there are the \mst@the.. prefixes, let's just use them! (don't know why I did not think of that earlier; perhaps I had in mind some more general character per character customization initially, which I just dropped.)
- (*) it is still important to not do twice the thing when the character is active, in which case the babel macros are patched.

As an aside, \$\hbox{\catcode'?=\active \$?\$}\$ for an ? which was unactive at the first \$

will just make mathastext overwrite the definition (assumed here to have been done earlier) of an active?, but the result is that the inner? can not be used in \label or \ref. So testing for active characters should be done always... I leave as is.

1.3i 2016/01/06 removes a spurious end of line space in \mst@mathactivate (did not show as anyhow done in math mode).

\mst@do@az \mst@addtodo@az \mst@addtodo@AZ \mst@the

- 1.2b 2012/12/28 now that we understand the great advantages of "8000 we do it also for all letters a-z and A-Z to insert automatically the italic corrections. See the discussion in the user manual. Ironically I wrote the code initially for the italic option only to realize later it was more suitable to using an *upright* text font in math mode! So this mathematical activation of the letters is not done if the font shape is detected to be it or sl; to bypass this the command \MTicinmath is provided.
- 1.2e 2013/01/10 corrects a bad oversight of 1.2b in \mst@mathactivate which made the reproduction of the user manual illustrations with \$f_i^i\$ impossible. As \mst@mathactivate was originally used also to get the non-letters obey math alphabet while maintaining the TeX spacings, it added no extra braces. The braces should however be added for expansion of math active letters, in order of things like x^y to work as expected. (the group braces do not prevent ligatures when the letters are arguments to the math alphabet commands, the added macros \mst@tetcorr and \mst@before<letter> expanding to nothing).

Added note 2016/01/06: it should be explicitly said that the extra {..} in \mst@mathactivate for letters end up creating \hbox'es around each letter with its extra skips and explicit italic correction, when present. These skips are thus set at natural width and do not add any break point.

\MTmathactiveletters \MTmathstandardletters 1.3 2013/09/02 extends the use of mathematically active letters to allow the user to specify muglue before and after the letter itself (see \MTsetmathskips, below). Mathematically active letters were previously used only to add the italic correction; the math activation has now been separated and put in \MTmathactiveletters. There is also \MTmathactiveLetters to allow math activation only for the uppercase letters. To cancel the (now default, even with option italic) math activation of letters, there is \MTmathstandardletters. Version 1.3a removes some silly \string's from the code, which prevented to pass macros as first argument to the command.

\MTnonlettersobeymathxx
\MTnonlettersdonotobeymathxx
\resetMathstrut@

These macros are modified in version 1.3a 2013/09/04 in order to cleverly adjust, or not, the amsmath \resetMathstrut@. When used in the preamble, they just modify \mst@the. And there is code at begin document to check the status there of \mst@the and if its meaning is \the, then \MTnonlettersobeymathxx is activated again to do the patch. When used in the body they adjust \resetMathstrut@.

Notice that the saved meaning is the one at begin document (thus, possibly patched by lualatex-math — not anymore since 1.5 of March 2016, as amsmath.sty now maintained by LaTeX team has modified \resetMathStrut@ to make it compatible to Unicode engines) but modifications done after that would not be seen in \mst@savedresetMathstrut@.

The new version of \resetMathStrut@ from LaTeX team release 2016/03/03 v2.15a of amsmath.sty is still not compatible with a math active opening parenthesis. Hence my patch here is still needed.

- 244 \newtoks\mst@do@nonletters
- 245 \newtoks\mst@do@easynonletters
- 246 \newtoks\mst@do@az
- 247 \newtoks\mst@do@AZ
- 248 \let\mst@the\@gobble

```
249 \newcommand*\MTnonlettersdonotobeymathxx{%
250
       \ifx\mst@the\@gobble
251
       \else
         \@ifundefined{mst@savedresetMathstrut@}{}{%
252
           \PackageInfo{mathastext}{restoring (for this group or environment) ams
   math \string\resetMathstrut@}%
         \let\resetMathstrut@\mst@savedresetMathstrut@}%
254
255
       \let\mst@the\@gobble
256
257 }
258 \newcommand*\MTnonlettersobeymathxx{%
       \ifx\mst@the\the
       \else
260
         \@ifundefined{mst@savedresetMathstrut@}{}{\%
261
262
           \ifmst@symboldelimiters
263
             \def\resetMathstrut@{%
              \setbox\z@\hbox{\the\textfont\symmtpsymbol\char40
264
                            \the\textfont\symmtoperatorfont\char40
265
                            \the\textfont\symoperators\char40}%
266
267
              \ht\Mathstrutbox@\ht\z@ \dp\Mathstrutbox@\dp\z@}%
268
           \else
             \def\resetMathstrut@{%
269
              \setbox\z@\hbox{\the\textfont\symmtoperatorfont\char40
270
                            \the\textfont\symoperators\char40}%
271
               \ht\Mathstrutbox@\ht\z@ \dp\Mathstrutbox@\dp\z@}%
272
273
           \fi
         \PackageInfo{mathastext}{\string\resetMathstrut@\space
274
275
         from amsmath replaced (for this group or environment)}}%
276
       \let\mst@the\the
277
278 }
279 \newcommand*\MTeasynonlettersdonotobeymathxx{\let\mst@theeasy\@gobble}
280 \newcommand*\MTeasynonlettersobeymathxx{\let\mst@theeasy\the}
281 \MTeasynonlettersobeymathxx
282 \newcommand*\MTmathactiveletters{\let\mst@thef\the \let\mst@theF\the}
283 \ifmst@subdued\else\MTmathactiveletters\fi
284 \newcommand*\MTmathactiveLetters{\let\mst@theF\the}
285 \newcommand*\MTmathstandardletters{\let\mst@thef\@gobble \let\mst@theF\@gobble}
```

\MTicinmath \MTICinmath \MTicalsoinmathxx

\MTnoicinmath can also be used from inside math mode.

\MTicalsoinmathxx is destined to be used inside \mathnormalbold as I didn't want to add \MTnoicinmath the complication of extracting the family number used inside \mathnormalbold (will perhaps come back if I have time to spend on source2e). Added note 2016/01/06: this number is a priori simply symmtletterfont+1.

> \MTicinmath can also be used inside math mode, to revert an earlier \MTnoicinmath from inside the same math group: the math mode had to be entered with the math activation of letters allowed.

1.3i 2016/01/06: For some reason which I have now forgotten I did until now:

% \def\mst@itcorr{\ifnum\fam=\m@ne\/\else\ifnum\fam=\symmtletterfont\/\fi\fi}%

%

hence italic corrections were also applied inside \mathnormal (for upright fonts; \mathnormal bold math alphabet was not treated like \mathnormal). I now drop this to be more in sync with the handling of the extra skips around letters. Everything gets suppressed inside all math alphabets, allowing ligatures, even for \mathnormal.

```
286 \newcommand*\MTicinmath{%
       \MTmathactiveletters
288
       \def\mst@itcorr{\ifnum\fam=\m@ne\/\fi}%
       \let\mst@ITcorr\mst@itcorr}
289
290 \newcommand*\MTICinmath{%
       \MTmathactiveLetters
291
       \def\mst@ITcorr{\ifnum\fam=\m@ne\/\fi}}
292
293 \newcommand*\MTnoicinmath{\let\mst@itcorr\@empty\let\mst@ITcorr\@empty}
294 \newcommand*\MTnoICinmath{\let\mst@ITcorr\@empty}
295 \newcommand*\MTicalsoinmathxx{%
       \ifx\mst@itcorr\@empty\else\def\mst@itcorr{\/}\fi
296
       \ifx\mst@ITcorr\@empty\else\def\mst@ITcorr{\/}\fi}
297
298 \AtEndOfPackage{\AtBeginDocument{%
299
     \everymath\expandafter{\the\everymath}
       \mst@the\mst@do@nonletters \let\mst@the\@gobble
300
       \mst@theeasy\mst@do@easynonletters \let\mst@theeasy\@gobble
301
       \mst@thef\mst@do@az \let\mst@thef\@gobble
302
       \mst@theF\mst@do@AZ \let\mst@theF\@gobble}%
303
     \everydisplay\expandafter{\the\everydisplay
304
305
       \mst@the\mst@do@nonletters \let\mst@the\@gobble
       \mst@theeasy\mst@do@easynonletters \let\mst@theeasy\@gobble
306
307
       \mst@thef\mst@do@az \let\mst@thef\@gobble
308
       \mst@theF\mst@do@AZ \let\mst@theF\@gobble}%
```

- 1.3j: moved here to be executed at begin document (and not from inside \Mathastext@.) The \MTeverymathoff does: \MTnormalasterisk, \MTnormalprime, \MTnonlettersdonotobey mathxx, \MTeasynonlettersdonotobeymathxx, \MTmathstandardletters.
- 1.3m: doing \MTmathactiveletters in subdued mode immediately after \begin{document} resulted in errors because \mst@itcorr had been left undefined. We thus add \MTnoicinmath to the subdued initialization.
- Since 1.3n there is \MTresetnewmcodes which needs \mst@originalnewmcodes@, itself defined at begin document. Thus we have wrapped the whole thing in \AtEndOfPackage.

And 1.3p adds here \MTcustomizenewmcodes which had been regrettably forgotten by 1.3n.

```
309 \MTcustomizenewmcodes
310 \ifmst@subdued
311 \MTeverymathoff
312 \MTresetnewmcodes
313 \MTnoicinmath
314 \MTmathoperatorsdonotobeymathxx
```

1.3j: an earlier version of this code was earlier part of \Mathastext@. As we are now in \At BeginDocument we try to be careful not to overwrite \MTicinmath, \MTnoicinmath, \MTical soinmathxx, ... if issued by the user in the preamble, though. And we do not execute \MTmath

activeletters, it is issued by the package at loading time in order to allow user to cancel it if desired from inside the preamble.

```
316
        \ifx\mst@itcorr\@undefined
            \def\mst@itcorr{\ifnum\fam=\m@ne\/\fi}%
317
            \@for\mst@tmp:=it,sl\do
318
319
               {\ifx\mst@tmp\mst@ltshape@normal\let\mst@itcorr\@empty\fi }%
        \fi
320
321
        \ifx\mst@ITcorr\@undefined
             \let\mst@ITcorr\mst@itcorr
322
             \ifmst@frenchmath
323
               \def\mst@ITcorr{\ifnum\fam=\m@ne\/\fi}%
324
325
               \@for\mst@tmp:=it,sl\do
326
                    {\ifx\mst@tmp\mst@shape@normal\let\mst@ITcorr\@empty\fi }%
327
             \fi
        \fi
328
329
     \fi
330 }}
```

\MTsetmathskips \MTunsetmathskips 1.3 2013/09/02: user level command to specify extra spaces in math mode around the letters (only the 7bit a,b,..,z and A,B,..,Z). First parameter is the letter, second is the math skip to be inserted before, and third the skip to be inserted after; for example \thickmuskip or explicitely 0.1mu.

For this, letters are made mathematically active. This is now the package default (version 1.2 did this only in the absence of option italic, or more precisely when the font used was not of shape it or s1). But if \MTsetmathskips has not been used for that letter, the only effect of the math activation is, as in 1.2, to add the italic correction automatically, except when the font shape is detected to be it or s1; in these latter cases, although mathematically active, the letter acts in the standard way.

The command \MTmathstandardletters turns off math activation and its effects for all letters. Ligatures within the argument of a math alphabet command are impeached by skips; so \MTunsetmathskips is provided to cancel the skips for one specific letter (f for example).

- 1.3a 2013/09/04: I strangely had \string#1 inside \MTsetmathskips. Phobic of catcode active letters... but with \string one needs some \expandafter to use \MTsetmathskips in an \@for loop for example. It is better to allow the first argument to be a macro or anything expanding to a letter, and to not be paranoid about improbable catcode active letters (the user just has to tame them at the time of the \MTsetmathskip) so I take out these \string's.
- 1.3i 2016/01/06: the extra skips are suppressed for the arguments of math alphabet commands. This applies in particular for amsmath's \DeclareMathOperator.

```
331 \newcommand*\MTsetmathskips[3] {%
332     \@namedef{mst@before#1}{\ifnum\fam=\m@ne\mskip#2\relax\fi }%
333     \@namedef{mst@after#1}{\ifnum\fam=\m@ne\mskip#3\relax\fi }%
334 }
335 \newcommand*\MTunsetmathskips[1] {%
336     \@namedef{mst@before#1}{}%
337     \@namedef{mst@after#1}{}%
338 }
```

\mst@mathactivate @addtodo@nonletters codo@easynonletters \mst@addtodo@az \mst@addtodo@AZ Added note 2016/01/06: Notice that the initially \relax tokens \mst@[before|after]@<letter> formed with \csname...\endcsname do not modify TeX's math layout: {\relax f\relax} is

```
like f (also for ligatures inside \mathrm for example).
339 \def\mst@magic@v #1#2#3#4#5{#1#3#4}
340 \def\mst@magic@vi #1#2#3#4#5#6{#1#2#4#5}
341 \def\mst@fork{\ifmmode\mst@magic@v\fi\@thirdofthree}
342 \def\mst@safefork{\ifmmode\if@safe@actives\else\mst@magic@vi\fi\fi\@thirdofthree}
343 \def\mst@do@activecase#1#2#3{% #1 is a category 11 or 12 character token
       \@ifundefined{active@char#1}{}{%
344
345
            \ifcat #1a\mathcode'#1=#2\else
            \ifx\relax #2\relax\mathcode'#1='#1 \else\mathcode'#1=#3\fi\fi
346
       \expandafter\expandafter\expandafter\let\expandafter\expandafter
347
                       \csname mst@orig@user@active#1\endcsname
348
349
                       \csname user@active#1\endcsname
350
       \expandafter\expandafter\expandafter\let\expandafter\expandafter
                       \csname mst@orig@normal@char#1\endcsname
351
                       \csname normal@char#1\endcsname
352
       \ifcat #1a%
353
354
         \expandafter\edef\csname user@active#1\endcsname
                       {\noexpand\mst@fork {{#2\noexpand#3}}{}\expandafter
355
                        \noexpand\csname mst@orig@user@active#1\endcsname
356
                       }%
357
358
         \expandafter\edef\csname normal@char#1\endcsname
                       {\noexpand\mst@safefork {{#2\noexpand#3}}{}\expandafter
359
360
                        \noexpand\csname mst@orig@normal@char#1\endcsname
                       }%
361
362
       \else
         \expandafter\edef\csname user@active#1\endcsname
363
364
                       {\noexpand\mst@fork {#2}\noexpand#3\expandafter
                        \noexpand\csname mst@orig@user@active#1\endcsname
365
                       }%
366
         \expandafter\edef\csname normal@char#1\endcsname
367
368
                       {\noexpand\mst@safefork {#2}\noexpand#3\expandafter
369
                        \noexpand\csname mst@orig@normal@char#1\endcsname
370
                       }%
       fi}
371
372 \begingroup
     \catcode'\~=\active
373
374
     \def\x{\endgroup
       \def\mst@mathactivate##1##2##3{% ##1 guaranteed of cat 11 or 12
375
376
         \begingroup
         \lccode'~='##1
377
         \lccode'##1='##1
378
379
         \lowercase{\endgroup
             \ifnum\catcode'##1=\active
380
381
               \mst@do@activecase ##1{##2}##3%
               \% careful as ##2 is empty in the asterisk and
382
               % prime case!
383
             \else
384
                \mathcode'##1="8000
385
               % version 1.3 adds the possibility of extra skips around letters,
386
```

```
% (only if non catcode active at the time of use).
387
388
               \ifcat##1a\edef~{% extra braces for a^b for example
                   {\expandafter\noexpand\csname mst@before##1\endcsname
389
390
                    ##2\noexpand##3%
391
                    \expandafter\noexpand\csname mst@after##1\endcsname}}%
               \else\def~{##2##3}\fi
392
             \fi}}}
393
394\x
395 \def\mst@addtodo@nonletters#1#2#3{%
     % #1 will be of cat 11 or 12.
     % #2 is empty for asterisk and right quote
397
     \mst@do@nonletters\expandafter
398
         {\the\mst@do@nonletters \mst@mathactivate#1{#2}#3}%
399
400 }
401 \def\mst@addtodo@easynonletters#1#2{% #1 is a one char control sequence
     \mst@do@easynonletters\expandafter{\the\mst@do@easynonletters\mathcode'#1=#2}%
403 }
404 \def\mst@addtodo@az#1#2{%
     \mst@do@az\expandafter{\the\mst@do@az\mst@mathactivate#1#2\mst@itcorr}
405
406 }
407 \def\mst@addtodo@AZ#1#2{%
     \mst@do@AZ\expandafter{\the\mst@do@AZ\mst@mathactivate#1#2\mst@ITcorr}%
408
409 }
```

\newmcodes@ \mst@newmcodes@ \MTresetnewmcodes Ccustomizenewmcodes

- 1.15d: the \newmcodes@ amsmath macro causes an error in Unicode engines as soon someone assigns a Unicode mathcode to the minus sign, and then makes a \DeclareMathOperator declaration. Furthermore it hard-codes the font family 0 as being the one to be used. Moreover just putting the concerned signs \neg , :, ., \,', * inside braces emulates enough the behavior (although the tick will give a prime).
 - 1.3: now tests if 'basic' option was used.
- 1.3d: I should re-examine the situation with \newmcodes@. In the meantime its relaxification will not be done if lualatex-math is loaded. And the whole thing is put at begin document.
- 1.3m: lualatex-math 1.5 n'a pas modifié son traitement de \newmcodes@ mais par contre a supprimé le patch de \resetMathstrut@. Mais la date de release est restée à 2015/09/22 (date de 1.4a) au lieu de quelque chose comme 2016/03/13 (date pour l'annonce sur CTAN). Il faudra suivre l'évolution future de amsmath.sty maintenant assurée par D.C.
- 1.3n 2016/04/22: there is no more a patch of \newmcodes@ by lualatex-math 1.6 (2016/04/16), as amsmath 2016/03/10 v2.15b has now a version compatible with LualATeX.

My very radical \let\newmcodes@\relax was only a temporary measure I adopted for lack of time on October 13, 2012, and apart from avoiding to do that in case lualatex-math was detected, I never came back... finally I handle it myself for 1.3n. The remaining problem of this macro (now that it does not anymore crash lualatex or vice versa) is that (also with amsmath version 2016/03/10 v2.15b) it hardcodes the font used. The aim of the macro is to modify the type of spacing affected to symbols ', *, ., -, /, :, in case they are used in operator names.

- As I don't want to monopolize a count register only for computations, let's just be mean if ε -TFX not there.
- mathastext makes (or not, depending on commands issued by the user) these characters math active (the right tick already is), which complicates recovery of former mathcode.

We have mathchar type *macros*, but then the complication is in diverging behaviours of the engines: \numexpr\mst@varfam@minus\relax works with LuaTFX, not with X¬TFX.

- the * must presumably really be the non-lowered text glyph.
- for the I hesitated but do use the hyphen in the end.
- seems I simply don't understand what the amsmath code does with \std@minus. It is used in \relbar and it escapes me why \newmcodes@ would ever want to redefine it, and more importantly why on earth it tests the mathcode of for that? yes, \std@minus is defined (at begin document) using the mathcode of -, but what's the connexion to \newmcodes@?? Any way mathastext defines \relbar with \mst@minus@sign. Thus I just drop this conditional.
- things are complicated by the options such as nominus, noparenthesis.
- the \newmcodes@ macro is anyhow assuming that if a new math font is used it occupies math groups 0 and 1!! very bad; fixing it in passing if the character has not been handled by mathastext could be envisioned, but that's not mathastext's job.
- years go by, and I remain as baffled as ever about the story of "more than 16 math families". I will not test again, but I am pretty sure that \DeclareMathSymbol does not work with more than 16 families, thus when I try to be a good boy and use \Umathcode syntax with symmtoperatorfont I am perhaps doing unnecessary efforts.
- I noticed that LualATEX does not apply the "TeX Ligature" (bad name) regarding the right tick APOSTROPHE being transformed into RIGHT SINGLE QUOTATION MARK in math mode, but XALATEX does. From the point of view of mathastext, the behaviour of XALATEX is the coherent one. It appears that LualATEX use in math mode of a text font does not obey set features, like this http://tex.stackexchange.com/questions/208688/oldstylefigure-issue-with-lualatex-and-mathastext perhaps illustrates. I opened a ticket at https://github.com/wspr/fontspec/issues/238, but as usual it is hard to figure out the best place where to report font matters.
- I make some effort not to require \numexpr in legacy engine... wipet should be happy if he ever reads these lines. Well no, too much pain as there is no immediate way to get hexadecimal digit. And wipet will not read this as this is a LATEX package, and I don't see why I should bother making wipet happy.
- Some hesitation about what to do under option symboldelimiters. I temporarily used \symmtpsymbol, except for the right quote and for the hyphen, but finally I drop that and use \symmtoperatorfont always. (after testing how it looked like).

All in all this is a great deal of trouble and I understand I postponed back in 2012! I spent some hours on this small thing, with consequent testing and for example this TeX Ligature issue with Unicode engines.

```
410 \ifmst@basic\else
411 \ifx\numexpr\undefined
```

412 \else

413 \ifmst@XeOrLua

414 \AtBeginDocument {%

415 \ifx\newmcodes@\@undefined\else

416 \edef\mst@newmcodes@{%

417 \mst@Umathcode '\noexpand\' 0 \symmtoperatorfont 39\relax

```
418
      \ifmst@asterisk
       419
      \else\mathcode'\noexpand\* 42
420
421
422
      \ifmst@nopunct\mathcode '\noexpand\."613A \mathcode '\noexpand\: "603A
423
      \else
      \mst@Umathcode '\noexpand\. 6 \symmtoperatorfont 46\relax
424
      \mst@Umathcode '\noexpand\: 6 \symmtoperatorfont 58\relax
425
426
427
      \ifmst@nominus\mathcode'\noexpand\- 45
      \else
428
         \mst@Umathcode '\noexpand\- 0 \symmtoperatorfont 45\relax
429
430
      \ifmst@noparen\mathcode '\noexpand\/ 47
431
432
433
         \mst@Umathcode '\noexpand\/ 0 \symmtoperatorfont 47\relax
     \fi
434
435
     }%
     \let\mst@originalnewmcodes@\newmcodes@
436
437
     \fi
438
     \else
439
     \AtBeginDocument {%
440
     \ifx\newmcodes@\@undefined\else
441
442
     \edef\mst@newmcodes@{%
443
       \mathcode'\noexpand\', \the\numexpr\symmtoperatorfont*\@cclvi+39\relax
       \mathcode'\noexpand\*
444
         \the\numexpr\ifmst@asterisk\symmtoperatorfont*\@cclvi\fi+42\relax
445
446
       \ifmst@nopunct\mathcode '\noexpand\."613A \mathcode '\noexpand\: "603A
       \else
447
448
         \mathcode'\noexpand\. \the\numexpr\mst@varfam@dot-"1000\relax
449
         \mathcode'\noexpand\: \the\numexpr\mst@varfam@colon-"1000\relax
450
       \fi
       \mathcode'\noexpand\-
451
        \the\numexpr\unless\ifmst@nominus\symmtoperatorfont*\@cclvi\fi+45\relax
452
453
       \mathcode'\noexpand\/
454
       \the\numexpr\unless\ifmst@noparen\symmtoperatorfont*\@cclvi\fi+47\relax\relax
455
     \let\mst@originalnewmcodes@\newmcodes@
456
457
     \fi
     }
458
    \fi
459
460 \fi\fi
461 \newcommand*\MTresetnewmcodes{\ifx\mst@originalnewmcodes@\undefined\else
                                  \let\newmcodes@\mst@originalnewmcodes@\fi}
463 \newcommand*\MTcustomizenewmcodes{\ifx\mst@originalnewmcodes@\undefined\else
                                  \let\newmcodes@\mst@newmcodes@\fi}
```

subdued 1.15: The subdued code was initiated in May 2011. I returned to mathastext on Sep 24, 2012,

and decided to complete what I had started then, but in the mean time I had forgotten almost all of the little I knew about LATEX macro programming.

The point was to extract the data about how are 'letters' and 'operators' in the normal and bold versions, through obtaining the math families of 'a' and '1', respectively¹. Due to the reassignements done for characters by mathastext I also had decided in 2011 that the OT1 encoding, if detected, should be replaced by T1 ((1): but the *euler* package for example assigns the digits to the *letters* symbol font...)

1.15d: Oct 13, 2012. The \mathcode thing has to be used with care under Unicode engines. Unfortunately the \luatexUmathcode macro is helpless as it is not possible to know if it will return a legacy mathcode or a Unicode mathcode. On the other hand the much saner \XeTeX mathcodenum always return a Unicode mathcode.

UPDATE for mathastext 1.3 (2013/09/02): since the release of lualatex as included in TL2013, \luatexUmathcodenum behaves as \XeTeXmathcodenum so mathastext 1.3 treats identically under both unicode engines the equal and minus signs (and the vertical bar).

- 1.15e: Oct 22, 2012. I add the necessary things to also subdue the \mathbf, \mathit, \mathsf and \mathtt macros (previous version only took care of the symbol alphabets \mathnormal and \mathrm.) [update: 1.15f does that in a completely different and much simpler way] Notice that the package defines a \mathnormalbold macro, but it will not be subdued in the normal and bold math versions.
- 1.15f: and also I take this opportunity to do the subdued math alphabets things in a much much easier way, see below.

```
465 \ifmst@subdued
    \def\mst@reserved#1\getanddefine@fonts\symletters#2#3\@nil{%
466
          \def\mst@normalmv@letter{#2}}
467
    \expandafter\mst@reserved\mv@normal\@nil
468
    469
          \def\mst@boldmv@letter{#2}}
470
    \expandafter\mst@reserved\mv@bold\@nil
471
472
    \def\mst@reserved#1\getanddefine@fonts\symoperators#2#3\@nil{%
          \def\mst@normalmv@operator{#2}}
473
474
    \expandafter\mst@reserved\mv@normal\@nil
    \def\mst@reserved#1\getanddefine@fonts\symoperators#2#3\@nil{%
475
476
          \def\mst@boldmv@operator{#2}}
    \expandafter\mst@reserved\mv@bold\@nil
477
478 %%
    \edef\mst@tmp{\encodingdefault}
479
480
    \def\mst@reserved#1/#2/#3/#4/{\gdef\mst@debut{#1}\gdef\mst@reste{#2/#3/#4}}
    \begingroup\escapechar\m@ne
481
```

```
\xdef\mst@funnyoti{\expandafter\string\csname OT1\endcsname}
482
483
         \expandafter\expandafter\expandafter
             \mst@reserved\expandafter\string\mst@normalmv@operator/
484
485
     \endgroup
486
     \ifx\mst@debut\mst@funnyoti\ifx\mst@tmp\mst@oti\def\mst@tmp{T1}\fi\fi
     \edef\mst@normalmv@operator{\expandafter\noexpand\csname
487
                                   \mst@tmp/\mst@reste\endcsname}
488
489
     \begingroup\escapechar\m@ne
         \expandafter\expandafter\expandafter
490
491
             \mst@reserved\expandafter\string\mst@boldmv@operator/
     \endgroup
492
     \ifx\mst@debut\mst@funnyoti\ifx\mst@tmp\mst@oti\def\mst@tmp{T1}\fi\fi
493
     \edef\mst@boldmv@operator{\expandafter\noexpand\csname
494
                                 \mst@tmp/\mst@reste\endcsname}
495
496
     \AtEndOfPackage{
497
     \typeout{** ...entering subdued mode...}
     \expandafter\SetSymbolFont@\expandafter\mv@normal\mst@normalmv@letter\symmtletterfont
498
     \expandafter\SetSymbolFont@ \expandafter\mv@bold\mst@boldmv@letter\symmtletterfont
499
     \expandafter\SetSymbolFont@\expandafter\mv@normal\mst@normalmv@operator\symmtoperatorfon
500
501
     \expandafter\SetSymbolFont@\expandafter\mv@bold\mst@boldmv@operator\symmtoperatorfont
502
     \typeout{** ...done.}
503
504 \fi % fin de ce \ifmst@subdued
In the short-lived 1.15e I was doing the following for alphabets:
\def\mst@reservedc#1#2#3#4{\def\mst@normalmv@mathbf{#4#3}}
\def\mst@reserveda#1{%
\def\mst@reservedb##1\install@mathalphabet#1##2##3\@nil{\mst@reservedc##2}%
\expandafter\mst@reservedb\mv@normal\@nil}
\expandafter\mst@reserveda\csname mathbf\space\endcsname
and later in the code:
\expandafter\expandafter\expandafter\SetMathAlphabet@
\expandafter\expandafter\mv@normal
\expandafter\mst@normalmv@mathbf\csname Mathbf\space \endcsname\Mathbf
It does work! but \let\mst@original@bf\mathbf is so much simpler. And also safer, because
\mathbf could have been redefined using \DeclareSymbolFontAlphabet... (I could have provided
the necessary check to the already bloated code...)
```

mtoperatorfont

Declaration of the current default font as our math font. The characteristics of the used font can be changed by a user call to the macros \Mathastext or \Mathastextwilluse, which will be defined next. We will also make one internal call to \Mathastext to set up the normal and bold math versions, so we will also employ \SetSymbolFont later.

505 \DeclareSymbolFont{mtoperatorfont}{\mst@enc}{\mst@fam}{\mst@ser}{\mst@opsh}

\operator@font

We modify this LATEX internal variable in order for the predefined \cos, \sin, etc... to be typeset with the mathastext font. This will also work for things declared through the amsmath package command \DeclareMathOperator. The alternative would have been to redefine the 'operators' Math Symbol Font. Obviously people who expect that \operator@font will always refer to the 'operators' math font might be in for a surprise... well, we'll see.

\MTmathoperatorsobeymathxx

1.2: rather than just replacing \symoperators by \symmtoperatorfont I add a modification which makes the declared operator names sensitive to the math alphabets... ouh le vilain!

\MTmathoperators-

506 \newcommand*{\MTmathoperatorsobeymathxx}

donot-

 $507 {\ensuremath{\verb|coup|ifnum|fam=\m@ne|symmtoperatorfont|else|fam|fi|}}$

obeymathxx 508 \newcommand*{\MTmathoperatorsdonotobeymathxx}

509 {\def\operator@font{\mathgroup\symmtoperatorfont}}

510 \MTmathoperatorsobeymathxx

mtletterfont

In version 1.1, we add the possibility to mimick the standard behavior, that is to have italic letters and upright digits. Thanks to Tariq Perwez and Kevin Klement who asked for such a feature.

 $\label{lem:cont} $$11 \encorement {\mst@enc}{\mst@fam}_{\mst@ser}_{\mst@tsh}$$$

\MTfixmathfonts

There is a long-standing issue https://github.com/lualatex/luaotfload/issues/204 on LualaTeX not applying OpenType features in math mode (this impacts \url macro too, as it uses math mode.) LuaTeX has two modes for handling of OpenType fonts, the default in text being to use the node mode, and this mode is non-working in math, thus mathastext needs to force use of base mode. Else one sees old style figures where one does not expect them, or the opposite, depending on the default font feature, see for example https://tex.stackexchange.com/questions/208688/oldstylefigure-issue-with-lualatex-and-mathastext/277628.

Once we know the cause, the fix is relatively easy. I will go for the $\operatorname{\tt \ensuremath}$ way, because I don't want to dwelve at all with the details of LATEX's handling of math fonts, of size changes, of math versions etc... perhaps in the future LATEX will fix the issue upstream by modifying $\operatorname{\tt \ensuremath}$ will be unneeded. Naturally, here we care only about the two maths fonts used by mathastext: mtoperatorfont and mtletterfont.

For the \url situation, I have posted a patch at: http://tex.stackexchange.com/questions/264206/cant-get-oldstyle-figures-in-url-with-lualatex.

Not all is resolved, as I comment at http://github.com/lualatex/luaotfload/issues/204#issuecomment-216465680 that with TeX Gyre Termes for example I can not get simultaneously Old Style and Tabular Figures to work in math mode, although the font name as constructed by my patch (which is like the code below, only simpler as we only have to consider \textfont0) is the correct one. Similarly with Vollkorn: I can then not get the two features lnum and tnum to work simultaneously when specified with mode=base. It does work with mode=node but this mode "does not work in math mode."

Done for 1.3o of 2016/05/03.

1.3p renames the macro to \MTfixmathfonts for public access.

```
512 \begingroup
```

513 \catcode'N 12

514 \catcode'O 12

515 \catcode'D 12

516 \catcode'E 12

517 \lowercase{\gdef\mst@fixmathfonts@ #1=NODE;#2#3\relax #4\@empty #5}%

518 {\ifx#2\empty\else\font\mst@mathfont=#1=base;#2#3\relax#5=\mst@mathfont\fi}

519 \lowercase{\gdef\MTfixmathfonts

520 {\expandafter\mst@fixmathfonts@

 $\verb| fontname\textfont\symmtoperatorfont\relax=NODE;\empty\relax\@empty| \\$

522 {\textfont\symmtoperatorfont}%

```
{\scriptfont\symmtoperatorfont}%
                 525
                 526 \expandafter\mst@fixmathfonts@
                 527
                      \fontname\scriptscriptfont\symmtoperatorfont\relax\relax=NODE;\empty\relax\@empty
                       {\scriptscriptfont\symmtoperatorfont}%
                 528
                 529 \expandafter\mst@fixmathfonts@
                      \fontname\textfont\symmtletterfont\relax\relax=NODE;\empty\relax\@empty
                 530
                       {\textfont\symmtletterfont}%
                 531
                 532 \expandafter\mst@fixmathfonts@
                      \fontname\scriptfont\symmtletterfont\relax\relax=NODE;\empty\relax\@empty
                 533
                       {\scriptfont\symmtletterfont}%
                 534
                     \expandafter\mst@fixmathfonts@
                 535
                      \fontname\scriptscriptfont\symmtletterfont\relax\relax=NODE;\empty\relax\@empty
                 536
                 537
                       {\scriptscriptfont\symmtletterfont}%
                 538
                      }%
                 539 }%
                 540 \endgroup
                 541 \ifmst@LuaTeX
                      \everymath\expandafter{\the\everymath\mst@fixmathfonts}%
                      \everydisplay\expandafter{\the\everydisplay\mst@fixmathfonts}%
                 544 \fi
                 545 \newcommand*\MTfixfonts{\let\mst@fixmathfonts\MTfixmathfonts}%
                 546 \newcommand*\MTdonotfixfonts{\let\mst@fixmathfonts\empty}%
                 547 \MTfixfonts
    \Mathnormal We redefine the default normal, rm, bf, it, sf, and tt alphabets, but this will be done via
        \Mathrm
                 \renewcommand{\mathrm}{\Mathrm} etc...and (1.15f) the previous status of the math alpha-
        \Mathbf bets is recorded for the sake of the subdued option.
        \Mathit
                    We follow the standard LATEX behavior for \mathbf, which is to pick up the bold series of the
        \Mathsf roman font (digits and operator names).
                    We will access (if no option is passed for Greek) the \omicron via \mathnormal. But un-
        \Mathtt
\mathnormalbold fortunately the fourier package with the upright option does not have an upright omicron
                 obtainable by simply typing \mathnormal{0}. So if fourier is loaded we use \mathrm and not
                  \mathnormal.
                 548 \let\mst@alph@omicron\mathnormal
                 549 \@ifpackageloaded{fourier}{\ifsloped\else\let\mst@alph@omicron\mathrm\fi}{}
                 550 \DeclareSymbolFontAlphabet{\Mathnormal}{mtletterfont}
                 551 \DeclareSymbolFontAlphabet{\Mathrm}{mtoperatorfont}
                 552 \ifmst@nonormalbold\else
                       \DeclareMathAlphabet{\mathnormalbold}{\mst@enc}{\mst@fam}{\mst@bold}{\mst@ltsh}
                 553
                 554\fi
                 555 \ifmst@defaultbf\else
                       \DeclareMathAlphabet{\Mathbf}{\mst@enc}{\mst@fam}{\mst@bold}{\mst@opsh}
                 556
                 557\fi
                 558 \ifmst@defaultit\else
                       \DeclareMathAlphabet{\Mathit}{\mst@enc}{\mst@fam}{\mst@ser}{\itdefault}
                 560 \fi
                 561 \ifmst@defaultsf\else
```

\fontname\scriptfont\symmtoperatorfont\relax\relax=NODE;\empty\relax\@empty

523 \expandafter\mst@fixmathfonts@

524

```
\DeclareMathAlphabet{\Mathsf}{\mst@enc}{\sfdefault}{\mst@ser}{\mst@opsh}
562
563\fi
564 \ifmst@defaulttt\else
      \DeclareMathAlphabet{\Mathtt}{\mst@enc}{\ttdefault}{\mst@ser}{\mst@opsh}
566 \fi
567 \let\mst@original@normal\mathnormal
568 \let\mst@original@rm\mathrm
569 \let\mst@original@bf\mathbf
570 \let\mst@original@it\mathit
571 \let\mst@original@sf\mathsf
572 \let\mst@original@tt\mathtt
573 \def\mst@restorealphabets{% for subdued
574
       \let\mathnormal\mst@original@normal
575
       \let\mathrm\mst@original@rm
576
       \let\mathbf\mst@original@bf
577
       \let\mathit\mst@original@it
       \let\mathsf\mst@original@sf
578
       \let\mathtt\mst@original@tt}
579
580 \def\mst@setalphabets{%
       \ifmst@defaultnormal\else\renewcommand{\mathnormal}{\Mathnormal}\fi
582
       \ifmst@defaultrm\else\renewcommand{\mathrm}{\Mathrm}\fi
       \ifmst@defaultbf\else\renewcommand{\mathbf}{\Mathbf}\fi
583
       \ifmst@defaultit\else\renewcommand{\mathit}{\Mathit}\fi
584
585
       \ifmst@defaultsf\else\renewcommand{\mathsf}{\Mathsf}\fi
       \ifmst@defaulttt\else\renewcommand{\mathtt}{\Mathtt}\fi}
586
587 \ifmst@subdued\else\mst@setalphabets\fi
```

LGRgreek selfGreek mtlgrfontupper mtlgrfontlower mtselfGreekfont 1.14b: We can not move the \DeclareSymbolFont to the \Mathastext macro because it resets the font family in *all* math versions, and some could have been defined by the user with previous calls to \Mathastext. So we have to have them here. The problem is that at this stage it is impossible to know if we really need (in the case of LGRgreek) two separate shapes for upper and lowercase, and (in the case of selfGreek) a shape distinct from the one used in mtoperatorfont. So I opted in the end for declaring possibly one too many font. To achieve more economy the only way would be to keep cumulative track of all previously declared math versions and to redeclare appropriately the LGR or self greek fonts at each call to \Mathastext (with no optional argument): a bit painful, and as I am possibly the sole user in the world of this possibility of multiple math versions with this package. Also the advantage to systematically allocate a font for the selfGreek option is that we can force the use of the OT1 encoding.

First we establish the cumulative effect of the greek related options.

1.15c introduces some possibilities to change the shapes of Greek letters in each math versions, and even the Greek font (in LGR encoding). The commands \MTitgreek etc... will be used in-between calls to \Mathastext and re-adjust the shapes. And the command \MTgreekfont changes the Greek font family.

```
588 \def\mst@update@greeksh{
589 \def\mst@greek@lsh{\mst@ltsh} %% default behavior
590 \def\mst@greek@ush{\mst@opsh}
591 \ifmst@itgreek\def\mst@greek@lsh{\itdefault}
592 \def\mst@greek@ush{\itdefault}\fi
593 \ifmst@upgreek\def\mst@greek@lsh{\updefault}
```

```
594
                          \def\mst@greek@ush{\updefault}\fi
595
       \ifmst@frenchmath
         \ifmst@itgreek\else
596
597
         \ifmst@upgreek\else
598
            \def\mst@greek@lsh{\mst@opsh}
            \def\mst@greek@ush{\mst@opsh}
599
         \fi\fi
600
       \fi
601
       \ifcase\mst@greek@select
602
603
            \or\def\mst@greek@ush{\itdefault}
            \or\def\mst@greek@ush{\updefault}
604
605
       fi
606 \mst@update@greeksh
607 \ifmst@LGRgreek
608
       \DeclareFontEncoding{LGR}{}{}
609
       \DeclareSymbolFont{mtlgrfontlower}{LGR}{\mst@fam}{\mst@ser}{\mst@greek@lsh}
       \DeclareSymbolFont{mtlgrfontupper}{LGR}{\mst@fam}{\mst@ser}{\mst@greek@ush}
610
611 \else
612 \ifmst@selfGreek
       \DeclareSymbolFont{mtselfGreekfont}{OT1}{\mst@fam}{\mst@ser}{\mst@greek@ush}
In case we need the Euler font, we declare it here. It will use uzeur.fd from the eulervm package
```

mteulervm \MathEuler \MathEulerBold of Walter Schmidt

615 \ifmst@needeuler\typeout{** will use Euler font; command \string\MTEulerScale}

616 \DeclareSymbolFont{mteulervm}{U}{zeur}{m}{n}

617 \DeclareSymbolFontAlphabet{\MathEuler}{mteulervm}

618 \DeclareMathAlphabet{\MathEulerBold}{U}{zeur}{\mst@bold}{n}

619\fi

620 \newcommand*\MTEulerScale[1]{\edef\zeu@Scale{#1}}

621 \let\MathastextEulerScale\MTEulerScale

 $\text{EAT}_{FX} 2_{\varepsilon}$ has a strange initial configuration where the capital Greek letters are of type mathalpha, but the lower Greek letters of type mathord, so that \mathbf does not act on them, although lowercase Greek letters and Latin letters are from the same font. This is because \mathbf is set up to be like a bold version of \mathrm, and \mathrm uses the 'operators' font, by default cmr, where there are NO lowercase greek letters. This set-up is ok for the Capital Greek letters which are together with the Latin letters in both cmmi and cmr.

The package eulerym sets the lowercase Greek letters to be of type mathalpha, the default \mathbf and \mathrm will act wierdly on them, but a \mathbold is defined which will use the bold series of the Euler roman font, it gives something coherent for Latin and Greek lowercase letters, and this is possible because the same font contains upright forms for them all.

Here in mathastext, Latin letters and Greek letters (lower and upper case) must be (generally) assumed to come from two different fonts, as a result the standard \mathbf (and \mathrm) will give weird results when used for Greek letters. We could coerce \mathbf to do something reasonable (cf http://tug.org/pipermail/texhax/2011-January/016605.html) but at this time 30-01-2011 09:42:27 CET I decided I would not try to implement it here. I prefer to respect the default things.

I followed the simpler idea of the eulervm package and defineed \MathEuler and \MathEuler Bold alphabet commands (the eulervm package does this only for the bold font).

```
In case we need the Symbol font, we declare it here. The macro \psy@scale will be used to scale
  \MathPSymbol
                 the font (see at the very end of this file).
                622 \ifmst@needsymbol\typeout{** will use Symbol font; command \string\MTSymbolScale}
                623 \def\psy@scale{1}
                624 \DeclareSymbolFont{mtpsymbol}{U}{psy}{m}{n}
                625 \DeclareSymbolFontAlphabet{\MathPSymbol}{mtpsymbol}
                626 \AtBeginDocument{%
                      \DeclareFontFamily{U}{psy}{}%
                627
                      \DeclareFontShape{U}{psy}{m}{n}{<->s*[\psy@scale] psyr}{}%
                628
                629 }
                630\fi
                631 \newcommand*\MTSymbolScale[1]{\edef\psy@scale{#1}}
                632 \let\MathastextSymbolScale\MTSymbolScale
                 I did not choose for name \MathSymbol as this may be defined somewhere for another thing. There
                 is no bold for the postscript Symbol font distributed with the LATEX 2\varepsilon psnffs core package.
        \pmvec Definition of a poor man version of the \vec accent
                633 \DeclareRobustCommand*\pmvec[1] {\mathord{\stackrel{\raisebox{-.5ex}%
                634 {\tiny\boldmath$\mathord{\rightarrow}$}}{{}#1}}}
                 The glyph is taken from the Fourier font of Michel BOVANI. Note: (oct 2012) I should not allocate
   \fouriervec
                 an entire symbol font just for one glyph! But I have not given any serious thought to what one
                 can do to simulate a math accent without doing such a wasteful thing.
                635 \ifmst@fouriervec
                636
                      \DeclareFontEncoding{FML}{}{}
                      \DeclareFontSubstitution{FML}{futm}{m}{it}
                637
                      \DeclareSymbolFont{mathastextfourier}{FML}{futm}{m}{it}
                638
                      \SetSymbolFont{mathastextfourier}{bold}{FML}{futm}{b}{it}
                639
                640
                      \DeclareMathAccent{\fouriervec}{\mathord}{mathastextfourier}{"7E}
                641\fi
   \MTencoding Some public macros to modify our private internals, and we will use them also ourself.
                   In version 1.1 we add the possibility to have two distinct font shapes for letters and digits.
     \MTfamily
     \MTseries
                So in fact we could as well have two really unrelated fonts but this is really not the spirit of the
      \MTshape package.
                   Note that using these macros in the preamble allows \Mathastext to set up math versions
\MTboldvariant
\MTlettershape
                with a given font for math mode, and at the same time not modifying the \familydefault or
                 \romandefault etc...
                642 \newcommand*\MTencoding[1]{\def\mst@enc{#1}}
                643 \newcommand*\MTfamily[1]{\def\mst@fam{#1}}
                644 \newcommand*\MTseries[1] {\def\mst@ser{#1}}
                645 \newcommand*\MTshape[1] {\def\mst@opsh{#1}
                     \ifmst@italic\else\def\mst@ltsh{#1}\fi}
                647 \newcommand*\MTboldvariant[1] {\def\mst@bold{#1}}
                648 \newcommand*\MTlettershape[1] {\def\mst@ltsh{#1}}
                649 \let\Mathastextencoding\MTencoding
                650 \let\Mathastextfamily\MTfamily
                651 \let\Mathastextseries\MTseries
```

652 \let\Mathastextshape\MTshape

```
653 \let\Mathastextboldvariant\MTboldvariant
              654 \let\Mathastextlettershape\MTlettershape
              1.15c: These new macros can be used in-between calls to \Mathastext. They reset the shapes for
  \MTitgreek
              Greek letters (applies to LGRgreek(s) and selfGreek(s) options). The \MTgreekfont presupposes
  \MTupgreek
  \MTitGreek
              either LGRgreek or selfGreek. \MTgreekfont{\familydefault} acts like turning on LGRgreeks
  \MTupGreek
              or selfGreeks.
\MTgreekfont 655
                     \newcommand*\MTitgreek{%
              656 \mst@itgreektrue\mst@upgreekfalse\def\mst@greek@select{0}}
                     \newcommand*\MTupgreek{%
              657
              658 \mst@upgreektrue\mst@itgreekfalse\def\mst@greek@select{0}}
                     \newcommand*\MTitGreek{\def\mst@greek@select{1}}
              659
                     \newcommand*\MTupGreek{\def\mst@greek@select{2}}
              660
              661 \let\Mathastextitgreek\MTitgreek
              662 \let\Mathastextupgreek\MTupgreek
              663 \let\MathastextitGreek\MTitGreek
              664 \let\MathastextupGreek\MTupGreek
              665 \@onlypreamble\MTitgreek
              666 \@onlypreamble\MTupgreek
              667 \@onlypreamble\MTitGreek
              668 \@onlypreamble\MTitGreek
              669 \@onlypreamble\Mathastextitgreek
              670 \@onlypreamble\Mathastextupgreek
              671 \@onlypreamble\MathastextitGreek
              672 \@onlypreamble\MathastextitGreek
                     \newcommand*\MTgreekfont[1]{\def\mst@greekfont{#1}}
              673
              674 \let\Mathastextgreekfont\MTgreekfont
              675 \@onlypreamble\MTgreekfont
              676 \@onlypreamble\Mathastextgreekfont
  \MTWillUse
              This is a preamble-only command, which can be used more than once, only the latest one counts.
              Sets up the math fonts in the normal and bold versions, as does \Mathastext.
              677 \newcommand*\MTWillUse[5][]{
                   \MTencoding{#2}
              678
                   \MTfamily{#3}
              679
                   \MTseries{#4}
              680
                   \MTshape{#5}
              681
                     \ifmst@italic\MTlettershape{\itdefault}\fi % was missing in v 1.14 and prior
              682
              683
                   \edef\mst@tmp{#1}
                   \ifx\mst@tmp\empty\else\MTlettershape{#1}\fi
              684
                   \Mathastext}
              686 \let\MathastextWillUse\MTWillUse
              687 \let\Mathastextwilluse\MTWillUse
              688 \@onlypreamble\MTWillUse
              689 \@onlypreamble\MathastextWillUse
              690 \@onlypreamble\Mathastextwilluse
```

\Mathastext The command \Mathastext can be used anywhere in the preamble and any number of time, the last one is the one that counts.

In version 1.1 we have two fonts: they only differ in shape. The mtletterfont is for letters, and the mtoperatorfont for digits and log-like operator names. The default is that both are upright.

Starting with version 1.12, an optional argument makes \Mathastext act as the declaration of a math version, to be later used in the document.

Versions 1.15x brought some adaptations related to the subdued option.

- 1.3c adds a second optional parameter to inherit previous settings from another version; mostly done to inherit the bold version fonts for symbols and large symbols. This is done in \MTDeclareVersion.
- 1.3j moves the code related to \MTicinmath from \Mathastext@ to \AtBeginDocument (code depending on whether subdued option in use). But we omit for this from \MTicinmath the \MT mathactiveletters and issue the latter during loading of package, hence allowing \MTmathstan dardletters to be effective in the preamble.

I forgot to document that under subdued option the \Mathastext command without optional parameter does not any \SetSymbolFont etc... has a few other taks to complete nevertheless.

```
691 \def\Mathastext {\@ifnextchar [\Mathastext@declare\Mathastext@}
692 \def\Mathastext@declare [#1]{%
693
     \edef\mst@tmp{#1}%
     \ifx\mst@tmp\empty
694
          \expandafter\@firstoftwo
695
696
     \else\expandafter\@secondoftwo
     \fi
697
698
     \Mathastext@
     {\MTDeclareVersion[\mst@ltsh]{#1}{\mst@enc}{\mst@fam}{\mst@ser}{\mst@opsh}}%
699
700 }
701 \def\Mathastext@ {%
702
     \mst@update@greeksh
     \edef\mst@encoding@normal{\mst@enc}%
703
704
     \edef\mst@family@normal{\mst@fam}%
     \edef\mst@series@normal{\mst@ser}%
705
706
     \edef\mst@shape@normal{\mst@opsh}%
707
     \edef\mst@ltshape@normal{\mst@ltsh}%
     \edef\mst@itdefault@normal{\itdefault}%
708
     \edef\mst@rmdefault@normal{\rmdefault}%
709
     \edef\mst@sfdefault@normal{\sfdefault}%
710
     \edef\mst@ttdefault@normal{\ttdefault}%
711
     \edef\mst@boldvariant@normal{\mst@bold}%
712
     \edef\mst@exists@skip@normal{\mst@exists@skip}%
713
     \edef\mst@forall@skip@normal{\mst@forall@skip}%
714
715
     \edef\mst@prime@skip@normal{\mst@prime@skip}%
716
     \edef\mst@encoding@bold{\mst@enc}%
717
     \edef\mst@family@bold{\mst@fam}%
     \edef\mst@series@bold{\mst@bold}%
718
719
     \edef\mst@shape@bold{\mst@opsh}%
     \edef\mst@ltshape@bold{\mst@ltsh}%
720
721
     \edef\mst@boldvariant@bold{\mst@bold}%
     \edef\mst@itdefault@bold{\itdefault}%
722
723
     \edef\mst@rmdefault@bold{\rmdefault}%
     \edef\mst@sfdefault@bold{\sfdefault}%
724
```

```
725 \edef\mst@ttdefault@bold{\ttdefault}%
726 \edef\mst@exists@skip@bold{\mst@exists@skip}%
727 \edef\mst@forall@skip@bold{\mst@forall@skip}%
728 \edef\mst@prime@skip@bold{\mst@prime@skip}%
729 \ifmst@subdued
```

Since 1.3j this branch is actually almost superfluous, as entering normal or bold with \MTver sion does \MTnormalexists, \MTnormalforall, and \MTnormalprime. But some default values are needed if the user insists on issuing \MTexistsdoesskip, etc... nevertheless.

```
\def\mst@exists@skip@normal{Omu}%
730
731
       \def\mst@forall@skip@normal{Omu}%
       \def\mst@prime@skip@normal{Omu}%
732
       \def\mst@exists@skip@bold{Omu}%
733
       \def\mst@forall@skip@bold{Omu}%
734
735
       \def\mst@prime@skip@bold{0mu}%
736
     \else % not subdued
       \ifmst@italic
737
         \ifmst@frenchmath
738
           \mst@exists@muskip\mst@exists@skip\relax
739
740
           \mst@forall@muskip\mst@forall@skip\relax
           \mst@prime@muskip\mst@prime@skip\relax
741
742
         \else
743
          \def\mst@exists@skip@normal{Omu}%
744
          \def\mst@forall@skip@normal{Omu}%
          \def\mst@prime@skip@normal{Omu}%
745
746
          \def\mst@exists@skip@bold{0mu}%
          \def\mst@forall@skip@bold{0mu}%
747
          \def\mst@prime@skip@bold{0mu}%
748
         \fi
749
750
       \else
751
           \mst@exists@muskip\mst@exists@skip\relax
           \mst@forall@muskip\mst@forall@skip\relax
752
           \mst@prime@muskip\mst@prime@skip\relax
753
754
       \fi
     \fi
755
756 %% v1.15f
     \ifmst@nonormalbold\else
757
      \SetMathAlphabet{\mathnormalbold}{normal}{\mst@encoding@normal}%
758
                                      {\mst@family@normal}%
759
                                      {\mst@boldvariant@normal}%
760
761
                                      {\mst@ltshape@normal}%
      \SetMathAlphabet{\mathnormalbold}{bold}{\mst@encoding@bold}%
762
763
                                      {\mst@family@bold}%
                                      {\mst@boldvariant@bold}%
764
                                      {\mst@ltshape@bold}%
765
     \fi
767 %% v1.15f adds \ifmst@default.. checks
     \ifmst@subdued\else
768
      \SetSymbolFont{mtletterfont}{normal}{\mst@encoding@normal}%
769
                                            {\mst@family@normal}%
770
```

```
771
                                            {\mst@series@normal}%
                                            {\mst@ltshape@normal}%
772
                                            {\mst@encoding@bold}%
773
      \SetSymbolFont{mtletterfont}{bold}
774
                                            {\mst@family@bold}%
775
                                            {\mst@series@bold}%
776
                                            {\mst@ltshape@bold}%
      \SetSymbolFont{mtoperatorfont}{normal}{\mst@encoding@normal}%
777
                                            {\mst@family@normal}%
778
                                            {\mst@series@normal}%
779
                                            {\mst@shape@normal}%
780
      \SetSymbolFont{mtoperatorfont}{bold} {\mst@encoding@bold}%
781
                                            {\mst@family@bold}%
782
783
                                            {\mst@series@bold}%
                                            {\mst@shape@bold}%
784
785
      \ifmst@defaultbf\else
786
       \SetMathAlphabet{\Mathbf}{normal}{\mst@encoding@normal}%
                                      {\mst@family@normal}%
787
788
                                      {\mst@series@bold}%
                                      {\mst@shape@normal}%
789
790
       \SetMathAlphabet{\Mathbf}{bold}{\mst@encoding@bold}%
791
                                      {\mst@family@bold}%
                                      {\mst@series@bold}%
792
                                      {\mst@shape@bold}%
793
794
      \fi
      \ifmst@defaultit\else
795
796
       \SetMathAlphabet{\Mathit}{normal}{\mst@encoding@normal}%
                                      {\mst@family@normal}%
797
                                      {\mst@series@normal}%
798
                                      {\mst@itdefault@normal}%
799
       \SetMathAlphabet{\Mathit}{bold}{\mst@encoding@bold}%
800
801
                                      {\mst@family@bold}%
802
                                      {\mst@series@bold}%
                                      {\mst@itdefault@bold}%
803
      \fi
804
      \ifmst@defaultsf\else
805
806
       \SetMathAlphabet{\Mathsf}{normal}{\mst@encoding@normal}%
807
                                      {\mst@sfdefault@normal}%
                                      {\mst@series@normal}%
808
                                      {\mst@shape@normal}%
809
       \SetMathAlphabet{\Mathsf}{bold}{\mst@encoding@bold}%
810
                                      {\mst@sfdefault@bold}%
811
                                      {\mst@series@bold}%
812
                                      {\mst@shape@bold}%
813
814
      \ifmst@defaulttt\else
815
       \SetMathAlphabet{\Mathtt}{normal}{\mst@encoding@normal}%
816
817
                                      {\mst@ttdefault@normal}%
818
                                      {\mst@series@normal}%
                                      {\mst@shape@normal}%
819
```

```
821
                                                      {\mst@ttdefault@bold}%
                                                      {\mst@series@bold}%
                822
                823
                                                      {\mst@shape@bold}%
                824
                      \fi
                825
                     \fi % de \ifmst@subdued
\MathEulerBold 1.14c: We reset mteulervm and \MathEulerBold here as the variant for bold may have been
                changed by the user via \Mathastextboldvariant{m}; and we should keep this local to math
                versions.
                826
                     \ifmst@needeuler
                       \SetSymbolFont{mteulervm}{bold}{U}{zeur}{\mst@boldvariant@normal}{n}%
                827
                       \SetMathAlphabet{\MathEulerBold}{normal}%
                828
                                   {U}{zeur}{\mst@boldvariant@normal}{n}%
                829
                       \SetMathAlphabet{\MathEulerBold}{bold}%
                830
                                   {U}{zeur}{\mst@boldvariant@normal}{n}%
                831
                     \fi
                832
                     \ifmst@needsymbol\SetSymbolFont{mtpsymbol}{bold}%
                833
                                         {U}{psy}{\mst@boldvariant@normal}{n}%
                834
                835
                     \fi
                LGRgreek, LGRgreeks, selfGreek, and selfGreeks options.
     LGRgreek*
    selfGreek*
                     \ifmst@subdued\else
               836
                      \ifmst@LGRgreek
                837
                       \verb|\SetSymbolFont{mtlgrfontlower}{normal}{LGR}||
                838
                                {\mst@greekfont}{\mst@series@normal}{\mst@greek@lsh}%
                839
                       \SetSymbolFont{mtlgrfontlower}{bold}{LGR}%
                840
                                {\mst@greekfont}{\mst@boldvariant@normal}{\mst@greek@lsh}%
                841
                       \SetSymbolFont{mtlgrfontupper}{normal}{LGR}%
                842
                843
                                {\mst@greekfont}{\mst@series@normal}{\mst@greek@ush}%
                       \SetSymbolFont{mtlgrfontupper}{bold}{LGR}%
                844
                845
                                {\mst@greekfont}{\mst@boldvariant@bold}{\mst@greek@ush}%
                      \else
                846
                       \ifmst@selfGreek
                847
                848
                        \SetSymbolFont{mtselfGreekfont}{normal}{OT1}%
                849
                                {\mst@greekfont}{\mst@series@normal}{\mst@greek@ush}%
                        \SetSymbolFont{mtselfGreekfont}{bold}{OT1}%
                850
                                {\mst@greekfont}{\mst@bold\ariant@bold}{\mst@greek@ush}%
                851
                852
                       \fi
                      \fi
                853
                     \fi
                854
                     \ifmst@subdued
                855
                      \typeout{** subdued mode will be activated for the normal and bold math ver
                856
                   sions}%
                     \else
                857
                      \typeout{** Latin letters in the normal (resp. bold) math versions are now^^J%
                858
                859
                                ** set up to use the fonts
```

\SetMathAlphabet{\Mathtt}{bold}{\mst@encoding@bold}%

820

```
860
      \mst@encoding@normal/\mst@family@normal/\mst@series@normal%
                   (\mst@boldvariant@normal)/\mst@ltshape@normal}%
861
      \ifmst@LGRgreek\typeout{** Greek letters (\mst@greek@lsh/\mst@greek@ush)
862
                                  will use LGR/\mst@greekfont}%
863
864
865
      \ifmst@nodigits\else
        \typeout{** Other characters (digits, ...) and \protect\log-like names will be^^J%
866
                 ** typeset with the \mst@shape@normal\space shape.}%
867
      \fi
868
869
     \fi
870 }
871 \let\mathastext\Mathastext
872 \@onlypreamble\Mathastext
873 \@onlypreamble\mathastext
```

\MTDeclareVersion

The \MTDeclareVersion command is to be used in the preamble to declare a math version. A more complicated variant would also specify a choice of series for the Euler and Symbol font: anyhow Symbol only has the medium series, and Euler has medium and bold, so what is lacking is the possibility to create a version with a bold Euler. There is already one such version: the default bold one. And there is always the possibility to add to the preamble \SetSymbolFont{mteulervm}{versionname}{U}{zeur}{bx}{n} if one wants to have a math version with bold Euler characters.

For version 1.1 we add an optional parameter specifying the shape to be used for letters.

Note: (2012/10/24) I really should check whether the user attempts to redefine the 'normal' and 'bold' versions and issue a warning in that case!

1.3c (2013/12/14) adds an extra optional parameter after all previous ones, to inherit the settings from another version. Typically to be used with [bold]. I take this opportunity to sanitize a bit some line endings to avoid generating (in the preamble, document macros were already careful of course) too many space tokens, at least inside macros. And I modify (correct? perhaps it was on purpose) the strange way I used \@onlypreamble in earlier version.

```
874 \newcommand*\MTDeclareVersion[6][]{%
     \def\mst@declareversionargs{{#1}{#2}{#3}{#4}{#5}{#6}}%
875
     \edef\mst@version{#2}%
876
877
     \DeclareMathVersion{\mst@version}%
878
     \MTDeclareVersion@
879 }
880 \newcommand*\MTDeclareVersion@[1][]{%
       \edef\mst@tmp{#1}%
882
       \ifx\mst@tmp\empty\else
         \global\expandafter\let\csname mv@\mst@version\expandafter\endcsname
883
                                 \csname mv@#1\endcsname
884
         \typeout{** Math version '\mst@version\string' inherits from '#1\string'.}%
885
886
       \fi
       \expandafter\MTDeclareVersion@@\mst@declareversionargs
887
888 }
889 \newcommand*\MTDeclareVersion@@[6]{%
890
     \edef\mst@tmp{#1}%
     \expandafter\edef\csname mst@encoding@\mst@version\endcsname{#3}%
891
     \expandafter\edef\csname mst@family@\mst@version\endcsname{#4}%
892
```

```
893
     \expandafter\edef\csname mst@series@\mst@version\endcsname{#5}%
894
     \expandafter\edef\csname mst@shape@\mst@version\endcsname{#6}%
     \expandafter\edef\csname mst@boldvariant@\mst@version\endcsname{\mst@bold}%
895
896
     \expandafter\edef\csname mst@itdefault@\mst@version\endcsname{\itdefault}%
897
     \expandafter\edef\csname mst@rmdefault@\mst@version\endcsname{\rmdefault}%
898
     \expandafter\edef\csname mst@sfdefault@\mst@version\endcsname{\sfdefault}%
     \expandafter\edef\csname mst@ttdefault@\mst@version\endcsname{\ttdefault}%
899
     \expandafter\edef\csname mst@exists@skip@\mst@version\endcsname
900
           {\mst@exists@skip}%
901
902
     \expandafter\edef\csname mst@forall@skip@\mst@version\endcsname
           {\mst@forall@skip}%
903
     \expandafter\edef\csname mst@prime@skip@\mst@version\endcsname
904
           {\mst@prime@skip}%
905
     \ifx\mst@tmp\empty
906
907
       \ifmst@italic
908
         \SetSymbolFont{mtletterfont}{#2}{#3}{#4}{#5}{\mst@ltsh}%
         \typeout{** Latin letters in math version '#2\string' will use the font
909
                     #3/#4/#5/\mst@ltsh^^J%
910
                  ** Other characters (digits, ...) and \protect\log-like names
911
912
                       will be in #6 shape.}%
913
         \expandafter\edef\csname mst@ltshape@\mst@version\endcsname{\mst@ltsh}%
       \else
914
         \SetSymbolFont{mtletterfont}{#2}{#3}{#4}{#5}{#6}%
915
          \typeout{** Latin letters in math version '#2\string' will use the fonts
916
917
                      #3/#4/#5(\mst@bold)/#6}%
918
         \expandafter\edef\csname mst@ltshape@\mst@version\endcsname{#6}%
       \fi
919
     \else
920
921
       \SetSymbolFont{mtletterfont}{#2}{#3}{#4}{#5}{#1}%
       \typeout{** Latin letters in math version '#2\string' will use the font
922
923
                   #3/#4/#5/#1^^J%
924
                ** Other characters (digits, ...) and \protect\log-like
925
                   names will be in #6 shape.}%
926
         \expandafter\edef\csname mst@ltshape@\mst@version\endcsname{#1}%
     \fi
927
928
     \ifmst@nonormalbold\else
929
          \SetMathAlphabet{\mathnormalbold}{#2}{#3}{#4}{\mst@bold}%
                      {\csname mst@ltshape@\mst@version\endcsname}%
930
931
     \SetSymbolFont{mtoperatorfont}{#2}{#3}{#4}{#5}{#6}%
932
     \ifmst@defaultbf\else\SetMathAlphabet{\Mathbf}{#2}{#3}{#4}{\mst@bold}{#6}\fi
933
     \ifmst@defaultit\else\SetMathAlphabet{\Mathit}{#2}{#3}{#4}{#5}{\itdefault}\fi
934
935
     \ifmst@defaultsf\else\SetMathAlphabet{\Mathsf}{#2}{#3}{\sfdefault}{#5}{#6}\fi
     \ifmst@defaulttt\else\SetMathAlphabet{\Mathtt}{#2}{#3}{\ttdefault}{#5}{#6}\fi
936
     \ifmst@needeuler
937
938
         \SetMathAlphabet{\MathEulerBold}{#2}{U}{zeur}{\mst@bold}{n}%
939
     \fi
```

LGRgreeks In the case of option LGRgreeks (selfGreeks), it is expected that the fonts used in each math selfGreeks

versions exist in LGR (OT1) encoding. We first recalculate the shapes to be used for lowercase and uppercase Greek letters depending on the frenchmath and [it/up][g/G]reek options as well as on the (local to this version) shapes for letters and digits.

```
\def\mst@greek@lsh@loc{\csname mst@ltshape@\mst@version\endcsname}%
940
     \def\mst@greek@ush@loc{\csname mst@shape@\mst@version\endcsname}%
941
942
     \ifmst@itgreek\def\mst@greek@lsh@loc{\itdefault}%
                         \def\mst@greek@ush@loc{\itdefault}\fi
943
     \ifmst@upgreek\def\mst@greek@lsh@loc{\updefault}%
944
                         \def\mst@greek@ush@loc{\updefault}\fi
945
946
     \ifmst@frenchmath
         \ifmst@itgreek\else
947
948
         \ifmst@upgreek\else
949
           \def\mst@greek@lsh@loc{\csname mst@shape@\mst@version\endcsname}%
           \def\mst@greek@ush@loc{\csname mst@shape@\mst@version\endcsname}%
950
         \fi\fi
951
952
     \fi
953
     \ifcase\mst@greek@select
           \or\def\mst@greek@ush@loc{\itdefault}%
954
           \or\def\mst@greek@ush@loc{\updefault}%
955
956
957
     \ifmst@LGRgreeks
         \SetSymbolFont{mtlgrfontlower}{#2}{LGR}{#4}{#5}{\mst@greek@lsh@loc}%
958
959
         \SetSymbolFont{mtlgrfontupper}{#2}{LGR}{#4}{#5}{\mst@greek@ush@loc}%
       \typeout{** Greek letters (\mst@greek@lsh@loc/\mst@greek@ush@loc) will use
960
                   LGR font #4\ifmst@subdued ^^J** (in non subdued versions)\fi}%
961
     \else
962
963
      \ifmst@selfGreeks
         \SetSymbolFont{mtselfGreekfont}{#2}{0T1}{#4}{#5}{\mst@greek@ush@loc}%
964
        \typeout{** Capital Greek letters (\mst@greek@lsh@loc/\mst@greek@ush@loc)
965
                    will use OT1 font #4\ifmst@subdued ^J** (in non subdued versions)\fi}%
966
967
      \else
968
       \ifmst@LGRgreek
         \SetSymbolFont{mtlgrfontlower}{#2}{LGR}{\mst@greekfont}{#5}{\mst@greek@lsh@loc}%
969
         \SetSymbolFont{mtlgrfontupper}{#2}{LGR}{\mst@greekfont}{#5}{\mst@greek@ush@loc}%
970
971
       \typeout{** Greek letters (\mst@greek@lsh@loc/\mst@greek@ush@loc) will use
                   LGR font \mst@greekfont\ifmst@subdued ^^J** (in non subdued ver
   sions)\fi}%
       \else
973
        \ifmst@selfGreek
974
          \SetSymbolFont{mtselfGreekfont}{#2}{OT1}{\mst@greekfont}{#5}{\mst@greek@ush@loc}%
975
          \typeout{** Capital Greek letters (\mst@greek@lsh@loc/\mst@greek@ush@loc)
976
                       will use OT1 font \mst@greekfont\ifmst@subdued ^^J** (in non sub
977
   dued versions)\fi}%
978
        \fi
       \fi
979
      \fi
980
981
     \fi
982 }
```

```
983 \let\MathastextDeclareVersion\MTDeclareVersion
984 \@onlypreamble\MTDeclareVersion
985 \@onlypreamble\MathastextDeclareVersion
```

\MTversion \MTversion@ \MTversion@s \MTversion@@ This is a wrapper around LATEX's \mathversion: here we have an optional argument allowing a quick and easy change of the text fonts additionally to the math fonts. Present already in the initial version of the package (January 2011.)

- 1.15: some modifications for the subdued option vs LGRgreek and for the math muskips after \exists and \forall.
- 1.2: with the subdued option sets the math alphabets in the normal and bold math versions do not apply to operator names and non-alphabetical symbols. The switch for braces is left as it is
- 1.2b: with the subdued option, the italic corrections are not added. Else, we check the shape of letters in this version. Also, there was a bug since 1.15: the values of the math skips were taken not from the settings for the math version (#2) but from those of the optional argument (#1), if present...
 - 1.3: activation of italic corrections is now separated from actual math activation of letters.
 - 1.3c: a starred variant is added which does not modify the text fonts, only the math set-tup.
- 1.3d: replaced in \MTversion@ things like \edef\mst@encoding{...} and \renewcommand{\encodingdefault by \edef\encodingdefault{...} etc...All those \mst@0... things were useless. I also redefine \seriesdefault rather than \mddefault.
- 1.3d: mechanism of restoration of Greek in subdued normal and bold versions has been to all cases, and not only for the LGRgreek option.

```
986 \newcommand*\MTversion {\@ifstar\MTversion@s\MTversion@ }
 987 \newcommand*\MTversion@s [1] {\mathversion{#1}\MTversion@@ {#1}}
 988 \newcommand*\MTversion@ [2][]{%
 989
        \mathversion{#2}%
        \edef\mst@tmpa{#1}%
 990
        \ifx\mst@tmpa\empty
 991
992
            \edef\mst@tmp{#2}%
        \else
993
 994
            \let\mst@tmp\mst@tmpa
995
        \edef\encodingdefault {\csname mst@encoding@\mst@tmp\endcsname}%
996
        \edef\familydefault
                               {\csname mst@family@\mst@tmp\endcsname}%
997
                               {\tt \{\csname\ mst@series@\mst@tmp\endcsname}\%}
998
        \edef\seriesdefault
999
        \edef\shapedefault
                               {\csname mst@shape@\mst@tmp\endcsname}%
1000
        \edef\bfdefault {\csname mst@boldvariant@\mst@tmp\endcsname}%
        \edef\itdefault {\csname mst@itdefault@\mst@tmp\endcsname}%
1001
1002
        \edef\rmdefault {\csname mst@rmdefault@\mst@tmp\endcsname}%
        \edef\sfdefault {\csname mst@sfdefault@\mst@tmp\endcsname}%
1003
        \edef\ttdefault {\csname mst@ttdefault@\mst@tmp\endcsname}%
1004
1005
        \usefont{\encodingdefault}{\familydefault}{\seriesdefault}{\shapedefault}%
1006
        \MTversion@@ {#2}%
1007 }
```

1.3j has a stronger subdued which does \MTnormalprime , \MTnormalexists , \MTnormalforall rather than setting the skips to Omu. Hence \MTversion by default should do \MTprimedoesskip , \MTexistsdoesskip , \MTforalldoesskip .

1008 \newcommand*\MTversion@@ [1]{%

```
1009
        \MTexistsdoesskip
1010
        \MTforalldoesskip
        \MTprimedoesskip
1011
1012
        \edef\mst@tmp{#1}%
 v1.15e: muskips.
1013
        \expandafter
         \mst@exists@muskip\csname mst@exists@skip@\mst@tmp\endcsname\relax
1014
1015
        \expandafter
         \mst@forall@muskip\csname mst@forall@skip@\mst@tmp\endcsname\relax
1016
 v1.2: muskip for \prime.
```

- \expandafter 1017
- \mst@prime@muskip\csname mst@prime@skip@\mst@tmp\endcsname\relax 1018
 - v1.2b: italic corrections except for italic/slanted (sic) letters, and of course except in the subdued normal and bold math versions.
 - v1.3: by default, letters are made mathematically active, even if italic corrections are not used, to allow the action of \MTsetmathskips.

```
\edef\mst@tmpa{\csname mst@ltshape@\mst@tmp\endcsname}%
1019
1020
        \edef\mst@tmpb{\csname mst@shape@\mst@tmp\endcsname}%
```

- v1.15c: extending subdued to LGRgreek.
 - v1.15f: subdueing math alphabets in a simpler way than in 1.15e.
 - v1.2b: subdueing the activation of characters in math mode.
 - v1.2d: special treatment of the asterisk.
 - v1.3d: extended LGRgreek mechanism of activation/restoration of Greek to all cases.
- v1.3j: use of \MTeverymathdefault, which includes \MTicinmath, but must be corrected then according to shape of letters and presence or absence of option frenchmath. We do only \def\mst@ITcorr{\ifnum\fam=\m@ne\/\fi} and not \MTICinmath to not overwrite some userdefined \MTeverymathdefault. Code for italic corrections or not according to letter shape is executed after \MTeverymathdefault which limits a bit user customizing possibilities, but if I moved it later, I would possibly have to put inside the \MTicinmath the check for it ot sl. Similary the \MTcustomgreek always executed (if not subdued).

```
1021
          \MTmathoperatorsobeymathxx
          \MTeverymathdefault
1022
1023
          \MTcustomizenewmcodes
          \@for\mst@tmpc:=it,sl\do{\ifx\mst@tmpc\mst@tmpa\MTnoicinmath\fi}%
1024
1025
          \ifmst@frenchmath
1026
             \def\mst@ITcorr{\ifnum\fam=\m@ne\/\fi}%
1027
             \label{lem:condition} $$ \end{\mathop{\t \nst0tmpc\mst0tmpb\MTnoICinmath\fi}} $$ \end{\mathop{\t \nst0tmpc\mst0tmpb\MTnoICinmath\fi}} $$
1028
```

1.3j has a stronger subdued which does \MTnormalprime, \MTnormalexists, \MTnormalforall rather than simply setting the skips to Omu. Note: \MTnormalprime is done as part of \MTevery mathoff.

```
\ifmst@subdued
1029
          \def\mst@tmpa{normal}%
1030
1031
          \ifx\mst@tmp\mst@tmpa
             \mst@restorealphabets
1032
1033
             \MTstandardgreek
             \MTmathoperatorsdonotobeymathxx
1034
```

```
1035
             \MTnormalexists
             \MTnormalforall
1036
             \MTeverymathoff
1037
             \MTresetnewmcodes
1038
1039
          \else
1040
             \def\mst@tmpa{bold}%
             \ifx\mst@tmp\mst@tmpa
1041
               \mst@restorealphabets
1042
               \MTstandardgreek
1043
1044
               \MTmathoperatorsdonotobeymathxx
               \MTnormalexists
1045
1046
               \MTnormalforall
               \MTeverymathoff
1047
               \MTresetnewmcodes
1048
1049
             \else
1050
               \mst@setalphabets
               \MTcustomgreek
1051
            \fi
1052
          \fi
1053
1054
        \else
1055
          \MTcustomgreek % new with 1.3d
1056
        \fi
1057 }
1058 \let\MathastextVersion\MTversion
1059 \let\Mathastextversion\MTversion
1060 \let\MTVersion\MTversion
1061 \let\mathastextversion\MTversion
```

\Mathastext Initialization call:

1062 \Mathastext

Additional appropriate messages to the terminal and the log.

```
1063 \ifmst@eulergreek
1064
          \typeout{** Greek letters will use the Euler font. Use \protect\MathastextEulerScale{
1065
                   font.}%
          \ifmst@subdued{\typeout{** (subdued mode: normal and bold math
1066
              version with default Greek letters.)}}\fi
1067
1068 \else
1069 \ifmst@symbolgreek
           \typeout{** Greek letters will use the PostScript Symbol font. Use^^J%
1070
                    ** \protect\MathastextSymbolScale{<factor>} to scale the font.}%
1071
1072
          \ifmst@subdued{\typeout{** (subdued mode: normal and bold math
              version with default Greek letters.)}}\fi
1073
1074 \fi\fi
```

At (long...) last we now change the font for the letters of the latin alphabet. In version 1.1, Latin letters have their own font (shape).

1.2b initiated the use of mathematically active letters to insert the italic corrections. With version 1.3 the use of math active letters is also for extra muglue added before and after the letters. Use of \@for to shorten the code initiated with release 1.3.

```
1075 \def\mst@DeclareMathLetter #1{%
        \DeclareMathSymbol {#1}{\mathalpha}{mtletterfont}{'#1}%
1076
        \expandafter
1077
1078
        \DeclareMathSymbol \csname mst@#1\endcsname{\mathalpha}{mtletterfont}{'#1}%
1079
        \expandafter\mst@addtodo@az\expandafter #1\csname mst@#1\endcsname
1080 }%
1081 \ensuremath{\mbox{\tt Qfor}\mbox{\tt mst}\mbox{\tt Qtmp}:=a,b,c,d,e,f,g,h,i,j,k,l,m,n,o,p,q,r,s,t,u,v,w,x,y,z\ensuremath{\mbox{\tt do}}
         {\expandafter\mst@DeclareMathLetter\mst@tmp}%
1083 \ifmst@frenchmath \def\mst@font@tbu{mtoperatorfont}%
1084
                        \def\mst@font@tbu{mtletterfont}%
1085 \fi
1086 \def\mst@DeclareMathLetter #1{%
        \DeclareMathSymbol {#1}{\mathalpha}{\mst@font@tbu}{'#1}%
1087
        \expandafter
1088
1089
        \DeclareMathSymbol \csname mst@#1\endcsname{\mathalpha}{\mst@font@tbu}{'#1}%
1090
        \expandafter\mst@addtodo@AZ\expandafter #1\csname mst@#1\endcsname
1091 }%
1092 \ensuremath{\mbox{\mbox{\mbox{$1092$}}} \ensuremath{\mbox{\mbox{$0$}}} = A,B,C,D,E,F,G,H,I,J,K,L,M,N,O,P,Q,R,S,T,U,V,W,X,Y,Z\do
          {\expandafter\mst@DeclareMathLetter\mst@tmp}%
1094 \let\mst@DeclareMathLetter\relax
1095 %%
1096 \ifmst@nodigits\else
1097 \def\mst@font@tbu{mtoperatorfont}%
  In version 1.1, we have now separated digits from letters, so paradoxically it is less problematic
  to give them the mathalpha type.
1098 \ifmst@symboldigits \def\mst@font@tbu{mtpsymbol} \fi
1099 \ifmst@eulerdigits \def\mst@font@tbu{mteulervm} \fi
1100 \DeclareMathSymbol{0}{\mathalpha}{\mst@font@tbu}{'0}%
1101 \DeclareMathSymbol{1}{\mathalpha}{\mst@font@tbu}{'1}%
1102 \DeclareMathSymbol{2}{\mathalpha}{\mst@font@tbu}{'2}%
1103 \DeclareMathSymbol{3}{\mathalpha}{\mst@font@tbu}{'3}%
1104 \DeclareMathSymbol{4}{\mathalpha}{\mst@font@tbu}{'4}%
1105 \DeclareMathSymbol{5}{\mathalpha}{\mst@font@tbu}{'5}%
1106 \DeclareMathSymbol{6}{\mathalpha}{\mst@font@tbu}{'6}%
1107 \DeclareMathSymbol{7}{\mathalpha}{\mst@font@tbu}{'7}%
1108 \DeclareMathSymbol{8}{\mathalpha}{\mst@font@tbu}{'8}%
1109 \DeclareMathSymbol{9}{\mathalpha}{\mst@font@tbu}{'9}%
1110\fi
  When symboldelimiters is passed as an option, we use the Symbol font for the printable
  characters other than letters and digits.
1111 \ifmst@symboldelimiters
1112 \def\mst@font@tbu{mtpsymbol}%
1113 \mst@endashfalse
1114 \mst@emdashfalse
1115 \else
1116 \def\mst@font@tbu{mtoperatorfont}%
1117 \fi
```

1.2 adds the tricks to let non letters/digits obey math alphabets. We have to double the defini-

tions for easy switch on-off of the mechanism, via a token list which is put into \everymath and \everydisplay.

```
1118 \ifmst@noexclam\else\typeout{** \string! and \string?}%
1119 \DeclareMathSymbol{!}{\mathclose}{\mst@font@tbu}{"21}%
1120 \DeclareMathSymbol{\mst@varfam@exclam}{\mathalpha}{\mst@font@tbu}{"21}%
1121 \expandafter\mst@addtodo@nonletters\string!\mathclose\mst@varfam@exclam
1122 \DeclareMathSymbol{?}{\mathclose}{\mst@font@tbu}{"3F}%
1123 \DeclareMathSymbol{\mst@varfam@question}{\mathalpha}{\mst@font@tbu}{"3F}%
1124 \expandafter\mst@addtodo@nonletters\string?\mathclose\mst@varfam@question
1125 \fi
```

\MTlowerast \mst@doasterisk \mst@@doasterisk \MTnormalasterisk \MTactiveasterisk 1.12d The \ast or * is defined in fontmath.ltx as a binary operator from the symbols font. Usually the asterisk from the text font is in a raised position. Previous versions of mathastext did nothing with \ast but strangely defined * to be the one from the text font, with type \mathalpha. The package now leaves by default both * and \ast untouched, and if passed option asterisk replaces both of them with a lowered text asterisk (or the one from the Symbol font), and of type \mathbin. A trick is used to optionally get both * and \ast obey the math alphabets.

The user macro \MTlowerast sets the amount of lowering to be applied to the text asterisk.

1.12e Somehow there was a big omission in 1.12d, the command \MTlowerast as described in the manual was missing!

nota bene: it is assumed that * is of type other when mathastext is loaded... it should neither be active, nor of type letter!

1.3i adds \MTnormalasterisk and \MTactiveasterisk. They do nothing without option asterisk.

```
1126 \def\mst@doasterisk{\let\ast\mst@ast\mst@mathactivate*{}\mst@ast}%
1127 \newcommand*\MTnormalasterisk {\let\mst@doasterisk\relax}
1128 \newcommand*\MTactiveasterisk {\let\mst@doasterisk\mst@doasterisk}
1129 \ifmst@asterisk\typeout{** asterisk: \string\ast\space and *}
        \AtBeginDocument{%
1130
1131
         \everymath\expandafter
1132
                  {\the\everymath
                                     \mst@doasterisk \MTnormalasterisk \%
         \everydisplay\expandafter
1133
1134
                  {\the\everydisplay\mst@doasterisk \MTnormalasterisk }}
      \ifmst@symbolmisc
1135
        \def\mst@bin@ast{%
1136
1137
        \mathbin{\mathchoice{\raisebox{-.1\height}%
                             {\the\textfont\symmtpsymbol\char42}}%
1138
                           {\raisebox{-.1\height}%
1139
                             {\the\textfont\symmtpsymbol\char42}}%
1140
                           {\raisebox{-.1\height}%
1141
1142
                             {\the\scriptfont\symmtpsymbol\char42}}%
                           {\raisebox{-.1\height}%
1143
                             {\the\scriptscriptfont\symmtpsymbol\char42}}}}%
1144
      \else
1145
        \def\mst@bin@ast{%
1146
        \mathbin{\mathchoice{\raisebox{-\mst@lowerast}%
1147
                             {\the\textfont\symmtoperatorfont\char42}}%
1148
                           {\raisebox{-\mst@lowerast}%
1149
                             {\the\textfont\symmtoperatorfont\char42}}%
1150
```

```
{\raisebox{-\mst@lowerast}%
1151
                             {\the\scriptfont\symmtoperatorfont\char42}}%
1152
                           {\raisebox{-\mst@lowerast}%
1153
                             {\the\scriptscriptfont\symmtoperatorfont\char42}}}}%
1154
1155
1156
      \def\mst@varfam@ast{\ifnum\fam=\m@ne\mst@bin@ast\else
        \mathbin{\mathchoice{\raisebox{-\mst@lowerast}}%
1157
                             {\the\textfont\fam\char42}}%
1158
                           {\raisebox{-\mst@lowerast}%
1159
1160
                             {\the\textfont\fam\char42}}%
                           {\raisebox{-\mst@lowerast}%
1161
1162
                             {\the\scriptfont\fam\char42}}%
                           {\raisebox{-\mst@lowerast}%
1163
                             {\the\scriptscriptfont\fam\char42}}}\fi}%
1164
      \MTactiveasterisk
1165
      \DeclareRobustCommand*{\mst@ast}{\mst@bin@ast}
1166
      \newcommand*\MTlowerast[1]{\def\mst@lowerast{#1}}
1167
      \MTlowerast{.3\height}
1168
      \mst@do@easynonletters\expandafter\expandafter\expandafter
1169
1170
        {\expandafter\the\expandafter\mst@do@easynonletters
1171
         \expandafter\def\csname mst@ast \endcsname{\mst@varfam@ast}}
1172\fi
```

(2011) I renounced to try to do things with all the various dots, they are defined in many different ways, and there is the amsmath also. Dealing with this issue would mean a lot a time for a minuscule result. Better to leave the user use the mathdots package and accept that we can not avoid the default fonts in that case. So here I just treat . (in the hope to really lessen by 1 the number of fonts embedded at the end in the PDF).

[(Dec. 2012) should I reexamine these definitive sounding remarks?]

```
1173 \ifmst@nopunct\else\typeout{** punctuation\string: \string, \string: \string: \string; and
1174 \DeclareMathSymbol{,}{\mathpunct}{\mst@font@tbu}{"2C}
1176 \expandafter\mst@addtodo@nonletters\string,\mathpunct\mst@varfam@comma
1177 \DeclareMathSymbol{.}{\mathord}{\mst@font@tbu}{"2E}
\label{lem:linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_linear_lin
1179 \mst@addtodo@easynonletters\.\mst@varfam@dot
1180 \DeclareMathSymbol{:}{\mathrel}{\mst@font@tbu}{"3A} % relation spacing
1182 \expandafter\mst@addtodo@nonletters\string:\mathrel\mst@varfam@colon
1183 \@ifpackageloaded{amsmath}
1184 {} % \colon defined in amsmath.sty in terms of : with some enlarged explicit
                 % spacing. No need to intervene.
1186 {% no amsmath, use standard punctuation spacing
1187 \let\colon\undefined
              \% the reason is if some package has redefined \colon which then
               % can not be used in \cs{DeclareMathSymbol} anymore (we
1190
              % shamelessly overwrite...)
                    \DeclareMathSymbol{\colon}{\mathpunct}{\mst@font@tbu}{"3A}
1191
                    \mst@do@nonletters\expandafter{\the\mst@do@nonletters
1192
```

```
1193 \def\colon{\mathpunct{\mst@varfam@colon}}}
1194 \DeclareMathSymbol{;}{\mathpunct}{\mst@font@tbu}{"3B}
1195 \DeclareMathSymbol{\mst@varfam@pointvirgule}{\mathalpha}{\mst@font@tbu}{"3B}
1196 \expandafter\mst@addtodo@nonletters\string;\mathpunct\mst@varfam@pointvirgule
1197 \fi
```

\relbar Due to the way = and - are used by LATEX in arrows, we will have to redefine \Relbar and \relbar in order for them to preserve their original meanings.

1.15d: Oct 13, 2012. Belated amendment of the code to be compatible with Unicode engines in case someone changed the mathcode of -. However, for the time being I can do it in an easy way only for XHTEX, not for LualATEX. Also I do my modifications to \relbar in a manner testing for the presence of amsmath.

```
1198 \ifmst@nominus
1199 \else
     \ifmst@XeOrLua
1200
1201
        \mst@Umathcharnumdef\mst@minus@sign=\mst@Umathcodenum'\-\relax
1202 %% I used this prior to the new \luatexUmathcodenum, as available with TL2013:
1203 %% \mathchardef\mst@minus@sign=8704\relax % "2200
     \else
1205
        \mathchardef\mst@minus@sign=\mathcode'\-\relax
1206
      \fi
1207 \@ifpackageloaded{amsmath}
1208 {\def\relbar{\mathrel{\mathpalette\mathsm@sh\mst@minus@sign}}}
1209 {\DeclareRobustCommand\relbar{\mathrel{\smash\mst@minus@sign}}}
1210 \def\rightarrowfill{$\m@th\mathord{\relbar}\mkern-7mu%
1211
      \cleaders\hbox{$\mkern-2mu\relbar\mkern-2mu$}\hfill
      \mkern-7mu\mathord\rightarrow$}
1212
1213 \def\leftarrowfill{$\m@th\mathord\leftarrow\mkern-7mu%
      \cleaders\hbox{$\mkern-2mu\relbar\mkern-2mu$}\hfill
1214
1215
      \mkern-7mu\mathord{\relbar}$}
1216 \fi
```

- endash 1.1 2011/01/29: Producing this next piece of code was not a piece of cake for a novice like myself!
 - $1.11\ 2011/02/05$: Compatibility with Unicode (via use of fontspec encodings EU1 and EU2)
 - 1.12 2011/02/07: Improved dealing of Unicode possibility.
 - $1.14b\ 2011/04/02$: Corrected some very irresponsible bug in the Unicode part which caused a problem when 10 or more math families have been allocated.
 - ${\tt 1.15~2012/09/24:}~{\rm Added~AtBeginDocument~to~circumvent~some~amsmath~problem~with~unicode~engines.}$
 - 1.31 2016/01/29: anticipating TL2016 fontspec's switch to TU.

```
1217 \def\mst@dothe@endashstuff{\edef\mst@tmp@enc{\encodingdefault}
1218 \if1\mst@OneifUniEnc
1219 \AtBeginDocument{% Unicode engines and font
1220 \mst@Umathcode'\-=2 \symmtoperatorfont "2013\relax
1221 \mst@Umathchardef\mst@varfam@minus=7 \symmtoperatorfont "2013\relax
1222 }
1223 \else
1224 \ifx\mst@tmp@enc\mst@ti % T1
```

```
1225
       \DeclareMathSymbol{-}{\mathbin}{mtoperatorfont}{21}
       \DeclareMathSymbol{\mst@varfam@minus}{\mathalpha}{mtoperatorfont}{21}
1226
1227 \else
1228 \ifx\mst@tmp@enc\mst@oti % OT1
1229
       \DeclareMathSymbol{-}{\mathbin}{mtoperatorfont}{123}
1230
       \DeclareMathSymbol{\mst@varfam@minus}{\mathalpha}{mtoperatorfont}{123}
1231 \else
1232 \ifx\mst@tmp@enc\mst@lyi % LY1
       \DeclareMathSymbol{-}{\mathbin}{mtoperatorfont}{150}
1233
1234
       \DeclareMathSymbol{\mst@varfam@minus}{\mathalpha}{mtoperatorfont}{150}
1235 \else % make sure we have neither xetex nor luatex
1236 \ifmst@XeOrLua\mst@aborttrue
1237 \else
       \DeclareMathSymbol{-}{\mathbin}{mtoperatorfont}
1238
1239
       \DeclareMathSymbol{\mst@varfam@minus}{\mathalpha}{mtoperatorfont}
1240 {\expandafter\the\expandafter\csname\mst@tmp@enc\string\textendash\endcsname}
1241 \fi
1242 fififi\}
1243 \def\mst@dothe@emdashstuff{\edef\mst@tmp@enc{\encodingdefault}
1244 \if1\mst@OneifUniEnc
     \AtBeginDocument{% Unicode engine and font
        \mst@Umathcode'\-=2 \symmtoperatorfont "2014\relax
1246
        \mst@Umathchardef\mst@varfam@minus=7 \symmtoperatorfont "2014\relax
1247
     }
1248
1249 \else
1250 \ifx\mst@tmp@enc\mst@ti % T1
       \DeclareMathSymbol{-}{\mathbin}{mtoperatorfont}{22}
1251
1252
       \DeclareMathSymbol{\mst@varfam@minus}{\mathalpha}{mtoperatorfont}{22}
1253 \else
1254 \ifx\mst@tmp@enc\mst@oti % OT1
1255
       \DeclareMathSymbol{-}{\mathbin}{mtoperatorfont}{124}
1256
       \DeclareMathSymbol{\mst@varfam@minus}{\mathalpha}{mtoperatorfont}{124}
1257 \else
1258 \ifx\mst@tmp@enc\mst@lyi % LY1
       \DeclareMathSymbol{-}{\mathbin}{mtoperatorfont}{151}
1259
       \DeclareMathSymbol{\mst@varfam@minus}{\mathalpha}{mtoperatorfont}{151}
1261 \else % make sure we have neither xetex nor luatex
1262 \ifmst@XeOrLua\mst@aborttrue
1263 \else
       \DeclareMathSymbol{-}{\mathbin}{mtoperatorfont}
1264
       \DeclareMathSymbol{\mst@varfam@minus}{\mathalpha}{mtoperatorfont}
1265
1266 {\expandafter\the\expandafter\csname\mst@tmp@enc\string\textemdash\endcsname}
1267 \fi
1268 \fi\fi\fi\fi\}
1269 \ifmst@nominus\else\typeout{** minus as endash}
1270 \mst@abortfalse
1271 \ifmst@endash\mst@dothe@endashstuff\else
1272 \ifmst@emdash\mst@dothe@emdashstuff\else
       \DeclareMathSymbol{-}{\mathbin}{\mst@font@tbu}{"2D}
1273
```

```
1274 \DeclareMathSymbol{\mst@varfam@minus}{\mathalpha}{\mst@font@tbu}{"2D}
1275 \fi\fi
1276 \ifmst@abort
1277 \DeclareMathSymbol{-}{\mathbin}{\mst@font@tbu}{"2D}
1278 \DeclareMathSymbol{\mst@varfam@minus}{\mathalpha}{\mst@font@tbu}{"2D}
1279 \fi
1280 \expandafter\mst@addtodo@nonletters\string-\mathbin\mst@varfam@minus
1281 \fi
```

\hbar 2011/01/31, 1.1 I decide to settle the question of the \hbar. First, the IATEX definition \mst@ltbar 1282 %%\def\hbar{{\mathchar'26\mkern-9muh}} % (original definition from latex.ltx)

Well, the fact is that there is a \DeclareMathSymbol in amsfonts.sty, so I can not always rely on the original which had the advantage that at least h would be in the correct font. But of course not the macron character (\=, \bar). And there is also the issue of the kern whose length is given in a way which depends on cmsy (18mu=1em and em taken from info in cmsy). The first problem is that I don't know how to get the slot position of the macron, given the encoding. So I found another way. I will need an rlap adapted to math mode, and this is provided by code from Alexander R. Perlis in his TugBoat article 22 (2001), 350-352, which I found by googling rlap. (as an aside, I am only now (April 2, 2011) aware that the package mathtools provides the mathrlap etc...)

1.31 2016/01/29: anticipating TL2016 fontspec's switch to TU.

```
1283 \def\mst@mathrlap{\mathpalette\mst@mathrlapinternal}
1284 \def\mst@mathrlapinternal#1#2{\rlap{$\mathsurround=0pt#1{#2}$}}
1285 \def\mst@dothe@hbarstuff{\edef\mst@tmp@enc{\encodingdefault}
1286 \if1\mst@OneifUniEnc
1287
      % Unicode engine and font
1288
      \mst@Umathchardef\hbar="7 \symmtletterfont "0127 \relax %% or 210F?
1289 \else % I must leave open the T1, OT1 possibility also for XeTeX or LuaTeX
       \ifx\mst@ti\mst@tmp@enc
1290
1291
       \DeclareMathAccent{\mst@ltbar}{\mathalpha}{mtletterfont}{9}
1292
          \else \% assume OT1. Bad idea? Should not provoke an error anyhow
1293
       1294
       \def\hbar{\mst@mathrlap{\mst@ltbar{\}}h}
1295
1296 \fi }
1297 \ifmst@nohbar\else\typeout{** \string\hbar}\mst@dothe@hbarstuff\fi
```

As h is from mtletterfont, the accent \mst@ltbar is the \bar accent from that same font. Of course, if the user defines math versions with other encodings than the default one when loading the package this will probably not work there (if I knew how to do for accents what I did for the endash I could do it for all encodings. Surely easy for a TeXpert.) Not to mention if he/she changes the letter shape... one never should give so much freedom to users ;-) Well this construction gives an acceptable result for some of the fonts I have tested, whether upright or in italies

1.15d: Oct 13, 2012. The \mathcode thing with = is (belatedly, sorry!) made Unicode compatible.

```
+,=,\Relbar
```

1298 \ifmst@noplus\else\typeout{** \string+ and \string=}

```
1299 \DeclareMathSymbol{+}{\mathbin}{\mst@font@tbu}{"2B}
1300 \DeclareMathSymbol{\mst@varfam@plus}{\mathalpha}{\mst@font@tbu}{"2B}
1301 \verb|\expandafter\mst@addtodo@nonletters\string+\mathbin\mst@varfam@plus|
1302\fi
1303 \ifmst@noequal\else
1304 \ifmst@XeOrLua
       \mst@Umathcharnumdef\mst@equal@sign=\mst@Umathcodenum'\=\relax
1305
1306 \else
       \mathchardef\mst@equal@sign=\mathcode'\=\relax
1307
1308\fi
1309 \@ifpackageloaded{amsmath}
1310 {\def\Relbar{\mathrel\mst@equal@sign}}
1311 {\DeclareRobustCommand\Relbar{\mathrel{\mst@equal@sign}}}
1312 \DeclareMathSymbol{=}{\mathrel}{\mst@font@tbu}{"3D}
```

\nfss@cat.codes

2012/12/18: Activating = (only in math mode actually) seems very bad but surprisingly works well. However I had a problem with eu2lmtt.fd which should not be loaded with an active =. 2012/12/25: Since then I had switched to only math activation. And in fact the problematic = from eu2lmtt.fd end up in \csname...\endcsname and I have learnt since that TFX does not look at the mathcode inside a \csname...\endcsname. Example:

```
% \mathcode'x="8000
% \begingroup
% \catcode'x=\active
% \global\everymath{\defx{Hello}}
% \endgroup
% \def\foox{World!}
% $x \csname foox\endcsname$
```

We need nevertheless to inactivate the =, for the following reason. Imagine someone did \catcode'==\active\def={\string=}, or another definition which would not lead to a tragedy in a \csname...\endcsname. Then the = is active and the re-definition done by mathastext will not be compatible with loading eu2lmtt.fd (for the first time) from math mode, as this re-definition can not be expanded inside a \csname...\endcsname.

2012/12/28: to be on the safe side, I add also; and + and do it without discriminating between engines

```
1314 \typeout{** adding \string= \string; and \string+ to \string\nfss@catcodes}
1315 \g@addto@macro\nfss@catcodes{%
      \@makeother\=%
1316
      \@makeother\;%
1317
1318
      \@makeother\+%
1319 }
1320 \expandafter\mst@addtodo@nonletters\string=\mathrel\mst@varfam@equal
1321\fi
```

(,),[,],/

noparenthesis \lbrack and \rbrack are defined in latex.ltx by \def\lbrack{[}\def\rbrack{]} so this fits well with what we do here. \lparen and \rparen are similarly defined in mathtools. On the other hand in latex.ltx with \{ and \} are defined (in math mode) in terms of the control sequences \lbrace and \rbrace. Such control sequences can not be simultaneously math symbols and math delimiters, thus, this complicates things for the mathastextification.

```
1322 \ifmst@noparen\else\typeout{** parentheses \string(\string) \string[\string] and slash \s
          1323 \ifmst@nosmalldelims
                   \DeclareMathSymbol{(){\mathopen}{\mst@font@tbu}{"28}
          1324
          1325
                   \DeclareMathSymbol{)}{\mathclose}{\mst@font@tbu}{"29}
                   \DeclareMathSymbol{[]{\mathopen} {\mst@font@tbu}{"5B}
          1326
          1327
                   \DeclareMathSymbol{]}{\mathclose}{\mst@font@tbu}{"5D}
                   \DeclareMathSymbol{/}{\mathord}{\mst@font@tbu}{"2F}
          1328
          1329 \else
                   \DeclareMathDelimiter{(){\mathopen}{\mst@font@tbu}{"28}{largesymbols}{"00}
          1330
          1331
                   \DeclareMathDelimiter{)}{\mathclose}{\mst@font@tbu}{"29}{largesymbols}{"01}
          1332
                   \DeclareMathDelimiter{[]}{\mathopen} {\mst@font@tbu}{"5B}{largesymbols}{"02}
                   \DeclareMathDelimiter{]}{\mathclose}{\mst@font@tbu}{"5D}{largesymbols}{"03}
          1333
                   \DeclareMathDelimiter{/}{\mathord}{\mst@font@tbu}{"2F}{largesymbols}{"0E}
          1334
          1335 \fi
          1336 \DeclareMathSymbol{\mst@varfam@lparen}{\mathalpha}{\mst@font@tbu}{40}
          1337 \DeclareMathSymbol{\mst@varfam@rparen}{\mathalpha}{\mst@font@tbu}{41}
          1338 \DeclareMathSymbol{\mst@varfam@lbrack}{\mathalpha}{\mst@font@tbu}{"5B}
          1339 \DeclareMathSymbol{\mst@varfam@rbrack}{\mathalpha}{\mst@font@tbu}{"5D}
          1340 \DeclareMathSymbol{\mst@varfam@slash}{\mathalpha}{\mst@font@tbu}{"2F}
          1341 \expandafter\mst@addtodo@nonletters\string(\mathopen\mst@varfam@lparen
          1342 \expandafter\mst@addtodo@nonletters\string)\mathclose\mst@varfam@rparen
          1343 \expandafter\mst@addtodo@nonletters\string[\mathopen\mst@varfam@lbrack
          1344 \expandafter\mst@addtodo@nonletters\string]\mathclose\mst@varfam@rbrack
           1345 \mst@addtodo@easynonletters\/\mst@varfam@slash
          1346\fi
     <,>,\1347\ifmst@alldelims\typeout{** alldelims: \string< \string>
 \setminus 1348
                \string\backslash\space\string\setminus\space\string|
\backslash <sub>1349</sub>
                \string\vert\space\string\mid\space\string\{\space and \string\}}
          1350 \ifmst@nosmalldelims
            Dec 18, 2012. We then want \let\backslash\mst@varfam@backslash to do nothing when the
            \backslash is used as a delimiter. So here the original definition from latex.ltx is copied,
            generally speaking when people use other math symbol fonts they do respect the encoding of
            the CM symbols and largesymbols, so this is 90% safe. But in truth I should extract from the
            meaning of \backslash the delcode.
          1351
                   \DeclareMathDelimiter{\mst@varfam@backslash}
                       {\mathalpha}{symbols}{"6E}{largesymbols}{"0F}
          1352
          1353 \else
                   \DeclareMathDelimiter{<}{\mathopen}{\mst@font@tbu}{"3C}{largesymbols}{"0A}
          1354
```

```
\DeclareMathDelimiter{>}{\mathclose}{\mst@font@tbu}{"3E}{largesymbols}{"0B}
1355
  There is no backslash in the Symbol font hence mtoperatorfont here.
```

alldelims

\DeclareMathDelimiter{\backslash} 1356 1357 {\mathord}{mtoperatorfont}{"5C}{largesymbols}{"0F} \DeclareMathDelimiter{\mst@varfam@backslash} 1358

{\mathalpha}{mtoperatorfont}{"5C}{largesymbols}{"0F} 1359

```
1360\fi
                  1361 \DeclareMathSymbol{<}{\mathrel}{\mst@font@tbu}{"3C}
                  1362 \DeclareMathSymbol{>}{\mathrel}{\mst@font@tbu}{"3E}
                  1363 \DeclareMathSymbol{\mst@varfam@less}{\mathalpha}{\mst@font@tbu}{"3C}
                  1364 \DeclareMathSymbol{\mst@varfam@more}{\mathalpha}{\mst@font@tbu}{"3E}
                  1365 \expandafter\mst@addtodo@nonletters\string<\mathrel\mst@varfam@less
                  1367 \mst@do@easynonletters\expandafter{\the\mst@do@easynonletters
                                  \let\backslash\mst@varfam@backslash}
                  1369 \DeclareMathSymbol{\setminus}{\mathbin}{mtoperatorfont}{"5C}
                  1370 \DeclareMathSymbol{\mst@varfam@setminus}{\mathalpha}{mtoperatorfont}{"5C}
                  1371 \mst@do@nonletters\expandafter{\the\mst@do@nonletters
                                  \def\setminus{\mathbin{\mst@varfam@setminus}}}
                  1372
           \models 1.15d: 13 oct 2012. Before modifying | we must preserve \models.
                  1373 \ifmst@XeOrLua
                       \mst@Umathcharnumdef\mst@vert@bar=\mst@Umathcodenum'\|\relax
                  1374
                  1375 \else
                  1376 \mathchardef\mst@vert@bar=\mathcode'\|\relax
                  1377 \fi
                  1378 \DeclareRobustCommand\models{\mathrel{\mst@vert@bar}\joinrel\Relbar}
      ,\mid,\vert (2011) I did not do anything then to try to emulate \Vert with the vertical bar from the text
                    font... and now (2012) mathastext is not as radical as it used to be anyhow, so it is too late.
                  1379 \ifmst@nosmalldelims
                          \DeclareMathSymbol{|}{\mathord}{\mst@font@tbu}{124}
                  1380
                  1381 \else
                          \DeclareMathDelimiter{|}{\mathord}{\mst@font@tbu}{124}{largesymbols}{"OC}
                  1382
                  1383 \fi
                  1384 \def\vert{|}
                  1386 \mst@addtodo@easynonletters\|\mst@varfam@vbar
                  1387 \let\mid\undefined % 1.3: to avoid problems with some packages
                  1388 \DeclareMathSymbol{\mid}{\mathrel}{\mst@font@tbu}{124}
                  1389 \mst@do@nonletters\expandafter{\the\mst@do@nonletters
                          \def\mid{\mathrel\mst@varfam@vbar}}
                   Braces. With version 1.2, \{ and \} will not be acceptable as delimiters anymore if the redefi-
\MTexplicitbraces-
       obeymathxx
                   nitions below in \mst@dobraces are enacted. But they will obey math alphabets. Improvements
\MTexplicitbraces-
                   in 1.2a, to preserve robustness.
   donotobeymathxx
                      For 1.3 I make \lbrace and \rbrace undefined first, else problems may arise with some
                    packages. 1.3e suppresses under option nosmalldelims the definitions of \lbrace and \rbrace
                    as math symbols as this bug made \left\lbrace cause an error, naturally.
                        \ifmst@nosmalldelims
                  1391
                  1392
                        \else
                           \let\lbrace\undefined \let\rbrace\undefined
                  1393
                           \DeclareMathDelimiter{\lbrace}
                  1394
                  1395
                              {\mathopen}{\mst@font@tbu}{123}{largesymbols}{"08}
                           \DeclareMathDelimiter{\rbrace}
```

1396

```
{\mathclose}{\mst@font@tbu}{125}{largesymbols}{"09}
1397
1398
      \fi
1399 \DeclareMathSymbol{\mst@varfam@lbrace}{\mathalpha}{\mst@font@tbu}{123}
1400 \DeclareMathSymbol{\mst@varfam@rbrace}{\mathalpha}{\mst@font@tbu}{125}
1401 \DeclareRobustCommand*{\mst@lbrace}
1402
            {\ifmmode\mathopen\mst@varfam@lbrace\else\textbraceleft\fi}
1403 \DeclareRobustCommand*{\mst@rbrace}
            {\ifmmode\mathclose\mst@varfam@rbrace\else\textbraceright\fi}
1404
1405 \mst@do@nonletters\expandafter{\the\mst@do@nonletters
1406
        \mst@dobraces{\let\{\mst@lbrace\let\}\mst@rbrace}}
1407 \fi % end of \ifmst@alldelims
1408 \newcommand*{\MTexplicitbracesobeymathxx}{\let\mst@dobraces\@firstofone}
1409 \newcommand*{\MTexplicitbracesdonotobeymathxx}{\let\mst@dobraces\@gobble}
1410 \MTexplicitbracesdonotobeymathxx
```

specials

- 1.14b 2011/04/02: the redefinitions of #, \$, % and & were buggy (this showed up when 10 or more math families had been created).
- 1.15f 2012/10/23: the code, although working, was perhaps a bit insane and had definitions which could surprise other packages. For example, it did:

\renewcommand{\\%}{\ifmmode\mt@mmode@percent\else\char37\relax\fi}

But it seems this provokes a problem with microtype. Perhaps the problem was that the command was not declared robust? For the dollar LATEX itself does

\DeclareRobustCommand{\\$}{\ifnmode\mathdollar\else\textdollar\fi}

- 1.2d 2013/01/01: previous versions imposed the variable family type. I hereby make it possible to de-activate this feature with the macro $\MTeasynonlettersdonotobeymathxx$. Besides, I have absolutely no idea why I had different looking code depending on the engine $X_{\overline{A}}T_{\overline{E}}X$, Lua $T_{\overline{E}}X$ or default. Removed.
- 1.3c 2013/12/14: I have absolutely no idea why I removed the XHTEX and LuaTEX code at the time of 1.2d! the code for tex/pdftex engine could not accommodate more than 16 math families. Code for XHTEX and LuaTEX again added. (and since TL2013 no more problems with \luatexUmathcode.)

```
1411 \ifmst@nospecials
1412 \else
       \typeout{** \string\#\space\string\mathdollar\space
1413
                    \string\%\space\string\&\space}
1414
1415
      \ifmst@XeOrLua
      \mst@Umathcode'\#=0 \symmtoperatorfont "23 \relax
1416
      \mst@Umathchardef\mathdollar=0 \symmtoperatorfont "24 \relax
1417
      \mst@Umathcode'\%=0 \symmtoperatorfont "25 \relax
1418
      \mst@Umathcode'\&=0 \symmtoperatorfont "26 \relax
1419
1420
      \mst@do@easynonletters\expandafter{%
        \the\mst@do@easynonletters
1421
        \mst@Umathcode'\#=7 \symmtoperatorfont "23 \relax
1422
```

```
\mst@Umathchardef\mathdollar=7 \symmtoperatorfont "24 \relax
1423
1424
        \mst@Umathcode'\%=7 \symmtoperatorfont "25 \relax
        \mst@Umathcode'\&=7 \symmtoperatorfont "26 \relax
1425
        }
1426
1427
      \else
1428
      \count@=\symmtoperatorfont
      \multiply\count@ by \@cclvi
1429
      \advance\count@ by 35
1430
          \mathcode'\#\count@
1431
1432
      \advance\count@ by \@ne
          \mathchardef\mathdollar\count@
1433
      \advance\count@ by \@ne
1434
          \mathcode'\%\count@
1435
      \advance\count@ by \@ne
1436
1437
          \mathcode'\&\count@
1438
      \count@=\symmtoperatorfont
      \multiply\count@ by \@cclvi
1439
      \advance\count0 by 28707 % = "7023
1440
          \mathchardef\mst@varfam@mathhash\count@
1441
1442
      \advance\count@ by \@ne
1443
          \mathchardef\mst@varfam@mathdollar\count@
      \advance\count@ by \@ne
1444
          \mathchardef\mst@varfam@mathpercent\count@
1445
      \advance\count@ by \@ne
1446
1447
          \mathchardef\mst@varfam@mathampersand\count@
      \mst@do@easynonletters\expandafter{\the\mst@do@easynonletters
1448
        \mathcode'\#=\mst@varfam@mathhash
1449
        \let\mathdollar\mst@varfam@mathdollar
1450
1451
        \mathcode'\%=\mst@varfam@mathpercent
        \mathcode '\&=\mst@varfam@mathampersand}
1452
1453
      \fi
1454\fi
```

symbolmisc

We construct (with some effort) some long arrows from the Symbol glyphs, of almost the same lengths as the standard ones. By the way, I always found the \iff to be too wide, but I follow here the default. Also, although there is a \longmapsto in standard LATEX, if I am not mistaken, there is no \longto. So I define one here. I could not construct in the same manner \Longrightarrow etc... as the = sign from Symbol does not combine easily with the logical arrows, well, I could have done some box manipulations, but well, life is finite.

\prod

1.13b: I correct the brutal re-definitions of \prod and \sum from the earlier versions of the package; most of the time the Symbol glyphs do appear to be too small in display mode. The new redefinitions do have some defects: \$\displaystyle\prod_1^2\$ changes the position of limits but not the glyph itself, and \$\$\textstyle\prod_1^2\$\$ change the limits but switches to the CM inline math glyph. So I tried

\renewcommand{\prod}{\mathchoice{\mst@prod}{\prodpsy}{\prodpsy}}\but this did not go well with subscripts and exponents.

Note oct 2012: maybe I should re-examine what I did? 1.3c (2013/12/14) renames \defaultprod to \MToriginalprod and \defaultsum to \MToriginalsum.

```
1455 \ifmst@symbolmisc\typeout{** symbolmisc: miscellaneous math symbols from Symbol font}
1456 \let\mst@prod\prod
1457 \let\MToriginalprod\prod
1458 \DeclareMathSymbol{\prodpsy}{\mathop}{mtpsymbol}{213}
1459 \renewcommand*{\prod}{\ifinner\prodpsy\else\mst@prod\fi}
1460 \let\mst@sum\sum
1461 \let\MToriginalsum\sum
1462 \ensuremath Symbol {\sumpsy} {\mbon} {\
1463 \renewcommand*{\sum}{\ifinner\sumpsy\else\mst@sum\fi}
1464 \DeclareMathSymbol{\mst@implies}{\mathrel}{mtpsymbol}{222}
1465 \DeclareRobustCommand*{\implies}{\;\mst@implies\;}
1466 \DeclareMathSymbol \\mst@impliedby \\mathrel \\ mtpsymbol \\ 220 \\
1467 \DeclareRobustCommand*{\impliedby}{\;\mst@impliedby\;}
1468 \DeclareRobustCommand*{\iff}{\;\mst@impliedby\mathrel{\mkern-3mu}\mst@implies\;}
1469 \DeclareMathSymbol{\mst@iff}{\mathrel}{mtpsymbol}{219}
1470 \DeclareRobustCommand*{\shortiff}{\;\mst@iff\;}
1471 \DeclareMathSymbol{\mst@to}{\mathrel}{mtpsymbol}{174}
1472 \DeclareMathSymbol{\mst@trait}{\mathrel}{mtpsymbol}{190}
1473 \DeclareRobustCommand*\to{\mst@to}
1474 \DeclareRobustCommand*\longto{\mkern2mu\mst@trait\mathrel{\mkern-10mu}\mst@to}
1475 \DeclareRobustCommand*\mapsto{\mapstochar\mathrel{\mkern0.2mu}\mst@to}
1476 \DeclareRobustCommand*\longmapsto{%
1477 \mapstochar\mathrel{\mkern2mu}\mst@trait\mathrel{\mkern-10mu}\mst@to}
1478 \DeclareMathSymbol{\aleph}{\mathord}{mtpsymbol}{192}
1479 \DeclareMathSymbol{\inftypsy}{\mathord}{mtpsymbol}{165}
1480 \DeclareMathSymbol{\emptyset}{\mathord}{mtpsymbol}{198}
1481 \let\varnothing\emptyset
1482 \end{\text{\colored}} {\bf 1482 \colored} {\bf 14
1483 \DeclareMathSymbol{\surd}{\mathop}{mtpsymbol}{214}
1484 \let\angle\undefined
1485 \DeclareMathSymbol{\angle}{\mathord}{mtpsymbol}{208}
1486 \ensuremath Symbol {\ensuremaths ymbol} {\en
1487 \DeclareMathSymbol{\exists}{\mathord}{mtpsymbol}{36}
1488 \DeclareMathSymbol{\neg}{\mathord}{mtpsymbol}{216}
1489 \DeclareMathSymbol{\clubsuit}{\mathord}{mtpsymbol}{167}
1490 \DeclareMathSymbol{\diamondsuit}{\mathord}{mtpsymbol}{168}
1491 \DeclareMathSymbol{\heartsuit}{\mathord}{mtpsymbol}{169}
1492 \DeclareMathSymbol{\spadesuit}{\mathord}{mtpsymbol}{170}
1493 \DeclareMathSymbol{\smallint}{\mathop}{mtpsymbol}{242}
1494 \DeclareMathSymbol{\wedge}{\mathbin}{mtpsymbol}{217}
1495 \DeclareMathSymbol{\vee}{\mathbin}{mtpsymbol}{218}
1496 \DeclareMathSymbol{\cap}{\mathbin}{mtpsymbol}{199}
1497 \DeclareMathSymbol{\cup}{\mathbin}{mtpsymbol}{200}
1498 \DeclareMathSymbol{\bullet}{\mathbin}{mtpsymbol}{183}
1499 \DeclareMathSymbol{\div}{\mathbin}{mtpsymbol}{184}
1500 \DeclareMathSymbol{\otimes}{\mathbin}{mtpsymbol}{196}
1501 \DeclareMathSymbol{\oplus}{\mathbin}{mtpsymbol}{197}
1502 \DeclareMathSymbol{\pm}{\mathbin}{mtpsymbol}{177}
```

```
1503 \DeclareMathSymbol{\times}{\mathbin}{mtpsymbol}{180}
              1504 \DeclareMathSymbol{\proptopsy}{\mathrel}{mtpsymbol}{181}
              1505 \DeclareMathSymbol{\mid}{\mathrel}{mtpsymbol}{124}
              1506 \DeclareMathSymbol{\leq}{\mathrel}{mtpsymbol}{163}
              1507 \DeclareMathSymbol{\geq}{\mathrel}{mtpsymbol}{179}
              1508 \DeclareMathSymbol{\approx}{\mathrel}{mtpsymbol}{187}
              1509 \DeclareMathSymbol{\supset}{\mathrel}{mtpsymbol}{201}
              1510 \DeclareMathSymbol{\subset}{\mathrel}{mtpsymbol}{204}
              1511 \DeclareMathSymbol{\supseteq}{\mathrel}{mtpsymbol}{202}
              1512 \DeclareMathSymbol{\subseteq}{\mathrel}{mtpsymbol}{205}
              1513 \DeclareMathSymbol{\in}{\mathrel}{mtpsymbol}{206}
              1514 \DeclareMathSymbol{\sim}{\mathrel}{mtpsymbol}{126}
              1515 \let\cong\undefined
              1516 \DeclareMathSymbol{\cong}{\mathrel}{mtpsymbol}{64}
              1517 \DeclareMathSymbol{\perp}{\mathrel}{mtpsymbol}{94}
              1518 \DeclareMathSymbol{\equiv}{\mathrel}{mtpsymbol}{186}
              1519 \let\notin\undefined
              1520 \DeclareMathSymbol{\notin}{\mathrel}{mtpsymbol}{207}
              1521 \DeclareMathDelimiter{\rangle}
                     {\mathclose}{mtpsymbol}{241}{largesymbols}{"OB}
              1523 \DeclareMathDelimiter{\langle}
                     {\mathopen}{mtpsymbol}{225}{largesymbols}{"OA}
              1524
              1525\fi
     symbolre I like the \Re and \Im from Symbol, so I overwrite the CM ones.
              1526 \ifmst@symbolre\typeout{** symbolre: \string\Re\space and \string\Im\space from Sym
              1527 \DeclareMathSymbol{\Re}{\mathord}{mtpsymbol}{"C2}
              1528 \DeclareMathSymbol{\Im}{\mathord}{mtpsymbol}{"C1}
              1529 \DeclareMathSymbol{\DotTriangle}{\mathord}{mtpsymbol}{92}
              1530\fi
Greek letters LGRgreek > selfGreek > eulergreek > symbolgreek
                  1.11 I correct some bugs on how eulergreek and symbolgreek interacted.
                  1.12b more bug fixes.
                  1.13
                  * Option LGRgreek.
                  * Also, a behavior has been changed: it regards the selfGreek case, the default shape is now
                the one for letters, not for operator-names and digits. This complies to the ISO standard.
                  * bugfix: version 1.12b did not define the \omicron in the case when no Greek-related option
                was passed to the package.
                  1.13d has new macros \MTstandardgreek and \MTcustomgreek. And in the subdued case
                \MTstandardgreek is done when switching to the normal or bold math versions (previously
                something like this was only done in case of LGRgreek option.)
              1531 \let\mst@mathord\mathalpha
              1532 \mst@goaheadtrue
              1533 \ifmst@selfGreek
              1534
                      \def\mst@font@tbu{mtselfGreekfont}
              1535 \else
```

```
\ifmst@eulergreek
1536
1537
             \def\mst@font@tbu{mteulervm}
1538
        \else
1539
           \ifmst@symbolgreek
1540
             \def\mst@font@tbu{mtpsymbol}
1541
             \let\mst@mathord\mathord
           \else
1542
              \ifmst@LGRgreek
1543
                 \mst@goaheadfalse
1544
1545
```

The \omicron requires special treatment. By default we use the o from the (original) normal alphabet, if eulergreek or symbolgreek we adapt. There is also a special adjustment if the package fourier was loaded in its upright variant: we then take \omicron from the (original) rm alphabet.

```
\mst@goaheadfalse
1546
             \def\mst@omicron {\mst@alph@omicron{o}}
1547
1548
         \fi
1549
      \fi
1550
1551\fi
1552 \ifmst@goahead
     \DeclareMathSymbol{\mst@Alpha}{\mst@mathord}{\mst@font@tbu}{"41}
1553
     1554
1555
     \DeclareMathSymbol{\mst@Epsilon}{\mst@mathord}{\mst@font@tbu}{"45}
     \DeclareMathSymbol{\mst@Zeta}{\mst@mathord}{\mst@font@tbu}{"5A}
1556
     \DeclareMathSymbol{\mst@Eta}{\mst@mathord}{\mst@font@tbu}{"48}
1557
     \DeclareMathSymbol{\mst@Iota}{\mst@mathord}{\mst@font@tbu}{"49}
1558
1559
     \DeclareMathSymbol{\mst@Kappa}{\mst@mathord}{\mst@font@tbu}{"4B}
1560
     \DeclareMathSymbol{\mst@Mu}{\mst@mathord}{\mst@font@tbu}{"4D}
     \DeclareMathSymbol{\mst@Nu}{\mst@mathord}{\mst@font@tbu}{"4E}
1561
     \DeclareMathSymbol{\mst@Omicron}{\mst@mathord}{\mst@font@tbu}{"4F}
1562
     \DeclareMathSymbol{\mst@Rho}{\mst@mathord}{\mst@font@tbu}{"50}
1563
     \DeclareMathSymbol{\mst@Tau}{\mst@mathord}{\mst@font@tbu}{"54}
1564
     1565
```

When we in fact use Symbol, we have to correct \Rho and \Chi. And \Digamma is non-existent in fact (no F in Symbol, F codes a \Phi).

1566 \ifx\mst@mathord\mathord

symbolgreek but neither eulergreek nor selfGreek

```
1567 %% attention le P de Symbol est un \Pi pas un \Rho
        \DeclareMathSymbol{\mst@Rho}{\mathord}{mtpsymbol}{"52}
1569 %% attention le X de Symbol est un \Xi pas un \Chi
1570
        \DeclareMathSymbol{\mst@Chi}{\mathord}{mtpsymbol}{"43}
1571 %% attention le F de Symbol est un \Phi. Il n'y a pas de \Digamma
        \DeclareMathSymbol{\mst@Gamma}{\mathord}{mtpsymbol}{"47}
1572
1573
        \DeclareMathSymbol{\mst@Delta}{\mathord}{mtpsymbol}{"44}
        \DeclareMathSymbol{\mst@Theta}{\mathord}{mtpsymbol}{"51}
1574
        \DeclareMathSymbol{\mst@Lambda}{\mathord}{mtpsymbol}{"4C}
1575
        \DeclareMathSymbol{\mst@Xi}{\mathord}{mtpsymbol}{"58}
1576
```

```
\DeclareMathSymbol{\mst@Pi}{\mathord}{mtpsymbol}{"50}
1577
1578
        \DeclareMathSymbol{\mst@Sigma}{\mathord}{mtpsymbol}{"53}
        \DeclareMathSymbol{\mst@Upsilon}{\mathord}{mtpsymbol}{"A1}
1579
        \DeclareMathSymbol{\mst@Phi}{\mathord}{mtpsymbol}{"46}
1580
1581
        \DeclareMathSymbol{\mst@Psi}{\mathord}{mtpsymbol}{"59}
1582
        \DeclareMathSymbol{\mst@Omega}{\mathord}{mtpsymbol}{"57}
      \else % de \mst@mathord=\mathord
1583
```

not symbolgreek but eulergreek or selfGreek. Note 2015/10/31: apparemment à un moment dans le passé je considérais eulergreek et selfGreek comme pouvant être utilisés simultanément car j'avais ici "or both". Mais je laisse tomber tout effort réel de m'en préoccuper.

```
\DeclareMathSymbol\mst@Digamma
                                         {\mathalpha}{\mst@font@tbu}{"46}
1584
1585
        \DeclareMathSymbol\mst@Gamma
                                          {\mathalpha}{\mst@font@tbu}{"00}
1586
        \DeclareMathSymbol\mst@Delta
                                          {\mathalpha}{\mst@font@tbu}{"01}
        \DeclareMathSymbol\mst@Theta
                                          {\mathalpha}{\mst@font@tbu}{"02}
1587
        \DeclareMathSymbol\mst@Lambda
                                          {\mathalpha}{\mst@font@tbu}{"03}
1588
        \DeclareMathSymbol\mst@Xi
                                          {\mathalpha}{\mst@font@tbu}{"04}
1589
1590
        \DeclareMathSymbol\mst@Pi
                                          {\mathalpha}{\mst@font@tbu}{"05}
        \DeclareMathSymbol\mst@Sigma
                                          {\mathalpha}{\mst@font@tbu}{"06}
1591
1592
        \DeclareMathSymbol\mst@Upsilon
                                          {\mathalpha}{\mst@font@tbu}{"07}
        \DeclareMathSymbol\mst@Phi
                                          {\mathalpha}{\mst@font@tbu}{"08}
1593
        \DeclareMathSymbol\mst@Psi
                                          {\mathalpha}{\mst@font@tbu}{"09}
1594
        \DeclareMathSymbol\mst@Omega
                                          {\mathalpha}{\mst@font@tbu}{"OA}
1595
1596
      \fi % de \mst@mathord=\mathord
```

1597 \fi % fin de goahead

There are differences regarding Euler and Symbol with respect to the available var-letters. We include one or two things like the wp and the partial.

The lower case Greek letters in default LATEX are of type mathord. If we use the Euler font it is perhaps better to have them be of type mathalpha

```
1598 \ifmst@goahead
1599
     \ifmst@eulergreek
      \DeclareMathSymbol{\mst@alpha}
                                       {\mathalpha}{mteulervm}{"OB}
1600
1601
      \DeclareMathSymbol{\mst@beta}
                                        {\mathalpha}{mteulervm}{"OC}
      \DeclareMathSymbol{\mst@gamma}
                                        {\mathalpha}{mteulervm}{"OD}
1602
1603
      \DeclareMathSymbol{\mst@delta}
                                        {\mathalpha}{mteulervm}{"OE}
1604
      \DeclareMathSymbol{\mst@epsilon}{\mathalpha}{mteulervm}{"OF}
1605
      \DeclareMathSymbol{\mst@zeta}
                                        {\mathalpha}{mteulervm}{"10}
      \DeclareMathSymbol{\mst@eta}
                                        {\mathalpha}{mteulervm}{"11}
1606
1607
      \DeclareMathSymbol{\mst@theta}
                                       {\mathalpha}{mteulervm}{"12}
1608
      \DeclareMathSymbol{\mst@iota}
                                        {\mathalpha}{mteulervm}{"13}
      \DeclareMathSymbol{\mst@kappa}
1609
                                        {\mathalpha}{mteulervm}{"14}
      \DeclareMathSymbol{\mst@lambda}
                                       {\mathalpha}{mteulervm}{"15}
1610
1611
      \DeclareMathSymbol{\mst@mu}
                                        {\mathalpha}{mteulervm}{"16}
1612
      \DeclareMathSymbol{\mst@nu}
                                        {\mathalpha}{mteulervm}{"17}
1613
      \DeclareMathSymbol{\mst@xi}
                                        {\mathalpha}{mteulervm}{"18}
1614
      \DeclareMathSymbol{\mst@omicron}{\mathalpha}{mteulervm}{"6F}
      \DeclareMathSymbol{\mst@pi}
                                        {\mathalpha}{mteulervm}{"19}
1615
1616
      \DeclareMathSymbol{\mst@rho}
                                        {\mathalpha}{mteulervm}{"1A}
      \DeclareMathSymbol{\mst@sigma}
                                       {\mathalpha}{mteulervm}{"1B}
1617
```

```
1618
      \DeclareMathSymbol{\mst@tau}
                                       {\mathalpha}{mteulervm}{"1C}
1619
      \DeclareMathSymbol{\mst@upsilon}{\mathalpha}{mteulervm}{"1D}
1620
      \DeclareMathSymbol{\mst@phi}
                                       {\mathalpha}{mteulervm}{"1E}
1621
      \DeclareMathSymbol{\mst@chi}
                                       {\mathalpha}{mteulervm}{"1F}
1622
      \DeclareMathSymbol{\mst@psi}
                                       {\mathalpha}{mteulervm}{"20}
1623
      \DeclareMathSymbol{\mst@omega}
                                       {\mathalpha}{mteulervm}{"21}
1624 %
      \DeclareMathSymbol{\mst@varepsilon}{\mathalpha}{mteulervm}{"22}
1625
      \DeclareMathSymbol{\mst@vartheta}{\mathalpha}{mteulervm}{"23}
1626
1627
      \DeclareMathSymbol{\mst@varpi} {\mathalpha}{mteulervm}{"24}
      \let\mst@varrho=\mst@rho
1628
1629
      \let\mst@varsigma=\mst@sigma
      \DeclareMathSymbol{\mst@varphi} {\mathalpha}{mteulervm}{"27}
1630
1631 %
      \DeclareMathSymbol{\mst@partial}{\mathalpha}{mteulervm}{"40}
1632
1633
      \DeclareMathSymbol{\mst@wp}{\mathalpha}{mteulervm}{"7D}
      \DeclareMathSymbol{\mst@ell}{\mathalpha}{mteulervm}{"60}
1634
1635
     \else
      \ifmst@symbolgreek
1636
      \DeclareMathSymbol{\mst@alpha}{\mathord}{mtpsymbol}{"61}
1637
1638
      \DeclareMathSymbol{\mst@beta}{\mathord}{mtpsymbol}{"62}
      \DeclareMathSymbol{\mst@gamma}{\mathord}{mtpsymbol}{"67}
1639
      \DeclareMathSymbol{\mst@delta}{\mathord}{mtpsymbol}{"64}
1640
1641
      \DeclareMathSymbol{\mst@epsilon}{\mathord}{mtpsymbol}{"65}
1642
      \DeclareMathSymbol{\mst@zeta}{\mathord}{mtpsymbol}{"7A}
1643
      \DeclareMathSymbol{\mst@eta}{\mathord}{mtpsymbol}{"68}
      \DeclareMathSymbol{\mst@theta}{\mathord}{mtpsymbol}{"71}
1644
      \DeclareMathSymbol{\mst@iota}{\mathord}{mtpsymbol}{"69}
1645
1646
      \DeclareMathSymbol{\mst@kappa}{\mathord}{mtpsymbol}{"6B}
      \DeclareMathSymbol{\mst@lambda}{\mathord}{mtpsymbol}{"6C}
1647
1648
      \DeclareMathSymbol{\mst@mu}{\mathord}{mtpsymbol}{"6D}
1649
      \DeclareMathSymbol{\mst@nu}{\mathord}{mtpsymbol}{"6E}
1650
      \DeclareMathSymbol{\mst@xi}{\mathord}{mtpsymbol}{"78}
      \DeclareMathSymbol{\mst@omicron}{\mathord}{mtpsymbol}{"6F}
1651
      \DeclareMathSymbol{\mst@pi}{\mathord}{mtpsymbol}{"70}
1652
1653
      \DeclareMathSymbol{\mst@rho}{\mathord}{mtpsymbol}{"72}
1654
      \DeclareMathSymbol{\mst@sigma}{\mathord}{mtpsymbol}{"73}
      \DeclareMathSymbol{\mst@tau}{\mathord}{mtpsymbol}{"74}
1655
1656
      \DeclareMathSymbol{\mst@upsilon}{\mathord}{mtpsymbol}{"75}
      \DeclareMathSymbol{\mst@phi}{\mathord}{mtpsymbol}{"66}
1657
      \DeclareMathSymbol{\mst@chi}{\mathord}{mtpsymbol}{"63}
1658
1659
      \DeclareMathSymbol{\mst@psi}{\mathord}{mtpsymbol}{"79}
1660
      \DeclareMathSymbol{\mst@omega}{\mathord}{mtpsymbol}{"77}
1661
      \let\mst@varepsilon=\mst@epsilon
      \DeclareMathSymbol{\mst@vartheta}{\mathord}{mtpsymbol}{"4A}
1662
      \DeclareMathSymbol{\mst@varpi}{\mathord}{mtpsymbol}{"76}
1663
1664
      \let\mst@varrho=\mst@rho
1665
      \DeclareMathSymbol{\mst@varsigma}{\mathord}{mtpsymbol}{"56}
      \DeclareMathSymbol{\mst@varphi}{\mathord}{mtpsymbol}{"6A}
1666
```

```
\DeclareMathSymbol{\mst@partial}{\mathord}{mtpsymbol}{"B6}
1667
1668
      \DeclareMathSymbol{\mst@wp}{\mathord}{mtpsymbol}{"C3}
     \fi
1669
1670 \fi
1671\fi
1672 \ifmst@LGRgreek
1673 % cf http://milde.users.sourceforge.net/LGR/lgrxenc.def.html
1674 % et greek.ldf du package babel
1675 \DeclareMathSymbol{\mst@Alpha}{\mathalpha}{\mtlgrfontupper}{65}
1676 \DeclareMathSymbol{\mst@Beta}{\mathalpha}{\mtlgrfontupper}{66}
1677 \DeclareMathSymbol{\mst@Epsilon}{\mathalpha}{mtlgrfontupper}{69}
1678 \DeclareMathSymbol \mst@Zeta \mathalpha \mtlgrfontupper \{90\
1679 \DeclareMathSymbol{\mst@Eta}{\mathalpha}{mtlgrfontupper}{72}
1680 \DeclareMathSymbol{\mst@Iota}{\mathalpha}{mtlgrfontupper}{73}
1681 \DeclareMathSymbol{\mst@Kappa}{\mathalpha}{mtlgrfontupper}{75}
1682 \DeclareMathSymbol{\mst@Mu}{\mathalpha}{mtlgrfontupper}{77}
1683 \DeclareMathSymbol \mst@Nu \{\mathalpha\{mtlgrfontupper\} \{78\}
1684 \DeclareMathSymbol \\mst@Omicron \ \mathalpha \ \mtlgrfontupper \ \ 79\
1685 \DeclareMathSymbol{\mst@Rho}{\mathalpha}{mtlgrfontupper}{82}
1686 \DeclareMathSymbol{\mst@Tau}{\mathalpha}{mtlgrfontupper}{84}
1687 \DeclareMathSymbol{\mst@Chi}{\mathalpha}{mtlgrfontupper}{81}
1688 %
1689 \DeclareMathSymbol{\mst@Digamma}{\mathalpha}{mtlgrfontlower}{195}
1690 %
1691 \DeclareMathSymbol{\mst@Gamma}{\mathalpha}{mtlgrfontupper}{71}
1692 \DeclareMathSymbol{\mst@Delta}{\mathalpha}{mtlgrfontupper}{68}
1693 \DeclareMathSymbol{\mst@Theta}{\mathalpha}{mtlgrfontupper}{74}
1694 \DeclareMathSymbol{\mst@Lambda}{\mathalpha}{mtlgrfontupper}{76}
1695 \DeclareMathSymbol{\mst@Xi}{\mathalpha}{mtlgrfontupper}{88}
1696 \DeclareMathSymbol{\mst@Pi}{\mathalpha}{mtlgrfontupper}{80}
1697 \DeclareMathSymbol{\mst@Sigma}{\mathalpha}{mtlgrfontupper}{83}
1698 \DeclareMathSymbol{\mst@Upsilon}{\mathalpha}{mtlgrfontupper}{85}
1699 \DeclareMathSymbol{\mst@Phi}{\mathalpha}{mtlgrfontupper}{70}
1700 \DeclareMathSymbol{\mst@Psi}{\mathalpha}{mtlgrfontupper}{89}
1701 \DeclareMathSymbol{\mst@Omega}{\mathalpha}{mtlgrfontupper}{87}
1703 \DeclareMathSymbol{\mst@alpha}{\mathalpha}{mtlgrfontlower}{97}
1704 \DeclareMathSymbol{\mst@beta}{\mathalpha}{mtlgrfontlower}{98}
1705 \DeclareMathSymbol{\mst@gamma}{\mathalpha}{mtlgrfontlower}{103}
1706 \DeclareMathSymbol{\mst@delta}{\mathalpha}{mtlgrfontlower}{100}
1707 \DeclareMathSymbol{\mst@epsilon}{\mathalpha}{mtlgrfontlower}{101}
1709 \DeclareMathSymbol \mst@eta \ (\mathalpha) \{mtlgrfontlower \} \{104\}
1710 \DeclareMathSymbol \mst@theta \ (\mathalpha) \{mtlgrfontlower \} \{106\}
1711 \DeclareMathSymbol{\mst@iota}{\mathalpha}{mtlgrfontlower}{105}
1712 \DeclareMathSymbol \mst@kappa \ (\mathalpha) \{ mtlgrfontlower \} \{ 107 \}
1714 \DeclareMathSymbol{\mst@mu}{\mathalpha}{mtlgrfontlower}{109}
1715 \DeclareMathSymbol{\mst@nu}{\mathalpha}{mtlgrfontlower}{110}
```

```
1716 \DeclareMathSymbol{\mst@xi}{\mathalpha}{mtlgrfontlower}{111}
1718 \DeclareMathSymbol{\mst@pi}{\mathalpha}{mtlgrfontlower}{112}
1719 \DeclareMathSymbol{\mst@rho}{\mathalpha}{mtlgrfontlower}{114}
1720 \DeclareMathSymbol{\mst@sigma}{\mathalpha}{mtlgrfontlower}{115}
1721 \DeclareMathSymbol{\mst@sigma}{\mathalpha}{mtlgrfontlower}{116}
1722 \DeclareMathSymbol{\mst@upsilon}{\mathalpha}{mtlgrfontlower}{117}
1723 \DeclareMathSymbol{\mst@phi}{\mathalpha}{mtlgrfontlower}{117}
1723 \DeclareMathSymbol{\mst@chi}{\mathalpha}{mtlgrfontlower}{112}
1724 \DeclareMathSymbol{\mst@chi}{\mathalpha}{mtlgrfontlower}{113}
1725 \DeclareMathSymbol{\mst@omega}{\mathalpha}{mtlgrfontlower}{121}
1726 \DeclareMathSymbol{\mst@omega}{\mathalpha}{mtlgrfontlower}{119}
1727 %
1728 \DeclareMathSymbol{\mst@digamma}{\mathalpha}{mtlgrfontlower}{147}
1729 % only varsigma defined (I should check this again)
1730 \DeclareMathSymbol{\mst@varsigma}{\mathalpha}{mtlgrfontlower}{99}
1731 \fi
```

\MTstandardgreek \MTcustomgreek recordstandardgreek

- 1.3d 2014/05/23 defines the commands \MTstandardgreek and \MTcustomgreek for package and user. I leave \MTrecordstandardgreek undocumented as I don't want to encourage people to load math packages after mathastext.
- 1.3h 2015/10/31: corrected \MTcustomgreek as it caused $\ensuremath{\mbox{\s\s\mbox{\s\mbox{\mbox{\mbox{\s\s\s\mbox{\s\s\mbox{\s\mbox{\s\s\mb$

```
1732 \newcommand*{\MTstandardgreek}{}
1733 \newcommand*{\MTcustomgreek}{}
1734 \newcommand*{\MTrecordstandardgreek}{}
1735 \ifmst@customgreek
1736 \renewcommand*{\MTrecordstandardgreek}{%
1737
        \let\mst@origAlpha\Alpha
1738
        \let\mst@origBeta\Beta
        \let\mst@origGamma\Gamma
1739
        \let\mst@origDelta\Delta
1740
        \let\mst@origEpsilon\Epsilon
1741
1742
        \let\mst@origZeta\Zeta
1743
        \let\mst@origEta\Eta
        \let\mst@origTheta\Theta
1744
        \let\mst@origIota\Iota
1745
        \let\mst@origKappa\Kappa
1746
        \let\mst@origLambda\Lambda
1747
        \let\mst@origMu\Mu
1748
        \let\mst@origNu\Nu
1749
        \let\mst@origXi\Xi
1750
        \let\mst@origOmicron\Omicron
1751
        \let\mst@origPi\Pi
1752
1753
        \let\mst@origRho\Rho
        \let\mst@origSigma\Sigma
1754
1755
        \let\mst@origTau\Tau
1756
        \let\mst@origUpsilon\Upsilon
```

\let\mst@origPhi\Phi

1757

```
1758
        \let\mst@origChi\Chi
1759
        \let\mst@origPsi\Psi
1760
        \let\mst@origOmega\Omega
1761 %
1762
        \let\mst@origalpha\alpha
1763
        \let\mst@origbeta\beta
        \let\mst@origgamma\gamma
1764
        \let\mst@origdelta\delta
1765
1766
        \let\mst@origepsilon\epsilon
        \let\mst@origvarepsilon\varepsilon
1767
1768
        \let\mst@origzeta\zeta
        \let\mst@origeta\eta
1769
1770
        \let\mst@origtheta\theta
1771
        \let\mst@origvartheta\vartheta
1772
        \let\mst@origiota\iota
1773
        \let\mst@origkappa\kappa
1774
        \let\mst@origlambda\lambda
1775
        \let\mst@origmu\mu
        \let\mst@orignu\nu
1776
1777
        \let\mst@origxi\xi
1778
        \let\mst@origomicron\omicron
        \let\mst@origpi\pi
1779
        \let\mst@origvarpi\varpi
1780
1781
        \let\mst@origrho\rho
        \let\mst@origvarrho\varrho
1782
1783
        \let\mst@origsigma\sigma
        \let\mst@origvarsigma\varsigma
1784
1785
        \let\mst@origtau\tau
        \let\mst@origupsilon\upsilon
1786
1787
        \let\mst@origphi\phi
1788
        \let\mst@origvarphi\varphi
1789
        \let\mst@origchi\chi
1790
        \let\mst@origpsi\psi
1791
        \let\mst@origomega\omega
        \let\mst@origDigamma\Digamma
1792
1793
        \let\mst@origdigamma\digamma
1794 %
1795
        \let\mst@origpartial\partial
1796
        \let\mst@origwp\wp
        \let\mst@origell\ell }
1797
1798 \MTrecordstandardgreek
1799 \renewcommand*{\MTstandardgreek}{%
        \let\Alpha\mst@origAlpha
1800
1801
        \let\Beta\mst@origBeta
1802
        \let\Gamma\mst@origGamma
        \let\Delta\mst@origDelta
1803
1804
        \let\Epsilon\mst@origEpsilon
1805
        \let\Zeta\mst@origZeta
        \let\Eta\mst@origEta
1806
```

```
1807
        \let\Theta\mst@origTheta
1808
        \let\Iota\mst@origIota
1809
        \let\Kappa\mst@origKappa
1810
        \let\Lambda\mst@origLambda
1811
        \let\Mu\mst@origMu
1812
        \let\Nu\mst@origNu
        \let\Xi\mst@origXi
1813
        \let\Omicron\mst@origOmicron
1814
1815
        \let\Pi\mst@origPi
        \let\Rho\mst@origRho
1816
1817
        \let\Sigma\mst@origSigma
1818
        \let\Tau\mst@origTau
1819
        \let\Upsilon\mst@origUpsilon
1820
        \let\Phi\mst@origPhi
1821
        \let\Chi\mst@origChi
1822
        \let\Psi\mst@origPsi
        \let\Omega\mst@origOmega
1823
1824 %
        \let\alpha\mst@origalpha
1825
1826
        \let\beta\mst@origbeta
1827
        \let\gamma\mst@origgamma
        \let\delta\mst@origdelta
1828
        \let\epsilon\mst@origepsilon
1829
1830
        \let\varepsilon\mst@origvarepsilon
        \let\zeta\mst@origzeta
1831
1832
        \let\eta\mst@origeta
        \let\theta\mst@origtheta
1833
1834
        \let\vartheta\mst@origvartheta
1835
        \let\iota\mst@origiota
1836
        \let\kappa\mst@origkappa
1837
        \let\lambda\mst@origlambda
1838
        \let\mu\mst@origmu
1839
        \let\nu\mst@orignu
        \let\xi\mst@origxi
1840
        \let\omicron\mst@origomicron
1841
1842
        \let\pi\mst@origpi
1843
        \let\varpi\mst@origvarpi
        \let\rho\mst@origrho
1844
1845
        \let\varrho\mst@origvarrho
        \let\sigma\mst@origsigma
1846
1847
        \let\varsigma\mst@origvarsigma
1848
        \let\tau\mst@origtau
1849
        \let\upsilon\mst@origupsilon
1850
        \let\phi\mst@origphi
1851
        \let\varphi\mst@origvarphi
1852
        \let\chi\mst@origchi
1853
        \let\psi\mst@origpsi
1854
        \let\omega\mst@origomega
```

\let\Digamma\mst@origDigamma

1855

```
1856
                     \let\digamma\mst@origdigamma
1857 %
                     \let\partial\mst@origpartial
1858
                     \let\wp\mst@origwp
1859
1860
                     \let\ell\mst@origell
1861 }
1862 \renewcommand*{\MTcustomgreek}{%
                     \let\Alpha\mst@Alpha
1863
1864
                     \let\Beta\mst@Beta
1865
                     \let\Epsilon\mst@Epsilon
                     1866
                     \let\Eta\mst@Eta
1867
1868
                     \let\Iota\mst@Iota
1869
                     \let\Kappa\mst@Kappa
1870
                     \let\Mu\mst@Mu
1871
                     \let\Nu\mst@Nu
                     \let\Omicron\mst@Omicron
1872
1873
                     \let\Rho\mst@Rho
                     \let\Tau\mst@Tau
1874
1875
                     \let\Chi\mst@Chi
1876 % 1.3h: \mst@Digamma not defined if symbolgreek option
                     \ifmst@symbolgreek\else\let\Digamma\mst@Digamma\fi
1877
1878 %
                     \let\Gamma\mst@Gamma
1879
                     \let\Delta\mst@Delta
1880
1881
                     \let\Theta\mst@Theta
                     \verb|\label{lambda}| $$  \label{lambda} $$  \label{l
1882
1883
                     \let\Xi\mst@Xi
1884
                     \let\Pi\mst@Pi
                     \let\Sigma\mst@Sigma
1885
1886
                     \let\Upsilon\mst@Upsilon
1887
                     \let\Phi\mst@Phi
                     \let\Psi\mst@Psi
1888
1889
                     \let\Omega\mst@Omega
     1.3h 2015/10/31 adds this conditional to correct the bad bug in 1.3d 2014/05/23 which caused
     \alpha etc... to become undefined under option selfGreek.
1890 \ifmst@selfGreek\else
                     \let\alpha\mst@alpha
1891
1892
                     \let\beta\mst@beta
1893
                     \let\gamma\mst@gamma
1894
                     \let\delta\mst@delta
                     \let\epsilon\mst@epsilon
1895
                     \let\zeta\mst@zeta
1896
                     \let\eta\mst@eta
1897
1898
                     \let\theta\mst@theta
1899
                     \let\iota\mst@iota
1900
                     \let\kappa\mst@kappa
                     \let\lambda\mst@lambda
1901
1902
                     \let\mu\mst@mu
```

```
1903
        \let\nu\mst@nu
1904
        \let\xi\mst@xi
        \let\omicron\mst@omicron
1905
1906
        \let\pi\mst@pi
1907
        \let\rho\mst@rho
1908
        \let\sigma\mst@sigma
        \let\tau\mst@tau
1909
        \let\upsilon\mst@upsilon
1910
        \let\phi\mst@phi
1911
1912
        \let\chi\mst@chi
        \let\psi\mst@psi
1913
1914
        \let\omega\mst@omega
1915 % 1.3h: digamma only defined with option LGRgreek:
        \ifmst@LGRgreek\let\digamma\mst@digamma\fi
1916
1917 %
1918
        \let\varsigma\mst@varsigma
1919 % conditional added 1.3h 2015/10/31
        \ifmst@LGRgreek\else
1920
          \let\varepsilon\mst@varepsilon
1921
1922
          \let\vartheta\mst@vartheta
1923
          \let\varpi\mst@varpi
          \let\varrho\mst@varrho
1924
          \let\varphi\mst@varphi
1925
1926 %
          \let\partial\mst@partial
1927
1928
          \let\wp\mst@wp
1929 % 1.3h: no \mst@ell if symbolgreek (bugfix 1.3h 2015/10/31)
          \ifmst@symbolgreek\else\let\ell\mst@ell\fi
1931
        \fi
1932 \fi
1933 }
1934\fi
1935 \let\Mathastextstandardgreek\MTstandardgreek
1936 \let\Mathastextcustomgreek\MTcustomgreek
1937 \ifmst@subdued\else\MTcustomgreek\fi
```

\inodot In 1.0, I had them of type mathord, here I choose mathalpha. If I used \i and \j from the text font the problem would be with the fontsize, if in scriptstyle. The amsmath \text would do the trick.

- $1.14b\ 2011/04/02$: again this bug in the EU1/EU2 encoding part, as in the code redefining \$ etc in math mode (see above). Fixed.
 - 1.31 2016/01/29: anticipating TL2016 fontspec's switch to TU.

```
1945 \ifx\mst@tmp@enc\mst@ti % T1
       \DeclareMathSymbol{\inodot}{\mathalpha}{mtletterfont}{25}
1946
       \DeclareMathSymbol{\jnodot}{\mathalpha}{mtletterfont}{26}
1947
1948 \else
1949 \ifx\mst@tmp@enc\mst@oti % OT1
       \DeclareMathSymbol{\inodot}{\mathalpha}{mtletterfont}{16}
1950
       \DeclareMathSymbol{\jnodot}{\mathalpha}{mtletterfont}{17}
1951
1952 \else
1953 \ifx\mst@tmp@enc\mst@lyi % LY1
1954
       \DeclareMathSymbol{\inodot}{\mathalpha}{mtletterfont}{16}
       \DeclareMathSymbol{\jnodot}{\mathalpha}{mtletterfont}{17}
1955
1956 \else
       \ifmst@XeOrLua\mst@goaheadfalse\else
1957
       \DeclareMathSymbol{\inodot}{\mathalpha}{mtletterfont}
1958
1959 {\expandafter\the\expandafter\csname\mst@tmp@enc\string\i\endcsname}
1960
       \DeclareMathSymbol{\jnodot}{\mathalpha}{mtletterfont}
1961 {\expandafter\the\expandafter\csname\mst@tmp@enc\string\j\endcsname}
1962
       \fi
1963 \fi\fi\fi\fi
1964 \ifmst@defaultimath\else\typeout{** \string\i\space and \string\j\space}
      \ifmst@goahead
1965
        \renewcommand*{\imath}{\inodot}
1966
        \renewcommand*{\jmath}{\jnodot}
1967
1968
        \let\mst@oldi\i \let\mst@oldj\j
        \DeclareRobustCommand*{\i}{\ifmmode\inodot\else\mst@oldi\fi}
1969
1970
        \DeclareRobustCommand*{\j}{\ifmmode\jnodot\else\mst@oldj\fi}
      \fi
1971
1972 \fi
```

math accents I don't know how to get from the encoding to the slot positions of the accents (apart from going to look at all possible encodings definition files and putting this info here). In standard LATEX, the mathaccents are taken from the 'operators' font. So we do the same here. Of course there is the problem that the user can define math versions with different encodings. Here I take T1 if it was the default at the time of loading the package, else OT1. 1.12b: I add LY1 which is quasi

```
1973 \edef\mst@tmp@enc{\encodingdefault} %% rather one too many than sorry
1974 \ifmst@mathaccents\typeout{** math accents}
1975 \ifx\mst@ti\mst@tmp@enc
1976 \DeclareMathAccent{\acute}{\mathalpha}{mtoperatorfont}{1}
1977 \DeclareMathAccent{\grave}{\mathalpha}{mtoperatorfont}{0}
1978 \DeclareMathAccent{\ddot}{\mathalpha}{mtoperatorfont}{4}
1979 \DeclareMathAccent{\tilde}{\mathalpha}{mtoperatorfont}{3}
1980 \DeclareMathAccent{\bar}{\mathalpha}{mtoperatorfont}{9}
1981 \DeclareMathAccent{\breve}{\mathalpha}{mtoperatorfont}{8}
1982 \DeclareMathAccent{\check}{\mathalpha}{mtoperatorfont}{7}
1983 \DeclareMathAccent{\hat}{\mathalpha}{mtoperatorfont}{2}
1984 \DeclareMathAccent{\dot}{\mathalpha}{mtoperatorfont}{10}
1985 \DeclareMathAccent{\mathring}{\mathalpha}{mtoperatorfont}{6}
1986 \else
```

```
1987 \DeclareMathAccent{\acute}{\mathalpha}{mtoperatorfont}{19}
          1988 \DeclareMathAccent{\grave}{\mathalpha}{mtoperatorfont}{18}
          1989 \DeclareMathAccent{\dot}{\mathcal {}}{\mathbf mathalpha}{\mathbf mtoperatorfont}{127}
          1990 \DeclareMathAccent{\tilde}{\mathalpha}{mtoperatorfont}{126}
           1991 \DeclareMathAccent{\bar}{\mathalpha}{mtoperatorfont}{22}
           1992 \DeclareMathAccent{\breve}{\mathalpha}{mtoperatorfont}{21}
           1993 \DeclareMathAccent{\check}{\mathalpha}{mtoperatorfont}{20}
          1994 \DeclareMathAccent{\hat}{\mathalpha}{mtoperatorfont}{94}
          1995 \DeclareMathAccent{\dot}{\mathalpha}{mtoperatorfont}{95}
          1996 \DeclareMathAccent{\mathring}{\mathalpha}{\mtoperatorfont}{23}
                 \ifx\mst@lyi\mst@tmp@enc
                                             % LY1 encoding
           1997
                   \DeclareMathAccent{\dot}{\mathalpha}{mtoperatorfont}{5}
           1998
                 \else
           1999
                    \ifx\mst@oti\mst@tmp@enc\else
           2000
           2001
                     \typeout{** mathastext: math accents have been assumed to be^^J%
           2002
                       ** as in OT1 encoding.}
           2003
                     \fi
           2004
                  \fi
           2005 \fi\fi
Math sizes I took the code for \Huge and \HUGE from the moresize package of Christian CORNELSSEN
          2006 \ifmst@defaultsizes\else
           2007 \providecommand\@xxxpt{29.86}
           2008 \providecommand\@xxxvipt{35.83}
           2009 \ifmst@twelve
                 \def\Huge{\@setfontsize\Huge\@xxxpt{36}}
           2010
                 \def\HUGE{\@setfontsize\HUGE\@xxxvipt{43}}
           2012 \typeout{** \protect\Huge\space and \protect\HUGE\space have been (re)-defined.}
           2013 \else
                 \def\HUGE{\@setfontsize\HUGE\@xxxpt{36}}
           2015 \typeout{** \protect\HUGE\space has been (re)-defined.}
          2016 \fi
            I choose rather big subscripts.
           2017 \def\defaultscriptratio{.8333}
           2018 \def\defaultscriptscriptratio{.7}
          2019 \DeclareMathSizes{9}{9}{7}{5}
           2020 \DeclareMathSizes{\@xpt}{\@xpt}{8}{6}
           2021 \DeclareMathSizes{\@xipt}{\@xipt}{9}{7}
           2022 \DeclareMathSizes{\@xiipt}{\@xiipt}{10}{8}
           2023 \DeclareMathSizes{\@xivpt}{\@xivpt}{\0xiipt}{10}
           2024 \DeclareMathSizes{\@xviipt}{\@xviipt}{\@xivpt}{\@xiipt}
           2025 \DeclareMathSizes{\@xxpt}{\@xxpt}{\@xviipt}{\@xivpt}
           2026 \DeclareMathSizes{\@xxvpt}{\@xxvpt}{\@xxpt}{\@xviipt}
          2027 \DeclareMathSizes{\@xxxpt}{\@xxxpt}{\@xxvpt}{\@xxvpt}}
          2028 \DeclareMathSizes{\@xxxvipt}{\@xxxvipt}{\@xxxpt}{\@xxxpt}
           2029 \typeout{** mathastext has declared larger sizes for subscripts.^^J%
           2030 ** To keep LaTeX defaults, use option 'defaultmathsizes\string'.}
           2031 \fi
```

\MTeverymathoff

- 1.3i 2016/01/06 Compatibility patch with \url from url.sty and \url/\nolinkurl from hyperref.sty.
- 1.3j 2016/01/15 renamed the macro from \MTactive mathoff to \MTevery mathoff, as it is not exclusively a matter of math active characters due to \MTeasy nonlettersdonotobeymathxx.
 - 1.30 2016/05/03 adds \MTdonotfixfonts . Operant with Lual*TEX only.

```
2032 \newcommand*\MTeverymathoff {%
        \MTnormalasterisk
2033
        \MTnormalprime
2034
        \MTnonlettersdonotobeymathxx
2035
        \MTeasynonlettersdonotobeymathxx
2036
        \MTmathstandardletters
2037
2038
        \MTdonotfixfonts
2039 }%
2040 \AtBeginDocument {%
       \@ifpackageloaded{hyperref}
2041
       {\def\Hurl{\begingroup\MTeverymathoff\Url}}
2042
2043
       {\@ifpackageloaded{url}{\DeclareUrlCommand\url{\MTeverymathoff}}}}}}
2044 }%
```

MTeverymathdefault

1.3j 2016/01/15 Customizable command which gets executed by \MTversion except when switching to normal/bold if option subdued. The included \MTicinmath does \MTmathactivelet ters which will also activate the math skips around letters.

The \MTeverymathdefault does not include \MTmathoperatorsobeymathxx as the latter does not correspond to something done during execution of \the\everymath.

Should I put \let\newmcodes@\mst@newmcodes@ here too? No, it is not done at everymath. During the loading, the (non subdued) package does \MTactiveasterisk (if option asterisk), \MTprimedoesskip, \MTeasynonlettersobeymathxx and \MTmathactiveletters. There is some code at begin document for decisions about italic corrections, this code does not emit again \MTmathactiveletters, hence a \MTmathstandardletters in the preamble is not overruled. Furthermore the at begin document code will not overrule user emitted \MTnoicinmath etc... commands in the preamble.

And user can employ \MTnormalexists, etc..., from inside the preamble, it will not be over-ruled (as it is delayed at begin document to after mathastext dealings).

1.30 2016/05/03 adds \MTfixfonts. Operant with LuaLATEX only.

```
2045 \newcommand*\MTeverymathdefault {%

2046 \MTactiveasterisk

2047 \MTprimedoesskip

2048 \MTeasynonlettersobeymathxx

2049 \MTicinmath

2050 \MTfixfonts

2051 }%

2052 \endinput
```