

The `mdframed` package

Examples for `framemethod=PSTricks`

Marco Daniel

v1.3a

2012/02/04

In this document I collect various examples for `framemethod=PSTricks`. Some presented examples are more or less exorbitant.

Contents

1 Loading	1	Example 2 – hidden line + frame	
		title	2
2 Examples	1	Example 3 – Dash Lines	3
Example 1 – very simple	2	Example 4 – Double Lines	3
		Example 5 – Shadow frame	3

1 Loading

In the preamble only the package `mdframed` width the option `framemethod=PSTricks` is loaded. All other modifications will be done by `\mdfdefinestyle` or `\mdfsetup`.

Note

Every `\global` inside the examples is necessary to work with the package `showexpl`.

2 Examples

All examples have the following settings:

```
\mdfsetup{skipabove=\topskip,skipbelow=\topskip}
\newrobustcmd\ExampleText{%
An \textit{inhomogeneous linear} differential equation
has the form
\begin{align}
L[v] = f,
\end{align}
where $L$ is a linear differential operator, $v$ is
the dependent variable, and $f$ is a given non-zero
function of the independent variables alone.
}
```

Example 1 – very simple

```
\global\mdfdefinestyle{exampledefault}{%
    linecolor=red, middlelinewidth=3pt,%
    leftmargin=1cm, rightmargin=1cm
}
\begin{mdframed}[style=exampledefault, roundcorner=5]
\ExampleText
\end{mdframed}
```

An *inhomogeneous linear* differential equation has the form

$$L[v] = f, \quad (1)$$

where L is a linear differential operator, v is the dependent variable, and f is a given non-zero function of the independent variables alone.

Example 2 – hidden line + frame title

```
\global\mdfapp{to definestyle}{exampledefault}{%
    topline=false, rightline=false, bottomline=false,
    frametitlerule=true, innertopmargin=6pt,
    outerlinewidth=6pt, outerlinecolor=blue,
    pstricksappsetting={\addtopsstyle{mdfouterlinestyle}{linestyle=dashed}},%
    innerlinecolor=yellow, innerlinewidth=5pt}%
\begin{mdframed}[style=exampledefault, frametitle={Inhomogeneous linear}]
\ExampleText
\end{mdframed}
```

Inhomogeneous linear

An *inhomogeneous linear* differential equation has the form

$$L[v] = f, \quad (2)$$

where L is a linear differential operator, v is the dependent variable, and f is a given non-zero function of the independent variables alone.

Example 3 – Dash Lines

```
\global\mdfdefinestyle{exampledefault}{%
  pstrickssetting={linestyle=dashed,}, linecolor=red, linewidth=5pt}
\begin{mdframed}[style=exampledefault,]
\ExampleText
\end{mdframed}
```

An *inhomogeneous linear* differential equation has the form

$$L[v] = f, \quad (3)$$

where L is a linear differential operator, v is the dependent variable, and f is a given non-zero function of the independent variables alone.

Example 4 – Double Lines

```
\global\mdfdefinestyle{exampledefault}{%
  pstrickssetting={doubleline=true, doublesep=6pt},
  linecolor=red, linewidth=5pt, middlelinewidth=4pt}
\begin{mdframed}[style=exampledefault,]
\ExampleText
\end{mdframed}
```

An *inhomogeneous linear* differential equation has the form

$$L[v] = f, \quad (4)$$

where L is a linear differential operator, v is the dependent variable, and f is a given non-zero function of the independent variables alone.

Example 5 – Shadow frame

```
\newmdenv[ shadow=true ,
           shadowsize=11pt ,
           linewidth=8pt ,
           frametitlerule=true ,
           roundcorner=10pt ,
           ]{myshadowbox}
\begin{myshadowbox}[frametitle={Inhomogeneous linear}]
\ExampleText
\end{myshadowbox}
```

Inhomogeneous linear

An *inhomogeneous linear* differential equation has the form

$$L[v] = f, \quad (5)$$

where L is a linear differential operator, v is the dependent variable, and f is a given non-zero function of the independent variables alone.