

The mdframed package

Examples for framemethod=TikZ

Marco Daniel

v1.0

November 13, 2011

In this document I collect various examples for framemethod=TikZ. Some presented examples are more or less exorbitant.

Contents

1 Loading	1	Example 2 - Gimmick	3
2 Examples	1	Example 3 - complex example with TikZ	3
Example 1 - hidden line + frame title	2		

1 Loading

In the preamble only the package `mdframed` with the option `framemethod=TikZ` is loaded. All other modifications will be done by `\mdfdefinestyle` or `\mdfsetup`.

Note

Every `\global` inside the examples is necessary to work with the package `showexpl`.

2 Examples

All examples have the following settings:

```
\mdfsetup{skipabove=\topskip,skipbelow=\topskip}
\newrobustcmd\ExampleText{%
An \textit{inhomogeneous linear} differential equation
has the form
\begin{align}
L[v] = f,
\end{align}
where $L$ is a linear differential operator, $v$ is
the dependent variable, and $f$ is a given non-zero
function of the independent variables alone.
}
```

An *inhomogeneous linear* differential equation has the form

$$L[\nu] = f, \quad (1)$$

where L is a linear differential operator, ν is the dependent variable, and f is a given non-zero function of the independent variables alone. round corner

```
\global\mdfdefinestyle{exampledefault}{%
    outerlinewidth=5pt, innerlinewidth=0pt,
    outerlinecolor=red, roundcorner=5pt
}
\begin{mdframed}[ style=exampledefault ]
\ExampleText
\end{mdframed}
```

An *inhomogeneous linear* differential equation has the form

$$L[\nu] = f, \quad (2)$$

where L is a linear differential operator, ν is the dependent variable, and f is a given non-zero function of the independent variables alone.

Example 1 – hidden line + frame title

```
\global\mdfapptodefinestyle{exampledefault}{%
    topline=false, leftline=false, }
\begin{mdframed}[ style=exampledefault, frametitle={Inhomogeneous linear} ]
\ExampleText
\end{mdframed}
```

Inhomogeneous linear

An *inhomogeneous linear* differential equation has the form

$$L[\nu] = f, \quad (3)$$

where L is a linear differential operator, ν is the dependent variable, and f is a given non-zero function of the independent variables alone.

Example 2 – Gimmick

```
\mdfsetup{splitbottomskip=0.8cm, splittopskip=0cm,
    innerrightmargin=2cm, innertopmargin=1cm,%
    innerlinewidth=2pt, outerlinewidth=2pt,
    middlelinewidth=10pt, backgroundcolor=red,
    linecolor=blue, middlelinecolor=gray,
    tikzsetting={draw=yellow, line width=3pt,%
        dashed,%
        dash pattern=on 10pt off 3pt},
    rightline=false, bottomline=false}
\begin{mdframed}
\ExampleText
\end{mdframed}
```

An *inhomogeneous linear* differential equation has the form

$$L[v] = f, \quad (4)$$

where L is a linear differential operator, v is the dependent variable, and f is a given non-zero function of the independent variables alone.

Example 3 – complex example with TikZ

```
\tikzstyle{titregris} =
[draw=gray, thick, fill=white, shading = exersicetitle, %
 text=gray, rectangle, rounded corners,
 right, minimum height=.7cm]

\pgfdeclarehorizontalshading{exercisefont}{100bp}
{color(0bp)=(green!40);
color(100bp)=(black!5)}

\pgfdeclarehorizontalshading{exercisetitle}{100bp}
{color(0bp)=(red!40);
color(100bp)=(black!5)}

\newcounter{exercise}
\renewcommand{\theexercise}{Exercise~\arabic{exercise}}
\makeatletter
\def\mdf@@exercisepoints{}
\define@key{mdf}{exercisepoints}{%
\def\mdf@@exercisepoints{\#1}}
\renewrobustcmd{\mdfcreateextratikz}{%
\node[titregris, xshift=1cm] at (P-O) %
{\sim\mdf@frametitlefont{\theexercise}\sim};
\ifdefempty{\mdf@@exercisepoints}{}%
{}}%
```

```

{ \node[ titregris ,left ,xshift=-1cm] at (P)%
  {~\mdf@frametitlefont{\mdf@@exercisepoints points}~}; }%
}

\makeatother

\mdfdefinestyle{exercisestyle}{%
  outerlinewidth=1pt,
  innerlinewidth=0pt,
  roundcorner=2pt,
  linecolor=gray,
  tikzsetting={shading = exersicebackground},
  innertopmargin=1.2\baselineskip,
  skipabove={\dimexpr0.5\baselineskip+\topskip\relax},
  needspace=3\baselineskip,
  frametitlefont=\sffamily\bfseries,
  settings={\global\stepcounter{exercise}},
}

\begin{mdframed}[ style=exercisestyle ,]
\ExampleText
\end{mdframed}

\begin{mdframed}[ style=exercisestyle ,exercisepoints=10]
\ExampleText
\end{mdframed}

```

Exercise n1

An *inhomogeneous linear* differential equation has the form

$$L[v] = f, \quad (5)$$

where L is a linear differential operator, v is the dependent variable, and f is a given non-zero function of the independent variables alone.

Exercise n2**10points**

An *inhomogeneous linear* differential equation has the form

$$L[v] = f, \quad (6)$$

where L is a linear differential operator, v is the dependent variable, and f is a given non-zero function of the independent variables alone.