

# The **breqn** package

Morten Høgholm  
`mh.ctan@gmail.com`

2007/12/22 v0.97a

## Abstract

The **breqn** package facilitates automatic line-breaking of displayed math expressions.

# User's guide

## 1 A bit of history

Originally **breqn**, **flexisym**, and **mathstyle** were created by Michael J. Downes from the American Mathematical Society during the 1990's up to late 2002. Sadly—and much to the shock of the T<sub>E</sub>X world—Michael passed away in early 2003 at the age of only 44.

The American Mathematical Society has kindly allowed me to assume maintainership of this part of his work and I wish to express my gratitude to them and to Barbara Beeton in particular for providing me with the files I needed.

I hope to continue Michael's work, thereby allowing users to create more *masterpieces of the publishing art* as I think he would have wanted.

## 2 Package loading

The recommended way of loading the **breqn** package is to load it *after* other packages dealing with math, i.e., after **amsmath**, **amssymb**, or packages such as **mathpazo** or **mathptmx**.

The **flexisym** package (described in section 11 on page 9) is required by **breqn** and ensures the math symbols are set up correctly. By default **breqn** loads it with support for Computer Modern but if you use a different math package requiring slightly different definitions, it must be loaded before **breqn**. Below is an example of how you enable **breqn** to work with the widely used **mathpazo** package.

```
\usepackage{mathpazo}
\usepackage[mathpazo]{flexisym}
\usepackage{breqn}
```

Currently, the packages **mathpazo** and **mathptmx** are supported. Despair not: Chances are that the package will work using the default settings. If you find that

a particular math font package doesn't work then please see implementation in `flexisym.dtx` for how to create a support file—it is easier than one might think. Contributions welcome.

The documentation for the package was formerly found in `breqndoc`. It has now been added to this implementation file. Below follows the contents of the original `breqn` documentation. Not all details hold anymore but I have prioritized fixing the package.

### 3 To do

- Handling of QED
- Space between `\end{dmath}` and following punctuation will prevent the punctuation from being drawn into the equation.
- Overriding the equation layout
- Overriding the placement of the equation number
- “alignid” option for more widely separated equations where shared alignment is desired (requires two passes)
- Or maybe provide an “alignwidths” option where you give lhs/rhs width in terms of ems? And get feedback later on discrepancies with the actual measured contents?
- `\intertext` not needed within dgroup! But currently there are limitations on floating objects within dgroup.
- `align={1}` or 2, 3, 4 expressing various levels of demand for group-wide alignment. Level 4 means force alignment even if some lines then have to run over the right margin! Level 1, the default, means first break LHS-RHS equations as if it occurred by itself, then move them left or right within the current line width to align them if possible. Levels 2 and 3 mean try harder to align but give up if overfull lines result.
- Need an `\hshift` command to help with alignment of lines broken at a discretionary times sign. Also useful for adjusting inside-delimiter breaks.

### 4 Introduction

The `breqn` package for L<sup>A</sup>T<sub>E</sub>X provides solutions to a number of common difficulties in writing displayed equations and getting high-quality output. For example, it is a well-known inconvenience that if an equation must be broken into more than one line, `\left ... \right` constructs cannot span lines. The `breqn` package makes them work as one would expect whether or not there is an intervening line break.

The single most ambitious goal of the `breqn` package, however, is to support automatic linebreaking of displayed equations. Such linebreaking cannot be done without substantial changes under the hood in the way math formulas are processed. For this reason, especially in the alpha release, users should proceed with care and keep an eye out for unexpected glitches or side effects.

## 5 Principal features

The principal features of the `breqn` package are:

**semantically oriented structure** The way in which compound displayed formulas are subdivided matches the logical structure more closely than, say, the standard `eqnarray` environment. Separate equations in a group of equations are written as separate environments instead of being bounded merely by `\\" commands. Among other things, this clears up a common problem of wrong math symbol spacing at the beginning of continuation lines. It also makes it possible to specify different vertical space values for the space between lines of a long, broken equation and the space between separate equations in a group of equations.`

**automatic line breaking** Overlong equations will be broken automatically to the prevailing column width, and continuation lines will be indented following standard conventions.

**line breaks within delimiters** Line breaks within `\left ... \right` delimiters work in a natural way. Line breaks can be forbidden below a given depth of delimiter nesting through a package option.

**mixed math and text** Display equations that contain mixed math and text, or even text only, are handled naturally by means of a `dseries` environment that starts out in text mode instead of math mode.

**ending punctuation** The punctuation at the end of a displayed equation can be handled in a natural way that makes it easier to promote or demote formulas from/to inline math, and to apply special effects such as adding space before the punctuation.

**flexible numbering** Equation numbering is handled in a natural way, with all the flexibility of the `amsmath` package and with no need for a special `\nonumber` command.

**special effects** It is easy to apply special effects to individual displays, e.g., changing the type size or adding a frame.

**using available space** Horizontal shrink is made use of whenever feasible. With most other equation macros it is frozen when it occurs between `\left ... \right` delimiters, or in any sort of multiline structure, so that some expressions require two lines that would otherwise fit on one.

**high-quality spacing** The `\abovedisplayshortskip` is used when applicable (other equation macros fail to apply it in equations of more than one line).

**abbreviations** Unlike the `amsmath` equation environments, the `breqn` environments can be called through user-defined abbreviations such as `\beq ... \eeq`.

## 6 Shortcomings of the package

The principal known deficiencies of the `breqn` package are:

## 6.1 Incompatibilities

As it pushes the envelope of what is possible within the context of L<sup>A</sup>T<sub>E</sub>X 2 <sub>$\varepsilon$</sub> , the *breqn* package will tend to break other packages when used in combination with them, or to fail itself, when there are any areas of internal overlap; successful use may in some cases depend on package loading order.

## 6.2 Indention of delimited fragments

When line breaks within delimiters are involved, the automatic indention of continuation lines is likely to be unsatisfactory and need manual adjustment. I don't see any easy way to provide a general solution for this, though I have some ideas on how to attain partial improvements.

## 6.3 Math symbol subversion

In order for automatic line breaking to work, the operation of all the math symbols of class 2, 3, 4, and 5 must be altered (relations, binary operators, opening delimiters, closing delimiters). This is done by an auxiliary package *flexisym*. As long as you stick to the advertised L<sup>A</sup>T<sub>E</sub>X interface for defining math symbols (`\DeclareMathSymbol`), things should work OK most of the time. Any more complex math symbol setup is quite likely to quarrel with the *flexisym* package. See Section 11 on page 9 for further information.

## 6.4 Subscripts and superscripts

Because of the changes to math symbols of class 2–5, writing certain combinations such as `^+` or `_\pm` or `^\geq` without braces would lead to error messages; (The problem described here already exists in standard L<sup>A</sup>T<sub>E</sub>X to a lesser extent, as you may know if you ever tried `^\neq` or `^\cong`; and indeed there are no examples in the L<sup>A</sup>T<sub>E</sub>X book to indicate any sanction for omitting braces around a subscript or superscript.)

The *flexisym* package therefore calls, as of version 0.92, another package called *mathstyle* which turns `^` and `_` into active characters. This is something that I believe is desirable in any case, in the long run, because having a proper *mathstyle* variable eliminates some enormous burdens that affect almost any nontrivial math macros, as well as many other things where the connection is not immediately obvious, e.g., the L<sup>A</sup>T<sub>E</sub>X facilities for loading fonts on demand.

Not that this doesn't introduce new and interesting problems of its own—for example, you don't want to put `usepackage` statements after *flexisym* for any package that refers to, e.g., `^J` or `^M` internally (too bad that the L<sup>A</sup>T<sub>E</sub>X package loading code does not include automatic defenses to ensure normal catcodes in the interior of a package; but it only handles the `@` character).

But I took a random AMS journal article, with normal end-user kind of L<sup>A</sup>T<sub>E</sub>X writing, did some straightforward substitutions to change all the equations into *dmath* environments, and ran it with active math sub/sup: everything worked OK. This suggests to me that it can work in the real world, without an impossible amount of compatibility work.

## 7 Incomplete

In addition, in the **alpha release [1997/10/30]** the following gaps remain to be filled in:

**documentation** The documentation could use amplification, especially more illustrations, and I have undoubtedly overlooked more than a few errors.

**group alignment** The algorithm for doing alignment of mathrel symbols across equations in a `dgroup` environment needs work. Currently the standard and `noalign` alternatives produce the same output.

**single group number** When a `dgroup` has a group number and the individual equations are unnumbered, the handling and placement of the group number aren't right.

**group frame** Framing a group doesn't work, you might be able to get frames on the individual equations at best.

**group brace** The `brace` option for `dgroup` is intended to produce a large brace encompassing the whole group. This hasn't been implemented yet.

**darray environment** The `darray` environment is unfinished.

**dseries environment** The syntax and usage for the `dseries` environment are in doubt and may change.

**failure arrangements** When none of the line-breaking passes for a `dmath` environment succeeds—i.e., at least one line is overfull—the final arrangement is usually rather poor. A better fall-back arrangement in the failure case is needed.

## 8 Package options

Many of the package options for the `breqn` package are the same as options of the `dmath` or `dgroup` environments, and some of them require an argument, which is something that cannot be done through the normal package option mechanism. Therefore most of the `breqn` package options are designed to be set with a `\setkeys` command after the package is loaded. For example, to load the package and set the maximum delimiter nesting depth for line breaks to 1:

```
\usepackage{breqn}
\setkeys{breqn}{breakdepth={1}}
```

See the discussion of environment options, Section 10 on page 8, for more information.

Debugging information is no longer available as a package option. Instead, the tracing information has been added in a fashion so that it can be enabled as a `docstrip` option:

```
\generate{\file{breqn.sty}}{\from{breqn.dtx}}{package,trace}}
```

## 9 Environments and commands

### 9.1 Environments

All of the following environments take an optional argument for applying local effects such as changing the typesize or adding a frame to an individual equation.

**dmath** Like `equation` but supports line breaking and variant numbers.

**dmath\*** Unnumbered; like `displaymath` but supports line breaking

**dseries** Like `equation` but starts out in text mode; intended for series of mathematical expressions of the form ‘A, B, and C’. As a special feature, if you use

```
\begin{math} ... \end{math}
```

for each expression in the series, a suitable amount of inter-expression space will be automatically added. This is a small step in the direction of facilitating conversion of display math to inline math, and vice versa: If you write a display as

```
\begin{dseries}
\begin{math}A\end{math},
\begin{math}B\end{math},
and
\begin{math}C\end{math}.
\end{dseries}
```

then conversion to inline form is simply a matter of removing the `\begin{dseries}` and `\end{dseries}` lines; the contents of the display need no alterations.

It would be nice to provide the same feature for `$` notation but there is no easy way to do that because the `$` function has no entry point to allow changing what happens before math mode is entered. Making it work would therefore require turning `$` into an active character, something that I hesitate to do in a L<sup>A</sup>T<sub>E</sub>X 2<sub>&</sub> context.

**dseries\*** Unnumbered variant of `dseries`

**dgroup** Like the `align` environment of `amsmath`, but with each constituent equation wrapped in a `dmath`, `dmath*`, `dseries`, or `dseries*` environment instead of being separated by `\backslash`. The equations are numbered with a group number. When the constituent environments are the numbered forms (`dmath` or `dseries`) they automatically switch to ‘subequations’-style numbering, i.e., something like (3a), (3b), (3c), ..., depending on the current form of non-grouped equation numbers. See also `dgroup*`.

**dgroup\*** Unnumbered variant of `dgroup`. If the constituent environments are the numbered forms, they get normal individual equation numbers, i.e., something like (3), (4), (5), ... .

**darray** Similar to **eqnarray** but with an argument like **array** for giving column specs. Automatic line breaking is not done here.

**darray\*** Unnumbered variant of **darray**, rather like **array** except in using **\displaystyle** for all column entries.

**dsuspend** Suspend the current display in order to print some text, without loss of the alignment. There is also a command form of the same thing, **\intertext**.

## 9.2 Commands

The commands provided by the **breqn** package are:

**\condition** This command is used for a part of a display which functions as a condition on the main assertion. For example:

```
\begin{dmath}
f(x)=\frac{1}{x} \condition{for $x\neq 0$}
\end{dmath}.
```

$$f(x) = \frac{1}{x}, \quad \text{for } x \neq 0. \tag{1}$$

The **\condition** command automatically switches to text mode (so that interword spaces function the way they should), puts in a comma, and adds an appropriate amount of space. To facilitate promotion/demotion of formulas, **\condition** “does the right thing” if used outside of display math.

To substitute a different punctuation mark instead of the default comma, supply it as an optional argument for the **\condition** command:

```
\condition[;]{...}
```

(Thus, to get no punctuation: **\condition[]{}{...}**.)

For conditions that contain no text, you can use the starred form of the command, which means to stay in math mode:

```
\begin{dmath}
f(x)=\frac{1}{x} \condition*[x\neq 0]
\end{dmath}.
```

If your material contains a lot of conditions like these, you might like to define shorter abbreviations, e.g.,  
**\begin{verbatim}**  
**\newcommand{\mc}{\condition\*{}**% math condition  
**\newcommand{\tc}{\condition}**% text condition

But the `breqn` package refrains from predefining such abbreviations in order that they may be left to the individual author's taste.

`\hiderel` In a compound equation it is sometimes desired to use a later relation symbol as the alignment point, rather than the first one. To do this, mark all the relation symbols up to the desired one with `\hiderel`:

```
T(n) \hiderel{\leq} T(2^n) \leq c(3^n - 2^n) ...
```

## 10 Various environment options

The following options are recognized for the `dmath`, `dgroup`, `darray`, and `dseries` environments; some of the options do not make sense for all of the environments, but if an option is used where not applicable it is silently ignored rather than treated as an error.

```
\begin{dmath}[style={\small}]
\begin{dmath}[number={BV}]
\begin{dmath}[label={xyz}]
\begin{dmath}[relindent={1em}]
\begin{dmath}[compact]
\begin{dmath}[spread={1pt}]
\begin{dmath}[frame]
\begin{dmath}[frame={1pt},framesep={2pt}]
\begin{dmath}[background={red}]
\begin{dmath}[color={purple}]
\begin{dmath}[breakdepth={0}]
```

Use the `style` option to change the type size of an individual equation. This option can also serve as a catch-all option for altering the equation style in other ways; the contents are simply executed directly within the context of the equation.

Use the `number` option if you want the number for a particular equation to fall outside of the usual sequence. If this option is used the equation counter is not incremented. If for some reason you need to increment the counter and change the number at the same time, use the `style` option in addition to the `number` option:

```
style={\refstepcounter{equation}}
```

Use of the normal `\label` command instead of the `label` option works, I think, most of the time (untested).

Use the `relindent` option to specify something other than the default amount for the indentation of relation symbols. The default is 2em.

Use the `compact` option in compound equations to inhibit line breaks at relation symbols. By default a line break will be taken before each relation symbol except the first one. With the `compact` option L<sup>A</sup>T<sub>E</sub>X will try to fit as much material as possible on each line, but breaks at relation symbols will still be preferred over breaks at binary operator symbols.

Use the `spread` option to increase (or decrease) the amount of interline space in an equation. See the example given above.

Use the `frame` option to produce a frame around the body of the equation. The thickness of the frame can optionally be specified by giving it as an argument of the option. The default thickness is `\fboxrule`.

Use the `framesep` option to change the amount of space separating the frame from what it encloses. The default space is `\fboxsep`.

Use the `background` option to produce a colored background for the equation body. The `breqn` package doesn't automatically load the `color` package, so this option won't work unless you remember to load the `color` package yourself.

Use the `color` option to specify a different color for the contents of the equation. Like the `background` option, this doesn't work if you forgot to load the `color` package.

Use the `breakdepth` option to change the level of delimiter nesting to which line breaks are allowed. To prohibit line breaks within delimiters, set this to 0:

```
\begin{dmath}[breakdepth={0}]
```

The default value for `breakdepth` is 2. Even when breaks are allowed inside delimiters, they are marked as less desirable than breaks outside delimiters. Most of the time a break will not be taken within delimiters until the alternatives have been exhausted.

Options for the `dgroup` environment: all of the above, and also

```
\begin{dgroup}[noalign]
\begin{dgroup}[brace]
```

By default the equations in a `dgroup` are mutually aligned on their relation symbols (`=`, `<`,  `$\geq$` , and the like). With the `noalign` option each equation is placed individually without reference to the others.

The `brace` option means to place a large brace encompassing the whole group on the same side as the equation number.

Options for the `darray` environment: all of the above (where sensible), and also

```
\begin{darray}[cols={lcr@{\hspace{2em}}lcr}]
```

The value of the `cols` option for the `darray` environment should be a series of column specs as for the `array` environment, with the following differences:

- For l, c, and r what you get is not text, but math, and `displaystyle` math at that. To get text you must use a 'p' column specifier, or put an `\mbox` in each of the individual cells.
- Vertical rules don't connect across lines.

## 11 The `flexisym` package

The `flexisym` package does some radical changes in the setup for math symbols to allow their definitions to change dynamically throughout a document. The `breqn`

package uses this to make symbols of classes 2, 3, 4, 5 run special functions inside an environment such as `dmath` that provide the necessary support for automatic line breaking.

The method used to effect these changes is to change the definitions of `\DeclareMathSymbol` and `\DeclareMathDelimiter`, and then re-execute the standard set of L<sup>A</sup>T<sub>E</sub>X math symbol definitions. Consequently, additional mathrel and mathbin symbols defined by other packages will get proper line-breaking behavior if the other package is loaded after the `flexisym` package and the symbols are defined through the standard interface.

## 12 Caution! Warning!

Things to keep in mind when writing documents with the `breqn` package:

- The notation `:=` must be written with the command `\coloneq`. Otherwise the `:` and the `=` will be treated as two separate relation symbols with an “empty RHS” between them, and they will be printed on separate lines.
- Watch out for constructions like `^+` where a single binary operator or binary relation symbol is subscripted or superscripted. When the `breqn` or `flexisym` package is used, braces are mandatory in such constructions: `^{+}`. This applies for both display and in-line math.
- If you want L<sup>A</sup>T<sub>E</sub>X to make intelligent decisions about line breaks when vert bars are involved, use proper pairing versions of the vert-bar symbols according to context: `\lvert n\rvert` instead of `|n|`. With the nondirectional `|` there is no way for L<sup>A</sup>T<sub>E</sub>X to reliably deduce which potential breakpoints are inside delimiters (more highly discouraged) and which are not.
- If you use the `german` package or some other package that turns double quote `"` into a special character, you may encounter some problems with named math symbols of type mathbin, mathrel, mathopen, or mathclose in moving arguments. For example, `\leq` in a section title will be written to the `.aux` file as something like `\mathchar "3214`. This situation probably ought to be improved, but for now use `\protect`.
- Watch out for the `[` character at the beginning of a `dmath` or similar environment, if it is supposed to be interpreted as mathematical content rather than the start of the environment’s optional argument.

This is OK:

```
\begin{dmath}
[\lambda, 1] ...
\end{dmath}
```

This will not work as expected:

```
\begin{dmath}[\lambda, 1] ... \end{dmath}
```

- Watch out for unpaired delimiter symbols (in display math only):

```
( ) [ ] \langle \rangle \{ \} \lvert \rvert ...
```

If an open delimiter is used without a close delimiter, or vice versa, it is normally harmless but may adversely affect line breaking. This is only for symbols that have a natural left or right directionality. Unpaired `\lvert` and so on are fine.

When a null delimiter is used as the other member of the pair (`\left.` or `\right.`) this warning doesn't apply.

- If you inadvertently apply `\left` or `\right` to something that is not a delimiter, the error messages are likely to be a bit more confusing than usual. The normal L<sup>A</sup>T<sub>E</sub>X response to an error such as

```
\left +
```

is an immediate message

```
! Missing delimiter (. inserted).
```

When the `breqn` package is in use, L<sup>A</sup>T<sub>E</sub>X will fail to realize anything is wrong until it hits the end of the math formula, or a closing delimiter without a matching opening delimiter, and then the first message is an apparently pointless

```
! Missing \endgroup inserted.
```

## 13 Examples

Knuth, SNA p74

*Example 1*

Replace  $j$  by  $h - j$  and by  $k - j$  in these sums to get [cf. ~ (26)]

```
\begin{dmath}[label={sna74}]
\frac{1}{6} \left( \sigma(k, h, 0) + \frac{3(h-1)}{h} \right) + \frac{1}{6} \left( \sigma(h, k, 0) + \frac{3(k-1)}{k} \right)
= \frac{1}{6} \left( \frac{h}{k} + \frac{k}{h} + \frac{1}{hk} \right) + \frac{1}{2} - \frac{1}{2h} - \frac{1}{2k},
\end{dmath}
```

which is equivalent to the desired result.

Replace  $j$  by  $h - j$  and by  $k - j$  in these sums to get [cf. (26)]

$$\begin{aligned}
& \frac{1}{6} \left( \sigma(k, h, 0) + \frac{3(h-1)}{h} \right) + \frac{1}{6} \left( \sigma(h, k, 0) + \frac{3(k-1)}{k} \right) \\
&= \frac{1}{6} \left( \frac{h}{k} + \frac{k}{h} + \frac{1}{hk} \right) + \frac{1}{2} - \frac{1}{2h} - \frac{1}{2k},
\end{aligned} \tag{13.2}$$

which is equivalent to the desired result.

Knuth, SNA 4.6.2, p387

*Example 2*

```
\newcommand\mx[1]{\begin{math}#1\end{math}}% math expression
%
Now every column which has no circled entry is completely zero;
so when $k=6$ and $k=7$ the algorithm outputs two more vectors,
namely
\begin{dseries}[frame]
\mx{v^{[2]}} = (0,5,5,0,9,5,1,0),
\mx{v^{[3]}} = (0,9,11,9,10,12,0,1).
\end{dseries}
```

From the form of the matrix  $A$  after  $k=5$ , it is evident that these vectors satisfy the equation  $vA = (0, \dots, 0)$ .

math expression

Now every column which has no circled entry is completely zero; so when  $k = 6$  and  $k = 7$  the algorithm outputs two more vectors, namely

$$v^{[2]} = (0, 5, 5, 0, 9, 5, 1, 0), \quad v^{[3]} = (0, 9, 11, 9, 10, 12, 0, 1). \quad (13.3)$$

From the form of the matrix  $A$  after  $k = 5$ , it is evident that these vectors satisfy the equation  $vA = (0, \dots, 0)$ .

*Example 3*

```
\begin{dmath*}
T(n) \hiderel{\leq} T(2^{\lceil \lg n \rceil})
\leq c(3^{\lceil \lg n \rceil} - 2^{\lceil \lg n \rceil})
< 3c \cdot 3^{\lg n}
= 3c n^{\lg 3}.
\end{dmath*}
```

$$\begin{aligned} T(n) &\leq T(2^{\lceil \lg n \rceil}) \leq c(3^{\lceil \lg n \rceil} - 2^{\lceil \lg n \rceil}) \\ &< 3c \cdot 3^{\lg n} \\ &= 3c n^{\lg 3}. \end{aligned}$$

*Example 4*

The reduced minimal Gr\"obner basis for  $I^q_3$  consists of

```
\begin{dgroup*}
\begin{dmath*}
H_1^3 = x_1 + x_2 + x_3
\end{dmath*},
\begin{dmath*}
H_2^2 = x_1^2 + x_1 x_2 + x_2^2 - q_1 - q_2
\end{dmath*}
\end{dgroup*}
```

```

\end{dmath*},
\begin{dsuspend}
and
\end{dsuspend}
\begin{dmath*}
H_3^1 = x_1^3 - 2x_1 q_1 - x_2 q_1
\end{dmath*}.
\end{dgroup*}

```

The reduced minimal Gröbner basis for  $I_3^q$  consists of

$$\begin{aligned} H_1^3 &= x_1 + x_2 + x_3, \\ H_2^2 &= x_1^2 + x_1 x_2 + x_2^2 - q_1 - q_2, \end{aligned}$$

and

$$H_3^1 = x_1^3 - 2x_1 q_1 - x_2 q_1.$$

## Implementation

The package version here is Michael's v0.90 updated by Bruce Miller. Michael's changes between v0.90 and his last v0.94 will be incorporated where applicable.

The original sources of `breqn` and related files exist in a non-dtx format devised by Michael Downes himself. Lars Madsen has kindly written a Perl script for transforming the original source files into near-perfect dtx state, requiring only very little hand tuning. Without his help it would have been nigh impossible to incorporate the original sources with Michael's comments. A big, big thank you to him.

## 14 Introduction

The `breqn` package provides environments `dmath`, `dseries`, and `dgroup` for displayed equations with *automatic line breaking*, including automatic indentation of relation symbols and binary operator symbols at the beginning of broken lines. These environments automatically pull in following punctuation so that it can be written in a natural way. The `breqn` package also provides a `darray` environment similar to the `array` environment but using `\displaystyle` for all the array cells and providing better interline spacing (because the vertical ruling feature of `array` is dropped). These are all autonumbered environments like `equation` and have starred forms that don't add a number. For a more comprehensive and detailed description of the features and intended usage of the `breqn` package see `breqndoc.tex`.

## 15 Strategy

Features of particular note are the ability to have linebreaks even within a `\left`-`\right` pair of delimiters, and the automatic alignment on relations and

binary operators of a split equation. To make `dmath` handle all this, we begin by setting the body of the equation in a special paragraph form with strategic line breaks whose purpose is not to produce line breaks in the final printed output but rather to mark significant points in the equation and give us entry points for unpacking `\left-``\right` boxes. After the initial typesetting, we take the resulting stack of line fragments and, working backward, splice them into a new, single-line paragraph; this will eventually be poured into a custom parshape, after we do some measuring to calculate what that parshape should be. This streamlined horizontal list may contain embedded material from user commands intended to alter line breaks, horizontal alignment, and interline spacing; such material requires special handling.

To make the ‘`shortskip`’ possibility work even for multiline equations, we must plug in a dummy `TEX` display to give us the value of `\predisplaysize`, and calculate for ourselves when to apply the short skips.

In order to measure the equation body and do various enervating calculations on whether the equation number will fit and so on, we have to set it in a box. Among other things, this means that we can’t `unhbox` it inside `$$...$$`, or even `$...$`: `TEX` doesn’t allow you to `unhbox` in math mode. But we do want to `unhbox` it rather than just call `\box`, otherwise we can’t take advantage of available shrink from `\medmuskip` to make equations shrink to fit in the available width. So even for simple one-line equations we are forced to fake a whole display without going through `TEX`’s primitive display mechanism (except for using it to get `\predisplaysize` as mentioned above).

In the case of a framed equation body, the current implementation is to set the frame in a separate box, of width zero and height zero, pinned to the upper left corner of the equation body, and then print the equation body on top of it. For attaching an equation number it would be much simpler to wrap the equation body in the frame and from then on treat the body as a single box instead of multiple line boxes. But I had a notion that it might be possible some day to support vertical stretching of the frame.

## 16 Prelim

This package doesn’t work with `LATEX` 2.09, nor with other versions of `LATEX` earlier than 1994/12/01.

```

1  <*package>
2  \NeedsTeXFormat{LaTeX2e}
3
4  Declare package name and date.
5  \ProvidesPackage{breqn}[2007/12/22 v0.97a]
```

## 17 Package options

Most options are set with the `\options` command (which calls `\setkeys`) because the standard package option mechanism doesn’t provide support for key-value syntax.

First we need to get the catcodes sorted out.

```

4  \edef\breqn{\catcode`\=\number\catcode`\"}
5  \catcode`\number`\=\number\catcode`\"
```

```

6   \relax}
7 \AtEndOfPackage{\breqnpopcats}%
8 \catcode`\^=7 \catcode`\_=8 \catcode`\'=12 \relax
9 \DeclareOption{mathstyleoff}{%
10  \PassOptionsToPackage{mathstyleoff}{flexisym}%
11 }

```

Process options.

```

12 \ProcessOptions\relax

```

## 18 Required packages

The `flexisym` package makes it possible to attach extra actions to math symbols, in particular `mathbin`, `mathrel`, `mathopen`, and `mathclose` symbols. Normally it would suffice to call `\RequirePackage` without any extra testing, but the nature of the package is such that it is likely to be called earlier with different (no) options. Then is it really helpful to be always warning the user about ‘Incompatible Package Options!’? I don’t think so.

```

13 \@ifpackageloaded{flexisym}{}{%
14  \RequirePackage{flexisym}[2007/12/19]
15  \edef\breqnpopcats{\breqnpopcats
16  \catcode\number`\^=\number\catcode`\^
17  \catcode\number`\_= \number\catcode`\_
18 }%
19 \catcode`\^=7 \catcode`\_=8 \catcode`\'=12 \relax
20 }

```

The `keyval` package for handling equation options and `calc` to ease writing computations.

```

21 \RequirePackage{keyval,calc}\relax

```

And add an `\options` cmd for processing package options that require an argument. Maybe this will get added to the `keyval` package eventually.

```

22 \@ifundefined{options}{%

```

`\options` Get the package options and run `setkeys` on them.

```

23 \newcommand{\options}[2]{%
24  \expandafter\options@a\csname opt@#1.sty\endcsname{#2}%
25  \setkeys{#1}{#2}%
26 }

```

`\options@a` Redefine `\opt@pkgnname.sty` as we go along to take out the options that are handled and leave the ones that are not.

```

27 \def\options@a#1#2{%
28  \edef\@tempa{\options@b#2,\@empty\@nil}%
29  \ifx#1\relax \let#1\@empty\fi
30  \xdef#1{\ifx#1\@empty\@xp\@gobble\@tempa\@empty\else\@tempa\@fi}%
31 }

```

Add the next option, and recurse if there remain more options.

```

32 \def\options@b#1,#2#3\@nil{%
33  \options@c#1\@nil
34  \ifx#2\@empty \else\options@b#2#3\@nil\fi
35 }

```

Discard everything after the first space.

36 \def\options@c#1 #2@nil{\options@d#1=@nil}

Discard everything after the first = sign; add a comma only if the remainder is not empty.

37 \def\options@d#1=#2@nil{\ifx\@empty #1\@empty\else ,\fi#1}

The tail of the \@ifundefined test.

38 }{}% end @ifundefined test

## 19 Some useful tools

**\@nx** The comparative brevity of \@nx and \@xp is valuable not so much for typing convenience as for reducing visual clutter in code sections that require a lot of expansion control.

39 \let\@nx\noexpand

40 \let\@xp\expandafter

**\@emptytoks** Constant empty token register, analogous to \@empty.

41 \@ifundefined{@emptytoks}{\newtoks\@emptytoks}{}

**\f@ur** Constants 0–3 are provided in plain TeX, but not 4.

42 \chardef\f@ur=4

**\inf@bad** \inf@bad is for testing box badness.

43 \newcount\inf@bad \inf@bad=1000000

**\maxint** We want to use \maxint rather than coerced \maxdimen for \linepenalty in one place.

44 \newcount\maxint \maxint=2147483647

**\int@a** Provide some shorter aliases for various scratch registers.

**\int@b** 45 \let\int@a=\@tempcnta

**\int@b** 46 \let\int@b=\@tempcntb

47 \let\int@c=\count@

**\dim@a** Same for dimen registers.

**\dim@b** 48 \let\dim@a\@tempdima

**\dim@c** 49 \let\dim@b\@tempdimb

**\dim@d** 50 \let\dim@c\@tempdimc

**\dim@e** 51 \let\dim@d\dimen@

**\dim@A** 52 \let\dim@e\dimen@ii

53 \let\dim@A\dimen@i

**\skip@a** Same for skip registers.

**\skip@b** 54 \let\skip@a\@tempskipa

**\skip@c** 55 \let\skip@b\@tempskipb

56 \let\skip@c\skip@

<code>\toks@a</code>	Same for token registers.
<code>\toks@b</code>	<code>57 \let\toks@a\@temptokena</code>
<code>\toks@c</code>	<code>58 \let\toks@b\toks@</code>
<code>\toks@d</code>	<code>59 \toksdef\toks@c=2</code>
<code>\toks@e</code>	<code>60 \toksdef\toks@d=4</code>
<code>\toks@f</code>	<code>61 \toksdef\toks@e=6</code>
	<code>62 \toksdef\toks@f=8</code>
<code>\abs@num</code>	We need an absolute value function for comparing penalties. <code>63 \def\abs@num{\ifnum#1&lt;\z@\-\fi#1}</code>
<code>\@ifnext</code>	The <code>\@ifnext</code> function is a variation of <code>\@ifnextchar</code> that doesn't skip over intervening whitespace. We use it for the optional arg of <code>\\\nside</code> <code>dmath</code> etc. because we don't want unwary users to be tripped up by an unexpected attempt on L <sup>A</sup> T <sub>E</sub> X's part to interpret a bit of math as an optional arg:
	<code>\begin{equation}</code> ...\\ [z,w]... <code>\end{equation}</code>
	.
	<code>64 \def\@ifnext#1#2#3{%</code> 65 <code>\let\@tempd= #1\def\@tempa{#2}\def\@tempb{#3}%</code> 66 <code>\futurelet\@tempc\@ifnexta</code> 67 }
	Switch to <code>\@tempa</code> iff the next token matches. <code>68 \def\@ifnexta{\ifx\@tempc\@tempd \let\@tempb\@tempa \fi \@tempb}</code>
<code>\@ifstar</code>	Similarly let's remove space-skipping from <code>\@ifstar</code> because in some rare case of <code>\\\nside</code> an equation, followed by a space and a <code>*</code> where the <code>*</code> is intended as the math binary operator, it would be a disservice to gobble the star as an option of the <code>\\\ommand</code> . In all other contexts the chance of having a space <i>before</i> the star is extremely small: either the command is a control word which will get no space token after it in any case because of T <sub>E</sub> X's tokenization rules; or it is a control symbol such as <code>\\"*</code> which is exceedingly unlikely to be written as <code>\\"*</code> by any one who really wants the <code>*</code> to act as a modifier for the <code>\\\ommand</code> .
	<code>69 \def\@ifstar#1#2{%</code> 70 <code>\let\@tempd*\def\@tempa*{#1}\def\@tempb{#2}%</code> 71 <code>\futurelet\@tempc\@ifnexta</code> 72 }
<code>\@optarg</code>	Utility function for reading an optional arg <i>without</i> skipping over any intervening spaces. <code>73 \def\@optarg#1#2{\@ifnext[#{1}]{#1}{#2}}</code>
<code>\@True</code>	After <code>\let\foo\@True</code> the test
<code>\@False</code>	<code>\if\foo</code>
<code>\@Not</code>	
<code>\@And</code>	evaluates to true. Would rather avoid <code>\newif</code> because it uses three csnames per Boolean variable; this uses only one. <code>74 \def\@True{00}</code>

```

75 \def\@False{0}
76 \def\@Not#1{0\ifcase#11 \or\exp 1\else \exp 0\fi}
77 \def\@And#1#2{0\ifcase#1#2 \exp 0\else \exp 1\fi}
78 \def\@Or#1#2{0\ifnum#1#2<101 \exp 0\else \exp 1\fi}
79 \def\theb@@le#1{\if#1 True\else False\fi}

\freeze@glue Remove the stretch and shrink from a glue register.
80 \def\freeze@glue{\#1\relax}

\z@rule Note well the intentional absence of \relax at the end of the replacement text of
\keep@glue \z@rule; use it with care.
81 \def\z@rule{\vrule\@width\z@} no \relax ! use with care

Different ways to keep a bit of glue from disappearing at the beginning of a line
after line breaking:


- Zero-thickness rule
- Null character
- \vadjust{} (The TeXbook, Exercise ??)



The null character idea would be nice except it creates a mathord which then
screws up math spacing for e.g., a following unary minus sign. (the vrule is trans-
parent to the math spacing). The vadjust is the cheapest in terms of box mem-
ory—it vanishes after the pass through TeX's paragrapher. It is what I would have
used, except that the equation contents get run through two paragraphing passes,
once for breaking up LR boxes and once for the real typesetting. If \keep@glue
were done with an empty vadjust, it would disappear after the first pass and—in
particular—the pre-bin-op adjustment for relation symbols would disappear at a
line break.
82 \def\keep@glue{\z@rule\relax}

\replicate This is a fully expandable way of making N copies of a token list. Based on a post
of David Kastrup to comp.text.tex circa January 1999. The extra application of
\number is needed for maximal robustness in case the repeat count N is given in
some weird TeX form such as "E9 or \count9.
83 % usage: \message{H\replicate{5}{i h}ow de doo dee!}
84 \begingroup \catcode`\&=11
85 \gdef\replicate#1{%
86   \csname &\expandafter\replicate@a\romannumeral\number\number#1 000q\endcsname
87 }
88 \endgroup

\replicate@a
89 \long\def\replicate@a#2\endcsname#3{\#1\endcsname{\#3}#2}

\8m fix
90 \begingroup \catcode`\&=11
91 \long\gdef\&#1{\#1\csname &\#2\endcsname{\#1}}
92 \endgroup

```

```

\8q fix
93 \exp\let\csname\string &q\endcsname\gobble

\mathchars@reset Need to patch up this function from flexisym a little, to better handle certain
constructed symbols like \neq.
94 \g@addto@macro\mathchars@reset{%
95   \let\@symRel\@secondoftwo \let\@symBin\@secondoftwo
96   \let\@symDeL\@secondoftwo \let\@symDeR\@secondoftwo
97   \let\@symDeB\@secondoftwo
98 }

\eq@cons LATEX's \@cons appends to the end of a list, but we need a function that adds
material at the beginning.
99 \def\eq@cons#1#2{%
100   \begingroup \let\@elt\relax \xdef#1{\@elt{#2}#1}\endgroup
101 }

\@saveprimitive If some preceding package redefined one of the primitives that we must change, we
had better do some checking to make sure that we are able to save the primitive
meaning for internal use. This is handled by the \@saveprimitive function.
We follow the example of \@@input where the primitive meaning is stored in
an internal control sequence with a @@ prefix. Primitive control sequences can be
distinguished by the fact that \string and \meaning return the same information.
Well, not quite all: \nullfont and \topmark and the other \...mark primitives
being the exceptions.
102 \providecommand{\@saveprimitive}[2]{%
103   \begingroup
104   \edef\@tempa{\string#1}\edef\@tempb{\meaning#1}%
105   \ifx\@tempa\@tempb \global\let#2#1%
106   \else
107     \edef\@tempb{\meaning#2}%
108     \ifx\@tempa\@tempb
109       \else \@saveprimitive@a#1#2%
110       \fi
111     \fi
112   \endgroup
113 }

If [arg1] is no longer primitive, then we are in trouble unless [arg2] was already
given the desired primitive meaning somewhere else.
107   \edef\@tempb{\meaning#2}%
108   \ifx\@tempa\@tempb
109     \else \@saveprimitive@a#1#2%
110     \fi
111   \fi
112 \endgroup
113 }

Aux function, check for the special cases. Most of the time this branch will be
skipped so we can stuff a lot of work into it without worrying about speed costs.
114 \providecommand{\@saveprimitive@a}[2]{%
115   \begingroup
116   \def\@tempb##1##2{\edef\@tempb{##2}\@car{}}
117   \ifx\@tempb\@empty\select font nullfont\%
118     \topmark{\string\topmark:}%
119     \firstmark{\string\firstmark:}%
120     \botmark{\string\botmark:}%
121     \splitfirstmark{\string\splitfirstmark:}%
122     \splitbotmark{\string\splitbotmark:}%
123     #1{\string#1}%

```

```

124 \edef\@tempa{\expandafter\strip@prefix\meaning\@tempb}%
125 \edef\@tempb{\meaning#1}%
126 \ifx\@tempa\@tempb \global\let#2#1%
127 \else
128   \PackageError{breqn}{%
129     {Unable to properly define \string#2; primitive
130      \noexpand#1 no longer primitive}\@eha
131   \fi
132 \fi
133 \endgroup
134 }

```

\@@math Move the math-start and math-end functions into control sequences. If I were redesigning TeX I guess I'd put these functions into primitive control words instead of linking them to a catcode. That way TeX would not have to do the special lookahead at a \$ to see if there's another one coming up. Of course that's related to the question of how to provide user shorthand for common constructions: TeX, or an editing interface of some sort.

```

135 \begingroup \catcode`$=\thr@@ % just to make sure
136 \global\let\@@math=$ \gdef\@@display{$$} $$$
137 \endgroup
138 \let\@@endmath=\@@math
139 \let\@@enddisplay=\@@display

\@@insert Save the primitives \vadjust, \insert, \mark because we will want to change
\@@mark them locally during equation measuring to keep them from getting in the way
\@@vadjust of our vertical decomposition procedures. We follow the example of \@@input,
\@@end, \@@par where the primitive meaning is stored in an internal control se-
quence with a @@ prefix.
140 \csaveprimitive\vadjust\@@vadjust
141 \csaveprimitive\insert\@@insert
142 \csaveprimitive\mark\@@mark

```

## 20 Debugging

Debugging help.

```

143 <*trace>
144 \errorcontextlines=2000\relax

```

\breqn@debugmsg Print a debugging message.

```

145 \long\def\breqn@debugmsg#1{\GenericInfo{||}{||=\space#1}}

```

\debugwr Sometimes the newline behavior of \message is unsatisfactory; this provides an alternative.

```

146 \def\debugwr#1{\immediate\write\sixt@@n{||= #1}}

```

\debug@box Record the contents of a box in the log file, without stopping.

```

147 \def\debug@box#1{%
148   \batchmode{\showboxbreadth\maxdimen\showboxdepth99\showbox#1}%
149   \errorstopmode
150 }

```

```

\eqinfo Show lots of info about the material before launching into the trials.
151 \def\eqinfo{%
152   \debug@box{EQ@copy}
153   \wlog{!! EQ@copy: \the\wd{EQ@copy}\space x}
154   \the\ht{EQ@copy}+\the\dp{EQ@copy}
155 }
156 }

\debug@para Check params that affect line breaking.
157 \def\debug@para{%
158   \debugwr{\hsize\the\hsize, \parfillskip\the\parfillskip}%
159   \breqn@debugmsg{\leftskip\the\leftskip, \rightskip\the\rightskip}%
160   \breqn@debugmsg{\linepenalty\the\linepenalty, \adjdemerits\the\adjdemerits}%
161   \breqn@debugmsg{\pretolerance\the\pretolerance, \tolerance\the\tolerance,
162     \parindent\the\parindent}%
163 }
164 </trace>

```

## 21 The \listwidth variable

The dimen variable `\listwidth` is `\linewidth` plus `\leftmargin` plus `\rightmargin`, which is typically less than `\hsize` if the list depth is greater than one. In case a future package will provide this variable, define it only if not yet defined.

```

165 \c@ifundefined{listwidth}{\newdimen\listwidth}{}
166 \listwidth=\z@

```

## 22 Parameters

Here follows a list of parameters needed.

<code>\eqfontsize</code>	Note: avoid M, m, P, p because they look like they might be the start of a keyword
<code>\eqcolor</code>	'minus' or 'plus'. Then TeX looks further to see if the next letter is i or l. And if
<code>\eqmargin</code>	the next thing is an undefined macro, the attempt to expand the macro results in
<code>\eqindent</code>	an error message.
<code>\eqbinoffset</code>	<sup>167</sup> \def\eqfontsize{} % Inherit from context [NOT USED?]
<code>\eqnumside</code>	<sup>168</sup> \def\eqcolor{black} % Default to black [NOT USED?]
<code>\eqnumplace</code>	<sup>169</sup> \newdimen\eqnumsep \eqnumsep=10pt % Min space between equ number and body
<code>\eqnumsep</code>	<sup>170</sup> \newdimen\eqmargin \eqmargin=8pt % For 'multiline' gap emulation
<code>\eqnumfont</code>	The <code>\eqindent</code> and <code>\eqnumside</code> variables need to have their values initialized
<code>\eqnumform</code>	from context, actually. But that takes a bit of work, which is postponed till later.
<code>\eqnumsize</code>	<sup>171</sup> \def\eqindent{C}% % C or I, centered or indented
<code>\eqnumcolor</code>	<sup>172</sup> \def\eqnumside{R}% % R or L, right or left
<code>\eqlinespacing</code>	<sup>173</sup> \def\eqnumplace{M}% % M or T or B, middle top or bottom
<code>\eqlineskip</code>	Typesetting the equation number is done thus:
<code>\eqlineskiplimit</code>	<code>\{ \eqnumcolor \eqnumsize \eqnumfont{ \eqnumform{ \eq@number } } }</code>
<code>\eqstyle</code>	.
<code>\eqinterlinepenalty</code>	
<code>\intereqpenalty</code>	
<code>\intereqskip</code>	<sup>174</sup> %d\eqnumfont{\upshape} % Upright even when surrounding text is slanted

```

175 \def\eqnumfont{}% Null for easier debugging [mjd,1997/09/26]
176 \def\eqnumform{\#1}(%#1\@italiccorr)% Add parens
177 \def\eqnumsize{}% Allow numbers to have different typesize ...

```

Tricky questions on `\eqnumsize`. Should the default be `\normalsize`? Then the user can scale down the equation body with `\small` and not affect the equation number. Or should the default be empty? Then in large sections of smaller text, like the dangerous bend stuff in *T<sub>E</sub>Xbook*, the equation number size will keep in synch with the context. Maybe need an `\eqbodysize` param as well to allow separating the two cases.

```

178 \def\eqnumcolor{}% ... or color than eq body e.g. \color{blue}
179 \newlength\eqlinespacing \eqlinespacing=14pt plus2pt% Base-to-base space between lines
180 \newlength\eqlineskip \eqlineskip=3pt plus2pt% Min space if eqlinespacing too small
181 \newdimen\eqlineskiplimit \eqlineskiplimit=2pt% Threshold for switching to eqlineskip

```

The value of `\eqbinoffset` should include a negative shrink component that cancels the shrink component of `medmuskip`, otherwise there can be a noticeable variation in the indent of adjacent lines if one is shrunken a lot and the other isn't.

```

182 \newmuskip\eqbinoffset \eqbinoffset=15mu minus-3mu% Offset from mathrel alignment pt for mat
183 \newmuskip\eqdelimoffset \eqdelimoffset=2mu% Additional offset for break inside delims
184 \newdimen\eqindentstep \eqindentstep=8pt% Indent used when LHS wd is n/a or too large
185 \newtoks\eqstyle% Customization hook
186 \newcount\eqbreakdepth \eqbreakdepth=2% Allow breaks within delimiters to this depth
187 \newcount\eqinterlinepenalty \eqinterlinepenalty=10000% No page breaks between equation lines
188 \newcount\intereqpenalty \intereqpenalty=1000% Pagebreak penalty between equations [BRM: V]
189 \newlength\intereqskip \intereqskip=3pt plus2pt% Additional vert space between equations
190 \newcount\prerelpenalty \prerelpenalty=-\@M% Linebreak penalty before mathrel symbols
191 \newcount\prebinoppenalty \prebinoppenalty=888% Linebreak penalty before mathbins

```

When breaking equations we never right-justify, so a stretch component of the `muskip` is never helpful and sometimes it is definitely undesirable. Note that thick/`medmuskip`s frozen inside a fraction or radical may turn out noticeably larger than neighboring unfrozen ones. Nonetheless I think this way is the best compromise short of a new T<sub>E</sub>X that can make those built-up objects shrink horizontally in proportion; the alternative is to pretty much eliminate the shrink possibility completely in displays.

```

192 \newmuskip\Dmedmuskip \Dmedmuskip=4mu minus 3mu% medmuskip in displays
193 \newmuskip\Dthickmuskip \Dthickmuskip=5mu minus 2mu% thickmuskip in displays

```

And now some internal variables. 1997/10/22: some of these are dead branches that need to be pruned.

MH: Started cleaning up a bit. No more funny loops.

```

194 \def\eq@number{}% Internal variable
195 \newlength\eqleftskip \eqleftskip=\@centering% Space on the left [NOT USED?]
196 \newlength\eqrightskip \eqrightskip=\@centering% Space on the right [NOT USED?]
197 \newlength\eq@vspan \eq@vspan=\z@skip% Glue used to vcenter the eq number
198 \newmuskip\eq@binoffset \eq@binoffset=\eqbinoffset% Roughly, \eqbinoffset + \eqdelimoffset
199 \newsavebox\EQ@box% Storage for equation body
200 \newsavebox\EQ@copy% For eq body sans vadjust/insert/mark material
201 \newsavebox\EQ@numbox% For equation number
202 \newdimen\eq@wdNum% width of number + separation [NEW]
203 \newsavebox\GRP@numbox% For group number [NEW]
204 \newdimen\grp@wdNum% width of number + separation [NEW]
205 %%B\EQ@vimbox% Vadjust, insert, or mark material

```

```

206 %%B\EQ@vimcopy      % Spare copy of same
207 %%B\eq@impinging    % Temporary box for measuring number placement
208 \newcount \eq@lines   % Internal counter, actual number of lines
209 \newcount \eq@curline  % Loop counter
210 \newcount \eq@badness  % Used in testing for overfull lines
211 \newcount \EQ@vims     % For bookkeeping
212 \def\@eq@numbertrue{\let\eq@hasNumber\@True}%
213 \def\@eq@numberfalse{\let\eq@hasNumber\@False}%
214 \let\eq@hasNumber\@False

```

Here for the dimens, it would be advisable to do some more careful management to conserve dimen registers. First of all, most of the dimen registers are needed in the measuring phase, which is a tightly contained step that happens after the contents of the equation have been typeset into a box and before any external functions have a chance to regain control—e.g., the output routine. Therefore it is possible to make use of the the dimen registers 0–9, reserved by convention for scratch use, without fear of conflict with other macros. But I don’t want to use them directly with the available names:

```
\dimen@ \dimen@i \dimen@ii \dimen3 \dimen4 ... \dimen9
```

. It would be much more useful to have names for these registers indicative of way they are used.

Another source whence dimen registers could be borrowed is the `amsmath` package, which allocates six registers for equation-measuring purposes. We can reuse them under different names since the `amsmath` functions and our functions will never be used simultaneously.

```
\eqnshift@ \alignsep@ \tagshift@ \tagwidth@ \totwidth@ \lineht@
```

```

215 \newdimen\eq@dp        % Depth of last line
216 \newdimen\eq@wdL       % Width of the left-hand-side
217 \newdimen\eq@wdT       % Total width for framing
218 \newdimen\eq@wdMin     % Width of narrowest line in equation
219 \newdimen\grp@wdL      % Max width of LHS's in a group
220 \newdimen\grp@wdR      % Max RHS of all equations in a group
221 \newdimen\grp@wdT
222 \newdimen\eq@wdRmax    % Height of first line
223 \newdimen\eq@firstht

```

BRM: measure the condition too.

```

224 \newdimen\eq@wdCond
225 \newdimen\eq@indentstep % Indent amount when LHS is not present
226 \newdimen\eq@linewidth % Width actually used for display
227 \newdimen\grp@linewidth % Max eq@linewidth over a group

```

Maybe `\eq@hshift` could share the same register as `\mathindent` [mjd,1997/10/22].

```

228 \newdimen\eq@hshift
229 \let\eq@isIntertext\@False

```

Init `\eq@indentstep` to a nonzero value so that we can detect and refrain from clobbering a user setting of zero. And `\eq@sidespace` to `\maxdimen` because that is the right init before computing a min.

```

230 \eq@indentstep=\maxdimen
231 \newdimen\eq@given@sidespace

```

```
\eq@overrun MH: Appears to be unused.  
Not a dimen register; don't need to advance it.  
232 \def\eq@overrun{Opt}
```

To initialize `\eqnumside` and `\eqindent` properly, we may need to grub around a bit in `\@filelist`. However, if the `amsmath` package was used, we can use its option data. More trouble: if a documentclass sends an option of `leqno` to `amsmath` by default, and it gets overridden by the user with a `reqno` documentclass option, then `amsmath` believes itself to have received *both* options.

```
233 \@ifpackagewith{amsmath}{leqno}{}%  
234 \@ifpackagewith{amsmath}{reqno}{}{\def\eqnumside{L}}%  
235 }%
```

If the `amsmath` package was not used, the next method for testing the `leqno` option is to see if `leqno.clo` is present in `\@filelist`.

```
236 \def\@tempa#1,leqno.clo,#2#3@nil{}%  
237 \ifx @#2\relax\else \def\eqnumside{L}\fi  
238 }%  
239 \xp\@tempa\@filelist,leqno.clo,@@nil
```

Even that test may fail in the case of `amsart` if it does not load `amsmath`. Then we have to look whether `\iftagsleft@` is defined, and if so whether it is true. This is tricky if you want to be careful about conditional nesting and don't want to put anything in the hash table unnecessarily.

```
240 \if L\eqnumside  
241 \else  
242 \@ifundefined{iftagsleft}{}{}%  
243 \edef\eqnumside{}%  
244 \if TT\csname fi\endcsname\csname iftagsleft@\endcsname  
245 L\else R\fi  
246 }%  
247 }  
248 \fi  
249 }
```

A similar sequence of tests handles the ‘fleqn or not fleqn’ question for the `article` and `amsart` documentclasses.

```
250 \@ifpackagewith{amsmath}{fleqn}{}%  
251 \def\eqindent{I}%  
252 }%  
253 \def\@tempa#1,fleqn.clo,#2#3@nil{}%  
254 \ifx @#2\relax\else \def\eqindent{I}\fi  
255 }%  
256 \xp\@tempa\@filelist,fleqn.clo,@@nil  
257 \if I\eqindent  
258 \else  
259 \@ifundefined{if@fleqn}{}{}%  
260 \edef\eqindent{}%  
261 \if TT\csname fi\endcsname\csname if@fleqn\endcsname  
262 I\else C\fi  
263 }%  
264 }%  
265 \fi  
266 }
```

BRM: This conditional implies we must use ALL indented or ALL centered?

```

267  \%if I\eqindent
268    \@ifundefined{mathindent}{%
269      \newdimen\mathindent
270    }%
271    \@ifundefined{@mathmargin}{}{%
272      \mathindent\@mathmargin
273    }%
274  }
275 \%fi

```

## 23 Measuring equation components

Measure the left-hand side of an equation. This function is called by mathrel symbols. For the first mathrel we want to discourage a line break more than for following mathrels; so `\mark@lhs` gobbles the following `\rel@break` and substitutes a higher penalty.

**Maybe the LHS should be kept in a separate box.**

`\EQ@hasLHS` Boolean: does this equation have a “left-hand side”?

```

276 \let\EQ@hasLHS=\@False

```

`\EQ@QED` If nonempty: the qed material that should be incorporated into this equation after the final punctuation.

```

277 \let\EQ@QED=\@empty

```

`\mark@lhs`

```

278 \def\mark@lhs#1{%
279   \ifnum\lr@level<\@ne
280     \let\mark@lhs\relax
281     \global\let\EQ@hasLHS=\@True
282     \global\let\EQ@prebin@space\EQ@prebin@space@a
283     \mark@lhs@a

```

But the penalty for the first mathrel should still be lower than a binoppenalty. If not, when the LHS contains a binop, the split will occur inside the LHS rather than at the mathrel. On the other hand if we end up with a multiline sort of equation layout where the RHS is very short, the break before the relation symbol should be made *less* desirable than the breakpoints inside the LHS. Since a lower penalty takes precedence over a higher one, we start by putting in the highest relpenalty; during subsequent measuring if we find that that RHS is not excessively short then we put in an extra “normal” relpenalty when rejoining the LHS and RHS.

```

284   \penalty9999 % instead of normal \rel@break
285   % else no penalty = forbid break
286   \fi
287 }

```

`\mark@lhs@a` Temporarily add an extra thickmuskip to the LHS; it will be removed later. This is necessary to compensate for the disappearance of the thickmuskip glue preceding a mathrel if a line break is taken at that point. Otherwise we would have to make our definition of mathrel symbols more complicated, like the one for mathbins.

The penalty of 2 put in with `vadjust` is a flag for `\eq@repack` to suggest that the box containing this line should be measured to find the value of `\eq@wdL`. The second `vadjust` ensures that the normal `prerelpenalty` and `thickmuskip` will not get lost at the line break during this preliminary pass.

BRM: I originally thought the `\mskip\thickmuskip` was messing up summation limits in LHS. But I may have fixed that problem by fixing other things...

```
288 \def\mark@lhs@{%
289   \mskip\thickmuskip \@@vadjust{\penalty\tw@\penalty-\@Mi\@@vadjust{}}
290 }
```

`\hiderel` If you want the LHS to extend past the first mathrel symbol to a following one, mark the first one with `\hiderel`:

```
a \hiderel{=} b = c...
```

I'm not sure now why I didn't use `\begingroup \endgroup` here

mjd,1999/01/21

```
291 \newcommand\hiderel[1]{\mathrel{\advance\lr@level@ne#1}}
292 \m@Bin cf. flexisym handling of mathbins and mathrels. These are alternate definitions of
293 \m@Rel \m@Bin and \m@Rel, activated by \display@setup.
294 \bin@break \let\m@Bin\m@Bin
295 \rel@break \let\m@Rel\m@Rel
296 \bin@mark \let\EQ@prebin@space\relax
297 \rel@mark \def\EQ@prebin@space@af{\mskip-\eq@binoffset \keep@glue \mskip\eq@binoffset}
298 \d@Bin \def\bin@break{\ifnum\lastpenalty=\z@\penalty\prebinoppenalty\fi
299   \EQ@prebin@space}
300 \d@Rel \def\rel@break{%
301   \ifnum\abs@num\lastpenalty <\abs@num\prerelpenalty
302     \penalty\prerelpenalty
303   \fi
304 }
```

303 \def\d@Bin{\bin@break \m@Bin}

304 \def\d@Rel{\mark@lhs \rel@break \m@Rel}

The difficulty of dealing properly with the subscripts and superscripts sometimes appended to mathbins and mathrels is one of the reasons that we do not attempt to handle the mathrels as a separate 'column' a la `eqnarray`.

```
\m@symRel More of the same.
\d@symRel \let\m@symRel@symRel \def\d@symRel{\mark@lhs \rel@break \m@symRel}
\m@symBin \let\m@symBin@symBin \def\d@symBin{\bin@break \m@symBin}
\m@symDel \let\m@symDel@symDel \m@symDel
\m@symDeR \let\m@symDeR@symDeR \m@symDeR
\m@symDeB \let\m@symDeB@symDeB \m@symDeB
\m@symDeA \let\m@symDeA@symDeA \m@symDeA

\d@symDeR \d@symDeR@setup
\m@symDeB \m@symDeB@frozen@everydisplay. BRM: Disable this! It also affects non-breqn math!!!!
\d@symDeB
\m@symDeA \global\everydisplay\expandafter{\the\everydisplay \display@setup}
\d@symDeA
```

Change some math symbol function calls.

```

312 \def\display@setup{%
313   \medmuskip\medmuskip \thickmuskip\thickmuskip
314   \let\m@Bin\d@@Bin \let\m@Rel\d@@Rel
315   \let\@symRel\d@@symRel \let\@symBin\d@@symBin
316   \let\m@Del\d@@DeL \let\m@DeR\d@@DeR \let\m@DeB\d@@DeB
317   \let\m@DeA\d@@DeA
318   \let\@symDeL\d@@symDeL \let\@symDeR\d@@symDeR
319   \let\@symDeB\d@@symDeB \let\@symDeA\d@@symDeA
320   \let\left\eq@left \let\right\eq@right \global\lr@level\z@
321   \global\eq@wdCond\z@           %BRM: new

```

If we have an embedded array environment (for example), we don't want to have each math cell within the array resetting `\lr@level` globally to 0—not good! And in general I think it is safe to say that whenever we have a subordinate level of boxing we want to revert to a normal math setup.

```

322 \everyhbox{\everyhbox@\emptytoks
323   \let\display@setup\relax \textmath@setup \let\textmath@setup\relax
324 }%
325 \everyvbox{\everyvbox@\emptytoks
326   \let\display@setup\relax \textmath@setup \let\textmath@setup\relax
327 }%
328 }

```

The `\textmath@setup` function is needed for embedded inline math inside text inside a display.

BRM: DS Experiment: Variant of `\display@setup` for use within dseries environments

```

329 \def\dseries@display@setup{%
330   \medmuskip\medmuskip \thickmuskip\thickmuskip
331   \let\m@Bin\d@@Bin
332 %\let\m@Rel\d@@Rel
333 % \let\@symRel\d@@symRel
334 \let\@symBin\d@@symBin
335 \let\m@Del\d@@DeL \let\m@DeR\d@@DeR \let\m@DeB\d@@DeB
336 \let\m@DeA\d@@DeA
337 \let\@symDeL\d@@symDeL \let\@symDeR\d@@symDeR
338 \let\@symDeB\d@@symDeB \let\@symDeA\d@@symDeA
339 \let\left\eq@left \let\right\eq@right \global\lr@level\z@
340 \everyhbox{\everyhbox@\emptytoks
341   \let\display@setup\relax \textmath@setup \let\textmath@setup\relax
342 }%
343 \everyvbox{\everyvbox@\emptytoks
344   \let\display@setup\relax \textmath@setup \let\textmath@setup\relax
345 }%
346 \displaystyle
347 }

348 \def\textmath@setup{%
349   \let\m@Bin\m@@Bin \let\m@Rel\m@@Rel
350   \let\@symRel\m@@symRel \let\@symBin\m@@symBin
351   \let\m@Del\m@@DeL \let\m@DeR\m@@DeR \let\m@DeB\m@@DeB
352   \let\m@DeA\m@@DeA
353   \let\@symDeL\m@@symDeL \let\@symDeR\m@@symDeR
354   \let\@symDeB\m@@symDeB \let\@symDeA\m@@symDeA

```

```

355   \let\left\@@left \let\right\@@right
356 }

\if@display The test \ifinner is unreliable for distinguishing whether we are in a displayed
\everydisplay formula or an inline formula: any display more complex than a simple one-line
equation typically involves the use of $ \displaystyle ... $ instead of $$...$$. So we provide a more reliable test. But it might have been provided already by
the amsmath package.

357 \@ifundefined{@displaytrue}{%
358   \xp\newif\csname if@display\endcsname
359   \everydisplay\xp{\the\everydisplay \@displaytrue}%
360 }{}
```

**Is there any reason to maintain separate \everydisplay and \eqstyle?**

## 24 The dmath and dmath\* environments

Options for the dmath and dmath\* environments.

```
\begin{dmath}[label={xyz}]
```

```

361 \define@key{breqn}{label}{\def\next@label{\label{#1}}}
362 \global\let\next@label\empty
```

Allow a variant number.

```
\begin{dmath}[number={\nref{foo}\textprime}]
```

```

363 \define@key{breqn}{number}{\def\eq@number{#1}%
364   \let\@currentlabel\eq@number
365 }
```

```
\begin{dmath}[shiftnumber]
\begin{dmath}[holdnumber]
```

Holding or shifting the number.

```

366 \define@key{breqn}{shiftnumber}{\let\eq@shiftnumber\@True}
367 \define@key{breqn}{holdnumber}{\let\eq@holdnumber\@True}
```

```
\begin{dmath}[density=.5]
```

```
368 \define@key{breqn}{density}{\def\eq@density@factor{#1}}
```

```
\begin{dmath}[indentstep=1em]
```

To change the amount of indent for post-initial lines. Note: for lines that begin with a mathbin symbol there is a fixed amount of indent already built in (\eqbinoffset) and it cannot be reduced through this option. The indentstep amount is the indent used for lines that begin with a mathrel symbol.

```
369 \define@key{breqn}{indentstep}{\eqindentstep#1\relax}
```

```
\begin{dmath}[compact]
```

```
\begin{dmath}[compact=-2000]
```

To make mathrels stay inline to the extent possible, use the `compact` option. Can give a numeric value in the range  $-10000 \dots 10000$  to adjust the behavior.  $-10000$ : always break at a rel symbol;  $10000$ : never break at a rel symbol.

```
370 \define@key{breqn}{compact}[-99]{\prerelpenalty=#1\relax}
```

`\begin{dmath}[layout={S}]%`

Specify a particular layout. We take care to ensure that `\eq@layout` ends up containing one and only one letter.

```
371 \define@key{breqn}{layout}[?]{%
372   \edef\eq@layout{\@car#1?\@nil}%
373 }
```

`\begin{dmath}[spread={1pt}]`

To change the interline spacing in a particular equation.

```
374 \define@key{breqn}{spread}{%
375   \addtolength\eqlinespacing{#1}%
376   \addtolength\eqlineskip{#1}%
377   \eqlineskiplimit\eqlineskip
378 }
```

To change the amount of space on the side for “multiline” layout.

```
379 \define@key{breqn}{sidespace}{%
380   \setlength\eq@given@sidespace{#1}%
381 }
```

`\begin{dmath}[style={\small}]`

The `style` option is mainly intended for changing the type size of an equation but as a matter of fact you could put arbitrary L<sup>A</sup>T<sub>E</sub>X code here—thus the option name is ‘style’ rather than just ‘typesize’. In order for this option to work when setting options globally, we need to put the code in `\eqstyle` rather than execute it directly.

```
382 \define@key{breqn}{style}{\exp{\@xp{\the\eqstyle #1}}}
```

`\begin{dmath}[shortskiplimit={1em}]`

If the line immediately preceding a display has length  $l$ , the first line of the display is indented  $i$ , and a shortskip limit  $s$  is set, then the spacing above the display is equal to `\abovedisplayshortskip` if  $l+s < i$  and `\abovedisplayskip` otherwise. The default shortskip limit is  $2\text{em}$  which is what TeX hardcodes but this parameter overrides that.

```
383 \define@key{breqn}{shortskiplimit}{\def\eq@shortskiplimit{#1}}
384 \def\eq@shortskiplimit{2em}
```

`\begin{dmath}[frame]`

The `frame` option merely puts a framebox around the body of the equation. To change the thickness of the frame, give the thickness as the argument of the option. For greater control, you can change the appearance of the frame by redefining `\eqframe`. It must be a command taking two arguments, the width and height of the equation body. The top left corner of the box produced by `\eqframe` will be pinned to the top-left corner of the equation body.

```
385 \define@key{breqn}{frame}{[\fboxrule]{\def\eq@frame{T}%
386 \dim@a#1\relax\edef\eq@framewd{\the\dim@a}}}
```

Until such time as we provide a frame implementation that allows the frame to stretch and shrink, we'd better remove any stretch/shrink from the interline glue in this case.

```

387   \freeze@glue\eqlinespacing \freeze@glue\eqlineskip
388 }
389 \define@key{breqn}{fullframe}[] {\def\eq@frame{U}%
390   \freeze@glue\eqlinespacing \freeze@glue\eqlineskip
391 }
392 \def\eq@frame{F} % no frame
393 \def\eq@framewd{\fboxrule}

```

Wishful thinking?

```
\begin{dmath}[frame={width={2pt},color={blue},sep={2pt}}]
```

To change the space between the frame and the equation there is a framesep option.

```

394 \define@key{breqn}{framesep}[\fboxsep]{%
395   \if\eq@frame F\def\eq@frame{T}\fi
396   \dim@a#1\relax \edef\eq@framesep{\the\dim@a}%
397   \freeze@glue\eqlinespacing \freeze@glue\eqlineskip
398 }
399 \def\eq@framesep{\fboxsep}

```

```
\begin{dmath}[background={red}]
```

Foreground and background colors for the equation. By default the background area that is colored is the size of the equation, plus fboxsep. If you need anything fancier for the background, you'd better do it by defining `\eqframe` in terms of `\colorbox` or `\fcolorbox`.

```

400 \define@key{breqn}{background}{\def\eq@background{\#1}%
401   \freeze@glue\eqlinespacing \freeze@glue\eqlineskip
402 }
403 % \end{macrocode}
404 % \begin{literalcode}
405 % \begin{dmath}[color={purple}]
406 % \end{literalcode}
407 % \begin{macrocode}
408 \define@key{breqn}{color}{\def\eq@foreground{\#1}}

```

  

```
\begin{dmath}[center]
\begin{dmath}[nocenter]
```

The `center` option means add leftskip stretch to make the individual lines be centered; this is the default for `dseries`.

```

409 \define@key{breqn}{center}[] {\let\eq@centerlines@\True}
410 \define@key{breqn}{nocenter}[] {\let\eq@centerlines@\False}
411 \let\eq@centerlines@\False

```

```
\begin{dgroup}[noalign]
```

Equation groups normally have alignment of the primary relation symbols across the whole group. The `noalign` option switches that behavior.

```

412 \define@key{breqn}{noalign}[] {\let\grp@aligned@\False}
413 \let\grp@aligned@\True % default

```

```
\begin{dgroup}[breakdepth={2}]
```

Break depth of 2 means that breaks are allowed at mathbin symbols inside two pairs of delimiters, but not three.

```
414 \define@key{breqn}{breakdepth}{\eqbreakdepth#1\relax}
```

```
\begin{darray}[cols={lcr lcr}]
```

The `cols` option only makes sense for the `darray` environment but we liberally allow all the options to be used with all the environments and just ignore any unsensible ones that happen to come along.

```
415 \define@key{breqn}{cols}{\global\let@\preamble\empty
416 \darray@mkpream#1\@percentchar
417 }
```

#### FORMAT STATUS

```
\def\eq@frame{T}%
CLM works tolerably
\def\eqindent{C}\def\eqnumside{L}\def\eqnumplace{M}
CLT works tolerably
\def\eqindent{C}\def\eqnumside{L}\def\eqnumplace{T}
ILM
\def\eqindent{I}\def\eqnumside{L}\def\eqnumplace{M}\mathindent40\p0
ILT
\def\eqindent{I}\def\eqnumside{L}\def\eqnumplace{T}\mathindent40\p0
Indended w/left number
    work ok if mathindent is larger than number width,
    but then equations must fit into smaller space.
    Is shiftnumber allowed to put eqn at left, instead of indent?
CRM
\def\eqindent{C}\def\eqnumside{R}\def\eqnumplace{M}
CRB
\def\eqindent{C}\def\eqnumside{R}\def\eqnumplace{B}
IRM
\def\eqindent{I}\def\eqnumside{R}\def\eqnumplace{M}\mathindent10\p0
IRB
\def\eqindent{I}\def\eqnumside{R}\def\eqnumplace{B}\mathindent10\p0
```

The main environments.

BRM: The following incorporates several changes: 1) modifications supplied by MJD to fix the eaten `\paragraph` problem. 2) Added `\display@setup` here, rather than globally.

`\dmath` For the `dmath` environment we don't want the standard optional arg processing because of the way it skips over whitespace, including newline, while looking for the `[` char; which is not good for math material. So we call `\@optarg` instead.

```
418 \newenvironment{dmath}{%
419 \let\eq@hasNumber\@True \@optarg\@dmath{}{}{}%
420 \def\@dmath[#1]{%
421 \trace \breqn@debugmsg{== DMATH ======%
422 \everydisplay\expandafter{\the\everydisplay \display@setup}%

```

```

423   \if@noskipsec \leavevmode \fi
424   \if@inlabel \leavevmode \global\@inlabelfalse \fi
425   \if\eq@group\else\eq@prelim\fi
426   \setkeys{breqn}{#1}%
427   \the\eqstyle

```

The equation number might have been overridden in #1.

```
428   \eq@setnumber
```

Start up the displayed equation by reading the contents into a box register. Enclose this phase in an extra group so that modified `\hsize` and other params will be auto-restored afterwards.

```

429   \begingroup
430   \eq@setup@a
431   \eq@startup
432 }

```

Before it finishes off the box holding the equation body, `\enddmath` needs to look ahead for punctuation (and `\qed?`).

```

433 \def\enddmath#1{\check@punct@or@qed}
434 \def\end@dmath{%
435   \gdef\EQ@setwdL{}% Occasionally undefined ???
436   \eq@capture
437   \endgroup
438   \EQ@setwdL

```

Measure (a copy of) the equation body to find the minimum width required to get acceptable line breaks, how many lines will be required at that width, and whether the equation number needs to be shifted to avoid overlapping. This information will then be used by `\eq@finish` to do the typesetting of the real equation body.

```
439   \eq@measure
```

Piece together the equation from its constituents, recognizing current constraints. If we are in an equation group, this might just save the material on a stack for later processing.

```

440   \if\eq@group \grp@push \else \eq@finish\fi
441 }

```

`\dmath*` Ah yes, now the lovely `dmath*` environment.

```

\enddmath* \newenvironment{dmath*}{%
  \let\eq@hasNumber\@False \coptarg\@dmath{}%
}{%
  \cnamedef{end@dmath*}{\end@dmath}
  \cnamedef{enddmath*}{\check@punct@or@qed}
}

```

`\eq@prelim` If `\everypar` has a non-null value, it's probably some code from `\@afterheading` that sets `\clubpenalty` and/or removes the parindent box. Both of those actions are irrelevant and interfering for our purposes and need to be deflected for the time being. If an equation appears at the very beginning of a list item (possibly from a trivlist such as `proof`), we need to trigger the item label.

```

447 \def\eq@prelim{%
448   \if@inlabel \indent \par \fi
449   \if@nobreak \global\@nobreakfalse \predisplaypenalty\@M \fi
450   \everypar\emptytoks
}

```

If for some reason `dmath` is called between paragraphs, `\noindent` is better than `\leavevmode`, which would produce an indent box and an empty line to hold it. If we are in a list environment, `\par` is defined as `{\@par}` to preserve `\parshape`.

```

451   \noindent
452   \eq@nulldisplay
453   \par %% \eq@saveparinfo %% needs work
454   \let\intertext\breqn@intertext
455 }
```

`\breqn@parshape@warning` Warning message extracted to a separate function to streamline the calling function.

```

456 \def\breqn@parshape@warning{%
457   \PackageWarning{breqn}{%
458     Complex paragraph shape cannot be followed by this equation}%
459 }
```

`\eq@prevshape` Storage; see `\eq@saveparinfo`.

```
460 \let\eq@prevshape\empty
```

`\eq@saveparinfo` Save the number of lines and parshape info for the text preceding the equation.

```

461 \def\eq@saveparinfo{%
462   \count@\prevgraf \advance\count@-\thr@@ % for the null display
463   \edef\eq@prevshape{\prevgraf\the\count@\space}%
464   \ifcase\parshape
465     % case 0: no action required
466   \or \edef\eq@prevshape{\eq@prevshape
467     \parshape\@ne\displayindent\displaywidth\relax
468   }%
```

Maybe best to set `\eq@prevshape` the same in the else case also. Better than nothing.

```

469 \else
470   \breqn@parshape@warning
471 \fi
472 }
```

`\eq@setnumber` If the current equation number is not explicitly given, then use an auto-generated number, unless the no-number switch has been thrown (`dmath*`). `\theequation` is the number form to be used for all equations, `\eq@number` is the actual value for the current equation (might be an exception to the usual sequence).

```

473 \def\eq@setnumber{%
474   \eq@wdNum\z@
475   \if\eq@hasNumber
476     \ifx\eq@number\empty
477       \stepcounter{equation}\let\eq@number\theequation
478     \fi
479   \% \fi
```

This sets up numbox, etc, even if unnumbered?????

```

480   \ifx\eq@number\empty
481   \else
```

Put the number in a box so we can use its measurements in our number-placement calculations. The extra braces around `\eqnumform` make it possible for `\eqnumfont` to have either an `\itshape` (recommended) or a `\textit` value.

```

482 <trace>      \breqn@debugmsg{Number \eq@number}%
483   \set@label{equation}\eq@number
484   \global\sbox\EQ@numbox{%
485     \next@label \global\let\next@label\empty
486     \eqnumcolor\eqnumsize\eqnumfont{\eqnumform{\eq@number}}%
487   }%
488   \global\eq@wdNum\wd\EQ@numbox\global\advance\eq@wdNum\eqnumsep
489 %   \let\eq@hasNumber\@True % locally true
490   \fi
491   \fi
492 }
```

`\eq@finish` The information available at this point from preliminary measuring includes the number of lines required, the width of the equation number, the total height of the equation body, and (most important) the parshape spec that was used in determining height and number of lines.

Invoke the equation formatter for the requested centering/indentation having worked out the best parshape. BRM: This portion is extensively refactored to get common operations together (so corrections get consistently applied).

MH: I've destroyed Bruce's nice refactoring a bit to get the abovedisplayskips correct for both groups of equations and single `dmath` environments. I will have to redo that later.

```

493 \newcount\eq@final@linecount
494 \let\eq@GRP@first@dmath\@True
495 \def\eq@finish{%
496   \begingroup
497   <trace> \breqn@debugmsg{Formatting equation}%
498   <trace> \debug@showmeasurements
499   \if F\eq@frame\else
500     \freeze@glue\eqlinespacing \freeze@glue\eqlineskip
501   \fi
502 %   \eq@topspace{\vskip\parskip}% Set top spacing
503   \csname eq@\eqindent @setsides\endcsname % Compute \leftskip,\rightskip
504   \adjust@parshape\eq@parshape% Final adjustment of parshape for left|right skips
```

If we are in an a group of equations we don't want to calculate the top space for the first one as that will be delayed until later when the space for the group is calculated. However, we do need to store the leftskip used here as that will be used later on for calculating the top space.

```

505   \if\eq@group
506     \if\eq@GRP@first@dmath
507       \global\let\eq@GRP@first@dmath\@False
508       \xdef\dmath@first@leftskip{\leftskip=\the\leftskip\relax}%
509   <trace> \breqn@debugmsg{Stored\space\dmath@first@leftskip}
510   \else
511     \eq@topspace{\vskip\parskip}% Set top spacing
512   \fi
513   \else
514     \eq@topspace{\vskip\parskip}% Set top spacing
515   \fi
```

```
516 <trace>    \debug@showformat
```

We now know the final line count of the display. If it is a single-line display, we want to know as that greatly simplifies the equation tag placement (until such a time where this algorithm has been straightened out).

```
517 \afterassignment\remove@to@nnil
518 \eq@final@linecount=\expandafter\@gobble\eq@parshape\@nnil
```

Now, invoke the appropriate typesetter according to number placement

```
519 \if\eq@hasNumber
520   \if\eq@shiftnumber
521     \csname eq@typeset@\eqnumside Shifted\endcsname
522   \else
```

If there is only one line and the tag doesn't have to be shifted, we call a special procedure to put the tag correctly.

```
523 \ifnum\eq@final@linecount=\@ne
524   \csname eq@typeset@\eqnumside @single\endcsname
525   \else
526     \csname eq@typeset@\eqnumside\eqnumplace\endcsname
527   \fi
528   \fi
529 \else
530   \eq@typeset@Unnumbered
531 \fi
532 \endgroup
533 \eq@botspace
534 }
```

These are temporary until the tag position algorithm gets rewritten. At least the tag is positioned correctly for single-line displays. The horizontal frame position is not correct but the problem lies elsewhere.

```
535 \def\eq@typeset@L@single{%
536   \nobreak
537   \eq@params\eq@parshape
538   \nointerlineskip\noindent
539   \add@grp@label
540   \rlap{\kern-\leftskip\box\EQ@numbox}%
541   \if F\eq@frame
542   \else
543     \rlap{\raise\eq@firstht\hbox to\z@{\eq@addframe\hss}}%
544   \fi
545   \eq@dump@box\unhbox\EQ@box \@@par
546 }
547 \def\eq@typeset@R@single{%
548   \nobreak
549   \eq@params\eq@parshape
550   \nointerlineskip\noindent
551   \add@grp@label
552   \if F\eq@frame
553   \else
554     \rlap{\raise\eq@firstht\hbox to\z@{\eq@addframe\hss}}%
555   \fi
556   \rlap{\kern-\leftskip\kern\linewidth\kern-\wd\EQ@numbox\copy\EQ@numbox}%
557   \eq@dump@box\unhbox\EQ@box
```

```
558     \@@par
559 }
```

## 25 Special processing for end-of-equation

At the end of a displayed equation environment we need to peek ahead for two things: following punctuation such as period or command that should be pulled in for inclusion at the end of the equation; and possibly also an `\end{proof}` with an implied “qed” symbol that is traditionally included at the end of the display rather than typeset on a separate line. We could require that the users type `\qed` explicitly at the end of the display when they want to have the display take notice of it. But the reason for doing that would only be to save work for the programmer; the most natural document markup would allow an inline equation and a displayed equation at the end of a proof to differ only in the environment name:

```
... \begin{math} ... \end{math}.
\end{proof}
```

versus

```
...
\begin{dmath}
...
\end{dmath}.
\end{proof}
```

. The technical difficulties involved in supporting this markup within L<sup>A</sup>T<sub>E</sub>X 2e are, admittedly, nontrivial. Nonetheless, let’s see how far we can go.

The variations that we will support are only the most straightforward ones:

```
\end{dmath}.
\end{proof}
```

or

```
\end{dmath}.
Perhaps a comment
\end{proof}
```

. If there is anything more complicated than a space after the period we will not attempt to scan any further for a possible `\end{proof}`. This includes material such as:

```
\begin{figure}... \end{figure}%
\footnote{...}
\renewcommand{\foo}{...}
\par
```

or even a blank line—because in L<sup>A</sup>T<sub>E</sub>X a blank line is equivalent to `\par` and the meaning of `\par` is “end-paragraph”; in my opinion if explicit end-of-paragraph markup is given before the end of an element, it has to be respected, and the preceding paragraph has to be fully finished off before proceeding further, even inside an element like “proof” whose end-element formatting requires integration

with the end of the paragraph text. And TeX nically speaking, a \par token that comes from a blank line and one that comes from the sequence of characters \ p a r are equally explicit. I hope to add support for \footnote in the future, as it seems to be a legitimate markup possibility in that context from a purely logical point of view, but there are additional technical complications if one wants to handle it in full generality

**mjd,1999/02/08**

\peek@branch This is a generalized “look at next token and choose some action based on it” function.

```

560 \def\peek@branch#1#2{%
561   \let\peek@b#1\let\peek@space#2\futurelet\@let@token\peek@a
562 }
563 \def\peek@skipping@spaces#1{\peek@branch#1\peek@skip@space}
564 \def\peek@a{%
565   \ifx\@let@token\@sptoken \expandafter\peek@space
566   \else \expandafter\peek@b\fi
567 }
568 \lowercase{\def\peek@skip@space} {\futurelet\@let@token\peek@a}%

```

\check@punct For this one we need to recognize and grab for inclusion any of the following tokens: , ; . ! ?, both catcode 12 (standard L<sup>A</sup>T<sub>E</sub>X value) and catcode 13 (as might hold when the Babel package is being used). We do not support a space preceding the punctuation since that would be considered simply invalid markup if a display-math environment were demoted to in-line math; and we want to keep their markup as parallel as possible. If punctuation does not follow, then the \check@qed branch is not applicable.

```

569 \def\check@punct{\futurelet\@let@token\check@punct@a}
570 \def\check@punct@a{%
571   \edef\@tempa{%
572     \ifx\@let@token\@sptoken\@nx\finish@end
573     \else\ifx\@let@token ,\@nx\check@qed
574     \else\ifx\@let@token .\@nx\check@qed
575     \else\check@punct@b % check the less common possibilities
576     \fi\fi\fi
577   }%
578   \@tempa
579 }
580 \begingroup
581 \toks@a{%
582   \ifx\@let@token ;\@nx\check@qed
583   \else\ifx\@let@token ?\@nx\check@qed
584   \else\ifx\@let@token !\@nx\check@qed
585   }%
586 \toks@c{\fi\fi\fi}%
587 \catcode`.=\active \catcode`\,=\active \catcode`\;=\active
588 \catcode`\?=\active \catcode`\!=\active
589 \toks@b{%
590   \else\ifx\@let@token ,\@nx\check@qed
591   \else\ifx\@let@token .\@nx\check@qed

```

```

592     \else\ifx\@let@token ;\@nx\check@qed
593     \else\ifx\@let@token ?\@nx\check@qed
594     \else\ifx\@let@token !\@nx\check@qed
595     \else\@nx\finish@end
596     \fi\fi\fi\fi\fi
597 }
598 \xdef\check@punct@b{%
599   \the\toks@a\the\toks@b\the\toks@c
600 }
601 \endgroup
602 \let\found@punct\empty
603 \def\check@qed#1{%
604   \gdef\found@punct{#1}%
605   \peek@skipping@spaces\check@qed@a
606 }
607 \def\check@qed@a{%
608   \ifx\end\@let@token \xp\check@qed@b
609   \else \xp\finish@end
610   \fi
611 }

```

For each environment ENV that takes an implied qed at the end, the control sequence ENVqed must be defined; and it must include suitable code to yield the desired results in a displayed equation.

```

612 \def\check@qed@b#1#2{%
613   \@ifundefined{#2qed}{}{%
614     \toks@\xp{\found@punct\csname#2qed\endcsname}%
615     \xdef\found@punct{\the\toks@}%
616   }%
617   \finish@end
618   \end{#2}%
619 }

```

`\@end` The lookahead for punctuation following a display requires mucking about with the normal operation of `\end`. Although this is not exactly something to be done lightly, on the other hand this whole package is so over-the-top anyway, what's a little more going to hurt? And rationalizing this aspect of equation markup is a worthy cause. Here is the usual definition of `\end`.

```

\def\end#1{
  \csname end#1\endcsname \checkend{#1}%
  \expandafter\endgroup\if@endpe\doendpe\fi
  \if@ignore \global\ignorefalse \ignorespaces \fi
}

```

We can improve the chances of this code surviving through future minor changes in the fundamental definition of `\end` by taking a little care in saving the original meaning.

```

620 \def@tempa#1\endcsname#2@nil{\def\@tempa{#1#2}%
621 \expandafter@tempa\end{#1}\@nil
622 \def\end#1{\csname end#1\endcsname \@tempa{#1}}%

```

Why don't we call `\CheckCommand` here? Because that doesn't help end users much; it works better to use it during package testing by the maintainer.

If a particular environment needs to call a different end action, the end command of the environment should be defined to gobble two args and then call a function like `\check@punct@or@qed`.

```

623 \def\check@punct@or@qed#1{%
624   \xdef\found@punct{\emptyset}% BRM: punctuation was being remembered past this eqn.
625   \def\finish@end{\csname end\#1\endcsname\latex@end{#1}}%
626   \check@punct
627 }
```

`\eqpunct` User-settable function for handling the punctuation at the end of an equation.  
You could, for example, define it to just discard the punctuation.

```
628 \newcommand\eqpunct[1]{\thinspace#1}
```

`\set@label` `\set@label` just sets `\@currentlabel` but it takes the counter as an argument, in the hope that L<sup>A</sup>T<sub>E</sub>X will some day provide an improved labeling system that includes type info on the labels.

```
629 \providecommand\set@label[2]{\protected@edef\@currentlabel{#2}}
```

`\eq@topspace` The action of `\eq@topspace` is complicated by the need to test whether the ‘short’ versions of the display skips should be used. This can be done only after the final parshape and indent have been determined, so the calls of this function are buried relatively deeply in the code by comparison to the calls of `\eq@botspace`. This also allows us to optimize slightly by setting the above-skip with `\parskip` instead of `\vskip`. #1 is either `\noindent` or `\vskip\parskip`.

BRM: Hmm; we need to do \*`@setspace` BEFORE this for small skips to work!

```

630 \def\eq@topspace#1{%
631   \begingroup
632     \global\let\EQ@shortskip\@False
```

If we are in `dgroup` or `dgroup*` and not before the top one, we just insert `\intereqskip`. Otherwise we must check for `shortskip`.

```

633 \if\@And{\eq@group}{\@Not\eq@GRP@first@dmath}%
634 <trace> \breqn@debugmsg{Between lines}%
635   \parskip\intereqskip \penalty\intereqpenalty
636 <trace> \breqn@debugmsg{parskip=\the\parskip}%
637   \else
638     \eq@check@shortskip
639     \if\EQ@shortskip
640       \parskip\abovedisplayshortskip
641       \aftergroup\belowdisplayskip\aftergroup\belowdisplayshortskip
```

BRM: Not exactly T<sub>E</sub>X’s approach, but seems right...

```

642   \ifdim\predisplaysize>\z@\nointerlineskip\fi
643   \else
644     \parskip\abovedisplayskip
645   \fi
646   \fi
647   \if F\eq@frame
648   \else
649     \addtolength\parskip{\eq@framesep+\eq@framewd}%
650   \fi
651 <*trace>
652   \breqn@debugmsg{Topspace: \theb@ole\EQ@shortskip, \parskip=\the\parskip,
```

```

653     \predisplaysize=\the\predisplaysize}%
654   </trace>
655   #1%
656   \endgroup
657 }

```

\eq@check@shortskip

```

658 \def\eq@check@shortskip {%
659   \global\let\EQ@shortskips\@False
660   \setlength\dim@a{\abovedisplayskip+\ht\EO@numbox}%

```

Here we work around the hardwired standard TeX value and use the designer parameter instead.

```

661 \ifdim\leftskip<\predisplaysize
662 \else

```

If the display was preceded by a blank line, \predisplaysize is  $-\maxdimen$  and so we should insert a fairly large skip to separate paragraphs, i.e., no short skip. Perhaps this should be a third parameter \abovedisplayparskip.

```

663 \ifdim -\maxdimen=\predisplaysize
664 \else
665   \if R\eqnumside
666     \global\let\EQ@shortskips\@True
667   \else
668     \if\eq@shiftnumber
669     \else
670       \if T\eqnumplace
671         \ifdim\dim@a<\eq@firstht
672           \global\let\EQ@shortskips\@True
673         \fi
674       \else
675         \setlength\dim@b{\eq@vspan/2}%
676         \ifdim\dim@a<\dim@b
677           \global\let\EQ@shortskips\@True
678         \fi
679       \fi
680     \fi
681   \fi
682 \fi
683 \fi
684 }

```

At the end of an equation, need to put in a pagebreak penalty and some vertical space. Also set some flags to remove parindent and extra word space if the current paragraph text continues without an intervening \par.

```

685 \def\eq@botspace{%
686   \penalty\postdisplaypenalty

```

Earlier calculations will have set \belowdisplayskip locally to \belowdisplayshortskip if applicable. So we can just use it here.

```

687 \if F\eq@frame
688 \else
689   \addtolength\belowdisplayskip{\eq@framesep+\eq@framewd}%
690 \fi
691 \vskip\belowdisplayskip

```

```

692     \cendpartrue % kill parindent if current paragraph continues
693     \global\cignoretrue % ignore following spaces
694     \eq@resume@parshape
695 }

```

\eq@resume@parshape This should calculate the total height of the equation, including space above and below, and set prevgraf to the number it would be if that height were taken up by normally-spaced normal-height lines. We also need to restore parshape if it had a non-null value before the equation. Not implemented yet.

```
696 \def\eq@resume@parshape{}
```

## 26 Preprocessing the equation body

\eq@startup Here is the function that initially collects the equation material in a box.

```

697 \def\eq@startup{%
698   \global\let\EQ@hasLHS\cFalse
699   \setbox\z@\vbox\bgroup
700     \noindent\math@displaystyle
701     \penalty-\cMi
702 }

```

This setup defines the environment for the first typesetting pass, note the \hsize value for example.

```

703 \def\eq@setup@a{%
704   \everymath\everydisplay
705   \%let\cnewline\eq@cnewline % future possibility?
706   \let\\eq\cnewline
707   \let\insert\eq@insert \let\mark\eq@mark \let\vadjust\eq@vadjust
708   \hsize\maxdimen \pretolerance\cM

```

Here it is better not to use \cflushglue (0pt plus1fil) for \rightskip, or else a negative penalty (such as -99 for \prerelpenalty) will tempt TeX to use more line breaks than necessary in the first typesetting pass. Ideal values for \rightskip and \linepenalty are unclear to me, but they are rather sensitively interdependent. Choice of 10000 pt for rightskip is derived by saying, let's use a value smaller than 1 fil and smaller than \hsize, but more than half of \hsize so that if a line is nearly empty, the glue stretch factor will always be less than 2.0 and so the badness will be less than 100 and so TeX will not issue badness warnings.

```

709   \linepenalty\cM
710   \rightskip\z@\cplus\cM\p@ \leftskip\z@skip \parfillskip\z@skip
711   \clubpenalty\cne \widowpenalty\z@ \interlinepenalty\z@

```

After a relation symbol is discovered, binop symbols should start including a special offset space. But until then \EQ@prebin@space is a no-op.

```
712 \global\let\EQ@prebin@space\relax
```

Set binoppenalty and relpenalty high to prohibit line breaks after mathbins and mathrels. As a matter of fact, the penalties are then omitted by TeX, since bare glue without a penalty is *not* a valid breakpoint if it occurs within mathon–mathoff items.

```

713   \binoppenalty\cM \relpenalty\cM
714 }

```

The contents of an equation after the initial typesetting pass, as shown by `\showlists`. This is the material on which the `\eq@repack` function operates.

The equation was

```
a=b +\left(\frac{c\sp 2}{2} -d\right) +(e -f) +g
```

. The contents are shown in four parts in this figure and the next three. The first part contains two line boxes, one for the mathon node and one for the LHS.

```
\hbox(0.0+0.0)x16383.99998, glue set 1.6384
.\mathon
.\penalty -10000
.\glue(\rightskip) 0.0 plus 10000.0
\penalty 1
\glue(\baselineskip) 7.69446
\hbox(4.30554+0.0)x16383.99998, glue set 1.63759
.\OML/cmm/m/it/10 a
.\glue 2.77771 minus 1.11108
.\penalty -10001
.\glue(\rightskip) 0.0 plus 10000.0
\penalty 2
\glue(\lineskip) 1.0
...
```

Figure 1: Preliminary equation contents, part 1

`\eq@capture` If an equation ends with a `\right` delim, the last thing on the math list will be a force-break penalty. Then don't redundantly add another forcing penalty. (question: when does a penalty after a linebreak not disappear? Answer: when you have two forced break penalties in a row). Ending punctuation, if any, goes into the last box with the mathoff kern. If the math list ends with a slanted letter, then there will be an italic correction added after it by TeX. Should we remove it? I guess so.

## 26.1 Capturing the equation

BRM: There's a problem here (or with `\ss@scan`). If the LHS has `\left` `\right` pairs, `\ss@scan` gets involved. It seems to produce a separate box marked w/`\penalty 3`. But it appears that `\eq@repack` is only expecting a single box for the LHS; when it measures that box it's missing the (typically larger) bracketed section, so the LHS is measured = $\approx$  0pt (or very small). I'm not entirely clear what Michael had in mind for this case; whether it's an oversight, or whether I've introduced some other bug. At any rate, my solution is to measure the RHS (accumulated in `\EQ@box`), at the time of the relation, and subtract that from the total size.

```
715 \newdimen\eq@wdR\eq@wdR\z@%BRM
716 \def\eq@capture{%
717 \ifnum\lastpenalty>-\@M \penalty-\@Mi \fi}
```

We want to keep the mathoff kern from vanishing at the line break, so that we can reuse it later.

This is the first part of the RHS, up to the `\right`, where a line break has been forced so that we can break open the left-right box.

```
...
\penalty 2
\glue(\lineskip) 1.0
\hbox(14.9051+9.50012)x16383.99998, glue set 1.63107
.\penalty -99
.\glue(\thickmuskip) 2.77771 minus 1.11108
.\OT1/cmr/m/n/10 =
.\glue(\thickmuskip) 2.77771 minus 1.11108
.\OML/cmm/m/it/10 b
.\penalty 888
.\glue -10.5553
.\rule(***)x0.0
.\penalty 10000
.\glue 10.5553
.\glue(\medmuskip) 2.22217 minus 1.66663
.\OT1/cmr/m/n/10 +
.\glue(\medmuskip) 2.22217 minus 1.66663
.\hbox(14.9051+9.50012)x43.36298
..\hbox(0.39998+23.60025)x7.36115, shifted -14.10013
...\OMX/cmex/m/n/5 \hat \hat R
..\hbox(14.9051+6.85951)x11.21368
..\hbox(14.9051+6.85951)x11.21368
.... [fraction contents, elided]
..\penalty 5332
..\glue -10.5553
..\rule(***)x0.0
..\penalty 10000
..\glue 10.5553
..\glue(\medmuskip) 2.22217 minus 1.66663
..\OMS/cmsy/m/n/10 \hat \hat @
..\glue(\medmuskip) 2.22217 minus 1.66663
..\OML/cmm/m/it/10 d
..\hbox(0.39998+23.60025)x7.36115, shifted -14.10013
...\OMX/cmex/m/n/5 \hat \hat S
.\penalty -10000
.\glue(\rightskip) 0.0 plus 10000.0
\penalty 3
\glue(\lineskip) 1.0
...
```

Figure 2: Preliminary equation contents, part 2

This is the remainder of the RHS after the post-\right split.

```
...
\penalty 3
\glue(\lineskip) 1.0
\hbox(7.5+2.5)x16383.99998, glue set 1.63239
.\penalty 888
.\glue -10.5553
.\rule(***)x0.0
.\penalty 10000
.\glue 10.5553
.\glue(\medmuskip) 2.22217 minus 1.66663
.\OT1/cmr/m/n/10 +
.\glue(\medmuskip) 2.22217 minus 1.66663
.\OT1/cmr/m/n/10 (
.\OML/cmm/m/it/10 e
.\penalty 5332
.\glue -10.5553
.\rule(***)x0.0
.\penalty 10000
.\glue 10.5553
.\glue(\medmuskip) 2.22217 minus 1.66663
.\OMS/cmsy/m/n/10 \hat \hat @
.\glue(\medmuskip) 2.22217 minus 1.66663
.\OML/cmm/m/it/10 f
.\kern1.0764
.\OT1/cmr/m/n/10 )
.\penalty 888
.\glue -10.5553
.\rule(***)x0.0
.\penalty 10000
.\glue 10.5553
.\glue(\medmuskip) 2.22217 minus 1.66663
.\OT1/cmr/m/n/10 +
.\glue(\medmuskip) 2.22217 minus 1.66663
.\OML/cmm/m/it/10 g
.\kern0.35878
.\penalty -10000
.\glue(\rightskip) 0.0 plus 10000.0
\glue(\baselineskip) 9.5
...
```

Figure 3: Preliminary equation contents, part 3

This is the mathoff fragment.

```
...
\glue(\baselineskip) 9.5
\hbox(0.0+0.0)x16383.99998, glue set 1.6384
.\mathoff
.\penalty 10000
.\glue(\parfillskip) 0.0
.\glue(\rightskip) 0.0 plus 10000.0
```

Figure 4: Preliminary equation contents, part 4

```
718 \keep@glue\@@endmath
719 \eq@addpunct
720 \@@par
721 \eq@wdL\z@
```

First snip the last box, which contains the mathoff node, and put it into \EQ@box. Then when we call \eq@repack it will recurse properly.

```
722 \setbox\tw@\lastbox
723 \global\setbox\EQ@box\hbox{\unhbox\tw@\unskip\unskip\unpenalty}%
724 \unskip\unpenalty
725 \global\setbox\EQ@copy\copy\EQ@box
726 %% \global\setbox\EQ@vimcopy\copy\EQ@vimbox
727 \clubpenalty\z@
728 \%batchmode\showboxbreadth\maxdimen\showboxdepth99\showlists\errorstopmode
729 \eq@wdR\z@\%BRM: eq@wdL patch
730 \eq@repack % recursive
```

Finally, add the mathon item to \EQ@box and \EQ@copy.

```
731 \setbox\tw@\lastbox
732 \global\setbox\EQ@box\hbox{\unhcopy\tw@\unskip\unpenalty \unhbox\EQ@box}%
733 \global\setbox\EQ@copy\hbox{\unhbox\tw@\unskip\unpenalty \unhbox\EQ@copy}%
734 \%batchmode\showbox\EQ@copy \showthe\eq@wdL\errorstopmode
735 \ifdim\eq@wdR>\z@\% BRM: eq@wdL patch
736 \setlength\dim@a{\wd\EQ@box-\eq@wdR
737 % Apparently missing a \thickmuskip = 5mu = 5/18em=0.277777777777.. ?
738 + 0.277777777777em}\% FUDGE??!?!?
739 \ifdim\dim@a>\eq@wdL
740 {*trace}
741 \breqn@debugmsg{Correcting LHS from \the\eq@wdL\space to
742 \the\dim@a = \the\wd\EQ@box - \the\eq@wdR}%
743 {/trace}
744 \eq@wdL\dim@a
745 \xdef\EQ@setwdL{\eq@wdL\the\eq@wdL\relax}%
746 \fi
747 \fi
748 {*trace}
749 \breqn@debugmsg{Capture: total length=\the\wd\EQ@box \MessageBreak
750 ===== has LHS=\theb@ole\EQ@hasLHS, \eq@wdL=\the\eq@wdL, \eq@wdR=\the\eq@wdR,
751 \MessageBreak
752 ===== \eq@wdCond=\the\eq@wdCond}%
753 {/trace}
754 \egroup % end vbox started earlier
```

```

755 <*trace>
756 %\debugwr{EQ@box}\debug@box\EQ@box
757 %\debugwr{EQ@copy}\debug@box\EQ@copy
758 </trace>
759 }

```

Now we have two copies of the equation, one in `\EQ@box`, and one in `\EQ@copy` with inconvenient stuff like inserts and marks omitted.

`\eq@addpunct` is for tacking on text punctuation at the end of a display, if any was captured by the ‘gp’ lookahead.

```

760 \def\eq@addpunct{%
761   \ifx\found@punct\@empty
762   \else \eqpunct{\found@punct}%
763   \fi
764   % BRM: Added; the punctuation kept getting carried to following environs
765   \xdef\found@punct{\@empty}%
766   \EQ@afterspace
767 }

```

Needed for the `dseries` environment, among other things.

```
768 \global\let\EQ@afterspace\@empty
```

`\eq@repack` The `\eq@repack` function looks at the information at hand and proceeds accordingly.

TeX Note: this scans BACKWARDS from the end of the math.

```

769 \def\eq@repack{%
770 % A previous penalty of 3 on the vertical list means that we need
771 % to break open a left-right box.
772 % \begin{macrocode}
773 \ifcase\lastpenalty
774   % case 0: normal case
775   \setbox\tw@\lastbox
776   \eq@repacka\EQ@copy \eq@repacka\EQ@box
777   \unskip
778   \or % case 1: finished recursing

```

Grab the `mathon` object since we need it to inhibit line breaking at bare glue nodes later.

```

779   \unpenalty
780   \setbox\tw@\lastbox
781   \eq@repacka\EQ@copy \eq@repacka\EQ@box
782   \xp\gobble
783   \or % case 2: save box width = LHS width

```

Don’t need to set `\EQ@hasLHS` here because it was set earlier if applicable.

```

784   \unpenalty
785   \setbox\tw@\lastbox
786   \setbox\z@\copy\tw@ \setbox\z@\hbox{\unhbox\z@\unskip\unpenalty}%
787   \addtolength\eq@wdL{\wd\z@}
788   \setlength\eq@wdR{\wd\EQ@box}% BRM: eq@wdL patch
789   \xdef\EQ@setwdL{\eq@wdL\the\eq@wdL\relax}%

```

At this point, box 2 typically ends with

```
.\mi10 a
.\glue 2.77771 plus 2.77771
```

```
.\penalty -10001
.\glue(\rightskip) 0.0 plus 10000.0
```

and we want to ensure that the thickmuskip glue gets removed. And we now arrange for `\EQ@copy` and `\EQ@box` to keep the LHS in a separate subbox; this is so that we can introduce a different penalty before the first relation symbol if necessary, depending on the layout decisions that are made later.

```
790   \global\setbox\EQ@copy\hbox{%
791     \hbox{\unhcopy\tw@\unskip\unpenalty\unskip}%
792     \box\EQ@copy
793   }%
794   \global\setbox\EQ@box\hbox{%
795     \hbox{\unhbox\tw@\unskip\unpenalty\unskip}%
796     \box\EQ@box
797   }%
798   \unskip
799   \or % case 3: unpack left-right box
800   \unpenalty
801   \eq@lrunpack
802   \else
803   \breqn@repack@err
804   \fi
805   \eq@repack % RECURSE
806 }
```

Error message extracted to streamline calling function.

```
807 \def\breqn@repack@err{%
808   \PackageError{breqn}{\eq@repack penalty neq 0,1,2,3}\relax
809 }
```

`\eq@repacka` We need to transfer each line into two separate boxes, one containing everything and one that omits stuff like `\inserts` that would interfere with measuring.

```
810 \def\eq@repacka#1{%
811   \global\setbox#1\hbox{\unhcopy\tw@\unskip
812   \count@-\lastpenalty
813   \ifnum\count@<\@M \else \advance\count@-\@M \fi
814   \unpenalty}
```

If creating the measure copy, ignore all cases above case 3 by folding them into case 1.

```
815   \ifx\EQ@copy#1\ifnum\count@>\thr@@ \count@{\@ne\fi\fi
816   \ifcase\count@
817     % case 0, normal line break
818     \penalty-\@M % put back the linebreak penalty
819   \or % case 1, do nothing (end of equation)
820     \relax
821   \or % case 2, no-op (obsolete case)
822   \or % case 3, transfer vspace and/or penalty
823     \ifx#1\EQ@box \eq@revspace \else \eq@revspaceb \fi
824   \or % case 4, put back an insert
825     \eq@reinsert
826   \or % case 5, put back a mark
827     \eq@remark
828   \or % case 6, put back a vadjust
```

```

829      \eq@readjust
830      \else % some other break penalty
831      \penalty-\count@
832      \fi
833      \unhbox#1}%
834 }

```

\eq@nulldisplay Throw in a null display in order to get predisplaysize etc.. My original approach here was to start the null display, then measure the equation, and set a phantom of the equation's first line before ending the null display. That would allow finding out if TeX used the short displayskips instead of the normal ones. But because of some complications with grouping and the desirability of omitting unnecessary invisible material on the vertical list, it seems better to just collect information about the display (getting \prevdepth requires \halign) and manually perform our own version of TeX's shortskip calculations. This approach also gives greater control, e.g.,, the threshold amount of horizontal space between predisplaysize and the equation's left edge that determines when the short skips kick in becomes a designer-settable parameter rather than hardwired into TeX.

```

835 \def\eq@nulldisplay{%
836   \begingroup \frozen@everydisplay\emptytoks
837   \@@display
838   \predisplaypenalty\@M \postdisplaypenalty\@M
839   \abovedisplayskip\z@skip \abovedisplayshortskip\z@skip
840   \belowdisplayskip\z@skip \belowdisplayshortskip\z@skip
841   \xdef\EQ@displayinfo{%
842     \prevgraf\the\prevgraf \predisplaysize\the\predisplaysize
843     \displaywidth\the\displaywidth \displayindent\the\displayindent
844     \listwidth\the\linewidth

```

Not sure how best to test whether leftmargin should be added. Let's do this for now [mjd,1997/10/08].

```

845   \ifdim\displayindent>\z@
846     \advance\listwidth\leftmargin
847     \advance\listwidth\rightmargin
848   \fi
849   \relax}%

```

An \halign containing only one \cr (for the preamble) puts no box on the vertical list, which means that no \baselineskip will be added (so we didn't need to set it to zero) and the previous value of prevdepth carries through. Those properties do not hold for an empty simple equation without \halign.

```

850   \halign{\#\cr}%
851   \@@enddisplay
852   \par
853   \endgroup
854   \EQ@displayinfo
855 }

```

\eq@newline Here we use \Qifnext so that in a sequence like  
\eq@newlinea ... \\  
\eq@newlineb [a,b]

LATeX does not attempt to interpret the [a,b] as a vertical space amount. We would have used \eq@break in the definition of \eq@newlineb except that it

puts in a `\keep@glue` object which is not such a good idea if a mathbin symbol follows—the indent of the mathbin will be wrong because the leading negative glue will not disappear as it should at the line break.

```
856 \def\eq@newline{%
857   \ifstar{\eq@newlinea\@M}{\eq@newlinea\eqinterlinepenalty}}
858 \def\eq@newlinea#1{%
859   \ifnext[{\eq@newlineb{#1}}{\eq@newlineb{#1}[\maxdimen]}]
860 \def\eq@newlineb#1[#2]{\penalty-\@M}
```

`\eq@revspace` When `\eq@revspace` (re-vspace) is called, we are the end of an equation line; we need to remove the existing penalty of  $-10002$  in order to put a `vadjust` object in front of it, then put back the penalty so that the line break will still take place in the final result.

```
861 \def\eq@revspace{%
862   \global\setbox\EQ@vimbox\vbox{\unvbox\EQ@vimbox
863     \unpenalty
864     \global\setbox\@ne\lastbox}%
865   \v@vadjust{\unvbox\@ne}%
866   \penalty-\@M
867 }
```

The b version is used for the `\EQ@copy` box.

```
868 \def\eq@revspaceb{%
869   \global\setbox\EQ@vimcopy\vbox{\unvbox\EQ@vimcopy
870     \unpenalty
871     \global\setbox\@ne\lastbox}%
872   \v@vadjust{\unvbox\@ne}%
873   \penalty-\@M
874 }
```

`\eq@break` The function `\eq@break` does a preliminary linebreak with a flag penalty.

```
875 \def\eq@break#1{\penalty-1000#1 \keep@glue}
```

## 27 Choosing optimal line breaks

The question of what line width to use when breaking an equation into several lines is best examined in the light of an extreme example. Suppose we have a two-column layout and a displayed equation falls inside a second-level list with nonzero `leftmargin` and `rightmargin`. Then we want to try in succession a number of different possibilities. In each case if the next possibility is no wider than the previous one, skip ahead to the one after.

1. First try `linewidth(2)`, the linewidth for the current level-2 list.
2. If we cannot find adequate linebreaks at that width, next try `listwidth(2)`, the sum of `leftmargin`, `linewidth`, and `rightmargin` for the current list.
3. If we cannot find linebreaks at that width, next try `linewidth (1)` (skipping this step if it is no larger than `listwidth(2)`).
4. If we cannot find linebreaks at that width, next try `listwidth(1)`.
5. If we cannot find linebreaks at that width, next try column width.

needs work

Figure 5: first-approximation parshape for equations

6. If we cannot find linebreaks at that width, next try text width.
7. If we cannot find linebreaks at that width, next try equation width, if it exceeds text width (i.e., if the style allows equations to extend into the margins).

At any given line width, we run through a series of parshape trials and, essentially, use the first one that gives decent line breaks. But the process is a bit more complicated in fact. In order to do a really good job of setting up the parshapes, we need to know how many lines the equation will require. And of course the number of lines needed depends on the parshape! So as our very first trial we run a simple first-approximation parshape (Figure 5) whose main purpose is to get an estimate on the number of lines that will be needed; it chooses a uniform indent for all lines after the first one and does not take any account of the equation number. A substantial majority of equations only require one line anyway, and for them this first trial will succeed. In the one-line case if there is an equation number and it doesn't fit on the same line as the equation body, we don't go on to other trials because breaking up the equation body will not gain us anything—we know that we'll have to use two lines in any case—so we might as well keep the equation body together on one line and shift the number to a separate line.

If we learn from the first trial that the equation body requires more than one line, the next parshape trial involves adjusting the previous parshape to leave room for the equation number, if present. If no number is present, again no further trials are needed.

Some remarks about parshape handling. The TeX primitive doesn't store the line specs anywhere, `\the\parshape` only returns the number of line specs. This makes it well nigh impossible for different packages that use `\parshape` to work together. Not that it would be terribly easy for the package authors to make inter-package collaboration work, if it were possible. If we optimistically conjecture that someone some day may take on such a task, then the thing to do, obviously, is provide a parshape interface that includes a record of all the line specs. For that we designate a macro `\@parshape` which includes not only the line specs, but also the line count and even the leading `\parshape` token. This allows it to be directly executed without an auxiliary if-empty test. It should include a trailing `\relax` when it has a nonempty value.

876 `\let\@parshape\@empty`

The function `\eq@measure` runs line-breaking trials on the copy of the equation body that is stored in the box register `\EQ@copy`, trying various possible layouts in order of preference until we get successful line breaks, where ‘successful’ means there were no overfull lines. The result of the trials is, first, a parshape spec that can be used for typesetting the real equation body in `\EQ@box`, and second, some information that depends on the line breaks such as the depth of the last line, the height of the first line, and positioning information for the equation number. The two main variables in the equation layout are the line width and the placement of the equation number, if one is present.

\eq@measure Run linebreak trials on the equation contents and measure the results.

```

877 \def\eq@measure{%
  If an override value is given for indentstep in the env options, use it.
  878 \ifdim\eq@indentstep=\maxdimen \eq@indentstep\eq@indentstep \fi
  If \eq@linewidth is nonzero at this point, it means that the user specified a
  particular target width for this equation. In that case we override the normal list
  of trial widths.
  879 \ifdim\eq@linewidth=\z@ \else \edef\eq@widths{{\the\eq@linewidth}}\fi
  880 \begingroup \eq@params
  881 \leftskip\z@skip
  Even if \hfuzz is greater than zero a box whose contents exceed the target width
  by less than hfuzz still has a reported badness value of 1000000 (infinitely bad).
  Because we use inf-bad to test whether a particular trial succeeds or fails, we want
  to make such boxes return a smaller badness. To this end we include an \hfuzz
  allowance in \rightskip. In fact, \eq@params ensures that \hfuzz for equations
  is at least 1pt.
  882 \rightskip\z@\@plus\columnwidth\@minus\hfuzz
  883 % \eqinfo
  884 \global\EQ@continue{\eq@trial}%
  885 \eq@trial % uses \eq@widths
  886 \eq@failout % will be a no-op if the trial succeeded
  887 \endgroup
  'local' parameter settings are passed outside the endgroup through \EQ@trial.
  888 \EQ@trial
  889 }

  890 <*trace>
  891 \def\debug@showmeasurements{%
  892 \breqn@debugmsg{=> \number\eq@lines\space lines}%
  893 \begingroup
  894 \def\@elt##1X##2{\MessageBreak===== \space\space##1/##2}%
  895 \let\@endelt@\empty
  896 \breqn@debugmsg{=> trial info:\eq@measurements}%
  897 \breqn@debugmsg{=> bounding box: \the\eq@wdT x\the\eq@vspan, badness=\the\eq@badness}%
  898 \let\@elt\relax \let\@endelt\relax
  899 \endgroup
  900 }
  901 \def\debug@showmeasurements{%
  902 \begingroup
  903 \def\@elt##1X##2{\MessageBreak===== ##1/##2}%
  904 \let\@endelt@\empty
  905 \breqn@debugmsg{==> Measurements: \number\eq@lines\space lines
    \eq@measurements
    \MessageBreak
    ===== bounding box: \the\eq@wdT x\the\eq@vspan, badness=\the\eq@badness
    \MessageBreak
    ===== \leftskip=\the\leftskip, \rightskip=\the\rightskip}%
  906 \endgroup
  907 }
  908 </trace>

```

Layout Trials Driver Basically, trying different sequences of parshapes.

```

\EQ@trial Init.
914 \let\EQ@trial\empty

\EQ@continue This is a token register used to carry trial info past a group boundary with only
one global assignment.
915 \newtoks\EQ@continue

\EQ@widths This is used for storing the actual line-width info of the equation contents after
breaking.
916 \let\EQ@widths\empty

\EQ@fallback
917 \let\EQ@fallback\empty

\eq@linewidths This is the list of target widths for line breaking.
===== BRM:
Odd; I don't think I've seen this use anything but \displaywidth...
918 \def\eq@linewidths{\displaywidth\linewidth\columnwidth}

\eq@trial The \eq@trial function tries each candidate line width in \eq@linewidths until
an equation layout is found that yields satisfactory line breaks.
919 \def\eq@trial{%
920   \ifx\empty\eq@linewidths
921     \global\EQ@continue{}%
922   \else
923     \iffalse{fi \exp\eq@trial@a \eq@linewidths}%
924   \fi
925   \the\EQ@continue
926 }

\eq@trial@a The \eq@trial@a function reads the leading line width from \eq@linewidths; if
the new line width is greater than the previous one, start running trials with it; otherwise do nothing with it. Finally, run a peculiar \edef that leaves
\eq@linewidths redefined to be the tail of the list. If we succeed in finding
satisfactory line breaks for the equation, we will reset \EQ@continue in such a
way that it will terminate the current trials. An obvious branch here would be
to check whether the width of \EQ@copy is less than \eq@linewidth and go im-
mediately to the one-line case if so. However, if the equation contains more than
one RHS, by default each additional RHS starts on a new line—i.e., we want the
ladder layout anyway. So we choose the initial trial on an assumption of multiple
lines and leave the one-line case to fall out naturally at a later point.
927 \def\eq@trial@a#1{%
928   \dim@c#1\relax
929   \if T\eq@frame \eq@frame@adjust\dim@c \fi
930   \ifdim\dim@c>\eq@linewidth
931     \eq@linewidth\dim@c
932   <trace> \breqn@debugmsg{Choose Shape for width(#1)=\the\eq@linewidth}%
933   \let\eq@trial@b\eq@trial@a
934   \csname eq@try@layout@\eq@layout\endcsname
935   <trace> \else
936   <trace> \breqn@debugmsg{Next width (#1) is shorter; skip it}%
937   \fi

```

```

938     \edef\eq@linewidths{\iffalse}\fi
939 }
940 \def\eq@frame@adjust#1{%
941   \%addtolength#1{-2\eq@framewd-2\eq@framesep}%
942   \dim@a\eq@framewd \advance\dim@a\eq@framesep
943   \advance#1-2\dim@a
944 }

===== Note cu-
rious control structure. Try to understand interaction of \EQ@fallback, \EQ@continue,
\eq@failout

945 \def\eq@trial@succeed{%
946   \aftergroup\breqn@debugmsg{End trial: Success!}%
947   \global\EQ@continue{\eq@trial@done}%
948 }

\eq@trial@done Success.

949 \def\eq@trial@done{%
950   \trace\breqn@debugmsg{End trial: Success!}%
951   \let\eq@failout\relax
952 }

\eq@trial@init This is called from \eq@trial@b to initialize or re-initialize certain variables as
needed when running one or more trials at a given line width. By default assume
success, skip the fallback code.

953 \def\eq@trial@init{\global\let\EQ@fallback\eq@nextlayout}

\eq@nextlayout In the fallback case cancel the current group to avoid unnecessary group nesting
(with associated save-stack cost, etc.).

954 \def\eq@nextlayout#1{%
955   \endgroup
956   \trace\breqn@debugmsg{ Nope ... that ain't gonna work.}%
957   \begingroup #1%
958 }

\eq@failout .

959 \def\eq@failout{%
960   \trace\breqn@debugmsg{End trial: failout}%
961   \global\let\EQ@trial\EQ@last@trial
962 }

\eq@trial@save Save the parameters of the current trial.

963 \def\eq@trial@save#1{%
964   (*trace)
965   % \begingroup \def\@elt##1##2{\MessageBreak==== \space\space##1##2}\let\@endelt\empty\breqn@debugmsg{=}
966   %           \breqn@debugmsg{= bounding box: \the\eq@wdT x\the\eq@vspan, badness=\the\eq@badness}
967   %           \let\@elt\relax \let\@endelt\relax
968   % \endgroup
969   /trace>
970   \xdef#1{%
971     \eq@linewidth\the\eq@linewidth
972     % save info about the fit
973     \eq@lines\the\eq@lines \eq@badness\the\eq@badness \def\@nx\eq@badline{\eq@badline}%

```

```

974     % save size info
975     \eq@wdT\the\eq@wdT \eq@wdMin\the\eq@wdMin
976     \eq@vspan\the\eq@vspan \eq@dp\the\eq@dp \eq@firstht\the\eq@firstht
977     % save info about the LHS
978     \eq@wdL\the\eq@wdL \def\@nx\EQ@hasLHS{\EQ@hasLHS}%
979     % save info about the numbering
980     \def\@nx\eq@hasNumber{\eq@hasNumber}%
981     % save info about the chosen layout
982     \def\@nx\eq@layout{\eq@layout}%
983     \def\@nx\eq@parshape{\@parshape}%
984     \def\@nx\eq@measurements{\eq@measurements}%
985     \def\@nx\adjust@rel@penalty{\adjust@rel@penalty}%
986     \def\@nx\eq@shiftnumber{\eq@shiftnumber}%
987     \def\@nx\eq@isIntertext{\@False}%
988   }%
989 }

```

\eq@trial@c By default this just runs \eq@trial@c; cf. \eq@trial@d.

```
990 \def\eq@trial@c{\eq@trial@c}
```

\eq@trial@c Run the equation contents through the current parshape.

```

991 \def\eq@trial@c#1#2{%
992   \trace@ \breqn@debugmsg{Trying layout "#1" with\MessageBreak===== parshape\space\exp\@gobble\@p
993   \begingroup
994   \eq@trial@init
995   \def\eq@layout{\#1}%
996   \setbox\z@\vbox{%
997     \hfuzz\maxdimen
998     \eq@trial@p % run the given parshape
999     \if\@Not{\eq@badline}%
1000       \eq@trial@save\EQ@trial

```

If there is a number, try the same parshape again with adjustments to make room for the number.

This is an awkward place for this: It only allows trying to fit the number w/the SAME layout shape!

```

1001 \if\eq@hasNumber\eq@retry@with@number\fi
1002 \if L\eq@layout \eq@check@density
1003 \else
1004   \if\@Not{\eq@badline}%
1005     \eq@trial@succeed
1006   \fi
1007   \fi
1008 \else
1009   \eq@trial@save\EQ@last@trial
1010 \fi
1011 }%
1012 \EQ@fallback{\#2}%
1013 \endgroup
1014 }

\eq@trial@d
1015 \def\eq@trial@d#1#2{\eq@trial@c{\#1}{#2}}

```

```

\eq@check@density
1016 \def\eq@check@density{%
1017 <trace> \breqn@debugmsg{Checking density for layout L}%
1018   \if\@Or{\@Not\EQ@hasLHS}{\eq@shortLHS}%
1019 <trace> \breqn@debugmsg{Density check: No LHS, or is short; OK}%
1020   \eq@trial@succeed
1021   \else\if\eq@dense@enough
1022     \eq@trial@succeed
1023   \fi\fi
1024 }

\eq@shortLHS Test to see if we need to apply the \eq@dense@enough test.
1025 \def\eq@shortLHS{\ifdim\eq@wdL>.44\eq@wdT 1\else 0\fi 0}

\def\eq@shortLHS{\@False} =====

\eq@trial@p Run a trial with the current \parshape and measure it.
1026 \def\eq@trial@p{%
1027   \parshape %
1028   \eq@dump@box\unhcopy\EQ@copy
1029   {\@par}%
1030   leave \parshape readable
1031   \eq@lines\prevgraf
1032   \eq@fix@lastline
1033   \let\eq@badline\@False
1034   \if i\eq@layout \ifnum\eq@lines>@ne \let\eq@badline\@True \fi\fi
1035   \eq@curline\eq@lines % loop counter for eq@measure@lines
1036   \let\eq@measurements\empty
1037   \eq@ml@record@indents
1038   \eq@measure@lines
1039   \eq@recalc
1040   <trace> \debug@showmeasurements
1041 }

\adjust@rel@penalty Normally this is a no-op.
1041 \let\adjust@rel@penalty\empty

\eq@fix@lastline Remove parfillskip from the last line box.
1042 \def\eq@fix@lastline{%
1043   \setbox\tw@\lastbox \dim@b\wd\tw@
1044   \eq@dp\dp\tw@

Remove \parfillskip but retain \rightskip. Need to keep the original line
width for later shrink testing.
1045   \nointerlineskip\hbox to\dim@b{\unhbox\tw@
1046     \skip@c\lastskip \unskip\unskip\hskip\skip@c
1047   }%
1048 }

\eq@recalc Calculate \eq@wdT et cetera.
1049 \def\eq@recalc{%
1050   \eq@wdT\z@ \eq@wdMin\maxdimen \eq@vspan\z@skip \eq@badness\z@
1051   \let\@elt\eq@recalc@a \eq@measurements \let\@elt\relax
1052 }

```

```

\eq@recalc@a
1053 \def\eq@recalc@a#1x#2+#3\endelt{%
1054   \eq@firstht#2\relax
1055   \let\elt\eq@recalc@b
1056   \elt#1x#2+#3\endelt
1057 }

\eq@recalc@b
1058 \def\eq@recalc@b#1X#2,#3x#4+#5@#6\endelt{%
1059   \setlength{\dim@a{#2+#3}}%
1060   \ifdim\dim@a>\eq@wdT \eq@wdT\dim@a \fi
1061   \ifdim\dim@a<\eq@wdMin \eq@wdMin\dim@a \fi
1062   \eq@dp#5\relax
1063   \addtolength{\eq@vspan{#1+#4+\eq@dp}}%
}

Record the max badness of all the lines in \eq@badness.
1064 \ifnum#6>\eq@badness \eq@badness#6\relax\fi
1065 }

\eq@layout A value of ? for \eq@layout means that we should deduce which layout to use by looking at the size of the components. Any other value means we have a user-specified override on the layout.
Layout Definitions. Based on initial equation measurements, we can choose a sequence of candidate parshapes that the equation might fit into. We accept the first shape that ‘works’, else fall to next one. [The sequence is hardcoded in the \eq@try@layout@jshape]. Would it be useful be more flexible? (eg. try layouts LDA, in order...)]
1066 \def\eq@layout{?}

\eq@try@layout@? This is a branching function used to choose a suitable layout if the user didn’t specify one in particular.
Default layout: Try Single line layout first, else try Multiline layouts
1067 \cnamedef{eq@try@layout@?}{%
1068   \let\eq@trial@b\eq@trial@c
1069   \edef\@parshape{\parshape 1 0pt \the\eq@linewidth\relax}%
1070 % \eq@trial@b{i}{\eq@try@layout@multi}%
1071 \setlength{\dim@a{\wd\copy-2em}}% Fudge; can’t shrink more than this?
1072 % if we’re in a numbered group, try hard to fit within the numbers
1073 \dim@b\eq@linewidth
1074 \if\eq@shiftnumber\else\if\eq@group
1075   \if\eq@hasNumber\addtolength{\dim@b{-\wd\copy-\eqnumsep}}%
1076   \else\if\grp@hasNumber\addtolength{\dim@b{-\wd\GRP@numbox-\eqnumsep}}%
1077   \fi\fi\fi
1078 \ifdim\dim@a<\dim@b% Do we even have a chance of fitting to one line?
1079 <trace> \breqn@debugmsg{Choose Shape: (\the\wd\copy) may fit in \the\dim@b}%
}

BRM: assuming it might fit, don’t push too hard
1080 \setlength{\dim@b{\columnwidth-\dim@a+\eq@wdCond}}%
1081 \rightskip\z@\plus\dim@b\minus\hfuzz
1082 \eq@trial@b{i}{\eq@try@layout@multi}%
1083 \else
1084 <trace> \breqn@debugmsg{Choose Shape: Too long (\the\wd\copy) for one line}
1085 
```

```

1086           (free width=\the\dim@b)}%
1087   </trace>
1088     \eq@try@layout@multi
1089   \fi
1090 }

Layout Multiline layout: If no LHS, try Stepped(S) layout Else try Stepped(S),
Ladder(L), Drop-ladder(D) or Stepladder(l), depending on LHS length.

1091 \def\eq@try@layout@multi{%
1092   \if\EQ@hasLHS
1093     \ifdim\eq@wdL>\eq@linewidth
1094   <trace>      \breqn@debugmsg{Choose Shape: LHS \the\eq@wdL > linewidth}%
Find the total width of the RHS. If it is relatively short, a step layout is the thing
to try.

1095   \setlength\dim@a{\wd\EQ@copy-\eq@wdL}%
1096   \ifdim\dim@a<.25\eq@linewidth \eq@try@layout@S
1097   \else \eq@try@layout@l
1098   \fi
1099   % BRM: Originally .7: Extreme for L since rhs has to wrap within the remaining 30+!%
1100   \else\ifdim\eq@wdL>.50\eq@linewidth
1101   <*trace>
1102     \breqn@debugmsg{Choose Shape: LHS (\the\eq@wdL) > .50 linewidth (linewidth=\the\eq@line
1103   </trace>
1104     \eq@try@layout@D
1105   \else
1106   <trace>      \breqn@debugmsg{Choose Shape: LHS (\the\eq@wdL) not extraordinarily wide}%
1107     \eq@try@layout@L
1108   \fi\fi
1109   \else
1110   <trace>      \breqn@debugmsg{Choose Shape: No LHS here}%
Try one-line layout first, then step layout.

1111   \eq@try@layout@S % (already checked case i)
1112   \fi
1113 }

```

\eq@try@layout@D Change the penalty before the first mathrel symbol to encourage a break there.  
 Layout D=Drop-Ladder Layout, for wide LHS.

```

L0000000ONG LHS
= RHS
= ...

```

If fails, try Almost-Columnar layout

```

1114 \def\eq@try@layout@D{%
1115   \setlength\dim@a{\eq@linewidth -\eq@indentstep}%
1116   \edef\@parshape{\parshape 2
1117     Opt \the\eq@wdL\space \the\eq@indentstep\space \the\dim@a\relax
1118   }%
1119   \def\adjust@rel@penalty{\penalty-99 }%
1120   \eq@trial@b{D}{\eq@try@layout@A}%
1121 }

```

\eq@try@layout@L Try a straight ladder layout. Preliminary filtering ensures that \eq@wdL is less than 70 of the current line width.

```

Layout L=Ladder layout
LHS = RHS
= RHS
...

```

If fails, try Drop-ladder layout. NOTE: This is great for some cases (multi relations?), but tends to break really badly when it fails....

```

1122 \def\eq@try@layout@L{%
1123   \setlength{\dim@b}{\eq@linewidth-\eq@wdL}%
1124   \edef\@parshape{\parshape 2 0pt \the\eq@linewidth\space
1125     \the\eq@wdL\space \the\dim@b\relax
1126   }%
1127   \eq@trial@b{L}{\eq@try@layout@D}%
1128 }

```

`\eq@try@layout@S` In the “stepped” layout there is no LHS, or LHS is greater than the line width and RHS is small. Then we want to split up the equation into lines of roughly equal width and stagger them downwards to the right, leaving a small amount of whitespace on both sides. But also, if there is an equation number, we want to try first a layout that leaves room for the number. Otherwise it would nearly always be the case that the number would get thrown on a separate line.

Layout S=Stepped layout, typically no LHS or very long, variations on

```

STUFF ....
+ MORE STUFF ...
+ MORE STUFF ...

```

If fails, try Almost-Columnar layout

```

1129 \def\eq@try@layout@S{%
1130   \setlength{\dim@b}{\eq@linewidth-2\eqmargin}%
   \advance\dim@b-1em%

```

About how many lines will we need if `\dim@b` is the line width?

```

1131 \int@a\wd\copy\divide\int@a\dim@b

```

Adjust the target width by number of lines times `indentstep`. We don’t need to decrement `\int@a` because TeX division is integer division with truncation.

```

1132 \addtolength{\dim@b}{-\int@a\eq@indentstep}%

```

Adjust for equation number. But try not to leave too little room for the equation body.

```

1133 \if\eq@hasNumber
1134   \ifdim\dim@b>15em%
1135 %     \advance\dim@b-\eqnumsep \advance\dim@b-\wd\copy\eq@numbox
1136     \addtolength{\dim@b}{-\eq@wdNum}%
1137   \fi
1138 \fi

```

Now some hand-waving to set up the parshape.

```

1139 \int@a\z@%
1140 \def\@tempa{\dim}%
1141 \edef\@parshape{\parshape 2 0pt \the\dim@b\space
1142   \the\eqmargin\space\the\dim@b\relax}%
1143 \eq@trial@b{S}{\eq@try@layout@A}%
1144 }

```

\eq@try@layout@1 This is the “step-ladder” layout: similar to the drop-ladder layout but the LHS is too wide and needs to be broken up.

Layout 1 = Stepladder Similar to Drop-Ladder, but LHS is long and needs to be broken up. If fails, try Almost-Columnar layout

```

1145 \def\eq@try@layout@1{%
1146   \setlength\dim@a{\eq@linewidth -\eq@indentstep}%
1147   \int@a\eq@wdL \divide\int@a\dim@a
1148   \advance\int@a\tw@
1149   \edef\@parshape{\parshape \number\int@a\space
1150     Opt \the\eq@linewidth
1151   }%
1152   \advance\int@a-\tw@
1153   \setlength\dim@b{2\eq@indentstep}%
1154   \setlength\dim@c{\eq@linewidth -\dim@b}%
1155   \edef\@parshape{\@parshape
1156     \replicate{\int@a}{\space\the\eq@indentstep\space\the\dim@a}%
1157     \space\the\dim@b\space\the\dim@c\relax
1158   }%
1159   \eq@trial@b{l}{\eq@try@layout@A}%
1160 }
```

\eq@try@layout@A In the “almost-columnar” layout, which is the layout of last resort, we let all lines run to the full width and leave the adjusting of the indents to later.

Layout A = Almost-Columnar layout. Pretty much straight full width, more of a last-resort. If fails, give up.

```

1161 \def\eq@try@layout@A{%
1162   \edef\@parshape{\parshape 1 Opt \the\eq@linewidth\relax}%
1163   \if\EQ@hasLHS \def\adjust@rel@penalty{\penalty-99 }\fi
1164   \eq@trial@b{A}{}%
1165 }
```

\eq@shiftnumber MH: Should be moved to a section where all keys are set to defaults.

```
1166 \let\eq@shiftnumber\@False
```

\eq@retry@with@number@a Number placement adjustments

```

1167 \def\eq@retry@with@number{%
1168   \if\eq@shiftnumber
1169   \trace \breqn@debugmsg{Place number: Shifted number requested}%
1170   \else
```

Condition and right numbers? We’re just going to have to shift.

```

1171   \ifdim\eq@wdCond>\z@\if R\eqnumside
1172   \trace \breqn@debugmsg{Place number: Condition w/Right number => Shift number}%
1173   \let\eq@shiftnumber\@True
1174   \fi\fi
```

Compute free space.

```

1175 %   \dim@b\eqnumsep\advance\dim@b\wd\EQ@numbox
1176   \dim@b\eq@wdNum
1177   \if L\eqnumside
1178     \ifdim\@totalleftmargin>\dim@b\dim@b\@totalleftmargin\fi
1179   \else
1180     \addtolength\dim@b{\@totalleftmargin}%
1181   \fi
1182   \setlength\dim@a{\eq@linewidth-\dim@b}\advance\dim@a1em\relax% Allowance for shrink?
```

Set up test against 1-line case only if not in a group

```
1183     \int@a\@ne\if\eq@group\int@a\maxint\fi
```

Now check for cases.

```
1184     \if\eq@shiftnumber          % Already know we need to shift
1185     \else\ifdim\eq@wdT<\dim@a % Fits!
```

left & right skips will be done later, and parshape adjusted if needed.

```
1186 <trace>      \breqn@debugmsg{Place number: eqn and number fit together}%
1187 %    \else\ifnum\eq@lines=\int@a % Shift, if single line, unless inside a dgroup.
```

NOTE: this is too strong for dgroup!

```
1188 <*trace>
1189 %      \breqn@debugmsg{Place number: single line too long with number => Shift number \the\int...
1190 </trace>
1191 %      \let\eq@shiftnumber\@True
1192 \else
```

Retry: use leftskip for space for number(for now; whether right/left) & adjust  
parshape

```
1193 %      \leftskip\wd\EQ@numbox\advance\leftskip\eqnumsep
1194 \setlength\leftskip{\eq@wdNum}%
1195 \setlength\rightskip{\z@\oplus\dim@a}%
1196 \adjust@parshape\@parshape
1197 <*trace>
1198     \breqn@debugmsg{Place number: Try with \leftskip=\the\leftskip, \rightskip=\the\rightskip,
1199                     \MessageBreak==== parshape\space\@xp\@gobble\@parshape}%
1200 </trace>
1201     \nointerlineskip
1202     \edef\eq@prev@lines{\the\eq@lines}%
1203     \edef\eq@prev@badness{\the\eq@badness}% BRM
1204     \eq@trial@p
1205     \int@a\eq@prev@badness\relax\advance\int@a 50\relax%?
1206     \int@b\eq@prev@lines \if\eq@group\advance\int@b\@ne\fi% Allow 1 extra line in group
1207     \ifnum\eq@lines>\int@b % \eq@prev@lines
1208 <trace>      \breqn@debugmsg{Adjustment causes more breaks => Shift number}%
1209     \let\eq@shiftnumber\@True
1210     \else\if\eq@badline
1211 <trace>      \breqn@debugmsg{Adjustment causes bad lines (\the\eq@badness) => Shift}%
1212     \let\eq@shiftnumber\@True
1213     \else\ifnum\eq@badness>\int@a % BRM: New case
1214 <*trace>
1215     \breqn@debugmsg{Adjustment is badder than previous
1216                     (\the\eq@badness >> \eq@prev@badness) => Shift}%
1217 </trace>
1218     \let\eq@shiftnumber\@True
1219     \else
1220 <trace>      \breqn@debugmsg{Adjustment succeeded}%
1221     \fi\fi%\fi
1222     \fi\fi\fi
```

If we got shifted, restore parshape, etc,

```
1223     \if\eq@shiftnumber
1224     \EQ@trial% Restore parshape & other params,
1225     \leftskip\z@\let\eq@shiftnumber\@True % But set shift & leftskip
1226     \edef\@parshape{\eq@parshape}% And copy saved parshape back to 'working copy' !?!?
```

```

1227     \fi
1228     \eq@trial@save\EQ@trial      % Either way, save the trial state.
1229   \fi
1230 }

```

\adjust@parshape Varies depending on the layout.

Adjust a parshape variable for a given set of left|right skips. Note that the fixed part of the left|right skips effectively comes out of the parshape widths (NOT in addition to it). We also must trim the widths so that the sum of skips, indents and widths add up to no more than the \eq@linewidth.

```

1231 \def\adjust@parshape#1{%
1232   \xp\adjust@parshape@a#1\relax
1233   \edef#1{\temp@a}%
1234 }

```

\adjust@parshape@a

\adjust@parshape@b

```

1235 \def\adjust@parshape@a#1 #2\relax{%
1236   \setlength\dim@a{\leftskip+\rightskip}%
1237   \edef\temp@a{\#1}%
1238   \adjust@parshape@b#2 @ @ \relax
1239 }
1240 \def\adjust@parshape@b#1 #2 {%
1241   \ifx @#1\edef\temp@a{\temp@a\relax}%
1242   \xp\gobble
1243   \else
1244     \dim@b#1\relax
1245     \dim@c#2\relax
1246     \addtolength\dim@c{\dim@a+\dim@b}%
1247     \ifdim\dim@c>\eq@linewidth\setlength\dim@c{\eq@linewidth}\fi
1248     \addtolength\dim@c{-\dim@b}%
1249     \edef\temp@a{\temp@a\space\the\dim@b\space\the\dim@c}%
1250   \fi
1251   \adjust@parshape@b
1252 }

```

\eq@ml@record@indents Plunk the parshape's indent values into an array for easy access when constructing \eq@measurements.

```

1253 \def\eq@ml@record@indents{%
1254   \int@a\z@
1255   \def\@tempa{%
1256     \advance\int@a\one
1257     \xp\edef\csname eq@i\number\int@a\endcsname{\the\dim@a}%
1258     \ifnum\int@a<\int@b \afterassignment\@tempb \fi
1259     \dim@a
1260   }%
1261   \def\@tempb{\afterassignment\@tempa \dim@a}%
1262   \def\@tempc##1##2 {\int@b##2\afterassignment\@tempa\dim@a}%
1263   \xp\@tempc\@parshape
1264 }

```

\@endelt This is a scan marker. It should get a non-expandable definition. It could be \relax, but let's try a chardef instead.

```

1265 \chardef\@endelt='?

```

\eq@measurements This is similar to a parshape spec but for each line we record more info: space above, indent, width x height + dp, and badness.

```
1266 \def\eq@measurements{%
1267   \oelt 4.5pt/5.0pt,66.0ptx6.8pt+2.4pt@27\oendelt
1268   ...
1269 }
```

\eq@measure@lines Loop through the list of boxes to measure things like total height (including interline stretch), etc.. We check the actual width of the current line against the natural width—after removing rightskip—in case the former is *less* than the latter because of shrinkage. In that case we do not want to use the natural width for RHS-max-width because it might unnecessarily exceed the right margin.

```
1270 \def\eq@measure@lines{%
1271   \let\eq@ml@continue\eq@measure@lines
1272   \setbox\tw@\lastbox \dim@b\wd\tw@ % find target width of line
1273   \setbox\z@\hbox to\dim@b{\unhbox\tw@}% check for overfull
1274   \eq@badness\badness
1275   \ifnum\eq@badness<\inf@bad \else \let\eq@badline\@True \fi
1276   \eq@ml@a \eq@ml@continue
1277 }
```

\eq@ml@a

```
1278 \def\eq@ml@a{%
1279   \setbox\tw@\hbox{\unhbox\z@\unskip}% find natural width
1280   {*trace}
1281   \ifnum\eq@badness<\inf@bad\else\breqn@debugmsg{!?! Overfull: \the\wd\tw@ > \the\dim@b}\fi
1282   /{*trace}
```

Is actual width less than natural width?

```
1283 \ifdim\dim@b<\wd\tw@ \setlength\dim@a{\dim@b}% shrunken line
1284 \else \setlength\dim@a{\wd\tw@}% OK to use natural width
1285 \fi
1286 \addtolength\dim@a{-\leftskip}% BRM: Deduct the skip if we're retrying w/number
```

If there's no aboveskip, assume we've reached the top of the equation.

```
1287 \skip@a\lastskip \unskip \unpenalty
1288 \ifdim\skip@a=\z@
1289   \let\eq@ml@continue\relax % end the recursion
1290 \else
1291   % Sum repeated vskips if present
1292   \def\@tempa{%
1293     \ifdim\lastskip=\z@
1294     \else \addtolength\skip@a{\lastskip}\unskip\unpenalty \exp\@tempa
1295     \fi
1296   }%
1297 \fi
1298 \edef\eq@measurements{\oelt
1299   \the\skip@a\space X% extra space to facilitate extracting only the
1300   % dimen part later
1301   \csname eq@i%
1302   \ifnum\eq@curline<\parshape \number\eq@curline
1303   \else\number\parshape
1304   \fi
1305 }
```

```

1306     \eq@measurements
1307 }
1308 \advance\eq@curline\m@ne
1309 \ifnum\eq@curline=\z@ \let\eq@ml@continue\relax\fi
1310 }

\eq@ml@vspace Handle an embedded vspace.
1311 \def\eq@ml@vspace{%
1312   \global\advance\eq@vspan\lastskip \unskip\unpenalty
1313   \ifdim\lastskip=\z@ \else \exp\eq@ml@vspace \fi
1314 }

\eq@dense@enough
1315 \def\eq@dense@enough{%
1316   \ifnum\eq@lines<\thr@@
1317   <trace> \breqn@debugmsg{Density check: less than 3 lines; OK}%
1318   \c@True
1319   \else
1320   \ifdim\eq@wdL >.7\eq@wdT
1321   <trace> \breqn@debugmsg{Density check: LHS too long; NOT OK}%
1322   \c@False
1323   \else \exp\exp\exp\eq@dense@enough@a
1324   \fi
1325   \fi
1326 }

\true@false@true
1327 \def\true@false@true{\fi\fi\iftrue\iffalse\iftrue}

\false@false@false
1328 \def\false@false@false{\fi\fi\iffalse\iffalse\iffalse}

\false@true@false
1329 \def\false@true@false{\fi\fi\iffalse\iftrue\iffalse}

\eq@density@factor This number specifies, for the ladder layout, how much of the equation's bounding box should contain visible material rather than whitespace. If the amount of visible material drops below this value, then we switch to the drop-ladder layout. The optimality of this factor is highly dependent on the equation contents; .475 was chosen as the default just because it worked well with the sample equation, designed to be as average as possible, that I used for testing.
1330 \def\eq@density@factor{.475}

\eq@dense@enough@a Calculate whether there is more visible material than whitespace within the equation's bounding box. Sum up the actual line widths and compare to the total "area" of the bounding box. But if we have an extremely large number of lines, fall back to an approximate calculation that is more conservative about the danger of exceeding \maxdimen.
1331 \def\eq@dense@enough@a{%
1332   \c@True \fi
1333   \ifnum\eq@lines>\sixt@n
1334   \eq@dense@enough@b

```

```

1335     \else
1336         \dim@b\z@ \let\@elt\eq@delt \eq@measurements
1337         \dim@c\eq@density@factor\eq@wdT \multiply\dim@c\eq@lines
1338 <trace>    \breqn@debugmsg{Density check: black \the\dim@b/\eq@density@factor total \the\dim@c}
1339         \ifdim\dim@b>\dim@c \true@false@true \else \false@false@false \fi
1340     \fi
1341 }

```

\eq@delt Args are space-above, indent, width, height, depth, badness.

```
1342 \def\eq@delt#1#2,#3#4+#5@#6{\endelt{\addtolength\dim@b{#3}}%
```

\eq@dense@enough@b This is an approximate calculation used to keep from going over \maxdimen if the number of lines in our trial break is large enough to make that a threat. If l, t, n represent left-side-width, total-width, and number of lines, the formula is

$$l/t < .4n/(.9n-1)$$

or equivalently, since rational arithmetic is awkward in TeX: b

$$l/t < 4n/(9n-10)$$

```

1343 \def\eq@dense@enough@b{%
1344     \int@b\eq@wdT \divide\int@b\p@
1345     \dim@b\eq@wdL \divide\dim@b\int@b
1346     \dim@c\eq@lines\p@ \multiply\dim@c\f@ur
1347     \int@b\eq@lines \multiply\int@b 9 \advance\int@b -10%
1348     \divide\dim@c\int@b
1349 <trace> \breqn@debugmsg{Density check: l/t \the\dim@b\space< \the\dim@c\space 4n/(9n-10)?}%
1350     \ifdim\dim@b<\dim@c \true@true@true \else \false@true@false \fi
1351 }

```

\eq@parshape

```
1352 \let\eq@parshape\empty
```

\eq@params The interline spacing and penalties in \eq@params are used during both preliminary line breaking and final typesetting.

```

1353 \def\eq@params{%
1354     \baselineskip\eqlinespacing
1355     \lineskip\eqlineskip \lineskiplimit\eqlineskiplimit

```

Forbid absolutely a pagebreak that separates the first line or last line of a multiline equation from the rest of it. Or in other words: no equation of three lines or less will be broken at the bottom of a page; instead it will be moved whole to the top of the next page. If you really really need a page break that splits the first or last line from the rest of the equation, you can always fall back to \pagebreak, I suppose.

```

1356     \clubpenalty\@M \widowpenalty\@M \interlinepenalty\eqinterlinepenalty
1357     \linepenalty199 \exhyphenpenalty5000 % was 9999: make breaks at, eg. \* a bit easier.

```

For equations, hfuzz should be at least 1pt. But we have to fake it a little because we are running the equation through TeX's paragrapher. In our trials we use minus 1pt in the rightskip rather than hfuzz; and we must do the same during final breaking of the equation, otherwise in borderline cases TeX will use two lines instead of one when our trial indicated that one line would be enough.

```

1358 \ifdim\hfuzz<\p@ \hfuzz\p@ \fi
1359 %\hfuzz=2pt
1360 % \ifdim\hfuzz<2pt\relax \hfuzz2pt \fi
1361 \parfillskip\z@skip
1362 % \hfuzz\z@
```

Make sure we skip T<sub>E</sub>X's preliminary line-breaking pass to save processing time.

```

1363 \tolerance9999 \pretolerance\m@ne
1364 }
```

## 28 Equation layout options

Using the notation C centered, I indented (applied to the equation body), T top, B bottom, M middle, L left, R right (applied to the equation number), the commonly used equation types are C, CRM, CRB, CLM, CLT, I, IRM, IRB, ILM, ILT. In other words, CLM stands for Centered equation body with Left-hand Middle-placed equation number, and IRB stands for Indented equation with Right-hand Bottom-placed equation number.

Here are some general thoughts on how to place an equation tag. Currently it does not work as desired: the L option positions the tag app. 10 lines below the math expression, the RM doesn't position the tag on the baseline for single-line math expressions. Therefore I am going to first write what I think is supposed to happen and then implement it.

Below is a small list where especially the two three specifications should be quite obvious, I just don't want to forget anything and it is important to the implementation.

**Definition 1** If a display consists of exactly one line, the tag should always be placed on the same baseline as the math expression.

The remaining comments refer to multi-line displays.

**Definition 2** If a tag is to be positioned at the top (T), it should be placed such that the baseline of the tag aligns with the baseline of the top line of the display.

**Definition 3** If a tag is to be positioned at the bottom (B), it should be placed such that the baseline of the tag aligns with the baseline of the bottom line of the display.

**Definition 4** If a tag is to be positioned vertically centered (M), it should be placed such that the baseline of the tag is positioned exactly halfway between the baseline of the top line of the display and the baseline of the bottom line of the display.

Definitions 1–3 are almost axiomatic in their simplicity. Definition 4 is different because I saw at least two possibilities for which area to span:

- Calculate distance from top of top line to the bottom of the bottom line, position the vertical center of the tag exactly halfway between those two extremes.

- Calculate the distance from the baseline of the top line to the baseline of the bottom line, position the baseline of the tag exactly halfway between these two extremes.

Additional combinations of these methods are possible but make little sense in my opinion. I have two reasons for choosing the latter of these possibilities: Firstly, two expressions looking completely identical with the exception of a superscript in the first line or a subscript in the last line will have the tag positioned identically. Secondly, then M means halfway between T and B positions which makes good sense and then also automatically fulfills Definition 1.

From an implementation perspective, these definitions should also make it possible to fix a deficiency in the current implementation, namely that the tag does not influence the height of a display, even if the display is a single line. This means that two single-line expressions in a `dgroup` can be closer together than `\intereqskip` if the math expressions are (vertically) smaller than the tag.

## 29 Centered Right-Number Equations

```
\eq@dump@box #1 might be \unhbox or \unhcopy; #2 is the box name.
```

```
1365 \def\eq@dump@box#1#2{%
1366 \%debug@box#1%
1367 \noindent #1#2\setbox\f@ur\lastbox \setbox\tw@\lastbox
```

If the LHS contains shrinkable glue, in an L layout the alignment could be thrown off if the first line is shrunk noticeably. For the time being, disable shrinking on the left-hand side. The proper solution requires more work

**mjd,1999/03/17**

```
1368 \if L\eq@layout \box\tw@ \else\unhbox\tw@\fi
1369 \adjust@rel@penalty \unhbox\f@ur
1370 }
```

Various typesetting bits, invoked from `\eq@finish` BRM: This has been extensively refactored from the original `breqn`, initially to get left|right skips and `parshape` used consistently, ultimately to get most things handled the same way, in the same order.

Given that left and right skips have been set, typeset the frame, number and equation with the given number side and placement

```
1371 \def\eq@typeset@Unnumbered{%
1372   \eq@typeset@frame
1373   \eq@typeset@equation
1374 }
1375 \def\eq@typeset@LM{%
1376   \setlength\dim@{\af{(\eq@vspan+\ht\EQ@numbox-\dp\EQ@numbox)/2}}%
1377   \eq@typeset@leftnumber
1378   \eq@typeset@frame
1379   \eq@typeset@equation
1380 }
```

Typeset equation and left-top number (and shifted)

```
1381 \def\eq@typeset@LT{%
1382   \dim@a\eq@firstht
1383   \eq@typeset@leftnumber
1384   \eq@typeset@frame
1385   \eq@typeset@equation
1386 }
```

Typeset equation and left shifted number

```
1387 \def\eq@typeset@LShifted{%
1388   % place number
1389   \copy\EQ@numbox \penalty\@M
1390   \dim@a\eq@lineskip
1391   \if F\eq@frame\else
1392     \setlength\dim@a{\eq@framesep+\eq@framewd}%
1393   \fi
1394   \kern\dim@a
1395   \eq@typeset@frame
1396   \eq@typeset@equation
1397 }
```

Typeset equation and right middle number

```
1398 \def\eq@typeset@RM{%
1399   \setlength\dim@a{(\eq@vspan+\ht\EQ@numbox-\dp\EQ@numbox)/2}%
1400   \eq@typeset@rightnumber
1401   \eq@typeset@frame
1402   \eq@typeset@equation
1403 }
```

Typeset equation and right bottom number

```
1404 \def\eq@typeset@RB{%
1405   % NOTE: is \eq@dp useful here
1406   \setlength\dim@a{\eq@vspan-\ht\EQ@numbox-\dp\EQ@numbox}%
1407   \eq@typeset@rightnumber
1408   \eq@typeset@frame
1409   \eq@typeset@equation
1410 }
```

Typeset equation and right shifted number

```
1411 \def\eq@typeset@RShifted{%
1412   % place number
1413   \eq@typeset@frame
1414   \eq@typeset@equation
1415   \penalty\@M
1416   \dim@a\eq@lineskip
1417   \if F\eq@frame\else
1418     \addtolength\dim@a{\eq@framesep+\eq@framewd}%
1419   \fi
1420   \parskip\dim@a
1421   \hbox to\hsize{\hfil\copy\EQ@numbox}\@@par%
1422 }
```

Debugging aid to show all relevant formatting info for a given eqn.

```
1423 {*trace}
1424 \def\debug@showformat{%
1425   \breqn@debugmsg{Formatting Layout:\eq@layout\space Center/indent: \eqindent\space}
```

```

1426 Number placement \eqnumside\eqnumplace:
1427 \MessageBreak==== \eq@linewidth=\the\eq@linewidth, \@totalleftmargin=\the\@totalleftmargin
1428 \MessageBreak==== Centered Lines=\theb@le\eq@centerlines, Shift Number=\theb@le\eq@shift
1429 \MessageBreak==== \eq@wdT=\the\eq@wdT, \eq@wdMin=\the\eq@wdMin,
1430 \MessageBreak==== LHS=\theb@le\EQ@hasLHS: \eq@wdL=\the\eq@wdL,
1431 \MessageBreak==== \eq@firstht=\the\eq@firstht, \eq@vspan=\the\eq@vspan
1432 \MessageBreak==== \eq@wdNum=\the\eq@wdNum
1433 \MessageBreak==== \eq@wdCond=\the\eq@wdCond, \conditionsep=\the\conditionsep,
1434 \MessageBreak==== \leftskip=\the\leftskip, \rightskip=\the\rightskip,
1435 \MessageBreak==== \abovedisplayskip=\the\abovedisplayskip,
1436 \MessageBreak==== \belowdisplayskip=\the\belowdisplayskip
1437 \MessageBreak==== parshape=\eq@parshape}%
1438 }
1439 </trace>

```

Set left & right skips for centered equations, making allowances for numbers (if any, right, left) and constraint. === Amazingly, I've managed to collect all the positioning logic for centered equations in one place, so it's more manageable. Unfortunately, by the time it does all it needs to do, it has evolved I'm (re)using so many temp variables, it's becoming unmanageable!

```

1440 \def\eq@C@setsides{%
1441   % \dim@c = space for number, if any, and not shifted.
1442   \dim@c\z@
1443   \if\eq@hasNumber\if\eq@shiftnumber\else
1444     \dim@c\eq@wdNum
1445   \fi\fi
1446   % \dim@e = space for condition(on right), if any and formula is only a single line.(to center)
1447   % but only count it as being right-aligned if we're not framing, since the frame must enclose
1448   \dim@e\z@
1449   \if F\eq@frame
1450     \ifnum\eq@lines=\@ne\ifdim\eq@wdCond>\z@
1451       \setlength{\dim@e}{\eq@wdCond+\conditionsep}%
1452     \fi\fi\fi
1453   % \dim@b = minimum needed on left max(totalleftmargin, left number space)
1454   \dim@b\z@
1455   \if L\eqnumside\ifdim\dim@b<\dim@c
1456     \dim@b\dim@c
1457   \fi\fi
1458   \ifdim\dim@b<\@totalleftmargin
1459     \dim@b\z@
1460   \else
1461     \addtolength{\dim@b}{-\@totalleftmargin}%
1462   \fi
1463   % \dim@d = minimum needed on right max(condition, right number space)
1464   \dim@d\dim@e
1465   \if R\eqnumside\ifdim\dim@d<\dim@c
1466     \dim@d\dim@c
1467   \fi\fi
1468   % \dim@a = left margin; initially half available space
1469   % \dim@c = right margin; ditto
1470   \setlength{\dim@a}{(\eq@linewidth-\eq@wdT+\dim@e+\@totalleftmargin)/2}%
1471   \dim@c=\dim@a
1472   % If too far to the left
1473   \ifdim\dim@a<\dim@b

```

```

1474     \addtolength\dim@c{\dim@a-\dim@b}%
1475     \ifdim\dim@c<\z@\dim@c=\z@\fi
1476     \dim@a=\dim@b
1477     % Or if too far to the right
1478     \else\ifdim\dim@c<\dim@d
1479         \addtolength\dim@c{\dim@c-\dim@d}%
1480         \ifdim\dim@a<\z@\dim@a=\z@\fi
1481         \dim@c=\dim@d
1482     \fi\fi
1483     % Now, \dim@d,\dim@e is the left & right glue to center each line for centerlines
1484     \setlength\dim@e{\eq@wdT-\eq@wdMin}\dim@d=\z@

```

NOTE: Need some work here centering when there's a condition

```

1485 % \advance\dim@e-\eq@wdT\multiply\dim@e-1\relax
1486 % \if\eq@wdMin<\dim@e\dim@e\eq@wdMin\fi
1487 % \multiply\dim@e-1\relax\advance\dim@e\eq@wdT
1488 \dim@d\z@
1489 \if\eq@centerlines
1490     \divide\dim@e2\relax
1491     \dim@d=\dim@e
1492 \fi
1493 \setlength\leftskip{\dim@a@plus\dim@d}%
1494 \addtolength\dim@e{\dim@c}%
1495 \setlength\rightskip{\z@@plus\dim@e}@\minus5\p@
1496 % Special case: if framing, reduce the stretchiness of the formula (eg. condition)
1497 % Or if we have a right number, FORCE space for it
1498 \dim@b\z@
1499 \if F\eq@frame\else
1500     \dim@b\dim@c
1501 \fi
1502 \if\@And{\eq@hasNumber}{\@Not{\eq@shiftnumber}}%
1503     \if R\eqnumside
1504         \dim@c\eq@wdNum
1505         \ifdim\dim@c>\dim@b
1506             \dim@b\dim@c
1507         \fi
1508     \fi
1509 \fi
1510 % If either of those cases requires hard rightskip, move that part from glue.
1511 \ifdim\dim@b>\z@
1512     \addtolength\dim@e{-\dim@c}%
1513     \rightskip\dim@b@plus\dim@e@\minus5\p@
1514 \fi
1515 % And peculiar further special case: in indented environs, width isn't where it would seem
1516 \ifdim\eq@wdCond>\z@
1517     \addtolength\rightskip{-\@totalleftmargin}%
1518 \fi
1519 \parfillskip\z@skip
1520 }

```

Set the left and right side spacing for indented equations Some things handled by eq@C@setsides that probably apply here????

- centerlines
- \@totalleftmargin: SHOULD we move farther right?

Leftskip is normally just the requested indentation

```
1521 \def\eq@I@setsides{%
1522   \leftskip\mathindent
```

But move left, if shifted number presumably because of clashed w/ number?

```
1523 \if\eq@shiftnumber
1524   \setlength{\dim@a}{\eq@linewidth-\eq@wdT-\mathindent}%
1525   \ifdim\dim@a<\z@
1526     \leftskip=\z@ % Or something minimal?
1527   \fi
1528 \fi
```

Push gently from right.

```
1529 \dim@a=\z@
1530 \setlength{\dim@b}{\eq@linewidth-\leftskip-\eq@wdMin}%
```

Special case: if framing be much more rigid(?)

```
1531 \if F\eq@frame
1532 \else
1533   \setlength{\dim@a}{\eq@linewidth-\leftskip-\eq@wdT}
1534   \addtolength{\dim@b}{-\dim@a}%
1535 \fi
1536 % Or force the space for right number, if needed
1537 % \begin{macrocode}
1538 \if@\And{\eq@hasNumber}{\Not{\eq@shiftnumber}}%
1539   \if R\eqnumside
1540     \dim@c=\eq@wdNum
1541     \if\dim@c>\dim@a
1542       \addtolength{\dim@b}{-\dim@c}%
1543     \dim@a=\dim@c
1544   \fi
1545 \fi
1546 \fi
1547 \setlength{\rightskip}{\dim@a\plus\dim@b \minus\hfuzz }%\hfuzz\z@
1548 \parfillskip\z@skip
1549 }
```

**Typesetting pieces: frame, equation and number (if any)**  $\dim@a$  should contain the downward displacement of number's baseline

```
1550 \def\eq@typeset@leftnumber{%
1551   \setlength{\skip@c}{\dim@a-\ht\EQ@numbox}%
1552   \vglue\skip@c% NON discardable
1553   \copy\EQ@numbox \penalty\@M
1554   \kern-\dim@a
1555 }
1556 \def\eq@typeset@rightnumber{%
1557   \setlength{\skip@c}{\dim@a-\ht\EQ@numbox}%
1558   \vglue\skip@c% NON discardable
1559   \hbox to \hsize{\hfil\copy\EQ@numbox}\penalty\@M
1560   \kern-\dim@a
1561 }
1562 \def\eq@typeset@equation{%
1563   \nobreak
1564   \eq@params\eq@parshape
```

```

1565   \nointerlineskip\noindent
1566   \add@grp@label
1567   \eq@dump@box\unhbox\EQ@box\@@par
1568 }

```

## 30 Framing an equation

- \eqframe The \eqframe function is called in vertical mode with the reference point at the top left corner of the equation, including any allowance for \fboxsep. Its arguments are the width and height of the equation body, plus fboxsep.

```

1569 \newcommand\eqframe[2]{%
1570   \begingroup
1571   \fboxrule=\eq@framewd\relax\fboxsep=\eq@framesep\relax
1572   \framebox{\z@rule\@height#2\kern#1}%
1573   \endgroup
1574 }

```

The frame is not typeset at the correct horizontal position. Will fix later.

```

1575 \def\eq@addframe{%
1576   \hbox to\z@{%
1577     \setlength\dim@a{\eq@framesep+\eq@framewd}%
1578     \kern-\dim@a
1579     \vbox to\z@{\kern-\dim@a
1580       \hbox{\eqframe{\eq@wdT}{\eq@vspan}}%
1581       \vss
1582     }%
1583     \hss
1584   }%
1585 }
1586 \def\eq@typeset@frame{%
1587   \if F\eq@frame\else
1588     % Tricky: put before \noindent, so it's not affected by glue in \leftskip
1589     \nobreak\nointerlineskip
1590     \vbox to\eq@firstht{\moveright\leftskip\hbox to\z@{\eq@addframe\hss}\vss}%
1591     \kern-\eq@firstht
1592   \fi
1593 }

```

## 31 Delimiter handling

The special handling of delimiters is rather complex, but everything is driven by two motives: to mark line breaks inside delimiters as less desirable than line breaks elsewhere, and to make it possible to break open left-right boxes so that line breaks between \left and \right delimiters are not absolutely prohibited. To control the extent to which line breaks will be allowed inside delimiters, set \eqbreakdepth to the maximum nesting depth. Depth 0 means never break inside delimiters.

Note: \eqbreakdepth is not implemented as a L<sup>A</sup>T<sub>E</sub>X counter because changes done by \setcounter etc. are always global.

It would be natural to use grouping in the implementation—at an open delimiter, start a group and increase mathbin penalties; at a close delimiter, close the

group. But this gives us trouble in situations like the `array` environment, where a close delimiter might fall in a different cell of the `\halign` than the open delimiter. Ok then, here's what we want the various possibilities to expand to. Note that `\right` and `\biggr` are being unnaturally applied to a naturally open-type delimiter.

```
( -> \delimiter"4... \after@open
\left( ->
  \@@left \delimiter"4... \after@open
\right( ->
  \@@right \delimiter"4... \after@close
\biggl( ->
  \mathopen{\@@left \delimiter... \vrule... \@@right.}
  \after@open
\biggr( ->
  \mathclose{\@@left \delimiter... \vrule... \@@right.}
  \after@close
\bigg\|vert ->
  \mathord{\@@left \delimiter... \vrule... \@@right.}
\biggm\|vert ->
  \mathrel{\@@left \delimiter... \vrule... \@@right.}
```

First save the primitive meanings of `\left` and `\right`.

```
1594 \csname\left\endcsname
1595 \csname\right\endcsname
```

The variable `\lr@level` is used by the first mathrel in an equation to tell whether it is at top level: yes? break and measure the LHS, no? keep going.

```
1596 \newcount\lr@level
```

It would be nice to have better error checking here if the argument is not a delimiter symbol at all.

```
1597 \def\eq@left{%
1598   \ifnext .{\eq@nullleft}{\begingroup \let\delimiter\eq@left@a}%
1599 }
1600 \def\eq@right{%
1601   \ifnext .{\eq@nullright}{\begingroup \let\delimiter\eq@right@a}%
1602 }
```

The arguments are: #1 delim symbol, #2 .

```
1603 \def\eq@left@a#1 #2{\endgroup\@@left\delimiter#1 \after@open}
1604 \def\eq@right@a#1 #2{\endgroup
1605   \@@right\delimiter#1 \after@close \ss@scan{#1}%
1606 }
```

The null versions.

```
1607 \def\eq@nullleft#1{\@@left#1\after@open}
1608 \def\eq@nullright#1{\@@right#1\after@close}
```

Here is the normal operation of `\biggl`, for example.

```
\biggl ->\mathopen \bigg
{\mathopen}
```

```
\bigg #1->{\hbox {$\left #1\vbox to14.5\p@ {} \right . \n@space $}}
#1<- (
```

For paren matching: ) Like `\left`, `\biggl` coerces its delimiter to be of `mathopen` type even if its natural inclination is towards closing.

The function `\delim@reset` makes delimiter characters work just about the same as they would in normal L<sup>A</sup>T<sub>E</sub>X.

```
1609 \def\delim@reset{%
1610   \let\after@open\relax \let\after@close\relax
1611   \let\left\@@left \let\right\@@right
1612 }
```

If the `amsmath` or `exscale` package is loaded, it will have defined `\bBigg@`; if not, the macros `\big` and variants will have hard-coded point sizes as inherited through the ages from `plain.tex`. In this case we can kluge a little by setting `\big@size` to `\p@`, so that our definition of `\bBigg@` will work equally well with the different multipliers.

```
1613 \@ifundefined{bBigg@}{% not defined
1614   \let\big@size\p@
1615   \def\big{\bBigg@\{8.5}\def\Big{\bBigg@\{11.5}\%
1616   \def\bigg{\bBigg@\{14.5}\def\Bigg{\bBigg@\{17.5}\%
1617   \def\biggg{\bBigg@\{20.5}\def\Biggg{\bBigg@\{23.5}\%
1618 }{}}
1619 \def\bBigg@#1#2{%
1620   {\delim@reset
1621     \left#2%
1622     \vrule\@height#1\big@size\@width-\nulldelimiterspace
1623     \right.
1624   }%
1625 }

.
.

1626 \def\bigl#1{\mathopen\big{#1}\after@open}
1627 \def\Bigl#1{\mathopen\Big{#1}\after@open}
1628 \def\biggl#1{\mathopen\bigg{#1}\after@open}
1629 \def\Biggl#1{\mathopen\Bigg{#1}\after@open}
1630 \def\bigggl#1{\mathopen\biggg{#1}\after@open}
1631 \def\Bigggl#1{\mathopen\Biggg{#1}\after@open}
1632
1633 \def\bigr#1{\mathclose\big{#1}\after@close}
1634 \def\Bigr#1{\mathclose\Big{#1}\after@close}
1635 \def\biggr#1{\mathclose\bigg{#1}\after@close}
1636 \def\Biggr#1{\mathclose\Bigg{#1}\after@close}
1637 \def\bigggr#1{\mathclose\biggg{#1}\after@close}
1638 \def\Biggg#1{\mathclose\Biggg{#1}\after@close}
1639
1640 %% No change needed, I think. [mjd,1998/12/04]
1641 %%\def\bigm{\mathrel\big}
1642 %%\def\Bigm{\mathrel\Big}
1643 %%\def\biggm{\mathrel\bigg}
1644 %%\def\Biggm{\mathrel\Bigg}
1645 %%\def\bigggm{\mathrel\biggg}
1646 %%\def\Bigggm{\mathrel\Biggg}
```

`\m@DeL` Original definition of `\m@DeL` from `flexisym` is as follows. `\m@DeR` and `\m@DeB` are `\d@DeL` the same except for the math class number.

`\m@DeR`  
`\d@DeR`  
`\m@DeB`  
`\d@DeB`

```

\def\m@DeL#1#2#3{%
  \delimiter"4\@xp\delim@a\csname sd@#1#2#3\endcsname #1#2#3 }

```

Save the existing meanings of `\m@De` [LRB].

```

1647 \let\m@DeL\m@DeL \let\m@DeR\m@DeR \let\m@DeB\m@DeB
1648 \def\d@DeL#1#2#3{%
1649   \delimiter"4\@xp\delim@a\csname sd@#1#2#3\endcsname #1#2#3 \after@open
1650 }
1651 \def\d@DeR#1#2#3{%
1652   \delimiter"5\@xp\delim@a\csname sd@#1#2#3\endcsname #1#2#3 \after@close
1653 }
1654 \def\d@DeB#1#2#3{%
1655   \delimiter"0\@xp\delim@a\csname sd@#1#2#3\endcsname #1#2#3 \after@bidir
1656 }

```

BRM: These weren't defined, but apparently should be. Are these the right values???

```
1657 \let\m@DeA\m@DeA\let\d@DeA\m@DeA%
```

`\after@open` `\after@open` and `\after@close` are carefully written to avoid the use of grouping  
`\after@close` and to run as fast as possible. `\zero@bop` is the value used for `\prebinoppenalty`  
`\after@bidir` at delimiter level 0, while `\bop@incr` is added for each level of nesting. The  
`\zero@bop` standard values provide that breaks will be prohibited within delimiters below  
`\bop@incr` nesting level 2.

```

1658 \let\after@bidir\empty
1659 \mathchardef\zero@bop=888 \relax
1660 \mathchardef\bop@incr=4444 \relax
1661 \def\after@open{%
1662   \global\advance\lr@level\one
1663   \prebinoppenalty\bop@incr \multiply\prebinoppenalty\lr@level
1664   \advance\prebinoppenalty\zero@bop
1665   \ifnum\eqbreakdepth<\lr@level
1666     \let\m@Bin\m@Bin

```

Inside delimiters, add some fillglue before binops so that a broken off portion will get thrown flush right. Also shift it slightly further to the right to ensure that it clears the opening delimiter.

```

1667   \else
1668     \eq@binoffset=\eqbinoffset
1669     \advance\eq@binoffset\lr@level\eqdelimoffset plus1fill\relax
1670     \def\dt@fill@cancel{\hskip\z@ minus1fill\relax}%
1671   \fi
1672   \penalty\@M % BRM: discourage break after an open fence?
1673 }
1674 \def\after@close{%
1675   \global\advance\lr@level\one
1676   \prebinoppenalty\bop@incr \multiply\prebinoppenalty\lr@level
1677   \advance\prebinoppenalty\zero@bop
1678   \ifnum\eqbreakdepth<\lr@level
1679     \else \let\m@Bin\d@DeBin
1680   \fi

```

When we get back to level 0, no delimiters, remove the stretch component of `\eqbinoffset`.

```

1681     \ifnum\lr@level<\@ne \eq@binoffset=\eqbinoffset\relax \fi
1682 }

```

\subsup@flag \ss@scan is called after a \right delimiter and looks ahead for sub and superscript tokens. If sub and/or superscripts are present, we adjust the line-ending penalty to distinguish the various cases (sub, sup, or both). This facilitates the later work of excising the sub/sup box and reattaching it with proper shifting.

#### Sub/Superscript measurement

BRM: There's possibly a problem here. When \ss@scan gets invoked after a \left... \right pair in the LHS during \eq@measure, it produces an extra box (marked with \penalty 3); Apparently \eq@repack expects only one for the LHS. The end result is \eq@wdL =*i* 0.0pt !!! (or at least very small)

```

1683 \let\subsup@flag=\count@
1684 \def\ss@delim@a#1#3#4{\xdef\right@delim@code{\number"#2#3#4}}

```

The argument of \ss@scan is an expanded form of a right-delimiter macro. We want to use the last three digits in the expansion to define \right@delim@code. The assignment to a temp register is just a way to scan away the leading digits that we don't care about.

```
1685 \def\ss@scan#1{%
```

This part of the code.

```

1686 \begingroup
1687   \let\delim@a\ss@delim@a \tempcnta#1\relax
1688 \endgroup
1689 \subsup@flag\OM \afterassignment\ss@scan@a \let@\let@token=}
1690 \def\ss@scan@a{%
1691   \ifx\let@token\sb \advance\subsup@flag\@ne\else
1692   \ifx\let@token\sp \advance\subsup@flag\tw@\else
1693     \ss@finish
1694     \expandafter\@firstoftwo % gobble \ss@scan@b
1695   \fi\fi
1696   \ss@scan@b\let@token
1697 }
1698 \def\ss@scan@b#1#2{#1{%

```

hack! coff!

```

1699   \let\m@Bin\m@@Bin \let\m@Rel\m@@Rel
1700   #2}\afterassignment\ss@scan@a \let@\let@token=}%
```

We need to keep following glue from disappearing—e.g., a thickmuskip or med-muskip from a following mathrel or mathbin symbol.

```

1701 \def\ss@finish{%
1702   \vadjust{\penalty\thr@@}%
1703   \penalty\right@delim@code \penalty-\subsup@flag \keep@glue
1704 }
```

\eq@lrunpack For \eq@lrunpack we need to break open a left-right box and reset it just in case it contains any more special breaks. After it is unpacked the recursion of \eq@repack will continue, acting on the newly created lines.

```
1705 \def\eq@lrunpack{\setbox\z@\lastbox
```

We remove the preceding glue item and deactivate baselineskip for the next line, otherwise we would end up with three items of glue (counting parskip) at this point instead of the single one expected by our recursive repacking procedure.

```
1706 \unskip \nointerlineskip
```

Then we open box 0, take the left-right box at the right end of it, and break that open. If the line-ending penalty is greater than 10000, it means a sub and/or superscript is present on the right delimiter and the box containing them must be taken off first.

```
1707 \noindent\unhbox\z@ \unskip
1708 \subsup@flag-\lastpenalty \unpenalty
1709 \xdef\right@delim@code{\number\lastpenalty}%
1710 \unpenalty
1711 \ifnum\subsup@flag>\@M
1712   \advance\subsup@flag-\@M
1713   \setbox\tw@\lastbox
1714 \else \setbox\tw@\box\voidb@x
1715 \fi
1716 \setbox\z@\lastbox
1717 \ifvoid\tw@ \unhbox\z@
1718 \else \lrss@reattach % uses \subsup@flag, box\z@, box\tw@
1719 \fi
```

The reason for adding a null last line here is that the last line will contain parfillskip in addition to rightskip, and a final penalty of 10000 instead of  $-1000N$  ( $1 \leq N \leq 9$ ), which would interfere with the usual processing. Setting a null last line and discarding it dodges this complication. The penalty value  $-10001$  is a no-op case in the case statement of \eq@repacka.

```
1720 \penalty-\@Mi\z@rule\@@par
1721 \setbox\z@\lastbox \unskip\unpenalty
1722 %%{\showboxbreadth\maxdimen\showboxdepth99\showlists}%
1723 }
```

\lrss@reattach Well, for a small self-contained computation, carefully hand-allocated dimens should be safe enough. But let the maintainer beware! This code cannot be arbitrarily transplanted or shaken up without regard to grouping and interaction with other hand-allocated dimens.

```
1724 \dimendef\sub@depth=8 \dimendef\sup@base=6
1725 \dimendef\prelim@sub@depth=4 \dimendef\prelim@sup@base=2
1726 \def\sym@xheight{\fontdimen5\textfont\tw@}
1727 \def\sup@base@one{\fontdimen13\textfont\tw@}
1728 \def\sub@base@one{\fontdimen16\textfont\tw@}
1729 \def\sub@base@two{\fontdimen17\textfont\tw@}
```

Note that only \sup@drop and \sub@drop come from the next smaller math style.

```
1730 \def\sup@drop{\fontdimen18\scriptfont\tw@}
1731 \def\sub@drop{\fontdimen19\scriptfont\tw@}
```

Provide a mnemonic name for the math axis fontdimen, if it's not already defined.

```
1732 \providecommand{\mathaxis}{\fontdimen22\textfont\tw@}
```

Assumes box 2 contains the sub/sup and box 0 contains the left-right box. This is just a repeat of the algorithm in `tex.web`, with some modest simplifications from knowing that this is only going to be called at top level in a displayed equation, thus always `mathstyle = uncramped displaystyle`.

```

1733 \def\lrss@reattach{%
1734   \begingroup
1735   % "The TeXbook" Appendix G step 18:
1736   \setlength\prelim@sup@base{\ht\z@-\sup@drop}%
1737   \setlength\prelim@sub@depth{\dp\z@ +\sub@drop}%
1738   \unhbox\z@
1739   \ifcase\subsup@flag      % case 0: this can't happen
1740   \or \lr@script          % case 1: subscript only
1741   \or \lr@superscript     % case 2: superscript only
1742   \else \lr@subsup        % case 3: sub and superscript both
1743   \fi
1744   \endgroup
1745 }
1746 \def\lr@subscript{%
1747   \sub@depth\sub@base@one
1748   \ifdim\prelim@sub@depth>\sub@depth \sub@depth\prelim@sub@depth\fi
1749   \setlength\dim@a{\ht\tw@ -.8\sym@xheight}%
1750   \ifdim\dim@a>\sub@depth \sub@depth=\dim@a \fi
1751   \twang@adjust\sub@depth
1752   \lower\sub@depth\box\tw@
1753 }
1754 \def\lr@superscript{%
1755   \sup@base\sup@base@one
1756   \ifdim\prelim@sup@base>\sup@base \sup@base\prelim@sup@base\fi
1757   \setlength\dim@a{\dp\tw@ -.25\sym@xheight}%
1758   \ifdim\dim@a>\sup@base \sup@base\dim@a \fi
1759   \twang@adjust\sup@base
1760   \raise\sup@base\box\tw@
1761 }
1762 \def\lr@subsup{%
1763   \sub@depth\sub@base@two
1764   \ifdim\prelim@sub@depth>\sub@depth \sub@depth\prelim@sub@depth\fi
1765   \twang@adjust\sub@depth
1766   \lower\sub@depth\box\tw@
1767 }

```

For delimiters that curve top and bottom, the twang factor allows horizontal shifting of the sub and superscripts so they don't fall too far away (or too close for that matter). This is accomplished by arranging for (e.g.,) `\right\rangle` to leave a penalty  $N$  in the math list before the subsup penalty that triggers `\lrss@reattach`, where  $N$  is the mathcode of `\rangle` (ignoring “small” variant).

```

1768 \def\twang@adjust#1{%
1769   \begingroup
1770   @ifundefined{twang@\right@delim@code}{}{%
1771     \setlength\dim@d{#1-\mathaxis}%
1772     % put an upper limit on the adjustment
1773     \ifdim\dim@d>1em \dim@d 1em \fi
1774     \kern\csname twang@\right@delim@code\endcsname\dim@d
1775   }%
1776   \endgroup
1777 }

```

The method used to apply a “twang” adjustment is just an approximate solution

to a complicated problem. We make the following assumptions that hold true, approximately, for the most common kinds of delimiters:

1. The right delimiter is symmetrical top to bottom.
2. There is an upper limit on the size of the adjustment.
3. When we have a superscript, the amount of left-skew that we want to apply is linearly proportional to the distance of the bottom left corner of the superscript from the math axis, with the ratio depending on the shape of the delimiter symbol.

. By symmetry, Assumption 3 is true also for subscripts (upper left corner). Assumption 2 is more obviously true for parens and braces, where the largest super-extended versions consist of truly vertical parts with slight bending on the ends, than it is for a `\rangleangle`. But suppose for the sake of expediency that it is approximately true for rangle symbols also.

Here are some passable twang factors for the most common types of delimiters in `cutex10`, as determined by rough measurements from magnified printouts.

```
vert bar, double vert: 0
square bracket: -.1
curly brace: -.25
parenthesis: -.33
rangle: -.4
```

Let's provide a non-private command for changing the twang factor of a given symbol.

```
1778 \newcommand{\DeclareTwang}[2]{%
1779   \ifcat.\@nx#1\begin{group}
1780     \lccode`\~='#1\lowercase{\endgroup \DeclareTwang{\~}}{#2}%
1781   \else
1782     \xp\decl@twang#1?\@nil{#2}%
1783   \fi
1784 }
```

Note that this is dependent on a fixed interpretation of the mathgroup number #4 .

```
1785 \def\decl@twang#1#2#3#4#5#6#7\@nil#8{%
1786   \namedef{twang@\number"##4##5##6}{#8}%
1787 }
1788 \DeclareTwang{\rangle}{-.4}
1789 \DeclareTwang{\{}{-.33}
1790 \DeclareTwang{\brace}{-.25}
```

## 32 Series of expressions

The `dseries` environment is for a display containing a series of expressions of the form ‘A, B’ or ‘A and B’ or ‘A, B, and C’ and so on. Typically the expressions are separated by a double quad of space. If the expressions in a series don’t all fit in a single line, they are continued onto extra lines in a ragged-center format.

```
1791 \newenvironment{dseries}{\let\eq@hasNumber\@True \optarg\@dseries{}{}%
1792 \def\enddseries#1{\check@punct@\or@qed}%

```

And the unnumbered version of same.

```
1793 \newenvironment{dseries}{\let\eq@hasNumber\@False \@optarg\@dseries{}{}%  
1794 \cnamedef{enddseries}*#1{\check@punct@or@qed}%  
1795 \cnamedef{end@dseries}*\{\end@dseries}%  
1796 \def\@dseries[#1]{%
```

Turn off the special breaking behavior of mathrels etc. for math formulas embedded in a `dseries` environment.

BRM: DS Experiment: Use alternative display setup.

```
1797 % \def\display@setup{\displaystyle}%  
1798 \let\display@setup\dseries@display@setup  
1799 % Question: should this be the default for dseries???  
1800 % \let\eq@centerlines\@True  
1801 \global\eq@wdCond\z@
```

BRM: use special layout for `dseries`

```
1802 % \@dmath[#1]%=  
1803 \@dmath[layout={M},#1]=  
1804 \mathsurround\z@\@math \penalty\@Mi  
1805 \let\endmath\ends@math  
1806 \def\premath{%
```

BRM: Tricky to cleanup space OR add space ONLY BETWEEN math!

```
1807 \ifdim\lastskip<.3em \unskip  
1808 \else\ifnum\lastpenalty<\@M \dquad\fi\fi  
1809 }%
```

BRM: Tricky; if a subformula breaks, we'd like to start the next on new line!

```
1810 \def\postmath{\unpenalty\eq@addpunct \penalty\intermath@penalty \dquad \@ignoretrue}%=  
1811 \ignorespaces  
1812 }  
1813 \def\end@dseries{%=  
1814 \unskip\unpenalty  
1815 \@@endmath \mathsurround\z@\end@dmath  
1816 }
```

BRM: Try this layout for `dseries`: Essentially layout i, but w/o limit to 1 line.  
And no fallback!

```
1817 \def\eq@try@layout@M{%=  
1818 \edef\@parshape{\parshape 1 0pt \the\eq@linewidth\relax}%=  
1819 \eq@trial@b{M}{}%  
1820 }
```

BRM: Tricky to get right value here. Prefer breaks between formula if we've got to break at all.

```
1821 \%def\intermath@penalty{-201}%=  
1822 \def\intermath@penalty{-221}%=
```

BRM: A bit tighter than it was ( 1em minus .25em )

```
1823 \%newcommand\dquad{\hskip0.4em}  
1824 \newcommand\dquad{\hskip0.6em minus .3em}  
1825 \newcommand\premath{}\newcommand\postmath{}
```

Change the `math` environment to add `\premath` and `\postmath`. They are no-ops except inside a `dseries` environment.

Redefinition of `math` environment to take advantage of `dseries` env.

```

1826 \renewenvironment{math}{%
1827   \leavevmode \premath
1828   \ifmmode\@badmath\else\@@math\fi
1829 }%
1830 \ifmmode\@@endmath\else\@badmath\fi
1831 }
1832 \def\ends@math#1{\check@punct@or@qed}
1833 \def\end@math{%
1834   \ifmmode\@@endmath\else\@badmath\fi
1835   \postmath
1836 }

```

### 33 Equation groups

For many equation groups the strategy is easy: just center each equation individually following the normal rules for a single equation. In some groups, each equation gets its own number; in others, a single number applies to the whole group (and may need to be vertically centered on the height of the group). In still other groups, the equations share a parent number but get individual equation numbers consisting of parent number plus a letter.

If the main relation symbols in a group of equations are to be aligned, then the final alignment computations cannot be done until the end of the group—i.e.,, the horizontal positioning of the first  $n - 1$  equations cannot be done immediately. Yet because of the automatic line breaking, we cannot calculate an initial value of RHS-max over the whole group unless we do a trial run on each equation first to find an RHS-max for that equation. Once we know RHS-group-max and LHS-group-max we must redo the trial set of each equation because they may affect the line breaks. If the second trial for an equation fails (one of its lines exceeds the available width), but the first one succeeded, fall back to the first trial, i.e., let that equation fall out of alignment with the rest of the group.

All right then, here is the general idea of the whole algorithm for group alignment. To start with, ignore the possibility of equation numbers so that our equation group has the form:

```

LHS [1]  RHS [1,1]  RHS [1,2]  ...  RHS [1,n[1]]
LHS [2]  RHS [2,1]  RHS [2,2]  ...  RHS [2,n[2]]
...
LHS [3]  RHS [3,1]  RHS [3,2]  ...  RHS [3,n[3]]

```

The number of RHS's might not be the same for all of the equations. First, accumulate all of the equation contents in a queue, checking along the way to find the maximum width of all the LHS's and the maximum width of all the RHS's. Call these widths maxwd\_L and maxwd\_R. Clearly if maxwd\_L + maxwd\_R is less than or equal to the available equation width then aligning all of the equations is going to be simple.

Otherwise we are going to have to break at least one of the RHS's and/or at least one of the LHS's. The first thing to try is using maxwd\_L for the LHS's and breaking all the RHS's as needed to fit in the remaining space. However, this might be a really dumb strategy if one or more of the LHS's is extraordinarily wide. So before trying that we check whether maxwd\_L exceeds some threshold width

beyond which it would be unsensible not to break the LHS. Such as, max(one-third of the available width; six ems), or something like that. Or how about this? Compare the average LHS width and RHS width and divide up the available width in the same ratio for line breaking purposes.

BRM: Fairly broad changes; it mostly didn't work before (for me).

`\begin{dgroup}` produces a ‘numbered’ group

The number is the next equation number. There are 2 cases:

- If ANY contained equations are numbered (`\begin{dmath}`), then they will be subnumbered: eg 1.1a and the group number is not otherwise displayed.
- If ALL contained equations are unnumbered (`\begin{dmath*}`) then the group, as a whole, gets a number displayed, using the same number placement as for equations.

`\begin{dgroup*}` produces an unnumbered group.

Contained equations are numbered, or not, as normal. But note that in the mixed case, it's too late to force the unnumbered eqns to `\retry@with@number`. We'll just do a simple check of dimensions, after the fact, and force a shiftnumber if we're stuck.

NOTE: Does this work for dseries, as well? (alignment?)

NOTE: Does `\label` attach to the expected thing?

**For number placement** We use shiftnumber placement on ALL equations if ANY equations need it, or if an unnumbered equation is too wide to be aligned, given that the group or other eqns are numbered. [does this latter case interact with the chosen alignment?]

**For Alignment** As currently coded, it tries to align on relations, by default. If LHS's are not all present, or too long, it switches to left-justify. Maybe there are other cases that should switch? Should there be a case for centered?

NOTE: Should there be some options to choose alignment?

```
\eq@group
\GRP@top 1837 \let\eq@group\@False
1838 \let\grp@shiftnumber\@False
1839 \let\grp@hasNumber\@False
1840 \let\grp@eqs@numbered\@False
1841 \let\grp@aligned\@True
```

Definition of the `dgroup` environment.

```
1842 \newenvironment{dgroup}{%
1843   \let\grp@hasNumber\@True\@optarg\@dgroup{}%
1844 }{%
1845   \end@dgroup
1846 }
```

And the.

```
1847 \newtoks\GRP@queue
1848 \newenvironment{dgroup*}{%
1849   \let\grp@hasNumber\@False\@optarg\@dgroup{}%
1850 }{%
```

```

1851   \end@dgroup
1852 }
1853 \def\@dgroup[#1]{%
1854 <trace> \breqn@debugmsg{== DGROUP ======%
1855   \let\eq@group\@True \global\let\eq@GRP@first@dmath\@True
1856   \global\GRP@queue\emptytoks \global\setbox\GRP@box\box\voidb@x
1857   \global\let\GRP@label\empty
1858   \global\grp@wdL\z@\global\grp@wdR\z@\global\grp@wdT\z@
1859   \global\grp@linewidth\z@\global\grp@wdNum\z@
1860   \global\let\grp@eqs@numbered\@False
1861   \global\let\grp@aligned\@True
1862   \global\let\grp@shiftnumber\@False
1863   \eq@prelim
1864   \setkeys{breqn}{#1}%
1865   \if\grp@hasNumber \grp@setnumber \fi
1866 }
1867 \def\end@dgroup{%
1868   \EQ@displayinfo \grp@finish
1869   \if\grp@hasNumber\grp@resetnumber\fi
1870 }

```

If the `amsmath` package is not loaded the `parentequation` counter will not be defined.

```
1871 @ifundefined{c@parentequation}{\newcounter{parentequation}}{}
```

Init.

```

1872 \global\let\GRP@label\empty
1873 \def\add@grp@label{%
1874   \ifx\empty\GRP@label
1875   \else \GRP@label \global\let\GRP@label\empty
1876   \fi
1877 }
```

Before sending down the ‘equation’ counter to the subordinate level, set the current number in `\EQ@numbox`. The `\eq@setnumber` function does everything we need here. If the child equations are unnumbered, `\EQ@numbox` will retain the group number at the end of the group.

```

1878 \def\grp@setnumber{%
1879   \global\let\GRP@label\next@label \global\let\next@label\empty
1880   % Trick \eq@setnumber to doing our work for us.
1881   \let\eq@hasNumber\@True
1882   \eq@setnumber

```

Define `\theparentequation` equivalent to current `\theequation`. `\edef` is necessary to expand the current value of the equation counter. This might in rare cases cause something to blow up, in which case the user needs to add `\protect`.

```

1883 \global\sbox\GRP@numbox{\unhbox\EQ@numbox}%
1884 \grp@wdNum\eq@wdNum
1885 \let\eq@hasNumber\@False
1886 \let\eq@number\empty
1887 \eq@wdNum\z@
1888 %
1889 \protected@edef\theparentequation{\theequation}%
1890 \setcounter{parentequation}{\value{equation}}%

```

And set the equation counter to 0, so that the normal incrementing processes will produce the desired results if the child equations are numbered.

```

1891   \setcounter{equation}{0}%
1892   \def\theequation{\theequation\alph{equation}}%
1893 {trace} \breqn@debugmsg{Group Number \theequation}%
1894 }
```

At the end of a group, need to reset the equation counter.

```

1895 \def\grp@resetnumber{%
1896   \setcounter{equation}{\value{parentequation}}%
1897 }
1898 \newbox\GRP@box
1899 \newbox\GRP@wholebox
```

Save data for this equation in the group

- push the trial data onto end of \GRP@queue.
- push an hbox onto the front of \GRP@box containing: \EQ@box, \EQ@copy, \penalty 1 and \EQ@numbox.

\grp@push For putting the equation on a queue.

```

1900 \def\grp@push{%
1901   \global\GRP@queue\exp\exp\exp{\exp\the\exp\GRP@queue
1902   \exp\elt\exp{\EQ@trial}}%
1903 }%
1904 \global\setbox\GRP@box\vbox{%
1905   \hbox{\box\EQ@box\box\EQ@copy\penalty\one\copy\EQ@numbox}%
1906   \unvbox\GRP@box
1907 }%
1908 \EQ@trial
1909 \if\eq@isIntertext\else
1910   \ifdim\eq@wdL>\grp@wdL \global\grp@wdL\eq@wdL \fi
1911   \ifdim\eq@wdT>\grp@wdT \global\grp@wdT\eq@wdT \fi
1912   \setlength\dim@a{\eq@wdT-\eq@wdL}%
1913   \ifdim\dim@a>\grp@wdR \global\grp@wdR\dim@a \fi
1914   \ifdim\eq@linewidth>\grp@linewidth \global\grp@linewidth\eq@linewidth\fi
1915   \if\eq@hasNumber
1916     \global\let\grp@eqs@numbered\@True
1917     \ifdim\eq@wdNum>\grp@wdNum\global\grp@wdNum\eq@wdNum\fi
1918   \fi
1919   \if\EQ@hasLHS\else\global\let\grp@aligned\@False\fi
1920   \if D\eq@layout \global\let\grp@aligned\@False\fi % Layout D (usually) puts rel on 2nd line
1921   \if\eq@shiftnumber\global\let\grp@shiftnumber\@True\fi % One eq shifted forces all.
1922 \fi
1923 }
```

\grp@finish Set accumulated equations from a dgroup environment.

BRM: Questionable patch!! When processing the \GRP@queue, put it into a \vbox, then \unvbox it. This since there's a bizarre problem when the \output routine gets invoked at an inopportune moment: All the not-yet-processed \GRP@queue ends up in the \freelist and bad name clashes happen. Of course, it could be due to some other problem entirely!!!

```

1924 \def\grp@finish{%
```

```

1925 % \debug@box\GRP@box
1926 % \breqn@debugmsg{\GRP@queue: \the\GRP@queue}%
== Now that we know the collective measurements, make final decision about
alignment & shifting. Check if alignment is still possible
1927 \setlength\dim@a{\grp@wdL+\grp@wdR-4em}%
1928 \if\grp@aligned
1929   \ifdim\dim@a>\grp@linewidth
1930     \global\let\grp@aligned@\False
1931   \fi
1932 \fi

```

If we're adding an unshifted group number that equations didn't know about, re-check shifting

```

1933 \addtolength\dim@a{\grp@wdNum}%
1934 \if\grp@shiftnumber
1935 \else
1936   \if@\And{\grp@hasNumber}{\@Not\grp@eqs@numbered}
1937     \ifdim\dim@a>\grp@linewidth
1938       \global\let\grp@shiftnumber@\True
1939     \fi
1940   \fi
1941 \fi

```

If we can still align, total width is sum of maximum LHS & RHS

```

1942 \if\grp@aligned
1943   \global\grp@wdT\grp@wdL
1944   \global\advance\grp@wdT\grp@wdR
1945 \fi
1946 {*trace}
1947 \breqn@debugmsg{===== DGROUP Formatting
1948   \MessageBreak==== \grp@wdL=\the\grp@wdL, \grp@wdR=\the\grp@wdR
1949   \MessageBreak==== Shift Number=\theb@le\grp@shiftnumber, Eqns. numbered=\theb@le\grp@eqs
1950   \MessageBreak==== Aligned=\theb@le\grp@aligned
1951   \MessageBreak==== \grp@wdNum=\the\grp@wdNum}%
1952 
```

BRM: Originally this stuff was dumped directly, without capturing it in a \vbox

```

1953 \setbox\GRP@wholebox\vbox{%
1954   \let\@elt\eqgrp@elt
1955   \the\GRP@queue
1956 }%

```

If we're placing a group number (not individual eqn numbers) NOTE: For now, just code up LM number NOTE: Come back and handle other cases. NOTE: Vertical spacing is off, perhaps because of inter eqn. glue

A bit of a hack to get the top spacing correct. Fix this logic properly some day. Also, we do the calculation in a group for maximum safety.

```

1957 \global\let\eq@GRP@first@dmath@\True
1958 \begingroup
1959 \dmath@first@leftskip
1960 \eq@topspace{\vskip\parskip}%
1961 \endgroup
1962 \if@\And{\grp@hasNumber}{\@Not{\grp@eqs@numbered}}%
1963 % \eq@topspace{\vskip\parskip}%
1964 \if\grp@shiftnumber

```

```

1965   \copy\GRP@numbox \penalty\@M
1966   \kern\eqlineskip
1967   \else
1968     \setlength\dim@af%
1969       (\ht\GRP@wholebox+\dp\GRP@wholebox+\ht\GRP@numbox-\dp\GRP@numbox)/2}%
1970     \setlength\skip@c{\dim@a-\ht\GRP@numbox}%
1971     \vglue\skip@c% NON discardable
1972     \copy\GRP@numbox \penalty\@M
1973   {*trace}
1974   \breqn@debugmsg{GROUP NUMBER: preskip:\the\skip@c, postkern:\the\dim@a, height:\the\ht\GRP@w
1975   \MessageBreak==== box height:\the\ht\GRP@numbox, box depth:\the\dp\GRP@numbox}%
1976   {/trace}
1977     \kern-\dim@a
1978     \kern-\abovedisplayskip % To cancel the topspace above the first eqn.
1979   \fi
1980   \fi
1981   {*trace}
1982   \%debug@box\GRP@wholebox
1983   {/trace}
1984   \unvbox\GRP@wholebox
1985   \let@\elt\relax

```

We'd need to handle shifted, right number here, too!!!

```

1986   \eq@botspace % not needed unless bottom number?
1987 }

```

\eqgrp@elt Mission is to typeset the next equation from the group queue.

The arg is an \EQ@trial

```

1988 \def\eqgrp@elt#1{%
1989   \global\setbox\GRP@box\vbox{%
1990     \unvbox\GRP@box
1991     \setbox\z@\lastbox
1992     \setbox\tw@\hbox{\unhbox\z@
1993       \ifnum\lastpenalty=\@ne
1994       \else
1995         \global\setbox\EQ@numbox\lastbox
1996       \fi
1997       \unpenalty
1998       \global\setbox\EQ@copy\lastbox
1999       \global\setbox\EQ@box\lastbox
2000     }%
2001   }%
2002   \begingroup \let\eq@botspace\relax
2003   #1%
2004   \if\eq@isIntertext
2005     \vskip\belowdisplayskip
2006     \unvbox\EQ@copy
2007   \else
2008     \grp@override
2009     \eq@finish
2010   \fi
2011   \endgroup
2012 }

```

Override the \eq@trial data as needed for this equation in this group NOTE:

w/ numbering variations (see above), we may need to tell `\eq@finish` to allocate space for a number, but not actually have one

```
2013 \def\grp@override{%
  For aligned (possibly becomes an option?) For now ASSUMING we started out
  as CLM!!!
2014 \def\eqindent{I}%
  compute nominal left for centering the group
2015 \setlength{\dim@a}{(\grp@linewidth-\grp@wdT)/2}%
  Make sure L+R not too wide; should already have unset alignment
2016 \ifdim\dim@a<\z@\dim@a=\z@\fi
2017 \dim@b\if L\eqnumside\grp@wdNum\else\z@\fi
  make sure room for number on left, if needed.
2018 \if\grp@shiftnumber\else
2019   \ifdim\dim@b>\dim@a\dim@a\dim@b\fi
2020 \fi
2021 \if\grp@aligned
2022   \addtolength{\dim@a}{\grp@wdL-\eq@wdL}%
2023 \fi
2024 \mathindent{\dim@a}
2025 \ifdim\dim@b>\dim@a
2026   \let\eq@shiftnumber\@True
2027 \fi
```

Could set `\def\eqnumplace{T}` (or even `(m)` if indentation is enough).

NOTE: Work out how this should interact with the various formats!!! NOTE: should recognize the case where the LHS's are a bit Wild, and then do simple left align (not on relation)

```
2028 }
```

## 34 The darray environment

There are two potential applications for `darray`. One is like `eqnarray` where the natural structure of the material crosses the table cell boundaries, and math operator spacing needs to be preserved across cell boundaries. And there is also the feature of attaching an equation number to each row. The other application is like a regular array but with automatic `displaystyle` math in each cell and better interline spacing to accommodate outsize cell contents. In this case it is difficult to keep the vert ruling capabilities of the standard `array` environment without redoing the implementation along the lines of Arseneau's `tabls` package. Because the vert ruling feature is at cross purposes with the feature of allowing interline stretch and page breaks within a multiline array of equations, the `darray` environment is targeted primarily as an alternative to `eqnarray`, and does not support vertical ruling.

Overall strategy for `darray` is to use `\halign` for the body. In the case of a group, use a single `halign` for the whole group!

**What about `intertext`?**

That's the most reliable way to get accurate column widths. Don't spread the `halign` to the column width, just use the natural width. Then, if we repack the contents of the `halign` into `\EQ@box` and `\EQ@copy`, as done for `dmath`, and twiddle a bit with the widths of the first and last cell in each row, we can use the same algorithms for centering and equation number placement as `dmath!` As well as handling footnotes and `vadjust` objects the same way.

We can't just use `\arraycolsep` for `darray`, if we want to be able to change it without screwing up interior arrays. So let's make a new `colsep` variable. The initial value is '2em, but let it shrink if necessary'.

```
2029 \newskip\darraycolsep \darraycolsep 20pt plus1fil minus12pt
```

Let's make a nice big default setup with eighteen columns, split up into six sets of lcr like `eqnarray`.

```
2030 \newcount\cur@row \newcount\cur@col
2031 \def\@tempa#1#2#3{%
2032   \cur@col#1 \hfil
2033   \setbox\z@\hbox{$\displaystyle####\m@th$}\@nx\col@box
2034   \tabskip\z@skip
2035   &\cur@col#2 \hfil
2036   \setbox\z@\hbox{$\displaystyle\mathord{}####\mathord{}\m@th$}\@nx\col@box
2037   \hfil
2038   &\cur@col#3 \setbox\z@\hbox{$\displaystyle####\m@th$}\@nx\col@box
2039   \hfil\tabskip\darraycolsep
2040 }
2041 \xdef\darray@preamble{%
2042   \@tempa 123&\@tempa 456&\@tempa 789%
2043   &\@tempa{10}{11}{12}&\@tempa{13}{14}{15}&\@tempa{16}{17}{18}%
2044   \cr
2045 }
2046 \@ifundefined{Mathstrut@}{\let\Mathstrut@\strut}{}%
2047 \def\darray@cr{\Mathstrut@\cr}
2048 \def\col@box{%
2049   (*trace)
2050   %\breqn@debugmsg{Col \number\cur@row, \number\cur@col: \the\wd\z@\space x \the\ht\z@+\the\dp\z@
2051   </trace>
2052   \unhbox\z@
2053 }
2054 \newenvironment{darray}{\@optarg\darray{}{}}{%
2055   \def\darray[#1]{%
2056     <trace> \breqn@debugmsg{== DARRAY ======%
2057     \if\eq@group\else\eq@prelim\fi
2058     \global\let\@preamble\empty
2059     \setkeys\breqn{#1}%
2060     \the\eqstyle \eq@setnumber
2061     \ifx\@preamble\empty \global\let\@preamble\darray@preamble \fi
2062     \check@mathfonts
2063     % \let\check@mathfonts\relax % tempting, but too risky
2064     \xp\let\csname\string\ \endcsname\darray@cr
2065     \setbox\z@\vbox\bggroup
2066     \everycr{\noalign{\global\advance\cur@row\@ne}}%
2067     \tabskip\z@skip \cur@col\z@
```

Init the `halign` preamble to empty, then unless the 'cols' key is used to provide a non-null preamble just use the default `darray` preamble which is a multiple lcr.

```
2058   \global\let\@preamble\empty
2059   \setkeys\breqn{#1}%
2060   \the\eqstyle \eq@setnumber
2061   \ifx\@preamble\empty \global\let\@preamble\darray@preamble \fi
2062   \check@mathfonts
2063   % \let\check@mathfonts\relax % tempting, but too risky
2064   \xp\let\csname\string\ \endcsname\darray@cr
2065   \setbox\z@\vbox\bggroup
2066   \everycr{\noalign{\global\advance\cur@row\@ne}}%
2067   \tabskip\z@skip \cur@col\z@
```

```

2068     \global\cur@row\z@
2069     \penalty\@ne % flag for \dar@repack
2070     \halign\@xp\bgroup\@preamble
2071 }

```

Assimilate following punctuation.

```

2072 \def\enddarray#1{\check@punct@or@qed}
2073 \def\end@darray{%
2074   \ifvmode\else \eq@addpunct \Mathstrut@\fi\crcr \egroup
2075   \dar@capture
2076   \egroup
2077 }

```

The \dar@capture function steps back through the list of row boxes and grinds them up in the best possible way.

```

2078 \def\dar@capture{%
2079   %% \showboxbreadth\maxdimen\showboxdepth99\showlists
2080   \eq@wdL\z@ \eq@wdRmax\z@
2081   \dar@repack
2082 }

```

The \dar@repack function is a variation of \eq@repack.

```

2083 \def\dar@repack{%
2084   \unpenalty
2085   \setbox\tw@\lastbox
2086 %\batchmode{\showboxbreadth\maxdimen\showboxdepth99\showbox\tw@}\errorstopmode
2087   \global\setbox\@EQ@box\hbox{%
2088     \hbox{\unhcry\tw@\unskip}\penalty-\@M \unhbox\@EQ@box}%
2089   \global\setbox\@EQ@copy\hbox{%
2090     \hbox{\unhbox\tw@\unskip}\penalty-\@M \unhbox\@EQ@copy}%
2091   \unskip
2092   \ifcase\lastpenalty \else\exp@gobble\fi
2093   \dar@repack
2094 }

```

## 35 Miscellaneous

The \condition command. With the star form, set the argument in math mode instead of text mode. In a series of conditions, use less space between members of the series than between the conditions and the main equation body.

BRM: Some modifications here, since I like for the condition to go flush right. (thus, it also affects centering, margins, etc)

```

2095 \newskip\conditionsep \conditionsep=10pt minus5pt%
2096 \newcommand{\conditionpunct}{,}
2097 \let\cond@gobble\@firstofone
2098 \newcommand\condition{%
2099   \begingroup\@tempswatrue
2100   \@ifstar{@\@tempswafalse \condition@a}\condition@a
2101 }
2102 \newcommand\condition@a[2][\conditionpunct]{%
2103   \unpenalty\unskip\unpenalty\unskip % BRM Added
2104   \hbox{\#1}%
2105   \penalty -201\relax\hbox{}% Penalty to allow breaks here.
2106   \hskip\conditionsep

```

```

2107   \if@tempswa \expandafter\hbox \else \expandafter\condition@b\fi
2108   {#2}%
2109   \endgroup

```

BRM: Testing if I can measure conditions?

```

2110   \setbox\z@\if@tempswa\hbox{#2}\else\hbox{\textmath@setup #2}\fi
2111   \global\eq@wdCond\wd\z@
2112   \let\cond@gobble\@gobble
2113 }

```

For a math condition. This is called inside a group so we don't need extra grouping to localize the effect of `\textmath@setup` which turns off the line-breaking features of bin, rel, and delimiter symbols.

```

2114 \newcommand\condition@b[1]{%
2115   \cond@gobble{\hskip\conditionsep}%
2116   \textmath@setup #1%
2117 }

```

The `dsuspend` environment. First the old one that didn't work.

```

2118 \newenvironment{XXXXdsuspend}{%
2119   \global\setbox\EQ@box\vbox\bgroup \parboxrestore

```

If we are inside a list environment, `\displayindent` and `\displaywidth` give us `\@totalleftmargin` and `\linewidth`.

```

2120   \parshape 1 \displayindent \displaywidth\relax
2121   \hsize=\columnwidth \noindent\ignorespaces
2122 }%
2123 \par\egroup

```

Let's try giving `\EQ@box` the correct height for the first line and `\EQ@copy` the depth of the last line.

```

2124 \global\setbox\GRP@box\vbox{%
2125   \vbox{\copy\EQ@box\vtop{\unvbox\EQ@box}}%
2126   \unvbox\GRP@box
2127 }%

```

Need to add a dummy element to `\GRP@queue`.

```

2128 \global\GRP@queue\exp{\the\GRP@queue
2129   \@elt{\gdef\EQ@trial{}}
2130 }%
2131 }

```

And then the one that does work.

```

2132 \newenvironment{dsuspend}{%
2133   \global\setbox\EQ@box\vbox\bgroup \parboxrestore
2134   \parshape 1 \displayindent \displaywidth\relax
2135   \hsize=\columnwidth \noindent\ignorespaces
2136 }%
2137 \par\egroup
2138 \global\setbox\GRP@box\vbox{%
2139   \hbox{\copy\EQ@box\vtop{\unvbox\EQ@box}}%
2140   \unvbox\GRP@box
2141 }%
2142 \global\GRP@queue\exp{\the\GRP@queue
2143 %   \@elt{\gdef\EQ@trial{\let\eq@isIntertext\@True}%
2144   \@elt{\let\eq@isIntertext\@True}%

```

```
2145     }%
2146 }
```

Allow `\intertext` as a short form of the `dsuspend` environment; it's more convenient to write, but it doesn't support embedded verbatim because it reads the material as a macro argument. To support simultaneous use of `amsmath` and `breqn`, the user command `\intertext` is left alone until we enter a `breqn` environment.

```
2147 \newcommand{\breqn@intertext}[1]{\dsuspend#1\enddsuspend}
```

`\discretionarytimes` Discretionary times sign. Standard L<sup>A</sup>T<sub>E</sub>X definition serves only for inline math.  
Should the thin space be included? Not sure.

```
2148 \renewcommand{\*}{%
2149   \if@display
```

Since `\eq@binoffset` is mu-glue, we can't use it directly with `\kern` but have to measure it separately in a box.

```
2150 \setbox\z@\hbox{\mathsurround\z@\mkern\eq@binoffset$}%
2151 \discretionary{}{%
2152   \kern\the\wd\z@ \textchar\discretionarytimes
2153 }{}%
2154 \thinspace
2155 \else
2156   \discretionary{\thinspace\textchar\discretionarytimes}{}{}%
2157 \fi
2158 }
```

This is only the symbol; it can be changed to some other symbol if desired.

```
2159 \newcommand{\discretionarytimes}{\times}
```

`\nref` This is like `\ref` but doesn't apply font changes or other guff if the reference is undefined. And it is fully expandable for use as a label value.

**Can break with Babel if author uses active characters in label key; need to address that**

mjd,1999/01/21

```
2160 \def\nref#1{\@xp\@ref\csname r@#1\endcsname}
2161 \def\@ref#1#2{\ifx\relax#1?\else \@xp\@firstoftwo#1\fi}
2162 %%%%%%%%%%%%%%
```

## 36 Wrap-up

The usual endinput.

```
2163 </package>
```

## 37 To do

1. Alignment for equation groups.
2. Use dpc's code for package options in keyval form.

3. Encapsulate “break math” into a subroutine taking suitable arguments.
4. Need a density check for layout S when linewidth is very small.
5. Make := trigger a warning about using \coloneq instead.
6. Ill-centered multiline equation (three-line case) in test008.
7. Attaching a single group number.
8. Make sure to dump out box registers after done using them.
9. Do the implementation for \eq@resume@parshape.
10. Check on stackrel and buildrel and relbar and ???.
11. Test math symbols at the beginning of array cells.
12. Test \\md in and out of delims.
13. Framing the equation body: the parshape and number placement need adjusting when a frame is present.
14. Cascading line widths in list env.
15. Noalign option for dmath = multiline arrangement?
16. Nocompact option, suggested 1998/05/19 by Andrew Swann.
17. \delbreak cmd to add discretionary space at a break within delimiters.
18. Reduce above/below skip when the number is shifted.
19. Need a \middelim command for marking a delimiter symbol as nondirectional if it has an innate directionality ()[] etc..
20. \xrightarrow from amsmath won’t participate in line breaking unless something extra is done. Make \BreakingRel and \BreakingBin functions?
21. Placement of number in an indented quotation or abstract.
22. If  $LHSwd > 2em$ , it might be a good idea to try with eq@indentstep = 2em before shifting the number. Currently this doesn’t happen if the first trial pass (without the number) succeeds with  $indentstep = LHSwd > 2em$ .
23. Read past \end{enumerate} when checking for \end{proof}?
24. Look into using a “qed-list” of environment names instead of checking the existence of \proofqed.
25. Pick up the vadjust/footnote/mark handling.
26. Forcing/prohibiting page breaks after/before an equation.
27. Adding a spanner brace on the left and individual numbers on the right (indy-numbered cases).
28. Provide \shiftnumber, \holdnumber to override the decision.

29. Provide a mechanism for adjusting the vertical position of the number. Here a version-specific selection macro would be useful.

```
\begin{dmath}
    style={\foredition{1}{\raisebox{13pt}}}
]
```

30. Add an alignleft option for an equation group to mean, break and align to a ladder layout as usual within the equations, but for the group alignment used the leftmost point (for equations that don't have an LHS, this makes no difference).
31. Test with Arseneau's wrapfig for parshape/everypar interaction.
32. Fix up the macro/def elements.
33. Convert the literal examples in section ‘Equation types and forms’ to typeset form.
34. Compile comparison-examples: e.g., a standard equation env with big left-right objects that don't shrink, versus how shrinking can allow it to fit.
35. Frame the “figures” since they are mostly text.

Possible enhancements:

1. Provide a `pull` option meaning to pull the first and last lines out to the margin, like the `multiline` environment of the `amsmath` package. Maybe this should get an optional argument, actually, to specify the amount of space left at the margin.
2. With the draft option, one would like to see the equation labels in the left margin. Need to check with the `showkeys` package.
3. Options for break preferences: if there's not enough room, do we first shift the number, or first try to break up the equation body?. In an aligned group, does sticking to the group alignment take precedence over minimizing the number of line breaks needed for individual equations?. And the general preferences probably need to be overridable for individual instances.
4. Extend suppress-breaks-inside-delimiters support to inline math (suggestion of Michael Doob).
5. Use belowdisplayshortskip above a dsuspend fragment if the fragment is only one line and short enough compared to the equation line above it.
6. Add `\eqfuzz` distinct from `\hfuzz`. Make use of it in the measuring phase.
7. Provision for putting in a ‘continued’ note.
8. Conserve box mem: modify `frac`, `sub`, `sup`, `overline`, `underline`, `sqr`, to turn off `\bin@break` and (less urgently) `\rel@break`.
9. More explicit support for Russian typesetting conventions (cf Grinchuk article).

10. With package option `refnumbers`, leave unnumbered all uncited equations, even if they are not done with the star form (Bertolazzi's easyeqn idea).
11. In an equation group, use a vertical bracket with the equation number to mark the lines contained in that equation.
12. For a two-line multiline thingamabob, try to make sure that the lines overlap in the middle by 2 em or whatever (settable design variable).
13. Provide a separate vertical column for the principal mathrel symbols and center them within the column if they aren't all the same width. Maybe an option for `dmath`: `relwidth=x`, so that two passes are not required to get the max width of all the mathrels. Or, no, just require it to be an `halign` or provide a macro to be applied to all the shorter rels:

```
lhs \widerel[19pt]{=} ...
\xrightarrow{foo} ...
```

14. try to use `vadjust` for `keepglue`

## Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
<code>\!</code> . . . . .	588
<code>\"</code> . . . . .	5, 8, 19
<code>\\$</code> . . . . .	135
<code>\&amp;</code> . . . . .	84, 90, 91
<code>\*</code> . . . . .	1357, <u>2148</u>
<code>\,</code> . . . . .	587
<code>\.</code> . . . . .	587
<code>\;</code> . . . . .	587
<code>\?</code> . . . . .	588, 1265
<code>\@@display</code> . . . . .	<u>135</u> , 837
<code>\@@enddisplay</code> . . . . .	<u>135</u> , 851
<code>\@@endmath</code> . .	<u>135</u> , 718, 1815, 1830, 1834
<code>\@@insert</code> . . . . .	<u>140</u>
<code>\@@italiccorr</code> . . . . .	176
<code>\@@left</code> . . .	355, 1594, 1603, 1607, 1611
<code>\@@mark</code> . . . . .	<u>140</u>
<code>\@@math</code> . . . . .	<u>135</u> , 700, 1804, 1828
<code>\@@par</code> . . . . .	545,
	558, 720, 1029, 1421, 1567, 1720
<code>\@@right</code> . . .	355, 1595, 1605, 1608, 1611
<code>\@@vadjust</code> . . .	<u>140</u> , 289, 865, 872, 1702
<code>\@And</code> . . .	<u>74</u> , 633, 1502, 1538, 1936, 1962
<code>\@False</code> . . . . .	<u>74</u> , 213, 214,
	229, 276, 410–412, 443, 507,
	632, 659, 698, 987, 1032, 1166,
<code>\@badmath</code> . . . . .	1322, 1793, 1837–1840, 1849,
	1860, 1862, 1885, 1919, 1920, 1930
<code>\@M</code> . . . . .	<u>188</u> , 190, 449, 708, 710,
	713, 717, 813, 818, 838, 857,
	860, 866, 873, 1356, 1389, 1415,
	1553, 1559, 1672, 1689, 1711,
	1712, 1808, 1965, 1972, 2088, 2090
<code>\@Mi</code> . . . . .	<u>289</u> , 701, 717, 1720, 1804
<code>\@Not</code> . . . . .	<u>74</u> , 633, 999,
	1004, 1018, 1502, 1538, 1936, 1962
<code>\@Or</code> . . . . .	<u>78</u> , 1018
<code>\@True</code> . . . . .	<u>74</u> , 212, 281, 366,
	367, 409, 413, 419, 489, 494,
	666, 672, 677, 1033, 1173, 1191,
	1209, 1212, 1218, 1225, 1275,
	1318, 1332, 1791, 1800, 1841,
	1843, 1855, 1861, 1881, 1916,
	1921, 1938, 1957, 2026, 2143, 2144
<code>\@badmath</code> . . . . .	1828, 1830, 1834
<code>\@car</code> . . . . .	116, 372
<code>\@centering</code> . . . . .	195, 196
<code>\@currentlabel</code> . . . . .	364, 629
<code>\@darray</code> . . . . .	2054, 2055
<code>\@dgroup</code> . . . . .	1843, 1849, 1853
<code>\@displaytrue</code> . . . . .	359
<code>\@dmath</code> . . . . .	419, 420, 443, 1802, 1803

\@dseries .....	1791, 1793, 1796	\@nx .....	39, 572–574, 582–
\@eha .....	130		584, 590–595, 973, 978, 980,
\@elt .....	100,		982–987, 1779, 2033, 2036, 2038
	894, 898, 903, 965, 967, 1051,	\@optarg .....	73, 419,
	1055, 1056, 1267, 1298, 1336,		443, 1791, 1793, 1843, 1849, 2054
	1902, 1954, 1985, 2129, 2143, 2144	\@parboxrestore .....	2119, 2133
\@empty .....	28–30, 34, 37, 277, 362, 415,	\@parshape .....	876, 983, 992, 1027, 1069,
	460, 476, 480, 485, 602, 624,		1116, 1124, 1141, 1149, 1155,
	761, 765, 768, 876, 895, 904,		1162, 1196, 1199, 1226, 1263, 1818
	914, 916, 917, 920, 965, 1035,	\@percentchar .....	416
	1041, 1352, 1658, 1857, 1872,	\@plus .....	710, 882,
	1874, 1875, 1879, 1886, 2058, 2061		1081, 1195, 1493, 1495, 1513, 1547
\@emptytoks .....	41,	\@preamble .....	415, 2058, 2061, 2070
	322, 325, 340, 343, 450, 836, 1856	\@saveprimitive .....	
\@endelt .....	895, 898, 904, 965, 967, 1053,		102, 140–142, 1594, 1595
	1056, 1058, 1265, 1267, 1305, 1342	\@saveprimitive@a .....	109, 114
\@endpetrue .....	692	\@secondoftwo .....	95–97
\@eq@numberfalse .....	213	\@sptoken .....	565, 572
\@eq@numbertrue .....	212	\@symBin .....	95, 306, 315, 334, 350
\@filelist .....	239, 256	\@symDeA .....	310, 319, 338, 354
\@firstofone .....	2097	\@symDeB .....	97, 309, 319, 338, 354
\@firstoftwo .....	1694, 2161	\@symDeL .....	96, 318, 337, 353
\@gobble .....	30, 93, 518,	\@symDeR .....	96, 308, 318, 337, 353
	782, 992, 1199, 1242, 2092, 2112	\@symDel .....	307
\@gobbletwo .....	946	\@symRel .....	95, 305, 315, 333, 350
\@height .....	1572, 1622	\@tempa .....	28, 30,
\@ifnext .....	64, 73, 859, 1598, 1601		65, 68, 70, 104, 105, 108, 124,
\@ifnexta .....	64, 71		126, 236, 239, 253, 256, 571,
\@ifpackageloaded .....	13		578, 620, 621, 1140, 1255, 1261,
\@ifpackagewith .....	233, 234, 250		1262, 1292, 1294, 2031, 2042, 2043
\@ifstar .....	69, 857, 2100	\@tempb .....	65, 68, 70, 104, 105, 107,
\@ifundefined .....			108, 116, 117, 124–126, 1258, 1261
	22, 41, 165, 242, 259, 268, 271,	\@tempc .....	66, 68, 71, 1262, 1263
	357, 613, 1613, 1770, 1871, 2046	\@tempcnta .....	45, 1687
\@ignoretrue .....	693, 1810	\@tempcntb .....	46
\@inlabelfalse .....	424	\@tempd .....	65, 68, 70
\@let@token .....	561, 565, 568, 569, 572–	\@tempdima .....	48
	574, 582–584, 590–594, 608,	\@tempdimb .....	49
	1689, 1691, 1692, 1696, 1700	\@tempdimc .....	50
\@m .....	709	\@tempskipa .....	54
\@mathmargin .....	272	\@tempskipb .....	55
\@minus .....	882, 1081, 1495, 1513, 1547	\@tempswafalse .....	2100
\@namedef .....		\@tempswatrue .....	2099
	. 445, 446, 1067, 1786, 1794, 1795	\@temptokena .....	57
\@ne .....	279, 291, 467, 523, 711,	\@totalleftmargin .....	1178,
	815, 864, 865, 871, 872, 1033,		1180, 1427, 1458, 1461, 1470, 1517
	1183, 1206, 1256, 1450, 1662,	\@width .....	81, 1622
	1681, 1691, 1905, 1993, 2066, 2069	\@xp .....	30, 39, 76–78,
\@newline .....	705		93, 239, 256, 358, 359, 382, 608,
\@nil .....	28, 32–34, 36, 37, 236, 239,		609, 614, 782, 923, 992, 1199,
	253, 256, 372, 620, 621, 1782, 1785		1232, 1242, 1257, 1263, 1294,
\@nnil .....	518		1313, 1323, 1649, 1652, 1655,
\@nobreakfalse .....	449		1782, 1901, 1902, 2064, 2070,
\@nref .....	2160, 2161		2092, 2107, 2128, 2142, 2160, 2161

\`	706	836, 880, 893, 902, 957, 965,
\^	8, 16, 19	993, 1570, 1598, 1601, 1686,
\_	8, 17, 19	1734, 1769, 1779, 1958, 2002, 2099
\~	1780	\belowdisplayshortskip . . . . . 641, 840
\&m	90	\belowdisplayskip . . . . . 641, 840, 1436, 2005
\&q	93	\bgroup . . . . . 699, 2065, 2070, 2119, 2133
\u	2064	\Big . . . . . 1615, 1627, 1634, 1642
<b>A</b>		
\abovedisplayshortskip	. . . . . 640, 839	\big . . . . . 1615, 1626, 1633, 1641
\abovedisplayskip	. . . . .	\big@size . . . . . 1614, 1622
	644, 660, 839, 1435, 1978	\Bigg . . . . . 1616, 1629, 1636, 1644
\abs@num	. . . . . 63, 299	\bigg . . . . . 1616, 1628, 1635, 1643
\active	. . . . . 587, 588	\Biggg . . . . . 1617, 1631, 1638, 1646
\add@grp@label	. . . . . 539, 551, 1566, 1873	\biggg . . . . . 1617, 1630, 1637, 1645
\addtolength	. . . . . 375,	\Bigggl . . . . . 1631
	376, 649, 689, 787, 941, 1063,	\bigggl . . . . . 1630
	1075, 1076, 1132, 1136, 1180,	\Bigggm . . . . . 1646
	1246, 1248, 1286, 1294, 1342,	\bigggm . . . . . 1645
	1418, 1461, 1474, 1479, 1494,	\Bigggr . . . . . 1638
	1512, 1517, 1534, 1542, 1933, 2022	\bigggr . . . . . 1637
\adjdemerits	. . . . . 160	\Biggl . . . . . 1629
\adjust@parshape	. . . . . 504, 1196, 1231	\biggl . . . . . 1628
\adjust@parshape@a	. . . . . 1232, 1235	\Biggm . . . . . 1644
\adjust@parshape@b	. . . . . 1235	\biggm . . . . . 1643
\adjust@rel@penalty	. . . . .	\Biggr . . . . . 1636
	985, 1041, 1119, 1163, 1369	\biggr . . . . . 1635
\advance	. . . . . 291,	\Bigl . . . . . 1627
	462, 488, 813, 846, 847, 942,	\bigl . . . . . 1626
	943, 1130, 1135, 1148, 1152,	\Bigm . . . . . 1642
	1175, 1182, 1193, 1205, 1206,	\bigm . . . . . 1641
	1256, 1308, 1312, 1347, 1485,	\Bigr . . . . . 1634
	1487, 1662, 1664, 1669, 1675,	\bigr . . . . . 1633
	1677, 1691, 1692, 1712, 1944, 2066	\bin@break . . . . . 292, 306
\after@bidir	. . . . . 1655, 1658	\bin@mark . . . . . 292
\after@close	. . . . . 1605,	\binoppenalty . . . . . 713
	1608, 1610, 1633–1638, 1652, 1658	\bop@incr . . . . . 1658
\after@open	. . . . . 1603,	\botmark . . . . . 120
	1607, 1610, 1626–1631, 1649, 1658	\box . . . . . 540, 792, 796, 1368,
\afterassignment	. . . . .	1714, 1752, 1760, 1766, 1856, 1905
	517, 1258, 1261, 1262, 1689, 1700	\breqn@debugmsg . . . . .
\aftergroup	. . . . . 641, 946	145, 159–161, 421, 482,
\alph	. . . . . 1892	497, 509, 634, 636, 652, 741,
\AtEndOfPackage	. . . . . 7	749, 892, 896, 897, 905, 932,
<b>B</b>		
\badness	. . . . . 1274	936, 950, 956, 960, 965, 966,
\baselineskip	. . . . . 1354	992, 1017, 1019, 1079, 1085,
\batchmode	. . . . . 148, 728, 734, 2086	1094, 1102, 1106, 1110, 1169,
\bBigg@	. . . . . 1615–1617, 1619	1172, 1186, 1189, 1198, 1208,
\begin	. . . . . 404, 405, 407, 772, 1537	1211, 1215, 1220, 1281, 1317,
\begingroup	. . . . . 84, 90, 100, 103,	1321, 1338, 1349, 1425, 1854,
	115, 135, 429, 496, 580, 631,	1893, 1926, 1947, 1974, 2050, 2056
		\breqn@intertext . . . . . 454, 2147
		\breqn@parshape@warning . . . . . 456, 470
		\breqn@repack@err . . . . . 803, 807
		\breqn@popcats . . . . . 4, 7, 15

**C**

\catcode ..... 5,  
   8, 16, 17, 19, 84, 90, 135, 587, 588  
\chardef ..... 42, 1265  
\check@mathfonts ..... 2062, 2063  
\check@punct ..... 569, 626  
\check@punct@a ..... 569, 570  
\check@punct@b ..... 575, 598  
\check@punct@or@qed ..... 433,  
   446, 623, 1792, 1794, 1832, 2072  
\check@qed .....  
   . 573, 574, 582–584, 590–594, 603  
\check@qed@a ..... 605, 607  
\check@qed@b ..... 608, 612  
\clubpenalty ..... 711, 727, 1356  
\col@box ..... 2033, 2036, 2038, 2048  
\color ..... 178  
\columnwidth ..... 882, 918, 1080, 2121, 2135  
\cond@gobble ..... 2097, 2112, 2115  
\condition ..... 2098  
\condition@a ..... 2100, 2102  
\condition@b ..... 2107, 2114  
\conditionpunct ..... 2096, 2102  
\conditionsep .....  
   . 1433, 1451, 2095, 2106, 2115  
\copy ..... 556,  
   725, 726, 786, 1389, 1421, 1553,  
   1559, 1905, 1965, 1972, 2125, 2139  
\count@ ..... 47, 462,  
   463, 812, 813, 815, 816, 831, 1683  
\cr ..... 850, 2044, 2047  
\crcr ..... 2074  
\csname ..... 24, 86, 91, 93, 244,  
   261, 358, 503, 521, 524, 526,  
   614, 622, 625, 934, 1257, 1301,  
   1649, 1652, 1655, 1774, 2064, 2160  
\cur@col .....  
   2030, 2032, 2035, 2038, 2050, 2067  
\cur@row ..... 2030, 2050, 2066, 2068

**D**

\d@@Bin ..... 292, 314, 331, 1679  
\d@@DeA ..... 317, 336, 1657  
\d@@DeB ..... 316, 335, 1647  
\d@@DeL ..... 316, 335, 1647  
\d@@DeR ..... 316, 335, 1647  
\d@@Rel ..... 292, 314, 332  
\d@@symBin ..... 305, 315, 334  
\d@@symDeA ..... 305, 319, 338  
\d@@symDeB ..... 305, 319, 338  
\d@@symDeL ..... 318, 337  
\d@@symDel ..... 305  
\d@@symDeR ..... 305, 318, 337  
\d@@symRel ..... 305, 315, 333

\dar@capture ..... 2075, 2078  
\dar@repack ..... 2069, 2081, 2083, 2093  
\darray@cr ..... 2047, 2064  
\darray@mkpream ..... 416  
\darray@preamble ..... 2041, 2061  
\darraycolsep ..... 2029, 2039  
\debug@box .....  
   147, 152, 756, 757, 1366, 1925, 1982  
\debug@para ..... 157  
\debug@showformat ..... 516, 1424  
\debug@showmeasurements .....  
   . 498, 891, 901, 1039  
\debugwr ..... 146, 158, 756, 757  
\decl@twang ..... 1782, 1785  
\DeclareOption ..... 9  
\DeclareTwang .. 1778, 1780, 1788–1790  
\def 27, 32, 36, 37, 63–65, 68–70, 73–  
   82, 89, 99, 116, 145–147, 151,  
   157, 167, 168, 171–173, 175–  
   178, 194, 212, 213, 232, 234,  
   236, 237, 251, 253, 254, 278,  
   288, 295, 296, 298, 303–306,  
   312, 329, 348, 361, 363, 368,  
   383–385, 389, 392, 393, 395,  
   399, 400, 408, 420, 433, 434,  
   447, 456, 461, 473, 495, 535,  
   547, 560, 563, 564, 568–570,  
   603, 607, 612, 620, 622, 623,  
   625, 630, 658, 685, 696, 697,  
   703, 716, 760, 769, 807, 810,  
   835, 856, 858, 860, 861, 868,  
   875, 877, 891, 894, 901, 903,  
   918, 919, 927, 940, 945, 949,  
   953, 954, 959, 963, 965, 973,  
   978, 980, 982–987, 990, 991,  
   995, 1015, 1016, 1025, 1026,  
   1042, 1049, 1053, 1058, 1066,  
   1091, 1114, 1119, 1122, 1129,  
   1140, 1145, 1161, 1163, 1167,  
   1231, 1235, 1240, 1253, 1255,  
   1261, 1262, 1266, 1270, 1278,  
   1292, 1311, 1315, 1327–1331,  
   1342, 1343, 1353, 1365, 1371,  
   1375, 1381, 1387, 1398, 1404,  
   1411, 1424, 1440, 1521, 1550,  
   1556, 1562, 1575, 1586, 1597,  
   1600, 1603, 1604, 1607–1609,  
   1615–1617, 1619, 1626–1631,  
   1633–1638, 1641–1646, 1648,  
   1651, 1654, 1661, 1670, 1674,  
   1684, 1685, 1690, 1698, 1701,  
   1705, 1726–1731, 1733, 1746,  
   1754, 1762, 1768, 1785, 1792,  
   1796, 1797, 1806, 1810, 1813,

1817, 1821, 1822, 1832, 1833,  
 1853, 1867, 1873, 1878, 1892,  
 1895, 1900, 1924, 1988, 2013,  
 2014, 2031, 2047, 2048, 2055,  
 2072, 2073, 2078, 2083, 2160, 2161  
 $\backslash\text{define@key}$  . . . . . 361, 363, 366–371,  
     374, 379, 382, 383, 385, 389,  
     394, 400, 408–410, 412, 414, 415  
 $\backslash\text{delim@a}$  . . . . . 1649, 1652, 1655, 1687  
 $\backslash\text{delim@reset}$  . . . . . 1609, 1620  
 $\backslash\text{delimiter}$  . . . . . 1598,  
     1601, 1603, 1605, 1649, 1652, 1655  
 $\backslash\text{dim}$  . . . . . 1140  
 $\backslash\text{dim@A}$  . . . . . 48  
 $\backslash\text{dim@a}$  . . . . . 48, 386,  
     396, 660, 671, 676, 736, 739,  
     742, 744, 942, 943, 1059–1061,  
     1071, 1078, 1080, 1095, 1096,  
     1115, 1117, 1146, 1147, 1156,  
     1182, 1185, 1195, 1236, 1246,  
     1257, 1259, 1261, 1262, 1283,  
     1284, 1286, 1305, 1376, 1382,  
     1390, 1392, 1394, 1399, 1406,  
     1416, 1418, 1420, 1468, 1470,  
     1471, 1473, 1474, 1476, 1479,  
     1480, 1493, 1524, 1525, 1529,  
     1533, 1534, 1541, 1543, 1547,  
     1551, 1554, 1557, 1560, 1577–  
     1579, 1749, 1750, 1757, 1758,  
     1912, 1913, 1927, 1929, 1933,  
     1937, 1968, 1970, 1974, 1977,  
     2015, 2016, 2019, 2022, 2024, 2025  
 $\backslash\text{dim@b}$  . . . . . 48, 675,  
     676, 1043, 1045, 1073, 1075,  
     1076, 1078–1081, 1086, 1123,  
     1125, 1130–1132, 1134–1136,  
     1141, 1142, 1153, 1154, 1157,  
     1175, 1176, 1178, 1180, 1182,  
     1244, 1246, 1248, 1249, 1272,  
     1273, 1281, 1283, 1336, 1338,  
     1339, 1342, 1345, 1349, 1350,  
     1453–1456, 1458, 1459, 1461,  
     1473, 1474, 1476, 1498, 1500,  
     1505, 1506, 1511, 1513, 1530,  
     1534, 1542, 1547, 2017, 2019, 2025  
 $\backslash\text{dim@c}$  . . . . . 48, 928–  
     931, 1154, 1157, 1245–1249,  
     1337–1339, 1346, 1348–1350,  
     1441, 1442, 1444, 1455, 1456,  
     1465, 1466, 1469, 1471, 1474,  
     1475, 1478, 1479, 1481, 1494,  
     1500, 1504–1506, 1512, 1540–1543  
 $\backslash\text{dim@d}$  . . . . . 48, 1463–1466,  
     1478, 1479, 1481, 1483, 1484,  
     1488, 1491, 1493, 1771, 1773, 1774  
 $\backslash\text{dim@e}$  . . . . . 48, 1446, 1448,  
     1451, 1464, 1470, 1483–1487,  
     1490, 1491, 1494, 1495, 1512, 1513  
 $\backslash\text{dimen@}$  . . . . . 51  
 $\backslash\text{dimen@i}$  . . . . . 53  
 $\backslash\text{dimen@ii}$  . . . . . 52  
 $\backslash\text{dimendef}$  . . . . . 1724, 1725  
 $\backslash\text{discretionary}$  . . . . . 2151, 2156  
 $\backslash\text{discretionarytimes}$  . . . . . 2148  
 $\backslash\text{display@setup}$  . . . . . 311, 422, 1797, 1798  
 $\backslash\text{displayindent}$  467, 843, 845, 2120, 2134  
 $\backslash\text{displaystyle}$  . . . . .  
     . . . . . 346, 700, 1797, 2033, 2036, 2038  
 $\backslash\text{displaywidth}$  467, 843, 918, 2120, 2134  
 $\backslash\text{divide}$  1131, 1147, 1344, 1345, 1348, 1490  
 $\backslash\text{dmath}$  . . . . . 418  
 $\backslash\text{dmath*}$  . . . . . 442  
 $\backslash\text{dmath@first@leftskip}$  . . . . . 508, 509, 1959  
 $\backslash\text{Dmedmuskip}$  . . . . . 192, 313, 330  
 $\backslash\text{dp}$  . . . . . 154, 1044, 1305, 1376, 1399,  
     1406, 1737, 1757, 1969, 1975, 2050  
 $\backslash\text{dquad}$  . . . . . 1808, 1810, 1823, 1824  
 $\backslash\text{dseries@display@setup}$  . . . . . 329, 1798  
 $\backslash\text{dsuspend}$  . . . . . 2147  
 $\backslash\text{dt@fill@cancel}$  . . . . . 1670  
 $\backslash\text{Dthickmuskip}$  . . . . . 193, 313, 330

## E

$\backslash\text{edef}$  . . . . . 4, 15, 28, 104, 107, 116, 124,  
     125, 243, 260, 372, 386, 396,  
     463, 466, 571, 879, 938, 1069,  
     1116, 1124, 1141, 1149, 1155,  
     1162, 1202, 1203, 1226, 1233,  
     1237, 1241, 1249, 1257, 1298, 1818  
 $\backslash\text{egroup}$  . . . . . 754, 2074, 2076, 2123, 2137  
 $\backslash\text{else}$  . . . . . 30, 34, 37, 76–79, 106,  
     109, 127, 237, 241, 245, 254,  
     258, 262, 425, 440, 469, 481,  
     499, 510, 513, 522, 525, 529,  
     542, 553, 566, 573–575, 583,  
     584, 590–595, 609, 637, 643,  
     648, 662, 664, 667, 669, 674,  
     688, 762, 802, 813, 823, 830,  
     879, 922, 935, 1003, 1008, 1021,  
     1025, 1074, 1076, 1083, 1097,  
     1100, 1105, 1109, 1170, 1179,  
     1185, 1187, 1192, 1210, 1213,  
     1219, 1243, 1275, 1281, 1284,  
     1290, 1294, 1303, 1313, 1319,  
     1323, 1335, 1339, 1350, 1368,  
     1391, 1417, 1443, 1460, 1478,  
     1499, 1532, 1587, 1667, 1679,  
     1691, 1692, 1714, 1718, 1742,

1781, 1808, 1828, 1830, 1834,  
 1875, 1909, 1919, 1935, 1967,  
 1994, 2007, 2017, 2018, 2057,  
 2074, 2092, 2107, 2110, 2155, 2161  
 $\end{array}$  ..... 403, 406, 608, 618, 621, 622  
 $\end{darray}$  ..... 2073  
 $\end{group}$  ..... 1845, 1851, 1867  
 $\end{math}$  ..... 434, 445, 1815  
 $\end{series}$  ..... 1795, 1813  
 $\end{math}$  ..... 1833  
 $\end{csname}$  24, 86, 89, 91, 93, 244, 261,  
     358, 503, 521, 524, 526, 614,  
     620, 622, 625, 934, 1257, 1305,  
     1649, 1652, 1655, 1774, 2064, 2160  
 $\end{array}$  ..... 2072  
 $\end{math}$  ..... 418  
 $\end{math>*$  ..... 442  
 $\end{series}$  ..... 1792  
 $\end{dsuspend}$  ..... 2147  
 $\end{group}$  ..... 88, 92, 100, 112,  
     133, 137, 437, 532, 601, 656,  
     853, 887, 899, 911, 955, 968,  
     1013, 1573, 1603, 1604, 1688,  
     1744, 1776, 1780, 1961, 2011, 2109  
 $\end{math}$  ..... 1805  
 $\end{math}$  ..... 1805, 1832  
 $\eq@addframe$  ..... 543, 554, 1575, 1590  
 $\eq@addpunct$  ..... 719, 760, 1810, 2074  
 $\EQ@afterspace$  ..... 766, 768  
 $\eq@background$  ..... 400  
 $\eq@badline$  ..... 973,  
     999, 1004, 1032, 1033, 1210, 1275  
 $\eq@badness$  ..... 210, 897, 908, 966,  
     973, 1050, 1064, 1203, 1211,  
     1213, 1216, 1274, 1275, 1281, 1305  
 $\eq@binoffset$  .....  
     198, 295, 1668, 1669, 1681, 2150  
 $\eq@botspace$  ..... 533, 630, 1986, 2002  
 $\EQ@box$  ..... 199,  
     545, 557, 723, 725, 732, 736,  
     742, 749, 756, 776, 781, 788,  
     794, 796, 823, 1567, 1905, 1999,  
     2087, 2088, 2119, 2125, 2133, 2139  
 $\eq@break$  ..... 875  
 $\eq@C@setsides$  ..... 1440  
 $\eq@capture$  ..... 436, 715  
 $\eq@centerlines$  .....  
     409–411, 1428, 1489, 1800  
 $\eq@check@density$  ..... 1002, 1016  
 $\eq@check@shortskip$  ..... 638, 658  
 $\eq@cons$  ..... 99  
 $\EQ@continue$  .. 884, 915, 921, 925, 947  
 $\EQ@copy$  152–154, 200, 725, 733, 734,  
     757, 776, 781, 790, 792, 815,  
     1028, 1071, 1079, 1085, 1095,  
     1131, 1905, 1998, 2006, 2089, 2090  
 $\eq@curline$  209, 1034, 1302, 1308, 1309  
 $\eq@delt$  ..... 1336, 1342  
 $\eq@dense@enough$  ..... 1021, 1315  
 $\eq@dense@enough@a$  ..... 1323, 1331  
 $\eq@dense@enough@b$  ..... 1334, 1343  
 $\eq@density@factor$  .....  
     368, 1330, 1337, 1338  
 $\EQ@displayinfo$  ..... 841, 854, 1868  
 $\eq@dp$  .. 215, 976, 1044, 1062, 1063, 1405  
 $\eq@dump@box$  545, 557, 1028, 1365, 1567  
 $\eq@failout$  ..... 886, 951, 959  
 $\EQ@fallback$  ..... 917, 946, 953, 1012  
 $\eq@final@linecount$  ... 493, 518, 523  
 $\eq@finish$  ..... 440, 493, 2009  
 $\eq@firstht$  .... 223, 543, 554, 671,  
     976, 1054, 1382, 1431, 1590, 1591  
 $\eq@fix@lastline$  ..... 1031, 1042  
 $\eq@foreground$  ..... 408  
 $\eq@frame$  ..... 385, 389, 392, 395,  
     499, 541, 552, 647, 687, 929,  
     1391, 1417, 1449, 1499, 1531, 1587  
 $\eq@frame@adjust$  ..... 929, 940  
 $\eq@framesep$  ... 396, 399, 649, 689,  
     941, 942, 1392, 1418, 1571, 1577  
 $\eq@framewd$  ... 386, 393, 649, 689,  
     941, 942, 1392, 1418, 1571, 1577  
 $\eq@given@sidespace$  ..... 231, 380  
 $\eq@group$  ..... 425, 440, 505, 633,  
     1074, 1183, 1206, 1837, 1855, 2057  
 $\eq@GRP@first@dmath$  .....  
     494, 506, 507, 633, 1855, 1957  
 $\EQ@hasLHS$  .... 276, 281, 698, 750,  
     978, 1018, 1092, 1163, 1430, 1919  
 $\eq@hasNumber$  ..... 212–214,  
     419, 443, 475, 489, 519, 980,  
     1001, 1075, 1133, 1443, 1502,  
     1538, 1791, 1793, 1881, 1885, 1915  
 $\eq@holdnumber$  ..... 367  
 $\eq@hshift$  ..... 228  
 $\eq@I@setsides$  ..... 1521  
 $\eq@impinging$  ..... 207  
 $\eq@indentstep$  .... 225, 230, 878,  
     1115, 1117, 1132, 1146, 1153, 1156  
 $\eq@insert$  ..... 707  
 $\eq@isIntertext$  .....  
     229, 987, 1909, 2004, 2143, 2144  
 $\EQ@last@trial$  ..... 961, 1009  
 $\eq@layout$  .... 372, 934, 982, 995,  
     1002, 1033, 1066, 1368, 1425, 1920  
 $\eq@left$  ..... 320, 339, 1597  
 $\eq@left@a$  ..... 1598, 1603

\eq@lines 208, 892, 905, 973, 1030,  
1033, 1034, 1187, 1202, 1207,  
1316, 1333, 1337, 1346, 1347, 1450  
\eq@linewidth . . . . . 226,  
879, 930–932, 971, 1069, 1073,  
1093, 1096, 1100, 1102, 1115,  
1123, 1124, 1130, 1146, 1150,  
1154, 1162, 1182, 1247, 1427,  
1470, 1524, 1530, 1533, 1818, 1914  
\eq@linewidths . . . . .  
. . . . . 879, 885, 918, 920, 923, 938  
\eq@lrunpack . . . . . 801, 1705  
\eq@mark . . . . . 707  
\eq@measure . . . . . 439, 877  
\eq@measure@lines . . . . . 1037, 1270  
\eq@measurements 896, 906, 965, 984,  
1035, 1051, 1266, 1298, 1306, 1336  
\eq@ml@a . . . . . 1276, 1278  
\eq@ml@continue 1271, 1276, 1289, 1309  
\eq@ml@record@indents . . . . 1036, 1253  
\eq@ml@vspace . . . . . 1311  
\eq@newline . . . . . 705, 706, 856  
\eq@newlinea . . . . . 856  
\eq@newlineb . . . . . 856  
\eq@nextlayout . . . . . 953, 954  
\eq@nulldisplay . . . . . 452, 835  
\eq@nullleft . . . . . 1598, 1607  
\eq@nullright . . . . . 1601, 1608  
\eq@number . . . . . 194, 363, 364,  
476, 477, 480, 482, 483, 486, 1886  
\EQ@numbox . . . . .  
. . . . . 201, 484, 488, 540, 556, 660,  
1075, 1135, 1175, 1193, 1376,  
1389, 1399, 1406, 1421, 1551,  
1553, 1557, 1559, 1883, 1905, 1995  
\eq@overrun . . . . . 232  
\eq@params . . . . . 537, 549, 880, 1353, 1564  
\eq@parshape . . . . . 504, 518, 537,  
549, 983, 1226, 1352, 1437, 1564  
\EQ@prebin@space . . . . . 282, 294, 297, 712  
\EQ@prebin@space@a . . . . . 282, 295  
\eq@prelim . . . . . 425, 447, 1863, 2057  
\eq@prev@badness . . . . . 1203, 1205, 1216  
\eq@prev@lines . . . . . 1202, 1206, 1207  
\eq@prevshape . . . . . 460, 463, 466  
\eq@punct . . . . . 715  
\EQ@QED . . . . . 277  
\eq@readjust . . . . . 829  
\eq@recalc . . . . . 1038, 1049  
\eq@recalc@a . . . . . 1051, 1053  
\eq@recalc@b . . . . . 1055, 1058  
\eq@reinsert . . . . . 825  
\eq@remark . . . . . 827  
\eq@repack . . . . . 730, 769  
\eq@repacka . . . . . 776, 781, 810  
\eq@resume@parshape . . . . . 694, 696  
\eq@retry@with@number . . . . . 1001, 1167  
\eq@retry@with@number@a . . . . . 1167  
\eq@revspace . . . . . 823, 861  
\eq@revspaceb . . . . . 823, 861  
\eq@right . . . . . 320, 339, 1600  
\eq@right@a . . . . . 1601, 1604  
\eq@saveparinfo . . . . . 453, 461  
\eq@setnumber 428, 473, 1880, 1882, 2060  
\eq@setup@a . . . . . 430, 703  
\EQ@setwDL . . . . . 435, 438, 745, 789  
\eq@shiftnumber . . . . .  
. . . . . 366, 520, 668, 986, 1074, 1166,  
1168, 1173, 1184, 1191, 1209,  
1212, 1218, 1223, 1225, 1428,  
1443, 1502, 1523, 1538, 1921, 2026  
\eq@shortLHS . . . . . 1018, 1025  
\eq@shortskiplimit . . . . . 383, 384  
\EQ@shortskips . . . . .  
. . . . . 632, 639, 652, 659, 666, 672, 677  
\eq@startup . . . . . 431, 697  
\eq@topspace . . . . .  
. . . . . 502, 511, 514, 630, 1960, 1963  
\EQ@trial . . . . . 888, 914, 961, 1000,  
1224, 1228, 1902, 1908, 2129, 2143  
\eq@trial . . . . . 884, 885, 919  
\eq@trial@a . . . . . 923, 927  
\eq@trial@b . . . . .  
. . . . . 933, 990, 1068, 1070, 1082,  
1120, 1127, 1143, 1159, 1164, 1819  
\eq@trial@c . . . . . 946, 990, 991, 1015, 1068  
\eq@trial@d . . . . . 933, 1015  
\eq@trial@done . . . . . 947, 949  
\eq@trial@init . . . . . 953, 994  
\eq@trial@p . . . . . 998, 1026, 1204  
\eq@trial@save . . . . . 963, 1000, 1009, 1228  
\eq@trial@succeed 945, 1005, 1020, 1022  
\eq@try@layout@? . . . . . 1067  
\eq@try@layout@A 1120, 1143, 1159, 1161  
\eq@try@layout@D . . . . . 1104, 1114, 1127  
\eq@try@layout@L . . . . . 1107, 1122  
\eq@try@layout@l . . . . . 1097, 1145  
\eq@try@layout@M . . . . . 1817  
\eq@try@layout@multi . . . . .  
. . . . . 1070, 1082, 1088, 1091  
\eq@try@layout@S . . . . . 1096, 1111, 1129  
\eq@typeset@equation . . . . . 1373, 1379,  
1385, 1396, 1402, 1409, 1414, 1562  
\eq@typeset@frame . . . . . 1372, 1378,  
1384, 1395, 1401, 1408, 1413, 1586  
\eq@typeset@L@single . . . . . 535  
\eq@typeset@leftnumber . . . . .

`\eq@typeset@LM` ..... 1375    `\eqlineskip` ..... 167,  
`\eq@typeset@LShifted` ..... 1387    375, 387, 390, 397, 401, 500, 1354  
`\eq@typeset@LT` ..... 1381    `\eqmargin` ..... 167, 1130, 1142  
`\eq@typeset@R@single` ..... 547    `\eqnumcolor` ..... 167, 486  
`\eq@typeset@RB` ..... 1404    `\eqnumfont` ..... 167, 486  
`\eq@typeset@rightnumber` ..... 1400, 1407, 1556    `\eqnumform` ..... 167, 486  
`\eq@typeset@RM` ..... 1398    `\eqnumplace` ..... 167, 526, 670, 1426  
`\eq@typeset@RShifted` ..... 1411    `\eqnumsep` ..... 167,  
`\eq@typeset@Unnumbered` ..... 530, 1371    488, 1075, 1076, 1135, 1175, 1193  
`\eqvadjust` ..... 707    `\eqnumsize` ..... 167, 486  
`\EQ@vimbox` ..... 205, 726, 862    `\eqpunct` ..... 628, 762  
`\EQ@vimcopy` ..... 206, 726, 869    `\eqrightskip` ..... 196  
`\EQ@vims` ..... 211    `\eqstyle` ..... 167, 382, 427, 2060  
`\eq@vspan` ..... 197, 675, 897, 908, 966, 976, 1050, 1063,  
`\eqwdCond` ..... 224, 321, 752, 1080, 1171, 1312, 1376, 1399, 1406, 1431, 1580  
`\eqwdL` ..... 216, 721, 734, 739, 741, 744, 1433, 1450, 1451, 1516, 1801, 2111  
`\eqwdMin` ..... 218, 975, 745, 750, 787, 789, 978, 1025,  
`\eqwdNum` ..... 202, 474, 1093–1095, 1100, 1102, 1106,  
`\eqwdR` ..... 715, 729, 735, 736, 742, 750, 788 1117, 1123, 1125, 1147, 1320,  
`\eqwdRmax` ..... 222, 2080 1345, 1430, 1910, 1912, 2022, 2080  
`\eqwdT` ..... 217, 897, 908, 966, 975, 1025,  
`\EQ@widths` ..... 916 1050, 1060, 1185, 1320, 1337,  
`\eqbinoffset` ..... 167, 198, 1668, 1681 1344, 1429, 1470, 1484, 1485,  
`\eqbreakdepth` ..... 186, 414, 1665, 1678 1487, 1524, 1533, 1580, 1911, 1912  
`\eqcolor` ..... 167  
`\eqdelimoffset` ..... 183, 198, 1669  
`\eqfontsize` ..... 167  
`\eqframe` ..... 1569, 1580  
`\eqgrp@elt` ..... 1954, 1988  
`\eqindent` ..... 167, 251,  
`\eqindentstep` ..... 254, 257, 260, 267, 503, 1425, 2014  
`\eqinfo` ..... 184, 369, 878  
`\eqinterlinepenalty` ..... 167, 857, 1356  
`\eqleftskip` ..... 195  
`\eqlineskip` ..... 167, 376, 377, 387, 390, 397,  
`\eqlineskiplimit` ..... 401, 500, 1355, 1390, 1416, 1966  
`\eqmargin` ..... 167, 1130, 1142  
`\eqnumcolor` ..... 167, 486  
`\eqnumfont` ..... 167, 486  
`\eqnumform` ..... 167, 486  
`\eqnumplace` ..... 167, 526, 670, 1426  
`\eqnumsep` ..... 167,  
`\eqnumsize` ..... 167, 486  
`\eqpunct` ..... 628, 762  
`\eqrightskip` ..... 196  
`\eqstyle` ..... 167, 382, 427, 2060  
`\errorcontextlines` ..... 144  
`\errorstopmode` ..... 149, 728, 734, 2086  
`\everycr` ..... 2066  
`\everydisplay` ..... 311, 357, 422, 704  
`\everyhbox` ..... 322, 340  
`\everymath` ..... 704  
`\everypar` ..... 450  
`\everyvbox` ..... 325, 343  
`\exhyphenpenalty` ..... 1357  
`\expandafter` ..... 24, 40, 86, 124,  
`\fi` ..... 311, 422, 518, 565, 566, 621, 1694

## F

`\f@ur` ..... 42, 1346, 1367, 1369  
`\false@false@false` ..... 1328, 1339  
`\false@true@false` ..... 1329, 1350  
`\fboxrule` ..... 385, 393, 1571  
`\fboxsep` ..... 394, 399, 1571  
`\fi` ..... 29, 30, 34, 37, 63,  
`\fboxrule` ..... 68, 76–79, 110, 111, 131, 132,  
`\fboxsep` ..... 237, 245, 248, 254, 262, 265,  
`\fboxx` ..... 275, 286, 296, 301, 395, 423–  
`\fboxy` ..... 425, 440, 448, 449, 471, 478,  
`\fboxz` ..... 479, 490, 491, 501, 512, 515,  
`\fboxx` ..... 527, 528, 531, 544, 555, 566,  
`\fboxy` ..... 576, 586, 596, 610, 642, 645,  
`\fboxz` ..... 646, 650, 673, 678–683, 690,  
`\fboxx` ..... 717, 746, 747, 763, 804, 813,  
`\fboxy` ..... 815, 823, 832, 848, 878, 879,  
`\fboxz` ..... 923, 924, 929, 937, 938, 1001,  
`\fboxx` ..... 1006, 1007, 1010, 1023, 1025,  
`\fboxy` ..... 1033, 1060, 1061, 1064, 1077,  
`\fboxz` ..... 1089, 1098, 1108, 1112, 1137,  
`\fboxx` ..... 1138, 1163, 1174, 1178, 1181,  
`\fboxy` ..... 1183, 1206, 1221, 1222, 1227,  
`\fboxz` ..... 1229, 1247, 1250, 1258, 1275,  
`\fboxx` ..... 1281, 1285, 1295, 1297, 1304,

1309, 1313, 1324, 1325, 1327–  
 1329, 1332, 1339, 1340, 1350,  
 1358, 1360, 1368, 1393, 1419,  
 1445, 1452, 1457, 1462, 1467,  
 1475, 1480, 1482, 1486, 1492,  
 1501, 1507–1509, 1514, 1518,  
 1527, 1528, 1535, 1544–1546,  
 1592, 1671, 1680, 1681, 1695,  
 1715, 1719, 1743, 1748, 1750,  
 1756, 1758, 1764, 1773, 1783,  
 1808, 1828, 1830, 1834, 1865,  
 1869, 1876, 1910, 1911, 1913,  
 1914, 1917–1922, 1931, 1932,  
 1939–1941, 1945, 1979, 1980,  
 1996, 2010, 2016, 2017, 2019,  
 2020, 2023, 2027, 2057, 2061,  
 2074, 2092, 2107, 2110, 2157, 2161  
`\finish@end` . . . . . 572, 595, 609, 617, [620](#)  
`\firstmark` . . . . . 119  
`\fontdimen` . . . . . 1726–1732  
`\found@punct` . . . . . 602,  
     604, 614, 615, 624, 761, 762, 765  
`\framebox` . . . . . 1572  
`\freeze@glue` [80](#), 387, 390, 397, 401, 500  
`\frozen@everydisplay` . . . . . 836  
`\futurelet` . . . . . 66, 71, 561, 568, 569

## G

`\g@addto@macro` . . . . . 94  
`\gdef` . . 85, 91, 136, 435, 604, 2129, 2143  
`\GenericInfo` . . . . . 145  
`\global` . . . . . 105, 126,  
     136, 281, 282, 311, 320, 321,  
     339, 362, 415, 424, 449, 484,  
     485, 488, 507, 632, 659, 666,  
     672, 677, 693, 698, 712, 723,  
     725, 726, 732, 733, 768, 790,  
     794, 811, 862, 864, 869, 871,  
     884, 921, 947, 953, 961, 1312,  
     1662, 1675, 1801, 1855–1862,  
     1872, 1875, 1879, 1883, 1901,  
     1904, 1910, 1911, 1913, 1914,  
     1916, 1917, 1919–1921, 1930,  
     1938, 1943, 1944, 1957, 1989,  
     1995, 1998, 1999, 2058, 2061,  
     2066, 2068, 2087, 2089, 2111,  
     2119, 2124, 2128, 2133, 2138, 2142  
`\grp@aligned` . . . . .  
     . . . 412, 413, 1841, 1861, 1919,  
     1920, 1928, 1930, 1942, 1950, 2021  
`\GRP@box` 1856, 1898, 1904, 1906, 1925,  
     1989, 1990, 2124, 2126, 2138, 2140  
`\grp@eqs@numbered` . . . . .  
     1840, 1860, 1916, 1936, 1949, 1962

## H

`\halign` . . . . . 850, 2070  
`\hbox` . . . . . 543, 554, 723, 732, 733,  
     786, 790, 791, 794, 795, 811,  
     1045, 1273, 1279, 1421, 1559,  
     1576, 1580, 1590, 1905, 1992,  
     2033, 2036, 2038, 2087–2090,  
     2104, 2105, 2107, 2110, 2139, 2150  
`\hfil` 1421, 1559, 2032, 2035, 2037, 2039  
`\hfuzz` . . . . . 882,  
     997, 1081, 1358–1360, 1362, 1547  
`\hiderel` . . . . . [291](#)  
`\hsize` . . 158, 708, 1421, 1559, 2121, 2135  
`\hskip` 1046, 1670, 1823, 1824, 2106, 2115  
`\hss` . . . . . 543, 554, 1583, 1590  
`\ht` . . . . . 154, 660, 1305, 1376,  
     1399, 1406, 1551, 1557, 1736,  
     1749, 1969, 1970, 1974, 1975, 2050

## I

`\if` . . . . . 79, 240, 244, 257, 261,  
     267, 395, 425, 440, 475, 499,  
     505, 506, 519, 520, 541, 552,  
     633, 639, 647, 665, 668, 670,  
     687, 929, 999, 1001, 1002, 1004,  
     1018, 1021, 1033, 1074–1076,  
     1092, 1133, 1163, 1168, 1171,  
     1177, 1183, 1184, 1206, 1210,

\interlinepenalty . . . . .	711, 1356
\intermath@penalty . . . . .	1810, 1821, 1822
\intertext . . . . .	454
<b>K</b>	
\keep@glue . . . . .	81, 295, 718, 875, 1703
\kern . . . . .	540, 556, 1394, 1554, 1560, 1572, 1578, 1579, 1591, 1774, 1966, 1977, 1978, 2152
<b>L</b>	
\label . . . . .	361
\lastbox . . . . .	722, 731, 775, 780, 785, 864, 871, 1043, 1272, 1367, 1705, 1713, 1716, 1721, 1991, 1995, 1998, 1999, 2085
\lastpenalty . . . . .	296, 299, 717, 773, 812, 1708, 1709, 1808, 1993, 2092
\lastskip . . . . .	1046, 1287, 1293, 1294, 1312, 1313, 1807
\latex@end . . . . .	620
\lccode . . . . .	1780
\leavevmode . . . . .	423, 424, 1827
\left . . . . .	320, 339, 355, 1594, 1611, 1621
\leftmargin . . . . .	846
\leftskip . . . . .	159, 503, 508, 540, 556, 661, 710, 881, 910, 1193, 1194, 1198, 1225, 1236, 1286, 1434, 1493, 1522, 1526, 1530, 1533, 1588, 1590
\let . . . . .	29, 39, 40, 45–58, 65, 68, 70, 93, 95–97, 100, 105, 126, 136, 138, 139, 212–214, 229, 276, 277, 280–282, 292–294, 305– 310, 314–320, 323, 326, 331– 339, 341, 344, 349–355, 362, 364, 366, 367, 409–413, 415, 419, 443, 454, 460, 477, 485, 489, 494, 507, 561, 602, 632, 659, 666, 672, 677, 698, 705– 707, 712, 768, 876, 895, 898, 904, 914, 916, 917, 933, 951, 953, 961, 965, 967, 1032, 1033, 1035, 1041, 1051, 1055, 1068, 1166, 1173, 1191, 1209, 1212, 1218, 1225, 1271, 1275, 1289, 1309, 1336, 1352, 1598, 1601, 1610, 1611, 1614, 1647, 1657, 1658, 1666, 1679, 1683, 1687, 1689, 1699, 1700, 1791, 1793, 1798, 1800, 1805, 1837–1841, 1843, 1849, 1855, 1857, 1860– 1862, 1872, 1875, 1879, 1881, 1885, 1886, 1916, 1919–1921, 1930, 1938, 1954, 1957, 1985,

\linepenalty	160, 709, 1357	\maxdimen	148, 230, 663, 708, 728, 859, 878, 997, 1050, 1722, 2079, 2086
\lineskip	1355	\maxint	44, 1183
\lineskiplimit	1355	\meaning	104, 107, 124, 125
\linewidth	556, 844, 918	\medmuskip	313, 330
\listwidth	165, 166, 844, 846, 847	\message	83
\long	89, 91, 145	\MessageBreak	749, 751, 894, 903, 907, 909, 965, 966, 992, 1199, 1427–1437, 1948–1951, 1975
\lower	1752, 1766	\mkern	2150
\lowercase	568, 1780	\moveright	1590
\lr@level	279, 291, 320, 339, 1596, 1662, 1663, 1665, 1669, 1675, 1676, 1678, 1681	\mskip	289, 295
\lr@subscript	1740, 1746	\multiply	1337, 1346, 1347, 1485, 1487, 1663, 1676
\lr@subsup	1742, 1762		
\lr@superscript	1741, 1754		
\lrss@reattach	1718, <u>1724</u>		
<b>M</b>			
\m@@Bin	<u>292</u> , 349, 1666, 1699	\NeedsTeXFormat	2
\m@@DeA	352, 1657	\newbox	1898, 1899
\m@@DeB	351, <u>1647</u>	\newcommand	23, 291, 628, 1569, 1778, 1823–1825, 2096, 2098, 2102, 2114, 2147, 2159
\m@@DeL	351, <u>1647</u>	\newcount	43, 44, 186–188, 190, 191, 208–211, 493, 1596, 2030
\m@@DeR	351, <u>1647</u>	\newcounter	1871
\m@@Rel	<u>292</u> , 349, 1699	\newdimen	165, 169, 170, 181, 184, 202, 204, 215–228, 231, 269, 715
\m@@symBin	305, 350	\newenvironment	418, 442, 1791, 1793, 1842, 1848, 2054, 2118, 2132
\m@@symDeA	305, 354	\newif	358
\m@@symDeB	305, 354	\newlength	179, 180, 189, 195–197
\m@@symDeL	353	\newmuskip	182, 183, 192, 193, 198
\m@@symDel	305	\newsavebox	199–201, 203
\m@@symDeR	305, 353	\newskip	2029, 2095
\m@@symRel	305, 350	\newtoks	41, 185, 915, 1847
\m@Bin	292, 314, 331, 349, 1666, 1679, 1699	\next@label	361, 362, 485, 1879
\m@DeA	317, 336, 352, 1657	\noalign	2066
\m@DeB	316, 335, 351, 1647	\nobreak	536, 548, 1563, 1589
\m@DeL	316, 335, 351, 1647	\noexpand	39, 130
\m@DeR	316, 335, 351, 1647	\noindent	451, 538, 550, 700, 1367, 1565, 1588, 1707, 2121, 2135
\m@ne	1308, 1363, 1675	\nointerlineskip	538, 550, 642, 1045, 1201, 1565, 1589, 1706
\m@Rel	293, 314, 332, 349, 1699	\nref	<u>2160</u>
\m@th	2033, 2036, 2038	\nulldelimiterspace	1622
\mark	142, 707	\nullfont	117
\mark@lhs	<u>278</u> , 304, 305	\number	5, 16, 17, 86, 892, 905, 1149, 1257, 1302, 1303, 1684, 1709, 1786, 2050
\mark@lhs@a	283, <u>288</u>		
\mathaxis	1732, 1771		
\mathchardef	1659, 1660		
\mathchars@reset	94		
\mathclose	1633–1638		
\mathindent	269, 272, 1522, 1524, 2024		
\mathopen	1626–1631		
\mathord	2036		
\mathrel	291, 1641–1646		
\Mathstrut@	2046, 2047, 2074		
\mathsurround	1804, 1815, 2150		
<b>O</b>			
\options		\options@a	24, 27
\options@b		\options@c	<u>27</u>
\options@c			

\options@d .....	27	\relax .....	6, 8,
\or .....	76, 466, 778, 783, 799, 819,		12, 19, 21, 29, 80–82, 100, 144,
	821, 822, 824, 826, 828, 1740, 1741		237, 254, 280, 294, 323, 326,
			341, 344, 369, 370, 386, 396,
			414, 467, 508, 712, 745, 789,
			808, 820, 849, 898, 928, 951,
			967, 1051, 1054, 1062, 1064,
			1069, 1117, 1125, 1142, 1157,
			1162, 1182, 1205, 1232, 1235,
			1238, 1241, 1244, 1245, 1289,
			1309, 1360, 1485, 1487, 1490,
			1571, 1610, 1659, 1660, 1669,
			1670, 1681, 1687, 1818, 1985,
			2002, 2063, 2105, 2120, 2134, 2161
		\relpenalty .....	713
		\remove@to@nnil .....	517
		\renewcommand .....	2148
		\renewenvironment .....	1826
		\replicate .....	83, 1156
		\replicate@a .....	86, 89
		\RequirePackage .....	14, 21
		\right .	320, 339, 355, 1595, 1611, 1623
		\right@delim@code .....	
			1684, 1703, 1709, 1770, 1774
		\rightmargin .....	847
		\rightskip .....	159, 503,
			710, 882, 910, 1081, 1195, 1198,
			1236, 1434, 1495, 1513, 1517, 1547
		\rlap .....	540, 543, 554, 556
		\romannumeral .....	86
		S	
		\sb .....	1691
		\sbox .....	484, 1883
		\scriptfont .....	1730, 1731
		\set@label .....	483, 629
		\setbox .....	699, 722,
			723, 725, 726, 731–733, 775,
			780, 785, 786, 790, 794, 811,
			862, 864, 869, 871, 996, 1043,
			1272, 1273, 1279, 1367, 1705,
			1713, 1714, 1716, 1721, 1856,
			1904, 1953, 1989, 1991, 1992,
			1995, 1998, 1999, 2033, 2036,
			2038, 2065, 2085, 2087, 2089,
			2110, 2119, 2124, 2133, 2138, 2150
		\setcounter .....	1890, 1891, 1896
		\setkeys .....	25, 426, 1864, 2059
		\setlength .....	380,
			660, 675, 736, 788, 1059, 1071,
			1080, 1095, 1115, 1123, 1130,
			1146, 1153, 1154, 1182, 1194,
			1195, 1236, 1247, 1283, 1284,
			1376, 1392, 1399, 1406, 1451,

1470, 1484, 1493, 1495, 1524,	427, 463, 508, 599, 615, 636,
1530, 1533, 1547, 1551, 1557,	652, 653, 741, 742, 745, 749,
1577, 1736, 1737, 1749, 1757,	750, 752, 789, 842–844, 846,
1771, 1912, 1927, 1968, 1970, 2015	847, 879, 897, 908, 910, 925,
\showbox . . . . . 148, 734, 2086	932, 966, 971, 973, 975, 976,
\showboxbreadth . . . . .	978, 1069, 1079, 1085, 1086,
. . . . . 148, 728, 1722, 2079, 2086	1094, 1102, 1106, 1117, 1124,
\showboxdepth 148, 728, 1722, 2079, 2086	1125, 1141, 1142, 1150, 1156,
\showlists . . . . . 728, 1722, 2079	1157, 1162, 1189, 1198, 1202,
\showthe . . . . . 734	1203, 1211, 1216, 1249, 1257,
\sixt@n . . . . . 146, 1333	1281, 1299, 1305, 1338, 1349,
\skip@ . . . . . 56	1427, 1429–1436, 1818, 1901,
\skip@a . . . . . 54, 1287, 1288, 1294, 1299	1926, 1948, 1951, 1955, 1974,
\skip@b . . . . . 54	1975, 2050, 2060, 2128, 2142, 2152
\skip@c . . . . . 54, 1046, 1551,	\theb@ole . . . . . 79,
1552, 1557, 1558, 1970, 1971, 1974	652, 750, 1428, 1430, 1949, 1950
\sp . . . . . 1692	\theequation . . . . . 477, 1889, 1892, 1893
\space . . . . . 145,	\theparentequation . . . . . 1889, 1892
153, 463, 509, 741, 892, 894,	\thickmuskip . . . . . 289, 313, 330, 737
905, 965, 992, 1117, 1124, 1125,	\thinspace . . . . . 628, 2154, 2156
1141, 1142, 1149, 1156, 1157,	\thr@ . . . . . 135, 462, 815, 1316, 1702
1199, 1249, 1299, 1349, 1425, 2050	\times . . . . . 2159
\splitbotmark . . . . . 122	\toks@ . . . . . 58, 614, 615
\splitfirstmark . . . . . 121	\toks@a . . . . . 57, 581, 586, 599
\ss@delim@a . . . . . 1684, 1687	\toks@b . . . . . 57, 589, 599
\ss@finish . . . . . 1693, 1701	\toks@c . . . . . 57, 586, 599
\ss@scan . . . . . 1605, 1683	\toks@d . . . . . 57
\ss@scan@a . . . . . 1689, 1690, 1700	\toks@e . . . . . 57
\ss@scan@b . . . . . 1694, 1696, 1698	\toks@f . . . . . 57
\stepcounter . . . . . 477	\toksdef . . . . . 59–62
\string . . . . . 93, 104, 118–123, 129, 2064	\tolerance . . . . . 161, 1363
\strip@prefix . . . . . 124	\topmark . . . . . 118
\strut . . . . . 2046	\true@false@true . . . . . 1327, 1339
\sub@base@one . . . . . 1728, 1747	\true@true@true . . . . . 1350
\sub@base@two . . . . . 1729, 1763	\tw@ . . . . . 289, 722, 723, 731–733,
\sub@depth . . . . . 1724,	775, 780, 785, 786, 791, 795,
1747, 1748, 1750–1752, 1763–1766	811, 1043–1045, 1148, 1152,
\sub@drop . . . . . 1731, 1737	1272, 1273, 1279, 1281, 1283,
\subsup@flag . . . . .	1284, 1305, 1367, 1368, 1692,
1683, 1708, 1711, 1712, 1718, 1739	1713, 1714, 1717, 1718, 1726–
\sup@base . . . . . 1724, 1755, 1756, 1758–1760	1732, 1749, 1752, 1757, 1760,
\sup@base@one . . . . . 1727, 1755	1766, 1992, 2085, 2086, 2088, 2090
\sup@drop . . . . . 1730, 1736	\twang@adjust . . . . . 1751, 1759, 1765, 1768
\sym@xheight . . . . . 1726, 1749, 1757	

## T

\tabskip . . . . . 2034, 2039, 2067
\temp@a . . . . . 1233, 1237, 1241, 1249
\textchar . . . . . 2152, 2156
\textfont . . . . . 1726–1729, 1732
\textmath@setup . . . . .
323, 326, 341, 344, 348, 2110, 2116
\the . . . . . 153, 154, 158–162,
311, 359, 382, 386, 396, 422,

## U

\unhbox . . . . . 545, 557, 723, 732, 733,
786, 795, 833, 1045, 1273, 1279,
1368, 1369, 1567, 1707, 1717,
1738, 1883, 1992, 2052, 2088, 2090
\unhcopy . . . . . 732, 791, 811, 1028, 2088
\unpenalty . . . . . 723,
724, 732, 733, 779, 784, 786,
791, 795, 800, 814, 863, 870,

1287, 1294, 1312, 1708, 1710, 1721, 1810, 1814, 1997, 2084, 2103	\widowpenalty ..... 711, 1356
\unskip ..... 723, 724, 732, 733, 777, 786, 791, 795, 798, 811, 1046, 1279, 1287, 1294, 1312, 1706, 1707, 1721, 1807, 1814, 2088, 2090, 2091, 2103	\wlog ..... 153
\unvbox 862, 865, 869, 872, 1906, 1984, 1990, 2006, 2125, 2126, 2139, 2140	\write ..... 146
\upshape ..... 174	
<b>V</b>	
\vadjust ..... 140, 707	\xdef 30, 100, 508, 598, 615, 624, 745, 765, 789, 841, 970, 1684, 1709, 2041
\value ..... 1890, 1896	
\vbox ..... 699, 862, 869, 996, 1579, 1590, 1904, 1953, 1989, 2065, 2119, 2124, 2125, 2133, 2138	
\vglue ..... 1552, 1558, 1971	<b>X</b>
\voidb@x ..... 1714, 1856	\z@ . 63, 81, 166, 296, 320, 321, 339, 474, 543, 554, 642, 699, 710, 711, 715, 721, 727, 729, 735, 786, 787, 845, 879, 882, 996, 1050, 1081, 1139, 1171, 1195, 1225, 1254, 1273, 1279, 1288, 1293, 1309, 1313, 1336, 1362, 1442, 1448, 1450, 1454, 1459, 1475, 1480, 1484, 1488, 1495, 1498, 1511, 1516, 1525, 1526, 1529, 1547, 1576, 1579, 1590, 1670, 1705, 1707, 1716–1718, 1721, 1736–1738, 1801, 1804, 1815, 1858, 1859, 1887, 1991, 1992, 2016, 2017, 2033, 2036, 2038, 2050, 2052, 2065, 2067, 2068, 2080, 2110, 2111, 2150, 2152
\vrule ..... 81, 1622	\z@rule . 81, 1572, 1720
\vskip 502, 511, 514, 691, 1960, 1963, 2005	\z@skip . 197, 710, 839, 840, 881, 1050, 1361, 1519, 1548, 2034, 2067
\vss ..... 1581, 1590	
\vtop ..... 2125, 2139	\zero@bop ..... 1658
<b>W</b>	
\wd ..... 153, 488, 556, 736, 742, 749, 787, 788, 1043, 1071, 1075, 1076, 1079, 1085, 1095, 1131, 1135, 1175, 1193, 1272, 1281, 1283, 1284, 2050, 2111, 2152	