

# The `breqn` package

Morten Høgholm  
`mh.ctan@gmail.com`

2008/07/28 v0.98

## Abstract

The `breqn` package facilitates automatic line-breaking of displayed math expressions.

## User's guide

### 1 A bit of history

Originally `breqn`, `flexisym`, and `mathstyle` were created by Michael J. Downes from the American Mathematical Society during the 1990's up to late 2002. Sadly—and much to the shock of the  $\text{\TeX}$  world—Michael passed away in early 2003 at the age of only 44.

The American Mathematical Society has kindly allowed me to assume maintainership of this part of his work and I wish to express my gratitude to them and to Barbara Beeton in particular for providing me with the files I needed.

I hope to continue Michael's work, thereby allowing users to create more *masterpieces of the publishing art* as I think he would have wanted.

### 2 Package loading

The recommended way of loading the `breqn` package is to load it *after* other packages dealing with math, i.e., after `amsmath`, `amssymb`, or packages such as `mathpazo` or `mathptmx`.

The `flexisym` package (described in section 11 on page 10) is required by `breqn` and ensures the math symbols are set up correctly. By default `breqn` loads it with support for Computer Modern but if you use a different math package requiring slightly different definitions, it must be loaded before `breqn`. Below is an example of how you enable `breqn` to work with the widely used `mathpazo` package.

```
\usepackage{mathpazo}  
\usepackage[mathpazo]{flexisym}
```

`\usepackage{breqn}`

Currently, the packages `mathpazo` and `mathptmx` are supported. Despair not: Chances are that the package will work using the default settings. If you find that a particular math font package doesn't work then please see implementation in `flexisym.dtx` for how to create a support file—it is easier than one might think. Contributions welcome.

The documentation for the package was formerly found in `breqndoc`. It has now been added to this implementation file. Below follows the contents of the original `breqn` documentation. Not all details hold anymore but I have prioritized fixing the package.

### 3 To do

- Handling of QED
- Space between `\end{dmath}` and following punctuation will prevent the punctuation from being drawn into the equation.
- Overriding the equation layout
- Overriding the placement of the equation number
- “alignid” option for more widely separated equations where shared alignment is desired (requires two passes)
- Or maybe provide an “alignwidths” option where you give lhs/rhs width in terms of ems? And get feedback later on discrepancies with the actual measured contents?
- `\intertext` not needed within `dgroup`! But currently there are limitations on floating objects within `dgroup`.
- `align={1}` or 2, 3, 4 expressing various levels of demand for group-wide alignment. Level 4 means force alignment even if some lines then have to run over the right margin! Level 1, the default, means first break LHS-RHS equations as if it occurred by itself, then move them left or right within the current line width to align them if possible. Levels 2 and 3 mean try harder to align but give up if overfull lines result.
- Need an `\hshift` command to help with alignment of lines broken at a discretionary times sign. Also useful for adjusting inside-delimiter breaks.

### 4 Introduction

The `breqn` package for L<sup>A</sup>T<sub>E</sub>X provides solutions to a number of common difficulties in writing displayed equations and getting high-quality output. For example, it

is a well-known inconvenience that if an equation must be broken into more than one line, `\left ... \right` constructs cannot span lines. The `breqn` package makes them work as one would expect whether or not there is an intervening line break.

The single most ambitious goal of the `breqn` package, however, is to support automatic linebreaking of displayed equations. Such linebreaking cannot be done without substantial changes under the hood in the way math formulas are processed. For this reason, especially in the alpha release, users should proceed with care and keep an eye out for unexpected glitches or side effects.

## 5 Principal features

The principal features of the `breqn` package are:

**semantically oriented structure** The way in which compound displayed formulas are subdivided matches the logical structure more closely than, say, the standard `eqnarray` environment. Separate equations in a group of equations are written as separate environments instead of being bounded merely by `\\` commands. Among other things, this clears up a common problem of wrong math symbol spacing at the beginning of continuation lines. It also makes it possible to specify different vertical space values for the space between lines of a long, broken equation and the space between separate equations in a group of equations.

**automatic line breaking** Overlong equations will be broken automatically to the prevailing column width, and continuation lines will be indented following standard conventions.

**line breaks within delimiters** Line breaks within `\left ... \right` delimiters work in a natural way. Line breaks can be forbidden below a given depth of delimiter nesting through a package option.

**mixed math and text** Display equations that contain mixed math and text, or even text only, are handled naturally by means of a `dseries` environment that starts out in text mode instead of math mode.

**ending punctuation** The punctuation at the end of a displayed equation can be handled in a natural way that makes it easier to promote or demote formulas from/to inline math, and to apply special effects such as adding space before the punctuation.

**flexible numbering** Equation numbering is handled in a natural way, with all the flexibility of the `amsmath` package and with no need for a special `\nonumber` command.

**special effects** It is easy to apply special effects to individual displays, e.g., changing the type size or adding a frame.

**using available space** Horizontal shrink is made use of whenever feasible. With most other equation macros it is frozen when it occurs between `\left ... \right` delimiters, or in any sort of multiline structure, so that some expressions require two lines that would otherwise fit on one.

**high-quality spacing** The `\abovedisplayshortskip` is used when applicable (other equation macros fail to apply it in equations of more than one line).

**abbreviations** Unlike the `amsmath` equation environments, the `breqn` environments can be called through user-defined abbreviations such as `\beq ... \eeq`.

## 6 Shortcomings of the package

The principal known deficiencies of the `breqn` package are:

### 6.1 Incompatibilities

As it pushes the envelope of what is possible within the context of  $\text{\LaTeX} 2_{\epsilon}$ , the `breqn` package will tend to break other packages when used in combination with them, or to fail itself, when there are any areas of internal overlap; successful use may in some cases depend on package loading order.

### 6.2 Indention of delimited fragments

When line breaks within delimiters are involved, the automatic indention of continuation lines is likely to be unsatisfactory and need manual adjustment. I don't see any easy way to provide a general solution for this, though I have some ideas on how to attain partial improvements.

### 6.3 Math symbol subversion

In order for automatic line breaking to work, the operation of all the math symbols of class 2, 3, 4, and 5 must be altered (relations, binary operators, opening delimiters, closing delimiters). This is done by an auxiliary package `flexisym`. As long as you stick to the advertised  $\text{\LaTeX}$  interface for defining math symbols (`\DeclareMathSymbol`), things should work OK most of the time. Any more complex math symbol setup is quite likely to quarrel with the `flexisym` package. See Section 11 on page 10 for further information.

### 6.4 Subscripts and superscripts

Because of the changes to math symbols of class 2–5, writing certain combinations such as `^+` or `_{\pm}` or `^{\geq}` without braces would lead to error messages; (The problem described here already exists in standard  $\text{\LaTeX}$  to a lesser extent, as you may know if you ever tried `^{\neq}` or `^{\cong}`; and indeed there are no examples in

the L<sup>A</sup>T<sub>E</sub>X book to indicate any sanction for omitting braces around a subscript or superscript.)

The flexisym package therefore calls, as of version 0.92, another package called `mathstyle` which turns `^` and `_` into active characters. This is something that I believe is desirable in any case, in the long run, because having a proper `mathstyle` variable eliminates some enormous burdens that affect almost any nontrivial math macros, as well as many other things where the connection is not immediately obvious, e.g., the L<sup>A</sup>T<sub>E</sub>X facilities for loading fonts on demand.

Not that this doesn't introduce new and interesting problems of its own—for example, you don't want to put `usepackage` statements after `flexisym` for any package that refers to, e.g., `^^J` or `^^M` internally (too bad that the L<sup>A</sup>T<sub>E</sub>X package loading code does not include automatic defenses to ensure normal catcodes in the interior of a package; but it only handles the `@` character).

But I took a random AMS journal article, with normal end-user kind of L<sup>A</sup>T<sub>E</sub>X writing, did some straightforward substitutions to change all the equations into `dmath` environments, and ran it with active math sub/sup: everything worked OK. This suggests to me that it can work in the real world, without an impossible amount of compatibility work.

## 7 Incomplete

In addition, in the **alpha release [1997/10/30]** the following gaps remain to be filled in:

**documentation** The documentation could use amplification, especially more illustrations, and I have undoubtedly overlooked more than a few errors.

**group alignment** The algorithm for doing alignment of `mathrel` symbols across equations in a `dgroup` environment needs work. Currently the standard and `noalign` alternatives produce the same output.

**single group number** When a `dgroup` has a group number and the individual equations are unnumbered, the handling and placement of the group number aren't right.

**group frame** Framing a group doesn't work, you might be able to get frames on the individual equations at best.

**group brace** The `brace` option for `dgroup` is intended to produce a large brace encompassing the whole group. This hasn't been implemented yet.

**darray environment** The `darray` environment is unfinished.

**dseries environment** The syntax and usage for the `dseries` environment are in doubt and may change.

**failure arrangements** When none of the line-breaking passes for a `dmath` environment succeeds—i.e., at least one line is overfull—the final arrangement

is usually rather poor. A better fall-back arrangement in the failure case is needed.

## 8 Package options

Many of the package options for the `breqn` package are the same as options of the `dmath` or `dgroup` environments, and some of them require an argument, which is something that cannot be done through the normal package option mechanism. Therefore most of the `breqn` package options are designed to be set with a `\setkeys` command after the package is loaded. For example, to load the package and set the maximum delimiter nesting depth for line breaks to 1:

```
\usepackage{breqn}
\setkeys{breqn}{breakdepth={1}}
```

See the discussion of environment options, Section 10 on page 8, for more information.

Debugging information is no longer available as a package option. Instead, the tracing information has been added in a fashion so that it can be enabled as a `docstrip` option:

```
\generate{\file{breqn.sty}{\from{breqn.dtx}{package,trace}}}
```

## 9 Environments and commands

### 9.1 Environments

All of the following environments take an optional argument for applying local effects such as changing the typesize or adding a frame to an individual equation.

**dmath** Like `equation` but supports line breaking and variant numbers.

**dmath\*** Unnumbered; like `displaymath` but supports line breaking

**dseries** Like `equation` but starts out in text mode; intended for series of mathematical expressions of the form ‘A, B, and C’. As a special feature, if you use

```
\begin{math} ... \end{math}
```

for each expression in the series, a suitable amount of inter-expression space will be automatically added. This is a small step in the direction of facilitating conversion of display math to inline math, and vice versa: If you write a display as

```

\begin{dseries}
\begin{math}A\end{math},
\begin{math}B\end{math},
and
\begin{math}C\end{math}.
\end{dseries}

```

then conversion to inline form is simply a matter of removing the `\begin{dseries}` and `\end{dseries}` lines; the contents of the display need no alterations.

It would be nice to provide the same feature for `$` notation but there is no easy way to do that because the `$` function has no entry point to allow changing what happens before math mode is entered. Making it work would therefore require turning `$` into an active character, something that I hesitate to do in a  $\text{\LaTeX} 2_\epsilon$  context.

**dseries\*** Unnumbered variant of **dseries**

**dgroup** Like the **align** environment of **amsmath**, but with each constituent equation wrapped in a **dmath**, **dmath\***, **dseries**, or **dseries\*** environment instead of being separated by `\\`. The equations are numbered with a group number. When the constituent environments are the numbered forms (**dmath** or **dseries**) they automatically switch to ‘subequations’-style numbering, i.e., something like (3a), (3b), (3c), ..., depending on the current form of non-grouped equation numbers. See also **dgroup\***.

**dgroup\*** Unnumbered variant of **dgroup**. If the constituent environments are the numbered forms, they get normal individual equation numbers, i.e., something like (3), (4), (5), ... .

**darray** Similar to **eqnarray** but with an argument like **array** for giving column specs. Automatic line breaking is not done here.

**darray\*** Unnumbered variant of **darray**, rather like **array** except in using `\displaystyle` for all column entries.

**dsuspend** Suspend the current display in order to print some text, without loss of the alignment. There is also a command form of the same thing, `\intertext`.

## 9.2 Commands

The commands provided by the **breqn** package are:

**\condition** This command is used for a part of a display which functions as a condition on the main assertion. For example:

```

\begin{dmath}
f(x)=\frac{1}{x} \ \condition{for \ $x\neq 0$}

```

`\end{dmath}`.

$$f(x) = \frac{1}{x}, \quad \text{for } x \neq 0. \quad (1)$$

The `\condition` command automatically switches to text mode (so that interword spaces function the way they should), puts in a comma, and adds an appropriate amount of space. To facilitate promotion/demotion of formulas, `\condition` “does the right thing” if used outside of display math.

To substitute a different punctuation mark instead of the default comma, supply it as an optional argument for the `\condition` command:

`\condition[;]{...}`

(Thus, to get no punctuation: `\condition[]{...}`.)

For conditions that contain no text, you can use the starred form of the command, which means to stay in math mode:

```
\begin{dmath}
f(x)=\frac{1}{x} \condition*{x\neq 0}
\end{dmath}.
```

If your material contains a lot of conditions like these, you might like to define shorter abbreviations, e.g.,

```
\begin{verbatim}
\newcommand{\mc}{\condition*}% math condition
\newcommand{\tc}{\condition}% text condition
```

But the `breqn` package refrains from predefining such abbreviations in order that they may be left to the individual author’s taste.

`\hiderel` In a compound equation it is sometimes desired to use a later relation symbol as the alignment point, rather than the first one. To do this, mark all the relation symbols up to the desired one with `\hiderel`:

```
T(n) \hiderel{\leq} T(2^n) \leq c(3^n - 2^n) ...
```

## 10 Various environment options

The following options are recognized for the `dmath`, `dgroup`, `darray`, and `dseries` environments; some of the options do not make sense for all of the environments, but if an option is used where not applicable it is silently ignored rather than treated as an error.



```

\begin{dmath}[style={\small}]
\begin{dmath}[number={BV}]
\begin{dmath}[labelprefix={eq:}]
\begin{dmath}[label={xyz}]
\begin{dmath}[relindent={1em}]
\begin{dmath}[compact]
\begin{dmath}[spread={1pt}]
\begin{dmath}[frame]
\begin{dmath}[frame={1pt},framesep={2pt}]
\begin{dmath}[background={red}]
\begin{dmath}[color={purple}]
\begin{dmath}[breakdepth={0}]

```

Use the **style** option to change the type size of an individual equation. This option can also serve as a catch-all option for altering the equation style in other ways; the contents are simply executed directly within the context of the equation.

Use the **number** option if you want the number for a particular equation to fall outside of the usual sequence. If this option is used the equation counter is not incremented. If for some reason you need to increment the counter and change the number at the same time, use the **style** option in addition to the **number** option:

```
style={\refstepcounter{equation}}
```

Use of the normal **\label** command instead of the **label** option works, I think, most of the time (untested). **labelprefix** prepends its argument to the label (only useful as a global option, really), and must be called before **label**.

Use the **relindent** option to specify something other than the default amount for the indentation of relation symbols. The default is 2em.

Use the **compact** option in compound equations to inhibit line breaks at relation symbols. By default a line break will be taken before each relation symbol except the first one. With the **compact** option L<sup>A</sup>T<sub>E</sub>X will try to fit as much material as possible on each line, but breaks at relation symbols will still be preferred over breaks at binary operator symbols.

Use the **spread** option to increase (or decrease) the amount of interline space in an equation. See the example given above.

Use the **frame** option to produce a frame around the body of the equation. The thickness of the frame can optionally be specified by giving it as an argument of the option. The default thickness is **\fboxrule**.

Use the **framesep** option to change the amount of space separating the frame from what it encloses. The default space is **\fboxsep**.

Use the **background** option to produce a colored background for the equation body. The **breqn** package doesn't automatically load the **color** package, so this option won't work unless you remember to load the **color** package yourself.

Use the **color** option to specify a different color for the contents of the equation. Like the **background** option, this doesn't work if you forgot to load the **color**

package.

Use the `breakdepth` option to change the level of delimiter nesting to which line breaks are allowed. To prohibit line breaks within delimiters, set this to 0:

```
\begin{dmath}[breakdepth={0}]
```

The default value for `breakdepth` is 2. Even when breaks are allowed inside delimiters, they are marked as less desirable than breaks outside delimiters. Most of the time a break will not be taken within delimiters until the alternatives have been exhausted.

Options for the `dgroup` environment: all of the above, and also

```
\begin{dgroup}[noalign]  
\begin{dgroup}[brace]
```

By default the equations in a `dgroup` are mutually aligned on their relation symbols (`=`, `<`, `>`, and the like). With the `noalign` option each equation is placed individually without reference to the others.

The `brace` option means to place a large brace encompassing the whole group on the same side as the equation number.

Options for the `darray` environment: all of the above (where sensible), and also

```
\begin{darray}[cols={lcr@{\hspace{2em}}lcr}]
```

The value of the `cols` option for the `darray` environment should be a series of column specs as for the `array` environment, with the following differences:

- For `l`, `c`, and `r` what you get is not text, but math, and `displaystyle math` at that. To get text you must use a `'p'` column specifier, or put an `\mbox` in each of the individual cells.
- Vertical rules don't connect across lines.

## 11 The flexisym package

The `flexisym` package does some radical changes in the setup for math symbols to allow their definitions to change dynamically throughout a document. The `breqn` package uses this to make symbols of classes 2, 3, 4, 5 run special functions inside an environment such as `dmath` that provide the necessary support for automatic line breaking.

The method used to effect these changes is to change the definitions of `\DeclareMathSymbol` and `\DeclareMathDelimiter`, and then re-execute the standard set of L<sup>A</sup>T<sub>E</sub>X math symbol definitions. Consequently, additional `mathrel` and `mathbin` symbols defined by other packages will get proper line-breaking behavior if the other package is loaded after the `flexisym` package and the symbols are defined through the standard interface.

## 12 Caution! Warning!

Things to keep in mind when writing documents with the `breqn` package:

- The notation  $:=$  must be written with the command `\coloneq`. Otherwise the `:` and the `=` will be treated as two separate relation symbols with an “empty RHS” between them, and they will be printed on separate lines.
- Watch out for constructions like  $\hat{+}$  where a single binary operator or binary relation symbol is subscripted or superscripted. When the `breqn` or `flexisym` package is used, braces are mandatory in such constructions:  $\hat{+}$  becomes `\hat{+}`. This applies for both display and in-line math.
- If you want  $\text{\LaTeX}$  to make intelligent decisions about line breaks when vertical bars are involved, use proper pairing versions of the vertical-bar symbols according to context: `\lvert` `n` `\rvert` instead of `|n|`. With the nondirectional `|` there is no way for  $\text{\LaTeX}$  to reliably deduce which potential breakpoints are inside delimiters (more highly discouraged) and which are not.
- If you use the `german` package or some other package that turns double quote `"` into a special character, you may encounter some problems with named math symbols of type `mathbin`, `mathrel`, `mathopen`, or `mathclose` in moving arguments. For example, `\leq` in a section title will be written to the `.aux` file as something like `\mathchar "3214`. This situation probably ought to be improved, but for now use `\protect`.
- Watch out for the `[` character at the beginning of a `\dmath` or similar environment, if it is supposed to be interpreted as mathematical content rather than the start of the environment’s optional argument.

This is OK:

```
\begin{dmath}
[\lambda,1] \dots
\end{dmath}
```

This will not work as expected:

```
\begin{dmath}[\lambda,1] \dots \end{dmath}
```

- Watch out for unpaired delimiter symbols (in display math only):

```
( ) [ ] \angle \rangle \{ \} \lvert \rvert \dots
```

If an open delimiter is used without a close delimiter, or vice versa, it is normally harmless but may adversely affect line breaking. This is only for symbols that have a natural left or right directionality. Unpaired `\vert` and so on are fine.

When a null delimiter is used as the other member of the pair (`\left.` or `\right.`) this warning doesn't apply.

- If you inadvertently apply `\left` or `\right` to something that is not a delimiter, the error messages are likely to be a bit more confusing than usual. The normal L<sup>A</sup>T<sub>E</sub>X response to an error such as

```
\left +
```

is an immediate message

```
! Missing delimiter (. inserted).
```

When the `breqn` package is in use, L<sup>A</sup>T<sub>E</sub>X will fail to realize anything is wrong until it hits the end of the math formula, or a closing delimiter without a matching opening delimiter, and then the first message is an apparently pointless

```
! Missing \endgroup inserted.
```

## 13 Examples

Knuth, SNA p74

*Example 1*

Replace `$j$` by `$h-j$` and by `$k-j$` in these sums to get [cf.~(26)]

```
\begin{dmath}[label={sna74}]
\frac{1}{6} \left( \sigma(k,h,0) + \frac{3(h-1)}{h} \right) + \frac{1}{6} \left( \sigma(h,k,0) + \frac{3(k-1)}{k} \right)
+ \frac{1}{6} \left( \sigma(h,k,0) + \frac{3(k-1)}{k} \right)
= \frac{1}{6} \left( \frac{h}{k} + \frac{k}{h} + \frac{1}{hk} \right) + \frac{1}{2} - \frac{1}{2h} - \frac{1}{2k},
\end{dmath}
```

which is equivalent to the desired result.

Replace  $j$  by  $h-j$  and by  $k-j$  in these sums to get [cf. (26)]

$$\begin{aligned} & \frac{1}{6} \left( \sigma(k, h, 0) + \frac{3(h-1)}{h} \right) + \frac{1}{6} \left( \sigma(h, k, 0) + \frac{3(k-1)}{k} \right) \\ &= \frac{1}{6} \left( \frac{h}{k} + \frac{k}{h} + \frac{1}{hk} \right) + \frac{1}{2} - \frac{1}{2h} - \frac{1}{2k}, \end{aligned} \tag{13.2}$$

which is equivalent to the desired result.

Knuth, SNA 4.6.2, p387

*Example 2*

```
\newcommand\mx[1]{\begin{math}#1\end{math}}% math expression
%
Now every column which has no circled entry is completely zero;
so when $k=6$ and $k=7$ the algorithm outputs two more vectors,
namely
\begin{dseries}[frame]
\mx{v^{[2]}}=(0,5,5,0,9,5,1,0),
\mx{v^{[3]}}=(0,9,11,9,10,12,0,1).
\end{dseries}
From the form of the matrix $A$ after $k=5$, it is evident that
these vectors satisfy the equation $vA=(0,\dotsc,0)$.
```

math expression

Now every column which has no circled entry is completely zero; so when  $k = 6$  and  $k = 7$  the algorithm outputs two more vectors, namely

$$v^{[2]} = (0, 5, 5, 0, 9, 5, 1, 0), \quad v^{[3]} = (0, 9, 11, 9, 10, 12, 0, 1). \quad (13.3)$$

From the form of the matrix  $A$  after  $k = 5$ , it is evident that these vectors satisfy the equation  $vA = (0, \dots, 0)$ .

*Example 3*

```
\begin{dmath*}
T(n) \hidere{\leq} T(2^{\lceil \lg n \rceil})
\leq c(3^{\lceil \lg n \rceil} - 2^{\lceil \lg n \rceil})
< 3c \cdot 3^{\lg n}
= 3cn^{\lg 3}
\end{dmath*}.
```

$$\begin{aligned} T(n) &\leq T(2^{\lceil \lg n \rceil}) \leq c(3^{\lceil \lg n \rceil} - 2^{\lceil \lg n \rceil}) \\ &< 3c \cdot 3^{\lg n} \\ &= 3cn^{\lg 3}. \end{aligned}$$

*Example 4*

The reduced minimal Gröbner basis for  $I^q_3$  consists of

```
\begin{dgroup*}
\begin{dmath*}
```

```

H_1^3 = x_1 + x_2 + x_3
\end{dmath*},
\begin{dmath*}
H_2^2 = x_1^2 + x_1 x_2 + x_2^2 - q_1 - q_2
\end{dmath*},
\begin{dsuspend}
and
\end{dsuspend}
\begin{dmath*}
H_3^1 = x_1^3 - 2x_1 q_1 - x_2 q_1
\end{dmath*}.
\end{dgroup*}

```

The reduced minimal Gröbner basis for  $I_3^q$  consists of

$$\begin{aligned}
H_1^3 &= x_1 + x_2 + x_3, \\
H_2^2 &= x_1^2 + x_1 x_2 + x_2^2 - q_1 - q_2,
\end{aligned}$$

and

$$H_3^1 = x_1^3 - 2x_1 q_1 - x_2 q_1.$$

## Implementation

The package version here is Michael's v0.90 updated by Bruce Miller. Michael's changes between v0.90 and his last v0.94 will be incorporated where applicable.

The original sources of **breqn** and related files exist in a non-dtx format devised by Michael Downes himself. Lars Madsen has kindly written a Perl script for transforming the original source files into near-perfect dtx state, requiring only very little hand tuning. Without his help it would have been nigh impossible to incorporate the original sources with Michael's comments. A big, big thank you to him.

## 14 Introduction

The **breqn** package provides environments **dmath**, **dseries**, and **dgroup** for displayed equations with *automatic line breaking*, including automatic indention of relation symbols and binary operator symbols at the beginning of broken lines. These environments automatically pull in following punctuation so that it can be written in a natural way. The **breqn** package also provides a **darray** environment similar to the **array** environment but using `\displaystyle` for all the array cells and providing better interline spacing (because the vertical ruling feature of **array** is dropped). These are all autonumbered environments like **equation**

and have starred forms that don't add a number. For a more comprehensive and detailed description of the features and intended usage of the `breqn` package see `breqndoc.tex`.

## 15 Strategy

Features of particular note are the ability to have linebreaks even within a `\left–\right` pair of delimiters, and the automatic alignment on relations and binary operators of a split equation. To make `dmath` handle all this, we begin by setting the body of the equation in a special paragraph form with strategic line breaks whose purpose is not to produce line breaks in the final printed output but rather to mark significant points in the equation and give us entry points for unpacking `\left–\right` boxes. After the initial typesetting, we take the resulting stack of line fragments and, working backward, splice them into a new, single-line paragraph; this will eventually be poured into a custom parshape, after we do some measuring to calculate what that parshape should be. This streamlined horizontal list may contain embedded material from user commands intended to alter line breaks, horizontal alignment, and interline spacing; such material requires special handling.

To make the ‘shortskip’ possibility work even for multiline equations, we must plug in a dummy  $\TeX$  display to give us the value of `\predisplaysize`, and calculate for ourselves when to apply the short skips.

In order to measure the equation body and do various enervating calculations on whether the equation number will fit and so on, we have to set it in a box. Among other things, this means that we can't `\unhbox` it inside `$$...$$`, or even `$...$`:  $\TeX$  doesn't allow you to `\unhbox` in math mode. But we do want to `\hbox` it rather than just call `\box`, otherwise we can't take advantage of available shrink from `\medmuskip` to make equations shrink to fit in the available width. So even for simple one-line equations we are forced to fake a whole display without going through  $\TeX$ 's primitive display mechanism (except for using it to get `\predisplaysize` as mentioned above).

In the case of a framed equation body, the current implementation is to set the frame in a separate box, of width zero and height zero, pinned to the upper left corner of the equation body, and then print the equation body on top of it. For attaching an equation number it would be much simpler to wrap the equation body in the frame and from then on treat the body as a single box instead of multiple line boxes. But I had a notion that it might be possible some day to support vertical stretching of the frame.

## 16 Prelim

This package doesn't work with  $\LaTeX$  2.09, nor with other versions of  $\LaTeX$  earlier than 1994/12/01.

<sup>1</sup> `\*package`

```

2 \NeedsTeXFormat{LaTeX2e}
   Declare package name and date.
3 \ProvidesPackage{breqn}[2008/07/28 v0.98]

```

## 17 Package options

Most options are set with the `\options` command (which calls `\setkeys`) because the standard package option mechanism doesn't provide support for key-value syntax.

First we need to get the catcodes sorted out.

```

4 \edef\breqnpopcats{%
5   \catcode\number'\number\catcode'\
6   \relax}
7 \AtEndOfPackage{\breqnpopcats}%
8 \catcode'\^=7 \catcode'\_ =8 \catcode'\="=12 \relax
9 \DeclareOption{mathstyleoff}{%
10  \PassOptionsToPackage{mathstyleoff}{flexisym}%
11 }

```

Process options.

```

12 \ProcessOptions\relax

```

## 18 Required packages

The `flexisym` package makes it possible to attach extra actions to math symbols, in particular `mathbin`, `mathrel`, `mathopen`, and `mathclose` symbols. Normally it would suffice to call `\RequirePackage` without any extra testing, but the nature of the package is such that it is likely to be called earlier with different (no) options. Then is it really helpful to be always warning the user about 'Incompatible Package Options'? I don't think so.

```

13 \@ifpackageloaded{flexisym}{}%
14   \RequirePackage{flexisym}[2007/12/19]
15   \edef\breqnpopcats{\breqnpopcats
16     \catcode\number'\^=\number\catcode'\^
17     \catcode\number'\_=\number\catcode'\_
18   }%
19   \catcode'\^=7 \catcode'\_ =8 \catcode'\="=12 \relax
20 }

```

The `keyval` package for handling equation options and `calc` to ease writing computations.

```

21 \RequirePackage{keyval,calc}\relax

```

And add an `\options` cmd for processing package options that require an argument. Maybe this will get added to the `keyval` package eventually.

```

22 \@ifundefined{options}{%

```



`\options` Get the package options and run setkeys on them.

```

23 \newcommand{\options}[2]{%
24   \expandafter\options@a\csname opt@#1.sty\endcsname{#2}%
25   \setkeys{#1}{#2}%
26 }

```

`\options@a` Redefine `\opt@pkgname.sty` as we go along to take out the options that are handled and leave the ones that are not.

`\options@b`

`\options@c` 27 `\def\options@a#1#2{%`

`\options@d` 28 `\edef\@tempa{\options@b#2,\@empty\@nil}%`

```

29   \ifx#1\relax \let#1\@empty\fi
30   \xdef#1{#1\ifx#1\@empty\@xp@gobble\@tempa\@empty\else\@tempa \fi}%
31 }

```

Add the next option, and recurse if there remain more options.

```

32 \def\options@b#1,#2#3\@nil{%
33   \options@c#1 \@nil
34   \ifx#2\@empty \else\options@b#2#3\@nil\fi
35 }

```

Discard everything after the first space.

```

36 \def\options@c#1 #2\@nil{\options@d#1=\@nil}

```

Discard everything after the first = sign; add a comma only if the remainder is not empty.

```

37 \def\options@d#1=#2\@nil{\ifx\@empty #1\@empty\else,\fi#1}

```

The tail of the `\@ifundefined` test.

```

38 }{}% end \@ifundefined test

```

## 19 Some useful tools

`\@nx` The comparative brevity of `\@nx` and `\@xp` is valuable not so much for typing convenience as for reducing visual clutter in code sections that require a lot of expansion control.

`\@xp`

```

39 \let\@nx\noexpand
40 \let\@xp\expandafter

```

`\@emptytoks` Constant empty token register, analogous to `\@empty`.

```

41 \@ifundefined{@emptytoks}{\newtoks\@emptytoks}{}

```

`\f@ur` Constants 0–3 are provided in plain T<sub>E</sub>X, but not 4.

```

42 \chardef\f@ur=4

```

`\inf@bad` `\inf@bad` is for testing box badness.

```

43 \newcount\inf@bad \inf@bad=1000000

```

`\maxint` We want to use `\maxint` rather than coerced `\maxdimen` for `\linepenalty` in one place.

```
44 \newcount\maxint \maxint=2147483647
```

`\int@a` Provide some shorter aliases for various scratch registers.

```
\int@b 45 \let\int@a=\@tempcnta
\int@c 46 \let\int@b=\@tempcntb
47 \let\int@c=\count@
```

`\dim@a` Same for `dimen` registers.

```
\dim@b 48 \let\dim@a\@tempdima
\dim@c 49 \let\dim@b\@tempdimb
\dim@d 50 \let\dim@c\@tempdimc
\dim@e 51 \let\dim@d\dimen@
\dim@A 52 \let\dim@e\dimen@ii
53 \let\dim@A\dimen@i
```

`\skip@a` Same for `skip` registers.

```
\skip@b 54 \let\skip@a\@tempskipa
\skip@c 55 \let\skip@b\@tempskipb
56 \let\skip@c\skip@
```

`\toks@a` Same for token registers.

```
\toks@b 57 \let\toks@a\@temptokena
\toks@c 58 \let\toks@b\toks@
\toks@d 59 \toksdef\toks@c=2
\toks@e 60 \toksdef\toks@d=4
\toks@f 61 \toksdef\toks@e=6
62 \toksdef\toks@f=8
```

`\abs@num` We need an absolute value function for comparing penalties.

```
63 \def\abs@num#1{\ifnum#1<\z@-\fi#1}
```

`\@ifnext` The `\@ifnext` function is a variation of `\@ifnextchar` that doesn't skip over intervening whitespace. We use it for the optional arg of `\inside dmath` etc. because we don't want unwary users to be tripped up by an unexpected attempt on L<sup>A</sup>T<sub>E</sub>X's part to interpret a bit of math as an optional arg:

```
\begin{equation}
...\\
[z,w]...
\end{equation}
```

```
.
64 \def\@ifnext#1#2#3{%
65 \let\@tempd= #1\def\@tempa{#2}\def\@tempb{#3}%
66 \futurelet\@tempc\@ifnexta
67 }
```

Switch to `\@tempa` iff the next token matches.

```
68 \def\@ifnexta{\ifx\@tempc\@tempd \let\@tempb\@tempa \fi \@tempb}
```

`\@ifstar` Similarly let's remove space-skipping from `\@ifstar` because in some rare case of `\@inside` an equation, followed by a space and a `*` where the `*` is intended as the math binary operator, it would be a disservice to gobble the star as an option of the `\@ommand`. In all other contexts the chance of having a space *before* the star is extremely small: either the command is a control word which will get no space token after it in any case because of `TeX`'s tokenization rules; or it is a control symbol such as `\\"*` which is exceedingly unlikely to be written as `\\"*` by any one who really wants the `*` to act as a modifier for the `\@ommand`.

```
69 \def\@ifstar#1#2{%
70   \let\@tempd*\def\@tempa*{#1}\def\@tempb{#2}%
71   \futurelet\@tempc\@ifnexta
72 }
```

`\@optarg` Utility function for reading an optional arg *without* skipping over any intervening spaces.

```
73 \def\@optarg#1#2{\@ifnext[#{#1}]{#1[#2]}}
```

`\@True` After `\let\foo\@True` the test

`\@False` `\if\foo`

`\@Not`

`\@And` evaluates to true. Would rather avoid `\newif` because it uses three csnames per Boolean variable; this uses only one.

```
74 \def\@True{00}
75 \def\@False{01}
76 \def\@Not#1{0\ifcase#11 \or\@xp 1\else \@xp 0\fi}
77 \def\@And#1#2{0\ifcase#1#2 \@xp 0\else \@xp 1\fi}
78 \def\@Or#1#2{0\ifnum#1#2<101 \@xp 0\else \@xp 1\fi}

79 \def\theb@@le#1{\if#1 True\else False\fi}
```

`\freeze@glue` Remove the stretch and shrink from a glue register.

```
80 \def\freeze@glue#1{#1#1\relax}
```

`\z@rule` Note well the intentional absence of `\relax` at the end of the replacement text of `\z@rule`; use it with care.

```
81 \def\z@rule{\vrule\@width\z@}% no \relax ! use with care
```

Different ways to keep a bit of glue from disappearing at the beginning of a line after line breaking:

- Zero-thickness rule
- Null character
- `\vadjust{}` (*The TeXbook*, Exercise ??)

The null character idea would be nice except it creates a mathord which then screws up math spacing for e.g., a following unary minus sign. (the *vrule* is transparent to the math spacing). The *vadjust* is the cheapest in terms of box memory—it vanishes after the pass through T<sub>E</sub>X’s paragrapher. It is what I would have used, except that the equation contents get run through two paragraphing passes, once for breaking up LR boxes and once for the real typesetting. If *\keep@glue* were done with an empty *vadjust*, it would disappear after the first pass and—in particular—the pre-bin-op adjustment for relation symbols would disappear at a line break.

```
82 \def\keep@glue{\z@rule\relax}
```

**\replicate** This is a fully expandable way of making N copies of a token list. Based on a post of David Kastrup to comp.text.tex circa January 1999. The extra application of *\number* is needed for maximal robustness in case the repeat count N is given in some weird T<sub>E</sub>X form such as "E9 or \count9.

```
83 % usage: \message{H\replicate{5}{i h}ow de doo dee!}
84 \begingroup \catcode'\&=11
85 \gdef\replicate#1{%
86   \csname &\expandafter\replicate@a\romannumeral\number\number#1 000q\endcsname
87 }
88 \endgroup
```

**\replicate@a**

```
89 \long\def\replicate@a#1#2\endcsname#3{#1\endcsname{#3}#2}
```

**\8m** fix

```
90 \begingroup \catcode'\&=11
91 \long\gdef\&m#1#2{#1\csname &#2\endcsname{#1}}
92 \endgroup
```

**\8q** fix

```
93 \@xp\let\csname\string &q\endcsname\@gobble
```

**\mathchars@reset** Need to patch up this function from flexisym a little, to better handle certain constructed symbols like *\neq*.

```
94 \g@addto@macro\mathchars@reset{%
95   \let\@symRel\@secondoftwo \let\@symBin\@secondoftwo
96   \let\@symDeL\@secondoftwo \let\@symDeR\@secondoftwo
97   \let\@symDeB\@secondoftwo
98 }
```

**\eq@cons** L<sup>A</sup>T<sub>E</sub>X’s *\@cons* appends to the end of a list, but we need a function that adds material at the beginning.

```
99 \def\eq@cons#1#2{%
100   \begingroup \let\@elt\relax \xdef#1{\@elt{#2}#1}\endgroup
101 }
```

`\@saveprimitive` If some preceding package redefined one of the primitives that we must change, we had better do some checking to make sure that we are able to save the primitive meaning for internal use. This is handled by the `\@saveprimitive` function. We follow the example of `\@@input` where the primitive meaning is stored in an internal control sequence with a `@@` prefix. Primitive control sequences can be distinguished by the fact that `\string` and `\meaning` return the same information. Well, not quite all: `\nullfont` and `\topmark` and the other `\...mark` primitives being the exceptions.

```

102 \providecommand{\@saveprimitive}[2]{%
103   \begingroup
104   \edef\@tempa{\string#1}\edef\@tempb{\meaning#1}%
105   \ifx\@tempa\@tempb \global\let#2#1%
106   \else

```

If `[arg1]` is no longer primitive, then we are in trouble unless `[arg2]` was already given the desired primitive meaning somewhere else.

```

107     \edef\@tempb{\meaning#2}%
108     \ifx\@tempa\@tempb
109     \else \@saveprimitive@a#1#2%
110     \fi
111 \fi
112 \endgroup
113 }

```

Aux function, check for the special cases. Most of the time this branch will be skipped so we can stuff a lot of work into it without worrying about speed costs.

```

114 \providecommand\@saveprimitive@a[2]{%
115   \begingroup
116   \def\@tempb##1#1##2{\edef\@tempb{##2}\@car{}}%
117   \@tempb\nullfont{select font nullfont}%
118   \topmark{\string\topmark:}%
119   \firstmark{\string\firstmark:}%
120   \botmark{\string\botmark:}%
121   \splitfirstmark{\string\splitfirstmark:}%
122   \splitbotmark{\string\splitbotmark:}%
123   #1{\string#1}%
124   \edef\@tempa{\expandafter\strip@prefix\meaning\@tempb}%
125   \edef\@tempb{\meaning#1}%
126   \ifx\@tempa\@tempb \global\let#2#1%
127   \else
128     \PackageError{breqn}%
129       {Unable to properly define \string#2; primitive
130       \noexpand#1no longer primitive}\@eha
131   \fi
132 \fi
133 \endgroup
134 }

```

`\@@math` Move the math-start and math-end functions into control sequences. If I were  
`\@@endmath` redesigning T<sub>E</sub>X I guess I'd put these functions into primitive control words instead  
`\@@display`  
`\@@enddisplay`

of linking them to a catcode. That way T<sub>E</sub>X would not have to do the special lookahead at a \$ to see if there's another one coming up. Of course that's related to the question of how to provide user shorthand for common constructions: T<sub>E</sub>X, or an editing interface of some sort.

```

135 \begingroup \catcode'\$=\thr@@ % just to make sure
136 \global\let\@@math=$ \gdef\@@display{$$}% $$$
137 \endgroup
138 \let\@@endmath=\@@math
139 \let\@@enddisplay=\@@display

```

**\@@insert** Save the primitives `\vadjust`, `\insert`, `\mark` because we will want to change them locally during equation measuring to keep them from getting in the way of our vertical decomposition procedures. We follow the example of `\@@input`, `\@@end`, `\@@par` where the primitive meaning is stored in an internal control sequence with a `@@` prefix.

```

140 \@saveprimitive\vadjust\@@vadjust
141 \@saveprimitive\insert\@@insert
142 \@saveprimitive\mark\@@mark

```

## 20 Debugging

Debugging help.

```

143 < *trace >
144 \errorcontextlines=2000\relax

```

**\breqn@debugmsg** Print a debugging message.

```

145 \long\def\breqn@debugmsg#1{\GenericInfo{||}{||}=\space#1}}

```

**\debugwr** Sometimes the newline behavior of `\message` is unsatisfactory; this provides an alternative.

```

146 \def\debugwr#1{\immediate\write\sixt@@n{||}=#1}}

```

**\debug@box** Record the contents of a box in the log file, without stopping.

```

147 \def\debug@box#1{%
148   \batchmode{\showboxbreadth\maxdimen\showboxdepth99\showbox#1}%
149   \errorstopmode
150 }

```

**\eqinfo** Show lots of info about the material before launching into the trials.

```

151 \def\eqinfo{%
152   \debug@box\EQ@copy
153   \wlog{!! EQ@copy: \the\wd\EQ@copy\space x
154     \the\ht\EQ@copy+\the\dp\EQ@copy
155   }%
156 }

```

`\debug@para` Check params that affect line breaking.

```

157 \def\debug@para{%
158   \debugwr{\hsize\the\hsize, \parfillskip\the\parfillskip}%
159   \breqn@debugmsg{\leftskip\the\leftskip, \rightskip\the\rightskip}%
160   \breqn@debugmsg{\linepenalty\the\linepenalty, \adjdemerits\the\adjdemerits}%
161   \breqn@debugmsg{\pretolerance\the\pretolerance, \tolerance\the\tolerance,
162     \parindent\the\parindent}%
163 }
164 </trace>

```

## 21 The `\listwidth` variable

The dimen variable `\listwidth` is `\linewidth` plus `\leftmargin` plus `\rightmargin`, which is typically less than `\hsize` if the list depth is greater than one. In case a future package will provide this variable, define it only if not yet defined.

```

165 \@ifundefined{listwidth}{\newdimen\listwidth}{\}
166 \listwidth=\z@

```

## 22 Parameters

Here follows a list of parameters needed.

<code>\eqfontsize</code>	Note: avoid M, m, P, p because they look like they might be the start of a keyword
<code>\eqcolor</code>	‘minus’ or ‘plus’. Then T <sub>E</sub> X looks further to see if the next letter is i or l. And if
<code>\eqmargin</code>	the next thing is an undefined macro, the attempt to expand the macro results in
<code>\eqindent</code>	an error message.

  

<code>\eqbinoffset</code>	167 <code>\def\eqfontsize{}</code>	% Inherit from context	[NOT USED?]
<code>\eqnumside</code>	168 <code>\def\eqcolor{black}</code>	% Default to black	[NOT USED?]
<code>\eqnumplace</code>	169 <code>\newdimen\eqnumsep \eqnumsep=10pt</code>	% Min space between equ number and body	
<code>\eqnumsep</code>	170 <code>\newdimen\eqmargin \eqmargin=8pt</code>	% For ‘multiline’ gap emulation	

  

The `\eqindent` and `\eqnumside` variables need to have their values initialized from context, actually. But that takes a bit of work, which is postponed till later.

<code>\eqnumfont</code>	171 <code>\def\eqindent{C}%</code>	% C or I, centered or indented
<code>\eqnumsize</code>	172 <code>\def\eqnumside{R}%</code>	% R or L, right or left
<code>\eqnumcolor</code>	173 <code>\def\eqnumplace{M}%</code>	% M or T or B, middle top or bottom

  

Typesetting the equation number is done thus:

```

\eqstyle {\eqnumcolor \eqnumsize \eqnumfont{\eqnumform{\eq@number}}}
\eqinterlinepenalty .
\intereqpenalty
\intereqskip
174 %d\eqnumfont{\upshape}% % Upright even when surrounding text is slanted
175 \def\eqnumfont{}% % Null for easier debugging [mjd,1997/09/26]
176 \def\eqnumform#1{(#1\@@italiccorr)} % Add parens
177 \def\eqnumsize{} % Allow numbers to have different typesize ...

```

Tricky questions on `\eqnumsize`. Should the default be `\normalsize`? Then the user can scale down the equation body with `\small` and not affect the equation number. Or should the default be empty? Then in large sections of smaller text, like the dangerous bend stuff in *T<sub>E</sub>Xbook*, the equation number size will keep in synch with the context. Maybe need an `\eqbodysize` param as well to allow separating the two cases.

```

178 \def\eqnumcolor{}           % ... or color than eq body e.g. \color{blue}
179 \newlength\eqlinespacing \eqlinespacing=14pt plus2pt % Base-to-base space between lines
180 \newlength\eqlineskip \eqlineskip=3pt plus2pt % Min space if eqlinespacing too small
181 \newdimen\eqlineskiplimit \eqlineskiplimit=2pt % Threshold for switching to eqlineskip
The value of \eqbinoffset should include a negative shrink component that
cancels the shrink component of medmuskip, otherwise there can be a noticeable
variation in the indent of adjacent lines if one is shrunk a lot and the other isn't.
182 \newmuskip \eqbinoffset \eqbinoffset=15mu minus-3mu % Offset from mathrel alignment pt for math
183 \newmuskip\eqdelimoffset \eqdelimoffset=2mu % Additional offset for break inside delims
184 \newdimen\eqindentstep \eqindentstep=8pt % Indent used when LHS wd is n/a or too large
185 \newtoks\eqstyle % Customization hook
186 \newcount\eqbreakdepth \eqbreakdepth=2 % Allow breaks within delimiters to this depth
187 \newcount \eqinterlinepenalty \eqinterlinepenalty=10000 % No page breaks between equation lines
188 \newcount \intereqpenalty \intereqpenalty=1000 % Pagebreak penalty between equations [BRM: Wa
189 \newlength \intereqskip \intereqskip=3pt plus2pt % Additional vert space between equations
190 \newcount\prerelpenalty \prerelpenalty=-\@M % Linebreak penalty before mathrel symbols
191 \newcount\prebinoppenalty \prebinoppenalty=888 % Linebreak penalty before mathbins

```

When breaking equations we never right-justify, so a stretch component of the muskip is never helpful and sometimes it is definitely undesirable. Note that thick/medmuskips frozen inside a fraction or radical may turn out noticeably larger than neighboring unfrozen ones. Nonetheless I think this way is the best compromise short of a new T<sub>E</sub>X that can make those built-up objects shrink horizontally in proportion; the alternative is to pretty much eliminate the shrink possibility completely in displays.

```

192 \newmuskip \Dmedmuskip \Dmedmuskip=4mu minus 3mu % medmuskip in displays
193 \newmuskip \Dthickmuskip \Dthickmuskip=5mu minus 2mu % thickmuskip in displays

```

And now some internal variables. 1997/10/22: some of these are dead branches that need to be pruned.

MH: Started cleaning up a bit. No more funny loops.

```

194 \def\eq@number{} % Internal variable
195 \newlength\eqleftskip \eqleftskip=\@centering % Space on the left [NOT USED?]
196 \newlength\eqrightskip \eqrightskip=\@centering % Space on the right [NOT USED?]
197 \newlength\eq@vspan \eq@vspan=\z@skip % Glue used to vcenter the eq number
198 \newmuskip\eq@binoffset \eq@binoffset=\eqbinoffset % Roughly, \eqbinoffset + \eqdelimoffset
199 \newsavebox\EQ@box % Storage for equation body
200 \newsavebox\EQ@copy % For eq body sans vadjust/insert/mark material
201 \newsavebox\EQ@numbox % For equation number
202 \newdimen\eq@wdNum % width of number + separation [NEW]
203 \newsavebox\GRP@numbox % For group number [NEW]
204 \newdimen\grp@wdNum % width of number + separation [NEW]

```



```

205 %%B\EQ@vimbox          % Vadjust, insert, or mark material
206 %%B\EQ@vimcopy        % Spare copy of same
207 %%B\eq@impinging       % Temporary box for measuring number placement
208 \newcount \eq@lines     % Internal counter, actual number of lines
209 \newcount \eq@curline   % Loop counter
210 \newcount \eq@badness    % Used in testing for overfull lines
211 \newcount \EQ@vims      % For bookkeeping
212 \def\@eq@numbertrue{\let\eq@hasNumber\@True}%
213 \def\@eq@numberfalse{\let\eq@hasNumber\@False}%
214 \let\eq@hasNumber\@False

```

Here for the `dimen`s, it would be advisable to do some more careful management to conserve `dimen` registers. First of all, most of the `dimen` registers are needed in the measuring phase, which is a tightly contained step that happens after the contents of the equation have been typeset into a box and before any external functions have a chance to regain control—e.g., the output routine. Therefore it is possible to make use of the the `dimen` registers 0–9, reserved by convention for scratch use, without fear of conflict with other macros. But I don’t want to use them directly with the available names:

```
\dimen@ \dimen@i \dimen@ii \dimen3 \dimen4 ... \dimen9
```

. It would be much more useful to have names for these registers indicative of way they are used.

Another source whence `dimen` registers could be borrowed is the `amsmath` package, which allocates six registers for equation-measuring purposes. We can reuse them under different names since the `amsmath` functions and our functions will never be used simultaneously.

```
\eqnshift@ \alignsep@ \tagshift@ \tagwidth@ \totwidth@ \lineht@
```

```

215 \newdimen\eq@dp          % Depth of last line
216 \newdimen\eq@wdL        % Width of the left-hand-side
217 \newdimen\eq@wdT        % Total width for framing
218 \newdimen\eq@wdMin       % Width of narrowest line in equation
219 \newdimen\grp@wdL        % Max width of LHS’s in a group
220 \newdimen\grp@wdR        % Max RHS of all equations in a group
221 \newdimen\grp@wdT
222 \newdimen\eq@wdRmax
223 \newdimen\eq@firstht     % Height of first line

```

BRM: measure the condition too.

```

224 \newdimen\eq@wdCond
225 \newdimen\eq@indentstep % Indent amount when LHS is not present
226 \newdimen\eq@linewidth % Width actually used for display
227 \newdimen\grp@linewidth % Max eq@linewidth over a group

```

Maybe `\eq@hshift` could share the same register as `\mathindent` [mjd,1997/10/22].

```

228 \newdimen\eq@hshift
229 \let\eq@isIntertext\@False

```

Init `\eq@indentstep` to a nonzero value so that we can detect and refrain from clobbering a user setting of zero. And `\eq@sidespace` to `\maxdimen` because that is the right init before computing a min.

```
230 \eq@indentstep=\maxdimen
231 \newdimen\eq@given@sidespace
```

`\eq@overrun` MH: Appears to be unused.

Not a dimen register; don't need to advance it.

```
232 \def\eq@overrun{0pt}
```

To initialize `\eqnumside` and `\eqindent` properly, we may need to grub around a bit in `\@filelist`. However, if the `amsmath` package was used, we can use its option data. More trouble: if a documentclass sends an option of `leqno` to `amsmath` by default, and it gets overridden by the user with a `reqno` documentclass option, then `amsmath` believes itself to have received *both* options.

```
233 \@ifpackagewith{amsmath}{leqno}{%
234   \@ifpackagewith{amsmath}{reqno}{}{\def\eqnumside{L}}}%
235 }%
```

If the `amsmath` package was not used, the next method for testing the `leqno` option is to see if `leqno.clo` is present in `\@filelist`.

```
236 \def\@tempa#1,leqno.clo,#2#3\@nil{%
237   \ifx @#2\relax\else \def\eqnumside{L}\fi
238 }%
239 \exp\@tempa\@filelist,leqno.clo,\@nil
```

Even that test may fail in the case of `amsart` if it does not load `amsmath`. Then we have to look whether `\iftagsleft@` is defined, and if so whether it is true. This is tricky if you want to be careful about conditional nesting and don't want to put anything in the hash table unnecessarily.

```
240 \if L\eqnumside
241 \else
242   \@ifundefined{iftagsleft@}{}{%
243     \edef\eqnumside{%
244       \if TT\csname fi\endcsname\csname iftagsleft\endcsname
245       L\else R\fi
246     }%
247   }
248 \fi
249 }
```

A similar sequence of tests handles the 'fleqn or not fleqn' question for the `article` and `amsart` documentclasses.

```
250 \@ifpackagewith{amsmath}{fleqn}{%
251   \def\eqindent{I}%
252 }{%
253   \def\@tempa#1,fleqn.clo,#2#3\@nil{%
254     \ifx @#2\relax\else \def\eqindent{I}\fi
255   }%
```

```

256 \exp\@tempa\@filelist,fleqn.clo,\@nil
257 \if I\eqindent
258 \else
259 \ifundefined{if@fleqn}{}%
260 \edef\eqindent{%
261 \if TT\csname fi\endcsname\csname if@fleqn\endcsname
262 I\else C\fi
263 }%
264 }%
265 \fi
266 }

```

BRM: This conditional implies we must use ALL indented or ALL centered?

```

267 %\if I\eqindent
268 \ifundefined{mathindent}{%
269 \newdimen\mathindent
270 }{%
271 \ifundefined{@mathmargin}{}%
272 \mathindent\@mathmargin
273 }%
274 }
275 %\fi

```

## 23 Measuring equation components

Measure the left-hand side of an equation. This function is called by mathrel symbols. For the first mathrel we want to discourage a line break more than for following mathrels; so `\mark@lhs` gobbles the following `\rel@break` and substitutes a higher penalty.

**Maybe the LHS should be kept in a separate box.**

`\EQ@hasLHS` Boolean: does this equation have a “left-hand side”?

```

276 \let\EQ@hasLHS=\@False

```

`\EQ@QED` If nonempty: the qed material that should be incorporated into this equation after the final punctuation.

```

277 \let\EQ@QED=\@empty

```

`\mark@lhs`

```

278 \def\mark@lhs#1{%
279 \ifnum\lr@level<\@ne
280 \let\mark@lhs\relax
281 \global\let\EQ@hasLHS=\@True
282 \global\let\EQ@prebin@space\EQ@prebin@space@a
283 \mark@lhs@a

```

But the penalty for the first mathrel should still be lower than a binoppenalty. If not, when the LHS contains a binop, the split will occur inside the LHS rather than

at the `mathrel`. On the other hand if we end up with a multiline sort of equation layout where the RHS is very short, the break before the relation symbol should be made *less* desirable than the breakpoints inside the LHS. Since a lower penalty takes precedence over a higher one, we start by putting in the highest `relpenalty`; during subsequent measuring if we find that that RHS is not excessively short then we put in an extra “normal” `relpenalty` when rejoining the LHS and RHS.

```

284 \penalty9999 % instead of normal \rel@break
285 % else no penalty = forbid break
286 \fi
287 }

```

`\mark@lhs@a` Temporarily add an extra `thickmuskip` to the LHS; it will be removed later. This is necessary to compensate for the disappearance of the `thickmuskip` glue preceding a `mathrel` if a line break is taken at that point. Otherwise we would have to make our definition of `mathrel` symbols more complicated, like the one for `mathbins`. The penalty of 2 put in with `vadjust` is a flag for `\eq@repack` to suggest that the box containing this line should be measured to find the value of `\eq@wdL`. The second `vadjust` ensures that the normal `prerelpenalty` and `thickmuskip` will not get lost at the line break during this preliminary pass.

BRM: I originally thought the `\mskip\thickmuskip` was messing up summation limits in LHS. But I may have fixed that problem by fixing other things...

```

288 \def\mark@lhs@a{%
289 \mskip\thickmuskip @@vadjust{\penalty\tw@}\penalty-\@Mi\@@vadjust{}}%
290 }

```

`\hiderel` If you want the LHS to extend past the first `mathrel` symbol to a following one, mark the first one with `\hiderel`:

```
a \hiderel{=} b = c...
```

.

I’m not sure now why I didn’t use `\begingroup \endgroup` here

mjd,1999/01/21

.

```

291 \newcommand\hiderel[1]{\mathrel{\advance\lr@level\@ne#1}}

```

`\m@@Bin` cf. `flexisym` handling of `mathbins` and `mathrels`. These are alternate definitions of

`\m@@Rel` `\m@Bin` and `\m@Rel`, activated by `\display@setup`.

```

\bin@break 292 \let\m@@Bin\m@Bin
\rel@break 293 \let\m@@Rel\m@Rel
\bin@mark 294 \let\EQ@prebin@space\relax
\rel@mark 295 \def\EQ@prebin@space@a{\mskip-\eq@binoffset \keep@glue \mskip\eq@binoffset}
\d@@Bin 296 \def\bin@break{\ifnum\lastpenalty=\z@\penalty\prebinoppenalty\fi
\d@@Rel 297 \EQ@prebin@space}
298 \def\rel@break{%
299 \ifnum\abs@num\lastpenalty <\abs@num\prerelpenalty

```

```

300     \penalty\prerelpenalty
301     \fi
302 }
303 \def\d@@Bin{\bin@break \m@@Bin}
304 \def\d@@Rel{\mark@lhs \rel@break \m@@Rel}

```

The difficulty of dealing properly with the subscripts and superscripts sometimes appended to mathbins and mathrels is one of the reasons that we do not attempt to handle the mathrels as a separate ‘column’ a la `eqnarray`.

```

\m@@symRel More of the same.
\d@@symRel 305 \let\m@@symRel\@symRel \def\d@@symRel{\mark@lhs \rel@break \m@@symRel}
\m@@symBin 306 \let\m@@symBin\@symBin \def\d@@symBin{\bin@break \m@@symBin}
\d@@symBin 307 \let\m@@symDel\@symDel
\m@@symDel 308 \let\m@@symDeR\@symDeR
\d@@symDel 309 \let\m@@symDeB\@symDeB
\m@@symDeR 310 \let\m@@symDeA\@symDeA
\d@@symDeR
\display@setup Setup. Note that LATEX reserves the primitive \everydisplay under the name
\m@@symDeB \frozen@everydisplay. BRM: Disable this! It also affects non-breqn math!!!!
\everydisplay \d@@symDeB
\m@@symDeA 311 %\global\everydisplay\expandafter{\the\everydisplay \display@setup}
\d@@symDeA Change some math symbol function calls.
312 \def\display@setup{%
313     \medmuskip\Dmedmuskip \thickmuskip\Dthickmuskip
314     \let\m@Bin\d@@Bin \let\m@Rel\d@@Rel
315     \let\@symRel\d@@symRel \let\@symBin\d@@symBin
316     \let\m@DeL\d@@DeL \let\m@DeR\d@@DeR \let\m@DeB\d@@DeB
317     \let\m@DeA\d@@DeA
318     \let\@symDeL\d@@symDeL \let\@symDeR\d@@symDeR
319     \let\@symDeB\d@@symDeB \let\@symDeA\d@@symDeA
320     \let\left@eq@left \let\right@eq@right \global\lr@level\z@
321     \global\eq@wdCond\z@ %BRM: new

```

If we have an embedded array environment (for example), we don’t want to have each math cell within the array resetting `\lr@level` globally to 0—not good! And in general I think it is safe to say that whenever we have a subordinate level of boxing we want to revert to a normal math setup.

```

322 \everyhbox{\everyhbox\@emptytoks
323     \let\display@setup\relax \textmath@setup \let\textmath@setup\relax
324 }%
325 \everyvbox{\everyvbox\@emptytoks
326     \let\display@setup\relax \textmath@setup \let\textmath@setup\relax
327 }%
328 }

```

The `\textmath@setup` function is needed for embedded inline math inside text inside a display.

BRM: DS Experiment: Variant of `\display@setup` for use within dseries environments

```

329 \def\dseries@display@setup{%
330   \medmuskip\medmuskip \thickmuskip\thickmuskip
331   \let\m@Bin\d@@Bin
332   %\let\m@Rel\d@@Rel
333   % \let\@symRel\d@@symRel
334   \let\@symBin\d@@symBin
335   \let\m@DeL\d@@DeL \let\m@DeR\d@@DeR \let\m@DeB\d@@DeB
336   \let\m@DeA\d@@DeA
337   \let\@symDeL\d@@symDeL \let\@symDeR\d@@symDeR
338   \let\@symDeB\d@@symDeB \let\@symDeA\d@@symDeA
339   \let\left@eq@left \let\right@eq@right \global\lr@level\z@
340   \everyhbox{\everyhbox\@emptytoks
341     \let\display@setup\relax \textmath@setup \let\textmath@setup\relax
342   }%
343   \everyvbox{\everyvbox\@emptytoks
344     \let\display@setup\relax \textmath@setup \let\textmath@setup\relax
345   }%
346 \displaystyle
347 }

348 \def\textmath@setup{%
349   \let\m@Bin\m@@Bin \let\m@Rel\m@@Rel
350   \let\@symRel\m@@symRel \let\@symBin\m@@symBin
351   \let\m@DeL\m@@DeL \let\m@DeR\m@@DeR \let\m@DeB\m@@DeB
352   \let\m@DeA\m@@DeA
353   \let\@symDeL\m@@symDeL \let\@symDeR\m@@symDeR
354   \let\@symDeB\m@@symDeB \let\@symDeA\m@@symDeA
355   \let\left@@@left \let\right@@@right
356 }

```

`\if@display` The test `\ifinner` is unreliable for distinguishing whether we are in a displayed formula or an inline formula: any display more complex than a simple one-line equation typically involves the use of `$ \displaystyle ... $` instead of `$$...$$`. So we provide a more reliable test. But it might have been provided already by the `amsmath` package.

```

357 \ifundefined{displaytrue}{%
358   \exp\newif\csname if@display\endcsname
359   \everydisplay\exp{\the\everydisplay \displaytrue}%
360 }{}

```

Is there any reason to maintain separate `\everydisplay` and `\eqstyle`?

## 24 The `dmath` and `dmath*` environments

Options for the `dmath` and `dmath*` environments.

```

\begin{dmath}[label={eq:xyz}]
\begin{dmath}[labelprefix={eq:},label={xyz}]

```

WSPR: added the option for a label prefix, designed to be used in the preamble like so:

```
\setkeys{breqn}{labelprefix={eq:}}
```

```
361 \define@key{breqn}{label}{%
362   \edef\next@label{\noexpand\label{\next@label@pre#1}}%
363   \let\next@label@pre\empty}
364 \define@key{breqn}{labelprefix}{\def\next@label@pre{#1}}
365 \global\let\next@label\empty
366 \global\let\next@label@pre\empty
```

Allow a variant number.

```
\begin{dmath}[number={\nref{foo}\textprime}]
```

```
367 \define@key{breqn}{number}{\def\eq@number{#1}%
368   \let\@currentlabel\eq@number
369 }
```

```
\begin{dmath}[shiftnumber]
```

```
\begin{dmath}[holdnumber]
```

Holding or shifting the number.

```
370 \define@key{breqn}{shiftnumber}{\let\eq@shiftnumber\@True}
371 \define@key{breqn}{holdnumber}{\let\eq@holdnumber\@True}
```

```
\begin{dmath}[density={.5}]
```

```
372 \define@key{breqn}{density}{\def\eq@density@factor{#1}}
```

```
\begin{dmath}[indentstep={1em}]
```

To change the amount of indent for post-initial lines. Note: for lines that begin with a `mathbin` symbol there is a fixed amount of indent already built in (`\eqbinooffset`) and it cannot be reduced through this option. The `indentstep` amount is the indent used for lines that begin with a `mathrel` symbol.

```
373 \define@key{breqn}{indentstep}{\eqindentstep#1\relax}
```

```
\begin{dmath}[compact]
```

```
\begin{dmath}[compact=-2000]
```

To make `mathrels` stay inline to the extent possible, use the `compact` option. Can give a numeric value in the range  $-10000 \dots 10000$  to adjust the behavior.  $-10000$ : always break at a `rel` symbol;  $10000$ : never break at a `rel` symbol.

```
374 \define@key{breqn}{compact}[-99]{\prerelpenalty=#1\relax}
```

```
\begin{dmath}[layout={S}]%
```

Specify a particular layout. We take care to ensure that `\eq@layout` ends up containing one and only one letter.

```
375 \define@key{breqn}{layout}{?}{%
376   \edef\eq@layout{\@car#1?\@nil}%
377 }
```

`\begin{dmath}[spread={1pt}]`

To change the interline spacing in a particular equation.

```
378 \define@key{breqn}{spread}{%
379   \addtolength\eq@linespacing{#1}%
380   \addtolength\eq@lineskip{#1}%
381   \eq@lineskiplimit\eq@lineskip
382 }
```

To change the amount of space on the side for “multiline” layout.

```
383 \define@key{breqn}{sidespace}{%
384   \setlength\eq@given@sidespace{#1}%
385 }
```

`\begin{dmath}[style={\small}]`

The `style` option is mainly intended for changing the type size of an equation but as a matter of fact you could put arbitrary L<sup>A</sup>T<sub>E</sub>X code here—thus the option name is ‘style’ rather than just ‘typesize’. In order for this option to work when setting options globally, we need to put the code in `\eqstyle` rather than execute it directly.

```
386 \define@key{breqn}{style}{\eqstyle\@xp{\the\eqstyle #1}}
```

`\begin{dmath}[shortskiplimit={1em}]`

If the line immediately preceeding a display has length  $l$ , the first line of the display is indented  $i$ , and a shortskip limit  $s$  is set, then the spacing above the display is equal to `\abovedisplayshortskip` if  $l + s < i$  and `\abovedisplayskip` otherwise. The default shortskip limit is 2em which is what T<sub>E</sub>X hardcodes but this parameter overrides that.

```
387 \define@key{breqn}{shortskiplimit}{\def\eq@shortskiplimit{#1}}
388 \def\eq@shortskiplimit{2em}
```

`\begin{dmath}[frame]`

The `frame` option merely puts a framebox around the body of the equation. To change the thickness of the frame, give the thickness as the argument of the option. For greater control, you can change the appearance of the frame by redefining `\eqframe`. It must be a command taking two arguments, the width and height of the equation body. The top left corner of the box produced by `\eqframe` will be pinned to the top-left corner of the equation body.

```
389 \define@key{breqn}{frame}{\fboxrule}{\def\eq@frame{T}%
390   \dim@a#1\relax\edef\eq@framewd{\the\dim@a}%
```



Until such time as we provide a frame implementation that allows the frame to stretch and shrink, we'd better remove any stretch/shrink from the interline glue in this case.

```

391 \freeze@glue\eqlinespacing \freeze@glue\eqlineskip
392 }
393 \define@key{breqn}{fullframe}[]{\def\eq@frame{U}%
394 \freeze@glue\eqlinespacing \freeze@glue\eqlineskip
395 }
396 \def\eq@frame{F} % no frame
397 \def\eq@framewd{\fboxrule}

```

Wishful thinking?

```
\begin{dmath}[frame={width={2pt},color={blue},sep={2pt}}]
```

To change the space between the frame and the equation there is a framesep option.

```

398 \define@key{breqn}{framesep}[\fboxsep]{%
399 \if\eq@frame F\def\eq@frame{T}\fi
400 \dim@a#1\relax \edef\eq@framesep{\the\dim@a}%
401 \freeze@glue\eqlinespacing \freeze@glue\eqlineskip
402 }
403 \def\eq@framesep{\fboxsep}

```

```
\begin{dmath}[background={red}]
```

Foreground and background colors for the equation. By default the background area that is colored is the size of the equation, plus fboxsep. If you need anything fancier for the background, you'd better do it by defining `\eqframe` in terms of `\colorbox` or `\fcolorbox`.

```

404 \define@key{breqn}{background}{\def\eq@background{#1}%
405 \freeze@glue\eqlinespacing \freeze@glue\eqlineskip
406 }
407 % \end{macrocode}
408 % \begin{literalcode}
409 % \begin{dmath}[color={purple}]
410 % \end{literalcode}
411 % \begin{macrocode}
412 \define@key{breqn}{color}{\def\eq@foreground{#1}}

```

```
\begin{dmath}[center]
\begin{dmath}[nocenter]
```

The `center` option means add leftskip stretch to make the individual lines be centered; this is the default for `dseries`.

```

413 \define@key{breqn}{center}[]{\let\eq@centerlines\@True}
414 \define@key{breqn}{nocenter}[]{\let\eq@centerlines\@False}
415 \let\eq@centerlines\@False

```

```
\begin{dgroup}[noalign]
```

Equation groups normally have alignment of the primary relation symbols across the whole group. The `noalign` option switches that behavior.

```
416 \define@key{breqn}{noalign}[]{\let\grp@aligned\@False}
417 \let\grp@aligned\@True % default
```

```
\begin{dgroup}[breakdepth={2}]
```

Break depth of 2 means that breaks are allowed at mathbin symbols inside two pairs of delimiters, but not three.

```
418 \define@key{breqn}{breakdepth}{\eqbreakdepth#1\relax}
```

```
\begin{darray}[cols={lcr}]{}
```

The `cols` option only makes sense for the `darray` environment but we liberally allow all the options to be used with all the environments and just ignore any unsensible ones that happen to come along.

```
419 \define@key{breqn}{cols}{\global\let\@preamble\@empty
420 \darray@mkpream#1\@percentchar
421 }
```

FORMAT STATUS

```
\def\eq@frame{T}%
CLM works tolerably
\def\eqindent{C}\def\eqnumside{L}\def\eqnumplace{M}
CLT works tolerably
\def\eqindent{C}\def\eqnumside{L}\def\eqnumplace{T}
ILM
\def\eqindent{I}\def\eqnumside{L}\def\eqnumplace{M}\mathindent40\p@
ILT
\def\eqindent{I}\def\eqnumside{L}\def\eqnumplace{T}\mathindent40\p@
Indended w/left number
work ok if mathindent is larger than number width,
but then equations must fit into smaller space.
Is shiftnumber allowed to put eqn at left, instead of indent?
CRM
\def\eqindent{C}\def\eqnumside{R}\def\eqnumplace{M}
CRB
\def\eqindent{C}\def\eqnumside{R}\def\eqnumplace{B}
IRM
\def\eqindent{I}\def\eqnumside{R}\def\eqnumplace{M}\mathindent10\p@
IRB
\def\eqindent{I}\def\eqnumside{R}\def\eqnumplace{B}\mathindent10\p@
```

The main environments.

BRM: The following incorporates several changes: 1) modifications supplied by MJD to fix the eaten `\paragraph` problem. 2) Added `\display@setup` here, rather than globally.

```

\dmath For the dmath environment we don't want the standard optional arg processing
\enddmath because of the way it skips over whitespace, including newline, while looking for
the [ char; which is not good for math material. So we call \@optarg instead.

422 \newenvironment{dmath}{%
423 \let\eq@hasNumber\@True \@optarg@dmath{}}{}
424 \def\@dmath[#1]{%
425 \trace \breqn@debugmsg{=== DMATH =====}%
426 \everydisplay\expandafter{\the\everydisplay \display@setup}%
427 \ifnoskipsec \leavevmode \fi
428 \ifinlabel \leavevmode \global\@inlabelfalse \fi
429 \if\eq@group\else\eq@prelim\fi
430 \setkeys{breqn}{#1}%
431 \the\eqstyle

The equation number might have been overridden in #1.

432 \eq@setnumber

Start up the displayed equation by reading the contents into a box register. Enclose
this phase in an extra group so that modified \hsize and other params will be
auto-restored afterwards.

433 \begingroup
434 \eq@setup@a
435 \eq@startup
436 }

Before it finishes off the box holding the equation body, \enddmath needs to look
ahead for punctuation (and \qed?).

437 \def\enddmath#1{\check@punct@or@qed}
438 \def\end@dmath{%
439 \gdef\EQ@setwdL{}}% Occasionally undefined ???
440 \eq@capture
441 \endgroup
442 \EQ@setwdL

Measure (a copy of) the equation body to find the minimum width required to get
acceptable line breaks, how many lines will be required at that width, and whether
the equation number needs to be shifted to avoid overlapping. This information
will then be used by \eq@finish to do the typesetting of the real equation body.

443 \eq@measure

Piece together the equation from its constituents, recognizing current constraints.
If we are in an equation group, this might just save the material on a stack for
later processing.

444 \if\eq@group \grp@push \else \eq@finish\fi
445 }

\dmath* Ah yes, now the lovely dmath* environment.
\enddmath*
446 \newenvironment{dmath*}{%
447 \let\eq@hasNumber\@False \@optarg@dmath{}}%
448 }{}

```

```

449 \@namedef{enddmath*}{\enddmath}
450 \@namedef{enddmath*}#1{\check@punct@or@qed}

```

`\eq@prelim` If `\everypar` has a non-null value, it's probably some code from `\@afterheading` that sets `\clubpenalty` and/or removes the parindent box. Both of those actions are irrelevant and interfering for our purposes and need to be deflected for the time being. If an equation appears at the very beginning of a list item (possibly from a trivlist such as `proof`), we need to trigger the item label.

```

451 \def\eq@prelim{%
452   \if@inlabel \indent \par \fi
453   \if@nobreak \global\@nobreakfalse \predisplaypenalty\@M \fi
454   \everypar\@emptytoks

```

If for some reason `dmath` is called between paragraphs, `\noindent` is better than `\leavevmode`, which would produce an indent box and an empty line to hold it. If we are in a list environment, `\par` is defined as `{\@@par}` to preserve `\parshape`.

```

455   \noindent
456   \eq@nulldisplay
457   \par %% \eq@saveparinfo %% needs work
458   \let\intertext\breqn@intertext
459 }

```

`\breqn@parshape@warning` Warning message extracted to a separate function to streamline the calling function.

```

460 \def\breqn@parshape@warning{%
461   \PackageWarning{breqn}{%
462     Complex paragraph shape cannot be followed by this equation}%
463 }

```

`\eq@prevshape` Storage; see `\eq@saveparinfo`.

```

464 \let\eq@prevshape\@empty

```

`\eq@saveparinfo` Save the number of lines and parshape info for the text preceding the equation.

```

465 \def\eq@saveparinfo{%
466   \count@\prevgraf \advance\count@-\thr@@ % for the null display
467   \edef\eq@prevshape{\prevgraf\the\count@\space}%
468   \ifcase\parshape
469     % case 0: no action required
470   \or \edef\eq@prevshape{\eq@prevshape
471     \parshape\@ne\displayindent\displaywidth\relax
472   }%

```

Maybe best to set `\eq@prevshape` the same in the else case also. Better than nothing.

```

473   \else
474     \breqn@parshape@warning
475   \fi
476 }

```

`\eq@setnumber` If the current equation number is not explicitly given, then use an auto-generated number, unless the no-number switch has been thrown (`\dmath*`). `\theequation` is the number form to be used for all equations, `\eq@number` is the actual value for the current equation (might be an exception to the usual sequence).

```

477 \def\eq@setnumber{%
478   \eq@wdNum\z@
479   \if\eq@hasNumber
480     \ifx\eq@number\@empty
481       \stepcounter{equation}\let\eq@number\theequation
482     \fi
483   % \fi

```

This sets up numbox, etc, even if unnumbered????

```

484     \ifx\eq@number\@empty
485     \else

```

Put the number in a box so we can use its measurements in our number-placement calculations. The extra braces around `\eqnumform` make it possible for `\eqnumfont` to have either an `\itshape` (recommended) or a `\textit` value.

```

486 <trace>      \breqn@debugmsg{Number \eq@number}%
487             \set@label{equation}\eq@number
488             \global\sbox\EQ@numbox{%
489               \next@label \global\let\next@label\@empty
490               \eqnumcolor\eqnumsize\eqnumfont{\eqnumform{\eq@number}}%
491             }%
492             \global\eq@wdNum\wd\EQ@numbox\global\advance\eq@wdNum\eqnumsep
493 %           \let\eq@hasNumber\@True % locally true
494           \fi
495         \fi
496       }

```

`\eq@finish` The information available at this point from preliminary measuring includes the number of lines required, the width of the equation number, the total height of the equation body, and (most important) the parshape spec that was used in determining height and number of lines.

Invoke the equation formatter for the requested centering/indentation having worked out the best parshape. BRM: This portion is extensively refactored to get common operations together (so corrections get consistently applied).

MH: I've destroyed Bruce's nice refactoring a bit to get the `\abovedisplayskip` correct for both groups of equations and single `\dmath` environments. I will have to redo that later.

```

497 \newcount\eq@final@linecount
498 \let\eq@GRP@first@dmath\@True
499 \def\eq@finish{%
500   \begingroup
501 <trace>      \breqn@debugmsg{Formatting equation}%
502 <trace>      \debug@showmeasurements
503             \if F\eq@frame\else
504             \freeze@glue\eqlinespacing \freeze@glue\eqlineskip

```

```

505 \fi
506 % \eq@topspace{\vskip\parskip}% Set top spacing
507 \csname eq@eqindent @setsides\endcsname % Compute \leftskip,\rightskip
508 \adjust@parshape\eq@parshape% Final adjustment of parshape for left|right skips

```

If we are in an a group of equations we don't want to calculate the top space for the first one as that will be delayed until later when the space for the group is calculated. However, we do need to store the leftskip used here as that will be used later on for calculating the top space.

```

509 \if\eq@group
510 \if\eq@GRP@first@dmath
511 \global\let\eq@GRP@first@dmath\@False
512 \xdef\dmath@first@leftskip{\leftskip=\the\leftskip\relax}%
513 <trace> \breqn@debugmsg{Stored\space\dmath@first@leftskip}
514 \else
515 \eq@topspace{\vskip\parskip}% Set top spacing
516 \fi
517 \else
518 \eq@topspace{\vskip\parskip}% Set top spacing
519 \fi
520 <trace> \debug@showformat

```

We now know the final line count of the display. If it is a single-line display, we want to know as that greatly simplifies the equation tag placement (until such a time where this algorithm has been straightened out).

```

521 \afterassignment\remove@to@nnil
522 \eq@final@linecount=\expandafter\@gobble\eq@parshape\@nnil

```

Now, invoke the appropriate typesetter according to number placement

```

523 \if\eq@hasNumber
524 \if\eq@shiftnumber
525 \csname eq@typeset@eqnumside Shifted\endcsname
526 \else

```

If there is only one line and the tag doesn't have to be shifted, we call a special procedure to put the tag correctly.

```

527 \ifnum\eq@final@linecount=\@ne
528 \csname eq@typeset@eqnumside @single\endcsname
529 \else
530 \csname eq@typeset@eqnumside\eqnumplace\endcsname
531 \fi
532 \fi
533 \else
534 \eq@typeset@Unnumbered
535 \fi
536 \endgroup
537 \eq@botSPACE
538 }

```

These are temporary until the tag position algorithm gets rewritten. At least the tag is positioned correctly for single-line displays. The horizontal frame posi-

tion is not correct but the problem lies elsewhere.

```

539 \def\eq@typeset@L@single{%
540   \nobreak
541   \eq@params\eq@parshape
542   \nointerlineskip\noindent
543   \add@grp@label
544   \rlap{\kern-\leftskip\box\EQ@numbox}%
545   \if F\eq@frame
546   \else
547     \rlap{\raise\eq@firstht\hbox to\z@{\eq@addframe\hss}}%
548   \fi
549   \eq@dump@box\unhbox\EQ@box \@@par
550 }
551 \def\eq@typeset@R@single{%
552   \nobreak
553   \eq@params\eq@parshape
554   \nointerlineskip\noindent
555   \add@grp@label
556   \if F\eq@frame
557   \else
558     \rlap{\raise\eq@firstht\hbox to\z@{\eq@addframe\hss}}%
559   \fi
560   \rlap{\kern-\leftskip\kern\linewidth\kern-\wd\EQ@numbox\copy\EQ@numbox}%
561   \eq@dump@box\unhbox\EQ@box
562   \@@par
563 }

```

## 25 Special processing for end-of-equation

At the end of a displayed equation environment we need to peek ahead for two things: following punctuation such as period or command that should be pulled in for inclusion at the end of the equation; and possibly also an `\end{proof}` with an implied “qed” symbol that is traditionally included at the end of the display rather than typeset on a separate line. We could require that the users type `\qed` explicitly at the end of the display when they want to have the display take notice of it. But the reason for doing that would only be to save work for the programmer; the most natural document markup would allow an inline equation and a displayed equation at the end of a proof to differ only in the environment name:

```

... \begin{math} ... \end{math}.
\end{proof}

```

versus

```

...
\begin{dmath}
...
\end{dmath}.

```

`\end{proof}`

. The technical difficulties involved in supporting this markup within L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> are, admittedly, nontrivial. Nonetheless, let’s see how far we can go.

The variations that we will support are only the most straightforward ones:

`\end{dmath}.`  
`\end{proof}`

or

`\end{dmath}.`  
`Perhaps a comment`  
`\end{proof}`

. If there is anything more complicated than a space after the period we will not attempt to scan any further for a possible `\end{proof}`. This includes material such as:

`\begin{figure}...\end{figure}%`  
`\footnote{...}`  
`\renewcommand{\foo}{...}`  
`\par`

or even a blank line—because in L<sup>A</sup>T<sub>E</sub>X a blank line is equivalent to `\par` and the meaning of `\par` is “end-paragraph”; in my opinion if explicit end-of-paragraph markup is given before the end of an element, it has to be respected, and the preceding paragraph has to be fully finished off before proceeding further, even inside an element like “proof” whose end-element formatting requires integration with the end of the paragraph text. And T<sub>E</sub>X nically speaking, a `\par` token that comes from a blank line and one that comes from the sequence of characters `\p a r` are equally explicit. I hope to add support for `\footnote` in the future, as it seems to be a legitimate markup possibility in that context from a purely logical point of view, but there are additional technical complications if one wants to handle it in full generality

mjd,1999/02/08

.

`\peek@branch` This is a generalized “look at next token and choose some action based on it” function.

```
564 \def\peek@branch#1#2{%
565   \let\peek@b#1\let\peek@space#2\futurelet\@let@token\peek@a
566 }
567 \def\peek@skipping@spaces#1{\peek@branch#1\peek@skip@space}
568 \def\peek@a{%
569   \ifx\@let@token\@sptoken \expandafter\peek@space
570   \else \expandafter\peek@b\fi
571 }
572 \lowercase{\def\peek@skip@space} {\futurelet\@let@token\peek@a}%
```



`\check@punct` For this one we need to recognize and grab for inclusion any of the following tokens: `,;.!?`, both catcode 12 (standard L<sup>A</sup>T<sub>E</sub>X value) and catcode 13 (as might hold when the Babel package is being used). We do not support a space preceding the punctuation since that would be considered simply invalid markup if a display-math environment were demoted to in-line math; and we want to keep their markup as parallel as possible. If punctuation does not follow, then the `\check@qed` branch is not applicable.

```

573 \def\check@punct{\futurelet\@let@token\check@punct@a}
574 \def\check@punct@a{%
575   \edef\@tempa{%
576     \ifx\@let@token\@sptoken\@nx\finish@end
577     \else\ifx\@let@token ,\@nx\check@qed
578     \else\ifx\@let@token .\@nx\check@qed
579     \else\check@punct@b % check the less common possibilities
580     \fi\fi\fi
581   }%
582   \@tempa
583 }
584 \begingroup
585 \toks@a{%
586   \ifx\@let@token ;\@nx\check@qed
587   \else\ifx\@let@token ?\@nx\check@qed
588   \else\ifx\@let@token !\@nx\check@qed
589   }
590 \toks@c{\fi\fi\fi}% matching with \toks@a
591 \catcode'\.=\active \catcode'\,=\active \catcode'\;=\active
592 \catcode'\?=\active \catcode'\!=\active
593 \toks@b{%
594   \else\ifx\@let@token ,\@nx\check@qed
595   \else\ifx\@let@token .\@nx\check@qed
596   \else\ifx\@let@token ;\@nx\check@qed
597   \else\ifx\@let@token ?\@nx\check@qed
598   \else\ifx\@let@token !\@nx\check@qed
599   \else\@nx\finish@end
600   \fi\fi\fi\fi\fi
601 }
602 \xdef\check@punct@b{%
603   \the\toks@a\the\toks@b\the\toks@c
604 }
605 \endgroup
606 \let\found@punct\@empty
607 \def\check@qed#1{%
608   \gdef\found@punct{#1}%
609   \peek@skipping@spaces\check@qed@a
610 }
611 \def\check@qed@a{%
612   \ifx\end\@let@token \@xp\check@qed@b
613   \else \@xp\finish@end
614   \fi

```

615 }

For each environment ENV that takes an implied qed at the end, the control sequence ENVqed must be defined; and it must include suitable code to yield the desired results in a displayed equation.

```
616 \def\check@qed@b#1#2{%
617   \ifundefined{#2qed}{}%
618   \toks@\xp{\found@punct\csname#2qed\endcsname}%
619   \xdef\found@punct{\the\toks@}%
620 }%
621 \finish@end
622 \end{#2}%
623 }
```

`\latex@end` The lookahead for punctuation following a display requires mucking about with  
`\finish@end` the normal operation of `\end`. Although this is not exactly something to be done lightly, on the other hand this whole package is so over-the-top anyway, what's a little more going to hurt? And rationalizing this aspect of equation markup is a worthy cause. Here is the usual definition of `\end`.

```
\def\end#1{
  \csname end#1\endcsname \@checkend{#1}%
  \expandafter\endgroup\if@endpe\@doendpe\fi
  \if@ignore \global\@ignorefalse \ignorespaces \fi
}
```

We can improve the chances of this code surviving through future minor changes in the fundamental definition of `\end` by taking a little care in saving the original meaning.

```
624 \def\@tempa#1\endcsname#2\@nil{\def\latex@end##1{#2}}
625 \expandafter\@tempa\end{#1}\@nil
626 \def\end#1{\csname end#1\endcsname \latex@end{#1}}%
```

Why don't we call `\CheckCommand` here? Because that doesn't help end users much; it works better to use it during package testing by the maintainer.

If a particular environment needs to call a different end action, the end command of the environment should be defined to gobble two args and then call a function like `\check@punct@or@qed`.

```
627 \def\check@punct@or@qed#1{%
628   \xdef\found@punct{\@empty}% BRM: punctuation was being remembered past this eqn.
629   % WSPR: err, why isn't that just \global\let\found@punct\@empty ?
630   \def\finish@end{\csname end#1\endcsname\latex@end{#1}}%
631   \check@punct
632 }
```

`\eqpunct` User-settable function for handling the punctuation at the end of an equation. You could, for example, define it to just discard the punctuation.

```
633 \newcommand\eqpunct[1]{\thinspace#1}
```

`\set@label` `\set@label` just sets `\@currentlabel` but it takes the counter as an argument, in the hope that L<sup>A</sup>T<sub>E</sub>X will some day provide an improved labeling system that includes type info on the labels.

```
634 \providecommand\set@label[2]{\protected@edef\@currentlabel{#2}}
```

`\eq@topspace` The action of `\eq@topspace` is complicated by the need to test whether the ‘short’ versions of the display skips should be used. This can be done only after the final parshape and indent have been determined, so the calls of this function are buried relatively deeply in the code by comparison to the calls of `\eq@botsspace`. This also allows us to optimize slightly by setting the above-skip with `\parskip` instead of `\vskip`. #1 is either `\noindent` or `\vskip\parskip`.

BRM: Hmm; we need to do `*@setsspace` BEFORE this for small skips to work!

```
635 \def\eq@topspace#1{%
```

```
636   \begingroup
```

```
637   \global\let\EQ@shortskips\@False
```

If we are in `dgroup` or `dgroup*` and not before the top one, we just insert `\intereqskip`. Otherwise we must check for shortskip.

```
638   \if@And{\eq@group}{\@Not\eq@GRP@first@dmath}%
```

```
639   <trace>\breqn@debugmsg{Between lines}%
```

```
640       \parskip\intereqskip \penalty\intereqpenalty
```

```
641   <trace>\breqn@debugmsg{parskip=\the\parskip}%
```

```
642   \else
```

```
643     \eq@check@shortskip
```

```
644     \if\EQ@shortskips
```

```
645       \parskip\abovedisplayshortskip
```

```
646       \aftergroup\belowdisplayskip\aftergroup\belowdisplayshortskip
```

BRM: Not exactly T<sub>E</sub>X’s approach, but seems right...

```
647       \ifdim\predisplaysize>\z@\nointerlineskip\fi
```

```
648     \else
```

```
649       \parskip\abovedisplayskip
```

```
650     \fi
```

```
651   \fi
```

```
652   \if F\eq@frame
```

```
653   \else
```

```
654     \addtolength\parskip{\eq@framesep+\eq@framewd}%
```

```
655   \fi
```

```
656   <*trace>
```

```
657     \breqn@debugmsg{Topsspace: \theb@le\EQ@shortskips, \parskip=\the\parskip,
```

```
658     \predisplaysize=\the\predisplaysize}%
```

```
659   </trace>
```

```
660   #1%
```

```
661   \endgroup
```

```
662 }
```

`\eq@check@shortskip`

```
663 \def\eq@check@shortskip {%
```

```
664   \global\let\EQ@shortskips\@False
```

```
665   \setlength\dim@a{\abovedisplayskip+\ht\EQ@numbox}%
```

Here we work around the hardwired standard TeX value and use the designer parameter instead.

```
666 \ifdim\leftskip<\predisplaysize
667 \else
```

If the display was preceded by a blank line, `\predisplaysize` is `-\maxdimen` and so we should insert a fairly large skip to separate paragraphs, i.e., no short skip. Perhaps this should be a third parameter `\abovedisplayparskip`.

```
668 \ifdim -\maxdimen=\predisplaysize
669 \else
670 \if R\eqnumside
671 \global\let\EQ@shortskips\@True
672 \else
673 \if\eq@shiftnumber
674 \else
675 \if T\eqnumplace
676 \ifdim\dim@a<\eq@firstht
677 \global\let\EQ@shortskips\@True
678 \fi
679 \else
680 \setlength\dim@b{\eq@vspan/2}%
681 \ifdim\dim@a<\dim@b
682 \global\let\EQ@shortskips\@True
683 \fi
684 \fi
685 \fi
686 \fi
687 \fi
688 \fi
689 }
```

At the end of an equation, need to put in a pagebreak penalty and some vertical space. Also set some flags to remove parindent and extra word space if the current paragraph text continues without an intervening `\par`.

```
690 \def\eq@botSPACE{%
691 \penalty\postdisplaypenalty
```

Earlier calculations will have set `\belowdisplayskip` locally to `\belowdisplayshortskip` if applicable. So we can just use it here.

```
692 \if F\eq@frame
693 \else
694 \addtolength\belowdisplayskip{\eq@framesep+\eq@framewd}%
695 \fi
696 \vskip\belowdisplayskip
697 \@endpetrue % kill parindent if current paragraph continues
698 \global\@ignoretrue % ignore following spaces
699 \eq@resume@parshape
700 }
```

`\eq@resume@parshape` This should calculate the total height of the equation, including space above and below, and set `prevgraf` to the number it would be if that height were taken up by normally-spaced normal-height lines. We also need to restore `parshape` if it had a non-null value before the equation. Not implemented yet.

```
701 \def\eq@resume@parshape{}
```

## 26 Preprocessing the equation body

`\eq@startup` Here is the function that initially collects the equation material in a box.

```
702 \def\eq@startup{%
703   \global\let\EQ@hasLHS\@False
704   \setbox\z@\vbox\bgroup
705     \noindent \@@math \displaystyle
706     \penalty-\@Mi
707 }
```

This setup defines the environment for the first typesetting pass, note the `\hsize` value for example.

```
708 \def\eq@setup@a{%
709   \everymath\everydisplay
710   %\let\@newline\eq@newline % future possibility?
711   \let\\\eq@newline
712   \let\insert\eq@insert \let\mark\eq@mark \let\vadjust\eq@vadjust
713   \hsize\maxdimen \pretolerance\@M
```

Here it is better not to use `\@flushglue` (0pt plus1fil) for `\rightskip`, or else a negative penalty (such as `-99` for `\prerelpenalty`) will tempt  $\TeX$  to use more line breaks than necessary in the first typesetting pass. Ideal values for `\rightskip` and `\linepenalty` are unclear to me, but they are rather sensitively interdependent. Choice of 10000 pt for `\rightskip` is derived by saying, let's use a value smaller than 1 fil and smaller than `\hsize`, but more than half of `\hsize` so that if a line is nearly empty, the glue stretch factor will always be less than 2.0 and so the badness will be less than 100 and so  $\TeX$  will not issue badness warnings.

```
714 \linepenalty\@m
715 \rightskip\z@\@plus\@M\p@ \leftskip\z@skip \parfillskip\z@skip
716 \clubpenalty\@ne \widowpenalty\z@ \interlinepenalty\z@
```

After a relation symbol is discovered, binop symbols should start including a special offset space. But until then `\EQ@prebin@space` is a no-op.

```
717 \global\let\EQ@prebin@space\relax
```

Set `binoppenalty` and `relpenalty` high to prohibit line breaks after mathbins and mathrels. As a matter of fact, the penalties are then omitted by  $\TeX$ , since bare glue without a penalty is *not* a valid breakpoint if it occurs within `mathon-mathoff` items.

```
718 \binoppenalty\@M \relpenalty\@M
719 }
```

The contents of an equation after the initial typesetting pass, as shown by `\showlists`. This is the material on which the `\eq@repack` function operates.

The equation was

$$a=b +\left(\frac{c\sqrt{2}}{2} -d\right) +(e -f) +g$$

. The contents are shown in four parts in this figure and the next three. The first part contains two line boxes, one for the mathon node and one for the LHS.

```
\hbox(0.0+0.0)x16383.99998, glue set 1.6384
.\mathon
.\penalty -10000
.\glue(\rightskip) 0.0 plus 10000.0
\penalty 1
\glue(\baselineskip) 7.69446
\hbox(4.30554+0.0)x16383.99998, glue set 1.63759
.\OML/cmm/m/it/10 a
.\glue 2.77771 minus 1.11108
.\penalty -10001
.\glue(\rightskip) 0.0 plus 10000.0
\penalty 2
\glue(\lineskip) 1.0
...
```

Figure 1: Preliminary equation contents, part 1

This is the first part of the RHS, up to the `\right`, where a line break has been forced so that we can break open the left-right box.

```

...
\penalty 2
\glue(\lineskip) 1.0
\hbox(14.9051+9.50012)x16383.99998, glue set 1.63107
.\penalty -99
.\glue(\thickmuskip) 2.77771 minus 1.11108
.\OT1/cmr/m/n/10 =
.\glue(\thickmuskip) 2.77771 minus 1.11108
.\OML/cmm/m/it/10 b
.\penalty 888
.\glue -10.5553
.\rule{**}x0.0
.\penalty 10000
.\glue 10.5553
.\glue(\medmuskip) 2.22217 minus 1.66663
.\OT1/cmr/m/n/10 +
.\glue(\medmuskip) 2.22217 minus 1.66663
.\hbox(14.9051+9.50012)x43.36298
..\hbox(0.39998+23.60025)x7.36115, shifted -14.10013
...\OMX/cmex/m/n/5 \hat \hat R
..\hbox(14.9051+6.85951)x11.21368
...\hbox(14.9051+6.85951)x11.21368
... [fraction contents, elided]
..\penalty 5332
..\glue -10.5553
..\rule{**}x0.0
..\penalty 10000
..\glue 10.5553
..\glue(\medmuskip) 2.22217 minus 1.66663
..\OMS/cmsy/m/n/10 \hat \hat @
..\glue(\medmuskip) 2.22217 minus 1.66663
..\OML/cmm/m/it/10 d
..\hbox(0.39998+23.60025)x7.36115, shifted -14.10013
...\OMX/cmex/m/n/5 \hat \hat S
.\penalty -10000
.\glue(\rightskip) 0.0 plus 10000.0
\penalty 3
\glue(\lineskip) 1.0
...

```

Figure 2: Preliminary equation contents, part 2

This is the remainder of the RHS after the post-\right split.

```

...
\penalty 3
\glue(\lineskip) 1.0
\hbox(7.5+2.5)x16383.99998, glue set 1.63239
.\penalty 888
.\glue -10.5553
.\rule{**}x0.0
.\penalty 10000
.\glue 10.5553
.\glue(\medmuskip) 2.22217 minus 1.66663
.\OT1/cmr/m/n/10 +
.\glue(\medmuskip) 2.22217 minus 1.66663
.\OT1/cmr/m/n/10 (
.\OML/cmm/m/it/10 e
.\penalty 5332
.\glue -10.5553
.\rule{**}x0.0
.\penalty 10000
.\glue 10.5553
.\glue(\medmuskip) 2.22217 minus 1.66663
.\OMS/cmsy/m/n/10 \hat \hat @
.\glue(\medmuskip) 2.22217 minus 1.66663
.\OML/cmm/m/it/10 f
.\kern1.0764
.\OT1/cmr/m/n/10 )
.\penalty 888
.\glue -10.5553
.\rule{**}x0.0
.\penalty 10000
.\glue 10.5553
.\glue(\medmuskip) 2.22217 minus 1.66663
.\OT1/cmr/m/n/10 +
.\glue(\medmuskip) 2.22217 minus 1.66663
.\OML/cmm/m/it/10 g
.\kern0.35878
.\penalty -10000
.\glue(\rightskip) 0.0 plus 10000.0
\glue(\baselineskip) 9.5
...

```

Figure 3: Preliminary equation contents, part 3



This is the mathoff fragment.

```
...
\glue(\baselineskip) 9.5
\hbox(0.0+0.0)x16383.99998, glue set 1.6384
.\mathoff
.\penalty 10000
.\glue(\parfillskip) 0.0
.\glue(\rightskip) 0.0 plus 10000.0
```

Figure 4: Preliminary equation contents, part 4

`\eq@capture` If an equation ends with a `\right` delim, the last thing on the math list will  
`\eq@punct` be a force-break penalty. Then don't redundantly add another forcing penalty.  
 (question: when does a penalty after a linebreak not disappear? Answer: when  
 you have two forced break penalties in a row). Ending punctuation, if any, goes  
 into the last box with the mathoff kern. If the math list ends with a slanted letter,  
 then there will be an italic correction added after it by `TEX`. Should we remove  
 it? I guess so.

## 26.1 Capturing the equation

BRM: There's a problem here (or with `\ss@scan`). If the LHS has `\left`  
`\right` pairs, `\ss@scan` gets involved. It seems to produce a separate box marked  
`w/\penalty 3`. But it appears that `\eq@repack` is only expecting a single box for  
 the LHS; when it measures that box it's missing the (typically larger) bracketed  
 section, so the LHS is measured =, 0pt (or very small). I'm not entirely clear  
 what Michael had in mind for this case; whether it's an oversight, or whether  
 I've introduced some other bug. At any rate, my solution is to measure the RHS  
 (accumulated in `\EQ@box`), at the time of the relation, and subtract that from the  
 total size.

```
720 \newdimen\eq@wdR\eq@wdR\z@%BRM
721 \def\eq@capture{%
722   \ifnum\lastpenalty>-\@M \penalty-\@Mi \fi
```

We want to keep the mathoff kern from vanishing at the line break, so that we  
 can reuse it later.

```
723 \keep@glue\@@endmath
724 \eq@addpunct
725 \@@par
726 \eq@wdL\z@
```

First snip the last box, which contains the mathoff node, and put it into `\EQ@box`.  
 Then when we call `\eq@repack` it will recurse properly.

```
727 \setbox\tw@\lastbox
728 \global\setbox\EQ@box\hbox{\unhbox\tw@\unskip\unskip\unpenalty}%
729 \unskip\unpenalty
```

```

730 \global\setbox\EQ@copy\copy\EQ@box
731 %% \global\setbox\EQ@vimcopy\copy\EQ@vimbox
732 \clubpenalty\z@
733 %\batchmode\showboxbreadth\maxdimen\showboxdepth99\showlists\errorstopmode
734 \eq@wdR\z@%BRM: eq@wdL patch
735 \eq@repack % recursive

```

Finally, add the mathon item to \EQ@box and \EQ@copy.

```

736 \setbox\tw@lastbox
737 \global\setbox\EQ@box\hbox{\unhcopy\tw@\unskip\unpenalty \unhbox\EQ@box}%
738 \global\setbox\EQ@copy\hbox{\unhbox\tw@\unskip\unpenalty \unhbox\EQ@copy}%
739 %\batchmode\showbox\EQ@copy \showthe\eq@wdL\errorstopmode
740 \ifdim\eq@wdR>\z@% BRM: eq@wdL patch
741 \setlength\dim@a{\wd\EQ@box-\eq@wdR
742 % Apparently missing a \thickmuskip = 5mu = 5/18em=0.277777777777.. ?
743 + 0.27777777777777em}% FUDGE??!?!?!
744 \ifdim\dim@a>\eq@wdL
745 {*trace}
746 \breqn@debugmsg{Correcting LHS from \the\eq@wdL\space to
747 \the\dim@a = \the\wd\EQ@box - \the\eq@wdR}%
748 {/trace}
749 \eq@wdL\dim@a
750 \xdef\EQ@setwdL{\eq@wdL\the\eq@wdL\relax}%
751 \fi
752 \fi
753 {*trace}
754 \breqn@debugmsg{Capture: total length=\the\wd\EQ@box \MessageBreak
755 ==== has LHS=\theb@le\EQ@hasLHS, \eq@wdL=\the\eq@wdL, \eq@wdR=\the\eq@wdR,
756 \MessageBreak
757 ==== \eq@wdCond=\the\eq@wdCond}%
758 {/trace}
759 \egroup % end vbox started earlier
760 {*trace}
761 %\debugwr{EQ@box}\debug@box\EQ@box
762 %\debugwr{EQ@copy}\debug@box\EQ@copy
763 {/trace}
764 }

```

Now we have two copies of the equation, one in \EQ@box, and one in \EQ@copy with inconvenient stuff like inserts and marks omitted.

\eq@addpunct is for tacking on text punctuation at the end of a display, if any was captured by the ‘gp’ lookahead.

```

765 \def\eq@addpunct{%
766 \ifx\found@punct\@empty
767 \else \eqpunct{\found@punct}%
768 \fi
769 % BRM: Added; the punctuation kept getting carried to following enviros
770 \xdef\found@punct{\@empty}%
771 \EQ@afterspace
772 }

```

Needed for the `dseries` environment, among other things.

```
773 \global\let\EQ@afterspace\@empty
```

`\eq@repack` The `\eq@repack` function looks at the information at hand and proceeds accordingly.

TeX Note: this scans BACKWARDS from the end of the math.

```
774 \def\eq@repack{%
775 % A previous penalty of 3 on the vertical list means that we need
776 % to break open a left-right box.
777 % \begin{macrocode}
778 \ifcase\lastpenalty
779 % case 0: normal case
780 \setbox\tw@\lastbox
781 \eq@repacka\EQ@copy \eq@repacka\EQ@box
782 \unskip
783 \or % case 1: finished recursing
```

Grab the mathon object since we need it to inhibit line breaking at bare glue nodes later.

```
784 \unpenalty
785 \setbox\tw@\lastbox
786 \eq@repacka\EQ@copy \eq@repacka\EQ@box
787 \@xp\@gobble
788 \or % case 2: save box width = LHS width
```

Don't need to set `\EQ@hasLHS` here because it was set earlier if applicable.

```
789 \unpenalty
790 \setbox\tw@\lastbox
791 \setbox\z@\copy\tw@ \setbox\z@\hbox{\unhbox\z@\unskip\unpenalty}%
792 \addtolength\eq@wdL{\wd\z@}
793 \setlength\eq@wdR{\wd\EQ@box}% BRM: eq@wdL patch
794 \xdef\EQ@setwdL{\eq@wdL\the\eq@wdL\relax}%
```

At this point, box 2 typically ends with

```
.\mi10 a
.\glue 2.77771 plus 2.77771
.\penalty -10001
.\glue(\rightskip)0.0 plus 10000.0
```

and we want to ensure that the thickmuskip glue gets removed. And we now arrange for `\EQ@copy` and `\EQ@box` to keep the LHS in a separate subbox; this is so that we can introduce a different penalty before the first relation symbol if necessary, depending on the layout decisions that are made later.

```
795 \global\setbox\EQ@copy\hbox{%
796 \hbox{\unhcopy\tw@\unskip\unpenalty\unskip}%
797 \box\EQ@copy
798 }%
799 \global\setbox\EQ@box\hbox{%
800 \hbox{\unhbox\tw@\unskip\unpenalty\unskip}%
801 \box\EQ@box
```

```

802     }%
803     \unskip
804 \or % case 3: unpack left-right box
805     \unpenalty
806     \eq@lrunpack
807 \else
808     \breqn@repack@err{%
809 \fi
810 \eq@repack % RECURSE
811 }

```

Error message extracted to streamline calling function.

```

812 \def\breqn@repack@err{%
813 \PackageError{breqn}{\eq@repack penalty neq 0,1,2,3}\relax
814 }

```

**\eq@repacka** We need to transfer each line into two separate boxes, one containing everything and one that omits stuff like `\inserts` that would interfere with measuring.

```

815 \def\eq@repacka#1{%
816 \global\setbox#1\hbox{\unhcopy\tw@ \unskip
817 \count@-\lastpenalty
818 \ifnum\count@<\@M \else \advance\count@-\@M \fi
819 \unpenalty

```

If creating the measure copy, ignore all cases above case 3 by folding them into case 1.

```

820 \ifx\EQ@copy#1\ifnum\count@>\thr@@ \count@\@ne\fi\fi
821 \ifcase\count@
822 % case 0, normal line break
823 \penalty-\@M % put back the linebreak penalty
824 \or % case 1, do nothing (end of equation)
825 \relax
826 \or % case 2, no-op (obsolete case)
827 \or % case 3, transfer vspace and/or penalty
828 \ifx#1\EQ@box \eq@revspace \else \eq@revspaceb \fi
829 \or % case 4, put back an insert
830 \eq@reinsert
831 \or % case 5, put back a mark
832 \eq@remark
833 \or % case 6, put back a vadjust
834 \eq@readjust
835 \else % some other break penalty
836 \penalty-\count@
837 \fi
838 \unhbox#1}%
839 }

```

**\eq@nulldisplay** Throw in a null display in order to get `predisplaysize` etc.. My original approach here was to start the null display, then measure the equation, and set a phantom of the equation's first line before ending the null display. That would allow finding

out if  $\TeX$  used the short `display skips` instead of the normal ones. But because of some complications with grouping and the desirability of omitting unnecessary invisible material on the vertical list, it seems better to just collect information about the display (getting `\prevdepth` requires `\halign`) and manually perform our own version of  $\TeX$ 's shortskip calculations. This approach also gives greater control, e.g., the threshold amount of horizontal space between `preplaysize` and the equation's left edge that determines when the short skips kick in becomes a designer-settable parameter rather than hardwired into  $\TeX$ .

```

840 \def\eq@nulldisplay{%
841   \begingroup \frozen@everydisplay\@emptytoks
842   \@@display
843   \predisplaypenalty\@M \postdisplaypenalty\@M
844   \abovedisplayskip\z@skip \abovedisplayshortskip\z@skip
845   \belowdisplayskip\z@skip \belowdisplayshortskip\z@skip
846   \xdef\EQ@displayinfo{%
847     \prevgraf\the\prevgraf \preplaysize\the\preplaysize
848     \displaywidth\the\displaywidth \displayindent\the\displayindent
849     \listwidth\the\linewidth

```

Not sure how best to test whether `leftmargin` should be added. Let's do this for now [mjd,1997/10/08].

```

850   \ifdim\displayindent>\z@
851     \advance\listwidth\the\leftmargin
852     \advance\listwidth\the\rightmargin
853   \fi
854   \relax}%

```

An `\halign` containing only one `\cr` (for the preamble) puts no box on the vertical list, which means that no `\baselineskip` will be added (so we didn't need to set it to zero) and the previous value of `prevdepth` carries through. Those properties do not hold for an empty simple equation without `\halign`.

```

855   \halign{##\cr}%
856   \@@enddisplay
857   \par
858   \endgroup
859   \EQ@displayinfo
860 }

```

```

\eq@newline Here we use \@ifnext so that in a sequence like
\eq@newlinea ...\\
\eq@newlineb [a,b]

```

$\LaTeX$  does not attempt to interpret the `[a,b]` as a vertical space amount. We would have used `\eq@break` in the definition of `\eq@newlineb` except that it puts in a `\keep@glue` object which is not such a good idea if a mathbin symbol follows—the indent of the mathbin will be wrong because the leading negative glue will not disappear as it should at the line break.

```

861 \def\eq@newline{%
862   \@ifstar{\eq@newlinea\@M}{\eq@newlinea\eqinterlinepenalty}}

```

```

863 \def\eq@newlinea#1{%
864   \@ifnext[\eq@newlineb{#1}]{\eq@newlineb{#1}[\maxdimen]}}
865 \def\eq@newlineb#1[#2]{\penalty-\@M}

```

`\eq@revspace` When `\eq@revspace` (re-vspace) is called, we are the end of an equation line; we need to remove the existing penalty of  $-10002$  in order to put a `vadjust` object in front of it, then put back the penalty so that the line break will still take place in the final result.

```

866 \def\eq@revspace{%
867   \global\setbox\EQ@vimbox\vbox{\unvbox\EQ@vimbox
868     \unpenalty
869     \global\setbox\@ne\lastbox}%
870   \@@vadjust{\unvbox\@ne}%
871   \penalty-\@M
872 }

```

The b version is used for the `\EQ@copy` box.

```

873 \def\eq@revspaceb{%
874   \global\setbox\EQ@vimcopy\vbox{\unvbox\EQ@vimcopy
875     \unpenalty
876     \global\setbox\@ne\lastbox}%
877   \@@vadjust{\unvbox\@ne}%
878   \penalty-\@M
879 }

```

`\eq@break` The function `\eq@break` does a preliminary linebreak with a flag penalty.

```

880 \def\eq@break#1{\penalty-1000#1 \keep@glue}

```

## 27 Choosing optimal line breaks

The question of what line width to use when breaking an equation into several lines is best examined in the light of an extreme example. Suppose we have a two-column layout and a displayed equation falls inside a second-level list with nonzero `leftmargin` and `rightmargin`. Then we want to try in succession a number of different possibilities. In each case if the next possibility is no wider than the previous one, skip ahead to the one after.

1. First try `linewidth(2)`, the `linewidth` for the current level-2 list.
2. If we cannot find adequate linebreaks at that width, next try `listwidth(2)`, the sum of `leftmargin`, `linewidth`, and `rightmargin` for the current list.
3. If we cannot find linebreaks at that width, next try `linewidth(1)` (skipping this step if it is no larger than `listwidth(2)`).
4. If we cannot find linebreaks at that width, next try `listwidth(1)`.
5. If we cannot find linebreaks at that width, next try column width.

needs work

Figure 5: first-approximation parshape for equations

6. If we cannot find linebreaks at that width, next try text width.
7. If we cannot find linebreaks at that width, next try equation width, if it exceeds text width (i.e., if the style allows equations to extend into the margins).

At any given line width, we run through a series of parshape trials and, essentially, use the first one that gives decent line breaks. But the process is a bit more complicated in fact. In order to do a really good job of setting up the parshapes, we need to know how many lines the equation will require. And of course the number of lines needed depends on the parshape! So as our very first trial we run a simple first-approximation parshape (Figure 5) whose main purpose is to get an estimate on the number of lines that will be needed; it chooses a uniform indent for all lines after the first one and does not take any account of the equation number. A substantial majority of equations only require one line anyway, and for them this first trial will succeed. In the one-line case if there is an equation number and it doesn't fit on the same line as the equation body, we don't go on to other trials because breaking up the equation body will not gain us anything—we know that we'll have to use two lines in any case—so we might as well keep the equation body together on one line and shift the number to a separate line.

If we learn from the first trial that the equation body requires more than one line, the next parshape trial involves adjusting the previous parshape to leave room for the equation number, if present. If no number is present, again no further trials are needed.

Some remarks about parshape handling. The  $\text{\TeX}$  primitive doesn't store the line specs anywhere, `\the\parshape` only returns the number of line specs. This makes it well nigh impossible for different packages that use `\parshape` to work together. Not that it would be terribly easy for the package authors to make inter-package collaboration work, if it were possible. If we optimistically conjecture that someone some day may take on such a task, then the thing to do, obviously, is provide a parshape interface that includes a record of all the line specs. For that we designate a macro `\@parshape` which includes not only the line specs, but also the line count and even the leading `\parshape` token. This allows it to be directly executed without an auxiliary if-empty test. It should include a trailing `\relax` when it has a nonempty value.

881 `\let\@parshape\@empty`

The function `\eq@measure` runs line-breaking trials on the copy of the equation body that is stored in the box register `\EQ@copy`, trying various possible layouts in order of preference until we get successful line breaks, where 'successful' means there were no overfull lines. The result of the trials is, first, a parshape spec that can be used for typesetting the real equation body in `\EQ@box`, and second, some information that depends on the line breaks such as the depth of the last line, the

height of the first line, and positioning information for the equation number. The two main variables in the equation layout are the line width and the placement of the equation number, if one is present.

`\eq@measure` Run linebreak trials on the equation contents and measure the results.

```

882 \def\eq@measure{%
    If an override value is given for indentstep in the env options, use it.
883 \ifdim\eq@indentstep=\maxdimen \eq@indentstep\eqindentstep \fi
    If \eq@linewidth is nonzero at this point, it means that the user specified a
    particular target width for this equation. In that case we override the normal list
    of trial widths.
884 \ifdim\eq@linewidth=\z@ \else \edef\eq@linewidths{{\the\eq@linewidth}}\fi
885 \begingroup \eq@params
886 \leftskip\z@skip
    Even if \hfuzz is greater than zero a box whose contents exceed the target width
    by less than hfuzz still has a reported badness value of 1000000 (infinitely bad).
    Because we use inf-bad to test whether a particular trial succeeds or fails, we want
    to make such boxes return a smaller badness. To this end we include an \hfuzz
    allowance in \rightskip. In fact, \eq@params ensures that \hfuzz for equations
    is at least 1pt.
887 \rightskip\z@ \@plus\columnwidth \@minus\hfuzz
888 % \eqinfo
889 \global\EQ@continue{\eq@trial}%
890 \eq@trial % uses \eq@linewidths
891 \eq@failout % will be a no-op if the trial succeeded
892 \endgroup
    'local' parameter settings are passed outside the endgroup through \EQ@trial.
893 \EQ@trial
894 }

895 <*trace>
896 \def\debug@showmeasurements{%
897 \breqn@debugmsg{=> \number\eq@lines\space lines}%
898 \begingroup
899 \def\@elt##1X##2{\MessageBreak==== \space\space##1/##2}%
900 \let\@endelt\@empty
901 \breqn@debugmsg{=> trial info:\eq@measurements}%
902 \breqn@debugmsg{=> bounding box: \the\eq@wdT x\the\eq@vspan, badness=\the\eq@badness}%
903 \let\@elt\relax \let\@endelt\relax
904 \endgroup
905 }
906 \def\debug@showmeasurements{%
907 \begingroup
908 \def\@elt##1X##2{\MessageBreak==== ##1/##2}%
909 \let\@endelt\@empty
910 \breqn@debugmsg{====> Measurements: \number\eq@lines\space lines
911 \eq@measurements

```



```

912         \MessageBreak
913         ==== bounding box: \the\eq@wdT x\the\eq@vspan, badness=\the\eq@badness
914         \MessageBreak
915         ==== \leftskip=\the\leftskip, \rightskip=\the\rightskip}%
916     \endgroup
917 }
918 </trace>

```

Layout Trials Driver Basically, trying different sequences of parshapes.

`\EQ@trial` Init.

```

919 \let\EQ@trial\@empty

```

`\EQ@continue` This is a token register used to carry trial info past a group boundary with only one global assignment.

```

920 \newtoks\EQ@continue

```

`\EQ@widths` This is used for storing the actual line-width info of the equation contents after breaking.

```

921 \let\EQ@widths\@empty

```

`\EQ@fallback`

```

922 \let\EQ@fallback\@empty

```

`\eq@linewidths` This is the list of target widths for line breaking.

===== BRM:

Odd; I don't think I've seen this use anything but `\displaywidth`...

```

923 \def\eq@linewidths{\displaywidth\linewidth\columnwidth}

```

`\eq@trial` The `\eq@trial` function tries each candidate line width in `\eq@linewidths` until an equation layout is found that yields satisfactory line breaks.

```

924 \def\eq@trial{%
925   \ifx\@empty\eq@linewidths
926     \global\EQ@continue{}%
927   \else
928     \iffalse{\fi \exp\eq@trial@a \eq@linewidths}%
929   \fi
930   \the\EQ@continue
931 }

```

`\eq@trial@a` The `\eq@trial@a` function reads the leading line width from `\eq@linewidths`; if the new line width is greater than the previous one, start running trials with it; otherwise do nothing with it. Finally, run a peculiar `\edef` that leaves `\eq@linewidths` redefined to be the tail of the list. If we succeed in finding satisfactory line breaks for the equation, we will reset `\EQ@continue` in such a way that it will terminate the current trials. An obvious branch here would be to check whether the width of `\EQ@copy` is less than `\eq@linewidth` and go immediately to the one-line case if so. However, if the equation contains more than

one RHS, by default each additional RHS starts on a new line—i.e., we want the ladder layout anyway. So we choose the initial trial on an assumption of multiple lines and leave the one-line case to fall out naturally at a later point.

```

932 \def\eq@trial@a#1{%
933   \dim@c#1\relax
934   \if T\eq@frame \eq@frame@adjust\dim@c \fi
935   \ifdim\dim@c>\eq@linewidth
936     \eq@linewidth\dim@c
937   <trace>   \breqn@debugmsg{Choose Shape for width(#1)=\the\eq@linewidth}%
938     \let\eq@trial@b\eq@trial@d
939     \csname eq@try@layout@\eq@layout\endcsname
940   <trace>   \else
941   <trace>   \breqn@debugmsg{Next width (#1) is shorter; skip it}%
942   \fi
943   \edef\eq@linewidths{\iffalse}\fi
944 }
945 \def\eq@frame@adjust#1{%
946   %\addtolength#1{-2\eq@framewd-2\eq@framesep}%
947   \dim@a\eq@framewd \advance\dim@a\eq@framesep
948   \advance#1-2\dim@a
949 }

```

===== Note curious control structure. Try to understand interaction of \EQ@fallback, \EQ@continue, \eq@failout

```

950 \def\eq@trial@succeed{%
951   \aftergroup\@gobbletwo % cancel the \EQ@fallback code; see \eq@trial@c (?)
952   \global\EQ@continue{\eq@trial@done}%
953 }

```

\eq@trial@done Success.

```

954 \def\eq@trial@done{%
955 <trace>   \breqn@debugmsg{End trial: Success!}%
956   \let\eq@failout\relax
957 }

```

\eq@trial@init This is called from \eq@trial@b to initialize or re-initialize certain variables as needed when running one or more trials at a given line width. By default assume success, skip the fallback code.

```

958 \def\eq@trial@init{\global\let\EQ@fallback\eq@nextlayout}

```

\eq@nextlayout In the fallback case cancel the current group to avoid unnecessary group nesting (with associated save-stack cost, etc.).

```

959 \def\eq@nextlayout#1{%
960   \endgroup
961 <trace>   \breqn@debugmsg{Nope ... that ain't gonna work.}%
962   \begingroup #1%
963 }

```

```

\eq@failout .
964 \def\eq@failout{%
965 <trace>\breqn@debugmsg{End trial: failout}%
966 \global\let\EQ@trial\EQ@last@trial
967 }

\eq@trial@save Save the parameters of the current trial.
968 \def\eq@trial@save#1{%
969 <*trace>
970 % \begingroup \def\@elt##1X##2{\MessageBreak==== \space\space##1/##2}\let\@endelt\@empty\breqn@
971 % \breqn@debugmsg{=> bounding box: \the\eq@wdT x\the\eq@vspan, badness=\the\eq@badness}%
972 % \let\@elt\relax \let\@endelt\relax
973 % \endgroup
974 </trace>
975 \xdef#1{%
976 \eq@linewidth\the\eq@linewidth
977 % save info about the fit
978 \eq@lines\the\eq@lines \eq@badness\the\eq@badness \def\@nx\eq@badline{\eq@badline}%
979 % save size info
980 \eq@wdT\the\eq@wdT \eq@wdMin\the\eq@wdMin
981 \eq@vspan\the\eq@vspan \eq@dp\the\eq@dp \eq@firstht\the\eq@firstht
982 % save info about the LHS
983 \eq@wdL\the\eq@wdL \def\@nx\EQ@hasLHS{\EQ@hasLHS}%
984 % save info about the numbering
985 \def\@nx\eq@hasNumber{\eq@hasNumber}%
986 % save info about the chosen layout
987 \def\@nx\eq@layout{\eq@layout}%
988 \def\@nx\eq@parshape{\@parshape}%
989 \def\@nx\eq@measurements{\eq@measurements}%
990 \def\@nx\adjust@rel@penalty{\adjust@rel@penalty}%
991 \def\@nx\eq@shiftnumber{\eq@shiftnumber}%
992 \def\@nx\eq@isIntertext{\@False}%
993 }%
994 }

\eq@trial@b By default this just runs \eq@trial@c; cf. \eq@trial@d.
995 \def\eq@trial@b{\eq@trial@c}

\eq@trial@c Run the equation contents through the current parshape.
996 \def\eq@trial@c#1#2{%
997 <trace> \breqn@debugmsg{Trying layout "#1" with\MessageBreak==== parshape\space\@xp\@gobble\@par
998 \begingroup
999 \eq@trial@init
1000 \def\eq@layout{#1}%
1001 \setbox\z@\vbox{%
1002 \hfuzz\maxdimen
1003 \eq@trial@p % run the given parshape
1004 \if\@Not{\eq@badline}%
1005 \eq@trial@save\EQ@trial

```

If there is a number, try the same parshape again with adjustments to make room for the number.

This is an awkward place for this: It only allows trying to fit the number w/the SAME layout shape!

```

1006     \if\eq@hasNumber\eq@retry@with@number\fi
1007     \if L\eq@layout \eq@check@density
1008     \else
1009         \if\@Not{\eq@badline}%
1010             \eq@trial@succeed
1011         \fi
1012     \fi
1013 \else
1014     \eq@trial@save\EQ@last@trial
1015 \fi
1016 }%
1017 \EQ@fallback{#2}%
1018 \endgroup
1019 }

```

`\eq@trial@d`

```

1020 \def\eq@trial@d#1#2{\eq@trial@c{#1}{}}

```

`\eq@check@density`

```

1021 \def\eq@check@density{%
1022   <trace> \breqn@debugmsg{Checking density for layout L}%
1023   \if\@Or{\@Not\EQ@hasLHS}{\eq@shortLHS}%
1024   <trace> \breqn@debugmsg{Density check: No LHS, or is short; OK}%
1025   \eq@trial@succeed
1026 \else\if\eq@dense@enough
1027   \eq@trial@succeed
1028 \fi\fi
1029 }

```

`\eq@shortLHS` Test to see if we need to apply the `\eq@dense@enough` test.

```

1030 \def\eq@shortLHS{\ifdim\eq@wdL>.44\eq@wdT 1\else 0\fi 0}

```

```

\def\eq@shortLHS{\@False} =====

```

`\eq@trial@p` Run a trial with the current `\@parshape` and measure it.

```

1031 \def\eq@trial@p{%
1032   \@parshape %
1033   \eq@dump@box\unhcopy\EQ@copy
1034   {\@par}% leave \parshape readable
1035   \eq@lines\prevgraf
1036   \eq@fix@lastline
1037   \let\eq@badline\@False
1038   \if i\eq@layout \ifnum\eq@lines>\@ne \let\eq@badline\@True \fi\fi
1039   \eq@curline\eq@lines % loop counter for eq@measure@lines
1040   \let\eq@measurements\@empty

```

```

1041 \eq@ml@record@indents
1042 \eq@measure@lines
1043 \eq@recalc
1044 <trace> \debug@showmeasurements
1045 }

\adjust@rel@penalty Normally this is a no-op.
1046 \let\adjust@rel@penalty\@empty

\eq@fix@lastline Remove parfillskip from the last line box.
1047 \def\eq@fix@lastline{%
1048 \setbox\tw@\lastbox \dim@b\wd\tw@
1049 \eq@dp\dp\tw@

Remove \parfillskip but retain \rightskip. Need to keep the original line
width for later shrink testing.

1050 \nointerlineskip\hbox to\dim@b{\unhbox\tw@
1051 \skip@c\lastskip \unskip\unskip\hskip\skip@c
1052 }%
1053 }

\eq@recalc Calculate \eq@wdT et cetera.
1054 \def\eq@recalc{%
1055 \eq@wdT\z@ \eq@wdMin\maxdimen \eq@vspan\z@skip \eq@badness\z@
1056 \let\@elt\eq@recalc@a \eq@measurements \let\@elt\relax
1057 }

\eq@recalc@a
1058 \def\eq@recalc@a#1x#2+#3\@endelt{%
1059 \eq@firstht#2\relax
1060 \let\@elt\eq@recalc@b
1061 \@elt#1x#2+#3\@endelt
1062 }

\eq@recalc@b
1063 \def\eq@recalc@b#1X#2,#3x#4+#5@#6\@endelt{%
1064 \setlength\dim@a{#2+#3}%
1065 \ifdim\dim@a>\eq@wdT \eq@wdT\dim@a \fi
1066 \ifdim\dim@a<\eq@wdMin \eq@wdMin\dim@a \fi
1067 \eq@dp#5\relax
1068 \addtolength\eq@vspan{#1+#4+\eq@dp}%

Record the max badness of all the lines in \eq@badness.

1069 \ifnum#6>\eq@badness \eq@badness#6\relax\fi
1070 }

\eq@layout A value of ? for \eq@layout means that we should deduce which layout to use
by looking at the size of the components. Any other value means we have a
user-specified override on the layout.

```

Layout Definitions. Based on initial equation measurements, we can choose a sequence of candidate parshapes that the equation might fit into. We accept the first shape that ‘works’, else fall to next one. [The sequence is hardcoded in the `\eq@try@layout@shape`; Would it be useful be more flexible? (eg. try layouts LDA, in order...)]

```
1071 \def\eq@layout{?}
```

`\eq@try@layout@?` This is a branching function used to choose a suitable layout if the user didn’t specify one in particular.

Default layout: Try Single line layout first, else try Multiline layouts

```
1072 \@namedef{eq@try@layout@?}{%
1073   \let\eq@trial@b\eq@trial@c
1074   \edef\@parshape{\parshape 1 0pt \the\eq@linewidth\relax}%
1075   % \eq@trial@b{fi}{\eq@try@layout@multi}%
1076   \setlength\dim@a{\wd\EQ@copy-2em}% Fudge; can’t shrink more than this?
1077   % if we’re in a numbered group, try hard to fit within the numbers
1078   \dim@b\eq@linewidth
1079   \if\eq@shiftnumber\else\if\eq@group
1080     \if\eq@hasNumber\addtolength\dim@b{-\wd\EQ@numbox-\eqnumsep}%
1081     \else\if\grp@hasNumber\addtolength\dim@b{-\wd\GRP@numbox-\eqnumsep}%
1082     \fi\fi\fi\fi
1083     \ifdim\dim@a<\dim@b% Do we even have a chance of fitting to one line?
1084     \trace \breqn@debugmsg{Choose Shape: (\the\wd\EQ@copy) may fit in \the\dim@b}%
1085     \setlength\dim@b{\columnwidth-\dim@a+\eq@wdCond}%
1086     \rightskip\z@+\dim@b\@minus\hfuzz
1087     \eq@trial@b{fi}{\eq@try@layout@multi}%
1088     \else
1089     \trace
1090     \breqn@debugmsg{Choose Shape: Too long (\the\wd\EQ@copy) for one line
1091       (free width=\the\dim@b)}%
1092     \trace
1093     \eq@try@layout@multi
1094     \fi
1095 }
```

Layout Multiline layout: If no LHS, try Stepped(S) layout Else try Stepped(S), Ladder(L), Drop-ladder(D) or Stepladder(l), depending on LHS length.

```
1096 \def\eq@try@layout@multi{%
1097   \if\EQ@hasLHS
1098     \ifdim\eq@wdL>\eq@linewidth
1099     \trace \breqn@debugmsg{Choose Shape: LHS \the\eq@wdL > linewidth}%
1100     \setlength\dim@a{\wd\EQ@copy-\eq@wdL}%
1101     \ifdim\dim@a<.25\eq@linewidth \eq@try@layout@S
1102     \else \eq@try@layout@l
1103     \fi
```

```

1104      % BRM: Originally .7: Extreme for L since rhs has to wrap within the remaining 30+%!
1105      \else\ifdim\eq@wdL>.50\eq@linewidth
1106      <*trace>
1107          \breqn@debugmsg{Choose Shape: LHS (\the\eq@wdL) > .50 linewidth (linewidth=\the\eq@linewi
1108      </trace>
1109          \eq@try@layout@D
1110      \else
1111      <trace>          \breqn@debugmsg{Choose Shape: LHS (\the\eq@wdL) not extraordinarily wide}%
1112          \eq@try@layout@L
1113      \fi\fi
1114      \else
1115      <trace>          \breqn@debugmsg{Choose Shape: No LHS here}%
      Try one-line layout first, then step layout.
1116      \eq@try@layout@S % (already checked case i)
1117      \fi
1118  }

```

`\eq@try@layout@D` Change the penalty before the first mathrel symbol to encourage a break there.  
Layout D=Drop-Ladder Layout, for wide LHS.

```

LOOOOOOOONG LHS
= RHS
= ...

```

If fails, try Almost-Columnar layout

```

1119 \def\eq@try@layout@D{%
1120   \setlength\dim@a{\eq@linewidth -\eq@indentstep}%
1121   \edef\@parshape{\parshape 2
1122     0pt \the\eq@wdL\space \the\eq@indentstep\space \the\dim@a\relax
1123   }%
1124   \def\adjust@rel@penalty{\penalty-99 }%
1125   \eq@trial@b{D}{\eq@try@layout@A}%
1126 }

```

`\eq@try@layout@L` Try a straight ladder layout. Preliminary filtering ensures that `\eq@wdL` is less than 70 of the current line width.

```

Layout L=Ladder layout
LHS = RHS
= RHS
...

```

If fails, try Drop-ladder layout. NOTE: This is great for some cases (multi relations?), but tends to break really badly when it fails....

```

1127 \def\eq@try@layout@L{%
1128   \setlength\dim@b{\eq@linewidth-\eq@wdL}%
1129   \edef\@parshape{\parshape 2 0pt \the\eq@linewidth\space
1130     \the\eq@wdL\space \the\dim@b\relax
1131   }%
1132   \eq@trial@b{L}{\eq@try@layout@D}%
1133 }

```

`\eq@try@layout@S` In the “stepped” layout there is no LHS, or LHS is greater than the line width and RHS is small. Then we want to split up the equation into lines of roughly equal width and stagger them downwards to the right, leaving a small amount of whitespace on both sides. But also, if there is an equation number, we want to try first a layout that leaves room for the number. Otherwise it would nearly always be the case that the number would get thrown on a separate line.

Layout S=Stepped layout, typically no LHS or very long, variations on

```
STUFF ....
+ MORE STUFF ...
+ MORE STUFF ...
```

If fails, try Almost-Columnar layout

```
1134 \def\eq@try@layout@S{%
1135   \setlength\dim@b{\eq@linewidth-2\eqmargin}% \advance\dim@b-1em%
```

About how many lines will we need if `\dim@b` is the line width?

```
1136   \int@a\wd\EQ@copy \divide\int@a\dim@b
```

Adjust the target width by number of lines times indentstep. We don’t need to decrement `\int@a` because  $\TeX$  division is integer division with truncation.

```
1137   \addtolength\dim@b{-\int@a\eq@indentstep}%
```

Adjust for equation number. But try not to leave too little room for the equation body.

```
1138   \if\eq@hasNumber
1139     \ifdim\dim@b>15em%
1140       \advance\dim@b-\eqnumsep \advance\dim@b-\wd\EQ@numbox
1141       \addtolength\dim@b{-\eq@wdNum}%
1142     \fi
1143   \fi
```

Now some hand-waving to set up the parshape.

```
1144   \int@b\z@
1145   \def\@tempa{\dim}%
1146   \edef\@parshape{\parshape 2 0pt \the\dim@b\space
1147     \the\eqmargin\space\the\dim@b\relax}%
1148   \eq@trial@b{S}{\eq@try@layout@A}%
1149 }
```

`\eq@try@layout@l` This is the “step-ladder” layout: similar to the drop-ladder layout but the LHS is too wide and needs to be broken up.

Layout l = Stepladder Similar to Drop-Ladder, but LHS is long and needs to be broken up. If fails, try Almost-Columnar layout

```
1150 \def\eq@try@layout@l{%
1151   \setlength\dim@a{\eq@linewidth -\eq@indentstep}%
1152   \int@a\eq@wdL \divide\int@a\dim@a
1153   \advance\int@a\tw@
1154   \edef\@parshape{\parshape \number\int@a\space
1155     0pt \the\eq@linewidth
1156   }%
```



```

1157 \advance\int@a-\tw@
1158 \setlength\dim@b{2\eq@indentstep}%
1159 \setlength\dim@c{\eq@linewidth -\dim@b}%
1160 \edef\@parshape{\@parshape
1161   \replicate{\int@a}{\space\the\eq@indentstep\space\the\dim@a}%
1162   \space\the\dim@b\space\the\dim@c\relax
1163 }%
1164 \eq@trial@b{1}{\eq@try@layout@A}%
1165 }

```

`\eq@try@layout@A` In the “almost-columnar” layout, which is the layout of last resort, we let all lines run to the full width and leave the adjusting of the indents to later.

Layout A = Almost-Columnar layout. Pretty much straight full width, more of a last-resort. If fails, give up.

```

1166 \def\eq@try@layout@A{%
1167   \edef\@parshape{\parshape 1 0pt \the\eq@linewidth\relax}%
1168   \if\EQ@hasLHS \def\adjust@rel@penalty{\penalty-99 } \fi
1169   \eq@trial@b{A}{}%
1170 }

```

`\eq@shiftnumber` MH: Should be moved to a section where all keys are set to defaults.

```

1171 \let\eq@shiftnumber\@False

```

`\eq@retry@with@number@a` Number placement adjustments

```

1172 \def\eq@retry@with@number{%
1173   \if\eq@shiftnumber
1174   <trace> \breqn@debugmsg{Place number: Shifted number requested}%
1175   \else

```

Condition and right numbers? We’re just going to have to shift.

```

1176   \ifdim\eq@wdCond>\z@\if R\eqnumside
1177   <trace> \breqn@debugmsg{Place number: Condition w/Right number => Shift number}%
1178   \let\eq@shiftnumber\@True
1179   \fi\fi

```

Compute free space.

```

1180 % \dim@b\eqnumsep\advance\dim@b\wd\EQ@numbox
1181 \dim@b\eq@wdNum
1182 \if L\eqnumside
1183   \ifdim\@totalleftmargin>\dim@b\dim@b\@totalleftmargin\fi
1184   \else
1185   \addtolength\dim@b{\@totalleftmargin}%
1186   \fi
1187   \setlength\dim@a{\eq@linewidth-\dim@b}\advance\dim@a1em\relax% Allowance for shrink?

```

Set up test against 1-line case only if not in a group

```

1188   \int@a\@ne\if\eq@group\int@a\maxint\fi

```

Now check for cases.

```

1189   \if\eq@shiftnumber % Already know we need to shift
1190   \else\ifdim\eq@wdT<\dim@a % Fits!

```

left & right skips will be done later, and parshape adjusted if needed.

```
1191 <trace>      \breqn@debugmsg{Place number: eqn and number fit together}%
1192 %      \else\ifnum\eq@lines=\int@a % Shift, if single line, unless inside a dgroup.
```

NOTE: this is too strong for dgroup!

```
1193 <*trace>
1194 %      \breqn@debugmsg{Place number: single line too long with number => Shift number \the\int@
1195 </trace>
1196 %      \let\eq@shiftnumber\@True
1197      \else
```

Retry: use leftskip for space for number(for now; whether right/left) & adjust parshape

```
1198 %      \leftskip\wd\EQ@numbox\advance\leftskip\eqnumsep
1199      \setlength\leftskip{\eq@wdNum}%
1200      \setlength\rightskip{\z@\@plus\dim@a}%
1201      \adjust@parshape\@parshape
1202 <*trace>
1203      \breqn@debugmsg{Place number: Try with \leftskip=\the\leftskip, \rightskip=\the\rightskip
1204      \MessageBreak==== parshape\space\@xp\@gobble\@parshape}%
1205 </trace>
1206      \nointerlineskip
1207      \edef\eq@prev@lines{\the\eq@lines}%
1208      \edef\eq@prev@badness{\the\eq@badness}% BRM
1209      \eq@trial@p
1210      \int@a\eq@prev@badness\relax\advance\int@a 50\relax%
1211      \int@b\eq@prev@lines \if\eq@group\advance\int@b\@ne\fi% Allow 1 extra line in group
1212      \ifnum\eq@lines>\int@b % \eq@prev@lines
1213 <trace>      \breqn@debugmsg{Adjustment causes more breaks => Shift number}%
1214      \let\eq@shiftnumber\@True
1215      \else\if\eq@badline
1216 <trace>      \breqn@debugmsg{Adjustment causes bad lines (\the\eq@badness) => Shift}%
1217      \let\eq@shiftnumber\@True
1218      \else\ifnum\eq@badness>\int@a % BRM: New case
1219 <*trace>
1220      \breqn@debugmsg{Adjustment is badder than previous
1221      (\the\eq@badness >> \eq@prev@badness) => Shift}%
1222 </trace>
1223      \let\eq@shiftnumber\@True
1224      \else
1225 <trace>      \breqn@debugmsg{Adjustment succeeded}%
1226      \fi\fi%\fi
1227      \fi\fi\fi

If we got shifted, restore parshape, etc,
1228      \if\eq@shiftnumber
1229      \EQ@trial% Restore parshape & other params,
1230      \leftskip\z@\let\eq@shiftnumber\@True % But set shift & leftskip
1231      \edef\@parshape{\eq@parshape}% And copy saved parshape back to 'working copy' !?!?
1232      \fi
1233      \eq@trial@save\EQ@trial      % Either way, save the trial state.
```

```

1234 \fi
1235 }

```

`\adjust@parshape` Varies depending on the layout.

Adjust a parshape variable for a given set of left|right skips. Note that the fixed part of the left|right skips effectively comes out of the parshape widths (NOT in addition to it). We also must trim the widths so that the sum of skips, indents and widths add up to no more than the `\eq@linewidth`.

```

1236 \def\adjust@parshape#1{%
1237   \xp\adjust@parshape@a#1\relax
1238   \edef#1{\temp@a}%
1239 }

```

`\adjust@parshape@a`

`\adjust@parshape@b`

```

1240 \def\adjust@parshape@a#1 #2\relax{%
1241   \setlength\dim@a{\leftskip+\rightskip}%
1242   \edef\temp@a{#1}%
1243   \adjust@parshape@b#2 @ @ \relax
1244 }
1245 \def\adjust@parshape@b#1 #2 {%
1246   \ifx @#1\edef\temp@a{\temp@a\relax}%
1247   \xp\@gobble
1248   \else
1249     \dim@b#1\relax
1250     \dim@c#2\relax
1251     \addtolength\dim@c{\dim@a+\dim@b}%
1252     \ifdim\dim@c>\eq@linewidth\setlength\dim@c{\eq@linewidth}\fi
1253     \addtolength\dim@c{-\dim@b}%
1254     \edef\temp@a{\temp@a\space\the\dim@b\space\the\dim@c}%
1255   \fi
1256   \adjust@parshape@b
1257 }

```

`\eq@ml@record@indents` Plunk the parshape's indent values into an array for easy access when constructing `\eq@measurements`.

```

1258 \def\eq@ml@record@indents{%
1259   \int@a\z@
1260   \def\@tempa{%
1261     \advance\int@a\@ne
1262     \xp\edef\csname eq@i\number\int@a\endcsname{\the\dim@a}%
1263     \ifnum\int@a<\int@b \afterassignment\@tempb \fi
1264     \dim@a
1265   }%
1266   \def\@tempb{\afterassignment\@tempa \dim@a}%
1267   \def\@tempc##1##2 {\int@b##2\afterassignment\@tempa\dim@a}%
1268   \xp\@tempc\@parshape
1269 }

```

`\@endelt` This is a scan marker. It should get a non-expandable definition. It could be `\relax`, but let's try a chardef instead.



```

1305 % dimen part later
1306 \csname eq@i%
1307 \ifnum\eq@curline<\parshape \number\eq@curline
1308 \else\number\parshape
1309 \fi
1310 \endcsname,\the\dim@a x\the\ht\tw@+\the\dp\tw@ @\the\eq@badness\@endelt
1311 \eq@measurements
1312 }%
1313 \advance\eq@curline\m@ne
1314 \ifnum\eq@curline=\z@ \let\eq@ml@continue\relax\fi
1315 }

```

`\eq@ml@vspace` Handle an embedded vspace.

```

1316 \def\eq@ml@vspace{%
1317 \global\advance\eq@vspan\lastskip \unskip\unpenalty
1318 \ifdim\lastskip=\z@ \else \@xp\eq@ml@vspace \fi
1319 }

```

`\eq@dense@enough`

```

1320 \def\eq@dense@enough{%
1321 \ifnum\eq@lines<\thr@@
1322 <trace> \breqn@debugmsg{Density check: less than 3 lines; OK}%
1323 \@True
1324 \else
1325 \ifdim\eq@wdL >.7\eq@wdT
1326 <trace> \breqn@debugmsg{Density check: LHS too long; NOT OK}%
1327 \@False
1328 \else \@xp\@xp\@xp\eq@dense@enough@a
1329 \fi
1330 \fi
1331 }

```

`\true@false@true`

```

1332 \def\true@false@true{\fi\fi\iftrue\iffalse\iftrue}

```

`\false@false@false`

```

1333 \def\false@false@false{\fi\fi\iffalse\iffalse\iffalse}

```

`\false@true@false`

```

1334 \def\false@true@false{\fi\fi\iffalse\iftrue\iffalse}

```

`\eq@density@factor` This number specifies, for the ladder layout, how much of the equation's bounding box should contain visible material rather than whitespace. If the amount of visible material drops below this value, then we switch to the drop-ladder layout. The optimality of this factor is highly dependent on the equation contents; .475 was chosen as the default just because it worked well with the sample equation, designed to be as average as possible, that I used for testing.

```

1335 \def\eq@density@factor{.475}

```

`\eq@dense@enough@a` Calculate whether there is more visible material than whitespace within the equation’s bounding box. Sum up the actual line widths and compare to the total “area” of the bounding box. But if we have an extremely large number of lines, fall back to an approximate calculation that is more conservative about the danger of exceeding `\maxdimen`.

```

1336 \def\eq@dense@enough@a{%
1337   \@True \fi
1338   \ifnum\eq@lines>\sixt@@n
1339     \eq@dense@enough@b
1340   \else
1341     \dim@b\z@ \let\@elt\eq@delt \eq@measurements
1342     \dim@c\eq@density@factor\eq@wdT \multiply\dim@c\eq@lines
1343     <trace> \breqn@debugmsg{Density check: black \the\dim@b/\eq@density@factor total \the\dim@c}%
1344     \ifdim\dim@b>\dim@c \true@false@true \else \false@false@false \fi
1345   \fi
1346 }
```

`\eq@delt` Args are space-above, indent, width, height, depth, badness.

```

1347 \def\eq@delt#1X#2,#3x#4+#5@#6\@endelt{\addtolength\dim@b{#3}}%
```

`\eq@dense@enough@b` This is an approximate calculation used to keep from going over `\maxdimen` if the number of lines in our trial break is large enough to make that a threat. If  $l$ ,  $t$ ,  $n$  represent left-side-width, total-width, and number of lines, the formula is

$$l/t < .4n/(.9n-1)$$

or equivalently, since rational arithmetic is awkward in T<sub>E</sub>X:  $b$

$$l/t < 4n/(9n-10)$$

```

.
1348 \def\eq@dense@enough@b{%
1349   \int@b\eq@wdT \divide\int@b\p@
1350   \dim@b\eq@wdL \divide\dim@b\int@b
1351   \dim@c\eq@lines\p@ \multiply\dim@c\f@ur
1352   \int@b\eq@lines \multiply\int@b 9 \advance\int@b -10%
1353   \divide\dim@c\int@b
1354   <trace> \breqn@debugmsg{Density check: l/t \the\dim@b\space< \the\dim@c\space 4n/(9n-10)?}%
1355   \ifdim\dim@b<\dim@c \true@true@true \else \false@true@false \fi
1356 }
```

`\eq@parshape`

```

1357 \let\eq@parshape\@empty
```

`\eq@params` The interline spacing and penalties in `\eq@params` are used during both preliminary line breaking and final typesetting.

```

1358 \def\eq@params{%
1359   \baselineskip\eq@linespacing
1360   \lineskip\eq@lineskip \lineskiplimit\eq@lineskiplimit
```

Forbid absolutely a pagebreak that separates the first line or last line of a multiline equation from the rest of it. Or in other words: no equation of three lines or less will be broken at the bottom of a page; instead it will be moved whole to the top of the next page. If you really really need a page break that splits the first or last line from the rest of the equation, you can always fall back to `\pagebreak`, I suppose.

```
1361 \clubpenalty\@M \widowpenalty\@M \interlinepenalty\eqinterlinepenalty
1362 \linepenalty199 \exhyphenpenalty5000 % was 9999: make breaks at, eg. \* a bit easier.
```

For equations, `hfuzz` should be at least 1pt. But we have to fake it a little because we are running the equation through  $\TeX$ 's paragrapher. In our trials we use minus 1pt in the `rightskip` rather than `hfuzz`; and we must do the same during final breaking of the equation, otherwise in borderline cases  $\TeX$  will use two lines instead of one when our trial indicated that one line would be enough.

```
1363 \ifdim\hfuzz<\p@ \hfuzz\p@ \fi
1364 %\hfuzz=2pt
1365 % \ifdim\hfuzz<2pt\relax \hfuzz2pt \fi
1366 \parfillskip\z@skip
1367 % \hfuzz\z@
```

Make sure we skip  $\TeX$ 's preliminary line-breaking pass to save processing time.

```
1368 \tolerance9999 \pretolerance\m@ne
1369 }
```

## 28 Equation layout options

Using the notation C centered, I indented (applied to the equation body), T top, B bottom, M middle, L left, R right (applied to the equation number), the commonly used equation types are C, CRM, CRB, CLM, CLT, I, IRM, IRB, ILM, ILT. In other words, CLM stands for Centered equation body with Left-hand Middle-placed equation number, and IRB stands for Indented equation with Right-hand Bottom-placed equation number.

Here are some general thoughts on how to place an equation tag. Currently it does not work as desired: the L option positions the tag app. 10 lines below the math expression, the RM doesn't position the tag on the baseline for single-line math expressions. Therefore I am going to first write what I think is supposed to happen and then implement it.

Below is a small list where especially the two three specifications should be quite obvious, I just don't want to forget anything and it is important to the implementation.

**Definition 1** If a display consists of exactly one line, the tag should always be placed on the same baseline as the math expression.

The remaining comments refer to multi-line displays.

**Definition 2** If a tag is to be positioned at the top (T), it should be placed such that the baseline of the tag aligns with the baseline of the top line of the display.

**Definition 3** If a tag is to be positioned at the bottom (B), it should be placed such that the baseline of the tag aligns with the baseline of the bottom line of the display.

**Definition 4** If a tag is to be positioned vertically centered (M), it should be placed such that the baseline of the tag is positioned exactly halfway between the baseline of the top line of the display and the baseline of the bottom line of the display.

Definitions 1–3 are almost axiomatic in their simplicity. Definition 4 is different because I saw at least two possibilities for which area to span:

- Calculate distance from top of top line to the bottom of the bottom line, position the vertical center of the tag exactly halfway between those two extremes.
- Calculate the distance from the baseline of the top line to the baseline of the bottom line, position the baseline of the tag exactly halfway between these two extremes.

Additional combinations of these methods are possible but make little sense in my opinion. I have two reasons for choosing the latter of these possibilities: Firstly, two expressions looking completely identical with the exception of a superscript in the first line or a subscript in the last line will have the tag positioned identically. Secondly, then M means halfway between T and B positions which makes good sense and then also automatically fulfills Definition 1.

From an implementation perspective, these definitions should also make it possible to fix a deficiency in the current implementation, namely that the tag does not influence the height of a display, even if the display is a single line. This means that two single-line expressions in a `dgroup` can be closer together than `\intereqskip` if the math expressions are (vertically) smaller than the tag.

## 29 Centered Right-Number Equations

`\eq@dump@box` #1 might be `\unhbox` or `\unhcopy`; #2 is the box name.

```
1370 \def\eq@dump@box#1#2{%
1371   %\debug@box#1%
1372   \noindent #1#2\setbox\four\lastbox \setbox\tw@\lastbox
```

If the LHS contains shrinkable glue, in an L layout the alignment could be thrown off if the first line is shrunk noticeably. For the time being, disable shrinking on the left-hand side. The proper solution requires more work

mjd,1999/03/17

```

1373   \if L\eq@layout \box\tw@ \else\unhbox\tw@\fi
1374   \adjust@rel@penalty \unhbox\four
1375 }
```



Various typesetting bits, invoked from `\eq@finish` BRM: This has been extensively refactored from the original `breqn`, initially to get left|right skips and `parshape` used consistently, ultimately to get most things handled the same way, in the same order.

Given that left and right skips have been set, typeset the frame, number and equation with the given number side and placement

```

1376 \def\eq@typeset@Unnumbered{%
1377   \eq@typeset@frame
1378   \eq@typeset@equation
1379 }
1380 \def\eq@typeset@LM{%
1381   \setlength\dim@a{(\eq@vspan+\ht\EQ@numbox-\dp\EQ@numbox)/2}%
1382   \eq@typeset@leftnumber
1383   \eq@typeset@frame
1384   \eq@typeset@equation
1385 }

```

Typeset equation and left-top number (and shifted)

```

1386 \def\eq@typeset@LT{%
1387   \dim@a\eq@firstht
1388   \eq@typeset@leftnumber
1389   \eq@typeset@frame
1390   \eq@typeset@equation
1391 }

```

Typeset equation and left shifted number

```

1392 \def\eq@typeset@LShifted{%
1393   % place number
1394   \copy\EQ@numbox \penalty\@M
1395   \dim@a\eq@lineskip
1396   \if F\eq@frame\else
1397     \setlength\dim@a{\eq@framesep+\eq@framewd}%
1398   \fi
1399   \kern\dim@a
1400   \eq@typeset@frame
1401   \eq@typeset@equation
1402 }

```

Typeset equation and right middle number

```

1403 \def\eq@typeset@RM{%
1404   \setlength\dim@a{(\eq@vspan+\ht\EQ@numbox-\dp\EQ@numbox)/2}%
1405   \eq@typeset@rightnumber
1406   \eq@typeset@frame
1407   \eq@typeset@equation
1408 }

```

Typeset equation and right bottom number

```

1409 \def\eq@typeset@RB{%
1410   % NOTE: is \eq@dp useful here
1411   \setlength\dim@a{\eq@vspan-\ht\EQ@numbox-\dp\EQ@numbox}%

```

```

1412 \eq@typeset@rightnumber
1413 \eq@typeset@frame
1414 \eq@typeset@equation
1415 }

```

Typeset equation and right shifted number

```

1416 \def\eq@typeset@RShifted{%
1417 % place number
1418 \eq@typeset@frame
1419 \eq@typeset@equation
1420 \penalty\@M
1421 \dim@a\eqlineskip
1422 \if F\eq@frame\else
1423 \addtolength\dim@a{\eq@framesep+\eq@framewd}%
1424 \fi
1425 \parskip\dim@a
1426 \hbox to\hsize{\hfil\copy\EQ@numbox}\@@par%
1427 }

```

Debugging aid to show all relevant formatting info for a given eqn.

```

1428 <*trace>
1429 \def\debug@showformat{%
1430 \breqn@debugmsg{Formatting Layout:\eq@layout\space Center/indent: \eqindent\space
1431 Number placement \eqnumside\eqnumplace:
1432 \MessageBreak==== \eq@linewidth=\the\eq@linewidth, \@totalleftmargin=\the\@totalleftmargin,
1433 \MessageBreak==== Centered Lines=\theb@@le\eq@centerlines, Shift Number=\theb@@le\eq@shiftn
1434 \MessageBreak==== \eq@wdT=\the\eq@wdT, \eq@wdMin=\the\eq@wdMin,
1435 \MessageBreak==== LHS=\theb@@le\EQ@hasLHS: \eq@wdL=\the\eq@wdL,
1436 \MessageBreak==== \eq@firstht=\the\eq@firstht, \eq@vspan=\the\eq@vspan
1437 \MessageBreak==== \eq@wdNum=\the\eq@wdNum
1438 \MessageBreak==== \eq@wdCond=\the\eq@wdCond, \conditionsep=\the\conditionsep,
1439 \MessageBreak==== \leftskip=\the\leftskip, \rightskip=\the\rightskip,
1440 \MessageBreak==== \abovedisplayskip=\the\abovedisplayskip,
1441 \MessageBreak==== \belowdisplayskip=\the\belowdisplayskip
1442 \MessageBreak==== parshape=\eq@parshape}%
1443 }
1444 </trace>

```

Set left & right skips for centered equations, making allowances for numbers (if any, right, left) and constraint.

Amazingly, I've managed to collect all the positioning logic for centered equations in one place, so it's more manageable. Unfortunately, by the time it does all it needs to do, it has evolved I'm (re)using so many temp variables, it's becoming unmanageable!

```

1445 \def\eq@C@setsides{%
1446 % \dim@c = space for number, if any, and not shifted.
1447 \dim@c\z@
1448 \if\eq@hasNumber\if\eq@shiftnumber\else
1449 \dim@c\eq@wdNum
1450 \fi\fi

```

```

1451 % \dim@e = space for condition(on right), if any and formula is only a single line.(to center
1452 % but only count it as being right-aligned if we're not framing, since the frame must enclose
1453 \dim@e\z@
1454 \if F\eq@frame
1455   \ifnum\eq@lines=\@ne\ifdim\eq@wdCond>\z@
1456     \setlength\dim@e{\eq@wdCond+\conditionsep}%
1457 \fi\fi\fi
1458 % \dim@b = minimum needed on left max(totalleftmargin, left number space)
1459 \dim@b\z@
1460 \if L\eqnumside\ifdim\dim@b<\dim@c
1461   \dim@b\dim@c
1462 \fi\fi
1463 \ifdim\dim@b<\totalleftmargin
1464   \dim@b\z@
1465 \else
1466   \addtolength\dim@b{-\totalleftmargin}%
1467 \fi
1468 % \dim@d = minimum needed on right max(condition, right number space)
1469 \dim@d\dim@e
1470 \if R\eqnumside\ifdim\dim@d<\dim@c
1471   \dim@d\dim@c
1472 \fi\fi
1473 % \dim@a = left margin; initially half available space
1474 % \dim@c = right margin; ditto
1475 \setlength\dim@a{(\eq@linewidth-\eq@wdT+\dim@e+\totalleftmargin)/2}%
1476 \dim@c=\dim@a
1477 % If too far to the left
1478 \ifdim\dim@a<\dim@b
1479   \addtolength\dim@c{\dim@a-\dim@b}%
1480   \ifdim\dim@c<\z@\dim@c=\z@\fi
1481   \dim@a=\dim@b
1482 % Or if too far to the right
1483 \else\ifdim\dim@c<\dim@d
1484   \addtolength\dim@a{\dim@c-\dim@d}%
1485   \ifdim\dim@a<\z@\dim@a=\z@\fi
1486   \dim@c=\dim@d
1487 \fi\fi
1488 % Now, \dim@d,\dim@e is the left & right glue to center each line for centerlines
1489 \setlength\dim@e{\eq@wdT-\eq@wdMin}\dim@d=\z@

```

NOTE: Need some work here centering when there's a condition

```

1490 % \advance\dim@e-\eq@wdT\multiply\dim@e-1\relax
1491 % \if\eq@wdMin<\dim@e\dim@e\eq@wdMin\fi
1492 % \multiply\dim@e-1\relax\advance\dim@e\eq@wdT
1493 \dim@d\z@
1494 \if\eq@centerlines
1495   \divide\dim@e2\relax
1496   \dim@d=\dim@e
1497 \fi
1498 \setlength\leftskip{\dim@a\@plus\dim@d}%

```

```

1499 \addtolength\dim@e{\dim@c}%
1500 \setlength\rightskip{\z@\@plus\dim@e%\@minus5\p@
1501 % Special case: if framing, reduce the stretchiness of the formula (eg. condition)
1502 % Or if we have a right number, FORCE space for it
1503 \dim@b\z@
1504 \if F\eq@frame\else
1505   \dim@b\dim@c
1506 \fi
1507 \if\@And{\eq@hasNumber}{\@Not{\eq@shiftnumber}}}%
1508   \if R\eq@numside
1509     \dim@c\eq@wdNum
1510     \ifdim\dim@c>\dim@b
1511       \dim@b\dim@c
1512     \fi
1513   \fi
1514 \fi
1515 % If either of those cases requires hard rightskip, move that part from glue.
1516 \ifdim\dim@b>\z@
1517   \addtolength\dim@e{-\dim@c}%
1518   \rightskip\dim@b\@plus\dim@e%\@minus5\p@
1519 \fi
1520 % And peculiar further special case: in indented environs, width isn't where it would seem
1521 \ifdim\eq@wdCond>\z@
1522   \addtolength\rightskip{-\@totalleftmargin}%
1523 \fi
1524 \parfillskip\z@skip
1525 }

```

Set the left and right side spacing for indented equations Some things handled by eq@C@setsides that probably apply here????

- centerlines
- \@totalleftmargin: SHOULD we move farther right?

Leftskip is normally just the requested indentation

```

1526 \def\eq@I@setsides{%
1527   \leftskip\mathindent

```

But move left, if shifted number presumably because of clashed w/ number?

```

1528   \if\eq@shiftnumber
1529     \setlength\dim@a{\eq@linewidth-\eq@wdT-\mathindent}%
1530     \ifdim\dim@a<\z@
1531       \leftskip=\z@ % Or something minimal?
1532     \fi
1533   \fi

```

Push gently from right.

```

1534   \dim@a=\z@
1535   \setlength\dim@b{\eq@linewidth-\leftskip-\eq@wdMin}%

```

Special case: if framing be much more rigid(?)

```

1536 \if F\eq@frame
1537 \else
1538   \setlength\dim@a{\eq@linewidth-\leftskip-\eq@wdT}
1539   \addtolength\dim@b{-\dim@a}%
1540 \fi
1541 % Or force the space for right number, if needed
1542 % \begin{macrocode}
1543 \if\@And{\eq@hasNumber}{\@Not{\eq@shiftnumber}}}%
1544   \if R\eqnumside
1545     \dim@c=\eq@wdNum
1546     \if\dim@c>\dim@a
1547       \addtolength\dim@b{-\dim@c}%
1548       \dim@a=\dim@c
1549   \fi
1550 \fi
1551 \fi
1552 \setlength\rightskip{\dim@a\@plus\dim@b \@minus\hfuzz }%\hfuzz\z@
1553 \parfillskip\z@skip
1554 }

```

**Typesetting pieces: frame, equation and number (if any)** \dim@a should contain the downward displacement of number's baseline

```

1555 \def\eq@typeset@leftnumber{%
1556   \setlength\skip@c{\dim@a-\ht\EQ@numbox}%
1557   \vglue\skip@c% NON discardable
1558   \copy\EQ@numbox \penalty\@M
1559   \kern-\dim@a
1560 }
1561 \def\eq@typeset@rightnumber{%
1562   \setlength\skip@c{\dim@a-\ht\EQ@numbox}%
1563   \vglue\skip@c% NON discardable
1564   \hbox to \hsize{\hfil\copy\EQ@numbox}\penalty\@M
1565   \kern-\dim@a
1566 }
1567 \def\eq@typeset@equation{%
1568   \nobreak
1569   \eq@params\eq@parshape
1570   \nointerlineskip\noindent
1571   \add@grp@label
1572   \eq@dump@box\unhbox\EQ@box\@@par
1573 }

```

## 30 Framing an equation

**\eqframe** The `\eqframe` function is called in vertical mode with the reference point at the top left corner of the equation, including any allowance for `\fboxsep`. Its arguments

are the width and height of the equation body, plus fboxsep.

```

1574 \newcommand\eqframe[2]{%
1575   \begingroup
1576   \fboxrule=\eq@framewd\relax\fboxsep=\eq@framesep\relax
1577   \framebox{\z@rule\@height#2\kern#1}%
1578   \endgroup
1579 }

```

The frame is not typeset at the correct horizontal position. Will fix later.

```

1580 \def\eq@addframe{%
1581   \hbox to\z@{%
1582     \setlength\dim@a{\eq@framesep+\eq@framewd}%
1583     \kern-\dim@a
1584     \vbox to\z@{\kern-\dim@a
1585       \hbox{\eqframe{\eq@wdT}{\eq@vspan}}}%
1586     \vss
1587   }%
1588   \hss
1589 }%
1590 }
1591 \def\eq@typeset@frame{%
1592   \if F\eq@frame\else
1593     % Tricky: put before \noindent, so it's not affected by glue in \leftskip
1594     \nobreak\nointerlineskip
1595     \vbox to\eq@firstht{\moveright\leftskip\hbox to\z@{\eq@addframe\hss}\vss}%
1596     \kern-\eq@firstht
1597   \fi
1598 }

```

## 31 Delimiter handling

The special handling of delimiters is rather complex, but everything is driven by two motives: to mark line breaks inside delimiters as less desirable than line breaks elsewhere, and to make it possible to break open left-right boxes so that line breaks between `\left` and `\right` delimiters are not absolutely prohibited. To control the extent to which line breaks will be allowed inside delimiters, set `\eqbreakdepth` to the maximum nesting depth. Depth 0 means never break inside delimiters.

Note: `\eqbreakdepth` is not implemented as a L<sup>A</sup>T<sub>E</sub>X counter because changes done by `\setcounter` etc. are always global.

It would be natural to use grouping in the implementation—at an open delimiter, start a group and increase mathbin penalties; at a close delimiter, close the group. But this gives us trouble in situations like the `array` environment, where a close delimiter might fall in a different cell of the `\halign` than the open delimiter. Ok then, here's what we want the various possibilities to expand to. Note that `\right` and `\biggr` are being unnaturally applied to a naturally open-type delimiter.

```

( -> \delimiter"4... \after@open
\left( ->
  \@@left \delimiter"4... \after@open
\right( ->
  \@@right \delimiter"4... \after@close
\biggl( ->
  \mathopen{\@@left \delimiter... \vrule... \@@right.}
  \after@open
\biggr( ->
  \mathclose{\@@left \delimiter... \vrule... \@@right.}
  \after@close
\bigg\vert ->
  \mathord{\@@left \delimiter... \vrule... \@@right.}
\biggm\vert ->
  \mathrel{\@@left \delimiter... \vrule... \@@right.}

```

First save the primitive meanings of `\left` and `\right`.

```

1599 \saveprimitive\left\@@left
1600 \saveprimitive\right\@@right

```

The variable `\lr@level` is used by the first `\mathrel` in an equation to tell whether it is at top level: yes? break and measure the LHS, no? keep going.

```

1601 \newcount\lr@level

```

It would be nice to have better error checking here if the argument is not a delimiter symbol at all.

```

1602 \def\eq@left{%
1603   \ifnext .{\eq@nullleft}{\begingroup \let\delimiter\eq@left@a}%
1604 }
1605 \def\eq@right{%
1606   \ifnext .{\eq@nullright}{\begingroup \let\delimiter\eq@right@a}%
1607 }

```

The arguments are: #1 delim symbol, #2 .

```

1608 \def\eq@left@a#1 #2{\endgroup\@@left\delimiter#1 \after@open}
1609 \def\eq@right@a#1 #2{\endgroup
1610   \@@right\delimiter#1 \after@close \ss@scan{#1}%
1611 }

```

The null versions.

```

1612 \def\eq@nullleft#1{\@@left#1\after@open}
1613 \def\eq@nullright#1{\@@right#1\after@close}

```

Here is the normal operation of `\biggl`, for example.

```

\biggl -> \mathopen \bigg
{\mathopen}

```

```

\bigg #1->{\hbox {$\left #1\ vbox to14.5\p@ {} \right .\n@space $}}
#1<-(

```

For paren matching: ) Like `\left`, `\biggl` coerces its delimiter to be of `mathopen` type even if its natural inclination is towards closing.

The function `\delim@reset` makes delimiter characters work just about the same as they would in normal L<sup>A</sup>T<sub>E</sub>X.

```

1614 \def\delim@reset{%
1615   \let\after@open\relax \let\after@close\relax
1616   \let\left@@\left \let\right@@\right
1617 }

If the amsmath or exscale package is loaded, it will have defined \bBigg@; if not,
the macros \big and variants will have hard-coded point sizes as inherited through
the ages from plain.tex. In this case we can kluge a little by setting \big@size
to \p@, so that our definition of \bBigg@ will work equally well with the different
multipliers.

1618 \@ifundefined{bBigg@}{% not defined
1619   \let\big@size\p@
1620   \def\big{\bBigg@{8.5}}\def\Big{\bBigg@{11.5}}%
1621   \def\bigg{\bBigg@{14.5}}\def\Bigg{\bBigg@{17.5}}%
1622   \def\biggg{\bBigg@{20.5}}\def\Biggg{\bBigg@{23.5}}%
1623 }{}
1624 \def\bBigg@#1#2{%
1625   {\delim@reset
1626     \left#2%
1627     \vrule\@height#1\big@size\@width-\nulldelimiterspace
1628     \right.
1629   }%
1630 }

.

1631 \def\bigl#1{\mathopen\big{#1}\after@open}
1632 \def\Bigl#1{\mathopen\Big{#1}\after@open}
1633 \def\biggl#1{\mathopen\bigg{#1}\after@open}
1634 \def\Biggl#1{\mathopen\Bigg{#1}\after@open}
1635 \def\bigggl#1{\mathopen\biggg{#1}\after@open}
1636 \def\Bigggl#1{\mathopen\Biggg{#1}\after@open}
1637
1638 \def\bigr#1{\mathclose\big{#1}\after@close}
1639 \def\Bigr#1{\mathclose\Big{#1}\after@close}
1640 \def\biggr#1{\mathclose\bigg{#1}\after@close}
1641 \def\Biggr#1{\mathclose\Bigg{#1}\after@close}
1642 \def\bigggr#1{\mathclose\biggg{#1}\after@close}
1643 \def\Bigggr#1{\mathclose\Biggg{#1}\after@close}
1644
1645 %% No change needed, I think. [mjd,1998/12/04]
1646 %%\def\bigm{\mathrel\big}
1647 %%\def\Bigm{\mathrel\Big}
1648 %%\def\biggm{\mathrel\bigg}
1649 %%\def\Biggm{\mathrel\Bigg}
1650 %%\def\bigggm{\mathrel\biggg}
1651 %%\def\Bigggm{\mathrel\Biggg}

```



\m@@DeL Original definition of \m@DeL from flexisym is as follows. \m@DeR and \m@DeB are the same except for the math class number.

```
\m@@DeR \def\m@DeL#1#2#3{%
\d@@DeR \delimiter"4\@xp\delim@a\csname sd@#1#2#3\endcsname #1#2#3 }
\m@@DeB Save the existing meanings of \m@De[LRB].
```

```
1652 \let\m@@DeL\m@DeL \let\m@@DeR\m@DeR \let\m@@DeB\m@DeB
1653 \def\d@@DeL#1#2#3{%
1654 \delimiter"4\@xp\delim@a\csname sd@#1#2#3\endcsname #1#2#3 \after@open
1655 }
1656 \def\d@@DeR#1#2#3{%
1657 \delimiter"5\@xp\delim@a\csname sd@#1#2#3\endcsname #1#2#3 \after@close
1658 }
1659 \def\d@@DeB#1#2#3{%
1660 \delimiter"0\@xp\delim@a\csname sd@#1#2#3\endcsname #1#2#3 \after@bidir
1661 }
```

BRM: These weren't defined, but apparently should be. Are these the right values???

```
1662 \let\m@@DeA\m@DeA\let\d@@DeA\m@DeA%
```

\after@open \after@open and \after@close are carefully written to avoid the use of grouping and to run as fast as possible. \zero@bop is the value used for \prebinoppenalty at delimiter level 0, while \bop@incr is added for each level of nesting. The standard values provide that breaks will be prohibited within delimiters below nesting level 2.

```
1663 \let\after@bidir\@empty
1664 \mathchardef\zero@bop=888 \relax
1665 \mathchardef\bop@incr=4444 \relax
1666 \def\after@open{%
1667 \global\advance\lr@level\@ne
1668 \prebinoppenalty\bop@incr \multiply\prebinoppenalty\lr@level
1669 \advance\prebinoppenalty\zero@bop
1670 \ifnum\eqbreakdepth<\lr@level
1671 \let\m@Bin\m@@Bin
```

Inside delimiters, add some fillglue before binops so that a broken off portion will get thrown flush right. Also shift it slightly further to the right to ensure that it clears the opening delimiter.

```
1672 \else
1673 \eq@binoffset=\eqbinoffset
1674 \advance\eq@binoffset\lr@level\eqdelimoffset plus1fill\relax
1675 \def\dt@fill@cancel{\hskip\z@ minus1fill\relax}%
1676 \fi
1677 \penalty\@M % BRM: discourage break after an open fence?
1678 }
1679 \def\after@close{%
1680 \global\advance\lr@level\m@ne
1681 \prebinoppenalty\bop@incr \multiply\prebinoppenalty\lr@level
```

```

1682 \advance\prebinoppenalty\zero@bop
1683 \ifnum\eqbreakdepth<\lr@level
1684 \else \let\m@Bin\d@Bin
1685 \fi

```

When we get back to level 0, no delimiters, remove the stretch component of `\eqbinoffset`.

```

1686 \ifnum\lr@level<\@ne \eq@binoffset=\eqbinoffset\relax \fi
1687 }

```

`\subsup@flag` `\ss@scan` is called after a `\right` delimiter and looks ahead for sub and superscript tokens. If sub and/or superscripts are present, we adjust the line-ending penalty to distinguish the various cases (sub, sup, or both). This facilitates the later work of excising the sub/sup box and reattaching it with proper shifting.

Sub/Superscript measurement

BRM: There's possibly a problem here. When `\ss@scan` gets invoked after a `\left...\right` pair in the LHS during `\eq@measure`, it produces an extra box (marked with `\penalty 3`); Apparently `\eq@repack` expects only one for the LHS. The end result is `\eq@wdL = 0.0pt !!!` (or at least very small)

```

1688 \let\subsup@flag=\count@
1689 \def\ss@delim@a#1#2#3#4{\xdef\right@delim@code{\number"#2#3#4}}

```

The argument of `\ss@scan` is an expanded form of a right-delimiter macro. We want to use the last three digits in the expansion to define `\right@delim@code`. The assignment to a temp register is just a way to scan away the leading digits that we don't care about.

```

1690 \def\ss@scan#1{%

```

This part of the code.

```

1691 \begingroup
1692 \let\delim@a\ss@delim@a \@tempcnta#1\relax
1693 \endgroup
1694 \subsup@flag\@M \afterassignment\ss@scan@a \let\@let@token=}
1695 \def\ss@scan@a{%
1696 \ifx\@let@token\sb \advance\subsup@flag\@ne\else
1697 \ifx\@let@token\sp \advance\subsup@flag\tw\else
1698 \ss@finish
1699 \expandafter\@firstoftwo % gobble \ss@scan@b
1700 \fi\fi
1701 \ss@scan@b\@let@token
1702 }

```

```

1703 \def\ss@scan@b#1#2{#1{%

```

hack! coff!

```

1704 \let\m@Bin\m@Bin \let\m@Rel\m@Rel
1705 #2}\afterassignment\ss@scan@a \let\@let@token=}%

```

We need to keep following glue from disappearing—e.g., a `thickmuskip` or `medmuskip` from a following `mathrel` or `mathbin` symbol.

```

1706 \def\ss@finish{%

```

```

1707 \@@vadjust{\penalty\thr@@}%
1708 \penalty\right@delim@code \penalty-\subsup@flag \keep@glue
1709 }

```

`\eq@lrunpack` For `\eq@lrunpack` we need to break open a left-right box and reset it just in case it contains any more special breaks. After it is unpacked the recursion of `\eq@repack` will continue, acting on the newly created lines.

```

1710 \def\eq@lrunpack{\setbox\z@\lastbox

```

We remove the preceding glue item and deactivate baselineskip for the next line, otherwise we would end up with three items of glue (counting parskip) at this point instead of the single one expected by our recursive repacking procedure.

```

1711 \unskip \nointerlineskip

```

Then we open box 0, take the left-right box at the right end of it, and break that open. If the line-ending penalty is greater than 10000, it means a sub and/or superscript is present on the right delimiter and the box containing them must be taken off first.

```

1712 \noindent\unhbox\z@ \unskip
1713 \subsup@flag-\lastpenalty \unpenalty
1714 \xdef\right@delim@code{\number\lastpenalty}%
1715 \unpenalty
1716 \ifnum\subsup@flag>\@M
1717 \advance\subsup@flag-\@M
1718 \setbox\tw@\lastbox
1719 \else \setbox\tw@\box\voidb@x
1720 \fi
1721 \setbox\z@\lastbox
1722 \ifvoid\tw@ \unhbox\z@
1723 \else \lrss@reattach % uses \subsup@flag, box\z@, box\tw@
1724 \fi

```

The reason for adding a null last line here is that the last line will contain parfillskip in addition to rightskip, and a final penalty of 10000 instead of  $-1000N$  ( $1 \leq N \leq 9$ ), which would interfere with the usual processing. Setting a null last line and discarding it dodges this complication. The penalty value  $-10001$  is a no-op case in the case statement of `\eq@repacka`.

```

1725 \penalty-\@Mi\z@rule\@@par
1726 \setbox\z@\lastbox \unskip\unpenalty
1727 %%\showboxbreadth\maxdimen\showboxdepth99\showlists}%
1728 }

```

`\lrss@reattach` Well, for a small self-contained computation, carefully hand-allocated `dimens` should be safe enough. But let the maintainer beware! This code cannot be arbitrarily transplanted or shaken up without regard to grouping and interaction with other hand-allocated `dimens`.

```

1729 \dimendef\sub@depth=8 \dimendef\sup@base=6
1730 \dimendef\prelim@sub@depth=4 \dimendef\prelim@sup@base=2
1731 \def\sym@xheight{\fontdimen5\textfont\tw@}

```

```

1732 \def\sup@base@one{\fontdimen13\textfont\tw@}
1733 \def\sub@base@one{\fontdimen16\textfont\tw@}
1734 \def\sub@base@two{\fontdimen17\textfont\tw@}

```

Note that only `\sup@drop` and `\sub@drop` come from the next smaller math style.

```

1735 \def\sup@drop{\fontdimen18\scriptfont\tw@}
1736 \def\sub@drop{\fontdimen19\scriptfont\tw@}

```

Provide a mnemonic name for the math axis fontdimen, if it's not already defined.

```

1737 \providecommand{\mathaxis}{\fontdimen22\textfont\tw@}

```

Assumes box 2 contains the sub/sup and box 0 contains the left-right box. This is just a repeat of the algorithm in `tex.web`, with some modest simplifications from knowing that this is only going to be called at top level in a displayed equation, thus always `mathstyle = uncramped displaystyle`.

```

1738 \def\lrss@reattach{%
1739   \begingroup
1740   % "The TeXbook" Appendix G step 18:
1741   \setlength\prelim@sup@base{\ht\z@-\sup@drop}%
1742   \setlength\prelim@sub@depth{\dp\z@ +\sub@drop}%
1743   \unhbox\z@
1744   \ifcase\subsup@flag      % case 0: this can't happen
1745   \or \lr@subscript      % case 1: subscript only
1746   \or \lr@superscript    % case 2: superscript only
1747   \else \lr@subsup      % case 3: sub and superscript both
1748   \fi
1749   \endgroup
1750 }

1751 \def\lr@subscript{%
1752   \sub@depth\sub@base@one
1753   \ifdim\prelim@sub@depth>\sub@depth \sub@depth\prelim@sub@depth\fi
1754   \setlength\dim@a{\ht\tw@ -.8\sym@xheight}%
1755   \ifdim\dim@a>\sub@depth \sub@depth=\dim@a \fi
1756   \twang@adjust\sub@depth
1757   \lower\sub@depth\box\tw@
1758 }

1759 \def\lr@superscript{%
1760   \sup@base\sup@base@one
1761   \ifdim\prelim@sup@base>\sup@base \sup@base\prelim@sup@base\fi
1762   \setlength\dim@a{\dp\tw@ -.25\sym@xheight}%
1763   \ifdim\dim@a>\sup@base \sup@base=\dim@a \fi
1764   \twang@adjust\sup@base
1765   \raise\sup@base\box\tw@
1766 }

1767 \def\lr@subsup{%
1768   \sub@depth\sub@base@two
1769   \ifdim\prelim@sub@depth>\sub@depth \sub@depth\prelim@sub@depth \fi
1770   \twang@adjust\sub@depth
1771   \lower\sub@depth\box\tw@
1772 }

```

For delimiters that curve top and bottom, the twang factor allows horizontal shifting of the sub and superscripts so they don't fall too far away (or too close for that matter). This is accomplished by arranging for (e.g.,) `\right\rrss@reattach` to leave a penalty  $N$  in the math list before the subsup penalty that triggers `\rrss@reattach`, where  $N$  is the mathcode of `\rangle` (ignoring “small” variant).

```

1773 \def\twang@adjust#1{%
1774   \begingroup
1775   \ifundefined{twang@right@delim@code}{\{%
1776     \setlength\dim@d{#1-\mathaxis}%
1777     % put an upper limit on the adjustment
1778     \ifdim\dim@d>1em \dim@d 1em \fi
1779     \kern\csname twang@right@delim@code\endcsname\dim@d
1780   }%
1781 \endgroup
1782 }
```

The method used to apply a “twang” adjustment is just an approximate solution to a complicated problem. We make the following assumptions that hold true, approximately, for the most common kinds of delimiters:

1. The right delimiter is symmetrical top to bottom.
2. There is an upper limit on the size of the adjustment.
3. When we have a superscript, the amount of left-skew that we want to apply is linearly proportional to the distance of the bottom left corner of the superscript from the math axis, with the ratio depending on the shape of the delimiter symbol.

. By symmetry, Assumption 3 is true also for subscripts (upper left corner). Assumption 2 is more obviously true for parens and braces, where the largest super-extended versions consist of truly vertical parts with slight bending on the ends, than it is for a `\rangle`. But suppose for the sake of expediency that it is approximately true for range symbols also.

Here are some passable twang factors for the most common types of delimiters in `cmex10`, as determined by rough measurements from magnified printouts.

```

vert bar, double vert: 0
square bracket: -.1
curly brace: -.25
parenthesis: -.33
rangle: -.4
```

Let's provide a non-private command for changing the twang factor of a given symbol.

```

1783 \newcommand{\DeclareTwang}[2]{%
1784   \ifcat.\@nx#1\begingroup
1785     \lccode'\~='#1\lowercase{\endgroup \DeclareTwang{\~}{#2}}%
1786   \else
1787     \@xp\decl@twang#1?\@nil{#2}%
```

```

1788 \fi
1789 }

```

Note that this is dependent on a fixed interpretation of the mathgroup number #4 .

```

1790 \def\decl@twang#1#2#3#4#5#6#7\@nil#8{%
1791 \namedef{twang@number"#4#5#6}{#8}%
1792 }
1793 \DeclareTwang{\rangle}{-.4}
1794 \DeclareTwang{)}{-.33}
1795 \DeclareTwang{\rbrace}{-.25}

```

## 32 Series of expressions

The `dseries` environment is for a display containing a series of expressions of the form ‘A, B’ or ‘A and B’ or ‘A, B, and C’ and so on. Typically the expressions are separated by a double quad of space. If the expressions in a series don’t all fit in a single line, they are continued onto extra lines in a ragged-center format.

```

1796 \newenvironment{dseries}{\let\eq@hasNumber\@True \optarg@dseries{}}{%
1797 \def\endseries#1{\check@punct@or@qed}%

```

And the unnumbered version of same.

```

1798 \newenvironment{dseries*}{\let\eq@hasNumber\@False \optarg@dseries{}}{%
1799 \namedef{endseries*}#1{\check@punct@or@qed}%
1800 \namedef{end@dseries*}{\end@dseries}%
1801 \def\@dseries[#1]{%

```

Turn off the special breaking behavior of `mathrels` etc. for math formulas embedded in a `dseries` environment.

BRM: DS Expermient: Use alternative display setup.

```

1802 % \def\display@setup{\displaystyle}%
1803 \let\display@setup\dseries@display@setup
1804 % Question: should this be the default for dseries???
1805 % \let\eq@centerlines\@True
1806 \global\eq@wdCond\z@

```

BRM: use special layout for `dseries`

```

1807 % \@dmath[#1]%
1808 \@dmath[layout={M},#1]%
1809 \mathsurround\z@\@math \penalty\@Mi
1810 \let\endmath\ends@math
1811 \def\premath{%

```

BRM: Tricky to cleanup space OR add space ONLY BETWEEN math!

```

1812 \ifdim\lastskip<.3em \unskip
1813 \else\ifnum\lastpenalty<\@M \dquad\fi\fi
1814 }%

```

BRM: Tricky; if a subformula breaks, we’d like to start the next on new line!

```

1815 \def\postmath{\unpenalty\eq@addpunct \penalty\intermath@penalty \dquad \@ignoretrue}%

```

```

1816 \ignorespaces
1817 }
1818 \def\end@dseries{%
1819   \unskip\unpenalty
1820   \@@endmath \mathsurround\z@ \end@dmath
1821 }

```

BRM: Try this layout for dseries: Essentially layout i, but w/o limit to 1 line. And no fallback!

```

1822 \def\eq@try@layout@M{%
1823   \edef\@parshape{\parshape 1 0pt \the\eq@linewidth\relax}%
1824   \eq@trial@b{M}{}%
1825 }

```

BRM: Tricky to get right value here. Prefer breaks between formula if we've got to break at all.

```

1826 %\def\intermath@penalty{-201}%
1827 \def\intermath@penalty{-221}%

```

BRM: A bit tighter than it was ( 1em minus.25em )

```

1828 %\newcommand\dquad{\hskip0.4em}
1829 \newcommand\dquad{\hskip0.6em minus.3em}
1830 \newcommand\premath{}\newcommand\postmath{}

```

Change the math environment to add `\premath` and `\postmath`. They are no-ops except inside a `dseries` environment.

Redefinition of math environment to take advantage of dseries env.

```

1831 \renewenvironment{math}{%
1832   \leavevmode \premath
1833   \ifmmode\@badmath\else\@@math\fi
1834 }{%
1835   \ifmmode\@@endmath\else\@badmath\fi
1836 }
1837 \def\ends@math#1{\check@punct@or@qed}
1838 \def\end@math{%
1839   \ifmmode\@@endmath\else\@badmath\fi
1840   \postmath
1841 }

```

### 33 Equation groups

For many equation groups the strategy is easy: just center each equation individually following the normal rules for a single equation. In some groups, each equation gets its own number; in others, a single number applies to the whole group (and may need to be vertically centered on the height of the group). In still other groups, the equations share a parent number but get individual equation numbers consisting of parent number plus a letter.

If the main relation symbols in a group of equations are to be aligned, then the final alignment computations cannot be done until the end of the group—i.e.,

the horizontal positioning of the first  $n - 1$  equations cannot be done immediately. Yet because of the automatic line breaking, we cannot calculate an initial value of RHS-max over the whole group unless we do a trial run on each equation first to find an RHS-max for that equation. Once we know RHS-group-max and LHS-group-max we must redo the trial set of each equation because they may affect the line breaks. If the second trial for an equation fails (one of its lines exceeds the available width), but the first one succeeded, fall back to the first trial, i.e., let that equation fall out of alignment with the rest of the group.

All right then, here is the general idea of the whole algorithm for group alignment. To start with, ignore the possibility of equation numbers so that our equation group has the form:

```
LHS[1] RHS[1,1] RHS[1,2] ... RHS[1,n[1]]
LHS[2] RHS[2,1] RHS[2,2] ... RHS[2,n[2]]
...
LHS[3] RHS[3,1] RHS[3,2] ... RHS[3,n[3]]
```

The number of RHS's might not be the same for all of the equations. First, accumulate all of the equation contents in a queue, checking along the way to find the maximum width of all the LHS's and the maximum width of all the RHS's. Call these widths maxwd\_L and maxwd\_R. Clearly if maxwd\_L + maxwd\_R is less than or equal to the available equation width then aligning all of the equations is going to be simple.

Otherwise we are going to have to break at least one of the RHS's and/or at least one of the LHS's. The first thing to try is using maxwd\_L for the LHS's and breaking all the RHS's as needed to fit in the remaining space. However, this might be a really dumb strategy if one or more of the LHS's is extraordinarily wide. So before trying that we check whether maxwd\_L exceeds some threshold width beyond which it would be unsensible not to break the LHS. Such as, max(one-third of the available width; six ems), or something like that. Or how about this? Compare the average LHS width and RHS width and divide up the available width in the same ratio for line breaking purposes.

BRM: Fairly broad changes; it mostly didn't work before (for me).

**`\begin{dgroup}` produces a 'numbered' group** The number is the next equation number. There are 2 cases:

- If ANY contained equations are numbered (`\begin{dmath}`), then they will be subnumbered: eg 1.1a and the group number is not otherwise displayed.
- If ALL contained equations are unnumbered (`\begin{dmath*}`) then the group, as a whole, gets a number displayed, using the same number placement as for equations.

**`\begin{dgroup*}` produces an unnumbered group.** Contained equations are numbered, or not, as normal. But note that in the mixed case, it's too late to force the unnumbered eqns to `\retry@with@number` We'll just do a simple check of dimensions, after the fact, and force a shiftnumber if we're stuck.



NOTE: Does this work for dseries, as well? (alignment?)

NOTE: Does \label attach to the expected thing?

**For number placement** We use shiftnumber placement on ALL equations if ANY equations need it, or if an unnumbered equation is too wide to be aligned, given that the group or other eqns are numbered. [does this latter case interact with the chosen alignment?]

**For Alignment** As currently coded, it tries to align on relations, by default. If LHS's are not all present, or too long, it switches to left-justify. Maybe there are other cases that should switch? Should there be a case for centered?

NOTE: Should there be some options to choose alignment?

\eq@group

```
\GRP@top 1842 \let\eq@group\@False
1843 \let\grp@shiftnumber\@False
1844 \let\grp@hasNumber\@False
1845 \let\grp@eqs@numbered\@False
1846 \let\grp@aligned\@True
```

Definition of the dgroup environment.

```
1847 \newenvironment{dgroup}{%
1848 \let\grp@hasNumber\@True\@optarg@dgroup}%
1849 }{%
1850 \end@dgroup
1851 }
```

And the.

```
1852 \newtoks\GRP@queue
1853 \newenvironment{dgroup*}{%
1854 \let\grp@hasNumber\@False\@optarg@dgroup}%
1855 }{%
1856 \end@dgroup
1857 }
1858 \def\@dgroup[#1]{%
1859 <trace> \breqn@debugmsg{=== DGROUP =====}%
1860 \let\eq@group\@True \global\let\eq@GRP@first@dmath\@True
1861 \global\GRP@queue\@emptytoks \global\setbox\GRP@box\box\voidb@x
1862 \global\let\GRP@label\@empty
1863 \global\grp@wdL\z@\global\grp@wdR\z@\global\grp@wdT\z@
1864 \global\grp@linewidth\z@\global\grp@wdNum\z@
1865 \global\let\grp@eqs@numbered\@False
1866 \global\let\grp@aligned\@True
1867 \global\let\grp@shiftnumber\@False
1868 \eq@prelim
1869 \setkeys{breqn}{#1}%
1870 \if\grp@hasNumber \grp@setnumber \fi
1871 }
1872 \def\end@dgroup{%
```

```

1873 \EQ@displayinfo \grp@finish
1874 \if\grp@hasNumber\grp@resetnumber\fi
1875 }

```

If the amsmath package is not loaded the parentequation counter will not be defined.

```

1876 \@ifundefined{c@parentequation}{\newcounter{parentequation}}{}

```

Init.

```

1877 \global\let\GRP@label\@empty
1878 \def\add@grp@label{%
1879   \ifx\@empty\GRP@label
1880   \else \GRP@label \global\let\GRP@label\@empty
1881   \fi
1882 }

```

Before sending down the ‘equation’ counter to the subordinate level, set the current number in \EQ@numbox. The \eq@setnumber function does everything we need here. If the child equations are unnumbered, \EQ@numbox will retain the group number at the end of the group.

```

1883 \def\grp@setnumber{%
1884   \global\let\GRP@label\next@label \global\let\next@label\@empty
1885   % Trick \eq@setnumber to doing our work for us.
1886   \let\eq@hasNumber\@True
1887   \eq@setnumber

```

Define \theparentequation equivalent to current \theequation. \edef is necessary to expand the current value of the equation counter. This might in rare cases cause something to blow up, in which case the user needs to add \protect.

```

1888   \global\sbox\GRP@numbox{\unhbox\EQ@numbox}%
1889   \grp@wdNum\eq@wdNum
1890   \let\eq@hasNumber\@False
1891   \let\eq@number\@empty
1892   \eq@wdNum\z@
1893   %
1894   \protected@edef\theparentequation{\theequation}%
1895   \setcounter{parentequation}{\value{equation}}%

```

And set the equation counter to 0, so that the normal incrementing processes will produce the desired results if the child equations are numbered.

```

1896   \setcounter{equation}{0}%
1897   \def\theequation{\theparentequation\alph{equation}}%
1898   <trace> \breqn@debugmsg{Group Number \theequation}%
1899 }

```

At the end of a group, need to reset the equation counter.

```

1900 \def\grp@resetnumber{%
1901   \setcounter{equation}{\value{parentequation}}%
1902 }
1903 \newbox\GRP@box
1904 \newbox\GRP@wholebox

```

Save data for this equation in the group

- push the trial data onto end of `\GRP@queue`.
- push an hbox onto the front of `\GRP@box` containing: `\EQ@box`, `\EQ@copy`, `\penalty 1` and `\EQ@numbox`.

`\grp@push` For putting the equation on a queue.

```

1905 \def\grp@push{%
1906   \global\GRP@queue\@xp\@xp\@xp{\@xp\the\@xp\GRP@queue
1907     \@xp\@elt\@xp{\EQ@trial}%
1908   }%
1909   \global\setbox\GRP@box\vbox{%
1910     \hbox{\box\EQ@box\box\EQ@copy\penalty\@ne\copy\EQ@numbox}%
1911     \unvbox\GRP@box
1912   }%
1913   \EQ@trial
1914   \if\eq@isIntertext\else
1915     \ifdim\eq@wdL>\grp@wdL \global\grp@wdL\eq@wdL \fi
1916     \ifdim\eq@wdT>\grp@wdT \global\grp@wdT\eq@wdT \fi
1917     \setlength\dim@a{\eq@wdT-\eq@wdL}%
1918     \ifdim\dim@a>\grp@wdR \global\grp@wdR\dim@a \fi
1919     \ifdim\eq@linewidth>\grp@linewidth \global\grp@linewidth\eq@linewidth\fi
1920     \if\eq@hasNumber
1921       \global\let\grp@eqs@numbered\@True
1922       \ifdim\eq@wdNum>\grp@wdNum\global\grp@wdNum\eq@wdNum\fi
1923     \fi
1924     \if\EQ@hasLHS\else\global\let\grp@aligned\@False\fi
1925     \if D\eq@layout \global\let\grp@aligned\@False\fi % Layout D (usually) puts rel on 2nd line
1926     \if\eq@shiftnumber\global\let\grp@shiftnumber\@True\fi % One eq shifted forces all.
1927   \fi
1928 }
```

`\grp@finish` Set accumulated equations from a dgroup environment.

BRM: Questionable patch!! When processing the `\GRP@queue`, put it into a `\vbox`, then `\unvbox` it. This since there's a bizarre problem when the `\output` routine gets invoked at an inopportune moment: All the not-yet-processed `\GRP@queue` ends up in the `\@freelist` and bad name clashes happen. Of course, it could be due to some other problem entirely!!!

```

1929 \def\grp@finish{%
1930   % \debug@box\GRP@box
1931   % \breqn@debugmsg{\GRP@queue: \the\GRP@queue}%
1932   == Now that we know the collective measurements, make final decision about
1933   alignment & shifting. Check if alignment is still possible
1934   \setlength\dim@a{\grp@wdL+\grp@wdR-4em}% Allowance for shrink?
1935   \if\grp@aligned
1936     \ifdim\dim@a>\grp@linewidth
1937       \global\let\grp@aligned\@False
1938     \fi
1939   \fi
```

1937   \fi

If we're adding an unshifted group number that equations didn't know about, re-check shifting

1938   \addtolength\dim@a{\grp@wdNum}% Effective length

1939   \if\grp@shiftnumber

1940   \else

1941     \if\@And{\grp@hasNumber}{\@Not\grp@eqs@numbered}

1942       \ifdim\dim@a>\grp@linewidth

1943         \global\let\grp@shiftnumber\@True

1944     \fi

1945   \fi

1946   \fi

If we can still align, total width is sum of maximum LHS & RHS

1947   \if\grp@aligned

1948     \global\grp@wdT\grp@wdL

1949     \global\advance\grp@wdT\grp@wdR

1950   \fi

1951   <\*trace>

1952   \breqn@debugmsg{===== DGROUP Formatting

1953    \MessageBreak===== \grp@wdL=\the\grp@wdL, \grp@wdR=\the\grp@wdR

1954    \MessageBreak===== Shift Number=\theb@@le\grp@shiftnumber, Eqns. numbered=\theb@@le\grp@eqs@n

1955    \MessageBreak===== Aligned=\theb@@le\grp@aligned

1956    \MessageBreak===== \grp@wdNum=\the\grp@wdNum}%

1957   </trace>

BRM: Originally this stuff was dumped directly, without capturing it in a \vbox

1958   \setbox\GRP@wholebox\vbox{%

1959     \let\@elt\eqgrp@elt

1960     \the\GRP@queue

1961   }%

If we're placing a group number (not individual eqn numbers) NOTE: For now, just code up LM number NOTE: Come back and handle other cases. NOTE: Vertical spacing is off, perhaps because of inter eqn. glue

A bit of a hack to get the top spacing correct. Fix this logic properly some day. Also, we do the calculation in a group for maximum safety.

1962   \global\let\eq@GRP@first@dmath\@True

1963   \beginngroup

1964   \dmath@first@leftskip

1965   \eq@topspace{\vskip\parskip}%

1966   \endgroup

1967   \if\@And{\grp@hasNumber}{\@Not{\grp@eqs@numbered}}%

1968   %   \eq@topspace{\vskip\parskip}%

1969   \if\grp@shiftnumber

1970     \copy\GRP@numbox \penalty\@M

1971     \kern\eqlineskip

1972   \else

1973     \setlength\dim@a{%

1974       (\ht\GRP@wholebox+\dp\GRP@wholebox+\ht\GRP@numbox-\dp\GRP@numbox)/2}%

```

1975         \setlength\skip@c{\dim@a-\ht\GRP@numbox}%
1976         \vglue\skip@c% NON discardable
1977         \copy\GRP@numbox \penalty\@M
1978     <*trace>
1979     \breqn@debugmsg{GROUP NUMBER: preskip:\the\skip@c, postkern:\the\dim@a, height:\the\ht\GRP@who
1980     \MessageBreak==== box height:\the\ht\GRP@numbox, box depth:\the\dp\GRP@numbox}%
1981 </trace>
1982     \kern-\dim@a
1983     \kern-\abovedisplayskip % To cancel the topspace above the first eqn.
1984     \fi
1985     \fi
1986 <*trace>
1987 %\debug@box\GRP@wholebox
1988 </trace>
1989     \unvbox\GRP@wholebox
1990     \let\@elt\relax

We'd need to handle shifted, right number here, too!!!
1991     \eq@botSPACE % not needed unless bottom number?
1992 }

```

`\eqgrp@elt` Mission is to typeset the next equation from the group queue.  
The arg is an `\EQ@trial`

```

1993 \def\eqgrp@elt#1{%
1994     \global\setbox\GRP@box\vbox{%
1995         \unvbox\GRP@box
1996         \setbox\z@\lastbox
1997         \setbox\tw@\hbox{\unhbox\z@
1998             \ifnum\lastpenalty=\@ne
1999             \else
2000                 \global\setbox\EQ@numbox\lastbox
2001             \fi
2002             \unpenalty
2003             \global\setbox\EQ@copy\lastbox
2004             \global\setbox\EQ@box\lastbox
2005         }%
2006     }%
2007     \begingroup \let\eq@botSPACE\relax
2008     #1%
2009     \if\eq@isIntertext
2010         \vskip\belowdisplayskip
2011         \unvbox\EQ@copy
2012     \else
2013         \grp@override
2014         \eq@finish
2015     \fi
2016     \endgroup
2017 }

```

Override the `\eq@trial` data as needed for this equation in this group NOTE:

w/ numbering variations (see above), we may need to tell `\eq@finish` to allocate space for a number, but not actually have one

```
2018 \def\grp@override{%
```

For aligned (possibly becomes an option?) For now ASSUMING we started out as CLM!!!

```
2019 \def\eqindent{I}%
```

compute nominal left for centering the group

```
2020 \setlength\dim@a{(\grp@linewidth-\grp@wdT)/2}%
```

Make sure L+R not too wide; should already have unset alignment

```
2021 \ifdim\dim@a<\z@\dim@a=\z@\fi
```

```
2022 \dim@b\if L\eqnumside\grp@wdNum\else\z@\fi
```

make sure room for number on left, if needed.

```
2023 \if\grp@shiftnumber\else
```

```
2024 \ifdim\dim@b>\dim@a\dim@a\dim@b\fi
```

```
2025 \fi
```

```
2026 \if\grp@aligned
```

```
2027 \addtolength\dim@a{\grp@wdL-\eq@wdL}%
```

```
2028 \fi
```

```
2029 \mathindent\dim@a
```

```
2030 \ifdim\dim@b>\dim@a
```

```
2031 \let\eq@shiftnumber\@True
```

```
2032 \fi
```

Could set `\def\eqnumplace{T}` (or even (m) if indentation is enough).

NOTE: Work out how this should interact with the various formats!!! NOTE: should recognize the case where the LHS's are a bit Wild, and then do simple left align (not on relation)

```
2033 }
```

## 34 The darray environment

There are two potential applications for `darray`. One is like `eqnarray` where the natural structure of the material crosses the table cell boundaries, and math operator spacing needs to be preserved across cell boundaries. And there is also the feature of attaching an equation number to each row. The other application is like a regular array but with automatic `displaystyle` math in each cell and better interline spacing to accommodate outside cell contents. In this case it is difficult to keep the vert ruling capabilities of the standard `array` environment without redoing the implementation along the lines of Arseneau's `tabls` package. Because the vert ruling feature is at cross purposes with the feature of allowing interline stretch and page breaks within a multiline array of equations, the `darray` environment is targeted primarily as an alternative to `eqnarray`, and does not support vertical ruling.

Overall strategy for `darray` is to use `\halign` for the body. In the case of a group, use a single `halign` for the whole group!

## What about intertext?

That's the most reliable way to get accurate column widths. Don't spread the `halign` to the column width, just use the natural width. Then, if we repack the contents of the `halign` into `\EQ@box` and `\EQ@copy`, as done for `dmath`, and twiddle a bit with the widths of the first and last cell in each row, we can use the same algorithms for centering and equation number placement as `dmath`! As well as handling footnotes and `vadjust` objects the same way.

We can't just use `\arraycolsep` for `darray`, if we want to be able to change it without screwing up interior arrays. So let's make a new `colsep` variable. The initial value is '2em, but let it shrink if necessary'.

2034 `\newskip\darraycolsep \darraycolsep 20pt plus1fil minus12pt`

Let's make a nice big default setup with eighteen columns, split up into six sets of `lcr` like `eqnarray`.

```

2035 \newcount\cur@row \newcount\cur@col
2036 \def\@tempa#1#2#3{%
2037   \cur@col#1 \hfil
2038   \setbox\z@\hbox{$\displaystyle####m@th$}\@nx\col@box
2039   \tabskip\z@skip
2040   &\cur@col#2 \hfil
2041   \setbox\z@\hbox{$\displaystyle\mathord{####\mathord{}}m@th$}\@nx\col@box
2042   \hfil
2043   &\cur@col#3 \setbox\z@\hbox{$\displaystyle####m@th$}\@nx\col@box
2044   \hfil\tabskip\darraycolsep
2045 }
2046 \xdef\darray@preamble{%
2047   \@tempa 123&\@tempa 456&\@tempa 789%
2048   &\@tempa{10}{11}{12}&\@tempa{13}{14}{15}&\@tempa{16}{17}{18}%
2049   \cr
2050 }
2051 \@ifundefined{Mathstrut@}{\let\Mathstrut@\strut}{}
2052 \def\darray@cr{\Mathstrut@\cr}
2053 \def\col@box{%
2054   <*trace>
2055   %\breqn@debugmsg{Col \number\cur@row,\number\cur@col: \the\wd\z@\space x \the\ht\z@+\the\dp\z@}
2056   </trace>
2057   \unhbox\z@
2058 }
2059 \newenvironment{darray}{\@optarg\darray{}}{}
2060 \def\@darray[#1]{%
2061   <trace> \breqn@debugmsg{=== DARRAY =====}%
2062   \if\eq@group\else\eq@prelim\fi

```

Init the `halign` preamble to empty, then unless the 'cols' key is used to provide a non-null preamble just use the default `darray` preamble which is a multiple `lcr`.

```

2063 \global\let\@preamble\@empty
2064 \setkeys{breqn}{#1}%
2065 \the\eqstyle \eq@setnumber
2066 \ifx\@preamble\@empty \global\let\@preamble\darray@preamble \fi

```

```

2067 \check@mathfonts
2068 % \let\check@mathfonts\relax % tempting, but too risky
2069 \@xp\let\csname\string\ \endcsname\darray@cr
2070 \setbox\z@\vbox\bgroup
2071 \everycr{\noalign{\global\advance\cur@row\@ne}}%
2072 \tabskip\z@skip \cur@col\z@
2073 \global\cur@row\z@
2074 \penalty\@ne % flag for \dar@repack
2075 \halign\@xp\bgroup\@preamble
2076 }

```

Assimilate following punctuation.

```

2077 \def\endddarray#1{\check@punct@or@qed}
2078 \def\end@ddarray{%
2079 \ifvmode\else \eq@addpunct \Mathstrut@\fi\crrc \egroup
2080 \dar@capture
2081 \egroup
2082 }

```

The `\dar@capture` function steps back through the list of row boxes and grinds them up in the best possible way.

```

2083 \def\dar@capture{%
2084 %% \showboxbreadth\maxdimen\showboxdepth99\showlists
2085 \eq@wdL\z@ \eq@wdRmax\z@
2086 \dar@repack
2087 }

```

The `\dar@repack` function is a variation of `\eq@repack`.

```

2088 \def\dar@repack{%
2089 \unpenalty
2090 \setbox\tw@lastbox
2091 %\batchmode{\showboxbreadth\maxdimen\showboxdepth99\showbox\tw@}\errorstopmode
2092 \global\setbox\EQ@box\hbox{%
2093 \hbox{\unhcopy\tw@\unskip}\penalty-\@M \unhbox\EQ@box}%
2094 \global\setbox\EQ@copy\hbox{%
2095 \hbox{\unhbox\tw@\unskip}\penalty-\@M \unhbox\EQ@copy}%
2096 \unskip
2097 \ifcase\lastpenalty \else\@xp@gobble\fi
2098 \dar@repack
2099 }

```

## 35 Miscellaneous

The `\condition` command. With the star form, set the argument in math mode instead of text mode. In a series of conditions, use less space between members of the series than between the conditions and the main equation body.

WSPR: tidied/fixed things up as it made sense to me but might have broken something else!

```

2100 \newskip\conditionsep \conditionsep=10pt minus5pt%
2101 \newcommand{\conditionpunct}{,}

```



`\condition`

```
2102 \newcommand\condition{%
2103   \begingroup\@tempswatrue
2104   \@ifstar{\@tempswafalse \condition@a}{\condition@a}}
```

`\condition@a`

```
2105 \newcommand\condition@a[2][\conditionpunct]{%
2106   \unpenalty\unskip\unpenalty\unskip % BRM Added
2107   \hbox{#1}%
2108   \penalty -201\relax\hbox{}}% Penalty to allow breaks here.
2109   \hskip\conditionsep
2110   \setbox\z@\if@tempswa\hbox{#2}\else\hbox{$\textmath@setup #2$}\fi
```

BRM's layout is achieved with this line commented out but it has the nasty side-effect of shifting the equation number to the next line:

```
2111 % \global\eq@wdCond\wd\z@
2112 \usebox\z@
2113 \endgroup}
```

The `dsuspend` environment. First the old one that didn't work.

```
2114 \newenvironment{XXXXdsuspend}{%
2115   \global\setbox\EQ@box\vbox\bgroup \@parboxrestore
```

If we are inside a list environment, `\displayindent` and `\displaywidth` give us `\totalleftmargin` and `\linewidth`.

```
2116   \parshape 1 \displayindent \displaywidth\relax
2117   \hsize=\columnwidth \noindent\ignorespaces
2118 }{%
2119   \par\egroup
```

Let's try giving `\EQ@box` the correct height for the first line and `\EQ@copy` the depth of the last line.

```
2120   \global\setbox\GRP@box\vbox{%
2121     \vbox{\copy\EQ@box\top{\unvbox\EQ@box}}%
2122     \unvbox\GRP@box
2123   }%
```

Need to add a dummy element to `\GRP@queue`.

```
2124   \global\GRP@queue\@xp{\the\GRP@queue
2125     \@elt{\gdef\EQ@trial{}}}%
2126   }%
2127 }
```

And then the one that does work.

```
2128 \newenvironment{dsuspend}{%
2129   \global\setbox\EQ@box\vbox\bgroup \@parboxrestore
2130   \parshape 1 \displayindent \displaywidth\relax
2131   \hsize=\columnwidth \noindent\ignorespaces
2132 }{%
2133   \par\egroup
2134   \global\setbox\GRP@box\vbox{%
```

```

2135 \hbox{\copy\EQ@box\top{\unvbox\EQ@box}}%
2136 \unvbox\GRP@box
2137 }%
2138 \global\GRP@queue\@xp{\the\GRP@queue
2139 % \@elt{\gdef\EQ@trial{\let\eq@isIntertext\@True}}%
2140 \@elt{\let\eq@isIntertext\@True}%
2141 }%
2142 }

```

Allow `\intertext` as a short form of the `dsuspend` environment; it's more convenient to write, but it doesn't support embedded verbatim because it reads the material as a macro argument. To support simultaneous use of `amsmath` and `breqn`, the user command `\intertext` is left alone until we enter a `breqn` environment.

```

2143 \newcommand\breqn@intertext[1]{\dsuspend#1\enddsuspend}

```

`\*` Discretionary times sign. Standard L<sup>A</sup>T<sub>E</sub>X definition serves only for inline math.  
`\discretionarytimes` Should the thin space be included? Not sure.

```

2144 \renewcommand{\*}{%
2145 \if@display
2146 \setbox\z@\hbox{\mathsurround\z@$ \mkern\eq@binoffset$}%
2147 \discretionary{}{%
2148 \kern\the\wd\z@ \textchar\discretionarytimes
2149 }{}%
2150 \thinspace
2151 \else
2152 \discretionary{\thinspace\textchar\discretionarytimes}{}{}%
2153 \fi
2154 }

```

This is only the symbol; it can be changed to some other symbol if desired.

```

2155 \newcommand{\discretionarytimes}{\times}

```

`\nref` This is like `\ref` but doesn't apply font changes or other guff if the reference is undefined. And it is fully expandable for use as a label value.

**Can break with Babel if author uses active characters in label  
key; need to address that**

**mjd,1999/01/21**

.

```

2156 \def\nref#1{\@xp\@nref\curname r@#1\endcsname}
2157 \def\@nref#1#2{\ifx\relax#1??\else \@xp\@firstoftwo#1\fi}
2158 %%%%%%%%%%%%%%%

```

## 36 Wrap-up

The usual endinput.

2159 `\endpackage`

## 37 To do

1. Alignment for equation groups.
2. Use dpc's code for package options in keyval form.
3. Encapsulate "break math" into a subroutine taking suitable arguments.
4. Need a density check for layout S when linewidth is very small.
5. Make `:=` trigger a warning about using `\coloneq` instead.
6. Ill-centered multiline equation (three-line case) in test008.
7. Attaching a single group number.
8. Make sure to dump out box registers after done using them.
9. Do the implementation for `\eq@resume@parshape`.
10. Check on `stackrel` and `buildrel` and `relbar` and ???.
11. Test math symbols at the beginning of array cells.
12. Test `\md` in and out of delims.
13. Framing the equation body: the `parshape` and number placement need adjusting when a frame is present.
14. Cascading line widths in list env.
15. Noalign option for `dmath = multiline` arrangement?
16. Nocompact option, suggested 1998/05/19 by Andrew Swann.
17. `\delbreak` cmd to add discretionary space at a break within delimiters.
18. Reduce above/below skip when the number is shifted.
19. Need a `\middelim` command for marking a delimiter symbol as nondirectional if it has an innate directionality `()[]` etc..
20. `\xrightarrow` from `amsmath` won't participate in line breaking unless something extra is done. Make `\BreakingRel` and `\BreakingBin` functions?
21. Placement of number in an indented quotation or abstract.

22. If  $LHSwd > 2em$ , it might be a good idea to try with `eq@indentstep = 2em` before shifting the number. Currently this doesn't happen if the first trial pass (without the number) succeeds with  $indentstep = LHSwd > 2em$ .
23. Read past `\end{enumerate}` when checking for `\end{proof}`?
24. Look into using a “qed-list” of environment names instead of checking the existence of `\proofqed`.
25. Pick up the `vadjust/footnote/mark` handling.
26. Forcing/prohibiting page breaks after/before an equation.
27. Adding a spanner brace on the left and individual numbers on the right (indy-numbered cases).
28. Provide `\shiftnumber`, `\holdnumber` to override the decision.
29. Provide a mechanism for adjusting the vertical position of the number. Here a version-specific selection macro would be useful.
 

```
\begin{dmath}[
  style={\foredition{1}{\raisenumber{13pt}}}
]
```
30. Add an `alignleft` option for an equation group to mean, break and align to a ladder layout as usual within the equations, but for the group alignment used the leftmost point (for equations that don't have an LHS, this makes no difference).
31. Test with Arseneau's `wrapfig` for `parshape/everypar` interaction.
32. Fix up the macro/def elements.
33. Convert the literal examples in section ‘Equation types and forms’ to typeset form.
34. Compile comparison-examples: e.g., a standard equation env with big left-right objects that don't shrink, versus how shrinking can allow it to fit.
35. Frame the “figures” since they are mostly text.

Possible enhancements:

1. Provide a `pull` option meaning to pull the first and last lines out to the margin, like the `multline` environment of the `amsmath` package. Maybe this should get an optional argument, actually, to specify the amount of space left at the margin.
2. With the `draft` option, one would like to see the equation labels in the left margin. Need to check with the `showkeys` package.

3. Options for break preferences: if there's not enough room, do we first shift the number, or first try to break up the equation body?. In an aligned group, does sticking to the group alignment take precedence over minimizing the number of line breaks needed for individual equations?. And the general preferences probably need to be overridable for individual instances.
4. Extend suppress-breaks-inside-delimiters support to inline math (suggestion of Michael Doob).
5. Use belowdisplayshortskip above a dsuspend fragment if the fragment is only one line and short enough compared to the equation line above it.
6. Add `\eqfuzz` distinct from `\hffuzz`. Make use of it in the measuring phase.
7. Provision for putting in a 'continued' note.
8. Conserve box mem: modify `frac`, `sub`, `sup`, `overline`, `underline`, `sqrt`, to turn off `\bin@break` and (less urgently) `\rel@break`.
9. More explicit support for Russian typesetting conventions (cf Grinchuk article).
10. With package option `refnumbers`, leave unnumbered all uncited equations, even if they are not done with the star form (Bertolazzi's easyeqn idea).
11. In an equation group, use a vertical bracket with the equation number to mark the lines contained in that equation.
12. For a two-line multiline thingamabob, try to make sure that the lines overlap in the middle by 2 em or whatever (settable design variable).
13. Provide a separate vertical column for the principal mathrel symbols and center them within the column if they aren't all the same width. Maybe an option for `dmath`: `relwidth=x`, so that two passes are not required to get the max width of all the mathrels. Or, no, just require it to be an `halign` or provide a macro to be applied to all the shorter rels:

```
lhs \widerel{19pt}{=} ...
    \xrightarrow{foo} ...
```

14. try to use `vadjust` for `keepglue`

## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

<b>Symbols</b>	<code>\"</code> .....	5, 8, 19
<code>\!</code> .....	592	

$\backslash$ \$	135	$\backslash$ e $\acute{e}$ ha	130
$\backslash$ &	84, 90, 91	$\backslash$ e $\acute{e}$ lt	100,
$\backslash$ *	1361, 2143		898, 902, 907, 969, 971, 1055,
$\backslash$ ,	591		1059, 1060, 1271, 1302, 1340,
$\backslash$ .	591		1906, 1958, 1989, 2124, 2138, 2139
$\backslash$ ;	591	$\backslash$ empty	28–30,
$\backslash$ ?	592, 1269		34, 37, 277, 363, 365, 366, 419,
$\backslash$ @@display	135, 841		464, 480, 484, 489, 606, 628,
$\backslash$ @@enddisplay	135, 855		765, 769, 772, 880, 899, 908,
$\backslash$ @@endmath	135, 722, 1819, 1834, 1838		918, 920, 921, 924, 969, 1039,
$\backslash$ @@insert	140		1045, 1356, 1662, 1861, 1876,
$\backslash$ @@italiccorr	176		1878, 1879, 1883, 1890, 2062, 2065
$\backslash$ @left	355, 1598, 1607, 1611, 1615	$\backslash$ emptytoks	41,
$\backslash$ @mark	140		322, 325, 340, 343, 454, 840, 1860
$\backslash$ @math	135, 704, 1808, 1832	$\backslash$ endelt	899, 902, 908, 969, 971, 1057,
$\backslash$ @par	549,		1060, 1062, 1269, 1271, 1309, 1346
	562, 724, 1033, 1425, 1571, 1724	$\backslash$ endpetrue	696
$\backslash$ @@right	355, 1599, 1609, 1612, 1615	$\backslash$ eq@numberfalse	213
$\backslash$ @@vadjust	140, 289, 869, 876, 1706	$\backslash$ eq@numbertrue	212
$\backslash$ @And	74, 637, 1506, 1542, 1940, 1966	$\backslash$ filelist	239, 256
$\backslash$ @False	74, 213, 214,	$\backslash$ firstoftwo	1698, 2156
	229, 276, 414–416, 447, 511,	$\backslash$ gobble	30,
	636, 663, 702, 991, 1036, 1170,		93, 522, 786, 996, 1203, 1246, 2096
	1326, 1797, 1841–1844, 1853,	$\backslash$ gobbletwo	950
	1864, 1866, 1889, 1923, 1924, 1934	$\backslash$ height	1576, 1626
$\backslash$ @M	188, 190, 453, 712, 714,	$\backslash$ ifnext	64, 73, 863, 1602, 1605
	717, 721, 817, 822, 842, 861,	$\backslash$ ifnexta	64, 71
	864, 870, 877, 1360, 1393, 1419,	$\backslash$ ifpackageloaded	13
	1557, 1563, 1676, 1693, 1715,	$\backslash$ ifpackagewith	233, 234, 250
	1716, 1812, 1969, 1976, 2092, 2094	$\backslash$ ifstar	69, 861, 2103
$\backslash$ @Mi	289, 705, 721, 1724, 1808	$\backslash$ ifundefined	
$\backslash$ @Not	74, 637, 1003,		22, 41, 165, 242, 259, 268, 271,
	1008, 1022, 1506, 1542, 1940, 1966		357, 617, 1617, 1774, 1875, 2050
$\backslash$ @Or	78, 1022	$\backslash$ ignoretrue	697, 1814
$\backslash$ @True	74, 212, 281, 370,	$\backslash$ inlabelfalse	428
	371, 413, 417, 423, 493, 498,	$\backslash$ let@token	565, 569, 572, 573, 576–
	670, 676, 681, 1037, 1177, 1195,		578, 586–588, 594–598, 612,
	1213, 1216, 1222, 1229, 1279,		1693, 1695, 1696, 1700, 1704
	1322, 1336, 1795, 1804, 1845,	$\backslash$ em	713
	1847, 1859, 1865, 1885, 1920,	$\backslash$ mathmargin	272
	1925, 1942, 1961, 2030, 2138, 2139	$\backslash$ minus	886, 1085, 1499, 1517, 1551
$\backslash$ @badmath	1832, 1834, 1838	$\backslash$ namedef	
$\backslash$ @car	116, 376		449, 450, 1071, 1790, 1798, 1799
$\backslash$ @centering	195, 196	$\backslash$ ne	279, 291, 471, 527, 715,
$\backslash$ @currentlabel	368, 633		819, 868, 869, 875, 876, 1037,
$\backslash$ @darray	2058, 2059		1187, 1210, 1260, 1454, 1666,
$\backslash$ @dgroup	1847, 1853, 1857		1685, 1695, 1909, 1997, 2070, 2073
$\backslash$ @displaytrue	359	$\backslash$ newline	709
$\backslash$ @dmath	423, 424, 447, 1806, 1807	$\backslash$ nil	28, 32–34, 36, 37, 236, 239,
$\backslash$ @dseries	1795, 1797, 1800		253, 256, 376, 624, 625, 1786, 1789



<code>\aftergroup</code> .....	645, 950	<code>\box</code> .....	544, 796, 800, 1372, 1718, 1756, 1764, 1770, 1860, 1909
<code>\alph</code> .....	1896	<code>\breqn@debugmsg</code> .....	145, 159–161, 425, 486, 501, 513, 638, 640, 656, 745, 753, 896, 900, 901, 909, 936, 940, 954, 960, 964, 969, 970, 996, 1021, 1023, 1083, 1089, 1098, 1106, 1110, 1114, 1173, 1176, 1190, 1193, 1202, 1212, 1215, 1219, 1224, 1285, 1321, 1325, 1342, 1353, 1429, 1858, 1897, 1930, 1951, 1978, 2054, 2060
<code>\AtEndOfPackage</code> .....	7	<code>\breqn@intertext</code> .....	458, 2142
<b>B</b>		<code>\breqn@parshape@warning</code> ...	460, 474
<code>\badness</code> .....	1278	<code>\breqn@repack@err</code> .....	807, 811
<code>\baselineskip</code> .....	1358	<code>\breqn@popcats</code> .....	4, 7, 15
<code>\batchmode</code> .....	148, 732, 738, 2090	<b>C</b>	
<code>\bBigg@</code> .....	1619–1621, 1623	<code>\catcode</code> .....	5, 8, 16, 17, 19, 84, 90, 135, 591, 592
<code>\begin</code> .....	408, 409, 411, 776, 1541	<code>\chardef</code> .....	42, 1269
<code>\begingroup</code> .....	84, 90, 100, 103, 115, 135, 433, 500, 584, 635, 840, 884, 897, 906, 961, 969, 997, 1574, 1602, 1605, 1690, 1738, 1773, 1783, 1962, 2006, 2102	<code>\check@mathfonts</code> .....	2066, 2067
<code>\belowdisplayshortskip</code> ....	645, 844	<code>\check@punct</code> .....	573, 630
<code>\belowdisplayskip</code> .....	645, 693, 695, 844, 1440, 2009	<code>\check@punct@a</code> .....	573, 574
<code>\bgroup</code> ...	703, 2069, 2074, 2114, 2128	<code>\check@punct@b</code> .....	579, 602
<code>\Big</code> .....	1619, 1631, 1638, 1646	<code>\check@punct@or@qed</code> .....	437, 450, 627, 1796, 1798, 1836, 2076
<code>\big</code> .....	1619, 1630, 1637, 1645	<code>\check@qed</code> .....	577, 578, 586–588, 594–598, 607
<code>\big@size</code> .....	1618, 1626	<code>\check@qed@a</code> .....	609, 611
<code>\Bigg</code> .....	1620, 1633, 1640, 1648	<code>\check@qed@b</code> .....	612, 616
<code>\bigg</code> .....	1620, 1632, 1639, 1647	<code>\clubpenalty</code> .....	715, 731, 1360
<code>\Biggg</code> .....	1621, 1635, 1642, 1650	<code>\col@box</code> .....	2037, 2040, 2042, 2052
<code>\biggg</code> .....	1621, 1634, 1641, 1649	<code>\color</code> .....	178
<code>\Bigggl</code> .....	1635	<code>\columnwidth</code> .....	886, 922, 1084, 2116, 2130
<code>\bigggl</code> .....	1634	<code>\condition</code> .....	2101
<code>\Bigggm</code> .....	1650	<code>\condition@a</code> .....	2103, 2104
<code>\bigggm</code> .....	1649	<code>\conditionpunct</code> .....	2100, 2104
<code>\Bigggr</code> .....	1642	<code>\conditionsep</code> ..	1437, 1455, 2099, 2108
<code>\bigggr</code> .....	1641	<code>\copy</code> .....	560, 729, 730, 790, 1393, 1425, 1557, 1563, 1909, 1969, 1976, 2120, 2134
<code>\Biggl</code> .....	1633	<code>\count@</code> .....	47, 466, 467, 816, 817, 819, 820, 835, 1687
<code>\biggl</code> .....	1632	<code>\cr</code> .....	854, 2048, 2051
<code>\Biggm</code> .....	1648	<code>\crrcr</code> .....	2078
<code>\biggm</code> .....	1647	<code>\csname</code> .....	24, 86, 91, 93, 244, 261, 358, 507, 525, 528, 530,
<code>\Biggr</code> .....	1640		
<code>\biggr</code> .....	1639		
<code>\Bigl</code> .....	1631		
<code>\bigl</code> .....	1630		
<code>\Bigm</code> .....	1646		
<code>\bigm</code> .....	1645		
<code>\Bigr</code> .....	1638		
<code>\bigr</code> .....	1637		
<code>\bin@break</code> .....	292, 306		
<code>\bin@mark</code> .....	292		
<code>\binoppenalty</code> .....	717		
<code>\bop@incr</code> .....	1662		
<code>\botmark</code> .....	120		



618, 626, 629, 938, 1261, 1305,  
 1653, 1656, 1659, 1778, 2068, 2155  
`\cur@col` .....  
 2034, 2036, 2039, 2042, 2054, 2071  
`\cur@row` ..... 2034, 2054, 2070, 2072

## D

`\d@@Bin` ..... 292, 314, 331, 1683  
`\d@@DeA` ..... 317, 336, 1661  
`\d@@DeB` ..... 316, 335, 1651  
`\d@@DeL` ..... 316, 335, 1651  
`\d@@DeR` ..... 316, 335, 1651  
`\d@@Rel` ..... 292, 314, 332  
`\d@@symBin` ..... 305, 315, 334  
`\d@@symDeA` ..... 305, 319, 338  
`\d@@symDeB` ..... 305, 319, 338  
`\d@@symDeL` ..... 318, 337  
`\d@@symDel` ..... 305  
`\d@@symDeR` ..... 305, 318, 337  
`\d@@symRel` ..... 305, 315, 333  
`\dar@capture` ..... 2079, 2082  
`\dar@repack` .... 2073, 2085, 2087, 2097  
`\darray@cr` ..... 2051, 2068  
`\darray@mkpream` ..... 420  
`\darray@preamble` ..... 2045, 2065  
`\darraycolsep` ..... 2033, 2043  
`\debug@box` .....  
 147, 152, 760, 761, 1370, 1929, 1986  
`\debug@para` ..... 157  
`\debug@showformat` ..... 520, 1428  
`\debug@showmeasurements` .....  
 ..... 502, 895, 905, 1043  
`\debugwr` ..... 146, 158, 760, 761  
`\decl@twang` ..... 1786, 1789  
`\DeclareOption` ..... 9  
`\DeclareTwang` .. 1782, 1784, 1792–1794  
`\def` 27, 32, 36, 37, 63–65, 68–70, 73–  
 82, 89, 99, 116, 145–147, 151,  
 157, 167, 168, 171–173, 175–  
 178, 194, 212, 213, 232, 234,  
 236, 237, 251, 253, 254, 278,  
 288, 295, 296, 298, 303–306,  
 312, 329, 348, 364, 367, 372,  
 387–389, 393, 396, 397, 399,  
 403, 404, 412, 424, 437, 438,  
 451, 460, 465, 477, 499, 539,  
 551, 564, 567, 568, 572–574,  
 607, 611, 616, 624, 626, 627,  
 629, 634, 662, 689, 700, 701,  
 707, 720, 764, 773, 811, 814,

839, 860, 862, 864, 865, 872,  
 879, 881, 895, 898, 905, 907,  
 922, 923, 931, 944, 949, 953,  
 957, 958, 963, 967, 969, 977,  
 982, 984, 986–991, 994, 995,  
 999, 1019, 1020, 1029, 1030,  
 1046, 1053, 1057, 1062, 1070,  
 1095, 1118, 1123, 1126, 1133,  
 1144, 1149, 1165, 1167, 1171,  
 1235, 1239, 1244, 1257, 1259,  
 1265, 1266, 1270, 1274, 1282,  
 1296, 1315, 1319, 1331–1335,  
 1346, 1347, 1357, 1369, 1375,  
 1379, 1385, 1391, 1402, 1408,  
 1415, 1428, 1444, 1525, 1554,  
 1560, 1566, 1579, 1590, 1601,  
 1604, 1607, 1608, 1611–1613,  
 1619–1621, 1623, 1630–1635,  
 1637–1642, 1645–1650, 1652,  
 1655, 1658, 1665, 1674, 1678,  
 1688, 1689, 1694, 1702, 1705,  
 1709, 1730–1735, 1737, 1750,  
 1758, 1766, 1772, 1789, 1796,  
 1800, 1801, 1810, 1814, 1817,  
 1821, 1825, 1826, 1836, 1837,  
 1857, 1871, 1877, 1882, 1896,  
 1899, 1904, 1928, 1992, 2017,  
 2018, 2035, 2051, 2052, 2059,  
 2076, 2077, 2082, 2087, 2155, 2156  
`\define@key` 361, 364, 367, 370–375,  
 378, 383, 386, 387, 389, 393,  
 398, 404, 412–414, 416, 418, 419  
`\delim@a` ..... 1653, 1656, 1659, 1691  
`\delim@reset` ..... 1613, 1624  
`\delim@ter` ..... 1602,  
 1605, 1607, 1609, 1653, 1656, 1659  
`\dim` ..... 1144  
`\dim@A` ..... 48  
`\dim@a` ..... 48, 390,  
 400, 664, 675, 680, 740, 743,  
 746, 748, 946, 947, 1063–1065,  
 1075, 1082, 1084, 1099, 1100,  
 1119, 1121, 1150, 1151, 1160,  
 1186, 1189, 1199, 1240, 1250,  
 1261, 1263, 1265, 1266, 1287,  
 1288, 1290, 1309, 1380, 1386,  
 1394, 1396, 1398, 1403, 1410,  
 1420, 1422, 1424, 1472, 1474,  
 1475, 1477, 1478, 1480, 1483,  
 1484, 1497, 1528, 1529, 1533,

1537, 1538, 1545, 1547, 1551, 1555, 1558, 1561, 1564, 1581– 1583, 1753, 1754, 1761, 1762, 1916, 1917, 1931, 1933, 1937, 1941, 1972, 1974, 1978, 1981, 2019, 2020, 2023, 2026, 2028, 2029		\dquad . . . . . 1812, 1814, 1827, 1828
\dim@b . . . . . 48, 679, 680, 1047, 1049, 1077, 1079, 1080, 1082–1085, 1090, 1127, 1129, 1134–1136, 1138–1140, 1145, 1146, 1157, 1158, 1161, 1179, 1180, 1182, 1184, 1186, 1248, 1250, 1252, 1253, 1276, 1277, 1285, 1287, 1340, 1342, 1343, 1346, 1349, 1353, 1354, 1457–1460, 1462, 1463, 1465, 1477, 1478, 1480, 1502, 1504, 1509, 1510, 1515, 1517, 1534, 1538, 1546, 1551, 2021, 2023, 2029		\dseries@display@setup . . . 329, 1802
\dim@c . . . . . 48, 932– 935, 1158, 1161, 1249–1253, 1341–1343, 1350, 1352–1354, 1445, 1446, 1448, 1459, 1460, 1469, 1470, 1473, 1475, 1478, 1479, 1482, 1483, 1485, 1498, 1504, 1508–1510, 1516, 1544–1547		\dsuspend . . . . . 2142
\dim@d . . . . . 48, 1467–1470, 1482, 1483, 1485, 1487, 1488, 1492, 1495, 1497, 1775, 1777, 1778		\dt@fill@cancel . . . . . 1674
\dim@e . . . . . 48, 1450, 1452, 1455, 1468, 1474, 1487–1491, 1494, 1495, 1498, 1499, 1516, 1517		\Dthickmuskip . . . . . 193, 313, 330
\dimen@ . . . . . 51		
\dimen@i . . . . . 53		
\dimen@ii . . . . . 52		
\dimendef . . . . . 1728, 1729		
\discretionary . . . . . 2146, 2151		
\discretionarytimes . . . . . 2143		
\display@setup . . . 311, 426, 1801, 1802		
\displayindent 471, 847, 849, 2115, 2129		
\displaystyle . . . . . . 346, 704, 1801, 2037, 2040, 2042		
\displaywidth 471, 847, 922, 2115, 2129		
\divide 1135, 1151, 1348, 1349, 1352, 1494		
\dmath . . . . . 422		
\dmath* . . . . . 446		
\dmath@first@leftskip . 512, 513, 1963		
\Dmedmuskip . . . . . 192, 313, 330		
\dp . . . 154, 1048, 1309, 1380, 1403, 1410, 1741, 1761, 1973, 1979, 2054		
	<b>E</b>	
	\edef . . . . . 4, 15, 28, 104, 107, 116, 124, 125, 243, 260, 362, 376, 390, 400, 467, 470, 575, 883, 942, 1073, 1120, 1128, 1145, 1153, 1159, 1166, 1206, 1207, 1230, 1237, 1241, 1245, 1253, 1261, 1302, 1822	
	\egroup . . . 758, 2078, 2080, 2118, 2132	
	\else . . . . . 30, 34, 37, 76– 79, 106, 109, 127, 237, 241, 245, 254, 258, 262, 429, 444, 473, 485, 503, 514, 517, 526, 529, 533, 546, 557, 570, 577–579, 587, 588, 594–599, 613, 641, 647, 652, 666, 668, 671, 673, 678, 692, 766, 806, 817, 827, 834, 883, 926, 939, 1007, 1012, 1025, 1029, 1078, 1080, 1087, 1101, 1104, 1109, 1113, 1174, 1183, 1189, 1191, 1196, 1214, 1217, 1223, 1247, 1279, 1285, 1288, 1294, 1298, 1307, 1317, 1323, 1327, 1339, 1343, 1354, 1372, 1395, 1421, 1447, 1464, 1482, 1503, 1536, 1591, 1671, 1683, 1695, 1696, 1718, 1722, 1746, 1785, 1812, 1832, 1834, 1838, 1879, 1913, 1923, 1939, 1971, 1998, 2011, 2021, 2022, 2061, 2078, 2096, 2109, 2150, 2156	
	\end . . . . . 407, 410, 612, 622, 625, 626	
	\end@ddarray . . . . . 2077	
	\end@dgroup . . . . . 1849, 1855, 1871	
	\end@dmath . . . . . 438, 449, 1819	
	\end@dseries . . . . . 1799, 1817	
	\end@math . . . . . 1837	
	\endcsname 24, 86, 89, 91, 93, 244, 261, 358, 507, 525, 528, 530, 618, 624, 626, 629, 938, 1261, 1309, 1653, 1656, 1659, 1778, 2068, 2155	
	\endddarray . . . . . 2076	
	\enddmath . . . . . 422	
	\enddmath* . . . . . 446	

<code>\endddseries</code> .....	1796	<code>\EQ@fallback</code> .....	921, 950, 957, 1016
<code>\enddsuspend</code> .....	2142	<code>\eq@final@linecount</code> ...	497, 522, 527
<code>\endgroup</code> .....	88, 92, 100, 112, 133, 137, 441, 536, 605, 660, 857, 891, 903, 915, 959, 972, 1017, 1577, 1607, 1608, 1692, 1748, 1780, 1784, 1965, 2015, 2112	<code>\eq@finish</code> .....	444, <u>497</u> , 2013
<code>\endmath</code> .....	1809	<code>\eq@firstht</code> ....	223, 547, 558, 675, 980, 1058, 1386, 1435, 1594, 1595
<code>\ends@math</code> .....	1809, 1836	<code>\eq@fix@lastline</code> .....	1035, <u>1046</u>
<code>\eq@addframe</code> ....	547, 558, 1579, 1594	<code>\eq@foreground</code> .....	412
<code>\eq@addpunct</code> ....	723, 764, 1814, 2078	<code>\eq@frame</code> .....	389, 393, 396, 399, 503, 545, 556, 651, 691, 933, 1395, 1421, 1453, 1503, 1535, 1591
<code>\EQ@afterspace</code> .....	770, 772	<code>\eq@frame@adjust</code> .....	933, 944
<code>\eq@background</code> .....	404	<code>\eq@framesep</code> ...	400, 403, 653, 693, 945, 946, 1396, 1422, 1575, 1581
<code>\eq@badline</code> .....	977, 1003, 1008, 1036, 1037, 1214, 1279	<code>\eq@framewd</code> ....	390, 397, 653, 693, 945, 946, 1396, 1422, 1575, 1581
<code>\eq@badness</code> ....	210, 901, 912, 970, 977, 1054, 1068, 1207, 1215, 1217, 1220, 1278, 1279, 1285, 1309	<code>\eq@given@sidespace</code> .....	231, 384
<code>\eq@binoffset</code> .....	198, 295, 1672, 1673, 1685, 2145	<code>\eq@group</code> .....	429, 444, 509, 637, 1078, 1187, 1210, <u>1841</u> , 1859, 2061
<code>\eq@botSPACE</code> ....	537, <u>634</u> , 1990, 2006	<code>\eq@GRP@first@dmath</code> .....	498, 510, 511, 637, 1859, 1961
<code>\EQ@box</code> .....	199, 549, 561, 727, 729, 736, 740, 746, 753, 760, 780, 785, 792, 798, 800, 827, 1571, 1909, 2003, 2091, 2092, 2114, 2120, 2128, 2134	<code>\EQ@hasLHS</code> ....	276, 281, 702, 754, 982, 1022, 1096, 1167, 1434, 1923
<code>\eq@break</code> .....	<u>879</u>	<code>\eq@hasNumber</code> .....	212–214, 423, 447, 479, 493, 523, 984, 1005, 1079, 1137, 1447, 1506, 1542, 1795, 1797, 1885, 1889, 1919
<code>\eq@C@setsides</code> .....	1444	<code>\eq@holdnumber</code> .....	371
<code>\eq@capture</code> .....	440, <u>719</u>	<code>\eq@hshift</code> .....	228
<code>\eq@centerlines</code> .....	413–415, 1432, 1493, 1804	<code>\eq@I@setsides</code> .....	1525
<code>\eq@check@density</code> .....	1006, <u>1020</u>	<code>\eq@impinging</code> .....	207
<code>\eq@check@shortskip</code> .....	642, <u>662</u>	<code>\eq@indentstep</code> ....	225, 230, 882, 1119, 1121, 1136, 1150, 1157, 1160
<code>\eq@cons</code> .....	<u>99</u>	<code>\eq@insert</code> .....	711
<code>\EQ@continue</code> ..	888, <u>919</u> , 925, 929, 951	<code>\eq@isIntertext</code> .....	229, 991, 1913, 2008, 2138, 2139
<code>\EQ@copy</code> 152–154, 200, 729, 737, 738, 761, 780, 785, 794, 796, 819, 1032, 1075, 1083, 1089, 1099, 1135, 1909, 2002, 2010, 2093, 2094		<code>\EQ@last@trial</code> .....	965, 1013
<code>\eq@curline</code> 209, 1038, 1306, 1312, 1313		<code>\eq@layout</code> ....	376, 938, 986, 999, 1006, 1037, <u>1070</u> , 1372, 1429, 1924
<code>\eq@delt</code> .....	1340, <u>1346</u>	<code>\eq@left</code> .....	320, 339, 1601
<code>\eq@dense@enough</code> .....	1025, <u>1319</u>	<code>\eq@left@a</code> .....	1602, 1607
<code>\eq@dense@enough@a</code> .....	1327, <u>1335</u>	<code>\eq@lines</code> 208, 896, 909, 977, 1034, 1037, 1038, 1191, 1206, 1211, 1320, 1337, 1341, 1350, 1351, 1454	
<code>\eq@dense@enough@b</code> .....	1338, <u>1347</u>	<code>\eq@linewidth</code> .....	226, 883, 934–936, 975, 1073, 1077, 1097, 1100, 1104, 1106, 1119, 1127, 1128, 1134, 1150, 1154, 1158, 1166, 1186, 1251, 1431, 1474, 1528, 1534, 1537, 1822, 1918
<code>\eq@density@factor</code> .....	372, <u>1334</u> , 1341, 1342		
<code>\EQ@displayinfo</code> .....	845, 858, 1872		
<code>\eq@dp</code> . 215, 980, 1048, 1066, 1067, 1409			
<code>\eq@dump@box</code> 549, 561, 1032, <u>1369</u> , 1571			
<code>\eq@failout</code> .....	890, 955, <u>963</u>		

<code>\eq@linewidths</code> .....	<code>\eq@revspaceb</code> .....
..... 883, 889, <u>922</u> , 924, 927, 942	827, <u>865</u>
<code>\eq@lrunpack</code> .....	<code>\eq@right</code> .....
805, <u>1709</u>	320, 339, 1604
<code>\eq@mark</code> .....	<code>\eq@right@a</code> .....
711	1605, 1608
<code>\eq@measure</code> .....	<code>\eq@saveparinfo</code> .....
443, <u>881</u>	457, <u>465</u>
<code>\eq@measure@lines</code> .....	<code>\eq@setnumber</code> 432, <u>477</u> , 1884, 1886, 2064
1041, <u>1274</u>	<code>\eq@setup@a</code> .....
<code>\eq@measurements</code> 900, 910, 969, 988,	434, 707
1039, 1055, <u>1270</u> , 1302, 1310, 1340	<code>\EQ@setwdL</code> .....
<code>\eq@ml@a</code> .....	439, 442, 749, 793
1280, <u>1282</u>	<code>\eq@shiftnumber</code> .....
<code>\eq@ml@continue</code> 1275, 1280, 1293, 1313	370, 524, 672, 990, 1078, <u>1170</u> ,
<code>\eq@ml@record@indents</code> ...	1172, 1177, 1188, 1195, 1213,
1040, <u>1257</u>	1216, 1222, 1227, 1229, 1432,
<code>\eq@ml@vspace</code> .....	1447, 1506, 1527, 1542, 1925, 2030
1315	<code>\eq@shortLHS</code> .....
<code>\eq@newline</code> .....	1022, <u>1029</u>
709, 710, <u>860</u>	<code>\eq@shortskiplimit</code> .....
<code>\eq@newlinea</code> .....	387, 388
<u>860</u>	<code>\EQ@shortskips</code> .....
<code>\eq@newlineb</code> .....	636, 643, 656, 663, 670, 676, 681
<u>860</u>	<code>\eq@startup</code> .....
<code>\eq@nextlayout</code> .....	435, <u>701</u>
957, <u>958</u>	<code>\eq@topspace</code> .....
<code>\eq@nulldisplay</code> .....	506, 515, 518, <u>634</u> , 1964, 1967
456, <u>839</u>	<code>\EQ@trial</code> ....
<code>\eq@nullleft</code> .....	892, <u>918</u> , 965, 1004,
1602, 1611	1228, 1232, 1906, 1912, 2124, 2138
<code>\eq@nullright</code> .....	<code>\eq@trial</code> .....
1605, 1612	888, 889, <u>923</u>
<code>\eq@number</code> .....	<code>\eq@trial@a</code> .....
194, 367, 368,	927, <u>931</u>
480, 481, 484, 486, 487, 490, 1890	<code>\eq@trial@b</code> .....
<code>\EQ@numbox</code> .....	937, <u>994</u> , 1072, 1074, 1086,
201, 488, 492, 544, 560, 664,	1124, 1131, 1147, 1163, 1168, 1823
1079, 1139, 1179, 1197, 1380,	<code>\eq@trial@c</code> ..
1393, 1403, 1410, 1425, 1555,	950, 994, <u>995</u> , 1019, 1072
1557, 1561, 1563, 1887, 1909, 1999	<code>\eq@trial@d</code> .....
<code>\eq@overrun</code> .....	937, <u>1019</u>
232	<code>\eq@trial@done</code> .....
<code>\eq@params</code> ..	951, <u>953</u>
541, 553, 884, <u>1357</u> , 1568	<code>\eq@trial@init</code> .....
<code>\eq@parshape</code> .....	957, 998
508, 522, 541,	<code>\eq@trial@p</code> .....
553, 987, 1230, <u>1356</u> , 1441, 1568	1002, <u>1030</u> , 1208
<code>\EQ@prebin@space</code> ..	<code>\eq@trial@save</code> ..
282, 294, 297, 716	967, 1004, 1013, 1232
<code>\EQ@prebin@space@a</code> .....	<code>\eq@trial@succeed</code> 949, 1009, 1024, 1026
282, 295	<code>\eq@try@layout@?</code> .....
<code>\eq@prelim</code> ....	<u>1071</u>
429, <u>451</u> , 1867, 2061	<code>\eq@try@layout@a</code> 1124, 1147, 1163, <u>1165</u>
<code>\eq@prev@badness</code> ...	1108, <u>1118</u> , 1131
1207, 1209, 1220	<code>\eq@try@layout@d</code> .....
<code>\eq@prev@lines</code> ....	1111, <u>1126</u>
1206, 1210, 1211	<code>\eq@try@layout@l</code> .....
<code>\eq@prevshape</code> .....	1101, <u>1149</u>
464, 467, 470	<code>\eq@try@layout@m</code> .....
<code>\eq@punct</code> .....	1821
<u>719</u>	<code>\eq@try@layout@multi</code> .....
<code>\EQ@QED</code> .....	1074, 1086, 1092, 1095
<u>277</u>	<code>\eq@try@layout@s</code> ...
<code>\eq@readjust</code> .....	1100, 1115, <u>1133</u>
833	<code>\eq@typeset@equation</code> ..
<code>\eq@recalc</code> .....	1377, 1383,
1042, <u>1053</u>	1389, 1400, 1406, 1413, 1418, 1566
<code>\eq@recalc@a</code> .....	<code>\eq@typeset@frame</code> ...
1055, <u>1057</u>	1376, 1382,
<code>\eq@recalc@b</code> .....	1388, 1399, 1405, 1412, 1417, 1590
1059, <u>1062</u>	<code>\eq@typeset@L@single</code> .....
<code>\eq@reinsert</code> .....	539
829	<code>\eq@typeset@leftnumber</code> .....
<code>\eq@remark</code> .....	1381, 1387, 1554
831	<code>\eq@typeset@LM</code> .....
<code>\eq@repack</code> .....	1379
734, <u>773</u>	
<code>\eq@repacka</code> .....	
780, 785, <u>814</u>	
<code>\eq@resume@parshape</code> .....	
698, <u>700</u>	
<code>\eq@retry@with@number</code> ...	
1005, 1171	
<code>\eq@retry@with@number@a</code> .....	
<u>1171</u>	
<code>\eq@revspace</code> .....	
827, <u>865</u>	

<code>\eq@typeset@LShifted</code> .....	1391	<code>\eqlineskip</code> .....	
<code>\eq@typeset@LT</code> .....	1385	. 167, 380, 381, 391, 394, 401,	
<code>\eq@typeset@R@single</code> .....	551	405, 504, 1359, 1394, 1420, 1970	
<code>\eq@typeset@RB</code> .....	1408	<code>\eqlineskiplimit</code> .....	167, 381, 1359
<code>\eq@typeset@rightnumber</code> .....		<code>\eqlinespacing</code> .....	167,
..... 1404, 1411, 1560		379, 391, 394, 401, 405, 504, 1358	
<code>\eq@typeset@RM</code> .....	1402	<code>\eqmargin</code> .....	167, 1134, 1146
<code>\eq@typeset@RShifted</code> .....	1415	<code>\eqnumcolor</code> .....	167, 490
<code>\eq@typeset@Unnumbered</code> ...	534, 1375	<code>\eqnumfont</code> .....	167, 490
<code>\eq@vadjust</code> .....	711	<code>\eqnumform</code> .....	167, 490
<code>\EQ@vimbox</code> .....	205, 730, 866	<code>\eqnumplace</code> .....	167, 530, 674, 1430
<code>\EQ@vimcopy</code> .....	206, 730, 873	<code>\eqnumsep</code> .....	167,
<code>\EQ@vims</code> .....	211	492, 1079, 1080, 1139, 1179, 1197	
<code>\eq@vspan</code> .....	197, 679,	<code>\eqnumside</code> 167, 234, 237, 240, 243,	
901, 912, 970, 980, 1054, 1067,		525, 528, 530, 669, 1175, 1181,	
1316, 1380, 1403, 1410, 1435, 1584		1430, 1459, 1469, 1507, 1543, 2021	
<code>\eq@wdCond</code> 224, 321, 756, 1084, 1175,		<code>\eqnumsize</code> .....	167, 490
1437, 1454, 1455, 1520, 1805, 2110		<code>\eqpunct</code> .....	632, 766
<code>\eq@wdL</code> 216, 725, 738, 743, 745, 748,		<code>\eqrightskip</code> .....	196
749, 754, 791, 793, 982, 1029,		<code>\eqstyle</code> .....	167, 386, 431, 2064
1097–1099, 1104, 1106, 1110,		<code>\errorcontextlines</code> .....	144
1121, 1127, 1129, 1151, 1324,		<code>\errorstopmode</code> ...	149, 732, 738, 2090
1349, 1434, 1914, 1916, 2026, 2084		<code>\everycr</code> .....	2070
<code>\eq@wdMin</code> .....	218, 979,	<code>\everydisplay</code> ....	311, 357, 426, 708
1054, 1065, 1433, 1488, 1490, 1534		<code>\everyhbox</code> .....	322, 340
<code>\eq@wdNum</code> .....	202, 478,	<code>\everymath</code> .....	708
492, 1140, 1180, 1198, 1436,		<code>\everypar</code> .....	454
1448, 1508, 1544, 1888, 1891, 1921		<code>\everyvbox</code> .....	325, 343
<code>\eq@wdR</code> 719, 733, 739, 740, 746, 754, 792		<code>\exhyphenpenalty</code> .....	1361
<code>\eq@wdRmax</code> .....	222, 2084	<code>\expandafter</code> ....	24, 40, 86, 124,
<code>\eq@wdT</code> 217, 901, 912, 970, 979, 1029,		311, 426, 522, 569, 570, 625, 1698	
1054, 1064, 1189, 1324, 1341,			
1348, 1433, 1474, 1488, 1489,			
1491, 1528, 1537, 1584, 1915, 1916			
<code>\EQ@widths</code> .....	920		
<code>\eqbinoffset</code> ....	167, 198, 1672, 1685		
<code>\eqbreakdepth</code> ...	186, 418, 1669, 1682		
<code>\eqcolor</code> .....	167		
<code>\eqdelimoffset</code> .....	183, 198, 1673		
<code>\eqfontsize</code> .....	167		
<code>\eqframe</code> .....	1573, 1584		
<code>\eqgrp@elt</code> .....	1958, 1992		
<code>\eqindent</code> .....	167, 251,		
254, 257, 260, 267, 507, 1429, 2018			
<code>\eqindentstep</code> .....	184, 373, 882		
<code>\eqinfo</code> .....	151, 887		
<code>\eqinterlinepenalty</code> ...	167, 861, 1360		
<code>\eqleftskip</code> .....	195		

## F

<code>\f@ur</code> .....	42, 1350, 1371, 1373
<code>\false@false@false</code> .....	1332, 1343
<code>\false@true@false</code> .....	1333, 1354
<code>\fboxrule</code> .....	389, 397, 1575
<code>\fboxsep</code> .....	398, 403, 1575
<code>\fi</code> .....	29, 30, 34,
37, 63, 68, 76–79, 110, 111, 131,	
132, 237, 245, 248, 254, 262,	
265, 275, 286, 296, 301, 399,	
427–429, 444, 452, 453, 475,	
482, 483, 494, 495, 505, 516,	
519, 531, 532, 535, 548, 559,	
570, 580, 590, 600, 614, 646,	
649, 650, 654, 677, 682–687,	
694, 721, 750, 751, 767, 808,	
817, 819, 827, 836, 852, 882,	
883, 927, 928, 933, 941, 942,	

1005, 1010, 1011, 1014, 1027, 1029, 1037, 1064, 1065, 1068, 1081, 1093, 1102, 1112, 1116, 1141, 1142, 1167, 1178, 1182, 1185, 1187, 1210, 1225, 1226, 1231, 1233, 1251, 1254, 1262, 1279, 1285, 1289, 1299, 1301, 1308, 1313, 1317, 1328, 1329, 1331–1333, 1336, 1343, 1344, 1354, 1362, 1364, 1372, 1397, 1423, 1449, 1456, 1461, 1466, 1471, 1479, 1484, 1486, 1490, 1496, 1505, 1511–1513, 1518, 1522, 1531, 1532, 1539, 1548– 1550, 1596, 1675, 1684, 1685, 1699, 1719, 1723, 1747, 1752, 1754, 1760, 1762, 1768, 1777, 1787, 1812, 1832, 1834, 1838, 1869, 1873, 1880, 1914, 1915, 1917, 1918, 1921–1926, 1935, 1936, 1943–1945, 1949, 1983, 1984, 2000, 2014, 2020, 2021, 2023, 2024, 2027, 2031, 2061, 2065, 2078, 2096, 2109, 2152, 2156	1942, 1947, 1948, 1961, 1993, 1999, 2002, 2003, 2062, 2065, 2070, 2072, 2091, 2093, 2110, 2114, 2119, 2123, 2128, 2133, 2137
<code>\finish@end</code> . . . 576, 599, 613, 621, <u>624</u>	<code>\grp@aligned</code> . . . . .
<code>\firstmark</code> . . . . . 119	. . . 416, 417, 1845, 1865, 1923, 1924, 1932, 1934, 1946, 1954, 2025
<code>\fontdimen</code> . . . . . 1730–1736	<code>\GRP@box</code> 1860, 1902, 1908, 1910, 1929, 1993, 1994, 2119, 2121, 2133, 2135
<code>\found@punct</code> . . . . . 606, 608, 618, 619, 628, 765, 766, 769	<code>\grp@eqs@numbered</code> . . . . . 1844, 1864, 1920, 1940, 1953, 1966
<code>\framebox</code> . . . . . 1576	<code>\grp@finish</code> . . . . . 1872, <u>1928</u>
<code>\freeze@glue</code> <u>80</u> , 391, 394, 401, 405, 504	<code>\grp@hasNumber</code> . . . . . 1080, 1843, 1847, 1853, 1869, 1873, 1940, 1966
<code>\frozen@everydisplay</code> . . . . . 840	<code>\GRP@label</code> 1861, 1876, 1878, 1879, 1883
<code>\futurelet</code> . . . . . 66, 71, 565, 572, 573	<code>\grp@linewidth</code> . . . . . 227, 1863, 1918, 1933, 1941, 2019
	<code>\GRP@numbox</code> . . . . . 203, 1080, 1887, 1969, 1973, 1974, 1976, 1979
	<code>\grp@override</code> . . . . . 2012, 2017
	<code>\grp@push</code> . . . . . 444, <u>1904</u>
	<code>\GRP@queue</code> . . . . . 1851, 1860, 1905, 1930, 1959, 2123, 2137
	<code>\grp@resetnumber</code> . . . . . 1873, 1899
	<code>\grp@setnumber</code> . . . . . 1869, 1882
	<code>\grp@shiftnumber</code> . . . . 1842, 1866, 1925, 1938, 1942, 1953, 1968, 2022
	<code>\GRP@top</code> . . . . . <u>1841</u>
	<code>\grp@wdL</code> . . . . . 219, 1862, 1914, 1931, 1947, 1952, 2026
	<code>\grp@wdNum</code> . . . . . 204, 1863, 1888, 1921, 1937, 1955, 2021
	<code>\grp@wdR</code> 220, 1862, 1917, 1931, 1948, 1952
	<code>\grp@wdT</code> 221, 1862, 1915, 1947, 1948, 2019
	<code>\GRP@wholebox</code> . . . . . 1903, 1957, 1973, 1978, 1986, 1988
<b>G</b>	
<code>\g@addto@macro</code> . . . . . 94	
<code>\gdef</code> . 85, 91, 136, 439, 608, 2124, 2138	
<code>\GenericInfo</code> . . . . . 145	
<code>\global</code> . . . . . 105, 126, 136, 281, 282, 311, 320, 321, 339, 365, 366, 419, 428, 453, 488, 489, 492, 511, 636, 663, 670, 676, 681, 697, 702, 716, 727, 729, 730, 736, 737, 772, 794, 798, 815, 866, 868, 873, 875, 888, 925, 951, 957, 965, 1316, 1666, 1679, 1805, 1859–1866, 1876, 1879, 1883, 1887, 1905, 1908, 1914, 1915, 1917, 1918, 1920, 1921, 1923–1925, 1934,	
	<b>H</b>
	<code>\halign</code> . . . . . 854, 2074
	<code>\hbox</code> . . . . . 547, 558, 727, 736, 737, 790, 794, 795, 798, 799, 815, 1049, 1277, 1283, 1425, 1563, 1580, 1584, 1594, 1909, 1996, 2037, 2040, 2042, 2091– 2094, 2106, 2107, 2109, 2134, 2145
	<code>\hfil</code> 1425, 1563, 2036, 2039, 2041, 2043
	<code>\hfuzz</code> . . . . . 886, 1001, 1085, 1362–1364, 1366, 1551
	<code>\hiderel</code> . . . . . <u>291</u>
	<code>\hsize</code> . 158, 712, 1425, 1563, 2116, 2130

<code>\hskip</code> . . .	1050, 1674, 1827, 1828, 2108	<code>\ifvoid</code> . . . . .	1721
<code>\hss</code> . . . . .	547, 558, 1587, 1594	<code>\ifx</code> . . . . .	29, 30, 34, 37, 68, 105, 108, 126, 237, 254, 480, 484, 569, 576–578, 586–588, 594– 598, 612, 765, 819, 827, 924, 1245, 1695, 1696, 1878, 2065, 2156
<code>\ht</code> . . . . .	154, 664, 1309, 1380, 1403, 1410, 1555, 1561, 1740, 1753, 1973, 1974, 1978, 1979, 2054	<code>\ignorespaces</code> . . . . .	1815, 2116, 2130
<b>I</b>			
<code>\if</code> . . . .	79, 240, 244, 257, 261, 267, 399, 429, 444, 479, 503, 509, 510, 523, 524, 545, 556, 637, 643, 651, 669, 672, 674, 691, 933, 1003, 1005, 1006, 1008, 1022, 1025, 1037, 1078–1080, 1096, 1137, 1167, 1172, 1175, 1181, 1187, 1188, 1210, 1214, 1227, 1372, 1395, 1421, 1447, 1453, 1459, 1469, 1490, 1493, 1503, 1506, 1507, 1527, 1535, 1542, 1543, 1545, 1591, 1869, 1873, 1913, 1919, 1923–1925, 1932, 1938, 1940, 1946, 1966, 1968, 2008, 2021, 2022, 2025, 2061	<code>\immediate</code> . . . . .	146
<code>\if@display</code> . . . . .	357, 2144	<code>\indent</code> . . . . .	452
<code>\if@inlabel</code> . . . . .	428, 452	<code>\inf@bad</code> . . . . .	43, 1279, 1285
<code>\if@nobreak</code> . . . . .	453	<code>\insert</code> . . . . .	141, 711
<code>\if@noskipsec</code> . . . . .	427	<code>\int@a</code> . . . . .	45, 1135, 1136, 1151– 1153, 1156, 1160, 1187, 1191, 1193, 1209, 1217, 1258, 1260–1262
<code>\if@tempswa</code> . . . . .	2109	<code>\int@b</code> . . . . .	45, 1143, 1210, 1211, 1262, 1266, 1348, 1349, 1351, 1352
<code>\ifcase</code> 76, 77, 468, 777, 820, 1743, 2096		<code>\int@c</code> . . . . .	47
<code>\ifcat</code> . . . . .	1783	<code>\intereqpenalty</code> . . . . .	167, 639
<code>\ifdim</code> . . . . .	646, 665, 667, 675, 680, 739, 743, 849, 882, 883, 934, 1029, 1064, 1065, 1082, 1097, 1100, 1104, 1138, 1175, 1182, 1189, 1251, 1287, 1292, 1297, 1317, 1324, 1343, 1354, 1362, 1364, 1454, 1459, 1462, 1469, 1477, 1479, 1482, 1484, 1509, 1515, 1520, 1529, 1752, 1754, 1760, 1762, 1768, 1777, 1811, 1914, 1915, 1917, 1918, 1921, 1933, 1941, 2020, 2023, 2029	<code>\intereqskip</code> . . . . .	167, 639
<code>\iffalse</code> . . . . .	927, 942, 1331–1333	<code>\interlinepenalty</code> . . . . .	715, 1360
<code>\ifmmode</code> . . . . .	1832, 1834, 1838	<code>\intermath@penalty</code> . .	1814, 1825, 1826
<code>\ifnum</code> . .	63, 78, 279, 296, 299, 527, 721, 817, 819, 1037, 1068, 1191, 1211, 1217, 1262, 1279, 1285, 1306, 1313, 1320, 1337, 1454, 1669, 1682, 1685, 1715, 1812, 1997	<code>\intertext</code> . . . . .	458
<code>\iftrue</code> . . . . .	1331, 1333	<b>K</b>	
<code>\ifvmode</code> . . . . .	2078	<code>\keep@glue</code> . . .	81, 295, 722, 879, 1707
		<code>\kern</code> . . . . .	544, 560, 1398, 1558, 1564, 1576, 1582, 1583, 1595, 1778, 1970, 1981, 1982, 2147
<b>L</b>			
<code>\label</code> . . . . .	362	<code>\lastbox</code> . . . . .	726, 735, 779, 784, 789, 868, 875, 1047, 1276, 1371, 1709, 1717, 1720, 1725, 1995, 1999, 2002, 2003, 2089
<code>\lastpenalty</code> . . .	296, 299, 721, 777, 816, 1712, 1713, 1812, 1997, 2096	<code>\lastskip</code> . . . . .	1050, 1291, 1297, 1298, 1316, 1317, 1811
<code>\lastskip</code> . . . . .	1050,	<code>\latex@end</code> . . . . .	624
<code>\lccode</code> . . . . .	1784	<code>\leavevmode</code> . . . . .	427, 428, 1831
<code>\left</code> . .	320, 339, 355, 1598, 1615, 1625	<code>\leftmargin</code> . . . . .	850
<code>\leftmargin</code> . . . . .	850	<code>\leftskip</code> 159, 507, 512, 544, 560, 665, 714, 885, 914, 1197, 1198, 1202, 1229, 1240, 1290, 1438, 1497, 1526, 1530, 1534, 1537, 1592, 1594	
<code>\leftskip</code> 159, 507, 512, 544, 560, 665, 714, 885, 914, 1197, 1198, 1202, 1229, 1240, 1290, 1438, 1497, 1526, 1530, 1534, 1537, 1592, 1594		<code>\let</code> . . .	29, 39, 40, 45–58, 65, 68, 70, 93, 95–97, 100, 105, 126, 136,

138, 139, 212–214, 229, 276, 277, 280–282, 292–294, 305– 310, 314–320, 323, 326, 331– 339, 341, 344, 349–355, 363, 365, 366, 368, 370, 371, 413– 417, 419, 423, 447, 458, 464, 481, 489, 493, 498, 511, 565, 606, 636, 663, 670, 676, 681, 702, 709–711, 716, 772, 880, 899, 902, 908, 918, 920, 921, 937, 955, 957, 965, 969, 971, 1036, 1037, 1039, 1045, 1055, 1059, 1072, 1170, 1177, 1195, 1213, 1216, 1222, 1229, 1275, 1279, 1293, 1313, 1340, 1356, 1602, 1605, 1614, 1615, 1618, 1651, 1661, 1662, 1670, 1683, 1687, 1691, 1693, 1703, 1704, 1795, 1797, 1802, 1804, 1809, 1841–1845, 1847, 1853, 1859, 1861, 1864–1866, 1876, 1879, 1883, 1885, 1889, 1890, 1920, 1923–1925, 1934, 1942, 1958, 1961, 1989, 2006, 2030, 2050, 2062, 2065, 2067, 2068, 2138, 2139	\m@@symDeB ..... <u>305</u> , 354 \m@@symDeL ..... 353 \m@@symDeI ..... <u>305</u> \m@@symDeR ..... <u>305</u> , 353 \m@@symRel ..... <u>305</u> , 350 \m@Bin 292, 314, 331, 349, 1670, 1683, 1703 \m@DeA ..... 317, 336, 352, 1661 \m@DeB ..... 316, 335, 351, 1651 \m@DeL ..... 316, 335, 351, 1651 \m@DeR ..... 316, 335, 351, 1651 \m@ne ..... 1312, 1367, 1679 \m@Rel ..... 293, 314, 332, 349, 1703 \m@th ..... 2037, 2040, 2042 \mark ..... 142, 711 \mark@lhs ..... <u>278</u> , 304, 305 \mark@lhs@a ..... 283, <u>288</u> \mathaxis ..... 1736, 1775 \mathchardef ..... 1663, 1664 \mathchars@reset ..... <u>94</u> \mathclose ..... 1637–1642 \mathindent . 269, 272, 1526, 1528, 2028 \mathopen ..... 1630–1635 \mathord ..... 2040 \mathrel ..... 291, 1645–1650 \Mathstrut@ ..... 2050, 2051, 2078 \mathsurround ..... 1808, 1819, 2145 \maxdimen 148, 230, 667, 712, 732, 863, 882, 1001, 1054, 1726, 2083, 2090 \maxint ..... <u>44</u> , 1187 \meaning ..... 104, 107, 124, 125 \medmuskip ..... 313, 330 \message ..... 83 \MessageBreak ..... 753, 755, 898, 907, 911, 913, 969, 970, 996, 1203, 1431–1441, 1952–1955, 1979 \mkern ..... 2145 \moveright ..... 1594 \mskip ..... 289, 295 \multiply ..... 1341, 1350, 1351, 1489, 1491, 1667, 1680
M	
\m@@Bin ..... <u>292</u> , 349, 1670, 1703 \m@@DeA ..... 352, 1661 \m@@DeB ..... 351, <u>1651</u> \m@@DeL ..... 351, <u>1651</u> \m@@DeR ..... 351, <u>1651</u> \m@Rel ..... <u>292</u> , 349, 1703 \m@@symBin ..... <u>305</u> , 350 \m@@symDeA ..... <u>305</u> , 354	N
\NeedsTeXFormat ..... 2 \newbox ..... 1902, 1903 \newcommand ..... 23, 291, 632, 1573, 1782, 1827– 1829, 2100, 2101, 2104, 2142, 2154 \newcount ..... 43, 44, 186–188, 190, 191, 208–211, 497, 1600, 2034 \newcounter ..... 1875	



<code>\newdimen</code> . . . . .	165, 169, 170, 181, 184, 202, 204, 215–228, 231, 269, 719
<code>\newenvironment</code> . . . . .	422, 446, 1795, 1797, 1846, 1852, 2058, 2113, 2127
<code>\newif</code> . . . . .	358
<code>\newlength</code> . . . . .	179, 180, 189, 195–197
<code>\newmuskip</code> . . . . .	182, 183, 192, 193, 198
<code>\newsavebox</code> . . . . .	199–201, 203
<code>\newskip</code> . . . . .	2033, 2099
<code>\newtoks</code> . . . . .	41, 185, 919, 1851
<code>\next@label</code> . . . . .	362, 365, 489, 1883
<code>\next@label@pre</code> . . . . .	362–364, 366
<code>\noalign</code> . . . . .	2070
<code>\nobreak</code> . . . . .	540, 552, 1567, 1593
<code>\noexpand</code> . . . . .	39, 130, 362
<code>\noindent</code> . . . . .	455, 542, 554, 704, 1371, 1569, 1592, 1711, 2116, 2130
<code>\nointerlineskip</code> . . . . .	542, 554, 646, 1049, 1205, 1569, 1593, 1710
<code>\nref</code> . . . . .	<u>2155</u>
<code>\nulldelimiterspace</code> . . . . .	1626
<code>\nullfont</code> . . . . .	117
<code>\number</code> . . . . .	5, 16, 17, 86, 896, 909, 1153, 1261, 1306, 1307, 1688, 1713, 1790, 2054
<b>O</b>	
<code>\options</code> . . . . .	<u>23</u>
<code>\options@a</code> . . . . .	24, <u>27</u>
<code>\options@b</code> . . . . .	<u>27</u>
<code>\options@c</code> . . . . .	<u>27</u>
<code>\options@d</code> . . . . .	<u>27</u>
<code>\or</code> . . . . .	76, 470, 782, 787, 803, 823, 825, 826, 828, 830, 832, 1744, 1745
<b>P</b>	
<code>\p@</code> . . . . .	714, 1348, 1350, 1362, 1499, 1517, 1618
<code>\PackageError</code> . . . . .	128, 812
<code>\PackageWarning</code> . . . . .	461
<code>\par</code> . . . . .	452, 457, 856, 2118, 2132
<code>\parfillskip</code> . . . . .	158, 714, 1365, 1523, 1552
<code>\parindent</code> . . . . .	162
<code>\parshape</code> . . . . .	468, 471, 1033, 1073, 1120, 1128, 1145, 1153, 1166, 1306, 1307, 1822, 2115, 2129
<code>\parskip</code> . . . . .	506, 515, 518, 639, 640, 644, 648, 653, 656, 1424, 1964, 1967
<code>\PassOptionsToPackage</code> . . . . .	10
<code>\peek@a</code> . . . . .	565, 568, 572
<code>\peek@b</code> . . . . .	565, 570
<code>\peek@branch</code> . . . . .	<u>564</u>
<code>\peek@skip@space</code> . . . . .	567, 572
<code>\peek@skipping@spaces</code> . . . . .	567, 609
<code>\peek@space</code> . . . . .	565, 569
<code>\penalty</code> . . . . .	284, 289, 296, 300, 639, 690, 705, 721, 822, 835, 864, 870, 877, 879, 1123, 1167, 1393, 1419, 1557, 1563, 1676, 1706, 1707, 1724, 1808, 1814, 1909, 1969, 1976, 2073, 2092, 2094, 2107
<code>\postdisplaypenalty</code> . . . . .	690, 842
<code>\postmath</code> . . . . .	1814, 1829, 1839
<code>\prebinoppenalty</code> . . . . .	. . . . .
	191, 296, 1667, 1668, 1680, 1681
<code>\predisplaypenalty</code> . . . . .	453, 842
<code>\predisplaysize</code> . . . . .	646, 657, 665, 667, 846
<code>\prelim@sub@depth</code> . . . . .	. . . . .
	1729, 1741, 1752, 1768
<code>\prelim@sup@base</code> . . . . .	1729, 1740, 1760
<code>\premath</code> . . . . .	1810, 1829, 1831
<code>\prerelpenalty</code> . . . . .	190, 299, 300, 374
<code>\pretolerance</code> . . . . .	161, 712, 1367
<code>\prevgraf</code> . . . . .	466, 467, 846, 1034
<code>\ProcessOptions</code> . . . . .	12
<code>\protected@edef</code> . . . . .	633, 1893
<code>\providecommand</code> . . . . .	102, 114, 633, 1736
<code>\ProvidesPackage</code> . . . . .	3
<b>R</b>	
<code>\raise</code> . . . . .	547, 558, 1764
<code>\rangle</code> . . . . .	1792
<code>\rbrace</code> . . . . .	1794
<code>\rel@break</code> . . . . .	284, <u>292</u> , 305
<code>\rel@mark</code> . . . . .	<u>292</u>
<code>\relax</code> . . . . .	6, 8, 12, 19, 21, 29, 80–82, 100, 144, 237, 254, 280, 294, 323, 326, 341, 344, 373, 374, 390, 400, 418, 471, 512, 716, 749, 793, 812, 824, 853, 902, 932, 955, 971, 1055, 1058, 1066, 1068, 1073, 1121, 1129, 1146, 1161, 1166, 1186, 1209, 1236, 1239, 1242, 1245, 1248, 1249, 1293, 1313, 1364, 1489, 1491, 1494, 1575, 1614, 1663, 1664, 1673, 1674, 1685, 1691, 1822, 1989, 2006, 2067, 2107, 2115, 2129, 2156
<code>\relpenalty</code> . . . . .	717

<code>\remove@to@nnil</code> .....	521	<code>\skip@</code> .....	56
<code>\renewcommand</code> .....	2143	<code>\skip@a</code> ....	<u>54</u> , 1291, 1292, 1298, 1303
<code>\renewenvironment</code> .....	1830	<code>\skip@b</code> .....	<u>54</u>
<code>\replicate</code> .....	<u>83</u> , 1160	<code>\skip@c</code> .....	<u>54</u> , 1050, 1555,
<code>\replicate@a</code> .....	86, <u>89</u>		1556, 1561, 1562, 1974, 1975, 1978
<code>\RequirePackage</code> .....	14, 21	<code>\sp</code> .....	1696
<code>\right</code> .	320, 339, 355, 1599, 1615, 1627	<code>\space</code> .....	145,
<code>\right@delim@code</code> .....			153, 467, 513, 745, 896, 898,
....	1688, 1707, 1713, 1774, 1778		909, 969, 996, 1121, 1128, 1129,
<code>\rightmargin</code> .....	851		1145, 1146, 1153, 1160, 1161,
<code>\rightskip</code> .....	159, 507,		1203, 1253, 1303, 1353, 1429, 2054
	714, 886, 914, 1085, 1199, 1202,	<code>\splitbotmark</code> .....	122
	1240, 1438, 1499, 1517, 1521, 1551	<code>\splitfirstmark</code> .....	121
<code>\rlap</code> .....	544, 547, 558, 560	<code>\ss@delim@a</code> .....	1688, 1691
<code>\romannumeral</code> .....	86	<code>\ss@finish</code> .....	1697, 1705
<b>S</b>			
<code>\sb</code> .....	1695	<code>\ss@scan</code> .....	1609, <u>1687</u>
<code>\sbox</code> .....	488, 1887	<code>\ss@scan@a</code> .....	1693, 1694, 1704
<code>\scriptfont</code> .....	1734, 1735	<code>\ss@scan@b</code> .....	1698, 1700, 1702
<code>\set@label</code> .....	487, <u>633</u>	<code>\stepcounter</code> .....	481
<code>\setbox</code> .....	703, 726,	<code>\string</code> ...	93, 104, 118–123, 129, 2068
	727, 729, 730, 735–737, 779,	<code>\strip@prefix</code> .....	124
	784, 789, 790, 794, 798, 815,	<code>\strut</code> .....	2050
	866, 868, 873, 875, 1000, 1047,	<code>\sub@base@one</code> .....	1732, 1751
	1276, 1277, 1283, 1371, 1709,	<code>\sub@base@two</code> .....	1733, 1767
	1717, 1718, 1720, 1725, 1860,	<code>\sub@depth</code> .....	1728,
	1908, 1957, 1993, 1995, 1996,		1751, 1752, 1754–1756, 1767–1770
	1999, 2002, 2003, 2037, 2040,	<code>\sub@drop</code> .....	1735, 1741
	2042, 2069, 2089, 2091, 2093,	<code>\subsup@flag</code> .....	
	2109, 2114, 2119, 2128, 2133, 2145		<u>1687</u> , 1712, 1715, 1716, 1722, 1743
<code>\setcounter</code> .....	1894, 1895, 1900	<code>\sup@base</code>	1728, 1759, 1760, 1762–1764
<code>\setkeys</code> .....	25, 430, 1868, 2063	<code>\sup@base@one</code> .....	1731, 1759
<code>\setlength</code> .....	384,	<code>\sup@drop</code> .....	1734, 1740
	664, 679, 740, 792, 1063, 1075,	<code>\sym@xheight</code> .....	1730, 1753, 1761
	1084, 1099, 1119, 1127, 1134,	<b>T</b>	
	1150, 1157, 1158, 1186, 1198,	<code>\tabskip</code> .....	2038, 2043, 2071
	1199, 1240, 1251, 1287, 1288,	<code>\temp@a</code> .....	1237, 1241, 1245, 1253
	1380, 1396, 1403, 1410, 1455,	<code>\textchar</code> .....	2147, 2151
	1474, 1488, 1497, 1499, 1528,	<code>\textfont</code> .....	1730–1733, 1736
	1534, 1537, 1551, 1555, 1561,	<code>\textmath@setup</code> .....	
	1581, 1740, 1741, 1753, 1761,		.... 323, 326, 341, 344, 348, 2109
	1775, 1916, 1931, 1972, 1974, 2019	<code>\the</code> .....	153, 154, 158–162,
<code>\showbox</code> .....	148, 738, 2090		311, 359, 386, 390, 400, 426,
<code>\showboxbreadth</code> .....			431, 467, 512, 603, 619, 640,
....	148, 732, 1726, 2083, 2090		656, 657, 745, 746, 749, 753,
<code>\showboxdepth</code>	148, 732, 1726, 2083, 2090		754, 756, 793, 846–848, 850,
<code>\showlists</code> .....	732, 1726, 2083		851, 883, 901, 912, 914, 929,
<code>\showthe</code> .....	738		936, 970, 975, 977, 979, 980,
<code>\sixt@n</code> .....	146, 1337		982, 1073, 1083, 1089, 1090,
			1098, 1106, 1110, 1121, 1128,

1129, 1145, 1146, 1154, 1160,  
 1161, 1166, 1193, 1202, 1206,  
 1207, 1215, 1220, 1253, 1261,  
 1285, 1303, 1309, 1342, 1353,  
 1431, 1433–1440, 1822, 1905,  
 1930, 1952, 1955, 1959, 1978,  
 1979, 2054, 2064, 2123, 2137, 2147  
`\theb@le` ..... 79,  
 656, 754, 1432, 1434, 1953, 1954  
`\theequation` ... 481, 1893, 1896, 1897  
`\theparentequation` ..... 1893, 1896  
`\thickmuskip` ..... 289, 313, 330, 741  
`\thinspace` ..... 632, 2149, 2151  
`\thr@@` ..... 135, 466, 819, 1320, 1706  
`\times` ..... 2154  
`\toks@` ..... 58, 618, 619  
`\toks@a` ..... 57, 585, 590, 603  
`\toks@b` ..... 57, 593, 603  
`\toks@c` ..... 57, 590, 603  
`\toks@d` ..... 57  
`\toks@e` ..... 57  
`\toks@f` ..... 57  
`\toksdef` ..... 59–62  
`\tolerance` ..... 161, 1367  
`\topmark` ..... 118  
`\true@false@true` ..... 1331, 1343  
`\true@true@true` ..... 1354  
`\tw@` ..... 289, 726, 727, 735–737,  
 779, 784, 789, 790, 795, 799,  
 815, 1047–1049, 1152, 1156,  
 1276, 1277, 1283, 1285, 1287,  
 1288, 1309, 1371, 1372, 1696,  
 1717, 1718, 1721, 1722, 1730–  
 1736, 1753, 1756, 1761, 1764,  
 1770, 1996, 2089, 2090, 2092, 2094  
`\twang@adjust` .. 1755, 1763, 1769, 1772

**U**

`\unhbox` ... 549, 561, 727, 736, 737,  
 790, 799, 837, 1049, 1277, 1283,  
 1372, 1373, 1571, 1711, 1721,  
 1742, 1887, 1996, 2056, 2092, 2094  
`\unhcopy` .... 736, 795, 815, 1032, 2092  
`\unpenalty` ..... 727,  
 728, 736, 737, 783, 788, 790,  
 795, 799, 804, 818, 867, 874,  
 1291, 1298, 1316, 1712, 1714,  
 1725, 1814, 1818, 2001, 2088, 2105  
`\unskip` ..... 727,  
 728, 736, 737, 781, 790, 795,  
 799, 802, 815, 1050, 1283, 1291,  
 1298, 1316, 1710, 1711, 1725,  
 1811, 1818, 2092, 2094, 2095, 2105  
`\unvbox` 866, 869, 873, 876, 1910, 1988,  
 1994, 2010, 2120, 2121, 2134, 2135  
`\upshape` ..... 174  
`\usebox` ..... 2111

**V**

`\vadjust` ..... 140, 711  
`\value` ..... 1894, 1900  
`\vbox` ..... 703, 866, 873, 1000,  
 1583, 1594, 1908, 1957, 1993,  
 2069, 2114, 2119, 2120, 2128, 2133  
`\vglue` ..... 1556, 1562, 1975  
`\voidb@x` ..... 1718, 1860  
`\vrule` ..... 81, 1626  
`\vskip` 506, 515, 518, 695, 1964, 1967, 2009  
`\vss` ..... 1585, 1594  
`\vtop` ..... 2120, 2134

**W**

`\wd` ..... 153, 492, 560, 740,  
 746, 753, 791, 792, 1047, 1075,  
 1079, 1080, 1083, 1089, 1099,  
 1135, 1139, 1179, 1197, 1276,  
 1285, 1287, 1288, 2054, 2110, 2147  
`\widowpenalty` ..... 715, 1360  
`\wlog` ..... 153  
`\write` ..... 146

**X**

`\xdef` 30, 100, 512, 602, 619, 628, 749,  
 769, 793, 845, 974, 1688, 1713, 2045

**Z**

`\z@` . 63, 81, 166, 296, 320, 321, 339,  
 478, 547, 558, 646, 703, 714,  
 715, 719, 725, 731, 733, 739,  
 790, 791, 849, 883, 886, 1000,  
 1054, 1085, 1143, 1175, 1199,  
 1229, 1258, 1277, 1283, 1292,  
 1297, 1313, 1317, 1340, 1366,  
 1446, 1452, 1454, 1458, 1463,  
 1479, 1484, 1488, 1492, 1499,  
 1502, 1515, 1520, 1529, 1530,  
 1533, 1551, 1580, 1583, 1594,  
 1674, 1709, 1711, 1720–1722,  
 1725, 1740–1742, 1805, 1808,  
 1819, 1862, 1863, 1891, 1995,

1996, 2020, 2021, 2037, 2040,	\z@skip . . . 197, 714, 843, 844, 885,
2042, 2054, 2056, 2069, 2071,	1054, 1365, 1523, 1552, 2038, 2071
2072, 2084, 2109–2111, 2145, 2147	
\z@rule . . . . . <u>81</u> , 1576, 1724	\zero@bop . . . . . <u>1662</u>