

The flexisym package

Morten Høgholm
mh.ctan@gmail.com

2008/07/23 v0.97

User's guide

For now, the user's guide is in breqn.

Implementation

1 flexisym

```
1 \<package>
2 \ProvidesPackage{flexisym}[2008/07/23 v0.97]
3 \let\@xp\expandafter \let\@nx\noexpand
4 \edef\do{%
5   \@nx\AtEndOfPackage{%
6     \catcode\number'\=\number\catcode'\
7     \relax
8   }%
9 }
10 \do \let\do\relax
11 \catcode'\=12
12 \let\@sym\@gobble
13 \DeclareOption{robust}{%
14   \def\@sym#1{%
15     \ifx\protect\@typeset@protect \else\protect#1\@xp\@gobblefour\fi
16   }%
17 }
18 \def\mg@bin{2}% binary operators
19 \def\mg@rel{2}% relations
20 %%\def\mg@nre{B}% negated relations
21 \def\mg@del{3}% delimiters
22 %%\def\mg@arr{B}% arrows
23 \def\mg@acc{0}% accents
24 \def\mg@cop{3}% cumulative operators (sum, int)
```

```

25 \def\mg@latin{1}% (Latin) letters
26 \def\mg@greek{1}% (lowercase) Greek
27 \def\mg@Greek{0}% (capital) Greek
28 %%\def\mg@bflatin{4}% bold upright Latin letters ?
29 %%\def\mg@Bbb{B}% blackboard bold
30 \def\mg@cal{2}% script/calligraphic
31 %%\def\mg@frak{5}% Fraktur letters
32 \def\mg@digit{0}% decimal digits % 1 = oldstyle, 0 = capital
33 \expandafter\let\csname MathChar \endcsname\mathchar
34 \expandafter\let\csname Delimiter \endcsname\delimiter
35 \expandafter\let\csname Radical \endcsname\radical
36 \newcommand{\MathChar}{}
37 \edef\MathChar{\csname MathChar \endcsname\noexpand\string}
38 \newcommand{\Delimiter}{}
39 \edef\Delimiter{\csname Delimiter \endcsname\noexpand\string}
40 \newcommand{\Radical}{}
41 \edef\Radical{\csname Radical \endcsname\noexpand\string}
42 \let\sumlimits\displaylimits
43 \let\intllimits\nolimits
44 \let\namelimits\displaylimits
45 \edef\m@Ord#1#2#3{\csname MathChar \endcsname"0#1#2#3 }
46 \edef\m@Var#1#2#3{\csname MathChar \endcsname"7#1#2#3 }
47 \edef\m@Bin#1#2#3{\csname MathChar \endcsname"2#1#2#3 }
48 \edef\m@Rel#1#2#3{\csname MathChar \endcsname"3#1#2#3 }
49 \edef\m@Pun#1#2#3{\csname MathChar \endcsname"6#1#2#3 }
50 \edef\m@COs#1#2#3{\csname MathChar \endcsname"1#1#2#3 \sumlimits}
51 \edef\m@COi#1#2#3{\csname MathChar \endcsname"1#1#2#3 \intllimits}
52 \def\delim@a#1#2#3#4{\ifx\relax#1#2#3#4\else#1\fi #2#3#4}
53 \def\delim@b#1#2#3#4{\ifx\relax#1#2#3#4\else#1\fi }
54 \def\@tempa{%
55   \@nx\@xp\@nx\delim@a\@nx\csname sd###1##2##3\@nx\endcsname ##1##2##3 }
56 \edef\m@DeL#1#2#3{\csname Delimiter \endcsname"4\@tempa}
57 \edef\m@DeR#1#2#3{\csname Delimiter \endcsname"5\@tempa}
58 \edef\m@DeB#1#2#3{\csname Delimiter \endcsname"0\@tempa}
59 \edef\m@DeA#1#2#3{\csname Delimiter \endcsname"3\@tempa}
60 \edef\m@Rad#1#2#3{\csname Radical \endcsname"\@tempa}
61 \def\do#1#2{\@xp\def\csname sd@#1\endcsname{#2}}
62 \do{300}{028}
63 \do{301}{029}
64 \do{302}{05B}
65 \do{303}{05D}
66 \do{304}{262}
67 \do{305}{263}
68 \do{306}{264}
69 \do{307}{265}
70 \do{308}{266}
71 \do{309}{267}
72 \do{30A}{268}
73 \do{30B}{269}
74 \do{30C}{26A}

```

```

75 \do{30D}{26B}
76 \do{30E}{13D}
77 \do{30F}{26E}
78 \do{340}{37A}
79 \do{341}{37B}
80 \do{33A}{33A}
81 \do{33B}{33B}
82 \do{33E}{33E}
83 \do{33C}{26A}
84 \do{33D}{26B}
85 \do{378}{222}
86 \do{379}{223}
87 \do{33F}{26C}
88 \do{37E}{22A}
89 \do{37F}{22B}
90 \do{377}{26D}
91 \do{30F}{26E}
92 \def\m@Acc#1#2#3#4{\mathaccent"#1#2#3{#4}}
93 \def\@symAcc{\@sym}
94 \let\@symtype\@firstofone
95 \def\@symOrd#1#2{\@symtype\mathord{\OrdSymbol{#2}}}
96 \def\@symVar{\@symOrd}
97 \def\@symBin#1#2{\@symtype\mathbin{\OrdSymbol{#2}}}
98 \def\@symRel#1#2{\@symtype\mathrel{\OrdSymbol{#2}}}
99 \def\@symPun#1#2{\@symtype\mathpunct{\OrdSymbol{#2}}}
100 \def\@symCoi#1#2{\@symtype{\mathop{\OrdSymbol{#2}}\intlimits}}
101 \def\@symCoi#1#2{\@symtype{\mathop{\OrdSymbol{#2}}\sumlimits}}
102 \def\@symOpe#1#2{\@symtype\mathopen{\OrdSymbol{#2}}}
103 \def\@symClo#1#2{\@symtype\mathclose{\OrdSymbol{#2}}}
104 \def\@symDeL#1#2{\@symtype\mathopen{\OrdSymbol{#2}}}
105 \def\@symDeR#1#2{\@symtype\mathclose{\OrdSymbol{#2}}}
106 \def\@symDeB#1#2{\@symtype\mathord{\OrdSymbol{#2}}}
107 \def\@symInn#1#2{\@symtype\mathinner{\OrdSymbol{#2}}}
108 \def\@xn#1{\@xp\@nx\csname#1\endcsname}
109 \let\sym@global\global
110 \def\DeclareFlexSymbol#1#2#3#4{%
111   \begingroup
112   \edef\@tempb{\@nx\@sym\@nx#1\@xn#2\@xn#3\@xn#4}%
113   \ifcat\@nx#1\relax
114     \sym@global\let#1\@tempb
115   \else
116     \sym@global\mathcode'#1="8000\relax
117     \lccode'\~='#1\relax
118     \lowercase{\sym@global\let~\@tempb}%
119   \fi
120   \endgroup
121 }
122 \def\DeclareFlexCompoundSymbol#1#2#3{%
123   \@xp\DeclareRobustCommand\@xp#1\@xp{\csname @sym#2\endcsname#1{#3}}%
124   \sym@global\let#1#1\relax

```

```

125 }
126 \DeclareRobustCommand\textchar{\text@char\textfont}
127 \DeclareRobustCommand\scriptchar{\text@char\scriptfont}%
128 \def\text@char@a{\?\endgroup}%
129 \def\text@char@sym#1#2#3{%
130   \begingroup
131     \let\@sym\relax % defense against infinite loops
132     \the\text@script@char#3%
133     \afterassignment\text@char@a
134     \chardef\?= "%
135 }
136 \def\text@char#1#2{\begingroup\check@mathfonts
137   \let\text@script@char#1\let\@sym\text@char@sym
138   \let\@syntype\@secondoftwo \let\OrdSymbol\@firstofone
139   \let\ifmmode\iftrue \everymath{\$\gobble}%$
140   \def\mkern{\mskip\z@\let\mskip\mkern
141     \ifcat\relax\noexpand#2#2%
142     \else
143       \lccode'\~=\expandafter'\string#2\relax
144       \lowercase{\~}%
145     \fi
146   \endgroup
147 }
148 \providecommand\textprime{}
149 \DeclareRobustCommand\textprime{\leavevmode
150   \raise.8ex\hbox{\text@char\scriptfont\prime}%
151 }
152 \@ifundefined{resetMathstrut@}{\}{%
153   \def\resetMathstrut@{%
154     \setbox\z@\hbox{\textchar\vert}%
155     \ht\Mathstrutbox@ \ht\z@ \dp\Mathstrutbox@ \dp\z@
156   }%
157 }
158 \@ifundefined{rightarrowfill@}{\}{%
159   \def\rightarrowfill@#1{\m@th\setboxz@h{#1\relbar$}\ht\z@\z@
160     $#1\copy\z@\mkern-6mu\cleaders
161     \hbox{#1\mkern-2mu\box\z@\mkern-2mu$}\hfill
162     \mkern-6mu\OrdSymbol{\rightarrow}$}
163   \def\leftarrowfill@#1{\m@th\setboxz@h{#1\relbar$}\ht\z@\z@
164     $#1\OrdSymbol{\leftarrow}\mkern-6mu\cleaders
165     \hbox{#1\mkern-2mu\copy\z@\mkern-2mu$}\hfill
166     \mkern-6mu\box\z@$}
167   \def\leftrightarrowfill@#1{\m@th\setboxz@h{#1\relbar$}\ht\z@\z@
168     $#1\OrdSymbol{\leftarrow}\mkern-6mu\cleaders
169     \hbox{#1\mkern-2mu\box\z@\mkern-2mu$}\hfill
170     \mkern-6mu\OrdSymbol{\rightarrow}$}
171 }
172 \def\binrel@sym#1#2#3#4#5{%
173   \xdef\binrel@##1{%
174     \ifx\m@Ord#2\@nx\@symOrd

```

```

175 \else\ifx\m@Var#2\@nx\@symVar
176 \else\ifx\m@C0s#2\@nx\@symC0s
177 \else\ifx\m@C0i#2\@nx\@symC0i
178 \else\ifx\m@Bin#2\@nx\@symBin
179 \else\ifx\m@Rel#2\@nx\@symRel
180 \else\ifx\m@Pun#2\@nx\@symPun
181 \else\@nx\@symErr \fi\fi\fi\fi\fi\fi\fi
182 ?{\@nx\OrdSymbol{##1}}}%
183 }
184 \def\binrel@a{%
185 \def\@symOrd##1##2{\gdef\binrel@#####1{\@symOrd##1{\OrdSymbol{#####1}}}}%
186 \def\@symVar##1##2{\gdef\binrel@#####1{\@symVar##1{\OrdSymbol{#####1}}}}%
187 \def\@symC0s##1##2{\gdef\binrel@#####1{\@symC0s##1{\OrdSymbol{#####1}}}}%
188 \def\@symC0i##1##2{\gdef\binrel@#####1{\@symC0i##1{\OrdSymbol{#####1}}}}%
189 \def\@symBin##1##2{\gdef\binrel@#####1{\@symBin##1{\OrdSymbol{#####1}}}}%
190 \def\@symRel##1##2{\gdef\binrel@#####1{\@symRel##1{\OrdSymbol{#####1}}}}%
191 \def\@symPun##1##2{\gdef\binrel@#####1{\@symPun##1{\OrdSymbol{#####1}}}}%
192 }
193 \def\binrel@#1{%
194 \setbox\z@\hbox{${}%
195 \let\mathchoice\@gobblethree
196 \let\@sym\binrel@sym \binrel@a
197 #1$}%
198 }
199 \def\@symextension{sym}
200 \newcommand\usesymbols[1]{%
201 \@for\@tempb:=#1\do{%
202 \exp\@onefilewithoptions\exp{\@tempb}[] []\@symextension
203 }%
204 }
205 \newcommand\ProvidesSymbols[1]{\ProvidesFile{#1.sym}}
206 \DeclareRobustCommand{\not}[1]{\@symRel\not{\OrdSymbol{\notRel#1}}}
207 \DeclareRobustCommand{\OrdSymbol}[1]{%
208 \begingroup\mathchars@reset#1\endgroup
209 }
210 \def\mathchars@reset{\let\@sym\@sym@ord \let\@symtype\@symtype@ord
211 \let\OrdSymbol\relax}
212 \def\@symtype@ord#1#2{\@sym@ord#1#2\@nil} a strange sort of \@gobble
213 \def\@sym@ord#1#2{\@exp\@sym@ord@a\string#2\@nil}%
214 \begingroup
215 \lccode'\.='\@ \lowercase{\endgroup
216 \def\@sym@ord@a#1.#2#3\@nil#4#5#6{%
217 \csname MathChar \endcsname"0%
218 \if D#2\@exp\delim@b\csname sd@#4#5#6\endcsname#4#5#6
219 \else #4#5#6
220 \fi
221 }

```

Before declaring any math characters active, we have to take care of a small problem with amsmath v2.x, if it is loaded before flexisym. `\std@minus` and

```

\std@equal are defined as
\mathchardef\std@minus\mathcode'\-\relax
\mathchardef\std@equal\mathcode'\=\relax

```

in `amsmath.sty` and again `\AtBeginDocument`. The latter is because

In case some alternative math fonts are loaded later. [`amsmath.dtx`]

The problem arises because `flexisym` sets the mathcode of all symbols to 32768 which is illegal for a `\mathchardef`.

We have to remove the assignments from the `\AtBeginDocument` hook as they will cause an error there.

```

222 \@ifpackageloaded{amsmath}{%
223   \begingroup

```

Split the contents of `\@begindocumenthook` by reading what we search for as a delimited argument and ensure these two assignments do not take place. It is questionable if anything reasonable can be done to them. In the case of a package such as `mathpazo` which defines

```

\DeclareMathSymbol{=}{\mathrel}{upright}{"3D}

```

the `\Relbar` will look wrong if we don't use the correct symbol. The way to solve this is define additional `.sym` files which contain the definition of `\relbar` and `\Relbar` needed. We need those additional files anyway for things like `\joinord`.

```

224   \long\def\next#1\mathchardef\std@minus\mathcode'\-\relax
225           \mathchardef\std@equal\mathcode'\=\relax#2\flexi@stop{%
226     \toks@{#1#2}%
227     \xdef\@begindocumenthook{\the\toks@}%
228   }%
229   \expandafter\next\@begindocumenthook\flexi@stop
230   \endgroup
231 }{}

```

There is problem when using `\DeclareMathOperator` as the operators defined call a command `\newmcodes@` which relies on the mathcode of `-` being less than 32768. We delay the definition `\AtBeginDocument` in case `amssymb` hasn't been loaded yet.

```

232 \AtBeginDocument{%
233   \def\newmcodes@{%
234     \mathcode '\ '39\mathcode '\ *42\mathcode '\ ."613A
235     \ifnum\mathcode'\-=45
236     \else

```

The extra check. Don't do anything if `-` is math active.

```

237     \ifnum\mathcode'\-=32768
238     \else
239       \mathchardef \std@minus \mathcode '\-\relax
240     \fi

```

```

241 \fi
242 \mathcode '\-45 \mathcode '\-/47\mathcode '\:"603A\relax
243 }%
244 }

```

And we then continue with the options.

```

245 \DeclareOption{mathstyleoff}{%
246   \PassOptionsToPackage{noactivechars}{mathstyle}}
247 \DeclareOption{cmbase}{\usesymbols{cmbase}}
248 \DeclareOption{mathpazo}{\usesymbols{mathpazo}}
249 \DeclareOption{mathptmx}{\usesymbols{mathptmx}}
250 \ExecuteOptions{cmbase}
251 \ProcessOptions\relax
252 \renewcommand{\lnot}{\neg}
253 \renewcommand{\land}{\wedge}
254 \renewcommand{\lor}{\vee}
255 \renewcommand{\le}{\leq}
256 \renewcommand{\ge}{\geq}
257 \renewcommand{\ne}{\neq}
258 \renewcommand{\owns}{\ni}
259 \renewcommand{\gets}{\leftarrow}
260 \renewcommand{\to}{\rightarrow}
261 \renewcommand{\|}{\Vert}
262 \RequirePackage{mathstyle}
263 \</package>\endinput

```

2 cmbase, mathpazo, mathptmx

For each math font package we define a corresponding symbol file with extension `sym`. The Computer Modern base is called `cmbase` and `mathpazo` and `mathptmx` corresponds to the packages. The definitions are almost identical as they mostly concern the positions in the math font encodings. Look for differences in `\joinord`, `\relbar` and `\Relbar`. If you inspect the source code, you'll see that the support for `mathptmx` didn't require any work but I thought it better to create a `sym` file to maintain a uniform interface.

Open question on ! and ?: maybe they should have type 'Pun' instead of 'DeR'. Need to search for uses in math in AMS archives. Or, maybe add a special 'Clo' type for them: non-extensible closing delimiter.

Default mathgroup setup.

```

264 <{*cmbase | mathpazo | mathptmx>
265 <{cmbase}\ProvidesSymbols{cmbase}[2007/12/19 v0.92]
266 <{mathpazo}\ProvidesSymbols{mathpazo}[2007/12/19 v0.2]
267 <{mathptmx}\ProvidesSymbols{mathptmx}[2007/12/19 v0.2]
268 \@xp\xdef\csname mg@0T1\endcsname{\hexnumber@\symoperators}
269 \@xp\xdef\csname mg@0ML\endcsname{\hexnumber@\symletters}

```

```

270 \@xp\xdef\csname mg@OMS\endcsname{\hexnumber@\symsymbols}
271 \@xp\xdef\csname mg@OMX\endcsname{\hexnumber@\symlargesymbols}
272 \gdef\mg@bin{\mg@OMS}
273 \gdef\mg@del{\mg@OMX}
274 \xdef\mg@digit{\@xp\@nx\csname mg@OT1\endcsname}
275 \gdef\mg@latin{\mg@OML}
276 \global\let\mg@Latin\mg@latin
277 \global\let\mg@greek\mg@latin
278 \global\let\mg@Greek\mg@digit
279 \global\let\mg@rel\mg@bin
280 \global\let\mg@ord\mg@bin
281 \global\let\mg@cop\mg@del

```

Symbols from the 128-character `cmr` encoding. Paren and square bracket delimiters from this encoding are covered by the definitions in the `cmex` section, however.

```

282 \DeclareFlexSymbol{!}      {Pun}{OT1}{21}
283 \DeclareFlexSymbol{+}      {Bin}{OT1}{2B}
284 \DeclareFlexSymbol{:}      {Rel}{OT1}{3A}
285 \DeclareFlexSymbol{\colon} {Pun}{OT1}{3A}
286 \DeclareFlexSymbol{;}      {Pun}{OT1}{3B}
287 \DeclareFlexSymbol{=}      {Rel}{OT1}{3D}
288 \DeclareFlexSymbol{?}      {Pun}{OT1}{3F}

```

$\mathcal{M}\mathrm{T}\mathrm{E}\mathrm{X}$, and therefore the `amsmath` package, make the uppercase Greek letters class 0 (nonvariable) instead of 7 (variable), to eliminate the glaring inconsistency with lowercase Greek. (In plain `TEX`, `\bf\Delta` works, while `\bf\delta` doesn't.) Let us try to make them both variable (fonts permitting) instead of nonvariable.

```

289 \DeclareFlexSymbol{\Gamma} {Var}{Greek}{00}
290 \DeclareFlexSymbol{\Delta}  {Var}{Greek}{01}
291 \DeclareFlexSymbol{\Theta}  {Var}{Greek}{02}
292 \DeclareFlexSymbol{\Lambda} {Var}{Greek}{03}
293 \DeclareFlexSymbol{\Xi}     {Var}{Greek}{04}
294 \DeclareFlexSymbol{\Pi}     {Var}{Greek}{05}
295 \DeclareFlexSymbol{\Sigma}  {Var}{Greek}{06}
296 \DeclareFlexSymbol{\Upsilon}{Var}{Greek}{07}
297 \DeclareFlexSymbol{\Phi}    {Var}{Greek}{08}
298 \DeclareFlexSymbol{\Psi}    {Var}{Greek}{09}
299 \DeclareFlexSymbol{\Omega}  {Var}{Greek}{0A}

```

Decimal digits.

```

300 \DeclareFlexSymbol{0}{Var}{digit}{30}
301 \DeclareFlexSymbol{1}{Var}{digit}{31}
302 \DeclareFlexSymbol{2}{Var}{digit}{32}
303 \DeclareFlexSymbol{3}{Var}{digit}{33}
304 \DeclareFlexSymbol{4}{Var}{digit}{34}
305 \DeclareFlexSymbol{5}{Var}{digit}{35}
306 \DeclareFlexSymbol{6}{Var}{digit}{36}
307 \DeclareFlexSymbol{7}{Var}{digit}{37}

```



```

308 \DeclareFlexSymbol{8}{Var}{digit}{38}
309 \DeclareFlexSymbol{9}{Var}{digit}{39}

```

Symbols from the 128-character cmmt encoding.

```

310 \DeclareFlexSymbol{,}{Pun}{OML}{3B}
311 \DeclareFlexSymbol{.}{Ord}{OML}{3A}
312 \DeclareFlexSymbol{/}{Ord}{OML}{3D}
313 \DeclareFlexSymbol{<}{Rel}{OML}{3C}
314 \DeclareFlexSymbol{>}{Rel}{OML}{3E}

```

To do: make the Var property of lc Greek work properly.

```

315 \DeclareFlexSymbol{\alpha}{Var}{greek}{0B}
316 \DeclareFlexSymbol{\beta}{Var}{greek}{0C}
317 \DeclareFlexSymbol{\gamma}{Var}{greek}{0D}
318 \DeclareFlexSymbol{\delta}{Var}{greek}{0E}
319 \DeclareFlexSymbol{\epsilon}{Var}{greek}{0F}
320 \DeclareFlexSymbol{\zeta}{Var}{greek}{10}
321 \DeclareFlexSymbol{\eta}{Var}{greek}{11}
322 \DeclareFlexSymbol{\theta}{Var}{greek}{12}
323 \DeclareFlexSymbol{\iota}{Var}{greek}{13}
324 \DeclareFlexSymbol{\kappa}{Var}{greek}{14}
325 \DeclareFlexSymbol{\lambda}{Var}{greek}{15}
326 \DeclareFlexSymbol{\mu}{Var}{greek}{16}
327 \DeclareFlexSymbol{\nu}{Var}{greek}{17}
328 \DeclareFlexSymbol{\xi}{Var}{greek}{18}
329 \DeclareFlexSymbol{\pi}{Var}{greek}{19}
330 \DeclareFlexSymbol{\rho}{Var}{greek}{1A}
331 \DeclareFlexSymbol{\sigma}{Var}{greek}{1B}
332 \DeclareFlexSymbol{\tau}{Var}{greek}{1C}
333 \DeclareFlexSymbol{\upsilon}{Var}{greek}{1D}
334 \DeclareFlexSymbol{\phi}{Var}{greek}{1E}
335 \DeclareFlexSymbol{\chi}{Var}{greek}{1F}
336 \DeclareFlexSymbol{\psi}{Var}{greek}{20}
337 \DeclareFlexSymbol{\omega}{Var}{greek}{21}
338 \DeclareFlexSymbol{\varepsilon}{Var}{greek}{22}
339 \DeclareFlexSymbol{\vartheta}{Var}{greek}{23}
340 \DeclareFlexSymbol{\varpi}{Var}{greek}{24}
341 \DeclareFlexSymbol{\varrho}{Var}{greek}{25}
342 \DeclareFlexSymbol{\varsigma}{Var}{greek}{26}
343 \DeclareFlexSymbol{\varphi}{Var}{greek}{27}

```

Note that in plain T_EX `\imath` and `\jmath` are not variable-font. But if a j changes font to, let's say, sans serif or calligraphic, a dotless j in the same context should change font in the same way.

```

344 \DeclareFlexSymbol{\imath}{Var}{OML}{7B}
345 \DeclareFlexSymbol{\jmath}{Var}{OML}{7C}
346 \DeclareFlexSymbol{\ell}{Ord}{OML}{60}
347 \DeclareFlexSymbol{\wp}{Ord}{OML}{7D}
348 \DeclareFlexSymbol{\partial}{Ord}{OML}{40}
349 \DeclareFlexSymbol{\flat}{Ord}{OML}{5B}
350 \DeclareFlexSymbol{\natural}{Ord}{OML}{5C}

```

```

351 \DeclareFlexSymbol{\sharp}{Ord}{OML}{5D}
352 \DeclareFlexSymbol{\triangleleft}{Bin}{OML}{2F}
353 \DeclareFlexSymbol{\triangleright}{Bin}{OML}{2E}
354 \DeclareFlexSymbol{\star}{Bin}{OML}{3F}
355 \DeclareFlexSymbol{\smile}{Rel}{OML}{5E}
356 \DeclareFlexSymbol{\frown}{Rel}{OML}{5F}
357 \DeclareFlexSymbol{\leftharpoonup}{Rel}{OML}{28}
358 \DeclareFlexSymbol{\leftharpoondown}{Rel}{OML}{29}
359 \DeclareFlexSymbol{\rightharpoonup}{Rel}{OML}{2A}
360 \DeclareFlexSymbol{\rightharpoondown}{Rel}{OML}{2B}
361 \DeclareFlexSymbol{a}{Var}{latin}{61}
362 \DeclareFlexSymbol{b}{Var}{latin}{62}
363 \DeclareFlexSymbol{c}{Var}{latin}{63}
364 \DeclareFlexSymbol{d}{Var}{latin}{64}
365 \DeclareFlexSymbol{e}{Var}{latin}{65}
366 \DeclareFlexSymbol{f}{Var}{latin}{66}
367 \DeclareFlexSymbol{g}{Var}{latin}{67}
368 \DeclareFlexSymbol{h}{Var}{latin}{68}
369 \DeclareFlexSymbol{i}{Var}{latin}{69}
370 \DeclareFlexSymbol{j}{Var}{latin}{6A}
371 \DeclareFlexSymbol{k}{Var}{latin}{6B}
372 \DeclareFlexSymbol{l}{Var}{latin}{6C}
373 \DeclareFlexSymbol{m}{Var}{latin}{6D}
374 \DeclareFlexSymbol{n}{Var}{latin}{6E}
375 \DeclareFlexSymbol{o}{Var}{latin}{6F}
376 \DeclareFlexSymbol{p}{Var}{latin}{70}
377 \DeclareFlexSymbol{q}{Var}{latin}{71}
378 \DeclareFlexSymbol{r}{Var}{latin}{72}
379 \DeclareFlexSymbol{s}{Var}{latin}{73}
380 \DeclareFlexSymbol{t}{Var}{latin}{74}
381 \DeclareFlexSymbol{u}{Var}{latin}{75}
382 \DeclareFlexSymbol{v}{Var}{latin}{76}
383 \DeclareFlexSymbol{w}{Var}{latin}{77}
384 \DeclareFlexSymbol{x}{Var}{latin}{78}
385 \DeclareFlexSymbol{y}{Var}{latin}{79}
386 \DeclareFlexSymbol{z}{Var}{latin}{7A}
387 \DeclareFlexSymbol{A}{Var}{Latin}{41}
388 \DeclareFlexSymbol{B}{Var}{Latin}{42}
389 \DeclareFlexSymbol{C}{Var}{Latin}{43}
390 \DeclareFlexSymbol{D}{Var}{Latin}{44}
391 \DeclareFlexSymbol{E}{Var}{Latin}{45}
392 \DeclareFlexSymbol{F}{Var}{Latin}{46}
393 \DeclareFlexSymbol{G}{Var}{Latin}{47}
394 \DeclareFlexSymbol{H}{Var}{Latin}{48}
395 \DeclareFlexSymbol{I}{Var}{Latin}{49}
396 \DeclareFlexSymbol{J}{Var}{Latin}{4A}
397 \DeclareFlexSymbol{K}{Var}{Latin}{4B}
398 \DeclareFlexSymbol{L}{Var}{Latin}{4C}
399 \DeclareFlexSymbol{M}{Var}{Latin}{4D}
400 \DeclareFlexSymbol{N}{Var}{Latin}{4E}

```

```

401 \DeclareFlexSymbol{O}{Var}{Latin}{4F}
402 \DeclareFlexSymbol{P}{Var}{Latin}{50}
403 \DeclareFlexSymbol{Q}{Var}{Latin}{51}
404 \DeclareFlexSymbol{R}{Var}{Latin}{52}
405 \DeclareFlexSymbol{S}{Var}{Latin}{53}
406 \DeclareFlexSymbol{T}{Var}{Latin}{54}
407 \DeclareFlexSymbol{U}{Var}{Latin}{55}
408 \DeclareFlexSymbol{V}{Var}{Latin}{56}
409 \DeclareFlexSymbol{W}{Var}{Latin}{57}
410 \DeclareFlexSymbol{X}{Var}{Latin}{58}
411 \DeclareFlexSymbol{Y}{Var}{Latin}{59}
412 \DeclareFlexSymbol{Z}{Var}{Latin}{5A}

```

The `\ldotPun` glyph is used in constructing the `\ldots` symbol. It is just a period with a different math symbol class. `\lhookRel` and `\rhookRel` are used in a similar way for building hooked arrow symbols.

```

413 \DeclareFlexSymbol{\ldotPun}{Pun}{OML}{3A}
414 \def\ldotp{\ldotPun}
415 \DeclareFlexSymbol{\lhookRel}{Rel}{OML}{2C}
416 \DeclareFlexSymbol{\rhookRel}{Rel}{OML}{2D}

```

Symbols from the 128-character `cmsy` encoding.

```

417 \DeclareFlexSymbol{*}{Bin}{bin}{03} % \ast
418 \DeclareFlexSymbol{-}{Bin}{bin}{00}
419 \DeclareFlexSymbol{|}{Ord}{OMS}{6A}
420 \DeclareFlexSymbol{\aleph}{Ord}{ord}{40}
421 \DeclareFlexSymbol{\Re}{Ord}{ord}{3C}
422 \DeclareFlexSymbol{\Im}{Ord}{ord}{3D}
423 \DeclareFlexSymbol{\infty}{Ord}{ord}{31}
424 \DeclareFlexSymbol{\prime}{Ord}{ord}{30}
425 \DeclareFlexSymbol{\emptyset}{Ord}{ord}{3B}
426 \DeclareFlexSymbol{\nabla}{Ord}{ord}{72}
427 \DeclareFlexSymbol{\top}{Ord}{ord}{3E}
428 \DeclareFlexSymbol{\bot}{Ord}{ord}{3F}
429 \DeclareFlexSymbol{\triangle}{Ord}{ord}{34}
430 \DeclareFlexSymbol{\forall}{Ord}{ord}{38}
431 \DeclareFlexSymbol{\exists}{Ord}{ord}{39}
432 \DeclareFlexSymbol{\neg}{Ord}{ord}{3A}
433 \DeclareFlexSymbol{\clubsuit}{Ord}{ord}{7C}
434 \DeclareFlexSymbol{\diamondsuit}{Ord}{ord}{7D}
435 \DeclareFlexSymbol{\heartsuit}{Ord}{ord}{7E}
436 \DeclareFlexSymbol{\spadesuit}{Ord}{ord}{7F}
437 \DeclareFlexSymbol{\smallint}{C0s}{OMS}{73}

```

Binary operators.

```

438 \DeclareFlexSymbol{\bigtriangleup}{Bin}{bin}{34}
439 \DeclareFlexSymbol{\bigtriangledown}{Bin}{bin}{35}
440 \DeclareFlexSymbol{\wedge}{Bin}{bin}{5E}
441 \DeclareFlexSymbol{\vee}{Bin}{bin}{5F}
442 \DeclareFlexSymbol{\cap}{Bin}{bin}{5C}
443 \DeclareFlexSymbol{\cup}{Bin}{bin}{5B}

```

```

444 \DeclareFlexSymbol{\ddagger}{Bin}{bin}{7A}
445 \DeclareFlexSymbol{\dagger}{Bin}{bin}{79}
446 \DeclareFlexSymbol{\sqcap}{Bin}{bin}{75}
447 \DeclareFlexSymbol{\sqcup}{Bin}{bin}{74}
448 \DeclareFlexSymbol{\uplus}{Bin}{bin}{5D}
449 \DeclareFlexSymbol{\amalg}{Bin}{bin}{71}
450 \DeclareFlexSymbol{\diamond}{Bin}{bin}{05}
451 \DeclareFlexSymbol{\bullet}{Bin}{bin}{0F}
452 \DeclareFlexSymbol{\wr}{Bin}{bin}{6F}
453 \DeclareFlexSymbol{\div}{Bin}{bin}{04}
454 \DeclareFlexSymbol{\odot}{Bin}{bin}{0C}
455 \DeclareFlexSymbol{\oslash}{Bin}{bin}{0B}
456 \DeclareFlexSymbol{\otimes}{Bin}{bin}{0A}
457 \DeclareFlexSymbol{\ominus}{Bin}{bin}{09}
458 \DeclareFlexSymbol{\oplus}{Bin}{bin}{08}
459 \DeclareFlexSymbol{\mp}{Bin}{bin}{07}
460 \DeclareFlexSymbol{\pm}{Bin}{bin}{06}
461 \DeclareFlexSymbol{\circ}{Bin}{bin}{0E}
462 \DeclareFlexSymbol{\bigcirc}{Bin}{bin}{0D}
463 \DeclareFlexSymbol{\setminus}{Bin}{bin}{6E}
464 \DeclareFlexSymbol{\cdot}{Bin}{bin}{01}
465 \DeclareFlexSymbol{\ast}{Bin}{bin}{03}
466 \DeclareFlexSymbol{\times}{Bin}{bin}{02}

```

Relation symbols.

```

467 \DeclareFlexSymbol{\propto}{Rel}{rel}{2F}
468 \DeclareFlexSymbol{\sqsubseteq}{Rel}{rel}{76}
469 \DeclareFlexSymbol{\sqsupseteq}{Rel}{rel}{77}
470 \DeclareFlexSymbol{\parallel}{Rel}{rel}{6B}
471 \DeclareFlexSymbol{\mid}{Rel}{rel}{6A}
472 \DeclareFlexSymbol{\dashv}{Rel}{rel}{61}
473 \DeclareFlexSymbol{\vdash}{Rel}{rel}{60}
474 \DeclareFlexSymbol{\nearrow}{Rel}{rel}{25}
475 \DeclareFlexSymbol{\searrow}{Rel}{rel}{26}
476 \DeclareFlexSymbol{\nwarrow}{Rel}{rel}{2D}
477 \DeclareFlexSymbol{\swarrow}{Rel}{rel}{2E}
478 \DeclareFlexSymbol{\Leftrightarrow}{Rel}{rel}{2C}
479 \DeclareFlexSymbol{\Leftarrow}{Rel}{rel}{28}
480 \DeclareFlexSymbol{\Rightarrow}{Rel}{rel}{29}
481 \DeclareFlexSymbol{\leq}{Rel}{rel}{14}
482 \DeclareFlexSymbol{\geq}{Rel}{rel}{15}
483 \DeclareFlexSymbol{\succ}{Rel}{rel}{1F}
484 \DeclareFlexSymbol{\prec}{Rel}{rel}{1E}
485 \DeclareFlexSymbol{\approx}{Rel}{rel}{19}
486 \DeclareFlexSymbol{\succeq}{Rel}{rel}{17}
487 \DeclareFlexSymbol{\preceq}{Rel}{rel}{16}
488 \DeclareFlexSymbol{\supseteq}{Rel}{rel}{1B}
489 \DeclareFlexSymbol{\subset}{Rel}{rel}{1A}
490 \DeclareFlexSymbol{\supseteq}{Rel}{rel}{13}
491 \DeclareFlexSymbol{\subseteq}{Rel}{rel}{12}

```

```

492 \DeclareFlexSymbol{\in}{Rel}{rel}{32}
493 \DeclareFlexSymbol{\ni}{Rel}{rel}{33}
494 \DeclareFlexSymbol{\gg}{Rel}{rel}{1D}
495 \DeclareFlexSymbol{\ll}{Rel}{rel}{1C}
496 \DeclareFlexSymbol{\leftrightharpoonup}{Rel}{rel}{24}
497 \DeclareFlexSymbol{\leftarrow}{Rel}{rel}{20}
498 \DeclareFlexSymbol{\rightarrow}{Rel}{rel}{21}
499 \DeclareFlexSymbol{\sim}{Rel}{rel}{18}
500 \DeclareFlexSymbol{\simeq}{Rel}{rel}{27}
501 \DeclareFlexSymbol{\perp}{Rel}{rel}{3F}
502 \DeclareFlexSymbol{\equiv}{Rel}{rel}{11}
503 \DeclareFlexSymbol{\asymp}{Rel}{rel}{10}

```

The `\notRel` glyph is a special zero-width glyph intended only for use in constructing negated symbols. `\mapstoRel` and `\cdotPun` have similar but more restricted applications.

```

504 \DeclareFlexSymbol{\notRel}{Rel}{rel}{36}
505 \DeclareFlexSymbol{\mapstoOrd}{Ord}{OMS}{37}
506 \DeclareFlexSymbol{\cdotOrd}{Ord}{OMS}{01}
507 \def\cdotp{\mathpunct{\cdotOrd}}

```

Symbols from the 128-character `cmex` encoding. `COs` stands for ‘cumulative operator (sum-like)’. `COi` stands for ‘cumulative operator (integral-like)’. These typically differ only in the default placement of limits. `cop` stands for ‘cumulative operator math group’.

```

508 \DeclareFlexSymbol{\coprod}{COs}{cop}{60}
509 \DeclareFlexSymbol{\bigvee}{COs}{cop}{57}
510 \DeclareFlexSymbol{\bigwedge}{COs}{cop}{56}
511 \DeclareFlexSymbol{\biguplus}{COs}{cop}{55}
512 \DeclareFlexSymbol{\bigcap}{COs}{cop}{54}
513 \DeclareFlexSymbol{\bigcup}{COs}{cop}{53}
514 \DeclareFlexSymbol{\int}{COi}{cop}{52}
515 \DeclareFlexSymbol{\prod}{COs}{cop}{51}
516 \DeclareFlexSymbol{\sum}{COs}{cop}{50}
517 \DeclareFlexSymbol{\bigotimes}{COs}{cop}{4E}
518 \DeclareFlexSymbol{\bigoplus}{COs}{cop}{4C}
519 \DeclareFlexSymbol{\bigodot}{COs}{cop}{4A}
520 \DeclareFlexSymbol{\oint}{COi}{cop}{48}
521 \DeclareFlexSymbol{\bigsqcup}{COs}{cop}{46}

```

Delimiter symbols. `DeL` stands for ‘delimiter (left)’. `DeR` stands for ‘delimiter (right)’. `DeB` stands for ‘delimiter (bidirectional)’. The principal encoding point for an extensible delimiter is the first link in the list of linked sizes as specified in the font metric information. For a math encoding such as OT1/OML/OMS/OMX where not all sizes of a given delimiter reside in a given font, the extra encoding point for the smallest delimiter must be supplied by defining

```
\sd@GXX
```

where `G` is the mathgroup and `XX` is the hexadecimal glyph position.

```

522 \DeclareFlexSymbol{\rangle}{DeR}{del}{0B}
523 \DeclareFlexSymbol{\langle}{DeL}{del}{0A}
524 \DeclareFlexSymbol{\rbrace}{DeR}{del}{09}
525 \DeclareFlexSymbol{\lbrace}{DeL}{del}{08}
526 \DeclareFlexSymbol{\rceil}{DeR}{del}{07}
527 \DeclareFlexSymbol{\lceil}{DeL}{del}{06}
528 \DeclareFlexSymbol{\rfloor}{DeR}{del}{05}
529 \DeclareFlexSymbol{\lfloor}{DeL}{del}{04}
530 \DeclareFlexSymbol{\}{DeL}{del}{00}
531 \DeclareFlexSymbol{\}{DeR}{del}{01}
532 \DeclareFlexSymbol{\[}{DeL}{del}{02}
533 \DeclareFlexSymbol{\]}{DeR}{del}{03}
534 \DeclareFlexSymbol{\lVert}{DeL}{del}{0D}
535 \DeclareFlexSymbol{\rVert}{DeR}{del}{0D}
536 \DeclareFlexSymbol{\lvert}{DeL}{del}{0C}
537 \DeclareFlexSymbol{\rvert}{DeR}{del}{0C}
538 \DeclareFlexSymbol{\Vert}{DeB}{del}{0D}
539 \DeclareFlexSymbol{\vert}{DeB}{del}{0C}

```

Maybe make the vert bars mathord instead of delimiter, to discourage poor usage.

```

540 \DeclareFlexSymbol{\}{DeB}{del}{0C}
541 \DeclareFlexSymbol{/}{DeB}{del}{0E}

```

These wacky delimiters need to be supported I guess for compabitility reasons.

The DeA delimiter type is a special case used only for these arrows.

```

542 \DeclareFlexSymbol{\lmoustache}{DeL}{del}{40}
543 \DeclareFlexSymbol{\rmoustache}{DeR}{del}{41}
544 \DeclareFlexSymbol{\lgroup}{DeL}{del}{3A}
545 \DeclareFlexSymbol{\rgroup}{DeR}{del}{3B}
546 \DeclareFlexSymbol{\bracevert}{DeB}{del}{3E}
547 \DeclareFlexSymbol{\arrowvert}{DeB}{del}{3C}
548 \DeclareFlexSymbol{\Arrowvert}{DeB}{del}{3D}
549 \DeclareFlexSymbol{\uparrow}{DeA}{del}{78}
550 \DeclareFlexSymbol{\downarrow}{DeA}{del}{79}
551 \DeclareFlexSymbol{\updownarrow}{DeA}{del}{3F}
552 \DeclareFlexSymbol{\Uparrow}{DeA}{del}{7E}
553 \DeclareFlexSymbol{\Downarrow}{DeA}{del}{7F}
554 \DeclareFlexSymbol{\Updownarrow}{DeA}{del}{77}
555 \DeclareFlexSymbol{\backslash}{DeB}{del}{0F}

```

3 Some compound symbols

The following symbols are not robust in standard L^AT_EX because they use # or `\mathpalette` (which is not robust and contains a # in its expansion): `\angle`, `\cong`, `\notin`, `\rightleftharpoons`.

In this definition of `\hbar`, the symbol is cobbled together from a math italic h and the cmr overbar accent glyph.

```

556 \DeclareFlexSymbol{\hbarOrd}{Ord}{0T1}{16}
557 \DeclareFlexCompoundSymbol{\hbar}{Ord}{\hbarOrd\mkern-9mu h}

```

For `\surd`, the interior symbol gets math class 1 (cumulative operator) to make the glyph vertically centered on the math axis, but the desired horizontal spacing is the spacing for a `mathord`. (Couldn't it just be class `mathopen`, though?)

```
558 \DeclareFlexSymbol{\surdOrd}{Ord}{OMS}{70}
559 \DeclareFlexCompoundSymbol{\surd}{Ord}{\mathop{\surdOrd}}
```

As shown in this definition of `\angle`, rule `dimens` are not allowed to use `math-` units, unfortunately.

```
560 \DeclareFlexCompoundSymbol{\angle}{Ord}{%
561   \vbox{\ialign{%
562     $\m@th\scriptstyle##$\crcr
563     \notRel\mathrel{\mkern14mu}\crcr
564     \noalign{\nointerlineskip}%
565     \mkern2.5mu\leaders\hrule \@height.34pt\hfill\mkern2.5mu}\crcr
566   }}%
567 }
```

The `\not` function, which is defined in the `flexisym` package, requires a suitably defined `\notRel` symbol.

```
568 \DeclareFlexCompoundSymbol{\neq}{Rel}{\not{=}}
```

.

```
569 \DeclareFlexCompoundSymbol{\mapsto}{Rel}{\mapstoOrd\rightarrow}
```

The `\@vereq` function ends by centering the whole construction on the math axis, unlike `\buildrel` where the base symbol remains at its normal altitude. Furthermore, `\@vereq` leaves the math style of the top symbol as given instead of downsizing to `scriptstyle`.

```
570 \DeclareFlexCompoundSymbol{\cong}{Rel}{\mathpalette\@vereq\sim}
```

The `\m@th` in the `fontmath.ltx` definition of `\notin` is superfluous unless `\c@ncel` doesn't include it (which was perhaps true in an older version of `plain.tex`).

```
571 \providecommand*\joinord{}
572 \cmbase | mathptmx \renewcommand*\joinord{\mkern-3mu }
573 \mathpazo \renewcommand*\joinord{\mkern-3.45mu }
574 \DeclareFlexCompoundSymbol{\notin}{Rel}{\mathpalette\c@ncel\in}
575 \DeclareFlexCompoundSymbol{\rightleftharpoons}{Rel}{\mathpalette\rlh@{}}
576 \DeclareFlexCompoundSymbol{\doteq}{Rel}{\buildrel\textstyle.\over=}
577 \DeclareFlexCompoundSymbol{\hookrightarrow}{Rel}{\lhookRel\joinord\rightarrow}
578 \DeclareFlexCompoundSymbol{\hookleftarrow}{Rel}{\leftarrow\joinord\rhookRel}
579 \DeclareFlexCompoundSymbol{\bowtie}{Rel}{\triangleright\joinord\triangleleft}
580 \DeclareFlexCompoundSymbol{\models}{Rel}{\vert\joinord=}
581 \DeclareFlexCompoundSymbol{\Longrightarrow}{Rel}{\Relbar\joinord\Rightarrow}
582 \DeclareFlexCompoundSymbol{\longrightarrow}{Rel}{\relbar\joinord\rightarrow}
583 \DeclareFlexCompoundSymbol{\Longleftarrow}{Rel}{\Leftarrow\joinord\Relbar}
584 \DeclareFlexCompoundSymbol{\longleftarrow}{Rel}{\leftarrow\joinord\relbar}
585 \DeclareFlexCompoundSymbol{\longmapsto}{Rel}{\mapstochar\longrightarrow}
586 \DeclareFlexCompoundSymbol{\longleftarrowrightarrow}{Rel}{\leftarrow\joinord\rightarrow}
587 \DeclareFlexCompoundSymbol{\Longleftarrowrightarrow}{Rel}{\Leftarrow\joinord\Rightarrow}
```

Here is what you get from the old definition of `\iff`.

```

\glue 2.77771 plus 2.77771
\glue(\thickmuskip) 2.77771 plus 2.77771
\OMS/cmsy/m/n/10 (
\hbox(0.0+0.0)x-1.66663
.\kern -1.66663
\OMS/cmsy/m/n/10 )
\penalty 500
\glue 2.77771 plus 2.77771
\glue(\thickmuskip) 2.77771 plus 2.77771

```

Looks like it could be simplified slightly. But it's not so easy as it looks to do it without screwing up the line breaking possibilities.

```

588 \renewcommand*\iff{%
589   \mskip\thickmuskip\Longlefttrightarrow\mskip\thickmuskip
590 }

```

Some dotly symbols.

```

591 \DeclareFlexCompoundSymbol{\cdots}{Inn}{\cdotp\cdotp\cdotp}%
592 \DeclareFlexCompoundSymbol{\vdots}{Ord}{%
593   \vbox{\baselineskip4p@ \lineskiplimit\z@
594     \kern6p@\hbox{.}\hbox{.}\hbox{.}}}
595 \DeclareFlexCompoundSymbol{\ddots}{Inn}{%
596   \mkern1mu\raise7p@
597   \vbox{\kern7p@\hbox{.}}\mkern2mu%
598   \raise4p@\hbox{.}\mkern2mu\raise\p@\hbox{.}\mkern1mu%
599 }

```

```

600 \def\relbar{\begingroup \def\smash@{tb}% in case amsmath is loaded
601   \mathpalette\mathsm@sh{\mathchar"200 }\endgroup}

```

For `\Relbar` we take an equal sign of class 0 (Ord) from the operator family. For `cmr` and `mathptmx` we know this is family 0.

```

602 <cmr | mathptmx> \def\Relbar{\mathchar"3D }

```

For the `mathpazo` setup we need to use the equal sign from `cmr` and so must insert class 0 and use the symbol from the upright symbols.

```

603 <mathpazo> \edef\Relbar{\mathchar\string"hexnumber@\symupright3D }

```

Done.

```

604 </cmr | mathpazo | mathptmx>

```

Various synonyms such as `\le` for `\leq` and `\to` for `\rightarrow` are defined in `flexisym` with `\def` instead of `\let`, for slower execution speed but smaller chance of synchronization problems.

```

605 <msabm>
606 \ProvidesSymbols{msabm}[2001/09/08 v0.91]
607 \RequirePackage{amsfonts}\relax
608 \exp\edef\csname mg@MSA\endcsname{\hexnumber@\symAMSa}%
609 \exp\edef\csname mg@MSB\endcsname{\hexnumber@\symAMSb}%

```



```

610 \DeclareFlexSymbol{\boxdot}      {Bin}{MSA}{00}
611 \DeclareFlexSymbol{\boxplus}     {Bin}{MSA}{01}
612 \DeclareFlexSymbol{\boxtimes}    {Bin}{MSA}{02}
613 \DeclareFlexSymbol{\square}      {Ord}{MSA}{03}
614 \DeclareFlexSymbol{\blacksquare} {Ord}{MSA}{04}
615 \DeclareFlexSymbol{\centerdot}   {Bin}{MSA}{05}
616 \DeclareFlexSymbol{\lozenge}     {Ord}{MSA}{06}
617 \DeclareFlexSymbol{\blacklozenge}{Ord}{MSA}{07}
618 \DeclareFlexSymbol{\circlearrowright}{Rel}{MSA}{08}
619 \DeclareFlexSymbol{\circlearrowleft}{Rel}{MSA}{09}

```

In amsfonts.sty:

```

620 %\DeclareFlexSymbol{\rightleftharpoons}{Rel}{MSA}{0A}
621 \DeclareFlexSymbol{\leftrightharpoons}{Rel}{MSA}{0B}
622 \DeclareFlexSymbol{\boxminus}      {Bin}{MSA}{0C}
623 \DeclareFlexSymbol{\Vdash}         {Rel}{MSA}{0D}
624 \DeclareFlexSymbol{\Vvdash}        {Rel}{MSA}{0E}
625 \DeclareFlexSymbol{\vDash}         {Rel}{MSA}{0F}
626 \DeclareFlexSymbol{\twoheadrightarrow}{Rel}{MSA}{10}
627 \DeclareFlexSymbol{\twoheadleftarrow}{Rel}{MSA}{11}
628 \DeclareFlexSymbol{\leftleftarrows}{Rel}{MSA}{12}
629 \DeclareFlexSymbol{\rightrightarrows}{Rel}{MSA}{13}
630 \DeclareFlexSymbol{\upuparrows}    {Rel}{MSA}{14}
631 \DeclareFlexSymbol{\downdownarrows}{Rel}{MSA}{15}
632 \DeclareFlexSymbol{\upharpoonright}{Rel}{MSA}{16}
633 \let\restriction\upharpoonright
634 \DeclareFlexSymbol{\downharpoonright}{Rel}{MSA}{17}
635 \DeclareFlexSymbol{\upharpoonleft}{Rel}{MSA}{18}
636 \DeclareFlexSymbol{\downharpoonleft}{Rel}{MSA}{19}
637 \DeclareFlexSymbol{\rightarrowtail}{Rel}{MSA}{1A}
638 \DeclareFlexSymbol{\leftarrowtail}{Rel}{MSA}{1B}
639 \DeclareFlexSymbol{\leftrightharpoons}{Rel}{MSA}{1C}
640 \DeclareFlexSymbol{\rightleftarrows}{Rel}{MSA}{1D}
641 \DeclareFlexSymbol{\Lsh}           {Rel}{MSA}{1E}
642 \DeclareFlexSymbol{\Rsh}           {Rel}{MSA}{1F}
643 \DeclareFlexSymbol{\rightsquigarrow}{Rel}{MSA}{20}
644 \DeclareFlexSymbol{\leftrightsquigarrow}{Rel}{MSA}{21}
645 \DeclareFlexSymbol{\looparrowleft}{Rel}{MSA}{22}
646 \DeclareFlexSymbol{\looparrowright}{Rel}{MSA}{23}
647 \DeclareFlexSymbol{\circeq}       {Rel}{MSA}{24}
648 \DeclareFlexSymbol{\succsim}      {Rel}{MSA}{25}
649 \DeclareFlexSymbol{\gtrsim}       {Rel}{MSA}{26}
650 \DeclareFlexSymbol{\gtrapprox}    {Rel}{MSA}{27}
651 \DeclareFlexSymbol{\multimap}     {Rel}{MSA}{28}
652 \DeclareFlexSymbol{\therefore}    {Rel}{MSA}{29}
653 \DeclareFlexSymbol{\because}      {Rel}{MSA}{2A}
654 \DeclareFlexSymbol{\doteqdot}     {Rel}{MSA}{2B}
655 \let\Doteq\doteqdot
656 \DeclareFlexSymbol{\triangleq}    {Rel}{MSA}{2C}
657 \DeclareFlexSymbol{\precsim}      {Rel}{MSA}{2D}

```

```

658 \DeclareFlexSymbol{\lessssim}      {Rel}{MSA}{2E}
659 \DeclareFlexSymbol{\lessapprox}     {Rel}{MSA}{2F}
660 \DeclareFlexSymbol{\eqslantless}    {Rel}{MSA}{30}
661 \DeclareFlexSymbol{\eqslantgtr}     {Rel}{MSA}{31}
662 \DeclareFlexSymbol{\curlyeqprec}    {Rel}{MSA}{32}
663 \DeclareFlexSymbol{\curlyeqsucc}    {Rel}{MSA}{33}
664 \DeclareFlexSymbol{\preccurlyeq}    {Rel}{MSA}{34}
665 \DeclareFlexSymbol{\leqq}           {Rel}{MSA}{35}
666 \DeclareFlexSymbol{\leqslant}       {Rel}{MSA}{36}
667 \DeclareFlexSymbol{\lessgtr}        {Rel}{MSA}{37}
668 \DeclareFlexSymbol{\backprime}      {Ord}{MSA}{38}
669 \DeclareFlexSymbol{\risingdotseq}   {Rel}{MSA}{3A}
670 \DeclareFlexSymbol{\fallingdotseq}  {Rel}{MSA}{3B}
671 \DeclareFlexSymbol{\succcurlyeq}    {Rel}{MSA}{3C}
672 \DeclareFlexSymbol{\geqq}           {Rel}{MSA}{3D}
673 \DeclareFlexSymbol{\geqslant}       {Rel}{MSA}{3E}
674 \DeclareFlexSymbol{\gtrless}        {Rel}{MSA}{3F}

in amsfonts.sty

675 % \DeclareFlexSymbol{\sqsubset}      {Rel}{MSA}{40}
676 % \DeclareFlexSymbol{\sqsupset}      {Rel}{MSA}{41}
677 \DeclareFlexSymbol{\vartriangleright}{Rel}{MSA}{42}
678 \DeclareFlexSymbol{\vartriangleleft}{Rel}{MSA}{43}
679 \DeclareFlexSymbol{\trianglerighteq}{Rel}{MSA}{44}
680 \DeclareFlexSymbol{\trianglelefteq}{Rel}{MSA}{45}
681 \DeclareFlexSymbol{\bigstar}        {Ord}{MSA}{46}
682 \DeclareFlexSymbol{\between}        {Rel}{MSA}{47}
683 \DeclareFlexSymbol{\blacktriangledown}{Ord}{MSA}{48}
684 \DeclareFlexSymbol{\blacktriangleright}{Rel}{MSA}{49}
685 \DeclareFlexSymbol{\blacktriangleleft}{Rel}{MSA}{4A}
686 \DeclareFlexSymbol{\vartriangle}     {Rel}{MSA}{4D}
687 \DeclareFlexSymbol{\blacktriangle}   {Ord}{MSA}{4E}
688 \DeclareFlexSymbol{\triangledown}    {Ord}{MSA}{4F}
689 \DeclareFlexSymbol{\eqcirc}          {Rel}{MSA}{50}
690 \DeclareFlexSymbol{\lesseqgtr}       {Rel}{MSA}{51}
691 \DeclareFlexSymbol{\gtreqless}        {Rel}{MSA}{52}
692 \DeclareFlexSymbol{\lesseqqgtr}      {Rel}{MSA}{53}
693 \DeclareFlexSymbol{\gtreqqless}      {Rel}{MSA}{54}
694 \DeclareFlexSymbol{\Rrightarrow}     {Rel}{MSA}{56}
695 \DeclareFlexSymbol{\Lleftarrow}      {Rel}{MSA}{57}
696 \DeclareFlexSymbol{\veebar}          {Bin}{MSA}{59}
697 \DeclareFlexSymbol{\barwedge}        {Bin}{MSA}{5A}
698 \DeclareFlexSymbol{\doublebarwedge}{Bin}{MSA}{5B}

In amsfonts.sty

699 %\DeclareFlexSymbol{\angle}          {Ord}{MSA}{5C}
700 \DeclareFlexSymbol{\measuredangle}   {Ord}{MSA}{5D}
701 \DeclareFlexSymbol{\sphericalangle}  {Ord}{MSA}{5E}
702 \DeclareFlexSymbol{\varpropto}       {Rel}{MSA}{5F}
703 \DeclareFlexSymbol{\smallsmile}      {Rel}{MSA}{60}
704 \DeclareFlexSymbol{\smallfrown}      {Rel}{MSA}{61}

```

705	<code>\DeclareFlexSymbol{\Subset}</code>	<code>{Rel}{MSA}{62}</code>
706	<code>\DeclareFlexSymbol{\Supset}</code>	<code>{Rel}{MSA}{63}</code>
707	<code>\DeclareFlexSymbol{\Cup}</code>	<code>{Bin}{MSA}{64}</code>
708	<code>\let\doublecup\Cup</code>	
709	<code>\DeclareFlexSymbol{\Cap}</code>	<code>{Bin}{MSA}{65}</code>
710	<code>\let\doublecap\Cap</code>	
711	<code>\DeclareFlexSymbol{\curlywedge}</code>	<code>{Bin}{MSA}{66}</code>
712	<code>\DeclareFlexSymbol{\curlyvee}</code>	<code>{Bin}{MSA}{67}</code>
713	<code>\DeclareFlexSymbol{\leftthreetimes}</code>	<code>{Bin}{MSA}{68}</code>
714	<code>\DeclareFlexSymbol{\rightthreetimes}</code>	<code>{Bin}{MSA}{69}</code>
715	<code>\DeclareFlexSymbol{\subseteq}</code>	<code>{Rel}{MSA}{6A}</code>
716	<code>\DeclareFlexSymbol{\supseteq}</code>	<code>{Rel}{MSA}{6B}</code>
717	<code>\DeclareFlexSymbol{\bumpeq}</code>	<code>{Rel}{MSA}{6C}</code>
718	<code>\DeclareFlexSymbol{\Bumpeq}</code>	<code>{Rel}{MSA}{6D}</code>
719	<code>\DeclareFlexSymbol{\lll}</code>	<code>{Rel}{MSA}{6E}</code>
720	<code>\let\llless\lll</code>	
721	<code>\DeclareFlexSymbol{\ggg}</code>	<code>{Rel}{MSA}{6F}</code>
722	<code>\let\gggtr\ggg</code>	
723	<code>\DeclareFlexSymbol{\circledS}</code>	<code>{Ord}{MSA}{73}</code>
724	<code>\DeclareFlexSymbol{\pitchfork}</code>	<code>{Rel}{MSA}{74}</code>
725	<code>\DeclareFlexSymbol{\dotplus}</code>	<code>{Bin}{MSA}{75}</code>
726	<code>\DeclareFlexSymbol{\backsim}</code>	<code>{Rel}{MSA}{76}</code>
727	<code>\DeclareFlexSymbol{\backsimeq}</code>	<code>{Rel}{MSA}{77}</code>
728	<code>\DeclareFlexSymbol{\complement}</code>	<code>{Ord}{MSA}{7B}</code>
729	<code>\DeclareFlexSymbol{\intercal}</code>	<code>{Bin}{MSA}{7C}</code>
730	<code>\DeclareFlexSymbol{\circledcirc}</code>	<code>{Bin}{MSA}{7D}</code>
731	<code>\DeclareFlexSymbol{\circledast}</code>	<code>{Bin}{MSA}{7E}</code>
732	<code>\DeclareFlexSymbol{\circleddash}</code>	<code>{Bin}{MSA}{7F}</code>
Begin AMSb declarations		
733	<code>\DeclareFlexSymbol{\lvertneqq}</code>	<code>{Rel}{MSB}{00}</code>
734	<code>\DeclareFlexSymbol{\gvertneqq}</code>	<code>{Rel}{MSB}{01}</code>
735	<code>\DeclareFlexSymbol{\nleq}</code>	<code>{Rel}{MSB}{02}</code>
736	<code>\DeclareFlexSymbol{\ngeq}</code>	<code>{Rel}{MSB}{03}</code>
737	<code>\DeclareFlexSymbol{\nless}</code>	<code>{Rel}{MSB}{04}</code>
738	<code>\DeclareFlexSymbol{\ngtr}</code>	<code>{Rel}{MSB}{05}</code>
739	<code>\DeclareFlexSymbol{\nprec}</code>	<code>{Rel}{MSB}{06}</code>
740	<code>\DeclareFlexSymbol{\nsucc}</code>	<code>{Rel}{MSB}{07}</code>
741	<code>\DeclareFlexSymbol{\lneqq}</code>	<code>{Rel}{MSB}{08}</code>
742	<code>\DeclareFlexSymbol{\gneqq}</code>	<code>{Rel}{MSB}{09}</code>
743	<code>\DeclareFlexSymbol{\nleqslant}</code>	<code>{Rel}{MSB}{0A}</code>
744	<code>\DeclareFlexSymbol{\ngeqslant}</code>	<code>{Rel}{MSB}{0B}</code>
745	<code>\DeclareFlexSymbol{\lneq}</code>	<code>{Rel}{MSB}{0C}</code>
746	<code>\DeclareFlexSymbol{\gneq}</code>	<code>{Rel}{MSB}{0D}</code>
747	<code>\DeclareFlexSymbol{\npreceq}</code>	<code>{Rel}{MSB}{0E}</code>
748	<code>\DeclareFlexSymbol{\nsucceq}</code>	<code>{Rel}{MSB}{0F}</code>
749	<code>\DeclareFlexSymbol{\precnsim}</code>	<code>{Rel}{MSB}{10}</code>
750	<code>\DeclareFlexSymbol{\succnsim}</code>	<code>{Rel}{MSB}{11}</code>
751	<code>\DeclareFlexSymbol{\lnsim}</code>	<code>{Rel}{MSB}{12}</code>
752	<code>\DeclareFlexSymbol{\gnsim}</code>	<code>{Rel}{MSB}{13}</code>

753	<code>\DeclareFlexSymbol{\nleqq}</code>	<code>{Rel}{MSB}{14}</code>
754	<code>\DeclareFlexSymbol{\ngeqq}</code>	<code>{Rel}{MSB}{15}</code>
755	<code>\DeclareFlexSymbol{\precneqq}</code>	<code>{Rel}{MSB}{16}</code>
756	<code>\DeclareFlexSymbol{\succneqq}</code>	<code>{Rel}{MSB}{17}</code>
757	<code>\DeclareFlexSymbol{\precnapprox}</code>	<code>{Rel}{MSB}{18}</code>
758	<code>\DeclareFlexSymbol{\succnapprox}</code>	<code>{Rel}{MSB}{19}</code>
759	<code>\DeclareFlexSymbol{\lnapprox}</code>	<code>{Rel}{MSB}{1A}</code>
760	<code>\DeclareFlexSymbol{\gnapprox}</code>	<code>{Rel}{MSB}{1B}</code>
761	<code>\DeclareFlexSymbol{\nsim}</code>	<code>{Rel}{MSB}{1C}</code>
762	<code>\DeclareFlexSymbol{\ncong}</code>	<code>{Rel}{MSB}{1D}</code>
763	<code>\DeclareFlexSymbol{\diagup}</code>	<code>{Ord}{MSB}{1E}</code>
764	<code>\DeclareFlexSymbol{\diagdown}</code>	<code>{Ord}{MSB}{1F}</code>
765	<code>\DeclareFlexSymbol{\varsubsetneq}</code>	<code>{Rel}{MSB}{20}</code>
766	<code>\DeclareFlexSymbol{\varsupsetneq}</code>	<code>{Rel}{MSB}{21}</code>
767	<code>\DeclareFlexSymbol{\nsubseteq}</code>	<code>{Rel}{MSB}{22}</code>
768	<code>\DeclareFlexSymbol{\nsupseteq}</code>	<code>{Rel}{MSB}{23}</code>
769	<code>\DeclareFlexSymbol{\subseteq}</code>	<code>{Rel}{MSB}{24}</code>
770	<code>\DeclareFlexSymbol{\supseteq}</code>	<code>{Rel}{MSB}{25}</code>
771	<code>\DeclareFlexSymbol{\varsubsetneqq}</code>	<code>{Rel}{MSB}{26}</code>
772	<code>\DeclareFlexSymbol{\varsupsetneqq}</code>	<code>{Rel}{MSB}{27}</code>
773	<code>\DeclareFlexSymbol{\subsetneq}</code>	<code>{Rel}{MSB}{28}</code>
774	<code>\DeclareFlexSymbol{\supsetneq}</code>	<code>{Rel}{MSB}{29}</code>
775	<code>\DeclareFlexSymbol{\nsubseteq}</code>	<code>{Rel}{MSB}{2A}</code>
776	<code>\DeclareFlexSymbol{\nsupseteq}</code>	<code>{Rel}{MSB}{2B}</code>
777	<code>\DeclareFlexSymbol{\nparallel}</code>	<code>{Rel}{MSB}{2C}</code>
778	<code>\DeclareFlexSymbol{\nmid}</code>	<code>{Rel}{MSB}{2D}</code>
779	<code>\DeclareFlexSymbol{\nshortmid}</code>	<code>{Rel}{MSB}{2E}</code>
780	<code>\DeclareFlexSymbol{\nshortparallel}</code>	<code>{Rel}{MSB}{2F}</code>
781	<code>\DeclareFlexSymbol{\nvdash}</code>	<code>{Rel}{MSB}{30}</code>
782	<code>\DeclareFlexSymbol{\nVdash}</code>	<code>{Rel}{MSB}{31}</code>
783	<code>\DeclareFlexSymbol{\nvDash}</code>	<code>{Rel}{MSB}{32}</code>
784	<code>\DeclareFlexSymbol{\nVDash}</code>	<code>{Rel}{MSB}{33}</code>
785	<code>\DeclareFlexSymbol{\ntrianglerighteq}</code>	<code>{Rel}{MSB}{34}</code>
786	<code>\DeclareFlexSymbol{\ntrianglelefteq}</code>	<code>{Rel}{MSB}{35}</code>
787	<code>\DeclareFlexSymbol{\ntriangleleft}</code>	<code>{Rel}{MSB}{36}</code>
788	<code>\DeclareFlexSymbol{\ntriangleright}</code>	<code>{Rel}{MSB}{37}</code>
789	<code>\DeclareFlexSymbol{\nleftarrow}</code>	<code>{Rel}{MSB}{38}</code>
790	<code>\DeclareFlexSymbol{\nrightarrow}</code>	<code>{Rel}{MSB}{39}</code>
791	<code>\DeclareFlexSymbol{\nLeftarrow}</code>	<code>{Rel}{MSB}{3A}</code>
792	<code>\DeclareFlexSymbol{\nRightarrow}</code>	<code>{Rel}{MSB}{3B}</code>
793	<code>\DeclareFlexSymbol{\nLeftrightarrow}</code>	<code>{Rel}{MSB}{3C}</code>
794	<code>\DeclareFlexSymbol{\nleqtrightharpoonup}</code>	<code>{Rel}{MSB}{3D}</code>
795	<code>\DeclareFlexSymbol{\divideontimes}</code>	<code>{Bin}{MSB}{3E}</code>
796	<code>\DeclareFlexSymbol{\varnothing}</code>	<code>{Ord}{MSB}{3F}</code>
797	<code>\DeclareFlexSymbol{\nexists}</code>	<code>{Ord}{MSB}{40}</code>
798	<code>\DeclareFlexSymbol{\Finv}</code>	<code>{Ord}{MSB}{60}</code>
799	<code>\DeclareFlexSymbol{\Game}</code>	<code>{Ord}{MSB}{61}</code>
In amsfonts.sty:		
800	<code>%%\DeclareFlexSymbol{\mho}</code>	<code>{Ord}{MSB}{66}</code>

```

801 \DeclareFlexSymbol{\eth}           {Ord}{MSB}{67}
802 \DeclareFlexSymbol{\eqsim}        {Rel}{MSB}{68}
803 \DeclareFlexSymbol{\beth}         {Ord}{MSB}{69}
804 \DeclareFlexSymbol{\gimel}        {Ord}{MSB}{6A}
805 \DeclareFlexSymbol{\daleth}       {Ord}{MSB}{6B}
806 \DeclareFlexSymbol{\lessdot}      {Bin}{MSB}{6C}
807 \DeclareFlexSymbol{\gtrdot}       {Bin}{MSB}{6D}
808 \DeclareFlexSymbol{\ltimes}        {Bin}{MSB}{6E}
809 \DeclareFlexSymbol{\rtimes}       {Bin}{MSB}{6F}
810 \DeclareFlexSymbol{\shortmid}     {Rel}{MSB}{70}
811 \DeclareFlexSymbol{\shortparallel} {Rel}{MSB}{71}
812 \DeclareFlexSymbol{\smallsetminus} {Bin}{MSB}{72}
813 \DeclareFlexSymbol{\thicksim}     {Rel}{MSB}{73}
814 \DeclareFlexSymbol{\thickapprox}  {Rel}{MSB}{74}
815 \DeclareFlexSymbol{\approxeq}     {Rel}{MSB}{75}
816 \DeclareFlexSymbol{\succapprox}   {Rel}{MSB}{76}
817 \DeclareFlexSymbol{\precapprox}   {Rel}{MSB}{77}
818 \DeclareFlexSymbol{\curvearrowleft} {Rel}{MSB}{78}
819 \DeclareFlexSymbol{\curvearrowright} {Rel}{MSB}{79}
820 \DeclareFlexSymbol{\digamma}      {Ord}{MSB}{7A}
821 \DeclareFlexSymbol{\varkappa}      {Ord}{MSB}{7B}
822 \DeclareFlexSymbol{\Bbbk}          {Ord}{MSB}{7C}
823 \DeclareFlexSymbol{\hslash}        {Ord}{MSB}{7D}

In amsfonts.sty:
824 %%\DeclareFlexSymbol{\hbar}        {Ord}{MSB}{7E}
825 \DeclareFlexSymbol{\backepsilon}   {Rel}{MSB}{7F}
826 </msabm>

```

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\@gobble	12, 139, 212
\@gobblefour	15
\@gobblethree	195
\@height	564
\@ifpackageloaded	222
\@ifundefined	152, 158
\@nil	213, 216
\@nx	3, 5, 55, 108, 112, 113, 174–182, 273
\@onefilewithoptions	202
\@secondoftwo	138
\@sym	12, 14, 93, 112, 131, 137, 196, 210
\@sym@ord	210, 213
\@sym@ord@a	213, 216
\@symAcc	93
\@begindocumenthook	227, 229
\@firstofone	94, 138
\@for	201
\"	6, 11
\'	234
*	234
\-	224, 235, 237, 239, 242
\.	215, 234
\/	242
\:	242
\=	225
\?	128, 134
\@	215

<code>\@symBin</code>	97, 178, 189	<code>\Bbbk</code>	821
<code>\@symCOi</code>	100, 177, 188	<code>\because</code>	652
<code>\@symCOs</code>	101, 176, 187	<code>\begingroup</code>	
<code>\@symClo</code>	103	. 111, 130, 136, 208, 214, 223, 599	
<code>\@symDeB</code>	106	<code>\beta</code>	315
<code>\@symDeL</code>	104	<code>\beth</code>	802
<code>\@symDeR</code>	105	<code>\between</code>	681
<code>\@symErr</code>	181	<code>\bigcap</code>	511
<code>\@symInn</code>	107	<code>\bigcirc</code>	461
<code>\@symOpe</code>	102	<code>\bigcup</code>	512
<code>\@symOrd</code>	95, 96, 174, 185	<code>\bigodot</code>	518
<code>\@symPun</code>	99, 180, 191	<code>\bigoplus</code>	517
<code>\@symRel</code>	98, 179, 190, 206	<code>\bigotimes</code>	516
<code>\@symVar</code>	96, 175, 186	<code>\bigsqcup</code>	520
<code>\@symextension</code>	199, 202	<code>\bigstar</code>	680
<code>\@symtype</code>	94, 95, 97–107, 138, 210	<code>\bigtriangledown</code>	438
<code>\@symtype@ord</code>	210, 212	<code>\bigtriangleup</code>	437
<code>\@tempa</code>	54, 56–60	<code>\biguplus</code>	510
<code>\@tempb</code>	112, 114, 118, 201, 202	<code>\bigvee</code>	508
<code>\@typeset@protect</code>	15	<code>\bigwedge</code>	509
<code>\@vereq</code>	569	<code>\binrel@</code>	193
<code>\@xncc</code>	108, 112	<code>\binrel@@</code>	173, 185–191
<code>\@exp</code> ...	3, 15, 55, 61, 108, 123, 202, 213, 218, 267–270, 273, 607, 608	<code>\binrel@a</code>	184, 196
<code>\ </code>	260	<code>\binrel@sym</code>	172, 196
<code>\~</code>	117, 143	<code>\blacklozenge</code>	616
A			
<code>\afterassignment</code>	133	<code>\blacktriangle</code>	686
<code>\aleph</code>	419	<code>\blacktriangledown</code>	682
<code>\alpha</code>	314	<code>\blacktriangleleft</code>	684
<code>\amalg</code>	448	<code>\blacktriangleright</code>	683
<code>\angle</code>	559, 698	<code>\bot</code>	427
<code>\approx</code>	484	<code>\bowtie</code>	578
<code>\approxeq</code>	814	<code>\box</code>	161, 166, 169
<code>\Arrowvert</code>	547	<code>\boxdot</code>	609
<code>\arrowvert</code>	546	<code>\boxminus</code>	621
<code>\ast</code>	416, 464	<code>\boxplus</code>	610
<code>\asymp</code>	502	<code>\boxtimes</code>	611
<code>\AtBeginDocument</code>	232	<code>\bracevert</code>	545
<code>\AtEndOfPackage</code>	5	<code>\buildrel</code>	575
B			
<code>\backepsilon</code>	824	<code>\bullet</code>	450
<code>\backprime</code>	667	<code>\Bumpeq</code>	717
<code>\backsim</code>	725	<code>\bumpeq</code>	716
<code>\backsimeq</code>	726	C	
<code>\backslash</code>	554	<code>\c@ncel</code>	573
<code>\barwedge</code>	696	<code>\Cap</code>	708, 709
<code>\baselineskip</code>	592	<code>\cap</code>	441
		<code>\catcode</code>	6, 11
		<code>\cdot</code>	463
		<code>\cdotOrd</code>	505, 506

<code>\cdotp</code>	506, 590	<code>\def</code>	14, 18–
<code>\cdots</code>	590		32, 52–54, 61, 92, 93, 95–108,
<code>\centerdot</code>	614		110, 122, 128, 129, 136, 140,
<code>\chardef</code>	134		153, 159, 163, 167, 172, 184–
<code>\check@mathfonts</code>	136		191, 193, 199, 210, 212, 213,
<code>\chi</code>	334		216, 224, 233, 413, 506, 599, 601
<code>\circ</code>	460	<code>\delim@a</code>	52, 55
<code>\circeq</code>	646	<code>\delim@b</code>	53, 218
<code>\circlearrowleft</code>	618	<code>\Delimiter</code>	38, 39
<code>\circlearrowright</code>	617	<code>\delimiter</code>	34
<code>\circledast</code>	730	<code>\Delta</code>	289
<code>\circledcirc</code>	729	<code>\delta</code>	317
<code>\circleddash</code>	731	<code>\diagdown</code>	763
<code>\circledS</code>	722	<code>\diagup</code>	762
<code>\cleaders</code>	160, 164, 168	<code>\diamond</code>	449
<code>\clubsuit</code>	432	<code>\diamondsuit</code>	433
<code>\colon</code>	284	<code>\digamma</code>	819
<code>\complement</code>	727	<code>\displaylimits</code>	42, 44
<code>\cong</code>	569	<code>\div</code>	452
<code>\coprod</code>	507	<code>\divideontimes</code>	794
<code>\copy</code>	160, 165	<code>\do</code>	4, 10, 61–91, 201
<code>\crrcr</code>	561, 562, 564	<code>\Doteq</code>	654
<code>\csname</code>	33–35, 37,	<code>\doteq</code>	575
	39, 41, 45–51, 55–61, 108, 123,	<code>\doteqdot</code>	653, 654
	217, 218, 267–270, 273, 607, 608	<code>\dotplus</code>	724
<code>\Cup</code>	706, 707	<code>\doublebarwedge</code>	697
<code>\cup</code>	442	<code>\doublecap</code>	709
<code>\curlyeqprec</code>	661	<code>\doublecup</code>	707
<code>\curlyeqsucc</code>	662	<code>\Downarrow</code>	552
<code>\curlyvee</code>	711	<code>\downarrow</code>	549
<code>\curlywedge</code>	710	<code>\downdownarrows</code>	630
<code>\curvearrowleft</code>	817	<code>\downharpoonleft</code>	635
<code>\curvearrowright</code>	818	<code>\downharpoonright</code>	633
		<code>\dp</code>	155
D			
<code>\dagger</code>	444	E	
<code>\daleth</code>	804	<code>\edef</code> 4, 37, 39, 41, 45–51, 56–60, 112, 602	
<code>\dashv</code>	471	<code>\ell</code>	345
<code>\ddagger</code>	443	<code>\else</code>	15, 52,
<code>\ddots</code>	594		53, 115, 142, 175–181, 219, 236, 238
<code>\DeclareFlexCompoundSymbol</code>		<code>\emptyset</code>	424
	122, 556, 558, 559,	<code>\endcsname</code>	33–35, 37,
	567–569, 573–586, 590, 591, 594		39, 41, 45–51, 55–61, 108, 123,
<code>\DeclareFlexSymbol</code>	110,		217, 218, 267–270, 273, 607, 608
	281–412, 414–505, 507–555,	<code>\endgroup</code>	
	557, 609–631, 633–653, 655–		120, 128, 146, 208, 215, 230, 600
	706, 708, 710–718, 720, 722–824	<code>\endinput</code>	262
<code>\DeclareOption</code>	13, 245–248	<code>\epsilon</code>	318
<code>\DeclareRobustCommand</code>		<code>\eqcirc</code>	688
	123, 126, 127, 149, 206, 207	<code>\eqsim</code>	801

<code>\eqslantgtr</code>	660	<code>\hbox</code>	150, 154, 161, 165, 169, 194, 593, 596, 597
<code>\eqslantless</code>	659	<code>\heartsuit</code>	434
<code>\equiv</code>	501	<code>\hexnumber@</code>	267–270, 602, 607, 608
<code>\eta</code>	320	<code>\hfill</code>	161, 165, 169, 564
<code>\eth</code>	800	<code>\hookleftarrow</code>	577
<code>\everymath</code>	139	<code>\hookrightarrow</code>	576
<code>\ExecuteOptions</code>	249	<code>\hrule</code>	564
<code>\exists</code>	430	<code>\hslash</code>	822
<code>\expandafter</code>	3, 33–35, 143, 229	<code>\ht</code>	155, 159, 163, 167
F			
<code>\fallingdotseq</code>	669	I	
<code>\fi</code>	15, 52, 53, 119, 145, 181, 220, 240, 241	<code>\ialign</code>	560
<code>\Finv</code>	797	<code>\if</code>	218
<code>\flat</code>	348	<code>\ifcat</code>	113, 141
<code>\flexi@stop</code>	225, 229	<code>\iff</code>	587
<code>\forall</code>	429	<code>\ifmmode</code>	139
<code>\frown</code>	355	<code>\ifnum</code>	235, 237
G			
<code>\Game</code>	798	<code>\iftrue</code>	139
<code>\Gamma</code>	288	<code>\ifx</code>	15, 52, 53, 174–180
<code>\gamma</code>	316	<code>\Im</code>	421
<code>\gdef</code>	185–191, 271, 272, 274	<code>\imath</code>	343
<code>\ge</code>	255	<code>\in</code>	491, 573
<code>\geq</code>	255, 481	<code>\infty</code>	422
<code>\geqq</code>	671	<code>\int</code>	513
<code>\geqslant</code>	672	<code>\intercal</code>	728
<code>\gets</code>	258	<code>\intlimits</code>	43, 51, 100
<code>\gg</code>	493	<code>\iota</code>	322
<code>\ggg</code>	720, 721	J	
<code>\gggtr</code>	721	<code>\jmath</code>	344
<code>\gimel</code>	803	<code>\joinord</code> ..	570–572, 576–583, 585, 586
<code>\global</code>	109, 275–280	K	
<code>\gnapprox</code>	759	<code>\kappa</code>	323
<code>\gneq</code>	745	<code>\kern</code>	593, 596
<code>\gneqq</code>	741	L	
<code>\gnsim</code>	751	<code>\Lambda</code>	291
<code>\gtrapprox</code>	649	<code>\lambda</code>	324
<code>\gtrdot</code>	806	<code>\land</code>	252
<code>\gtreqless</code>	690	<code>\langle</code>	522
<code>\gtreqqless</code>	692	<code>\lbrace</code>	524
<code>\gtrless</code>	673	<code>\lccode</code>	117, 143, 215
<code>\gtrsim</code>	648	<code>\lceil</code>	526
<code>\gvertneqq</code>	733	<code>\ldotp</code>	413
H			
<code>\hbar</code>	556, 823	<code>\ldotPun</code>	412, 413
<code>\hbarOrd</code>	555, 556	<code>\le</code>	254
		<code>\leaders</code>	564
		<code>\leavevmode</code>	149

<code>\mg@arr</code>	22	<code>\nleftarrow</code>	788
<code>\mg@Bbb</code>	29	<code>\nLeftrightarrow</code>	792
<code>\mg@bflatin</code>	28	<code>\nleftrightharpoonrightarrow</code>	793
<code>\mg@bin</code>	18, 271, 278, 279	<code>\nleq</code>	734
<code>\mg@cal</code>	30	<code>\nleqq</code>	752
<code>\mg@cop</code>	24, 280	<code>\nleqslant</code>	742
<code>\mg@del</code>	21, 272, 280	<code>\nless</code>	736
<code>\mg@digit</code>	32, 273, 277	<code>\nmid</code>	777
<code>\mg@frak</code>	31	<code>\noalign</code>	563
<code>\mg@Greek</code>	27, 277	<code>\noexpand</code>	3, 37, 39, 41, 141
<code>\mg@greek</code>	26, 276	<code>\nointerlineskip</code>	563
<code>\mg@Latin</code>	275	<code>\nolimits</code>	43
<code>\mg@latin</code>	25, 274–276	<code>\not</code>	206, 567
<code>\mg@nre</code>	20	<code>\notin</code>	573
<code>\mg@OML</code>	274	<code>\notRel</code>	206, 503, 562
<code>\mg@OMS</code>	271	<code>\nparallel</code>	776
<code>\mg@OMX</code>	272	<code>\nprec</code>	738
<code>\mg@ord</code>	279	<code>\npreceq</code>	746
<code>\mg@rel</code>	19, 278	<code>\nrightarrow</code>	791
<code>\mho</code>	799	<code>\nrightharpoonrightarrow</code>	789
<code>\mid</code>	470	<code>\nshortmid</code>	778
<code>\mkern</code>	140, 160–162, 164–166, 168–170, 556, 562, 564, 571, 572, 595–597	<code>\nshortparallel</code>	779
<code>\models</code>	579	<code>\nsim</code>	760
<code>\mp</code>	458	<code>\nsubseteq</code>	774
<code>\mskip</code>	140, 588	<code>\nsubseteqq</code>	766
<code>\mu</code>	325	<code>\nsucc</code>	739
<code>\multimap</code>	650	<code>\nsucceq</code>	747
<code>\muskip</code>	140	<code>\nsupseteq</code>	775
N			
<code>\nabla</code>	425	<code>\nsupseteqq</code>	767
<code>\namelimits</code>	44	<code>\ntriangleleft</code>	786
<code>\natural</code>	349	<code>\ntrianglelefteq</code>	785
<code>\ncong</code>	761	<code>\ntriangleright</code>	787
<code>\ne</code>	256	<code>\ntrianglerighteq</code>	784
<code>\nearrow</code>	473	<code>\nu</code>	326
<code>\neg</code>	251, 431	<code>\number</code>	6
<code>\neq</code>	256, 567	<code>\nVDash</code>	783
<code>\newcommand</code>	36, 38, 40, 200, 205	<code>\nVdash</code>	781
<code>\newmcodes@</code>	233	<code>\nvDash</code>	782
<code>\nexists</code>	796	<code>\nvdash</code>	780
<code>\next</code>	224, 229	<code>\nwarrow</code>	475
<code>\ngeq</code>	735	O	
<code>\ngeqq</code>	753	<code>\odot</code>	453
<code>\ngeqslant</code>	743	<code>\oint</code>	519
<code>\ngtr</code>	737	<code>\Omega</code>	298
<code>\ni</code>	257, 492	<code>\omega</code>	336
<code>\nLeftarrow</code>	790	<code>\ominus</code>	456
		<code>\oplus</code>	457

<code>\OrdSymbol</code>	95, 97–107, 138, 162, 164, 168, 170, 182, 185–191, 206, 207, 211
<code>\oslash</code>	454
<code>\otimes</code>	455
<code>\over</code>	575
<code>\owns</code>	257
P	
<code>\p@</code>	592, 593, 595–597
<code>\parallel</code>	469
<code>\partial</code>	347
<code>\PassOptionsToPackage</code>	245
<code>\perp</code>	500
<code>\Phi</code>	296
<code>\phi</code>	333
<code>\Pi</code>	293
<code>\pi</code>	328
<code>\pitchfork</code>	723
<code>\pm</code>	459
<code>\prec</code>	483
<code>\precapprox</code>	816
<code>\preccurlyeq</code>	663
<code>\preceq</code>	486
<code>\precnapprox</code>	756
<code>\precneqq</code>	754
<code>\precnsim</code>	748
<code>\precsim</code>	656
<code>\prime</code>	150, 423
<code>\ProcessOptions</code>	250
<code>\prod</code>	514
<code>\propto</code>	466
<code>\protect</code>	15
<code>\providecommand</code>	148, 570
<code>\ProvidesFile</code>	205
<code>\ProvidesPackage</code>	2
<code>\ProvidesSymbols</code> ..	205, 264–266, 605
<code>\Psi</code>	297
<code>\psi</code>	335
R	
<code>\Radical</code>	40, 41
<code>\radical</code>	35
<code>\raise</code>	150, 595, 597
<code>\rangle</code>	521
<code>\rbrace</code>	523
<code>\rceil</code>	525
<code>\Re</code>	420
<code>\relax</code>	7, 10, 52, 53, 113, 116, 117, 124, 131, 141, 143, 211, 224, 225, 239, 242, 250, 606
<code>\Relbar</code>	580, 582, 601, 602
<code>\relbar</code> ..	159, 163, 167, 581, 583, 599
<code>\renewcommand</code> ..	251–260, 571, 572, 587
<code>\RequirePackage</code>	261, 606
<code>\resetMathstrut@</code>	153
<code>\restriction</code>	632
<code>\rfloor</code>	527
<code>\rgroup</code>	544
<code>\rho</code>	329
<code>\rhoRel</code>	415, 577
<code>\rightarrow</code>	479, 580, 586
<code>\rightarrowtail</code>	162, 170, 259, 497, 568, 576, 581, 585
<code>\rightarrowfill@</code>	159
<code>\rightarrowtail</code>	636
<code>\rightharpoondown</code>	359
<code>\rightharpoonup</code>	358
<code>\rightleftarrows</code>	639
<code>\rightleftharpoons</code>	574, 619
<code>\rightrightarrows</code>	628
<code>\rightsquigarrow</code>	642
<code>\rightthreetimes</code>	713
<code>\risingdotseq</code>	668
<code>\rlh@</code>	574
<code>\rmoustache</code>	542
<code>\Rrightarrow</code>	693
<code>\Rsh</code>	641
<code>\rtimes</code>	808
<code>\rVert</code>	534
<code>\rvert</code>	536
S	
<code>\scriptchar</code>	127
<code>\scriptfont</code>	127, 150
<code>\scriptstyle</code>	561
<code>\searrow</code>	474
<code>\setbox</code>	154, 194
<code>\setboxz@h</code>	159, 163, 167
<code>\setminus</code>	462
<code>\sharp</code>	350
<code>\shortmid</code>	809
<code>\shortparallel</code>	810
<code>\Sigma</code>	294
<code>\sigma</code>	330
<code>\sim</code>	498, 569
<code>\simeq</code>	499
<code>\smallfrown</code>	703

<code>\smallint</code>	436	<code>\symupright</code>	602
<code>\smallsetminus</code>	811		
<code>\smallsmile</code>	702		
<code>\smash@</code>	599		
<code>\smile</code>	354		
<code>\spadesuit</code>	435		
<code>\sphericalangle</code>	700		
<code>\sqcap</code>	445		
<code>\sqcup</code>	446		
<code>\sqsubset</code>	674		
<code>\sqsubseteq</code>	467		
<code>\sqsupset</code>	675		
<code>\sqsupseteq</code>	468		
<code>\square</code>	612		
<code>\star</code>	353		
<code>\std@equal</code>	225		
<code>\std@minus</code>	224, 239		
<code>\string</code>	37, 39, 41, 143, 213, 602		
<code>\Subset</code>	704		
<code>\subset</code>	488		
<code>\subseteq</code>	490		
<code>\subseteqq</code>	714		
<code>\subsetneq</code>	772		
<code>\subsetneqq</code>	768		
<code>\succ</code>	482		
<code>\succapprox</code>	815		
<code>\succcurlyeq</code>	670		
<code>\succeq</code>	485		
<code>\succnapprox</code>	757		
<code>\succneqq</code>	755		
<code>\succnsim</code>	749		
<code>\succsim</code>	647		
<code>\sum</code>	515		
<code>\sumlimits</code>	42, 50, 101		
<code>\Supset</code>	705		
<code>\supset</code>	487		
<code>\supseteq</code>	489		
<code>\supseteqq</code>	715		
<code>\supsetneq</code>	773		
<code>\supsetneqq</code>	769		
<code>\surd</code>	558		
<code>\surdOrd</code>	557, 558		
<code>\swarrow</code>	476		
<code>\sym@global</code>	109, 114, 116, 118, 124		
<code>\symAMSa</code>	607		
<code>\symAMSb</code>	608		
<code>\symlargesymbols</code>	270		
<code>\symletters</code>	268		
<code>\symoperators</code>	267		
<code>\symsymbols</code>	269		
		T	
		<code>\tau</code>	331
		<code>\text@char</code>	126, 127, 136, 150
		<code>\text@char@a</code>	128, 133
		<code>\text@char@sym</code>	129, 137
		<code>\text@script@char</code>	132, 137
		<code>\textchar</code>	126, 154
		<code>\textfont</code>	126
		<code>\textprime</code>	148, 149
		<code>\textstyle</code>	575
		<code>\the</code>	132, 227
		<code>\therefore</code>	651
		<code>\Theta</code>	290
		<code>\theta</code>	321
		<code>\thickapprox</code>	813
		<code>\thickmuskip</code>	588
		<code>\thicksim</code>	812
		<code>\times</code>	465
		<code>\to</code>	259
		<code>\toks@</code>	226, 227
		<code>\top</code>	426
		<code>\triangle</code>	428
		<code>\triangledown</code>	687
		<code>\triangleleft</code>	351, 578
		<code>\trianglelefteq</code>	679
		<code>\triangleq</code>	655
		<code>\triangleright</code>	352, 578
		<code>\trianglerighteq</code>	678
		<code>\twoheadleftarrow</code>	626
		<code>\twoheadrightarrow</code>	625
		U	
		<code>\Uparrow</code>	551
		<code>\uparrow</code>	548
		<code>\Updownarrow</code>	553
		<code>\updownarrow</code>	550
		<code>\upharpoonleft</code>	634
		<code>\upharpoonright</code>	631, 632
		<code>\uplus</code>	447
		<code>\Upsilon</code>	295
		<code>\upsilon</code>	332
		<code>\upuparrows</code>	629
		<code>\usesymbols</code>	200, 246–248
		V	
		<code>\varepsilon</code>	337
		<code>\varkappa</code>	820
		<code>\varnothing</code>	795

<code>\varphi</code>	342	<code>\veebar</code>	695
<code>\varpi</code>	339	<code>\Vert</code>	260, 537
<code>\varpropto</code>	701	<code>\vert</code>	154, 538, 579
<code>\varrho</code>	340	<code>\Vdash</code>	623
<code>\varsigma</code>	341		
<code>\varsubsetneq</code>	764	W	
<code>\varsubsetneqq</code>	770	<code>\wedge</code>	252, 439
<code>\varsupsetneq</code>	765	<code>\wp</code>	346
<code>\varsupsetneqq</code>	771	<code>\wr</code>	451
<code>\vartheta</code>	338		
<code>\vartriangle</code>	685	X	
<code>\vartriangleleft</code>	677	<code>\xdef</code>	173, 227, 267–270, 273, 607, 608
<code>\vartriangleright</code>	676	<code>\Xi</code>	292
<code>\vbox</code>	560, 592, 596	<code>\xi</code>	327
<code>\Vdash</code>	622		
<code>\vDash</code>	624	Z	
<code>\vdash</code>	472	<code>\z@</code>	140, 154, 155, 159–
<code>\vdots</code>	591		161, 163, 165–167, 169, 194, 592
<code>\vee</code>	253, 440	<code>\zeta</code>	319