

texlinks.sty

T_EX-Related Links for `hyperref`, `blog.sty` (and maybe more)*

Uwe Lück[†]

December 8, 2012

Abstract

`texlinks.sty` provides a couple of shorthands for making hyperlinks with `hyperref`'s¹ `\href` command, linking to URLs that one often refers to in discussing T_EX-related material. Especially, TUG material (including texhax postings and TUGboat articles) and CTAN pages (package descriptions, directories, Catalogue) are supported, also the UK FAQ, the L^AT_EX Wikibook, and Wikipedia (where much T_EX-related software is described in a visually appealing manner). However, up to now I have used them for *HTML* overviews generated with `blog.sty`. They may as well be useful with better known (and better developed) T_EX → HTML software such as `tex4ht`² or `LaTeX2HTML`³ (I don't know).

Contents

1	Usage	2
2	Package File Header (Legalese)	3
3	Outline	3
4	Package Options	3
5	Fonts for URLs and File/Package Names	4

*This document describes version [v0.71](#) of `texlinks.sty` as of 2012/12/08.

[†]<http://contact-ednotes.sty.de.vu>

¹<http://ctan.org/pkg/hyperref>

²<http://ctan.org/pkg/tex4ht>

³<http://ctan.org/pkg/latex2html>

1	USAGE	2
6	Providing \httpref and \httpsref	4
7	Variants of \httpref and \httpsref	5
7.1	URLs as Links	5
7.2	Linking URLs in Footnotes	6
7.3	URL Bases	6
8	Wikipedia	7
8.1	Backbones	7
8.2	Piped Links	8
8.3	English and German	9
8.4	“Implicit” Choice of Language	9
8.5	Blanks and Umlauts in URLs and Anchors	10
9	T_EX-related	11
9.1	CTAN	11
9.1.1	Directories and Files in a T _E X Archive	11
9.1.2	Jürgen Fenn’s Topical T _E X Catalogue	12
9.1.3	Jim Hefferon’s Package Descriptions	12
9.2	Mailing Lists	13
9.3	CTAN Announcements	14
9.4	TUG	14
9.4.1	texhax	15
9.4.2	Other	15
9.5	UK FAQ	16
9.6	Wikibooks	16
10	Leaving and Version HISTORY	16

1 Usage

The file `texlinks.sty` is provided ready, installation only requires putting it somewhere where T_EX finds it (which may need updating the filename data base).⁴

Below the `\documentclass` line(s) and above `\begin{document}`, you load `texlinks.sty` (as usually) by

```
\usepackage{texlinks}
```

Package options and user commands are described near their definitions below in the implementation section.

⁴<http://www.tex.ac.uk/cgi-bin/texfaq2html?label=inst-wlcf>

2 Package File Header (Legalese)

```

1 \NeedsTeXFormat{LaTeX2e}[1994/12/01] %% \newcommand* etc.
2 \ProvidesPackage{texlinks}[2012/12/08 v0.71 TeX-related links (UL)]
3 %% copyright (C) 2011 2012 Uwe Lueck,
4 %% http://www.contact-ednotes.sty.de.vu
5 %% -- author-maintained in the sense of LPPL below.
6 %%
7 %% This file can be redistributed and/or modified under
8 %% the terms of the LaTeX Project Public License; either
9 %% version 1.3c of the License, or any later version.
10 %% The latest version of this license is in
11 %% http://www.latex-project.org/lppl.txt
12 %% We did our best to help you, but there is NO WARRANTY.
13 %%
14 %% Please report bugs, problems, and suggestions via
15 %%
16 %% http://www.contact-ednotes.sty.de.vu
17 %%

```

3 Outline

The link macros of `texlinks` are based on macros `\httpref` and `\httpsref`. For use of `texlinks` with `blog.sty`, the latter provides definitions of `\httpref` and `\httpsref` suitable for HTML, where a choice of opening a new tab or window—or not—is relevant.

For use with `hyperref` (or ...?), `texlinks` may provide definitions of `\httpref` and `\httpsref` based on `\href`. The decision to do so or not may happen at `\begin{document}`. `blog.sty` generates HTML without using the `{document}` environment, so we might assume that when `\begin{document}` is found, we are running `hyperref`, or just *something* that provides a useful `\href`. We might then execute a definition of `\httpref` in terms of `\href`. Well, not sure ...

Moreover, a PDF file with links may be *printed*, and clicking the links on the paper may fail. URLs in main text, on the other hand, sometimes are troublesome. I consider it a good idea to present links with their URL as the displayed text in *footnotes* (or *endnotes*). It may even be useful with HTML to present the URLs displayed in some “appendix.”—This idea has been resumed in v0.2 only, `\urlfoot`.

4 Package Options

Somebody may want to suppress a definition of `\httpref` at `\begin{document}` ... [2011/01/24, [TODO](#)]

v0.3: Package option `[blog]` suppresses *any* `\AtBeginDocument` actions—fine for use with `blog.sty`.

```

18 \DeclareOption{blog}{\let\AtBeginDocument\@gobble}

```

This option may be improved, and another option may be useful for different purposes than running `blog.sty`.

19 `\ProcessOptions`

5 Fonts for URLs and File/Package Names

This section “provides” markup for displaying URLs (`\urlfmt`), file names (`\filenamefmt`)—thinking of single files that may be found in the internet or on your computer—, and “packages” (`\pkgnamefmt`). For the latter two, in certain files I use shorthands `\file` and `\pkg`, resp., ... (Not sure about `\providecommand` `TODO` ...)

It is usual to use `\texttt` for formatting T_EX code (“verbatim”, `\verb` etc.). It may also be common to use `\texttt` for file names, perhaps even for URLs. Therefore we provide `\urlfmt{<url>}` as follows:

20 `\providecommand*{\urlfmt}{\texttt}`

The file name format `\filenamefmt{<file-name>}` may differ from the format for URLs—if somebody wants/adjusts it, *here* it is the *same*:

21 `\providecommand*{\filenamefmt}{\texttt}`

... I favour `\code` over `\texttt` as “logical markup,” inspired by the `<code>` element in HTML, but it is too difficult to provide this right now here ...

`\pkgnamefmt{<package-name>}` displays the name of a “package”. Using `\textsf` for `\pkgnamefmt` seems to conform to common practice today—implemented here. The following code may later be suppressed at some package options, as with the choice for `\httpref`:

22 `% \@ifdefinable\pkgnamefmt {\let\pkgnamefmt\@firstofone}`
 23 `% \@AtBeginDocument {\let\pkgnamefmt\textsf}`

← This was here until v0.7, makes a difference for PDF vs. `blog` HTML. Now we choose the same as with `\urlfmt`:

24 `\providecommand*{\pkgnamefmt}{\textsf}`

Indeed, the same day we are providing `\textsf` in `blog.sty`. However, the rationale of the earlier solution was that web pages use sans-serif as the *normal* font ...

6 Providing `\httpref` and `\httpsref`

`\httpref{<host-path[#frag]>}{<text>}`

should display `<text>` as a link to `http://<host-path[#frag]>`;

`\httpsref{<host-path[#frag]>}{<text>}`

is the obvious analogue for `https:` URLs. In case `\begin{document}` is found with a definition of `\href` present, we provide definitions of `\httpref` and `\httpsref` in terms of `\href` there:

```

25 \AtBeginDocument{%
26   \@ifundefined{href}{%
27     % \PackageError ... TODO!? 2011/01/24
28     }{\newcommand*\httpref}[1]{\href {http://#1}}%
29     \newcommand*\httpsref}[1]{\href {https://#1}}}
```

7 Variants of \httpref and \httpsref

`\NormalHTTPref` may be used as an alias for `\httpref` in situations where the latter has been redefined (as in Section 7.2):

```

30 \AtBeginDocument{%% TODO: options, guarded \let (mine, HO)
31   \@ifdefinable\NormalHTTPref{\let\NormalHTTPref\httpref}}
```

`\ithttpref{<url>}{<text>}` displays *<text>* in italics:

```

32 % \newcommand*\ithttpref[2]{\NormalHTTPref{#1}{\textit{#2}}}
```

However, I seem never to have used it. And I would now prefer `\metahttpref`
 TODO ...

7.1 URLs as Links

With `\urlhttpref{<url>}`, that URL *<url>* is displayed:

```

33 \newcommand*\urlhttpref[1]{%
34   \NormalHTTPref{#1}{\urlfmt{\httpprefix#1}}}
```

In `blog.sty` (as of 2010/05/26), there was a command `\urlref` instead of `\urlhttpref`. It did not provide `\urlfmt`.

`\httpprefix` is an idea that was missing in `blog.sty` up to v0.3. It may be used to determine generally whether a display of an URL should include `http://`. I choose as default what was default in `blog.sty` (i.e., “don’t include”):

```

35 \@ifdefinable\httpprefix{\let\httpprefix\@empty} %% TODO cf. above
\let\httpprefix\relax would be bad for blog.sty (would display \relax),
while it would be somewhat more efficient.
```

Now you may customize `\httpprefix` by

```
\renewcommand{\httpprefix}{http://}
```

—or by `\let\httpprefix\theHTTPprefix`:

```

36 \newcommand*\theHTTPprefix{http://}
```

With `\urlhttpsref{<url>}`, we *force* displaying ‘https://’:

```

37 \newcommand*\urlhttpsref[1]{\httpsref{#1}{\urlfmt{https://#1}}}
```

7.2 Linking URLs in Footnotes

`\foothttpurlref{<url>}` just is like `\footnote{\urlhttpref{<url>}}`:

```
38 \newcommand*{\foothttpurlref}[1]{\footnote{\urlhttpref{#1}}}
```

`\urlfoot{<short>}{<id>}` redefines `\httpref` so that you can use all the shorthand macros based on `\httpref` to get the according URL display (as provided by `\urlhttpref`) in a footnote without the need to include the entire URL in your source code. `\urlfoot` is available with `<short>` and `<id>` when a shorthand `\<short>{<id>}{<text>}` has been defined where `\<short>` is the macro name and `<id>` is the target identifier (usually part of the URL generated from `<id>`) according to the syntax declaration of `\<short>`.

```
39 \newcommand*{\urlfoot}[2]{%
40   \let\httpref\foothttpurlref
41   \let\httpprefix\theHTTPprefix   %% TODO customizable!?
42   \csname #1\endcsname{#2}{}}
```

Example:

`\CtanPkgRef{morehype}{MoreHype}` and `\ctanpkgref{morehype}`

are provided below for linking to <http://ctan.org/pkg/morehype>.

- Try `CtanPkgRef` *here*: `MoreHype`,
for the *footnote* try `\urlfoot{CtanPkgRef}{morehype}`;⁵
- try `ctanpkgref` *here*: `morehype`,
for the *footnote* try `\urlfoot{ctanpkgref}{morehype}`.⁶`morehype`

The lonely ‘morehype’ you see there above demonstrates that it doesn’t work with `ctanpkgref` because `\ctanpkgref` doesn’t have separate arguments for `<id>` and `<text>`, it actually doubles `<id>`. A local `\let\ctanpkgref\CtanPkgRef` could help, but right now I prefer waiting for a better idea. [TODO]

v0.3: Now that using `\urlfoot` and `ctanpkgref` together is so clumsy, while I use it quite often, we get `\urlpkgfoot{<package-id>}`, abbreviating `\urlfoot{CtanPkgRef}{<package-id>}`:

```
43 \newcommand* {\urlpkgfoot} {\urlfoot{CtanPkgRef}}
```

7.3 URL Bases

We typically refer to many web pages under a certain domain, or in certain subdirectories there. Before v0.6, I made many definitions like

```
\newcommand*{\myref}[1]{\httpref{<my-base>/#1}}
```

⁵<http://ctan.org/pkg/morehype>

⁶<http://ctan.org/pkg/morehype>

for this purpose. Storing the definition of such a `\myref` uses 6 tokens (including parameter text—[TODO](#)) in addition to those from `\my-base`. With

```
\newcommand*\myref{\httpbaseref{\my-base}}
```

we need 3 tokens instead, using `\httpbaseref{\base}{\rest}` defined as follows:

```
44 \newcommand*\httpbaseref[2]{\httpref{#1/#2}}
```

We change many definitions in ensuing sections accordingly.

The situation is similar with (many) anchors of a (large) web page. With v0.6, we introduce `\httppancref{\page-url}{\anchor}`—perhaps, with `\mirrorctanref` (Sec. 9.1.2) etc.? [TODO](#)

```
45 % \newcommand*\httppancref[2]{\httpref{#1\##2}}
```

8 Wikipedia

8.1 Backbones

As of v0.6, we have a backbone macro

```
\wikilangref{\language-code}{\lemma}{\text}
```

for links to Wikipedia. (It was `\wikiref` before, starting with v0.4—sorry!) `\language-code` consists of two characters like ‘de’ for German Wikipedia articles or ‘en’ for English ones. `\lemma` is the identifier of the article, and `\text` is displayed as the link:

```
46 % \newcommand*\wikilangref[2]{\httpref{#1.wikipedia.org/wiki/#2}}
```

← 2012/03/09 etc. with Sec. 7.3 →

```
47 \newcommand*\wikilangref[1]{\httpbaseref{#1.wikipedia.org/wiki}}
```

There is `\Wikilangref{\language-code}{\lemma}` for the case that `\lemma` and `\text` are the same. With v0.7 however, this command becomes more powerful, see Section 8.2.

```
48 % \newcommand*\Wikilangref[2]{\wikilangref{#1}{#2}{#2}}
```

`\wikilangref{\lang}{\lemma}{\text}` would be nicer; however, the present code is to work with `blog.sty` which does not support optional arguments.

Quite often, programs share their names with movies, biological species, etc., then lemma disambiguation is required. Usually, we don’t want to display the disambiguation.

```
\Wikilangdisambref{\language-code}{\term}{\suffix}
```

will link to

```
http://\language-code.wikipedia.org/wiki/\term_{\suffix}
```

```
49 \newcommand*\Wikilangdisambref}[3]{\wikilangref{#1}{#2 (#3)}{#2}}
```

There was something like a more general variant `\wikidisambref`, now I doubt its usefulness and `omit` it in order to see where it occurs (2011/05/13).

For **anchors**, ‘#’ can be used with `blog.sty`—and even with `hyperref`.

Example: `\wikilangref{en}{TeX#History}{\TeX}` for \TeX .

8.2 Piped Links

v0.7 emulates Wikipedia’s piped links as with Wikipedia source code

```
[[Pipeline|Pipe]]
```

to get a link to article ‘Pipeline’ with displayed text ‘Pipe’. The same syntax (double brackets) is actually supported by `blog.sty` with `markblog.sty`, while otherwise only

```
\Wikilangref{<language-code>}{<lemma>|<text>}
```

works—with settings more below something like `\Wikiref{<lemma>|<text>}`—which admittedly is not much better than the equivalent

```
\wikiref{<lemma>}{<text>}
```

Even Wikipedia’s feature that empty `<text>` removes the disambiguation term as with `[[PipeL(computing)|]]` resulting in ‘Pipe’ is supported.

```
50 \newcommand*\Wikilangref}[2]{%
51   \@wikilpref{#1}#2\BiteSep|\@nnil\BiteSep\@nil{#2}}
```

I have introduced `\BiteSep` and this kind of parsing in the `bitelist`⁷ package.

```
52 \def\@wikilpref#1#2|#3\BiteSep#4\@nil#5{%
53   \ifx\@nnil#3\@empty
54     \wikilangref{#1}{#5}{#5}%
55   \else
56     \wikilangref{#1}{#2}{%
57       \ifx\@three#3\@three
58         \wiki@noparen#2\@nil%
59       \else
60         #3%
61       \fi}%
62   \fi}
63 \def\wiki@noparen#1 (#2\@nil{#1}
```

I have thought about improving `bitelist.sty`, resulting in the following code. In the present application, I do not consider it superior. It uses the same number of tokens but new one has additional expansion step. The situation is different to the general case because doing everything before `\fi` is okay here.

⁷<http://ctan.org/pkg/bitelist>


```

64 % \newcommand*{\Wikilangref}[2]{%
65 %     \@wikilPref{#1}#2\BiteSep\@secondoftwo
66 %     |\BiteSep\@firstoftwo\@nil{#2}}
67 % \def\@wikilPref#1#2|#3\BiteSep#4#5\@nil#6{%
68 %     #4{\wikilangref{#1}{#6}{#6}}%
69 %     {\wikilangref{#1}{#2}{%
70 %         \ifx\@three#3\@three
71 %         \wiki@noparen#2\@nil%
72 %         \else
73 %         #3%
74 %         \fi}}}

```

8.3 English and German

The next macros just save you from typing braces around the language codes for English and German: `\wikienref{<lemma>}{<text>}` refers to the English Wikipedia, `\wikideref{<lemma>}{<text>}` refers to the German one.

```

75 \newcommand*{\wikideref}{\wikilangref{de}}
76 \newcommand*{\wikienref}{\wikilangref{en}}

```

`\Wikideref{<lemma>}` refers to article `<lemma>` in the German Wikipedia and displays `<lemma>` as `<text>`:

```

77 \newcommand*{\Wikideref}{\Wikilangref{de}}

```

`\Wikienref{<lemma>}` is `\Wikideref`’s analogue for English:

```

78 \newcommand*{\Wikienref}{\Wikilangref{en}}

```

`\Wikidedisambref{<lemma>}{<suffix>}` chooses a disambiguation according to `<suffix>` for the German Wikipedia, `\Wikiendisambref{<lemma>}{<suffix>}` for the English one:

```

79 \newcommand*{\Wikidedisambref}{\Wikilangdisambref{de}}
80 \newcommand*{\Wikiendisambref}{\Wikilangdisambref{en}}

```

8.4 “Implicit” Choice of Language

With v0.6, `\wikiref{<lemma>}{<text>}` works like

```
\wikilangref{<lc>}{<lemma>}{<text>}
```

when `\langcode` expands to `<lc>` (the two-letter language code according to ISO 639-1). The default for `<lc>` is ‘en’ for English. It can be overridden even before loading texlinks (e.g., by an earlier `\newcommand\langcode{de}`):

```

81 \providecommand*{\langcode}{en}

```

For the German versions, use `\renewcommand{\langcode}{de}`. The langcode package provides a command `\uselangcode{<lc>}` that works like `\renewcommand*{\langcode}{<lc>}` and adjusts a number of other settings.

```
82 \newcommand*{\wikiref}{\wikilangref\langcode}
```

`\Wikiref` and `\Wikidisambref` are the obvious analogues:

```
83 \newcommand*{\Wikiref}{\Wikilangref\langcode}
```

```
84 \newcommand*{\Wikidisambref}{\Wikilangdisambref\langcode}
```

8.5 Blanks and Umlauts in URLs and Anchors

`\underscorechar` seemed to be useful in macro definitions. The name was inspired by L^AT_EX's `\@backslashchar` and `\@percentchar`. However, I am now trying what happens without it. It occurred in `blog.tex` for the documentation of the `blog` package, but `\string_` seems to be a good replacement.

```
85 % \newcommand \underscorechar {}
```

```
86 % {\@makeother\_ \gdef\underscorechar{\_}}
```

Anyway, in my notes I have a more elegant macro for providing “other” versions of special characters.

Guessing what `\underscorechar` was good for (2011-05-17): Wikipedia lemmas and anchors often or even *typically* contain *blank spaces*. The Wikipedia software usually converts them into underscore characters. Blank spaces in *lemmas* seem *not* to need treatment here in `texlinks`. However, Wikipedia also creates *anchors* from *section headings*, which typically contain blank spaces. This has been more difficult ...

Likewise with umlauts: text encoding suffices for *lemmas* (my `\urluml` is not needed for this purpose). But umlauts in *anchors* generated from *section headings* are different. While umlauts in *lemmas* are represented by sequences starting with a *percent* character, the anchors use a *dot* instead of the percent character. Therefore now `\ancuml{⟨char⟩}` is provided:

```
87 \newcommand*{\ancuml}[1]{\csname ancuml:#1\endcsname}
```

```
88 \@namedef{ancuml:a}{.C3.A4}
```

```
89 \@namedef{ancuml:o}{.C3.B6}
```

```
90 \@namedef{ancuml:u}{.C3.BC}
```

```
91 \@namedef{ancuml:s}{.C3.9F}
```

```
92 % \newcommand*{\itwikideref}[2]{\wikideref{#1}{\textit{#2}}}
```

```
93 % \newcommand*{\itwikienref}[2]{\wikienref{#1}{\textit{#2}}}
```

```
94 % \newcommand*{\urluml}[1]{\csname urluml:#1\endcsname}
```

```
95 % \@namedef{urluml:a}{\#C3\#A4}
```

```
96 % \@namedef{urluml:o}{\#C3\#B6}
```

```
97 % \@namedef{urluml:u}{\#C3\#BC}
```

```
98 % \@namedef{urluml:s}{\#C3\#9F}          %% 2010/08/09
```

9 T_EX-related

9.1 CTAN

9.1.1 Directories and Files in a T_EX Archive

`\tugctanref{<path>}{<text>}` makes `<text>` a link to a T_EX Archive directory or file `<path>`:

```
99 \newcommand*{\tugctanref}{\httpbaseref{tug.ctan.org/tex-archive}}
```

Alternatively, you can refer to an (automatically chosen) CTAN *mirror* using

`\mirrorctanref{<path>}{<text>}`.

(I prefer the *appearance* of the TUG archive, designed by Jim Hefferon.)

```
100 \newcommand*{\mirrorctanref}{\httpbaseref{mirror.ctan.org}}
```

You may actually want to “open” a file `<file-name>` in `<path>` on CTAN, `<file-name>` displayed as the link text, either by

`\tugctanfileref{<path>}{<file-name>}`

or (for a mirror) by

`\mirrorctanfileref{<path>}{<file-name>}`.

```
101 \newcommand*{\tugctanfileref}[2]{%
102   \tugctanref{#1/#2}{\filenamefmt{#2}}}
103 \newcommand*{\mirrorctanfileref}[2]{%
104   \mirrorctanref{#1/#2}{\filenamefmt{#2}}}
```

Typically, L^AT_EX macro packages in `macros/latex/contrib/` are discussed, so here is `\ltxcontrib` saving a few characters:

```
105 \newcommand*{\ltxcontrib}{macros/latex/contrib/}
```

`\ctanref` works like `\tugctanref` or like `\mirrorctanref`, depending on `\usetugctan` vs. `\usemirrorctan`. So in any case its syntax is

`\ctanref{<path>}{<text>}`.

Likewise, `\ctanfileref` works like

`\tugctanfileref` or `\mirrorctanfileref`,

depending on the same `\usetugctan` vs. `\usemirrorctan`, so the syntax is

`\ctanfileref{<path>}{<file-name>}`

```
106 \newcommand*{\ctanref}{} \newcommand*{\ctanfileref}{}
107 \newcommand*{\usemirrorctan}{%
108   \let \ctanref \mirrorctanref
109   \let \ctanfileref \mirrorctanfileref}
110 \newcommand*{\usetugctan}{%
111   \let \ctanref \tugctanref
112   \let \ctanfileref \tugctanfileref}
```

`\usemirrorctan` is the **default**, i.e., `\ctanref` and `\ctanfileref` use `mirror.ctan.org`:

```
113 \usemirrorctan
```

Remark (TODO): Another implementation I consider is using some `\ctanurl-` prefix that you can redefine for accessing your favourite mirror.

9.1.2 Jürgen Fenn’s Topical T_EX Catalogue

`\bytopicref{⟨anchor⟩}{⟨text⟩}` makes `⟨text⟩` a link to `⟨anchor⟩` of Jürgen Fenn’s Topical Index of the T_EX Catalogue. You find the `⟨anchor⟩` by clicking at the respective TOC entry on top of the page and then read the URL from the browser’s navigation display.

```
114 \newcommand*{\bytopicref}[1]{%
115     \mirrorctanref{help/Catalogue/bytopic.html\##1}}
```

(Example: `\bytopicref{html}{\acro{HTML}}` for HTML.)

9.1.3 Jim Hefferon’s Package Descriptions

For v0.6 and in the spirit of Sec. 7.3, we introduce an auxiliary

`\ctanorgbaseref{⟨more-path⟩}{⟨text⟩}`:

```
116 \newcommand*{\ctanorgbaseref}{\httpbaseref{ctan.org}}
```

`\ctanpkgref{⟨pkg-name⟩}` makes `⟨text⟩` a link to the CTAN package info page for the package `⟨pkg-name⟩`. `\CtanPkgRef{⟨name⟩}{⟨Name⟩}` is a variant for the cases where authors have a special idea `⟨Name⟩` using some capital letters when they describe their packages (ASCII versions of “logos” such as BibTeX) while the identifier `⟨name⟩` doesn’t allow capital letters. Also, `⟨Name⟩` may be a package from a *bundle* `⟨name⟩` where `⟨name⟩` has a description page while `⟨Name⟩` doesn’t have its *own* description page (such as `makedoc`—before 2012/04/10!).

```
117 \newcommand*{\CtanPkgRef}[2]{%
118     \ctanorgbaseref{pkg/#1}{\pkgnamefmt{#2}}}
119 \newcommand*{\ctanpkgref}[1]{\CtanPkgRef{#1}{#1}}
```

`\ctanpkgstyref{⟨name⟩}` adds ‘.sty’ to the package name:

```
120 \newcommand*{\ctanpkgstyref}[1]{\CtanPkgRef{#1}{#1.sty}}
```

Jim Hefferon also offers pages listing of all the packages of a given author, accessible by her/his `⟨id⟩`. `\ctanpkgautoref{⟨id⟩}{⟨text⟩}` makes `⟨text⟩` a link to that page:

```
121 \newcommand*{\ctanpkgautoref}[1]{\ctanorgbaseref{author/id/#1}}
```

E.g., see *my* packages.

9.2 Mailing Lists

v0.7 relies on package `langcode` for `\enmonthname{<month-number>}` and `\demonthname{<month-number>}`, for tricks with language codes extending those in Section 8.4:

```
122 \RequirePackage{langcode}
```

The next definitions are backbones for generating links to web pages about T_EX mailing lists. `\TL@piper@parse<year>-<month-number>-<id>` will be used for referring to single postings:

```
123 \def\TL@piper@parse#1-#2-#3/{#1-\enmonthname{#2}/#3}
```

```
\texlistyearmonthref<list-ref>{<2-digits>-<month-no>}
```

will generate `\<list-ref>{<path>}` for linking to the list of postings of the `<month-no>`th month in the year 20<2-digits>:

```
124 \newcommand*{\texlistyearmonthref}[2]{\texlist@yearmonthref#1#2\@nil}
125 \def\texlist@yearmonthref#1#2-#3\@nil{#1{20#2-\enmonthname{#3}}}
```

‘<path>’ will be ‘20<2-digits>-<month>’, and `<month>` will be the *English* name of the `<month-no>`th month of the year.

```
\texlanglistmonthref<month-cmd><list-ref>{<2-digits>-<month-no>}
```

will generate `\<list-ref>{<path>}{<month>}` where `<month>` is determined from `<month-no>` by `<month-cmd>`:

```
126 \newcommand*{\texlanglistmonthref}[3]{\texlanglistm@nthref#1#2#3\@nil}
127 \def\texlanglistm@nthref#1#2#3-#4\@nil{%
128     #2{20#3-\enmonthname{#4}}{#1{#4}}}
```

`\detexlistmonthref<list-ref>{<2-digits>-<month-no>}` now could be used for `<list-ref>{<path>}{<month>}` German `<month>` ...

```
129 \newcommand*{\detexlistmonthref}{\texlanglistmonthref\demonthname}
```

... as could be `\entexlistmonthref<list-ref>{<2-digits>-<month-no>}` for *English* `<month>` ...

```
130 \newcommand*{\entexlistmonthref}{\texlanglistmonthref\enmonthname}
```

With proper use of `langcode` however,

```
\texlistmonthref<list-ref>{<2-digits>-<month-no>}
```

automatically chooses between English and German `<month>` (according to intention ...):

```
131 \newcommand*{\texlistmonthref}{\texlanglistmonthref\monthname}
```

9.3 CTAN Announcements

`\ctanannref{⟨id⟩}{⟨text⟩}` makes `⟨text⟩` a link to the DANTE web page displaying a CTAN announcement. You find `⟨id⟩` by searching

`https://lists.dante.de/pipermail/ctan-ann/`

and then reading the URL. `⟨id⟩` is composed as

`⟨year⟩-⟨month⟩/⟨6-digits⟩.html`

where `⟨year⟩` consists of 4 digits and `⟨month⟩` is an *English* month name:

```
132 \newcommand*\ctanannref{[1]{%
133     \httpsref{lists.dante.de/pipermail/ctan-ann/#1}}
```

`\ctanannpref{⟨id-code⟩}{⟨text⟩}` is a variant of `\ctanannref` where in place of `⟨id⟩` you only type the third and fourth digit of the year (`⟨2-digits⟩`), then a ‘-’, then the (arabic) number `⟨month-no⟩` of the month (cf. Section 9.2 so far), then another ‘-’, and then the actual internal identifier `⟨running-no⟩` (a number of six digits preceding ‘.html’ of the URL). I.e., ‘`⟨id-code⟩`’ is ‘`⟨2-digits⟩-⟨month-no⟩-⟨running-no⟩`’.

```
134 \newcommand*\ctanannpref{[1]{%
135     \ctanannref{20\TL@piper@parse#1/.html}}           %% ‘20’ 2012/12/08
```

`\ctanannyearmonthref{⟨2-digits⟩-⟨month-no⟩}`

generates `\ctanannref{⟨path⟩}` from ‘`⟨2-digits⟩-⟨month-no⟩`’—`⟨path⟩` as in Section 9.2 ...

```
136 \newcommand*\ctanannyearmonthref{\texlistyearmonthref\ctanannref}
```

`\ctanannmonthref{⟨2-digits⟩-⟨month-no⟩}`

generates `\ctanannref{⟨path⟩}{⟨month⟩}` where `⟨month⟩` obeys `\langcode` ...

```
137 \newcommand*\ctanannmonthref{\texlistmonthref\ctanannref}
```

9.4 TUG

`\tugref{⟨path⟩}{⟨text⟩}` makes `⟨text⟩` a link to `⟨path⟩` on domain `tug.org`:

```
138 \newcommand*\tugref{\httpbaseref{tug.org}}
```

9.4.1 texhax

`\texhaxref{⟨id⟩}{⟨text⟩}` makes `⟨text⟩` a link to the TUG web page displaying a texhax posting. You find `⟨id⟩` by searching `tug.org/pipermail/texhax/` and then reading the URL. `⟨id⟩` is composed as `⟨year⟩-⟨month⟩/⟨6-digits⟩.html`.

```
139 \newcommand*{\texhaxref}[1]{\tugref{pipermail/texhax/#1}}
```

`\THref{⟨id⟩}` saves you from choosing `⟨text⟩` and uses `texhax` instead.

```
140 \newcommand*{\THref}[1]{\texhaxref{#1}{texhax}}
```

(It was `\prg{texhax}` in `blog.sty`, to have something logo-like, without a good idea how to implement it.)

`\texhaxpref{⟨id-code⟩}{⟨text⟩}` is a variant of `\texhaxref` where in place of `⟨id⟩` you only type the third and fourth digit of the year, then a `-`, then the (arabic) number of the month, then another `-`, and then the actual internal identifier (a number of six digits preceding `.html` of the URL). I made this macro because I prefer typing to copying from the URL.

```
141 \newcommand*{\texhaxpref}[1]{%           %% 2010/09/07
142 \texhaxref{20\TL@piper@parse#1/.html}} %% 2011/05/03
```

TODO: `\texhaxPref#1` searches list of offsets to determine year/month from id
...

`\texhaxyearmonthref{⟨2-digits⟩-⟨month-no⟩}`

generates `\texhaxref{⟨path⟩}` from ‘`⟨2-digits⟩-⟨month-no⟩`’—`⟨path⟩` as in Section 9.2 ...

```
143 \newcommand*{\texhaxyearmonthref}{\texlistyearmonthref\texhaxref}
```

`\texhaxmonthref{⟨2-digits⟩-⟨month-no⟩}`

generates `\texhaxref{⟨path⟩}{⟨month⟩}` where `⟨month⟩` obeys `\langcode` ...

```
144 \newcommand*{\texhaxmonthref}{\texlistmonthref\texhaxref}
```

9.4.2 Other

`\tugbartref{tb⟨vol⟩-⟨issue⟩/⟨filename-base⟩}{⟨text⟩}` makes `⟨text⟩` a link to the TUGboat article `⟨filename-base⟩.pdf` in vol. `⟨vol⟩` and issue `⟨issue⟩`:

```
145 % \newcommand*{\tugbartref}[1]{\tugref{TUGboat/Articles/#1.pdf}}
146 \newcommand*{\tugbartref}[1]{\tugref{TUGboat/#1.pdf}}
```

`\tugiref{⟨anchor⟩}{⟨text⟩}` makes `⟨text⟩` a link to an `⟨anchor⟩` on the TUG web page entitled ‘TeX Resources on the Web’ (e.g., ‘Web Projects’):

```
147 \newcommand*{\tugiref}[1]{\tugref{interest.html\##1}}
```

It was `\TUGIref` until v0.6, we keep this for compatibility (deprecated):

```
148 \newcommand*{\TUGIref}{} \let\TUGIref\tugiref
```

9.5 UK FAQ

`\ukfaqref{<label>}{<text>}` makes `<text>` a link to the UK T_EX FAQ page with “label” = `<label>`:

```
149 \newcommand*{\ukfaqref}[1]{\httpref{%
150     www.tex.ac.uk/cgi-bin/texfaq2html?label=#1}}
```

9.6 Wikibooks

`\wikilangbooksref{<language-code>}{<book>/<subject>}{<text>}`

```
151 \newcommand*{\wikilangbooksref}[1]{%           %% ‘lang’ 2012/01/06
152     \httpbaseref{#1.wikibooks.org/wiki}}
```

`\latexwikibookref{<subject>}{<text>}` refers to the (English) L^AT_EX Wiki-book:

```
153 \newcommand*{\latexwikibookref}[1]{\wikilangbooksref{en}{LaTeX/#1}}
```

The German L^AT_EX-Kompedium is somewhat difficult, I leave it for now ...

10 Leaving and Version HISTORY

```
154 \endinput
```

VERSION HISTORY

```
155 v0.1    2011/01/24  new file, code from blog.sty v0.3
156 v0.2    2011/01/27  \urlfoot, \NormalHTTTPref, \foothttppurlref,
157                    "outline" adjusted;
158                    more consistent use of \newcommand and
159                    \@ifdefinable (TODO: guarded \let)
160 v0.3    2011/02/10  [blog]; \urlpkgfoot
161 v0.4    2011/04/27  doc. \tugbartref\ corrected
162                    2011/04/30  shortened link in \tugbartref
163                    2011/05/03  \TL@piper@parse, tried \ctanannref
164                    2011/05/13  reworking Wikipedia, arbitrary languages
165                    2011/06/27  doc.: \acro; \httpsref, \ctanannref
166                    2011/07/23  doc.: typo \acro{TUG}, ‘Almost all’, page breaks;
167                    \Wikidisambref: different order of arg.s
168                    2011/08/18  doc.: \acro with UK; wikibooks
169                    2011/08/27  doc. \acro with URL and PDF;
170                    more doc and code changes for https
171  uploaded with MOREHYPE r0.4 (not touched by r0.41)
172 v0.41    2011/09/03  doc.: more specific on \urluml/Wikipedia
173                    2011/10/06  \mirrorctanref, \tugctanfileref,
174                    \mirrorctanfileref, \ltxcontrib
175                    2011/10/10  doc. formatting of previous
176  uploaded with MOREHYPE r0.5(1)
177 v0.5    2011/10/19  doc. fix LaTeX Wikibook
```



```

178          2011/10/20 \urlfmt, \filenamefmt and \pkgnamefmt
179                    changed and moved, modified doc. on them,
180                    doc. uses \URL
181          2011/10/21 re-order CTAN, \pagebreak's, \ctanref and
182                    choice for it, doc. modified; rm. \ithttpref
183  uploaded with MOREHYPE r0.52
184  v0.6    2012/01/06 \wikilangref etc., \wikiref etc. depend on
185                    \langcode
186          2012/01/11 removed old comments for Wikipedia; (C)
187          2012/03/09 "URL bases" (\httpbaseref etc.), applied;
188                    \bytopicref uses \mirrorctanref
189          2012/03/12 fixed \texhaxref
190          2012/04/09 \ctanorgbaseref, \ctanpkgaref
191          2012/04/10 makedoc link works!
192          2012/05/13 example for \wikilangref corrected
193  uploaded with MOREHYPE r0.6
194  v0.7    2012/07/23 doc.: <text>
195          2012/08/05 \tugiref
196          2012/10/04 doc. wikibooks: ref
197          2012/10/24 ...monthref... requiring 'langcode.sty', moving
198                    links to mailing list pages from 'texblog.fdf'
199                    here; doc.: \pagebreak s, wikibooks: <book>...,
200                    corr. args, \wikiref refers to 'langcode.sty',
201                    'ref', using \qtdcode (new in 'makedoc.cfg')
202          2012/11/08 doc.: Jim corr.
203          2012/11/27 \ctanpkgstyref from 'texblog.fdf'
204          2012/11/28 [[...|...]]
205  uploaded with MOREHYPE r0.7
206  v0.7a   2012/12/01 link fix "Piped link"
207          -> r0.7a
208  v0.7b   2012/12/06 there again: blogexec -> markblog, above entry ...
209          -> r0.7b
210  v0.71   2012/12/08 \ctanannpref like \texhaxpref
211          -> r0.71
212

```