

The `alphalph` package

Heiko Oberdiek

<oberdiek@uni-freiburg.de>

2007/09/09 v2.0

Abstract

The package provides methods to represent numbers with a limited set of symbols. Both L^AT_EX and plain-T_EXare supported.

Contents

1 Documentation	2
1.1 Introduction	2
1.2 Use cases	2
1.2.1 Number system based on symbols	2
1.2.2 Wrap symbols around	3
1.2.3 Multiple symbols	3
1.3 Glossary	4
1.4 Package usage	4
1.5 User commands	4
1.6 Programmer commands	5
1.7 Design principles	5
1.7.1 Number presentation commands	5
1.7.2 General usability	6
2 Implementation	6
2.1 Begin of package	6
2.2 Catcodes	7
2.3 Package loading	8
2.4 ε -T _E X detection	8
2.5 Help macros	8
2.6 Symbol provider	9
2.6.1 Alphabet	9
2.7 Finding number of symbols	10
2.8 Methods	12
2.8.1 Common methods	12
2.8.2 Method ‘alph’	12
2.8.3 Method ‘wrap’	13
2.8.4 Method ‘mult’	13
2.9 User interface	14
3 Test	15
3.1 Catcode checks for loading	15
4 Macro tests	17

5 Installation	21
5.1 Download	21
5.2 Bundle installation	21
5.3 Package installation	21
5.4 Refresh file name databases	21
5.5 Some details for the interested	22
6 History	22
[1999/03/19 v0.1]	22
[1999/04/12 v1.0]	22
[1999/04/13 v1.1]	22
[1999/06/26 v1.2]	23
[2006/02/20 v1.3]	23
[2006/05/30 v1.4]	23
[2007/04/11 v1.5]	23
[2007/09/09 v2.0]	23
7 Index	23

1 Documentation

1.1 Introduction

L^AT_EX counter can be represented in different ways by using presentation commands:

```
\arabic, \roman, \Roman,  
 \alph, \Alph, \fnsymbol
```

The ranges of supported counter values are more or less restricted. Only `\arabic` can be used with any counter value T_EX supports.

Presentation command	Supported domain	Ignored values	Error message “Counter too large”
<code>\arabic</code>	-MAX..MAX		
<code>\roman, \Roman</code>	1..MAX	MAX..0	
<code>\alph, \Alph</code>	1..26	0	MAX..-1, 27..MAX
<code>\fnsymbol</code>	1..9	0	-MAX..-1, 10..MAX

MAX = 2147483647

Ordinal numbers are often used in documents: numbering of chapters, sections, figures, footnotes and so on. The layouter chooses `\Alph` for chapter numbers and `\fnsymbol` for footnotes. But what can be done if there are more than 26 chapters or more than 10 footnotes? This package `alphalph` allows to define new presentation commands. They rely on a existing command and define presentations for values greater the limits. Three different methods are provided by the package. In the following use cases they are presented.

1.2 Use cases

1.2.1 Number system based on symbols

Asume you are writing a book and your lecturer demands that chapter numbers must be letters. But you have already 30 chapters and you have only 26 letters?

In the decimal system the situation would be clear. If you run out of digits, you are using more digits to represent a number. This method can be also be used for letters. After chapter 26 with Z we us AA, AB, AC, and AD for the remaining chapters.

Happily this package already defines this presentation command:

```
\usepackage{alphalph}
\renewcommand*{\thechapter}{%
    \AlphAlpha{\value{chapter}}%
}
```

`\AlphAlpha` generates: A, B, C, ..., Z, AA, AB, ...

The other presentation command is `\alphalph` for lowercase letters.

1.2.2 Wrap symbols around

Nine footnote symbols are quite a few. Too soon the symbols are consumed and L^AT_EX complains with the error “Counter too large”. However, it could be acceptable to start again with the symbols from the beginning, especially if there are less than nine symbols on a page. This could be achieved by a counter reset. But finding the right place can be difficult or needs manual actions. Also a unique counter value can be desirable (e.g. for generating unique anchor/link names). Package `alphalph` allows you to define a macro that implements a “wrap around”, but letting the value of the counter untouched:

```
\usepackage{alphalph}
\makeatletter
\newalphalph{\fnsymbolwrap}[wrap]{\@fnsymbol}{}
\makeatother
\renewcommand*{\thefootnote}{%
    \fnsymbolwrap{\value{footnote}}%
}
```

`\fnsymbolwrap` generates: * (1), † (2), ‡ (3), ..., §§ (9), * (10), † 11, ...

1.2.3 Multiple symbols

L^AT_EX’s standard set of footnote symbols contains doubled symbols at the higher positions. Could this principle be generalized? Yes, but first we need a clean footnote symbol list without doubled entries, example:

```
\usepackage{alphalph}
\makeatletter
\newcommand*{\fnsymbolsingle}[1]{%
    \ensuremath{%
        \ifcase#1%
            \or *%
            \or \dagger%
            \or \ddagger%
            \or \mathsection%
            \or \mathparagraph%
        \else
            \text{@ctrerr}%
        \fi
    }%
}
\makeatother
\newalphalph{\fnsymbolmult}[mult]{\fnsymbolsingle}{}
\renewcommand*{\thefootnote}{%
    \fnsymbolmult{\value{footnote}}%
}
```

The own definition of `\fnsymbolsingle` has the advantage that this list can easily modified. Otherwise you can use `\@fnsymbol` directly, because it uses the same first five symbols.

```
\usepackage{alphalph}
\makeatletter
\newalphalph{\fnsymbolmult}[mult]{\@fnsymbol}{5}
```

```

\makeatother
\renewcommand*{\thefootnote}{%
  \fnsymbolmult{\value{footnote}}%
}

\fnsymbolmult generates: * (1), † (2), ‡ (3), § (4), ¶ (5), ** (6), ..., **** 16,
†††† 17, ...

```

The same method can also be used for the chapter problem in the first discussed use case:

```

\usepackage{alphalph}
\makeatletter
\newalphalph{\AlphMult}[mult]{\@Alph}{26}
\makeatother
\renewcommand*{\chapter}{%
  \AlphMult{\value{chapter}}%
}

```

\AlphMult then generates AA, BB, CC, and DD for chapters 27–30.

1.3 Glossary

Counter presentation command is a macro that expects a L^AT_EX counter name as argument. Numbers cannot be used. Examples: \arabic, \alph, \fnsymbol.

Number presentation command is a macro that expects a number as argument. A number is anything that T_EX accepts as number including \value. Examples: \alphalph, \AlphAlpha, \alphalph@alph

However, \alph or \fnsymbol are not number presentation commands because they expect a counter name as argument. Happily L^AT_EX counter presentation commands internally uses number presentation commands with the same name, but prefixed by ‘@’. Thus \@alph, \@fnsymbol are number presentation commands.

Symbols provider is a command that can be used to get a list of symbols. For example, \@Alph provides the 26 uppercase letters from ‘A’ to ‘Z’. Basically a symbol provider is a number presentation command, usually with a limited range.

Number of symbols is the number of the last symbol slot of a symbol provider. Thus \@Alph generates 26 symbols, \@fnsymbol provides 9 symbols.

1.4 Package usage

The package alphalph can be used with both plain-T_EX and L^AT_EX:

plain-T_EX: \input alphalph.sty

L^AT_EX 2_<: \usepackage{alphalph}
There aren’t any options.

1.5 User commands

\AlphAlpha {\langle number\rangle}
\alphalph {\langle number\rangle}

Both macros are number presentation commands that expects a number as argument. L^AT_EX counters are used with \value.

The macros represents a number by letters. First single letters A..Z are used, then two letters AA..ZZ, three letters AAA...ZZZ, ... follow.

Macro `\AlphAlph` uses uppercase letters, `\alphalph` generates the lowercase variant.

$\langle number \rangle$	<code>\AlphAlph{\langle number \rangle}</code>	<code>\alphalph{\langle number \rangle}</code>
1	A	a
2	B	b
26	Z	z
27	AA	aa
30	AD	ad
2000	BXX	bxx
3752127	HELLO	hello
10786572	WORLD	world
2147483647	FXSHRXW	fxshrxw

```
\newalphalph {\langle cmd \rangle} [⟨ method ⟩] {⟨ symbols provider ⟩} {⟨ number of symbols ⟩}
```

Macro `\newalphalph` defines $\langle cmd \rangle$ as new number presentation command. Like `\newcommand` an error is thrown, if macro $\langle cmd \rangle$ already exists.

The $\langle method \rangle$ is one of `alph`, `wrap`, or `mult`. The default is `alph`.

As symbol provider a number presentation command can be used, e.g. `\@fnsymbol`, `\@Alph`, or `\alphalph@\alph`.

The last argument is the number of symbols. If the argument is empty, then `\newalphalph` tries to find this number itself. L^AT_EX's number presentation commands throw an error message, if the number is too large. This error message is put in a macro `\@ctrerr`. Thus `\newalphalph` calls the symbol provider and tests a number by typesetting it in a temporary box. The error macro `\@ctrerr` is caught, it proofs that the number is not supported. Also if the width of the result is zero the number is considered as unavailable.

The empty argument is useful for potentially variable lists. However if the end cannot be detected, then the number of symbols must be given. This is also a lot faster. Therefore don't let the argument empty without reason.

1.6 Programmer commands

```
\alphalph@Alph {\langle number \rangle}
\alphalph@alph {\langle number \rangle}
```

They are basically the same as `\@Alph` and `\@alph`. Some languages of package `babel` redefine L^AT_EX's macros to include some font setup that breaks expandability. Therefore `\AlphAlph` and `\alphalph` are based on `\alphalph@Alph` and `\alphalph@alph` to get the letters. The behaviour of these symbol providers for numbers outside the range 1..26 is undefined.

1.7 Design principles

1.7.1 Number presentation commands

All number presentation commands that this package defines (including `\alphalph` and `\AlphAlph`) have the following properties:

- They are fully expandable. This means that they can safely
 - be written to a file,
 - used in moving arguments (L^AT_EX: they are *robust*),
 - used in a `\csname-\endcsname` pair.

- If the argument is zero or negative, the commands expand to nothing like `\romannumeral`.
- The argument is a `\TeX` number. Anything that would be accepted by `\number` is a valid argument:
 - explicite constants,
 - macros that expand to a number,
 - count registers, `\TeX` counter can used via `\value`, e.g.:
 `\alphan{value{page}}`
 - ...
- ε -`\TeX`'s numeric expressions are supported, if ε -`\TeX` is available. Then `\numexpr` is applied to the argument. Package `\calc`'s expressions are not supported. That would violate the expandibility.

1.7.2 General usability

`\TeX` format: The package does not depend on `\TeX`, it can also be used by plain-`\TeX`, for example.

ε -`\TeX`: ε -`\TeX` is supported, the macros are shorter and faster. But ε -`\TeX`'s extensions are not requirements. Without ε -`\TeX`, just the implementation changes. The properties remain unchanged.

2 Implementation

2.1 Begin of package

1 `(*package)`

Reload check, especially if the package is not used with `\TeX`.

```

2 \begingroup
3   \catcode44 12 % ,
4   \catcode45 12 % -
5   \catcode46 12 % .
6   \catcode58 12 % :
7   \catcode64 11 % @
8   \expandafter\let\expandafter\x\csname ver@alphan{.sty}\endcsname
9   \ifcase 0%
10     \ifx\x\relax % plain
11     \else
12       \ifx\x\empty % \TeX
13         \else
14           1%
15         \fi
16       \fi
17     \else
18       \catcode35 6 % #
19       \catcode123 1 % {
20       \catcode125 2 % }
21       \expandafter\ifx\x\csname PackageInfo\endcsname\relax
22         \def\x#1#2{%
23           \immediate\write-1{Package #1 Info: #2.}%
24         }%
25       \else
26         \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27       \fi
28       \x{alphan}{The package is already loaded}%
29     \endgroup
30   \expandafter\endinput

```

```

31   \fi
32 \endgroup
Package identification:
33 \begingroup
34   \catcode35 6 % #
35   \catcode40 12 % (
36   \catcode41 12 % )
37   \catcode44 12 % ,
38   \catcode45 12 % -
39   \catcode46 12 % .
40   \catcode47 12 % /
41   \catcode58 12 % :
42   \catcode64 11 % @
43   \catcode123 1 % {
44   \catcode125 2 % }
45 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
46     \def\x#1#2#3[#4]{\endgroup
47       \immediate\write-1{Package: #3 #4}%
48       \xdef#1[#4]%
49     }%
50 \else
51   \def\x#1#2[#3]{\endgroup
52     #2[#3]%
53     \ifx#1\relax
54       \xdef#1[#3]%
55     \fi
56   }%
57 \fi
58 \expandafter\x\csname ver@alphalph.sty\endcsname
59 \ProvidesPackage{alphalph}%
60 [2007/09/09 v2.0 Converting numbers to letters (HO)]

```

2.2 Catcodes

```

61 \begingroup
62   \catcode123 1 % {
63   \catcode125 2 % }
64 \def\x{\endgroup
65   \expandafter\edef\csname A1Ph@AtEnd\endcsname{%
66     \catcode35 \the\catcode35\relax
67     \catcode64 \the\catcode64\relax
68     \catcode123 \the\catcode123\relax
69     \catcode125 \the\catcode125\relax
70   }%
71 }%
72 \x
73 \catcode35 6 % #
74 \catcode64 11 % @
75 \catcode123 1 % {
76 \catcode125 2 % }
77 \def\TMP@EnsureCode#1#2{%
78   \edef\A1Ph@AtEnd{%
79     \A1Ph@AtEnd
80     \catcode#1 \the\catcode#1\relax
81   }%
82   \catcode#1 #2\relax
83 }
84 \TMP@EnsureCode{33}{12}%
85 \TMP@EnsureCode{39}{12}%
86 \TMP@EnsureCode{40}{12}%
87 \TMP@EnsureCode{41}{12}%
88 \TMP@EnsureCode{43}{12}%
89 \TMP@EnsureCode{44}{12}%

```

```

90 \TMP@EnsureCode{46}{12}%
91 \TMP@EnsureCode{47}{12}%
92 \TMP@EnsureCode{59}{12}%
93 \TMP@EnsureCode{60}{12}%
94 \TMP@EnsureCode{61}{12}%
95 \TMP@EnsureCode{62}{12}%
96 \TMP@EnsureCode{91}{12}%
97 \TMP@EnsureCode{93}{12}%
98 \TMP@EnsureCode{96}{12}%
99 \TMP@EnsureCode{124}{12}%

```

2.3 Package loading

```

100 \begingroup\expandafter\expandafter\expandafter\endgroup
101 \expandafter\ifx\csname RequirePackage\endcsname\relax
102   \input infwarerr.sty\relax
103   \input intcalc.sty\relax
104 \else
105   \RequirePackage{infwarerr}[2007/09/09]%
106   \RequirePackage{intcalc}[2007/09/09]%
107 \fi

```

2.4 ε -**T_EX** detection

```

108 \begingroup\expandafter\expandafter\expandafter\endgroup
109 \expandafter\ifx\csname numexpr\endcsname\relax
110   \catcode124=9 % '!': ignore
111   \catcode43=14 % '+': comment
112 \else
113   \catcode124=14 % '!': comment
114   \catcode43=9 % '+': ignore
115 \fi

```

2.5 Help macros

```

\AlPh@Error
116 \def\AlPh@Error#1{%
117   \begingroup
118     \escapechar=92 % backslash
119     \@PackageError{alphan}{#1}\@ehc
120   \endgroup
121 }

\AlPh@IfDefinable
122 \begingroup\expandafter\expandafter\expandafter\endgroup
123 \expandafter\ifx\csname @ifdefinable\endcsname\relax
124   \def\AlPh@IfDefinable#1#2{%
125     \ifcase\ifx#1\undefined\else\ifx#1\relax\else1\fi\fi0 %
126     #2%
127   \else
128     \AlPh@Error{%
129       Command \string#1 already defined%
130     }%
131   \fi
132 }
133 \else

\AlPh@IfDefinable
134 \let\AlPh@IfDefinable\@ifdefinable
135 \fi

```

\@ReturnAfterElseFi The following commands moves the ‘then’ and ‘else’ part respectively behind the \if-construct. This prevents a too deep \if-nesting and so a T_EX capacity error because of a limited input stack size. I use this trick in several packages, so I don’t prefix these internal commands in order not to have the same macros with different names. (It saves memory.)

```
136 \long\def \@ReturnAfterElseFi#1\else#2\fi{\fi#1}
137 \long\def \@ReturnAfterFi#1\fi{\fi#1}
```

\@gobblefour L_AT_EX defines commands for eating arguments. Define \@gobblefour if it is not defined (plain-T_EX).

```
138 \expandafter\ifx\csname @gobblefour\endcsname\relax
139   \long\def \@gobblefour#1#2#3#4{}%
140 \fi
```

AlPh@IfOptArg

```
141 \begingroup\expandafter\expandafter\expandafter\endgroup
142 \expandafter\ifx\csname kernel@ifnextchar\endcsname\relax
143   \begingroup\expandafter\expandafter\expandafter\endgroup
144   \expandafter\ifx\csname @ifnextchar\endcsname\relax
145     \def\AlPh@IfOptArg#1#2{%
146       \def\AlPh@TempA{#1}%
147       \def\AlPh@TempB{#2}%
148       \futurelet\AlPh@Token\AlPh@IfOptArgNext
149     }%
150   \let\AlPh@BracketLeft=[%
151   \def\AlPh@IfOptArgNext{%
152     \ifx\AlPh@Token\AlPh@BracketLeft
153       \expandafter\AlPh@TempA
154     \else
155       \expandafter\AlPh@TempB
156     \fi
157   }%
158   \else
159     \def\AlPh@IfOptArg{\@ifnextchar[]{}}
160   \fi
161 \else
162   \def\AlPh@IfOptArg{\kernel@ifnextchar[]{}}
163 \fi
```

2.6 Symbol provider

2.6.1 Alphabet

The output of \alphalph and \AlphAlpha should be usable as part of command names (see \@namedef, \csname, ...). Unhappily some languages of package babel redefine L_AT_EX’s \@alph and \@Alph in a manner that they cannot be used in expandable context any more. Therefore package alphalph provides its own commands.

\alphalph@Alph The two commands \AlPh@Alph and \AlPh@alph convert a number into a letter (uppercase and lowercase respectively). The character @ is used as an error symbol, if the number isn’t in the range of 1 until 26. Here we need no space after the number #1, because the error symbol @ for the zero case stops scanning the number. This error symbol should not appear anywhere (except for bugs).

```
164 \def\alphalph@Alph#1{%
165   \ifcase#1%
166     @@
167     \or A\or B\or C\or D\or E\or F\or G\or H\or I\or J\or K\or L\or M%
168     \or N\or O\or P\or Q\or R\or S\or T\or U\or V\or W\or X\or Y\or Z%
169   \else
170     \AlPh@ctrerr
```

```

171      @%
172      \fi
173 }
174 \def\alphalph{\alpha#1{%
175   \ifcase#1%
176     @%
177     \or a\or b\or c\or d\or e\or f\or g\or h\or i\or j\or k\or l\or m%
178     \or n\or o\or p\or q\or r\or s\or t\or u\or v\or w\or x\or y\or z%
179   \else
180     \AlPh@ctrerr
181     @%
182   \fi
183 }

```

\AlPh@ctrerr Macro \AlPh@ctrerr is used as hook for the algorithm to get the available number of symbols.

```
184 \def\AlPh@ctrerr{}
```

2.7 Finding number of symbols

\AlPh@GetNumberOfSymbols #1: symbols provider

```

185 \def\AlPh@GetNumberOfSymbols#1{%
186   \AlPh@TestNumber1!{#1}%
187   \ifAlPh@Unavailable
188     \def\AlPh@Number{0}%
189     \AlPh@Error{No symbols found}%
190   \else
191     \def\AlPh@Number{1}%
192     \AlPh@ExpSearch2!{#1}%
193   \fi
194 }
```

\ifAlPh@Unavailable

```

195 \newif\ifAlPh@Unavailable
196 \def\AlPh@Unavailabletrue{%
197   \global\let\ifAlPh@Unavailable\iftrue
198 }
199 \def\AlPh@Unavailablefalse{%
200   \global\let\ifAlPh@Unavailable\iffalse
201 }
```

\AlPh@TestNumber #1: number to be tested

#2: symbols provider

```

202 \def\AlPh@TestNumber#1!#2{%
203   \AlPh@Unavailablefalse
204   \begingroup
205     \setbox0=\hbox{%
206       \begingroup % color
207         \let\@ctrerr\AlPh@Unavailabletrue
208         \let\AlPh@ctrerr\AlPh@Unavailabletrue
209         #2!{#1}%
210       \endgroup
211     }%
212     \ifdim\wd0=0pt %
213       \AlPh@Unavailabletrue
214     \fi
215   \endgroup
216 }
```

\AlPh@ExpSearch #1: number to be tested

#2: symbols provider

```

217 \def\AlPh@ExpSearch#1!#2{%
218   \let\AlPh@Next\relax
219   \AlPh@TestNumber#1!{#2}%
220   \ifAlPh@Unavailable
221     \expandafter\AlPh@BinSearch\AlPh@Number!#1!{#2}%
222   \else
223     \def\AlPh@Number{#1}%
224     \ifnum#1>1073741823 %
225       \AlPh@TestNumber2147483647!{#2}%
226       \ifAlPh@Unavailable
227         \AlPh@BinSearch#1!2147483647!{#2}%
228       \else
229         \def\AlPh@Number{0}%
230         \AlPh@Error{%
231           Maximal symbol number not found%
232         }%
233       \fi
234     \else
235       \def\AlPh@Next{%
236         \expandafter\AlPh@ExpSearch\number\intcalcShl{#1}!{#2}%
237       }%
238     \fi
239   \fi
240   \AlPh@Next
241 }

\AlPh@BinSearch #1: available number
#2: unavailable number, #2 > #1
#3: symbols provider
242 \def\AlPh@BinSearch#1!#2!#3{%
243   \expandafter\AlPh@ProcessBinSearch
244   \number\intcalcShr{\intcalcAdd{#1}{#2}}!%
245   #1!#2!{#3}%
246 }

\AlPh@ProcessBinSearch #1: number to be tested, #2 ≤ #1 ≤ #3
#2: available number
#3: unavailable number
#4: symbols provider
247 \def\AlPh@ProcessBinSearch#1!#2!#3!#4{%
248   \let\AlPh@Next\relax
249   \ifnum#1>#2 %
250     \ifnum#1<#3 %
251       \AlPh@TestNumber#1!{#4}%
252       \ifAlPh@Unavailable
253         \def\AlPh@Next{%
254           \AlPh@BinSearch#2!#1!{#4}%
255         }%
256       \else
257         \def\AlPh@Next{%
258           \AlPh@BinSearch#1!#3!{#4}%
259         }%
260       \fi
261     \else
262       \def\AlPh@Number{#2}%
263     \fi
264   \else
265     \def\AlPh@Number{#2}%
266   \fi
267   \AlPh@Next
268 }

```

2.8 Methods

The names of method macros start with `\AlPh@Method`. These macros do the main job in converting a number to its representation. A method command is called with three arguments. The first argument is the number of symbols. The second argument is the basic macro for converting a number with limited number range. The last parameter is the number that needs converting.

2.8.1 Common methods

```
\AlPh@CheckPositive #1: number to be checked #2: continuation macro
#3: number of symbols (hidden here)
#4: symbol provider (hidden here)
269 \def\AlPh@CheckPositive#1!#2{%
270   \ifnum#1<1 %
271     \expandafter\gobblefour
272   \fi
273   #2{#1}%
274 }
```

2.8.2 Method ‘alph’

```
\AlPh@Method@alph #1: number of symbols
#2: symbols provider
#3: number to be converted
275 \def\AlPh@Method@alph#1#2#3{%
276   \expandafter\AlPh@CheckPositive
277 |   \number#3!%
278 +   \the\numexpr#3!%
279   \AlPh@ProcessAlph
280   {#1}-{#2}%
281 }

\AlPh@ProcessAlph #1: current number
#2: number of symbols
#3: symbols provider
282 \def\AlPh@ProcessAlph#1#2#3{%
283   \ifnum#1>#2 %
284     \@ReturnAfterElseFi{%
285       \expandafter\AlPh@StepAlph\number
286       \intcalcInc{%
287         \intcalcMod{\intcalcDec{#1}}{#2}%
288       }%
289       \expandafter!\number
290       \intcalcDiv{\intcalcDec{#1}}{#2}%
291       !{#2}{#3}%
292     }%
293   \else
294     \@ReturnAfterFi{%
295       #3{#1}%
296     }%
297   \fi
298 }

\AlPh@StepAlph #1: current last digit
#2: new current number
#3: number of symbols
#4: symbols provider
299 \def\AlPh@StepAlph#1!#2!#3#4{%
300   \AlPh@ProcessAlph{#2}{#3}{#4}%
301   #4{#1}%
302 }
```

2.8.3 Method ‘wrap’

```
\AlPh@Method@wrap #1: number of symbols
#2: symbols provider
#3: number to be converted
303 \def\AlPh@Method@wrap#1#2#3{%
304   \expandafter\AlPh@CheckPositive
305 |   \number#3!%
306 +   \the\numexpr#3!%
307   \AlPh@ProcessWrap
308   {#1}{#2}%
309 }

\AlPh@ProcessWrap #1: number to be converted
#2: number of symbols
#3: symbols provider
310 \def\AlPh@ProcessWrap#1#2#3{%
311   \ifnum#1>#2 %
312     \@ReturnAfterElseFi{%
313       \expandafter\AlPh@StepWrap\number
314       \intcalcInc{\intcalcMod{\intcalcDec{#1}}{#2}}%
315       !{#3}%
316     }%
317   \else
318     \@ReturnAfterFi{%
319       #3{#1}%
320     }%
321   \fi
322 }

\AlPh@StepWrap #1: final number
#2: symbols provider
323 \def\AlPh@StepWrap#1!#2{%
324   #2{#1}%
325 }
```

2.8.4 Method ‘mult’

After the number of symbols is exhausted, repetitions of the symbol are used.

$$\begin{aligned} x &:= \text{number to be converted} \\ n &:= \text{number of symbols} \\ r &:= \text{repetition length} \\ s &:= \text{symbol slot} \\ r &= ((x - 1) \div n) + 1 \\ s &= ((x - 1) \mod n) + 1 \end{aligned}$$

```
\AlPh@Method@mult #1: number of symbols
#2: symbols provider
#3: number to be converted
326 \def\AlPh@Method@mult#1#2#3{%
327   \expandafter\AlPh@CheckPositive
328 |   \number#3!%
329 +   \the\numexpr#3!%
330   \AlPh@ProcessMult
331   {#1}{#2}%
332 }
```

```

\AlPh@ProcessMult #1: number to be converted
#2: number of symbols
#3: symbols provider
333 \def\AlPh@ProcessMult#1#2#3{%
334   \ifnum#1>#2 %
335     \c@ReturnAfterElseFi{%
336       \expandafter\AlPh@StepMult\romannumeral
337         \intcalcInc{\intcalcDiv{\intcalcDec{#1}}{#2}}%
338         000%
339       \expandafter!\number
340         \intcalcInc{\intcalcMod{\intcalcDec{#1}}{#2}}%
341         !{#3}%
342     }%
343   \else
344     \c@ReturnAfterFi{%
345       #3{#1}%
346     }%
347   \fi
348 }

\AlPh@StepMult #1#2: repetitions coded as list of character ‘m’
#3: symbol slot
#4: symbols provider
349 \def\AlPh@StepMult#1#2!#3!#4{%
350   \ifx\#2\%
351   \else
352     \c@ReturnAfterFi{%
353       \AlPh@StepMult#2!#3!{#4}%
354     }%
355   \fi
356   #4{#3}%
357 }

```

2.9 User interface

```

\newalphalph Macro \newalphalph had three arguments in versions below 2.0. For the new
method argument we use an optional argument an first position.
#1: cmd
[#2]: method name: alph (default), wrap, mult
hash-ok #3: symbols provider
#4: number of symbols
358 \AlPh@IfDefinable\newalphalph{%
359   \def\newalphalph#1{%
360     \AlPh@IfOptArg{%
361       \AlPh@newalphalph{#1}%
362     }{%
363       \AlPh@newalphalph{#1}[alph]%
364     }%
365   }%
366 }

\AlPh@newalphalph #1: cmd #2: method name
#3: symbols provider
#4: number of symbols
367 \def\AlPh@newalphalph#1[#2]#3#4{%
368   \begingroup\expandafter\expandafter\expandafter\endgroup
369   \expandafter\ifx\csname AlPh@Method@#2\endcsname\relax
370     \AlPh@Error{%
371       Unknown method %
372 |     '#2'%
373 +     '\detokenize{#2}'%

```

```

374      }%
375  \else
376    \ifx\#4\%
377      \AlPh@GetNumberOfSymbols{#3}%
378      \ifcase\AlPh@Number
379      \else
380        \begingroup
381          \escapechar=92 % backslash
382          \QPackageInfo{alphalph}{%
383            Number of symbols for \string#1 is \AlPh@Number
384          }%
385        \endgroup
386        \expandafter\AlPh@NewAlphAlph
387        \csname AlPh@Method@#2\expandafter\endcsname
388        \AlPh@Number!{#1}{#3}%
389      \fi
390    \else
391      \expandafter\AlPh@NewAlphAlph
392      \csname AlPh@Method@#2\expandafter\endcsname
393 |    \number#4!%
394 +    \the\numexpr#4!%
395      {#1}{#3}%
396    \fi
397  \fi
398 }%

```

\AlPh@NewAlphAlph #1: method macro
#2: number of symbols
#3: cmd
#4: symbols provider

```

399 \def\AlPh@NewAlphAlph#1#2!#3#4{%
400   \AlPh@IfDefinable#3{%
401     \ifnum#2>0 %
402       \def#3{#1{#2}{#4}}%
403     \else
404       \AlPh@Error{%
405         Definition of \string#3 failed,\MessageBreak
406         because number of symbols (#2) is not positive%
407       }%
408     \fi
409   }%
410 }

```

\AlphAlph

```

411 \newalphalph\AlphAlph\alphalph@Alph{26}

```

\alphalph

```

412 \newalphalph\alphalph\alphalph@alph{26}

413 \AlPh@AtEnd
414 
```

3 Test

3.1 Catcode checks for loading

```

415 <*test1>
416 \catcode`\f=1 %
417 \catcode`\j=2 %
418 \catcode`\#=6 %
419 \catcode`\@=11 %

```

```

420 \expandafter\ifx\csname count@\endcsname\relax
421   \countdef{count@}{255}%
422 \fi
423 \expandafter\ifx\csname @gobble\endcsname\relax
424   \long\def{@gobble#1}{}%
425 \fi
426 \expandafter\ifx\csname @firstofone\endcsname\relax
427   \long\def{@firstofone#1{#1}}%
428 \fi
429 \expandafter\ifx\csname loop\endcsname\relax
430   \expandafter{@firstofone}
431 \else
432   \expandafter@gobble
433 \fi
434 {%
435   \def{loop#1\repeat}{%
436     \def{body{#1}}{%
437       \iterate{%
438         }{%
439           \def{\iterate}{%
440             \body{%
441               \let{\next}{\iterate}%
442             \else{%
443               \let{\next}{\relax}%
444             \fi{%
445               \next{%
446             }{%
447               \let{\repeat}{\fi}%
448             }{%
449               \def{\RestoreCatcodes}{%
450                 \count@=0}%
451               \loop{%
452                 \edef{\RestoreCatcodes}{%
453                   \RestoreCatcodes{%
454                     \catcode{\the\count@=\the\catcode{\count@}\relax}%
455                   }{%
456                     \ifnum{\count@<255}%
457                       \advance{\count@}{1}%
458                     \repeat{%
459                       }{%
460                         \def{\RangeCatcodeInvalid#1#2}{%
461                           \count@=#1\relax}%
462                           \loop{%
463                             \catcode{\count@=15}%
464                             \ifnum{\count@<#2}\relax{%
465                               \advance{\count@}{1}%
466                               \repeat{%
467                                 }{%
468                               \expandafter\ifx\csname LoadCommand\endcsname\relax
469                                 \def{\LoadCommand}{\input alphalph.sty}\relax}%
470                               \fi{%
471                                 \def{\Test}{%
472                                   \RangeCatcodeInvalid{0}{47}%
473                                   \RangeCatcodeInvalid{58}{64}%
474                                   \RangeCatcodeInvalid{91}{96}%
475                                   \RangeCatcodeInvalid{123}{255}%
476                                   \catcode`@=12}%
477                                   \catcode`\|=0}%
478                                   \catcode`\{=1}%
479                                   \catcode`\}=2}%
480                                   \catcode`\#=6}%
481                                   \catcode`\[=12}%

```

```

482  \catcode`\]=12 %
483  \catcode`\%=14 %
484  \catcode`\ =10 %
485  \catcode`13=5 %
486  \LoadCommand
487  \RestoreCatcodes
488 }
489 \Test
490 \csname @@end\endcsname
491 \end
492 
```

4 Macro tests

```

493 <*test2>
494 \NeedsTeXFormat{LaTeX2e}
495 \nofiles
496 \documentclass{article}
497 <*noetex>
498 \makeatletter
499 \let\saved@numexpr\numexpr
500 \newcommand*{\DisableNumexpr}{%
501   \let\numexpr\@undefined
502 }
503 \newcommand*{\RestoreNumexpr}{%
504   \let\numexpr\saved@numexpr
505 }
506 \DisableNumexpr
507 
```

</noetex>

508 \usepackage{alphalph}[2007/09/09]

509 <noetex> \RestoreNumexpr

510 \usepackage{qstest}

511 \IncludeTests{*}

512 \LogTests{log}{*}{*}

513

514 \newcommand*{\TestCmd}[3]{%

515 \setbox0=\hbox{%

516 <noetex> \DisableNumexpr

517 \edef\TestString{\#1\#2}%

518 \expandafter\Expect\expandafter{\TestString}{#3}%

519 \edef\TestString{\#1\#2}%

520 \expandafter\Expect\expandafter{\TestString}{#3}%

521 }%

522 \Expect*{\the\wd0}{0.0pt}%

523 }

524

525 \makeatletter

526 \newalphalph{LaTeXAlphaAlpha}{\Alpha}{26}

527 \newalphalph{LaTeXalphaAlpha}{\alpha}{26}

528 \newalphalph{AlphaWrap}{wrap}{\alpha}{26}

529 \newalphalph{alphwrap}{wrap}{\alpha}{26}

530 \newalphalph{LaTeXAlphaWrap}{wrap}{\Alpha}{26}

531 \newalphalph{LaTeXalphwrap}{wrap}{\alpha}{26}

532 \def\LastSymbol#1{%

533 \ifx\\#1\\%

534 \else

535 \LastSymbol#1\@nil

536 \fi

537 }

538 \def\@LastSymbol#1#2\@nil{%

539 \ifx\\#2\\%

540 #1%

```

541 \else
542   \@LastSymbol#2\@nil
543 \fi
544 }
545 \makeatother
546 \newcommand*{\TestAlph}[2]{%
547   \uppercase{\TestCallCmd\AlphAlph{#2}}{#1}%
548   \lowercase{\TestCallCmd\alphalph{#2}}{#1}%
549   \uppercase{\TestCallCmd\LaTeXAlphAlph{#2}}{#1}%
550   \lowercase{\TestCallCmd\LaTeXalphalph{#2}}{#1}%
551   \edef\WrapString{\LastSymbol{#2}}%
552   \expandafter\TestAlphWrap\expandafter{\WrapString}{#1}%
553 }
554 \newcommand*{\TestAlphWrap}[2]{%
555   \uppercase{\TestCallCmd\AlphWrap{#1}}{#2}%
556   \lowercase{\TestCallCmd\alphwrap{#1}}{#2}%
557   \uppercase{\TestCallCmd\LaTeXAlphWrap{#1}}{#2}%
558   \lowercase{\TestCallCmd\LaTeXalphwrap{#1}}{#2}%
559 }
560 \newcommand*{\TestCallCmd}[3]{%
561   \TestCmd#1{#3}{#2}%
562 }
563 \begin{qstest}{AlphSymbols}{alphalph, AlphAlph, symbols}
564   \TestAlph{1}{a}%
565   \TestAlph{2}{b}%
566   \TestAlph{3}{c}%
567   \TestAlph{4}{d}%
568   \TestAlph{5}{e}%
569   \TestAlph{6}{f}%
570   \TestAlph{7}{g}%
571   \TestAlph{8}{h}%
572   \TestAlph{9}{i}%
573   \TestAlph{10}{j}%
574   \TestAlph{11}{k}%
575   \TestAlph{12}{l}%
576   \TestAlph{13}{m}%
577   \TestAlph{14}{n}%
578   \TestAlph{15}{o}%
579   \TestAlph{16}{p}%
580   \TestAlph{17}{q}%
581   \TestAlph{18}{r}%
582   \TestAlph{19}{s}%
583   \TestAlph{20}{t}%
584   \TestAlph{21}{u}%
585   \TestAlph{22}{v}%
586   \TestAlph{23}{w}%
587   \TestAlph{24}{x}%
588   \TestAlph{25}{y}%
589   \TestAlph{26}{z}%
590 \end{qstest}
591 \begin{qstest}{AlphRange}{alphalph, range}
592   \TestAlph{0}{}%
593   \TestAlph{-1}{}%
594   \TestAlph{-2147483647}{}%
595   \TestAlph{27}{aa}%
596   \TestAlph{28}{ab}%
597   \TestAlph{52}{az}%
598   \TestAlph{53}{ba}%
599   \TestAlph{78}{bz}%
600   \TestAlph{79}{ca}%
601   \TestAlph{702}{zz}%
602   \TestAlph{703}{aaa}%

```

```

603  \TestAlpha{2147483647}{fxshrxw}%
604 \end{qstest}
605
606 \makeatletter
607 \newcommand*{\myvocals}[1]{%
608   \ifcase#1X\or A\or E\or I\or O\or U\else Y\fi
609 }
610 \makeatother
611 \newalphalph\vocalsvocals\myvocals{5}
612 \newcommand*{\TestVocals}{%
613   \TestCmd\vocalsvocals
614 }
615 \begin{qstest}{vocals}{vocals}
616   \TestVocals{0}%
617   \TestVocals{1}{A}%
618   \TestVocals{2}{E}%
619   \TestVocals{3}{I}%
620   \TestVocals{4}{O}%
621   \TestVocals{5}{U}%
622   \TestVocals{6}{AA}%
623   \TestVocals{7}{AE}%
624   \TestVocals{8}{AI}%
625   \TestVocals{9}{AO}%
626   \TestVocals{10}{AU}%
627   \TestVocals{11}{EA}%
628   \TestVocals{24}{OO}%
629   \TestVocals{25}{OU}%
630   \TestVocals{26}{UA}%
631   \TestVocals{29}{UO}%
632   \TestVocals{30}{UU}%
633   \TestVocals{31}{AAA}%
634   \TestVocals{155}{UUU}%
635   \TestVocals{156}{AAAA}%
636   \TestVocals{2147483647}{AII00EEIOIIUOE}%
637 \end{qstest}
638
639 \makeatletter
640 \newalphalph\AlphMult[mult]{\alphalph@Alpha}{26}
641 \newalphalph\alphmult[mult]{\alphalph@alpha}{26}
642 \newalphalph\LaTeXAlphaMult[mult]{\@Alpha}{26}
643 \newalphalph\LaTeXalphmult[mult]{\@alpha}{26}
644 \makeatother
645 \newcommand*{\TestMult}[2]{%
646   \uppercase{\TestCallCmd\AlphMult{\#2}{\#1}}%
647   \lowercase{\TestCallCmd\alphmult{\#2}{\#1}}%
648   \uppercase{\TestCallCmd\LaTeXAlphaMult{\#2}{\#1}}%
649   \lowercase{\TestCallCmd\LaTeXalphmult{\#2}{\#1}}%
650 }
651 \begin{qstest}{mult}{mult}
652   \TestMult{0}%
653   \TestMult{-1}%
654   \TestMult{-2147483647}%
655   \TestMult{1}{a}%
656   \TestMult{2}{b}%
657   \TestMult{26}{z}%
658   \TestMult{27}{aa}%
659   \TestMult{28}{bb}%
660   \TestMult{52}{zz}%
661   \TestMult{53}{aaa}%
662   \TestMult{54}{bbb}%
663   \TestMult{259}{yyyyyyyyyy}%
664   \TestMult{260}{zzzzzzzz}%

```

```

665  \TestMult{261}{aaaaaaaaaaa}%
666  \TestMult{262}{bbbbbbbbbbb}%
667 \end{qstest}
668
669 \def\myvocalsB#1{%
670   \ifcase#1\or A\or E\or I\or O\or U\fi
671 }
672 \begin{qstest}{symbolnum}{symbolnum}
673   \makeatletter
674   \def\Test#1#2{%
675     \let\TestCmd\relax
676     \newalphalph\TestCmd{#1}{}%
677     \Expect*\{\AlPh@Number\}{#2}%
678   }%
679   \Test\@alph{26}%
680   \Test\@Alpha{26}%
681   \Test\@fnsymbol{9}%
682   \Test\myvocalsB{5}%
683   \Test\alphalph@alph{26}%
684   \Test\alphalph@Alpha{26}%
685 \end{qstest}
686
687 \begin{qstest}{list}{list}
688   \makeatletter
689   \def\catch#1\relax{%
690     \def\FoundList{\catch#1}%
691   }%
692   \def\Test[#1]#2#3#4{%
693     \let\testcmd\relax
694     \newalphalph\testcmd{[#1]}{\catch}{#2}%
695     \testcmd{#3}|\relax
696     \expandafter\Expect\expandafter{\FoundList}{#4}%
697   }%
698   \let\SavedCatch\catch
699   \def\catch{\noexpand\catch\noexpand\foo}%
700   \edef\Result{\#4}%
701   \Onelevel@sanitize\Result
702   \let\catch\SavedCatch
703   \let\testcmd\relax
704   \newalphalph\testcmd{[#1]}{\catch\foo}{#2}%
705   \testcmd{#3}|\relax
706   \Onelevel@sanitize\FoundList
707   \Expect*\{\FoundList\}{\Result}%
708 }%
709 \Test[alph]{26}{3}{\catch{3}}%
710 \Test[alph]{26}{12}{\catch{12}}%
711 \Test[alph]{26}{27}{\catch{1}\catch{1}}%
712 \Test[alph]{26}{78}{\catch{2}\catch{26}}%
713 \Test[wrap]{26}{7}{\catch{7}}%
714 \Test[wrap]{26}{14}{\catch{14}}%
715 \Test[wrap]{26}{80}{\catch{2}}%
716 \Test[wrap]{26}{700}{\catch{24}}%
717 \Test[mult]{26}{4}{\catch{4}}%
718 \Test[mult]{26}{17}{\catch{17}}%
719 \Test[mult]{26}{54}{\catch{2}\catch{2}\catch{2}}%
720 \end{qstest}
721
722 \begin{document}
723 \end{document}
724 
```

5 Installation

5.1 Download

Package. This package is available on CTAN¹:

`CTAN:macros/latex/contrib/oberdiek/alphalph.dtx` The source file.

`CTAN:macros/latex/contrib/oberdiek/alphalph.pdf` Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

`CTAN:install/macros/latex/contrib/oberdiek.tds.zip`

TDS refers to the standard “A Directory Structure for TeX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

5.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDSScripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

5.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain-Tex:

```
tex alphalph.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>alphalph.sty</code>	→ <code>tex/generic/oberdiek/alphalph.sty</code>
<code>alphalph.pdf</code>	→ <code>doc/latex/oberdiek/alphalph.pdf</code>
<code>test/alphalph-test1.tex</code>	→ <code>doc/latex/oberdiek/test/alphalph-test1.tex</code>
<code>test/alphalph-test2.tex</code>	→ <code>doc/latex/oberdiek/test/alphalph-test2.tex</code>
<code>test/alphalph-test3.tex</code>	→ <code>doc/latex/oberdiek/test/alphalph-test3.tex</code>
<code>alphalph.dtx</code>	→ <code>source/latex/oberdiek/alphalph.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

5.4 Refresh file name databases

If your Tex distribution (teTeX, mikTeX, ...) relies on file name databases, you must refresh these. For example, teTeX users run `texhash` or `mktexlsr`.

¹<http://ftp.ctan.org/tex-archive/>

5.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk alphalph.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain-T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{alphalph.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex alphalph.dtx
makeindex -s gind.ist alphalph.idx
pdflatex alphalph.dtx
makeindex -s gind.ist alphalph.idx
pdflatex alphalph.dtx
```

6 History

[1999/03/19 v0.1]

- The first version was built as a response to a question² of Will Douglas³ and the request⁴ of Donald Arsenau⁵, published in the newsgroup `comp.text.tex`: “Re: alph counters > 26”⁶
- Copyright: LPPL ([CTAN:macros/latex/base/lppl.txt](#))

[1999/04/12 v1.0]

- Documentation added in dtx format.
- ε -T_EX support added.

[1999/04/13 v1.1]

- Minor documentation change.
- First CTAN release.

²Url: [http://www.dejanews.com/\[ST_rn=ps\]/getdoc.xp?AN=455791936](http://www.dejanews.com/[ST_rn=ps]/getdoc.xp?AN=455791936)

³Will Douglas's email address: william.douglas@wolfson.ox.ac.uk

⁴Url: [http://www.dejanews.com/\[ST_rn=ps\]/getdoc.xp?AN=456358639](http://www.dejanews.com/[ST_rn=ps]/getdoc.xp?AN=456358639)

⁵Donald Arsenau's email address: asnd@reg.triumf.ca

⁶Url: [http://www.dejanews.com/\[ST_rn=ps\]/getdoc.xp?AN=456485421](http://www.dejanews.com/[ST_rn=ps]/getdoc.xp?AN=456485421)

[1999/06/26 v1.2]

- First generic code about \ProvidesPackage improved.
- Documentation: Installation part revised.

[2006/02/20 v1.3]

- Reload check (for plain-T_EX)
- New DTX framework.
- LPPL 1.3

[2006/05/30 v1.4]

- \newalphalph added.

[2007/04/11 v1.5]

- Line ends sanitized.

[2007/09/09 v2.0]

- New implementation that uses package \intcalc. This removes the dependency on ε-T_EX.
- \newalphalph is extended to support new methods ‘wrap’ and ‘multi’.
- Documentation rewritten.

7 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\#	418, 480
\%	483
\@	419, 476
\@Alph	526, 530, 642, 680
\@LastSymbol	535, 538, 542
\@PackageError	119
\@PackageInfo	382
\@ReturnAfterElseFi	<u>136</u> , 284, 312, 335
\@ReturnAfterFi	<u>136</u> , 294, 318, 344, 352
\@alph	527, 531, 643, 679
\@ctrerr	207
\@ehc	119
\@firstofone	427, 430
\@fnssymbol	681
\@gobble	424, 432
\@gobblefour	<u>138</u> , 271
\@ifdefinable	134
\@ifnextchar	159
\@nil	535, 538, 542
\@onellevel@sanitize	701, 706
\@undefined	125, 501
\[.	481
\\"	350, 376, 477, 533, 539
\f	416, 478
\}	417, 479
\]	482
_	484
	A
\advance	457, 465
\AlPh@AtEnd	78, 79, 413
\AlPh@BinSearch	<u>221</u> , 227, <u>242</u> , 254, 258
\AlPh@BracketLeft	150, 152
\AlPh@CheckPositive	269, 276, 304, 327
\AlPh@ctrerr	170, 180, <u>184</u> , 208
\AlPh@Error	<u>116</u> , 128, 189, 230, 370, 404
\AlPh@ExpSearch	192, 217
\AlPh@GetNumberOfSymbols	<u>185</u> , 377
\AlPh@IfDefinable	<u>122</u> , <u>134</u> , 358, 400
\AlPh@IfOptArg	<u>141</u> , <u>145</u> , 159, 162, 360
\AlPh@IfOptArgNext	148, 151
\AlPh@Method@alph	275
\AlPh@Method@mult	326
\AlPh@Method@wrap	303
\AlPh@NewAlphAlph	386, 391, <u>399</u>
\AlPh@newalphalph	361, 363, <u>367</u>

\AlPh@Next	F
. 218, 235, 240, 248, 253, 257, 267	
\AlPh@Number . . . 188, 191, 221, 223,	
229, 262, 265, 378, 383, 388, 677	
\AlPh@ProcessAlpha . . . 279, 282, 300	
\AlPh@ProcessBinSearch . . . 243, 247	
\AlPh@ProcessMult . . . 330, 333	
\AlPh@ProcessWrap . . . 307, 310	
\AlPh@StepAlpha . . . 285, 299	I
\AlPh@StepMult . . . 336, 349	
\AlPh@StepWrap . . . 313, 323	
\AlPh@TempA . . . 146, 153	
\AlPh@TempB . . . 147, 155	
\AlPh@TestNumber 186, 202, 219, 225, 251	
\AlPh@Token . . . 148, 152	
\AlPh@Unavailablefalse . . . 199, 203	
\AlPh@Unavailabletrue . . .	
. 196, 207, 208, 213	
\AlphAlpha . . . 4, 411, 547	
\alphalph . . . 412, 548	
\alphalph@Alpha 5, 164, 411, 528, 640, 684	
\alphalph@alph 164, 412, 529, 641, 683	
\AlphMult . . . 640, 646	
\alphmult . . . 641, 647	
\AlphWrap . . . 528, 555	
\alphwrap . . . 529, 556	
B	
\begin{ 563, 591, 615, 651, 672, 687, 722	
\body 436, 440	
C	
\catch . . . 689, 690, 694, 698, 699,	K
702, 704, 709, 710, 711, 712,	
713, 714, 715, 716, 717, 718, 719	
\catcode . . . 3, 4, 5, 6, 7, 18,	
19, 20, 34, 35, 36, 37, 38, 39, 40,	
41, 42, 43, 44, 62, 63, 66, 67, 68,	
69, 73, 74, 75, 76, 80, 82, 110,	
111, 113, 114, 416, 417, 418,	
419, 454, 463, 476, 477, 478,	
479, 480, 481, 482, 483, 484, 485	
\count@ 421, 450,	
454, 456, 457, 461, 463, 464, 465	
\countdef 421	
\csname . 8, 21, 45, 58, 65, 101, 109,	
123, 138, 142, 144, 369, 387,	
392, 420, 423, 426, 429, 468, 490	
D	
\detokenize 373	M
\DisableNumexpr . . . 500, 506, 516	
\documentclass 496	
E	
\empty 12	N
\end 491, 590, 604, 637, 667, 685, 720, 723	
\endcsname 8, 21, 45, 58, 65, 101, 109,	
123, 138, 142, 144, 369, 387,	
392, 420, 423, 426, 429, 468, 490	
\endinput 30	
\escapechar 118, 381	
\Expect . . . 518, 520, 522, 677, 696, 707	
F	
\foo 699, 704	
\FoundList 690, 696, 706, 707	
\futurelet 148	
H	
\hbox 205, 515	
I	
\ifAlPh@Unavailable	
. 187, 195, 220, 226, 252	
\ifcase . 9, 125, 165, 175, 378, 608, 670	
\ifdim 212	
\iffalse 200	
\ifnum 224, 249, 250,	
270, 283, 311, 334, 401, 456, 464	
\iftrue 197	
\ifx 10, 12, 21,	
45, 53, 101, 109, 123, 125, 138,	
142, 144, 152, 350, 369, 376,	
420, 423, 426, 429, 468, 533, 539	
\immediate 23, 47	
\IncludeTests 511	
\input 102, 103, 469	
\intcalcAdd 244	
\intcalcDec 287, 290, 314, 337, 340	
\intcalcDiv 290, 337	
\intcalcInc 286, 314, 337, 340	
\intcalcMod 287, 314, 340	
\intcalcShl 236	
\intcalcShr 244	
\iterate 437, 439, 441	
K	
\kernel@ifnextchar 162	
L	
\LastSymbol 532, 551	
\LaTeXAlphaAlpha 526, 549	
\LaTeXalphalph 527, 550	
\LaTeXAlphaMult 642, 648	
\LaTeXalphmult 643, 649	
\LaTeXAlphaWrap 530, 557	
\LaTeXalphwrap 531, 558	
\LoadCommand 469, 486	
\LogTests 512	
\loop 435, 451, 462	
\lowercase 548, 550, 556, 558, 647, 649	
M	
\makeatletter	
. 498, 525, 606, 639, 673, 688	
\makeatother 545, 610, 644	
\MessageBreak 405	
\myvocals 607, 611	
\myvocalsB 669, 682	
N	
\NeedsTeXFormat 494	
\newalphalph . 5, 358, 411, 412, 526,	
527, 528, 529, 530, 531, 611,	
640, 641, 642, 643, 676, 694, 704	
\newcommand 500, 503,	
514, 546, 554, 560, 607, 612, 645	
\newif 195	

\next	441, 443, 445	
\nofiles	495	589, 592, 593, 594, 595, 596,
\number	236, 244, 277,	597, 598, 599, 600, 601, 602, 603
	285, 289, 305, 313, 328, 339, 393	\TestAlphaWrap
\numexpr	278, 306, 329, 394, 499, 501, 504	552, 554
		\TestCallCmd
P		
\PackageInfo	26	. 547, 548, 549, 550, 555, 556,
\ProvidesPackage	59	557, 558, 560, 646, 647, 648, 649
		\TestCmd
		514, 561, 613, 675, 676
R		\testcmd .. 693, 694, 695, 703, 704, 705
\RangeCatcodeInvalid		\TestMult
	460, 472, 473, 474, 475	645, 652, 653,
\repeat	435, 447, 458, 466	654, 655, 656, 657, 658, 659,
\RequirePackage	105, 106	660, 661, 662, 663, 664, 665, 666
\RestoreCatcodes ..	449, 452, 453, 487	\TestString
\RestoreNumexpr	503, 509	517, 518, 519, 520
\Result	700, 701, 707	\TestVocals
\romannumeral	336	612, 616, 617,
		618, 619, 620, 621, 622, 623,
S		624, 625, 626, 627, 628, 629,
\saved@numexpr	499, 504	630, 631, 632, 633, 634, 635, 636
\SavedCatch	698, 702	\the
\setbox	205, 515	66, 67, 68,
		69, 80, 278, 306, 329, 394, 454, 522
		\TMP@EnsureCode
T		
\Test	471, 489, 77, 84, 85, 86, 87, 88, 89,
	674, 679, 680, 681, 682, 683,	90, 91, 92, 93, 94, 95, 96, 97, 98, 99
	684, 692, 709, 710, 711, 712,	
	713, 714, 715, 716, 717, 718, 719	
\TestAlpha	546, 564,	
	565, 566, 567, 568, 569, 570,	
	571, 572, 573, 574, 575, 576,	
	577, 578, 579, 580, 581, 582,	
	583, 584, 585, 586, 587, 588,	
U		
\uppercase	547, 549, 555, 557, 646, 648	
\usepackage		\usepackage .. 508, 510
V		
\vocalsvocals		611, 613
W		
\wd		212, 522
\WrapString		551, 552
\write		23, 47
X		
\x	8, 10, 12, 22, 26, 28, 46, 51, 58, 64, 72	