

# The classlist package

Heiko Oberdiek  
<heiko.oberdiek at gmail.com>

2011/10/17 v1.4

## Abstract

This package records the loaded classes and stores them in a list.

## Contents

<b>1 Documentation</b>	<b>1</b>
1.1 Background	1
1.2 Usage	2
<b>2 Implementation</b>	<b>2</b>
<b>3 Installation</b>	<b>4</b>
3.1 Download	4
3.2 Bundle installation	5
3.3 Package installation	5
3.4 Refresh file name databases	5
3.5 Some details for the interested	5
<b>4 Catalogue</b>	<b>6</b>
<b>5 History</b>	<b>7</b>
[2005/06/19 v1.0]	7
[2005/06/19 v1.1]	7
[2006/02/20 v1.2]	7
[2008/08/11 v1.3]	7
[2011/10/17 v1.4]	7
<b>6 Index</b>	<b>7</b>

## 1 Documentation

### 1.1 Background

This packages is an answer of a newsgroup question:

Newsgroup: comp.text.tex  
Subject: Finding the Document Class  
From: Herber Schulz  
Date: 18 Jun 2005 13:16:49 -0500  
Message-ID: <herbs-D55DB9.13170418062005@news.isp.giganews.com>

## 1.2 Usage

Load this package before `\documentclass`:

```
\RequirePackage{classlist}
\documentclass[some,options]{whatever}
```

It then records the classes with options.

If used after `\documentclass`, `\@filelist` is parsed for classes. The additional data specified options and requested version is no longer available here.

`\MainClassName` contains the first loaded class.

`\ClassList` stores the class entries, eg.

```
\ClassList → \ClassListEntry{myarticle}{a4paper}{}
              \ClassListEntry{article}{}{}
```

`\ClassListEntry` has three arguments:

```
#1:  class name
#2:  options given in \documentclass/\LoadClass
#3:  requested version, not the version of class
```

`\PrintClassList` prints the list on screen it can be configured by

`\PrintClassListTitle` for the title and

`\PrintClassListEntry` for formatting the entries. See the implementation how to use these.

## 2 Implementation

```
1 (*package)
Package identification.
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{classlist}%
4   [2011/10/17 v1.4 Record classes used in a document (HO)]
5 \let\ClassList\@empty
6 \let\MainClassName\relax
Test, whether we are called before \documentclass.
7 \ifx\@classoptionslist\relax
8   \let\CL@org@fileswith@pti@ns\@fileswith@pti@ns
9   \def\@fileswith@pti@ns#1[#2]#3[#4]{%
#1:  \@clsextension
#2:  options of \documentclass/\LoadClass
#3:  class name
#4:  requested version
10   \ifx#1\@clsextension
11     \@ifl@aded#1[#3]{%
12       \PackageInfo{classlist}{%
13         Skipping class ‘#3’, because\MessageBreak
14         this class is already loaded%
15       }%
16     }{%
17       \@ifundefined{MainClassName}{%
18         \def\MainClassName{#3}%

```

```

19      }{}%
20      \@temptokena\expandafter{%
21        \ClassList
22        \ClassListEntry{#3}{#2}{#4}%
23      }%
24      \edef\ClassList{\the\@temptokena}%
25    }%
26  \fi
27  \CL@org@fileswith@pti@ns{#1}[\{#2\}]{#3}[\{#4\}]%
28 }%
29 \let\@@fileswith@pti@ns\@fileswith@pti@ns
30 \else
Called after \documentclass.
31 \PackageInfo{classlist}{Use \string\@filelist\space method}%
32
33 \let\ClassListEntry\relax
34 \expandafter\def\expandafter\CL@test
35   \expandafter#\expandafter1\@clsextension#2\@nil{%
36   \ifx\#2\%
Name does not contain \@clsextension
37   \else
38     \expandafter\CL@test@i\CL@entry\@nil
39   \fi
40 }%
41 \expandafter\def\expandafter\CL@test@i
42   \expandafter#\expandafter1\@clsextension#2\@nil{%
43   \ifx\#2\%
44     \@ifundefined{opt@\CL@entry}{%
45     }{%
46       \@ifundefined{MainClassName}{%
47       \let\MainClassName\CL@entry
48       }{%
49       }%
50     \edef\ClassList{%
51       \ClassList
52       \ClassListEntry{\CL@entry}{\{}}%
53     }%
54   }%
55   \else
Names with more than one \@clsextension are not supported.
56   \fi
57 }%
58 \@for\CL@entry:=\@filelist\do{%
59   \expandafter\expandafter\expandafter\CL@test\expandafter
60     \CL@entry\@clsextension\@nil
61 }%
62 \fi

\PrintClassListEntry
63 \providecommand*\PrintClassListEntry[3]{%
64   \toks@{* #1}%
65   \typeout{\the\toks@}%
66 }

\PrintClassListTitle
67 \providecommand*\PrintClassListTitle{%
68   \typeout{Class list:}%
69 }

```

```

\PrintClassList
70 \providecommand*\PrintClassList{%
71   \begingroup
72   \let\ClassListEntry\PrintClassListEntry
73   \PrintClassListTitle
74   \ClassList
75   \endgroup
76 }

\CL@InfoEntry
77 \def\CL@InfoEntry#1#2#3{%
78   \advance\count@ by \@ne
79   \def\x{#2}%
80   \@onelevel@sanitize\x
81   \edef\CL@Info{%
82     \CL@Info
83     \noexpand\MessageBreak
84     (\the\count@) %
85     #1 [\x]%
86     \ifx\#3\%
87     \else
88       \space[#3]% hash-ok
89     \fi
90   }%
91 }

92 \AtBeginDocument{%
93   \begingroup
94   \count@=\z@
95   \def\CL@Info{Class List:}%
96   \let\ClassListEntry\CL@InfoEntry
97   \ClassList
98   \let\online\@empty
99   \PackageInfo{classlist}{\CL@Info}%
100 \endgroup
101 }
102 \</package>

```

## 3 Installation

### 3.1 Download

**Package.** This package is available on CTAN<sup>1</sup>:

[CTAN:macros/latex/contrib/oberdiek/classlist.dtx](http://ctan.org/ctan/ctan/macros/latex/contrib/oberdiek/classlist.dtx) The source file.

[CTAN:macros/latex/contrib/oberdiek/classlist.pdf](http://ctan.org/ctan/ctan/macros/latex/contrib/oberdiek/classlist.pdf) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](http://ctan.org/ctan/ctan/install/macros/latex/contrib/oberdiek.tds.zip)

*TDS* refers to the standard “A Directory Structure for  $\TeX$  Files” ([CTAN:tds/tds.pdf](http://ctan.org/ctan/ctan/tds/tds.pdf)). Directories with `texmf` in their name are usually organized this way.

---

<sup>1</sup>[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

## 3.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

## 3.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain  $\mathrm{T\!E\!X}$ :

```
tex classlist.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
classlist.sty → tex/latex/oberdiek/classlist.sty
classlist.pdf → doc/latex/oberdiek/classlist.pdf
classlist.dtx → source/latex/oberdiek/classlist.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

## 3.4 Refresh file name databases

If your  $\mathrm{T\!E\!X}$  distribution (`te $\mathrm{T\!E\!X}$` , `mik $\mathrm{T\!E\!X}$` , ...) relies on file name databases, you must refresh these. For example, `te $\mathrm{T\!E\!X}$`  users run `texhash` or `mktexlsr`.

## 3.5 Some details for the interested

**Attached source.** The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk classlist.pdf unpack_files output .
```

**Unpacking with  $\mathrm{L\!A\!T\!E\!X}$ .** The `.dtx` chooses its action depending on the format:

**plain  $\mathrm{T\!E\!X}$ :** Run `docstrip` and extract the files.

**$\mathrm{L\!A\!T\!E\!X}$ :** Generate the documentation.

If you insist on using  $\mathrm{L\!A\!T\!E\!X}$  for `docstrip` (really, `docstrip` does not need  $\mathrm{L\!A\!T\!E\!X}$ ), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{classlist.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL<sup>A</sup>T<sub>E</sub>X:

```
pdflatex classlist.dtx
makeindex -s gind.ist classlist.idx
pdflatex classlist.dtx
makeindex -s gind.ist classlist.idx
pdflatex classlist.dtx
```

## 4 Catalogue

The following XML file can be used as source for the [T<sub>E</sub>X Catalogue](#). The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `classlist.xml`.

```
103 (*catalogue)
104 <?xml version='1.0' encoding='us-ascii'?>
105 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
106 <entry datestamp='$Date$' modifier='$Author$' id='classlist'>
107   <name>classlist</name>
108   <caption>Record classes used in a document.</caption>
109   <authorref id='auth:oberdiek'>/>
110   <copyright owner='Heiko Oberdiek' year='2005,2006,2008,2011'>/>
111   <license type='lppl1.3'>/>
112   <version number='1.4'>/>
113   <description>
114     Load this package before \documentclass:
115     <p>
116       &nbsp;&nbsp;&nbsp;<tt>\RequirePackage{classlist}</tt><br/>
117       &nbsp;&nbsp;&nbsp;<tt>\documentclass[some,options]{whatever}</tt>
118     </p>
119     After doing this, <tt>\MainClass</tt> contains the name of the
120     first loaded class, <tt>\ClassList</tt> contains a set of triples
121     <tt>\class name</tt>, <tt>\options directly requested</tt>, and
122     <tt>\version requested</tt>. (The package may also be loaded after
123     <tt>\documentclass</tt>, in which case some information is not
124     available.)
125     <p>
126       The package is part of the <xref refid='oberdiek'>oberdiek</xref>
127       bundle.
128     </p>
129   </description>
130   <documentation details='Package documentation'
131     href='ctan:/macros/latex/contrib/oberdiek/classlist.pdf'>/>
132   <ctan file='true' path='/macros/latex/contrib/oberdiek/classlist.dtx'>/>
133   <miktex location='oberdiek'>/>
134   <texlive location='oberdiek'>/>
135   <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip'>/>
136 </entry>
137 </catalogue>
```

## 5 History

[2005/06/19 v1.0]

- First published version: CTAN and newsgroup `comp.text.tex`: “Re: Finding the Document Class”<sup>2</sup>

[2005/06/19 v1.1]

- After `\documentclass` the package looks at `\@filelist` instead of aborting with error.

[2006/02/20 v1.2]

- DTX framework.
- Fix for `\@fileswith@pti@ns`.

[2008/08/11 v1.3]

- Code is not changed.
- URLs updated.

[2011/10/17 v1.4]

- Documentation fix: `\MainClass` → `\MainClassName`.

## 6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols			
<code>\@fileswith@pti@ns</code>	29	<code>\CL@Info</code>	81, 82, 95, 99
<code>\@classoptionslist</code>	7	<code>\CL@InfoEntry</code>	77, 96
<code>\@clsextension</code>	10, 35, 42, 60	<code>\CL@org@fileswith@pti@ns</code>	8, 27
<code>\@empty</code>	5, 98	<code>\CL@test</code>	34, 59
<code>\@filelist</code>	31, 58	<code>\CL@test@i</code>	38, 41
<code>\@fileswith@pti@ns</code>	8, 9, 29	<code>\ClassList</code>	5, 21, 24, 50, 51, 74, 97, 120
<code>\@for</code>	58	<code>\ClassListEntry</code>	22, 33, 52, 72, 96
<code>\@ifl@aded</code>	11	<code>\count@</code>	78, 84, 94
<code>\@ifundefined</code>	17, 44, 46	<b>D</b>	
<code>\@ne</code>	78	<code>\do</code>	58
<code>\@nil</code>	35, 38, 42, 60	<code>\documentclass</code>	114, 117, 123
<code>\@onelevel@sanitize</code>	80	<b>I</b>	
<code>\@temptokena</code>	20, 24	<code>\ifx</code>	7, 10, 36, 43, 86
<code>\@</code>	36, 43, 86	<b>M</b>	
<b>A</b>		<code>\MainClass</code>	119
<code>\advance</code>	78	<code>\MainClassName</code>	6, 18, 47
<code>\AtBeginDocument</code>	92	<code>\MessageBreak</code>	13, 83
<b>C</b>			
<code>\CL@entry</code>	38, 44, 47, 52, 58, 60		

<sup>2</sup>Url: <http://groups.google.com/group/comp.text.tex/msg/8ee9523c2dc13666>

<b>N</b>		<b>S</b>	
\NeedsTeXFormat	2	\space	31, 88
<b>O</b>		<b>T</b>	
\on@line	98	\the	24, 65, 84
<b>P</b>		\toks@	64, 65
\PackageInfo	12, 31, 99	\typeout	65, 68
\PrintClassList	70	<b>X</b>	
\PrintClassListEntry	63, 72	\x	79, 80, 85
\PrintClassListTitle	67, 73	<b>Z</b>	
\providecommand	63, 67, 70	\z@	94
\ProvidesPackage	3		
<b>R</b>			
\RequirePackage	116		