

# The colonequals package

Heiko Oberdiek  
<oberdiek@uni-freiburg.de>

2006/08/01 v1.0

## Abstract

Package `colonequals` defines poor man's symbols for math relation symbols such as “colon equals”. The colon is centered around the horizontal math axis.

## Contents

<b>1</b>	<b>User interface</b>	<b>1</b>
1.1	Introduction . . . . .	1
1.2	Symbols . . . . .	2
1.3	Fine tuning . . . . .	2
1.3.1	Example . . . . .	3
<b>2</b>	<b>Implementation</b>	<b>3</b>
2.1	Identification . . . . .	3
2.2	Distance control . . . . .	3
2.3	Centered colons . . . . .	3
2.4	Combined symbols . . . . .	4
<b>3</b>	<b>Installation</b>	<b>5</b>
3.1	Download . . . . .	5
3.2	Bundle installation . . . . .	5
3.3	Package installation . . . . .	5
3.4	Refresh file name databases . . . . .	5
3.5	Some details for the interested . . . . .	5
<b>4</b>	<b>References</b>	<b>6</b>
<b>5</b>	<b>History</b>	<b>6</b>
	[2006/08/01 v1.0] . . . . .	6
<b>6</b>	<b>Index</b>	<b>6</b>

## 1 User interface

### 1.1 Introduction

Math symbols consisting of the colon character can be constructed with the colon text character, if the math font lacks of the complete symbol. Often, however, the colon text character is not centered around the math axis. Especially combined with the equals symbol the composed symbol does not look symmetrically. Thus this packages defines a colon math symbol `\ratio` that is centered around the horizontal math axis. Also math symbols are provided that consist of the colon symbol. The package is not necessary, if the math font contains the composed symbols. Examples are `txfonts` ([1]) or `mathabx` ([2]).

## 1.2 Symbols

All symbols of this package are relation symbols. The relation property can be changed by the appropriate T<sub>E</sub>X command `\mathbin`, `\mathord`, ...

Table 1: Unicode mathematical operators

U+2236	RATIO	:	<code>\ratio</code>
U+2237	PROPORTION	::	<code>\coloncolon</code>
U+2239	EXCESS	:-	<code>\colonminus</code>
U+2254	COLON EQUALS	:=	<code>\colonequals</code>
U+2255	EQUALS COLON	=:	<code>\equalscolon</code>

The following grammar generates all symbols that are supported by this package:

Table 2: Symbol grammar

symbols	::=	col
		col symbol
		symbol col
		;
col	::=	'.'
		'::'
		;
symbol	::=	'='
		'−'
		'≈'
		'∼'
		;

Table 3: All relation symbols

:	<code>\ratio</code>
::	<code>\coloncolon</code>
:=	<code>\colonequals</code>
::=	<code>\coloncolonequals</code>
=:	<code>\equalscolon</code>
=::	<code>\equalscoloncolon</code>
:-	<code>\colonminus</code>
::-	<code>\coloncolonminus</code>
−:	<code>\minuscolon</code>
−::	<code>\minuscoloncolon</code>
:≈	<code>\colonapprox</code>
::≈	<code>\coloncolonapprox</code>
≈:	<code>\approxcolon</code>
≈::	<code>\approxcoloncolon</code>
:~	<code>\colonsim</code>
::~	<code>\coloncolonsim</code>
~:	<code>\simcolon</code>
~::	<code>\simcoloncolon</code>

## 1.3 Fine tuning

The distances in composed symbols can be configured:

`\colonsep`

Macro `\colonsep` is executed between the colon and the other symbol.

`\doublecolonsep`

Macro `\doublecolonsep` controls the distance between two colons.

### 1.3.1 Example

```
\renewcommand*{\colonsep}{\mskip-.5\thinmuskip}
```

## 2 Implementation

### 2.1 Identification

```
1 (*package)
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{colonequals}%
4 [2006/08/01 v1.0 Colon equals symbols (H0)]%
```

### 2.2 Distance control

`\colonsep`

```
5 \newcommand*{\colonsep}{}%
```

`\doublecolonsep`

```
6 \newcommand*{\doublecolonsep}{}%
```

### 2.3 Centered colons

```
7 \def\@center@colon{%
8   \mathpalette\@center@math{:}%
9 }
10 \def\@center@math#1#2{%
11   \vcenter{%
12     \m@th
13     \hbox{#1#2}%
14   }%
15 }
```

`\ratio` Because the name `\colon` is already in use, the Unicode name `\ratio` is used for the centered colon relation symbol. (The `\ratio` of package `calc` is not used outside `calc` expressions.)

```
16 \newcommand*{\ratio}{%
17   \ensuremath{%
18     \mathrel{%
19       \@center@colon
20     }%
21   }%
22 }
```

`\coloncolon`

```
23 \newcommand*{\coloncolon}{%
24   \ensuremath{%
25     \mathrel{%
26       \@center@colon
27       \doublecolonsep
28       \@center@colon
29     }%
30   }%
31 }
```

## 2.4 Combined symbols

```

32 \def\@make@colon@set#1#2{%
33   \begingroup
34     \let\@center@colon\relax
35     \let\newcommand\relax
36     \let\ensuremath\relax
37     \let\mathrel\relax
38     \let\colonsep\relax
39     \let\doublecolonsep\relax
40     \def\csx##1{%
41       \expandafter\noexpand\csname ##1\endcsname
42     }%
43   \edef\x{\endgroup
44     \newcommand*{\csx{colon#1}}{%
45       \ensuremath{%
46         \mathrel{%
47           \@center@colon
48           \colonsep
49           {#2}%
50         }%
51       }%
52     }%
53     \newcommand*{\csx{coloncolon#1}}{%
54       \ensuremath{%
55         \mathrel{%
56           \@center@colon
57           \doublecolonsep
58           \@center@colon
59           \colonsep
60           {#2}%
61         }%
62       }%
63     }%
64     \newcommand*{\csx{#1colon}}{%
65       \ensuremath{%
66         \mathrel{%
67           {#2}%
68           \colonsep
69           \@center@colon
70         }%
71       }%
72     }%
73     \newcommand*{\csx{#1coloncolon}}{%
74       \ensuremath{%
75         \mathrel{%
76           {#2}%
77           \colonsep
78           \@center@colon
79           \doublecolonsep
80           \@center@colon
81         }%
82       }%
83     }%
84   }%
85   \x
86 }

87 \@make@colon@set{equals}{=}%
88 \@make@colon@set{minus}{-}%
89 \@make@colon@set{approx}{\approx}
90 \@make@colon@set{sim}{\sim}
91 \end{package}

```

## 3 Installation

### 3.1 Download

**Package.** This package is available on CTAN<sup>1</sup>:

[CTAN:macros/latex/contrib/oberdiek/colonequals.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/colonequals.pdf](#) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:macros/latex/contrib/oberdiek/oberdiek-tds.zip](#)

### 3.2 Bundle installation

**Unpacking.** Unpack the oberdiek-tds.zip in the TDS tree (also known as texmf tree) of your choice. Example (linux):

```
unzip oberdiek-tds.zip -d ~/texmf
```

**Script installation.** Check the directory TDS:scripts/oberdiek/ for scripts that need further installation steps. Package attachfile2 comes with the Perl script pdfatfi.pl that should be installed in such a way that it can be called as pdfatfi. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

### 3.3 Package installation

**Unpacking.** The .dtx file is a self-extracting docstrip archive. The files are extracted by running the .dtx through plain-TeX:

```
tex colonequals.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as texmf tree):

```
colonequals.sty → tex/latex/oberdiek/colonequals.sty
colonequals.pdf → doc/latex/oberdiek/colonequals.pdf
colonequals.dtx → source/latex/oberdiek/colonequals.dtx
```

If you have a docstrip.cfg that configures and enables docstrip’s TDS installing feature, then some files can already be in the right place, see the documentation of docstrip.

### 3.4 Refresh file name databases

If your TeX distribution (TeX, mikTeX, ...) relies on file name databases, you must refresh these. For example, TeX users run texhash or mktexlsr.

### 3.5 Some details for the interested

**Attached source.** The PDF documentation on CTAN also includes the .dtx source file. It can be extracted by AcrobatReader 6 or higher. Another option is pdftk, e.g. unpack the file into the current directory:

```
pdftk colonequals.pdf unpack_files output .
```

---

<sup>1</sup><http://ftp.ctan.org/tex-archive/>

**Unpacking with L<sup>A</sup>T<sub>E</sub>X.** The .dtx chooses its action depending on the format:

**plain-T<sub>E</sub>X:** Run docstrip and extract the files.

**L<sup>A</sup>T<sub>E</sub>X:** Generate the documentation.

If you insist on using L<sup>A</sup>T<sub>E</sub>X for docstrip (really, docstrip does not need L<sup>A</sup>T<sub>E</sub>X), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{colonequals.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the .dtx or the .drv to generate the documentation. The process can be configured by the configuration file ltxdoc.cfg. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL<sup>A</sup>T<sub>E</sub>X:

```
pdflatex colonequals.dtx
makeindex -s gind.ist colonequals.idx
pdflatex colonequals.dtx
makeindex -s gind.ist colonequals.idx
pdflatex colonequals.dtx
```

## 4 References

- [1] Young Ryu: *The TX Fonts*; 2000/12/15; [CTAN:fonts/txfonts/](#).
- [2] Anthony Phan: *Mathabx font series*; 2005/05/16; [CTAN:fonts/mathabx/](#).

## 5 History

[2006/08/01 v1.0]

- First version.

## 6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		D	
\@center@colon	..... 7, 19, 26, 28, 34, 47, 56, 58, 69, 78, 80	\doublecolonsep	... 3, <u>6</u> , 27, 39, 57, 79
\@center@math	..... 8, 10	E	
\@make@colon@set	... 32, 87, 88, 89, 90	\endcsname	..... 41
		\ensuremath	.. 17, 24, 36, 45, 54, 65, 74
A		H	
\approx	..... 89	\hbox	..... 13
C		M	
\coloncolon	..... 23	\m@th	..... 12
\colonsep	..... 3, <u>5</u> , 38, 48, 59, 68, 77	\mathpalette	..... 8
\csname	..... 41	\mathrel	... 18, 25, 37, 46, 55, 66, 75
\csx	..... 40, 44, 53, 64, 73		

N		S	
<code>\NeedsTeXFormat</code>	2	<code>\sim</code>	90
<code>\newcommand</code>	5, 6, 16, 23, 35, 44, 53, 64, 73		
P		V	
<code>\ProvidesPackage</code>	3	<code>\vcenter</code>	11
R		X	
<code>\ratio</code>	<u>16</u>	<code>\x</code>	43, 85