

The `engord` package

Heiko Oberdiek

<oberdiek@uni-freiburg.de>

2007/04/26 v1.4

Abstract

The package generates the suffix of English ordinal numbers. It can be used with plain and L^AT_EX formats.

Contents

1	Usage	1
1.1	Package options	2
1.2	Examples	2
2	Implementation	3
2.1	Reload check and identification	3
2.2	Help commands for plain compatibility	3
2.3	User macros	4
2.4	Suffix generation	5
3	Installation	6
3.1	Download	6
3.2	Bundle installation	7
3.3	Package installation	7
3.4	Refresh file name databases	7
3.5	Some details for the interested	7
4	History	8
[2000/05/23 v1.0]	8
[2003/04/28 v1.1]	8
[2006/02/20 v1.2]	8
[2007/04/11 v1.3]	8
[2007/04/26 v1.4]	8
5	Index	8

1 Usage

`\engord{\{LATEX counter name\}}`

It prints the value of the L^AT_EX counter as English ordinal number. It can be used in the same way as `\arabic`, `\roman`, or `\alph`. The command is not available in plain-T_EX.

`\engordnumber{\{any TEX number\}}`

It prints the number as English ordinal number.

```
\engordletters{#1}
```

This command formats the English ordinal letters after the number. It defaults to `\textsuperscript`.

```
\engorderror{#1}
```

It can be redefined, if an other error handling is wanted. The argument is a negative number or zero.

```
\engordraisetrue  
\engordraisefalse
```

These commands set the switch `\ifengordraise` that is asked by the default `\engordletters` before raising the ordinal letters.

1.1 Package options

normal: `\engordraisefalse`

raise: `\engordraisetrue`

Default is `raise`.

1.2 Examples

- `\usepackage[normal]{engord}`
`\engordnumber{1} → 1st`
`\engordnumber{12} → 12th`
`\engordnumber{123} → 123rd`
`\engord{page} → 1st (if page has the value of one)`
`\engordraisetrue`
`\engordnumber{12} → 12th`

- The default output of a counter can be redefined:

```
\newcounter{mycounter}  
\renewcommand{\theengcounter}{\engord{mycounter}}
```

- Because the implementation of `\engord` and `\engordnumber` is kept expandable, these commands can be used to make command names with an appropriate definition of `\engordletters`:

```
\renewcommand*{\engordletters}[1]{#1}  
\@namedef{My\engordnumber{3}Command}{...}
```

This generates the command name ‘`\My4rdCommand`’. Since version 1.2 the redefinition can be dropped if the letters are not raised.

- If the letters should not be raised, use L^AT_EX package option `normal` or use

```
\engordraisefalse
```

Also `\engordletters` could be redefined for this purpose:

```
\renewcommand*{\engordletters}[1]{#1}
```

2 Implementation

2.1 Reload check and identification

1 `(*package)`

Reload check, especially if the package is not used with L^AT_EX.

```
2 \begingroup
3   \catcode44 12 % ,
4   \catcode45 12 % -
5   \catcode46 12 % .
6   \catcode58 12 % :
7   \catcode64 11 % @
8   \expandafter\let\expandafter\x\csname ver@engord.sty\endcsname
9   \ifcase 0%
10     \ifx\x\relax % plain
11     \else
12       \ifx\x\empty % LaTeX
13       \else
14         1%
15       \fi
16     \fi
17   \else
18     \expandafter\ifx\csname PackageInfo\endcsname\relax
19       \def\x#1#2{%
20         \immediate\write-1{Package #1 Info: #2.}%
21       }%
22     \else
23       \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
24     \fi
25   \x{engord}{The package is already loaded}%
26   \endgroup
27   \expandafter\endinput
28 \fi
29 \endgroup
```

Package identification:

```
30 \begingroup
31   \catcode44 12 % ,
32   \catcode45 12 % -
33   \catcode46 12 % .
34   \catcode58 12 % :
35   \catcode64 11 % @
36   \expandafter\ifx\csname ProvidesPackage\endcsname\relax
37     \def\x#1#2#3[#4]{\endgroup
38       \immediate\write-1{Package: #3 #4}%
39       \xdef#1[#4]%
40     }%
41   \else
42     \def\x#1#2[#3]{\endgroup
43       #2[#3]%
44       \ifx#1\relax
45         \xdef#1[#3]%
46       \fi
47     }%
48   \fi
49 \expandafter\x\csname ver@engord.sty\endcsname
50 \ProvidesPackage{engord}%
51 [2007/04/26 v1.4 Provides the ifpdf switch (HO)]
```

2.2 Help commands for plain compatibility

\E0@atcode Save catcode of @.

```
52 \expandafter\chardef\csname E0@atcode\endcsname\catcode`@"
53 \catcode`\@=11 %
```

```

\EO@def Definitions, \newcommand does not exist in plain-TEX.
54 \begingroup\expandafter\expandafter\expandafter\endgroup
55 \expandafter\ifx\csname newcommand\endcsname\relax
56   \def\EO@def{\def}%
57 \else
58   \def\EO@def#1{%
59     \newcommand*{#1}{}}%
60   \def#1{%
61 }%
62 \fi

63 \begingroup\expandafter\expandafter\expandafter\endgroup
64 \expandafter\ifx\csname RequirePackage\endcsname\relax
65   \input infwarerr.sty\relax
66 \else
67   \RequirePackage{infwarerr}%
68 \fi

```

2.3 User macros

\ifengordraise The switch \ifengordraise, whether the ordinal letters are raised or not. Default is raised because of compatibility.

```

69 \newif\ifengordraise
70 \engordraisetrue

```

In L^AT_EX this also can be controlled by option *normal* or *raise*.

```

71 \begingroup\expandafter\expandafter\expandafter\endgroup
72 \expandafter\ifx\csname DeclareOption\endcsname\relax
73 \else
74   \DeclareOption{normal}{\engordraisefalse}%
75   \DeclareOption{raise}{\engordraisetrue}%
76   \ProcessOptions*\relax
77 \fi

```

\engordletters \engordletters is called with one argument, the english ordinal letters, and contains the code to format them. It defaults to \textsuperscript depending on \ifengordraise.

```

78 \expandafter\ifx\csname engordletters\endcsname\relax
79   \EO@def\engordletters{%
80     \ifengordraise
81       \expandafter\engordtextsuperscript
82     \fi
83 }%
84 \fi

```

\engordtextsuperscript For plain-T_EX the definition is quite ugly, redefine \engordtextsuperscript if you have a better one.

```

85 \expandafter\ifx\csname engordtextsuperscript\endcsname\relax
86   \begingroup\expandafter\expandafter\expandafter\endgroup
87   \expandafter\ifx\csname textsuperscript\endcsname\relax
88     \def\engordtextsuperscript#1{%
89       \relax
90       \ifmmode
91         ^{\rm#1}%
92       \else
93         $^{\rm#1}$%
94       \fi
95     }%
96   \else
97     \def\engordtextsuperscript{\textsuperscript}%
98   \fi
99 \fi

```

\engorderror \engorderror is called, if the number is zero or negative.

```

100 \expandafter\ifx\csname engorderror\endcsname\relax
101   \EO@def\engorderror#1{%
102     #1\engordletters{!ERROR!}%
103     \PackageWarning{engord}{%
104       '#1' is not an ordinal number%
105     }%
106   }%
107 \fi

```

\engord \engord expects a L^AT_EX counter name as argument and calls \engordnumber. It is defined only, if L^AT_EX is used.

```

108 \begingroup\expandafter\expandafter\expandafter\endgroup
109 \expandafter\ifx\csname newcounter\endcsname\relax
110 \else
111   \EO@def\engord#1{%
112     \engordnumber{\value{#1}}%
113   }%
114 \fi

```

\engordnumber \engordnumber is the user command to print a number as english ordinal number. The argument can be any T_EX number like explicit numbers, register values, ... In a safe way it converts the T_EX number argument into a form that only consists of decimal digits.

```

115 \EO@def\engordnumber#1{%
116   \expandafter\EO@number\expandafter{\number#1}%
117 }

```

2.4 Suffix generation

\EO@number \EO@number expects a number with decimal digits as argument and looks at the size of the number and the count of the digits:

```

118 \def\EO@number#1{%
119   \ifnum#1<1 % handle the error case
120     \engorderror{#1}%
121   \else
122     \ifnum#1<21 %
123       \EO@ord{#1}%
124     \else
125       \ifnum#1<100 %
126         \EO@twodigits{#1}%
127       \else
128         \QReturnAfterFi{%
129           \EO@reverse#1\@nil{}\EO@afterreverse
130         }%
131       \fi
132     \fi
133   \fi
134 }

```

\QReturnAfterFi An internal help macro to prevent a too deep \if nesting.

```

135 \long\def\QReturnAfterFi#1\fi{\fi#1}

```

\EO@ord \EO@ord prints the number with ord letters.
#1: decimal digits, #1 < 21

```

136 \def\EO@ord#1{%
137   #1%
138   \expandafter\engordletters
139   \ifcase#1{th}\or
140     {st}\or
141     {nd}\or

```

```

142     {rd}\else
143     {th}%
144   \fi
145 }

\EO@twodigits \EO@twodigits expects a number with two digits,
20 < number < 100
146 \def\EO@twodigits#1#2{%
147   #1\EO@ord{#2}%
148 }

\EO@reverse \EO@reverse reverses the digits of the number.
#1: next digit
#2: rest of the digits
#3: already reversed digits
#4: next command to call with the reversed number as argument
149 \def\EO@reverse#1#2\@nil#3#4{%
150   \ifx\#2\%
151     #4{#1#3}%
152   \else
153     \EO@ReturnAfterFi{%
154       \EO@reverse#2\@nil{#1#3}{#4}%
155     }%
156   \fi
157 }

\EO@afterreverse \EO@afterreverse calls \EO@reverseback so that \EO@reverseback can inspect
the digits of the number.
158 \def\EO@afterreverse#1{%
159   \EO@reverseback#1\@nil
160 }

\EO@reverseback \EO@reverseback reverses the reversion.
#1: the last digit of the number
#2: the second last digit of the number
#3: first digits of the number in reversed order, it is not empty, because
\EO@reverseback is only called with numbers > 100.
161 \def\EO@reverseback#1#2#3\@nil{%
162   \EO@reverse#3\@nil{}@\firstofone
163   \ifnum#2#1<21 %
164     \EO@ord{#2#1}%
165   \else
166     #2\EO@ord{#1}%
167   \fi
168 }

      Restore catcode of @.
169 \catcode`@=\EO@atcode
170 
```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/engord.dtx](http://CTAN.mirror/macros/latex/contrib/oberdiek/engord.dtx) The source file.

[CTAN:macros/latex/contrib/oberdiek/engord.pdf](http://CTAN.mirror/macros/latex/contrib/oberdiek/engord.pdf) Documentation.

¹[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

CTAN:macros/latex/contrib/oberdiek/oberdiek-tds.zip

3.2 Bundle installation

Unpacking. Unpack the `oberdiek-tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek-tds.zip -d ~/texmf
```

Script installation. Check the directory `TDSScripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain-T_EX:

```
tex engord.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
engord.sty → tex/generic/oberdiek/engord.sty
engord.pdf → doc/latex/oberdiek/engord.pdf
engord.dtx → source/latex/oberdiek/engord.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your T_EX distribution (teT_EX, mikT_EX, ...) relies on file name databases, you must refresh these. For example, teT_EX users run `texhash` or `mktexlsr`.

3.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk engord.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain-T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{engord.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex engord.dtx
makeindex -s gind.ist engord.idx
pdflatex engord.dtx
makeindex -s gind.ist engord.idx
pdflatex engord.dtx
```

4 History

[2000/05/23 v1.0]

- First public release.

[2003/04/28 v1.1]

- Bug fix for 30, 40, 50, ..., 100, 130, ...
- `\ordletters` renamed to documented `\engordletters`.

[2006/02/20 v1.2]

- Support for plain-T_EX.
- Switch `\ifengordraise` added.
- Package options `raise` and `normal` added.
- DTX framework.

[2007/04/11 v1.3]

- Line ends sanitized.

[2007/04/26 v1.4]

- Use of package `infwarerr`.

5 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
<code>\@</code>	52, 53, 169
<code>\@PackageWarning</code>	103
<code>\@ReturnAfterFi</code>	128, <u>135</u> , 153
<code>\@firstofone</code>	162
<code>\@nil</code>	129, 149, 154, 159, 161, 162
<code>\\\</code>	150
	D
	E
<code>\catcode</code>	3, 4, 5,
	<code>\empty</code>
	12

\endcsname	8, 18, 36, 49, 52, 55, 64, 72, 78, 85, 87, 100, 109	\input	65
\endinput	27	N	
\engord	1, 108	\newcommand	59
\engorderror	2, 100, 120	\newif	69
\engordletters	2, 78, 102, 138	\number	116
\engordnumber	1, 112, 115	P	
\engordraisefalse	2, 74	\PackageInfo	23
\engordraisetrue	2, 70, 75	\ProcessOptions	76
\engordtextsuperscript	81, 85	\ProvidesPackage	50
\EO@afterreverse	129, 158	R	
\EO@atcode	52, 169	\RequirePackage	67
\EO@def	54, 79, 101, 111, 115	\rm	91, 93
\EO@number	116, 118	T	
\EO@ord	123, 136, 147, 164, 166	\textsuperscript	97
\EO@reverse	129, 149, 162	V	
\EO@reverseback	159, 161	\value	112
\EO@twodigits	126, 146	W	
\immediate	20, 38	\write	20, 38
		X	
		x	8, 10, 12, 19, 23, 25, 37, 42, 49