

The `engord` package

Heiko Oberdiek
<heiko.oberdiek at gmail.com>

2010/03/01 v1.8

Abstract

The package generates the suffix of English ordinal numbers. It can be used with plain and \LaTeX formats.

Contents

1	Usage	2
1.1	Package options	2
1.2	Examples	2
2	Implementation	3
2.1	Reload check and identification	3
2.2	Help commands for plain compatibility	4
2.3	User macros	5
2.4	Suffix generation	6
3	Test	8
3.1	Catcode checks for loading	8
4	Installation	9
4.1	Download	9
4.2	Bundle installation	10
4.3	Package installation	10
4.4	Refresh file name databases	10
4.5	Some details for the interested	10
5	History	11
	[2000/05/23 v1.0]	11
	[2003/04/28 v1.1]	11
	[2006/02/20 v1.2]	11
	[2007/04/11 v1.3]	11
	[2007/04/26 v1.4]	11
	[2007/09/09 v1.5]	11
	[2007/09/20 v1.6]	11
	[2008/08/11 v1.7]	11
	[2010/03/01 v1.8]	12
6	Index	12

1 Usage

`\engord{<LATEX counter name>}`

It prints the value of the L^AT_EX counter as English ordinal number. It can be used in the same way as `\arabic`, `\roman`, or `\alph`. The command is not available in plain T_EX.

`\engordnumber{<any TEX number>}`

It prints the number as English ordinal number.

`\engordletters{#1}`

This command formats the English ordinal letters after the number. It defaults to `\textsuperscript`.

`\engorderror{#1}`

It can be redefined, if an other error handling is wanted. The argument is a negative number or zero.

`\engordraisetrue`
`\engordraisefalse`

These commands set the switch `\ifengordraise` that is asked by the default `\engordletters` before raising the ordinal letters.

1.1 Package options

normal: `\engordraisefalse`

raise: `\engordraisetrue`

Default is raise.

1.2 Examples

- `\usepackage[normal]{engord}`
`\engordnumber{1}` → 1st
`\engordnumber{12}` → 12th
`\engordnumber{123}` → 123rd
`\engord{page}` → 1st (if page has the value of one)
`\engordraisetrue`
`\engordnumber{12}` → 12th

- The default output of a counter can be redefined:

```
\newcounter{mycounter}  
\renewcommand{\theengcounter}{\engord{mycounter}}
```

- Because the implementation of `\engord` and `\engordnumber` is kept expandable, these commands can be used to make command names with an appropriate definition of `\engordletters`:

```
\renewcommand*{\engordletters}[1]{#1}  
\@namedef{My\engordnumber{3}Command}{...}
```

This generates the command name ‘\My4rdCommand’. Since version 1.2 the redefinition can be dropped if the letters are not raised.

- If the letters should not be raised, use L^AT_EX package option `normal` or use

```
\engordraisefalse
```

Also `\engordletters` could be redefined for this purpose:

```
\renewcommand*\engordletters}[1]{#1}
```

2 Implementation

2.1 Reload check and identification

```
1 \<package>
```

Reload check, especially if the package is not used with L^AT_EX.

```
2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3 \catcode13=5 % ^~M
4 \endlinechar=13 %
5 \catcode35=6 % #
6 \catcode39=12 % '
7 \catcode44=12 % ,
8 \catcode45=12 % -
9 \catcode46=12 % .
10 \catcode58=12 % :
11 \catcode64=11 % @
12 \catcode123=1 % {
13 \catcode125=2 % }
14 \expandafter\let\expandafter\x\csname ver@engord.sty\endcsname
15 \ifx\x\relax % plain-TEX, first loading
16 \else
17 \def\empty{}%
18 \ifx\x\empty % LATEX, first loading,
19 % variable is initialized, but \ProvidesPackage not yet seen
20 \else
21 \expandafter\ifx\csname PackageInfo\endcsname\relax
22 \def\x#1#2{%
23 \immediate\write-1{Package #1 Info: #2.}%
24 }%
25 \else
26 \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27 \fi
28 \x{engord}{The package is already loaded}%
29 \aftergroup\endinput
30 \fi
31 \fi
32 \endgroup%
```

Package identification:

```
33 \begingroup\catcode61\catcode48\catcode32=10\relax%
34 \catcode13=5 % ^~M
35 \endlinechar=13 %
36 \catcode35=6 % #
37 \catcode39=12 % '
38 \catcode40=12 % (
39 \catcode41=12 % )
40 \catcode44=12 % ,
41 \catcode45=12 % -
42 \catcode46=12 % .
43 \catcode47=12 % /
44 \catcode58=12 % :
45 \catcode64=11 % @
```

```

46 \catcode91=12 % [
47 \catcode93=12 % ]
48 \catcode123=1 % {
49 \catcode125=2 % }
50 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
51   \def\x#1#2#3[#4]{\endgroup
52     \immediate\write-1{Package: #3 #4}%
53     \xdef#1{#4}%
54   }%
55 \else
56   \def\x#1#2[#3]{\endgroup
57     #2[{#3}]%
58     \ifx#1@undefined
59       \xdef#1{#3}%
60     \fi
61     \ifx#1\relax
62       \xdef#1{#3}%
63     \fi
64   }%
65 \fi
66 \expandafter\x\csname ver@engord.sty\endcsname
67 \ProvidesPackage{engord}%
68 [2010/03/01 v1.8 Provides English ordinal numbers (H0)]%

```

2.2 Help commands for plain compatibility

```

69 \begingroup\catcode61\catcode48\catcode32=10\relax%
70 \catcode13=5 % ^^M
71 \endlinechar=13 %
72 \catcode123=1 % {
73 \catcode125=2 % }
74 \catcode64=11 % @
75 \def\x{\endgroup
76   \expandafter\edef\csname EO@AtEnd\endcsname{%
77     \endlinechar=\the\endlinechar\relax
78     \catcode13=\the\catcode13\relax
79     \catcode32=\the\catcode32\relax
80     \catcode35=\the\catcode35\relax
81     \catcode61=\the\catcode61\relax
82     \catcode64=\the\catcode64\relax
83     \catcode123=\the\catcode123\relax
84     \catcode125=\the\catcode125\relax
85   }%
86 }%
87 \x\catcode61\catcode48\catcode32=10\relax%
88 \catcode13=5 % ^^M
89 \endlinechar=13 %
90 \catcode35=6 % #
91 \catcode64=11 % @
92 \catcode123=1 % {
93 \catcode125=2 % }
94 \def\TMP@EnsureCode#1#2{%
95   \edef\EO@AtEnd{%
96     \EO@AtEnd
97     \catcode#1=\the\catcode#1\relax
98   }%
99   \catcode#1=#2\relax
100 }
101 \TMP@EnsureCode{33}{12}% !
102 \TMP@EnsureCode{36}{3}% $
103 \TMP@EnsureCode{39}{12}% '
104 \TMP@EnsureCode{42}{12}% *
105 \TMP@EnsureCode{46}{12}% .

```

```

106 \TMP@EnsureCode{47}{12}% /
107 \TMP@EnsureCode{60}{12}% <
108 \TMP@EnsureCode{91}{12}% [
109 \TMP@EnsureCode{93}{12}% ]
110 \TMP@EnsureCode{94}{7}% ^ (superscript)
111 \TMP@EnsureCode{96}{12}% '
112 \edef\EO@AtEnd{\EO@AtEnd\noexpand\endinput}

\EO@def Definitions, \newcommand does not exist in plain TEX.

113 \begingroup\expandafter\expandafter\expandafter\endgroup
114 \expandafter\ifx\csname newcommand\endcsname\relax
115   \def\EO@def{\def}%
116 \else
117   \def\EO@def#1{%
118     \newcommand*{#1}{}%
119     \def#1%
120   }%
121 \fi

122 \begingroup\expandafter\expandafter\expandafter\endgroup
123 \expandafter\ifx\csname RequirePackage\endcsname\relax
124   \input infwarerr.sty\relax
125   \input ltxcmds.sty\relax
126 \else
127   \RequirePackage{infwarerr}[2007/09/09]%
128   \RequirePackage{ltxcmds}[2010/03/01]%
129 \fi

```

2.3 User macros

\ifengordraise The switch `\ifengordraise`, whether the ordinal letters are raised or not. Default is raised because of compatibility.

```

130 \ltx@newif\ifengordraise
131 \engordraisetrue

```

In L^AT_EX this also can be controlled by option `normal` or `raise`.

```

132 \begingroup\expandafter\expandafter\expandafter\endgroup
133 \expandafter\ifx\csname DeclareOption\endcsname\relax
134 \else
135   \DeclareOption{normal}{\engordraisefalse}%
136   \DeclareOption{raise}{\engordraisetrue}%
137   \ProcessOptions*\relax
138 \fi

```

\engordletters `\engordletters` is called with one argument, the english ordinal letters, and contains the code to format them. It defaults to `\textsuperscript` depending on `\ifengordraise`.

```

139 \expandafter\ifx\csname engordletters\endcsname\relax
140   \EO@def\engordletters{%
141     \ifengordraise
142       \expandafter\engordtextsuperscript
143     \fi
144   }%
145 \fi

```

\engordtextsuperscript For plain T_EX the definition is quite ugly, redefine `\engordtextsuperscript` if you have a better one.

```

146 \expandafter\ifx\csname engordtextsuperscript\endcsname\relax
147   \begingroup\expandafter\expandafter\expandafter\endgroup
148   \expandafter\ifx\csname textsuperscript\endcsname\relax
149     \def\engordtextsuperscript#1{%
150       \relax

```

```

151     \ifmmode
152       ~{\rm#1}%
153     \else
154       $~{\rm#1}$%
155     \fi
156   }%
157 \else
158   \def\engordtextsuperscript{\textsuperscript}%
159 \fi
160 \fi

\engorderror \engorderror is called, if the number is zero or negative.

161 \expandafter\ifx\csname engorderror\endcsname\relax
162   \EO@def\engorderror#1{%
163     #1\engordletters{!ERROR!}%
164     \@PackageWarning{engord}{%
165       ‘#1’ is not an ordinal number%
166     }%
167   }%
168 \fi

\engord \engord expects a LATEX counter name as argument and calls \engordnumber. It
is defined only, if LATEX is used.

169 \begingroup\expandafter\expandafter\expandafter\endgroup
170 \expandafter\ifx\csname newcounter\endcsname\relax
171 \else
172   \EO@def\engord#1{%
173     \engordnumber{\value{#1}}%
174   }%
175 \fi

\engordnumber \engordnumber is the user command to print a number as english ordinal number.
The argument can be any TEX number like explicit numbers, register values, ...
In a safe way it converts the TEX number argument into a form that only
consists of decimal digits.

176 \EO@def\engordnumber#1{%
177   \expandafter\EO@number\expandafter{\number#1}%
178 }
```

2.4 Suffix generation

```

\EO@number \EO@number expects a number with decimal digits as argument and looks at the
size of the number and the count of the digits:

179 \def\EO@number#1{%
180   \ifnum#1<1 % handle the error case
181     \engorderror{#1}%
182   \else
183     \ifnum#1<21 %
184       \EO@ord{#1}%
185     \else
186       \ifnum#1<100 %
187         \EO@twodigits#1%
188       \else
189         \@ReturnAfterFi{%
190           \EO@reverse#1\@nil}\EO@afterreverse
191         }%
192       \fi
193     \fi
194   \fi
195 }
```

```

\@ReturnAfterFi  An internal help macro to prevent a too deep \if nesting.
196 \long\def\@ReturnAfterFi#1\fi{\fi#1}

\EO@ord  \EO@ord prints the number with ord letters.
#1: decimal digits, #1 < 21
197 \def\EO@ord#1{%
198   #1%
199   \expandafter\engordletters
200   \ifcase#1{th}\or
201     {st}\or
202     {nd}\or
203     {rd}\else
204     {th}%
205   \fi
206 }

\EO@twodigits  \EO@twodigits expects a number with two digits,
20 < number < 100
207 \def\EO@twodigits#1#2{%
208   #1\EO@ord{#2}%
209 }

\EO@reverse  \EO@reverse reverses the digits of the number.
#1: next digit
#2: rest of the digits
#3: already reversed digits
#4: next command to call with the reversed number as argument
210 \def\EO@reverse#1#2\@nil#3#4{%
211   \ifx\#2\%
212     #4{#1#3}%
213   \else
214     \@ReturnAfterFi%
215     \EO@reverse#2\@nil{#1#3}{#4}%
216   }%
217   \fi
218 }

\EO@afterreverse  \EO@afterreverse calls \EO@reverseback so that \EO@reverseback can inspect
the digits of the number.
219 \def\EO@afterreverse#1{%
220   \EO@reverseback#1\@nil
221 }

\EO@reverseback  \EO@reverseback reverses the reversion.
#1: the last digit of the number
#2: the second last digit of the number
#3: first digits of the number in reversed order, it is not empty, because
\EO@reverseback is only called with numbers > 100.
222 \def\EO@reverseback#1#2#3\@nil{%
223   \EO@reverse#3\@nil{}\@firstofone
224   \ifnum#2#1<21 %
225     \EO@ord{#2#1}%
226   \else
227     #2\EO@ord{#1}%
228   \fi
229 }

230 \EO@AtEnd%
231 \</package>

```

3 Test

3.1 Catcode checks for loading

```
232 ⟨*test1⟩
233 \catcode'\{=1 %
234 \catcode'\}=2 %
235 \catcode'\#=6 %
236 \catcode'\@=11 %
237 \expandafter\ifx\csname count@\endcsname\relax
238   \countdef\count@=255 %
239 \fi
240 \expandafter\ifx\csname @gobble\endcsname\relax
241   \long\def\@gobble#1{}%
242 \fi
243 \expandafter\ifx\csname @firstofone\endcsname\relax
244   \long\def\@firstofone#1{#1}%
245 \fi
246 \expandafter\ifx\csname loop\endcsname\relax
247   \expandafter\@firstofone
248 \else
249   \expandafter\@gobble
250 \fi
251 {%
252   \def\loop#1\repeat{%
253     \def\body{#1}%
254     \iterate
255   }%
256   \def\iterate{%
257     \body
258     \let\next\iterate
259   \else
260     \let\next\relax
261   \fi
262   \next
263 }%
264 \let\repeat=\fi
265 }%
266 \def\RestoreCatcodes{}
267 \count@=0 %
268 \loop
269   \edef\RestoreCatcodes{%
270     \RestoreCatcodes
271     \catcode\the\count@=\the\catcode\count@\relax
272   }%
273 \ifnum\count@<255 %
274   \advance\count@ 1 %
275 \repeat
276
277 \def\RangeCatcodeInvalid#1#2{%
278   \count@=#1\relax
279   \loop
280     \catcode\count@=15 %
281   \ifnum\count@<#2\relax
282     \advance\count@ 1 %
283   \repeat
284 }
285 \def\RangeCatcodeCheck#1#2#3{%
286   \count@=#1\relax
287   \loop
288     \ifnum#3=\catcode\count@
289     \else
```



```

290     \errmessage{%
291         Character \the\count@\space
292         with wrong catcode \the\catcode\count@\space
293         instead of \number#3%
294     }%
295     \fi
296     \ifnum\count@<#2\relax
297         \advance\count@ 1 %
298     \repeat
299 }
300 \def\space{ }
301 \expandafter\ifx\csname LoadCommand\endcsname\relax
302     \def\LoadCommand{\input engord.sty\relax}%
303 \fi
304 \def\Test{%
305     \RangeCatcodeInvalid{0}{47}%
306     \RangeCatcodeInvalid{58}{64}%
307     \RangeCatcodeInvalid{91}{96}%
308     \RangeCatcodeInvalid{123}{255}%
309     \catcode'\@=12 %
310     \catcode'\=0 %
311     \catcode'\%=14 %
312     \LoadCommand
313     \RangeCatcodeCheck{0}{36}{15}%
314     \RangeCatcodeCheck{37}{37}{14}%
315     \RangeCatcodeCheck{38}{47}{15}%
316     \RangeCatcodeCheck{48}{57}{12}%
317     \RangeCatcodeCheck{58}{63}{15}%
318     \RangeCatcodeCheck{64}{64}{12}%
319     \RangeCatcodeCheck{65}{90}{11}%
320     \RangeCatcodeCheck{91}{91}{15}%
321     \RangeCatcodeCheck{92}{92}{0}%
322     \RangeCatcodeCheck{93}{96}{15}%
323     \RangeCatcodeCheck{97}{122}{11}%
324     \RangeCatcodeCheck{123}{255}{15}%
325     \RestoreCatcodes
326 }
327 \Test
328 \csname @@end\endcsname
329 \end
330 </test1>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/engord.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/engord.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

¹[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain `TEX`:

```
tex engord.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>engord.sty</code>	→ <code>tex/generic/oberdiek/engord.sty</code>
<code>engord.pdf</code>	→ <code>doc/latex/oberdiek/engord.pdf</code>
<code>test/engord-test1.tex</code>	→ <code>doc/latex/oberdiek/test/engord-test1.tex</code>
<code>engord.dtx</code>	→ <code>source/latex/oberdiek/engord.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your `TEX` distribution (te`TEX`, mik`TEX`, ...) relies on file name databases, you must refresh these. For example, te`TEX` users run `texhash` or `mktextlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk engord.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{engord.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex engord.dtx
makeindex -s gind.ist engord.idx
pdflatex engord.dtx
makeindex -s gind.ist engord.idx
pdflatex engord.dtx
```

5 History

[2000/05/23 v1.0]

- First public release, published in newsgroup [de.comp.text.tex](#):
“[Re: Ordinalzahlen in LaTeX?](#)”²

[2003/04/28 v1.1]

- Bug fix for 30, 40, 50, ..., 100, 130, ...
- `\ordletters` renamed to documented `\engordletters`.

[2006/02/20 v1.2]

- Support for plain T_EX.
- Switch `\ifengordraise` added.
- Package options `raise` and `normal` added.
- DTX framework.

[2007/04/11 v1.3]

- Line ends sanitized.

[2007/04/26 v1.4]

- Use of package `infwarerr`.

[2007/09/09 v1.5]

- Catcode section added.

[2007/09/20 v1.6]

- Short description fixed (George White).

[2008/08/11 v1.7]

- Code is not changed.
- URLs updated.

²Url: <http://groups.google.com/group/de.comp.text.tex/msg/738e2cb4c51759d6>

- Compatibility with ini-TeX.

6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
<code>\#</code>	235
<code>\%</code>	311
<code>\@</code>	236, 309
<code>\@PackageWarning</code>	164
<code>\@ReturnAfterFi</code>	189, <u>196</u> , 214
<code>\@firstofone</code>	223, 244, 247
<code>\@gobble</code>	241, 249
<code>\@nil</code>	190, 210, 215, 220, 222, 223
<code>\@undefined</code>	58
<code>\@</code>	211, 310
<code>\{</code>	233
<code>\}</code>	234
A	
<code>\advance</code>	274, 282, 297
<code>\aftergroup</code>	29
B	
<code>\body</code>	253, 257
C	
<code>\catcode</code>	2, 3, 5, 6, 7, 8, 9, 10, 11, 12, 13, 33, 34, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 69, 70, 72, 73, 74, 78, 79, 80, 81, 82, 83, 84, 87, 88, 90, 91, 92, 93, 97, 99, 233, 234, 235, 236, 271, 280, 288, 292, 309, 310, 311
<code>\count@</code>	238, 267, 271, 273, 274, 278, 280, 281, 282, 286, 288, 291, 292, 296, 297
<code>\countdef</code>	238
<code>\csname</code>	14, 21, 50, 66, 76, 114, 123, 133, 139, 146, 148, 161, 170, 237, 240, 243, 246, 301, 328
D	
<code>\DeclareOption</code>	135, 136
E	
<code>\empty</code>	17, 18
<code>\end</code>	329
<code>\endcsname</code>	14, 21, 50, 66, 76, 114, 123, 133, 139, 146, 148, 161, 170, 237, 240, 243, 246, 301, 328
<code>\endinput</code>	29, 112
<code>\endlinechar</code>	4, 35, 71, 77, 89
<code>\engord</code>	2, <u>169</u>
<code>\engorderror</code>	2, <u>161</u> , 181
<code>\engordletters</code>	2, <u>139</u> , 163, 199
<code>\engordnumber</code>	2, 173, <u>176</u>
<code>\engordraisefalse</code>	2, 135
<code>\engordraisetrue</code>	2, 131, 136
<code>\engordtextsuperscript</code>	142, <u>146</u>
<code>\EO@afterreverse</code>	190, <u>219</u>
<code>\EO@AtEnd</code>	95, 96, 112, 230
<code>\EO@def</code>	<u>113</u> , 140, 162, 172, 176
<code>\EO@number</code>	177, <u>179</u>
<code>\EO@ord</code>	184, <u>197</u> , 208, 225, 227
<code>\EO@reverse</code>	190, <u>210</u> , 223
<code>\EO@reverseback</code>	220, <u>222</u>
<code>\EO@twodigits</code>	187, <u>207</u>
<code>\errmessage</code>	290
I	
<code>\ifcase</code>	200
<code>\ifengordraise</code>	<u>130</u> , 141
<code>\ifmmode</code>	151
<code>\ifnum</code>	180, 183, 186, 224, 273, 281, 288, 296
<code>\ifx</code>	15, 18, 21, 50, 58, 61, 114, 123, 133, 139, 146, 148, 161, 170, 211, 237, 240, 243, 246, 301
<code>\immediate</code>	23, 52
<code>\input</code>	124, 125, 302
<code>\iterate</code>	254, 256, 258
L	
<code>\LoadCommand</code>	302, 312
<code>\loop</code>	252, 268, 279, 287
<code>\ltx@newif</code>	130
N	
<code>\newcommand</code>	118
<code>\next</code>	258, 260, 262
<code>\number</code>	177, 293
P	
<code>\PackageInfo</code>	26
<code>\ProcessOptions</code>	137
<code>\ProvidesPackage</code>	19, 67
R	
<code>\RangeCatcodeCheck</code>	285, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324
<code>\RangeCatcodeInvalid</code>	277, 305, 306, 307, 308
<code>\repeat</code>	252, 264, 275, 283, 298
<code>\RequirePackage</code>	127, 128
<code>\RestoreCatcodes</code> ..	266, 269, 270, 325
<code>\rm</code>	152, 154
S	
<code>\space</code>	291, 292, 300

T		V	
\Test	304, 327	\value	173
\textsuperscript	158		
		W	
\the	77, 78, 79,		
	80, 81, 82, 83, 84, 97, 271, 291, 292	\write	23, 52
\TMP@EnsureCode			
	94, 101, 102, 103, 104,	X	
	105, 106, 107, 108, 109, 110, 111	\x 14, 15, 18, 22, 26, 28, 51, 56, 66, 75, 87	