

# The **engord** package

Heiko Oberdiek  
<oberdiek@uni-freiburg.de>

2006/02/20 v1.2

## Abstract

The package generates the suffix of English ordinal numbers. It can be used with plain and L<sup>A</sup>T<sub>E</sub>X formats.

## Contents

<b>1</b>	<b>Usage</b>	<b>1</b>
1.1	Package options . . . . .	2
1.2	Examples . . . . .	2
<b>2</b>	<b>Implementation</b>	<b>2</b>
2.1	Reload check and identification . . . . .	2
2.2	Help commands for plain compatibility . . . . .	3
2.3	User macros . . . . .	4
2.4	Suffix generation . . . . .	5
<b>3</b>	<b>Installation</b>	<b>6</b>
3.1	Some details for the interested . . . . .	7
<b>4</b>	<b>History</b>	<b>7</b>
	[2000/05/23 v1.0] . . . . .	7
	[2003/04/28 v1.1] . . . . .	7
	[2006/02/20 v1.2] . . . . .	7
<b>5</b>	<b>Index</b>	<b>8</b>

## 1 Usage

`\engord{<LATEX counter name>}`

It prints the value of the L<sup>A</sup>T<sub>E</sub>X counter as English ordinal number. It can be used in the same way as `\arabic`, `\roman`, or `\alph`. The command is not available in plain-T<sub>E</sub>X.

`\engordnumber{<any TEX number>}`

It prints the number as English ordinal number.

`\engordletters{#1}`

This command formats the English ordinal letters after the number. It defaults to `\textsuperscript`.

`\engorderror{#1}`

It can be redefined, if an other error handling is wanted. The argument is a negative number or zero.

`\engordraisetrue`  
`\engordraisefalse`

These commands set the switch `\ifengordraise` that is asked by the default `\engordletters` before raising the ordinal letters.

## 1.1 Package options

**normal:** `\engordraisefalse`

**raise:** `\engordraisetrue`

Default is raise.

## 1.2 Examples

- `\usepackage[normal]{engord}`  
`\engordnumber{1}` → 1st  
`\engordnumber{12}` → 12th  
`\engordnumber{123}` → 123rd  
`\engord{page}` → 1st (if page has the value of one)  
`\engordraisetrue`  
`\engordnumber{12}` → 12<sup>th</sup>

- The default output of a counter can be redefined:

```
\newcounter{mycounter}
\renewcommand{\theengcounter}{\engord{mycounter}}
```

- Because the implementation of `\engord` and `\engordnumber` is kept expandable, these commands can be used to make command names with an appropriate definition of `\engordletters`:

```
\renewcommand*{\engordletters}[1]{#1}
\@namedef{My\engordnumber{3}Command}{...}
```

This generates the command name `'\My4rdCommand'`. Since version 1.2 the redefinition can be dropped if the letters are not raised.

- If the letters should not be raised, use L<sup>A</sup>T<sub>E</sub>X package option `normal` or use

```
\engordraisefalse
```

Also `\engordletters` could be redefined for this purpose:

```
\renewcommand*{\engordletters}[1]{#1}
```

# 2 Implementation

## 2.1 Reload check and identification

```
1 <*package>
```

Reload check, especially if the package is not used with L<sup>A</sup>T<sub>E</sub>X.

```
2 \begingroup
```

```
3 \expandafter\let\expandafter\x\csname ver@engord.sty\endcsname
```

```
4 \ifcase 0%
```

```

5   \ifx\x\relax % plain
6   \else
7     \ifx\x\empty % LaTeX
8     \else
9       1%
10    \fi
11  \fi
12 \else
13   \expandafter\ifx\csname PackageInfo\endcsname\relax
14     \def\x#1#2{%
15       \immediate\write-1{Package #1 Info: #2.}%
16     }%
17   \else
18     \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
19   \fi
20   \x{engord}{The package is already loaded}%
21   \endgroup
22   \expandafter\endinput
23 \fi
24 \endgroup

```

Package identification:

```

25 \begingroup
26   \expandafter\ifx\csname ProvidesPackage\endcsname\relax
27     \def\x#1#2#3[#4]{\endgroup
28       \immediate\write-1{Package: #3 #4}%
29       \xdef#1{#4}%
30     }%
31   \else
32     \def\x#1#2[#3]{\endgroup
33       #2[#{#3}]%
34       \ifx#1\relax
35         \xdef#1{#3}%
36       \fi
37     }%
38   \fi
39 \expandafter\x\csname ver@engord.sty\endcsname
40 \ProvidesPackage{engord}%
41 [2006/02/20 v1.2 Provides the ifpdf switch (H0)]

```

## 2.2 Help commands for plain compatibility

`\EO@atcode` Save catcode of @.

```

42 \expandafter\chardef\csname EO@atcode\endcsname\catcode'\@
43 \catcode'\@=11 %

```

`\EO@def` Definitions, `\newcommand` does not exist in plain-TeX.

```

44 \begingroup\expandafter\expandafter\expandafter\endgroup
45 \expandafter\ifx\csname newcommand\endcsname\relax
46   \def\EO@def{\def}%
47 \else
48   \def\EO@def#1{%
49     \newcommand*{#1}{}%
50   \def#1%
51 }%
52 \fi

```

`\EO@PackageWarning`

```

53 \begingroup\expandafter\expandafter\expandafter\endgroup
54 \expandafter\ifx\csname PackageWarning\endcsname\relax
55   \def\EO@PackageWarning#1#2{%
56     \immediate\write16{%
57       Package #1 Warning: #2 on input line \the\inputlineno.%

```

```

58     }%
59 }%
60 \else
61   \def\EO@PackageWarning{\PackageWarning}%
62 \fi

```

## 2.3 User macros

`\ifengordraise` The switch `\ifengordraise`, whether the ordinal letters are raised or not. Default is raised because of compatibility.

```

63 \newif\ifengordraise
64 \engordraisetrue

```

In L<sup>A</sup>T<sub>E</sub>X this also can be controlled by option `normal` or `raise`.

```

65 \begingroup\expandafter\expandafter\expandafter\endgroup
66 \expandafter\ifx\csname DeclareOption\endcsname\relax
67 \else
68   \DeclareOption{normal}{\engordraisefalse}%
69   \DeclareOption{raise}{\engordraisetrue}%
70   \ProcessOptions*\relax
71 \fi

```

`\engordletters` `\engordletters` is called with one argument, the english ordinal letters, and contains the code to format them. It defaults to `\textsuperscript` depending on `\ifengordraise`.

```

72 \expandafter\ifx\csname engordletters\endcsname\relax
73   \EO@def\engordletters{%
74     \ifengordraise
75       \expandafter\engordtextsuperscript
76     \fi
77   }%
78 \fi

```

`\engordtextsuperscript` For plain- $\text{T}_{\text{E}}\text{X}$  the definition is quite ugly, redefine `\engordtextsuperscript` if you have a better one.

```

79 \expandafter\ifx\csname engordtextsuperscript\endcsname\relax
80   \begingroup\expandafter\expandafter\expandafter\endgroup
81   \expandafter\ifx\csname textsuperscript\endcsname\relax
82     \def\engordtextsuperscript#1{%
83       \relax
84       \ifmmode
85         ^{\rm#1}%
86       \else
87         $\sim{\rm#1}$%
88       \fi
89     }%
90   \else
91     \def\engordtextsuperscript{\textsuperscript}%
92   \fi
93 \fi

```

`\engorderror` `\engorderror` is called, if the number is zero or negative.

```

94 \expandafter\ifx\csname engorderror\endcsname\relax
95   \EO@def\engorderror#1{%
96     #1\engordletters{!ERROR!}%
97     \EO@PackageWarning{engord}{%
98       '#1' is not an ordinal number%
99     }%
100   }%
101 \fi

```

`\engord` `\engord` expects a L<sup>A</sup>T<sub>E</sub>X counter name as argument and calls `\engordnumber`. It is defined only, if L<sup>A</sup>T<sub>E</sub>X is used.

```

102 \begingroup\expandafter\expandafter\expandafter\endgroup
103 \expandafter\ifx\csname newcounter\endcsname\relax
104 \else
105   \EO@def\engord#1{%
106     \engordnumber{\value{#1}}%
107   }%
108 \fi

```

`\engordnumber` `\engordnumber` is the user command to print a number as english ordinal number. The argument can be any T<sub>E</sub>X number like explicit numbers, register values, ...

In a safe way it converts the T<sub>E</sub>X number argument into a form that only consists of decimal digits.

```

109 \EO@def\engordnumber#1{%
110   \expandafter\EO@number\expandafter{\number#1}%
111 }

```

## 2.4 Suffix generation

`\EO@number` `\EO@number` expects a number with decimal digits as argument and looks at the size of the number and the count of the digits:

```

112 \def\EO@number#1{%
113   \ifnum#1<1 % handle the error case
114     \engorderror{#1}%
115   \else
116     \ifnum#1<21
117       \EO@ord{#1}%
118     \else
119       \ifnum#1<100
120         \EO@twodigits#1%
121       \else
122         \@ReturnAfterFi{%
123           \EO@reverse#1\@nil{}\EO@afterreverse
124         }%
125       \fi
126     \fi
127   \fi
128 }

```

`\@ReturnAfterFi` An internal help macro to prevent a too deep `\if` nesting.

```

129 \long\def\@ReturnAfterFi#1\fi{\fi#1}

```

`\EO@ord` `\EO@ord` prints the number with ord letters.

#1: decimal digits, #1 < 21

```

130 \def\EO@ord#1{%
131   #1%
132   \expandafter\engordletters
133   \ifcase#1{th}\or
134     {st}\or
135     {nd}\or
136     {rd}\else
137     {th}%
138   \fi
139 }

```

`\EO@twodigits` `\EO@twodigits` expects a number with two digits, 20 < number < 100

```

140 \def\EO@twodigits#1#2{%
141   #1\EO@ord{#2}%
142 }

```

```

\EO@reverse \EO@reverse reverses the digits of the number.
#1: next digit
#2: rest of the digits
#3: already reversed digits
#4: next command to call with the reversed number as argument
143 \def\EO@reverse#1#2\@nil#3#4{%
144   \ifx\#2\%
145     #4{#1#3}%
146   \else
147     \@ReturnAfterFi{%
148       \EO@reverse#2\@nil{#1#3}{#4}%
149     }%
150   \fi
151 }

\EO@afterreverse \EO@afterreverse calls \EO@reverseback so that \EO@reverseback can inspect
the digits of the number.
152 \def\EO@afterreverse#1{%
153   \EO@reverseback#1\@nil
154 }

\EO@reverseback \EO@reverseback reverses the reversion.
#1: the last digit of the number
#2: the second last digit of the number
#3: first digits of the number in reversed order, it is not empty, because
\EO@reverseback is only called with numbers > 100.
155 \def\EO@reverseback#1#2#3\@nil{%
156   \EO@reverse#3\@nil{}\@firstofone
157   \ifnum#2#1<21
158     \EO@ord{#2#1}%
159   \else
160     #2\EO@ord{#1}%
161   \fi
162 }

Restore catcode of @.
163 \catcode'\@=\EO@atcode
164 \end{package}

```

### 3 Installation

**CTAN.** This package is available on CTAN<sup>1</sup>:

[CTAN:macros/latex/contrib/oberdiek/engord.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/engord.pdf](#) Documentation.

**Unpacking.** The .dtx file is a self-extracting docstrip archive. The files are extracted by running the .dtx through plain-TEX:

```
tex engord.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as texmf tree):

```

engord.sty → tex/generic/oberdiek/engord.sty
engord.pdf → doc/latex/oberdiek/engord.pdf
engord.dtx → source/latex/oberdiek/engord.dtx

```

---

<sup>1</sup><http://ftp.ctan.org/tex-archive/>

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

**Refresh file databases.** If your  $\text{T}_{\text{E}}\text{X}$  distribution (`te $\text{T}_{\text{E}}\text{X}$` , `mik $\text{T}_{\text{E}}\text{X}$` , ...) rely on file databases, you must refresh these. For example, `te $\text{T}_{\text{E}}\text{X}$`  users run `texhash` or `mktexlsr`.

### 3.1 Some details for the interested

**Attached source.** The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk engord.pdf unpack_files output .
```

**Unpacking with  $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ .** The `.dtx` chooses its action depending on the format:  
**plain- $\text{T}_{\text{E}}\text{X}$ :** Run `docstrip` and extract the files.

**$\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ :** Generate the documentation.

If you insist on using  $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$  for `docstrip` (really, `docstrip` does not need  $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ ), then inform the autodetect routine about your intension:

```
latex \install=y\input{engord.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdf $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$` :

```
pdflatex engord.dtx
makeindex -s gind.ist engord.idx
pdflatex engord.dtx
makeindex -s gind.ist engord.idx
pdflatex engord.dtx
```

## 4 History

[2000/05/23 v1.0]

- First public release.

[2003/04/28 v1.1]

- Bug fix for 30, 40, 50, ..., 100, 130, ...
- `\ordletters` renamed to documented `\engordletters`.

[2006/02/20 v1.2]

- Support for plain- $\text{T}_{\text{E}}\text{X}$ .
- Switch `\ifengordraise` added.
- Package options `raise` and `normal` added.
- DTX framework.

## 5 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		I	
\@	42, 43, 163	\ifcase	4, 133
\@ReturnAfterFi	122, <u>129</u> , 147	\ifengordraise	<u>63</u> , 74
\@firstofone	156	\ifmmode	84
\@nil	123, 143, 148, 153, 155, 156	\ifnum	113, 116, 119, 157
\\	144	\ifx	5, 7, 13, 26, 34, 45, 54, 66, 72, 79, 81, 94, 103, 144
C		N	
\catcode	42, 43, 163	\immediate	15, 28, 56
\chardef	42	\inputlineno	57
\csname	3, 13, 26, 39, 42, 45, 54, 66, 72, 79, 81, 94, 103	P	
D		\newcommand	49
\DeclareOption	68, 69	\newif	63
E		\number	110
\empty	7	R	
\endcsname	3, 13, 26, 39, 42, 45, 54, 66, 72, 79, 81, 94, 103	\rm	85, 87
\endinput	22	T	
\engord	1, <u>102</u>	\textsuperscript	91
\engorderror	2, <u>94</u> , 114	\the	57
\engordletters	1, <u>72</u> , 96, 132	V	
\engordnumber	1, 106, <u>109</u>	\value	106
\engordraisefalse	2, 68	W	
\engordraisetrue	2, 64, 69	\write	15, 28, 56
\engordtextsuperscript	75, <u>79</u>	X	
\EO@afterreverse	123, <u>152</u>	\x	3, 5, 7, 14, 18, 20, 27, 32, 39
\EO@atcode	<u>42</u> , 163		
\EO@def	<u>44</u> , 73, 95, 105, 109		
\EO@number	110, <u>112</u>		
\EO@ord	117, <u>130</u> , 141, 158, 160		
\EO@PackageWarning	53, 97		
\EO@reverse	123, <u>143</u> , 156		
\EO@reverseback	153, <u>155</u>		
\EO@twodigits	120, <u>140</u>		