

The `engord` package

Heiko Oberdiek
<oberdiek@uni-freiburg.de>

2007/09/20 v1.6

Abstract

The package generates the suffix of English ordinal numbers. It can be used with plain and L^AT_EX formats.

Contents

1	Usage	1
1.1	Package options	2
1.2	Examples	2
2	Implementation	3
2.1	Reload check and identification	3
2.2	Help commands for plain compatibility	3
2.3	User macros	4
2.4	Suffix generation	5
3	Test	7
3.1	Catcode checks for loading	7
4	Installation	8
4.1	Download	8
4.2	Bundle installation	8
4.3	Package installation	8
4.4	Refresh file name databases	8
4.5	Some details for the interested	9
5	History	9
	[2000/05/23 v1.0]	9
	[2003/04/28 v1.1]	9
	[2006/02/20 v1.2]	9
	[2007/04/11 v1.3]	9
	[2007/04/26 v1.4]	10
	[2007/09/09 v1.5]	10
	[2007/09/20 v1.6]	10
6	Index	10

1 Usage

<code>\engord{<L^AT_EX counter name>}</code>
--

It prints the value of the L^AT_EX counter as English ordinal number. It can be used in the same way as `\arabic`, `\roman`, or `\alph`. The command is not available in plain-T_EX.

`\engordnumber {⟨any TEX number⟩}`

It prints the number as English ordinal number.

`\engordletters {#1}`

This command formats the English ordinal letters after the number. It defaults to `\textsuperscript`.

`\engorderror {#1}`

It can be redefined, if an other error handling is wanted. The argument is a negative number or zero.

`\engordraisetrue`
`\engordraisefalse`

These commands set the switch `\ifengordraise` that is asked by the default `\engordletters` before raising the ordinal letters.

1.1 Package options

normal: `\engordraisefalse`

raise: `\engordraisetrue`

Default is `raise`.

1.2 Examples

- `\usepackage[normal]{engord}`
`\engordnumber{1}` → 1st
`\engordnumber{12}` → 12th
`\engordnumber{123}` → 123rd
`\engord{page}` → 1st (if page has the value of one)
`\engordraisetrue`
`\engordnumber{12}` → 12th

- The default output of a counter can be redefined:

```
\newcounter{mycounter}  
\renewcommand{\theengcounter}{\engord{mycounter}}
```

- Because the implementation of `\engord` and `\engordnumber` is kept expandable, these commands can be used to make command names with an appropriate definition of `\engordletters`:

```
\renewcommand*{\engordletters}[1]{#1}  
\@namedef{My\engordnumber{3}Command}{...}
```

This generates the command name ‘`\My4rdCommand`’. Since version 1.2 the redefinition can be dropped if the letters are not raised.

- If the letters should not be raised, use L^AT_EX package option `normal` or use

```
\engordraisefalse
```

Also `\engordletters` could be redefined for this purpose:

```
\renewcommand*{\engordletters}[1]{#1}
```

2 Implementation

2.1 Reload check and identification

```
1 (*package)
```

Reload check, especially if the package is not used with L^AT_EX.

```
2 \begingroup
3   \catcode44 12 % ,
4   \catcode45 12 % -
5   \catcode46 12 % .
6   \catcode58 12 % :
7   \catcode64 11 % @
8   \expandafter\let\expandafter\x\csname ver@engord.sty\endcsname
9   \ifcase 0%
10    \ifx\x\relax % plain
11    \else
12      \ifx\x\empty % LaTeX
13      \else
14        1%
15      \fi
16    \fi
17  \else
18    \expandafter\ifx\csname PackageInfo\endcsname\relax
19      \def\x#1#2{%
20        \immediate\write-1{Package #1 Info: #2.}%
21      }%
22    \else
23      \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
24    \fi
25    \x{engord}{The package is already loaded}%
26  \endgroup
27  \expandafter\endinput
28  \fi
29 \endgroup
```

Package identification:

```
30 \begingroup
31   \catcode40 12 % (
32   \catcode41 12 % )
33   \catcode44 12 % ,
34   \catcode45 12 % -
35   \catcode46 12 % .
36   \catcode47 12 % /
37   \catcode58 12 % :
38   \catcode64 11 % @
39   \expandafter\ifx\csname ProvidesPackage\endcsname\relax
40     \def\x#1#2#3[#4]{\endgroup
41       \immediate\write-1{Package: #3 #4}%
42       \xdef#1{#4}%
43     }%
44   \else
45     \def\x#1#2[#3]{\endgroup
46       #2[{#3}]%
47       \ifx#1\relax
48         \xdef#1{#3}%
49       \fi
50     }%
51   \fi
52   \expandafter\x\csname ver@engord.sty\endcsname
53   \ProvidesPackage{engord}%
54   [2007/09/20 v1.6 Provides English ordinal numbers (H0)]
```

2.2 Help commands for plain compatibility

```

55 \expandafter\edef\csname EO@AtEnd\endcsname{%
56   \catcode64 \the\catcode64\relax
57 }
58 \catcode64 11 % @
59 \def\TMP@EnsureCode#1#2{%
60   \edef\EO@AtEnd{%
61     \EO@AtEnd
62     \catcode#1 \the\catcode#1\relax
63   }%
64   \catcode#1 #2\relax
65 }
66 \TMP@EnsureCode{33}{12}% !
67 \TMP@EnsureCode{36}{3}% $
68 \TMP@EnsureCode{39}{12}% '
69 \TMP@EnsureCode{42}{12}% *
70 \TMP@EnsureCode{46}{12}% .
71 \TMP@EnsureCode{47}{12}% /
72 \TMP@EnsureCode{60}{12}% <
73 \TMP@EnsureCode{94}{7}% ^ (superscript)
74 \TMP@EnsureCode{96}{12}% ‘

```

\EO@def Definitions, \newcommand does not exist in plain-TeX.

```

75 \begingroup\expandafter\expandafter\expandafter\endgroup
76 \expandafter\ifx\csname newcommand\endcsname\relax
77   \def\EO@def{\def}%
78 \else
79   \def\EO@def#1{%
80     \newcommand*{#1}{}%
81     \def#1%
82   }%
83 \fi

84 \begingroup\expandafter\expandafter\expandafter\endgroup
85 \expandafter\ifx\csname RequirePackage\endcsname\relax
86   \input infwarerr.sty\relax
87 \else
88   \RequirePackage{infwarerr}[2007/09/09]%
89 \fi

```

2.3 User macros

\ifengordraise The switch \ifengordraise, whether the ordinal letters are raised or not. Default is raised because of compatibility.

```

90 \newif\ifengordraise
91 \engordraisetrue

```

In L^AT_EX this also can be controlled by option normal or raise.

```

92 \begingroup\expandafter\expandafter\expandafter\endgroup
93 \expandafter\ifx\csname DeclareOption\endcsname\relax
94 \else
95   \DeclareOption{normal}{\engordraisefalse}%
96   \DeclareOption{raise}{\engordraisetrue}%
97   \ProcessOptions*\relax
98 \fi

```

\engordletters \engordletters is called with one argument, the english ordinal letters, and contains the code to format them. It defaults to \textsuperscript depending on \ifengordraise.

```

99 \expandafter\ifx\csname engordletters\endcsname\relax
100 \EO@def\engordletters{%
101   \ifengordraise
102     \expandafter\engordtextsuperscript

```

```

103   \fi
104 }%
105 \fi

```

`\engordtextsuperscript` For plain- \TeX the definition is quite ugly, redefine `\engordtextsuperscript` if you have a better one.

```

106 \expandafter\ifx\csname engordtextsuperscript\endcsname\relax
107   \begingroup\expandafter\expandafter\expandafter\endgroup
108   \expandafter\ifx\csname textsuperscript\endcsname\relax
109     \def\engordtextsuperscript#1{%
110       \relax
111       \ifmode
112         ^{\rm#1}%
113       \else
114         $\sim{\rm#1}$%
115       \fi
116     }%
117   \else
118     \def\engordtextsuperscript{\textsuperscript}%
119   \fi
120 \fi

```

`\engorderror` `\engorderror` is called, if the number is zero or negative.

```

121 \expandafter\ifx\csname engorderror\endcsname\relax
122   \EO@def\engorderror#1{%
123     #1\engordletters{!ERROR!}%
124     \@PackageWarning{engord}{%
125       ‘#1’ is not an ordinal number%
126     }%
127   }%
128 \fi

```

`\engord` `\engord` expects a \LaTeX counter name as argument and calls `\engordnumber`. It is defined only, if \LaTeX is used.

```

129 \begingroup\expandafter\expandafter\expandafter\endgroup
130 \expandafter\ifx\csname newcounter\endcsname\relax
131 \else
132   \EO@def\engord#1{%
133     \engordnumber{\value{#1}}%
134   }%
135 \fi

```

`\engordnumber` `\engordnumber` is the user command to print a number as english ordinal number. The argument can be any \TeX number like explicit numbers, register values, ...

In a safe way it converts the \TeX number argument into a form that only consists of decimal digits.

```

136 \EO@def\engordnumber#1{%
137   \expandafter\EO@number\expandafter{\number#1}%
138 }

```

2.4 Suffix generation

`\EO@number` `\EO@number` expects a number with decimal digits as argument and looks at the size of the number and the count of the digits:

```

139 \def\EO@number#1{%
140   \ifnum#1<1 % handle the error case
141     \engorderror{#1}%
142   \else
143     \ifnum#1<21 %
144       \EO@ord{#1}%
145     \else

```

```

146     \ifnum#1<100 %
147         \EO@twodigits#1%
148     \else
149         \@ReturnAfterFi{%
150             \EO@reverse#1\@nil{}\EO@afterreverse
151         }%
152     \fi
153 \fi
154 \fi
155 }

```

\@ReturnAfterFi An internal help macro to prevent a too deep \if nesting.

```

156 \long\def\@ReturnAfterFi#1\fi{\fi#1}

```

\EO@ord \EO@ord prints the number with ord letters.

#1: decimal digits, #1 < 21

```

157 \def\EO@ord#1{%
158     #1%
159     \expandafter\engordletters
160     \ifcase#1{th}\or
161         {st}\or
162         {nd}\or
163         {rd}\else
164         {th}%
165     \fi
166 }

```

\EO@twodigits \EO@twodigits expects a number with two digits,
20 < number < 100

```

167 \def\EO@twodigits#1#2{%
168     #1\EO@ord{#2}%
169 }

```

\EO@reverse \EO@reverse reverses the digits of the number.

#1: next digit

#2: rest of the digits

#3: already reversed digits

#4: next command to call with the reversed number as argument

```

170 \def\EO@reverse#1#2\@nil#3#4{%
171     \ifx\#2\%
172         #4{#1#3}%
173     \else
174         \@ReturnAfterFi{%
175             \EO@reverse#2\@nil{#1#3}{#4}%
176         }%
177     \fi
178 }

```

\EO@afterreverse \EO@afterreverse calls \EO@reverseback so that \EO@reverseback can inspect the digits of the number.

```

179 \def\EO@afterreverse#1{%
180     \EO@reverseback#1\@nil
181 }

```

\EO@reverseback \EO@reverseback reverses the reversion.

#1: the last digit of the number

#2: the second last digit of the number

#3: first digits of the number in reversed order, it is not empty, because
\EO@reverseback is only called with numbers > 100.

```

182 \def\EO@reverseback#1#2#3\@nil{%
183     \EO@reverse#3\@nil{}\@firstofone

```

```

184 \ifnum#2#1<21 %
185   \E0@ord{#2#1}%
186 \else
187   #2\E0@ord{#1}%
188 \fi
189 }

190 \E0@AtEnd
191 \end{package}

```

3 Test

3.1 Catcode checks for loading

```

192 \test1
193 \catcode'\@=11 %
194 \def\RestoreCatcodes{}
195 \count@=0 %
196 \loop
197   \edef\RestoreCatcodes{%
198     \RestoreCatcodes
199     \catcode\the\count@=\the\catcode\count@\relax
200   }%
201 \ifnum\count@<255 %
202   \advance\count@\@ne
203 \repeat
204
205 \def\RangeCatcodeInvalid#1#2{%
206   \count@=#1\relax
207   \loop
208     \catcode\count@=15 %
209     \ifnum\count@<#2\relax
210       \advance\count@\@ne
211     \repeat
212 }
213 \def\Test{%
214   \RangeCatcodeInvalid{0}{47}%
215   \RangeCatcodeInvalid{58}{64}%
216   \RangeCatcodeInvalid{91}{96}%
217   \RangeCatcodeInvalid{123}{255}%
218   \catcode'\@=12 %
219   \catcode'\=0 %
220   \catcode'\{=1 %
221   \catcode'\}=2 %
222   \catcode'\#=6 %
223   \catcode'\[=12 %
224   \catcode'\]=12 %
225   \catcode'\%=14 %
226   \catcode'\ =10 %
227   \catcode13=5 %
228   \input engord.sty\relax
229   \RestoreCatcodes
230 }
231 \Test
232 \csname @@end\endcsname
233 \end
234 \test1

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/engord.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/engord.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:macros/latex/contrib/oberdiek/oberdiek-tds.zip](#)

TDS refers to the standard “A Directory Structure for \TeX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek-tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek-tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain- \TeX :

```
tex engord.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>engord.sty</code>	\rightarrow <code>tex/generic/oberdiek/engord.sty</code>
<code>engord.pdf</code>	\rightarrow <code>doc/latex/oberdiek/engord.pdf</code>
<code>test/engord-test1.tex</code>	\rightarrow <code>doc/latex/oberdiek/test/engord-test1.tex</code>
<code>engord.dtx</code>	\rightarrow <code>source/latex/oberdiek/engord.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your \TeX distribution (te \TeX , mi \TeX , ...) relies on file name databases, you must refresh these. For example, te \TeX users run `texhash` or `mktextlsr`.

¹<http://ftp.ctan.org/tex-archive/>

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk engord.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain-T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{engord.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex engord.dtx
makeindex -s gind.ist engord.idx
pdflatex engord.dtx
makeindex -s gind.ist engord.idx
pdflatex engord.dtx
```

5 History

[2000/05/23 v1.0]

- First public release.

[2003/04/28 v1.1]

- Bug fix for 30, 40, 50, ..., 100, 130, ...
- `\ordletters` renamed to documented `\engordletters`.

[2006/02/20 v1.2]

- Support for plain-T_EX.
- Switch `\ifengordraise` added.
- Package options `raise` and `normal` added.
- DTX framework.

[2007/04/11 v1.3]

- Line ends sanitized.

[2007/04/26 v1.4]

- Use of package infwarerr.

[2007/09/09 v1.5]

- Catcode section added.

[2007/09/20 v1.6]

- Short description fixed (George White).

6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
<code>\#</code>	222
<code>\%</code>	225
<code>\@</code>	193, 218
<code>\@PackageWarning</code>	124
<code>\@ReturnAfterFi</code>	149, 156, 174
<code>\@firstofone</code>	183
<code>\@one</code>	202, 210
<code>\@nil</code>	150, 170, 175, 180, 182, 183
<code>\[</code>	223
<code>\</code>	171, 219
<code>\{</code>	220
<code>\}</code>	221
<code>\]</code>	224
<code>_</code>	226
A	
<code>\advance</code>	202, 210
C	
<code>\catcode</code>	3, 4, 5, 6, 7, 31, 32, 33, 34, 35, 36, 37, 38, 56, 58, 62, 64, 193, 199, 208, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227
<code>\count@</code>	195, 199, 201, 202, 206, 208, 209, 210
<code>\csname</code>	8, 18, 39, 52, 55, 76, 85, 93, 99, 106, 108, 121, 130, 232
D	
<code>\DeclareOption</code>	95, 96
E	
<code>\empty</code>	12
<code>\end</code>	233
<code>\endcsname</code> ...	8, 18, 39, 52, 55, 76, 85, 93, 99, 106, 108, 121, 130, 232
<code>\endinput</code>	27
<code>\engord</code>	1, 129
<code>\engorderror</code>	2, 121, 141
<code>\engordletters</code>	2, 99, 123, 159
<code>\engordnumber</code>	2, 133, 136
<code>\engordraisefalse</code>	2, 95
<code>\engordraisetrue</code>	2, 91, 96
<code>\engordtextsuperscript</code>	102, 106
<code>\EO@afterreverse</code>	150, 179
<code>\EO@AtEnd</code>	60, 61, 190
<code>\EO@def</code>	75, 100, 122, 132, 136
<code>\EO@number</code>	137, 139
<code>\EO@ord</code>	144, 157, 168, 185, 187
<code>\EO@reverse</code>	150, 170, 183
<code>\EO@reverseback</code>	180, 182
<code>\EO@twodigits</code>	147, 167
I	
<code>\ifcase</code>	9, 160
<code>\ifengordraise</code>	90, 101
<code>\ifmmode</code>	111
<code>\ifnum</code>	140, 143, 146, 184, 201, 209
<code>\ifx</code>	10, 12, 18, 39, 47, 76, 85, 93, 99, 106, 108, 121, 130, 171
<code>\immediate</code>	20, 41
<code>\input</code>	86, 228
L	
<code>\loop</code>	196, 207
N	
<code>\newcommand</code>	80
<code>\newif</code>	90
<code>\number</code>	137
P	
<code>\PackageInfo</code>	23
<code>\ProcessOptions</code>	97
<code>\ProvidesPackage</code>	53
R	
<code>\RangeCatcodeInvalid</code>	205, 214, 215, 216, 217
<code>\repeat</code>	203, 211
<code>\RequirePackage</code>	88
<code>\RestoreCatcodes</code> ..	194, 197, 198, 229
<code>\rm</code>	112, 114

T	V
\Test	\value 133
\textsuperscript	W
\the	\write 20, 41
\TMP@EnsureCode	X
66, 67, 68, 69, 70, 71, 72, 73, 74	\x 8, 10, 12, 19, 23, 25, 40, 45, 52