

The engord package

Heiko Oberdiek

<heiko.oberdiek at gmail.com>

2010/03/01 v1.8

Abstract

The package generates the suffix of English ordinal numbers. It can be used with plain and L^AT_EX formats.

Contents

1	Usage	2
1.1	Package options	2
1.2	Examples	2
2	Implementation	3
2.1	Reload check and identification	3
2.2	Help commands for plain compatibility	4
2.3	User macros	5
2.4	Suffix generation	6
3	Test	8
3.1	Catcode checks for loading	8
4	Installation	10
4.1	Download	10
4.2	Bundle installation	10
4.3	Package installation	10
4.4	Refresh file name databases	11
4.5	Some details for the interested	11
5	Catalogue	12
6	History	12
	[2000/05/23 v1.0]	12
	[2003/04/28 v1.1]	12
	[2006/02/20 v1.2]	12
	[2007/04/11 v1.3]	13
	[2007/04/26 v1.4]	13
	[2007/09/09 v1.5]	13
	[2007/09/20 v1.6]	13
	[2008/08/11 v1.7]	13
	[2010/03/01 v1.8]	13
7	Index	13

1 Usage

`\engord{<LATEX counter name>}`

It prints the value of the L^AT_EX counter as English ordinal number. It can be used in the same way as `\arabic`, `\roman`, or `\alph`. The command is not available in plain T_EX.

`\engordnumber{<any TEX number>}`

It prints the number as English ordinal number.

`\engordletters{#1}`

This command formats the English ordinal letters after the number. It defaults to `\textsuperscript`.

`\engorderror{#1}`

It can be redefined, if an other error handling is wanted. The argument is a negative number or zero.

`\engordraisetrue`
`\engordraisefalse`

These commands set the switch `\ifengordraise` that is asked by the default `\engordletters` before raising the ordinal letters.

1.1 Package options

normal: `\engordraisefalse`

raise: `\engordraisetrue`

Default is raise.

1.2 Examples

- ```
\usepackage[normal]{engord}
\engordnumber{1} → 1st
\engordnumber{12} → 12th
\engordnumber{123} → 123rd
\engord{page} → 1st (if page has the value of one)
\engordraisetrue
\engordnumber{12} → 12th
```
- The default output of a counter can be redefined:

```
\newcounter{mycounter}
\renewcommand{\theengcounter}{\engord{mycounter}}
```
- Because the implementation of `\engord` and `\engordnumber` is kept expandable, these commands can be used to make command names with an appropriate definition of `\engordletters`:

```

\renewcommand*{\engordletters}[1]{#1}
\@namedef{My\engordnumber{3}Command}{...}

```

This generates the command name ‘\My4rdCommand’. Since version 1.2 the redefinition can be dropped if the letters are not raised.

- If the letters should not be raised, use L<sup>A</sup>T<sub>E</sub>X package option `normal` or use

```
\engordraisefalse
```

Also `\engordletters` could be redefined for this purpose:

```
\renewcommand*{\engordletters}[1]{#1}
```

## 2 Implementation

### 2.1 Reload check and identification

```
1 \<{*package}
```

Reload check, especially if the package is not used with L<sup>A</sup>T<sub>E</sub>X.

```

2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3 \catcode13=5 % ^M
4 \endlinechar=13 %
5 \catcode35=6 % #
6 \catcode39=12 % '
7 \catcode44=12 % ,
8 \catcode45=12 % -
9 \catcode46=12 % .
10 \catcode58=12 % :
11 \catcode64=11 % @
12 \catcode123=1 % {
13 \catcode125=2 % }
14 \expandafter\let\expandafter\x\csname ver@engord.sty\endcsname
15 \ifx\x\relax % plain-TeX, first loading
16 \else
17 \def\empty{}%
18 \ifx\x\empty % LaTeX, first loading,
19 % variable is initialized, but \ProvidesPackage not yet seen
20 \else
21 \expandafter\ifx\csname PackageInfo\endcsname\relax
22 \def\x#1#2{%
23 \immediate\write-1{Package #1 Info: #2.}%
24 }%
25 \else
26 \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27 \fi
28 \x{engord}{The package is already loaded}%
29 \aftergroup\endinput
30 \fi
31 \fi
32 \endgroup%

```

Package identification:

```

33 \begingroup\catcode61\catcode48\catcode32=10\relax%
34 \catcode13=5 % ^M
35 \endlinechar=13 %
36 \catcode35=6 % #
37 \catcode39=12 % '

```

```

38 \catcode40=12 % (
39 \catcode41=12 %)
40 \catcode44=12 % ,
41 \catcode45=12 % -
42 \catcode46=12 % .
43 \catcode47=12 % /
44 \catcode58=12 % :
45 \catcode64=11 % @
46 \catcode91=12 % [
47 \catcode93=12 %]
48 \catcode123=1 % {
49 \catcode125=2 % }
50 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
51 \def\x#1#2#3[#4]{\endgroup
52 \immediate\write-1{Package: #3 #4}%
53 \xdef#1[#4}%
54 }%
55 \else
56 \def\x#1#2[#3]{\endgroup
57 #2[#{#3}]%
58 \ifx#1\@undefined
59 \xdef#1[#3}%
60 \fi
61 \ifx#1\relax
62 \xdef#1[#3}%
63 \fi
64 }%
65 \fi
66 \expandafter\x\csname ver@engord.sty\endcsname
67 \ProvidesPackage{engord}%
68 [2010/03/01 v1.8 Provides English ordinal numbers (H0)]%

```

## 2.2 Help commands for plain compatibility

```

69 \begingroup\catcode61\catcode48\catcode32=10\relax%
70 \catcode13=5 % ^M
71 \endlinechar=13 %
72 \catcode123=1 % {
73 \catcode125=2 % }
74 \catcode64=11 % @
75 \def\x{\endgroup
76 \expandafter\edef\csname EO@AtEnd\endcsname{%
77 \endlinechar=\the\endlinechar\relax
78 \catcode13=\the\catcode13\relax
79 \catcode32=\the\catcode32\relax
80 \catcode35=\the\catcode35\relax
81 \catcode61=\the\catcode61\relax
82 \catcode64=\the\catcode64\relax
83 \catcode123=\the\catcode123\relax
84 \catcode125=\the\catcode125\relax
85 }%
86 }%
87 \x\catcode61\catcode48\catcode32=10\relax%
88 \catcode13=5 % ^M
89 \endlinechar=13 %
90 \catcode35=6 % #
91 \catcode64=11 % @
92 \catcode123=1 % {
93 \catcode125=2 % }

```

```

94 \def\TMP@EnsureCode#1#2{%
95 \edef\EO@AtEnd{%
96 \EO@AtEnd
97 \catcode#1=\the\catcode#1\relax
98 }%
99 \catcode#1=#2\relax
100 }
101 \TMP@EnsureCode{33}{12}% !
102 \TMP@EnsureCode{36}{3}% $
103 \TMP@EnsureCode{39}{12}% '
104 \TMP@EnsureCode{42}{12}% *
105 \TMP@EnsureCode{46}{12}% .
106 \TMP@EnsureCode{47}{12}% /
107 \TMP@EnsureCode{60}{12}% <
108 \TMP@EnsureCode{91}{12}% [
109 \TMP@EnsureCode{93}{12}%]
110 \TMP@EnsureCode{94}{7}% ^ (superscript)
111 \TMP@EnsureCode{96}{12}% '
112 \edef\EO@AtEnd{\EO@AtEnd\noexpand\endinput}
\EO@def Definitions, \newcommand does not exist in plain TEX.
113 \begingroup\expandafter\expandafter\expandafter\endgroup
114 \expandafter\ifx\csname newcommand\endcsname\relax
115 \def\EO@def{\def}%
116 \else
117 \def\EO@def#1{%
118 \newcommand*{#1}{}%
119 \def#1%
120 }%
121 \fi

122 \begingroup\expandafter\expandafter\expandafter\endgroup
123 \expandafter\ifx\csname RequirePackage\endcsname\relax
124 \input infwarerr.sty\relax
125 \input ltxcmds.sty\relax
126 \else
127 \RequirePackage{infwarerr}[2007/09/09]%
128 \RequirePackage{ltxcmds}[2010/03/01]%
129 \fi

```

## 2.3 User macros

`\ifengordraise` The switch `\ifengordraise`, whether the ordinal letters are raised or not. Default is raised because of compatibility.

```

130 \ltx@newif\ifengordraise
131 \engordraisetrue

```

In L<sup>A</sup>T<sub>E</sub>X this also can be controlled by option `normal` or `raise`.

```

132 \begingroup\expandafter\expandafter\expandafter\endgroup
133 \expandafter\ifx\csname DeclareOption\endcsname\relax
134 \else
135 \DeclareOption{normal}{\engordraisefalse}%
136 \DeclareOption{raise}{\engordraisetrue}%
137 \ProcessOptions*\relax
138 \fi

```

`\engordletters` `\engordletters` is called with one argument, the english ordinal letters, and contains the code to format them. It defaults to `\textsuperscript` depending on `\ifengordraise`.

```

139 \expandafter\ifx\csname engordletters\endcsname\relax
140 \EO@def\engordletters{%
141 \ifengordraise
142 \expandafter\engordtextsuperscript
143 \fi
144 }%
145 \fi

```

`\engordtextsuperscript` For plain T<sub>E</sub>X the definition is quite ugly, redefine `\engordtextsuperscript` if you have a better one.

```

146 \expandafter\ifx\csname engordtextsuperscript\endcsname\relax
147 \begingroup\expandafter\expandafter\expandafter\endgroup
148 \expandafter\ifx\csname textsuperscript\endcsname\relax
149 \def\engordtextsuperscript#1{%
150 \relax
151 \ifmmode
152 ^{\rm#1}%
153 \else
154 $\rm#1$%
155 \fi
156 }%
157 \else
158 \def\engordtextsuperscript{\textsuperscript}%
159 \fi
160 \fi

```

`\engorderror` `\engorderror` is called, if the number is zero or negative.

```

161 \expandafter\ifx\csname engorderror\endcsname\relax
162 \EO@def\engorderror#1{%
163 #1\engordletters{!ERROR!}%
164 \@PackageWarning{engord}{%
165 ‘#1’ is not an ordinal number%
166 }%
167 }%
168 \fi

```

`\engord` `\engord` expects a L<sup>A</sup>T<sub>E</sub>X counter name as argument and calls `\engordnumber`. It is defined only, if L<sup>A</sup>T<sub>E</sub>X is used.

```

169 \begingroup\expandafter\expandafter\expandafter\endgroup
170 \expandafter\ifx\csname newcounter\endcsname\relax
171 \else
172 \EO@def\engord#1{%
173 \engordnumber{\value{#1}}%
174 }%
175 \fi

```

`\engordnumber` `\engordnumber` is the user command to print a number as english ordinal number. The argument can be any T<sub>E</sub>X number like explicit numbers, register values, ...

In a safe way it converts the T<sub>E</sub>X number argument into a form that only consists of decimal digits.

```

176 \EO@def\engordnumber#1{%
177 \expandafter\EO@number\expandafter{\number#1}%
178 }

```

## 2.4 Suffix generation

`\EO@number` `\EO@number` expects a number with decimal digits as argument and looks at the size of the number and the count of the digits:

```

179 \def\EO@number#1{%
180 \ifnum#1<1 % handle the error case
181 \engorderror{#1}%
182 \else
183 \ifnum#1<21 %
184 \EO@ord{#1}%
185 \else
186 \ifnum#1<100 %
187 \EO@twodigits#1%
188 \else
189 \@ReturnAfterFi{%
190 \EO@reverse#1\@nil{}}\EO@afterreverse
191 }%
192 \fi
193 \fi
194 \fi
195 }

```

`\@ReturnAfterFi` An internal help macro to prevent a too deep `\if` nesting.

```

196 \long\def\@ReturnAfterFi#1\fi{\fi#1}

```

`\EO@ord` `\EO@ord` prints the number with ord letters.

**#1:** decimal digits,  $\#1 < 21$

```

197 \def\EO@ord#1{%
198 #1%
199 \expandafter\engordletters
200 \ifcase#1{th}\or
201 {st}\or
202 {nd}\or
203 {rd}\else
204 {th}%
205 \fi
206 }

```

`\EO@twodigits` `\EO@twodigits` expects a number with two digits,

$20 < \text{number} < 100$

```

207 \def\EO@twodigits#1#2{%
208 #1\EO@ord{#2}%
209 }

```

`\EO@reverse` `\EO@reverse` reverses the digits of the number.

**#1:** next digit

**#2:** rest of the digits

**#3:** already reversed digits

**#4:** next command to call with the reversed number as argument

```

210 \def\EO@reverse#1#2\@nil#3#4{%
211 \ifx\#2\%
212 #4{#1#3}%
213 \else
214 \@ReturnAfterFi{%
215 \EO@reverse#2\@nil{#1#3}{#4}%
216 }%
217 \fi
218 }

```

`\EO@afterreverse` `\EO@afterreverse` calls `\EO@reverseback` so that `\EO@reverseback` can inspect the digits of the number.

```

219 \def\EO@afterreverse#1{%
220 \EO@reverseback#1\@nil
221 }

\EO@reverseback \EO@reverseback reverses the reversion.
#1: the last digit of the number
#2: the second last digit of the number
#3: first digits of the number in reversed order, it is not empty, because
\EO@reverseback is only called with numbers > 100.
222 \def\EO@reverseback#1#2#3\@nil{%
223 \EO@reverse#3\@nil{}\@firstofone
224 \ifnum#2#1<21 %
225 \EO@ord{#2#1}%
226 \else
227 #2\EO@ord{#1}%
228 \fi
229 }

230 \EO@AtEnd%
231 \</package>

```

### 3 Test

#### 3.1 Catcode checks for loading

```

232 \<test1>
233 \catcode'\{=1 %
234 \catcode'\}=2 %
235 \catcode'\#=6 %
236 \catcode'\@=11 %
237 \expandafter\ifx\csname count@\endcsname\relax
238 \countdef\count@=255 %
239 \fi
240 \expandafter\ifx\csname @gobble\endcsname\relax
241 \long\def\@gobble#1{%
242 \fi
243 \expandafter\ifx\csname @firstofone\endcsname\relax
244 \long\def\@firstofone#1{#1}%
245 \fi
246 \expandafter\ifx\csname loop\endcsname\relax
247 \expandafter\@firstofone
248 \else
249 \expandafter\@gobble
250 \fi
251 {%
252 \def\loop#1\repeat{%
253 \def\body{#1}%
254 \iterate
255 }%
256 \def\iterate{%
257 \body
258 \let\next\iterate
259 \else
260 \let\next\relax
261 \fi
262 \next

```



```

263 }%
264 \let\repeat=\fi
265 }%
266 \def\RestoreCatcodes{}
267 \count@=0 %
268 \loop
269 \edef\RestoreCatcodes{%
270 \RestoreCatcodes
271 \catcode\the\count@=\the\catcode\count@\relax
272 }%
273 \ifnum\count@<255 %
274 \advance\count@ 1 %
275 \repeat
276
277 \def\RangeCatcodeInvalid#1#2{%
278 \count@=#1\relax
279 \loop
280 \catcode\count@=15 %
281 \ifnum\count@<#2\relax
282 \advance\count@ 1 %
283 \repeat
284 }
285 \def\RangeCatcodeCheck#1#2#3{%
286 \count@=#1\relax
287 \loop
288 \ifnum#3=\catcode\count@
289 \else
290 \errmessage{%
291 Character \the\count@\space
292 with wrong catcode \the\catcode\count@\space
293 instead of \number#3%
294 }%
295 \fi
296 \ifnum\count@<#2\relax
297 \advance\count@ 1 %
298 \repeat
299 }
300 \def\space{ }
301 \expandafter\ifx\csname LoadCommand\endcsname\relax
302 \def\LoadCommand{\input engord.sty\relax}%
303 \fi
304 \def\Test{%
305 \RangeCatcodeInvalid{0}{47}%
306 \RangeCatcodeInvalid{58}{64}%
307 \RangeCatcodeInvalid{91}{96}%
308 \RangeCatcodeInvalid{123}{255}%
309 \catcode'\@=12 %
310 \catcode'\=0 %
311 \catcode'\%=14 %
312 \LoadCommand
313 \RangeCatcodeCheck{0}{36}{15}%
314 \RangeCatcodeCheck{37}{37}{14}%
315 \RangeCatcodeCheck{38}{47}{15}%
316 \RangeCatcodeCheck{48}{57}{12}%
317 \RangeCatcodeCheck{58}{63}{15}%
318 \RangeCatcodeCheck{64}{64}{12}%
319 \RangeCatcodeCheck{65}{90}{11}%
320 \RangeCatcodeCheck{91}{91}{15}%

```

```

321 \RangeCatcodeCheck{92}{92}{0}%
322 \RangeCatcodeCheck{93}{96}{15}%
323 \RangeCatcodeCheck{97}{122}{11}%
324 \RangeCatcodeCheck{123}{255}{15}%
325 \RestoreCatcodes
326 }
327 \Test
328 \csname @@end\endcsname
329 \end
330 </test1>

```

## 4 Installation

### 4.1 Download

**Package.** This package is available on CTAN<sup>1</sup>:

[CTAN:macros/latex/contrib/oberdiek/engord.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/engord.pdf](#) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

*TDS* refers to the standard “A Directory Structure for T<sub>E</sub>X Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

### 4.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```

chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/

```

### 4.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting docstrip archive. The files are extracted by running the `.dtx` through plain T<sub>E</sub>X:

```
tex engord.dtx
```

---

<sup>1</sup><http://ftp.ctan.org/tex-archive/>

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
engord.sty → tex/generic/oberdiek/engord.sty
engord.pdf → doc/latex/oberdiek/engord.pdf
test/engord-test1.tex → doc/latex/oberdiek/test/engord-test1.tex
engord.dtx → source/latex/oberdiek/engord.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

## 4.4 Refresh file name databases

If your  $\text{\TeX}$  distribution (`te $\text{\TeX}$` , `mik $\text{\TeX}$` , ...) relies on file name databases, you must refresh these. For example, `te $\text{\TeX}$`  users run `texhash` or `mktextlsr`.

## 4.5 Some details for the interested

**Attached source.** The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk engord.pdf unpack_files output .
```

**Unpacking with  $\text{\LaTeX}$ .** The `.dtx` chooses its action depending on the format:

**plain  $\text{\TeX}$ :** Run `docstrip` and extract the files.

**$\text{\LaTeX}$ :** Generate the documentation.

If you insist on using  $\text{\LaTeX}$  for `docstrip` (really, `docstrip` does not need  $\text{\LaTeX}$ ), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{engord.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdf $\text{\LaTeX}$` :

```
pdflatex engord.dtx
makeindex -s gind.ist engord.idx
pdflatex engord.dtx
makeindex -s gind.ist engord.idx
pdflatex engord.dtx
```

## 5 Catalogue

The following XML file can be used as source for the **TeX Catalogue**. The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `engord.xml`.

```
331 (*catalogue)
332 <?xml version='1.0' encoding='us-ascii'?>
333 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
334 <entry datestamp='$Date$' modifier='$Author$' id='engord'>
335 <name>engord</name>
336 <caption>Converts numbers to English ordinal numbers.</caption>
337 <authorref id='auth:oberdiek' />
338 <copyright owner='Heiko Oberdiek' year='2000,2003,2006-2008,2010' />
339 <license type='lppl1.3' />
340 <version number='1.8' />
341 <description>
342 Defines <tt>\engord</tt> (used like <tt>\arabic</tt>,
343 <tt>\roman</tt>, etc.), and <tt>\engordnumber</tt> (which formats
344 a “TeX number”).
345 <p/>
346 So <tt>\pagenumbering{engord}</tt> gives page numbers <tt>1st,
347 2nd, 3rd, ...</tt>
348 <p/>
349 The package is part of the <xref refid='oberdiek'>oberdiek</xref>
350 bundle.
351 </description>
352 <documentation details='Package documentation'
353 href='ctan:/macros/latex/contrib/oberdiek/engord.pdf' />
354 <ctan file='true' path='/macros/latex/contrib/oberdiek/engord.dtx' />
355 <miktex location='oberdiek' />
356 <texlive location='oberdiek' />
357 <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip' />
358 </entry>
359 </catalogue>
```

## 6 History

[2000/05/23 v1.0]

- First public release, published in newsgroup `de.comp.text.tex`:  
“Re: Ordinalzahlen in LaTeX?”<sup>2</sup>

[2003/04/28 v1.1]

- Bug fix for 30, 40, 50, ..., 100, 130, ...
- `\ordletters` renamed to documented `\engordletters`.

[2006/02/20 v1.2]

- Support for plain TeX.
- Switch `\ifengordraise` added.
- Package options `raise` and `normal` added.
- DTX framework.

---

<sup>2</sup>Url: <http://groups.google.com/group/de.comp.text.tex/msg/738e2cb4c51759d6>

[2007/04/11 v1.3]

- Line ends sanitized.

[2007/04/26 v1.4]

- Use of package infwarerr.

[2007/09/09 v1.5]

- Catcode section added.

[2007/09/20 v1.6]

- Short description fixed (George White).

[2008/08/11 v1.7]

- Code is not changed.
- URLs updated.

[2010/03/01 v1.8]

- Compatibility with ini-TeX.

## 7 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

| Symbols                             |                                                                                                                                                                                           |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>\#</code> .....               | 235                                                                                                                                                                                       |
| <code>\%</code> .....               | 311                                                                                                                                                                                       |
| <code>\@</code> .....               | 236, 309                                                                                                                                                                                  |
| <code>\@PackageWarning</code> ..... | 164                                                                                                                                                                                       |
| <code>\@ReturnAfterFi</code> .....  | 189, <u>196</u> , 214                                                                                                                                                                     |
| <code>\@firstofone</code> .....     | 223, 244, 247                                                                                                                                                                             |
| <code>\@gobble</code> .....         | 241, 249                                                                                                                                                                                  |
| <code>\@nil</code> .....            | 190, 210, 215, 220, 222, 223                                                                                                                                                              |
| <code>\@undefined</code> .....      | 58                                                                                                                                                                                        |
| <code>\</code> .....                | 211, 310                                                                                                                                                                                  |
| <code>\{</code> .....               | 233                                                                                                                                                                                       |
| <code>\}</code> .....               | 234                                                                                                                                                                                       |
|                                     | 40, 41, 42, 43, 44, 45, 46, 47, 48,<br>49, 69, 70, 72, 73, 74, 78, 79, 80,<br>81, 82, 83, 84, 87, 88, 90, 91, 92,<br>93, 97, 99, 233, 234, 235, 236,<br>271, 280, 288, 292, 309, 310, 311 |
| <code>\count@</code> .....          | 238, 267,<br>271, 273, 274, 278, 280, 281,<br>282, 286, 288, 291, 292, 296, 297                                                                                                           |
| <code>\countdef</code> .....        | 238                                                                                                                                                                                       |
| <code>\csname</code> ....           | 14, 21, 50, 66, 76, 114,<br>123, 133, 139, 146, 148, 161,<br>170, 237, 240, 243, 246, 301, 328                                                                                            |
| D                                   |                                                                                                                                                                                           |
| <code>\DeclareOption</code> .....   | 135, 136                                                                                                                                                                                  |
| E                                   |                                                                                                                                                                                           |
| <code>\empty</code> .....           | 17, 18                                                                                                                                                                                    |
| <code>\end</code> .....             | 329                                                                                                                                                                                       |
| <code>\endcsname</code> .           | 14, 21, 50, 66, 76, 114,<br>123, 133, 139, 146, 148, 161,<br>170, 237, 240, 243, 246, 301, 328                                                                                            |
| <code>\endinput</code> .....        | 29, 112                                                                                                                                                                                   |
| <code>\endlinechar</code> .....     | 4, 35, 71, 77, 89                                                                                                                                                                         |
| <code>\engord</code> .....          | 2, <u>169</u> , 342                                                                                                                                                                       |
| A                                   |                                                                                                                                                                                           |
| <code>\advance</code> .....         | 274, 282, 297                                                                                                                                                                             |
| <code>\aftergroup</code> .....      | 29                                                                                                                                                                                        |
| <code>\arabic</code> .....          | 342                                                                                                                                                                                       |
| B                                   |                                                                                                                                                                                           |
| <code>\body</code> .....            | 253, 257                                                                                                                                                                                  |
| C                                   |                                                                                                                                                                                           |
| <code>\catcode</code> ....          | 2, 3, 5, 6, 7, 8, 9, 10,<br>11, 12, 13, 33, 34, 36, 37, 38, 39,                                                                                                                           |

|                        |                                                                                              |  |  |
|------------------------|----------------------------------------------------------------------------------------------|--|--|
| \engorderror           | 2, 161, 181                                                                                  |  |  |
| \engordletters         | 2, 139, 163, 199                                                                             |  |  |
| \engordnumber          | 2, 173, 176, 343                                                                             |  |  |
| \engordraisefalse      | 2, 135                                                                                       |  |  |
| \engordraisetrue       | 2, 131, 136                                                                                  |  |  |
| \engordtextsuperscript | 142, 146                                                                                     |  |  |
| \EO@afterreverse       | 190, 219                                                                                     |  |  |
| \EO@AtEnd              | 95, 96, 112, 230                                                                             |  |  |
| \EO@def                | 113, 140, 162, 172, 176                                                                      |  |  |
| \EO@number             | 177, 179                                                                                     |  |  |
| \EO@ord                | 184, 197, 208, 225, 227                                                                      |  |  |
| \EO@reverse            | 190, 210, 223                                                                                |  |  |
| \EO@reverseback        | 220, 222                                                                                     |  |  |
| \EO@twodigits          | 187, 207                                                                                     |  |  |
| \errmessage            | 290                                                                                          |  |  |
| <b>I</b>               |                                                                                              |  |  |
| \ifcase                | 200                                                                                          |  |  |
| \ifengordraise         | 130, 141                                                                                     |  |  |
| \ifmmode               | 151                                                                                          |  |  |
| \ifnum                 | 180, 183, 186, 224, 273, 281, 288, 296                                                       |  |  |
| \ifx                   | 15, 18, 21, 50, 58, 61, 114, 123, 133, 139, 146, 148, 161, 170, 211, 237, 240, 243, 246, 301 |  |  |
| \immediate             | 23, 52                                                                                       |  |  |
| \input                 | 124, 125, 302                                                                                |  |  |
| \iterate               | 254, 256, 258                                                                                |  |  |
| <b>L</b>               |                                                                                              |  |  |
| \LoadCommand           | 302, 312                                                                                     |  |  |
| \loop                  | 252, 268, 279, 287                                                                           |  |  |
| \ltx@newif             | 130                                                                                          |  |  |
| <b>N</b>               |                                                                                              |  |  |
| \newcommand            | 118                                                                                          |  |  |
| \next                  | 258, 260, 262                                                                                |  |  |
| \number                | 177, 293                                                                                     |  |  |
| <b>P</b>               |                                                                                              |  |  |
| \PackageInfo           | 26                                                                                           |  |  |
| \pagenumbering         | 346                                                                                          |  |  |
| \ProcessOptions        | 137                                                                                          |  |  |
| \ProvidesPackage       | 19, 67                                                                                       |  |  |
| <b>R</b>               |                                                                                              |  |  |
| \RangeCatcodeCheck     | 285, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324                              |  |  |
| \RangeCatcodeInvalid   | 277, 305, 306, 307, 308                                                                      |  |  |
| \repeat                | 252, 264, 275, 283, 298                                                                      |  |  |
| \RequirePackage        | 127, 128                                                                                     |  |  |
| \RestoreCatcodes       | 266, 269, 270, 325                                                                           |  |  |
| \rm                    | 152, 154                                                                                     |  |  |
| \roman                 | 343                                                                                          |  |  |
| <b>S</b>               |                                                                                              |  |  |
| \space                 | 291, 292, 300                                                                                |  |  |
| <b>T</b>               |                                                                                              |  |  |
| \Test                  | 304, 327                                                                                     |  |  |
| \textsuperscript       | 158                                                                                          |  |  |
| \the                   | 77, 78, 79, 80, 81, 82, 83, 84, 97, 271, 291, 292                                            |  |  |
| \TMP@EnsureCode        | 94, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111                                    |  |  |
| <b>V</b>               |                                                                                              |  |  |
| \value                 | 173                                                                                          |  |  |
| <b>W</b>               |                                                                                              |  |  |
| \write                 | 23, 52                                                                                       |  |  |
| <b>X</b>               |                                                                                              |  |  |
| \x                     | 14, 15, 18, 22, 26, 28, 51, 56, 66, 75, 87                                                   |  |  |