

The `epstopdf` package

Heiko Oberdiek

<oberdiek@uni-freiburg.de>

2009/09/24 v2.3

Abstract

This packages adds support of handling eps images to package `graphics` or `graphicx` with option `pdftex`. If an eps image is detected, `epstopdf` is automatically called to convert it to pdf format.

Contents

1 Documentation	2
1.1 Introduction	2
1.2 Requirements	2
1.3 Usage	3
1.4 Options	3
1.5 Configuration	5
1.5.1 System configuration file <code>epstopdf-sys.cfg</code>	5
1.5.2 User configuration file <code>epstopdf.cfg</code>	5
1.5.3 Conversion program	5
1.6 Other image formats	5
2 Implementation	6
2.1 Wrapper package	6
2.1.1 Option handling	7
2.2 Base package	7
2.3 Preparations	8
2.3.1 Relead check and identification	8
2.3.2 Catcodes	9
2.3.3 Load packages	9
2.4 Checks	9
2.5 Package loading	10
2.6 Options	10
2.6.1 Default setting	10
2.7 Make and verbose	10
2.8 Adding conversion support	11
2.9 Declare graphics rule	14
3 Test	15
3.1 Preface for standard catcode check	15
3.2 Catcode checks for loading	15
4 Installation	16
4.1 Download	16
4.2 Bundle installation	17
4.3 Package installation	17
4.4 Refresh file name databases	17
4.5 Some details for the interested	17

5 History	18
[2001/01/06 v1.0]	18
[2001/02/04 v1.1]	18
[2006/02/20 v1.2]	18
[2006/08/26 v1.3]	18
[2007/04/26 v1.4]	18
[2007/10/02 v1.5]	18
[2007/11/11 v1.6]	18
[2008/05/06 v1.7]	19
[2009/03/01 v1.8]	19
[2009/07/06 v1.9]	19
[2009/07/07 v1.10]	19
[2009/07/12 v2.0]	19
[2009/07/15 v2.1]	19
[2009/07/16 v2.2]	19
[2009/09/24 v2.3]	19
6 Index	19

1 Documentation

1.1 Introduction

LATEX provides its graphics bundle to include graphics files. Both packages `graphics` or `graphicx` may be used. the latter one loads the first and adds options in key value style for `\includegraphics`.

Usually the drivers do not support all kind of graphics files. Other image types must be converted, before they become usable. In case of driver `dvips`, the graphics rule may contain a conversion rule. Then all that package `graphics` must know is the bounding box, the command is passed to `dvips` that calls it and embeds the converted image.

However, pdfTEX has its driver for PDF output already build in. It's graphics inclusion commands (`\pdfximage`) does not allow the execution of external commands. Therefore commands in the last argument of `\DeclareGraphicsRule` were of no use. But external programs can be called within pdfTEX. This feature is called "shell escape" or "write 18" and must usually enabled explicitly because of security reasons. Now, this package `epstopdf` hooks into package `graphics`' code to catch that argument with the external command and executes it to convert the graphics file to a supported format and passes the control of graphics inclusion back to package `graphics`.

1.2 Requirements

- The feature `\write18` must be enabled. This allows the running of external programs during TeX's compile run. Keep in mind that this is a security risk. The feature is an addition to \TeX. MikTeX, teTeX, TeX Live support it. In Web2C based TeX distributions (teTeX, TeX Live) it can be enabled in the configuration file `texmf.cnf`:

```
shell_escape = 1
```

Because of the security risk, it is better to do it on the command line only:

```
--shell-escape (teTeX, TeX Live)
--enable-write18 (MiKTeX)
```

Example:

```
pdflatex -shell-escape test.tex
```

- The program `epstopdf` for the conversion from EPS to PDF. However, other programs can be used and configured by `\DeclareGraphicsRule`. Example:

```
\epstopdfDeclareGraphicsRule{.eps}{pdf}{.pdf}{%
  ps2pdf -dEPSCrop #1 \OutputFile
}
```

1.3 Usage

The package is loaded after `graphic{s,x}`, e.g.:

```
\usepackage[pdftex]{graphicx}
\usepackage{epstopdf}
```

Now images with file name extension `.eps` are detected and supported using `\includegraphics`.

If the graphics file name is explicitly specified with extension `.eps` the new rule for EPS files is called and the conversion performed. If option `update` is in force then the conversion step is dropped if the target file already exists and is not older than the EPS file.

The situation is more complicate if the graphics file is given without file name extension. Then the `graphics` package must search for a supported image file. The possible extensions are stored in the graphics extension list, that can be set by `\DeclareGraphicsExtensions`. The algorithm:

```
function search( <filebase> )
  foreach <ext> in <graphics extensions>
    foreach <dir> in <current directory>, <\graphicspath>
      <file> := <dir> + <filebase> + <ext>
      if exist <file>
        return found
      return not found
```

Package `epstopdf` puts `.eps` at the end of the graphics extension search list. This is the behaviour of option `append` that is enabled by default. That means, the conversion is called last unless a supported file type cannot be found earlier. This avoids unnecessary conversion steps that slow down the L^AT_EX run. If you want to use option `update` and your pdfT_EX supports it, then an outdated PDF file also would be found earlier unless `suffix` is used that is the default since version 2.0.

With an empty option `suffix` and option `prepend` there is a risk that an original PDF file is overwritten:

If the original image file is the PDF file and there is also a generated EPS file, then the original PDF file can be regenerated (depending on the option settings) and the original PDF file gets lost. Therefore option `suffix` is introduced in version 1.9 to create a separate name space for generated output files.

Note: Usually the conversion program needs the exact location of the image file. Usually the current directory works. Also if the image file is found using `\graphicspath`, the location is known. However, if the image is somewhere in a directory of environment variable `TEXINPUTS`, then the package does not know the exact location and the conversion program will not find the image file unless it implements a search using `TEXINPUTS` (program `kpsewhich` may be of help in this task).

1.4 Options

Options can be given as package options or later using:

```
\epstopdfsetup {\{key value list\}}
```

L^AT_EX expands the option list before passing the option list to the package's option handling code. This can fail for option **suffix** if it contains some of the macros described below. Use **\epstopdfsetup** after the package is loaded. Or load package **kvoptions-patch** before. This package is also loaded by option **patch** of package **kvoptions**. L^AT_EX's option code is redefined to respect key value options and let the values untouched.

update: The conversion program is only called, if the target file does not exist or is older than the source image file.

append: Puts the extension **.eps** at the end of the graphics extension list (default).

prepend: Puts the extension **.eps** at the begin of the graphics extension list.

outdir: The converted file may put in an other output directory. The value of **outdir** must include the directory separator. Example for the current directory:

```
\epstopdfsetup{outdir=./}
```

For other directories ensure, that they can be found. See **\graphicspath** or **TEXINPUTS**.

suffix: This option takes a string that is put between the file name base and the extension of the output file. Rationale: It can happen, that a PDF file is the original file and the EPS file the generated file. If now the package thinks, that the PDF file is the generated file, it will 'regenerate' it. But in reality the original file is lost. Therefore I recommend to use this option always to generate a separate name space for generated files. Proposed value is **-generated** or **.generated**. The suffix **.generated** will also work here without the need for package **grffile**).

Example:

```
\epstopdfsetup{suffix=-generated}  
Then foo.eps is converted to foo-generated.pdf.
```

\SourceExt can be used inside the suffix string. It's will be replaced by the extension of the image source file without the leading dot, for instance:

```
\epstopdfsetup{suffix=-\SourceExt-converted-to}  
foo.eps ⇒ foo-eps-converted-to.pdf
```

See also the next option **prefersuffix** that modifies the behaviour of option **suffix** in some cases.

Default for **suffix** is '**-\SourceExt-converted-to**'.

prefersuffix: If a suffix is set by option **suffix**, then there can be two image file names that could be taken into account for inclusion: A image file name with the suffix string inside its name and a image file name without; e.g. for **foo.eps** the names could be:

```
foo-suffix.pdf, foo.pdf
```

If option **prefersuffix** is turned on, the file **foo-suffix.pdf** and its generation is preferred over using **foo.pdf**. Otherwise **foo.pdf** is included without generating **foo-suffix.pdf**. The default of option **prefersuffix** is **true**.

verbose: It prints some information about the image in the **.log** file (default).

1.5 Configuration

1.5.1 System configuration file `epstopdf-sys.cfg`

If `epstopdf-sys` exists it is loaded at the end of the package `epstopdf-base` and before the user configuration file. It's intended for TeX distributors. Thus they could add additional conversion rules (e.g., `.gif -i .png`) or set options.

1.5.2 User configuration file `epstopdf.cfg`

A configuration file `epstopdf.cfg` is loaded at the end of the package if it exists. It can be used for changing the default option setting. Example:

```
\epstopdfsetup{verbose=false}
```

1.5.3 Conversion program

You can use `\DeclareGraphicsRule` in a similar way as the route via `dvips` to specify the conversion command line. The conversion argument starts with a back tick, followed by the conversion command including parameters.

The whole conversion argument should also be wrapped inside `\epstopdfcall`. This reduces the problem with packages (e.g. `pst-pdf`) that use the conversion argument and expands it. Macros `\SourceFile`, `\OutputFile`, and `\SourceExt` are not defined outside `epstopdf-base`'s `\Gin@setfile` and error messages because of undefined command names are the result. If `\epstopdfcall` detects that it is called outside `epstopdf-base`'s `\Gin@setfile` then it replaces the conversion argument by package `graphics`'s default, usually the image file.

The following macros are available inside:

```
\OutputFile: : output file name (with known path and extension)  
\SourceFile: : source file name (with known path and extension), usually the  
same as #1,  
\SourceExt: : source extension without leading dot.
```

Conversion from EPS to PDF. Other programs than `epstopdf` can be used to convert from EPS to PDF. Example that uses `Ghostscript`:

```
\DeclareGraphicsRule{.eps}{pdf}{.pdf}{%  
    \epstopdfcall{'ps2pdf -dEPSCrop #1 \noexpand\OutputFile}'%  
}
```

`\DeclareGraphicsRule` expands the argument, therefore `\noexpand` is necessary. As convenience package `epstopdf-base` defines `\epstopdfDeclareGraphicsRule`. Then the conversion argument is not expanded, `\epstopdfcall` and the back tick are added:

```
\epstopdfDeclareGraphicsRule{.eps}{pdf}{.pdf}{%  
    ps2pdf -dEPSCrop #1 \OutputFile  
}
```

Also `\OutputFile` respects the setting of option `outdir`.

1.6 Other image formats

The support that package `epstopdf` implements is not limited to EPS files. Other image conversions can be declared. The following example shows it for GIF images under Unix with ImageMagick's `convert`:

```
\epstopdfDeclareGraphicsRule{.gif}{png}{.png}{%  
    convert #1 \OutputFile  
}
```

The file extension `.gif` can be added to the extension list that package `graphics` searches if the file extension is not given in `\includegraphics`. The list can be set by `\GraphicsExtensions`.

```
\AppendGraphicsExtensions{.gif}
or
\PrependGraphicsExtensions{.gif}
```

2 Implementation

1 `<*package>`

2.1 Wrapper package

Reload check, especially if the package is not used with L^AT_EX.

```
2 \begingroup
3   \catcode44 12 % ,
4   \catcode45 12 % -
5   \catcode46 12 % .
6   \catcode58 12 % :
7   \catcode64 11 % @
8   \catcode123 1 % {
9   \catcode125 2 % }
10  \expandafter\let\expandafter\x\csname ver@epstopdf.sty\endcsname
11  \ifx\x\relax % plain-TeX, first loading
12  \else
13    \def\empty{}%
14    \ifx\x\empty % LaTeX, first loading,
15      % variable is initialized, but \ProvidesPackage not yet seen
16    \else
17      \catcode35 6 % #
18      \expandafter\ifx\csname PackageInfo\endcsname\relax
19        \def\x#1#2{%
20          \immediate\write-1{Package #1 Info: #2.}%
21        }%
22    \else
23      \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
24    \fi
25    \x{epstopdf}{The package is already loaded}%
26    \aftergroup\endinput
27  \fi
28 \fi
29 \endgroup
```

Package identification:

```
30 \begingroup
31   \catcode35 6 % #
32   \catcode40 12 % (
33   \catcode41 12 % )
34   \catcode44 12 % ,
35   \catcode45 12 % -
36   \catcode46 12 % .
37   \catcode47 12 % /
38   \catcode58 12 % :
39   \catcode64 11 % @
40   \catcode91 12 % [
41   \catcode93 12 % ]
42   \catcode123 1 % {
43   \catcode125 2 % }
44   \expandafter\ifx\csname ProvidesPackage\endcsname\relax
45     \def\x#1#2#3[#4]{\endgroup
46       \immediate\write-1{Package: #3 #4}%
47 }
```

```

47      \xdef#1{#4}%
48      }%
49 \else
50   \def\x#1#2[#3]{\endgroup
51     #2[{#3}]%
52     \ifx#1\undefined
53       \xdef#1{#3}%
54     \fi
55     \ifx#1\relax
56       \xdef#1{#3}%
57     \fi
58   }%
59 \fi
60 \expandafter\x\csname ver@epstopdf.sty\endcsname
61 \ProvidesPackage{epstopdf}%
62 [2009/09/24 v2.3 Conversion with epstopdf on the fly (HO)]
63 \begingroup
64   \catcode123 1 % {
65   \catcode125 2 % }
66   \def\x{\endgroup
67     \expandafter\edef\csname ETE@AtEnd\endcsname{%
68       \catcode35 \the\catcode35\relax
69       \catcode64 \the\catcode64\relax
70       \catcode123 \the\catcode123\relax
71       \catcode125 \the\catcode125\relax
72     }%
73   }%
74 \x
75 \catcode35 6 % #
76 \catcode64 11 % @
77 \catcode123 1 % {
78 \catcode125 2 % }
79 \def\TMP@EnsureCode#1#2{%
80   \edef\ETE@AtEnd{%
81     \ETE@AtEnd
82     \catcode#1 \the\catcode#1\relax
83   }%
84   \catcode#1 #2\relax
85 }
86 \TMP@EnsureCode{42}{12} * *
87 \TMP@EnsureCode{45}{12} -
88 \TMP@EnsureCode{47}{12} /
89 \let\ETE@SavedAtEnd\ETE@AtEnd
90 \RequirePackage{epstopdf-base}[2009/09/24]
91 \let\ETE@AtEnd\ETE@SavedAtEnd

```

2.1.1 Option handling

```

92 \DeclareOption*{%
93   \expandafter\epstopdfsetup\expandafter{\CurrentOption}%
94 }
95 \ProcessOptions*\relax
96 \ETE@AtEnd
97 
```

2.2 Base package

```

98 
```

2.3 Preparations

2.3.1 Relead check and identification

Reload check, especially if the package is not used with L^AT_EX.

```
99 \begingroup
100  \catcode44 12 %
101  \catcode45 12 %
102  \catcode46 12 %
103  \catcode58 12 %
104  \catcode64 11 %
105  \catcode123 1 %
106  \catcode125 2 %
107  \expandafter\let\expandafter\x\csname ver@epstopdf-base.sty\endcsname
108  \ifx\x\relax % plain-TeX, first loading
109  \else
110    \def\empty{}%
111    \ifx\x\empty % LaTeX, first loading,
112      % variable is initialized, but \ProvidesPackage not yet seen
113    \else
114      \catcode35 6 %
115      \expandafter\ifx\csname PackageInfo\endcsname\relax
116        \def\x#1#2{%
117          \immediate\write-1{Package #1 Info: #2.}%
118        }%
119    \else
120      \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
121    \fi
122    \x{epstopdf-base}{The package is already loaded}%
123    \aftergroup\endinput
124  \fi
125 \fi
126 \endgroup
```

Package identification:

```
127 \begingroup
128  \catcode35 6 %
129  \catcode40 12 %
130  \catcode41 12 %
131  \catcode44 12 %
132  \catcode45 12 %
133  \catcode46 12 %
134  \catcode47 12 %
135  \catcode58 12 %
136  \catcode64 11 %
137  \catcode91 12 %
138  \catcode93 12 %
139  \catcode123 1 %
140  \catcode125 2 %
141  \expandafter\ifx\csname ProvidesPackage\endcsname\relax
142    \def\x#1#2#3[#4]{\endgroup
143      \immediate\write-1{Package: #3 #4}%
144      \xdef#1{#4}%
145    }%
146  \else
147    \def\x#1#2[#3]{\endgroup
148      #2[#3]%
149      \ifx#1\undefined
150        \xdef#1{#3}%
151      \fi
152      \ifx#1\relax
153        \xdef#1{#3}%
154      \fi
155    }%
```

```

155      }%
156  \fi
157 \expandafter\x\csname ver@epstopdf-base.sty\endcsname
158 \ProvidesPackage{epstopdf-base}%
159 [2009/09/24 v2.3 Base part for package epstopdf]

```

2.3.2 Catcodes

```

160 \begingroup
161   \catcode123 1 % {
162   \catcode125 2 % }
163   \def\x{\endgroup
164     \expandafter\edef\csname ETE@AtEnd\endcsname{%
165       \catcode35 \the\catcode35\relax
166       \catcode64 \the\catcode64\relax
167       \catcode123 \the\catcode123\relax
168       \catcode125 \the\catcode125\relax
169     }%
170   }%
171 \x
172 \catcode35 6 % #
173 \catcode64 11 % @
174 \catcode123 1 % {
175 \catcode125 2 % }
176 \def\TMP@EnsureCode#1#2{%
177   \edef\ETE@AtEnd{%
178     \ETE@AtEnd
179     \catcode#1 \the\catcode#1\relax
180   }%
181   \catcode#1 #2\relax
182 }
183 \TMP@EnsureCode{33}{12}! !
184 \TMP@EnsureCode{39}{12}!
185 \TMP@EnsureCode{42}{12}!* ,
186 \TMP@EnsureCode{44}{12}%, -
187 \TMP@EnsureCode{45}{12}%- .
188 \TMP@EnsureCode{46}{12}%. .
189 \TMP@EnsureCode{47}{12}/
190 \TMP@EnsureCode{58}{12}:-
191 \TMP@EnsureCode{60}{12}<=
192 \TMP@EnsureCode{61}{12}=>
193 \TMP@EnsureCode{62}{12}%
194 \TMP@EnsureCode{96}{12}‘

```

2.3.3 Load packages

```

195 \RequirePackage{infwarerr}[2007/09/09]
196 \RequirePackage{grfext}\relax
197 \RequirePackage{kvoptions}[2007/10/02]
198 \RequirePackage{pdftexcmds}[2007/11/11]

```

2.4 Checks

Check, whether package graphics is loaded (also graphicx loads graphics). Because miniltx.tex does not know \ifpackageloaded we test for \Gin@setfile instead.

```

199 \begingroup\expandafter\expandafter\expandafter\endgroup
200 \expandafter\ifx\csname Gin@setfile\endcsname\relax
201   \PackageWarningNoLine{epstopdf}{%
202     No graphics package `graphic[s,x]` loaded%
203   }%
204   \newcommand*\epstopdfsetup[1]{%
205     \ETE@AtEnd
206     \expandafter\endinput
207   }%

```

Check, whether pdftex.def is loaded. `\ver@pdftex.def` is not available with `miniltx.tex`, thus we test for `\Gin@driver`.

```
208 \begingroup
209   \def\x{pdftex.def}%
210   \ifx\Gin@driver\x
211   \else
212     \@PackageWarningNoLine{epstopdf}{%
213       Other drivers than 'pdftex.def' are not supported%
214     }%
215   \endgroup
216   \newcommand*\epstopdfsetup[1]{%
217     \ETE@AtEnd
218     \expandafter\endinput
219   \fi
220 \endgroup
```

Check, whether the shell escape feature is enabled.

```
221 \begingroup
222   \expandafter\ifx\csname pdf@shellescape\endcsname\relax
223   \else
224     \ifnum\pdf@shellescape>0 %
225   \else
226     \@PackageWarningNoLine{epstopdf}{%
227       Shell escape feature is not enabled%
228     }%
229   \fi
230 \fi
231 \endgroup
```

2.5 Package loading

2.6 Options

```
232 \SetupKeyvalOptions{family=ETE,prefix=ETE@}
233 \DeclareBoolOption{update}
234 \DeclareBoolOption{verbose}
235 \newif\ifETE@prepend
236 \DeclareVoidOption{prepend}{\ETE@prependtrue}
237 \DeclareVoidOption{append}{\ETE@prependfalse}
238 \DeclareStringOption{outdir}
239 \DeclareStringOption{suffix}
240 \DeclareBoolOption{prefersuffix}
```

Options `disable` and `enable` are for testing only. Therefore they are not documented on purpose.

```
241 \DeclareBoolOption{disable}
242 \DeclareComplementaryOption{enable}{disable}
243 \newcommand*\epstopdfsetup{\setkeys{ETE}}
```

2.6.1 Default setting

```
244 \epstopdfsetup{%
245   verbose,%  

246   enable,%  

247   append,%  

248   update,%  

249   prefersuffix,%  

250   suffix=-\SourceExt-converted-to%
```

2.7 Make and verbose

```
252 \begingroup\expandafter\expandafter\expandafter\endgroup
253 \expandafter\ifx\csname pdf@filemoddate\endcsname\relax
```

```

254 \def\ETE@Make#1#2{%
255   \ifETE@update
256     \ETE@WarnModDate
257   \fi
258   \etefirstofone
259 }%
260 \def\ETE@WarnModDate{%
261   \@PackageWarningNoLine{epstopdf}{%
262     \string\pdffilemoddate\space is not available,\MessageBreak
263     option 'update' will be ignored%
264   }%
265   \global\let\ETE@WarnModDate\relax
266 }%
267 \def\ETE@FileInfo#1#2{#1 file: <#2>}%
268 \else
269   \def\ETE@Make#1#2{%
270     \ifETE@update
271       \ifnum\pdfstrcmp{\pdf@filemoddate{#1}}{\pdf@filemoddate{#2}}>0 %
272         \expandafter\expandafter\expandafter\etefirstofone
273       \else
274         \@PackageInfoNoLine{epstopdf}{%
275           Output file is already uptodate%
276         }%
277         \expandafter\expandafter\expandafter\gobble
278       \fi
279     \else
280       \expandafter\etefirstofone
281     \fi
282   }%
283 \def\ETE@FileInfo#1#2{%
284   #1 file: <#2>%
285   \expandafter\expandafter\expandafter
286   \ETE@Date\pdf@filemoddate{#2}\@nil
287   \expandafter\expandafter\expandafter
288   \ETE@Size\pdf@filesize{#2}\@nil
289 }%
290 \def\ETE@Date#1\@nil{%
291   \ifx\\#1\\%
292   \else
293     \ETE@@Date#1\@nil
294   \fi
295 }%
296 \def\ETE@@Date#1:#2#3#4#5#6#7#8#9{%
297   \MessageBreak
298   \@spaces\space\space\space date: #2#3#4#5-#6#7-#8#9 %
299   \ETE@@Time
300 }%
301 \def\ETE@@Time#1#2#3#4#5#6#7\@nil{%
302   #1#2:#3#4:#5#6%
303 }%
304 \def\ETE@Size#1\@nil{%
305   \ifx\\#1\\%
306   \else
307     \MessageBreak
308     \@spaces\space\space\space size: #1 bytes%
309   \fi
310 }%
311 \fi

```

2.8 Adding conversion support

Patch `\Gin@setfile` to execute #3, if it contains a command.

```
312 \expandafter\ifx\csname ETE@OrgGin@setfile\endcsname\relax
```

```

313   \let\ETE@OrgGin@setfile\Gin@setfile
314 \else
315   \PackageError{epstopdf}{%
316     Command \string\ETE@OrgGin@setfile\space
317     already defined.\MessageBreak
318   }{%
319     Probably some package has included the code of this package%
320     \MessageBreak
321     instead of using \string\RequirePackage{epstopdf}.%
322     \MessageBreak
323     \Oehc
324   }%
325 \fi
326 \def\ETE@IfFileExists{%
327   \begingroup\expandafter\expandafter\expandafter\endgroup
328   \expandafter\ifx\csname grffile@IfFileExists\endcsname\relax
329     \expandafter\IfFileExists
330   \else
331     \global\let\ETE@IfFileExists\grffile@IfFileExists
332     \expandafter\grffile@IfFileExists
333   \fi
334 }%
335 \def\ETE@Skip#1#2\x\fi\fi{%
336   \fi
337   \fi
338   \endgroup
339   \fi
340   \fi
341   #1%
342 }%
343 \newif\iff\ETE@InsideSetfile
344 \newcommand*{\epstopdfcall}[1]{%
345   \if\ETE@InsideSetfile
346     \expandafter\@firstoftwo
347   \else
348     \expandafter\@secondoftwo
349   \fi
350   {'#1}%
351   {\Gin@base\Gin@ext}%
352 }%
353 \def\ETE@DefCommandLine#1{%
354   \edef\CommandLine{\expandafter\fi\if' '#1}%
355 }%
356 \def\ETE@DefX#1{%
357   \expandafter\expandafter\expandafter\def
358   \expandafter\expandafter\expandafter\x
359   \expandafter\expandafter\expandafter\expandafter{%
360     \expandafter\fi\if' '#1\relax\else
361   }%
362 }%
363 \def\Gin@setfile#1#2#3{%
364   \if\ETE@disable
365     \ETE@OrgGin@setfile{#1}{#2}{#3}%
366   \else
367     \begingroup
368       \ETE@InsideSetfiletrue
369       \ETE@DefX{#3}%
370     \expandafter\endgroup
371     \ifx\x\empty
372       \ETE@OrgGin@setfile{#1}{#2}{#3}%
373     \else
374       \begingroup

```

```

375      \ETE@InsideSetfiletrue
376      \def\GraphicsType{#1}%
377      \def\GraphicsRead{#2}%
378      \ifETE@prefersuffix
379      \else
380          \ifx\ETE@suffix\@empty
381          \else
382              \ETE@IfExists{\Gin@base\GraphicsRead}{%
383                  \ETE@Skip{%
384                      \ETE@OrgGin@setfile{#1}{#2}{\Gin@base#2}%
385                  }%
386                  }{%
387                      \let\next\relax
388                  }%
389                  \next
390          \fi
391      \fi
392      \ifx\Gin@ext\relax
393          \let\SourceExt\Gin@eext
394          \def\SourceFile{\Gin@base\Gin@eext}%
395      \else
396          \let\SourceExt\Gin@ext
397          \def\SourceFile{\Gin@base\Gin@ext}%
398      \fi
399      \edef\SourceExt{%
400          \expandafter\@cdr\SourceExt\@empty\@nil
401      }%
402      \let\OutputDirectory\ETE@outdir
403      \ifx\OutputDirectory\@empty
404          \edef\OutputFile{\ETE@GenerateName{\Gin@base}{#2}}%
405      \else
406          \begingroup
407              \filename@parse{\Gin@base#2}%
408              \edef\x{\endgroup
409                  \def\noexpand\OutputFile{%
410                      \ETE@GenerateName{%
411                          \OutputDirectory\filename@base
412                      }{#2}%
413                  }%
414              }%
415          \x
416      \fi
417      \ETE@DefCommandLine{#3}%
418      \ifETE@verbose
419          \@PackageInfo{epstopdf}{%
420              \ETE@FileInfo{Source}\SourceFile\MessageBreak
421              \ETE@FileInfo{Output}\OutputFile\MessageBreak
422              Command: <\CommandLine>\MessageBreak
423              \string\includegraphics
424          }%
425      \fi
426      \ETE@Make\SourceFile\OutputFile{%
427          \pdf@system{\CommandLine}%
428          \ifETE@verbose
429              \@PackageInfoNoLine{epstopdf}{%
430                  \ETE@FileInfo{Result}\OutputFile
431              }%
432          \fi
433      }%
434      \edef\x{\endgroup
435          \ifx\OutputDirectory\@empty
436          \else

```

```

437      \def\noexpand\Gin@base{%
438          \OutputDirectory\noexpand\filename@base
439      }%
440      \fi
441      \ifx\ETE@suffix\@empty
442      \else
443          \edef\noexpand\Gin@base{%
444              \noexpand\Gin@base\ETE@suffix
445          }%
446      \fi
447      \noexpand\ETE@OrgGin@setfile{%
448          \GraphicsType
449      }%
450      \GraphicsRead
451      }%
452      \OutputFile
453      }%
454      }%
455      \x
456      \fi
457      \fi
458 }
459 \def\ETE@GenerateName#1#2{%
460   #1\ETE@suffix#2%
461 }

```

2.9 Declare graphics rule

```

462 \newcommand*{\epstopdfDeclareGraphicsRule}[4]{%
463   \ifx\#4\%
464     \@PackageError{epstopdf-base}{%
465       Conversion command is missing%
466     }\@ehc
467   \else
468     \begingroup
469       \@ifundefined{Gin@rule@\#1}{%
470         }{%
471           \@PackageInfo{epstopdf-base}{%
472             Redefining graphics rule for '#1'%
473           }%
474         }%
475       \endgroup
476       \namedef{Gin@rule@\#1}##1{##2}{##3}{\epstopdfcall{##4}}{%
477     \fi
478   }

  \DeclareGraphicsRule for .eps
479 \epstopdfDeclareGraphicsRule{.eps}{pdf}{.pdf}{%
480   \ETE@epstopdf{#1}%
481 }
482 \def\ETE@epstopdf#1{%
483   epstopdf %
484   \ifcase\ifx\OutputDirectory\@empty
485     \ifx\ETE@suffix\@empty
486       1%
487     \fi
488     \fi
489     0 %
490     --outfile=\OutputFile\space
491   \fi
492   #1%
493 }
494 \ifETE@prepend

```

```

495  \expandafter\PrependGraphicsExtensions
496 \else
497  \expandafter\AppendGraphicsExtensions
498 \fi
499 {.eps}
500 \let\ETE@prepend\undefined
501 \DeclareVoidOption{prepend}{%
502  \PrependGraphicsExtensions{.eps}%
503 }
504 \let\ETE@append\undefined
505 \DeclareVoidOption{append}{%
506  \AppendGraphicsExtensions{.eps}%
507 }

508 \InputIfFileExists{epstopdf-sys.cfg}{}{}
509 \InputIfFileExists{epstopdf.cfg}{}{}

510 \ETE@AtEnd
511 </base>

```

3 Test

3.1 Preface for standard catcode check

```

512 <*test1>
513 \input miniltx.tex\relax
514 \def\Gin@driver{pdftex.def}
515 \input graphicx.sty\relax
516 \resetatcatcode
517 </test1>

```

3.2 Catcode checks for loading

```

518 <*test1>
519 \catcode`\{=1 %
520 \catcode`\}=2 %
521 \catcode`\#=6 %
522 \catcode`\@=11 %
523 \expandafter\ifx\csname count@\endcsname\relax
524   \countdef\count@=255 %
525 \fi
526 \expandafter\ifx\csname @firstofone\endcsname\relax
527   \long\def\@firstofone#1{}%
528 \fi
529 \expandafter\ifx\csname @firstofone\endcsname\relax
530   \long\def\@firstofone#1{#1}%
531 \fi
532 \expandafter\ifx\csname loop\endcsname\relax
533   \expandafter\@firstofone
534 \else
535   \expandafter\@gobble
536 \fi
537 {%
538   \def\loop#1\repeat{%
539     \def\body{#1}%
540     \iterate
541   }%
542   \def\iterate{%
543     \body
544     \let\next\iterate
545   \else
546     \let\next\relax
547   \fi
548   \next

```

```

549  }%
550  \let\repeat=\fi
551 }%
552 \def\RestoreCatcodes{%
553 \count@=0 %
554 \loop
555 \edef\RestoreCatcodes{%
556   \RestoreCatcodes
557   \catcode\the\count@=\the\catcode\count@\relax
558 }%
559 \ifnum\count@<255 %
560   \advance\count@ 1 %
561 \repeat
562
563 \def\RangeCatcodeInvalid#1#2{%
564   \count@=#1\relax
565   \loop
566   \catcode\count@=15 %
567   \ifnum\count@<#2\relax
568     \advance\count@ 1 %
569   \repeat
570 }
571 \expandafter\ifx\csname LoadCommand\endcsname\relax
572   \def\LoadCommand{\input epstopdf.sty\relax}%
573 \fi
574 \def\Test{%
575   \RangeCatcodeInvalid{0}{47}%
576   \RangeCatcodeInvalid{58}{64}%
577   \RangeCatcodeInvalid{91}{96}%
578   \RangeCatcodeInvalid{123}{255}%
579   \catcode`@=12 %
580   \catcode`\|=0 %
581   \catcode`\{=1 %
582   \catcode`\}=2 %
583   \catcode`\#=6 %
584   \catcode`\[=12 %
585   \catcode`\]=12 %
586   \catcode`\%=14 %
587   \catcode`\ =10 %
588   \catcode13=5 %
589   \LoadCommand
590   \RestoreCatcodes
591 }
592 \Test
593 \csname @@end\endcsname
594 \end
595 </test1>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/epstopdf.dtx](http://CTAN.mirror/obsolete/oberdiek/epstopdf.dtx) The source file.

[CTAN:macros/latex/contrib/oberdiek/epstopdf.pdf](http://CTAN.mirror/obsolete/oberdiek/epstopdf.pdf) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

¹[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for \TeX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDSScripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdflatfi.pl` that should be installed in such a way that it can be called as `pdflatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdflatfi.pl
cp scripts/oberdiek/pdflatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain- \TeX :

```
tex epstopdf.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>epstopdf.sty</code>	→ <code>tex/latex/oberdiek/epstopdf.sty</code>
<code>epstopdf-base.sty</code>	→ <code>tex/latex/oberdiek/epstopdf-base.sty</code>
<code>epstopdf.pdf</code>	→ <code>doc/latex/oberdiek/epstopdf.pdf</code>
<code>test/epstopdf-test1.tex</code>	→ <code>doc/latex/oberdiek/test/epstopdf-test1.tex</code>
<code>epstopdf.dtx</code>	→ <code>source/latex/oberdiek/epstopdf.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your \TeX distribution (te \TeX , mik \TeX , ...) relies on file name databases, you must refresh these. For example, te \TeX users run `texhash` or `mktexlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk epstopdf.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain- \TeX : Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{epstopdf.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfLATEX:

```
pdflatex epstopdf.dtx
makeindex -s gind.ist epstopdf.idx
pdflatex epstopdf.dtx
makeindex -s gind.ist epstopdf.idx
pdflatex epstopdf.dtx
```

5 History

[2001/01/06 v1.0]

- First public version, published in the pdfTEX mailing list.

[2001/02/04 v1.1]

- Minor documentation update.
- CTAN.

[2006/02/20 v1.2]

- DTX framework.
- Compatibility for `miniltx.tex`.

[2006/08/26 v1.3]

- Check for `\write18` if available and print a warning if the feature is not enabled.

[2007/04/26 v1.4]

- Documentation rewritten and extended.

[2007/10/02 v1.5]

- New option `update`: If the converted file exists, it will be only converted if it is out of date.
- Updating the extension list is delegated to package `grfext`. Fine tuning is done by the new options `append`, `prepend`.
- New option `outdir` for changing the output directory.
- New option `verbose`.
- `\SourceFile` and `\OutputFile` introduced.
- Configuration file support added.

[2007/11/11 v1.6]

- Use of package `pdftexcmds` for LUATEX support.

[2008/05/06 v1.7]

- Warning messages uses “loaded” instead of “found”.

[2009/03/01 v1.8]

- Warning message for missing `pdftex.def` changed.

[2009/07/06 v1.9]

- Option `suffix` added.

[2009/07/07 v1.10]

- `\SourceExt` added.
- If option `suffix` is set, the inclusion of an image without the suffix namespace is preferred over generating the the image within the suffix namespace.

[2009/07/12 v2.0]

- New default settings.
- Package is split into `epstopdf` that only takes package options and loads `epstopdf-base` that does the work.
- `\epstopdfDeclareGraphicsRule` and `\epstopdfcall` added.
- `epstopdf-sys.cfg` is loaded before `epstopdf.cfg` if `epstopdf-sys.cfg` exists.

[2009/07/15 v2.1]

- Default setting: `verbose` is now turned on as the documentation for v2.0 said.
- Documentation fixes.

[2009/07/16 v2.2]

- Fixed redefined `\Gin@setfile`.
- Documentation extended for package options.

[2009/09/24 v2.3]

- Bug fix for the case that both option `suffix` and `outdir` are used.

6 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	...	201, 212, 226, 261	
<code>\#</code>	<code>521, 583</code>	<code>\@cdr</code>	<code>400</code>
<code>\%</code>	<code>586</code>	<code>\@ehc</code>	<code>323, 466</code>
<code>\@</code>	<code>522, 579</code>	<code>\@empty</code>	<code>371,</code>
<code>\@PackageError</code>	<code>315, 464</code>	<code>380, 400, 403, 435, 441, 484, 485</code>	
<code>\@PackageInfo</code>	<code>419, 471</code>	<code>\@firstofone</code> ..	<code>258, 272, 280, 530, 533</code>
<code>\@PackageInfoNoLine</code>	<code>274, 429</code>	<code>\@firstoftwo</code>	<code>346</code>
<code>\@PackageWarningNoLine</code>		<code>\@gobble</code>	<code>277, 527, 535</code>

\@ifundefined	469	\epstopdfsetup	4, 93, 204, 216, 243, 244
\@namedef	476	\ETE@@Date	293, 296
\@nil	286, 288, 290, 293, 301, 304, 400	\ETE@@Time	299, 301
\@secondoftwo	348	\ETE@append	504
\@spaces	298, 308	\ETE@AtEnd	80, 81,
\@undefined	52, 149, 500, 504	89, 91, 96, 177, 178, 205, 217, 510	
\[.....	584	\ETE@Date	286, 290
\\"	291, 305, 463, 580	\ETE@DefCommandLine	353, 417
\{	519, 581	\ETE@DefX	356, 369
\}	520, 582	\ETE@epstopdf	480, 482
\]	585	\ETE@FileInfo	267, 283, 420, 421, 430
_	587	\ETE@GenerateName	404, 410, 459
		\ETE@IfFileExists	326, 331, 382
		\ETE@InsideSetfiletrue	368, 375
		\ETE@Make	254, 269, 426
		\ETE@OrgGin@setfile	
		313, 316, 365, 372, 384, 447
		\ETE@outdir	402
		\ETE@prepend	500
		\ETE@prependfalse	237
		\ETE@prependtrue	236
		\ETE@SavedAtEnd	89, 91
		\ETE@Size	288, 304
		\ETE@Skip	335, 383
		\ETE@suffix	380, 441, 444, 460, 485
		\ETE@WarnModDate	256, 260, 265
		F	
		\filename@base	411, 438
		\filename@parse	407
		G	
		\Gin@base	351, 382, 384,
		394, 397, 404, 407, 437, 443, 444	
		\Gin@driver	210, 514
		\Gin@eext	393, 394
		\Gin@ext	351, 392, 396, 397
		\Gin@setfile	313, 363
		\GraphicsRead	377, 382, 450
		\GraphicsType	376, 448
		\grffile@IfFileExists	331, 332
		I	
		\if	354, 360
		\ifcase	484
		\ifETE@disable	364
		\ifETE@InsideSetfile	343, 345
		\ifETE@prefersuffix	378
		\ifETE@prepend	235, 494
		\ifETE@update	255, 270
		\ifETE@verbose	418, 428
		\IfFileExists	329
		\ifnum	224, 271, 559, 567
		\ifx	11,
		14, 18, 44, 52, 55, 108, 111, 115,	
		141, 149, 152, 200, 210, 222,	
		253, 291, 305, 312, 328, 371,	
		380, 392, 403, 435, 441, 463,	
		484, 485, 523, 526, 529, 532, 571	
		\immediate	20, 46, 117, 143
		\includegraphics	423
		\input	513, 515, 572
		\InputIfFileExists	508, 509
		\iterate	540, 542, 544

	L		
\LoadCommand	572, 589	\repeat	538, 550, 561, 569
\loop	538, 554, 565	\RequirePackage 90, 195, 196, 197, 198, 321
		\resetatcatcode	516
	M	\RestoreCatcodes ..	552, 555, 556, 590
\MessageBreak	262, 297, 307, 317, 320, 322, 420, 421, 422		
	N		S
\newcommand ...	204, 216, 243, 344, 462	\setkeys	243
\newif	235, 343	\SetupKeyvalOptions	232
\next	387, 389, 544, 546, 548	\SourceExt ...	250, 393, 396, 399, 400
	O	\SourceFile	394, 397, 420, 426
\OutputDirectory 402, 403, 411, 435, 438, 484	\space	262, 298, 308, 316, 490
\OutputFile 404, 409, 421, 426, 430, 452, 490		
	P		T
\PackageInfo	23, 120	\Test	574, 592
\pdf@filemoddate	271, 286	\the	68, 69, 70, 71, 82, 165, 166, 167, 168, 179, 557
\pdf@filesize	288	\TMP@EnsureCode	79, 86, 87, 88, 176, 183, 184, 185, 186, 187, 188, 189, 190, 191, 192, 193, 194
\pdf@shellescape	224		
\pdf@strcmp	271		W
\pdf@system	427	\write	20, 46, 117, 143
\pdffilemoddate	262		
\PrependGraphicsExtensions ..	495, 502		X
\ProcessOptions	95	\x	10, 11, 14, 19, 23, 25, 45, 50, 60, 66, 74, 107, 108, 111, 116, 120, 122, 142, 147, 157, 163, 171, 209, 210, 335, 358, 371, 408, 415, 434, 455
\ProvidesPackage	15, 61, 112, 158		
	R		
\RangeCatcodeInvalid 563, 575, 576, 577, 578		