

The `epstopdf` package

Heiko Oberdiek
<oberdiek@uni-freiburg.de>

2009/07/16 v2.2

Abstract

This packages adds support of handling eps images to package `graphics` or `graphicx` with option `pdftex`. If an eps image is detected, `epstopdf` is automatically called to convert it to pdf format.

Contents

1	Documentation	2
1.1	Introduction	2
1.2	Requirements	2
1.3	Usage	3
1.4	Options	3
1.5	Configuration	5
1.5.1	System configuration file <code>epstopdf-sys.cfg</code>	5
1.5.2	User configuration file <code>epstopdf.cfg</code>	5
1.5.3	Conversion program	5
1.6	Other image formats	5
2	Implementation	6
2.1	Wrapper package	6
2.1.1	Option handling	7
2.2	Base package	7
2.3	Preparations	8
2.3.1	Relead check and identification	8
2.3.2	Catcodes	9
2.3.3	Load packages	9
2.4	Checks	9
2.5	Package loading	10
2.6	Options	10
2.6.1	Default setting	10
2.7	Make and verbose	10
2.8	Adding conversion support	11
2.9	Declare graphics rule	14
3	Test	15
3.1	Preface for standard catcode check	15
3.2	Catcode checks for loading	15
4	Installation	16
4.1	Download	16
4.2	Bundle installation	17
4.3	Package installation	17
4.4	Refresh file name databases	17
4.5	Some details for the interested	17

5	History	18
	[2001/01/06 v1.0]	18
	[2001/02/04 v1.1]	18
	[2006/02/20 v1.2]	18
	[2006/08/26 v1.3]	18
	[2007/04/26 v1.4]	18
	[2007/10/02 v1.5]	18
	[2007/11/11 v1.6]	18
	[2008/05/06 v1.7]	19
	[2009/03/01 v1.8]	19
	[2009/07/06 v1.9]	19
	[2009/07/07 v1.10]	19
	[2009/07/12 v2.0]	19
	[2009/07/15 v2.1]	19
	[2009/07/16 v2.2]	19
6	Index	19

1 Documentation

1.1 Introduction

L^AT_EX provides its graphics bundle to include graphics files. Both packages **graphics** or **graphicx** may be used. the latter one loads the first and adds options in key value style for `\includegraphics`.

Usually the drivers do not support all kind of graphics files. Other image types must be converted, before they become usable. In case of driver **dvips**, the **graphics** rule may contain a conversion rule. Then all that package **graphics** must know is the bounding box, the command is passed to **dvips** that calls it and embeds the converted image.

However, pdf_TE_X has its driver for PDF output already build in. It's graphics inclusion commands (`\pdfximage`) does not allow the execution of external commands. Therefore commands in the last argument of `\DeclareGraphicsRule` were of no use. But external programs can be called within pdf_TE_X. This feature is called "shell escape" or "write 18" and must usually enabled explicitley because of security reasons. Now, this package **epstopdf** hooks into package **graphics**' code to catch that argument with the external command and executes it to convert the graphics file to a supported format and passes the control of graphics inclusion back to package **graphics**.

1.2 Requirements

- The feature `\write18` must be enabled. This allows the running of external programs during T_EX's compile run. Keep in mind that this is a security risk. The feature is an addition to T_EX. MikT_EX, teT_EX, T_EX Live support it. In Web2C based T_EX distributions (teT_EX, T_EX Live) it can be enabled in the configuration file `texmf.cnf`:

```
shell_escape = 1
```

Because of the security risk, it is better to do it on the command line only:

```
--shell-escape (teTEX, TEX Live)
--enable-write18 (MiKTEX)
```

Example:

```
pdflatex -shell-escape test.tex
```

- The program `epstopdf` for the conversion from EPS to PDF. However, other programs can be used and configured by `\DeclareGraphicsRule`. Example:

```
\epstopdfDeclareGraphicsRule{.eps}{pdf}{.pdf}{%
  ps2pdf -dEPSCrop #1 \OutputFile
}
```

1.3 Usage

The package is loaded after `graphic{s,x}`, e.g.:

```
\usepackage[pdftex]{graphicx}
\usepackage{epstopdf}
```

Now images with file name extension `.eps` are detected and supported using `\includegraphics`.

If the graphics file name is explicitly specified with extension `.eps` the new rule for EPS files is called and the conversion performed. If option `update` is in force then the conversion step is dropped if the target file already exists and is not older than the EPS file.

The situation is more complicate if the graphics file is given without file name extension. Then the `graphics` package must search for a supported image file. The possible extensions are stored in the graphics extension list, that can be set by `\DeclareGraphicsExtensions`. The algorithm:

```
function search( <filebase> )
  foreach <ext> in <graphics extensions>
    foreach <dir> in <current directory>, <\graphicspath>
      <file> := <dir> + <filebase> + <ext>
      if exist <file>
        return found
  return not found
```

Package `epstopdf` puts `.eps` at the end of the graphics extension search list. This is the behaviour of option `append` that is enabled by default. That means, the conversion is called last unless a supported file type cannot be found earlier. This avoids unnecessary conversion steps that slow down the \LaTeX run. If you want to use option `update` and your `pdfTeX` supports it, then an outdated PDF file also would be found earlier unless `suffix` is used that is the default since version 2.0.

With an empty option `suffix` and option `prepend` there is a risk that an original PDF file is overwritten:

If the original image file is the PDF file and there is also a generated EPS file, then the original PDF file can be regenerated (depending on the option settings) and the original PDF file gets lost. Therefore option `suffix` is introduced in version 1.9 to create a separate name space for generated output files.

Note: Usually the conversion program needs the exact location of the image file. Usually the current directory works. Also if the image file is found using `\graphicspath`, the location is known. However, if the image is somewhere in a directory of environment variable `TEXINPUTS`, then the package does not know the exact location and the conversion program will not find the image file unless it implements a search using `TEXINPUTS` (program `kpsewhich` may be of help in this task).

1.4 Options

Options can be given as package options or later using:

`\epstopdfsetup {⟨key value list⟩}`

L^AT_EX expands the option list before passing the option list to the package's option handling code. This can fail for option `suffix` if it contains some of the macros described below. Use `\epstopdfsetup` after the package is loaded. Or load package `kvoptions-patch` before. This package is also loaded by option `patch` of package `kvoptions`. L^AT_EX's option code is redefined to respect key value options and let the values untouched.

update: The conversion program is only called, if the target file does not exist or is older than the source image file.

append: Puts the extension `.eps` at the end of the graphics extension list (default).

prepend: Puts the extension `.eps` at the begin of the graphics extension list.

outdir: The converted file may put in an other output directory. The value of `outdir` must include the directory separator. Example for the current directory:

```
\epstopdfsetup{outdir=./}
```

For other directories ensure, that they can be found. See `\graphicspath` or `TEXINPUTS`.

suffix: This option takes a string that is put between the file name base and the extension of the output file. Rationale: It can happen, that a PDF file is the original file and the EPS file the generated file. If now the package thinks, that the PDF file is the generated file, it will 'regenerate' it. But in reality the original file is lost. Therefore I recommend to use this option always to generate a separate name space for generated files. Proposed value is `-generated` or `.generated`. The suffix `.generated` will also work here without the need for package `grffile`).

Example:

```
\epstopdfsetup{suffix=-generated}
Then foo.eps is converted to foo-generated.pdf.
```

`\SourceExt` can be used inside the suffix string. It's will be replaced by the extension of the image source file without the leading dot, for instance:

```
\epstopdfsetup{suffix=-\SourceExt-converted-to}
foo.eps ⇒ foo-eps-converted-to.pdf
```

See also the next option `prefersuffix` that modifies the behaviour of option `suffix` in some cases.

Default for `suffix` is `'-\SourceExt-converted-to'`.

prefersuffix: If a suffix is set by option `suffix`, then there can be two image file names that could be taken into account for inclusion: A image file name with the suffix string inside its name and a image file name without; e.g. for `foo.eps` the names could be:

```
foo-suffix.pdf, foo.pdf
```

If option `perfersuffix` is turned on, the file `foo-suffix.pdf` and its generation is preferred over using `foo.pdf`. Otherwise `foo.pdf` is included without generating `foo-suffix.pdf`. The default of option `prefersuffix` is `true`.

verbose: It prints some information about the image in the `.log` file (default).

1.5 Configuration

1.5.1 System configuration file `epstopdf-sys.cfg`

If `epstopdf-sys` exists it is loaded at the end of the package `epstopdf-base` and before the user configuration file. It's intended for TeX distributors. Thus they could add additional conversion rules (e.g., `.gif -i .png`) or set options.

1.5.2 User configuration file `epstopdf.cfg`

A configuration file `epstopdf.cfg` is loaded at the end of the package if it exists. It can be used for changing the default option setting. Example:

```
\epstopdfsetup{verbose=false}
```

1.5.3 Conversion program

You can use `\DeclareGraphicsRule` in a similar way as the route via `dvips` to specify the conversion command line. The conversion argument starts with a back tick, followed by the conversion command including parameters.

The whole conversion argument should also be wrapped inside `\epstopdfcall`. This reduces the problem with packages (e.g. `pst-pdf`) that use the conversion argument and expands it. Macros `\SourceFile`, `\OutputFile`, and `\SourceExt` are not defined outside `epstopdf-base`'s `\Gin@setfile` and error messages because of undefined command names are the result. If `\epstopdfcall` detects that it is called outside `epstopdf-base`'s `\Gin@setfile` then it replaces the conversion argument by package `graphics`'s default, usually the image file.

The following macros are available inside:

`\OutputFile`: : output file name (with known path and extension)

`\SourceFile`: : source file name (with known path and extension), usually the same as `#1`,

`\SourceExt`: : source extension without leading dot.

Conversion from EPS to PDF. Other programs than `epstopdf` can be used to convert from EPS to PDF. Example that uses `Ghostscript`:

```
\DeclareGraphicsRule{.eps}{pdf}{.pdf}{%  
  \epstopdfcall{'ps2pdf -dEPSCrop #1 \noexpand\OutputFile}%  
}
```

`\DeclareGraphicsRule` expands the argument, therefore `\noexpand` is necessary. As convenience package `epstopdf-base` defines `\epstopdfDeclareGraphicsRule`. Then the conversion argument is not expanded, `\epstopdfcall` and the back tick are added:

```
\epstopdfDeclareGraphicsRule{.eps}{pdf}{.pdf}{%  
  ps2pdf -dEPSCrop #1 \OutputFile  
}
```

Also `\OutputFile` respects the setting of option `outdir`.

1.6 Other image formats

The support that package `epstopdf` implements is not limited to EPS files. Other image conversions can be declared. The following example shows it for GIF images under Unix with ImageMagick's `convert`:

```
\epstopdfDeclareGraphicsRule{.gif}{png}{.png}{%  
  convert #1 \OutputFile  
}
```

The file extension `.gif` can be added to the extension list that package `graphics` searches if the file extension is not given in `\includegraphics`. The list can be set by `\GraphicsExtensions`.

```
\AppendGraphicsExtensions{.gif}
or
\PrependGraphicsExtensions{.gif}
```

2 Implementation

```
1 (*package)
```

2.1 Wrapper package

Reload check, especially if the package is not used with L^AT_EX.

```
2 \begingroup
3 \catcode44 12 % ,
4 \catcode45 12 % -
5 \catcode46 12 % .
6 \catcode58 12 % :
7 \catcode64 11 % @
8 \catcode123 1 % {
9 \catcode125 2 % }
10 \expandafter\let\expandafter\x\csname ver@epstopdf.sty\endcsname
11 \ifx\x\relax % plain-TeX, first loading
12 \else
13 \def\empty{}%
14 \ifx\x\empty % LaTeX, first loading,
15 % variable is initialized, but \ProvidesPackage not yet seen
16 \else
17 \catcode35 6 % #
18 \expandafter\ifx\csname PackageInfo\endcsname\relax
19 \def\x#1#2{%
20 \immediate\write-1{Package #1 Info: #2.}%
21 }%
22 \else
23 \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
24 \fi
25 \x{epstopdf}{The package is already loaded}%
26 \aftergroup\endinput
27 \fi
28 \fi
29 \endgroup
```

Package identification:

```
30 \begingroup
31 \catcode35 6 % #
32 \catcode40 12 % (
33 \catcode41 12 % )
34 \catcode44 12 % ,
35 \catcode45 12 % -
36 \catcode46 12 % .
37 \catcode47 12 % /
38 \catcode58 12 % :
39 \catcode64 11 % @
40 \catcode91 12 % [
41 \catcode93 12 % ]
42 \catcode123 1 % {
43 \catcode125 2 % }
44 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
45 \def\x#1#2#3[#4]{\endgroup
46 \immediate\write-1{Package: #3 #4}%
```

```

47     \xdef#1{#4}%
48 }%
49 \else
50     \def\x#1#2[#3]{\endgroup
51     #2[#3]}%
52     \ifx#1\@undefined
53         \xdef#1{#3}%
54     \fi
55     \ifx#1\relax
56         \xdef#1{#3}%
57     \fi
58 }%
59 \fi
60 \expandafter\x\csname ver@epstopdf.sty\endcsname
61 \ProvidesPackage{epstopdf}%
62 [2009/07/16 v2.2 Conversion with epstopdf on the fly (HO)]

63 \begingroup
64 \catcode123 1 % {
65 \catcode125 2 % }
66 \def\x{\endgroup
67     \expandafter\edef\csname ETE@AtEnd\endcsname{%
68         \catcode35 \the\catcode35\relax
69         \catcode64 \the\catcode64\relax
70         \catcode123 \the\catcode123\relax
71         \catcode125 \the\catcode125\relax
72     }%
73 }%
74 \x
75 \catcode35 6 % #
76 \catcode64 11 % @
77 \catcode123 1 % {
78 \catcode125 2 % }
79 \def\TMP@EnsureCode#1#2{%
80     \edef\ETE@AtEnd{%
81         \ETE@AtEnd
82         \catcode#1 \the\catcode#1\relax
83     }%
84     \catcode#1 #2\relax
85 }
86 \TMP@EnsureCode{42}{12}% *
87 \TMP@EnsureCode{45}{12}% -
88 \TMP@EnsureCode{47}{12}% /

89 \let\ETE@SavedAtEnd\ETE@AtEnd
90 \RequirePackage{epstopdf-base}[2009/07/16]
91 \let\ETE@AtEnd\ETE@SavedAtEnd

```

2.1.1 Option handling

```

92 \DeclareOption*{%
93     \expandafter\epstopdfsetup\expandafter{\CurrentOption}%
94 }
95 \ProcessOptions*\relax

96 \ETE@AtEnd
97 \</package>

```

2.2 Base package

```

98 <*base>

```

2.3 Preparations

2.3.1 Relead check and identification

Reload check, especially if the package is not used with L^AT_EX.

```
99 \begingroup
100 \catcode44 12 % ,
101 \catcode45 12 % -
102 \catcode46 12 % .
103 \catcode58 12 % :
104 \catcode64 11 % @
105 \catcode123 1 % {
106 \catcode125 2 % }
107 \expandafter\let\expandafter\x\csname ver@epstopdf-base.sty\endcsname
108 \ifx\x\relax % plain-TeX, first loading
109 \else
110   \def\empty{}%
111   \ifx\x\empty % LaTeX, first loading,
112     % variable is initialized, but \ProvidesPackage not yet seen
113   \else
114     \catcode35 6 % #
115     \expandafter\ifx\csname PackageInfo\endcsname\relax
116       \def\x#1#2{%
117         \immediate\write-1{Package #1 Info: #2.}%
118       }%
119     \else
120       \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
121     \fi
122     \x{epstopdf-base}{The package is already loaded}%
123     \aftergroup\endinput
124   \fi
125 \fi
126 \endgroup
```

Package identification:

```
127 \begingroup
128 \catcode35 6 % #
129 \catcode40 12 % (
130 \catcode41 12 % )
131 \catcode44 12 % ,
132 \catcode45 12 % -
133 \catcode46 12 % .
134 \catcode47 12 % /
135 \catcode58 12 % :
136 \catcode64 11 % @
137 \catcode91 12 % [
138 \catcode93 12 % ]
139 \catcode123 1 % {
140 \catcode125 2 % }
141 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
142   \def\x#1#2#3[#4]{\endgroup
143     \immediate\write-1{Package: #3 #4}%
144     \xdef#1{#4}%
145   }%
146 \else
147   \def\x#1#2[#3]{\endgroup
148     #2[#{#3}]%
149     \ifx#1\@undefined
150       \xdef#1{#3}%
151     \fi
152     \ifx#1\relax
153       \xdef#1{#3}%
154     \fi
```



```

155     }%
156   \fi
157 \expandafter\x\csname ver@epstopdf-base.sty\endcsname
158 \ProvidesPackage{epstopdf-base}%
159 [2009/07/16 v2.2 Base part for package epstopdf]

```

2.3.2 Catcodes

```

160 \begingroup
161   \catcode\123 1 % {
162   \catcode\125 2 % }
163   \def\x{\endgroup
164     \expandafter\edef\csname ETE@AtEnd\endcsname{%
165       \catcode\35 \the\catcode\35\relax
166       \catcode\64 \the\catcode\64\relax
167       \catcode\123 \the\catcode\123\relax
168       \catcode\125 \the\catcode\125\relax
169     }%
170   }%
171 \x
172 \catcode\35 6 % #
173 \catcode\64 11 % @
174 \catcode\123 1 % {
175 \catcode\125 2 % }
176 \def\TMP@EnsureCode#1#2{%
177   \edef\ETE@AtEnd{%
178     \ETE@AtEnd
179     \catcode#1 \the\catcode#1\relax
180   }%
181   \catcode#1 #2\relax
182 }
183 \TMP@EnsureCode{33}{12}% !
184 \TMP@EnsureCode{39}{12}% '
185 \TMP@EnsureCode{42}{12}% *
186 \TMP@EnsureCode{44}{12}% ,
187 \TMP@EnsureCode{45}{12}% -
188 \TMP@EnsureCode{46}{12}% .
189 \TMP@EnsureCode{47}{12}% /
190 \TMP@EnsureCode{58}{12}% :
191 \TMP@EnsureCode{60}{12}% <
192 \TMP@EnsureCode{61}{12}% =
193 \TMP@EnsureCode{62}{12}% >
194 \TMP@EnsureCode{96}{12}% `

```

2.3.3 Load packages

```

195 \RequirePackage{infwarerr}[2007/09/09]
196 \RequirePackage{grfext}\relax
197 \RequirePackage{kvoptions}[2007/10/02]
198 \RequirePackage{pdftexcmds}[2007/11/11]

```

2.4 Checks

Check, whether package graphics is loaded (also graphicx loads graphics). Because miniltx.tex does not know \@ifpackageloaded we test for \Gin@setfile instead.

```

199 \begingroup\expandafter\expandafter\expandafter\endgroup
200 \expandafter\ifx\csname Gin@setfile\endcsname\relax
201   \@PackageWarningNoLine{epstopdf}{%
202     No graphics package \string'graphic{s,x}\string' loaded%
203   }%
204   \newcommand*{\epstopdfsetup}[1]{}%
205   \ETE@AtEnd
206 \expandafter\endinput
207 \fi

```

Check, whether pdftex.def is loaded. \ver@pdftex.def is not available with minilTeX, thus we test for \Gin@driver.

```

208 \begingroup
209   \def\x{pdftex.def}%
210   \ifx\Gin@driver\x
211   \else
212     \@PackageWarningNoLine{epstopdf}{%
213       Other drivers than 'pdftex.def' are not supported%
214     }%
215   \endgroup
216   \newcommand*{\epstopdfsetup}[1]{}%
217   \ETE@AtEnd
218   \expandafter\endinput
219 \fi
220 \endgroup

```

Check, whether the shell escape feature is enabled.

```

221 \begingroup
222   \expandafter\ifx\csname pdf@shellescape\endcsname\relax
223   \else
224     \ifnum\pdf@shellescape>0 %
225     \else
226       \@PackageWarningNoLine{epstopdf}{%
227         Shell escape feature is not enabled%
228       }%
229     \fi
230   \fi
231 \endgroup

```

2.5 Package loading

2.6 Options

```

232 \SetupKeyvalOptions{family=ETE,prefix=ETE@}
233 \DeclareBoolOption{update}
234 \DeclareBoolOption{verbose}
235 \newif\ifETE@prepend
236 \DeclareVoidOption{prepend}{\ETE@prependtrue}
237 \DeclareVoidOption{append}{\ETE@prependfalse}
238 \DeclareStringOption{outdir}
239 \DeclareStringOption{suffix}
240 \DeclareBoolOption{prefersuffix}

```

Options disable and enable are for testing only. Therefore they are not documented on purpose.

```

241 \DeclareBoolOption{disable}
242 \DeclareComplementaryOption{enable}{disable}
243 \newcommand*{\epstopdfsetup}{\setkeys{ETE}}

```

2.6.1 Default setting

```

244 \epstopdfsetup{%
245   verbose,%
246   enable,%
247   append,%
248   update,%
249   prefersuffix,%
250   suffix=-\SourceExt-converted-to%
251 }

```

2.7 Make and verbose

```

252 \begingroup\expandafter\expandafter\expandafter\endgroup
253 \expandafter\ifx\csname pdf@filemoddate\endcsname\relax

```

```

254 \def\ETE@Make#1#2{%
255   \ifETE@update
256     \ETE@WarnModDate
257   \fi
258   \@firstofone
259 }%
260 \def\ETE@WarnModDate{%
261   \@PackageWarningNoLine{epstopdf}{%
262     \string\pdf@filemoddate\space is not available,\MessageBreak
263     option 'update' will be ignored%
264   }%
265   \global\let\ETE@WarnModDate\relax
266 }%
267 \def\ETE@FileInfo#1#2{#1 file: <#2>}%
268 \else
269 \def\ETE@Make#1#2{%
270   \ifETE@update
271     \ifnum\pdf@strcmp{\pdf@filemoddate{#1}}{\pdf@filemoddate{#2}}>0 %
272     \expandafter\expandafter\expandafter\@firstofone
273   \else
274     \@PackageInfoNoLine{epstopdf}{%
275       Output file is already uptodate%
276     }%
277     \expandafter\expandafter\expandafter\@gobble
278   \fi
279 \else
280   \expandafter\@firstofone
281 \fi
282 }%
283 \def\ETE@FileInfo#1#2{%
284   #1 file: <#2>%
285   \expandafter\expandafter\expandafter
286   \ETE@Date\pdf@filemoddate{#2}\@nil
287   \expandafter\expandafter\expandafter
288   \ETE@Size\pdf@filesize{#2}\@nil
289 }%
290 \def\ETE@Date#1\@nil{%
291   \ifx\#1\%
292   \else
293     \ETE@@Date#1\@nil
294   \fi
295 }%
296 \def\ETE@@Date#1:#2#3#4#5#6#7#8#9{%
297   \MessageBreak
298   \@spaces\space\space\space date: #2#3#4#5-#6#7-#8#9 %
299   \ETE@@Time
300 }%
301 \def\ETE@@Time#1#2#3#4#5#6#7\@nil{%
302   #1#2:#3#4:#5#6%
303 }%
304 \def\ETE@Size#1\@nil{%
305   \ifx\#1\%
306   \else
307     \MessageBreak
308     \@spaces\space\space\space size: #1 bytes%
309   \fi
310 }%
311 \fi

```

2.8 Adding conversion support

Patch \Gin@setfile to execute #3, if it contains a command.

```

312 \expandafter\ifx\csname ETE@OrgGin@setfile\endcsname\relax

```

```

313 \let\ETE@OrgGin@setfile\Gin@setfile
314 \else
315 \@PackageError{epstopdf}{%
316   Command \string\ETE@OrgGin@setfile\space
317   already defined.\MessageBreak
318 }{%
319   Probably some package has included the code of this package%
320   \MessageBreak
321   instead of using \string\RequirePackage{epstopdf}.%
322   \MessageBreak
323   \@ehc
324 }%
325 \fi
326 \def\ETE@IfFileExists{%
327   \begingroup\expandafter\expandafter\expandafter\endgroup
328   \expandafter\ifx\csname grffile@IfFileExists\endcsname\relax
329     \expandafter\IfFileExists
330   \else
331     \global\let\ETE@IfFileExists\grffile@IfFileExists
332     \expandafter\grffile@IfFileExists
333   \fi
334 }
335 \def\ETE@Skip#1#2\x\fi\fi{%
336   \fi
337   \fi
338   \endgroup
339   \fi
340   \fi
341   #1%
342 }
343 \newif\ifETE@InsideSetfile
344 \newcommand*{\epstopdfcall}[1]{%
345   \ifETE@InsideSetfile
346     \expandafter\@firstoftwo
347   \else
348     \expandafter\@secondoftwo
349   \fi
350   {'#1}%
351   {\Gin@base\Gin@ext}%
352 }
353 \def\ETE@DefCommandLine#1{%
354   \edef\CommandLine{\expandafter\fi\if'#1}%
355 }
356 \def\ETE@DefX#1{%
357   \expandafter\expandafter\expandafter\def
358   \expandafter\expandafter\expandafter\x
359   \expandafter\expandafter\expandafter{%
360     \expandafter\fi\if'#1\relax\else
361   }%
362 }
363 \def\Gin@setfile#1#2#3{%
364   \ifETE@disable
365     \ETE@OrgGin@setfile{#1}{#2}{#3}%
366   \else
367     \begingroup
368       \ETE@InsideSetfiletrue
369       \ETE@DefX{#3}%
370     \expandafter\endgroup
371     \ifx\x\@empty
372       \ETE@OrgGin@setfile{#1}{#2}{#3}%
373     \else
374       \begingroup

```

```

375 \ETE@InsideSetfiletrue
376 \def\GraphicsType{#1}%
377 \def\GraphicsRead{#2}%
378 \ifETE@prefersuffix
379 \else
380 \ifx\ETE@suffix\empty
381 \else
382 \ETE@IfFileExists{\Gin@base\GraphicsRead}{%
383 \ETE@Skip{%
384 \ETE@OrgGin@setfile{#1}{#2}{\Gin@base#2}%
385 }%
386 }{%
387 \let\next\relax
388 }%
389 \next
390 \fi
391 \fi
392 \ifx\Gin@ext\relax
393 \let\SourceExt\Gin@eext
394 \def\SourceFile{\Gin@base\Gin@eext}%
395 \else
396 \let\SourceExt\Gin@ext
397 \def\SourceFile{\Gin@base\Gin@ext}%
398 \fi
399 \edef\SourceExt{% remove dot
400 \expandafter\@cdr\SourceExt\@empty\@nil
401 }%
402 \let\OutputDirectory\ETE@outdir
403 \ifx\OutputDirectory\empty
404 \edef\OutputFile{\ETE@GenerateName{\Gin@base}{#2}}%
405 \else
406 \begingroup
407 \filename@parse{\Gin@base#2}%
408 \edef\x{\endgroup
409 \def\noexpand\OutputFile{%
410 \ETE@GenerateName{%
411 \OutputDirectory\filename@base
412 }{#2}%
413 }%
414 }%
415 \x
416 \fi
417 \ETE@DefCommandLine{#3}%
418 \ifETE@verbose
419 \@PackageInfo{epstopdf}{%
420 \ETE@FileInfo{Source}\SourceFile\MessageBreak
421 \ETE@FileInfo{Output}\OutputFile\MessageBreak
422 Command: <\CommandLine>\MessageBreak
423 \string\includegraphics
424 }%
425 \fi
426 \ETE@Make\SourceFile\OutputFile{%
427 \pdf@system{\CommandLine}%
428 \ifETE@verbose
429 \@PackageInfoNoLine{epstopdf}{%
430 \ETE@FileInfo{Result}\OutputFile
431 }%
432 \fi
433 }%
434 \edef\x{\endgroup
435 \ifx\OutputDirectory\empty
436 \else

```

```

437         \def\noexpand\Gin@base{%
438             \OutputDirectory\noexpand\filename@base
439         }%
440     \fi
441     \ifx\ETE@suffix\@empty
442     \else
443         \edef\noexpand\Gin@base{\Gin@base\ETE@suffix}%
444     \fi
445     \noexpand\ETE@OrgGin@setfile{%
446         \GraphicsType
447     }{%
448         \GraphicsRead
449     }{%
450         \OutputFile
451     }%
452 }%
453 \x
454 \fi
455 \fi
456 }
457 \def\ETE@GenerateName#1#2{%
458     #1\ETE@suffix#2%
459 }

```

2.9 Declare graphics rule

```

460 \newcommand*{\epstopdfDeclareGraphicsRule}[4]{%
461     \ifx\\#4\\%
462         \@PackageError{epstopdf-base}{%
463             Conversion command is missing%
464         }\@ehc
465     \else
466         \begingroup
467             \@ifundefined{Gin@rule@#1}{%
468                 }{%
469                     \@PackageInfo{epstopdf-base}{%
470                         Redefining graphics rule for ‘#1’%
471                     }%
472                 }%
473         \endgroup
474         \@namedef{Gin@rule@#1}##1{{#2}{#3}{\epstopdfcall{#4}}}%
475     \fi
476 }

\DeclareGraphicsRule for .eps
477 \epstopdfDeclareGraphicsRule{.eps}{pdf}{.pdf}{%
478     \ETE@epstopdf{#1}%
479 }
480 \def\ETE@epstopdf#1{%
481     epstopdf %
482     \ifcase\ifx\OutputDirectory\@empty
483         \ifx\ETE@suffix\@empty
484             1%
485         \fi
486     \fi
487     0 %
488     --outfile=\OutputFile\space
489 \fi
490 #1%
491 }

492 \ifETE@prepend
493     \expandafter\PrependGraphicsExtensions
494 \else

```

```

495 \expandafter\AppendGraphicsExtensions
496 \fi
497 {.eps}
498 \let\ETE@prepend\@undefined
499 \DeclareVoidOption{prepend}{%
500   \PrependGraphicsExtensions{.eps}%
501 }
502 \let\ETE@append\@undefined
503 \DeclareVoidOption{append}{%
504   \AppendGraphicsExtensions{.eps}%
505 }

506 \InputIfFileExists{epstopdf-sys.cfg}{-}{-}
507 \InputIfFileExists{epstopdf.cfg}{-}{-}

508 \ETE@AtEnd
509 />base

```

3 Test

3.1 Preface for standard catcode check

```

510 (*test1)
511 \input miniltx.tex\relax
512 \def\Gin@driver{pdftex.def}
513 \input graphicx.sty\relax
514 \resetatcatcode
515 </test1>

```

3.2 Catcode checks for loading

```

516 (*test1)

517 \catcode'\{=1 %
518 \catcode'\}=2 %
519 \catcode'\#=6 %
520 \catcode'\@=11 %
521 \expandafter\ifx\csname count@\endcsname\relax
522   \countdef\count@=255 %
523 \fi
524 \expandafter\ifx\csname @gobble\endcsname\relax
525   \long\def\@gobble#1{}%
526 \fi
527 \expandafter\ifx\csname @firstofone\endcsname\relax
528   \long\def\@firstofone#1{#1}%
529 \fi
530 \expandafter\ifx\csname loop\endcsname\relax
531   \expandafter\@firstofone
532 \else
533   \expandafter\@gobble
534 \fi
535 {%
536   \def\loop#1\repeat{%
537     \def\body{#1}%
538     \iterate
539   }%
540   \def\iterate{%
541     \body
542     \let\next\iterate
543   \else
544     \let\next\relax
545   \fi
546   \next
547 }%
548 \let\repeat=\fi

```

```

549 }%
550 \def\RestoreCatcodes{}
551 \count@=0 %
552 \loop
553   \edef\RestoreCatcodes{%
554     \RestoreCatcodes
555     \catcode\the\count@=\the\catcode\count@\relax
556   }%
557 \ifnum\count@<255 %
558   \advance\count@ 1 %
559 \repeat
560
561 \def\RangeCatcodeInvalid#1#2{%
562   \count@=#1\relax
563   \loop
564     \catcode\count@=15 %
565     \ifnum\count@<#2\relax
566       \advance\count@ 1 %
567     \repeat
568 }
569 \expandafter\ifx\csname LoadCommand\endcsname\relax
570   \def\LoadCommand{\input epstopdf.sty\relax}%
571 \fi
572 \def\Test{%
573   \RangeCatcodeInvalid{0}{47}%
574   \RangeCatcodeInvalid{58}{64}%
575   \RangeCatcodeInvalid{91}{96}%
576   \RangeCatcodeInvalid{123}{255}%
577   \catcode'\@=12 %
578   \catcode'\=0 %
579   \catcode'\{=1 %
580   \catcode'\}=2 %
581   \catcode'\#=6 %
582   \catcode'\[=12 %
583   \catcode'\]=12 %
584   \catcode'\%=14 %
585   \catcode'\ =10 %
586   \catcode13=5 %
587   \LoadCommand
588   \RestoreCatcodes
589 }
590 \Test
591 \csname @@end\endcsname
592 \end
593 </test1>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/epstopdf.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/epstopdf.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

¹[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

TDS refers to the standard “A Directory Structure for \TeX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain- \TeX :

```
tex epstopdf.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>epstopdf.sty</code>	→ <code>tex/latex/oberdiek/epstopdf.sty</code>
<code>epstopdf-base.sty</code>	→ <code>tex/latex/oberdiek/epstopdf-base.sty</code>
<code>epstopdf.pdf</code>	→ <code>doc/latex/oberdiek/epstopdf.pdf</code>
<code>test/epstopdf-test1.tex</code>	→ <code>doc/latex/oberdiek/test/epstopdf-test1.tex</code>
<code>epstopdf.dtx</code>	→ <code>source/latex/oberdiek/epstopdf.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your \TeX distribution (`te \TeX` , `mik \TeX` , ...) relies on file name databases, you must refresh these. For example, `te \TeX` users run `texhash` or `mktextlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk epstopdf.pdf unpack_files output .
```

Unpacking with \LaTeX . The `.dtx` chooses its action depending on the format:

plain- \TeX : Run `docstrip` and extract the files.

\LaTeX : Generate the documentation.

If you insist on using \LaTeX for `docstrip` (really, `docstrip` does not need \LaTeX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{epstopdf.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex epstopdf.dtx
makeindex -s gind.ist epstopdf.idx
pdflatex epstopdf.dtx
makeindex -s gind.ist epstopdf.idx
pdflatex epstopdf.dtx
```

5 History

[2001/01/06 v1.0]

- First public version, published in the pdfT_EX mailing list.

[2001/02/04 v1.1]

- Minor documentation update.
- CTAN.

[2006/02/20 v1.2]

- DTX framework.
- Compatibility for `miniltx.tex`.

[2006/08/26 v1.3]

- Check for `\write18` if available and print a warning if the feature is not enabled.

[2007/04/26 v1.4]

- Documentation rewritten and extended.

[2007/10/02 v1.5]

- New option `update`: If the converted file exists, it will be only converted if it is out of date.
- Updating the extension list is delegated to package `grfext`. Fine tuning is done by the new options `append`, `prepend`.
- New option `outdir` for changing the output directory.
- New option `verbose`.
- `\SourceFile` and `\OutputFile` introduced.
- Configuration file support added.

[2007/11/11 v1.6]

- Use of package `pdftexcmds` for L^AT_EX support.

[2008/05/06 v1.7]

- Warning messages uses “loaded” instead of “found”.

[2009/03/01 v1.8]

- Warning message for missing `pdftex.def` changed.

[2009/07/06 v1.9]

- Option suffix added.

[2009/07/07 v1.10]

- `\SourceExt` added.
- If option suffix is set, the inclusion of an image without the suffix namespace is preferred over generating the the image within the suffix namespace.

[2009/07/12 v2.0]

- New default settings.
- Package is split into `epstopdf` that only takes package options and loads `epstopdf-base` that does the work.
- `\epstopdfDeclareGraphicsRule` and `\epstopdfcall` added.
- `epstopdf-sys.cfg` is loaded before `epstopdf.cfg` if `epstopdf-sys.cfg` exists.

[2009/07/15 v2.1]

- Default setting: `verbose` is now turned on as the documentation for v2.0 said.
- Documentation fixes.

[2009/07/16 v2.2]

- Fixed redefined `\Gin@setfile`.
- Documentation extended for package options.

6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		380, 400, 403, 435, 441, 482, 483
<code>\#</code>	519, 581	<code>\@firstofone</code> .. 258, 272, 280, 528, 531
<code>\%</code>	584	<code>\@firstoftwo</code> 346
<code>\@</code>	520, 577	<code>\@gobble</code> 277, 525, 533
<code>\@PackageError</code>	315, 462	<code>\@ifundefined</code> 467
<code>\@PackageInfo</code>	419, 469	<code>\@namedef</code> 474
<code>\@PackageInfoNoLine</code>	274, 429	<code>\@nil</code> . 286, 288, 290, 293, 301, 304, 400
<code>\@PackageWarningNoLine</code>	201, 212, 226, 261	<code>\@secondoftwo</code> 348
<code>\@cdr</code>	400	<code>\@spaces</code> 298, 308
<code>\@ehc</code>	323, 464	<code>\@undefined</code> 52, 149, 498, 502
<code>\@empty</code>	371,	<code>\[</code> 582
		<code>\</code> 291, 305, 461, 578

\{	517, 579	\ETE@DefX	356, 369
\}	518, 580	\ETE@epstopdf	478, 480
\]	583	\ETE@FileInfo	267, 283, 420, 421, 430
		\ETE@GenerateName	404, 410, 457
		\ETE@ifFileExists	326, 331, 382
_	585	\ETE@InsideSetfiletrue	368, 375
		\ETE@Make	254, 269, 426
		\ETE@OrgGin@setfile	313, 316, 365, 372, 384, 445
A		\ETE@outdir	402
\advance	558, 566	\ETE@prepend	498
\aftergroup	26, 123	\ETE@prependfalse	237
\AppendGraphicsExtensions	495, 504	\ETE@prependtrue	236
		\ETE@SavedAtEnd	89, 91
B		\ETE@Size	288, 304
\body	537, 541	\ETE@Skip	335, 383
		\ETE@suffix	380, 441, 443, 458, 483
C		\ETE@WarnModDate	256, 260, 265
\catcode	3, 4, 5, 6, 7, 8, 9, 17, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 64, 65, 68, 69, 70, 71, 75, 76, 77, 78, 82, 84, 100, 101, 102, 103, 104, 105, 106, 114, 128, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 161, 162, 165, 166, 167, 168, 172, 173, 174, 175, 179, 181, 517, 518, 519, 520, 555, 564, 577, 578, 579, 580, 581, 582, 583, 584, 585, 586		
\CommandLine	354, 422, 427		
\count@	522, 551, 555, 557, 558, 562, 564, 565, 566		
\countdef	522		
\csname	10, 18, 44, 60, 67, 107, 115, 141, 157, 164, 200, 222, 253, 312, 328, 521, 524, 527, 530, 569, 591		
\CurrentOption	93		
D			
\DeclareBoolOption	233, 234, 240, 241		
\DeclareComplementaryOption	242		
\DeclareOption	92		
\DeclareStringOption	238, 239		
\DeclareVoidOption	236, 237, 499, 503		
E			
\empty	13, 14, 110, 111		
\end	592		
\endcsname	10, 18, 44, 60, 67, 107, 115, 141, 157, 164, 200, 222, 253, 312, 328, 521, 524, 527, 530, 569, 591		
\endinput	26, 123, 206, 218		
\epstopdfcall	344, 474		
\epstopdfDeclareGraphicsRule	460, 477		
\epstopdfsetup	4, 93, 204, 216, 243, 244		
\ETE@Date	293, 296		
\ETE@Time	299, 301		
\ETE@append	502		
\ETE@AtEnd	80, 81, 89, 91, 96, 177, 178, 205, 217, 508		
\ETE@Date	286, 290		
\ETE@DefCommandLine	353, 417		
		F	
		\filename@base	411, 438
		\filename@parse	407
		G	
		\Gin@base	351, 382, 384, 394, 397, 404, 407, 437, 443
		\Gin@driver	210, 512
		\Gin@eext	393, 394
		\Gin@ext	351, 392, 396, 397
		\Gin@setfile	313, 363
		\GraphicsRead	377, 382, 448
		\GraphicsType	376, 446
		\grffile@ifFileExists	331, 332
		I	
		\if	354, 360
		\ifcase	482
		\ifETE@disable	364
		\ifETE@InsideSetfile	343, 345
		\ifETE@prefersuffix	378
		\ifETE@prepend	235, 492
		\ifETE@update	255, 270
		\ifETE@verbose	418, 428
		\IfFileExists	329
		\ifnum	224, 271, 557, 565
		\ifx	11, 14, 18, 44, 52, 55, 108, 111, 115, 141, 149, 152, 200, 210, 222, 253, 291, 305, 312, 328, 371, 380, 392, 403, 435, 441, 461, 482, 483, 521, 524, 527, 530, 569
		\immediate	20, 46, 117, 143
		\includegraphics	423
		\input	511, 513, 570
		\InputIfFileExists	506, 507
		\iterate	538, 540, 542
		L	
		\LoadCommand	570, 587
		\loop	536, 552, 563
		M	
		\MessageBreak	262, 297, 307, 317, 320, 322, 420, 421, 422

N			
\newcommand ...	204, 216, 243, 344, 460	\resetatcatcode	514
\newif	235, 343	\RestoreCatcodes ..	550, 553, 554, 588
\next	387, 389, 542, 544, 546	S	
O		\setkeys	243
\OutputDirectory		\SetupKeyvalOptions	232
.....	402, 403, 411, 435, 438, 482	\SourceExt ...	250, 393, 396, 399, 400
\OutputFile		\SourceFile	394, 397, 420, 426
.	404, 409, 421, 426, 430, 450, 488	\space	262, 298, 308, 316, 488
P		T	
\PackageInfo	23, 120	\Test	572, 590
\pdf@filemoddate	271, 286	\the	68, 69, 70,
\pdf@filesize	288		71, 82, 165, 166, 167, 168, 179, 555
\pdf@shellescape	224	\TMP@EnsureCode	79, 86, 87,
\pdf@strcmp	271		88, 176, 183, 184, 185, 186, 187,
\pdf@system	427		188, 189, 190, 191, 192, 193, 194
\pdffilemoddate	262	W	
\PrependGraphicsExtensions .	493, 500	\write	20, 46, 117, 143
\ProcessOptions	95	X	
\ProvidesPackage	15, 61, 112, 158	\x	10, 11, 14, 19,
R			23, 25, 45, 50, 60, 66, 74, 107,
\RangeCatcodeInvalid			108, 111, 116, 120, 122, 142,
.....	561, 573, 574, 575, 576		147, 157, 163, 171, 209, 210,
\repeat	536, 548, 559, 567		335, 358, 371, 408, 415, 434, 453
\RequirePackage			
.....	90, 195, 196, 197, 198, 321		