

# The `fibnum` package

Heiko Oberdiek

<heiko.oberdiek at gmail.com>

2012/04/08 v1.0

## Abstract

The package `fibnum` provides expandable fibonacci numbers for both  $\text{\LaTeX}$  and plain  $\text{\TeX}$ .

## Contents

<b>1</b>	<b>Documentation</b>	<b>1</b>
<b>2</b>	<b>Implementation</b>	<b>4</b>
2.1	Identification . . . . .	4
2.2	Package resources . . . . .	6
2.3	Setup precalculated values . . . . .	6
2.4	Macros for precalculating values . . . . .	7
2.5	Expandable calculations . . . . .	8
<b>3</b>	<b>Test</b>	<b>9</b>
3.1	Catcode checks for loading . . . . .	9
3.2	Test calculations . . . . .	11
<b>4</b>	<b>Installation</b>	<b>13</b>
4.1	Download . . . . .	13
4.2	Bundle installation . . . . .	13
4.3	Package installation . . . . .	14
4.4	Refresh file name databases . . . . .	14
4.5	Some details for the interested . . . . .	14
<b>5</b>	<b>History</b>	<b>15</b>
	[2012/04/08 v1.0] . . . . .	15
<b>6</b>	<b>Index</b>	<b>15</b>

## 1 Documentation

In the mailing list `texhax` Jan Abraham asked the question, how to get Fibonacci numbers in  $\text{\TeX}$  [`texhax:abraham`]:

Write a Macro in  $\text{\TeX}$  that compute the function `\fib{m}`. All fibonacci numbers from 1 to  $m$  ( $m < 40$ ).

This packages provides an expandable implementation for the calculation of these numbers for a much larger set of indexes. For practical reasons the index is restricted to the same limitations that apply for T<sub>E</sub>X integer numbers. The range of the Fibonacci numbers, however, are not limited by the algorithm. They are only restricted to memory limitations, if they are hit.

The package is loaded as L<sup>A</sup>T<sub>E</sub>X package in L<sup>A</sup>T<sub>E</sub>X:

```
\usepackage{fibnum}
```

and as file in plain T<sub>E</sub>X:

```
\input fibnum.sty
```

The package does not know any options and it provides the macros `\fibnum` and `\fibnumPreCalc`.

`\fibnum {⟨index⟩}`

Macro `\fibnum` expects a T<sub>E</sub>X number as  $\langle index \rangle$  in the official T<sub>E</sub>X number range from  $-(2^{31} - 1)$  up to  $2^{31} - 1$ . In exact two expansion steps the macro expands to the Fibnoacci number  $F_{\langle index \rangle}$ . In case of a negative  $\langle index \rangle$ , the “negafibonacci” number [**wikipedia:negafibonacci**] is used. Formally the Fibonacci number  $F_n$  with integer index  $n$ ,  $n \in \mathbb{Z}$  and  $n \in [-2\,147\,483\,647, 2\,147\,483\,647]$  that is returned by macro `\fibnum` with numerical argument  $n$  is defined the following way:

$$F_n = \begin{cases} 0 & \text{for } n = 0 \\ 1 & \text{for } n = 1 \\ F_{n-1} + F_{n-2} & \text{for } n > 1 \\ (-1)^{n+1} F_n & \text{for } n < 0 \end{cases} \quad (1)$$

Examples:

```

\fibnum{-6} → -8
\fibnum{-5} → 5
\fibnum{-4} → -3
\fibnum{-3} → 2
\fibnum{-2} → -1
\fibnum{-1} → 1
\fibnum{0} → 0
\fibnum{1} → 1
\fibnum{2} → 1
\fibnum{3} → 2
\fibnum{4} → 3
\fibnum{5} → 5
\fibnum{6} → 8
⋮
\fibnum{10} → 55
⋮
\fibnum{46} → 1836311903
⋮
\fibnum{100} → 354224848179261915075
⋮
\fibnum{200} → 280571172992510140037611932413038677189525
⋮
\fibnum{1000} → 434665576869374564356885276750406258025646
605173717804024817290895365554179490518904
038798400792551692959225930803226347752096
896232398733224711616429964409065331879382
98969649928516003704476137795166849228875

```

`\fibnumPreCalc {⟨index⟩}`

The package already provides precalculated Fibonacci numbers up to index 46. That means that calculations are not necessary for Fibonacci numbers that fit into the range of  $\text{T}_{\text{E}}\text{X}$  numbers. Because macro `\fibnum` is expandable, it cannot store calculated Fibonacci numbers for later use. Macro definitions are forbidden in expandable contexts. If larger Fibonacci numbers are used more than once, then the compilation time can be shortened by calculating and storing the Fibonacci numbers beforehand. The argument  $\langle index \rangle$  is a  $\text{T}_{\text{E}}\text{X}$  number and macro `\fibnumPreCalc` ensures that the Fibonacci numbers  $F_0$  up to  $F_{|\langle index \rangle|}$  that are not already known are calculated and stored in internal macros. Internally only non-negative Fibonacci numbers are stored. If  $\langle index \rangle$  is negative, then the needed positive Fibonacci numbers are calculated and stored. Example:

```

\fibnumPreCalc{50}
% calculates and stores the values for indexes 47..50.
% (Values for 0..46 are already stored by the package.)
\fibnum{49} % uses the stored value
\fibnum{51} % only calculates  $F_{51}$  from stored values  $F_{49}$  and  $F_{50}$ 
\fibnumPreCalc{100}
% calculates and stores the values for indexes 51..100
\fibnum{100} % uses the stored value for  $F_{100}$ 
\fibnum{-100} % uses the stored value for  $F_{100}$ 

```

$F_{-100} = -F_{100}$  according to equation (1).

## 2 Implementation

### 2.1 Identification

```

1 (*package)
Reload check, especially if the package is not used with LATEX.
2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3 \catcode13=5 % ^M
4 \endlinechar=13 %
5 \catcode35=6 % #
6 \catcode39=12 % '
7 \catcode44=12 % ,
8 \catcode45=12 % -
9 \catcode46=12 % .
10 \catcode58=12 % :
11 \catcode64=11 % @
12 \catcode123=1 % {
13 \catcode125=2 % }
14 \expandafter\let\expandafter\x\csname ver@fibnum.sty\endcsname
15 \ifx\x\relax % plain-TeX, first loading
16 \else
17 \def\empty{}%
18 \ifx\x\empty % LaTeX, first loading,
19 % variable is initialized, but \ProvidesPackage not yet seen
20 \else
21 \expandafter\ifx\csname PackageInfo\endcsname\relax
22 \def\x#1#2{%
23 \immediate\write-1{Package #1 Info: #2.}%
24 }%
25 \else
26 \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27 \fi
28 \x{fibnum}{The package is already loaded}%
29 \aftergroup\endinput
30 \fi
31 \fi
32 \endgroup%
Package identification:
33 \begingroup\catcode61\catcode48\catcode32=10\relax%
34 \catcode13=5 % ^M
35 \endlinechar=13 %
36 \catcode35=6 % #
37 \catcode39=12 % '
38 \catcode40=12 % (
39 \catcode41=12 % )
40 \catcode44=12 % ,
41 \catcode45=12 % -
42 \catcode46=12 % .
43 \catcode47=12 % /
44 \catcode58=12 % :
45 \catcode64=11 % @
46 \catcode91=12 % [
47 \catcode93=12 % ]
48 \catcode123=1 % {
49 \catcode125=2 % }

```

```

50 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
51 \def\x#1#2#3[#4]{\endgroup
52 \immediate\write-1{Package: #3 #4}%
53 \xdef#1{#4}%
54 }%
55 \else
56 \def\x#1#2[#3]{\endgroup
57 #2[{#3}]%
58 \ifx#1\@undefined
59 \xdef#1{#3}%
60 \fi
61 \ifx#1\relax
62 \xdef#1{#3}%
63 \fi
64 }%
65 \fi
66 \expandafter\x\csname ver@fibnum.sty\endcsname
67 \ProvidesPackage{fibnum}%
68 [2012/04/08 v1.0 Fibonacci numbers (HO)]%
69 \begingroup\catcode61\catcode48\catcode32=10\relax%
70 \catcode13=5 % ^~M
71 \endlinechar=13 %
72 \catcode123=1 % {
73 \catcode125=2 % }
74 \catcode64=11 % @
75 \def\x{\endgroup
76 \expandafter\edef\csname FibNum@AtEnd\endcsname{%
77 \endlinechar=\the\endlinechar\relax
78 \catcode13=\the\catcode13\relax
79 \catcode32=\the\catcode32\relax
80 \catcode35=\the\catcode35\relax
81 \catcode61=\the\catcode61\relax
82 \catcode64=\the\catcode64\relax
83 \catcode123=\the\catcode123\relax
84 \catcode125=\the\catcode125\relax
85 }%
86 }%
87 \x\catcode61\catcode48\catcode32=10\relax%
88 \catcode13=5 % ^~M
89 \endlinechar=13 %
90 \catcode35=6 % #
91 \catcode64=11 % @
92 \catcode123=1 % {
93 \catcode125=2 % }
94 \def\TMP@EnsureCode#1#2{%
95 \edef\FibNum@AtEnd{%
96 \FibNum@AtEnd
97 \catcode#1=\the\catcode#1\relax
98 }%
99 \catcode#1=#2\relax
100 }
101 \TMP@EnsureCode{33}{12}% !
102 %\TMP@EnsureCode{36}{3}% $
103 %\TMP@EnsureCode{38}{4}% &
104 \TMP@EnsureCode{40}{12}% (
105 \TMP@EnsureCode{41}{12}% )
106 \TMP@EnsureCode{45}{12}% -
107 \TMP@EnsureCode{46}{12}% .

```

```

108 \TMP@EnsureCode{47}{12}% /
109 \TMP@EnsureCode{58}{12}% :
110 \TMP@EnsureCode{60}{12}% <
111 \TMP@EnsureCode{62}{12}% >
112 \TMP@EnsureCode{91}{12}% [
113 %\TMP@EnsureCode{96}{12}% '
114 \TMP@EnsureCode{93}{12}% ]
115 %\TMP@EnsureCode{94}{12}% ^ (superscript) (!)
116 %\TMP@EnsureCode{124}{12}% |
117 \edef\FibNum@AtEnd{\FibNum@AtEnd\noexpand\endinput}

```

## 2.2 Package resources

```

118 \begingroup\expandafter\expandafter\expandafter\endgroup
119 \expandafter\ifx\csname RequirePackage\endcsname\relax
120   \def\TMP@RequirePackage#1[#2]{%
121     \begingroup\expandafter\expandafter\expandafter\endgroup
122     \expandafter\ifx\csname ver@#1.sty\endcsname\relax
123       \input #1.sty\relax
124     \fi
125   }%
126   \TMP@RequirePackage{ltxcmds}[2011/04/18]%
127   \TMP@RequirePackage{intcalc}[2007/09/27]%
128   \TMP@RequirePackage{bigintcalc}[2007/11/11]%
129 \else
130   \RequirePackage{ltxcmds}[2011/04/18]%
131   \RequirePackage{intcalc}[2007/09/27]%
132   \RequirePackage{bigintcalc}[2007/11/11]%
133 \fi

```

## 2.3 Setup precalculated values

```

134 \def\FibNum@temp#1{%
135   \expandafter\def\csname FibNum@#1\endcsname
136 }
137 \catcode46=9 % dots are ignored
138 \FibNum@temp{0}{0}
139 \FibNum@temp{1}{1}
140 \FibNum@temp{2}{1}
141 \FibNum@temp{3}{2}
142 \FibNum@temp{4}{3}
143 \FibNum@temp{5}{5}
144 \FibNum@temp{6}{8}
145 \FibNum@temp{7}{13}
146 \FibNum@temp{8}{21}
147 \FibNum@temp{9}{34}
148 \FibNum@temp{10}{55}
149 \FibNum@temp{11}{89}
150 \FibNum@temp{12}{144}
151 \FibNum@temp{13}{233}
152 \FibNum@temp{14}{377}
153 \FibNum@temp{15}{610}
154 \FibNum@temp{16}{987}
155 \FibNum@temp{17}{1.597}
156 \FibNum@temp{18}{2.584}
157 \FibNum@temp{19}{4.181}
158 \FibNum@temp{20}{6.765}
159 \FibNum@temp{21}{10.946}
160 \FibNum@temp{22}{17.711}
161 \FibNum@temp{23}{28.657}

```

```

162 \FibNum@temp{24}{46.368}
163 \FibNum@temp{25}{75.025}
164 \FibNum@temp{26}{121.393}
165 \FibNum@temp{27}{196.418}
166 \FibNum@temp{28}{317.811}
167 \FibNum@temp{29}{514.229}
168 \FibNum@temp{30}{832.040}
169 \FibNum@temp{31}{1.346.269}
170 \FibNum@temp{32}{2.178.309}
171 \FibNum@temp{33}{3.524.578}
172 \FibNum@temp{34}{5.702.887}
173 \FibNum@temp{35}{9.227.465}
174 \FibNum@temp{36}{14.930.352}
175 \FibNum@temp{37}{24.157.817}
176 \FibNum@temp{38}{39.088.169}
177 \FibNum@temp{39}{63.245.986}
178 \FibNum@temp{40}{102.334.155}
179 \FibNum@temp{41}{165.580.141}
180 \FibNum@temp{42}{267.914.296}
181 \FibNum@temp{43}{433.494.437}
182 \FibNum@temp{44}{701.408.733}
183 \FibNum@temp{45}{1.134.903.170}
184 \FibNum@temp{46}{1.836.311.903}

\FibNum@max

185 \def\FibNum@max{46}

```

## 2.4 Macros for precalculating values

```

\fibnumPreCalc

186 \def\fibnumPreCalc#1{%
187   \expandafter\expandafter\expandafter
188   \FibNum@PreCalc\intcalcNum{#1}/%
189 }

\FibNum@PreCalc

190 \def\FibNum@PreCalc#1/{%
191   \ifnum#1<\ltx@zero
192     \expandafter\FibNum@PreCalc\ltx@gobble#1/%
193   \else
194     \ifnum#1>\FibNum@max
195       \begingroup
196         \ltx@LocDimenA=#1sp\relax
197         \countdef\FibNum@i=255\relax
198         \FibNum@i=\FibNum@max\relax
199         \edef\FibNum@temp{%
200           \csname FibNum@the\FibNum@i\endcsname/%
201         }%
202         \advance\FibNum@i by -1\relax
203         \edef\FibNum@temp{%
204           \FibNum@temp
205           \csname FibNum@the\FibNum@i\endcsname
206         }%
207         \advance\FibNum@i\ltx@two
208         \iftrue
209           \expandafter\FibNum@PreCalcAux\FibNum@temp
210         \fi
211       \endgroup

```

```

212   \fi
213   \fi
214 }

\FibNum@PreCalcAux

215 \def\FibNum@PreCalcAux#1/#2\fi{%
216   \fi
217   \edef\FibNum@temp{\BigIntCalcAdd#1!#2!}%
218   \global\expandafter
219   \let\csname FibNum@\the\FibNum@i\endcsname\FibNum@temp
220   \ifnum\FibNum@i=\ltx@LocDimenA
221     \xdef\FibNum@max{\the\FibNum@i}%
222   \else
223     \advance\FibNum@i\ltx@one
224     \expandafter\FibNum@PreCalcAux\FibNum@temp/#1%
225   \fi
226 }

```

## 2.5 Expandable calculations

```

\fibnum

227 \def\fibnum#1{%
228   \romannumeral
229   \expandafter\expandafter\expandafter\FibNum@Do\intcalcNum{#1}/%
230 }

\FibNum@Do

231 \def\FibNum@Do#1/{%
232   \ifnum#1<\ltx@zero
233     \FibNum@ReturnAfterElseFiFi{%
234       \ifodd#1 %
235         \expandafter\expandafter\expandafter\ltx@zero
236       \else
237         \expandafter\expandafter\expandafter\ltx@zero
238         \expandafter\expandafter\expandafter~%
239       \fi
240       \romannumeral
241       \expandafter\FibNum@Do\ltx@gobble#1/%
242     }%
243   \else
244     \ifnum\FibNum@max<#1 %
245       \ltx@ReturnAfterElseFiFi{%
246         \expandafter
247         \FibNum@ExpCalc\number\expandafter\IntCalcInc\FibNum@max!%
248         \expandafter\expandafter\expandafter/%
249         \csname FibNum@\FibNum@max
250         \expandafter\expandafter\expandafter\endcsname
251         \expandafter\expandafter\expandafter/%
252         \csname FibNum@\expandafter\IntCalcDec\FibNum@max!%
253         \endcsname/%
254         #1%
255       }%
256     \else
257       \expandafter\expandafter\expandafter\ltx@zero
258       \csname FibNum@#1\expandafter\expandafter\expandafter\endcsname
259     \fi
260   \fi
261 }

```

\FibNum@ReturnAfterElseFiFi

```
262 \def\FibNum@ReturnAfterElseFiFi#1\else#2\fi\fi{\fi#1}
```

\FibNum@ExpCalc

```
263 \def\FibNum@ExpCalc#1/#2/#3/#4\fi{%
264   \fi
265   \ifnum#1=#4 %
266     \ltx@ReturnAfterElseFi{%
267       \expandafter\expandafter\expandafter\ltx@zero
268       \BigIntCalcAdd#2!#3!%
269     }%
270   \else
271     \expandafter\FibNum@ExpCalc
272     \number\IntCalcInc#1!%
273     \expandafter\expandafter\expandafter/%
274     \BigIntCalcAdd#2!#3!/%
275     #2/#4%
276   \fi
277 }

278 \FibNum@AtEnd%
279 \</package>
```

### 3 Test

#### 3.1 Catcode checks for loading

```
280 \<{*test1}

281 \catcode'\{=1 %
282 \catcode'\}=2 %
283 \catcode'\#=6 %
284 \catcode'\@=11 %
285 \expandafter\ifx\csname count@\endcsname\relax
286   \countdef\count@=255 %
287 \fi
288 \expandafter\ifx\csname @gobble\endcsname\relax
289   \long\def\@gobble#1{%
290 \fi
291 \expandafter\ifx\csname @firstofone\endcsname\relax
292   \long\def\@firstofone#1{#1}%
293 \fi
294 \expandafter\ifx\csname loop\endcsname\relax
295   \expandafter\@firstofone
296 \else
297   \expandafter\@gobble
298 \fi
299 {%
300   \def\loop#1\repeat{%
301     \def\body{#1}%
302     \iterate
303   }%
304   \def\iterate{%
305     \body
306     \let\next\iterate
307   \else
308     \let\next\relax
309   \fi
```

```

310 \next
311 }%
312 \let\repeat=\fi
313 }%
314 \def\RestoreCatcodes{}
315 \count@=0 %
316 \loop
317 \edef\RestoreCatcodes{%
318 \RestoreCatcodes
319 \catcode\the\count@=\the\catcode\count@\relax
320 }%
321 \ifnum\count@<255 %
322 \advance\count@ 1 %
323 \repeat
324
325 \def\RangeCatcodeInvalid#1#2{%
326 \count@=#1\relax
327 \loop
328 \catcode\count@=15 %
329 \ifnum\count@<#2\relax
330 \advance\count@ 1 %
331 \repeat
332 }
333 \def\RangeCatcodeCheck#1#2#3{%
334 \count@=#1\relax
335 \loop
336 \ifnum#3=\catcode\count@
337 \else
338 \errmessage{%
339 Character \the\count@\space
340 with wrong catcode \the\catcode\count@\space
341 instead of \number#3%
342 }%
343 \fi
344 \ifnum\count@<#2\relax
345 \advance\count@ 1 %
346 \repeat
347 }
348 \def\space{ }
349 \expandafter\ifx\csname LoadCommand\endcsname\relax
350 \def\LoadCommand{\input fibnum.sty\relax}%
351 \fi
352 \def\Test{%
353 \RangeCatcodeInvalid{0}{47}%
354 \RangeCatcodeInvalid{58}{64}%
355 \RangeCatcodeInvalid{91}{96}%
356 \RangeCatcodeInvalid{123}{255}%
357 \catcode'\@=12 %
358 \catcode'\=0 %
359 \catcode'\%=14 %
360 \LoadCommand
361 \RangeCatcodeCheck{0}{36}{15}%
362 \RangeCatcodeCheck{37}{37}{14}%
363 \RangeCatcodeCheck{38}{47}{15}%
364 \RangeCatcodeCheck{48}{57}{12}%
365 \RangeCatcodeCheck{58}{63}{15}%
366 \RangeCatcodeCheck{64}{64}{12}%
367 \RangeCatcodeCheck{65}{90}{11}%

```

```

368 \RangeCatcodeCheck{91}{91}{15}%
369 \RangeCatcodeCheck{92}{92}{0}%
370 \RangeCatcodeCheck{93}{96}{15}%
371 \RangeCatcodeCheck{97}{122}{11}%
372 \RangeCatcodeCheck{123}{255}{15}%
373 \RestoreCatcodes
374 }
375 \Test
376 \csname @@end\endcsname
377 \end
378 </test1>

```

### 3.2 Test calculations

```

379 <*test-calc>
380 \catcode'\{=1 %
381 \catcode'\}=2 %
382 \catcode'\#=6 %
383 \catcode'\@=11 %
384 \begingroup\expandafter\expandafter\expandafter\endgroup
385 \expandafter\ifx\csname RequirePackage\endcsname\relax
386 \input fibnum.sty\relax
387 \else
388 \RequirePackage{fibnum}[2012/04/08]%
389 \fi
390 \def\TestSet{%
391 \test{0}{0}%
392 \test{1}{1}%
393 \test{2}{1}%
394 \test{3}{2}%
395 \test{4}{3}%
396 \test{5}{5}%
397 \test{6}{8}%
398 \test{7}{13}%
399 \test{8}{21}%
400 \test{9}{34}%
401 \test{10}{55}%
402 \test{11}{89}%
403 \test{12}{144}%
404 \test{13}{233}%
405 \test{14}{377}%
406 \test{15}{610}%
407 \test{16}{987}%
408 \test{17}{1597}%
409 \test{18}{2584}%
410 \test{19}{4181}%
411 \test{20}{6765}%
412 \test{21}{10946}%
413 \test{22}{17711}%
414 \test{23}{28657}%
415 \test{24}{46368}%
416 \test{25}{75025}%
417 \test{26}{121393}%
418 \test{27}{196418}%
419 \test{28}{317811}%
420 \test{29}{514229}%
421 \test{30}{832040}%
422 \test{31}{1346269}%
423 \test{32}{2178309}%

```

```

424 \test{33}{3524578}%
425 \test{34}{5702887}%
426 \test{35}{9227465}%
427 \test{36}{14930352}%
428 \test{37}{24157817}%
429 \test{38}{39088169}%
430 \test{39}{63245986}%
431 \test{40}{102334155}%
432 \test{41}{165580141}%
433 \test{42}{267914296}%
434 \test{43}{433494437}%
435 \test{44}{701408733}%
436 \test{45}{1134903170}%
437 \test{46}{1836311903}%
438 \test{47}{2971215073}%
439 \test{48}{4807526976}%
440 \test{49}{7778742049}%
441 \test{50}{12586269025}%
442 \test{51}{20365011074}%
443 \test{52}{32951280099}%
444 \test{53}{53316291173}%
445 \test{54}{86267571272}%
446 \test{55}{139583862445}%
447 \test{56}{225851433717}%
448 \test{57}{365435296162}%
449 \test{58}{591286729879}%
450 \test{59}{956722026041}%
451 \test{60}{1548008755920}%
452 \test{61}{2504730781961}%
453 \test{62}{4052739537881}%
454 \test{63}{6557470319842}%
455 \test{64}{10610209857723}%
456 \test{65}{17167680177565}%
457 \test{66}{27777890035288}%
458 \test{67}{44945570212853}%
459 \test{68}{72723460248141}%
460 \test{69}{117669030460994}%
461 \test{70}{190392490709135}%
462 \test{71}{308061521170129}%
463 \test{72}{498454011879264}%
464 \test{73}{806515533049393}%
465 }
466 \def\msg#{\immediate\write16}
467 \def\test#1#2{%
468   \TestAux{#1}{#2}%
469   \ifnum#1=0 %
470   \else
471     \ifodd#1 %
472       \TestAux{-#1}{#2}%
473     \else
474       \TestAux{-#1}{-#2}%
475     \fi
476   \fi
477 }
478 \def\TestAux#1#2{%
479   \def\Expected{#2}%
480   \expandafter\expandafter\expandafter\def
481   \expandafter\expandafter\expandafter\Result

```

```

482 \expandafter\expandafter\expandafter{%
483   \fibnum{#1}%
484 }%
485 \ltx@onelevel@sanitize\Result
486 \ifx\Result\Expected
487   \msg{* #1: ok.}%
488 \else
489   \msg{! fib(#1) = #2}%
490   \errmessage{fib(#1) <> \Result}%
491 \fi
492 }
493 \TestSet
494 \setbox0=\hbox{%
495   \msg{* PreCalc{73}}%
496   \fibnumPreCalc{73}%
497 }
498 \ifdim\wd0=0pt
499 \else
500   \errmessage{Unwanted stuff in PreCalc}%
501 \fi
502 \TestSet
503 \csname @@end\endcsname\end
504 \</test-calc>

```

## 4 Installation

### 4.1 Download

**Package.** This package is available on CTAN<sup>1</sup>:

[CTAN:macros/latex/contrib/oberdiek/fibnum.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/fibnum.pdf](#) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

*TDS* refers to the standard “A Directory Structure for  $\TeX$  Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

### 4.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```

chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/

```

---

<sup>1</sup>[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

### 4.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain  $\text{\TeX}$ :

```
tex fibnum.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
fibnum.sty          → tex/generic/oberdiek/fibnum.sty
fibnum.pdf          → doc/latex/oberdiek/fibnum.pdf
test/fibnum-test1.tex → doc/latex/oberdiek/test/fibnum-test1.tex
test/fibnum-test-calc.tex → doc/latex/oberdiek/test/fibnum-test-calc.tex
fibnum.dtx          → source/latex/oberdiek/fibnum.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

### 4.4 Refresh file name databases

If your  $\text{\TeX}$  distribution (`te $\text{\TeX}$` , `mik $\text{\TeX}$` , ...) relies on file name databases, you must refresh these. For example, `te $\text{\TeX}$`  users run `texhash` or `mktextlsr`.

### 4.5 Some details for the interested

**Attached source.** The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk fibnum.pdf unpack_files output .
```

**Unpacking with  $\text{\LaTeX}$ .** The `.dtx` chooses its action depending on the format:

**plain  $\text{\TeX}$ :** Run `docstrip` and extract the files.

**$\text{\LaTeX}$ :** Generate the documentation.

If you insist on using  $\text{\LaTeX}$  for `docstrip` (really, `docstrip` does not need  $\text{\LaTeX}$ ), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{fibnum.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdf $\text{\LaTeX}$` :

```
pdflatex fibnum.dtx
bibtex fibnum.aux
makeindex -s gind.ist fibnum.idx
pdflatex fibnum.dtx
makeindex -s gind.ist fibnum.idx
pdflatex fibnum.dtx
```

## 5 History

[2012/04/08 v1.0]

- First version.

## 6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols			
\#	283, 382	\errmessage	338, 490, 500
\%	359	\Expected	479, 486
\@	284, 357, 383	F	
\@firstofone	292, 295	\fibnum	2, 227, 483
\@gobble	289, 297	\FibNum@AtEnd	95, 96, 117, 278
\@undefined	58	\FibNum@Do	229, 231
\\	358	\FibNum@ExpCalc	247, 263
\{	281, 380	\FibNum@i	197, 198, 200,
\}	282, 381		202, 205, 207, 219, 220, 221, 223
A		\FibNum@max	185,
\advance	202, 207, 223, 322, 330, 345		194, 198, 221, 244, 247, 249, 252
\aftergroup	29	\FibNum@PreCalc	188, 190
B		\FibNum@PreCalcAux	209, 215
\BigIntCalcAdd	217, 268, 274	\FibNum@ReturnAfterElseFiFi	233, 262
\body	301, 305	\FibNum@temp	
C			134, 138, 139, 140, 141, 142,
\catcode	2, 3, 5, 6, 7, 8,		143, 144, 145, 146, 147, 148,
	9, 10, 11, 12, 13, 33, 34, 36, 37,		149, 150, 151, 152, 153, 154,
	38, 39, 40, 41, 42, 43, 44, 45, 46,		155, 156, 157, 158, 159, 160,
	47, 48, 49, 69, 70, 72, 73, 74, 78,		161, 162, 163, 164, 165, 166,
	79, 80, 81, 82, 83, 84, 87, 88, 90,		167, 168, 169, 170, 171, 172,
	91, 92, 93, 97, 99, 137, 281, 282,		173, 174, 175, 176, 177, 178,
	283, 284, 319, 328, 336, 340,		179, 180, 181, 182, 183, 184,
	357, 358, 359, 380, 381, 382, 383		199, 203, 204, 209, 217, 219, 224
\count@	286, 315,	\fibnumPreCalc	3, 186, 496
	319, 321, 322, 326, 328, 329,	H	
	330, 334, 336, 339, 340, 344, 345	\hbox	494
\countdef	197, 286	I	
\csname	14, 21,	\ifdim	498
	50, 66, 76, 119, 122, 135, 200,	\ifnum	191, 194, 220, 232,
	205, 219, 249, 252, 258, 285,		244, 265, 321, 329, 336, 344, 469
	288, 291, 294, 349, 376, 385, 503	\ifodd	234, 471
E		\iftrue	208
\empty	17, 18	\ifx	15, 18, 21, 50, 58, 61, 119, 122,
\end	377, 503		285, 288, 291, 294, 349, 385, 486
\endcsname	14, 21,	\immediate	23, 52, 466
	50, 66, 76, 119, 122, 135, 200,	\input	123, 350, 386
	205, 219, 250, 253, 258, 285,	\IntCalcDec	252
	288, 291, 294, 349, 376, 385, 503	\IntCalcInc	247, 272
\endinput	29, 117	\intcalcNum	188, 229
\endlinechar	4, 35, 71, 77, 89	\iterate	302, 304, 306

L		S	
\LoadCommand	350, 360	\setbox	494
\loop	300, 316, 327, 335	\space	339, 340, 348
\ltx@gobble	192, 241	T	
\ltx@LocDimenA	196, 220	\Test	352, 375
\ltx@one	223	\test	391, 392,
\ltx@onelevel@sanitize	485		393, 394, 395, 396, 397, 398,
\ltx@ReturnAfterElseFi	245, 266		399, 400, 401, 402, 403, 404,
\ltx@two	207		405, 406, 407, 408, 409, 410,
\ltx@zero	191, 232, 235, 237, 257, 267		411, 412, 413, 414, 415, 416,
M			417, 418, 419, 420, 421, 422,
\msg	466, 487, 489, 495		423, 424, 425, 426, 427, 428,
N			429, 430, 431, 432, 433, 434,
\next	306, 308, 310		435, 436, 437, 438, 439, 440,
\number	247, 272, 341		441, 442, 443, 444, 445, 446,
P			447, 448, 449, 450, 451, 452,
\PackageInfo	26		453, 454, 455, 456, 457, 458,
\ProvidesPackage	19, 67		459, 460, 461, 462, 463, 464, 467
R		\TestAux	468, 472, 474, 478
\RangeCatcodeCheck	333, 361, 362, 363, 364, 365,	\TestSet	390, 493, 502
	366, 367, 368, 369, 370, 371, 372	\the	77, 78, 79, 80, 81, 82, 83, 84,
\RangeCatcodeInvalid	325, 353, 354, 355, 356		97, 200, 205, 219, 221, 319, 339, 340
\repeat	300, 312, 323, 331, 346	\TMP@EnsureCode	94, 101, 102, 103,
\RequirePackage	130, 131, 132, 388		104, 105, 106, 107, 108, 109,
\RestoreCatcodes	314, 317, 318, 373		110, 111, 112, 113, 114, 115, 116
\Result	481, 485, 486, 490	\TMP@RequirePackage	120, 126, 127, 128
\romannumeral	228, 240	W	
		\wd	498
		\write	23, 52, 466
		X	
		\x	14, 15, 18, 22, 26, 28, 51, 56, 66, 75, 87