

The `getttitlestring` package

Heiko Oberdiek

<oberdiek@uni-freiburg.de>

2009/12/08 v1.0

Abstract

The L^AT_EX package addresses packages that are dealing with references to titles (`\section`, `\caption`, ...). The package tries to remove `\label` and other commands from title strings.

Contents

| | |
|---|-----------|
| 1 Documentation | 1 |
| 1.1 Macros | 1 |
| 1.2 Options | 2 |
| 2 Implementation | 2 |
| 2.1 Options | 4 |
| 2.2 <code>\GetTitleString</code> | 4 |
| 2.2.1 Expand method | 5 |
| 2.2.2 Non-expand method | 5 |
| 3 Test | 7 |
| 3.1 Catcode checks for loading | 7 |
| 3.2 Test of non-expand method | 8 |
| 4 Installation | 9 |
| 4.1 Download | 9 |
| 4.2 Bundle installation | 9 |
| 4.3 Package installation | 9 |
| 4.4 Refresh file name databases | 10 |
| 4.5 Some details for the interested | 10 |
| 5 References | 10 |
| 6 History | 10 |
| [2009/12/08 v1.0] | 10 |
| 7 Index | 11 |

1 Documentation

1.1 Macros

```
\GetTitleStringSetup {\{key value list\}}
```

The options are given as comma separated key value pairs. See section 1.2.

```
\GetTitleString {\text}
\GetTitleStringExpand {\text}
\GetTitleStringNonExpand {\text}
```

Macro `\GetTitleString` tries to remove unwanted stuff from `\text` the result is stored in Macro `\GetTitleStringResult`. Two methods are available:

`\GetTitleStringExpand`: The `\text` is expanded in a context where the unwanted macros are redefined to remove themselves. This is the method used in packages `titleref` [2], `zref-titleref` [3] or class `memoir` [1]. `\protect` is supported, but fragile material might break.

`\GetTitleStringNonExpand`: The `\text` is not expanded. Thus the removal of unwanted material is more difficult. It is especially removed at the start of the `\text` and spaces are removed from the end. Currently only `\label` is removed in the whole string, if it is not hidden inside curly braces or part of macro definitions. Thus the removal of unwanted stuff might not be complete, but fragile material will not break. (But the result string can break at a later time, of course).

Option `expand` controls which method is used by macro `\GetTitleString`.

```
\GetTitleStringDisableCommands {\code}
```

The `\code` is called right before the text is expanded in `\GetTitleStringExpand`. Additional definitions can be given for macros that should be removed. Keep in mind that expansion means that the definitions must work in expandable context. Macros like `\@ifstar` or `\@ifnextchar` or optional arguments will not work. The macro names in `\code` may contain the at sign `@`, it has catcode 11 (letter).

1.2 Options

expand: Boolean option, takes values `true` or `false`. No value means `true`. The option specifies the method to remove unwanted stuff from the title string, see below.

Options can be set at the following places:

- `\usepackage`
- Configuration file `getttitlestring.cfg`.
- `\GetTitleStringSetup`

2 Implementation

1 `(*package)`

Reload check, especially if the package is not used with L^AT_EX.

```
2 \begingroup
3   \catcode44 12 % ,
4   \catcode45 12 % -
5   \catcode46 12 % .
6   \catcode58 12 % :
7   \catcode64 11 % @
8   \catcode123 1 % {
9   \catcode125 2 % }
10  \expandafter\let\expandafter\x\csname ver@getttitlestring.sty\endcsname
11  \ifx\x\relax % plain-TeX, first loading
12  \else
13    \def\empty{}%
```

```

14  \ifx\x\empty % LaTeX, first loading,
15    % variable is initialized, but \ProvidesPackage not yet seen
16  \else
17    \catcode35 6 % #
18    \expandafter\ifx\csname PackageInfo\endcsname\relax
19      \def\x#1#2{%
20        \immediate\write-1{Package #1 Info: #2.}%
21      }%
22  \else
23    \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
24  \fi
25  \x{getttitlestring}{The package is already loaded}%
26  \aftergroup\endinput
27 \fi
28 \fi
29 \endgroup

Package identification:
30 \begingroup
31  \catcode35 6 % #
32  \catcode40 12 % (
33  \catcode41 12 % )
34  \catcode44 12 % ,
35  \catcode45 12 % -
36  \catcode46 12 % .
37  \catcode47 12 % /
38  \catcode58 12 % :
39  \catcode64 11 % @
40  \catcode91 12 % [
41  \catcode93 12 % ]
42  \catcode123 1 % {
43  \catcode125 2 % }
44  \expandafter\ifx\csname ProvidesPackage\endcsname\relax
45    \def\x#1#2#3[#4]{\endgroup
46      \immediate\write-1{Package: #3 #4}%
47      \xdef#1[#4]%
48    }%
49  \else
50    \def\x#1#2[#3]{\endgroup
51      #2[#3]%
52      \ifx#1\undefined
53        \xdef#1[#3]%
54      \fi
55      \ifx#1\relax
56        \xdef#1[#3]%
57      \fi
58    }%
59  \fi
60 \expandafter\x\csname ver@getttitlestring.sty\endcsname
61 \ProvidesPackage{getttitlestring}%
62 [2009/12/08 v1.0 Cleanup strings for title referencing (HO)]

63 \begingroup
64  \catcode123 1 % {
65  \catcode125 2 % }
66  \def\x{\endgroup
67    \expandafter\edef\csname GTS@AtEnd\endcsname{%
68      \catcode35 \the\catcode35\relax
69      \catcode64 \the\catcode64\relax
70      \catcode123 \the\catcode123\relax
71      \catcode125 \the\catcode125\relax
72    }%
73  }%
74 \x

```

```

75 \catcode35 6 % #
76 \catcode64 11 % @
77 \catcode123 1 % {
78 \catcode125 2 % }
79 \def\TMP@EnsureCode#1#2{%
80   \edef\GTS@AtEnd{%
81     \GTS@AtEnd
82     \catcode#1 \the\catcode#1\relax
83   }%
84   \catcode#1 #2\relax
85 }
86 \TMP@EnsureCode{42}{12} * *
87 \TMP@EnsureCode{44}{12} , ,
88 \TMP@EnsureCode{45}{12} -
89 \TMP@EnsureCode{46}{12} .
90 \TMP@EnsureCode{47}{12} /
91 \TMP@EnsureCode{61}{12} =
92 \TMP@EnsureCode{91}{12} [
93 \TMP@EnsureCode{93}{12} ]

```

2.1 Options

```

94 \RequirePackage{kvoptions}[2009/07/17]
95 \SetupKeyvalOptions{%
96   family=gettitlestring,%
97   prefix=GTS@%
98 }
99 \newcommand*{\GetTitleStringSetup}{%
100   \setkeys{gettitlestring}{%
101 }
102 \DeclareBoolOption{expand}
103 \InputIfFileExists{gettitlestring.cfg}{}
104 \ProcessKeyvalOptions*\relax

```

2.2 \GetTitleString

\GetTitleString

```

105 \newcommand*{\GetTitleString}{%
106   \ifGTS@expand
107     \expandafter\GetTitleStringExpand
108   \else
109     \expandafter\GetTitleStringNonExpand
110   \fi
111 }

```

\GetTitleStringExpand

```

112 \newcommand{\GetTitleStringExpand}[1]{%
113   \def\GetTitleStringResult{\#1}%
114   \begingroup
115     \GTS@DisablePredefinedCmds
116     \GTS@DisableHook
117     \edef\x{\endgroup
118       \noexpand\def\noexpand\GetTitleStringResult{%
119         \GetTitleStringResult
120       }%
121     }%
122   \x
123 }

```

\GetTitleString

```

124 \newcommand{\GetTitleStringNonExpand}[1]{%
125   \def\GetTitleStringResult{\#1}%
126   \global\let\GTS@GlobalString\GetTitleStringResult

```

```

127  \begingroup
128    \GTS@RemoveLeft
129    \GTS@RemoveRight
130  \endgroup
131  \let\GetTitleStringResult\GTS@GlobalString
132 }

```

2.2.1 Expand method

\GTS@DisablePredefinedCmds

```

133 \def\GTS@DisablePredefinedCmds{%
134   \let\label@gobble
135   \let\zlabel@gobble
136   \let\zref@label@gobble
137   \let\zref@labelbylist@gobbletwo
138   \let\zref@labelbyprops@gobbletwo
139   \let\index@gobble
140   \let\glossary@gobble
141   \let\markboth@gobbletwo
142   \let\mkboth@gobbletwo
143   \let\markright@gobble
144   \let\phantomsection@\empty
145   \def\addcontentsline{\expandafter\@gobble\@gobbletwo}%
146   \let\raggedright@\empty
147   \let\raggedleft@\empty
148   \let\centering@\empty
149   \let\protect\@unexpandable@protect
150 }

```

\GTS@DisableHook

```
151 \providecommand*\GTS@DisableHook{}%
```

GetTitleStringDisableCommands

```

152 \def\GetTitleStringDisableCommands{%
153   \begingroup
154     \makeatletter
155     \GTS@DisableCommands
156 }

\GTS@DisableCommands
157 \long\def\GTS@DisableCommands#1{%
158   \toks0=\expandafter{\GTS@DisableHook}%
159   \toks2={#1}%
160   \xdef\GTS@GlobalString{\the\toks0 \the\toks2}%
161 \endgroup
162 \let\GTS@DisableHook\GTS@GlobalString
163 }

```

2.2.2 Non-expand method

```

164 \def\GTS@RemoveLeft{%
165   \toks@\expandafter\expandafter\expandafter{%
166     \expandafter\GTS@Car\GTS@GlobalString{}{}{}{}{}\GTS@Nil
167   }%
168   \edef\GTS@Token{\the\toks@}%
169   \GTS@PredefinedLeftCmds
170   \expandafter\futurelet\expandafter\GTS@Token
171   \expandafter\GTS@TestLeftSpace\GTS@GlobalString\GTS@Nil
172   \GTS@End
173 }
174 \def\GTS@End{}%
175 \long\def\GTS@TestLeft#1#2{%

```

```

176  \def\GTS@temp{#1}%
177  \ifx\GTS@temp\GTS@Token
178    \toks@\expandafter\expandafter\expandafter{%
179      \expandafter#2\GTS@GlobalString\GTS@Nil
180    }%
181    \expandafter\GTS@TestLeftEnd
182  \fi
183 }
184 \long\def\GTS@TestLeftEnd#1\GTS@End{%
185   \xdef\GTS@GlobalString{\the\toks@}%
186   \GTS@RemoveLeft
187 }
188 \long\def\GTS@Car#1#2\GTS@Nil{#1}
189 \long\def\GTS@Cdr#1#2\GTS@Nil{#2}
190 \long\def\GTS@CdrTwo#1#2#3\GTS@Nil{#3}
191 \long\def\GTS@CdrThree#1#2#3#4\GTS@Nil{#4}
192 \long\def\GTS@CdrFour#1#2#3#4#5\GTS@Nil{#5}
193 \long\def\GTS@TestLeftSpace#1\GTS@Nil{%
194   \ifx\GTS@Token@sptoken
195     \toks@\expandafter{%
196       \romannumerical-0\GTS@GlobalString
197     }%
198     \expandafter\GTS@TestLeftEnd
199   \fi
200 }

\GTS@PredefinedLeftCmds

201 \def\GTS@PredefinedLeftCmds{%
202   \GTS@TestLeft\Hy@sectionAnchor\GTS@Cdr
203   \GTS@TestLeft\Hy@phantomsection\GTS@Cdr
204   \GTS@TestLeft\label\GTS@CdrTwo
205   \GTS@TestLeft\zlabel\GTS@CdrTwo
206   \GTS@TestLeft\index\GTS@CdrTwo
207   \GTS@TestLeft\glossary\GTS@CdrTwo
208   \GTS@TestLeft\markboth\GTS@CdrThree
209   \GTS@TestLeft\@mkboth\GTS@CdrThree
210   \GTS@TestLeft\addcontentsline\GTS@CdrFour
211 }

212 \def\GTS@RemoveRight{%
213   \toks@{}%
214   \expandafter\GTS@TestRightLabel\GTS@GlobalString
215     \label{}\GTS@Nil\@nil
216   \GTS@RemoveRightSpace
217 }

218 \begingroup
219   \def\GTS@temp#1{\endgroup
220     \def\GTS@RemoveRightSpace{%
221       \expandafter\GTS@TestRightSpace\GTS@GlobalString
222         \GTS@Nil#1\GTS@Nil\@nil
223     }%
224   }%
225 \GTS@temp{ }
226 \def\GTS@TestRightSpace#1 \GTS@Nil#2\@nil{%
227   \ifx\relax#2\relax
228   \else
229     \gdef\GTS@GlobalString{#1}%
230     \expandafter\GTS@RemoveRightSpace
231   \fi
232 }
233 \def\GTS@TestRightLabel#1\label#2#3\GTS@Nil#4\@nil{%
234   \def\GTS@temp{#3}%
235   \ifx\GTS@temp\@empty

```

```

236      \expandafter\gdef\expandafter\GTS@GlobalString\expandafter{%
237          \the\toks@
238          #1%
239      }%
240      \expandafter\@gobble
241  \else
242      \expandafter\@firstofone
243  \fi
244 {%
245     \toks@\expandafter{\the\toks@#1}%
246     \GTS@TestRightLabel#3\GTS@Nil\@nil
247 }%
248 }

249 \GTS@AtEnd
250 </package>

```

3 Test

3.1 Catcode checks for loading

```

251 <*test1>
252 \catcode`\#=1 %
253 \catcode`\#=2 %
254 \catcode`\#=6 %
255 \catcode`\@=11 %
256 \expandafter\ifx\csname count@\endcsname\relax
257   \countdef\count@=255 %
258 \fi
259 \expandafter\ifx\csname @gobble\endcsname\relax
260   \long\def\@gobble#1{}%
261 \fi
262 \expandafter\ifx\csname @firstofone\endcsname\relax
263   \long\def\@firstofone#1{#1}%
264 \fi
265 \expandafter\ifx\csname loop\endcsname\relax
266   \expandafter\@firstofone
267 \else
268   \expandafter\@gobble
269 \fi
270 {%
271   \def\loop#1\repeat{%
272     \def\body{#1}%
273     \iterate
274   }%
275   \def\iterate{%
276     \body
277     \let\next\iterate
278   \else
279     \let\next\relax
280   \fi
281   \next
282 }%
283   \let\repeat=\fi
284 }%
285 \def\RestoreCatcodes{}
286 \count@=0 %
287 \loop
288   \edef\RestoreCatcodes{%
289     \RestoreCatcodes
290     \catcode\the\count@=\the\catcode\count@\relax
291   }%

```

```

292 \ifnum\count@<255 %
293   \advance\count@ 1 %
294 \repeat
295
296 \def\RangeCatcodeInvalid#1#2{%
297   \count@=#1\relax
298   \loop
299     \catcode\count@=15 %
300   \ifnum\count@<#2\relax
301     \advance\count@ 1 %
302   \repeat
303 }
304 \expandafter\ifx\csname LoadCommand\endcsname\relax
305   \def\LoadCommand{\input gettitlestring.sty\relax}%
306 \fi
307 \def\Test{%
308   \RangeCatcodeInvalid{0}{47}%
309   \RangeCatcodeInvalid{58}{64}%
310   \RangeCatcodeInvalid{91}{96}%
311   \RangeCatcodeInvalid{123}{255}%
312   \catcode`\@=12 %
313   \catcode`\\=0 %
314   \catcode`{=1 %
315   \catcode`}=2 %
316   \catcode`\#=6 %
317   \catcode`\[=12 %
318   \catcode`\]=12 %
319   \catcode`\%=14 %
320   \catcode`\ =10 %
321   \catcode13=5 %
322   \LoadCommand
323   \RestoreCatcodes
324 }
325 \Test
326 \csname @@end\endcsname
327 \end
328 </test1>

```

3.2 Test of non-expand method

```

329 <*test2>
330 \NeedsTeXFormat{LaTeX2e}
331 \documentclass{minimal}
332 \usepackage{gettitlestring}[2009/12/08]
333 \usepackage{qstest}
334 \IncludeTests{*}
335 \LogTests{log}{*}{*}
336 \begin{document}
337 \begin{qstest}{non-expand}{non-expand}
338   \def\test#1#2{%
339     \sbox0{%
340       \GetTitleString{#1}%
341       \Expect{#2}*\{\GetTitleStringResult\}%
342     }%
343     \Expect{0.0pt}*\{\the\wd0\}%
344   }%
345   \test{}{}%
346   \test{}{}%
347   \test{x}{x}%
348   \test{x y}{x y}%
349   \test{\relax}{\relax}%
350   \test{\label{f}a}{a}%
351   \test{\label{f}a}{a}%

```

```

352  \test{\label{f} a}{a}%
353  \test{ \label{f} a}{a}%
354  \test{a\label{f}}{a}%
355  \test{a\label{f} }{a}%
356  \test{a \label{f}}{a}%
357  \test{a \label{f} }{a}%
358  \test{a\label{f}b\label{g}}{ab}%
359  \test{a \label{f}b \label{g} }{a b}%
360  \test{a\label{f} b \label{g} }{a b}%
361 \end{qstest}
362 \end{document}
363 
```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

CTAN:macros/latex/contrib/oberdiek/gettitlestring.dtx The source file.

CTAN:macros/latex/contrib/oberdiek/gettitlestring.pdf Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

CTAN:install/macros/latex/contrib/oberdiek.tds.zip

TDS refers to the standard “A Directory Structure for T_EX Files” (CTAN:tds/tds.pdf). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory TDS:`scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain-T_EX:

```
tex gettitlestring.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

| | |
|--|---|
| <code>gettitlestring.sty</code> | → <code>tex/generic/oberdiek/gettitlestring.sty</code> |
| <code>gettitlestring.pdf</code> | → <code>doc/latex/oberdiek/gettitlestring.pdf</code> |
| <code>test/gettitlestring-test1.tex</code> | → <code>doc/latex/oberdiek/test/gettitlestring-test1.tex</code> |
| <code>test/gettitlestring-test2.tex</code> | → <code>doc/latex/oberdiek/test/gettitlestring-test2.tex</code> |
| <code>gettitlestring.dtx</code> | → <code>source/latex/oberdiek/gettitlestring.dtx</code> |

¹[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your Te_EX distribution (te_ET_EX, mik_ET_EX, ...) relies on file name databases, you must refresh these. For example, te_ET_EX users run `texhash` or `mktexlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk gettitlestring.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain-T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{gettitlestring.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex gettitlestring.dtx
makeindex -s gind.ist gettitlestring.idx
pdflatex gettitlestring.dtx
makeindex -s gind.ist gettitlestring.idx
pdflatex gettitlestring.dtx
```

5 References

- [1] Peter Wilson, Lars Madsen: *The Memoir Class*; 2009/11/17 v1.61803398c; [CTAN:macros/latex/contrib/memoir/](#)
- [2] Donald Arsenau: *Titleref.sty*; 2001/04/05 ver 3.1; [CTAN:macros/latex/contrib/misc/titleref.sty](#)
- [3] Heiko Oberdiek: *The zref package*; 2009/12/08 v2.7; [CTAN:macros/latex/contrib/oberdiek/zref.pdf](#)

6 History

[2009/12/08 v1.0]

- The first version.

7 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

| Symbols | F |
|---|--|
| \# | 254, 316 |
| \% | 319 |
| \@ | 255, 312 |
| \@empty | 144, 146, 147, 148, 235 |
| \@firstofone | 242, 263, 266 |
| \@gobble | 134, 135, 136, 139, 140, 143, 145, 240, 260, 268 |
| \@gobbletwo | 137, 138, 141, 142, 145 |
| \@mkboth | 142, 209 |
| \@nil | 215, 222, 226, 233, 246 |
| \@sptoken | 194 |
| \@undefined | 52 |
| \@unexpandable@protect | 149 |
| \[..... | 317 |
| \\\ | 313 |
| \{ | 252, 314 |
| \} | 253, 315 |
| \] | 318 |
| _ | 320 |
| A | |
| \addcontentsline | 145, 210 |
| \advance | 293, 301 |
| \aftergroup | 26 |
| B | |
| \begin | 336, 337 |
| \body | 272, 276 |
| C | |
| \catcode <i>3, 4, 5, 6, 7, 8, 9, 17, 31, 32,</i> <i>33, 34, 35, 36, 37, 38, 39, 40, 41,</i> <i>42, 43, 64, 65, 68, 69, 70, 71, 75,</i> <i>76, 77, 78, 82, 84, 252, 253, 254,</i> <i>255, 290, 299, 312, 313, 314,</i> <i>315, 316, 317, 318, 319, 320, 321</i> | |
| \centering | 148 |
| \count@ | 257, 286, 290, 292, 293, 297, 299, 300, 301 |
| \countdef | 257 |
| \csname | 10, 18, 44, 60, 67, 256, 259, 262, 265, 304, 326 |
| D | |
| \DeclareBoolOption | 102 |
| \documentclass | 331 |
| E | |
| \empty | 13, 14 |
| \end | 327, 361, 362 |
| \endcsname | 10, 18, 44, 60, 67, 256, 259, 262, 265, 304, 326 |
| \endinput | 26 |
| \Expect | 341, 343 |
| F | |
| \futurelet | 170 |
| G | |
| \gdef | 229, 236 |
| \GetTitleString | 2, 105, 124, 340 |
| \GetTitleStringDisableCommands | 2, 152 |
| \GetTitleStringExpand | 107, 112 |
| \GetTitleStringNonExpand | 109, 124 |
| \GetTitleStringResult | 113, 118, 119, 125, 126, 131, 341 |
| \GetTitleStringSetup | 1, 99 |
| \glossary | 140, 207 |
| \GTS@AtEnd | 80, 81, 249 |
| \GTS@Car | 166, 188 |
| \GTS@Cdr | 189, 202, 203 |
| \GTS@CdrFour | 192, 210 |
| \GTS@CdrThree | 191, 208, 209 |
| \GTS@CdrTwo | 190, 204, 205, 206, 207 |
| \GTS@DisableCommands | 155, 157 |
| \GTS@DisableHook | 116, 151, 158, 162 |
| \GTS@DisablePredefinedCmds | 115, 133 |
| \GTS@End | 172, 174, 184 |
| \GTS@GlobalString | 126, 131, 160, 162, 166, 171, 179, 185, 196, 214, 221, 229, 236 |
| \GTS@Nil | 166, 171, 179, 188, 189, 190, 191, 192, 193, 215, 222, 226, 233, 246 |
| \GTS@PredefinedLeftCmds | 169, 201 |
| \GTS@RemoveLeft | 128, 164, 186 |
| \GTS@RemoveRight | 129, 212 |
| \GTS@RemoveRightSpace | 216, 220, 230 |
| \GTS@temp | 176, 177, 219, 225, 234, 235 |
| \GTS@TestLeft | 175, 202, 203, 204, 205, 206, 207, 208, 209, 210 |
| \GTS@TestLeftEnd | 181, 184, 198 |
| \GTS@TestLeftSpace | 171, 193 |
| \GTS@TestRightLabel | 214, 233, 246 |
| \GTS@TestRightSpace | 221, 226 |
| \GTS@Token | 168, 170, 177, 194 |
| H | |
| \Hy@phantomsection | 203 |
| \Hy@sectionAnchor | 202 |
| I | |
| \ifGTS@expand | 106 |
| \ifnum | 292, 300 |
| \ifx | 11, 14, 18, 44, 52, 55, 177, 194, 227, 235, 256, 259, 262, 265, 304 |
| \immediate | 20, 46 |
| \IncludeTests | 334 |
| \index | 139, 206 |
| \input | 305 |
| \InputIfFileExists | 103 |
| \iterate | 273, 275, 277 |

| L | S |
|--|---|
| \label 134, 204, 215, 233, 350, 351, 352, 353, 354, 355, 356, 357, 358, 359, 360 | \sbox 339 |
| \LoadCommand 305, 322 | \setkeys 100 |
| \LogTests 335 | \SetupKeyvalOptions 95 |
| \loop 271, 287, 298 | |
| | T |
| | \Test 307, 325 |
| M | \test 338, 345, 346, 347, 348, 349, 350, 351, 352, 353, 354, 355, 356, 357, 358, 359, 360 |
| \makeatletter 154 | \the 68, 69, 70, 71, 82, 160, 168, 185, 237, 245, 290, 343 |
| \markboth 141, 208 | |
| \markright 143 | \TMP@EnsureCode 79, 86, 87, 88, 89, 90, 91, 92, 93 |
| | \toks 158, 159, 160 |
| N | \toks@ 165, 168, 178, 185, 195, 213, 237, 245 |
| \NeedsTeXFormat 330 | |
| \newcommand 99, 105, 112, 124 | |
| \next 277, 279, 281 | |
| | U |
| P | \usepackage 332, 333 |
| \PackageInfo 23 | |
| \phantomsection 144 | |
| \ProcessKeyvalOptions 104 | |
| \protect 149 | |
| \providecommand 151 | |
| \ProvidesPackage 15, 61 | |
| | W |
| R | \wd 343 |
| \raggedleft 147 | \write 20, 46 |
| \raggedright 146 | |
| \RangeCatcodeInvalid 296, 308, 309, 310, 311 | |
| \repeat 271, 283, 294, 302 | |
| \RequirePackage 94 | |
| \RestoreCatcodes .. 285, 288, 289, 323 | |
| \romannumeral 196 | |
| | X |
| | \x 10, 11, 14, 19, 23, 25, 45, 50, 60, 66, 74, 117, 122 |
| | |
| | Z |
| | \zlabel 135, 205 |
| | \zref@label 136 |
| | \zref@labelbylist 137 |
| | \zref@labelbyprops 138 |