

The grffile package

Heiko Oberdiek
<oberdiek@uni-freiburg.de>

2008/10/13 v1.9

Abstract

The package extends the file name processing of package `graphics` to support a larger range of file names. For example, the file name may contain several dots. Or in case of pdfTeX in PDF mode the file name may contain spaces.

Contents

1	Usage	2
1.1	Option <code>multidot</code>	2
1.2	Option <code>babel</code>	2
1.3	Option <code>extendedchars</code>	2
1.4	Option <code>encoding</code>	2
1.4.1	Option <code>inputencoding</code>	3
1.4.2	Option <code>filenameencoding</code>	3
1.4.3	Example	3
1.5	Option <code>space</code>	3
1.6	General use	4
1.7	Default settings	4
2	Implementation	4
2.1	Identification	4
2.2	Catcode stuff	4
2.3	Options	5
3	Test	8
3.1	Multidot with default rule	8
4	Installation	9
4.1	Download	9
4.2	Bundle installation	9
4.3	Package installation	10
4.4	Refresh file name databases	10
4.5	Some details for the interested	10
5	References	11
6	History	11
	[2004/07/18 v0.5]	11
	[2006/08/15 v1.0]	11
	[2006/08/17 v1.1]	11
	[2006/11/30 v1.2]	11
	[2007/04/11 v1.3]	11
	[2007/06/13 v1.4]	11
	[2007/08/16 v1.5]	11

[2007/11/11 v1.6]	11
[2007/11/24 v1.7]	11
[2008/08/11 v1.8]	12
[2008/10/13 v1.9]	12

7 Index	12
----------------	-----------

1 Usage

1.1 Option `multidot`

The file name parsing of package `graphics` is changed, in order to detect known extensions. This allows both the use of dots inside the base file name and extensions with several dots.

Assume there are two files in the current directory: `Hello.World.eps` and `Hello.World.pdf`. `\includegraphics{Hello.World}` will find `Hello.World.pdf` with driver `pdftex` or `Hello.World.eps` with driver `dvips`.

Limitations: Problem could occur on systems, which don't use the dot as extension delimiter. These systems needs an own `texsys.cfg` containing definitions for `\filename@parse`. The author could not test that, due to a missing example.

1.2 Option `babel`

This option allows the use of shorthand characters of package `babel` inside the `graphics` file name. Additionally the tilde '~' is supported. The option is turned on as default. (In version v1.1 or below of this package, the features of this option were part of option `extendedchars`.)

Example:

```
\usepackage[frenchb]{babel}
\usepackage{grffile}
Image: \includegraphics{C:/path/image}
```

1.3 Option `extendedchars`

If the input encoding is the same encoding as the encoding that is used for file names and the driver allows non-ascii characters. Without option `extendedchars` the 8-bit characters are expanded, if they are active characters. For example, see the \LaTeX package `inputenc`. However a file name is not input for \LaTeX . Therefore this option `extendedchars` removes the active status and the 8-bit characters are not expandable any more.

Example:

```
\usepackage[latin1]{inputenc}
\usepackage[extendedchars]{grffile}
\includegraphics{Bäckerstraße}
```

If the `draft` option of the `graphics` package is enabled, the file name is printed with the current font encoding for `\ttfamily`. Thus it is possible, that such characters are omitted or the wrong characters are displayed, if the font encoding is not the same as the file name encoding.

1.4 Option `encoding`

Consider the following scenario. Your file system is using UTF-8 as encoding for file names. But you use `latin1` as input encoding for your \TeX files, because some packages are not ready for multi-byte encodings (`listings`, ...).

Then this option `encoding` loads support for converting encodings by loading package `stringenc`. The option is not defined after the preamble, because \LaTeX limits package loading to the preamble.

File names are converted, if package `stringenc` is loaded and the encodings are known, see options `inputencoding` and `filenameencoding`.

1.4.1 Option `inputencoding`

Option `inputencoding` specifies the encoding of the file name in your \TeX input file.

Package `inputenx` and package `inputenc` since version 2006/02/22 v1.1a remember the name of the input encoding that is looked up by this package. Therefore option `inputencoding` is usually not mandatory.

1.4.2 Option `filenameencoding`

This is the encoding of the filename of your file system. This option is mandatory, file names are not converted without this option. The option is disabled, if the value is empty.

1.4.3 Example

Back to the scenario where the file system uses UTF-8 and the \LaTeX input files are encoded in `latin1`.

```
\usepackage[latin1]{inputenc}[2006/02/22]
% \usepackage[latin1]{inputenx}
\usepackage{graphicx}
\usepackage[encoding,filenameencoding=utf8]{grffile}
```

For older versions of package `inputenc` option `inputencoding` provides the necessary informations.

```
\usepackage[latin1]{inputenc}
\usepackage{graphicx}
\usepackage{grffile}
\grffilesetup{
  encoding,
  inputencoding=latin1,
  filenameencoding=utf8,
}
```

1.5 Option `space`

This option allows graphics file names that contain spaces if possible.

In general it is not possible to use space inside file names, because \TeX considers the space character as termination in its syntax for commands that expect a file name.

Regarding graphics inclusion with the package `graphics` file names are used in two or three contexts:

1. The basic `\special` statement or primitive command for graphics inclusion. The `\special` statements for drivers `dvips` or `dvipdfm` do not allow spaces. However $\text{pdf}\text{\TeX}$'s primitive `\pdfximage` uses curly braces to delimit the file name and allows spaces.
2. `\includegraphics` checks the existence of the file. Also it looks for the right extension if the extension is not given. If $\text{pdf}\text{\TeX}$ 1.30 is given, the file existence test can be rewritten using a new primitive that allows spaces. This works in both modes DVI and PDF.

3. Sometimes files are read as T_EX input files. For example, .bb files or MPS files.

If pdfT_EX 1.30 or greater is used in PDF mode then the graphics file names may contain spaces except for MPS files. Therefore option `space` is only enabled by default, if the supported pdfT_EX in PDF mode is detected. You can enable the option manually, if you know, your DVI driver supports spaces in its `\special` syntax and if there is no need to read the image file as T_EX input file (third context).

1.6 General use

The options can be given at many places:

1. As package options:
`\usepackage[<options>]{grffile}`
2. Setup command of package grffile:
`\grffilesetup{<options>}`
3. The options are also available as options for package `graphicx`:
`\setkeys{Gin}{<options>}`
4. If package `graphicx` is loaded the options can also be applied for a single image:
`\includegraphics[<options>]{...}`

1.7 Default settings

<code>multidot</code>	<code>true</code>	
<code>babel</code>	<code>true</code>	
<code>extendedchars</code>	<code>false</code>	
<code>space</code>	<code>true</code>	if pdfT _E X 1.30 or greater is used in PDF mode
	<code>false</code>	otherwise

2 Implementation

2.1 Identification

```

1 <*package>
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{grffile}%
4 [2008/10/13 v1.9 Extended file name support for graphics (HO)]%
```

2.2 Catcode stuff

```

5 \edef\grffile@RestoreCatcodes{%
6   \catcode'\noexpand\=\the\catcode'\=\relax
7   \catcode'\noexpand\:\the\catcode'\:\relax
8   \catcode'\noexpand\.\the\catcode'\.\relax
9   \catcode'\noexpand\' \the\catcode\' \relax
10  \catcode'\noexpand\<\the\catcode'\<\relax
11  \catcode'\noexpand\>\the\catcode'\>\relax
12  \catcode'\noexpand*\the\catcode'*\relax
13  \catcode'\noexpand^\the\catcode'^\relax
14  \catcode'\noexpand~\the\catcode'~\relax
15 }
16 \@makeother\=
17 \@makeother\:
18 \@makeother\.
19 \@makeother\'
20 \@makeother\<
```

```

21 \@makeother\>
22 \@makeother\*
23 \catcode'\^=7 %
24 \catcode'\~=active

```

2.3 Options

```

25 \RequirePackage{ifpdf}
26 \RequirePackage{kvoptions}[2006/08/17]
27 \SetupKeyvalOptions{%
28   family=Gin,%
29   prefix=grffile@%
30 }
31 \DeclareBoolOption[true]{multidot}
32 \DeclareBoolOption[true]{babel}
33 \DeclareBoolOption[false]{extendedchars}
34 \DeclareBoolOption{space}
35 \DeclareVoidOption{encoding}{%
36   \RequirePackage{stringenc}\relax
37 }
38 \DeclareStringOption{inputencoding}
39 \DeclareStringOption{filenameencoding}
40 \DeclareDefaultOption{%
41   \PassOptionsToPackage\CurrentOption{graphics}%
42 }

```

Default setting for option space.

```

43 \RequirePackage{pdftexcmds}[2007/11/11]
44 \begingroup\expandafter\expandafter\expandafter\endgroup
45 \expandafter\ifx\curname pdf@filesize\endcurname\relax
46   \grffile@spacefalse
47   \let\grffile@space@disabled\@empty
48   \def\grffile@spacetrue{%
49     \PackageWarning{grffile}{%
50       Option 'space' is not available,\MessageBreak
51       because it needs pdfTeX >= 1.30%
52     }%
53   }%
54 \else
55   \ifpdf
56     \grffile@spacetrue
57   \else
58     \grffile@spacefalse
59   \fi
60 \fi
61 \ProcessKeyvalOptions*
62 \AtBeginDocument{%
63   \DisableKeyvalOption[package=grffile]{Gin}{encoding}%
64 }
65 \RequirePackage{graphics}

\grffilesetup

66 \newcommand*\grffilesetup{%
67   \setkeys{Gin}%
68 }

69 \let\grffile@org@Gininclude@graphics\Gininclude@graphics
70 \renewcommand*\Gininclude@graphics{%
71   \ifx\grffile@filenameencoding\@empty
72   \else
73     \ifx\grffile@inputencoding\@empty
74       \expandafter\ifx\curname inputencodingname\endcurname\relax
75       \expandafter\ifx\curname
76         CurrentInputEncodingOption\endcurname\relax

```

```

77         \else
78         \let\grffile@inputencoding\CurrentInputEncodingOption
79         \fi
80     \else
81         \let\grffile@inputencoding\inputencodingname
82         \fi
83     \fi
84     \ifx\grffile@inputencoding\@empty
85     \else
86         \grffile@extendedcharstrue
87     \fi
88 \fi
89 \ifnum0\ifgrffile@babel 1\fi\ifgrffile@extendedchars 1\fi>\z@
90     \begingroup

```

Support of babel's shorthand characters.

```

91         \ifgrffile@babel
92         \csname @safe@activestrue\endcsname

```

Support of active tilde.

```

93         \edef~{\string~}%

```

Support of characters controlled by package inputenc.

```

94     \fi
95     \ifgrffile@extendedchars
96         \grffile@inputenc@loop\^^A\^^H%
97         \grffile@inputenc@loop\^^K\^^K%
98         \grffile@inputenc@loop\^^N\^^_%
99         \grffile@inputenc@loop\^^?\^^ff%
100    \fi
101    \expandafter\grffile@extchar@Ginclude@graphics
102 \else
103     \expandafter\grffile@Ginclude@graphics
104 \fi
105 }
106 \def\grffile@extchar@Ginclude@graphics#1{%
107     \def\grffile@filename{#1}%
108     \ifx\grffile@inputencoding\@empty
109     \else
110         \ifx\grffile@filenameencoding\@empty
111         \else
112             \ifx\grffile@inputencoding\grffile@filenameencoding
113             \else
114                 \expandafter\ifx\csname StringEncodingConvert\endcsname\relax
115                 \PackageError{grffile}{%
116                     Package 'stringenc' is not loaded,\MessageBreak
117                     omitting file name conversion%
118                 }\@ehc
119             \else
120                 \StringEncodingConvert\grffile@temp\grffile@filename
121                 \grffile@inputencoding\grffile@filenameencoding
122                 \StringEncodingSuccessFailure{%
123                     \let\grffile@filename\grffile@temp
124                 }{%
125                     \PackageError{grffile}{%
126                         Filename conversion failed%
127                     }\@ehc
128                 }%
129             \fi
130         \fi
131     \fi
132 \fi
133 \edef\x{\endgroup
134     \noexpand\grffile@Ginclude@graphics{\grffile@filename}%

```

```

135 }%
136 \x
137 }
138 \def\grffile@inputenc@loop#1#2{%
139   \count@=#1\relax
140   \loop
141     \begingroup
142       \uccode'\~=\count@
143       \uppercase{%
144         \endgroup
145         \edef~{\string~}%
146       }%
147   \ifnum\count@<#2\relax
148     \advance\count@\@ne
149   \repeat
150 }

Support for option space
151 \def\grffile@space@getbase#1{%
152   \edef\grffile@tempa{%
153     \def\noexpand\@tempa####1#1\noexpand\@nil{%
154       \def\noexpand\Gin@base{####1}%
155     }%
156   }%
157   \grffile@ifFileExists{\filename@area\filename@base#1}{%
158     \grffile@tempa
159     \expandafter\@tempa\grffile@file@found\@nil
160     \edef\Gin@ext{#1}%
161   }{%
162   }%
163 }
164 \def\grffile@ifFileExists#1{%
165   \expandafter\expandafter\expandafter
166   \ifx\expandafter\expandafter\expandafter\\\pdf@filesize{#1}\\\%
167     \let\reserved@a\@secondoftwo
168     \ifx\input@path\@undefined
169     \else
170       \expandafter\@tfor\expandafter\reserved@b\expandafter
171       : \expandafter=\input@path\do{%
172         \expandafter\expandafter\expandafter
173         \ifx\expandafter\expandafter\expandafter
174           \\\pdf@filesize{\reserved@b#1}\\\%
175         \else
176           \edef\grffile@file@found{\reserved@b#1}%
177           \let\reserved@a\@firstoftwo
178           \@break@tfor
179         \fi
180       }%
181     \fi
182     \expandafter\reserved@a
183   \else
184     \edef\grffile@file@found{#1}%
185     \expandafter\@firstoftwo
186   \fi
187 }
188
189 \def\grffile@Gininclude@graphics#1{%
190   \begingroup
191     \ifgrffile@space
192       \let\Gin@getbase\grffile@space@getbase
193     \fi
194     \ifgrffile@multidot
195       \let\filename@base\@empty

```

```

196     \let\filename@simple\grffile@filename@simple
197     \fi
198     \grffile@org@Gininclude@graphics{#1}%
199 \endgroup
200 }%
201
202 \def\grffile@filename@simple#1.#2\\{%
203     \ifx\\#2\\%
204         \ifx\filename@base@empty
205             \let\filename@ext\relax
206         \else
207             \grffile@ReturnAfterFiFiBase{%
208                 \edef\filename@base{\expandafter\filename@dot\filename@base\\}%
209                 \edef\filename@ext{#1}%
210             }%
211         \fi
212     \else
213         \expandafter\ifx\csname
214             Gin@rule@.\filename@dot #2\\endcsname\relax
215             \edef\filename@base{\filename@base #1.}%
216             \grffile@ReturnAfterFiFiBase{\grffile@filename@simple #2\\}%
217         \else
218             \edef\filename@ext{\filename@dot #2\\}%
219         \fi
220     \fi
221     \edef\filename@base{\filename@base #1}%
222 }
223 \def\grffile@ReturnAfterFiFiBase#1#2\fi\edef\filename@base#3{\fi\fi#1}
    Print current option setting
224 \def\grffile@option@status#1{%
225     \begingroup
226     \let\on@line@empty
227     \PackageInfo{grffile}{%
228         Option ‘#1’ is %
229         \expandafter\ifx\csname ifgrffile@#1\expandafter\endcsname
230             \csname iftrue\endcsname
231             set to ‘true’%
232         \else
233             \expandafter\ifx\csname grffile@#1@disabled\endcsname\@empty
234                 not available%
235             \else
236                 set to ‘false’%
237             \fi
238         \fi
239     }%
240 \endgroup
241 }
242 \grffile@option@status{multidot}
243 \grffile@option@status{extendedchars}
244 \grffile@option@status{space}
245 \grffile@RestoreCatcodes
246 \end{package}

```

3 Test

3.1 Multidot with default rule

```

247 \test1
248 \NeedsTeXFormat{LaTeX2e}
249 \documentclass{article}

```



```

250 \usepackage{filecontents}
251 % file grffile-test.mp:
252 % beginfig(1);
253 %   draw fullcircle scaled 2cm withpen pencircle scaled 2mm;
254 % endfig;
255 % end
256 \begin{filecontents*}{grffile-test.1}
257 %!PS
258 %%BoundingBox: -32 -32 32 32
259 %%Creator: MetaPost
260 %%CreationDate: 2004.06.16:1257
261 %%Pages: 1
262 %%EndProlog
263 %%Page: 1 1
264 0 5.66928 dtransform truncate idtransform setlinewidth pop [] 0 setdash
265 1 setlinejoin 10 setmiterlimit
266 newpath 28.34645 0 moveto
267 28.34645 7.51828 25.35938 14.72774 20.04356 20.04356 curveto
268 14.72774 25.35938 7.51828 28.34645 0 28.34645 curveto
269 -7.51828 28.34645 -14.72774 25.35938 -20.04356 20.04356 curveto
270 -25.35938 14.72774 -28.34645 7.51828 -28.34645 0 curveto
271 -28.34645 -7.51828 -25.35938 -14.72774 -20.04356 -20.04356 curveto
272 -14.72774 -25.35938 -7.51828 -28.34645 0 -28.34645 curveto
273 7.51828 -28.34645 14.72774 -25.35938 20.04356 -20.04356 curveto
274 25.35938 -14.72774 28.34645 -7.51828 28.34645 0 curveto closepath stroke
275 showpage
276 %%EOF
277 \end{filecontents*}
278 \usepackage{graphicx}
279 \usepackage[multidot]{grffile}[2008/10/13]
280 \DeclareGraphicsRule{*}{mps}{*}{} % for pdflatex
281 \begin{document}
282 \includegraphics{grffile-test.1}
283 \end{document}
284 </test1>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/grffile.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/grffile.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

¹<http://ftp.ctan.org/tex-archive/>

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain- \TeX :

```
tex grffile.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
grffile.sty          → tex/latex/oberdiek/grffile.sty
grffile.pdf          → doc/latex/oberdiek/grffile.pdf
test/grffile-test1.tex → doc/latex/oberdiek/test/grffile-test1.tex
grffile.dtx          → source/latex/oberdiek/grffile.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your \TeX distribution (te \TeX , mi \TeX , ...) relies on file name databases, you must refresh these. For example, te \TeX users run `texhash` or `mktextlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk grffile.pdf unpack_files output .
```

Unpacking with \LaTeX . The `.dtx` chooses its action depending on the format:

plain- \TeX : Run `docstrip` and extract the files.

\LaTeX : Generate the documentation.

If you insist on using \LaTeX for `docstrip` (really, `docstrip` does not need \LaTeX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{grffile.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdf \LaTeX :

```
pdflatex grffile.dtx
makeindex -s gind.ist grffile.idx
pdflatex grffile.dtx
makeindex -s gind.ist grffile.idx
pdflatex grffile.dtx
```

5 References

- [1] David Carlisle, Sebastian Rahtz: *The graphics package*; 2006/02/20 v1.0o;
[CTAN:macros/latex/required/graphics/graphics.dtx](#).
- [2] Sebastian Rahtz, Heiko Oberdiek: *The graphicx package*; 1999/02/16 v1.0f;
[CTAN:macros/latex/required/graphics/graphicx.dtx](#).

6 History

[2004/07/18 v0.5]

- First version, published in newsgroup [de.comp.text.tex](#):
“[Re: Dateinamenproblem](#)”²

[2006/08/15 v1.0]

- File existence check by new primitives of pdfTeX 1.30.
- Implementation partly rewritten.
- New DTX framework.

[2006/08/17 v1.1]

- Adaptation to version 2.3 of package kvoptions.

[2006/11/30 v1.2]

- New option babel. Before this feature was part of option extendedchars.

[2007/04/11 v1.3]

- Line ends sanitized.

[2007/06/13 v1.4]

- Encoding support added with options encoding, inputencoding, and file-nameencoding.

[2007/08/16 v1.5]

- Bug fix in encoding support.

[2007/11/11 v1.6]

- Use of package pdftexcmds for L^AT_EX support.

[2007/11/24 v1.7]

- Bug fix of broken previous version.

²Url: <http://groups.google.com/group/de.comp.text.tex/msg/b85984095d1a3c95>

[2008/08/11 v1.8]

- Code is not changed.
- URLs updated.

[2008/10/13 v1.9]

- Fix for option ‘multidot’ with default rule.

7 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\’	9, 19
*	12, 22
\.	8, 18
\:	7, 17
\<	10, 20
\=	6, 16
\>	11, 21
\@break@tfor	178
\@ehc	118, 127
\@empty	47, 71, 73, 84, 108, 110, 195, 204, 226, 233
\@firstoftwo	177, 185
\@makeoother	16, 17, 18, 19, 20, 21, 22
\@ne	148
\@nil	153, 159
\@secondoftwo	167
\@tempa	153, 159
\@tfor	170
\@undefined	168
\\	166, 174, 202, 203, 208, 214, 216, 218
\^	13, 23, 96, 97, 98, 99
\~	14, 24, 142
A	
\active	24
\advance	148
\AtBeginDocument	62
B	
\begin	256, 281
C	
\catcode	6, 7, 8, 9, 10, 11, 12, 13, 14, 23, 24
\count@	139, 142, 147, 148
\csname	45, 74, 75, 92, 114, 213, 229, 230, 233
\CurrentInputEncodingOption	78
\CurrentOption	41
D	
\DeclareBoolOption	31, 32, 33, 34
\DeclareDefaultOption	40
\DeclareGraphicsRule	280
\DeclareStringOption	38, 39
\DeclareVoidOption	35
\DisableKeyvalOption	63
\do	171
\documentclass	249
E	
\end	277, 283
\endcsname	45, 74, 76, 92, 114, 214, 229, 230, 233
F	
\filename@area	157
\filename@base	157, 195, 204, 208, 215, 221, 223
\filename@dot	208, 214, 218
\filename@ext	205, 209, 218
\filename@simple	196
G	
\Gin@base	154
\Gin@ext	160
\Gin@getbase	192
\Gininclude@graphics	69, 70
\grffile@extchar@Gininclude@graphics	101, 106
\grffile@extendedcharstrue	86
\grffile@file@found	159, 176, 184
\grffile@filename	107, 120, 123, 134
\grffile@filename@simple	196, 202, 216
\grffile@filenameencoding	71, 112, 121
\grffile@Gininclude@graphics	103, 134, 189
\grffile@IfFileExists	157, 164
\grffile@inputenc@loop	96, 97, 98, 99, 138
\grffile@inputencoding	73, 78, 81, 84, 108, 112, 121
\grffile@option@status	224, 242, 243, 244
\grffile@org@Gininclude@graphics	69, 198
\grffile@RestoreCatcodes	5, 245
\grffile@ReturnAfterFiFiBase	207, 216, 223
\grffile@space@disabled	47
\grffile@space@getbase	151, 192

\grffile@spacefalse	46, 58		
\grffile@spacetrue	48, 56		
\grffile@temp	120, 123		
\grffile@tempa	152, 158		
\grffilesetup	66		
\grfile@filenameencoding	110		
I			
\ifgrffile@babel	89, 91		
\ifgrffile@extendedchars	89, 95		
\ifgrffile@multidot	194		
\ifgrffile@space	191		
\ifnum	89, 147		
\ifpdf	55		
\ifx	45, 71, 73, 74,		
	75, 84, 108, 110, 112, 114, 166,		
	168, 173, 203, 204, 213, 229, 233		
\includegraphics	282		
\input@path	168, 171		
\inputencodingname	81		
L			
\loop	140		
M			
\MessageBreak	50, 116		
N			
\NeedsTeXFormat	2, 248		
\newcommand	66		
O			
\on@line	226		
P			
\PackageError	115, 125		
\PackageInfo	227		
\PackageWarning	49		
\PassOptionsToPackage	41		
\pdf@filesize	166, 174		
\ProcessKeyvalOptions	61		
\ProvidesPackage	3		
R			
\renewcommand	70		
\repeat	149		
\RequirePackage	25, 26, 36, 43, 65		
\reserved@a	167, 177, 182		
\reserved@b	170, 174, 176		
S			
\setkeys	67		
\SetupKeyvalOptions	27		
\StringEncodingConvert	120		
\StringEncodingSuccessFailure ..	122		
T			
\the	6, 7, 8, 9, 10, 11, 12, 13, 14		
U			
\uccode	142		
\uppercase	143		
\usepackage	250, 278, 279		
X			
\x	133, 136		
Z			
\z@	89		