

# The grffile package

Heiko Oberdiek\*  
<heiko.oberdiek at googlemail.com>

2017/06/30 v1.18

## Abstract

The package extends the file name processing of package `graphics` to support a larger range of file names. For example, the file name may contain several dots. Or in case of pdfTeX in PDF mode the file name may contain spaces.

## Contents

<b>1</b>	<b>Usage</b>	<b>2</b>
1.1	Option <code>multidot</code>	2
1.2	Option <code>babel</code>	2
1.3	Option <code>extendedchars</code>	2
1.4	Option <code>encoding</code>	3
1.4.1	Option <code>inputencoding</code>	3
1.4.2	Option <code>filenameencoding</code>	3
1.4.3	Example	3
1.5	Option <code>space</code>	4
1.6	General use	4
1.7	Default settings	4
<b>2</b>	<b>Implementation</b>	<b>5</b>
2.1	Identification	5
2.2	Catcode stuff	5
2.3	Options	5
2.4	Fix <code>\Gin@ii</code> of package <code>graphicx</code>	12
<b>3</b>	<b>Test</b>	<b>13</b>
3.1	Multidot with default rule	13
<b>4</b>	<b>Installation</b>	<b>14</b>
4.1	Download	14
4.2	Bundle installation	14
4.3	Package installation	15
4.4	Refresh file name databases	15
4.5	Some details for the interested	15
<b>5</b>	<b>Catalogue</b>	<b>15</b>
<b>6</b>	<b>References</b>	<b>16</b>

---

\*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

<b>7 History</b>	<b>16</b>
[2004/07/18 v0.5]	16
[2006/08/15 v1.0]	16
[2006/08/17 v1.1]	16
[2006/11/30 v1.2]	16
[2007/04/11 v1.3]	17
[2007/06/13 v1.4]	17
[2007/08/16 v1.5]	17
[2007/11/11 v1.6]	17
[2007/11/24 v1.7]	17
[2008/08/11 v1.8]	17
[2008/10/13 v1.9]	17
[2009/09/25 v1.10]	17
[2010/01/28 v1.11]	17
[2010/08/26 v1.12]	17
[2010/12/09 v1.13]	17
[2011/10/04 v1.14]	17
[2011/10/17 v1.15]	17
[2012/04/05 v1.16]	18
[2016/05/16 v1.17]	18
[2017/06/30 v1.18]	18
<b>8 Index</b>	<b>18</b>

## 1 Usage

### 1.1 Option `multidot`

The file name parsing of package `graphics` is changed, in order to detect known extensions. This allows both the use of dots inside the base file name and extensions with several dots.

Assume there are two files in the current directory: `Hello.World.eps` and `Hello.World.pdf`. `\includegraphics{Hello.World}` will find `Hello.World.pdf` with driver `pdftex` or `Hello.World.eps` with driver `dvips`.

**Limitations:** Problem could occur on systems, which don't use the dot as extension delimiter. These systems need an own `texsys.cfg` containing definitions for `\filename@parse`. The author could not test that, due to a missing example.

### 1.2 Option `babel`

This option allows the use of shorthand characters of package `babel` inside the `graphics` file name. Additionally the tilde '~' is supported. The option is turned on as default. (In version v1.1 or below of this package, the features of this option were part of option `extendedchars`.)

Example:

```
\usepackage[frenchb]{babel}
\usepackage{grffile}
Image: \includegraphics{C:/path/image}
```

### 1.3 Option `extendedchars`

If the input encoding is the same encoding as the encoding that is used for file names and the driver allows non-ascii characters. Without option `extendedchars` the 8-bit characters are expanded, if they are active characters. For example, see the  $\text{\LaTeX}$  package `inputenc`. However a file name is not input for  $\text{\LaTeX}$ . Therefore

this option `extendedchars` removes the active status and the 8-bit characters are not expandable any more.

Example:

```
\usepackage[latin1]{inputenc}
\usepackage[extendedchars]{grffile}
\includegraphics{B ckerstra e}
```

If the `draft` option of the graphics package is enabled, the file name is printed with the current font encoding for `\ttfamily`. Thus it is possible, that such characters are omitted or the wrong characters are displayed, if the font encoding is not the same as the file name encoding.

## 1.4 Option encoding

Consider the following scenario. Your file system is using UTF-8 as encoding for file names. But you use `latin1` as input encoding for your  $\text{\TeX}$  files, because some packages are not ready for multi-byte encodings (`listings`, ...).

Then this option `encoding` loads support for converting encodings by loading package `stringenc`. The option is not defined after the preamble, because  $\text{\LaTeX}$  limits package loading to the preamble.

File names are converted, if package `stringenc` is loaded and the encodings are known, see options `inputencoding` and `filenameencoding`.

### 1.4.1 Option inputencoding

Option `inputencoding` specifies the encoding of the file name in your  $\text{\TeX}$  input file.

Package `inputenx` and package `inputenc` since version 2006/02/22 v1.1a remember the name of the input encoding that is looked up by this package. Therefore option `inputencoding` is usually not mandatory.

### 1.4.2 Option filenameencoding

This is the encoding of the filename of your file system. This option is mandatory, file names are not converted without this option. The option is disabled, if the value is empty.

### 1.4.3 Example

Back to the scenario where the file system uses UTF-8 and the  $\text{\LaTeX}$  input files are encoded in `latin1`.

```
\usepackage[latin1]{inputenc}[2006/02/22]
% \usepackage[latin1]{inputenx}
\usepackage{graphicx}
\usepackage[encoding,filenameencoding=utf8]{grffile}
```

For older versions of package `inputenc` option `inputencoding` provides the necessary informations.

```
\usepackage[latin1]{inputenc}
\usepackage{graphicx}
\usepackage{grffile}
\grffilesetup{
  encoding,
  inputencoding=latin1,
  filenameencoding=utf8,
}
```

## 1.5 Option space

This option allows graphics file names that contain spaces if possible.

In general it is not possible to use space inside file names, because  $\text{\TeX}$  considers the space character as termination in its syntax for commands that expect a file name.

Regarding graphics inclusion with the package `graphics` file names are used in two or three contexts:

1. The basic `\special` statement or primitive command for graphics inclusion. The `\special` statements for drivers `dvips` or `dvipdfm` do not allow spaces. However `pdf\TeX`'s primitive `\pdfximage` uses curly braces to delimit the file name and allows spaces. In case of  $\text{\TeX}$  file names can be enclosed in quotes to support spaces (at the cost that quotes no longer work).

2. `\includegraphics` checks the existence of the file. Also it looks for the right extension if the extension is not given.

If `pdf\TeX` 1.30 is given, the file existence test can be rewritten using a new primitive that allows spaces. This works in both modes DVI and PDF.

In case of  $\text{\TeX}$  the file existence test is rewritten to automatically add quotes.

3. Sometimes files are read as  $\text{\TeX}$  input files. For example, `.bb` files or MPS files.

If `pdf\TeX` 1.30 or greater is used in PDF mode then the graphics file names may contain spaces except for MPS files. Therefore option `space` is only enabled by default, if the supported `pdf\TeX` in PDF mode is detected or  $\text{\TeX}$  is running. You can enable the option manually, if you know, your DVI driver supports spaces in its `\special` syntax and if there is no need to read the image file as  $\text{\TeX}$  input file (third context).

## 1.6 General use

The options can be given at many places:

1. As package options:  
`\usepackage[<options>]{grffile}`
2. Setup command of package `grffile`:  
`\grffilesetup{<options>}`
3. The options are also available as options for package `graphicx`:  
`\setkeys{Gin}{<options>}`
4. If package `graphicx` is loaded the options can also be applied for a single image:  
`\includegraphics[<options>]{...}`

## 1.7 Default settings

<code>multidot</code>	<code>true</code>	
<code>babel</code>	<code>true</code>	
<code>extendedchars</code>	<code>false</code>	
<code>space</code>	<code>true</code>	if <code>pdf\TeX</code> 1.30 or greater is used in PDF mode
	<code>false</code>	otherwise

## 2 Implementation

### 2.1 Identification

```
1 (*package)
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{grffile}%
4 [2017/06/30 v1.18 Extended file name support for graphics (HO)]%
```

### 2.2 Catcode stuff

```
5 \edef\grffile@RestoreCatcodes{%
6   \catcode`\noexpand\=\the\catcode`\=\relax
7   \catcode`\noexpand\:\the\catcode`\:\relax
8   \catcode`\noexpand\.\the\catcode`\.\relax
9   \catcode`\noexpand\'\the\catcode`\'\relax
10  \catcode`\noexpand\<\the\catcode`\<\relax
11  \catcode`\noexpand\>\the\catcode`\>\relax
12  \catcode`\noexpand\*\the\catcode`\*\relax
13  \catcode`\noexpand\^\the\catcode`\^\relax
14  \catcode`\noexpand\~\the\catcode`\~\relax
15 }
16 \@makeother\=
17 \@makeother\:
18 \@makeother\.
19 \@makeother\'
20 \@makeother\<
21 \@makeother\>
22 \@makeother\*
23 \catcode`\^=7 %
24 \catcode`\~=active
```

### 2.3 Options

```
25 \RequirePackage{ifpdf}[2010/01/28]
26 \RequirePackage{ifxetex}[2010/09/12]
27 \RequirePackage{kvoptions}[2006/08/17]
28 \SetupKeyvalOptions{%
29   family=Gin,%
30   prefix=grffile@%
31 }
32 \DeclareDefaultOption{\@unknownoptionerror}
33 \DeclareBoolOption[true]{multidot}
34 \DeclareBoolOption[true]{babel}
35 \DeclareBoolOption[false]{extendedchars}
36 \DeclareBoolOption{space}
37 \DeclareVoidOption{encoding}{%
38   \RequirePackage{stringenc}\relax
39 }
40 \DeclareStringOption{inputencoding}
41 \DeclareStringOption{filenameencoding}
42 \DeclareDefaultOption{%
43   \PassOptionsToPackage\CurrentOption{graphics}%
44 }
```

Default setting for option space.

```
45 \RequirePackage{pdftexcmds}[2007/11/11]
46 \ifxetex
47   \grffile@spacetrue
48 \else
49   \begingroup\expandafter\expandafter\expandafter\endgroup
50   \expandafter\ifx\csname pdf@filesize\endcsname\relax
51     \grffile@spacefalse
52     \let\grffile@space@disabled\@empty
53   \def\grffile@spacetrue{%
```

```

54     \PackageWarning{grffile}{%
55       Option `space' is not available,\MessageBreak
56       because it needs pdfTeX >= 1.30 or XeTeX%
57     }%
58   }%
59   \else
60     \ifpdf
61       \grffile@spacetrue
62     \else
63       \grffile@spacefalse
64     \fi
65   \fi
66 \fi

67 \ProcessKeyvalOptions*
68 \AtBeginDocument{%
69   \DisableKeyvalOption[package=grffile]{Gin}{encoding}%
70 }

71 \RequirePackage{graphics}

\grffilesetup

72 \newcommand*{\grffilesetup}{%
73   \setkeys{Gin}%
74 }

```

\grffile@org@Gininclude@graphics

```

75 \let\grffile@org@Gininclude@graphics\Gininclude@graphics

```

\Gininclude@graphics

```

76 \renewcommand*{\Gininclude@graphics}{%
77   \ifx\grffile@filenameencoding\@empty
78   \else
79     \ifx\grffile@inputencoding\@empty
80       \expandafter\ifx\csname inputencodingname\endcsname\relax
81         \expandafter\ifx\csname
82           CurrentInputEncodingOption\endcsname\relax
83         \else
84           \let\grffile@inputencoding\CurrentInputEncodingOption
85         \fi
86       \else
87         \let\grffile@inputencoding\inputencodingname
88       \fi
89     \fi
90     \ifx\grffile@inputencoding\@empty
91     \else
92       \grffile@extendedcharstrue
93     \fi
94   \fi
95   \ifnum0\ifgrffile@babel 1\fi\ifgrffile@extendedchars 1\fi>\z@
96   \begingroup

```

Support of babel's shorthand characters.

```

97     \ifgrffile@babel
98       \csname @safe@activetrue\endcsname

```

Support of active tilde.

```

99     \edef~{\string~}%

```

Support of characters controlled by package inputenc.

```

100   \fi
101   \ifgrffile@extendedchars
102     \grffile@inputenc@loop\^^A\^^H%
103     \grffile@inputenc@loop\^^K\^^K%
104     \grffile@inputenc@loop\^^N\^^_%

```

```

105     \grffile@inputenc@loop\^^?\^^ff%
106     \fi
107     \expandafter\grffile@extchar@Ginclude@graphics
108 \else
109     \expandafter\grffile@Ginclude@graphics
110 \fi
111 }

\grffile@extchar@Ginclude@graphics
112 \def\grffile@extchar@Ginclude@graphics#1{%
113     \toks@{#1}%
114     \edef\grffile@filename{\the\toks@}%
115     \ifx\grffile@inputencoding\@empty
116     \else
117         \ifx\grffile@filenameencoding\@empty
118         \else
119             \ifx\grffile@inputencoding\grffile@filenameencoding
120             \else
121                 \expandafter\ifx\csname StringEncodingConvert\endcsname\relax
122                 \PackageError{grffile}{%
123                     Package `stringenc' is not loaded,\MessageBreak
124                     omitting file name conversion%
125                 }\@ehc
126             \else
127                 \StringEncodingConvert\grffile@temp\grffile@filename
128                 \grffile@inputencoding\grffile@filenameencoding
129                 \StringEncodingSuccessFailure{%
130                     \let\grffile@filename\grffile@temp
131                 }{%
132                     \PackageError{grffile}{%
133                         Filename conversion failed%
134                     }\@ehc
135                 }%
136             \fi
137         \fi
138     \fi
139 \fi
140 % \toks@\expandafter{\grffile@filename}%
141 \edef\x{\endgroup
142 % \noexpand\grffile@Ginclude@graphics{\the\toks@}%
143 \noexpand\grffile@Ginclude@graphics{\grffile@filename}%
144 }%
145 \x
146 }

```

\grffile@inputenc@loop

```

147 \def\grffile@inputenc@loop#1#2{%
148     \count@=#1\relax
149     \loop
150         \begingroup
151         \uccode`~=\count@
152         \uppercase{%
153             \endgroup
154             \edef~{\string~}%
155         }%
156     \ifnum\count@<`#2\relax
157         \advance\count@\@ne
158     \repeat
159 }

```

Support for option space

\grffile@space@getbase

```

160 \def\grffile@space@getbase#1{%
161   \edef\grffile@tempa{%
162     \def\noexpand\@tempa####1#1\noexpand\@nil{%
163       \def\noexpand\Gin@base{####1}%
164     }%
165   }%
166   \grffile@ifFileExists{\filename@area\filename@base#1}{%
167     \grffile@tempa
168     \expandafter\@tempa\grffile@file@found\@nil
169     \edef\Gin@ext{#1}%
170   }{%
171   }%
172 }

173 \begingroup\expandafter\expandafter\expandafter\endgroup
174 \expandafter\ifx\csname pdf@filesize\endcsname\relax
175   \ifxetex

```

\grffile@XeTeX@ifFileExists

```

176   \long\def\grffile@XeTeX@ifFileExists#1{%
177     \openin\@inputcheck"#1" %
178     \ifeof\@inputcheck
179       \closein\@inputcheck
180       \expandafter\@secondoftwo
181     \else
182       \closein\@inputcheck
183       \expandafter\@firstoftwo
184     \fi
185   }%

```

\grffile@ifFileExists

```

186   \long\def\grffile@ifFileExists#1{%
187     \grffile@XeTeX@ifFileExists{#1}{%
188       \edef\grffile@file@found{#1}%
189       \@firstoftwo
190     }{%
191       \let\reserved@a\@secondoftwo
192       \ifx\input@path\@undefined
193       \else
194         \expandafter\@tfor\expandafter\reserved@b\expandafter
195         :\expandafter=\input@path\do{%
196           \grffile@XeTeX@ifFileExists{\reserved@b#1}{%
197             \edef\grffile@file@found{\reserved@b#1}%
198             \let\reserved@a\@firstoftwo
199             \iftrue\@break@tfor\fi
200           }{}%
201         }%
202       \fi
203       \reserved@a
204     }%
205   }%

```

\grffile@org@Gread@QTm Patch \Gread@QTm of xetex.def.

```

206   \def\grffile@org@Gread@QTm#1{%
207     \ifFileExists{\Gin@base.bb}{%
208       \Gread@eps{\Gin@base.bb}%
209     }{%
210       \G@measure@QTm{\Gin@base}{\Gin@ext}%
211     }%
212   }%

213   \ifx\Gread@QTm\grffile@org@Gread@QTm

```



```

\Gread@QTm
214 \def\Gread@QTm#1{%
215 \grffile@ifFileExists{\Gin@base.bb}{%
216 \Gread@eps{\Gin@base.bb}%
217 }{%
218 \G@measure@QTm{\Gin@base}{\Gin@ext}%
219 }%
220 }%

221 \PackageInfo{grffile}{\string\Gread@QTm\space patched}%
222 \else
223 \begingroup\expandafter\expandafter\expandafter\endgroup
224 \expandafter\ifx\csname Gread@QTm\endcsname\relax
225 \@ifpackagelater{graphics}{2017/06/01}
226 {}
227 {%
228 \PackageWarning{grffile}{%
229 \string\Gread@QTm\space of xetex.def not found%
230 }%
231 }%
232 \else

\grffile@org@Gread@QTm
233 \let\grffile@org@Gread@QTm\Gread@QTm

\Gread@QTm
234 \def\Gread@QTm#1{%
235 \let\grffile@saved@ifFileExists@ifFileExists
236 \let@ifFileExists\grffile@ifFileExists
237 \grffile@org@Gread@QTm{#1}%
238 \let@ifFileExists\grffile@saved@ifFileExists
239 }%

240 \fi
241 \fi

\grffile@org@Gread@eps
242 \let\grffile@org@Gread@eps\Gread@eps

243 \def\grffile@temp#1\immediate\openin#2 #3\grffile@nil#4\grffile@NIL{%
244 \begingroup
245 \toks@{#2}%
246 \edef\grffile@temp{\the\toks@}%
247 \def\grffile@test{\@inputcheck###1}%
248 \ifx\grffile@temp\grffile@test
249 \expandafter\@firstoftwo
250 \else
251 \expandafter\@secondoftwo
252 \fi
253 {%
254 \toks@{%
255 #1%
256 \immediate\openin\@inputcheck"###1"\relax
257 #3%
258 }%
259 \expandafter\endgroup
260 \expandafter\def\expandafter\Gread@eps
261 \expandafter##\expandafter1\expandafter{%
262 \the\toks@
263 }%
264 \PackageInfo{grffile}{%
265 \string\Gread@eps\space patched%
266 }%

```

```

267   }{%
268     \@ifpackagelater{graphics}{2017/06/01}
269     {}
270     {%
271       \PackageWarning{grffile}{%
272         Unsupported \string\Gread@eps\space not patched%
273       }%
274     }%
275     \endgroup
276   }%
277 }%
278 \expandafter\grffile@temp\Gread@eps{#1}\grffile@nil
279 \immediate\openin{}\grffile@nil\grffile@NIL
280 \else
281   \begingroup
282   \let\on@line\@empty
283   \PackageInfo{grffile}{%
284     \string\grffile@ifFileExists\space without space support,%
285     \MessageBreak
286     because pdfTeX's \string\pdffilesize\space is not available%
287     \MessageBreak
288     or XeTeX is not running%
289   }%
290 \endgroup

```

\grffile@ifFileExists

```

291 \long\def\grffile@ifFileExists#1{%
292   \ifFileExists{#1}{%
293     \let\grffile@IFE@next\@firstoftwo
294   }{%
295     \let\grffile@file@found\@file@und
296     \let\grffile@IFE@next\@secondoftwo
297   }%
298   \grffile@IFE@next
299 }%

300 \fi
301 \else

```

\grffile@ifFileExists

```

302 \long\def\grffile@ifFileExists#1{%
303   \expandafter\expandafter\expandafter
304   \ifx\expandafter\expandafter\expandafter\\\pdf@filesize{#1}\\\%
305   \let\reserved@a\@secondoftwo
306   \ifx\input@path\@undefined
307   \else
308     \expandafter\@tfor\expandafter\reserved@b\expandafter
309     : \expandafter=\input@path\do{%
310       \expandafter\expandafter\expandafter
311       \ifx\expandafter\expandafter\expandafter
312         \\\pdf@filesize{\reserved@b#1}\\\%
313       \else
314         \edef\grffile@file@found{\reserved@b#1}%
315         \let\reserved@a\@firstoftwo
316         \@break@tfor
317       \fi
318     }%
319   \fi
320   \expandafter\reserved@a
321 \else
322   \edef\grffile@file@found{#1}%
323   \expandafter\@firstoftwo

```

```

324 \fi
325 }%

326 \fi

\grffile@Ginclude@graphics
327 \def\grffile@Ginclude@graphics#1{%
328 \begingroup
329 \ifgrffile@space
330 \let\Gin@getbase\grffile@space@getbase
331 \fi
332 \ifgrffile@multidot
333 \let\filename@base\@empty
334 \let\filename@simple\grffile@filename@simple
335 \fi
336 \grffile@org@Ginclude@graphics{#1}%
337 \endgroup
338 }%

\grffile@filename@simple
339 \def\grffile@filename@simple#1.#2\\{%
340 \ifx\\#2\\%
341 \def\filename@base{#1}%
342 \let\filename@ext\relax
343 \else
344 \def\filename@base{}%
345 \grffile@analyze@ext{#1}.#2\\%
346 \fi
347 }

\grffile@analyze@ext
348 \def\grffile@analyze@ext#1.#2\\{%
349 \let\grffile@next\relax
350 \ifx\\#2\\%
351 \edef\filename@base{\filename@base#1}%
352 \let\filename@ext\relax
353 \def\grffile@next{\grffile@try@extlist}%
354 \else
355 \edef\filename@base{\filename@base #1}%
356 \edef\filename@ext{\filename@dot#2\\}%
357 \expandafter\ifx\csname Gin@rule@.\filename@ext\endcsname\relax
358 \edef\filename@base{\filename@base.}%
359 \def\grffile@next{\grffile@analyze@ext#2\\}%
360 \else
361 \grffile@ifFileExists{\filename@area\filename@base.\filename@ext}{%
362 % success
363 }{%
364 \edef\filename@base{\filename@base.\filename@ext}%
365 \let\filename@ext\relax
366 \def\grffile@next{\grffile@try@extlist}%
367 }%
368 \fi
369 \fi
370 \grffile@next
371 }

\grffile@try@extlist
372 \def\grffile@try@extlist{%
373 \@for\grffile@temp:=\Gin@extensions\do{%
374 \grffile@ifFileExists{\filename@area\filename@base\grffile@temp}{%
375 \ifx\filename@ext\relax
376 \edef\filename@ext{\expandafter\@gobble\grffile@temp\@empty}%

```

```

377     \fi
378   }{}%
379 }%
380 \ifx\filename@ext\relax
381   \expandafter\let\expandafter\filename@base\expandafter\@empty
382   \expandafter\grffile@use@last@ext\filename@base.\%
383 \fi
384 }

```

\grffile@use@last@ext

```

385 \def\grffile@use@last@ext#1.#2\{%
386   \ifx\#2\%
387     \edef\filename@base{\expandafter\filename@dot\filename@base\}%
388     \def\filename@ext{#1}%
389     \expandafter\@gobble
390   \else
391     \edef\filename@base{\filename@base#1}%
392     \expandafter\@firstofone
393   \fi
394   {%
395     \grffile@use@last@ext#2\%
396   }%
397 }

```

Print current option setting

\grffile@option@status

```

398 \def\grffile@option@status#1{%
399   \begingroup
400   \let\on@line\@empty
401   \PackageInfo{grffile}{%
402     Option `#1' is %
403     \expandafter\ifx\csname ifgrffile@#1\expandafter\endcsname
404       \csname iftrue\endcsname
405       set to `true'%
406     \else
407       \expandafter\ifx\csname grffile@#1@disabled\endcsname\@empty
408       not available%
409     \else
410       set to `false'%
411     \fi
412   \fi
413   }%
414 \endgroup
415 }

416 \grffile@option@status{multidot}
417 \grffile@option@status{extendedchars}
418 \grffile@option@status{space}

```

## 2.4 Fix \Gin@ii of package graphicx

If the image file name contains the hash character macro \Gin@ii of package graphicx breaks.

\grffile@Gin@ii@graphicx

```

419 \def\grffile@Gin@ii@graphicx[#1]#2{%
420   \def\@tempa{[]}%
421   \def\@tempb{#2}%
422   \ifx\@tempa\@tempb
423     \def\@tempa{\Gin@iii[#1][]}% hash-ok
424     \expandafter\@tempa
425   \else

```

```

426 \begingroup
427 \@tempswafalse
428 \toks@{\Gininclude@graphics{#2}}%
429 \setkeys{Gin}{#1}%
430 \Gin@esetsize
431 \the\toks@
432 \endgroup
433 \fi
434 }

```

`\grffile@Gin@ii@fixed`

```

435 \def\grffile@Gin@ii@fixed[#1]#2{%
436 \def\@tempa{[]}%
437 \begingroup
438 \toks@={#2}%
439 \edef\@tempb{\the\toks@}%
440 \expandafter\endgroup
441 \ifx\@tempa\@tempb
442 \def\@tempa{\Gin@iii[#1][[]}% hash-ok
443 \expandafter\@tempa
444 \else
445 \begingroup
446 \@tempswafalse
447 \toks@{\Gininclude@graphics{#2}}%
448 \setkeys{Gin}{#1}%
449 \Gin@esetsize
450 \the\toks@
451 \endgroup
452 \fi
453 }

```

`\grffile@Fix@Gin@ii`

```

454 \def\grffile@Fix@Gin@ii{%
455 \let\Gin@ii\grffile@Gin@ii@fixed
456 \begingroup
457 \escapechar=92 %
458 \PackageInfo{grffile}{\string\Gin@ii\space of package `graphicx' fixed}%
459 \endgroup
460 }

461 \ifx\Gin@ii\grffile@Gin@ii@graphicx
462 \grffile@Fix@Gin@ii
463 \else
464 \AtBeginDocument{\grffile@Fix@Gin@ii}%
465 \fi

466 \grffile@RestoreCatcodes
467 </package>

```

## 3 Test

### 3.1 Multidot with default rule

```

468 (*test1)
469 \NeedsTeXFormat{LaTeX2e}
470 \documentclass{article}
471 \usepackage{filecontents}
472 % file grffile-test.mp:
473 % beginfig(1);
474 % draw fullcircle scaled 2cm withpen pencircle scaled 2mm;
475 % endfig;
476 % end

```

```

477 \begin{filecontents*}{grfile-test.1}
478 %!PS
479 %%BoundingBox: -32 -32 32 32
480 %%Creator: MetaPost
481 %%CreationDate: 2004.06.16:1257
482 %%Pages: 1
483 %%EndProlog
484 %%Page: 1 1
485 0 5.66928 dtransform truncate idtransform setlinewidth pop [] 0 setdash
486 1 setlinejoin 10 setmiterlimit
487 newpath 28.34645 0 moveto
488 28.34645 7.51828 25.35938 14.72774 20.04356 20.04356 curveto
489 14.72774 25.35938 7.51828 28.34645 0 28.34645 curveto
490 -7.51828 28.34645 -14.72774 25.35938 -20.04356 20.04356 curveto
491 -25.35938 14.72774 -28.34645 7.51828 -28.34645 0 curveto
492 -28.34645 -7.51828 -25.35938 -14.72774 -20.04356 -20.04356 curveto
493 -14.72774 -25.35938 -7.51828 -28.34645 0 -28.34645 curveto
494 7.51828 -28.34645 14.72774 -25.35938 20.04356 -20.04356 curveto
495 25.35938 -14.72774 28.34645 -7.51828 28.34645 0 curveto closepath stroke
496 showpage
497 %%EOF
498 \end{filecontents*}
499 \usepackage{graphicx}
500 \usepackage[multidot]{grfile}[2008/10/13]
501 \DeclareGraphicsRule{*}{mps}{*}{} % for pdflatex
502 \begin{document}
503 \includegraphics{grfile-test.1}
504 \end{document}
505 \end{test1}

```

## 4 Installation

### 4.1 Download

**Package.** This package is available on CTAN<sup>1</sup>:

[CTAN:macros/latex/contrib/oberdiek/grfile.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/grfile.pdf](#) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

*TDS* refers to the standard “A Directory Structure for T<sub>E</sub>X Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

### 4.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

---

<sup>1</sup><http://ctan.org/pkg/grfile>

### 4.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting docstrip archive. The files are extracted by running the `.dtx` through plain  $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ :

```
tex grffile.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
grffile.sty      → tex/latex/oberdiek/grffile.sty
grffile.pdf      → doc/latex/oberdiek/grffile.pdf
test/grffile-test1.tex → doc/latex/oberdiek/test/grffile-test1.tex
grffile.dtx      → source/latex/oberdiek/grffile.dtx
```

If you have a `docstrip.cfg` that configures and enables docstrip's TDS installing feature, then some files can already be in the right place, see the documentation of docstrip.

### 4.4 Refresh file name databases

If your  $\mathrm{T}_{\mathrm{E}}\mathrm{X}$  distribution (te $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ , mik $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ , ...) relies on file name databases, you must refresh these. For example, te $\mathrm{T}_{\mathrm{E}}\mathrm{X}$  users run `texhash` or `mktextlsr`.

### 4.5 Some details for the interested

**Unpacking with  $\mathrm{L}^{\mathrm{A}}\mathrm{T}_{\mathrm{E}}\mathrm{X}$ .** The `.dtx` chooses its action depending on the format:

**plain  $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ :** Run docstrip and extract the files.

**$\mathrm{L}^{\mathrm{A}}\mathrm{T}_{\mathrm{E}}\mathrm{X}$ :** Generate the documentation.

If you insist on using  $\mathrm{L}^{\mathrm{A}}\mathrm{T}_{\mathrm{E}}\mathrm{X}$  for docstrip (really, docstrip does not need  $\mathrm{L}^{\mathrm{A}}\mathrm{T}_{\mathrm{E}}\mathrm{X}$ ), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{grffile.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdf $\mathrm{L}^{\mathrm{A}}\mathrm{T}_{\mathrm{E}}\mathrm{X}$ :

```
pdflatex grffile.dtx
makeindex -s gind.ist grffile.idx
pdflatex grffile.dtx
makeindex -s gind.ist grffile.idx
pdflatex grffile.dtx
```

## 5 Catalogue

The following XML file can be used as source for the  [\$\mathrm{T}\_{\mathrm{E}}\mathrm{X}\$  Catalogue](#). The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `grffile.xml`.

```
506 (*catalogue)
507 <?xml version='1.0' encoding='us-ascii'?>
508 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
```

```

509 <entry datestamp='$Date$' modifier='$Author$' id='grffile'>
510   <name>grffile</name>
511   <caption>Extended file name support for graphics.</caption>
512   <authorref id='auth:oberdiek' />
513   <copyright owner='Heiko Oberdiek' year='2006-2012' />
514   <license type='lppl1.3' />
515   <version number='1.18' />
516   <description>
517     The package extends the file name processing of package
518     <xref refid='graphics'>graphics</xref> to support a larger range
519     of file names. For example, the file name may contain several dots.
520
521     Or in case of <xref refid='pdfTeX'>pdfTeX</xref> in PDF mode the
522     file name may contain spaces.
523   <p/>
524   The package is part of the <xref refid='oberdiek'>oberdiek</xref>
525   bundle.
526 </description>
527 <documentation details='Package documentation'
528   href='ctan:/macros/latex/contrib/oberdiek/grffile.pdf' />
529 <ctan file='true' path='/macros/latex/contrib/oberdiek/grffile.dtx' />
530 <miktex location='oberdiek' />
531 <texlive location='oberdiek' />
532 <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip' />
533 </entry>
534 </catalogue>

```

## 6 References

- [1] David Carlisle, Sebastian Rahtz: *The graphics package*; 2006/02/20 v1.0o;  
[CTAN:macros/latex/required/graphics/graphics.dtx](#).
- [2] Sebastian Rahtz, Heiko Oberdiek: *The graphicx package*; 1999/02/16 v1.0f;  
[CTAN:macros/latex/required/graphics/graphicx.dtx](#).

## 7 History

[2004/07/18 v0.5]

- First version, published in newsgroup [de.comp.text.tex](#):  
 “[Re: Dateinamenproblem](#)”<sup>2</sup>

[2006/08/15 v1.0]

- File existence check by new primitives of pdfTeX 1.30.
- Implementation partly rewritten.
- New DTX framework.

[2006/08/17 v1.1]

- Adaptation to version 2.3 of package kvoptions.

[2006/11/30 v1.2]

- New option babel. Before this feature was part of option extendedchars.

---

<sup>2</sup>Url: <http://groups.google.com/group/de.comp.text.tex/msg/b85984095d1a3c95>



[2007/04/11 v1.3]

- Line ends sanitized.

[2007/06/13 v1.4]

- Encoding support added with options `encoding`, `inputencoding`, and `filenameencoding`.

[2007/08/16 v1.5]

- Bug fix in encoding support.

[2007/11/11 v1.6]

- Use of package `pdftexcmds` for LuaTeX support.

[2007/11/24 v1.7]

- Bug fix of broken previous version.

[2008/08/11 v1.8]

- Code is not changed.
- URLs updated.

[2008/10/13 v1.9]

- Fix for option ‘`multidot`’ with default rule.

[2009/09/25 v1.10]

- Rewrite of ‘`multidot`’ algorithm to fix a problem (‘`multidot`’ with `\graphicspath`).

[2010/01/28 v1.11]

- Undefined `\pdf@filesize` fixed.

[2010/08/26 v1.12]

- Macro `\Gin@ii` of package `graphicx` fixed for the case that the file name contains a hash.

[2010/12/09 v1.13]

- Option `space` also supports X<sub>Y</sub>TeX.

[2011/10/04 v1.14]

- Fix for option `space` support of X<sub>Y</sub>TeX for EPS files (`\Gread@eps`). (Bug reported by Peter Davis.)

[2011/10/17 v1.15]

- Bug fix for option `space` support of X<sub>Y</sub>TeX. Wrong usage of `\@break@tfor` fixed. (Bug reported by Martin Schröder.)

[2012/04/05 v1.16]

- Some fix for option extendedchars.

[2016/05/16 v1.17]

- Documentation updates.

[2017/06/30 v1.18]

- Update to follow graphics changes.

## 8 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	C
\' ..... 9, 19	\catcode ..... 6,
\* ..... 12, 22	7, 8, 9, 10, 11, 12, 13, 14, 23, 24
\. .... 8, 18	\closein ..... 179, 182
\: ..... 7, 17	\count@ ..... 148, 151, 156, 157
\< ..... 10, 20	\csname ..... 50, 80, 81,
\= ..... 6, 16	98, 121, 174, 224, 357, 403, 404, 407
\> ..... 11, 21	\CurrentInputEncodingOption .... 84
\@break@tfor ..... 199, 316	\CurrentOption ..... 43
\@ehc ..... 125, 134	
\@empty ..... 52, 77, 79, 90, 115,	D
117, 282, 333, 376, 381, 400, 407	\DeclareBoolOption ..... 33, 34, 35, 36
\@filef@und ..... 295	\DeclareDefaultOption ..... 32, 42
\@firstofone ..... 392	\DeclareGraphicsRule ..... 501
\@firstoftwo ..... 183, 189, 198, 249, 293, 315, 323	\DeclareStringOption ..... 40, 41
\@for ..... 373	\DeclareVoidOption ..... 37
\@gobble ..... 376, 389	\DisableKeyvalOption ..... 69
\@ifpackagelater ..... 225, 268	\do ..... 195, 309, 373
\@inputcheck 177, 178, 179, 182, 247, 256	\documentclass ..... 470
\@makeother .. 16, 17, 18, 19, 20, 21, 22	E
\@ne ..... 157	\end ..... 498, 504
\@nil ..... 162, 168	\endcsname ..... 50, 80, 82,
\@secondoftwo .. 180, 191, 251, 296, 305	98, 121, 174, 224, 357, 403, 404, 407
\@tempa ..... 162, 168, 420,	\escapechar ..... 457
422, 423, 424, 436, 441, 442, 443	F
\@tempb ..... 421, 422, 439, 441	\filename@area ..... 166, 361, 374
\@tempswafalse ..... 427, 446	\filename@base ..... 166,
\@tfor ..... 194, 308	333, 341, 344, 351, 355, 358,
\@undefined ..... 192, 306	361, 364, 374, 381, 382, 387, 391
\@unknownoptionerror ..... 32	\filename@dot ..... 356, 387
\\ 304, 312, 339, 340, 345, 348, 350,	\filename@ext .. 342, 352, 356, 357,
356, 359, 382, 385, 386, 387, 395	361, 364, 365, 375, 376, 380, 388
\^ ..... 13, 23, 102, 103, 104, 105	\filename@simple ..... 334
\~ ..... 14, 24, 151	G
A	\G@measure@QTm ..... 210, 218
\active ..... 24	\Gin@base ..... 163, 207, 208, 210, 215, 216, 218
\advance ..... 157	\Gin@esetsize ..... 430, 449
\AtBeginDocument ..... 68, 464	\Gin@ext ..... 169, 210, 218
B	\Gin@extensions ..... 373
\begin ..... 477, 502	\Gin@getbase ..... 330

\Gin@ii	455, 458, 461	174, 192, 213, 224, 248, 304,	
\Gin@iii	423, 442	306, 311, 340, 350, 357, 375,	
\Gin@graphics	75, 76, 428, 447	380, 386, 403, 407, 422, 441, 461	
\Gread@eps	208, 216, 242, 260, 265, 272, 278	\ifxetex	46, 175
\Gread@QTm	213, 214, 221, 229, 233, 234	\immediate	243, 256, 279
\grffile@analyze@ext	345, 348	\includegraphics	503
\grffile@extchar@Gin@graphics	107, 112	\input@path	192, 195, 306, 309
\grffile@extendedchartrue	92	\inputencodingname	87
\grffile@file@found	168, 188, 197, 295, 314, 322	<b>L</b>	
\grffile@filename	114, 127, 130, 140, 143	\loop	149
\grffile@filename@simple	334, 339	<b>M</b>	
\grffile@filenameencoding	77, 119, 128	\MessageBreak	55, 123, 285, 287
\grffile@Fix@Gin@ii	454, 462, 464	<b>N</b>	
\grffile@Gin@ii@fixed	435, 455	\NeedsTeXFormat	2, 469
\grffile@Gin@ii@graphicx	419, 461	\newcommand	72
\grffile@Gin@graphics	109, 142, 143, 327	<b>O</b>	
\grffile@IFE@next	293, 296, 298	\on@line	282, 400
\grffile@IfFileExists	166, 186, 215, 236, 284, 291, 302, 361, 374	\openin	177, 243, 256, 279
\grffile@inputenc@loop	102, 103, 104, 105, 147	<b>P</b>	
\grffile@inputencoding	79, 84, 87, 90, 115, 119, 128	\PackageError	122, 132
\grffile@next	349, 353, 359, 366, 370	\PackageInfo	221, 264, 283, 401, 458
\grffile@NIL	243, 279	\PackageWarning	54, 228, 271
\grffile@nil	243, 278, 279	\PassOptionsToPackage	43
\grffile@option@status	398, 416, 417, 418	\pdf@filesize	304, 312
\grffile@org@Gin@graphics	75, 336	\pdfsize	286
\grffile@org@Gread@eps	242	\ProcessKeyvalOptions	67
\grffile@org@Gread@QTm	206, 213, 233	\ProvidesPackage	3
\grffile@org@Gread@QTm	237	<b>R</b>	
\grffile@RestoreCatcodes	5, 466	\renewcommand	76
\grffile@sav@IfFileExists	235, 238	\repeat	158
\grffile@space@disabled	52	\RequirePackage	25, 26, 27, 38, 45, 71
\grffile@space@getbase	160, 330	\reserved@a	191, 198, 203, 305, 315, 320
\grffile@space@false	51, 63	\reserved@b	194, 196, 197, 308, 312, 314
\grffile@space@true	47, 53, 61	<b>S</b>	
\grffile@temp	127, 130, 243, 246, 248, 278, 373, 374, 376	\setkeys	73, 429, 448
\grffile@tempa	161, 167	\SetupKeyvalOptions	28
\grffile@test	247, 248	\space	221, 229, 265, 272, 284, 286, 458
\grffile@try@extlist	353, 366, 372	\StringEncodingConvert	127
\grffile@use@last@ext	382, 385	\StringEncodingSuccessFailure	129
\grffile@XeTeX@IfFileExists	176, 187, 196	<b>T</b>	
\grffile@setup	72	\the	6, 7, 8, 9, 10, 11, 12, 13, 14, 114, 142, 246, 262, 431, 439, 450
\grffile@filenameencoding	117	\toks@	113, 114, 140, 142, 245, 246, 254, 262, 428, 431, 438, 439, 447, 450
<b>I</b>		<b>U</b>	
\ifeof	178	\uccode	151
\IfFileExists	207, 235, 236, 238, 292	\uppercase	152
\ifgrffile@babel	95, 97	\usepackage	471, 499, 500
\ifgrffile@extendedchars	95, 101	<b>X</b>	
\ifgrffile@multidot	332	\x	141, 145
\ifgrffile@space	329	<b>Z</b>	
\ifnum	95, 156	\z@	95
\ifpdf	60		
\iftrue	199		
\ifx	50, 77, 79, 80, 81, 90, 115, 117, 119, 121,		