

The `holo` package

Heiko Oberdiek*
<heiko.oberdiek at googlemail.com>

2016/05/16 v1.12

Abstract

This package starts a collection of logos with support for bookmarks strings.

Contents

1 Documentation	3
1.1 Logo macros	3
1.2 Setup macros	4
1.3 Options	5
1.4 Driver options	5
1.5 Font setup	6
1.5.1 Font order	7
1.6 Additional user macros	7
1.7 Supported contexts	7
1.8 Example	8
2 Implementation	10
2.1 Logo list	12
2.2 Load resources	13
2.3 Setup macros	14
2.4 Options	15
2.5 Break/no-break support	16
2.6 Font support	18
2.6.1 Font defaults	18
2.6.2 Font setup	20
2.7 Generic logo commands	21
2.7.1 \holo and friends	21
2.7.2 \holoRobust and friends	24
2.8 Helpers	25
2.8.1 Text subscript	27
2.9 TeX and friends	27
2.9.1 TeX	27
2.9.2 plain TeX	28
2.9.3 LATEX	29
2.9.4 (L)ATEX	30
2.9.5 LATEX 2 ε	32
2.9.6 LATEX3	33

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

2.9.7	$\text{\LaTeX}\text{XML}$	34
2.9.8	$\varepsilon\text{-}\text{\TeX}$	34
2.9.9	ini \TeX	35
2.9.10	vir \TeX	36
2.9.11	SLi \TeX	36
2.9.12	Lua \TeX	39
2.9.13	Lua \LaTeX	39
2.9.14	X \TeX , X \LaTeX	39
2.9.15	pdf \TeX , pdf \LaTeX	44
2.9.16	VT \TeX	45
2.9.17	$\mathcal{AM}\mathcal{S}$	45
2.9.18	BIB \TeX	46
2.9.19	BIB \TeX 8	48
2.9.20	Con \TeX t	49
2.9.21	em \TeX	50
2.9.22	$\varepsilon_X\text{\TeX}$	50
2.9.23	MiK \TeX	51
2.9.24	Oz \TeX and friends	51
2.9.25	PCT \TeX	52
2.9.26	PiC \TeX	52
2.9.27	te \TeX	54
2.9.28	T \TeX 4ht	54
2.9.29	Sage \TeX	54
2.10	METAFONT and friends	55
2.11	Others	55
2.11.1	biber	55
2.11.2	KOMA-Script	56
2.11.3	LyX	57
2.11.4	N $\mathcal{T}\mathcal{S}$	58
2.11.5	T H (T \TeX to HTML translator)	58
2.11.6	Hàn Thé Thành	58
2.12	Driver detection	59
2.12.1	Reflect box macros	62
3	Test	64
3.1	Catcode checks for loading	64
3.2	Spacefactor	66
3.3	Complete list	67
4	Installation	68
4.1	Download	68
4.2	Bundle installation	69
4.3	Package installation	69
4.4	Refresh file name databases	69
4.5	Some details for the interested	69
5	Catalogue	70
6	References	71

7	History	71
[2010/04/08 v1.0]		71
[2010/04/16 v1.1]		71
[2010/04/24 v1.2]		71
[2010/11/21 v1.3]		71
[2011/03/25 v1.4]		72
[2011/04/21 v1.5]		72
[2011/10/01 v1.6]		72
[2011/11/22 v1.7]		72
[2011/11/29 v1.8]		72
[2011/12/21 v1.9]		72
[2012/04/26 v1.10]		72
[2016/05/12 v1.11]		72
[2016/05/16 v1.12]		73

8	Index	74
----------	--------------	-----------

1 Documentation

1.1 Logo macros

`\hologo {\langle name\rangle}`

Macro `\hologo` sets the logo with name $\langle name \rangle$. The following table shows the supported names.

name	variant	logo	since
(La)TeX		(L)TeX	2011/10/01
AmSLaTeX		$\mathcal{A}\mathcal{M}\mathcal{S}$ -LATEX	2010/04/16
AmSTeX		$\mathcal{A}\mathcal{M}\mathcal{S}$ -TeX	2010/04/16
biber		biber	2011/10/01
BibTeX		BIBTeX	2011/10/01
BibTeX	sf	BIBTeX	2011/10/01
BibTeX	sc	BIBTeX	2011/10/01
BibTeX8		BIBTeX8	2011/11/22
ConTeXt		ConTeXt	2011/03/25
ConTeXt	narrow	ConTeXt	2011/03/25
ConTeXt	simple	ConTeXt	2011/03/25
emTeX		emTeX	2010/04/26
eTeX		ε -TeX	2010/04/08
ExTeX		ε_X TeX	2011/10/01
HanTheThanh		Hàn Thé Thành	2011/11/29
iniTeX		iniTeX	2011/10/01
KOMAScript		KOMA-Script	2011/10/01
La		LA	2010/05/08
LaTeX		LATEX	2010/04/08
LaTeX2e		LATEX 2 ε	2010/04/08
LaTeX3		LATEX3	2010/04/24
LaTeXe		LATEX 2 ε	2010/04/08
LaTeXML		LATEXML	2011/11/22
LaTeXTeX		(L)TeX	2011/10/01
LuaLaTeX		LuaLATEX	2010/04/08

name	variant	logo	since
LuaTeX		\texttt{LuaT}\texttt{E}\texttt{X}	2010/04/08
LyX		\texttt{Ly}\texttt{X}	2011/10/01
METAFONT		\texttt{META}\texttt{F}\texttt{O}\texttt{N}\texttt{T}	2011/10/01
MetaFun		\texttt{Meta}\texttt{F}\texttt{u}\texttt{n}	2011/10/01
METAPOST		\texttt{META}\texttt{P}\texttt{O}\texttt{S}\texttt{T}	2011/10/01
MetaPost		\texttt{Meta}\texttt{P}\texttt{o}\texttt{s}\texttt{t}	2011/10/01
MiKTeX		\texttt{MiK}\texttt{T}\texttt{E}\texttt{X}	2011/10/01
NTS		\texttt{N}\texttt{\tilde{T}}\texttt{S}	2011/10/01
OzMF		\texttt{Oz}\texttt{M}\texttt{F}	2011/10/01
OzMP		\texttt{Oz}\texttt{M}\texttt{P}	2011/10/01
OzTeX		\texttt{Oz}\texttt{T}\texttt{E}\texttt{X}	2011/10/01
OzTtH		\texttt{Oz}\texttt{Tt}\texttt{H}	2011/10/01
PCTeX		\texttt{PCT}\texttt{E}\texttt{X}	2011/10/01
pdfTeX		\texttt{pdf}\texttt{T}\texttt{E}\texttt{X}	2011/10/01
pdfLaTeX		\texttt{pdfL}\texttt{A}\texttt{T}\texttt{E}\texttt{X}	2011/10/01
PiC		\texttt{Pi}\texttt{C}	2011/10/01
PiCTeX		\texttt{Pi}\texttt{C}\texttt{T}\texttt{E}\texttt{X}	2011/10/01
plainTeX		\texttt{plain }\texttt{T}\texttt{E}\texttt{X}	2010/04/08
plainTeX	space	\texttt{plain }\texttt{T}\texttt{E}\texttt{X}	2010/04/16
plainTeX	hyphen	\texttt{plain-}\texttt{T}\texttt{E}\texttt{X}	2010/04/16
plainTeX	runtogther	\texttt{plainT}\texttt{E}\texttt{X}	2010/04/16
SageTeX		\texttt{SageT}\texttt{E}\texttt{X}	2011/11/22
SLiTeX		\texttt{SLiT}\texttt{E}\texttt{X}	2011/10/01
SLiTeX	lift	\texttt{SLiT}\texttt{E}\texttt{X}	2011/10/01
SLiTeX	narrow	\texttt{SLiT}\texttt{E}\texttt{X}	2011/10/01
SLiTeX	simple	\texttt{SLiT}\texttt{E}\texttt{X}	2011/10/01
SLiTeX		\texttt{SLiT}\texttt{E}\texttt{X}	2011/10/01
SLiTeX	narrow	\texttt{SLiT}\texttt{E}\texttt{X}	2011/10/01
SLiTeX	simple	\texttt{SLiT}\texttt{E}\texttt{X}	2011/10/01
SLiTeX	lift	\texttt{SLiT}\texttt{E}\texttt{X}	2011/10/01
teTeX		\texttt{teT}\texttt{E}\texttt{X}	2011/10/01
TeX		\texttt{T}\texttt{E}\texttt{X}	2010/04/08
TeX4ht		\texttt{T}\texttt{E}\texttt{X}4\texttt{ht}	2011/11/22
TTH		\texttt{T}\texttt{T}\texttt{H}	2011/11/22
virTeX		\texttt{virT}\texttt{E}\texttt{X}	2011/10/01
VTex		\texttt{V}\texttt{T}\texttt{E}\texttt{X}	2010/04/24
Xe		\texttt{X}\texttt{\tilde{E}}	2010/04/08
XeLaTeX		\texttt{X}\texttt{\tilde{E}}\texttt{L}\texttt{A}\texttt{T}\texttt{E}\texttt{X}	2010/04/08
XeTeX		\texttt{X}\texttt{\tilde{E}}\texttt{T}\texttt{E}\texttt{X}	2010/04/08

\texttt{\textbackslash Hologo \{*name*\}}

Macro \texttt{\textbackslash Hologo} starts the logo *name* with an uppercase letter. As an exception small greek letters are not converted to uppercase. Examples, see ε -TeX and ε_X -TeX.

1.2 Setup macros

The package does not support package options, but the following setup macros can be used to set options.

```
\hologoSetup {\langle key value list\rangle}
```

Macro `\hologoSetup` sets global options.

```
\hologoLogoSetup {\langle logo\rangle} {\langle key value list\rangle}
```

Some options can also be used to configure a logo. These settings take precedence over global option settings.

1.3 Options

There are boolean and string options:

Boolean option: It takes `true` or `false` as value. If the value is omitted, then `true` is used.

String option: A value must be given as string. (But the string might be empty.)

The following options can be used both in `\hologoSetup` and `\hologoLogoSetup`:

break: enables or disables line breaks inside the logo. This setting is refined by options `hyphenbreak`, `spacebreak` or `discretionarybreak`. Default is `false`.

hyphenbreak: enables or disables the line break right after the hyphen character.

spacebreak: enables or disables line breaks at space characters.

discretionarybreak: enables or disables line breaks at hyphenation points (inserted by `\-`).

Macro `\hologoLogoSetup` also knows:

variant: This is a string option. It specifies a variant of a logo that must exist. An empty string selects the package default variant.

Example:

```
\hologoSetup{break=false}
\hologoLogoSetup{plainTeX}{variant=hyphen,hyphenbreak}
Then "plain-TEX" contains one break point after the hyphen.
```

1.4 Driver options

Sometimes graphical operations are needed to construct some glyphs (e.g. X_ET_EX). If package `graphics` or package `pgf` are found, then the macros are taken from there. Otherwise the packge defines its own operations and therefore needs the driver information. Many drivers are detected automatically (pdfT_EX/LuaT_EX in PDF mode, X_ET_EX, V_TE_X). These have precedence over a driver option. The driver can be given as package option or using `\hologoDriverSetup`. The following list contains the recognized driver options:

- `pdftex`, `lualatex`
- `dvipdfm`, `dvipdfmx`
- `dvips`, `dvipsone`, `xdvi`
- `xetex`

- **vtx**

The left driver of a line is the driver name that is used internally. The following names are aliases for drivers that use the same method. Therefore the entry in the `.log` file for the used driver prints the internally used driver name.

driverfallback: This option expects a driver that is used, if the driver could not be detected automatically.

`\hologoDriverSetup {<driver option>}`

The driver can also be configured after package loading using `\hologoDriverSetup`, also the way for plain \TeX to setup the driver.

1.5 Font setup

Some logos require a special font, but should also be usable by plain \TeX . Therefore the package provides some ways to influence the font settings. The options below take font settings as values. Both font commands such as `\sffamily` and macros that take one argument like `\textsf` can be used.

`\hologoFontSetup {<key value list>}`

Macro `\hologoFontSetup` sets the fonts for all logos. Supported keys:

general: This font is used for all logos. The default is empty. That means no special font is used.

bibsf: This font is used for $\text{BIB}\text{\TeX}$ with variant `sf`.

rm: This font is a serif font. It is used for $\varepsilon_X\text{\TeX}$.

sc: This font specifies a small caps font. It is used for $\text{BIB}\text{\TeX}$ with variant `sc`.

sf: This font specifies a sans serif font. The default is `\sffamily`, then `\sf` is tried. Otherwise a warning is given. It is used by KOMA-Script.

sy: This is the font for math symbols (e.g. `cmsy`). It is used by $\mathcal{AM}\mathcal{S}$, $\mathcal{N}\mathcal{T}\mathcal{S}$, $\varepsilon_X\text{\TeX}$.

logo: METAFONT and METAPOST are using that font. In \LaTeX `\logofamily` is used and the definitions of package `mflogo` are used if the package is not loaded. Otherwise the `\tenlogo` is used and defined if it does not already exists.

`\hologoLogoFontSetup {<logo>} {<key value list>}`

Fonts can also be set for a logo or logo component separately, see the following list. The keys are the same as for `\hologoFontSetup`.

<code><logo></code>	keys	result
BibTeX	bibsf	$\text{BIB}\text{\TeX}$
BibTeX	sc	$\text{BIB}\text{\TeX}$
ExTeX	rm	$\varepsilon_X\text{\TeX}$
SliTeX	rm	$\text{Sli}\text{\TeX}$

$\langle logo \rangle$	keys	result
AmS	sy	$\mathcal{A}\mathcal{M}\mathcal{S}$
ExTeX	sy	$\varepsilon_X\mathbf{T}\mathbf{E}\mathbf{X}$
NTS	sy	$\mathcal{N}\mathcal{T}\mathcal{S}$
KOMAScript	sf	KOMA-Script
METAFONT	logo	METAFONT
METAPOST	logo	METAPOST
SLiTeX	sc	SLiTeX

1.5.1 Font order

For all logos the font general is applied first. Example:

```
\holoFontSetup{general=\color{red}}
```

will print red logos. Then if the font uses a special font sf, for example, the font is applied that is setup by `\holoLogoFontSetup`. If this font is not setup, then the common font setup by `\holoFontSetup` is used. Otherwise a warning is given, that there is no font configured.

1.6 Additional user macros

Usually a variant of a logo is configured by using `\holoLogoSetup`, because it is bad style to mix different variants of the same logo in the same text. There the following macros are a convenience for testing.

```
\holoVariant {\langle name \rangle} {\langle variant \rangle}
\HoloVariant {\langle name \rangle} {\langle variant \rangle}
```

Logo $\langle name \rangle$ is set using $\langle variant \rangle$ that specifies explicitly which variant of the macro is used. If the argument is empty, then the default form of the logo is used (configurable by `\holoLogoSetup`).

`\HoloVariant` is used if the logo is set in a context that needs an uppercase first letter (beginning of a sentence, ...).

```
\holoList
\holoEntry {\langle logo \rangle} {\langle variant \rangle} {\langle since \rangle}
```

Macro `\holoList` contains all logos that are provided by the package including variants. The list consists of calls of `\holoEntry` with three arguments starting with the logo name $\langle logo \rangle$ and its variant $\langle variant \rangle$. An empty variant means the current default. Argument $\langle since \rangle$ specifies with version of the package `holo` is needed to get the logo. If the logo is fixed, then the date gets updated. Therefore the date $\langle since \rangle$ is not exactly the date of the first introduction, but rather the date of the latest fix.

Before `\holoList` can be used, macro `\holoEntry` needs a definition. The example file in section 1.8 shows applications of `\holoList`.

1.7 Supported contexts

Macros `\holo` and friends support special contexts:

- L^AT_EX's protection mechanism.

- Bookmarks of package `hyperref`.
- Package `tex4ht`.
- The macros can be used inside `\csname` constructs, if `\ifin csname` is available (pdfTeX, XeTeX, LuaTeX).

1.8 Example

The following example prints the logos in different fonts.

```

1  /*example*/
2 %<<verbatim
3 \NeedsTeXFormat{LaTeX2e}
4 \documentclass[a4paper]{article}
5 \usepackage[
6   hmargin=20mm,
7   vmargin=20mm,
8 ]{geometry}
9 \pagestyle{empty}
10 \usepackage[hologo][2016/05/16]
11 \usepackage{longtable}
12 \usepackage{array}
13 \setlength{\extrarowheight}{2pt}
14 \usepackage[T1]{fontenc}
15 \usepackage{lmodern}
16 \usepackage{pdflscape}
17 \usepackage[
18   pdfencoding=auto,
19 ]{hyperref}
20 \hypersetup{
21   pdfauthor={Heiko Oberdiek},
22   pdftitle={Example for package ‘hologo’},
23   pdfsubject={Logos with fonts lmr, lmss, qtm, qpl, qhv},
24 }
25 \usepackage{bookmark}
26
27 % Print the logo list on the console
28
29 \begingroup
30   \typeout{%%
31   \typeout{*** Begin of logo list ***}%
32   \newcommand*{\hologoEntry}[3]{%
33     \typeout{#1 \ifx\#2\else(\#2)\fi[#3]}%
34   }%
35   \hologoList
36   \typeout{*** End of logo list ***}%
37   \typeout{%%
38 \endgroup
39
40 \begin{document}
41 \begin{landscape}
42
43 \section{Example file for package ‘hologo’}
44
45 % Table for font names
46
47 \begin{longtable}{>{\bfseries}l}
48   \textbf{font} & \textbf{Font name}\\

```

```

49   \hline
50   lmr & Latin Modern Roman\\
51   lmss & Latin Modern Sans\\
52   qtm & \TeX\ Gyre Termes\\
53   qhv & \TeX\ Gyre Heros\\
54   qpl & \TeX\ Gyre Pagella\\
55 \end{longtable}
56
57 % Logo list with logos in different fonts
58
59 \begingroup
60 \newcommand*{\SetVariant}[2]{%
61   \ifx\#2\%
62   \else
63     \hologoLogoSetup{\#1}{variant=\#2}%
64   \fi
65 }%
66 \newcommand*{\hologoEntry}[3]{%
67   \SetVariant{\#1}{\#2}%
68   \raisebox{1em}[0pt][0pt]{\hypertarget{\#1@\#2}{}}%
69   \bookmark[%
70     dest=\#1@\#2,%
71   ]{%
72     #1\ifx\#2\%\else\space(\#2)\fi: \Hologo{\#1}, \hologo{\#1} %
73     [Unicode]%
74   }%
75   \hypersetup{unicode=false}%
76   \bookmark[%
77     dest=\#1@\#2,%
78   ]{%
79     #1\ifx\#2\%\else\space(\#2)\fi: \Hologo{\#1}, \hologo{\#1} %
80     [PDFDocEncoding]%
81   }%
82   \texttt{\#1}%
83   &%
84   \texttt{\#2}%
85   &%
86   \Hologo{\#1}%
87   &%
88   \SetVariant{\#1}{\#2}%
89   \hologo{\#1}%
90   &%
91   \SetVariant{\#1}{\#2}%
92   \fontfamily{qtm}\selectfont
93   \hologo{\#1}%
94   &%
95   \SetVariant{\#1}{\#2}%
96   \fontfamily{qpl}\selectfont
97   \hologo{\#1}%
98   &%
99   \SetVariant{\#1}{\#2}%
100  \textsf{\hologo{\#1}}%
101  &%
102  \SetVariant{\#1}{\#2}%
103  \fontfamily{qhv}\selectfont
104  \hologo{\#1}%
105  \tabularnewline
106 }%

```

```

107 \begin{longtable}{lllllllll}%
108   \textbf{\textit{\textit{logo}}} & \textbf{\textit{\textit{variant}}} &
109   \texttt{\string\Hologo} &
110   \textbf{\textit{lmr}} & \textbf{\textit{qtm}} & \textbf{\textit{qpl}} &
111   \textbf{\textit{lmss}} & \textbf{\textit{qhv}}%
112   \tabularnewline
113   \hline
114   \endhead
115   \hologoList
116 \end{longtable}%
117 \endgroup
118
119 \end{landscape}
120 \end{document}
121 %verbatim
122 \example

```

2 Implementation

123 (*package)

Reload check, especially if the package is not used with L^AT_EX.

```

124 \begingroup\catcode61\catcode48\catcode32=10\relax%
125   \catcode13=5 % ^M
126   \endlinechar=13 %
127   \catcode35=6 % #
128   \catcode39=12 % ,
129   \catcode44=12 % ,
130   \catcode45=12 % -
131   \catcode46=12 % .
132   \catcode58=12 % :
133   \catcode64=11 % @
134   \catcode123=1 % {
135   \catcode125=2 % }
136 \expandafter\let\expandafter\x\csname ver@hologo.sty\endcsname
137 \ifx\x\relax % plain-TeX, first loading
138 \else
139   \def\empty{}%
140   \ifx\x\empty % LaTeX, first loading,
141     % variable is initialized, but \ProvidesPackage not yet seen
142   \else
143     \expandafter\ifx\x\csname PackageInfo\endcsname\relax
144       \def\x#1#2{%
145         \immediate\write-1{Package #1 Info: #2.}%
146       }%
147     \else
148       \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
149     \fi
150     \x{hologo}{The package is already loaded}%
151     \aftergroup\endinput
152   \fi
153 \fi
154 \endgroup%

```

Package identification:

```

155 \begingroup\catcode61\catcode48\catcode32=10\relax%
156   \catcode13=5 % ^M
157   \endlinechar=13 %
158   \catcode35=6 % #

```

```

159  \catcode39=12 %
160  \catcode40=12 %
161  \catcode41=12 %
162  \catcode44=12 %
163  \catcode45=12 %
164  \catcode46=12 %
165  \catcode47=12 %
166  \catcode58=12 %
167  \catcode64=11 %
168  \catcode91=12 %
169  \catcode93=12 %
170  \catcode123=1 %
171  \catcode125=2 %
172  \expandafter\ifx\csname ProvidesPackage\endcsname\relax
173  \def\x#1#2#3[#4]{\endgroup
174  \immediate\write-1{Package: #3 #4}%
175  \xdef#1[#4]%
176  }%
177  \else
178  \def\x#1#2[#3]{\endgroup
179  #2[{#3}]%
180  \ifx#1\@undefined
181  \xdef#1{#3}%
182  \fi
183  \ifx#1\relax
184  \xdef#1{#3}%
185  \fi
186  }%
187  \fi
188 \expandafter\x\csname ver@hologo.sty\endcsname
189 \ProvidesPackage{hologo}%
190  [2016/05/16 v1.12 A logo collection with bookmark support (HO)]%
191 \begingroup\catcode61\catcode48\catcode32=10\relax%
192  \catcode13=5 % ^M
193  \endlinechar=13 %
194  \catcode123=1 %
195  \catcode125=2 %
196  \catcode64=11 %
197  \def\x{\endgroup
198  \expandafter\edef\csname HOLOGO@AtEnd\endcsname{%
199  \endlinechar=\the\endlinechar\relax
200  \catcode13=\the\catcode13\relax
201  \catcode32=\the\catcode32\relax
202  \catcode35=\the\catcode35\relax
203  \catcode61=\the\catcode61\relax
204  \catcode64=\the\catcode64\relax
205  \catcode123=\the\catcode123\relax
206  \catcode125=\the\catcode125\relax
207  }%
208  }%
209 \x\catcode61\catcode48\catcode32=10\relax%
210 \catcode13=5 % ^M
211 \endlinechar=13 %
212 \catcode35=6 %
213 \catcode64=11 %
214 \catcode123=1 %
215 \catcode125=2 %
216 \def\TMP@EnsureCode#1#2{%

```

```

217 \edef\HOLOGO@AtEnd{%
218   \HOLOGO@AtEnd
219   \catcode#1=\the\catcode#1\relax
220 }%
221 \catcode#1=#2\relax
222 }
223 \TMP@EnsureCode{10}{12}%
224 \TMP@EnsureCode{33}{12}%
225 \TMP@EnsureCode{34}{12}%
226 \TMP@EnsureCode{36}{3}%
227 \TMP@EnsureCode{38}{4}%
228 \TMP@EnsureCode{39}{12}%
229 \TMP@EnsureCode{40}{12}%
230 \TMP@EnsureCode{41}{12}%
231 \TMP@EnsureCode{42}{12}%
232 \TMP@EnsureCode{43}{12}%
233 \TMP@EnsureCode{44}{12}%
234 \TMP@EnsureCode{45}{12}%
235 \TMP@EnsureCode{46}{12}%
236 \TMP@EnsureCode{47}{12}%
237 \TMP@EnsureCode{58}{12}%
238 \TMP@EnsureCode{59}{12}%
239 \TMP@EnsureCode{60}{12}%
240 \TMP@EnsureCode{62}{12}%
241 \TMP@EnsureCode{63}{12}%
242 \TMP@EnsureCode{91}{12}%
243 \TMP@EnsureCode{93}{12}%
244 \TMP@EnsureCode{94}{7}%
245 \TMP@EnsureCode{95}{8}%
246 \TMP@EnsureCode{96}{12}%
247 \TMP@EnsureCode{124}{12}%
248 \edef\HOLOGO@AtEnd{%
249   \HOLOGO@AtEnd
250   \escapechar\the\escapechar\relax
251   \noexpand\endinput
252 }
253 \escapechar=92 %

```

2.1 Logo list

```

\hologoList
254 \def\hologoList{%
255   \hologoEntry{(La)TeX}{}{2011/10/01}%
256   \hologoEntry{AmSLaTeX}{}{2010/04/16}%
257   \hologoEntry{AmSTeX}{}{2010/04/16}%
258   \hologoEntry{biber}{}{2011/10/01}%
259   \hologoEntry{BibTeX}{}{2011/10/01}%
260   \hologoEntry{BibTeX}{sf}{2011/10/01}%
261   \hologoEntry{BibTeX}{sc}{2011/10/01}%
262   \hologoEntry{BibTeX8}{}{2011/11/22}%
263   \hologoEntry{ConTeXt}{}{2011/03/25}%
264   \hologoEntry{ConTeXt}{narrow}{2011/03/25}%
265   \hologoEntry{ConTeXt}{simple}{2011/03/25}%
266   \hologoEntry{emTeX}{}{2010/04/26}%
267   \hologoEntry{eTeX}{}{2010/04/08}%
268   \hologoEntry{ExTeX}{}{2011/10/01}%
269   \hologoEntry{HanTheThanh}{}{2011/11/29}%
270   \hologoEntry{iniTeX}{}{2011/10/01}%
271   \hologoEntry{KOMAScript}{}{2011/10/01}%

```

```

272 \hologoEntry{La}{}{2010/05/08}%
273 \hologoEntry{LaTeX}{}{2010/04/08}%
274 \hologoEntry{LaTeXe}{}{2010/04/08}%
275 \hologoEntry{LaTeX3}{}{2010/04/24}%
276 \hologoEntry{LaTeXe}{}{2010/04/08}%
277 \hologoEntry{LaTeXML}{}{2011/11/22}%
278 \hologoEntry{LaTeXTeX}{}{2011/10/01}%
279 \hologoEntry{LuaLaTeX}{}{2010/04/08}%
280 \hologoEntry{LuaTeX}{}{2010/04/08}%
281 \hologoEntry{LyX}{}{2011/10/01}%
282 \hologoEntry{METAFONT}{}{2011/10/01}%
283 \hologoEntry{MetaFun}{}{2011/10/01}%
284 \hologoEntry{METAPOST}{}{2011/10/01}%
285 \hologoEntry{MetaPost}{}{2011/10/01}%
286 \hologoEntry{MiKTeX}{}{2011/10/01}%
287 \hologoEntry{NTS}{}{2011/10/01}%
288 \hologoEntry{OzMF}{}{2011/10/01}%
289 \hologoEntry{OzMP}{}{2011/10/01}%
290 \hologoEntry{OzTeX}{}{2011/10/01}%
291 \hologoEntry{OzTtH}{}{2011/10/01}%
292 \hologoEntry{PCTeX}{}{2011/10/01}%
293 \hologoEntry{pdfTeX}{}{2011/10/01}%
294 \hologoEntry{pdfLaTeX}{}{2011/10/01}%
295 \hologoEntry{Pic}{}{2011/10/01}%
296 \hologoEntry{PiCTeX}{}{2011/10/01}%
297 \hologoEntry{plainTeX}{}{2010/04/08}%
298 \hologoEntry{plainTeX}{space}{2010/04/16}%
299 \hologoEntry{plainTeX}{hyphen}{2010/04/16}%
300 \hologoEntry{plainTeX}{runtogether}{2010/04/16}%
301 \hologoEntry{SageTeX}{}{2011/11/22}%
302 \hologoEntry{SLiTeX}{}{2011/10/01}%
303 \hologoEntry{SLiTeX}{lift}{2011/10/01}%
304 \hologoEntry{SLiTeX}{narrow}{2011/10/01}%
305 \hologoEntry{SLiTeX}{simple}{2011/10/01}%
306 \hologoEntry{SLiTeX}{}{2011/10/01}%
307 \hologoEntry{SLiTeX}{narrow}{2011/10/01}%
308 \hologoEntry{SLiTeX}{simple}{2011/10/01}%
309 \hologoEntry{SLiTeX}{lift}{2011/10/01}%
310 \hologoEntry{teTeX}{}{2011/10/01}%
311 \hologoEntry{TeX}{}{2010/04/08}%
312 \hologoEntry{TeX4ht}{}{2011/11/22}%
313 \hologoEntry{TTH}{}{2011/11/22}%
314 \hologoEntry{virTeX}{}{2011/10/01}%
315 \hologoEntry{VTeX}{}{2010/04/24}%
316 \hologoEntry{Xe}{}{2010/04/08}%
317 \hologoEntry{XeLaTeX}{}{2010/04/08}%
318 \hologoEntry{XeTeX}{}{2010/04/08}%
319 }

```

2.2 Load resources

```

320 \begingroup\expandafter\expandafter\expandafter\endgroup
321 \expandafter\ifx\csname RequirePackage\endcsname\relax
322   \def\TMP@RequirePackage#1[#2]{%
323     \begingroup\expandafter\expandafter\expandafter\endgroup
324     \expandafter\ifx\csname ver@#1.sty\endcsname\relax
325       \input #1.sty\relax
326     \fi

```

```

327  }%
328  \TMP@RequirePackage{ltxcmds}[2011/02/04]%
329  \TMP@RequirePackage{infwarerr}[2010/04/08]%
330  \TMP@RequirePackage{kvsetkeys}[2010/03/01]%
331  \TMP@RequirePackage{kvdefinekeys}[2010/03/01]%
332  \TMP@RequirePackage{pdftexcmds}[2010/04/01]%
333  \TMP@RequirePackage{ifpdf}[2010/01/28]%
334  \TMP@RequirePackage{ifluatex}[2010/03/01]%
335  \ltx@ifundefined{newif}{%
336      \expandafter\let\csname newif\endcsname\ltx@newif
337  }{%
338  \TMP@RequirePackage{ifxetex}[2009/01/23]%
339  \TMP@RequirePackage{ifvtex}[2010/03/01]%
340 \else
341  \RequirePackage{ltxcmds}[2011/02/04]%
342  \RequirePackage{infwarerr}[2010/04/08]%
343  \RequirePackage{kvsetkeys}[2010/03/01]%
344  \RequirePackage{kvdefinekeys}[2010/03/01]%
345  \RequirePackage{pdftexcmds}[2010/04/01]%
346  \RequirePackage{ifpdf}[2010/01/28]%
347  \RequirePackage{ifluatex}[2010/03/01]%
348  \RequirePackage{ifxetex}[2009/01/23]%
349  \RequirePackage{ifvtex}[2010/03/01]%
350 \fi
\HOLOGO@ifdefined
351 \def\HOLOGO@ifexists#1{%
352  \ifx\@undefined#1%
353      \expandafter\ltx@secondoftwo
354  \else
355      \ifx\relax#1%
356          \expandafter\ltx@secondoftwo
357      \else
358          \expandafter\expandafter\expandafter\ltx@firstoftwo
359      \fi
360  \fi
361 }

```

2.3 Setup macros

```

\hologoSetup
362 \def\hologoSetup{%
363  \let\HOLOGO@name\relax
364  \HOLOGO@Setup
365 }

\hologoLogoSetup
366 \def\hologoLogoSetup#1{%
367  \edef\HOLOGO@name{\#1}%
368  \ltx@ifundefined{HoLogo@\HOLOGO@name}{%
369      \@PackageError{hologo}{%
370          Unknown logo '\HOLOGO@name'%
371      }%
372      \ltx@gobble
373  }{%
374      \HOLOGO@Setup
375  }%
376 }

```

```

\HOLOGO@Setup
377 \def\HOLOGO@Setup{%
378   \kvsetkeys{HoLogo}{%
379 }

```

2.4 Options

```

\HOLOGO@DeclareBoolOption
380 \def\HOLOGO@DeclareBoolOption#1{%
381   \expandafter\chardef\csname HOLOGOOPT@#1\endcsname\ltx@zero
382   \kv@define@key{HoLogo}{#1}[true]{%
383     \def\HOLOGO@temp{##1}%
384     \ifx\HOLOGO@temp\HOLOGO@true
385       \ifx\HOLOGO@name\relax
386         \expandafter\chardef\csname HOLOGOOPT@#1\endcsname=\ltx@one
387       \else
388         \expandafter\chardef\csname
389           HoLogoOpt@#1@\HOLOGO@name\endcsname\ltx@one
390       \fi
391       \HOLOGO@SetBreakAll{#1}%
392     \else
393       \ifx\HOLOGO@temp\HOLOGO@false
394         \ifx\HOLOGO@name\relax
395           \expandafter\chardef\csname HOLOGOOPT@#1\endcsname=\ltx@zero
396         \else
397           \expandafter\chardef\csname
398             HoLogoOpt@#1@\HOLOGO@name\endcsname\ltx@zero
399         \fi
400         \HOLOGO@SetBreakAll{#1}%
401       \else
402         \@PackageError{hologo}{%
403           Unknown value ‘#1’ for boolean option ‘#1’. \MessageBreak
404           Known values are ‘true’ and ‘false’%
405         }@\ehc
406       \fi
407     \fi
408   }%
409 }

```

```

\HOLOGO@SetBreakAll
410 \def\HOLOGO@SetBreakAll#1{%
411   \def\HOLOGO@temp{#1}%
412   \ifx\HOLOGO@temp\HOLOGO@break
413     \ifx\HOLOGO@name\relax
414       \chardef\HOLOGOOPT@hyphenbreak=\HOLOGOOPT@break
415       \chardef\HOLOGOOPT@spacebreak=\HOLOGOOPT@break
416       \chardef\HOLOGOOPT@discretionarybreak=\HOLOGOOPT@break
417     \else
418       \expandafter\chardef
419         \csname HoLogoOpt@hyphenbreak@\HOLOGO@name\endcsname=%
420         \csname HoLogoOpt@break@\HOLOGO@name\endcsname
421       \expandafter\chardef
422         \csname HoLogoOpt@spacebreak@\HOLOGO@name\endcsname=%
423         \csname HoLogoOpt@break@\HOLOGO@name\endcsname
424       \expandafter\chardef
425         \csname HoLogoOpt@discretionarybreak@\HOLOGO@name
426           \endcsname=%

```

```

427           \csname HoLogoOpt@break@\HOLOGO@name\endcsname
428       \fi
429   \fi
430 }

\HOLOGO@true
431 \def\HOLOGO@true{true}

\HOLOGO@false
432 \def\HOLOGO@false{false}

\HOLOGO@break
433 \def\HOLOGO@break{break}

434 \HOLOGO@DeclareBoolOption{break}
435 \HOLOGO@DeclareBoolOption{hyphenbreak}
436 \HOLOGO@DeclareBoolOption{spacebreak}
437 \HOLOGO@DeclareBoolOption{discretionarybreak}

438 \kv@define@key{HoLogo}{variant}{%
439   \ifx\HOLOGO@name\relax
440     \@PackageError{hologo}{%
441       Option ‘variant’ is not available in \string\hologoSetup,%
442       \MessageBreak
443       Use \string\hologoLogoSetup\space instead%
444     }\@ehc
445   \else
446     \edef\HOLOGO@temp{\#1}%
447     \ifx\HOLOGO@temp\ltx@empty
448       \expandafter
449       \let\csname HoLogoOpt@variant@\HOLOGO@name\endcsname\@undefined
450     \else
451       \ltx@ifUndefined{HoLogo@\HOLOGO@name @\HOLOGO@temp}{%
452         \@PackageError{hologo}{%
453           Unknown variant ‘\HOLOGO@temp’ of logo ‘\HOLOGO@name’%
454         }\@ehc
455       }%
456       \expandafter
457       \let\csname HoLogoOpt@variant@\HOLOGO@name\endcsname
458         \HOLOGO@temp
459       }%
460     \fi
461   \fi
462 }

\HOLOGO@Variant
463 \def\HOLOGO@Variant#1{%
464   #1%
465   \ltx@ifundefined{HoLogoOpt@variant@#1}{%
466     }%
467     @\csname HoLogoOpt@variant@#1\endcsname
468   }%
469 }

\HOLOGO@space
470 \def\HOLOGO@space{%

```

2.5 Break/no-break support

```

471 \ltx@ifundefined{HoLogoOpt@spacebreak@\HOLOGO@name}{%
472   \ltx@ifundefined{HoLogoOpt@break@\HOLOGO@name}{%
473     \chardef\HOLOGO@temp=\HOLOGOPT@spacebreak
474   }{%
475     \chardef\HOLOGO@temp=%
476     \csname HoLogoOpt@break@\HOLOGO@name\endcsname
477   }%
478 }{%
479   \chardef\HOLOGO@temp=%
480   \csname HoLogoOpt@spacebreak@\HOLOGO@name\endcsname
481 }%
482 \ifcase\HOLOGO@temp
483   \penalty10000 %
484 \fi
485 \ltx@space
486 }

\HOLOGO@hyphen
487 \def\HOLOGO@hyphen{%
488   \ltx@ifundefined{HoLogoOpt@hyphenbreak@\HOLOGO@name}{%
489     \ltx@ifundefined{HoLogoOpt@break@\HOLOGO@name}{%
490       \chardef\HOLOGO@temp=\HOLOGOPT@hyphenbreak
491     }{%
492       \chardef\HOLOGO@temp=%
493       \csname HoLogoOpt@break@\HOLOGO@name\endcsname
494     }%
495   }{%
496     \chardef\HOLOGO@temp=%
497     \csname HoLogoOpt@hyphenbreak@\HOLOGO@name\endcsname
498   }%
499 \ifcase\HOLOGO@temp
500   \ltx@mbox{-}%
501 \else
502   -%
503 \fi
504 }

\HOLOGO@discretionary
505 \def\HOLOGO@discretionary{%
506   \ltx@ifundefined{HoLogoOpt@discretionarybreak@\HOLOGO@name}{%
507     \ltx@ifundefined{HoLogoOpt@break@\HOLOGO@name}{%
508       \chardef\HOLOGO@temp=\HOLOGOPT@discretionarybreak
509     }{%
510       \chardef\HOLOGO@temp=%
511       \csname HoLogoOpt@break@\HOLOGO@name\endcsname
512     }%
513   }{%
514     \chardef\HOLOGO@temp=%
515     \csname HoLogoOpt@discretionarybreak@\HOLOGO@name\endcsname
516   }%
517 \ifcase\HOLOGO@temp
518 \else
519   -%
520 \fi
521 }

\HOLOGO@mbox
522 \def\HOLOGO@mbox#1{%

```

```

523  \ltx@ifundefined{HoLogoOpt@break@\HOLOGO@name}{%
524    \chardef\HOLOGO@temp=\HOLOGOPT@hyphenbreak
525  }{%
526    \chardef\HOLOGO@temp=%
527    \csname HoLogoOpt@break@\HOLOGO@name\endcsname
528  }%
529 \ifcase\HOLOGO@temp
530   \ltx@mbox{#1}%
531 \else
532   #1%
533 \fi
534 }

2.6 Font support

#1: logo name
\HoLogoFont@font #2: font short name
#3: text

535 \def\HoLogoFont@font#1#2#3{%
536   \begingroup
537   \ltx@IfUndefined{HoLogoFont@logo@#1.#2}{%
538     \ltx@IfUndefined{HoLogoFont@font@#2}{%
539       \PackageWarning{hologo}{%
540         Missing font '#2' for logo '#1'%
541       }%
542       #3%
543     }{%
544       \csname HoLogoFont@font@#2\endcsname{#3}%
545     }%
546   }{%
547     \csname HoLogoFont@logo@#1.#2\endcsname{#3}%
548   }%
549   \endgroup
550 }

\HoLogoFont@Def
551 \def\HoLogoFont@Def#1{%
552   \expandafter\def\csname HoLogoFont@font@#1\endcsname
553 }

\HoLogoFont@LogoDef
554 \def\HoLogoFont@LogoDef#1#2{%
555   \expandafter\def\csname HoLogoFont@logo@#1.#2\endcsname
556 }

2.6.1 Font defaults

\HoLogoFont@font@general
557 \HoLogoFont@Def{general}{}%

\HoLogoFont@font@rm
558 \ltx@IfUndefined{rmfamily}{%
559   \ltx@IfUndefined{rm}{%
560     }{%
561       \HoLogoFont@Def{rm}{\rm}%
562     }%
563 }%

```

```

564   \HoLogoFont@Def{\rm}{\rmfamily}%
565 }

\HoLogoFont@font@sf

566 \ltx@ifundefined{sffamily}{%
567   \ltx@ifundefined{sf}{%
568     }{%
569       \HoLogoFont@Def{sf}{\sf}%
570     }%
571   }{%
572     \HoLogoFont@Def{sf}{\sffamily}%
573   }

```

\HoLogoFont@font@bibsfs In case of plain TeX the original small caps variant is used as default. In L^AT_EX the definition of package `dtklogos` [2] is used.

```

\DeclareRobustCommand{\BibTeX}{%
  B%
  \kern-.05em%
  \hbox{%
    \$\m@th\$% %% force math size calculations
    \csname S@\f@size\endcsname
    \fontsize\sf@size\z@
    \math@fontsfalse
    \selectfont
    I%
    \kern-.025em%
    B
  }%
  \kern-.08em%
  \-
  \TeX
}

574 \ltx@ifundefined{selectfont}{%
575   \ltx@ifundefined{tencsc}{%
576     \font\tencsc=cmcsc10\relax
577   }{}%
578   \HoLogoFont@Def{bibsfs}{\tencsc}%
579 }{%
580   \HoLogoFont@Def{bibsfs}{%
581     \$\mathsurround=0pt\$%
582     \csname S@\f@size\endcsname
583     \fontsize\sf@size{0pt}%
584     \math@fontsfalse
585     \selectfont
586   }%
587 }

\HoLogoFont@font@sc

588 \ltx@ifundefined{scshape}{%
589   \ltx@ifundefined{tencsc}{%
590     \font\tencsc=cmcsc10\relax
591   }{}%
592   \HoLogoFont@Def{sc}{\tencsc}%
593 }{%
594   \HoLogoFont@Def{sc}{\scshape}%
595 }

```

```

\HoLogoFont@font@sy
596 \ltx@ifundefined{usefont}{%
597   \ltx@ifundefined{tensy}{%
598     }{%
599       \HoLogoFont@Def{sy}{\tensy}%
600     }{%
601   }{%
602     \HoLogoFont@Def{sy}{%
603       \usefont{OMS}{cmsy}{m}{n}%
604     }{%
605   }
}

\HoLogoFont@font@logo
606 \begingroup
607   \def\x{LaTeX2e}%
608 \expandafter\endgroup
609 \ifx\fmtname\x
610   \ltx@ifundefined{logofamily}{%
611     \DeclareRobustCommand{\logofamily}{%
612       \not@math@alphabet{\logofamily}\relax
613       \fontencoding{U}%
614       \fontfamily{logo}%
615       \selectfont
616     }{%
617   }{%
618   }{%
619   }{%
620     \HoLogoFont@Def{logo}{\logofamily}%
621   }{%
622 \else
623   \ltx@ifundefined{tenlogo}{%
624     \font\tenlogo=logo10\relax
625   }{%
626     \HoLogoFont@Def{logo}{\tenlogo}%
627 \fi

```

2.6.2 Font setup

```

\holoFontSetup
628 \def\holoFontSetup{%
629   \let\HOLOGO@name\relax
630   \HOLOGO@FontSetup
631 }

\holoLogoFontSetup
632 \def\holoLogoFontSetup#1{%
633   \edef\HOLOGO@name{#1}%
634   \ltx@ifundefined{HoLogo@\HOLOGO@name}{%
635     \PackageError{holo}{%
636       Unknown logo '\HOLOGO@name'%
637     }{%
638       \ltx@gobble
639     }{%
640     \HOLOGO@FontSetup
641   }{%
642 }

```

```

\HOLOGO@FontSetup
643 \def\HOLOGO@FontSetup{%
644   \kvsetkeys{HoLogoFont}{%
645 }

646 \def\HOLOGO@temp#1{%
647   \kv@define@key{HoLogoFont}{#1}{%
648     \ifx\HOLOGO@name\relax
649       \HoLogoFont@Def{#1}{}{#1}%
650     \else
651       \HoLogoFont@LogoDef\HOLOGO@name{#1}{}{#1}%
652     \fi
653   }%
654 }
655 \HOLOGO@temp{general}
656 \HOLOGO@temp{sf}

```

2.7 Generic logo commands

```

657 \HOLOGO@IfExists\hologo{%
658   \PackageError{hologo}{%
659     \string\hologo\space is already defined.\MessageBreak
660     Package loading is aborted%
661   }\@ehc
662   \HOLOGO@AtEnd
663 }%
664 \HOLOGO@IfExists\hologoRobust{%
665   \PackageError{hologo}{%
666     \string\hologoRobust\space is already defined.\MessageBreak
667     Package loading is aborted%
668   }\@ehc
669   \HOLOGO@AtEnd
670 }%

```

2.7.1 \hologo and friends

```

671 \ifluatex
672   \expandafter\ltx@firstofone
673 \else
674   \expandafter\ltx@gobble
675 \fi
676 {%
677   \ltx@ifUndefined{ifinclsname}{%
678     \ifnum\luatexversion<36 %
679       \expandafter\ltx@gobble
680     \else
681       \expandafter\ltx@firstofone
682     \fi
683   {%
684     \begingroup
685     \ifcase0%
686       \directlua{%
687         if tex.enableprimitives then %
688           tex.enableprimitives('HOLOGO@', {'ifinclsname'})%
689         else %
690           tex.print('1')%
691         end%
692       }%
693       \ifx\HOLOGO@ifinclsname\undefined 1\fi%

```

```

694          \relax
695          \expandafter\ltx@firstofone
696      \else
697          \endgroup
698          \expandafter\ltx@gobble
699      \fi
700      {%
701          \global\let\ifinccsname\HOLOGO@ifinccsname
702      }%
703      \HOLOGO@temp
704  }%
705 }{%
706 }

707 \ltx@IfUndefined{ifinccsname}{%
708     \catcode`$=14 %
709 }{%
710     \catcode`$=9 %
711 }

\hologo
712 \def\hologo#1{%
713 $ \ifinccsname
714 $     \ltx@ifundefined{HoLogoCs@\HOLOGO@Variant{\#1}}{%
715 $         #1%
716 $     }{%
717 $         \csname HoLogoCs@\HOLOGO@Variant{\#1}\endcsname\ltx@firstoftwo
718 $     }%
719 $ \else
720     \HOLOGO@IfExists\texorpdfstring\texorpdfstring\ltx@firstoftwo
721     {%
722         \hologoRobust{\#1}%
723     }{%
724         \ltx@ifundefined{HoLogoBkm@\HOLOGO@Variant{\#1}}{%
725             \ltx@ifundefined{HoLogo@\#1}{?#1?}{\#1}%
726         }{%
727             \csname HoLogoBkm@\HOLOGO@Variant{\#1}\endcsname
728             \ltx@firstoftwo
729         }%
730     }%
731 $ \fi
732 }

\Hologo
733 \def\Hologo#1{%
734 $ \ifinccsname
735 $     \ltx@ifundefined{HoLogoCs@\HOLOGO@Variant{\#1}}{%
736 $         #1%
737 $     }{%
738 $         \csname HoLogoCs@\HOLOGO@Variant{\#1}\endcsname\ltx@secondoftwo
739 $     }%
740 $ \else
741     \HOLOGO@IfExists\texorpdfstring\texorpdfstring\ltx@firstoftwo
742     {%
743         \HologoRobust{\#1}%
744     }{%
745         \ltx@ifundefined{HoLogoBkm@\HOLOGO@Variant{\#1}}{%
746             \ltx@ifundefined{HoLogo@\#1}{?#1?}{\#1}%
747         }{%

```

```

748      \csname HoLogoBkm@\HOLOGO@Variant{\#1}\endcsname
749      \ltx@secondoftwo
750      }%
751      }%
752 $ \fi
753 }

\holoVariant

754 \def\holoVariant#1#2{%
755   \ifx\relax#2\relax
756     \holo{\#1}%
757   \else
758     \ifincsname
759       \ltx@ifundefined{HoLogoCs@#1@#2}{%
760         #1%
761       }{%
762         \csname HoLogoCs@#1@#2\endcsname\ltx@firstoftwo
763       }%
764     \else
765       \HOLOGO@IfExists\texorpdfstring\texorpdfstring\ltx@firstoftwo
766       {%
767         \holoVariantRobust{\#1}{#2}%
768       }{%
769         \ltx@ifundefined{HoLogoBkm@#1@#2}{%
770           \ltx@ifundefined{HoLogo@#1}{?#1?}{#1}%
771         }{%
772           \csname HoLogoBkm@#1@#2\endcsname
773           \ltx@firstoftwo
774         }%
775       }%
776     \fi
777   \fi
778 }

\HoloVariant

779 \def\HoloVariant#1#2{%
780   \ifx\relax#2\relax
781     \Holo{\#1}%
782   \else
783     \ifincsname
784       \ltx@ifundefined{HoLogoCs@#1@#2}{%
785         #1%
786       }{%
787         \csname HoLogoCs@#1@#2\endcsname\ltx@secondoftwo
788       }%
789     \else
790       \HOLOGO@IfExists\texorpdfstring\texorpdfstring\ltx@firstoftwo
791       {%
792         \HoloVariantRobust{\#1}{#2}%
793       }{%
794         \ltx@ifundefined{HoLogoBkm@#1@#2}{%
795           \ltx@ifundefined{HoLogo@#1}{?#1?}{#1}%
796         }{%
797           \csname HoLogoBkm@#1@#2\endcsname
798           \ltx@secondoftwo
799         }%
800       }%
801     \fi

```

```

802   \fi
803 }

804 \catcode`\$=3 %

```

2.7.2 \hologoRobust and friends

```

\hologoRobust
805 \ltx@IfUndefined{protected}{%
806   \ltx@IfUndefined{DeclareRobustCommand}{%
807     \def\hologoRobust#1{%
808   }{%
809     \DeclareRobustCommand*\hologoRobust[1]{%
810   }{%
811 }{%
812   \protected\def\hologoRobust#1{%
813 }{%
814 }{%
815   \edef\HOLOGO@name{\#1}{%
816   \ltx@IfUndefined{HoLogo@\HOLOGO@Variant\HOLOGO@name}{%
817     \@PackageError{hologo}{%
818       Unknown logo '\HOLOGO@name'%
819     }{%
820       ?\HOLOGO@name?%
821     }{%
822     \ltx@IfUndefined{ver@tex4ht.sty}{%
823       \HoLogoFont@font\HOLOGO@name{general}{%
824         \csname HoLogo@\HOLOGO@Variant\HOLOGO@name\endcsname
825         \ltx@firstoftwo
826       }{%
827     }{%
828     \ltx@IfUndefined{HoLogoHtml@\HOLOGO@Variant\HOLOGO@name}{%
829       \HOLOGO@name
830     }{%
831       \csname HoLogoHtml@\HOLOGO@Variant\HOLOGO@name\endcsname
832       \ltx@firstoftwo
833     }{%
834   }{%
835 }{%
836 }

\HologoRobust
837 \ltx@IfUndefined{protected}{%
838   \ltx@IfUndefined{DeclareRobustCommand}{%
839     \def\HologoRobust#1{%
840   }{%
841     \DeclareRobustCommand*\HologoRobust[1]{%
842   }{%
843 }{%
844   \protected\def\HologoRobust#1{%
845 }{%
846 }{%
847   \edef\HOLOGO@name{\#1}{%
848   \ltx@IfUndefined{HoLogo@\HOLOGO@Variant\HOLOGO@name}{%
849     \@PackageError{hologo}{%
850       Unknown logo '\HOLOGO@name'%
851     }{%
852       ?\HOLOGO@name?%

```

```

853  }{%
854    \ltx@ifundefined{ver@tex4ht.sty}{%
855      \HoLogoFont@font\HOLOGO@name{general}{%
856        \csname HoLogo@\HOLOGO@Variant\HOLOGO@name\endcsname
857        \ltx@secondoftwo
858      }%
859    }{%
860      \ltx@ifundefined{HoLogoHtml@\HOLOGO@Variant\HOLOGO@name}{%
861        \expandafter\HOLOGO@Uppercase\HOLOGO@name
862      }{%
863        \csname HoLogoHtml@\HOLOGO@Variant\HOLOGO@name\endcsname
864        \ltx@secondoftwo
865      }%
866    }%
867  }%
868 }

\hologoVariantRobust
869 \ltx@ifundefined{protected}{%
870   \ltx@ifundefined{DeclareRobustCommand}{%
871     \def\hologoVariantRobust#1#2%
872   }{%
873     \DeclareRobustCommand*\hologoVariantRobust[2]%
874   }%
875 }{%
876   \protected\def\hologoVariantRobust#1#2%
877 }%
878 {%
879   \begingroup
880     \hologoLogoSetup{#1}{variant={#2}}%
881     \hologoRobust{#1}%
882   \endgroup
883 }

\HologoVariantRobust
884 \ltx@ifundefined{protected}{%
885   \ltx@ifundefined{DeclareRobustCommand}{%
886     \def\HologoVariantRobust#1#2%
887   }{%
888     \DeclareRobustCommand*\HologoVariantRobust[2]%
889   }%
890 }{%
891   \protected\def\HologoVariantRobust#1#2%
892 }%
893 {%
894   \begingroup
895     \hologoLogoSetup{#1}{variant={#2}}%
896     \HologoRobust{#1}%
897   \endgroup
898 }

\hologorobust Macro \hologorobust is only defined for compatibility. Its use is deprecated.
899 \def\hologorobust{\hologoRobust}

```

2.8 Helpers

\HOLOGO@Uppercase Macro \HOLOGO@Uppercase is restricted to \uppercase, because plain T_EX or iniT_EX do not provide \MakeUppercase.

```

900 \def\HOLOGO@Uppercase#1{\uppercase{#1}}


\HOLOGO@PfdDocUnicode
901 \def\HOLOGO@PfdDocUnicode{%
902   \ifx\ifHy@unicode\iftrue
903     \expandafter\ltx@secondoftwo
904   \else
905     \expandafter\ltx@firstoftwo
906   \fi
907 }

\HOLOGO@Math
908 \def\HOLOGO@MathSetup{%
909   \mathsurround0pt\relax
910   \HOLOGO@IfExists{f@series}{%
911     \if b\expandafter\ltx@car\f@series x@\nil
912       \csname boldmath\endcsname
913     \fi
914   }{}%
915 }

\HOLOGO@TempDimen
916 \dimendef\HOLOGO@TempDimen=\ltx@zero


\HOLOGO@NegativeKerning
917 \def\HOLOGO@NegativeKerning#1{%
918   \begingroup
919     \HOLOGO@TempDimen=0pt\relax
920     \comma@parse@normalized{#1}{%
921       \ifdim\HOLOGO@TempDimen=0pt %
922         \expandafter\HOLOGO@@NegativeKerning\comma@entry
923       \fi
924       \ltx@gobble
925     }%
926     \ifdim\HOLOGO@TempDimen<0pt %
927       \kern\HOLOGO@TempDimen
928     \fi
929   \endgroup
930 }

\HOLOGO@@NegativeKerning
931 \def\HOLOGO@@NegativeKerning#1#2{%
932   \setbox\ltx@zero\hbox{#1#2}%
933   \HOLOGO@TempDimen=\wd\ltx@zero
934   \setbox\ltx@zero\hbox{#1\kern0pt#2}%
935   \advance\HOLOGO@TempDimen by -\wd\ltx@zero
936 }

\HOLOGO@SpaceFactor
937 \def\HOLOGO@SpaceFactor{%
938   \spacefactor1000 %
939 }

\HOLOGO@Span
940 \def\HOLOGO@Span#1#2{%
941   \HCode{<span class="HoLogo-#1">}%
942   #2%
943   \HCode{</span>}%
944 }

```

2.8.1 Text subscript

```
\HOLOGO@SubScript
945 \def\HOLOGO@SubScript#1{%
946   \ltx@ifundefined{textsubscript}{%
947     \ltx@ifundefined{text}{%
948       \ltx@mbox{%
949         \mathsurround=0pt\relax
950         $%
951         -{%
952           \ltx@ifundefined{sf@size}{%
953             \mathrm{#1}%
954           }{%
955             \mbox{%
956               \fontsize{sf@size{0pt}}{selectfont
957               #1}%
958             }%
959           }%
960         }%
961         $%
962       }%
963     }{%
964       \ltx@mbox{%
965         \mathsurround=0pt\relax
966         $_{\text{#1}}$%
967       }%
968     }%
969   }{%
970     \textsubscript{#1}%
971   }%
972 }
```

2.9 TeX and friends

2.9.1 TeX

```
\HoLogo@TeX Source: LATEX kernel.
973 \def\HoLogo@TeX#1{%
974   T\kern-.1667em\lower.5ex\hbox{E}\kern-.125em X\HOLOGO@SpaceFactor
975 }
```

```
\HoLogoHtml@TeX
976 \def\HoLogoHtml@TeX#1{%
977   \HoLogoCss@TeX
978   \HOLOGO@Span{TeX}{%
979     T%
980     \HOLOGO@Span{e}{%
981       E%
982     }%
983     X%
984   }%
985 }
```

```
\HoLogoCss@TeX
986 \def\HoLogoCss@TeX{%
987   \Css{%
988     span.HoLogo-TeX span.HoLogo-e{%
989       position:relative;}}
```

```

990     top:.5ex;%
991     margin-left:-.1667em;%
992     margin-right:-.125em;%
993   }%
994 }%
995 \Css{%
996   a span.HoLogo-TeX span.HoLogo-e{%
997     text-decoration:none;%
998   }%
999 }%
1000 \global\let\HoLogoCss@TeX\relax
1001 }

2.9.2 plain TeX

\HoLogo@plainTeX@space Source: "The TeXbook"
1002 \def\HoLogo@plainTeX@space#1{%
1003   \HOLOGO@mbox{\#1{p}{P}lain}\HOLOGO@space\hologo{TeX}%
1004 }

\HoLogoCs@plainTeX@space
1005 \def\HoLogoCs@plainTeX@space#1{\#1{p}{P}lain TeX}%

\HoLogoBkm@plainTeX@space
1006 \def\HoLogoBkm@plainTeX@space#1{%
1007   #1{p}{P}lain \hologo{TeX}%
1008 }

\HoLogoHtml@plainTeX@space
1009 \def\HoLogoHtml@plainTeX@space#1{%
1010   #1{p}{P}lain \hologo{TeX}%
1011 }

\HoLogo@plainTeX@hyphen
1012 \def\HoLogo@plainTeX@hyphen#1{%
1013   \HOLOGO@mbox{\#1{p}{P}lain}\HOLOGO@hyphen\hologo{TeX}%
1014 }

\HoLogoCs@plainTeX@hyphen
1015 \def\HoLogoCs@plainTeX@hyphen#1{\#1{p}{P}lain-TeX}%

\HoLogoBkm@plainTeX@hyphen
1016 \def\HoLogoBkm@plainTeX@hyphen#1{%
1017   #1{p}{P}lain-\hologo{TeX}%
1018 }

\HoLogoHtml@plainTeX@hyphen
1019 \def\HoLogoHtml@plainTeX@hyphen#1{%
1020   #1{p}{P}lain-\hologo{TeX}%
1021 }

\HoLogo@plainTeX@runtogether
1022 \def\HoLogo@plainTeX@runtogether#1{%
1023   \HOLOGO@mbox{\#1{p}{P}lain\hologo{TeX}}%
1024 }

```

```

\HoLogoCs@plainTeX@runtogether
1025 \def\HoLogoCs@plainTeX@runtogether#1{\#1{p}{P}lainTeX}

\HoLogoBkm@plainTeX@runtogether
1026 \def\HoLogoBkm@plainTeX@runtogether#1{%
1027   #1{p}{P}lain\hologo{TeX}%
1028 }

\HoLogoHtml@plainTeX@runtogether
1029 \def\HoLogoHtml@plainTeX@runtogether#1{%
1030   #1{p}{P}lain\hologo{TeX}%
1031 }

\HoLogo@plainTeX
1032 \def\HoLogo@plainTeX{\HoLogo@plainTeX@space}

\HoLogoCs@plainTeX
1033 \def\HoLogoCs@plainTeX{\HoLogoCs@plainTeX@space}

\HoLogoBkm@plainTeX
1034 \def\HoLogoBkm@plainTeX{\HoLogoBkm@plainTeX@space}

\HoLogoHtml@plainTeX
1035 \def\HoLogoHtml@plainTeX{\HoLogoHtml@plainTeX@space}

```

2.9.3 L^AT_EX

Source: L^AT_EX kernel.

```

\DeclareRobustCommand{\LaTeX}{%
  L%
  \kern-.36em%
  {%
    \sbox{z@ T}%
    \vbox to\ht{z@}{%
      \hbox{%
        \check@mathfonts
        \fontsize{sf@size}{z@}
        \math@fontsfal se
        \selectfont
        A%
      }%
      \vss
    }%
  }%
  \kern-.15em%
  \TeX
}

```

```

\HoLogo@La
1036 \def\HoLogo@La#1{%
1037   L%
1038   \kern-.36em%
1039   \begingroup
1040     \setbox\ltx@zero\hbox{T}%
1041     \vbox to\ht\ltx@zero{%
1042       \hbox{%

```

```

1043      \ltx@ifundefined{check@mathfonts}{%
1044          \csname sevenrm\endcsname
1045      }{%
1046          \check@mathfonts
1047          \fontsize\sf@size{0pt}%
1048          \math@fontsfalse\selectfont
1049      }%
1050      A%
1051  }%
1052  \vss
1053 }%
1054 \endgroup
1055 }

```

\HoLogo@LaTeX Source: L^AT_EX kernel.

```

1056 \def\HoLogo@LaTeX#1{%
1057   \hlogo{La}%
1058   \kern-.15em%
1059   \hlogo{TeX}%
1060 }

```

\HoLogoHtml@LaTeX

```

1061 \def\HoLogoHtml@LaTeX#1{%
1062   \HoLogoCss@LaTeX
1063   \HOLOGO@Span{LaTeX}{%
1064     L%
1065     \HOLOGO@Span{a}{%
1066       A%
1067     }%
1068     \hlogo{TeX}%
1069   }%
1070 }

```

\HoLogoCss@LaTeX

```

1071 \def\HoLogoCss@LaTeX{%
1072   \Css{%
1073     span.HoLogo-LaTeX span.HoLogo-a{%
1074       position:relative;%
1075       top:-.5ex;%
1076       margin-left:-.36em;%
1077       margin-right:-.15em;%
1078       font-size:85\%;%
1079     }%
1080   }%
1081   \global\let\HoLogoCss@LaTeX\relax
1082 }

```

2.9.4 (I)TeX

\HoLogo@LaTeXTeX The kerning around the parentheses is taken from package dtklogos [2].

```

\DeclareRobustCommand{\LaTeXTeX}{%
(%
\kern-.15em%
L%
\kern-.36em%
)%
\sbox{z@ T}

```

```

        \vbox to\ht0{%
          \hbox{%
            $m@th$%
            \csname S@\f@size\endcsname
            \fontsize\sf@size\z@
            \math@fontsfalse
            \selectfont
            A%
          }%
        }%
      }%
      \vss
    }%
  }%
  \kern-.2em%
)%
\kern-.15em%
\TeX
}

1083 \def\HoLogo@LaTeXTeX#1{%
1084   (%
1085   \kern-.15em%
1086   \hologo{La}%
1087   \kern-.2em%
1088   )%
1089   \kern-.15em%
1090   \hologo{TeX}%
1091 }

\HoLogoBkm@LaTeXTeX
1092 \def\HoLogoBkm@LaTeXTeX#1{((La)TeX}

\HoLogo@(La)TeX
1093 \expandafter
1094 \let\csname HoLogo@(La)TeX\endcsname\HoLogo@LaTeXTeX

\HoLogoBkm@(La)TeX
1095 \expandafter
1096 \let\csname HoLogoBkm@(La)TeX\endcsname\HoLogoBkm@LaTeXTeX

\HoLogoHtml@LaTeXTeX
1097 \def\HoLogoHtml@LaTeXTeX#1{%
1098   \HoLogoCss@LaTeXTeX
1099   \HOLOGO@Span{LaTeXTeX}{%
1100     (%
1101     \HOLOGO@Span{L}{L}%
1102     \HOLOGO@Span{a}{A}%
1103     \HOLOGO@Span{ParenRight}{}}%
1104   \hologo{TeX}%
1105 }%
1106 }

\HoLogoHtml@(La)TeX Kerning after opening parentheses and before closing parentheses is -0.1 em. The
original values -0.15 em looked too ugly for a serif font.
1107 \expandafter
1108 \let\csname HoLogoHtml@(La)TeX\endcsname\HoLogoHtml@LaTeXTeX

\HoLogoCss@LaTeXTeX
1109 \def\HoLogoCss@LaTeXTeX{%

```

```

1110  \Css{%
1111      span.HoLogo-LaTeXe span.HoLogo-L{%
1112          margin-left:-.1em;%
1113      }%
1114  }%
1115  \Css{%
1116      span.HoLogo-LaTeXe span.HoLogo-a{%
1117          position:relative;%
1118          top:-.5ex;%
1119          margin-left:-.36em;%
1120          margin-right:-.1em;%
1121          font-size:85\%;%
1122      }%
1123  }%
1124  \Css{%
1125      span.HoLogo-LaTeXe span.HoLogo-ParenRight{%
1126          margin-right:-.15em;%
1127      }%
1128  }%
1129  \global\let\HoLogoCss@LaTeXe\relax
1130 }

```

2.9.5 L^AT_EX 2_ε

```

\HoLogo@LaTeXe Source: LATEX kernel
1131 \def\HoLogo@LaTeXe#1{%
1132     \hologo{LaTeX}%
1133     \kern.15em%
1134     \hbox{%
1135         \HOLOGO@MathSetup
1136         2%
1137         ${_{\textstyle\backslash}\textstyle\varepsilon}$%
1138     }%
1139 }

\HoLogoCs@LaTeXe
1140 \ifnum64='`^\^0040\relax % test for big chars of LuaTeX/XeTeX
1141     \catcode`\$=9 %
1142     \catcode`\&=14 %
1143 \else
1144     \catcode`\$=14 %
1145     \catcode`\&=9 %
1146 \fi
1147 \def\HoLogoCs@LaTeXe#1{%
1148     LaTeX2%
1149 $ \string ^``0395%
1150 & e%
1151 }%
1152 \catcode`\$=3 %
1153 \catcode`\&=4 %

\HoLogoBkm@LaTeXe
1154 \def\HoLogoBkm@LaTeXe#1{%
1155     \hologo{LaTeX}%
1156     2%
1157     \HOLOGO@PdfdocUnicode{e}{\textepsilon}%
1158 }

```

```

\HoLogoHtml@LaTeXe

1159 \def\HoLogoHtml@LaTeXe#1{%
1160   \HoLogoCss@LaTeXe
1161   \HOLOGO@Span{LaTeX2e}{%
1162     \hologo{LaTeX}%
1163     \HOLOGO@Span{2}{2}%
1164     \HOLOGO@Span{e}{%
1165       \HOLOGO@MathSetup
1166       \ensuremath{\textstyle\varepsilon}%
1167     }%
1168   }%
1169 }

\HoLogoCss@LaTeXe

1170 \def\HoLogoCss@LaTeXe{%
1171   \Css{%
1172     span.HoLogo-LaTeX2e span.HoLogo-2{%
1173       padding-left:.15em;%
1174     }%
1175   }%
1176   \Css{%
1177     span.HoLogo-LaTeX2e span.HoLogo-e{%
1178       position:relative;%
1179       top:.35ex;%
1180       text-decoration:none;%
1181     }%
1182   }%
1183   \global\let\HoLogoCss@LaTeXe\relax
1184 }

\HoLogo@LaTeX2e

1185 \expandafter
1186 \let\csname HoLogo@LaTeX2e\endcsname\HoLogo@LaTeXe

\HoLogoCs@LaTeX2e

1187 \expandafter
1188 \let\csname HoLogoCs@LaTeX2e\endcsname\HoLogoCs@LaTeXe

\HoLogoBkm@LaTeX2e

1189 \expandafter
1190 \let\csname HoLogoBkm@LaTeX2e\endcsname\HoLogoBkm@LaTeXe

\HoLogoHtml@LaTeX2e

1191 \expandafter
1192 \let\csname HoLogoHtml@LaTeX2e\endcsname\HoLogoHtml@LaTeXe

2.9.6 LATEX3

\HoLogo@LaTeX3 Source: LATEX kernel

1193 \expandafter\def\csname HoLogo@LaTeX3\endcsname#1{%
1194   \hologo{LaTeX}%
1195   3%
1196 }

\HoLogoBkm@LaTeX3

1197 \expandafter\def\csname HoLogoBkm@LaTeX3\endcsname#1{%
1198   \hologo{LaTeX}%

```

```

1199   3%
1200 }

\HoLogoHtml@LaTeX3

1201 \expandafter
1202 \let\csname HoLogoHtml@LaTeX3\expandafter\endcsname
1203 \csname HoLogo@LaTeX3\endcsname

```

2.9.7 L^AT_EXml

```

\HoLogo@LaTeXML

1204 \def\HoLogo@LaTeXML#1{%
1205   \HOLOGO@mbox{%
1206     \hologo{La}%
1207     \kern-.15em%
1208     T%
1209     \kern-.1667em%
1210     \lower.5ex\hbox{E}%
1211     \kern-.125em%
1212     \HoLogoFont@font{LaTeXML}{sc}{xml}%
1213   }%
1214 }

```

```

\HoLogoHtml@pdfLaTeX

1215 \def\HoLogoHtml@LaTeXML#1{%
1216   \HOLOGO@Span{LaTeXML}{%
1217     \HoLogoCss@LaTeX
1218     \HoLogoCss@TeX
1219     \HOLOGO@Span{TeX}{%
1220       L%
1221       \HOLOGO@Span{a}{%
1222         A%
1223       }%
1224     }%
1225     \HOLOGO@Span{TeX}{%
1226       T%
1227       \HOLOGO@Span{e}{%
1228         E%
1229       }%
1230     }%
1231     \HCode{<span style="font-variant: small-caps;">}%
1232     xml%
1233     \HCode{</span>}%
1234   }%
1235 }

```

2.9.8 ε-T_EX

```

\HoLogo@eTeX Source: package etex

1236 \def\HoLogo@eTeX#1{%
1237   \ltx@mbox{%
1238     \HOLOGO@MathSetup
1239     $ \varepsilon %
1240     - %
1241     \HOLOGO@NegativeKerning{-T, T-, To}%
1242     \hologo{TeX}%
1243   }%
1244 }

```

```

\HoLogoCs@eTeX

1245 \ifnum64='\^^^0040\relax % test for big chars of LuaTeX/XeTeX
1246   \catcode`\$=9 %
1247   \catcode`\&=14 %
1248 \else
1249   \catcode`\$=14 %
1250   \catcode`\&=9 %
1251 \fi
1252 \def\HoLogoCs@eTeX#1{%
1253 $ #1{\string ^^^0395}{\string ^^^03b5}%
1254 & #1{e}{E}%
1255   TeX%
1256 }%
1257 \catcode`\$=3 %
1258 \catcode`\&=4 %

```

```

\HoLogoBkm@eTeX

1259 \def\HoLogoBkm@eTeX#1{%
1260   \HOLOGO@PpdfdocUnicode{#1{e}{E}}{\textepsilon}%
1261   -%
1262   \hologo{TeX}%
1263 }

```

```

\HoLogoHtml@eTeX

1264 \def\HoLogoHtml@eTeX#1{%
1265   \ltx@mbox{%
1266     \HOLOGO@MathSetup
1267     $\varepsilon$%
1268     -%
1269     \hologo{TeX}%
1270   }%
1271 }

```

2.9.9 iniTeX

```

\HoLogo@iniTeX

1272 \def\HoLogo@iniTeX#1{%
1273   \HOLOGO@mbox{%
1274     #1{i}{I}ni\hologo{TeX}%
1275   }%
1276 }

```

```

\HoLogoCs@iniTeX

1277 \def\HoLogoCs@iniTeX#1{#1{i}{I}niTeX}

```

```

\HoLogoBkm@iniTeX

1278 \def\HoLogoBkm@iniTeX#1{%
1279   #1{i}{I}ni\hologo{TeX}%
1280 }

```

```

\HoLogoHtml@iniTeX

1281 \let\HoLogoHtml@iniTeX\HoLogo@iniTeX

```

2.9.10 virTeX

```
\HoLogo@virTeX
1282 \def\HoLogo@virTeX#1{%
1283   \HOLOGO@mbox{%
1284     #1{v}{V}ir\hologo{TeX}%
1285   }%
1286 }

\HoLogoCs@virTeX
1287 \def\HoLogoCs@virTeX#1{#1{v}{V}irTeX}
```

```
\HoLogoBkm@virTeX
1288 \def\HoLogoBkm@virTeX#1{%
1289   #1{v}{V}ir\hologo{TeX}%
1290 }
```

```
\HoLogoHtml@virTeX
1291 \let\HoLogoHtml@virTeX\HoLogo@virTeX
```

2.9.11 SliTeX

Definitions of the three variants.

```
\HoLogo@SLiTeX@lift
1292 \def\HoLogo@SLiTeX@lift#1{%
1293   \HoLogoFont@font{SliTeX}{rm}{%
1294     S%
1295     \kern-.06em%
1296     L%
1297     \kern-.18em%
1298     \raise.32ex\hbox{\HoLogoFont@font{SliTeX}{sc}{i}}%
1299     \HOLOGO@discretionary%
1300     \kern-.06em%
1301     \hologo{TeX}%
1302   }%
1303 }
```

```
\HoLogoBkm@SLiTeX@lift
1304 \def\HoLogoBkm@SLiTeX@lift#1{SLiTeX}
```

```
\HoLogoHtml@SLiTeX@lift
1305 \def\HoLogoHtml@SLiTeX@lift#1{%
1306   \HoLogoCss@SLiTeX@lift
1307   \HOLOGO@Span{SLiTeX-lift}{%
1308     \HoLogoFont@font{SliTeX}{rm}{%
1309       S%
1310       \HOLOGO@Span{L}{L}%
1311       \HOLOGO@Span{i}{i}%
1312       \hologo{TeX}%
1313     }%
1314   }%
1315 }
```

```
\HoLogoCss@SLiTeX@lift
1316 \def\HoLogoCss@SLiTeX@lift{%
1317   \Css{%
```

```

1318     span.HoLogo-SLiTeX-lift span.HoLogo-L{%
1319         margin-left:-.06em;%
1320         margin-right:-.18em;%
1321     }%
1322 }%
1323 \Css{%
1324     span.HoLogo-SLiTeX-lift span.HoLogo-i{%
1325         position:relative;%
1326         top:-.32ex;%
1327         margin-right:-.06em;%
1328         font-variant:small-caps;%
1329     }%
1330 }%
1331 \global\let\HoLogoCss@SLiTeX@lift\relax
1332 }

\HoLogo@SLiTeX@simple
1333 \def\HoLogo@SLiTeX@simple#1{%
1334     \HoLogoFont@font{SLiTeX}{rm}{%
1335         \ltx@mbox{%
1336             \HoLogoFont@font{SLiTeX}{sc}{Sli}%
1337         }%
1338         \Hologo@discretionary
1339         \hologo{TeX}%
1340     }%
1341 }

\HoLogoBkm@SLiTeX@simple
1342 \def\HoLogoBkm@SLiTeX@simple#1{SliTeX}

\HoLogoHtml@SLiTeX@simple
1343 \let\HoLogoHtml@SLiTeX@simple\HoLogo@SLiTeX@simple

\HoLogo@SLiTeX@narrow
1344 \def\HoLogo@SLiTeX@narrow#1{%
1345     \HoLogoFont@font{SLiTeX}{rm}{%
1346         \ltx@mbox{%
1347             S%
1348             \kern-.06em%
1349             \HoLogoFont@font{SLiTeX}{sc}{%
1350                 1%
1351                 \kern-.035em%
1352                 i%
1353             }%
1354         }%
1355         \Hologo@discretionary
1356         \kern-.06em%
1357         \hologo{TeX}%
1358     }%
1359 }

\HoLogoBkm@SLiTeX@narrow
1360 \def\HoLogoBkm@SLiTeX@narrow#1{SliTeX}

\HoLogoHtml@SLiTeX@narrow
1361 \def\HoLogoHtml@SLiTeX@narrow#1{%
1362     \HoLogoCss@SLiTeX@narrow

```

```

1363  \HOLOGO@Span{SliTeX-narrow}{%
1364    \HoLogoFont@font{SliTeX}{rm}{%
1365      S%
1366      \HOLOGO@Span{l}{l}%
1367      \HOLOGO@Span{i}{i}%
1368      \hologo{TeX}%
1369    }%
1370  }%
1371 }

\HoLogoCss@SliTeX@narrow
1372 \def\HoLogoCss@SliTeX@narrow{%
1373   \Css{%
1374     span.HoLogo-SliTeX-narrow span.HoLogo-l{%
1375       margin-left:-.06em;%
1376       margin-right:-.035em;%
1377       font-variant:small-caps;%
1378     }%
1379   }%
1380   \Css{%
1381     span.HoLogo-SliTeX-narrow span.HoLogo-i{%
1382       margin-right:-.06em;%
1383       font-variant:small-caps;%
1384     }%
1385   }%
1386   \global\let\HoLogoCss@SliTeX@narrow\relax
1387 }

```

Macro set completion.

```

\HoLogo@SLiTeX@simple
1388 \def\HoLogo@SLiTeX@simple{\HoLogo@SliTeX@simple}

\HoLogoBkm@SLiTeX@simple
1389 \def\HoLogoBkm@SLiTeX@simple{\HoLogoBkm@SliTeX@simple}

\HoLogoHtml@SLiTeX@simple
1390 \def\HoLogoHtml@SLiTeX@simple{\HoLogoHtml@SliTeX@simple}

\HoLogo@SLiTeX@narrow
1391 \def\HoLogo@SLiTeX@narrow{\HoLogo@SliTeX@narrow}

\HoLogoBkm@SLiTeX@narrow
1392 \def\HoLogoBkm@SLiTeX@narrow{\HoLogoBkm@SliTeX@narrow}

\HoLogoHtml@SLiTeX@narrow
1393 \def\HoLogoHtml@SLiTeX@narrow{\HoLogoHtml@SliTeX@narrow}

\HoLogo@SliTeX@lift
1394 \def\HoLogo@SliTeX@lift{\HoLogo@SLiTeX@lift}

\HoLogoBkm@SliTeX@lift
1395 \def\HoLogoBkm@SliTeX@lift{\HoLogoBkm@SLiTeX@lift}

\HoLogoHtml@SliTeX@lift
1396 \def\HoLogoHtml@SliTeX@lift{\HoLogoHtml@SLiTeX@lift}

```

Defaults.

```
\HoLogo@SLiTeX
1397 \def\HoLogo@SLiTeX{\HoLogo@SLiTeX@lift}

\HoLogoBkm@SLiTeX
1398 \def\HoLogoBkm@SLiTeX{\HoLogoBkm@SLiTeX@lift}

\HoLogoHtml@SLiTeX
1399 \def\HoLogoHtml@SLiTeX{\HoLogoHtml@SLiTeX@lift}

\HoLogo@SliTeX
1400 \def\HoLogo@SliTeX{\HoLogo@SliTeX@narrow}

\HoLogoBkm@SliTeX
1401 \def\HoLogoBkm@SliTeX{\HoLogoBkm@SliTeX@narrow}

\HoLogoHtml@SliTeX
1402 \def\HoLogoHtml@SliTeX{\HoLogoHtml@SliTeX@narrow}
```

2.9.12 LuaTeX

\HoLogo@LuaTeX The kerning is an idea of Hans Hagen, see mailing list ‘luatex at tug dot org’ in March 2010.

```
1403 \def\HoLogo@LuaTeX#1{%
1404   \HOLOGO@mbox{%
1405     Lua%
1406     \HOLOGO@NegativeKerning{aT,oT,To}%
1407     \hologo{TeX}%
1408   }%
1409 }
```

```
\HoLogoHtml@LuaTeX
1410 \let\HoLogoHtml@LuaTeX\HoLogo@LuaTeX
```

2.9.13 LuaATEX

```
\HoLogo@LuaLaTeX
1411 \def\HoLogo@LuaLaTeX#1{%
1412   \HOLOGO@mbox{%
1413     Lua%
1414     \hologo{LaTeX}%
1415   }%
1416 }
```

```
\HoLogoHtml@LuaLaTeX
1417 \let\HoLogoHtml@LuaLaTeX\HoLogo@LuaLaTeX
```

2.9.14 X_HTeX, X_HATEX

```
\HOLOGO@IfCharExists
1418 \ifluatex
1419   \ifnum\luatexversion<36 %
1420   \else
1421     \def\HOLOGO@IfCharExists#1{%
1422       \ifnum
```

```

1423     \directlua{%
1424         if luatofload and luatofload.aux then
1425             if luatofload.aux.font_has_glyph(%
1426                 font.current(), \number#1) then %
1427                 tex.print("1") %
1428             end %
1429         elseif font and font.fonts and font.current then %
1430             local f = font.fonts[font.current()]%
1431             if f.characters and f.characters[\number#1] then %
1432                 tex.print("1")%
1433             end %
1434         end%
1435     }0=\ltx@zero
1436     \expandafter\ltx@secondoftwo
1437     \else
1438         \expandafter\ltx@firstoftwo
1439     \fi
1440 }
1441 \fi
1442 \fi
1443 \ltx@ifundefined{HOLOGO@IfCharExists}{%
1444     \def\HOLOGO@@IfCharExists#1{%
1445         \begin{group}
1446             \tracinglostchars=\ltx@zero
1447             \setbox\ltx@zero=\hbox{%
1448                 \kern7sp\char#1\relax
1449                 \ifnum\lastkern>\ltx@zero
1450                     \expandafter\aftergroup\csname iffalse\endcsname
1451                 \else
1452                     \expandafter\aftergroup\csname iftrue\endcsname
1453                 \fi
1454             }%
1455             % \if{true|false} from \aftergroup
1456             \endgroup
1457             \expandafter\ltx@firstoftwo
1458         \else
1459             \endgroup
1460             \expandafter\ltx@secondoftwo
1461         \fi
1462     }%
1463     \ifxetex
1464         \ltx@ifundefined{XeTeXfonttype}{}{%
1465             \ltx@ifundefined{XeTeXcharglyph}{}{%
1466                 \def\HOLOGO@IfCharExists#1{%
1467                     \ifnum\XeTeXfonttype>\ltx@zero
1468                         \expandafter\ltx@firstofthree
1469                     \else
1470                         \expandafter\ltx@gobble
1471                     \fi
1472                 }%
1473                     \ifnum\XeTeXcharglyph#1>\ltx@zero
1474                         \expandafter\ltx@firstoftwo
1475                     \else
1476                         \expandafter\ltx@secondoftwo
1477                     \fi
1478                 }%
1479                 \HOLOGO@@IfCharExists{#1}%
1480             }%

```

```

1481      }%
1482      }%
1483      \fi
1484  }{%
1485  \ltx@ifundefined{HOLOGO@IfCharExists}{%
1486    \ifnum64='\^^^0040\relax % test for big chars of LuaTeX/XeTeX
1487    \let\HOLOGO@IfCharExists\HOLOGO@@IfCharExists
1488  \else
1489    \def\HOLOGO@IfCharExists#1{%
1490      \ifnum#1>255 %
1491        \expandafter\ltx@fourthoffour
1492        \fi
1493        \HOLOGO@@IfCharExists{#1}%
1494    }%
1495    \fi
1496  }{%

```

\HoLogo@Xe Source: package dtklogos

```

1497 \def\HoLogo@Xe#1{%
1498   X%
1499   \kern-.1em\relax
1500   \HOLOGO@IfCharExists{"018E}{%
1501     \lower.5ex\hbox{\char"018E}}%
1502  }{%
1503    \chardef\HOLOGO@choice=\ltx@zero
1504    \ifdim\fontdimen\ltx@one\font>0pt %
1505      \ltx@IfUndefined{rotatebox}{%
1506        \ltx@IfUndefined{pgftext}{%
1507          \ltx@IfUndefined{psscalebox}{%
1508            \ltx@IfUndefined{HOLOGO@ScaleBox@\holoDriver}{%
1509              }{%
1510                \chardef\HOLOGO@choice=4 %
1511              }%
1512            }{%
1513              \chardef\HOLOGO@choice=3 %
1514            }%
1515          }{%
1516            \chardef\HOLOGO@choice=2 %
1517          }%
1518        }{%
1519          \chardef\HOLOGO@choice=1 %
1520        }%
1521        \ifcase\HOLOGO@choice
1522          \HOLOGO@WarningUnsupportedDriver{Xe}%
1523          e%
1524        \or % 1: \rotatebox
1525          \begingroup
1526            \setbox\ltx@zero\hbox{\rotatebox{180}{E}}%
1527            \ltx@LocDimenA=\dp\ltx@zero
1528            \advance\ltx@LocDimenA by -.5ex\relax
1529            \raise\ltx@LocDimenA\box\ltx@zero
1530          \endgroup
1531        \or % 2: \pgftext
1532          \lower.5ex\hbox{%
1533            \pgfpicture
1534              \pgftext[rotate=180]{E}%
1535            \endpgfpicture
1536          }%

```

```

1537      \or % 3: \psscalebox
1538          \begingroup
1539              \setbox\ltx@zero\hbox{\psscalebox{-1 -1}{E}}%
1540              \ltx@LocDimenA=\dp\ltx@zero
1541              \advance\ltx@LocDimenA by -.5ex\relax
1542              \raise\ltx@LocDimenA\box\ltx@zero
1543          \endgroup
1544      \or % 4: \HOLOGO@PointReflectBox
1545          \lower.5ex\hbox{\HOLOGO@PointReflectBox{E}}%
1546      \else
1547          \PackageError{hologo}{Internal error (choice/it)}\@ehc
1548      \fi
1549  \else
1550      \ltx@ifundefined{reflectbox}%
1551          \ltx@ifundefined{pgftext}%
1552              \ltx@ifundefined{psscalebox}%
1553                  \ltx@ifundefined{HOLOGO@ScaleBox@\hologoDriver}%
1554                      }%
1555                      \chardef\HOLOGO@choice=4 %
1556                      }%
1557                      }%
1558                      \chardef\HOLOGO@choice=3 %
1559                      }%
1560                      }%
1561                      \chardef\HOLOGO@choice=2 %
1562                      }%
1563                      }%
1564                      \chardef\HOLOGO@choice=1 %
1565                  }%
1566          \ifcase\HOLOGO@choice
1567              \HOLOGO@WarningUnsupportedDriver{Xe}%
1568              e%
1569          \or % 1: reflectbox
1570              \lower.5ex\hbox{%
1571                  \reflectbox{E}%
1572              }%
1573          \or % 2: \pgftext
1574              \lower.5ex\hbox{%
1575                  \pgfpicture
1576                      \pgftransformxscale{-1}%
1577                      \pgftext{E}%
1578                  \endpgfpicture
1579              }%
1580          \or % 3: \psscalebox
1581              \lower.5ex\hbox{%
1582                  \psscalebox{-1 1}{E}%
1583              }%
1584          \or % 4: \HOLOGO@Reflectbox
1585              \lower.5ex\hbox{%
1586                  \HOLOGO@ReflectBox{E}%
1587              }%
1588          \else
1589              \PackageError{hologo}{Internal error (choice/up)}\@ehc
1590          \fi
1591      \fi
1592  }%
1593 }

```

```

\HoLogoHtml@Xe
1594 \def\HoLogoHtml@Xe#1{%
1595   \HoLogoCss@Xe
1596   \HOLOGO@Span{Xe}{%
1597     X%
1598     \HOLOGO@Span{e}{%
1599       \HCode{&\ltx@hashchar x018e;}%
1600     }%
1601   }%
1602 }

\HoLogoCss@Xe
1603 \def\HoLogoCss@Xe{%
1604   \Css{%
1605     span.HoLogo-Xe span.HoLogo-e{%
1606       position:relative;%
1607       top:.5ex;%
1608       left-margin:-.1em;%
1609     }%
1610   }%
1611   \global\let\HoLogoCss@Xe\relax
1612 }

\HoLogo@XeTeX
1613 \def\HoLogo@XeTeX#1{%
1614   \hologo{Xe}%
1615   \kern-.15em\relax
1616   \hologo{TeX}%
1617 }

\HoLogoHtml@XeTeX
1618 \def\HoLogoHtml@XeTeX#1{%
1619   \HoLogoCss@XeTeX
1620   \HOLOGO@Span{XeTeX}{%
1621     \hologo{Xe}%
1622     \hologo{TeX}%
1623   }%
1624 }

\HoLogoCss@XeTeX
1625 \def\HoLogoCss@XeTeX{%
1626   \Css{%
1627     span.HoLogo-XeTeX span.HoLogo-TeX{%
1628       margin-left:-.15em;%
1629     }%
1630   }%
1631   \global\let\HoLogoCss@XeTeX\relax
1632 }

\HoLogo@XeLaTeX
1633 \def\HoLogo@XeLaTeX#1{%
1634   \hologo{Xe}%
1635   \kern-.13em%
1636   \hologo{TeX}%
1637 }

\HoLogoHtml@XeLaTeX

```

```

1638 \def\HoLogoHtml@XeLaTeX#1{%
1639   \HoLogoCss@XeLaTeX
1640   \HOLOGO@Span{XeLaTeX}{%
1641     \hologo{Xe}%
1642     \hologo{LaTeX}%
1643   }%
1644 }

\HoLogoCss@XeLaTeX
1645 \def\HoLogoCss@XeLaTeX{%
1646   \Css{%
1647     span.HoLogo-XeLaTeX span.HoLogo-Xe{%
1648       margin-right:-.13em;%
1649     }%
1650   }%
1651 \global\let\HoLogoCss@XeLaTeX\relax
1652 }

```

2.9.15 pdfTeX, pdfLATEX

```

\HoLogo@pdfTeX
1653 \def\HoLogo@pdfTeX#1{%
1654   \HOLOGO@mbox{%
1655     #1{p}{P}df\hologo{TeX}%
1656   }%
1657 }

\HoLogoCs@pdfTeX
1658 \def\HoLogoCs@pdfTeX#1{#1{p}{P}dfTeX}

```

```

\HoLogoBkm@pdfTeX
1659 \def\HoLogoBkm@pdfTeX#1{%
1660   #1{p}{P}df\hologo{TeX}%
1661 }

```

```

\HoLogoHtml@pdfTeX
1662 \let\HoLogoHtml@pdfTeX\HoLogo@pdfTeX

```

```

\HoLogo@pdfLaTeX
1663 \def\HoLogo@pdfLaTeX#1{%
1664   \HOLOGO@mbox{%
1665     #1{p}{P}df\hologo{LaTeX}%
1666   }%
1667 }

```

```

\HoLogoCs@pdfLaTeX
1668 \def\HoLogoCs@pdfLaTeX#1{#1{p}{P}dfLaTeX}

```

```

\HoLogoBkm@pdfLaTeX
1669 \def\HoLogoBkm@pdfLaTeX#1{%
1670   #1{p}{P}df\hologo{LaTeX}%
1671 }

```

```

\HoLogoHtml@pdfLaTeX
1672 \let\HoLogoHtml@pdfLaTeX\HoLogo@pdfLaTeX

```

2.9.16 VTeX

```
\HoLogo@VTeX
1673 \def\HoLogo@VTeX#1{%
1674   \HOLOGO@mbox{%
1675     V\hologo{TeX}%
1676   }%
1677 }

\HoLogoHtml@VTeX
1678 \let\HoLogoHtml@VTeX\HoLogo@VTeX

2.9.17  $\mathcal{AMS}$ , ...
Source: class amsdtx

\HoLogo@AmS
1679 \def\HoLogo@AmS#1{%
1680   \HoLogoFont@font{AmS}{sy}{%
1681     A%
1682     \kern-.1667em%
1683     \lower.5ex\hbox{M}%
1684     \kern-.125em%
1685     S%
1686   }%
1687 }

\HoLogoBkm@AmS
1688 \def\HoLogoBkm@AmS#1{AmS}

\HoLogoHtml@AmS
1689 \def\HoLogoHtml@AmS#1{%
1690   \HoLogoCss@AmS
1691 % \HoLogoFont@font{AmS}{sy}{%
1692   \HOLOGO@Span{AmS}{%
1693     A%
1694     \HOLOGO@Span{M}{M}%
1695     S%
1696   }%
1697 % }%
1698 }

\HoLogoCss@AmS
1699 \def\HoLogoCss@AmS{%
1700   \Css{%
1701     span.HoLogo-AmS span.HoLogo-M{%
1702       position:relative;%
1703       top:.5ex;%
1704       margin-left:-.1667em;%
1705       margin-right:-.125em;%
1706       text-decoration:none;%
1707     }%
1708   }%
1709   \global\let\HoLogoCss@AmS\relax
1710 }
```

```

\HoLogo@AmSTeX
1711 \def\HoLogo@AmSTeX#1{%
1712   \hologo{AmS}%
1713   \HOLOGO@hyphen
1714   \hologo{TeX}%
1715 }

\HoLogoBkm@AmSTeX
1716 \def\HoLogoBkm@AmSTeX#1{AmS-TeX}%

\HoLogoHtml@AmSTeX
1717 \let\HoLogoHtml@AmSTeX\HoLogo@AmSTeX

\HoLogo@AmSLaTeX
1718 \def\HoLogo@AmSLaTeX#1{%
1719   \hologo{AmS}%
1720   \HOLOGO@hyphen
1721   \hologo{LaTeX}%
1722 }

\HoLogoBkm@AmSLaTeX
1723 \def\HoLogoBkm@AmSLaTeX#1{AmS-LaTeX}%

\HoLogoHtml@AmSLaTeX
1724 \let\HoLogoHtml@AmSLaTeX\HoLogo@AmSLaTeX

```

2.9.18 BIBTeX

\HoLogo@BibTeX@sc A definition of BIBTeX is provided in the documentation source for the manual of BIBTeX [1].

```

\def\BibTeX{%
  %
  \rm
  B%
  \kern-.05em%
  %
  \sc
  i%
  \kern-.025em %
  b%
}%
\kern-.08em
T%
\kern-.1667em%
\lower.7ex\hbox{E}%
\kern-.125em%
X%
}%
}

1725 \def\HoLogo@BibTeX@sc#1{%
1726   B%
1727   \kern-.05em%
1728   \HoLogoFont@font{BibTeX}{sc}{%
1729     i%
1730     \kern-.025em%
1731     b%
}

```

```

1732  }%
1733  \HOLOGO@discretionary
1734  \kern-.08em%
1735  \hologo{TeX}%
1736 }

\HoLogoHtml@BibTeX@sc
1737 \def\HoLogoHtml@BibTeX@sc#1{%
1738   \HoLogoCss@BibTeX@sc
1739   \HOLOGO@Span{BibTeX-sc}{%
1740     B%
1741     \HOLOGO@Span{i}{i}%
1742     \HOLOGO@Span{b}{b}%
1743     \hologo{TeX}%
1744   }%
1745 }

\HoLogoCss@BibTeX@sc
1746 \def\HoLogoCss@BibTeX@sc{%
1747   \Css{%
1748     span.HoLogo-BibTeX-sc span.HoLogo-i{%
1749       margin-left:-.05em;%
1750       margin-right:-.025em;%
1751       font-variant:small-caps;%
1752     }%
1753   }%
1754   \Css{%
1755     span.HoLogo-BibTeX-sc span.HoLogo-b{%
1756       margin-right:-.08em;%
1757       font-variant:small-caps;%
1758     }%
1759   }%
1760   \global\let\HoLogoCss@BibTeX@sc\relax
1761 }

```

\HoLogo@BibTeX@sf Variant sf avoids trouble with unavailable small caps fonts (e.g., bold versions of Computer Modern or Latin Modern). The definition is taken from package `dtklogos` [2].

```

\DeclareRobustCommand{\BibTeX}{%
B%
\kern-.05em%
\hbox{%
  \$\m@th\$% %% force math size calculations
  \csname S@\f@size\endcsname
  \fontsize{sf@size}{z@}
  \math@fontsffalse
  \selectfont
I%
\kern-.025em%
B
}%
\kern-.08em%
\TeX
}

\def\HoLogo@BibTeX@sf#1{%
B%

```

```

1764  \kern-.05em%
1765  \HoLogoFont@font{BibTeX}{bibsff}%
1766  I%
1767  \kern-.025em%
1768  B%
1769 }%
1770  \HOLOGO@discretionary
1771  \kern-.08em%
1772  \hologo{TeX}%
1773 }

\HoLogoHtml@BibTeX@sf
1774 \def\HoLogoHtml@BibTeX@sf#1{%
1775   \HoLogoCss@BibTeX@sf
1776   \HOLOGO@Span{BibTeX-sf}%
1777   B%
1778   \HoLogoFont@font{BibTeX}{bibsff}%
1779   \HOLOGO@Span{i}{I}%
1780   B%
1781 }%
1782   \hologo{TeX}%
1783 }%
1784 }

\HoLogoCss@BibTeX@sf
1785 \def\HoLogoCss@BibTeX@sf{%
1786   \Css{%
1787     span.HoLogo-BibTeX-sf span.HoLogo-i{%
1788       margin-left:-.05em;%
1789       margin-right:-.025em;%
1790     }%
1791   }%
1792   \Css{%
1793     span.HoLogo-BibTeX-sf span.HoLogo-TeX{%
1794       margin-left:-.08em;%
1795     }%
1796   }%
1797   \global\let\HoLogoCss@BibTeX@sf\relax
1798 }

\HoLogo@BibTeX
1799 \def\HoLogo@BibTeX{\HoLogo@BibTeX@sf}

\HoLogoHtml@BibTeX
1800 \def\HoLogoHtml@BibTeX{\HoLogoHtml@BibTeX@sf}

2.9.19 BIBTeX8

\HoLogo@BibTeX8
1801 \expandafter\def\csname HoLogo@BibTeX8\endcsname#1{%
1802   \hologo{BibTeX}%
1803   8%
1804 }

\HoLogoBkm@BibTeX8
1805 \expandafter\def\csname HoLogoBkm@BibTeX8\endcsname#1{%
1806   \hologo{BibTeX}%
1807   8%
1808 }

```

```
\HoLogoHtml@BibTeX8
1809 \expandafter
1810 \let\csname HoLogoHtml@BibTeX8\expandafter\endcsname
1811 \csname HoLogo@BibTeX8\endcsname
```

2.9.20 ConTeXt

```
\HoLogo@ConTeXt@simple
```

```
1812 \def\HoLogo@ConTeXt@simple#1{%
1813   \HOLOGO@mbox{Con}%
1814   \HOLOGO@discretionary
1815   \HOLOGO@mbox{\hologo{TeX}t}%
1816 }
```

```
\HoLogoHtml@ConTeXt@simple
```

```
1817 \let\HoLogoHtml@ConTeXt@simple\HoLogo@ConTeXt@simple
```

\HoLogo@ConTeXt@narrow This definition of logo ConTeXt with variant narrow comes from TUGboat's class `tugboat` (version 2010/11/15 v2.8).

```
1818 \def\HoLogo@ConTeXt@narrow#1{%
1819   \HOLOGO@mbox{C\kern-.0333emon}%
1820   \HOLOGO@discretionary
1821   \kern-.0667em%
1822   \HOLOGO@mbox{\hologo{TeX}\kern-.0333emt}%
1823 }
```

```
\HoLogoHtml@ConTeXt@narrow
```

```
1824 \def\HoLogoHtml@ConTeXt@narrow#1{%
1825   \HoLogoCss@ConTeXt@narrow
1826   \HOLOGO@Span{ConTeXt-narrow}{%
1827     \HOLOGO@Span{C}{C}%
1828     on%
1829     \hologo{TeX}%
1830     t%
1831   }%
1832 }
```

```
\HoLogoCss@ConTeXt@narrow
```

```
1833 \def\HoLogoCss@ConTeXt@narrow{%
1834   \Css{%
1835     span.HoLogo-ConTeXt-narrow span.HoLogo-C{%
1836       margin-left:-.0333em;%
1837     }%
1838   }%
1839   \Css{%
1840     span.HoLogo-ConTeXt-narrow span.HoLogo-TeX{%
1841       margin-left:-.0667em;%
1842       margin-right:-.0333em;%
1843     }%
1844   }%
1845   \global\let\HoLogoCss@ConTeXt@narrow\relax
1846 }
```

```
\HoLogo@ConTeXt
```

```
1847 \def\HoLogo@ConTeXt{\HoLogo@ConTeXt@narrow}
```

```
\HoLogoHtml@ConTeXt
```

```
1848 \def\HoLogoHtml@ConTeXt{\HoLogoHtml@ConTeXt@narrow}
```

2.9.21 emTeX

```
\HoLogo@emTeX
1849 \def\HoLogo@emTeX#1{%
1850   \HOLOGO@mbox{\#1{e}{E}m}%
1851   \HOLOGO@discretionary
1852   \hologo{TeX}%
1853 }

\HoLogoCs@emTeX
1854 \def\HoLogoCs@emTeX#1{\#1{e}{E}mTeX}%

\HoLogoBkm@emTeX
1855 \def\HoLogoBkm@emTeX#1{%
1856   \#1{e}{E}m\hologo{TeX}%
1857 }

\HoLogoHtml@emTeX
1858 \let\HoLogoHtml@emTeX\HoLogo@emTeX
```

2.9.22 ε_X TeX

\HoLogo@ExTeX The definition is taken from the FAQ of the project ε_X TeX [4].

```
\def\ExTeX{%
  \textrm{\% Logo always with serifs
    \ensuremath{%
      \textstyle
      \varepsilon
      \kern-0.15em
      \mathcal{X}}%
  }%
}%
\kern-.15em
\TeX
}%
}

1859 \def\HoLogo@ExTeX#1{%
1860   \HoLogoFont@font{ExTeX}{rm}{%
1861     \ltx@mbox{%
1862       \HOLOGO@MathSetup
1863       $%
1864         \textstyle
1865         \varepsilon
1866         \kern-0.15em
1867         \HoLogoFont@font{ExTeX}{sy}{X}%
1868       }%
1869       $%
1870     }%
1871     \HOLOGO@discretionary
1872     \kern-.15em
1873     \hologo{TeX}%
1874   }%
1875 }

\HoLogoHtml@ExTeX
1876 \def\HoLogoHtml@ExTeX#1{%
```

```

1877  \HoLogoCss@ExTeX
1878  \HoLogoFont@font{ExTeX}{rm}{%
1879    \HOLOGO@Span{ExTeX}{%
1880      \ltx@mbox{%
1881        \HOLOGO@MathSetup
1882        $ \textstyle\varepsilon $%
1883        \HOLOGO@Span{X}{$ \textstyle\chi $}%
1884        \hologo{TeX}%
1885      }%
1886    }%
1887  }%
1888 }

\HoLogoBkm@ExTeX
1889 \def\HoLogoBkm@ExTeX#1{%
1890   \HOLOGO@PfdDocUnicode{\#1{e}{E}x}{\textepsilon\textchi}%
1891   \hologo{TeX}%
1892 }

\HoLogoCss@ExTeX
1893 \def\HoLogoCss@ExTeX{%
1894   \Css{%
1895     span.HoLogo-ExTeX{%
1896       font-family: serif;%
1897     }%
1898   }%
1899   \Css{%
1900     span.HoLogo-ExTeX span.HoLogo-TeX{%
1901       margin-left: -.15em;%
1902     }%
1903   }%
1904   \global\let\HoLogoCss@ExTeX\relax
1905 }

```

2.9.23 MiKTeX

```

\HoLogo@MiKTeX
1906 \def\HoLogo@MiKTeX#1{%
1907   \HOLOGO@mbox{MiK}%
1908   \HOLOGO@discretionary
1909   \hologo{TeX}%
1910 }

```

```

\HoLogoHtml@MiKTeX
1911 \let\HoLogoHtml@MiKTeX\HoLogo@MiKTeX

```

2.9.24 OzTeX and friends

Source: OzTeX FAQ [6]:

```

\def\OzTeX{0\kern-.03em z\kern-.15em\TeX}
(There is no kerning in OzMF, OzMP and OzTtH.)

```

```

\HoLogo@OzTeX
1912 \def\HoLogo@OzTeX#1{%
1913   0%
1914   \kern-.03em %

```

```

1915  z%
1916  \kern-.15em %
1917  \hologo{TeX}%
1918 }

\HoLogoHtml@OzTeX
1919 \def\HoLogoHtml@OzTeX#1{%
1920   \HoLogoCss@OzTeX
1921   \HOLOGO@Span{OzTeX}{%
1922     0%
1923     \HOLOGO@Span{z}{z}%
1924     \hologo{TeX}%
1925   }%
1926 }

\HoLogoCss@OzTeX
1927 \def\HoLogoCss@OzTeX{%
1928   \Css{%
1929     span.HoLogo-OzTeX span.HoLogo-z{%
1930       margin-left:-.03em;%
1931       margin-right:-.15em;%
1932     }%
1933   }%
1934   \global\let\HoLogoCss@OzTeX\relax
1935 }

\HoLogo@OzMf
1936 \def\HoLogo@OzMf#1{%
1937   \HOLOGO@mbox{OzMf}%
1938 }

\HoLogo@OzMP
1939 \def\HoLogo@OzMP#1{%
1940   \HOLOGO@mbox{OzMP}%
1941 }

\HoLogo@OzTtH
1942 \def\HoLogo@OzTtH#1{%
1943   \HOLOGO@mbox{OzTtH}%
1944 }

```

2.9.25 PCTEX

```

\HoLogo@PCTeX
1945 \def\HoLogo@PCTeX#1{%
1946   \HOLOGO@mbox{PC}%
1947   \hologo{TeX}%
1948 }

\HoLogoHtml@PCTeX
1949 \let\HoLogoHtml@PCTeX\HoLogo@PCTeX

```

2.9.26 PICTEX

The original definitions from `pictex.tex` [7]:

```

\def\PiC{%
  P%
  \kern-.12em%
  \lower.5ex\hbox{I}%
  \kern-.075em%
  C%
}
\def\PiCTeX{%
  \PiC
  \kern-.11em%
  \TeX
}

\HoLogo@PiC
1950 \def\HoLogo@PiC#1{%
1951   P%
1952   \kern-.12em%
1953   \lower.5ex\hbox{I}%
1954   \kern-.075em%
1955   C%
1956   \HOLOGO@SpaceFactor
1957 }

\HoLogoHtml@PiC
1958 \def\HoLogoHtml@PiC#1{%
1959   \HoLogoCss@PiC
1960   \HOLOGO@Span{PiC}{%
1961     P%
1962     \HOLOGO@Span{i}{I}%
1963     C%
1964   }%
1965 }

\HoLogoCss@PiC
1966 \def\HoLogoCss@PiC{%
1967   \Css{%
1968     span.HoLogo-PiC span.HoLogo-i{%
1969       position:relative;%
1970       top:.5ex;%
1971       margin-left:-.12em;%
1972       margin-right:-.075em;%
1973       text-decoration:none;%
1974     }%
1975   }%
1976   \global\let\HoLogoCss@PiC\relax
1977 }

\HoLogo@PiCTeX
1978 \def\HoLogo@PiCTeX#1{%
1979   \hologo{PiC}%
1980   \HOLOGO@discretionary
1981   \kern-.11em%
1982   \hologo{TeX}%
1983 }

\HoLogoHtml@PiCTeX
1984 \def\HoLogoHtml@PiCTeX#1{%
1985   \HoLogoCss@PiCTeX

```

```

1986  \HOLOGO@Span{PiCTeX}{%
1987    \hologo{PiC}%
1988    \hologo{TeX}%
1989  }%
1990 }

\HoLogoCss@PiCTeX
1991 \def\HoLogoCss@PiCTeX{%
1992   \Css{%
1993     span.HoLogo-PiCTeX span.HoLogo-PiC{%
1994       margin-right:-.11em;%
1995     }%
1996   }%
1997   \global\let\HoLogoCss@PiCTeX\relax
1998 }

```

2.9.27 teTeX

```

\HoLogo@teTeX
1999 \def\HoLogo@teTeX#1{%
2000   \HOLOGO@mbox{\#1{t}{T}e}%
2001   \HOLOGO@discretionary
2002   \hologo{TeX}%
2003 }

\HoLogoCs@teTeX
2004 \def\HoLogoCs@teTeX#1{\#1{t}{T}dfTeX}

\HoLogoBkm@teTeX
2005 \def\HoLogoBkm@teTeX#1{%
2006   #1{t}{T}e\hologo{TeX}%
2007 }

\HoLogoHtml@teTeX
2008 \let\HoLogoHtml@teTeX\HoLogo@teTeX

```

2.9.28 TeX4ht

```

\HoLogo@TeX4ht
2009 \expandafter\def\csname HoLogo@TeX4ht\endcsname#1{%
2010   \HOLOGO@mbox{\hologo{TeX}4ht}%
2011 }

\HoLogoHtml@TeX4ht
2012 \expandafter
2013 \let\csname HoLogoHtml@TeX4ht\expandafter\endcsname
2014 \csname HoLogo@TeX4ht\endcsname

```

2.9.29 SageTeX

```

\HoLogo@sageTeX
2015 \def\HoLogo@sageTeX#1{%
2016   \HOLOGO@mbox{Sage}%
2017   \HOLOGO@discretionary
2018   \HOLOGO@NegativeKerning{eT,oT,To}%
2019   \hologo{TeX}%
2020 }

```

```
\HoLogoHtml@SageTeX
2021 \let\HoLogoHtml@SageTeX\HoLogo@SageTeX
```

2.10 METAFONT and friends

```
\HoLogo@METAFONT
2022 \def\HoLogo@METAFONT#1{%
2023   \HoLogoFont@font{METAFONT}{logo}{%
2024     \HOLOGO@mbox{META}%
2025     \HOLOGO@discretionary
2026     \HOLOGO@mbox{FONT}%
2027   }%
2028 }
```

```
\HoLogo@METAPOST
2029 \def\HoLogo@METAPOST#1{%
2030   \HoLogoFont@font{METAPOST}{logo}{%
2031     \HOLOGO@mbox{META}%
2032     \HOLOGO@discretionary
2033     \HOLOGO@mbox{POST}%
2034   }%
2035 }
```

```
\HoLogo@MetaFun
2036 \def\HoLogo@MetaFun#1{%
2037   \HOLOGO@mbox{Meta}%
2038   \HOLOGO@discretionary
2039   \HOLOGO@mbox{Fun}%
2040 }
```

```
\HoLogo@MetaPost
2041 \def\HoLogo@MetaPost#1{%
2042   \HOLOGO@mbox{Meta}%
2043   \HOLOGO@discretionary
2044   \HOLOGO@mbox{Post}%
2045 }
```

2.11 Others

2.11.1 biber

```
\HoLogo@biber
2046 \def\HoLogo@biber#1{%
2047   \HOLOGO@mbox{\#1{b}{B}i}%
2048   \HOLOGO@discretionary
2049   \HOLOGO@mbox{ber}%
2050 }
```

```
\HoLogoCs@biber
2051 \def\HoLogoCs@biber#1{\#1{b}{B}iber}
```

```
\HoLogoBkm@biber
2052 \def\HoLogoBkm@biber#1{%
2053   \#1{b}{B}iber%
2054 }
```

```
\HoLogoHtml@biber
2055 \let\HoLogoHtml@biber\HoLogo@biber
```

2.11.2 KOMA-Script

\HoLogo@KOMAScript The definition for KOMA-Script is taken from KOMA-Script (`scrlogo.dtx`, reformatted) [8]:

```

2054 \@ifundefined{KOMAScript}{%
2055   \DeclareRobustCommand{\KOMAScript}{%
2056     \textsf{%
2057       K\kern.05em O\kern.05emM\kern.05em A%
2058       \kern.1em-\kern.1em %
2059       Script%
2060     }%
2061   }%
2062 }{%
2063   }%
2064   \kern.1em%
2065   \HOLOGO@hyphen
2066   \kern.1em%
2067   \HOLOGO@mbox{Script}%
2068 }%
2069 }

\HoLogoBkm@KOMAScript
2070 \def\HoLogoBkm@KOMAScript#1{%
2071   KOMA-Script%
2072 }

\HoLogoHtml@KOMAScript
2073 \def\HoLogoHtml@KOMAScript#1{%
2074   \HoLogoCss@KOMAScript
2075   \HoLogoFont@font{KOMAScript}{sf}{%
2076     \HOLOGO@Span{KOMAScript}{%
2077       K%
2078       \HOLOGO@Span{O}{O}%
2079       M%
2080       \HOLOGO@Span{A}{A}%
2081       \HOLOGO@Span{hyphen}{-}%
2082       Script%
2083     }%
2084   }%
2085 }

\HoLogoCss@KOMAScript
2086 \def\HoLogoCss@KOMAScript{%
2087   \Css{%
2088     span.HoLogo-KOMAScript{%
2089       font-family:sans-serif;%
2090     }%
2091   }%
2092   \Css{%
2093     span.HoLogo-KOMAScript span.HoLogo-O{%

```

```

2094     padding-left:.05em;%
2095     padding-right:.05em;%
2096   }%
2097 }%
2098 \Css{%
2099   span.HoLogo-KOMAScript span.HoLogo-A{%
2100     padding-left:.05em;%
2101   }%
2102 }%
2103 \Css{%
2104   span.HoLogo-KOMAScript span.HoLogo-hyphen{%
2105     padding-left:.1em;%
2106     padding-right:.1em;%
2107   }%
2108 }%
2109 \global\let\HoLogoCss@KOMAScript\relax
2110 }

```

2.11.3 LyX

\HoLogo@LyX The definition is taken from the documentation source files of LyX, Intro.lyx [5]:

```

\def\LyX{%
  \texorpdfstring{%
    L\kern-.1667em\lower.25em\hbox{Y}\kern-.125emX\@%
  }{%
    LyX%
  }%
}

2111 \def\HoLogo@LyX#1{%
2112   L%
2113   \kern-.1667em%
2114   \lower.25em\hbox{Y}%
2115   \kern-.125em%
2116   X%
2117   \HOLOGO@SpaceFactor
2118 }

\HoLogoHtml@LyX
2119 \def\HoLogoHtml@LyX#1{%
2120   \HoLogoCss@LyX
2121   \HOLOGO@Span{LyX}{%
2122     L%
2123     \HOLOGO@Span{y}{Y}%
2124     X%
2125   }%
2126 }

\HoLogoCss@LyX
2127 \def\HoLogoCss@LyX{%
2128   \Css{%
2129     span.HoLogo-LyX span.HoLogo-y{%
2130       position:relative;%
2131       top:.25em;%
2132       margin-left:-.1667em;%
2133       margin-right:-.125em;%
2134       text-decoration:none;%
2135     }%

```

```

2136  }%
2137  \global\let\HoLogoCss@LyX\relax
2138 }

```

2.11.4 \mathcal{NTS}

\HoLogo@NTS Definition for \mathcal{NTS} can be found in package etex_man for the ε -TeX manual [3] and in package dtklogos [2]:

```

\def\NTS{%
  \leavevmode
  \hbox{%
    $%
    \cal N%
    \kern-0.35em%
    \lower0.5ex\hbox{$\cal T$}%
    \kern-0.2em%
    S%
    $%
  }%
}

2139 \def\HoLogo@NTS#1{%
2140   \HoLogoFont@font{NTS}{sy}{%
2141     N/%
2142     \kern-.35em%
2143     \lower.5ex\hbox{T}/%
2144     \kern-.2em%
2145     S/%
2146   }%
2147   \HOLOGO@SpaceFactor
2148 }

```

2.11.5 $T_{\text{T}}H$ (\TeX to HTML translator)

Source: <http://hutchinson.belmont.ma.us/tth/> In the HTML source the second ‘T’ is printed as subscript.

$T<\sub>T</sub>H$

```

\HoLogo@TTH
2149 \def\HoLogo@TTH#1{%
2150   \ltx@mbox{%
2151     T\HOLOGO@SubScript{T}H%
2152   }%
2153   \HOLOGO@SpaceFactor
2154 }

```

```

\HoLogoHtml@TTH
2155 \def\HoLogoHtml@TTH#1{%
2156   T\HCode{<sub>}T\HCode{</sub>}H%
2157 }

```

2.11.6 Hán Thé Thành

Partial source: Package dtklogos. The double accent is U+1EBF (latin small letter e with circumflex and acute).

```

\HoLogo@HanTheThanh
2158 \def\HoLogo@HanTheThanh#1{%
2159   \ltx@mbox{H\`an}%
2160   \HOLOGO@space
2161   \ltx@mbox{%
2162     Th%
2163     \HOLOGO@IfCharExists{"1EBF}{%
2164       \char"1EBF\relax
2165     }{%
2166       ^e\hbox to .5ex{\hss\raise .5ex\hbox{\vbox{}{}}}}%
2167     }%
2168   }%
2169   \HOLOGO@space
2170   \ltx@mbox{Th\`anh}%
2171 }

```

```

\HoLogoBkm@HanTheThanh
2172 \def\HoLogoBkm@HanTheThanh#1{%
2173   H\`an %
2174   Th\HOLOGO@PfdDocUnicode{\^e}{\9036\277} %
2175   Th\`anh%
2176 }

```

```

\HoLogoHtml@HanTheThanh
2177 \def\HoLogoHtml@HanTheThanh#1{%
2178   H\`an %
2179   Th\HCode{&\ltx@hashchar x1ebf;} %
2180   Th\`anh%
2181 }

```

2.12 Driver detection

```

2182 \HOLOGO@IfExists\InputIfFileExists{%
2183   \InputIfFileExists{hologo.cfg}{}{}%
2184 }{%
2185   \ltx@ifundefined{pdf@filesize}{%
2186     \def\HOLOGO@InputIfExists{%
2187       \openin\HOLOGO@temp=hologo.cfg\relax
2188       \ifeof\HOLOGO@temp
2189         \closein\HOLOGO@temp
2190       \else
2191         \closein\HOLOGO@temp
2192         \begingroup
2193           \def\x{LaTeX2e}%
2194           \expandafter\endgroup
2195           \ifx\fmtname\x
2196             \input{hologo.cfg}%
2197           \else
2198             \input hologo.cfg\relax
2199           \fi
2200         \fi
2201     }%
2202     \ltx@ifundefined{newread}{%
2203       \chardef\HOLOGO@temp=15 %
2204       \def\HOLOGO@CheckRead{%
2205         \ifeof\HOLOGO@temp
2206           \HOLOGO@InputIfExists
2207         \else

```

```

2208      \ifcase\HOLOGO@temp
2209          \@PackageWarningNoLine{hologo}{%
2210              Configuration file ignored, because\MessageBreak
2211              a free read register could not be found%
2212          }%
2213      \else
2214          \begingroup
2215              \count\ltx@cclv=\HOLOGO@temp
2216              \advance\ltx@cclv by \ltx@minusone
2217              \edef\x{\endgroup
2218                  \chardef\noexpand\HOLOGO@temp=\the\count\ltx@cclv
2219                  \relax
2220              }%
2221              \x
2222              \fi
2223              \fi
2224          }%
2225      }{%
2226          \csname newread\endcsname\HOLOGO@temp
2227          \HOLOGO@InputIfExists
2228      }%
2229  }{%
2230      \edef\HOLOGO@temp{\pdf@filesize{hologo.cfg}}%
2231      \ifx\HOLOGO@temp\ltx@empty
2232          \else
2233              \ifnum\HOLOGO@temp>0 %
2234                  \begingroup
2235                      \def\x{LaTeX2e}%
2236                      \expandafter\endgroup
2237                      \ifx\fmtname\x
2238                          \input{hologo.cfg}%
2239                      \else
2240                          \input hologo.cfg\relax
2241                      \fi
2242                  \else
2243                      \@PackageInfoNoLine{hologo}{%
2244                          Empty configuration file ‘hologo.cfg’ ignored%
2245                      }%
2246                  \fi
2247              \fi
2248  }%
2249 }

2250 \def\HOLOGO@temp#1#2{%
2251     \kv@define@key{HoLogoDriver}{#1}[]{%
2252         \begingroup
2253             \def\HOLOGO@temp{##1}%
2254             \ltx@onelvel@sanitize\HOLOGO@temp
2255             \ifx\HOLOGO@temp\ltx@empty
2256                 \else
2257                     \@PackageError{hologo}{%
2258                         Value (\HOLOGO@temp) not permitted for option ‘#1’%
2259                     }%
2260                     \ehc
2261                 \fi
2262             \endgroup
2263             \def\hologoDriver{#2}%
2264     }%
2265 }%

```

```

2266 \def\HOLOGO@@temp#1#2{%
2267   \ifx\kv@value\relax
2268     \HOLOGO@@temp{#1}{#1}%
2269   \else
2270     \HOLOGO@@temp{#1}{#2}%
2271   \fi
2272 }%
2273 \kv@parse@normalized{%
2274   pdftex,%
2275   luatex=pdftex,%
2276   dvipdfm,%
2277   dvipdfmx=dvipdfm,%
2278   dvips,%
2279   dvipsone=dvips,%
2280   xdvi=dvips,%
2281   xetex,%
2282   vtex,%
2283 }\HOLOGO@@temp
2284 \kv@define@key{HoLogoDriver}{driverfallback}{%
2285   \def\HOLOGO@DriverFallback{#1}%
2286 }
\HOLOGO@DriverFallback
2287 \def\HOLOGO@DriverFallback{dvips}

\hologoDriverSetup
2288 \def\hologoDriverSetup{%
2289   \let\hologoDriver\ltx@undefined
2290   \HOLOGO@DriverSetup
2291 }

\HOLOGO@DriverSetup
2292 \def\HOLOGO@DriverSetup#1{%
2293   \kvsetkeys{HoLogoDriver}{#1}%
2294   \HOLOGO@CheckDriver
2295   \ltx@ifundefined{hologoDriver}{%
2296     \begingroup
2297     \edef\x{\endgroup
2298       \noexpand\kvsetkeys{HoLogoDriver}{\HOLOGO@DriverFallback}%
2299     }\x
2300   }{}%
2301   \PackageInfoNoLine{hologo}{Using driver '\hologoDriver'}%
2302 }

\HOLOGO@CheckDriver
2303 \def\HOLOGO@CheckDriver{%
2304   \ifpdf
2305     \def\hologoDriver{pdftex}%
2306     \let\HOLOGO@pdfliteral\pdfliteral
2307     \ifluatex
2308       \ifx\pdfextension\undefined\else
2309         \protected\def\pdfliteral{\pdfextension literal}%
2310         \let\HOLOGO@pdfliteral\pdfliteral
2311       \fi
2312       \ltx@ifUndefined{\HOLOGO@pdfliteral}{%
2313         \ifnum\luatexversion<36 %
2314         \else
2315           \begingroup

```

```

2316      \let\HOLOGO@temp\endgroup
2317      \ifcase0%
2318          \directlua{%
2319              if tex.enableprimitives then %
2320                  tex.enableprimitives('HOLOGO@', {'pdfliteral'})%
2321              else %
2322                  tex.print('1')%
2323              end%
2324          }%
2325          \ifx\HOLOGO@pdfliteral@\undefined 1\fi%
2326          \relax%
2327      \endgroup
2328      \let\HOLOGO@temp\relax
2329      \global\let\HOLOGO@pdfliteral\HOLOGO@pdfliteral
2330      \fi%
2331      \HOLOGO@temp
2332      \fi
2333  }{}%
2334  \fi
2335  \ltx@ifundefined{HOLOGO@pdfliteral}{}{%
2336      \@PackageWarning{hologo}{%
2337          Cannot find \string\pdfliteral
2338      }%
2339  }{}%
2340 \else
2341     \ifxetex
2342         \def\hologoDriver{xetex}%
2343     \else
2344         \ifvtex
2345             \def\hologoDriver{vtex}%
2346         \fi
2347     \fi
2348 \fi
2349 }

```

HOLOGO@WarningUnsupportedDriver

```

2350 \def\HOLOGO@WarningUnsupportedDriver#1{%
2351     \@PackageWarning{hologo}{%
2352         Logo '#1' needs driver specific macros,\MessageBreak
2353         but driver '\hologoDriver' is not supported.\MessageBreak
2354         Use a different driver or\MessageBreak
2355         load package 'graphics' or 'pgf'%
2356     }%
2357 }

```

2.12.1 Reflect box macros

Skip driver part if not needed.

```

2358 \ltx@ifundefined{reflectbox}{}{%
2359     \ltx@ifundefined{rotatebox}{}{%
2360         \HOLOGO@AtEnd
2361     }%
2362 }
2363 \ltx@ifundefined{pgftext}{}{%
2364     \HOLOGO@AtEnd
2365 }
2366 \ltx@ifundefined{psscalebox}{}{%
2367     \HOLOGO@AtEnd

```

```

2368 }

2369 \def\HOLOGO@temp{LaTeX2e}
2370 \ifx\fmtname\HOLOGO@temp
2371   \RequirePackage{kvoptions}[2011/06/30]%
2372   \ProcessKeyvalOptions{HoLogoDriver}%
2373 \fi
2374 \HOLOGO@DriverSetup{}

\HOLOGO@ReflectBox

2375 \def\HOLOGO@ReflectBox#1{%
2376   \begingroup
2377   \setbox\ltx@zero\hbox{\begingroup#1\endgroup}%
2378   \setbox\ltx@two\hbox{%
2379     \kern\wd\ltx@zero
2380     \csname HOLOGO@ScaleBox@\hologoDriver\endcsname{-1}{1}{%
2381       \hbox to \Opt{\copy\ltx@zero\hss}%
2382     }%
2383   }%
2384   \wd\ltx@two=\wd\ltx@zero
2385   \box\ltx@two
2386 \endgroup
2387 }

\HOLOGO@PointReflectBox

2388 \def\HOLOGO@PointReflectBox#1{%
2389   \begingroup
2390   \setbox\ltx@zero\hbox{\begingroup#1\endgroup}%
2391   \setbox\ltx@two\hbox{%
2392     \kern\wd\ltx@zero
2393     \raise\ht\ltx@zero\hbox{%
2394       \csname HOLOGO@ScaleBox@\hologoDriver\endcsname{-1}{-1}{%
2395         \hbox to \Opt{\copy\ltx@zero\hss}%
2396       }%
2397     }%
2398   }%
2399   \wd\ltx@two=\wd\ltx@zero
2400   \box\ltx@two
2401 \endgroup
2402 }

```

We must define all variants because of dynamic driver setup.

```
2403 \def\HOLOGO@temp#1#2{#2}
```

```
\HOLOGO@ScaleBox@pdftex

2404 \HOLOGO@temp{pdftex}{%
2405   \def\HOLOGO@ScaleBox@pdftex#1#2#3{%
2406     \HOLOGO@pdfliteral{%
2407       q #1 0 0 #2 0 0 cm%
2408     }%
2409     #3%
2410     \HOLOGO@pdfliteral{%
2411       Q%
2412     }%
2413   }%
2414 }
```

```
\HOLOGO@ScaleBox@dvips
```

```

2415 \HOLOGO@temp{dvips}{%
2416   \def\HOLOGO@ScaleBox@dvips#1#2#3{%
2417     \special{ps:}%
2418     gsave %
2419     currentpoint %
2420     currentpoint translate %
2421     #1 #2 scale %
2422     neg exch neg exch translate%
2423   }%
2424   #3%
2425   \special{ps:}%
2426     currentpoint %
2427     grestore %
2428     moveto%
2429   }%
2430 }%
2431 }

\HOLOGO@ScaleBox@dvipdfm
2432 \HOLOGO@temp{dvipdfm}{%
2433   \let\HOLOGO@ScaleBox@dvipdfm\HOLOGO@ScaleBox@dvips
2434 }

Since XHTEX v0.6.

\HOLOGO@ScaleBox@xetex
2435 \HOLOGO@temp{xetex}{%
2436   \def\HOLOGO@ScaleBox@xetex#1#2#3{%
2437     \special{x:gsave}%
2438     \special{x:scale #1 #2}%
2439     #3%
2440     \special{x:grestore}%
2441   }%
2442 }

\HOLOGO@ScaleBox@vtx
2443 \HOLOGO@temp{vtx}{%
2444   \def\HOLOGO@ScaleBox@vtx#1#2#3{%
2445     \special{r(#1,0,0,#2,0,0)}%
2446     #3%
2447     \special{r})}%
2448   }%
2449 }

2450 \HOLOGO@AtEnd%
2451 </package>

```

3 Test

3.1 Catcode checks for loading

```

2452 /*test1*/
2453 \catcode`{\=1 %
2454 \catcode`{\}=2 %
2455 \catcode`\#=6 %
2456 \catcode`\@=11 %
2457 \expandafter\ifx\csname count@\endcsname\relax

```

```

2458 \countdef\count@=255 %
2459 \fi
2460 \expandafter\ifx\csname @gobble\endcsname\relax
2461   \long\def\@gobble#1{}%
2462 \fi
2463 \expandafter\ifx\csname @firstofone\endcsname\relax
2464   \long\def\@firstofone#1{#1}%
2465 \fi
2466 \expandafter\ifx\csname loop\endcsname\relax
2467   \expandafter\@firstofone
2468 \else
2469   \expandafter\@gobble
2470 \fi
2471 {%
2472   \def\loop#1\repeat{%
2473     \def\body{#1}%
2474     \iterate
2475   }%
2476   \def\iterate{%
2477     \body
2478     \let\next\iterate
2479   \else
2480     \let\next\relax
2481   \fi
2482   \next
2483 }%
2484 \let\repeat=\fi
2485 }%
2486 \def\RestoreCatcodes(){}
2487 \count@=0 %
2488 \loop
2489   \edef\RestoreCatcodes{%
2490     \RestoreCatcodes
2491     \catcode\the\count@=\the\catcode\count@\relax
2492   }%
2493 \ifnum\count@<255 %
2494   \advance\count@ 1 %
2495 \repeat
2496
2497 \def\RangeCatcodeInvalid#1#2{%
2498   \count@=#1\relax
2499   \loop
2500     \catcode\count@=15 %
2501   \ifnum\count@<#2\relax
2502     \advance\count@ 1 %
2503   \repeat
2504 }
2505 \def\RangeCatcodeCheck#1#2#3{%
2506   \count@=#1\relax
2507   \loop
2508     \ifnum#3=\catcode\count@
2509     \else
2510       \errmessage{%
2511         Character \the\count@\space
2512         with wrong catcode \the\catcode\count@\space
2513         instead of \number#3%
2514     }%
2515   \fi

```

```

2516 \ifnum\count@<#2\relax
2517   \advance\count@ 1 %
2518   \repeat
2519 }
2520 \def\space{ }
2521 \expandafter\ifx\csname LoadCommand\endcsname\relax
2522   \def\LoadCommand{\input hologo.sty\relax}%
2523 \fi
2524 \def\Test{%
2525   \RangeCatcodeInvalid{0}{47}%
2526   \RangeCatcodeInvalid{58}{64}%
2527   \RangeCatcodeInvalid{91}{96}%
2528   \RangeCatcodeInvalid{123}{255}%
2529   \catcode`\@=12 %
2530   \catcode`\\=0 %
2531   \catcode`\%=14 %
2532   \LoadCommand
2533   \RangeCatcodeCheck{0}{36}{15}%
2534   \RangeCatcodeCheck{37}{37}{14}%
2535   \RangeCatcodeCheck{38}{47}{15}%
2536   \RangeCatcodeCheck{48}{57}{12}%
2537   \RangeCatcodeCheck{58}{63}{15}%
2538   \RangeCatcodeCheck{64}{64}{12}%
2539   \RangeCatcodeCheck{65}{90}{11}%
2540   \RangeCatcodeCheck{91}{91}{15}%
2541   \RangeCatcodeCheck{92}{92}{0}%
2542   \RangeCatcodeCheck{93}{96}{15}%
2543   \RangeCatcodeCheck{97}{122}{11}%
2544   \RangeCatcodeCheck{123}{255}{15}%
2545   \RestoreCatcodes
2546 }
2547 \Test
2548 \csname @@end\endcsname
2549 \end
2550 
```

3.2 Spacefactor

The space factor must be 1000 after a logo. If it is greater 1000 then the following space is a space after a sentence closing point. If the space factor is smaller 1000 then an immediate following dot is interpreted as abbreviation, not sentence closing point.

```

2551 <*test-spacefactor>
2552 \NeedsTeXFormat{LaTeX2e}
2553 \documentclass{article}
2554 \usepackage{hologo}[2016/05/16]
2555 \usepackage{kvsetkeys}
2556 \usepackage{qstest}
2557 \IncludeTests{*}
2558 \LogTests{log}{*}{*}
2559 \begin{document}
2560 \begin{qstest}{spacefactor}{spacefactor}
2561 \newcommand*\Test[1]{%
2562   \sbox0{%
2563     \hologo{#1}%
2564     \Expect*{1000 (#1)}*\the\spacefactor\space(#1)%
2565   }%
2566 }%

```

```

2567 \makeatletter
2568 \def\TestList{}
2569 \def\hologoEntry#1#2#3{%
2570   \edef\TestList{%
2571     \ifx\TestList\empty
2572     \else
2573       \TestList,%
2574     \fi
2575     #1%
2576     \ifx\#2\%
2577     \else
2578       ={variant=#2}%
2579     \fi
2580   }%
2581 }
2582 \hologoList
2583 \expandafter\kv@parse@normalized\expandafter{%
2584   \TestList
2585 }{%
2586   \begingroup
2587     \let\@logo=\kv@key
2588     \ifx\kv@value\relax
2589     \else
2590       \expandafter\hologoLogoSetup\expandafter\@logo\expandafter{%
2591         \kv@value
2592       }%
2593     \fi
2594     \Test\@logo
2595   \endgroup
2596   \@gobbletwo
2597 }
2598 \end{qstest}
2599 \end{document}
2600 </test-spacefactor>

```

3.3 Complete list

```

2601 (*test-list)
2602 \NeedsTeXFormat{LaTeX2e}
2603 \documentclass[12pt,a4paper]{article}
2604 \usepackage{hologo}[2016/05/16]
2605 \usepackage[T1]{fontenc}
2606 \usepackage{lmodern}
2607 \usepackage{parskip}
2608 \usepackage[unicode]{hyperref}[2011/09/28]
2609 \usepackage{bookmark}[2011/09/19]
2610 \bookmarksetup{%
2611   numbered,%
2612   open,%
2613   openlevel=2,%
2614 }
2615 \renewcommand*\contentsname{List of logos}
2616 \begin{document}
2617 \tableofcontents
2618 \def\TestFont#1#2#3#4#5#6{%
2619   \begingroup
2620     \usefont{#3}{#4}{#5}{#6}%
2621     \HologoVariant{#1}{#2}/\hologoVariant{#1}{#2}%

```

```

2622     \quad
2623     \begingroup\scriptsize\hologoVariant{\#1}{\#2}\endgroup
2624     \quad
2625   \endgroup
2626   (#3/#4/#5/#6)%
2627   \par
2628 }
2629 \makeatletter
2630 \def\hologoEntry#1#2#3{%
2631   \section{%
2632     \HologoVariant{\#1}{\#2}/\hologoVariant{\#1}{\#2} %
2633     {[#1\ifx\\#2\\\else\space(#2)\fi]}% hash-ok
2634   }% braces around [] because of bug in tex4ht
2635   \begingroup
2636     \hypersetup{unicode=false}%
2637     \bookmark[%
2638       dest=\@currentHref,%  

2639       rellevel=1,%  

2640       keeplevel,%  

2641     ]{%
2642       \HologoVariant{\#1}{\#2}/\hologoVariant{\#1}{\#2} %
2643       (PDFDocEncoding)%  

2644     }%
2645   \endgroup
2646   \TestFont{\#1}{\#2}{OT1}{cmr}{m}{n}%
2647   \TestFont{\#1}{\#2}{OT1}{cmss}{m}{n}%
2648   \TestFont{\#1}{\#2}{OT1}{cmr}{b}{n}%
2649   \TestFont{\#1}{\#2}{OT1}{cmr}{m}{it}%
2650   \TestFont{\#1}{\#2}{OT1}{cmtt}{m}{n}%
2651   \TestFont{\#1}{\#2}{T1}{lmr}{m}{n}%
2652   \TestFont{\#1}{\#2}{T1}{lmss}{m}{n}%
2653   \TestFont{\#1}{\#2}{T1}{lmr}{b}{n}%
2654   \TestFont{\#1}{\#2}{T1}{lmr}{m}{it}%
2655   \TestFont{\#1}{\#2}{T1}{lmitt}{m}{n}%
2656   \TestFont{\#1}{\#2}{T1}{lmvtt}{m}{n}%
2657   \TestFont{\#1}{\#2}{T1}{qtm}{m}{n}%
2658   \TestFont{\#1}{\#2}{T1}{qhv}{m}{n}%
2659   \TestFont{\#1}{\#2}{T1}{qtm}{b}{n}%
2660   \TestFont{\#1}{\#2}{T1}{qtm}{m}{it}%
2661   \TestFont{\#1}{\#2}{T1}{qcr}{m}{n}%
2662   \newpage
2663 }
2664 \makeatother
2665 \hologoList
2666 \end{document}
2667 </test-list>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

CTAN:macros/latex/contrib/oberdiek/hologo.dtx The source file.

CTAN:macros/latex/contrib/oberdiek/hologo.pdf Documentation.

¹<http://ctan.org/pkg/hologo>

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for *TEX* Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDSScripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain *TEX*:

```
tex hologo.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>hologo.sty</code>	→ <code>tex/generic/oberdiek/hologo.sty</code>
<code>hologo.pdf</code>	→ <code>doc/latex/oberdiek/hologo.pdf</code>
<code>example/hologo-example.tex</code>	→ <code>doc/latex/oberdiek/example/hologo-example.tex</code>
<code>test/hologo-test1.tex</code>	→ <code>doc/latex/oberdiek/test/hologo-test1.tex</code>
<code>test/hologo-test-spacefactor.tex</code>	→ <code>doc/latex/oberdiek/test/hologo-test-spacefactor.tex</code>
<code>test/hologo-test-list.tex</code>	→ <code>doc/latex/oberdiek/test/hologo-test-list.tex</code>
<code>hologo.dtx</code>	→ <code>source/latex/oberdiek/hologo.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your *TEX* distribution (te*TEX*, mik*TEX*, ...) relies on file name databases, you must refresh these. For example, te*TEX* users run `texhash` or `mktextslr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk hologo.pdf unpack_files output .
```

Unpacking with L^AT_EX. The .dtx chooses its action depending on the format:

plain T_EX: Run docstrip and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for docstrip (really, docstrip does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{hologo.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the .dtx or the .drv to generate the documentation. The process can be configured by the configuration file ltxdoc.cfg. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex hologo.dtx
makeindex -s gind.ist hologo.idx
pdflatex hologo.dtx
makeindex -s gind.ist hologo.idx
pdflatex hologo.dtx
```

5 Catalogue

The following XML file can be used as source for the **T_EX Catalogue**. The elements **caption** and **description** are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is **hologo.xml**.

```
2668 (*catalogue)
2669 <?xml version='1.0' encoding='us-ascii'?>
2670 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
2671 <entry datestamp='$Date$' modifier='$Author$' id='hologo'>
2672   <name>hologo</name>
2673   <caption>A collection of logos with bookmark support.</caption>
2674   <authorref id='auth:oberdiek' />
2675   <copyright owner='Heiko Oberdiek' year='2010-2012' />
2676   <license type='lppl1.3' />
2677   <version number='1.10' />
2678   <description>
2679     The package defines a single command <tt>\hologo</tt>, whose
2680     argument is the usual case-confused ASCII version of the logo.
2681     The command is bookmark-enabled, so that every logo becomes
2682     available in bookmarks without further work.
2683     <p/>
2684     The package is part of the <xref refid='oberdiek'>oberdiek</xref>
2685     bundle.
2686   </description>
2687   <documentation details='Package documentation'
2688     href='ctan:/macros/latex/contrib/oberdiek/hologo.pdf' />
2689   <ctan file='true' path='/macros/latex/contrib/oberdiek/hologo.dtx' />
2690   <miktex location='oberdiek' />
2691   <texlive location='oberdiek' />
2692   <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip' />
2693 </entry>
2694 </catalogue>
```

6 References

- [1] Oren Patashnik, *BIBTEXing*, 1988-02-08.
CTAN:biblio/bibtex/base/
- [2] Gerd Neugebauer, DANTE, *Package dtklogos*, 2011-04-25.
CTAN:usergrps/dante/dtk/dtklogos.sty
- [3] The $\mathcal{N}\mathcal{T}\mathcal{S}$ Team, *The ε -TEX manual*, 1998-02.
CTAN:systems/e-tex/v2/doc/
- [4] The ε_X TEX group, *ε_X TEX: FAQ – How is ε_X TEX typeset?*, 2007-04-14.
<http://www.extex.org/documentation/faq.html>
- [5] @MISC LyX, title = LyX 2.0.0 – The Document Processor [Computer software and manual], author = The LyX Team, howpublished = Internet: <http://www.lyx.org>, year = 2011-05-08, note = Retrieved May 10, 2011, from <http://www.lyx.org>, url = <http://www.lyx.org/> The LyX Team, *LyX – The Document Processor*, 2011-05-08.
<http://www.lyx.org/>
- [6] Andrew Trevorrow, OzTEX FAQ: What is the correct way to typeset “OzTEX”? , 2011-09-15 (visited).
<http://www.trevorrow.com/oztex/ozfaq.html#oztex-logo>
- [7] Michael Wichura, *The PICTEX macro package*, 1987-09-21.
CTAN:graphics/pictex/
- [8] Markus Kohm, *KOMA-Script Datei scrlogo.dtx*, 2009-01-30.
CTAN:install/macros/latex/contrib/komascript.tds.zip

7 History

[2010/04/08 v1.0]

- The first version.

[2010/04/16 v1.1]

- \Hologo added for support of logos at start of a sentence.
- \hologoSetup and \hologoLogoSetup added.
- Options break, hyphenbreak, spacebreak added.
- Variant support added by option variant.

[2010/04/24 v1.2]

- LATEX3 added.
- VTEX added.

[2010/11/21 v1.3]

- iniTEX, virTEX added.

[2011/03/25 v1.4]

- ConTEXt with variants added.
- Option `discretionarybreak` added as refinement for option `break`.

[2011/04/21 v1.5]

- Wrong TDS directory for test files fixed.

[2011/10/01 v1.6]

- Support for package `tex4ht` added.
- Support for `\csname` added if `\ifin csname` is available.
- New logos: (L)TeX, biber, BiBTeX (sc, sf), emTeX, ε_XTeX, KOMA-Script, I^A, LYX, MiKTeX, NTS, OzMF, OzMP, OzTeX, OzTtH, PCTeX, PiC, PiCTeX, METAFONT, MetaFun, METAPOST, MetaPost, SLiTEx (lift, narrow, simple), SLiTEx (narrow, simple, lift), teTeX.
- Fixes: iniTeX, pdfIATeX, pdfTeX, virTeX.
- `\holoFontSetup` and `\holoLogoFontSetup` added.
- `\holoVariant` and `\HoloVariant` added.

[2011/11/22 v1.7]

- New logos: BiBTeX8, IATEXML, SageTeX, TeX4ht, TTH.
- X_E and friends: Driver stuff fixed.
- X_E and friends: Support for italic added.
- X_E and friends: Package support for pgf and pstricks added.

[2011/11/29 v1.8]

- New logos: H_Àn Th_È Thành.

[2011/12/21 v1.9]

- Patch for package ifxetex added for the case that `\newif` is undefined in iniTeX.
- Some fixes for iniTeX.

[2012/04/26 v1.10]

- Fix in bookmark version of logo “H_Àn Th_È Thành”.

[2016/05/12 v1.11]

- Update HOLOGO@IfCharExists (previously in texlive)
- define pdfliteral in current luatex.

[2016/05/16 v1.12]

- Documentation updates.

8 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	\box 1529, 1542, 2385, 2400
\#	2455
\\$ 804, 1141, 1144, 1152, 1246, 1249, 1257	
\% 1078, 1121, 2531	
\& 1142, 1145, 1153, 1247, 1250, 1258	
\' 2166	
\- 519	
\/ 2141, 2143, 2145	
\@ 2456, 2529	
\@PackageError	
. 369, 402, 440, 452, 635,	
658, 665, 817, 849, 1547, 1589, 2257	
\@PackageInfoNoLine 2243, 2301	
\@PackageWarning 539	
\@PackageWarningNoLine	
. 2209, 2336, 2351	
\@currentHref 2638	
\@ehc 371, 405, 444, 454, 637,	
661, 668, 819, 851, 1547, 1589, 2260	
\@empty 2571	
\@firstofone 2464, 2467	
\@gobble 2461, 2469	
\@gobbletwo 2596	
\@logo 2587, 2590, 2594	
\@nil 911	
\@undefined	
. 180, 352, 449, 693, 2308, 2325	
\\" 33, 48, 50, 51, 52,	
53, 54, 61, 72, 79, 2530, 2576, 2633	
\{ 2453	
\} 2454	
\^ 1140, 1245, 1486, 2166, 2174	
\` 2159, 2170, 2173, 2175, 2178, 2180	
Numbers	C
\2 2174	\catcode 124, 125, 127, 128,
\9 2174	129, 130, 131, 132, 133, 134,
_ 52, 53, 54	135, 155, 156, 158, 159, 160,
	161, 162, 163, 164, 165, 166,
	167, 168, 169, 170, 171, 191,
	192, 194, 195, 196, 200, 201,
	202, 203, 204, 205, 206, 209,
	210, 212, 213, 214, 215, 219,
	221, 708, 710, 804, 1141, 1142,
	1144, 1145, 1152, 1153, 1246,
	1247, 1249, 1250, 1257, 1258,
	2453, 2454, 2455, 2456, 2491,
	2500, 2508, 2512, 2529, 2530, 2531
	\char 1448, 1501, 2164
	\chardef 381, 386, 388, 395,
	397, 414, 415, 416, 418, 421,
	424, 473, 475, 479, 490, 492,
	496, 508, 510, 514, 524, 526,
	1503, 1510, 1513, 1516, 1519,
	1555, 1558, 1561, 1564, 2203, 2218
	\check@mathfonts 1046
	\chi 1883
	\closein 2189, 2191
	\comma@entry 922
	\comma@parse@normalized 920
	\contentsname 2615
	\copy 2381, 2395
	\count 2215, 2218
	\count@ 2458, 2487, 2491, 2493,
	2494, 2498, 2500, 2501, 2502,
	2506, 2508, 2511, 2512, 2516, 2517
	\countdef 2458
	\csname 136, 143, 172, 188,
	198, 321, 324, 336, 381, 386,
	388, 395, 397, 419, 420, 422,
	423, 425, 427, 449, 457, 467,
	476, 480, 493, 497, 511, 515,
	527, 544, 547, 552, 555, 582,
	717, 727, 738, 748, 762, 772,
	787, 797, 824, 831, 856, 863,
	912, 1044, 1094, 1096, 1108,
	1186, 1188, 1190, 1192, 1193,
	1197, 1202, 1203, 1450, 1452,
	1801, 1805, 1810, 1811, 2009,
	2013, 2014, 2226, 2380, 2394,
	2457, 2460, 2463, 2466, 2521, 2548
	\css 987, 995, 1072, 1110, 1115, 1124,
	1171, 1176, 1317, 1323, 1373,
	1380, 1604, 1626, 1646, 1700,

1747, 1754, 1786, 1792, 1834, 1839, 1894, 1899, 1928, 1967, 1992, 2087, 2092, 2098, 2103, 2128	\hline 49, 113 \Hologo 4, 72, 79, 86, 109, 733, 781 \hologo 3, 72, 79, 89, 93, 97, 100, 104, 657, 659, 712, 756, 1003, 1007, 1010, 1013, 1017, 1020, 1023, 1027, 1030, 1057, 1059, 1068, 1086, 1090, 1104, 1132, 1155, 1162, 1194, 1198, 1206, 1242, 1262, 1269, 1274, 1279, 1284, 1289, 1301, 1312, 1339, 1357, 1368, 1407, 1414, 1614, 1616, 1621, 1622, 1634, 1636, 1641, 1642, 1655, 1660, 1665, 1670, 1675, 1712, 1714, 1719, 1721, 1735, 1743, 1772, 1782, 1802, 1806, 1815, 1822, 1829, 1852, 1856, 1873, 1884, 1891, 1909, 1917, 1924, 1947, 1979, 1982, 1987, 1988, 2002, 2006, 2010, 2019, 2563, 2679
D	
\DeclareRobustCommand 611, 809, 841, 873, 888
\dimendef 916
\directlua 686, 1423, 2318
\documentclass 4, 2553, 2603
\dp 1527, 1540
E	
\empty 139, 140
\end 55, 116, 119, 120, 2549, 2598, 2599, 2666
\endcsname 136, 143, 172, 188, 198, 321, 324, 336, 381, 386, 389, 395, 398, 419, 420, 422, 423, 426, 427, 449, 457, 467, 476, 480, 493, 497, 511, 515, 527, 544, 547, 552, 555, 582, 717, 727, 738, 748, 762, 772, 787, 797, 824, 831, 856, 863, 912, 1044, 1094, 1096, 1108, 1186, 1188, 1190, 1192, 1193, 1197, 1202, 1203, 1450, 1452, 1801, 1805, 1810, 1811, 2009, 2013, 2014, 2226, 2380, 2394, 2457, 2460, 2463, 2466, 2521, 2548
\endhead 114
\endinput 151, 251
\endlinechar 126, 157, 193, 199, 211
\endpgfpicture 1535, 1578
\ensuremath 1166
\errmessage 2510
\escapechar 250, 253
\Expect 2564
\extrarowheight 13
F	
\f@series 910, 911
\f@size 582
\fmtname 609, 2195, 2237, 2370
\font 576, 590, 624, 1467, 1504
\fontdimen 1504
\fontencoding 613
\fontfamily 92, 96, 103, 614
\fontsize 583, 956, 1047
H	
\hbox 932, 934, 974, 1040, 1042, 1134, 1210, 1298, 1447, 1501, 1526, 1532, 1539, 1545, 1570, 1574, 1581, 1585, 1683, 1953, 2114, 2143, 2166, 2377, 2378, 2381, 2390, 2391, 2393, 2395
\HCode 941, 943, 1231, 1233, 1599, 2156, 2179
\hline 49, 113
\Hologo 4, 72, 79, 86, 109, 733, 781
\hologo 3, 72, 79, 89, 93, 97, 100, 104, 657, 659, 712, 756, 1003, 1007, 1010, 1013, 1017, 1020, 1023, 1027, 1030, 1057, 1059, 1068, 1086, 1090, 1104, 1132, 1155, 1162, 1194, 1198, 1206, 1242, 1262, 1269, 1274, 1279, 1284, 1289, 1301, 1312, 1339, 1357, 1368, 1407, 1414, 1614, 1616, 1621, 1622, 1634, 1636, 1641, 1642, 1655, 1660, 1665, 1670, 1675, 1712, 1714, 1719, 1721, 1735, 1743, 1772, 1782, 1802, 1806, 1815, 1822, 1829, 1852, 1856, 1873, 1884, 1891, 1909, 1917, 1924, 1947, 1979, 1982, 1987, 1988, 2002, 2006, 2010, 2019, 2563, 2679
\HoLogo@{(La)TeX} 1093
\HOLOGO@@IfCharExists 1444, 1479, 1487, 1493
\HOLOGO@@NegativeKerning 922, 931
\HOLOGO@@temp 2266, 2283
\HoLogo@AmS 1679
\HoLogo@AmSLaTeX 1718, 1724
\HoLogo@AmSTeX 1711, 1717
\HOLOGO@AtEnd 217, 218, 248, 249, 662, 669, 2360, 2364, 2367, 2450
\HoLogo@biber 2046, 2055
\HoLogo@BibTeX 1799
\HoLogo@BibTeX8 1801
\HoLogo@BibTeX@sc 1725
\HoLogo@BibTeX@sf 1762, 1799
\HOLOGO@break 412, 433
\HOLOGO@CheckDriver 2294, 2303
\HOLOGO@CheckRead 2204
\HOLOGO@choice 1503, 1510, 1513, 1516, 1519, 1521, 1555, 1558, 1561, 1564, 1566
\HoLogo@ConTeXt 1847
\HoLogo@ConTeXt@narrow 1818, 1847
\HoLogo@ConTeXt@simple 1812, 1817
\HOLOGO@DeclareBoolOption 380, 434, 435, 436, 437
\HOLOGO@discretionary 505, 1299, 1338, 1355, 1733, 1770, 1814, 1820, 1851, 1871, 1908, 1980, 2001, 2017, 2025, 2032, 2038, 2043, 2048
\HOLOGO@DriverFallback 2285, 2287, 2298
\HOLOGO@DriverSetup 2290, 2292, 2374
\HoLogo@emTeX 1849, 1858
\HoLogo@eTeX 1236
\HoLogo@ExTeX 1859
\HOLOGO@false 393, 432

\HOLOGO@FontSetup	630, 640, 643	\HoLogo@pdfLaTeX	1663, 1672
\HoLogo@HanTheThanh	2158	\HOLOGO@pdfliteral	
\HOLOGO@hyphen		2306, 2310, 2325, 2329, 2406, 2410	
.	487, 1013, 1713, 1720, 2065	\HoLogo@pdfTeX	1653, 1662
\HOLOGO@ifCharExists	1418, 1500, 2163	\HoLogo@PiC	1950
\HOLOGO@ifDefined	351	\HoLogo@PiCTeX	1978
\HOLOGO@ifExists	351, 657,	\HoLogo@plainTeX	1032
664, 720, 741, 765, 790, 910, 2182		\HoLogo@plainTeX@hyphen	1012
\HOLOGO@ifincsname	693, 701	\HoLogo@plainTeX@runtogether . . .	1022
\HoLogo@iniTeX	1272, 1281	\HoLogo@plainTeX@space	1002, 1032
\HOLOGO@InputIfExists	2186, 2206, 2227	\HOLOGO@PointReflectBox	
\HoLogo@KOMAScript	2056	1544, 1545, 2388
\HoLogo@La	1036	\HOLOGO@ReflectBox	1586, 2375
\HoLogo@LaTeX	1056	\HOLOGO@Reflectbox	1584
\HoLogo@LaTeXe	1185	\HoLogo@SageTeX	2015, 2021
\HoLogo@LaTeX3	1193	\HOLOGO@ScaleBox@dvipdfm	2432
\HoLogo@LaTeXe	1131, 1186	\HOLOGO@ScaleBox@dvips	2415, 2433
\HoLogo@LaTeXML	1204	\HOLOGO@ScaleBox@pdftex	2404
\HoLogo@LaTeXTeX	1083, 1094	\HOLOGO@ScaleBox@vtex	2443
\HoLogo@LuaLaTeX	1411, 1417	\HOLOGO@ScaleBox@xetex	2435
\HoLogo@LuaTeX	1403, 1410	\HOLOGO@SetBreakAll	391, 400, 410
\HoLogo@LyX	2111	\HOLOGO@Setup	364, 374, 377
\HOLOGO@Math	908	\HoLogo@SLiTeX	1397
\HOLOGO@MathSetup	908,	\HoLogo@SLiTeX	1400
1135, 1165, 1238, 1266, 1862, 1881		\HoLogo@SLiTeX@lift	1292, 1394, 1397
\HOLOGO@mbox	522,	\HoLogo@SLiTeX@lift	1394
1003, 1013, 1023, 1205, 1273,		\HoLogo@SLiTeX@narrow	1391
1283, 1404, 1412, 1654, 1664,		\HoLogo@SLiTeX@narrow	1344, 1391, 1400
1674, 1813, 1815, 1819, 1822,		\HoLogo@SLiTeX@simple	1388
1850, 1907, 1937, 1940, 1943,		\HoLogo@SLiTeX@simple	1333, 1343, 1388
1946, 2000, 2010, 2016, 2024,		\HOLOGO@space	470, 1003, 2160, 2169
2026, 2031, 2033, 2037, 2039,		\HOLOGO@SpaceFactor	
2042, 2044, 2047, 2049, 2058, 2067		937, 974, 1956, 2117, 2147, 2153
\HoLogo@METAFONT	2022	\HOLOGO@Span	940, 978, 980,
\HoLogo@MetaFun	2036	1063, 1065, 1099, 1101, 1102,	
\HoLogo@METAPOST	2029	1103, 1161, 1163, 1164, 1216,	
\HoLogo@MetaPost	2041	1219, 1221, 1225, 1227, 1307,	
\HoLogo@MiKTeX	1906, 1911	1310, 1311, 1363, 1366, 1367,	
\HOLOGO@name	363, 367, 368,	1596, 1598, 1620, 1640, 1692,	
370, 385, 389, 394, 398, 413,		1694, 1739, 1741, 1742, 1776,	
419, 420, 422, 423, 425, 427,		1779, 1826, 1827, 1879, 1883,	
439, 449, 451, 453, 457, 471,		1921, 1923, 1960, 1962, 1986,	
472, 476, 480, 488, 489, 493,		2076, 2078, 2080, 2081, 2121, 2123	
497, 506, 507, 511, 515, 523,		\HOLOGO@SubScript	945, 2151
527, 629, 633, 634, 636, 648,		\HOLOGO@temp	383, 384, 393, 411, 412,
651, 815, 816, 818, 820, 823,		446, 447, 451, 453, 458, 473,	
824, 828, 829, 831, 847, 848,		475, 479, 482, 490, 492, 496,	
850, 852, 855, 856, 860, 861, 863		499, 508, 510, 514, 517, 524,	
\HOLOGO@NegativeKerning		526, 529, 646, 655, 656, 703,	
.	917, 1241, 1406, 2018	2187, 2188, 2189, 2191, 2203,	
\HoLogo@NTS	2139	2205, 2208, 2215, 2218, 2226,	
\HoLogo@OzMF	1936	2230, 2231, 2233, 2250, 2253,	
\HoLogo@OzMP	1939	2254, 2255, 2258, 2268, 2270,	
\HoLogo@OzTeX	1912	2316, 2328, 2331, 2369, 2370,	
\HoLogo@OzTtH	1942	2403, 2404, 2415, 2432, 2435, 2443	
\HoLogo@PCTeX	1945, 1949	\HOLOGO@TempDimen	
\HOLOGO@PdfdocUnicode	916, 919, 921, 926, 927, 933, 935
.	901, 1157, 1260, 1890, 2174	\HoLogo@teTeX	1999, 2008

\HoLogo@TeX	973	\HoLogoCs@plainTeX@hyphen	1015
\HoLogo@TeX4ht	2009	\HoLogoCs@plainTeX@runtogether	1025
\HOLOGO@true	384, 431	\HoLogoCs@plainTeX@space	1005, 1033
\HoLogo@TTH	2149	\HoLogoCs@teTeX	2004
\HOLOGO@Uppercase	861, 900	\HoLogoCs@virTeX	1287
\HOLOGO@Variant	463, 714, 717, 724, 727, 735, 738, 745, 748, 816, 824, 828, 831, 848, 856, 860, 863	\HoLogoCss@AmS	1690, 1699
\HoLogo@virTeX	1282, 1291	\HoLogoCss@BibTeX@sc	1738, 1746
\HoLogo@VTeX	1673, 1678	\HoLogoCss@BibTeX@sf	1775, 1785
\HOLOGO@WarningUnsupportedDriver	1522, 1567, 2350	\HoLogoCss@ConTeXt@narrow	1825, 1833
\HoLogo@Xe	1497	\HoLogoCss@ExTeX	1877, 1893
\HoLogo@XeLaTeX	1633	\HoLogoCss@KOMAScript	2074, 2086
\HoLogo@XeTeX	1613	\HoLogoCss@LaTeX	1062, 1071, 1217
\HoLogoBkm@(La)TeX	1095	\HoLogoCss@LaTeXe	1160, 1170
\HoLogoBkm@AmS	1688	\HoLogoCss@LaTeXTeX	1098, 1109
\HoLogoBkm@AmSLaTeX	1723	\HoLogoCss@LyX	2120, 2127
\HoLogoBkm@AmSTeX	1716	\HoLogoCss@OzTeX	1920, 1927
\HoLogoBkm@biber	2052	\HoLogoCss@PiC	1959, 1966
\HoLogoBkm@BibTeX8	1805	\HoLogoCss@PiCTeX	1985, 1991
\HoLogoBkm@emTeX	1855	\HoLogoCss@SLiTeX@lift	1306, 1316
\HoLogoBkm@eTeX	1259	\HoLogoCss@SLiTeX@narrow	1362, 1372
\HoLogoBkm@ExTeX	1889	\HoLogoCss@TeX	977, 986, 1218
\HoLogoBkm@HanTheThanh	2172	\HoLogoCss@Xe	1595, 1603
\HoLogoBkm@iniTeX	1278	\HoLogoCss@XeLaTeX	1639, 1645
\HoLogoBkm@KOMAScript	2070	\HoLogoCss@XeTeX	1619, 1625
\HoLogoBkm@LaTeX2e	1189	\hologoDriver	
\HoLogoBkm@LaTeX3	1197	\hologoDriverSetup	6, 2288
\HoLogoBkm@LaTeXe	1154, 1190	\hologoEntry	
\HoLogoBkm@LaTeXTeX	1092, 1096		
\HoLogoBkm@pdfLaTeX	1669		
\HoLogoBkm@pdfTeX	1659		
\HoLogoBkm@plainTeX	1034		
\HoLogoBkm@plainTeX@hyphen	1016		
\HoLogoBkm@plainTeX@runtogether	1026		
\HoLogoBkm@plainTeX@space	1006, 1034		
\HoLogoBkm@SLiTeX	1398		
\HoLogoBkm@SLiTeX	1401		
\HoLogoBkm@SLiTeX@lift	1304, 1395, 1398		
\HoLogoBkm@SLiTeX@lift	1395	\HoLogoFont@Def	551, 557,
\HoLogoBkm@SLiTeX@narrow	1392		561, 564, 569, 572, 578, 580,
\HoLogoBkm@SLiTeX@narrow	1360, 1392, 1401		592, 594, 599, 602, 620, 626, 649
\HoLogoBkm@SLiTeX@simple	1389	\HoLogoFont@font	535, 823, 855, 1212,
\HoLogoBkm@SLiTeX@simple	1342, 1389		1293, 1298, 1308, 1334, 1336,
\HoLogoBkm@teTeX	2005		1345, 1349, 1364, 1680, 1691,
\HoLogoBkm@virTeX	1288		1728, 1765, 1778, 1860, 1867,
\HoLogoCs@biber	2051		1878, 2023, 2030, 2057, 2075, 2140
\HoLogoCs@emTeX	1854	\HoLogoFont@font@bibsfs	574
\HoLogoCs@eTeX	1245	\HoLogoFont@font@general	557
\HoLogoCs@iniTeX	1277	\HoLogoFont@font@logo	606
\HoLogoCs@LaTeX2e	1187	\HoLogoFont@font@rm	558
\HoLogoCs@LaTeXe	1140, 1188	\HoLogoFont@font@sc	588
\HoLogoCs@pdfLaTeX	1668	\HoLogoFont@font@sfs	566
\HoLogoCs@pdfTeX	1658	\HoLogoFont@font@sy	596
\HoLogoCs@plainTeX	1033	\HoLogoFont@LogoDef	554, 651
		\hologoFontSetup	6, 628
		\HoLogoHtml@LaTeX	1107

\HoLogoHtml@AmS 1689 \holoList . 7, 35, 115, 254, 2582, 2665
 \HoLogoHtml@AmSLaTeX 1724 \holoLogoFontSetup 6, 632
 \HoLogoHtml@AmSTeX 1717 \holoLogoSetup
 \HoLogoHtml@biber 2055 5, 63, 366, 443, 880, 895, 2590
 \HoLogoHtml@BibTeX 1800 \HOLOGOOPT@break 414, 415, 416
 \HoLogoHtml@BibTeX8 1809 \HOLOGOOPT@discretionarybreak
 \HoLogoHtml@BibTeX@sc 1737 416, 508
 \HoLogoHtml@BibTeX@sf 1774, 1800 \HOLOGOOPT@hyphenbreak 414, 490, 524
 \HoLogoHtml@ConTeXt 1848 \HOLOGOOPT@spacebreak 415, 473
 \HoLogoHtml@ConTeXt@narrow 1824, 1848 \HologoRobust 743, 837, 896
 \HoLogoHtml@ConTeXt@simple 1817 \holoRobust
 \HoLogoHtml@emTeX 1858 664, 666, 722, 805, 881, 899
 \HoLogoHtml@eTeX 1264 \holoRobust 899
 \HoLogoHtml@ExTeX 1876 \holoSetup 5, 362, 441
 \HoLogoHtml@HanTheThanh 2177 \HologoVariant 779, 2621, 2632, 2642
 \HoLogoHtml@iniTeX 1281 \holoVariant
 \HoLogoHtml@KOMAScript 2073 7, 754, 2621, 2623, 2632, 2642
 \HoLogoHtml@LaTeX 1061 \HologoVariantRobust 792, 884
 \HoLogoHtml@LaTeX2e 1191 \holoVariantRobust 767, 869
 \HoLogoHtml@LaTeX3 1201 \hss 2166, 2381, 2395
 \HoLogoHtml@LaTeXe 1159, 1192 \ht 1041, 2393
 \HoLogoHtml@LaTeXML 1215 \hypersetup 20, 75, 2636
 \HoLogoHtml@LaTeXTeX 1097, 1108 \hypertarget 68
 \HoLogoHtml@LuaLaTeX 1417
 \HoLogoHtml@LuaTeX 1410 **I**
 \HoLogoHtml@LyX 2119 \if 911, 1455
 \HoLogoHtml@MiKTeX 1911 \ifcase 482, 499, 517,
 \HoLogoHtml@OzTeX 1919 529, 685, 1521, 1566, 2208, 2317
 \HoLogoHtml@PCTeX 1949 \ifdim 921, 926, 1504
 \HoLogoHtml@pdfLaTeX 1215, 1672 \ifeof 2188, 2205
 \HoLogoHtml@pdfTeX 1662 \ifHy@unicode 902
 \HoLogoHtml@PiC 1958 \ifincsname 701, 713, 734, 758, 783
 \HoLogoHtml@PiCTeX 1984 \ifluatex 671, 1418, 2307
 \HoLogoHtml@plainTeX 1035 \ifnum 678, 1140, 1245, 1419, 1422,
 \HoLogoHtml@plainTeX@hyphen 1019 1449, 1467, 1473, 1486, 1490,
 \HoLogoHtml@plainTeX@runtogether 2233, 2313, 2493, 2501, 2508, 2516
 1029 \ifpdf 2304
 \HoLogoHtml@plainTeX@space 1009, 1035 \iftrue 902
 \HoLogoHtml@SageTeX 2021 \ifvtex 2344
 \HoLogoHtml@SLiTeX 1399 \ifx 33, 61, 72, 79, 137,
 \HoLogoHtml@SLiTeX 1402 140, 143, 172, 180, 183, 321,
 \HoLogoHtml@SLiTeX@lift 1305, 1396, 1399 324, 352, 355, 384, 385, 393,
 1396 394, 412, 413, 439, 447, 609,
 \HoLogoHtml@SLiTeX@lift 1396 648, 693, 755, 780, 902, 2195,
 \HoLogoHtml@SLiTeX@narrow 1393 2231, 2237, 2255, 2267, 2308,
 \HoLogoHtml@SLiTeX@narrow 1361, 1393, 1402 2325, 2370, 2457, 2460, 2463,
 2466, 2521, 2571, 2576, 2588, 2633
 \HoLogoHtml@SLiTeX@simple 1390 \ifxetex 1463, 2341
 \HoLogoHtml@SLiTeX@simple 1343, 1390 \immediate 145, 174
 \HoLogoHtml@teTeX 2008 \IncludeTests 2557
 \HoLogoHtml@TeX 976 \input 325, 2196, 2198, 2238, 2240, 2522
 \HoLogoHtml@TeX4ht 2012 \InputIfExists 2182, 2183
 \HoLogoHtml@TTH 2155 \iterate 2474, 2476, 2478
 \HoLogoHtml@virTeX 1291
 \HoLogoHtml@VTeX 1678
 \HoLogoHtml@Xe 1594 \kern 927, 934, 974, 1038, 1058,
 \HoLogoHtml@XeLaTeX 1638 1085, 1087, 1089, 1133, 1207,
 \HoLogoHtml@XeTeX 1618 1209, 1211, 1295, 1297, 1300,

\ltx@secondoftwo
	353, 356, 738, 749, 787,
	798, 857, 864, 903, 1436, 1460, 1476
\ltx@space 485, 659, 666
\ltx@two
	2378, 2384, 2385, 2391, 2399, 2400
\ltx@undefined 2289
\ltx@zero	. 381, 395, 398, 916, 932,
	933, 934, 935, 1040, 1041, 1435,
	1446, 1447, 1449, 1467, 1473,
	1503, 1526, 1527, 1529, 1539,
	1540, 1542, 2377, 2379, 2381,
	2384, 2390, 2392, 2393, 2395, 2399
\luatexversion 678, 1419, 2313
L	
\lastkern 1449
\LoadCommand 2522, 2532
\logofamily 611, 612, 620
\LogTests 2558
\loop 2472, 2488, 2499, 2507
\lower 974, 1210,
	1501, 1532, 1545, 1570, 1574,
	1581, 1585, 1683, 1953, 2114, 2143
\ltx@car 911
\ltx@cclv 2215, 2216, 2218
\ltx@empty 447, 2231, 2255
\ltx@firstofone 672, 681, 695
\ltx@firstofthree 1468
\ltx@firstoftwo 358, 717,
	720, 728, 741, 762, 765, 773,
	790, 825, 832, 905, 1438, 1457, 1474
\ltx@fourthoffour 1491
\ltx@gobble
	372, 638, 674, 679, 698, 924, 1470
\ltx@hashchar 1599, 2179
\ltx@IfUndefined
	335, 368, 451, 537, 538,
	558, 559, 566, 567, 574, 575,
	588, 589, 596, 597, 610, 618,
	623, 634, 677, 707, 805, 806,
	816, 822, 828, 837, 838, 848,
	854, 860, 869, 870, 884, 885,
	946, 947, 952, 1443, 1464, 1465,
	1505, 1506, 1507, 1508, 1550,
	1551, 1552, 1553, 2185, 2202,
	2312, 2335, 2358, 2359, 2363, 2366
\ltx@ifundefined	465, 471, 472, 488,
	489, 506, 507, 523, 714, 724,
	725, 735, 745, 746, 759, 769,
	770, 784, 794, 795, 1043, 1485, 2295
\ltx@LocDimenA
	1527, 1528, 1529, 1540, 1541, 1542
\ltx@mbox 500, 530, 948,
	964, 1237, 1265, 1335, 1346,
	1861, 1880, 2150, 2159, 2161, 2170
\ltx@minusone 2216
\ltx@newif 336
\ltx@one 386, 389, 1504
\ltx@onellevel@sanitize 2254
M	
\makeatletter 2567, 2629
\makeatother 2664
\math@fontsfalse 584, 1048
\mathrm 953
\mathsurround 581, 909, 949, 965
\mbox 955
\MessageBreak 403, 442,
	659, 666, 2210, 2352, 2353, 2354
N	
\NeedsTeXFormat 3, 2552, 2602
\newcommand 32, 60, 66, 2561
\newpage 2662
\next 2478, 2480, 2482
\not@math@alphabet 612
\number 1426, 1431, 2513
O	
\openin 2187
P	
\PackageInfo 148
\pagestyle 9
\par 2627
\pdf@filesize 2230
\pdfextension 2308, 2309
\pdfliteral 2306, 2309, 2310, 2337
\penalty 483
\pgfpicture 1533, 1575
\pgftext 1531, 1534, 1573, 1577
\pgftransformxscale 1576
\ProcessKeyvalOptions 2372
\protected	... 812, 844, 876, 891, 2309
\ProvidesPackage 141, 189
\psscalebox 1537, 1539, 1580, 1582
Q	
\quad 2622, 2624
R	
\raise	... 1298, 1529, 1542, 2166, 2393
\raisebox 68

\RangeCatcodeCheck	2505, 2533, 2534, 2535, 2536, 2537, 2538, 2539, 2540, 2541, 2542, 2543, 2544	\TeX	52, 53, 54
\RangeCatcodeInvalid 2497, 2525, 2526, 2527, 2528	\texorpdfstring	720, 741, 765, 790
\reflectbox	1571	\text	966
\renewcommand	2615	\textbf	48, 108, 110, 111
\repeat	2472, 2484, 2495, 2503, 2518	\textchi	1890
\RequirePackage 341, 342, 343, 344, 345, 346, 347, 348, 349, 2371	\textepsilon	1157, 1260, 1890
\RestoreCatcodes	2486, 2489, 2490, 2545	\textit	108
\rm 561	\textsf	100
\rmfamily 564	\textstyle	1137, 1166, 1864, 1882, 1883
\rotatebox	1524, 1526	\textsubscript	970
		\texttt	82, 84, 109
		\the	199, 200, 201, 202, 203, 204, 205, 206, 219, 250, 2218, 2491, 2511, 2512, 2564
		\TMP@EnsureCode	216, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245, 246, 247
		\TMP@RequirePackage	322, 328, 329, 330, 331, 332, 333, 334, 338, 339
		\tracinglostchars	1446
		\typeout	30, 31, 33, 36, 37
			U
		\uppercase	900
		\usefont	603, 2620
		\usepackage	5, 10, 11, 12, 14, 15, 16, 17, 25, 2554, 2555, 2556, 2604, 2605, 2606, 2607, 2608, 2609
			V
		\varepsilon 1137, 1166, 1239, 1267, 1865, 1882
		\vbox	1041
		\vss	1052
			W
		\wd 933, 935, 2379, 2384, 2392, 2399
		\write	145, 174
			X
		\x 136, 137, 140, 144, 148, 150, 173, 178, 188, 197, 209, 607, 609, 2193, 2195, 2217, 2221, 2235, 2237, 2297, 2299
		\XeTeXcharglyph	1473
		\XeTeXfonttype	1467