

The holtxdoc package

Heiko Oberdiek
<heiko.oberdiek at googlemail.com>

2010/02/03 v0.14

Abstract

The package is used for the documentation of my packages in DTX format. It contains some private macros and setup for my needs. Thus do not use it. I have separated the part that may be useful for others in package hypdoc.

Contents

| | | |
|--------------------|---------------------------------|----------|
| 1 | No usage | 2 |
| 2 | Implementation | 2 |
| 2.1 | Help macros | 2 |
| 2.2 | History | 2 |
| 2.3 | Formatting macros | 3 |
| 2.4 | Names | 4 |
| 2.5 | Setup | 5 |
| 2.5.1 | Package doc | 5 |
| 2.5.2 | Page layout | 5 |
| 3 | Installation | 5 |
| 3.1 | Download | 5 |
| 3.2 | Bundle installation | 5 |
| 3.3 | Package installation | 6 |
| 3.4 | Refresh file name databases | 6 |
| 3.5 | Some details for the interested | 6 |
| 4 | History | 7 |
| [1999/06/26 v0.3] | | 7 |
| [2000/08/14 v0.4] | | 7 |
| [2001/08/27 v0.5] | | 7 |
| [2001/09/02 v0.6] | | 7 |
| [2006/06/02 v0.7] | | 7 |
| [2007/10/21 v0.8] | | 7 |
| [2007/11/11 v0.9] | | 7 |
| [2007/12/12 v0.10] | | 7 |
| [2008/08/11 v0.11] | | 7 |
| [2009/08/07 v0.12] | | 7 |
| [2009/12/02 v0.13] | | 7 |
| [2010/02/03 v0.14] | | 7 |
| 5 | Index | 7 |

1 No usage

Caution: *This package is not intended for public use!*

It contains the macros and settings to generate the documentation of my packages in CTAN:macros/latex/contrib/oberdiek/. Thus the package does not know anything about compatibility. Only my current packages' documentation must compile.

Older versions were more interesting, because they contained code to add hyperref's features to L^AT_EX's doc system, e.g. bookmarks and index links. I separated this stuff and made a new package hypdoc.

2 Implementation

```
1 \*package)
```

Package identification.

```
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{holtxdoc}%
4   [2010/02/03 v0.14 Private additional ltxdoc support (HO)]
5 \RequirePackage[numbered]{hypdoc}
6 \RequirePackage{array}
```

2.1 Help macros

```
7 \def\hld@info#1{%
8   \PackageInfo{holtxdoc}{#1\@gobble}%
9 }
10 \def\hld@warn#1{%
11   \PackageWarningNoLine{holtxdoc}{#1}%
12 }
```

2.2 History

```
13 \newcommand*\StartHistory{%
14   \section{History}%
15 }
16 \@ifpackagelater{hyperref}{2009/11/27}{%
17   \newcommand*\HistVersion[1]{%
18     \subsection*{[#1]}% hash-ok
19     \addcontentsline{toc}{subsection}{[#1]}% hash-ok
20     \def\HistLabel##1{%
21       \begingroup
22         \edef\@currentlabel{[#1]}% hash-ok
23         \label{##1}%
24       \endgroup
25     }%
26   }%
27 }{%
28   \newcommand*\HistVersion[1]{%
29     \subsection*{%
30       \phantomsection
31       \addcontentsline{toc}{subsection}{[#1]}% hash-ok
32       [#1]% hash-ok
33     }%
34     \def\HistLabel##1{%
35       \begingroup
36         \edef\@currentlabel{[#1]}% hash-ok
37         \label{##1}%
38       \endgroup
39     }%
40   }%
41 }
42 \newenvironment{History}{%
```

```

43 \StartHistory
44 \def\Version##1{%
45   \HistVersion{##1}%
46   \itemize
47 }%
48 \let\endVersion\enditemize
49 }{}

```

2.3 Formatting macros

```

\UrlFoot
#1: text
#2: url

50 \newcommand{\URL}[2]{%
51   \begingroup
52   \def\link{\href{#2}}%
53   #1%
54   \endgroup
55   \footnote{Url: \url{#2}}%
56 }

\NameEmail
#1: name
#2: email address

57 \newcommand*\NameEmail[2]{%
58   \expandafter\hld@NameEmail\expandafter{#2}{#1}%
59 }
60 \def\hld@NameEmail#1#2{%
61   \expandafter\hld@@NameEmail\expandafter{#2}{#1}%
62 }
63 \def\hld@@NameEmail#1#2{%
64   \ifx\#1#2\%
65     \hld@warn{%
66       Command \string\NameEmail\space without name and email%
67     }%
68   \else
69     \ifx\#1\%
70       \href{mailto:#2}{\nolinkurl{#2}}%
71     \else
72       #1%
73       \ifx\#2\%
74       \else
75         \footnote{%
76           #1's email address: %
77           \href{mailto:#2}{\nolinkurl{#2}}%
78         }%
79       \fi
80     \fi
81   \fi
82 }

83 \newcommand*\Package[1]{\texttt{#1}}
84 \newcommand*\File[1]{\texttt{#1}}
85 \newcommand*\Verb[1]{\texttt{#1}}
86 \newcommand*\CS[1]{\texttt{\expandafter\@gobble\string\#1}}

87 \newcommand*\CTAN[1]{%
88   \href{ftp://ftp.ctan.org/tex-archive/#1}{\nolinkurl{CTAN:#1}}%
89 }

90 \newcommand*\Newsgroup[1]{%
91   \href{http://groups.google.com/group/#1/topics}{\nolinkurl{news:#1}}%
92 }

93 \newcommand*\xpackage[1]{\textsf{#1}}

```

```

94 \newcommand*{\xmodule}[1]{\textsf{#1}}
95 \newcommand*{\xclass}[1]{\textsf{#1}}
96 \newcommand*{\xoption}[1]{\textsf{#1}}
97 \newcommand*{\xfile}[1]{\texttt{#1}}
98 \newcommand*{\xext}[1]{\texttt{.#1}}
99 \newcommand*{\xemail}[1]{%
100   \textless\texttt{#1}\textgreater%
101 }
102 \newcommand*{\xnewsgroup}[1]{%
103   \href{news:#1}{\nolinkurl{#1}}%
104 }

```

The following environment declcs is derived from environment decl of ltxguide.cls:

```

105 \newenvironment{declcs}[1]{%
106   \par
107   \addvspace{4.5ex plus 1ex}%
108   \vskip -\parskip
109   \noindent
110   \hspace{-\leftmargini}%
111   \def\M##1{\texttt{\{}\meta{##1}\texttt{\}}}%
112   \def\*{\unskip\,\texttt{*}}%
113   \begin{tabular}{|l|}%
114     \hline
115     \expandafter\SpecialUsageIndex\csname #1\endcsname
116     \cs{#1}%
117   }{%
118     \\%
119     \hline
120   \end{tabular}%
121   \nobreak
122   \par
123   \nobreak
124   \vspace{2.3ex}%
125   \vskip -\parskip
126   \noindent
127   \ignorespacesafterend
128 }

```

2.4 Names

```

129 \providecommand*{\eTeX}{\mbox{$\varepsilon$-TeX}}
130 \providecommand*{\pdfTeX}{pdfTeX}
131 \providecommand*{\pdfLaTeX}{pdfLaTeX}
132 \providecommand*{\LuaTeX}{L\textsc{ua}TeX}
133 \def\@temp#1#2{%
134   \@ifundefined{\expandafter\@gobble\string#1}{%
135     \DeclareRobustCommand*{#1}{%
136       \texorpdfstring{%
137         \begingroup
138           X%
139           \kern-.1em\relax
140         \@ifundefined{rotatebox}{e}{%
141           \lower0.5ex\hbox{%
142             \setbox0=\hbox{E}%
143             \dimen0=\ht0 %
144             \advance\dimen0 by \dp0 %
145             \raise\dimen0\hbox{\rotatebox{180}{\box0}}}%
146           }%
147         }{Xe}%
148       }{Xe}%
149     \ifx\TeX#2\relax
150       \kern-.15em\relax

```

```

151         \fi
152         #2%
153     \endgroup
154 }%
155 }{}%
156 }
157 \@temp\XeTeX\TeX
158 \@temp\XeLaTeX\LaTeX
159 \providecommand*{\teTeX}{te\TeX}
160 \providecommand*{\mikTeX}{mik\TeX}
161 \providecommand*{\MakeIndex}{\textsl{MakeIndex}}
162 \providecommand*{\docstrip}{\textsf{docstrip}}
163 \providecommand*{\plainTeX}{\mbox{plain-\TeX}}
164 \providecommand*{\iniTeX}{\mbox{ini-\TeX}}
165 \providecommand*{\VTeX}{V\TeX}

```

2.5 Setup

2.5.1 Package doc

```

166 \CodelineIndex
167 \EnableCrossrefs
168 \setcounter{IndexColumns}{2}

169 \DoNotIndex{\begingroup,\endgroup,\bgroup,\egroup}
170 \DoNotIndex{\def,\edef,\xdef,\global,\long,\let}
171 \DoNotIndex{\expandafter,\noexpand,\string}
172 \DoNotIndex{\else,\fi,\or}
173 \DoNotIndex{\relax}

```

2.5.2 Page layout

```

174 \addtolength{\textheight}{\headheight}
175 \addtolength{\textheight}{\headsep}
176 \setlength{\headheight}{0pt}
177 \setlength{\headsep}{0pt}

178 \addtolength{\topmargin}{-10mm}
179 \addtolength{\textheight}{20mm}

180 </package>

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/holtxdoc.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/holtxdoc.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for \TeX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

¹<http://ftp.ctan.org/tex-archive/>

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain- \TeX :

```
tex holtxdoc.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
holtxdoc.sty → tex/latex/oberdiek/holtxdoc.sty
holtxdoc.pdf → doc/latex/oberdiek/holtxdoc.pdf
holtxdoc.dtx → source/latex/oberdiek/holtxdoc.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your \TeX distribution (te \TeX , mi \TeX , ...) relies on file name databases, you must refresh these. For example, te \TeX users run `texhash` or `mktexlsr`.

3.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk holtxdoc.pdf unpack_files output .
```

Unpacking with \LaTeX . The `.dtx` chooses its action depending on the format:

plain- \TeX : Run `docstrip` and extract the files.

\LaTeX : Generate the documentation.

If you insist on using \LaTeX for `docstrip` (really, `docstrip` does not need \LaTeX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{holtxdoc.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdf \LaTeX :

```
pdflatex holtxdoc.dtx
makeindex -s gind.ist holtxdoc.idx
pdflatex holtxdoc.dtx
makeindex -s gind.ist holtxdoc.idx
pdflatex holtxdoc.dtx
```

4 History

[1999/06/26 v0.3]

- ...

[2000/08/14 v0.4]

- ...

[2001/08/27 v0.5]

- ...

[2001/09/02 v0.6]

- ...

[2006/06/02 v0.7]

- Major change: most is put into a new package `hypdoc`.

[2007/10/21 v0.8]

- `\XeTeX` and `\XeLaTeX` added.

[2007/11/11 v0.9]

- `\LuaTeX` added.

[2007/12/12 v0.10]

- `\iniTeX` added.

[2008/08/11 v0.11]

- `\Newsgroup`, `\xnewsgroup`, and `\URL` updated.

[2009/08/07 v0.12]

- `\xmodule` added.

[2009/12/02 v0.13]

- Anchor hack for unnumbered subsections is removed for `hyperref` \geq 2009/11/27 6.79k.

[2010/02/03 v0.14]

- `\XeTeX` and `\XeLaTeX` are made robust.

5 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

| | | |
|-----------------------|--|---------------|
| Symbols | <code>\,</code> | 112 |
| <code>*</code> | 112 <code>\@currentlabel</code> | 22, 36 |

| | | | |
|-----------------------|-------------------------|-----------------------|---|
| \@gobble | 8, 86, 134 | K | |
| \@ifpackagelater | 16 | \kern | 139, 150 |
| \@ifundefined | 134, 140 | L | |
| \@temp | 133, 157, 158 | \label | 23, 37 |
| \\ | 64, 69, 73, 86, 118 | \LaTeX | 131, 158 |
| \{ | 111 | \leftmargini | 110 |
| \} | 111 | \link | 52 |
| A | | \lower | 141 |
| \addcontentsline | 19, 31 | \LuaTeX | 132 |
| \addtolength | 174, 175, 178, 179 | M | |
| \addvspace | 107 | \M | 111 |
| \advance | 144 | \MakeIndex | 161 |
| B | | \mbox | 129, 163, 164 |
| \begin | 113 | \meta | 111 |
| \box | 145 | \miktex | 160 |
| C | | N | |
| \CodelineIndex | 166 | \NameEmail | 57, 66 |
| \CS | 86 | \NeedsTeXFormat | 2 |
| \cs | 116 | \newcommand | 13, 17, 28, 50, 57, 83, 84, 85, 86, 87, 90, 93, 94, 95, 96, 97, 98, 99, 102 |
| \csname | 115 | \newenvironment | 42, 105 |
| \CTAN | 87 | \Newsgroup | 90 |
| D | | \nobreak | 121, 123 |
| \DeclareRobustCommand | 135 | \noindent | 109, 126 |
| \dimen | 143, 144, 145 | \nolinkurl | 70, 77, 88, 91, 103 |
| \docstrip | 162 | P | |
| \DoNotIndex | 169, 170, 171, 172, 173 | \Package | 83 |
| \dp | 144 | \PackageInfo | 8 |
| E | | \PackageWarningNoLine | 11 |
| \EnableCrossrefs | 167 | \par | 106, 122 |
| \end | 120 | \parskip | 108, 125 |
| \endcsname | 115 | \pdfLaTeX | 131 |
| \enditemize | 48 | \pdfTeX | 130 |
| \endVersion | 48 | \phantomsection | 30 |
| \eTeX | 129 | \plainTeX | 163 |
| F | | \providecommand | 129, 130, 131, 132, 159, 160, 161, 162, 163, 164, 165 |
| \File | 84 | \ProvidesPackage | 3 |
| \footnote | 55, 75 | R | |
| H | | \raise | 145 |
| \hbox | 141, 142, 145 | \RequirePackage | 5, 6 |
| \headheight | 174, 176 | \rotatebox | 145 |
| \headsep | 175, 177 | S | |
| \HistLabel | 20, 34 | \section | 14 |
| \HistVersion | 17, 28, 45 | \setbox | 142 |
| \hld@@NameEmail | 61, 63 | \setcounter | 168 |
| \hld@info | 7 | \setlength | 176, 177 |
| \hld@NameEmail | 58, 60 | \space | 66 |
| \hld@warn | 10, 65 | \SpecialUsageIndex | 115 |
| \hline | 114, 119 | \StartHistory | 13, 43 |
| \href | 52, 70, 77, 88, 91, 103 | \subsection | 18, 29 |
| \hspace | 110 | T | |
| \ht | 143 | \teTeX | 159 |
| I | | \TeX | 129, 130, 132, 149, 157, 159, 160, 163, 164, 165 |
| \ifx | 64, 69, 73, 149 | \texorpdfstring | 136 |
| \ignorespacesafterend | 127 | \textgreater | 100 |
| \iniTeX | 164 | | |
| \itemize | 46 | | |

| | | | |
|--------------------------------|-----------------------------------|--------------------------------|----------|
| <code>\textheight</code> | 174, 175, 179 | <code>\Version</code> | 44 |
| <code>\textless</code> | 100 | <code>\vskip</code> | 108, 125 |
| <code>\textsc</code> | 132 | <code>\vspace</code> | 124 |
| <code>\textsf</code> | 93, 94, 95, 96, 162 | <code>\VTeX</code> | 165 |
| <code>\textsl</code> | 161 | | |
| <code>\texttt</code> | 83, | | |
| | 84, 85, 86, 97, 98, 100, 111, 112 | | |
| <code>\topmargin</code> | 178 | | |
| | | | |
| | U | | |
| <code>\unskip</code> | 112 | <code>\xclass</code> | 95 |
| <code>\URL</code> | 50 | <code>\XeLaTeX</code> | 158 |
| <code>\url</code> | 55 | <code>\xemail</code> | 99 |
| | | <code>\XeTeX</code> | 157 |
| | | <code>\xext</code> | 98 |
| | | <code>\xfile</code> | 97 |
| | | <code>\xmodule</code> | 94 |
| | | <code>\xnewsgroup</code> | 102 |
| | | <code>\xoption</code> | 96 |
| | | <code>\xpackage</code> | 93 |
| | | | |
| | V | | |
| <code>\varepsilon</code> | 129 | | |
| <code>\Verb</code> | 85 | | |