

The `holtxdoc` package

Heiko Oberdiek
<heiko.oberdiek at googlemail.com>

2010/04/24 v0.19

Abstract

The package is used for the documentation of my packages in DTX format. It contains some private macros and setup for my needs. Thus do not use it. I have separated the part that may be useful for others in package `hypdoc`.

Contents

1 No usage	2
2 Implementation	2
2.1 Help macros	2
2.2 Date	2
2.3 History	3
2.4 Formatting macros	3
2.5 Names	5
2.6 Setup	5
2.6.1 Package doc	5
2.6.2 Page layout	6
3 Installation	6
3.1 Download	6
3.2 Bundle installation	6
3.3 Package installation	6
3.4 Refresh file name databases	7
3.5 Some details for the interested	7
4 History	7
[1999/06/26 v0.3]	7
[2000/08/14 v0.4]	7
[2001/08/27 v0.5]	8
[2001/09/02 v0.6]	8
[2006/06/02 v0.7]	8
[2007/10/21 v0.8]	8
[2007/11/11 v0.9]	8
[2007/12/12 v0.10]	8
[2008/08/11 v0.11]	8
[2009/08/07 v0.12]	8
[2009/12/02 v0.13]	8
[2010/02/03 v0.14]	8
[2010/03/10 v0.15]	8
[2010/04/03 v0.16]	8
[2010/04/08 v0.17]	8
[2010/04/18 v0.18]	8
[2010/04/24 v0.19]	9

1 No usage

Caution: This package is not intended for public use!

It contains the macros and settings to generate the documentation of my packages in [CTAN:macros/latex/contrib/oberdiek/](#). Thus the package does not know anything about compatibility. Only my current packages' documentation must compile.

Older versions were more interesting, because they contained code to add `hyperref`'s features to L^AT_EX's `doc` system, e.g. bookmarks and index links. I separated this stuff and made a new package `hypdoc`.

2 Implementation

```

1 <*package>
2 Package identification.
3 \NeedsTeXFormat{LaTeX2e}
4 \ProvidesPackage{holtxdoc}%
5 [2010/04/24 v0.19 Private additional ltxdoc support (HO)]
6 \PassOptionsToPackage{pdfencoding=auto}{hyperref}
7 \RequirePackage[numbered]{hypdoc} [2010/03/26]
8 \RequirePackage{hyperref} [2010/03/30]
9 \RequirePackage{pdftexcmds} [2010/04/01]
10 \RequirePackage{ltxcmds} [2010/03/09]
11 \RequirePackage{hologo} [2010/04/24]
12 \RequirePackage{array}
```

2.1 Help macros

```

13 \def\hld@info#1{%
14   \PackageInfo{holtxdoc}{#1\@gobble}%
15 }
16 \def\hld@warn#1{%
17   \PackageWarningNoLine{holtxdoc}{#1}%
}
```

2.2 Date

```

18 \ltx@ifundefined{pdf@filemoddate}{%
19 }{%
20   \edef\hld@temp{\pdf@filemoddate{\jobname.dtx}}%
21   \ifx\hld@temp\ltx@empty
22   \else
23     \begingroup
24       \def\x#1:#2#3#4#5#6#7#8#9{%
25         \year=#2#3#4#5\relax
26         \month=#6#7\relax
27         \day=#8#9\relax
28         \y
29       }%
30       \def\y#1#2#3#4#5\@nil{%
31         \time=#1#2\relax
32         \multiply\time by 60\relax
33         \advance\time#3#4\relax
34       }%
35       \expandafter\x\hld@temp\@nil
36       \edef\x{\endgroup
37         \year=\the\year\relax
38         \month=\the\month\relax
39         \day=\the\day\relax
}
```

```

40          \time=\the\time\relax
41      }%
42      \x
43      \edef\hld@temp{%
44          \noexpand\hypersetup{%
45              pdfcreationdate=\hld@temp,%
46              pdfmoddate=\hld@temp
47      }%
48  }%
49  \hld@temp
50 \fi
51 }

2.3 History

52 \newcommand*{\StartHistory}{%
53   \section{History}%
54 }
55 \@ifpackagelater{hyperref}{2009/11/27}{%
56   \newcommand*{\HistVersion}[1]{%
57     \subsection*{[#1]}% hash-ok
58     \addcontentsline{toc}{subsection}{[#1]}% hash-ok
59     \def\HistLabel##1{%
60       \begingroup
61         \edef@\currentlabel{[#1]}% hash-ok
62         \label{##1}%
63       \endgroup
64     }%
65   }%
66 }{%
67   \newcommand*{\HistVersion}[1]{%
68     \subsection*{%
69       \phantomsection
70       \addcontentsline{toc}{subsection}{[#1]}% hash-ok
71       [#1]}% hash-ok
72   }%
73   \def\HistLabel##1{%
74     \begingroup
75       \edef@\currentlabel{[#1]}% hash-ok
76       \label{##1}%
77     \endgroup
78   }%
79 }
80 }

81 \newenvironment{History}{%
82   \StartHistory
83   \def\Version##1{%
84     \HistVersion{##1}%
85     \itemize
86   }%
87   \let\endVersion\enditemize
88 }{}
```

2.4 Formatting macros

```

\UrlFoot
#1: text
#2: url
89 \newcommand{\URL}[2]{%
90   \begingroup
91     \def\link{\href{#2}}%
92     #1%
93   \endgroup
94   \footnote{Url: \url{#2}}%
```

```

95 }
\NameEmail
#1: name
#2: email address
96 \newcommand*{\NameEmail}[2]{%
97   \expandafter\hld@NameEmail\expandafter{#2}{#1}%
98 }
99 \def\hld@NameEmail#1#2{%
100   \expandafter\hld@@NameEmail\expandafter{#2}{#1}%
101 }
102 \def\hld@@NameEmail#1#2{%
103   \ifx\#1#2\%
104     \hld@warn{%
105       Command \string\NameEmail\space without name and email%
106     }%
107   \else
108     \ifx\#1\%
109       \href{mailto:#2}{\nolinkurl{#2}}%
110     \else
111       \#1%
112     \ifx\#2\%
113       \else
114         \footnote{%
115           #1's email address: %
116           \href{mailto:#2}{\nolinkurl{#2}}%
117         }%
118       \fi
119     \fi
120   \fi
121 }

122 \newcommand*{\Package}[1]{\texttt{\#1}}
123 \newcommand*{\File}[1]{\texttt{\#1}}
124 \newcommand*{\Verb}[1]{\texttt{\#1}}
125 \newcommand*{\CS}[1]{\texttt{\expandafter\gobble\string\#1}}
126 \newcommand*{\CTAN}[1]{%
127   \href{ftp://ftp.ctan.org/tex-archive/#1}{\nolinkurl{CTAN:#1}}%
128 }

129 \newcommand*{\Newsgroup}[1]{%
130   \href{http://groups.google.com/group/#1/topics}{\nolinkurl{news:#1}}%
131 }

132 \newcommand*{\xpackage}[1]{\textsf{\#1}}
133 \newcommand*{\xmodule}[1]{\textsf{\#1}}
134 \newcommand*{\xclass}[1]{\textsf{\#1}}
135 \newcommand*{\xooption}[1]{\textsf{\#1}}
136 \newcommand*{\xfile}[1]{\texttt{\#1}}
137 \newcommand*{\xext}[1]{\texttt{\. #1}}
138 \newcommand*{\xemail}[1]{%
139   \textless\texttt{\#1}\textgreater%
140 }
141 \newcommand*{\xnewsgroup}[1]{%
142   \href{news:#1}{\nolinkurl{#1}}%
143 }

```

The following environment `declcs` is derived from environment `decl` of `ltxguide.cls`:

```

144 \newenvironment{declcs}[1]{%
145   \par
146   \addvspace{4.5ex plus 1ex}%
147   \vskip -\parskip
148   \noindent

```

```

149  \hspace{-\leftmargini}%
150  \def\M##1{\texttt{\{##1\}\meta{##1}\texttt{\}}\}%
151  \def\*{\unskip,\texttt{*}\}%
152  \begin{tabular}{|l|}%
153  \hline
154  \expandafter\SpecialUsageIndex\csname #1\endcsname
155  \cs{#1}%
156 \}%
157  \\%
158  \hline
159  \end{tabular}%
160  \nobreak
161  \par
162  \nobreak
163  \vspace{2.3ex}%
164  \vskip -\parskip
165  \noindent
166  \ignorespacesafterend
167 }

```

2.5 Names

```

168 \def\TeX{\holo{TeX}}
169 \def\pdfTeX{\holo{pdfTeX}}
170 \def\pdfLaTeX{\holo{pdfLaTeX}}
171 \def\LuaTeX{\holo{LuaTeX}}
172 \def\LuaLaTeX{\holo{LuaLaTeX}}
173 \def\XeTeX{\holo{XeTeX}}
174 \def\XeLaTeX{\holo{XeLaTeX}}
175 \def\plainTeX{\holo{plainTeX}}
176 \providecommand*\tex{\TeX}
177 \providecommand*\mik{\TeX}
178 \providecommand*\MakeIndex{\textsl{MakeIndex}}
179 \providecommand*\docstrip{\textsf{docstrip}}
180 \providecommand*\ini{\TeX}
181 \providecommand*\VTeX{\V\TeX}

```

2.6 Setup

2.6.1 Package doc

```

182 \CodelineIndex
183 \EnableCrossrefs
184 \setcounter{IndexColumns}{2}

185 \DoNotIndex{\begingroup,\endgroup,\bgroup,\egroup}
186 \DoNotIndex{\def,\edef,\xdef,\global,\long,\let}
187 \DoNotIndex{\expandafter,\noexpand,\string}
188 \DoNotIndex{\else,\fi,\or}
189 \DoNotIndex{\relax}

190 \IndexPrologue{%
191   \section*{Index}%
192   \markboth{Index}{Index}%
193   Numbers written in italic refer to the page %
194   where the corresponding entry is described; %
195   numbers underlined refer to the %
196   \ifcodeline@index
197     code line of the %
198   \fi
199   definition; plain numbers refer to the %
200   \ifcodeline@index
201     code lines %
202   \else
203     pages %

```

```

204 \fi
205 where the entry is used.%}
206 }

2.6.2 Page layout

207 \addtolength{\textheight}{\headheight}
208 \addtolength{\textheight}{\headsep}
209 \setlength{\headheight}{0pt}
210 \setlength{\headsep}{0pt}
211 \addtolength{\topmargin}{-10mm}
212 \addtolength{\textheight}{20mm}
213 </package>

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

CTAN:macros/latex/contrib/oberdiek/holtxdoc.dtx The source file.

CTAN:macros/latex/contrib/oberdiek/holtxdoc.pdf Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

CTAN:install/macros/latex/contrib/oberdiek.tds.zip

TDS refers to the standard “A Directory Structure for T_EX Files” (CTAN:tds/tds.pdf). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TD\$:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain T_EX:

```
tex holtxdoc.dtx
```

¹[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
holtxdoc.sty → tex/latex/oberdiek/holtxdoc.sty  
holtxdoc.pdf → doc/latex/oberdiek/holtxdoc.pdf  
holtxdoc.dtx → source/latex/oberdiek/holtxdoc.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your `TeX` distribution (`teTeX`, `mikTeX`, ...) relies on file name databases, you must refresh these. For example, `teTeX` users run `texhash` or `mktexlsr`.

3.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk holtxdoc.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain TeX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
\latex \let\install=y\input{holtxdoc.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex holtxdoc.dtx  
makeindex -s gind.ist holtxdoc.idx  
pdflatex holtxdoc.dtx  
makeindex -s gind.ist holtxdoc.idx  
pdflatex holtxdoc.dtx
```

4 History

[1999/06/26 v0.3]

• ...

[2000/08/14 v0.4]

• ...

[2001/08/27 v0.5]

- ...

[2001/09/02 v0.6]

- ...

[2006/06/02 v0.7]

- Major change: most is put into a new package `hypdoc`.

[2007/10/21 v0.8]

- `\XeTeX` and `\XeLaTeX` added.

[2007/11/11 v0.9]

- `\LuaTeX` added.

[2007/12/12 v0.10]

- `\iniTeX` added.

[2008/08/11 v0.11]

- `\Newsgroup`, `\xnewsgroup`, and `\URL` updated.

[2009/08/07 v0.12]

- `\xmodule` added.

[2009/12/02 v0.13]

- Anchor hack for unnumbered subsections is removed for `hyperref` $\geq 2009/11/27$ 6.79k.

[2010/02/03 v0.14]

- `\XeTeX` and `\XeLaTeX` are made robust.

[2010/03/10 v0.15]

- `\LuaTeX` changed according to Hans Hagen's definition in the luatex mailing list.

[2010/04/03 v0.16]

- Use date and time of `.dtx` file.

[2010/04/08 v0.17]

- Option `pdfencoding=auto` added for package `hyperref`.
- Package `hologo` added.

[2010/04/18 v0.18]

- Standard index prologue replaced by corrected prologue.

- Requested date of package `hologo` updated.

5 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
*	151
\,	151
\@currentlabel	61, 75
\@gobble	13, 125
\@ifpackagelater	55
\@nil	30, 35
\@{}	103, 108, 112, 125, 157
\{	150
\}	150
A	
\addcontentsline	58, 70
\addtolength	207, 208, 211, 212
\addvspace	146
\advance	33
B	
\begin	152
C	
\CodelineIndex	182
\CS	125
\cs	155
\csname	154
\CTAN	126
D	
\day	27, 39
\docstrip	179
\DoNotIndex	185, 186, 187, 188, 189
E	
\EnableCrossrefs	183
\end	159
\endcsname	154
\enditemize	87
\endVersion	87
\eTeX	168
F	
\File	123
\footnote	94, 114
H	
\headheight	207, 209
\headsep	208, 210
\HistLabel	59, 73
\HistVersion	56, 67, 84
\hld@NameEmail	100, 102
\hld@info	12
\hld@NameEmail	97, 99
I	
\ifcodeline@index	196, 200
\ifx	21, 103, 108, 112
\ignorespacesafterend	166
\IndexPrologue	190
\iniTeX	180
\itemize	85
J	
\jobname	20
L	
\label	62, 76
\leftmargini	149
\link	91
\ltx@empty	21
\ltx@ifundefined	18
\LuaLaTeX	172
\LuaTeX	171
M	
\M	150
\MakeIndex	178
\markboth	192
\mbox	180
\meta	150
\mikTeX	177
\month	26, 38
\multiply	32
N	
\NameEmail	96, 105
\NeedsTeXFormat	2
\newcommand	52, 56, 67, 89, 96, 122, 123, 124, 125, 126, 129, 132, 133, 134, 135, 136, 137, 138, 141
\newenvironment	81, 144
\Newsgroup	129
\nobreak	160, 162
\noindent	148, 165
\nolinkurl	109, 116, 127, 130, 142
P	
\Package	122

\PackageInfo	13	\textttt	122, 123, 124, 125, 136, 137, 139, 150, 151
\PackageWarningNoLine	16	\the	37, 38, 39, 40
\par	145, 161	\time	31, 32, 33, 40
\parskip	147, 164	\topmargin	211
\PassOptionsToPackage	5		
\pdf@filemoddate	20		
\pdfLaTeX	170	U	
\pdfTeX	169	\unskip	151
\phantomsection	69	\URL	89
\plainTeX	175	\url	94
\providecommand 176, 177, 178, 179, 180, 181		
\ProvidesPackage	3		
		V	
		\Verb	124
R		\Version	83
\RequirePackage	6, 7, 8, 9, 10, 11	\vskip	147, 164
		\vspace	163
		\VTeX	181
S		X	
\section	53, 191	\x	24, 35, 36, 42
\setcounter	184	\xclass	134
\setlength	209, 210	\XeLaTeX	174
\space	105	\xemail	138
\SpecialUsageIndex	154	\XeTeX	173
\StartHistory	52, 82	\xext	137
\subsection	57, 68	\xfile	136
		\xmodule	133
T		\xnewsgroup	141
\teTeX	176	\xoption	135
\TeX	176, 177, 180, 181	\xpackage	132
\textgreater	139		
\textheight	207, 208, 212	Y	
\textless	139	\y	28, 30
\textsf	132, 133, 134, 135, 179	\year	25, 37
\textsl	178		