

The holtxdoc package

Heiko Oberdiek
<oberdiek@uni-freiburg.de>

2006/06/02 v0.7

Abstract

The package is used for the documentation of my packages in DTX format. It contains some private macros and setup for my needs. Thus do not use it. I have separated the part that may be useful for others in package hypdoc.

Contents

1	No usage	1
2	Implementation	2
2.1	Help macros	2
2.2	History	2
2.3	Formatting macros	2
2.4	Names	4
2.5	Setup	4
2.5.1	Package doc	4
2.5.2	Page layout	4
3	Installation	4
3.1	Download	4
3.2	Bundle installation	4
3.3	Package installation	5
3.4	Refresh file name databases	5
3.5	Some details for the interested	5
4	History	6
	[1999/06/26 v0.3]	6
	[2000/08/14 v0.4]	6
	[2001/08/27 v0.5]	6
	[2001/09/02 v0.6]	6
	[2006/06/02 v0.7]	6
5	Index	6

1 No usage

Caution: *This package is not intended for public use!*

It contains the macros and settings to generate the documentation of my packages in CTAN:macros/latex/contrib/oberdiek/. Thus the package does not know anything about compatibility. Only my current packages' documentation must compile.

Older versions were more interesting, because they contained code to add hyperref's features to L^AT_EX's doc system, e.g. bookmarks and index links. I separated this stuff and made a new package hypdoc.

2 Implementation

```
1 (*package)
```

Package identification.

```
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{holtxdoc}%
4   [2006/06/02 v0.7 Private additional ltxdoc support (H0)]
5 \RequirePackage[numbered]{hypdoc}
6 \RequirePackage{array}
```

2.1 Help macros

```
7 \def\hld@info#1{%
8   \PackageInfo{holtxdoc}{#1@gobble}%
9 }
10 \def\hld@warn#1{%
11   \PackageWarningNoLine{holtxdoc}{#1}%
12 }
```

2.2 History

```
13 \newcommand*\StartHistory{%
14   \section{History}%
15 }
16 \newcommand*\HistVersion[1]{%
17   \subsection*{%
18     \phantomsection
19     \addcontentsline{toc}{subsection}{[#1]}%
20     [#1]%
21   }%
22   \def\HistLabel##1{%
23     \begingroup
24       \edef\x{[#1]}%
25       \let\@currentlabel\x
26       \label{##1}%
27     \endgroup
28   }%
29 }
30 \newenvironment{History}{%
31   \StartHistory
32   \def\Version##1{%
33     \HistVersion{##1}%
34     \itemize
35   }%
36   \let\endVersion\enditemize
37 }{}
```

2.3 Formatting macros

\UrlFoot

#1: text

#2: url

```
38 \newcommand{\URL}[2]{%
39   #1\footnote{Url: \url{#2}}%
40 }
```

\NameEmail

#1: name

#2: email address

```
41 \newcommand*\NameEmail[2]{%
42   \expandafter\hld@NameEmail\expandafter{#2}{#1}%
43 }
44 \def\hld@NameEmail#1#2{%
45   \expandafter\hld@@NameEmail\expandafter{#2}{#1}%
46 }
```

```

46 }
47 \def\hld@@NameEmail#1#2{%
48   \ifx\\#1#2\\%
49     \hld@warn{%
50       Command \string\NameEmail\space without name and email%
51     }%
52   \else
53     \ifx\\#1\\%
54       \href{mailto:#2}{\nolinkurl{#2}}%
55     \else
56       #1%
57     \ifx\\#2\\%
58     \else
59       \footnote{%
60         #1's email address: %
61         \href{mailto:#2}{\nolinkurl{#2}}%
62       }%
63     \fi
64   \fi
65 \fi
66 }

67 \newcommand*{\Package}[1]{\texttt{#1}}
68 \newcommand*{\File}[1]{\texttt{#1}}
69 \newcommand*{\Verb}[1]{\texttt{#1}}
70 \newcommand*{\CS}[1]{\texttt{\expandafter\@gobble\string\#1}}

71 \newcommand*{\CTAN}[1]{%
72   \href{ftp://ftp.ctan.org/tex-archive/#1}{\nolinkurl{CTAN:#1}}%
73 }

74 \newcommand*{\Newsgroup}[1]{%
75   \href{http://groups.google.com/group/#1}{\nolinkurl{news:#1}}%
76 }

77 \newcommand*{\xpackage}[1]{\textsf{#1}}
78 \newcommand*{\xclass}[1]{\textsf{#1}}
79 \newcommand*{\xoption}[1]{\textsf{#1}}
80 \newcommand*{\xfile}[1]{\texttt{#1}}
81 \newcommand*{\xext}[1]{\texttt{.#1}}
82 \newcommand*{\xemail}[1]{%
83   \textless\texttt{#1}\textgreater%
84 }
85 \newcommand*{\xnewsgroup}[1]{\texttt{#1}}

```

The following environment declcs is derived from environment decl of ltxguide.cls:

```

86 \newenvironment{declcs}[1]{%
87   \par
88   \addvspace{4.5ex plus 1ex}%
89   \vskip -\parskip
90   \noindent
91   \hspace{-\leftmargin}%
92   \def\M##1{\texttt{\{}\meta{##1}\texttt{\}}}%
93   \def\*{\unskip\,\texttt{*}}%
94   \begin{tabular}{|l|}%
95     \hline
96     \expandafter\SpecialUsageIndex\csname #1\endcsname
97     \cs{#1}%
98   }\%
99   \\
100   \hline
101   \end{tabular}%
102   \nobreak
103   \par

```


Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting docstrip archive. The files are extracted by running the `.dtx` through plain- \TeX :

```
tex holtxdoc.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
holtxdoc.sty → tex/latex/oberdiek/holtxdoc.sty
holtxdoc.pdf → doc/latex/oberdiek/holtxdoc.pdf
holtxdoc.dtx → source/latex/oberdiek/holtxdoc.dtx
```

If you have a `docstrip.cfg` that configures and enables docstrip's TDS installing feature, then some files can already be in the right place, see the documentation of docstrip.

3.4 Refresh file name databases

If your \TeX distribution (te \TeX , mi \TeX , ...) relies on file name databases, you must refresh these. For example, te \TeX users run `texhash` or `mktexlsr`.

3.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk holtxdoc.pdf unpack_files output .
```

Unpacking with \LaTeX . The `.dtx` chooses its action depending on the format:
plain- \TeX : Run docstrip and extract the files.

\LaTeX : Generate the documentation.

If you insist on using \LaTeX for docstrip (really, docstrip does not need \LaTeX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{holtxdoc.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdf \LaTeX :

```
pdflatex holtxdoc.dtx
makeindex -s gind.ist holtxdoc.idx
pdflatex holtxdoc.dtx
makeindex -s gind.ist holtxdoc.idx
pdflatex holtxdoc.dtx
```

4 History

[1999/06/26 v0.3]

- ...

[2000/08/14 v0.4]

- ...

[2001/08/27 v0.5]

- ...

[2001/09/02 v0.6]

- ...

[2006/06/02 v0.7]

- Major change: most is put into a new package `hypdoc`.

5 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols			
<code>*</code>	93	<code>\endVersion</code>	36
<code>\,</code>	93	<code>\eTeX</code>	110
<code>\@currentlabel</code>	25	F	
<code>\@gobble</code>	8, 70	<code>\File</code>	68
<code>\%</code>	48, 53, 57, 70, 99	<code>\footnote</code>	39, 59
<code>\{</code>	92	H	
<code>\}</code>	92	<code>\headheight</code>	127, 129
A		<code>\headsep</code>	128, 130
<code>\addcontentsline</code>	19	<code>\HistLabel</code>	22
<code>\addtolength</code>	127, 128, 131, 132	<code>\HistVersion</code>	16, 33
<code>\addvspace</code>	88	<code>\hld@NameEmail</code>	45, 47
B		<code>\hld@info</code>	7
<code>\begin</code>	94	<code>\hld@NameEmail</code>	42, 44
C		<code>\hld@warn</code>	10, 49
<code>\CodelineIndex</code>	119	<code>\hline</code>	95, 100
<code>\CS</code>	70	<code>\href</code>	54, 61, 72, 75
<code>\cs</code>	97	<code>\hspace</code>	91
<code>\csname</code>	96	I	
<code>\CTAN</code>	71	<code>\ifx</code>	48, 53, 57
D		<code>\ignorespacesafterend</code>	108
<code>\docstrip</code>	116	<code>\itemize</code>	34
<code>\DoNotIndex</code>	122, 123, 124, 125, 126	L	
E		<code>\label</code>	26
<code>\EnableCrossrefs</code>	120	<code>\LaTeX</code>	112
<code>\end</code>	101	<code>\leftmargin</code>	91
<code>\endcsname</code>	96	M	
<code>\enditemize</code>	36	<code>\M</code>	92
		<code>\MakeIndex</code>	115

<code>\mbox</code>	110, 117	<code>\StartHistory</code>	13, 31
<code>\meta</code>	92	<code>\subsection</code>	17
<code>\miktex</code>	114		
N			
<code>\NameEmail</code>	41, 50	<code>\teTeX</code>	113
<code>\NeedsTeXFormat</code>	2	<code>\TeX</code>	110, 111, 113, 114, 117, 118
<code>\newcommand</code> 13, 16, 38, 41, 67, 68, 69, 70, 71, 74, 77, 78, 79, 80, 81, 82, 85		<code>\textgreater</code>	83
<code>\newenvironment</code>	30, 86	<code>\textheight</code>	127, 128, 132
<code>\Newsgroup</code>	74	<code>\textless</code>	83
<code>\nobreak</code>	102, 104	<code>\textsf</code>	77, 78, 79, 116
<code>\noindent</code>	90, 107	<code>\textsl</code>	115
<code>\nolinkurl</code>	54, 61, 72, 75	<code>\texttt</code>	67, 68, 69, 70, 80, 81, 83, 85, 92, 93
P			
<code>\Package</code>	67	<code>\topmargin</code>	131
<code>\PackageInfo</code>	8		
<code>\PackageWarningNoLine</code>	11	U	
<code>\par</code>	87, 103	<code>\unskip</code>	93
<code>\parskip</code>	89, 106	<code>\URL</code>	38
<code>\pdfLaTeX</code>	112	<code>\url</code>	39
<code>\pdfTeX</code>	111		
<code>\phantomsection</code>	18	V	
<code>\plainTeX</code>	117	<code>\varepsilon</code>	110
<code>\providecommand</code>	110, 111, 112, 113, 114, 115, 116, 117, 118	<code>\Verb</code>	69
<code>\ProvidesPackage</code>	3	<code>\Version</code>	32
R			
<code>\RequirePackage</code>	5, 6	<code>\vskip</code>	89, 106
S			
<code>\section</code>	14	<code>\vspace</code>	105
<code>\setcounter</code>	121	<code>\VTeX</code>	118
<code>\setlength</code>	129, 130		
<code>\space</code>	50	X	
<code>\SpecialUsageIndex</code>	96	<code>\x</code>	24, 25
		<code>\xclass</code>	78
		<code>\xemail</code>	82
		<code>\xext</code>	81
		<code>\xfile</code>	80
		<code>\xnewsgroup</code>	85
		<code>\xoption</code>	79
		<code>\xpackage</code>	77