

The holtxdoc package

Heiko Oberdiek
<oberdiek@uni-freiburg.de>

2008/08/11 v0.11

Abstract

The package is used for the documentation of my packages in DTX format. It contains some private macros and setup for my needs. Thus do not use it. I have separated the part that may be useful for others in package hypdoc.

Contents

1	No usage	1
2	Implementation	2
2.1	Help macros	2
2.2	History	2
2.3	Formatting macros	2
2.4	Names	4
2.5	Setup	4
2.5.1	Package doc	4
2.5.2	Page layout	5
3	Installation	5
3.1	Download	5
3.2	Bundle installation	5
3.3	Package installation	5
3.4	Refresh file name databases	6
3.5	Some details for the interested	6
4	History	6
[1999/06/26 v0.3]		6
[2000/08/14 v0.4]		6
[2001/08/27 v0.5]		6
[2001/09/02 v0.6]		6
[2006/06/02 v0.7]		6
[2007/10/21 v0.8]		7
[2007/11/11 v0.9]		7
[2007/12/12 v0.10]		7
[2008/08/11 v0.11]		7
5	Index	7

1 No usage

Caution: *This package is not intended for public use!*

It contains the macros and settings to generate the documentation of my packages in [CTAN:macros/latex/contrib/oberdiek/](#). Thus the package does not

know anything about compatibility. Only my current packages' documentation must compile.

Older versions were more interesting, because they contained code to add `hyperref`'s features to L^AT_EX's `doc` system, e.g. bookmarks and index links. I separated this stuff and made a new package `hypdoc`.

2 Implementation

```
1 (*package)
```

Package identification.

```
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{holtxdoc}%
4   [2008/08/11 v0.11 Private additional ltxdoc support (HO)]
5 \RequirePackage[numbered]{hypdoc}
6 \RequirePackage{array}
```

2.1 Help macros

```
7 \def\hld@info#1{%
8   \PackageInfo{holtxdoc}{#1\@gobble}%
9 }
10 \def\hld@warn#1{%
11   \PackageWarningNoLine{holtxdoc}{#1}%
12 }
```

2.2 History

```
13 \newcommand*\StartHistory{%
14   \section{History}%
15 }
16 \newcommand*\HistVersion[1]{%
17   \subsection{%
18     \phantomsection
19     \addcontentsline{toc}{subsection}{[#1]}% hash-ok
20     [#1]% hash-ok
21   }%
22   \def\HistLabel##1{%
23     \begingroup
24       \edef\x{[#1]}% hash-ok
25       \let\@currentlabel\x
26       \label{##1}%
27     \endgroup
28   }%
29 }
30 \newenvironment{History}{%
31   \StartHistory
32   \def\Version##1{%
33     \HistVersion{##1}%
34     \itemize
35   }%
36   \let\endVersion\enditemize
37 }{}
```

2.3 Formatting macros

`\UrlFoot`

`#1`: text

`#2`: url

```
38 \newcommand{\URL}[2]{%
39   \begingroup
40     \def\link{\href{#2}}%
41     #1%
```

```

42 \endgroup
43 \footnote{Url: \url{#2}}%
44 }

\NameEmail
#1: name
#2: email address

45 \newcommand*{\NameEmail}[2]{%
46   \expandafter\hld@NameEmail\expandafter{#2}{#1}%
47 }
48 \def\hld@NameEmail#1#2{%
49   \expandafter\hld@@NameEmail\expandafter{#2}{#1}%
50 }
51 \def\hld@@NameEmail#1#2{%
52   \ifx\\#1#2\\%
53     \hld@warn{%
54       Command \string\NameEmail\space without name and email%
55     }%
56   \else
57     \ifx\\#1\\%
58       \href{mailto:#2}{\nolinkurl{#2}}%
59     \else
60       #1%
61       \ifx\\#2\\%
62       \else
63         \footnote{%
64           #1's email address: %
65           \href{mailto:#2}{\nolinkurl{#2}}%
66         }%
67       \fi
68     \fi
69   \fi
70 }

71 \newcommand*{\Package}[1]{\texttt{#1}}
72 \newcommand*{\File}[1]{\texttt{#1}}
73 \newcommand*{\Verb}[1]{\texttt{#1}}
74 \newcommand*{\CS}[1]{\texttt{\expandafter\@gobble\string\#1}}

75 \newcommand*{\CTAN}[1]{%
76   \href{ftp://ftp.ctan.org/tex-archive/#1}{\nolinkurl{CTAN:#1}}%
77 }

78 \newcommand*{\Newsgroup}[1]{%
79   \href{http://groups.google.com/group/#1/topics}{\nolinkurl{news:#1}}%
80 }

81 \newcommand*{\xpackage}[1]{\textsf{#1}}
82 \newcommand*{\xclass}[1]{\textsf{#1}}
83 \newcommand*{\xoption}[1]{\textsf{#1}}
84 \newcommand*{\xfile}[1]{\texttt{#1}}
85 \newcommand*{\xext}[1]{\texttt{.#1}}
86 \newcommand*{\xemail}[1]{%
87   \textless\texttt{#1}\textgreater%
88 }
89 \newcommand*{\xnewsgroup}[1]{%
90   \href{news:#1}{\nolinkurl{#1}}%
91 }

```

The following environment declcs is derived from environment decl of ltxguide.cls:

```

92 \newenvironment{declcs}[1]{%
93   \par
94   \addvspace{4.5ex plus 1ex}%
95   \vskip -\parskip

```

```

96 \noindent
97 \hspace{-\leftmargin}%
98 \def\M##1{\texttt{\{}\meta{##1}\texttt{\}}}%
99 \def\*{\unskip\,\texttt{*}}%
100 \begin{tabular}{|l|}%
101 \hline
102 \expandafter\SpecialUsageIndex\csname #1\endcsname
103 \cs{#1}%
104 }{%
105 \\\%
106 \hline
107 \end{tabular}%
108 \nobreak
109 \par
110 \nobreak
111 \vspace{2.3ex}%
112 \vskip -\parskip
113 \noindent
114 \ignorespacesafterend
115 }

```

2.4 Names

```

116 \providecommand*\eTeX{\mbox{$\varepsilon$-TeX}}
117 \providecommand*\pdfTeX{\pdf\TeX}
118 \providecommand*\pdfLaTeX{\pdf\LaTeX}
119 \providecommand*\LuaTeX{\L\textsc{ua}\TeX}
120 \def\@temp#1#2{%
121 \providecommand*{#1}{%
122 \begingroup
123 X%
124 \@ifundefined{rotatebox}{e}{%
125 \lower0.5ex\hbox{%
126 \setbox0=\hbox{E}%
127 \dimen0=\ht0 %
128 \advance\dimen0 by \dp0 %
129 \raise\dimen0\hbox{\rotatebox{180}{\box0}}}%
130 }%
131 }%
132 #2%
133 \endgroup
134 }%
135 }
136 \@temp\XeTeX\TeX
137 \@temp\XeLaTeX\LaTeX
138 \providecommand*\teTeX{\te\TeX}
139 \providecommand*\mikTeX{\mik\TeX}
140 \providecommand*\MakeIndex{\textsl{MakeIndex}}
141 \providecommand*\docstrip{\textsf{docstrip}}
142 \providecommand*\plainTeX{\mbox{plain-TeX}}
143 \providecommand*\iniTeX{\mbox{ini-TeX}}
144 \providecommand*\VTeX{\V\TeX}

```

2.5 Setup

2.5.1 Package doc

```

145 \CodelineIndex
146 \EnableCrossrefs
147 \setcounter{IndexColumns}{2}

148 \DoNotIndex{\begingroup,\endgroup,\bgroup,\egroup}
149 \DoNotIndex{\def,\edef,\xdef,\global,\long,\let}
150 \DoNotIndex{\expandafter,\noexpand,\string}

```

```

151 \DoNotIndex{\else,\fi,\or}
152 \DoNotIndex{\relax}

```

2.5.2 Page layout

```

153 \addtolength{\textheight}{\headheight}
154 \addtolength{\textheight}{\headsep}
155 \setlength{\headheight}{0pt}
156 \setlength{\headsep}{0pt}
157 \addtolength{\topmargin}{-10mm}
158 \addtolength{\textheight}{20mm}
159 \end{package}

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/holtxdoc.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/holtxdoc.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```

chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/

```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain-T_EX:

```
tex holtxdoc.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```

holtxdoc.sty → tex/latex/oberdiek/holtxdoc.sty
holtxdoc.pdf → doc/latex/oberdiek/holtxdoc.pdf
holtxdoc.dtx → source/latex/oberdiek/holtxdoc.dtx

```

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

¹<http://ftp.ctan.org/tex-archive/>

3.4 Refresh file name databases

If your $\text{T}_{\text{E}}\text{X}$ distribution ($\text{t}_{\text{E}}\text{T}_{\text{E}}\text{X}$, $\text{m}_{\text{ik}}\text{T}_{\text{E}}\text{X}$, ...) relies on file name databases, you must refresh these. For example, $\text{t}_{\text{E}}\text{T}_{\text{E}}\text{X}$ users run `texhash` or `mktextlsr`.

3.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk holtxdoc.pdf unpack_files output .
```

Unpacking with $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$. The `.dtx` chooses its action depending on the format:

plain- $\text{T}_{\text{E}}\text{X}$: Run `docstrip` and extract the files.

$\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$: Generate the documentation.

If you insist on using $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ for `docstrip` (really, `docstrip` does not need $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{holtxdoc.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdf $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$` :

```
pdflatex holtxdoc.dtx
makeindex -s gind.ist holtxdoc.idx
pdflatex holtxdoc.dtx
makeindex -s gind.ist holtxdoc.idx
pdflatex holtxdoc.dtx
```

4 History

[1999/06/26 v0.3]

- ...

[2000/08/14 v0.4]

- ...

[2001/08/27 v0.5]

- ...

[2001/09/02 v0.6]

- ...

[2006/06/02 v0.7]

- Major change: most is put into a new package `hypdoc`.

[2007/10/21 v0.8]

- \XeTeX and \XeLaTeX added.

[2007/11/11 v0.9]

- \LuaTeX added.

[2007/12/12 v0.10]

- \iniTeX added.

[2008/08/11 v0.11]

- \Newsgroup, \xnewsgroup, and \URL updated.

5 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	\eTeX	116
*		99
\,		99
\@currentlabel		25
\@gobble		8, 74
\@ifundefined		124
\@temp		120, 136, 137
\\		52, 57, 61, 74, 105
\{		98
\}		98
A		
\addcontentsline		19
\addtolength		153, 154, 157, 158
\advspace		94
\advance		128
B		
\begin		100
\box		129
C		
\CodelineIndex		145
\CS		74
\cs		103
\csname		102
\CTAN		75
D		
\dimen		127, 128, 129
\docstrip		141
\DoNotIndex		148, 149, 150, 151, 152
\dp		128
E		
\EnableCrossrefs		146
\end		107
\endcsname		102
\enditemize		36
\endVersion		36
F		
\File		72
\footnote		43, 63
H		
\hbox		125, 126, 129
\headheight		153, 155
\headsep		154, 156
\HistLabel		22
\HistVersion		16, 33
\hld@@NameEmail		49, 51
\hld@info		7
\hld@NameEmail		46, 48
\hld@warn		10, 53
\hline		101, 106
\href		40, 58, 65, 76, 79, 90
\hspace		97
\ht		127
I		
\ifx		52, 57, 61
\ignorespacesafterend		114
\iniTeX		143
\itemize		34
L		
\label		26
\LaTeX		118, 137
\leftmargin		97
\link		40
\lower		125
\LuaTeX		119
M		
\M		98
\MakeIndex		140
\mbox		116, 142, 143
\meta		98
\miktex		139

N		<code>\subsection</code> 17
<code>\NameEmail</code> 45, 54		T
<code>\NeedsTeXFormat</code> 2		<code>\teTeX</code> 138
<code>\newcommand</code> 13, 16, 38, 45, 71, 72, 73, 74, 75, 78, 81, 82, 83, 84, 85, 86, 89		<code>\TeX</code> 116, 117, 119, 136, 138, 139, 142, 143, 144
<code>\newenvironment</code> 30, 92		<code>\textgreater</code> 87
<code>\Newsgroup</code> 78		<code>\textheight</code> 153, 154, 158
<code>\nobreak</code> 108, 110		<code>\textless</code> 87
<code>\noindent</code> 96, 113		<code>\textsc</code> 119
<code>\nolinkurl</code> 58, 65, 76, 79, 90		<code>\textsf</code> 81, 82, 83, 141
P		<code>\textsl</code> 140
<code>\Package</code> 71		<code>\texttt</code> 71, 72, 73, 74, 84, 85, 87, 98, 99
<code>\PackageInfo</code> 8		<code>\topmargin</code> 157
<code>\PackageWarningNoLine</code> 11		U
<code>\par</code> 93, 109		<code>\unskip</code> 99
<code>\parskip</code> 95, 112		<code>\URL</code> 38
<code>\pdfLaTeX</code> 118		<code>\url</code> 43
<code>\pdfTeX</code> 117		V
<code>\phantomsection</code> 18		<code>\varepsilon</code> 116
<code>\plainTeX</code> 142		<code>\Verb</code> 73
<code>\providecommand</code> 116, 117, 118, 119, 121, 138, 139, 140, 141, 142, 143, 144		<code>\Version</code> 32
<code>\ProvidesPackage</code> 3		<code>\vskip</code> 95, 112
R		<code>\vspace</code> 111
<code>\raise</code> 129		<code>\VTeX</code> 144
<code>\RequirePackage</code> 5, 6		X
<code>\rotatebox</code> 129		<code>\x</code> 24, 25
S		<code>\xclass</code> 82
<code>\section</code> 14		<code>\XeLaTeX</code> 137
<code>\setbox</code> 126		<code>\xemail</code> 86
<code>\setcounter</code> 147		<code>\XeTeX</code> 136
<code>\setlength</code> 155, 156		<code>\xext</code> 85
<code>\space</code> 54		<code>\xfile</code> 84
<code>\SpecialUsageIndex</code> 102		<code>\xnewsgroup</code> 89
<code>\StartHistory</code> 13, 31		<code>\xoption</code> 83
		<code>\xpackage</code> 81