

The `hypcap` package

Heiko Oberdiek*

2016/05/16 v1.12

Abstract

This package tries a solution of the problem with `hyperref`, that links to floats points below the caption and not at the beginning of the float. Therefore this package divides the task into two part, the link setting with `\capstart` or automatically at the beginning of a float and the rest in the `\caption` command.

Contents

1	Usage	2
1.1	Package options	2
1.2	User commands	2
1.3	Limitations	3
2	Implementation	3
3	Installation	5
3.1	Download	5
3.2	Bundle installation	6
3.3	Package installation	6
3.4	Refresh file name databases	6
3.5	Some details for the interested	6
4	History	7
	[1999/02/13 v1.0]	7
	[2000/08/14 v1.1]	7
	[2000/09/07 v1.2]	7
	[2001/08/27 v1.3]	7
	[2001/09/06 v1.4]	7
	[2006/02/20 v1.5]	7
	[2007/02/19 v1.6]	7
	[2007/04/09 v1.7]	7
	[2008/04/14 v1.8]	8
	[2008/08/11 v1.9]	8
	[2008/09/08 v1.10]	8
	[2011/02/16 v1.11]	8
	[2016/05/16 v1.12]	8

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

1 Usage

The package `hycap` requires that `hyperref` is loaded first:

```
\usepackage[...]{hyperref}
\usepackage[...]{hycap}
```

1.1 Package options

The names of the four float environments `figure`, `figure*`, `table`, or `table*` can be used as option. Then the package redefines the environment in order to insert `\capstart` (see below) in the beginning of the environment automatically.

Option `all` enables the redefinitions of all four float environments. For other environments see the user command `\hycapredef`.

1.2 User commands

`\capstart` **\capstart:** First this command increments the counter (`\@captype`). Then it makes an anchor for package `hyperref`. At last `\caption` is redefined to remove the anchor setting part from `hyperref`'s `\caption`.

The package expects the following structure of a float environment:

```
\begin{float}...
\capstart
...
\caption{...}
...
\end{float}
```

There can be several `\caption` commands. For these you need `\capstart` again:

```
\capstart ... \caption... \capstart ... \caption...
```

And the `\caption` command itself can be put in a group.

With the options, described above, the extra writing of `\capstart` can be avoided. Consequently, there must be a `\caption` in every environment of this type, specified by the option. If you want to use more than one `\caption` in this environment, you have to state `\capstart` again.

`\hycapSPACE` **\hycapSPACE:** Because it looks poor, if the link points exactly at top of the figure, there is additional space: `\hycapSPACE`, the default is `0.5\baselineskip`, examples:

```
\renewcommand{\hycapSPACE}{0pt} removes the space
\renewcommand{\hycapSPACE}{1pt} sets a fix value
```

`\hycapredef` **\hycapredef:** If there are other float environments, that should automatically execute `\capstart`, then a redefinition with `\hycapredef` can be tried:

```
\hycapredef{myfloat}
```

Only environments with one optional parameter are supported.

`\capstartfalse` **\capstartfalse, \capstarttrue:** Since 2008/09/08 v1.10.
`\capstarttrue` They disable and enable `\capstart`. They can be used to cancel the effect of a redefined float environment. Example:

```

\documentclass{article}
\usepackage{hyperref}
\usepackage[figure]{hypcap}[2008/09/08]

\begin{document}
  \section{Hello World}
  \begin{figure}
    \caption{Figure with caption A}
  \end{figure}
  \capstartfalse
  \begin{figure}
    Figure without caption
  \end{figure}
  \capstarttrue
  \begin{figure}
    \caption{Figure with caption B}
  \end{figure}
\end{document}

```

1.3 Limitations

- Packages that redefine `\caption` or `\@caption`.

2 Implementation

```
1 \<{*package}
```

Package identification.

```

2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{hypcap}%
4   [2016/05/16 v1.12 Adjusting the anchors of captions (H0)]

```

For unique command names this package uses `hc@` as prefix for internal command names.

First we check, if package `hyperref` is loaded:

```

5 \@ifundefined{hyper@@anchor}{%
6   \PackageError{hypcap}{You have to load 'hyperref' first}\@ehc
7   \endinput
8 }{}
9 \RequirePackage{letltxmacro}[2008/06/24]

```

`\hc@org@caption` Save the original meaning of `\caption`:

```

10 \newcommand*\hc@org@caption{}
11 \let\hc@org@caption\caption

```

`\if@capstart` The switch `\if@capstart` helps to detect `\capstart` commands with missing `\caption` macros. Because `\caption` can occur inside a group, assignments to the switch have to be made global.

```
12 \newif\if@capstart
```

`\hypcapSPACE` The anchor is raised by `\hypcapSPACE`.

```
13 \newcommand*\hypcapSPACE{.5\baselineskip}
```

`\ifcapstart`

```

14 \newif\ifcapstart
15 \capstarttrue

```

`\capstart` The macro `\capstart` contains the first part of the `\caption` command: Incrementing the counter and setting the anchor.

```

16 \newcommand*\capstart{%
17   \ifcapstart
18     \H@refstepcounter\@captype % first part of caption
19     \hyper@makecurrent\@captype
20     \global\let\hc@currentHref\@currentHref
21     \vspace*{-\hypcapspace}%
22     \begingroup
23       \let\leavevmode\relax
24       \hyper@@anchor\@currentHref\relax
25     \endgroup
26     \vspace*{\hypcapspace}%
27     \hc@hyperref{\let\caption\hc@caption}%
28     \global\@capstarttrue
29     \global\advance\csname c@\@captype\endcsname\m@ne
30   \fi
31 }

32 \@ifpackagelater{hyperref}{2007/04/09}{%
33   \let\hc@hyperref\@gobble
34 }{%
35   \let\hc@hyperref\@firstofone
36 }

```

`\hc@caption` The new `\caption` command without the first part is defined in the macro `\hc@caption`.

```

37 \def\hc@caption{%
38   \global\advance\csname c@\@captype\endcsname\@ne
39   \@dblarg{\hc@@caption\@captype}%
40 }

```

`\hc@@caption` This is a copy of package `hyperref`'s `\@caption` macro without making the anchor, because this is already done in `\capstart`.

```

41 \long\def\hc@@caption#1[#2]#3{%
42   \let\caption\hc@org@caption
43   \global\@capstartfalse
44   \ifHy@hypertextnames
45     \hyper@makecurrent\@captype
46   \else
47     \global\let\@currentHref\hc@currentHref
48   \fi
49   \par\addcontentsline{%
50     \csname ext@#1\endcsname\}{#1}{%
51     \protect\numberline{%
52       \csname the#1\endcsname
53     }\ignorespaces #2}%
54   }%
55   \begingroup
56     \@parboxrestore
57     \normalsize
58     \@makecaption{\csname fnum@#1\endcsname}{%
59       \ignorespaces#3%
60     }%
61   \par
62 \endgroup
63 }

```

`\hypcapredef` The macro `\hypcapredef` prepares the call of `\hc@redef` that will redefine the environment that is given in the argument.

```

64 \def\hypcapredef#1{%
65   \expandafter\hc@redef\csname hc@org#1\expandafter\endcsname
66                                   \csname hc@orgend#1\expandafter\endcsname
67                                   \expandafter{#1}%
68 }

```

`\hc@redef` The old meaning of the environment is saved. Then `\capstart` is appended in the begin part. The end part contains a check that produces an error message in case of `\capstart` without `\capstart` (`\capstart` has incremented the counter).

```

69 \def\hc@redef#1#2#3{%
70   \newcommand#1{%
71     \expandafter\LetLtxMacro\expandafter#1\csname#3\endcsname
72     \expandafter\LetLtxMacro\expandafter#2\csname end#3\endcsname
73     \renewenvironment*{#3}[1] []{%
74       \ifx\##1\%
75         #1\relax
76       \else
77         #1[##1]% hash-ok (compatibility for float)
78       \fi
79       \capstart
80     }{%
81       \if@capstart
82         \PackageError{hypcap}{You have forgotten to use \string\caption}%
83         \global\@capstartfalse
84       \else
85         \fi
86       #2%
87     }%
88 }

```

At last the options are defined and processed.

```

89 \DeclareOption{figure}{\hypcapredef{\CurrentOption}}
90 \DeclareOption{figure*}{\hypcapredef{\CurrentOption}}
91 \DeclareOption{table}{\hypcapredef{\CurrentOption}}
92 \DeclareOption{table*}{\hypcapredef{\CurrentOption}}
93 \DeclareOption{all}{%
94   \hypcapredef{figure}%
95   \hypcapredef{figure*}%
96   \hypcapredef{table}%
97   \hypcapredef{table*}%
98 }
99 \ProcessOptions\relax
100 \end{package}

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

CTAN:macros/latex/contrib/oberdiek/hypcap.dtx The source file.

CTAN:macros/latex/contrib/oberdiek/hypcap.pdf Documentation.

¹CTAN:pkg/hypcap

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps.

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain T_EX:

```
tex hypcap.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
hypcap.sty → tex/latex/oberdiek/hypcap.sty
hypcap.pdf → doc/latex/oberdiek/hypcap.pdf
hypcap.dtx → source/latex/oberdiek/hypcap.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your T_EX distribution (t_eT_EX, m_ikT_EX, ...) relies on file name databases, you must refresh these. For example, t_eT_EX users run `texhash` or `mktextlsr`.

3.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{hypcap.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex hypcap.dtx
makeindex -s gind.ist hypcap.idx
pdflatex hypcap.dtx
makeindex -s gind.ist hypcap.idx
pdflatex hypcap.dtx
```

4 History

[1999/02/13 v1.0]

- A beginning version, published in newsgroup `comp.text.tex`:
“Re: `hyperref` and figures”²

[2000/08/14 v1.1]

- Global assignments of `\if@capstart` in order to allow `\caption` in groups.
- Option `all` added.

[2000/09/07 v1.2]

- Package in dtx format.

[2001/08/27 v1.3]

- Bug fix with `hyperref`’s `pdfmark` driver
(`\leavevmode` in `\hyper@@anchor/\pdf@rect`).

[2001/09/06 v1.4]

- Small fixes in the dtx file.

[2006/02/20 v1.5]

- Code is not changed.
- New DTX framework.

[2007/02/19 v1.6]

- Fix for `hypertextnames=false`.

[2007/04/09 v1.7]

- Stuff in `\caption` moved to `hyperref`. This avoids redefinitions of `\caption` and `\@caption` (idea of Axel Sommerfeldt).
- Fix for subfigure (Marco Kuhlmann, Amilcar do Carmo Lucas).

²Url: <https://groups.google.com/group/comp.text.tex/msg/5c9b47b001a9379c>

[2008/04/14 v1.8]

- `\hc@redef` fixed to get package float work (Axel Sommerfeldt).

[2008/08/11 v1.9]

- Code is not changed.
- URLs updated.

[2008/09/08 v1.10]

- `\capstartfalse` and `\capstarttrue` added.

[2011/02/16 v1.11]

- `\hc@redef` fixed by using package `letltxmacro`.

[2016/05/16 v1.12]

- Documentation updates.

5 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
<code>\@capstartfalse</code>	43, 83
<code>\@capstarttrue</code>	28
<code>\@captype</code>	18, 19, 29, 38, 39, 45
<code>\@currentHref</code>	20, 24, 47
<code>\@dblarg</code>	39
<code>\@ehc</code>	6
<code>\@firstofone</code>	35
<code>\@gobble</code>	33
<code>\@ifpackagelater</code>	32
<code>\@ifundefined</code>	5
<code>\@makecaption</code>	58
<code>\@ne</code>	38
<code>\@parboxrestore</code>	56
<code>\@</code>	74
A	
<code>\addcontentsline</code>	49
<code>\advance</code>	29, 38
B	
<code>\baselineskip</code>	13
C	
<code>\capstart</code>	2, <u>16</u> , 79
<code>\capstartfalse</code>	2
<code>\capstarttrue</code>	2, 15
<code>\caption</code>	11, 27, 42, 82
<code>\csname</code> 29, 38, 50, 52, 58, 65, 66, 71, 72	
<code>\CurrentOption</code>	89, 90, 91, 92
D	
<code>\DeclareOption</code>	89, 90, 91, 92, 93
E	
<code>\endcsname</code>	29, 38, 50, 52, 58, 65, 66, 71, 72
<code>\endinput</code>	7
H	
<code>\H@refstepcounter</code>	18
<code>\hc@caption</code>	39, <u>41</u>
<code>\hc@caption</code>	27, <u>37</u>
<code>\hc@currentHref</code>	20, 47
<code>\hc@hyperref</code>	27, 33, 35
<code>\hc@org@caption</code>	<u>10</u> , 42
<code>\hc@redef</code>	65, <u>69</u>
<code>\hycapredef</code>	2, <u>64</u> , 89, 90, 91, 92, 94, 95, 96, 97
<code>\hycapspace</code>	2, <u>13</u> , 21, 26
<code>\hyper@anchor</code>	24
<code>\hyper@makecurrent</code>	19, 45
I	
<code>\if@capstart</code>	<u>12</u> , 12, 81
<code>\ifcapstart</code>	<u>14</u> , 17
<code>\ifHy@hypertexnames</code>	44
<code>\ifx</code>	74
<code>\ignorespaces</code>	53, 59

L		P	
<code>\leavevmode</code>	23	<code>\PackageError</code>	6, 82
<code>\LetLtxMacro</code>	71, 72	<code>\par</code>	49, 61
M		R	
<code>\m@ne</code>	29	<code>\ProcessOptions</code>	99
		<code>\protect</code>	51
		<code>\ProvidesPackage</code>	3
N		V	
<code>\NeedsTeXFormat</code>	2	<code>\renewenvironment</code>	73
<code>\newcommand</code>	10, 13, 16, 70	<code>\RequirePackage</code>	9
<code>\newif</code>	12, 14		
<code>\normalsize</code>	57		
<code>\numberline</code>	51	<code>\vspace</code>	21, 26