

# The hypdoc package

Heiko Oberdiek  
<heiko.oberdiek at gmail.com>

2010/03/26 v1.9

## Abstract

This package adds hyper features to the package `doc` that is used in the documentation system of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>. Bookmarks are added and references are linked as far as possible.

## Contents

<b>1</b>	<b>Features</b>	<b>2</b>
<b>2</b>	<b>Usage</b>	<b>3</b>
2.1	Options	3
2.2	Simple example	3
2.3	Example <code>source2e.tex</code>	4
<b>3</b>	<b>Implementation</b>	<b>4</b>
3.1	Options	4
3.2	Package loading	4
3.2.1	Patch for bug latex/4096	5
3.3	Bookmarks	5
3.4	<code>\tableofcontents</code>	6
3.5	<code>\listoffigures</code>	6
3.6	<code>\listoftables</code>	7
3.7	<code>\thebibliography</code>	7
3.8	<code>\theindex</code>	7
3.9	<code>\theglossary</code>	8
3.10	Index	9
3.11	<code>\PrintDescribeMacro</code>	11
3.12	<code>\PrintMacroName</code>	11
3.13	<code>\theCodelineNo</code>	12
3.14	<code>\SpecialUsageIndex</code>	12
3.15	<code>\autoindex</code>	12
3.16	<code>\SpecialEnvIndex</code>	13
3.17	<code>\SortIndex</code>	13
3.18	<code>\@wrglossary</code>	13
3.19	<code>\MacroIndent</code>	14
<b>4</b>	<b>Installation</b>	<b>14</b>
4.1	Download	14
4.2	Bundle installation	14
4.3	Package installation	15
4.4	Refresh file name databases	15
4.5	Some details for the interested	15

<b>5 History</b>	<b>15</b>
[2002/05/10 v1.0]	15
[2006/02/20 v1.1]	16
[2006/04/27 v1.2]	16
[2006/06/01 v1.3]	16
[2006/06/02 v1.4]	16
[2007/04/11 v1.5]	16
[2007/11/12 v1.6]	16
[2009/12/10 v1.7]	16
[2010/02/03 v1.8]	16
[2010/03/26 v1.9]	16
<b>6 Index</b>	<b>16</b>

# 1 Features

The package adds the following features:

**Bookmarks:** For supporting bookmarks package `hyperref` is loaded. Some  $\text{\TeX}$  code inside section titles can cause problems during bookmark processing; these can be warnings, ugly bookmark titles or even errors. With the help of `\pdfstringdefDisableCommands` or `\texorpdfstring` you can manage these things, see `hyperref`'s package documentation.

**Additional bookmarks:** Unnumbered bookmark entries are generated for:

- Table of contents
- List of figures
- List of tables
- Index
- Glossary

Option `numbered` controls, whether these section or chapters should be numbered. The exception is the table of contents if this it would be the first numbered section. Then just a bookmark is added.

**Metadata:** The loaded package `hyperref`, enforced by option `pdfusetitle`, tries to detect `\title` and `\author` and sets the corresponding PDF information fields. In case of problems see the previous item about bookmarks. These entries can be overwritten or new ones added by `\hypersetup` after the package is loaded, see documentation of package `hyperref`.

**References, links:** Because of package `\hyperref` `\ref` become links, also `\url`, footnote referencing are supported.

**Index:** The main part of this package deals with index links in order to support the kind of index that package `doc` provides.

**Thumbnails:** Package `thumbpdf` is loaded for the case that the PDF file also should contain thumbnails, see the documentation of this package. But thumbnail embedding is not really necessary, because nowadays AcrobatReader is able to generate and view thumbnails on the fly.

## 2 Usage

The purpose of this packages is to add PDF features to the documentation of LaTeX packages. Thus just load the package in the driver file that generates the documentation:

```
\usepackage{hypdoc}
```

Package `doc` is loaded by `hypdoc`, thus you also can replace a `\usepackage{doc}` with this line. At any case, the package must be loaded before macros of package `doc` such as `\CodelineIndex` or `\PageIndex` are used.

If the class `ltxdoc` is used, you can also use the configuration file for this class to add package `hypdoc`. Add the following line to the file `ltxdoc.cfg` (or create a new one):

```
\AtEndOfClass{\RequirePackage{hypdoc}}
```

### 2.1 Options

There is one option `numbered`. It controls, whether the starred versions of section or chapter inside `\tableofcontents`, `\listoffigures`, ... should be replaced by the non-star versions.

### 2.2 Simple example

Example of a simple driver file `foobar.drv` of a package `foobar`. Often the driver file is packed in the file `foobar.dtx` and can be extracted by `docstrip` or if an instruction file for `docstrip` is provided by:

```
tex foobar.ins
```

Note that although `docstrip` doesn't rely on L<sup>A</sup>T<sub>E</sub>X, sometimes you need to run the `.ins` file through L<sup>A</sup>T<sub>E</sub>X. Oddly enough, often the only L<sup>A</sup>T<sub>E</sub>X feature in use is `\NeedsTeXFormat{LaTeX2e}` in the first line.

```
\documentclass{ltxdoc}
\usepackage{hypdoc}
\RecordChanges
\EnableCrossrefs
\CodelineIndex
\begin{document}
\title{Title for package \texttt{foobar}}
\author{Author of package \texttt{foobar}}
\date{...}
\maketitle
\tableofcontents
\DocInput{foobar.dtx}
\PrintChanges
\PrintIndex
\end{document}
```

Then compile it, for example with `pdfLATEX`.

```
pdflatex foobar.drv
makeindex -s gind.ist foobar.idx
makeindex -s gglo.ist -o foobar.gls foobar.glo
pdflatex foobar.drv
```

You will need several cycles until the cross references and similar things are correct.

## 2.3 Example source2e.tex

The source code of the base of L<sup>A</sup>T<sub>E</sub>X is available as a bunch of .dtx files. L<sup>A</sup>T<sub>E</sub>X provides the file `source2e.tex` to merge them all together.

Now you can either load package `hypdoc` in a private copy of this file (please, respect the LPPL) or use the configuration file `ltxdoc.cfg`. Example that also sets A4 paper size:

```
\PassOptionsToClass{a4paper}{article}
\AtEndOfClass{\RequirePackage{hypdoc}}
```

Then `source2e.tex` can be compiled by pdfT<sub>E</sub>X, for example:

```
pdflatex source2e
makeindex -s gind.ist source2e.idx
makeindex -s gglo.ist -o source2e.glo source2e.gls
pdflatex source2e
makeindex -s gind.ist source2e.idx
makeindex -s gglo.ist -o source2e.glo source2e.gls
pdflatex source2e
```

## 3 Implementation

```
1 (*package)
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{hypdoc}%
4 [2010/03/26 v1.9 Hyper extensions for doc.sty (H0)]%
```

The package identification is done at the top of the .dtx file in order to use only one identification string.

For unique command names this package uses HD@ as prefix

### 3.1 Options

```
\ifHD@numbered
5 \newif\ifHD@numbered
6 \DeclareOption{numbered}{\HD@numberedtrue}
7 \ProcessOptions*\relax
```

### 3.2 Package loading

```
8 \RequirePackage{atveryend}[2010/03/24]
9 \RequirePackage{doc}
10 \ifx\numexpr\@undefined
11   \RequirePackage{calc}%
12 \fi
13 \RequirePackage[%
14   hyperindex=false,%
15   pdfusetitle,%
16   colorlinks,%
17   pdfpagelabels,%
18 ]{hyperref}[2002/05/09]%
19 \hypersetup[%
20   plainpages=false,%
21   bookmarksopen,%
22   bookmarksnumbered,%
23   bookmarksopenlevel=0,%
24   pdfstartview={FitBH \hypercalcbp{
25     \paperheight-\topmargin-1in-\headheight-\headsep
26   }},%
27 }
28 \RequirePackage{thumbpdf}
```

```

29 \newcounter{HD@unique}

\theHD@unique

30 \renewcommand{\theHD@unique}{%
31   \number\value{HD@unique}%
32 }

33 \g@addto@macro\Hy@UseMaketitleInfos{%
34   \ifundefined{fileinfo}{}%
35   \ifx\@pdfsubject\@empty
36     \hypersetup{pdfsubject={\fileinfo}}%
37   \fi
38 }%
39 }

40 \pdfstringdefDisableCommands{%
41   \let\thanks\@gobble
42   \let\footnote\@gobble
43   \def\cs#1{\textbackslash #1}%
44   \let\normalfont\@empty
45   \let\scshape\@empty
46   \def\and{and }%
47 }

```

### 3.2.1 Patch for bug latex/4096

```

48 \begingroup\expandafter\expandafter\expandafter\endgroup
49 \expandafter\ifx\csname mod@math@codes\endcsname\relax
50 \else
51   \def\HD@ModFix#1{%
52     \mathcode'#1=#1\relax
53   }%
54   \g@addto@macro\mod@math@codes{%
55     \HD@ModFix\-%
56     \HD@ModFix\+%
57     \HD@ModFix\:%
58     \HD@ModFix\=%
59     \HD@ModFix\*%
60   }%
61 \fi

```

## 3.3 Bookmarks

\HD@sectionpatch

```

62 \def\HD@sectionpatch{%
63   \ifHD@numbered
64     \HD@@sectionpatch{section}%
65     \HD@@sectionpatch{chapter}%
66   \else
67     \let\Hy@writebookmark\HD@disable@writebookmark
68   \fi
69 }

```

\HD@@sectionpatch

```

70 \def\HD@@sectionpatch#1{%
71   \expandafter\let\csname HDorg@@#1\endcsname
72   \csname #1\endcsname
73   \@namedef{#1}{%
74     \ifstar{\@nameuse{HDorg@@#1}}{\@nameuse{HDorg@@#1}}%
75   }%
76 }

```

\HD@disable@writebookmark

```

77 \def\HD@disable@writebookmark#1#2#3#4#5{}

```

`\HD@guesstoclevel` A wild guessing of the toplevel. There is the hope, that the macro #1 starts with a sectioning command.

```
78 \def\HD@guesstoclevel#1{%
79   \expandafter\HD@@guesstoclevel#1\section\HD@end
80 }
```

`\HD@@guesstoclevel`

```
81 \def\HD@@guesstoclevel#1#2\HD@end{%
82   \@ifundefined{toclevel@}{\expandafter\@gobble\string#1\@empty}{%
83     1%
84   }{%
85     \@nameuse{toclevel@}{\expandafter\@gobble\string#1\@empty}%
86   }%
87 }
```

### 3.4 `\tableofcontents`

`\HDorg@tableofcontents`

```
88 \let\HDorg@tableofcontents\tableofcontents
```

`\tableofcontents` As first section the table of contents shouldn't go into the toc itself. Also a number looks too funny then. Just a bookmark is enough in this case.

```
89 \def\tableofcontents{%
90   \begingroup
91     \@ifundefined{c@section}{%
92       \def\c@section{0}%
93     }{%
94     }%
95   \expandafter\endgroup
96   \ifcase\c@section
97     \stepcounter{HD@unique}%
98     \pdfbookmark[\HD@guesstoclevel{\HDorg@tableofcontents}]{%
99       {\contentsname}{toc\theHD@unique}%
100     }%
101   \else
102     \ifHD@numbered
103     \else
104       \stepcounter{HD@unique}%
105       \pdfbookmark[\HD@guesstoclevel{\HDorg@tableofcontents}]{%
106         {\contentsname}{toc\theHD@unique}%
107       }%
108     \fi
109     \begingroup
110       \HD@sectionpatch
111       \HDorg@tableofcontents
112     \endgroup
113   \fi
114 }
```

### 3.5 `\listoffigures`

`\HDorg@listoffigures`

```
113 \let\HDorg@listoffigures\listoffigures
```

`\listoffigures`

```
114 \def\listoffigures{%
115   \ifHD@numbered
116   \else
117     \stepcounter{HD@unique}%
118     \pdfbookmark[\HD@guesstoclevel{\HDorg@listoffigures}]{%
119       {\contentsname}{toc\theHD@unique}%
120     }%
121   \fi
122 }
```

```

121 \begingroup
122   \HD@sectionpatch
123   \HDorg@listoffigures
124 \endgroup
125 }

```

### 3.6 \listoftables

\HDorg@listoftables

```

126 \let\HDorg@listoftables\listoftables

\listoftables

127 \def\listoftables{%
128   \ifHD@numbered
129   \else
130     \stepcounter{HD@unique}%
131     \pdfbookmark[\HD@guesstoclevel{\HDorg@listoftables}]{%
132       {\contentsname}{toc\theHD@unique}%
133     \fi
134     \begingroup
135       \HD@sectionpatch
136       \HDorg@listoftables
137     \endgroup
138 }

```

### 3.7 \thebibliography

\HDorg@thebibliography

```

139 \let\HDorg@thebibliography\thebibliography

\thebibliography

140 \def\thebibliography{%
141   \ifHD@numbered
142   \else
143     \stepcounter{HD@unique}%
144     \pdfbookmark[\HD@guesstoclevel{\HDorg@thebibliography}]{%
145       {\@ifundefined{chapter}{\refname}{\bibname}}{\bib\theHD@unique}%
146     \fi
147     \HD@sectionpatch
148     \HDorg@thebibliography
149 }

```

### 3.8 \theindex

\HDorg@theindex

```

150 \let\HDorg@theindex\theindex

\theindex

151 \def\theindex{%
152   \let\HDorg@index@prologue\index@prologue
153   \let\HDorg@writebookmark\Hy@writebookmark
154   \HD@sectionpatch
155   \g@addto@macro\IndexParms{%
156     \ifHD@numbered
157     \else
158       \let\Hy@writebookmark\HDorg@writebookmark
159     \fi
160     \let\bfseries\HD@bfseries
161   }%
162   \edef\HD@toclevel@index{\HD@guesstoclevel{\index@prologue}}%

```

```

163 \begingroup
164   \count@=\HD@toclevel@index\relax
165   \advance\count@ by 1 %
166   \xdef\HD@toclevel@subindex{\the\count@}%
167 \endgroup
168 \def\index@prologue{%
169   \ifHD@numbered
170   \else
171     \begingroup
172       \stepcounter{HD@unique}%
173       \let\Hy@writebookmark\HDorg@writebookmark
174       \pdfbookmark[\HD@toclevel@index]%
175         {\indexname}{index\theHD@unique}%
176     \endgroup
177   \fi
178   \HDorg@index@prologue
179 }%
180 \HDorg@theindex
181 }

```

\HDorg@bfseries

```
182 \let\HDorg@bfseries\bfseries
```

\HD@bfseries

```
183 \def\HD@bfseries{\futurelet\HD@hfil\HD@@bfseries}%

```

\HD@@bfseries

```

184 \def\HD@@bfseries{%
185   \HDorg@bfseries
186   \ifx\HD@hfil\hfil
187     \expandafter\HD@@@bfseries
188   \fi
189 }

```

\HD@@@bfseries

```

190 \def\HD@@@bfseries\hfil#1\hfil{%
191   \ifx\#1\%
192   \else
193     \raisebox{\baselineskip}[Opt]{%
194       \kern-\HD@margin\relax
195       \pdfbookmark[\HD@toclevel@subindex]{#1}{HD.#1}%
196       \kern\HD@margin\relax
197     }%
198   \fi
199   \hfil#1\hfil
200 }%

```

\HD@margin

```
201 \def\HD@margin{1mm}
```

### 3.9 \theglossary

\HDorg@theglossary

```
202 \let\HDorg@theglossary\theglossary
```

\theglossary

```

203 \def\theglossary{%
204   \let\HDorg@glossary@prologue\glossary@prologue
205   \let\HDorg@writebookmark\Hy@writebookmark
206   \HD@sectionpatch

```



```

207 \def\glossary@prologue{%
208   \ifHD@numbered
209   \else
210     \begingroup
211       \let\Hy@writebookmark\HDorg@writebookmark
212       \stepcounter{HD@unique}%
213       \pdfbookmark[\HD@guesstoclevel{\HDorg@glossary@prologue}]{%
214         {\glossaryname}{glossary\theHD@unique}}%
215       \endgroup
216     \fi
217   \HDorg@glossary@prologue
218 }%
219 \HDorg@theglossary
220 }

```

\glossaryname

```

221 \providecommand*{\glossaryname}{Change History}

```

### 3.10 Index

```

222 \newcounter{HD@hypercount}

```

\HD@helplength

```

223 \newlength{\HD@helplength}

```

\ifHD@savedest

```

224 \newif\ifHD@savedest
225 \HD@savedesttrue

226 \AtBeginDocument{%
227   \HD@savedest@init
228 }

229 \RequirePackage{rerunfilecheck}[2009/12/10]

```

\HD@savedest@init

```

230 \begingroup
231   \catcode'\^^M=\active
232   \@firstofone{\endgroup
233     \def\HD@savedest@init{%
234       \ifHD@savedest
235         \let\HDorg@tilde~%
236         \let~\HD@savedest@entry
237         \edef\HDorg@catcodeM{\the\catcode'\^^M}%
238         \catcode'\^^M=\active
239         \def^^M{}%
240         \InputIfFileExists{\jobname.hd}{-}{-}%
241         \let~\HDorg@tilde
242         \catcode'\^^M=\HDorg@catcodeM\relax
243         \newwrite\HD@savedest@out
244         \RerunFileCheck{\jobname.hd}{-}%
245         \immediate\closeout\HD@savedest@out
246       }{}%
247       \immediate\openout\HD@savedest@out=\jobname.hd\relax
248     \else
249       \let\HD@savedest@add\@gobble
250     \fi
251   }%

```

\HD@savedest@entry

```

252   \def\HD@savedest@entry#1^^M{%
253     \@namedef{HD.#1}{-}}%
254   }%
255 }

```

```

\HD@savedest@add
256 \def\HD@savedest@add#1{%
257   \immediate\write\HD@savedest@out{\string~#1}%
258 }

\ifHD@targetraise
259 \newif\ifHD@targetraise
260 \HD@targetraisetrue

\HD@target
261 \def\HD@target{%
262   \ifHD@targetraise
263     \ifhmode
264       \settoheight{\HD@helplength}{[H]}%
265       \addtolength{\HD@helplength}{0.4ex}%
266       \raisebox{\HD@helplength}{%
267         \HD@maketarget
268       }%
269     \else
270       \HD@maketarget
271     \fi
272   \else
273     \HD@maketarget
274   \fi
275 }

\HD@maketarget
276 \def\HD@maketarget{%
277   \stepcounter{HD@hypercount}%
278   \def\HD@next{%
279     \llap{\hypertarget{HD.\the\c@HD@hypercount}{\,\,}%
280   }%
281   \ifHD@savedest
282     \expandafter\ifx\csname HD.\the\c@HD@hypercount\endcsname\@empty
283     \else
284       \let\HD@next\relax
285     \fi
286   \fi
287   \HD@next
288 }

\CodelineIndex
289 \g@addto@macro\CodelineIndex{%
290   \let\special@index\HD@codeline@wrindex
291 }

\PageIndex
292 \g@addto@macro\PageIndex{%
293   \let\special@index\HD@page@wrindex
294 }

\HD@codeline@wrindex
295 \def\HD@codeline@wrindex#1{%
296   \begingroup
297   \let\HDorg@encapchar\encapchar
298   \def\encapchar##1\encapchar##2\@nil{%
299     \HDorg@encapchar
300     hdclindex{\the\c@HD@hypercount}{##1}%
301   }%
302   \codeline@wrindex{%
303     #1\encapchar\encapchar\@nil

```

```

304     }%
305 \endgroup
306 }

\HD@page@wrindex

307 \def\HD@page@wrindex#1{%
308 \begingroup
309 \let\HDorg@encapchar\encapchar
310 \def\encapchar##1\encapchar##2\@nil{%
311 \HDorg@encapchar
312 hdpindex{##1}%
313 }%
314 \HDorg@index{#1\encapchar\encapchar\@nil}%
315 \endgroup
316 }

\hdclindex

317 \def\hdclindex#1#2#3{%
318 \csname\ifx\\#2\\relax\else#2\fi\endcsname{%
319 \hyperlink{HD.#1}{#3}%
320 \HD@savedest@add{#1}%
321 }%
322 }

\hdpindex

323 \def\hdpindex#1#2{%
324 \csname\ifx\\#1\\relax\else#1\fi\endcsname{%
325 \hyperpage{#2}%
326 }%
327 }

```

### 3.11 \PrintDescribeMacro

```

\HDorg@PrintDescribeMacro

328 \let\HDorg@PrintDescribeMacro\PrintDescribeMacro

\PrintDescribeMacro

329 \renewcommand\PrintDescribeMacro[1]{%
330 \begingroup
331 \let\HDorg@MacroFont\MacroFont
332 \def\MacroFont{%
333 \HD@target
334 \HDorg@MacroFont
335 }%
336 \HDorg@PrintDescribeMacro{#1}%
337 \endgroup
338 }

```

### 3.12 \PrintMacroName

```

\HDorg@PrintMacroName

339 \let\HDorg@PrintMacroName\PrintMacroName

\PrintMacroName

340 \renewcommand\PrintMacroName[1]{%
341 \begingroup
342 \let\HDorg@MacroFont\MacroFont
343 \def\MacroFont{%
344 \HD@target
345 \HDorg@MacroFont

```

```

346     }%
347     \HDorg@PrintMacroName{#1}%
348 \endgroup
349 }

```

### 3.13 \theCodelineNo

\HDorg@theCodelineNo

```

350 \let\HDorg@theCodelineNo\theCodelineNo

\theCodelineNo

351 \renewcommand*\theCodelineNo{%
352   \settowidth{\HD@helplength}{\HDorg@theCodelineNo\ }%
353   \ifdim\HD@helplength<\MacroIndent
354     \addtolength{\HD@helplength}{-\MacroIndent}%
355     \llap{%
356       \begingroup\HD@target\endgroup
357       \hspace*{-\HD@helplength}%
358     }%
359   \else
360     \HD@target
361   \fi
362   \HDorg@theCodelineNo
363 }

```

\HDorg@index

```

364 \AtBeginDocument{%
365   \let\HDorg@index\index
366 }

```

### 3.14 \SpecialUsageIndex

\HDorg@SpecialUsageIndex

```

367 \let\HDorg@SpecialUsageIndex\SpecialUsageIndex
368 \renewcommand*\SpecialUsageIndex[1]{%
369   \@bsphack
370   \begingroup
371     \HD@target
372     \let\index\HDorg@index
373     \let\HDorg@encapchar\encapchar
374     \edef\encapchar usage{%
375       \HDorg@encapchar hdclindex{\the\c@HD@hypercount}{usage}%
376     }%
377     \HDorg@SpecialUsageIndex{#1}%
378   \endgroup
379   \@esphack
380 }

```

### 3.15 \autoindex

```

381 \begingroup\expandafter\expandafter\expandafter\endgroup
382 \expandafter\ifx\csname autoindex\endcsname\relax
383 \else

```

\HDorg@autoindex

```

384   \let\HDorg@autoindex\autoindex

```

\autoindex

```

385   \renewcommand*\autoindex[1]{%
386     \@bsphack
387     \begingroup

```

```

388     \HD@target
389     \let\index\HDorg@index
390     \let\HDorg@encapchar\encapchar
391     \edef\encapchar usage{%
392         \HDorg@encapchar hdclindex{\the\c@HD@hypercount}{usage}%
393     }%
394     \HDorg@autoindex{#1}%
395 \endgroup
396 \esphack
397 }%
398 \fi

```

### 3.16 \SpecialEnvIndex

\HDorg@SpecialEnvIndex

```

399 \let\HDorg@SpecialEnvIndex\SpecialEnvIndex

```

\SpecialEnvIndex

```

400 \renewcommand*\SpecialEnvIndex[1]{%
401     \@bsphack
402     \begingroup
403         \HD@target
404         \let\HDorg@encapchar\encapchar
405         \edef\encapchar usage{%
406             \HDorg@encapchar hdclindex{\the\c@HD@hypercount}{usage}%
407         }%
408         \HDorg@SpecialEnvIndex{#1}%
409     \endgroup
410     \@esphack
411 }

```

### 3.17 \SortIndex

\HDorg@SortIndex

```

412 \let\HDorg@SortIndex\SortIndex

```

\SortIndex

```

413 \renewcommand*\SortIndex[2]{%
414     \@bsphack
415     \begingroup
416         \let\index\HD@page@wrindex
417         \HDorg@SortIndex{#1}{#2}%
418     \endgroup
419     \@esphack
420 }

```

### 3.18 \@wrglossary

\HDorg@wrglossary

```

421 \let\HDorg@wrglossary\@wrglossary

```

\@wrglossary

```

422 \def\@wrglossary#1{%
423     \let\HDorg@encapchar\encapchar
424     \def\encapchar##1\encapchar##2\@nil{%
425         \HDorg@encapchar
426         hdpindex{##1}%
427     }%
428     \HDorg@wrglossary{#1\encapchar\encapchar\@nil}%
429 }

```

### 3.19 \MacroIndent

\MacroIndent automatically calculated.

```
430 \AfterLastShipout{%
431   \if@files
432     \immediate\write\@auxout{%
433       \string\providecommand\string\HD@SetMacroIndent[1]{}%
434     }%
435     \immediate\write\@auxout{%
436       \string\HD@SetMacroIndent{\number\value{CodelineNo}}}%
437     }%
438   \fi
439 }
```

\HD@SetMacroIndent

```
440 \def\HD@SetMacroIndent#1{%
441   \begingroup
442     \value{CodelineNo}=#1\relax
443     \settowidth{\MacroIndent}{\HD@org@theCodelineNo\ }%
444     \global\MacroIndent\MacroIndent
445   \endgroup
446 }

447 \end{package}
```

## 4 Installation

### 4.1 Download

**Package.** This package is available on CTAN<sup>1</sup>:

[CTAN:macros/latex/contrib/oberdiek/hypdoc.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/hypdoc.pdf](#) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T<sub>E</sub>X Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

### 4.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

---

<sup>1</sup><http://ftp.ctan.org/tex-archive/>

### 4.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain- $\TeX$ :

```
tex hypdoc.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
hypdoc.sty → tex/latex/oberdiek/hypdoc.sty
hypdoc.pdf → doc/latex/oberdiek/hypdoc.pdf
hypdoc.dtx → source/latex/oberdiek/hypdoc.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

### 4.4 Refresh file name databases

If your  $\TeX$  distribution (`te $\TeX$` , `mik $\TeX$` , ...) relies on file name databases, you must refresh these. For example, `te $\TeX$`  users run `texhash` or `mktextlsr`.

### 4.5 Some details for the interested

**Attached source.** The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk hypdoc.pdf unpack_files output .
```

**Unpacking with  $\LaTeX$ .** The `.dtx` chooses its action depending on the format:

**plain- $\TeX$ :** Run `docstrip` and extract the files.

**$\LaTeX$ :** Generate the documentation.

If you insist on using  $\LaTeX$  for `docstrip` (really, `docstrip` does not need  $\LaTeX$ ), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{hypdoc.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdf $\LaTeX$` :

```
pdflatex hypdoc.dtx
makeindex -s gind.ist hypdoc.idx
pdflatex hypdoc.dtx
makeindex -s gind.ist hypdoc.idx
pdflatex hypdoc.dtx
```

## 5 History

[2002/05/10 v1.0]

- First standalone version.

## [2006/02/20 v1.1]

- Option `numbered` added.
- `\HD@savedest@init` fixed (empty `.hd` file triggered first page with fl ligature).
- Bookmarks for `\listoffigures` and `\listoftables`.
- Documentation: features and usage added.
- LPPL 1.3.

## [2006/04/27 v1.2]

- `\HD@target` fixed (`multicol.dtx`).

## [2006/06/01 v1.3]

- Support for package `amsdtx`'s `\autoindex` added.

## [2006/06/02 v1.4]

- Bookmark fixed if there are several table of contents, bibliographies, glossaries, ...

## [2007/04/11 v1.5]

- Line ends sanitized.

## [2007/11/12 v1.6]

- Bug fix in `\listoffigures` (Axel Sommerfeldt).
- Markup added in implementation section.

## [2009/12/10 v1.7]

- Use of package `rerunfilecheck`.

## [2010/02/03 v1.8]

- Fix for bug `latex/4096` added.

## [2010/03/26 v1.9]

- Definition of `\HD@SetMacroIndex` is provided in the `.aux` file.

## 6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
<code>\*</code>	59	<code>\@auxout</code> 432, 435
<code>\+</code>	56	<code>\@bsphack</code> 369, 386, 401, 414
<code>\,</code>	279	<code>\@empty</code> 35, 44, 45, 82, 85, 282
<code>\-</code>	55	<code>\@esphack</code> 379, 396, 410, 419
<code>\:</code>	57	<code>\@firstofone</code> 232



\@gobble	41, 42, 82, 85, 249	\HD@guesstoclevel	79, 81
\@ifstar	74	\HD@@sectionpatch	64, 65, 70
\@ifundefined	34, 82, 91, 145	\HD@bfseries	160, 183
\@namedef	73, 253	\HD@codeline@wrindex	290, 295
\@nameuse	74, 85	\HD@disable@writebookmark	67, 77
\@nil	298, 303, 310, 314, 424, 428	\HD@end	79, 81
\@pdfsubject	35	\HD@guesstoclevel	78,
\@undefined	10	97, 104, 118, 131, 144, 162, 213	
\@wrglossary	421, 422	\HD@helplength	223,
\\	191, 318, 324	264, 265, 266, 352, 353, 354, 357	
\^	231, 237, 238, 242	\HD@hfil	183, 186
\_	352, 443	\HD@maketarget	267, 270, 273, 276
<b>A</b>			
\active	231, 238	\HD@margin	194, 196, 201
\addtolength	265, 354	\HD@ModFix	51, 55, 56, 57, 58, 59
\advance	165	\HD@next	278, 284, 287
\AfterLastShipout	430	\HD@numberedtrue	6
\and	46	\HD@page@wrindex	293, 307, 416
\AtBeginDocument	226, 364	\HD@savedest@add	249, 256, 320
\autoindex	384, 385	\HD@savedest@entry	236, 252
<b>B</b>			
\baselineskip	193	\HD@savedest@init	227, 230
\bfseries	160, 182	\HD@savedest@out	243, 245, 247, 257
\bibname	145	\HD@savedesttrue	225
<b>C</b>			
\c@HD@hypercount	279, 282, 300, 375, 392, 406	\HD@sectionpatch	62, 108, 122, 135, 147, 154, 206
\c@section	92, 95	\HD@SetMacroIndent	433, 436, 440
\catcode	231, 237, 238, 242	\HD@target	261,
\closeout	245	333, 344, 356, 360, 371, 388, 403	
\codeline@wrindex	302	\HD@targetraisetrue	260
\CodelineIndex	289	\HD@toclevel@index	162, 164, 174
\contentsname	98, 105, 119, 132	\HD@toclevel@subindex	166, 195
\count@	164, 165, 166	\hdclindex	317
\cs	43	\HDorg@autoindex	384, 394
\csname	49, 71, 72, 282, 318, 324, 382	\HDorg@bfseries	182, 185
<b>D</b>			
\DeclareOption	6	\HDorg@catcodeM	237, 242
<b>E</b>			
\encapchar	297, 298,	\HDorg@encapchar	297, 299, 309, 311, 373,
303, 309, 310, 314, 373, 374,		375, 390, 392, 404, 406, 423, 425	
390, 391, 404, 405, 423, 424, 428		\HDorg@glossary@prologue	204, 213, 217
\endcsname	49, 71, 72, 282, 318, 324, 382	\HDorg@index	314, 364, 372, 389
<b>F</b>			
\fileinfo	36	\HDorg@index@prologue	152, 178
\footnote	42	\HDorg@listoffigures	113, 118, 123
\futurelet	183	\HDorg@listoftables	126, 131, 136
<b>G</b>			
\g@addto@macro	33, 54, 155, 289, 292	\HDorg@MacroFont	331, 334, 342, 345
\glossary@prologue	204, 207	\HDorg@PrintDescribeMacro	328, 336
\glossaryname	214, 221	\HDorg@PrintMacroName	339, 347
<b>H</b>			
\HD@@@bfseries	187, 190	\HDorg@SortIndex	412, 417
\HD@bfseries	183, 184	\HDorg@SpecialEnvIndex	399, 408
		\HDorg@SpecialUsageIndex	367
		\HDorg@tableofcontents	88, 97, 99, 104, 109
		\HDorg@thebibliography	139, 144, 148
		\HDorg@theCodelineNo	350, 352, 362, 443
		\HDorg@theglossary	202, 219
		\HDorg@theindex	150, 180
		\HDorg@tilde	235, 241
		\HDorg@wrglossary	421, 428
		\HDorg@writebookmark	153, 158, 173, 205, 211
		\hdpindex	323
		\headheight	25
		\headsep	25
		\hfil	186, 190, 199

\hspace	357	<b>O</b>	
\Hy@UseMaketitleInfos	33	\openout	247
\Hy@writebookmark		<b>P</b>	
.....	67, 153, 158, 173, 205, 211	\PageIndex	292
\hypercalcbp	24	\paperheight	25
\hyperlink	319	\pdfbookmark	97,
\hyperpage	325	104, 118, 131, 144, 174, 195, 213	
\hypersetup	19, 36	\pdfstringdefDisableCommands	40
\hypertarget	279	\PrintDescribeMacro	328, 329
<b>I</b>		\PrintMacroName	339, 340
\if@filesw	431	\ProcessOptions	7
\ifcase	95	\providecommand	221, 433
\ifdim	353	\ProvidesPackage	3
\ifHD@numbered	5,	<b>R</b>	
63, 101, 115, 128, 141, 156, 169, 208		\raisebox	193, 266
\ifHD@savedest	224, 234, 281	\refname	145
\ifHD@targetraise	259, 262	\renewcommand	30,
\ifhmode	263	329, 340, 351, 368, 385, 400, 413	
\ifx	10,	\RequirePackage	8, 9, 11, 13, 28, 229
35, 49, 186, 191, 282, 318, 324, 382		\RerunFileCheck	244
\immediate	245, 247, 257, 432, 435	<b>S</b>	
\index	365, 372, 389, 416	\scshape	45
\index@prologue	152, 162, 168	\section	79
\indexname	175	\settoheight	264
\IndexParms	155	\settowidth	352, 443
\InputIfFileExists	240	\SortIndex	412, 413
<b>J</b>		\special@index	290, 293
\jobname	240, 244, 247	\SpecialEnvIndex	399, 400
<b>K</b>		\SpecialUsageIndex	367, 368
\kern	194, 196	\stepcounter	96,
<b>L</b>		103, 117, 130, 143, 172, 212, 277	
\listoffigures	113, 114	<b>T</b>	
\listoftables	126, 127	\tableofcontents	88, 89
\llap	279, 355	\textbackslash	43
<b>M</b>		\thanks	41
\MacroFont	331, 332, 342, 343	\the	166, 237, 279, 282, 300, 375, 392, 406
\MacroIndent	353, 354, 443, 444	\thebibliography	139, 140
\mathcode	52	\theCodelineNo	350, 351
\mod@math@codes	54	\theglossary	202, 203
<b>N</b>		\theHD@unique	30,
\NeedsTeXFormat	2	98, 105, 119, 132, 145, 175, 214	
\newcounter	29, 222	\theindex	150, 151
\newif	5, 224, 259	\topmargin	25
\newlength	223	<b>V</b>	
\newwrite	243	\value	31, 436, 442
\normalfont	44	<b>W</b>	
\number	31, 436	\write	257, 432, 435
\numexpr	10		