

The `hypdoc` package

Heiko Oberdiek*

2018/09/07 v1.14

Abstract

This package adds hyper features to the package `doc` that is used in the documentation system of L^AT_EX 2_&. Bookmarks are added and references are linked as far as possible.

Contents

| | | |
|----------|---|----------|
| 1 | Features | 2 |
| 2 | Usage | 3 |
| 2.1 | Options | 3 |
| 2.2 | Simple example | 3 |
| 2.3 | Example <code>source2e.tex</code> | 4 |
| 3 | Implementation | 4 |
| 3.1 | Options | 4 |
| 3.2 | Package loading | 4 |
| 3.2.1 | Patch for bug <code>latex/4096</code> | 5 |
| 3.3 | Bookmarks | 5 |
| 3.4 | <code>\tableofcontents</code> | 6 |
| 3.5 | <code>\listoffigures</code> | 7 |
| 3.6 | <code>\listoftables</code> | 7 |
| 3.7 | <code>\thebibliography</code> | 7 |
| 3.8 | <code>\theindex</code> | 8 |
| 3.9 | <code>\theglossary</code> | 9 |
| 3.10 | Index | 9 |
| 3.11 | <code>\PrintDescribeMacro</code> | 12 |
| 3.12 | <code>\PrintMacroName</code> | 12 |
| 3.13 | <code>\theCodelineNo</code> | 12 |
| 3.14 | <code>\SpecialUsageIndex</code> | 13 |
| 3.15 | <code>\autoindex</code> | 13 |
| 3.16 | <code>\SpecialEnvIndex</code> | 14 |
| 3.17 | <code>\SortIndex</code> | 14 |
| 3.18 | <code>\@wrglossary</code> | 14 |
| 3.19 | <code>\MacroIndent</code> | 14 |

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

| | |
|---|-----------|
| 4 Installation | 15 |
| 4.1 Download | 15 |
| 4.2 Bundle installation | 15 |
| 4.3 Package installation | 15 |
| 4.4 Refresh file name databases | 16 |
| 4.5 Some details for the interested | 16 |
| 5 History | 16 |
| [2002/05/10 v1.0] | 16 |
| [2006/02/20 v1.1] | 17 |
| [2006/04/27 v1.2] | 17 |
| [2006/06/01 v1.3] | 17 |
| [2006/06/02 v1.4] | 17 |
| [2007/04/11 v1.5] | 17 |
| [2007/11/12 v1.6] | 17 |
| [2009/12/10 v1.7] | 17 |
| [2010/02/03 v1.8] | 17 |
| [2010/03/26 v1.9] | 17 |
| [2011/05/05 v1.10] | 17 |
| [2011/08/19 v1.11] | 17 |
| [2016/05/16 v1.12] | 18 |
| [2016/10/02 v1.13] | 18 |
| [2018/09/07 v1.14] | 18 |

1 Features

The package adds the following features:

Bookmarks: For supporting bookmarks package `hyperref` is loaded. Some `TEX` code inside section titles can cause problems during bookmark processing; these can be warnings, ugly bookmark titles or even errors. With the help of `\pdfstringdefDisableCommands` or `\texorpdfstring` you can manage these things, see `hyperref`'s package documentation.

Additional bookmarks: Unnumbered bookmark entries are generated for:

- Table of contents
- List of figures
- List of tables
- Index
- Glossary

Option `numbered` controls, whether these section or chapters should be numbered. The exception is the table of contents if this it would be the first numbered section. Then just a bookmark is added.

Metadata: The loaded package `hyperref`, enforced by option `pdfusetitle`, tries to detect `\title` and `\author` and sets the corresponding PDF information fields. In case of problems see the previous item about bookmarks. These entries can be overwritten or new ones added by `\hypersetup` after the packages is loaded, see documentation of package `hyperref`.

References, links: Because of package `\hyperref` `\ref` become links, also `\url`, footnote referencing are supported.

Index: The main part of this package deals with index links in order to support the kind of index that package `doc` provides.

Thumbnails: Package `thumbpdf` may additionally be loaded for the case that the PDF file also should contain thumbnails, see the documentation of this package. But thumbnail embedding is not really necessary, because nowadays AcrobatReader is able to generate and view thumbnails on the fly.

2 Usage

The purpose of this packages is to add PDF features to the documentation of LaTeX packages. Thus just load the package in the driver file that generates the documentation:

```
\usepackage{hypdoc}
```

Package `doc` is loaded by `hypdoc`, thus you also can replace a `\usepackage{doc}` with this line. At any case, the package must be loaded before macros of package `doc` such as `\CodelineIndex` or `\PageIndex` are used.

If the class `ltxdoc` is used, you can also use the configuration file for this class to add package `hypdoc`. Add the following line to the file `ltxdoc.cfg` (or create a new one):

```
\AtEndOfClass{\RequirePackage{hypdoc}}
```

2.1 Options

There is one option `numbered`. It controls, whether the starred versions of section or chapter inside `\tableofcontents`, `\listoffigures`, ...should be replaced by the non-star versions.

2.2 Simple example

Example of a simple driver file `foobar.drv` of a package `foobar`. Often the driver file is packed in the file `foobar.dtx` and can be extracted by `docstrip` or if an instruction file for `docstrip` is provided by:

```
tex foobar.ins
```

Note that although `docstrip` doesn't rely on L^AT_EX, sometimes you need to run the `.ins` file through L^AT_EX. Oddly enough, often the only L^AT_EX feature in use is `\NeedsTeXFormat{LaTeX2e}` in the first line.

```
\documentclass{ltxdoc}
\usepackage{hypdoc}
\RecordChanges
\EnableCrossrefs
\CodelineIndex
\begin{document}
\title{Title\_for\_package\_\\texttt{foobar}}
\author{Author\_of\_package\_\\texttt{foobar}}
\date{...}
\maketitle
\tableofcontents
\DocInput{foobar.dtx}
\PrintChanges
\PrintIndex
\end{document}
```

Then compile it, for example with pdflatEX.

```
pdflatex_foobar.drv
makeindex_-s_gind.ist_foobar.idx
makeindex_-s_gglo.ist_-o_foobar.gls_foobar.glo
pdflatex_foobar.drv
```

You will need several cycles until the cross references and similar things are correct.

2.3 Example source2e.tex

The source code of the base of LATEX is available as a bunch of .dtx files. LATEX provides the file `source2e.tex` to merge them all together.

Now you can either load package `hypdoc` in a private copy of this file (please, respect the LPPL) or use the configuration file `ltxdoc.cfg`. Example that also sets A4 paper size:

```
\PassOptionsToClass{a4paper}{article}
\AtEndOfClass{\RequirePackage{hypdoc}}
```

Then `source2e.tex` can be compiled by pdfTEx, for example:

```
pdflatex_source2e
makeindex_-s_gind.ist_source2e.idx
makeindex_-s_gglo.ist_-o_source2e.glo_source2e.gls
pdflatex_source2e
makeindex_-s_gind.ist_source2e.idx
makeindex_-s_gglo.ist_-o_source2e.glo_source2e.gls
pdflatex_source2e
```

3 Implementation

```
1 (*package)
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{hypdoc}%
4 [2018/09/07 v1.14 Hyper extensions for doc.sty (HO)]%
```

The package identification is done at the top of the .dtx file in order to use only one identification string.

For unique command names this package uses HD@ as prefix

3.1 Options

```
\ifHD@numbered
5 \newif\ifHD@numbered
6 \DeclareOption{numbered}{\HD@numberedtrue}
7 \ProcessOptions*\relax
```

3.2 Package loading

```
8 \RequirePackage{atveryend}[2010/03/24]
9 \RequirePackage{doc}
10 \ifx\numexpr\undefined
11   \RequirePackage{calc}%
12 \fi
13 \RequirePackage[%]
14   hyperindex=false,%
15   pdfusetitle,%
```

```

16   colorlinks,%  

17   pdfpagelabels%  

18 ]{hyperref}[2002/05/09]  

19 \hypersetup{  

20   plainpages=false,%  

21   bookmarksopen,%  

22   bookmarksnumbered,%  

23   bookmarksopenlevel=0,%  

24   pdfstartview={FitBH \hypercalcbp{  

25     \paperheight-\topmargin-1in-\headheight-\headsep  

26   }},%  

27 }  

28 \newcounter{HD@unique}  

  
\theHD@unique  

29 \renewcommand{\theHD@unique}{%  

30   \number\value{HD@unique}%  

31 }  

  
32 \g@addto@macro\Hy@UseMaketitleInfos{  

33   \Qifundefined{fileinfo}{}{  

34     \ifx\Qpdfsubject\empty  

35       \hypersetup{pdfsubject={\fileinfo}}%  

36     \fi  

37   }%  

38 }  

  
39 \pdfstringdefDisableCommands{  

40   \let\thanks\gobble  

41   \let\footnote\gobble  

42   \def\cs#1{\textbackslash #1}%  

43   \let\normalfont\empty  

44   \let\scshape\empty  

45   \def\and{and }%  

46 }

```

3.2.1 Patch for bug latex/4096

```

47 \begingroup\expandafter\expandafter\expandafter\endgroup  

48 \expandafter\ifx\csname mod@math@codes\endcsname\relax  

49 \else  

50   \def\HD@ModFix#1{  

51     \mathcode`#1=\#1\relax  

52   }%  

53 \g@addto@macro\mod@math@codes{  

54   \HD@ModFix\-%  

55   \HD@ModFix\+  

56   \HD@ModFix\:  

57   \HD@ModFix\=  

58   \HD@ModFix\*  

59 }%  

60 \fi

```

3.3 Bookmarks

```
\HD@sectionpatch  

61 \def\HD@sectionpatch{  

62   \ifHD@numbered  

63     \HD@@sectionpatch{section}%
```

```

64      \HD@@sectionpatch{chapter}%
65  \else
66    \let\Hy@writebookmark\HD@disable@writebookmark
67  \fi
68 }

\HD@@sectionpatch
69 \def\HD@@sectionpatch#1{%
70   \expandafter\let\csname HDorg@@#1\expandafter\endcsname
71   \csname #1\endcsname
72   \namedef{#1}{%
73     \@ifstar{\nameuse{HDorg@@#1}}{\nameuse{HDorg@@#1}}%
74   }%
75 }

\HD@disable@writebookmark
76 \def\HD@disable@writebookmark#1#2#3#4#5{}

\HD@guesstoclevel A wild guessing of the toplevel. There is the hope, that the macro #1 starts with a sectioning command.
77 \def\HD@guesstoclevel#1{%
78   \expandafter\HD@guesstoclevel#1\section\HD@end
79 }

\HD@@guesstoclevel
80 \def\HD@@guesstoclevel#1#2\HD@end{%
81   \@ifundefined{toclevel}\expandafter\gobble\string#1\empty}%
82   1%
83 }%
84   \@nameuse{toclevel}\expandafter\gobble\string#1\empty}%
85 }%
86 }

```

3.4 \tableofcontents

```

\HDorg@tableofcontents
87 \let\HDorg@tableofcontents\tableofcontents

 As first section the table of contents shouldn't go into the toc itself. Also a number looks too funny then. Just a bookmark is enough in this case.
88 \def\tableofcontents{%
89   \begingroup
90   \@ifundefined{c@section}{%
91     \def\c@section{0}%
92   }{%
93   \expandafter\endgroup
94   \ifcase\c@section
95     \stepcounter{HD@unique}%
96     \pdfbookmark[\HD@guesstoclevel{\HDorg@tableofcontents}]{\contentsname}{toc\theHD@unique}%
97   \else
98     \HDorg@tableofcontents
99   \else
100     \ifHD@numbered
101   \else
102     \stepcounter{HD@unique}%
103     \pdfbookmark[\HD@guesstoclevel{\HDorg@tableofcontents}]{\contentsname}{toc\theHD@unique}%
104   
```

```

105     \fi
106     \begingroup
107         \HD@sectionpatch
108         \HDorg@tableofcontents
109     \endgroup
110     \fi
111 }

```

3.5 \listoffigures

```

\HDorg@listoffigures
112 \let\HDorg@listoffigures\listoffigures

\listoffigures
113 \def\listoffigures{%
114     \ifHD@numbered
115     \else
116         \stepcounter{HD@unique}%
117         \pdfbookmark[\HD@guesstoclevel{\HDorg@listoffigures}]{%
118             \listfigurename}{toc\theHD@unique}%
119     \fi
120     \begingroup
121         \HD@sectionpatch
122         \HDorg@listoffigures
123     \endgroup
124 }

```

3.6 \listoftables

```

\HDorg@listoftables
125 \let\HDorg@listoftables\listoftables

\listoftables
126 \def\listoftables{%
127     \ifHD@numbered
128     \else
129         \stepcounter{HD@unique}%
130         \pdfbookmark[\HD@guesstoclevel{\HDorg@listoftables}]{%
131             \listtablename}{toc\theHD@unique}%
132     \fi
133     \begingroup
134         \HD@sectionpatch
135         \HDorg@listoftables
136     \endgroup
137 }

```

3.7 \thebibliography

```

\HDorg@thebibliography
138 \let\HDorg@thebibliography\thebibliography

\thebibliography
139 \def\thebibliography{%
140     \ifHD@numbered
141     \else
142         \stepcounter{HD@unique}%

```

```

143      \pdfbookmark[\HD@guesstoclevel{\HDorg@thebibliography}]{%
144          {\@ifundefined{chapter}{\refname}{\bibname}}{\bib\theHD@unique}}%
145      \fi
146      \HD@sectionpatch
147      \HDorg@thebibliography
148 }



### 3.8 \theindex



\HDorg@theindex



```

149 \let\HDorg@theindex\theindex

\theindex
150 \def\theindex{%
151 \let\HDorg@index@prologue\index@prologue
152 \let\HDorg@writebookmark\Hy@writebookmark
153 \HD@sectionpatch
154 \g@addto@macro\IndexParms{%
155 \ifHD@numbered
156 \else
157 \let\Hy@writebookmark\HDorg@writebookmark
158 \fi
159 \let\bfseries\HD@bfseries
160 }%
161 \edef\HD@toclevel@index{\HD@guesstoclevel{\index@prologue}}%
162 \begingroup
163 \count@=\HD@toclevel@index\relax
164 \advance\count@ by 1 %
165 \xdef\HD@toclevel@subindex{\the\count@}%
166 \endgroup
167 \def\index@prologue{%
168 \ifHD@numbered
169 \else
170 \begingroup
171 \stepcounter{HD@unique}%
172 \let\Hy@writebookmark\HDorg@writebookmark
173 \pdfbookmark[\HD@toclevel@index]{%
174 {\indexname}\index@theHD@unique}%
175 \endgroup
176 \fi
177 \HDorg@index@prologue
178 }%
179 \HDorg@theindex
180 }

\HDorg@bfseries
181 \let\HDorg@bfseries\bfseries

\HD@bfseries
182 \def\HD@bfseries{\futurelet\HD@hfil\HD@@bfseries}%

\HD@@bfseries
183 \def\HD@@bfseries{%
184 \HDorg@bfseries
185 \ifx\HD@hfil\hfil
186 \expandafter\HD@@@bfseries
187 \fi
188 }

```


```

```

\HD@@@bfseries
189 \def\HD@@@bfseries\hfil#1\hfil{%
190   \ifx\\#1\\%
191   \else
192     \raisebox{\baselineskip}[0pt]{%
193       \kern-\HD@margin\relax
194       \pdfbookmark[\HD@toclevel@subindex]{#1}{\HD.#1}%
195       \kern\HD@margin\relax
196     }%
197   \fi
198   \hfil#1\hfil
199 }%

```

```

\HD@margin
200 \def\HD@margin{1mm}

```

3.9 \theglossary

```

\HDorg@theglossary
201 \let\HDorg@theglossary\theglossary

\theglossary
202 \def\theglossary{%
203   \let\HDorg@glossary@prologue\glossary@prologue
204   \let\HDorg@writebookmark\Hy@writebookmark
205   \HD@sectionpatch
206   \def\glossary@prologue{%
207     \ifHD@numbered
208     \else
209       \begingroup
210         \let\Hy@writebookmark\HDorg@writebookmark
211         \stepcounter{HD@unique}%
212         \pdfbookmark[\HD@guesstoclevel{\HDorg@glossary@prologue}]{%
213           \changehistoryname{\glossary\theHD@unique}}%
214       \endgroup
215     \fi
216   \HDorg@glossary@prologue
217 }%
218 \HDorg@theglossary
219 }

\glossaryname
220 \providecommand*\glossaryname{Change History}

\glossaryname
221 \providecommand*\changehistoryname{\glossaryname}

```

3.10 Index

```

222 \newcounter{HD@hypercount}

\HD@helplength
223 \newlength{\HD@helplength}

\ifHD@savestore
224 \newif\ifHD@savestore
225 \HD@savestoretrue

```

```

226 \AtBeginDocument{%
227   \HD@savedest@init
228 }
229 \RequirePackage{rerunfilecheck}[2009/12/10]

\HD@savedest@init
230 \begingroup
231   \catcode`^\^M=\active
232 @firstofone{\endgroup
233   \def\HD@savedest@init{%
234     \ifHD@savedest
235       \let\HDorg@tilde-
236       \let~\HD@savedest@entry
237       \edef\HDorg@catcodeM{\the\catcode`^\^M}%
238       \catcode`^\^M=\active
239       \def^\^M{%
240         \InputIfFileExists{\jobname.hd}{}{}%
241         \let~\HDorg@tilde
242         \catcode`^\^M=\HDorg@catcodeM\relax
243         \newwrite\HD@savedest@out
244         \RerunFileCheck{\jobname.hd}{%
245           \immediate\closeout\HD@savedest@out
246         }{}%
247         \immediate\openout\HD@savedest@out=\jobname.hd\relax
248       \else
249         \let\HD@savedest@add@gobble
250       \fi
251     }%
252   \def\HD@savedest@entry#1^\^M{%
253     \namedef{HD.#1}{}%
254   }%
255 }

\HD@savedest@entry
256 \def\HD@savedest@add#1{%
257   \immediate\write\HD@savedest@out{\string~#1}%
258 }

\HD@savedest@add
259 \newif\ifHD@targetraise
260 \HD@targetraisetrue

\HD@target
261 \def\HD@target{%
262   \ifHD@targetraise
263     \ifhmode
264       \settoheight{\HD@helplength}{[H]}%
265       \addtolength{\HD@helplength}{0.4ex}%
266       \raisebox{\HD@helplength}[Opt][Opt]{%
267         \HD@maketarget
268       }%
269     \else
270       \HD@maketarget
271     \fi
272   \else

```

```

273      \HD@maketarget
274    \fi
275 }

\HD@maketarget
276 \def\HD@maketarget{%
277   \stepcounter{HD@hypercount}%
278   \def\HD@next{%
279     \llap{\hypertarget{HD.\the\c@HD@hypercount}{}},}%
280   }%
281   \ifHD@savedest
282     \expandafter\ifx\csname HD.\the\c@HD@hypercount\endcsname\empty
283     \else
284       \let\HD@next\relax
285     \fi
286   \fi
287   \HD@next
288 }

\CodelineIndex
289 \g@addto@macro\CodelineIndex{%
290   \let\special@index\HD@codeline@wrindex
291 }

\PageIndex
292 \g@addto@macro\PageIndex{%
293   \let\special@index\HD@page@wrindex
294 }

\HD@codeline@wrindex
295 \def\HD@codeline@wrindex#1{%
296   \begingroup
297     \let\HDorg@encapchar\encapchar
298     \def\encapchar##1\encapchar##2\@nil{%
299       \HDorg@encapchar
300       hdclindex{\the\c@HD@hypercount}{##1}%
301     }%
302     \codeline@wrindex{%
303       #1\encapchar\encapchar\@nil
304     }%
305   \endgroup
306 }

\HD@page@wrindex
307 \def\HD@page@wrindex#1{%
308   \begingroup
309     \let\HDorg@encapchar\encapchar
310     \def\encapchar##1\encapchar##2\@nil{%
311       \HDorg@encapchar
312       hdpindex{##1}%
313     }%
314     \HDorg@index{#1\encapchar\encapchar\@nil}%
315   \endgroup
316 }

\hdclindex
317 \def\hdclindex#1#2#3{%

```

```

318   \csname\ifx\\#2\relax\else#2\fi\endcsname{%
319     \hyperlink{HD.#1}{#3}%
320     \HD@savedest@add{#1}%
321   }%
322 }

\hdpindex
323 \def\hdpindex#1#2{%
324   \csname\ifx\\#1\relax\else#1\fi\endcsname{%
325     \hyperpage{#2}%
326   }%
327 }

```

3.11 \PrintDescribeMacro

```

\HDorg@PrintDescribeMacro
328 \let\HDorg@PrintDescribeMacro\PrintDescribeMacro

\PrintDescribeMacro
329 \renewcommand\PrintDescribeMacro[1]{%
330   \begingroup
331     \let\HDorg@MacroFont\MacroFont
332     \def\MacroFont{%
333       \HD@target
334       \HDorg@MacroFont
335     }%
336     \HDorg@PrintDescribeMacro{#1}%
337   \endgroup
338 }

```

3.12 \PrintMacroName

```

\HDorg@PrintMacroName
339 \let\HDorg@PrintMacroName\PrintMacroName

\PrintMacroName
340 \renewcommand\PrintMacroName[1]{%
341   \begingroup
342     \let\HDorg@MacroFont\MacroFont
343     \def\MacroFont{%
344       \HD@target
345       \HDorg@MacroFont
346     }%
347     \HDorg@PrintMacroName{#1}%
348   \endgroup
349 }

```

3.13 \theCodelineNo

```

\HDorg@theCodelineNo
350 \let\HDorg@theCodelineNo\theCodelineNo

\theCodelineNo
351 \renewcommand*\theCodelineNo{%
352   \settowidth{\HD@helplength}{\HDorg@theCodelineNo\ }%
353   \ifdim\HD@helplength<\MacroIndent

```

```

354   \addtolength{\HD@helplength}{-\MacroIndent}%
355   \llap{%
356     \begingroup\HD@target\endgroup
357     \hspace*{-\HD@helplength}%
358   }%
359   \else
360     \HD@target
361   \fi
362 \HDorg@theCodelineNo
363 }

\HDorg@index
364 \AtBeginDocument{%
365   \let\HDorg@index\index
366 }

```

3.14 \SpecialUsageIndex

```

\HDorg@SpecialUsageIndex
367 \let\HDorg@SpecialUsageIndex\SpecialUsageIndex
368 \renewcommand*\SpecialUsageIndex[1]{%
369   \@bsphack
370   \begingroup
371     \HD@target
372     \let\index\HDorg@index
373     \let\HDorg@encapchar\encapchar
374     \edef\encapchar usage{%
375       \HDorg@encapchar hdclindex{\the\c@HD@hypercount}{usage}%
376     }%
377     \HDorg@SpecialUsageIndex{#1}%
378   \endgroup
379   \@esphack
380 }

```

3.15 \autoindex

```

381 \begingroup\expandafter\expandafter\expandafter\endgroup
382 \expandafter\ifx\csname autoindex\endcsname\relax
383 \else

```

```

\HDorg@autoindex
384   \let\HDorg@autoindex\autoindex

\autoindex
385   \renewcommand*\autoindex[1]{%
386     \@bsphack
387     \begingroup
388       \HD@target
389       \let\index\HDorg@index
390       \let\HDorg@encapchar\encapchar
391       \edef\encapchar usage{%
392         \HDorg@encapchar hdclindex{\the\c@HD@hypercount}{usage}%
393       }%
394       \HDorg@autoindex{#1}%
395     \endgroup
396     \@esphack
397   }%
398 \fi

```

3.16 \SpecialEnvIndex

```
\HDorg@SpecialEnvIndex
 399 \let\HDorg@SpecialEnvIndex\SpecialEnvIndex

\SpecialEnvIndex
 400 \renewcommand*\SpecialEnvIndex[1]{%
 401   \@bsphack
 402   \begingroup
 403   \HD@target
 404   \let\HDorg@encapchar\encapchar
 405   \edef\encapchar usage{%
 406     \HDorg@encapchar hdclindex{\the\c@HD@hypercount}{usage}%
 407   }%
 408   \HDorg@SpecialEnvIndex{#1}%
 409   \endgroup
 410   \@esphack
 411 }
```

3.17 \SortIndex

```
\HDorg@SortIndex
 412 \let\HDorg@SortIndex\SortIndex

\SortIndex
 413 \renewcommand*{\SortIndex}[2]{%
 414   \@bsphack
 415   \begingroup
 416   \let\index\HD@page@wrindex
 417   \HDorg@SortIndex{#1}{#2}%
 418   \endgroup
 419   \@esphack
 420 }
```

3.18 \@wrglossary

```
\HDorg@wrglossary
 421 \let\HDorg@wrglossary@\wrglossary

@\wrglossary
 422 \def@\wrglossary#1{%
 423   \let\HDorg@encapchar\encapchar
 424   \def\encapchar##1\encapchar##2@nil{%
 425     \HDorg@encapchar
 426     hdpindex{##1}%
 427   }%
 428   \HDorg@wrglossary{#1\encapchar\encapchar@nil}%
 429 }
```

3.19 \MacroIndent

```
\MacroIndent automatically calculated.
430 \AfterLastShipout{%
431   \if@filesw
432     \immediate\write\auxout{%
433       \string\providecommand\string\HD@SetMacroIndent[1]{}%
```

```

434      }%
435      \immediate\write\@auxout{%
436        \string\HD@SetMacroIndent{\number\value{CodelineNo}}%
437      }%
438    \fi
439  }

\HD@SetMacroIndent
440 \def\HD@SetMacroIndent#1{%
441   \begingroup
442     \value{CodelineNo}=#1\relax
443     \settowidth{\MacroIndent}{\HDorg@theCodelineNo\ }%
444     \global\MacroIndent\MacroIndent
445   \endgroup
446 }
447 </package>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/hypdoc.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/hypdoc.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for TeX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDSScripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain TeX:

```
tex hypdoc.dtx
```

¹[CTAN:pkg/hypdoc](#)

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
hypdoc.sty → tex/latex/oberdiek/hypdoc.sty  
hypdoc.pdf → doc/latex/oberdiek/hypdoc.pdf  
hypdoc.dtx → source/latex/oberdiek/hypdoc.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your `TeX` distribution (`teTeX`, `mikTeX`, ...) relies on file name databases, you must refresh these. For example, `teTeX` users run `texhash` or `mktextslr`.

4.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain TeX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{hypdoc.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex hypdoc.dtx  
makeindex -s gind.ist hypdoc.idx  
pdflatex hypdoc.dtx  
makeindex -s gind.ist hypdoc.idx  
pdflatex hypdoc.dtx
```

5 History

[2002/05/10 v1.0]

- First standalone version.

[2006/02/20 v1.1]

- Option numbered added.
- `\HD@savedest@init` fixed (empty .hd file triggered first page with fl ligature).
- Bookmarks for `\listoffigures` and `\listoftables`.
- Documentation: features and usage added.
- LPPL 1.3.

[2006/04/27 v1.2]

- `\HD@target` fixed (`multicol.dtx`).

[2006/06/01 v1.3]

- Support for package `amsdtx`'s `\autoindex` added.

[2006/06/02 v1.4]

- Bookmark fixed if there are several table of contents, bibliographies, glossaries, ...

[2007/04/11 v1.5]

- Line ends sanitized.

[2007/11/12 v1.6]

- Bug fix in `\listoffigures` (Axel Sommerfeldt).
- Markup added in implementation section.

[2009/12/10 v1.7]

- Use of package `rerunfilecheck`.

[2010/02/03 v1.8]

- Fix for bug latex/4096 added.

[2010/03/26 v1.9]

- Definition of `\HD@SetMacroIndex` is provided in the `.aux` file.

[2011/05/05 v1.10]

- `\raisebox` in `\HD@target` with height and depth of 0pt (request of GL).

[2011/08/19 v1.11]

- Latest comma in option list for hyperref removed to avoid option clash because of L^AT_EX 2011/06/27 with the new `\in@`.

[2016/05/16 v1.12]

- Documentation updates.

[2016/10/02 v1.13]

- Fixes to bookmarknames, also introduce \changehistoryname

[2018/09/07 v1.14]

- Do not load thumpdf.

6 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

| Symbols | |
|--------------------|---|
| * | 58 |
| \+ | 55 |
| \, | 279 |
| \- | 54 |
| \: | 56 |
| \= | 57 |
| \auxout | 432, 435 |
| \bsphack | 369, 386, 401, 414 |
| \empty | 34, 43, 44, 81, 84, 282 |
| \esphack | 379, 396, 410, 419 |
| \firstofone | 232 |
| \gobble | 40, 41, 81, 84, 249 |
| \ifstar | 73 |
| \ifundefined | 33, 81, 90, 144 |
| \namedef | 72, 253 |
| \nameuse | 73, 84 |
| \nil | 298, 303, 310, 314, 424, 428 |
| \pdfsubject | 34 |
| \undefined | 10 |
| \wrglossary | 421, 422 |
| \` | 190, 318, 324 |
| \^ | 231, 237, 238, 242 |
| \bibname | 144 |
| C | |
| \c@HD@hypercount | 279, 282, 300, 375, 392, 406 |
| \c@section | 91, 94 |
| \catcode | 231, 237, 238, 242 |
| \changehistoryname | 213, 221 |
| \closeout | 245 |
| \codeline@wrindex | 302 |
| \CodelineIndex | 289 |
| \contentsname | 97, 104 |
| \count@ | 163, 164, 165 |
| \cs | 42 |
| \csname | 48, 70, 71, 282, 318, 324, 382 |
| D | |
| \DeclareOption | 6 |
| E | |
| \encapchar | 297, 298, 303, 309, 310, 314, 373, 374, 390, 391, 404, 405, 423, 424, 428 |
| \endcsname | 48, 70, 71, 282, 318, 324, 382 |
| F | |
| _ | 352, 443 |
| A | |
| \active | 231, 238 |
| \addtolength | 265, 354 |
| \advance | 164 |
| \AfterLastShipout | 430 |
| \and | 45 |
| \AtBeginDocument | 226, 364 |
| \autoindex | 384, 385 |
| B | |
| \baselineskip | 192 |
| \bfseries | 159, 181 |
| G | |
| \g@addto@macro | 32, 53, 154, 289, 292 |
| \glossary@prologue | 203, 206 |
| \glossaryname | 220, 221 |
| H | |
| \HD@@bfseries | 186, 189 |
| \HD@@bfseries | 182, 183 |
| \HD@@guesstoclevel | 78, 80 |
| \HD@@sectionpatch | 63, 64, 69 |

| | | | |
|---------------------------|--|-----------------------|---|
| \HD@bfseries | 159, 182 | \headsep | 25 |
| \HD@codeline@wrindex | 290, 295 | \hfil | 185, 189, 198 |
| \HD@disable@writebookmark | 66, 76 | \hspace | 357 |
| \HD@end | 78, 80 | \Hy@UseMaketitleInfos | 32 |
| \HD@guesstoclevel | 77, 96, 103, 117, 130, 143, 161, 212 | \Hy@writebookmark | 66, 152, 157, 172, 204, 210 |
| \HD@helplength | 223, 264, 265, 266, 352, 353, 354, 357 | \hypercalcbp | 24 |
| \HD@hfil | 182, 185 | \hyperlink | 319 |
| \HD@maketarget | 267, 270, 273, 276 | \hyperpage | 325 |
| \HD@margin | 193, 195, 200 | \hypersetup | 19, 35 |
| \HD@ModFix | 50, 54, 55, 56, 57, 58 | \hypertarget | 279 |
| \HD@next | 278, 284, 287 | | |
| \HD@numberedtrue | 6 | I | |
| \HD@page@wrindex | 293, 307 , 416 | \if@filesw | 431 |
| \HD@savedest@add | 249, 256 , 320 | \ifcase | 94 |
| \HD@savedest@entry | 236, 252 | \ifdim | 353 |
| \HD@savedest@init | 227, 230 | \ifHD@numbered | 5, 62, 100, 114, 127, 140, 155, 168, 207 |
| \HD@savedest@out | 243, 245, 247, 257 | \ifHD@savedest | 224 , 234, 281 |
| \HD@savedesttrue | 225 | \ifHD@targetraise | 259 , 262 |
| \HD@sectionpatch | ... 61, 107, 121, 134, 146, 153, 205 | \ifhmode | 263 |
| \HD@SetMacroIndent | 433, 436, 440 | \ifx | 10, 34, 48, 185, 190, 282, 318, 324, 382 |
| \HD@target | 261, 333, 344, 356, 360, 371, 388, 403 | \immediate | 245, 247, 257, 432, 435 |
| \HD@targetraisetrue | 260 | \index | 365, 372, 389, 416 |
| \HD@toclevel@index | 161, 163, 173 | \index@prologue | 151, 161, 167 |
| \HD@toclevel@subindex | 165, 194 | \indexname | 174 |
| \hdclindex | 317 | \IndexParms | 154 |
| \HDorg@autoindex | 384, 394 | \InputIfFileExists | 240 |
| \HDorg@bfseries | 181, 184 | | |
| \HDorg@catcodeM | 237, 242 | J | |
| \HDorg@encapchar | ... 297, 299, 309, 311, 373, 375, 390, 392, 404, 406, 423, 425 | \jobname | 240, 244, 247 |
| \HDorg@glossary@prologue | 203, 212, 216 | | |
| \HDorg@index | 314, 364 , 372, 389 | K | |
| \HDorg@index@prologue | 151, 177 | \kern | 193, 195 |
| \HDorg@listoffigures | 112, 117, 122 | | |
| \HDorg@listoftables | 125, 130, 135 | L | |
| \HDorg@MacroFont | 331, 334, 342, 345 | \listfigurename | 118 |
| \HDorg@PrintDescribeMacro | 328, 336 | \listoffigures | 112, 113 |
| \HDorg@PrintMacroName | 339, 347 | \listoftables | 125, 126 |
| \HDorg@SortIndex | 412, 417 | \listtablename | 131 |
| \HDorg@SpecialEnvIndex | 399, 408 | \llap | 279, 355 |
| \HDorg@SpecialUsageIndex | 367 | | |
| \HDorg@tableofcontents | ... 87, 96, 98, 103, 108 | M | |
| \HDorg@thebibliography | 138, 143, 147 | \MacroFont | 331, 332, 342, 343 |
| \HDorg@theCodelineNo | 350, 352, 362, 443 | \MacroIndent | 353, 354, 443, 444 |
| \HDorg@theglossary | 201, 218 | \mathcode | 51 |
| \HDorg@theindex | 149, 179 | \mod@math@codes | 53 |
| \HDorg@tilde | 235, 241 | | |
| \HDorg@wrglossary | 421, 428 | N | |
| \HDorg@writebookmark | ... 152, 157, 172, 204, 210 | \NeedsTeXFormat | 2 |
| \hdpindex | 323 | \newcounter | 28, 222 |
| \headheight | 25 | \newif | 5, 224 , 259 |
| | | \newlength | 223 |
| | | \newwrite | 243 |
| | | \normalfont | 43 |
| | | \number | 30, 436 |
| | | \numexpr | 10 |
| | | O | |
| | | \openout | 247 |

| | | | |
|--|--|------------------------------|--|
| P | | | |
| \PageIndex | 292 | \SortIndex | 412, 413 |
| \paperheight | 25 | \special@index | 290, 293 |
| \pdfbookmark | 96, 103, 117, 130, 143, 173, 194, 212 | \SpecialEnvIndex | 399, 400 |
| \pdfstringdefDisableCommands | 39 | \SpecialUsageIndex | 367, 368 |
| \PrintDescribeMacro | 328, 329 | \stepcounter | 95, 102, 116, 129, 142, 171, 211, 277 |
| \PrintMacroName | 339, 340 | | T |
| \ProcessOptions | 7 | \tableofcontents | 87, 88 |
| \providecommand | 220, 221, 433 | \textbackslash | 42 |
| \ProvidesPackage | 3 | \thanks | 40 |
| | | \the | 165, 237, 279, 282, 300, 375, 392, 406 |
| R | | \thebibliography | 138, 139 |
| \raisebox | 192, 266 | \theCodelineNo | 350, 351 |
| \refname | 144 | \theglossary | 201, 202 |
| \renewcommand | 29, 329, 340, 351, 368, 385, 400, 413 | \theHD@unique | 29, 97, 104, 118, 131, 144, 174, 213 |
| \RequirePackage | 8, 9, 11, 13, 229 | \theindex | 149, 150 |
| \RerunFileCheck | 244 | \topmargin | 25 |
| | | | |
| S | | V | |
| \scshape | 44 | \value | 30, 436, 442 |
| \section | 78 | | |
| \settoheight | 264 | W | |
| \settowidth | 352, 443 | \write | 257, 432, 435 |