

The hypgotoe package

Heiko Oberdiek*

2016/05/16 v0.2

Abstract

Experimental package for links to embedded files.

Contents

1	Documentation	1
1.1	Introduction	1
1.2	User interface	2
1.3	Example	2
2	Implementation	3
2.1	Identification	3
2.2	Load packages	3
2.3	Color support	3
2.4	Extend \href	4
2.5	Implement gotoe action	4
2.6	Keys for gotoe action	5
3	Installation	6
3.1	Download	6
3.2	Bundle installation	6
3.3	Package installation	6
3.4	Refresh file name databases	7
3.5	Some details for the interested	7
4	References	7
5	History	7
	[2007/10/30 v0.1]	7
	[2016/05/16 v0.2]	8

1 Documentation

1.1 Introduction

This is a first experiment for links to embedded files. The package hypgotoe is named after the PDF action name /GoToE. Feedback is welcome, especially to the user interface.

- Currently only embedded files and named destinations are supported.

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

- Missing are support for destination arrays and attached files.
- Special characters aren't supported either.

In the future the package may be merged into package `hyperref`.

1.2 User interface

`\href` is extended to detect the prefix `'gotoe:'`. The part after the prefix is evaluated as key value list from left to right. For details, see “8.5.3 Action Types, Embedded Go-To Actions” [1].

dest: The destination name. The destination name can be set by `\hypertarget` in the target document. Or check the `.aux` file for destination names of `\label` commands. Also the target PDF file can be inspected, look for `/Dests` in the `/Names` entry of the catalog for named destinations. (Required.)

root: The file name of the root document. (Optional.)

parent: Go to the parent document. (No value, optional.)

embedded: Go to the embedded document. The value is the file name as it appears in `/EmbeddedFiles` of the current document.

The colors are controlled by `hyperref`'s options `gotoecolor` and `gotoebordercolor`. They can be set in `\hypersetup`, for example. Default is the color of file links.

1.3 Example

```

1 (*example)
2 \NeedsTeXFormat{LaTeX2e}
3 \RequirePackage{filecontents}
4 \begin{filecontents}{hypgotoe-child.tex}
5 \NeedsTeXFormat{LaTeX2e}
6 \documentclass{article}
7 \usepackage{hypgotoe}[2016/05/16]
8 \begin{document}
9 \section{This is the child document.}
10 \href{gotoe:%
11   dest={page.1},parent%
12 }{Go to first page of main document}\\
13 \href{gotoe:%
14   dest={page.2},parent%
15 }{Go to second page of main document}
16 \newpage
17 \section{This is the second page of the child document.}
18 \href{gotoe:%
19   dest={page.1},parent%
20 }{Go to first page of main document}\\
21 \href{gotoe:%
22   dest={page.2},parent%
23 }{Go to second page of main document}
24
25 \hypertarget{foobar}{}
26 Anker foobar is here.
27 \end{document}
28 \end{filecontents}
29 \documentclass{article}
30 \usepackage{hypgotoe}[2016/05/16]

```

```

31 \usepackage{embedfile}
32 \IfFileExists{hypgotoe-child.pdf}{%
33   \embedfile{hypgotoe-child.pdf}%
34 }{%
35   \typeout{}%
36   \typeout{--> Run hypgotoe-child.tex through pdflatex}%
37   \typeout{}%
38 }
39 \begin{document}
40 \section{First page of main document}
41 \href{gotoe:%
42   dest=page.1,embedded=hypgotoe-child.pdf%
43 }{Go to first page of child document}\\
44 \href{gotoe:%
45   dest=page.2,embedded=hypgotoe-child.pdf%
46 }{Go to second page of child document}\\
47 \href{gotoe:%
48   dest=foobar,embedded=hypgotoe-child.pdf%
49 }{Go to foobar in child document}
50 \newpage
51 \section{Second page of main document}
52 \href{gotoe:%
53   dest=section.1,embedded=hypgotoe-child.pdf%
54 }{Go to first section of child document}\\
55 \href{gotoe:%
56   dest=section.2,embedded=hypgotoe-child.pdf%
57 }{Go to second section of child document}\\
58 \href{gotoe:%
59   dest=foobar,embedded=hypgotoe-child.pdf%
60 }{Go to foobar in child document}
61 \end{document}
62 \end{example}

```

2 Implementation

2.1 Identification

```

63 (*package)
64 \NeedsTeXFormat{LaTeX2e}
65 \ProvidesPackage{hypgotoe}%
66 [2016/05/16 v0.2 Links to embedded files (H0)]%

```

2.2 Load packages

```

67 \RequirePackage{ifpdf}[2007/09/09]
68 \ifpdf
69 \else
70   \PackageError{hypgotoe}{%
71     Other drivers than pdfTeX in PDF mode are not supported.%
72     \MessageBreak
73     Package loading is aborted%
74   }\@ehc
75   \expandafter\endinput
76 \fi
77 \RequirePackage{pdfescape}[2007/10/27]
78 \RequirePackage{hyperref}[2016/05/16]

```

2.3 Color support

```

79 \define@key{Hyp}{gotoebordercolor}{%

```

```

80 \HyColor@HyperrefBordercolor{#1}%
81 \@gotoebordercolor{hyperref}{gotoebordercolor}%
82 }
83 \providecommand*\@gotoecolor{\@filecolor}
84 \providecommand*\@gotoebordercolor{\@filebordercolor}

```

2.4 Extend \href

\@hyper@readexternallink

```

85 \def\@hyper@readexternallink#1#2#3#4:#5:#6\\#7{%
86   \ifx\\#6\\%
87     \expandafter\@hyper@linkfile file:#7\\{#3}{#2}%
88   \else
89     \ifx\\#4\\%
90       \expandafter\@hyper@linkfile file:#7\\{#3}{#2}%
91     \else
92       \def\@pdftempa{#4}%
93       \ifx\@pdftempa\@pdftempwordfile
94         \expandafter\@hyper@linkfile#7\\{#3}{#2}%
95       \else
96         \ifx\@pdftempa\@pdftempwordrun
97           \expandafter\@hyper@launch#7\\{#3}{#2}%
98         \else
99           \ifx\@pdftempa\@pdftempwordgotoe
100            \hyper@linkgotoe{#3}{#5}%
101          \else
102            \hyper@linkurl{#3}{#7\ifx\\#2\\#2\\else\hyper@hash#2\fi}%
103          \fi
104        \fi
105      \fi
106    \fi
107  \fi
108 }

```

\@pdftempwordgotoe

```

109 \def\@pdftempwordgotoe{gotoe}

```

2.5 Implement gotoe action

\hyper@linkgotoe

```

110 \def\hyper@linkgotoe#1#2{%
111   \begingroup
112   \let\HyGoToE@Root\@empty
113   \let\HyGoToE@Dest\@empty
114   \let\HyGoToE@TBegin\@empty
115   \let\HyGoToE@TEnd\@empty
116   \setkeys{HyGoToE}{#2}%
117   \leavevmode
118   \pdfstartlink
119     attr{%
120       \Hy@setpdfborder
121       \ifx\@pdfhighlight\@empty
122       \else
123         /H\@pdfhighlight
124       \fi
125       \ifx\@urlbordercolor\relax
126       \else
127         /C[\@urlbordercolor]%

```

```

128     \fi
129   }%
130   user{%
131     /Subtype/Link%
132     /A<<%
133     /Type/Action%
134     /S/GoToE%
135     \Hy@SetNewWindow
136     \HyGoToE@Root
137     \HyGoToE@Dest
138     \HyGoToE@TBegin
139     \HyGoToE@TEnd
140   >>%
141   }%
142   \relax
143   \Hy@colorlink\@gotoecolor#1%
144   \close@pdflink
145 \endgroup
146 }

```

2.6 Keys for gotoe action

```

147 \define@key{HyGoToE}{root}{%
148   \EdefEscapeString\HyGoToE@temp{#1}%
149   \edef\HyGoToE@Root{%
150     /F<<%
151     /Type/Filespec%
152     /F(\HyGoToE@temp)%
153   >>%
154   }%
155 }
156 \define@key{HyGoToE}{dest}{%
157   \EdefEscapeString\HyGoToE@temp{#1}%
158   \edef\HyGoToE@Dest{%
159     /D(\HyGoToE@temp)%
160   }%
161 }
162 \define@key{HyGoToE}{parent}[]{%
163   \def\HyGoToE@temp{#1}%
164   \ifx\HyGoToE@temp\@empty
165   \else
166     \PackageWarning{hypgotoe}{Ignore value for `parent'}%
167   \fi
168   \edef\HyGoToE@TBegin{%
169     \HyGoToE@TBegin
170     /T<<%
171     /R/P%
172   }%
173   \edef\HyGoToE@TEnd{%
174     \HyGoToE@TEnd
175     >>%
176   }%
177 }
178 \define@key{HyGoToE}{embedded}{%
179   \EdefEscapeString\HyGoToE@temp{#1}%
180   \edef\HyGoToE@TBegin{%
181     \HyGoToE@TBegin
182     /T<<%

```

```

183   /R/C%
184   /N(\HyGoToE@temp)%
185   }%
186   \edef\HyGoToE@TEnd{%
187     \HyGoToE@TEnd
188     >>%
189   }%
190 }
191 \end{package}

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/hypgotoc.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/hypgotoc.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for \TeX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain \TeX :

```
tex hypgotoc.dtx
```

¹[CTAN:pkg/hypgotoc](#)

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
hypgotoe.sty      → tex/latex/oberdiek/hypgotoe.sty
hypgotoe.pdf      → doc/latex/oberdiek/hypgotoe.pdf
hypgotoe-example.tex → doc/latex/oberdiek/hypgotoe-example.tex
hypgotoe.dtx      → source/latex/oberdiek/hypgotoe.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your `TEX` distribution (`teTEX`, `mikTEX`, ...) relies on file name databases, you must refresh these. For example, `teTEX` users run `texhash` or `mktextlsr`.

3.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{hypgotoe.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdfLATEX`:

```
pdflatex_hypgotoe.dtx
makeindex_s_gind.ist_hypgotoe.idx
pdflatex_hypgotoe.dtx
makeindex_s_gind.ist_hypgotoe.idx
pdflatex_hypgotoe.dtx
```

4 References

- [1] Adobe Systems Incorporated: *PDF Reference, Sixth Edition, Version 1.7*, Oktober 2006; http://www.adobe.com/devnet/pdf/pdf_reference.html.

5 History

[2007/10/30 v0.1]

- First experimental version.

- Documentation updates.

6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
<code>\@ehc</code>	74
<code>\@empty</code> ...	112, 113, 114, 115, 121, 164
<code>\@filebordercolor</code>	84
<code>\@filecolor</code>	83
<code>\@gotoebordercolor</code>	81, 84
<code>\@gotoecolor</code>	83, 143
<code>\@hyper@launch</code>	97
<code>\@hyper@linkfile</code>	87, 90, 94
<code>\@hyper@readexternallink</code>	<u>85</u>
<code>\@pdfhighlight</code>	123
<code>\@pdfhighlightlight</code>	121
<code>\@pdftempa</code>	92, 93, 96, 99
<code>\@pdftempwordfile</code>	93
<code>\@pdftempwordgotoe</code>	99, <u>109</u>
<code>\@pdftempwordrun</code>	96
<code>\@urlbordercolor</code>	125, 127
<code>\@</code>	12, 20, 43, 46, 54, 57, 85, 86, 87, 89, 90, 94, 97, 102
B	
<code>\begin</code>	4, 8, 39
C	
<code>\close@pdflink</code>	144
D	
<code>\define@key</code>	79, 147, 156, 162, 178
<code>\documentclass</code>	6, 29
E	
<code>\EdefEscapeString</code>	148, 157, 179
<code>\embedfile</code>	33
<code>\end</code>	27, 28, 61
<code>\endinput</code>	75
H	
<code>\href</code> 10, 13, 18, 21, 41, 44, 47, 52, 55, 58	
<code>\Hy@colorlink</code>	143
<code>\Hy@SetNewWindow</code>	135
<code>\Hy@setpdfborder</code>	120
<code>\HyColor@HyperrefBordercolor</code> ...	80
<code>\HyGoToE@Dest</code>	113, 137, 158
<code>\HyGoToE@Root</code>	112, 136, 149
<code>\HyGoToE@TBegin</code>	114, 138, 168, 169, 180, 181
<code>\HyGoToE@temp</code>	148, 152, 157, 159, 163, 164, 179, 184
<code>\HyGoToE@TEnd</code>	115, 139, 173, 174, 186, 187
<code>\hyper@hash</code>	102
<code>\hyper@linkgotoe</code>	100, <u>110</u>
<code>\hyper@linkurl</code>	102
<code>\hypertarget</code>	25
I	
<code>\IfFileExists</code>	32
<code>\ifpdf</code>	68
<code>\ifx</code> 86, 89, 93, 96, 99, 102, 121, 125, 164	
L	
<code>\leavevmode</code>	117
M	
<code>\MessageBreak</code>	72
N	
<code>\NeedsTeXFormat</code>	2, 5, 64
<code>\newpage</code>	16, 50
P	
<code>\PackageError</code>	70
<code>\PackageWarning</code>	166
<code>\pdfstartlink</code>	118
<code>\providecommand</code>	83, 84
<code>\ProvidesPackage</code>	65
R	
<code>\RequirePackage</code>	3, 67, 77, 78
S	
<code>\section</code>	9, 17, 40, 51
<code>\setkeys</code>	116
T	
<code>\typeout</code>	35, 36, 37
U	
<code>\usepackage</code>	7, 30, 31