

# The `hyphsubst` package

Heiko Oberdiek  
<heiko.oberdiek at googlemail.com>

2008/06/09 v0.2

## Abstract

A TeX format file may include alternative hyphenation patterns for a language with a different name. If the naming convention follows `babel`'s rules, then the hyphenation patterns for a language can be replaced by the alternative hyphenation patterns, provided in the format file.

## Contents

<b>1 Documentation</b>	<b>1</b>
1.1 In short . . . . .	1
1.2 Longer version . . . . .	2
1.3 L <sup>A</sup> T <sub>E</sub> X . . . . .	2
1.4 plain-T <sub>E</sub> X . . . . .	3
<b>2 Implementation</b>	<b>3</b>
2.1 Reload check and package identification . . . . .	3
2.2 Package . . . . .	4
<b>3 Test</b>	<b>6</b>
3.1 Catcode checks for loading . . . . .	6
3.2 Main tests . . . . .	7
<b>4 Installation</b>	<b>8</b>
4.1 Download . . . . .	8
4.2 Bundle installation . . . . .	8
4.3 Package installation . . . . .	9
4.4 Refresh file name databases . . . . .	9
4.5 Some details for the interested . . . . .	9
<b>5 History</b>	<b>10</b>
[2008/06/07 v0.1] . . . . .	10
[2008/06/09 v0.2] . . . . .	10
<b>6 Index</b>	<b>10</b>

## 1 Documentation

### 1.1 In short

The package is an experimental package that allows the substitution of hyphenation patterns, example:

```
\RequirePackage[ngerman=ngerman-x-20080601]{hyphsubst}
\documentclass{article}
\usepackage[ngerman]{babel}
```

The patterns `ngerman` are replaced by the patterns `ngerman-x-20080601`. The format must contain these patterns and should use the naming scheme of either `babel`'s `language.dat` or `etex.src`'s `language.def`.

## 1.2 Longer version

Assume the format may contain the following hyphenation patterns (excerpt from `language.dat`):

```
...
ngerman dehyphn.tex
ngerman-x-20071231 dehyphn-x-20071231
ngerman-x-20080601 dehyphn-x-20080601
=ngerman-x-latest % alias for ngerman-x-20080601
...
```

The patterns that contain `-x-` are experimental new patterns for `ngerman`. However, package `babel` does not provide the use of patterns that do not have the same name as the used language (dialect). The `babel` system remembers patterns in macros: `\l@⟨name⟩`.  $\varepsilon$ -`TEX`'s `etex.src` uses `\lang@⟨name⟩` instead. In the following we use `babel`'s naming scheme, but `etex.src`'s naming scheme is supported, too.

This package `hyphsubst` solves the problem by redefining the macro `\l@⟨name⟩` to use other patterns.

`\HyphSubstLet {⟨nameA⟩} {⟨nameB⟩}`

`\l@⟨nameA⟩` now has the same meaning as `\l@⟨nameB⟩`. The patterns for `nameB` must exist. If the patterns for `nameA` exist, then they will be overwritten to use the patterns for `nameB`. Example:

```
\documentclass{article}
\usepackage{hyphsubst}
\HyphSubstLet{ngerman}{ngerman-x-20080601}
\usepackage[ngerman]{babel}
```

Now the patterns `ngerman-x-20080601` are be used.

Or if you want to compare hyphenations:

```
\documentclass{article}
\usepackage{hyphsubst}
% save original patterns for ngerman in ngerman-saved
\HyphSubstLet{ngerman-saved}{ngerman}
\usepackage[ngerman]{babel}
\begin{document}
We start with the original patterns for ngerman.
\HyphSubstLet{ngerman}{ngerman-x-latest}%
Now we are using ngerman-x-latest.
\HyphSubstLet{ngerman}{ngerman-saved}%
Again we are using the original patterns.
\end{document}
```

`\HyphSubstIfExists {⟨name⟩} {⟨then⟩} {⟨else⟩}`

Tests if patterns with name `⟨name⟩` exist and execute `⟨then⟩` in case of success and `⟨else⟩` otherwise.

## 1.3 L<sup>A</sup>T<sub>E</sub>X

The package can also be loaded before `\documentclass`:

```
\RequirePackage[ngerman=ngerman-x-20080601]{hyphsubst}
\documentclass{article}
...
```

This allows to put the package in a format file.

Package options are interpreted as ‘let’ assignments and passed to macro \HyphSubstLet:

```
\usepackage[ngerman=ngerman-x-20080601]{hyphsubst}
```

The part before the equal sign is the first argument for \HyphSubstLet and the part after the equal sign forms the second argument:

```
\HyphSubstLet{ngerman}{ngerman-x-20080601}
```

Note, this only works for direct package options. Global options are ignored.

## 1.4 plain-TeX

The package can be loaded and used with plain-TeX, e.g.:

```
\input hyphsubst.sty
\HyphSubstLet{ngerman}{ngerman-x-latest}
```

# 2 Implementation

1 (\*package)

## 2.1 Reload check and package identification

Reload check, especially if the package is not used with L<sup>A</sup>T<sub>E</sub>X.

```
2 \begingroup
3   \catcode44 12 % ,
4   \catcode45 12 % -
5   \catcode46 12 % .
6   \catcode58 12 % :
7   \catcode64 11 % @
8   \catcode123 1 % {
9   \catcode125 2 % }
10  \expandafter\let\expandafter\x\csname ver@hyphsubst.sty\endcsname
11  \ifx\x\relax % plain-TeX, first loading
12  \else
13    \def\empty{}%
14    \ifx\x\empty % LaTeX, first loading,
15      % variable is initialized, but \ProvidesPackage not yet seen
16    \else
17      \catcode35 6 % #
18      \expandafter\ifx\csname PackageInfo\endcsname\relax
19        \def\x#1#2{%
20          \immediate\write-1{Package #1 Info: #2.}%
21        }%
22      \else
23        \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
24      \fi
25      \x{hyphsubst}{The package is already loaded}%
26      \aftergroup\endinput
27    \fi
28  \fi
29 \endgroup
```

Package identification:

```
30 \begingroup
31   \catcode35 6 % #
32   \catcode40 12 % (
```

```

33 \catcode41 12 %
34 \catcode44 12 %
35 \catcode45 12 %
36 \catcode46 12 %
37 \catcode47 12 %
38 \catcode58 12 %
39 \catcode64 11 %
40 \catcode91 12 %
41 \catcode93 12 %
42 \catcode123 1 %
43 \catcode125 2 %
44 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
45   \def\x#1#2#3[#4]{\endgroup
46     \immediate\write-1{Package: #3 #4}%
47     \xdef#1[#4]%
48   }%
49 \else
50   \def\x#1#2[#3]{\endgroup
51     #2[#3]%
52     \ifx#1\undefined
53       \xdef#1[#3]%
54     \fi
55     \ifx#1\relax
56       \xdef#1[#3]%
57     \fi
58   }%
59 \fi
60 \expandafter\x\csname ver@hyphsubst.sty\endcsname
61 \ProvidesPackage{hyphsubst}%
62 [2008/06/09 v0.2 Substitute hyphenation patterns (HO)]%
63 \begingroup
64 \catcode123 1 %
65 \catcode125 2 %
66 \def\x{\endgroup
67   \expandafter\edef\csname HyphSubst@AtEnd\endcsname{%
68     \catcode35 \the\catcode35\relax
69     \catcode64 \the\catcode64\relax
70     \catcode123 \the\catcode123\relax
71     \catcode125 \the\catcode125\relax
72   }%
73 }%
74 \x
75 \catcode35 6 %
76 \catcode64 11 %
77 \catcode123 1 %
78 \catcode125 2 %
79 \def\TMP@EnsureCode#1#2{%
80   \edef\HyphSubst@AtEnd{%
81     \HyphSubst@AtEnd
82     \catcode#1 \the\catcode#1\relax
83   }%
84   \catcode#1 #2\relax
85 }
86 \TMP@EnsureCode{39}{12}%
87 \TMP@EnsureCode{46}{12}%
88 \TMP@EnsureCode{47}{12}%
89 \TMP@EnsureCode{58}{12}%
90 \TMP@EnsureCode{61}{12}%
91 \TMP@EnsureCode{96}{12}%

```

## 2.2 Package

```

92 \begingroup\expandafter\expandafter\expandafter\endgroup
93 \expandafter\ifx\csname RequirePackage\endcsname\relax
94   \input infwarerr.sty\relax
95 \else
96   \RequirePackage{infwarerr}[2007/09/09]%
97 \fi

\HyphSubst@l

98 \begingroup\expandafter\expandafter\expandafter\endgroup
99 \expandafter\ifx\csname et@xlang\endcsname\relax
100 \def\HyphSubst@l{10}%
101 \else
102 \def\HyphSubst@l{lang@}%
103 \fi

\HyphSubstLet

104 \def\HyphSubstLet#1#2{%
105   \begingroup
106     \def\x{}%
107     \expandafter\ifx\csname\HyphSubst@l#2\endcsname\relax
108       \@PackageError{hyphsubst}{Unknown pattern '#2'}\@ehc
109     \else
110       \def\lmsg{}%
111       \expandafter\ifx\csname\HyphSubst@l#1\endcsname\relax
112         \edef\msg{%
113           New: \expandafter\string\csname\HyphSubst@l#1\endcsname
114           \noexpand\MessageBreak
115         }%
116     \else
117       \edef\msg{%
118         Redefined: \expandafter\string\csname\HyphSubst@l#1\endcsname
119         \noexpand\MessageBreak
120         old value: \number\csname\HyphSubst@l#1\endcsname
121         \noexpand\MessageBreak
122       }%
123       \ifnum\csname\HyphSubst@l#1\endcsname=\language
124         \edef\x{%
125           \noexpand\language=%
126           \number\csname\HyphSubst@l#2\endcsname\relax
127         }%
128         \edef\lmsg{%
129           \noexpand\MessageBreak
130           \string\language\noexpand\space updated%
131         }%
132       \fi
133     \fi
134     \expandafter\global\expandafter\let
135       \csname\HyphSubst@l#1\expandafter\endcsname
136       \csname\HyphSubst@l#2\endcsname
137     \@PackageInfo{hyphsubst}{%
138       \msg
139       new value: \number\csname\HyphSubst@l#1\endcsname
140       \lmsg
141     }%
142   \fi
143 \expandafter\endgroup\x
144 }

\HyphSubstIfExists

145 \def\HyphSubstIfExists#1{%
146   \begingroup\expandafter\expandafter\expandafter\endgroup
147   \expandafter\ifx\csname\HyphSubst@l#1\endcsname\relax

```

```

148      \expandafter\@secondoftwo
149  \else
150      \expandafter\@firstoftwo
151  \fi
152 }

\f@rstoftwo
153 \expandafter\ifx\csname @firstoftwo\endcsname\relax
154   \long\def\@firstoftwo#1#2{#1}%
155 \fi

\@secondoftwo
156 \expandafter\ifx\csname @secondoftwo\endcsname\relax
157   \long\def\@secondoftwo#1#2{#2}%
158 \fi

\begingroup\expandafter\expandafter\expandafter\endgroup
159 \expandafter\ifx\csname documentclass\endcsname\relax
160   \HyphSubst@AtEnd
161   \expandafter\endinput
162 \fi
163 \Declarerelax*\%
164 \expandafter\HyphSubst@Option\Currentrelax==\relax
165 }
166 \def\HyphSubst@Option#1=#2=#3\relax{%
167   \HyphSubstLet{#1}{#2}%
168 }
169 \ProcessOptions*\relax
170 \HyphSubst@AtEnd
171 
```

### 3 Test

#### 3.1 Catcode checks for loading

```

173 <*test1>
174 \catcode`\#=1 %
175 \catcode`\#=2 %
176 \catcode`\#=6 %
177 \catcode`\#=11 %
178 \expandafter\ifx\csname count@\endcsname\relax
179   \countdef\count@=255 %
180 \fi
181 \expandafter\ifx\csname @gobble\endcsname\relax
182   \long\def\@gobble#1{}%
183 \fi
184 \expandafter\ifx\csname @firstofone\endcsname\relax
185   \long\def\@firstofone#1{#1}%
186 \fi
187 \expandafter\ifx\csname loop\endcsname\relax
188   \expandafter\@firstofone
189 \else
190   \expandafter\@gobble
191 \fi
192 {%
193   \def\loop#1\repeat{%
194     \def\body{#1}%
195     \iterate
196   }%
197   \def\iterate{%

```

```

198     \body
199         \let\next\iterate
200     \else
201         \let\next\relax
202     \fi
203     \next
204   }%
205   \let\repeat=\fi
206 }%
207 \def\RestoreCatcodes{}
208 \count@=0 %
209 \loop
210   \edef\RestoreCatcodes{%
211     \RestoreCatcodes
212     \catcode\the\count@=\the\catcode\count@\relax
213   }%
214 \ifnum\count@<255 %
215   \advance\count@ 1 %
216 \repeat
217
218 \def\RangeCatcodeInvalid#1#2{%
219   \count@=#1\relax
220   \loop
221     \catcode\count@=15 %
222   \ifnum\count@<#2\relax
223     \advance\count@ 1 %
224   \repeat
225 }
226 \expandafter\ifx\csname LoadCommand\endcsname\relax
227   \def\LoadCommand{\input hyphsubst.sty\relax}%
228 \fi
229 \def\Test{%
230   \RangeCatcodeInvalid{0}{47}%
231   \RangeCatcodeInvalid{58}{64}%
232   \RangeCatcodeInvalid{91}{96}%
233   \RangeCatcodeInvalid{123}{255}%
234   \catcode`\@=12 %
235   \catcode`\|=0 %
236   \catcode`\{=1 %
237   \catcode`\}=2 %
238   \catcode`\#=6 %
239   \catcode`\[=12 %
240   \catcode`\]=12 %
241   \catcode`\%=14 %
242   \catcode`\ =10 %
243   \catcode13=5 %
244   \LoadCommand
245   \RestoreCatcodes
246 }
247 \Test
248 \csname @@end\endcsname
249 \end
250 
```

### 3.2 Main tests

```

251 <*test2>
252 \input hyphsubst.sty\relax
253
254 \catcode`\@=11\relax
255 \ifx\et@xlang\@undefined
256   \def\l#1{\csname l@#1\endcsname}%
257 \else

```

```

258 \def\l#1{\csname lang@#1\endcsname}%
259 \fi
260 \def\Check#1#2{%
261   \ifnum#1=#2\relax
262   \else
263     \@PackageError{test}{Wrong number: #1 <> #2}\@ehc
264   \fi
265 }
266
267 \language=0\relax
268 \HyphSubstLet{ZeroSaved}{ngerman}
269 \Check{\l{USenglish}}{0}%
270 \HyphSubstLet{USenglish}{ngerman}
271 \Check{\l{USenglish}}{\l{ngerman}}
272 \ifnum\l{USenglish}>0 %
273 \else
274   \@PackageError{test}{\string\language\space is not updated}\@ehc
275 \fi
276 \HyphSubstLet{german}{ngerman}
277 \Check{\l{german}}{\l{ngerman}}
278 \Check{\l{USenglish}}{\l{ngerman}}
279 \csname @@end\endcsname\end
280 
```

## 4 Installation

### 4.1 Download

**Package.** This package is available on CTAN<sup>1</sup>:

<CTAN:macros/latex/contrib/oberdiek/hyphsubst.dtx> The source file.

<CTAN:macros/latex/contrib/oberdiek/hyphsubst.pdf> Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

<CTAN:install/macros/latex/contrib/oberdiek.tds.zip>

*TDS* refers to the standard “A Directory Structure for *TeX* Files” (<CTAN:tds/tds.pdf>). Directories with `texmf` in their name are usually organized this way.

### 4.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDSScripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

---

<sup>1</sup><ftp://ftp.ctan.org/tex-archive/>

### 4.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain-**TEX**:

```
tex hyphsubst.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

hyphsubst.sty	→ tex/generic/oberdiek/hyphsubst.sty
hyphsubst.pdf	→ doc/latex/oberdiek/hyphsubst.pdf
test/hyphsubst-test1.tex	→ doc/latex/oberdiek/test/hyphsubst-test1.tex
test/hyphsubst-test2.tex	→ doc/latex/oberdiek/test/hyphsubst-test2.tex
hyphsubst.dtx	→ source/latex/oberdiek/hyphsubst.dtx

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

### 4.4 Refresh file name databases

If your **TEX** distribution (`teTEX`, `mikTEX`, ...) relies on file name databases, you must refresh these. For example, `teTEX` users run `texhash` or `mktexlsr`.

### 4.5 Some details for the interested

**Attached source.** The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk hyphsubst.pdf unpack_files output .
```

**Unpacking with LATEX.** The `.dtx` chooses its action depending on the format:

**plain-TEX:** Run `docstrip` and extract the files.

**LATEX:** Generate the documentation.

If you insist on using LATEX for `docstrip` (really, `docstrip` does not need LATEX), then inform the autodetect routine about your intention:

```
\tex \let\install=y\input{hyphsubst.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfLATEX:

```
pdflatex hyphsubst.dtx
makeindex -s gind.ist hyphsubst.idx
pdflatex hyphsubst.dtx
makeindex -s gind.ist hyphsubst.idx
pdflatex hyphsubst.dtx
```

## 5 History

[2008/06/07 v0.1]

- First public version.

[2008/06/09 v0.2]

- Support for  $\varepsilon$ -TEX's `language.def` added.
- Fix for undefined `\lmsg`.

## 6 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
<code>\#</code> . . . . .	176, 238
<code>\%</code> . . . . .	241
<code>\@</code> . . . . .	177, 234, 254
<code>\@PackageError</code> . . . . .	108, 263, 274
<code>\@PackageInfo</code> . . . . .	137
<code>\@ehc</code> . . . . .	108, 263, 274
<code>\@firstofone</code> . . . . .	185, 188
<code>\@firstoftwo</code> . . . . .	150, <u>153</u>
<code>\@gobble</code> . . . . .	182, 190
<code>\@secondoftwo</code> . . . . .	148, <u>156</u>
<code>\@undefined</code> . . . . .	52, 255
<code>\[</code> . . . . .	239
<code>\\\</code> . . . . .	235
<code>\{</code> . . . . .	174, 236
<code>\}</code> . . . . .	175, 237
<code>\]</code> . . . . .	240
<b>A</b>	
<code>\advance</code> . . . . .	215, 223
<code>\aftergroup</code> . . . . .	26
<b>B</b>	
<code>\body</code> . . . . .	194, 198
<b>C</b>	
<code>\catcode</code> . . . . .	3, 4, 5, 6, 7, 8, 9, 17, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 64, 65, 68, 69, 70, 71, 75, 76, 77, 78, 82, 84, 174, 175, 176, 177, 212, 221, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 254
<code>\Check</code> . . . . .	260, 269, 271, 277, 278
<code>\count@</code> . . . . .	179, 208, 212, 214, 215, 219, 221, 222, 223
<code>\countdef</code> . . . . .	179
<code>\csname</code> . . . . .	10, 18, <u>44</u> , 60, 67, 93, 99, 107, 111, 113, 118, 120, 123, 126, 135, 136, 139,
<b>D</b>	
<code>\CurrentOption</code> . . . . .	165
<b>E</b>	
<code>\empty</code> . . . . .	13, 14
<code>\end</code> . . . . .	249, 279
<code>\endcsname</code> . . . . .	10, 18, 44, 60, 67, 93, 99, 107, 111, 113, 118, 120, 123, 126, 135, 136, 139, 147, 153, 156, 160, 178, 181, 184, 187, 226, 248, 256, 258, 279
<code>\endinput</code> . . . . .	26, 162
<code>\et@xlang</code> . . . . .	255
<b>H</b>	
<code>\HyphSubst@AtEnd</code> . . . . .	80, 81, 161, 171
<code>\HyphSubst@l</code> . . . . .	<u>98</u> , 107, 111, 113, 118, 120, 123, 126, 135, 136, 139, 147
<code>\HyphSubst@Option</code> . . . . .	165, 167
<code>\HyphSubstIfExists</code> . . . . .	2, <u>145</u>
<code>\HyphSubstLet</code> . . . . .	2, <u>104</u> , 168, 268, 270, 276
<b>I</b>	
<code>\ifnum</code> . . . . .	123, 214, 222, 261, 272
<code>\ifx</code> . . . . .	11, 14, 18, 44, 52, 55, 93, 99, 107, 111, 147, 153, 156, 160, 178, 181, 184, 187, 226, 255
<code>\immediate</code> . . . . .	20, 46
<code>\input</code> . . . . .	94, 227, 252
<code>\iterate</code> . . . . .	195, 197, 199
<b>L</b>	
<code>\l</code> . . . . .	256, 258, 269, 271, 272, 277, 278
<code>\language</code> . . . . .	123, 125, 130, 267, 274
<code>\lmsg</code> . . . . .	110, 128, 140
<code>\LoadCommand</code> . . . . .	227, 244
<code>\loop</code> . . . . .	193, 209, 220
<b>M</b>	
<code>\MessageBreak</code> . . . . .	114, 119, 121, 129

<code>\msg</code>	.....	112, 117, 138	<code>\RestoreCatcodes</code>	..	207, 210, 211, 245
	<b>N</b>			<b>S</b>	
<code>\next</code>	.....	199, 201, 203	<code>\space</code>	.....	130, 274
<code>\number</code>	.....	120, 126, 139			
	<b>P</b>			<b>T</b>	
<code>\PackageInfo</code>	.....	23	<code>\Test</code>	.....	229, 247
<code>\ProcessOptions</code>	.....	170	<code>\the</code>	.....	68, 69, 70, 71, 82, 212
<code>\ProvidesPackage</code>	.....	15, 61	<code>\TMP@EnsureCode</code>	79, 86, 87, 88, 89, 90, 91	
	<b>R</b>			<b>W</b>	
<code>\RangeCatcodeInvalid</code>	.....		<code>\write</code>	.....	20, 46
	.....	218, 230, 231, 232, 233			
<code>\repeat</code>	.....	193, 205, 216, 224	<code>\x</code>	.....	10, 11, 14, 19, 23,
<code>\RequirePackage</code>	.....	96			25, 45, 50, 60, 66, 74, 106, 124, 143
	<b>X</b>				