

The `ifvtex` package

Heiko Oberdiek

<oberdiek@uni-freiburg.de>

2007/09/09 v1.3

Abstract

This package looks for VTEX, implements and sets the switches `\ifvtex`, `\ifvtex<mode>`, `\ifvtexgex`. It works with plain or LATEX formats.

Contents

1	Usage	1
2	Implementation	2
2.1	Reload check and package identification	2
2.2	Catcodes	3
2.3	Check for previously defined <code>\ifvtex</code>	3
2.4	<code>\ifvtex</code>	4
2.5	Mode and GeX switches	4
2.6	Protocol entry	5
3	Test	5
3.1	Catcode checks for loading	5
4	Installation	6
4.1	Download	6
4.2	Bundle installation	6
4.3	Package installation	6
4.4	Refresh file name databases	7
4.5	Some details for the interested	7
5	History	7
[2001/09/26 v1.0]	7
[2006/02/20 v1.1]	7
[2007/01/10 v1.2]	8
[2007/09/09 v1.3]	8
6	Index	8

1 Usage

The package `ifvtex` can be used with both plain-TEX and LATEX:

plain-TEX: `\input ifvtex.sty`

LATEX 2_ε: `\usepackage{ifvtex}`

The package implements switches for VTeX and its different modes and interprets `\VTeXversion`, `\OpMode`, and `\gemode`.

`\ifvtex`

The package provides the switch `\ifvtex`:

```
\ifvtex
... do things, if VTeX is running ...
\else
... other TeX compiler ...
\fi
```

Users of the package `ifthen` can use the switch as boolean:

```
\boolean{ifvtex}
```

`\ifvtexdvi` `\ifvtexpdf` `\ifvtexps` `\ifvtexhtml`

VTeX knows different output modes that can be asked by these switches.

`\ifvtexgex`

This switch shows, whether GeX is available.

2 Implementation

2.1 Reload check and package identification

```
1 {*package}
```

Reload check, especially if the package is not used with LATEX.

```
2 \begingroup
3   \catcode44 12 % ,
4   \catcode45 12 % -
5   \catcode46 12 % .
6   \catcode58 12 % :
7   \catcode64 11 % @
8   \expandafter\let\expandafter\x\csname ver@ifvtex.sty\endcsname
9   \ifcase 0%
10     \ifx\x\relax % plain
11     \else
12       \ifx\x\empty % LaTeX
13         \else
14           1%
15         \fi
16       \fi
17     \else
18       \expandafter\ifx\x\csname PackageInfo\endcsname\relax
19         \def\x#1#2{%
20           \immediate\write-1{Package #1 Info: #2.}%
21         }%
22       \else
23         \def\x#1#2{\PackageInfo{#1}{#2, stopped}%
24       \fi
25       \x{ifvtex}{The package is already loaded}%
26     \endgroup
```

```

27      \expandafter\endinput
28  \fi
29 \endgroup
Package identification:
30 \begingroup
31  \catcode40 12 % (
32  \catcode41 12 % )
33  \catcode44 12 % ,
34  \catcode45 12 % -
35  \catcode46 12 % .
36  \catcode47 12 % /
37  \catcode58 12 % :
38  \catcode64 11 % @
39 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
40   \def\x#1#2#3[#4]{\endgroup
41     \immediate\write-1{Package: #3 #4}%
42     \xdef#1[#4]%
43   }%
44 \else
45   \def\x#1#2[#3]{\endgroup
46     #2[#3]%
47     \ifx#1\relax
48       \xdef#1[#3]%
49     \fi
50   }%
51 \fi
52 \expandafter\x\csname ver@ifvtex.sty\endcsname
53 \ProvidesPackage{ifvtex}%
54 [2007/09/09 v1.3 Switches for detecting VTeX and its modes (HO)]

```

2.2 Catcodes

```

55 \expandafter\edef\csname ifvtex@AtEnd\endcsname{%
56   \catcode64 \the\catcode64\relax
57 }
58 \catcode64 11 % @
59 \def\TMP@EnsureCode#1#2{%
60   \edef\ifvtex@AtEnd{%
61     \ifvtex@AtEnd
62     \catcode#1 \the\catcode#1\relax
63   }%
64   \catcode#1 #2\relax
65 }
66 \TMP@EnsureCode{10}{12}%^J
67 \TMP@EnsureCode{39}{12}', '
68 \TMP@EnsureCode{44}{12}, '
69 \TMP@EnsureCode{45}{12} -, '
70 \TMP@EnsureCode{46}{12}., '
71 \TMP@EnsureCode{47}{12}/ '
72 \TMP@EnsureCode{58}{12} :, '
73 \TMP@EnsureCode{60}{12}< =
74 \TMP@EnsureCode{61}{12}>
75 \TMP@EnsureCode{62}{12}^ ^
76 \TMP@EnsureCode{94}{7}^ ^
77 \TMP@EnsureCode{96}{12}^ '

```

2.3 Check for previously defined \ifvtex

```

78 \begingroup
79  \expandafter\ifx\csname ifvtex\endcsname\relax
80  \else
81    \edef\i{\expandafter\string\csname ifvtex\endcsname}%
82    \expandafter\ifx\csname PackageError\endcsname\relax
83      \def\x#1#2{%

```

```

84      \edef\z{\#2}%
85      \expandafter\errhelp\expandafter{\z}%
86      \errmessage{Package ifvtex Error: #1}%
87  }%
88  \def\y{{}^J}%
89  \newlinechar=10 %
90 \else
91  \def\x{\#1\#2}%
92  \PackageError{ifvtex}{\#1}{\#2}%
93  }%
94  \def\y{\MessageBreak}%
95 \fi
96 \x{Name clash, \i/ is already defined}{%
97   Incompatible versions of \i/ can cause problems,\y
98   therefore package loading is aborted.%}
99 }%
100 \endgroup
101 \ifvtex@AtEnd
102   \expandafter\endinput
103 \fi
104 \endgroup

```

2.4 \ifvtex

\ifvtex Create and set the switch. \newif initializes the switch with \iffalse.

```

105 \newif\ifvtex
106 \begingroup\expandafter\expandafter\expandafter\endgroup
107 \expandafter\ifx\csname VTeXversion\endcsname\relax
108 \else
109  \begingroup\expandafter\expandafter\expandafter\endgroup
110  \expandafter\ifx\csname OpMode\endcsname\relax
111  \else
112    \vtexttrue
113  \fi
114 \fi

```

2.5 Mode and GeX switches

```

115 \newif\ifvtexdvi
116 \newif\ifvtexpdf
117 \newif\ifvtexps
118 \newif\ifvtexhtml
119 \newif\ifvtexgex
120 \ifvtex
121  \ifcase\OpMode\relax
122    \vtexdvittrue
123  \or % 1
124    \vtexpdftrue
125  \or % 2
126    \vtexpstrue
127  \or % 3
128    \vtexstrue
129  \or\or\or\or\or\or\or\or % 10
130    \vtexhtmltrue
131  \fi
132 \begingroup\expandafter\expandafter\expandafter\endgroup
133 \expandafter\ifx\csname gemode\endcsname\relax
134 \else
135   \ifnum\gemode>0 %
136     \vtxgextrue
137   \fi
138 \fi

```

```

139 \fi

2.6 Protocol entry

Log comment:
140 \begingroup
141   \expandafter\ifx\csname PackageInfo\endcsname\relax
142     \def\x#1#2{%
143       \immediate\write-1{Package #1 Info: #2.}%
144     }%
145   \else
146     \let\x\PackageInfo
147     \expandafter\let\csname on@line\endcsname\empty
148   \fi
149 \x{ifvtex}{%
150   VTeX %
151   \ifvtex
152     in \ifvtexdvi DVI\fi
153     \ifvtexpdf PDF\fi
154     \ifvtexps PS\fi
155     \ifvtexhtml HTML\fi
156     \space mode %
157     with\ifvtexgex\else out\fi\space GeX %
158   \else
159     not %
160   \fi
161   detected%
162 }%
163 \endgroup
164 \ifvtex@AtEnd
165 {/package}

```

3 Test

3.1 Catcode checks for loading

```

166 {*test1}
167 \catcode`\@=11 %
168 \def\RestoreCatcodes{%
169 \count@=0 %
170 \loop
171   \edef\RestoreCatcodes{%
172     \RestoreCatcodes
173     \catcode\the\count@=\the\catcode\count@\relax
174   }%
175 \ifnum\count@<255 %
176   \advance\count@\@ne
177 \repeat
178
179 \def\RangeCatcodeInvalid#1#2{%
180   \count@=#1\relax
181   \loop
182     \catcode\count@=15 %
183   \ifnum\count@<#2\relax
184     \advance\count@\@ne
185   \repeat
186 }
187 \def\Test{%
188   \RangeCatcodeInvalid{0}{47}%
189   \RangeCatcodeInvalid{58}{64}%
190   \RangeCatcodeInvalid{91}{96}%

```

```

191  \RangeCatcodeInvalid{123}{255}%
192  \catcode`\@=12 %
193  \catcode`\!=0 %
194  \catcode`\{=1 %
195  \catcode`\}=2 %
196  \catcode`\#=6 %
197  \catcode`\[=12 %
198  \catcode`\]=12 %
199  \catcode`\%=14 %
200  \catcode`\ =10 %
201  \catcode`13=5 %
202  \input ifvtex.sty\relax
203  \RestoreCatcodes
204 }
205 \Test
206 \csname @@end\endcsname
207 \end
208 
```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

<CTAN:macros/latex/contrib/oberdiek/ifvtex.dtx> The source file.

<CTAN:macros/latex/contrib/oberdiek/ifvtex.pdf> Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

<CTAN:macros/latex/contrib/oberdiek/oberdiek-tds.zip>

TDS refers to the standard “A Directory Structure for TeX Files” (<CTAN:tds/tds.pdf>). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek-tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek-tds.zip -d ~/texmf
```

Script installation. Check the directory `TDSScripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain-TEX:

```
tex ifvtex.dtx
```

¹<ftp://ftp.ctan.org/tex-archive/>

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
ifvtex.sty          → tex/generic/oberdiek/ifvtex.sty  
ifvtex.pdf         → doc/latex/oberdiek/ifvtex.pdf  
test/ifvtex-test1.tex → doc/latex/oberdiek/test/ifvtex-test1.tex  
ifvtex.dtx          → source/latex/oberdiek/ifvtex.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your `TeX` distribution (`teTeX`, `mikTeX`, ...) relies on file name databases, you must refresh these. For example, `teTeX` users run `texhash` or `mktexlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk ifvtex.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain-TeX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{ifvtex.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex ifvtex.dtx  
makeindex -s gind.ist ifvtex.idx  
pdflatex ifvtex.dtx  
makeindex -s gind.ist ifvtex.idx  
pdflatex ifvtex.dtx
```

5 History

[2001/09/26 v1.0]

- First public version.

[2006/02/20 v1.1]

- DTX framework.
- Undefined tests changed.

[2007/01/10 v1.2]

- Fix of the \ProvidesPackage description.

[2007/09/09 v1.3]

- Catcode section added.

6 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\#	196
\%	199
\@	167, 192
\@ne	176, 184
\[.	197
\\"	193
\{	194
\}	195
\]	198
_	200
A	
\advance	176, 184
C	
\catcode	3, 4, 5, 6, 7, 31, 32, 33, 34, 35, 36, 37, 38, 56, 58, 62, 64, 167, 173, 182, 192, 193, 194, 195, 196, 197, 198, 199, 200, 201
\count@	169,
\csname	173, 175, 176, 180, 182, 183, 184
\endcsname	8, 18, 39, 52, 55, 79, 81, 82, 107, 110, 133, 141, 147, 206
E	
\empty	12, 147
\end	207
\endcsname	8, 18, 39, 52, 55, 79, 81, 82, 107, 110, 133, 141, 147, 206
\endinput	27, 102
\errhelp	85
\errmessage	86
G	
\gexmode	135
I	
\i	81, 96, 97
\ifcase	9, 121
\ifnum	135, 175, 183
\ifvtex	2, 105, 120, 151
\ifvtex@AtEnd	60, 61, 101, 164
\ifvtexdvi	2, 115, 152
\ifvtexgex	2, 119, 157
\ifvtexhtml	2, 118, 155
L	
\loop	170, 181
M	
\MessageBreak	94
N	
\newif	105, 115, 116, 117, 118, 119
\newlinechar	89
O	
\OpMode	121
P	
\PackageError	92
\PackageInfo	23, 146
\ProvidesPackage	53
R	
\RangeCatcodeInvalid	179, 188, 189, 190, 191
\repeat	177, 185
\RestoreCatcodes	168, 171, 172, 203
S	
\space	156, 157
T	
\Test	187, 205
\the	56, 62, 173
\TMP@EnsureCode	59, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77
V	
\vtxdvittrue	122
\vtxgexttrue	136
\vtxhtmltrue	130
\vtxpdftrue	124
\vtxpstrue	126, 128
\vtxtrue	112
W	
\write	20, 41, 143

X	Y
\x 8, 10, 12, 19, 23, 25, 40, 45, 52, 83, 91, 96, 142, 146, 149	\y 88, 94, 97
	Z \z 84, 85