

The kvdefinekeys package

Heiko Oberdiek
<heiko.oberdiek at gmail.com>

2011/04/07 v1.3

Abstract

Package kvdefinekeys provides `\kv@define@key` to define keys the same way as keyval's `\define@key`. However, it works also using ini-TeX.

Contents

| | | |
|----------|---|----------|
| 1 | Documentation | 1 |
| 1.1 | Motivation | 1 |
| 2 | Implementation | 2 |
| 2.1 | Identification | 2 |
| 2.2 | Package loading | 3 |
| 2.3 | Provide key defining macro | 4 |
| 3 | Test | 4 |
| 3.1 | Catcode checks for loading | 4 |
| 4 | Installation | 6 |
| 4.1 | Download | 6 |
| 4.2 | Bundle installation | 6 |
| 4.3 | Package installation | 7 |
| 4.4 | Refresh file name databases | 7 |
| 4.5 | Some details for the interested | 7 |
| 5 | References | 8 |
| 6 | History | 8 |
| | [2010/03/01 v1.0] | 8 |
| | [2010/08/19 v1.1] | 8 |
| | [2011/01/30 v1.2] | 8 |
| | [2011/04/07 v1.3] | 8 |
| 7 | Index | 8 |

1 Documentation

1.1 Motivation

`\kvsetkeys` serves as replacement for keyval's `\setkeys`. This package adds macros to define keys, closing the gap `\kvsetkeys` leaves.

| |
|---|
| <code>\kv@define@key {<family>} {<key>} [<default>] {<definition>}</code> |
|---|

Macro `\kv@define@key` reimplements keyval's `\define@key`. Differences to the original:

- The defined keys also allow `\par` inside values.
- Shorthands of package `babel` are supported in family and key names.
- Macro `\kv@define@key` is made robust if ε -TeX's `\protected` or L^AT_EX's `\DeclareRobustCommand` are found.

2 Implementation

2.1 Identification

```
1 (*package)
```

Reload check, especially if the package is not used with L^AT_EX.

```
2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3 \catcode13=5 % ^~M
4 \endlinechar=13 %
5 \catcode35=6 % #
6 \catcode39=12 % '
7 \catcode44=12 % ,
8 \catcode45=12 % -
9 \catcode46=12 % .
10 \catcode58=12 % :
11 \catcode64=11 % @
12 \catcode123=1 % {
13 \catcode125=2 % }
14 \expandafter\let\expandafter\x\csname ver@kvdefinekeys.sty\endcsname
15 \ifx\x\relax % plain-TeX, first loading
16 \else
17 \def\empty{}%
18 \ifx\x\empty % LaTeX, first loading,
19 % variable is initialized, but \ProvidesPackage not yet seen
20 \else
21 \expandafter\ifx\csname PackageInfo\endcsname\relax
22 \def\x#1#2{%
23 \immediate\write-1{Package #1 Info: #2.}%
24 }%
25 \else
26 \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27 \fi
28 \x{kvdefinekeys}{The package is already loaded}%
29 \aftergroup\endinput
30 \fi
31 \fi
32 \endgroup%
```

Package identification:

```
33 \begingroup\catcode61\catcode48\catcode32=10\relax%
34 \catcode13=5 % ^~M
35 \endlinechar=13 %
36 \catcode35=6 % #
37 \catcode39=12 % '
38 \catcode40=12 % (
39 \catcode41=12 % )
40 \catcode44=12 % ,
41 \catcode45=12 % -
42 \catcode46=12 % .
43 \catcode47=12 % /
44 \catcode58=12 % :
45 \catcode64=11 % @
46 \catcode91=12 % [
47 \catcode93=12 % ]
48 \catcode123=1 % {
```

```

49 \catcode125=2 % }
50 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
51 \def\x#1#2#3[#4]{\endgroup
52 \immediate\write-1{Package: #3 #4}%
53 \xdef#1{#4}%
54 }%
55 \else
56 \def\x#1#2[#3]{\endgroup
57 #2[#3]}%
58 \ifx#1\@undefined
59 \xdef#1{#3}%
60 \fi
61 \ifx#1\relax
62 \xdef#1{#3}%
63 \fi
64 }%
65 \fi
66 \expandafter\x\csname ver@kvdefinekeys.sty\endcsname
67 \ProvidesPackage{kvdefinekeys}%
68 [2011/04/07 v1.3 Defining keys (H0)]%
69 \begingroup\catcode61\catcode48\catcode32=10\relax%
70 \catcode13=5 % ^^M
71 \endlinechar=13 %
72 \catcode123=1 % {
73 \catcode125=2 % }
74 \catcode64=11 % @
75 \def\x{\endgroup
76 \expandafter\edef\csname KVD@AtEnd\endcsname{%
77 \endlinechar=\the\endlinechar\relax
78 \catcode13=\the\catcode13\relax
79 \catcode32=\the\catcode32\relax
80 \catcode35=\the\catcode35\relax
81 \catcode61=\the\catcode61\relax
82 \catcode64=\the\catcode64\relax
83 \catcode123=\the\catcode123\relax
84 \catcode125=\the\catcode125\relax
85 }%
86 }%
87 \x\catcode61\catcode48\catcode32=10\relax%
88 \catcode13=5 % ^^M
89 \endlinechar=13 %
90 \catcode35=6 % #
91 \catcode64=11 % @
92 \catcode123=1 % {
93 \catcode125=2 % }
94 \def\TMP@EnsureCode#1#2{%
95 \edef\KVD@AtEnd{%
96 \KVD@AtEnd
97 \catcode#1=\the\catcode#1\relax
98 }%
99 \catcode#1=#2\relax
100 }
101 \TMP@EnsureCode{42}{12}% *
102 \TMP@EnsureCode{46}{12}% .
103 \TMP@EnsureCode{47}{12}% /
104 \TMP@EnsureCode{91}{12}% [
105 \TMP@EnsureCode{93}{12}% ]
106 \edef\KVD@AtEnd{\KVD@AtEnd\noexpand\endinput}

```

2.2 Package loading

```

107 \begingroup\expandafter\expandafter\expandafter\endgroup
108 \expandafter\ifx\csname RequirePackage\endcsname\relax

```

```

109 \def\TMP@RequirePackage#1[#2]{%
110   \begingroup\expandafter\expandafter\expandafter\endgroup
111   \expandafter\ifx\csname ver@#1.sty\endcsname\relax
112     \input #1.sty\relax
113   \fi
114 }%
115 \TMP@RequirePackage{ltxcms}[2010/03/01]%
116 \else
117   \RequirePackage{ltxcms}[2010/03/01]%
118 \fi

```

2.3 Provide key defining macro

`\kv@define@key`

```

119 \ltx@ifundefined{protected}{%
120   \ltx@ifundefined{DeclareRobustCommand}{%
121     \def\kv@define@key#1#2%
122   }{%
123     \DeclareRobustCommand*{\kv@define@key}[2]%
124   }%
125 }{%
126   \protected\def\kv@define@key#1#2%
127 }%
128 {%
129   \begingroup
130     \csname @safe@activestrue\endcsname
131     \let\ifincsname\iftrue
132     \edef\KVD@temp{\endgroup
133       \noexpand\KVD@DefineKey{#1}{#2}%
134     }%
135   \KVD@temp
136 }

```

`\KVD@DefineKey`

```

137 \def\KVD@DefineKey#1#2{%
138   \ltx@ifnextchar[{%
139     \KVD@DefineKeyWithDefault{#1}{#2}%
140   }{%
141     \long\expandafter\def\csname KV@#1@#2\endcsname##1%
142   }%
143 }

```

`\KVD@DefineKeyWithDefault`

```

144 \long\def\KVD@DefineKeyWithDefault#1#2[#3]{%
145   \expandafter\def\csname KV@#1@#2default\endcsname
146   \expandafter{%
147     \csname KV@#1@#2\endcsname{#3}%
148   }%
149   \long\expandafter\def\csname KV@#1@#2\endcsname##1%
150 }

151 \KVD@AtEnd%
152 </package>

```

3 Test

3.1 Catcode checks for loading

```

153 <*test1>

154 \catcode'\{=1 %
155 \catcode'\}=2 %

```

```

156 \catcode'\#=6 %
157 \catcode'\@=11 %
158 \expandafter\ifx\csname count@\endcsname\relax
159 \countdef\count@=255 %
160 \fi
161 \expandafter\ifx\csname @gobble\endcsname\relax
162 \long\def\@gobble#1{%
163 \fi
164 \expandafter\ifx\csname @firstofone\endcsname\relax
165 \long\def\@firstofone#1{#1}%
166 \fi
167 \expandafter\ifx\csname loop\endcsname\relax
168 \expandafter\@firstofone
169 \else
170 \expandafter\@gobble
171 \fi
172 {%
173 \def\loop#1\repeat{%
174 \def\body{#1}%
175 \iterate
176 }%
177 \def\iterate{%
178 \body
179 \let\next\iterate
180 \else
181 \let\next\relax
182 \fi
183 \next
184 }%
185 \let\repeat=\fi
186 }%
187 \def\RestoreCatcodes{
188 \count@=0 %
189 \loop
190 \edef\RestoreCatcodes{%
191 \RestoreCatcodes
192 \catcode\the\count@=\the\catcode\count@\relax
193 }%
194 \ifnum\count@<255 %
195 \advance\count@ 1 %
196 \repeat
197
198 \def\RangeCatcodeInvalid#1#2{%
199 \count@=#1\relax
200 \loop
201 \catcode\count@=15 %
202 \ifnum\count@<#2\relax
203 \advance\count@ 1 %
204 \repeat
205 }
206 \def\RangeCatcodeCheck#1#2#3{%
207 \count@=#1\relax
208 \loop
209 \ifnum#3=\catcode\count@
210 \else
211 \errmessage{%
212 Character \the\count@\space
213 with wrong catcode \the\catcode\count@\space
214 instead of \number#3%
215 }%
216 \fi
217 \ifnum\count@<#2\relax

```

```

218     \advance\count@ 1 %
219 \repeat
220 }
221 \def\space{ }
222 \expandafter\ifx\csname LoadCommand\endcsname\relax
223 \def\LoadCommand{\input kvdefinekeys.sty\relax}%
224 \fi
225 \def\Test{%
226 \RangeCatcodeInvalid{0}{47}%
227 \RangeCatcodeInvalid{58}{64}%
228 \RangeCatcodeInvalid{91}{96}%
229 \RangeCatcodeInvalid{123}{255}%
230 \catcode'\@=12 %
231 \catcode'\=0 %
232 \catcode'\%=14 %
233 \LoadCommand
234 \RangeCatcodeCheck{0}{36}{15}%
235 \RangeCatcodeCheck{37}{37}{14}%
236 \RangeCatcodeCheck{38}{47}{15}%
237 \RangeCatcodeCheck{48}{57}{12}%
238 \RangeCatcodeCheck{58}{63}{15}%
239 \RangeCatcodeCheck{64}{64}{12}%
240 \RangeCatcodeCheck{65}{90}{11}%
241 \RangeCatcodeCheck{91}{91}{15}%
242 \RangeCatcodeCheck{92}{92}{0}%
243 \RangeCatcodeCheck{93}{96}{15}%
244 \RangeCatcodeCheck{97}{122}{11}%
245 \RangeCatcodeCheck{123}{255}{15}%
246 \RestoreCatcodes
247 }
248 \Test
249 \csname @@end\endcsname
250 \end
251 </test1>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/kvdefinekeys.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/kvdefinekeys.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

¹[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain `TeX`:

```
tex kvdefinekeys.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
kvdefinekeys.sty      → tex/generic/oberdiek/kvdefinekeys.sty
kvdefinekeys.pdf      → doc/latex/oberdiek/kvdefinekeys.pdf
test/kvdefinekeys-test1.tex → doc/latex/oberdiek/test/kvdefinekeys-test1.tex
kvdefinekeys.dtx      → source/latex/oberdiek/kvdefinekeys.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your `TeX` distribution (`teTeX`, `mikTeX`, ...) relies on file name databases, you must refresh these. For example, `teTeX` users run `texhash` or `mktextlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk kvdefinekeys.pdf unpack_files output .
```

Unpacking with \LaTeX . The `.dtx` chooses its action depending on the format:

plain `TeX`: Run `docstrip` and extract the files.

\LaTeX : Generate the documentation.

If you insist on using \LaTeX for `docstrip` (really, `docstrip` does not need \LaTeX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{kvdefinekeys.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdf \LaTeX` :

```
pdflatex kvdefinekeys.dtx
makeindex -s gind.ist kvdefinekeys.idx
pdflatex kvdefinekeys.dtx
makeindex -s gind.ist kvdefinekeys.idx
pdflatex kvdefinekeys.dtx
```

5 References

- [1] David Carlisle: *The keyval package*; 1999/03/16 v1.13; [CTAN:macros/latex/required/graphics/keyval.dtx](#).

6 History

[2010/03/01 v1.0]

- First version.

[2010/08/19 v1.1]

- Documentation fix, no code change.

[2011/01/30 v1.2]

- Already loaded package files are not input in plain T_EX.

[2011/04/07 v1.3]

- Support for package `babel`'s shorthands added.
- `\kv@define@key` is made robust if available.

7 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

| Symbols | | | |
|---------------------------|--|------------------------------------|---|
| <code>\#</code> | 156 | <code>\countdef</code> | 159 |
| <code>\%</code> | 232 | <code>\csname</code> | 14, 21, 50, 66, 76, 108, 111, 130, 141, 145, 147, 149, 158, 161, 164, 167, 222, 249 |
| <code>\@</code> | 157, 230 | D | |
| <code>\@firstofone</code> | 165, 168 | <code>\DeclareRobustCommand</code> | 123 |
| <code>\@gobble</code> | 162, 170 | E | |
| <code>\@undefined</code> | 58 | <code>\empty</code> | 17, 18 |
| <code>\@</code> | 231 | <code>\end</code> | 250 |
| <code>\{</code> | 154 | <code>\endcsname</code> | 14, 21, 50, 66, 76, 108, 111, 130, 141, 145, 147, 149, 158, 161, 164, 167, 222, 249 |
| <code>\}</code> | 155 | <code>\endinput</code> | 29, 106 |
| A | | <code>\endlinechar</code> | 4, 35, 71, 77, 89 |
| <code>\advance</code> | 195, 203, 218 | <code>\errmessage</code> | 211 |
| <code>\aftergroup</code> | 29 | I | |
| B | | <code>\ifincsn</code> | 131 |
| <code>\body</code> | 174, 178 | <code>\ifnum</code> | 194, 202, 209, 217 |
| C | | <code>\iftrue</code> | 131 |
| <code>\catcode</code> | 2, 3, 5, 6, 7, 8, 9, 10, 11, 12, 13, 33, 34, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 69, 70, 72, 73, 74, 78, 79, 80, 81, 82, 83, 84, 87, 88, 90, 91, 92, 93, 97, 99, 154, 155, 156, 157, 192, 201, 209, 213, 230, 231, 232 | <code>\ifx</code> | 15, 18, 21, 50, 58, 61, 108, 111, 158, 161, 164, 167, 222 |
| <code>\count@</code> | 159, 188, 192, 194, 195, 199, 201, 202, 203, 207, 209, 212, 213, 217, 218 | <code>\immediate</code> | 23, 52 |
| | | <code>\input</code> | 112, 223 |
| | | <code>\iterate</code> | 175, 177, 179 |
| | | K | |
| | | <code>\kv@define@key</code> | 1, 119 |

| | | | |
|---------------------------|--|----------------------|--|
| \KVD@AtEnd | 95, 96, 106, 151 | \RangeCatcodeInvalid | |
| \KVD@DefineKey | 133, 137 | | 198, 226, 227, 228, 229 |
| \KVD@DefineKeyWithDefault | 139, 144 | \repeat | 173, 185, 196, 204, 219 |
| \KVD@temp | 132, 135 | \RequirePackage | 117 |
| | | \RestoreCatcodes | 187, 190, 191, 246 |
| L | | | |
| \LoadCommand | 223, 233 | | |
| \loop | 173, 189, 200, 208 | S | |
| \ltx@ifnextchar | 138 | \space | 212, 213, 221 |
| \ltx@ifUndefined | 119, 120 | | |
| N | | | |
| \next | 179, 181, 183 | \Test | 225, 248 |
| \number | 214 | \the | 77, 78, 79, 80, 81, 82, 83, 84, 97, 192, 212, 213 |
| P | | | |
| \PackageInfo | 26 | \TMP@EnsureCode | 94, 101, 102, 103, 104, 105 |
| \protected | 126 | \TMP@RequirePackage | 109, 115 |
| \ProvidesPackage | 19, 67 | | |
| R | | | |
| \RangeCatcodeCheck | 206, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245 | W | |
| | | \write | 23, 52 |
| X | | | |
| | | \x | 14, 15, 18, 22, 26, 28, 51, 56, 66, 75, 87 |