

The `kvoptions` package

Heiko Oberdiek

<oberdiek@uni-freiburg.de>

2007/06/11 v2.7

Abstract

This package is intended for package authors who want to use options in key value format for their package options.

Contents

1	Introduction	2
1.1	The beginning	2
1.2	Overview	2
2	Usage	3
2.1	Process options	3
2.1.1	\ProcessKeyvalOptions	3
2.1.2	\SetupKeyvalOptions	3
2.2	Option declarations	4
2.2.1	\DeclareStringOption	4
2.2.2	\DeclareBoolOption	4
2.2.3	\DeclareComplementaryOption	5
2.2.4	\DeclareVoidOption	5
2.2.5	\DeclareDefaultOption	5
2.2.6	Dynamic options	6
2.2.7	\DisableKeyvalOption	6
2.3	Summary of internal macros	7
3	Example	7
4	Package options	9
4.1	Option patch	9
4.2	Option debugshow	10
5	Limitations	11
5.1	Compatibility	11
5.1.1	Option patch vs. package <code>xkvltxp</code>	11
5.2	Limitations	11
5.2.1	Option comparisons	11
5.2.2	Option list parsing with option patch	11
6	Implementation	12
6.1	Preamble	12
6.2	Option declaration macros	12
6.2.1	\SetupKeyvalOptions	12
6.2.2	\DeclareBoolOption	13
6.2.3	\DeclareStringOption	15
6.2.4	\DeclareVoidOption	16
6.2.5	\DeclareDefaultOption	17

6.3	Dynamic options	17
6.3.1	\DisableKeyvalOption	17
6.4	Process options	19
6.5	\ProcessKeyvalOptions	19
6.5.1	Helper macros	21
6.6	Patch	22
7	Installation	29
7.1	Download	29
7.2	Bundle installation	29
7.3	Package installation	29
7.4	Refresh file name databases	29
7.5	Some details for the interested	30
8	References	30
9	History	31
[0000/00/00 v0.0]	31
[2004/02/22 v1.0]	31
[2006/02/16 v2.0]	31
[2006/02/20 v2.1]	31
[2006/06/01 v2.2]	31
[2006/08/17 v2.3]	31
[2006/08/22 v2.4]	31
[2007/04/11 v2.5]	31
[2007/05/06 v2.6]	31
[2007/06/11 v2.7]	31
10	Index	32

1 Introduction

1.1 The beginning

This package addresses class or package writers that want to allow their users to specify options as key value pairs, e.g.:

```
\documentclass[verbose=false,name=me]{myclass}
\usepackage[format=print]{mylayout}
```

Prominent example is package `hyperref`, probably the first package that offers this service. It's `\ProcessOptionsWithKV` is often copied und used in other packages, e.g. package `helvet` that uses this interface for its option `scaled`.

However copying code is not the most modern software development technique. And `hyperref`'s code for `\ProcessOptionsWithKV` was changed to fix bugs. The version used in other packages depends on the time of copying and the awareness of `hyperref`'s changes. Now the code is sourced out into this package and available for other package or class writers.

1.2 Overview

Package `kvoptions` connects package `keyval` with L^AT_EX's package and class *options*:

Package <code>keyval</code>	Package <code>kvoptions</code>	\LaTeX kernel
<code>\define@key</code>	<code>\DeclareVoidOption</code> <code>\DeclareStringOption</code> <code>\DeclareBoolOption</code> <code>\DeclareComplementaryOption</code> <code>\DisableKeyvalOption</code>	<code>\DeclareOption</code>
	<code>\DeclareDefaultOption</code>	<code>\DeclareOption*</code>
	<code>\ProcessKeyvalOptions</code>	<code>\ProcessOptions*</code>
	Option patch	Class/package option system
	<code>\SetupKeyvalOptions</code>	

2 Usage

2.1 Process options

2.1.1 `\ProcessKeyvalOptions`

```
\ProcessKeyvalOptions {\langle family \rangle}
\ProcessKeyvalOptions *
```

This command evaluates the global or local options of the package that are defined with keyval's interface within the family $\langle family \rangle$. It acts the same way as \LaTeX 's `\ProcessOptions*`. In a package unknown global options are ignored, in a class they are added to the unknown option list. The known global options and all local options are passed to keyval's `\setkeys` command for executing the options. Unknown options are reported to the user by an error.

If the family name happens to be the same as the name of the package or class where `\ProcessKeyvalOptions` is used or the family name has previously been setup by `\SetupKeyvalOptions`, then `\ProcessKeyvalOptions` knows the family name already and you can use the star form without mandatory argument.

Note, neither of the following commands are necessary for `\ProcessKeyvalOptions`. They just help the package/class author in common tasks.

2.1.2 `\SetupKeyvalOptions`

```
\SetupKeyvalOptions {
  family = \langle family \rangle,
  prefix = \langle prefix \rangle
}
```

This command allows to configure the default assumptions that are based on the current package or class name. \LaTeX remembers this name in `\@currname`. The syntax description of the default looks a little weird, therefor an example is given for a package or class named `foobar`.

Key	Default (example)	Used by
<code>family</code>	<code>\@currname</code> (<code>foobar</code>)	<code>\ProcessKeyvalOptions*</code> <code>\DeclareBoolOption</code> <code>\DeclareStringOption</code>
<code>prefix</code>	<code>\@currname@</code> (<code>foobar@</code>)	<code>\DeclareBoolOption</code> <code>\DeclareStringOption</code> <code>\DeclareVoidOption</code>

2.2 Option declarations

The options for `\ProcessKeyvalOptions` are defined by `keyval`'s `\define@key`. Common purposes of such keys are boolean switches, they enable or disable something. Or they store a name or some kind of string in a macro. The following commands help the user. He declares what he wants and `kvoptions` take care of the key definition, resource allocation and initialization.

In order to avoid name clashes of macro names, internal commands are prefixed. Both the prefix and the family name for the defined keys can be configured by `\SetupKeyvalOptions`.

2.2.1 `\DeclareStringOption`

```
\DeclareStringOption [<init>] {<key>} [<default>]
```

A macro is created that remembers the value of the key `<key>`. The name of the macro consists of the option name `<key>` that is prefixed by the prefix (see 2.1.2). The initial contents of the macro can be given by the first optional argument `<init>`. The default is empty.

The the option `<key>` is defined. The option code just stores its value in the macro. If the optional argument at the end of `\DeclareStringOption` is given, then option `<key>` is defined with the default `<default>`.

Example for a package with the following two lines:

```
\ProvidesPackage{foobar}
\DeclareStringOption[me]{name}
```

Then `\DeclareStringOption` defines the macro with content `me`, note L^AT_EX complains if the name of the macro already exists:

```
\newcommand*{\foobar@name}{me}
```

The option definition is similar to:

```
\define@key{foobar}{name}{%
  \renewcommand*{\foobar@name}{#1}%
}
```

2.2.2 `\DeclareBoolOption`

```
\DeclareBoolOption [<init>] {<key>}
```

A boolean switch is generated, initialized by value `<init>` and the corresponding key `<key>` is defined. If the initialization value is not given, `false` is used as default.

The internal actions of `\DeclareBoolOption` are shown below. The example is given for a package author who has the following two lines in his package/class:

```
\ProvidesPackage{foobar}
\DeclareBoolOption{verbose}
```

First a new switch is created:

```
\newif\iffoobar@verbose
```

and initialized:

```
\foobar@verbosefalse
```

Finally the key is defined:

```
\define@key{foobar}{verbose}[true]{...}
```

The option code configures the boolean option in the following way: If the author specifies `true` or `false` then the switch is turned on or off respectively. Also the option can be given without explicit value. Then the switch is enabled. Other values are reported as errors.

Now the switch is ready to use in the package/class, e.g.:

```
\iffboar@verbose
% print verbose message
\else
% be quiet
\fi
```

Users of package `\ifthen` can use the switch as boolean:

```
\boolean{foobar@verbose}
```

2.2.3 \DeclareComplementaryOption

<code>\DeclareComplementaryOption{\langle key\rangle}{\langle parent\rangle}</code>

Sometimes contrasting names are used to characterize the two states of a boolean switch, for example `final` vs. `final`. Both options behave like boolean options but they do not need to different switches, they should share one. `\DeclareComplementaryOption` allows this. The option `\langle key\rangle` shares the switch of option `\langle parent\rangle`. Example:

```
\DeclareBoolOption{draft}
\DeclareComplementaryOption{final}{draft}
```

Then `final` sets the switch of `draft` to `false`, and `final=false` enables the `draft` switch.

2.2.4 \DeclareVoidOption

<code>\DeclareVoidOption{\langle key\rangle}{\langle code\rangle}</code>

`\ProcessKeyvalOptions` can be extended to recognize options that are declared in traditional way by `\DeclareOption`. But in case of the error that the user specifies a value, then this option would not be recognized as key value option because of `\DeclareOption` and not detected as traditional option because of the value part. The user would get an unknown option error, difficult to understand.

`\DeclareVoidOption` solves this problem. It defines the option `\langle key\rangle` as key value option. If the user specifies a value, a warning is given and the value is ignored.

The code part `\langle code\rangle` is stored in a macro. The name of the macro consists of the option name `\langle key\rangle` that is prefixed by the prefix (see 2.1.2). If the option is set, the macro will be executed. During the execution `\CurrentOption` is available with the current key name.

2.2.5 \DeclareDefaultOption

<code>\DeclareDefaultOption{\langle code\rangle}</code>

This command does not define a key, it is the equivalent to L^AT_EX's `\DeclareOption*`. It allows the specification of a default action `\langle code\rangle` that is invoked if an unknown option is found. During the execution of `\langle code\rangle` `\CurrentOption` contains the current option string. Additionally `\CurrentOptionValue` contains the value part if the option string is parsable as key value pair, otherwise it is `\relax`.

\CurrentOptionKey contains the key of the key value pair, or the whole option string, if it misses the equal sign.

Inside packages typical default actions are to pass unknown options to another package. Or an error message can be thrown by \unknowoptionerror. This is the original error message that L^AT_EX gives for unkown package options. This error message is easier to understand for the user as the error message from package keyval that is given otherwise.

A Class ignores unknown options and puts them on the unused option list. Let L^AT_EX do the job and just call \OptionNotUsed. Or the options can be passed to another class that is later loaded.

2.2.6 Dynamic options

Options of L^AT_EX's package/class system are cleared in \ProcessOptions. They modify the static model of a package. For example, depending on option bookmarks package hyperref loads differently.

Options, however, defined by keyval's \define@key remain defined, if the options are processed by \setkeys. Therefore these options can also be used to model the dynamic behaviour of a package. For example, in hyperref the link colors can be changed everywhere until the end in \end{document}.

However package color is necessary and it cannot be loaded after \begin{document}. Option colorlinks that loads color should be active until \begin{document} and die in some way if it is too late for loading packages. With \DisableKeyvalOption the package/class author can specify and configure the death of an option and controls the life period of the option.

2.2.7 \DisableKeyvalOption

\DisableKeyvalOption [<i>options</i>] { <i>family</i> } { <i>key</i> }	
<i>options</i> :	
action = undef, warning, error, or ignore	default: undef
global or local	default: global
package or class = <i>name</i>	

\DisableKeyvalOption can be called to mark the end when the option *key* is no longer useful. The behaviour of an option after its death can be configured by action:

undef: The option will be undefined, If it is called, \setkeys reports an error because of unknown key.

error or warning: Use of the option will cause an error or warning message. Also these actions require that exclusivly either the package or class name is given in options package or class.

ignore: The use of the option will silently be ignored.

The option's death can be limited to the end of the current group, if option local is given. Default is global.

The package/class author can wish the end of the option already during the package loading, then he will have static behaviour. In case of dynamic options \DisableKeyvalOptions can be executed everywhere, also outside the package. Therefore the family name and the package/class name is usually unknown for \DisableKeyvalOptions. Therefore the argument for the family name is mandatory and for some actions the package/class name must be provided.

Usually a macro would configure the option death, Example:

```
\ProvidesPackage{foobar}
\DeclareBoolOption{color}
```

```

\DeclareStringOption[red]{emphcolor}
\ProcessKeyvalOptions*

\newcommand*\{\foobar@DisableOption}[2]{%
  \DisableKeyValueOption[
    action={#1},
    package=foobar
  ]{foobar}{#2}%
}

\iffoobar@color
  \RequirePackage{color}
  \renewcommand*\{\emph}[1]{\textcolor{\foobar@emphcolor}{#1}}
\else
  % Option emphcolor is not wrong, if we have color support.
  % otherwise the option has no effect, but we don't want to
  % remove it. Therefore action 'ignore' is the best choice:
  \foobar@DisableOption{ignore}{emphcolor}
\fi
% No we don't need the option 'color'.
\foobar@DisableOption{warning}{color}

% With color support option 'emphcolor' will dynamically change
% the color of \emph statements.

```

2.3 Summary of internal macros

The `\Declare...Option` commands define macros, additionally to the macros generated by the key definition. These macros can be used by the package/class author. The name of the macros starts with the prefix *<prefix>* that can be configured by `\SetupKeyvalOptions`.

Declare <i><key></i>	Defined macro	Description
<code>\DeclareStringOption</code>	<code>\<prefix>\<key></code>	holds the string
<code>\DeclareBoolOption</code>	<code>\if<prefix>\<key></code> <code>\<prefix>\<key>false</code> <code>\<prefix>\<key>true</code>	boolean switch disable switch enable switch
<code>\DeclareComplementaryOption</code>	<code>\<prefix>\<key>false</code> <code>\<prefix>\<key>true</code>	enable parent switch disable parent switch
<code>\DeclareVoidOption</code>	<code>\<prefix>\<key></code>	holds the action

3 Example

The following example defined a package that serves some private color management. A boolean option `print` enables print mode without colors. An option `emph` redefines `\emph` to print in the given color. And the driver can be specified by option `driver`.

```

1 <*example>
2   % Package identification
3   % -----
4 \NeedsTeXFormat{LaTeX2e}
5 \ProvidesPackage{example-mycolorsetup}[2007/06/11 Managing my colors]
6
7 \RequirePackage{ifpdf}
8 \RequirePackage{kvoptions}
9
10  % Option declarations
11  % -----
12
13 \SetupKeyvalOptions{

```

```

14   family=MCS,
15   prefix=MCS@
16 }
17   % Use a shorter family name and prefix
18
19   % Option print
20 \DeclareBoolOption{print}
21   % is the same as
22   % \DeclareBoolOption[false]{print}
23
24   % Option driver
25 \ifpdf
26   \DeclareStringOption[pdftex]{driver}
27 \else
28   \DeclareStringOption[dvips]{driver}
29 \fi
30
31   % Alternative interface for driver options
32 \DeclareVoidOption{dvips}{\SetupDriver}
33 \DeclareVoidOption{dvipdfm}{\SetupDriver}
34 \DeclareVoidOption{pdftex}{\SetupDriver}
35   % In \SetupDriver we take the current option \CurrentOption
36   % and pass it to the driver option.
37   % The \expandafter commands expand \CurrentOption at the
38   % time, when \SetupDriver is executed and \CurrentOption
39   % has the correct meaning.
40 \newcommand*{\SetupDriver}%
41   \expandafter\@SetupDriver\expandafter{\CurrentOption}%
42 }
43 \newcommand*{\@SetupDriver}[1]%
44   \setkeys{MCS}{driver={#1}}%
45 }
46
47   % Option emph
48   % An empty value means, we want to have no color for \emph.
49   % If the user specifies option emph without value, the red is used.
50 \DeclareStringOption{emph}[red]
51   % is the same as
52   % \DeclareStringOption[]{}{emph}[red]
53
54   % Default option rule
55 \DeclareDefaultOption{%
56   \ifx\CurrentOptionValue\relax
57     \PackageWarningNoLine{\currname}{%
58       Unknown option '\CurrentOption'\MessageBreak
59       is passed to package 'color'%}
60   }%
61   % Pass the option to package color.
62   % Again it is better to expand \CurrentOption.
63   \expandafter\PassOptionsToPackage\expandafter{\CurrentOption}{color}%
64 \else
65   % Package color does not take options with values.
66   % We provide the standard LaTeX error.
67   \@unknowntoptionerror
68 \fi
69 }
70
71   % Process options
72   % -----
73 \ProcessKeyvalOptions*
74
75   % Implementation depending on option values

```

```

76      % -----
77      % Code for print mode
78 \ifMCS@print
79   \PassOptionsToPackage{monochrome}{color}
80   % tells package color to use black and white
81 \fi
82
83 \RequirePackage[\MCS@driver]{color}
84   % load package color with the correct driver
85
86   % \emph setup
87 \ifx\MCS@emph\@empty
88   % \@empty is a predefined macro with empty contents.
89   % the option value of option emph is empty, thus
90   % we do not want a redefinition of \emph.
91 \else
92   \renewcommand*\emph[1]{%
93     \textcolor{\MCS@emph}{#1}%
94   }
95 \fi
96 
```

4 Package options

The package `kvoptions` knows two package options `patch` and `debugshow`. The options of package `kvoptions` are intended for authors, not for package/class writers. Inside a package it is too late for option `patch` and `debugshow` enables some messages that are perhaps useful for the debugging phase. Also L^AT_EX is unhappy if a package is loaded later again with options that are previously not given. Thus package and class authors, stay with `\RequirePackage{kvoptions}` without options.

4.1 Option patch

L^AT_EX's system of package/class options has some severe limitations that especially affects the value part if options are used as pair of key and value.

- Spaces are removed, regardless where:

```
\documentclass[box=0 0 400 600]{article}
```

Now each package will see `box=00400600` as global option.

- In the previous case also braces would not help:

```
\documentclass[box={0 0 400 600}]{article}
```

The result is an error message:

```
! LaTeX Error: Missing \begin{document}.
```

As local option, however, it works if the package knows about key value options (By using this package, for example).

- The requirements on robustness are extremely high. L^AT_EX expands the option. All that will not work as environment name will break also as option. Even a `\relax` will generate an error message:

```
! Missing \endcsname inserted.
```

Of course, L^AT_EX does not use its protecting mechanisms. On contrary `\protect` itself will cause errors.

- The options are expanded. But perhaps the package will do that, because it has to setup some things before? Example `hyperref`:

```
\usepackage[pdfauthor=M\"uller]{hyperref}
```

Package `hyperref` does not see `M\"uller` but its expansion and it does not like it, you get many warnings

```
Token not allowed in a PDFDocEncoded string
```

And the title becomes: `Mu127uller`. Therefore such options must usually be given after package `hyperref` is loaded:

```
\usepackage{hyperref}
\hypersetup{pdfauthor=Fran\c coise M\"uller}
```

As package option it will even break with `Fran\c coise` because of the cedilla `\c c`, it is not robust enough.

For users that do not want with this limitations the package offers option `patch`. It patches L^AT_EX's option system and tries to teach it also to handle options that are given as pairs of key and value and to prevent expansion. It can already be used at the very beginning, before `\documentclass`:

```
\RequirePackage[patch]{kvoptions}
\documentclass[pdfauthor=Fran\c coise M\"uller]{article}
\usepackage{hyperref}
```

The latest time is before the package where you want to use problematic values:

```
\usepackage[patch]{kvoptions}
\usepackage[Fran\c coise M\"uller]{hyperref}
```

Some remarks:

- The patch requires ε -T_EX, its `\unexpanded` feature is much to nice. It is possible to work around using token registers. But the code becomes longer, slower, more difficult to read and maintain. The package without option `patch` works and will work without ε -T_EX.
- The code for the patch is quite long, there are many test cases. Thus the probability for bugs is probably not too small.

4.2 Option `debugshow`

The name of this option follows the convention of packages `multicol`, `tabularx`, and `tracefnt`. Currently it prints the setting of boolean options, declared by `\DeclareBoolOption` in the `.log` file, if that boolean option is used. You can activate the option by

- `\PassOptionsToPackage{debugshow}{kvoptions}`
Put this somewhere before package `kvoptions` is loaded first, e.g. before `\documentclass`.
- `\RequirePackage[debugshow]{kvoptions}`
Before `\documentclass` even an author has to use `\RequirePackage`. `\usepackage` only works after `\documentclass`.

The preferred method is `\PassOptionsToPackage`, because it does not force the package loading and does not disturb, if the package is not loaded later at all.

5 Limitations

5.1 Compatibility

5.1.1 Option `patch` vs. package `xkvltxp`

Package `xkvltxp` from the `xkeyval` project has the same goal as `kvoptions`'s option patch and patches L^AT_EX's kernel commands. Of course they cannot be used both. The user must decide, which method he prefers. Package `kvoptions` drops option patch if it detects that `xkvltxp` is already loaded.

However both *packages* can be used together, example:

```
\usepackage{xkvltxp}
\usepackage[...]{foobar} % foobar using kvoptions
```

The other way should work, too.

Package `kvoptions` tries to catch more situations and to be more robust. For example, during the comparison of options it normalizes them by removing spaces around = and the value. Thus the following is not reported as option clash:

```
\RequirePackage[patch]{kvoptions}
\documentclass{article}

\usepackage[scaled=0.7]{helvet}
\usepackage[scaled = 0.7]{helvet}

\begin{document}
\end{document}
```

5.2 Limitations

5.2.1 Option comparisons

In some situations L^AT_EX compares options, e.g. option clash check, `\@ifpackagewith`, `\@ifclasswith`. Apart from catcode and sanitizing problems of option `patch`, there is another problem. L^AT_EX does not know about the type and default values of options in key value style. Thus an option clash is reported, even if the key value has the same meaning:

```
\usepackage[scaled]{helvet} % default is .95
\usepackage[.95]{helvet}
\usepackage[0.95]{helvet}
```

5.2.2 Option list parsing with option `patch`

With option `patch` the range of possible values in key value specifications is much large, for example the comma can be used, if enclosed in curly braces.

Other packages, especially the packages that uses their own process option code can be surprised to find tokens inside options that they do not expect and errors would be the consequence. To avoid errors the options, especially the unused option list is sanitized. That means the list will only contain tokens with catcode 12 (other) and perhaps spaces (catcode 10). This allows a safe parsing for other packages. But a comma in the value part is no longer protected by curly braces because they have lost their special meaning. This is the price for compatibility.

Example:

```
\RequirePackage[patch]{kvoptions}
\documentclass[a={a,b,c},b]{article}
\begin{document}
\end{document}
```

Result:

```
LaTeX Warning: Unused global option(s):
 [a={a,c},b] .
```

6 Implementation

6.1 Preamble

Package identification.

```
97 <*package>
98 \NeedsTeXFormat{LaTeX2e}
99 \ProvidesPackage{kvoptions}
100 [2007/06/11 v2.7 Connects package keyval with LaTeX options (HO)]%
```

External resources. The package extends the support for key value pairs of package `\keyval` to package options. Thus the package needs to be loaded anyway. and we use it for `\SetupKeyvalOptions`. AFAIK this does not disturb users of `xkeyval`.

```
101 \RequirePackage{keyval}
```

Options Option `debugshow` enables additional lines of code that prints information into the `.log` file.

```
102 \begingroup
103   \edef\x{\endgroup
104   \noexpand\AtEndOfPackage{%
105     \catcode\@ne=\the\catcode\@ne\relax
106     \catcode\tw@=\the\catcode\tw@\relax
107   }%
108 }%
109 \x
110 \catcode\@ne=14 %
111 \catcode\tw@=14 %
112 \DeclareOption{debugshow}{\catcode\@ne=9 }
113 \DeclareOption{patch}{\catcode\tw@=9 }
```

Optionen auswerten:

```
114 \ProcessOptions\relax
```

6.2 Option declaration macros

6.2.1 `\SetupKeyvalOptions`

The family for the key value pairs can be setup once and is remembered later. The package name seems a reasonable default for the family key, if it is not set by the package author.

`\KVO@family` We cannot store the family setting in one macro, because the package should be usable for many other packages, too. Thus we remember the family setting in a macro, whose name contains the package name with extension, a key in L^AT_EX's class/package system.

```
115 \define@key{KVO}{family}{%
116   \expandafter\edef\csname KVO@family@\@currname.\@currext\endcsname{#1}%
117 }
118 \def\KVO@family{%
119   \@ifundefined{KVO@family@\@currname.\@currext}{%
120     \@currname
121   }{%
122     \csname KVO@family@\@currname.\@currext\endcsname
```

123 }%	
124 }	
\KVO@prefix	The value settings of options, declared by \DeclareBoolOption and \DeclareStringOption need to be saved in macros. in the first case this is a switch \if<prefix><key>, in the latter case a macro \<prefix><key>. The prefix can be configured, by prefix that is declared here. The default is the package name with @ appended.
125 \define@key{KVO}{prefix}{%	
126 \expandafter\edef\csname KVO@prefix@\@currname.\@currext\endcsname{#1}%	
127 }	
128 \def\KVO@prefix{%	
129 \@ifundefined{KVO@prefix@\@currname.\@currext}{%	
130 \@currname @%	
131 }{%	
132 \csname KVO@prefix@\@currname.\@currext\endcsname	
133 }%	
134 }	
\SetupKeyvalOptions	The argument of \SetupKeyvalOptions expects a key value list, known keys are family and prefix.
135 \newcommand*{\SetupKeyvalOptions}{%	
136 \setkeys{KVO}{%	
137 }	
6.2.2 \DeclareBoolOption	
\DeclareBoolOption	Usually options of boolean type can be given by the user without value and this means a setting to <i>true</i> . We follow this convention here. Also it simplifies the user interface.
	The switch is created and initialized with <i>false</i> . The default setting can be overwritten by the optional argument.
	LaTeX's \newif does not check for already defined macros, therefore we add this check here to prevent the user from accidentally redefining of TeX's primitives and other macros.
138 \newcommand*{\DeclareBoolOption}[2][false]{%	
139 \KVO@ifdefinable{if\KVO@prefix#2}{%	
140 \KVO@ifdefinable{\KVO@prefix#2true}{%	
141 \KVO@ifdefinable{\KVO@prefix#2false}{%	
142 \expandafter\newif\csname if\KVO@prefix#2\endcsname	
143 \@ifundefined{\KVO@prefix#2#1}{%	
144 PackageWarning{kvoptions}{%	
145 Initialization of option '#2' failed,\MessageBreak	
146 cannot set boolean option to '#1',\MessageBreak	
147 use 'true' or 'false', now using 'false'%	
148 }%	
149 }{%	
150 \csname\KVO@prefix#2#1\endcsname	
151 }%	
152 \begingroup	
153 \edef\x{\endgroup	
154 \noexpand\define@key{\KVO@family}{#2}[true]{%	
155 \noexpand\KVO@boolkey{\@currname}{%	
156 \ifx\@currext\@clsextension	
157 \noexpand\@clsextension	
158 \else	
159 \noexpand\@pkgextension	
160 \fi	
161 {\KVO@prefix}{#2}{{\#\#\#1}}%	
162 }%	
163 }%	
164 \x	

```

165      }%
166      }%
167      }%
168 }

```

`\DeclareComplementaryOption` The first argument is the key name, the second the key that must be a boolean option with the same current family and prefix. A new switch is not created for the new key, we have already a switch. Instead we define switch setting commands to work on the parent switch.

```

169 \newcommand*{\DeclareComplementaryOption}[2]{%
170   \@ifundefined{if\KVO@prefix#2}{%
171     \PackageError{koptions}{%
172       Cannot generate option code for '#1',\MessageBreak
173       parent switch '#2' does not exist}%
174   }{%
175     You are inside %
176     \ifx@\currname@\clsextension class\else package\fi\space
177     '@currname.\@currname'.\MessageBreak
178     '\KVO@family' is used as family for the keyval options.\MessageBreak
179     '\KVO@prefix' serves as prefix for internal switch macros.\MessageBreak
180     \MessageBreak
181     \gdef
182   }%
183 }{%
184   \KVO@ifdefinable{\KVO@prefix#1true}{%
185     \KVO@ifdefinable{\KVO@prefix#1false}{%
186       \expandafter\let\csname\KVO@prefix#1false\expandafter\endcsname
187         \csname\KVO@prefix#2true\endcsname
188       \expandafter\let\csname\KVO@prefix#1true\expandafter\endcsname
189         \csname\KVO@prefix#2false\endcsname

```

The same code part as in `\DeclareBoolOption` can now be used.

```

190   \begingroup
191     \edef\x{\endgroup
192       \noexpand\define@key{\KVO@family}{#1}[true]{%
193         \noexpand\KVO@boolkey{@currname}%
194         \ifx@\currname@\clsextension
195           \noexpand\@clsextension
196         \else
197           \noexpand\@pkgextension
198         \fi
199         {\KVO@prefix}{#1}{####1}%
200       }%
201     }%
202     \x
203   }%
204 }%
205 }%
206 }

```

`\KVO@ifdefinable` Generate the command token LaTeX's `\@ifdefinable` expects.

```

207 \def\KVO@ifdefinable#1{%
208   \expandafter\@ifdefinable\csname #1\endcsname
209 }

```

`\KVO@boolkey` We check explicitly for `true` and `false` to prevent the user from accidentally calling other macros.

```

#1  package/class name
#2  \@pkgextension/\@clsextension
#3  prefix
#4  key name
#5  new value

```

```

210 \def\KV0@boolkey#1#2#3#4#5{%
211   \edef\KV0@param{#5}%
212   \cnelevel@sanitize\KV0@param
213   \ifx\KV0@param\KV0@true
214     \expandafter\@firstofone
215   \else
216     \ifx\KV0@param\KV0@false
217       \expandafter\expandafter\expandafter\@firstofone
218     \else
219       \ifx#2\@clsextension
220         \expandafter\ClassWarning
221       \else
222         \expandafter\PackageWarning
223       \fi
224     {#1}{%
225       Value '\KV0@param' is not supported by\MessageBreak
226       option '#4'%
227     }%
228     \expandafter\expandafter\expandafter\@gobble
229   \fi
230 \fi
231 {%
232   ^~A\ifx#2\@clsextension
233   ^~A \expandafter\ClassInfo
234   ^~A\else
235   ^~A \expandafter\PackageInfo
236   ^~A\fi
237   ^~A{#1}{[option] #4=\KV0@param}%
238   \csname#3#4\KV0@param\endcsname
239 }%
240 }

```

\KV0@true The macros \KV0@true and \KV0@false are used for string comparisons. After \cnelevel@sanitize we have only tokens with catcode 12 (other).

```

241 \def\KV0@true{true}
242 \def\KV0@false{false}
243 \cnelevel@sanitize\KV0@true
244 \cnelevel@sanitize\KV0@false

```

6.2.3 \DeclareStringOption

\DeclareStringOption

```

245 \newcommand*\{\DeclareStringOption}[2][]{%
246   \cifnextchar[{%
247     \KV0@DeclareStringOption{#1}{#2}%
248   }{%
249     \KV0@DeclareStringOption{#1}{#2}{}[]%
250   }%
251 }

```

\KV0@DeclareStringOption

```

252 \def\KV0@DeclareStringOption#1#2#3[#4]{%
253   \KV0@ifdefinable{\KV0@prefix#2}{%
254     \cnamedef{\KV0@prefix#2}{#1}%
255     \begingroup
256       \ifx\\#3\\%
257         \toks@{}%
258       \else
259         \toks@{[#4]}%
260       \fi
261     \edef\x{\endgroup
262       \noexpand\define@key{\KV0@family}{#2}\the\toks@{%

```

```

263      ^^A\begingroup
264      ^^A \toks@{####1}%
265      ^^A \ifx\@currext\@clsextension
266      ^^A \noexpand\ClassInfo
267      ^^A \else
268      ^^A \noexpand\PackageInfo
269      ^^A \fi
270      ^^A {\@currname}\%
271      ^^A [option] #2=\{\noexpand\the\toks@\}%
272      ^^A }%
273      ^^A\endgroup
274      \noexpand\def
275      \expandafter\noexpand\csname\KV0@prefix#2\endcsname{####1}%
276      }%
277      }%
278      \x
279      }%
280 }

```

6.2.4 \DeclareVoidOption

```

\DeclareVoidOption
281 \newcommand*\{\DeclareVoidOption}[1]{%
282   \begingroup
283   \let\next\gobbletwo
284   \KV0@ifdefinable{\KV0@prefix#1}{%
285     \let\next\firstofone
286   }%
287   \expandafter\endgroup
288   \next{%
289     \begin{group}
290     \edef\x{\endgroup
291       \noexpand\define@key{\KV0@family}{#1}[\KV0@VOID@]{%
292         \noexpand\KV0@voidkey{\@currname}%
293         \ifx\@currext\@clsextension
294           \noexpand\@clsextension
295         \else
296           \noexpand\@pkgextension
297         \fi
298         {#1}%
299         ####1}%
300       \expandafter\noexpand\csname\KV0@prefix#1\endcsname
301     }%
302   }%
303   \x
304   \namedef{\KV0@prefix#1}%
305 }%
306 }
307 \def\KV0@VOID@{\VOID@}

#1 package/class name
#2 @pkgextension/@clsextension
\KV0@voidkey #3 key name
#4 default (@VOID@)
#5 macro with option code

308 \def\KV0@voidkey#1#2#3#4{%
309   \def\CurrentOption{#3}%
310   \begingroup
311   \def\x{#4}%
312   \expandafter\endgroup
313   \ifx\x\KV0@VOID@
314   \else

```

```

315      \ifx#2\@clsextension
316          \expandafter\ClassWarning
317      \else
318          \expandafter\PackageWarning
319      \fi
320      {#1}{%
321          Unexpected value for option '#3'\MessageBreak
322          is ignored%
323      }%
324  \fi
325  ^^A\ifx#2\@clsextension
326  ^^A \expandafter\ClassInfo
327  ^^A\else
328  ^^A \expandafter\PackageInfo
329  ^^A\fi
330  ^^A{#1}{[option] #3}%
331 }

```

6.2.5 \DeclareDefaultOption

```

\DeclareDefaultOption
332 \newcommand*{\DeclareDefaultOption}{%
333     \@namedef{KV0@default@\@currname.\@currext}%
334 }

```

6.3 Dynamic options

6.3.1 \DisableKeyvalOption

```

335 \SetupKeyvalOptions{%
336   family=KV0dyn,%
337   prefix=KV0dyn@%
338 }
339 \DeclareBoolOption[true]{global}
340 \DeclareComplementaryOption{local}{global}
341 \DeclareStringOption[undef]{action}
342 \let\KV0dyn@name\relax
343 \let\KV0dyn@ext\empty
344 \define@key{KV0dyn}{class}{%
345   \def\KV0dyn@name{#1}%
346   \let\KV0dyn@ext\@clsextension
347 }
348 \define@key{KV0dyn}{package}{%
349   \def\KV0dyn@name{#1}%
350   \let\KV0dyn@ext\@pkgextension
351 }
352 \newcommand*{\DisableKeyvalOption}[3][]{%
353   \begingroup
354   \setkeys{KV0dyn}{#1}%
355   \def\x{\endgroup}%
356   \@ifundefined{KV0@action@\KV0dyn@action}{%
357     \PackageError{kvoptions}{%
358       Unknown disable action %
359       '\expandafter\strip@prefix\meaning\KV0dyn@action'\MessageBreak
360       for option '#3' in keyval family '#2'%
361     }{\@ehc}%
362   }{%
363     \csname KV0@action@\KV0dyn@action\endcsname{#2}{#3}%
364   }%
365   \x
366 }
367 \def\KV0@action@undef#1#2{%

```

```

368 \edef\x{\endgroup
369   \ifKV0dyn@global\global\fi
370   \let
371   \expandafter\noexpand\csname KV@#1@#2\endcsname
372   \relax
373   \ifKV0dyn@global\global\fi
374   \let
375   \expandafter\noexpand\csname KV@#1@#2@default\endcsname
376   \relax
377 }%
378 ^^A\PackageInfo{kvoptions}{%
379   ^^^A [option] key '#2' of family '#1'\MessageBreak
380   ^^^A is disabled (undef, \ifKV0dyn@global global\else local\fi)%
381   ^^^A}%
382 }
383 \def\KV0@action@ignore#1#2{%
384   \edef\x{\endgroup
385     \ifKV0dyn@global\global\fi
386     \let
387     \expandafter\noexpand\csname KV@#1@#2\endcsname
388     \@gobble
389     \ifKV0dyn@global\global\fi
390     \let
391     \expandafter\noexpand\csname KV@#1@#2@default\endcsname
392     \@empty
393 }%
394   ^^^A\PackageInfo{kvoptions}{%
395   ^^^A [option] key '#2' of family '#1'\MessageBreak
396   ^^^A is disabled (ignore, \ifKV0dyn@global global\else local\fi)%
397   ^^^A}%
398 }
399 \def\KV0@action@error{%
400   \KV0@do@action{error}%
401 }
402 \def\KV0@action@warning{%
403   \KV0@do@action{warning}%
404 }

#1 error or warning
#2 <family>
#3 <key>

405 \def\KV0@do@action#1#2#3{%
406   \ifx\KV0dyn@name\relax
407     \PackageError{kvoptions}{%
408       Action type '#1' needs package/class name\MessageBreak
409       for key '#3' in family '#2'%
410     }\@ehc
411   \else
412     \edef\x{\endgroup
413       \noexpand\define@key{#2}{#3}[]{}{%
414         \expandafter\noexpand\csname KV0@disable@#1\endcsname
415         {\KV0dyn@name}\noexpand\KV0dyn@ext{#3}%
416       }%
417       \ifKV0dyn@global
418         \global\let
419         \expandafter\noexpand\csname KV@#2@#3\endcsname
420         \expandafter\noexpand\csname KV@#2@#3\endcsname
421         \global\let
422         \expandafter\noexpand\csname KV@#2@#3@default\endcsname
423         \expandafter\noexpand\csname KV@#2@#3@default\endcsname
424       \fi
425     }%
426   ^^^A\ifx\KV0dyn@ext\@clsextension

```

```

427      ^^A \expandafter\ClassInfo
428      ^^A\else
429      ^^A \expandafter\PackageInfo
430      ^^A\fi
431      ^^A{\KV0dyn@name}{%
432      ^^A [option] key '#3' of family '#2'\MessageBreak
433      ^^A is disabled (#1, \ifKV0dyn@global global\else local\fi)%
434      ^^A}%
435 \fi
436 }
437 \def\KV0@disable@error#1#2#3{%
438   \ifx#2\@clsextension
439     \expandafter\ClassError
440   \else
441     \expandafter\PackageError
442   \fi
443 {#1}{%
444   Option '#3' is given too late,\MessageBreak
445   now the option is ignored%
446 }\@ehc
447 }
448 \def\KV0@disable@warning#1#2#3{%
449   \ifx#2\@clsextension
450     \expandafter\ClassWarning
451   \else
452     \expandafter\PackageWarning
453   \fi
454 {#1}{%
455   Option '#3' is already consumed\MessageBreak
456   and has no effect%
457 }%
458 }

```

6.4 Process options

6.5 \ProcessKeyvalOptions

\ProcessKeyvalOptions If the optional star is given, we get the family name and expand it for safety.

```

459 \newcommand*\ProcessKeyvalOptions{%
460   \@ifstar{%
461     \begingroup
462       \edef\x{\endgroup
463         \noexpand\KV0@ProcessKeyvalOptions{\KV0@family}%
464       }%
465     \x
466   }%
467   \KV0@ProcessKeyvalOptions
468 }

469 \def\KV0@ProcessKeyvalOptions#1{%
470   \let\@tempc\relax
471   \let\KV0@temp\empty

```

Add any global options that are known to KV to the start of the list being built in \KV0@temp and mark them used (by removing them from the unused option list).

```

472   \ifx\@currext\@clsextension
473   \else
474     \ifx\@classoptionslist\relax
475     \else
476       \for\KV0@CurrentOption:=\@classoptionslist\do{%
477         \ifundefined{KV@#1@\expandafter\KV0@getkey\KV0@CurrentOption=\@nil}{%
478           }{%
479             \edef\KV0@temp{%
480 ^~B               \etex@unexpanded\expandafter{%

```

```

481           \KVO@temp
482 ^~B       }%
483           ,%
484 ^~B       \etex@unexpanded\expandafter{%
485           \KVO@CurrentOption
486 ^~B       }%
487           ,%
488       }%
489 ^~B       \@onelvel@sanitize\KVO@CurrentOption
490       \@expandtwoargs\@removeelement\KVO@CurrentOption
491           \@unusedoptionlist\@unusedoptionlist
492       }%
493       }%
494   \fi
495   \fi

```

Now stick the package options at the end of the list and wrap in a call to `\setkeys`. A class ignores unknown global options, we must remove them to prevent error messages from `\setkeys`.

```

496   \begingroup
497     \toks\tw@{}%
498     \@ifundefined{opt@\currname.\currext}{%
499       \toks@\expandafter{\KVO@temp}%
500     }{%
501       \toks@\expandafter\expandafter\expandafter{%
502         \csname opt@\currname.\currext\endcsname
503       }%
504       \ifx\currext\clsextension
505         \edef\CurrentOption{\the\toks}%
506         \toks@\expandafter{\KVO@temp}%
507         \@for\CurrentOption:=\CurrentOption\do{%
508           \ifundefined{%
509             KV@#1@\expandafter\KVO@getkey\CurrentOption=\@nil
510           }{%

```

A class puts not used options in the unused option list.

```

511 ^~B       \@onelvel@sanitize\CurrentOption
512       \ifx\@unusedoptionlist\empty
513         \global\let\@unusedoptionlist\CurrentOption
514       \else
515         \expandafter\expandafter\expandafter\gdef
516         \expandafter\expandafter\expandafter\@unusedoptionlist
517         \expandafter\expandafter\expandafter{%
518           \expandafter\@unusedoptionlist
519           \expandafter,\CurrentOption
520         }%
521       \fi
522     }{%
523       \toks@\expandafter{%
524         \the\expandafter\toks@\expandafter,\CurrentOption
525       }%
526     }%
527   }%
528   \else

```

Without default action we pass all options to `\setkeys`. Otherwise we have to check which options are known. These are passed to `\setkeys`. For the others the default action is performed.

```

529     \ifundefined{KV0@default@\currname.\currext}{%
530       \toks@\expandafter\expandafter\expandafter{%
531         \expandafter\KVO@temp\the\toks@
532       }%
533     }{%
534       \edef\CurrentOption{\the\toks}%

```

```

535      \toks@\\expandafter{\KV@temp}%
536      \\@for\\CurrentOption:=\\CurrentOption\\do{%
537          \\@ifundefined{%
538              KV@#1\\expandafter\\KV@getkey\\CurrentOption=\\nil
539          }{%
540              \\toks\\tw@\\expandafter{%
541                  \\the\\toks\\expandafter\\tw@\\expandafter,\\CurrentOption
542              }%
543          }{%
544              \\toks@\\expandafter{%
545                  \\the\\expandafter\\toks@\\expandafter,\\CurrentOption
546              }%
547          }%
548      }%
549      }%
550      \\fi
551  }%
552  \\edef\\KV@temp{\\endgroup
553      \\noexpand\\KV@calldefault{\\the\\toks\\tw@}%
554      \\noexpand\\setkeys{#1}{\\the\\toks@}%
555  }%
556  \\KV@temp
Some cleanup of \\ProcessOptions.
557  \\let\\CurrentOption@empty
558  \\AtEndOfPackage{\\let\\unprocessedoptions\\relax}%
559 }

```

6.5.1 Helper macros

`\KV@getkey` Extract the key part of a key=value pair.

```
560 \\def\\KV@getkey#1=#2\\nil{#1}
```

`\KV@calldefault`

```

561 \\def\\KV@calldefault#1{%
562     \\begingroup
563     \\def\\x{#1}%
564     \\expandafter\\endgroup
565     \\ifx\\x\\empty
566     \\else
567         \\@for\\CurrentOption:=#1\\do{%
568             \\ifx\\CurrentOption\\empty
569             \\else
570                 \\expandafter\\KV@setcurrents\\CurrentOption=\\nil
571                 \\nameuse{KV@default@\\currname.\\currext}%
572             \\fi
573         }%
574     \\fi
575 }

```

`\KV@setcurrents` Extract the key part of a key=value pair.

```

576 \\def\\KV@setcurrents#1=#2\\nil{
577     \\def\\CurrentOptionValue{#2}%
578     \\ifx\\CurrentOptionValue\\empty
579         \\let\\CurrentOptionKey\\CurrentOption
580         \\let\\CurrentOptionValue\\relax
581     \\else
582         \\edef\\CurrentOptionKey{\\zap@space#1 \\empty}%
583         \\expandafter\\KV@setcurrentvalue\\CurrentOption\\nil
584     \\fi
585 }

```

\KV@setcurrentvalue Here the value part is parsed. Package keyval's \KV@sp@def helps in removing spaces at the begin and end of the value.

```
586 \def\KV@setcurrentvalue#1=#2\@nil{%
587   \KV@sp@def\CurrentOptionValue{#2}%
588 }
```

6.6 Patch

Caution: docstrip stops at \endinput at begin of line!

```
589 ^^B\@gobble
590           \endinput
591 \PackageInfo{kvoptions}{Patching LaTeX's option system}
      Check for e-TeX.
592 \begingroup\expandafter\expandafter\expandafter\endgroup
593 \expandafter\ifx\csname eTeXversion\endcsname\relax
594   \PackageWarningNoLine{kvoptions}{%
595     Option 'patch' ignored, because e-TeX is missing%
596   }%
597   \expandafter\endinput
598 \fi
      Package etexcmds for \etex@unexpanded.
599 \RequirePackage{etexcmds}
600 \ifetex@unexpanded
601 \else
602   \PackageError{kvoptions}{%
603     Could not find eTeX's \string\unexpanded.\MessageBreak
604     Try adding \string\RequirePackage\string{etexcmds}\string{ %
605     before \string\documentclass%
606   }\@ehd
607   \expandafter\endinput
608 \fi
      Check for package xkvltxp.
609 \@ifpackageloaded{xkvltxp}{%
610   \PackageWarningNoLine{kvoptions}{%
611     Option 'patch' cannot be used together with\MessageBreak
612     package 'xkvltxp' that is already loaded.\MessageBreak
613     Therefore option 'patch' will be ignored%
614   }%
615   \endinput
616 }{}%
617 \def\@ifoptions#1#2#3{%
618   \begingroup
619     \KV@normalize\KV@temp{#3}%
620     \edef\x{\endgroup
621       \noexpand\@ifopti@ns{%
622         \detokenize\expandafter\expandafter\expandafter{%
623           \csname opt@#2.#1\endcsname
624         }%
625       }{%
626         \detokenize\expandafter{\KV@temp}%
627       }%
628     }%
629     \x
630   }%
631 \def\@pass@ptions#1#2#3{%
632   \KV@normalize\KV@temp{#2}%
633   \@undefined{opt@#3.#1}{%
634     \expandafter\gdef\csname opt@#3.#1%
635     \expandafter\endcsname\expandafter{%
```

```

636      \KVO@temp
637  }%
638 }{%
639   \expandafter\gdef\csname opt@#3.#1%
640     \expandafter\expandafter\expandafter\endcsname
641     \expandafter\expandafter\expandafter{%
642       \csname opt@#3.#1\expandafter\endcsname\expandafter,\KVO@temp
643     }%
644   }%
645 }
646 \def\ProcessOptions{%
647   \let\ds@\empty
648   \@ifundefined{opt@\currname.\currext}{%
649     \let\curroptions\empty
650   }{%
651     \expandafter\expandafter\expandafter\def
652     \expandafter\expandafter\expandafter\curroptions
653     \expandafter\expandafter\expandafter{%
654       \csname opt@\currname.\currext\endcsname
655     }%
656   }%
657   \ifstar\KVO@xprocessoptions\KVO@processoptions
658 }
659 \def\KVO@processoptions{%
660   @for\CurrentOption:=\declaredoptions\do{%
661     \ifx\CurrentOption\empty
662     \else
663       \begingroup
664         \ifx\currext\clsextension
665           \toks@{ }%
666         \else
667           \toks@\expandafter{\@classoptionslist,}%
668         \fi
669         \toks\tw@\expandafter{\curroptions}%
670         \edef\x{\endgroup
671           \noexpand\in@\{,\CurrentOption,\}{,\the\toks@,\the\toks\tw@,}%
672         }%
673       \x
674       \ifin@
675         \KVO@useoption
676         \expandafter\let\csname ds@\CurrentOption\endcsname\empty
677       \fi
678     \fi
679   }%
680   \KVO@processoptions
681 }
682 \def\KVO@xprocessoptions{%
683   \ifx\currext\clsextension
684   \else
685     @for\CurrentOption:=\@classoptionslist\do{%
686       \ifx\CurrentOption\empty
687       \else
688         \KVO@in@\CurrentOption\declaredoptions
689         \ifin@
690           \KVO@useoption
691           \expandafter\let\csname ds@\CurrentOption\endcsname\empty
692         \fi
693       \fi
694     }%
695   \fi
696   \KVO@processoptions
697 }

```

```

698 \def\KVO@in@#1#2{%
699   \in@false
700   \begingroup
701   \@for\x:=#2\do{%
702     \ifx\x#1\relax
703       \in@true
704     \fi
705   }%
706   \edef\x{\endgroup
707   \ifin@
708     \noexpand\in@true
709   \fi
710 }%
711 \x
712 }

713 \def\KVO@process@pti@ns{%
714   \@for\CurrentOption:=\@curroptions\do{%
715     \@ifundefined{ds@\KVO@SanitizedCurrentOption}{%
716       \KVO@use@option
717       \default@ds
718     }%
719     \KVO@use@option
720   }%
721   \@for\CurrentOption:=\@declaredoptions\do{%
722     \expandafter\let\csname ds@\CurrentOption\endcsname\relax
723   }%
724   \let\CurrentOption\empty
725   \let\@fileswith@pti@ns\@fileswith@pti@ns
726   \AtEndOfPackage{\let\@unprocessedoptions\relax}%
727 }

728 \def\KVO@use@option{%
729   \begingroup
730   \edef\x{\endgroup
731   \noexpand\@removeelement{%
732     \detokenize\expandafter{\CurrentOption}}%
733   }%
734   \detokenize\expandafter{\@unusedoptionlist}%
735 }%
736 }%
737 \x\@unusedoptionlist
738 \csname ds@\KVO@SanitizedCurrentOption\endcsname
739 }

740 \def\OptionNotUsed{%
741   \ifx@\currentt@clsextension
742     \xdef\@unusedoptionlist{%
743       \ifx\@unusedoptionlist\empty
744         \else
745           \detokenize\expandafter{\@unusedoptionlist,}%
746         \fi
747       \detokenize\expandafter{\CurrentOption}}%
748   }%
749 }%
750 }

Variant of \ExecuteOptions that better protects \CurrentOption.

751 \def\CurrentOption@SaveLevel{0}
752 \def\ExecuteOptions{%
753   \expandafter\KVO@ExecuteOptions
754   \csname CurrentOption@\CurrentOption@SaveLevel\endcsname
755 }
756 \def\KVO@ExecuteOptions#1#2{%
757   \let#1\CurrentOption

```

```

758 \edef\CurrentOption@SaveLevel{\the\numexpr\CurrentOption@SaveLevel+1}%
759 \for\CurrentOption:=#2\do{%
760   \csname ds@\CurrentOption\endcsname
761 }%
762 \edef\CurrentOption@SaveLevel{\the\numexpr\CurrentOption@SaveLevel-1}%
763 \let\CurrentOption#1%
764 }

765 \def\KVO@fileswith@opti@ns#1[#2]#3[#4]{%
766   \ifx#1\@clsextension
767     \ifx@\classoptionslist\relax
768       \KVO@normalize\KVO@temp{#2}%
769       \expandafter\gdef\expandafter\@classoptionslist\expandafter{%
770         \KVO@temp
771     }%
772     \def\reserved@a{%
773       \KVO@onefilewithoptions{#3}[{#2}] [{#4}]#1%
774       \documentclasshook
775     }%
776   \else
777     \def\reserved@a{%
778       \KVO@onefilewithoptions{#3}[{#2}] [{#4}]#1%
779     }%
780   \fi
781 \else
782   \begingroup
783     \let\KVO@temp\relax
784     \let\KVO@onefilewithoptions\relax
785     \let\@pkgextension\relax
786     \def\reserved@b##1{%
787       \ifx@\nil##1\relax
788     \else
789       \ifx\relax##1\relax
790     \else
791       \KVO@onefilewithoptions{##1}[{\KVO@temp}] [{#4}]\@pkgextension
792     \fi
793     \expandafter\reserved@b
794     \fi
795   }%
796   \edef\reserved@a{\zap@space#3 \empty}%
797   \edef\reserved@a{\expandafter\reserved@b\reserved@a,\@nil,}%
798   \toks@{#2}%
799   \def\KVO@temp{\the\toks@}%
800   \edef\reserved@a{\endgroup \reserved@a}%
801 \fi
802 \reserved@a
803 }

804 \def\KVO@onefilewithoptions#1[#2]#3[#4]{%
805   \pushfilename
806   \xdef\currname{#1}%
807   \global\let\currext#4%
808   \expandafter\let\csname\currname.\@currext-h@k\endcsname\empty
809   \let\CurrentOption\empty
810   \reset@ptions
811   \makeatletter
812   \def\reserved@a{%
813     \@ifl@aded\currext{#1}{%
814       \@if@ptions\currext{#1}{#2}{%
815     }{%
816       \begingroup
817         \@ifundefined{opt@#1.\currext}{%
818           \def\x{}%
819         }{%

```

```

820     \edef\x{%
821         \expandafter\expandafter\expandafter\strip@prefix
822         \expandafter\meaning\csname opt@#1.\@currext\endcsname
823     }%
824 }%
825 \def\y{#2}%
826 \edef\y{\expandafter\strip@prefix\meaning\y}%
827 \@latex@error{Option clash for \@cls@pkg\space #1}{%
828     The package #1 has already been loaded %
829     with options:\MessageBreak
830     \space\space[\x]\MessageBreak
831     There has now been an attempt to load it %
832     with options\MessageBreak
833     \space\space[\y]\MessageBreak
834     Adding the global options:\MessageBreak
835     \space\space
836         \x,\y\MessageBreak
837     to your \noexpand\documentclass declaration may fix this.%\MessageBreak
838     Try typing \space <return> \space to proceed.%\MessageBreak
839 }%
840     \endgroup
841 }%
842 }{%
843     \@pass@ptions\@currext{#2}{#1}%
844     \global\expandafter
845     \let\csname ver@\@currname.\@currext\endcsname\@empty
846     \InputIfFileExists
847         {\@currname.\@currext}%
848         {}%
849         {\@missingfileerror\@currname\@currext}%
850     \let\@unprocessedoptions\@unprocessedoptions
851     \csname\@currname.\@currext-h@k\endcsname
852     \expandafter\let\csname\@currname.\@currext-h@k\endcsname
853         \undefined
854     \@unprocessedoptions
855 }%
856 \@ifl@ter\@currext{#1}{#3}{%
857 }{%
858     \@latex@warning@no@line{%
859         You have requested,\on@line, %
860         version\MessageBreak
861         #3' of \@cls@pkg\space #1,\MessageBreak
862         but only version\MessageBreak
863         '\csname ver@#1.\@currext\endcsname'\MessageBreak
864         is available%
865     }%
866 }%
867 }%
868 \ifx\@currext\@clsextension\let\LoadClass\@two@loadclass@error\fi
869 \@popfilename
870 \@reset@ptions
871 }%
872 \reserved@a
873 }%
874 \def\@unknownoptionerror{%
875     \@latex@error{%
876         Unknown option '\KVO@SanitizedCurrentOption' %
877         for \@cls@pkg\space`\@currname'%
878     }{%
879         The option '\KVO@SanitizedCurrentOption' was not declared in %
880         \@cls@pkg\space`\@currname', perhaps you\MessageBreak
881         misspelled its name. %

```

```

882     Try typing \space <return> %
883     \space to proceed.%
884 }%
885 }

886 \def\@@unprocessedoptions{%
887   \ifx\@currext\@pkgextension
888     \@ifundefined{opt@\@currname.\@currext}{%
889       \let\@curroptions\@empty
890     }{%
891       \expandafter\let\expandafter\@curroptions
892         \csname opt@\@currname.\@currext\endcsname
893     }%
894   \@for\CurrentOption:=\@curroptions\do{%
895     \ifx\CurrentOption\@empty\else\@unknownoptionerror\fi
896   }%
897 }%
898 }

899 \def\KVO@SanitizedCurrentOption{%
900   \expandafter\strip@prefix\meaning\CurrentOption
901 }

```

Normalize option list.

```

902 \def\KVO@normalize#1#2{%
903   \let\KVO@result\@empty
904   \KVO@splitcomma#2,\@nil
905   \let#1\KVO@result
906 }
907 \def\KVO@splitcomma#1,#2\@nil{%
908   \KVO@ifempty{#1}{}{%
909     \KVO@checkkv#1=\@nil
910   }%
911   \KVO@ifempty{#2}{}{\KVO@splitcomma#2\@nil}%
912 }
913 \def\KVO@ifempty#1{%
914   \expandafter\ifx\expandafter\\\detokenize{#1}\\\%
915   \expandafter\@firstoftwo
916   \else
917   \expandafter\@secondoftwo
918 }%
919 }
920 \def\KVO@checkkv#1=#2\@nil{%
921   \KVO@ifempty{#2}{}{%
922     % option without value
923     \edef\KVO@x{\zap@space#1 \@empty}%
924     \ifx\KVO@x\@empty
925       % ignore empty option
926     \else
927       % append to list
928     \edef\KVO@result{%
929       \etex@unexpanded\expandafter{\KVO@result},\KVO@x
930     }%
931   }%
932 }{%
933   % #1: "key", #2: "value="
934   % add key part
935   \edef\KVO@result{%
936     \etex@unexpanded\expandafter{\KVO@result},%
937     \zap@space#1 \@empty
938   }%
939   \futurelet\@let@token\KVO@checkfirsttok#2 \@nil| = \@nil|\KVO@nil
940 }%
941 }

```

```

942 \def\KV@checkfirsttok{%
943   \ifx\@let@token\bgroup
944     % no space at start
945     \expandafter\KV@removelastspace\expandafter=%
946     % "<value><spaceopt>= \@nil"
947   \else
948     \expandafter\KV@checkfirstA
949   \fi
950 }
951 \def\KV@checkfirstA#1 #2\@nil{%
952   \KV@isempty{#2}{%
953     \KV@removelastspace=#1 \@nil
954   }{%
955     \KV@isempty{#1}{%
956       \KV@removelastspace=#2\@nil
957     }{%
958       \KV@removelastspace=#1 #2\@nil
959     }%
960   }%
961 }
962 \def\KV@removelastspace#1 = \@nil|#2\KV@nil{%
963   \KV@isempty{#2}{%
964     \edef\KV@result{%
965       \etex@unexpanded\expandafter{\KV@result}%
966       \etex@unexpanded\expandafter{\KV@removegarbage#1\KV@nil}%
967     }%
968   }{%
969     \edef\KV@result{%
970       \etex@unexpanded\expandafter{\KV@result}%
971       \etex@unexpanded{#1}%
972     }%
973   }%
974 }
975 \def\KV@removegarbage#1= \@nil#2\KV@nil{#1}%

```

Arguments #1 and #2 are macros.

```

976 \def\KV@removeelement#1#2{%
977   \begingroup
978   \toks@={}
979   \@for\x:=#2\do{%
980     \ifx\x\empty
981     \else
982       \ifx\x#1\relax
983       \else
984         \edef\t{\the\toks@}%
985         \ifx\t\empty
986         \else
987           \toks@\expandafter{\the\toks@,}%
988         \fi
989         \toks@\expandafter{\the\expandafter\toks@\x}%
990       \fi
991     \fi
992   }%
993   \edef\x{\endgroup
994   \def\noexpand#2{\the\toks@}%
995   }%
996   \x
997 }

998 \let\@files@with@pti@ns\KV@files@with@pti@ns
999 \ifx\@files@with@pti@ns\@badrequireerror
1000 \else
1001   \let\@files@with@pti@ns\KV@files@with@pti@ns
1002 \fi

```

7 Installation

7.1 Download

Package. This package is available on CTAN¹:

<CTAN:macros/latex/contrib/oberdiek/kvoptions.dtx> The source file.

<CTAN:macros/latex/contrib/oberdiek/kvoptions.pdf> Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

<CTAN:macros/latex/contrib/oberdiek/oberdiek-tds.zip>

TDS refers to the standard “A Directory Structure for TeX Files” (<CTAN:tds/tds.pdf>). Directories with `texmf` in their name are usually organized this way.

7.2 Bundle installation

Unpacking. Unpack the `oberdiek-tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek-tds.zip -d ~/texmf
```

Script installation. Check the directory `TDSScripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

7.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain-TeX:

```
tex kvoptions.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>kvoptions.sty</code>	→ <code>tex/latex/oberdiek/kvoptions.sty</code>
<code>kvoptions.pdf</code>	→ <code>doc/latex/oberdiek/kvoptions.pdf</code>
<code>example-mycolorsetup.sty</code>	→ <code>doc/latex/oberdiek/example-mycolorsetup.sty</code>
<code>kvoptions.dtx</code>	→ <code>source/latex/oberdiek/kvoptions.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

7.4 Refresh file name databases

If your TeX distribution (teTeX, mikTeX, ...) relies on file name databases, you must refresh these. For example, teTeX users run `texhash` or `mktexlsr`.

¹<ftp://ftp.ctan.org/tex-archive/>

7.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk kvoptions.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain-TeX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{kvoptions.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex kvoptions.dtx
makeindex -s gind.ist kvoptions.idx
pdflatex kvoptions.dtx
makeindex -s gind.ist kvoptions.idx
pdflatex kvoptions.dtx
```

8 References

- [1] Package `ifthen`, David Carlisle, 2001/05/26.[CTAN:macros/latex/base/ifthen.dtx](#)
- [2] Package `helvet`, Sebastian Rahtz, Walter Schmidt, 2004/01/26.[CTAN:macros/latex/required/psnfss/psfonts.dtx](#)
- [3] Package `hyperref`, Sebastian Rahtz, Heiko Oberdiek, 2006/02/12.[CTAN:macros/latex/contrib/hyperref/](#)
- [4] Package `keyval`, David Carlisle, 1999/03/16.[CTAN:macros/latex/required/graphics/keyval.dtx](#)
- [5] Package `multicol`, Frank Mittelbach, 2004/02/14.[CTAN:macros/latex/required/tools/multicol.dtx](#)
- [6] Package `tabularx`, David Carlisle, 1999/01/07.[CTAN:macros/latex/required/tools/tabularx.dtx](#)
- [7] Package `tracefn`, Frank Mittelbach, Rainer Schöpf, 1997/05/29.[CTAN:macros/latex/base/ltfssstrc.dtx](#)
- [8] Package `xkeyval`, Hendri Adriaens, 2005/05/07.[CTAN:macros/latex/contrib/xkeyval/](#)
- [9] The L^AT_EX3 Project, *L^AT_EX2_E for class and package writers*, 2003/12/09.
[CTAN:macros/latex/doc/clsguide.pdf](#)

9 History

[0000/00/00 v0.0]

- Probably David Carlisle's code in `hyperref` was the start.

[2004/02/22 v1.0]

- The first version was never published. It also has offered a patch to get rid of L^AT_EX's option expansion.

[2006/02/16 v2.0]

- Now the package is redesigned with an easier user interface.
- `\ProcessKeyvalOptions` remains the central service, inherited from `hyperref`'s `\ProcessOptionsWithKV`. Now the use inside classes is also supported.
- Provides help macros for boolean and simple string options.
- Fixes for the patch of L^AT_EX. The patch is only enabled, if the user requests it.

[2006/02/20 v2.1]

- Unused option list is sanitized to prevent problems with other packages that uses own processing methods for key value options. Disadvantage: the unused global option detection is weakened.
- New option type by `\DeclareVoidOption` for options without value.
- Default rule by `\DeclareDefaultOption`.
- Dynamic options: `\DisableKeyvalOption`.

[2006/06/01 v2.2]

- Fixes for option patch.

[2006/08/17 v2.3]

- `\DeclareBooleanOption` renamed to `\DeclareBoolOption` to avoid a name clash with package `\ifoption`.

[2006/08/22 v2.4]

- Option patch: `\ExecuteOptions` does not change meaning of `\CurrentOption` at all.

[2007/04/11 v2.5]

- Line ends sanitized.

[2007/05/06 v2.6]

- Uses package `etexcmds`.

[2007/06/11 v2.7]

- The patch part fixes LaTeX bug latex/3965.

10 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\@files with @pti@ns	725, 998
\@unprocessedoptions	851, 886
\@SetupDriver	41, 43
\@badrequireerror	999
\@classoptionslist	474, 476, 667, 685, 767, 769
\@cls@pkg	827, 862, 877, 880
\@clsextension	156, 157, 176, 194, 195, 219, 232, 265, 293, 294, 315, 325, 346, 426, 438, 449, 472, 504, 664, 683, 741, 766, 868
\@curr ext	116, 119, 122, 126, 129, 132, 156, 176, 177, 194, 265, 293, 333, 472, 498, 502, 504, 529, 571, 648, 654, 664, 683, 741, 807, 808, 813, 814, 817, 822, 844, 846, 848, 850, 852, 853, 857, 864, 868, 887, 888, 892
\@currname	57, 116, 119, 120, 122, 126, 129, 130, 132, 155, 177, 193, 270, 292, 333, 498, 502, 529, 571, 648, 654, 806, 808, 846, 848, 850, 852, 853, 877, 880, 888, 892
\@curroptions	649, 652, 669, 714, 889, 891, 894
\@declaredoptions	660, 688, 721
\@documentclasshook	774
\@ehc	181, 361, 410, 446
\@ehd	606
\@empty	87, 88, 343, 392, 471, 512, 557, 565, 568, 578, 582, 647, 649, 661, 676, 686, 691, 724, 743, 796, 808, 809, 846, 889, 895, 903, 923, 924, 937, 980, 985
\@expandtwoargs	490
\@files with @pti@ns	725, 999, 1001
\@firstofone	214, 217, 285
\@firstoftwo	915
\@for	476, 507, 536, 567, 660, 685, 701, 714, 721, 759, 894, 979
\@gobble	228, 388, 589
\@gobbletwo	283
\@if@pti@ns	621
\@if@ptions	617, 814
\@ifdefinable	208
\@ifl@aded	813
\@ifl@ter	857
\@ifnextchar	246
\@ifpackageloaded	609
\@ifstar	460, 657
\@ifundefined	119, 129, 143, 170, 356, 477, 498, 508, 529, 537, 633, 648, 715, 817, 888
\@latex@error	827, 875
\@latex@warning@no@line	859
\@let@token	939, 943
\@missingfileerror	850
\@namedef	254, 304, 333
\@nameuse	571
\@ne	105, 110, 112
\@nil	477, 509, 538, 560, 570, 576, 583, 586, 787, 797, 904, 907, 909, 911, 920, 939, 946, 951, 953, 956, 958, 962, 975
\@onel level@sanitize	212, 243, 244, 489, 511
\@pass@ptions	631, 844
\@pk gextension	159, 197, 296, 350, 785, 791, 887
\@popfilename	869
\@pushfilename	805
\@removeelement	490, 731
\@reset@ptions	810, 870
\@secondoftwo	917
\@tempc	470
\@twoloadclasserror	868
\@undefined	854
\@unknownoptionerror	67, 874, 895
\@unprocessedoptions	558, 726, 851, 855
\@unusedoptionlist	491, 512, 513, 516, 518, 734, 737, 742, 743, 745
\\"	256, 914
A	
\AtEndOfPackage	104, 558, 726
C	
\catcode	105, 106, 110, 111, 112, 113
\ClassError	439
\ClassInfo	233, 266, 326, 427
\ClassWarning	220, 316, 450
\csname	116, 122, 126, 132, 142, 150, 186, 187, 188, 189, 208, 238, 275, 300, 363, 371, 375, 387, 391, 414, 419, 420, 422, 423, 502, 593, 623, 634, 639, 642, 654, 676, 691, 722, 738, 754, 760, 808, 822, 846, 852, 853, 864, 892
\CurrentOption	35, 37, 38, 41, 58, 62, 63, 309, 505, 507, 509, 511, 513, 519, 524, 534, 536, 538, 541, 545, 557, 567, 568, 570, 579, 583, 660, 661, 671, 676, 685, 686, 688, 691, 714, 721, 722, 724, 732, 747, 757, 759, 760, 763, 809, 894, 895, 900
\CurrentOption@SaveLevel	751, 754, 758, 762
\CurrentOptionKey	579, 582

\CurrentOptionValue	K
..... 56, 577, 578, 580, 587	\KV@sp@def 587
D	\KV@setcurrentvalue 586
\DeclareBoolOption . 4, 20, 22, 138, 339	\KV@action@error 399
\DeclareComplementaryOption	\KV@action@ignore 383
..... 5, 169, 340	\KV@action@undef 367
\DeclareDefaultOption 5, 55, 332	\KV@action@warning 402
\DeclareOption 112, 113	\KV@boolkey 155, 193, 210
\DeclareStringOption	\KV@calldefault 553, 561
..... 4, 26, 28, 50, 52, 245, 341	\KV@checkfirstA 948, 951
\DeclareVoidOption .. 5, 32, 33, 34, 281	\KV@checkfirsttok 939, 942
\default@ds	\KV@checkkv 909, 920
\define@key	\KV@CurrentOption 476, 477, 485, 489, 490
..... 115, 125,	\KV@DeclareStringOption 247, 249, 252
154, 192, 262, 291, 344, 348, 413	\KV@disable@error 437
\detokenize	\KV@disable@warning 448
..... 622, 626, 732, 734, 745, 747, 914	\KV@do@action 400, 403, 405
\DisableKeyvalOption	\KV@ExecuteOptions 753, 756
\do 476, 507, 536, 567, 660,	\KV@false 216, 241
685, 701, 714, 721, 759, 894, 979	\KV@family 115, 154, 178, 192, 262, 291, 463
\documentclass	\KV@fileswith@pti@ns . 765, 998, 1001
\ds@	\KV@getkey 477, 509, 538, 560
E	\KV@ifdefinable 139,
\emph	140, 141, 184, 185, 207, 253, 284
\endcsname	\KV@ifempty 908, 911, 913, 921, 952, 955, 963
..... 116,	\KV@in@ 688, 698
122, 126, 132, 142, 150, 186,	\KV@nil 939, 962, 966, 975
187, 188, 189, 208, 238, 275,	\KV@normalize 619, 632, 768, 902
300, 363, 371, 375, 387, 391,	\KV@onefilewithoptions 773, 778, 784, 791, 804
414, 419, 420, 422, 423, 502,	\KV@param 211, 212, 213, 216, 225, 237, 238
593, 623, 635, 640, 642, 654,	\KV@prefix 125, 139, 140, 141,
676, 691, 722, 738, 754, 760,	142, 143, 150, 161, 170, 179,
808, 822, 846, 852, 853, 864, 892	184, 185, 186, 187, 188, 189,
\endinput	199, 253, 254, 275, 284, 300, 304
\etex@unexpanded	\KV@process@pti@ns 680, 696, 713
..... 480,	\KV@process@ptions 657, 659
484, 929, 936, 965, 966, 970, 971	\KV@ProcessKeyvalOptions 463, 467, 469
\ExecuteOptions	\KV@removeelement 976
F	\KV@removegarbage 966, 975
\futurelet	\KV@removelastspace 945, 953, 956, 958, 962
G	\KV@result 903, 905, 928,
\gdef	929, 935, 936, 964, 965, 969, 970
I	\KV@SanitizedCurrentOption
\ifetex@unexpanded 715, 738, 876, 879, 899
..... 600	\KV@setcurrents 570, 576
\ifin@	\KV@setcurrentvalue 583, 586
..... 674, 689, 707	\KV@splitcomma 904, 907, 911
\ifKV0dyn@global	\KV@temp 471, 479, 481, 499, 506, 531,
..... 369,	535, 552, 556, 619, 626, 632,
373, 380, 385, 389, 396, 417, 433	636, 642, 768, 770, 783, 791, 799
\ifMCS@print	\KV@true 213, 241
..... 78	\KV@use@option 675, 690, 716, 719, 728
\ifpdf	\KV@VOID@ 291, 307, 313
..... 25	\KV@voidkey 292, 308
\ifx	\KV@x 923, 924, 929
..... 56, 87, 156, 176, 194,	
213, 216, 219, 232, 256, 265,	
293, 313, 315, 325, 406, 426,	
438, 449, 472, 474, 504, 512,	
565, 568, 578, 593, 661, 664,	
683, 686, 702, 741, 743, 766,	
767, 787, 789, 868, 887, 895,	
914, 924, 943, 980, 982, 985, 999	
\in@	
..... 671	
\in@false	
..... 699	
\in@true	
..... 703, 708	
\InputIfFileExists	
..... 847	

\KV@xprocess@ptions	657, 682	\RequirePackage	7, 8, 83, 101, 599, 604
\KV@dyn@action	356, 359, 363	\reserved@a	772, 777, 796, 797, 800, 802, 812, 872
\KV@dyn@ext	343, 346, 350, 415, 426	\reserved@b	786, 793, 797
\KV@dyn@name	342, 345, 349, 406, 415, 431		
L			
\LoadClass	868	\setkeys	44, 136, 354, 554
M			
\makeatletter	811	\SetupDriver	32, 33, 34, 35, 38, 40
\MCS@driver	83	\SetupKeyvalOptions	3, 13, 135, 335
\MCS@emph	87, 93	\space	176, 827, 830, 833, 835, 839, 862, 877, 880, 882, 883
\meaning	359, 822, 826, 900	\strip@prefix	359, 821, 826, 900
\MessageBreak	58,		
	145, 146, 172, 177, 178, 179, 180, 225, 321, 359, 379, 395, 408, 432, 444, 455, 603, 611, 612, 829, 830, 832, 833, 834, 836, 838, 861, 862, 863, 864, 880		
N			
\NeedsTeXFormat	4, 98	\t	984, 985
\newcommand	40, 43, 135, 138, 169, 245, 281, 332, 352, 459	\textcolor	93
\newif	142	\the	105, 106, 262, 271, 505, 524, 531, 534, 541, 545, 553, 554, 671, 758, 762, 799, 984, 987, 989, 994
\next	283, 285, 288	\toks	497, 540, 541, 553, 669, 671
\numexpr	758, 762	\toks@	257, 259, 262, 264, 271, 499, 501, 505, 506, 523, 524, 530, 531, 534, 535, 544, 545, 554, 665, 667, 671, 798, 799, 978, 984, 987, 989, 994
		\tw@	106, 111, 113, 497, 540, 541, 553, 669, 671
O			
\on@line	860	\unexpanded	603
\OptionNotUsed	740		
P			
\PackageError	171, 357, 407, 441, 602	\x	103, 109, 153, 164, 191, 202, 261, 278, 290, 303, 311, 313, 355, 365, 368, 384, 412, 462, 465, 563, 565, 620, 629, 670, 673, 701, 702, 706, 711, 730, 737, 818, 820, 830, 836, 979, 980, 982, 989, 993, 996
\PackageInfo 235, 268, 328, 378, 394, 429, 591		
\PackageWarning	144, 222, 318, 452		
\PackageWarningNoLine	57, 594, 610		
\PassOptionsToPackage	63, 79		
\ProcessKeyvalOptions	3, 73, 459		
\ProcessOptions	114, 646		
\ProvidesPackage	5, 99		
R			
\renewcommand	92	\y	825, 826, 833, 836
S			
T			
U			
X			
Y			
Z			