

The `kvsetkeys` package

Heiko Oberdiek

<oberdiek@uni-freiburg.de>

2007/09/29 v1.3

Abstract

Package `kvsetkeys` provides `\kvsetkeys`, a variant of package `keyval`'s `\setkeys`. It allows to specify a handler that deals with unknown options. Active commas and equal signs may be used (e.g. see `babel`'s shorthands) and only one level of curly braces is removed from the values.

Contents

1 Documentation	2
1.1 Motivation	2
1.2 Normalizing key value lists	2
1.3 Parsing key value lists	3
1.4 Processing key value pairs	3
1.5 Default family handler	4
1.6 Put it all together	4
1.7 Comma separated lists	4
2 Example	5
3 Implementation	5
3.1 Identification	5
3.2 Package loading	7
3.3 Check for ε - <code>TeX</code>	7
3.4 Generic help macros	8
3.5 Normalizing	8
3.6 Parsing key value lists	11
3.7 Parsing comma lists	11
3.8 Processing key value pairs	12
3.9 Error handling	13
3.10 Do it all	13
4 Test	13
4.1 Catcode checks for loading	13
4.2 Macro tests	14
4.2.1 Preamble	14
4.2.2 Time	15
4.2.3 Test sets	15
5 Installation	18
5.1 Download	18
5.2 Bundle installation	19
5.3 Package installation	19
5.4 Refresh file name databases	19
5.5 Some details for the interested	19

6	References	20
7	History	20
	[2006/03/06 v1.0]	20
	[2006/10/19 v1.1]	20
	[2007/09/09 v1.2]	20
	[2007/09/29 v1.3]	20
8	Index	20

1 Documentation

1.1 Motivation

\kvsetkeys serves as replacement for keyval's \setkeys. It basically uses the same syntax. But the implementation is more robust and predictable:

Active syntax characters: Comma ',' and the equals sign '=' are used inside key value lists as syntax characters. Package keyval uses the catcode of the characters that is active during package loading, usually this is catcode 12 (other). But it can happen that the catcode setting of the syntax characters changes. Especially active characters are of interest, because some language adaptations uses them. For example, option turkish of package babel uses the equals sign as active shorthand character. Therefore package kvsetkeys deals with both catcode settings 12 (other) and 13 (active).

Brace removal: Package keyval's \setkeys removes up to two levels of curly braces around the value in some unpredictable way:

```
\setkeys{fam}{key={{value}}} → value
\setkeys{fam}{key={{value}}}} → {value}
\setkeys{fam}{key= {{value}}}} → {{value}}
```

This package kvsetkeys follows a much stronger rule: Exactly one level of braces are removed from an item, if the item is surrounded by curly braces. An item can be a the key value pair, the key or the value.

```
\kvsetkeys{fam}{key={value}} → value
\kvsetkeys{fam}{key={{value}}} → {value}
\kvsetkeys{fam}{key= {{value}}}} → {{value}}
```

Arbitrary values: Unmatched conditionals are supported.

Before I describe \kvsetkeys in more detail, first I want to explain, how this package deals with key value lists. For the package also provides low level interfaces that can be used by package authors.

1.2 Normalizing key value lists

```
\kv@normalize {(key value list)}
```

If the user specifies key value lists, he usually prefers nice formatted source code, e.g.:

```
\hypersetup{
  pdftitle    = {...},
  pdfsubject  = {...},
  pdfauthor   = {...},
  pdfkeywords = {...},
  ...
}
```

Thus there can be spaces around keys, around = or around the value. Also empty entries are possible by too many commas. Therefore these spaces and empty entries are silently removed by package `keyval` and this package. Whereas the contents of the value can be protected by curly braces, especially if spaces or commas are used inside, a key name must not use spaces or other syntax characters.

`\kv@normalize` takes a key value list and performs the cleanup:

- Spaces are removed.
- Syntax characters (comma and equal sign) that are active are replaced by the same characters with standard catcode. (Example: `babel`'s language option `turkish` uses the equal sign as active shorthand character.)

The result is stored in `\kv@list`, e.g.:

```
\kv@list → ,pdftitle={...},pdfsubject={...},...,
```

Curly braces around values (or keys) remain untouched.

v1.3+: One comma is added in front of the list and each pair ends with a comma. Thus an empty list consists of one comma, otherwise two commas encloses the list. Empty entries other than the first are removed.

v1.0 – v1.2: Empty entries are removed later. In fact it adds a comma at the begin and end to protect the last value and an easier implementation.

1.3 Parsing key value lists

```
\kv@parse {⟨key value list⟩} {⟨processor⟩}
```

It is easier to parse a normalized list, thus `\kv@parse` normalizes the list and calls `\kv@parse@normalized`.

```
\kv@parse@normalized {⟨key value list⟩} {⟨processor⟩}
```

Now the key value list is split into single key value pairs. For further processing the key and value are given as arguments for the `⟨processor⟩`:

```
⟨processor⟩ {⟨key⟩} {⟨value⟩}
```

Also key and value are stored in macro names:

- `\kv@key` stores the key.
- `\kv@value` stores the value or if the value was not specified it has the meaning `\relax`.

The behaviour in pseudo code:

```
foreach (⟨key⟩, ⟨value⟩) in (⟨key value list⟩)
  \kv@key := ⟨key⟩
  \kv@value := ⟨value⟩
  ⟨processor⟩ {⟨key⟩} {⟨value⟩}
```

1.4 Processing key value pairs

```
\kv@processor@default {⟨family⟩} {⟨key⟩} {⟨value⟩}
```

There are many possibilities to process key value pairs. `\kv@processor@default` is the processor used in `\kvsetkeys`. It reimplements and extends the behaviour of `keyval`'s `\setkeys`. In case of unknown keys `\setkeys` raise an error. This processor, however, calls a handler instead, if it is provided by the family.

The behaviour in pseudo code:

```

if <key> exists
    call the keyval code of <key>
else
    if <handler> for <family> exists
        <handler> {<key>} {<value>}
    else
        raise unknown key error
    fi
fi

```

1.5 Default family handler

\kv@processor@default calls *<handler>*, the default handler for the family, if the key does not exist in the family. The handler is called with two arguments, the key and the value. It can be defined with \kv@set@family@handler:

```
\kv@set@family@handler {<family>} {<handler definition>}
```

This sets the default family handler for the keyval family *<family>*. Inside *<handler definition>* #1 stands for the key and #2 is the value. Also \kv@key and \kv@value can be used for the key and the value. If the value is not given, \kv@value has the meaning \relax.

1.6 Put it all together

```
\kvsetkeys {<family>} {<key value list>}
```

The work is done by the previous commands. \kvsetkeys just calls them:

```
\kv@parse {<key value list>} {\kv@processor@default {<family>}}
```

Thus you can replace \setkeys of package keyval by the key value parser of this package:

```
\renewcommand*{\setkeys}{\kvsetkeys}
or
\let\setkeys\kvsetkeys
```

1.7 Comma separated lists

Since version 2007/09/29 v1.3 this package also supports the normalizing and parsing of general comma separated lists.

```
\comma@normalize {<comma list>}
```

Macro \comma@normalize normalizes the comma separated list, removes spaces around commas. The result is put in macro \comma@list.

```
\comma@parse {<comma list>} {<processor>}
```

Macro \comma@parse first normalizes the comma separated list and then parses the list by calling \comma@parse@normalized.

```
\comma@parse@normalized {<normalized comma list>} {<processor>}
```

The list is parsed. Empty entries are ignored. *<processor>* is called for each non-empty entry with the entry as argument:

```
<processor>{<entry>}
```

Also the entry is stored in the macro `\comma@entry`.

2 Example

The following example prints a short piece of HTML code using the tabbing environment for indenting purpose and a key value syntax for specifying the attributes of an HTML tag. The example illustrates the use of a default family handler.

```
1 <*example>
2 \documentclass{article}
3 \usepackage[T1]{fontenc}
4 \usepackage{kvsetkeys}
5 \usepackage{keyval}
6
7 \makeatletter
8 \newcommand*{\tag}[2][]{\%
9   % #1: attributes
10  % #2: tag name
11  \begingroup
12  \toks@={}
13  \let\endslash\empty
14  \kvsetkeys{tag}{#1}%
15  \texttt{%
16    \textless #2\the\toks@\endslash\textgreater
17  }%
18 \endgroup
19 }
20 \kv@set@family@handler{tag}{%
21  % #1: key
22  % #2: value
23  \toks@\expandafter{%
24    \the\toks@
25    \space
26    #1=\string"#2\string"%
27  }%
28 }
29 \define@key{tag}{/}{}{%
30  \def\endslash{/}%
31 }
32 \makeatother
33
34 \begin{document}
35 \begin{tabbing}
36   \mbox{}\qquad\=\qquad\=\kill
37   \tag{html} \\
38   \>\dots\\
39   \>\tag[border=1]{table}\\
40   \>\>\tag[width=200, span=3, ]{colgroup}\\
41   \>\>\dots\\
42   \>\tag{/table}\\
43   \>\dots\\
44   \tag{/html}\\
45 \end{tabbing}
46 \end{document}
47 </example>
```

3 Implementation

3.1 Identification

```

48 <*package>
Reload check, especially if the package is not used with LATEX.
49 \begingroup
50   \catcode44 12 % ,
51   \catcode45 12 % -
52   \catcode46 12 % .
53   \catcode58 12 % :
54   \catcode64 11 % @
55   \expandafter\let\expandafter\x\csname ver@kvsetkeys.sty\endcsname
56   \ifcase 0%
57     \ifx\x\relax % plain
58     \else
59       \ifx\x\empty % LaTeX
60       \else
61         1%
62       \fi
63     \fi
64   \else
65     \catcode35 6 % #
66     \catcode123 1 % {
67     \catcode125 2 % }
68   \expandafter\ifx\x\csname PackageInfo\endcsname\relax
69     \def\x#1#2{%
70       \immediate\write-1{Package #1 Info: #2.}%
71     }%
72   \else
73     \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
74   \fi
75   \x{kvsetkeys}{The package is already loaded}%
76   \endgroup
77   \expandafter\endinput
78 \fi
79 \endgroup
Package identification:
80 \begingroup
81   \catcode35 6 % #
82   \catcode40 12 % (
83   \catcode41 12 % )
84   \catcode44 12 % ,
85   \catcode45 12 % -
86   \catcode46 12 % .
87   \catcode47 12 % /
88   \catcode58 12 % :
89   \catcode64 11 % @
90   \catcode123 1 % {
91   \catcode125 2 % }
92   \expandafter\ifx\x\csname ProvidesPackage\endcsname\relax
93     \def\x#1#2#3[#4]{\endgroup
94       \immediate\write-1{Package: #3 #4}%
95       \xdef#1{#4}%
96     }%
97   \else
98     \def\x#1#2[#3]{\endgroup
99       #2[{#3}]%
100      \ifx#1\relax
101        \xdef#1{#3}%
102      \fi
103    }%
104  \fi
105 \expandafter\x\csname ver@kvsetkeys.sty\endcsname
106 \ProvidesPackage{kvsetkeys}%
107 [2007/09/29 v1.3 Key value parser with default handler support (HO)]
```

```

108 \begingroup
109   \catcode123 1 % {
110   \catcode125 2 % }
111   \def\x{\endgroup
112     \expandafter\edef\csname KVS@AtEnd\endcsname{%
113       \catcode35 \the\catcode35\relax
114       \catcode64 \the\catcode64\relax
115       \catcode123 \the\catcode123\relax
116       \catcode125 \the\catcode125\relax
117     }%
118   }%
119 \x
120 \catcode35 6 % #
121 \catcode64 11 % @
122 \catcode123 1 % {
123 \catcode125 2 % }
124 \def\TMP@EnsureCode#1#2{%
125   \edef\KVS@AtEnd{%
126     \KVS@AtEnd
127     \catcode#1 \the\catcode#1\relax
128   }%
129   \catcode#1 #2\relax
130 }%
131 \TMP@EnsureCode{36}{3}%
132 \TMP@EnsureCode{38}{4}%
133 \TMP@EnsureCode{39}{12}%
134 \TMP@EnsureCode{44}{12}%
135 \TMP@EnsureCode{46}{12}%
136 \TMP@EnsureCode{47}{12}%
137 \TMP@EnsureCode{61}{12}%
138 \TMP@EnsureCode{94}{7}%
139 \TMP@EnsureCode{96}{12}%
140 \TMP@EnsureCode{126}{13}%

```

3.2 Package loading

```

141 \begingroup\expandafter\expandafter\expandafter\endgroup
142 \expandafter\ifx\csname RequirePackage\endcsname\relax
143   \input infwarerr.sty\relax
144   \input etexcmds.sty\relax
145 \else
146   \RequirePackage{infwarerr}[2007/09/09]%
147   \RequirePackage{etexcmds}[2007/09/09]%
148 \fi

```

3.3 Check for ε -**TeX**

`\unexpanded`, `\ifcsname`, and `\unless` are used if found.

```

149 \begingroup\expandafter\endgroup
150 \ifcase0\ifetex@\unexpanded
151   \expandafter\ifx\csname ifcsname\endcsname\relax
152   \else
153     \expandafter\ifx\csname unless\endcsname\relax
154     \else
155       1%
156     \fi
157   \fi
158 \fi
159 \catcode`\$=9 % ignore
160 \catcode`\&=14 % comment
161 \else % e-TeX
162 \catcode`\$=14 % comment
163 \catcode`\&=9 % ignore
164 \fi

```

3.4 Generic help macros

```
\KVS@Empty
165 \def\KVS@Empty{}

\KVS@FirstOfTwo
166 \long\def\KVS@FirstOfTwo#1#2{#1}

\KVS@SecondOfTwo
167 \long\def\KVS@SecondOfTwo#1#2{#2}

\KVS@IfEmpty
168 \def\KVS@IfEmpty#1{%
169 & \edef\KVS@Temp{\etex@unexpanded{#1}}%
170 $ \begingroup
171 $ \toks@{#1}%
172 $ \edef\KVS@Temp{\the\toks@}%
173 $ \expandafter\endgroup
174 \ifx\KVS@Temp\KVS@Empty
175 \expandafter\KVS@FirstOfTwo
176 \else
177 \expandafter\KVS@SecondOfTwo
178 \fi
179 }
```

3.5 Normalizing

```
\kv@normalize
180 \def\kv@normalize#1{%
181 \begingroup
182 \toks@{,#1,}%
183 \KVS@Comma
184 \KVS@SpaceComma{ }%
185 \KVS@CommaSpace
186 \KVS@CommaComma
187 \KVS@Equals
188 \KVS@SpaceEquals{ }%
189 \KVS@EqualsSpace{ }%
190 \xdef\KVS@Global{\the\toks@}%
191 \endgroup
192 \let\kv@list\KVS@Global
193 }

\comma@normalize
194 \def\comma@normalize#1{%
195 \begingroup
196 \toks@{,#1,}%
197 \KVS@Comma
198 \KVS@SpaceComma{ }%
199 \KVS@CommaSpace
200 \KVS@CommaComma
201 \xdef\KVS@Global{\the\toks@}%
202 \endgroup
203 \let\comma@list\KVS@Global
204 }
```

\KVS@Comma Converts active commas into comma with catcode other. Also adds a comma at the end to protect the last value for next cleanup steps.

```
205 \begingroup
206 \lccode``,`=\`,%
207 \lccode`~=\`,%
```

```

208 \lowercase{\endgroup
209   \def\KVS@Comma{%
210     \toks@\expandafter{\expandafter}\expandafter
211     \KVS@@Comma\the\toks@\~\KVS@Nil
212   }%
213   \def\KVS@@Comma#1~#2\KVS@Nil{%
214     \toks@\expandafter{\the\toks@#1}%
215     \KVS@IfEmpty{#2}{%
216       }{%
217         \KVS@@Comma,#2\KVS@Nil
218       }%
219     }%
220   }%

```

\KVS@SpaceComma Removes spaces before the comma, may add commas at the end.

```

221 \def\KVS@SpaceComma#1{%
222   \toks@\expandafter{\the\toks@#1,}%
223   \expandafter\KVS@@SpaceComma\the\toks@\KVS@Nil
224 }

```

\KVS@@SpaceComma

```

225 \def\KVS@@SpaceComma#1 ,#2\KVS@Nil{%
226   \KVS@IfEmpty{#2}{%
227     \toks@{#1}%
228   }{%
229     \toks@{#1,#2}%
230     \expandafter\KVS@@SpaceComma\the\toks@\KVS@Nil
231   }%
232 }

```

\KVS@CommaSpace Removes spaces after the comma, may add commas at the end.

```

233 \def\KVS@CommaSpace{%
234   \toks@\expandafter{\the\toks@, }%
235   \expandafter\KVS@@CommaSpace\the\toks@\KVS@Nil
236 }

```

\KVS@@CommaSpace

```

237 \def\KVS@@CommaSpace#1, #2\KVS@Nil{%
238   \KVS@IfEmpty{#2}{%
239     \toks@{#1}%
240   }{%
241     \toks@{#1,#2}%
242     \expandafter\KVS@@CommaSpace\the\toks@\KVS@Nil
243   }%
244 }

```

\KVS@CommaComma Replaces multiple commas by one comma.

```

245 \def\KVS@CommaComma{%
246   \toks@\expandafter{\the\toks@,}%
247   \expandafter\KVS@@CommaComma\the\toks@\KVS@Nil
248 }

```

\KVS@@CommaComma

```

249 \def\KVS@@CommaComma#1,,#2\KVS@Nil{%
250   \toks@{#1,#2}%
251   \KVS@IfEmpty{#2}{%
252     }{%
253       \expandafter\KVS@@CommaComma\the\toks@\KVS@Nil
254     }%
255 }

```

\KVS@Equals Converts active equals signs into catcode other characters.

```
256 \begingroup
257   \lccode`\==`\=%
258   \lccode`\~=`\=%
259 \lowercase{\endgroup
260   \def\KVS@Equals{%
261     \toks@\expandafter{\expandafter}\expandafter
262     \KVS@@Equals\the\toks@\~\KVS@Nil
263   }%
264   \def\KVS@Equals#1#2\KVS@Nil{%
265     \edef\KVS@Temp{\the\toks@}%
266     \ifx\KVS@Temp\KVS@Empty
267       \expandafter\KVS@FirstOfTwo
268     \else
269       \expandafter\KVS@SecondOfTwo
270     \fi
271   }%
272   \toks@{\#1}%
273 }{%
274   \toks@\expandafter{\the\toks@=\#1}%
275 }%
276 \KVS@IfEmpty{\#2}{%
277 }{%
278   \KVS@@Equals#2\KVS@Nil
279 }%
280 }%
281 }
```

\KVS@SpaceEquals Removes spaces before the equals sign.

```
282 \def\KVS@SpaceEquals#1{%
283   \toks@\expandafter{\the\toks@#1=}%
284   \expandafter\KVS@@SpaceEquals\the\toks@\KVS@Nil
285 }
```

\KVS@@SpaceEquals

```
286 \def\KVS@@SpaceEquals#1 =#2\KVS@Nil{%
287   \KVS@IfEmpty{\#2}{%
288     \toks@{\#1}%
289   }{%
290     \toks@{\#1=\#2}%
291     \expandafter\KVS@@SpaceEquals\the\toks@\KVS@Nil
292   }%
293 }
```

\KVS@EqualsSpace Removes spaces after the equals sign.

```
294 \def\KVS@EqualsSpace{%
295   \toks@\expandafter{\the\toks@= }%
296   \expandafter\KVS@@EqualsSpace\the\toks@\KVS@Nil
297 }
```

\KVS@@EqualsSpace

```
298 \def\KVS@@EqualsSpace#1= #2\KVS@Nil{%
299   \KVS@IfEmpty{\#2}{%
300     \toks@{\#1}%
301   }{%
302     \toks@{\#1=\#2}%
303     \expandafter\KVS@@EqualsSpace\the\toks@\KVS@Nil
304   }%
305 }
```

3.6 Parsing key value lists

```
\kv@parse Normalizes and parses the key value list. Also sets \kv@list.  
306 \def\kv@parse#1{  
307   \kv@normalize{#1}  
308   \expandafter\kv@parse@normalized\expandafter{\kv@list}  
309 }  
  
\kv@parse@normalized #1: key value list  
#2: processor  
310 \def\kv@parse@normalized#1#2{  
311   \KVS@Parse#1,\KVS@Nil{#2}  
312 }  
  
\KVS@Parse #1,#2: key value list  
#3: processor  
313 \def\KVS@Parse#1,#2\KVS@Nil#3{  
314   \KVS@IfEmpty{#1}{  
315     }{  
316       \KVS@Process#1=\KVS@Nil{#3}  
317     }  
318   \KVS@IfEmpty{#2}{  
319     }{  
320       \KVS@Parse#2\KVS@Nil{#3}  
321     }  
322 }  
  
\KVS@Process #1: key  
#2: value, =  
#3: processor  
323 \def\KVS@Process#1=#2\KVS@Nil#3{  
324   \def\kv@key{#1}  
325   \KVS@IfEmpty{#2}{  
326     \let\kv@value\relax  
327     #3{#1}{  
328   }{  
329     \KVS@@Process{#1}#2\KVS@Nil{#3}  
330   }  
331 }  
  
\KVS@@Process #1: key  
#2: value  
#3: processor  
332 \def\KVS@@Process#1#2=\KVS@Nil#3{  
333 & \edef\kv@value{\etex@unexpanded{#2}}  
334 $ \begingroup  
335 $ \toks@{#2}  
336 $ \xdef\KVS@Global{\the\toks@}  
337 $ \endgroup  
338 $ \let\kv@value\KVS@Global  
339 #3{#1}{#2}  
340 }
```

3.7 Parsing comma lists

```
\comma@parse Normalizes and parses the key value list. Also sets \comma@list.  
341 \def\comma@parse#1{  
342   \comma@normalize{#1}  
343   \expandafter\comma@parse@normalized\expandafter{\comma@list}  
344 }
```

```

\comma@parse@normalized #1: comma list
#2: processor
345 \def\comma@parse@normalized#1#2{%
346   \KVS@CommaParse#1,\KVS@Nil{#2}%
347 }

\KVS@CommaParse #1,#2: comma list
#3: processor
348 \def\KVS@CommaParse#1,#2\KVS@Nil#3{%
349   \KVS@IfEmpty{#1}{%
350     }{%
351       \def\comma@entry{#1}{%
352         #3{#1}{%
353       }%
354       \KVS@IfEmpty{#2}{%
355         }{%
356           \KVS@CommaParse#2\KVS@Nil{#3}{%
357         }%
358       }%
}

```

3.8 Processing key value pairs

```

\kv@processor@default
359 \def\kv@processor@default#1#2#3{%
360 & \unless\ifcsname KV@#1@#2\endcsname
361 $ \begingroup\expandafter\expandafter\expandafter\endgroup
362 $ \expandafter\ifx\csname KV@#1@#2\endcsname\relax
363 & \unless\ifcsname KVS@#1@handler\endcsname
364 $ \begingroup\expandafter\expandafter\expandafter\endgroup
365 $ \expandafter\ifx\csname KVS@#1@handler\endcsname\relax
366   \kv@error@unknownkey{#1}{#2}%
367   \else
368     \csname KVS@#1@handler\endcsname{#2}{#3}%
369     \relax
370   \fi
371 \else
372   \ifx\kv@value\relax
373 & \unless\ifcsname KV@#1@#2@default\endcsname
374 $ \begingroup\expandafter\expandafter\expandafter\endgroup
375 $ \expandafter\ifx\csname KV@#1@#2@default\endcsname\relax
376   \kv@error@novalue{#1}{#2}%
377   \else
378     \csname KV@#1@#2@default\endcsname
379     \relax
380   \fi
381 \else
382   \csname KV@#1@#2\endcsname{#3}%
383   \fi
384 \fi
385 }

\kv@set@family@handler
386 \def\kv@set@family@handler#1{%
387   \KVS@SetFamilyHandler{#1}\@nil
388 }

\KVS@SetFamilyHandler
389 \def\KVS@SetFamilyHandler#1\@nil#{%
390   \expandafter\def\csname KVS@#1@handler\endcsname##1##2{%
391 }
```

3.9 Error handling

```
\kv@error@novalue
392 \def\kv@error@novalue{%
393   \kv@error@generic{No value specified for}%
394 }

\kv@error@unknownkey
395 \def\kv@error@unknownkey{%
396   \kv@error@generic{Undefined}%
397 }

\kv@error@generic
398 \def\kv@error@generic#1#2#3{%
399   \@PackageError{kvsetkeys}{%
400     #1 key '#3'%
401   }{%
402     The keyval family of the key '#3' is '#2'.\MessageBreak
403     \MessageBreak
404     \@ehc
405   }%
406 }
```

3.10 Do it all

```
\kvsetkeys
407 \def\kvsetkeys#1#2{%
408   \kv@parse{#2}{\kv@processor@default{#1}}%
409 }

410 \KVS@AtEnd
411 </package>
```

4 Test

4.1 Catcode checks for loading

```
412 <*test1>
413 \catcode`{=1 %
414 \catcode`}=2 %
415 \catcode`\#=6 %
416 \catcode`\@=11 %
417 \expandafter\ifx\csname count@\endcsname\relax
418   \countdef\count@=255 %
419 \fi
420 \expandafter\ifx\csname @gobble\endcsname\relax
421   \long\def\@gobble#1{}%
422 \fi
423 \expandafter\ifx\csname @firstofone\endcsname\relax
424   \long\def\@firstofone#1{}%
425 \fi
426 \expandafter\ifx\csname loop\endcsname\relax
427   \expandafter\@firstofone
428 \else
429   \expandafter\@gobble
430 \fi
431 {%
432   \def\loop#1\repeat{%
433     \def\body{#1}%
434     \iterate
435   }%
```

```

436  \def\iterate{%
437    \body
438    \let\next\iterate
439    \else
440      \let\next\relax
441    \fi
442    \next
443  }%
444  \let\repeat=\fi
445 }%
446 \def\RestoreCatcodes{}%
447 \count@=0 %
448 \loop
449   \edef\RestoreCatcodes{%
450     \RestoreCatcodes
451     \catcode`\the\count@=\the\catcode\count@\relax
452   }%
453 \ifnum\count@<255 %
454   \advance\count@ 1 %
455 \repeat
456
457 \def\RangeCatcodeInvalid#1#2{%
458   \count@=#1\relax
459   \loop
460     \catcode\count@=15 %
461   \ifnum\count@<#2\relax
462     \advance\count@ 1 %
463   \repeat
464 }
465 \def\Test{%
466   \RangeCatcodeInvalid{0}{47}%
467   \RangeCatcodeInvalid{58}{64}%
468   \RangeCatcodeInvalid{91}{96}%
469   \RangeCatcodeInvalid{123}{255}%
470   \catcode`\\=12 %
471   \catcode`\\=0 %
472   \catcode`{=1 %
473   \catcode`}=2 %
474   \catcode`#=6 %
475   \catcode`[=12 %
476   \catcode`]=12 %
477   \catcode`%=14 %
478   \catcode` =10 %
479   \catcode`13=5 %
480   \input kvsetkeys.sty\relax
481   \RestoreCatcodes
482 }
483 \Test
484 \csname @@end\endcsname
485 \end
486 </test1>

```

4.2 Macro tests

4.2.1 Preamble

```

487 <*test2>
488 \NeedsTeXFormat{LaTeX2e}
489 \nofiles
490 \documentclass{article}
491 <noetex>\let\SavedUnexpanded\unexpanded
492 <noetex>\let\unexpanded\UNDEFINED
493 \makeatletter

```

```

494 \chardef\KVS@TestMode=1 %
495 \makeatother
496 \usepackage{kvsetkeys}[2007/09/29]
497 <noetex>\let\unexpanded\SavedUnexpanded
498 \usepackage{qstest}
499 \IncludeTests{*}
500 \LogTests{log}{*}{*}

```

4.2.2 Time

```

501 \begingroup\expandafter\expandafter\expandafter\endgroup
502 \expandafter\ifx\csname pdfresettimer\endcsname\relax
503 \else
504   \makeatletter
505   \newcount\SummaryTime
506   \newcount\TestTime
507   \SummaryTime=\z@
508   \newcommand*\PrintTime[2]{%
509     \typeout{%
510       [Time #1: \strip@pt\dimexpr\number#2sp\relax\space s]%
511     }%
512   }%
513   \newcommand*\StartTime[1]{%
514     \renewcommand*\TimeDescription{#1}%
515     \pdfresettimer
516   }%
517   \newcommand*\TimeDescription{}%
518   \newcommand*\StopTime{}%
519   \TestTime=\pdfelapsedtime
520   \global\advance\SummaryTime\TestTime
521   \PrintTime\TimeDescription\TestTime
522 }%
523 \let\saved@qstest\qstest
524 \let\saved@endqstest\endqstest
525 \def\qstest#1#2{%
526   \saved@qstest{#1}{#2}%
527   \StartTime{#1}%
528 }%
529 \def\endqstest{%
530   \StopTime
531   \saved@endqstest
532 }%
533 \AtEndDocument{%
534   \PrintTime{summary}\SummaryTime
535 }%
536 \makeatother
537 \fi

```

4.2.3 Test sets

```

538 \makeatletter
539 \def\@makeactive#1{%
540   \catcode`#1=13\relax
541 }
542 \@makeactive\,
543 \def,{\errmessage{COMMA}}
544 \@makeother\,
545 \@makeactive\=
546 \def={\errmessage{EQUALS}}
547 \@makeother\=
548
549 \begin{qstest}{normalize}{normalize,active-chars,space-removal}%
550 \def\Test#1#2{%
551   \@makeother\,%
552   \@makeother\=%

```

```

553      \scantokens{\toks@={#2}}%
554      \edef\Result{\the\toks@}%
555      \makeother\,%
556      \makeother\=%
557      \CTest{#1}%
558      \makeactive\,%
559      \CTest{#1}%
560      \makeactive\=%
561      \CTest{#1}%
562      \makeother\,%
563      \CTest{#1}%
564      \makeother\=%
565  }%
566  \def\CTest#1{%
567    \scantokens{\kv@normalize{#1}}%
568    \expandafter\expandafter\expandafter\Expect
569    \expandafter\expandafter\expandafter
570    {\expandafter\kv@list\expandafter}\expandafter{\Result}%
571    \Expect*{\ifx\kv@list\Result true\else false\fi}{true}%
572  }%
573  \Test{}{},%
574  \Test{},{}{},%
575  \Test{},{}{},%
576  \Test{},{}{},{}%
577  \Test{,}{}{},%
578  \Test{{a}}{},{}a,}%
579  \Test{{a}}{},{}a,}%
580  \Test{{a}},{}{},{}a,}%
581  \Test{{a},{}b}{}{},{}a,{}b,}%
582  \Test{{b}}={c},{}=,{}=,{}d}={}b}={c},{}=,{}=,{}d}=,}%
583  \Test{{}}{},{}},}%
584  \Test{{},{}},{}},{}},{}},}%
585  \Test{=},{}=,}%,{}=,{}=,}%
586  \Test{=,{}=,}%,{}=,{}=,}%
587  \def\TestSet#1{%
588    \Test{#1#1}{}%
589    \Test{#1#1,#1#1}{}%
590    \Test{#1#1,#1#1,#1#1}{}%
591    \Test{#1#1#1#1}{}%
592    \Test{{a}}#1#1=#1#1{b}{}{},{}a}={b},}%
593  }%
594  \TestSet{}%
595  \begingroup
596    \let\saved@normalize\kv@normalize
597    \def\kv@normalize#1{%
598      \saved@normalize{#1}%
599      \onelevel@sanitize\kv@list
600      \onelevel@sanitize\Result
601    }%
602    \Test{#,{}=,{}=,{}=,{}=,{}=,{}=,{}=,{}=,{}=,{}=,}%
603  \endgroup
604  \begingroup
605    \def\Test#1#2{%
606      \edef\Result{#2}%
607      \CTest{#1}%
608    }%
609    \Test{{ a = b }}{},{} a = b ,}%
610    \makeactive\,%
611    \Test{{}}{\string,{\noexpand,\}\string,}%
612    \makeother\,%
613    \makeactive\=%
614    \Test{a={}}{},{}a\string={\noexpand=} ,}%

```

```

615  \endgroup
616  \Test{a=b}{,a=b,}%
617  \Test{a={b}}{,a={b},}%
618  \Test{a = {b}}{,a={b},}%
619  \Test{a= {b}}{,a={b},}%
620  \Test{a = {b}}{,a={b},}%
621  \Test{a = {b} ,}{,a={b},}%
622  \Test{a}{,a,}%
623  \Test{ a}{,a,}%
624  \Test{a }{,a,}%
625  \Test{ a }{,a,}%
626  \Test{, a ,}{,a,}%
627  \Test{, a b ,}{,a b,}%
628  \Test{,a ,}{,a,}%
629  \Test{ a =}{,a=,}%
630  \Test{ a = }{,a=,}%
631  \Test{a =}{,a=,}%
632  \Test{{a} =}{,{a}=,}%
633  \Test{{a}= {}}{,{a}={},}%
634  \Test{, a = {}}{,a={},}%
635  \Test{a,,b}{,a,b,}%
636  \Test{a=\fi}{,a=\fi,}%
637  \Test{a=\iffalse}{,a=\iffalse,}%
638  \Test{a=\iffalse,b=\fi}{,a=\iffalse,b=\fi,}%
639 \end{qstest}
640
641 \begin{qstest}{parse}{parse,brace-removal}
642   \def\Processor#1#2{%
643     \expandafter\Expect\expandafter{\kv@key}{#1}%
644     \toks@{#2}%
645     \edef\x{\the\toks@}%
646     \ifx\kv@value\relax
647       \Expect*{\the\toks@}{}%
648       \def\Value{<>}%
649     \else
650       \edef\Value{[\the\toks@]}%
651       \onelevel@sanitize\Value
652     \fi
653     \toks@{#1}%
654     \ifx\Result\empty
655       \edef\Result{[\the\toks@]=\Value}%
656     \else
657       \edef\Result{\Result,[\the\toks@]=\Value}%
658     \fi
659     \onelevel@sanitize\Result
660   }%
661   \def\Test#1#2{%
662     \let\Result\empty
663     \kv@parse{#1}\Processor
664     \Expect*{\Result}{#2}%
665   }%
666   \Test{}{}%
667   \Test{}{}%
668   \Test{{}}{[]=<>}%
669   \Test{{{}}}{[{}]=<>}%
670   \Test{a}{[a]=<>}%
671   \Test{{a}}{[a]=<>}%
672   \Test{{a}}{[a]=<>}%
673   \Test{{{a}}}{[a]=<>}%
674   \Test{{{a}}}{[[a]]=<>}%
675   \Test{a=}{[a]=[]}%
676   \Test{{a}=}{[a]=[]}%

```

```

77 \Test{{[a]}={[a]}=[[]]}%
678 \Test{a={} {[a]}=[[]]}%
679 \Test{{[a]}={{} }} {[a]}=[{} ]}%
680 \Test{a=b {[a]}=[b]}%
681 \Test{a=\fi {[a]}=[\fi]}%
682 \Test{a=\iffalse {[a]}=[\iffalse]}%
683 \Test{a=\iffalse , b=\fi {[a]}=[\iffalse] , [b]=[ \fi]}%
684 \Test{{ a = b } {[ a ]=[ b ]}}%
685 \Test{{ a = b } {[ a = b ]=<>}}%
686 \end{qstest}
687
688 \begin{qstest}{comma}{comma,parse}
689 \def\Processor#1{%
690     \expandafter\Expect\expandafter{\comma@entry}{#1}%
691     \toks0{#1}%
692     \ifx\Result\empty
693         \edef\Result{[\the\toks0]}%
694     \else
695         \edef\Result{\Result,[\the\toks0]}%
696     \fi
697     \onelevel@sanitize\Result
698 }%
699 \def\Test#1#2{%
700     \let\Result\empty
701     \comma@parse{#1}\Processor
702     \Expect*\{\Result\}{#2}%
703 }%
704 \tracingmacros=1
705 \Test{}{}%
706 \Test{{}}{}%
707 \Test{{{} }}{{{} }}%
708 \Test{a {[a]}}%
709 \Test{{a}} {[a]}%
710 \Test{{a}} {[ [a] ]}%
711 \Test{a {[a=]}}%
712 \Test{a\fi {[a\fi]}}%
713 \Test{a\iffalse {[a\iffalse]}}%
714 \Test{\iffalse , \fi {[ \iffalse , [ \fi ] ]}%
715 \Test{ a , b , c {[a],[b],[c]}}%
716 \Test{ { } , { } , { } , { } , { } {[ [ ] , [ ] , [ ] , [ ] , [ ] ]}%
717 \Test{ {{}} , {{}} , {{}} , {{}} , {{}} {[ {{}} , [ {{}} , [ {{}} , [ {{}} , [ {{}} ] ]}%
718 \end{qstest}
719
720 \begin{document}
721 \end{document}
722 //test2

```

5 Installation

5.1 Download

Package. This package is available on CTAN¹:

CTAN:macros/latex/contrib/oberdiek/kvsetkeys.dtx The source file.

CTAN:/macros/latex/contrib/oberdiek/kvsetkeys.pdf Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

CTAN:macros/latex/contrib/oberdiek/oberdiek-tds.zip

¹ <ftp://ftp.ctan.org/tex-archive/>

TDS refers to the standard “A Directory Structure for \TeX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

5.2 Bundle installation

Unpacking. Unpack the `oberdiek-tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek-tds.zip -d ~/texmf
```

Script installation. Check the directory `TDSScripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

5.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain- \TeX :

```
tex kvsetkeys.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>kvsetkeys.sty</code>	→ <code>tex/generic/oberdiek/kvsetkeys.sty</code>
<code>kvsetkeys.pdf</code>	→ <code>doc/latex/oberdiek/kvsetkeys.pdf</code>
<code>kvsetkeys-example.tex</code>	→ <code>doc/latex/oberdiek/kvsetkeys-example.tex</code>
<code>test/kvsetkeys-test1.tex</code>	→ <code>doc/latex/oberdiek/test/kvsetkeys-test1.tex</code>
<code>test/kvsetkeys-test2.tex</code>	→ <code>doc/latex/oberdiek/test/kvsetkeys-test2.tex</code>
<code>test/kvsetkeys-test3.tex</code>	→ <code>doc/latex/oberdiek/test/kvsetkeys-test3.tex</code>
<code>kvsetkeys.dtx</code>	→ <code>source/latex/oberdiek/kvsetkeys.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

5.4 Refresh file name databases

If your \TeX distribution (te \TeX , mik \TeX , ...) relies on file name databases, you must refresh these. For example, te \TeX users run `texhash` or `mktexlsr`.

5.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk kvsetkeys.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain- \TeX : Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{kvsetkeys.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the .dtx or the .drv to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfLATEX:

```
pdflatex kvsetkeys.dtx  
makeindex -s gind.ist kvsetkeys.idx  
pdflatex kvsetkeys.dtx  
makeindex -s gind.ist kvsetkeys.idx  
pdflatex kvsetkeys.dtx
```

6 References

- [1] David Carlisle: *The keyval package*; 1999/03/16 v1.13; CTAN:macros/latex/required/graphics/keyval.dtx.

7 History

[2006/03/06 v1.0]

- First version.

[2006/10/19 v1.1]

- Fix of \kv@set@family@handler.
 - Example added.

[2007/09/09 v1.2]

- Using package `infwarerr` for error messages.
 - Catcode section rewritten.

[2007/09/29 v1.3]

- Normalizing and parsing of comma separated lists added.
 - `\kv@normalize` rewritten.
 - Robustness increased for normalizing and parsing, e.g. for values with unmatched conditionals.
 - ε - \TeX is used if available.
 - Tests added for normalizing and parsing.

8 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	\%	477	
\#	415, 474	\&	160, 163
\\$	159, 162	\,	206, 207, 542,

\=	36, 257, 258, 545, 547, 552, 556, 560, 564, 613	\documentclass	2, 490
\>	38, 39, 40, 41, 42, 43	\dots	38, 41, 43
\@	416, 470	E	
\@PackageError	399	\empty	59
\@Test	557, 559, 561, 563, 566, 607	\end	45, 46, 485, 639, 686, 718, 721
\@ehc	404	\endcsname	55, 68, 92, 105, 112, 142, 151, 153, 360, 362, 363, 365, 368, 373, 375, 378, 382, 390, 417, 420, 423, 426, 484, 502
\@empty	13, 654, 662, 692, 700	\endinput	77
\@endslash	13, 16, 30	\endqstest	524, 529
\@firstofone	424, 427	\errmessage	543, 546
\@gobble	421, 429	\etex@unexpanded	169, 333
\@makeactive	539, 542, 545, 558, 560, 610, 613	\Expect	568, 571, 643, 647, 664, 690, 702
\@makeother	544, 547, 551, 552, 555, 556, 562, 564, 612		
\@nil	387, 389	I	
\@onellevel@sanitize	599, 600, 651, 659, 697	\ifcase	56, 150
\[475	\ifcsname	360, 363, 373
\\"	37, 38, 39, 40, 41, 42, 43, 44, 471	\ifetex@unexpanded	150
\{	413, 472	\iffalse	637, 638, 682, 683, 713, 714
\}	414, 473	\ifnum	453, 461
\]	476	\ifx	57, 59, 68, 92, 100, 142, 151, 153, 174, 266, 362, 365, 372, 375, 417, 420, 423, 426, 502, 571, 646, 654, 692
\~	207, 258	\immediate	70, 94
\□	478	\IncludeTests	499
A		\input	143, 144, 480
\advance	454, 462, 520	\iterate	434, 436, 438
\AtEndDocument	533		
B		K	
\begin	34, 35, 549, 641, 688, 720	\kill	36
\body	433, 437	\kv@error@generic	393, 396, 398
C		\kv@error@novalue	376, 392
\catcode	50, 51, 52, 53, 54, 65, 66, 67, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 109, 110, 113, 114, 115, 116, 120, 121, 122, 123, 127, 129, 159, 160, 162, 163, 413, 414, 415, 416, 451, 460, 470, 471, 472, 473, 474, 475, 476, 477, 478, 479, 540	\kv@error@unknownkey	366, 395
\chardef	494	\kv@key	324, 643
\comma@entry	351, 690	\kv@list	192, 308, 570, 571, 599
\comma@list	203, 343	\kv@normalize	2, 180, 307, 567, 596, 597
\comma@normalize	4, 194, 342	\kv@parse	3, 306, 408, 663
\comma@parse	4, 341, 701	\kv@parse@normalized	3, 308, 310
\comma@parse@normalized	4, 343, 345	\kv@processor@default	3, 359, 408
\count@	418, 447, 451, 453, 454, 458, 460, 461, 462	\kv@set@family@handler	4, 20, 386
\countdef	418	\kv@value	326, 333, 338, 372, 646
\csname	55, 68, 92, 105, 112, 142, 151, 153, 362, 365, 368, 375, 378, 382, 390, 417, 420, 423, 426, 484, 502	\KVS@Comma	211, 213, 217
D		\KVS@CommaComma	247, 249
\define@key	29	\KVS@CommaSpace	235, 237
\dimexpr	510	\KVS@Equals	262, 264, 278
		\KVS@EqualsSpace	296, 298
		\KVS@Process	329, 332
		\KVS@SpaceComma	223, 225
		\KVS@SpaceEquals	284, 286
		\KVS@AtEnd	125, 126, 410
		\KVS@Comma	183, 197, 205
		\KVS@CommaComma	186, 200, 245
		\KVS@CommaParse	346, 348
		\KVS@CommaSpace	185, 199, 233
		\KVS@Empty	165, 174, 266
		\KVS@Equals	187, 256
		\KVS@EqualsSpace	189, 294
		\KVS@FirstOfTwo	166, 175, 267
		\KVS@Global	190, 192, 201, 203, 336, 338

\KVS@IfEmpty	596, 598
.	168, 215, 226, 238, 251, 276,
287, 299, 314, 318, 325, 349, 354	
\KVS@Nil	523, 526
211, 213, 217, 223, 225, 230,	491, 497
235, 237, 242, 247, 249, 253,	553, 567
262, 264, 278, 284, 286, 291,	25, 510
296, 298, 303, 311, 313, 316,	513, 527
320, 323, 329, 332, 346, 348, 356	518, 530
\KVS@Parse	510
\KVS@Process	510
\KVS@SecondOfTwo	510
\KVS@SetFamilyHandler	510
\KVS@SpaceComma	510
\KVS@SpaceEquals	510
\KVS@Temp	510
\KVS@TestMode	510
\kvsetkeys	510
L	
\lccode	206, 207, 257, 258
\LogTests	500
\loop	432, 448, 459
\lowercase	208, 259
M	
\makeatletter	7, 493, 504, 538
\makeatother	32, 495, 536
\mbox	36
\MessageBreak	402, 403
N	
\NeedsTeXFormat	488
\newcommand	8, 508, 513, 517, 518
\newcount	505, 506
\next	438, 440, 442
\nofiles	489
\number	510
P	
\PackageInfo	73
\pdfelapsedtime	519
\pdfresettimer	515
\PrintTime	508, 521, 534
\Processor	642, 663, 689, 701
\ProvidesPackage	106
Q	
\qquad	36
\qtest	523, 525
R	
\RangeCatcodeInvalid	492
.	457, 466, 467, 468, 469
\renewcommand	492
\repeat	492
\RequirePackage	492
\RestoreCatcodes	492
\Result	492
554, 570, 571, 600,	492
606, 654, 655, 657, 659, 662,	492
664, 692, 693, 695, 697, 700, 702	492
S	
\saved@endqtest	524, 531
T	
\tag	8, 37, 39, 40, 42, 44
\Test	465, 483, 550, 573, 574, 575,
576, 577, 578, 579, 580, 581,	582, 583, 584, 585, 586, 588,
589, 590, 591, 592, 602, 605,	590, 591, 592, 602, 605,
609, 611, 614, 616, 617, 618,	609, 611, 614, 616, 617, 618,
619, 620, 621, 622, 623, 624,	619, 620, 621, 622, 623, 624,
625, 626, 627, 628, 629, 630,	625, 626, 627, 628, 629, 630,
631, 632, 633, 634, 635, 636,	631, 632, 633, 634, 635, 636,
637, 638, 661, 666, 667, 668,	637, 638, 661, 666, 667, 668,
669, 670, 671, 672, 673, 674,	669, 670, 671, 672, 673, 674,
675, 676, 677, 678, 679, 680,	675, 676, 677, 678, 679, 680,
681, 682, 683, 684, 685, 699,	681, 682, 683, 684, 685, 699,
705, 706, 707, 708, 709, 710,	705, 706, 707, 708, 709, 710,
711, 712, 713, 714, 715, 716, 717	711, 712, 713, 714, 715, 716, 717
\TestSet	587, 594
\TestTime	506, 519, 520, 521
\textgreater	16
\textless	16
\texttt	15
\the	16, 24, 113,
114, 115, 116, 127, 172, 190,	114, 115, 116, 127, 172, 190,
201, 211, 214, 222, 223, 230,	201, 211, 214, 222, 223, 230,
234, 235, 242, 246, 247, 253,	234, 235, 242, 246, 247, 253,
262, 265, 274, 283, 284, 291,	262, 265, 274, 283, 284, 291,
295, 296, 303, 336, 451, 554,	295, 296, 303, 336, 451, 554,
645, 647, 650, 655, 657, 693, 695	645, 647, 650, 655, 657, 693, 695
\TimeDescription	514, 517, 521
\TMP@EnsureCode	124, 131, 132, 133,
134, 135, 136, 137, 138, 139, 140	134, 135, 136, 137, 138, 139, 140
\toks@	12, 16, 23, 24, 171, 172, 182,
190, 196, 201, 210, 211, 214,	190, 196, 201, 210, 211, 214,
222, 223, 227, 229, 230, 234,	222, 223, 227, 229, 230, 234,
235, 239, 241, 242, 246, 247,	235, 239, 241, 242, 246, 247,
250, 253, 261, 262, 265, 272,	250, 253, 261, 262, 265, 272,
274, 283, 284, 288, 290, 291,	274, 283, 284, 288, 290, 291,
295, 296, 300, 302, 303, 335,	295, 296, 300, 302, 303, 335,
336, 553, 554, 644, 645, 647,	336, 553, 554, 644, 645, 647,
650, 653, 655, 657, 691, 693, 695	650, 653, 655, 657, 691, 693, 695
\tracingmacros	704
\typeout	509
U	
\UNDEFINED	492
\unexpanded	491, 492, 497
\unless	360, 363, 373
\usepackage	3, 4, 5, 496, 498
V	
\Value	648, 650, 651, 655, 657
W	
\write	70, 94

	X		Z	
\x	55, 57, 59, 69, 73, 75, 93, 98, 105, 111, 119, 645	\z@	507