

The `letltxmacro` package

Heiko Oberdiek

<oberdiek@uni-freiburg.de>

2008/06/12 v1.1

Abstract

`TEX`'s `\let` assignment does not work for `LATEX` macros with optional arguments or for macros that are defined as robust macros by `\DeclareRobustCommand`. This package defines `\LetLtxMacro` that also takes care of the involved internal macros.

Contents

1 Documentation	1
1.1 Supported macro definition commands	2
2 Implementation	2
2.1 Show cases	2
2.1.1 <code>letltxmacro-showcases.tex</code>	2
2.1.2 Result	3
2.2 Package	4
2.2.1 Catcodes and identification	4
2.2.2 Main macros	4
3 Test	6
3.1 Catcode checks for loading	6
3.2 Package tests	7
4 Installation	9
4.1 Download	9
4.2 Bundle installation	9
4.3 Package installation	10
4.4 Refresh file name databases	10
4.5 Some details for the interested	10
5 History	11
[2008/06/09 v1.0]	11
[2008/06/12 v1.1]	11
6 Index	11

1 Documentation

If someone wants to redefine a macro with using the old meaning, then one method is `TEX`'s command `\let`:

```
\newcommand{\Macro}{\typeout{Test Macro}}
\let\SavedMacro=\Macro
\renewcommand{\Macro}{%
  \typeout{Begin}%
}
```

```

  \SavedMacro
  \typeout{End}%
}

```

However, this method fails, if `\Macro` is defined by `\DeclareRobustCommand` and/or has an optional argument. In both cases L^AT_EX defines an additional internal macro that is forgotten in the simple `\let` assignment of the example above.

```
\LetLtxMacro {\langle new macro\rangle} {\langle old macro\rangle}
```

Macro `\LetLtxMacro` behaves similar to T_EX's `\let` assignment, but it takes care of macros that are defined by `\DeclareRobustCommand` and/or have optional arguments. Example:

```

\DeclareRobustCommand{\Macro}[1][default]{...}
\LetLtxMacro{\SavedMacro}{\Macro}

```

Then macro `\SavedMacro` only uses internal macro names that are derived from `\SavedMacro`'s macro name. Macro `\Macro` can now be redefined without affecting `\SavedMacro`.

1.1 Supported macro definition commands

<code>\newcommand</code> , <code>\renewcommand</code>	latex/base
<code>\newenvironment</code> , <code>\renewenvironment</code>	latex/base
<code>\DeclareRobustCommand</code>	latex/base
<code>\newrobustcmd</code> , <code>\renewrobustcmd</code>	etoolbox

2 Implementation

2.1 Show cases

2.1.1 letltxmacro-showcases.tex

```

1 {*showcases}
2 \NeedsTeXFormat{LaTeX2e}
3 \makeatletter

```

`\Line` The result is displayed by macro `\Line`. The percent symbol at line start allows easy grepping and inserting into the DTX file.

```

4 \newcommand*{\Line}[1]{%
5   \typeout{@percentchar#1}%
6 }

7 \newcommand*{\ShowCmdName}[1]{%
8   \@ifundefined{#1}{}{%
9     \Line{%
10       \space\space(\expandafter\string\csname#1\endcsname) = %
11       (\expandafter\meaning\csname#1\endcsname)}%
12   }%
13 }%
14 }
15 \newcommand*{\ShowCmds}[1]{%
16   \ShowCmdName{#1}%
17   \ShowCmdName{#1 }%
18   \ShowCmdName{\#1}%
19   \ShowCmdName{\#1 }%
20 }
21 \let\\@backslashchar

```

```

\ShowDef

22 \newcommand*{\ShowDef}[2]{%
23   \begingroup
24     \Line{%
25       \newcommand*{\DefString}{#2}%
26       \Onelevel@sanitize\DefString
27       \Line{\DefString}%
28       #2%
29       \ShowCmbs{#1}%
30     }\endgroup
31 }

32 \typeout{}
33 \Line{* LaTeX definitions:}
34 \ShowDef{cmd}{%
35   \newcommand{\cmd}[2][default]{}%
36 }
37 \ShowDef{cmd}{%
38   \DeclareRobustCommand{\cmd}{}%
39 }
40 \ShowDef{cmd}{%
41   \DeclareRobustCommand{\cmd}[2][default]{}%
42 }
43 \typeout{}
44 \RequirePackage{etoolbox}\relax
45 \Line{* etoolbox's robust definitions:}
46 \ShowDef{cmd}{%
47   \newrobustcmd{\cmd}{}%
48 }
49 \ShowDef{cmd}{%
50   \newrobustcmd{\cmd}[2][default]{}%
51 }
52 }

53 \typeout{}
54 \@@end
55 (/showcases)

```

2.1.2 Result

* LaTeX definitions:

```

\newcommand {\cmd }[2][default]{}
  (\cmd ) = (macro:->\@protected@testopt \cmd \\cmd {default})
  (\cmd ) = (\long macro:[#1]\#2->)

\DeclareRobustCommand {\cmd }{%
  (\cmd ) = (macro:->\protect \cmd_ )
  (\cmd_ ) = (\long macro:->)

\DeclareRobustCommand {\cmd }[2][default]{}
  (\cmd ) = (macro:->\protect \cmd_ )
  (\cmd_ ) = (macro:->\@protected@testopt \cmd_ \\cmd_ {default})
  (\cmd_ ) = (\long macro:[#1]\#2->)

```

* etoolbox's robust definitions:

```

\newrobustcmd {\cmd }{%
  (\cmd ) = (\protected\long macro:->)

\newrobustcmd {\cmd }[2][default]{}
  (\cmd ) = (\protected macro:->\@testopt \\cmd {default})
  (\cmd ) = (\protected\long macro:[#1]\#2->)

```

2.2 Package

56 ⟨*package⟩

2.2.1 Catcodes and identification

```
57 \begingroup
58   \catcode123 1 % {
59   \catcode125 2 % }
60   \def\x{\endgroup
61     \expandafter\edef\csname l1m@AtEnd\endcsname{%
62       \catcode35 \the\catcode35\relax
63       \catcode64 \the\catcode64\relax
64       \catcode123 \the\catcode123\relax
65       \catcode125 \the\catcode125\relax
66     }%
67   }%
68 \x
69 \catcode35 6 % #
70 \catcode64 11 % @
71 \catcode123 1 % {
72 \catcode125 2 % }
73 \def\TMP@EnsureCode#1#2{%
74   \edef\l1m@AtEnd{%
75     \l1m@AtEnd
76     \catcode#1 \the\catcode#1\relax
77   }%
78   \catcode#1 #2\relax
79 }
80 \TMP@EnsureCode{40}{12}%
81 \TMP@EnsureCode{41}{12}%
82 \TMP@EnsureCode{42}{12}%
83 \TMP@EnsureCode{45}{12}%
84 \TMP@EnsureCode{46}{12}%
85 \TMP@EnsureCode{47}{12}%
86 \TMP@EnsureCode{58}{12}%
87 \TMP@EnsureCode{61}{12}%
88 \TMP@EnsureCode{62}{12}%
89 \edef\l1m@AtEnd{%
90   \l1m@AtEnd
91   \escapechar\the\escapechar\relax
92 }
93 \escapechar=92 % ' \\
94 Package identification.
95 \NeedsTeXFormat{LaTeX2e}
96 \ProvidesPackage{letltmacro}%
97 [2008/06/12 v1.1 Let assignment for LaTeX macros (HO)]
```

2.2.2 Main macros

\LetLtxMacro

```
97 \newcommand*{\LetLtxMacro}[2]{%
98   \edef\reserved@a{%
99     \noexpand\protect
100    \expandafter\noexpand
101      \csname\expandafter\@gobble\string#2\endcsname
102    }%
103   \ifx\reserved@a\relax
104     \edef#1{%
105       \noexpand\protect
106       \expandafter\noexpand
107         \csname\expandafter\@gobble\string#1\endcsname
108     }%
109   \expandafter\let
```

```

110      \csname\expandafter\@gobble\string#1 \expandafter\endcsname
111      \csname\expandafter\@gobble\string#2 \endcsname
112      \expandafter\llm@LetLtxMacro
113          \csname\expandafter\@gobble\string#1 \expandafter\endcsname
114          \csname\expandafter\@gobble\string#2 \endcsname
115  \else
116      \llm@LetLtxMacro{#1}{#2}%
117  \fi
118 }

\llm@LetLtxMacro
119 \def\llm@LetLtxMacro#1#2{%
120   \expandafter\llm@CheckParams\meaning#2:->\@nil{%
121     \begingroup
122       \ifx\llm@protected\@empty
123         \edef\x{%
124           \noexpand\@protected@testopt
125           \noexpand#2%
126           \expandafter\noexpand\csname\string#2\endcsname
127         }%
128         \expandafter\expandafter\expandafter\def
129         \expandafter\expandafter\expandafter\y
130         \expandafter\expandafter\expandafter{%
131           \expandafter\llm@CarThree#2{}{}{}\llm@nil
132         }%
133     \else
134       \edef\x{%
135         \noexpand\@testopt
136         \expandafter\noexpand\csname\string#2\endcsname
137       }%
138       \expandafter\expandafter\expandafter\def
139       \expandafter\expandafter\expandafter\y
140       \expandafter\expandafter\expandafter{%
141         \expandafter\llm@CarTwo#2{}{}{}\llm@nil
142       }%
143     \fi
144   \expandafter\endgroup\ifx\x\y
145     \begingroup
146       \def\@protected@testopt##1##2##3{%
147         \toks@={##3}%
148         \xdef\llm@GlobalTemp{%
149           \noexpand\@protected@testopt
150           \noexpand#1%
151           \expandafter\noexpand\csname\string#1\endcsname
152           {\the\toks@}%
153         }%
154       }%
155       \def\@testopt##1##2{%
156         \toks@={##2}%
157         \protected\xdef\llm@GlobalTemp{%
158           \noexpand\@testopt
159           \expandafter\noexpand\csname\string#1\endcsname
160           {\the\toks@}%
161         }%
162       }%
163       #2%
164     \endgroup
165     \let#1=\llm@GlobalTemp
166     \expandafter\let\csname\string#1\expandafter\endcsname
167             \csname\string#2\endcsname
168   \else
169     \let#1=#2\relax
170   \fi

```

```

171  }{%
172   \let#1=#2\relax
173  }%
174 }

\llm@CheckParams

175 \def\llm@CheckParams#1:->#2@nil{%
176   \begingroup
177   \def\x{\#1}%
178   \ifx\x\llm@macro
179   \endgroup
180   \def\llm@protected{}%
181   \expandafter\@firstoftwo
182 \else
183   \ifx\x\llm@protectedmacro
184   \endgroup
185   \def\llm@protected{\protected}%
186   \expandafter\expandafter\expandafter\@firstoftwo
187 \else
188   \endgroup
189   \expandafter\expandafter\expandafter\expandafter\@secondoftwo
190 \fi
191 \fi
192 }

\llm@macro

193 \def\llm@macro{macro}
194 \@onelvel@sanitize\llm@macro

\llm@protectedmacro

195 \def\llm@protectedmacro{\protected macro}
196 \@onelvel@sanitize\llm@protectedmacro

\llm@CarThree

197 \def\llm@CarThree#1#2#3#4\llm@nil{#1#2#3}%

\llm@CarTwo

198 \def\llm@CarTwo#1#2#3\llm@nil{#1#2}%

199 \llm@AtEnd
200 </package>

```

3 Test

3.1 Catcode checks for loading

```

201 <*test1>
202 \NeedsTeXFormat{LaTeX2e}
203 \documentclass{minimal}
204 \makeatletter
205 \def\RestoreCatcodes{}
206 \count@=0 %
207 \loop
208   \edef\RestoreCatcodes{%
209     \RestoreCatcodes
210     \catcode`\the\count@=\the\catcode\count@\relax
211   }%
212 \ifnum\count@<255 %
213   \advance\count@\@ne
214 \repeat

```

```

215
216 \def\RangeCatcodeInvalid#1#2{%
217   \count@=#1\relax
218   \loop
219     \catcode\count@=15 %
220   \ifnum\count@<#2\relax
221     \advance\count@\@ne
222   \repeat
223 }
224 \def\Test{%
225   \RangeCatcodeInvalid{0}{47}%
226   \RangeCatcodeInvalid{58}{64}%
227   \RangeCatcodeInvalid{91}{96}%
228   \RangeCatcodeInvalid{123}{127}%
229   \catcode`\@=12 %
230   \catcode`\\"=0 %
231   \catcode`\{=1 %
232   \catcode`\}=2 %
233   \catcode`\#=6 %
234   \catcode`\[=12 %
235   \catcode`\]=12 %
236   \catcode`\%=14 %
237   \catcode`\ =10 %
238   \catcode13=5 %
239   \RequirePackage{letltxmacro}[2008/06/12]\relax
240   \RestoreCatcodes
241 }
242 \Test
243 \csname @@end\endcsname
244 \end
245 
```

3.2 Package tests

```

246 <*test2>
247 \NeedsTeXFormat{LaTeX2e}
248 \nofiles
249 \documentclass{minimal}
250
251 \usepackage{letltxmacro}[2008/06/12]
252
253 \usepackage{qstest}
254 \IncludeTests{*}
255 \LogTests{log}{*}{*}
256
257 \makeatletter
258
259 \def\TestDef#1{%
260   \begingroup
261     \makeother\\%
262     \makeother\ %
263     \expandafter\@TestDef\csname #1\endcsname
264 }
265 \def\@TestDef#1#2{%
266   \edef\@a{\expandafter\strip@prefix\meaning#1}%
267   \edef\@b{\detokenize{#2}}%
268   \ifx\@a\@b
269     \else
270       \typeout{1 [\@a]}%
271       \typeout{2 [\@b]}%
272     \fi
273   \endgroup
274   \Expect*\expandafter\strip@prefix\meaning#1*{\detokenize{#2}}%

```

```

275 }
276 \def\TestEquals#1#2{%
277   \Expect*{%
278     \expandafter\ifx\csname#1\expandafter\endcsname
279       \csname#2\endcsname
280     equals%
281   \else
282     wrong%
283   \fi
284 }{equals}%
285 }
286 \def\SaveA{%
287   \let\SavedA\TestA
288   \expandafter\let\csname string\SavedA\expandafter\endcsname
289     \csname string\TestA\endcsname
290   \expandafter\let\csname SavedA \expandafter\endcsname
291     \csname TestA \endcsname
292 }
293 \def\CheckA{%
294   \TestEquals{SavedA}{TestA}%
295   \TestEquals{\string\SavedA}{\string\TestA}%
296   \TestEquals{SavedA }{TestA }%
297 }
298
299 \begin{qstest}{robust}{robust}
300   \DeclareRobustCommand*\{\TestA\}{\Test}%
301   \SaveA
302   \TestDef{\TestA}{\protect \TestA }%
303   \CheckA
304   \DeclareRobustCommand{\TestA}{\Test}%
305   \SaveA
306   \TestDef{\TestA}{\protect \TestA }%
307   \LetLtxMacro{\TestB}{\TestA}
308   \TestDef{\TestB}{\protect \TestB }%
309   \TestEquals{\TestB }{\TestA }%
310   \CheckA
311 \end{qstest}
312
313 \begin{qstest}{default}{default}
314   \newcommand{\TestA}[1][\relax default \empty]{\TestA #1}%
315   \SaveA
316   \TestDef
317   {\TestA}{\@protected@testopt \TestA \\ \TestA {\relax default \empty}}%
318   \LetLtxMacro{\TestB}{\TestA}
319   \TestDef
320   {\TestB}{\@protected@testopt \TestB \\ \TestB {\relax default \empty}}%
321   \CheckA
322 \end{qstest}
323
324 \begin{qstest}{robustdefault}{robustdefault}
325   \DeclareRobustCommand{\TestA}[1][\default]{\TestA}%
326   \SaveA
327   \LetLtxMacro{\TestB}{\TestA}
328   \TestDef{\TestB}{\protect \TestB }%
329   \TestDef{\TestB }{\@protected@testopt \TestB \\ \TestB {\default}}%
330   \CheckA
331 \end{qstest}
332
333 \begin{qstest}{plain}{plain}
334   \LetLtxMacro{\NewRelax}{\relax}
335   \Expect*{\meaning\relax}{\string\relax}%
336   \Expect*{\meaning\NewRelax}{\string\relax}%

```

```

337  \LetLtxMacro{\NewHbox}{\hbox}
338  \Expect*{\meaning{\hbox}}*\{\string{\hbox}\}%
339  \Expect*{\meaning{\NewHbox}}*\{\string{\hbox}\}%
340  \LetLtxMacro{\NewEmpty}{\empty}
341  \Expect*{\meaning{\empty}}{\macro:->}%
342  \Expect*{\meaning{\NewEmpty}}{\macro:->}%
343 \end{qstest}

344 \usepackage{etoolbox}
345
346 \begin{qstest}{newrobustcmd}{newrobustcmd}
347   \newrobustcmd{\TestA}[1][\default]{\TestA}%
348   \SaveA
349   \LetLtxMacro{\TestB}{\TestA}
350   \TestDef{\TestB}{\@testopt \\ \TestB {\default}}%
351   \protected\edef{\TestC}{%
352     \noexpand\@testopt
353     \expandafter\noexpand\csname\string\TestB\endcsname
354     {\noexpand\default}}%
355   }%
356   \TestEqual{\TestB}{\TestC}%
357   \CheckA
358 \end{qstest}

359 \csname @@end\endcsname
360 
```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

CTAN:macros/latex/contrib/oberdiek/letltxmacro.dtx The source file.

CTAN:macros/latex/contrib/oberdiek/letltxmacro.pdf Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

CTAN:install/macros/latex/contrib/oberdiek.tds.zip

TDS refers to the standard “A Directory Structure for TEX Files” (CTAN:tds/tds.pdf). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDSScripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdflatfi.pl` that should be installed in such a way that it can be called as `pdflatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdflatfi.pl
cp scripts/oberdiek/pdflatfi.pl /usr/local/bin/
```

¹[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain-**TEX**:

```
tex letltxmacro.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
letltxmacro.sty          → tex/latex/oberdiek/letltxmacro.sty  
letltxmacro.pdf         → doc/latex/oberdiek/letltxmacro.pdf  
letltxmacro-showcases.tex → doc/latex/oberdiek/letltxmacro-showcases.tex  
test/letltxmacro-test1.tex → doc/latex/oberdiek/test/letltxmacro-test1.tex  
test/letltxmacro-test2.tex → doc/latex/oberdiek/test/letltxmacro-test2.tex  
letltxmacro.dtx          → source/latex/oberdiek/letltxmacro.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your **TEX** distribution (`teTEX`, `mikTEX`, ...) relies on file name databases, you must refresh these. For example, `teTEX` users run `texhash` or `mktexlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk letltxmacro.pdf unpack_files output .
```

Unpacking with LATEX. The `.dtx` chooses its action depending on the format:

plain-TEX: Run `docstrip` and extract the files.

LATEX: Generate the documentation.

If you insist on using LATEX for `docstrip` (really, `docstrip` does not need LATEX), then inform the autodetect routine about your intention:

```
\latex \let\install=y\input{letltxmacro.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdfLATEX`:

```
pdflatex letltxmacro.dtx  
makeindex -s gind.ist letltxmacro.idx  
pdflatex letltxmacro.dtx  
makeindex -s gind.ist letltxmacro.idx  
pdflatex letltxmacro.dtx
```

5 History

[2008/06/09 v1.0]

- First version.

[2008/06/12 v1.1]

- Support for etoolbox's \newrobustcmd added.

6 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\#	233
\%	236
\@	229
\@end	54
\@TestDef	263, 265
\@backslashchar	21
\@empty	122
\@firstoftwo	181, 186
\@gobble	101, 107, 110, 111, 113, 114
\@ifundefined	8
\@makeother	261, 262
\@ne	213, 221
\@nil	120, 175
\@onlevel@sanitize	26, 194, 196
\@percentchar	5
\@protected@testopt	124, 146, 149, 317, 320, 329
\@secondoftwo	189
\@testopt	135, 155, 158, 350, 352
\[.	234
\\"	18, 19, 21, 93, 230, 261, 317, 320, 329, 350
\{	231
\}	232
\]	235
_	237, 262
A	
\a	266, 268, 270
\advance	213, 221
B	
\b	267, 268, 271
\begin{	299, 313, 324, 333, 346
C	
\catcode	58, 59, 62, 63, 64, 65, 69, 70, 71, 72, 76, 78, 210, 219, 229, 230, 231, 232, 233, 234, 235, 236, 237, 238
\CheckA	293, 303, 310, 321, 330, 357
\cmd	35, 38, 41, 48, 51
D	
\count@	206, 210, 212, 213, 217, 219, 220, 221
\csname	10, 11, 61, 101, 107, 110, 111, 113, 114, 126, 136, 151, 159, 166, 167, 243, 263, 278, 279, 288, 289, 290, 291, 353, 359
\DeclareRobustCommand	38, 41, 300, 304, 325
\default	325, 329, 347, 350, 354
\DefString	25, 26, 27
\detokenize	267, 274
\documentclass	203, 249
E	
\empty	314, 317, 320, 340, 341
\end	244, 311, 322, 331, 343, 358
\endcsname	10, 11, 61, 101, 107, 110, 111, 113, 114, 126, 136, 151, 159, 166, 167, 243, 263, 278, 279, 288, 289, 290, 291, 353, 359
\escapechar	91, 93
\Expect	274, 277, 335, 336, 338, 339, 341, 342
H	
\hbox	337, 338, 339
I	
\ifnum	212, 220
\ifx	103, 122, 144, 178, 183, 268, 278
\IncludeTests	254
L	
\LetLtxMacro	2, 97, 307, 318, 327, 334, 337, 340, 349
\Line	4, 9, 24, 27, 33, 45, 46
\l@rm@AtEnd	74, 75, 89, 90, 199
\l@rm@CarThree	131, 197
\l@rm@CarTwo	141, 198
\l@rm@CheckParams	120, 175
\l@rm@GlobalTemp	148, 157, 165
\l@rm@LetLtxMacro	112, 116, 119
\l@rm@macro	178, 193
\l@rm@nil	131, 141, 197, 198

\llm@protected	122, 180, 185	\SavedA	287, 288, 295
\llm@protectedmacro	183, 195	\ShowCmdName	7, 16, 17, 18, 19
\LogTests	255	\ShowCmds	15, 29
\loop	207, 218	\ShowDef	<u>22</u> , 34, 37, 40, 47, 50
M			
\makeatletter	3, 204, 257	\space	10
\meaning	11, 120, 266,	\strip@prefix	266, 274
274, 335, 336, 338, 339, 341, 342		T	
N			
\NeedsTeXFormat	2, 94, 202, 247	\Test	224, 242
\newcommand	4, 7, 15, 22, 25, 35, 97, 314	\TestA	287, 289,
\NewEmpty	340, 342	295, 300, 302, 304, 306, 307,	
\NewHbox	337, 339	314, 317, 318, 325, 327, 347, 349	
\NewRelax	334, 336	\TestB	307, 308,
\newrobustcmd	48, 51, 347	318, 320, 327, 328, 329, 349, 353	
\nofiles	248	\TestC	351
P		\TestDef	259, 302,
\protect ...	99, 105, 302, 306, 308, 328	306, 308, 316, 319, 328, 329, 350	
\protected	157, 185, 195, 351	\TestEquals	276, 294, 295, 296, 309, 356
\ProvidesPackage	95	\the	62, 63, 64, 65, 76, 91, 152, 160, 210
R		\TMP@EnsureCode	73,
\RangeCatcodeInvalid	216, 225, 226, 227, 228	80, 81, 82, 83, 84, 85, 86, 87, 88	
\repeat	214, 222	\toks@	147, 152, 156, 160
\RequirePackage	44, 239	\typeout	5, 32, 43, 53, 270, 271
\reserved@a	98, 103	U	
\RestoreCatcodes	205, 208, 209, 240	\usepackage	251, 253, 344
S			
\SaveA	286, 301, 305, 315, 326, 348	X	
Y			
\y	129, 139, 144		